

Oracle® Revenue Management and Billing

Version 2.5.0.0.0

Database Administrator's Guide

Revision 7.1

E67618-01

October, 2015

ORACLE®

Oracle Revenue Management and Billing Database Administrator's Guide

E67618-01

Copyright Notice

Copyright © 2015, Oracle and/or its affiliates. All rights reserved.

Trademark Notice

Oracle, Java, JD Edwards, PeopleSoft, and Siebel are registered trademarks of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

License Restrictions Warranty/Consequential Damages Disclaimer

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure, and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or de-compilation of this software, unless required by law for interoperability, is prohibited.

Warranty Disclaimer

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

Restricted Rights Notice

If this software or related documentation is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, the following notice is applicable:

U.S. GOVERNMENT RIGHTS

Oracle programs, including any operating system, integrated software, any programs installed on the hardware, documentation, and/or technical data delivered to U.S. Government end users are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, documentation, and/or technical data shall be subject to license terms and restrictions as mentioned in Oracle License Agreement, and to the extent applicable, the additional rights set forth in FAR 52.227-19, Commercial Computer Software--Restricted Rights (June 1987). No other rights are granted to the U.S. Government.

Hazardous Applications Notice

This software is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure the safe use of this software. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software in dangerous applications.

Third Party Content, Products, and Services Disclaimer

This software and documentation may provide access to or information on content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third party content, products, or services.

Preface

About This Document

This document will help you to understand how to install and maintain the Oracle Revenue Management and Billing (ORMB) database.

Intended Audience

This document is intended for the following audience:

- End-Users
- Database Administrators
- Consulting Team
- Implementation Team

Organization of the Document

The information in this document is organized into the following sections:

Section No.	Section Name	Description
Section 1	Database Overview	Lists the database server supported on each platform. It also lists the dos and don'ts while maintaining a database.
Section 2	Database Installation	Explains how to install the Oracle Revenue Management and Billing database.
Section 3	Database Design	Lists the naming conventions for various database objects. It also lists and describes the column data types and foreign key constraints.
Section 4	Exadata Database Settings	Lists a set of activities that you need to perform if you are using the Oracle Exadata Database machine as the database server.
Section 5	Database Implementation Guidelines	Lists and describes the general guidelines for configuring various objects in the database and implementing Oracle Database.
Appendix A	New Objects in the Oracle Revenue Management and Billing V2.5.0.0.0 Database	Lists the objects that are newly added in the Oracle Revenue Management and Billing V2.5.0.0.0 database.

Section No.	Section Name	Description
Appendix B	New Objects in the Oracle Utilities Application Framework V4.3.0.0.1 Database	Lists the objects that are newly added in the Oracle Utilities Application Framework V4.3.0.0.1 database.
Appendix C	Oracle Application Framework System Table Guide	Lists and describes the system tables of Oracle Utilities Application Framework. It also explains the guidelines for updating these system tables.
Appendix D	License and Copyright Notices	Lists all notices with reference to usage of third party products.

Related Documents

You can refer to the following documents for more information:

Document	Description
<i>Oracle Revenue Management and Billing Version 2.5.0.0.0 Release Notes</i>	Provides a brief description about the new features, enhancements, UI and database level changes, supported platforms, framework upgrade, supported upgrades, and technology upgrade made in this release. It also highlights the discontinued features, bug fixes, and known issues in this release.
<i>Oracle Revenue Management and Billing Installation Guide</i>	Lists the application server pre-requisites, supported platforms, and software and hardware requirements for installing the Oracle Revenue Management and Billing application. It explains how to install the Oracle Revenue Management and Billing application.
<i>Oracle Revenue Management and Billing Quick Installation Guide</i>	Provides high-level information on how to install the Oracle Revenue Management and Billing (ORMB) application and selected additional software.
<i>Oracle Revenue Management and Billing Server Administration Guide</i>	Explains the Oracle Revenue Management and Billing (ORMB) architecture and technical know-how required for configuring and using the ORMB application. It explains how to configure and deploy web and business application servers. In addition, it explains how to monitor client machines, web and/or business application servers, and database connections.
<i>Oracle Revenue Management and Billing Security Guide</i>	Lists the security features available in the Oracle Revenue Management and Billing application. It explains how to configure security for the Oracle Revenue Management and Billing application using the default security features.

Change Log

Revision	Last Update	Updated Section	Comments
7.1	30-June-2016	Section 5.1.11: Shrink Tables	Added Information

Contents

1. Database Overview.....	1
1.1 Supported Database Platforms	1
1.1.1 Supported Platforms Summary Table.....	1
1.1.2 Support for Software Patches and Upgrades	2
1.2 Database Maintenance Rules.....	2
1.2.1 Permitted Database Changes.....	2
1.2.2 Non-Permitted Database Changes.....	3
2. Installing Oracle Revenue Management and Billing Version 2.5.0.0.0 Database	4
2.1 Installation Overview.....	4
2.2 Creating the Database	4
2.3 Oracle Database Installation	6
2.3.1 Initial Install, or Installing Version 2.5.0.0.0 for the First Time	6
2.3.2 Demo Install	16
3. Database Design	23
3.1 Database Object Standard.....	23
3.1.1 Categories of Data.....	23
3.1.2 Naming Standards.....	23
3.2 Column Data Type and Constraints	27
3.2.1 User Defined Code	27
3.2.2 System Assigned Identifier.....	27
3.2.3 Date/Time/Timestamp.....	27
3.2.4 Number	27
3.2.5 Fixed Length/Variable Length Character Columns	27
3.2.6 Null Column Support.....	28
3.2.7 XML Type Support.....	28
3.2.8 Cache and Key Validation Flags.....	28
3.2.9 Table Classification and Table Volume Flags	28
3.2.10 Default Value Setting.....	29
3.2.11 Foreign Key Constraints.....	29
3.3 Standard Columns	29
3.3.1 Owner Flag	29
3.3.2 Version	29
4. Exadata Database Settings	30
5. Database Implementation Guidelines	31
5.1 Configuration Guidelines.....	31
5.1.1 Index.....	31

5.1.2	Temporary and Undo Tablespace	31
5.1.3	Transparent Data Encryption Recommendations.....	32
5.1.4	Data Compression Recommendations.....	32
5.1.5	Database Vault Recommendations.....	33
5.1.6	Oracle Fuzzy Search Support	33
5.1.7	Storage Recommendations.....	34
5.1.8	Database Configuration Recommendations.....	35
5.1.9	Database Syntax.....	35
5.1.10	Database Initialization Parameters	35
5.1.11	Shrink Tables	37
5.2	Oracle Database Implementation Guidelines	38
5.2.1	Oracle Partitioning	38
5.2.2	Database Statistic.....	38
5.2.3	Materialized View	39
Appendix A :	New Objects in the Oracle Revenue Management and Billing V2.5.0.0.0 Database	40
A.1	Schema Changes.....	40
A.1.1	New Tables.....	40
A.1.2	Added Columns.....	42
A.1.3	Dropped Tables.....	43
A.1.4	Dropped Columns	43
A.1.5	Column Format Change	43
A.2	New System Data	50
A.2.1	Algorithm Type.....	50
A.2.2	Algorithm	51
A.2.3	Business Service	53
A.2.4	Application Service.....	54
A.2.5	Batch Control	55
A.2.6	Foreign Key Reference	55
A.2.7	Maintenance Object	55
A.2.8	Business Object.....	56
A.2.9	Script	56
A.2.10	To Do Type	58
A.2.11	Portal	58
A.2.12	Zone.....	59
A.2.13	UI Map.....	62
A.2.14	Lookup.....	64
Appendix B :	New Objects in the Oracle Utilities Application Framework V4.3.0.0.1 Database.....	67
B.1	Schema Changes.....	67
B.1.1	New Tables.....	67

B.1.2	New Views.....	67
B.1.3	Dropped Tables.....	67
B.1.4	Unsupported Tables.....	67
B.1.5	Added Columns.....	68
B.1.6	Dropped Columns	68
B.1.7	Unsupported Table Columns	68
B.1.8	Column Format Change	68
B.2	New System Data	70
B.2.1	Algorithm Type.....	70
B.2.2	Algorithm	70
B.2.3	Application Service.....	70
B.2.4	Access Mode Added to Application Service.....	71
B.2.5	Batch Control	71
B.2.6	Business Object.....	71
B.2.7	FK Reference	72
B.2.8	Lookups.....	72
B.2.9	Maintenance Object	73
B.2.10	Script.....	73
B.2.11	To Do Type.....	73
B.2.12	Portal	73
B.2.13	Portal Zone	73
B.2.14	UI Map.....	73
B.2.15	XAI Inbound Service	74
B.2.16	Zone Type	74
B.2.17	Zone.....	74
Appendix C	: Oracle Application Framework System Table Guide	75
C.1	About the Application Framework System Tables	75
C.2	System Table Standards	75
C.3	Guidelines for System Table Updates.....	76
C.3.1	Business Configuration Tables	76
C.3.2	Development and Implementation System Tables.....	78
C.3.3	Oracle Utilities Application Framework Only Tables	90
C.4	System Table List	90
Appendix D	: License and Copyright Notices.....	103
D.1	Third-Party Products.....	103
D.1.1	Notice Concerning Usage of ANTLR	103
D.1.2	Notice Concerning Usage of Apache Software	104
D.1.3	Notice Concerning Usage of ASM	108
D.1.4	Notice Concerning Usage of Concurrent	108

D.1.5	Notice Concerning Usage of DOM4J	108
D.1.6	Notice Concerning Usage of International Components for Unicode (ICU4J)	109
D.1.7	Notice Concerning Usage of Jaxen	110
D.1.8	Notice Concerning Usage of JCIP Annotations	110
D.1.9	Notice Concerning Usage of JQuery	114
D.1.10	Notice Concerning Usage of SLF4J	115
D.1.11	Notice Concerning Usage of Staxmate	115
D.1.12	Notice Concerning Usage of XMLPULL	116
D.1.13	Notice Concerning Usage of XStream	116
D.1.14	Notice Concerning Usage of YUI	117

1. Database Overview

This section provides an overview of the Oracle Revenue Management and Billing database, including:

- Supported Database Platforms
- Database Maintenance Rules

1.1 Supported Database Platforms

This section defines the platforms on which Oracle Revenue Management and Billing is verified to operate.

1.1.1 Supported Platforms Summary Table

Oracle Revenue Management and Billing (ORMB) is supported on the following platforms:

Platform	Database Server
AIX 7.1 TL1 (POWER 64-bit)	Oracle Database Server 12.1.0.2 (64-bit)
Oracle Linux 6.5 and 7.0 (64-bit)	Oracle Database Server 12.1.0.2 (64-bit)
Red Hat Enterprise Linux ¹ 6.5 and 7.0 (64-bit)	Oracle Database Server 12.1.0.2 (64-bit)
Windows Server 2012 R2 (64-bit)	Oracle Database Server 12.1.0.2 (64-bit)

Note:

Oracle Corporation distributes Oracle Linux with the following two kernels:

- **Red Hat Compatible Kernel** – This kernel is identical to the kernel shipped in Red Hat Enterprise Linux.
- **Unbreakable Enterprise Kernel** – This kernel is based on a later Linux 2.6-series kernel, with Oracle's own enhancements for OLTP, InfiniBand, SSD disk access, NUMA-optimizations, Reliable Datagram Sockets (RDS), async I/O, OCFS2, and networking.

Oracle claims that the Unbreakable Enterprise Kernel is compatible with Red Hat Enterprise Linux; and Oracle middleware and third-party Red Hat Enterprise Linux-certified applications can be installed and run unchanged on Unbreakable Enterprise Kernel. However, for users requiring strict compatibility with Red Hat or for users running kernel modules dependent on specific kernel versions, the Red Hat Compatible Kernel offers 100% compatibility with Red Hat Enterprise Linux.

The following Oracle Database Server Editions are supported:

- Oracle Database Enterprise Edition

Oracle Database Client 12.1.0.1 is required for Oracle Database Server 12.1.0.2.

¹ Oracle Revenue Management and Billing is tested and certified on Oracle Linux 6.5 and 7.0. Oracle Linux is 100% userspace-compatible with Red Hat Enterprise Linux, and therefore Oracle Revenue Management and Billing is supported on Red Hat Enterprise Linux.

Note: We strongly recommend you to install Oracle Revenue Management and Billing (ORMB) on Windows platform only for non-production activities, such as User Acceptance Testing (UAT), development setup, and so on.

1.1.2 Support for Software Patches and Upgrades

Due to the ongoing nature of software improvement, vendors will issue patches and service packs for the operating systems, application servers and database servers on top of specific versions that Oracle Revenue Management and Billing has been tested with.

If it is necessary to apply an upgrade, please do so in a test environment that is running on the same platform as your production environment prior to updating the Oracle Revenue Management and Billing production environment.

The exception from this rule is Hibernate Version 4.1 GA. This version should not be upgraded.

Always contact Oracle Support prior to applying vendor updates that do not guarantee backward compatibility.

1.2 Database Maintenance Rules

The database supplied with the product consists of the following elements:

- A set of users to administrate, execute and read the database schema provided.
- A set of database roles to implement security for each of the users provided.
- A tablespace and a schema containing the base database objects used by the product.

The installation of these components is outlined in the installation section of this document.

1.2.1 Permitted Database Changes

During and after installation of the product the following changes may be performed by the database administrator personnel on site:

- Users supplied by product may be changed according to the site standards.
- Database objects may be added to the schema according to database naming standards outlined later in this document.
- Database views and indexes may be created against base database objects. Please make sure to prefix new items with "CM" (for customer modification).
- Database storage attributes for base indexes and base tables may be changed according to site standards and hardware used.
- Tablespace names, attributes and locations may be changed according to site standards.
- Database topology (that is, base table/index to tablespace, tablespace to data file, data file to location) may be altered according to tuning and/or site standards.
- Database triggers may be created against base database objects unless they attempt to contravene base data integrity rules.
- Database initialization and parameter settings may be altered according to site standards unless otherwise advised by Oracle Support or outlined in this document.

1.2.2 Non-Permitted Database Changes

In order to maintain operability and upgradeability of the product, during and after the installation of the product, the following changes may not be performed by the database administration personnel on site:

- Base objects must not be removed or altered in the following ways:
 - Columns in base tables must not be altered in anyway (altered, removed or added).
 - Columns in Indexes must not be altered or removed.
 - Tables must not be renamed or removed.
 - Base views must not be renamed or removed.
 - Base Triggers and Sequences must not be renamed or removed.
 - Base indexes must not be altered or removed.

2. Installing Oracle Revenue Management and Billing Version 2.5.0.0 Database

This section provides the instructions for installing the Oracle Revenue Management and Billing database. This section includes the following topics:

- [Installation Overview](#)
- [Creating the Database](#)
- [Oracle Database Installation](#)

2.1 Installation Overview

Note: Refer to the [Supported Database Platforms](#) section for information about the supported platforms on which Oracle Revenue Management and Billing is verified to operate.

The following types of installation are available for Oracle Revenue Management and Billing:

- Initial Install — a database without demo data
- Demo Install — a database with demo data

The database installation requires Java Development Kit Version 6.0 Update 20 or later and Oracle Database Client 12.1.0.1 (32-bit) installed on the Windows 64-bit or 32-bit desktop where the install package is staged and run from.

2.2 Creating the Database

For an initial install or demo install, you will create an empty database on a UNIX or Windows database server on which you operate the production instance of Oracle Revenue Management and Billing.

To create the database:

1. Create the database using the Database Configuration Assistant (DBCA). Refer to the article *Master Note: Overview of Database Configuration Assistant (DBCA)* (Doc ID 1488770.1) on [My Oracle Support](#) for more information. Ensure that you set the database character set to AL32UTF8.

Note: In the prior versions of the product, the cdxdba utility (cdxdba.plx for UNIX and CDXDBA.exe for Windows) was included in the package. However, it is no longer supported from this release onwards. Instead of using the cdxdba utility, use the Database Configuration Assistant to create the database.

2. Enable the following mandatory software options:
 - Oracle Spatial OR Oracle Locator
 - Oracle Text
3. Execute the following SQL command to verify whether the above mandatory software options are enabled:

```
SELECT COMP_NAME, STATUS FROM DBA_REGISTRY WHERE COMP_NAME IN ('Spatial', 'Oracle Text');
```

4. Create default tablespace named CISTS using the following command:

```
CREATE TABLESPACE CISTS_01 LOGGING DATAFILE
'<db_file_location>/oradata/<DB_NAME>/cists01.dbf' SIZE 1024M
REUSE AUTOEXTEND ON NEXT 8192K MAXSIZE UNLIMITED EXTENT
MANAGEMENT LOCAL UNIFORM SIZE 1M;
```

5. Create the CIS_USER and CIS_READ roles using the following commands:

```
CREATE ROLE CIS_USER;
CREATE ROLE CIS_READ;
```

6. Create the CISADM, CISUSER, CISOPR, and CISREAD users using the following commands:

```
CREATE USER CISADM IDENTIFIED BY CISADM DEFAULT TABLESPACE
CISTS_01 TEMPORARY TABLESPACE TEMP PROFILE DEFAULT;
GRANT UNLIMITED TABLESPACE TO CISADM WITH ADMIN OPTION; GRANT
SELECT ANY TABLE TO CISADM;
GRANT CREATE DATABASE LINK TO CISADM; GRANT CONNECT TO CISADM;
GRANT RESOURCE TO CISADM;
GRANT DBA TO CISADM WITH ADMIN OPTION; GRANT CREATE ANY SYNONYM
TO CISADM; GRANT SELECT ANY DICTIONARY TO CISADM;
```

```
CREATE USER CISUSER PROFILE DEFAULT IDENTIFIED BY CISUSER DEFAULT
TABLESPACE CISTS_01 TEMPORARY TABLESPACE TEMP;
GRANT SELECT ANY TABLE TO CISUSER; GRANT CIS_USER TO CISUSER;
GRANT CIS_READ TO CISUSER; GRANT CONNECT TO CISUSER;
```

```
CREATE USER CISOPR PROFILE DEFAULT IDENTIFIED BY OPRPLUS DEFAULT
TABLESPACE CISTS_01 TEMPORARY TABLESPACE TEMP;
GRANT CONNECT,RESOURCE,EXP_FULL_DATABASE TO CISOPR;
```

```
CREATE USER CISREAD IDENTIFIED BY CISREAD DEFAULT TABLESPACE
CISTS_01 TEMPORARY TABLESPACE TEMP;
GRANT SELECT ANY TABLE TO CISREAD; GRANT CIS_READ TO CISREAD;
GRANT CONNECT TO CISREAD;
```

7. Review the Storage.xml file under the FW\FW43001\Install-Upgrade\ folder prior to initial install. This file allocates all base tables and indexes to the default tablespace (CISTS_01) and the required users and roles. Information in this file is used by ORADBI while installing the Oracle Revenue Management and Billing database objects. Refer to the [Updating Storage.xml](#) section for more information on how to update the Storage.xml file.

Note: You will need to review the Storage.xml file, prior to an initial install, to update the default values to custom values (for example, TableSpace Name). OraDBI can be executed by a non-schema owner in order to upgrade the database. The Initial Install still needs to be done by the schema owner.

If you decide to allocate some tables or indexes outside of the default tablespace, change the tablespace name from the default value to a custom value in the `Storage.xml` file.

For instance, if you decide to allocate table `CI_ACCT` in a tablespace `MyTablespace`, change `Storage.xml` as shown:

```
<CI_ACCT>
<TABLESPACE>MyTablespace</TABLESPACE>
</CI_ACCT>
```

For optimum storage allocation, database administrators should create multiple tablespaces with extents sized to store different types of tables/indexes. They can then edit the `storage.xml` file before install process, to spread tables and indexes across these tablespaces. Tables and indexes can be created in parallel by editing degree of parallelism. Tablespace, storage options, secure file options, Advanced Compression, and parallel information are used only for new objects. Therefore, for initial installs, information for each object should be reviewed. Be careful while editing this file. Make sure that tablespace names being used exist in the database. Do not change the basic format of this file.

Note: Prior to the installation of the database schema for the product, please ensure that the Database Management System software is installed according to your site standards and the installation guide provided by the database vendor. Also please make sure that you have necessary licenses to use some of the advanced database features, such as Advanced Compression.

2.3 Oracle Database Installation

This section describes how to install Oracle Database for Oracle Revenue Management and Billing Version 2.5.0.0.0. It contains the following topics:

- [Initial Install, or Installing Version 2.5.0.0.0 for the First Time](#)
- [Demo Install](#)

Note: The installation tools outlined in this guide run on Windows and UNIX/Linux only. Please refer to the [Supported Database Platforms](#) section for more information on supported platforms.

2.3.1 Initial Install, or Installing Version 2.5.0.0.0 for the First Time

This section describes how to install the database components of Oracle Revenue Management and Billing. It includes the following topics:

- [Copying and Decompressing Install Media](#)
- [Creating the Database](#)
- [Installing Oracle Utilities Application Framework](#)
- [Installing Oracle Revenue Management and Billing](#)
- [Post Installation Tasks](#)

Note:

You must have a supported version of the Java Development Kit installed on the Windows desktop where you stage and run the database installation package. Refer to the *Oracle Revenue Management and Billing Installation Guide* for more information.

Before you begin with the installation, ensure that you have Oracle Database Client installed on the Windows desktop.

2.3.1.1 Copying and Decompressing Install Media

To download and decompress the ORMB Database package:

1. Download the Oracle Revenue Management and Billing V2.5.0.0.0 Oracle Database package from the Oracle Revenue Management and Billing V2.5.0.0.0 media pack which is available on [Oracle Software Delivery Cloud](#). A zip file is downloaded.
2. Create a temporary directory named TEMPDIR on your local machine.
3. Unzip the downloaded file in the TEMPDIR directory. The contents include the following sub-folders:
 - Demo_dump
 - FW
 - RMB

2.3.1.2 Creating the Database

Note: You must have Oracle Database Server 12.1.0.2 installed on your machine in order to create the database.

Creating the Database on UNIX

Create the database using the Database Configuration Assistant (DBCA). Refer to the article *Master Note: Overview of Database Configuration Assistant (DBCA)* (Doc ID 1488770.1) on [My Oracle Support](#) for more information. Ensure that you set the database character set to AL32UTF8.

For more information on how to create the database, refer to the [Creating the Database](#) section.

Creating the Database on Windows

You should be logged in as a user who is a member of the local ORA_DBA group on that server. The ORA_DBA group should have “administrator” privileges assigned to it.

Create the database using the Database Configuration Assistant (DBCA). Refer to the article *Master Note: Overview of Database Configuration Assistant (DBCA)* (Doc ID 1488770.1) on [My Oracle Support](#) for more information. Ensure that you set the database character set to AL32UTF8.

For more information on how to create the database, refer to the [Creating the Database](#) section.

2.3.1.3 Installing Oracle Utilities Application Framework

You need to install Oracle Utilities Application Framework Version 4.3.0.0.1 prior to Oracle Revenue Management and Billing Version 2.5.0.0.0. The files for Oracle Utilities Application Framework installation are located in the `FW\FW43001` folder. The installation process will prompt you to provide the following information:

- The target database name in which the product is to be installed.
- A database user that will own the application schema (for example, CISADM).
- A database user that has read-write (select, update, insert, and delete) privileges to the objects in the application schema (for example, CISUSER). The application will access the database as this user.
- A database user with read-only privileges to the objects in the application schema (for example, CISREAD).
- A database role that has read-write (select, update, insert, and delete) privileges to the objects in the application schema (for example, CIS_USER).
- A database role with read-only privileges to the objects in the application schema (for example, CIS_READ).
- Location of the jar files. (The Jar files are bundled in the database package.)
- Java Home (for example, C:\Java\jdk1.7.0_21)

Note: Ensure that you do not create more than one schema on a database.

To install Oracle Utilities Application Framework (OUAF), you need to install the following in the specified order:

1. [Install Oracle Utilities Application Framework Version 4.3.0.0.1](#)
2. [Install Rollup Pack for Oracle Utilities Application Framework Version 4.3.0.0.1](#)

Installing Oracle Utilities Application Framework Version 4.3.0.0.1

To install the schema for Oracle Utilities Application Framework Version 4.3.0.0.1:

1. Execute the `OraDBI.exe` utility from the `..\TEMPDIR\FW\FW43001\Install-Upgrade\` directory.

Note:

Please run the utility from the command prompt.

The `TEMPDIR` folder is the location where you have extracted the contents of the Oracle Revenue Management and Billing V2.5.0.0.0 Oracle Database package.

Ensure that you execute the `OraDBI` utility from the Window 32-bit or 64-bit desktop that has Oracle Database Client 12.1.0.1 (32-bit) and Java Development Kit Version 6.0 Update 20 or later installed. The database must be listed in the `tnsnames.ora` file on your local machine.

This utility prompts you to enter values for the following parameters:

Parameter	Value
Enter the name of the target database	<DB_NAME>
Enter your database username	<DB_USER> Example: CISADM
Enter your password username	<DB_USER_PASSWORD>
Enter the location for Java Home (e.g. C:\Java\jdk1.6.0_18)	..\jdk1.6.0_20
Enter the TUGBU jarfiles location (e.g. C:\Database-Install\Jarfiles)	..\FW\FW43001\jarfiles
Enter the Oracle user with read-write privileges to Database Schema	<DB_USER> Example: CISUSER
Enter the Oracle user with read-only privileges to Database Schema	<DB_USER> Example: CISREAD
Enter the database role with read-write privileges to Database Schema	<DB_USER_ROLE> Example: CIS_USER
Enter the database role with read-only privileges to Database Schema	<DB_USER_ROLE> Example: CIS_READ
Enter the name of the target Schema where you want to install or upgrade	<Schema_Name>
Enter the password for <DB_USER> schema	<DB_USER_PASSWORD>
Re-enter the password	<DB_USER_PASSWORD>

2. Enter the required parameter values. The following message appears in the command line:

Ready to upgrade the target database from V4.2.0.3.0 to V4.3.0.0.1, do you want to continue (Y/N) ?

3. Type **Y** and then press **Enter**. The following message appears in the command line:

Ready to upgrade the target database, Do you want to continue? (Y/N)

4. Type **Y** and then press **Enter**. A message appears indicating that the process is completed successfully.

On installing Oracle Utilities Application Framework Version 4.3.0.0.1, various objects are created in the database under CISADM schema. The following table lists the number of objects that are created when you install framework:

Object Type	Count
INDEX	692
LOB	45

Object Type	Count
SEQUENCE	4
TABLE	501
TRIGGER	1
VIEW	8

Ideally, the Oracle Utilities Application Framework Version 4.3.0.0.1 installation should approximately finish in 5 minutes. The execution time can vary to great extent depending on network speed between local machine and server location.

Note:

OraDBI performs the following tasks:

- Interacts with the user to collect information about the name of Oracle account that will own the application schema (for example, CISADM), password of this account, and the name of the Oracle account that the application user will use (for example, CISUSER), and the name of the Oracle account that will be assigned read-only privileges to the application schema (for example, CISREAD).
- Verifies whether tablespace names already exist in the Storage.xml file (if not, the process will abort).
- Installs the schema, installs the system data, and configures security.
- Maintains upgrade log tables in the database.
- Updates release ID when the upgrade is completed successfully.
- If an error occurs while executing a SQL script or another utility, it logs and displays the error message and allows you to re-execute the current step. Log files OraDBI###.log are created in the same folder as OraDBI and contains all the SQL commands executed against the database along with the results. The log files are incremental so that the results are never overwritten. If warning messages are generated during the upgrade, OraDBI prompts the user at the end of the process. Users should check the log files to verify the warning messages.
- Warning messages are only alerts and do not necessarily mean a problem exists.
- Stores the Schema owner and password in the feature configuration table. The password is stored in encrypted format.
- OraDBI can be executed by a non-schema owner.

Installing Rollup Pack for Oracle Utilities Application Framework Version 4.3.0.0.1

To install the rollup pack for Oracle Utilities Application Framework Version 4.3.0.0.1:

1. Download the Oracle Utilities Application Framework V4.3.0.0.1 Single Fix Prerequisite Rollup for RMB V2.5.0.0.0 package from the Oracle Revenue Management and Billing V2.5.0.0.0 media pack which is available on [Oracle Software Delivery Cloud](#). A zip file is downloaded.
2. Unzip the downloaded file in the TEMPDIR directory. The contents include the _ORMB-V25000-FW-PREREQ-MultiPlatform.jar file.

3. Decompress the JAR file using the following command:

```
cd TEMPDIR
jar -xvf ORMB-V25000-FW-PREREQ-MultiPlatform.jar
```

A sub-directory named FW-V4.3.0.0.1-Rollup is extracted. It contains the following two sub-folders:

- Application
- Database

4. Initialize the application environment where you want to install the rollup pack using the following command:

UNIX:

```
$SPLEBASE/bin/splenviron.sh -e $SPLEVIRO
```

Windows:

```
$SPLEBASE\bin\splenviron.cmd -e %SPLEVIRO%
```

5. Change to the Database directory using the following command:

```
cd TEMPDIR/FW-V4.3.0.0.1-Rollup/Database
```

6. Execute the ouafDatabasePatch utility using the following command:

UNIX:

```
chmod a+x *.sh ./ouafDatabasePatch.sh -p "-t 0 -d SCHEMA_NAME,
DBSERVER:DBPORT:DBSID"
```

Windows:

```
ouafDatabasePatch.cmd -p "-t 0 -d SCHEMA_NAME,
DBSERVER:DBPORT:DBSID"
```

This utility prompts you to enter values for the following parameters:

Parameter	Value
Enter the password for <DB_USER> schema	<DB_USER_PASSWORD>

7. Enter the required parameter value. The following message appears in the command line:

Ready to process patches, Do you want to continue? (Y/N)

8. Type **Y** and then press **Enter**. A message appears indicating that the patches are applied successfully.

On installing the rollup pack for Oracle Utilities Application Framework Version 4.3.0.0.1, various objects are created in the database under CISADM schema. The following table lists the number of objects that are created when you install the framework rollup pack:

Object Type	Count
INDEX	692
LOB	45

Object Type	Count
SEQUENCE	4
TABLE	501
TRIGGER	1
VIEW	8

Ideally, the framework rollup pack installation should approximately finish in 5 minutes. The execution time can vary to great extent depending on network speed between local machine and server location.

2.3.1.4 Installing Oracle Revenue Management and Billing

To install Oracle Revenue Management and Billing Version 2.5.0.0.0:

1. Execute the CdxDBI utility from the ..\TEMPDIR\RMB\Upgrade\Oracle\Install-Upgrade\ directory.

Note:

The TEMPDIR folder is the location where you have extracted the contents of the Oracle Revenue Management and Billing V2.5.0.0.0 Oracle Database package.

Ensure that you execute the CdxDBI utility from the Window 32-bit or 64-bit desktop that has Oracle Database Client 12.1.0.1 (32-bit) and Java Development Kit Version 6.0 Update 20 or later installed. The database must be listed in the tnsnames.ora file on your local machine.

This utility prompts you to enter values for the following parameters:

Parameter	Value
Enter the name of the target database	<DB_NAME>
Enter the name of the owner of Database Schema	<DB_USER> Example: CISADM
Enter the location for Java Home (e.g. C:\Java\jdk1.6.0_18)	..\jdk1.6.0_20
Enter the TUGBU jarfiles location (e.g. C:\Database-Install\Jarfiles)	..\RMB\jarfiles
Enter the password for <DB_USER> schema (or hit ENTER to quit)	<DB_USER_PASSWORD>
Re-enter the password	<DB_USER_PASSWORD>
Enter the Oracle user with read-write privileges to Database Schema	<DB_USER> Example: CISUSER
Enter the Oracle user with read-only privileges to Database Schema	<DB_USER> Example: CISREAD
Enter the database role with read-write privileges to Database Schema	<DB_USER_ROLE> Example: CIS_USER

Parameter	Value
Enter the database role with read-only privileges to Database Schema	<DB_USER_ROLE> Example: CIS_READ

2. Enter the required parameter values. The following message appears in the command line:

Ready to upgrade the target database from V2.4.0.1.0 to V2.5.0.0.0 do you want to continue (Y/N) ?

3. Type **Y** and then press **Enter**. The following message appears in the command line:

Ready to upgrade the target database, Do you want to continue? (Y/N)

4. Type **Y** and then press **Enter**. The utility upgrades the schema and system data definitions, and thereby reflects the metadata changes in the database. If an error occurs while executing the utility, it logs and displays the error message and allows you to re-execute the current step.

On installing Oracle Revenue Management and Billing Version 2.5.0.0.0, various objects are created in the database under CISADM schema. The following table lists the number of objects that are created when you install ORMB:

Object Type	Count
FUNCTION	14
INDEX	2574
LOB	142
PACKAGE	3
PACKAGE BODY	3
PROCEDURE	1
SEQUENCE	17
TABLE	1741
TRIGGER	1
TYPE	17
TYPE BODY	1
VIEW	154

Ideally, the Oracle Revenue Management and Billing Version 2.5.0.0.0 installation should approximately finish in 15 minutes. The execution time can vary to great extent depending on network speed between local machine and server location.

2.3.1.5 Post Installation Tasks

Once you install the Oracle Revenue Management and Billing Version 2.5.0.0.0 database, you need to do the following:

If you...	Then
Want to use the Transaction Feed Management feature...	<ol style="list-style-type: none"> 1. Enable USER_LOCK Package 2. Grant Permissions to the DBMS_LOCK Package and Recompile Database Objects 3. Generate Database Statistics
Do not want to use the Transaction Feed Management feature...	<ol style="list-style-type: none"> 1. Enable USER_LOCK Package 2. Increase INITRANS Values 3. Grant Permissions to the DBMS_LOCK Package and Recompile Database Objects 4. Generate Database Statistics

Enable USER_LOCK Package

To enable inbound web services, you must grant permissions to the USER_LOCK package. This is a one-time activity. To grant permissions to the USER_LOCK package:

1. Login as SYS user.
2. On SQL prompt, execute the following SQL:
`@?/rdbms/admin/userlock.sql`
3. Grant permission using the following SQL command:
`grant execute on USER_LOCK to public;`

Note: You can also grant permission to a specific database user (for example, CISADM or CISUSER) instead of granting permissions to all database users.

Increase INITRANS Values

To increase the INITRANS values of some indexes and tables:

1. Connect to the ORMB database using any SQL client (such as Oracle SQL Developer or PL/SQL Developer) and the `cisadm` credentials.
2. Execute the following statements:

```

ALTER TABLE CISADM.CI_BCHG_SQ INITRANS 20;
ALTER INDEX CISADM.XT081P0 INITRANS 40;
ALTER INDEX CISADM.IDX_SQ INITRANS 40;
ALTER TABLE CISADM.CI_BILL_CHG INITRANS 20;
ALTER INDEX CISADM.XT035P0 INITRANS 40;
ALTER INDEX CISADM.XT035S1 INITRANS 40;
ALTER INDEX CISADM.XT035S2 INITRANS 40;

```

```
ALTER INDEX CISADM.XT035S3 INITRANS 40;  
ALTER INDEX CISADM.XT035S4 INITRANS 40;
```

Note: The INITRANS values can be set as per the client's data volume.

Grant Permissions to the DBMS_LOCK Package and Recompile Database Objects

To grant permissions to the DBMS_LOCK package, execute the following commands:

UNIX:

```
export ORACLE_SID=[DB_NAME]  
sqlplus /nolog  
conn sys as sysdba
```

Note: On executing the above command, you will be prompted to enter the SYS user password.

```
grant EXECUTE, DEBUG on DBMS_LOCK to <DB_USER/ [CISADM]>;
```

Note:

These commands should be executed using Oracle SQL Developer.

If you have created the database using any user other than CISADM, you need to specify the respective user name in the above grant statement.

After executing the above grant statement, recompile the invalid objects, if any, in the database.

Windows:

```
set ORACLE_SID=[DB_NAME]  
sqlplus /nolog  
conn sys as sysdba
```

Note: On executing the above command, you will be prompted to enter the SYS user password.

```
grant EXECUTE, DEBUG on DBMS_LOCK to <DB_USER/ [CISADM]>;
```

Note:

These commands should be executed using Oracle SQL Developer.

If you have created the database using any user other than CISADM, you need to specify the respective user name in the above alter and grant statements.

After executing the above grant statement, recompile the invalid objects, if any, in the database.

Generate Database Statistics

During the installation process, new database objects may be added to the target database. Before you use the target database, we recommend you to gather statistics for the database objects. You can gather schema level statistics using the following statement:

```
BEGIN
DBMS_STATS.GATHER_SCHEMA_STATS(OWNNAME=>'CISADM', METHOD_OPT=>'FOR ALL
COLUMNS SIZE AUTO', GRANULARITY=>'ALL', CASCADE=>TRUE, DEGREE=>16);
END;
```

You can also gather the statistics for individual tables using the following statement:

```
BEGIN
DBMS_STATS.GATHER_TABLE_STATS(OWNNAME=>'CISADM',
TABNAME=>'<Table_Name>', GRANULARITY=>'ALL', CASCADE=>TRUE,
METHOD_OPT=> 'FOR ALL COLUMNS SIZE AUTO', DEGREE=>32);
END;
```

We strongly recommend you to schedule batch jobs to gather the schema level statistics on the daily basis in the non peak hours. Please note that the statistics should not be gathered while the application batches are running because this will degrade the application batch performance.

2.3.2 Demo Install

This section describes how to install the demo database components of Oracle Revenue Management and Billing. It includes the following topics:

- [Copying and Decompressing Install Media](#)
- [Creating the Database](#)
- [Importing the Demo Dump File](#)
- [Post Demo Database Creation Tasks](#)
- [Configuring Security](#)

2.3.2.1 Copying and Decompressing Install Media

To download and decompress the ORMB Database package:

1. Download the Oracle Revenue Management and Billing V2.5.0.0.0 Oracle Database package from the Oracle Revenue Management and Billing V2.5.0.0.0 media pack which is available on [Oracle Software Delivery Cloud](#). A zip file is downloaded.
2. Create a temporary directory named TEMPDIR on your local machine.
3. Unzip the downloaded file in the TEMPDIR directory. The contents include the following sub-folders:
 - Demo_dump
 - FW
 - RMB

2.3.2.2 Creating the Database

Note: You must have Oracle Database Server 12.1.0.2 installed on your machine in order to create the database.

Creating the Database on UNIX

Create the database using the Database Configuration Assistant (DBCA). Refer to the article *Master Note: Overview of Database Configuration Assistant (DBCA)* (Doc ID 1488770.1) on [My Oracle Support](#) for more information. Ensure that you set the database character set to AL32UTF8.

For more information on how to create the database, refer to the [Creating the Database](#) section.

Creating the Database on Windows

You should be logged in as a user who is a member of the local ORA_DBA group on that server. The ORA_DBA group should have “administrator” privileges assigned to it.

Create the database using the Database Configuration Assistant (DBCA). Refer to the article *Master Note: Overview of Database Configuration Assistant (DBCA)* (Doc ID 1488770.1) on [My Oracle Support](#) for more information. Ensure that you set the database character set to AL32UTF8.

For more information on how to create the database, refer to the [Creating the Database](#) section.

2.3.2.3 Importing the Demo Dump File

Once you create the database, you can import the `demo_dump.dmp` file. To import the demo dump file:

1. Create a database directory named `data_pump_dir` (If not available) and copy the dump file to this location.
2. Set the `ORACLE_SID` and `ORACLE_HOME` environment variables.
3. If the target schema is `CISADM`, then use the following command to import demo dump:

```
impdp system/<pwd>@<dbname> NOLOGFILE=N DIRECTORY=DATA_PUMP_DIR  
DUMPFILE=<dumpfilename>.dmp SCHEMAS=CISADM
```

4. If the target schema is other than `CISADM` (for example, `TRGSCHEM`), then use the following command to import demo dump:

```
impdp system/<pwd>@<dbname> NOLOGFILE=N DIRECTORY=DATA_PUMP_DIR  
DUMPFILE=<dumpfilename>.dmp REMAP_SCHEMA=CISADM:TRGSCHEMA
```

2.3.2.4 Post Demo Database Creation Tasks

Once you import the demo dump file, you need to do the following:

1. [Install Oracle Revenue Management and Billing Version 2.5.0.0.0](#)
2. [Enable USER_LOCK Package](#)
3. [Grant Permissions to the DBMS_LOCK Package and Recompile Database Objects](#)
4. [Generate Database Statistics](#)

Installing Oracle Revenue Management and Billing Version 2.5.0.0.0

To install Oracle Revenue Management and Billing Version 2.5.0.0.0:

1. Execute the CdxDBI .exe utility from ..\TEMPDIR\RMB\Upgrade\Oracle\Install-Upgrade\ directory.

Note:

The TEMPDIR folder is the location where you have extracted the contents of the Oracle Revenue Management and Billing V2.5.0.0.0 Oracle Database package.

Ensure that you execute the CdxDBI utility from the Window 32-bit or 64-bit desktop that has Oracle Database Client 12.1.0.1 (32-bit) and Java Development Kit Version 6.0 Update 20 or later installed. The database must be listed in the tnsnames.ora file on your local machine.

This utility prompts you to enter values for the following parameters:

Parameter	Value
Enter the name of the target database	<DB_NAME>
Enter the name of the owner of Database Schema	<DB_USER> Example: CISADM
Enter the location for Java Home (e.g. C:\Java\jdk1.6.0_18)	..\jdk1.6.0_20
Enter the TUGBU jarfiles location (e.g. C:\Database-Install\Jarfiles)	..\RMB\jarfiles
Enter the password for <DB_USER> schema (or hit ENTER to quit)	<DB_USER_PASSWORD>
Re-enter the password	<DB_USER_PASSWORD>
Enter the Oracle user with read-write privileges to Database Schema	<DB_USER> Example: CISUSER
Enter the Oracle user with read-only privileges to Database Schema	<DB_USER> Example: CISREAD
Enter the database role with read-write privileges to Database Schema	<DB_USER_ROLE> Example: CIS_USER
Enter the database role with read-only privileges to Database Schema	<DB_USER_ROLE> Example: CIS_READ

2. Enter the required parameter values. The following message appears in the command line:

Ready to upgrade the target database from V2.4.0.1.0 to V2.5.0.0.0 do you want to continue (Y/N) ?

3. Type **Y** and then press **Enter**. The following message appears in the command line:

Ready to upgrade the target database, Do you want to continue? (Y/N)

4. Type **Y** and then press **Enter**. The utility upgrades the schema and system data definitions, and thereby reflects the metadata changes in the database. If an error occurs while executing the utility, it logs and displays the error message and allows you to re-execute the current step.

On installing Oracle Revenue Management and Billing Version 2.5.0.0.0, various objects are created in the database under CISADM schema. The following table lists the number of objects that are created when you install ORMB:

Object Type	Count
FUNCTION	14
INDEX	2589
INDEX PARTITION	34
LOB	148
PACKAGE	3
PACKAGE BODY	3
PROCEDURE	2
SEQUENCE	23
TABLE	1764
TABLE PARTITION	2
TRIGGER	11
TYPE	20
TYPE BODY	1
VIEW	154

Ideally, the Oracle Revenue Management and Billing Version 2.5.0.0.0 installation should approximately finish in 15 minutes. The execution time can vary to great extent depending on network speed between local machine and server location.

Enable USER_LOCK Package

To enable inbound web services, you must grant permissions to the USER_LOCK package. This is a one-time activity. To grant permissions to the USER_LOCK package:

1. Login as SYS user.
2. On SQL prompt, execute the following SQL:
`@?/rdbms/admin/userlock.sql`
3. Grant permission using the following SQL command:
`grant execute on USER_LOCK to public;`

Note: You can also grant permission to a specific database user (for example, CISADM or CISUSER) instead of granting permissions to all database users.

Grant Permissions to the DBMS_LOCK Package and Recompile Database Objects

To grant permissions to the DBMS_LOCK package, execute the following commands:

UNIX:

```
export ORACLE_SID=[DB_NAME]
sqlplus /nolog
conn sys as sysdba
```

Note: On executing the above command, you will be prompted to enter the **SYS** user password.

```
grant EXECUTE, DEBUG on DBMS_LOCK to <DB_USER/ [CISADM]>;
```

Note:

These commands should be executed using Oracle SQL Developer.

If you have created the database using any user other than CISADM, you need to specify the respective user name in the above alter and grant statements.

After executing the above grant statement, recompile the invalid objects, if any, in the database.

Windows:

```
set ORACLE_SID=[DB_NAME]
sqlplus /nolog
conn sys as sysdba
```

Note: On executing the above command, you will be prompted to enter the **SYS** user password.

```
grant EXECUTE, DEBUG on DBMS_LOCK to <DB_USER/ [CISADM]>;
```

Note:

These commands should be executed using Oracle SQL Developer.

If you have created the database using any user other than CISADM, you need to specify the respective user name in the above alter and grant statements.

After executing the above grant statement, recompile the invalid objects, if any, in the database.

Generate Database Statistics

During the installation process, new database objects may be added to the target database. Before you use the target database, we recommend you to gather statistics for the database objects. You can gather schema level statistics using the following statement:

```
BEGIN
DBMS_STATS.GATHER_SCHEMA_STATS(OWNNAME=>'CISADM', METHOD_OPT=>'FOR ALL
COLUMNS SIZE AUTO', GRANULARITY=>'ALL', CASCADE=>TRUE, DEGREE=>16);
END;
```

You can also gather the statistics for individual tables using the following statement:

```
BEGIN
DBMS_STATS.GATHER_TABLE_STATS(OWNNAME=>'CISADM',
TABNAME=>'<Table_Name>', GRANULARITY=>'ALL', CASCADE=>TRUE,
METHOD_OPT=> 'FOR ALL COLUMNS SIZE AUTO', DEGREE=>32);
END;
```

We strongly recommend you to schedule batch jobs to gather the schema level statistics on the daily basis in the non peak hours. Please note that the statistics should not be gathered while the application batches are running because this will degrade the application batch performance.

2.3.2.5 Configuring Security

The configuration utility and scripts are located in the ..\TEMPDIR\RMB\Security folder. The TEMPDIR folder is the location where you have extracted the contents of the Oracle Revenue Management and Billing V2.5.0.0.0 Oracle Database package. To configure security, follow these steps:

1. Execute the OraGenSec.exe utility.

Note:

Database vault must be disabled before running.

Ensure that you execute the OraGenSec utility from the Window 32-bit or 64-bit desktop that has Oracle Database Client 12.1.0.1 (32-bit) and Java Development Kit Version 6.0 Update 20 or later installed. The database must be listed in the tnsnames.ora file on your local machine.

This utility prompts you to enter values for the following parameters:

Parameter	Value
Enter the application read-only user or Schema Owner in the database	<DB_USER> Example: CISADM
Enter the password for the <DB_USER> user	<DB_USER_PASSWORD> Example: CISADM
Enter the name of the Oracle database	<DB_NAME>
Enter a comma-separated list of Oracle users in which synonyms need to be created (e.g. cisuser, cisread)	<DB_USER> Example: CISUSER, CISREAD

2. Enter the required parameter values. The following message appears in the command line:

(A/a): Generate security for All objects in the Database?

(O/o): Generate security for specific Objects inputted in this terminal?

(F/f): Generate security for specific objects generated from an input File?

3. Type **A** to generate security for all objects in the database, and then press **Enter**. A message appears indicating that the database connection is established and security is defined for all objects in the database.

Note:

This utility configures security for the application owner schema objects.

If you run `Oragensec` in the Interactive Mode (i.e. without using the command line options), it will by default grant permissions to `CIS_USER` and `CIS_READ` role. If you prefer to use site-specific roles, then execute `Oragensec` after providing command line options.

For example:

```
(Oragensec.exe -d [Schema Owner]I[Schema OwnerIs Password]I[Database Name] -u [Read/Write User]I[Read Only User] -r [Read Only Role]I[Read Write Role] -a A -l [Logfile Name])
```

3. Database Design

This section provides a standard for database objects such as tables, columns, and indexes, for products using the Oracle Utilities Application Framework. This standard helps smooth integration and upgrade processes by ensuring clean database design, promoting communications, and reducing errors. Just as Oracle Utilities Application Framework goes through innovation in every release of the software, it is also inevitable that the product will take advantage of various database vendors' new features in each release. The recommendations in the database installation section include only the ones that have been proved by vigorous QA processes, field tests and benchmarks. This section includes:

- Database Object Standard
- Column Data Type and Constraints
- Standard Columns

3.1 Database Object Standard

This section discusses the rules applied to naming database objects and the attributes that are associated with these objects.

3.1.1 Categories of Data

A table can belong to one of the three categories:

- Control (admin)
- Master
- Transaction

For purposes of physical table space design, metadata and control tables can belong to the same category.

Example of tables in each category:

- Control: SC_USER, CI_ADJ_TYPE, F1_BUS_OBJ
- Master: CI_PER, CI_PREM,
- Transaction: F1_FACT, CI_FT

All tables have the category information in their index name. The second letter of the index carries this information. See the [Indexes](#) section for more information.

3.1.2 Naming Standards

The following naming standards must be applied to database objects.

Table

Table names are prefixed with the owner flag value of the product. For customer modification CM must prefix the table name. The length of the table names must be less than or equal to 30 characters. A language table should be named by suffixing _L to the main table. The key table name should be named by suffixing _K to the main table.

It is recommended to start a table name with the 2-3 letter acronym of the subsystem name that the table belongs to. For example, MD stands for metadata subsystem and all metadata table names start with CI_MD.

Some examples are:

- CI_ADJ_TYPE
- CI_ADJ_TYPE_L

A language table stores language sensitive columns such as a description of a code. The primary key of a language table consists of the primary key of the code table plus language code (LANGUAGE_CD).

A key table accompanies a table with a surrogate key column. A key value is stored with the environment id that the key value resides in the key table.

The tables prior to V2.0.0 are prefixed with CI_ or SC_.

Columns

The length of a column name must be less than or equal to 30 characters. For customer modification, CM must be prefixed in the column name. The following conventions apply when you define special types of columns in the database.

- Use the suffix FLG to define a lookup table field. Flag columns must be CHAR(4). Choose lookup field names carefully as these column names are defined in the lookup table (CI_LOOKUP_FLD) and must be prefixed by the product owner flag value.
- Use the suffix CD to define user-defined codes. User-defined codes are primarily found as the key column of the admin tables.
- Use the suffix ID to define system assigned key columns.
- Use the suffix SW to define Boolean columns. The valid values of the switches are 'Y' or 'N'. The switch columns must be CHAR(1)
- Use the suffix DT to define Date columns.
- Use the suffix DTTM to define Date Time columns.
- Use the suffix TM to define Time columns.

Some examples are:

- ADJ_STATUS_FLG
- CAN_RSN_CD

Indexes

Index names are composed of the following parts:

[OF][application specific prefix][C/M/T]NNN[P/S]

- OF- Owner Flag. The standard is to use the two characters of the product's owner flag. Note that there may be some older indexes that use only the first character of the owner flag. For client specific implementation of index, use CM for Owner Flag. If implementation creates a CM Index on table-columns for which the base product already provides an index, then the CM Index will be overridden by the base index.
- Application specific prefix could be C, F, T or another letter.

- C/M/T - The second character can be either C or M or T. C is used for control tables
- (Admin tables). M is for the master tables. T is reserved for the transaction tables.
- NNN - A three-digit number that uniquely identifies the table on which the index is defined.
- P/S - P indicates that this index is the primary key index. S is used for indexes other than primary keys.
- n is the index number, unique across all indexes on a given table (0 for primary and 1, 2, etc., for the secondary indexes).

Some examples are:

- F1C066P0
- F1C066S1
- XT206C2
- CMT206S2

Warning: Do not use index names in the application as the names can change due to unforeseeable reasons.

Updating Storage.xml

The `storage.xml` file that comes with the product allocates all base tables and indexes to the default tablespace `CISTS_01`. If you decide to allocate some tables or indexes outside of the default tablespace, then this has to be reflected in the `storage.xml` file by changing the tablespace name from the default value to a custom value, according to the format shown below:

Format:

```

<Table_Name>
<TABLESPACE>CISTS_01</TABLESPACE>
<PARALLEL>1</PARALLEL>
- <LOB>
- <Column Name>
<TABLESPACE>CISTS_01</TABLESPACE>
<SECUREFILE>Y</SECUREFILE>
<CHUNK>8192</CHUNK>
<CACHE>N</CACHE>
<LOGGING>Y</LOGGING>
<INROW>Y</INROW>
<COMPRESS>N</COMPRESS>
</Column Name>
</LOB>
</Table_Name>

```

Where Parallel defines the number of threads, that Oracle DB Server will use to access a table or create an index.

We recommend you to create CLOBs and store them in SECUREFILE with medium compression and cache enabled. Note that, by default, medium compression is turned-off and must be enabled only if you have the Advanced Compression license.

For instance, if a DBA decided to allocate table CI_ACCT in a tablespace MyTablespace, then they would have to change the storage.xml as follows:

```
<CI_ACCT>
<TABLESPACE>MyTablespace</TABLESPACE>
</CI_ACCT>
```

The oradbi process uses the storage.xml file to place the new database objects into defined tablespaces. A tablespace referenced in the storage.xml file must exist in the database.

The storage.xml file must be updated before each upgrade and/or new installation as required to allocate the tables and indexes across those tablespaces.

Table name is included as a comment for each of the indexes for clarity.

For an initial install, information for each object should be reviewed by a DBA. For each upgrade, only tablespace information for the objects added in the new release needs to be reviewed by a DBA.

Be careful while editing this file. Make sure that the tablespace names being used exist in the database. Do not change the basic format of this file.

Sequence

The base sequence name must be prefixed with the owner flag value of the product. For customer modification CM must prefix the sequence name. The sequence numbers should be named as below:

1. If the sequence is used for a specific table, then use the following sequence name:
[OF] [C/M/T] NNN_SEQ
 - OF stands for Owner Flag. For example, F1 stands for Framework. Other examples are W1, W2, M1, C1, D1, D2, etc.
 - C/M/T stands for Control (Admin)/Master/Transaction Tables.
 - NNN is a three digit unique Identifier for a table on which the sequence is defined.

For Example: F1T220_SEQ

2. If more than one sequence is used for a specific table then use the following sequence Name:
[OF] [C/M/T] NNN_Column_Name_SEQ
 - OF stands for Owner Flag. For example, F1 stands for framework. Other examples are W1, W2, M1, C1, D1, D2, etc.
 - C/M/T stands for Control (Admin)/Master/Transaction tables.
 - NNN is a three digit unique identifier for a table on which the sequence is defined.

For Example: F1T220_BO_STATUS_CD_SEQ and F1T220_BUS_OBJ_CD_SEQ.

3. If sequence is used for a generic requirement and not specific to a table, then use the following sequence name.

[OF]Column_Name_SEQ

- OF stands for Owner Flag. For example, F1 stands for framework. Other examples are W1, W2, M1, C1, D1, D2, etc. For Example: F1FKVALID_SEQ
- For a customer modification, CM must be prefixed in the sequence name.

Trigger

The base trigger name must be prefixed with the owner flag value of the product. When implementers add database objects, such as tables, triggers and sequences, the name of the objects should be prefixed by CM.

3.2 Column Data Type and Constraints

This section discusses the rules applied to column data type and constraints, and the attributes that are associated with these objects.

3.2.1 User Defined Code

User Defined Codes are defined as CHAR type. The length can vary by the business requirements but a minimum of eight characters is recommended. You will find columns defined in less than eight characters but with internationalization in mind new columns should be defined as CHAR(10) or CHAR(12). Also note that when the code is referenced in the application the descriptions are shown to users in most cases.

3.2.2 System Assigned Identifier

System assigned random numbers are defined as CHAR type. The length of the column varies to meet the business requirements. Number type key columns are used when a sequential key assignment is allowed or number type is required to interface with external software. For example, Notification Upload Staging ID is a Number type because most EDI software uses a sequential key assignment mechanism. For sequential key assignment implementation, the DBMS sequence generator is used in conjunction with Number Type ID columns.

3.2.3 Date/Time/Timestamp

Date, Time and Timestamp columns are defined physically as DATE in Oracle. Non-null constraints are implemented only for the required columns.

3.2.4 Number

Numeric columns are implemented as NUMBER type in Oracle. The precision of the number should always be defined. The scale of the number might be defined. Non-null constraints are implemented for all number columns.

3.2.5 Fixed Length/Variable Length Character Columns

When a character column is a part of the primary key of a table define the column in CHAR type. For the non-key character columns, the length should be the defining factor. If the column length should be greater than 10, use VARCHAR2 type in Oracle.

3.2.6 Null Column Support

The product supports Nullable columns. This means that the application can write NULLs instead of a blank space or zero (for numeric columns) by using NULLABLE_SW on CI_MD_TBL_FLD. If REQUIRED_SW is set to 'N' and the NULLABLE_SW is set to 'Y', the application will write a NULL in that column. The artifact generator will create hibernate mapping files with appropriate parameters so that the framework hibernate mapping types will know if a given property supports a null value.

NULLABLE_SW is not new, but has previously been used for certain fields such as dates, and some string and number foreign-key columns. Because of this, there is the possibility that there is incorrect metadata for some columns, and that turning on this new feature could result in incorrect behaviour when using that metadata. The upgrade script added to FW410 Group Fix 2 fixes the metadata to make sure that the existing tables will not be affected.

This new feature only supports tables maintained by Java, and not by Java program converted from COBOL. Thus, enhancing any existing tables to use null columns must be done only after making sure that the tables are maintained by Java, and not by Java converted COBOL programs.

3.2.7 XML Type Support

The product supports XML Type. XML Type provides following advantages.

1. The ability to use XQuery for querying nodes in the XML document stored within a column defined as XMLType.
2. The option to use the XML engine, which is built into the Oracle Database, to create indexes using nodes within the XML document stored in the XMLType column.

3.2.8 Cache and Key Validation Flags

By default, the Cache Flag is set to NONE. For most of the admin tables the CACHE Flag should be 'Cached for Batch'. This specifies that the table is cached as L2 cache to reduce database trips.

By default the Key Validation Flag is set to ALL. For tables which have the user defined keys, the KEY_VALIDATION_FLG should be set as 'ALL'. This checks the existence of the key before inserting a new one.

3.2.9 Table Classification and Table Volume Flags

There are multiple types of tables in the application, namely Admin system tables, Admin non- system tables, master tables and transaction tables. The Table Classification flag (TBL_CLASSIFICATION_FLG) sets the appropriate value for this lookup field to give a better view of the table classification.

Table Volume flag (TBL_VOLUME_FLG) is a customer modifiable field which is initially populated by product, but can be overridden by implementation. The field gives an idea of the relative data volume (categorized as highVolume, lowVolume and mediumVolume) of the table to make informed decisions.

3.2.10 Default Value Setting

The rules for setting the database default values are as follows:

- When a predefined default value is not available, set the default value of Non-null CHAR or VARCHAR columns to blank except the primary key columns.
- When a predefined default value is not available, set the default value Non-null Number columns to 0 (zero) except the primary key columns.
- No database default values should be assigned to the Non Null Date, Time, and Timestamp columns.

3.2.11 Foreign Key Constraints

Referential integrity is enforced by the application. In the database do not define FK constraints. Indexes are created on most of Foreign Key columns to increase performance.

3.3 Standard Columns

This section discusses the rules applied to standard columns and the attributes that are associated with these objects.

3.3.1 Owner Flag

Owner Flag (OWNER_FLG) columns exist on the system tables that are shared by multiple products. Oracle Utilities Application Framework limits the data modification of the tables that have owner flag to the data owned by the product.

3.3.2 Version

The Version column is used to for optimistic concurrency control in the application code. Add the Version column to all tables that are maintained by a Row Maintenance program.

4. Exadata Database Settings

If you are using the Oracle Exadata Database machine as the database server, ensure that you do the following:

- Use the Write-Back Flash Cache feature to leverage the Exadata Flash hardware
- Use the Exadata Smart Flash Logging feature

Note: By default, 512 MB of the Exadata flash is allocated to Smart Flash Logging. This is sufficient enough to handle the load of 300 million transactions daily in TFM.

- Set the temporary tablespace size to at least 600 GB
- Create `CISTS_01` tablepsace to store the `cisadm` objects using the BIGFILE and EXTENT MANAGEMENT LOCAL AUTOALLOCATE clauses. For example:

```
CREATE BIGFILE TABLESPACE CISTS_01 DATAFILE
  '+DATAC1/DBNAME/datafile/cists01.dbf' SIZE 800G AUTOEXTEND ON
  EXTENT MANAGEMENT LOCAL AUTOALLOCATE;
```

Note: Exadata servers can have two types of disks – High Capacity and High Performance. The Exadata throughput may vary depending on the disk type.

5. Database Implementation Guidelines

The following section outlines the general implementation guidelines for the database components, including:

- Configuration Guidelines
- Oracle Database Implementation Guidelines

5.1 Configuration Guidelines

This section includes general recommendations for configuring various database objects and includes a brief syntax overview. It covers the general aspects of the database objects and does not cover any specific implementation requirements. This section includes the following topics:

- [Index](#)
- [Temporary and Undo Tablespace](#)
- [Transparent Data Encryption Recommendations](#)
- [Data Compression Recommendations](#)
- [Database Vault Recommendations](#)
- [Oracle Fuzzy Search Support](#)
- [Storage Recommendations](#)
- [Database Configuration Recommendations](#)
- [Database Syntax](#)
- [Database Initialization Parameters](#)
- [Shrink Tables](#)

5.1.1 Index

Index recommendations specify points that need to be considered when creating indexes on a table.

1. Indexes on a table should be created according to the functional requirements of the table and not in order to perform SQL tuning.
2. The foreign keys on a table should be indexes.

Note: If the implementation creates a CM index on table-columns for which the product already provides an index, then the CM index will be overridden by the base index.

5.1.2 Temporary and Undo Tablespace

To begin with, we recommend you to set the temporary tablespace to at least 100GB auto extendable till 200GB and the undo tablespace to at least 100GB auto extendable till 300GB. The upper limit of both the tablespaces will vary as per the volume of the data and preferred chunk size of the batch.

5.1.3 Transparent Data Encryption Recommendations

Oracle Utilities supports Oracle Transparent Data Encryption (TDE). Oracle 11gR1 and 12c supports tablespace level encryption. The application supports tablespace level encryption for all application data. Make sure that the hardware resources are sufficiently sized for this as TDE uses additional hardware resources. The Oracle Advanced Security license is a prerequisite for using TDE.

Please consider the following when implementing TDE:

- Create a wallet folder to store the master key. By default, the wallet folder should be created under \$ORACLE_BASE/admin/<sid>.
alter system set encryption key authenticated by "keypasswd"
- The wallet containing the master key can be created using the following command:
alter system set wallet open identified by "keypasswd";
alter system set wallet close;
- The wallet can be closed or opened using the following commands:
alter system set wallet open identified by "keypasswd";
alter system set wallet close;
- Column level encryption can be achieved using the following commands:
create table <table_name>
(name varchar2(200) default ' ' not null,
bo_data_area CLOB encrypt using 'AES128',
bo_status_cd char(12) encrypt using 'AES128')
lob (bo_data_area) store as securefile (cache compress)
tablespace <tablespace_name>;
- AES128 is the default encryption algorithm.
- Tablespace level encryption is also supported using the following command:
Create tablespace <tablespace_name> logging datafile '<datafile location>' size <initial size> reuse autoextend on next <next size> maxsize unlimited extent management local uniform size <uniform size> encryption using 'AES128' default storage(encrypt) ;
- Indexed columns can only be encrypted using the NO SALT Option. Salt is a way to strengthen the security of encrypted data. It is a random string added to the data before it is encrypted, causing repetition of text in the clear to appear different when encrypted.

5.1.4 Data Compression Recommendations

Oracle Utilities supports Advanced Data Compression, available with Oracle 11gR1 onwards, to reduce the database storage footprint. Make sure that your resources are sufficiently sized for this as it uses additional system resources. Compression can be enabled at the Tablespace level or at the Table level.

5.1.4.1 Exadata Hardware

For Exadata hardware, the compression recommendations are:

- For high volumes tables, keep the current table partition uncompressed. All of the older partitions will be compressed based on QUERY HIGH compression.
- For high volume tables with CLOBs ensure to always keep CLOBs in securefile and medium compressed. Also keep the current table partition uncompressed. All of the older partitions will be compressed based on QUERY HIGH compression.
- Load data into the uncompressed table partitions using a conventional load and then, once data is loaded using a CTAS operation, load into a temporary heap table. Then truncate the original partition. Alter the original partition into HCC compressed and then partition exchange this with the temporary heap table.
- All multi column Indexes (primary as well as secondary) will be compressed using the default compression. HCC or OLTP compression is not applicable on the top of compressed Indexes.

5.1.4.2 Non- Exadata Hardware

For non-Exadata hardware the recommendations are the same as above, except that you cannot use HCC compression (it is only available in Exadata database machine). Instead of HCC, you can use any other compression tool available to you for non-Exadata hardware.

5.1.4.3 CLOB Fields

All CLOB fields should be stored as SecureFiles and Medium compressed. This requires a separate license for Advanced Data Compression. As a part of the schema, we create the product- owned tables with compression turned OFF at the LOB level. If you have the license for Advanced Data Compression, you can enable compression by updating the storage.xml.

5.1.5 Database Vault Recommendations

The product supports Database Vault. All non-application User IDs can be prevented from using DDL or DML statements against the application schema. So SYS and SYSTEM cannot issue DDL or DML statements against CISADM schema. The application-specific administration account can issue DDL statements but should not be able to perform any DML or DCL statements. Application user must be given DML only permissions. Database Vault can be used to control access during patch process and Install/Upgrade process. Configuration is also supported beginning with the Oracle Utilities Application Framework 4.2.0.0.0 patch application with Database Vault.

5.1.6 Oracle Fuzzy Search Support

The product supports Oracle Fuzzy searches. To use this feature, Oracle Text must be installed. After Oracle Text is installed, an index must be created on the table where the fuzzy search needs to be performed from the application. This is only an Oracle database option and is not supported by other databases. Additionally, not all languages are supported. Refer to the Oracle Database documentation for more information about fuzzy searching.

A typical syntax for implementation of fuzzy searching is as below. For the most updated syntax please refer to Oracle Fuzzy documentation.

```

GRANT CTXAPP TO <Application schema owner e.g. CISADM>;
GRANT EXECUTE ON CTX_DDL TO <Application schema owner e.g. CISADM>;
Create index <Application schema owner e.g. CISADM>.<Index_Name> on
<Application schema owner e.g. CISADM>.<Table_Name> (<column_name>)
indextype is ctxsys.context parameters ('sync (on commit)');
begin
  ctx_ddl.sync_index('Application schema owner e.g.
CISADM>.<Index_Name>');
end
/

```

5.1.7 Storage Recommendations

This section specifies recommended options for storing the database objects.

5.1.7.1 SecureFile for Storing LOBs

Beginning with Oracle 11g, tables having fields with data type of CLOB or BLOBS should have the LOB Columns stored as SecureFiles.

- The storage options with SecureFiles for Heap Tables should be ENABLE STORAGE IN ROW, CACHE and COMPRESS.
- For the IOT Table the PCTTHRESHOLD 50 OVERFLOW clause should be specified and the storage options with SecureFiles should be ENABLE STORAGE IN ROW, CACHE and COMPRESS.
- The PCTTHRESHOLD should be specified as a percentage of the block size. This value defines the maximum size of the portion of the row that is stored in the Index block when an overflow segment is used.
- The CHUNK option for storage, which is the data size used when accessing or modifying LOB values, can be set to higher than one database block size if big LOBs are used in the IO Operation.
- For SecureFiles, make sure that the initialization parameter db_securefile is set to ALWAYS.
- The Tablespace where you are creating the SecureFiles should be enabled with Automatic Segment Space Management (ASSM). In Oracle Database 11g, the default mode of Tablespace creation is ASSM so it may already be set for the Tablespace. If it's not, then you have to create the SecureFiles on a new ASSM Tablespace.

Note:

To enable compression on SecureFiles, you must have an Oracle Advanced Compression license in addition to Oracle Database Enterprise Edition. This feature is not available for the standard edition of Oracle Database.

If you are using Oracle Database Enterprise Edition, you must ensure that the **COMPRESS** flag is set to **Y** in the **Storage.xml** file. See the [Database Syntax](#) section for more information on SecureFiles.

5.1.8 Database Configuration Recommendations

This section specifies the recommended methods for configuring the database with a focus on specific functional area.

5.1.8.1 Large Redo Log File Sizes

The Redo Log files are written by the Log Writer Background process. These log files are written in a serial manner. Once a log file is full, a log switch occurs and the next log file starts getting populated.

It is recommended that the size of the Redo Log files should be sufficiently high so that you do not see frequent Log Switches in the alert logs of the database. Frequent Log Switches impact the IO performance and can be avoided by having a larger Redo Log File size.

We recommend you to set the redo log file size to at least 4GB or more depending on the volume of transactions. This will help you to ensure that there are not more than 5 to 6 log switches per hour.

5.1.9 Database Syntax

5.1.9.1 SecureFile

```
CREATE TABLE <Table_Name>
(COLUMN1 ... , COLUMN2 (CLOB) )
LOB (COLUMN2) STORE AS SECUREFILE (CACHE COMPRESS);
```

```
CREATE TABLE <Table_Name>
(COLUMN1 ... , COLUMN2 (CLOB) CONSTRAINT <> PRIMARY KEY(...))
ORGANIZATION INDEX PCTTHRESHOLD 50 OVERFLOW
LOB (COLUMN2) STORE AS SECUREFILE (ENABLE STORAGE IN ROW CHUNK CACHE
COMPRESS) ;
```

5.1.10 Database Initialization Parameters

This section recommends value for each parameter in the `init.ora` file. These parameters are a starting point for database tuning. The actual or optimal value for a production environment may differ from one deployment to another.

The following recommendations must be treated as guidelines and not as the actual values:

Parameter	Recommended Value
MEMORY_MAX_TARGET	40-50% of total available RAM on the node
MEMORY_TARGET	Value should be less than or equal to the value set for the <code>MEMORY_MAX_TARGET</code> parameter and at the same time it should be greater than or equal to the sum of <code>SGA_TARGET</code> and <code>PGA_AGGREGATE_TARGET</code>

Parameter	Recommended Value
SGA_TARGET	50-70% of the value defined for the MEMORY_TARGET parameter
SGA_MAX_SIZE	70-80% of the value defined for the MEMORY_MAX_TARGET parameter
DB_CACHE_SIZE	4GB
PGA_AGGREGATE_TARGET	2GB
STATISTICS_LEVEL	TYPICAL or ALL <div style="border: 1px solid black; padding: 5px; margin-top: 5px;"> Note: This parameter is mandatory when you want to use automatic memory management. </div>
OPTIMIZER_INDEX_COST_ADJ	100 <div style="border: 1px solid black; padding: 5px; margin-top: 5px;"> Note: The value for this parameter should not be changed because it can drastically degrade the batch performance. </div>
OPTIMIZER_INDEX_CACHING	0 <div style="border: 1px solid black; padding: 5px; margin-top: 5px;"> Note: The value for this parameter should not be changed because it can drastically degrade the batch performance. </div>
DB_BLOCK_SIZE	8192
LOG_CHECKPOINT_INTERVAL	0
DB_FILE_MULTIBLOCK_READ_COUNT	8
TRANSACTIONS	3000
OPEN_CURSORS	30000
DB_WRITER_PROCESSES	10 <div style="border: 1px solid black; padding: 5px; margin-top: 5px;"> Note: The value for this parameter must be within the range of 1 to 20. Ideally, it must be set to 1 or CPU_COUNT/8, whichever is greater. </div>
DB_FILES	1024
DBWR_IO_SLAVES	10 <div style="border: 1px solid black; padding: 5px; margin-top: 5px;"> Note: You must set this parameter to a nonzero value only when the system does not support asynchronous IO. </div>
SESSIONS	4500
PROCESSES	3000

Parameter	Recommended Value
DML_LOCKS	48600
_B_TREE_BITMAP_PLANS	FALSE
SESSION_CACHED_CURSORS	500

For example, we recommend you to specify the following values when 100GB of RAM is available on the node:

MEMORY_MAX_TARGET = 50G

MEMORY_TARGET = 40G

SGA_TARGET = 30G

SGA_MAX_SIZE = 40G

DB_CACHE_SIZE = 4G

PGA_AGGREGATE_TARGET = 2G

STATISTICS_LEVEL=TYPICAL

5.1.11 Shrink Tables

A large number of rows are inserted and then deleted from the following three tables:

- CI_TXN_DTL_PRITM_SUMMARY
- CI_TXN_DETAIL_STG
- CI_ROLLBACK_TXN_DETAIL

Therefore, these tables need to be shrunk periodically. This activity should be carried out when no other transactions are active on the database.

1. Extract and keep the DDL scripts for all the existing indexes on the above tables from the data dictionary.
2. Drop all the indexes on the above tables.
3. Shrink the tables by executing following statements using SQL client:

```
ALTER TABLE CI_TXN_DTL_PRITM_SUMMARY ENABLE ROW MOVEMENT;
ALTER TABLE CI_TXN_DTL_PRITM_SUMMARY SHRINK SPACE CASCADE;
ALTER TABLE CI_TXN_DETAIL_STG ENABLE ROW MOVEMENT;
ALTER TABLE CI_TXN_DETAIL_STG SHRINK SPACE CASCADE;
ALTER TABLE CI_ROLLBACK_TXN_DETAIL ENABLE ROW MOVEMENT;
ALTER TABLE CI_ROLLBACK_TXN_DETAIL SHRINK SPACE CASCADE;
```

4. Recreate all the indexes using scripts generated in step 1 above.

You can execute these statements either manually or through a batch process which is configured to run at regular interval.

Note: Shrink operations can be performed only on segments in locally managed tablespaces with Automatic Segment Space Management (ASSM).

Once the above statements are executed, you must gather statistics using the following statements:

```
BEGIN

DBMS_STATS.GATHER_TABLE_STATS(OWNNAME=>'CISADM',
TABNAME=>'CI_TXN_DTL_PRITM_SUMMARY', GRANULARITY=>'ALL', CASCADE=>TRUE,
METHOD_OPT=>'FOR ALL COLUMNS SIZE AUTO', DEGREE=>32);

DBMS_STATS.GATHER_TABLE_STATS(OWNNAME=>'CISADM',
TABNAME=>'CI_TXN_DETAIL_STG', GRANULARITY=>'ALL', CASCADE=>TRUE,
METHOD_OPT=>'FOR ALL COLUMNS SIZE AUTO', DEGREE=>32);

DBMS_STATS.GATHER_TABLE_STATS(OWNNAME=>'CISADM',
TABNAME=>'CI_ROLLBACK_TXN_DETAIL', GRANULARITY=>'ALL', CASCADE=>TRUE,
METHOD_OPT=>'FOR ALL COLUMNS SIZE AUTO', DEGREE=>32);

END;
```

5.2 Oracle Database Implementation Guidelines

This section provides specific guidelines for implementing the Oracle database.

5.2.1 Oracle Partitioning

If you use a base index as the partitioning key, rename the index to CM**. If you use the primary key index of the table as the partitioning key:

- Make the index non-unique.
- Primary constraints should still exist.

The upgrade on the partitioned table works best if the partitioning key is not unique. This allows the upgrade tool to drop the PK constraints if the primary key columns are modified and recreate the PK constraints without dropping the index.

5.2.2 Database Statistic

During an install process, new database objects may be added to the target database. Before starting to use the database, generate the complete statistics for these new objects by using the DBMS_STATS package. You should gather statistics periodically for objects where the statistics become stale over time because of changing data volumes or changes in column values. New statistics should be gathered after a schema object's data or structure are modified in ways that make the previous statistics inaccurate. For example, after loading a significant number of rows into a table, collect new statistics on the number of rows. After updating data in a table, you do not need to collect new statistics on the number of rows, but you might need new statistics on the average row length.

A sample syntax that can be used is as follows:

```
BEGIN

SYS.DBMS_STATS.GATHER_SCHEMA_STATS (OwnName => 'CISADM', Degree =>
16, Cascade => TRUE, Method_opt => 'FOR ALL COLUMNS SIZE AUTO',
Granularity => 'ALL');

END;
/
```

5.2.3 Materialized View

Oracle Database Enterprise Edition supports query rewrite using Materialized View. If you use Oracle Database Enterprise Edition, you can create the following Materialized View to improve performance of the C1- TRMDD batch:

```
CREATE MATERIALIZED VIEW F1 BO LIFECYCLE STATUS MVW
(
BUS OBJ CD,
LIFE CYCLE BO CD,
BO STATUS CD,
BATCH CD
)
BUILD IMMEDIATE REFRESH ON COMMIT ENABLE QUERY REWRITE AS SELECT
BO2. BUS OBJ CD, BO.LIFE CYCLE BO CD, BOSA.BO STATUS CD, LCBOS.BATCH
CD as
LC BATCH CD
FROM
F1 BUS OBJ BO2,
F1 BUS OBJ BO,
F1 BUS OBJ STATUS LCBOS,
F1 BUS OBJ STATUS ALG BOSA
WHERE
BO2.LIFE CYCLE BO CD =BO.LIFE CYCLE BO CD AND
BO.BUS OBJ CD = BOSA.BUS OBJ CD AND
BOSA.BO STATUS SEVT FLG = 'F1AT' AND
LCBOS.BUS OBJ CD = BO.LIFE CYCLE BO CD AND
LCBOS.BO STATUS CD = BOSA.BO STATUS CD
/
```

Appendix A : New Objects in the Oracle Revenue Management and Billing V2.5.0.0.0 Database

This section lists the objects that are newly added in the Oracle Revenue Management and Billing V2.5.0.0.0 database. These objects are classified under the following two sections:

- Schema Changes
- New System Data

A.1 Schema Changes

This section lists schema related changes made in the Oracle Revenue Management and Billing V2.5.0.0.0 database.

A.1.1 New Tables

The following tables are newly added in the Oracle Revenue Management and Billing V2.5.0.0.0 database:

Table	Description
C1_DIV_PER_REL_SEQ	Person Relationship Type Sequence for Division
C1_DIV_PRICEITEM_PER_REL_SEQ	Person Relationship Type Sequence for Product
C1_PAY_DETAILS	Payment Details
C1_PAY_DISTRIBUTION	Payment Distribution
C1_PAY_MATCH_TYPE	Payment Match Type
C1_PAY_REQ	Payment Request
C1_PAY_REQUEST_TYPE	Payment Request Type
C1_PAY_REQUEST_TYPE_CHAR	Payment Request Type Characteristics
C1_PAY_REQUEST_TYPE_L	Payment Request Type Language
C1_PAY_REQ_K	Payment Request Key
C1_PAY_REQ_LOG	Payment Request Log
C1_PAY_REQ_LOG_PARM	Payment Request Log Message Parameter
C1_PAY_TNDR_CHAR_REQ	Payment Tender Characteristic Request
C1_PAY_TNDR_REQ	Payment Tender Request
C1_REQUEST	Request

Table	Description
C1_REQUEST_CHAR	Request Characteristic
C1_REQUEST_K	Request Key
C1_REQUEST_LOG	Request Log
C1_REQUEST_LOG_PARM	Request Log Message Parameter
C1_REQUEST_REL_OBJ	Request Related Object
C1_REQUEST_TYPE	Request Type
C1_REQUEST_TYPE_CHAR	Request Type Characteristics
C1_REQUEST_TYPE_L	Request Type Language
C1_UPL_REQUEST	Upload Request
C1_UPL_REQUEST_K	Upload Request Key
C1_UPL_REQUEST_TYPE	Upload Request Type
C1_UPL_REQUEST_TYPE_CHAR	Upload Request Type Characteristics
C1_UPL_REQUEST_TYPE_L	Upload Request Type Language
C1_UPL_REQ_DTLS	Upload Request Details
C1_UPL_REQ_LOG	Upload Request Log
C1_UPL_REQ_LOG_PARM	Upload Request Log Message Parameter
CI_ACCUM_ASL_AMT	Aggregate Stop Loss Accumulations
CI_ACCUM_GRP	Accumulation Group
CI_ACCUM_GRP_ASL	Aggregate Stop Loss Information of an Accumulation Group
CI_ACCUM_GRP_CHAR	Accumulation Group Characteristics
CI_ACCUM_GRP_K	Accumulation Group Key
CI_ACCUM_GRP_SL_LASER_EXC	Lasering and Exclusion Information of an Accumulation Group
CI_ACCUM_GRP_SL_PRICEITEM	Accumulation Group and Product Mapping
CI_ACCUM_GRP_SSL	Specific Stop Loss Information of an Accumulation Group
CI_ACCUM_SSL_AMT	Specific Stop Loss Accumulations
CI_AGG_PARM_GRP_DTL	Number of Parameters in the Product Parameter Group
CI_TXN_CALC_ACCUM_GRP	Transaction Product Calculation and Accumulation Group Mapping
CI_TXN_CALC	Transaction Product Calculation Details
CI_TXN_CALC_LN	Transaction Product Calculation Lines
CI_TXN_CALC_LN_CHAR	Transaction Product Calculation Line Characteristics
CI_TXN_SQ	Transaction Product Service Quantity

A.1.2 Added Columns

The following columns are newly added in the Oracle Revenue Management and Billing V2.5.0.0.0 database:

Table	Column	Required (Yes or No)
CI_ADJ	BILL_ID	No
	SET_CONSTRUCT_ID	No
	SET_VERSION_NUM	No
	SETTLEMENT_ACCT_ID	No
	SETTLEMENT_ID_NBR	No
CI_ADJ_TYPE	INFLNC_BILL_BAL	No
CI_APAY_CLR_STG	SETTLEMENT_ID_NBR	No
	SETTLEMENT_ACCT_ID	No
CI_BILL_CHG	AGG_PARM_GRP_ID	No
CI_BSEG_EXT	SETTLEMENT_ACCT_ID	No
	SET_CONSTRUCT_ID	No
	SET_VERSION_NUM	No
	SETTLEMENT_ID_NBR	No
CI_CONSTRUCT_TEMPLATE	SETTLEMENT_ACCT_ID	No
CI_DISAGG_TXN_PRITM_DETAIL	AGG_PARM_GRP_ID	No
	TXN_RATING_CRITERIA	No
	TXN_CALC_ID	No
CI_FT	FXLG_CALC_AMT	No
	SETTLEMENT_ID_NBR	No
	FXLG_CALC_STATUS	No
	PRSN_BILL_ID	No
CI_FT_GL	FT_GL_CATEGORY	No
CI_PRC_AGRD	PER_REL_TYPE_CD	No
	TXN_RATING_CRITERIA	No
CI_PRC_INH_PL	PER_REL_TYPE_CD	No
	TXN_RATING_CRITERIA	No
CI_PRC_PL	PER_REL_TYPE_CD	No
	TXN_RATING_CRITERIA	No

Table	Column	Required (Yes or No)
CI_PRICEASGN	TXN_RATING_CRITERIA	No
CI_PRICEITEM_REL	WEIGHTAGE	Yes
CI_SUB_RULE	RHS_FLD_NAME	Yes
	RHS_ALG_CD	Yes
CI_TEMPLATE_VAR	ZONE_CD	No
CI_TXN_DTL_PRITM	AGG_PARM_GRP_ID	No
	TXN_RATING_CRITERIA	No
	TXN_CALC_ID	No
CI_TXN_DTL_PRITM_STG	AGG_PARM_GRP_ID	No
	TXN_RATING_CRITERIA	No
	TXN_CALC_ID	No
CI_TXN_DTL_PRITM_SUMMARY	AGG_PARM_GRP_ID	No
	TXN_RATING_CRITERIA	No
	TXN_CALC_ID	No

A.1.3 Dropped Tables

None

A.1.4 Dropped Columns

None

A.1.5 Column Format Change

The format of the following columns is changed in the Oracle Revenue Management and Billing V2.5.0.0.0 database:

Table	Column	From	To
CI_ENRL_PER_ID	PER_ID_NBR	VARCHAR2 (16)	VARCHAR2 (90)
CI_MEMBERSHIP	EXT_MEMBER_ID	VARCHAR2 (15)	VARCHAR2 (100)
CI_PER_ID	PER_ID_NBR	VARCHAR2 (16)	VARCHAR2 (90)
C1_PAY_REQ_LOG_PARM	MSG_PARM_VAL	VARCHAR2(30)	VARCHAR2(2000)
C1_REQUEST_LOG_PARM	MESSAGE_PARM	VARCHAR2(30)	VARCHAR2(2000)
C1_UPL_REQ_LOG_PARM	MESSAGE_PARM	VARCHAR2(30)	VARCHAR2(2000)
CI_ACCT_MSG_PRM	MSG_PARM_VAL	VARCHAR2(30)	VARCHAR2(2000)

Table	Column	From	To
CI_ACC_CUR_LOG_PARM	MESSAGE_PARM	VARCHAR2(30)	VARCHAR2(2000)
CI_ADJ_STG_CTL_MSGP	MESSAGE_PARM	VARCHAR2(30)	VARCHAR2(2000)
CI_ADJ_STG_UP_MSGP	MESSAGE_PARM	VARCHAR2(30)	VARCHAR2(2000)
CI_AM_REQ_LOG_PARM	MESSAGE_PARM	VARCHAR2(30)	VARCHAR2(2000)
CI_APAY_STGUP_EXC	MESSAGE_PARM1	VARCHAR2(30)	VARCHAR2(2000)
CI_APAY_STGUP_EXC	MESSAGE_PARM2	VARCHAR2(30)	VARCHAR2(2000)
CI_APAY_STGUP_EXC	MESSAGE_PARM3	VARCHAR2(30)	VARCHAR2(2000)
CI_APAY_STGUP_EXC	MESSAGE_PARM4	VARCHAR2(30)	VARCHAR2(2000)
CI_APAY_STGUP_EXC	MESSAGE_PARM5	VARCHAR2(30)	VARCHAR2(2000)
CI_APAY_STGUP_EXC	MESSAGE_PARM6	VARCHAR2(30)	VARCHAR2(2000)
CI_APAY_STGUP_EXC	MESSAGE_PARM7	VARCHAR2(30)	VARCHAR2(2000)
CI_APAY_STGUP_EXC	MESSAGE_PARM8	VARCHAR2(30)	VARCHAR2(2000)
CI_APAY_STGUP_EXC	MESSAGE_PARM9	VARCHAR2(30)	VARCHAR2(2000)
CI_APPR_REQ_LOG_PARM	MESSAGE_PARM	VARCHAR2(30)	VARCHAR2(2000)
CI_BATCH_CTRL	EMAILID	VARCHAR2(254)	VARCHAR2(70)
CI_BATCH_JOB	EMAILID	VARCHAR2(254)	VARCHAR2(70)
CI_BCHG_STG_EXCP	MESSAGE_PARM1	VARCHAR2(30)	VARCHAR2(2000)
CI_BCHG_STG_EXCP	MESSAGE_PARM2	VARCHAR2(30)	VARCHAR2(2000)
CI_BCHG_STG_EXCP	MESSAGE_PARM3	VARCHAR2(30)	VARCHAR2(2000)
CI_BCHG_STG_EXCP	MESSAGE_PARM4	VARCHAR2(30)	VARCHAR2(2000)
CI_BCHG_STG_EXCP	MESSAGE_PARM5	VARCHAR2(30)	VARCHAR2(2000)
CI_BCHG_STG_EXCP	MESSAGE_PARM6	VARCHAR2(30)	VARCHAR2(2000)
CI_BCHG_STG_EXCP	MESSAGE_PARM7	VARCHAR2(30)	VARCHAR2(2000)
CI_BCHG_STG_EXCP	MESSAGE_PARM8	VARCHAR2(30)	VARCHAR2(2000)
CI_BCHG_STG_EXCP	MESSAGE_PARM9	VARCHAR2(30)	VARCHAR2(2000)
CI_BCHG_UP_EXCP	MESSAGE_PARM1	VARCHAR2(30)	VARCHAR2(2000)
CI_BCHG_UP_EXCP	MESSAGE_PARM2	VARCHAR2(30)	VARCHAR2(2000)
CI_BCHG_UP_EXCP	MESSAGE_PARM3	VARCHAR2(30)	VARCHAR2(2000)
CI_BCHG_UP_EXCP	MESSAGE_PARM4	VARCHAR2(30)	VARCHAR2(2000)
CI_BCHG_UP_EXCP	MESSAGE_PARM5	VARCHAR2(30)	VARCHAR2(2000)
CI_BCHG_UP_EXCP	MESSAGE_PARM6	VARCHAR2(30)	VARCHAR2(2000)

Table	Column	From	To
CI_BCHG_UP_EXCP	MESSAGE_PARM7	VARCHAR2(30)	VARCHAR2(2000)
CI_BCHG_UP_EXCP	MESSAGE_PARM8	VARCHAR2(30)	VARCHAR2(2000)
CI_BCHG_UP_EXCP	MESSAGE_PARM9	VARCHAR2(30)	VARCHAR2(2000)
CI_BILL_EXCP	MESSAGE_PARM1	VARCHAR2(30)	VARCHAR2(2000)
CI_BILL_EXCP	MESSAGE_PARM2	VARCHAR2(30)	VARCHAR2(2000)
CI_BILL_EXCP	MESSAGE_PARM3	VARCHAR2(30)	VARCHAR2(2000)
CI_BILL_EXCP	MESSAGE_PARM4	VARCHAR2(30)	VARCHAR2(2000)
CI_BILL_EXCP	MESSAGE_PARM5	VARCHAR2(30)	VARCHAR2(2000)
CI_BILL_EXCP	MESSAGE_PARM6	VARCHAR2(30)	VARCHAR2(2000)
CI_BILL_EXCP	MESSAGE_PARM7	VARCHAR2(30)	VARCHAR2(2000)
CI_BILL_EXCP	MESSAGE_PARM8	VARCHAR2(30)	VARCHAR2(2000)
CI_BILL_EXCP	MESSAGE_PARM9	VARCHAR2(30)	VARCHAR2(2000)
CI_BILL_MSG_PRM	MSG_PARM_VAL	VARCHAR2(30)	VARCHAR2(2000)
CI_BSEG_EXCP	MESSAGE_PARM1	VARCHAR2(30)	VARCHAR2(2000)
CI_BSEG_EXCP	MESSAGE_PARM2	VARCHAR2(30)	VARCHAR2(2000)
CI_BSEG_EXCP	MESSAGE_PARM3	VARCHAR2(30)	VARCHAR2(2000)
CI_BSEG_EXCP	MESSAGE_PARM4	VARCHAR2(30)	VARCHAR2(2000)
CI_BSEG_EXCP	MESSAGE_PARM5	VARCHAR2(30)	VARCHAR2(2000)
CI_BSEG_EXCP	MESSAGE_PARM6	VARCHAR2(30)	VARCHAR2(2000)
CI_BSEG_EXCP	MESSAGE_PARM7	VARCHAR2(30)	VARCHAR2(2000)
CI_BSEG_EXCP	MESSAGE_PARM8	VARCHAR2(30)	VARCHAR2(2000)
CI_BSEG_EXCP	MESSAGE_PARM9	VARCHAR2(30)	VARCHAR2(2000)
CI_CASE_LOG_PARM	MESSAGE_PARM	VARCHAR2(30)	VARCHAR2(2000)
CI_CONSTRUCT_LOG_PARM	MESSAGE_PARM	VARCHAR2(30)	VARCHAR2(2000)
CI_COP_EVT_EXP	MESSAGE_PARM	VARCHAR2(30)	VARCHAR2(2000)
CI_DV_TEST_EXCP	MESSAGE_PARM1	VARCHAR2(30)	VARCHAR2(2000)
CI_DV_TEST_EXCP	MESSAGE_PARM2	VARCHAR2(30)	VARCHAR2(2000)
CI_DV_TEST_EXCP	MESSAGE_PARM3	VARCHAR2(30)	VARCHAR2(2000)
CI_DV_TEST_EXCP	MESSAGE_PARM4	VARCHAR2(30)	VARCHAR2(2000)
CI_DV_TEST_EXCP	MESSAGE_PARM5	VARCHAR2(30)	VARCHAR2(2000)
CI_DV_TEST_EXCP	MESSAGE_PARM6	VARCHAR2(30)	VARCHAR2(2000)

Table	Column	From	To
CI_DV_TEST_EXCP	MESSAGE_PARM7	VARCHAR2(30)	VARCHAR2(2000)
CI_DV_TEST_EXCP	MESSAGE_PARM8	VARCHAR2(30)	VARCHAR2(2000)
CI_DV_TEST_EXCP	MESSAGE_PARM9	VARCHAR2(30)	VARCHAR2(2000)
CI_ENRL	EMAILID	VARCHAR2(254)	VARCHAR2(70)
CI_EXT_STMT_LOG_PARM	MESSAGE_PARM	VARCHAR2(30)	VARCHAR2(2000)
CI_FA_Rem_EXP	MESSAGE_PARM	VARCHAR2(30)	VARCHAR2(2000)
CI_FA_STGUP_EXC	MESSAGE_PARM1	VARCHAR2(30)	VARCHAR2(2000)
CI_FA_STGUP_EXC	MESSAGE_PARM2	VARCHAR2(30)	VARCHAR2(2000)
CI_FA_STGUP_EXC	MESSAGE_PARM3	VARCHAR2(30)	VARCHAR2(2000)
CI_FA_STGUP_EXC	MESSAGE_PARM4	VARCHAR2(30)	VARCHAR2(2000)
CI_FA_STGUP_EXC	MESSAGE_PARM5	VARCHAR2(30)	VARCHAR2(2000)
CI_FA_STGUP_EXC	MESSAGE_PARM6	VARCHAR2(30)	VARCHAR2(2000)
CI_FA_STGUP_EXC	MESSAGE_PARM7	VARCHAR2(30)	VARCHAR2(2000)
CI_FA_STGUP_EXC	MESSAGE_PARM8	VARCHAR2(30)	VARCHAR2(2000)
CI_FA_STGUP_EXC	MESSAGE_PARM9	VARCHAR2(30)	VARCHAR2(2000)
CI_INTV_DS_EXC	MESSAGE_PARM1	VARCHAR2(30)	VARCHAR2(2000)
CI_INTV_DS_EXC	MESSAGE_PARM2	VARCHAR2(30)	VARCHAR2(2000)
CI_INTV_DS_EXC	MESSAGE_PARM3	VARCHAR2(30)	VARCHAR2(2000)
CI_INTV_DS_EXC	MESSAGE_PARM4	VARCHAR2(30)	VARCHAR2(2000)
CI_INTV_DS_EXC	MESSAGE_PARM5	VARCHAR2(30)	VARCHAR2(2000)
CI_INTV_DS_EXC	MESSAGE_PARM6	VARCHAR2(30)	VARCHAR2(2000)
CI_INTV_DS_EXC	MESSAGE_PARM7	VARCHAR2(30)	VARCHAR2(2000)
CI_INTV_DS_EXC	MESSAGE_PARM8	VARCHAR2(30)	VARCHAR2(2000)
CI_INTV_DS_EXC	MESSAGE_PARM9	VARCHAR2(30)	VARCHAR2(2000)
CI_MEMBERSHIP_LOG_PARM	MESSAGE_PARM	VARCHAR2(30)	VARCHAR2(2000)
CI_MR_Rem_EXCP	MESSAGE_PARM1	VARCHAR2(30)	VARCHAR2(2000)
CI_MR_Rem_EXCP	MESSAGE_PARM2	VARCHAR2(30)	VARCHAR2(2000)
CI_MR_Rem_EXCP	MESSAGE_PARM3	VARCHAR2(30)	VARCHAR2(2000)
CI_MR_Rem_EXCP	MESSAGE_PARM4	VARCHAR2(30)	VARCHAR2(2000)
CI_MR_Rem_EXCP	MESSAGE_PARM5	VARCHAR2(30)	VARCHAR2(2000)
CI_MR_Rem_EXCP	MESSAGE_PARM6	VARCHAR2(30)	VARCHAR2(2000)

Table	Column	From	To
CI_MR_Rem_EXCP	MESSAGE_PARM7	VARCHAR2(30)	VARCHAR2(2000)
CI_MR_Rem_EXCP	MESSAGE_PARM8	VARCHAR2(30)	VARCHAR2(2000)
CI_MR_Rem_EXCP	MESSAGE_PARM9	VARCHAR2(30)	VARCHAR2(2000)
CI_MR_STGUP_EXC	MESSAGE_PARM1	VARCHAR2(30)	VARCHAR2(2000)
CI_MR_STGUP_EXC	MESSAGE_PARM2	VARCHAR2(30)	VARCHAR2(2000)
CI_MR_STGUP_EXC	MESSAGE_PARM3	VARCHAR2(30)	VARCHAR2(2000)
CI_MR_STGUP_EXC	MESSAGE_PARM4	VARCHAR2(30)	VARCHAR2(2000)
CI_MR_STGUP_EXC	MESSAGE_PARM5	VARCHAR2(30)	VARCHAR2(2000)
CI_MR_STGUP_EXC	MESSAGE_PARM6	VARCHAR2(30)	VARCHAR2(2000)
CI_MR_STGUP_EXC	MESSAGE_PARM7	VARCHAR2(30)	VARCHAR2(2000)
CI_MR_STGUP_EXC	MESSAGE_PARM8	VARCHAR2(30)	VARCHAR2(2000)
CI_MR_STGUP_EXC	MESSAGE_PARM9	VARCHAR2(30)	VARCHAR2(2000)
CI_MR_ST_EXC_VW	MESSAGE_PARM1	VARCHAR2(30)	VARCHAR2(2000)
CI_MR_ST_EXC_VW	MESSAGE_PARM2	VARCHAR2(30)	VARCHAR2(2000)
CI_MR_ST_EXC_VW	MESSAGE_PARM3	VARCHAR2(30)	VARCHAR2(2000)
CI_MR_ST_EXC_VW	MESSAGE_PARM4	VARCHAR2(30)	VARCHAR2(2000)
CI_MR_ST_EXC_VW	MESSAGE_PARM5	VARCHAR2(30)	VARCHAR2(2000)
CI_MR_ST_EXC_VW	MESSAGE_PARM6	VARCHAR2(30)	VARCHAR2(2000)
CI_MR_ST_EXC_VW	MESSAGE_PARM7	VARCHAR2(30)	VARCHAR2(2000)
CI_MR_ST_EXC_VW	MESSAGE_PARM8	VARCHAR2(30)	VARCHAR2(2000)
CI_MR_ST_EXC_VW	MESSAGE_PARM9	VARCHAR2(30)	VARCHAR2(2000)
CI_NT_UP_EXC_VW	MESSAGE_PARM1	VARCHAR2(30)	VARCHAR2(2000)
CI_NT_UP_EXC_VW	MESSAGE_PARM2	VARCHAR2(30)	VARCHAR2(2000)
CI_NT_UP_EXC_VW	MESSAGE_PARM3	VARCHAR2(30)	VARCHAR2(2000)
CI_NT_UP_EXC_VW	MESSAGE_PARM4	VARCHAR2(30)	VARCHAR2(2000)
CI_NT_UP_EXC_VW	MESSAGE_PARM5	VARCHAR2(30)	VARCHAR2(2000)
CI_NT_UP_EXC_VW	MESSAGE_PARM6	VARCHAR2(30)	VARCHAR2(2000)
CI_NT_UP_EXC_VW	MESSAGE_PARM7	VARCHAR2(30)	VARCHAR2(2000)
CI_NT_UP_EXC_VW	MESSAGE_PARM8	VARCHAR2(30)	VARCHAR2(2000)
CI_NT_UP_EXC_VW	MESSAGE_PARM9	VARCHAR2(30)	VARCHAR2(2000)
CI_OD_PROC_LOGPARM	MESSAGE_PARM	VARCHAR2(30)	VARCHAR2(2000)

Table	Column	From	To
CI_PAY_EVT_EXCP	MESSAGE_PARM1	VARCHAR2(30)	VARCHAR2(2000)
CI_PAY_EVT_EXCP	MESSAGE_PARM2	VARCHAR2(30)	VARCHAR2(2000)
CI_PAY_EVT_EXCP	MESSAGE_PARM3	VARCHAR2(30)	VARCHAR2(2000)
CI_PAY_EVT_EXCP	MESSAGE_PARM4	VARCHAR2(30)	VARCHAR2(2000)
CI_PAY_EVT_EXCP	MESSAGE_PARM5	VARCHAR2(30)	VARCHAR2(2000)
CI_PAY_EVT_EXCP	MESSAGE_PARM6	VARCHAR2(30)	VARCHAR2(2000)
CI_PAY_EVT_EXCP	MESSAGE_PARM7	VARCHAR2(30)	VARCHAR2(2000)
CI_PAY_EVT_EXCP	MESSAGE_PARM8	VARCHAR2(30)	VARCHAR2(2000)
CI_PAY_EVT_EXCP	MESSAGE_PARM9	VARCHAR2(30)	VARCHAR2(2000)
CI_PAY_EXCP	MESSAGE_PARM1	VARCHAR2(30)	VARCHAR2(2000)
CI_PAY_EXCP	MESSAGE_PARM2	VARCHAR2(30)	VARCHAR2(2000)
CI_PAY_EXCP	MESSAGE_PARM3	VARCHAR2(30)	VARCHAR2(2000)
CI_PAY_EXCP	MESSAGE_PARM4	VARCHAR2(30)	VARCHAR2(2000)
CI_PAY_EXCP	MESSAGE_PARM5	VARCHAR2(30)	VARCHAR2(2000)
CI_PAY_EXCP	MESSAGE_PARM6	VARCHAR2(30)	VARCHAR2(2000)
CI_PAY_EXCP	MESSAGE_PARM7	VARCHAR2(30)	VARCHAR2(2000)
CI_PAY_EXCP	MESSAGE_PARM8	VARCHAR2(30)	VARCHAR2(2000)
CI_PAY_EXCP	MESSAGE_PARM9	VARCHAR2(30)	VARCHAR2(2000)
CI_PER	EMAILID	VARCHAR2(254)	VARCHAR2(70)
CI_POLICY_LOG_PARM	MESSAGE_PARM	VARCHAR2(30)	VARCHAR2(2000)
CI_QUOTE_RTG	EMAILID	VARCHAR2(254)	VARCHAR2(70)
CI_REBATE_CLAIM_LOG_PARM	MESSAGE_PARM	VARCHAR2(30)	VARCHAR2(2000)
CI_RECON_DTL_LOG_PARAM	MESSAGE_PARM	VARCHAR2(30)	VARCHAR2(2000)
CI_RECON_LOG_PARAM	MESSAGE_PARM	VARCHAR2(30)	VARCHAR2(2000)
CI_REG_DS_EXP	MESSAGE_PARM	VARCHAR2(30)	VARCHAR2(2000)
CI_SS_ADDR_OVRD	EMAILID	VARCHAR2(254)	VARCHAR2(70)
CI_TEMPLATE_LOG_PARM	MESSAGE_PARM	VARCHAR2(30)	VARCHAR2(2000)
CI_TNDR_ST_EXCP	MESSAGE_PARM1	VARCHAR2(30)	VARCHAR2(2000)
CI_TNDR_ST_EXCP	MESSAGE_PARM2	VARCHAR2(30)	VARCHAR2(2000)
CI_TNDR_ST_EXCP	MESSAGE_PARM3	VARCHAR2(30)	VARCHAR2(2000)
CI_TNDR_ST_EXCP	MESSAGE_PARM4	VARCHAR2(30)	VARCHAR2(2000)

Table	Column	From	To
CI_TNDR_ST_EXCP	MESSAGE_PARM5	VARCHAR2(30)	VARCHAR2(2000)
CI_TNDR_ST_EXCP	MESSAGE_PARM6	VARCHAR2(30)	VARCHAR2(2000)
CI_TNDR_ST_EXCP	MESSAGE_PARM7	VARCHAR2(30)	VARCHAR2(2000)
CI_TNDR_ST_EXCP	MESSAGE_PARM8	VARCHAR2(30)	VARCHAR2(2000)
CI_TNDR_ST_EXCP	MESSAGE_PARM9	VARCHAR2(30)	VARCHAR2(2000)
CI_TOU_DS_EXP	MESSAGE_PARM	VARCHAR2(30)	VARCHAR2(2000)
CI_TRL_BILL_EXCP	MESSAGE_PARM1	VARCHAR2(30)	VARCHAR2(2000)
CI_TRL_BILL_EXCP	MESSAGE_PARM2	VARCHAR2(30)	VARCHAR2(2000)
CI_TRL_BILL_EXCP	MESSAGE_PARM3	VARCHAR2(30)	VARCHAR2(2000)
CI_TRL_BILL_EXCP	MESSAGE_PARM4	VARCHAR2(30)	VARCHAR2(2000)
CI_TRL_BILL_EXCP	MESSAGE_PARM5	VARCHAR2(30)	VARCHAR2(2000)
CI_TRL_BILL_EXCP	MESSAGE_PARM6	VARCHAR2(30)	VARCHAR2(2000)
CI_TRL_BILL_EXCP	MESSAGE_PARM7	VARCHAR2(30)	VARCHAR2(2000)
CI_TRL_BILL_EXCP	MESSAGE_PARM8	VARCHAR2(30)	VARCHAR2(2000)
CI_TRL_BILL_EXCP	MESSAGE_PARM9	VARCHAR2(30)	VARCHAR2(2000)
CI_TRL_BILL_MSG_PRM	MSG_PARM_VAL	VARCHAR2(30)	VARCHAR2(2000)
CI_TRL_BSEXCP	MESSAGE_PARM1	VARCHAR2(30)	VARCHAR2(2000)
CI_TRL_BSEXCP	MESSAGE_PARM2	VARCHAR2(30)	VARCHAR2(2000)
CI_TRL_BSEXCP	MESSAGE_PARM3	VARCHAR2(30)	VARCHAR2(2000)
CI_TRL_BSEXCP	MESSAGE_PARM4	VARCHAR2(30)	VARCHAR2(2000)
CI_TRL_BSEXCP	MESSAGE_PARM5	VARCHAR2(30)	VARCHAR2(2000)
CI_TRL_BSEXCP	MESSAGE_PARM6	VARCHAR2(30)	VARCHAR2(2000)
CI_TRL_BSEXCP	MESSAGE_PARM7	VARCHAR2(30)	VARCHAR2(2000)
CI_TRL_BSEXCP	MESSAGE_PARM8	VARCHAR2(30)	VARCHAR2(2000)
CI_TRL_BSEXCP	MESSAGE_PARM9	VARCHAR2(30)	VARCHAR2(2000)
CI_TXN_DETAIL_EXCP	MESSAGE_PARM1	VARCHAR2(30)	VARCHAR2(2000)
CI_TXN_DETAIL_EXCP	MESSAGE_PARM2	VARCHAR2(30)	VARCHAR2(2000)
CI_TXN_DETAIL_EXCP	MESSAGE_PARM3	VARCHAR2(30)	VARCHAR2(2000)
CI_TXN_DETAIL_EXCP	MESSAGE_PARM4	VARCHAR2(30)	VARCHAR2(2000)
CI_TXN_DETAIL_EXCP	MESSAGE_PARM5	VARCHAR2(30)	VARCHAR2(2000)
CI_TXN_DTL_PRITM_SUMMARY	MESSAGE_PARM1	VARCHAR2(30)	VARCHAR2(2000)

Table	Column	From	To
CI_TXN_DTL_PRITM_SUMMARY	MESSAGE_PARM2	VARCHAR2(30)	VARCHAR2(2000)
CI_UPLPAY_STG_ERR	MESSAGE_PARM1	VARCHAR2(30)	VARCHAR2(2000)
CI_UPLPAY_STG_ERR	MESSAGE_PARM2	VARCHAR2(30)	VARCHAR2(2000)
CI_UPLPAY_STG_ERR	MESSAGE_PARM3	VARCHAR2(30)	VARCHAR2(2000)
CI_UPLPAY_STG_ERR	MESSAGE_PARM4	VARCHAR2(30)	VARCHAR2(2000)
CI_UPLPAY_STG_ERR	MESSAGE_PARM5	VARCHAR2(30)	VARCHAR2(2000)
CX_PER	EMAILID	VARCHAR2(254)	VARCHAR2(70)
SC_USER	EMAILID	VARCHAR2(254)	VARCHAR2(70)

A.2 New System Data

The system data is used to configure various features in Oracle Revenue Management and Billing. This section lists the system data that is newly added in the Oracle Revenue Management and Billing V2.5.0.0.0 database.

A.2.1 Algorithm Type

The following algorithm types are newly added in the Oracle Revenue Management and Billing V2.5.0.0.0 database:

Algorithm Type	Description
C1-ADJ-MNTR	Adjustment Upload Request - Monitor Algorithm for Offline Processing
C1-ADJCRTION	Adjustment Creation
C1-ADJUPAPVL	Adjustment Upload Request - Approval
C1-ADJUPLDEF	Adjustment Upload Request - Enter Status Algorithm for Create Adjustment
C1-ADVALREQ	Adjustment Upload Request - Validation
C1-BILLSETT	Stamp Settlement ID on Bill Completion
C1-BILLTOLR	Pre Bill Completion - Bill Tolerance Review
C1-CUSRLALGT	Person to Person Relationship Type Sequence Search
C1-FLREQ-INF	Upload Request Information
C1-IC-AD-XFR	Transfer Adjustments from Usage Account's Contract to Invoice Account's Contract
C1-MD-BILL	Payment Request - Manual Distribution When Match Type is Bill Regular and Bill Weighted
C1-MD-BSEG	Payment Request - Manual Distribution When Match Type is Bill Segment

Algorithm Type	Description
C1-MD-ONSA	Payment Request - Manual Distribution When Match Type is Suspense Contract
C1-MD-SID	Payment Request - Manual Distribution When Match Type is Settlement ID
C1-MTCIALG	Contract ID Match Type
C1-MTCTALG	Contract Type Match Type
C1-PAY-APP	Payment Request - Approval
C1-PAY-COUNT	Payment Request Type - Defer Payment Creation or Transfer
C1-PAY-DFT	Payment Request - Enter Status Algorithm for Draft
C1-PAY-DIST	Payment Request - Defer Payment Creation or Transfer
C1-PAY-MONT	Payment Request - Monitor Algorithm for Offline Processing
C1-PAY-PFA	Payment Request - Create To Do for Approver
C1-PAYCREATE	Payment Request - Create Payment Event
C1-PAYDFTEXT	Payment Request - Exit Status Validation Algorithm for Draft
C1-PAYPFAEXT	Payment Request - User Validation during Approval
C1-PAYREQPOS	Payment Request - Post Processing
C1-PAYREQVAL	Payment Request - Validation
C1-PAYRQ-INF	Payment Request Information
C1-PAYTRANS	Payment Transfer Request - Enter Status Algorithm for Distributing
C1-PDOV-PYSL	OI ONLY! Match by Settlement ID
C1-REQST-INF	Request Information
C1-REQTYPEP	Request Type - Approval Validation (Pre-Processing)
C1-UPLDEFEVL	Defer Adjustment Upload Request
C1_PRDR_PSPC	Transaction Product Derivation - Post-Processing

A.2.2 Algorithm

The following algorithms are newly added in the Oracle Revenue Management and Billing V2.5.0.0.0 database:

Algorithm	Description
C1-ADJ-MNTR	Adjustment Upload Request - Monitor Algorithm for Offline Processing
C1-ADJCRTION	Adjustment Creation
C1-ADJUPAPVL	Adjustment Upload Request - Approval
C1-ADVALREQ	Adjustment Upload Request - Validation

Algorithm	Description
C1-BILLSETT	Stamp Settlement ID on Bill Completion
C1-CUSRELALG	Person to Person Relationship Type Sequence Search
C1-FLREQ-INF	Upload Request Information
C1-GEN-MOERR	Maintenance Object Transition Error Log
C1-GTPRBLME	Fetch Previous Bill Match Event ID for Adjustments
C1-MD-BILL	Payment Request - Manual Distribution When Match Type is Bill Regular and Bill Weighted
C1-MD-BSEG	Payment Request - Manual Distribution When Match Type is Bill Segment
C1-MD-ONSA	Payment Request - Manual Distribution When Match Type is Suspense Contract
C1-MD-SID	Payment Request - Manual Distribution When Match Type is Settlement ID
C1-MTCIALG	Contract ID Match Type
C1-MTCTALG	Contract Type Match Type
C1-PAY-APP	Payment Request - Approval
C1-PAY-COUNT	Payment Request Type - Defer Payment Creation or Transfer
C1-PAY-DFT	Payment Request - Enter Status Algorithm for Draft
C1-PAY-DIST	Payment Request - Defer Payment Creation or Transfer
C1-PAY-MONT	Payment Request - Monitor Algorithm for Offline Processing
C1-PAY-PFA	Payment Request - Create To Do for Approver
C1-PAYCREATE	Payment Request - Create Payment Event
C1-PAYDFTEXT	Payment Request - Exit Status Validation Algorithm for Draft
C1-PAYPFAEXT	Payment Request - User Validation during Approval
C1-PAYREQPOS	Payment Request - Post Processing
C1-PAYREQVAL	Payment Request - Validation
C1-PAYRQ-INF	Payment Request Information
C1-PAYTRANS	Payment Transfer Request - Enter Status Algorithm for Distributing
C1-PDOV-PYSL	OI ONLY! Match by Settlement ID
C1-REQST-INF	Request Information
C1-REQTYPEP	Request Type - Approval Validation (Pre-Processing)
C1-UPLDEFEVL	Defer Adjustment Upload Request
C1_IC-AD-XFR	Transfer Adjustments from Usage Account's Contract to Invoice Account's Contract

Algorithm	Description
C1_PRASN_PP	Price Assignment Search
C1_PRDR_PSPC	Transaction Product Derivation - Post-Processing
C1-ADJUPLDEF	Adjustment Upload Request - Enter Status Algorithm for Create Adjustment

A.2.3 Business Service

The following business services are newly added in the Oracle Revenue Management and Billing V2.5.0.0.0 database:

Business Service	Description
C1-AddAdjUplLog	Adjustment Upload- Add User Log
C1-AddUserPaymentRequestLo	Payment Request - Add User Log
C1-AddUserRequestLog	Request - Add User Log
C1-AdjUplButton	Upload Request - Retrieve Buttons
C1-AdjUploadFileParser	Parsing Adjustment Data File
C1-CheckAutoPaySwitch	Check Auto Pay Switch
C1-EntityIdSearch	Edit Payment Amount - Entity ID Drop-Down
C1-FetchPaymentsForTransfe	Payment Request Transfer - Fetch Payment Event Details
C1-FetchTenderTypeList	Fetch Tender Type List
C1-GenAutoPaySource	Fetch Auto Pay Data
C1-GetAllMoBoStates	Fetch Status of all Business Objects Created for a Maintenance Object
C1-GetFileSize	Request Type File Size
C1-GetReqTypeList	Get Request Type List for a Maintenance Object
C1-MatchTypeSearch	Edit Payment Amount - Match Type Drop-Down
C1-PayReqButton	Retrieve Buttons based on the Payment Request Status
C1-PayTenderIDStatus	Fetch Number of Payments for a Payment Event ID
C1-PaymentAction	Payment Cancel/Delete Action
C1-PaymentCount	Fetch Number of Pending Payment Requests for a Payment Event ID
C1-PaymentEventAction	Payment Event Cancel/Delete Action
C1-PaymentRequestDist	Save Data from the Edit Payment Amount Screen
C1-RetrieveFileUplReqTypes	Fetch Active Upload Request Types
C1-RetrievePayReqTypes	Fetch Active Payment Request Types
C1-RetrieveReqTypes	Fetch Active Request Types

Business Service	Description
C1-RetrieveToDoRoles	Request - Retrieve To Do Roles
C1_PerRelOnDiv	View/Edit Person Relationship Type Seq for Division
C1_PerRelOnDivCheck	Validate Person Relationship Type Seq for Division
C1_PerRelOnPrd	View/Edit Person Relationship Type Seq for Product
C1_PerRelOnPrdCheck	Validate Person Relationship Type Seq for Product
C1_PerRelTypeCdSearch	Person to Person Relationship Type Search

A.2.4 Application Service

The following application services are newly added in the Oracle Revenue Management and Billing V2.5.0.0.0 database:

Application Service	Description
C1-PAY-REQ	Payment Request
C1-REQUEST	Request
C1-REQUEST-TYPE	Request Type
C1ADJSTP	Adjustment Upload Request
C1ADJUPL	Adjustment Upload Request
C1FLRQTY	Upload Request Type
C1PAYREQ	Search Payment Request
C1PAYRQ	Payment Request
C1PAYSRC	Payment Event Summary
C1PYRQTY	Payment Request Type
C1REQSTP	Request
C1REQSTS	Request Query
C1REQTYP	Request Type Portal
C1SETTHR	Settlement Hierarchy
C1UPLREQTYPE	Upload Request Type
C1_DIVPERREL	Person Relationship Type Seq for Division
C1_PERRL	Person to Person Relationship Type Sequence
C1_PRDPERREL	Person Relationship Type Seq for Product
CIDIVPERREL	Person Relationship Type Sequence for Division (BO)
CIDIVPRITMPERREL	Person Relationship Type Sequence for Product (BO)

A.2.5 Batch Control

The following batch controls are newly added in the Oracle Revenue Management and Billing V2.5.0.0.0 database:

Batch Control	Description
C1-FXLG	Foreign Exchange Gain Loss Calculation
C1-PAYRQ	Payment Request Periodic Monitor
C1-UPLRQ	Upload Request Periodic Monitor
C1-ACSSL	Specific Stop Loss Accumulation
C1-ACASL	Accumulate Aggregate Stop Loss
C1-BCSSL	Create Billable Charge for Specific Stop Loss
C1-BCASL	Create Billable Charge for Aggregate Stop Loss Amounts

A.2.6 Foreign Key Reference

The following foreign key references are newly added in the Oracle Revenue Management and Billing V2.5.0.0.0 database:

Foreign Key Reference	Description
C1-FLRQT	Upload Request Type
C1-MTCTY	Match Type
C1-PAYEE	Payee Information
C1-PAYRE	Payment Request
C1-PYRQT	Payment Request Type
C1-REQ	Request
C1-REQTY	Request Type
C1-UPLRQ	Upload Request
DEP_CTL	Deposit Control

A.2.7 Maintenance Object

The following maintenance objects are newly added in the Oracle Revenue Management and Billing V2.5.0.0.0 database:

Maintenance Object	Description
C1-PAYREQ	Payment Request
C1-PAYRQTYPE	Payment Request Type

Maintenance Object	Description
C1-REQ-TYPE	Request Type
C1-REQUEST	Request
C1-TXNCALC	Transaction Product Calculation Details
C1-UPLREQ	Upload Request
C1-UPLREQTYP	Upload Request Type
C1_DIVPERREL	Person to Person Relationship Type Sequence for Division
C1_PRDPERREL	Person to Person Relationship Type Sequence for Product
ACCUM_GROUP	Accumulation Group

A.2.8 Business Object

The following business objects are newly added in the Oracle Revenue Management and Billing V2.5.0.0.0 database:

Business Object	Description
C1-ADJUPLD	Adjustment Upload Request
C1-AdjRequestType	Upload Request Type
C1-PayRequestType	Payment Request Type
C1-PaymentRequest	Payment Request
C1-PaymentTransferRequest	Payment Transfer Request
C1-Request	Request
C1-RequestType	Request Type
C1-RequestWithCharCollection	Request with Char Collection
C1_DIVPERREL_BO	Person to Person Relationship Type Sequence for Division
C1_PRDPERREL_BO	Person to Person Relationship Type Sequence for Product
C1-AccumulationGroup	Accumulation Group

A.2.9 Script

The following scripts are newly added in the Oracle Revenue Management and Billing V2.5.0.0.0 database:

Script	Description
C1-AddAdjLog	Upload Request - Add User Log Entry
C1-AddReqLog	Request - Add User Log Entry

Script	Description
C1-AdjUpFI	Upload Adjustment Data File
C1-EditDist	Payment Request - Edit Payment Amount
C1-FIRqInfo	Generate Upload Request Information String
C1-FIRqTyLst	Upload Request - Fetch Active Request Types
C1-FIRqTyMnt	Upload Request Type - Maintain
C1-FIRqTyV	Upload Request - Validate Request Type
C1-PAYSRCBUT	Payment Event Summary - Show/Hide Buttons
C1-PayAction	Payment Event Summary - Payment Actions
C1-PayEvtAct	Payment Event Action
C1-PayEvtSrc	Payment Event - View Details
C1-PayReqLog	Payment Request - Add User Log Entry
C1-PayReqTyV	Payment Request - Validate Request Type
C1-PayReqTyp	Payment Request Type - Maintain
C1-PayRqInfo	Generate Payment Request Information String
C1-PayRqMain	Payment Request - Maintain
C1-PayRqTrsf	Payment Transfer Request - Maintain
C1-PayRqTyLi	Payment Request - Fetch Active Payment Request Types
C1-ReqInform	Request - Information
C1-ReqTyList	Request Type - Build Active Request Type List
C1-ReqTyMain	Request Type - Maintain
C1-ReqTyV	Request - Validate Request Type
C1-ReqstMain	Request - Maintain
C1-SelFIRqTy	Upload Request - Select Request Type
C1-SelPyRqTy	Payment Request - Select Request Type
C1-SelReqTyp	Request Type - Select Request Type
C1-UpIRqMain	Upload Request - Maintain
C1-VAL-VIEW	Validation Script for View Type
C1_ACCASGN	Copy Price Assignment of Account - Criteria Validation
C1_CUSTASGN	Copy Price Assignment of Customer - Criteria Validation
C1_DIVPERREL	Add/Edit/Delete Person to Person Relationship Type Sequence for Division

Script	Description
C1_PLASGN	Copy Price Assignment of Price List - Criteria Validation
C1_PRDPERREL	Add/Delete Person to Person Relationship Type Sequence for Product
C1_PRDPERRLE	Edit/View Person to Person Relationship Type Sequence for Product
C1_PRDPPV	Display Data in the Product Parameters Screen
C1_PRRELSRCH	Relationship Type Sequence - Minimum One Search Criteria Validation
C1_VAL_SACCT	Validation while Searching a Construct
C1_VAL_SCUST	Validation while Viewing Settlement Hierarchy

A.2.10 To Do Type

The following To Do types are newly added in the Oracle Revenue Management and Billing V2.5.0.0.0 database:

To Do Type	Description
C1-ADJUP	Upload Request Approval
C1-PAYRQ	Payment Request Approval

A.2.11 Portal

The following portals are newly added in the Oracle Revenue Management and Billing V2.5.0.0.0 database:

Portal	Description
C1ADJLGTB	Adjustment Upload Request Log
C1ADJSTP	Adjustment Upload Request
C1ADJUPL	Adjustment Upload Request
C1FLRQTY	Upload Request Type
C1PAYREQ	Payment Request
C1PAYRQ	Payment Request
C1PAYRQLOG	Payment Request Log
C1PAYSRC	Payment Event Summary
C1PYRQTY	Payment Request Type
C1REQLGTB	Request Log
C1REQSTP	Request
C1REQSTS	Request Query

Portal	Description
C1REQTYP	Request Type
C1SETTHR	Settlement Hierarchy
C1_PERRL	Person to Person Relationship Type Sequence

A.2.12 Zone

The following zones are newly added in the Oracle Revenue Management and Billing V2.5.0.0.0 database:

Zone	Description
C1-ADJUPDTL	Adjustment Data Records
C1-ADJUPL	Adjustment Upload Request
C1-ADJUPLLOG	Upload Request Log
C1-ADJUPLS1	Upload Request
C1-ADJUPLSRC	Search Adjustment Upload Request
C1-APAYCHECK	Check Auto Pay Switch
C1-APAYSRCCD	Search Auto Pay Source Code
C1-CHECKAPAY	Check Auto Pay Switch
C1-ENTIDSRCH	Edit Payment Amount - Entity ID Drop-Down
C1-FETCHPAY	Fetch Payments of a Payment Event
C1-FLREQTY	Upload Request Type
C1-FLRQTYLT	Upload Request Type List
C1-FMFLDSRCH	Search Temporary Field
C1-FMTEMPFLD	Temporary Field Name/Description
C1-GETFILESI	Request Type File Size
C1-MOBOSTATS	Fetch Status of all Business Objects Created for a Maintenance Object
C1-MTCTYPSRC	Edit Payment Amount - Match Type Drop-Down
C1-PAYCNT	Payment Count
C1-PAYDIST	Payment Distribution
C1-PAYMENTS	Payments
C1-PAYREQ	Payment Request
C1-PAYREQLOG	Payment Request Log

Zone	Description
C1-PAYREQSRC	Payment Request Query
C1-PAYREQTY	Payment Request Type List
C1-PAYREQTYD	Payment Request Type
C1-PAYRQSRC	Search Payment Request
C1-PAYRQSRC1	Request Details
C1-PAYRQSRC2	Payment Details
C1-PAYSRCH	Search Payment Event
C1-PAYSRCH1	Payor Account/Payment Event
C1-PAYSRCH2	Tender Details
C1-REQSRCH	Request Search
C1-REQSRCH1	Create Date / Request Type / Status
C1-REQSRCH2	Request Type / User
C1-REQSRCH3	Related Object
C1-REQTYLIST	Request Type List
C1-REQTYLST	Retrieve Request Type list (code + description)
C1-REQTYPE	Request Type
C1-REQUEST	Request
C1-REQUESTLOG	Request Log
C1-RETFLRQTY	Active Upload Request Types
C1-RETPYRQTY	Active Payment Request Types
C1-RETREQTYS	Active Request Types
C1-RETTDRL	To Do Roles
C1-TDTYSRCH	Search To Do Type
C1-TDTYSRCH1	Search by To Do Type
C1-TENDERDTL	Fetch Tender ID and Tender Status
C1-TENDERS	Tender Type Details
C1_ASTOAC_A	Price Assignment of an Account
C1_ASTOAC_AV	Price Assignment of an Account
C1_ASTOAC_C	Price Assignment of a Customer
C1_ASTOAC_CV	Price Assignment of a Customer

Zone	Description
C1_ASTOAC_P	Price Assignment of a Price List
C1_ASTOAC_PV	Price Assignment of a Price List
C1_ASTOCU_A	Price Assignment of an Account
C1_ASTOCU_AV	Price Assignment of an Account
C1_ASTOCU_C	Price Assignment of a Customer
C1_ASTOCU.CV	Price Assignment of a Customer
C1_ASTOCU_P	Price Assignment of a Price List
C1_ASTOCU_PV	Price Assignment of a Price List
C1_ASTOPL_A	Price Assignment of an Account
C1_ASTOPL_AV	Price Assignment of an Account
C1_ASTOPL_C	Price Assignment of a Customer
C1_ASTOPL.CV	Price Assignment of a Customer
C1_ASTOPL_P	Price Assignment of a Price List
C1_ASTOPL_PV	Price Assignment of a Price List
C1_DIVRLSEQ	Search Person Relationship Type Sequence for Division
C1_FEED_N2	Transaction Product Information
C1_FEED_N3	Transaction Product Calculation Details
C1_FEED_N4	Transaction Product Service Quantity
C1_FEED_N5	Transaction Product Calculation Lines
C1_FEED_N6	Transaction Product Calculation Line Characteristics
C1_PERRELTYPE	Search Person Relationship Type
C1_PERRLSEQ	Search Person Relationship Type Sequence for Product
C1_SETTACCT	Settlement Hierarchy - Search Using Account
C1_SETTCUST	Settlement Hierarchy - Search Using Customer
C1_SETTHIER	Search Settlement Accounts
C1_SETT_INFO	Settlement Information
C1_SRHTOCAY	Search Price Assignment to Copy
C1_SRHTOCAYV	Search Price Assignment to Copy
C1_SRHTOCCY	Search Price Assignment to Copy
C1_SRHTOCCYV	Search Price Assignment to Copy

Zone	Description
C1_SRHTOCPY	Search Price Assignment to Copy
C1_SRHTOCPYV	Search Price Assignment to Copy

A.2.13 UI Map

The following UI maps are newly added in the Oracle Revenue Management and Billing V2.5.0.0.0 database:

UI Map	Description
C1-AddUserAdjUplLog	Upload Request - Add User Log Entry
C1-AddUserPaymentRequestLog	Payment Request - Add User Log Entry
C1-AddUserRequestLog	Request- Add User Log Entry
C1-AdjReqCheckboxesDispFrg	Upload Request Type - Check Boxes (Display UI)
C1-AdjReqCheckboxesMainFrg	Upload Request Type - Check Boxes (Input UI)
C1-AdjUplCancelReason	Upload Request - Cancellation Reason
C1-AdjUplFile	Adjustment Upload Data File
C1-AdjUplRejectReason	Upload Request - Rejection Reason
C1-AdjUplSearch	Search Upload Request
C1-AdjUploadBOJScriptFrag	Upload Request - Show/Hide Business Object Status Actions
C1-BillSegmentSelCriteria	Bill Segment Selection Criteria
C1-ConfirmDeletePayment	Confirm Payment Deletion
C1-ConstructPurposeSelect	Select Construct Purpose
C1-EditPayDistributionDetails	Payment Request - Edit Payment Amount
C1-FileUplReqTypeCharMaintFrag	Upload Request Type Characteristics - Maintenance Fragment
C1-FileUplReqTypeCharsDispFrag	Upload Request Type Characteristics - Display Fragment
C1-PayReqTypeCharsDispFrag	Payment Request Type Characteristics - Display Fragment
C1-PayReqTypeCharsMaintFrag	Payment Request Type Characteristics - Maintenance Fragment
C1-PayRequestSrchFilter1	Payment Request Search - Create Date / Request Type / Status / User
C1-PaymentBOJScriptFrag	Payment Request - Show/Hide Business Object Status Actions
C1-PaymentDetailsDisplay	Payment Request - Payment Details (Display UI)
C1-PaymentDetailsInput	Payment Request - Payment Details (Input UI)

UI Map	Description
C1-PaymentMatchTypesDisplay	Payment Match Types (Display UI)
C1-PaymentMatchTypesInput	Payment Match Types (Input UI)
C1-PaymentReqCheckBoxesDispFrg	Payment Request Type - Check Boxes (Display UI)
C1-PaymentReqCheckBoxesMainFrg	Payment Request Type - Check Boxes (Input UI)
C1-PayorInfoDisplay	Payment Request – Pay or Information (Display UI)
C1-RequestCharacteristicsDpFrg	Request Characteristics - Display Fragment
C1-RequestCharacteristicsFrag	Request Characteristics - Maintenance Fragment
C1-RequestSearchFilter1	Request Search Filter - Create Date / Request Type / Status
C1-RequestSearchFilter2	Request Search Filter - Create Date / Person / Account
C1-RequestTypeCharsDispFrag	Request Type Characteristics - Display Fragment
C1-RequestTypeCharsMaintFrag	Request Type Characteristics - Maintenance Fragment
C1-SelFileUploadReqType	Upload Request - Select Request Type
C1-SelectPaymentRequestType	Payment Request - Select Payment Request Type
C1-SelectRequestType	Request Type - Select Request Type
C1-SingleTenderDisplay	Payment Tender Display UI
C1-SingleTenderInput	Payment Tender Input UI
C1-StatusReasonInput	State Transition - Status Reason
C1-TenderCharDispFrag	Tender Characteristics - Display Fragment
C1-TenderCharMaintFrag	Tender Characteristics - Maintenance Fragment
C1-TenderCharTypeInfo	Tender Characteristic Type Information
C1-ToDoTypeSearch	Search by To Do Type
C1_ACASRH	Search Price Assignment from an Account
C1_ADD_DIVPERREL	Add Person Relationship Type Sequence for Division
C1_ADD_PRDPERREL	Add Person Relationship Type Sequence for Product
C1_CUSASRH	Search Price Assignment from a Customer
C1_DIVREL	Search Person Relationship Type Sequence for Division
C1_PLASRH	Search Price Assignment from a Price List
C1_PRODREL	Search Person Relationship Type Sequence for Product
C1_ViewSettHier_Acct	Settlement Hierarchy - Search Using Account
C1_ViewSettHier_Cust	Settlement Hierarchy - Search Using Customer

A.2.14 Lookup

The following lookups are newly added in the Oracle Revenue Management and Billing V2.5.0.0.0 database:

Field	Field Value	Description
ADJ_MATCH_TYPE	CNTY	Contract Type
	CONT	Contract
ATY_ALG_ENTITY_FLG	ADCA	Adjustment Cancellation
	ADFR	Adjustment Freeze
	ADJG	Generate Adjustment
	ADJT	Adjustment Financial Transaction
	APFR	Post Adjustment Freeze
	C1AR	Resolve Suspense
	C1AS	Determine Contract
	C1AT	Adjustment Information
	C1VA	Validate Adjustment
	DAMT	Default Adjustment Amount
C1_INPUT_OUTPUT_TYPE	B	Input and Output
	I	Input
	O	Output
C1_REQ_REL_OBJ_TYPE_FLG	C1AC	Account
	C1PR	Person
CONV_TYPE_FLG	FERR	Ferris
	RGLR	Regular
IN_OT_SW_VALUE	B	Input and Output
	I	Input
	O	Output
MATCH_TYPE_ENTITY_FLG	BILL	Bill
	BSEG	Bill Segment
	SA	Contract
	SETT	Settlement

Field	Field Value	Description
PAYP_OPT_TYP_FLG	BILL	FK Reference for Bill
	BSEG	FK Reference for Bill Segment
	OVPY	Allow Overpayment
	SA	FK Reference for Contract
PL_STATUS_FLG	ACTV	Active
	PRPD	Proposed
	TMPL	Template
PRICE_STATUS_FLG	ACTV	Active
	INAC	Inactive
	PRPD	Proposed
	REJT	Rejected
	TMPL	Template
RULE_CRT_OPR_FLG	<	<
	<=	<=
	<>	<>
	=	=
	>	>
	>=	>=
	ALG	Algorithm
	BETW	Between
	IN	In
	LIKE	Like
SETT_TYPE_FLG	SETL	Settlement
	USIV	Usage or Invoice
TEMPLATE_PURPOSE_FLG	ACTS	Usage Account Selection
	ADJT	Adjustment Selection
	BICS	Billable Charge Selection
	BLSG	Bill Segment Selection
	UIAS	Usage and Invoice Account Selection

Field	Field Value	Description
TXN_RATING_CRITERIA_LOOKUP	AGTR	Aggregate Transactions and Rate Aggregated Service Quantities
	DNRT	Do Not Rate Transactions
	RITA	Rate Individual Transaction and Aggregate Calculation Lines
TXN_RATING_CRITERIA_LOOKUP1	DNRT	Do Not Rate Transactions
	RITX	Rate Transactions
LASER_EXCLUSION_CRIT	MEMB	Member
	SUBS	Subscriber
	TXID	Tax ID
ACCUM_STATUS	ACTV	Active
	STLD	Completed
ACCUM_TYPE	ASL	Aggregate Stop Loss
	SSL	Specific Stop Loss
SETTLEMENT_FREQUENCY_FLG	ANNL	Annual
	IMMD	Immediate
	NEVR	Never
LASER_EXCLUSION_TYPE	EXCL	Exclusion
	LASR	Lasering
HCC_CD	DN	Dental
	HT	Human Organ/Tissue Transplant
	MD	Medical
	MH	Mental Health
	RX	Drug
	VS	Vision
ACCUM_OPTION	MEMB	Member
	SUBS	Subscriber

Appendix B : New Objects in the Oracle Utilities Application Framework V4.3.0.0.1 Database

This section lists the objects that are newly added in the Oracle Utilities Application Framework V4.3.0.0.1 database. These objects are classified under the following two sections:

- Schema Changes
- New System Data

B.1 Schema Changes

This section lists schema related changes made in the Oracle Utilities Application Framework V4.3.0.0.1 database.

B.1.1 New Tables

The following tables are newly added in the Oracle Utilities Application Framework V4.3.0.0.1 database:

Table	Description
CI_PORTAL_OPT	Portal Option
CI_USR_BOOKMARK	User Bookmarks
CI_USR_ZONE_SAVE	User Zone Save
F1_REQ_CHAR	Request Characteristics

B.1.2 New Views

None

B.1.3 Dropped Tables

None

B.1.4 Unsupported Tables

None

B.1.5 Added Columns

The following columns are newly added in the Oracle Utilities Application Framework V4.3.0.0.1 database:

Table	Column	Required (Yes or No)
CI_SCR_L	DESCR4000	Y
CI_NAV_OPT	MULTI_QUERY_ZONE_CD	N
CI_NAV_OPT	SUB_QUERY_ZONE_CD	N
CI_SCR_L	DESCR4000	N
CI_ZONE_L	DESCR_OVRD	N
F1_OBJ_REV	ILM_ARCH_SW	N
F1_OBJ_REV	ILM_DT	N
F1_OUTMSG	ILM_ARCH_SW	N
F1_OUTMSG	ILM_DT	N
F1_SVC_TASK	ILM_ARCH_SW	N
F1_SVC_TASK	ILM_DT	N
F1_SYNC_REQ	ILM_ARCH_SW	N
F1_SYNC_REQ	ILM_DT	N
F1_SYNC_REQ_IN	ILM_ARCH_SW	N
F1_SYNC_REQ_IN	ILM_DT	N

B.1.6 Dropped Columns

None

B.1.7 Unsupported Table Columns

None

B.1.8 Column Format Change

The format of the following columns is changed in the Oracle Utilities Application Framework V4.3.0.0.1 database:

Table	Column	From	To
CI_MSG_LOGPARM	MESSAGE_PARM	VARCHAR2(30)	VARCHAR2(2000)
CI_NT_DWN_EXP	MESSAGE_PARM	VARCHAR2(30)	VARCHAR2(2000)
CI_NT_UP_EXCP	MESSAGE_PARM1	VARCHAR2(30)	VARCHAR2(2000)

Table	Column	From	To
CI_NT_UP_EXCP	MESSAGE_PARM2	VARCHAR2(30)	VARCHAR2(2000)
CI_NT_UP_EXCP	MESSAGE_PARM3	VARCHAR2(30)	VARCHAR2(2000)
CI_NT_UP_EXCP	MESSAGE_PARM4	VARCHAR2(30)	VARCHAR2(2000)
CI_NT_UP_EXCP	MESSAGE_PARM5	VARCHAR2(30)	VARCHAR2(2000)
CI_NT_UP_EXCP	MESSAGE_PARM6	VARCHAR2(30)	VARCHAR2(2000)
CI_NT_UP_EXCP	MESSAGE_PARM7	VARCHAR2(30)	VARCHAR2(2000)
CI_NT_UP_EXCP	MESSAGE_PARM8	VARCHAR2(30)	VARCHAR2(2000)
CI_NT_UP_EXCP	MESSAGE_PARM9	VARCHAR2(30)	VARCHAR2(2000)
CI_ROOT_OBJ_EXP	MESSAGE_PARM	VARCHAR2(30)	VARCHAR2(2000)
CI_TD_MSG_PARM	MSG_PARM_VAL	VARCHAR2(30)	VARCHAR2(2000)
CI_VAL_ERR	MESSAGE_PARM1	VARCHAR2(30)	VARCHAR2(2000)
CI_VAL_ERR	MESSAGE_PARM2	VARCHAR2(30)	VARCHAR2(2000)
CI_VAL_ERR	MESSAGE_PARM3	VARCHAR2(30)	VARCHAR2(2000)
CI_VAL_ERR	MESSAGE_PARM4	VARCHAR2(30)	VARCHAR2(2000)
CI_VAL_ERR	MESSAGE_PARM5	VARCHAR2(30)	VARCHAR2(2000)
CI_VAL_ERR	MESSAGE_PARM6	VARCHAR2(30)	VARCHAR2(2000)
CI_VAL_ERR	MESSAGE_PARM7	VARCHAR2(30)	VARCHAR2(2000)
CI_VAL_ERR	MESSAGE_PARM8	VARCHAR2(30)	VARCHAR2(2000)
CI_VAL_ERR	MESSAGE_PARM9	VARCHAR2(30)	VARCHAR2(2000)
CI_WF_EVT_EXP	MESSAGE_PARM	VARCHAR2(30)	VARCHAR2(2000)
CI_WF_PROC_MSGP	MESSAGE_PARM	VARCHAR2(30)	VARCHAR2(2000)
CI_XAI_DWN_EXP	MESSAGE_PARM	VARCHAR2(30)	VARCHAR2(2000)
CI_XML_STGUPEXP	MESSAGE_PARM	VARCHAR2(30)	VARCHAR2(2000)
F1_BNDL_LOG_PARM	MSG_PARM_VAL	VARCHAR2(30)	VARCHAR2(2000)
F1_BUS_EVT_LOG_MSG_P	MSG_PARM_VAL	VARCHAR2(30)	VARCHAR2(2000)
F1_FACT_LOG_PARM	MSG_PARM_VAL	VARCHAR2(30)	VARCHAR2(2000)
F1_IWS_SVC_LOG_PARM	MSG_PARM_VAL	VARCHAR2(30)	VARCHAR2(2000)
F1_MIGR_DATA_ST_LOG_PARM	MSG_PARM_VAL	VARCHAR2(30)	VARCHAR2(2000)
F1_MIGR_OBJ_LOG_PARM	MSG_PARM_VAL	VARCHAR2(30)	VARCHAR2(2000)
F1_MIGR_TRANS_LOG_PA	MSG_PARM_VAL	VARCHAR2(30)	VARCHAR2(2000)
F1_OBJ_REV_LOG_PARM	MSG_PARM_VAL	VARCHAR2(30)	VARCHAR2(2000)

Table	Column	From	To
F1_OUTMSG_ERRPARM	MSG_PARM_VAL	VARCHAR2(30)	VARCHAR2(2000)
F1_REQ_LOG_PARM	MSG_PARM_VAL	VARCHAR2(30)	VARCHAR2(2000)
F1_REQ_TYPE_LOG_PARM	MSG_PARM_VAL	VARCHAR2(30)	VARCHAR2(2000)
F1_SVC_TASK_LOG_PARM	MSG_PARM_VAL	VARCHAR2(30)	VARCHAR2(2000)
F1_SYNC_REQ_IN_EXCP_PARM	MSG_PARM_VAL	VARCHAR2(30)	VARCHAR2(2000)
F1_SYNC_REQ_IN_LOG_P	MSG_PARM_VAL	VARCHAR2(30)	VARCHAR2(2000)
F1_SVC_TASK_LOG_PARM	MSG_PARM_VAL	VARCHAR2(30)	VARCHAR2(2000)
F1_WEB_SVC_LOG_PARM	MSG_PARM_VAL	VARCHAR2(30)	VARCHAR2(2000)

B.2 New System Data

The system data is used to configure various features in Oracle Revenue Management and Billing. This section lists the system data that is newly added in the Oracle Utilities Application Framework V4.3.0.0.1 database.

B.2.1 Algorithm Type

The following algorithm types are newly added in the Oracle Utilities Application Framework V4.3.0.0.1 database:

Algorithm Type	Description
F1-ILMELIG	ILM Eligibility Based on Status
F1-VALIDOWNR	Extendable Lookup - Validate Owner

B.2.2 Algorithm

The following algorithms are newly added in the Oracle Utilities Application Framework V4.3.0.0.1 database:

Algorithm	Description
F1-ILMELIG	ILM Eligibility Based on Status
F1-VALIDOWNR	Extendable Lookup - Validate Owner

B.2.3 Application Service

The following application services are newly added in the Oracle Utilities Application Framework V4.3.0.0.1 database:

Application Service	Description
F1-BOOKMARKS	Bookmarks

Application Service	Description
F1ANNTYP	Web Service Annotation Type MO
F1_USRFAVSCH	Favorite Searches Zone

B.2.4 Access Mode Added to Application Service

The access modes are added to the following application services in the Oracle Utilities Application Framework V4.3.0.0.1 database:

Application Service	Description
F1IWSDPLY	Inbound Web Service DeploymentExecute(F1EX)

B.2.5 Batch Control

The following batch controls are newly added in the Oracle Utilities Application Framework V4.3.0.0.1 database:

Batch Control	Description
F1-ILMIN	ILM Crawler Initiator
F1-ORCRL	ILM Crawler - Object Revision
F1-OUCRL	ILM Crawler - Outbound Message
F1-SICRL	ILM Crawler - Inbound Sync Request
F1-SRCRL	ILM Crawler - Sync Request
F1-STCRL	ILM Crawler - Service Task
F1-TDCRL	ILM Crawler - To Do Entry

B.2.6 Business Object

The following business objects are newly added in the Oracle Utilities Application Framework V4.3.0.0.1 database:

Business Object	Description
F1-DeviceDisplayTypes	UI Device Display Types
F1-ILMMSConfig	ILM Configuration

B.2.7 FK Reference

The following foreign key references are newly added in the Oracle Utilities Application Framework V4.3.0.0.1 database:

FK Reference	Description
F1-TODO	To Do Entry
F1PA-PO	Portal Option - Page Actions Menu
F1PK-PO	Portal Option - Page Info FK Reference
FIBC-MO	MO Option - Batch Control ILM

B.2.8 Lookups

The following lookups are newly added in the Oracle Utilities Application Framework V4.3.0.0.1 database:

Lookup Field Name	Field Value	Language	Description
ALG_ENTITY_FLG	F1CZ	ENG	Zone
ALG_ENTITY_FLG	F1GD	ENG	Installation – Guaranteed Delivery
ALG_ENTITY_FLG	F1LR	ENG	Deprecated Value - Do not use
BO_OPT_FLG	F1AT	ENG	Allow Manual Monitor
CHAR_ENTITY_FLG	F1RQ	ENG	Request
F1_BATCH_CTGY_FLG	F1IL	ENG	ILM
F1_CAL_ITEM_TYP_CLR	BL	ENG	LightSkyBlue
F1_CAL_ITEM_TYP_CLR	GL	ENG	Gold
F1_CAL_ITEM_TYP_CLR	GR	ENG	PaleGreen
F1_CAL_ITEM_TYP_CLR	RD	ENG	Pink
F1_IWS_TRANS_TYPE_FLG	ADD	ENG	Add
F1_IWS_TRANS_TYPE_FLG	DELT	ENG	Delete
F1_IWS_TRANS_TYPE_FLG	READ	ENG	Read
F1_IWS_TRANS_TYPE_FLG	UPDT	ENG	Update
INS_ALG_ENTITY_FLG	F1GD	ENG	Guaranteed Delivery
MAINT_OBJ_OPT_FLG	FIRB	ENG	ILM Restrict By BO Final Status
MENU_TYPE_FLG	PGAT	ENG	Page Action Menu
MENU_TYPE_FLG	TBAR	ENG	Toolbar
MENU_TYPE_FLG	USRM	ENG	User Menu

Lookup Field Name	Field Value	Language	Description
NAV_OPT_TYPE_FLG	F1IF	ENG	Internal Function
PORTAL_OPT_FLG	F1PA	ENG	Page Action Menu
PORTAL_OPT_FLG	F1PK	ENG	Page Info FK Reference

B.2.9 Maintenance Object

None

B.2.10 Script

The following scripts are newly added in the Oracle Utilities Application Framework V4.3.0.0.1 database:

Script	Description
F1-IlmDisp	ILMMasterConfigurationDisplayDetails
F1-IlmMstCfg	Master Configuration - Maintain
F1-ReqMain	Request - Maintain
F1-ValidOwnr	Extendable Lookup - Validate Owner

B.2.11 To Do Type

None

B.2.12 Portal

None

B.2.13 Portal Zone

The following portal zones are newly added in the Oracle Utilities Application Framework V4.3.0.0.1 database:

Portal	Zone
CI_DASHBOARD	F1-BOOKMARKS

B.2.14 UI Map

The following UI maps are newly added in the Oracle Utilities Application Framework V4.3.0.0.1 database:

UI Map	Description
F1-BookmarkPopup	Bookmark Popup
F1-DisplayBookmarks	Display Bookmarks

UI Map	Description
F1-GenerateBsSchemaContext	Generate a Business Service Schema

B.2.15 XAI Inbound Service

None

B.2.16 Zone Type

The following zone types are newly added in the Oracle Utilities Application Framework V4.3.0.0.1 database:

Zone Type	Description
F1-Calendar	Calendar

B.2.17 Zone

The following zones are newly added in the Oracle Utilities Application Framework V4.3.0.0.1 database:

Zone	Zone Type	Description
F1-BOOKMARKS	F1-MAPEXPL	Bookmarks
F1-GENBSCHM	F1-MAPEXPL	Generate Schema
F1-GETBKMRKS	F1-DE-SINGLE	Get Bookmarks
F1-USRFAVSCH	F1-DE-SINGLE	Retrieve User's Favorite Searches

Appendix C : Oracle Application Framework System Table Guide

This section lists the system tables owned by the Oracle Utilities Application Framework V4.3.0.0.1 and explains the data standards of the system tables. The data standards are required for the installation of Oracle Utilities Application Framework, development within the Oracle Utilities Application Framework, and the configuration and customization of Oracle Utilities products. Adhering to the data standards is a prerequisite for seamless upgrade to future releases.

This section includes:

- About the Application Framework System Tables
- System Table Standards
- Guidelines for System Table Updates
- System Table List

C.1 About the Application Framework System Tables

System tables are a subset of the tables that must be populated at the time the product is installed. They include Metadata and configuration tables. The data stored in the system tables are the information that Oracle Utilities Application Framework product operations are based on.

As the product adds more functionality, the list of system tables can grow. The complete list of the system tables can be found in the System Table List section.

C.2 System Table Standards

System table standards must be observed for the following reasons:

- The product installation and upgrade process and customer modification data extract processes depend on the data prefix and owner flag values to determine the system data owned by each product.
- The standards ensure that there will be no data conflict in the product being developed and the future Oracle Utilities Application Framework release.
- The standards ensure that there will be no data conflict between customer modifications and future Oracle Utilities product releases.
- The data prefix is used to prevent test data from being released to production.

Developer's Note: All test data added to the system data tables must be prefixed by ZZ (all upper case) in order for the installation and upgrade utility to recognize them as test data.

C.3 Guidelines for System Table Updates

This section describes guidelines regarding the updating of the system table properties.

C.3.1 Business Configuration Tables

The majority of data in the tables in this group belongs to the customer. But these tables are shipped with some initial data in order for the customer to login to the system and begin configuring the product. Unless specified otherwise, the initial data is maintained by Oracle Utilities Application Framework and subject to subsequent upgrade.

C.3.1.1 Application Security and User Profile

These tables define the access rights of a User Group to Application Services and Application Users.

Properties	Description
Tables	SC_ACCESS_CNTL, SC_USER, SC_USR_GRP_PROF, SC_USR_GRP_USR, SC_USER_GROUP, SC_USER_GROUP_L
Initial Data	User Group All SERVICES and default system user SYSUSER. Upon installation the system default User Group All SERVICES is given unrestricted accesses to all services defined in Oracle Utilities Application Framework.

Developer's Note: When a new service is added to the system, all actions defined for the service must be made available to the User Group All SERVICES.

C.3.1.2 Currency Code

The ISO 4217 three-letter codes are taken as the standard code for the representation of each currency.

Properties	Description
Tables	CI_CURRENCY_CD, CI_CURRENCY_CD_L
Initial Data	United States Dollar (USD).

C.3.1.3 DB Process

Properties	Description
Tables	CI_DB_PROC, CI_DB_PROC_L, CI_DB_INSTR, CI_DB_INSTR_L, L, CI_DB_INSTR_OVRD
Initial Data	Copy DB Process (CL-COPDB). This DB process allows users to copy a DB process from one database to another using Config Lab utility.

C.3.1.4 Display Profile

The Display Profile Code is referenced in the User (SC_USER) table.

Properties	Description
Tables	CI_DISP_PROF, CI_DISP_PROF_L
Initial Data	North America (NORTHAM), HIJRI Format (HIJRI) and Europe (EURO).

Configuration Note: In order to use HIJRI Format display profile, additional configuration is needed to define the mappings between Hijri and Gregorian dates. Refer to the Display Profile documentation for more information.

C.3.1.5 Installation Options

Installation Option has only one row that is shipped with the initial installation of the Oracle Utilities Application Framework. The updatable columns in these tables are customer data and will not be overridden by the upgrade process unless a special script is written and included in the upgrade process.

Properties	Description
Tables	F1_INSTALLATION, CI_INSTALL_ALG, CI_INSTALL_MSG, CI_INSTALL_MSG_L, CI_INSTALL_PROD
Initial Data	Option 11111.

Developer's Note: The system data owner of an environment is defined in the Installation Option. This Owner Flag value is stamped on all system data that is added to this environment. The installation default value is Customer Modification (CM). This value must be changed in the base product development environments.

C.3.1.6 Language Code

Language Code must be a valid code defined in ISO 639-2 Alpha-3. Adding a new language code to the table without translating all language dependent objects in the system can cause errors when a user chooses the language.

Properties	Description
Tables	CI_LANGUAGE
Initial Data	English (ENG).

C.3.1.7 To Do Priority and Role

New To Do Types released will be linked to the default To Do Role and set to the product assigned priority value initially. These initial settings can be overridden by the implementation.

Properties	Description
Tables	CI_ROLE(L), CI_TD_VAL_ROLE
Initial Data	F1_DFLT

C.3.2 Development and Implementation System Tables

This section defines the standards for the system tables that contain data for application development. The data in these tables implement business logic and UI functions shared by various products and product extensions in the same database.

C.3.2.1 Standards

When adding new data, the owner flag value of the environment must prefix certain fields of these tables. For example, when a developer adds a new algorithm type to an <Product Name> environment, C1 should prefix the new Algorithm Type code. The fields that are subject to this rule are listed in Standard Data Fields property.

The data that is already in these tables cannot be modified if the data owner is different than the environment owner. This prevents the developers from accidentally modifying system data that belongs to the Oracle Utilities Application Framework or the base products. However, some fields are exempt from this rule and can be modified by Customer Modification. These fields are listed in the Customer Modification Fields property.

Note that the system supports a system upgrade rule called Override Owner flag. If duplicate data rows (data row with same primary key values) are found at the time of upgrade, the owner flag values will get overridden. The lower level application system data will override the upper level system data. For example, F1 overrides C1, F1&C1 override CM, and so on. This rule will be applied to the following tables: CI_CHAR_ENTITY, CI_MD_MO_ALG, C1_PORTAL_OPT, F1_BUS_OBJ_ALG, F1_BUS_OBJ_STATUS_ALG, CI_MD_MO_OPT, F1_BUS_OBJ_OPT, F1_BUS_OBJ_STATUS_OPT, F1_BUS_OBJ_STATUS, and F1_BUS_OBJ_STATUS_L.

C.3.2.2 Algorithm Type

Properties	Description
Tables	CI_ALG_TYPE, CI_ALG_TYPE_L, CI_ALG_TYPE_PRM, CI_ALG_TYPE_PRM_L
Standard Data Fields	Algorithm Type (ALG_TYPE_CD)
Customer Modification	None

C.3.2.3 Algorithm

Properties	Description
Tables	CI_ALG, CI_ALG_L, CI_ALG_PARM, CI_ALG_VER
Standard Data Fields	Algorithm (ALG_CD)
Customer Modification	None

C.3.2.4 Application Security

Properties	Description
Tables	SC_APP_SERVICE, SC_APP_SERVICE_L, CI_APP_SVC_ACC
Standard Data Fields	Application Service ID (APP_SVC_ID). Revenue Management and Billing products prior to version 2.0 will continue to use CI as a prefix for the application service.
Customer Modification	None

C.3.2.5 Batch Control

Properties	Description
Tables	CI_BATCH_CTRL, CI_BATCH_CTRL_L, CI_BATCH_CTRL_P, CI_BATCH_CTRL_P_L
Standard Data Fields	Batch Process (BATCH_CD), Program Name (PROGRAM_NAME)
Customer Modification	Next Batch Number (NEXT_BATCH_NBR), Last Update Instance (LAST_UPDATE_INST), Last Update Date time (LAST_UPDATE_DTTM) and the batch process update these columns. Time Interval (TIMER_INTERVAL), Thread Count (BATCH_THREAD_CNT), Maximum Commit Records (MAX_COMMIT_RECS), User (USER_ID), Language (LANGUAGE_CD), Email Address (EMAILID), Start program debug tracing (TRC_PGM_STRT_SW), End Program Debug trace (TRC_PGM_END_SW), SQL debug tracing (TRC_SQL_SW) and Standard debug tracing (TRC_STD_SW) on CI_BATCH_CTRL Table. Batch Parameter Value (BATCH_PARM_VAL) on Batch Control Parameters Table (CI_BATCH_CTRL_P)

C.3.2.6 Business Object

Properties	Description
Tables	F1_BUS_OBJ, F1_BUS_OBJ_L, F1_BUS_OBJ_ALG, F1_BUS_OBJ_OPT, F1_BUS_OBJ_STATUS, F1_BUS_OBJ_STATUS_L, F1_BUS_OBJ_STATUS_ALG, F1_BUS_OBJ_STATUS_OPT, F1_BUS_OBJ_STATUS_RSN, F1_BUS_OBJ_STATUS_RSN_L, F1_BUS_OBJ_STATUS_RSN_CHAR F1_BUS_OBJ_TR_RULE, F1_BUS_OBJ_TR_RULE_L
Standard Data Fields	Business Object (BUS_OBJ_CD), Status Reason (BO_STATUS_REASON_CD)
Customer Modification	Batch Control (BATCH_CD), Alert (BO_ALERT_FLG), Sequence (SORT_SEQ5), Status Reason (STATUS_REASON_FLG) fields on Business Object Status Table (F1_BUS_OBJ_STATUS). Instance Control (INSTANCE_CTRL_FLG), Application Service (APP_SVC_ID) on Business Object Table (F1_BUS_OBJ). Status Reason Selection (STATUS_REASON_SELECT_FLG) on Status Reason Table (F1_BUS_OBJ_STATUS_RSN).

C.3.2.7 Business Service

Properties	Description
Tables	F1_BUS_SVC, F1_BUS_SVC_L
Standard Data Fields	Business Service (BUS_SVC_CD)
Customer Modification	Application Service (APP_SVC_ID)

C.3.2.8 Characteristics

Properties	Description
Tables	CI_CHAR_TYPE, CI_CHAR_TYPE_L, CI_CHAR_ENTITY, CI_CHAR_VAL, CI_CHAR_VAL_L
Standard Data Fields	Characteristic Type (CHAR_TYPE_CD)

Properties	Description
Customer Modification	Adhoc Characteristic Value Validation Rule (ADHOC_VAL_ALG_CD) on Characteristic Entity Table (CI_CHAR_ENTITY)

C.3.2.9 Configuration Migration Assistant

Properties	Description
Tables	F1_MIGR_PLAN, F1_MIGR_PLAN_L, F1_MIGR_PLAN_INSTR, F1_MIGR_PLAN_INSTR_L, F1_MIGR_PLAN_INSTR_ALG, F1_MIGR_REQ, F1_MIGR_REQ_L, F1_MIGR_REQ_INSTR, F1_MIGR_REQ_INST R_L, F1_MIGR_REQ_INSTR_ENTITY
Standard Data Fields	Migration Plan Code (MIGR_PLAN_CD), Migration Request Code (MIGR_REQ_CD)
Customer Modification	None

C.3.2.10 Data Area

Properties	Description
Tables	F1_DATA_AREA, F1_DATA_AREA_L
Standard Data Fields	Data Area Code (DATA_AREA_CD)
Customer Modification	None

C.3.2.11 Display Icon

Properties	Description
Tables	CI_DISP_ICON, CI_DISP_ICON_L
Standard Data Fields	Display Icon Code (DISP_ICON_CD)
Customer Modification	None

C.3.2.12 Extendable Lookup

Properties	Description
Tables	F1_EXT_LOOKUP_VAL, F1_EXT_LOOKUP_VAL_L
Standard Data Fields	Business Object (BUS_OBJ_CD), Extendable Lookup Value (F1_EXT_LOOKUP_VALUE)
Customer Modification	Override Description (DESCR_OVRD) on Extendable Lookup Field Value Language Table (F1_EXT_LOOKUP_VAL_L)

C.3.2.13 Foreign Key Reference

Properties	Description
Tables	CI_FK_REF, CI_FK_REF_L
Standard Data Fields	FK reference code (FK_REF_CD)
Customer Modification	Info Program Name (INFO_PRG), Zone (ZONE_CD)

C.3.2.14 Inbound Web Service

Properties	Description
Tables	F1_MIGR_PLAN, F1_MIGR_PLAN_L, F1_MIGR_PLAN_INSTR, F1_MIGR_PLAN_INSTR_L, F1_MIGR_PLAN_INSTR_ALG, F1_MIGR_REQ, F1_MIGR_REQ_L, F1_MIGR_REQ_INSTR, F1_MIGR_REQ_INST_R_L, F1_MIGR_REQ_INSTR_ENTITY
Standard Data Fields	Webservice Name (IN_SVC_NAME), Annotation (ANN_CD), Annotation Type (ANN_TYPE_CD)
Customer Modification	Debug (DEBUG_SW), Active (ACTIVE_SW), Trace (TRACE_SW), Post Error (POST_ERROR_SW), Request XSL (REQUEST_XSL), Response XSL (RESPONSE_XSL)

C.3.2.15 Lookup

Properties	Description
Tables	CI_LOOKUP_FIELD, CI_LOOKUP_VAL, CI_LOOKUP_VAL_L
Standard Data Fields	<p>Field Name (FIELD_NAME)</p> <ul style="list-style-type: none"> A lookup field name must have corresponding field metadata. The name of the lookup field column must be assigned to avoid conflicts among different products. If you follow the standards for database field names, a Customer Modification lookup field name will be automatically Customer Modification prefixed. <p>Field Value (FIELD_VALUE)</p> <ul style="list-style-type: none"> If a lookup field is customizable, Customer Modification can insert new lookup values. X or Y must prefix when implementers introduce a new lookup value. Product development may add lookup values to the Oracle Utilities Application Framework owned lookup field's value. When extended new value is added, the Owner Flag is used to prefix the value. For example, when the Oracle Revenue Management and Billing product adds a new value to the algorithm entity flag (ALG_ENTITY_FLG), it is prefixed with C1.
Customer Modification	Override Description (DESCR_OVRD) on Lookup Field Value Language Table (CI_LOOKUP_VAL_L)

C.3.2.16 Map

Properties	Description
Tables	F1_MAP, F1_MAP_L
Standard Data Fields	UI Map (MAP_CD)
Customer Modification	None

C.3.2.17 Managed Content

Properties	Description
Tables	F1_MANAG_CONTENT, F1_MANAG_CONTENT_L
Standard Data Fields	Managed Content (MANAG_CONTENT_CD)
Customer Modification	None

C.3.2.18 Messages

Properties	Description
Tables	CI_MSG_CATEGORY, CI_MSG_CATEGORY_L, CI_MSG, CI_MSG_L
Standard Data Fields	<p>Message Category (MESSAGE_CAT_NBR)</p> <ul style="list-style-type: none"> Messages are grouped in categories and each category has message numbers between 1 and 99999. A range of message categories is assigned to a product. An implementation may only use categories assigned for customization use. Implementer Message Categories are 80000 and 90000 Reserved for Tests – 99999 <p>Message Number (MESSAGE_NBR) for COBOL message categories</p> <ul style="list-style-type: none"> Message numbers below 1000 are reserved for common messages. Implementers must not use message numbers below 1000. <p>Message Number (MESSAGE_NBR) for Java message categories</p> <ul style="list-style-type: none"> Subsystem Standard Messages - 00001 thru 02000 Reserved - 02001 thru 09999 Published Messages - 10001 thru 11000 Package Messages - 10001 thru 90000 Reserved - 90001 thru 99999 Each package is allocated 100 message numbers, each starting from 101. Published Messages are messages that are special-interest

Properties	Description
	<p>messages that implementations need to know about and are therefore published in the user docs. Examples of these include messages that are highly likely to be changed for an implementation, or messages that are embedded into other texts/messages and therefore the message number is never shown.</p> <ul style="list-style-type: none"> • Reserved message number ranges are for future use and therefore must not be used by all products.
Customer Modification	Override Description (DESCRLONG_OVRD), Message Text Override (MESSAGE_TEXT_OVRD)

C.3.2.19 Meta Data - Table and Field

Properties	Description
Tables	CI_MD_TBL, CI_MD_TBL_FLD, CI_MD_TBL_L, CI_MD_TBL_FLD_L, CI_MD_FLD, CI_MD_FLD_L, F1_DB_OBJECTS_REPO
Standard Data Fields	<p>Table Name (TBL_NAME)</p> <ul style="list-style-type: none"> • Table names must match with the physical table name or view name in the database. • Field Name (FLD_NAME) Field name must match with the physical column name in the database unless the field is a work field. Field name does not have to follow the prefixing standard unless the field is a work field or customer modification field. • F1_DB_OBJECTS_REPO Table stores information about Indexes, Sequences, Triggers and other database objects excluding Tables and Fields (as they are already stored in the other Metadata tables)
Customer Modification	Audit Switches (AUDIT_INSERT_SW, AUDIT_UPDATE_SW, AUDIT_DELETE_SW), Override label (OVRD_LABEL) on MD Table Field Table (CI_MD_TBL_FLD). Audit Program Name (AUDIT_PGM_NAME), Audit Table Name (AUDIT_TBL_NAME), Audit Program Type (AUDIT_PGM_TYPE_FLG), Key Validation (KEY_VALIDATION_FLG) and Caching strategy (CACHE_FLG) on MD Table (CI_MD_TBL). Override Label (OVRD_LABEL) and Customer Specific Description (DESCRLONG_OVRD) on Field Table.

C.3.2.20 Meta Data – Constraints

Properties	Description
Tables	CI_MD_CONST, CI_MD_CONST_FLD

Properties	Description
Standard Data Fields	Constraint Id (CONST_ID) <ul style="list-style-type: none"> Index Name for Primary Constraints <Index Name>Rnn for Foreign Key Constraints Where nn: integer, 01 through 99
Customer Modification	None

C.3.2.21 Meta Data - Menu

Menus can be extended to support multiple products by adding a new menu line to an existing menu. The sequence number on the menu line language table (CI_MD_MENU_LINE_L) determines the order the menu lines appear. Within the same sequence, alphabetic sorting is used.

Properties	Description
Tables	CI_MD_MENU, CI_MD_MENU_L, CI_MD_MENU_ITEM, CI_MD_MENU_ITEM_L, CI_MD_MENU_LINE, CI_MD_MENU_LINE_L
Standard Data Fields	Menu Name (MENU_NAME), Menu Item Id (MENU_ITEM_ID), Menu Line Id (MENU_LINE_ID)
Customer Modification	Override Label (OVRD_LABEL) on Menu Line Language Table (CI_MD_MENU_LINE_L)

C.3.2.22 Meta Data - Program, Location and Services

Properties	Description
Tables	CI_MD_PRG_COM, CI_MD_PRG_LOC, CI_MD_SVC, CI_MD_SVC_L, CI_MD_SVC_PRG, CI_MD_PRG_MOD, CI_MD_PRG_EL_AT, CI_MD_PRG_ELEM, CI_MD_PRG_SEC, CI_MD_PRG_SQL, CI_MD_PRG_VAR, CI_MD_PRG_TAB
Standard Data Fields	Program Component Id (PROG_COM_ID), Location Id (LOC_ID), Program Component Name (PROG_COM_NAME), Service Name (SVC_NAME), Navigation Key (NAVIGATION_KEY)
Customer Modification	User Exit Program Name (USER_EXIT_PGM_NAME) on Program Components Table (CI_MD_PRG_COM),

C.3.2.23 Meta Data - Maintenance Object

Properties	Description
Tables	CI_MD_MO, CI_MD_MO_L, CI_MD_MO_TBL, CI_MD_MO_OPT, CI_MD_MO_ALG
Standard Data Fields	Maintenance Object (MAINT_OBJ_CD)
Customer Modification	None

C.3.2.24 Meta Data - Work Tables

Properties	Description
Tables	CI_MD_WRK_TBL, CI_MD_WRK_TBL_L, CI_MD_WRK_TBLFLD, CI_MD_MO_WRK
Standard Data Fields	Work Table Name (WRK_TBL_NAME)
Customer Modification	None

C.3.2.25 Meta Data - Search Object

Properties	Description
Tables	CI_MD_SO, CI_MD_SO_L, CI_MD_SO_RSFLD, CI_MD_SO_RSFLDAT, CI_MD_SOCG, CI_MD_SOCG_FLD, CI_MD_SOCG_FLDAT, CI_MD_SOCG_L, CI_MD_SOCG_SORT
Standard Data Fields	Search Object (SO_CD)
Customer Modification	None

C.3.2.26 Migration Plan

Properties	Description
Tables	F1_MIGR_PLAN, F1_MIGR_PLAN_L, F1_MIGR_PLAN_INSTR, F1_MIGR_PLAN_INSTR_L, F1_MIGR_PLAN_INSTR_ALG
Standard Data Fields	Migration Plan (MIGR_PLAN_CD)
Customer Modification	None

C.3.2.27 Migration Request

Properties	Description
Tables	F1_MIGR_REQ, F1_MIGR_REQ_L, F1_MIGR_REQ_INSTR, F1_MIGR_REQ_INSTR_L, F1_MIGR_REQ_INSTR_ENTITY
Standard Data Fields	Migration Request (MIGR_REQ_CD)
Customer Modification	None

C.3.2.28 Navigation Option

Properties	Description
Tables	CI_NAV_OPT, CI_NAV_OPT_L, CI_NAV_OPT_CTXT, CI_NAV_OPT_USG, CI_MD_NAV
Standard Data Fields	Navigation Option Code (NAV_OPT_CD), Navigation Key (NAVIGATION_KEY)
Customer Modification	None

C.3.2.29 Portal and Zone

Properties	Description
Tables	CI_PORTAL, CI_PORTAL_L, CI_PORTAL_ZONE, CI_ZONE, CI_ZONE_L, CI_ZONE_PRM, CI_ZONE_HDL, CI_ZONE_HDL_L, CI_ZONE_HDL_PRM, CI_ZONE_HDL_PRM_L, CI_UI_ZONE
Standard Data Fields	Portal Code (PORTAL_CD), Zone Code (ZONE_CD), Zone Type Code (ZONE_HDL_CD) <ul style="list-style-type: none"> • A new Zone can be added to the Product owned Portal Pages. • The existing Zones cannot be removed from the Product owned Portal Pages.
Customer Modification	Sort Sequence (SORT_SEQ) on Context Sensitive Zone Table (CI_UI_ZONE). Show on Portal Preferences (USER_CONFIG_FLG) on Portal Table (CI_PORTAL). Override Sequence (SORT_SEQ_OVRD) on Portal Zone Table (CI_PORTAL_ZONE). Customer Specific Description (DESCRLONG_OVRD) on Zone Language Table (CI_ZONE_L). Override Parameter Value (ZONE_HDL_PARM_OVRD) on Zone Type Parameters Table (CI_ZONE_HDL_PRM). Override Parameter Value (ZONE_PARM_VAL_OVRD) on Zone Parameters Table (CI_ZONE_PRM).

C.3.2.30 Sequence

Properties	Description
Tables	CI_SEQ
Standard Data Fields	Sequence Name (SEQ_NAME)
Customer Modification	Sequence Number (SEQ_NBR) This field is updated by the application process and must be set to 1 initially.

C.3.2.31 Schema

Properties	Description
Tables	F1_SCHEMA
Standard Data Fields	Schema Name (SCHEMA_NAME)
Customer Modification	None

C.3.2.32 Script

Properties	Description
Tables	CI_SCR, CI_SCR_L, CI_SCR_CRT, CI_SCR_CRT_GRP, CI_SCR_CRT_GRP_L, CI_SCR_DA, CI_SCR_FLD_MAP, CI_SCR_PRMPT, CI_SCR_PRMPT_L, CI_SCR_STEP, CI_SCR_STEP_L
Standard Data Fields	Script (SCR_CD)
Customer Modification	None

C.3.2.33 To Do Type

Properties	Description
Tables	CI_TD_TYPE, CI_TD_TYPE_L, CI_TD_SRTKEY_TY, CI_TD_DRLKEY_TY, CI_TD_SRTKEY_TY_L
Standard Data Fields	To Do Type Code (TD_TYPE_CD)
Customer Modification	Creation Batch Code (CRE_BATCH_CD), Route Batch Code (RTE_BATCH_CD), Priority Flag (TD_PRIORITY_FLG) on To Do Type Table (CI_TD_TYPE)

C.3.2.34 XAI Configuration

Properties	Description
Tables	CI_XAI_ADAPTER, CI_XAI_ADAPTER_L, CI_XAI_CLASS, CI_XAI_CLASS_L, CI_XAI_ENV_HNDL, CI_XAI_ENV_HNDL_L, CI_XAI_FORMAT, CI_XAI_FORMAT_L, CI_XAI_RCVR, CI_XAI_RCVR_L, CI_XAI_RCVR_CTX, CI_XAI_RCVR_RSP, CI_XAI_RCVR_RGRP, CI_XAI_SENDER, CI_XAI_SERNDER_L, CI_XAI_SNDR_CTX, CI_XAI_OPTION
Standard Data Fields	Adapter Id (XAI_ADAPTER_ID), Class Id (XAI_CLASS_ID), Envelope Handler Id (XAI_ENV_HNDL_ID), XAI Format Id (XAI_FORMAT_ID), Receiver Id (XAI_RCVR_ID), Sender Id (XAI_SENDER_ID)
Customer Modification	Option Value (OPTION_VALUE) on Message Option Table (CI_XAI_OPTION)

The following XAI tables might have system data installed upon the initial installation but a subsequent system data upgrade process will not update the content of these tables unless the change is documented in the database upgrade guide: CI_XAI_RCVR, CI_XAI_RCVR_L, CI_XAI_RCVR_CTX, CI_XAI_RCVR_RSP, CI_XAI_RCVR_RGRP, CI_XAI_SENDER, CI_XAI_SERNDER_L, CI_XAI_SNDR_CTX.

C.3.2.35 XAI Services

Properties	Description
Tables	CI_XAI_IN_SVC, CI_XAI_IN_SVC_L, CI_XAI_SVC_PARM
Standard Data Fields	XAI Inbound Service Id (XAI_IN_SVC_ID), XAI Inbound Service Name (XAI_IN_SVC_NAME)
Customer Modification	XAI Version (XAI_VERSION_ID), Trace (TRACE_SW), Debug (DEBUG_SW), Request XSL (INPUT_XSL), Response XSL (RESPONSE_XSL), Record XSL (RECORD_XSL) and Post Error (POST_ERROR_SW) on XAI Inbound Service Table (CI_XAI_IN_SVC)

C.3.3 Oracle Utilities Application Framework Only Tables

All data of the tables in this group belong to the Oracle Utilities Application Framework. No data modification or addition is allowed for these tables by base product development and customer modification. When an environment is upgraded to the next release of the Oracle Utilities Application Framework, the upgrade process will refresh the data in these tables.

- CI_MD_AT_DTL / CI_MD_AT_DTL_L
- CI_MD_ATT_TY
- CI_MD_CTL / CI_MD_CTL_L
- CI_MD_CTL_TMPL
- CI_MD_ELTY / CI_MD_ELTY_L
- CI_MD_ELTY_AT
- CI_MD_LOOKUP_F
- CI_MD_PDF / CI_MD_PDF_VAL
- CI_MD_MSG / CI_MD_MSG_L
- CI_MD_SRC_TYPE / CI_MD_SRC_TYPE_L
- CI_MD_TMPL / CI_MD_TMPL_L
- CI_MD_TMPL_ELTY
- CI_MD_TMPL_VAR / CI_MD_TMPL_VAR_L
- CI_MD_VAR / CI_MD_VAR_DTL / CI_MD_VAR_DTL_L
- CI_XAI_EXECUTER / CI_XAI_EXECUTER_L

C.4 System Table List

This section contains names of system tables, upgrade actions, and a brief description of tables. The upgrade actions are explained below.

Keep (KP): The data in the table in the customer's database is kept untouched. No insert or delete is performed to this table by the upgrade process. The initial installation will add necessary data for the system.

Merge (MG): The non-base product data in the table in the database is kept untouched. If the data belongs to the base product, any changes pertaining to the new version of the software are performed.

Refresh (RF): The existing data in the table is replaced with the data from the base product table.

Note: New product data is also inserted into tables marked as 'Merge'. If implementers add rows for a customer specific enhancement, it can cause duplication when the system data gets upgraded to the next version. We strongly recommend following the guidelines on how to use designated range of values or prefixes to segregate the implementation data from the base product data.

Table Name	Upgrade Action	Description
CI_ALG	MG	Algorithm
CI_ALG_L	MG	Algorithm Language
CI_ALG_PARM	MG	Algorithm Parameters
CI_ALG_TYPE	MG	Algorithm Type
CI_ALG_TYPE_L	MG	Algorithm Type Language
CI_ALG_TYPE_PRM	MG	Algorithm Type Parameter
CI_ALG_TYPE_PRM_L	MG	Algorithm Type Parameter Language
CI_ALG_VER	MG	Algorithm Version
CI_APP_SVC_ACC	MG	Application Service Access Mode
CI_BATCH_CTRL	MG	Batch Control
CI_BATCH_CTRL_ALG	MG	Batch Control Algorithm
CI_BATCH_CTRL_L	MG	Batch Control Language
CI_BATCH_CTRL_P	MG	Batch Control Parameters
CI_BATCH_CTRL_P_L	MG	Batch Control Parameters Language
CI_CHAR_ENTITY	MG	Characteristic Type Entity
CI_CHAR_TYPE	MG	Characteristic Type
CI_CHAR_TYPE_L	MG	Characteristic Type Language
CI_CHAR_VAL	MG	Characteristic Type Value
CI_CHAR_VAL_L	MG	Characteristic Type Value Language
CI_DISP_ICON	MG	Display Icon
CI_DISP_ICON_L	MG	Display Icon Language
CI_FK_REF	MG	Foreign Key Reference
CI_FK_REF_L	MG	Foreign Key Reference Language
CI_LANGUAGE	MG	Language Code
CI_LOOKUP_FIELD	MG	Lookup Field
CI_LOOKUP_VAL	MG	Lookup Field Value
CI_LOOKUP_VAL_L	MG	Lookup Field Value Language
CI_MD_CONST	MG	Constraints
CI_MD_CONST_FLD	MG	Constraint Fields
CI_MD_FLD	MG	Field

Table Name	Upgrade Action	Description
CI_MD_FLD_L	MG	Field Language
CI_MD_MENU	MG	Menu Information
CI_MD_MENU_IMOD	MG	Menu Item Module Maint
CI_MD_MENU_ITEM	MG	Menu Item
CI_MD_MENU_ITEM_L	MG	Menu Item Language
CI_MD_MENU_L	MG	Menu Language
CI_MD_MENU_LINE	MG	Menu Line
CI_MD_MENU_LINE_L	MG	Menu Line Language
CI_MD_MENU_MOD	MG	Menu Product Components
CI_MD_MO	MG	Maintenance Object
CI_MD_MO_ALG	MG	Maintenance Object Algorithm
CI_MD_MO_L	MG	Maintenance Object Language
CI_MD_MO_OPT	MG	Maintenance Object Option
CI_MD_MO_TBL	MG	Maintenance Object Table
CI_MD_MO_WRK	MG	Maintenance Object Work Tables
CI_MD_NAV	MG	Navigation Key
CI_MD_PRG_COM	MG	Program Components
CI_MD_PRG_ELEM	MG	UI Page Elements
CI_MD_PRG_EL_AT	MG	UI Page Element Attributes
CI_MD_PRG_LOC	MG	Program Location
CI_MD_PRG_MOD	MG	Program Module
CI_MD_PRG_SEC	MG	UI Page Sections
CI_MD_PRG_SQL	MG	MD SQL Meta Data
CI_MD_PRG_TAB	MG	UI Tab Meta Data
CI_MD_PRG_VAR	MG	Program Variable
CI_MD_SO	MG	Search Object
CI_MD_SOCG	MG	Search Object Criteria Group
CI_MD_SOCG_FLD	MG	Search Object Criteria Group Field
CI_MD_SOCG_FLDAT	MG	Search Criteria Group Field Attribute
CI_MD_SOCG_L	MG	Search Object Criteria Group Language
CI_MD_SOCG_SORT	MG	Search Criteria Group Result Sort Order

Table Name	Upgrade Action	Description
CI_MD_SO_L	MG	Search Object Language
CI_MD_SO_RSFLD	MG	Search Object Result Field
CI_MD_SO_RSFLDAT	MG	Search Object Result Field Attribute
CI_MD_SVC	MG	MD Service
CI_MD_SVC_L	MG	MD Service Language
CI_MD_SVC_PRG	MG	MD Service Program
CI_MD_TAB_MOD	MG	UI Tab Module
CI_MD_TBL	MG	MD Table
CI_MD_TBL_FLD	MG	MD Table Field
CI_MD_TBL_FLD_L	MG	MD Table Field Language
CI_MD_TBL_L	MG	MD Table Language
CI_MD_WRK_TBL	MG	Work Table
CI_MD_WRK_TBLFLD	MG	Work Table Field
CI_MD_WRK_TBL_L	MG	Work Table Language
CI_MSG	MG	Message
CI_MSG_CATEGORY	MG	Message Category
CI_MSG_CATEGORY_L	MG	Message Category Language
CI_MSG_L	MG	Message Language
CI_NAV_OPT	MG	Navigation Option
CI_NAV_OPT_CTXT	MG	Navigation Option Context
CI_NAV_OPT_L	MG	Navigation Option Language
CI_NAV_OPT_USG	MG	Navigation Option Usage
CI_PORTAL	MG	Portal
CI_PORTAL_L	MG	Portal Language
C1_PORTAL_OPT	MG	Portal Option
CI_PORTAL_ZONE	MG	Portal Zone
CI_SCR	MG	Script
CI_SCR_CRT	MG	Script Criteria
CI_SCR_CRT_GRP	MG	Script Criteria Group
CI_SCR_CRT_GRP_L	MG	Script Criteria Group Language
CI_SCR_DA	MG	Script Data Area

Table Name	Upgrade Action	Description
CI_SCR_FLD_MAP	MG	Script Field Mapping
CI_SCR_L	MG	Script Language
CI_SCR_PRMPT	MG	Script Prompt
CI_SCR_PRMPT_L	MG	Script Prompt Language
CI_SCR_STEP	MG	Script Step
CI_SCR_STEP_L	MG	Script Step Language
CI_SEQ	MG	Sequence
CI_TD_DRLKEY_TY	MG	To Do Type Drill Key
CI_TD_SRTKEY_TY	MG	To Do Type Sort Key
CI_TD_SRTKEY_TY_L	MG	To Do Type Sort Key Language
CI_TD_TYPE	MG	To Do Type
CI_TD_TYPE_L	MG	To Do Type Language
CI_UI_ZONE	MG	Context Sensitive Zone
CI_USR_NAV_LINK	MG	User Favorite Links
CI_XAI_ADAPTER	MG	XAI Adapter
CI_XAI_ADAPTER_L	MG	XAI Adapter Lang
CI_XAI_CLASS	MG	XAI Class
CI_XAI_CLASS_L	MG	XAI Class Language
CI_XAI_ENV_HNDL	MG	XAI Envelope Handler
CI_XAI_ENV_HNDL_L	MG	XAI Envelope Handler Language
CI_XAI_IN_SVC	MG	XAI Inbound Service
CI_XAI_IN_SVC_L	MG	XAI Inbound Service Language
CI_XAI_SVC_PARM	MG	XAI Inbound Service Parameters
CI_ZONE	MG	Zone
CI_ZONE_HDL	MG	Zone Type
CI_ZONE_HDL_L	MG	Zone Type Language
CI_ZONE_HDL_PRM	MG	Zone Type Parameters
CI_ZONE_HDL_PRM_L	MG	Zone Type Parameters Language
CI_ZONE_L	MG	Zone Language
CI_ZONE_PRM	MG	Zone Parameters
F1_BUS_OBJ	MG	Business Object

Table Name	Upgrade Action	Description
F1_BUS_OBJ_ALG	MG	Business Object Algorithm
F1_BUS_OBJ_L	MG	Business Object Language
F1_BUS_OBJ_OPT	MG	Business Object Option
F1_BUS_OBJ_STATUS	MG	Business Object Status
F1_BUS_OBJ_STATUS_ALG	MG	Business Object Status Algorithm
F1_BUS_OBJ_STATUS_L	MG	Business Object Status Language
F1_BUS_OBJ_STATUS_OPT	MG	Business Object Status Option
F1_BUS_OBJ_STATUS_RSN	MG	Status Reason
F1_BUS_OBJ_STATUS_RSN_L	MG	Status Reason Language
F1_BUS_OBJ_TR_RULE	MG	Business Object Transition Rule
F1_BUS_OBJ_TR_RULE_L	MG	Business Object Transition Rule Language
F1_BUS_SVC	MG	Business Service
F1_BUS_SVC_L	MG	Business Service Language
F1_DATA_AREA	MG	Data Area
F1_DATA_AREA_L	MG	Data Area Language
F1_DB_OBJECTS_REPO	MG	Database Objects Repository
F1_EXT_LOOKUP_VAL	MG	Extendable Lookup
F1_EXT_LOOKUP_VAL_L	MG	Extendable Lookup Language
F1_IWS_ANN	MG	-Web Service Annotation
F1_IWS_ANN_L	MG	Web Service Annotation Language
F1_IWS_ANN_PARM	MG	Web Service Annotation Parameter
F1_IWS_ANN_TYPE	MG	Web Service Annotation Type
F1_IWS_ANN_TYPE_L	MG	Web Service Annotation Type Language
F1_IWS_ANN_TYPE_PARM	MG	Web Service Annotation Type Parm
F1_IWS_ANN_TYPE_PARM_L	MG	Web Service Annotation Type Parameter Language
F1_IWS_SVC	MG	Inbound Web Service
F1_IWS_SVC_L	MG	Inbound Web Service Language
F1_IWS_SVC_OPER	MG	Inbound Web Service Operations
F1_IWS_SVC_OPER_L	MG	Inbound Web Service Operations Language
F1_MANAG_CONTENT	MG	Managed Content

Table Name	Upgrade Action	Description
F1_MANAG_CONTENT_L	MG	Managed Content Language
F1_MAP	MG	UI Map
F1_MAP_L	MG	UI Map Language
F1_MIGR_PLAN	MG	Migration Plan
F1_MIGR_PLAN_INSTR	MG	Migration Plan Instruction
F1_MIGR_PLAN_INSTR_ALG	MG	Migration Plan Instruction Algorithm
F1_MIGR_PLAN_INSTR_L	MG	Migration Plan Instruction Language
F1_MIGR_PLAN_L	MG	Migration Plan Language
F1_MIGR_REQ	MG	Migration Request
F1_MIGR_REQ_INSTR	MG	Migration Request Instruction
F1_MIGR_REQ_INSTR_ENTITY	MG	Migration Request Instruction Entity
F1_MIGR_REQ_INSTR_L	MG	Migration Request Instruction Language
F1_MIGR_REQ_L	MG	Migration Request Language
F1_SCHEMA	MG	Schema
SC_ACCESS_CNTL	MG	User Group Access Control
SC_APP_SERVICE	MG	Application Service
SC_APP_SERVICE_L	MG	Application Service Language
SC_USR_GRP_PROF	MG	User Group Profile
CI_ACC_GRP	KP	Access Group
CI_ACC_GRP_DAR	KP	Access Group / Data Access Group
CI_ACC_GRP_L	KP	Access Group Language
CI_APP_SVC_SCTY	KP	Security Type Application Service
CI_CAL_HOL	KP	Work Calendar Holidays
CI_CAL_HOL_L	KP	Work Calendar Holidays Language
CI_CAL_WORK	KP	Work Calendar
CI_CAL_WORK_L	KP	Work Calendar Language
CI_CHTY_TDTY	KP	To Do Type Template Characteristics
CI_COUNTRY	KP	Country
CI_COUNTRY_L	KP	Country Language
CI_CURRENCY_CD	KP	Currency Code
CI_CURRENCY_CD_L	KP	Currency Code Language

Table Name	Upgrade Action	Description
CI_DAR	KP	Data Access Role
CI_DAR_L	KP	Data Access Language
CI_DAR_USR	KP	Data Access User
CI_DISP_PROF	KP	Display Profile
CI_DISP_PROF_L	KP	Display Profile Language
CI_FUNC	KP	Function
CI_FUNC_FLD	KP	Function Field
CI_FUNC_FLD_L	KP	Function Field Language
CI_FUNC_L	KP	Function Language
CI_GEO_TYPE	KP	Geographic Type
CI_GEO_TYPE_L	KP	Geographic Type Language
CI_INSTALL_ALG	KP	Installation Algorithm
CI_INSTALL_MSG	KP	Installation Message
CI_INSTALL_MSG_L	KP	Installation Message Language
CI_INSTALL_PROD	KP	Installation Product
CI_MD_RPT	KP	Report Definition
CI_MD_RPT_L	KP	Report Language
CI_MD_RPT_LBL	KP	Report Labels
CI_MD_RPT_PARM	KP	Report Parameters
CI_MD_RPT_PARM_L	KP	Report Parameters Language
CI_MD_TOOLREP_XML	KP	MD Tool Reference XML
CI_MD_TOOL REP	KP	MD Tool Reference
CI_NT_DNTY_CTXT	KP	Notification Download Type Context
CI_NT_DWN_FORM	KP	Notification Download Format
CI_NT_DWN_FORM_L	KP	Notification Download Format Language
CI_NT_DWN_PROF	KP	Notification Download Profile
CI_NT_DWN_PROF_L	KP	Notification Download Profile Language
CI_NT_DWN_TYPE	KP	Notification Download Type
CI_NT_DWN_TYPE_L	KP	Notification Download Type Language
CI_NT_UP_XTYPE	KP	Notification Upload Type
CI_NT_UP_XTYPE_L	KP	Notification Upload Type Language

Table Name	Upgrade Action	Description
CI_NT_XID	KP	External System
CI_NT_XID_L	KP	External System Language
CI_PHONE_TYPE	KP	Phone Type
CI_PHONE_TYPE_L	KP	Phone Type Language
CI_ROLE	KP	Role
CI_ROLE_L	KP	Role Language
CI_ROLE_USER	KP	Role User
CI_RPT_OPTION	KP	Report Options
CI_SC_AUTH_LVL	KP	Security Type Auth Level
CI_SC_AUTH_LVL_L	KP	Security Type Auth Level Language
CI_SC_TYPE	KP	Security Type
CI_SC_TYPE_L	KP	Security Type Language
CI_SEAS_SHIFT	KP	Seasonal Time Shift Schedule
CI_SEAS_TM_SHIFT	KP	Seasonal Time Shift
CI_SEAS_TM_SHIFT_L	KP	Seasonal Shift Language
CI_STATE	KP	State
CI_STATE_L	KP	State Language
CI_TD_EX_LIST	KP	To Do Type Message Overrides
CI_TD_TYPE_ALG	KP	To Do Type Algorithms
CI_TD_TYPE_CHAR	KP	To Do Type Characteristic
CI_TD_VAL_ROLE	KP	To Do Type Role
CI_TIME_ZONE	KP	Time Zone
CI_TIME_ZONE_L	KP	Time Zone Language
CI_USR_GRP_SC	KP	User Group Security Type
CI_USR_BOOKMARK	KP	User Bookmarks
CI_USR_PORTAL	KP	User Portal
CI_USR_SCR	KP	User Scripts
CI_USR_ZONE	KP	User Zone
CI_USR_ZONE_SAVE	KP	User Zone Save
CI_WFM	KP	Feature Configuration
CI_WFM_L	KP	Feature Configuration Language

Table Name	Upgrade Action	Description
CI_WFM_MSG	KP	Feature Configuration Message
CI_WFM_OPT	KP	Feature Configuration Options
CI_WF_EVT_TYPE	KP	WF Event Type
CI_WF_EVT_TYPE_L	KP	WF Event Type Language
CI_WF_PP	KP	WF Process Profile
CI_WF_PP_L	KP	WF Process Profile Language
CI_WF_PP_NT	KP	WF Process Notification
CI_WF_PP_NT_CRT	KP	WF Process Notification Criteria
CI_WF_PROC_SCHED	KP	WF Process Creation Schedule
CI_WF_PROC_SCHED_K	KP	WF Process Creation Schedule Key
CI_WF_PROC_TMPL	KP	WF Process Template
CI_WF_PROC_TMPL_L	KP	WF Process Template Language
CI_WF_RESP	KP	WF Response
CI_WF_RESP_DEP	KP	WF Response Dependency
CI_XAI_JDBC_CON	KP	XAI JDBC Connection
CI_XAI_JDBC_CON_L	KP	XAI JDBC Connection Language
CI_XAI_JMS_CON	KP	XAI JMS Connection
CI_XAI_JMS_CON_L	KP	XAI JMS Connection Language
CI_XAI_JMS_Q	KP	XAI JMS Queue
CI_XAI_JMS_Q_L	KP	XAI JMS Queue Language
CI_XAI_JMS_TPC	KP	XAI JMS Topic
CI_XAI_JMS_TPC_L	KP	XAI JMS Topic Language
CI_XAI_JNDI_SVR	KP	XAI JNDI Server
CI_XAI_JNDI_SVR_L	KP	XAI JNDI Server Language
CI_XAI_OPTION	KP	Message Option
CI_XAI_RCVR	KP	XAI Receiver
CI_XAI_RCVR_CTX	KP	XAI Receiver Context
CI_XAI_RCVR_L	KP	XAI Receiver Language
CI_XAI_RCVR_RGRP	KP	XAI Receiver Rule Group
CI_XAI_RCVR_RSP	KP	XAI Receiver Response
CI_XAI_RGRP	KP	XAI Rule Group

Table Name	Upgrade Action	Description
CI_XAI_RGRP_ATT	KP	XAI Rule Group Attachment
CI_XAI_RGRP_L	KP	XAI Rule Group Language
CI_XAI_ROUTING	KP	XAI Routing
CI_XAI_RT_TYPE	KP	XAI Route Type
CI_XAI_RT_TYPE_L	KP	XAI Route Type Language
CI_XAI_RULE	KP	XAI Rule
CI_XAI_SENDER	KP	Message Sender
CI_XAI_SENDER_L	KP	Message Sender Language
CI_XAI_SNDR_CTX	KP	Message Sender Context
F1_BKT_CONFIG	KP	Bucket Configuration
F1_BKT_CONFIG_L	KP	Bucket Configuration Language
F1_BKT_CONFIG_REL_OBJ	KP	Bucket Configuration Related Object
F1_BKT_CONFIG_VAL	KP	Bucket Configuration Value
F1_BKT_CONFIG_VAL_L	KP	Bucket Configuration Value Language
F1_BUS_OBJ_STATUS_RS_N_CHAR	KP	Status Reason Characteristic
F1_EXTSYS_OUTMSG_PROF	KP	External System Outbound Message Type
F1_INSTALLATION	KP	Installation Option - Framework
F1_IWS_ANN_CHAR	KP	Web Service Annotation Characteristics
F1_IWS_ANN_TYPE_CHAR	KP	Web Service Annotation Type Characteristics
F1_IWS_SVC_ANN	KP	Inbound Web Service Link to Annotation
F1_IWS_SVC_CHAR	KP	Inbound Web Service Characteristics
F1_IWS_SVC_LOG	KP	Inbound Web Service Log
F1_IWS_SVC_LOG_PARM	KP	Inbound Web Service Log Parameter
F1_MAP_OVRD	KP	UI Map Override
F1_MD_DB_OBJ	KP	MD Database Object
F1_MST_CONFIG	KP	Master Configuration
F1_OUTMSG_TYPE	KP	Outbound Message Type
F1_OUTMSG_TYPE_L	KP	Outbound Message Type Language
F1_REQ_TYPE	KP	Request Type
F1_REQ_TYPE_L	KP	Request Type Language

Table Name	Upgrade Action	Description
F1_REQ_TYPE_LOG	KP	Request Type Log
F1_REQ_TYPE_LOG_PARM	KP	Request Type Log Parameters
F1_SVC_TASK_TYPE	KP	Service Task Type
F1_SVC_TASK_TYPE_CHAR	KP	Service Task Type Characteristics
F1_SVC_TASK_TYPE_L	KP	Service Task Type Language
F1_WEB_SVC	KP	Web Service Adapter
F1_WEB_SVC_CHAR	KP	Web Service Adapter Characteristics
F1_WEB_SVC_L	KP	Web Service Adapter Language
F1_WEB_SVC_LOG	KP	Web Service Adapter Log
F1_WEB_SVC_LOG_PARM	KP	Web Service Adapter Log Parameter
F1_WEB_SVC_OPERATIONS	KP	Web Service Adapter Operations
SC_USER	KP	User
SC_USER_CHAR	KP	User Characteristic
SC_USER_GROUP	KP	User Group
SC_USER_GROUP_L	KP	User Group Language
SC_USR_GRP_USR	KP	User Group User
CI_MD_ATT_TY	RF	MD Element Attribute Type
CI_MD_AT_DTL	RF	MD Element Attribute Type Detail
CI_MD_AT_DTL_L	RF	MD Element Attribute Type Detail Language
CI_MD_CTL	RF	Generator Control
CI_MD_CTL_L	RF	Generator Control Language
CI_MD_CTL_TMPL	RF	Generator Control Template
CI_MD_ELTY	RF	MD Element Type
CI_MD_ELTY_AT	RF	Element Type Attributes
CI_MD_ELTY_L	RF	Element Type Language
CI_MD_LOOKUP_F	RF	MD Lookup Field
CI_MD_MSG	RF	MD Message
CI_MD_MSG_L	RF	MD Message Language
CI_MD_PDF	RF	Predefined Fields
CI_MD_PDF_VAL	RF	Predefined Values

Table Name	Upgrade Action	Description
CI_MD_SRC_TYPE	RF	Source Type
CI_MD_SRC_TYPE_L	RF	Source Type Language
CI_MD_TMPL	RF	Template
CI_MD_TMPL_ELTY	RF	Template Element Types
CI_MD_TMPL_L	RF	Template Language
CI_MD_TMPL_VAR	RF	Template Variable
CI_MD_TMPL_VAR_L	RF	Template Variable Language
CI_MD_VAR	RF	Variable
CI_MD_VAR_DTL	RF	Variable Detail
CI_MD_VAR_DTL_L	RF	Variable Detail Language
CI_XAI_EXECUTER	RF	XAI Executer
CI_XAI_EXECUTER_L	RF	XAI Executer Language

Appendix D : License and Copyright Notices

This section provides license and copyright information for the associated products. It includes the following notices:

- [Notice Concerning Usage of ANTLR](#)
- [Notice Concerning Usage of Apache Software](#)
- [Notice Concerning Usage of ASM](#)
- [Notice Concerning Usage of Concurrent](#)
- [Notice Concerning Usage of DOM4J](#)
- [Notice Concerning Usage of International Components for Unicode \(ICU4J\)](#)
- [Notice Concerning Usage of Jaxen](#)
- [Notice Concerning Usage of JCIP Annotations](#)
- [Notice Concerning Usage of JQuery](#)
- [Notice Concerning Usage of SLF4J](#)
- [Notice Concerning Usage of Staxmate](#)
- [Notice Concerning Usage of XMLPULL](#)
- [Notice Concerning Usage of XStream](#)
- [Notice Concerning Usage of YUI](#)

D.1 Third-Party Products

The following sections provide notices and information about the third party products indicated.

D.1.1 Notice Concerning Usage of ANTLR

[The BSD License]

Copyright (c) 2012 Terence Parr and Sam Harwell.

All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- Neither the name of the author nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

D.1.2 Notice Concerning Usage of Apache Software

The following files are covered under the Apache 2.0 license:

- bsf-2.4.0.jar
- castor-1.3.2-core.jar
- castor-1.3.2-xml-schema.jar
- castor-1.3.2-xml.jar
- cglib-3.1.jar
- commons-logging-1.0.4.jar
- ehcache-core-2.5.2.jar
- commons-beanutils-core-1.8.3.jar
- commons-cli-1.1.jar
- commons-codec-1.6.jar
- commons-collections-3.2.1.jar
- commons-fileupload-1.3.1.jar
- commons-httpclient-3.0.1.jar
- commons-io-1.3.2.jar
- commons-lang-2.2.jar
- jackson-core-asl-1.9.2.jar
- jackson-jaxrs-1.9.2.jar
- jackson-mapper-asl-1.9.2.jar
- jackson-xc-1.9.2.jar
- jettison-1.0.0.0_1-1.jar
- joda-time-2.3.jar
- log4j-1.2.17.jar
- serializer-2.7.1.jar
- stax2-2.1.jar
- stax2-api-3.0.4.jar
- wstx-asl-3.2.7.jar
- xalan-mod-2.7.1.jar

Apache License

Version 2.0, January 2004

<http://www.apache.org/licenses/>

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

“License” shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

“Licensor” shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

“Legal Entity” shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, “control” means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

“You” (or “Your”) shall mean an individual or Legal Entity exercising permissions granted by this License.

“Source” form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

“Object” form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

“Work” shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

“Derivative Works” shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

“Contribution” shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, “submitted” means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as “Not a Contribution.”

“Contributor” shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License.

Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License.

Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution.

You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that you meet the following conditions:

- You must give any other recipients of the Work or Derivative Works a copy of this License; and
- You must cause any modified files to carry prominent notices stating that You changed the files; and
- You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and
- If the Work includes a “NOTICE” text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add your own attribution notices within Derivative Works that you distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License. You may add your own copyright statement to your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of your modifications, or for any such Derivative Works as a whole, provided your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions.

Unless you explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by you to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks.

This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty.

Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with your exercise of permissions under this License.

8. Limitation of Liability.

In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability.

While redistributing the Work or Derivative Works thereof, you may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

D.1.3 Notice Concerning Usage of ASM

Copyright (c) 2000-2011 INRIA, France Telecom

All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. Neither the name of the copyright holders nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

D.1.4 Notice Concerning Usage of Concurrent

All classes are released to the public domain and may be used for any purpose whatsoever without permission or acknowledgment.

<http://g.oswego.edu/dl/classes/EDU/oswego/cs/dl/util/concurrent/intro.html>

D.1.5 Notice Concerning Usage of DOM4J

Copyright 2001-2010 (C) MetaStuff, Ltd.

All Rights Reserved.

Redistribution and use of this software and associated documentation ("Software"), with or without modification, are permitted provided that the following conditions are met:

- * Redistributions of source code must retain copyright statements and notices. Redistributions must also contain a copy of this document.
- * Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

- * The name "DOM4J" must not be used to endorse or promote products derived from this Software without prior written permission of MetaStuff, Ltd. For written permission, please contact dom4j-info@metastuff.com.
- * Products derived from this Software may not be called "DOM4J" nor may "DOM4J" appear in their names without prior written permission of MetaStuff, Ltd. DOM4J is a registered trademark of MetaStuff, Ltd.
- * Due credit should be given to the DOM4J Project - <http://dom4j.sourceforge.net>

THIS SOFTWARE IS PROVIDED BY METASTUFF, LTD. AND CONTRIBUTORS

"AS IS" AND ANY EXPRESSED OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL METASTUFF, LTD. OR ITS CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

D.1.6 Notice Concerning Usage of International Components for Unicode (ICU4J)

COPYRIGHT AND PERMISSION NOTICE

Copyright (c) 1995-2012 International Business Machines Corporation and others all rights reserved.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, provided that the above copyright notice(s) and this permission notice appear in all copies of the Software and that both the above copyright notice(s) and this permission notice appear in supporting documentation.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OF THIRD PARTY RIGHTS. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR HOLDERS INCLUDED IN THIS NOTICE BE LIABLE FOR ANY CLAIM, OR ANY SPECIAL INDIRECT OR CONSEQUENTIAL DAMAGES, OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

Except as contained in this notice, the name of a copyright holder shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Software without prior written authorization of the copyright holder.

D.1.7 Notice Concerning Usage of Jaxen

Copyright 2003-2006 The Werken Company.

All Rights Reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- * Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- * Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- * Neither the name of the Jaxen Project nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

D.1.8 Notice Concerning Usage of JCIP Annotations

Attribution 2.5

CREATIVE COMMONS CORPORATION IS NOT A LAW FIRM AND DOES NOT PROVIDE LEGAL SERVICES. DISTRIBUTION OF THIS LICENSE DOES NOT CREATE AN ATTORNEY-CLIENT RELATIONSHIP. CREATIVE COMMONS PROVIDES THIS INFORMATION ON AN "AS-IS" BASIS. CREATIVE COMMONS MAKES NO WARRANTIES REGARDING THE INFORMATION PROVIDED, AND DISCLAIMS LIABILITY FOR DAMAGES RESULTING FROM ITS USE.

License

THE WORK (AS DEFINED BELOW) IS PROVIDED UNDER THE TERMS OF THIS CREATIVE COMMONS PUBLIC LICENSE ("CCPL" OR "LICENSE"). THE WORK IS PROTECTED BY COPYRIGHT AND/OR OTHER APPLICABLE LAW. ANY USE OF THE WORK OTHER THAN AS AUTHORIZED UNDER THIS LICENSE OR COPYRIGHT LAW IS PROHIBITED.

BY EXERCISING ANY RIGHTS TO THE WORK PROVIDED HERE, YOU ACCEPT AND AGREE TO BE BOUND BY THE TERMS OF THIS LICENSE. THE LICENSOR GRANTS YOU THE RIGHTS CONTAINED HERE IN CONSIDERATION OF YOUR ACCEPTANCE OF SUCH TERMS AND CONDITIONS.

1. Definitions -

- a. "Collective Work" means a work, such as a periodical issue, anthology or encyclopedia, in which the Work in its entirety in unmodified form, along with a number of other contributions, constituting separate and independent works in themselves, are assembled into a collective whole. A work that constitutes a Collective Work will not be considered a Derivative Work (as defined below) for the purposes of this License.
- b. "Derivative Work" means a work based upon the Work or upon the Work and other pre-existing works, such as a translation, musical arrangement, dramatization, fictionalization, motion picture version, sound recording, art reproduction, abridgment, condensation, or any other form in which the Work may be recast, transformed, or adapted, except that a work that constitutes a Collective Work will not be considered a Derivative Work for the purpose of this License. For the avoidance of doubt, where the Work is a musical composition or sound recording, the synchronization of the Work in timed-relation with a moving image ("synching") will be considered a Derivative Work for the purpose of this License.
- c. "Licensor" means the individual or entity that offers the Work under the terms of this License.
- d. "Original Author" means the individual or entity who created the Work.
- e. "Work" means the copyrightable work of authorship offered under the terms of this License.
- f. "You" means an individual or entity exercising rights under this License who has not previously violated the terms of this License with respect to the Work, or who has received express permission from the Licensor to exercise rights under this License despite a previous violation.

2. **Fair Use Rights** - Nothing in this license is intended to reduce, limit, or restrict any rights arising from fair use, first sale or other limitations on the exclusive rights of the copyright owner under copyright law or other applicable laws.
3. **License Grant** - Subject to the terms and conditions of this License, Licensor hereby grants You a worldwide, royalty-free, non-exclusive, perpetual (for the duration of the applicable copyright) license to exercise the rights in the Work as stated below:
 - a. to reproduce the Work, to incorporate the Work into one or more Collective Works, and to reproduce the Work as incorporated in the Collective Works;
 - b. to create and reproduce Derivative Works;
 - c. to distribute copies or phonorecords of, display publicly, perform publicly, and perform publicly by means of a digital audio transmission the Work including as incorporated in Collective Works;
 - d. to distribute copies or phonorecords of, display publicly, perform publicly, and perform publicly by means of a digital audio transmission Derivative Works.

- e. For the avoidance of doubt, where the work is a musical composition:
 - i. Performance Royalties Under Blanket Licenses. Licensor waives the exclusive right to collect, whether individually or via a performance rights society (e.g. ASCAP, BMI, SESAC), royalties for the public performance or public digital performance (e.g. webcast) of the Work.
 - ii. Mechanical Rights and Statutory Royalties. Licensor waives the exclusive right to collect, whether individually or via a music rights agency or designated agent (e.g. Harry Fox Agency), royalties for any phonorecord You create from the Work ("cover version") and distribute, subject to the compulsory license created by 17 USC Section 115 of the US Copyright Act (or the equivalent in other jurisdictions).
- f. Webcasting Rights and Statutory Royalties. For the avoidance of doubt, where the Work is a sound recording, Licensor waives the exclusive right to collect, whether individually or via a performance-rights society (e.g. SoundExchange), royalties for the public digital performance (e.g. webcast) of the Work, subject to the compulsory license created by 17 USC Section 114 of the US Copyright Act (or the equivalent in other jurisdictions).

The above rights may be exercised in all media and formats whether now known or hereafter devised. The above rights include the right to make such modifications as are technically necessary to exercise the rights in other media and formats. All rights not expressly granted by Licensor are hereby reserved.

4. **Restrictions** - The license granted in Section 3 above is expressly made subject to and limited by the following restrictions:
 - a. You may distribute, publicly display, publicly perform, or publicly digitally perform the Work only under the terms of this License, and you must include a copy of, or the Uniform Resource Identifier for, this License with every copy or phonorecord of the Work You distribute, publicly display, publicly perform, or publicly digitally perform. You may not offer or impose any terms on the Work that alter or restrict the terms of this License or the recipients' exercise of the rights granted hereunder. You may not sublicense the Work. You must keep intact all notices that refer to this License and to the disclaimer of warranties. You may not distribute, publicly display, publicly perform, or publicly digitally perform the Work with any technological measures that control access or use of the Work in a manner inconsistent with the terms of this License Agreement. The above applies to the Work as incorporated in a Collective Work, but this does not require the Collective Work apart from the Work itself to be made subject to the terms of this License. If you create a Collective Work, upon notice from any Licensor You must, to the extent practicable, remove from the Collective Work any credit as required by clause 4(b), as requested. If you create a Derivative Work, upon notice from any Licensor You must, to the extent practicable, remove from the Derivative Work any credit as required by clause 4(b), as requested.

- b. If you distribute, publicly display, publicly perform, or publicly digitally perform the Work or any Derivative Works or Collective Works, You must keep intact all copyright notices for the Work and provide, reasonable to the medium or means You are utilizing: (i) the name of the Original Author (or pseudonym, if applicable) if supplied, and/or (ii) if the Original Author and/or Licensor designate another party or parties (e.g. a sponsor institute, publishing entity, journal) for attribution in Licensor's copyright notice, terms of service or by other reasonable means, the name of such party or parties; the title of the Work if supplied; to the extent reasonably practicable, the Uniform Resource Identifier, if any, that Licensor specifies to be associated with the Work, unless such URI does not refer to the copyright notice or licensing information for the Work; and in the case of a Derivative Work, a credit identifying the use of the Work in the Derivative Work (e.g., "French translation of the Work by Original Author," or "Screenplay based on original Work by Original Author"). Such credit may be implemented in any reasonable manner; provided, however, that in the case of a Derivative Work or Collective Work, at a minimum such credit will appear where any other comparable authorship credit appears and in a manner at least as prominent as such other comparable authorship credit.
5. **Representations, Warranties and Disclaimer** - UNLESS OTHERWISE MUTUALLY AGREED TO BY THE PARTIES IN WRITING, LICENSOR OFFERS THE WORK AS-IS AND MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND CONCERNING THE WORK, EXPRESS, IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, WITHOUT LIMITATION, WARRANTIES OF TITLE, MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NONINFRINGEMENT, OR THE ABSENCE OF LATENT OR OTHER DEFECTS, ACCURACY, OR THE PRESENCE OF ABSENCE OF ERRORS, WHETHER OR NOT DISCOVERABLE. SOME JURISDICTIONS DO NOT ALLOW THE EXCLUSION OF IMPLIED WARRANTIES, SO SUCH EXCLUSION MAY NOT APPLY TO YOU.
6. **Limitation on Liability** - EXCEPT TO THE EXTENT REQUIRED BY APPLICABLE LAW, IN NO EVENT WILL LICENSOR BE LIABLE TO YOU ON ANY LEGAL THEORY FOR ANY SPECIAL, INCIDENTAL, CONSEQUENTIAL, PUNITIVE OR EXEMPLARY DAMAGES ARISING OUT OF THIS LICENSE OR THE USE OF THE WORK, EVEN IF LICENSOR HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.
7. **Termination** -
 - a. This License and the rights granted hereunder will terminate automatically upon any breach by you of the terms of this License. Individuals or entities who have received Derivative Works or Collective Works from You under this License, however, will not have their licenses terminated provided such individuals or entities remain in full compliance with those licenses. Sections 1, 2, 5, 6, 7, and 8 will survive any termination of this License.
 - b. Subject to the above terms and conditions, the license granted here is perpetual (for the duration of the applicable copyright in the Work). Notwithstanding the above, Licensor reserves the right to release the Work under different license terms or to stop distributing the Work at any time; provided, however that any such election will not serve to withdraw this License (or any other license that has been, or is required to be, granted under the terms of this License), and this License will continue in full force and effect unless terminated as stated above.

8. Miscellaneous -

- a. Each time you distribute or publicly digitally perform the Work or a Collective Work, the Licensor offers to the recipient a license to the Work on the same terms and conditions as the license granted to you under this License.
- b. Each time you distribute or publicly digitally perform a Derivative Work, Licensor offers to the recipient a license to the original Work on the same terms and conditions as the license granted to you under this License.
- c. If any provision of this License is invalid or unenforceable under applicable law, it shall not affect the validity or enforceability of the remainder of the terms of this License, and without further action by the parties to this agreement, such provision shall be reformed to the minimum extent necessary to make such provision valid and enforceable.
- d. No term or provision of this License shall be deemed waived and no breach consented to unless such waiver or consent shall be in writing and signed by the party to be charged with such waiver or consent.
- e. This License constitutes the entire agreement between the parties with respect to the Work licensed here. There are no understandings, agreements or representations with respect to the Work not specified here. Licensor shall not be bound by any additional provisions that may appear in any communication from you. This License may not be modified without the mutual written agreement of the Licensor and You.

Creative Commons is not a party to this License, and makes no warranty whatsoever in connection with the Work. Creative Commons will not be liable to you or any party on any legal theory for any damages whatsoever, including without limitation any general, special, incidental or consequential damages arising in connection to this license. Notwithstanding the foregoing two (2) sentences, if Creative Commons has expressly identified itself as the Licensor hereunder, it shall have all rights and obligations of Licensor.

Except for the limited purpose of indicating to the public that the Work is licensed under the CCPL, neither party will use the trademark "Creative Commons" or any related trademark or logo of Creative Commons without the prior written consent of Creative Commons. Any permitted use will be in compliance with Creative Commons' then-current trademark usage guidelines, as may be published on its website or otherwise made available upon request from time to time.

Creative Commons may be contacted at <http://creativecommons.org/>.

D.1.9 Notice Concerning Usage of JQuery

jQuery Foundation projects are released under the terms of the license specified in the project's repo or if not specified, under the MIT license.

<https://tldrlegal.com/license/mit-license>

The MIT License is simple and easy to understand and it places almost no restrictions on what you can do with a jQuery Foundation project.

You are free to use any jQuery Foundation project in any other project (even commercial projects) as long as the copyright header is left intact.

D.1.10 Notice Concerning Usage of SLF4J

The following files are covered under the SLF4J license:

- slf4j-api-1.6.4.jar
- jcl-over-slf4j-1.6.4.jar

SLF4J License

SLF4J source code and binaries are distributed under the MIT license.

Copyright (c) 2004-2013 QOS.ch

All rights reserved.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

D.1.11 Notice Concerning Usage of Staxmate

Copyright (c) 2007, Tatu Saloranta

All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- * Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- * Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- * Neither the name of the <organization> nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY <copyright holder> "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL <copyright holder> BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

D.1.12 Notice Concerning Usage of XMLPULL

XMLPULL API IS FREE

All of the XMLPULL API source code, compiled code, and documentation contained in this distribution *except* for tests (see separate LICENSE_TESTS.txt) are in the Public Domain.

XMLPULL API comes with NO WARRANTY or guarantee of fitness for any purpose.

Initial authors: Stefan Haustein and Aleksander Slominski

2001-12-12

D.1.13 Notice Concerning Usage of XStream

XStream is open source software, made available under a BSD license.

Copyright (c) 2003-2006, Joe Walnes

Copyright (c) 2006-2009, 2011 XStream Committers

All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
3. Neither the name of XStream nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

D.1.14 Notice Concerning Usage of YUI

Copyright © 2013 Yahoo! Inc. All rights reserved.

Redistribution and use of this software in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- * Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- * Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- * Neither the name of Yahoo! Inc. nor the names of YUI's contributors may be used to endorse or promote products derived from this software without specific prior written permission of Yahoo! Inc.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.