

**Oracle® Retail Order Broker Cloud  
Service 19.0**

Administration Guide

December 2019

Copyright © 2019, Oracle and/or its affiliates. All rights reserved.

Primary Author: Elise Kaplan

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this software or related documentation is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information on content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

## Oracle Retail VAR Applications

The following restrictions and provisions only apply to the programs referred to in this section and licensed to you. You acknowledge that the programs may contain third party software (VAR applications) licensed to Oracle. Depending upon your product and its version number, the VAR applications may include:

(i) the MicroStrategy Components developed and licensed by MicroStrategy Services Corporation (MicroStrategy) of McLean, Virginia to Oracle and imbedded in the MicroStrategy for Oracle Retail Data Warehouse and MicroStrategy for Oracle Retail Planning & Optimization applications.

(ii) the Wavelink component developed and licensed by Wavelink Corporation (Wavelink) of Kirkland, Washington, to Oracle and imbedded in Oracle Retail Mobile Store Inventory Management.

(iii) the software component known as Access Via™ licensed by Access Via of Seattle, Washington, and imbedded in Oracle Retail Signs and Oracle Retail Labels and Tags.

(iv) the software component known as Adobe Flex™ licensed by Adobe Systems Incorporated of San Jose, California, and imbedded in Oracle Retail Promotion Planning & Optimization application.

You acknowledge and confirm that Oracle grants you use of only the object code of the VAR Applications. Oracle will not deliver source code to the VAR Applications to you. Notwithstanding any other term or condition of the agreement and this ordering document, you shall not cause or permit alteration of any VAR Applications. For purposes of this section, "alteration" refers to all alterations, translations, upgrades, enhancements, customizations or modifications of all or any portion of the VAR Applications including all reconfigurations, reassembly or reverse assembly, re-engineering or reverse engineering and recompilations or reverse compilations of the VAR Applications or any derivatives of the VAR Applications. You acknowledge that it shall be a breach of the agreement to utilize the relationship, and/or confidential information of the VAR Applications for purposes of competitive discovery.

The VAR Applications contain trade secrets of Oracle and Oracle's licensors and Customer shall not attempt, cause, or permit the alteration, decompilation, reverse engineering, disassembly or other reduction of the VAR Applications to a human perceivable form. Oracle reserves the right to replace, with functional equivalent software, any of the VAR Applications in future releases of the applicable program.

---

---

# Contents

Send Us Your Comments .....	v
<b>Preface .....</b>	<b>vi</b>
Audience .....	1-vi
Documentation Accessibility .....	1-vi
Customer Support .....	1-vi
Improved Process for Oracle Retail Documentation Corrections .....	1-vii
Oracle Retail Documentation on the Oracle Help Center .....	1-vii
Conventions .....	1-vii
<b>1 Setting Up Data</b>	
Before You Start .....	1-2
Logging in for the First Time .....	1-2
Creating an Organization .....	1-2
Creating the Default System .....	1-4
Creating Each Additional System that will Integrate with Order Broker .....	1-6
Creating User Profiles .....	1-8
Before You Start: Background on IDCS Integration .....	1-8
IDCS User Synchronization .....	1-9
Scheduling the Identity Cloud User Synchronization Job .....	1-13
Assigning the Default Shipping System to the Admin User Profile .....	1-13
Uploading Proximity Data .....	1-13
Creating Location Types .....	1-14
Setting up a Default Carrier and, Optionally, Additional Carriers .....	1-15
Creating the Default Unfulfillable Location .....	1-17
Setting up Preferences for your Organization .....	1-17
Scheduling Jobs .....	1-21
About Scheduling Imports .....	1-22
Restart All .....	1-22
Adjust and Save Preferences .....	1-23
Setting up Web Service Authentication .....	1-24

---

---

## Send Us Your Comments

Oracle welcomes customers' comments and suggestions on the quality and usefulness of this document.

Your feedback is important, and helps us to best meet your needs as a user of our products. For example:

- Are the implementation steps correct and complete?
- Did you understand the context of the procedures?
- Did you find any errors in the information?
- Does the structure of the information help you with your tasks?
- Do you need different information or graphics? If so, where, and in what format?
- Are the examples correct? Do you need more examples?

If you find any errors or have any other suggestions for improvement, then please tell us your name, the name of the company who has licensed our products, the title and part number of the documentation and the chapter, section, and page number (if available).

---

---

**Note:** Before sending us your comments, you might like to check that you have the latest version of the document and if any concerns are already addressed. To do this, access the Online Documentation available on the Oracle Help Center Web site. It contains the most current Documentation Library plus all documents revised or released recently.

---

---

Send your comments to us using the electronic mail address: [retail-doc\\_us@oracle.com](mailto:retail-doc_us@oracle.com)

Please give your name, address, electronic mail address, and telephone number (optional).

If you need assistance with Oracle software, then please contact your support representative or Oracle Support Services.

If you require training or instruction in using Oracle software, then please contact your Oracle local office and inquire about our Oracle University offerings. A list of Oracle offices is available on our Web site at <http://www.oracle.com>.

---

---

# Preface

Order Broker Cloud Service Administration Guide describes the process an administrator follows to set up essential data for the Routing Module.

## Audience

This Administration Guide is intended for administrators who are responsible for system configuration.

## Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <http://www.oracle.com/us/corporate/accessibility/index.html>.

### Access to Oracle Support

Customers that have purchased support have access to electronic support at My Oracle Support. For information, visit

<http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit

<http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

- 

- *Oracle Retail Order Broker Cloud Service Store Connect Online Help*

See the

<https://www.oracle.com/documentation/retail.html>

## Customer Support

To contact Oracle Customer Support, access My Oracle Support at the following URL:

<https://support.oracle.com>

When contacting Customer Support, please provide the following:

- Product version and program/module name
- Functional and technical description of the problem (include business impact)
- Detailed step-by-step instructions to re-create
- Exact error message received
- Screen shots of each step you take

## Improved Process for Oracle Retail Documentation Corrections

To more quickly address critical corrections to Oracle Retail documentation content, Oracle Retail documentation may be republished whenever a critical correction is needed. For critical corrections, the republication of an Oracle Retail document may at times not be attached to a numbered software release; instead, the Oracle Retail document will simply be replaced on the Oracle Help Center Web site.

This process will prevent delays in making critical corrections available to customers. For the customer, it means that you must verify that you have the most recent version of the Oracle Retail documentation set. Oracle Retail documentation is available on the Oracle Help Center at the following URL:

<https://www.oracle.com/documentation/retail.html>

An updated version of the applicable Oracle Retail document is indicated by Oracle part number, as well as print date (month and year). An updated version uses the same part number, with a higher-numbered suffix. For example, part number E123456-02 is an updated version of a document with part number E123456-01.

If a more recent version of a document is available, that version supersedes all previous versions.

## Oracle Retail Documentation on the Oracle Help Center

Oracle Retail product documentation is available on the following web site:

<https://www.oracle.com/documentation/retail.html>

## Conventions

The following text conventions are used in this document:

Convention	Meaning
<b>boldface</b>	Boldface type indicates graphical user interface elements associated with an action, emphasis, screen names, book titles, or terms defined in text or the glossary.
<i>italic</i>	Italic type indicates field labels or placeholder variables for which you supply particular values.
monospace	Monospace type indicates commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter.

---

---

## Setting Up Data

**Purpose:** Follow the steps below to set up data for the Routing Module as part of Order Broker installation. The Routing Module enables you to search for locations to fulfill orders, create orders across the enterprise, and track order activity.

**Other setup steps and options:** See the Online Help for more information on setting up data, including steps for configuration of the Routing Engine, as well as steps required for:

- Configuring the Supplier Direct Fulfillment module
- Configuring the Store Connect module
- Additional configuration options, such as probability rules and zone fulfillment
- Testing operations, such as searching for locations and creating orders
- Details on importing and exporting data, including additional import and export options
- Changing the time zone for screens, reports, emails, and order update history

---

---

**Note:** For a cloud implementation, Oracle staff need to make sure that any external URLs are added to the proxy server's white list.

---

---

### In this chapter:

- [Before You Start](#) on page 1-2
- [Logging in for the First Time](#) on page 1-2
- [Creating an Organization](#) on page 1-2
- [Creating the Default System](#) on page 1-4
- [Creating Each Additional System that will Integrate with Order Broker](#) on page 1-6
- [Creating User Profiles](#) on page 1-8
  - [Before You Start: Background on IDCS Integration](#) on page 1-8
  - [IDCS User Synchronization](#) on page 1-9
  - [Scheduling the Identity Cloud User Synchronization Job](#) on page 1-13
- [Assigning the Default Shipping System to the Admin User Profile](#) on page 1-13

- [Uploading Proximity Data](#) on page 1-13
- [Creating Location Types](#) on page 1-14
- [Setting up a Default Carrier and, Optionally, Additional Carriers](#) on page 1-15
- [Creating the Default Unfulfillable Location](#) on page 1-17
- [Setting up Preferences for your Organization](#) on page 1-17
- [Scheduling Jobs](#) on page 1-21
  - [About Scheduling Imports](#) on page 1-22
  - [Restart All](#) on page 1-22
  - [Adjust and Save Preferences](#) on page 1-23
- [Setting up Web Service Authentication](#) on page 1-24

## Before You Start

Before you begin configuration of Order Broker, you need:

- **URL:** The URL to use when logging into Order Broker.
- **Default user profile:** A default admin user profile for you to use when completing configuration in Order Broker, including creating additional users, configuring systems, setting preferences, and importing data.

Contact your Oracle representative for the user ID of the default admin user. This user needs to exist in both Order Broker and Oracle Identity Cloud Service (IDCS).

You will need to assign the *Default Shipping System* to the user profile once you have completed these configuration steps below.

- **New install:** You need to create all users in IDCS to map to all users in Order Broker, including Order Broker users, Store Connect users, vendor users, and web service users. See [Creating User Profiles](#) for more information.
- **Upgrade to release 19.0 or higher:** You need to create all users in IDCS before users can begin using Order Broker, including Order Broker users, Store Connect users, vendor users, and web service users, if their records do not already exist in IDCS. Users can use the *Can't sign in?* link at the login page to set their passwords.

See [Creating User Profiles](#) for more information on creating users.

## Logging in for the First Time


**Use IDCS:** You need to select the *Use IDCS* flag at the Tenant-Admin screen if it is not already selected. To display this screen, select **Systems > Tenant** while logged in as the default admin user. If the flag is not already selected, select it now.

## Creating an Organization

**About organizations:** The organization is the second level in the Order Broker hierarchy, below the tenant. All systems are assigned to a single organization, and item searching, order creation, and drop ship fulfillment takes place within the organization. You need at least one organization.

**For more information:** See the **Order Broker Routing Engine Overview** in the Online Help for a discussion of the organization hierarchy.

1. Select **Organizations and Preferences** at the home screen.



2. At the **Organizations and Preferences** screen:

- Enter the organization code in the *Organization* field. The organization code can be 1 to 10 positions long, can include spaces and special characters, and must be unique within Order Broker.
- Enter the name for the organization in the *Name* field. The name can be from 1 to 35 positions long, and can include spaces and special characters.
- Click **New**.

Organizations and Preferences

Organization  Name

**Search** **New**

**Search Results**

- At the **New Organization** screen:
  - \* Confirm your entries in the *Organization* and *Name* fields.
  - \* If ship-for-pickup orders will not be enabled, set the *Enable Ship For Pickup* option to **No**.

---

**Important:** See the Routing Engine Overview in the Operations Guide or the online help for considerations on enabling ship-for-pickup.

---

- \* Complete the **Data Formats** fields to control the formats for reports, forms, and system-generated emails.

**New Organization**

Organization

---

Name  Save Cancel

Enable Ship For Pickup  Yes  No

This setting controls whether to support ship-for-pickup orders rather than retail pickup and ship-to-store orders. The ship-for-pickup order type can use a sourcing location that is different from the placed location or the pickup location.

No: Select only if your external system does not support a separate sourcing location, and you need to process retail pickup and ship-to-store orders.

Yes: Select to support a single ship-for-pickup order type. Once you select this setting, you cannot reverse it.

**Data Formats**

Language	<input type="text" value="United States-English"/>	*
Date Format	<input type="text" value="MM/DD/YYYY"/>	*
Time Format	<input type="text" value="AM/PM"/>	*
Decimal Separator	<input type="text" value="Period"/>	*
Thousands Separator	<input type="text" value="Comma"/>	*

- \* Click **Save**.

## Creating the Default System

**About systems:** Each system in Order Broker represents an application, such as Oracle Retail Order Management System Cloud Service, CWDirect, or Xstore, that shares inventory information via Order Broker and creates cross-channel orders or purchase orders.

**About the default system:** The default system identifies the application that is the system of record for product creation and naming. The first system created for your organization is automatically flagged as the default. System product codes in other systems are cross references to the products in the default system.

---

**Note:** If you integrate with Oracle Retail Order Management System Cloud Service or with CWDirect, the system code should be the same as the company number, without padding zeros: for example, 6 rather than 006. Also, the code for the system must match the setting of the *Locate System (K50)* system control value.

---




---


**Note:** The system flagged as the Vendor Default should not be the default system for the organization.

---

1. Select **Systems > Systems** to advance to the **Systems** screen.



2. At the **System** screen:
3. Select an organization from the *Organization* drop-down box.
  - Enter a system code in the *System* field. System codes can be 1 to 10 positions in length, can include spaces and special characters, and must be unique.
  - For Order Management System or CWDirect, the system code should be the same as the company number, without padding zeros.
  - Optionally, enter a name in the *Name* field. Names can be 1 to 40 positions in length and can include spaces and special characters. If you do not enter a name here, you need to enter it at the System screen when creating a system.



- Click **New**. If:
  - \* The system already exists in the organization, or if you did not select an organization or enter a *System* code, Order Broker displays an error message;

## Creating Each Additional System that will Integrate with Order Broker

- \* Otherwise, you advance to the **System** screen, where you can complete the creation of the system.

### System

Organization: New - New updated \*

System: sample \*

Name: \*

Organization Default:

Vendor Default:

Store Connect Default:

Inventory | Orders | Reservation | RICS Integration | OCDS Integration Import

Online:

Probable Qty Export:

Track Fulfilled Qty: Do Not Track Fulfilled

Connection Type: None

#### Note:

- If you click **Cancel** at the **System** screen after clicking **New**, the system is not created.
- The *Organization Default* flag is selected when you create the first system for an organization, and the flag cannot be unselected at this time. To designate a different system as the default, you need to create another system and flag that system as the default; this unflags the first system.

**Order Management System or CWDirect integration:** The code for the Order Management System or CWDirect system must match the setting of the *OROB System (K50)* or *Locate System (K50)* system control value. However, names for systems do not need to be the same as the Order Management System or CWDirect company descriptions.

**For more information:** See the **System** screen in the Online Help for information on additional system configuration options.

## Creating Each Additional System that will Integrate with Order Broker


Follow the steps below to create:

- A default vendor system, if you will use the Supplier Direct Fulfillment module.


**Note:** The system flagged as the Vendor Default should not be the default system for the organization.

- The Store Connect system, if you will use the Store Connect module.
- Each additional system, such as a POS system.

1. Select **Systems** > **System**.



2. At the **System** screen, select your organization from the *Organization* drop-down box.



3. Enter a system code in the *System* field. System codes can be 1 to 10 positions in length, can include spaces and special characters, and must be unique within the organization.
4. Enter a name in the *Name* field. Names can be 1 to 40 positions in length and can include spaces and special characters. If you do not enter a name here, you need to enter it at the **System** screen when creating a system.
5. Select **New**:
  - If the system already exists in the organization, or if you did not select an organization or enter a system code, Order Broker displays an error message;

- Otherwise, you advance to the **System** screen, where you can complete the creation of the system.

[/stem](#)

- Select **Save**.

**Note:** If you select **Cancel** at the **System** screen without first selecting **Save**, the system is not created.

See the **System** screen in the Online Help for information on the fields and options available at this screen.

## Creating User Profiles

**In this section:**

- [Before You Start: Background on IDCS Integration](#)
- [IDCS User Synchronization](#)
  - [Required Setup in Order Broker for Identity Cloud Service User Synchronization](#)
  - [User Creation in IDCS](#)
  - [Importing Users through the Identity Cloud User Synchronization Job](#)
  - [Creating Vendor Users](#)
  - [Creating Store Associate Users](#)
- [Scheduling the Identity Cloud User Synchronization Job](#)

### Before You Start: Background on IDCS Integration

**Background on user mapping with IDCS and user setup:**

- Authentication for all users takes place using the password defined for the user in Oracle Identity Cloud Service (IDCS); however, if OAuth authentication is enabled, the user ID defined in Order Broker for a Web Service user maps to a client ID defined in IDCS, and IDCS defines a token for web service authentication, rather than a password.

**About OAuth:** OAuth is a standard for web service authentication through the use of access tokens rather than passwords.

- Role assignments in Order Broker control the user's screen and feature authority at Order Broker, Store Connect, and Vendor Portal screens. You can change the role assignments for existing users through the **Role Wizard**. See the *Role Wizard* in the online help for more information.
- No role authority is required for web service users.
- Since Order Broker requires a lower case user ID, you should create lower case user IDs in IDCS for validation into Order Broker.
- When the user logs into Order Broker or Store Connect, the user ID entered at the login screen must match the user ID in IDCS. If the user ID in IDCS is the Cloud Service User ID, then the user enters the Cloud Service User ID at the login screen.
- User ID matching is case-sensitive, whether through the Order Broker user ID or the Cloud Service User ID.
- Order Broker, Store Connect, and vendor users can use the *Can't sign in?* link at the login page to reset their passwords.

**Multiple omni-channel systems:** You can use the same IDCS user records for multiple omni-channel systems. You can use the Cloud Service User ID as a cross-reference to Order Broker users and Store Connect users, but this option is not available for Vendor Portal users or web service users. You can also use the same user ID for any user type, except that Order Broker requires a lowercase user ID, as noted above.

Although Order Management System uses an uppercase user ID, user validation is not case-sensitive, so a lowercase user ID from IDCS passes validation.

**Authentication for outbound web service requests:** Use IDCS to set up users for the authentication of web service requests across omni-channel systems, such as Order Management System Cloud Service or Customer Engagement Cloud Services if the omni-channel systems use the same instance of IDCS.

## IDCS User Synchronization

**About identity cloud service user synchronization:** Use IDCS to create users for omnichannel applications, including Order Broker and Oracle Retail Order Management System Cloud Service. Users that exist in IDCS and are configured there for Order Broker access are then created in Order Broker:

- Through the **Identity Cloud User Synchronization** job, available through the **Schedule Jobs** screen, or,
- Automatically, when the user logs into Order Broker.

Users are created in Order Broker with the default authority defined from IDCS, described below.

If you need to create Store Associate users and/or Vendor users in addition to Order Broker users, see [Creating Vendor Users](#) or [Creating Store Associate Users](#), below.

The **Identity Cloud User Synchronization** job does not delete, deactivate, or update authority for any user records, including vendor users and store associates, in Order Broker. Use the related screen in Order Broker to update users once they have been created.

**Web service authentication:** The **Identity Cloud User Synchronization** job does not create web service users. See [Setting up Web Service Authentication](#) for information on creating web service users.

### Required Setup in Order Broker for Identity Cloud Service User Synchronization

The following steps describe creating Order Broker (retailer) user profiles.

**Setup at the Tenant (admin) screen:** Complete the **Identity Cloud Service** settings at the **Tenant** screen:

- **User IDCS:** This flag must be selected.
- **Client ID:** The Name identifying Order Broker as an application in IDCS. Typically formatted as `RGBU_OBCS_ENV_APPID` where `OBCS` identifies Order Broker and `ENV` identifies the environment, such as production.
- **Endpoint URL:** The URL to use for requests to IDCS.
- **Client Secret:** The client secret assigned by IDCS and used for authentication. Select **Show Secret** in the Configuration tab in IDCS to display the secret.

See the **Tenant (admin)** screen in the online help for more information.

**About the default user:** The `default` user is created automatically, with a user name of Identity Cloud Default User. This is not an actual user record that can log into Order Broker; instead, it serves as a template for creating actual users. You cannot delete the `default` user.

**Configuring the default user:** Before creating additional, actual users, update the `default` user with the settings to apply to actual users when they are created in Order Broker:

- Role assignments with a *Role Type* of **Retailer**, controlling the default authority to Order Broker screens. See the Role Wizard for more information.
- The *Default Shipping System* that controls system product code to display as the **Item #** at the **Order** screen, as well as the organization to default at other screens.

**Multiple groups of users:** You can modify the configuration of the `default` user if you will import multiple groups of users into Order Broker. For example, you could first configure the `default` user with just order inquiry and maintenance authority, import a group of users, and then reconfigure the `default` user with different authority for the next group of users.

### User Creation in IDCS

You can use the following process in IDCS to create users and control their attributes through group assignment, using the application record in IDCS for Order Broker. The application record typically has a *Name* such as `RGBU_OBCS_<ENV>_APPID`, where `ENV` represents the environment.

- Create one or more groups to use for assignment of roles to users. For example, create an `ob_users` group to use for creation of regular users, and an `ob_admin` group to use for creation of admin users. Assign the group to the appropriate application role in IDCS: either `OBCS_Admin` or `OBCS_User`.
- Create each user in IDCS, specifying the user's first name, last name, user name, and email address.

**About defining the user name in IDCS:**

- The user name be lower case.
- The user name in Order Broker cannot exceed 10 positions, so the name assigned in IDCS will be truncated in Order Broker if it exceeds 10 positions. If multiple users imported from IDCS share the same first 10 positions of the user name, the import process will use the first 9 positions and assign a unique character as the 10th position. For example, if user names created in IDCS are joanneohjnsn and joannejohnston, the first user created in Order Broker is joannejoh1, and the second user created in Order Broker is joannejoh2.
  - \* Assign each created user to the appropriate group.
  - \* Assign each group to the Order Broker application in IDCS.
  - \* Assign each user to the appropriate application role in IDCS.
  - \* Assign or reset the password for each user in IDCS. This triggers an email to the email address specified for the user, who can log in using either the user name defined in IDCS if it does not exceed 10 positions, or the email address.

---

**Note:** If the user logs in after configuration in IDCS, this creates the user record in Order Broker; otherwise, the record is created through the import job, described below.

---

### Importing Users through the Identity Cloud User Synchronization Job

After completing the required setup describe above, Select **Systems > Schedule Jobs** and run the **Identity Cloud User Synchronization** job to import the new users from IDCS.

#### Schedule Jobs

##### Identity Cloud User Synchronization

This job synchronizes users created in Identity Cloud Service.

Each new user is created in Order Broker with the application role assignments from IDCS:

- The user ID, name, email address, and cloud service user ID are from IDCS; however, if the user ID is longer than 10 positions or is a duplicate of an existing user ID of 10 positions, it is truncated as described above.
- The admin flag is selected if the user is assigned to the OBCS\_Admin application role in IDCS.
- The role-based authority is from the default user's current settings.

**After creation:** Once users are created in Order Broker, you can maintain them; for example, you can change the email address, date formats, user name, authority, and default shipping system for Order Broker users, and you can flag a user as inactive so that the user cannot log in; however, this does not update the user's record in IDCS. You can also delete the users from Order Broker, although this does not delete the corresponding records in IDCS, and the user would be created again in Order Broker the next time the synchronization job runs.

---



---

**Note:** The synchronization job does not update existing users in Order Broker.

---



---

### Creating Vendor Users

If you also need to create vendor users in Order Broker, use the following process:

- In Order Broker, create one or more vendors. See the **Vendors** screen in the online help for more information.
- In Order Broker, create one or more role assignments with a *Role Type* of **Vendor**, controlling the default authority to Vendor Portal screens. Select the *Identity Cloud User Default* flag at the **Specify Role Name** step of the **Role Wizard**.
- In Order Broker, run the **Identity Cloud User Synchronization** job to create the vendor user groups in IDCS corresponding to each vendor created in Order Broker. The vendor user group is created as <system>|<vendor>, where <system> is the system code identifying the default vendor system, and <vendor> is the code identifying the vendor. The synchronization job performs this creation in IDCS each time it runs based on the existing roles in Order Broker.
- In IDCS, assign each vendor user group to the OBCS\_Vendor\_User application role for the Order Broker application.
- In IDCS, create each vendor user and assign it to the vendor user group associated with the same vendor. See [User Creation in IDCS](#) for background on creating the user in IDCS and notes about defining the user name.

---



---

**Note:** Assign the vendor user only to the vendor user group associated with the correct vendor. Order Broker does not support assigning a vendor user to more than one vendor.

---



---

- Run the **Identity Cloud User Synchronization** job again to import new vendor users from IDCS. The vendor users are assigned role-based authority based on the vendor role types set up through the **Role Wizard** with the *Identity Cloud User Default* flag selected.

---



---

**Note:** The synchronization job does not update existing vendor users in Order Broker.

---



---

### Creating Store Associate Users

If you also need to create store associate users in Order Broker, use the following process:

- In Order Broker, create the default Store Connect system for your organization. See the **Systems** screen in the online help for more information.

- In Order Broker, create one or more role assignments with a *Role Type* of **Store Associate**, controlling the default authority to Store Connect screens. Select the *Identity Cloud User Default* flag at the **Specify Role Name** step of the **Role Wizard**.
- In Order Broker, run the **Identity Cloud User Synchronization** job to create store user groups in IDCS for each system that is flagged as the Store Connect default for an organization. The user group is named *STC-SYSTEM*, where *SYSTEM* is the system code of the Store Connect default system in your organization. The synchronization job performs this creation in IDCS each time it runs based on the existing roles in Order Broker.
- In IDCS, assign each store user group to the *OBCS\_Store\_User* role.
- In IDCS, create each store associate user and assign it to the store user group associated with the appropriate system. See [User Creation in IDCS](#) for background on creating the user in IDCS and notes about defining the user name.
- In Order Broker, run the **Identity Cloud User Synchronization** job again to import new store associate users from IDCS.
- Use the **Edit Store Associate User Profile** screen to finish configuration of the store associate user, including assigning one or more locations and flagging the user as active. The *Requires Location* field at the **Store Associate User Profiles** screen indicates that the store associate user requires location assignment.

---

---

**Note:** The synchronization job does not update existing store associate users in Order Broker.

---

---

### Scheduling the Identity Cloud User Synchronization Job

Schedule the **Identity Cloud User Synchronization** job to run daily.

## Assigning the Default Shipping System to the Admin User Profile

Follow the steps above under [Creating User Profiles](#) on page 1-8 to assign the *Default Shipping System* to the Admin user profile. The *Default Shipping System* assigned to a user indicates the system product code to display on Order Broker screens.

---

---

**Note:** The *Default Shipping System* is not a required field at the User Profile screen if you have not yet created any systems in Order Broker.

---

---

## Uploading Proximity Data

**About proximity data:** Proximity data enables you to search for merchandise or assign orders based on the approximate distance from a store, warehouse, or customer address.

---

---

**Note:** This step is required only if you are using proximity locator searching for locations through the Routing Engine, and only if you are not using the Oracle Maps Cloud Service. You can also perform this step at a later time.

---

---

If you are using Proximity Locator searching to restrict locate items searches or order assignment based on geographical location, and if you are not using the Oracle Maps Cloud Service, obtain the required .CSV file of postal code information before you begin the upload:

1. Select **Systems > Proximity Uploads**.



2. At the **Proximity Uploads** screen:

- Select **Canada, International, or United States** from the *Proximity Data Type* drop-down list.
- Enter the *Country Code* to apply to proximity records.
- Use the **Choose Files...** button below the *File Name* field to select the .CSV file on your local computer.
- Select **Upload**.



3. Wait until the upload status is completed. Optionally, you can select **Refresh** to check the status.

**For more information:** See the **Proximity Uploads** screen in the Online Help for more information, including the file layout and troubleshooting. Also, see the **Order Broker Routing Engine Overview** in the Online Help or the Operations Guide for a discussion of proximity locator searching and preferences, including the use of the Oracle Maps Cloud Service.

## Creating Location Types

**About location types:** Location types identify a group of locations based on the system to which they belong, such as your order management system or your POS system, as well as their function, such as distribution center or retail store.

At least one location type is required for you to create locations.

1. Select **Locations > Location Types**.



2. At the **Location Types** screen, select your organization at the *Organization* drop-down box, if necessary.

A screenshot of the 'Location Types' screen. At the top, there are tabs for 'Location Types' and 'Search', and a 'New' button. Below the tabs are four input fields: 'Organization' (a drop-down menu), 'Type' (a text field), 'Name' (a text field), and 'Category' (a drop-down menu with 'S - Store' selected). Below the form is a 'Search Results' section with a table. The table has columns for 'Organization', 'Type', 'Name', 'Category', 'Edit', and 'Delete'. One row is visible with 'Store' in the 'Category' column. The 'Edit' column has a plus icon, and the 'Delete' column has a trash icon.

3. In the *Type* field, enter a code to represent the location type. The code cannot exceed 10 positions.
4. In the *Name* field, enter a name for the location type. The name cannot exceed 40 positions.
5. Select the correct category from the *Category* drop-down box.
6. Select **New**. The location type is created.

## Setting up a Default Carrier and, Optionally, Additional Carriers

**About carriers:** A carrier is required on each order. At a minimum you need to set up a default carrier, specified at the **Preferences** screen.

If the Submit Order message creating a retail pickup, delivery, or ship-to-store order:

- specifies a *ship\_via* that matches a carrier you have set up through the **Carriers** screen, Order Broker uses this carrier on the order and resets the carrier as active, if needed.
- specifies a *ship\_via* that does not match a carrier you have set up through the **Carriers** screen, Order Broker creates the carrier and uses this carrier on the order.
- does not specify a *ship\_via*, Order Broker uses the default carrier you specify at the **Preferences** screen.

Default carriers for other order types:


- For a pickup order, Order Broker uses the default PICKUP carrier it creates automatically, regardless of whether a *ship\_via* is passed in the Submit Order message.
- For a ship-to-store order, Order Broker uses the default SHIP2STORE carrier it creates automatically, regardless of whether a *ship\_via* is passed.

The following steps are required to set up the default carrier:


1. Select **Systems > Carriers**.



2. At the **Carriers** screen, select your organization if necessary and, optionally, enter a *Code* and *Description*. If you do not enter them here, you can enter them at the **New Carrier** window. Select **New**.



3. At the **New Carrier** window, complete any additional fields and select **Save**.



**For more information:** See the **Carriers** screen in the Online Help.

## Creating the Default Unfulfillable Location

**About the default unfulfillable location:** The Routing Engine assigns an order to the default unfulfillable location when it cannot find a location to fulfill the order. You need to specify a default unfulfillable location at the **Preferences** screen.

1. Select **Locations > Locations**.
2. At the **Locations** screen:
  - Select your organization if necessary.
  - In the *Type* field, select the location type. The default unfulfillable location is ordinarily a warehouse or distribution center type.
  - In the *Location* field, enter a location code. The code cannot exceed 10 positions.
  - In the *Name* field, enter a name for the location. The name cannot exceed 40 positions.
  - In the *System* field, select the default system for your organization.
  - Select **New**.
3. At the **New Location** screen, enter any additional information about the default unfulfillable location, and select **Save** to save your entries.

**For more information:** See [Setting up Preferences for your Organization](#) on page 1-17 for information on identifying the default unfulfillable location for the Routing Engine.

## Setting up Preferences for your Organization


**About preferences:** Use the **Preferences** screen to set rules governing locate item searching and order assignment. You can set preferences at the organization, location type, and location level.

**Saving again after running imports:** After you import locations, products, system products, and product locations, you will need to reopen the **Preferences** screen, make any desired updates, and select **Save** to have your preferences apply to all locations. See [Scheduling Jobs](#) on page 1-21 for more information.

1. Select **Locations > Organizations and Preferences**.




- At the **Organizations and Preferences** screen, select the *Order Broker Preferences* icon (  ) for your organization.



Orga...	Name	System	Order... Prefer...	Drop ... Prefer...	Store ... Prefer...	Edit	Delete
		23					

- At the **Preferences** screen:

- Specify basic Routing Engine options, including whether to use the Proximity Locator, the default distance to use when searching for a location, and whether to use probability rules and zone fulfillment.



Use Proximity Locator  Yes  No

Default Distance  \* miles

Use Offline Newer Than  \*

No Offline Response Action  \*

Use Probability Rules  Acknowledge Order Before Brokering

Use Zone Fulfillment  Exclude Locations with Zero Availability

Use Maximum Order Limits  Use Weighted Brokering Rules

Use Attribute Rules  Update Offline Inventory

- At the **Order Broker Settings** tab:
  - \* Specify whether to group shipment locations in responses to LocateItems requests for delivery or retail pickup orders, simply indicating whether the requested merchandise is available for shipment rather than listing locations in the LocateItems response.
  - \* Indicate whether to support splitting orders or lines, or process partial status updates for order lines.
  - \* Specify the maximum number of locations to return in a LocateItems response.
  - \* Specify the default unfulfillable location (set up through [Creating the Default Unfulfillable Location](#) on page 1-17). This location needs to have all of the Yes/No options under **Fulfillment** (*Backorder Available, Pickup Available, Delivery Available, and Retail Pickup Available, or Ship For Pickup Sourcing and Ship For Pickup Receiving/Pickup*) set to **No**.

- \* Specify the default carrier (set up through [Setting up a Default Carrier and, Optionally, Additional Carriers](#) on page 1-15).

The screenshot displays the 'Preference Options' configuration interface. On the left, a tree view shows a folder containing 'store' and 'warehouse'. The main area is titled 'Preference Options' and includes a 'Save' button. The 'Use Proximity Locator' is set to 'Yes'. 'Default Distance' is 9999 miles. 'Use Offline Newer Than' is 01:00:00. 'No Offline Response Action' is 'Use Offline'. 'Use Probability Rules' is checked, with 'Acknowledge Order Before Brokering' also checked. 'Use Zone Fulfillment' is unchecked, with 'Exclude Locations with Zero Availability' also unchecked. 'Use Maximum Order Limits' is checked, with 'Use Weighted Brokering Rules' also checked. 'Use Attribute Rules' is checked, with 'Update Offline Inventory' also checked. Below these are four tabs: 'Order Broker Settings', 'Fulfillment', 'Standard Brokering', and 'Weighted Brokering'. The 'Fulfillment' tab is active, showing 'Group Shipment Locations' unchecked, 'Allow Split Line' checked, 'Allow Split Order' checked, 'Allow Partial Updates' unchecked, 'Maximum No. Responses' set to 9, 'Default Unfulfillable Location' set to 'DEFAULT - Default Unfulfillab...', and 'Default Carrier' set to 'DEFAULT - Default Carrier'.

- At the **Fulfillment** tab:

- \* Specify the fulfillment types supported. Note that the options here differ based on whether ship-for-pickup orders are supported.
- \* Specify the priority to use for order assignment, and the maximum number of orders to assign per day.
- \* At the organization level, specify the maximum number of times to reassign (“reshop”) an order if it is rejected by the assigned fulfilling or sourcing location.
- \* If your organization supports ship-for-pickup orders, specify the sourcing distance for the Routing Engine to use when shopping for sourcing locations.

## Setting up Preferences for your Organization

- \* Also at the **Fulfillment** tab, complete the settings related to automatically canceling unclaimed pickup or ship-for-pickup orders.

Organizations and Preferences ✕ Preferences ✕

**Preferences**

Organization

**Preference Options** Save

Use Proximity Locator  Yes  No

Default Distance  \* miles \*

Use Offline Newer Than  \*

No Offline Response Action  \*

Use Probability Rules  Acknowledge Order Before Brokering

Use Zone Fulfillment  Exclude Locations with Zero Availability

Use Maximum Order Limits  Use Weighted Brokering Rules

Use Attribute Rules  Update Offline Inventory

Order Broker Settings **Fulfillment** **Standard Brokering** Weighted Brokering

Pickup Available  Yes  No \*

Delivery Available  Yes  No \*

Ship For Pickup Sourcing Available  Yes  No \*

Ship For Pickup Receiving/Pickup Available  Yes  No \*

Backorder Available  Yes  No \*

Location Priority  \*

Search Retries  \*

Maximum Daily Orders  \* 0 is Unlimited

Sourcing Distance  \* miles \*

Auto Cancel Days of Unclaimed Pickup Orders  \*

Auto Cancel Days of Unclaimed Ship For Pickup Orders  \*

Auto Cancel Reason

- At the **Standard Brokering** tab, complete the fields that control brokering orders if you do not use Weighted Brokering.

Order Broker Settings **Fulfillment** **Standard Brokering** Weighted Brokering

Proximity  Order By  \*

On Hand Count  Order By  \*

Location Priority  Order By  \*

Last Order Assigned  Order By  \*

Sales Velocity Rank  Order By  \*

- At the **Weighted Brokering** tab, complete the fields that control brokering orders if you do use Weighted Brokering.

**For more information:** See the **Preferences** screen in the Online Help for complete field descriptions and background.

---



---

**Important:** You need to set all Order Broker preferences at the organization level before integrating any external systems with Order Broker. See the description of the **Preferences** screen for complete information on setting preferences.

---



---

**Preference overrides:** Optionally, you can set up overrides at the order type and system level for the Routing Engine to use when searching for fulfilling locations. For example, you can have the Routing Engine sort locations for pickup orders by proximity, while it sorts locations for delivery and retail pickup orders by available quantity. Unless you set up overrides, each level “inherits” the settings from the **Preferences** screen. See the **Order Broker Preference Overrides** screen in the Online Help for more information.

## Scheduling Jobs

Use the **Schedule Jobs** screen to create schedules for jobs:

- Data Hygiene:
  - Completed Order Private Data Purge
  - Daily Clean Up
- Exports:
  - Fulfilled Inventory Export
  - Probable Quantity Export
  - Sales Order Data Extract
- Imports:
  - Identity Cloud User Synchronization
  - Incremental Inventory Import
  - Product Import
- Orders:
  - Auto Cancel Unclaimed Pickup Orders

- Email Notifications

See the **Schedule Jobs** screen in the online help for more information.

---

---

**Note:** Do not attempt to schedule jobs before creating systems.

---

---

## About Scheduling Imports

**About imports:** The automated import process enables you to import and update locations, products, system products, product locations, and product barcodes from an integrated system.

---

---

**Note:** If you are using the Oracle Maps Cloud Service instead of the proximity upload to support proximity locator searching, you should complete Oracle Maps Cloud Service configuration before importing locations, so that the latitude and longitude of each location can be assigned as it is created. Contact your Oracle representative for information on implementing the Oracle Maps Cloud Service.

---

---

**Import from default system first?** In order to create product records in the default system before you create system product records in any other systems, you need to run the import for the default system before the other systems.

**Processing steps:** If you use the File Storage API, the import checks the OROB-IMPORTS container in the FILE\_STORAGE table for a pipe-delimited file containing each type of information for import (location, product, system product, product location, and product bar code). Otherwise, if you use secure FTP, the import checks the *Product Import Files* folder specified at the **Tenant - Admin** screen for the pipe-delimited files. The cloud administrator specifies the locations of these folders. See *Importing Items/Products, Inventory, Barcodes, and Locations into the Database* in the online help for background on the import process.

---

---

**Important:** Oracle recommends that you schedule imports daily at a time when demands on the system are limited, and when it does not interfere with the database backup, and that you do not schedule more than one import at a time against the same database.

---

---

**Mapping from integrating systems:** Consult the integrating system's documentation and complete the **Schedule Jobs** screen for systems that support the import process, including CWSerenade and SIM.

**For more information:** See the **Order Broker Routing Engine Overview** in the online help for a process overview, and see **Schedule Jobs** in the online help for file layouts, file naming conventions, and mapping details.

## Restart All

Use the **Reschedule All** option at the **View Active Schedules** screen to start all scheduled jobs and programs listed above. as well as:

- scheduled report generation
- polling of orders for Store Connect.

View Active Schedules ✕

**View Active Schedules**

Job Name: Email Notifications Organization:

**Search Results**

Job Name	Organization	Last Updated	Last Run	Next Run	History
Email Notifications		01/18/2019 03:57	08/09/2019 14:00	08/09/2019 14:01	

## Adjust and Save Preferences

After importing locations, products, system products, and product locations, you need to return to the **Preferences** screen, make any necessary adjustments, and select **Save** again to apply the preference settings. You also need to save your preference settings after creating a new location to have the settings apply to each new location.

1. Select **Locations > Organizations and Preferences**.

Locations Reports Systems D

- Organizations and Preferences
- Order Broker Preference Overrides
- Brands
- Location Types
- Locations
- Location Bulk Updates
- Attribute Definitions
- Fulfillment Zones
- Vendors

2. At the **Organizations and Preferences** screen, select the *Order Broker Preferences* icon (  ) for your organization.

Organizations and Preferences ✕

**Organizations and Preferences**

Organization:  Name:

**Search Results**

Orga...	Name	System	Order... Prefer...	Drop ... Prefer...	Store ... Prefer...	Edit	Delete
		23					

At the **Preferences** screen, make any necessary changes at the organization, location type, or location type level, and select **Save**.

## Setting up Web Service Authentication

**About web service authentication:** By setting up and requiring user IDs and passwords or OAuth authentication for web services, you confirm that Order Broker authenticates the identify of the system submitting web service messages. Web service authentication is required. If Order Broker receives a web service request message without a valid web service user and password, the request is refused with an error: Inbound Message failed validation.


The web services requiring authentication are:

- *Admin:* Requests include Product Update, Location Update, and Location Detail.
- *Discovery:* Requests include location and system discovery, so an integrating system can obtain a list of locations or systems in Order Broker.
- *Locate:* Includes all requests related to the Routing Engine.
- *Private Data Request:* Includes requests to inquire on or delete private data.
- *Purchasing:* Includes all requests related to the Supplier Direct Fulfillment module.
- *Storage:* Includes all requests related to inquiring on, importing, exporting, or deleting files when you use the File Storage API.
- *Vendor:* Includes requests submitted by an integrated vendor using the Supplier Direct Fulfillment module.

**IDCS:** You also need to create each user in IDCS, where you set the user’s initial password unless using OAuth.

To create users for web service authentication:

**1. Select Systems > Web Service Authorization.**



**2. At the Web Service Authorization screen, select the Edit icon (  ) for a web service you will be using.**

- At the **Web Service User** screen, select **New**.



- At the **New Web Service User** window, enter the *User ID* and select **Save**.



**Note:** If you use OAuth for authentication of inbound web services, the User specified here is the IDCS Client ID that generates the OAuth token.

- Close the **Web Service User** screen when you have finished creating each web service user that an integrating system will use to authenticate web service messages.



- Repeat the steps above for each web service that you will be using.

**For more information:** See the **Operations Guide** for more information on supported web services.