

Deploying Oracle FLEXCUBE Application on WebLogic
Oracle FLEXCUBE Universal Banking
Release 12.2.0.0.0
[May] [2016]



Table of Contents

- 1. DEPLOYING ORACLE FLEXCUBE ON WEBLOGIC 1-1**
- 1.1 INTRODUCTION 1-1
- 1.2 BUILDING APPLICATION 1-1
 - 1.2.1 *Building Application in Centralized Mode* 1-1
 - 1.2.2 *Building Application in Decentralized Mode*..... 1-1
- 1.3 DEPLOYING APPLICATION IN ORACLE WEBLOGIC 1-1
 - 1.3.1 *Deploying Dependency Library “Jersey-bundle”* 1-1
 - 1.3.2 *Deploying FCUBS Application from WebLogic Administration Console* 1-5
 - 1.3.3 *Deploying Gateway/Scheduler Applications from WebLogic Administration Console* 1-14

1. Deploying Oracle FLEXCUBE on WebLogic

1.1 Introduction

This chapter explains the steps to deploy Oracle FLEXCUBE UBS application into Oracle WebLogic application server in centralized and decentralized modes. In centralized mode, branch and host are setup in a single PC. In decentralized mode, branch and host are setup in different PCs.

1.2 Building Application

For building Oracle FLEXCUBE Application in centralized and decentralized modes, refer to the following chapters.

1.2.1 Building Application in Centralized Mode

Refer to the chapter 'Building Application in Centralized Mode'. This includes the following details:

- Creating Property File
- Building Centralized EAR File
- Configuring Plug-ins
- Loading Properties File

1.2.2 Building Application in Decentralized Mode

Refer to the chapter 'Building Application in Centralized Mode'. This includes the following details:

- Creating Property File
- Building Centralized EAR File
- Configuring Plug-ins
- Loading Properties File

1.3 Deploying Application in Oracle WebLogic


This section explains the method of deploying Oracle FLEXCUBE Application Oracle WebLogic application server.

1.3.1 Deploying Dependency Library "Jersey-bundle"

This library must be installed before deploying FCUBSApp.ear. Follow the below steps


1. Start the Administrative Console of WebLogic application server. You can start this by entering Oracle WebLogic Admin Console URL in the address bar in an internet browser.
Eg: <http://10.10.10.10:1001/console>

2. The following screen is displayed:



3. Specify the WebLogic administrator user name and password. Click 'Log In'.

The following screen is displayed:



Click install button

ORACLE WebLogic Server Administration Console 12c

Home Log Out Preferences Record Help

Welcome, infra Connected to: STD_PAYMENT

Change Center

View changes and restarts

No pending changes exist. Click the Release Configuration button to allow others to edit the domain.

Lock & Edit

Release Configuration

Domain Structure

STD_PAYMENT

- Domain Partitions
- Environment
- Deployments
- Services
- Security Realms
- Interoperability
- Diagnostics

How do I...?

- Install an enterprise application
- Configure an enterprise application
- Update (redeploy) an enterprise application
- Monitor the modules of an enterprise application
- Deploy EJB modules
- Install a Web application

System Status

Health of Running Servers

Failed (0)

Critical (0)

Overloaded (0)

Warning (0)

OK (2)

Summary of Deployments

Configuration Control Monitoring

This page displays the list of Java EE applications and standalone application modules installed to this domain.

You can update (redeploy) or delete installed applications and modules from the domain by selecting the checkbox next to the application name and then using the controls on this page.

To install a new application or module for deployment to targets in this domain, click **Install**.

Customize this table

Deployments

Name	State	Health	Type	Targets	Scope	Domain Partitions	Deployment Order
<input type="checkbox"/> adf.oracle.businesseditor(1.0,12.2.1.0.0)	Active		Library	AdminServer_payments, pm_server1	Global	100	
<input type="checkbox"/> adf.oracle.domain(1.0,12.2.1.0.0)	Active		Library	AdminServer_payments, pm_server1	Global	100	
<input type="checkbox"/> adf.oracle.domain.webapp(1.0,12.2.1.0.0)	Active		Library	AdminServer_payments, pm_server1	Global	100	
<input type="checkbox"/> coherence-transaction-var	Active	OK	Resource Adapter	AdminServer_payments, pm_server1	Global	100	
<input type="checkbox"/> DMS Application (12.2.1.0.0)	Active	OK	Web Application	AdminServer_payments, pm_server1	Global	5	
<input type="checkbox"/> em	Active	OK	Enterprise Application	AdminServer_payments	Global	400	
<input type="checkbox"/> emagentdkimplpriv_jar(12.4,12.1.0.4.0)	Active		Library	AdminServer_payments	Global	100	
<input type="checkbox"/> emagentdkimpl_jar(12.4,12.1.0.4.0)	Active		Library	AdminServer_payments	Global	100	
<input type="checkbox"/> emagentdk_jar(12.4,12.1.0.4.0)	Active		Library	AdminServer_payments	Global	100	
<input type="checkbox"/> emas	Active		Library	AdminServer_payments	Global	100	
<input type="checkbox"/> emcore	Active		Library	AdminServer_payments	Global	100	
<input type="checkbox"/> emcoresclient_jar	Active		Library	AdminServer_payments	Global	100	
<input type="checkbox"/> emcorescommon_jar	Active		Library	AdminServer_payments	Global	100	
<input type="checkbox"/> emcoresconsole_jar	Active		Library	AdminServer_payments	Global	100	
<input type="checkbox"/> emcoresintask_jar(11.2.0.1.0,12.1.0.0.0)	Active		Library	AdminServer_payments	Global	100	
<input type="checkbox"/> emcorespbis_jar	Active		Library	AdminServer_payments	Global	100	
<input type="checkbox"/> emcoresdkimpl_jar(11.2.0.1.0,12.1.0.0.0)	Active		Library	AdminServer_payments	Global	100	
<input type="checkbox"/> emcoresdk_jar(11.2.0.1.0,12.1.0.0.0)	Active		Library	AdminServer_payments	Global	100	
<input type="checkbox"/> emcore_jar	Active		Library	AdminServer_payments	Global	100	
<input type="checkbox"/> em_common(12.4,12.1.0.4.0)	Active		Library	AdminServer_payments	Global	100	

http://localhost:7001/console/cons... Install Application Assistant...

Pending changes exist. They must be activated to take effect. You may activate them now. Otherwise, they will be automatically activated when you next modify, add or delete items in this domain.

Activate Changes

Undo All Changes

Domain Structure

base_domain

- Environment
 - Servers
 - Clusters
 - Coherence Clusters
 - Machines
 - Virtual Hosts
 - Work Managers
 - Startup and Shutdown Classes
- Deployments
- Services
- Security Realms
- Interoperability
- Diagnostics

How do I...?

- Start and stop a deployed enterprise application
- Configure an enterprise application
- Create a deployment plan
- Target an enterprise application to a server
- Test the modules in an enterprise application

System Status

Install Application Assistant

Back Next Finish Cancel

Locate deployment to install and prepare for deployment

Select the file path that represents the application root directory, archive file, exploded archive directory, or application module descriptor that you want to install. You can also enter the path of the application directory or file in the Path field.

Note: Only valid file paths are displayed below. If you cannot find your deployment files, upload your file(s) and/or confirm that your application contains the required deployment descriptors.

Path: C:\Oracle\Middleware\Oracle_Home\wlserver\common\deployable-libraries\jersey-bundle-1.9.war

Recently Used Paths:


- D:\DESTMPDIR
- C:\Oracle\Middleware\Oracle_Home\wlserver\common\deployable-libraries
- D:\DESTMPDIR\20150720__1825\build
- D:\DESTMPDIR\20150703__1915\build

Current Location: localhost \ C : \ Oracle \ Middleware \ Oracle_Home \ wlserver \ common \ deployable-libraries


- active-cache-1.0.jar
- jax-rs-2.0.war
- jersey-bundle-1.9.war
- jsf-1.2.war
- jsf-2.0.war
- jsr311-api-1.1.1.war
- jstl-1.1.2.war
- jstl-1.2.war
- pubsub-1.0.war
- weblogic-sca-1.2.war

Back Next Finish Cancel


Navigate and select jersey bundle under the path “wlserver\common\deployable-libraries\jersey-bundle-x.x.war” and click next



Select "install this deployment as library" and click next



Click finish button



This library must appear in the deployment with Type column as "Library"

1.3.2 Deploying FCUBS Application from WebLogic Administration Console

To deploy Oracle FLEXCUBE Application from Oracle WebLogic administration console, follow the steps given below.


1. Start the Administrative Console of WebLogic application server. You can start this by entering Oracle WebLogic Admin Console URL in the address bar in an internet browser.
Eg: <http://10.10.10.10:1001/console>

2. The following screen is displayed:



3. Specify the WebLogic administrator user name and password. Click 'Log In'.

The following screen is displayed:



4. You need to deploy an EAR. For e.g. 'FCUBSApp.ear'. Go to 'Deployment'.

Click 'Lock & Edit' button to enable the buttons. This action enables the buttons.

The screenshot shows the Oracle WebLogic Server Administration Console. On the left, the 'Change Center' has the 'Lock & Edit' button highlighted. The main content area is titled 'Summary of Deployments' and contains a table of installed applications and modules. The table has columns for Name, State, Health, Type, Targets, Scope, Domain Partitions, and Deployment Order. The table lists various applications like 'adf.oracle.businesseditor', 'adf.oracle.domain', 'coherence-transaction-rar', 'DMS Application', 'em', 'emagentdbkmp', 'emagentdbkmp_jar', 'emagentdbk_jar', 'emas', 'emacore', 'emacoreclient_jar', 'emacorecommon_jar', 'emacoreconsole_jar', 'emacorestd_jar', 'emacorepb_jar', 'emacorestdmp_jar', 'emacorestd_jar', 'emacore_jar', and 'em_common'.


Name	State	Health	Type	Targets	Scope	Domain Partitions	Deployment Order
adf.oracle.businesseditor(1.0,12.2.1.0.0)	Active		Library	AdminServer_payments, pm_server1	Global		100
adf.oracle.domain(1.0,12.2.1.0.0)	Active		Library	AdminServer_payments, pm_server1	Global		100
adf.oracle.domain.webapp(1.0,12.2.1.0.0)	Active		Library	AdminServer_payments, pm_server1	Global		100
coherence-transaction-rar	Active	OK	Resource Adapter	AdminServer_payments, pm_server1	Global		100
DMS Application (12.2.1.0.0)	Active	OK	Web Application	AdminServer_payments, pm_server1	Global		5
em	Active	OK	Enterprise Application	AdminServer_payments	Global		400
emagentdbkmp(12.4,12.1.0.4.0)	Active		Library	AdminServer_payments	Global		100
emagentdbkmp_jar(12.4,12.1.0.4.0)	Active		Library	AdminServer_payments	Global		100
emagentdbk_jar(12.4,12.1.0.4.0)	Active		Library	AdminServer_payments	Global		100
emas	Active		Library	AdminServer_payments	Global		100
emacore	Active		Library	AdminServer_payments	Global		100
emacoreclient_jar	Active		Library	AdminServer_payments	Global		100
emacorecommon_jar	Active		Library	AdminServer_payments	Global		100
emacoreconsole_jar	Active		Library	AdminServer_payments	Global		100
emacorestd_jar(11.2.0.1.0,12.1.0.0.0)	Active		Library	AdminServer_payments	Global		100
emacorepb_jar	Active		Library	AdminServer_payments	Global		100
emacorestdmp_jar(11.2.0.1.0,12.1.0.0.0)	Active		Library	AdminServer_payments	Global		100
emacorestd_jar(11.2.0.1.0,12.1.0.0.0)	Active		Library	AdminServer_payments	Global		100
emacore_jar	Active		Library	AdminServer_payments	Global		100
em_common(12.4,12.1.0.4.0)	Active		Library	AdminServer_payments	Global		100

5. Click 'Install' button. The following screen is displayed:


The screenshot shows the 'Install Application Assistant' dialog box. The 'Locate deployment to install and prepare for deployment' step is active. The dialog prompts the user to select a file path for the application root directory, archive file, exploded archive directory, or application module descriptor. The 'Path' field is set to 'D:\'. Below the path field, a file browser view shows the contents of the D:\ drive, including folders like '11.0', '9NT1272', 'APPOINT SOFTWARE SOLUTIONS', 'backup', 'bea', 'bea11g', 'bea_100', 'BinDlgs', 'ClearCase', 'CRC', 'Desktop', and 'Documents and Settings'.

6. In order to specify the path/location of the enterprise archive file, click the link 'upload your file(s)'.

7. Click 'Next'. The following screen is displayed:




8. Specify the EAR file path. You can use the 'Browse' button to locate the file.
9. Click 'Next'. The following screen is displayed.



10. Select the application 'FCUBSApp.ear' from the list.


11. Click 'Next'. Following screen is displayed:



12. Choose the targeting style 'Install this deployment as an application'.


13. Click 'Next'.

The following screen is displayed




14. Select the target of the application. You can choose the server 'AdminServer' or 'Managed Server(s)'.

15. Click 'Next'. The following screen is displayed.




16. Check the deployment name.

The remaining portion of the screen is shown below:




17. Check whether the deployment location is accessible or not.

The following screen is displayed.




18. Click 'Finish' button. The following screen is displayed.

Change **Deployment Order** to **400** if the application includes **BPEL plug-in**.




19. Click 'Save' button. The message 'Settings updated successfully' is displayed.




20. Click 'Activate Changes' button on the left pane. The message 'All the changes have been activated. No restarts are necessary' is displayed.

The screen is given below:




Click 'Deployment' on the left pane. Switch to Control tab .The following screen is displayed.




21. Click 'Start' drop-down button and select 'Servicing all requests'.

22. The following screen is displayed.



23. Click 'Yes'. The following screen is displayed.



This completes the deployment process.

1.3.3 Deploying Gateway/Scheduler Applications from WebLogic Administration Console


To deploy Oracle FLEXCUBE Gateway/Scheduler Application from Oracle WebLogic administration console, follow the steps given below.

1. Launch Administrative Console of WebLogic application server. You can launch this by entering Oracle WebLogic Admin Console URL in the address bar in an internet browser. Eg: <http://10.10.10.10:1001/console>
2. The following screen is displayed:




3. Specify the WebLogic administrator user name and password. Click 'Log In'.

The following screen is displayed:




4. You need to deploy an EAR. For e.g. 'GWEJB.ear'. Go to 'Deployment'.

Click 'Lock & Edit' button to enable the buttons. This action enables the buttons.




5. Click 'Install' button. The following screen is displayed:




6. In order to specify the path/location of the enterprise archive file, click the link 'upload your file(s)'.

7. Click 'Next'. The following screen is displayed:




8. Specify the EAR file path. You can use the 'Browse' button to locate the file.

9. Click 'Next'. The following screen is displayed.



10. Select the application from the list.


11. Click 'Next'. Following screen is displayed:



12. Choose the targeting style 'Install this deployment as an application'.


13. Click 'Next'.

The following screen is displayed



14. Select the target of the application. You can choose the server 'AdminServer' or 'Managed Server(s)'.

15. Click 'Next'. The following screen is displayed.



16. Check the deployment name.

The remaining portion of the screen is shown below:

The screenshot shows the 'Install Application Assistant' configuration screen in the Oracle WebLogic Server Administration Console. The left sidebar contains navigation menus for 'Services', 'System Status', 'How do I...', and 'System Status'. The main content area is titled 'Name: GWEJB' and 'Archive Version: 12.2.0.0.0'. It includes sections for 'Security' (with radio buttons for 'DD Only', 'Custom Roles', and 'Advanced'), 'Source Accessibility' (with radio buttons for 'Use defaults', 'Copy to every target', and 'I will make'), and 'Plan Source Accessibility' (with radio buttons for 'Use same accessibility', 'Copy plan to every target', and 'Do not copy'). At the bottom, there are 'Back', 'Next', 'Finish', and 'Cancel' buttons.

17. Check whether the deployment location is accessible or not.

The following screen is displayed.

The screenshot shows the 'Review your choices and click Finish' screen in the Oracle WebLogic Server Administration Console. The left sidebar is the same as in the previous screenshot. The main content area is titled 'Review your choices and click Finish' and includes a 'Summary' section with the following details:

- Deployment: /scratch/app/fmw122/Oracle/user_projects/domains/PM1221TR2/servers/Admin_PM1TR2/upload/GWEJB.ear/app/GWEJB.ear
- Name: GWEJB
- Staging Mode: Use the defaults defined by the chosen targets
- Plan Staging Mode: Use the same accessibility as the application
- Security Model: DDOnly: Use only roles and policies that are defined in the deployment descriptors.
- Scope: Global

 Below the summary is a 'Target Summary' table:

Components	Targets
GWEJB.ear	payments_server1

 At the bottom, there are 'Back', 'Next', 'Finish', and 'Cancel' buttons.

18. Click 'Finish' button. The following screen is displayed.

ORACLE WebLogic Server Administration Console 12c

Home > Summary of Deployments > GWEJB(12.2.0.0.0)

Settings for GWEJB(12.2.0.0.0)

Overview | Deployment Plan | Configuration | Security | Targets | Control | Testing | Monitoring | Notes

Save

Use this page to view the general configuration of an enterprise application, such as its name, the physical path to the application files, the associated deployment plan, and so on. The table at the end of the page lists the modules (such as Web applications) contained in the enterprise application. Click on the name of the module to view and update its configuration.

Name:	GWEJB	The name of this enterprise application. More Info...
Scope:	Global	Specifies if this enterprise application is accessible within the domain, a partition, or a resource template. More Info...
Archive Version:	12.2.0.0.0	The archive version, specified from from the manifest or overridden during deployment. More Info...
Path:	/scratch/app/fmw122/Oracle/user_projects/domains/PM1221TR2/servers/Admin_PMT1R2/upload/GWEJB.ear/app/GWEJB.ear	The path to the source of the deployable unit on the Administration Server. More Info...
Deployment Plan:	(no plan specified)	The path to the deployment plan document on the Administration Server. More Info...
Staging Mode:	(not specified)	Specifies whether a deployment's files are copied from a source on the Administration Server's staging area during application preparation. More Info...
Plan Staging Mode:	(not specified)	Specifies whether an application's deployment plan is copied from a source on the Administration Server's staging area during application preparation. More Info...
Security Model:	DDOnly	The security model that is used to secure a deployed module. More Info...
Deployment Order:	100	An integer value that indicates when this unit is deployed, relative to other deployable units during startup. More Info...
Deployment Principal Name:		A string value that indicates the principal that should be used when deploying the file or an and shutdown. This principal will be used to set the current subject when calling out into interfaces such as ApplicationLifecycleListener. If no principal name is specified, then the a will be used. More Info...

Save

Modules and Components

Showing 1 to 1 of 1:

Name
GWEJB (12.2.0.0.0)
EJBs
FCMainProcEJB
FCSvrRouterEJB
GWEJB

19. Click 'Save' button. The message 'Settings updated successfully' is displayed.

ORACLE WebLogic Server Administration Console 12c

Home > Summary of Deployments > GWEJB(12.2.0.0.0)

Messages

Settings updated successfully.

Settings for GWEJB(12.2.0.0.0)

Overview | Deployment Plan | Configuration | Security | Targets | Control | Testing | Monitoring | Notes

Save

Use this page to view the general configuration of an enterprise application, such as its name, the physical path to the application files, the associated deployment plan, and so on. The table at the end of the page lists the modules (such as Web applications) contained in the enterprise application. Click on the name of the module to view and update its configuration.

Name:	GWEJB	The name of this enterprise application. More Info...
Scope:	Global	Specifies if this enterprise application is accessible within the domain, templates. More Info...
Archive Version:	12.2.0.0.0	The archive version, specified from from the manifest or overridden d More Info...
Path:	/scratch/app/fmw122/Oracle/user_projects/domains/PM1221TR2/servers/Admin_PMT1R2/upload/GWEJB.ear/app/GWEJB.ear	The path to the source of the deployable unit on the Administration S More Info...
Deployment Plan:	(no plan specified)	The path to the deployment plan document on the Administration Ser More Info...
Staging Mode:	(not specified)	Specifies whether a deployment's files are copied from a source on th More Info...
Plan Staging Mode:	(not specified)	Specifies whether an application's deployment plan is copied from a s More Info...
Security Model:	DDOnly	The security model that is used to secure a deployed module. More Info...
Deployment Order:	100	An integer value that indicates when this unit is deployed, relative to More Info...
Deployment Principal Name:		A string value that indicates the principal that should be used when d More Info...

Save

Modules and Components

Showing 1 to 1 of 1:

Name
GWEJB (12.2.0.0.0)
EJBs
FCMainProcEJB
FCSvrRouterEJB

20. Click 'Activate Changes' button on the left pane. The message 'All the changes have been activated. No restarts are necessary' is displayed.

The screen is given below:

ORACLE WebLogic Server Administration Console 12c

Home > Summary of Deployments > GWEJB(12.2.0.0.0)

Messages
 All changes have been activated. No restarts are necessary.

Settings for GWEJB(12.2.0.0.0)

Overview | Deployment Plan | Configuration | Security | Targets | Control | Testing | Monitoring | Notes

Click the **Lock & Edit** button in the Change Center to modify the settings on this page.

Save

Use this page to view the general configuration of an enterprise application, such as its name, the physical path to the application files, the associated deployment plan, and so on. The table at the end of the page lists the modules (such as Web containers) contained in the enterprise application. Click on the name of the module to view and update its configuration.

Name:	GWEJB	The name of this enterprise application. More Info...
Scope:	Global	Specifies if this enterprise application is accessible within the domain, a part of a template. More Info...
Archive Version:	12.2.0.0.0	The archive version, specified from the manifest or overridden during deployment. More Info...
Path:	/scratch/app/fmw122/Oracle/user_projects/domains/PM1221TR2/servers/Admin_PM1TR2/upload/GWEJB_ear/app/GWEJB_ear	The path to the source of the deployable unit on the Administration Server.
Deployment Plan:	(no plan specified)	The path to the deployment plan document on the Administration Server.
Staging Mode:	(not specified)	Specifies whether a deployment's files are copied from a source on the Administration Server's staging area during application preparation. More Info...
Plan Staging Mode:	(not specified)	Specifies whether an application's deployment plan is copied from a source on the Administration Server's staging area during application preparation. More Info...
Security Model:	DDOnly	The security model that is used to secure a deployed module. More Info...
Deployment Order:	100	An integer value that indicates when this unit is deployed, relative to other units during startup. More Info...
Deployment Principal Name:		A string value that indicates the principal that should be used when deploying and shutting down. This principal will be used to set the current subject when calling interfaces such as ApplicationLifecycleListener. If no principal name is specified, the current subject will be used. More Info...

Modules and Components

Name
GWEJB (12.2.0.0.0)
EJBs
FCMainProcEJB
FCServerRouterEJB

Click 'Deployment' on the left pane. Switch to Control tab. The following screen is displayed.

ORACLE WebLogic Server Administration Console 12c

Home > Summary of Deployments > GWEJB(12.2.0.0.0) > Summary of Deployments

Configuration | **Control** | Monitoring

This page displays the list of Java EE applications and standalone application modules installed to this domain.

You can start and stop applications and modules from the domain by selecting the checkbox next to the application name and then using the controls on this page.

Customize this table

Deployments

Start | Stop

Start	Stop	State	Health	Type	Targets	Scope	Domain Partition
<input type="checkbox"/>	<input type="checkbox"/>	Active	OK	Resource Adapter	Admin_PM1TR2	Global	
<input type="checkbox"/>	<input type="checkbox"/>	Active	OK	Web Application	Admin_PM1TR2	Global	
<input type="checkbox"/>	<input type="checkbox"/>	Active	OK	Enterprise Application	Admin_PM1TR2	Global	
<input type="checkbox"/>	<input type="checkbox"/>	Active	Warning	Enterprise Application	payments_server1	Global	
<input checked="" type="checkbox"/>	<input type="checkbox"/>	Prepared	OK	Enterprise Application	payments_server1	Global	
<input type="checkbox"/>	<input type="checkbox"/>	Active	OK	Web Application	Admin_PM1TR2	Global	
<input type="checkbox"/>	<input type="checkbox"/>	Active	OK	EJB	payments_server1	Global	
<input type="checkbox"/>	<input type="checkbox"/>	Active	OK	Resource Adapter	Admin_PM1TR2	Global	


Showing 1 to 8 of 8 Prev

Showing 1 to 8 of 8 Prev


WebLogic Server Version 12.2.1.0.0
 Copyright (c) 1996-2015, Oracle and/or its affiliates. All rights reserved.
 Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

21. Click 'Start' drop-down button and select 'Servicing all requests'.

22. The following screen is displayed.



23. Click 'Yes'. The following screen is displayed.



This completes the deployment process.



Deploying Oracle FLEXCUBE on WebLogic
[May] [2016]
Version 12.2.0.0.0

Oracle Financial Services Software Limited
Oracle Park
Off Western Express Highway
Goregaon (East)
Mumbai, Maharashtra 400 063
India

Worldwide Inquiries:
Phone: +91 22 6718 3000
Fax: +91 22 6718 3001
www.oracle.com/financialservices/

Copyright © 2007, 2016, Oracle and/or its affiliates. All rights reserved.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate failsafe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.