

FLEXCUBE UBS Inbound
Application Adapter Installation
Document
Version 12.2.0.0.0
FLEXCUBE KERNEL
[May] [2016]



Contents

1	Installation Steps	2
1.1	Prerequisite	2
1.2	Steps	2

Installation Steps

1.1 Prerequisite

- ✓ Ensure that the basic MDB Gateway Environment Setup is done.
[Please refer [GW MDB Installation.doc.](#)]
- ✓ Ensure that the basic Adapter Environment Setup is done.
[Please refer [SSIAD Installation FCUBSV.UM8.0.0.0.0.0Lot1.doc.](#)]

1.2 Steps

A. Configure FCC – FC SSI MH Integration Adapter Properties

Edit `<KERNEL_INSTALL_DIR>/SSIAD_EJB/config/SSIAD_EJB_Prop.xml` file to give appropriate values for the properties as described below,

1. XSD_PATH: This property specifies the path where the AckFile.XSD is stored.
e.g. XSD_PATH=<KERNEL_INSTALL_DIR>/SSIAD_EJB_ACK/XSD/
[NOTE: Give XSD file path with forward slash (/) as file separator and remember to give a slash at the end.]
2. SSIAD_ACK_XSD: This property specifies the name of the XSD against which SSIAD Envelope validation is done for acknowledgement messages.
eg. SSIAD_ACK_XSD = "AckFile.XSD".
3. SSIAD_ERR_XSD: This property specifies the name of the XSD against which SSIAD Envelope validation is done for error messages.
eg. SSIAD_ERR_XSD = "ErrorInfo.xsd".
4. IS_XSD_VAL_REQD - This property specifies whether XSD validation should be done or not. To enable XSD validation specify "Y" and to make is disable specify "N".
5. IB_EJB_SERVER_URL: This property specifies protocol, server url and the port on which WAS server is running "protocol://serverurl:port/application name" format
eg. IB_EJB_SERVER_URL = ormi://10.80.44.103:23791/SSIAD_EJB_ACK_Bean
6. IB_EJB_CTX_FACTORY: This property define context factory for OC4J server used by Oracle Application Server applications to perform JNDI operations

eg. IB_EJB_CTX_FACTORY = " com.evermind.server.rmi.RMIInitialContextFactory"

7. IB_EJB_SECURITY_PRINCIPAL: specifying the identity of the principal for authenticating the caller to the service if required otherwise can be left blank.
8. IB_EJB_SECURITY_CREDENTIALS: specifies the credentials of the principal for authenticating the caller to the service if required otherwise can be left blank.
9. IB_EJB_CALL_TYPE: This property specifies the call type of EJB. This must always be REMOTE.
10. IB_EJB_LOCAL_CALL: This must always be LOCAL.
11. IB_EJB_REMOTE_CALL: This must always be REMOTE.
12. FCUBS_DB_SERVER_IP: This property defines FCUBS Database server IP address.
13. FCUBS_DB_SERVER_UID: This property defines user id for FCUBS Database server.
14. FCUBS_DB_SERVER_PWD: This property defines password for FCUBS Database server.
15. FCUBS_DB_PAYLOAD_PATH: This property defines payload file path on FCUBS database server.
16. FCUBS_DB_DEAD_LETTER_PATH: This property defines dead letter file path on FCUBS database server.
[NOTE: Give XSD file path with forward slash (/) as file separator and remember to give a slash at the end.]
17. SSIAD_EJB_MH_IP: This property defines SSI MH server IP address.
18. SSIAD_EJB_MH_USERID: This property defines user id for SSI MH server.
19. SSIAD_EJB_MH_PASSWORD: This property defines password for SSI MH server.
20. SSIAD_EJB_MH_ENVELOPE: This property defines envelope file path on SSI MH Server.

21. SSIAD_MH_PAYLOAD_PATH: This property defines payload file path on SSI MH server.
22. SSIAD_EJB_MH_ACKNOWLEDGE: This property defines acknowledgement file path on SSI MH server.
23. SSIAD_EJB_JMS_ICF: This property defines InitialContextFactory that is responsible for getting and instance of the initial context. It is also responsible for looking up JMS topics and queues.
24. SSIAD_EJB_JMS_PROVIDER_URL: This property is used for external JNDI lookups. eg. provider URL in <host>[:<port>] format.
Specify whole path of the binding file that has been created for Gateway MDB Installation.
25. SSIAD_EJB_JMS_SECURITY_PRINCIPAL: This property defines the name of the entity (user) that is authenticated when the connection to the JMS provider is established. The Security Principal and the Security Credentials are included in the naming context when the connection factory is looked up from the naming.
26. SSIAD_EJB_JMS_SECURITY_CREDENTIALS: This property defines the credentials (typically a password) that authenticate the security principal to the JMS provider.
27. SSIAD_EJB_JMS_QCF: This property specifies the Queue Connection Factory of the Queue Manager to which Gateway MDB is associated.
eg. SSIAD_EJB_JMS_QCF =MDBQCF
28. SSIAD_EJB_JMS_QUEUE_NAME: This property specifies the Queue on which the Gateway MDB is listening.
SSIAD_EJB_JMS_QUEUE_NAME =MDB_QUEUE
29. SSIAD_EJB_JMS_Q_ACKNOWLEDGE: This property specifies the mode of acknowledgement to be given to the MOM by the application. The possible values are CLIENT_ACKNOWLEDGE, DUPS_OK_ACKNOWLEDGE and AUTO_ACKNOWLEDGE.
30. SSIAD_EJB_JMS_Q_TRANSACTION: This property specifies whether the message

sent/received has to be transacted or not. The value is false.

31. SSIAD_EJB_JMS_Q_DELIVERY_OPT: The message delivery option represents whether the message will be delivered with the Delivery mode as PERSISTENT or NON-PERSISTENT. Possible values are 1 and 2. 1 represents delivery mode to be NON-PERSISTENT while 2 represents the delivery mode to be PERSISTENT.
32. SSIAD_EJB_JMS_Q_TIME_TO_LIVE: This is the maximum time in milliseconds for which the outgoing/reply message will remain in the queue before expiring, if not already picked up by the external system application. Value 0 ensures that message will NEVER expire.
33. SSIAD_EJB_JMS_Q_PRIORITY: This is the priority of the outgoing/reply message. Priority value can be ranging from 0 to 9, 9 being highest priority and 0 being lowest priority. Priorities 0-4 are gradations of normal priority and priorities 5-9 are gradations of expedited priority.
34. XSL_PATH: This property specifies the path where the SSIAD_EJB_ACK_XSL.XSL is stored.
eg. XSL_PATH = "<KERNEL_INSTALL_DIR>/SSIAD_EJB_ACK/XSL/"
[NOTE: Give XSD file path with forward slash (/) as file separator and remember to give a slash at the end.]
35. SSIAD_EJB_ACK_XSL: This property specifies the acknowledgement XSL file name.
eg. SSIAD_EJB_ACK_XSL = SSIAD_EJB_ACK_XSL.xsl
36. SSIAD_EJB_ERR_XSL: This property specifies the error XSL file name.
eg. SSIAD_EJB_ERR_XSL = SSIAD_EJB_ERR_XSL.xsl
37. EJB_OBJ_PATH: This property specifies the path to store ejb reference .
[NOTE: Give XSD file path with forward slash (/) as file separator and remember to give a slash at the end.]
38. LOGGER_PATH: This property specifies the path of the logger property file. This file can be found at <KERNEL_INSTALL_DIR>/SSIAD_EJB_ACK/config.
[NOTE: Give XSD file path with forward slash (/) as file separator and remember to give a slash at the end.]
39. MSG_REPOLL_SLEEP_TIME: This property specifies interval of polling in milliseconds

The SSIAD_EJB_ACK_Prop.xml will look similar as follows,

```
<add key="XSD_PATH" value="D:/KernelSSIAD_OC4J/SSIAD_EJB_ACK/XSD"/>
<add key="SSIAD_ACK_XSD" value="AckFile.xsd"/>
<add key="SSIAD_ERR_XSD" value="ErrorInfo.xsd"/>
<add key="IS_XSD_VAL_REQD" value="Y"/>
<add key="IB_EJB_JNDI_NAME" value="SSIAD_EJB_ACK_Bean"/>
<add key="IB_EJB_SERVER_URL"
      value="ormi://10.80.44.103:23791/SSIAD_EJB_ACK_Bean"/>
<add key="IB_EJB_CTX_FACTORY"
      value="com.evermind.server.rmi.RMIInitialContextFactory"/>
<add key="IB_EJB_SECURITY_PRINCIPAL" value="oc4jadmin"/>
<add key="IB_EJB_SECURITY_CREDENTIALS" value="alJWEK]U_"/>
<add key="IB_EJB_CALL_TYPE" value="REMOTE"/>
<add key="IB_EJB_LOCAL_CALL" value="LOCAL"/>
<add key="IB_EJB_REMOTE_CALL" value="REMOTE"/>
<!--
      <add key="MAX_CLOB_LEN" value="32512"/>
      <add key="DB_TIMEOUT" value="20"/>
-->
      <!-- FTP details -->
<add key="FCUBS_DB_SERVER_IP" value="10.80.50.227"/>
<add key="FCUBS_DB_SERVER_UID" value="kerneldev"/>
<add key="FCUBS_DB_SERVER_PWD" value="YMg_M[KMo"/>
<add key="FCUBS_DB_PAYLOAD_PATH" value="users/TestDes"/>
<add key="FCUBS_DB_ACK_DEAD_LETTER_PATH" value="C:/Documents and Settings/Default
User/ejback/ACK_ERR_DLF"/>
<add key="SSIAD_EJB_MH_IP" value="10.80.44.85"/>
<add key="SSIAD_EJB_MH_USERID" value="i-flex\sanjaym"/>
<add key="SSIAD_EJB_MH_PASSWORD" value="7t[]Mgv&amp;"/>
<add key="SSIAD_MH_ACK_FOLDER" value="Line2/SERVER/ACK"/>
<!--
      <add key="SSIAD_EJB_MH_ENVELOPE" value="Line1/CLIENT/REQ"/>
      <add key="SSIAD_MH_PAYLOAD_PATH" value="Line1/CLIENT/FILEACT/PAYLOAD/PUT"/>
-->
      <!-- JMS details -->
<add key="SSIAD_EJB_JMS_ICF" value="com.sun.jndi.fscontext.ReffFSContextFactory"/>
<add key="SSIAD_EJB_JMS_PROVIDER_URL" value="file:/D:/bindings"/>
```

```

<add key="SSIAD_EJB_JMS_SECURITY_PRINCIPAL" value=""/>
<add key="SSIAD_EJB_JMS_SECURITY_CREDENTIALS" value=""/>
<add key="SSIAD_EJB_JMS_QCF" value="MDBQCF"/>
<add key="SSIAD_EJB_JMS_QUEUE_NAME" value="MDB_QUEUE"/>
<add key="SSIAD_EJB_JMS_Q_ACKNOWLEDGE" value="AUTO_ACKNOWLEDGE"/>
<add key="SSIAD_EJB_JMS_Q_TRANSACTION" value="false"/>
<add key="SSIAD_EJB_JMS_Q_DELIVERY_OPT" value="2"/>
<add key="SSIAD_EJB_JMS_Q_TIME_TO_LIVE" value="500000"/>
<add key="SSIAD_EJB_JMS_Q_PRIORITY" value="7"/>
    <!-- XSL -->
<add key="XSL_PATH" value="D:/KernelSSIAD_OC4J/SSIAD_EJB_ACK/XSL"/>
<add key="SSIAD_EJB_ACK_XSL" value="SSIAD_EJB_ACK_XSL.xml"/>
<add key="SSIAD_EJB_ERR_XSL" value="SSIAD_EJB_ERR_XSL.xml"/>
    <!-- Client -->
<add key="EJB_OBJ_PATH" value="C:/Documents and Settings/Default User/ejback/obj"/>
    <!-- ISCELLANEOUS PROPERTIES -->
<add key="LOGGER_PATH"
    value="D:/KernelSSIAD_OC4J/SSIAD_EJB_ACK/config/ssiad_ejb_ack_logger.xml"/>
<!-- Kernel 8.0 Lot 1 ITR1 SFR#86 <Start> -->
<add key="MSG_REPOLL_SLEEP_TIME" value="1000"/>

```


B. Configure logger parameters

- Edit <KERNEL_INSTALL_DIR>/SSIAD_EJB_ACK/config/ssiad_ejb_logger.xml file to change the value of the property "SSIAD.LOGGER.FPATH" to <KERNEL_INSTALL_DIR>/SSIAD_EJB_ACK/log/.

e.g. If the value of your <KERNEL_INSTALL_DIR> is D:/Kernel8.0, then the entry for this property will be,

```
<add key="SSIAD.LOGGER.FPATH" value="D:/Kernel8.0/SSIAD_EJB_ACK/log/" />
```

[NOTE: Give SSIAD.LOGGER.FPATH with forward slash (/) as file separator and remember to give a slash (/) at the end.]

C. Run the build file

- ✓ For WINDOWS
 - Go to the folder <KERNEL_INSTALL_DIR>\setup in the command prompt, type "**set_env**" and press enter.
 - Change directory to <KERNEL_INSTALL_DIR>\SSIAD_EJB_ACK\setup\OC4J in the command prompt, type "**ant**" and press enter.
- ✓ For UNIX
 - Go to the folder <KERNEL_INSTALL_DIR>/setup in the shell prompt, type "**set_env.sh**" and press enter.
 - Change directory to <KERNEL_INSTALL_DIR>/SSIAD_EJB_ACK/setup/OC4J in the shell prompt, type "**ant**" and press enter.

[NOTE: Please make sure that you get a message BUILD SUCCESSFUL after compilation.]

D. Deploy the EJB in Oracle 10g Application Server

1. Stop the application server.

- ✓ For WINDOWS
 - Set JAVA_HOME and ORACLE_HOME with the paths in your machine
eg.
set ORACLE_HOME=D:\Oracle10gAS
set JAVA_HOME=%ORACLE_HOME%\jdk
 - Go to the <APP_SERVER_HOME>/bin directory in the command prompt
eg. cd %APP_SERVER_HOME%\bin
 - Type oc4j -start
This will start the server. Ensure that you get no error during start up. If the server start up is proper we shall get the following screen.

- ✓ For UNIX
 - Set JAVA_HOME and ORACLE_HOME with the paths in your machine
e.g.
export ORACLE_HOME=/home/Oracle10gAS
export JAVA_HOME=\${ORACLE_HOME}/jdk
 - Go to the <APP_SERVER_HOME>/bin directory in the command prompt
e.g. cd \${APP_SERVER_HOME}/bin
 - Type **oc4j -shutdown -port 23791 -password <admin_password>**
e.g. oc4j -shutdown -port 23791 -password oc4jadmin
This will stop the server.

2. Start the application server.

- ✓ For WINDOWS
 - Set JAVA_HOME and ORACLE_HOME with the paths in your machine.
e.g.
set ORACLE_HOME=D:\Oracle10gAS
set JAVA_HOME=%ORACLE_HOME%\jdk
 - Go to the <APP_SERVER_HOME>/bin directory in the command prompt
E.g. cd %APP_SERVER_HOME%\bin
 - Type **oc4j -start**
This will start the server. Ensure that you get no error during start up. If the server start up is proper, the following be displayed on the command prompt.
- ✓ For UNIX
 - Set JAVA_HOME and ORACLE_HOME with the paths in your machine.
e.g.
export ORACLE_HOME=/home/Oracle10gAS
export JAVA_HOME=\${ORACLE_HOME}/jdk
 - Go to the <APP_SERVER_HOME>/bin directory in the command prompt
E.g. cd \${APP_SERVER_HOME}/bin
 - Type **oc4j -start**
This will start the server. Ensure that you get no error during start up.

3. Open the Administrative Console of Oracle Enterprise Manager

- ✓ Open an internet browser and type the OC4J Admin Console URL Address of the server.

e.g. <http://10.80.161.40:8888/em>

where, 10.80.4.116 is the machine IP Address on which OC4J is running.

- ✓ Login to Administrative Console

Enter OC4J administrator username/password and press **Login**.

ORACLE Enterprise Manager 10g 
Application Server Control

Login

* User Name	<input type="text" value="oc4jadmin"/>
* Password	<input type="password" value="*****"/>
	<input type="button" value="Login"/>

4. Deploying SSIAD_EJB_ACK_Bean.ear

- ✓ Click on Applications -> Deploy.

This page shows the J2EE applications and application components (EJB Modules, WAR Modules, Resource Adapter Modules) deployed to this OC4J instance.

View ▾

[Expand All](#) | [Collapse All](#)

Select	Name	Status	Start Time	Active Requests	Request Processing Time (seconds)	Active EJB Methods	Application Defined MBeans
<input type="radio"/>	▼ All Applications						
<input type="radio"/>	ascontrol	↑	Jun 27, 2007 1:13:06 PM IST	1	0.63	0	
<input checked="" type="radio"/>	▼ default	↑	Jun 27, 2007 1:13:06 PM IST	0	0.00	0	
<input type="radio"/>	▼ GW_EJB_Bean	↑	Jun 27, 2007 1:13:07 PM IST	0	0.00	0	
<input type="radio"/>	GW_HTTP_Servlet	↑	Jun 27, 2007 1:13:07 PM IST	0	0.00	0	
<input type="radio"/>	GW_MDB_Bean	↑	Jun 27, 2007 1:13:16 PM IST	0	0.00	0	
<input type="radio"/>	SSIAD_Client_Servlet	↑	Jun 27, 2007 1:13:17 PM IST	0	0.00	0	
<input type="radio"/>	bc4j	↑	Jun 27, 2007 1:13:06 PM IST	0	0.00	0	

5. Following screen will be displayed.

- ✓ Click on **Browse**.
- ✓ Specify the local path of the enterprise archive file:
 <KERNEL_INSTALL_DIR>/SSIAD_EJB_ACK/build/SSIAD_EJB_ACK_Bean.ear
- ✓ Click on **Next**.



Deploy: Select Archive

[Cancel](#) Step 1 of 3 [Next](#)

Archive

The following types of archives can be deployed: J2EE application (EAR files), Web Modules (WAR files), EJB Modules (EJB JAR files) and Resource Adapter Modules (RAR files).

- Archive is present on local host. Upload the archive to the server where Application Server Control is running.
 Archive Location [Browse...](#)
- Archive is already present on the server where Application Server Control is running.
 Location on Server
The location on server must be the absolute path or the relative path from j2ee/home

Deployment Plan

The deployment plan is an XML file that contains the deployment settings for an application. If you do not have a deployment plan, one will be created automatically during the deployment process. Later in the deployment process, you can optionally edit the deployment plan and save it for a future deployment of this application.

- Automatically create a new deployment plan.
The deployment plan settings will be based on OC4J defaults and information contained in the archive
- Deployment plan is present on local host. Upload the deployment plan to the server where Application Server Control is running.
 Plan Location [Browse...](#)
- Deployment plan is already present on server where Application Server Control is running.
 Location on Server
The location on server must be the absolute path or the relative path from j2ee/home

[Cancel](#) Step 1 of 3 [Next](#)

6. Following screen will be displayed.

- ✓ Click on **Next**.

The screenshot shows the Oracle Enterprise Manager 10g Application Server Control interface. At the top, the title bar reads "ORACLE Enterprise Manager 10g Application Server Control" with "Help" and "Logout" links on the right. A progress bar below the title bar has three steps: "Select Archive" (inactive), "Application Attributes" (active), and "Deployment Settings" (inactive). The main content area is titled "Deploy: Application Attributes" and contains the following information:

- Archive Type: **J2EE Application (EAR file)**
- Archive Location: **D:\KERNEL_SSIAD_OC4J\SSIAD_EJB_ACK\build\SSIAD_EJB_ACK_Bean.ear**
- Deployment Plan: **Creating a new plan**

At the bottom right of the main content area, there are buttons for "Cancel", "Back", "Step 2 of 3", and "Next". The "Next" button is highlighted with a red box. Below this, there are three input fields:

- * Application Name: (highlighted with a red box)
- Parent Application: (dropdown menu)
- Bind Web Module to Site: (dropdown menu)

At the bottom right of the page, there are buttons for "Cancel", "Back", "Step 2 of 3", and "Next". The "Next" button is highlighted with a red box. At the bottom center, there are links for "Help" and "Logout". At the bottom left, the copyright notice reads "Copyright © 1996, 2005, Oracle. All rights reserved."

7. Following screen will be displayed.

- ✓ Go to **Configure EJBs** Task.



Deploy: Deployment Settings

[Cancel](#) [Back](#) Step 3 of 3 [Deploy](#)

Archive Type **J2EE Application (EAR file)**
 Archive Location **D:\KERNEL_SSIAD_OC4J\SSIAD_EJB_ACK\build\SSIAD_EJB_ACK_Bean.ear**
 Deployment Plan **Creating a new plan**

Application Name **SSIAD_EJB_ACK_Bean**
 Parent Application **default**
 Bind Web Module to Site **default-web-site**
 Context Root

Deployment Tasks

The table below provides a set of common deployment tasks you might want to perform for this application. Only those tasks that apply to the current application are enabled.

Task Name	Go To Task	Description
Map Environment References		Map any environment references in your application (for example, data sources) to physical entities currently present on the operational environment.
Select Security Provider		A security provider acts as the source for available users and groups when mapping security roles.
Map Security Roles		Map any security roles exposed by your application to existing users and groups. The list of users and groups is obtained from the security provider you selected for this application.
Configure EJBs		Configure the Enterprise JavaBeans in your application.
Configure Clustering		Configure clustering of your application.
Configure Class Loading		Manipulate the classpath of your application.

Advanced Deployment Plan Editing

Click Edit Deployment Plan to set more advanced deployment options.

[Edit Deployment Plan](#)

8. Following screen will be displayed.

- ✓ **JNDI Name to Bind this EJB** – Enter **SSIAD_EJB_Bean**
- ✓ Click on **OK**



Deployment Settings: Configure Enterprise Beans

Cancel OK

Archive Type **J2EE Application (EAR file)**
 Archive Location **D:\KERNEL_SSIAD_OC4J\SSIAD_EJB_ACK\build\SSIAD_EJB_ACK_Bean.ear**
 Deployment Plan **Creating a new plan**

Application Name **SSIAD_EJB_ACK_Bean**
 Parent Application **default**
 Bind Web Module to Site **default-web-site**
 Context Root

Configure Entity Beans

Entity Bean	EJB Module	Persistence Type	Pool Size		Max Transaction Retries	Pool Cache Timeout (sec)	JNDI Name to Bind this EJB
			Min Instances	Max Instances			
No entity beans found							

Configure Session Beans

Session Bean ▲	EJB Module	Pool Size		Max Transaction Retries (default: 0)	Timeouts		JNDI Name to Bind this EJB
		Min Instances (default: 0)	Max Instances (default: 0)		Call Timeout (ms) (default: 90,000)	Pool Cache Timeout (sec) (default: 60)	
SSIAD_EJB_ACK_Bean	SSIAD_EJB_ACK_Bean.jar	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	SSIAD_EJB_ACK_Bean

9. Following screen will be displayed.

- ✓ Go to **Configure Class Loading** Task.



Deploy: Deployment Settings

[Cancel](#) [Back](#) Step 3 of 3 [Deploy](#)

Archive Type **J2EE Application (EAR file)**
 Archive Location **D:\KERNEL_SSIAD_OC4J\SSIAD_EJB_ACK\build\SSIAD_EJB_ACK_Bean.ear**
 Deployment Plan **Creating a new plan**

Application Name **SSIAD_EJB_ACK_Bean**
 Parent Application **default**
 Bind Web Module to Site **default-web-site**
 Context Root

Deployment Tasks

The table below provides a set of common deployment tasks you might want to perform for this application. Only those tasks that apply to the current application are enabled.

Task Name	Go To Task	Description
Map Environment References		Map any environment references in your application (for example, data sources) to physical entities currently present on the operational environment.
Select Security Provider		A security provider acts as the source for available users and groups when mapping security roles.
Map Security Roles		Map any security roles exposed by your application to existing users and groups. The list of users and groups is obtained from the security provider you selected for this application.
Configure EJBs		Configure the Enterprise JavaBeans in your application.
Configure Clustering		Configure clustering of your application.
Configure Class Loading		Manipulate the classpath of your application.

Advanced Deployment Plan Editing

Click Edit Deployment Plan to set more advanced deployment options.

[Edit Deployment Plan](#)

10. Following screen will be displayed.

- ✓ Uncheck **oracle.xml**
- ✓ Click on **Ok**



Deployment Settings: Configure Class Loading

Cancel OK

Archive Type **J2EE Application (EAR file)**
 Archive Location **D:\KERNEL_SSIAD_OC4J\SSIAD_EJB_ACK\build\SSIAD_EJB_ACK_Bean.ear**
 Deployment Plan **Creating a new plan**

Application Name **SSIAD_EJB_ACK_Bean**
 Parent Application **default**
 Bind Web Module to Site **default-web-site**
 Context Root

Import Shared Libraries

The following table lists the shared libraries installed in this OC4J instance. Select Import to declare your application's dependency on a shared library. Optionally specify a minimum or maximum version to import.

- Inherit parent application's shared library imports
- TIP** When checked, future changes to the parent application's shared library imports will be effective to this application.

Previous 10 11-20 of 22 Next 2					
Shared Library	Available Versions	Minimum Version To Use	Maximum Version To Use	Imported By Parent Application	Import
oracle.jdbc	10.1.0_2	<input type="text"/>	<input type="text"/>	✓	<input checked="" type="checkbox"/>
oracle.jwsdl	10.1.3	<input type="text"/>	<input type="text"/>	✓	<input checked="" type="checkbox"/>
oracle.sqlj	10.1.3	<input type="text"/>	<input type="text"/>	✓	<input checked="" type="checkbox"/>
oracle.toplink	10.1.3	<input type="text"/>	<input type="text"/>	✓	<input checked="" type="checkbox"/>
oracle.ws.client	10.1.3	<input type="text"/>	<input type="text"/>	✓	<input checked="" type="checkbox"/>
oracle.ws.core	10.1.3	<input type="text"/>	<input type="text"/>		<input type="checkbox"/>
oracle.ws.reliability	10.1.3	<input type="text"/>	<input type="text"/>		<input type="checkbox"/>
oracle.ws.security	10.1.3	<input type="text"/>	<input type="text"/>		<input type="checkbox"/>
oracle.wsm	10.1.3	<input type="text"/>	<input type="text"/>		<input type="checkbox"/>
oracle.xml	10.1.0_2	<input type="text"/>	<input type="text"/>	✓	<input type="checkbox"/>

[Previous 10](#) 11-20 of 22 [Next 2](#)

Configure Application Libraries

Add additional archives or directories to this application's classpath. Specify a path relative to the root of the EAR, or an absolute path on the target server.

11. Following screen will be displayed.

- ✓ Click on **Deploy**



i Information

Deployment plan has been updated successfully.

Deploy: Deployment Settings

Step 3 of 3

Archive Type **J2EE Application (EAR file)**
 Archive Location **D:\KERNEL_SSIAD_OC4J\SSSIAD_EJB_ACK\build\SSSIAD_EJB_ACK_Bean.ear**
 Deployment Plan **Creating a new plan**

Application Name **SSSIAD_EJB_ACK_Bean**
 Parent Application **default**
 Bind Web Module to Site **default-web-site**
 Context Root

Deployment Tasks

The table below provides a set of common deployment tasks you might want to perform for this application. Only those tasks that apply to the current application are enabled.

Task Name	Go To Task	Description
Map Environment References		Map any environment references in your application (for example, data sources) to physical entities currently present on the operational environment.
Select Security Provider		A security provider acts as the source for available users and groups when mapping security roles.
Map Security Roles		Map any security roles exposed by your application to existing users and groups. The list of users and groups is obtained from the security provider you selected for this application.
Configure EJBs		Configure the Enterprise JavaBeans in your application.
Configure Clustering		Configure clustering of your application.
Configure Class Loading		Manipulate the classpath of your application.

Advanced Deployment Plan Editing

Click Edit Deployment Plan to set more advanced deployment options.

12. Following screen will be displayed.

✓ Click on **Return**

 **Confirmation**

[Return](#)

The Application "SSIAD_EJB_ACK_Bean" has been successfully deployed.

Progress Messages

```
[Jun 27, 2007 3:56:32 PM] Application Deployer for SSIAD_EJB_ACK_Bean STARTS.  
[Jun 27, 2007 3:56:33 PM] Copy the archive to D:\OracleAS_1\j2ee\home\applications\SSIAD_EJB_ACK_Bean.ear  
[Jun 27, 2007 3:56:33 PM] Initialize D:\OracleAS_1\j2ee\home\applications\SSIAD_EJB_ACK_Bean.ear begins...  
[Jun 27, 2007 3:56:33 PM] Unpacking SSIAD_EJB_ACK_Bean.ear  
[Jun 27, 2007 3:56:33 PM] Done unpacking SSIAD_EJB_ACK_Bean.ear  
[Jun 27, 2007 3:56:33 PM] Initialize D:\OracleAS_1\j2ee\home\applications\SSIAD_EJB_ACK_Bean.ear ends...  
[Jun 27, 2007 3:56:33 PM] Starting application : SSIAD_EJB_ACK_Bean  
[Jun 27, 2007 3:56:33 PM] Initializing ClassLoader(s)  
[Jun 27, 2007 3:56:33 PM] Initializing EJB container  
[Jun 27, 2007 3:56:33 PM] Loading connector(s)  
[Jun 27, 2007 3:56:33 PM] Starting up resource adapters  
[Jun 27, 2007 3:56:33 PM] Processing EJB module: SSIAD_EJB_ACK_Bean.jar  
[Jun 27, 2007 3:56:34 PM] Compiling EJB generated code  
[Jun 27, 2007 3:56:43 PM] Initializing EJB sessions  
[Jun 27, 2007 3:56:43 PM] Committing ClassLoader(s)  
[Jun 27, 2007 3:56:43 PM] Started application : SSIAD_EJB_ACK_Bean  
[Jun 27, 2007 3:56:43 PM] Binding web application(s) to site default-web-site begins...  
[Jun 27, 2007 3:56:43 PM] Binding web application(s) to site default-web-site ends...  
[Jun 27, 2007 3:56:43 PM] Application Deployer for SSIAD_EJB_ACK_Bean COMPLETES. Operation time: 10593 msec
```

[Return](#)

13. Following screen will be displayed

ORACLE Enterprise Manager 10g
Application Server Control Setup Logs Help Logout

Cluster Topology > Application Server: oracle.DDTD0270.i-flex.com >
OC4J: home Page Refreshed Jun 27, 2007 3:58:22 PM IST

Home Applications Web Services Performance Administration

This page shows the J2EE applications and application components (EJB Modules, WAR Modules, Resource Adapter Modules) deployed to this OC4J instance.

View Applications

Start Stop Restart Undeploy Redeploy | Deploy

Expand All | Collapse All

Select	Name	Status	Start Time	Active Requests	Request Processing Time (seconds)	Active EJB Methods	Application Defined MBeans
<input type="radio"/>	▼ All Applications						
<input type="radio"/>	ascontrol	↑	Jun 27, 2007 1:13:06 PM IST	1	0.00	0	
<input checked="" type="radio"/>	▼ default	↑	Jun 27, 2007 1:13:06 PM IST	0	0.00	0	
<input type="radio"/>	▼ GW_EJB_Bean	↑	Jun 27, 2007 1:13:07 PM IST	0	0.00	0	
<input type="radio"/>	GW_HTTP_Servlet	↑	Jun 27, 2007 1:13:07 PM IST	0	0.00	0	
<input type="radio"/>	GW_MDB_Bean	↑	Jun 27, 2007 1:13:16 PM IST	0	0.00	0	
<input type="radio"/>	SSIAD_Client_Servlet	↑	Jun 27, 2007 1:13:17 PM IST	0	0.00	0	
<input type="radio"/>	SSIAD_EJB_ACK_Bean	↑	Jun 27, 2007 3:56:43 PM IST	0	0.00	0	
<input type="radio"/>	SSIAD_EJB_Bean	↑	Jun 27, 2007 2:54:11 PM IST	0	0.00	0	
<input type="radio"/>	bc4j	↑	Jun 27, 2007 1:13:06 PM IST	0	0.00	0	

Start Stop Restart Undeploy Redeploy | Deploy

Home Applications Web Services Performance Administration

Setup | Logs | Help | Logout

E. Notifying the SSIAD_EJB_ACK_Bean to start polling on Folder

- ✓ For Windows
 1. Open a Command prompt
 2. Go to <KERNEL_INSTALL_DIR>\setup
 3. Type **set_env** and press Enter.
 4. Go to <KERNEL_INSTALL_DIR>\SSIAD_EJB_ACK\client\OC4J
 5. Type **runEJB_ACKClient START** and press enter

- ✓ For Unix
 1. Go to <KERNEL_INSTALL_DIR>/setup
 2. Type **chmod +x set_env.sh** and press Enter.
 3. Type **set_env.sh** and Press Enter.
 4. Go to <KERNEL_INSTALL_DIR>/ SSIAD_EJB_ACK/client/OC4J
 5. Type **chmod +x runEJB_ACKClient.sh**
 6. Type **runEJB_ACKClient.sh START** and press Enter

F. Canceling the SSIAD_EJB_ACK_Bean so as to stop polling on Folder

- ✓ For Windows
 1. Open a Command prompt
 2. Go to <KERNEL_INSTALL_DIR>/setup
 3. Type **set_env** and press Enter.
 4. Go to <KERNEL_INSTALL_DIR>/ SSIAD_EJB_ACK/client/OC4J
 5. Type **runEJBClient STOP** and press enter

- ✓ For Unix
 1. Go to <KERNEL_INSTALL_DIR>/setup
 2. Type **chmod +x set_env.sh** and press Enter.
 3. Type **set_env.sh** and Press Enter.
 4. Go to <KERNEL_INSTALL_DIR>/ SSIAD_EJB_ACK/client/OC4J
 5. Type **chmod +x runEJB_ACKClient.sh**
 6. Type **runEJB_ACKClient.sh STOP** and press Enter



FLEXCUBE UBS Inbound Application Adapter Installation Document

[May] [2016]
Version 12.2.0.0.0

Oracle Financial Services Software Limited
Oracle Park
Off Western Express Highway
Goregaon (East)
Mumbai, Maharashtra 400 063
India

Worldwide Inquiries:
Phone: +91 22 6718 3000
Fax: +91 22 6718 3001
www.oracle.com/financialservices/

Copyright © [2008], [2016], Oracle and/or its affiliates. All rights reserved.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate failsafe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.