

Oracle® Retail Category Management

Configuration Guide

Release 13.2

July 2010

Copyright © 2010, Oracle and/or its affiliates. All rights reserved.

Primary Author: Barrett Gaines

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this software or related documentation is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, the following notice is applicable:

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation shall be subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License (December 2007). Oracle USA, Inc., 500 Oracle Parkway, Redwood City, CA 94065.

This software is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications which may create a risk of personal injury. If you use this software in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure the safe use of this software. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software in dangerous applications.

Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

This software and documentation may provide access to or information on content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.

Licensing Note: This media pack includes a Restricted Use license for Oracle Retail Predictive Application Server (RPAS) - Enterprise Engine to support Oracle® Retail Category Management only.

Value-Added Reseller (VAR) Language

Oracle Retail VAR Applications

The following restrictions and provisions only apply to the programs referred to in this section and licensed to you. You acknowledge that the programs may contain third party software (VAR applications) licensed to Oracle. Depending upon your product and its version number, the VAR applications may include:

- (i) the software component known as **ACUMATE** developed and licensed by Lucent Technologies Inc. of Murray Hill, New Jersey, to Oracle and imbedded in the Oracle Retail Predictive Application Server - Enterprise Engine, Oracle Retail Category Management, Oracle Retail Item Planning, Oracle Retail Merchandise Financial Planning, Oracle Retail Advanced Inventory Planning, Oracle Retail Demand Forecasting, Oracle Retail Regular Price Optimization, Oracle Retail Size Profile Optimization, Oracle Retail Replenishment Optimization applications.
- (ii) the **MicroStrategy** Components developed and licensed by MicroStrategy Services Corporation (MicroStrategy) of McLean, Virginia to Oracle and imbedded in the MicroStrategy for Oracle Retail Data Warehouse and MicroStrategy for Oracle Retail Planning & Optimization applications.
- (iii) the **SeeBeyond** component developed and licensed by Sun Microsystems, Inc. (Sun) of Santa Clara, California, to Oracle and imbedded in the Oracle Retail Integration Bus application.
- (iv) the **Wavelink** component developed and licensed by Wavelink Corporation (Wavelink) of Kirkland, Washington, to Oracle and imbedded in Oracle Retail Mobile Store Inventory Management.
- (v) the software component known as **Crystal Enterprise Professional and/or Crystal Reports Professional** licensed by SAP and imbedded in Oracle Retail Store Inventory Management.
- (vi) the software component known as **Access Via™** licensed by Access Via of Seattle, Washington, and imbedded in Oracle Retail Signs and Oracle Retail Labels and Tags.
- (vii) the software component known as **Adobe Flex™** licensed by Adobe Systems Incorporated of San Jose, California, and imbedded in Oracle Retail Promotion Planning & Optimization application.
- (viii) the software component known as **Style Report™** developed and licensed by InetSoft Technology Corp. of Piscataway, New Jersey, to Oracle and imbedded in the Oracle Retail Value Chain Collaboration application.
- (ix) the software component known as **DataBeacon™** developed and licensed by Cognos Incorporated of Ottawa, Ontario, Canada, to Oracle and imbedded in the Oracle Retail Value Chain Collaboration application.

You acknowledge and confirm that Oracle grants you use of only the object code of the VAR Applications. Oracle will not deliver source code to the VAR Applications to you. Notwithstanding any other term or condition of the agreement and this ordering document, you shall not cause or permit alteration of any VAR Applications. For purposes of this section, "alteration" refers to all alterations, translations, upgrades, enhancements, customizations or modifications of all or any portion of the VAR Applications including all reconfigurations, reassembly or reverse assembly, re-engineering or reverse engineering and recompilations or reverse compilations of the VAR Applications or any derivatives of the VAR Applications. You acknowledge that it shall be a breach of the agreement to utilize the relationship, and/or confidential information of the VAR Applications for purposes of competitive discovery.

The VAR Applications contain trade secrets of Oracle and Oracle's licensors and Customer shall not attempt, cause, or permit the alteration, decompilation, reverse engineering, disassembly or other reduction of the VAR Applications to a human perceivable form. Oracle reserves the right to replace, with functional equivalent software, any of the VAR Applications in future releases of the applicable program.

Contents

Send Us Your Comments	ix
Preface	xi
Audience.....	xi
Documentation Accessibility	xi
Related Documents	xii
Customer Support	xii
Review Patch Documentation	xii
Oracle Retail Documentation on the Oracle Technology Network	xiii
Conventions	xiii
 1 Introduction	
Function Registration Requirements	1-1
Syntax Conventions	1-1
 2 Configuring the ASOSpace Function	
Data Requirements for ASOSpace (Macro)	2-1
Profit Table Information.....	2-1
Constraint Information.....	2-1
ASOSpace Function Syntax.....	2-2
Configuration Parameters and Rules	2-3
Input Parameters.....	2-3
Output Parameters.....	2-5
ASOSpace Troubleshooting	2-6
ASOSpace Error Codes.....	2-6
 3 Configuring the ASOAssort Function	
Data Requirements for ASOAssort (Micro)	3-1
Demand, Retail, and Replenishment Requirements	3-1
Planogram Information	3-2
Shelf Information	3-2
Store and Stock Clerk Operation Hours Information	3-2
Optional Values	3-2

Additional Inputs	3-2
ASOAssort Function Syntax	3-3
Configuration Parameters and Rules	3-4
Input Parameters	3-4
Output Parameters.....	3-8
ASOAssort Troubleshooting	3-9
ASOAssort Error Codes	3-9

A Appendix: Using the Category Management Sample Data Set

List of Tables

1-1	Syntax Conventions	1-1
2-1	ASOSpace Input Parameters	2-3
2-2	ASOSpace Output Parameters	2-5
2-3	ASOSpace Error Codes	2-6
3-1	ASOAssort Input Parameters	3-4
3-2	ASOAssort Output Parameters	3-8
3-3	ASOAssort Error Codes	3-9
A-1	Category Management Data Files	A-1

Send Us Your Comments

Oracle Retail Category Management Configuration Guide, 13.2

Oracle welcomes customers' comments and suggestions on the quality and usefulness of this document.

Your feedback is important, and helps us to best meet your needs as a user of our products. For example:

- Are the implementation steps correct and complete?
- Did you understand the context of the procedures?
- Did you find any errors in the information?
- Does the structure of the information help you with your tasks?
- Do you need different information or graphics? If so, where, and in what format?
- Are the examples correct? Do you need more examples?

If you find any errors or have any other suggestions for improvement, then please tell us your name, the name of the company who has licensed our products, the title and part number of the documentation and the chapter, section, and page number (if available).

Note: Before sending us your comments, you might like to check that you have the latest version of the document and if any concerns are already addressed. To do this, access the new Applications Release Online Documentation CD available on My Oracle Support and <http://www.oracle.com>. It contains the most current Documentation Library plus all documents revised or released recently.

Send your comments to us using the electronic mail address: retail-doc_us@oracle.com

Please give your name, address, electronic mail address, and telephone number (optional).

If you need assistance with Oracle software, then please contact your support representative or Oracle Support Services.

If you require training or instruction in using Oracle software, then please contact your Oracle local office and inquire about our Oracle University offerings. A list of Oracle offices is available on our Web site at <http://www.oracle.com>.

Preface

Oracle Retail Configuration Guides are designed so that you can view and understand the application's "behind-the-scenes" processing, including such information as the key system administration configuration settings.

Audience

Anyone who has an interest in better understanding the inner workings of the Category Management system can find valuable information in this guide. There are three audiences in general for whom this guide is written:

- System analysts and system operation personnel:
 - Who are looking for information about Category Management processes internally or in relation to the systems across the enterprise.
 - Who operate Category Management on a regular basis.
- Integrators and implementation staff who have the overall responsibility for implementing Category Management into their enterprise.
- Business analysts who are looking for information about processes and interfaces to validate the support for business scenarios within Category Management and other systems across the enterprise.

Documentation Accessibility

Our goal is to make Oracle products, services, and supporting documentation accessible to all users, including users that are disabled. To that end, our documentation includes features that make information available to users of assistive technology. This documentation is available in HTML format, and contains markup to facilitate access by the disabled community. Accessibility standards will continue to evolve over time, and Oracle is actively engaged with other market-leading technology vendors to address technical obstacles so that our documentation can be accessible to all of our customers. For more information, visit the Oracle Accessibility Program Web site at <http://www.oracle.com/accessibility/>.

Accessibility of Code Examples in Documentation

Screen readers may not always correctly read the code examples in this document. The conventions for writing code require that closing braces should appear on an otherwise empty line; however, some screen readers may not always read a line of text that consists solely of a bracket or brace.

Accessibility of Links to External Web Sites in Documentation

This documentation may contain links to Web sites of other companies or organizations that Oracle does not own or control. Oracle neither evaluates nor makes any representations regarding the accessibility of these Web sites.

Access to Oracle Support

Oracle customers have access to electronic support through My Oracle Support. For information, visit <http://www.oracle.com/support/contact.html> or visit <http://www.oracle.com/accessibility/support.html> if you are hearing impaired.

Related Documents

For more information, see the following documents in the Oracle Retail Category Management 13.2 documentation set:

- *Oracle Retail Category Management Release Notes*
- *Oracle Retail Category Management Installation Guide*
- *Oracle Retail Category Management User Guide*
- Oracle Retail Predictive Application Server documentation set

Customer Support

To contact Oracle Customer Support, access My Oracle Support at the following URL:

<https://support.oracle.com>

When contacting Customer Support, please provide the following:

- Product version and program/module name
- Functional and technical description of the problem (include business impact)
- Detailed step-by-step instructions to re-create
- Exact error message received
- Screen shots of each step you take

Review Patch Documentation

When you install the application for the first time, you install either a base release (for example, 13.1) or a later patch release (for example, 13.1.2). If you are installing the base release, additional patch, and bundled hot fix releases, read the documentation for all releases that have occurred since the base release before you begin installation. Documentation for patch and bundled hot fix releases can contain critical information related to the base release, as well as information about code changes since the base release.

Oracle Retail Documentation on the Oracle Technology Network

Documentation is packaged with each Oracle Retail product release. Oracle Retail product documentation is also available on the following Web site:

http://www.oracle.com/technology/documentation/oracle_retail.html

(Data Model documents are not available through Oracle Technology Network. These documents are packaged with released code, or you can obtain them through My Oracle Support.)

Documentation should be available on this Web site within a month after a product release.

Conventions

The following text conventions are used in this document:

Convention	Meaning
boldface	Boldface type indicates graphical user interface elements associated with an action, or terms defined in text or the glossary.
<i>italic</i>	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.
<code>monospace</code>	Monospace type indicates commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter.

Introduction

This document provides information on the Assortment and Space Optimization (ASO) Solution Extension library for Category Management, which contains the following functions:

- ASOSpace
- ASOAssort

Function Registration Requirements

Make sure the ASOExpressions function is registered in any domains that use the ASO Solution Extension. This function is automatically registered by the Category Manager Installer during the installation process.

Syntax Conventions

The table below displays the syntax conventions used in this document.

Table 1–1 Syntax Conventions

Indicator	Definition
[...]	All options listed in brackets are optional.
{... ...}	Options listed in "{}" with " " separators are mutually exclusive (either/or).
{...,...}	Options listed in "{}" with "," separators way are a complete set.
Bold	Labels
<i>Italics</i>	Italics indicate a temporary placeholder for a constant or a measure.
<i>Italics/meas</i>	This indicates that the placeholder can be either a constant or a measure.
<i>Bold Italics</i>	This indicates a numeric placeholder for the dynamic portion of a label. Usually a number from 1 to N.
Normal	Normal text signifies required information.
<u>Underlined</u>	This convention is used to identify the function name.

Configuring the ASOSpace Function

Space optimization begins with an RPAS special expression called ASOSpace. The expression is evaluated in a procedure and will be the starting point for all calculations. This special expression will be recognizable by RPAS and will be used as a calc rule for the appropriate measures. Since all measures are registered at the week level and Space optimizes at the phase level, the calc rule will aggregate all the appropriate measures to the correct level using the aggregated method specified for each measure. All measures are configured at the appropriate subcategory level and ASOSpace can differentiate between the different configurations so no alterations are needed.

ASOSpace will take data from specific measures in the domain and use this data to perform the calculation process to create and calculate a Profit Matrix and a Plano Size Matrix at the subcategory level. For result measures, the phase level result will be spread down to be stored at the week level. 100 histogram data points will also be recorded in the domain.

Data Requirements for ASOSpace (Macro)

This section provides information about the various data requirements when using the ASOSpace function. Some of this information may need to be combined through rules before calling the special expression, as called out in the parameter descriptions provided.

Profit Table Information

ASOSpace requires the following profit table information:

- Profit Vector
- Planogram Length Vector

Constraint Information

ASOSpace requires the following constraint information:

- Minimum Space by SubCat/Str/Phase
- Maximum Space by SubCat/Str/Phase
- Maximum Capacity constraint by Str/Phase
- Constraint Type (L for LESSEQUAL, E for EQUAL)

ASOSpace Function Syntax

The syntax for using the ASOSpace function appears below. The input and out parameter table explain the specific usage of the parameters names use in the function.

Generic Example:

```
OPTPROFITLB, OPTSPACELB, HISTPROFITLB, HISTSPACELB, OPTRESULTLB <-  
ASOSpace(MAXCAPACITYLB, CONSTRAINTMODEL, INCLUDELB, MANDATORYLB, MINSPACELB,  
MAXSPACELB, PROFITLISTLB, SPACELISTLB, OPTMETHODLB)
```

Sample:

```
OPTPROFITLB:MgOtExpProfR.level([clnd].[phse]),  
OPTSPACELB:MgOtSpaceX.level([clnd].[phse]),  
HISTPROFITLB:MgOtHistProfR.level([clnd].[phse]),  
HISTSPACELB:MgOtHistCostX.level([clnd].[phse]),  
OPTRESULTLB:MgOtResultX.level([clnd].[phse]) <-  
ASOSpace(MAXCAPACITYLB:MgWpMaxCapX.level([clnd].[phse]),  
CONSTRAINTMODEL:MgWpConsTypSl.level([clnd].[phse]),  
INCLUDELB:MgWpIncludeB.level([clnd].[phse]),  
MANDATORYLB:MgWpManCatB.level([clnd].[phse]),  
MINSPACELB:MgWpMinSpX.level([clnd].[phse]),  
MAXSPACELB:MgWpMaxSpX.level([clnd].[phse]),  
PROFITLISTLB:AdWpPogPftR.level([clnd].[phse]),  
SPACELISTLB:AdWpPogLX.level([clnd].[phse]),  
OPTMETHODLB:MgWpOptMthX.level([clnd].[phse]))
```

Configuration Parameters and Rules

The following tables contain the input and output parameters.

Input Parameters

The table below provides the input parameters for the ASOSpace function.

Table 2–1 ASOSpace Input Parameters

Parameter	Measure Name from Category Management Template	Description
MAXCAPACITYLB	MgWpMaxCapX	A real number indicating the maximum total space that the optimized solution can reach per LOC/CLND. Data Type: Real Intersection: STR/PHSE Required: Yes
CONSTRAINTMODELB	MgWpConsTypSl	An integer measure indicating the space constraint type per LOC/CLND. The following four modes are available: - less/equal - approxequal - exactlyequal - greater/equal The default value is less/equal. Data Type: Real Intersection: STR/PHSE Required: No
INCLUDELB	MgWpIncludeB	A Boolean measure indicating if a PRD/LOC/CLND is included in the space optimization. Data Type: Boolean Intersection: SCAT/STR/PHSE Required: Yes
MANADATORYLB	MgWpManCatB	A Boolean measure indicating that a PROD/LOC/CLND has to be included in the optimization solution. Data Type: Boolean Intersection: SCAT/STR Required: Yes
MINSPACELB	MgWpMinSpX	Minimum Space Constraint for a PROD/LOC/CLND. Data Type: Real Intersection: SCAT/STR/PHSE Required: Yes

Table 2–1 (Cont.) ASOSpace Input Parameters

Parameter	Measure Name from Category Management Template	Description
MAXSPACELB	MgWpMaxSpX	Maximum Space Constraint for a PROD/LOC/CLND. Data Type: Real Intersection: SCAT/STR/PHSE Required: Yes
PROFITLISTLB	AdWpPogPftR	A real measure indicating the profit per PROD/LOC/CLND/POG Data Type: Real Intersection: SCAT/STR/PHSE/PLNG Required: Yes
SPACELISTLB	AdWpPogLX	A real measure indicating the profit per PROD/LOC/CLND/POG. Data Type: Real Intersection: SCAT/STR/PHSE/PLNG Required: Yes
OPTMETHODLB	MgWpOptMthX	An integer measure indicating the optimization method per LOC/CLND. The available methods are as follows: ■ Optimal (dynamic programming) ■ Heuristic To use the optimal (dynamic programming) method, this value should be 0. To use the heuristic method, this value should be 1. Data Type: Real Intersection: STR/PHSE Required: No

Output Parameters

The table below provides the output parameters for the ASOSpace function.

Table 2–2 ASOSpace Output Parameters

Parameter Name	Measure Name from Category Management Template	Description
OPTPROFITLB	MgOtExpProfR	The Optimized Profit Solution per PROD/LOC/CLND. Data Type: Real Intersection: SCAT/STR/PHSE Required: Yes
OPTSPACELB	MgOtSpaceX	The Optimized Space per PROD/LOC/CLND. Data Type: Real Intersection: SCAT/STR/PHSE Required: Yes
HISTPROFITLB	MgOtHistProfR	Profit histogram from optimization. This parameter is only an option when choosing the dynamic programming as OPTMETHODLB. Data Type: Real Intersection: STR/PHSE/LNUM Required: No
HISTSPACELB	MgOtHistCostX	The corresponding space for the histogram. This parameter is only an option when choosing the dynamic programming as OPTMETHOD. Data Type: Real Intersection: STR/PHSE/LNUM Required: No
OPTRESULTLB	MgOtResultX	The corresponding space for the histogram. This parameter is only an option when choosing the dynamic programming as OPTMETHOD. Data Type: Real Intersection: STR/PSHE Required: No

ASOSpace Troubleshooting

If errors and issues are encountered when working with the ASOSpace function, inspect the following items:

- Ensure that the lhs and rhs of the expression have the correct number of arguments.
- Ensure that the lhs and rhs of the expression are measures.
- Ensure that all non-Boolean measures are set to a type of Real.
- Ensure that all measures are set to the proper base intersections.
- Ensure that the Product, Location, and Calendar positions being used for the optimization have populated input values.

ASOSpace Error Codes

Data validation will be performed per LOC/CLND combination prior to optimization. Optimization will be skipped if the data validation fails. Optimized profit can store some of the errors on PROD/LCO/CLND level. It can be displayed in the RPAS Client as a picklist. The following table provides a list of error codes that may be displayed if an issue is encountered.

Table 2–3 ASOSpace Error Codes

Error Code	Description
-999	Invalid maxcapacity
-998	Invalid optimization method
-997	Invalid constraint mode
-996	Maximum space less than minimum space
-995	Invalid mandatory subcategory with invalid maximum space
-994	Solution not feasible, the total of mandatory minimum space is over maximum capacity
-992	Mandatory items with invalid profit table

Configuring the ASOAssort Function

ASOAssort function uses a specialized Dynamic Programming method to generate optimal Assortment plan that maximize total profit constraint by total shelf space. This is based on each item's size, cost, retail price, and demand as well as a store's operating time and replenishment strategy.

Although the target of the optimization is for each item, the ASOAssort function divides the total problem into two levels and solves it level by level to improve performance. The first level is called Collection in Assortment Planning terminology, which is usually implemented on the STYL dimension. The second level is called Subcategory, which is usually implemented on the SCAT dimension. For this reason, the ASOAssort function requires some duplicated inputs on multiple levels, like Include Flag and Mandatory Flag. For Calendar, the time period used for Assort Optimization is usually called a Phase, which is implemented on the PHSE dimension.

Input arguments for the ASOAssort function (like Cost and Retail Prices) are in the unit of Dollars. Demand is in the unit of Units. For Size arguments, the unit is usually Planogram size, which will be converted to real size metric like inches or centimeters based on UOM inputs.

The output of ASOAssort is the optimal planogram. Both the solutions at the Subcategory level and the Collection level are returned together with the profit/cost table at each level, the Stock Out unit/dollars table, and the histogram table at the item level.

Data Requirements for ASOAssort (Micro)

This section provides information about the various data requirements when using the ASOAssort function. Some of this information may need to be combined through rules before calling the special expression, as called out in the parameter descriptions provided.

Demand, Retail, and Replenishment Requirements

ASOAssort requires the following demand, retail, and replenishment information:

- Regular Demand
 - Average Weekly Regular demand per Item/Str/Phase
- Maximum Demand by SKU/Store/Phase
- Item Cost by SKU/Str/Phase
- Item Price by SKU/Str/Phase
- Lead Time by SKU/Str/Phase

- Minimum number of facings to be included in the Planogram by SKU/Str/Phase
- Maximum number of facings to be included in the Planogram by SKU/Str/Phase
- Minimum shelf presence in units by SKU/Str/Phase

Planogram Information

ASOAssort requires the following planogram information:

- The planogram length by Str/Phase
- The unit of measure for Planogram length

Shelf Information

ASOAssort requires the following shelf information:

- Number of Shelves by SKU/Str/Phase
- Number of units that can sit on a shelf depth wise by SKU/Str/Phase by SKU/Str/Phase
- The Number of Shelves that can be used by Str/Phase
- Item width by SKU/Str/Phase
- The unit of measure for ITEMWIDTHLB
- The incremental size that will be considered for each sub-category

Store and Stock Clerk Operation Hours Information

ASOAssort requires the following store and stock clerk information:

- Number of hours the store is open for business per optimization period (Phase) by Str/Phase
- Number of hours between the stock clerk's rounds by Str.

Optional Values

The following optional values can be set to default values for demonstration purposes:

- Percentage of Safety Stock relative to Regular Demand by SKU/Str/Phase
- Probability the stock clerk will successfully replenish the shelf when supply falls below Minimum Shelf Presence quantity

Additional Inputs

When using the ASOAssort function, the user is expected to provide following inputs from the workbook:

- Identify if the item is required (mandatory) in the final item mix
- Identify the Constraint Type (L for LESSEQUAL, E for EQUAL)
- Indicate whether a STYL is required (mandatory) to show up in the final mix
- Indicate whether a STYL is included in the calculation

ASOAssort Function Syntax

The syntax for using the ASOAssort function appears below. The input and out parameter table explain the specific usage of the parameters names use in the function.

Generic Example:

```
OPTFACINGLB, OPTPROFITLB, OPTSPACELB, OPTSALESB, OPTLOSTSALESB,
OPTLOSTSALESBOLLARLB, HISTPROFITLB, HISTSPACEB, OPTRESULTB <-
ASOAssort(INCLUDEB, MINFACINGLB, MAXFACINGLB, MINSHELFPRESLB, FACINGCAPACITYB,
DEMANDB, MAXSUPPLYB, MANDATORYB, ITEMCOSTB, OPERATINGHOURS,
STOCKCLERKSUCCESSRATEB, STOCKCLERKCYCLETIMELB, ITEMRETAILB, ITEMWIDTHB,
CONSTRAINTMODEL, MAXCAPACITYB, OBJFUNCLB, OPTMETHODB, WEIGHTB)
```

Sample:

```
OPTFACINGLB:PlotItmRecFacX.level([clnd].[phse]),
OPTPROFITLB:PlotItmProfR.level([clnd].[phse]),
OPTSPACEB:PlotItmSolCstX.level([clnd].[phse]),
OPTSALESB:PlotItmBuyQtyU.level([clnd].[phse]),
OPTLOSTSALESB:PlotItmStkOutU.level([clnd].[phse]),
OPTLOSTSALESBOLLARLB:PlotItmStkOutR.level([clnd].[phse]),
HISTPROFITLB:PlotHistProfR.level([clnd].[phse]),
HISTSPACEB:PlotHistCostX.level([clnd].[phse]),
OPTRESULTB:PlotResultX.level([clnd].[phse])<- ASOAssort(INCLUDEB:
PlWpIncludeB.level([clnd].[phse]), MINFACINGLB:PlWpMinFacX.level([clnd].[phse]),
MAXFACINGLB:PlWpMaxFacX.level([clnd].[phse]), MINSHELFPRESLB:PlWpRstKTrgU.level([clnd].[phse]),
FACINGCAPACITYB:PlWpFacCapX.level([clnd].[phse]),
DEMANDB:PlFcDemandU.level([clnd].[phse]),
MAXSUPPLYB:PlWpSupplyMaxU.level([clnd].[phse]),
MANDATORYB:PlWpManItmB.level([clnd].[phse]),
ITEMCOSTB:PlWpItmCstC.level([clnd].[phse]),
OPERATINGHOURS:AdWpOpHrsX.level([clnd].[phse]),
STOCKCLERKSUCCESSRATEB:AdWpStkClSrtX, STOCKCLERKCYCLETIMELB:AdWpStkClkCTX,
ITEMRETAILB:PlWpItmRetR.level([clnd].[phse]),
ITEMWIDTHB:PlWpItmW2X.level([clnd].[phse]),
CONSTRAINTMODEL:PlWpConsTypSl.level([clnd].[phse]), MAXCAPACITYB:
PlWpMaxCapX.level([clnd].[phse]), OBJFUNCLB:PlWpObjFuncX.level([clnd].[phse]),
OPTMETHODB:PlWpOptMthX.level([clnd].[phse]),
WEIGHTB:PlWpWeightX.level([clnd].[phse]))
```

Configuration Parameters and Rules

The following tables contain the input and output parameters.

Input Parameters

Note that the Optimization special expression can take inputs with or without the planogram dimension. Also, planogram dimension could be called anything; the special expression is not hard coded to look for specific dimension names that represent planogram. The intersection of the INCLUDELB parameter drives the intersections that are expected by the special expression. For example, if the INCLUDELB parameter includes a planogram dimension, then the special expression expects other relevant measures (as listed below) to include the same planogram dimension as well.

The table below provides the input parameters for the ASOAssort function.

Table 3–1 ASOAssort Input Parameters

Parameter Name	Measure Name from Category Management Template	Description
INCLUDELB	PIWpIncludeB	A Boolean measure indicating if a PROD/LOC/CLND is included in the assortment optimization. Data Type: Boolean Intersection: SKU/STR/PHSE or SKU/STR/Planogram/PHSE Required: Yes
MINFACINGLB	PIWpMinFacX	The Minimum Number of Facings that must be included in the planogram. Data Type: Real Measure must have a non-zero value. Intersection: SKU/STR/PHSE or SKU/STR/Planogram/PHSE Required: Yes
MAXFACINGLB	PIWpMaxFacX	The Maximum Number of Facings that can be included in the planogram. Data Type: Real Measure must have a non-zero value. Intersection: SKU/STR/PHSE or SKU/STR/Planogram/PHSE Required: Yes

Table 3–1 (Cont.) ASOAssort Input Parameters

Parameter Name	Measure Name from Category Management Template	Description
MINSHELFPRESLB	PIWpRstkTrgU	The Minimum Shelf Presence in Units. Data Type: Real Measure values must be less than FACINGCAPACITYLB. Intersection: SKU/STR/PHSE or SKU/STR/Planogram/PHSE Required: Yes
FACINGCAPACITYLB	PIWpFacCapX	The number of units deep that can sit on a shelf. Data Type: Real Measure values must be greater than MINSHELFPRESLB. Intersection: SKU/STR/PHSE or SKU/STR/Planogram/PHSE Required: Yes
DEMANDLB	PIFcDemandU	Regular Demand Rate; the number of units in demand per PHSE. Data Type: Real Intersection: SKU/STR/PHSE or SKU/STR/Planogram/PHSE Required: Yes
MAXSUPPLYLB	PIWpSupplyMaxU	The maximum supply amount per PROD/LOC/CLND. This input should be decided by replenishment setting. It can be configured as $\text{MaxDemand} * \text{LeadTime} * (1 + \text{SafetyStockFactor})$. Data Type: Real Intersection: SKU/STR/PHSE or SKU/STR/PLANOGRAM/PHSE Required: Yes
MANDATORYLB	PIWpManItmB	The Mandatory Include Flag measure. Indicates whether the item is required in the final mix. Data Type: Boolean Intersection: SKU/STR/PHSE or SKU/STR/Planogram/PHSE Required: Yes
ITEMCOSTLB	PIWpItmCstC	The cost of the item to the retailer. Data Type: Real Intersection: SKU/STR/PHSE Required: Yes

Table 3–1 (Cont.) ASOAssort Input Parameters

Parameter Name	Measure Name from Category Management Template	Description
OPERATINGHOURS _{SLB}	AdWpOpHrsX	The number of Hours that the store is open for business, per optimization period (PHSE). Data Type: Real Intersection: STR/PHSE Required: Yes
STOCKCLERKSUCCESS _{RATE_{LB}}	AdWpStkClSRtX	Defined as the probability that the stock clerk will successfully replenish the shelf when the supply falls below the Minimum Shelf Presence (MINSHELF _{PRES_{LB}}) quantity. Data Type: Real Intersection: STR Required: Yes
STOCKCLERKCYCLE _{TIMELB}	AdWpStkClkCTX	The number of hours between the stock clerk's rounds. Measure values must be greater than zero (0). Data Type: Real Intersection: STR Required: Yes
ITEM _{RETAIL_{LB}}	PIWpItmRetR	The item cost to the consumer. Must be in the same unit as item cost. Data Type: Real Intersection: SKU/STR/PHSE Required: Yes
ITEM _{WIDTH_{LB}}	PIWpItmW2X	A real measure indicating item width on the shelf. The item width must be inches. Data Type: Real Intersection: SKU/STR/PHSE Required: Yes
CONSTRAINT _{MODEL_B}	IWpConsTypSl	Constraint type, which are defined as follows: ■ L for LESSEQUAL ■ E for EQUAL Data Type: Real Intersection: STR/PHSE Required: No

Table 3–1 (Cont.) ASOAssort Input Parameters

Parameter Name	Measure Name from Category Management Template	Description
MAXCAPACITYLB	PIWpMaxCapX	A real measure indicating the maximum total space that the optimized solution can reach per LOC/CLND/PLANOGRAM. This input must be in inches. It can be calculated as $\text{planosize} * \text{numofShelves}$. Data Type: Real Intersection: STR/PHSE Required: Yes
OBJFUNCLB	PIWpObjFuncX	An integer measure indicating which objective function is used in the optimization. The available modes are as follows: ■ Profit ■ Revenue return on space ■ Unit return on space ■ Gross margin return on space The default value is profit. Data Type: Real Intersection: STR/PHSE Required: No
OPTMETHODLB	PIWpOptMthX	An integer measure indicating the optimization method per LOC/CLND. The available methods are as follows: ■ Optimal (dynamic programming) ■ Heuristic The default value is Heuristic. Data Type: Real Intersection: STR/PHSE Required: No
WEIGHTLB	PIWpWeightX	A real measure to be multiplied with the OBJECTIVEFUNC for optimization. Data Type: Real Intersection: SKU/STR/PHASE Required: No

Output Parameters

The table below provides the output parameters for the ASOAssort function.

Table 3–2 ASOAssort Output Parameters

Parameter	Measure Name from Category Management Template	Description
OPTFACINGLB	PIOtItrRecFacX	Item solution recommended facing table. Data Type: Real Intersection: SKU/STR/PHSE Required: No
OPTPROFITLEB	PIOtItrProfR	Item solution expected profit table. Data Type: Real Intersection: SKU/STR/PHSE Required: Yes
OPTSPACELB	PIOtItrSolCstX	Item solution expected cost table. Data Type: Real Intersection: SKU/STR/PHSE Required: Yes
OPTSALESLB	PIOtItrBuyQtyU	Item solution expected buy quantity table. Data Type: Real Intersection: SKU/STR/PHSE Required: No
OPTLOSTSALESLB	PIOtItrStkOutU	Item solution stock out units table. Data Type: Real Intersection: SKU/STR/PHSE Required: No
OPTLOSTSALESDO LLARLB	PIOtItrStkOutR	Item solution stock out dollars table. Data Type: Real Intersection: SKU/STR/PHSE Required: No
HISTPROFITLEB	PIOtHistProfR	Histogram profit data points. Data Type: Real Intersection: STR/PHSE/LNUM Required: No
HISTSPACELB	PIOtHistCostX	Histogram cost data points. Data Type: Real Intersection: STR/PHSE/LNUM Required: No

Table 3–2 (Cont.) ASOAssort Output Parameters

Parameter	Measure Name from Category Management Template	Description
OPTRESULTLB	PIOtResultX	The corresponding space for the histogram. This parameter is only an option when choosing dynamic programming as OPTMETHODLB. Data Type: Real Intersection: STR/PSHE Required: No

ASOAssort Troubleshooting

If errors and issues are encountered when working with the ASOAssort function, inspect the following items:

- Ensure Measure Usage Comments are complied.
- Ensure that the lhs and rhs of the expression have the correct number of arguments.
- Ensure that the lhs and rhs of the expression are measures.
- Ensure that all non-Boolean measures are set to a type of Real.
- Ensure that all measures are set to the proper base intersections.
- Ensure that the Product, Location and Calendar positions being used for the optimization have populated input values.

ASOAssort Error Codes

Data validation will be performed per LOC/CLND/PLANOGRAM combination prior to optimization. Optimization will be skipped if the data validation fails. Optimized profit can store some of the errors on PROD/LCO/CLND/PLOANOGRAM level. It can be displayed in the RPAS Client as a picklist. The following table provides a list of error codes that may be displayed if an issue is encountered.

Table 3–3 ASOAssort Error Codes

Error Code	Description
-999	Invalid maxcapacity
-998	Invalid optimization method
-997	Invalid constraint mode
-996	Maximum space less than minimum space
-995	Invalid mandatory item with invalid maximum space
-994	Solution not feasible, the total of mandatory minimum space is over maximum capacity
-993	Weights for all the products are zero
-992	Mandatory items with invalid profit table
-991	Invalid objective function
-990	Invalid store operating hours

Table 3–3 (Cont.) ASOAssort Error Codes

Error Code	Description
-989	Invalid stock clerk success rate
-988	Invalid stock clerk cycle time
-987	No include item
-986	Invalid facing capacity
-985	Invalid minimum shelf presence
-984	Invalid item width
-983	Invalid item retail
-982	Invalid item cost
-981	Invalid demand
-980	Mandatory item with invalid maximum supply

Appendix: Using the Category Management Sample Data Set

The Category Management configuration is now packaged with a sample data set that supports the use of the template for demonstration purposes. The table below provides a list of data files (.ovr) that are now included (in addition to the hierarchy files) in the input directory of the Category Management package: The Category Management package also includes the load_meas script to support the loading of these measures into the resulting domain. Before executing the script, the DOMAIN environment variable must be set to the location of the Category Management domain.

Table A-1 Category Management Data Files

Category Management Data Files		
AdWpCompDefTx	IWpGMR	PIWpScatClstLTx
AdWpOpHrsX	PIWpGMRp	PIWpScatClstNTx
AdWpPogLDptX	PIWpItmCst2C	PIWpSctClstLTx
AdWpPogLX	PIWpItmCstC	PIWpSctClstNTx
AdWpPogPftDptR	PIWpItmDescTx	PIWpSfySkMultX
dWpPogPftRA	PIWpItmRet2R	PIWpSkuBrndB
AdWpStkClkCTX	PIWpItmRetR	PIWpSkuFeatTx
PIFcDemandU	PIWpLeadTimeX	PIWpSlsAr
PISpFacCapX	PIWpMaxFacX	PIWpSlsC
PISpItmWX	PIWpMaxLTX	PIWpSlsProC
PIWpAvgInvC	PIWpMinFacX	PIWpSlsR
PIWpAvgInvR	PIWpMkdC	PIWpSlsU
PIWpAvgInvU	PIWpNMR	PIWpStrClstLTx
PIWpCarryCstC	PIWpNMRp	PIWpStrClstNTx
PIWpCstFndsC	PIWpPayTermsX	PIWpStrDescTx
PIWpFreightC	PIWpRstkTrgU	PIWpVndRvAlwC

Note: It is important to note that the sample data set does not include data for all locations, products, and calendar positions. To generate optimization results, you must select relevant data.

