

Gateway Documentation - ICCF Service  
Oracle FLEXCUBE Universal Banking Release 11.3.83.02.0  
Release FCUBS\_11.3.2.0.0LA  
[April] [2014]



# Table Of Contents

<b>1. BACKGROUND</b>	<b>1</b>
<b>2. FCUBSCFService</b>	<b>2</b>
<b>2.1. AuthCFFloatRateMaint</b>	<b>2</b>
2.1.1. CF-AuthCFFloatRateMaint-Req-Full-MSG.xsd	2
2.1.2. CF-AuthCFFloatRateMaint-Req-IO-MSG.xsd	15
2.1.3. CF-AuthCFFloatRateMaint-Res-Full-MSG.xsd	22
2.1.4. CF-AuthCFFloatRateMaint-Res-PK-MSG.xsd	38
<b>2.2. AuthCFRateCodeMaint</b>	<b>55</b>
2.2.1. CF-AuthCFRateCodeMaint-Req-Full-MSG.xsd	55
2.2.2. CF-AuthCFRateCodeMaint-Req-IO-MSG.xsd	67
2.2.3. CF-AuthCFRateCodeMaint-Res-Full-MSG.xsd	74
2.2.4. CF-AuthCFRateCodeMaint-Res-PK-MSG.xsd	88
<b>2.3. AuthCFRateTypeDefn</b>	<b>102</b>
2.3.1. CF-AuthCFRateTypeDefn-Req-Full-MSG.xsd	102
2.3.2. CF-AuthCFRateTypeDefn-Req-IO-MSG.xsd	112
2.3.3. CF-AuthCFRateTypeDefn-Res-Full-MSG.xsd	119
2.3.4. CF-AuthCFRateTypeDefn-Res-PK-MSG.xsd	132
<b>2.4. AuthFLTRTDefn</b>	<b>145</b>
2.4.1. CF-AuthFLTRTDefn-Req-Full-MSG.xsd	145
2.4.2. CF-AuthFLTRTDefn-Req-IO-MSG.xsd	158
2.4.3. CF-AuthFLTRTDefn-Res-Full-MSG.xsd	165
2.4.4. CF-AuthFLTRTDefn-Res-PK-MSG.xsd	191
<b>2.5. AuthorizeFloatRateMaint</b>	<b>207</b>
2.5.1. CF-AuthorizeFloatRateMaint-Req-Full-MSG.xsd	207
2.5.2. CF-AuthorizeFloatRateMaint-Req-IO-MSG.xsd	223
2.5.3. CF-AuthorizeFloatRateMaint-Res-Full-MSG.xsd	230
2.5.4. CF-AuthorizeFloatRateMaint-Res-PK-MSG.xsd	248
<b>2.6. CloseFloatRateMaint</b>	<b>258</b>
2.6.1. CF-CloseFloatRateMaint-Req-Full-MSG.xsd	258
2.6.2. CF-CloseFloatRateMaint-Req-IO-MSG.xsd	274
2.6.3. CF-CloseFloatRateMaint-Res-Full-MSG.xsd	281
2.6.4. CF-CloseFloatRateMaint-Res-PK-MSG.xsd	299
<b>2.7. CreateCFFloatRateMaint</b>	<b>309</b>
2.7.1. CF-CreateCFFloatRateMaint-Req-Full-MSG.xsd	309
2.7.2. CF-CreateCFFloatRateMaint-Req-IO-MSG.xsd	322
2.7.3. CF-CreateCFFloatRateMaint-Res-Full-MSG.xsd	334
2.7.4. CF-CreateCFFloatRateMaint-Res-PK-MSG.xsd	355
<b>2.8. CreateCFRateCodeMaint</b>	<b>377</b>
2.8.1. CF-CreateCFRateCodeMaint-Req-Full-MSG.xsd	377
2.8.2. CF-CreateCFRateCodeMaint-Req-IO-MSG.xsd	389
2.8.3. CF-CreateCFRateCodeMaint-Res-Full-MSG.xsd	401
2.8.4. CF-CreateCFRateCodeMaint-Res-PK-MSG.xsd	420
<b>2.9. CreateCFRateTypeDefn</b>	<b>439</b>
2.9.1. CF-CreateCFRateTypeDefn-Req-Full-MSG.xsd	439
2.9.2. CF-CreateCFRateTypeDefn-Req-IO-MSG.xsd	449
2.9.3. CF-CreateCFRateTypeDefn-Res-Full-MSG.xsd	459
2.9.4. CF-CreateCFRateTypeDefn-Res-PK-MSG.xsd	476
<b>2.10. CreateFLTRTDefn</b>	<b>493</b>
2.10.1. CF-CreateFLTRTDefn-Req-Full-MSG.xsd	493
2.10.2. CF-CreateFLTRTDefn-Req-IO-MSG.xsd	506
2.10.3. CF-CreateFLTRTDefn-Res-Full-MSG.xsd	519
2.10.4. CF-CreateFLTRTDefn-Res-PK-MSG.xsd	545
<b>2.11. CreateFloatRateMaint</b>	<b>571</b>
2.11.1. CF-CreateFloatRateMaint-Req-Full-MSG.xsd	571

2.11.2. CF-CreateFloatRateMaint-Req-IO-MSG.xsd	587
2.11.3. CF-CreateFloatRateMaint-Res-Full-MSG.xsd	602
2.11.4. CF-CreateFloatRateMaint-Res-PK-MSG.xsd	620
<b>2.12. DeleteCFFloatRateMaint</b>	<b>637</b>
2.12.1. CF-DeleteCFFloatRateMaint-Req-Full-MSG.xsd	637
2.12.2. CF-DeleteCFFloatRateMaint-Req-IO-MSG.xsd	650
2.12.3. CF-DeleteCFFloatRateMaint-Res-Full-MSG.xsd	657
2.12.4. CF-DeleteCFFloatRateMaint-Res-PK-MSG.xsd	673
<b>2.13. DeleteCFRateCodeMaint</b>	<b>690</b>
2.13.1. CF-DeleteCFRateCodeMaint-Req-Full-MSG.xsd	690
2.13.2. CF-DeleteCFRateCodeMaint-Req-IO-MSG.xsd	702
2.13.3. CF-DeleteCFRateCodeMaint-Res-Full-MSG.xsd	708
2.13.4. CF-DeleteCFRateCodeMaint-Res-PK-MSG.xsd	722
<b>2.14. DeleteCFRateTypeDefn</b>	<b>736</b>
2.14.1. CF-DeleteCFRateTypeDefn-Req-Full-MSG.xsd	736
2.14.2. CF-DeleteCFRateTypeDefn-Req-IO-MSG.xsd	746
2.14.3. CF-DeleteCFRateTypeDefn-Res-Full-MSG.xsd	752
2.14.4. CF-DeleteCFRateTypeDefn-Res-PK-MSG.xsd	765
<b>2.15. DeleteFLTRTDefn</b>	<b>778</b>
2.15.1. CF-DeleteFLTRTDefn-Req-Full-MSG.xsd	778
2.15.2. CF-DeleteFLTRTDefn-Req-IO-MSG.xsd	791
2.15.3. CF-DeleteFLTRTDefn-Res-Full-MSG.xsd	798
2.15.4. CF-DeleteFLTRTDefn-Res-PK-MSG.xsd	813
<b>2.16. DeleteFloatRateMaint</b>	<b>822</b>
2.16.1. CF-DeleteFloatRateMaint-Req-Full-MSG.xsd	822
2.16.2. CF-DeleteFloatRateMaint-Req-IO-MSG.xsd	838
2.16.3. CF-DeleteFloatRateMaint-Res-Full-MSG.xsd	845
2.16.4. CF-DeleteFloatRateMaint-Res-PK-MSG.xsd	863
<b>2.17. ExecuteQryFLTRTDefn</b>	<b>872</b>
2.17.1. CF-ExecuteQryFLTRTDefn-Req-IO-MSG.xsd	872
2.17.2. CF-ExecuteQryFLTRTDefn-Res-Full-MSG.xsd	879
<b>2.18. ModifyCFFloatRateMaint</b>	<b>894</b>
2.18.1. CF-ModifyCFFloatRateMaint-Req-Full-MSG.xsd	894
2.18.2. CF-ModifyCFFloatRateMaint-Req-IO-MSG.xsd	907
2.18.3. CF-ModifyCFFloatRateMaint-Res-Full-MSG.xsd	917
2.18.4. CF-ModifyCFFloatRateMaint-Res-PK-MSG.xsd	936
<b>2.19. ModifyCFRateCodeMaint</b>	<b>956</b>
2.19.1. CF-ModifyCFRateCodeMaint-Req-Full-MSG.xsd	956
2.19.2. CF-ModifyCFRateCodeMaint-Req-IO-MSG.xsd	968
2.19.3. CF-ModifyCFRateCodeMaint-Res-Full-MSG.xsd	977
2.19.4. CF-ModifyCFRateCodeMaint-Res-PK-MSG.xsd	994
<b>2.20. ModifyCFRateTypeDefn</b>	<b>1011</b>
2.20.1. CF-ModifyCFRateTypeDefn-Req-Full-MSG.xsd	1011
2.20.2. CF-ModifyCFRateTypeDefn-Req-IO-MSG.xsd	1021
2.20.3. CF-ModifyCFRateTypeDefn-Res-Full-MSG.xsd	1029
2.20.4. CF-ModifyCFRateTypeDefn-Res-PK-MSG.xsd	1044
<b>2.21. ModifyFLTRTDefn</b>	<b>1059</b>
2.21.1. CF-ModifyFLTRTDefn-Req-Full-MSG.xsd	1059
2.21.2. CF-ModifyFLTRTDefn-Req-IO-MSG.xsd	1072
2.21.3. CF-ModifyFLTRTDefn-Res-Full-MSG.xsd	1083
2.21.4. CF-ModifyFLTRTDefn-Res-PK-MSG.xsd	1097
<b>2.22. ModifyFloatRateMaint</b>	<b>1122</b>
2.22.1. CF-ModifyFloatRateMaint-Req-Full-MSG.xsd	1122
2.22.2. CF-ModifyFloatRateMaint-Req-IO-MSG.xsd	1138
2.22.3. CF-ModifyFloatRateMaint-Res-Full-MSG.xsd	1153
2.22.4. CF-ModifyFloatRateMaint-Res-PK-MSG.xsd	1171
<b>2.23. QueryCFFloatRateMaint</b>	<b>1188</b>
2.23.1. CF-QueryCFFloatRateMaint-Req-IO-MSG.xsd	1188

2.23.2. CF-QueryCFFloatRateMaint-Res-Full-MSG.xsd	1195
<b>2.24. QueryCFRateCodeMaint</b>	<b>1211</b>
2.24.1. CF-QueryCFRateCodeMaint-Req-IO-MSG.xsd	1211
2.24.2. CF-QueryCFRateCodeMaint-Res-Full-MSG.xsd	1217
<b>2.25. QueryCFRateTypeDefn</b>	<b>1231</b>
2.25.1. CF-QueryCFRateTypeDefn-Req-IO-MSG.xsd	1231
2.25.2. CF-QueryCFRateTypeDefn-Res-Full-MSG.xsd	1237
<b>2.26. QueryFloatRateMaint</b>	<b>1250</b>
2.26.1. CF-QueryFloatRateMaint-Req-IO-MSG.xsd	1250
2.26.2. CF-QueryFloatRateMaint-Res-Full-MSG.xsd	1257
<b>2.27. ReopenFloatRateMaint</b>	<b>1276</b>
2.27.1. CF-ReopenFloatRateMaint-Req-Full-MSG.xsd	1276
2.27.2. CF-ReopenFloatRateMaint-Req-IO-MSG.xsd	1292
2.27.3. CF-ReopenFloatRateMaint-Res-Full-MSG.xsd	1299
2.27.4. CF-ReopenFloatRateMaint-Res-PK-MSG.xsd	1317

# 1.BACKGROUND

Integration of different applications and solutions is a key area in today's systems. A variety of specialized applications deployed on disparate platforms and using different infrastructure need to be able to communicate and integrate seamlessly with FLEXCUBE UBS in order to exchange data. The FLEXCUBE UBS Integration Gateway (referred to as Gateway) will cater to these integration needs.

The integration needs supported by the Gateway can be broadly categorized from the perspective of the Gateway as follows:

**1. Inbound application integration** – used when any external system needs to add, modify or query information within FLEXCUBE UBS

**2. Outbound application integration**– used when any external system needs to be notified of the various events that occur within FLEXCUBE UBS

The following sections provide detailed XSD documentation of all operations available in FCUBSCFService of Core-Module

## 2.FCUBSCFService

ICCF Service|CCF Service

### 2.1.AuthCFFloatRateMaint

Authorisation of Flostrate maintenance

#### 2.1.1.CF-AuthCFFloatRateMaint-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Cftm-Rate-Master-Full*

*RATECODE*

*RATECODEDESCRIPTION*

*TENORCODE*

*TENORCODEDESCRIPTION*

*CCYCODE*

*CCYNAME*

*EFFECTIVEDATE*

*RATESOURCE*

*RATESOURCEDESCRIPTION*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

CHECKERDTSTAMP  
 MODNO  
 AUTHSTAT  
 RECSTAT  
 ONCEAUTH  
 Cftm-Rate-Detail  
     RATETYPE  
     RATETYPEDESCRIPTION  
     INTERESTRATE  
 UDFDETAILS  
     FUNCTIONID  
     FIELD\_NAME  
     DATATYPE  
     FIELD\_VALUE  
     VAL\_TYPE

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true



**SERVICE**

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**OPERATION**

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description
-----------	-------------

Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

[TOP](#)

## Cftm-Rate-Master-Full

Attribute	Description
Name	Cftm-Rate-Master-Full
Datatype	
Description	Includes the Authorisation of Flostrate maintenance Details.

[TOP](#)

## RATECODE

Attribute	Description				
Name	RATECODE				
Datatype	String				
Description	Specifies The Rate Code.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
Attribute	Description				
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>10</td></tr></tbody></table>	Restrictions	Description	maxLength	10
Restrictions	Description				
maxLength	10				

[TOP](#)

## RATECODEDESCRIPTION

Attribute	Description				
Name	RATECODEDESCRIPTION				
Datatype	String				
Description	Specifies The Rate Code Description.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>105</td></tr></tbody></table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

[TOP](#)

## TENORCODE

Attribute	Description
Name	TENORCODE

Datatype	String	
Description	Specifies The Tenor Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## TENORCODEDESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	TENORCODEDESCRIPTION	
Datatype	String	
Description	Specifies The Tenor Code Description.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## CCYCODE

<b>Attribute</b>	<b>Description</b>	
Name	CCYCODE	
Datatype	String	
Description	Specifies The Currency Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## CCYNAME

<b>Attribute</b>	<b>Description</b>	
Name	CCYNAME	
Datatype	String	
Description	Specifies The Currency Code Description.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## EFFECTIVEDATE

<b>Attribute</b>	<b>Description</b>	
Name	EFFECTIVEDATE	
Datatype	Date	
Description	Specifies The Effective Date.	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## RATESOURCE

<b>Attribute</b>	<b>Description</b>	
Name	RATESOURCE	
Datatype	String	
Description	Specifies The Rate Source.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## RATESOURCEDESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	RATESOURCEDESCRIPTION	
Datatype	String	
Description	Specifies The Rate Source Description.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	The User id who has booked the contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has booked the contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

**CHECKERID**

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	The User id who has authorized the booked contract	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CHECKERDTSTAMP**

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has authorized the booked contract	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Specifies The Modification Number.	
Attributes	Attribute	Description
	minOccurs	0

**AUTHSTAT**

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Specifies The Authorization Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**RECSTAT**

Attribute	Description
Name	RECSTAT

Datatype	String	
Description	Specifies The Record Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorized.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Cftm-Rate-Detail

<b>Attribute</b>	<b>Description</b>	
Name	Cftm-Rate-Detail	
Datatype		
Description	Indicates The Rate Details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## RATETYPE

<b>Attribute</b>	<b>Description</b>	
Name	RATETYPE	
Datatype	String	
Description	Specifies The Rate Type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## RATETYPEDESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	RATETYPEDESCRIPTION	
Datatype	String	
Description	Specifies The Rate Type Description.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## INTERESTRATE

<b>Attribute</b>	<b>Description</b>	
Name	INTERESTRATE	
Datatype	Number	
Description	Specifies The Interest Rate.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description	Indicates The UDF Details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## FIELD\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

[TOP](#)

## DATATYPE

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

[TOP](#)

## FIELD\_VALUE

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

[TOP](#)

## VAL\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2
	minLength	0

[TOP](#)

## 2.1.2.CF-AuthCFFloatRateMaint-Req-IO-MSG.xsd

### FCUBS\_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE\_OPERATION

SOURCE\_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

### FCUBS\_BODY

Cftm-Rate-Master-IO

RATECODE

TENORCODE

CCYCODE

EFFECTIVEDATE

MODNO

### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

### SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**UBSCOMP**

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description
-----------	-------------

Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MSGSTAT**

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

**PASSWORD**

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

**ADDL**

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

**PARAM**

Attribute	Description
-----------	-------------

Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

[TOP](#)

## Cftm-Rate-Master-IO

Attribute	Description
Name	Cftm-Rate-Master-IO
Datatype	
Description	Includes the Authorisation of Flostrate maintenance primary key Details.

[TOP](#)

## RATECODE

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description	Specifies The Rate Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)



## TENORCODE

Attribute	Description				
Name	TENORCODE				
Datatype	String				
Description	Specifies The Tenor Code.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
	Restrictions	Description			
maxLength	12				

[TOP](#)

## CCYCODE

Attribute	Description				
Name	CCYCODE				
Datatype	String				
Description	Specifies The Currency Code.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

[TOP](#)

## EFFECTIVEDATE

Attribute	Description
Name	EFFECTIVEDATE
Datatype	Date
Description	Specifies The Effective Date.

[TOP](#)

## MODNO

Attribute	Description				
Name	MODNO				
Datatype	Number				
Description	Specifies The Modification Number.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr></tbody></table>	Restrictions	Description	totalDigits	22
	Restrictions	Description			
totalDigits	22				

[TOP](#)

## 2.1.3.CF-AuthCFFloatRateMaint-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Cftm-Rate-Master-IO*

*RATECODE*

*TENORCODE*

*CCYCODE*

*EFFECTIVEDATE*

*MODNO*

*Cftm-Rate-Master-Full*

*RATECODE*

*RATECODEDESCRIPTION*

*TENORCODE*

*TENORCODEDESCRIPTION*

*CCYCODE*

*CCYNAME*

*EFFECTIVEDATE*

*RATESOURCE*

*RATESOURCEDESCRIPTION*

*MAKERID*

*MAKERDTSTAMP*

CHECKERID  
 CHECKERDTSTAMP  
 MODNO  
 AUTHSTAT  
 RECSTAT  
 ONCEAUTH  
 Cftm-Rate-Detail  
   RATETYPE  
   RATETYPEDESCRIPTION  
   INTERESTRATE  
 UDFDETAILS  
   FUNCTIONID  
   FIELD\_NAME  
   DATATYPE  
   FIELD\_VALUE  
   VAL\_TYPE  
 FCUBS\_ERROR\_RESP  
   ERROR  
   ECODE  
   EDESC  
 FCUBS\_WARNING\_RESP  
   WARNING  
   WCODE  
   WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

**MODULEID**

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

**SERVICE**

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**OPERATION**

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description
Name	ACTION

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Cftm-Rate-Master-IO

Attribute	Description
Name	Cftm-Rate-Master-IO
Datatype	
Description	Includes the Authorisation of Flostrate maintenance Primary Key Details.

[TOP](#)

## RATECODE

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description	Specifies The Rate Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10



**TENORCODE**

Attribute	Description	
Name	TENORCODE	
Datatype	String	
Description	Specifies The Tenor Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CCYCODE**

Attribute	Description	
Name	CCYCODE	
Datatype	String	
Description	Specifies The Currency Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

**EFFECTIVEDATE**

Attribute	Description	
Name	EFFECTIVEDATE	
Datatype	Date	
Description	Specifies The Effective Date.	

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Specifies The Modification Number.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

**Cftm-Rate-Master-Full**

Attribute	Description	
Name	Cftm-Rate-Master-Full	
Datatype		
Description	Includes the Authorisation of Flostrate maintenance Full Details.	

**RATECODE**

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description	Specifies The Rate Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

**RATECODEDESCRIPTION**

Attribute	Description	
Name	RATECODEDESCRIPTION	
Datatype	String	
Description	Specifies The Rate Code Description.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

**TENORCODE**

Attribute	Description	
Name	TENORCODE	
Datatype	String	
Description	Specifies The Tenor Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**TENORCODEDESCRIPTION**

Attribute	Description	
Name	TENORCODEDESCRIPTION	
Datatype	String	
Description	Specifies The Tenor Code Description.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

**CCYCODE**

Attribute	Description	
Name	CCYCODE	
Datatype	String	
Description	Specifies The Currency Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## CCYNAME

Attribute	Description	
Name	CCYNAME	
Datatype	String	
Description	Specifies The Currency Code Description.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

## EFFECTIVEDATE

Attribute	Description	
Name	EFFECTIVEDATE	
Datatype	Date	
Description	Specifies The Effective Date.	

[TOP](#)

## RATESOURCE

Attribute	Description	
Name	RATESOURCE	
Datatype	String	
Description	Specifies The Rate Source.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

## RATESOURCEDESCRIPTION

Attribute	Description	
Name	RATESOURCEDESCRIPTION	
Datatype	String	
Description	Specifies The Rate Source Description.	
Attributes	Attribute	Description
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	The User id who has booked the contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has booked the contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	The User id who has authorized the booked contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has authorized the booked contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Specifies The Modification Number.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

**AUTHSTAT**

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Specifies The Authorization Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**RECSTAT**

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Specifies The Record Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**ONCEAUTH**

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorized.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**Cftm-Rate-Detail**

Attribute	Description	
Name	Cftm-Rate-Detail	
Datatype		
Description	Indicates The Rate Details.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## RATETYPE

Attribute	Description	
Name	RATETYPE	
Datatype	String	
Description	Specifies The Rate Type.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## RATETYPEDESCRIPTION

Attribute	Description	
Name	RATETYPEDESCRIPTION	
Datatype	String	
Description	Specifies The Rate Type Description.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

## INTERESTRATE

Attribute	Description	
Name	INTERESTRATE	
Datatype	Number	
Description	Specifies The Interest Rate.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description	Indicates The UDF Details.	

Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## FIELD\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

[TOP](#)

## DATATYPE

<b>Attribute</b>	<b>Description</b>	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

[TOP](#)

## FIELD\_VALUE

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

**VAL\_TYPE**

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

**FCUBS\_ERROR\_RESP**

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**ERROR**

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

**ECODE**

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

**EDESC**

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		



## FCUBS\_WARNING\_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
	Attribute	Description			
maxOccurs	unbounded				

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.1.4.CF-AuthCFFloatRateMaint-Res-PK-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Cftm-Rate-Master-PK*

*RATECODE*

*TENORCODE*

*CCYCODE*

*EFFECTIVEDATE*

*Cftm-Rate-Master-IO*

*RATECODE*

*TENORCODE*

*CCYCODE*

*EFFECTIVEDATE*

*MODNO*

*Cftm-Rate-Master-Full*

*RATECODE*

*RATECODEDESCRIPTION*

*TENORCODE*

*TENORCODEDESCRIPTION*

*CCYCODE*

*CCYNAME*

EFFECTIVEDATE  
 RATESOURCE  
 RATESOURCEDESCRIPTION  
 MAKERID  
 MAKERDTSTAMP  
 CHECKERID  
 CHECKERDTSTAMP  
 MODNO  
 AUTHSTAT  
 RECSTAT  
 ONCEAUTH  
 Cftm-Rate-Detail  
     RATETYPE  
     RATETYPEDESCRIPTION  
     INTERESTRATE  
 UDFDETAILS  
     FUNCTIONID  
     FIELD\_NAME  
     DATATYPE  
     FIELD\_VALUE  
     VAL\_TYPE  
 FCUBS\_ERROR\_RESP  
     ERROR  
         ECODE  
         EDESC  
 FCUBS\_WARNING\_RESP  
     WARNING  
         WCODE  
         WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**UBSCOMP**

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description

Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MSGSTAT**

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

**PASSWORD**

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

**ADDL**

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

**PARAM**

Attribute	Description
-----------	-------------

Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Cftm-Rate-Master-PK

Attribute	Description
Name	Cftm-Rate-Master-PK
Datatype	
Description	Includes the Authorisation of Floatrate maintenance primary key Details.

[TOP](#)

## RATECODE

Attribute	Description
Name	RATECODE
Datatype	String
Description	Specifies The Rate Code.



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## TENORCODE

<b>Attribute</b>	<b>Description</b>	
Name	TENORCODE	
Datatype	String	
Description	Specifies The Tenor Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CCYCODE

<b>Attribute</b>	<b>Description</b>	
Name	CCYCODE	
Datatype	String	
Description	Specifies The Currency Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## EFFECTIVEDATE

<b>Attribute</b>	<b>Description</b>
Name	EFFECTIVEDATE
Datatype	Date
Description	Specifies The Effective Date.

[TOP](#)

## Cftm-Rate-Master-IO

<b>Attribute</b>	<b>Description</b>
Name	Cftm-Rate-Master-IO
Datatype	
Description	Includes the Authorisation of Floatrate maintenance IO details.

[TOP](#)

## RATECODE

<b>Attribute</b>	<b>Description</b>
Name	RATECODE
Datatype	String
Description	Specifies The Rate Code.

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## TENORCODE

<b>Attribute</b>	<b>Description</b>	
Name	TENORCODE	
Datatype	String	
Description	Specifies The Tenor Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CCYCODE

<b>Attribute</b>	<b>Description</b>	
Name	CCYCODE	
Datatype	String	
Description	Specifies The Currency Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## EFFECTIVEDATE

<b>Attribute</b>	<b>Description</b>
Name	EFFECTIVEDATE
Datatype	Date
Description	Specifies The Effective Date.

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Specifies The Modification Number.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

## Cftm-Rate-Master-Full

Attribute	Description
Name	Cftm-Rate-Master-Full
Datatype	
Description	Includes the Authorisation of Flostrate maintenance Full details.

[TOP](#)

## RATECODE

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description	Specifies The Rate Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

## RATECODEDESCRIPTION

Attribute	Description	
Name	RATECODEDESCRIPTION	
Datatype	String	
Description	Specifies The Rate Code Description.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

## TENORCODE

Attribute	Description	
Name	TENORCODE	
Datatype	String	
Description	Specifies The Tenor Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## TENORCODEDESCRIPTION

Attribute	Description	
Name	TENORCODEDESCRIPTION	
Datatype	String	
Description	Specifies The Tenor Code Description.	
Attributes	Attribute	Description
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## CCYCODE

<b>Attribute</b>	<b>Description</b>	
Name	CCYCODE	
Datatype	String	
Description	Specifies The Currency Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## CCYNAME

<b>Attribute</b>	<b>Description</b>	
Name	CCYNAME	
Datatype	String	
Description	Specifies The Currency Code Description.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## EFFECTIVEDATE

<b>Attribute</b>	<b>Description</b>	
Name	EFFECTIVEDATE	
Datatype	Date	
Description	Specifies The Effective Date.	

[TOP](#)

## RATESOURCE

<b>Attribute</b>	<b>Description</b>	
Name	RATESOURCE	
Datatype	String	
Description	Specifies The Rate Source.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## RATESOURCEDESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	RATESOURCEDESCRIPTION	

Datatype	String	
Description	Specifies The Rate Source Description.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	The User id who has booked the contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has booked the contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	The User id who has authorized the booked contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has authorized the booked contract	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Specifies The Modification Number.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Specifies The Authorization Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	Specifies The Record Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorized.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## Cftm-Rate-Detail

Attribute	Description	
Name	Cftm-Rate-Detail	
Datatype		
Description	Indicates The Rate Details.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## RATETYPE

Attribute	Description	
Name	RATETYPE	
Datatype	String	
Description	Specifies The Rate Type.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## RATETYPEDESCRIPTION

Attribute	Description	
Name	RATETYPEDESCRIPTION	
Datatype	String	
Description	Specifies The Rate Type Description.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

## INTERESTRATE

Attribute	Description	
Name	INTERESTRATE	
Datatype	Number	
Description	Specifies The Interest Rate.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## UDFDETAILS

Attribute	Description
-----------	-------------

Name	UDFDETAILS	
Datatype		
Description	Indicates The UDF Details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## FIELD\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

[TOP](#)

## DATATYPE

<b>Attribute</b>	<b>Description</b>	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

[TOP](#)

## FIELD\_VALUE

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

[TOP](#)

## VAL\_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.2.AuthCFRateCodeMaint

Authorisation of Rate Code Maintenance

### 2.2.1.CF-AuthCFRateCodeMaint-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Cftm-Rate-Code-Defn-Full*

*RATECODE*

*RATECODEDESCRIPTION*

*HOLIDAYCCY*

*PROPAGATIONACROSSBRANCHES*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

*Cftm-Tenor-Code-Defn*

*TENORCODE*

*TENORCODEDESCRIPTION*

UDFDETAILS  
 FUNCTIONID  
 FIELD\_NAME  
 DATATYPE  
 FIELD\_VALUE  
 VAL\_TYPE

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description						
Name	MSGID						
Datatype	String						
Description							
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nullable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	nullable	true
Attribute	Description						
minOccurs	0						
nullable	true						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*		
Restrictions	Description						
pattern	[a-zA-Z_0-9]*						

[TOP](#)

## CORRELID

Attribute	Description
Name	CORRELID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**OPERATION**

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTITRIPID**

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description
-----------	-------------

Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about FullRequest	



**Cftm-Rate-Code-Defn-Full**

Attribute	Description
Name	Cftm-Rate-Code-Defn-Full
Datatype	
Description	Includes the Authorisation of Rate Code Maintenance Full Details.

**RATECODE**

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description	Indicates Rate Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

**RATECODEDESCRIPTION**

Attribute	Description	
Name	RATECODEDESCRIPTION	
Datatype	String	
Description	Indicates the description of rate code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

**HOLIDAYCCY**

Attribute	Description	
Name	HOLIDAYCCY	
Datatype	String	
Description	Specifies Holiday Currency .	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

**PROPAGATIONACROSSBRANCHES**

Attribute	Description
Name	PROPAGATIONACROSSBRANCHES
Datatype	String
Description	Propagate Across Branches

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Specifies the User id who has saved the record.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates the date and time when the user has saved the record.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates the User id who has authorized the record.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has authorized the booked contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	It indicates the modification number.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	It indicates the status of the record,whether open or Closed.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorized.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Cftm-Tenor-Code-Defn

Attribute	Description	
Name	Cftm-Tenor-Code-Defn	
Datatype		
Description	Includes Tenor code details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## TENORCODE

Attribute	Description	
Name	TENORCODE	
Datatype	String	
Description	Indicates the tenor code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

## TENORCODEDESCRIPTION

Attribute	Description	
Name	TENORCODEDESCRIPTION	
Datatype	String	
Description	Indicates the description of tenor code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

## UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## FIELD\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

[TOP](#)

## DATATYPE

<b>Attribute</b>	<b>Description</b>	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

[TOP](#)

## FIELD\_VALUE

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

[TOP](#)

## VAL\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

[TOP](#)

## 2.2.2.CF-AuthCFRateCodeMaint-Req-IO-MSG.xsd

### FCUBS\_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE\_OPERATION

SOURCE\_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

### FCUBS\_BODY

Cftm-Rate-Code-Defn-IO

RATECODE

MODNO

### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

### SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

### UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		



Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

[TOP](#)

## Cftm-Rate-Code-Defn-IO

Attribute	Description
Name	Cftm-Rate-Code-Defn-IO
Datatype	
Description	Includes the Authorisation of Rate Code Maintenance primary key details.

[TOP](#)

## RATECODE

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description	Indicates Rate Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## MODNO

Attribute	Description
-----------	-------------

Name	MODNO	
Datatype	Number	
Description	indicates the modification number.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

## 2.2.3.CF-AuthCFRateCodeMaint-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Cftm-Rate-Code-Defn-IO*

*RATECODE*

*MODNO*

*Cftm-Rate-Code-Defn-Full*

*RATECODE*

*RATECODEDESCRIPTION*

*HOLIDAYCCY*

*PROPAGATIONACROSSBRANCHES*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

*Cftm-Tenor-Code-Defn*

*TENORCODE*

TENORCODEDESCRIPTION  
 UDFDETAILS  
 FUNCTIONID  
 FIELD\_NAME  
 DATATYPE  
 FIELD\_VALUE  
 VAL\_TYPE  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true



**SERVICE**

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**OPERATION**

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description
-----------	-------------

Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Cftm-Rate-Code-Defn-IO

Attribute	Description
Name	Cftm-Rate-Code-Defn-IO
Datatype	
Description	Includes the Authorisation of Rate Code Maintenance IO details.

[TOP](#)

## RATECODE

Attribute	Description				
Name	RATECODE				
Datatype	String				
Description	Indicates Rate Code.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>10</td></tr></tbody></table>	Restrictions	Description	maxLength	10
	Restrictions	Description			
maxLength	10				

[TOP](#)

## MODNO

Attribute	Description				
Name	MODNO				
Datatype	Number				
Description	indicates the modification number.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

## Cftm-Rate-Code-Defn-Full

Attribute	Description
Name	Cftm-Rate-Code-Defn-Full
Datatype	
Description	Includes the Authorisation of Rate Code Maintenance Full Details.

[TOP](#)

## RATECODE

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description	Indicates Rate Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## RATECODEDESCRIPTION

Attribute	Description	
Name	RATECODEDESCRIPTION	
Datatype	String	
Description	Indicates the description of rate code	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## HOLIDAYCCY

Attribute	Description	
Name	HOLIDAYCCY	
Datatype	String	
Description	Specifies Holiday Currency .	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## PROPAGATIONACROSSBRANCHES

Attribute	Description
Name	PROPAGATIONACROSSBRANCHES

Datatype	String	
Description	Propagate Across Branches	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Specifies the User id who has saved the record.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates the date and time when the user has saved the record.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates the User id who has authorized the record.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has authorized the booked contract	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	indicates the modification number.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	It indicates the status of the record,whether open or Closed.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorized.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Cftm-Tenor-Code-Defn

<b>Attribute</b>	<b>Description</b>	
Name	Cftm-Tenor-Code-Defn	
Datatype		
Description	Includes Tenor code details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## TENORCODE

<b>Attribute</b>	<b>Description</b>	
Name	TENORCODE	
Datatype	String	
Description	Indicates the tenor code	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## TENORCODEDESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	TENORCODEDESCRIPTION	
Datatype	String	
Description	Indicates the description of tenor code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FUNCTIONID



Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## FIELD\_NAME

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

[TOP](#)

## DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

## FIELD\_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

[TOP](#)

## VAL\_TYPE

Attribute	Description
-----------	-------------

Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2
	minLength	0

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description
Name	FCUBS_WARNING_RESP
Datatype	
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

<b>Attribute</b>	<b>Description</b>	
Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## WCODE

<b>Attribute</b>	<b>Description</b>
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

<b>Attribute</b>	<b>Description</b>
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.2.4.CF-AuthCFRateCodeMaint-Res-PK-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Cftm-Rate-Code-Defn-PK*

*RATECODE*

*Cftm-Rate-Code-Defn-IO*

*RATECODE*

*MODNO*

*Cftm-Rate-Code-Defn-Full*

*RATECODE*

*RATECODEDESCRIPTION*

*HOLIDAYCCY*

*PROPAGATIONACROSSBRANCHES*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

*Cftm-Tenor-Code-Defn*  
 TENORCODE  
 TENORCODEDESCRIPTION  
 UDFDETAILS  
 FUNCTIONID  
 FIELD\_NAME  
 DATATYPE  
 FIELD\_VALUE  
 VAL\_TYPE  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description
Name	MSGID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*



## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+!]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Cftm-Rate-Code-Defn-PK

Attribute	Description
Name	Cftm-Rate-Code-Defn-PK
Datatype	
Description	Includes the Authorisation of Rate Code Maintenance primary key Details.

[TOP](#)

## RATECODE

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description	Indicates Rate Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

## Cftm-Rate-Code-Defn-IO

Attribute	Description
Name	Cftm-Rate-Code-Defn-IO
Datatype	
Description	Includes the Authorisation of Rate Code Maintenance IO details.

**RATECODE**

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description	Indicates Rate Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates the modification number.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

**Cftm-Rate-Code-Defn-Full**

Attribute	Description
Name	Cftm-Rate-Code-Defn-Full
Datatype	
Description	Includes the Authorisation of Rate Code Maintenance Full Details.

**RATECODE**

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description	Indicates Rate Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

**RATECODEDESCRIPTION**

Attribute	Description
Name	RATECODEDESCRIPTION
Datatype	String
Description	Indicates the description of rate code

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## HOLIDAYCCY

<b>Attribute</b>	<b>Description</b>	
Name	HOLIDAYCCY	
Datatype	String	
Description	Specifies Holiday Currency .	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## PROPAGATIONACROSSBRANCHES

<b>Attribute</b>	<b>Description</b>	
Name	PROPAGATIONACROSSBRANCHES	
Datatype	String	
Description	Propagate Across Branches	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Specifies the User id who has saved the record.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates the date and time when the user has saved the record.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates the User id who has authorized the record.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has authorized the booked contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates the modification number.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

**RECSTAT**

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	It indicates the status of the record,whether open or Closed.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**ONCEAUTH**

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorized.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**Cftm-Tenor-Code-Defn**

Attribute	Description	
Name	Cftm-Tenor-Code-Defn	
Datatype		
Description	Includes Tenor code details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**TENORCODE**

Attribute	Description	
Name	TENORCODE	
Datatype	String	
Description	Indicates the tenor code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

**TENORCODEDESCRIPTION**

Attribute	Description
-----------	-------------

Name	TENORCODEDESCRIPTION	
Datatype	String	
Description	Indicates the description of tenor code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## FIELD\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

[TOP](#)

## DATATYPE

<b>Attribute</b>	<b>Description</b>	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

## FIELD\_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

[TOP](#)

## VAL\_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)



## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
	Attribute	Description			
maxOccurs	unbounded				

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.3.AuthCFRateTypeDefn

Authorisation of Rate Type Maintenance

### 2.3.1.CF-AuthCFRateTypeDefn-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Cftm-Rate-Type-Defn-Full*

*RATETYPE*

*RATETYPEDESCRIPTION*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

*UDFDETAILS*

*FUNCTIONID*

*FIELD\_NAME*

*DATATYPE*

*FIELD\_VALUE*

VAL\_TYPE

FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description
-----------	-------------

Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

[TOP](#)

## Cftm-Rate-Type-Defn-Full

Attribute	Description
-----------	-------------

Name	Cftm-Rate-Type-Defn-Full
Datatype	
Description	Includes the Authorisation of Rate Type Maintenance Full Details.

[TOP](#)

## RATETYPE

Attribute	Description	
Name	RATETYPE	
Datatype	String	
Description	Indicates The Rate Type.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## RATETYPEDESCRIPTION

Attribute	Description	
Name	RATETYPEDESCRIPTION	
Datatype	String	
Description	Indicates The Rate Type Description.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

## MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	The User Id who has created\last modified the Rate Type Definition details.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates Date and Stamp when the user hascreated\last modified the Rate Type Definition details.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25



**CHECKERID**

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	The User Id who has Authorized the creation\modification of Rate Type Definition details.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CHECKERDTSTAMP**

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates Date and Stamp when the user has Authorized the creation\ modification of Rate Type Definition details.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number i.e. the number of times Rate Type Definition detail has been modified.	
Attributes	Attribute	Description
	minOccurs	0

**AUTHSTAT**

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status. A - Authorized U - Unauthorized	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**RECSTAT**

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Indicates the Record Status O - Open C - Close	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**ONCEAUTH**

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates whether Rate Type Definition detail has been Authorized atleast Once.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**UDFDETAILS**

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**FIELD\_NAME**

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

**DATATYPE**

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

**FIELD\_VALUE**

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

**VAL\_TYPE**

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

## 2.3.2.CF-AuthCFRateTypeDefn-Req-IO-MSG.xsd

### FCUBS\_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE\_OPERATION

SOURCE\_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

### FCUBS\_BODY

*Cftm-Rate-Type-Defn-IO*

RATETYPE

MODNO

### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

### SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

### UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		

Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		



Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

[TOP](#)

## Cftm-Rate-Type-Defn-IO

Attribute	Description
Name	Cftm-Rate-Type-Defn-IO
Datatype	
Description	Includes the Authorisation of Rate Type Maintenance IO Details.

[TOP](#)

## RATETYPE

Attribute	Description	
Name	RATETYPE	
Datatype	String	
Description	Indicates The Rate Type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MODNO

Attribute	Description
-----------	-------------

Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number i.e. the number of times Rate Type Definition has been modified.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

### 2.3.3.CF-AuthCFRateTypeDefn-Res-Full-MSG.xsd

*FCUBS\_HEADER*  
*SOURCE*  
*UBSCOMP*  
*MSGID*  
*CORRELID*  
*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*CHOICE*  
*Cftm-Rate-Type-Defn-IO*  
*RATETYPE*  
*MODNO*  
*Cftm-Rate-Type-Defn-Full*  
*RATETYPE*  
*RATETYPEDESCRIPTION*  
*MAKERID*  
*MAKERDTSTAMP*  
*CHECKERID*  
*CHECKERDTSTAMP*  
*MODNO*  
*AUTHSTAT*  
*RECSTAT*  
*ONCEAUTH*  
*UDFDETAILS*  
*FUNCTIONID*  
*FIELD\_NAME*  
*DATATYPE*

FIELD\_VALUE  
 VAL\_TYPE  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

**MODULEID**

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

**SERVICE**

Attribute	Description	
Name	SERVICE	
Datatype	String	

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

**PASSWORD**

Attribute		Description
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

**ADDL**

Attribute		Description
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

**PARAM**

Attribute		Description
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**NAME**

Attribute		Description
Name	NAME	
Datatype	String	
Description		

**VALUE**

Attribute		Description
Name	VALUE	
Datatype	String	
Description		



## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Cftm-Rate-Type-Defn-IO

Attribute	Description
Name	Cftm-Rate-Type-Defn-IO
Datatype	
Description	Includes the Authorisation of Rate Type Maintenance IO details.

[TOP](#)

## RATETYPE

Attribute	Description				
Name	RATETYPE				
Datatype	String				
Description	Indicates The Rate Type.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

[TOP](#)

## MODNO

Attribute	Description				
Name	MODNO				
Datatype	Number				
Description	Indicates Modification Number i.e. the number of times Rate Type Definition has been modified.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr></tbody></table>	Restrictions	Description	totalDigits	22
Restrictions	Description				
totalDigits	22				

[TOP](#)

## Cftm-Rate-Type-Defn-Full

Attribute	Description
Name	Cftm-Rate-Type-Defn-Full

Datatype	
Description	Includes the Authorisation of Rate Type Maintenance Full details.

[TOP](#)

## RATETYPE

Attribute	Description	
Name	RATETYPE	
Datatype	String	
Description	Indicates The Rate Type.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## RATETYPEDESCRIPTION

Attribute	Description	
Name	RATETYPEDESCRIPTION	
Datatype	String	
Description	Indicates The Rate Type Description.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

## MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	The User Id who has created\last modified the Rate Type Definition details.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates Date and Stamp when the user hascreated\last modified the Rate Type Definition details.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

**CHECKERID**

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	The User Id who has Authorized the creation\modification of Rate Type Definition details.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CHECKERDTSTAMP**

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates Date and Stamp when the user has Authorized the creation\ modification of Rate Type Definition details.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number i.e. the number of times Rate Type Definition has been modified.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

**AUTHSTAT**

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status.  A - Authorized U - Unauthorized	
Attributes	Attribute	Description
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	Indicates the Record Status O - Open C - Close	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates whether Rate Type Definition detail has been Authorized atleast Once.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## FIELD\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

[TOP](#)

## DATATYPE

<b>Attribute</b>	<b>Description</b>	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

[TOP](#)

## FIELD\_VALUE

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

[TOP](#)

## VAL\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2
	minLength	0

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
-----------	-------------	--

Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.3.4.CF-AuthCFRateTypeDefn-Res-PK-MSG.xsd

*FCUBS\_HEADER*  
*SOURCE*  
*UBSCOMP*  
*MSGID*  
*CORRELID*  
*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*CHOICE*  
*Cftm-Rate-Type-Defn-PK*  
*RATETYPE*  
*Cftm-Rate-Type-Defn-IO*  
*RATETYPE*  
*MODNO*  
*Cftm-Rate-Type-Defn-Full*  
*RATETYPE*  
*RATETYPEDESCRIPTION*  
*MAKERID*  
*MAKERDTSTAMP*  
*CHECKERID*  
*CHECKERDTSTAMP*  
*MODNO*  
*AUTHSTAT*  
*RECSTAT*  
*ONCEAUTH*  
*UDFDETAILS*  
*FUNCTIONID*



FIELD\_NAME  
 DATATYPE  
 FIELD\_VALUE  
 VAL\_TYPE  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description						
Name	MSGID						
Datatype	String						
Description							
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

## DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	

Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Cftm-Rate-Type-Defn-PK

Attribute	Description
Name	Cftm-Rate-Type-Defn-PK
Datatype	
Description	Includes the Authorisation of Rate Type Maintenance Primary Key details.

[TOP](#)

## RATETYPE

Attribute	Description	
Name	RATETYPE	
Datatype	String	
Description	Indicates The Rate Type.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## Cftm-Rate-Type-Defn-IO

Attribute	Description
Name	Cftm-Rate-Type-Defn-IO
Datatype	
Description	Includes the Authorisation of Rate Type Maintenance IO details.

[TOP](#)

## RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates The Rate Type.

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number i.e. the number of times Rate Type Definition has been modified.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

## Cftm-Rate-Type-Defn-Full

<b>Attribute</b>	<b>Description</b>
Name	Cftm-Rate-Type-Defn-Full
Datatype	
Description	Includes the Authorisation of Rate Type Maintenance Full details.

[TOP](#)

## RATETYPE

<b>Attribute</b>	<b>Description</b>	
Name	RATETYPE	
Datatype	String	
Description	Indicates The Rate Type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## RATETYPEDESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	RATETYPEDESCRIPTION	
Datatype	String	
Description	Indicates The Rate Type Description.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## MAKERID

Attribute	Description				
Name	MAKERID				
Datatype	String				
Description	The User Id who has created\last modified the Rate Type Definition details.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
	Restrictions	Description			
maxLength	12				

[TOP](#)

## MAKERDTSTAMP

Attribute	Description				
Name	MAKERDTSTAMP				
Datatype	String				
Description	Indicates Date and Stamp when the user has created\last modified the Rate Type Definition details.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>25</td></tr></tbody></table>	Restrictions	Description	maxLength	25
	Restrictions	Description			
maxLength	25				

[TOP](#)

## CHECKERID

Attribute	Description				
Name	CHECKERID				
Datatype	String				
Description	The User Id who has Authorized the creation\modification of Rate Type Definition details.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
	Restrictions	Description			
maxLength	12				

[TOP](#)

## CHECKERDTSTAMP

Attribute	Description				
Name	CHECKERDTSTAMP				
Datatype	String				
Description	Indicates Date and Stamp when the user has Authorized the creation\ modification of Rate Type Definition details.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>25</td></tr></tbody></table>	Restrictions	Description	maxLength	25
	Restrictions	Description			
maxLength	25				

[TOP](#)



## MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number i.e. the number of times Rate Type Definition has been modified.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status. A - Authorized U - Unauthorized	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Indicates the Record Status O - Open C - Close	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates whether Rate Type Definition detail has been Authorized atleast Once.	
Attributes	Attribute	Description
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## FIELD\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

[TOP](#)

## DATATYPE

<b>Attribute</b>	<b>Description</b>	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

[TOP](#)

## FIELD\_VALUE

Attribute	Description						
Name	FIELD_VALUE						
Datatype	String						
Description	Indicates the User Defined Field Value.						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></tbody></table>	Restrictions	Description	maxLength	255	minLength	0
	Restrictions	Description					
	maxLength	255					
minLength	0						

[TOP](#)

## VAL\_TYPE

Attribute	Description						
Name	VAL_TYPE						
Datatype	String						
Description	Indicates Value type.						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></tbody></table>	Restrictions	Description	maxLength	2	minLength	0
	Restrictions	Description					
	maxLength	2					
minLength	0						

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description						
Name	FCUBS_ERROR_RESP						
Datatype							
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## ERROR

Attribute	Description				
Name	ERROR				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
	Attribute	Description			
maxOccurs	unbounded				

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String

Description	
-------------	--

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
Attribute	Description						
maxOccurs	unbounded						
minOccurs	0						

[TOP](#)

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxOccurs</td> <td>unbounded</td> </tr> </tbody> </table>	Attribute	Description	maxOccurs	unbounded
Attribute	Description				
maxOccurs	unbounded				

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.4.AuthFLTRTDefn

Authorisation of Floating Rate Definition

### 2.4.1.CF-AuthFLTRTDefn-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Cftms-Rate-Code-Details-Full*

*RATECODE*

*RATEDESC*

*BRANCHCODE*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

*Cftms-Rate-Ccy-Details*

*CCYCODE*

*Cftms-Float-Rate-Master-Details*

*AMNTSLAB*

EFFECTDATE  
 BRWLENDINDCR  
 Cftms-Float-Rate-Detail-Description  
 TENORTO  
 INTRATE  
 UDFDETAILS  
 FUNCTIONID  
 FIELD\_NAME  
 DATATYPE  
 FIELD\_VALUE  
 VAL\_TYPE

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

**MODULEID**

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

**SERVICE**

Attribute	Description
Name	SERVICE
Datatype	String

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

[TOP](#)

## Cftms-Rate-Code-Details-Full

Attribute	Description
Name	Cftms-Rate-Code-Details-Full
Datatype	
Description	Includes the Authorisation of Floating Rate Definition Full details.

[TOP](#)

## RATECODE

Attribute	Description				
Name	RATECODE				
Datatype	String				
Description	Specifies The Rate Code.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>10</td></tr></tbody></table>	Restrictions	Description	maxLength	10
	Restrictions	Description			
maxLength	10				

[TOP](#)

## RATEDESC

Attribute	Description				
Name	RATEDESC				
Datatype	String				
Description	Specifies The Rate Description.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>105</td></tr></tbody></table>	Restrictions	Description	maxLength	105
	Restrictions	Description			
maxLength	105				

[TOP](#)

## BRANCHCODE

Attribute	Description				
Name	BRANCHCODE				
Datatype	String				
Description	Specifies The Branch Code.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

**MAKERID**

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	The User id who has booked the contract	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**MAKERDTSTAMP**

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has booked the contract	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

**CHECKERID**

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Specifies The Checker Identification.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CHECKERDTSTAMP**

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has authorized the booked contract	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Specifies The Modification Number.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Specifies The Authorization Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Specifies The Record Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorized.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## Cftms-Rate-Ccy-Details

Attribute	Description
Name	Cftms-Rate-Ccy-Details
Datatype	
Description	Includes Rate-Currency details

Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## CCYCODE

<b>Attribute</b>	<b>Description</b>	
Name	CCYCODE	
Datatype	String	
Description	Specifies The Currency Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## Cftms-Float-Rate-Master-Details

<b>Attribute</b>	<b>Description</b>	
Name	Cftms-Float-Rate-Master-Details	
Datatype		
Description	Includes Rate details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## AMNTSLAB

<b>Attribute</b>	<b>Description</b>	
Name	AMNTSLAB	
Datatype	Number	
Description	Specifies The Amount Slab.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## EFFECTDATE

<b>Attribute</b>	<b>Description</b>	
Name	EFFECTDATE	
Datatype	Date	
Description	Specifies The Effective Date.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## BRWLENDINDCR

<b>Attribute</b>	<b>Description</b>	
Name	BRWLENDINDCR	

Datatype	String	
Description	Specifies The Borrow Lend Indicator 1 : Borrow : B 2 : Lend : L 3 : MID : M	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	B,L,M

[TOP](#)

## Cftms-Float-Rate-Detail-Description

<b>Attribute</b>	<b>Description</b>	
Name	Cftms-Float-Rate-Detail-Description	
Datatype		
Description	Specifies The Tenor and Interest Rate Details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## TENORTO

<b>Attribute</b>	<b>Description</b>	
Name	TENORTO	
Datatype	Number	
Description	Specifies The Tenor.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## INTRATE

<b>Attribute</b>	<b>Description</b>	
Name	INTRATE	
Datatype	Number	
Description	Specifies The Interest Rate.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**FIELD\_NAME**

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

**DATATYPE**

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

**FIELD\_VALUE**

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0



## VAL\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2
	minLength	0

[TOP](#)

## 2.4.2.CF-AuthFLTRTDefn-Req-IO-MSG.xsd

### FCUBS\_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE\_OPERATION

SOURCE\_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

### FCUBS\_BODY

*Cftms-Rate-Code-Details-IO*

RATECODE

BRANCHCODE

MODNO

### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

### SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

[TOP](#)

## Cftms-Rate-Code-Details-IO

Attribute	Description
Name	Cftms-Rate-Code-Details-IO
Datatype	
Description	Includes the Authorisation of Floating Rate Definition IO Details.

[TOP](#)

## RATECODE

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description	Specifies The Rate Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## BRANCHCODE

Attribute	Description
-----------	-------------

Name	BRANCHCODE	
Datatype	String	
Description	Specifies The Branch Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Specifies The Modification Number.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)



### 2.4.3.CF-AuthFLTRTDefn-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Cftms-Rate-Code-Details-PK*

*RATECODE*

*BRANCHCODE*

*Cftms-Rate-Code-Details-IO*

*RATECODE*

*RATEDESC*

*BRANCHCODE*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

*Cftms-Rate-Ccy-Details*

*CCYCODE*

*Cftms-Float-Rate-Master-Details*

AMNTSLAB  
EFFECTDATE  
BRWLENDINDCR  
*Cftms-Float-Rate-Detail-Description*

TENORTO

INTRATE

TENORTO

INTRATE

AMNTSLAB  
EFFECTDATE  
BRWLENDINDCR  
*Cftms-Float-Rate-Detail-Description*

TENORTO

INTRATE

TENORTO

INTRATE

UDFDETAILS

FUNCTIONID

FIELD\_NAME

DATATYPE

FIELD\_VALUE

VAL\_TYPE

*Cftms-Rate-Code-Details-Full*

RATECODE

RATEDESC

BRANCHCODE

MAKERID

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

*Cftms-Rate-Ccy-Details*

CCYCODE

*Cftms-Float-Rate-Master-Details*

AMNTSLAB

EFFECTDATE

BRWLENDINDCR

*Cftms-Float-Rate-Detail-Description*

TENORTO

INTRATE

TENORTO

INTRATE  
 AMNTSLAB  
 EFFECTDATE  
 BRWLENDINDCR  
*Cftms-Float-Rate-Detail-Description*  
 TENORTO  
 INTRATE  
 TENORTO  
 INTRATE  
 UDFDETAILS  
 FUNCTIONID  
 FIELD\_NAME  
 DATATYPE  
 FIELD\_VALUE  
 VAL\_TYPE  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

**MODULEID**

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

**SERVICE**

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**OPERATION**

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description
Name	ACTION

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**NAME**

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)**VALUE**

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

[TOP](#)**CHOICE**

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)**Cftms-Rate-Code-Details-PK**

Attribute	Description
Name	Cftms-Rate-Code-Details-PK
Datatype	
Description	Includes the Authorisation of Floating Rate Definition Primary Key Details.

[TOP](#)**RATECODE**

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description	Specifies The Rate Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16



**BRANCHCODE**

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description	Specifies The Branch Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

**Cftms-Rate-Code-Details-IO**

Attribute	Description	
Name	Cftms-Rate-Code-Details-IO	
Datatype		
Description	Includes the Authorisation of Floating Rate Definition IO Details.	

**RATECODE**

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description	Specifies The Rate Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

**RATEDESC**

Attribute	Description	
Name	RATEDESC	
Datatype	String	
Description	Specifies The Rate Description.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

**BRANCHCODE**

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description	Specifies The Branch Code.	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	The User id who has booked the contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has booked the contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	The User id who has authorized the booked contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has authorized the booked contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Specifies The Modification Number.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Specifies The Authorization Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	Specifies The Record Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorized.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Cftms-Rate-Ccy-Details

Attribute	Description	
Name	Cftms-Rate-Ccy-Details	
Datatype		
Description	Includes Rate-Currency details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## CCYCODE

Attribute	Description	
Name	CCYCODE	
Datatype	String	
Description	Specifies The Currency Code.	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## Cftms-Float-Rate-Master-Details

Attribute	Description	
Name	Cftms-Float-Rate-Master-Details	
Datatype		
Description	Includes Rate details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## AMNTSLAB

Attribute	Description	
Name	AMNTSLAB	
Datatype	Number	
Description	Specifies The Amount Slab.	
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

## EFFECTDATE

Attribute	Description	
Name	EFFECTDATE	
Datatype	Date	
Description	Specifies The Effective Date.	
Attributes	Attribute	Description
	minOccurs	1

**BRWLENDINDCR**

Attribute	Description	
Name	BRWLENDINDCR	
Datatype	String	
Description	Specifies The Borrow Lend Indicator 1 : Borrow : B 2 : Lend : L 3 : MID : M	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	B,L,M

**Cftms-Float-Rate-Detail-Description**

Attribute	Description	
Name	Cftms-Float-Rate-Detail-Description	
Datatype		
Description	Specifies The Tenor and Interest Rate Details.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**TENORTO**

Attribute	Description	
Name	TENORTO	
Datatype	Number	
Description	Specifies The Tenor.	
Attributes	Attribute	Description
	minOccurs	0

**INTRATE**

Attribute	Description	
Name	INTRATE	
Datatype	Number	
Description	Specifies The Interest Rate.	
Attributes	Attribute	Description
	minOccurs	0

**TENORTO**

Attribute	Description
-----------	-------------

Name	TENORTO	
Datatype	Number	
Description	Specifies The Tenor.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## INTRATE

<b>Attribute</b>	<b>Description</b>	
Name	INTRATE	
Datatype	Number	
Description	Specifies The Interest Rate.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AMNTSLAB

<b>Attribute</b>	<b>Description</b>	
Name	AMNTSLAB	
Datatype	Number	
Description	Specifies The Amount Slab.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## EFFECTDATE

<b>Attribute</b>	<b>Description</b>	
Name	EFFECTDATE	
Datatype	Date	
Description	Specifies The Effective Date.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## BRWLENDINDCR

<b>Attribute</b>	<b>Description</b>	
Name	BRWLENDINDCR	
Datatype	String	
Description	Specifies The Borrow Lend Indicator	
	1 : Borrow : B	
	2 : Lend : L	
		3 : MID : M
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	B,L,M

**Cftms-Float-Rate-Detail-Description**

Attribute	Description	
Name	Cftms-Float-Rate-Detail-Description	
Datatype		
Description	Specifies The Tenor and Interest Rate Details.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**TENORTO**

Attribute	Description	
Name	TENORTO	
Datatype	Number	
Description	Specifies The Tenor.	
Attributes	Attribute	Description
	minOccurs	0

**INTRATE**

Attribute	Description	
Name	INTRATE	
Datatype	Number	
Description	Specifies The Interest Rate.	
Attributes	Attribute	Description
	minOccurs	0

**TENORTO**

Attribute	Description	
Name	TENORTO	
Datatype	Number	
Description	Specifies The Tenor.	
Attributes	Attribute	Description
	minOccurs	0

**INTRATE**

Attribute	Description	
Name	INTRATE	
Datatype	Number	
Description	Specifies The Interest Rate.	
Attributes	Attribute	Description
	minOccurs	0

**UDFDETAILS**

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**FIELD\_NAME**

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

**DATATYPE**

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

**FIELD\_VALUE**

Attribute	Description
-----------	-------------



Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

[TOP](#)

## VAL\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2
	minLength	0

[TOP](#)

## Cftms-Rate-Code-Details-Full

<b>Attribute</b>	<b>Description</b>
Name	Cftms-Rate-Code-Details-Full
Datatype	
Description	Includes the Authorisation of Floating Rate Definition Full Details.

[TOP](#)

## RATECODE

<b>Attribute</b>	<b>Description</b>	
Name	RATECODE	
Datatype	String	
Description	Specifies The Rate Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## RATEDESC

<b>Attribute</b>	<b>Description</b>	
Name	RATEDESC	
Datatype	String	
Description	Specifies The Rate Description.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## BRANCHCODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCHCODE	
Datatype	String	
Description	Specifies The Branch Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	The User id who has booked the contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has booked the contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	The User id who has authorized the booked contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

**CHECKERDTSTAMP**

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has authorized the booked contract	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Specifies The Modification Number.	
Attributes	Attribute	Description
	minOccurs	0

**AUTHSTAT**

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Specifies The Authorization Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**RECSTAT**

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Specifies The Record Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**ONCEAUTH**

Attribute	Description
Name	ONCEAUTH

Datatype	String	
Description	Indicates Once Authorized.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

### Cftms-Rate-Ccy-Details

<b>Attribute</b>	<b>Description</b>	
Name	Cftms-Rate-Ccy-Details	
Datatype		
Description	Includes Rate-Currency details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

### CCYCODE

<b>Attribute</b>	<b>Description</b>	
Name	CCYCODE	
Datatype	String	
Description	Specifies The Currency Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

### Cftms-Float-Rate-Master-Details

<b>Attribute</b>	<b>Description</b>	
Name	Cftms-Float-Rate-Master-Details	
Datatype		
Description	Includes Rate details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

### AMNTSLAB

<b>Attribute</b>	<b>Description</b>	
Name	AMNTSLAB	
Datatype	Number	
Description	Specifies The Amount Slab.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

**EFFECTDATE**

Attribute	Description	
Name	EFFECTDATE	
Datatype	Date	
Description	Specifies The Effective Date.	
Attributes	Attribute	Description
	minOccurs	1

**BRWLENDINDCR**

Attribute	Description	
Name	BRWLENDINDCR	
Datatype	String	
Description	Specifies The Borrow Lend Indicator 1 : Borrow : B 2 : Lend : L 3 : MID : M	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	B,L,M

**Cftms-Float-Rate-Detail-Description**

Attribute	Description	
Name	Cftms-Float-Rate-Detail-Description	
Datatype		
Description	Specifies The Tenor and Interest Rate Details.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**TENORTO**

Attribute	Description	
Name	TENORTO	
Datatype	Number	
Description	Specifies The Tenor.	
Attributes	Attribute	Description
	minOccurs	0

**INTRATE**

Attribute	Description
-----------	-------------

Name	INTRATE	
Datatype	Number	
Description	Specifies The Interest Rate.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TENORTO

<b>Attribute</b>	<b>Description</b>	
Name	TENORTO	
Datatype	Number	
Description	Specifies The Tenor.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## INTRATE

<b>Attribute</b>	<b>Description</b>	
Name	INTRATE	
Datatype	Number	
Description	Specifies The Interest Rate.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AMNTSLAB

<b>Attribute</b>	<b>Description</b>	
Name	AMNTSLAB	
Datatype	Number	
Description	Specifies The Amount Slab.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## EFFECTDATE

<b>Attribute</b>	<b>Description</b>	
Name	EFFECTDATE	
Datatype	Date	
Description	Specifies The Effective Date.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## BRWLENDINDCR

<b>Attribute</b>	<b>Description</b>	
Name	BRWLENDINDCR	
Datatype	String	

Description	Specifies The Borrow Lend Indicator 1 : Borrow : B 2 : Lend : L 3 : MID : M	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	B,L,M

[TOP](#)

## Cftms-Float-Rate-Detail-Description

<b>Attribute</b>	<b>Description</b>	
Name	Cftms-Float-Rate-Detail-Description	
Datatype		
Description	Specifies The Tenor and Interest Rate Details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## TENORTO

<b>Attribute</b>	<b>Description</b>	
Name	TENORTO	
Datatype	Number	
Description	Specifies The Tenor.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## INTRATE

<b>Attribute</b>	<b>Description</b>	
Name	INTRATE	
Datatype	Number	
Description	Specifies The Interest Rate.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TENORTO

<b>Attribute</b>	<b>Description</b>	
Name	TENORTO	
Datatype	Number	
Description	Specifies The Tenor.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## INTRATE

Attribute	Description				
Name	INTRATE				
Datatype	Number				
Description	Specifies The Interest Rate.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## UDFDETAILS

Attribute	Description						
Name	UDFDETAILS						
Datatype							
Description	Includes User Defined Fields details						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

## FIELD\_NAME

Attribute	Description						
Name	FIELD_NAME						
Datatype	String						
Description	Indicates the User Defined Field Name.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	105	minLength	1
	Restrictions	Description					
	maxLength	105					
minLength	1						

[TOP](#)

## DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

[TOP](#)

## FIELD\_VALUE

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

[TOP](#)

## VAL\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2
	minLength	0

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)**ECODE**

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)**EDESC**

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)**FCUBS\_WARNING\_RESP**

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**WARNING**

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)**WCODE**

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)**WDESC**

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.4.4.CF-AuthFLTRTDefn-Res-PK-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Cftms-Rate-Code-Details-PK*

*RATECODE*

*BRANCHCODE*

*Cftms-Rate-Code-Details-IO*

*RATECODE*

*BRANCHCODE*

*MODNO*

*Cftms-Rate-Code-Details-Full*

*RATECODE*

*RATEDESC*

*BRANCHCODE*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

ONCEAUTH

*Cftms-Rate-Ccy-Details*

CCYCODE

*Cftms-Float-Rate-Master-Details*

AMNTSLAB

EFFECTDATE

BRWLENDINDCR

*Cftms-Float-Rate-Detail-Description*

TENORTO

INTRATE

UDFDETAILS

FUNCTIONID

FIELD\_NAME

DATATYPE

FIELD\_VALUE

VAL\_TYPE

FCUBS\_ERROR\_RESP

ERROR

ECODE

EDESC

FCUBS\_WARNING\_RESP

WARNING

WCODE

WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

**MODULEID**

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

**SERVICE**

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**OPERATION**

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description
Name	ACTION

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0



[TOP](#)**NAME**

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)**VALUE**

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

[TOP](#)**CHOICE**

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)**Cftms-Rate-Code-Details-PK**

Attribute	Description
Name	Cftms-Rate-Code-Details-PK
Datatype	
Description	Includes the Authorisation of Floating Rate Definition Primary Key Details.

[TOP](#)**RATECODE**

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description	Specifies The Rate Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

**BRANCHCODE**

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description	Specifies The Branch Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

**Cftms-Rate-Code-Details-IO**

Attribute	Description	
Name	Cftms-Rate-Code-Details-IO	
Datatype		
Description	Includes the Authorisation of Floating Rate Definition IO Details.	

**RATECODE**

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description	Specifies The Rate Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

**BRANCHCODE**

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description	Specifies The Branch Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Specifies The Modification Number.	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

## Cftms-Rate-Code-Details-Full

<b>Attribute</b>	<b>Description</b>
Name	Cftms-Rate-Code-Details-Full
Datatype	
Description	Includes the Authorisation of Floating Rate Definition Full Details.

[TOP](#)

## RATECODE

<b>Attribute</b>	<b>Description</b>	
Name	RATECODE	
Datatype	String	
Description	Specifies The Rate Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## RATEDESC

<b>Attribute</b>	<b>Description</b>	
Name	RATEDESC	
Datatype	String	
Description	Specifies The Rate Description.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## BRANCHCODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCHCODE	
Datatype	String	
Description	Specifies The Branch Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	The User id who has booked the contract	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has booked the contract	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

## CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Specifies The Checker Identification.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has authorized the booked contract	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

## MODNO

Attribute	Description
Name	MODNO

Datatype	Number	
Description	Specifies The Modification Number.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Specifies The Authorization Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	Specifies The Record Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorized.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Cftms-Rate-Ccy-Details

<b>Attribute</b>	<b>Description</b>
Name	Cftms-Rate-Ccy-Details
Datatype	
Description	Includes Rate-Currency details

Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## CCYCODE

<b>Attribute</b>	<b>Description</b>	
Name	CCYCODE	
Datatype	String	
Description	Specifies The Currency Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## Cftms-Float-Rate-Master-Details

<b>Attribute</b>	<b>Description</b>	
Name	Cftms-Float-Rate-Master-Details	
Datatype		
Description	Includes Rate details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## AMNTSLAB

<b>Attribute</b>	<b>Description</b>	
Name	AMNTSLAB	
Datatype	Number	
Description	Specifies The Amount Slab.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## EFFECTDATE

<b>Attribute</b>	<b>Description</b>	
Name	EFFECTDATE	
Datatype	Date	
Description	Specifies The Effective Date.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## BRWLENDINDCR

<b>Attribute</b>	<b>Description</b>	
Name	BRWLENDINDCR	

Datatype	String	
Description	Specifies The Borrow Lend Indicator 1 : Borrow : B 2 : Lend : L 3 : MID : M	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	B,L,M

[TOP](#)

## Cftms-Float-Rate-Detail-Description

<b>Attribute</b>	<b>Description</b>	
Name	Cftms-Float-Rate-Detail-Description	
Datatype		
Description	Specifies The Tenor and Interest Rate Details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## TENORTO

<b>Attribute</b>	<b>Description</b>	
Name	TENORTO	
Datatype	Number	
Description	Specifies The Tenor.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## INTRATE

<b>Attribute</b>	<b>Description</b>	
Name	INTRATE	
Datatype	Number	
Description	Specifies The Interest Rate.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**FIELD\_NAME**

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

**DATATYPE**

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

**FIELD\_VALUE**

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0



## VAL\_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description	
Name	WCODE	
Datatype	String	
Description		

[TOP](#)

## WDESC

Attribute	Description	
Name	WDESC	
Datatype	String	
Description		

[TOP](#)

## 2.5.AuthorizeFloatRateMaint

AuthorizeFloatRateMaint

### 2.5.1.CF-AuthorizeFloatRateMaint-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Rate-Code-Full*

*RATE\_CODE*

*RATEDESC*

*BRANCH\_CODE*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*Rate-Ccy*

*RATE\_CODE*

*CCY\_CODE*

*BRANCH\_CODE*

*Fload-Rate*

*RATE\_CODE*  
*CCY\_CODE*  
*AMOUNT\_SLAB1*  
*EFFECTIVE\_DATE*  
*BRANCH\_CODE*  
*BORROW\_LEND\_IND*

*Ftrate-Detail*

*RATE\_CODE*  
*CCY\_CODE*  
*AMOUNT\_SLAB*  
*EFFECTIVE\_DATE*  
*BRANCH\_CODE*  
*BORROW\_LEND\_IND*  
*TENOR\_TO1*  
*INTEREST\_RATE*  
*RATECODEC*  
*CCYCODEC*  
*AMOUNTSLABC*  
*EFFECTIVEDATEC*  
*BRANCHCODEC*  
*BORROWLENDINDC*  
*TENORTOC*  
*TDMAXRATE*  
*TDPREDIFF*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		

Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		



Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

[TOP](#)

## Rate-Code-Full

<b>Attribute</b>	<b>Description</b>
Name	Rate-Code-Full
Datatype	
Description	

[TOP](#)

## RATE\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## RATEDESC

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	RATEDESC	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

**Rate-Ccy**

Attribute	Description	
Name	Rate-Ccy	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**RATE\_CODE**

Attribute	Description	
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

**CCY\_CODE**

Attribute	Description	
Name	CCY_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

**BRANCH\_CODE**

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

**Fload-Rate**

Attribute	Description
-----------	-------------

Name	Flood-Rate	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## RATE\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## CCY\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	CCY_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## AMOUNT\_SLAB1

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNT_SLAB1	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## EFFECTIVE\_DATE

<b>Attribute</b>	<b>Description</b>	
Name	EFFECTIVE_DATE	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

**BRANCH\_CODE**

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

**BORROW\_LEND\_IND**

Attribute	Description	
Name	BORROW_LEND_IND	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	B,L,M

**Filtrate-Detail**

Attribute	Description	
Name	Filtrate-Detail	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**RATE\_CODE**

Attribute	Description	
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

**CCY\_CODE**

Attribute	Description
-----------	-------------

Name	CCY_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## AMOUNT\_SLAB

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNT_SLAB	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## EFFECTIVE\_DATE

<b>Attribute</b>	<b>Description</b>	
Name	EFFECTIVE_DATE	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## BORROW\_LEND\_IND

<b>Attribute</b>	<b>Description</b>	
Name	BORROW_LEND_IND	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	B,L,M

**TENOR\_TO1**

Attribute		Description
Name	TENOR_TO1	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

**INTEREST\_RATE**

Attribute		Description
Name	INTEREST_RATE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

**RATECODEC**

Attribute		Description
Name	RATECODEC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

**CCYCODEC**

Attribute		Description
Name	CCYCODEC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

**AMOUNTSLABC**

Attribute		Description
Name	AMOUNTSLABC	
Datatype	Number	
Description		



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## EFFECTIVEDATEC

<b>Attribute</b>	<b>Description</b>	
Name	EFFECTIVEDATEC	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## BRANCHCODEC

<b>Attribute</b>	<b>Description</b>	
Name	BRANCHCODEC	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## BORROWLENDINDC

<b>Attribute</b>	<b>Description</b>	
Name	BORROWLENDINDC	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## TENORTOC

<b>Attribute</b>	<b>Description</b>	
Name	TENORTOC	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TDMAXRATE

<b>Attribute</b>	<b>Description</b>
Name	TDMAXRATE

Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TDPREDIFF

<b>Attribute</b>	<b>Description</b>	
Name	TDPREDIFF	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

[TOP](#)

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

[TOP](#)

## 2.5.2.CF-AuthorizeFloatRateMaint-Req-IO-MSG.xsd

### FCUBS\_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE\_OPERATION

SOURCE\_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

### FCUBS\_BODY

Rate-Code-IO

RATE\_CODE

BRANCH\_CODE

CHECKER

CHECKERSTAMP

MODNO

### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

### SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**UBSCOMP**

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description
-----------	-------------

Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MSGSTAT**

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

**PASSWORD**

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

**ADDL**

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

**PARAM**

Attribute	Description
-----------	-------------

Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

[TOP](#)

## Rate-Code-IO

Attribute	Description
Name	Rate-Code-IO
Datatype	
Description	

[TOP](#)

## RATE\_CODE

Attribute	Description	
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)



## BRANCH\_CODE

Attribute	Description				
Name	BRANCH_CODE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

[TOP](#)

## CHECKER

Attribute	Description				
Name	CHECKER				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
	Restrictions	Description			
maxLength	12				

[TOP](#)

## CHECKERSTAMP

Attribute	Description				
Name	CHECKERSTAMP				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
	Restrictions	Description			
maxLength	35				

[TOP](#)

## MODNO

Attribute	Description				
Name	MODNO				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## 2.5.3.CF-AuthorizeFloatRateMaint-Res-Full-MSG.xsd

### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

### *FCUBS\_BODY*

*Rate-Code-Full*

*RATE\_CODE*

*RATEDESC*

*BRANCH\_CODE*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*Rate-Ccy*

*RATE\_CODE*

*CCY\_CODE*

*BRANCH\_CODE*

*Fload-Rate*

*RATE\_CODE*

*CCY\_CODE*

*AMOUNT\_SLAB1*

EFFECTIVE\_DATE  
BRANCH\_CODE  
BORROW\_LEND\_IND

*Filtrate-Detail*

RATE\_CODE  
CCY\_CODE  
AMOUNT\_SLAB  
EFFECTIVE\_DATE  
BRANCH\_CODE  
BORROW\_LEND\_IND  
TENOR\_TO1  
INTEREST\_RATE  
RATECODEC  
CCYCODEC  
AMOUNTSLABC  
EFFECTIVEDATEC  
BRANCHCODEC  
BORROWLENDINDC  
TENORTOC  
TDMAXRATE  
TDPREDIFF

UDFDETAILS

FLDNAM

FLDVAL

FCUBS\_ERROR\_RESP

ERROR

ECODE

EDESC

FCUBS\_WARNING\_RESP

WARNING

WCODE

WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

<b>Attribute</b>	<b>Description</b>	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description							
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
	Restrictions	Description					
	length	3					
pattern	[a-zA-Z_0-9]{3}						

[TOP](#)

## MODULEID

Attribute	Description						
Name	MODULEID						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nullable	true
	Attribute	Description					
	minOccurs	0					
nullable	true						

[TOP](#)

## SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	nullable	true
	Attribute	Description			
nullable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	nullable	true
	Attribute	Description			
nullable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)**PARAM**

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**NAME**

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

[TOP](#)**VALUE**

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)**FCUBS\_BODY**

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about Full Response	

[TOP](#)**Rate-Code-Full**

Attribute	Description	
Name	Rate-Code-Full	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**RATE\_CODE**

Attribute	Description	
Name	RATE_CODE	
Datatype	String	
Description		



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## RATEDESC

<b>Attribute</b>	<b>Description</b>	
Name	RATEDESC	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## Rate-Ccy

Attribute	Description	
Name	Rate-Ccy	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## RATE\_CODE

Attribute	Description	
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

## CCY\_CODE

Attribute	Description	
Name	CCY_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## BRANCH\_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## Fload-Rate

<b>Attribute</b>	<b>Description</b>	
Name	Fload-Rate	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## RATE\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## CCY\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	CCY_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## AMOUNT\_SLAB1

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNT_SLAB1	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

**EFFECTIVE\_DATE**

Attribute	Description	
Name	EFFECTIVE_DATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	1

**BRANCH\_CODE**

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

**BORROW\_LEND\_IND**

Attribute	Description	
Name	BORROW_LEND_IND	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	B,L,M

**Filtrate-Detail**

Attribute	Description	
Name	Filtrate-Detail	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**RATE\_CODE**

Attribute	Description	
Name	RATE_CODE	
Datatype	String	

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## CCY\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	CCY_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## AMOUNT\_SLAB

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNT_SLAB	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## EFFECTIVE\_DATE

<b>Attribute</b>	<b>Description</b>	
Name	EFFECTIVE_DATE	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## BORROW\_LEND\_IND

Attribute	Description	
Name	BORROW_LEND_IND	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	B,L,M

[TOP](#)

## TENOR\_TO1

Attribute	Description	
Name	TENOR_TO1	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

## INTEREST\_RATE

Attribute	Description	
Name	INTEREST_RATE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## RATECODEC

Attribute	Description	
Name	RATECODEC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

## CCYCODEC

Attribute	Description	
Name	CCYCODEC	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## AMOUNTSLABC

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNTSLABC	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## EFFECTIVEDATEC

<b>Attribute</b>	<b>Description</b>	
Name	EFFECTIVEDATEC	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## BRANCHCODEC

<b>Attribute</b>	<b>Description</b>	
Name	BRANCHCODEC	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## BORROWLENDINDC

<b>Attribute</b>	<b>Description</b>	
Name	BORROWLENDINDC	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## TENORTOC



Attribute	Description	
Name	TENORTOC	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## TDMAXRATE

Attribute	Description	
Name	TDMAXRATE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## TDPREDIFF

Attribute	Description	
Name	TDPREDIFF	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

[TOP](#)

## FLDVAL

Attribute	Description						
Name	FLDVAL						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></tbody></table>	Restrictions	Description	maxLength	255	minLength	0
	Restrictions	Description					
	maxLength	255					
minLength	0						

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description				
Name	FCUBS_ERROR_RESP				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## ERROR

Attribute	Description				
Name	ERROR				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
	Attribute	Description			
maxOccurs	unbounded				

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description
-----------	-------------

Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## WARNING

<b>Attribute</b>	<b>Description</b>	
Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## WCODE

<b>Attribute</b>	<b>Description</b>
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

<b>Attribute</b>	<b>Description</b>
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.5.4.CF-AuthorizeFloatRateMaint-Res-PK-MSG.xsd

*FCUBS\_HEADER*  
*SOURCE*  
*UBSCOMP*  
*MSGID*  
*CORRELID*  
*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*CHOICE*  
*Rate-Code-PK*  
*RATE\_CODE*  
*BRANCH\_CODE*  
*Rate-Code-IO*  
*RATE\_CODE*  
*BRANCH\_CODE*  
*CHECKER*  
*CHECKERSTAMP*  
*MODNO*  
*FCUBS\_ERROR\_RESP*  
*ERROR*  
*ECODE*  
*EDESC*  
*FCUBS\_WARNING\_RESP*  
*WARNING*  
*WCODE*  
*WDESC*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

[TOP](#)

## CHOICE

Attribute	Description
-----------	-------------

Name	CHOICE
Datatype	
Description	

[TOP](#)

### Rate-Code-PK

Attribute	Description	
Name	Rate-Code-PK	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

### RATE\_CODE

Attribute	Description	
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

### BRANCH\_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

### Rate-Code-IO

Attribute	Description	
Name	Rate-Code-IO	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

### RATE\_CODE

Attribute	Description
-----------	-------------

Name	RATE_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description
-----------	-------------

Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.6.CloseFloatRateMaint

CloseFloatRateMaint

### 2.6.1.CF-CloseFloatRateMaint-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Rate-Code-Full*

*RATE\_CODE*

*RATEDESC*

*BRANCH\_CODE*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*Rate-Ccy*

*RATE\_CODE*

*CCY\_CODE*

*BRANCH\_CODE*

*Fload-Rate*

RATE\_CODE  
 CCY\_CODE  
 AMOUNT\_SLAB1  
 EFFECTIVE\_DATE  
 BRANCH\_CODE  
 BORROW\_LEND\_IND

*Fltrate-Detail*

RATE\_CODE  
 CCY\_CODE  
 AMOUNT\_SLAB  
 EFFECTIVE\_DATE  
 BRANCH\_CODE  
 BORROW\_LEND\_IND  
 TENOR\_TO1  
 INTEREST\_RATE  
 RATECODEC  
 CCYCODEC  
 AMOUNTSLABC  
 EFFECTIVEDATEC  
 BRANCHCODEC  
 BORROWLENDINDC  
 TENORTOC  
 TDMAXRATE  
 TDPREDIFF

UDFDETAILS

FLDNAM

FLDVAL

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		



Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTITRIPID**

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

[TOP](#)

## Rate-Code-Full

Attribute	Description
Name	Rate-Code-Full
Datatype	
Description	

[TOP](#)

## RATE\_CODE

Attribute	Description	
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## RATEDESC

Attribute	Description
-----------	-------------

Name	RATEDESC	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

**Rate-Ccy**

Attribute	Description	
Name	Rate-Ccy	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**RATE\_CODE**

Attribute	Description	
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

**CCY\_CODE**

Attribute	Description	
Name	CCY_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

**BRANCH\_CODE**

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

**Fload-Rate**

Attribute	Description
-----------	-------------

Name	Flood-Rate	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## RATE\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## CCY\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	CCY_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## AMOUNT\_SLAB1

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNT_SLAB1	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## EFFECTIVE\_DATE

<b>Attribute</b>	<b>Description</b>	
Name	EFFECTIVE_DATE	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1



**BRANCH\_CODE**

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

**BORROW\_LEND\_IND**

Attribute	Description	
Name	BORROW_LEND_IND	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	B,L,M

**Filtrate-Detail**

Attribute	Description	
Name	Filtrate-Detail	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**RATE\_CODE**

Attribute	Description	
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

**CCY\_CODE**

Attribute	Description
-----------	-------------

Name	CCY_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## AMOUNT\_SLAB

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNT_SLAB	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## EFFECTIVE\_DATE

<b>Attribute</b>	<b>Description</b>	
Name	EFFECTIVE_DATE	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## BORROW\_LEND\_IND

<b>Attribute</b>	<b>Description</b>	
Name	BORROW_LEND_IND	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	B,L,M

[TOP](#)**TENOR\_TO1**

Attribute		Description
Name	TENOR_TO1	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)**INTEREST\_RATE**

Attribute		Description
Name	INTEREST_RATE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**RATECODEC**

Attribute		Description
Name	RATECODEC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)**CCYCODEC**

Attribute		Description
Name	CCYCODEC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)**AMOUNTSLABC**

Attribute		Description
Name	AMOUNTSLABC	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## EFFECTIVEDATEC

Attribute	Description	
Name	EFFECTIVEDATEC	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## BRANCHCODEC

Attribute	Description	
Name	BRANCHCODEC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## BORROWLENDINDC

Attribute	Description	
Name	BORROWLENDINDC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## TENORTOC

Attribute	Description	
Name	TENORTOC	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## TDMAXRATE

Attribute	Description
Name	TDMAXRATE

Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TDPREDIFF

<b>Attribute</b>	<b>Description</b>	
Name	TDPREDIFF	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

[TOP](#)

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

[TOP](#)

2.6.2.CF-CloseFloatRateMaint-Req-IO-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Rate-Code-IO*

*RATE\_CODE*

*BRANCH\_CODE*

*MAKER*

*MAKERSTAMP*

*MODNO*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

**SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**UBSCOMP**

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description
-----------	-------------

Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true



Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MSGSTAT**

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

**PASSWORD**

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

**ADDL**

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

**PARAM**

Attribute	Description
-----------	-------------

Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

[TOP](#)

## Rate-Code-IO

Attribute	Description
Name	Rate-Code-IO
Datatype	
Description	

[TOP](#)

## RATE\_CODE

Attribute	Description	
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## BRANCH\_CODE

Attribute	Description				
Name	BRANCH_CODE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

[TOP](#)

## MAKER

Attribute	Description				
Name	MAKER				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
	Restrictions	Description			
maxLength	12				

[TOP](#)

## MAKERSTAMP

Attribute	Description				
Name	MAKERSTAMP				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
	Restrictions	Description			
maxLength	35				

[TOP](#)

## MODNO

Attribute	Description				
Name	MODNO				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## 2.6.3.CF-CloseFloatRateMaint-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Rate-Code-Full*

*RATE\_CODE*

*RATEDESC*

*BRANCH\_CODE*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*Rate-Ccy*

*RATE\_CODE*

*CCY\_CODE*

*BRANCH\_CODE*

*Fload-Rate*

*RATE\_CODE*

*CCY\_CODE*

*AMOUNT\_SLAB1*

EFFECTIVE\_DATE  
BRANCH\_CODE  
BORROW\_LEND\_IND

*Filtrate-Detail*

RATE\_CODE  
CCY\_CODE  
AMOUNT\_SLAB  
EFFECTIVE\_DATE  
BRANCH\_CODE  
BORROW\_LEND\_IND  
TENOR\_TO1  
INTEREST\_RATE  
RATECODEC  
CCYCODEC  
AMOUNTSLABC  
EFFECTIVEDATEC  
BRANCHCODEC  
BORROWLENDINDC  
TENORTOC  
TDMAXRATE  
TDPREDIFF

UDFDETAILS

FLDNAM

FLDVAL

FCUBS\_ERROR\_RESP

ERROR

ECODE

EDESC

FCUBS\_WARNING\_RESP

WARNING

WCODE

WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

<b>Attribute</b>	<b>Description</b>	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description							
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
	Restrictions	Description					
	length	3					
pattern	[a-zA-Z_0-9]{3}						

[TOP](#)

## MODULEID

Attribute	Description						
Name	MODULEID						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nullable	true
	Attribute	Description					
	minOccurs	0					
nullable	true						

[TOP](#)

## SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	nullable	true
	Attribute	Description			
nullable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	nullable	true
	Attribute	Description			
nullable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about Full Response	

[TOP](#)

## Rate-Code-Full

Attribute	Description	
Name	Rate-Code-Full	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## RATE\_CODE

Attribute	Description	
Name	RATE_CODE	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## RATEDESC

<b>Attribute</b>	<b>Description</b>	
Name	RATEDESC	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## Rate-Ccy

Attribute	Description	
Name	Rate-Ccy	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## RATE\_CODE

Attribute	Description	
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

## CCY\_CODE

Attribute	Description	
Name	CCY_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## BRANCH\_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## Fload-Rate

<b>Attribute</b>	<b>Description</b>	
Name	Fload-Rate	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## RATE\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## CCY\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	CCY_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## AMOUNT\_SLAB1

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNT_SLAB1	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

**EFFECTIVE\_DATE**

Attribute		Description
Name	EFFECTIVE_DATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	1

**BRANCH\_CODE**

Attribute		Description
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

**BORROW\_LEND\_IND**

Attribute		Description
Name	BORROW_LEND_IND	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	B,L,M

**Filtrate-Detail**

Attribute		Description
Name	Filtrate-Detail	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**RATE\_CODE**

Attribute		Description
Name	RATE_CODE	
Datatype	String	



Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## CCY\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	CCY_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## AMOUNT\_SLAB

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNT_SLAB	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## EFFECTIVE\_DATE

<b>Attribute</b>	<b>Description</b>	
Name	EFFECTIVE_DATE	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## BORROW\_LEND\_IND

Attribute	Description				
Name	BORROW_LEND_IND				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>B,L,M</td></tr></tbody></table>	Restrictions	Description	enumeration	B,L,M
	Restrictions	Description			
enumeration	B,L,M				

[TOP](#)

## TENOR\_TO1

Attribute	Description				
Name	TENOR_TO1				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				

[TOP](#)

## INTEREST\_RATE

Attribute	Description				
Name	INTEREST_RATE				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## RATECODEC

Attribute	Description				
Name	RATECODEC				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>10</td></tr></tbody></table>	Restrictions	Description	maxLength	10
	Restrictions	Description			
maxLength	10				

[TOP](#)

## CCYCODEC

Attribute	Description
Name	CCYCODEC
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## AMOUNTSLABC

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNTSLABC	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## EFFECTIVEDATEC

<b>Attribute</b>	<b>Description</b>	
Name	EFFECTIVEDATEC	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## BRANCHCODEC

<b>Attribute</b>	<b>Description</b>	
Name	BRANCHCODEC	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## BORROWLENDINDC

<b>Attribute</b>	<b>Description</b>	
Name	BORROWLENDINDC	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## TENORTOC

Attribute	Description	
Name	TENORTOC	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## TDMAXRATE

Attribute	Description	
Name	TDMAXRATE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## TDPREDIFF

Attribute	Description	
Name	TDPREDIFF	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

[TOP](#)

## FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description
-----------	-------------

Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.6.4.CF-CloseFloatRateMaint-Res-PK-MSG.xsd

*FCUBS\_HEADER*  
*SOURCE*  
*UBSCOMP*  
*MSGID*  
*CORRELID*  
*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*CHOICE*  
*Rate-Code-PK*  
*RATE\_CODE*  
*BRANCH\_CODE*  
*Rate-Code-IO*  
*RATE\_CODE*  
*BRANCH\_CODE*  
*MAKER*  
*MAKERSTAMP*  
*MODNO*  
*FCUBS\_ERROR\_RESP*  
*ERROR*  
*ECODE*  
*EDESC*  
*FCUBS\_WARNING\_RESP*  
*WARNING*  
*WCODE*  
*WDESC*  
**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*



[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

[TOP](#)

## CHOICE

Attribute	Description
-----------	-------------

Name	CHOICE
Datatype	
Description	

[TOP](#)

### Rate-Code-PK

Attribute	Description	
Name	Rate-Code-PK	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

### RATE\_CODE

Attribute	Description	
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

### BRANCH\_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

### Rate-Code-IO

Attribute	Description	
Name	Rate-Code-IO	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

### RATE\_CODE

Attribute	Description
-----------	-------------

Name	RATE_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description
-----------	-------------

Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)



## 2.7.CreateCFFloatRateMaint

Input of Floating rate Maintenance

### 2.7.1.CF-CreateCFFloatRateMaint-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Cftm-Rate-Master-Full*

*RATECODE*

*RATECODEDESCRIPTION*

*TENORCODE*

*TENORCODEDESCRIPTION*

*CCYCODE*

*CCYNAME*

*EFFECTIVEDATE*

*RATESOURCE*

*RATESOURCEDESCRIPTION*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

[RECSTAT](#)  
[ONCEAUTH](#)  
[Cftm-Rate-Detail](#)  
[RATETYPE](#)  
[RATETYPEDESCRIPTION](#)  
[INTERESTRATE](#)  
[UDFDETAILS](#)  
[FUNCTIONID](#)  
[FIELD\\_NAME](#)  
[DATATYPE](#)  
[FIELD\\_VALUE](#)  
[VAL\\_TYPE](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description						
Name	MSGID						
Datatype	String						
Description							
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	nillable	true
	Attribute	Description					
	minOccurs	0					
nillable	true						

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

## DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	

Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

[TOP](#)

## Cftm-Rate-Master-Full

Attribute	Description
Name	Cftm-Rate-Master-Full
Datatype	
Description	This indicates the rate maintenance Full request

[TOP](#)

## RATECODE

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description	Specifies The Rate Code.	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

## RATECODEDESCRIPTION

Attribute	Description	
Name	RATECODEDESCRIPTION	
Datatype	String	
Description	Specifies The Rate Code Description.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

## TENORCODE

Attribute	Description	
Name	TENORCODE	
Datatype	String	
Description	Specifies The Tenor Code.	
Attributes	Attribute	Description
	minOccurs	1

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## TENORCODEDESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	TENORCODEDESCRIPTION	
Datatype	String	
Description	Specifies The Tenor Code Description.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## CCYCODE

<b>Attribute</b>	<b>Description</b>	
Name	CCYCODE	
Datatype	String	
Description	Specifies The Currency Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## CCYNAME

<b>Attribute</b>	<b>Description</b>	
Name	CCYNAME	
Datatype	String	
Description	Specifies The Currency Code Description.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## EFFECTIVEDATE

<b>Attribute</b>	<b>Description</b>	
Name	EFFECTIVEDATE	
Datatype	Date	
Description	Specifies The Effective Date.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## RATESOURCE



Attribute	Description	
Name	RATESOURCE	
Datatype	String	
Description	Specifies The Rate Source.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

## RATESOURCEDESCRIPTION

Attribute	Description	
Name	RATESOURCEDESCRIPTION	
Datatype	String	
Description	Specifies The Rate Source Description.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

## MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	The User id who has booked the contract	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has booked the contract	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

## CHECKERID

Attribute	Description
Name	CHECKERID

Datatype	String	
Description	The User id who has authorized the booked contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has authorized the booked contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Specifies The Modification Number.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Specifies The Authorization Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	Specifies The Record Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorized.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## Cftm-Rate-Detail

Attribute	Description	
Name	Cftm-Rate-Detail	
Datatype		
Description	Indicates The Rate Details.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## RATETYPE

Attribute	Description	
Name	RATETYPE	
Datatype	String	
Description	Specifies The Rate Type.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## RATETYPEDESCRIPTION

Attribute	Description	
Name	RATETYPEDESCRIPTION	
Datatype	String	
Description	Specifies The Rate Type Description.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

## INTERESTRATE

Attribute	Description				
Name	INTERESTRATE				
Datatype	Number				
Description	Specifies The Interest Rate.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## UDFDETAILS

Attribute	Description						
Name	UDFDETAILS						
Datatype							
Description	Indicates The UDF Details.						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

## FIELD\_NAME

Attribute	Description						
Name	FIELD_NAME						
Datatype	String						
Description	Indicates the User Defined Field Name.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	105	minLength	1
	Restrictions	Description					
	maxLength	105					
minLength	1						

[TOP](#)

## DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

[TOP](#)

## FIELD\_VALUE

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

[TOP](#)

## VAL\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2
	minLength	0

[TOP](#)

## 2.7.2.CF-CreateCFFloatRateMaint-Req-IO-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Cftm-Rate-Master-IO*

*RATECODE*

*TENORCODE*

*CCYCODE*

*EFFECTIVEDATE*

*RATESOURCE*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

*Cftm-Rate-Detail*

*RATETYPE*

*RATETYPEDESCRIPTION*

*INTERESTRATE*

*UDFDETAILS*

[FUNCTIONID](#)  
[FIELD\\_NAME](#)  
[DATATYPE](#)  
[FIELD\\_VALUE](#)  
[VAL\\_TYPE](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description						
Name	MSGID						
Datatype	String						
Description							
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nullable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	nullable	true
	Attribute	Description					
	minOccurs	0					
nullable	true						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*		
	Restrictions	Description					
pattern	[a-zA-Z_0-9]*						

[TOP](#)

## CORRELID

Attribute	Description
Name	CORRELID
Datatype	String

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*



**OPERATION**

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTITRIPID**

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description
-----------	-------------

Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about IORequest	

**Cftm-Rate-Master-IO**

Attribute	Description
Name	Cftm-Rate-Master-IO
Datatype	
Description	Indicates the Input of Floating rate Maintenance.

**RATECODE**

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description	Specifies The Rate Code.	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

**TENORCODE**

Attribute	Description	
Name	TENORCODE	
Datatype	String	
Description	Specifies The Tenor Code.	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	12

**CCYCODE**

Attribute	Description	
Name	CCYCODE	
Datatype	String	
Description	Specifies The Currency Code.	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

**EFFECTIVEDATE**

Attribute	Description
Name	EFFECTIVEDATE
Datatype	Date
Description	Specifies The Effective Date.

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## RATESOURCE

<b>Attribute</b>	<b>Description</b>	
Name	RATESOURCE	
Datatype	String	
Description	Specifies The Rate Source.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Specifies The Maker Identification.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Specifies The Maker Date Stamp.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Specifies The Checker Identification.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

**CHECKERDTSTAMP**

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Specifies The Checker Date Stamp.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Specifies The Modification Number.	
Attributes	Attribute	Description
	minOccurs	0

**AUTHSTAT**

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Specifies The Authorization Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**RECSTAT**

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Specifies The Record Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**ONCEAUTH**

Attribute	Description
Name	ONCEAUTH

Datatype	String	
Description	Indicates Whether The Floating Rate Maintenance Record is Authorized Atleast Once.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Cftm-Rate-Detail

<b>Attribute</b>	<b>Description</b>	
Name	Cftm-Rate-Detail	
Datatype		
Description	Specifies The Rate Details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	1

[TOP](#)

## RATETYPE

<b>Attribute</b>	<b>Description</b>	
Name	RATETYPE	
Datatype	String	
Description	Specifies The Rate Type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## RATETYPEDESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	RATETYPEDESCRIPTION	
Datatype	String	
Description	Specifies The Rate Type Description.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## INTERESTRATE

<b>Attribute</b>	<b>Description</b>	
Name	INTERESTRATE	
Datatype	Number	
Description	Specifies The Interest Rate.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

**UDFDETAILS**

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description	Indicates The UDF Details.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**FIELD\_NAME**

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

**DATATYPE**

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

**FIELD\_VALUE**

Attribute	Description
-----------	-------------



Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

[TOP](#)

## VAL\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2
	minLength	0

[TOP](#)

## 2.7.3.CF-CreateCFFloatRateMaint-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Cftm-Rate-Master-IO*

*RATECODE*

*TENORCODE*

*CCYCODE*

*EFFECTIVEDATE*

*RATESOURCE*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

*Cftm-Rate-Detail*

*RATETYPE*

*RATETYPEDESCRIPTION*

*INTERESTRATE*

*UDFDETAILS*

*FUNCTIONID*

*FIELD\_NAME*

*DATATYPE*

*FIELD\_VALUE*

*VAL\_TYPE*

*Cftm-Rate-Master-Full*

*RATECODE*

*RATECODEDESCRIPTION*

*TENORCODE*

*TENORCODEDESCRIPTION*

*CCYCODE*

*CCYNAME*

*EFFECTIVEDATE*

*RATESOURCE*

*RATESOURCEDESCRIPTION*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

*Cftm-Rate-Detail*

*RATETYPE*

*RATETYPEDESCRIPTION*

*INTERESTRATE*

*UDFDETAILS*

*FUNCTIONID*

*FIELD\_NAME*

*DATATYPE*

*FIELD\_VALUE*

*VAL\_TYPE*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

[TOP](#)

## CHOICE

Attribute	Description
-----------	-------------



Name	CHOICE
Datatype	
Description	

[TOP](#)

## Cftm-Rate-Master-IO

Attribute	Description
Name	Cftm-Rate-Master-IO
Datatype	
Description	Includes the Input of Floating rate Maintenance IO details.

[TOP](#)

## RATECODE

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description	Specifies The Rate Code.	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

## TENORCODE

Attribute	Description	
Name	TENORCODE	
Datatype	String	
Description	Specifies The Tenor Code.	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## CCYCODE

Attribute	Description	
Name	CCYCODE	
Datatype	String	
Description	Specifies The Currency Code.	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## EFFECTIVEDATE

Attribute	Description
-----------	-------------

Name	EFFECTIVEDATE	
Datatype	Date	
Description	Specifies The Effective Date.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## RATESOURCE

<b>Attribute</b>	<b>Description</b>	
Name	RATESOURCE	
Datatype	String	
Description	Specifies The Rate Source.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Specifies The Maker Identification.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Specifies The Maker Date Stamp.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Specifies The Checker Identification.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Specifies The Checker Date Stamp.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Specifies The Modification Number.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Specifies The Authorization Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	Specifies The Record Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Whether The Floating Rate Maintenance Record is Authorized Atleast Once.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## Cftm-Rate-Detail

Attribute	Description	
Name	Cftm-Rate-Detail	
Datatype		
Description	Specifies The Rate Details.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	1

[TOP](#)

## RATETYPE

Attribute	Description	
Name	RATETYPE	
Datatype	String	
Description	Specifies The Rate Type.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## RATETYPEDESCRIPTION

Attribute	Description	
Name	RATETYPEDESCRIPTION	
Datatype	String	
Description	Specifies The Rate Type Description.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

## INTERESTRATE

Attribute	Description
Name	INTERESTRATE
Datatype	Number

Description	Specifies The Interest Rate.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description	Indicates The UDF Details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## FIELD\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

[TOP](#)

## DATATYPE

<b>Attribute</b>	<b>Description</b>	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

**FIELD\_VALUE**

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

**VAL\_TYPE**

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

**Cftm-Rate-Master-Full**

Attribute	Description
Name	Cftm-Rate-Master-Full
Datatype	
Description	Includes the Input of Floating rate Maintenance Full details.

**RATECODE**

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description	Specifies The Rate Code.	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

**RATECODEDESCRIPTION**

Attribute	Description
Name	RATECODEDESCRIPTION

Datatype	String	
Description	Specifies The Rate Code Description.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## TENORCODE

<b>Attribute</b>	<b>Description</b>	
Name	TENORCODE	
Datatype	String	
Description	Specifies The Tenor Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## TENORCODEDESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	TENORCODEDESCRIPTION	
Datatype	String	
Description	Specifies The Tenor Code Description.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## CCYCODE

<b>Attribute</b>	<b>Description</b>	
Name	CCYCODE	
Datatype	String	
Description	Specifies The Currency Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## CCYNAME

<b>Attribute</b>	<b>Description</b>	
Name	CCYNAME	
Datatype	String	
Description	Specifies The Currency Code Description.	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## EFFECTIVEDATE

<b>Attribute</b>	<b>Description</b>	
Name	EFFECTIVEDATE	
Datatype	Date	
Description	Specifies The Effective Date.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## RATESOURCE

<b>Attribute</b>	<b>Description</b>	
Name	RATESOURCE	
Datatype	String	
Description	Specifies The Rate Source.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## RATESOURCEDESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	RATESOURCEDESCRIPTION	
Datatype	String	
Description	Specifies The Rate Source Description.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Specifies The Maker Identification.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12



**MAKERDTSTAMP**

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Specifies The Maker Date Stamp.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

**CHECKERID**

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Specifies The Checker Identification.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CHECKERDTSTAMP**

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Specifies The Checker Date Stamp.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Specifies The Modification Number.	
Attributes	Attribute	Description
	minOccurs	0

**AUTHSTAT**

Attribute	Description
Name	AUTHSTAT

Datatype	String	
Description	Specifies The Authorization Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	Specifies The Record Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Whether The Floating Rate Maintenance Record is Authorized Atleast Once.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Cftm-Rate-Detail

<b>Attribute</b>	<b>Description</b>	
Name	Cftm-Rate-Detail	
Datatype		
Description	Specifies The Rate Details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	1

[TOP](#)

## RATETYPE

<b>Attribute</b>	<b>Description</b>	
Name	RATETYPE	
Datatype	String	
Description	Specifies The Rate Type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## RATETYPEDESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	RATETYPEDESCRIPTION	
Datatype	String	
Description	Specifies The Rate Type Description.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## INTERESTRATE

<b>Attribute</b>	<b>Description</b>	
Name	INTERESTRATE	
Datatype	Number	
Description	Specifies The Interest Rate.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description	Indicates The UDF Details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## FIELD\_NAME

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

[TOP](#)

## DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

## FIELD\_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

[TOP](#)

## VAL\_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description

Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

<b>Attribute</b>	<b>Description</b>	
Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.7.4.CF-CreateCFFloatRateMaint-Res-PK-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Cftm-Rate-Master-PK*

*RATECODE*

*TENORCODE*

*CCYCODE*

*EFFECTIVEDATE*

*Cftm-Rate-Master-IO*

*RATECODE*

*TENORCODE*

*CCYCODE*

*EFFECTIVEDATE*

*RATESOURCE*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

ONCEAUTH  
Cftm-Rate-Detail  
RATETYPE  
RATETYPEDESCRIPTION  
INTERESTRATE  
UDFDETAILS  
FUNCTIONID  
FIELD\_NAME  
DATATYPE  
FIELD\_VALUE  
VAL\_TYPE  
Cftm-Rate-Master-Full  
RATECODE  
RATECODEDESCRIPTION  
TENORCODE  
TENORCODEDESCRIPTION  
CCYCODE  
CCYNAME  
EFFECTIVEDATE  
RATESOURCE  
RATESOURCEDESCRIPTION  
MAKERID  
MAKERDTSTAMP  
CHECKERID  
CHECKERDTSTAMP  
MODNO  
AUTHSTAT  
RECSTAT  
ONCEAUTH  
Cftm-Rate-Detail  
RATETYPE  
RATETYPEDESCRIPTION  
INTERESTRATE  
UDFDETAILS  
FUNCTIONID  
FIELD\_NAME  
DATATYPE  
FIELD\_VALUE  
VAL\_TYPE  
FCUBS\_ERROR\_RESP  
ERROR  
ECODE  
EDESC  
FCUBS\_WARNING\_RESP



WARNING  
WCODE  
WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**OPERATION**

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTITRIPID**

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description
-----------	-------------

Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about PKResponse	

[TOP](#)**CHOICE**

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)**Cftm-Rate-Master-PK**

Attribute	Description
Name	Cftm-Rate-Master-PK
Datatype	
Description	Includes the Input of Floating rate Maintenance Primary key Details.

[TOP](#)**RATECODE**

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description	Specifies The Rate Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)**TENORCODE**

Attribute	Description	
Name	TENORCODE	
Datatype	String	
Description	Specifies The Tenor Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)**CCYCODE**

Attribute	Description	
Name	CCYCODE	
Datatype	String	
Description	Specifies The Currency Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

**EFFECTIVEDATE**

Attribute	Description
Name	EFFECTIVEDATE
Datatype	Date
Description	Specifies The Effective Date.

**Cftm-Rate-Master-IO**

Attribute	Description
Name	Cftm-Rate-Master-IO
Datatype	
Description	Includes the Input of Floating rate Maintenance IO Details.

**RATECODE**

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description	Specifies The Rate Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

**TENORCODE**

Attribute	Description	
Name	TENORCODE	
Datatype	String	
Description	Specifies The Tenor Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CCYCODE**

Attribute	Description	
Name	CCYCODE	
Datatype	String	
Description	Specifies The Currency Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

**EFFECTIVEDATE**

Attribute	Description
Name	EFFECTIVEDATE
Datatype	Date
Description	Specifies The Effective Date.

**RATESOURCE**

Attribute	Description	
Name	RATESOURCE	
Datatype	String	
Description	Specifies The Rate Source.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

**MAKERID**

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Specifies The Maker Identification.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**MAKERDTSTAMP**

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Specifies The Maker Date Stamp.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

**CHECKERID**

Attribute	Description
Name	CHECKERID
Datatype	String
Description	Specifies The Checker Identification.



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Specifies The Checker Date Stamp.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Specifies The Modification Number.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Specifies The Authorization Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	Specifies The Record Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

**ONCEAUTH**

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Whether The Floating Rate Maintenance Record is Authorized Atleast Once.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**Cftm-Rate-Detail**

Attribute	Description	
Name	Cftm-Rate-Detail	
Datatype		
Description	Specifies The Rate Details.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	1

**RATETYPE**

Attribute	Description	
Name	RATETYPE	
Datatype	String	
Description	Specifies The Rate Type.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**RATETYPEDESCRIPTION**

Attribute	Description	
Name	RATETYPEDESCRIPTION	
Datatype	String	
Description	Specifies The Rate Type Description.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

**INTERESTRATE**

Attribute	Description	
Name	INTERESTRATE	
Datatype	Number	
Description	Specifies The Interest Rate.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description	Indicates The UDF Details.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## FIELD\_NAME

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

[TOP](#)

## DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	Attribute	Description
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

[TOP](#)

## FIELD\_VALUE

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

[TOP](#)

## VAL\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2
	minLength	0

[TOP](#)

## Cftm-Rate-Master-Full

<b>Attribute</b>	<b>Description</b>
Name	Cftm-Rate-Master-Full
Datatype	
Description	Includes the Input of Floating rate Maintenance Full Details.

[TOP](#)

## RATECODE

<b>Attribute</b>	<b>Description</b>	
Name	RATECODE	
Datatype	String	
Description	Specifies The Rate Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## RATECODEDESCRIPTION

Attribute	Description	
Name	RATECODEDESCRIPTION	
Datatype	String	
Description	Specifies The Rate Code Description.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

## TENORCODE

Attribute	Description	
Name	TENORCODE	
Datatype	String	
Description	Specifies The Tenor Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## TENORCODEDESCRIPTION

Attribute	Description	
Name	TENORCODEDESCRIPTION	
Datatype	String	
Description	Specifies The Tenor Code Description.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

## CCYCODE

Attribute	Description	
Name	CCYCODE	
Datatype	String	
Description	Specifies The Currency Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## CCYNAME

Attribute	Description
Name	CCYNAME

Datatype	String	
Description	Specifies The Currency Code Description.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## EFFECTIVEDATE

<b>Attribute</b>	<b>Description</b>
Name	EFFECTIVEDATE
Datatype	Date
Description	Specifies The Effective Date.

[TOP](#)

## RATESOURCE

<b>Attribute</b>	<b>Description</b>	
Name	RATESOURCE	
Datatype	String	
Description	Specifies The Rate Source.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## RATESOURCEDESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	RATESOURCEDESCRIPTION	
Datatype	String	
Description	Specifies The Rate Source Description.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Specifies The Maker Identification.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

**MAKERDTSTAMP**

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Specifies The Maker Date Stamp.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

**CHECKERID**

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Specifies The Checker Identification.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CHECKERDTSTAMP**

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Specifies The Checker Date Stamp.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Specifies The Modification Number.	
Attributes	Attribute	Description
	minOccurs	0

**AUTHSTAT**

Attribute	Description
Name	AUTHSTAT

Datatype	String	
Description	Specifies The Authorization Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	Specifies The Record Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Whether The Floating Rate Maintenance Record is Authorized Atleast Once.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Cftm-Rate-Detail

<b>Attribute</b>	<b>Description</b>	
Name	Cftm-Rate-Detail	
Datatype		
Description	Specifies The Rate Details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	1

[TOP](#)

## RATETYPE

<b>Attribute</b>	<b>Description</b>	
Name	RATETYPE	
Datatype	String	
Description	Specifies The Rate Type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## RATETYPEDESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	RATETYPEDESCRIPTION	
Datatype	String	
Description	Specifies The Rate Type Description.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## INTERESTRATE

<b>Attribute</b>	<b>Description</b>	
Name	INTERESTRATE	
Datatype	Number	
Description	Specifies The Interest Rate.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description	Indicates The UDF Details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## FIELD\_NAME

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

[TOP](#)

## DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

## FIELD\_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

[TOP](#)

## VAL\_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description

Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

<b>Attribute</b>	<b>Description</b>	
Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.8.CreateCFRateCodeMaint

Input of Rate Code Maintenance

### 2.8.1.CF-CreateCFRateCodeMaint-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Cftm-Rate-Code-Defn-Full*

*RATECODE*

*RATECODEDESCRIPTION*

*HOLIDAYCCY*

*PROPAGATIONACROSSBRANCHES*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

*Cftm-Tenor-Code-Defn*

*TENORCODE*

*TENORCODEDESCRIPTION*

UDFDETAILS  
 FUNCTIONID  
 FIELD\_NAME  
 DATATYPE  
 FIELD\_VALUE  
 VAL\_TYPE

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description						
Name	MSGID						
Datatype	String						
Description							
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nullable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	nullable	true
	Attribute	Description					
	minOccurs	0					
nullable	true						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*		
	Restrictions	Description					
pattern	[a-zA-Z_0-9]*						

[TOP](#)

## CORRELID

Attribute	Description
Name	CORRELID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**OPERATION**

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**



Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description
-----------	-------------

Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about FullRequest	

**Cftm-Rate-Code-Defn-Full**

Attribute	Description
Name	Cftm-Rate-Code-Defn-Full
Datatype	
Description	Includes the Input of Rate Code Maintenance Full Details.

**RATECODE**

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description	Indicates Rate Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

**RATECODEDESCRIPTION**

Attribute	Description	
Name	RATECODEDESCRIPTION	
Datatype	String	
Description	Indicates the description of rate code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

**HOLIDAYCCY**

Attribute	Description	
Name	HOLIDAYCCY	
Datatype	String	
Description	Specifies Holiday Currency .	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

**PROPAGATIONACROSSBRANCHES**

Attribute	Description
Name	PROPAGATIONACROSSBRANCHES
Datatype	String
Description	Propagate Across Branches

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Specifies the User id who has saved the record.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates the date and time when the user has saved the record.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates the User id who has authorized the record.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has authorized the booked contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	It indicates the modification number.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	It indicates the status of the record,whether open or Closed.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorized.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Cftm-Tenor-Code-Defn

Attribute	Description	
Name	Cftm-Tenor-Code-Defn	
Datatype		
Description	Includes Tenor code details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## TENORCODE

Attribute	Description	
Name	TENORCODE	
Datatype	String	
Description	Indicates the tenor code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

## TENORCODEDESCRIPTION

Attribute	Description	
Name	TENORCODEDESCRIPTION	
Datatype	String	
Description	Indicates the description of tenor code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

## UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## FIELD\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

[TOP](#)

## DATATYPE

<b>Attribute</b>	<b>Description</b>	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

[TOP](#)

## FIELD\_VALUE

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

[TOP](#)

## VAL\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

[TOP](#)



## 2.8.2.CF-CreateCFRateCodeMaint-Req-IO-MSG.xsd

### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

### *FCUBS\_BODY*

*Cftm-Rate-Code-Defn-IO*

*RATECODE*

*RATECODEDESCRIPTION*

*HOLIDAYCCY*

*PROPAGATIONACROSSBRANCHES*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

*Cftm-Tenor-Code-Defn*

*TENORCODE*

*TENORCODEDESCRIPTION*

*UDFDETAILS*

*FUNCTIONID*

*FIELD\_NAME*

DATATYPE  
FIELD\_VALUE  
VAL\_TYPE

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description						
Name	MSGID						
Datatype	String						
Description							
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	nillable	true
	Attribute	Description					
	minOccurs	0					
nillable	true						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*		
	Restrictions	Description					
pattern	[a-zA-Z_0-9]*						

[TOP](#)

## CORRELID

Attribute	Description
Name	CORRELID
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**OPERATION**

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTITRIPID**

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description
-----------	-------------

Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about IORequest	

**Cftm-Rate-Code-Defn-IO**

Attribute	Description
Name	Cftm-Rate-Code-Defn-IO
Datatype	
Description	Includes the Input of Rate Code Maintenance IO details.

**RATECODE**

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description	Indicates rate code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

**RATECODEDESCRIPTION**

Attribute	Description	
Name	RATECODEDESCRIPTION	
Datatype	String	
Description	Indicates the description of rate code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

**HOLIDAYCCY**

Attribute	Description	
Name	HOLIDAYCCY	
Datatype	String	
Description	Specifies Holiday Currency.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

**PROPAGATIONACROSSBRANCHES**

Attribute	Description
Name	PROPAGATIONACROSSBRANCHES
Datatype	String
Description	Propagate Across Branches

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Specifies the User id who has saved the record.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates the date and time when the user has saved the record.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates the User id who has authorized the record.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has authorized the booked contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	It indicates the modification number.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	It indicates the status of the record,whether open or Closed.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorized.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Cftm-Tenor-Code-Defn

Attribute	Description	
Name	Cftm-Tenor-Code-Defn	
Datatype		
Description	Includes Tenor code details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	1

[TOP](#)

## TENORCODE

Attribute	Description	
Name	TENORCODE	
Datatype	String	
Description	Indicates Tenor code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

## TENORCODEDESCRIPTION

Attribute	Description	
Name	TENORCODEDESCRIPTION	
Datatype	String	
Description	Specifies the description of Tenor Code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

## UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## FIELD\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

[TOP](#)

## DATATYPE

<b>Attribute</b>	<b>Description</b>	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

[TOP](#)

## FIELD\_VALUE

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

[TOP](#)

## VAL\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2
	minLength	0

[TOP](#)

### 2.8.3.CF-CreateCFRateCodeMaint-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Cftm-Rate-Code-Defn-IO*

*RATECODE*

*RATECODEDESCRIPTION*

*HOLIDAYCCY*

*PROPAGATIONACROSSBRANCHES*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

*Cftm-Tenor-Code-Defn*

*TENORCODE*

*TENORCODEDESCRIPTION*

*UDFDETAILS*

*FUNCTIONID*

FIELD\_NAME  
DATATYPE  
FIELD\_VALUE  
VAL\_TYPE

*Cftm-Rate-Code-Defn-Full*

RATECODE  
RATECODEDESCRIPTION  
HOLIDAYCCY  
PROPAGATIONACROSSBRANCHES  
MAKERID  
MAKERDTSTAMP  
CHECKERID  
CHECKERDTSTAMP  
MODNO  
AUTHSTAT  
RECSTAT  
ONCEAUTH

*Cftm-Tenor-Code-Defn*

TENORCODE  
TENORCODEDESCRIPTION  
UDFDETAILS  
FUNCTIONID  
FIELD\_NAME  
DATATYPE  
FIELD\_VALUE  
VAL\_TYPE

*FCUBS\_ERROR\_RESP*

ERROR  
ECODE  
EDESC

*FCUBS\_WARNING\_RESP*

WARNING  
WCODE  
WDESC

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

**SOURCE**

Attribute	Description
Name	SOURCE

Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

<b>Attribute</b>	<b>Description</b>	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

**MODULEID**

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

**SERVICE**

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**OPERATION**

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description
Name	SOURCE_OPERATION



Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)**PARAM**

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**NAME**

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

[TOP](#)**VALUE**

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)**FCUBS\_BODY**

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about FullResponse	

[TOP](#)**CHOICE**

Attribute	Description	
Name	CHOICE	
Datatype		
Description		

[TOP](#)**Cftm-Rate-Code-Defn-IO**

Attribute	Description	
Name	Cftm-Rate-Code-Defn-IO	
Datatype		
Description	Includes the Input of Rate Code Maintenance IO Details.	

[TOP](#)

## RATECODE

Attribute	Description				
Name	RATECODE				
Datatype	String				
Description	Indicates rate code				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>10</td></tr></tbody></table>	Restrictions	Description	maxLength	10
	Restrictions	Description			
maxLength	10				

[TOP](#)

## RATECODEDESCRIPTION

Attribute	Description				
Name	RATECODEDESCRIPTION				
Datatype	String				
Description	Indicates the description of rate code.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>105</td></tr></tbody></table>	Restrictions	Description	maxLength	105
	Restrictions	Description			
maxLength	105				

[TOP](#)

## HOLIDAYCCY

Attribute	Description				
Name	HOLIDAYCCY				
Datatype	String				
Description	Specifies Holiday Currency.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

[TOP](#)

## PROPAGATIONACROSSBRANCHES

Attribute	Description				
Name	PROPAGATIONACROSSBRANCHES				
Datatype	String				
Description	Propagate Across Branches				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	1
	Restrictions	Description			
maxLength	1				

[TOP](#)

## MAKERID

Attribute	Description
-----------	-------------

Name	MAKERID	
Datatype	String	
Description	Specifies the User id who has saved the record.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates the date and time when the user has saved the record.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates the User id who has authorized the record.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has authorized the booked contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	It indicates the modification number.	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	It indicates the status of the record,whether open or Closed.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorized.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Cftm-Tenor-Code-Defn

<b>Attribute</b>	<b>Description</b>	
Name	Cftm-Tenor-Code-Defn	
Datatype		
Description	Includes Tenor code details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	1

[TOP](#)

## TENORCODE

Attribute	Description				
Name	TENORCODE				
Datatype	String				
Description	Indicates Tenor code.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>10</td></tr></tbody></table>	Restrictions	Description	maxLength	10
	Restrictions	Description			
maxLength	10				

[TOP](#)

## TENORCODEDESCRIPTION

Attribute	Description				
Name	TENORCODEDESCRIPTION				
Datatype	String				
Description	Specifies the description of Tenor Code				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>105</td></tr></tbody></table>	Restrictions	Description	maxLength	105
	Restrictions	Description			
maxLength	105				

[TOP](#)

## UDFDETAILS

Attribute	Description						
Name	UDFDETAILS						
Datatype							
Description	Includes User Defined Fields details						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

## FIELD\_NAME

Attribute	Description
-----------	-------------

Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

[TOP](#)

## DATATYPE

<b>Attribute</b>	<b>Description</b>	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

[TOP](#)

## FIELD\_VALUE

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

[TOP](#)

## VAL\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2
	minLength	0

[TOP](#)

## Cftm-Rate-Code-Defn-Full

<b>Attribute</b>	<b>Description</b>	
Name	Cftm-Rate-Code-Defn-Full	
Datatype		
Description	Includes the Input of Rate Code Maintenance Full Details.	



**RATECODE**

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description	Indicates rate code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

**RATECODEDESCRIPTION**

Attribute	Description	
Name	RATECODEDESCRIPTION	
Datatype	String	
Description	Indicates the description of rate code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

**HOLIDAYCCY**

Attribute	Description	
Name	HOLIDAYCCY	
Datatype	String	
Description	Specifies Holiday Currency.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

**PROPAGATIONACROSSBRANCHES**

Attribute	Description	
Name	PROPAGATIONACROSSBRANCHES	
Datatype	String	
Description	Propagate Across Branches	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**MAKERID**

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Specifies the User id who has saved the record.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates the date and time when the user has saved the record.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

## CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Indicates the User id who has authorized the record.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has authorized the booked contract	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

## MODNO

Attribute	Description
Name	MODNO

Datatype	Number	
Description	It indicates the modification number.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	It indicates the status of the record,whether open or Closed.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorized.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Cftm-Tenor-Code-Defn

<b>Attribute</b>	<b>Description</b>	
Name	Cftm-Tenor-Code-Defn	
Datatype		
Description	Includes Tenor code details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	1

**TENORCODE**

Attribute	Description	
Name	TENORCODE	
Datatype	String	
Description	Indicates Tenor code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

**TENORCODEDESCRIPTION**

Attribute	Description	
Name	TENORCODEDESCRIPTION	
Datatype	String	
Description	Specifies the description of Tenor Code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

**UDFDETAILS**

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**FIELD\_NAME**

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

[TOP](#)

## DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

## FIELD\_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

[TOP](#)

## VAL\_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description

Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

<b>Attribute</b>	<b>Description</b>	
Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.8.4.CF-CreateCFRateCodeMaint-Res-PK-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Cftm-Rate-Code-Defn-PK*

*RATECODE*

*Cftm-Rate-Code-Defn-IO*

*RATECODE*

*RATECODEDESCRIPTION*

*HOLIDAYCCY*

*PROPAGATIONACROSSBRANCHES*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

*Cftm-Tenor-Code-Defn*

*TENORCODE*

*TENORCODEDESCRIPTION*



*UDFDETAILS*

*FUNCTIONID*

*FIELD\_NAME*

*DATATYPE*

*FIELD\_VALUE*

*VAL\_TYPE*

*Cftm-Rate-Code-Defn-Full*

*RATECODE*

*RATECODEDESCRIPTION*

*HOLIDAYCCY*

*PROPAGATIONACROSSBRANCHES*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

*Cftm-Tenor-Code-Defn*

*TENORCODE*

*TENORCODEDESCRIPTION*

*UDFDETAILS*

*FUNCTIONID*

*FIELD\_NAME*

*DATATYPE*

*FIELD\_VALUE*

*VAL\_TYPE*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

**FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

**SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description						
Name	SOURCE_OPERATION						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nullable	true
	Attribute	Description					
	minOccurs	0					
nullable	true						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*		
	Restrictions	Description					
pattern	[a-zA-Z_0-9]*						

[TOP](#)

## SOURCE\_USERID

Attribute	Description						
Name	SOURCE_USERID						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nullable	true
	Attribute	Description					
	minOccurs	0					
nullable	true						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*		
	Restrictions	Description					
pattern	[a-zA-Z_0-9]*						

[TOP](#)

## DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
	minOccurs	0			
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
	minOccurs	0			
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## FUNCTIONID

Attribute	Description
-----------	-------------

Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Cftm-Rate-Code-Defn-PK

Attribute	Description
Name	Cftm-Rate-Code-Defn-PK
Datatype	

Description	Includes the Input of Rate Code Maintenance primary key Details.
-------------	--

[TOP](#)

## RATECODE

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description	Indicates Rate Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

## Cftm-Rate-Code-Defn-IO

Attribute	Description
Name	Cftm-Rate-Code-Defn-IO
Datatype	
Description	Includes the Input of Rate Code Maintenance IO Details.

[TOP](#)

## RATECODE

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description	Indicates Rate Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

## RATECODEDESCRIPTION

Attribute	Description	
Name	RATECODEDESCRIPTION	
Datatype	String	
Description	Indicates the description of rate code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

## HOLIDAYCCY

Attribute	Description
Name	HOLIDAYCCY

Datatype	String	
Description	Specifies Holiday Currency.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## PROPAGATIONACROSSBRANCHES

<b>Attribute</b>	<b>Description</b>	
Name	PROPAGATIONACROSSBRANCHES	
Datatype	String	
Description	Propagate Across Branches	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Specifies the User id who has saved the record.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates the date and time when the user has saved the record.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates the User id who has authorized the record.	



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has authorized the booked contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	It indicates the modification number.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	It indicates the status of the record,whether open or Closed.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

**ONCEAUTH**

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorized.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**Cftm-Tenor-Code-Defn**

Attribute	Description	
Name	Cftm-Tenor-Code-Defn	
Datatype		
Description	Includes Tenor code details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	1

**TENORCODE**

Attribute	Description	
Name	TENORCODE	
Datatype	String	
Description	Indicates Tenor code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

**TENORCODEDESCRIPTION**

Attribute	Description	
Name	TENORCODEDESCRIPTION	
Datatype	String	
Description	Specifies the description of Tenor Code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

**UDFDETAILS**

Attribute	Description
-----------	-------------

Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## FIELD\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

[TOP](#)

## DATATYPE

<b>Attribute</b>	<b>Description</b>	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

[TOP](#)

## FIELD\_VALUE

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

[TOP](#)

## VAL\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2
	minLength	0

[TOP](#)

## Cftm-Rate-Code-Defn-Full

<b>Attribute</b>	<b>Description</b>
Name	Cftm-Rate-Code-Defn-Full
Datatype	
Description	Includes the Input of Rate Code Maintenance Full Details.

[TOP](#)

## RATECODE

<b>Attribute</b>	<b>Description</b>	
Name	RATECODE	
Datatype	String	
Description	Indicates Rate Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## RATECODEDESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	RATECODEDESCRIPTION	
Datatype	String	
Description	Indicates the description of rate code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## HOLIDAYCCY

Attribute	Description				
Name	HOLIDAYCCY				
Datatype	String				
Description	Specifies Holiday Currency.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

[TOP](#)

## PROPAGATIONACROSSBRANCHES

Attribute	Description				
Name	PROPAGATIONACROSSBRANCHES				
Datatype	String				
Description	Propagate Across Branches				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	1
	Restrictions	Description			
maxLength	1				

[TOP](#)

## MAKERID

Attribute	Description				
Name	MAKERID				
Datatype	String				
Description	Specifies the User id who has saved the record.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
	Restrictions	Description			
maxLength	12				

[TOP](#)

## MAKERDTSTAMP

Attribute	Description				
Name	MAKERDTSTAMP				
Datatype	String				
Description	Indicates the date and time when the user has saved the record.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>25</td></tr></tbody></table>	Restrictions	Description	maxLength	25
	Restrictions	Description			
maxLength	25				

[TOP](#)

## CHECKERID

Attribute	Description
-----------	-------------

Name	CHECKERID	
Datatype	String	
Description	Indicates the User id who has authorized the record.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has authorized the booked contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	It indicates the modification number.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	It indicates the status of the record,whether open or Closed.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorized.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Cftm-Tenor-Code-Defn

<b>Attribute</b>	<b>Description</b>	
Name	Cftm-Tenor-Code-Defn	
Datatype		
Description	Includes Tenor code details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	1

[TOP](#)

## TENORCODE

<b>Attribute</b>	<b>Description</b>	
Name	TENORCODE	
Datatype	String	
Description	Indicates Tenor code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## TENORCODEDESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	TENORCODEDESCRIPTION	
Datatype	String	
Description	Specifies the description of Tenor Code	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## UDFDETAILS

Attribute	Description						
Name	UDFDETAILS						
Datatype							
Description	Includes User Defined Fields details						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

## FIELD\_NAME

Attribute	Description						
Name	FIELD_NAME						
Datatype	String						
Description	Indicates the User Defined Field Name.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	105	minLength	1
	Restrictions	Description					
	maxLength	105					
minLength	1						

[TOP](#)

## DATATYPE

Attribute	Description				
Name	DATATYPE				
Datatype	String				
Description	Indicates Data Type				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>15</td></tr></tbody></table>	Restrictions	Description	maxLength	15
	Restrictions	Description			
maxLength	15				

[TOP](#)

## FIELD\_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String



Description	Indicates the User Defined Field Value.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

[TOP](#)

## VAL\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2
	minLength	0

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.9.CreateCFRateTypeDefn

Input of Rate Type Maintenance

### 2.9.1.CF-CreateCFRateTypeDefn-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Cftm-Rate-Type-Defn-Full*

*RATETYPE*

*RATETYPEDESCRIPTION*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

*UDFDETAILS*

*FUNCTIONID*

*FIELD\_NAME*

*DATATYPE*

*FIELD\_VALUE*

VAL\_TYPE

FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description
-----------	-------------

Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

[TOP](#)

## Cftm-Rate-Type-Defn-Full

Attribute	Description
-----------	-------------



Name	Cftm-Rate-Type-Defn-Full
Datatype	
Description	Includes the Input of Rate Type Maintenance Full details.

[TOP](#)

## RATETYPE

Attribute	Description	
Name	RATETYPE	
Datatype	String	
Description	Indicates The Rate Type.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## RATETYPEDESCRIPTION

Attribute	Description	
Name	RATETYPEDESCRIPTION	
Datatype	String	
Description	Indicates The Rate Type Description.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

## MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	The User Id who has created\last modified the Rate Type Definition details.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates Date and Stamp when the user hascreated\last modified the Rate Type Definition details.	
Attributes	Attribute	Description
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	The User Id who has Authorized the creation\modification of Rate Type Definition details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates Date and Stamp when the user has Authorized the creation\modification of Rate Type Definition details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number i.e. the number of times Rate Type Definition detail has been modified.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status. A - Authorized U - Unauthorized	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	Indicates the Record Status O - Open C - Close	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates whether Rate Type Definition detail has been Authorized atleast Once.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## FIELD\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

[TOP](#)

## DATATYPE

<b>Attribute</b>	<b>Description</b>	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

[TOP](#)

## FIELD\_VALUE

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

[TOP](#)

## VAL\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2
	minLength	0

[TOP](#)

## 2.9.2.CF-CreateCFRateTypeDefn-Req-IO-MSG.xsd

### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

### *FCUBS\_BODY*

*Cftm-Rate-Type-Defn-IO*

*RATETYPE*

*RATETYPEDESCRIPTION*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

*UDFDETAILS*

*FUNCTIONID*

*FIELD\_NAME*

*DATATYPE*

*FIELD\_VALUE*

*VAL\_TYPE*

### **FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

[TOP](#)

## Cftm-Rate-Type-Defn-IO

Attribute	Description
-----------	-------------

Name	Cftm-Rate-Type-Defn-IO
Datatype	
Description	Includes the Input of Rate Type Maintenance IO details.

[TOP](#)

## RATETYPE

Attribute	Description	
Name	RATETYPE	
Datatype	String	
Description	Indicates The Rate Type.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## RATETYPEDESCRIPTION

Attribute	Description	
Name	RATETYPEDESCRIPTION	
Datatype	String	
Description	Indicates The Rate Type Description.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

## MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	The User Id who has created\last modified the Rate Type Definition details.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates Date and Stamp when the user has created\last modified the Rate Type Definition details.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

**CHECKERID**

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	The User Id who has Authorized the creation\modification of Rate Type Definiton details.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CHECKERDTSTAMP**

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates Date and Stamp when the user has Authorized the creation\modification of Rate Type Defintion details.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number i.e the number of times the Rate Type Definition detail has been modified.	
Attributes	Attribute	Description
	minOccurs	0

**AUTHSTAT**

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status. A - Authorized U - Unauthorized	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**RECSTAT**

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Indicates the Record Status. O - Open C - Close	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**ONCEAUTH**

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates whether the Rate Type Definition detail has been Authorized atleast Once.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**UDFDETAILS**

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**FIELD\_NAME**

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

**DATATYPE**

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

**FIELD\_VALUE**

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

**VAL\_TYPE**

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

### 2.9.3.CF-CreateCFRateTypeDefn-Res-Full-MSG.xsd

*FCUBS\_HEADER*  
*SOURCE*  
*UBSCOMP*  
*MSGID*  
*CORRELID*  
*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*CHOICE*  
*Cftm-Rate-Type-Defn-IO*  
*RATETYPE*  
*RATETYPEDESCRIPTION*  
*MAKERID*  
*MAKERDTSTAMP*  
*CHECKERID*  
*CHECKERDTSTAMP*  
*MODNO*  
*AUTHSTAT*  
*RECSTAT*  
*ONCEAUTH*  
*UDFDETAILS*  
*FUNCTIONID*  
*FIELD\_NAME*  
*DATATYPE*  
*FIELD\_VALUE*  
*VAL\_TYPE*  
*Cftm-Rate-Type-Defn-Full*

RATETYPE  
 RATETYPEDESCRIPTION  
 MAKERID  
 MAKERDTSTAMP  
 CHECKERID  
 CHECKERDTSTAMP  
 MODNO  
 AUTHSTAT  
 RECSTAT  
 ONCEAUTH  
 UDFDETAILS  
     FUNCTIONID  
     FIELD\_NAME  
     DATATYPE  
     FIELD\_VALUE  
     VAL\_TYPE  
 FCUBS\_ERROR\_RESP  
     ERROR  
         ECODE  
         EDESC  
 FCUBS\_WARNING\_RESP  
     WARNING  
         WCODE  
         WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	



Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

**MODULEID**

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

**SERVICE**

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**OPERATION**

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description
Name	ACTION

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**NAME**

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)**VALUE**

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

[TOP](#)**CHOICE**

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)**Cftm-Rate-Type-Defn-IO**

Attribute	Description
Name	Cftm-Rate-Type-Defn-IO
Datatype	
Description	Includes the Input of Rate Type Maintenance IO Details.

[TOP](#)**RATETYPE**

Attribute	Description	
Name	RATETYPE	
Datatype	String	
Description	Indicates The Rate Type.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**RATETYPEDESCRIPTION**

Attribute	Description	
Name	RATETYPEDESCRIPTION	
Datatype	String	
Description	Indicates The Rate Type Description.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

**MAKERID**

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	The User Id who has created\last modified the Rate Type Definition details.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**MAKERDTSTAMP**

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates Date and Stamp when the user has created\last modified the Rate Type Definition details.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

**CHECKERID**

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	The User Id who has Authorized the creation\modification of Rate Type Definiton details.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

## CHECKERDTSTAMP

Attribute	Description				
Name	CHECKERDTSTAMP				
Datatype	String				
Description	Indicates Date and Stamp when the user has Authorized the creation\modification of Rate Type Defintion details.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>25</td></tr></tbody></table>	Restrictions	Description	maxLength	25
	Restrictions	Description			
maxLength	25				

[TOP](#)

## MODNO

Attribute	Description				
Name	MODNO				
Datatype	Number				
Description	Indicates Modification Number i.e the number of times the Rate Type Definition detail has been modified.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## AUTHSTAT

Attribute	Description				
Name	AUTHSTAT				
Datatype	String				
Description	Indicates Authorization Status. A - Authorized U - Unauthorized				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	1
	Restrictions	Description			
maxLength	1				

[TOP](#)

## RECSTAT

Attribute	Description				
Name	RECSTAT				
Datatype	String				
Description	Indicates the Record Status. O - Open C - Close				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	1
	Restrictions	Description			
maxLength	1				

**ONCEAUTH**

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates whether the Rate Type Definition detail has been Authorized atleast Once.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**UDFDETAILS**

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**FIELD\_NAME**

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

**DATATYPE**



Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

## FIELD\_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

[TOP](#)

## VAL\_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

[TOP](#)

## Cftm-Rate-Type-Defn-Full

Attribute	Description
Name	Cftm-Rate-Type-Defn-Full
Datatype	
Description	Includes the Input of Rate Type Maintenance Full Details.

[TOP](#)

## RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String
Description	Indicates The Rate Type.

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## RATETYPEDESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	RATETYPEDESCRIPTION	
Datatype	String	
Description	Indicates The Rate Type Description.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	The User Id who has created\last modified the Rate Type Definition details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates Date and Stamp when the user has created\last modified the Rate Type Definition details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	The User Id who has Authorized the creation\modification of Rate Type Definiton details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates Date and Stamp when the user has Authorized the creation\modification of Rate Type Defintion details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number i.e the number of times the Rate Type Definition detail has been modified.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status. A - Authorized U - Unauthorized	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	Indicates the Record Status. O - Open C - Close	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates whether the Rate Type Definition detail has been Authorized atleast Once.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## FIELD\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

[TOP](#)

## DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

## FIELD\_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

[TOP](#)

## VAL\_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description	
Name	WCODE	
Datatype	String	
Description		

**WDESC**

<b>Attribute</b>	<b>Description</b>
Name	WDESC
Datatype	String
Description	

## 2.9.4.CF-CreateCFRateTypeDefn-Res-PK-MSG.xsd

*FCUBS\_HEADER*  
*SOURCE*  
*UBSCOMP*  
*MSGID*  
*CORRELID*  
*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*CHOICE*  
*Cftm-Rate-Type-Defn-PK*  
*RATETYPE*  
*Cftm-Rate-Type-Defn-IO*  
*RATETYPE*  
*RATETYPEDESCRIPTION*  
*MAKERID*  
*MAKERDTSTAMP*  
*CHECKERID*  
*CHECKERDTSTAMP*  
*MODNO*  
*AUTHSTAT*  
*RECSTAT*  
*ONCEAUTH*  
*UDFDETAILS*  
*FUNCTIONID*  
*FIELD\_NAME*  
*DATATYPE*  
*FIELD\_VALUE*



VAL\_TYPE  
 Cftm-Rate-Type-Defn-Full  
 RATETYPE  
 RATETYPEDESCRIPTION  
 MAKERID  
 MAKERDTSTAMP  
 CHECKERID  
 CHECKERDTSTAMP  
 MODNO  
 AUTHSTAT  
 RECSTAT  
 ONCEAUTH  
 UDFDETAILS  
 FUNCTIONID  
 FIELD\_NAME  
 DATATYPE  
 FIELD\_VALUE  
 VAL\_TYPE  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description
Name	UBSCOMP

Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

**MODULEID**

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

**SERVICE**

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**OPERATION**

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description
Name	ACTION

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**NAME**

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)**VALUE**

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

[TOP](#)**CHOICE**

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)**Cftm-Rate-Type-Defn-PK**

Attribute	Description
Name	Cftm-Rate-Type-Defn-PK
Datatype	
Description	Includes the Input of Rate Type Maintenance primary key Details.

[TOP](#)**RATETYPE**

Attribute	Description	
Name	RATETYPE	
Datatype	String	
Description	Indicates The Rate Type.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**Cftm-Rate-Type-Defn-IO**

Attribute	Description
Name	Cftm-Rate-Type-Defn-IO
Datatype	
Description	Includes the Input of Rate Type Maintenance IO Details.

**RATETYPE**

Attribute	Description	
Name	RATETYPE	
Datatype	String	
Description	Indicates The Rate Type.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**RATETYPEDESCRIPTION**

Attribute	Description	
Name	RATETYPEDESCRIPTION	
Datatype	String	
Description	Indicates The Rate Type Description.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

**MAKERID**

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	The User Id who has created\last modified the Rate Type Definition details.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**MAKERDTSTAMP**

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Date and Stamp when the user has created\last modified the Rate Type Definition details.

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	The User Id who has Authorized the creation\modification of Rate Type Definiton details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates Date and Stamp when the user has Authorized the creation\modification of Rate Type Defintion details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number i.e the number of times the Rate Type Definition detail has been modified.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status. A - Authorized U - Unauthorized	



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	Indicates the Record Status. O - Open C - Close	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates whether the Rate Type Definition detail has been Authorized atleast Once.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## FIELD\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

[TOP](#)

## DATATYPE

<b>Attribute</b>	<b>Description</b>	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

[TOP](#)

## FIELD\_VALUE

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

[TOP](#)

## VAL\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2
	minLength	0

**Cftm-Rate-Type-Defn-Full**

Attribute	Description
Name	Cftm-Rate-Type-Defn-Full
Datatype	
Description	Includes the Input of Rate Type Maintenance Full Details.

**RATETYPE**

Attribute	Description	
Name	RATETYPE	
Datatype	String	
Description	Indicates The Rate Type.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**RATETYPEDESCRIPTION**

Attribute	Description	
Name	RATETYPEDESCRIPTION	
Datatype	String	
Description	Indicates The Rate Type Description.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

**MAKERID**

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	The User Id who has created\last modified the Rate Type Definition details.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**MAKERDTSTAMP**

Attribute	Description
Name	MAKERDTSTAMP
Datatype	String
Description	Indicates Date and Stamp when the user has created\last modified the Rate Type Definition details.

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	The User Id who has Authorized the creation\modification of Rate Type Definiton details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates Date and Stamp when the user has Authorized the creation\modification of Rate Type Defintion details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number i.e the number of times the Rate Type Definition detail has been modified.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status. A - Authorized U - Unauthorized	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	Indicates the Record Status. O - Open C - Close	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates whether the Rate Type Definition detail has been Authorized atleast Once.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## FIELD\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

[TOP](#)

## DATATYPE

<b>Attribute</b>	<b>Description</b>	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

[TOP](#)

## FIELD\_VALUE

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

[TOP](#)

## VAL\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2
	minLength	0

[TOP](#)**FCUBS\_ERROR\_RESP**

Attribute		Description
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**ERROR**

Attribute		Description
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**ECODE**

Attribute		Description
Name	ECODE	
Datatype	String	
Description		

[TOP](#)**EDESC**

Attribute		Description
Name	EDESC	
Datatype	String	
Description		

[TOP](#)**FCUBS\_WARNING\_RESP**

Attribute		Description
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**WARNING**

Attribute	Description
-----------	-------------

Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)



## 2.10.CreateFLTRTDefn

Input of Floating rate Maintenance

### 2.10.1.CF-CreateFLTRTDefn-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Cftms-Rate-Code-Details-Full*

*RATECODE*

*RATEDESC*

*BRANCHCODE*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

*Cftms-Rate-Ccy-Details*

*CCYCODE*

*Cftms-Float-Rate-Master-Details*

*AMNTSLAB*

EFFECTDATE  
 BRWLENDINDCR  
 Cftms-Float-Rate-Detail-Description  
 TENORTO  
 INTRATE  
 UDFDETAILS  
 FUNCTIONID  
 FIELD\_NAME  
 DATATYPE  
 FIELD\_VALUE  
 VAL\_TYPE

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

**MODULEID**

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

**SERVICE**

Attribute	Description
Name	SERVICE
Datatype	String

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

[TOP](#)

## Cftms-Rate-Code-Details-Full

Attribute	Description
Name	Cftms-Rate-Code-Details-Full
Datatype	
Description	Includes the Input of Floating rate Maintenance Details.

[TOP](#)

## RATECODE

Attribute	Description				
Name	RATECODE				
Datatype	String				
Description	Specifies The Rate Code.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>10</td></tr></tbody></table>	Restrictions	Description	maxLength	10
	Restrictions	Description			
maxLength	10				

[TOP](#)

## RATEDESC

Attribute	Description				
Name	RATEDESC				
Datatype	String				
Description	Specifies The Rate Description.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>105</td></tr></tbody></table>	Restrictions	Description	maxLength	105
	Restrictions	Description			
maxLength	105				

[TOP](#)

## BRANCHCODE

Attribute	Description				
Name	BRANCHCODE				
Datatype	String				
Description	Specifies The Branch Code.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

**MAKERID**

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	The User id who has booked the contract	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**MAKERDTSTAMP**

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has booked the contract	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

**CHECKERID**

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Specifies The Checker Identification.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CHECKERDTSTAMP**

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has authorized the booked contract	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

**MODNO**



Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Specifies The Modification Number.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Specifies The Authorization Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Specifies The Record Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorized.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## Cftms-Rate-Ccy-Details

Attribute	Description
Name	Cftms-Rate-Ccy-Details
Datatype	
Description	Includes Rate-Currency details

Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## CCYCODE

<b>Attribute</b>	<b>Description</b>	
Name	CCYCODE	
Datatype	String	
Description	Specifies The Currency Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## Cftms-Float-Rate-Master-Details

<b>Attribute</b>	<b>Description</b>	
Name	Cftms-Float-Rate-Master-Details	
Datatype		
Description	Includes Rate details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## AMNTSLAB

<b>Attribute</b>	<b>Description</b>	
Name	AMNTSLAB	
Datatype	Number	
Description	Specifies The Amount Slab.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## EFFECTDATE

<b>Attribute</b>	<b>Description</b>	
Name	EFFECTDATE	
Datatype	Date	
Description	Specifies The Effective Date.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## BRWLENDINDCR

<b>Attribute</b>	<b>Description</b>	
Name	BRWLENDINDCR	

Datatype	String	
Description	Specifies The Borrow Lend Indicator 1 : Borrow : B 2 : Lend : L 3 : MID : M	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	B,L,M

[TOP](#)

## Cftms-Float-Rate-Detail-Description

<b>Attribute</b>	<b>Description</b>	
Name	Cftms-Float-Rate-Detail-Description	
Datatype		
Description	Specifies The Tenor and Interest Rate Details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## TENORTO

<b>Attribute</b>	<b>Description</b>	
Name	TENORTO	
Datatype	Number	
Description	Specifies The Tenor.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## INTRATE

<b>Attribute</b>	<b>Description</b>	
Name	INTRATE	
Datatype	Number	
Description	Specifies The Interest Rate.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

**FUNCTIONID**

Attribute		Description
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**FIELD\_NAME**

Attribute		Description
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

**DATATYPE**

Attribute		Description
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

**FIELD\_VALUE**

Attribute		Description
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

## VAL\_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

[TOP](#)

## 2.10.2.CF-CreateFLTRTDefn-Req-IO-MSG.xsd

### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

### *FCUBS\_BODY*

*Cftms-Rate-Code-Details-IO*

*RATECODE*

*RATEDESC*

*BRANCHCODE*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

*Cftms-Rate-Ccy-Details*

*CCYCODE*

*Cftms-Float-Rate-Master-Details*

*AMNTSLAB*

*EFFECTDATE*

*BRWLENDINDCR*

*Cftms-Float-Rate-Detail-Description*

TENORTO  
 INTRATE  
 UDFDETAILS  
 FUNCTIONID  
 FIELD\_NAME  
 DATATYPE  
 FIELD\_VALUE  
 VAL\_TYPE

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		



Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute		Description
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute		Description
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute		Description
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute		Description
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

Attribute		Description
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

[TOP](#)

## Cftms-Rate-Code-Details-IO

Attribute	Description
Name	Cftms-Rate-Code-Details-IO
Datatype	
Description	Includes the Input of Floating rate Maintenance details.

[TOP](#)

## RATECODE

Attribute	Description				
Name	RATECODE				
Datatype	String				
Description	Specifies The Rate Code.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>10</td></tr></tbody></table>	Restrictions	Description	maxLength	10
	Restrictions	Description			
maxLength	10				

[TOP](#)

## RATEDESC

Attribute	Description				
Name	RATEDESC				
Datatype	String				
Description	Specifies The Rate Description.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>105</td></tr></tbody></table>	Restrictions	Description	maxLength	105
	Restrictions	Description			
maxLength	105				

[TOP](#)

## BRANCHCODE

Attribute	Description				
Name	BRANCHCODE				
Datatype	String				
Description	Specifies The Branch Code.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

**MAKERID**

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	The User id who has booked the contract	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**MAKERDTSTAMP**

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has booked the contract	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

**CHECKERID**

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	The User id who has authorized the booked contract	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CHECKERDTSTAMP**

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has authorized the booked contract	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Specifies The Modification Number.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Specifies The Authorization Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Specifies The Record Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorized.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## Cftms-Rate-Ccy-Details

Attribute	Description
Name	Cftms-Rate-Ccy-Details
Datatype	
Description	Includes Rate-Currency details

Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## CCYCODE

<b>Attribute</b>	<b>Description</b>	
Name	CCYCODE	
Datatype	String	
Description	Specifies The Currency Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## Cftms-Float-Rate-Master-Details

<b>Attribute</b>	<b>Description</b>	
Name	Cftms-Float-Rate-Master-Details	
Datatype		
Description	Includes Rate details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## AMNTSLAB

<b>Attribute</b>	<b>Description</b>	
Name	AMNTSLAB	
Datatype	Number	
Description	Specifies The Amount Slab.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## EFFECTDATE

<b>Attribute</b>	<b>Description</b>	
Name	EFFECTDATE	
Datatype	Date	
Description	Specifies The Effective Date.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## BRWLENDINDCR

<b>Attribute</b>	<b>Description</b>
Name	BRWLENDINDCR

Datatype	String	
Description	Specifies The Borrow Lend Indicator 1 : Borrow : B 2 : Lend : L 3 : MID : M	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	B,L,M

[TOP](#)

## Cftms-Float-Rate-Detail-Description

<b>Attribute</b>	<b>Description</b>	
Name	Cftms-Float-Rate-Detail-Description	
Datatype		
Description	Specifies The Tenor and Interest Rate Details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## TENORTO

<b>Attribute</b>	<b>Description</b>	
Name	TENORTO	
Datatype	Number	
Description	Specifies The Tenor.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## INTRATE

<b>Attribute</b>	<b>Description</b>	
Name	INTRATE	
Datatype	Number	
Description	Specifies The Interest Rate.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0



**FUNCTIONID**

Attribute		Description
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**FIELD\_NAME**

Attribute		Description
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

**DATATYPE**

Attribute		Description
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

**FIELD\_VALUE**

Attribute		Description
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

## VAL\_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

[TOP](#)

### 2.10.3.CF-CreateFLTRTDefn-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Cftms-Rate-Code-Details-PK*

*RATECODE*

*BRANCHCODE*

*Cftms-Rate-Code-Details-IO*

*RATECODE*

*RATEDESC*

*BRANCHCODE*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

*Cftms-Rate-Ccy-Details*

*CCYCODE*

*Cftms-Float-Rate-Master-Details*

AMNTSLAB  
EFFECTDATE  
BRWLENDINDCR  
*Cftms-Float-Rate-Detail-Description*

TENORTO

INTRATE

TENORTO

INTRATE

AMNTSLAB  
EFFECTDATE  
BRWLENDINDCR  
*Cftms-Float-Rate-Detail-Description*

TENORTO

INTRATE

TENORTO

INTRATE

UDFDETAILS

FUNCTIONID

FIELD\_NAME

DATATYPE

FIELD\_VALUE

VAL\_TYPE

*Cftms-Rate-Code-Details-Full*

RATECODE

RATEDESC

BRANCHCODE

MAKERID

MAKERDTSTAMP

CHECKERID

CHECKERDTSTAMP

MODNO

AUTHSTAT

RECSTAT

ONCEAUTH

*Cftms-Rate-Ccy-Details*

CCYCODE

*Cftms-Float-Rate-Master-Details*

AMNTSLAB

EFFECTDATE

BRWLENDINDCR

*Cftms-Float-Rate-Detail-Description*

TENORTO

INTRATE

TENORTO

INTRATE  
 AMNTSLAB  
 EFFECTDATE  
 BRWLENDINDCR  
*Cftms-Float-Rate-Detail-Description*  
 TENORTO  
 INTRATE  
 TENORTO  
 INTRATE  
 UDFDETAILS  
 FUNCTIONID  
 FIELD\_NAME  
 DATATYPE  
 FIELD\_VALUE  
 VAL\_TYPE  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

**MODULEID**

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

**SERVICE**

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**OPERATION**

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description
Name	ACTION



Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**NAME**

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)**VALUE**

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

[TOP](#)**CHOICE**

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)**Cftms-Rate-Code-Details-PK**

Attribute	Description
Name	Cftms-Rate-Code-Details-PK
Datatype	
Description	Includes the Input of Floating rate Maintenance primary key Details.

[TOP](#)**RATECODE**

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description	Specifies The Rate Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

**BRANCHCODE**

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description	Specifies The Branch Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

**Cftms-Rate-Code-Details-IO**

Attribute	Description	
Name	Cftms-Rate-Code-Details-IO	
Datatype		
Description	Includes the Input of Floating rate Maintenance IO Details.	

**RATECODE**

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description	Specifies The Rate Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

**RATEDESC**

Attribute	Description	
Name	RATEDESC	
Datatype	String	
Description	Specifies The Rate Description.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

**BRANCHCODE**

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description	Specifies The Branch Code.	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	The User id who has booked the contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has booked the contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	The User id who has authorized the booked contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has authorized the booked contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Specifies The Modification Number.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Specifies The Authorization Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	Specifies The Record Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorized.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Cftms-Rate-Ccy-Details

Attribute	Description	
Name	Cftms-Rate-Ccy-Details	
Datatype		
Description	Includes Rate-Currency details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## CCYCODE

Attribute	Description	
Name	CCYCODE	
Datatype	String	
Description	Specifies The Currency Code.	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## Cftms-Float-Rate-Master-Details

Attribute	Description	
Name	Cftms-Float-Rate-Master-Details	
Datatype		
Description	Includes Rate details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## AMNTSLAB

Attribute	Description	
Name	AMNTSLAB	
Datatype	Number	
Description	Specifies The Amount Slab.	
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

## EFFECTDATE

Attribute	Description	
Name	EFFECTDATE	
Datatype	Date	
Description	Specifies The Effective Date.	
Attributes	Attribute	Description
	minOccurs	1

**BRWLENDINDCR**

Attribute	Description	
Name	BRWLENDINDCR	
Datatype	String	
Description	Specifies The Borrow Lend Indicator 1 : Borrow : B 2 : Lend : L 3 : MID : M	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	B,L,M

**Cftms-Float-Rate-Detail-Description**

Attribute	Description	
Name	Cftms-Float-Rate-Detail-Description	
Datatype		
Description	Specifies The Tenor and Interest Rate Details.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**TENORTO**

Attribute	Description	
Name	TENORTO	
Datatype	Number	
Description	Specifies The Tenor.	
Attributes	Attribute	Description
	minOccurs	0

**INTRATE**

Attribute	Description	
Name	INTRATE	
Datatype	Number	
Description	Specifies The Interest Rate.	
Attributes	Attribute	Description
	minOccurs	0

**TENORTO**

Attribute	Description
-----------	-------------

Name	TENORTO	
Datatype	Number	
Description	Specifies The Tenor.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## INTRATE

<b>Attribute</b>	<b>Description</b>	
Name	INTRATE	
Datatype	Number	
Description	Specifies The Interest Rate.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AMNTSLAB

<b>Attribute</b>	<b>Description</b>	
Name	AMNTSLAB	
Datatype	Number	
Description	Specifies The Amount Slab.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## EFFECTDATE

<b>Attribute</b>	<b>Description</b>	
Name	EFFECTDATE	
Datatype	Date	
Description	Specifies The Effective Date.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## BRWLENDINDCR

<b>Attribute</b>	<b>Description</b>	
Name	BRWLENDINDCR	
Datatype	String	
Description	Specifies The Borrow Lend Indicator 1 : Borrow : B 2 : Lend : L 3 : MID : M	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	B,L,M



**Cftms-Float-Rate-Detail-Description**

Attribute	Description	
Name	Cftms-Float-Rate-Detail-Description	
Datatype		
Description	Specifies The Tenor and Interest Rate Details.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**TENORTO**

Attribute	Description	
Name	TENORTO	
Datatype	Number	
Description	Specifies The Tenor.	
Attributes	Attribute	Description
	minOccurs	0

**INTRATE**

Attribute	Description	
Name	INTRATE	
Datatype	Number	
Description	Specifies The Interest Rate.	
Attributes	Attribute	Description
	minOccurs	0

**TENORTO**

Attribute	Description	
Name	TENORTO	
Datatype	Number	
Description	Specifies The Tenor.	
Attributes	Attribute	Description
	minOccurs	0

**INTRATE**

Attribute	Description	
Name	INTRATE	
Datatype	Number	
Description	Specifies The Interest Rate.	
Attributes	Attribute	Description
	minOccurs	0

**UDFDETAILS**

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**FIELD\_NAME**

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

**DATATYPE**

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

**FIELD\_VALUE**

Attribute	Description
-----------	-------------

Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

[TOP](#)

## VAL\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2
	minLength	0

[TOP](#)

## Cftms-Rate-Code-Details-Full

<b>Attribute</b>	<b>Description</b>
Name	Cftms-Rate-Code-Details-Full
Datatype	
Description	Includes the Input of Floating rate Maintenance Full Details.

[TOP](#)

## RATECODE

<b>Attribute</b>	<b>Description</b>	
Name	RATECODE	
Datatype	String	
Description	Specifies The Rate Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## RATEDESC

<b>Attribute</b>	<b>Description</b>	
Name	RATEDESC	
Datatype	String	
Description	Specifies The Rate Description.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## BRANCHCODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCHCODE	
Datatype	String	
Description	Specifies The Branch Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	The User id who has booked the contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has booked the contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	The User id who has authorized the booked contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

**CHECKERDTSTAMP**

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has authorized the booked contract	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Specifies The Modification Number.	
Attributes	Attribute	Description
	minOccurs	0

**AUTHSTAT**

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Specifies The Authorization Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**RECSTAT**

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Specifies The Record Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**ONCEAUTH**

Attribute	Description
Name	ONCEAUTH

Datatype	String	
Description	Indicates Once Authorized.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Cftms-Rate-Ccy-Details

<b>Attribute</b>	<b>Description</b>	
Name	Cftms-Rate-Ccy-Details	
Datatype		
Description	Includes Rate-Currency details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## CCYCODE

<b>Attribute</b>	<b>Description</b>	
Name	CCYCODE	
Datatype	String	
Description	Specifies The Currency Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## Cftms-Float-Rate-Master-Details

<b>Attribute</b>	<b>Description</b>	
Name	Cftms-Float-Rate-Master-Details	
Datatype		
Description	Includes Rate details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## AMNTSLAB

<b>Attribute</b>	<b>Description</b>	
Name	AMNTSLAB	
Datatype	Number	
Description	Specifies The Amount Slab.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

**EFFECTDATE**

Attribute	Description	
Name	EFFECTDATE	
Datatype	Date	
Description	Specifies The Effective Date.	
Attributes	Attribute	Description
	minOccurs	1

**BRWLENDINDCR**

Attribute	Description	
Name	BRWLENDINDCR	
Datatype	String	
Description	Specifies The Borrow Lend Indicator 1 : Borrow : B 2 : Lend : L 3 : MID : M	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	B,L,M

**Cftms-Float-Rate-Detail-Description**

Attribute	Description	
Name	Cftms-Float-Rate-Detail-Description	
Datatype		
Description	Specifies The Tenor and Interest Rate Details.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**TENORTO**

Attribute	Description	
Name	TENORTO	
Datatype	Number	
Description	Specifies The Tenor.	
Attributes	Attribute	Description
	minOccurs	0

**INTRATE**

Attribute	Description
-----------	-------------

Name	INTRATE	
Datatype	Number	
Description	Specifies The Interest Rate.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TENORTO

<b>Attribute</b>	<b>Description</b>	
Name	TENORTO	
Datatype	Number	
Description	Specifies The Tenor.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## INTRATE

<b>Attribute</b>	<b>Description</b>	
Name	INTRATE	
Datatype	Number	
Description	Specifies The Interest Rate.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AMNTSLAB

<b>Attribute</b>	<b>Description</b>	
Name	AMNTSLAB	
Datatype	Number	
Description	Specifies The Amount Slab.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## EFFECTDATE

<b>Attribute</b>	<b>Description</b>	
Name	EFFECTDATE	
Datatype	Date	
Description	Specifies The Effective Date.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## BRWLENDINDCR

<b>Attribute</b>	<b>Description</b>	
Name	BRWLENDINDCR	
Datatype	String	



Description	Specifies The Borrow Lend Indicator 1 : Borrow : B 2 : Lend : L 3 : MID : M	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	B,L,M

[TOP](#)

## Cftms-Float-Rate-Detail-Description

<b>Attribute</b>	<b>Description</b>	
Name	Cftms-Float-Rate-Detail-Description	
Datatype		
Description	Specifies The Tenor and Interest Rate Details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## TENORTO

<b>Attribute</b>	<b>Description</b>	
Name	TENORTO	
Datatype	Number	
Description	Specifies The Tenor.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## INTRATE

<b>Attribute</b>	<b>Description</b>	
Name	INTRATE	
Datatype	Number	
Description	Specifies The Interest Rate.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TENORTO

<b>Attribute</b>	<b>Description</b>	
Name	TENORTO	
Datatype	Number	
Description	Specifies The Tenor.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## INTRATE

Attribute	Description				
Name	INTRATE				
Datatype	Number				
Description	Specifies The Interest Rate.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## UDFDETAILS

Attribute	Description						
Name	UDFDETAILS						
Datatype							
Description	Includes User Defined Fields details						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

## FIELD\_NAME

Attribute	Description						
Name	FIELD_NAME						
Datatype	String						
Description	Indicates the User Defined Field Name.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	105	minLength	1
	Restrictions	Description					
	maxLength	105					
minLength	1						

[TOP](#)

## DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

[TOP](#)

## FIELD\_VALUE

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

[TOP](#)

## VAL\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2
	minLength	0

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.10.4.CF-CreateFLTRTDefn-Res-PK-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Cftms-Rate-Code-Details-PK*

*RATECODE*

*BRANCHCODE*

*Cftms-Rate-Code-Details-IO*

*RATECODE*

*RATEDESC*

*BRANCHCODE*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

*Cftms-Rate-Ccy-Details*

*CCYCODE*

*Cftms-Float-Rate-Master-Details*

AMNTSLAB  
EFFECTDATE  
BRWLENDINDCR  
*Cftms-Float-Rate-Detail-Description*  
TENORTO  
INTRATE  
TENORTO  
INTRATE

AMNTSLAB  
EFFECTDATE  
BRWLENDINDCR  
*Cftms-Float-Rate-Detail-Description*  
TENORTO  
INTRATE  
TENORTO  
INTRATE

UDFDETAILS  
FUNCTIONID  
FIELD\_NAME  
DATATYPE  
FIELD\_VALUE  
VAL\_TYPE

*Cftms-Rate-Code-Details-Full*

RATECODE  
RATEDESC  
BRANCHCODE  
MAKERID  
MAKERDTSTAMP  
CHECKERID  
CHECKERDTSTAMP  
MODNO  
AUTHSTAT  
RECSTAT  
ONCEAUTH

*Cftms-Rate-Ccy-Details*

CCYCODE

*Cftms-Float-Rate-Master-Details*

AMNTSLAB  
EFFECTDATE  
BRWLENDINDCR  
*Cftms-Float-Rate-Detail-Description*  
TENORTO  
INTRATE  
TENORTO

INTRATE  
 AMNTSLAB  
 EFFECTDATE  
 BRWLENDINDCR  
*Cftms-Float-Rate-Detail-Description*  
 TENORTO  
 INTRATE  
 TENORTO  
 INTRATE  
 UDFDETAILS  
 FUNCTIONID  
 FIELD\_NAME  
 DATATYPE  
 FIELD\_VALUE  
 VAL\_TYPE  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}



**MODULEID**

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

**SERVICE**

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**OPERATION**

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description
Name	ACTION

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**NAME**

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)**VALUE**

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

[TOP](#)**CHOICE**

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)**Cftms-Rate-Code-Details-PK**

Attribute	Description
Name	Cftms-Rate-Code-Details-PK
Datatype	
Description	Includes the Input of Floating rate Maintenance primary key details.

[TOP](#)**RATECODE**

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description	Specifies The Rate Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

**BRANCHCODE**

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description	Specifies The Branch Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

**Cftms-Rate-Code-Details-IO**

Attribute	Description	
Name	Cftms-Rate-Code-Details-IO	
Datatype		
Description	Includes the Input of Floating rate Maintenance IO details.	

**RATECODE**

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description	Specifies The Rate Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

**RATEDESC**

Attribute	Description	
Name	RATEDESC	
Datatype	String	
Description	Specifies The Rate Description.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

**BRANCHCODE**

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description	Specifies The Branch Code.	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	The User id who has booked the contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has booked the contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	The User id who has authorized the booked contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has authorized the booked contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Specifies The Modification Number.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Specifies The Authorization Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	Specifies The Record Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorized.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Cftms-Rate-Ccy-Details

Attribute	Description	
Name	Cftms-Rate-Ccy-Details	
Datatype		
Description	Includes Rate-Currency details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## CCYCODE

Attribute	Description	
Name	CCYCODE	
Datatype	String	
Description	Specifies The Currency Code.	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## Cftms-Float-Rate-Master-Details

Attribute	Description	
Name	Cftms-Float-Rate-Master-Details	
Datatype		
Description	Includes Rate details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## AMNTSLAB

Attribute	Description	
Name	AMNTSLAB	
Datatype	Number	
Description	Specifies The Amount Slab.	
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

## EFFECTDATE

Attribute	Description	
Name	EFFECTDATE	
Datatype	Date	
Description	Specifies The Effective Date.	
Attributes	Attribute	Description
	minOccurs	1



**BRWLENDINDCR**

Attribute	Description	
Name	BRWLENDINDCR	
Datatype	String	
Description	Specifies The Borrow Lend Indicator 1 : Borrow : B 2 : Lend : L 3 : MID : M	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	B,L,M

**Cftms-Float-Rate-Detail-Description**

Attribute	Description	
Name	Cftms-Float-Rate-Detail-Description	
Datatype		
Description	Specifies The Tenor and Interest Rate Details.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**TENORTO**

Attribute	Description	
Name	TENORTO	
Datatype	Number	
Description	Specifies The Tenor.	
Attributes	Attribute	Description
	minOccurs	0

**INTRATE**

Attribute	Description	
Name	INTRATE	
Datatype	Number	
Description	Specifies The Interest Rate.	
Attributes	Attribute	Description
	minOccurs	0

**TENORTO**

Attribute	Description
-----------	-------------

Name	TENORTO	
Datatype	Number	
Description	Specifies The Tenor.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## INTRATE

<b>Attribute</b>	<b>Description</b>	
Name	INTRATE	
Datatype	Number	
Description	Specifies The Interest Rate.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AMNTSLAB

<b>Attribute</b>	<b>Description</b>	
Name	AMNTSLAB	
Datatype	Number	
Description	Specifies The Amount Slab.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## EFFECTDATE

<b>Attribute</b>	<b>Description</b>	
Name	EFFECTDATE	
Datatype	Date	
Description	Specifies The Effective Date.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## BRWLENDINDCR

<b>Attribute</b>	<b>Description</b>	
Name	BRWLENDINDCR	
Datatype	String	
Description	Specifies The Borrow Lend Indicator	
	1 : Borrow : B	
	2 : Lend : L	
		3 : MID : M
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	B,L,M

**Cftms-Float-Rate-Detail-Description**

Attribute	Description	
Name	Cftms-Float-Rate-Detail-Description	
Datatype		
Description	Specifies The Tenor and Interest Rate Details.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**TENORTO**

Attribute	Description	
Name	TENORTO	
Datatype	Number	
Description	Specifies The Tenor.	
Attributes	Attribute	Description
	minOccurs	0

**INTRATE**

Attribute	Description	
Name	INTRATE	
Datatype	Number	
Description	Specifies The Interest Rate.	
Attributes	Attribute	Description
	minOccurs	0

**TENORTO**

Attribute	Description	
Name	TENORTO	
Datatype	Number	
Description	Specifies The Tenor.	
Attributes	Attribute	Description
	minOccurs	0

**INTRATE**

Attribute	Description	
Name	INTRATE	
Datatype	Number	
Description	Specifies The Interest Rate.	
Attributes	Attribute	Description
	minOccurs	0

**UDFDETAILS**

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**FIELD\_NAME**

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

**DATATYPE**

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

**FIELD\_VALUE**

Attribute	Description
-----------	-------------

Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

[TOP](#)

## VAL\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2
	minLength	0

[TOP](#)

## Cftms-Rate-Code-Details-Full

<b>Attribute</b>	<b>Description</b>
Name	Cftms-Rate-Code-Details-Full
Datatype	
Description	Includes the Input of Floating rate Maintenance Full details.

[TOP](#)

## RATECODE

<b>Attribute</b>	<b>Description</b>	
Name	RATECODE	
Datatype	String	
Description	Specifies The Rate Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## RATEDESC

<b>Attribute</b>	<b>Description</b>	
Name	RATEDESC	
Datatype	String	
Description	Specifies The Rate Description.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## BRANCHCODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCHCODE	
Datatype	String	
Description	Specifies The Branch Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	The User id who has booked the contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has booked the contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	The User id who has authorized the booked contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

**CHECKERDTSTAMP**

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has authorized the booked contract	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Specifies The Modification Number.	
Attributes	Attribute	Description
	minOccurs	0

**AUTHSTAT**

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Specifies The Authorization Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**RECSTAT**

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Specifies The Record Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**ONCEAUTH**

Attribute	Description
Name	ONCEAUTH

Datatype	String	
Description	Indicates Once Authorized.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Cftms-Rate-Ccy-Details

<b>Attribute</b>	<b>Description</b>	
Name	Cftms-Rate-Ccy-Details	
Datatype		
Description	Includes Rate-Currency details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## CCYCODE

<b>Attribute</b>	<b>Description</b>	
Name	CCYCODE	
Datatype	String	
Description	Specifies The Currency Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## Cftms-Float-Rate-Master-Details

<b>Attribute</b>	<b>Description</b>	
Name	Cftms-Float-Rate-Master-Details	
Datatype		
Description	Includes Rate details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## AMNTSLAB

<b>Attribute</b>	<b>Description</b>	
Name	AMNTSLAB	
Datatype	Number	
Description	Specifies The Amount Slab.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1



**EFFECTDATE**

Attribute	Description	
Name	EFFECTDATE	
Datatype	Date	
Description	Specifies The Effective Date.	
Attributes	Attribute	Description
	minOccurs	1

**BRWLENDINDCR**

Attribute	Description	
Name	BRWLENDINDCR	
Datatype	String	
Description	Specifies The Borrow Lend Indicator 1 : Borrow : B 2 : Lend : L 3 : MID : M	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	B,L,M

**Cftms-Float-Rate-Detail-Description**

Attribute	Description	
Name	Cftms-Float-Rate-Detail-Description	
Datatype		
Description	Specifies The Tenor and Interest Rate Details.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**TENORTO**

Attribute	Description	
Name	TENORTO	
Datatype	Number	
Description	Specifies The Tenor.	
Attributes	Attribute	Description
	minOccurs	0

**INTRATE**

Attribute	Description
-----------	-------------

Name	INTRATE	
Datatype	Number	
Description	Specifies The Interest Rate.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TENORTO

<b>Attribute</b>	<b>Description</b>	
Name	TENORTO	
Datatype	Number	
Description	Specifies The Tenor.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## INTRATE

<b>Attribute</b>	<b>Description</b>	
Name	INTRATE	
Datatype	Number	
Description	Specifies The Interest Rate.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AMNTSLAB

<b>Attribute</b>	<b>Description</b>	
Name	AMNTSLAB	
Datatype	Number	
Description	Specifies The Amount Slab.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## EFFECTDATE

<b>Attribute</b>	<b>Description</b>	
Name	EFFECTDATE	
Datatype	Date	
Description	Specifies The Effective Date.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## BRWLENDINDCR

<b>Attribute</b>	<b>Description</b>	
Name	BRWLENDINDCR	
Datatype	String	

Description	Specifies The Borrow Lend Indicator 1 : Borrow : B 2 : Lend : L 3 : MID : M	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	B,L,M

[TOP](#)

## Cftms-Float-Rate-Detail-Description

<b>Attribute</b>	<b>Description</b>	
Name	Cftms-Float-Rate-Detail-Description	
Datatype		
Description	Specifies The Tenor and Interest Rate Details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## TENORTO

<b>Attribute</b>	<b>Description</b>	
Name	TENORTO	
Datatype	Number	
Description	Specifies The Tenor.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## INTRATE

<b>Attribute</b>	<b>Description</b>	
Name	INTRATE	
Datatype	Number	
Description	Specifies The Interest Rate.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TENORTO

<b>Attribute</b>	<b>Description</b>	
Name	TENORTO	
Datatype	Number	
Description	Specifies The Tenor.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## INTRATE

Attribute	Description				
Name	INTRATE				
Datatype	Number				
Description	Specifies The Interest Rate.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## UDFDETAILS

Attribute	Description						
Name	UDFDETAILS						
Datatype							
Description	Includes User Defined Fields details						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

## FIELD\_NAME

Attribute	Description						
Name	FIELD_NAME						
Datatype	String						
Description	Indicates the User Defined Field Name.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	105	minLength	1
	Restrictions	Description					
	maxLength	105					
minLength	1						

[TOP](#)

## DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

[TOP](#)

## FIELD\_VALUE

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

[TOP](#)

## VAL\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2
	minLength	0

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)**ECODE**

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)**EDESC**

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)**FCUBS\_WARNING\_RESP**

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**WARNING**

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)**WCODE**

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)**WDESC**

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.11.CreateFloatRateMaint

CreateFloatRateMaint

### 2.11.1.CF-CreateFloatRateMaint-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Rate-Code-Full*

*RATE\_CODE*

*RATEDESC*

*BRANCH\_CODE*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*Rate-Ccy*

*RATE\_CODE*

*CCY\_CODE*

*BRANCH\_CODE*

*Fload-Rate*

*RATE\_CODE*  
*CCY\_CODE*  
*AMOUNT\_SLAB1*  
*EFFECTIVE\_DATE*  
*BRANCH\_CODE*  
*BORROW\_LEND\_IND*

*Ftrate-Detail*

*RATE\_CODE*  
*CCY\_CODE*  
*AMOUNT\_SLAB*  
*EFFECTIVE\_DATE*  
*BRANCH\_CODE*  
*BORROW\_LEND\_IND*  
*TENOR\_TO1*  
*INTEREST\_RATE*  
*RATECODEC*  
*CCYCODEC*  
*AMOUNTSLABC*  
*EFFECTIVEDATEC*  
*BRANCHCODEC*  
*BORROWLENDINDC*  
*TENORTOC*  
*TDMAXRATE*  
*TDPREDIFF*

*UDFDETAILS*

*FLDNAM*  
*FLDVAL*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

**SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

**UBSCOMP**



Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		

Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

[TOP](#)

## Rate-Code-Full

Attribute	Description
Name	Rate-Code-Full
Datatype	
Description	

[TOP](#)

## RATE\_CODE

Attribute	Description	
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## RATEDESC

Attribute	Description
-----------	-------------

Name	RATEDESC	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

**Rate-Ccy**

Attribute	Description	
Name	Rate-Ccy	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**RATE\_CODE**

Attribute	Description	
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

**CCY\_CODE**

Attribute	Description	
Name	CCY_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

**BRANCH\_CODE**

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

**Flood-Rate**

Attribute	Description
-----------	-------------



Name	Flood-Rate	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## RATE\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## CCY\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	CCY_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## AMOUNT\_SLAB1

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNT_SLAB1	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## EFFECTIVE\_DATE

<b>Attribute</b>	<b>Description</b>	
Name	EFFECTIVE_DATE	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

**BRANCH\_CODE**

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

**BORROW\_LEND\_IND**

Attribute	Description	
Name	BORROW_LEND_IND	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	B,L,M

**Filtrate-Detail**

Attribute	Description	
Name	Filtrate-Detail	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**RATE\_CODE**

Attribute	Description	
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

**CCY\_CODE**

Attribute	Description
-----------	-------------

Name	CCY_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## AMOUNT\_SLAB

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNT_SLAB	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## EFFECTIVE\_DATE

<b>Attribute</b>	<b>Description</b>	
Name	EFFECTIVE_DATE	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## BORROW\_LEND\_IND

<b>Attribute</b>	<b>Description</b>	
Name	BORROW_LEND_IND	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	B,L,M

**TENOR\_TO1**

Attribute		Description
Name	TENOR_TO1	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

**INTEREST\_RATE**

Attribute		Description
Name	INTEREST_RATE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

**RATECODEC**

Attribute		Description
Name	RATECODEC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

**CCYCODEC**

Attribute		Description
Name	CCYCODEC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

**AMOUNTSLABC**

Attribute		Description
Name	AMOUNTSLABC	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## EFFECTIVEDATEC

Attribute	Description	
Name	EFFECTIVEDATEC	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## BRANCHCODEC

Attribute	Description	
Name	BRANCHCODEC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## BORROWLENDINDC

Attribute	Description	
Name	BORROWLENDINDC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## TENORTOC

Attribute	Description	
Name	TENORTOC	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## TDMAXRATE

Attribute	Description
Name	TDMAXRATE

Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TDPREDIFF

<b>Attribute</b>	<b>Description</b>	
Name	TDPREDIFF	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

[TOP](#)

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

[TOP](#)

## 2.11.2.CF-CreateFloatRateMaint-Req-IO-MSG.xsd

### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

### *FCUBS\_BODY*

*Rate-Code-IO*

*RATE\_CODE*

*RATEDESC*

*BRANCH\_CODE*

*Rate-Ccy*

*RATE\_CODE*

*CCY\_CODE*

*BRANCH\_CODE*

*Fload-Rate*

*RATE\_CODE*

*CCY\_CODE*

*AMOUNT\_SLAB1*

*EFFECTIVE\_DATE*

*BRANCH\_CODE*

*BORROW\_LEND\_IND*

*Filtrate-Detail*

*RATE\_CODE*

*CCY\_CODE*

*AMOUNT\_SLAB*

EFFECTIVE\_DATE  
 BRANCH\_CODE  
 BORROW\_LEND\_IND  
 TENOR\_TO1  
 INTEREST\_RATE  
 RATECODEC  
 CCYCODEC  
 AMOUNTSLABC  
 EFFECTIVEDATEC  
 BRANCHCODEC  
 BORROWLENDINDC  
 TENORTOC  
 TDMAXRATE  
 TDPREDIFF

UDFDETAILS

FLDNAM  
 FLDVAL

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

**SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

**UBSCOMP**

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

**MSGID**

Attribute	Description
Name	MSGID



Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

[TOP](#)

## Rate-Code-IO

Attribute	Description
Name	Rate-Code-IO
Datatype	
Description	

[TOP](#)

## RATE\_CODE

Attribute	Description				
Name	RATE_CODE				
Datatype	String				
Description					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>1</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	1
Attribute	Description				
minOccurs	1				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>10</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	10
Restrictions	Description				
maxLength	10				

[TOP](#)

## RATEDESC

Attribute	Description				
Name	RATEDESC				
Datatype	String				
Description					
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>105</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

[TOP](#)

## BRANCH\_CODE

Attribute	Description
-----------	-------------

Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## Rate-Ccy

<b>Attribute</b>	<b>Description</b>	
Name	Rate-Ccy	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## RATE\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## CCY\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	CCY_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## Fload-Rate

<b>Attribute</b>	<b>Description</b>	
Name	Fload-Rate	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## RATE\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## CCY\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	CCY_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## AMOUNT\_SLAB1

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNT_SLAB1	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## EFFECTIVE\_DATE

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	EFFECTIVE_DATE	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## BORROW\_LEND\_IND

<b>Attribute</b>	<b>Description</b>	
Name	BORROW_LEND_IND	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	B,L,M

[TOP](#)

## Filtrate-Detail

<b>Attribute</b>	<b>Description</b>	
Name	Filtrate-Detail	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## RATE\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10



[TOP](#)**CCY\_CODE**

Attribute		Description
Name	CCY_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)**AMOUNT\_SLAB**

Attribute		Description
Name	AMOUNT_SLAB	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**EFFECTIVE\_DATE**

Attribute		Description
Name	EFFECTIVE_DATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)**BRANCH\_CODE**

Attribute		Description
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)**BORROW\_LEND\_IND**

Attribute		Description
Name	BORROW_LEND_IND	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	B,L,M

[TOP](#)

## TENOR\_TO1

<b>Attribute</b>	<b>Description</b>	
Name	TENOR_TO1	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## INTEREST\_RATE

<b>Attribute</b>	<b>Description</b>	
Name	INTEREST_RATE	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## RATECODEC

<b>Attribute</b>	<b>Description</b>	
Name	RATECODEC	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## CCYCODEC

<b>Attribute</b>	<b>Description</b>	
Name	CCYCODEC	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## AMOUNTSLABC

Attribute	Description	
Name	AMOUNTSLABC	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## EFFECTIVEDATEC

Attribute	Description	
Name	EFFECTIVEDATEC	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## BRANCHCODEC

Attribute	Description	
Name	BRANCHCODEC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## BORROWLENDINDC

Attribute	Description	
Name	BORROWLENDINDC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## TENORTOC

Attribute	Description	
Name	TENORTOC	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

**TDMAXRATE**

Attribute	Description	
Name	TDMAXRATE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

**TDPREDIFF**

Attribute	Description	
Name	TDPREDIFF	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

**UDFDETAILS**

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**FLDNAM**

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

**FLDVAL**

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

[TOP](#)

### 2.11.3.CF-CreateFloatRateMaint-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Rate-Code-Full*

*RATE\_CODE*

*RATEDESC*

*BRANCH\_CODE*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*Rate-Ccy*

*RATE\_CODE*

*CCY\_CODE*

*BRANCH\_CODE*

*Fload-Rate*

*RATE\_CODE*

*CCY\_CODE*

*AMOUNT\_SLAB1*

EFFECTIVE\_DATE  
 BRANCH\_CODE  
 BORROW\_LEND\_IND  
 Fltrate-Detail  
 RATE\_CODE  
 CCY\_CODE  
 AMOUNT\_SLAB  
 EFFECTIVE\_DATE  
 BRANCH\_CODE  
 BORROW\_LEND\_IND  
 TENOR\_TO1  
 INTEREST\_RATE  
 RATECODEC  
 CCYCODEC  
 AMOUNTSLABC  
 EFFECTIVEDATEC  
 BRANCHCODEC  
 BORROWLENDINDC  
 TENORTOC  
 TDMAXRATE  
 TDPREDIFF

UDFDETAILS

FLDNAM

FLDVAL

FCUBS\_ERROR\_RESP

ERROR

ECODE

EDESC

FCUBS\_WARNING\_RESP

WARNING

WCODE

WDESC

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

**SOURCE**

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

<b>Attribute</b>	<b>Description</b>	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)



## BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description							
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
	Restrictions	Description					
	length	3					
pattern	[a-zA-Z_0-9]{3}						

[TOP](#)

## MODULEID

Attribute	Description						
Name	MODULEID						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nullable	true
	Attribute	Description					
	minOccurs	0					
nullable	true						

[TOP](#)

## SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	nullable	true
	Attribute	Description			
nullable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	nullable	true
	Attribute	Description			
nullable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about Full Response	

[TOP](#)

## Rate-Code-Full

Attribute	Description	
Name	Rate-Code-Full	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## RATE\_CODE

Attribute	Description	
Name	RATE_CODE	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## RATEDESC

<b>Attribute</b>	<b>Description</b>	
Name	RATEDESC	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## Rate-Ccy

Attribute	Description	
Name	Rate-Ccy	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## RATE\_CODE

Attribute	Description	
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

## CCY\_CODE

Attribute	Description	
Name	CCY_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## BRANCH\_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## Fload-Rate

<b>Attribute</b>	<b>Description</b>	
Name	Fload-Rate	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## RATE\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## CCY\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	CCY_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## AMOUNT\_SLAB1

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNT_SLAB1	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1



**EFFECTIVE\_DATE**

Attribute	Description	
Name	EFFECTIVE_DATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	1

**BRANCH\_CODE**

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

**BORROW\_LEND\_IND**

Attribute	Description	
Name	BORROW_LEND_IND	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	B,L,M

**Filtrate-Detail**

Attribute	Description	
Name	Filtrate-Detail	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**RATE\_CODE**

Attribute	Description	
Name	RATE_CODE	
Datatype	String	

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## CCY\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	CCY_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## AMOUNT\_SLAB

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNT_SLAB	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## EFFECTIVE\_DATE

<b>Attribute</b>	<b>Description</b>	
Name	EFFECTIVE_DATE	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## BORROW\_LEND\_IND

Attribute	Description				
Name	BORROW_LEND_IND				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>B,L,M</td></tr></tbody></table>	Restrictions	Description	enumeration	B,L,M
	Restrictions	Description			
enumeration	B,L,M				

[TOP](#)

## TENOR\_TO1

Attribute	Description				
Name	TENOR_TO1				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				

[TOP](#)

## INTEREST\_RATE

Attribute	Description				
Name	INTEREST_RATE				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## RATECODEC

Attribute	Description				
Name	RATECODEC				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>10</td></tr></tbody></table>	Restrictions	Description	maxLength	10
	Restrictions	Description			
maxLength	10				

[TOP](#)

## CCYCODEC

Attribute	Description
Name	CCYCODEC
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## AMOUNTSLABC

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNTSLABC	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## EFFECTIVEDATEC

<b>Attribute</b>	<b>Description</b>	
Name	EFFECTIVEDATEC	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## BRANCHCODEC

<b>Attribute</b>	<b>Description</b>	
Name	BRANCHCODEC	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## BORROWLENDINDC

<b>Attribute</b>	<b>Description</b>	
Name	BORROWLENDINDC	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## TENORTOC

Attribute	Description	
Name	TENORTOC	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## TDMAXRATE

Attribute	Description	
Name	TDMAXRATE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## TDPREDIFF

Attribute	Description	
Name	TDPREDIFF	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

[TOP](#)

## FLDVAL

Attribute	Description						
Name	FLDVAL						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></tbody></table>	Restrictions	Description	maxLength	255	minLength	0
	Restrictions	Description					
	maxLength	255					
minLength	0						

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description				
Name	FCUBS_ERROR_RESP				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## ERROR

Attribute	Description				
Name	ERROR				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
	Attribute	Description			
maxOccurs	unbounded				

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description
-----------	-------------

Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.11.4.CF-CreateFloatRateMaint-Res-PK-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Rate-Code-PK*

*RATE\_CODE*

*BRANCH\_CODE*

*Rate-Code-IO*

*RATE\_CODE*

*RATEDESC*

*BRANCH\_CODE*

*Rate-Ccy*

*RATE\_CODE*

*CCY\_CODE*

*BRANCH\_CODE*

*Fload-Rate*

*RATE\_CODE*

*CCY\_CODE*

*AMOUNT\_SLAB1*

*EFFECTIVE\_DATE*

*BRANCH\_CODE*

*BORROW\_LEND\_IND*



*Filtrate-Detail*

RATE\_CODE  
CCY\_CODE  
AMOUNT\_SLAB  
EFFECTIVE\_DATE  
BRANCH\_CODE  
BORROW\_LEND\_IND  
TENOR\_TO1  
INTEREST\_RATE  
RATECODEC  
CCYCODEC  
AMOUNTSLABC  
EFFECTIVEDATEC  
BRANCHCODEC  
BORROWLENDINDC  
TENORTOC  
TDMAXRATE  
TDPREDIFF

UDFDETAILS

FLDNAM

FLDVAL

FCUBS\_ERROR\_RESP

ERROR

ECODE

EDESC

FCUBS\_WARNING\_RESP

WARNING

WCODE

WDESC

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

**SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**UBSCOMP**

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description
-----------	-------------

Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MSGSTAT**

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

**PASSWORD**

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

**ADDL**

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

**PARAM**

Attribute	Description
-----------	-------------

Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Rate-Code-PK

Attribute	Description	
Name	Rate-Code-PK	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## RATE\_CODE

Attribute	Description
Name	RATE_CODE

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## Rate-Code-IO

<b>Attribute</b>	<b>Description</b>	
Name	Rate-Code-IO	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## RATE\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## RATEDESC

<b>Attribute</b>	<b>Description</b>	
Name	RATEDESC	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## Rate-Ccy

<b>Attribute</b>	<b>Description</b>	
Name	Rate-Ccy	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## RATE\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## CCY\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	CCY_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)



## BRANCH\_CODE

Attribute	Description				
Name	BRANCH_CODE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

[TOP](#)

## Fload-Rate

Attribute	Description						
Name	Fload-Rate						
Datatype							
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## RATE\_CODE

Attribute	Description				
Name	RATE_CODE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>10</td></tr></tbody></table>	Restrictions	Description	maxLength	10
	Restrictions	Description			
maxLength	10				

[TOP](#)

## CCY\_CODE

Attribute	Description				
Name	CCY_CODE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

[TOP](#)

## AMOUNT\_SLAB1

Attribute	Description
Name	AMOUNT_SLAB1

Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## EFFECTIVE\_DATE

<b>Attribute</b>	<b>Description</b>	
Name	EFFECTIVE_DATE	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## BORROW\_LEND\_IND

<b>Attribute</b>	<b>Description</b>	
Name	BORROW_LEND_IND	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	B,L,M

[TOP](#)

## Filtrate-Detail

<b>Attribute</b>	<b>Description</b>	
Name	Filtrate-Detail	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## RATE\_CODE

Attribute	Description				
Name	RATE_CODE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>10</td></tr></tbody></table>	Restrictions	Description	maxLength	10
	Restrictions	Description			
maxLength	10				

[TOP](#)

## CCY\_CODE

Attribute	Description				
Name	CCY_CODE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

[TOP](#)

## AMOUNT\_SLAB

Attribute	Description				
Name	AMOUNT_SLAB				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## EFFECTIVE\_DATE

Attribute	Description				
Name	EFFECTIVE_DATE				
Datatype	Date				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				

[TOP](#)

## BRANCH\_CODE

Attribute	Description
Name	BRANCH_CODE
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## BORROW\_LEND\_IND

<b>Attribute</b>	<b>Description</b>	
Name	BORROW_LEND_IND	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	B,L,M

[TOP](#)

## TENOR\_TO1

<b>Attribute</b>	<b>Description</b>	
Name	TENOR_TO1	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## INTEREST\_RATE

<b>Attribute</b>	<b>Description</b>	
Name	INTEREST_RATE	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## RATECODEC

<b>Attribute</b>	<b>Description</b>	
Name	RATECODEC	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## CCYCODEC

Attribute	Description	
Name	CCYCODEC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## AMOUNTSLABC

Attribute	Description	
Name	AMOUNTSLABC	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## EFFECTIVEDATEC

Attribute	Description	
Name	EFFECTIVEDATEC	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## BRANCHCODEC

Attribute	Description	
Name	BRANCHCODEC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## BORROWLENDINDC

Attribute	Description	
Name	BORROWLENDINDC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## TENORTOC

Attribute	Description	
Name	TENORTOC	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## TDMAXRATE

Attribute	Description	
Name	TDMAXRATE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## TDPREDIFF

Attribute	Description	
Name	TDPREDIFF	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description		

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

[TOP](#)

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	
Description		

[TOP](#)**FCUBS\_WARNING\_RESP**

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**WARNING**

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**WCODE**

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)**WDESC**

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)



## 2.12.DeleteCFFloatRateMaint

Deletion of Floating rate Maintenance

### 2.12.1.CF-DeleteCFFloatRateMaint-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Cftm-Rate-Master-Full*

*RATECODE*

*RATECODEDESCRIPTION*

*TENORCODE*

*TENORCODEDESCRIPTION*

*CCYCODE*

*CCYNAME*

*EFFECTIVEDATE*

*RATESOURCE*

*RATESOURCEDESCRIPTION*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

[RECSTAT](#)  
[ONCEAUTH](#)  
[Cftm-Rate-Detail](#)  
[RATETYPE](#)  
[RATETYPEDESCRIPTION](#)  
[INTERESTRATE](#)  
[UDFDETAILS](#)  
[FUNCTIONID](#)  
[FIELD\\_NAME](#)  
[DATATYPE](#)  
[FIELD\\_VALUE](#)  
[VAL\\_TYPE](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description						
Name	MSGID						
Datatype	String						
Description							
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

## DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	

Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

[TOP](#)

## Cftm-Rate-Master-Full

Attribute	Description
Name	Cftm-Rate-Master-Full
Datatype	
Description	Includes the Deletion of Floating rate Maintenance Full details.

[TOP](#)

## RATECODE

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description	Specifies The Rate Code.	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

## RATECODEDESCRIPTION

Attribute	Description	
Name	RATECODEDESCRIPTION	
Datatype	String	
Description	Specifies The Rate Code Description.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

## TENORCODE

Attribute	Description	
Name	TENORCODE	
Datatype	String	
Description	Specifies The Tenor Code.	
Attributes	Attribute	Description
	minOccurs	1

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## TENORCODEDESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	TENORCODEDESCRIPTION	
Datatype	String	
Description	Specifies The Tenor Code Description.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## CCYCODE

<b>Attribute</b>	<b>Description</b>	
Name	CCYCODE	
Datatype	String	
Description	Specifies The Currency Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## CCYNAME

<b>Attribute</b>	<b>Description</b>	
Name	CCYNAME	
Datatype	String	
Description	Specifies The Currency Code Description.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## EFFECTIVEDATE

<b>Attribute</b>	<b>Description</b>	
Name	EFFECTIVEDATE	
Datatype	Date	
Description	Specifies The Effective Date.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## RATESOURCE



Attribute	Description	
Name	RATESOURCE	
Datatype	String	
Description	Specifies The Rate Source.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

## RATESOURCEDESCRIPTION

Attribute	Description	
Name	RATESOURCEDESCRIPTION	
Datatype	String	
Description	Specifies The Rate Source Description.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

## MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	The User id who has booked the contract	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has booked the contract	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

## CHECKERID

Attribute	Description
Name	CHECKERID

Datatype	String	
Description	The User id who has authorized the booked contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has authorized the booked contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Specifies The Modification Number.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Specifies The Authorization Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	Specifies The Record Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorized.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## Cftm-Rate-Detail

Attribute	Description	
Name	Cftm-Rate-Detail	
Datatype		
Description	Indicates The Rate Details.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## RATETYPE

Attribute	Description	
Name	RATETYPE	
Datatype	String	
Description	Specifies The Rate Type.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## RATETYPEDESCRIPTION

Attribute	Description	
Name	RATETYPEDESCRIPTION	
Datatype	String	
Description	Specifies The Rate Type Description.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

## INTERESTRATE

Attribute	Description				
Name	INTERESTRATE				
Datatype	Number				
Description	Specifies The Interest Rate.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## UDFDETAILS

Attribute	Description						
Name	UDFDETAILS						
Datatype							
Description	Indicates The UDF Details.						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

## FIELD\_NAME

Attribute	Description						
Name	FIELD_NAME						
Datatype	String						
Description	Indicates the User Defined Field Name.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	105	minLength	1
	Restrictions	Description					
	maxLength	105					
minLength	1						

[TOP](#)

## DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

[TOP](#)

## FIELD\_VALUE

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

[TOP](#)

## VAL\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2
	minLength	0

[TOP](#)

2.12.2.CF-DeleteCFFloatRateMaint-Req-IO-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Cftm-Rate-Master-IO*

*RATECODE*

*TENORCODE*

*CCYCODE*

*EFFECTIVEDATE*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

**SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**UBSCOMP**

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description
-----------	-------------

Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true



Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute		Description
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MSGSTAT**

Attribute		Description
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

**PASSWORD**

Attribute		Description
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

**ADDL**

Attribute		Description
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

**PARAM**

Attribute	Description
-----------	-------------

Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

[TOP](#)

## Cftm-Rate-Master-IO

Attribute	Description
Name	Cftm-Rate-Master-IO
Datatype	
Description	Includes the Deletion of Floating rate Maintenance primary key Details.

[TOP](#)

## RATECODE

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description	Specifies The Rate Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## TENORCODE

Attribute	Description				
Name	TENORCODE				
Datatype	String				
Description	Specifies The Tenor Code.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
	Restrictions	Description			
maxLength	12				

[TOP](#)

## CCYCODE

Attribute	Description				
Name	CCYCODE				
Datatype	String				
Description	Specifies The Currency Code.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

[TOP](#)

## EFFECTIVEDATE

Attribute	Description
Name	EFFECTIVEDATE
Datatype	Date
Description	Specifies The Effective Date.

[TOP](#)

## 2.12.3.CF-DeleteCFFloatRateMaint-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Cftm-Rate-Master-IO*

*RATECODE*

*TENORCODE*

*CCYCODE*

*EFFECTIVEDATE*

*Cftm-Rate-Master-Full*

*RATECODE*

*RATECODEDESCRIPTION*

*TENORCODE*

*TENORCODEDESCRIPTION*

*CCYCODE*

*CCYNAME*

*EFFECTIVEDATE*

*RATESOURCE*

*RATESOURCEDESCRIPTION*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

CHECKERDTSTAMP  
 MODNO  
 AUTHSTAT  
 RECSTAT  
 ONCEAUTH  
 Cftm-Rate-Detail  
     RATETYPE  
     RATETYPEDESCRIPTION  
     INTERESTRATE  
 UDFDETAILS  
     FUNCTIONID  
     FIELD\_NAME  
     DATATYPE  
     FIELD\_VALUE  
     VAL\_TYPE  
 FCUBS\_ERROR\_RESP  
     ERROR  
     ECODE  
     EDESC  
 FCUBS\_WARNING\_RESP  
     WARNING  
     WCODE  
     WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)**MODULEID**

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

[TOP](#)**SERVICE**

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)**OPERATION**

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)**SOURCE\_USERID**



Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description
Name	ACTION

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**NAME**

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)**VALUE**

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

[TOP](#)**CHOICE**

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)**Cftm-Rate-Master-IO**

Attribute	Description
Name	Cftm-Rate-Master-IO
Datatype	
Description	This gives the Deletion of Floating Rate maintenance PK details

[TOP](#)**RATECODE**

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description	Specifies The Rate Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

**TENORCODE**

Attribute		Description
Name	TENORCODE	
Datatype	String	
Description	Specifies The Tenor Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CCYCODE**

Attribute		Description
Name	CCYCODE	
Datatype	String	
Description	Specifies The Currency Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

**EFFECTIVEDATE**

Attribute		Description
Name	EFFECTIVEDATE	
Datatype	Date	
Description	Specifies The Effective Date.	

**Cftm-Rate-Master-Full**

Attribute		Description
Name	Cftm-Rate-Master-Full	
Datatype		
Description	Includes the Deletion of Floating rate Maintenance Full Details.	

**RATECODE**

Attribute		Description
Name	RATECODE	
Datatype	String	
Description	Specifies The Rate Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

**RATECODEDESCRIPTION**

Attribute	Description	
Name	RATECODEDESCRIPTION	
Datatype	String	
Description	Specifies The Rate Code Description.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

**TENORCODE**

Attribute	Description	
Name	TENORCODE	
Datatype	String	
Description	Specifies The Tenor Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**TENORCODEDESCRIPTION**

Attribute	Description	
Name	TENORCODEDESCRIPTION	
Datatype	String	
Description	Specifies The Tenor Code Description.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

**CCYCODE**

Attribute	Description	
Name	CCYCODE	
Datatype	String	
Description	Specifies The Currency Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

**CCYNAME**

Attribute	Description	
Name	CCYNAME	
Datatype	String	
Description	Specifies The Currency Code Description.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

## EFFECTIVEDATE

Attribute	Description	
Name	EFFECTIVEDATE	
Datatype	Date	
Description	Specifies The Effective Date.	

[TOP](#)

## RATESOURCE

Attribute	Description	
Name	RATESOURCE	
Datatype	String	
Description	Specifies The Rate Source.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

## RATESOURCEDESCRIPTION

Attribute	Description	
Name	RATESOURCEDESCRIPTION	
Datatype	String	
Description	Specifies The Rate Source Description.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

## MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	The User id who has booked the contract	
Attributes	Attribute	Description
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has booked the contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	The User id who has authorized the booked contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has authorized the booked contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Specifies The Modification Number.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Specifies The Authorization Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Specifies The Record Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorized.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## Cftm-Rate-Detail

Attribute	Description	
Name	Cftm-Rate-Detail	
Datatype		
Description	Indicates The Rate Details.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String



Description	Specifies The Rate Type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## RATETYPEDESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	RATETYPEDESCRIPTION	
Datatype	String	
Description	Specifies The Rate Type Description.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## INTERESTRATE

<b>Attribute</b>	<b>Description</b>	
Name	INTERESTRATE	
Datatype	Number	
Description	Specifies The Interest Rate.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description	Indicates The UDF Details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

**FIELD\_NAME**

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

**DATATYPE**

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

**FIELD\_VALUE**

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

**VAL\_TYPE**

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

## FCUBS\_ERROR\_RESP

Attribute	Description						
Name	FCUBS_ERROR_RESP						
Datatype							
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## ERROR

Attribute	Description				
Name	ERROR				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
	Attribute	Description			
maxOccurs	unbounded				

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## WARNING

Attribute	Description
Name	WARNING
Datatype	

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.12.4.CF-DeleteCFFloatRateMaint-Res-PK-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Cftm-Rate-Master-IO*

*RATECODE*

*TENORCODE*

*CCYCODE*

*EFFECTIVEDATE*

*Cftm-Rate-Master-PK*

*RATECODE*

*TENORCODE*

*CCYCODE*

*EFFECTIVEDATE*

*Cftm-Rate-Master-Full*

*RATECODE*

*RATECODEDESCRIPTION*

*TENORCODE*

*TENORCODEDESCRIPTION*

*CCYCODE*

*CCYNAME*

*EFFECTIVEDATE*

RATESOURCE  
 RATESOURCEDESCRIPTION  
 MAKERID  
 MAKERDTSTAMP  
 CHECKERID  
 CHECKERDTSTAMP  
 MODNO  
 AUTHSTAT  
 RECSTAT  
 ONCEAUTH  
 Cftm-Rate-Detail  
     RATETYPE  
     RATETYPEDESCRIPTION  
     INTERESTRATE  
 UDFDETAILS  
     FUNCTIONID  
     FIELD\_NAME  
     DATATYPE  
     FIELD\_VALUE  
     VAL\_TYPE  
 FCUBS\_ERROR\_RESP  
     ERROR  
         ECODE  
         EDESC  
 FCUBS\_WARNING\_RESP  
     WARNING  
         WCODE  
         WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description
Name	BRANCH
Datatype	String

Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*



**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Cftm-Rate-Master-IO

Attribute	Description
Name	Cftm-Rate-Master-IO
Datatype	
Description	Includes the Deletion of Floating rate Maintenance IO details.

[TOP](#)

## RATECODE

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description	Specifies The Rate Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## TENORCODE

<b>Attribute</b>	<b>Description</b>	
Name	TENORCODE	
Datatype	String	
Description	Specifies The Tenor Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CCYCODE

<b>Attribute</b>	<b>Description</b>	
Name	CCYCODE	
Datatype	String	
Description	Specifies The Currency Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## EFFECTIVEDATE

<b>Attribute</b>	<b>Description</b>	
Name	EFFECTIVEDATE	
Datatype	Date	
Description	Specifies The Effective Date.	

[TOP](#)

## Cftm-Rate-Master-PK

<b>Attribute</b>	<b>Description</b>	
Name	Cftm-Rate-Master-PK	
Datatype		
Description	Includes the Deletion of Floating rate Maintenance primary Key details.	

[TOP](#)

## RATECODE

<b>Attribute</b>	<b>Description</b>	
Name	RATECODE	
Datatype	String	
Description	Specifies The Rate Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## TENORCODE

<b>Attribute</b>	<b>Description</b>	
Name	TENORCODE	
Datatype	String	
Description	Specifies The Tenor Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CCYCODE

<b>Attribute</b>	<b>Description</b>	
Name	CCYCODE	
Datatype	String	
Description	Specifies The Currency Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## EFFECTIVEDATE

<b>Attribute</b>	<b>Description</b>	
Name	EFFECTIVEDATE	
Datatype	Date	
Description	Specifies The Effective Date.	

[TOP](#)

## Cftm-Rate-Master-Full

<b>Attribute</b>	<b>Description</b>	
Name	Cftm-Rate-Master-Full	
Datatype		
Description	Includes the Deletion of Floating rate Maintenance Full details.	

[TOP](#)

## RATECODE

<b>Attribute</b>	<b>Description</b>	
Name	RATECODE	
Datatype	String	
Description	Specifies The Rate Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## RATECODEDESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	RATECODEDESCRIPTION	
Datatype	String	
Description	Specifies The Rate Code Description.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## TENORCODE

<b>Attribute</b>	<b>Description</b>	
Name	TENORCODE	
Datatype	String	
Description	Specifies The Tenor Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## TENORCODEDESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	TENORCODEDESCRIPTION	
Datatype	String	
Description	Specifies The Tenor Code Description.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## CCYCODE

<b>Attribute</b>	<b>Description</b>	
Name	CCYCODE	
Datatype	String	
Description	Specifies The Currency Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

**CCYNAME**

Attribute	Description	
Name	CCYNAME	
Datatype	String	
Description	Specifies The Currency Code Description.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

**EFFECTIVEDATE**

Attribute	Description	
Name	EFFECTIVEDATE	
Datatype	Date	
Description	Specifies The Effective Date.	

**RATESOURCE**

Attribute	Description	
Name	RATESOURCE	
Datatype	String	
Description	Specifies The Rate Source.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

**RATESOURCEDESCRIPTION**

Attribute	Description	
Name	RATESOURCEDESCRIPTION	
Datatype	String	
Description	Specifies The Rate Source Description.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

**MAKERID**

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	The User id who has booked the contract	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has booked the contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	The User id who has authorized the booked contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has authorized the booked contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Specifies The Modification Number.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



**AUTHSTAT**

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Specifies The Authorization Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**RECSTAT**

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Specifies The Record Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**ONCEAUTH**

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorized.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**Cftm-Rate-Detail**

Attribute	Description	
Name	Cftm-Rate-Detail	
Datatype		
Description	Indicates The Rate Details.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**RATETYPE**

Attribute	Description
-----------	-------------

Name	RATETYPE	
Datatype	String	
Description	Specifies The Rate Type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## RATETYPEDESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	RATETYPEDESCRIPTION	
Datatype	String	
Description	Specifies The Rate Type Description.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## INTERESTRATE

<b>Attribute</b>	<b>Description</b>	
Name	INTERESTRATE	
Datatype	Number	
Description	Specifies The Interest Rate.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description	Indicates The UDF Details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## FIELD\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

[TOP](#)

## DATATYPE

<b>Attribute</b>	<b>Description</b>	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

[TOP](#)

## FIELD\_VALUE

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

[TOP](#)

## VAL\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2
	minLength	0

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description
-----------	-------------

Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.13.DeleteCFRateCodeMaint

Deletion of Rate Code Maintenance

### 2.13.1.CF-DeleteCFRateCodeMaint-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Cftm-Rate-Code-Defn-Full*

*RATECODE*

*RATECODEDESCRIPTION*

*HOLIDAYCCY*

*PROPAGATIONACROSSBRANCHES*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

*Cftm-Tenor-Code-Defn*

*TENORCODE*

*TENORCODEDESCRIPTION*

UDFDETAILS  
 FUNCTIONID  
 FIELD\_NAME  
 DATATYPE  
 FIELD\_VALUE  
 VAL\_TYPE

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description						
Name	MSGID						
Datatype	String						
Description							
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nullable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	nullable	true
	Attribute	Description					
	minOccurs	0					
nullable	true						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*		
	Restrictions	Description					
pattern	[a-zA-Z_0-9]*						

[TOP](#)

## CORRELID

Attribute	Description
Name	CORRELID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*



**OPERATION**

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTITRIPID**

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description
-----------	-------------

Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about FullRequest	

**Cftm-Rate-Code-Defn-Full**

Attribute	Description
Name	Cftm-Rate-Code-Defn-Full
Datatype	
Description	Includes CF-Rate Code Maintenance Deletion details

**RATECODE**

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description	Indicates Rate Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

**RATECODEDESCRIPTION**

Attribute	Description	
Name	RATECODEDESCRIPTION	
Datatype	String	
Description	Indicates the description of rate code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

**HOLIDAYCCY**

Attribute	Description	
Name	HOLIDAYCCY	
Datatype	String	
Description	Specifies Holiday Currency .	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

**PROPAGATIONACROSSBRANCHES**

Attribute	Description
Name	PROPAGATIONACROSSBRANCHES
Datatype	String
Description	Propagate Across Branches

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Specifies the User id who has saved the record.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates the date and time when the user has saved the record.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates the User id who has authorized the record.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has authorized the booked contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	It indicates the modification number.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	It indicates the status of the record,whether open or Closed.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorized.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Cftm-Tenor-Code-Defn

Attribute	Description	
Name	Cftm-Tenor-Code-Defn	
Datatype		
Description	Includes Tenor code details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## TENORCODE

Attribute	Description	
Name	TENORCODE	
Datatype	String	
Description	Indicates the tenor code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

## TENORCODEDESCRIPTION

Attribute	Description	
Name	TENORCODEDESCRIPTION	
Datatype	String	
Description	Indicates the description of tenor code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

## UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## FIELD\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

[TOP](#)

## DATATYPE

<b>Attribute</b>	<b>Description</b>	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

[TOP](#)

## FIELD\_VALUE

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

[TOP](#)

## VAL\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2
	minLength	0

[TOP](#)

2.13.2.CF-DeleteCFRateCodeMaint-Req-IO-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Cftm-Rate-Code-Defn-IO*

*RATECODE*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

**SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

**UBSCOMP**

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		

Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

[TOP](#)

## Cftm-Rate-Code-Defn-IO

Attribute	Description
Name	Cftm-Rate-Code-Defn-IO
Datatype	
Description	Includes CF-Rate Code Maintenance Deletion-IO details

[TOP](#)

## RATECODE

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description	Indicates Rate Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

### 2.13.3.CF-DeleteCFRateCodeMaint-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Cftm-Rate-Code-Defn-IO*

*RATECODE*

*Cftm-Rate-Code-Defn-Full*

*RATECODE*

*RATECODEDESCRIPTION*

*HOLIDAYCCY*

*PROPAGATIONACROSSBRANCHES*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

*Cftm-Tenor-Code-Defn*

*TENORCODE*

*TENORCODEDESCRIPTION*



UDFDETAILS  
 FUNCTIONID  
 FIELD\_NAME  
 DATATYPE  
 FIELD\_VALUE  
 VAL\_TYPE  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

**SERVICE**

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**OPERATION**

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description
-----------	-------------

Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Cftm-Rate-Code-Defn-IO

Attribute	Description
Name	Cftm-Rate-Code-Defn-IO
Datatype	
Description	Includes CF-Rate Code Maintenance Deletion-IO details

[TOP](#)

## RATECODE

Attribute	Description				
Name	RATECODE				
Datatype	String				
Description	Indicates Rate Code.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>10</td></tr></tbody></table>	Restrictions	Description	maxLength	10
	Restrictions	Description			
maxLength	10				

[TOP](#)

## Cftm-Rate-Code-Defn-Full

Attribute	Description
Name	Cftm-Rate-Code-Defn-Full
Datatype	
Description	Includes CF-Rate Code Maintenance Deletion details

[TOP](#)

## RATECODE

Attribute	Description				
Name	RATECODE				
Datatype	String				
Description	Indicates Rate Code.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>10</td></tr></tbody></table>	Restrictions	Description	maxLength	10
	Restrictions	Description			
maxLength	10				

[TOP](#)

## RATECODEDESCRIPTION

Attribute	Description				
Name	RATECODEDESCRIPTION				
Datatype	String				
Description	Indicates the description of rate code				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>105</td></tr></tbody></table>	Restrictions	Description	maxLength	105
	Restrictions	Description			
maxLength	105				

[TOP](#)

## HOLIDAYCCY

Attribute	Description				
Name	HOLIDAYCCY				
Datatype	String				
Description	Specifies Holiday Currency .				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

[TOP](#)

## PROPAGATIONACROSSBRANCHES

Attribute	Description				
Name	PROPAGATIONACROSSBRANCHES				
Datatype	String				
Description	Propagate Across Branches				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	1
	Restrictions	Description			
maxLength	1				

[TOP](#)

## MAKERID

Attribute	Description
-----------	-------------

Name	MAKERID	
Datatype	String	
Description	Specifies the User id who has saved the record.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates the date and time when the user has saved the record.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates the User id who has authorized the record.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has authorized the booked contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	It indicates the modification number.	



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	It indicates the status of the record,whether open or Closed.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorized.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Cftm-Tenor-Code-Defn

<b>Attribute</b>	<b>Description</b>	
Name	Cftm-Tenor-Code-Defn	
Datatype		
Description	Includes Tenor code details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## TENORCODE

Attribute	Description				
Name	TENORCODE				
Datatype	String				
Description	Indicates the tenor code				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>10</td></tr></tbody></table>	Restrictions	Description	maxLength	10
	Restrictions	Description			
maxLength	10				

[TOP](#)

## TENORCODEDESCRIPTION

Attribute	Description				
Name	TENORCODEDESCRIPTION				
Datatype	String				
Description	Indicates the description of tenor code.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>105</td></tr></tbody></table>	Restrictions	Description	maxLength	105
	Restrictions	Description			
maxLength	105				

[TOP](#)

## UDFDETAILS

Attribute	Description						
Name	UDFDETAILS						
Datatype							
Description	Includes User Defined Fields details						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

## FIELD\_NAME

Attribute	Description
-----------	-------------

Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

[TOP](#)

## DATATYPE

<b>Attribute</b>	<b>Description</b>	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

[TOP](#)

## FIELD\_VALUE

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

[TOP](#)

## VAL\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2
	minLength	0

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

<b>Attribute</b>	<b>Description</b>	
Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.13.4.CF-DeleteCFRateCodeMaint-Res-PK-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Cftm-Rate-Code-Defn-IO*

*RATECODE*

*Cftm-Rate-Code-Defn-PK*

*RATECODE*

*Cftm-Rate-Code-Defn-Full*

*RATECODE*

*RATECODEDESCRIPTION*

*HOLIDAYCCY*

*PROPAGATIONACROSSBRANCHES*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

*Cftm-Tenor-Code-Defn*

[TENORCODE](#)  
[TENORCODEDESCRIPTION](#)  
[UDFDETAILS](#)  
[FUNCTIONID](#)  
[FIELD\\_NAME](#)  
[DATATYPE](#)  
[FIELD\\_VALUE](#)  
[VAL\\_TYPE](#)  
[FCUBS\\_ERROR\\_RESP](#)  
[ERROR](#)  
[ECODE](#)  
[EDESC](#)  
[FCUBS\\_WARNING\\_RESP](#)  
[WARNING](#)  
[WCODE](#)  
[WDESC](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true



**SERVICE**

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**OPERATION**

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description
-----------	-------------

Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Cftm-Rate-Code-Defn-IO

Attribute	Description
Name	Cftm-Rate-Code-Defn-IO
Datatype	
Description	Includes CF-Rate Code Maintenance Deletion-IO details

[TOP](#)

## RATECODE

Attribute	Description				
Name	RATECODE				
Datatype	String				
Description	Indicates Rate Code.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>10</td></tr></tbody></table>	Restrictions	Description	maxLength	10
Restrictions	Description				
maxLength	10				

[TOP](#)

## Cftm-Rate-Code-Defn-PK

Attribute	Description
Name	Cftm-Rate-Code-Defn-PK
Datatype	
Description	Includes CF-Rate Code Maintenance Deletion-Primary key details

[TOP](#)

## RATECODE

Attribute	Description				
Name	RATECODE				
Datatype	String				
Description	Indicates Rate Code.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>10</td></tr></tbody></table>	Restrictions	Description	maxLength	10
	Restrictions	Description			
maxLength	10				

[TOP](#)

## Cftm-Rate-Code-Defn-Full

Attribute	Description
Name	Cftm-Rate-Code-Defn-Full
Datatype	
Description	Includes CF-Rate Code Maintenance Deletion details

[TOP](#)

## RATECODE

Attribute	Description				
Name	RATECODE				
Datatype	String				
Description	Indicates Rate Code.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>10</td></tr></tbody></table>	Restrictions	Description	maxLength	10
	Restrictions	Description			
maxLength	10				

[TOP](#)

## RATECODEDESCRIPTION

Attribute	Description				
Name	RATECODEDESCRIPTION				
Datatype	String				
Description	Indicates the description of rate code				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>105</td></tr></tbody></table>	Restrictions	Description	maxLength	105
	Restrictions	Description			
maxLength	105				

[TOP](#)

## HOLIDAYCCY

Attribute	Description
Name	HOLIDAYCCY
Datatype	String
Description	Specifies Holiday Currency .

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## PROPAGATIONACROSSBRANCHES

<b>Attribute</b>	<b>Description</b>	
Name	PROPAGATIONACROSSBRANCHES	
Datatype	String	
Description	Propagate Across Branches	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Specifies the User id who has saved the record.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates the date and time when the user has saved the record.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates the User id who has authorized the record.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has authorized the booked contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	It indicates the modification number.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	It indicates the status of the record,whether open or Closed.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorized.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## Cftm-Tenor-Code-Defn

Attribute	Description	
Name	Cftm-Tenor-Code-Defn	
Datatype		
Description	Includes Tenor code details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## TENORCODE

Attribute	Description	
Name	TENORCODE	
Datatype	String	
Description	Indicates the tenor code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

## TENORCODEDESCRIPTION

Attribute	Description	
Name	TENORCODEDESCRIPTION	
Datatype	String	
Description	Indicates the description of tenor code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

## UDFDETAILS

Attribute	Description
Name	UDFDETAILS
Datatype	



Description	Includes User Defined Fields details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## FIELD\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

[TOP](#)

## DATATYPE

<b>Attribute</b>	<b>Description</b>	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

[TOP](#)

## FIELD\_VALUE

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

[TOP](#)

## VAL\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2
	minLength	0

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.14.DeleteCFRateTypeDefn

Deletion of Rate Type Maintenance

### 2.14.1.CF-DeleteCFRateTypeDefn-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Cftm-Rate-Type-Defn-Full*

*RATETYPE*

*RATETYPEDESCRIPTION*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

*UDFDETAILS*

*FUNCTIONID*

*FIELD\_NAME*

*DATATYPE*

*FIELD\_VALUE*

VAL\_TYPE

FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description
-----------	-------------

Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

[TOP](#)

## Cftm-Rate-Type-Defn-Full

Attribute	Description
-----------	-------------

Name	Cftm-Rate-Type-Defn-Full
Datatype	
Description	Includes CF-Rate Type Maintenance Deletion details

[TOP](#)

## RATETYPE

Attribute	Description	
Name	RATETYPE	
Datatype	String	
Description	Indicates The Rate Type.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## RATETYPEDESCRIPTION

Attribute	Description	
Name	RATETYPEDESCRIPTION	
Datatype	String	
Description	Indicates The Rate Type Description.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

## MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	The User Id who has created\last modified the Rate Type Definition details.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates Date and Stamp when the user hascreated\last modified the Rate Type Definition details.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

**CHECKERID**

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	The User Id who has Authorized the creation\modification of Rate Type Definition details.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CHECKERDTSTAMP**

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates Date and Stamp when the user has Authorized the creation\ modification of Rate Type Definition details.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number i.e. the number of times Rate Type Definition detail has been modified.	
Attributes	Attribute	Description
	minOccurs	0

**AUTHSTAT**

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status. A - Authorized U - Unauthorized	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**RECSTAT**

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Indicates the Record Status O - Open C - Close	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**ONCEAUTH**

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates whether Rate Type Definition detail has been Authorized atleast Once.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**UDFDETAILS**

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**FIELD\_NAME**

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

**DATATYPE**

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

**FIELD\_VALUE**

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

**VAL\_TYPE**

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

2.14.2.CF-DeleteCFRateTypeDefn-Req-IO-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Cftm-Rate-Type-Defn-IO*

*RATETYPE*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

**SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

**UBSCOMP**

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		

Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*



**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

[TOP](#)

## Cftm-Rate-Type-Defn-IO

<b>Attribute</b>	<b>Description</b>
Name	Cftm-Rate-Type-Defn-IO
Datatype	
Description	Includes CF-Rate Type Maintenance Deletion-IO details

[TOP](#)

## RATETYPE

<b>Attribute</b>	<b>Description</b>	
Name	RATETYPE	
Datatype	String	
Description	Indicates The Rate Type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

### 2.14.3.CF-DeleteCFRateTypeDefn-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Cftm-Rate-Type-Defn-IO*

*RATETYPE*

*Cftm-Rate-Type-Defn-Full*

*RATETYPE*

*RATETYPEDESCRIPTION*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

*UDFDETAILS*

*FUNCTIONID*

*FIELD\_NAME*

*DATATYPE*

*FIELD\_VALUE*

[VAL\\_TYPE](#)  
[FCUBS\\_ERROR\\_RESP](#)  
[ERROR](#)  
[ECODE](#)  
[EDESC](#)  
[FCUBS\\_WARNING\\_RESP](#)  
[WARNING](#)  
[WCODE](#)  
[WDESC](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description						
Name	MSGID						
Datatype	String						
Description							
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*		
Restrictions	Description						
pattern	[a-zA-Z_0-9]*						

[TOP](#)

## CORRELID

Attribute	Description						
Name	CORRELID						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nullable	true
	Attribute	Description					
	minOccurs	0					
nullable	true						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*		
	Restrictions	Description					
pattern	[a-zA-Z_0-9]*						

[TOP](#)

## USERID

Attribute	Description						
Name	USERID						
Datatype	String						
Description							
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	12					
pattern	[A-Z_0-9]*						

[TOP](#)

## BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description							
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
	Restrictions	Description					
	length	3					
pattern	[a-zA-Z_0-9]{3}						

[TOP](#)

## MODULEID

Attribute	Description						
Name	MODULEID						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nullable	true
	Attribute	Description					
	minOccurs	0					
nullable	true						

[TOP](#)

## SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE



[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Cftm-Rate-Type-Defn-IO

Attribute	Description
Name	Cftm-Rate-Type-Defn-IO
Datatype	
Description	Includes CF-Rate Type Maintenance Deletion-IO details

[TOP](#)

## RATETYPE

Attribute	Description				
Name	RATETYPE				
Datatype	String				
Description	Indicates The Rate Type.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

[TOP](#)

## Cftm-Rate-Type-Defn-Full

Attribute	Description
Name	Cftm-Rate-Type-Defn-Full
Datatype	
Description	Includes CF-Rate Type Maintenance Deletion details

[TOP](#)

## RATETYPE

Attribute	Description				
Name	RATETYPE				
Datatype	String				
Description	Indicates The Rate Type.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## RATETYPEDESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	RATETYPEDESCRIPTION	
Datatype	String	
Description	Indicates The Rate Type Description.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	The User Id who has created\last modified the Rate Type Definition details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates Date and Stamp when the user hascreated\last modified the Rate Type Definition details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	The User Id who has Authorized the creation\modification of Rate Type Definition details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

**CHECKERDTSTAMP**

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates Date and Stamp when the user has Authorized the creation\ modification of Rate Type Definition details.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number i.e. the number of times Rate Type Definition detail has been modified.	
Attributes	Attribute	Description
	minOccurs	0

**AUTHSTAT**

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status. A - Authorized U - Unauthorized	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**RECSTAT**

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Indicates the Record Status O - Open C - Close	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**ONCEAUTH**

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates whether Rate Type Definition detail has been Authorized atleast Once.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**UDFDETAILS**

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**FIELD\_NAME**

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

**DATATYPE**

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

## FIELD\_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

[TOP](#)

## VAL\_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description
-----------	-------------

Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)



## 2.14.4.CF-DeleteCFRateTypeDefn-Res-PK-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Cftm-Rate-Type-Defn-IO*

*RATETYPE*

*Cftm-Rate-Type-Defn-PK*

*RATETYPE*

*Cftm-Rate-Type-Defn-Full*

*RATETYPE*

*RATETYPEDESCRIPTION*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

*UDFDETAILS*

*FUNCTIONID*

*FIELD\_NAME*

DATATYPE  
 FIELD\_VALUE  
 VAL\_TYPE  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

**MODULEID**

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

**SERVICE**

Attribute	Description
Name	SERVICE
Datatype	String

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Cftm-Rate-Type-Defn-IO

Attribute	Description
Name	Cftm-Rate-Type-Defn-IO
Datatype	
Description	Includes CF-Rate Type Maintenance Deletion-IO details

[TOP](#)

## RATETYPE

Attribute	Description				
Name	RATETYPE				
Datatype	String				
Description	Indicates The Rate Type.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
Restrictions	Description				
maxLength	12				

[TOP](#)

## Cftm-Rate-Type-Defn-PK

Attribute	Description
Name	Cftm-Rate-Type-Defn-PK
Datatype	
Description	Includes CF-Rate Type Maintenance Deletion-Primary key details

[TOP](#)

## RATETYPE

Attribute	Description				
Name	RATETYPE				
Datatype	String				
Description	Indicates The Rate Type.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## Cftm-Rate-Type-Defn-Full

Attribute	Description
Name	Cftm-Rate-Type-Defn-Full
Datatype	
Description	Includes CF-Rate Type Maintenance Deletion details

[TOP](#)

## RATETYPE

Attribute	Description	
Name	RATETYPE	
Datatype	String	
Description	Indicates The Rate Type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## RATETYPEDESCRIPTION

Attribute	Description	
Name	RATETYPEDESCRIPTION	
Datatype	String	
Description	Indicates The Rate Type Description.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	The User Id who has created\last modified the Rate Type Definition details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

Attribute	Description
Name	MAKERDTSTAMP



Datatype	String	
Description	Indicates Date and Stamp when the user has created\last modified the Rate Type Definition details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	The User Id who has Authorized the creation\modification of Rate Type Definition details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates Date and Stamp when the user has Authorized the creation\modification of Rate Type Definition details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number i.e. the number of times Rate Type Definition detail has been modified.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	

Description	Indicates Authorization Status. A - Authorized U - Unauthorized	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	Indicates the Record Status O - Open C - Close	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates whether Rate Type Definition detail has been Authorized atleast Once.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## FIELD\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

[TOP](#)

## DATATYPE

<b>Attribute</b>	<b>Description</b>	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

[TOP](#)

## FIELD\_VALUE

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

[TOP](#)

## VAL\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.15.DeleteFLTRTDefn

Deletion of Floating rate Maintenance

### 2.15.1.CF-DeleteFLTRTDefn-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Cftms-Rate-Code-Details-Full*

*RATECODE*

*RATEDESC*

*BRANCHCODE*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

*Cftms-Rate-Ccy-Details*

*CCYCODE*

*Cftms-Float-Rate-Master-Details*

*AMNTSLAB*

EFFECTDATE  
 BRWLENDINDCR  
 Cftms-Float-Rate-Detail-Description  
 TENORTO  
 INTRATE  
 UDFDETAILS  
 FUNCTIONID  
 FIELD\_NAME  
 DATATYPE  
 FIELD\_VALUE  
 VAL\_TYPE

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

**MODULEID**

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

**SERVICE**

Attribute	Description
Name	SERVICE
Datatype	String



Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute		Description
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute		Description
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute		Description
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute		Description
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

Attribute		Description
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

[TOP](#)

## Cftms-Rate-Code-Details-Full

Attribute	Description
Name	Cftms-Rate-Code-Details-Full
Datatype	
Description	Includes CF-Floating rate Maintenance Deletion details

[TOP](#)

## RATECODE

Attribute	Description				
Name	RATECODE				
Datatype	String				
Description	Specifies The Rate Code.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>10</td></tr></tbody></table>	Restrictions	Description	maxLength	10
	Restrictions	Description			
maxLength	10				

[TOP](#)

## RATEDESC

Attribute	Description				
Name	RATEDESC				
Datatype	String				
Description	Specifies The Rate Description.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>105</td></tr></tbody></table>	Restrictions	Description	maxLength	105
	Restrictions	Description			
maxLength	105				

[TOP](#)

## BRANCHCODE

Attribute	Description				
Name	BRANCHCODE				
Datatype	String				
Description	Specifies The Branch Code.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

**MAKERID**

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	The User id who has booked the contract	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**MAKERDTSTAMP**

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has booked the contract	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

**CHECKERID**

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Specifies The Checker Identification.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CHECKERDTSTAMP**

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has authorized the booked contract	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Specifies The Modification Number.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Specifies The Authorization Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Specifies The Record Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorized.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## Cftms-Rate-Ccy-Details

Attribute	Description
Name	Cftms-Rate-Ccy-Details
Datatype	
Description	Includes Rate-Currency details

Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## CCYCODE

<b>Attribute</b>	<b>Description</b>	
Name	CCYCODE	
Datatype	String	
Description	Specifies The Currency Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## Cftms-Float-Rate-Master-Details

<b>Attribute</b>	<b>Description</b>	
Name	Cftms-Float-Rate-Master-Details	
Datatype		
Description	Includes Rate details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## AMNTSLAB

<b>Attribute</b>	<b>Description</b>	
Name	AMNTSLAB	
Datatype	Number	
Description	Specifies The Amount Slab.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## EFFECTDATE

<b>Attribute</b>	<b>Description</b>	
Name	EFFECTDATE	
Datatype	Date	
Description	Specifies The Effective Date.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## BRWLENDINDCR

<b>Attribute</b>	<b>Description</b>	
Name	BRWLENDINDCR	

Datatype	String	
Description	Specifies The Borrow Lend Indicator 1 : Borrow : B 2 : Lend : L 3 : MID : M	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	B,L,M

[TOP](#)

## Cftms-Float-Rate-Detail-Description

<b>Attribute</b>	<b>Description</b>	
Name	Cftms-Float-Rate-Detail-Description	
Datatype		
Description	Specifies The Tenor and Interest Rate Details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## TENORTO

<b>Attribute</b>	<b>Description</b>	
Name	TENORTO	
Datatype	Number	
Description	Specifies The Tenor.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## INTRATE

<b>Attribute</b>	<b>Description</b>	
Name	INTRATE	
Datatype	Number	
Description	Specifies The Interest Rate.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0



**FUNCTIONID**

Attribute		Description
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**FIELD\_NAME**

Attribute		Description
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

**DATATYPE**

Attribute		Description
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

**FIELD\_VALUE**

Attribute		Description
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

## VAL\_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

[TOP](#)

## 2.15.2.CF-DeleteFLTRTDefn-Req-IO-MSG.xsd

### FCUBS\_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE\_OPERATION

SOURCE\_USERID

DESTINATION

MULTIRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

### FCUBS\_BODY

*Cftms-Rate-Code-Details-IO*

RATECODE

BRANCHCODE

### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

### SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

### UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		

Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTITRIPID**

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

[TOP](#)

## Cftms-Rate-Code-Details-IO

Attribute	Description
Name	Cftms-Rate-Code-Details-IO
Datatype	
Description	Includes CF-Floating rate Maintenance Deletion-IO details

[TOP](#)

## RATECODE

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description	Specifies The Rate Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## BRANCHCODE

Attribute	Description
-----------	-------------



Name	BRANCHCODE	
Datatype	String	
Description	Specifies The Branch Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

### 2.15.3.CF-DeleteFLTRTDefn-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Cftms-Rate-Code-Details-IO*

*RATECODE*

*BRANCHCODE*

*Cftms-Rate-Code-Details-Full*

*RATECODE*

*RATEDESC*

*BRANCHCODE*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

*Cftms-Rate-Ccy-Details*

*CCYCODE*

*Cftms-Float-Rate-Master-Details*

AMNTSLAB  
 EFFECTDATE  
 BRWLENDINDCR  
 Cftms-Float-Rate-Detail-Description  
 TENORTO  
 INTRATE  
 UDFDETAILS  
 FUNCTIONID  
 FIELD\_NAME  
 DATATYPE  
 FIELD\_VALUE  
 VAL\_TYPE  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description						
Name	MSGID						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nullable	true
	Attribute	Description					
	minOccurs	0					
nullable	true						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*		
	Restrictions	Description					
pattern	[a-zA-Z_0-9]*						

[TOP](#)

## CORRELID

Attribute	Description						
Name	CORRELID						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nullable	true
	Attribute	Description					
	minOccurs	0					
nullable	true						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*		
	Restrictions	Description					
pattern	[a-zA-Z_0-9]*						

[TOP](#)

## USERID

Attribute	Description						
Name	USERID						
Datatype	String						
Description							
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	12					
pattern	[A-Z_0-9]*						

[TOP](#)

## BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description							
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
	Restrictions	Description					
	length	3					
pattern	[a-zA-Z_0-9]{3}						

[TOP](#)

## MODULEID

Attribute	Description
Name	MODULEID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Cftms-Rate-Code-Details-IO

Attribute	Description
Name	Cftms-Rate-Code-Details-IO
Datatype	
Description	Includes CF-Floating rate Maintenance Deletion-IO details

[TOP](#)

## RATECODE

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description	Specifies The Rate Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## BRANCHCODE



Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description	Specifies The Branch Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## Cftms-Rate-Code-Details-Full

Attribute	Description	
Name	Cftms-Rate-Code-Details-Full	
Datatype		
Description	Includes CF-Floating rate Maintenance Deletion details	

[TOP](#)

## RATECODE

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description	Specifies The Rate Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## RATEDESC

Attribute	Description	
Name	RATEDESC	
Datatype	String	
Description	Specifies The Rate Description.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

## BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description	Specifies The Branch Code.	
Attributes	Attribute	Description
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	The User id who has booked the contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has booked the contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Specifies The Checker Identification.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has authorized the booked contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Specifies The Modification Number.	
Attributes	Attribute	Description
	minOccurs	0

**AUTHSTAT**

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Specifies The Authorization Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**RECSTAT**

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Specifies The Record Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**ONCEAUTH**

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorized.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**Cftms-Rate-Ccy-Details**

Attribute	Description
Name	Cftms-Rate-Ccy-Details

Datatype		
Description	Includes Rate-Currency details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## CCYCODE

<b>Attribute</b>	<b>Description</b>	
Name	CCYCODE	
Datatype	String	
Description	Specifies The Currency Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## Cftms-Float-Rate-Master-Details

<b>Attribute</b>	<b>Description</b>	
Name	Cftms-Float-Rate-Master-Details	
Datatype		
Description	Includes Rate details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## AMNTSLAB

<b>Attribute</b>	<b>Description</b>	
Name	AMNTSLAB	
Datatype	Number	
Description	Specifies The Amount Slab.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## EFFECTDATE

<b>Attribute</b>	<b>Description</b>	
Name	EFFECTDATE	
Datatype	Date	
Description	Specifies The Effective Date.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## BRWLENDINDCR

Attribute	Description	
Name	BRWLENDINDCR	
Datatype	String	
Description	Specifies The Borrow Lend Indicator 1 : Borrow : B 2 : Lend : L 3 : MID : M	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	B,L,M

[TOP](#)

### Cftms-Float-Rate-Detail-Description

Attribute	Description	
Name	Cftms-Float-Rate-Detail-Description	
Datatype		
Description	Specifies The Tenor and Interest Rate Details.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

### TENORTO

Attribute	Description	
Name	TENORTO	
Datatype	Number	
Description	Specifies The Tenor.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

### INTRATE

Attribute	Description	
Name	INTRATE	
Datatype	Number	
Description	Specifies The Interest Rate.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

### UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	

Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## FIELD\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

[TOP](#)

## DATATYPE

<b>Attribute</b>	<b>Description</b>	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

[TOP](#)

## FIELD\_VALUE

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

[TOP](#)**VAL\_TYPE**

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

[TOP](#)**FCUBS\_ERROR\_RESP**

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**ERROR**

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**ECODE**

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)**EDESC**

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
	Attribute	Description			
maxOccurs	unbounded				

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)



2.15.4.CF-DeleteFLTRTDefn-Res-PK-MSG.xsd

*FCUBS\_HEADER*  
*SOURCE*  
*UBSCOMP*  
*MSGID*  
*CORRELID*  
*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*CHOICE*  
*Cftms-Rate-Code-Details-PK*  
*RATECODE*  
*BRANCHCODE*  
*Cftms-Rate-Code-Details-IO*  
*RATECODE*  
*BRANCHCODE*  
*FCUBS\_ERROR\_RESP*  
*ERROR*  
*ECODE*  
*EDESC*  
*FCUBS\_WARNING\_RESP*  
*WARNING*  
*WCODE*  
*WDESC*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	
-------------	--

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description

Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute		Description
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute		Description
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

**DESTINATION**

Attribute		Description
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTITRIPID**

Attribute		Description
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Cftms-Rate-Code-Details-PK

Attribute	Description
Name	Cftms-Rate-Code-Details-PK
Datatype	
Description	Includes CF-Floating rate Maintenance Deletion-Primary key details

[TOP](#)

## RATECODE

Attribute	Description				
Name	RATECODE				
Datatype	String				
Description	Specifies The Rate Code.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>16</td></tr></tbody></table>	Restrictions	Description	maxLength	16
	Restrictions	Description			
maxLength	16				

[TOP](#)

## BRANCHCODE

Attribute	Description				
Name	BRANCHCODE				
Datatype	String				
Description	Specifies The Branch Code.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>16</td></tr></tbody></table>	Restrictions	Description	maxLength	16
	Restrictions	Description			
maxLength	16				

[TOP](#)

## Cftms-Rate-Code-Details-IO

Attribute	Description
Name	Cftms-Rate-Code-Details-IO
Datatype	
Description	Includes CF-Floating rate Maintenance Deletion-IO details

[TOP](#)

## RATECODE

Attribute	Description				
Name	RATECODE				
Datatype	String				
Description	Specifies The Rate Code.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>16</td></tr></tbody></table>	Restrictions	Description	maxLength	16
	Restrictions	Description			
maxLength	16				

[TOP](#)**BRANCHCODE**

Attribute		Description
Name	BRANCHCODE	
Datatype	String	
Description	Specifies The Branch Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)**FCUBS\_ERROR\_RESP**

Attribute		Description
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**ERROR**

Attribute		Description
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**ECODE**

Attribute		Description
Name	ECODE	
Datatype	String	
Description		

[TOP](#)**EDESC**

Attribute		Description
Name	EDESC	
Datatype	String	
Description		

[TOP](#)**FCUBS\_WARNING\_RESP**



Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description	
Name	WCODE	
Datatype	String	
Description		

[TOP](#)

## WDESC

Attribute	Description	
Name	WDESC	
Datatype	String	
Description		

[TOP](#)

## 2.16.DeleteFloatRateMaint

DeleteFloatRateMaint

### 2.16.1.CF-DeleteFloatRateMaint-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Rate-Code-Full*

*RATE\_CODE*

*RATEDESC*

*BRANCH\_CODE*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*Rate-Ccy*

*RATE\_CODE*

*CCY\_CODE*

*BRANCH\_CODE*

*Fload-Rate*

RATE\_CODE  
 CCY\_CODE  
 AMOUNT\_SLAB1  
 EFFECTIVE\_DATE  
 BRANCH\_CODE  
 BORROW\_LEND\_IND

*Ftrate-Detail*

RATE\_CODE  
 CCY\_CODE  
 AMOUNT\_SLAB  
 EFFECTIVE\_DATE  
 BRANCH\_CODE  
 BORROW\_LEND\_IND  
 TENOR\_TO1  
 INTEREST\_RATE  
 RATECODEC  
 CCYCODEC  
 AMOUNTSLABC  
 EFFECTIVEDATEC  
 BRANCHCODEC  
 BORROWLENDINDC  
 TENORTOC  
 TDMAXRATE  
 TDPREDIFF

UDFDETAILS

FLDNAM

FLDVAL

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		

Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTITRIPID**

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

[TOP](#)

## Rate-Code-Full

<b>Attribute</b>	<b>Description</b>
Name	Rate-Code-Full
Datatype	
Description	

[TOP](#)

## RATE\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## RATEDESC

<b>Attribute</b>	<b>Description</b>
------------------	--------------------



Name	RATEDESC	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

**Rate-Ccy**

Attribute	Description	
Name	Rate-Ccy	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**RATE\_CODE**

Attribute	Description	
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

**CCY\_CODE**

Attribute	Description	
Name	CCY_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

**BRANCH\_CODE**

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

**Fload-Rate**

Attribute	Description
-----------	-------------

Name	Flood-Rate	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## RATE\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## CCY\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	CCY_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## AMOUNT\_SLAB1

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNT_SLAB1	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## EFFECTIVE\_DATE

<b>Attribute</b>	<b>Description</b>	
Name	EFFECTIVE_DATE	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

**BRANCH\_CODE**

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

**BORROW\_LEND\_IND**

Attribute	Description	
Name	BORROW_LEND_IND	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	B,L,M

**Filtrate-Detail**

Attribute	Description	
Name	Filtrate-Detail	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**RATE\_CODE**

Attribute	Description	
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

**CCY\_CODE**

Attribute	Description
-----------	-------------

Name	CCY_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## AMOUNT\_SLAB

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNT_SLAB	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## EFFECTIVE\_DATE

<b>Attribute</b>	<b>Description</b>	
Name	EFFECTIVE_DATE	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## BORROW\_LEND\_IND

<b>Attribute</b>	<b>Description</b>	
Name	BORROW_LEND_IND	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	B,L,M

**TENOR\_TO1**

Attribute		Description
Name	TENOR_TO1	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

**INTEREST\_RATE**

Attribute		Description
Name	INTEREST_RATE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

**RATECODEC**

Attribute		Description
Name	RATECODEC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

**CCYCODEC**

Attribute		Description
Name	CCYCODEC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

**AMOUNTSLABC**

Attribute		Description
Name	AMOUNTSLABC	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## EFFECTIVEDATEC

Attribute	Description	
Name	EFFECTIVEDATEC	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## BRANCHCODEC

Attribute	Description	
Name	BRANCHCODEC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## BORROWLENDINDC

Attribute	Description	
Name	BORROWLENDINDC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## TENORTOC

Attribute	Description	
Name	TENORTOC	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## TDMAXRATE

Attribute	Description
Name	TDMAXRATE



Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TDPREDIFF

<b>Attribute</b>	<b>Description</b>	
Name	TDPREDIFF	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

[TOP](#)

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

[TOP](#)

## 2.16.2.CF-DeleteFloatRateMaint-Req-IO-MSG.xsd

### FCUBS\_HEADER

SOURCE

UBSCOMP

MSGID

CORRELID

USERID

BRANCH

MODULEID

SERVICE

OPERATION

SOURCE\_OPERATION

SOURCE\_USERID

DESTINATION

MULTITRIPID

FUNCTIONID

ACTION

MSGSTAT

PASSWORD

ADDL

PARAM

NAME

VALUE

### FCUBS\_BODY

Rate-Code-IO

RATE\_CODE

BRANCH\_CODE

### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

### SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

### UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		

Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTITRIPID**

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

[TOP](#)

## Rate-Code-IO

Attribute	Description
Name	Rate-Code-IO
Datatype	
Description	

[TOP](#)

## RATE\_CODE

Attribute	Description	
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## BRANCH\_CODE

Attribute	Description
-----------	-------------

Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)



### 2.16.3.CF-DeleteFloatRateMaint-Res-Full-MSG.xsd

#### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

#### *FCUBS\_BODY*

*Rate-Code-Full*

*RATE\_CODE*

*RATEDESC*

*BRANCH\_CODE*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*Rate-Ccy*

*RATE\_CODE*

*CCY\_CODE*

*BRANCH\_CODE*

*Fload-Rate*

*RATE\_CODE*

*CCY\_CODE*

*AMOUNT\_SLAB1*

EFFECTIVE\_DATE  
 BRANCH\_CODE  
 BORROW\_LEND\_IND

*Filtrate-Detail*

RATE\_CODE  
 CCY\_CODE  
 AMOUNT\_SLAB  
 EFFECTIVE\_DATE  
 BRANCH\_CODE  
 BORROW\_LEND\_IND  
 TENOR\_TO1  
 INTEREST\_RATE  
 RATECODEC  
 CCYCODEC  
 AMOUNTSLABC  
 EFFECTIVEDATEC  
 BRANCHCODEC  
 BORROWLENDINDC  
 TENORTOC  
 TDMAXRATE  
 TDPREDIFF

UDFDETAILS

FLDNAM

FLDVAL

FCUBS\_ERROR\_RESP

ERROR

ECODE

EDESC

FCUBS\_WARNING\_RESP

WARNING

WCODE

WDESC

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

**SOURCE**

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

<b>Attribute</b>	<b>Description</b>	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description							
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
	Restrictions	Description					
	length	3					
pattern	[a-zA-Z_0-9]{3}						

[TOP](#)

## MODULEID

Attribute	Description						
Name	MODULEID						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nullable	true
	Attribute	Description					
	minOccurs	0					
nullable	true						

[TOP](#)

## SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	nullable	true
	Attribute	Description			
nullable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	nullable	true
	Attribute	Description			
nullable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about Full Response	

[TOP](#)

## Rate-Code-Full

Attribute	Description	
Name	Rate-Code-Full	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## RATE\_CODE

Attribute	Description	
Name	RATE_CODE	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## RATEDESC

<b>Attribute</b>	<b>Description</b>	
Name	RATEDESC	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## Rate-Ccy

Attribute	Description	
Name	Rate-Ccy	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## RATE\_CODE

Attribute	Description	
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

## CCY\_CODE

Attribute	Description	
Name	CCY_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## BRANCH\_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## Fload-Rate

<b>Attribute</b>	<b>Description</b>	
Name	Fload-Rate	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## RATE\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## CCY\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	CCY_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## AMOUNT\_SLAB1

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNT_SLAB1	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

**EFFECTIVE\_DATE**

Attribute	Description	
Name	EFFECTIVE_DATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	1

**BRANCH\_CODE**

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

**BORROW\_LEND\_IND**

Attribute	Description	
Name	BORROW_LEND_IND	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	B,L,M

**Filtrate-Detail**

Attribute	Description	
Name	Filtrate-Detail	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**RATE\_CODE**

Attribute	Description	
Name	RATE_CODE	
Datatype	String	

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## CCY\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	CCY_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## AMOUNT\_SLAB

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNT_SLAB	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## EFFECTIVE\_DATE

<b>Attribute</b>	<b>Description</b>	
Name	EFFECTIVE_DATE	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## BORROW\_LEND\_IND

Attribute	Description	
Name	BORROW_LEND_IND	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	B,L,M

[TOP](#)

## TENOR\_TO1

Attribute	Description	
Name	TENOR_TO1	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

## INTEREST\_RATE

Attribute	Description	
Name	INTEREST_RATE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## RATECODEC

Attribute	Description	
Name	RATECODEC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

## CCYCODEC

Attribute	Description	
Name	CCYCODEC	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## AMOUNTSLABC

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNTSLABC	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## EFFECTIVEDATEC

<b>Attribute</b>	<b>Description</b>	
Name	EFFECTIVEDATEC	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## BRANCHCODEC

<b>Attribute</b>	<b>Description</b>	
Name	BRANCHCODEC	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## BORROWLENDINDC

<b>Attribute</b>	<b>Description</b>	
Name	BORROWLENDINDC	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## TENORTOC

Attribute	Description	
Name	TENORTOC	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## TDMAXRATE

Attribute	Description	
Name	TDMAXRATE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## TDPREDIFF

Attribute	Description	
Name	TDPREDIFF	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

[TOP](#)



## FLDVAL

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description
-----------	-------------

Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## WARNING

<b>Attribute</b>	<b>Description</b>	
Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## WCODE

<b>Attribute</b>	<b>Description</b>
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

<b>Attribute</b>	<b>Description</b>
Name	WDESC
Datatype	String
Description	

[TOP](#)

2.16.4.CF-DeleteFloatRateMaint-Res-PK-MSG.xsd

*FCUBS\_HEADER*  
*SOURCE*  
*UBSCOMP*  
*MSGID*  
*CORRELID*  
*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*CHOICE*  
*Rate-Code-PK*  
*RATE\_CODE*  
*BRANCH\_CODE*  
*Rate-Code-IO*  
*RATE\_CODE*  
*BRANCH\_CODE*  
*FCUBS\_ERROR\_RESP*  
*ERROR*  
*ECODE*  
*EDESC*  
*FCUBS\_WARNING\_RESP*  
*WARNING*  
*WCODE*  
*WDESC*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	

Description	
-------------	--

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description

Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTITRIPID**

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)



## Rate-Code-PK

Attribute	Description	
Name	Rate-Code-PK	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## RATE\_CODE

Attribute	Description	
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## BRANCH\_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## Rate-Code-IO

Attribute	Description	
Name	Rate-Code-IO	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## RATE\_CODE

Attribute	Description
Name	RATE_CODE
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.17.ExecuteQryFLTRTDefn

Query of Floating rate Maintenance

### 2.17.1.CF-ExecuteQryFLTRTDefn-Req-IO-MSG.xsd

#### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

#### *FCUBS\_BODY*

*Cftms-Rate-Code-Details-IO*

*RATECODE*

*BRANCHCODE*

#### **FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

#### **SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**UBSCOMP**

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description
-----------	-------------

Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MSGSTAT**

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

**PASSWORD**

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

**ADDL**

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

**PARAM**

Attribute	Description
-----------	-------------



Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

[TOP](#)

## Cftms-Rate-Code-Details-IO

Attribute	Description
Name	Cftms-Rate-Code-Details-IO
Datatype	
Description	Includes CF-Floating rate Maintenance Query-IO details

[TOP](#)

## RATECODE

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description	Specifies The Rate Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## BRANCHCODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCHCODE	
Datatype	String	
Description	Specifies The Branch Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## 2.17.2.CF-ExecuteQryFLTRTDefn-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Cftms-Rate-Code-Details-IO*

*RATECODE*

*BRANCHCODE*

*Cftms-Rate-Code-Details-Full*

*RATECODE*

*RATEDESC*

*BRANCHCODE*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

*Cftms-Rate-Ccy-Details*

*CCYCODE*

*Cftms-Float-Rate-Master-Details*

AMNTSLAB  
 EFFECTDATE  
 BRWLENDINDCR  
 Cftms-Float-Rate-Detail-Description  
 TENORTO  
 INTRATE  
 UDFDETAILS  
 FUNCTIONID  
 FIELD\_NAME  
 DATATYPE  
 FIELD\_VALUE  
 VAL\_TYPE  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description						
Name	MSGID						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nullable	true
	Attribute	Description					
	minOccurs	0					
nullable	true						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*		
	Restrictions	Description					
pattern	[a-zA-Z_0-9]*						

[TOP](#)

## CORRELID

Attribute	Description						
Name	CORRELID						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nullable	true
	Attribute	Description					
	minOccurs	0					
nullable	true						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*		
	Restrictions	Description					
pattern	[a-zA-Z_0-9]*						

[TOP](#)

## USERID

Attribute	Description						
Name	USERID						
Datatype	String						
Description							
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	12					
pattern	[A-Z_0-9]*						

[TOP](#)

## BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description							
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
	Restrictions	Description					
	length	3					
pattern	[a-zA-Z_0-9]{3}						

[TOP](#)

## MODULEID

Attribute	Description
Name	MODULEID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME



Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Cftms-Rate-Code-Details-IO

Attribute	Description
Name	Cftms-Rate-Code-Details-IO
Datatype	
Description	Includes CF-Floating rate Maintenance Query-IO details

[TOP](#)

## RATECODE

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description	Specifies The Rate Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description	Specifies The Branch Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## Cftms-Rate-Code-Details-Full

Attribute	Description	
Name	Cftms-Rate-Code-Details-Full	
Datatype		
Description	Includes CF-Floating rate Maintenance Query details	

[TOP](#)

## RATECODE

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description	Specifies The Rate Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

[TOP](#)

## RATEDESC

Attribute	Description	
Name	RATEDESC	
Datatype	String	
Description	Specifies The Rate Description.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

## BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description	Specifies The Branch Code.	
Attributes	Attribute	Description
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	The User id who has booked the contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has booked the contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Specifies The Checker Identification.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has authorized the booked contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Specifies The Modification Number.	
Attributes	Attribute	Description
	minOccurs	0

**AUTHSTAT**

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Specifies The Authorization Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**RECSTAT**

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Specifies The Record Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**ONCEAUTH**

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorized.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**Cftms-Rate-Ccy-Details**

Attribute	Description
Name	Cftms-Rate-Ccy-Details

Datatype		
Description	Includes Rate-Currency details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## CCYCODE

<b>Attribute</b>	<b>Description</b>	
Name	CCYCODE	
Datatype	String	
Description	Specifies The Currency Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## Cftms-Float-Rate-Master-Details

<b>Attribute</b>	<b>Description</b>	
Name	Cftms-Float-Rate-Master-Details	
Datatype		
Description	Includes Rate details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## AMNTSLAB

<b>Attribute</b>	<b>Description</b>	
Name	AMNTSLAB	
Datatype	Number	
Description	Specifies The Amount Slab.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## EFFECTDATE

<b>Attribute</b>	<b>Description</b>	
Name	EFFECTDATE	
Datatype	Date	
Description	Specifies The Effective Date.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## BRWLENDINDCR

Attribute	Description	
Name	BRWLENDINDCR	
Datatype	String	
Description	Specifies The Borrow Lend Indicator 1 : Borrow : B 2 : Lend : L 3 : MID : M	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	B,L,M

[TOP](#)

### Cftms-Float-Rate-Detail-Description

Attribute	Description	
Name	Cftms-Float-Rate-Detail-Description	
Datatype		
Description	Specifies The Tenor and Interest Rate Details.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

### TENORTO

Attribute	Description	
Name	TENORTO	
Datatype	Number	
Description	Specifies The Tenor.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

### INTRATE

Attribute	Description	
Name	INTRATE	
Datatype	Number	
Description	Specifies The Interest Rate.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

### UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	

Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## FIELD\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

[TOP](#)

## DATATYPE

<b>Attribute</b>	<b>Description</b>	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

[TOP](#)

## FIELD\_VALUE

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

[TOP](#)**VAL\_TYPE**

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

[TOP](#)**FCUBS\_ERROR\_RESP**

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**ERROR**

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**ECODE**

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)**EDESC**

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

[TOP](#)



## FCUBS\_WARNING\_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## WARNING

Attribute	Description				
Name	WARNING				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
	Attribute	Description			
maxOccurs	unbounded				

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.18.ModifyCFFloatRateMaint

Modification of Floating rate Maintenance

### 2.18.1.CF-ModifyCFFloatRateMaint-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Cftm-Rate-Master-Full*

*RATECODE*

*RATECODEDESCRIPTION*

*TENORCODE*

*TENORCODEDESCRIPTION*

*CCYCODE*

*CCYNAME*

*EFFECTIVEDATE*

*RATESOURCE*

*RATESOURCEDESCRIPTION*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

[RECSTAT](#)  
[ONCEAUTH](#)  
[Cftm-Rate-Detail](#)  
[RATETYPE](#)  
[RATETYPEDESCRIPTION](#)  
[INTERESTRATE](#)  
[UDFDETAILS](#)  
[FUNCTIONID](#)  
[FIELD\\_NAME](#)  
[DATATYPE](#)  
[FIELD\\_VALUE](#)  
[VAL\\_TYPE](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description						
Name	MSGID						
Datatype	String						
Description							
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	nillable	true
Attribute	Description						
minOccurs	0						
nillable	true						

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

[TOP](#)

## DESTINATION

Attribute	Description
Name	DESTINATION

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	

Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

[TOP](#)

## Cftm-Rate-Master-Full

Attribute	Description
Name	Cftm-Rate-Master-Full
Datatype	
Description	Includes CF-Floating rate Maintenance Modification details

[TOP](#)

## RATECODE

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description	Specifies The Rate Code.	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

## RATECODEDESCRIPTION

Attribute	Description	
Name	RATECODEDESCRIPTION	
Datatype	String	
Description	Specifies The Rate Code Description.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

## TENORCODE

Attribute	Description	
Name	TENORCODE	
Datatype	String	
Description	Specifies The Tenor Code.	
Attributes	Attribute	Description
	minOccurs	1



Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## TENORCODEDESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	TENORCODEDESCRIPTION	
Datatype	String	
Description	Specifies The Tenor Code Description.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## CCYCODE

<b>Attribute</b>	<b>Description</b>	
Name	CCYCODE	
Datatype	String	
Description	Specifies The Currency Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## CCYNAME

<b>Attribute</b>	<b>Description</b>	
Name	CCYNAME	
Datatype	String	
Description	Specifies The Currency Code Description.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## EFFECTIVEDATE

<b>Attribute</b>	<b>Description</b>	
Name	EFFECTIVEDATE	
Datatype	Date	
Description	Specifies The Effective Date.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## RATESOURCE

Attribute	Description	
Name	RATESOURCE	
Datatype	String	
Description	Specifies The Rate Source.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

## RATESOURCEDESCRIPTION

Attribute	Description	
Name	RATESOURCEDESCRIPTION	
Datatype	String	
Description	Specifies The Rate Source Description.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

## MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	The User id who has booked the contract	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has booked the contract	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

## CHECKERID

Attribute	Description
Name	CHECKERID

Datatype	String	
Description	The User id who has authorized the booked contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has authorized the booked contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Specifies The Modification Number.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Specifies The Authorization Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	Specifies The Record Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorized.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Cftm-Rate-Detail

<b>Attribute</b>	<b>Description</b>	
Name	Cftm-Rate-Detail	
Datatype		
Description	Indicates The Rate Details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## RATETYPE

<b>Attribute</b>	<b>Description</b>	
Name	RATETYPE	
Datatype	String	
Description	Specifies The Rate Type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## RATETYPEDESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	RATETYPEDESCRIPTION	
Datatype	String	
Description	Specifies The Rate Type Description.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## INTERESTRATE

Attribute	Description				
Name	INTERESTRATE				
Datatype	Number				
Description	Specifies The Interest Rate.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## UDFDETAILS

Attribute	Description						
Name	UDFDETAILS						
Datatype							
Description	Indicates The UDF Details.						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

## FIELD\_NAME

Attribute	Description						
Name	FIELD_NAME						
Datatype	String						
Description	Indicates the User Defined Field Name.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	105	minLength	1
	Restrictions	Description					
	maxLength	105					
minLength	1						

[TOP](#)

## DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

[TOP](#)

## FIELD\_VALUE

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

[TOP](#)

## VAL\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2
	minLength	0

[TOP](#)

## 2.18.2.CF-ModifyCFFloatRateMaint-Req-IO-MSG.xsd

### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

### *FCUBS\_BODY*

*Cftm-Rate-Master-IO*

*RATECODE*

*TENORCODE*

*CCYCODE*

*EFFECTIVEDATE*

*MODNO*

*Cftm-Rate-Detail*

*RATETYPE*

*RATETYPEDESCRIPTION*

*INTERESTRATE*

*UDFDETAILS*

*FUNCTIONID*

*FIELD\_NAME*

*DATATYPE*

*FIELD\_VALUE*

*VAL\_TYPE*

### **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER

Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID



Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute		Description
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute		Description
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MSGSTAT**

Attribute		Description
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

**PASSWORD**

Attribute		Description
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

[TOP](#)

## Cftm-Rate-Master-IO

Attribute	Description
Name	Cftm-Rate-Master-IO
Datatype	
Description	Includes CF-Floating rate Maintenance-IO Modification details

**RATECODE**

Attribute		Description
Name	RATECODE	
Datatype	String	
Description	Specifies The Rate Code.	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

**TENORCODE**

Attribute		Description
Name	TENORCODE	
Datatype	String	
Description	Specifies The Tenor Code.	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	12

**CCYCODE**

Attribute		Description
Name	CCYCODE	
Datatype	String	
Description	Specifies The Currency Code.	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

**EFFECTIVEDATE**

Attribute		Description
Name	EFFECTIVEDATE	
Datatype	Date	
Description	Specifies The Effective Date.	
Attributes	Attribute	Description
	minOccurs	0

**MODNO**

Attribute		Description
Name	MODNO	

Datatype	Number	
Description	Specifies The Modification Number.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

## Cftm-Rate-Detail

<b>Attribute</b>	<b>Description</b>	
Name	Cftm-Rate-Detail	
Datatype		
Description	Specifies The Rate Details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	1

[TOP](#)

## RATETYPE

<b>Attribute</b>	<b>Description</b>	
Name	RATETYPE	
Datatype	String	
Description	Specifies The Rate Type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## RATETYPEDESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	RATETYPEDESCRIPTION	
Datatype	String	
Description	Specifies The Rate Type Description.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## INTERESTRATE

<b>Attribute</b>	<b>Description</b>	
Name	INTERESTRATE	
Datatype	Number	
Description	Specifies The Interest Type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

**UDFDETAILS**

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description	Indicates The UDF Details.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**FIELD\_NAME**

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

**DATATYPE**

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

**FIELD\_VALUE**

Attribute	Description
-----------	-------------

Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

[TOP](#)

## VAL\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2
	minLength	0

[TOP](#)



### 2.18.3.CF-ModifyCFFloatRateMaint-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Cftm-Rate-Master-IO*

*RATECODE*

*TENORCODE*

*CCYCODE*

*EFFECTIVEDATE*

*MODNO*

*Cftm-Rate-Detail*

*RATETYPE*

*RATETYPEDESCRIPTION*

*INTERESTRATE*

*UDFDETAILS*

*FUNCTIONID*

*FIELD\_NAME*

*DATATYPE*

*FIELD\_VALUE*

*VAL\_TYPE*

*Cftm-Rate-Master-Full*

*RATECODE*

RATECODEDESCRIPTION  
 TENORCODE  
 TENORCODEDESCRIPTION  
 CCYCODE  
 CCYNAME  
 EFFECTIVEDATE  
 RATESOURCE  
 RATESOURCEDESCRIPTION  
 MAKERID  
 MAKERDTSTAMP  
 CHECKERID  
 CHECKERDTSTAMP  
 MODNO  
 AUTHSTAT  
 RECSTAT  
 ONCEAUTH  
 Cftm-Rate-Detail  
     RATETYPE  
     RATETYPEDESCRIPTION  
     INTERESTRATE  
 UDFDETAILS  
     FUNCTIONID  
     FIELD\_NAME  
     DATATYPE  
     FIELD\_VALUE  
     VAL\_TYPE  
 FCUBS\_ERROR\_RESP  
     ERROR  
         ECODE  
         EDESC  
 FCUBS\_WARNING\_RESP  
     WARNING  
         WCODE  
         WDESC

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

**SOURCE**

Attribute	Description
Name	SOURCE

Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

<b>Attribute</b>	<b>Description</b>	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

**MODULEID**

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

**SERVICE**

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**OPERATION**

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description
Name	SOURCE_OPERATION

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about FullResponse	

[TOP](#)

## CHOICE

Attribute	Description	
Name	CHOICE	
Datatype		
Description		

[TOP](#)

## Cftm-Rate-Master-IO

Attribute	Description	
Name	Cftm-Rate-Master-IO	
Datatype		
Description	Includes CF-Floating rate Maintenance-IO Modification details	

[TOP](#)

## RATECODE

Attribute	Description				
Name	RATECODE				
Datatype	String				
Description	Specifies The Rate Code.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>10</td></tr></tbody></table>	Restrictions	Description	maxLength	10
	Restrictions	Description			
maxLength	10				

[TOP](#)

## TENORCODE

Attribute	Description				
Name	TENORCODE				
Datatype	String				
Description	Specifies The Tenor Code.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
	Restrictions	Description			
maxLength	12				

[TOP](#)

## CCYCODE

Attribute	Description				
Name	CCYCODE				
Datatype	String				
Description	Specifies The Currency Code.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

[TOP](#)

## EFFECTIVEDATE

Attribute	Description				
Name	EFFECTIVEDATE				
Datatype	Date				
Description	Specifies The Effective Date.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## MODNO

Attribute	Description
Name	MODNO
Datatype	Number



Description	Specifies The Modification Number.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

## Cftm-Rate-Detail

<b>Attribute</b>	<b>Description</b>	
Name	Cftm-Rate-Detail	
Datatype		
Description	Specifies The Rate Details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	1

[TOP](#)

## RATETYPE

<b>Attribute</b>	<b>Description</b>	
Name	RATETYPE	
Datatype	String	
Description	Specifies The Rate Type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## RATETYPEDESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	RATETYPEDESCRIPTION	
Datatype	String	
Description	Specifies The Rate Type Description.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## INTERESTRATE

<b>Attribute</b>	<b>Description</b>	
Name	INTERESTRATE	
Datatype	Number	
Description	Specifies The Interest Type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

**UDFDETAILS**

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description	Indicates The UDF Details.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**FIELD\_NAME**

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

**DATATYPE**

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

**FIELD\_VALUE**

Attribute	Description
-----------	-------------

Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

[TOP](#)

## VAL\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2
	minLength	0

[TOP](#)

## Cftm-Rate-Master-Full

<b>Attribute</b>	<b>Description</b>
Name	Cftm-Rate-Master-Full
Datatype	
Description	Includes CF-Floating rate Maintenance Modification details

[TOP](#)

## RATECODE

<b>Attribute</b>	<b>Description</b>	
Name	RATECODE	
Datatype	String	
Description	Specifies The Rate Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## RATECODEDESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	RATECODEDESCRIPTION	
Datatype	String	
Description	Specifies The Rate Code Description.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## TENORCODE

<b>Attribute</b>	<b>Description</b>	
Name	TENORCODE	
Datatype	String	
Description	Specifies The Tenor Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## TENORCODEDESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	TENORCODEDESCRIPTION	
Datatype	String	
Description	Specifies The Tenor Code Description.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## CCYCODE

<b>Attribute</b>	<b>Description</b>	
Name	CCYCODE	
Datatype	String	
Description	Specifies The Currency Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## CCYNAME

<b>Attribute</b>	<b>Description</b>	
Name	CCYNAME	
Datatype	String	
Description	Specifies The Currency Code Description.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

**EFFECTIVEDATE**

Attribute	Description	
Name	EFFECTIVEDATE	
Datatype	Date	
Description	Specifies The Effective Date.	
Attributes	Attribute	Description
	minOccurs	0

**RATESOURCE**

Attribute	Description	
Name	RATESOURCE	
Datatype	String	
Description	Specifies The Rate Source.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

**RATESOURCEDESCRIPTION**

Attribute	Description	
Name	RATESOURCEDESCRIPTION	
Datatype	String	
Description	Specifies The Rate Source Description.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

**MAKERID**

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	The User id who has booked the contract	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**MAKERDTSTAMP**

Attribute	Description
Name	MAKERDTSTAMP

Datatype	String	
Description	Indicates date and stamp when the user has booked the contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	The User id who has authorized the booked contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has authorized the booked contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Specifies The Modification Number.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Specifies The Authorization Status.	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	Specifies The Record Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorized.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Cftm-Rate-Detail

<b>Attribute</b>	<b>Description</b>	
Name	Cftm-Rate-Detail	
Datatype		
Description	Specifies The Rate Details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	1

[TOP](#)

## RATETYPE

<b>Attribute</b>	<b>Description</b>	
Name	RATETYPE	
Datatype	String	
Description	Specifies The Rate Type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

**RATETYPEDESCRIPTION**

Attribute	Description	
Name	RATETYPEDESCRIPTION	
Datatype	String	
Description	Specifies The Rate Type Description.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

**INTERESTRATE**

Attribute	Description	
Name	INTERESTRATE	
Datatype	Number	
Description	Specifies The Interest Type.	
Attributes	Attribute	Description
	minOccurs	0

**UDFDETAILS**

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description	Indicates The UDF Details.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**FIELD\_NAME**

Attribute	Description
Name	FIELD_NAME



Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

[TOP](#)

## DATATYPE

<b>Attribute</b>	<b>Description</b>	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

[TOP](#)

## FIELD\_VALUE

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

[TOP](#)

## VAL\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2
	minLength	0

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

<b>Attribute</b>	<b>Description</b>	
Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.18.4.CF-ModifyCFFloatRateMaint-Res-PK-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Cftm-Rate-Master-PK*

*RATECODE*

*TENORCODE*

*CCYCODE*

*EFFECTIVEDATE*

*Cftm-Rate-Master-IO*

*RATECODE*

*TENORCODE*

*CCYCODE*

*EFFECTIVEDATE*

*MODNO*

*Cftm-Rate-Detail*

*RATETYPE*

*RATETYPEDESCRIPTION*

*INTERESTRATE*

*UDFDETAILS*

*FUNCTIONID*

*FIELD\_NAME*

DATATYPE  
FIELD\_VALUE  
VAL\_TYPE

*Cftm-Rate-Master-Full*

RATECODE  
RATECODEDESCRIPTION  
TENORCODE  
TENORCODEDESCRIPTION  
CCYCODE  
CCYNAME  
EFFECTIVEDATE  
RATESOURCE  
RATESOURCEDESCRIPTION  
MAKERID  
MAKERDTSTAMP  
CHECKERID  
CHECKERDTSTAMP  
MODNO  
AUTHSTAT  
RECSTAT  
ONCEAUTH

*Cftm-Rate-Detail*

RATETYPE  
RATETYPEDESCRIPTION  
INTERESTRATE  
UDFDETAILS  
FUNCTIONID  
FIELD\_NAME  
DATATYPE  
FIELD\_VALUE  
VAL\_TYPE

*FCUBS\_ERROR\_RESP*

ERROR  
ECODE  
EDESC

*FCUBS\_WARNING\_RESP*

WARNING  
WCODE  
WDESC

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

**SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**UBSCOMP**

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description
Name	USERID

Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute		Description
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	
	minOccurs	0
	nullable	true
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute		Description
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	
	minOccurs	0
	nullable	true

**DESTINATION**

Attribute		Description
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	
	minOccurs	0
	nullable	true
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute		Description
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	
	minOccurs	0
	nullable	true
Restrictions	Restrictions	
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**



Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Cftm-Rate-Master-PK

Attribute	Description
Name	Cftm-Rate-Master-PK
Datatype	
Description	Includes CF-Floating rate Maintenance-Primary key Modification details

[TOP](#)

## RATECODE

Attribute	Description				
Name	RATECODE				
Datatype	String				
Description	Specifies The Rate Code.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>10</td></tr></tbody></table>	Restrictions	Description	maxLength	10
	Restrictions	Description			
maxLength	10				

[TOP](#)

## TENORCODE

Attribute	Description				
Name	TENORCODE				
Datatype	String				
Description	Specifies The Tenor Code.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
	Restrictions	Description			
maxLength	12				

[TOP](#)

## CCYCODE

Attribute	Description				
Name	CCYCODE				
Datatype	String				
Description	Specifies The Currency Code.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

[TOP](#)

## EFFECTIVEDATE

Attribute	Description
Name	EFFECTIVEDATE
Datatype	Date
Description	Specifies The Effective Date.

**Cftm-Rate-Master-IO**

Attribute	Description
Name	Cftm-Rate-Master-IO
Datatype	
Description	Includes CF-Floating rate Maintenance-IO Modification details

**RATECODE**

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description	Specifies The Rate Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

**TENORCODE**

Attribute	Description	
Name	TENORCODE	
Datatype	String	
Description	Specifies The Tenor Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CCYCODE**

Attribute	Description	
Name	CCYCODE	
Datatype	String	
Description	Specifies The Currency Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

**EFFECTIVEDATE**

Attribute	Description
Name	EFFECTIVEDATE
Datatype	Date
Description	Specifies The Effective Date.

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Specifies The Modification Number.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

**Cftm-Rate-Detail**

Attribute	Description	
Name	Cftm-Rate-Detail	
Datatype		
Description	Specifies The Rate Details.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	1

**RATETYPE**

Attribute	Description	
Name	RATETYPE	
Datatype	String	
Description	Specifies The Rate Type.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**RATETYPEDESCRIPTION**

Attribute	Description	
Name	RATETYPEDESCRIPTION	
Datatype	String	
Description	Specifies The Rate Type Description.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

**INTERESTRATE**

Attribute	Description
-----------	-------------

Name	INTERESTRATE	
Datatype	Number	
Description	Specifies The Interest Type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description	Indicates The UDF Details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## FIELD\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

[TOP](#)

## DATATYPE

<b>Attribute</b>	<b>Description</b>	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

**FIELD\_VALUE**

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

**VAL\_TYPE**

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

**Cftm-Rate-Master-Full**

Attribute	Description
Name	Cftm-Rate-Master-Full
Datatype	
Description	Includes CF-Floating rate Maintenance Modification details

**RATECODE**

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description	Specifies The Rate Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

**RATECODEDESCRIPTION**

Attribute	Description
Name	RATECODEDESCRIPTION

Datatype	String	
Description	Specifies The Rate Code Description.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## TENORCODE

<b>Attribute</b>	<b>Description</b>	
Name	TENORCODE	
Datatype	String	
Description	Specifies The Tenor Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## TENORCODEDESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	TENORCODEDESCRIPTION	
Datatype	String	
Description	Specifies The Tenor Code Description.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## CCYCODE

<b>Attribute</b>	<b>Description</b>	
Name	CCYCODE	
Datatype	String	
Description	Specifies The Currency Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## CCYNAME

<b>Attribute</b>	<b>Description</b>	
Name	CCYNAME	
Datatype	String	
Description	Specifies The Currency Code Description.	



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## EFFECTIVEDATE

<b>Attribute</b>	<b>Description</b>
Name	EFFECTIVEDATE
Datatype	Date
Description	Specifies The Effective Date.

[TOP](#)

## RATESOURCE

<b>Attribute</b>	<b>Description</b>	
Name	RATESOURCE	
Datatype	String	
Description	Specifies The Rate Source.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## RATESOURCEDESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	RATESOURCEDESCRIPTION	
Datatype	String	
Description	Specifies The Rate Source Description.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	The User id who has booked the contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has booked the contract	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

## CHECKERID

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	The User id who has authorized the booked contract	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has authorized the booked contract	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Specifies The Modification Number.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

[TOP](#)

## AUTHSTAT

Attribute	Description
Name	AUTHSTAT

Datatype	String	
Description	Specifies The Authorization Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	Specifies The Record Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorized.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Cftm-Rate-Detail

<b>Attribute</b>	<b>Description</b>	
Name	Cftm-Rate-Detail	
Datatype		
Description	Specifies The Rate Details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	1

[TOP](#)

## RATETYPE

<b>Attribute</b>	<b>Description</b>	
Name	RATETYPE	
Datatype	String	
Description	Specifies The Rate Type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## RATETYPEDESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	RATETYPEDESCRIPTION	
Datatype	String	
Description	Specifies The Rate Type Description.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## INTERESTRATE

<b>Attribute</b>	<b>Description</b>	
Name	INTERESTRATE	
Datatype	Number	
Description	Specifies The Interest Type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description	Indicates The UDF Details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## FIELD\_NAME

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

[TOP](#)

## DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

## FIELD\_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

[TOP](#)

## VAL\_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description

Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

<b>Attribute</b>	<b>Description</b>	
Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.19.ModifyCFRateCodeMaint

Modification of Rate Code Maintenance

### 2.19.1.CF-ModifyCFRateCodeMaint-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Cftm-Rate-Code-Defn-Full*

*RATECODE*

*RATECODEDESCRIPTION*

*HOLIDAYCCY*

*PROPAGATIONACROSSBRANCHES*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

*Cftm-Tenor-Code-Defn*

*TENORCODE*

*TENORCODEDESCRIPTION*



UDFDETAILS  
 FUNCTIONID  
 FIELD\_NAME  
 DATATYPE  
 FIELD\_VALUE  
 VAL\_TYPE

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description						
Name	MSGID						
Datatype	String						
Description							
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nullable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	nullable	true
	Attribute	Description					
	minOccurs	0					
nullable	true						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*		
	Restrictions	Description					
pattern	[a-zA-Z_0-9]*						

[TOP](#)

## CORRELID

Attribute	Description
Name	CORRELID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nilable	true

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nilable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description
-----------	-------------

Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about FullRequest	

**Cftm-Rate-Code-Defn-Full**

Attribute	Description
Name	Cftm-Rate-Code-Defn-Full
Datatype	
Description	Includes CF-Rate Code Maintenance Modification details

**RATECODE**

Attribute	Description				
Name	RATECODE				
Datatype	String				
Description	Indicates Rate Code.				
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>10</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	10
	Restrictions	Description			
maxLength	10				

**RATECODEDESCRIPTION**

Attribute	Description				
Name	RATECODEDESCRIPTION				
Datatype	String				
Description	Indicates the description of rate code				
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>105</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	105
	Restrictions	Description			
maxLength	105				

**HOLIDAYCCY**

Attribute	Description				
Name	HOLIDAYCCY				
Datatype	String				
Description	Specifies Holiday Currency .				
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>maxLength</td> <td>3</td> </tr> </tbody> </table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

**PROPAGATIONACROSSBRANCHES**

Attribute	Description
Name	PROPAGATIONACROSSBRANCHES
Datatype	String
Description	Propagate Across Branches

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Specifies the User id who has saved the record.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates the date and time when the user has saved the record.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates the User id who has authorized the record.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has authorized the booked contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	It indicates the modification number.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	It indicates the status of the record,whether open or Closed.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorized.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Cftm-Tenor-Code-Defn



Attribute	Description	
Name	Cftm-Tenor-Code-Defn	
Datatype		
Description	Includes Tenor code details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## TENORCODE

Attribute	Description	
Name	TENORCODE	
Datatype	String	
Description	Indicates the tenor code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

## TENORCODEDESCRIPTION

Attribute	Description	
Name	TENORCODEDESCRIPTION	
Datatype	String	
Description	Indicates the description of tenor code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

## UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FUNCTIONID

Attribute	Description
Name	FUNCTIONID
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## FIELD\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

[TOP](#)

## DATATYPE

<b>Attribute</b>	<b>Description</b>	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

[TOP](#)

## FIELD\_VALUE

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

[TOP](#)

## VAL\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

[TOP](#)

## 2.19.2.CF-ModifyCFRateCodeMaint-Req-IO-MSG.xsd

### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

### *FCUBS\_BODY*

*Cftm-Rate-Code-Defn-IO*

*RATECODE*

*RATECODEDESCRIPTION*

*HOLIDAYCCY*

*MODNO*

*Cftm-Tenor-Code-Defn*

*TENORCODE*

*TENORCODEDESCRIPTION*

*UDFDETAILS*

*FUNCTIONID*

*FIELD\_NAME*

*DATATYPE*

*FIELD\_VALUE*

*VAL\_TYPE*

### **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

**SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**UBSCOMP**

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description
Name	USERID

Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTITRIPID**

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL



Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

[TOP](#)

## Cftm-Rate-Code-Defn-IO

Attribute	Description
Name	Cftm-Rate-Code-Defn-IO
Datatype	
Description	Includes CF-Rate Code Maintenance Modification-IO details

[TOP](#)

## RATECODE

Attribute	Description				
Name	RATECODE				
Datatype	String				
Description	Indicates Rate code.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>10</td></tr></tbody></table>	Restrictions	Description	maxLength	10
	Restrictions	Description			
maxLength	10				

[TOP](#)

## RATECODEDESCRIPTION

Attribute	Description				
Name	RATECODEDESCRIPTION				
Datatype	String				
Description	Indicates the description of Rate Code				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>105</td></tr></tbody></table>	Restrictions	Description	maxLength	105
	Restrictions	Description			
maxLength	105				

[TOP](#)

## HOLIDAYCCY

Attribute	Description				
Name	HOLIDAYCCY				
Datatype	String				
Description	Specifies Holiday Currency.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

[TOP](#)

## MODNO

Attribute	Description				
Name	MODNO				
Datatype	Number				
Description	It indicates the modification number.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>totalDigits</td><td>22</td></tr></tbody></table>	Restrictions	Description	totalDigits	22
	Restrictions	Description			
totalDigits	22				

[TOP](#)

## Cftm-Tenor-Code-Defn

Attribute	Description
-----------	-------------

Name	Cftm-Tenor-Code-Defn	
Datatype		
Description	Includes Tenor code details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	1

[TOP](#)

## TENORCODE

<b>Attribute</b>	<b>Description</b>	
Name	TENORCODE	
Datatype	String	
Description	Indicates the tenor code	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## TENORCODEDESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	TENORCODEDESCRIPTION	
Datatype	String	
Description	Indicates the description of tenor code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## FIELD\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

[TOP](#)

## DATATYPE

<b>Attribute</b>	<b>Description</b>	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

[TOP](#)

## FIELD\_VALUE

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

[TOP](#)

## VAL\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2
	minLength	0

[TOP](#)

## 2.19.3.CF-ModifyCFRateCodeMaint-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Cftm-Rate-Code-Defn-IO*

*RATECODE*

*RATECODEDESCRIPTION*

*HOLIDAYCCY*

*MODNO*

*Cftm-Tenor-Code-Defn*

*TENORCODE*

*TENORCODEDESCRIPTION*

*UDFDETAILS*

*FUNCTIONID*

*FIELD\_NAME*

*DATATYPE*

*FIELD\_VALUE*

*VAL\_TYPE*

*Cftm-Rate-Code-Defn-Full*

*RATECODE*

*RATECODEDESCRIPTION*

*HOLIDAYCCY*

PROPAGATIONACROSSBRANCHES  
 MAKERID  
 MAKERDTSTAMP  
 CHECKERID  
 CHECKERDTSTAMP  
 MODNO  
 AUTHSTAT  
 RECSTAT  
 ONCEAUTH  
 Cftm-Tenor-Code-Defn  
     TENORCODE  
     TENORCODEDESCRIPTION  
 UDFDETAILS  
     FUNCTIONID  
     FIELD\_NAME  
     DATATYPE  
     FIELD\_VALUE  
     VAL\_TYPE  
 FCUBS\_ERROR\_RESP  
     ERROR  
         ECODE  
         EDESC  
 FCUBS\_WARNING\_RESP  
     WARNING  
         WCODE  
         WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description
Name	UBSCOMP

Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

**MODULEID**

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

**SERVICE**

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**OPERATION**

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**



Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description
Name	ACTION

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**NAME**

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)**VALUE**

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

[TOP](#)**CHOICE**

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)**Cftm-Rate-Code-Defn-IO**

Attribute	Description
Name	Cftm-Rate-Code-Defn-IO
Datatype	
Description	Includes CF-Rate Code Maintenance Modification-IO details

[TOP](#)**RATECODE**

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description	Indicates Rate code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

**RATECODEDESCRIPTION**

Attribute	Description	
Name	RATECODEDESCRIPTION	
Datatype	String	
Description	Indicates the description of Rate Code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

**HOLIDAYCCY**

Attribute	Description	
Name	HOLIDAYCCY	
Datatype	String	
Description	Specifies Holiday Currency.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	It indicates the modification number.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

**Cftm-Tenor-Code-Defn**

Attribute	Description	
Name	Cftm-Tenor-Code-Defn	
Datatype		
Description	Includes Tenor code details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	1

**TENORCODE**

Attribute	Description
-----------	-------------

Name	TENORCODE	
Datatype	String	
Description	Indicates the tenor code	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## TENORCODEDESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	TENORCODEDESCRIPTION	
Datatype	String	
Description	Indicates the description of tenor code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## FIELD\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

[TOP](#)

## DATATYPE

<b>Attribute</b>	<b>Description</b>	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

[TOP](#)

## FIELD\_VALUE

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

[TOP](#)

## VAL\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2
	minLength	0

[TOP](#)

## Cftm-Rate-Code-Defn-Full

<b>Attribute</b>	<b>Description</b>
Name	Cftm-Rate-Code-Defn-Full
Datatype	
Description	Includes CF-Rate Code Maintenance Modification details

[TOP](#)

## RATECODE

Attribute	Description				
Name	RATECODE				
Datatype	String				
Description	Indicates Rate code.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>10</td></tr></tbody></table>	Restrictions	Description	maxLength	10
	Restrictions	Description			
maxLength	10				

[TOP](#)

## RATECODEDESCRIPTION

Attribute	Description				
Name	RATECODEDESCRIPTION				
Datatype	String				
Description	Indicates the description of Rate Code				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>105</td></tr></tbody></table>	Restrictions	Description	maxLength	105
	Restrictions	Description			
maxLength	105				

[TOP](#)

## HOLIDAYCCY

Attribute	Description				
Name	HOLIDAYCCY				
Datatype	String				
Description	Specifies Holiday Currency.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

[TOP](#)

## PROPAGATIONACROSSBRANCHES

Attribute	Description				
Name	PROPAGATIONACROSSBRANCHES				
Datatype	String				
Description	Propagate Across Branches				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	1
	Restrictions	Description			
maxLength	1				

[TOP](#)

## MAKERID

Attribute	Description
-----------	-------------

Name	MAKERID	
Datatype	String	
Description	Specifies the User id who has saved the record.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates the date and time when the user has saved the record.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates the User id who has authorized the record.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has authorized the booked contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	It indicates the modification number.	



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	It indicates the status of the record,whether open or Closed.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorized.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Cftm-Tenor-Code-Defn

<b>Attribute</b>	<b>Description</b>	
Name	Cftm-Tenor-Code-Defn	
Datatype		
Description	Includes Tenor code details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	1

**TENORCODE**

Attribute	Description	
Name	TENORCODE	
Datatype	String	
Description	Indicates the tenor code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

**TENORCODEDESCRIPTION**

Attribute	Description	
Name	TENORCODEDESCRIPTION	
Datatype	String	
Description	Indicates the description of tenor code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

**UDFDETAILS**

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**FIELD\_NAME**

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

[TOP](#)

## DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

## FIELD\_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

[TOP](#)

## VAL\_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description

Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

<b>Attribute</b>	<b>Description</b>	
Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.19.4.CF-ModifyCFRateCodeMaint-Res-PK-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Cftm-Rate-Code-Defn-PK*

*RATECODE*

*Cftm-Rate-Code-Defn-IO*

*RATECODE*

*RATECODEDESCRIPTION*

*HOLIDAYCCY*

*MODNO*

*Cftm-Tenor-Code-Defn*

*TENORCODE*

*TENORCODEDESCRIPTION*

*UDFDETAILS*

*FUNCTIONID*

*FIELD\_NAME*

*DATATYPE*

*FIELD\_VALUE*

*VAL\_TYPE*

*Cftm-Rate-Code-Defn-Full*

*RATECODE*

RATECODEDESCRIPTION  
 HOLIDAYCCY  
 PROPAGATIONACROSSBRANCHES  
 MAKERID  
 MAKERDTSTAMP  
 CHECKERID  
 CHECKERDTSTAMP  
 MODNO  
 AUTHSTAT  
 RECSTAT  
 ONCEAUTH  
 Cftm-Tenor-Code-Defn  
     TENORCODE  
     TENORCODEDESCRIPTION  
 UDFDETAILS  
     FUNCTIONID  
     FIELD\_NAME  
     DATATYPE  
     FIELD\_VALUE  
     VAL\_TYPE  
 FCUBS\_ERROR\_RESP  
     ERROR  
         ECODE  
         EDESC  
 FCUBS\_WARNING\_RESP  
     WARNING  
         WCODE  
         WDESC

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

**SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description
Name	BRANCH
Datatype	String



Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Cftm-Rate-Code-Defn-PK

Attribute	Description
Name	Cftm-Rate-Code-Defn-PK
Datatype	
Description	Includes CF-Rate Code Maintenance Modification-Primary key details

[TOP](#)

## RATECODE

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description	Indicates Rate Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## Cftm-Rate-Code-Defn-IO

Attribute	Description
Name	Cftm-Rate-Code-Defn-IO
Datatype	
Description	Includes CF-Rate Code Maintenance Modification-IO details

[TOP](#)

## RATECODE

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description	Indicates Rate Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## RATECODEDESCRIPTION

Attribute	Description	
Name	RATECODEDESCRIPTION	
Datatype	String	
Description	Indicates the description of Rate Code	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## HOLIDAYCCY

Attribute	Description	
Name	HOLIDAYCCY	
Datatype	String	
Description	Specifies Holiday Currency.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## MODNO

Attribute	Description
Name	MODNO

Datatype	Number	
Description	It indicates the modification number.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

## Cftm-Tenor-Code-Defn

<b>Attribute</b>	<b>Description</b>	
Name	Cftm-Tenor-Code-Defn	
Datatype		
Description	Includes Tenor code details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	1

[TOP](#)

## TENORCODE

<b>Attribute</b>	<b>Description</b>	
Name	TENORCODE	
Datatype	String	
Description	Indicates the tenor code	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## TENORCODEDESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	TENORCODEDESCRIPTION	
Datatype	String	
Description	Indicates the description of tenor code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

**FUNCTIONID**

Attribute		Description
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**FIELD\_NAME**

Attribute		Description
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

**DATATYPE**

Attribute		Description
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

**FIELD\_VALUE**

Attribute		Description
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

## VAL\_TYPE

Attribute	Description						
Name	VAL_TYPE						
Datatype	String						
Description	Indicates Value type.						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>2</td></tr><tr><td>minLength</td><td>0</td></tr></tbody></table>	Restrictions	Description	maxLength	2	minLength	0
	Restrictions	Description					
	maxLength	2					
minLength	0						

[TOP](#)

## Cftm-Rate-Code-Defn-Full

Attribute	Description
Name	Cftm-Rate-Code-Defn-Full
Datatype	
Description	Includes CF-Rate Code Maintenance Modification details

[TOP](#)

## RATECODE

Attribute	Description				
Name	RATECODE				
Datatype	String				
Description	Indicates Rate Code.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>10</td></tr></tbody></table>	Restrictions	Description	maxLength	10
	Restrictions	Description			
maxLength	10				

[TOP](#)

## RATECODEDESCRIPTION

Attribute	Description				
Name	RATECODEDESCRIPTION				
Datatype	String				
Description	Indicates the description of Rate Code				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>105</td></tr></tbody></table>	Restrictions	Description	maxLength	105
	Restrictions	Description			
maxLength	105				

[TOP](#)

## HOLIDAYCCY

Attribute	Description
Name	HOLIDAYCCY
Datatype	String
Description	Specifies Holiday Currency.



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## PROPAGATIONACROSSBRANCHES

<b>Attribute</b>	<b>Description</b>	
Name	PROPAGATIONACROSSBRANCHES	
Datatype	String	
Description	Propagate Across Branches	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Specifies the User id who has saved the record.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates the date and time when the user has saved the record.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates the User id who has authorized the record.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has authorized the booked contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	It indicates the modification number.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	It indicates the status of the record,whether open or Closed.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

**ONCEAUTH**

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorized.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**Cftm-Tenor-Code-Defn**

Attribute	Description	
Name	Cftm-Tenor-Code-Defn	
Datatype		
Description	Includes Tenor code details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	1

**TENORCODE**

Attribute	Description	
Name	TENORCODE	
Datatype	String	
Description	Indicates the tenor code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

**TENORCODEDESCRIPTION**

Attribute	Description	
Name	TENORCODEDESCRIPTION	
Datatype	String	
Description	Indicates the description of tenor code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

**UDFDETAILS**

Attribute	Description
-----------	-------------

Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## FIELD\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

[TOP](#)

## DATATYPE

<b>Attribute</b>	<b>Description</b>	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

[TOP](#)

## FIELD\_VALUE

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

[TOP](#)

## VAL\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2
	minLength	0

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.20.ModifyCFRateTypeDefn

Modification of Rate Type Maintenance

### 2.20.1.CF-ModifyCFRateTypeDefn-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Cftm-Rate-Type-Defn-Full*

*RATETYPE*

*RATETYPEDESCRIPTION*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

*UDFDETAILS*

*FUNCTIONID*

*FIELD\_NAME*

*DATATYPE*

*FIELD\_VALUE*

[VAL\\_TYPE](#)

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

**SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

**UBSCOMP**

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true



Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description
-----------	-------------

Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

[TOP](#)

## Cftm-Rate-Type-Defn-Full

Attribute	Description
-----------	-------------

Name	Cftm-Rate-Type-Defn-Full
Datatype	
Description	Includes CF-Rate Type Maintenance Modification details

[TOP](#)

## RATETYPE

Attribute	Description	
Name	RATETYPE	
Datatype	String	
Description	Indicates The Rate Type.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## RATETYPEDESCRIPTION

Attribute	Description	
Name	RATETYPEDESCRIPTION	
Datatype	String	
Description	Indicates The Rate Type Description.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

## MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	The User Id who has created\last modified the Rate Type Definition details.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates Date and Stamp when the user hascreated\last modified the Rate Type Definition details.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

**CHECKERID**

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	The User Id who has Authorized the creation\modification of Rate Type Definition details.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CHECKERDTSTAMP**

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates Date and Stamp when the user has Authorized the creation\ modification of Rate Type Definition details.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number i.e. the number of times Rate Type Definition detail has been modified.	
Attributes	Attribute	Description
	minOccurs	0

**AUTHSTAT**

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status. A - Authorized U - Unauthorized	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**RECSTAT**

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Indicates the Record Status O - Open C - Close	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**ONCEAUTH**

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates whether Rate Type Definition detail has been Authorized atleast Once.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**UDFDETAILS**

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**FIELD\_NAME**

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

**DATATYPE**

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

**FIELD\_VALUE**

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

**VAL\_TYPE**

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
	minLength	0



## 2.20.2.CF-ModifyCFRateTypeDefn-Req-IO-MSG.xsd

### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

### *FCUBS\_BODY*

*Cftm-Rate-Type-Defn-IO*

*RATETYPE*

*RATETYPEDESCRIPTION*

*MODNO*

*UDFDETAILS*

*FUNCTIONID*

*FIELD\_NAME*

*DATATYPE*

*FIELD\_VALUE*

*VAL\_TYPE*

### **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

### **SOURCE**

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

<b>Attribute</b>	<b>Description</b>	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description
Name	SOURCE_OPERATION

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about IORequest	

[TOP](#)

## Cftm-Rate-Type-Defn-IO

Attribute	Description	
Name	Cftm-Rate-Type-Defn-IO	
Datatype		
Description	Includes CF-Rate Type Maintenance Modification-IO details	

[TOP](#)

## RATETYPE

Attribute	Description	
Name	RATETYPE	
Datatype	String	
Description	Indicates the Rate Type.	
Attributes	Attribute	Description
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## RATETYPEDESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	RATETYPEDESCRIPTION	
Datatype	String	
Description	Indicates the Rate Type Description.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number i.e. the number of times the Rate Type Definition detail has been modified.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

**FIELD\_NAME**

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

**DATATYPE**

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

**FIELD\_VALUE**

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

**VAL\_TYPE**

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
	minLength	0



### 2.20.3.CF-ModifyCFRateTypeDefn-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Cftm-Rate-Type-Defn-IO*

*RATETYPE*

*RATETYPEDESCRIPTION*

*MODNO*

*UDFDETAILS*

*FUNCTIONID*

*FIELD\_NAME*

*DATATYPE*

*FIELD\_VALUE*

*VAL\_TYPE*

*Cftm-Rate-Type-Defn-Full*

*RATETYPE*

*RATETYPEDESCRIPTION*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

AUTHSTAT  
 RECSTAT  
 ONCEAUTH  
 UDFDETAILS  
 FUNCTIONID  
 FIELD\_NAME  
 DATATYPE  
 FIELD\_VALUE  
 VAL\_TYPE  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description
Name	MSGID

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description				
Name	MSGSTAT				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></tbody></table>	Restrictions	Description	enumeration	SUCCESS,WARNING,FAILURE
	Restrictions	Description			
enumeration	SUCCESS,WARNING,FAILURE				

[TOP](#)

## PASSWORD

Attribute	Description						
Name	PASSWORD						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+/*]</td></tr></tbody></table>	Restrictions	Description	maxLength	128	pattern	[a-zA-Z_0-9=+/*]
	Restrictions	Description					
	maxLength	128					
pattern	[a-zA-Z_0-9=+/*]						

[TOP](#)

## ADDL

Attribute	Description				
Name	ADDL				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## PARAM

Attribute	Description						
Name	PARAM						
Datatype							
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Cftm-Rate-Type-Defn-IO

Attribute	Description
Name	Cftm-Rate-Type-Defn-IO
Datatype	
Description	Includes CF-Rate Type Maintenance Modification-IO details

[TOP](#)

## RATETYPE

Attribute	Description	
Name	RATETYPE	
Datatype	String	
Description	Indicates the Rate Type.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## RATETYPEDESCRIPTION

Attribute	Description
Name	RATETYPEDESCRIPTION
Datatype	String
Description	Indicates the Rate Type Description.

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number i.e. the number of times the Rate Type Definition detail has been modified.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## FIELD\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1



**DATATYPE**

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

**FIELD\_VALUE**

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

**VAL\_TYPE**

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

**Cftm-Rate-Type-Defn-Full**

Attribute	Description
Name	Cftm-Rate-Type-Defn-Full
Datatype	
Description	Includes CF-Rate Type Maintenance Modification details

**RATETYPE**

Attribute	Description
Name	RATETYPE

Datatype	String	
Description	Indicates the Rate Type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## RATETYPEDESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	RATETYPEDESCRIPTION	
Datatype	String	
Description	Indicates the Rate Type Description.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	The User Id who has created\last modified the Rate Type Definition details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates Date and Stamp when the user hascreated\last modified the Rate Type Definition details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	The User Id who has Authorized the creation\modification of Rate Type Definition details.	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates Date and Stamp when the user has Authorized the creation\ modification of Rate Type Definition details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number i.e. the number of times the Rate Type Definition detail has been modified.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status. A - Authorized U - Unauthorized	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	

Description	Indicates the Record Status O - Open C - Close	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates whether Rate Type Definition detail has been Authorized atleast Once.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## FIELD\_NAME

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

[TOP](#)

## DATATYPE

<b>Attribute</b>	<b>Description</b>	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

[TOP](#)

## FIELD\_VALUE

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

[TOP](#)

## VAL\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2
	minLength	0

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**ERROR**

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**ECODE**

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)**EDESC**

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)**FCUBS\_WARNING\_RESP**

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**WARNING**

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**WCODE**

Attribute	Description
Name	WCODE

Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.20.4.CF-ModifyCFRateTypeDefn-Res-PK-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Cftm-Rate-Type-Defn-PK*

*RATETYPE*

*Cftm-Rate-Type-Defn-IO*

*RATETYPE*

*RATETYPEDESCRIPTION*

*MODNO*

*UDFDETAILS*

*FUNCTIONID*

*FIELD\_NAME*

*DATATYPE*

*FIELD\_VALUE*

*VAL\_TYPE*

*Cftm-Rate-Type-Defn-Full*

*RATETYPE*

*RATETYPEDESCRIPTION*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*



CHECKERDTSTAMP  
 MODNO  
 AUTHSTAT  
 RECSTAT  
 ONCEAUTH  
 UDFDETAILS  
 FUNCTIONID  
 FIELD\_NAME  
 DATATYPE  
 FIELD\_VALUE  
 VAL\_TYPE  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description				
Name	MSGSTAT				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></tbody></table>	Restrictions	Description	enumeration	SUCCESS,WARNING,FAILURE
	Restrictions	Description			
enumeration	SUCCESS,WARNING,FAILURE				

[TOP](#)

## PASSWORD

Attribute	Description						
Name	PASSWORD						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+]*</td></tr></tbody></table>	Restrictions	Description	maxLength	128	pattern	[a-zA-Z_0-9=+]*
	Restrictions	Description					
	maxLength	128					
pattern	[a-zA-Z_0-9=+]*						

[TOP](#)

## ADDL

Attribute	Description				
Name	ADDL				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## PARAM

Attribute	Description						
Name	PARAM						
Datatype							
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Cftm-Rate-Type-Defn-PK

Attribute	Description
Name	Cftm-Rate-Type-Defn-PK
Datatype	
Description	Includes CF-Rate Type Maintenance Modification-Primary key details

[TOP](#)

## RATETYPE

Attribute	Description	
Name	RATETYPE	
Datatype	String	
Description	Indicates The Rate Type.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## Cftm-Rate-Type-Defn-IO

Attribute	Description
Name	Cftm-Rate-Type-Defn-IO
Datatype	
Description	Includes CF-Rate Type Maintenance Modification-IO details

**RATETYPE**

Attribute	Description	
Name	RATETYPE	
Datatype	String	
Description	Indicates The Rate Type.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**RATETYPEDESCRIPTION**

Attribute	Description	
Name	RATETYPEDESCRIPTION	
Datatype	String	
Description	Indicates the Rate Type Description.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number i.e. the number of times the Rate Type Definition detail has been modified.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

**UDFDETAILS**

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## FIELD\_NAME

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

[TOP](#)

## DATATYPE

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

## FIELD\_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

[TOP](#)

## VAL\_TYPE

Attribute	Description
-----------	-------------



Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2
	minLength	0

[TOP](#)

## Cftm-Rate-Type-Defn-Full

Attribute	Description
Name	Cftm-Rate-Type-Defn-Full
Datatype	
Description	Includes CF-Rate Type Maintenance Modification details

[TOP](#)

## RATETYPE

Attribute	Description	
Name	RATETYPE	
Datatype	String	
Description	Indicates The Rate Type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## RATETYPEDESCRIPTION

Attribute	Description	
Name	RATETYPEDESCRIPTION	
Datatype	String	
Description	Indicates the Rate Type Description.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	The User Id who has created\last modified the Rate Type Definition details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

**MAKERDTSTAMP**

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates Date and Stamp when the user has created/last modified the Rate Type Definition details.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

**CHECKERID**

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	The User Id who has Authorized the creation/modification of Rate Type Definition details.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CHECKERDTSTAMP**

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates Date and Stamp when the user has Authorized the creation/modification of Rate Type Definition details.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number i.e. the number of times the Rate Type Definition detail has been modified.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

**AUTHSTAT**

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status. A - Authorized U - Unauthorized	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**RECSTAT**

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Indicates the Record Status O - Open C - Close	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**ONCEAUTH**

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates whether Rate Type Definition detail has been Authorized atleast Once.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**UDFDETAILS**

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**FIELD\_NAME**

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

**DATATYPE**

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

**FIELD\_VALUE**

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

## VAL\_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description	
Name	WCODE	
Datatype	String	
Description		

[TOP](#)

## WDESC

Attribute	Description	
Name	WDESC	
Datatype	String	
Description		

[TOP](#)

## 2.21.ModifyFLTRTDefn

Modification of Floating rate Maintenance

### 2.21.1.CF-ModifyFLTRTDefn-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Cftms-Rate-Code-Details-Full*

*RATECODE*

*RATEDESC*

*BRANCHCODE*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

*Cftms-Rate-Ccy-Details*

*CCYCODE*

*Cftms-Float-Rate-Master-Details*

*AMNTSLAB*

EFFECTDATE  
 BRWLENDINDCR  
 Cftms-Float-Rate-Detail-Description  
 TENORTO  
 INTRATE  
 UDFDETAILS  
 FUNCTIONID  
 FIELD\_NAME  
 DATATYPE  
 FIELD\_VALUE  
 VAL\_TYPE

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*



**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

**MODULEID**

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

**SERVICE**

Attribute	Description
Name	SERVICE
Datatype	String

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

[TOP](#)

## Cftms-Rate-Code-Details-Full

Attribute	Description
Name	Cftms-Rate-Code-Details-Full
Datatype	
Description	Includes CF-Floating rate modification details

[TOP](#)

## RATECODE

Attribute	Description				
Name	RATECODE				
Datatype	String				
Description	Specifies The Rate Code.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>10</td></tr></tbody></table>	Restrictions	Description	maxLength	10
	Restrictions	Description			
maxLength	10				

[TOP](#)

## RATEDESC

Attribute	Description				
Name	RATEDESC				
Datatype	String				
Description	Specifies The Rate Description.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>105</td></tr></tbody></table>	Restrictions	Description	maxLength	105
	Restrictions	Description			
maxLength	105				

[TOP](#)

## BRANCHCODE

Attribute	Description				
Name	BRANCHCODE				
Datatype	String				
Description	Specifies The Branch Code.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

**MAKERID**

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	The User id who has booked the contract	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**MAKERDTSTAMP**

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has booked the contract	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

**CHECKERID**

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Specifies The Checker Identification.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CHECKERDTSTAMP**

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has authorized the booked contract	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Specifies The Modification Number.	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Specifies The Authorization Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Specifies The Record Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorized.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## Cftms-Rate-Ccy-Details

Attribute	Description
Name	Cftms-Rate-Ccy-Details
Datatype	
Description	Includes Rate-Currency details

Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## CCYCODE

<b>Attribute</b>	<b>Description</b>	
Name	CCYCODE	
Datatype	String	
Description	Specifies The Currency Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## Cftms-Float-Rate-Master-Details

<b>Attribute</b>	<b>Description</b>	
Name	Cftms-Float-Rate-Master-Details	
Datatype		
Description	Includes Rate details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## AMNTSLAB

<b>Attribute</b>	<b>Description</b>	
Name	AMNTSLAB	
Datatype	Number	
Description	Specifies The Amount Slab.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## EFFECTDATE

<b>Attribute</b>	<b>Description</b>	
Name	EFFECTDATE	
Datatype	Date	
Description	Specifies The Effective Date.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## BRWLENDINDCR

<b>Attribute</b>	<b>Description</b>
Name	BRWLENDINDCR



Datatype	String	
Description	Specifies The Borrow Lend Indicator 1 : Borrow : B 2 : Lend : L 3 : MID : M	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	B,L,M

[TOP](#)

## Cftms-Float-Rate-Detail-Description

<b>Attribute</b>	<b>Description</b>	
Name	Cftms-Float-Rate-Detail-Description	
Datatype		
Description	Specifies The Tenor and Interest Rate Details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## TENORTO

<b>Attribute</b>	<b>Description</b>	
Name	TENORTO	
Datatype	Number	
Description	Specifies The Tenor.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## INTRATE

<b>Attribute</b>	<b>Description</b>	
Name	INTRATE	
Datatype	Number	
Description	Specifies The Interest Rate.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**FIELD\_NAME**

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

**DATATYPE**

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

**FIELD\_VALUE**

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

## VAL\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2
	minLength	0

[TOP](#)

## 2.21.2.CF-ModifyFLTRTDefn-Req-IO-MSG.xsd

### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

### *FCUBS\_BODY*

*Cftms-Rate-Code-Details-IO*

*RATECODE*

*RATEDESC*

*BRANCHCODE*

*MODNO*

*Cftms-Rate-Ccy-Details*

*CCYCODE*

*Cftms-Float-Rate-Master-Details*

*AMNTSLAB*

*EFFECTDATE*

*BRWLENDINDCR*

*Cftms-Float-Rate-Detail-Description*

*TENORTO*

*INTRATE*

*UDFDETAILS*

*FUNCTIONID*

*FIELD\_NAME*

*DATATYPE*

*FIELD\_VALUE*

[VAL\\_TYPE](#)

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

**SOURCE**

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

**UBSCOMP**

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

**MSGID**

Attribute	Description						
Name	MSGID						
Datatype	String						
Description							
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	nillable	true
	Attribute	Description					
	minOccurs	0					
nillable	true						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*		
	Restrictions	Description					
pattern	[a-zA-Z_0-9]*						

[TOP](#)

**CORRELID**

Attribute	Description						
Name	CORRELID						
Datatype	String						
Description							
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	nillable	true
	Attribute	Description					
	minOccurs	0					
nillable	true						

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description
-----------	-------------

Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

[TOP](#)

## Cftms-Rate-Code-Details-IO

Attribute	Description
-----------	-------------

Name	Cftms-Rate-Code-Details-IO
Datatype	
Description	Includes CF-Floating rate modification-IO details

[TOP](#)

## RATECODE

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description	Specifies The Rate Code.	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

## RATEDESC

Attribute	Description	
Name	RATEDESC	
Datatype	String	
Description	Specifies The Rate Description.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

## BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description	Specifies The Branch Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Specifies The Modification Number.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

**Cftms-Rate-Ccy-Details**

Attribute	Description	
Name	Cftms-Rate-Ccy-Details	
Datatype		
Description	Includes Rate-Currency details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**CCYCODE**

Attribute	Description	
Name	CCYCODE	
Datatype	String	
Description	Specifies The Currency Code.	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

**Cftms-Float-Rate-Master-Details**

Attribute	Description	
Name	Cftms-Float-Rate-Master-Details	
Datatype		
Description	Includes Rate details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**AMNTSLAB**

Attribute	Description	
Name	AMNTSLAB	
Datatype	Number	
Description	Specifies The Amount Slab.	
Attributes	Attribute	Description
	minOccurs	1

**EFFECTDATE**

Attribute	Description	
Name	EFFECTDATE	
Datatype	Date	
Description	Specifies The Effective Date.	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## BRWLENDINDCR

<b>Attribute</b>	<b>Description</b>	
Name	BRWLENDINDCR	
Datatype	String	
Description	Specifies The Borrow Lend Indicator 1 : Borrow : B 2 : Lend : L 3 : MID : M	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	B,L,M

[TOP](#)

## Cftms-Float-Rate-Detail-Description

<b>Attribute</b>	<b>Description</b>	
Name	Cftms-Float-Rate-Detail-Description	
Datatype		
Description	Specifies The Tenor and Interest Rate Details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## TENORTO

<b>Attribute</b>	<b>Description</b>	
Name	TENORTO	
Datatype	Number	
Description	Specifies The Tenor.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## INTRATE

<b>Attribute</b>	<b>Description</b>	
Name	INTRATE	
Datatype	Number	
Description	Specifies The Interest Rate.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## UDFDETAILS

Attribute	Description						
Name	UDFDETAILS						
Datatype							
Description	Includes User Defined Fields details						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

## FIELD\_NAME

Attribute	Description						
Name	FIELD_NAME						
Datatype	String						
Description	Indicates the User Defined Field Name.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	105	minLength	1
	Restrictions	Description					
	maxLength	105					
minLength	1						

[TOP](#)

## DATATYPE

Attribute	Description				
Name	DATATYPE				
Datatype	String				
Description	Indicates Data Type				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>15</td></tr></tbody></table>	Restrictions	Description	maxLength	15
	Restrictions	Description			
maxLength	15				

[TOP](#)

## FIELD\_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String

Description	Indicates the User Defined Field Value.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

[TOP](#)

## VAL\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2
	minLength	0

[TOP](#)

### 2.21.3.CF-ModifyFLTRTDefn-Res-Full-MSG.xsd

#### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

#### *FCUBS\_BODY*

*Cftms-Rate-Code-Details-Full*

*RATECODE*

*RATEDESC*

*BRANCHCODE*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

*Cftms-Rate-Ccy-Details*

*CCYCODE*

*Cftms-Float-Rate-Master-Details*

*AMNTSLAB*

*EFFECTDATE*

*BRWLENDINDCR*

*Cftms-Float-Rate-Detail-Description*

[TENORTO](#)  
[INTRATE](#)  
[UDFDETAILS](#)  
[FUNCTIONID](#)  
[FIELD\\_NAME](#)  
[DATATYPE](#)  
[FIELD\\_VALUE](#)  
[VAL\\_TYPE](#)  
[FCUBS\\_ERROR\\_RESP](#)  
[ERROR](#)  
[ECODE](#)  
[EDESC](#)  
[FCUBS\\_WARNING\\_RESP](#)  
[WARNING](#)  
[WCODE](#)  
[WDESC](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

**SERVICE**

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**OPERATION**

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description
-----------	-------------

Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

[TOP](#)

## Cftms-Rate-Code-Details-Full

Attribute	Description
Name	Cftms-Rate-Code-Details-Full
Datatype	
Description	Includes CF-Floating rate modification details

[TOP](#)

## RATECODE

Attribute	Description				
Name	RATECODE				
Datatype	String				
Description	Specifies The Rate Code.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
Attribute	Description				
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>10</td></tr></tbody></table>	Restrictions	Description	maxLength	10
Restrictions	Description				
maxLength	10				

[TOP](#)

## RATEDESC

Attribute	Description				
Name	RATEDESC				
Datatype	String				
Description	Specifies The Rate Description.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>105</td></tr></tbody></table>	Restrictions	Description	maxLength	105
Restrictions	Description				
maxLength	105				

[TOP](#)

## BRANCHCODE

Attribute	Description
Name	BRANCHCODE

Datatype	String	
Description	Specifies The Branch Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	The User id who has booked the contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has booked the contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Specifies The Checker Identification.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has authorized the booked contract	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Specifies The Modification Number.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Specifies The Authorization Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	Specifies The Record Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorized.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

**Cftms-Rate-Ccy-Details**

Attribute	Description	
Name	Cftms-Rate-Ccy-Details	
Datatype		
Description	Includes Rate-Currency details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**CCYCODE**

Attribute	Description	
Name	CCYCODE	
Datatype	String	
Description	Specifies The Currency Code.	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

**Cftms-Float-Rate-Master-Details**

Attribute	Description	
Name	Cftms-Float-Rate-Master-Details	
Datatype		
Description	Includes Rate details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**AMNTSLAB**

Attribute	Description	
Name	AMNTSLAB	
Datatype	Number	
Description	Specifies The Amount Slab.	
Attributes	Attribute	Description
	minOccurs	1

**EFFECTDATE**

Attribute	Description	
Name	EFFECTDATE	
Datatype	Date	
Description	Specifies The Effective Date.	



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## BRWLENDINDCR

<b>Attribute</b>	<b>Description</b>	
Name	BRWLENDINDCR	
Datatype	String	
Description	Specifies The Borrow Lend Indicator 1 : Borrow : B 2 : Lend : L 3 : MID : M	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	B,L,M

[TOP](#)

## Cftms-Float-Rate-Detail-Description

<b>Attribute</b>	<b>Description</b>	
Name	Cftms-Float-Rate-Detail-Description	
Datatype		
Description	Specifies The Tenor and Interest Rate Details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## TENORTO

<b>Attribute</b>	<b>Description</b>	
Name	TENORTO	
Datatype	Number	
Description	Specifies The Tenor.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## INTRATE

<b>Attribute</b>	<b>Description</b>	
Name	INTRATE	
Datatype	Number	
Description	Specifies The Interest Rate.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## UDFDETAILS

Attribute	Description						
Name	UDFDETAILS						
Datatype							
Description	Includes User Defined Fields details						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

## FIELD\_NAME

Attribute	Description						
Name	FIELD_NAME						
Datatype	String						
Description	Indicates the User Defined Field Name.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	105	minLength	1
	Restrictions	Description					
	maxLength	105					
minLength	1						

[TOP](#)

## DATATYPE

Attribute	Description				
Name	DATATYPE				
Datatype	String				
Description	Indicates Data Type				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>15</td></tr></tbody></table>	Restrictions	Description	maxLength	15
	Restrictions	Description			
maxLength	15				

[TOP](#)

## FIELD\_VALUE

Attribute	Description
Name	FIELD_VALUE
Datatype	String

Description	Indicates the User Defined Field Value.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

[TOP](#)

## VAL\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2
	minLength	0

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.21.4.CF-ModifyFLTRTDefn-Res-PK-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Cftms-Rate-Code-Details-PK*

*RATECODE*

*BRANCHCODE*

*Cftms-Rate-Code-Details-IO*

*RATECODE*

*RATEDESC*

*BRANCHCODE*

*MODNO*

*Cftms-Rate-Ccy-Details*

*CCYCODE*

*Cftms-Float-Rate-Master-Details*

*AMNTSLAB*

*EFFECTDATE*

*BRWLENDINDCR*

*Cftms-Float-Rate-Detail-Description*

*TENORTO*

*INTRATE*

*TENORTO*

INTRATE  
AMNTSLAB  
EFFECTDATE  
BRWLENDINDCR  
*Cftms-Float-Rate-Detail-Description*

TENORTO  
INTRATE  
TENORTO  
INTRATE

UDFDETAILS  
FUNCTIONID  
FIELD\_NAME  
DATATYPE  
FIELD\_VALUE  
VAL\_TYPE

*Cftms-Rate-Code-Details-Full*

RATECODE  
RATEDESC  
BRANCHCODE  
MAKERID  
MAKERDTSTAMP  
CHECKERID  
CHECKERDTSTAMP  
MODNO  
AUTHSTAT  
RECSTAT  
ONCEAUTH

*Cftms-Rate-Ccy-Details*

CCYCODE

*Cftms-Float-Rate-Master-Details*

AMNTSLAB  
EFFECTDATE  
BRWLENDINDCR  
*Cftms-Float-Rate-Detail-Description*

TENORTO  
INTRATE  
TENORTO  
INTRATE

AMNTSLAB  
EFFECTDATE  
BRWLENDINDCR  
*Cftms-Float-Rate-Detail-Description*

TENORTO  
INTRATE

[TENORTO](#)  
[INTRATE](#)  
[UDFDETAILS](#)  
[FUNCTIONID](#)  
[FIELD\\_NAME](#)  
[DATATYPE](#)  
[FIELD\\_VALUE](#)  
[VAL\\_TYPE](#)  
[FCUBS\\_ERROR\\_RESP](#)  
[ERROR](#)  
[ECODE](#)  
[EDESC](#)  
[FCUBS\\_WARNING\\_RESP](#)  
[WARNING](#)  
[WCODE](#)  
[WDESC](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true



**SERVICE**

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**OPERATION**

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description
-----------	-------------

Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Cftms-Rate-Code-Details-PK

Attribute	Description
Name	Cftms-Rate-Code-Details-PK
Datatype	
Description	Includes CF-Floating rate modification-Primary key details

[TOP](#)

## RATECODE

Attribute	Description				
Name	RATECODE				
Datatype	String				
Description	Specifies The Rate Code.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>16</td></tr></tbody></table>	Restrictions	Description	maxLength	16
	Restrictions	Description			
maxLength	16				

[TOP](#)

## BRANCHCODE

Attribute	Description				
Name	BRANCHCODE				
Datatype	String				
Description	Specifies The Branch Code.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## Cftms-Rate-Code-Details-IO

Attribute	Description
Name	Cftms-Rate-Code-Details-IO
Datatype	
Description	Includes CF-Floating rate modification-IO details

[TOP](#)

## RATECODE

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description	Specifies The Rate Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## RATEDESC

Attribute	Description	
Name	RATEDESC	
Datatype	String	
Description	Specifies The Rate Description.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## BRANCHCODE

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description	Specifies The Branch Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

[TOP](#)

## MODNO

Attribute	Description
Name	MODNO

Datatype	Number	
Description	Specifies The Modification Number.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	totalDigits	22

[TOP](#)

## Cftms-Rate-Ccy-Details

<b>Attribute</b>	<b>Description</b>	
Name	Cftms-Rate-Ccy-Details	
Datatype		
Description	Includes Rate-Currency details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## CCYCODE

<b>Attribute</b>	<b>Description</b>	
Name	CCYCODE	
Datatype	String	
Description	Specifies The Currency Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## Cftms-Float-Rate-Master-Details

<b>Attribute</b>	<b>Description</b>	
Name	Cftms-Float-Rate-Master-Details	
Datatype		
Description	Includes Rate details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## AMNTSLAB

<b>Attribute</b>	<b>Description</b>	
Name	AMNTSLAB	
Datatype	Number	
Description	Specifies The Amount Slab.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

**EFFECTDATE**

Attribute	Description	
Name	EFFECTDATE	
Datatype	Date	
Description	Specifies The Effective Date.	
Attributes	Attribute	Description
	minOccurs	1

**BRWLENDINDCR**

Attribute	Description	
Name	BRWLENDINDCR	
Datatype	String	
Description	Specifies The Borrow Lend Indicator 1 : Borrow : B 2 : Lend : L 3 : MID : M	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	B,L,M

**Cftms-Float-Rate-Detail-Description**

Attribute	Description	
Name	Cftms-Float-Rate-Detail-Description	
Datatype		
Description	Specifies The Tenor and Interest Rate Details.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**TENORTO**

Attribute	Description	
Name	TENORTO	
Datatype	Number	
Description	Specifies The Tenor.	
Attributes	Attribute	Description
	minOccurs	0

**INTRATE**

Attribute	Description
-----------	-------------

Name	INTRATE	
Datatype	Number	
Description	Specifies The Interest Rate.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TENORTO

<b>Attribute</b>	<b>Description</b>	
Name	TENORTO	
Datatype	Number	
Description	Specifies The Tenor.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## INTRATE

<b>Attribute</b>	<b>Description</b>	
Name	INTRATE	
Datatype	Number	
Description	Specifies The Interest Rate.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AMNTSLAB

<b>Attribute</b>	<b>Description</b>	
Name	AMNTSLAB	
Datatype	Number	
Description	Specifies The Amount Slab.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## EFFECTDATE

<b>Attribute</b>	<b>Description</b>	
Name	EFFECTDATE	
Datatype	Date	
Description	Specifies The Effective Date.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## BRWLENDINDCR

<b>Attribute</b>	<b>Description</b>	
Name	BRWLENDINDCR	
Datatype	String	



Description	Specifies The Borrow Lend Indicator 1 : Borrow : B 2 : Lend : L 3 : MID : M	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	B,L,M

[TOP](#)

## Cftms-Float-Rate-Detail-Description

<b>Attribute</b>	<b>Description</b>	
Name	Cftms-Float-Rate-Detail-Description	
Datatype		
Description	Specifies The Tenor and Interest Rate Details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## TENORTO

<b>Attribute</b>	<b>Description</b>	
Name	TENORTO	
Datatype	Number	
Description	Specifies The Tenor.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## INTRATE

<b>Attribute</b>	<b>Description</b>	
Name	INTRATE	
Datatype	Number	
Description	Specifies The Interest Rate.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TENORTO

<b>Attribute</b>	<b>Description</b>	
Name	TENORTO	
Datatype	Number	
Description	Specifies The Tenor.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## INTRATE

Attribute	Description				
Name	INTRATE				
Datatype	Number				
Description	Specifies The Interest Rate.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## UDFDETAILS

Attribute	Description						
Name	UDFDETAILS						
Datatype							
Description	Includes User Defined Fields details						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

## FIELD\_NAME

Attribute	Description						
Name	FIELD_NAME						
Datatype	String						
Description	Indicates the User Defined Field Name.						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>105</td></tr><tr><td>minLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	105	minLength	1
	Restrictions	Description					
	maxLength	105					
minLength	1						

[TOP](#)

## DATATYPE

Attribute	Description
Name	DATATYPE
Datatype	String
Description	Indicates Data Type

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

[TOP](#)

## FIELD\_VALUE

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

[TOP](#)

## VAL\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2
	minLength	0

[TOP](#)

## Cftms-Rate-Code-Details-Full

<b>Attribute</b>	<b>Description</b>
Name	Cftms-Rate-Code-Details-Full
Datatype	
Description	Includes CF-Floating rate modification details

[TOP](#)

## RATECODE

<b>Attribute</b>	<b>Description</b>	
Name	RATECODE	
Datatype	String	
Description	Specifies The Rate Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	16

**RATEDESC**

Attribute	Description	
Name	RATEDESC	
Datatype	String	
Description	Specifies The Rate Description.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

**BRANCHCODE**

Attribute	Description	
Name	BRANCHCODE	
Datatype	String	
Description	Specifies The Branch Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	16

**MAKERID**

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	The User id who has booked the contract	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**MAKERDTSTAMP**

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has booked the contract	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

**CHECKERID**

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Specifies The Checker Identification.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has authorized the booked contract	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Specifies The Modification Number.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	totalDigits	22

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Specifies The Authorization Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## RECSTAT

Attribute	Description
Name	RECSTAT

Datatype	String	
Description	Specifies The Record Status.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorized.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Cftms-Rate-Ccy-Details

<b>Attribute</b>	<b>Description</b>	
Name	Cftms-Rate-Ccy-Details	
Datatype		
Description	Includes Rate-Currency details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## CCYCODE

<b>Attribute</b>	<b>Description</b>	
Name	CCYCODE	
Datatype	String	
Description	Specifies The Currency Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## Cftms-Float-Rate-Master-Details

<b>Attribute</b>	<b>Description</b>	
Name	Cftms-Float-Rate-Master-Details	
Datatype		
Description	Includes Rate details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

**AMNTSLAB**

Attribute	Description	
Name	AMNTSLAB	
Datatype	Number	
Description	Specifies The Amount Slab.	
Attributes	Attribute	Description
	minOccurs	1

**EFFECTDATE**

Attribute	Description	
Name	EFFECTDATE	
Datatype	Date	
Description	Specifies The Effective Date.	
Attributes	Attribute	Description
	minOccurs	1

**BRWLENDINDCR**

Attribute	Description	
Name	BRWLENDINDCR	
Datatype	String	
Description	Specifies The Borrow Lend Indicator 1 : Borrow : B 2 : Lend : L 3 : MID : M	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	B,L,M

**Cftms-Float-Rate-Detail-Description**

Attribute	Description	
Name	Cftms-Float-Rate-Detail-Description	
Datatype		
Description	Specifies The Tenor and Interest Rate Details.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**TENORTO**

Attribute	Description
-----------	-------------

Name	TENORTO	
Datatype	Number	
Description	Specifies The Tenor.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## INTRATE

<b>Attribute</b>	<b>Description</b>	
Name	INTRATE	
Datatype	Number	
Description	Specifies The Interest Rate.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TENORTO

<b>Attribute</b>	<b>Description</b>	
Name	TENORTO	
Datatype	Number	
Description	Specifies The Tenor.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## INTRATE

<b>Attribute</b>	<b>Description</b>	
Name	INTRATE	
Datatype	Number	
Description	Specifies The Interest Rate.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AMNTSLAB

<b>Attribute</b>	<b>Description</b>	
Name	AMNTSLAB	
Datatype	Number	
Description	Specifies The Amount Slab.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## EFFECTDATE

<b>Attribute</b>	<b>Description</b>	
Name	EFFECTDATE	
Datatype	Date	
Description	Specifies The Effective Date.	



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## BRWLENDINDCR

<b>Attribute</b>	<b>Description</b>	
Name	BRWLENDINDCR	
Datatype	String	
Description	Specifies The Borrow Lend Indicator 1 : Borrow : B 2 : Lend : L 3 : MID : M	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	B,L,M

[TOP](#)

## Cftms-Float-Rate-Detail-Description

<b>Attribute</b>	<b>Description</b>	
Name	Cftms-Float-Rate-Detail-Description	
Datatype		
Description	Specifies The Tenor and Interest Rate Details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## TENORTO

<b>Attribute</b>	<b>Description</b>	
Name	TENORTO	
Datatype	Number	
Description	Specifies The Tenor.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## INTRATE

<b>Attribute</b>	<b>Description</b>	
Name	INTRATE	
Datatype	Number	
Description	Specifies The Interest Rate.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TENORTO

Attribute	Description				
Name	TENORTO				
Datatype	Number				
Description	Specifies The Tenor.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## INTRATE

Attribute	Description				
Name	INTRATE				
Datatype	Number				
Description	Specifies The Interest Rate.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## UDFDETAILS

Attribute	Description						
Name	UDFDETAILS						
Datatype							
Description	Includes User Defined Fields details						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

## FIELD\_NAME

Attribute	Description
Name	FIELD_NAME
Datatype	String
Description	Indicates the User Defined Field Name.

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

[TOP](#)

## DATATYPE

<b>Attribute</b>	<b>Description</b>	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

[TOP](#)

## FIELD\_VALUE

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

[TOP](#)

## VAL\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2
	minLength	0

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**ERROR**

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**ECODE**

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)**EDESC**

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)**FCUBS\_WARNING\_RESP**

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**WARNING**

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)**WCODE**

Attribute	Description
Name	WCODE

Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.22.ModifyFloatRateMaint

ModifyFloatRateMaint

### 2.22.1.CF-ModifyFloatRateMaint-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Rate-Code-Full*

*RATE\_CODE*

*RATEDESC*

*BRANCH\_CODE*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*Rate-Ccy*

*RATE\_CODE*

*CCY\_CODE*

*BRANCH\_CODE*

*Fload-Rate*

*RATE\_CODE*  
*CCY\_CODE*  
*AMOUNT\_SLAB1*  
*EFFECTIVE\_DATE*  
*BRANCH\_CODE*  
*BORROW\_LEND\_IND*

*Ftrate-Detail*

*RATE\_CODE*  
*CCY\_CODE*  
*AMOUNT\_SLAB*  
*EFFECTIVE\_DATE*  
*BRANCH\_CODE*  
*BORROW\_LEND\_IND*  
*TENOR\_TO1*  
*INTEREST\_RATE*  
*RATECODEC*  
*CCYCODEC*  
*AMOUNTSLABC*  
*EFFECTIVEDATEC*  
*BRANCHCODEC*  
*BORROWLENDINDC*  
*TENORTOC*  
*TDMAXRATE*  
*TDPREDIFF*

*UDFDETAILS*

*FLDNAM*

*FLDVAL*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

**SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

**UBSCOMP**

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		



Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

[TOP](#)

## Rate-Code-Full

Attribute	Description
Name	Rate-Code-Full
Datatype	
Description	

[TOP](#)

## RATE\_CODE

Attribute	Description	
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## RATEDESC

Attribute	Description
-----------	-------------

Name	RATEDESC	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

**Rate-Ccy**

Attribute	Description	
Name	Rate-Ccy	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**RATE\_CODE**

Attribute	Description	
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

**CCY\_CODE**

Attribute	Description	
Name	CCY_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

**BRANCH\_CODE**

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

**Fload-Rate**

Attribute	Description
-----------	-------------

Name	Fload-Rate	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## RATE\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## CCY\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	CCY_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## AMOUNT\_SLAB1

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNT_SLAB1	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## EFFECTIVE\_DATE

<b>Attribute</b>	<b>Description</b>	
Name	EFFECTIVE_DATE	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1



**BRANCH\_CODE**

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

**BORROW\_LEND\_IND**

Attribute	Description	
Name	BORROW_LEND_IND	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	B,L,M

**Filtrate-Detail**

Attribute	Description	
Name	Filtrate-Detail	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**RATE\_CODE**

Attribute	Description	
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

**CCY\_CODE**

Attribute	Description
-----------	-------------

Name	CCY_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## AMOUNT\_SLAB

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNT_SLAB	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## EFFECTIVE\_DATE

<b>Attribute</b>	<b>Description</b>	
Name	EFFECTIVE_DATE	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## BORROW\_LEND\_IND

<b>Attribute</b>	<b>Description</b>	
Name	BORROW_LEND_IND	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	B,L,M

**TENOR\_TO1**

Attribute		Description
Name	TENOR_TO1	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

**INTEREST\_RATE**

Attribute		Description
Name	INTEREST_RATE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

**RATECODEC**

Attribute		Description
Name	RATECODEC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

**CCYCODEC**

Attribute		Description
Name	CCYCODEC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

**AMOUNTSLABC**

Attribute		Description
Name	AMOUNTSLABC	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## EFFECTIVEDATEC

Attribute	Description	
Name	EFFECTIVEDATEC	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## BRANCHCODEC

Attribute	Description	
Name	BRANCHCODEC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## BORROWLENDINDC

Attribute	Description	
Name	BORROWLENDINDC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## TENORTOC

Attribute	Description	
Name	TENORTOC	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## TDMAXRATE

Attribute	Description
Name	TDMAXRATE

Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TDPREDIFF

<b>Attribute</b>	<b>Description</b>	
Name	TDPREDIFF	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

[TOP](#)

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

[TOP](#)

## 2.22.2.CF-ModifyFloatRateMaint-Req-IO-MSG.xsd

### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

### *FCUBS\_BODY*

*Rate-Code-IO*

*RATE\_CODE*

*BRANCH\_CODE*

*MAKER*

*MAKERSTAMP*

*Rate-Ccy*

*RATE\_CODE*

*CCY\_CODE*

*BRANCH\_CODE*

*Fload-Rate*

*RATE\_CODE*

*CCY\_CODE*

*AMOUNT\_SLAB1*

*EFFECTIVE\_DATE*

*BRANCH\_CODE*

*BORROW\_LEND\_IND*

*Fltrate-Detail*

*RATE\_CODE*

*CCY\_CODE*

AMOUNT\_SLAB  
 EFFECTIVE\_DATE  
 BRANCH\_CODE  
 BORROW\_LEND\_IND  
 TENOR\_TO1  
 INTEREST\_RATE  
 RATECODEC  
 CCYCODEC  
 AMOUNTSLABC  
 EFFECTIVEDATEC  
 BRANCHCODEC  
 BORROWLENDINDC  
 TENORTOC  
 TDMAXRATE  
 TDPREDIFF

UDFDETAILS

FLDNAM

FLDVAL

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

**SOURCE**

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

**UBSCOMP**

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

**MSGID**

Attribute	Description
-----------	-------------

Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTIRIPID**

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

## MSGSTAT

Attribute	Description				
Name	MSGSTAT				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>SUCCESS,WARNING,FAILURE</td></tr></tbody></table>	Restrictions	Description	enumeration	SUCCESS,WARNING,FAILURE
	Restrictions	Description			
enumeration	SUCCESS,WARNING,FAILURE				

[TOP](#)

## PASSWORD

Attribute	Description						
Name	PASSWORD						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>128</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9=+]*</td></tr></tbody></table>	Restrictions	Description	maxLength	128	pattern	[a-zA-Z_0-9=+]*
	Restrictions	Description					
	maxLength	128					
pattern	[a-zA-Z_0-9=+]*						

[TOP](#)

## ADDL

Attribute	Description				
Name	ADDL				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## PARAM

Attribute	Description						
Name	PARAM						
Datatype							
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

[TOP](#)

## Rate-Code-IO

Attribute	Description
Name	Rate-Code-IO
Datatype	
Description	

[TOP](#)

## RATE\_CODE

Attribute	Description	
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

## BRANCH\_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## MAKER

Attribute	Description
-----------	-------------

Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## Rate-Ccy

<b>Attribute</b>	<b>Description</b>	
Name	Rate-Ccy	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	1

[TOP](#)

## RATE\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## CCY\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	CCY_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## Fload-Rate

<b>Attribute</b>	<b>Description</b>	
Name	Fload-Rate	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	1

[TOP](#)

## RATE\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## CCY\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	CCY_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## AMOUNT\_SLAB1

Attribute	Description				
Name	AMOUNT_SLAB1				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				

[TOP](#)

## EFFECTIVE\_DATE

Attribute	Description				
Name	EFFECTIVE_DATE				
Datatype	Date				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				

[TOP](#)

## BRANCH\_CODE

Attribute	Description				
Name	BRANCH_CODE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

[TOP](#)

## BORROW\_LEND\_IND

Attribute	Description				
Name	BORROW_LEND_IND				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>B,L,M</td></tr></tbody></table>	Restrictions	Description	enumeration	B,L,M
	Restrictions	Description			
enumeration	B,L,M				

[TOP](#)

## Filtrate-Detail

Attribute	Description
Name	Filtrate-Detail
Datatype	
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	1

[TOP](#)

## RATE\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## CCY\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	CCY_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## AMOUNT\_SLAB

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNT_SLAB	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## EFFECTIVE\_DATE

<b>Attribute</b>	<b>Description</b>	
Name	EFFECTIVE_DATE	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>
------------------	--------------------



Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## BORROW\_LEND\_IND

<b>Attribute</b>	<b>Description</b>	
Name	BORROW_LEND_IND	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	B,L,M

[TOP](#)

## TENOR\_TO1

<b>Attribute</b>	<b>Description</b>	
Name	TENOR_TO1	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## INTEREST\_RATE

<b>Attribute</b>	<b>Description</b>	
Name	INTEREST_RATE	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## RATECODEC

<b>Attribute</b>	<b>Description</b>	
Name	RATECODEC	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

**CCYCODEC**

Attribute		Description
Name	CCYCODEC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

**AMOUNTSLABC**

Attribute		Description
Name	AMOUNTSLABC	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

**EFFECTIVEDATEC**

Attribute		Description
Name	EFFECTIVEDATEC	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

**BRANCHCODEC**

Attribute		Description
Name	BRANCHCODEC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

**BORROWLENDINDC**

Attribute		Description
Name	BORROWLENDINDC	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## TENORTOC

<b>Attribute</b>	<b>Description</b>	
Name	TENORTOC	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TDMAXRATE

<b>Attribute</b>	<b>Description</b>	
Name	TDMAXRATE	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TDPREDIFF

<b>Attribute</b>	<b>Description</b>	
Name	TDPREDIFF	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	String	

Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

[TOP](#)

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

[TOP](#)

### 2.22.3.CF-ModifyFloatRateMaint-Res-Full-MSG.xsd

#### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

#### *FCUBS\_BODY*

*Rate-Code-Full*

*RATE\_CODE*

*RATEDESC*

*BRANCH\_CODE*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*Rate-Ccy*

*RATE\_CODE*

*CCY\_CODE*

*BRANCH\_CODE*

*Fload-Rate*

*RATE\_CODE*

*CCY\_CODE*

*AMOUNT\_SLAB1*

EFFECTIVE\_DATE  
 BRANCH\_CODE  
 BORROW\_LEND\_IND  
 Fltrate-Detail  
 RATE\_CODE  
 CCY\_CODE  
 AMOUNT\_SLAB  
 EFFECTIVE\_DATE  
 BRANCH\_CODE  
 BORROW\_LEND\_IND  
 TENOR\_TO1  
 INTEREST\_RATE  
 RATECODEC  
 CCYCODEC  
 AMOUNTSLABC  
 EFFECTIVEDATEC  
 BRANCHCODEC  
 BORROWLENDINDC  
 TENORTOC  
 TDMAXRATE  
 TDPREDIFF

UDFDETAILS

FLDNAM

FLDVAL

FCUBS\_ERROR\_RESP

ERROR

ECODE

EDESC

FCUBS\_WARNING\_RESP

WARNING

WCODE

WDESC

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

**SOURCE**

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

<b>Attribute</b>	<b>Description</b>	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description							
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
	Restrictions	Description					
	length	3					
pattern	[a-zA-Z_0-9]{3}						

[TOP](#)

## MODULEID

Attribute	Description						
Name	MODULEID						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nullable	true
	Attribute	Description					
	minOccurs	0					
nullable	true						

[TOP](#)

## SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	nullable	true
	Attribute	Description			
nullable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	nullable	true
	Attribute	Description			
nullable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about Full Response	

[TOP](#)

## Rate-Code-Full

Attribute	Description	
Name	Rate-Code-Full	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## RATE\_CODE

Attribute	Description	
Name	RATE_CODE	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## RATEDESC

<b>Attribute</b>	<b>Description</b>	
Name	RATEDESC	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## Rate-Ccy

Attribute	Description	
Name	Rate-Ccy	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## RATE\_CODE

Attribute	Description	
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

## CCY\_CODE

Attribute	Description	
Name	CCY_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## BRANCH\_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## Fload-Rate

<b>Attribute</b>	<b>Description</b>	
Name	Fload-Rate	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## RATE\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## CCY\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	CCY_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## AMOUNT\_SLAB1

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNT_SLAB1	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

**EFFECTIVE\_DATE**

Attribute	Description	
Name	EFFECTIVE_DATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	1

**BRANCH\_CODE**

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

**BORROW\_LEND\_IND**

Attribute	Description	
Name	BORROW_LEND_IND	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	B,L,M

**Filtrate-Detail**

Attribute	Description	
Name	Filtrate-Detail	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**RATE\_CODE**

Attribute	Description	
Name	RATE_CODE	
Datatype	String	



Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## CCY\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	CCY_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## AMOUNT\_SLAB

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNT_SLAB	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## EFFECTIVE\_DATE

<b>Attribute</b>	<b>Description</b>	
Name	EFFECTIVE_DATE	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## BORROW\_LEND\_IND

Attribute	Description	
Name	BORROW_LEND_IND	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	B,L,M

[TOP](#)

## TENOR\_TO1

Attribute	Description	
Name	TENOR_TO1	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)

## INTEREST\_RATE

Attribute	Description	
Name	INTEREST_RATE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## RATECODEC

Attribute	Description	
Name	RATECODEC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

## CCYCODEC

Attribute	Description	
Name	CCYCODEC	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## AMOUNTSLABC

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNTSLABC	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## EFFECTIVEDATEC

<b>Attribute</b>	<b>Description</b>	
Name	EFFECTIVEDATEC	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## BRANCHCODEC

<b>Attribute</b>	<b>Description</b>	
Name	BRANCHCODEC	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## BORROWLENDINDC

<b>Attribute</b>	<b>Description</b>	
Name	BORROWLENDINDC	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## TENORTOC

Attribute	Description	
Name	TENORTOC	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## TDMAXRATE

Attribute	Description	
Name	TDMAXRATE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## TDPREDIFF

Attribute	Description	
Name	TDPREDIFF	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

[TOP](#)

## FLDVAL

Attribute	Description						
Name	FLDVAL						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></tbody></table>	Restrictions	Description	maxLength	255	minLength	0
	Restrictions	Description					
	maxLength	255					
minLength	0						

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description				
Name	FCUBS_ERROR_RESP				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## ERROR

Attribute	Description				
Name	ERROR				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
	Attribute	Description			
maxOccurs	unbounded				

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description
-----------	-------------

Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.22.4.CF-ModifyFloatRateMaint-Res-PK-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Rate-Code-PK*

*RATE\_CODE*

*BRANCH\_CODE*

*Rate-Code-IO*

*RATE\_CODE*

*BRANCH\_CODE*

*MAKER*

*MAKERSTAMP*

*Rate-Ccy*

*RATE\_CODE*

*CCY\_CODE*

*BRANCH\_CODE*

*Fload-Rate*

*RATE\_CODE*

*CCY\_CODE*

*AMOUNT\_SLAB1*

*EFFECTIVE\_DATE*

*BRANCH\_CODE*

BORROW\_LEND\_IND

*Fltrate-Detail*

RATE\_CODE

CCY\_CODE

AMOUNT\_SLAB

EFFECTIVE\_DATE

BRANCH\_CODE

BORROW\_LEND\_IND

TENOR\_T01

INTEREST\_RATE

RATECODEC

CCYCODEC

AMOUNTSLABC

EFFECTIVEDATEC

BRANCHCODEC

BORROWLENDINDC

TENORTOC

TDMAXRATE

TDPREDIFF

UDFDETAILS

FLDNAM

FLDVAL

FCUBS\_ERROR\_RESP

ERROR

ECODE

EDESC

FCUBS\_WARNING\_RESP

WARNING

WCODE

WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*



**UBSCOMP**

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description
-----------	-------------

Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MSGSTAT**

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

**PASSWORD**

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

**ADDL**

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

**PARAM**

Attribute	Description
-----------	-------------

Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Rate-Code-PK

Attribute	Description	
Name	Rate-Code-PK	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## RATE\_CODE

Attribute	Description
Name	RATE_CODE

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## Rate-Code-IO

<b>Attribute</b>	<b>Description</b>	
Name	Rate-Code-IO	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## RATE\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## Rate-Ccy

<b>Attribute</b>	<b>Description</b>	
Name	Rate-Ccy	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	1

[TOP](#)

## RATE\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## CCY\_CODE

Attribute	Description				
Name	CCY_CODE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

[TOP](#)

## BRANCH\_CODE

Attribute	Description				
Name	BRANCH_CODE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

[TOP](#)

## Flood-Rate

Attribute	Description						
Name	Flood-Rate						
Datatype							
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	1
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	1						

[TOP](#)

## RATE\_CODE

Attribute	Description				
Name	RATE_CODE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>10</td></tr></tbody></table>	Restrictions	Description	maxLength	10
	Restrictions	Description			
maxLength	10				

[TOP](#)

## CCY\_CODE

Attribute	Description
Name	CCY_CODE



Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## AMOUNT\_SLAB1

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNT_SLAB1	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## EFFECTIVE\_DATE

<b>Attribute</b>	<b>Description</b>	
Name	EFFECTIVE_DATE	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## BORROW\_LEND\_IND

<b>Attribute</b>	<b>Description</b>	
Name	BORROW_LEND_IND	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	B,L,M

**Fltrate-Detail**

Attribute		Description
Name	Fltrate-Detail	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	1

**RATE\_CODE**

Attribute		Description
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

**CCY\_CODE**

Attribute		Description
Name	CCY_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

**AMOUNT\_SLAB**

Attribute		Description
Name	AMOUNT_SLAB	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

**EFFECTIVE\_DATE**

Attribute		Description
Name	EFFECTIVE_DATE	
Datatype	Date	

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## BORROW\_LEND\_IND

<b>Attribute</b>	<b>Description</b>	
Name	BORROW_LEND_IND	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	B,L,M

[TOP](#)

## TENOR\_TO1

<b>Attribute</b>	<b>Description</b>	
Name	TENOR_TO1	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## INTEREST\_RATE

<b>Attribute</b>	<b>Description</b>	
Name	INTEREST_RATE	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## RATECODEC

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	RATECODEC	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## CCYCODEC

<b>Attribute</b>	<b>Description</b>	
Name	CCYCODEC	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## AMOUNTSLABC

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNTSLABC	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## EFFECTIVEDATEC

<b>Attribute</b>	<b>Description</b>	
Name	EFFECTIVEDATEC	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## BRANCHCODEC

<b>Attribute</b>	<b>Description</b>	
Name	BRANCHCODEC	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

**BORROWLENDINDC**

Attribute	Description	
Name	BORROWLENDINDC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**TENORTOC**

Attribute	Description	
Name	TENORTOC	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

**TDMAXRATE**

Attribute	Description	
Name	TDMAXRATE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

**TDPREDIFF**

Attribute	Description	
Name	TDPREDIFF	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

**UDFDETAILS**

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

[TOP](#)

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.23.QueryCFFloatRateMaint

Query of Floating rate Maintenance

### 2.23.1.CF-QueryCFFloatRateMaint-Req-IO-MSG.xsd

#### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

#### *FCUBS\_BODY*

*Cftm-Rate-Master-IO*

*RATECODE*

*TENORCODE*

*CCYCODE*

*EFFECTIVEDATE*

#### **FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

#### **SOURCE**

Attribute	Description
Name	SOURCE
Datatype	String
Description	



Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

<b>Attribute</b>	<b>Description</b>	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description							
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
	Restrictions	Description					
	length	3					
pattern	[a-zA-Z_0-9]{3}						

[TOP](#)

## MODULEID

Attribute	Description						
Name	MODULEID						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nullable	true
	Attribute	Description					
	minOccurs	0					
nullable	true						

[TOP](#)

## SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	nullable	true
	Attribute	Description			
nullable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	nullable	true
	Attribute	Description			
nullable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about IORequest	

[TOP](#)

## Cftm-Rate-Master-IO

Attribute	Description	
Name	Cftm-Rate-Master-IO	
Datatype		
Description	Includes CF Floating rate Maintenance Query-IO details	

[TOP](#)

## RATECODE

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description	Specifies The Rate Code.	
Attributes	Attribute	Description
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## TENORCODE

<b>Attribute</b>	<b>Description</b>	
Name	TENORCODE	
Datatype	String	
Description	Specifies The Tenor Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CCYCODE

<b>Attribute</b>	<b>Description</b>	
Name	CCYCODE	
Datatype	String	
Description	Specifies The Currency Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## EFFECTIVEDATE

<b>Attribute</b>	<b>Description</b>	
Name	EFFECTIVEDATE	
Datatype	Date	
Description	Specifies The Effective Date.	

[TOP](#)

## 2.23.2.CF-QueryCFFloatRateMaint-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Cftm-Rate-Master-IO*

*RATECODE*

*TENORCODE*

*CCYCODE*

*EFFECTIVEDATE*

*Cftm-Rate-Master-Full*

*RATECODE*

*RATECODEDESCRIPTION*

*TENORCODE*

*TENORCODEDESCRIPTION*

*CCYCODE*

*CCYNAME*

*EFFECTIVEDATE*

*RATESOURCE*

*RATESOURCEDESCRIPTION*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

CHECKERDTSTAMP  
 MODNO  
 AUTHSTAT  
 RECSTAT  
 ONCEAUTH  
 Cftm-Rate-Detail  
     RATETYPE  
     RATETYPEDESCRIPTION  
     INTERESTRATE  
 UDFDETAILS  
     FUNCTIONID  
     FIELD\_NAME  
     DATATYPE  
     FIELD\_VALUE  
     VAL\_TYPE  
 FCUBS\_ERROR\_RESP  
     ERROR  
     ECODE  
     EDESC  
 FCUBS\_WARNING\_RESP  
     WARNING  
     WCODE  
     WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description
Name	UBSCOMP
Datatype	String
Description	



Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

[TOP](#)

## DESTINATION

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description
Name	ACTION

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)**NAME**

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)**VALUE**

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)**FCUBS\_BODY**

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

[TOP](#)**CHOICE**

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)**Cftm-Rate-Master-IO**

Attribute	Description
Name	Cftm-Rate-Master-IO
Datatype	
Description	Includes CF Floating rate Maintenance Query-IO details

[TOP](#)**RATECODE**

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description	Specifies The Rate Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

**TENORCODE**

Attribute	Description	
Name	TENORCODE	
Datatype	String	
Description	Specifies The Tenor Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CCYCODE**

Attribute	Description	
Name	CCYCODE	
Datatype	String	
Description	Specifies The Currency Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

**EFFECTIVEDATE**

Attribute	Description	
Name	EFFECTIVEDATE	
Datatype	Date	
Description	Specifies The Effective Date.	

**Cftm-Rate-Master-Full**

Attribute	Description	
Name	Cftm-Rate-Master-Full	
Datatype		
Description	Includes CF Floating rate Maintenance Query details	

**RATECODE**

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description	Specifies The Rate Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

**RATECODEDESCRIPTION**

Attribute		Description
Name	RATECODEDESCRIPTION	
Datatype	String	
Description	Specifies The Rate Code Description.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

**TENORCODE**

Attribute		Description
Name	TENORCODE	
Datatype	String	
Description	Specifies The Tenor Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**TENORCODEDESCRIPTION**

Attribute		Description
Name	TENORCODEDESCRIPTION	
Datatype	String	
Description	Specifies The Tenor Code Description.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

**CCYCODE**

Attribute		Description
Name	CCYCODE	
Datatype	String	
Description	Specifies The Currency Code.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

**CCYNAME**

Attribute	Description	
Name	CCYNAME	
Datatype	String	
Description	Specifies The Currency Code Description.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

## EFFECTIVEDATE

Attribute	Description	
Name	EFFECTIVEDATE	
Datatype	Date	
Description	Specifies The Effective Date.	

[TOP](#)

## RATESOURCE

Attribute	Description	
Name	RATESOURCE	
Datatype	String	
Description	Specifies The Rate Source.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

## RATESOURCEDESCRIPTION

Attribute	Description	
Name	RATESOURCEDESCRIPTION	
Datatype	String	
Description	Specifies The Rate Source Description.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

## MAKERID

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	The User id who has booked the contract	
Attributes	Attribute	Description
	minOccurs	0



Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has booked the contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	The User id who has authorized the booked contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has authorized the booked contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Specifies The Modification Number.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Specifies The Authorization Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Specifies The Record Status.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorized.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## Cftm-Rate-Detail

Attribute	Description	
Name	Cftm-Rate-Detail	
Datatype		
Description	Indicates The Rate Details.	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## RATETYPE

Attribute	Description
Name	RATETYPE
Datatype	String

Description	Specifies The Rate Type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## RATETYPEDESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	RATETYPEDESCRIPTION	
Datatype	String	
Description	Specifies The Rate Type Description.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## INTERESTRATE

<b>Attribute</b>	<b>Description</b>	
Name	INTERESTRATE	
Datatype	Number	
Description	Specifies The Interest Rate.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description	Indicates The UDF Details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

**FIELD\_NAME**

Attribute		Description
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	Restrictions	
	maxLength	105
	minLength	1

**DATATYPE**

Attribute		Description
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	maxLength	15

**FIELD\_VALUE**

Attribute		Description
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	maxLength	255
	minLength	0

**VAL\_TYPE**

Attribute		Description
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	Attribute	
	minOccurs	0
Restrictions	Restrictions	
	maxLength	2
	minLength	0

## FCUBS\_ERROR\_RESP

Attribute	Description						
Name	FCUBS_ERROR_RESP						
Datatype							
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## ERROR

Attribute	Description				
Name	ERROR				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
	Attribute	Description			
maxOccurs	unbounded				

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description						
Name	FCUBS_WARNING_RESP						
Datatype							
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## WARNING

Attribute	Description
Name	WARNING
Datatype	

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.24.QueryCFRateCodeMaint

Query of Rate Code Maintenance

### 2.24.1.CF-QueryCFRateCodeMaint-Req-IO-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Cftm-Rate-Code-Defn-IO*

*RATECODE*

#### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

#### SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**UBSCOMP**

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description
-----------	-------------



Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MSGSTAT**

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

**PASSWORD**

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

**ADDL**

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

**PARAM**

Attribute	Description
-----------	-------------

Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

[TOP](#)

## Cftm-Rate-Code-Defn-IO

Attribute	Description
Name	Cftm-Rate-Code-Defn-IO
Datatype	
Description	Includes CF Rate Code Maintenance Query-IO details

[TOP](#)

## RATECODE

Attribute	Description	
Name	RATECODE	
Datatype	String	
Description	Indicates Rate Code.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## 2.24.2.CF-QueryCFRateCodeMaint-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Cftm-Rate-Code-Defn-IO*

*RATECODE*

*Cftm-Rate-Code-Defn-Full*

*RATECODE*

*RATECODEDESCRIPTION*

*HOLIDAYCCY*

*PROPAGATIONACROSSBRANCHES*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

*Cftm-Tenor-Code-Defn*

*TENORCODE*

*TENORCODEDESCRIPTION*

UDFDETAILS  
 FUNCTIONID  
 FIELD\_NAME  
 DATATYPE  
 FIELD\_VALUE  
 VAL\_TYPE  
 FCUBS\_ERROR\_RESP  
 ERROR  
 ECODE  
 EDESC  
 FCUBS\_WARNING\_RESP  
 WARNING  
 WCODE  
 WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description
Name	MSGID
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

**SERVICE**

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**OPERATION**

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

**DESTINATION**



Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

Attribute	Description	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description
-----------	-------------

Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Cftm-Rate-Code-Defn-IO

Attribute	Description
Name	Cftm-Rate-Code-Defn-IO
Datatype	
Description	Includes CF Rate Code Maintenance Query-IO details

[TOP](#)

## RATECODE

Attribute	Description				
Name	RATECODE				
Datatype	String				
Description	Indicates Rate Code.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>10</td></tr></tbody></table>	Restrictions	Description	maxLength	10
	Restrictions	Description			
maxLength	10				

[TOP](#)

## Cftm-Rate-Code-Defn-Full

Attribute	Description
Name	Cftm-Rate-Code-Defn-Full
Datatype	
Description	Includes CF Rate Code Maintenance Query details

[TOP](#)

## RATECODE

Attribute	Description				
Name	RATECODE				
Datatype	String				
Description	Indicates Rate Code.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>10</td></tr></tbody></table>	Restrictions	Description	maxLength	10
	Restrictions	Description			
maxLength	10				

[TOP](#)

## RATECODEDESCRIPTION

Attribute	Description				
Name	RATECODEDESCRIPTION				
Datatype	String				
Description	Indicates the description of rate code				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>105</td></tr></tbody></table>	Restrictions	Description	maxLength	105
	Restrictions	Description			
maxLength	105				

[TOP](#)

## HOLIDAYCCY

Attribute	Description				
Name	HOLIDAYCCY				
Datatype	String				
Description	Specifies Holiday Currency .				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

[TOP](#)

## PROPAGATIONACROSSBRANCHES

Attribute	Description				
Name	PROPAGATIONACROSSBRANCHES				
Datatype	String				
Description	Propagate Across Branches				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>1</td></tr></tbody></table>	Restrictions	Description	maxLength	1
	Restrictions	Description			
maxLength	1				

[TOP](#)

## MAKERID

Attribute	Description
-----------	-------------

Name	MAKERID	
Datatype	String	
Description	Specifies the User id who has saved the record.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates the date and time when the user has saved the record.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates the User id who has authorized the record.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and stamp when the user has authorized the booked contract	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	It indicates the modification number.	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	It indicates the status of the record,whether open or Closed.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorized.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Cftm-Tenor-Code-Defn

<b>Attribute</b>	<b>Description</b>	
Name	Cftm-Tenor-Code-Defn	
Datatype		
Description	Includes Tenor code details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## TENORCODE

Attribute	Description				
Name	TENORCODE				
Datatype	String				
Description	Indicates the tenor code				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>10</td></tr></tbody></table>	Restrictions	Description	maxLength	10
	Restrictions	Description			
maxLength	10				

[TOP](#)

## TENORCODEDESCRIPTION

Attribute	Description				
Name	TENORCODEDESCRIPTION				
Datatype	String				
Description	Indicates the description of tenor code.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>105</td></tr></tbody></table>	Restrictions	Description	maxLength	105
	Restrictions	Description			
maxLength	105				

[TOP](#)

## UDFDETAILS

Attribute	Description						
Name	UDFDETAILS						
Datatype							
Description	Includes User Defined Fields details						
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## FUNCTIONID

Attribute	Description						
Name	FUNCTIONID						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>8</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	8	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	8					
pattern	[A-Z_0-9]*						

[TOP](#)

## FIELD\_NAME

Attribute	Description
-----------	-------------

Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

[TOP](#)

## DATATYPE

<b>Attribute</b>	<b>Description</b>	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	15

[TOP](#)

## FIELD\_VALUE

<b>Attribute</b>	<b>Description</b>	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

[TOP](#)

## VAL\_TYPE

<b>Attribute</b>	<b>Description</b>	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	2
	minLength	0

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		



Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

<b>Attribute</b>	<b>Description</b>	
Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.25.QueryCFRateTypeDefn

Query of Rate Type Maintenance

### 2.25.1.CF-QueryCFRateTypeDefn-Req-IO-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Cftm-Rate-Type-Defn-IO*

*RATETYPE*

#### FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

#### SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**UBSCOMP**

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description
-----------	-------------

Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MSGSTAT**

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

**PASSWORD**

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

**ADDL**

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

**PARAM**

Attribute	Description
-----------	-------------

Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

[TOP](#)

## Cftm-Rate-Type-Defn-IO

Attribute	Description
Name	Cftm-Rate-Type-Defn-IO
Datatype	
Description	Includes CF Rate Type Maintenance Query-IO details

[TOP](#)

## RATETYPE

Attribute	Description	
Name	RATETYPE	
Datatype	String	
Description	Indicates The Rate Type.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)



## 2.25.2.CF-QueryCFRateTypeDefn-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Cftm-Rate-Type-Defn-IO*

*RATETYPE*

*Cftm-Rate-Type-Defn-Full*

*RATETYPE*

*RATETYPEDESCRIPTION*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

*UDFDETAILS*

*FUNCTIONID*

*FIELD\_NAME*

*DATATYPE*

*FIELD\_VALUE*

[VAL\\_TYPE](#)  
[FCUBS\\_ERROR\\_RESP](#)  
[ERROR](#)  
[ECODE](#)  
[EDESC](#)  
[FCUBS\\_WARNING\\_RESP](#)  
[WARNING](#)  
[WCODE](#)  
[WDESC](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>enumeration</td> <td>FCUBS,FCIS</td> </tr> </tbody> </table>	Restrictions	Description	enumeration	FCUBS,FCIS
	Restrictions	Description			
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description						
Name	MSGID						
Datatype	String						
Description							
Attributes	<table border="1"> <thead> <tr> <th>Attribute</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>minOccurs</td> <td>0</td> </tr> <tr> <td>nillable</td> <td>true</td> </tr> </tbody> </table>	Attribute	Description	minOccurs	0	nillable	true
	Attribute	Description					
	minOccurs	0					
nillable	true						
Restrictions	<table border="1"> <thead> <tr> <th>Restrictions</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>pattern</td> <td>[a-zA-Z_0-9]*</td> </tr> </tbody> </table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*		
	Restrictions	Description					
pattern	[a-zA-Z_0-9]*						

[TOP](#)

## CORRELID

Attribute	Description						
Name	CORRELID						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nullable	true
	Attribute	Description					
	minOccurs	0					
nullable	true						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*		
	Restrictions	Description					
pattern	[a-zA-Z_0-9]*						

[TOP](#)

## USERID

Attribute	Description						
Name	USERID						
Datatype	String						
Description							
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr><tr><td>pattern</td><td>[A-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	maxLength	12	pattern	[A-Z_0-9]*
	Restrictions	Description					
	maxLength	12					
pattern	[A-Z_0-9]*						

[TOP](#)

## BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description							
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
	Restrictions	Description					
	length	3					
pattern	[a-zA-Z_0-9]{3}						

[TOP](#)

## MODULEID

Attribute	Description						
Name	MODULEID						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nullable	true
	Attribute	Description					
	minOccurs	0					
nullable	true						

[TOP](#)

## SERVICE

Attribute	Description
Name	SERVICE
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Cftm-Rate-Type-Defn-IO

Attribute	Description
Name	Cftm-Rate-Type-Defn-IO
Datatype	
Description	Includes CF Rate Type Maintenance Query-IO details

[TOP](#)

## RATETYPE

Attribute	Description				
Name	RATETYPE				
Datatype	String				
Description	Indicates The Rate Type.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
	Restrictions	Description			
maxLength	12				

[TOP](#)

## Cftm-Rate-Type-Defn-Full

Attribute	Description
Name	Cftm-Rate-Type-Defn-Full
Datatype	
Description	Includes CF Rate Type Maintenance Query details

[TOP](#)

## RATETYPE

Attribute	Description				
Name	RATETYPE				
Datatype	String				
Description	Indicates The Rate Type.				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## RATETYPEDESCRIPTION

<b>Attribute</b>	<b>Description</b>	
Name	RATETYPEDESCRIPTION	
Datatype	String	
Description	Indicates The Rate Type Description.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	The User Id who has created\last modified the Rate Type Definition details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates Date and Stamp when the user hascreated\last modified the Rate Type Definition details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	The User Id who has Authorized the creation\modification of Rate Type Definition details.	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12



**CHECKERDTSTAMP**

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates Date and Stamp when the user has Authorized the creation\ modification of Rate Type Definition details.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates Modification Number i.e. the number of times Rate Type Definition detail has been modified.	
Attributes	Attribute	Description
	minOccurs	0

**AUTHSTAT**

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status. A - Authorized U - Unauthorized	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**RECSTAT**

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Indicates the Record Status O - Open C - Close	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**ONCEAUTH**

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates whether Rate Type Definition detail has been Authorized atleast Once.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**UDFDETAILS**

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description	Includes User Defined Fields details	
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**FIELD\_NAME**

Attribute	Description	
Name	FIELD_NAME	
Datatype	String	
Description	Indicates the User Defined Field Name.	
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

**DATATYPE**

Attribute	Description	
Name	DATATYPE	
Datatype	String	
Description	Indicates Data Type	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	15

[TOP](#)

## FIELD\_VALUE

Attribute	Description	
Name	FIELD_VALUE	
Datatype	String	
Description	Indicates the User Defined Field Value.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

[TOP](#)

## VAL\_TYPE

Attribute	Description	
Name	VAL_TYPE	
Datatype	String	
Description	Indicates Value type.	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	2
	minLength	0

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description
-----------	-------------

Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

<b>Attribute</b>	<b>Description</b>	
Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## WCODE

<b>Attribute</b>	<b>Description</b>
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.26.QueryFloatRateMaint

QueryFloatRateMaint

### 2.26.1.CF-QueryFloatRateMaint-Req-IO-MSG.xsd

#### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

#### *FCUBS\_BODY*

*Rate-Code-IO*

*RATE\_CODE*

*BRANCH\_CODE*

#### **FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

#### **SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**UBSCOMP**

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description
-----------	-------------

Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true



Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MSGSTAT**

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

**PASSWORD**

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

**ADDL**

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

**PARAM**

Attribute	Description
-----------	-------------

Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

[TOP](#)

## Rate-Code-IO

Attribute	Description
Name	Rate-Code-IO
Datatype	
Description	

[TOP](#)

## RATE\_CODE

Attribute	Description	
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## BRANCH\_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## 2.26.2.CF-QueryFloatRateMaint-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Rate-Code-IO*

*RATE\_CODE*

*BRANCH\_CODE*

*Rate-Code-Full*

*RATE\_CODE*

*RATEDESC*

*BRANCH\_CODE*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*Rate-Ccy*

*RATE\_CODE*

*CCY\_CODE*

*BRANCH\_CODE*

*Fload-Rate*

*RATE\_CODE*  
*CCY\_CODE*  
*AMOUNT\_SLAB1*  
*EFFECTIVE\_DATE*  
*BRANCH\_CODE*  
*BORROW\_LEND\_IND*

*Fltrate-Detail*

*RATE\_CODE*  
*CCY\_CODE*  
*AMOUNT\_SLAB*  
*EFFECTIVE\_DATE*  
*BRANCH\_CODE*  
*BORROW\_LEND\_IND*  
*TENOR\_T01*  
*INTEREST\_RATE*  
*RATECODEC*  
*CCYCODEC*  
*AMOUNTSLABC*  
*EFFECTIVEDATEC*  
*BRANCHCODEC*  
*BORROWLENDINDC*  
*TENORTOC*  
*TDMAXRATE*  
*TDPREDIFF*

*UDFDETAILS*

*FLDNAM*  
*FLDVAL*

*FCUBS\_ERROR\_RESP*

*ERROR*  
*ECODE*  
*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*  
*WCODE*  
*WDESC*

**FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

**SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)



## SOURCE\_OPERATION

Attribute	Description						
Name	SOURCE_OPERATION						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nullable	true
	Attribute	Description					
	minOccurs	0					
nullable	true						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*		
	Restrictions	Description					
pattern	[a-zA-Z_0-9]*						

[TOP](#)

## SOURCE\_USERID

Attribute	Description						
Name	SOURCE_USERID						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nullable	true
	Attribute	Description					
	minOccurs	0					
nullable	true						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*		
	Restrictions	Description					
pattern	[a-zA-Z_0-9]*						

[TOP](#)

## DESTINATION

Attribute	Description				
Name	DESTINATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
	minOccurs	0			
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## MULTITRIPID

Attribute	Description				
Name	MULTITRIPID				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
	minOccurs	0			
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## FUNCTIONID

Attribute	Description
-----------	-------------

Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Response

[TOP](#)

## CHOICE

<b>Attribute</b>	<b>Description</b>
Name	CHOICE
Datatype	
Description	

[TOP](#)

## Rate-Code-IO

<b>Attribute</b>	<b>Description</b>
Name	Rate-Code-IO
Datatype	
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## RATE\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## Rate-Code-Full

<b>Attribute</b>	<b>Description</b>	
Name	Rate-Code-Full	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## RATE\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## RATEDESC

Attribute	Description	
Name	RATEDESC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	105

[TOP](#)

## BRANCH\_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## MAKER

Attribute	Description	
Name	MAKER	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

[TOP](#)

## MAKERSTAMP

Attribute	Description	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	35

[TOP](#)

## CHECKER

Attribute	Description
Name	CHECKER

Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## Rate-Ccy

<b>Attribute</b>	<b>Description</b>	
Name	Rate-Ccy	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## RATE\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## CCY\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	CCY_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## Fload-Rate

Attribute	Description						
Name	Fload-Rate						
Datatype							
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded	minOccurs	0
	Attribute	Description					
	maxOccurs	unbounded					
minOccurs	0						

[TOP](#)

## RATE\_CODE

Attribute	Description				
Name	RATE_CODE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>10</td></tr></tbody></table>	Restrictions	Description	maxLength	10
	Restrictions	Description			
maxLength	10				

[TOP](#)

## CCY\_CODE

Attribute	Description				
Name	CCY_CODE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

[TOP](#)

## AMOUNT\_SLAB1

Attribute	Description				
Name	AMOUNT_SLAB1				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				

[TOP](#)

## EFFECTIVE\_DATE

Attribute	Description
Name	EFFECTIVE_DATE
Datatype	Date
Description	



Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## BORROW\_LEND\_IND

<b>Attribute</b>	<b>Description</b>	
Name	BORROW_LEND_IND	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	B,L,M

[TOP](#)

## Fltrate-Detail

<b>Attribute</b>	<b>Description</b>	
Name	Fltrate-Detail	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## RATE\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## CCY\_CODE

Attribute	Description				
Name	CCY_CODE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

[TOP](#)

## AMOUNT\_SLAB

Attribute	Description				
Name	AMOUNT_SLAB				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## EFFECTIVE\_DATE

Attribute	Description				
Name	EFFECTIVE_DATE				
Datatype	Date				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				

[TOP](#)

## BRANCH\_CODE

Attribute	Description				
Name	BRANCH_CODE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

[TOP](#)

## BORROW\_LEND\_IND

Attribute	Description
Name	BORROW_LEND_IND
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	B,L,M

[TOP](#)

## TENOR\_TO1

<b>Attribute</b>	<b>Description</b>	
Name	TENOR_TO1	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## INTEREST\_RATE

<b>Attribute</b>	<b>Description</b>	
Name	INTEREST_RATE	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## RATECODEC

<b>Attribute</b>	<b>Description</b>	
Name	RATECODEC	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## CCYCODEC

<b>Attribute</b>	<b>Description</b>	
Name	CCYCODEC	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## AMOUNTSLABC

Attribute	Description	
Name	AMOUNTSLABC	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## EFFECTIVEDATEC

Attribute	Description	
Name	EFFECTIVEDATEC	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## BRANCHCODEC

Attribute	Description	
Name	BRANCHCODEC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## BORROWLENDINDC

Attribute	Description	
Name	BORROWLENDINDC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## TENORTOC

Attribute	Description	
Name	TENORTOC	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

**TDMAXRATE**

Attribute	Description	
Name	TDMAXRATE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

**TDPREDIFF**

Attribute	Description	
Name	TDPREDIFF	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

**UDFDETAILS**

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**FLDNAM**

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

**FLDVAL**

Attribute	Description	
Name	FLDVAL	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	255
	minLength	0

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

Attribute	Description	
Name	EDESC	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description	
Name	WCODE	
Datatype	String	
Description		

[TOP](#)

## WDESC

Attribute	Description	
Name	WDESC	
Datatype	String	
Description		

[TOP](#)

## 2.27.ReopenFloatRateMaint

ReopenFloatRateMaint

### 2.27.1.CF-ReopenFloatRateMaint-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Rate-Code-Full*

*RATE\_CODE*

*RATEDESC*

*BRANCH\_CODE*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*Rate-Ccy*

*RATE\_CODE*

*CCY\_CODE*

*BRANCH\_CODE*

*Fload-Rate*



RATE\_CODE  
 CCY\_CODE  
 AMOUNT\_SLAB1  
 EFFECTIVE\_DATE  
 BRANCH\_CODE  
 BORROW\_LEND\_IND

*Fltrate-Detail*

RATE\_CODE  
 CCY\_CODE  
 AMOUNT\_SLAB  
 EFFECTIVE\_DATE  
 BRANCH\_CODE  
 BORROW\_LEND\_IND  
 TENOR\_TO1  
 INTEREST\_RATE  
 RATECODEC  
 CCYCODEC  
 AMOUNTSLABC  
 EFFECTIVEDATEC  
 BRANCHCODEC  
 BORROWLENDINDC  
 TENORTOC  
 TDMAXRATE  
 TDPREDIFF

UDFDETAILS

FLDNAM  
 FLDVAL

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

**SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

**UBSCOMP**

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		

Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTITRIPID**

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**

Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about Full Request

[TOP](#)

## Rate-Code-Full

<b>Attribute</b>	<b>Description</b>
Name	Rate-Code-Full
Datatype	
Description	

[TOP](#)

## RATE\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## RATEDESC

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	RATEDESC	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1



**Rate-Ccy**

Attribute	Description	
Name	Rate-Ccy	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**RATE\_CODE**

Attribute	Description	
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

**CCY\_CODE**

Attribute	Description	
Name	CCY_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

**BRANCH\_CODE**

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

**Fload-Rate**

Attribute	Description
-----------	-------------

Name	Flood-Rate	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## RATE\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## CCY\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	CCY_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## AMOUNT\_SLAB1

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNT_SLAB1	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## EFFECTIVE\_DATE

<b>Attribute</b>	<b>Description</b>	
Name	EFFECTIVE_DATE	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

**BRANCH\_CODE**

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

**BORROW\_LEND\_IND**

Attribute	Description	
Name	BORROW_LEND_IND	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	B,L,M

**Filtrate-Detail**

Attribute	Description	
Name	Filtrate-Detail	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**RATE\_CODE**

Attribute	Description	
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

**CCY\_CODE**

Attribute	Description
-----------	-------------

Name	CCY_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## AMOUNT\_SLAB

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNT_SLAB	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## EFFECTIVE\_DATE

<b>Attribute</b>	<b>Description</b>	
Name	EFFECTIVE_DATE	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## BORROW\_LEND\_IND

<b>Attribute</b>	<b>Description</b>	
Name	BORROW_LEND_IND	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	B,L,M

[TOP](#)**TENOR\_TO1**

Attribute		Description
Name	TENOR_TO1	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	1

[TOP](#)**INTEREST\_RATE**

Attribute		Description
Name	INTEREST_RATE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)**RATECODEC**

Attribute		Description
Name	RATECODEC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)**CCYCODEC**

Attribute		Description
Name	CCYCODEC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)**AMOUNTSLABC**

Attribute		Description
Name	AMOUNTSLABC	
Datatype	Number	
Description		

Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## EFFECTIVEDATEC

Attribute	Description	
Name	EFFECTIVEDATEC	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## BRANCHCODEC

Attribute	Description	
Name	BRANCHCODEC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## BORROWLENDINDC

Attribute	Description	
Name	BORROWLENDINDC	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## TENORTOC

Attribute	Description	
Name	TENORTOC	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## TDMAXRATE

Attribute	Description	
Name	TDMAXRATE	

Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TDPREDIFF

<b>Attribute</b>	<b>Description</b>	
Name	TDPREDIFF	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## UDFDETAILS

<b>Attribute</b>	<b>Description</b>	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FLDNAM

<b>Attribute</b>	<b>Description</b>	
Name	FLDNAM	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105
	minLength	1

[TOP](#)

## FLDVAL

<b>Attribute</b>	<b>Description</b>	
Name	FLDVAL	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	255
	minLength	0

[TOP](#)

2.27.2.CF-ReopenFloatRateMaint-Req-IO-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*Rate-Code-IO*

*RATE\_CODE*

*BRANCH\_CODE*

*MAKER*

*MAKERSTAMP*

*MODNO*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

**SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*



**UBSCOMP**

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

**BRANCH**

Attribute	Description
-----------	-------------

Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

**ACTION**

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MSGSTAT**

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

**PASSWORD**

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

**ADDL**

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

**PARAM**

Attribute	Description
-----------	-------------

Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IO Request

[TOP](#)

## Rate-Code-IO

Attribute	Description
Name	Rate-Code-IO
Datatype	
Description	

[TOP](#)

## RATE\_CODE

Attribute	Description	
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## BRANCH\_CODE

Attribute	Description				
Name	BRANCH_CODE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>3</td></tr></tbody></table>	Restrictions	Description	maxLength	3
	Restrictions	Description			
maxLength	3				

[TOP](#)

## MAKER

Attribute	Description				
Name	MAKER				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>12</td></tr></tbody></table>	Restrictions	Description	maxLength	12
	Restrictions	Description			
maxLength	12				

[TOP](#)

## MAKERSTAMP

Attribute	Description				
Name	MAKERSTAMP				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>35</td></tr></tbody></table>	Restrictions	Description	maxLength	35
	Restrictions	Description			
maxLength	35				

[TOP](#)

## MODNO

Attribute	Description				
Name	MODNO				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

### 2.27.3.CF-ReopenFloatRateMaint-Res-Full-MSG.xsd

#### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

#### *FCUBS\_BODY*

*Rate-Code-Full*

*RATE\_CODE*

*RATEDESC*

*BRANCH\_CODE*

*MAKER*

*MAKERSTAMP*

*CHECKER*

*CHECKERSTAMP*

*MODNO*

*TXNSTAT*

*AUTHSTAT*

*Rate-Ccy*

*RATE\_CODE*

*CCY\_CODE*

*BRANCH\_CODE*

*Fload-Rate*

*RATE\_CODE*

*CCY\_CODE*

*AMOUNT\_SLAB1*

EFFECTIVE\_DATE  
 BRANCH\_CODE  
 BORROW\_LEND\_IND  
 Fltrate-Detail  
 RATE\_CODE  
 CCY\_CODE  
 AMOUNT\_SLAB  
 EFFECTIVE\_DATE  
 BRANCH\_CODE  
 BORROW\_LEND\_IND  
 TENOR\_TO1  
 INTEREST\_RATE  
 RATECODEC  
 CCYCODEC  
 AMOUNTSLABC  
 EFFECTIVEDATEC  
 BRANCHCODEC  
 BORROWLENDINDC  
 TENORTOC  
 TDMAXRATE  
 TDPREDIFF

UDFDETAILS

FLDNAM

FLDVAL

FCUBS\_ERROR\_RESP

ERROR

ECODE

EDESC

FCUBS\_WARNING\_RESP

WARNING

WCODE

WDESC

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

**SOURCE**

Attribute	Description
Name	SOURCE
Datatype	String
Description	



Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

<b>Attribute</b>	<b>Description</b>	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description							
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
	Restrictions	Description					
	length	3					
pattern	[a-zA-Z_0-9]{3}						

[TOP](#)

## MODULEID

Attribute	Description						
Name	MODULEID						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nullable	true
	Attribute	Description					
	minOccurs	0					
nullable	true						

[TOP](#)

## SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	nullable	true
	Attribute	Description			
nullable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	nullable	true
	Attribute	Description			
nullable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about Full Response	

[TOP](#)

## Rate-Code-Full

Attribute	Description	
Name	Rate-Code-Full	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## RATE\_CODE

Attribute	Description	
Name	RATE_CODE	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## RATEDESC

<b>Attribute</b>	<b>Description</b>	
Name	RATEDESC	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	105

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## CHECKER

<b>Attribute</b>	<b>Description</b>	
Name	CHECKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## TXNSTAT

<b>Attribute</b>	<b>Description</b>	
Name	TXNSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## Rate-Ccy

Attribute	Description	
Name	Rate-Ccy	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## RATE\_CODE

Attribute	Description	
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

## CCY\_CODE

Attribute	Description	
Name	CCY_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

## BRANCH\_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	



Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## Fload-Rate

<b>Attribute</b>	<b>Description</b>	
Name	Fload-Rate	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## RATE\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## CCY\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	CCY_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## AMOUNT\_SLAB1

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNT_SLAB1	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

**EFFECTIVE\_DATE**

Attribute	Description	
Name	EFFECTIVE_DATE	
Datatype	Date	
Description		
Attributes	Attribute	Description
	minOccurs	1

**BRANCH\_CODE**

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

**BORROW\_LEND\_IND**

Attribute	Description	
Name	BORROW_LEND_IND	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	enumeration	B,L,M

**Filtrate-Detail**

Attribute	Description	
Name	Filtrate-Detail	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**RATE\_CODE**

Attribute	Description	
Name	RATE_CODE	
Datatype	String	

Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## CCY\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	CCY_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## AMOUNT\_SLAB

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNT_SLAB	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## EFFECTIVE\_DATE

<b>Attribute</b>	<b>Description</b>	
Name	EFFECTIVE_DATE	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## BORROW\_LEND\_IND

Attribute	Description				
Name	BORROW_LEND_IND				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>B,L,M</td></tr></tbody></table>	Restrictions	Description	enumeration	B,L,M
	Restrictions	Description			
enumeration	B,L,M				

[TOP](#)

## TENOR\_TO1

Attribute	Description				
Name	TENOR_TO1				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
	Attribute	Description			
minOccurs	1				

[TOP](#)

## INTEREST\_RATE

Attribute	Description				
Name	INTEREST_RATE				
Datatype	Number				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## RATECODEC

Attribute	Description				
Name	RATECODEC				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>10</td></tr></tbody></table>	Restrictions	Description	maxLength	10
	Restrictions	Description			
maxLength	10				

[TOP](#)

## CCYCODEC

Attribute	Description
Name	CCYCODEC
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## AMOUNTSLABC

<b>Attribute</b>	<b>Description</b>	
Name	AMOUNTSLABC	
Datatype	Number	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## EFFECTIVEDATEC

<b>Attribute</b>	<b>Description</b>	
Name	EFFECTIVEDATEC	
Datatype	Date	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## BRANCHCODEC

<b>Attribute</b>	<b>Description</b>	
Name	BRANCHCODEC	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## BORROWLENDINDC

<b>Attribute</b>	<b>Description</b>	
Name	BORROWLENDINDC	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## TENORTOC

Attribute	Description	
Name	TENORTOC	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## TDMAXRATE

Attribute	Description	
Name	TDMAXRATE	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## TDPREDIFF

Attribute	Description	
Name	TDPREDIFF	
Datatype	Number	
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## UDFDETAILS

Attribute	Description	
Name	UDFDETAILS	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## FLDNAM

Attribute	Description	
Name	FLDNAM	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	105
	minLength	1

[TOP](#)

## FLDVAL

Attribute	Description						
Name	FLDVAL						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0		
	Attribute	Description					
minOccurs	0						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>255</td></tr><tr><td>minLength</td><td>0</td></tr></tbody></table>	Restrictions	Description	maxLength	255	minLength	0
	Restrictions	Description					
	maxLength	255					
minLength	0						

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description				
Name	FCUBS_ERROR_RESP				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
	Attribute	Description			
minOccurs	0				

[TOP](#)

## ERROR

Attribute	Description				
Name	ERROR				
Datatype					
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>maxOccurs</td><td>unbounded</td></tr></tbody></table>	Attribute	Description	maxOccurs	unbounded
	Attribute	Description			
maxOccurs	unbounded				

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description
-----------	-------------

Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## WARNING

<b>Attribute</b>	<b>Description</b>	
Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## WCODE

<b>Attribute</b>	<b>Description</b>
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

<b>Attribute</b>	<b>Description</b>
Name	WDESC
Datatype	String
Description	

[TOP](#)



## 2.27.4.CF-ReopenFloatRateMaint-Res-PK-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*Rate-Code-PK*

*RATE\_CODE*

*BRANCH\_CODE*

*Rate-Code-IO*

*RATE\_CODE*

*BRANCH\_CODE*

*MAKER*

*MAKERSTAMP*

*MODNO*

*FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

*FCUBS\_WARNING\_RESP*

*WARNING*

*WCODE*

*WDESC*

**FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description
Name	OPERATION
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PK Response

[TOP](#)

## CHOICE

Attribute	Description
-----------	-------------

Name	CHOICE
Datatype	
Description	

[TOP](#)

### Rate-Code-PK

Attribute	Description	
Name	Rate-Code-PK	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

### RATE\_CODE

Attribute	Description	
Name	RATE_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

### BRANCH\_CODE

Attribute	Description	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	3

[TOP](#)

### Rate-Code-IO

Attribute	Description	
Name	Rate-Code-IO	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

### RATE\_CODE

Attribute	Description
-----------	-------------

Name	RATE_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## BRANCH\_CODE

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH_CODE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	1
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	3

[TOP](#)

## MAKER

<b>Attribute</b>	<b>Description</b>	
Name	MAKER	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERSTAMP	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	35

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description		



Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description	
Name	FCUBS_ERROR_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## ERROR

Attribute	Description	
Name	ERROR	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## ECODE

Attribute	Description
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

Attribute	Description
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

Attribute	Description	
Name	FCUBS_WARNING_RESP	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description
-----------	-------------

Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)



ICCF Service  
[April] [2014]

Oracle Financial Services software Limited  
Oracle Park  
Off Western Express Highway  
Goregaon (East)  
Mumbai, Maharashtra 400 063  
India

Worldwide Inquiries:  
Phone: +91 22 6718 3000  
Fax: +91 22 6718 3001  
[www.oracle.com/financialservices/](http://www.oracle.com/financialservices/)

Copyright © [2013], [2014], Oracle and/or its affiliates. All rights reserved.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

**U.S. GOVERNMENT END USERS:** Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are commercial computer software pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate failsafe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any

kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.