

Gateway Documentation - Generic Interface Service  
Oracle FLEXCUBE Universal Banking Release 11.3.83.02.0  
Release FCUBS\_11.3.2.0.0LA  
[April] [2014]



# Table Of Contents

---

<b>1. BACKGROUND</b>	.....	<b>1</b>
<b>2. FCUBSGIService</b>	.....	<b>2</b>
<b>2.1. interfaceProcessNew</b>	.....	<b>2</b>
2.1.1. <i>GI-InterfaceProcessNew-Req-Full-MSG.xsd</i>	.....	2
2.1.2. <i>GI-InterfaceProcessNew-Req-IO-MSG.xsd</i>	.....	11
2.1.3. <i>GI-InterfaceProcessNew-Res-Full-MSG.xsd</i>	.....	20
2.1.4. <i>GI-InterfaceProcessNew-Res-PK-MSG.xsd</i>	.....	31
<b>2.2. InterfaceProcessQuery</b>	.....	<b>43</b>
2.2.1. <i>GI-InterfaceProcessQuery-Req-IO-MSG.xsd</i>	.....	43
2.2.2. <i>GI-InterfaceProcessQuery-Res-Full-MSG.xsd</i>	.....	50

# 1.BACKGROUND

Integration of different applications and solutions is a key area in today's systems. A variety of specialized applications deployed on disparate platforms and using different infrastructure need to be able to communicate and integrate seamlessly with FLEXCUBE UBS in order to exchange data. The FLEXCUBE UBS Integration Gateway (referred to as Gateway) will cater to these integration needs.

The integration needs supported by the Gateway can be broadly categorized from the perspective of the Gateway as follows:

**1. Inbound application integration** – used when any external system needs to add, modify or query information within FLEXCUBE UBS

**2. Outbound application integration**– used when any external system needs to be notified of the various events that occur within FLEXCUBE UBS

The following sections provide detailed XSD documentation of all operations available in FCUBSGIService of GI-Module

## 2.FCUBSGIService

Generic Interface ServiceGeneric Interface Service

### 2.1.interfaceProcessNew

Triggering of Interface Processing

#### 2.1.1.GI-InterfaceProcessNew-Req-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*InterfaceProcess-Full*

*INTERFACECODE*

*FILENAME*

*PROCESSCODE*

*STATUS*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description				
Name	SOURCE				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
Restrictions	Description				
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## UBSCOMP

Attribute	Description				
Name	UBSCOMP				
Datatype	String				
Description					
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>enumeration</td><td>FCUBS,FCIS</td></tr></tbody></table>	Restrictions	Description	enumeration	FCUBS,FCIS
Restrictions	Description				
enumeration	FCUBS,FCIS				

[TOP](#)

## MSGID

Attribute	Description						
Name	MSGID						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nullable	true
Attribute	Description						
minOccurs	0						
nullable	true						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*		
Restrictions	Description						
pattern	[a-zA-Z_0-9]*						

[TOP](#)

## CORRELID

Attribute	Description						
Name	CORRELID						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nullable	true
Attribute	Description						
minOccurs	0						
nullable	true						
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*		
Restrictions	Description						
pattern	[a-zA-Z_0-9]*						

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description	
Name	OPERATION	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTITRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullRequest

[TOP](#)

## InterfaceProcess-Full

Attribute	Description
-----------	-------------

Name	InterfaceProcess-Full
Datatype	
Description	Includes Generic Interface File Process Creation Full details

[TOP](#)

## INTERFACECODE

Attribute	Description	
Name	INTERFACECODE	
Datatype	String	
Description	Indicates the Interface Code	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

## FILENAME

Attribute	Description	
Name	FILENAME	
Datatype	String	
Description	Indicates the File Name	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

## PROCESSCODE

Attribute	Description	
Name	PROCESSCODE	
Datatype	String	
Description	Indicates the Process Code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	FP,DP,AL,RT,RE

[TOP](#)

## STATUS

Attribute	Description	
Name	STATUS	
Datatype	String	
Description	Indicates Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**MAKERID**

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates the User id who created the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**MAKERDTSTAMP**

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates date and time when the user created the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

**CHECKERID**

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Indicates the Userid who authorized the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CHECKERDTSTAMP**

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and time when the user has authorized the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates the Modification Number	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorized : A Unauthorized : U	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorized status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## 2.1.2.GI-InterfaceProcessNew-Req-IO-MSG.xsd

### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

### *FCUBS\_BODY*

*InterfaceProcess-IO*

*INTERFACECODE*

*FILENAME*

*PROCESSCODE*

*STATUS*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

## **FCUBS\_HEADER**

<b>Attribute</b>	<b>Description</b>
Name	FCUBS_HEADER
Datatype	
Description	

**SOURCE**

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**UBSCOMP**

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

**MSGID**

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**CORRELID**

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**USERID**

Attribute	Description
Name	USERID

Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

<b>Attribute</b>	<b>Description</b>	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

<b>Attribute</b>	<b>Description</b>	
Name	MODULEID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

<b>Attribute</b>	<b>Description</b>	
Name	SERVICE	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

**SOURCE\_OPERATION**

Attribute	Description	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**SOURCE\_USERID**

Attribute	Description	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

**DESTINATION**

Attribute	Description	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**MULTITRIPID**

Attribute	Description	
Name	MULTITRIPID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

**FUNCTIONID**



Attribute	Description	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

Attribute	Description	
Name	ACTION	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

Attribute	Description	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description
Name	NAME
Datatype	String
Description	

[TOP](#)

## VALUE

Attribute	Description
Name	VALUE
Datatype	String
Description	

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about IORequest

[TOP](#)

## InterfaceProcess-IO

Attribute	Description
Name	InterfaceProcess-IO
Datatype	
Description	Includes Generic Interface File Process Creation Input Only details

[TOP](#)

## INTERFACECODE

Attribute	Description	
Name	INTERFACECODE	
Datatype	String	
Description	Indicates the Interface Code	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

## FILENAME

Attribute	Description	
Name	FILENAME	
Datatype	String	
Description	Indicates the File Name	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

## PROCESSCODE

Attribute	Description	
Name	PROCESSCODE	
Datatype	String	
Description	Indicates the Process Code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	FP,DP,AL,RT,RE

[TOP](#)

## STATUS

Attribute	Description	
Name	STATUS	
Datatype	String	
Description	Indicates Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## MAKERID

Attribute	Description
-----------	-------------

Name	MAKERID	
Datatype	String	
Description	Indicates the User id who created the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates date and time when the user created the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates the Userid who authorized the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and time when the user has authorized the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates the Modification Number	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorized : A Unauthorized : U	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## ONCEAUTH

<b>Attribute</b>	<b>Description</b>	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorized status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

### 2.1.3.GI-InterfaceProcessNew-Res-Full-MSG.xsd

#### *FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

#### *FCUBS\_BODY*

*InterfaceProcess-Full*

*INTERFACECODE*

*FILENAME*

*PROCESSCODE*

*STATUS*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

#### *FCUBS\_ERROR\_RESP*

*ERROR*

*ECODE*

*EDESC*

#### *FCUBS\_WARNING\_RESP*

*WARNING*

WCODE

WDESC

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true

Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nillable	true

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		
Attributes	Attribute	Description
	nillable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

Attribute	Description
-----------	-------------



Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

<b>Attribute</b>	<b>Description</b>	
Name	PARAM	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

<b>Attribute</b>	<b>Description</b>	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

<b>Attribute</b>	<b>Description</b>	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about FullResponse	

[TOP](#)

## InterfaceProcess-Full

<b>Attribute</b>	<b>Description</b>
------------------	--------------------

Name	InterfaceProcess-Full
Datatype	
Description	Includes Generic Interface File Process Creation Full details

[TOP](#)

## INTERFACECODE

Attribute	Description	
Name	INTERFACECODE	
Datatype	String	
Description	Indicates the Interface Code	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

[TOP](#)

## FILENAME

Attribute	Description	
Name	FILENAME	
Datatype	String	
Description	Indicates the File Name	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

[TOP](#)

## PROCESSCODE

Attribute	Description	
Name	PROCESSCODE	
Datatype	String	
Description	Indicates the Process Code	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	enumeration	FP,DP,AL,RT,RE

[TOP](#)

## STATUS

Attribute	Description	
Name	STATUS	
Datatype	String	
Description	Indicates Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**MAKERID**

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates the User id who created the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**MAKERDTSTAMP**

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates date and time when the user created the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

**CHECKERID**

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Indicates the Userid who authorized the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CHECKERDTSTAMP**

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and time when the user has authorized the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

**MODNO**

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates the Modification Number	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorized : A Unauthorized : U	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorized status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## FCUBS\_ERROR\_RESP

Attribute	Description
Name	FCUBS_ERROR_RESP
Datatype	

Description	Includes Error Response details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>
Name	ECODE
Datatype	String
Description	

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>
Name	EDESC
Datatype	String
Description	

[TOP](#)

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Includes Warning Response details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

<b>Attribute</b>	<b>Description</b>	
Name	WARNING	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)



## 2.1.4.GI-InterfaceProcessNew-Res-PK-MSG.xsd

*FCUBS\_HEADER*  
*SOURCE*  
*UBSCOMP*  
*MSGID*  
*CORRELID*  
*USERID*  
*BRANCH*  
*MODULEID*  
*SERVICE*  
*OPERATION*  
*SOURCE\_OPERATION*  
*SOURCE\_USERID*  
*DESTINATION*  
*MULTITRIPID*  
*FUNCTIONID*  
*ACTION*  
*MSGSTAT*  
*PASSWORD*  
*ADDL*  
*PARAM*  
*NAME*  
*VALUE*  
*FCUBS\_BODY*  
*CHOICE*  
*InterfaceProcess-PK*  
*INTERFACECODE*  
*FILENAME*  
*STATUS*  
*InterfaceProcess-IO*  
*INTERFACECODE*  
*FILENAME*  
*PROCESSCODE*  
*STATUS*  
*MAKERID*  
*MAKERDTSTAMP*  
*CHECKERID*  
*CHECKERDTSTAMP*  
*MODNO*  
*AUTHSTAT*  
*RECSTAT*  
*ONCEAUTH*  
*FCUBS\_ERROR\_RESP*

[ERROR](#)  
[ECODE](#)  
[EDESC](#)  
[FCUBS\\_WARNING\\_RESP](#)  
[WARNING](#)  
[WCODE](#)  
[WDESC](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

**PASSWORD**

Attribute		Description
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

**ADDL**

Attribute		Description
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

**PARAM**

Attribute		Description
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

**NAME**

Attribute		Description
Name	NAME	
Datatype	String	
Description		

**VALUE**

Attribute		Description
Name	VALUE	
Datatype	String	
Description		

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about PKResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## InterfaceProcess-PK

Attribute	Description
Name	InterfaceProcess-PK
Datatype	
Description	Includes Generic Interface File Process Creation Primary Key details

[TOP](#)

## INTERFACECODE

Attribute	Description				
Name	INTERFACECODE				
Datatype	String				
Description	Indicates the Interface Code				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>10</td></tr></tbody></table>	Restrictions	Description	maxLength	10
Restrictions	Description				
maxLength	10				

[TOP](#)

## FILENAME

Attribute	Description				
Name	FILENAME				
Datatype	String				
Description	Indicates the File Name				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>50</td></tr></tbody></table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

[TOP](#)

## STATUS

Attribute	Description
Name	STATUS

Datatype	String	
Description	Indicates Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## InterfaceProcess-IO

<b>Attribute</b>	<b>Description</b>
Name	InterfaceProcess-IO
Datatype	
Description	Includes Generic Interface File Process Creation Input Only details

[TOP](#)

## INTERFACECODE

<b>Attribute</b>	<b>Description</b>	
Name	INTERFACECODE	
Datatype	String	
Description	Indicates the Interface Code	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## FILENAME

<b>Attribute</b>	<b>Description</b>	
Name	FILENAME	
Datatype	String	
Description	Indicates the File Name	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

[TOP](#)

## PROCESSCODE

<b>Attribute</b>	<b>Description</b>	
Name	PROCESSCODE	
Datatype	String	
Description	Indicates the Process Code	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FP,DP,AL,RT,RE



**STATUS**

Attribute	Description	
Name	STATUS	
Datatype	String	
Description	Indicates Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**MAKERID**

Attribute	Description	
Name	MAKERID	
Datatype	String	
Description	Indicates the User id who created the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**MAKERDTSTAMP**

Attribute	Description	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates date and time when the user created the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

**CHECKERID**

Attribute	Description	
Name	CHECKERID	
Datatype	String	
Description	Indicates the Userid who authorized the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	12

**CHECKERDTSTAMP**

Attribute	Description	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and time when the user has authorized the record	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	25

[TOP](#)

## MODNO

Attribute	Description	
Name	MODNO	
Datatype	Number	
Description	Indicates the Modification Number	
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## AUTHSTAT

Attribute	Description	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorized : A UnAuthorized : U	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## RECSTAT

Attribute	Description	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

[TOP](#)

## ONCEAUTH

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	

Description	Indicates Once Authorized status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes Error Response details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Includes Warning Response details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)

## 2.2.InterfaceProcessQuery

Query Interface Processing Status

### 2.2.1.GI-InterfaceProcessQuery-Req-IO-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*InterfaceProcess-IO*

*INTERFACECODE*

*FILENAME*

*STATUS*

#### **FCUBS\_HEADER**

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

#### **SOURCE**

Attribute	Description
Name	SOURCE
Datatype	String
Description	

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

<b>Attribute</b>	<b>Description</b>	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

<b>Attribute</b>	<b>Description</b>	
Name	MSGID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

<b>Attribute</b>	<b>Description</b>	
Name	CORRELID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nullable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

<b>Attribute</b>	<b>Description</b>	
Name	USERID	
Datatype	String	
Description		
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description						
Name	BRANCH						
Datatype	String						
Description							
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>length</td><td>3</td></tr><tr><td>pattern</td><td>[a-zA-Z_0-9]{3}</td></tr></tbody></table>	Restrictions	Description	length	3	pattern	[a-zA-Z_0-9]{3}
	Restrictions	Description					
	length	3					
pattern	[a-zA-Z_0-9]{3}						

[TOP](#)

## MODULEID

Attribute	Description						
Name	MODULEID						
Datatype	String						
Description							
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	minOccurs	0	nullable	true
	Attribute	Description					
	minOccurs	0					
nullable	true						

[TOP](#)

## SERVICE

Attribute	Description				
Name	SERVICE				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	nullable	true
	Attribute	Description			
nullable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## OPERATION

Attribute	Description				
Name	OPERATION				
Datatype	String				
Description					
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>nullable</td><td>true</td></tr></tbody></table>	Attribute	Description	nullable	true
	Attribute	Description			
nullable	true				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>pattern</td><td>[a-zA-Z_0-9]*</td></tr></tbody></table>	Restrictions	Description	pattern	[a-zA-Z_0-9]*
	Restrictions	Description			
pattern	[a-zA-Z_0-9]*				

[TOP](#)

## SOURCE\_OPERATION

Attribute	Description
Name	SOURCE_OPERATION
Datatype	String
Description	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0



Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE

[TOP](#)

## PASSWORD

<b>Attribute</b>	<b>Description</b>	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	128
	pattern	[a-zA-Z_0-9=+/*]*

[TOP](#)

## ADDL

<b>Attribute</b>	<b>Description</b>	
Name	ADDL	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

Attribute	Description	
Name	FCUBS_BODY	
Datatype		
Description	This XSD Gives Information about IORequest	

[TOP](#)

## InterfaceProcess-IO

Attribute	Description	
Name	InterfaceProcess-IO	
Datatype		
Description	Includes Generic Interface File Process Querying Input Only details	

[TOP](#)

## INTERFACECODE

Attribute	Description	
Name	INTERFACECODE	
Datatype	String	
Description	Indicates the Interface Code	
Attributes	Attribute	Description
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	10

[TOP](#)

## FILENAME

<b>Attribute</b>	<b>Description</b>	
Name	FILENAME	
Datatype	String	
Description	Indicates the File Name	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	50

[TOP](#)

## STATUS

<b>Attribute</b>	<b>Description</b>	
Name	STATUS	
Datatype	String	
Description	Indicates Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## 2.2.2.GI-InterfaceProcessQuery-Res-Full-MSG.xsd

*FCUBS\_HEADER*

*SOURCE*

*UBSCOMP*

*MSGID*

*CORRELID*

*USERID*

*BRANCH*

*MODULEID*

*SERVICE*

*OPERATION*

*SOURCE\_OPERATION*

*SOURCE\_USERID*

*DESTINATION*

*MULTITRIPID*

*FUNCTIONID*

*ACTION*

*MSGSTAT*

*PASSWORD*

*ADDL*

*PARAM*

*NAME*

*VALUE*

*FCUBS\_BODY*

*CHOICE*

*InterfaceProcess-Full*

*INTERFACECODE*

*FILENAME*

*PROCESSCODE*

*STATUS*

*MAKERID*

*MAKERDTSTAMP*

*CHECKERID*

*CHECKERDTSTAMP*

*MODNO*

*AUTHSTAT*

*RECSTAT*

*ONCEAUTH*

*InterfaceProcess-IO*

*INTERFACECODE*

*FILENAME*

*STATUS*

*FCUBS\_ERROR\_RESP*

[ERROR](#)  
[ECODE](#)  
[EDESC](#)  
[FCUBS\\_WARNING\\_RESP](#)  
[WARNING](#)  
[WCODE](#)  
[WDESC](#)

## FCUBS\_HEADER

Attribute	Description
Name	FCUBS_HEADER
Datatype	
Description	

[TOP](#)

## SOURCE

Attribute	Description	
Name	SOURCE	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## UBSCOMP

Attribute	Description	
Name	UBSCOMP	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	enumeration	FCUBS,FCIS

[TOP](#)

## MSGID

Attribute	Description	
Name	MSGID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## CORRELID

Attribute	Description	
Name	CORRELID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true
Restrictions	Restrictions	Description
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## USERID

Attribute	Description	
Name	USERID	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	maxLength	12
	pattern	[A-Z_0-9]*

[TOP](#)

## BRANCH

Attribute	Description	
Name	BRANCH	
Datatype	String	
Description		
Restrictions	Restrictions	Description
	length	3
	pattern	[a-zA-Z_0-9]{3}

[TOP](#)

## MODULEID

Attribute	Description	
Name	MODULEID	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
	nullable	true

[TOP](#)

## SERVICE

Attribute	Description	
Name	SERVICE	
Datatype	String	
Description		

Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_OPERATION

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_OPERATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## SOURCE\_USERID

<b>Attribute</b>	<b>Description</b>	
Name	SOURCE_USERID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
	nillable	true

[TOP](#)

## DESTINATION

<b>Attribute</b>	<b>Description</b>	
Name	DESTINATION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MULTIRIPID

<b>Attribute</b>	<b>Description</b>	
Name	MULTIRIPID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## FUNCTIONID

<b>Attribute</b>	<b>Description</b>	
Name	FUNCTIONID	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	8
	pattern	[A-Z_0-9]*

[TOP](#)

## ACTION

<b>Attribute</b>	<b>Description</b>	
Name	ACTION	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	pattern	[a-zA-Z_0-9]*

[TOP](#)

## MSGSTAT

<b>Attribute</b>	<b>Description</b>	
Name	MSGSTAT	
Datatype	String	
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	SUCCESS,WARNING,FAILURE



[TOP](#)

## PASSWORD

Attribute	Description	
Name	PASSWORD	
Datatype	String	
Description		
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	128
	pattern	[a-zA-Z_0-9=+]*

[TOP](#)

## ADDL

Attribute	Description	
Name	ADDL	
Datatype		
Description		
Attributes	Attribute	Description
	minOccurs	0

[TOP](#)

## PARAM

Attribute	Description	
Name	PARAM	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## NAME

Attribute	Description	
Name	NAME	
Datatype	String	
Description		

[TOP](#)

## VALUE

Attribute	Description	
Name	VALUE	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_BODY

Attribute	Description
Name	FCUBS_BODY
Datatype	
Description	This XSD Gives Information about FullResponse

[TOP](#)

## CHOICE

Attribute	Description
Name	CHOICE
Datatype	
Description	

[TOP](#)

## InterfaceProcess-Full

Attribute	Description
Name	InterfaceProcess-Full
Datatype	
Description	Includes Generic Interface File Process Querying Full details

[TOP](#)

## INTERFACECODE

Attribute	Description				
Name	INTERFACECODE				
Datatype	String				
Description	Indicates the Interface Code				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>1</td></tr></tbody></table>	Attribute	Description	minOccurs	1
Attribute	Description				
minOccurs	1				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>10</td></tr></tbody></table>	Restrictions	Description	maxLength	10
Restrictions	Description				
maxLength	10				

[TOP](#)

## FILENAME

Attribute	Description				
Name	FILENAME				
Datatype	String				
Description	Indicates the File Name				
Attributes	<table border="1"><thead><tr><th>Attribute</th><th>Description</th></tr></thead><tbody><tr><td>minOccurs</td><td>0</td></tr></tbody></table>	Attribute	Description	minOccurs	0
Attribute	Description				
minOccurs	0				
Restrictions	<table border="1"><thead><tr><th>Restrictions</th><th>Description</th></tr></thead><tbody><tr><td>maxLength</td><td>50</td></tr></tbody></table>	Restrictions	Description	maxLength	50
Restrictions	Description				
maxLength	50				

[TOP](#)

## PROCESSCODE

Attribute	Description
Name	PROCESSCODE

Datatype	String	
Description	Indicates the Process Code	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	enumeration	FP,DP,AL,RT,RE

[TOP](#)

## STATUS

<b>Attribute</b>	<b>Description</b>	
Name	STATUS	
Datatype	String	
Description	Indicates Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## MAKERID

<b>Attribute</b>	<b>Description</b>	
Name	MAKERID	
Datatype	String	
Description	Indicates the User id who created the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## MAKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	MAKERDTSTAMP	
Datatype	String	
Description	Indicates date and time when the user created the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## CHECKERID

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERID	
Datatype	String	
Description	Indicates the Userid who authorized the record	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	12

[TOP](#)

## CHECKERDTSTAMP

<b>Attribute</b>	<b>Description</b>	
Name	CHECKERDTSTAMP	
Datatype	String	
Description	Indicates date and time when the user has authorized the record	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	25

[TOP](#)

## MODNO

<b>Attribute</b>	<b>Description</b>	
Name	MODNO	
Datatype	Number	
Description	Indicates the Modification Number	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0

[TOP](#)

## AUTHSTAT

<b>Attribute</b>	<b>Description</b>	
Name	AUTHSTAT	
Datatype	String	
Description	Indicates Authorization Status Authorized : A UnAuthorized : U	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## RECSTAT

<b>Attribute</b>	<b>Description</b>	
Name	RECSTAT	
Datatype	String	
Description	Indicates Record Status	
Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

**ONCEAUTH**

Attribute	Description	
Name	ONCEAUTH	
Datatype	String	
Description	Indicates Once Authorized status	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	1

**InterfaceProcess-IO**

Attribute	Description	
Name	InterfaceProcess-IO	
Datatype		
Description	Includes Generic Interface File Process Querying Input Only details	

**INTERFACECODE**

Attribute	Description	
Name	INTERFACECODE	
Datatype	String	
Description	Indicates the Interface Code	
Attributes	Attribute	Description
	minOccurs	1
Restrictions	Restrictions	Description
	maxLength	10

**FILENAME**

Attribute	Description	
Name	FILENAME	
Datatype	String	
Description	Indicates the File Name	
Attributes	Attribute	Description
	minOccurs	0
Restrictions	Restrictions	Description
	maxLength	50

**STATUS**

Attribute	Description	
Name	STATUS	
Datatype	String	
Description	Indicates Status	

Attributes	<b>Attribute</b>	<b>Description</b>
	minOccurs	0
Restrictions	<b>Restrictions</b>	<b>Description</b>
	maxLength	1

[TOP](#)

## FCUBS\_ERROR\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_ERROR_RESP	
Datatype		
Description	Includes Error Response details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## ERROR

<b>Attribute</b>	<b>Description</b>	
Name	ERROR	
Datatype		
Description		
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded

[TOP](#)

## ECODE

<b>Attribute</b>	<b>Description</b>	
Name	ECODE	
Datatype	String	
Description		

[TOP](#)

## EDESC

<b>Attribute</b>	<b>Description</b>	
Name	EDESC	
Datatype	String	
Description		

[TOP](#)

## FCUBS\_WARNING\_RESP

<b>Attribute</b>	<b>Description</b>	
Name	FCUBS_WARNING_RESP	
Datatype		
Description	Includes Warning Response details	
Attributes	<b>Attribute</b>	<b>Description</b>
	maxOccurs	unbounded
	minOccurs	0

[TOP](#)

## WARNING

Attribute	Description	
Name	WARNING	
Datatype		
Description		
Attributes	Attribute	Description
	maxOccurs	unbounded

[TOP](#)

## WCODE

Attribute	Description
Name	WCODE
Datatype	String
Description	

[TOP](#)

## WDESC

Attribute	Description
Name	WDESC
Datatype	String
Description	

[TOP](#)



**Generic Interface Service**

[April] [2014]

**Oracle Financial Services software Limited**

**Oracle Park**

**Off Western Express Highway**

**Goregaon (East)**

**Mumbai, Maharashtra 400 063**

**India**

**Worldwide Inquiries:**

**Phone: +91 22 6718 3000**

**Fax: +91 22 6718 3001**

**[www.oracle.com/financialservices/](http://www.oracle.com/financialservices/)**

**Copyright © [2013], [2014], Oracle and/or its affiliates. All rights reserved.**

**Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.**

**U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are commercial computer software pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.**

**This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate failsafe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.**

**This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.**

**The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.**

**This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any**



kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.