Oracle Banking Digital Experience

OBDX-OHS UI Configurations Manual

Release 17.1.0.0.0

Part No. E83887-01

March 2017

ORACLE®

OBDX-OHS UI Configurations Manual

March 2017

Oracle Financial Services Software Limited

Oracle Park

Off Western Express Highway

Goregaon (East)

Mumbai, Maharashtra 400 063

India

Worldwide Inquiries:

Phone: +91 22 6718 3000

Fax:+91 22 6718 3001

www.oracle.com/financialservices/

Table of Contents

1. Preface

1.1 Intended Audience

This document is intended for the following audience:

- Customers

- Partners

1.2 Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc.

1.3 Access to OFSS Support

Oracle customers have access to electronic support through My Oracle Support. For information, visit http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info or visit http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs if you are hearing impaired.

1.4 Structure

This manual is organized into the following categories:

Preface gives information on the intended audience. It also describes the overall structure of the User Manual.

The subsequent chapters describes following details:

- Prerequisite

- UI Deployment

- Configuration / Installation

1.5 Related Information Sources

For more information on Oracle Banking Digital Experience Release 17.1.0.0.0, refer to the following documents:

- Oracle Banking Digital Experience Licensing Guide

- Oracle Banking Digital Experience Security Guide

2.   Pre-requisite

OHS software along with instance should be available for use.

3. UI deployment

Below steps needs to be performed for UI deployment on OHS server.

- Copy the obdx.conf from OBDX_Installer/installables/ui/config directory into the instance config directory (where httpd.conf is present).

- Create a directory where obdx UI files would be deployed on OHS server.

- Copy all files / directories from OBDX_Installer/installables/ui/deploy into newly created directory.

4. Configuration to run UI on Oracle HTTP Server

Make sure following OHS modules must be loaded

- mod_rewrite.so
- mod_deflate.so
- mod_expires.so
- mod_vhost_alias.so
- mod_mime.so
- mod_alias.so
- mod_headers.so

Following are the changes need to be done in the obdx.conf file and place this file in same folder where httpd.conf file exists.

1. Replace the <CHANNEL_PATH> (all occurrences) with the newly created directory (from previous UI deployment step).

2. Configuration for Content Security Policy, refer to the below document

    Oracle Banking Digital Experience Security Guide

Include the obdx.conf into httpd.conf using below configuration

```
 include "obdx.conf" (needs to be added in httpd.conf)
```

Following are the changes need to be done in mod_wl_ohs.conf

Copy below configuration into mod_wl_ohs.conf

<IfModule weblogic_module>

   WebLogicHost HOSTNAME

   WebLogicPort MANAGE_SERVER_PORT

   Debug ON

  WLLogFile DIR/FILENAEME

   MatchExpression /digx/*
         </IfModule>

Configure below properties

    a. HOSTNAME – Weblogic server hostname (where OBDX weblogic domain is configured)

    b. MANAGE_SERVER_PORT – Weblogic manage server port (where OBDX application is deployed)

    c. DIR / FILENAME – Path where log file should be generated

Sample configuration (for reference purpose only)

<IfModule weblogic_module>

      WebLogicHost wls_server1

    WebLogicPort 7003

      Debug ON

      WLLogFile /tmp/weblogic_obp.log

      MatchExpression /digx/*

</IfModule>

Configuring the OAM Server:

By default OAM server URL is set as **http://mum00aon.in.oracle.com:14100/oam/server**

Replace it to you OAM server URL in the following files:

- <CHANNEL_PATH>/index/components/login/login-form/ko/bindings/login-form-bindings.js

- <CHANNEL_PATH>/index/components/login/login-screen/ko/bindings/login-screen-bindings.js

Once all above steps are completed, restart the OHS server.