

**Oracle® Communications**  
**Diameter Signaling Router**  
DCA Programmer's Guide  
Release 8.2  
**E89013 Revision 01**

January 2018

**ORACLE®**

**Oracle® Communications Diameter Signaling Router DCA Programmer's Guide, DSR Release 8.2**

Copyright © 2011, 2018, Oracle and/or its affiliates. All rights reserved.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

**U.S. GOVERNMENT END USERS:** Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

## Table of Contents

<b>Table of Contents.....</b>	<b>3</b>
<b>List of Tables.....</b>	<b>7</b>
<b>List of Figures .....</b>	<b>7</b>
<b>1. Introduction .....</b>	<b>10</b>
1.1 References .....	10
1.2 Glossary .....	10
1.3 Terminology.....	11
1.4 WARNING on Copying and Pasting Code from this Guide .....	11
<b>2. DCA Activation and Deactivation.....</b>	<b>12</b>
2.1 DCA Activation .....	12
2.1.1 DCA Framework Activation .....	13
2.1.2 DCA Activation .....	13
2.1.3 Post-Activation DCA State .....	14
2.2 DCA Deactivation .....	14
2.2.1 DCA De-Activation .....	14
2.2.2 DCA Framework De-Activation .....	14
<b>3. DCA Provisioning – The Blacklist DCA .....</b>	<b>14</b>
3.1 The Blacklist DCA.....	15
3.2 Prerequisites.....	15
3.3 The Process .....	15
3.3.1 Step 1: Configure DCA General Options and Behavior .....	15
3.3.2 Step 2: Create New Development Application Version.....	15
3.3.3 Step 3: Define the Configuration Data Structure.....	17
3.3.4 Step 4: Provision the Configuration Data .....	18
3.3.5 Step 5: Provision the Business Logic.....	19
3.3.5.1 Where is the Perl Script Being Executed? .....	20
3.3.5.2 How Do the Event Handlers Get Invoked? .....	20
3.3.5.3 How Does DCA Configuration Data Get Accessed?.....	20
3.3.5.4 What is the Main Part Good For?.....	20
3.3.6 Step 6: Render Flow Control Chart, Save Script, Check Syntax .....	21
3.3.7 Step 7: Test the DCA Version .....	22
3.3.8 Step 8: Promote the DCA Version to Production State.....	22
<b>4. DCA Lifecycle .....</b>	<b>23</b>
<b>5. Developing Stateful DCA .....</b>	<b>26</b>
<b>6. A Stateful DCA Using the U-SBR Infrastructure.....</b>	<b>26</b>

6.1	The CountULR DCA .....	26
6.2	Prerequisites.....	26
6.3	The Process .....	27
6.3.1	Step 1: Configure DCA Global Options and Behavior.....	27
6.3.2	Step 2: Create a New Development Version .....	28
6.3.3	Step A: Configure the U-SBR DBs.....	28
6.3.3.1	Step A.1: Servers Configuration .....	29
6.3.3.2	Step A.2: Server Group Configuration.....	29
6.3.3.3	Step A.3: Places Configuration .....	30
6.3.3.4	Step A.4: Place Associations Configuration.....	31
6.3.3.5	Step A.5: Resource Domain Configuration.....	32
6.3.3.6	Step A.6: SBR Database Configuration .....	34
6.3.4	Step 3: Define the Configuration Data Schema .....	35
6.3.5	Step 4: Provision the Configuration Data .....	35
6.3.6	Step 5: Provision DCA Business Logic .....	35
6.3.6.1	What Does a State Consist Of?.....	39
6.3.6.2	What are Asynchronous API Calls and Callbacks?.....	40
6.3.6.3	How is the U-SBR State Returned to the Perl Script?.....	40
6.3.6.4	What is Concurrent in a concurrentUpdate? .....	40
6.3.7	Step 6: Render the Flow Control Chart .....	42
6.3.8	Step B: Logical to Physical U-SBR DB Name Mapping .....	42
6.3.9	Step 7: Test the DCA Version .....	43
6.3.10	Step 8: Promote the DCA Version to Production .....	43
<b>7.</b>	<b>Monitoring DCA.....</b>	<b>43</b>
<b>8.</b>	<b>DCA Using Custom MEALs .....</b>	<b>44</b>
8.1	The Rate DCA .....	44
8.2	Prerequisites.....	44
8.3	The Process .....	44
8.3.1	Step I: Differentiate a C-MEAL.....	45
8.3.2	Step 1: Configure DCA General Options and Behavior .....	45
8.3.3	Step 2: Create a New Development Version .....	45
8.3.4	Step 3: Define the Configuration Data Schema .....	45
8.3.5	Step 4: Provision the Configuration Data .....	45
8.3.6	Step 5: Provision DCA Business Logic .....	45
8.3.7	Step 6: Render the Flow Control Chart .....	46
8.3.8	Step 7: Test the DCA Version .....	46

8.3.9 Step 8: Promote the DCA Version to Production .....	48
<b>9. GUI Overview.....</b>	<b>49</b>
9.1 NO/SO differences .....	49
9.2 NO Screens .....	49
9.2.1 Configuration Screen.....	50
9.2.2 Custom MEALs.....	51
9.2.2.1 View Custom MEALs.....	51
9.2.2.2 Configure the Counter Custom MEAL Template.....	51
9.2.2.3 Configure the Basic Custom MEAL Template.....	52
9.2.2.4 Configure the Rate Custom MEAL Template.....	53
9.2.2.5 Configure the Event Custom MEAL Template.....	54
9.2.3 General Options Screen.....	55
9.2.4 Trial MPs Assignment Screen .....	55
9.2.5 Application Control Screen .....	56
9.2.6 Create New Development Screen.....	57
9.2.7 Copy to New Development Screen .....	57
9.2.8 Export Pop-Up Window .....	58
9.2.9 Import Pop-Up Window .....	58
9.2.10 SBR DB Name Mapping Screen .....	60
9.2.11 Development Environment .....	61
9.2.12 Tables Screen .....	61
9.2.13 Provision Tables Screen .....	64
9.3 SO Screens .....	66
9.3.1 Application Control Screen.....	67
9.3.2 Export Pop-Up Window .....	67
9.3.3 Import Pop-Up Window .....	67
9.3.4 Tables Screen .....	67
9.3.5 Provision Tables Screen .....	68
9.4 System Options .....	69
<b>10. Development Environment Overview .....</b>	<b>70</b>
10.1 Development Environment Modes .....	70
10.2 Layout	71
10.3 Code Text Editor.....	73
10.4 Flow Control Chart.....	73
10.4.1 Start Symbol .....	74
10.4.2 Execution Block Symbol .....	74
10.4.3 Asynchronous Call Symbol .....	74

10.4.4 Termination Symbol .....	74
10.4.5 Delete symbol from the Flow Control Chart .....	74
10.4.6 Flow Control Chart Validation.....	75
10.4.7 Command Output Area .....	75
10.4.8 Render Chart.....	75
10.4.9 Save .....	76
10.4.10        Check Syntax .....	76
10.4.11        Compile .....	76
10.5 Race Conditions .....	76
<b>11. APIs.....</b>	<b>78</b>
11.1 The EDL API.....	78
11.1.1 API to Manipulate the Diameter Header .....	78
11.1.2 API to Manipulate the Diameter AVPs .....	81
11.1.3 API to Manipulate the Diameter Grouped AVPs .....	86
11.2 Diameter Transaction Stateful APIs .....	87
11.2.1 Internal Variables .....	87
11.2.2 Diameter Transaction Context Variables .....	88
11.3 Read DCA Configuration Data .....	88
11.4 Routing API .....	89
11.5 Debugging API .....	90
11.6 Custom MEAL API.....	91
11.6.1 Counter Template API.....	91
11.6.2 Rate Template.....	92
11.6.3 Basic Template.....	95
11.6.4 Event Template .....	97
11.7 U-SBR API.....	98
11.7.1 The Prototype of Queries and Query Results .....	99
11.7.1.1 Specifying the Query .....	99
11.7.1.2 Retrieving the Query Result .....	100
11.7.2 The U-SBR API Functions.....	101
11.8 Peer Information .....	104
11.8.1 Check for Configured Peer .....	104
11.8.2 Fethc the Originator Peer .....	104
<b>12. Interaction with IDIH.....</b>	<b>105</b>
<b>13. Best Practices .....</b>	<b>107</b>
13.1 The Main Part of the Perl Script .....	107
13.2 Perl Global Variables.....	108

13.3 Returning Control from a Perl Subroutine .....	108
13.4 Callbacks .....	109
13.5 Sending multiple U-SBR Queries .....	109
13.6 Accessing Lower Layer Data from Mediation.....	110
13.7 Performance Tuning .....	110

## **List of Tables**

Table 1: NO/SO GUI differences .....	49
Table 2: NO GUI Tables and Configuration Data Accessibility.....	62
Table 3: SO GUI Tables and Configuration Data Accessibility.....	68
Table 4: IDIH Events .....	105

## **List of Figures**

Figure 1: DCA Activation- Deactivation Lifecycle .....	12
Figure 2: DCA Framework Menu .....	13
Figure 3: DCA Measurements.....	13
Figure 4: DCA KPIs.....	13
Figure 5: DCA Menu .....	14
Figure 6: Create a New Application Version .....	16
Figure 7: New Application Version Created .....	16
Figure 8: Create a New Database .....	17
Figure 9: Provision Table BlackList.....	18
Figure 10: Insert a New Data Row to the BlackList Table .....	18
Figure 11: Provision DCA DB Tables.....	18
Figure 12: The Blacklist DCA Development Environment .....	19
Figure 13: Blacklist Perl Code.....	19
Figure 14: Event Handler Subroutine Name Configuration .....	20
Figure 15: Development Environment Buttons .....	21
Figure 16: Trial MP Assignment.....	22
Figure 17: Transitions from Development to Production State .....	23
Figure 18: Creating a New DCA Version .....	24
Figure 19: Assignment of the Version to a DA-MP .....	25
Figure 20: SBR Topology Example.....	28
Figure 21: Servers Configuration .....	29
Figure 22: Server Groups Configuration .....	30
Figure 23: Places Configuration.....	30

Figure 24: View Places .....	31
Figure 25: Create Place Association.....	31
Figure 26: View Place Association.....	32
Figure 27: SBR Resource Domain Configuration .....	32
Figure 28: DCA MP Resource Domain Configuration .....	33
Figure 29: View Resource Domain Configuration.....	33
Figure 30: Create SBR Database .....	34
Figure 31: View SBR Database .....	35
Figure 32: CountULR Call Flow .....	36
Figure 33: CountULR Perl Code .....	39
Figure 34: A Counter Increment Race .....	41
Figure 35: Flow Control Chart.....	42
Figure 36: SBR DB Name Mapping .....	42
Figure 37: View SBR DB Name Mapping .....	43
Figure 38: TestRate Differentiation .....	45
Figure 39: The Rate DCA Code.....	45
Figure 40: Filter DCA:Rate KPIs .....	46
Figure 41: Display TestRate KPI.....	47
Figure 42: Filter DCA:Rate Measurements.....	47
Figure 43: Display the TestRate measurements.....	48
Figure 44: TestRate Alarm History.....	48
Figure 45: NO Screens .....	50
Figure 46: NO Configuration Screen.....	50
Figure 47: The Custom MEAL View Screen .....	51
Figure 48: The Counter Template Configuration Screen.....	51
Figure 49: The Basic Template Configuration Screen .....	52
Figure 50: The Rate Template Configuration Screen .....	53
Figure 51: The Event Template Configuration Screen .....	54
Figure 52: NO General Options .....	55
Figure 53: NO Trial MPs Assignment .....	55
Figure 54: NO Application Control .....	56
Figure 55: NO Create New Development Screen.....	57
Figure 56: NO Copy to New Development.....	57
Figure 57: NO Export .....	58
Figure 58: NO Import Business Logic .....	59
Figure 59: NO Import Configuration Data .....	59
Figure 60: NO SBR DB Name Mapping View.....	60

Figure 61: NO SBR DB Name Mapping Insert.....	60
Figure 62: NO Tables View Screen .....	61
Figure 63: NO Tables Insert Screen .....	63
Figure 64: Provision Table Button.....	64
Figure 65: NO Provision Table View Screen .....	65
Figure 66: NO Provision Table Insert Screen .....	65
Figure 67: SO Screens.....	66
Figure 68: SO Application Control Screen.....	67
Figure 69: SO Tables View Screen (empty) .....	68
Figure 70: System Options for the Unavailable Operation Status .....	69
Figure 71: System Options for the Exhausted DRL Resources.....	69
Figure 72: System Options for the Run-Time Error .....	70
Figure 73: System Options for the Realm and FQDN .....	70
Figure 74: System Options for the Application Invocation .....	70
Figure 75: Layout Structure.....	71
Figure 76: Layout Print Screen .....	72
Figure 77: Toolbox and Actions .....	72
Figure 78: Code Text Editor .....	73
Figure 79: IDIH Event Trace of an U-SBR Query .....	107

## 1. Introduction

Diameter Custom Applications (DCA) is a framework that enables a significant reduction of the coding – testing – deployment – maintenance cycle in the development of Diameter applications.

This document is intended for developers of DCAs. It describes how DCAs can be created, how their business logic and configuration data can be provisioned, how their lifecycle from development to production can be managed, and the various APIs available.

Following the DCA framework and DCA activation (Chapter 2), the document is organized around three DCA examples: Blacklist (Chapter 3), CountULR (Chapter 6), and Rate (Chapter 8), which demonstrate the basic features of the DCA framework. A number of additional chapters, interleaved with the chapters describing the three DCAs provide a gradual insight into essential capabilities of the DCA framework, like the DCA lifecycle management (Chapter 4), stateful DCA development mechanisms (Chapter 5), and tools for monitoring the execution of DCA (Chapter 7).

Chapter 9 provides a complete GUI reference, with the Development Environment described in Chapter 10.

The various APIs available are described in Chapter 11.

### 1.1 References

- [1] CGBU\_018429 - DCA Framework and Application Activation and Deactivation
- [2] E58954-02, DSR Software Installation and Configuration Procedure

### 1.2 Glossary

This section lists terms and acronyms specific to this document.

Acronym	Description
API	Application Programming Interface
ART	Application Routing Table
AVP	Attribute Value Pair (in context of Diameter protocol)
ComAgent	Communication Agent
DA-MP	Diameter Agent Message Processor
DAI	DSR Application Infrastructure
DAL	Diameter Application Layer
DBCA	Database Change Agent
DCA	Diameter Custom Applications (framework)
DRL	Diameter Routing Layer
DSR	Diameter Signaling Router
EDL	Encode-Decode Library
I-SBR	Independent SBR (Session Binding Repository)
JSON	Java Script Object Notation
MEAL	Measurement, Event and Alarm
MO	Managed Object
NOAM	Network Operations Administration and Maintenance

Acronym	Description
OAM	Operations, Administration & Maintenance
OID	Object Identifier (SNMP)
Perl	Practical Extraction and Reporting Language – a scripting language
PRT	Peer Routing Table
SNMP	Simple Network Management Protocol
SOAM	Site Operations Administration and Maintenance
TTR	Trace Transaction Record (in context of IDIH)
U-SBR	Universal SBR (Session Binding Repository) – used by DCA to store generic application state data

### 1.3 Terminology

Acronym	Description
A-Level	NOAM –level
Asynchronous Call Symbol	Symbol in the Development Environment that represents a code statement that calls an asynchronous function provided by the DCA Perl API. The code statement occurs within a preceding Execution Block. The symbol displays the name of an asynchronous function that is invoked.
B-Level	SOAM- level
DCE Development Environment	Web application where a custom Diameter application developer can edit, save, check syntax, compile the application code for a Diameter Custom Application, and generate an Interactive Flow Control Chart from the application code.
Execution Block Symbol	Symbol in the Development Environment that corresponds to an application subroutine where the name of the symbol is also the name of the subroutine.
Internal Variable	A storage mechanism that allows persistence during a Diameter transaction lifetime.
Start Symbol	Symbol in the Development Environment that marks the start of execution for the application.
Termination Symbol	Symbol in the Development Environment that represents the end of the application's execution.

### 1.4 WARNING on Copying and Pasting Code from this Guide

Please note that when copying and pasting code from Microsoft Word or other editors or document viewers into the Development Environment editor, some characters (typically punctuation characters like quotes) may end up having non-ASCII character codes, which leads to compilation errors. For instance:

Checking syntax...

Unrecognized character \x<...> in column <...> at script file line <...>.

Check Syntax found errors. Correct the syntax errors and try again

The solution is to delete the copied and pasted punctuation character and re-type it in the Development Environment editor.

## 2. DCA Activation and Deactivation

Activation and deactivation are standard procedures that enable the DSR applications in general and DCA in particular to be installed and uninstalled on a network.

### 2.1 DCA Activation

To start developing a new DCA, perform the following two steps:

1. Activate the DCA framework on the NO. See Procedure 5 in [1] CGBU\_018429 - DCA Framework and Application Activation and Deactivation for the instructions.

This step needs to be performed only once for a given network.

2. Activate the new DCA on the NO. See Procedure 6 in [1] CGBU\_018429 - DCA Framework and Application Activation and Deactivation for the instructions.

Perform this step once per DCA (similar to native DSR applications). Note, however, that only a limited number of DCAs (currently 5) can be simultaneously activated. Therefore, deactivate old DCAs to make room for new DCAs.

Figure 1 provides an overview of the activation-deactivation lifecycle.




Figure 1: DCA Activation- Deactivation Lifecycle

## 2.1.1 DCA Framework Activation

When the DCA framework is initialized, the **DCA Framework** folder with the **Configuration** file displays in the left side menu (Figure 2).




Figure 2: DCA Framework Menu

All measurements (Figure 3) and KPIs (Figure 4) associated with the DCA framework also display.

### Main Menu: Measurements -> Report

Figure 3: DCA Measurements

### Main Menu: Status & Manage -> KPIs


Name	Max	Min	Median	Average	Sum	Description
Ingress Message Rate	0.00	0.00	0.00	0.00	0.00	Average Ingress Message Rate (messages per second) of Diameter messages received by the DCA Application.
Runtime Errors Rate	0.00	0.00	0.00	0.00	0.00	Instant Runtime Error Rate (runtime errors per second during the last sampling interval)
Completed Transactions	0.00	0.00	0.00	0.00	0.00	Diameter transactions that a DCA App successfully relays
Transactions Discard Request	0.00	0.00	0.00	0.00	0.00	Allows the operator to determine how many transactions a DCA app relay terminates by discarding the request (by comparison with the Completed Transactions).

Figure 4: DCA KPIs

## 2.1.2 DCA Activation

When the new DCA is activated, the DCA subfolder with the name provided by the user during the activation procedure becomes visible in the left side menu (Figure 5). The DCA subfolder includes the

screens for enabling the business logic and provisioning configuration data. DCA becomes visible across DSR (ART, maintenance screen, etc.).



**Figure 5: DCA Menu**

### 2.1.3 Post-Activation DCA State

Following the activation procedure, DCA is in the disabled state. While in the disabled state, Diameter traffic is not delivered to DCA. First, enable DCA from the **SO Main Menu: Diameter > Maintenance > Applications**. Note that on this screen DCA is identified by the short name configured by the user during the DCA activation procedure.

Independently from the enabled/disabled state of DCA, at this stage no version of DCA has been provisioned yet. As a result, there is no version in Production and Trial state. As long as no Production or Trial version is available for a DA-MP to run, the DCA operational status is **Unavailable** (see **SO Main Menu: Diameter > Maintenance > Applications**).

The behavior of DCA while in the **Unavailable** operational state (provided DCA has been enabled) is configurable from the **SO Main Menu: DCA Framework > <DCA Name> > System Options** (see Section 9.4); possible options are dropping the Diameter request, forwarding the Diameter request, or returning a Diameter answer with a configurable error code.

From this point on the user can provision the configuration and business logic for DCA.

## 2.2 DCA Deactivation

The deactivation procedures enable DCA and, respectively, the DCA framework to be removed from a given network.

### 2.2.1 DCA De-Activation

The deactivation of DCA is not allowed as long as versions of the respective DCA are still in Production and/or a Trial state (see Chapter 4).

Following deactivation, the DCA GUI folder under the DCA Framework menu item disappears. DCA is deregistered from the ART; its KPIs and measurements do not display or report any longer.

### 2.2.2 DCA Framework De-Activation

DCA framework deactivation is not allowed as long as at least one DCA is activated in the network.

Following deactivation, the DCA framework GUI folder disappears from the left-hand GUI menu.

## 3. DCA Provisioning – The Blacklist DCA

This section provisions the configuration data and business logic for a simple DCA.

### 3.1 The Blacklist DCA

The Blacklist DCA checks the Origin-Host AVP of incoming Diameter requests and verifies whether it is blacklisted or not. In case the Origin-Host is blacklisted, the Diameter request is dropped, otherwise, the Diameter request is forwarded unchanged.

### 3.2 Prerequisites

The DCA framework must have been previously activated as described in [1] CGBU\_018429 - DCA Framework and Application Activation and Deactivation. Also, a DCA with the name Blacklist is activated as described in [1] CGBU\_018429 - DCA Framework and Application Activation and Deactivation.

The Blacklist DCA has to be enabled on all the DA-MPs in the network from the **SO Main Menu: Diameter > Maintenance > Applications**.

An ART rule is added that enables Diameter messages to be delivered to the Blacklist DCA.

### 3.3 The Process

The following step must be followed to provision the Blacklist DCA:

**Step 1:** Configure the general options and behavior of the Blacklist DCA.

**Step 2:** Create a new development version of the Blacklist DCA.

**Step 3:** Define the structure of tables to store the Blacklist configuration data.

**Step 4:** Provision the Blacklist configuration data.

**Step 5:** Provision the Blacklist business logic – essentially a Perl script.

**Step 6:** Render the Flow Control Chart based on the Perl script. Save and perform syntax checks.

**Step 7:** Test the Blacklist DCA: configure the Trial DA-MPs and promote Blacklist to Trial state.

**Step 8:** Compile Blacklist, promote Blacklist to Production state.

#### 3.3.1 Step 1: Configure DCA General Options and Behavior

At this stage, there is no version available for the Blacklist DCA. As a result, DCA is in the **Unavailable** operational state. No traffic is forwarded to the Blacklist DCA and, for outside observers, DCA behaves as specified in the **SO Main Menu: DCA Framework > <DCA Name> > System Options, Application unavailable configuration** section (see also Section 9.4).

The **Run-time error configuration** section of the same screen defines the behavior of DCA in case a runtime error occurs during the execution of the event handlers.


Finally, the DCA programmer must ensure the names specified on the **NO Main Menu: DCA Framework > <DCA Name> > General Options** (see Section 9.2.3) for the Diameter request and answer event handlers (Perl subroutines) are consistently used in the Perl script.

For Blacklist in particular, **Perl Subroutine for Diameter Answer** is left empty because there is no event handler defined to process the Diameter answers.

#### 3.3.2 Step 2: Create New Development Application Version

Go to the **NO Main Menu: DCA Framework > <DCA Name> > Application Control** and click **Create New Development** (see Figure 6). The Create New Development screen displays. Specify a name for the newly created Blacklist version and optionally provide comments (for example, author name, brief description of the business logic, etc.). Figure 7 shows the newly created version.


Main Menu: DCA Framework -&gt; Test DCA Application -&gt; Application Control



The screenshot shows a table with columns: Version Name, Status, Comments, Creation Time, Production Time, Flowchart Checksum, and Schema Checksum. Below the table are several buttons: Config Tables and Data, Development Environment, SBR DB Name Mapping, Create New Development (which is circled in red), Copy to New Development, Delete, Make Development, Make Trial, and Make Production. To the right of the table is a sidebar with Import and Export options for Business Logic and A Level Config Data.

Figure 6: Create a New Application Version

Main Menu: DCA Framework -&gt; Test DCA Application -&gt; Application Control



The screenshot shows the same table as Figure 6, but the 'BlackList' row is highlighted with a red line. The 'Status' column for 'BlackList' shows 'Development'. The rest of the interface is identical to Figure 6.

Figure 7: New Application Version Created

### 3.3.3 Step 3: Define the Configuration Data Structure

Select the newly created development application version on the Application Control screen and click **Config Tables and Data**. The Tables screen (Figure 8) displays. Click **Insert** on the Tables screen and create a new configuration table for provisioning the blacklist. The Blacklist DCA configuration table contains only one field: OriginHost, which is of type DiameterIdentity, see Figure 8.

Main Menu: DCA Framework -> Test DCA Application -> Application Control -> Blacklist -> Tables -> [Insert]

Adding a new table		
Field	Value	Description
Table Name	BlackList	Unique name of the Table. [Default = n/a, Range = A 32-character string. Valid characters are alphanumeric and underscore. Must contain at least one alpha and must not start with a digit.]
Description		Optional Description. [Default = n/a, Range = A 255 character string].
Single Row	<input type="checkbox"/>	Indicates if the table must have one single row. [Default=Unchecked, Range= Checked, Unchecked].
Level	<input checked="" type="radio"/> NO <input type="radio"/> SO	Configuration level of the table (NO or SO). [Default=NO, Range=NO, SO].
<b>Table Fields *</b>		
Field Name	OriginHost	Unique name of the Table Field [Default = n/a, Range = A 32-character string. Valid characters are alphanumeric and underscore. Must contain at least one alpha and must not start with a digit.]
Description		Optional description. [Default = n/a, Range = A 255 character string].
Unique	<input type="checkbox"/>	Indicates if the table field must be unique. [Default=Unchecked, Range=Checked, Unchecked].
Mandatory	<input type="checkbox"/>	Indicates if the table field must be mandatory. [Default=Unchecked, Range=Checked, Unchecked].
Data Type	DiameterIdentity	Data Type. [Default=n/a, Range= Integer, Float, UTF8String, OctetString, IP Address, DiameterURI, DiameterIdentity, Enumerated, Boolean]. <ul style="list-style-type: none"> <li>• Integer: Unsigned64/Signed64</li> <li>• Float: [+/-]number[.number][eE][+/-]number, for example 12.3 or 1.23e+1</li> <li>• UTF8String</li> <li>• OctetString: hexadecimal value prefixed with 0x</li> <li>• IP Address: IPv4 (decimal numbers separated by a period) /IPv6 (RFC4291, section 2.2; form 1 and 2 are supported)</li> <li>• DiameterURI: "aaa://" FQDN [ port ] [ transport ]  protocol "aaa://" FQDN [ port ] [ transport ]  protocol, see RFC6733</li> <li>• DiameterIdentity: FQDN or Realm, see RFC6733</li> <li>• Enumerated: Comma separated list of values, which can be separate items (a,b,c) or in form of: (a:1,b:2,c:3).</li> <li>• Boolean: true/false</li> </ul>
Default Value		Default Value. [Default=n/a, Range= FQDN or Realm, see RFC6733].
		<input type="button" value="Remove"/> <input type="button" value="Add"/>
<input type="button" value="Ok"/> <input type="button" value="Apply"/> <input type="button" value="Cancel"/>		

Figure 8: Create a New Database

**Note:** In this example, the configuration table is defined at the NO level. That means the configuration table is replicated to all the DA-MPs in the network.

Alternatively, a configuration table may be defined at the SO level. That means, while its structure is defined across the entire NO, its content is replicated only to the DA-MPs in each individual SO. In this way distinct SOs may use different configuration data (see Section 9.3.5).

### 3.3.4 Step 4: Provision the Configuration Data

Once the structure of the Blacklist table is defined, the table displays on the Tables screen. Select it and click **Provision Table**. The Provision Table View screen displays (Figure 9). Click **Insert** on the Provision Table View screen and insert all the Blacklisted Origin-Hosts to the table one by one (Figure 10).

**Main Menu: DCA Framework -> DCA Test Application -> Application Control -> BlackList -> Provision Table**

Table: BlackList

OriginHost
------------

Insert Edit Delete Delete All Back

Figure 9: Provision Table BlackList

**Main Menu: DCA Framework -> DCA Test Application -> Application Control -> BlackList -> Provision Table ->[Insert]**

Adding a new entry

Table: BlackList

Field	Value	Description
OriginHost	<input type="text"/>	

Ok Apply Cancel

Figure 10: Insert a New Data Row to the BlackList Table

**Main Menu: DCA Framework -> DCA Test Application -> Application Control -> BlackList -> Provision Table**

Table: BlackList

OriginHost
mme1.test.com
mme2.test.com
mme3.test.com
mme4.test.com
mme5.test.com

Insert Edit Delete Delete All Back

Figure 11: Provision DCA DB Tables

### 3.3.5 Step 5: Provision the Business Logic

Go back to the Application Control screen, select the application version, and click **Development Environment**.

In the development environment, you can edit, save, check syntax, and compile DCA Perl code, which defines the business logic DCA implements. An interactive Flow Control Chart is also rendered based on DCA Perl script. The Flow Control Chart provides an overview of the control flow within DCA and is useful in following the asynchronous calls and indicating the terminating actions (forward, drop, or return answer). See Chapter 10 for more details on Development Environment.

The development environment of the Blacklist DCA is illustrated in Figure 12.




Figure 12: The Blacklist DCA Development Environment

First, the DCA programmer has to write in the right-hand panel the Perl code illustrated Figure 13. The left-hand panel containing the flowchart is empty until the flowchart is rendered in Step 6.

```

sub process_request {
    my $param = shift;
    my $msg = diameter::Param::message($param) ;
    die "Missing Diameter message" unless defined ($msg);
    my $originHost = diameter::Message::getAvpValue($msg, "Origin-Host");
    die "Missing Origin-Host" unless defined($originHost);
    if (isBlacklisted ($originHost)) {
        dca::action::drop();
    } else {
        dca::action::forward();
    }
}
sub isBlacklisted {
    my $originHost = shift;
    my $blacklist = $dca::appConfig{"BlackList"};
    my $i = 0;
    while ($i <= $#{$blacklist}) {
        return 1 if $blacklist->[$i]{"OriginHost"} eq $originHost;
        $i++;
    }
    return 0;
}

```

Figure 13: Blacklist Perl Code

The Perl script (see Figure 13) makes use of the `getAvpValue` function to read the value of an AVP. The `getAvpValue` function is part of the EDL API, which is described in Section 11.1.2. It also uses the

drop and forward functions to discard and respectively forward the Diameter request. The drop function is part of the basic routing API, which is described in Section 11.4.

### 3.3.5.1 Where is the Perl Script Being Executed?

Although the Perl script is edited using the NO GUI, the Perl script is replicated to and eventually executed on the DA-MPs. In other words, there is no possibility of making the Perl script process traffic other than running it on the DA-MPs.

### 3.3.5.2 How Do the Event Handlers Get Invoked?

The business logic of DCA consists of a collection of event handlers, which are invoked when a Diameter message is delivered to the respective DCA. DCA may, therefore, define one event handler for Diameter requests and one event handler for Diameter answers. Subsequent sections introduce another category of event handlers, related to asynchronous database queries, but let's stick to the Blacklist DCA for now. Blacklist defines only one event handler: `process_request`. Unlike `isBlacklisted`, which is a standard Perl subroutine invoked from `process_request`, `process_request` itself is not explicitly invoked from anywhere in the Perl script. The event handlers are explicitly invoked by the Perl running environment of the DCA framework. Their names are configured in the **NO Main Menu: DCA Framework > <Application Name> > General Options** screen and by default these names are `process_request` and `process_answer`. These names may be changed, but one needs to make sure that the configured event handler names are consistent with the names used in the Perl script. Also, the event handler names are left empty if there is no corresponding event handler defined in the Perl script (see Figure 14).

Main Menu: DCA Framework ->Test DCA Application -> General Options

DCA Application General Options		
Field	Value	Description
Perl Subroutine for Diameter Request	<input type="text" value="process_request"/> *	The name of the Perl subroutine to be invoked when a Diameter request is received. [Default = <code>process_request</code> . Range = A 255 character string Valid characters are alphanumeric and underscore. Must contain at least one alpha and must not start with a digit.]
Perl Subroutine for Diameter Answer	<input type="text"/>	The name of the Perl subroutine to be invoked when a Diameter answer is received. [Default = <code>process_answer</code> . Range = A 255 character string Valid characters are alphanumeric and underscore. Must contain at least one alpha and must not start with a digit.]
State TTL	<input type="text" value="120"/>	The TTL of the application state data stored in the U-SBR by the DCA App, in seconds. [Default = 120]

Figure 14: Event Handler Subroutine Name Configuration

### 3.3.5.3 How Does DCA Configuration Data Get Accessed?

The configuration data of DCA are accessible to the Perl script through the `$dca::appConfig` variable, which is a complex variable representing a hash of arrays of hashes. One has to dereference it with exactly the same table names and field names specified when the structure of the configuration tables has been defined in step 3.3.3:

```
$dca::appConfig{"<table_name>"}->[<record_number>]{"<field_name>"}
```

in our case:

```
$dca::appConfig{"BlackList"}->[<record_number>]{"OriginHost"}
```

### 3.3.5.4 What is the Main Part Good For?

Blacklist has an empty Main Part. The Main Part of a Perl script is where the Perl interpreter starts executing instructions. In DCA, the main part is executed **only once** following the successfully compilation of the script.

The Main Part is typically used to perform whatever initializations are necessary (like for instance Custom MEAL objects, as we describe later on).

Another task that fits into the Main Part is DCA configuration data post-processing. We have seen in Section 3.3.5.3 that the Blacklist configuration data is accessible to the business logic (Perl script) as an array. Blacklist simply loops through the array when looking for each Origin-Host, but a more performance-aware version would certainly convert the array into a more performant data structure, like for instance a hash table keyed by the Origin-Host values.

Other DCAs may even need to use multiple keys (hence multiple hash tables) or compound keys; the Main Part is the right place to perform this kind of structural optimizations on DCA configuration data.

### 3.3.6 Step 6: Render Flow Control Chart, Save Script, Check Syntax

After editing the script, while in the Development state, the following actions are possible (see Figure 15):

- **Render Chart** (to generate the flowchart from the Perl code);
- **Save** (to save the Perl code and the flowchart);
- **Check Syntax** (to check syntax of Perl script).




Figure 15: Development Environment Buttons

The **Render Chart** action generates a flowchart based on the Perl code. Note that the flowchart has a Perl subroutine granularity and not a Perl instruction granularity. The flowchart's main purposes are: (i) to describe how the callback subroutines are linked to the event handlers (Diameter message handlers or other callback subroutines) that registers them and (ii) to indicate the terminating actions (drop, forward or return answer).

The flowchart does not illustrate on which condition a Perl subroutine is invoked (for example, if conditions) or how many times a Perl subroutine is invoked (for example, loop conditions). Also, the

**Render Chart** action is explicitly triggered by clicking the corresponding button after each modification of the Perl script.

**Save** allows the flowchart and Perl code to be saved, while the DCA version is in Development or Trial state.

**Check Syntax** becomes enabled once the **Save** action has been completed, while the DCA version is in Development or Trial state. It performs a syntax check on the Perl code and displays the errors if the syntax check fails.

### 3.3.7 Step 7: Test the DCA Version

Having the configuration data and business logic provisioned, it is now time to test the Blacklist DCA.


The DCA version is tested by promoting it to the Trial state, which automatically results in running it on the dedicated Trial DA-MPs.

The first step is, therefore, to configure the Trial DA-MPs, which can be done from the Trial MPs Assignment screen (see Figure 16 and Section 9.2.4).

The Trial DA-MPs assignment is configured per DCA, that is, it needs not be repeated for each DCA version.

Note also that our network contains only one DA-MP, which is also a Trial DA-MP. However, in a real life deployment, there would typically be a few Trial DA-MPs and a number of non-Trial DA-MPs.

**Main Menu: DCA Framework -> Test DCA Application -> Trial MPs assignment**



**Figure 16: Trial MP Assignment**

Next, on the Application Control screen, promote the DCA version from Development to Trial state by selecting it and clicking **Make Trial**.

While in Trial state, the DCA version can be: modified, saved, have the syntax checked and, in addition to the Development state, it can also be compiled (by clicking **Compile**, see Figure 15), as further described in Chapter 4. During each new cycle starting with the first Perl code modification and lasting until the next successful compilation (with an arbitrarily number of modifications, save and syntax check actions taking place during this time), the Trial DA-MPs execute the previously successfully compiled Perl script of the respective DCA version.

If successfully compiled, the Blacklist DCA on the Trial DA-MP switches into the operational state Available (see the **SO Main Menu: Diameter > Maintenance > Applications** screen). On the non-Trial DA-MPs, the DCA operational state remains **Unavailable** because there is no DCA version in Production state at this moment.

### 3.3.8 Step 8: Promote the DCA Version to Production State

A successfully compiled Trial DCA version can be promoted to the Production state. For this purpose, on the Application Control screen, select the DCA version and click **Make Production**.

At this stage the only DCA version available so far is in Production state. All non-Trial DA-MPs start running it and on these DA-MPs, the DCA operational state becomes **Available**. Because there is no DCA version in the Trial state, the Trial DA-MPs run the Production version as well.

Please note that our network is a very particular case that contains one single DA-MP, which is configured as a Trial DA-MP. This means that the Production version is executed on only this DA-MP if and only if no Trial version exists. As soon as a (new) Development version is promoted to the Trial state, the Trial DA-MP stops executing the Production version and starts executing the (new) Trial version.

While in Production state, the business logic of the DCA version cannot be changed anymore. It is only the configuration data that can be updated.

We have achieved our initial objective of running the Blacklist DCA in our network. From this point on a number of alternatives are possible:

- Demote the DCA version from Production state back to Development to fix bugs, re- test and promote back to Production state.
- Copy the DCA version into a new version with the purpose to improve its business logic (in terms of efficiency, functionality, or both) and eventually promote the newer version to Production state.
- Export the DCA version from the current network and import it onto another network.

We are touching on the DCA lifecycle management topic, which is described in more detail in the next chapter.

#### 4. DCA Lifecycle

The DCA lifecycle enables the DCA programmer to manage the lifecycle of a DCA.

So far we have developed one single DCA version, and we tested it and promoted it to the Production state. The state transitions are illustrated in Figure 17.





Figure 17: Transitions from Development to Production State

In a real life deployment, DCA may need to be continuously enhanced both in terms of efficiency as well as features. A typical approach would be to clone the DCA version currently in Production state to a new version in Development state, work on the new version (while the old version is processing the Diameter traffic), test the new version and eventually replace the older version in Production state with the newer one. This process is illustrated by the transition path 7 > 3 > 5b > 9 in Figure 18.



**Figure 18: Creating a New DCA Version**

The DCA lifecycle management is done by navigating to the **Main Menu: DCA Framework > <DCA Name> > Application Control** screen.

Each DCA version can be in one of the following states:


- **Development** (initial state)
  - There are zero or more Development versions in the system.
  - Development version is not executed on any MP.
  - Configuration schema (databases), configuration data, flowchart may be updated.
  - A new version in Development state is created in the system when:
    - **Create New Development** is clicked, see Section 9.2.5. In this case, the version has an empty flowchart, empty configuration schema, and empty configuration data.
    - Importing the business logic (with or without configuration data), see Section 9.2.9. In this case the flowchart and the configuration schema (databases) is copied from the imported version. Optionally, configuration data may be imported along with the business logic as well.
    - Copying a new Development version from an existing version in the system, see Section 9.2.7. In this case, the business logic and the configuration data of the selected version are copied into the new version.
- **Trial**
  - There are zero or one Trial versions in the system.
  - Trial version is executed on the DA-MPs assigned to run the Trial version
  - If no Trial version exists, then the Trial MPs runs the Production version (see Figure 19).
  - Configuration schema (databases), configuration data, flowchart may be updated.
- **Production**
  - There is zero or one Production version in the system.
  - When no Production version exists in the system, the operational state of DCA on MPs running the Production version is set to **Unavailable** (Main Menu: Diameter > Maintenance >

**Applications).** This may happen if the Production version is rolled back to the Development state or deleted.

- Is executed:
  - On all the DA-MPs, if no Trial version exists, or
  - On all the DA-MPs except the DA-MPs assigned to run the Trial version, if a Trial version exists (see Figure 19).
- Configuration schema (databases) & Flowchart are read-only.
- Configuration data may be updated.

• **Archived**

- There are zero or more Archived versions in the system.
- Archived versions are the application versions that have previously been in the Production state. They serve as backups for bringing the system back to a previous known state with minimum service interruption.
- Archived version is not executed on any MP.
- Configuration schema (databases), Configuration Data and Flowchart are read-only, but can be exported and copied into a new version.



**Figure 19: Assignment of the Version to a DA-MP**

The following transitions are possible for a given DCA version:

- Development > Trial (only if syntax was successfully checked and no other version is in Trial state)
- Trial > Production (only if the code/flow control chart was successfully compiled and no other version is in Production state)
- Production > Archived (automatic transition when a new version is promoted to Production)

- Trial > Development
- Production > Development (DCA operational state becomes **Unavailable**)
- Archived > Development
- Archived > Trial
- Archived > Production

## 5. Developing Stateful DCA

The Blacklist DCA introduced in Chapter 3 was a stateless Diameter application because it was processing each Diameter message individually without maintaining any state between a Diameter request and its corresponding answer (Diameter transaction state) or across Diameter transactions (for example, Diameter session state) or across Diameter sessions (for example, user state).

DCA may need to store state:

1. Diameter transaction state – for instance collect some information from the Diameter request and use that information when processing the Diameter answer.

This task can be addressed in two ways:

- a. Using the Diameter transaction context variables API documented in Section 11.2.2.
- b. Developers familiar with the Internal Variables from the Mediation feature may use Internal Variables for this purpose, as described in Section 11.2.1. However, Internal Variables involve a configuration overhead and therefore unless there is a strong argument in favor of using them (for example, they need to be set or read from Mediation rules) the Diameter transaction context variables, being a purely programming interface, are preferable

2. Diameter session or user state – for instance collect information across multiple Diameter transactions in the same session or user information across multiple Diameter sessions.

This task can be addressed using the Universal Session Binding Repository (U-SBR) and is described in Section 11.7.

## 6. A Stateful DCA Using the U-SBR Infrastructure

In Chapter 3 we developed a stateless DCA. Chapter 5 introduces the mechanisms available in DCA to develop stateful DCA.

This chapter describes the additional configuration steps to perform, and introduces the API available to develop a stateful DCA that uses the U-SBR (Universal Session Binding Repository). The U-SBR provides a generic interface to the I-SBR (Independent Session Binding Repository), which implements a scalable, distributed, and persistent database infrastructure, which DCA and other Oracle applications may use.

### 6.1 The CountULR DCA

The CountULR DCA maintains a per-user count of ULR messages and deletes it when a CLR message from the respective user is received. The user is identified based on the content of the User-Name AVP in the incoming Diameter requests.

### 6.2 Prerequisites

The DCA framework must have been previously activated as described in [1] CGBU\_018429 - DCA Framework and Application Activation and Deactivation. Also, a DCA with the name CountULR is activated as described in [1] CGBU\_018429 - DCA Framework and Application Activation and Deactivation.

The CountULR DCA has to be enabled on all the DA-MPs in the network from the **SO Main Menu: Diameter > Maintenance > Applications**.

An ART rule is added that enables ULR and CLR Diameter requests to be delivered to the CountULR DCA.

### 6.3 The Process

The following steps must be followed to provision the CountULR DCA:

Business Logic and Configuration Data Provisioning	U-SBR DB Configuration
<b>Step 1:</b> Configure the general options and behavior of the CountULR DCA.	<b>Step A:</b> Configure one or more U-SBR DBs (as required by DCA business logic).
<b>Step 2:</b> Create a new development version of the CountULR DCA.	
<b>Step 3:</b> Define the structure of tables to store the CountULR configuration data.	<b>Step B:</b> Configure a logical-to-physical U-SBR DB mapping
<b>Step 4:</b> Provision the CountULR configuration data.	
<b>Step 5:</b> Provision the CountULR business logic – essentially a Perl script.	
<b>Step 6:</b> Render the Flow Control Chart based on the Perl script. Save and perform syntax checks.	
<b>Step 7:</b> Test the CountULR DCA: configure the Trial DA-MPs and promote CountULR to Trial state.	
<b>Step 8:</b> Compile CountULR, promote CountULR to Production state.	

Steps 1 to 8 are similar to those described in Chapter 3.

Steps A and B are required to create an U-SBR DB and allow the CountULR DCA to interact with it. U-SBR DB configuration is independent from DCA configuration, except that a relative ordering must be followed:

- Step A may be executed in any order relative to steps 1 and 2.
- Step B must follow step 2 because a logical-to-physical mapping is always associated with a DCA version.
- Step B may be executed in any order relative to steps 3 to 6;
- Step 7 must follow step B.

A valid execution sequence is steps 1, 2 > A > 3, 4, 5, 6 > B > 7, 8.

#### 6.3.1 Step 1: Configure DCA Global Options and Behavior

In addition to the considerations discussed in Section 3.3.1, for DCAs that use U-SBR, the following configuration options may need to be adjusted:

- On the **NO Main Menu: DCA Framework > <DCA Name> > General Options** (see Section 9.2.3):
  - Application State Data TTL, which defines the time interval after which the state data is considered expired and is deleted by the U-SBR audit mechanism. The lifetime of the state data is initialized to TTL when created and is then automatically extended with the TTL value each time the state data is updated. The lifetime of the state data depends on the business logic that DCA implements and as a rule of thumb, it is twice the expected validity period of the state data stored. For instance, if DCA is supposed to reject, under some specific circumstances, an user's Diameter requests for a certain time interval, then the double of this time interval would be a good value for the state data lifetime
  - Read-Only U-SBR Access as Guest, which may be used to control the access of DCA to U-SBR DBs owned by other DCAs. This option is not relevant to CountULR because CountULR exclusively uses the U-SBR DB owned by itself (see Section 6.3.3.5)

- It is recommended the state data size (consisting of the size of the lookup key and respectively the size of the state data itself) of any new DCA is kept below the default values configured on the **NO Main Menu: DCA Framework > Configuration** screen (see Section 9.2.1). If, for good reasons, DCA requires a larger lookup key or more data to store, then these limits are increased.
- Note that these limits apply globally to all active DCAs. As a result, decreasing these value may result in existing DCAs having their U-SBR queries rejected with a `dca::sbr::ResultCode::MaxStateSize` error, and is, therefore, not recommended.

### 6.3.2 Step 2: Create a New Development Version

See Section 3.3.2.

### 6.3.3 Step A: Configure the U-SBR DBs

Configuring a U-SBR DB must be preceded by configuring the underlying I-SBR topology:

- Configure the I-SBR topology
  - Step A.1:** Servers Configuration
  - Step A.2:** Server Groups Configuration
  - Step A.3:** Places Configuration
  - Step A.4:** Place Associations Configuration
  - Step A.5:** Resource Domains Configuration
- Configure the U-SBR DB
  - Step A.6:** U-SBR Database Configuration

The configuration of the I-SBR topology and SBR Databases is also described in more detail in [2] E58954-02, DSR Software Installation and Configuration Procedure.




Figure 20: SBR Topology Example

The CountULR DCA uses a simple I-SBR topology, illustrated in Figure 20.

The topology consists of a DA-MP (DCAMP1), which processes the Diameter messages; a SBR-MP (DCASBR1), which stores the U-SBR DB (USBRDB1); and a NO and a SO.

Next, we have:

- One server per each server group (DCAMP1 in MPSG and DCASBR1 in SBRSG1)
- One server group per resource domain (MPSG in DCARD1 and SBRSG1 in SBRRD1)
- Both resource domains are in the same place (Site1)
- The Place Association (DCAPA1) includes just one Place (Site1)

### 6.3.3.1 Step A.1: Servers Configuration

Servers are the processing units of the application with various roles within the application: Network OAM&P (NOAMP), System OAM (SOAM), and MP. For our case, we would need to configure two MPs – one for the DA-MP that processes the Diameter messages and one for the SBR-MP.

On the Servers screen, configure the SBR MP DCASBR1 with the MP Role and the DA-MP DCAMP1, see Figure 21.

Hostname	Role	System ID	Server Group	Network Element	Location	Place	Details
DCANO	Network OAM&P	DCANO	NOSG	NO		Site1	INTERNALXMI: 10.240.90.238 INTERNALIMI: 169.254.5.57
DCASO	System OAM	DCASO	SOSG	SOAM		Site1	INTERNALXMI: 10.240.90.242 INTERNALIMI: 169.254.5.50
DCAMP1	MP		MPSG	SOAM		Site1	INTERNALXMI: 10.240.90.191 INTERNALIMI: 169.254.5.49 More...
DCASBR1	MP		SBRSG1	SOAM		Site1	INTERNALXMI: 10.240.90.245 INTERNALIMI: 169.254.5.33
DCASBR2	MP			SOAM		Site1	INTERNALXMI: 10.240.90.244 INTERNALIMI: 169.254.5.32
DCASBR3	MP			SOAM		Site1	INTERNALXMI: 10.240.90.243 INTERNALIMI: 169.254.5.31

Figure 21: Servers Configuration

### 6.3.3.2 Step A.2: Server Group Configuration

The Server Groups allow the user to assign a function (DSR, SBR, etc.), parent relationships, and levels to a group of servers that share the same role, such as NOAMP, SOAM, and MP servers.

On the Server Group screen, configure the new SBR Server Group SBRSG1 that includes the DCASBR1 server and has SBR function, see Figure 22. Assign the Parent Relationship and Level C to a group of servers that share the SBR Role. Configure the DA-MP MPSG Server Group that includes DCAMP1 server and has the function of DSR.

Figure 22: Server Groups Configuration

### 6.3.3.3 Step A.3: Places Configuration

The Places allow building associations for groups of servers at a single geographic location. These places can then be grouped into place associations, which create relationships between one or more place.

On the Places screen configure a new place Site1. Set a unique instance name, a Place Type Site, and a group of server members belonging to the site. For our example, all available servers are in the same place, see Figure 23 and Figure 24.

A Place Type is always Site.

Figure 23: Places Configuration

Place Name	Type	Parent Place	Servers
Site1	Site		<input type="checkbox"/> DCANO <input type="checkbox"/> DCASO <input type="checkbox"/> DCAMP1 <input type="checkbox"/> DCASBR1 <input type="checkbox"/> DCASBR2 <input type="checkbox"/> DCASBR3

Figure 24: View Places

#### 6.3.3.4 Step A.4: Place Associations Configuration

The Place Association function allows you to create relationships between places. Places are groups of servers at a single geographic location.

On the Place Associations screen, create the new place association DCAPA1 that includes Site1. Select the Place Association Type Applications Region, see Figure 25 and Figure 26.

Always select Applications Region type for the DCAs and the SBR databases they use.

The Place Association in the SBR Databases configuration defines the scope of Database users. The database in the associated Place Association can only be accessed by the DA-MPs in the same Place Association.

Figure 25: Create Place Association

Place Association Name	Type	Places
DCAPA1	Applications Region	Site1

Figure 26: View Place Association

### 6.3.3.5 Step A.5: Resource Domain Configuration

The Resource Domains (RD) screen enables users to assign a set of Server Groups to a Resource Domain profile, which identified the database type.

On the Resource Domains screen configure the new resource domain SBRRD1. Assign the Server Group SBRSG1, select the Resource Domain Profile Session Binding Repository for the SBR database (see Figure 27 and Figure 29).

Field	Value	Description
Resource Domain Name *	SBRRD1	Unique identifier used to label a Resource Domain. [Default = n/a. Range = A 1-32-character string. Valid characters are alphanumeric and underscore.] [A value is required.]
Resource Domain Profile *	Session Binding Repository	The Profile of this Resource Domain [A value is required.]
Server Groups	<input type="checkbox"/> MPSG <input type="checkbox"/> NOSG <input checked="" type="checkbox"/> SBRSG1 <input type="checkbox"/> SBRSG2 <input type="checkbox"/> SOSG	Server Groups associated with this Resource Domain

Figure 27: SBR Resource Domain Configuration

On the Resource Domains screen, configure the new resource domain DCARD1. Assign a Server Group MPSG, select the Resource Domain Profile DCA MPs (see Figure 28 and Figure 29).

Field	Value	Description
Resource Domain Name *	DCARD1	Unique identifier used to label a Resource Domain. [Default = n/a. Range = A 1-32-character string. Valid characters are alphanumeric and underscore.] [A value is required.]
Resource Domain Profile *	DCA Application MPs	The Profile of this Resource Domain [A value is required.]
Server Groups	<input checked="" type="checkbox"/> MPSG <input type="checkbox"/> NOSG <input type="checkbox"/> SBRSG1 <input type="checkbox"/> SBRSG2 <input type="checkbox"/> SOSG	Server Groups associated with this Resource Domain

Figure 28: DCA MP Resource Domain Configuration

Resource Domain Name	Profile	Server Groups
DCARD1	DCA Application MPs	<input checked="" type="checkbox"/> MPSG
SBRRD1	Session Binding Repository	<input checked="" type="checkbox"/> SBRSG1

Figure 29: View Resource Domain Configuration

### 6.3.3.6 Step A.6: SBR Database Configuration

On the SBR Databases screen, create the new database USBR1 (see Figure 30).

Select Database Type: Universal, Resource Domain: SBRRD1, Number of Service Groups: 1, Place Association: DCAPA1, Owner Application: CountULR, as illustrated in Figure 31.

Main Menu: SBR -> Configuration -> SBR Databases -> [Insert]

Field	Value	Description
Database Name *	<input type="text"/>	A name that uniquely identifies the SBR Database. [Default = n/a; Range = A 32-character string. Valid characters are alphanumeric and underscore. Must contain at least one alpha and must not start with a digit.] [A value is required.]
Database Type *	<input type="button" value="- Select -"/>	The type of SBR Database. Select 'Binding' for a Policy Binding database, or 'Session' for a Policy DRA or Online Charging DRA Session database or Universal for Universal SBR database. [Default = n/a; Range = 'Binding' or 'Session' or 'Universal'] [A value is required.]
Resource Domain *	<input type="button" value="- Select -"/>	The Resource Domain that contains the SBR Server Groups configured for use by this database. Select the Resource Domain that will host this database. [Default = n/a; Range = Configured Resource Domains matching the selected Database Type that have not already been assigned to a Database] [A value is required.]
Number of Server Groups *	<input type="text"/>	The number of SBR Server Groups required to host this database. Enter or change the number of Server Groups necessary to support the desired capacity of the database. If the selected Resource Domain already contains Server Groups, the number of Server Groups in the Resource Domain is displayed in the field, but can be overridden as desired. [Default = n/a; Range = 1 to 8] [A value is required.]
Place Association *	<input type="button" value="- Select -"/>	The Place Association that contains the Places (Sites) that will use this database. Select the Place Association that is to use this SBR Database. [Default = n/a; Range = Configured Place Associations matching the selected Database Type that have not already been assigned to a Database] [A value is required.]
Owner Application	<input type="button" value="- Select -"/>	The name of application that owns the configured SBR DB. Select Owner Application that is the owner of the SBR Database if the Database Type is Universal. Otherwise the Owner Application is displayed automatically as 'PCA'. [Default = none; Range = None, PCA and configured DCA application names]

Ok    Apply    Cancel

Figure 30: Create SBR Database

Each U-SBR DB is assigned to an owner DCA. This is necessary for the U-SBR to support multiple DCAs (meaning, the owner DCA and an arbitrary number of guest DCAs) to query the same U-SBR DB. The owner DCA can perform all possible queries on the U-SBR DB. Guest DCAs, on the other hand, can restrict their access to read-only access to the U-SBR DB by checking the Read Only U-SBR Access as Guest option on the **Main Menu: DCA Framework > <DCA Name> > General Options** (see Section 9.2.3).

The U-SBR DB configured in a Place Association is only accessed by the DA-MPs in the same Place Association.

Database Name	Database Type	Resource Domain	Number of Server Groups	Place Association	Owner Application
USBR1	Universal	SBRD1	1	DCAPA1	First Dca Application

Figure 31: View SBR Database

From the **NO Main Menu: SBR > Maintenance > SBR Database Status** screen, prepare and enable the USBR1 database.

### 6.3.4 Step 3: Define the Configuration Data Schema

CountULR does not use any DCA configuration data.

### 6.3.5 Step 4: Provision the Configuration Data

CountULR does not use any DCA configuration data.

### 6.3.6 Step 5: Provision DCA Business Logic

The CountULR DCA implements the following business logic:

- When receiving a ULR message, extract the user name from the User-Name AVP and check if a state has been created for the respective user:
  - If the user name is not found, create a state that contains a counter set to 1.
  - If the user name already exists, read the existing state, increment the counter and write the state back to the U-SBR DB.
- When receiving a CLR message, extract the user name from the User-Name AVP and delete the state corresponding to the respective user, if it exists.

Figure 32 illustrates a typical call flow. CountULR uses three U-SBR API calls: createOrRead, concurrentUpdate and delete. The U-SBR API is described in Section 11.7.




Figure 32: CountULR Call Flow

The Perl code is illustrated in Figure 25.

```
use constant{
    # key types for our app - only NAI is currently used,
    # the others are for exemplification
    IMSI => 0,
    SESSION => 1,
    NAI => 2,
    IPv4 => 3,
    # command codes for S6 commands
    ULR_CMD => 316,
    CLR_CMD => 317,
};

# this function is called when receiving a diameter request message
sub process_request{
    # session state to be stored on the sbr
    # the session state stores:
    # - no of requests for this user-name
    # - no of success replies for this user-name
    # - no of error replies for this user-name
    my $sbr_state =
    {
        requests => 1                # only requests are currently counted
        #ok_replies => 0,
        #err_replies => 0
    };
}
```

```

# diameter message is the first parameter
my $param = shift;
# only one key type for this app: NAI
my $key_type = NAI;
# get the diameter message object
my $msg = diameter::Param::message($param);
if(!defined($msg)){
    die "Bad diameter message parameter.";
}

# try to get the the diameter command code from the diameter message
my $cmd = diameter::Message::commandCode($msg);
if(!defined($cmd)){
    die "No command code in diameter message.";
}

# get User-Name from the message
my $user = diameter::Message::getAvpValue($msg, "User-Name");
if(!defined($user)){
    # could not create $user
    die "Could not get the User-Name value from the message"
}

if(ULR_CMD == $cmd){
    # process Update-Location-Request
    # instantiate and send the "CreateOrRead" SBR stack event
    my $result = dca::sbr::sbrInstance("sbr")->createOrRead(
        $key_type,
        dca::sbr::KeyDataType::STRING, $user,
        dca::sbr::StateDataType::STRING, $sbr_state,
        "createOrReadCb");
    # check the "synchronous" error
    if(!defined($result)){
        # could not create the sbr request
        die "could not create the SBR request";
    }
}

elsif(CLR_CMD == $cmd){
    # process Cancel-Location-Request
    # instantiate and send the "Delete" SBR stack event
    my $result = dca::sbr::sbrInstance("sbr")->delete($key_type,
        dca::sbr::KeyDataType::STRING, $user,
        "deleteCb");
    # check the "synchronous" error
    if(!defined($result)){
        # could not create the sbr request
        die "could not create the SBR request";
    }
}
else{
    die "unknown diameter command received";
}

# this function is called when receiving a diameter answer message
sub process_answer{

```

```

}

# this function is called when receiving an DeleteStateResult
# answer from the SBR
sub deleteCb{
    my $sbr_code = dca::sbr::result()->code();
    if(!defined($sbr_code)){
        # could not get the result code of the SBR answer
        die "did not get the result code of SBR answer";
    }

    if(dca::sbr::ResultCode::RecNotFound == $sbr_code){
        die "could not find a record with the given key on the SBR";
    }
    elsif( dca::sbr::ResultCode::Ok != $sbr_code){
        die "SBR error: $sbr_code";
    }
}

# this function is called when receiving an CreateOrReadStateResult
# answer from the SBR
sub createOrReadCb
{
    my $sbr_code = dca::sbr::result()->code();
    # check the result code
    if(dca::sbr::ResultCode::RecExists == $sbr_code){
        my $sbr_state = dca::sbr::result()->data();

        # diameter message is the first parameter
        my $param = shift;
        # only one key type for this app: NAI
        my $key_type = NAI;
        # get the diameter message object
        my $msg = diameter::Param::message($param);
        if(!defined($msg)){
            die "Bad diameter message parameter.";
        }

        # get User-Name from the message
        my $user = diameter::Message::getAvpValue($msg, "User-Name");
        if(!defined($user)){
            # could not create $user
            die "Could not get the User-Name value from the message"
        }

        # record was already existing on the SBR; update it
        $sbr_state->{requests}++;
        my $result = dca::sbr::sbrInstance("sbr")->concurrentUpdate(
            $key_type,
            dca::sbr::KeyDataType::STRING, $user,
            dca::sbr::StateDataType::STRING, $sbr_state,
            "concurrentUpdateCb");
        # check the error
        if(!defined($result)){
            # could not create the sbr request
            die "could not create the SBR request";
        }
    }
}

```

```

        }
    }
    elsif( dca::sbr::ResultCode::Ok != $sbr_code) {
        die "SBR error: $sbr_code";
    }
}

# this function is called when receiving an ConcurrentUpdateStateResult
# answer from the SBR
sub concurrentUpdateCb{
    # use "result" API function to retrieve error code and data:
    my $sbr_code = dca::sbr::result()->code();

    # check the result code
    if(dca::sbr::ResultCode::RecObsoleted == $sbr_code){
        # record was already updated by another MP on the SBR;
        # try to update it once again
        my $sbr_state = dca::sbr::result()->data();
        # diameter message is the first parameter
        my $param = shift;
        # only one key type for this app: NAI
        my $key_type = NAI;
        # get the diameter message object
        my $msg = diameter::Param::message($param);
        if(!defined($msg)){
            die "Bad diameter message parameter.";
        }

        # get User-Name from the message
        my $user = diameter::Message::getAvpValue($msg, "User-Name");
        if(!defined($user)){
            # could not create $user
            die "Could not get the User-Name value from the message"
        }
        $sbr_state->{requests}++;
        my $result = dca::sbr::sbrInstance("sbr")->concurrentUpdate(
            $key_type,
            dca::sbr::KeyDataType::STRING, $user,
            dca::sbr::KeyDataType::STRING, $sbr_state,
            "concurrentUpdateCb");
        # check the error
        if(!defined($result)){
            # could not create the sbr request
            die "could not create the SBR request";
        }
    }
    elsif( dca::sbr::ResultCode::Ok != $sbr_code) {
        die "SBR error: $sbr_code";
    }
}
}

```

Figure 33: CountULR Perl Code

### 6.3.6.1 What Does a State Consist Of?

A state is essentially a mapping between a key and a value. What exactly the key and value are is completely under DCA control. The U-SBR does not attach any semantics to DCA state. In CountULR

the key is the user name extracted from the User-Name AVP and the Value is basically a counter that counts the total number of ULR messages.

Even though CountULR uses a single key (of type NAI), DCA may, in general, use multiple keys (IMSI, MSISDN, IP addresses, Diameter Session-ID, etc.).

DCA may distinguish between the different keys by declaring their Key Types. The Key Type helps avoid collisions like for instance between NAI key “fred” and IPv4 address key 66.72.65.64, or between IP source address key 1.2.3.4 and destination IP address key 1.2.3.4.

The value associated to a key is the value of a Perl variable. For CountULR, the value is a Perl hash table containing one key requests that store an integer representing the ULR counter. Perl complex data structures like hash tables and arrays are converted to JSON and stored in the U-SBR DB as strings. When retrieved from the U-SBR they are converted back to the original data structure. Scalar Perl variables, on the other hand, need not undergo a JSON conversion.

Finally, the data type of key and value need to be specified to one of the pre-configured data types:

- `dca::sbr::KeyDataType::BCD`, `dca::sbr::KeyDataType::UINT32`, `dca::sbr::KeyDataType::INT64`
- `dca::sbr::KeyDataType::STRING`, `dca::sbr::KeyDataType::IPv4`, `dca::sbr::KeyDataType::IPv6`
- `dca::sbr::StateDataType::BCD`, `dca::sbr::StateDataType::UINT32`, `dca::sbr::StateDataType::STRING`,  
`dca::sbr::StateDataType::IPv4`, `dca::sbr::StateDataType::IPv6`

This helps the U-SBR DB to optimize the way the Key-Value pair is stored and retrieved.

### 6.3.6.2 What are Asynchronous API Calls and Callbacks?

The `dca::sbr::sbrInstance("sbr") > createOrRead`, `dca::sbr::sbrInstance("sbr") > concurrentUpdate`, and `dca::sbr::sbrInstance("sbr") > delete` API functions initiate, each of them, an U-SBR DB query. They are **asynchronous** functions, in the sense that they do not wait until a response from the U-SBR is received. They construct the U-SBR DB query and return immediately, to allow the other Diameter messages to be processed. The query itself is sent after the event handler execution completes.

How can DCA learn about the outcome of the U-SBR DB query it just sent? It may be observed that all the U-SBR API functions can register, as the last parameter, the name of a **callback** subroutine. The callback subroutine is invoked by the DCA framework when the outcome of the corresponding U-SBR DB query is known. The outcome may be: (i) an error condition that prevented the U-SBR query to even be sent; (ii) the U-SBR DB response itself; or (iii) an error condition indicating that no response has been received within a certain timeout interval.

### 6.3.6.3 How is the U-SBR State Returned to the Perl Script?

In the callback subroutine the DCA programmer can use the `dca::sbr::result()` class to retrieve the error code and, if the query was successful, the result.

### 6.3.6.4 What is Concurrent in a concurrentUpdate?

Incrementing a counter in a distributed system is not as trivial an operation as it may seem because race conditions may occur between different threads, processes or hosts that attempt to increment the same counter at the same time.

In our case, such race condition may occur when ULR messages for the same user name are received at around the same time or in quick succession. This can obviously happen when the network contains multiple DA-MPs, but it can also happen in our simplified topology with one single DA-MP because there are always multiple Perl interpreters running simultaneously that execute the event handlers. There are therefore multiple CountULR execution instances, running in parallel, at any given time.

A CountULR execution instance is basically reading the counter value from the U-SBR DB record that corresponds to the user name, incrementing it and updating the record on the U-SBR, for example, a read-increment-update sequence. The trick is to check that the record a CountULR execution instance is trying to update is the same record that was previously read. If it is not the same, then one or more other CountULR execution instances have incremented the counter in the meantime and the operation needs to be repeated on the new counter value, otherwise the counter value is corrupted and the counter value is, in the end, less than it should be.

When the concurrentUpdate query detects that the U-SBR DB record has been updated, it automatically returns the new record so that an explicit new read operation is not needed.

This mechanism is called optimistic offline locking and is often encountered in transactional DBs. It is optimistic because the rate of the race conditions is expected to be relative low compared to total number of increment operations. It is offline because the race condition is resolved by re-trying the operation, rather than effectively locking the record. Figure 34 illustrates such a race and how the optimistic offline locking mechanism solves it. For simplicity, we show two competing DA-MPs, however, as already mentioned, it equally applies to one single DA-MP running multiple Perl interpreters.




Figure 34: A Counter Increment Race

### 6.3.7 Step 6: Render the Flow Control Chart

Render the Flow Control Chart based on the Perl script. Save the code and check the syntax.




Figure 35: Flow Control Chart

### 6.3.8 Step B: Logical to Physical U-SBR DB Name Mapping

Logical-to-physical U-SBR name mapping provides the glue between the Perl script and the U-SBR topology. It enables:

- The Perl script to remain unchanged across deployments (**Lab > Live, Oracle > Customer**) by using the same logical names for the U-SBR DBs, while the topology and names of the physical U-SBR DBs in each particular network may vary.
- The Perl script to remain unchanged across Place Associations inside the same deployment, because the names of physical U-SBR DBs are different in each Place Association. This situation is not apparent in our example, because we are using a network that consists of only one site.
- Different versions of the same DCA to use different logical names mapping to the same physical U-SBR DBs.
- Different versions of the same DCA to use the same logical names mapping to different physical U-SBR DBs, because the DB layout (number of U-SBR DBs or their scope site vs. global) has changed in newer versions.
- A DCA to map a logical U-SBR DB name to a physical U-SBR DBs of another DCA.

The logical-to-physical U-SBR DB mapping is configured per DCA version. In the Application Control screen, select a DCA version and click the **SBR DB Name Mapping**, see Figure 36.

Main Menu: DCA Framework ->CountULR -> Application Control




Figure 36: SBR DB Name Mapping

Assign the logical U-SBR name “sbr” to the physical U-SBR Name USBR1, see Figure 37.

The “sbr” name must be consistently used in the Perl script as a parameter to the sbrInstance() each time an U-SBR API function is invoked. As a result, the queries sent from the Perl script to “sbr” is delivered to the USBRDB1.

**Main Menu: DCA Framework -> CountULR -> Application Control -> Version1 -> SBR DB Name Mapping**

SBR Database Logical Name	SBR Database Physical Name
sbr	USBR1

**Insert** **Edit** **Delete**

**Figure 37: View SBR DB Name Mapping**

### 6.3.9 Step 7: Test the DCA Version

See Section 3.3.7.

### 6.3.10 Step 8: Promote the DCA Version to Production

See Section 3.3.8.

## 7. Monitoring DCA

This chapter provides a general description of Custom MEALs, templates and their purpose. The monitoring of the execution of DCA is possible using the Custom MEAL feature.

The Custom MEAL feature enables a DCA programmer to define and use measurements, KPIs, and events, on demand:

- Measurements are used to count specific events or amounts, as required by DCA business logic. Their historical values measured during specific time intervals and/or on specific hosts are available via reports;
- KPIs display real-time statistics of the measured events or amounts, like for instance average values;
- Events may be triggered automatically when the currently measured values exceed the configured thresholds.
- Alternatively, events may be triggered explicitly from DCA code.

The Custom MEAL feature hides most of the complexity of the underlying DSR objects that implement the measurements, KPIs, and events by defining a number of four templates, which are designed to implement specific tasks:

- The Counter template – is used to count events. The counter values are available only off-line through the Measurement Reports.
- The Rate template – is most typically used to calculate message rates. It generates KPIs, Measurement Reports and may be used to automatically raise alarms if the configured threshold values are exceeded.
- The Basic template – is used to measure averages or number of elements in a set (for example, to calculate average size of AVPs, messages or number of users registering/deregistering). It generates KPIs, Measurement Reports and may be used to automatically raise alarms if the configured threshold values are exceeded.

- The Event template – is used to explicitly raise/clear alarms or generate events from the Perl script when specific business logic conditions are detected.

Each of the templates is available in scalar and arrayed format.

We denote by "differentiation" the process of assigning a C-MEAL template instance to a DCA. We denote by "un-differentiation" the reverse process of removing a C-MEAL from a DCA and basically returning it to the pool of un-differentiated C-MEAL, from where it can be re-assigned to another (or even the same) DCA.

## 8. DCA Using Custom MEALs

Chapter 7 introduced the Custom MEAL (C-MEAL) templates and their applicability. This chapter describes a simple DCA that uses a Rate C-MEAL to monitor the rate of the incoming Diameter requests with just two lines of Perl code.

### 8.1 The Rate DCA

The Rate DCA differentiates a Rate C-MEAL, initializes it, and pegs it every time a Diameter request is received. The operator can monitor the incoming message rate in real time (KPI), check the history of the measured value (measurement report) and get notified when the configured thresholds are exceeded (alarm).

### 8.2 Prerequisites

The DCA framework must have been previously activated as described in [1] CGBU\_018429 - DCA Framework and Application Activation and Deactivation. Also, a DCA with the name "Rate" is activated as described in [1] CGBU\_018429 - DCA Framework and Application Activation and Deactivation.

The Rate DCA has to be enabled on all the DA-MPs in the network from the **SO Main Menu: Diameter > Maintenance > Applications**.

An ART rule is added that enables Diameter requests to be delivered to the Rate DCA.

### 8.3 The Process

The following steps must be followed to provision the Rate DCA:

Business Logic and Configuration Data Provisioning	Custom MEAL Configuration
<p><b>Step 1:</b> Configure the general options and behavior of the Rate DCA.</p> <p><b>Step 2:</b> Create a new development version of the Rate DCA.</p> <p><b>Step 3:</b> Define the structure of tables to store the Rate configuration data.</p> <p><b>Step 4:</b> Provision the Rate configuration data.</p> <p><b>Step 5:</b> Provision the Rate business logic – essentially a Perl script.</p> <p><b>Step 6:</b> Render the Flow Control Chart based on the Perl script. Save and perform syntax checks.</p> <p><b>Step 7:</b> Test the Rate DCA: configure the Trial DA-MPs and promote Rate to Trial state.</p> <p><b>Step 8:</b> Compile Rate, promote Rate to Production state.</p>	<p><b>Step I:</b> Differentiate a scalar Rate C-MEAL.</p>

Steps 1 to 8 are similar to those described in Chapter 3. Step I is required to assign a C-MEAL to the Rate DCA, which can be then be used via the C-MEAL API, which is described in Section 11.6.

Step I may be executed in any order relative to steps 1 to 5.

### 8.3.1 Step I: Differentiate a C-MEAL

C-MEALs are differentiated from the **Main Menu: DCA Framework > Rate > Custom MEALs** screen, by clicking **Insert**. For the Rate DCA in particular, TestRate, a scalar rate C-MEAL, is differentiated (see Figure 38). TestRate raises an alarm when the configured thresholds are exceeded. The threshold values represent percentages from the 100% Threshold Value, which in our example is exactly 100.

Main Menu: DCA Framework -> Rate -> Custom MEALs													Tue Jul 12
													Filter*
Name	Template Type	Measurement Type	State	100% Threshold Value	Alarm Autoclear Interval	Alarm Throttling Interval	Threshold Min Clear	Threshold Min Set	Threshold Maj Clear	Threshold Maj Set	Threshold Crit Clear	Threshold Crit Set	
TestRate	Rate	Scalar	Completed	100	~	~	65	70	75	80	85	90	

Pause updates

Figure 38: TestRate Differentiation

### 8.3.2 Step 1: Configure DCA General Options and Behavior

See Section 3.3.1.

### 8.3.3 Step 2: Create a New Development Version

See Section 3.3.2.

### 8.3.4 Step 3: Define the Configuration Data Schema

Rate does not need any DCA configuration data.

### 8.3.5 Step 4: Provision the Configuration Data

Rate does not need any DCA configuration data.

### 8.3.6 Step 5: Provision DCA Business Logic

The Rate DCA implements a simple business logic that consists of pegging the Rate C-MEAL each time a Diameter request is received.

The Perl code is illustrated in Figure 39. Note that the C-MEAL name used to initialize the Perl object must be the same as the one configured for the C-MEAL during differentiation (TestRate).

```

my $rateObject = new dca::meal::rate("TestRate");
die "Failed to bind to the rate template" unless $rateObject;
    # force *compilation* error if
    # rateObject initialization fails

sub process_request{
    die "Pegging 'TestRate' Failed" unless $rateObject->peg();
        # a *runtime* error will be generated in the unlikely
        # event peg() fails
}

# And that's it! Alarms will be automatically raised when the configured
# thresholds are exceeded

```

Figure 39: The Rate DCA Code

### 8.3.7 Step 6: Render the Flow Control Chart

The same process described in Section 3.3.6 is followed.

### 8.3.8 Step 7: Test the DCA Version

The same process described in Section 3.3.7 is followed.

At this stage, we can finally monitor the Rate DCA in the following ways:

- The DCA:Rate KPI group includes all the KPIs that belong to the Rate DCA. On the **Main Menu: Status & Manage > KPIs** the DCA:Rate group is included in the KPI filter criteria (see Figure 40). As a result, the exponentially smoothed average of the ingress rate (TestRate) is displayed in real time (see Figure 41).
- The history of the measured values can be accessed from the **Main Menu: Measurements > Report** screen. The DCA:Rate measurements group includes all the measurements that belong to the Rate DCA and is included in the filtering criteria (see Figure 42). As a result, the history of the TestRate measurements is displayed (see Figure 43).
- An alarm with the corresponding severity is raised when the respective threshold values are exceeded. This can be seen for instance in Figure 41. The alarm details can be accessed from **Main Menu: Alarms & Events**. Figure 44 illustrates the alarm history, obtained by progressively increasing the message rate above the critical set threshold and then progressively reducing it below the minor clear threshold.

Main Menu: Status & Manage -> KPIs [Group: 'Server']

Tue Jul 12 08:39:14 2016 EDT

Name	Value	Desc
CPU	0.61 %	Percentage utilization of all processors on the system
R&M	4.36 %	Percentage utilization of physical memory
Swap	0.00 %	Percentage utilization of swap space on the system
Disk	0.21 %	Percentage utilization of disk space on the system
ShMem	0.03 %	Percentage utilization of shared memory on the system
Uptime	4.95 days	The total amount of time(days HH:MM:SS) the system has been up

Filter Options

Group

Go Reset

DCA:Rate

-Groups-

ComAgent

DCA Framework

DCA:Rate

SBR

Server

USBR

-Place Associations-

Figure 40: Filter DCA:Rate KPIs

Main Menu: Status & Manage -> KPIs [Group: 'DCA:Rate']

Tue Jul 12 08:51:03 2016 EDT

Entire-Network

Non Arrayed

Name	Average	Max	Min	Median	Sum	Desc
TestRate	78.71	78.71	78.71	78.71	78.71	test rate kpi

The ingress rate has increased above the major threshold set value (70)

33355 test rate alarm  
32351 HP disk problem

0 2 3 0

Figure 41: Display TestRate KPI

## Main Menu: Measurements -&gt; Report (Filtered)

Filter Tasks

MPSG HPC06MP1

Non-Arrayed

Filter

Measurement: DCA:Rate Fifteen Minute Reset

Scope: Network Element MPSG - Resource Domain - - Place - - Place Association - Reset

Column Filter: None Like Reset

Time Range: 1 Hours Ending 2016 Jul 12 09 00 Reset

Go

Figure 42: Filter DCA:Rate Measurements

## Main Menu: Measurements -> Report (Filtered)

Filter\* Tasks

MPSG HPC06MP1

Non-Arrayed

Timestamp	Percent Complete	TestRateAvg	TestRateCnt	TestRatePeak
2016-07-12 08:00:00 EDT	100	0.000000	0	0
2016-07-12 08:15:00 EDT	100	12.135344	10923	111
2016-07-12 08:30:00 EDT	100	99.995589	89998	120
2016-07-12 08:45:00 EDT	100	67.921644	61125	129

Figure 43: Display the TestRate measurements

Main Menu: Alarms & Events -> View History (Filtered) Tue Jul 12

Filter\* Tasks

Event ID	Timestamp	Severity	Product	Process	NE	Server	Type	Instar
<u>Event Text</u>								
33355	2016-07-12 08:53:37.948 EDT	<a href="#">CLEAR</a>	...	ProcWatch	SO_HPC06	HPC06MP1	DCA	DCA5
TestRateAlrm								
33355	2016-07-12 08:53:18.948 EDT	<a href="#">MINOR</a>	...	ProcWatch	SO_HPC06	HPC06MP1	DCA	DCA5
TestRateAlrm								
33355	2016-07-12 08:53:18.948 EDT	<a href="#">CLEAR</a>	...	ProcWatch	SO_HPC06	HPC06MP1	DCA	DCA5
TestRateAlrm								
33355	2016-07-12 08:51:15.948 EDT	<a href="#">MAJOR</a>	...	ProcWatch	SO_HPC06	HPC06MP1	DCA	DCA5
TestRateAlrm								
33355	2016-07-12 08:51:15.948 EDT	<a href="#">CLEAR</a>	...	ProcWatch	SO_HPC06	HPC06MP1	DCA	DCA5
TestRateAlrm								
33355	2016-07-12 08:51:15.948 EDT	<a href="#">CRITICAL</a>	...	ProcWatch	SO_HPC06	HPC06MP1	DCA	DCA5
TestRateAlrm								
33355	2016-07-12 08:29:47.948 EDT	<a href="#">MAJOR</a>	...	ProcWatch	SO_HPC06	HPC06MP1	DCA	DCA5

Export Report

Figure 44: TestRate Alarm History

### 8.3.9 Step 8: Promote the DCA Version to Production

The same process described in Section 3.3.8 is followed.

## 9. GUI Overview

### 9.1 NO/SO differences

Table 1: NO/SO GUI differences

NO	SO
Framework Configuration	Read-only
General Options	Read-only
Custom MEALs	Read-only
Trial MP Assignment	Read-only
New application versions are created	-
Existing application versions are copied	-
Business Logic and/or NO Config data imported/exported	SO Config data imported/exported
SBR DB Mane Mapping	Read-only
Flowchart and Script Development	Read-only
Application version state transitions	Read-only
Defining the configuration tables (schema)	Read-only
Provisioning NO Configuration Data (table content)	Provisioning SO Configuration Data (table content) NO configuration read-only.
-	System Options

### 9.2 NO Screens

The DCA framework left hand menu on the NO includes the following screens:

- Configuration Screen

Each activated application is represented by the separate menu folder with the given application name. The application folder on the NO includes the following screens (Application Control screen contains the buttons that lead to other DCA screens):

- Custom Meals
- General Options Screen
- Trial MPs Assignment Screen
- Application Control Screen
  - Create New Development Screen
  - Copy to New Development Screen
  - Import Pop-Up Window
  - Export Pop-Up Window
  - SBR Database Name Mapping
  - Development Environment
  - Tables Screen
    - Provision Tables Screen




Figure 45: NO Screens

### 9.2.1 Configuration Screen

The **NO Main Menu: DCA Framework > Configuration** screen allows configuring DCA Framework parameters: Maximum Size of Application State and Maximum Size of the Key. See Figure 46.

**Main Menu: DCA Framework -> Configuration**

**DCA Framework Configuration**

Field	Value	Description
Maximum Size of Application State *	267	Maximum size of the application state (in bytes) to be stored in the U-SBR. [Default = 256; Range = 1-64 kB.] [A value is required.]
Maximum Size of the Key *	268	Maximum size of the key (in bytes) used to lookup the application state stored in the U-SBR. [Default = 256; Range = 1-1024 B.] [A value is required.]

**Buttons:** Apply   Cancel

Figure 46: NO Configuration Screen

## 9.2.2 Custom MEALs


### 9.2.2.1 View Custom MEALs

The **NO Main Menu: DCA Framework > <DCA Name> > Custom MEALs** screen (illustrated in Figure 47) lists the Custom MEAL templates differentiated for the current DCA. It also enables new Custom MEAL templates to be differentiated and differentiated Custom MEAL templates to be modified.

There are a limited number of Custom MEAL templates of each type for all DCAs activated in a network. An error displays if the DCA programmer attempts to exceed these limits.

It is not possible to modify the counter/basic/rate/event and scalar/arrayed type of a differentiated Custom MEAL template. If the type needs to be modified, then a new Custom MEAL template is created (provided the limits have not been exceeded yet) and the old one is deleted.

Main Menu: DCA Framework -> First Dca App -> Custom MEALs



The screenshot shows a table with the following columns: Name, Template Type, Measurement Type, State, 100% Threshold Value, Alarm Autoclear Interval, Alarm Throttling Interval, Threshold Min Clear, Threshold Min Set, Threshold Maj Clear, Threshold Maj Set, Threshold Crit Clear, and Threshold Crit Set. One row is visible with the values: MyEvent, Event, ~, Completed, ~, 300, 60, ~, ~, ~, ~, ~, ~. Below the table are buttons for Insert, Edit, Delete, and a checkbox for Pause updates.

Name	Template Type	Measurement Type	State	100% Threshold Value	Alarm Autoclear Interval	Alarm Throttling Interval	Threshold Min Clear	Threshold Min Set	Threshold Maj Clear	Threshold Maj Set	Threshold Crit Clear	Threshold Crit Set
MyEvent	Event	~	Completed	~	300	60	~	~	~	~	~	~


Buttons: Insert, Edit, Delete, Pause updates

Figure 47: The Custom MEAL View Screen

### 9.2.2.2 Configure the Counter Custom MEAL Template

Figure 48 illustrates the configuration options for inserting a Counter template.

Main Menu: DCA Framework -> First Dca App -> Custom MEALs -> [Insert]



The screenshot shows a configuration form for a Counter template. It includes fields for Measurement Name (MyCnt), Template Type (Counter), and Measurement Type (Scalar). The form also includes a detailed description for each field. At the bottom are Ok, Apply, and Cancel buttons.

Field	Value	Description
Measurement Name *	MyCnt	Measurement/Event name. It will be used to derive the names of related counters, KPIs, max and average measurements, alarms. [Default = empty; Range = A 32-character string]. [A value is required.]
Template Type	Counter	Custom MEAL template type. [Default = Rate; Range = Counter, Rate, Basic, Event]
Measurement Type	Scalar	For Counter, Rate and Basic Custom MEALs, specify if the Custom MEAL is Scalar or Arrayed. [Default = Scalar; Range = Scalar, Arrayed].

Buttons: Ok, Apply, Cancel

Figure 48: The Counter Template Configuration Screen

### 9.2.2.3 Configure the Basic Custom MEAL Template

Figure 49 illustrates the configuration options for inserting a Basic template. The Basic template is optionally associated with an alarm, which is automatically raised if the configured thresholds are exceeded.

Main Menu: DCA Framework > First Dca App > Custom MEALs > [Insert]

Adding a new custom measurement or event

Field	Value	Description
Measurement Name *	MyBasic	Measurement/Event name. It will be used to derive the names of related counters, KPIs, max and average measurements, alarms. [Default = empty; Range = A 32-character string]. [A value is required.]
Template Type	Basic	Custom MEAL template type. [Default = Rate; Range = Counter, Rate, Basic, Event]
Measurement Type	Scalar	For Counter, Rate and Basic Custom MEALs, specify if the Custom MEAL is Scalar or Arrayed. [Default = Scalar; Range = Scalar, Arrayed].
KPI Description	MyBasic Description	KPI description text. [Default = Empty; Range = A 255-character string].
Generate Alarm	<input checked="" type="checkbox"/>	If checked, an alarm will be created. [Default = Checked; Range = Checked, Unchecked]
Alarm Description	Alarm Description	Alarm description text. [Default = Empty; Range = A 255-character string].
100% Threshold Value	5000	An absolute value that specifies: For Rate templates: the maximum events per second the Custom MEAL is expected to count (for instance the maximum messages per second). For Basic templates: the maximum value the Custom MEAL is expected to measure (for instance the maximum number of bytes, AVPs, etc. in a message). The minor, major and critical threshold values are defined as percentages from this value. [Default = Empty; Range = 1 - (2^63)-1 (i.e. 9223372036854775807)].
Alarm Minor Set Threshold	50	Minor alarm set threshold in %. [Default = Empty; Range = 2 - 98].
Alarm Minor Clear Threshold	40	Minor alarm clear threshold in %. [Default = Empty; Range = 1 - 95].
Alarm Major Set Threshold	70	Major alarm set threshold in %. [Default = Empty; Range = 4 - 98].
Alarm Major Clear Threshold	60	Major alarm clear threshold in %. [Default = Empty; Range = 3 - 97].
Alarm Critical Set Threshold	90	Critical alarm set threshold in %. [Default = Empty; Range = 6 - 100].
Alarm Critical Clear Threshold	80	Critical alarm clear threshold in %. [Default = Empty; Range = 5 - 99].
<input type="button" value="Ok"/> <input type="button" value="Apply"/> <input type="button" value="Cancel"/>		

Figure 49: The Basic Template Configuration Screen

### 9.2.2.4 Configure the Rate Custom MEAL Template

Figure 50 illustrates the configuration options for inserting a Rate template. The Rate template is optionally associated with an alarm, which is automatically raised if the configured thresholds are exceeded.

Main Menu: DCA Framework > First Dca App > Custom MEALs > [Insert]

Adding a new custom measurement or event

Field	Value	Description
Measurement Name *	MyRate	Measurement/Event name. It will be used to derive the names of related counters, KPIs, max and average measurements, alarms. [Default = empty; Range = A 32-character string]. [A value is required.]
Template Type	Rate <input type="button" value="▼"/>	Custom MEAL template type. [Default = Rate; Range = Counter, Rate, Basic, Event]
Measurement Type	Scalar <input type="button" value="▼"/>	For Counter, Rate and Basic Custom MEALs, specify if the Custom MEAL is Scalar or Arrayed. [Default = Scalar; Range = Scalar, Arrayed].
KPI Description	MyRate Description	KPI description text. [Default = Empty; Range = A 255-character string].
Generate Alarm	<input checked="" type="checkbox"/>	If checked, an alarm will be created. [Default = Checked; Range = Checked, Unchecked]
Alarm Description	Alarm Description	Alarm description text. [Default = Empty; Range = A 255-character string].
100% Threshold Value	40000	An absolute value that specifies: For Rate templates: the maximum events per second the Custom MEAL is expected to count (for instance the maximum messages per second). For Basic templates: the maximum value the Custom MEAL is expected to measure (for instance the maximum number of bytes, AVPs, etc. in a message). The minor, major and critical threshold values are defined as percentages from this value. [Default = Empty; Range = 1 - (2^63)-1 (i.e. 9223372036854775807)].
Alarm Minor Set Threshold	50	Minor alarm set threshold in %. [Default = Empty; Range = 2 - 96].
Alarm Minor Clear Threshold	40	Minor alarm clear threshold in %. [Default = Empty; Range = 1 - 95].
Alarm Major Set Threshold	70	Major alarm set threshold in %. [Default = Empty; Range = 4 - 98].
Alarm Major Clear Threshold	60	Major alarm clear threshold in %. [Default = Empty; Range = 3 - 97].
Alarm Critical Set Threshold	90	Critical alarm set threshold in %. [Default = Empty; Range = 6 - 100].
Alarm Critical Clear Threshold	80	Critical alarm clear threshold in %. [Default = Empty; Range = 5 - 99].
<input type="button" value="Ok"/> <input type="button" value="Apply"/> <input type="button" value="Cancel"/>		

Figure 50: The Rate Template Configuration Screen

### 9.2.2.5 Configure the Event Custom MEAL Template

Figure 51 illustrates the configuration options for inserting an Event template.

Main Menu: DCA Framework > First Dca App > Custom MEALs > [Insert]

#### Adding a new custom measurement or event

Field	Value	Description
Measurement Name *	MyEvent	Measurement/Event name. It will be used to derive the names of related counters, KPIs, max and average measurements, alarms. [Default = empty; Range = A 32-character string]. [A value is required.]
Template Type	Event	Custom MEAL template type. [Default = Rate; Range = Counter, Rate, Basic, Event]
Alarm Description	Alarm Description	Alarm description text. [Default = Empty; Range = A 255-character string].
Alarm Autoclear Interval	300	Time Interval in seconds after which a raised alarm is autocleared unless not explicitly cleared or re-asserted. A value of 0 means the alarm never autoclears. [Default = 300; Range = 0-3600]
Alarm Throttling Interval	60	Time interval in seconds during which multiple events with the same event number and instance are suppressed if raised. A value of 0 means no throttling is performed. [Default = 60; Range = 0-300]

Ok    Apply    Cancel

Figure 51: The Event Template Configuration Screen

### 9.2.3 General Options Screen

The **NO Main Menu: DCA Framework > <Application Name> > General Options** screen enables specifying the Perl Subroutines for Diameter Request and Answer, Application State Data TTL, Read Only U-SBR Access as Guest and Max. U-SBR Queries per Message. See Figure 52.

Main Menu: DCA Framework -> DCA Frame Work Application -> General Options

Mon Jun 13 06:46:20 2016

DCA Application General Options		
Perl Subroutine for Diameter Request *	process_request	[Default = process_request. Range = A 255 character string Valid characters are alphanumeric and underscore. Must contain at least one alpha and must not start with a digit.] [A value is required.]
Perl Subroutine for Diameter Answer	process_answer	The name of the Perl subroutine to be invoked when a Diameter answer is received. [Default = process_answer. Range = A 255 character string Valid characters are alphanumeric and underscore. Must contain at least one alpha and must not start with a digit.]
Application State Data TTL *	120	The TTL of the application state data stored in the U-SBR by the DCA App, in seconds. [Default = 120. Range = 60 - 604800] [A value is required.]
Read Only U-SBR Access as Guest	<input checked="" type="checkbox"/>	If checked the DCA App will be able to access U-SBR DBs owned by other DCA Apps only read-only. Attempts to update or delete such U-SBR DB records will result in an error. If unchecked the DCA App will have full access rights to U-SBR DBs owned by other DCA Apps. Note that if one or more "guest" DCA Apps handle application states stored in a U-SBR DB owned by another DCA, unexpected behavior of the DCA Apps or even race conditions may occur if the business logics of the "guest" and "owner" DCA App are not semantically consistent. A typical restriction in this sense would be for instance that the U-SBR DB records can only be deleted by the DCA App that created them. Also note that a "guest" DCA App will use its own Application State Data TTL setting for updating the TTL of the U-SBR DB records that it handles. Unexpected behavior of the DCA Apps or even race conditions may occur if the "guest" and "owner" DCA App have substantially different stateTTLsec settings. [Default = Checked. Range = Checked, Unchecked].
Max. U-SBR Queries per Message *	5	Maximum number of SBR Queries a DCA App may send per Diameter message (request or answer). Subsequent U-SBR queries will return an error. [Default = 5. Range = 1 - 10] [A value is required.]
<input type="button" value="Apply"/> <input type="button" value="Cancel"/>		

Figure 52: NO General Options

### 9.2.4 Trial MPs Assignment Screen

The **NO Main Menu: DCA Framework > <DCA Name> > Trial MPs Assignment** screen allows specifying which DA-MPs run the Trial version of DCA (see Figure 53). If there is no Trial version available, the Trial DA-MPs runs the Production version, if there is any available.

If a DCA version is promoted to the Trial state but no Trial DA-MPs are currently configured assigned, a warning message displays.

Main Menu: DCA Framework -> DCA Frame Work Application -> Trial MPs assignment

Trial MP assignment

:::::::::: Available MPs ::::::::::::		:::::::::: Trial MPs ::::::::::::	
<input type="checkbox"/> Gremlin-DAMP-1 <input type="checkbox"/> Gremlin-DAMP-3 <input type="checkbox"/> Gremlin-DAMP-4		<input type="button" value="&gt;&gt;"/> <input type="button" value="&lt;&lt;"/> <div style="border: 1px solid black; padding: 5px; display: inline-block;">           Gremlin-DAMP-2         </div>	
<input type="button" value="Apply"/> <input type="button" value="Cancel"/>			

Figure 53: NO Trial MPs Assignment


## 9.2.5 Application Control Screen

The **NO Main Menu: DCA Framework > <Application Name> > Application Control** screen (see Figure 54) allows:

- Listing all application versions configured in the system
- Inserting a new application version (via NO New Development Insert Screen)
- Copying and modifying an existing application version (via NO New Development Copy Screen)
- Exporting an application version entirely (business logic + provisioned data from the NO)
- Exporting only the NO provisioned data of an application version
- Importing a previously exported application version (business logic + NO provisioned data) (via NO Import Pop-Up Window).
- Importing only the NO provisioned data to an existing application version (via NO Import Pop-Up Window)
- Accessing the application version configuration tables (via NO Tables View Screen)
- Accessing business logic and flowchart of an application version (via NO Development Environment Screen)
- Deleting an existing application version
- Changing the status of an application version (Development, Trial, Production, Archived)

Main Menu: DCA Framework -> DCA Frame Work Application -> Application Control

Mon Jun 13 07:07:20 2016 EDT



The screenshot shows a table of application versions with the following data:

Version Name	Status	Comments	Creation Time	Production Time	Flowchart Checksum	Schema Checksum
DCA_FW_App_v1	Archived	first app	2016-May-20 10:07:53 EDT	2016-Jun-09 16:44:44 EDT	800afa59e0fb0f1c1562ce3b6279ccaf	d7caf76eb65e06e999174260bbd4e85d
DCA_FW_App_v5	Development	fifth app			800afa59e0fb0f1c1562ce3b6279ccaf	
DCA_FW_App_v3	Development	third app	2016-May-23 10:23:39 EDT	2016-Jun-09 16:34:10 EDT	800afa59e0fb0f1c1562ce3b6279ccaf	f66cd730fe34b4aef71fb3b144a6c07
DCA_FW_App_v4	Development	fourth app	2016-May-23 10:24:02 EDT		800afa59e0fb0f1c1562ce3b6279ccaf	a610cb96499621dc7a2e5446392ee28
dca_fw_app_v1	Development	first-pt2 app	2016-May-23 10:57:55 EDT		800afa59e0fb0f1c1562ce3b6279ccaf	
AA_BB_CC_V2	Development	second-pt2 app	2016-May-23 10:58:35 EDT		800afa59e0fb0f1c1562ce3b6279ccaf	
AA_BB_CC_V3	Development	third-pt2 app	2016-May-23 11:00:01 EDT		800afa59e0fb0f1c1562ce3b6279ccaf	
DCA_FW_App_v6	Development	fifth-pt2 app	2016-May-23 11:02:23 EDT		800afa59e0fb0f1c1562ce3b6279ccaf	
DCA_FW_App_v2	Trial	second app	2016-May-23 10:20:41 EDT	2016-Jun-09 16:37:39 EDT	800afa59e0fb0f1c1562ce3b6279ccaf	044e690951b203465e9dc5b3a82e0002
RBAR_Lite	Production		2016-Jun-03 13:27:40 EDT	2016-Jun-09 16:45:40 EDT	ebfbfd277205b83e7086fc60011d54f24	be0ab3817634b3870e4b8dd652ef0953

Below the table are several buttons:

- Config Tables and Data
- Development Environment
- SBR DB Name Mapping
- Create New Development
- Copy to New Development
- Delete
- Import: Business Logic, A Level Config Data
- Export: Business Logic, A Level Config Data, Both
- Make Development
- Make Trial
- Make Production

Figure 54: NO Application Control

### 9.2.6 Create New Development Screen

The **NO Main Menu: DCA Framework > <Application Name> > Application Control > Create New Development** screen allows creating a new DCA version with a given name and comments. It is accessed by clicking **Create New Development** on the Application Control screen, see Figure 55.

Main Menu: DCA Framework -> Test App Number 4 -> Application Control -> [Create New Development]

Adding a new application version

Field	Value	Description
Version Name *	<input type="text"/>	Unique name of the Application Version. [Default = n/a; Range = A 32-character string. Valid characters are alphanumeric and underscore. Must contain at least one alpha and must not start with a digit.] [A value is required.]
Comments	<input type="text"/>	Optional comment. [Default = n/a. Range = A 255 character string].

Ok Apply Cancel

Figure 55: NO Create New Development Screen

Currently, there might be up to 10 application versions at a time.

### 9.2.7 Copy to New Development Screen

The **NO Main Menu: DCA Framework > <Application Name> > Application Control > Copy to New Development** screen allows copying an entire DCA version, consisting of business logic (Perl script, flowchart, and configuration table schemas) and the NO provisioned configuration data, into a new version. It is accessed by selecting the application version and clicking **Copy to New Development** on the Application Control screen, see Figure 56.

Main Menu: DCA Framework -> Test App Number 4 -> Application Control -> [Copy to New Development]

Info

Info

The version will be copied together with the business logic (tables + flowchart) and A level config data.

Version Name *	<input type="text" value="Testapp4v1"/>	Unique name of the Application Version. [Default = n/a; Range = A 32-character string. Valid characters are alphanumeric and underscore. Must contain at least one alpha and must not start with a digit.] [A value is required.]
Comments	<input type="text"/>	Optional comment. [Default = n/a. Range = A 255 character string].

Ok Apply Cancel

Figure 56: NO Copy to New Development

When the new Application Version is copied, it becomes visible on the Application Control screen displaying the user provisioned name in the Version Name column and comments in the Comments column.

The copied Application also includes the business logic (DB tables + Perl script) and the A level (NO level) configuration data (if any was specified).

## 9.2.8 Export Pop-Up Window

The exported application version is stored in the form of a JSON file.

DCA Framework GUI offers three export options:

- Export the business logic only (that includes the defined tables, flow control chart, the script, custom Meals, KPIs, Events associated with the application version, logical to physical SBR Mapping. It does not include the provisioned data).
- Export the business logic and the configuration data (in addition to the business logic the provisioned data for the tables is also exported).
- Export the configuration data only.

For the first option, select the application version and click **Export Business Logic** (becomes enabled when the row is selected).

For the second option, select the application version and click **Export Both** (becomes enabled when the row is selected).

For the third option, select the application version and click **Export A Level Config Data** (becomes enabled when the row is selected). The export popup window is illustrated in Figure 57.




Figure 57: NO Export

When the user tries to export the business logic, there is a validation to check whether the flowchart/script has been compiled. If not, the export is aborted and the error is given.

The A level (NO level) configuration data can be exported from the NO machine, but not from the SO.

## 9.2.9 Import Pop-Up Window

The NO Import Pop-Up window allows specifying a JSON file from which the business logic (if required) and the NO provisioned data is imported.

**Note:** The provisioned data imported to the existing business logic is appended to the existing data rows.

If the user wants to overwrite the configuration data, it is recommended to first delete all provisioned rows on the Provision Table screen and then import the new configuration data.

DCA Framework GUI offers three import options:

- Import the business logic only (that includes the defined tables, flow control chart, the script, custom Meals, KPIs, Events associated with the application version, logical to physical SBR Mapping. It does not include the provisioned data import; hence, the defined tables are empty after the import).
- Import the business logic and the configuration data (in addition to the business logic the provisioned data for the tables is also imported).
- Import the configuration data only.

For the first option, click **Import Business Logic** (always enabled) on the NO Application Control screen. Leave the checkbox **Import also Config data** unchecked, see Figure 58. Select the file.

For the second option, click **Import Business Logic** (always enabled) on the NO Application Control screen. Check **Import also Config data** the checkbox. Select the file.

For the third option, select the application version and click **Import A Level Config Data** (becomes enabled when the row is selected), see Figure 59. Select the file.




Figure 58: NO Import Business Logic




Figure 59: NO Import Configuration Data

During the import, validations are performed in a particular order to ensure the format of DCA configuration data to be imported is compatible with that of the target DCA version.

As a result, a number of fatal errors may occur during the import, which forces the import to be aborted regardless of **Abort on first error** checkbox. Such fatal errors are:

- File larger than 25MB.

- File has wrong structure or missing data.
- All the errors that happen during the business logic import.
- If the user tries to import the configuration data to an existing application version, but none of the table names from the imported file matches the table names of the selected application.
- If the user tries to import the configuration data to an existing application version, but none of the field names in the tables from the imported file matches the field names in the tables of the selected application.
- Level mismatch. A-level DCA configuration data can be imported only on the A level. The same applies to the B level data.

Non-fatal errors, on the other hand, let the user decide whether to abort the import or not (depending on the value of **Abort on first error** checkbox).

### 9.2.10 SBR DB Name Mapping Screen

The **NO Main Menu: DCA Framework > <Application Name> > Application Control > <Version Name> > SBR Database Name Mapping View** screen (see Figure 60) allows viewing and configuring the mapping between U-SBR DB logical names (as used in Perl script) and U-SBR DB physical names. It is accessed by selecting an application version and clicking **SBR DB Name Mapping** on the Application Control screen.

**Note:** All the SBR names referred in the application version script are matched to the SBR physical names.

Main Menu: DCA Framework -> Test App Number 4 -> Application Control -> Testapp4v1 -> SBR DB Name Mapping

SBR Database Logical Name	SBR Database Physical Name

Insert    Edit    Delete

Filter\* ▾

Figure 60: NO SBR DB Name Mapping View

The **NO Main Menu: DCA Framework > <Application Name> > Application Control > <Version Name> > SBR DB Name Mapping Insert** screen (see Figure 61) allows creating the new mapping between U-SBR DB logical names (as used in Perl script) and U-SBR DB physical names. It is accessed by clicking **Insert** on the SBR DB Name Mapping View screen.

Main Menu: DCA Framework -> DCA Frame Work Application -> Application Control -> AA\_BB\_CC\_v3 -> SBR DB Name Mapping -> [Insert] Mon Jun 13 08:52:

Field	Value	Description
SBR DB Logical Name *	<input type="text"/>	Logical name of the SBR database as defined in the script. [Default = n/a; Range = A 32-character string. Valid characters are alphanumeric and underscore. Must contain at least one alpha and must not start with a digit.] [A value is required.]

Available SBR Databases    Included SBR Databases

Ok    Apply    Cancel

Figure 61: NO SBR DB Name Mapping Insert

Specify the logical name that is used by the application version script and move the corresponding physical SBRs to the right list Included SBR Databases.

Each DCA running on a particular DA-MP monitors the administrative state of the resolved physical U-SBR DBs and their sub-resource routing state, and updates its own operational state to Unavailable in any of the following cases:

- The U-SBR DB's administrative state is not Enabled.
- The U-SBR DB's administrative state is Enabled but all of its sub-resources are unavailable or are not reporting.

The Alarm ID 33306 is raised if a logical U-SBR DB name cannot be resolved to a physical U-SBR DB name (none of the physical U-SBR DBs mapped to a logical U-SBR DB is located in the same Place Association as the DA-MP performing the resolution). The Alarm ID 33306 is cleared when the logical-to-physical U-SBR DB resolution process is (re-)triggered.

The **NO Main Menu: DCA Framework > <Application Name> > Application Control > <Version Name> > SBR Database Name Mapping Edit** screen allows editing the mapping between U-SBR DB logical names (as used in Perl script) and U-SBR DB physical names.

### 9.2.11 Development Environment

Development Environment is accessed by selecting the application version and clicking **Development Environment** on the Application Control screen. The DCA Development Environment (DCA-DE) is where a custom Diameter application developer can edit, save, check syntax, and compile the application code for a Diameter Custom Application.

See [1] CGBU\_018429 - DCA Framework and Application Activation and Deactivation for more details.

### 9.2.12 Tables Screen

The **NO Main Menu: DCA Framework > <Application Name> > Application Control > <Version Name> > Tables View** screen (see Figure 62) allows:

- Listing all the config tables (NO+SO) defined for an application version
- Inserting/editing a new config table (NO or SO) for the development or trial application version (via NO Table Insert/Edit Screen).
- Deleting an existing config table (NO or SO) for the development or trial application version
- Viewing an existing config table of an archived or production application version (via NO Table View Screen).
- Accessing the Provision Table View and Insert/Edit screens (via NO Provision Table View Screen, NO Provision Table Insert Screen and NO Provision Table Edit Screen).

The Tables View screen is accessed by selecting the application version and clicking **Config Tables and Data** on the Application Control screen.

Main Menu: DCA Framework -> DCA Frame Work Application -> Application Control -> DCA\_FW\_App\_v2 -> Tables

Tables			
Table Name	Description	Single Row	Level
table2		NO	NO

Buttons: Insert, Edit, View, Delete, Provision Table

Figure 62: NO Tables View Screen

**Insert**, **Edit**, and **Delete** are disabled on the Tables View screen for the archived and production application versions.

**View** is enabled for the archived and production application versions if the table is selected.

**View** is disabled for the development and trial application version.

**Provision Table** is always enabled if the NO table is selected (it is disabled for the SO tables from the NO GUI).

Table 2 illustrates the access rights for DCA configuration schema and data provisioning tables. The NO/SO DCA database tables (schema) can be created, deleted, and modified from the NO GUI for the development and trial application versions; they can be only viewed for the archived and production application version. The NO DCA database tables can be provisioned anytime from the NO GUI. The SO tables cannot be provisioned from the NO GUI.

**Table 2: NO GUI Tables and Configuration Data Accessibility**

The accessibility of level A and level B table schema and content from the NO GUI	SO GUI		
	Archived	Production	Development, Trial
<b>NO tables schema (level A)</b>	ro	ro	rw
<b>NO tables content (level A)</b>	rw	rw	rw
<b>SO tables schema (level A – shares same field as NO tables schema)</b>	ro	ro	rw
<b>SO tables content (level B)</b>	N/A	N/A	N/A

ro: read-only rw: read-write N/A: not applicable

The **NO Main Menu: DCA Framework > <Application Name> > Application Control > <Version Name> > Table Insert** screen (see Figure 63) allows defining a new configuration table (NO or SO). It is accessed by clicking **Insert** on the Tables View screen for the development and trial application versions.

## Adding a new table

Field	Value	Description
Table Name *	<input type="text"/>	Unique name of the Table. [Default = n/a; Range = A 32-character string. Valid characters are alphanumeric and underscore. Must contain at least one alpha and must not start with a digit.] [A value is required.]
Description	<input type="text"/>	Optional Description. [Default = n/a. Range = A 255 character string].
Single Row	<input type="checkbox"/>	Indicates if the table must have one single row. [Default=Unchecked. Range= Checked, Unchecked].
Level	<input checked="" type="radio"/> NO <input type="radio"/> SO	Configuration level of the table (NO or SO). [Default=NO. Range=NO, SO].
<b>Table Fields *</b>		
Field Name	<input type="text"/> *	Unique name of the Table Field [Default = n/a; Range = A 32-character string. Valid characters are alphanumeric and underscore. Must contain at least one alpha and must not start with a digit.]
Description	<input type="text"/>	Optional description. [Default = n/a. Range = A 255 character string].
Unique	<input type="checkbox"/>	Indicates if the table field must be unique. [Default=Unchecked. Range=Checked, Unchecked].
Mandatory	<input type="checkbox"/>	Indicates if the table field must be mandatory. [Default=Unchecked. Range=Checked, Unchecked].
Data Type	- Select - <input type="button" value="▼"/>	Data Type. [Default=n/a. Range= Integer, Float, UTF8String, OctetString, IP Address, DiameterURI, DiameterIdentity, Enumerated, Boolean]. <ul style="list-style-type: none"> <li>• Integer: Unsigned64/Signed64</li> <li>• Float: [+/-]number[.number][eE[+/-]number], for example 12.3 or 1.23e+1</li> <li>• UTF8String</li> <li>• OctetString: hexadecimal value prefixed with 0x</li> <li>• IP Address: IPv4 (decimal numbers separated by a period) /IPv6 (RFC4291, section 2.2, form 1 and 2 are supported)</li> <li>• DiameterURI: "aaa://" FQDN [ port ] [ transport ] [ protocol ] "aaaas://" FQDN [ port ] [ transport ] [ protocol ], see RFC6733</li> <li>• DiameterIdentity: FQDN or Realm, see RFC6733</li> <li>• Enumerated: Comma separated list of values, which can be separate items (a,b,c) or in form of: (a:1,b:2,c:3).</li> <li>• Boolean: true/false</li> </ul>
		<input type="button" value="Remove"/>
	<input type="button" value="Add"/>	
<input type="button" value="Ok"/> <input type="button" value="Apply"/> <input type="button" value="Cancel"/>		

**Figure 63: NO Tables Insert Screen**

Currently, there might be up to 10 configuration tables per application version (NO+SO).

The configuration table definition includes:

- Table Name and Description
- Number of table rows (single vs multiple up to 2000 rows)
- Table level (whether the table resides on the NO or the SO)
- Table Fields (up to 20 now)
  - Field Name and Description
  - Whether the field is unique
  - Whether the field is mandatory
  - Field Data Type
  - Field Default value

The table fields can be of the following types (depending on the selected data type, ranges must be also defined):

- Integer (Range: Min. and Max. values)
- Float (Range: Min. and Max. values)

- UTF8String (Range: Max. length)
- OctetString (Range: Max. length)
- IPaddress
- DiameterURI
- DiameterIdentity
- Enumerated (The values)
- Boolean

The **NO Main Menu: DCA Framework > <Application Name> > Application Control > <Version Name> > Table Edit** screen allows editing the schema of an existing DCA configuration table (NO or SO).

The **NO Main Menu: DCA Framework > <Application Name> > Application Control > <Version Name> > Table View (Read-only Insert/Edit)** screen allows viewing a DCA configuration table in read-only mode. It is accessed when the table is selected and **View** is clicked on the NO Tables View screen for the archived and production application version.


### 9.2.13 Provision Tables Screen

The **NO Main Menu: DCA Framework > <Application Name> > Application Control > <Version Name> > Provision Table View** screen (Figure 65) allows:

- Listing all the data rows provisioned for the NO configuration table
- Inserting a new data row to the NO configuration table (via NO Provision Table Insert Screen)
- Editing a data row of the NO configuration table (via NO Provision Table Edit Screen)
- Deleting a data row from the NO configuration table
- Deleting all provisioned rows at once

It is accessed by selecting the table and clicking **Provision Table** on the Tables View screen, see Figure 64.

Main Menu: DCA Framework -> DCA Frame Work Application -> Application Control -> DCA\_FW\_App\_v2 -> Tables



Tables			
Table Name	Description	Single Row	Level
Parm	parm	NO	NO
table2		NO	NO
v4Table1	210	YES	SO

Buttons: Insert, Edit, View, Delete, Provision Table

**Figure 64: Provision Table Button**

**Provision Table** is disabled for the SO tables from the NO GUI, see Table 2.

Main Menu: DCA Framework -&gt; DCA Frame Work Application -&gt; Application Control -&gt; DCA\_FW\_App\_v2 -&gt; Provision Table

Table: table2

kit	int5	Ipokipo

Insert Edit Delete Delete All Back

Figure 65: NO Provision Table View Screen

Up to 2000 rows of data can be provisioned per table unless the table has only single row (the **Single row** checkbox has been checked on the Table Insert screen).

The **NO Main Menu: DCA Framework > <Application Name> > Application Control > <Version Name> > Provision Table Insert** screen (see Figure 66) allows inserting a new data row to the NO configuration table.

Main Menu: DCA Framework -> DCA Frame Work Application -> Application Control -> DCA\_FW\_App\_v2 -> Provision Table -> [Insert] Tu

Adding a new entry

Table: table2

Field	Value	Description
kit *	<input type="text"/>	[A value is required.]
int5 *	<input type="text"/>	[A value is required.]
Ipokipo *	<input type="checkbox"/>	[A value is required.]

Ok Apply Cancel

Figure 66: NO Provision Table Insert Screen

During the data insert, the GUI performs the following validations:

- Whether the mandatory value is present
- Whether the unique value is unique
- Whether the maximum of data rows is reached
- Whether the data inserted corresponds to the specified field data type
- Whether the data inserted is between the specified min-max range for the field
- Whether the entered sting value is no longer than the allowed maximum for the field
- Whether the entered enumerated value is within the allowed range of enumerated values for the field
- Etc.

The **NO Main Menu: DCA Framework > <Application Name> > Application Control > <Version Name> > Provision Table Edit** screen allows editing a data row of the NO configuration table.

### 9.3 SO Screens

The DCA framework left hand menu on the SO includes the following screens:

- Configuration Screen (NO screen, read-only on the SO)

Each activated application is represented by the separate menu folder with the given application name. The application folder on the NO includes the following screens (Application Control screen contains the buttons that lead to other DCA screens):

- Custom Meals (NO screen, read-only on the SO)
- General Options Screen (NO screen, read-only on the SO)
- Trial MPs Assignment Screen (NO screen, read-only on the SO)
- Application Control Screen
  - Import Pop-Up Window
  - Export Pop-Up Window
  - SBR Database Name Mapping (NO screen, read-only on the SO)
  - Development Environment (NO screen, read-only on the SO)
  - Tables Screen (NO screen, read-only on the SO, except for **View** and **Provision Table**)
    - Provision Tables Screen
  - System Options Screen





Figure 67: SO Screens

### 9.3.1 Application Control Screen

The **SO Main Menu: DCA Framework > <Application Name> > Application Control** screen (see Figure 68) allows:

- Listing all application versions configured in the system
- Exporting only the SO provisioned data of an application version (via SO Export Pop-Up Window)
- Importing only the SO provisioned data to an existing application version (via SO Import Pop-Up Window).
- Accessing the application version configuration tables (via SO Tables View Screen)
- Accessing the flowchart and business logic of an application version (via development environment, read-only)

Main Menu: DCA Framework -> First Dca Appl -> Application Control



The screenshot shows a table with the following data:

Version Name	Status	Comments	Creation Time	Production Time	Flowchart Checksum	Schema Check
Version1	Trial		2016-Jun-01 14:12:56 EDT		c0adbb8b5cd7a0a36d237e5d135f3685	

Below the table are buttons for 'Config Data', 'Development Environment', and 'SBR DB Name Mapping'. To the right are 'Import' and 'Export' buttons, both labeled 'B Level Config Data'.

Figure 68: SO Application Control Screen

### 9.3.2 Export Pop-Up Window

The B level (SO level) configuration data can be exported from the SO machine, but not from the NO.

To export the configuration data to a JSON file, select the application version and click **Export B Level Config Data** (becomes enabled when the row is selected).

### 9.3.3 Import Pop-Up Window

The SO Import Pop-Up window allows specifying a JSON file from which the SO provisioned data is imported.

**Note:** The provisioned data imported to the existing business logic is appended to the existing data rows.

If the user wants to overwrite the configuration data, it is recommended to first delete all provisioned rows on the Provision Table screen and then import the new configuration data.

The B level (SO level) configuration data can be imported only to the SO machine.

To import the configuration data from the JSON file, select the application version and click **Import B Level Config Data** (becomes enabled when the row is selected). Select the file.

### 9.3.4 Tables Screen

The **SO Main Menu: DCA Framework > <Application Name> > Application Control > <Version Name> > Tables View** screen (see Figure 69) allows:

- Listing all the config tables (NO+SO) defined for an application version
- Viewing an existing config table (via NO/SO Table View Screen)
- Accessing the Provision Table View and Insert/Edit screens (via SO Provision Table View Screen, SO Provision Table Insert screen and SO Provision Table Edit Screen).

The SO Tables View screen is accessed by selecting the application version and clicking **Config Data** on the SO Application Control screen.

**Main Menu: DCA Framework -> First Dca Appl -> Application Control -> Version1 -> Tables**



The screenshot shows a table with the following columns: Table Name, Description, Single Row, and Level. At the bottom, there are buttons for Insert, Edit, View, Delete, and Provision Table. The View button is highlighted in yellow, indicating it is enabled.

**Figure 69: SO Tables View Screen (empty)**

**Insert**, **Edit**, and **Delete** are disabled on the SO Tables View screen.

**View** is enabled if the table is selected.

**Provision Table** is always enabled if the NO/SO table is selected.

Table 3 illustrates the access rights for DCA configuration schema and data provisioning tables on the SO. The NO/SO DCA table schemas can only be viewed. The level A DCA configuration tables content can only be viewed from the SO GUI. The level B DCA configuration tables can be provisioned.

**Table 3: SO GUI Tables and Configuration Data Accessibility**

The accessibility of level A and level B table schema and content from the SO GUI	SO GUI		
	Archived	Production	Development, Trial
<b>NO tables schema (level A)</b>	ro (replicated)	ro (replicated)	ro (replicated)
<b>NO tables content (level A)</b>	ro (replicated)	ro (replicated)	ro (replicated)
<b>SO tables schema (level A – shares same field as NO tables schema)</b>	ro (replicated)	ro (replicated)	ro (replicated)
<b>SO tables content (level B)</b>	rw	rw	rw

ro: read-only    rw: read-write

The **SO Main Menu: DCA Framework > <Application Name> > Application Control > <Version Name> > Table View (Read-only Insert/Edit)** screen allows viewing a configuration table in read-only mode. It is accessed when the table is selected and **View** is clicked on the SO Tables View screen.

### 9.3.5 Provision Tables Screen

The **SO Main Menu: DCA Framework > <Application Name> > Application Control > <Version Name> > Provision Table**, View screen allows:

- Listing all the data rows provisioned for the SO-rooted DCA configuration table.
- Inserting a new data row to the SO-rooted DCA configuration table (via SO Provision Table Insert Screen).
- Editing a data row of the SO-rooted DCA configuration table (via SO Provision table Edit Screen).
- Deleting a data row from the SO-rooted DCA configuration table.
- Deleting all provisioned rows at once.

**Note:** The NO-rooted DCA configuration tables, as well as the schema definitions of both the NO-rooted and SO-rooted DCA configuration tables are accessible on the SO only in read-only mode.

The SO Provision Table View screen is accessed by selecting the table and clicking **Provision Table** on the SO Tables View screen.

The **SO Main Menu: DCA Framework > <Application Name> > Application Control > <Version Name> > Provision Table**, Insert screen allows inserting a new data row to the SO-rooted DCA configuration table.

The **SO Main Menu: DCA Framework > <Application Name> > Application Control > <Version Name> > Provision Table**, Edit screen allows editing a data row of the SO-rooted DCA configuration table.

## 9.4 System Options

System Options screen is present on the SO only. See Figure 70- Figure 74.

System Options screen enables the configuration of the DSR application parameters that are:

- Relevant to the operational status Unavailable. These options allow you to specify the behavior when the application state is Unavailable (**Main Menu: Diameter > Maintenance > Applications**). The possible behavior is:
  - Continue Routing
  - Use default route + specify application unavailable route list
  - Send Answer with Result-Code AVP + specify Result-Code and Error Message
  - Send Answer with Experimental-Result AVO + specify Result-Code, Error Message, and Vendor-ID.

Application unavailable configuration		
Application Unavailable Action	<input checked="" type="radio"/> Continue Routing <input type="radio"/> Default Route <input type="radio"/> Send Answer with Result-Code AVP <input type="radio"/> Send Answer with Experimental-Result AVP	Action to be taken when the application is unavailable to process messages.
Application Unavailable Route List	<input type="button" value="- Select -"/>	If the Unavailability Action is "Default Route" and the application is not available, the requests will be routed using this Route List and Peer Routing Rules will be bypassed.
Application Unavailable Result-Code	<input checked="" type="radio"/> 3002 UNABLE_TO_DELIVER <input type="radio"/>	The Result-Code or Experimental-Result-Code value to be returned in an Answer message when a message is not successfully routed because of the application being unavailable. If Vendor-Id is configured, this value is encoded as Experimental-Result-Code AVP else Result-Code AVP. [Default = 3002; Range = 1000 - 5999]
Application Unavailable Error Message	Application Unavailable	The Error-Message AVP value to be returned in an Answer message when a message is not successfully routed because of the application being unavailable. [Default = "Application Unavailable"; Range = 0 to 64 characters]
Application Unavailable Vendor-Id		The Vendor-Id AVP value to be returned in an Answer message when a message is not successfully routed because of the application being unavailable. [Default = n/a; Range = 1 - 4294967295]

**Figure 70: System Options for the Unavailable Operation Status**

- Relevant to the case when the DRL resources are exhausted. The behavior is to send an error message with the specified Result-Code, Error Message, and Vendor-Id.

Resource exhaustion configuration		
Resource Exhaustion Result-Code	<input checked="" type="radio"/> 3004 TOO_BUSY <input type="radio"/>	The Result-Code or Experimental-Result-Code value to be returned in an Answer message when a message is not successfully routed because of internal resource being exhausted. If Vendor-Id is configured, this value is encoded as Experimental-Result-Code AVP else Result-Code AVP. [Default = 3004; Range = 1000 - 5999]
Resource Exhaustion Error Message	Application Resource Exhaust	The Error-Message AVP value to be returned in an Answer message when a message is not successfully routed because of internal resource being exhausted. [Default = "Application Resource Exhausted"; Range = 0 to 64 characters]
Resource Exhaustion Vendor-Id		The Vendor-Id AVP value to be returned in an Answer message when a message is not successfully routed because of internal resource being exhausted. [Default = n/a; Range = 1 - 4294967295]

**Figure 71: System Options for the Exhausted DRL Resources**

- Relevant to the run-time error. These options allow to specify the behavior in case of a run-time error. Runtime errors fall into two categories:
  - Perl specific runtime errors, for example, division by zero, a “die” statement, calling an undefined (utility, not event handler) subroutine etc.
  - Runtime errors triggered by the DCA framework, for example, invoking an event handler that does not exist or exceeding the maximum configured number of executed opcodes.

The possible behavior is:

- Continue Routing
- Discard
- Send Answer with Result-Code AVP + specify Result-Code and Error Message
- Send Answer with Experimental-Result AVO + specify Result-Code, Error Message, and Vendor-Id.

Field	Value	Description
<b>Run-time error configuration</b>		
Run-Time Error Action	<input checked="" type="radio"/> Continue Routing <input type="radio"/> Discard <input type="radio"/> Send Answer with Result-Code AVP <input type="radio"/> Send Answer with Experimental-Result AVO	Action to be taken when the DSR application experiences a run-time error.
Run-Time Error Result-Code	<input checked="" type="radio"/> 3002 UNABLE_TO_DELIVER <input type="radio"/>	The Result-Code or Experimental-Result-Code value to be returned in an Answer message when a message is not successfully routed because of the application run-time error. If Vendor-Id is configured, this value is encoded as Experimental-Result-Code AVP else Result-Code AVP. <small>[Default = 3002; Range = 1000 - 5999]</small>
Run-Time Error Message	Run-Time Error	The Error-Message AVP value to be returned in an Answer message when a message is not successfully routed because of the application run-time error. <small>[Default = "Run-Time Error"; Range = 0 to 64 characters]</small>
Run-Time Error Vendor-Id		The Vendor-Id AVP value to be returned in an Answer message when a message is not successfully routed because of the application run-time error. <small>[Default = n/a; Range = 1 - 4294967295]</small>

**Figure 72: System Options for the Run-Time Error**

- Realm and FQDN that are placed in Answer message generated by DCA. These are the values that are placed in the Origin-Realm and Origin-Host AVPs of the Answer message generated by DCA. If they are not configured, local node Realm and FQDN for the egress connection are used.

Configuration for the DCA generated Answer		
Realm		Value to be placed in the Origin-Realm AVP of the Answer message generated by DCA. If not configured, local node Realm for the egress connection is used. Realm is a case-insensitive string consisting of a list of labels separated by dots, where a label may contain letters, digits, dashes (-) and underscore (_). A label must start with a letter, digit or underscore and must end with a letter or digit. Underscores may be used only as the first character. A label must be at most 63 characters long and a Realm must be at most 255 characters long. Fully Qualified Domain Name is required to configure Realm. <small>[Default = n/a; Range = A valid Realm.]</small>
Fully Qualified Domain Name		Value to be placed in the Origin-Host AVP of the Answer message generated by DCA. If not configured, local node FQDN for the egress connection is used. FQDN is a case-insensitive string consisting of a list of labels separated by dots, where a label may contain letters, digits, dashes (-) and underscore (_). A label must start with a letter, digit or underscore and must end with a letter or digit. Underscores may be used only as the first character. A label must be at most 63 characters long and a FQDN must be at most 255 characters long. Realm is required to configure Fully Qualified Domain Name. <small>[Default = n/a; Range = A valid FQDN.]</small>

**Figure 73: System Options for the Realm and FQDN**

- Application invocation. This option is needed to indicate if the subsequent invocation of application on a different node in the network is allowed or not.
- If unchecked, the DSR-Application-Invoked AVP is inserted, preventing the same DSR application on another DSR node from receiving the Diameter message.

Application invocation		
Allow Subsequent Application Invocation	<input type="checkbox"/>	If checked, subsequent invocation of DCA Framework Application on a different node in the network is allowed. If unchecked, the DSR-Application-Invoked AVP will be inserted, preventing the same DSR application on another DSR node from receiving the Diameter message. <small>[Default=Unchecked; Range=Checked, Unchecked]</small>

**Figure 74: System Options for the Application Invocation**

## 10. Development Environment Overview

### 10.1 Development Environment Modes

DCA Development Environment opens if the user clicks Development Environment on the **Main Menu: [Application Name] > Application Control** screen. Development Environment is disabled if the Application Control: Script and Flow Control Chart DCA Framework View Permission is unchecked.

The DCA Development Environment can be accessible in two modes of operation:

- Edit Mode (any change is possible and can be saved)

- View Mode (the Code Text Editor is read-only, Toolbox and Action commands are disabled, the Flow Control Chart interactions are disabled)

The DCA DE can be accessible in the View only mode for the following cases:

- If the selected application version is either in Production or Archived status.
- If the **Application Control: Script and Flow Control Chart** DCA Framework Edit Permission is unchecked while the View Permission is checked.

DCA DE starts, but does not retrieve the Perl code and Flow Control Chart data if the **View Permission** is unchecked.

The DCA DE can be accessible in the Edit mode for the following cases:

- If the selected application version is either in Development or Trial status and the **Application Control: Script and Flow Control Chart** DCA Framework Edit Permission is checked.

## 10.2 Layout

The DCA Development Environment GUI Layout contains a top banner and the following sections, see Figure 75 and Figure 76:





Figure 75: Layout Structure



**Figure 76: Layout Print Screen**

The **Application Banner** displays the application version name and status.


The **Toolbox** displays the available commands for creating Flow Control Chart symbols: Create Exec Block, Create Async Call, Create Termination, Create Connection, see Figure 77.

The **Action Commands** display the available commands for managing the application code and Flow Control Chart: Render Chart, Save, Check Syntax, Compile, see Figure 77.

The **Flow Control Chart** displays the Flow Control Chart illustration of the application code structure.

The **Code Text Editor** displays the application code.

The **Commands Output** displays output messages from Action Commands.



**Figure 77: Toolbox and Actions**

### 10.3 Code Text Editor

The Code Text Editor includes the drop-down menus File, Edit, Exec Blocks and a **Fit Resize** button.



Figure 78: Code Text Editor

The File drop-down menu contains the following commands:

- Open (for uploading the Perl script from the selected file )
- Save (for saving the Perl script as a file)

The Exec Blocks drop-down menu contains all executions blocks present on the Flow Control Chart, providing navigation of code subroutines.

The Edit drop-down menu contains the following commands:

- Undo (the command erases the last change in the code, revert it to an older state)
- Redo (the command reverses the undo)
- Find/ Replace (the command searches for a specified text and when found, replace it with another specified text).

The application code consists of:

- Internal variable declarations
- The main subroutine
- Other referenced subroutines (if any)

The Code Text Editor provides automatic text markers that cause parts of the Perl code to be distinctively highlighted to the user for the following code elements:

- Perl subroutines
- DCA API asynchronous calls
- DCA API termination calls
- DCA API call

### 10.4 Flow Control Chart

- The Toolbox commands are used to add symbols and connections to the Flow Control Chart area to illustrate the flow of control between executions blocks and asynchronous calls for the application.
- The symbol can be added to the Flow Control Chart area or adjusted by dragging the symbol to the desired location. The connection is maintained during dragging.
- The Render Chart action command renders a new Flow Control Chart from the application code in the Code Text Editor.
- The Save action command saves the chart data along with the application code.
- There is a pan and zoom control panel above the Flow Control Chart for adjusting the location and scale of the visible chart boundaries to reveal hidden chart content.
- The symbol selected in the Flow Control Chart area becomes highlighted. Selecting the symbol in the Flow Control Chart area causes the Code Text Editor to select the code associated with the symbol and to scroll the selected code into view.
- The start of the connection line is marked by the circle representing an exit from a previous symbol, and the other end of the line marks an entry to a symbol.

#### 10.4.1 Start Symbol

- Start symbol is automatically created by the Render Chart action command. Start symbols are connected to the Execution Block symbols for the request and answer subroutines specified on the Application General Options screen (Section 9.2.3).
- If the subroutine names are not yet configured, or the configured names do not match any subroutines in the code, Start symbols are rendered in the chart with no connections and are marked with validation errors.
- Selecting the Start symbol causes the Code Text Editor to scroll to the first line of code for the connected Execution block.

#### 10.4.2 Execution Block Symbol

- The name of an Execution Block symbol is also the name of the subroutine.
- An Execution Block has one entry connection, which can proceed from one of the following symbols: Start, execution Block, or Async Call.
- An Execution Block has one or more exit connections to any of the following symbols: Execution Block, Termination, or Async Call.
- Selecting the Execution Block symbol causes the Code Text Editor to select the code for the associated subroutine and scroll it into view.

#### 10.4.3 Asynchronous Call Symbol

- The Asynchronous Call symbol displays the name of the asynchronous function that is invoked.
- An Async Call symbol always has an entry connection from an Execution Block Symbol.
- Note:** A symbol inserted by the user with no connections is ignored.
- An Async Call symbol always has an exit connection to an Execution Block that has a name, which matches the callback subroutine name input parameter to the asynchronous call.
- Selecting the Async Call symbol displays the asynchronous function call statement in the Code Text Editor.

#### 10.4.4 Termination Symbol

- The Termination symbol displays a final action name that corresponds to an occurrence of a termination call in the Execution Block connected to the Termination symbol.
- The allowed final action names are Forward, Drop, Answer.
- A Termination symbol can only have an entry connection and no exit connection.
- A Termination symbol can only be connected to the exit of an Execution Block symbol.
- Selecting the Termination symbol displays the code statement for the final action in the Code Text Editor.

#### 10.4.5 Delete symbol from the Flow Control Chart

- Right-clicking the symbol or connection in the Flow Control Chart area causes a hidden menu to be displayed.
- The menu associated with every chart symbol and connection displays the following commands:
  - Delete (selecting this command deletes the symbol or connection from the Flow Control Chart)
  - Delete is enabled only for symbols/connections created using the Toolbox commands and that are not yet associated to the code.

**Note:** Symbols and connections created using the Render Chart cannot be deleted because they are associated with code in the Code Text Editor. The associated code must be deleted first, and then Render Chart can update the Flow Control Chart to reflect the deletion.

- Rename (selecting this command enables renaming the symbol).

**Note:** Rename displays only for the exec, async, and termination blocks and not for connections.

#### 10.4.6 Flow Control Chart Validation

- The Flow Control Chart validation (validation errors show up and/or clear ) is triggered by the following events:
  - A new chart is rendered by the Render Chart command
  - Right as a change is made
- The Flow Control Chart Validation finds errors in the structure of the application code before the Compile action command is clicked.
- An error icon is displayed beside each chart symbol name that has a validation error.
- Hovering over the error icon of a symbol displays the validation error message for the symbol.
- Existing validation errors are cleared at the start of validation.
- The Flow Control Chart validates each Start symbol is connected to a single Execution Block. Otherwise, the **Start symbol has no Execution Block connection** error displays.
- The Flow Control Chart validates the Execution Block connected to a Start symbol has an exit connection that directly or indirectly leads to a Termination symbol. Otherwise, the **Starting Execution Block exit connection does not lead to a direct or indirect Termination** error displays.
- The Flow Control Chart validates each Async Call connects to a post-processing Execution Block. Otherwise, the **Async Call has no connection to a post-processing Execution Block** error displays.
- **Note:** This error message occurs when the Async Call statement in the code references a post-processing subroutine that does not exist.

#### 10.4.7 Command Output Area

- The output messages from the action commands are displayed in the Command Output text area.
- When the Command Output text area gets full, the oldest text lines are removed to make room for the new lines.
- The Command Output text area is able to display a maximum of 500 lines of text.
- The Save, Check Syntax, and Compile action commands produce log events in the system log where DSR stores all GUI log events.
- Each log event includes the user, app ID, app name, app version, and action command name.

#### 10.4.8 Render Chart

- The Render Chart action command analyzes the current application code and create a new Flow Control Chart to depict the code.
- The command output of the Render Chart action command reads “Rendering Chart...” and “Render Chart done”.
- The Render Chart action command renders chart symbols on detecting subroutines, asynchronous calls and termination calls in the application code.
- The detection of a subroutine declaration works on the following coding convention:

The declaration of a subroutine name and opening brace appear on the same line. The closing brace for the subroutine appears alone on a separate line. Example:

```
# Perl language example
sub process_request {
    # Code statements here . . .
}
```

- The detection of an asynchronous call declaration works on the following coding convention:  
For an asynchronous call statement the logical database name input argument must be passed as a literal string (quoted text) – not a variable or expression.
- For an asynchronous call statement, the callback input argument is the name of the post-processing subroutine where execution continues after the asynchronous call. The callback input argument must be passed as a literal string (quoted text) – not as a subroutine reference. For example:

```
# Perl language example
sub process_request {
    # Asynchronous call
    dca::sbr::sbrInstance("sbrDB")->read (
        $subscription_type, # key type
        $subscription_key, # key value
        "read_result" # callback to process result
    );
}
```

#### 10.4.9 Save

- The Save action command is enabled in Edit Mode if the current known Application State is Development or Trial.
- The Save action command saves the application code and Flow Control Chart to the system database.
- The command output of the Save action command reads “Saving...” and “Save done”.

#### 10.4.10 Check Syntax

- The Check Syntax action command makes the Perl interpreter check the syntax of the last saved code and report any syntax errors.
- The Check Syntax action command is enabled in Edit Mode if the current known Application State is Development or Trial and the application code and chart have been saved.
- Click **Check Syntax** to retrieve the latest application data and compare current application data.

#### 10.4.11 Compile

- The Compile action command compiles the application code and is enabled in Edit mode if the current known Application State is Trial, and this action command has not been run since the last Check Syntax Action command was executed.
- The command output of the Compile action command reads “Compiling...” and “Compile done”.

### 10.5 Race Conditions

- If multiple users are changing the application version code/flowchart simultaneously, only the first one is able to submit the changes (commands Save, Check Syntax, Compile). If the rest are trying to

submit the changes, the flowchart checksum validation fails and they would not be able to overwrite the code/flowchart in the database.

- If the Save action command is clicked while the current application state is Development or Trial, and the last-saved checksum has changed, saving is aborted and the error message displays:

"Action command 'Check Save' aborted. A newer version of the application code and Flow Control Chart has been saved in the system.

Select OK to overwrite the latest saved data.

Select Cancel to close without overwriting."

If the user confirms, overwrite the latest version of the code and Flow Control chart with the current application data.

- If the Check Syntax action command is clicked while the current application state is Development or Trial, and the last-saved checksum has changed, checking syntax is aborted and the error message displays:

"Action command 'Check Syntax' aborted. A newer version of the application code and Flow Control Chart has been saved in the system.

Select OK to overwrite the latest saved data.

Select Cancel to close without overwriting."

If the user confirms, overwrite the latest version of the code and Flow Control chart with the current application data.

- If the Compile action command is clicked while the current application state is Trial, and the last-saved checksum has changed, compiling is aborted and the error message displays:

"Action command 'compile' aborted. A more recent version of the code and Flow Control Chart exists. Do you want to overwrite the current code and Flow Control chart with the latest data?"

If the user confirms, overwrite the latest version of the code and Flow Control chart with the current application data.

- If multiple users are working with the application version, and there is an attempt to submit the code/flowchart changes (commands Save, Check Syntax, Compile) while the application state has changed and now is inappropriate for the code/flowchart update, the error occurs. (The web application running in the browser polls the web server every 10 seconds to get the latest application data and check for an application state change. The enabled/disabled state of **Save/Check Syntax/Compile** is only accurate within a 10 seconds time window).

- If **Save** is clicked while the current application state is Production or Archived, saving is aborted and the error message displays:

"Action command 'Save' aborted. The Application Version Status has changed from '<state>' to '<state>' which is invalid for the action command."

A confirmation dialog box displays with **Ok** and **Cancel** and the following text:

"The Application Version Status has changed from '<state>' to '<state>'.

You will now be switched to View Mode and will not be able to save changes.

Select OK to load and view the latest saved data.

Select Cancel to continue viewing the current data."

If the user confirms, the current code and Flow Control chart is overwritten with the latest data.

- If the Check Syntax action command is clicked while the current application state is Production or Archived, checking syntax is aborted and the error message displays:

"Action command 'Check Syntax' aborted. The Application Version Status has changed from '<state>' to '<state>' which is invalid for the action command."

A confirmation dialog box displays **OK** and **Cancel** and the following text:

"The Application Version Status has changed from '<state>' to '<state>'.

You will now be switched to View Mode and will not be able to save changes.

Select OK to load and view the latest saved data.

Select Cancel to continue viewing the current data."

If the user confirms, overwrite the current code and Flow Control chart with the latest data.

- If the Compile action command is clicked while the current application state is Development, Production or Archived, compiling is aborted and the error message displays:

"Action command 'Compile' aborted. The Application Version Status has changed from '<state>' to '<state>' which is invalid for the action command."

## 11. APIs

This chapter documents the various APIs available to a DCA programmer.

### 11.1 The EDL API

#### 11.1.1 API to Manipulate the Diameter Header

**Purpose:** Retrieve the Diameter message object needed for subsequent operations on the Diameter message header and body.

**Prototype:**

```
my $msg = diameter::Param::message($param);
```

where \$param is a default parameter provided by all the event handlers and may be retrieved with:

```
my $param = shift;
```

**Purpose:** Read the Diameter version number in the Diameter header.

**Prototype:**

```
my $ver = diameter::Message::version($msg);
```

where \$ver is undef in case of failure (for example, wrong object passed in \$msg) or the Diameter version number if success.

**Purpose:** Set the Diameter version number in the Diameter header.

**Prototype:**

```
$err = diameter::Message::setVersion($msg, $ver);
```

where \$err is undef in case of failure (for example, wrong object passed in \$msg) or a non-zero value in case of success.

**Purpose:** Return the length (as number of bytes) of the Diameter message.

**Prototype:**

```
my $len = diameter::Message::messageLength($msg);
```

where \$len is undef in case of failure (for example, wrong object passed in \$msg) or the length of the Diameter message if success

**Purpose:** Read the Command Flags of the Diameter message.

**Prototype:**

```
my $cmdFlags = diameter::Message::commandFlags($msg);
```

where \$cmdFlags is undef in case of failure (for example, wrong object passed in \$msg) or the Command Flags if success.

**Purpose:** Read the Request flag of the Diameter message.

**Prototype:**

```
my $r = diameter::Message::isRequest($msg);
```

where \$r is 1 if the Request flag is set, 0 if the Request flag is not set, or undef if error (for example, wrong object passed in \$msg).

**Purpose:** Read the Diameter Proxiable flag in the Diameter header.

**Prototype:**

```
my $p = diameter::Message::isProxiable($msg);
```

where \$p is 1 if the Proxiable flag is set, 0 if the Proxiable flag is not set or undef if error (for example, wrong object passed in \$msg).

**Purpose:** Set (set to 1) the Diameter Proxiable flag in the Diameter header.

**Prototype:**

```
$err = diameter::Message::setProxiable($msg);
```

where \$err is undef if error (for example, wrong object passed in \$msg) or a non-zero value if success.

**Purpose:** Clear (set to 0) the Diameter Proxiable flag in the Diameter header.

**Prototype:**

```
$err = diameter::Message::clearProxiable($msg);
```

where \$err is undef if error (for example, wrong object passed in \$msg) or a non-zero value if success.

**Purpose:** Read the Diameter Error flag in the Diameter header.

**Prototype:**

```
my $e = diameter::Message::isError($msg)
```

where \$e is 1 if the Error flag is set, 0 if the Error flag is not set or undef if error (for example, wrong object passed in \$msg).

**Purpose:** Set (set to 1) the Diameter Error flag in the Diameter header.

**Prototype:**

```
$err = diameter::Message::setError($msg);
```

where \$err is undef if error (for example, wrong object passed in \$msg) or a non-zero value if success.

**Purpose:** Clear (set to 0) the Diameter Error flag in the Diameter header.

**Prototype:**

```
$err = diameter::Message::clearError($msg);
```

where \$err is undef if error (for example, wrong object passed in \$msg) or a non-zero value if success.

**Purpose:** Read the Diameter Retransmission flag in the Diameter header.

**Prototype:**

```
my $t = diameter::Message::isRetransmission($msg);
```

where \$t is 1 if the Retransmission flag is set, 0 if the Retransmission flag is not set or undef if error (for example, wrong object passed in \$msg).

**Purpose:** Set (set to 1) the Diameter Retransmission flag in the Diameter header.

**Prototype:**

```
$err = diameter::Message::setRetransmission($msg);
```

where \$err is undef if error (for example, wrong object passed in \$msg) or a non-zero value if success.

**Purpose:** Clear (set to 0) the Diameter Retransmission flag in the Diameter header.

**Prototype:**

```
$err = diameter::Message::clearRetransmission($msg);
```

where \$err is undef if error (for example, wrong object passed in \$msg) or a non-zero value if success.

**Purpose:** Read the Diameter 4<sup>th</sup> reserved bit of the Command Flags in the Diameter header.

**Prototype:**

```
my $r4 = diameter::Message::isReservedBit4($msg);
```

where \$t is 1 if the 4<sup>th</sup> bit in the Command Flags flag is set, 0 if the bit is not set or undef if error (for example, wrong object passed in \$msg).

**Purpose:** Set (set to 1) the Diameter 4<sup>th</sup> reserved bit of the Command Flags in the Diameter header.

**Prototype:**

```
$err = diameter::Message::setReservedBit4($msg);
```

where \$err is undef if error (for example, wrong object passed in \$msg) or a non-zero value if success.

**Purpose:** Clear (set to 0) the Diameter 4<sup>th</sup> reserved bit of the Command Flags in the Diameter header.

**Prototype:**

```
$err = diameter::Message::clearReservedBit4($msg);
```

where \$err is undef if error (for example, wrong object passed in \$msg) or a non-zero value if success.

**Purpose:** Read/Set/Clear the Diameter 5<sup>th</sup>, 6<sup>th</sup>, and 7<sup>th</sup> reserved bit in the Command Flags in the Diameter header.

**Prototype:**

See three examples above where the Bit4 suffix in the function names is accordingly replaced by Bit5, Bit6, and Bit7, respectively.

**Purpose:** Read the Diameter Command Code in the Diameter header.

**Prototype:**

```
my $cmd = diameter::Message::commandCode($msg);
```

where \$cmd is undef if error (for example, wrong object passed in \$msg) or contains the Command Code if success.

**Purpose:** Set the Diameter Command Code in the Diameter header.

**Prototype:**

```
$err = diameter::Message::setCommandCode($msg, $cmd);
```

where \$err is undef if error (for example, wrong object passed in \$msg) or a non-zero value if success.

**Purpose:** Read the Diameter Application-ID in the Diameter header.

**Prototype:**

```
my $appId = diameter::Message::applicationId($msg);
```

where \$appId is undef if error (for example, wrong object passed in \$msg) or contains the Application-ID if success.

**Purpose:** Set the Diameter Application-ID in the Diameter header.

**Prototype:**

```
$err = diameter::Message::setApplicationId($msg, $appId);
```

where \$err is undef if error (for example, wrong object passed in \$msg) or a non-zero value if success.

**Purpose:** Read the Diameter Hop-by-Hop Identifier in the Diameter header.

**Prototype:**

```
my $hbb = diameter::Message::hopByHopId($msg);
```

where \$hbb is undef if error (for example, wrong object passed in \$msg) or contains the Hop-by-Hop Identifier if success.

**Purpose:** Set the Diameter Hop-by-Hop Identifier in the Diameter header.

**Prototype:**

```
$err = diameter::Message::setHopByHopId($msg, $hbb);
```

where \$err is undef if error (for example, wrong object passed in \$msg) or a non-zero value if success.

**Purpose:** Read the Diameter End-to-End Identifier in the Diameter header.

**Prototype:**

```
my $err = diameter::Message::endToEndId($msg);
```

where \$err is undef if error (for example, wrong object passed in \$msg) or contains the End-to-End Identifier if success.

**Purpose:** Set the Diameter End-to-End Identifier in the Diameter header.

**Prototype:**

```
$err = diameter::Message::setEndToEndId($msg, $e2e);
```

where \$err is undef if error (e.g wrong object passed in \$msg) or a non-zero value if success.

## 11.1.2 API to Manipulate the Diameter AVPs

**Purpose:** Read from a Diameter message the value of an AVP identified by name and instance number.

**Prototype:**

```
my $val = diameter::Message::getAvpValue($msg, $avp_name [, $instance]);
```

The return values are:

- `undef` if `$instance` is 0.
- `undef` if there are less instances of the AVPin the Diameter message than the `$instance` value or an AVP with the specified name does not exist in the Diameter message or the AVP name is not specified in the AVP Dictionary.
- The value of the `$instance`-th instance of the AVP (starting from 1).
- The value of the first instance of the AVP if `$instance` has been omitted.
- `undef` if `$msg` does not contain a `diameter::Message` or `diameter::GroupedAvp` object or the other parameters (if any) are `undef`.

**Purpose:** Add at the end of the Diameter message an AVP identified by name and value.

**Prototype:**

```
my $err = diameter::Message::addAvpValue($msg, $avp_name, $avp_val);
```

The return values are:

- Non-zero in case of success.
- `undef` if the AVP name does not exist in the AVP Dictionary.
- `undef` if the AVP name exists in the AVP Dictionary.
- `undef` if the AVP value cannot be converted to the AVP data type specified in the AVP Dictionary.
- `undef` if `$msg` does not contain a `diameter::Message` or `diameter::GroupedAvp` object or the other parameters (if any) are `undef`.

**Purpose:** Set the value of an AVP in a Diameter message.

**Prototype:**

```
my $err = diameter::Message::setAvpValue($msg, $avp_name, $avp_val [, $instance]);
```

If `$instance` has been omitted, the first instance of the AVP is set.

The return values are:

- Non-zero in case of success.
- `undef` if the AVP name does not exist in the AVP Dictionary.
- `undef` if the AVP name exists in the AVP Dictionary.
- `undef` if the AVP name is valid but no such AVP exists in the Diameter message.
- `undef` if `$instance` is 0.
- `undef` if the AVP exists in the Diameter message but `$instance` value is greater than the number of AVP instances in the Diameter message.
- `undef` if the AVP value cannot be converted to the AVP data type specified in the AVP Dictionary.
- `undef` if `$msg` does not contain a `diameter::Message` or `diameter::GroupedAvp` object or the other parameters (if any) are `undef`.

**Purpose:** Set the value of an existing AVP in a Diameter message or add that AVP at the end of the Diameter message if the message already contains exactly `$instance` – 1 AVPs.

**Prototype:**

```
my $err = diameter::Message::setAddAvpValue($msg, $avp_name, $avp_val [, $instance]);
```

If `$instance` has been omitted, it defaults to 1.

The return values are:

- 1 in case an AVP with the specified instance number exists and its value has been successfully set.
- 2 if the Diameter messages contains exactly `$instance - 1` AVPs of the specified type, in which case the `$instance`'s AVP is added to the end of the message.
- `undef` if the Diameter messages contains strictly less than `$instance - 1` AVPs of the specified type.
- `undef` if the AVP name does not exist in the AVP Dictionary.
- `undef` if the AVP name exists in the AVP Dictionary.
- `undef` if the AVP name is valid but the Diameter messages already contains `$instance` or more AVPs of the specified type.
- `undef` if `$instance` is 0.
- `undef` if the AVP value cannot be converted to the AVP data type specified in the AVP Dictionary.
- `undef` if `$msg` does not contain a `diameter::Message` or `diameter::GroupedAvp` object or the other parameters (if any) are `undef`.

**Purpose:** Read the value of an AVP's flag octet.

**Prototype:**

```
my $flags = diameter::Message::getAvpFlags($msg, $avp_name [, $instance]);
```

The return values are:

- The value of flags octet of the `$instance`-th instance of the AVP (starting from 1).
- The value of the first instance of the AVP if `$instance` has been omitted.
- `undef` if there are less instances of the AVP in the Diameter message than the `$instance` value.
- `undef` if `$instance` is 0.
- `undef` if an AVP with the specified name does not exist in the Diameter message.
- `undef` if the AVP name is not specified in the AVP Dictionary.
- `undef` if `$msg` does not contain a `diameter::Message` or `diameter::GroupedAvp` object or the other parameters (if any) are `undef`.

**Purpose:** Set the value of an AVP's flag octet.

**Prototype:**

```
my $err = diameter::Message::setAvpFlags($msg, $avp_name, $mask [, $instance]);
```

A 1 bit in `$mask` indicates a bit to set, while a 0 bit in `$mask` preserves the original bit value.

If `$instance` has been omitted, the flags of the first instance of the AVP is set.

The return values are:

- Non-zero in case of success.
- `undef` if the AVP name does not exist in the AVP Dictionary.
- `undef` if the AVP name is valid but no such AVP exists in the Diameter message.
- `undef` if the AVP exists in the Diameter message but `$instance` value is greater than the number of AVP instances in the Diameter message.
- `undef` if `$instance` is 0.
- `undef` if `$msg` does not contain a `diameter::Message` or `diameter::GroupedAvp` object or the other parameters (if any) are `undef`.

**Note:** The V bit preserves the original value regardless the \$mask value.

**Purpose:** Clear specific bits in an AVP's flag.

**Prototype:**

```
my $err = diameter::Message::clearAvpFlags($msg, $avp_name, $mask [, $instance]);
```

A 1 bit in \$mask indicates a bit to clear, while a 0 bit in \$mask preserves the original bit value.

If \$instance has been omitted, the flags first instance of the AVP is cleared.

The return values are:

- Non-zero in case of success.
- undef if the AVP name does not exist in the AVP Dictionary.
- undef if the AVP name is valid but no such AVP exists in the Diameter message.
- undef if the AVP exists in the Diameter message but \$instance value is greater than the number of AVP instances in the Diameter message.
- undef if \$instance is 0.
- undef if \$msg does not contain a diameter::Message or diameter::GroupedAvp object or the other parameters (if any) are undef.

**Note:** The V bit preserves the original value regardless the \$mask value.

**Purpose:** Delete an AVP identified by name, from a Diameter message.

**Prototype:**

```
my $err = diameter::Message::delAvp($msg, $avp_name [, $instance]);
```

If \$instance has been omitted, the first instance of the AVP is deleted.

The return values are:

- 1 in case AVP is deleted.
- 0 if AVP does not exist in message.
- undef if the AVP name does not exist in the AVP Dictionary.
- undef if the AVP exists in the Diameter message but \$instance value is greater than the number of AVP instances in the Diameter message.
- undef if \$instance is 0.
- undef if \$msg does not contain a diameter::Message or diameter::GroupedAvp object or the other parameters (if any) are undef.

**Purpose:** Delete all the instances of an AVP from a Diameter message.

**Prototype:**

```
my $err = diameter::Message::delAvpAll($msg, $avp_name);
```

The return values are:

- 1 in case AVP is deleted.
- 0 if AVP does not exist in message.
- undef if the AVP name does not exist in the AVP Dictionary.
- undef if \$msg does not contain a diameter::Message or diameter::GroupedAvp object or the other parameters (if any) are undef.

**Note:** The AVPs on the same nesting level are deleted, meaning, the un-grouped AVPs in a Diameter message, if the function is called with a Diameter message parameter or the AVPs in a specific

grouped AVP that are not deeper nested in a further grouped AVP, if the function is called with a Grouped AVP parameter.

**Purpose:** Return the number of instances of an AVP from a Diameter message.

**Prototype:**

```
my $cnt = diameter::Message::countAvp($msg, $avp_name);
```

The return values are:

- 0 if the AVP does not exist in the Diameter message.
- A strictly positive number indicating the number of occurrences of the respective AVP in the Diameter message.
- `undef` if the AVP name does not exist in the AVP Dictionary.
- `undef` if `$msg` does not contain a `diameter::Message` or `diameter::GroupedAvp` object or the other parameters (if any) are `undef`.

**Note:** The AVPs on the same nesting level are counted, meaning, the un-grouped AVPs in a Diameter message, if the function is called with a Diameter message parameter or the AVPs in a specific grouped AVP that are not deeper nested in a further grouped AVP, if the function is called with a Grouped AVP parameter.

**Purpose:** Check whether a specific AVP (instance) exists in a Diameter message.

**Prototype:**

```
my $exists = diameter::Message::avpExists($msg, $avp_name [, $instance]);
```

The return values are:

- True if `$instance` is omitted and at least one AVP with the specified name exists.
- True if `$instance` is specified and an AVP with the specified name and instance number exists.
- False if no AVP with the specified name exists in the Diameter message.
- False if `$instance` is specified, at least one AVP with the specified name exists, but the number of instances of the respective AVP is strictly less than the specified `$instance`.
- `undef` if the AVP name does not exist in the AVP Dictionary.
- `undef` if `$msg` does not contain a `diameter::Message` or `diameter::GroupedAvp` object or the other parameters (if any) are `undef`.

**Note:** The AVPs on the same nesting level are checked, meaning, the un-grouped AVPs in a Diameter message, if the function is called with a Diameter message parameter or the AVPs in a specific grouped AVP that are not deeper nested in a further grouped AVP, if the function is called with a Grouped AVP parameter.

**Purpose:** Return the length of the payload of an AVP from a Diameter message.

**Prototype:**

```
my $len = diameter::Message::avpDataLength($msg, $avp_name [, $instance]);
```

If `$instance` has been omitted, the length of the first instance of the AVP is returned.

The return values are:

- `undef` if no AVP with that name exists in the Diameter message.
- `undef` if `$instance` is specified but less than `$instance` AVPs exists in the Diameter message.
- A strictly positive number or 0, indicating the length of the payload of the indicated AVP instance.
- `undef` if the AVP name does not exist in the AVP Dictionary.

- `undef` if `$msg` does not contain a `diameter::Message` or `diameter::GroupedAvp` object or the other parameters (if any) are `undef`.

### 11.1.3 API to Manipulate the Diameter Grouped AVPs

All the API functions introduced in the previous section, work on grouped AVPs as well. For instance, the value of the Subscription-Id grouped AVP may be read with:

```
my $gVal = diameter::Message::getAvpValue($msg, "Subscription-Id");
```

and the Subscription-Id grouped AVP may be added to a Diameter message with:

```
my $err = diameter::Message::addAvpValue($msg, "Subscription-Id", $gVal);
```

Note that in this case, `$gVal` is an `OctetString` that contains both the Subscription-Id-Type and the Subscription-Id-Data AVPs.

This approach is particularly handy when the Subscriber-Id grouped AVP needs to be copied from one Diameter message to another, without having to look into the individual AVPs included in it.

However, if accessing the individual AVPs included into a grouped AVP is desired, then the `getGroupedAvp` and `addGroupedAvp` API calls provide the necessary support:

**Purpose:** Access a Grouped AVP in a Diameter message.

**Prototype:**

```
my $gAvp = diameter::Message::getGroupedAvp($msg, $avp_name [, $instance]);
```

The return values are:

- `undef` if the AVP name does not exist in the AVP dictionary.
- `undef` if AVP name exists in the AVP dictionary but it is not defined as a Grouped AVP.
- `undef` if the AVP name is valid but the Diameter message does not contain a Grouped AVP with that name.
- `undef` if the AVP name is valid but the Diameter message contains less Grouped AVPs with that name than specified in `$instance`.
- A `diameter::GroupedAvp` Grouped AVP object that corresponds to the respective instance of the Grouped AVP (or to the first instance if `$instance` is omitted).

The `$gAvp` `diameter::GroupedAvp` object can be used to manipulate the AVPs that it contains using any of the API functions introduced so far:

```
$result = diameter::GroupedAvp::<API_function>($gAvp, <API_function_params>);
```

where the `$gAvp` object of type `diameter::GroupedAvp` replaces the `$msg` object of type `diameter::Message` and `$result` represents the return parameter of the respective API function..

**Note:** `getGroupedAvp` works recursively to get a grouped AVP (`$nested_gAvp`) contained in another grouped AVP (`$gAvp`):

```
my $nested_gAvp = diameter::Message::getGroupedAvp($gAvp, $avp_name);
```

where `$gAvp` is a `diameter::GroupedAvp` object

**Purpose:** Add a Grouped AVP to the end of a Diameter message.

**Prototype:**

```
my $gAvp = diameter::Message::addGroupedAvp($msg, $avp_name);
```

where \$gAvp is a `diameter::GroupedAvp` object.

The return values are:

- `undef` if the AVP name does not exist in the AVP dictionary.
- `undef` if AVP name exists in the AVP dictionary but it is not defined as a Grouped AVP.

A `diameter::GroupedAvp` Grouped AVP object can be further used to manipulate the AVPs that it contains:

```
my $subscription_id = diameter::Message::addGroupedAvp($msg,
"Subscription-Id");

diameter::GroupedAvp::addAvpValue($subscription_id, "Subscription-Id-Type",
$avp_val);

diameter::GroupedAvp::addAvpValue($subscription_id, "Subscription-Id-
Data", $avp_val);
```

**Note:** `addGroupedAvp` works recursively to add a grouped AVP (`$nested_gAvp`) within another grouped AVP (`$gAvp`):

```
my $nested_gAvp = diameter::Message::addGroupedAvp($gAvp,
$avp_name);
```

where `$gAvp` is a `diameter::GroupedAvp` object.

## 11.2 Diameter Transaction Stateful APIs

### 11.2.1 Internal Variables

This API is primary intended to enable DCA to interact with Mediation Rules through Internal Variables. Internal Variables have been introduced by the Mediation feature and can be configured from **Main Menu: Diameter > Mediation > Internal Variables**. Internal Variables are persistent throughout the lifetime of a Diameter transaction.

**Purpose:** Access Internal Variables.

**Prototype:**

```
my $iv_ref = new diameter::InternalVarDef("<IV_Name>");

my $internalVarMap = diameter::Param::internalVarMap($param);
```

where `$param` is the opaque parameter passed to every event handler and `<IV_Name>` is the name assigned to the Internal Variable in **Main Menu: Diameter > Mediation > Internal Variables**.

**Note:** The Internal Variables are configurable at the B level, therefore the `<IV_Name>` must be configured on all the sites. Otherwise, the initialization fails when invoked on those DA-MP located in sites where `<IV_Name>` does not exist.

**Purpose:** Set and Get Internal Variables.

**Prototype:**

```
diameter::InternalVarMap::set($internalVarMap, $iv_ref, $val);

$val = diameter::InternalVarMap::get($internalVarMap, $iv_ref);
```

Enables setting values to and retrieving values from an internal variable, where `$iv_ref` and `$internalVarMap` are initialized as shown before.

## 11.2.2 Diameter Transaction Context Variables

The Diameter transaction context variables offer Diameter transaction persistent storage, similar to Internal Variables. Unlike Internal Variables, Diameter transaction context variables are not configurable via the GUI (which provides for a much simpler API) and cannot be shared with other features.

**Purpose:** Store Diameter transaction context variables

**Prototype:**

```
$err = dca::transctx::store("<var_id>", $var)
```

The function returns `undef` if `$var` is `undef` or any error occurs (for example, `$var` is a Perl hash or array that cannot be successfully encoded into JSON or DSR cannot allocate more memory space for the Diameter context variable) and 1 if the operation is successful.

**Purpose:** Retrieve Diameter transaction context variables

**Prototype:**

```
$var = dca::transctx::fetch("<var_id>");
```

`undef` is returned in case of failure (for example, `<var_id>` is not found because no variable with that name has been previously stored).

## 11.3 Read DCA Configuration Data

This API enables DCA to access its configuration data, which was specified and provisioned as described in Sections 3.3.3 and 3.3.4.

When the Perl script is generated, DCA configuration data is converted into a Perl variable. The Perl variable name is `%dca::appConfig` and is a hash (one key for each table) of arrays (one index for each record) of hashes (one key for each field in the table).

Read-only access on DCA configuration data is enforced using the `Const::Fast` CPAN module and applies to the data included in the `%dca::appConfig` definition (which is automatically generated from DCA configuration data).

Note that there are semantical differences from one `Const::Fast` version to another, which affect the way `%dca::appConfig` can be subsequently manipulated in the Perl script with regard to adding new records to `%dca::appConfig` or accessing records that are not defined in `%dca::appConfig`.

For instance, in version 0.006, which is the one currently used, an attempt to read or assign a value to an nonexistent table (outermost hash key) `%dca::appConfig` results in a runtime error.

On the other hand, assigning values to nonexistent indexes (table records) and/or nonexistent fields (innermost hash key) succeeds and can be subsequently successful read, while reading from nonexistent indexes and/or nonexistent fields return `undef`. These indexes and fields are not written back to DCA configuration data.

**Purpose:** Read DCA configuration data.

**Prototype:**

```
$dca::appConfig{"<config_table_name>"}[<row_index>]{"<field_name>"}
```

for non-“single row” configuration tables.

```
$dca::appConfig{"<config_table_name>"}{"<field_name>"}
```

for “single row” configuration tables.

**Example:** Assuming DCA defines a configuration table called “MyTable” with two fields “FieldA” and “FieldB” and provisions a few rows, it is possible to retrieve the NOAM and SOAM provisioned data from DCA in the following way:

```
for $i (0 .. $#dca::appConfig{"MyTable"}) {  
    dca::application::logInfo($dca::appConfig{"MyTable"}[$i]{"Field1"});  
    dca::application::logInfo($dca::appConfig{"MyTable"}[$i]{"Field2"});  
}
```

## 11.4 Routing API

The routing API enables DCA to perform some basic routing functions.

The `dca::action::forward()`, `dca::action::answer($ans)` and `dca::action::drop()` API functions terminate the execution of the event handler. This means that the statements that follow them in the Perl code are not executed. This also has a side effect on the U-SBR queries initiated before invoking any of `dca::action::forward()`, `dca::action::answer($ans)` and `dca::action::drop()` because, as mentioned in Section 6.3.6.2, the U-SBR queries are actually sent after the execution of the event handler completes: the side effect is the U-SBR queries are also not executed (that is, sent to the U-SBR).

Besides `dca::action::forward()`, `dca::action::answer($ans)` and `dca::action::drop()`, an event handler's execution flow also terminates (as any other Perl subroutine) when a `return` statement is encountered or when the enclosing curly bracket is reached. In this case, the implicit routing decision that the DCA framework takes depends on the Perl subroutine return value:

- If the return value is greater or equal to 0, then the Diameter message is forwarded.
- If the return value is negative, then the runtime error behavior (Section 3.3.1) is executed.

**Purpose:** Complete the processing and drop the message.

**Prototype:**

```
dca::action::drop();
```

**Note:** Invoking `dca::action::drop()` causes the event handler to immediately terminate execution.

**Purpose:** Build a Diameter Answer.

**Prototype:**

```
$ans = new dca::application::answer(<error_code>, <error_text>,  
<vendor_id>);
```

The function returns `undef` in case of failure or a `diameter::Message` object.

When receiving a Diameter request or answer this API function enables DCA to construct a Diameter answer and either return it to the originator of the corresponding Diameter request or, respectively, substitute the original Diameter answer message.

The EDL API (see Section 11.1) may be used to further process the `$ans` Diameter answer (for example, add more AVPs).

**Purpose:** Send a Diameter Answer Created by DCA.

**Prototype:**

```
dca::action::answer($ans);
```

**Note:** Invoking `dca::action::answer($ans)` causes the event handler to immediately terminate execution.

**Purpose:** Complete the processing and pass the message.

**Prototype:**

```
dca::action::forward();
```

Enables DCA to pass a Diameter message to the Diameter Routing Layer for routing.

**Note:** Invoking `dca::action::forward()` causes the event handler to immediately terminate execution.

**Purpose:** Specify an ART based on which a Diameter request is routed.

**Prototype:**

```
$err = dca::route::setART(<ART_table_name>);
```

The function returns `undef` if the name of the ART does not exist (failure) or 1 if success.

Before invoking `dca::action::forward()` on a Diameter request, this routing API function enables DCA to specify which ART to be used for routing the respective Diameter request.

**Note:** The ART is configurable at the B level; therefore, the `<ART_table_name>` must be configured on all the sites. Otherwise, the API function fails when invoked on those DA-MP located in sites where `<ART_table_name>` does not exist.

**Purpose:** Specify a PRT based on which a Diameter request is routed.

**Prototype:**

```
$err = dca::route::setPRT(<PRT_table_name>);
```

The function returns `undef` if the name of the PRT does not exist (failure) or 1 if success.

Before invoking `dca::action::forward()` on a Diameter request, this routing API function enables DCA to specify which PRT to be used for routing the respective Diameter request.

**Note:** The PRT is configurable at the B level, therefore the `<PRT_table_name>` must be configured on all the sites. Otherwise, the API function fails when invoked on those DA-MP located in sites where `<PRT_table_name>` does not exist.

## 11.5 Debugging API

The Debugging API allows tracking the execution of the event handlers by supporting the equivalent of `printf`, `log`, `echo`, etc., functions in other programming/scripting languages.

The messages are logged in the `dsr.DCA` trace file (use `tr.tail dsr.DCA`). The following masks may be applied using the `tr.set` command to filter the ERROR, INFO, and WARNING error messages: 0x00000001 (error), 0x00000002 (info) and respectively 0x00000004 (warning).

All the traces generated by DCA using the API calls is prefixed with the DCA name (to allow for further filtering, for example, using the `grep` utility).

The `log[Info|Warn|Error]` API functions also generate an IDIH trace (see Section 12).

Note, however, that in a production network DSR logs only the vital traces are therefore the main debugging tool for DCAs in production networks is the IDIH feature.

**Purpose:** Retrieve the application name.

**Prototype:**

```
$appname = dca::application::getAppName();
```

**Purpose:** Retrieve the version name

**Prototype:**

```
$vername = dca::application::getVersionName();
```

**Note:** Besides debugging, another possible use case for reading the version name is including it in the DCA state stored on the U-SBR. This supports backward compatibility in case DCA frequently changes the format of DCA across DCA versions.

**Purpose:** Retrieve the current state.

**Prototype:**

```
$verstate = dca::application::getState();
```

**Note:** The states returned can be either Trial or Production, since these are the only states when DCA is executed.

**Purpose:** Generate a trace containing user-defined messages and having a severity of INFO.

**Prototype:**

```
dca::application::logInfo(<message>);
```

The user-defined messages is logged into dsr.DCA (tr.tail dsr.DCA).

**Purpose:** Generate a trace containing user-defined messages and having a severity of WARNING.

**Prototype:**

```
dca::application::logWarn(<message>);
```

**Purpose:** Generate a trace containing user-defined messages and having a severity of ERROR

**Prototype:**

```
dca::application::logErr(<message>);
```

## 11.6 Custom MEAL API

Once the Custom MEAL objects are differentiated from the **Main Menu: DCA Framework > <DCA Name> > Custom MEALs** screen (see Section 9.2.2), they can be initialized and used from DCA.

### 11.6.1 Counter Template API

**Purpose:** DCA can bind to a Scalar Counter Custom MEAL by referring to it by the Custom MEAL configured name.

**Prototype:**

```
my $all_Cnt = new dca::meal::counter("MyCnt");
```

where "MyCnt" is the name specified when differentiating a Custom MEAL template of type **Counter** and measurement type **Scalar**.

The API call returns a valid Custom MEAL object in case of success. The Custom MEAL object may be used in subsequent API calls to perform specific operations on the Scalar Counter.

In case of failure, `undef` is returned.

Possible failure cases are:

- No Custom MEAL with the specified name is currently defined.
- A Custom MEAL with that name exists, but either the differentiation process is not yet completed, or the un-differentiation process was initiated.
- A Custom MEAL with that name exists, but it is not a Scalar Counter.

**Note:** As a matter of best practice, the initialization of the Custom MEAL objects is performed in the main body of the Perl script, which is executed once right after a successful compilation (rather than in an event handler):

```
Die "Custom MEAL differentiation failure"
```

```
unless $obj = new dca::meal::<TemplateType>("MyCustomMeal");
```

This ensures a compilation error is triggered if the binding process has failed, for instance because there is a name mismatch between the Perl script and the differentiation GUI screen. Using an undefined \$obj later in the event handlers triggers run-time errors.

**Purpose:** DCA can peg a Scalar Counter Custom MEAL.

**Prototype:**

```
$err = $all_Cnt->peg();
```

where \$all\_Cnt is a valid Scalar Counter Custom MEAL object.

The API call returns 1 if success and undef if the operation on the underlying Comcol object has failed.

**Purpose:** DCA can bind to an Arrayed Counter Custom MEAL by referring to it by the Custom MEAL configured name.

**Prototype:**

```
my $per_Cnt = new dca::meal::arrayedCounter("MyArrayedCnt");
```

where "MyArrayedCnt" is the name specified when differentiating a Custom MEAL template of type **Counter** and measurement type **Arrayed**.

The API call returns a valid Custom MEAL object in case of success. The Custom MEAL object may be used in subsequent API calls to perform specific operations on the Arrayed Counter.

In case of failure, undef is returned.

Possible failure cases are:

- No Custom MEAL with the specified name is currently defined.
- A Custom MEAL with that name exists, but either the differentiation process is not yet completed, or the un-differentiation process was initiated.
- A Custom MEAL with that name exists, but it is not an Arrayed Counter.

**Purpose:** DCA can peg a specific index of an Arrayed Counter Custom MEAL.

**Prototype:**

```
$err = $per_Cnt->peg($index);
```

where \$per\_Cnt is a valid Arrayed Counter Custom MEAL object and \$index is the index to be pegged.

The API call returns 1 if success and undef if the either operation on the underlying Comcol object has failed or the index value is negative.

## 11.6.2 Rate Template

**Purpose:** DCA can bind to a Scalar Rate Custom MEAL by referring to it by the Custom MEAL configured name.

**Prototype:**

```
my $all_Rate = new dca::meal::rate("MyRate");
```

where "MyRate" is the name specified when differentiating a Custom MEAL template of type **Rate** and measurement type **Scalar**.

The API call returns a valid Custom MEAL object in case of success. The Custom MEAL object may be used in subsequent API calls to perform specific operations on the Scalar Rate.

In case of failure, undef is returned.

Possible failure cases are:

- No Custom MEAL with the specified name is currently defined.
- A Custom MEAL with that name exists, but either the differentiation process is not yet completed, or the un-differentiation process was initiated.
- A Custom MEAL with that name exists, but it is not a Scalar Rate.

**Purpose:** DCA can peg a Scalar Rate Custom MEAL.

**Prototype:**

```
$err = $all_Rate->peg();
```

where \$all\_Rate is a valid Scalar Rate Custom MEAL object.

The API call returns 1 if success and `undef` if the operation on the underlying Comcol object has failed.

**Purpose:** DCA can read the current value of a Scalar Rate Custom MEAL.

**Prototype:**

```
$val = $all_Rate->readRate();
```

where \$all\_Rate is a valid Scalar Rate Custom MEAL object.

The API call returns an integer representing the current value in case of success and `undef` if the operation on the underlying Comcol object has failed.

**Purpose:** DCA can read the average value of a Scalar Rate Custom MEAL.

**Prototype:**

```
$val = $all_Rate->readAvgRate();
```

where \$all\_Rate is a valid Scalar Rate Custom MEAL object.

The API call returns an integer representing the average value in case of success and `undef` if the operation on the underlying Comcol object has failed.

**Purpose:** DCA can determine the current severity of the alarm associated to an Scalar Rate template.

**Prototype:**

```
$err = $all_Rate->getSeverity();
```

where \$all\_Rate is a valid Scalar Rate Custom MEAL object.

The API call returns:

```
dca::meal::Critical, dca::meal::Major, dca::meal::Minor,  
dca::meal::Cleared
```

`undef` if the operation on the underlying Comcol object has failed.

**Note:** The severity values are defined as:

```
use constant {  
    Cleared    => 0,  
    Info       => 1,  
    Minor      => 2,  
    Major      => 3,  
    Critical   => 4,  
};
```

which enables comparing them. For instance:

```
if ($all_Rate->getSeverity() >= dca::meal::Major)
```

is true if the severity is Major or Critical and is false if the severity is Minor. This also applies to Basic as well as arrayed templates.

**Purpose:** DCA can bind to an Arrayed Rate Custom MEAL by referring to it by the Custom MEAL configured name.

**Prototype:**

```
my $per_Rate = new dca::meal::arrayedRate("MyArrayedRate");
```

where "MyArrayedRate" is the name specified when differentiating a Custom MEAL template of type **Rate** and measurement type **Arrayed**.

The API call returns a valid Custom MEAL object in case of success. The Custom MEAL object may be used in subsequent API calls to perform specific operations on the Arrayed Rate.

In case of failure, `undef` is returned.

Possible failure cases are:

- No Custom MEAL with the specified name is currently defined.
- A Custom MEAL with that name exists, but either the differentiation process is not yet completed, or the un-differentiation process was initiated.
- A Custom MEAL with that name exists, but it is not an Arrayed Rate.

**Purpose:** DCA can peg a specific index of an Arrayed Rate Custom MEAL.

**Prototype:**

```
$err = $per_Rate->peg($index);
```

where `$per_Rate` is a valid Arrayed Rate Custom MEAL object and `$index` is the index to be pegged.

The API call returns 1 if success and `undef` if either the operation on the underlying Comcol object has failed or the index value is negative.

**Purpose:** DCA can read the current value of a specific index of an Arrayed Rate Custom MEAL.

**Prototype:**

```
$val = $per_Rate->readRate($index);
```

where `$per_Rate` is a valid Arrayed Rate Custom MEAL object and `$index` is the index the current value of which is read.

The API call returns an integer representing the current value of the specified index in case of success and `undef` if either the operation on the underlying Comcol object has failed or the index value is negative.

**Purpose:** DCA can read the average value of a specific index of an Arrayed Rate Custom MEAL.

**Prototype:**

```
$val = $per_Rate->readAvgRate($index);
```

where `$per_Rate` is a valid Arrayed Rate Custom MEAL object and `$index` is the index the average value of which is pegged.

The API call returns an integer representing the average value of the specified index in case of success and `undef` if either the operation on the underlying Comcol object has failed or the index value is negative.

**Purpose:** DCA can determine the current severity of the alarm associated to an Arrayed Rate template:

**Prototype:**

```
$err = $per_Rate->getSeverity($index);
```

where `$per_Rate` is a valid Arrayed Rate Custom MEAL object and `$index` identifies the particular index the alarm status of which is read.

The API call returns:

```
dca::meal::Critical, dca::meal::Major, dca::meal::Minor,
dca::meal::Cleared
```

`undef` if either the operation on the underlying Comcol object has failed or the index value is negative.

### 11.6.3 Basic Template

**Purpose:** DCA can bind to a Scalar Basic Custom MEAL by referring to it by the Custom MEAL configured name.

**Prototype:**

```
my $all_Size = new dca::meal::basic("MyBasic");
```

where “`MyBasic`” is the name specified when differentiating a Custom MEAL template of type **Basic** and measurement type **Scalar**.

The API call returns a valid Custom MEAL object in case of success. The Custom MEAL object may be used in subsequent API calls to perform specific operations on the Scalar Basic template.

In case of failure, `undef` is returned.

Possible failure cases are:

- No Custom MEAL with the specified name is currently defined.
- A Custom MEAL with that name exists, but either the differentiation process is not yet completed, or the un-differentiation process was initiated.
- A Custom MEAL with that name exists, but it is not a Scalar Basic.

**Purpose:** DCA can set the value of a Scalar Basic Custom MEAL.

**Prototype:**

```
$err = $all_Size->setValue($value);
```

where `$all_Size` is a valid Scalar Basic Custom MEAL object and `$value` is the value the Scalar Basic Custom MEAL is set to.

The API call returns 1 if success and `undef` if the operation on the underlying Comcol object has failed.

**Purpose:** DCA can increment the value of a Scalar Basic Custom MEAL.

**Prototype:**

```
$err = $all_Size->increment($count);
```

where `$all_Size` is a valid Scalar Basic Custom MEAL object and `$count` is the value the Scalar Basic Custom MEAL is incremented with.

The API call returns 1 if success and `undef` if the operation on the underlying Comcol object has failed.

**Purpose:** DCA can decrement the value of a Scalar Basic Custom MEAL.

**Prototype:**

```
$err = $all_Size->decrement($count);
```

where `$all_Size` is a valid Scalar Basic Custom MEAL object and `$count` is the value the Scalar Basic Custom MEAL is decremented with.

The API call returns 1 if success and `undef` if the operation on the underlying Comcol object has failed.

**Purpose:** DCA can read the current value of a Scalar Basic Custom MEAL.

**Prototype:**

```
$val = $all_Size->getValue();
```

where `$all_Size` is a valid Scalar Basic Custom MEAL object.

The API call returns an integer representing the current value in case of success and `undef` if the operation on the underlying Comcol object has failed.

**Purpose:** DCA can read the average value of a Scalar Basic Custom MEAL.

**Prototype:**

```
$val = $all_Size->getAvgValue();
```

where `$all_Size` is a valid Scalar Basic Custom MEAL object.

The API call returns an integer representing the average value in case of success and `undef` if the operation on the underlying Comcol object has failed.

**Purpose:** DCA can determine the current severity of the alarm associated to an Scalar Basic template.

**Prototype:**

```
$err = $all_Size->getSeverity();
```

where `$all_Size` is a valid Scalar Basic Custom MEAL object.

The API call returns:

`dca::meal::Critical, dca::meal::Major, dca::meal::Minor, dca::meal::Cleared`

`undef` if the operation on the underlying Comcol object has failed.

**Purpose:** DCA can bind to an Arrayed Basic Custom MEAL by referring to it by the Custom MEAL configured name.

**Prototype:**

```
my $per_Size = new dca::meal::arrayedBasic("MyArrayedBasic");
```

where `"MyArrayedBasic"` is the name specified when differentiating a Custom MEAL template of type **Basic** and measurement type **Arrayed**.

The API call returns a valid Custom MEAL object in case of success. The Custom MEAL object may be used in subsequent API calls to perform specific operations on the Arrayed Basic template.

In case of failure, `undef` is returned.

Possible failure cases are:

- No Custom MEAL with the specified name is currently defined.
- A Custom MEAL with that name exists, but either the differentiation process is not yet completed, or the un-differentiation process was initiated.
- A Custom MEAL with that name exists, but it is not an Arrayed Basic.

**Purpose:** DCA can set the value of an Arrayed Basic Custom MEAL.

**Prototype:**

```
$err = $per_Size->setValue($value, $index);
```

where `$per_Size` is a valid Arrayed Basic Custom MEAL object, `$index` is the index the value of which is set and `$value` is the value it is set to.

The API call returns 1 if success and `undef` if either the operation on the underlying Comcol object has failed or the index value is negative.

**Purpose:** DCA can increment the value of an Arrayed Basic Custom MEAL.

**Prototype:**

```
$err = $per_Size->increment($count, $index);
```

where `$per_Size` is a valid Arrayed Basic Custom MEAL object, `$index` is the index the value of which is incremented and `$count` is the value it is incremented with.

The API call returns 1 if success and `undef` if either the operation on the underlying Comcol object has failed or the index value is negative.

**Purpose:** DCA can decrement the value of an Arrayed Basic Custom MEAL.

**Prototype:**

```
$err = $per_Size->decrement($count, $index);
```

where `$per_Size` is a valid Arrayed Basic Custom MEAL object, `$index` is the index the value of which is decremented and `$count` is the value it is decremented with.

The API call returns 1 if success and `undef` if either the operation on the underlying Comcol object has failed or the index value is negative.

**Purpose:** DCA can read the current value of an Arrayed Basic Custom MEAL.

**Prototype:**

```
$val = $per_Size->getValue($index);
```

where `$per_Size` is a valid Arrayed Basic Custom MEAL object and `$index` is the index the value of which is read.

The API call returns an integer representing the current value of the specified index in case of success and `undef` if either the operation on the underlying Comcol object has failed or the index value is negative.

**Purpose:** DCA can read the average value of an Arrayed Basic Custom MEAL.

**Prototype:**

```
$val = $per_Size->getAvgValue($index);
```

where `$per_Size` is a valid Arrayed Basic Custom MEAL object and `$index` is the index the average value of which is read.

The API call returns an integer representing the average value of the specified index in case of success and `undef` if either the operation on the underlying Comcol object has failed or the index value is negative.

**Purpose:** DCA can determine the current severity of the alarm associated to an Arrayed Basic template.

**Prototype:**

```
$err = $per_Size->getSeverity($index);
```

where `$per_Size` is a valid Arrayed Basic Custom MEAL object and `$index` identifies the particular index the alarm status of which is read.

The API call returns:

```
dca::meal::Critical, dca::meal::Major, dca::meal::Minor,  
dca::meal::Cleared
```

`undef` if either the operation on the underlying Comcol object has failed or the index value is negative.

#### 11.6.4 Event Template

**Purpose:** DCA can bind to an Event Custom MEAL by referring to it by the Custom MEAL configured name.

**Prototype:**

```
my $errorEvent = new dca::meal::event("MyEvent");  
where "MyEvent" is the name specified when differentiating a Custom MEAL template of type Event.
```

The API call returns a valid Custom MEAL object in case of success. The Custom MEAL object may be used in subsequent API calls to perform specific operations on the Event.

In case of failure, `undef` is returned.

Possible failure cases are:

- No Custom MEAL with the specified name is currently defined.
- A Custom MEAL with that name exists, but either the differentiation process is not yet completed, or the un-differentiation process was initiated.
- A Custom MEAL with that name exists, but it is not a Event.

**Purpose:** DCA can generate an event (Info severity), raise an alarm (Minor, Major, Critical severity) and clear an alarm (Clear severity).

**Prototype:**

```
$err = $errorEvent->log($severity, $addInfoText);
```

where `$errorEvent` is a valid Event Custom MEAL object, `$severity` is one of the possible values (dca::meal::Critical, dca::meal::Major, dca::meal::Minor, dca::meal::Cleared), and `$addInfoText` is the text that should be included in the alarm's additional information field.

The API call returns 1 if success and `undef` if the operation on the underlying Comcol object has failed.

**Purpose:** DCA can determine whether an event or alarm is throttled before trying to raise it (again).

**Prototype:**

```
$err = $errorEvent->isThrottled($severity);
```

where `$errorEvent` is a valid Event Custom MEAL object and `$severity` is one of the possible values (dca::meal::Critical, dca::meal::Major, dca::meal::Minor, dca::meal::Info).

The API call returns:

- 1 if the event/alarm is throttled.
- 0 if the event/alarm is not throttled.
- `undef` if the operation on the underlying Comcol object has failed.

**Purpose:** DCA can determine the current severity of an event or alarm:

**Prototype:**

```
$err = $errorEvent->getSeverity();
```

where `$errorEvent` is a valid Event Custom MEAL object.

The API call returns:

```
dca::meal::Critical, dca::meal::Major, dca::meal::Minor, dca::meal::Info,  
dca::meal::Cleared
```

`undef` if the operation on the underlying Comcol object has failed.

## 11.7 U-SBR API

The U-SBR API enables DCA to create, read, update, and delete data in a U-SBR DB. As described in Section 6.3.6.2 the U-SBR API calls work asynchronously and a callback subroutine is necessary to fetch the result of the query.

## 11.7.1 The Prototype of Queries and Query Results

This section describes the common structure of the U-SBR API functions and how the results of a U-SBR query can be retrieved in the Perl script.

Section 11.7.2 further describes the particularities of each individual U-SBR API function.

### 11.7.1.1 Specifying the Query

All the U-SBR API functions share a common prototype:

```
$err = dca::sbr::sbrInstance(<usbr_logical_name>) -><API_function>(
    <key_type>, <key_data_type>, $key,
    <value_data_type>, $value,
    <callback_subroutine>,
    [<flags>]);
```

where:

- <usbr\_logical\_name> is a string (a constant value or a scalar variable) containing the logical name of the U-SBR DB the query is sent to. The logical names for the physical U-SBR DBs are configured from **Main Menu: DCA Framework > <DCA Name> > Application Control**, by selecting the DCA version and clicking on **SBR DB Name Mapping**.
- <API\_function> is one of: create, createOrRead, read, update, concurrentUpdate, and delete, respectively.
- <key\_type> is typically a constant value defined by DCA. It distinguishes between different key types DCA may use (for example, IMSI, NAI, IP, IP\_SRC, etc.). For example, the key value "fred" of type **NAI** is a different key from 66.72.65.64 of type **IP**, even though they have the same binary representation.
- <key\_data\_type> is pre-defined constant that describes the data type of the key and must be one of:
  - dca::sbr::KeyDataType::BCD – the key is a scalar.
  - dca::sbr::KeyDataType::UINT32 – the key is a scalar.
  - dca::sbr::KeyDataType::INT64 – the key is a scalar.
  - dca::sbr::KeyDataType::STRING – the key is a scalar.
  - dca::sbr::KeyDataType::IPv4 – the key is a NetAddr::IP object.
  - dca::sbr::KeyDataType::IPv6 – the key is a NetAddr::IP object.

**Note:** There is no explicit data type for float numbers; float numbers are converted to strings.

- \$key is a Perl variable that holds the key part of the key-value pair to be created, read, updated or deleted.
- <value\_data\_type> is pre-defined constant that describes the data type of the key and must be one of:
  - dca::sbr::StateDataType::BCD – the key is a scalar.
  - dca::sbr::StateDataType::UINT32 – the key is a scalar.
  - dca::sbr::StateDataType::STRING – the key is a scalar, an array reference or a hash reference.

**Note:** Arrays and hashes are encoded into JSON and stored in the U-SBR DB in string format.

- dca::sbr::StateDataType::IPv4 – the key is a NetAddr::IP object.
- dca::sbr::StateDataType::IPv6 – the key is a NetAddr::IP object.

**Note:** There is no explicit data type for float numbers; float numbers are converted to strings.

- `$value` is a Perl variable that holds the value part of the key-value pair to be written into the U-SBR (via create or update operations). Note, therefore, that read and delete do not specify a `$value` parameter and as a result no `<value_data_type>` parameter.
- `<callback_subroutine>` is a string representing the name of the Perl subroutine that are invoked by the DCA framework to deliver the query result,
- `<flags>` is an optional OR-mask of predefined flags that may apply to certain API functions.

The API call returns:

- 1 if the parameters are successfully parsed and encoding into a Stack Event.
- Note that, because the API call works asynchronously, at this stage the query has not been sent yet, its outcome cannot be known, `$err` merely tells whether a query could be successfully built.
- `undef` if parsing or encoding the parameters fails.

### 11.7.1.2 Retrieving the Query Result

The result of a U-SBR query can be retrieved in the callback function by using the `dca::sbr::result()` class. An error code is always returned and some queries also return data (consisting of the data type along with the data itself):

- `$err_code = dca::sbr::result()->code();`

Retrieves the error code. If the error codes indicates success (`dca::sbr::ResultCode::Ok`) then **some** API functions also return data, which can be retrieved using the `dataType()` and `data()` methods described below.

A number of error codes are common to all U-SBR API functions:

- `dca::sbr::ResultCode::Ok` – indicates the query has successfully executed the intended operation;
- `dca::sbr::ResultCode::DBError` – an error occurred on the SBR side that prevented the query to be executed;
- `dca::sbr::ResultCode::SendError` – an error occurred when attempting to send the query, typically because of ComAgent overload (ComAgent related alarms are raised in this case);
- `dca::sbr::ResultCode::LogicalNameMismatch` – indicates that no mappings to physical U-SBR DBs have been configured for the logical name used in the `<usbr_logical_name>` parameter. Alarm 33313 is raised;
- `dca::sbr::ResultCode::AccessError` – occurs when (i) the physical U-SBR DBs, to which the `<usbr_logical_name>` parameter is mapped to, are owned by another DCA (see **Main Menu: SBR > Configuration > SBR Databases**, Owner Application column) and (ii) the current DCA is configured to access the physical U-SBR DBs owned by other DCAs only in read-only mode (see **Main Menu: DCA Framework > <DCA Name> > General Options, Read-Only U-SBR Access as Guest** option);
- `dca::sbr::ResultCode::MaxStateSize` – the size of either the key or the data DCA attempts to look up or respectively store in the U-SBR DB, exceeds the configured maximum sizes (**Main Menu: DCA Framework > Configuration, Maximum Size of Application State** and respectively **Maximum Size of the Key** options);
- `dca::sbr::ResultCode::MaxEventReached` – the maximum number of U-SBR queries that a Diameter message event handler is allowed to send has been exceeded (see **Main Menu: DCA Framework > <DCA Name> > General Options, Max. U-SBE Queries per Message** option).

A few error codes (`dca::sbr::ResultCode::GenericErrRecExists`, `dca::sbr::ResultCode::GenericErrRecNotFound` and `dca::sbr::ResultCode::GenericErrRecObsolete`) are specific to certain U-SBR API functions.

```
$data_type = dca::sbr::result()->dataType();
```

If the result contains data, then datatype() returns the data type of the stored data, that is, one of:  
 dca::sbr::StateDataType::BCD, dca::sbr::StateDataType::UINT32,  
 dca::sbr::StateDataType::INT64, dca::sbr::StateDataType::STRING,  
 dca::sbr::StateDataType::IPv4, dca::sbr::StateDataType::IPv6;

If the result contains **no data**, then datatype() returns undef.

```
$data = dca::sbr::result()->data();
```

If the result contains data, then data() returns the stored data.

If the result contains **no data**, then data() returns undef.

## 11.7.2 The U-SBR API Functions

**Purpose:** Attempts to create a key-value record in a U-SBR DB or fails if a record with the same key already exists.

**Prototype:** (see also Section 11.7.1.1)

```
$err = dca::sbr::sbrInstance(<usbr_logical_name>)->create(
    <key_type>, <key_data_type>, $key,
    <value_data_type>, $value,
    <callback_subroutine>);
```

**Query Results:** The possible result of the create API function are described in the table below (see also Section 11.7.1.2):

dca::sbr::result()->code()	dca::sbr::result()->dataType()	dca::sbr::result()->data()
dca::sbr::ResultCode::Ok (The record does not exist and was created)	N/A <sup>1</sup>	N/A
dca::sbr::ResultCode::DBError, dca::sbr::ResultCode::SendError dca::sbr::ResultCode::LogicalNameMismatch dca::sbr::ResultCode::AccessError dca::sbr::ResultCode::MaxStateSize dca::sbr::ResultCode::MaxEventReached	N/A	N/A
dca::sbr::ResultCode::ErrRecExists	N/A	N/A

**Purpose:** Creates a key-value record in a U-SBR DB or returns the record, if a record with the same key already exists.

**Prototype:** (see also Section 11.7.1.1)

```
$err = dca::sbr::sbrInstance(<usbr_logical_name>)->createOrRead(
    <key_type>, <key_data_type>, $key,
    <value_data_type>, $value,
    <callback_subroutine>);
```

**Query Results:** The possible result of the create API function are described in the table below (see also Section 11.7.1.2):

---

<sup>1</sup> The programmer does not rely on the returned variable being defined, undefined, or having any particular value.

<b>dca::sbr::result()-&gt;code()</b>	<b>dca::sbr::result() -&gt;dataType()</b>	<b>dca::sbr::result() -&gt;data()</b>
dca::sbr::resultCode::Ok (The record does not exist and was created)	N/A	N/A
dca::sbr::resultCode::DBError, dca::sbr::resultCode::SendError dca::sbr::resultCode::LogicalNameMismatch dca::sbr::resultCode::AccessError dca::sbr::resultCode::MaxStateSize dca::sbr::resultCode::MaxEventReached	N/A	N/A
dca::sbr::resultCode::ErrRecExists	The data type of the existing record	The existing record

**Purpose:** Reads the value associated to a key from the U-SBR DB, or fails if the key is not found.

**Prototype:** (see also Section 11.7.1.1)

```
$err = dca::sbr::sbrInstance(<usbr_logical_name>)->read(  
    <key_type>, <key_data_type>, $key,  
    <callback_subroutine>);
```

Note that no \$value parameter is present since no value is supposed to be written into the U-SBR DB.

**Query Results:** The possible result of the create API function are described in the table below (see also Section 11.7.1.2):

<b>dca::sbr::result()-&gt;code()</b>	<b>dca::sbr::result() -&gt;dataType()</b>	<b>dca::sbr::result() -&gt;data()</b>
dca::sbr::resultCode::Ok (The record exists and was read)	The data type of the existing record	The existing record
dca::sbr::resultCode::DBError, dca::sbr::resultCode::SendError dca::sbr::resultCode::LogicalNameMismatch dca::sbr::resultCode::AccessError dca::sbr::resultCode::MaxStateSize dca::sbr::resultCode::MaxEventReached	N/A	N/A
dca::sbr::resultCode::ErrRecNotFound	N/A	N/A

**Purpose:** Attempts to update the value associated with a key in the U-SBR DB or fails if a record with the key could not be found.

**Prototype:** (see also Section 11.7.1.1)

```
$err = dca::sbr::sbrInstance(<usbr_logical_name>)->update(  
    <key_type>, <key_data_type>, $key,  
    <value_data_type>, $value,  
    <callback_subroutine>);
```

**Query Results:** The possible result of the create API function are described in the table below (see also Section 11.7.1.2):

<b>dca::sbr::result()-&gt;code()</b>	<b>dca::sbr::result() -&gt;dataType()</b>	<b>dca::sbr::result() -&gt;data()</b>

<b>dca::sbr::result()-&gt;code()</b>	<b>dca::sbr::result() -&gt;dataType()</b>	<b>dca::sbr::result() -&gt;data()</b>
dca::sbr::resultCode::Ok (The record exists and was updated)	N/A	N/A
dca::sbr::resultCode::DBError, dca::sbr::resultCode::SendError dca::sbr::resultCode::LogicalNameMismatch dca::sbr::resultCode::AccessError dca::sbr::resultCode::MaxStateSize dca::sbr::resultCode::MaxEventReached	N/A	N/A
dca::sbr::resultCode::ErrRecNotFound	N/A	N/A

**Purpose:** Attempts to update the value associated with a key that was previously retrieved (typically using a read or a createOrRead operation) from the U-SBR DB. It fails if the key-value record has been updated in the meantime by a concurrent update query.

**Prototype:** (see also Section 11.7.1.1)

```
$err = dca::sbr::sbrInstance(<usbr_logical_name>)->concurrentUpdate( <key_type>, <key_data_type>, $key, <value_data_type>, $value, <callback_subroutine>);
```

**Query Results:** The possible result of the create API function are described in the table below (see also Section 11.7.1.2):

<b>dca::sbr::result()-&gt;code()</b>	<b>dca::sbr::result() -&gt;dataType()</b>	<b>dca::sbr::result() -&gt;data()</b>
dca::sbr::resultCode::Ok (The record exists and was successfully updated)	N/A	N/A
dca::sbr::resultCode::DBError, dca::sbr::resultCode::SendError dca::sbr::resultCode::LogicalNameMismatch dca::sbr::resultCode::AccessError dca::sbr::resultCode::MaxStateSize dca::sbr::resultCode::MaxEventReached	N/A	N/A
dca::sbr::resultCode::ErrRecNotFound	N/A	N/A
dca::sbr::resultCode::ErrRecObsoleted (The record exists but was updated by a concurrent update query. DCA re-processes the returned value and retries the operation)	The data type of the updated record	The updated record

**Purpose:** Deletes a key-value record from the U-SBR DB, or fails if the key is not found.

**Prototype:** (see also Section 11.7.1.1)

```
$err = dca::sbr::sbrInstance(<usbr_logical_name>)->delete( <key_type>, <key_data_type>, $key, <callback_subroutine>);
```

Note that no \$value parameter is present since no value is supposed to be written into the U-SBR DB.

**Query Results:** The possible result of the create API function are described in the table below (see also Section 11.7.1.2):

<b>dca::sbr::result()-&gt;code()</b>	<b>dca::sbr::result()-&gt;dataType()</b>	<b>dca::sbr::result()-&gt;data()</b>
dca::sbr::ResultCode::Ok (The record exists and was deleted)	N/A	N/A
dca::sbr::ResultCode::DBError, dca::sbr::ResultCode::SendError dca::sbr::ResultCode::LogicalNameMismatch dca::sbr::ResultCode::AccessError dca::sbr::ResultCode::MaxStateSize dca::sbr::ResultCode::MaxEventReached	N/A	N/A
dca::sbr::ResultCode::ErrRecNotFound	N/A	N/A

## 11.8 Peer Information

This section describes the APIs to fetch the peer information.

### 11.8.1 Check for Configured Peer

A DCA can check if a Peer Name is configured in the system (SO).

**Prototype:**

```
$status = dca::peerInfo::isPeerExists(<Peer name>);
```

where <Peer Name> is the name of configured peer in the system (SO) and \$status is 1 if the <Peer Name> is configured in the SO GUI or 0 if <Peer Name> is not configured.

### 11.8.2 Fethc the Originator Peer

When receiving a Diameter message, DCA can fetch the originator of the message.

**Prototype:**

```
$peerName = dca::peerInfo::getOriginPeerName();
```

where \$peerName is the Peer Node name as configured in the SO GUI or `undef` if there is a failure while fetching the peer node detail.

## 12. Interaction with IDIH

Table 4 illustrates the IDIH events generated by DCA.

**Table 4: IDIH Events**

Event ID	Event	Type	Scope	Instance Data	When Recorded
2300	Diameter Request processing routine invoked	Routine Invocation	App Data	<ul style="list-style-type: none"> <li>• DCA short name</li> <li>• Subroutine name</li> </ul>	The Diameter Request processing routine of a DCA is invoked by the DCA framework.
2301	Diameter Answer processing routine invoked	Routine Invocation	App Data	<ul style="list-style-type: none"> <li>• DCA short name</li> <li>• Subroutine name</li> </ul>	The Diameter Answer processing routine of a DCA is invoked by the DCA framework.
2302	U-SBR Query send	U-SBR Query	App Data	<ul style="list-style-type: none"> <li>• DCA short name</li> <li>• Stack Event ID (create, read, update, ...)</li> <li>• DAL ID of the application owning the U-SBR DB</li> <li>• Key value</li> <li>• Key type</li> </ul>	An U-SBR query is prepared by a DCA.
2303	Callback invoked	Routine Invocation	App Data	<ul style="list-style-type: none"> <li>• DCA short name</li> <li>• Callback name</li> </ul>	An U-SBR query returns a result and a callback subroutine is invoked.
2304	Subroutine name not found	Execution Exception	App Data	<ul style="list-style-type: none"> <li>• DCA short name</li> <li>• Subroutine name</li> </ul>	The scripting language interpreter returns an error indicating the subroutine doesn't exist.
2305	Runtime error	Execution Exception	App Data	<ul style="list-style-type: none"> <li>• DCA short name</li> <li>• Subroutine name</li> <li>• Error message returned by the interpreter</li> </ul>	The scripting language interpreter returns an error indicating the a runtime error occurred.
2306	Debug message	Debug	App Data	<ul style="list-style-type: none"> <li>• A debug message</li> </ul>	A module included by default by the DCA framework enables DCA to generate debug messages.

Event ID	Event	Type	Scope	Instance Data	When Recorded
2307	U-SBR Query Result received	U-SBR Query	App Data	<ul style="list-style-type: none"> <li>• DCA short name</li> <li>• Stack Event ID (create, read, update, ...)</li> <li>• Data value</li> <li>• Data type</li> <li>• Query Result return code</li> </ul>	An U-SBR query result is received by a DCA.
2308	U-SBR Query send failed	U-SBR Query	App Data	<ul style="list-style-type: none"> <li>• DCA short name</li> <li>• Error code</li> </ul>	Sending the U-SBR query has failed because business logic related issues (for example, max. limit of queries has been reached, L2P mapping error, etc.), due to ComAgent related issues (for example, routing) or due to transport issues (for example, timeout).

Except for event 2306, which is explicitly generated by the debug API functions, and event 2305, which is generated when a runtime error is encountered, all other events are generated automatically by the DCA framework when a specific point in the control flow is reached. For instance, Figure 79 illustrates the IDIH event trace of a U-SBR query from the moment the query is initiated until the callback is invoked.




Figure 79: IDIH Event Trace of an U-SBR Query

The event 2302 is preceded by event 2300, 2301, or 2303, depending on whether the U-SBR query has been initiated from a Diameter request event handler, from a Diameter answer event handler or, respectively, from the callback subroutine of a previous U-SBR query like for instance when a concurrent update is retried.

## 13. Best Practices

This chapter summarizes the basic rules to follow when writing a DCA.

### 13.1 The Main Part of the Perl Script

The main part of the Perl script is executed only once when the Perl script is compiled. It is, therefore, the right place to perform sanity checks and post-process DCA configuration data. For instance the code below:

```

if(! defined($dca::appConfig{XYZ_Table}) || 
    ("ARRAY" ne ref($dca::appConfig{XYZ_Table}))) {
    # dca::application::logInfo("Missing XYZ configuration table");
    die "Missing XYZ configuration table";
}
  
```

checks that the XYZ\_Table exists and that it is a valid reference to an array. Note that single-row configuration tables are references to hash tables (for example, use HASH instead of ARRAY).

If the validation fails, then Alarm 33309 Script Compilation Error is raised when the Perl script is compiled.

DCA configuration data for multi-row (that is, not single-row) tables is stored in a Perl variable of type array; in our example \$dca::appConfig{XYZ\_Table} is a reference to such an array. Arrays are however very inefficient data structures to perform real-time lookups because they require looping through them each time. For this reason, depending on which fields DCA uses to look up the configuration data in real time, DCA would typically post-process the configuration data (in the Perl script main part) by going record-by-record through it and copying each record into a separate hash table where the tags are the values of the lookup field. If necessary multiple such hash table may be prepared for real-time use, or other data structured (for example, trees) may be created from the initial configuration data.

Post-processing increases the memory usage (with the new data structures that are created) and increases the Perl script compilation time (because the execution of the main part is always triggered by a successful Perl script compilation and therefore it may be regarded as a side effect to compiling the Perl script). However, the real-time performance gain is likely to be significant – probably orders of magnitude depending on DCA configuration data size.

## 13.2 Perl Global Variables

Do not use Perl global variables (defined in the main part of the script) to pass data between the various event handlers and callbacks in a DCA. This is because the event handlers and callbacks are executed on demand by a pool of Perl interpreter threads, which means:

1. Event handlers and callbacks that process the same Diameter message may be executed by different Perl interpreters;
2. The same Perl interpreter executes event handlers and callbacks that process many different Diameter messages.

Use instead the transaction context variables defined in Section 11.2.2.

## 13.3 Returning Control from a Perl Subroutine

The control flow paths of an event handler or callback end in one of the following ways:

1. A dca:::action API call.
2. An U-SBR query.

The example below provides an example of how an event handler or callback ends with an U-SBR query:

```
my $result = dca:::sbr:::sbrInstance("sbr")->createOrRead ($key_type,
                                                               dca:::sbr:::KeyDataType:::INT64, $imsi,
                                                               dca:::sbr:::StateDataType:::STRING, $sbr_state,
                                                               "create_or_read_nopref_cb");

# check for "synchronous" error
if(!defined($result)) {
    # could not create the sbr request - depending on the business
    logic,
    # log an error message and fall back, or raise runtime error
    alarm:
```

```
    die "could not create the SBR request";  
} else {  
    # the processing continues asynchronously  
    # in the "create_or_read_nonpref_cb"  
    exit;  
}
```

Note that no `dca::action` API call follows an U-SBR query because the U-SBR query is not going to be sent at all in this case: a `dca::action` API call ends the processing of the Diameter message, no query and no callback are executed any longer for the respective Diameter message.

### 3. A `die` statement.

Alarm 33304 DCA Runtime Errors is raised and the Diameter message is routed as indicated by the configuration (see Section 9.4). The text specified as a parameter to the `die` statement is included in the alarm's additional information.

4. The control flow reaches (i) a `return` statement or (ii) the closing bracket that ends the Perl subroutine scope. In this case, the action taken by the DCA framework depends on the value returned from the respective Perl subroutine; in the latter case the return value is the result of the last executed evaluation before the ending bracket is reached:
  - a. If the return value is grater or equal to zero, the Diameter message is forwarded.
  - b. If the return value is less than zero, Alarm 33304 DCA Runtime Errors is raised and the Diameter message is routed as indicated by the configuration (see Section 9.4).

## 13.4 Callbacks

The first thing to do in a callback is to check the result code. Section 11.7.1.2 describes the error codes that apply to all U-SBR API functions. For most DCAs, it is enough to check if the U-SBR query was successful (`dca::sbr::ResultCode::Ok` was returned) and continue processing and to abort execution (by invoking `die`) in all other cases.

Note, however, that individual U-SBR queries have specific error codes – these are highlighted with a red background throughout Section 11.7.2. Some of these specific error codes do not necessary involve that the processing is aborted; for instance: `dca::sbr::ResultCode::ErrRecExists` in case of a `createOrRead` query indicates that the query performed "read" rather than a "create", `dca::sbr::ResultCode::ErrRecObsoleted` in case of a `concurrentUpdate` indicates that the query is repeated.

## 13.5 Sending multiple U-SBR Queries

There might be situations when processing a Diameter message requires a sequence of U-SBR queries (for example, a read and, based on the state data returned, also an update). It is not possible to send concurrent U-SBR queries, that is., more than one U-SBR query from the same Perl subroutine (event handler or callback); if multiple U-SBR queries are initiated from a Perl subroutine, only the last one is sent.

Multiple U-SBR queries (during the processing of the same Diameter message) are sent sequentially, meaning, the event handler initiates the first U-SBR query, the callback of the first U-SBR query initiates the second U-SBR query, the callback of the second U-SBR query initiates the third U-SBR query, etc., the callback of the last U-SBR query routes the Diameter message (for example, by using a `dca::action` API call).

## 13.6 Accessing Lower Layer Data from Mediation

DCA EDL API (see Section 11.1) and part of the Routing API (see Section 11.4 `setART` and `setPRT`) are similar to API offered by the Mediation feature. However, there are a couple of API functions supported by Mediation that are not available in DCA. This is because Mediation is invoked in the context of the Diameter Routing Layer (DRL), whereas DCA operates at the application layer (that is, one layer above DRL). These API calls are:

```
$param->ingressConnectionName( );
      Return the name of the ingress connection if available.

$param->ingressPeerName( );
      Return the name of the ingress peer if available.
```

(where `$param` is retrieved as described in Section 11.1.1) and may be needed if DCA business logic depends on the connections or peers the Diameter messages are received from. This information may be made available to DCA through Internal Variables, using the following procedure: (i) a Mediation script uses the above API calls to retrieve the ingress connection/peer and (ii) writes it into an Internal Variable, from where (iii) DCA can read when the event handler is invoked.

Note that the following API functions:

```
$param->egressConnectionName( );
      Return the name of the egress connection if available.

$param->egressPeerName( );
      Return the name of the egress peer if available.
```

are not usable in DCA because the routing decision is made after DCA event handlers complete the execution (and the message is returned back to DRL).

## 13.7 Performance Tuning

DCAs may require performance tuning depending upon the complexity of business logic and need for MPS.

Users can determine the need to do performance tuning based on:

- The number of `DcaRequestTaskThr` and `DcaAnswerTaskThr` threads needed on a DA-MP, which depends on whether DCA performs computation on:
  - Diameter request leg of the diameter transaction.
  - Diameter answer leg of the diameter transaction.
  - Both diameter request and diameter answer leg of the diameter transaction.
- The number of `DcaSbrEventTaskThr` threads, which must be directly proportional with number of SBR transactions per diameter transactions performed by DCA.
- The number of SBR SGs in a U-SBR DB (resource domain) is based on how many SBR transactions per second are planned to be processed by the respective U-SBR DB, which depends on DCA requirements.

**Note:** Please contact the customer support team for tuning the performance parameters.