

Oracle Communications ASAP Cartridge for Nokia SRRi

The *ASAP Cartridge for Nokia SRRi* is an optional software component that enables ASAP to handle SRR Numbers in Nokia SRRi.

Supported Services

The *ASAP Cartridge for Nokia SRRi* supports the following actions for SSR Numbers:

Service	Description
Create Numbers	Create number entries in the SRR (Service Routing Register) network element.
Delete Numbers	Delete number entries in the SRR (Service Routing Register) network element.
Modify Numbers	Modify number entries in the SRR (Service Routing Register) network element.
Query Numbers	Output number entries in the SRR (Service Routing Register) network element.

Cartridge Contents

The *ASAP Cartridge for Nokia SRRi* includes:

- Common Service Description Layer Commands (CSDLs)
- Atomic Service Description Layer Commands (ASDLs)
- Java methods
- Installation scripts
- Sample work orders

This cartridge can be extended by any of the following groups:

- Customers
- Systems Integrators
- Oracle Communications Professional Services

For information on the guidelines for extending a cartridge, refer to the *ASAP Cartridge Development Kit (CDK) for Service Activation*.

Technical Specifications

Network Element Hardware & Software Requirements

The *ASAP Cartridge for Nokia SRRi* is designed to operate with the following hardware and software:

- Nokia SRRi M12.

Network Element Interface

This cartridge interfaces with the Nokia SRRi using its command line interface over telnet.