# **Oracle Communications ASAP Cartridge for Nokia VLR**

The ASAP Cartridge for Nokia VLR is an optional software component that enables ASAP to activate subscriber related services on the Nokia VLR system.

## **Supported Services**

The ASAP Cartridge for Nokia VLR supports the following subscriber related services:

Service	Actions & Description
Subscriber	Create a subscriber in the VLR
	<ul> <li>Removes an existing subscriber from the VLR. The HLR of the subscriber is informed about the removal</li> </ul>
	<ul> <li>Retrieves subscribers CAMEL data from the VLR (Visitor Location Register)</li> </ul>
	Retrieves the total number of normal as well     as telemetric subscribers from the VLR
	Retrieves the subscribers data from VLR
	<ul> <li>Retrieves the international mobile station equipment identity (IMEI) of the subscriber from the VLR</li> </ul>
	Retrieves the supplementary services of the subscriber from the VLR
	<ul> <li>Retrieves the operator determined barring (ODB) data of the subscriber from the VLR</li> </ul>
	Retrieves the closed user group (CUG) data of the subscriber from the VLR

## **Cartridge Contents**

The ASAP Cartridge for Nokia VLR includes:

- Common Service Description Layer Commands (CSDLs)
- Atomic Service Description Layer Commands (ASDLs)
- Java methods
- Installation scripts
- Sample work orders

This cartridge can be extended by any of the following groups:

- Customers
- Systems Integrators
- Oracle Communications Professional Services

For information on the guidelines for extending a cartridge, refer to the ASAP Cartridge Development Kit (CDK) for Service Activation.

### **Technical Specifications**

### Network Element Hardware & Software Requirements

The ASAP Cartridge for Nokia VLR is designed to operate with the following hardware and software:

• Nokia VLR system running on software load M12-ED1.

### Network Element Interface

This cartridge interfaces with the Nokia VLR using the TCP/IP telnet protocol.