

# **Oracle Financial Services Sanctions Pack**

## **Installation Guide**

**Release 8.1.2.7.0**

**July 2024**

**F21664-05**

**ORACLE®**

**Financial Services**

Oracle Financial Services Sanctions Pack Installation Guide.

Copyright © 2024 Oracle and/or its affiliates. All rights reserved.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are “commercial computer software” pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

For information on third party licenses, click [here](#).

# Document Control

**Table 1: Document Control**

Revision Number	Revision Date	Change Log
8.1.2.7.0	February 2024	The first publication of this guide.

---

# Contents

<b>1</b>	<b>About This Guide</b> .....	<b>2</b>
1.1	How This Guide is Organized .....	2
1.2	Conventions .....	2
1.3	Acronyms.....	3
<b>2</b>	<b>Pre-Installation</b> .....	<b>4</b>
2.1	Files Packaged in This ML Release.....	4
2.1.1	<i>Modified Files</i> .....	4
2.1.2	<i>Build-related Files</i> .....	10
<b>3</b>	<b>Applying This Maintenance Level Release</b> .....	<b>12</b>
<b>4</b>	<b>Post-Installation Steps - Customer Screening</b> .....	<b>14</b>
<b>5</b>	<b>Post-Installation Steps - Transaction Filtering</b> .....	<b>16</b>
<b>6</b>	<b>Post-Installation Steps - Pack on Pack</b> .....	<b>19</b>
<b>7</b>	<b>Post-Installation Scripts to Remove TF Application Groups</b> .....	<b>21</b>
<b>8</b>	<b>OFSAA Support Contact Details</b> .....	<b>23</b>
<b>9</b>	<b>Send Us Your Comments</b> .....	<b>24</b>

# 1 About This Guide

*Oracle Financial Services Sanctions Pack (OFS SP) 8.1.2.6.0 Installation Guide* provides step-by-step instructions to install the OFS SP 8.1.2.6.0 Maintenance Level (ML) release.

The OFS SP 8.1.2.6.0 ML release includes all the bug fixes and minor enhancements since the GA (General Availability) release, 8.1.2.0.0.

## 1.1 How This Guide is Organized

This guide includes the following chapters:

- *Chapter 2, Pre-Installation*, provides details of the pre-installation requirements and the files packaged in this ML release.
- *Chapter 3, Applying This Maintenance Level Release*, details the steps to install the OFS SP 8.1.2.6.0 ML patch.
- *Chapter 4, Post-Installation Steps - Customer Screening*, provides details of the Customer Screening post Installation steps.
- *Chapter 5, Post-Installation Steps - Transaction Filtering*, provides details of the Transaction Filtering post Installation Steps.
- *Post-Installation Scripts to Remove TF Application Groups*, provides details of the Transaction Filtering post Installation Steps.

## 1.2 Conventions

*Table 1* lists the conventions used in this guide.

**Table 1: Conventions Used in this Guide**

Conventions	Description
<i>Italics</i>	<ul style="list-style-type: none"> <li>• Names of books, chapters, and sections as references</li> <li>• Emphasis</li> </ul>
<b>Bold</b>	<ul style="list-style-type: none"> <li>• The object of an action (menu names, field names, options, button names) in a step-by-step procedure</li> <li>• Commands typed at a prompt</li> <li>• User input</li> </ul>
Monospace	<ul style="list-style-type: none"> <li>• Directories and subdirectories</li> <li>• File names and extensions</li> <li>• Process names</li> <li>• Code sample, including keywords and variables within the text and as separate paragraphs, and user-defined program elements within the text</li> </ul>
Asterisk	Mandatory fields in the User Interface
<Variable>	Substitute input value

## 1.3 Acronyms

Table 2 lists the acronyms used in this guide.

**Table 2: Acronyms**

Conventions	Description
ML	Maintenance Level
OFSAAI	Oracle Financial Services Analytical Applications Infrastructure
EAR / WAR	Enterprise Archive / Web Archive
ECM	Enterprise Case Management
MOS	My Oracle Support

## 2 Pre-Installation

**NOTE** Before you run the patch, perform a backup of the Schema (Atomic and Config), `FIC_HOME`, and `ftpshare` directories.

**NOTE** If the Behavior Detection Application Pack version 8.1.2.6.0 patch to be installed on Sanctions Pack Version 8.1.2.0.0, or later, then follow these steps:

- `create table KDD_BUS_DMN_TEMP as (select * from KDD_BUS_DMN);`
- `UPDATE KDD_BUS_DMN SET TF_BUS_DMN_NM=NULL; commit;`

1. The OFS Sanctions Application Pack v8.1.2.0.0 must be installed.
2. Download and install the following mandatory patches from [My Oracle Support](#) by searching the patch under the Patches & Updates tab:
  - Bug 35681234 - OFSAA 8.1.2.0.0 AAI ML Release #4 (8.1.2.4.0) (OFSAAI)
  - Bug 35936594 - OFS ECM Application Pack v8.1.2.0.0 Minor Release 8.1.2.7.0

**NOTE** Download and install the above patch if the ECM Application is installed on the same pack.

- Bug 35958115- OFS BD Application Pack v8.1.2.0.0 Minor Release 8.1.2.7.0

**NOTE** Download and install the above patch if the BD Application is installed on the same pack.

3. The Patch will add primary key to the `stg_party_party_relationship` table. Before installing this patch make sure the default value (**MSG**) is present in the `v_relationship_type_code` column.

### 2.1 Files Packaged in This ML Release

The list of files packaged in this ML release is as follows:

- [Modified Files](#)
- [Build-related Files](#)

#### 2.1.1 Modified Files

The product files modified for this ML release are as follow

- [.jar Files](#)
- [.html Files](#)
- [.js Files](#)
- [.css Files](#)
- [.jsp Files](#)

- [.txt Files](#)
- [.dxi Files](#)
- [.sh Files](#)
- [.xml](#)
- [.xsl](#)
- [Message Type](#)

### 2.1.1.1 **.jar Files**

- `realTimeScreening.jar`
- `TFLTService.jar`
- `QueueService.jar`
- `TF_XML_QUEUE_POPULATION.jar`
- `TF_XML_HIGHLIGHT.jar`
- `TF_US_NACHA.jar`
- `TFLTTransformer.jar`
- `SEPARTCacheService.jar`
- `SEPAParser.jar`
- `csprocessing.jar`
- `SEPA_TFLT_TransformerReTrigger.jar`
- `swiftRTCachService.jar`
- `SEPATFLTTransformer.jar`
- `FDTFLTTransformer.jar`
- `swiftService.jar`
- `MergeUtility.jar`
- `sentry-djw-connector.jar`
- `SEPA_TFLTActions.jar`
- `SwiftRegexParser.jar`
- `TF_XML_XSD_CONF_UI.jar`
- `CS_EDQ_CALL.jar`
- `fdService.jar`
- `TF_XML_LOGGER.jar`
- `TFLTTransformerAudit.jar`
- `TFLTActions.jar`
- `FDTFLTActions.jar`
- `TFLTTransformerReTrigger.jar`
- `FDTFLTTransformerReTrigger.jar`
- `TF_XML_PARSER.jar`



- fccm-simulation-common-ipe.jar
- fccm-simulation-common-logger.jar
- fccm-simulation-common-aaiaapi.jar
- fccm-simulation-tf.jar
- TF\_XML\_IMMEDIATE\_FEEDBACK.jar
- TF\_XML\_FINAL\_FEEDBACK.jar

### **2.1.1.2 .html Files**

- RiskSummary.html
- TFDetailScreen.html
- sectionDtls.html
- trxnDetails.html
- RTScreening.html
- QueueCreation.html
- DetailScreen.html
- AuditScreen.html
- ListScreening.html
- AlertSummaryTable.html
- TFListScreening.html
- ListApprovalSummary.html
- ListApprovalHistorySummary.html
- SwiftConfigScreen.html
- 8.1.2.7.0 Vs 8.1.2.5.1 Watchlist\_Management\_DXI\_Comparison Report.html
- 8.1.2.5.0 Vs 8.1.2.7.0 Customer\_Screening\_DXI\_Comparison Report.html
- 8.1.2.5.0 Vs 8.1.2.7.0 Transaction\_Screening\_DXI\_Comparison Report.html
- 8.1.2.4.0 Vs 8.1.2.7.0 Transaction\_Screening\_Batch\_DXI\_Comparison Report.html
- Admin.html
- AdminFingerPrintScreen.html
- AdminScreenTabs.html
- WSDetailScreen.html
- TFAuditScreen.html
- AppLevelConfiguration.html
- AlertsHeaderList.html
- QueueHome.html

### **2.1.1.3 .js Files**

- TFDetailScreen.js

- RTScreening.js
- QueueCreation.js
- Admin.js
- AdminList.js
- AlertSummaryTable.js
- DetailScreen.js
- AuditScreen.js
- ListScreening.js
- cspagination.js
- TFListScreening.js
- tfpagination.js
- SwiftConfigScreen.js
- RestServiceList.js
- main.js
- AdminFingerPrintScreen.js
- WSDetailScreen.js
- MessageAdditionalDetailsTreeLayout.js
- sectionDtls.js
- matchedSectionXMLDtls.js
- TFAuditScreen.js
- RiskSummary.js
- AppLevelConfiguration.js
- TFListScreeningHeader.js
- TFRelatedDetailScreen.js
- AutoAssignConfig.js
- AutoRelease.js
- Identifier.js
- Jurisdiction.js
- ListApprovalHistorySummary.js
- ListApprovalResponseSummary.js
- ListApprovalSummary.js
- ListHistorySearch.js
- ListResponseSearch.js
- ListSummarySearch.js
- Origin Record ID.js
- Origin Record Name.js

- Origin.js
- Record Name.js
- SLAConfigurationScreen.js
- SwiftCutOffScreen.js
- QueueHome.js
- CutOffConfiguration.js
- IdentificationDetails.js

#### **2.1.1.4 .css Files**

- override.css
- zipper.css
- preferences.css

#### **2.1.1.5 .jsp Files**

- QueueMessageConstants.jsp
- CSRTMessageConstants.jsp
- TFLTMessageConstants.jsp
- SwiftMessageConstants.jsp
- index.jsp
- CSMessageConstants.jsp
- index\_admin.jsp
- fd\_index\_admin.jsp
- index\_cutoff.jsp
- swift\_mapping.jsp
- index\_GoodGuyListDetls.jsp
- index\_sepa\_admin.jsp
- indexqueue.jsp
- index\_appLevelConfiguration.jsp
- SEPAMessageConstants.jsp

#### **2.1.1.6 .txt Files**

- Watchlist\_Management\_8.1.2.7.0\_DXI\_Readme.txt
- Customer\_Screening\_8.1.2.7.0\_DXI\_Readme.txt
- Transaction\_Screening\_8.1.2.7.0\_DXI\_Readme.txt
- Transaction\_Screening\_Batch\_8.1.2.7.0\_DXI\_Readme.txt

#### **2.1.1.7 .dxi Files**

- Watchlist\_Management\_8.1.2.7.0.dxi
- Customer-Screening\_8.1.2.7.0.dxi

- Transaction\_Screening\_8.1.2.7.0.dxi
- Transaction\_Screening\_Batch\_8.1.2.7.0.dxi

### **2.1.1.8 .sh Files**

- CallImmediateXMLFeedbackCreation.sh
- CallImmediateXMLFeedbackFileCreation.sh
- UpdateAdditionalMsgDtls.sh
- nachaAdditionalDetails.sh
- nachaAlertGeneration.sh
- nachaedq.sh
- nachaEdqInputConfig.sh
- nachaFeedback.sh
- nachaIPEInputConfig.sh
- nachaParser.sh
- nachaPopulateQueue.sh
- NachaValidation.sh
- CallXMLAlertGeneration.sh
- CallXMLEdQ.sh
- CallXMLHighlight.sh
- CallXMLParser.sh
- CallXMLPopulateQueue.sh
- CallXMLRTIPopulation.sh
- CallXMLStructuredSepa.sh
- ant.sh
- OWSFileMigration.sh
- OWSFileInsert.sh

### **2.1.1.9 .xml**

- RTIExport\_TransactionFiltering\_IPE\_Assessments\_Swift\_8.1.2.4.0.xml
- RTIExport\_TransactionFiltering\_IPE\_Assessments\_SEPA\_RT\_8.1.2.4.0.xml

### **2.1.1.10 .xsl**

- export\_To\_PDF\_ZCS\_fo.xsl

### **2.1.1.11 Message Type**

- MT202COV.sql
- MT566.sql
- MT765.sql
- camt.052.001.08.sql

- camt.052.001.10.sql
- camt.053.001.08.sql
- camt.053.001.10.sql
- camt.054.001.08.sql
- camt.054.001.09.sql
- camt.054.001.10.sql
- camt.060.001.05.sql
- camt.060.001.06.sql
- camt.026.001.09.sql
- camt.027.001.09.sql
- camt.028.001.11.sql
- camt.029.001.11.sql
- camt.031.001.06.sql
- camt.032.001.04.sql
- camt.033.001.06.sql
- camt.038.001.04.sql
- camt.056.001.10.sql
- camt.087.001.08.sql
- camt.030.001.05.sql
- camt.034.001.06.sql
- pacs.002.001.13.sql
- pacs.007.001.12.sql

**NOTE**

- Take a backup of the above mentioned files as a precautionary measure.
- If any customizations done to these files, they need to be re-applied.

### 2.1.2 Build-related Files

The build-related files added for this ML release are as follows:

- DB\_Install.xml
- INSERT\_INFODOM\_PATCHES.sql

**NOTE**

The below given files are required for the patch utility to work.

- merge\_wsdd.xsl
- merge\_Persistence.xsl
- merge\_web.xsl

- merge\_Menu.xsl

### 3 Applying This Maintenance Level Release

To apply this ML release, follow these steps:

**NOTE** The following files are required for the patch utility to work:

- merge\_wd.xsl
- merge\_Persissdtence.xsl
- merge\_web.xsl
- merge\_Menu.xsl

1. Load the **.profile** and make sure that `$FIC_HOME` directory corresponds to the proper environment where the patch application is required.

**NOTE** The FIC server must be up and running.

2. Start the OFSAAI Services.
3. Download and copy the `35947382_GENERIC.zip` file (in Binary mode) to the server where OFSAAI is installed.
4. Navigate to the `<USER_PATCH_DIR>` directory and extract the contents of the patch archive file using the following command:

```
unzip -a <name of the archive file to be unzipped>
```

For example: `unzip -a 35947382_GENERIC.zip`.

**NOTE**

- `<USER_PATCH_DIR>` is the directory containing the `<patch>.zip` file copied in step 3.
- The `-a` option is mandatory to unzip the patch. In case, you receive an error message `unzip; not found [No such file or directory]` when the package is not installed, contact your *UNIX Administrator*.

The list of files available when you unzip the folder are as follows:

- PatchConfig.xml
  - install.sh
  - Setup.bin
  - validateXMLInputs.jar
  - Readme\_OFSSANC\_8.1.2.7.0.txt
5. Navigate to the `<USER_PATCH_DIR>/35947382/bin` directory and grant 755 permission using the following command:
 

```
$ chmod 755 *
```
  6. Navigate to `<USER_PATCH_DIR>/35947382/conf/PatchConfig.xml` directory and provide the following place holder values:
    - `##SCHEMA_OUT_XML_PATH##` - This attribute refers to the path which needs to be pointed to `OFS_SANC_SCHEMA_OUTPUT.xml`, which was generated at the time of installation.

- FSDF\_UPLOAD\_MODEL- The value to this parameter should be **1** for pack on-pack or stand-alone.
7. Install the patch by executing the following install.sh command:  

```
$ ./install.sh
```
  8. Check if the ML release is applied successfully by verifying the patch install logs under the <USER\_PATCH\_DIR>/35947382/logs directory. Contact [My Oracle Support](#) in case of any errors.
  9. After the patch is installed successfully, re-create the OFSAA EAR/WAR file and re-deploy a new EAR/WAR file on the web application server.
  10. Restart the OFSAA Application server and the web server.

For more information on the application configuration, see *Administration Guide* on [OHC](#).

**NOTE**

Once installation is successful, execute the following script in the atomic schema:

- ALTER TABLE KDD\_BUS\_DMN add TF\_BUS\_DMN\_NM varchar2(20 CHAR);
- Copy data from table KDD\_BUS\_DMN\_TEMP to table KDD\_BUS\_DMN against column TF\_BUS\_DMN\_NM



## 4 Post-Installation Steps - Customer Screening

This section provides the post installation steps for the Customer Screening application.

To perform the post-installation activities, follow these steps:

1. Once the patch is installed successfully, re-create the ear & war file by executing `./ant.sh` file for sanctions under `$FIC_WEB_HOME` folder.
2. Copy the `##EDQ_INSTALLATION_PATH##/edq/oracle.edq/jmxtools.jar` file into the `##FIC_DB_HOME##/lib` folder.
3. Navigate to `$FIC_HOME/Customer_Screening` folder and copy the `Customer_Screening_8.1.2.7.0.dxi` file to the local setup.
4. Open EDQ and import the `Customer_Screening_8.1.2.7.0.dxi` file from the local directory.
5. To configure the Security Mapping, do the necessary configurations in the `fcc_zcs_security_attr_grp_map` table for Customer Screening.
6. To configure the Priority of Alert, do the necessary configurations in the `fcc_zcs_alert_priority_conf` table for Customer Screening.
7. To configure the temporary and permanent directories to save the uploaded documents, set the `DOCUMENT_UPLOAD_TEMP` and `DOCUMENT_UPLOAD_SAVE` parameters in the `CONFIGURATION` table of the `Config` Schema as shown in the [Table 3](#).

[Table 3](#) provides the list of parameter value examples.

**Table 3: Parameter Value Examples**

Parameter Name	Parameter Value
<code>DOCUMENT_UPLOAD_SAVE</code>	<code>/DocStorage</code>
<code>DOCUMENT_UPLOAD_TEMP</code>	<code>/Temp</code>

For more details, see the 10.1.1 Configure Document Upload Location Properties section in [Oracle Financial Services Analytical Applications Infrastructure Administration and Configuration Guide](#).

8. Restart the servers.
9. Execute the following command in `Config` Schema:
 

```
GRANT SELECT ON cssms_group_mast_pack TO ##atomic_user##
```
10. Login as system user and use the following command:
 

```
grant execute on dbms_crypto to ##atomic_user##
```
11. Navigate to `$FIC_HOME/utility/AppPckMastSynch/bin` directory and follow the below steps:
  - a. Open the shell `AppPckMastSynch.sh` file.
  - b. Replace the token `$PackName` to `OFS_SANC_PACK`.
  - c. Execute the shell file as below:
 

```
$ ./AppPckMastSynch.sh
```

12. After the execution is complete, replace `OFS_SANC_PACK` to `$PackName` in `AppPckMast-Synch.sh` file and close the file.

## 5 Post-Installation Steps - Transaction Filtering

This section provides the post installation steps for the Transaction Filtering application.

To perform the post-installation activities, follow these steps:

1. Once the patch is installed successfully, re-create the ear & war file by executing `./ant.sh` file for sanctions under `$FIC_WEB_HOME` directory.
2. Navigate to the `$FIC_HOME/Transaction_Processing` folder and re-create the ear & war file by executing the `./ant.sh` for `TFLT` file in the same path.
3. Navigate to the `$FIC_HOME/Fedwire_Processing` folder and execute the `ant.sh` file and then deploy the `FEDTFLT.ear` or `FEDTFLT.war` file.
4. Navigate to the `$FICHOME/Sepa_Real_Time_Processing` folder and execute the `ant.sh` file and then deploy the `SEPATFLT.ear` or `SEPATFLT.war` file.
5. Navigate to the `$FIC_HOME/Transaction_Processing/IPEAssessmentImport` folder and import the `RTIExport_TransactionFiltering_IPE_Assessments_Swift_8.0.8.2.0.xml` file. (See the [OFS Sanctions Pack Installation and Configuration Guide 8.0.8.0.0](#) for more information on the `RTIExport_TransactionFiltering_IPE_Assessments_Swift_8.0.8.2.0.xml` file.)
6. Navigate to the `$FIC_HOME/Transaction_Processing/IPEAssessmentImport` folder and import the `RTIExport_TransactionFiltering_IPE_Assessments_Sepa_8.0.8.2.0.xml` file. (See the [OFS Sanctions Pack Installation and Configuration Guide 8.0.8.0.0](#) for more information on the `RTIExport_TransactionFiltering_IPE_Assessments_Sepa_8.0.8.2.0.xml` file.)
7. Navigate to the `$FIC_HOME/Transaction_Processing/IPEAssessmentImport` folder and import the `RTIExport_TransactionFiltering_IPE_Assessments_Nacha_8.0.8.2.0.xml` file. (See the [OFS Sanctions Pack Installation and Configuration Guide 8.0.8.0.0](#) for more information on the `RTIExport_TransactionFiltering_IPE_Assessments_Nacha_8.0.8.2.0.xml` file.)
8. Navigate to the `$FIC_HOME/Transaction_Processing/IPEAssessmentImport` folder and import the `RTIExport_TransactionFiltering_IPE_Assessments_AutoRelease_8.0.8.2.0.xml` file. (See the [OFS Sanctions Pack Installation and Configuration Guide 8.0.8.0.0](#) for more information on the `RTIExport_TransactionFiltering_IPE_Assessments_Nacha_8.0.8.2.0.xml` file.)
9. Navigate to the `$FIC_HOME/Sepa_Real_Time_Processing/IPEAssessmentImport` folder and import the `RTIExport_TransactionFiltering_IPE_Assessments_SEPA_RT.xml` file. (See the post installation steps section in the [OFS Sanctions Pack Installation and Configuration Guide 8.0.8.0.0](#) for more information on the `RTIExport_TransactionFiltering_IPE_Assessments_SEPA_RT.xml` file.)
10. Navigate to `$FIC_HOME/Transaction_Processing/IPEAssessmentImport` folder and Import the `RTIExport_TransactionFiltering_IPE_Assessments_Swift_8.1.2.4.0.xml` file.
11. Navigate to `$FIC_HOME/Sepa_Real_Time_Processing/IPEAssessmentImport` folder and Import the `RTIExport_TransactionFiltering_IPE_Assessments_SEPA_RT_8.1.2.4.0.xml` file.
12. For deploying repository and catalog, see the Deploying Analytic Reports and Threshold Analyzer section in the [OFS Sanctions Pack Installation and Configuration Guide 8.0.8.0.0](#).
13. Navigate to `$FIC_HOME/utility/AppPckMastSynch/bin` folder and open `AppPckMastSynch.sh` file. Update the `$PackName` to respective pack ID and save the file.

14. Execute this `AppPckMastSynch.sh` file using `./AppPckMastSynch.sh`.
15. Navigate to the `$FIC_HOME/SanctionsCommon` folder and copy the `config.zip` file to the local setup.
16. Unzip `config.zip` file. Copy the files inside each folder of `config` file into the corresponding folders under `oedq.local.home` folder.
17. Open EDQ and import the `Transaction_Screening_8.1.2.6.0.dxi` and `Transaction_Screening_Batch_8.1.2.7.0.dxi` from the local setup.
18. Navigate to the `$FIC_HOME/SanctionsCommon` folder and copy the `Watchlist_Management_8.1.2.6.0.dxi` file to the local setup.
19. Open EDQ and import the `Watchlist_Management_8.1.2.7.0.dxi` file from the local setup.
20. Navigate to the `$FIC_HOME/Transaction_Processing/EDQDXIFiles` folder and import `Transaction_Screening_8.1.2.7.0.dxi` file into the EDQ directory. (See the [OFS Sanctions Pack Installation and Configuration Guide 8.0.8.0.0](#) for more information on how to import `Transaction_Screening.dxi` file in EDQ.)
21. Navigate to the `$FIC_HOME/Transaction_Processing/EDQDXIFiles` folder and import `Transaction_Screening_Batch_8.1.2.7.0.dxi` file into the EDQ directory. (See the [OFS Sanctions Pack Installation and Configuration Guide 8.0.8.0.0](#) for more information on how to import `Transaction_Screening.dxi` file in EDQ.)
22. To configure the Security Mapping, do the necessary configurations in the `domain_jur_grp_map` table for the Transaction Filtering.
23. To configure the Priority of Alert for Transaction Filtering, do the following necessary configurations:  

```
Select t.v_attribute_value1 from setup_rt_params t where t.n_param_identifier=34;
```
24. To configure the temporary and permanent directories to save the uploaded documents, set the `DOCUMENT_UPLOAD_TEMP` and `DOCUMENT_UPLOAD_SAVE` parameters in the `CONFIGURATION` table of the `Config` Schema as shown in the [Table 4](#).

[Table 4](#) provides the list of parameter value examples.

**Table 4: Parameter Value Example**

Parameter Name	Parameter Value
<code>DOCUMENT_UPLOAD_SAVE</code>	<code>/DocStorage</code>
<code>DOCUMENT_UPLOAD_TEMP</code>	<code>/Temp</code>

For more details, see the 10.1.1 Configure Document Upload Location Properties section in [Oracle Financial Services Analytical Applications Infrastructure Administration and Configuration Guide](#).

25. Restart the servers.
26. Execute the following command in `Config` Schema:  

```
GRANT SELECT ON cssms_group_mast_pack TO ##atomic_user##
```
27. Login as system user and use the following command:  

```
grant execute on dbms_crypto to ##atomic_user##
```

28. Navigate to `$FIC_HOME/utility/AppPckMastSynch/bin` directory and follow the below steps:

- a. Open the shell `AppPckMastSynch.sh` file.
- b. Replace the token `$PckName` to `OFS_SANC_PACK`.
- c. Execute the shell file as below:

```
$ ./AppPckMastSynch.sh
```

29. After the execution is complete, replace `OFS_SANC_PACK` to `$PckName` in `AppPckMast-Synch.sh` file and close the file.

## 6 Post-Installation Steps - Pack on Pack

This section provides the pack on pack, post installation steps for Sanctions application pack.

To perform the pack on pack post installation of the Sanctions application pack above the ECM application pack, execute the following queries in the Config Schema:

**NOTE** ECM application pack version 8.1.2.0.0 must be already installed.

```

MERGE INTO AAI_AOM_APP_COMP_ATTR_MAPPING T USING ( SELECT '1' APP_COM-
P_ATTR_MAP_ID, '1' N_ATTRIBUTE_ID, 'Action' V_ATTR_CODE, '1002' N_ATTR_
TYPE_ID, 'select t.action_cd,t.action_nm from kdd_action t where
t.action_category_code is not null and t.action_category_code not in
('ENT','PR','EXP','AS','DD','OBS')' V_ATTRIBUTE_VALUE1, ''
V_ATTRIBUTE_VALUE2,'OFS_NGECM' N_APP_ID, '-1' N_COMP_ID, '' V_UDP_CODE,
''V_ATTR_CONTROL_TYPE FROM DUAL) S
ON ( T.APP_COMP_ATTR_MAP_ID = S.APP_COMP_ATTR_MAP_ID AND T.N_APP_ID =
S.N_APP_ID )
WHEN NOT MATCHED THEN INSERT
(APP_COMP_ATTR_MAP_ID,N_ATTRIBUTE_ID,V_ATTR_CODE,N_ATTR_TYPE_ID,V_ATTRIB
UTE_VALUE1,V_ATTRIBUTE_VALUE2,N_APP_ID,N_COMP_ID,V_UDP_CODE,V_ATTR_CON-
TROL_TYPE)VALUES
(S.APP_COMP_ATTR_MAP_ID,S.N_ATTRIBUTE_ID,S.V_ATTR_CODE,S.N_ATTR_TYPE_ID,
S.V_ATTRIBUTE_VALUE1,S.V_ATTRIBUTE_VALUE2,S.N_APP_ID,S.N_COMP_ID,S.V_UD-
P_CODE,S.V_ATTR_CONTROL_TYPE)
/
MERGE INTO AAI_AOM_APP_COMP_ATTR_MAPPING T USING ( SELECT '2' APP_COM-
P_ATTR_MAP_ID, '2' N_ATTRIBUTE_ID, 'Status' V_ATTR_CODE, '1002' N_ATTR_
TYPE_ID, 'select t.status_cd,t.status_nm from kdd_status t where
t.viewd_result_status_cd is null or t.viewd_result_status_cd <>
'OBS'' V_ATTRIBUTE_VALUE1, '' V_ATTRIBUTE_VALUE2,'OFS_NGECM' N_APP_ID,
'-1' N_COMP_ID, '' V_UDP_CODE, ''V_ATTR_CONTROL_TYPE FROM DUAL) S
ON ( T.APP_COMP_ATTR_MAP_ID = S.APP_COMP_ATTR_MAP_ID AND T.N_APP_ID =
S.N_APP_ID )
WHEN NOT MATCHED THEN INSERT
(APP_COMP_ATTR_MAP_ID,N_ATTRIBUTE_ID,V_ATTR_CODE,N_ATTR_TYPE_ID,V_ATTRIB
UTE_VALUE1,V_ATTRIBUTE_VALUE2,N_APP_ID,N_COMP_ID,V_UDP_CODE,V_ATTR_CON-
TROL_TYPE)VALUES
(S.APP_COMP_ATTR_MAP_ID,S.N_ATTRIBUTE_ID,S.V_ATTR_CODE,S.N_ATTR_TYPE_ID,
S.V_ATTRIBUTE_VALUE1,S.V_ATTRIBUTE_VALUE2,S.N_APP_ID,S.N_COMP_ID,S.V_UD-
P_CODE,S.V_ATTR_CONTROL_TYPE)
/
MERGE INTO AAI_AOM_APP_COMP_ATTR_MAPPING T USING ( SELECT '9' APP_COM-
P_ATTR_MAP_ID, '9' N_ATTRIBUTE_ID, 'NextStatus' V_ATTR_CODE, '1002'
N_ATTR_TYPE_ID, 'select t.status_cd,t.status_nm from kdd_status t where
t.viewd_result_status_cd is null or t.viewd_result_status_cd <>

```

```
'OBS''' V_ATTRIBUTE_VALUE1, ' ' V_ATTRIBUTE_VALUE2, 'OFS_NGECM' N_APP_ID,
'-1' N_COMP_ID, ' ' V_UDP_CODE, ' 'V_ATTR_CONTROL_TYPE FROM DUAL) S
ON ( T.APP_COMP_ATTR_MAP_ID = S.APP_COMP_ATTR_MAP_ID AND T.N_APP_ID =
S.N_APP_ID )
WHEN NOT MATCHED THEN INSERT
(APP_COMP_ATTR_MAP_ID,N_ATTRIBUTE_ID,V_ATTR_CODE,N_ATTR_TYPE_ID,V_ATTRIB
UTE_VALUE1,V_ATTRIBUTE_VALUE2,N_APP_ID,N_COMP_ID,V_UDP_CODE,V_ATTR_CON-
TROL_TYPE)VALUES
(S.APP_COMP_ATTR_MAP_ID,S.N_ATTRIBUTE_ID,S.V_ATTR_CODE,S.N_ATTR_TYPE_ID,
S.V_ATTRIBUTE_VALUE1,S.V_ATTRIBUTE_VALUE2,S.N_APP_ID,S.N_COMP_ID,S.V_UD-
P_CODE,S.V_ATTR_CONTROL_TYPE)
/
```

## 7 Post-Installation Scripts to Remove TF Application Groups

This section provides the Scripts to Remove TF Application Groups after the installation of the sanctions application.

Execute the below script to remove the TF application group:

```
delete from CSSMS_USR_GROUP_DSN_MAP_UNAUTH where v_group_code in (select
v_group_code from CSSMS_USRGRP_DSN_UNAUTH_PACK where v_app_id = 'OFS_TFLT'
and v_group_code like 'TF%');
```

```
delete from CSSMS_USRGRP_DSN_UNAUTH_PACK where v_app_id = 'OFS_TFLT' and
v_group_code like 'TF%';
```

```
delete from CSSMS_USR_GROUP_DSN_SEG_MAP where v_group_code in (select
v_group_code from CSSMS_USR_GROUP_DSN_MAP_PACK where v_app_id = 'OFS_TFLT'
and v_group_code like 'TF%');
```

```
delete from CSSMS_USR_GROUP_DSN_MAP_PACK where v_app_id = 'OFS_TFLT' and
v_group_code like 'TF%';
```

```
delete from CSSMS_GROUP_ROLE_MAP_UNAUTH where v_group_code in (select
v_group_code from CSSMS_GRP_ROLE_MAP_UNAUTH_PACK where v_app_id = 'OFS_TFLT'
and v_group_code like 'TF%');
```

```
delete from CSSMS_GRP_ROLE_MAP_UNAUTH_PACK where v_app_id = 'OFS_TFLT' and
v_group_code like 'TF%';
```

```
delete from cssms_group_role_map where V_GROUP_CODE in (select V_GROUP_CODE
from cssms_group_role_map_pack where v_app_id = 'OFS_TFLT');
```

```
delete from cssms_group_role_map_pack where v_app_id = 'OFS_TFLT';
```

```
delete from DOCUMENT_USER_GROUP_MAP where v_usergroup_id in (select
v_group_code from CSSMS_GROUP_MAST_PACK where v_app_id = 'OFS_TFLT' and
v_group_code like 'TF%');
```

```
delete from CSSMS_GROUP_MAST where v_group_code in (select v_group_code from
CSSMS_GROUP_MAST_PACK where v_app_id = 'OFS_TFLT' and v_group_code like
'TF%');
```

```
delete from CSSMS_GROUP_MAST_PACK where v_app_id = 'OFS_TFLT' and
v_group_code like 'TF%';
```

```
delete from cssms_role_function_map where exists (select 1 from
cssms_role_function_map_pack where cssms_role_function_map.v_function_code =
cssms_role_function_map_pack.v_function_code
```

```
and cssms_role_function_map.V_ROLE_CODE =
cssms_role_function_map_pack.V_ROLE_CODE and v_app_id = 'OFS_TFLT');
```



```
delete from cssms_role_function_map_pack where v_app_id = 'OFS_TFLT';  
delete from CSSMS_ROLE_MAST_PACK where v_app_id = 'OFS_TFLT';  
delete from CSSMS_FUNCTION_MAST_PACK where v_app_id = 'OFS_TFLT';
```

## **OFSAA Support Contact Details**

Raise a Service Request (SR) in [My Oracle Support \(MOS\)](#) for queries related to OFSAA applications.

## Send Us Your Comments

Oracle welcomes your comments and suggestions on the quality and usefulness of this publication. Your input is an important part of the information used for revision.

- Did you find any errors?
- Is the information clearly presented?
- Do you need more information? If so, where?
- Are the examples correct? Do you need more examples?
- What features did you like most about this manual?

If you find any errors or have any other suggestions for improvement, indicate the title and part number of the documentation along with the chapter/section/page number (if available) and contact the Oracle Support.

Before sending us your comments, you might like to ensure that you have the latest version of the document wherein any of your concerns have already been addressed. You can access My Oracle Support site which has all the revised/recently released documents.

