

Oracle Financial Services
Compliance Regulatory Reporting
Administration Guide Canada STR

Release 8.0.6.0.0

May 2018



Oracle Financial Services
Compliance Regulatory Reporting
Administration Guide Canada STR

Release 8.0.6.0.0
May 2018

Part Number: E86129-02

Oracle Financial Services Software, Inc.
1900 Oracle Way
Reston, VA 20190

Part Number: E70640-02
First Edition (May 2018)

Copyright © 2018 Oracle and/or its affiliates. All rights reserved.

Printed in U.S.A. No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise without the prior written permission.

Trademarks

Oracle is a registered trademark of Oracle Corporation and/or its affiliates.
Other names may be trademarks of their respective owners.

Oracle Financial Services Software, Inc.
1900 Oracle Way
Reston, VA 20190
Phone: (703) 478-9000
Fax: (703) 318-6340
Internet: www.oracle.com/financialservices

Contents

About This Guide	III
Who Should Use this Guide	III
How this Guide is Organized	III
Where to Find More Information.....	IV
Conventions Used in this Guide	IV
CHAPTER 1 <i>OFS CRR User Setup</i>.....	1
Creating Users and User Groups	1
Mapping User Group to Infodomain.....	1
Mapping Users To User Groups.....	1
CHAPTER 2 <i>Loading the Static Data and Product Supplied Metadata into OFS CRR</i>.....	3
Loading Client Specific Data	3
Configuring Security Attributes for Users	4
Loading Product Supplied Metadata	5
CHAPTER 3 <i>Integrating OFS CRR Application with Multiple AML Systems ...</i>	7
Prerequisites.....	7
Integrating OFS CRR Application with OFSFCCM	9
Integrating OFS CRR Application with Oracle Mantas 5.x.....	11
CHAPTER 4 <i>Configuring Parameters</i>.....	13
Report Lock Period.....	13
Due Date.....	13
Currency Code Configuration	13
UCM_GROUP_NAME	14

About This Guide

This guide provides comprehensive instructions to perform administration activities to configure the Oracle Financial Services Compliance Regulatory Reporting (herein referred to as OFS CRR).

This chapter focuses on the following topics:

- Who Should Use this Guide
- How this Guide is Organized
- Where to Find More Information
- Conventions Used in this Guide

Who Should Use this Guide

The *Oracle Financial Services Compliance Regulatory Reporting Administration Guide* is designed for use by Oracle Financial Services administration users. Their roles and responsibilities, as they operate within the OFS CRR application, include the following:

- **System Administrator:** This user configures, maintains, and adjusts the system and is usually an employee of a specific Oracle Financial Services client. The System Administrator maintains user accounts and roles, archives data, and loads data feeds.

How this Guide is Organized

The *Oracle Financial Services Compliance Regulatory Reporting Administration Guide*, includes the following topics:

- Chapter 1, *OFS CRR User Setup*, describes the steps involved in user creation.
- Chapter 2, *Loading the Static Data and Product Supplied Metadata into OFS CRR*, explains the steps involved in loading static data.
- Chapter 3, *Integrating OFS CRR Application with Multiple AML Systems*, explains the steps involved in integration of RR application with OFSFCCM / Oracle Mantas 5.x application.
- Chapter 4, *Configuring Parameters*, explains the steps to configure the report lock time period, due date, and currency code parameters.

Where to Find More Information

For more information on OFS CRR, refer to the following documents in [OTN](#):

- *Oracle Financial Services Compliance Regulatory Reporting Installation Guide*
- *Oracle Financial Services Compliance Regulatory Reporting Data Model Reference Guide*
- *Oracle Financial Services Compliance Regulatory Reporting Release Notes*
- *Oracle Financial Services Compliance Regulatory Reporting Canada Suspicious Transaction Report User Guide*
- *Oracle Financial Services Compliance Regulatory Reporting Web Services Guide*
- *Oracle Financial Services Compliance Regulatory Reporting ReadMe*

To find additional information about how Oracle Financial Services solves real business problems, see our website at www.oracle.com/financialservices.

Conventions Used in this Guide

Table 1 lists the conventions used in this guide.

Table 1. Conventions Used in this Guide

Convention	Meaning
<i>Italics</i>	<ul style="list-style-type: none">● Names of books, chapters, and sections as references● Emphasis
Bold	<ul style="list-style-type: none">● Object of an action (menu names, field names, options, button names) in a step-by-step procedure● Commands typed at a prompt● User input
Monospace	<ul style="list-style-type: none">● Directories and subdirectories● File names and extensions● Process names● Code sample, including keywords and variables within text and as separate paragraphs, and user-defined program elements within text
<Variable>	Substitute input value

This chapter describes how to provide access to users in the OFS CRR applications, through the user groups.

This chapter includes the following topics:

- Creating Users and User Groups
- Mapping User Group to Infodom
- Mapping Users To User Groups

Creating Users and User Groups

1. For creating users, refer to the *Oracle Financial Services Analytical Applications Infrastructure User Guide*, available in [OTN](#).

Note: If you are integrating OFS CRR with OFSFCCM, then do not create the OFS CRR administration user. The user mapped to the role of OFSFCCM administrator is automatically mapped to the role of OFSCRR administrator.

2. Once the users are created, map the users to the predefined user groups, which in turn map to a user role.

For more information about the above sections, refer *Oracle Financial Services Analytical Applications Infrastructure User Guide*, available in [OTN](#).

Note: While creating user groups manually using the SMS AAI interface, use the precedence range/values between 3001 to 3899.

Table 2. Group Description

Group Code	Group NAME	Group DESCRIPTION
RRCAANALYST1	RRCAANALYST1	RR Canada Analyst1 User Group
RRCAANALYST2	RRCAANALYST2	RR Canada Analyst2 User Group
RRCAAUDITOR	RRCAAUDITOR	RR Canada Auditor User Group
RRCASUP	RRCASUP	RR Canada Supervisor Group

Mapping User Group to Infodom

Map all RR user groups to the RR Infodom (Regulatory Reporting Information Domain). For how to map user groups to an infodom, refer to the *Oracle Financial Services Analytical Applications Infrastructure User Guide* available in [OTN](#).

Mapping Users To User Groups

To create the Regulatory Report Analyst1 user for Canada, map to the RRCAANALYST1.

To create the Regulatory Report Analyst2 user for Canada, map to the RRCAANALYST2.

To create the Regulatory Report Auditor user for Canada, map to the RRCAAUDITOR.

To create the Regulatory Report Supervisor user for Canada, map to the RRCASUP.

Loading the Static Data and Product Supplied Metadata into OFS CRR

Loading Client Specific Data

1. To add client-specific security attributes to the OFS CRR system, navigate to <ftpshare path>/STAGE/Excelupload/Templates. The <ftpshare path> is the same path given in variable APP_DRIVE_TM while installing OFSAAI. For more information, refer to the *Oracle Financial Services Analytical Applications Infrastructure Installation and Configuration Guide* available in [OTN](#).
2. Download the following Excel sheets to the Windows machine from the path given in the previous step:
 - a. DIM_DOMAIN1.xlsx
 - b. DIM_DOMAIN2.xlsx
 - c. DIM_DOMAIN3.xlsx
 - d. DIM_DOMAIN4.xlsx
 - e. DIM_DOMAIN5.xlsx
 - f. DIM_REPORTING_ENTITY_LOC.xlsx
 - g. DIM_REPORTING_ENTITY_DTLS.xlsx
 - h. DIM_REPORTING_PERSON.xlsx
 - i. MAP_REPENTITYLOC_REPTYPE.xlsx
 - j. MAP_REPENTITY_DTLS.xls
 - k. MAP_REPPERSON.xls
 - l. DIM_STATES.xlsx
3. Add data in each Excel sheet as per your report requirement by referring to the *Oracle Financial Services Data Model Reference Guide*.
 - a. DIM_DOMAIN1.xlsx must be filled with Jurisdictions which are available in OFSFCCM. For more information refer to section, *Security Attribute1 Static Information* in the *Oracle Financial Services Data Model Reference Guide*.
 - b. DIM_DOMAIN2.xlsx must be filled with Business Domains which are available in OFSFCCM. For more information refer to section, *Security Attribute2 Static Information* in the *Oracle Financial Services Data Model Reference Guide*.
 - c. DIM_DOMAIN3.xlsx must be filled with Case Type and Case SubType which are available in OFSFCCM. For more information refer to section, *Security Attribute3 Static Information* in the *Oracle Financial Services Data Model Reference Guide*.
 - d. DIM_DOMAIN4.xlsx must be filled with Organizations which are available in OFSFCCM. For more information refer to section, *Security Attribute4 Static Information* in the *Oracle Financial Services Data Model Reference Guide*.
 - e. DIM_DOMAIN5.xlsx must be filled with Scenario Classes which are available in OFSFCCM. For more information refer to section, *Security Attribute5 Static Information* in the *Oracle Financial Services Data Model Reference Guide*.

- f. `DIM_REPORTING_ENTITY_LOC.xlsx`, for more information, refer to section Reporting Entity Location in *Oracle Financial Services Data Model Reference Guide*.
 - g. `DIM_REPORTING_ENTITY_DTLS.xlsx`, for more information, refer to section Reporting Entity Details in *Oracle Financial Services Data Model Reference Guide*.
 - h. `DIM_REPORTING_PERSON.xlsx`, for more information, refer to section Reporting Person Information in *Oracle Financial Services Data Model Reference Guide*.
 - i. `DIM_STATES.xlsx`, for more information, refer to section State Information in *Oracle Financial Services Data Model Reference Guide*.
4. Login to OFS CRR as Admin user created in the previous section.
 5. Navigate to Unified Metadata Manager > Data Entry Forms and Queries > Excel Upload. The Excel Upload page is displayed.
Note: After logging into the application, make sure the OFS CRR application Information Domain is selected from the drop-down list at the left hand corner of the page.
 6. Click **Browse** under Excel File to Upload.
 7. Select the Excel sheet.
 8. Click the Arrow button next to Browse.
 9. Preview the data created under the Preview section.
 10. In the Excel - Entity Mappings section, click the Arrow.
 11. Select the table name with the same name as that of the Excel sheet.
 12. Click **Upload**. The following message is displayed: *Successfully uploaded data*
 13. Click **OK**.
Note: Scan the web application server log for any errors after uploading each Excel sheet. For example, for Oracle Weblogic, the web application server log is `wls.out`, for Websphere, the web application server log is `Systemout.log` and `Systemerr.log`.
 14. Close the Excel Upload page.

Configuring Security Attributes for Users

1. If OFS CRR is installed on top of OFSFCCM, click **FCCM**. Navigate to Administration menu > User Administration > Regulatory Report User's Attribute Administration. A new page displays a drop-down list containing the OFS CRR users created in the previous section.

OR

If OFS CRR is installed as a standalone application, click **Administration**. A new page displays a drop-down list containing the OFS CRR users created in the previous section.

2. Assign attributes to each user from the drop-down list.
3. Close the Regulatory Report User's Attribute Administration screen.
4. Logout from the OFS CRR application.

5. Login with each created user in OFS CRR. The Password Reset page opens when the user logs in for the first time immediately after the creation, or every time that the SYSADMIN user resets the password for various reasons, such as when the user forgets the password or when the password is locked.
6. Reset the password. The OFS CRR application login page displays.
Note: You must log into the application using the new password.
7. If OFS CRR is installed on top of OFSFCCM, click **FCCM**. The OFS CRR application page displays.

OR

If OFS CRR is installed as a standalone application, click **Canada STR**. The OFS CRR application page displays.

Note: Follow these steps whenever a new user is added or modified (for User Details, User Group mapping, Roles mapping, Security Attribute mapping, and Password Change) in the OFS CRR application.

Loading Product Supplied Metadata

Follow these steps to configure the database:

Note: The following steps are not required if you already have the OFSFCCM application installed.

1. Add the meta data in the database by following these steps:

Note: The following steps can be followed if OFSBDF is installed. If OFSBDF is not installed or OFS CRR is installed as a standalone then run these sql's manually in RR Atomic schema.

2. Copy the following files from the ProductSuppliedMetadata folder under the Installer Kit to <OFSBDF_HOME>/database/db_tools/bin

For Canada STR

AtomicCASTR.sql and AtomicCASTR.cfg

For Indonesia STR

AtomicIDSTR.sql and AtomicIDSTR.cfg

For KCB STR

AtomicKCBSTR.sql and AtomicKCBSTR.cfg

For Egypt STR

AtomicEgyptSTR.sql and AtomicEgyptSTR.cfg

For Bahamas STR

AtomicBahamasSTR.sql and AtomicBahamasSTR.cfg

For Pakistan STR

AtomicPakistanSTR.sql and AtomicPakistanSTR.cfg

For New Zealand STR

AtomicNewZealandSTR.sql and AtomicNewZealandSTR.cfg

For Kenyan STR

Copy the below files from the ProductSuppliedMetadata folder under patch 2.5.1.0.0

AtomicKenyaSTR.sql and AtomicKenyaSTR.cfg

- a. Add rrs to variable `dbscript.execution.users` available in `<OFSBDF_HOME>/database/db_tools/mantas_cfg/install.cfg`

For example:

```
dbscript.execution.users=(system|business|mantas|market|miner|ingest|report|kdd_alt  
io|kdd|algorithms|case|rrs)
```

- b. Add the following variables in `<OFSBDF_HOME>/database/db_tools/mantas_cfg/db_variables.cfg`

```
rrs=<OFS CRR Atomic Schema User Name>, Refer place holder ##RRS_ATOMIC_USER## in  
GRC_InstallConfig.xml
```

```
RRSINFODOM=<OFS CRR Information Domain Name> , Refer place holder ##INFODOM_1##in  
GRC_InstallConfig.xml
```

```
RRSEGMENT=<OFS CRR Segment Name>, Refer place holder ##SEGMENT_1## in  
GRC_InstallConfig.xml
```

- c. Execute the following command:

```
<OFSBDF_HOME>/database/db_tools/bin/run_dbbuilder_utility.sh <the appropriate *.cfg  
file from step a>
```

- d. Enter the password of the OFS CRR atomic schema user password when it prompts.
- e. Check the `<OFSBDF_HOME>/database/db_tools/logs/db_builder.log` for any error in execution.

Integrating OFS CRR Application with Multiple AML Systems

Prerequisites

This section explains the prerequisites to be added in the `web.xml` if it is a standalone application. The following figure shows the `web.xml` files before entering axis servlet.

```

:
<servlet-mapping xmlns="http://java.sun.com/xml/ns/javaee_6" xmlns:web="http://java.sun.com/xml/ns/javaee/web-app_2_5_xsd">
  <servlet-name>QuestionreAnalyse</servlet-name>
  <url-pattern>/QuestionreAnalyse</url-pattern>
</servlet-mapping>
<servlet-mapping xmlns="http://java.sun.com/xml/ns/javaee_6" xmlns:web="http://java.sun.com/xml/ns/javaee/web-app_2_5_xsd">
  <servlet-name>QustnnnaireAnalyseOptions</servlet-name>
  <url-pattern>/QustnnnaireAnalyseOptions</url-pattern>
</servlet-mapping>
<servlet>
  <servlet-name>RRServlet</servlet-name>
  <servlet-class>com.ofs.reveleus.rrs.servlets.RRServlet</servlet-class>
</servlet>
<servlet>
  <servlet-name>RRDownloadServlet</servlet-name>
  <servlet-class>com.ofs.reveleus.rrs.servlets.RRDownloadServlet</servlet-class>
</servlet>
<servlet-mapping>
  <servlet-name>RRServlet</servlet-name>
  <url-pattern>/RRServlet</url-pattern>
</servlet-mapping>
<servlet-mapping>
  <servlet-name>RRDownloadServlet</servlet-name>
  <url-pattern>/RRDownloadServlet</url-pattern>
</servlet-mapping>
<resource-ref>
  <description>DB Connection RRINFO4</description>
  <res-ref-name>jdbc/RRINFO4</res-ref-name>
  <res-type>javax.sql.DataSource</res-type>
  <res-auth>Container</res-auth>
</resource-ref>
</web-app>

```

Add the following entries:

```

<servlet>
<servlet-name>AdminServlet</servlet-name>
<!-- <display-name>Axis Admin Servlet</display-name> -->
<servlet-class>org.apache.axis.transport.http.AdminServlet</servlet-class>
</servlet>
<servlet>
<servlet-name>AxisServlet</servlet-name>
<!-- <display-name>Apache-Axis Servlet</display-name> -->
<servlet-class>org.apache.axis.transport.http.AxisServlet</servlet-class>
</servlet>

```

```

</servlet>
<servlet>
  <servlet-name>AdminServlet</servlet-name>
  <!-- <display-name>Axis Admin Servlet</display-name> -->
  <servlet-class>org.apache.axis.transport.http.AdminServlet</servlet-class>
</servlet>
<servlet>
  <servlet-name>AxisServlet</servlet-name>
  <!-- <display-name>Apache-Axis Servlet</display-name> -->
  <servlet-class>org.apache.axis.transport.http.AxisServlet</servlet-class>
</servlet>

```

```

<servlet-mapping>
<servlet-name>AxisServlet</servlet-name>
<url-pattern>/servlet/AxisServlet</url-pattern>
</servlet-mapping>
<servlet-mapping>
<servlet-name>AxisServlet</servlet-name>
<url-pattern>*.jws</url-pattern>
</servlet-mapping>
<servlet-mapping>
<servlet-name>AxisServlet</servlet-name>
<url-pattern>/services/*</url-pattern>
</servlet-mapping>

```

```

</servlet-mapping>
<servlet-mapping>
  <servlet-name>AxisServlet</servlet-name>
  <url-pattern>/servlet/AxisServlet</url-pattern>
</servlet-mapping>
<servlet-mapping>
  <servlet-name>AxisServlet</servlet-name>
  <url-pattern>*.jws</url-pattern>
</servlet-mapping>
<servlet-mapping>
  <servlet-name>AxisServlet</servlet-name>
  <url-pattern>/services/*</url-pattern>
</servlet-mapping>

```

The following screenshots shows the web.xml files after entering the axis servlet entries:


```

<servlet-mapping xmlns="http://java.sun.com/xml/ns/javaee_6" xmlns:web="http://java.sun.com/xml/ns/javaee/web-app_2_5.xsd">
  <servlet-name>QuestionAnalyse</servlet-name>
  <url-pattern>/QuestionAnalyse</url-pattern>
</servlet-mapping>
<servlet-mapping xmlns="http://java.sun.com/xml/ns/javaee_6" xmlns:web="http://java.sun.com/xml/ns/javaee/web-app_2_5.xsd">
  <servlet-name>QustnnaireAnalyseOptions</servlet-name>
  <url-pattern>/QustnnaireAnalyseOptions</url-pattern>
</servlet-mapping>
<servlet>
  <servlet-name>RREServlet</servlet-name>
  <servlet-class>com.ofs.reveleus.rrs.servlets.RREServlet</servlet-class>
</servlet>
<servlet>
  <servlet-name>RRDownloadServlet</servlet-name>
  <servlet-class>com.ofs.reveleus.rrs.servlets.RRDownloadServlet</servlet-class>
</servlet>
<servlet>
  <servlet-name>AdminServlet</servlet-name>
  <!-- <display-name>Axis Admin Servlet</display-name -->
  <servlet-class>org.apache.axis.transport.http.AdminServlet</servlet-class>
</servlet>
<servlet>
  <servlet-name>AxisServlet</servlet-name>
  <!-- <display-name>Apache-Axis Servlet</display-name -->
  <servlet-class>org.apache.axis.transport.http.AxisServlet</servlet-class>
</servlet>
<servlet-mapping>
  <servlet-name>RREServlet</servlet-name>
  <url-pattern>/RREServlet</url-pattern>
</servlet-mapping>
<servlet-mapping>
  <servlet-name>RRDownloadServlet</servlet-name>
  <url-pattern>/RRDownloadServlet</url-pattern>
</servlet-mapping>
<servlet-mapping>
  <servlet-name>AxisServlet</servlet-name>
  <url-pattern>/servlet/AxisServlet</url-pattern>
</servlet-mapping>
<servlet-mapping>
  <servlet-name>AxisServlet</servlet-name>
  <url-pattern>*.jws</url-pattern>
</servlet-mapping>
<servlet-mapping>
  <servlet-name>AxisServlet</servlet-name>
  <url-pattern>/services/*</url-pattern>
</servlet-mapping>

```

The entries need to be made in the following locations:

- <>FIC_WEB_HOME) /webroot /WEB-INF /web.xml
- <Deployed Area> /profile.ear /profile.war /WEB-INF /web.xml

If the server is Websphere, then the same entries need to be added in the following location:

- <>FIC_WEB_HOME) /webroot /WEB-INF /web.xml
- <Deployed Area> /profile.ear /profile.war /WEB-INF /web.xml
- /<Deployed Area> /profiles /Profile_name /config /cells /<server>Node2Cell /applications /Profile_name.ear /deployments /Profile_name /Profile_name.war /WEB-INF /web.xml

Integrating OFS CRR Application with OFSFCCM

OFSFCCM or Oracle Mantas 5.x can be integrated with OFS CRR to post alerts or cases to generate reports with Webservice Calls. To know more about Webservices, refer *Oracle Financial Services Webservices Guide*. Both OFSFCCM/Oracle Mantas 5.x and OFS CRR application must be configured to use this webservice. This is an optional configuration and is required only when you want to integrate OFS CRR with OFSFCCM/Oracle Mantas 5.x.

1. For OFS CRR:

The OFS CRR application's Webservice is already configured with a default user name and password. This default password must be reset before performing the OFS CRR and OFSFCCM/Oracle Mantas 5.x integration. This step is mandatory from security aspect.

- a. To update password, follow these steps:
 - i. Log in as Administrator user.
 - ii. Navigate to **Administration > Web Service Configuration > Regulatory Report Web Service**.
 - iii. Enter the User ID as rruser. Do not add any other user name.
 - iv. Enter the desired password.
 - v. Click **Save**.
2. For OFSFCCM:
 - a. Login to the OFSFCCM application as Administration User.
 - b. Navigate to FCCM > Administration > Manage Parameters > Manage Common Parameters.
 - c. Select **Deployment Based** in the Parameter Category drop-down list.
 - d. Select **Regulatory Report Solution Web Service** from the Parameter Name drop-down list.
 - e. Set Parameter Value text box = Y.
 - f. Update the OFSRR web service URL by setting Attribute 3 Value: = <OFSRR URL>/services/InitiateRequest and ATTR_4_VALUE_TX <URL>/CRRframeworkDataingestion.
 - g. Click **Save**.
 - h. To update OFS CRR Webservice password in OFSFCCM, Navigate to FCCM > Administration > Web Service Configuration > Common Web Service
 - i. Enter the same password set in OFS CRR side in *Enter Password for Web Service* text box and click **Encrypt**.
 - j. Logout from the application.

3. Configuring CRR Service URL in Atomic Schema.

Execute the following SQL in atomic schema:

```
UPDATE CRR_CONFIGURATION SET V_PARAM_VALUE= '<URL>'
WHERE V_PARAM_NAME= 'CRR_SERVICE_URL';
commit;
```

Note: To perform PMF configuration, see PMF Chapter in [ECM Administration Guide](#)

Integrating OFS CRR Application with Oracle Mantas 5.x

1. For Oracle Mantas 5.x

a. Update the variables in <Oracle Mantas

Home>/alert_management/alert_mgmt/WEB-INF/classes/conf/mantas_cfg/install.cfg as follows

```
#RRS Web Service parameters
```

```
rrs.userid=rruser
```

```
rrs.password= <Encrypt the same password given in step 1 using Change Password Utility of Oracle Mantas 5.x>
```

```
rrs.service.url=<OFS CRR URL>/services/InitiateRequest
```

```
rrs.version=2.5
```

then recreate the war file and deploy in the web application server.

b. By default, OFS CRR Web Service is configured to capture data coming from OFSFCCM. If OFS CRR is to be configured to accept data from Oracle Mantas 5.x, then execute the following SQL using OFS CRR atomic schema user:

```
UPDATE SETUP_WEBSERVICE_CONFIG SET V_WEB_SERIVICE_URL = '<Mantas 5.x URL>/services/RRSUpdateService ' WHERE V_SOURCE_NAME = 'MANTAS'COMMIT;
```

Note: The above highlighted placeholder needs to be updated with the mantas URL.

c. For disabling or enabling the feedback to Mantas, execute the following SQL using OFS CRR atomic schema user:

```
UPDATE SETUP_WEBSERVICE_CONFIG T SET T.F_ENABLE_FLAG = '<N or Y>' WHERE T.V_SOURCE_NAME = 'MANTAS'COMMIT;
```

To enable feedback, value must be 'Y' and for disabling feedback, it should be 'N'.

Report Lock Period

If any user forgets to logoff from the OFS CRR application or if the OFS CRR screen is closed while accessing a report, the report gets locked for a pre configured duration. By default, the duration is 60 minutes. This duration can be altered as per your requirement.

Execute the following SQL using OFS CRR atomic schema user:

```
UPDATE APPLN_PARAMETERS SET V_ATTRIBUTE_VALUE1= '<DURATION IN MINUTES>'
WHERE V_ATTRIBUTE_NAME1= 'LOCK PERIOD IN MINUTES';
COMMIT;
```

Due Date

The due date is set to N days from the date the request is sent from Alert Management/Case Management to RR, where N is a configurable number of days. The N days filing time should exclude both holidays and weekends, that is, it refers specifically to business days. Due date can be modified by any user, based on the configurability as mentioned in the following table.

Table 3. Due Date

Attribute Name	Value	Default pre-pack aged value	Behavior	SQL
Number of Days	N	5 (Days)	When an RR report is created manually or via action from alert/ case, automatically sets due date to action date + N calendar days. If parameter is blank then no date is set.	<pre>UPDATE APPLN_PARAMETERS SET V_ATTRIBUTE_VALUE1= '<NUMBER OF DAYS>' WHERE N_PARAM_IDENTIFIER= 33; COMMIT;</pre>

Currency Code Configuration

This field is used to set a currency code for the template.

```
UPDATE APPLN_PARAMETERS SET V_ATTRIBUTE_VALUE1= '<CURRENCY_CODE>' WHERE N_PARAM_IDENTIFIER=
37; COMMIT;
```

UCM_GROUP_NAME

When you attach a report to the regulatory report, the group code configured in the `UCM_GROUP_NAME` parameter of the configuration table of AAI is validated. This parameter contains the value of a valid group name that appears during the AAI installation and is mapped to the business user performing the action. You can get the value for this parameter by executing the following query in the configuration schema of the AAI application:

```
select PARAMVALUE from  
configuration  
where PARAMNAME='UCM_GROUP_NAME'
```


