

Oracle Financial Services Compliance Regulatory Reporting

Canadian STR Administration Guide

Release 8.1.2.1.0

August 2023

F28072-01

ORACLE[®]
Financial Services

OFS CRR Canadian STR Administration Guide

Copyright © 2023 Oracle and/or its affiliates. All rights reserved.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are “commercial computer software” pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

For information on third party licenses, click [here](#).

Document Control

Table 1: Document Control

Version Number	Revision Date	Change Log
1.0	June 2022	No content updates for this release.

Contents

1	About This Guide.....	3
1.1	Who Should Use This Guide	3
1.2	How this Guide is Organized.....	3
1.3	Where to Find More Information	3
1.4	Conventions Used in this Guide.....	4
2	Administration Workflow.....	5
3	Setting Users	6
3.1	Creating Users.....	6
3.2	Mapping Users To User Groups.....	6
3.3	Logging in and Resetting Password.....	7
4	Loading Data into OFSCRR.....	8
4.1	Loading Client-Specific Data	8
4.1.1	<i>Uploading Excel</i>	9
4.2	Loading Product Supplied Metadata	10
4.3	Configuring Security Attributes for Users.....	10
5	Integrating with the ECM Application.....	11
5.1	Configuring Webservice in OFSCRR.....	11
5.2	Configuring CRR Service URL in Atomic Schema	11
5.3	Configuring Webservice in OFSECM.....	11
5.3.1	<i>Updating OFSCRR Webservice password in OFSECM</i>	12
5.4	Configuring Processing Modeling Framework (PMF)	13
6	Configuring Parameters	14
6.1	Report Lock Period	14
6.2	Activity Information	14
6.3	Currency Code	15
6.4	UCM Group Name	15
6.5	Assigning Default User	15
6.6	Configuring Institution Name for Cash Transaction	16
6.7	Configuring Multiple Instances	16
6.7.1	<i>Configuring Multiple Instance Attribute Flag</i>	16

6.7.2	<i>Configuring PMF</i>	16
6.7.3	<i>Configuring Report URLs</i>	17
6.7.4	<i>Configuring Case Jurisdiction and Report Type Mapping</i>	17
6.8	Configuring Prohibited Documents	18
6.9	Configuring CA STR OPERATIONAL MODE	18
7	OFSAA Support Contact Details	19
8	Send Us Your Comments	20

1 About This Guide

This guide provides instructions to configure the Oracle Financial Services Compliance Regulatory Reporting Report (OFS CRR).

This chapter focuses on the following topics:

- [Who Should Use This Guide](#)
- [How this Guide is Organized](#)
- [Where to Find More Information](#)
- [Conventions Used in this Guide](#)

1.1 Who Should Use This Guide

The *Oracle Financial Services Compliance Regulatory Reporting* is designed for use by Oracle Financial Services Administration users.

Their roles and responsibilities, as they operate within the OFSCRR application, include the following:

- Configure, maintain, and adjust the system
- Maintain user accounts and roles, archive data, and load data feeds

1.2 How this Guide is Organized

The *Oracle Financial Services Compliance Regulatory Reporting* includes the following chapters:

- [Chapter 2, Administration Workflow](#)
Explains the administration work flow in the OFSCRR application.
- [Chapter 3, Setting Users](#),
describes the steps involved in creating users.
- [Chapter 4, Loading Data into OFSCRR](#), explains the steps for loading client-specific data and product supplied metadata.
- [Chapter 5, Integrating with the ECM Application](#), explains the steps involved in the integration of the CRR application with OFS ECM.
- [Chapter 6, Configuring Parameters](#), explains the steps to configure the report lock time period, due date, and currency code parameters.

1.3 Where to Find More Information

For more information on OFSCRR, refer to the following documents in [OHC](#):

- Oracle Financial Services Compliance Regulatory Reporting Installation Guide
- Oracle Financial Services Compliance Regulatory Reporting Data Model Reference Guide
- Oracle Financial Services Compliance Regulatory Reporting Release Notes/ReadMe
- Oracle Financial Services Compliance Regulatory Reporting User Guide
- Oracle Financial Services Compliance Regulatory Reporting Web Services Guide

To find additional information about how Oracle Financial Services solves real business problems, see our website at

www.oracle.com/financialservices.

1.4 Conventions Used in this Guide

Table 1 lists the conventions used in this guide.

Table 1: Conventions Used in this Guide

Conventions	Descriptions
Italics	<ul style="list-style-type: none"> Names of books, chapters, and sections as references Emphasis
Bold	<ul style="list-style-type: none"> An Object of an action (menu names, field names, options, button names) in a step-by-step procedure Commands typed at a prompt User input
Monospace	<ul style="list-style-type: none"> Directories and subdirectories File names and extensions Process names Code sample, including keywords and variables within a text and as separate paragraphs, and user-defined program elements within a text
<Variable>	Substitute input value

2 Administration Workflow

This chapter describes the Administrator workflow in the OFSCRR application. The following image shows the workflow for an Administrator.

Figure 1: Administrator workflow




Table 2 lists the administration workflow in tabular format.

Table 2: Administrator workflow

Workflow	Description
Setting Users	Provide access to users in the OFSCRR application through the user groups.
Loading Data into OFSCRR	Load-client specific data and product supplied metadata in the OFSCRR application.
Integrating with the ECM Application	Integrate OFSECM with OFSCRR to post cases to generate reports with Webservice calls.
Configuring Parameters	Configure the Report Lock Period, Activity Information, Currency Code, UCM Group Name, Assigning Default User, Configuring Institution Name for Cash Transaction, Configuring Case Jurisdiction and Report Type, and Mapping Configuring Multiple Instances, Configuring CA STR OPERATIONAL MODE, Configuring Lookback Period in Days.

3 Setting Users

This chapter describes how to provide access to users in the OFSCRR application through the user groups and includes the following topics:

- [Creating Users](#)
- [Mapping Users To User Groups](#)
- [Logging in and Resetting Password](#)

3.1 Creating Users

To create users, follow these steps:

1. To create the users, see the *Object Administration* section in the [Oracle Financial Services Analytical Applications Infrastructure User Guide](#).

NOTE If you are integrating OFSCRR with OFSECM, it is optional to create the OFSCRR Administrator user. The user mapped to the role of OFSECM Administrator can be mapped to the role of OFSCRR Administrator.

2. Map the users to the predefined user groups, which in turn map to the user role. For more information, see the *Object Administration* section in the [Oracle Financial Services Analytical Applications Infrastructure User Guide](#).

The following table provides information about the predefined user groups that are mapped to the created users.

[Table 3](#) explains the group code, group name, and group description.

Table 3: Group Description

Group Code	Group Name	Group Description
RRCAANALYST1	RRCAANALYST1	RR Canada Analyst1 User Group
RRCAANALYST2	RRCAANALYST2	RR Canada Analyst2 User Group
RRCAAUDITOR	RRCAAUDITOR	RR Canada Auditor User Group
RRCASUP	RRCASUP	RR Canada Supervisor Group
RRADMINISTRATOR	RRADMINISTRATOR	RR Administrator Group

3.2 Mapping Users To User Groups

Use the following table to map the users to pre-defined user groups.

[Table 4](#) explains user names, their actions, and group name the user is associated.

Table 4: Mapping Users to User Groups

User	Description	Group Name
Analyst1	Reg Report Analyst Role	RRCAANALYST1
Analyst2	Reg Report Analyst Role	RRCAANALYST2

Table 4: Mapping Users to User Groups

User	Description	Group Name
Supervisor	Reg Report Supervisor Role	RRCASUP
Auditor	Reg Report Auditor Role	RRCAAUDITOR
Administrator	Reg Report Administrator Role	RRADMINISTRATOR

3.3 Logging in and Resetting Password

To log in and reset password, follow these steps:

1. Log in with each created user in OFSCRR. The Password Reset page is displayed.

NOTE This page is displayed when a user logs in for the first time immediately after that user has been created, or every time the SYS-ADMN user resets the password. For example, when the user forgets the password or when the password is locked.

2. Reset the password. The OFSCRR application login page is displayed.

NOTE You must log in to the application using the new password.

3. The OFSCRR application landing page is displayed. Click **Compliance Regulatory Reporting**.
4. Hover over **Canadian STR**. Select Search and List page, Create New Report or File Reports.

NOTE Follow these steps whenever a new user is added or modified (for User Details, User Group mapping, Security Attribute mapping, and Password Change).

4 Loading Data into OFSCRR

This chapter includes the following topics:

- Loading Client-Specific Data
- Loading Product Supplied Metadata
- Configuring Security Attributes for Users

4.1 Loading Client-Specific Data

This section explains steps to load client specific data in to the OFSCRR application.

To load client-specific data, follow these steps:

1. Navigate to <ftpshare path>/STAGE/Excelupload/Templates.
2. The <ftpshare path> is the same path given in variable OFSAAI_FTP in OFSAAI_InstallConfig.xml while installing OFSAAI. For more information, see *Configuring OFSAAI_InstallConfig.xml File* section in the [Oracle Financial Services Analytical Applications Infrastructure User Guide](#).
3. Download the following Excel sheets to the Windows machine from the path given in the previous step

[Table 5](#) describes table name and reference to the data model.

Table 5: Excel Sheets

Excel Sheet	Description	Reference to the Data Model Reference Guide
DIM_DOMAIN1.xlsx	Provide the list of all Jurisdictions which are available in OFSECM.	Security Attribute1 Static Information section.
DIM_DOMAIN2.xlsx	Provide the list of all Business Domains which are available in OFSECM.	Security Attribute2 Static Information section.
DIM_DOMAIN3.xlsx	Provide the list of all Case Type and Case SubType which are available in OFSECM.	Security Attribute3 Static Information section.
DIM_DOMAIN4.xlsx	Provide the list of all Organizations that are available in OFSECM.	Security Attribute4 Static Information section.
DIM_DOMAIN5.xlsx	Provide the list of all Scenario Classes which are available in OFSECM.	Security Attribute5 Static Information section.
DIM_COUNTRY.xlsx	Provide the list of all Countries that need to be made available to the application	Country Information section
DIM_STATES.xlsx	Provide the list of all states for the countries that need to be made available to the application.	State Information section
DIM_REPORTING_ENTITY_LOC.xlsx	Provide the list of all reporting entity location.	Reporting Entity Location section

Table 5: Excel Sheets

Excel Sheet	Description	Reference to the Data Model Reference Guide
DIM_REPORTING_ENTITY_DTLS.xlsx	Provide the list of all reporting entities.	Reporting Entity Details section
DIM_REPORTING_PERSON.xlsx	Provide the list of all reporting persons.	Reporting Person Information section
DIM_TRXN_LOC_INFO.xlsx	Provide the list of all branches.	Branch Information section
MAP_REPENTITYDTLS_REPTYPE.xlsx	Provide the list of all mapping for reporting entity and CA-STR report type.	Reporting Entity Details section
MAP_REPENTITYLOC_REPTYPE.xlsx	Provide the list of all mapping for branches/reporting entity location and CA-STR report type.	Report type Information section
MAP_TRXNLOC_ENTITY_DTLS.xlsx	Provide the list of all mapping for reporting entity and branches/reporting entity location.	Report entity Information section.
MAP_REPPERSON_REPTYPE.xlsx	Provide the list of all mapping for reporting person and CA-STR report type.	Report person type Information section.
MAP_ENTITY_DTLS_LOC.xlsx	Provide the list of all mapping for reporting entity, entity location and CA-STR report type.	Report entity location Information section.
MAP_REP_NTITY_REP_PERSON	Provide the list of all mappings for reporting entity and reporting person with priority.	Report entity Information section.

NOTE

- The column `N_PRNT_REPENTITY_SKEY` in `DIM_REPORTING_ENTITY_DTLS` table is used to capture the parent reporting entity key value.
- If your reporting entity does not have parent reporting entity, then do not enter any value in this column.
- In case, an incorrect value is provided, the reporting entity information will not be populated in the E-File batch header, which may lead to the rejection of report by regulator.
- The column `F_DEFAULT_FL` in `MAP_REP_NTITY_REP_PERSON` table is used to capture the default mapping of the reporting person to the reporting entity. The value =Y indicates the default value.

4. Add data in each Excel sheet as per your report requirement. For more information, see the [Oracle Financial Services Data Model Reference Guide](#).

4.1.1 Uploading Excel

To upload the Excel, follow these steps:

1. Log in to OFSCRR application as the Administrator user.
2. Navigate to Compliance Regulatory Reporting. Click **Excel Upload (Atomic)**.
3. Select the **Excel Upload**. The Excel Upload page is displayed.

Figure 2: Excel Upload

The screenshot shows the 'Excel Upload' interface. At the top, there's a title 'Excel Upload' and a sub-header 'Excel Upload'. Below this, there's a section titled 'Excel File to Upload' which contains a file selection area with a 'Choose File' button and 'No file chosen' text, and a 'Sheet:' dropdown menu. Below that, there's a section titled 'Excel-Entity Mappings' which contains a 'Select Mapping' dropdown menu. At the bottom of the page, there are two buttons: 'Upload' and 'View Log'.

4. Click **Choose File** from Excel File to Upload. Select the sheet from the drop-down list.
5. In the Excel - Entity Mappings section, click the **Select the Mapping** arrow. Select the table name with the same name as that of the Excel sheet.
6. Click **Upload**. The confirmation message is displayed.

4.2 Loading Product Supplied Metadata

This section explains how to load the pre-packaged data of the OFS CRR application, such as the ISO code of the country, template (CA STR) specific codes, and so on

To load the product supplied metadata, follow these steps:

Execute the SQL AtomicCANSTR.sql in the CRR Atomic schema.

This file is packaged in the CRR installer kit under the path OFS_CRR_PACK/OFS_CRR/ProductSuppliedMetadata/CANSTR.

4.3 Configuring Security Attributes for Users

To configure security attributes for users, follow these steps:

1. Log in as the Administrator user.
2. Click **User Administration**. The User Attribute page is displayed.
3. Select the user from the User Name drop-down list.
4. Assign attributes to each user from the drop-down list.
5. Click **Save**. The confirmation message is displayed.

5 Integrating with the ECM Application

OFSECM is integrated with OFSCRR to post cases to generate reports with Webservice calls. For more information about Webservice, see the [Oracle Financial Services Webservices Guide](#).

Both OFSECM and OFSCRR applications must be configured to use this Webservice.

NOTE This is an optional configuration and is required only when you want to integrate OFSCRR with OFSECM.

This chapter covers the following topics:

- [Configuring Webservice in OFSCRR](#)
- [Configuring CRR Service URL in Atomic Schema](#)
- [Configuring Webservice in OFSECM](#)
- [Configuring Processing Modeling Framework \(PMF\)](#)

5.1 Configuring Webservice in OFSCRR

The OFSCRR application's Webservice is already configured with a default user name and password. This default password must be reset before performing the OFSCRR and OFSECM integration. This step is mandatory for security reasons.

To update the password, follow these steps:

1. Log in as the Administrator.
2. Navigate to Compliance Regulatory Reporting.
3. Select **Webservice Configuration**. The Configuring Web service User ID and Password page is displayed.
4. Enter the User ID as `rruser`.

NOTE Do not add any other user name.

5. Enter the desired password.
6. Click **Save**. A confirmation message is displayed.

5.2 Configuring CRR Service URL in Atomic Schema

To configure the CRR service URL in the Atomic Schema, execute the following SQL:

```
UPDATE CRR_CONFIGURATION SET V_PARAM_VALUE= '<URL>'
WHERE V_PARAM_NAME= 'CRR_SERVICE_URL';
commit;
```

5.3 Configuring Webservice in OFSECM

To configure Webservice in OFSECM, follow these steps:

1. Login to the OFSECM application as the Administrator.

2. Navigate to Financial Services Case Management.
3. Select **Case Management Configuration** and click **Manage Common Parameters**. The Manage Common Parameter page is displayed.
4. Select *Deployment Based* from the Parameter Category drop-down list.
5. Select *Regulatory Report Solution Web Service* from the Parameter Name drop-down list.
6. Set Parameter Value text box = Y.
7. Update the OFSRR web service URL by setting the following attribute values.
 - Attribute1 value = ruser
 - Attribute 3 Value = <URL>/RRSService/InitiateRequest
 - Attribute 4 Value = <URL>/CRRframeworkDataingestion

NOTE <URL> must be in the following format: http://<Web application server name>:<port>/<context>

8. Click **Save**. A confirmation message is displayed.

5.3.1 Updating OFSCRR Webservice password in OFSECM

To update the OFSCRR Webservice password in OFSECM, follow these steps:

1. Login to the OFSECM application as the Administrator.
2. Navigate to Financial Services Case Management. Select *Case Management Configuration*.
3. Click **Configuration of Web Service**. The Configuration of Web Service page is displayed.

Figure 3: Configuration of Web Service

Encrypt Utility		
Enter Password for Regulatory Reporting Web Service:	<input type="text"/>	Encrypt
Enter Password for Common Gateway Service:	<input type="text"/>	Encrypt
Enter Password for Create JSON Service:	<input type="text"/>	Encrypt
Enter Password for KYC Onboarding Risk Score Service URL:	<input type="text"/>	Encrypt

4. Enter the password for *Regulatory Reporting Web Service* and click **Encrypt**.

NOTE Enter the same password as set in OFSCRR.

5. Logout from the application.

5.4 Configuring Processing Modeling Framework (PMF)

The Enterprise Case Management Processing Modeling Framework (PMF) facilitates built-in tooling for orchestration of human and automatic workflow interfaces. This enables the Administrator to create process-based ECM. It also enables the Administrator to model business processes and workflow.

To perform PMF configuration, see the PMF Chapter in the [ECM Administration Guide](#).

6 Configuring Parameters

This chapter covers the following topics:

- Report Lock Period
- Activity Information
- Currency Code
- UCM Group Name
- Assigning Default User
- Configuring Institution Name for Cash Transaction
- Configuring Prohibited Documents
- Configuring CA STR OPERATIONAL MODE
- Configuring Lookback Period in Days

6.1 Report Lock Period

If a user forgets to log off from the OFSRR application or if the OFSRR screen is closed while accessing a report, the report gets locked for a pre-configured duration. By default, the duration is 60 minutes. This duration can be altered as per your requirement.

To alter the duration, execute the following SQL using OFSRR atomic schema user:

```
UPDATE APPLN_PARAMETERS SET V_ATTRIBUTE_VALUE1= '<DURATION IN MINUTES>'
WHERE V_ATTRIBUTE_NAME1= 'LOCK PERIOD IN MINUTES';
COMMIT;
```

6.2 Activity Information

The due date is set to N days from the date the request is sent from ECM to CRR, where N is a configurable number of days. The N days filing time should exclude both holidays and weekends, that is, it refers specifically to business days. The Due date can be modified by any user, based on the configuration mentioned in the following table.

Table 6 provides activity details such as attribute name, value, default pre-packaged value, behavior, and SQL.

Table 6: Activity Information

Attribute Name	Value	Default pre-packaged value	Behavior	SQL
Number of Days	N	5 (Days)	When a CRR report is created manually or through ECM action, it automatically sets due date to action date + N calendar days. If the parameter is blank then no date is set.	<pre>UPDATE APPLN_PARAMETERS SET V_ATTRIBUTE_VALUE1 = '<NUMBER OF DAYS>' WHERE N_PARAM_IDENTIFIER = 33; COMMIT;</pre>

6.3 Currency Code

To configure currency code for the template, use the field - 'Currency'

To get the value for Currency Code, execute the following query in the atomic schema for CRR application

```
SELECT V_ATTRIBUTE_NAME1, V_ATTRIBUTE_VALUE1 from APPLN_PARAMETERS where
N_PARAM_IDENTIFIER=44;
```

To configure the Report Lock Period, execute the following SQL using OFSCRR atomic schema user:

```
UPDATE APPLN_PARAMETERS SET V_ATTRIBUTE_VALUE1= 'CAD' WHERE N_PARAM_IDENTIFIER = 44;
COMMIT;
```

6.4 UCM Group Name

When you attach a report to the regulatory report, the group code configured in the UCM_GROUP_NAME parameter of the configuration table of AAI is validated. This parameter contains the value of a valid group name that appears during the AAI installation and it is mapped to the business user performing the action.

You can get the value for this parameter by executing the following query in the configuration schema of the AAI application.

```
select PARAMVALUE from
configuration
where PARAMNAME='UCM_GROUP_NAME'
```

To update the above parameter, execute the following query.

```
update CONFIGURATION set PARAMVALUE = 'RRADMINISTRATOR' where PARAMNAME =
'UCM_GROUP_NAME';
```

6.5 Assigning Default User

This parameter defines the default user who shall be assigned all the CA STR reports that are created through the OFSECM system through posting by taking the 'Generate CA STR' action.

To get the value for this parameter, execute the following query in the atomic schema of the OFSCRR application.

```
SELECT V_ATTRIBUTE_NAME2, V_ATTRIBUTE_VALUE2 FROM APPLN_PARAMETERS WHERE
N_PARAM_IDENTIFIER = 44;
```

To update the above parameter, execute the following query.

```
UPDATE APPLN_PARAMETERS SET V_ATTRIBUTE_VALUE2 = '<User Id for Default User>' WHERE
N_PARAM_IDENTIFIER = 44;
```

6.6 Configuring Institution Name for Cash Transaction

This parameter defines the value to be populated in the **Part B1.8 - Other institution name and number or other person or entity** field in the UI.

NOTE This is applicable when a report is generated through OFS ECM by taking **Generate CASTR** action.

To get the value for this parameter, execute the following query in the atomic schema of the OFSCRR application.

```
SELECT V_ATTRIBUTE_NAME1, V_ATTRIBUTE_VALUE1 FROM APPLN_PARAMETERS WHERE
N_PARAM_IDENTIFIER = 53;
```

To update the above parameter, execute the following query.

```
UPDATE APPLN_PARAMETERS SET V_ATTRIBUTE_VALUE1 = '<institution name that needs to be
displayed>' WHERE N_PARAM_IDENTIFIER = 53;
```

6.7 Configuring Multiple Instances

This configuration enables multiple instances (STRs) of OFS CRR application from the single OFS ECM instance. You can use a single OFS ECM application instance to generate multiple report types.

This section covers the following topics:

- [Configuring Multiple Instance Attribute Flag](#)
- [Configuring PMF](#)
- [Configuring Report URLs](#)
- [Configuring Case Jurisdiction and Report Type Mapping](#)

6.7.1 Configuring Multiple Instance Attribute Flag

To configure multi instances of the OFS CRR application, follow these steps:

1. Login to the OFSECM application as an Administrator.
2. Navigate to Financial Services Case Management.
3. Select **Case Management Configuration** and click **Manage Common Parameters**. The Manage Common Parameter page is displayed.

4. Select **Deployment Based** on the **Parameter Category** drop-down list.
5. Select **Regulatory Report Solution Web Service** from the Parameter Name drop-down list.
6. Set Parameter Value text box = **Y**.
7. Update the multiple instance attribute flag by setting, **Attribute 6 value = Y**.
8. Click **Save**. A confirmation message is displayed.

6.7.2 Configuring PMF

To enable two or more **Generate STR** actions in the OFS ECM application for each STR type, you must configure process modeling framework. For more information, see the *Configuring Processing Modeling Framework* chapter in the [Administration and Configuration Guide](#).

6.7.3 Configuring Report URLs

Login into the ECM Atomic Schema and execute the following SQL statement by replacing the placeholder:

```
update KDD_REG_REPORT_TYPE t set t.REPORT_URL = '<URL for STR>/RRService/InitiateRequest' where t.REG_TYPE_CD = 'CASTR';
```

For example, update KDD_REG_REPORT_TYPE t set t.REPORT_URL = 'http://whf00abc:1200/CRR808/RRService/InitiateRequest' where t.REG_TYPE_CD = 'CASTR';

6.7.4 Configuring Case Jurisdiction and Report Type Mapping

NOTE

One or more jurisdictions can be mapped to only one Regulatory Report Type if the **MultInstance** option is enabled.

For example, if AMEA and APAC are mapped to CA STR, then they cannot be mapped to any other STRs.

In the Enterprise Case Management (ECM) application, case jurisdiction must be mapped to the report type to generate a report in the OFS CRR CA STR application.

To perform this activity, follow these steps:

1. Login into the ECM Atomic Schema and execute the following SQL statement by replacing the following placeholders
 - **##Jurisdiction Code##** : The values for KDD_JRSDCN_REPORT_TYPE_MAP.JRSDCN_CD must come from the table KDD_JRSDCN.JRSDCN_CD.
 - **##Regulatory Report Type Code##** : The values for KDD_JRSDCN_REPORT_TYPE_MAP.REG_TYPE_CD must come from the table KDD_REG_REPORT_TYPE.REG_TYPE_CD.
 2. Insert into KDD_JRSDCN_REPORT_TYPE_MAP values ('##Jurisdiction Code##', '##Regulatory Report Type Code##');
- For example, insert into KDD_JRSDCN_REPORT_TYPE_MAP values ('JRSD1' , 'RTYP1');

6.8 Configuring Prohibited Documents

This attribute specifies the configurable values for document types that are confidential and should not be migrated to CRR.

To perform this activity, follow these steps:

1. Login into the ECM Atomic Schema and execute the following SQL statement by replacing the following placeholders
 - **##Prohibited Document Names##**: The value for the prohibited documents must be provided in the parameter. These document types shall not be migrated to CRR during the promote to the STR process.
2. UPDATE KDD_INSTALL_PARAM SET ATTR_7_VALUE_TX = ##Prohibited Document Names## where PARAM_ID= 7;

For example,

3. Update KDD_INSTALL_PARAM SET ATTR_7_VALUE_TX = 'SIN, SIN NUMBER' where PARAM_ID= 7;

6.9 Configuring CA STR OPERATIONAL MODE

The parameter “CA STR OPERATIONAL MODE” is used to set the Operation Mode of the CASTR Application and the value of this parameter is captured in the CASTR E-file. When the CASTR application is used in test or lower environments for implementation, the value of this parameter must be set to “T”, but once the CASTR application is migrated to production and is used to file CASTR reports in the Production environment, this value must be updated to “P”.

NOTE An incorrect value of this parameter will lead to the E-File rejection on the regulatory portal. Acceptable values are P and T.

To perform this activity, follow these steps:

1. Login into the ECM Atomic Schema and execute the following SQL statement by replacing the following placeholders.

```
UPDATE APPLN_PARAMETERS SET V_ATTRIBUTE_VALUE1= '<MODE OF OPERATION>'
WHERE N_PARAM_IDENTIFIER = 52;
COMMIT;
```

For example,

```
UPDATE APPLN_PARAMETERS SET V_ATTRIBUTE_VALUE1= 'T'
WHERE N_PARAM_IDENTIFIER = 52;
COMMIT;
```

6.10 Configuring Lookback Period in Days

This configuration allows you customize the Created Date From in the Report Search and List, E-File Tab Search, and Acknowledgment Tab Search.

- Attribute value for Report Search and List - 1

- Attribute value for E-File tab Search and List - 2
- Attribute value for Acknowledgment tab Search and List - 3

To configure lookback period in days, follow these steps:

1. Login into AtomicSchema and update the following paramvalue in the query:

```
select * from appln_parameters where n_param_identifier='54';
```

OFSAA Support Contact Details

Raise a Service Request (SR) in [My Oracle Support \(MOS\)](#) for queries related to OFSAA applications.

Send Us Your Comments

Oracle welcomes your comments and suggestions on the quality and usefulness of this publication. Your input is an important part of the information used for revision.

- Did you find any errors?
- Is the information clearly presented?
- Do you need more information? If so, where?
- Are the examples correct? Do you need more examples?
- What features did you like most about this manual?

If you find any errors or have any other suggestions for improvement, indicate the title and part number of the documentation along with the chapter/section/page number (if available) and contact the Oracle Support.

Before sending us your comments, you might like to ensure that you have the latest version of the document wherein any of your concerns have already been addressed. You can access My Oracle Support site which has all the revised/recently released documents.

