

**Oracle® ZFS Storage Appliance Object
API Guide for Swift Service Support,
Release OS8.8.0**

ORACLE®

Part No: E91295-02
January 2019

Part No: E91295-02

Copyright © 2018, 2019, Oracle and/or its affiliates. All rights reserved.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

Access to Oracle Support

Oracle customers that have purchased support have access to electronic support through My Oracle Support. For information, visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

Référence: E91295-02

Copyright © 2018, 2019, Oracle et/ou ses affiliés. Tous droits réservés.

Ce logiciel et la documentation qui l'accompagne sont protégés par les lois sur la propriété intellectuelle. Ils sont concédés sous licence et soumis à des restrictions d'utilisation et de divulgation. Sauf stipulation expresse de votre contrat de licence ou de la loi, vous ne pouvez pas copier, reproduire, traduire, diffuser, modifier, accorder de licence, transmettre, distribuer, exposer, exécuter, publier ou afficher le logiciel, même partiellement, sous quelque forme et par quelque procédé que ce soit. Par ailleurs, il est interdit de procéder à toute ingénierie inverse du logiciel, de le désassembler ou de le décompiler, excepté à des fins d'interopérabilité avec des logiciels tiers ou tel que prescrit par la loi.

Les informations fournies dans ce document sont susceptibles de modification sans préavis. Par ailleurs, Oracle Corporation ne garantit pas qu'elles soient exemptes d'erreurs et vous invite, le cas échéant, à lui en faire part par écrit.

Si ce logiciel, ou la documentation qui l'accompagne, est livré sous licence au Gouvernement des Etats-Unis, ou à quiconque qui aurait souscrit la licence de ce logiciel pour le compte du Gouvernement des Etats-Unis, la notice suivante s'applique :

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

Ce logiciel ou matériel a été développé pour un usage général dans le cadre d'applications de gestion des informations. Ce logiciel ou matériel n'est pas conçu ni n'est destiné à être utilisé dans des applications à risque, notamment dans des applications pouvant causer un risque de dommages corporels. Si vous utilisez ce logiciel ou ce matériel dans le cadre d'applications dangereuses, il est de votre responsabilité de prendre toutes les mesures de secours, de sauvegarde, de redondance et autres mesures nécessaires à son utilisation dans des conditions optimales de sécurité. Oracle Corporation et ses affiliés déclinent toute responsabilité quant aux dommages causés par l'utilisation de ce logiciel ou matériel pour des applications dangereuses.

Oracle et Java sont des marques déposées d'Oracle Corporation et/ou de ses affiliés. Tout autre nom mentionné peut correspondre à des marques appartenant à d'autres propriétaires qu'Oracle.

Intel et Intel Xeon sont des marques ou des marques déposées d'Intel Corporation. Toutes les marques SPARC sont utilisées sous licence et sont des marques ou des marques déposées de SPARC International, Inc. AMD, Opteron, le logo AMD et le logo AMD Opteron sont des marques ou des marques déposées d'Advanced Micro Devices. UNIX est une marque déposée de The Open Group.

Ce logiciel ou matériel et la documentation qui l'accompagne peuvent fournir des informations ou des liens donnant accès à des contenus, des produits et des services émanant de tiers. Oracle Corporation et ses affiliés déclinent toute responsabilité ou garantie expresse quant aux contenus, produits ou services émanant de tiers, sauf mention contraire stipulée dans un contrat entre vous et Oracle. En aucun cas, Oracle Corporation et ses affiliés ne sauraient être tenus pour responsables des pertes subies, des coûts occasionnés ou des dommages causés par l'accès à des contenus, produits ou services tiers, ou à leur utilisation, sauf mention contraire stipulée dans un contrat entre vous et Oracle.

Accès aux services de support Oracle

Les clients Oracle qui ont souscrit un contrat de support ont accès au support électronique via My Oracle Support. Pour plus d'informations, visitez le site <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> ou le site <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> si vous êtes malentendant.

Contents

About ZFS Object Store	7
OpenStack Object Storage API	9
Supported OpenStack Object Storage API Capabilities	9
Discoverability	9
Accounts	10
Containers	10
Objects	12
Swift Command-Line Client	13
Swift Examples	13
List containers using the default path	14
List containers using a specified share location	14
List objects in a container	14
Create/upload object to container	14
Download container	14
Delete container	14
Download object	14
Delete object	14
Set metadata to an object	15
Get metadata from an object	15
Upload a large file with segments using Dynamic Large Object	15
Download large file uploaded using Dynamic Large Object	15
Bulk Delete or Bulk Upload	15
Curl Command-Line Examples	16
Get authorization token	16
Create a container	17
List containers in plain text format	17
List containers in json format	18

List objects inside a container	18
List objects inside a container in json format	19
Upload a local file image.jpg to a container	20
Delete an object from a container	20
Download an object to the local filesystem	20
Set user metadata to an object	21
Get metadata of an object	21
Copy an object from one container to another container	21
Versioning Objects	22

About ZFS Object Store

Oracle ZFS Storage Appliance systems allow users to store data objects using ZFS object store. This capability is implemented using either OpenStack Object Storage API V1.0, also known as Swift, which uses an HTTP RESTful interface, or the Amazon Simple Storage Service (S3) API, which also uses an HTTP RESTful interface. This guide describes how to use the OpenStack Object Storage APIs.

For information on how to configure the ZFS object store data service, see [“Object API Configuration”](#) in *Oracle ZFS Storage Appliance Administration Guide, Release OS8.8.0*.

For information on how to use the Amazon S3 API, see *Oracle ZFS Storage Appliance Object API Guide for Amazon S3 Service Support, Release OS8.8.0*.

For best practices and more information about object store, refer to the whitepaper [Using Oracle ZFS Storage Appliance as an Object Store Repository](#).

OpenStack Object Storage API

Oracle ZFS Storage Appliance systems implement their object capability with OpenStack Object Storage API v1.0, also known as Swift, using an HTTP RESTful interface.

The OpenStack Object Storage API uses three elements to access an object: <Account-Name>, <Container-Name>, and <Object-Name>.

In the Oracle ZFS Storage Appliance object storage implementation, the share export path is used for the OpenStack account object. It is specified in the storage URL; for example, `http://<ObjectStoreNode>/v1/export/<ShareName>/<ContainerName>/<ObjectName>`

For more information on OpenStack Object Storage API, see the following topics:

- “Supported OpenStack Object Storage API Capabilities” on page 9
- “Swift Command-Line Client” on page 13
- “Curl Command-Line Examples” on page 16

Supported OpenStack Object Storage API Capabilities

The following topics describe the supported OpenStack Object Storage API V1.0 capabilities for Oracle ZFS Storage Appliance.

For full details about OpenStack Object Storage API, including descriptions of the request and response parameters, see the OpenStack Object Storage API documentation: <http://developer.openstack.org/api-ref-objectstorage-v1.html>.

Note - Some optional request and response parameters are not supported by Oracle ZFS Storage Appliance systems. Unsupported parameters are listed in the following tables.

Discoverability

If configured, lists the activated capabilities for this version of the OpenStack Object Storage API.

TABLE 1 Discoverability Commands

Request	Path	Description	Normal response codes	Unsupported Request Parameters	Unsupported Response Parameters
GET	/info	Lists the activated capabilities for this version of the OpenStack Object Storage API.	200	swiftinfo_sig, swiftinfo_expires	

Accounts

These operations are used to perform account-level tasks.

TABLE 2 Accounts Commands

Request	Path	Description	Normal response codes	Unsupported Request Parameters	Unsupported Response Parameters
GET	/v1/{account}	Shows account details and list containers, sorted by name, in the account	200, 204	X-Newest, Accept, X-Trans-Id-Extra	X-Account-Meta-Temp-URL-Key, X-Account-Meta-Temp-URL-Key-2
POST	/v1/{account}	Creates, updates, or deletes account metadata	204	X-Account-Meta-Temp-URL-Key, X-Account-Meta-Temp-URL-Key-2, X-Trans-Id-Extra	
HEAD	/v1/{account}	Shows account metadata	204	X-Newest, X-Trans-Id-Extra	X-Account-Meta-Temp-URL-Key, X-Account-Meta-Temp-URL-Key-2

Containers

These operations are used to perform container-level tasks.

TABLE 3 Containers Commands

Request	Path	Description	Normal response codes	Unsupported Request Parameters	Unsupported Response Parameters
GET	/v1/{account}/ {container}	Shows details for a container and lists objects, sorted	200, 204	X-Newest, Accept, X-Container-Meta-Temp-URL-Key, X-Container-Meta-	X-Container-Meta-Temp-URL-Key, X-Container-Meta-Temp-URL-Key-2

Request	Path	Description	Normal response codes	Unsupported Request Parameters	Unsupported Response Parameters
		by name, in the container		Temp-URL-Key-2, X-Trans-Id-Extra	
PUT	/v1/{account}/ {container}	Creates a container	201, 204	X-Container-Sync-To, X-Container-Sync-Key, X-Container-Meta-Access-Control-Allow-Origin, X-Container-Meta-Access-Control-Max-Age, X-Container-Meta-Access-Control-Expose-Headers, X-Newest, Accept, X-Container-Meta-Temp-URL-Key, X-Container-Meta-Temp-URL-Key-2, X-Trans-Id-Extra	
DELETE	/v1/{account}/ {container}	Deletes an empty container	204	X-Container-Meta-Temp-URL-Key, X-Container-Meta-Temp-URL-Key-2, X-Trans-Id-Extra	
POST	/v1/{account}/ {container}	Creates, updates, or deletes container metadata	204	X-Remove-Container-name, X-Container-Sync-To, X-Container-Sync-Key, X-Container-Meta-Access-Control-Allow-Origin, X-Container-Meta-Access-Control-Max-Age, X-Container-Meta-Access-Control-Expose-Headers, X-Container-Meta-Quota-Bytes, X-Container-Meta-Quota-Count, X-Container-Meta-Web-Directory-Type, X-Container-Meta-Temp-URL-Key, X-Container-Meta-Temp-URL-Key-2, X-Trans-Id-Extra	

Request	Path	Description	Normal response codes	Unsupported Request Parameters	Unsupported Response Parameters
HEAD	/v1/{account}/ {container}	Shows container metadata, including the number of objects and the total bytes of all objects stored in the container.	204	X-Newest, X-Trans-Id-Extra, X-Container-Meta-Temp-URL-Key, X-Container-Meta-Temp-URL-Key-2, X-Trans-Id-Extra	X-Container-Meta-Access-Control-Allow-Origin, X-Container-Meta-Access-Control-Max-Age, X-Container-Meta-Access-Control-Expose-Headers,, X-Container-Meta-Quota-Bytes, X-Container-Meta-Quota-Count, X-Container-Sync-To, X-Container-Sync-Key, X-Container-Meta-Temp-URL-Key, X-Container-Meta-Temp-URL-Key-2

Objects

These operations are used to perform object-level tasks.

TABLE 4 Objects Commands

Request	Path	Description	Normal response codes	Unsupported Request Parameters	Unsupported Response Parameters
GET	/v1/{account}/ {container}/{object}	Downloads the object content and gets the object metadata	200	X-Newest, temp_url_sig, temp_url_expires, filename, X-Trans-Id-Extra	Content-Disposition, X-Static-Large-Object
PUT	/v1/{account}/ {container}/{object}	Creates an object with data content and metadata, or replaces an existing object with data content and metadata	201	temp_url_sig, temp_url_expires, filename, Transfer-Encoding, Content-Disposition, X-Trans-Id-Extra	
COPY	/v1/{account}/ {container}/{object}	Copies an object to another object in the object store	201	Content-Disposition, X-Fresh-Metadata, X-Trans-Id-Extra	

Request	Path	Description	Normal response codes	Unsupported Request Parameters	Unsupported Response Parameters
DELETE	/v1/{account}/ {container}/{object}	Permanently deletes an object from the object store	204	X-Trans-Id-Extra	
POST	/v1/{account}/ {container}/{object}	Creates or updates object metadata	202	Content-Disposition, X-Trans-Id-Extra,	
HEAD	/v1/{account}/ {container}/{object}	Shows object metadata	200, 204	temp_url_sig, temp_url_expires, filename, X-Newest, X-Trans-Id-Extra	Content-Disposition, X-Static-Large-Object

Swift Command-Line Client

OpenStack Object Storage provides a command-line client, `swift`, that can be used to interface with ZFS object store. The `swift` command-line client is an open-source Python client that can be run on Linux or Mac OS X systems.

The following table describes the `swift` client commands.

TABLE 5 Swift Commands

Command	Description
<code>delete</code>	Delete a container or objects within a container.
<code>download</code>	Download objects from containers.
<code>list</code>	Lists the containers for the account or the objects for a container.
<code>post</code>	Updates meta information for the account, container, or object; creates containers if not present.
<code>copy</code>	Copies object, optionally adds meta.
<code>stat</code>	Displays information for the account, container, or object.
<code>upload</code>	Uploads files or directories to the given container.

Swift Examples

The following examples show how to use the `swift` command-line client.

Note - The HTTPS protocol is supported as well as HTTP.

List containers using the default path

```
swift -A http://zfssa:80/auth/v1.0 -U user -K key list
```

The output lists the containers that are part of an account.

List containers using a specified share location

```
swift -A http://zfssa:80/auth/v1.0/export/fs1 -U user -K key list
```

List objects in a container

```
swift -A http://zfssa:80/auth/v1.0/ -U user -K key list containerA
```

Create/upload object to container

```
swift -A http://zfssa:80/auth/v1.0/ -U user -K key upload containerA object1
```

Download container

```
swift -A http://zfssa:80/auth/v1.0/ -U user -K key download containerA
```

Delete container

```
swift -A http://zfssa:80/auth/v1.0/ -U user -K key delete containerA
```

Download object

```
swift -A http://zfssa:80/auth/v1.0/ -U user -K key download containerA object1
```

Delete object

```
swift -A http://zfssa:80/auth/v1.0/ -U user -K key delete containerA object1
```

Set metadata to an object

```
swift -A http://zfssa:80/auth/v1.0/ -U user -K key post containerA object1 --header "X-Object-Meta-Movie: comedy"
```

Get metadata from an object

```
swift -A http://zfssa:80/auth/v1.0/ -U user -K key stat -v containerA object1
```

Upload a large file with segments using Dynamic Large Object

Dynamic Large Object is a middleware component supported by Oracle ZFS Storage Appliance.

```
swift -A http://zfssa:80/auth/v1.0/ -U user -K key upload containerA large_file -S 100000000
```

Download large file uploaded using Dynamic Large Object

Dynamic Large Object is a middleware component supported by Oracle ZFS Storage Appliance.

```
swift -A http://zfssa:80/auth/v1.0/ -U user -K key download containerA large_file
```

Bulk Delete or Bulk Upload

Bulk Delete and Bulk Upload are middleware components supported by Oracle ZFS Storage Appliance.

In the following example, three objects are created in a container called Various. A file called `object_to_delete` contains the name of the objects to be deleted. A `curl` command is used to delete those objects.

Multiple file uploads can be accomplished in a similar manner, using the `bulk-upload` option.

```
        # swift -U swift1 -K swift1 \ -A http://192.168.0.200/v1/export/MyMusic \
upload --object-name a1 Various aa.txt
a1
# swift -U swift1 -K swift1 \ -A http://192.168.0.200/v1/export/MyMusic \ upload --
object-name a2 Various aa.txt
a2
# swift -U swift1 -K swift1 \ -A http://192.168.0.200/v1/export/MyMusic \ upload --
object-name a3 Various aa.txt
a3
# vi object_to_delete

        # cat objects_to_delete
Various/a1
Various/a2
Various/a3
# swift -U swift1 -K swift1 \ -A http://192.168.0.200/v1/export/MyMusic/Various list
DabyToure&SkipMcDonald.mp3
a1
a2
a3
aa.txt
# curl -X DELETE -H "X-Auth-Token: $token" \ -T objects_to_delete \ "http://192.
168.0.200/v1/export/MyMusic/Various/?bulk-delete"
Number Deleted: 3
Number Not Found: 0
Response Body:
Response Status: 200 OK
Errors:
# swift -U swift1 -K swift1 \ -A http://192.168.0.200/v1/export/MyMusic/Various list
DabyToure&SkipMcDonald.mp3
aa.txt
#
```

Curl Command-Line Examples

This section shows examples of how to use curl to execute different requests.

Get authorization token

Example input:


```
curl -i http://zfssa:80/auth/v1.0 -X GET -H "X-Auth-User: user" -H "X-Auth-Key: key"  
curl -i http://zfssa:80/auth/v1.0/export/fs1 -X GET -H "X-Auth-User: user" -H "X-Auth-  
Key: key"
```

Example output:

```
HTTP/1.1 200 OK  
Date: Wed, 04 Apr 2018 15:09:39 GMT  
Server: Apache  
X-Storage-Url: http://zfssa:80/object/v1/export/fs1  
X-Storage-Token: ZFSSA_4607de64-def4-11e5-9326-7b36bda5fa3f  
X-Auth-Token: ZFSSA_4607de64-def4-11e5-9326-7b36bda5fa3f  
Content-Length: 0  
X-Trans-Id: tx8f482f16643e495eadee4-0056d45f34
```

Note - Use X-Storage-Url as the endpoint and X-Auth-Token for the remainder of the transactions.

Create a container

The following example input creates a container named containerA:

```
curl -i http://zfssa:80/v1/export/fs1/containerA -X PUT -H "Content-Length: 0" -H "X-  
Auth-Token: ZFSSA_4607de64-def4-11e5-9326-7b36bda5fa3f"
```

List containers in plain text format

Example input:

```
curl -i http://zfssa:80/object/v1/export/fs1 -X GET -H "X-Auth-Token: ZFSSA_4607de64-  
def4-11e5-9326-7b36bda5fa3f"
```

Example output:

```
HTTP/1.1 200 OK  
Date: Wed, 04 Apr 2018 13:48:57 GMT  
Server: Apache  
X-Timestamp: 1491400137.51  
X-Account-Object-Count: 39  
X-Account-Container-Count: 3  
X-Account-Bytes-Used: 9823586  
X-Trans-Id: tx1fd6145d8b3d4d9fdf0a8-0058e4f5c9  
Transfer-Encoding: chunked
```

```
Content-Type: text/plain; charset=utf-8
```

```
cont1  
container2  
test2
```

List containers in json format

Example input:

```
curl "http://zfssa:80/v1/export/fs1?format=json" -X GET -H "X-Auth-Token:  
ZFSSA_4607de64-def4-11e5-9326-7b36bda5fa3f" | python -mjson.tool
```

Example output:

```
[  
  {  
    "bytes": 1664,  
    "count": 5,  
    "name": "cont1",  
    ...  
  },  
  {  
    "bytes": 8902134,  
    "count": 25,  
    "name": "container2",  
    ...  
  },  
  {  
    "bytes": 919788,  
    "count": 9,  
    "name": "test2",  
    ...  
  }  
]
```

List objects inside a container

Example input:

```
curl -i "http://zfssa:80/v1/export/fs1/cont1" -X GET -H "X-Auth-Token: ZFSSA_efcd2042-  
1a05-11e7-baf9-80144f20c6bc"
```

Example output:

```

HTTP/1.1 200 OK
Date: Wed, 04 Apr 2018 14:01:16 GMT
X-Container-Bytes-Used: 1664
...
X-Container-Object-Count: 5
...
source.conf
source.conf_cam_rev
source.conf_chena
source.conf_demo
source.sh
]

```

List objects inside a container in json format

Example input:

```
curl "http://zfssa:80/v1/export/fs1/cont1?format=json" -X GET -H "X-Auth-Token: ZFSSA_efcd2042-1a05-11e7-baf9-80144f20c6bc" | python -mjson.tool
```

Example output:

```

[
  {
    "bytes": 360,
    "content_type": "None",
    "hash": "d3ca560c566fb522e5cb3d923ffd398a",
    "last_modified": "2018-03-08T00:21:18",
    "name": "source.conf"
  },
  {
    "bytes": 229,
    "content_type": "None",
    "hash": "cde5bd3e14dc1a1f6182a09f38b9c7f5",
    "last_modified": "2018-03-08T00:21:12",
    "name": "source.conf_cam_rev"
  },
  {
    "bytes": 223,
    "content_type": "None",
    "hash": "264d93bd075da83fd2f027bf96eb508f",
    "last_modified": "2018-03-08T00:21:15",
    "name": "source.conf_chena"
  },
  {
    "bytes": 375,
    "content_type": "None",

```

```
    "hash": "21b1e9e1378a825ac026ced97cccc6b9",
    "last_modified": "2018-03-08T00:21:16",
    "name": "source.conf_demo"
  },
  {
    "bytes": 477,
    "content_type": "None",
    "hash": "2b79330805bd6c6163404b5ec85ea776",
    "last_modified": "2018-03-08T00:21:12",
    "name": "source.sh"
  }
]
```

Upload a local file image.jpg to a container

Example input:

```
curl -i http://zfssa:80/v1/export/fs1/cont1/image.jpg -X PUT -H "X-Auth-Token:
ZFSSA_efcd2042-1a05-11e7-baf9-80144f20c6bc" -T image.jpg
```

Example output:

```
HTTP/1.1 201 Created
Date: Wed, 04 Apr 2018 14:24:17 GMT
Etag: 93e67dc3fc447b9a368dafa03cbf4aa7
```

Delete an object from a container

Example input:

```
curl -i http://zfssa:80/v1/export/fs1/cont1/image.jpg -X DELETE -H "X-Auth-Token:
ZFSSA_efcd2042-1a05-11e7-baf9-80144f20c6bc"
```

Example output:

```
HTTP/1.1 204 No Content
Date: Wed, 04 Apr 2018 14:27:34 GMT
...
```

Download an object to the local filesystem

Example input:

```
curl http://zfssa:80/v1/export/fs1/cont1/image.jpg -X GET -H "X-Auth-Token: ZFSSA_efcd2042-1a05-11e7-baf9-80144f20c6bc" -O
```

Set user metadata to an object

A user's metadata can be done as part of a PUT operation when uploading the object, or a POST operation (updating an existing object). In this example, the user's metadata is tagged as `movie` and the value is `comedy`.

Example input:

```
curl -i http://zfssa:80/v1/export/fs1/cont1/source.conf_demo -X POST -H "X-Object-Meta-Movie: comedy" -H "X-Auth-Token: ZFSSA_efcd2042-1a05-11e7-baf9-80144f20c6bc"
```

Get metadata of an object

Getting metadata of an object does not download the content of the object.

Example input:

```
curl -i http://zfssa:80/v1/export/fs1/cont1/source.conf_demo -I -H "X-Auth-Token: ZFSSA_efcd2042-1a05-11e7-baf9-80144f20c6bc"
```

Example output:

```
HTTP/1.1 200 OK
Content-Length: 375
...
X-Object-Meta-MOVIE: comedy
...
```

Copy an object from one container to another container

In this example, `image.jpg` is copied from container `cont1` to container `cont2` on the same account.

Example input:

```
curl -i -X PUT -H "Content-Length: 0" -H "X-Auth-Token: ZFSSA_efcd2042-1a05-11e7-baf9-80144f20c6bc" -H "X-Copy-From: /cont1/image.jpg" http://zfssa:80/v1/export/fs1/cont2/image.jpg
```

Example output:

```
HTTP/1.1 201 Created
Date: Wed, 04 Apr 2018 15:24:21 GMT
X-Object-Meta-MTIME: 1491401363.904874
X-Copied-From: cont1/image.jpg
...
Etag: 93e67dc3fc447b9a368dafa03cbf4aa7
X-Copy-From-Account: user
X-Copied-From-Last-Modified: 1491402764
...
```

Versioning Objects

The following examples show how to create a container to archive objects, enable versioning on that container, upload several versions of an object, and then show the archive for the container.

Create a container to archive objects:

```
curl -i http://zfssa:80/v1/export/fs1/archive -X PUT -H "Content-Length: 0" -H "X-Auth-Token: ZFSSA_4607de64-def4-11e5-9326-7b36bda5fa3f"
```

Enable versioning on a container:

```
curl -i http://zfssa:80/v1/export/fs1/container1 -X PUT -H "Content-Length: 0" -H "X-Auth-Token: ZFSSA_4607de64-def4-11e5-9326-7b36bda5fa3f" -H "X-Versions-Location: archive"
```

Upload object to container 'container1':

```
echo xx > example.txt
curl -i http://zfssa:80/v1/export/fs1/container1/example.txt -X PUT -H "X-Auth-Token: ZFSSA_4607de64-def4-11e5-9326-7b36bda5fa3f" -T example.txt
```

Modify object and upload it again:

```
echo yy > example.txt
curl -i http://zfssa:80/v1/export/fs1/container1/example.txt -X PUT -H "X-Auth-Token: ZFSSA_4607de64-def4-11e5-9326-7b36bda5fa3f" -T example.txt
```

List container1 content:

```
curl -i http://zfssa:80/v1/export/fs1/container1 -H "X-Auth-Token: ZFSSA_4607de64-def4-11e5-9326-7b36bda5fa3f"
HTTP/1.1 200 OK
.....
X-Container-Object-Count: 1
```

```
X-Versions-Location: archive
```

```
....  
f.txt
```

List archive content:

```
curl -i http://zfssa:80/v1/export/fs1/archive -H "X-Auth-Token: ZFSSA_4607de64-def4-11e5-9326-7b36bda5fa3f"
```

```
X-Container-Bytes-Used: 33
```

```
...
```

```
X-Container-Object-Count: 2
```

```
...
```

```
005example.txt/1493210484.16
```

```
005example.txt/1493210812.52
```

List archive content using swift:

```
swift -A http://zfssa:80/v1/export/fs1/archive -U user -K key list -l archive
```

```
15 2018-04-26 12:41:24 f.txt
```

```
18 2018-04-26 12:46:52 f.txt
```

```
33
```

