

Oracle Financial Services Data Foundation Application Pack

Installation and Configuration Guide

Release 8.0.9.2.0

Dec 2020

ORACLE
Financial Services

ORACLE

OFS Data Foundation Application Pack Installation and Configuration Guide

Copyright © 2020 Oracle and/or its affiliates. All rights reserved.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are “commercial computer software” pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

For information on third party licenses, click [here](#).

Document Control

Version Number	Revision Date	Change Log
1.0	10-July-2020	Created the document and redesigned with instructions for the installation and configuration of the OFSDF Release 8.0.9.2.0.
2.0	14-December-2020	Added the WebLogic upgrade information in the Pre-installation Requirements section.
3.0	17-December-2021	The OFSAAI mandatory patch 33663417 information is added.

Table of Contents

1	Preface	5
1.1	Summary.....	Error! Bookmark not defined.
1.2	Audience	5
1.3	Prerequisites for the Audience	Error! Bookmark not defined.
1.4	How this Guide is Organized	5
1.5	Access to Oracle Support	5
1.6	Related Documents	6
1.7	Conventions	6
1.8	Abbreviations	7
2	OFS Data Foundation Application Pack Maintenance Release v8.0.9.2.0	9
2.1	Pre-installation Requirements	9
2.2	How to Apply this Maintenance Release?	10
2.2.1	<i>Downloading OFS Data Foundation Application Pack</i>	10
2.2.2	<i>Pre-installation Activities</i>	12
2.2.3	<i>Installing the OFS Data Foundation Application Pack</i>	12
2.2.4	<i>Post-installation Activities</i>	13
3	Appendix A	16
3.1	Frequently Asked Questions	16

1 Preface

This document provides instructions to install the Oracle Financial Services Data Foundation (OFSDF) Application Pack v8.0.9.2.0 Maintenance Level (ML) Release.

Topics:

- [Audience](#)
- [How this Guide is Organized](#)
- [Access to the Oracle Support](#)
- [Related Documents](#)
- [Conventions](#)
- [Abbreviations](#)

1.1 Audience

This document is intended for Administrators, Business User, Strategists, and Data Analyst, who are responsible for installing and maintaining the application pack components.

- OFSAA Application Components
- OFSAA Architecture
- UNIX Commands
- Database Concepts
- OFSDF Data Model

1.2 How this Guide is Organized

The OFSDF Application Pack Installation Guide includes the following sections:

- [OFSDF Application Pack Release 8.0.9.2.0](#): This section provides information about the prerequisites, pre-installation, installation, and post-installation procedures for the OFSDF Application Pack Release v8.0.9.2.0.
- [Appendix A](#): This section provides information about the FAQs for the OFSDF Application Pack Release v8.0.9.2.0.

1.3 Access to the Oracle Support

Oracle customers have access to electronic support through My Oracle Support. For information, visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

1.4 Related Documents

We strive to keep this and all other related documents updated regularly; visit the [OHC Documentation Library](#) to download the latest version available there. The list of related documents is provided as follows:

- [OHC Documentation Library](#) for the OFSDF Application Pack Release 8.0.9.x.x User Guide documents:
 - *Oracle Financial Services Data Foundation Application Pack User Guide Release 8.0.9.0.0*
- [OHC Documentation Library](#) for the OFSDF Application Pack Release 8.0.9.x.x Installation and Configuration Guide documents:
 - *Oracle Financial Services Data Foundation Application Pack Installation and Configuration Guide Release 8.0.9.0.0*
- [OHC Documentation Library](#) for the OFS AAI Application Pack Release 8.0.9.x.x Installation and Configuration Guide documents:
 - *Oracle Financial Services Analytical Applications Infrastructure Installation Guide 8.0.9.1.0*
 - *Oracle Financial Services Analytical Applications Infrastructure Installation Guide Release 8.0.7.0.0*
- [OHC Documentation Library](#) for the OFS AAI Application Pack Release 8.0.9.x.x User Guide documents:
 - *Oracle Financial Services Analytical Applications Infrastructure User Guide Release 8.0.9.0.0*
- [OHC Documentation Library](#) for the OFS AAI Application Pack Release 8.0.9.x.x Technology Matrix documents:
 - *Oracle Financial Services Analytical Applications Technology Matrix*

1.5 Conventions

The following text conventions are used in this document.

Table 1: Document Conventions

Convention	Meaning
boldface	Boldface type indicates graphical user interface elements associated with an action or terms defined in text or the glossary.
<i>Italic</i>	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.
Monospace	Monospace type indicates commands within a paragraph, URLs, code in examples, file names, text that appears on the screen, or text that you enter.
Hyperlink	Hyperlink type indicates the links to external websites, internal document links to sections.

1.6 Abbreviations

The following table lists the abbreviations used in this document.

Table 2: Abbreviations

Conventions	Description
AIX	Advanced Interactive executive
DEFQ	Data Entry Forms and Queries
DML	Data Manipulation Language
EAR	Enterprise Archive
EJB	Enterprise JavaBean
ERM	Enterprise Resource Management
FTP	File Transfer Protocol
GUI	Graphical User Interface
HTTPS	Hypertext Transfer Protocol Secure
J2C	J2EE Connector
J2EE	Java 2 Enterprise Edition
JDBC	Java Database Connectivity
JDK	Java Development Kit
JNDI	Java Naming and Directory Interface
JRE	Java Runtime Environment
JVM	Java Virtual Machine
LDAP	Lightweight Directory Access Protocol
LHS	Left Hand Side
MFA	Multi-Factor Authentication
MOS	My Oracle Support
OFS	Oracle Financial Services
OFSAAI	Oracle Financial Services Analytical Application Infrastructure
OFSDF	Oracle Financial Services Data Foundation
OHC	Oracle Help Center
OLAP	On-Line Analytical Processing
OS	Operating System
RAM	Random Access Memory
RDMS	Relational Database Management System
SFTP	Secure File Transfer Protocol

Conventions	Description
SID	System Identifier
SSL	Secure Sockets Layer
TDE	Transparent Data Encryption
TNS	Transparent Network Substrate
URL	Uniform Resource Locator
VM	Virtual Machine
Web Archive	WAR
XML	Extensible Markup Language

2 OFS Data Foundation Application Pack Maintenance Release v8.0.9.2.0

This Maintenance Release of the OFS Data Foundation Application Pack includes all enhancements and bug fixes that are done since the OFSDF Application Pack v8.0.9.0.0 release.

Topics:

- [Pre-installation Requirements](#)
- [How to Apply this Maintenance Release?](#)

NOTE

The schemas/domains for OFSDF are referred to as BFND.

2.1 Pre-installation Requirements

These are the pre-installation requirements for the OFSDF Application Pack v8.0.9.2.0 release:

NOTE

Before installing OFSDF Application Pack v8.0.9.2.0, if Data Management Release v8.0.5.0.0 Application Pack (full installer) is already installed on the system, then execute the following statements in the Atomic schema:

- DROP INDEX DIM_DATES_CALENDAR_DATE;
 - DROP INDEX DIM_KI_GROUP_LRI;
- The OFSDF Application Pack Release v8.0.9.2.0 is compatible with the WebLogic v12.2.x and does not support the WebLogic v12.1.3. If the WebLogic version is 12.1.3, upgrade to the WebLogic 12.2.x version.
 - Oracle Financial Services Analytical Applications Infrastructure (OFSAAI) v8.0.9.1.0 (patch **30893508**) plus other prerequisite OFSAAI patches (see the *Pre-Installation Requirements* section of the [OFSAAI Installation Guide Release 8.0.9.1.0](#)) must be installed and configured on your machine ([OHC Documentation Library](#)).
 - Oracle Financial Services Data Foundation (OFSDF) Application Pack version 8.0.9.0.0 (patch **30692880**). See the OFSDF 8.0.9.0.0 ReadMe for instructions to install this patch. See the *Installer and Installation Prerequisites* section of the [OFSDF Application Pack Installation and Configuration Guide Release 8.0.9.0.0](#) for the installation prerequisites.

NOTE

The erwin files for OFSDF Application Pack v8.0.9.2.0 is available at [My Oracle Support](#) in the patch **31372462**.

- Oracle Database Release 19c Server and Client configuration:

- For information about configuring the Oracle Database Release 19c Server and Client for existing installations of OFSAA running Oracle Database Release 12c Server and Client, see the MOS Doc ID: [2699715.1](#).
- Enable the unlimited cryptographic policy. By default, JCE Policy JAR files are available for the Java versions mentioned in the following link and for later versions:

https://bugs.java.com/view_bug.do?bug_id=JDK-8170157

For the Java versions, where unlimited cryptographic policy is disabled by default, follow these steps:

- a. Download the JCE Policy related jar files `local_policy.jar` and `US_export_policy.jar`.
 - For Oracle Java, download the `local_policy.jar` and `US_export_policy.jar` files from <http://www.oracle.com/technetwork/java/javase/downloads/jce-7-download-432124.html>.
 - For IBM Java, download the `local_policy.jar` and `US_export_policy.jar` files from <https://www14.software.ibm.com/webapp/iwm/web/preLogin.do?source=icesdk>.
- b. Copy (or replace) the downloaded JCE Policy related jar files `local_policy.jar` and `US_export_policy.jar` to the `/jre/lib/security` directory of the Java installation directory used for OFSAAI and the Web Application Servers.

NOTE For information about the Hardware and Software Requirements, see the [Oracle Financial Services Analytical Applications 8.0.9.0.0 Technology Matrix](#).

2.2 How to Apply this Maintenance Release?

This section provides information about how to apply this Maintenance Release.

NOTE This Maintenance Release patch is applicable only for the RDBMS installation.

2.2.1 Downloading OFS Data Foundation Application Pack

To download and extract the release content, follow these steps:

NOTE Enable the unlimited cryptographic policy. By default, JCE Policy JAR files are available for Java.

1. Log in to [My Oracle Support](#). In the **Patches & Updates** tab, search for patch ID **31336111**.
2. Download the OFSDF Application Pack v8.0.9.2.0 archive file and copy it to your OFSAA server in the Binary mode.

NOTE

The archive files are different for different operating systems such as AIX, Solaris, and RHEL/Oracle Linux.

3. Shut down all the OFSAAI Services. For more information, see the *Start/Stop Infrastructure Services* section in the [OFSAAI Application Pack Installation and Configuration Guide 8.0.7.0.0](#).
4. Log in to [My Oracle Support](#), search for the **33663417** Mandatory Patch in the **Patches & Updates** Tab and download it.

ATTENTION

On the 10th of December 2021, Oracle released Security Alert CVE-2021-44228 in response to the disclosure of a new vulnerability affecting Apache Log4J prior to version 2.15. The application of the **33663417** Mandatory Patch fixes the issue.

For details, see the My Oracle Support Doc ID [2827801.1](#).

Ensure that you reapply the OFSAAI Mandatory Patch **33663417** whenever you Install or Upgrade the Application, or whenever you apply an Incremental Patch.

5. Log in to the OFSAA Server as a non-root user.
6. Execute the following command:

```
chmod -R 750 $FIC_HOME
```
7. Assign the WRITE permission to the files and folders such as `commonscripts`, `EXEWebService`, `ficapp`, `ficweb`, and `ficdb` by using the command:

```
chmod -R 775 *
```
8. If you have an Unzip utility, skip to the next step. Download the Unzip utility (OS-specific) `unzip_<os>.Z` and copy it in the Binary mode to the directory that is included in the `PATH` variable, in the `$HOME` path or directory in which you have copied the OFSDF Application Pack v8.0.9.2.0 installer.
 - a. Extract the unzip installer file using the following command:

```
uncompress unzip_<os>.Z
```

NOTE

If you notice an error message “uncompress: not found [No such file or directory]” when the package is not installed, contact your UNIX administrator.

- b. Give EXECUTE permission to the file using the following command:

```
chmod 751 OFS_BFND_8.0.9.2.0_<OperatingSystem>.zip
```

9. Extract the contents of the OFSDF v8.0.9.2.0 archive file using the following command:

```
unzip_<os> -a <name_of_the_file_to_be_unzipped>
```

NOTE

- Rename or remove the existing OFSAA Application Pack folder from the OFSAA server prior to extracting the contents from the release archive (.zip).

For example: When this release is extracted from the archive, it creates a folder named `OFS_BFND_PACK`. Rename or remove any existing folder with the same name, which exists in the path where the release archive is copied.

- The `-a` option in this step is mandatory to unzip the archive file.

For example:

```
unzip_aix -a
OFS_BFND_8.0.9.2.0_<OperatingSystem>.zip
```

2.2.2 Pre-installation Activities

This section provides pre-installation activities required for the installation of the OFSDF Application Pack v8.0.9.2.0.

2.2.2.1 Model Upload Parameter

You must upload the configuration file `params.conf` before triggering the installation. The `params.conf` file is present in the `/OFS_BFND_PACK/OFS_BFND/conf/` directory.

The following are the input parameters for the `params.conf` file:

- **Model Upload Process**
 - The required input value is 0 or 1.
 - **0** indicates to skip the model upload process.
 - **1** indicates to trigger the model upload process.
 - If the value is **1**, then select the type of the model for the Model Upload process:
 - **0** indicates the Released Data Model.
 - **1** indicates the Customized Data Model.

If the value is **1**, then provide the inputs for the Data Model Name and the Path of the Data Model.

2.2.3 Installing the OFS Data Foundation Application Pack

To install the OFSDF application pack, follow these steps:

1. Assign the EXECUTE permission to the Maintenance release archive file. Navigate to the `./OFS_BFND_PACK` directory and execute the following command:


```
chmod 750 OFSAAIUpdate.sh
```
2. Execute the `OFSAAIUpdate.sh` file using the following command:


```
./OFSAAIUpdate.sh
```
3. If OFSAA is deployed on the Oracle WebLogic Server version 12.2.x, install the one-off patch **25343603**. See the ReadMe available with the patch for further instructions on installing the patch.

NOTE If this one-off patch is already applied as a part of the v8.0.9.0.0 Release, this step is not required.

See the [Oracle Financial Services Analytical Applications 8.0.9.0.0 Technology Matrix](#) for a list of supported servers for OFSAA v8.0.9.0.0.

Verify if the release is applied successfully by checking the log file generated in the installation folder. The log files are stored in the `/OFS_BFND_PACK/logs/` and `/OFS_BFND_PACK/OFS_BFND/logs/` directories. You can ignore the ORA-00001, ORA-00955, ORA-02260, ORA-01031, and ORA-01430 errors in the log file. For any other errors, contact [My Oracle Support](#).

2.2.4 Post-installation Activities

The following sections provides information about the post-installation procedures for the OFSDF Application Pack v8.0.9.2.0 release.

2.2.4.1 Platform-related Post-installation Activities

After the OFSDF Application Pack is successfully installed, to perform the OFSAAI-related post-installation activities, follow these steps:

1. Clear the application cache.
2. Navigate to the following directory depending on the configured web application server and delete the following files:

- **Tomcat:**

```
<Tomcat installation folder>/work/Catalina/localhost/<Application name>/org/apache/jsp
```

- **WebLogic:**

```
<Weblogic installation location>/domains/<Domain name>/servers/<Server name>/tmp/_WL_user/<Application name>/<auto generated folder>/jsp_servlet
```

- **Websphere:**

```
<Websphere installation directory>/AppServer/profiles/<Profile
name>/temp/<Node name>/server1/<Application name>/<.war file name>
```

3. Add `umask 0027` in the `.profile` file of the UNIX account, which manages the webserver to ensure restricted access permissions.
4. Perform any necessary additional configuration as mentioned in the *Additional Configurations* section in [Oracle Financial Services Data Foundation \(OFSDF\) Application Pack Installation and Configuration Guide Release 8.0.9.0.0](#).
5. Apply the OFSAAI Mandatory Patch **33663417**.

See the Readme that is packaged with the Patch for instructions about installing the Patch.

ATTENTION

On the 10th of December 2021, Oracle released Security Alert CVE-2021-44228 in response to the disclosure of a new vulnerability affecting Apache Log4J prior to version 2.15. The application of the **33663417** Mandatory Patch fixes the issue.

For details, see the My Oracle Support Doc ID [2827801.1](#).

Ensure that you reapply the OFSAAI Mandatory Patch **33663417** whenever you Install or Upgrade the Application, or whenever you apply an Incremental Patch.

6. Generate the application EAR/WAR file and redeploy the application on the configured web application server. For more information on generating and deploying the EAR/WAR file, see the *Post Installation Configuration* section in the [Oracle Financial Services Data Foundation \(OFSDF\) Application Pack Installation and Configuration Guide Release 8.0.9.0.0](#).
7. After the successful installation of the OFSDF Application Pack v8.0.9.2.0 Release, restart all the OFSAAI services. For more information, see the *Start/Stop Infrastructure Services* section in the [Oracle Financial Services Data Foundation \(OFSDF\) Application Pack Installation and Configuration Guide Release 8.0.9.0.0](#).

2.2.4.2 OFSDF Related Post-installation Activities

This section provides the post-installation procedures for the OFSDF Application Pack v8.0.9.2.0 release.

2.2.4.2.1 Change Batch ICC Ownership

All the seeded batches in the OFSDF Application Pack are automatically assigned to the SYSADMIN user during the installation process. To see batches in the **Batch Maintenance** menu, execute the following queries in the Config schema of the database.

Syntax:

```
begin
```

```
AAI_OBJECT_ADMIN.TRANSFER_BATCH_OWNERSHIP ('fromUser','toUser','infodom');
```

```
end;
```

```
OR  
begin  
AAI_OBJECT_ADMIN.TRANSFER_BATCH_OWNERSHIP ('fromuser','touser');  
end;
```

- `fromUser` indicates the user who currently owns the batch.
- `toUser` indicates the user to whom the ownership must be transferred.
- `infodom` is an optional parameter. If you specify this parameter, the ownership of the batches pertaining to that `infodom` is changed.

For example:

```
begin  
AAI_OBJECT_ADMIN.TRANSFER_BATCH_OWNERSHIP  
( 'SYSADMN', 'FSDFOP', 'OFSBFNDINFO' );  
end;
```

2.2.4.2.2 Configuration to Enable the Restatement Support

The Restatement Support feature enables the backdated Run execution for any Start Date/End Date explicitly on a specific list of metadata for the purpose of data refiling in the OFSDF Application Pack.

NOTE This section is applicable only for the RDBMS based installation.

To enable the Restatement Support feature in the OFSDF Application Pack, see the procedure in the *Configurations to Enable the Restatement Support* section in the [Oracle Financial Services Data Foundation \(OFSDF\) Application Pack Installation and Configuration Guide Release 8.0.9.0.0](#).

3 Appendix A

This chapter includes FAQs for the OFSDF Application Pack v8.0.9.2.0 release.

Topic:

- [Frequently Asked Questions](#)

3.1 Frequently Asked Questions

What checks does the v8.0.9.2.0 release patch perform?

This release patch performs the following checks:

- Environment Check: During the environment check, it performs Java validation, Environment Variables validation, OS-specific validation, DB specific validation, and shuts down all the OFSAAI Services (Infrastructure Server, ICC Server, and back-end services).
- Post-installation check: As a part of the Post-installation check, the patch checks if the OFSAAI services can be successfully started.

Which version of the erwin Data Modeler does OFSAAI support?

OFSAAI now supports the erwin Data Modeler version 9.8 generated XMLs.

What should I do for viewing the log files at the Debug level for troubleshooting?

By default, the log level is set as **INFO**. You must manually change the log level to **Debug** to view the log files in the debug level. Based on your requirements, you can also change the log level to Warn, Error, or Fatal. To view log files, follow these steps:

1. Navigate to the `$FIC_HOME/conf` directory in the APP layer of your OFSAAI installation.
 - Change the priority value to **Debug** in the `RevLog4jConfig.xml` file.

For example:

```
<root>
<priority value ="debug" />
<appender-ref ref="ConsoleAppender1"/>
</root>
```

- Replace the value of the `LOGGERLEVEL` parameter in the `DynamicServices.xml` file from 20 with 0 (20 is the value for Info and 0 for Debug).

NOTE

For multi-tier installation, also change the `LOGGERLEVEL` value to 0 (Debug) in the `DynamicServices.xml` and `RevLog4jConfig.xml` files, which are present in the `$FIC_APP_HOME/conf`, `$FIC_DB_HOME/conf`, and `$FIC_WEB_HOME/conf` directories.

2. Navigate to the `$FIC_WEB_HOME/webroot/conf` directory and change the **priority** value to **Debug** in the `ExportLog4jConfig.xml`, `MDBLogger.xml`, and `PR2Logger.xml` files to view

the log files at the Debug level for the modules Archive/Restore, Metadata Browser, and RRF respectively.

3. Generate the application EAR/WAR file and redeploy the application on the configured web application server. For more information on generating and deploying the EAR/WAR file, see the Post-installation Configuration section in the [OFSAAAI Application Pack Installation and Configuration Guide 8.0.7.0.0](#).
4. Restart the OFSAAI Services (APP and WEB). For more information, see the Start/Stop Infrastructure Services section in the [OFSAAAI Application Pack Installation and Configuration Guide 8.0.7.0.0](#).

OFSAA Support

Raise a Service Request (SR) in [My Oracle Support \(MOS\)](#) for queries related to the OFSAA applications.

Send Us Your Comments

Oracle welcomes your comments and suggestions on the quality and usefulness of this publication. Your input is an important part of the information used for revision.

- Did you find any errors?
- Is the information clearly presented?
- Do you need more information? If so, where?
- Are the examples correct? Do you need more examples?
- What features did you like most about this manual?

If you find any errors or have any other suggestions for improvement, indicate the title and part number of the documentation along with the chapter/section/page number (if available) and contact the Oracle Support.

Before sending us your comments, you might like to ensure that you have the latest version of the document wherein any of your concerns have already been addressed. You can access My Oracle Support site that has all the revised/recently released documents.

