

Oracle Financial Services AgileREPORTER Application

Installation Guide

Release 8.0.8.1.0

Jan 2020

ORACLE[®]
Financial Services

Copyright © 2020 Oracle and/or its affiliates. All rights reserved.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are “commercial computer software” pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

For information on third party licenses, click [here](#).

Document Control

Version Number	Revision Date	Change Description
02	January 06, 2020	Updated: Final version published
01	December 23, 2019	Created: Draft published

Executive Summary

The document consists of all the installation, Pre and Post configuration procedures which have been structured considering all the 8.0.8.1.0 features. You can find the latest copy of this document in the [OHC](#) Documentation Library which includes all the recent additions/revisions (if any) done to date.

Before you begin the installation, ensure that you have access to Oracle Support Portal with the required login credentials to quickly notify us for any specific issues. You can obtain one by contacting [Oracle Support Services](#).

Table of Contents

1	Preface	6
1.1	Summary	6
1.2	Audience	6
1.3	Prerequisites for the Audience	6
1.4	Documentation Accessibility	6
1.5	Access to Oracle Support	6
1.6	Conventions and Acronyms	7
2	About OFS AgileREPORTER and OFS AgileREPORTER Packs	8
2.1	About OFS AgileREPORTER	8
2.2	About OFS AgileREPORTER Platform Architecture	8
2.3	About OFS AgileREPORTER Modules	9
3	Preparing for Installation	10
3.1	Installer and Installation Prerequisites	10
3.1.1	<i>Supported Operating Systems</i>	10
3.1.2	<i>Required Software</i>	10
3.1.3	<i>Supported Databases</i>	11
3.1.4	<i>Other Requirements</i>	13
3.2	Obtaining the Software	13
3.3	Common Installation Activities	13
3.3.1	<i>Identifying the Installation Directory</i>	14
3.3.2	<i>Copying and Extracting the Software</i>	14
4	Installing OFS AgileREPORTER Applications Pack	15
4.1	Running the OFS AgileREPORTER Applications Pack Installer	15
4.1.1	<i>Running the Installer in GUI Mode</i>	15
4.1.2	<i>Running the Installer in GUI Mode for Upgrade</i>	29
4.1.3	<i>Running the Installer in SILENT Mode</i>	29
4.1.4	<i>Running the Installer in SILENT Mode for Upgrade</i>	33
4.1.5	<i>Verifying the Log File</i>	33
5	Trial Template Package Installation	34

5.1	Trial Template Package for US FED.....	34
5.2	Trial Template Package for RBI	34
5.3	Installing Trial Template Packages	34
6	Start/Stop AgileREPORTER Services.....	36
6.1	Start AgileREPORTER Web Server.....	36
6.2	Stop AgileREPORTER Web Server.....	36
7	Error Dictionary.....	37
7.1	Accessing Error Dictionary	37
7.2	Error Code Dictionary.....	37
7.2.1	<i>Error code - OFSAAI-1002</i>	<i>37</i>

1 Preface

This preface provides supporting information for the OFS AgileREPORTER Installation Guide and includes the following topics:

- [Summary](#)
- [Audience](#)
- [Prerequisites for the Audience](#)
- [Documentation Accessibility](#)
- [Related Documents](#)
- [Conventions and Acronyms](#)

1.1 Summary

You can find the latest copy of this document in the [OHC](#) library which includes all the recent additions/revisions (if any) done to date.

Before you begin the installation, ensure that you have access to the Oracle Support Portal with the required login credentials to quickly notify us of any issues at any stage. You can obtain the login credentials by contacting Oracle Support.

1.2 Audience

The OFS AgileREPORTER Pack Installation and Configuration Guide is intended for Administrators, Business User, Strategists, and Data Analyst, who are responsible for installing and maintaining the application pack components.

1.3 Prerequisites for the Audience

Following are the expected preparations before starting the actual installation:

The document assumes you have experience in installing Enterprise components. Basic knowledge about the Oracle Financial Services Advanced Analytical Applications Infrastructure Applications Pack components, OFSAA Architecture, UNIX commands, Database concepts, and Web Server/ Web Application Server is recommended.

1.4 Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

1.5 Access to Oracle Support

Oracle customers have access to electronic support through My Oracle Support. For information, visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> for the hearing impaired.

1.6 Conventions and Acronyms

The conventions and acronyms used in this guide are as follows.

Conventions	Description
AIX	Advanced Interactive executive
DEFQ	Data Entry Forms and Queries
DML	Data Manipulation Language
EAR	Enterprise Archive
EJB	Enterprise JavaBean
ERM	Enterprise Resource Management
FTP	File Transfer Protocol
GUI	Graphical User Interface
HTTPS	Hypertext Transfer Protocol Secure
J2C	J2EE Connector
J2EE	Java 2 Enterprise Edition
JDBC	Java Database Connectivity
JDK	Java Development Kit
JNDI	Java Naming and Directory Interface
JRE	Java Runtime Environment
JVM	Java Virtual Machine
RBI	Reserve Bank of India
US FED	US Federal Reserve

2 About OFS AgileREPORTER and OFS AgileREPORTER Packs

This chapter includes the following topics:

- [About OFS AgileREPORTER](#)
- [About OFS AgileREPORTER Platform Architecture](#)
- [About OFS AgileREPORTER Modules](#)

2.1 About OFS AgileREPORTER

OFS AgileREPORTER is a form and workflow tool that enables the creation and submission of regulatory returns. The OFS AgileREPORTER platform is configured with product configurations delivered using configuration packages. Different configuration packages are loaded into OFS AgileREPORTER to support different sets of regulatory returns, normally on jurisdictional lines.

For example, one configuration package may support US Broker / Dealer returns, whereas another configuration package may support European Common Reporting. When a regulation changes, only a new version of the related configuration package is required, there is usually no need to upgrade OFS AgileREPORTER.

A configuration package contains the following core artifacts:

- Return template
- Description of the submission files for the regulator
- XBRL taxonomies
- Validation rules and edit checks
- Bindings to the FSDF data model

If you are using an OFSAA - OFS AgileREPORTER integrated solution, two configuration packages are required. One is from VERMEG, containing artifacts 1-4 above; and one from Oracle, containing artifact 5.


[Chapter 3 – Preparing for Installation](#) until [Chapter 6 – Start/Stop AgileREPORTER Services](#) describes how to install, update, configure, start, and stop the OFS AgileREPORTER platform.

2.2 About OFS AgileREPORTER Platform Architecture

OFS AgileREPORTER has a web-based user interface. Users interact with OFS AgileREPORTER to view and edit their regulatory returns using a standard web browser. No browser plugins are required – its user interface is completely standard compliant (HTML, CSS, and JavaScript).

OFS AgileREPORTER platform contains an embedded Java EE server. All the business logic of OFS AgileREPORTER is executed within this server. The server itself is a single Java process running on the application server.

OFS AgileREPORTER requires a relational database. Oracle database is supported. For more details, see [Chapter 3 – Preparing for Installation](#).



The installation of OFS AgileREPORTER has a prerequisite described in [Chapter 3 - Preparing for Installation](#) to correctly configure the OFS AgileREPORTER database.

2.3 About OFS AgileREPORTER Modules

If licensed sufficiently, OFS AgileREPORTER can also work with optional modules:

- **REPORTER:** AgileREPORTER® Suite provides calculated return data and form (template) metadata for OFS AgileREPORTER. If the REPORTER module is installed for OFS AgileREPORTER, the REPORTER form (template) metadata is used instead of OFS AgileREPORTER return metadata.
- **OFSAA:** The OFSAA Module for OFS AgileREPORTER provides integration with Oracle Financial Services Application Architecture. Oracle's OFSAA provides calculated return data which is read directly from OFSAA's results area and applied to form (template) metadata in OFS AgileREPORTER.

3 Preparing for Installation

This chapter provides the necessary information to review before installing the OFS AgileREPORTER Applications Pack v8.0.8.1.0. This chapter includes the following topics:

- [Installer and Installation Prerequisites](#)
- [Obtaining the Software](#)
- [Common Installation Activities](#)

3.1 Installer and Installation Prerequisites

This section describes the installation prerequisites for OFS AgileREPORTER Pack.

3.1.1 Supported Operating Systems

OFS AgileREPORTER is supported on the following operating system:

- Linux
 - Red Hat Enterprise Linux 7.x
 - Oracle Enterprise Linux 7.x

3.1.2 Required Software

The required software for this release are as follows:

- Java Runtime Environment (JRE) (version 8 update 91 or later updates of version 8, Oracle HotSpot™). The `JAVA_HOME` environment variable should point at the JRE installation folder, and `java` (in Unix) or `java.exe` (in Windows) should be placed in the system path.

NOTE Use the Oracle JRE distribution. Open JDK is not supported.

How Java is used?

If the application server that OFS AgileREPORTER is installed on has multiple version of Java installed, OFS AgileREPORTER attempts to use Java in the following order, moving to the next location if Java cannot be found:

- a. `JAVA_HOME` properties defined in the `ocelot.properties` file. This is a local version of the `JAVA_HOME` properties and does not impact other applications using this variable.
- b. `JAVA_HOME` defined at the system level (if not defined/overridden in the `ocelot.properties` file). This variable can be shared by other applications, so be careful if you want to modify it.
- c. The Java executable in the system path. This is the version of Java that is used when `java` is entered at the command line.

Ensure that the `JAVA_HOME` property points to a valid Java folder. For example, if the Java executable is in `/opt/java/Jre17/bin/java`, then set `JAVA_HOME=/opt/java/Jre17`.

Java Use Case Examples

- **Use the system-level** `JAVA_HOME`
 Ensure that the System level `JAVA_HOME` is valid and that `JAVA_HOME` is not defined in the `ocelot.properties` file.
- **Use a different version of Java than the one defined by the system-level** `JAVA_HOME`
 Define `JAVA_HOME` in the `ocelot.properties` file.
- **Unsure about** `JAVA_HOME` **and it is not defined on the installation computer**
 Check if `JAVA_HOME` is defined in your system by entering the following at the command line:

Linux:

```
echo $JAVA_HOME
```

If `JAVA_HOME` is not defined in your system, then check if `java -version` can be run at the command line. If so, OFS AgileREPORTER uses the same version.

- Oracle Financial Services Data Foundation (OFSDF) 8.0.8.1.0 (patch **30124064**) or above, mandatory one-off patch **30281084**, plus other prerequisite OFSDF patches (see **Section 3.1 Installer and Installation Prerequisites** of Oracle Financial Services Data Foundation Installation Guide, version 8.0.8.1.0, [OHC](#) Documentation Library) should be installed and configured in your Machine.

3.1.3 Supported Databases

OFS AgileREPORTER supports Oracle Database 11g Release 2 and 12c Release 1.

This guide mentions SQL Server throughout. Please do not use these SQL Server options and settings. Full SQL Server support will be finalized in a later version.

3.1.3.1 Oracle-specific Settings

OFS AgileREPORTER requires a schema for installation and runtime. The same schema can be used for both. If desired, for security reasons you can use two different schemas:

- An owner schema that has DDL privileges. This schema is only used at installation and during Configuration Manager operations, and can otherwise be locked.
- An app schema that only has DML privileges. This schema is used at runtime.

The owner schema requires the following privileges (granted by someone with system database administrator privileges):

You require SYSDBA privileges to run the last four grants.

- `grant create session to <owner>;`
- `grant create trigger to <owner>;`
- `grant create table to <owner>;`
- `grant create sequence to <owner>;`
- `grant create view to <owner>;`
- `grant select on pending_trans$ to <owner>;`
- `grant select on dba_2pc_pending to <owner>;`

- `grant select on dba_pending_transactions to <owner>;`
- `grant execute on dbms_xa to <owner>;`

The app schema and all accessible schemas that appear in the required alias of installed configurations are granted the following privileges (granted by someone with system database administrator privileges):

You need SYSDBA privileges to run the last four grants.

- `grant create session to <app>;`
- `grant select on pending_trans$ to <app>;`
- `grant select on dba_2pc_pending to <app>;`
- `grant select on dba_pending_transactions to <app>;`
- `grant execute on dbms_xa to <app>;`

Schema/Login examples

Following are examples of DDL (owner) and DML (app) schemas/logins for OFS AgileREPORTER in Oracle and SQL Server, with user-definable items shown in **bold**:

- **Oracle**

Schema Owner

- `CREATE USER RP$OWNER IDENTIFIED BY password`
- `DEFAULT TABLESPACE users`
- `TEMPORARY TABLESPACE temp`
- `QUOTA UNLIMITED ON users;`
- `grant create session to RP$OWNER;`
- `grant create trigger to RP$OWNER;`
- `grant create table to RP$OWNER;`
- `grant create sequence to RP$OWNER;`
- `grant create view to RP$OWNER;`
- `grant select on pending_trans$ to RP$OWNER;`
- `grant select on dba_2pc_pending to RP$OWNER;`
- `grant select on dba_pending_transactions to RP$OWNER;`
- `grant execute on dbms_xa to RP$OWNER;`

Application User

- `CREATE USER RP$APP IDENTIFIED BY password`
- `DEFAULT TABLESPACE users`
- `TEMPORARY TABLESPACE temp`
- `QUOTA UNLIMITED ON users;`
- `grant create session to RP$APP;`
- `grant select on pending_trans$ to RP$APP;`
- `grant select on dba_2pc_pending to RP$APP;`

- grant select on dba_pending_transactions to **RP\$APP**;
 - grant execute on dbms_xa to **RP\$APP**;
- create and grant object privilege role to application user to let application user access the table of the schema owner
- CREATE ROLE **RP\$RW_ROLE**;
 - CREATE ROLE **RP\$R_ROLE**;
 - grant **RP\$RW_ROLE** to **RP\$APP**;

3.1.4 Other Requirements

The other requirements for this release are:

- Shut down any OFS AgileREPORTER Web Server currently running on the target server.
- Ensure that there is a free service port for OFS AgileREPORTER web server (default 8080) and a free service port for ActiveMQ (default 61616). If either default port is already being used by another application, find an alternative free port.
- To use Oracle functionality that fulfills General Data Protection Regulation (GDPR) requirements, set the db.redacted property equal to True in the aliasinfo.properties file.
- For example:

```
config.sh -ea OFSAA_DW_DT -iv 1.11.0.1 -alias "OFSAA DS" -aif  
aliasinfo.properties
```

From version 1.15.5, a new property is added related to encrypted passwords. If encrypted passwords are used in the properties file, the `password.encrypted` property in the alias properties file must be uncommented and its value set to True.

3.2 Obtaining the Software

This release of OFS AgileREPORTER Applications Pack 8.0.8.1.0 can be downloaded from the Oracle Support site (<https://support.oracle.com/>). Log in and search for **30672152** under the Patches and Updates tab to download.

3.3 Common Installation Activities

The following are the common pre-installation activities that you must carry out before installing the OFS AgileREPORTER application.

This section includes the following topics:

- [Identifying the Installation, Download and Metadata Repository Directories](#)
- [Configuration for GUI Mode Installation](#)
- [Downloading and Copying the OFS AgileREPORTER Application Installer](#)
- [Copying and Extracting the Software](#)
- [Setting up the Web Server/ Web Application Server](#)

3.3.1 Identifying the Installation Directory

For the installation of any OFS AgileREPORTER Applications, the following folders/ directories required to be created.

- **OFS AgileREPORTER Download Directory** (Optional): Create a download directory and copy the OFS AgileREPORTER Application Installer File (Archive). This is the directory where the downloaded installer/ patches can be copied.

NOTE Ensure the user permission is set to 755 on the Installation and Download Directory.

3.3.2 Copying and Extracting the Software

Once you obtain the installer, copy the installer (in BINARY mode) to the system on which the OFS AgileREPORTER Applications components are installed.

NOTE You must be logged in to the UNIX operating system as a non-root user.

1. Download the unzip utility (OS-specific) `unzip_<os>.Z`, and copy it in Binary mode to any directory and include the directory in your PATH variable. If you already have the unzip utility to extract the contents of the downloaded archive, skip to the next step.
2. Uncompress the unzip installer file using the command:

```
uncompress unzip_<os>.Z
```

NOTE If you notice an error message "uncompress: not found [No such file or directory]" when the package is not installed, contact your UNIX administrator.

3. Give EXECUTE permission to the file using the command:

```
chmod 751 unzip_<os>
```

For example, `chmod 751 unzip_sparc`

4. Extract the contents of the OFS AgileREPORTER Application 8.0.8.1.0 to the downloaded directory using the following command:

```
unzip OFS_AGILE_REPORTER_8.0.8.1.0_LINUX.zip
```

NOTE DO NOT rename the Application Pack installer folder name on extraction from the archive.

5. Give the following permission to the installer folder. Navigate to the downloaded directory and execute the command:

```
chmod -R 755 OFS_AGILE_REPORTER
```

4 Installing OFS AgileREPORTER Applications Pack

Follow the instructions in this chapter to install the OFS AgileREPORTER Applications Pack depending on the mode of installation.

This chapter includes the following topics:

- [Running the OFS AgileREPORTER Applications Pack Installer](#)
- [Verifying the Installation](#)

4.1 Running the OFS AgileREPORTER Applications Pack Installer

OFS AgileREPORTER Applications Pack installation supports two modes of installation:

- [Running the Installer in GUI Mode](#)
- [Running the Installer in SILENT Mode](#)

4.1.1 Running the Installer in GUI Mode

Before proceeding, ensure that all pre-installation requirements listed in [Chapter 2 - Preparing for Installation](#) are met.

NOTE The following screenshots are taken from a Windows system but will look similar in Linux configuration for GUI Mode Installation.

To install this product in GUI mode, you need to ensure the following software and configurations are available:

- Install and configure any PC X Server software such as Open Text Exceed (formerly Hummingbird Exceed) on the user desktop system from which the installation is triggered.
- Configure the DISPLAY variable.

Ensure to set the DISPLAY variable (in user .profile) on the system on which the OFSAA Infrastructure is installed, to point to the user desktop system where the PC X Server software is installed.

Syntax:

```
export DISPLAY = hostname:n
```

where, the **hostname** is the IP Address/ Hostname of the user desktop system and n is the sequence number (usually 0).

For example: 10.XXX.XXX.XXX:0000 or myhostname:0


To install OFS AgileREPORTER using the installer GUI, follow these steps (click **Next** to advance after each step):

1. Navigate to the path where the OFS AgileREPORTER installer kit is unzipped.
2. Navigate to OFS_AGILE_REPORTER/AgileREPORTER/bin directory.
3. Execute ./Setup.sh GUI command in the console.



The initial splash screen is displayed. Select **Next** to continue the installation.

4. Select the location where OFS AgileREPORTER must be installed.



5. The installer checks for the OFSAA database when the database details are entered.

Check OFSAA

OFSAA Database type

- Oracle (SID / Service name)
- Oracle (TNS connect string)

Database server host or address

Database server port

Connect by


- SID
- Service name

SID / Service name

OFSAA username

OFSAA password

NOTE If Oracle FSDF is not available, the following message is displayed.



If Oracle FSDF is available, the following screens continue as part of the installation.

6. Select the JBOSS options as applicable.

Use WildFly provided in the installer?

Yes

No

Select Yes, if you don't have a JBOSS EAP installation.
Select No, if you have a preferred JBOSS EAP installation.
(Your JBOSS EAP installation must be clear and only serve this AgileREPORTER installation.)

Previous Next Quit

7. Select the installation mode as applicable.

Install mode

AgileREPORTER Installation Mode

Default(Recommend)

Customized

Previous Next Quit

8. Select the network settings as applicable.

Network Settings

HTTP Port:

Enable HTTPS?

Yes

No

HTTPS Port:

Messaging (ActiveMQ) Settings

Port:

Host:


9. Provide the MQ authentication details.

ActiveMQ authentication

Username:

Password:

10. Select **Enable return workflow** to enable approval workflow for changes made to returns and set how many approvers are required per change.



Enable / Disable return workflow

Enable return workflow

Approver count

Before checking the Enable Workflow box, please refer to the Installation Guide.

[← Previous](#) [Next →](#) [Quit](#)

NOTE The following screenshots are taken from a Windows system but will look similar in Linux configuration for GUI Mode Installation.

If your installation of OFS AgileREPORTER is connected to the REPORTER module, then OFS AgileREPORTER uses approval workflow settings from there instead of showing you this step. You may require a new license to enable the approval workflow feature, contact VERMEG.

11. Select how AgileREPORTER users must be authenticated when logging in.

User Authentication

AgileREPORTER User Access type

AgileREPORTER

Single Sign On

LDAP Only

Mixed - LDAP and AgileREPORTER

LDAP is used for user login. Users are managed in AgileREPORTER database but passwords are not needed to be present in AgileREPORTER.

[← Previous](#) [Next →](#) [Quit](#)

NOTE

- **Single Sign On:** Users are managed in the AgileREPORTER database but passwords can be optional in AgileREPORTER. An SSO server is used to provide user authentication.
- **LDAP Only:** Users are managed in the AgileREPORTER database but passwords can be optional in AgileREPORTER. An LDAP server is used to provide user authentication.

12. If you select **Single Sign-On**, then enter values for **Identity Provider URL** and **Service Provider URL**.

Enable Single Sign-On

Identity Provider URL

Service Provider URL

1. Identity Provider URL is the IdP url where the SAML request needs to be posted to.
You can ask your administrator for this url.
2. Service Provider URL should set AgileREPORTER web home url.

[← Previous](#) [Next →](#) [✖ Quit](#)

Identity Provider URL: Where OFS AgileREPORTER sends SSO requests, for example to an identity provider set up within your infrastructure.

Service Provider URL: Must be [http\(s\)://<hostname>:<port>/agilereporter/](http(s)://<hostname>:<port>/agilereporter/) (the OFS AgileREPORTER URL).

NOTE

OFS AgileREPORTER supports Single Sign-On by using the SAML v2 protocol. If you have the SAML v2 compatible Identity Provider in your IT infrastructure already, the Identity Provider can be used to authenticate users of OFS AgileREPORTER. One possible usage of this functionality is that OFS AgileREPORTER, OBIEE, and OFSAA web share single sign-on using SAML v2 implemented by Oracle Identity Federation. This requires that OFS AgileREPORTER as a SAML service provider (SP) is configured with the details of Oracle Identity Federation as a SAML v2 identity provider (IdP). The OFSAA results area database credentials are added post-installation using OFS AgileREPORTER's Configuration Manager. For accurate SSO usage in OFS AgileREPORTER, ensure the following:

- The times on the identity provider server and the OFS AgileREPORTER server are synchronized.
- The identity provider uses a plain text username in the SAML assertion sent to OFS AgileREPORTER when attempting a user login.
- The same username exists in OFS AgileREPORTER.
- The identity provider includes the role LRM_RP_USER in the SAML assertion sent to OFS AgileREPORTER when attempting a user login.




13. Enter the database connection information and credentials for the OFS AgileREPORTER schemas with DDL (at installation) or DML (at application runtime).

NOTE Credentials must match those defined in the schemas referenced in the [Supported Databases](#) section of Chapter 2. Select **Oracle (SID / Service name)**. Full SQL Server support will be supplied in a later version.

AgileREPORTER Database Configuration

AgileREPORTER Database type

- Oracle (SID / Service name)
- Oracle (TNS connect string)
- SQL Server (SQL Server authentication)
- SQL Server (Windows / Domain authentication)

Oracle (SID / Service name):

AgileREPORTER Database Configuration

Database server host or address

Database server port

Connect by

- SID
- Service name

SID / Service name




AgileREPORTER owner username

AgileREPORTER owner password


AgileREPORTER application username

AgileREPORTER application password

AgileREPORTER database rolename

Oracle (TNS connect string):



AgileREPORTER Database Configuration

Oracle TNS connect string

AgileREPORTER owner username

AgileREPORTER owner password

AgileREPORTER application username

AgileREPORTER application password

Does this installation require Microsoft SQL Server database support for your data source?

NOTE For domain single sign-on, enter **OFS AgileREPORTER system domain**, but leave the **Domain username** and **Domain password** blank.
For domain authentication, enter **OFS AgileREPORTER system domain**, **Domain username**, and **Domain password**.

14. Set up the initial AgileREPORTER administration user account.

NOTE This step only appears during a fresh installation of OFS AgileREPORTER.

Create AgileREPORTER administration user

Username: SYS

Password: [masked]

Confirm password: [masked]

Previous Next Quit

If Single Sign-On is enabled, the **Username** must be a valid user in the Identity Provider and the password can be left blank. This user is created as an administrative user in OFS AgileREPORTER.

15. Select **Yes** for **Always validate database connection** to check if there is a firewall between the application server and database server.

Enable Check Database Valid Connection

Tick on the radio box yes selected below, if there is a firewall between the application server and the database server.

If the radio box yes is selected the installer will add connection validation for all datasources.

Always validate database connection.

Yes

No

Previous Next Quit

16. Enter the Java minimum and maximum heap size.


The screenshot shows a dialog box titled "AgileREPORTER Java Settings". It contains two input fields: "Initial heap size (MB)" with the value "2048" and "Maximum heap size (MB)" with the value "4096". At the bottom right, there are three buttons: "Previous" (with a left arrow), "Next" (with a right arrow), and "Quit" (with a red X icon).

17. Select the shortcut settings if required.

The screenshot shows a dialog box for selecting shortcut settings. It has two checked checkboxes: "Create shortcuts in the XDG-Menu" and "Create additional shortcuts on the desktop". Below these is the text "Select a Program Group for the Shortcuts:". Underneath, it says "create shortcut for:" followed by two radio button options: "current user" (which is selected) and "all users". A text input field contains "Lombard Risk\AgileREPORTER" and a "Default" button is to its right. At the bottom right, there are three buttons: "Previous" (with a left arrow), "Next" (with a right arrow), and "Quit" (with a red X icon).

18. Select **Create UNIX service** to create a UNIX service on the server where OFS AgileREPORTER is running.

Enter the **starter user account name**, which is the Linux operating system account that starts the service.



Unix Settings


Create Unix service

Unix service suffix name 19.4.1-b156

Unix service starter user account name jboss

Previous Next Quit

19. Wait for unpacking and installation to complete.



⚙ Pack installation progress:
/scratch/ofsaar/AR/tools/ocelot-builder/ocelot-builder-jar-with-dependencies.jar
AgileREPORTER Ant


⚙ Overall installation progress:
1 / 7

Previous Next Quit

20. Select **Start AgileREPORTER now** (to open immediately) and click **Next**.



21. Click **Done** to finish the installation process.



NOTE

If required, the DDL schema/login can be locked after successfully installing the OFS AgileREPORTER.

You can now try opening OFS AgileREPORTER in a web browser. For example, open Internet Explorer and enter `http(s)://<server>:<port>` or `http(s)://<server>:<port>/agilereporter`, specifying the chosen http protocol, server address and port.

4.1.2 Running the Installer in GUI Mode for Upgrade

To upgrade OFS AgileREPORTER using the installer in GUI mode, follow these steps (click **Next** to advance after each step):

1. Repeat the section "[4.1.1 Running the Installer in GUI Mode](#)" till you specify the installation path.
2. Specify the installation path and click **Next**.
3. The subsequent GUI screens get auto-populated with the existing information and you must click **Next** to continue and complete the installation.

NOTE After upgrading from one version of AgileREPORTER to another, any manual changes made to the AgileREPORTER configuration in the previous version must be reapplied to the configuration in the upgraded installation. For example, changes made to the `standalone.xml` file in the previous version will be overwritten when upgrading.

4.1.3 Running the Installer in SILENT Mode

NOTE Before proceeding, ensure that all pre-installation requirements listed in [Chapter 3 - Preparing for Installation](#) are met. You must fill the `Silent.props` file from `OFS_AGILE_REPORTER/AgileREPORTER/conf` directory before starting the installation.

The following table describes the installation properties that should be filled in the `Silent.props` Java Properties file. This file uses a standardized format consisting of a key followed by an equals sign '=', followed by a value on each line.

The following characters must be appended with a backslash '\' for the Escaped version when used in keys and values:

Character Name	Character Symbol	Escaped Version
Equals	=	\=
Colon	:	\:
Backslash	\	\\

For example:

`\:\=\\bin\\temp` when un-escaped translates to `:=\bin\temp`.

For more information, see <http://docs.oracle.com/javase/6/docs/api/java/util/Properties.html#load> (`java.io.Reader`) or contact VERMEG support.

The configurable properties with a grey background are not shown in the OFS AgileREPORTER installer user interface. Do not alter these unless instructed to do so by VERMEG support.

NOTE

If the password is encrypted in the properties file, the `ocelot.secret.key` property must be added to the `Silent.props` file to specify the secret key used to encrypt the password.

For upgrading an existing AR, use the existing `ocelot.properties` file and the upgrading will automatically generate a secret key for you.

For new AR, use the `ocelot-encoding` tool to generate a secret key, then use this secret key to encrypt all passwords in `Silent.props` file before you can use it to install AR.

To encrypt the password using an existing secret key, see “AppendixA-EncodingTool” in [AgileREPORTER 19.4 - Installation and Administration Guide.pdf](#).

All passwords mentioned in the `Silent.props` properties file should be encrypted. Execute the following command to encrypt all passwords using the utility `ocelot-encoding-1.2809.8.jar` under the `/utility` folder:

To generate a secret key:

```
java -jar encoding-tool.jar -gk
```

To encrypt with an existing secret key:

```
java -jar encoding-tool.jar -en <PASSWORD> -k <SECRET KEY>
```

To encrypt with random secret key:

```
java -jar ocelot-encoding-1.2809.8.jar -en "password"
```

Property Name	Description of Property	Permissible values	Comments
<code>ocelot.install.path</code>	AgileREPORTER Home Directory Install Path	Not applicable	For example: /scratch/ofsaapp/reporter_portal
<code>singleLoginModel</code>	Single Login Model	True False	Default value is False. NOTE: Enter True if you want to restrict one user per session.
<code>main.host.name</code>	Current machine’s IP address or hostname	Not applicable	For example: 10.XXX.XXX.XXX
<code>activemq.port</code>	AgileREPORTER jBoss AMQ Port	Not applicable	For example: 61616.
<code>agile.reporter.web.app</code>	AgileREPORTER Web Application	True False	Default value is True.
<code>host.port</code>	AgileREPORTER Web Host Port	Not applicable	For example: 8090.

Property Name	Description of Property	Permissible values	Comments
httpsMode	HTTPS/SSL Required or Not	True False	Default value is False. The value should be True only if HTTP is false. (Optional. Required only when HTTPS is used).
host.port.https	HTTPS Port	Not applicable	(Optional. Required only when HTTPS is used). Default value: host.port.https = 0000
did.retrieve.job	DID Retrieve Job activation	True False	Default value is True.
data.schedule.export.job	Data Schedule Export Job activation	True False	Default value is True.
other.brokers	Other ActiveMQ Broker activation	True False	Default value is False.
other.brokers.hosts	Other ActiveMQ Broker Host Name and Port	Not applicable	For example: 10.XXX.XXX.XXX:0000
ocelot.database.type	Ocelot Database Type	Oracle	Default value is Oracle.
ocelot.jdbc.url	Ocelot JDBC URL	For SID: jdbc:oracle:thin:@ IPADDRESS:PORT :SID For Service Name: jdbc:oracle:thin:@// IPADDRESS:PORT /SERVICE_NAME	For example: jdbc:oracle:thin:@10.XXX.XXX.X XX:0000:AGILERP jdbc:oracle:thin:@//10.XXX.XXX. XXX:0000/SERVICE_NAME
ocelot.jdbc.username	RP OWNER Schema User Name	Not applicable	For example: AGILE_RPOWNER
ocelot.jdbc.password	RP OWNER Schema Password	Not applicable	For example: 5dfc52b51bd355539bd9a0b76da 9b8e7
ocelot.database.role name	RP Read/Write Role Name	Not applicable	For example: AGILE_RPRW_ROLE
ocelot.app.jdbc.user name	RP Application Schema User Name	Not applicable	For example: AGILE_RPAPP
ocelot.app.jdbc.password	RP Application Schema Password	Not applicable	For example: 5dfc52b51bd355539bd9a0b76da 9b8e7
check.db.valid.connection.enabled	Database Connection Validation activation	True False	Default value: False
ocelot.user.name	AgileREPORTER User Interface Login User Name	Not applicable	For example: RP Admin
ocelot.user.password	AgileREPORTER User Interface Login Password	Not applicable	For example: 5dfc52b51bd355539bd9a0b76da 9b8e7
ocelot.user.authentication.mode	Agile Reporter User Interface Login Mode	SYSTEM, SSO, LDAP	Default Value: SYSTEM

Property Name	Description of Property	Permissible values	Comments
sso.idp.url sso.service.provider.url	Agile Reporter UI using SSO Credentials	Not applicable	Optional. Required only if ocelot.user.authentication.mode = SSO
ldap.host ldap.port dap.baseDN ldap.adminDN ldap.username ldap.password ldap.search.filter ldap.userdn ldap.test.username ldap.test.password	Agile Reporter UI using LDAP Login Model	Not applicable	Optional. Required only if ocelot.user.authentication.mode = LDAP
jvm.parameters.Xms jvm.parameters.Xmx	Java Heap Memory	1024 2048	Optional. For example: jvm.parameters.Xms = 1024 jvm.parameters.Xmx = 2048
ocelot.ofsaa.server	OFSAA Config Database server address	Host Name or IP address of the database server that has FSDf installed	For example: 10.XXX.XXXX.XXX
ocelot.ofsaa.port	OFSAA Config Database server port	Database Port	For example: 1521
ocelot.ofsaa.dbType	OFSAA database type (SID / Service name, TNS)	Oracle	Default value is Oracle.
ocelot.ofsaa.connectType	OFSAA connect by SID or Service name	SID Service Oracle TNS	For example: SID Service Oracle TNS
ocelot.ofsaa.instance	OFSAA SID or Service name to connect to OFSAA CONFIG schema	SID / Service name	For example: ORACLEDB
ofsaa.database.tns	OFSAA Connect string	Leave empty if SID or Service name is used. jdbc:oracle:thin:@(TNS String)	For example: jdbc:oracle:thin:@(DESCRIPTION=(ADDRESS=(PROTOCOL=TCP)(HOST=10.XXX.XXX.XXX)(PORT=1521))(CONNECT_DATA=(SERVER=DEDICATED)(SERVICE_NAME=RP_SVC)))
ocelot.ofsaa.username	OFSAA Config Schema Username	Not applicable	For example: AGILE_RPCOWNER
ocelot.ofsaa.password	OFSAA Config Schema password	Not applicable	For example: 5dfc52b51bd355539bd9a0b76da9b8e7
ocelot.secret.key	The secret key used to encrypt the password	Not applicable	For example: M7zsrc2WcWyhz9a0rbkPQw== (A random secret key can be generated using the ocelot-encoding tool.)

Property Name	Description of Property	Permissible values	Comments
activemq.authentication.user	AgileREPORTER admin user	Not applicable	For example: rpadmin
activemq.authentication.password	AgileREPORTER admin password (encrypted)	Not applicable	For example: 5dfc52b51bd355539bd9a0b76da9b8e7

4. Navigate to the path where OFS AgileREPORTER installer kit unzipped.
5. Navigate to OFS_AGILE_REPORTER/AgileREPORTER/conf directory.
6. Rename the file `Silent.template` to `Silent.props` and update the file as explained in [Section 4.1.3](#)
7. Navigate to OFS_AGILE_REPORTER/AgileREPORTER/bin directory in the console.
8. Execute `./Setup.sh SILENT` command.

If installation fails, check the log file at `<RP_HOME>/log/install.log` in your installation path.

You can now try opening OFS AgileREPORTER in a web browser. For example, open Internet Explorer and enter `http(s)://<server>:<port>/agilereporter`, specifying the chosen HTTP protocol, server address, and port.

4.1.4 Running the Installer in SILENT Mode for Upgrade

To upgrade OFS AgileREPORTER using the installer in SILENT mode, follow these steps:

1. Take a backup of the `ocelot.properties` file that was used for installing the earlier version of AgileREPORTER and keep it for your reference to fill the `Silent.props` file.
2. Repeat the section "[4.1.3 Running the Installer in SILENT Mode](#)" to upgrade AgileREPORTER.

NOTE	After upgrading from one version of AgileREPORTER to another, any manual changes made to the AgileREPORTER configuration in the previous version must be reapplied to the configuration in the upgraded installation. For example, changes made to the <code>standalone.xml</code> file in the previous version will be overwritten when upgrading.
-------------	---

4.1.5 Verifying the Log File

The log file `install.log` can be found in the path `<RP_HOME>/log/`. The log files contain a detailed summary of installation processes. It also shows the number of Fatal Errors, Errors, Debug Statements, Information, and Warnings.

5 Trial Template Package Installation

As part of the AgileREPORTER installer, you are allowed to install Trial Template Packages for RBI and US FED.

5.1 Trial Template Package for US FED

OFS AgileREPORTER US FED Configuration Package Installation is a new Application, which is used for submitting the regulatory reports to the regulator.

- This installer contains the following three US FED return templates:
- FR Y-9C
- FFIEC-101
- FFIEC-031

NOTE This is a trial pack installer, which can be used only for three returns. Please reach [Oracle Support Services](#) for procuring the license for complete US FED return templates.

5.2 Trial Template Package for RBI

OFS AgileREPORTER RBI Configuration Package Installation is a new application, which is used for submitting the regulatory reports to the regulator Reserve Bank of India.

This installer contains the following three RBI return templates:

- RCA3
- IRS
- RAQ

NOTE This is a trial pack installer, which can be used only for three returns. Please reach [Oracle Support Services](#) for procuring the license for complete RBI return templates.

5.3 Installing Trial Template Packages

This section describes the steps to install sample Template Packages.

1. Navigate to `/OFS_AGILE_REPORTER/Template_Packages/conf` directory.
2. Update the parameters in `params.conf` file present in the directory. The update instructions are present in the file itself.

Parameter	Description	Values
RP_HOME	Agile Reporter Home Directory Install Path.	For example: <code>/scratch/ofsaapp/reporter_portal</code>

Parameter	Description	Values
PACK_ID	Pack ID of Trial Template Package you want to install. NOTE: Only one value at a time is permitted.	The list of values expected are RBI and USFED. For example: USFED

3. Navigate to `/OFS_AGILE_REPORTER/Template_Packages/` directory and execute the command:

```
chmod 755 *
```

4. Navigate to `/OFS_AGILE_REPORTER/Template_Packages/bin` directory.

5. Execute `install.sh` file using the following command.

```
./install.sh
```

6. Verify if the release is applied successfully by checking the log file generated in the installation folder. Logs can be found in the `[Installed path]/log/install.log` file.

6 Start/Stop AgileREPORTER Services

This section describes the steps to start and stop the AgileREPORTER services.

6.1 Start AgileREPORTER Web Server

Following are the steps to start the AgileREPORTER Web server:

1. Navigate to the path where AgileREPORTER is installed and then go the `/bin` directory under the installed location.
2. Execute `nohup ./start.sh > rplog.txt &` command.

6.2 Stop AgileREPORTER Web Server

Following are the steps to stop the AgileREPORTER Web server:

1. Navigate to the path where AgileREPORTER is installed and then go the `/bin` directory under the installed location.
2. Execute `./stop.sh` command.

7 Error Dictionary

The content of this section has been created with the interest to help you resolve the installation issues if any. There is a compilation of all the possible errors that might arise during the installation process with the possible cause and the resolution to quickly fix the issue and proceed further with the installation.

7.1 Accessing Error Dictionary

Instead of scrolling through the document to find the error code, you can use the PDF search functionality. In the Find dialog available in any of the Adobe Acrobat version that you are using to view the PDF document, follow the instructions to quickly find the error resolution.

1. With the Installation Guide PDF open, press **Ctrl+F** or select **Edit → Find**.
2. The **Find** dialog is displayed.
3. Enter the **error code** that is displayed on-screen during infrastructure installation.
4. Press **Enter**. The search results are displayed and highlighted as follows.

Error code - OFSAAI-1003	
Cause	JAVA_HOME/bin not found in PATH variable.
Resolution	Import <JAVA_HOME>/bin into PATH variable. Example: PATH = \$JAVA_HOME/bin:\$PATH export PATH.

Error Dictionary

View the details of the issues, its cause, and resolution specific to the error code. Repeat the step to find an answer to any other errors that you notice during installation. If you are not able to resolve the issue even after following the steps provided in the resolution, you can contact [Oracle Support Services](#) along with log files and appropriate screenshots.

7.2 Error Code Dictionary

7.2.1 Error code - OFSAAI-1002

Cause	No proper arguments are available.
Resolution	Provide proper arguments. Invoke Setup.sh using either SILENT or GUI mode. Example: ./Setup.sh SILENT or ./Setup.sh GUI

OFSAAI Support Contact Details

- Raise an SR in [My Oracle Support \(MOS\)](#) if you have any queries related to EPM, ERM, and FCCM applications.

Send Us Your Comments

Oracle welcomes your comments and suggestions on the quality and usefulness of this publication. Your input is an important part of the information used for revision.

- Did you find any errors?
- Is the information clearly presented?
- Do you need more information? If so, where?
- Are the examples correct? Do you need more examples?
- What features did you like most about this manual?

If you find any errors or have any other suggestions for improvement, indicate the title and part number of the documentation along with the chapter/section/page number (if available) and contact the Oracle Support.

Before sending us your comments, you might like to ensure that you have the latest version of the document wherein any of your concerns have already been addressed. You can access My Oracle Support site which has all the revised/recently released documents.

