

FCUBS GridLink Datasource Configuration
Oracle FLEXCUBE Universal Banking
Release 14.2.0.0.0
[December] [2018]



Table of Contents

- 1. WEBLOGIC JDBC GRIDLINK DATASOURCE..... 1-2
 - 1.1 PREFACE..... 1-2
 - 1.2 PURPOSE..... 1-2
 - 1.3 WEBLOGIC DATA-GRID DATASOURCE OVERVIEW..... 1-2
 - 1.4 INTRODUCTION..... 1-2
 - 1.5 DATABASE RELATED CONFIGURATION 1-3
 - 1.5.1 *ONS Setup*..... 1-3
 - 1.5.2 *Database Service Modification and Monitoring*..... 1-3
 - 1.6 CONFIGURING GRIDLINK DATASOURCE..... 1-4
 - 1.6.1 *Non-XA Gridlink Datasource* 1-4
 - 1.6.2 *XA Gridlink Datasource* 1-8

1. Weblogic JDBC GridLink Datasource

1.1 Preface

You need to carry out certain tasks manually before Oracle FLEXCUBE deployment. This document details out the pre-deployment tasks based on GridLink Datasource configuration in Weblogic Application Server.

1.2 Purpose

Purpose of this document is to give understanding and configuration of Weblogic GridLink Datasource for Oracle FLEXCUBE.

1.3 Weblogic Data-Grid Datasource Overview

In WebLogic Server 12c (12.1.2), JDBC GridLink includes Oracle Database 12c integration, having the latest functionalities of Application Continuity, Database Resident Connection Pool, Pluggable Database and Global Data Services.

The RAC integration capabilities of Universal Connection Pool (UCP) have been utilized by the WebLogic Server GridLink Data Source implementation to provide the Fast Connection Failover (FCF), Runtime Connection Load-Balancing (RCLB),

The active management of the connections in the pool is based on static settings configured on the connection pool itself (min/max capacity, timeouts, etc.) and real time information the connection pool receives from the RAC Oracle Notification Service (ONS) subsystem that advises the “client” of any state changes within the RAC cluster.

WebLogic GridLink Data Sources and JDBC connection pools leverage the load balancing functionality provided by an Oracle RAC database to provide better throughput and more efficient use of resources.

1.4 Introduction

FLEXCUBE is a financial application which needs fast connection failover on runtime to ensure zero downtime and proper disaster recovery.

FLEXCUBE will use GridLink data source for Fast Connection Failover and responds to Oracle RAC events using Oracle Notification Service (ONS). This ensures that the connection pool in the GridLink data source contains valid connections (including reserved connections) without the need to poll and test connections. It also ensures that connections are created on new nodes as they become available.

A GridLink data source uses Fast Connection Failover to:

- Provide rapid failure detection.
- Abort and remove invalid connections from the connection pool.
- Perform graceful shutdown for planned and unplanned Oracle RAC node outages. See Graceful Handling for Oracle RAC Outages.

- Adapt to changes in topology, such as adding or removing a node.
- Distribute runtime work requests to all active Oracle RAC instances, including those rejoining a cluster.

WebLogic GridLink Data Sources and JDBC connection pools leverage the runtime load balancing functionality provided by an Oracle RAC database to provide better throughput and more efficient use by FLEXCUBE application.

Runtime connection load balancing provides the following benefits:

- Manages pooled connections for high performance and scalability.
- Receives continuous recommendations on the percentage of work to route to database instances.
- Adjusts distribution of work based on different back-end node capacities such as CPU capacity or response time.
- Reacts quickly to changes in cluster reconfiguration, application workload, overworked nodes, or hangs.
- Receives metrics from the Oracle RAC Load Balance by ONS. Connections to well performing instances are used most often. New and unused connections to under-performing instances will gravitate away over time.

1.5 **Database Related Configuration**

1.5.1 **ONS Setup**

Make Sure ONS service is running in each of the database servers by issuing the below command.(To be run from GRID home)

ONS Status Check:

```
$ORACLE_HOME/opmn/bin/onsctl ping
ons is not running ...
```

Starting ONS:

```
$ORACLE_HOME/opmn/bin/onsctl start
onsctl start: ons started
$ORACLE_HOME/opmn/bin/onsctl ping
ons is running ...
```

By default ONS runs on port 6200.

1.5.2 **Database Service Modification and Monitoring**

For the database service that we use in the Datasource which makes use of Active Grid Link, goal needs to be defined which defaults to none.

The below sql block needs to be run in the database where the service is created.

```

BEGIN
  DBMS_SERVICE.MODIFY_SERVICE ( service_name => 'psrcbt'
    , aq_ha_notifications => true
    , goal => DBMS_SERVICE.GOAL_THROUGHPUT
    , clb_goal => DBMS_SERVICE.CLB_GOAL_SHORT
  );
END;

```

Also we can monitor the metric generation for our service via v\$servicemetric

1.6 Configuring GridLink Datasource

1.6.1 Non-XA Gridlink Datasource

1) Navigate to Domain → Services → Data Sources → select New > **GridLink data source**

The screenshot shows the Oracle WebLogic Server Administration Console. The main content area displays the 'Summary of JDBC Data Sources' page. A table titled 'Data Sources (Filtered - More Columns Exist)' lists several data sources. The 'GridLink Data Source' is highlighted with a red box. The table has the following columns: Name, Type, JNDI Name, Targets, Scope, and Domain Partitions.

Name	Type	JNDI Name	Targets	Scope	Domain Partitions
Generic Data Source					
GridLink Data Source	Generic	jdbc/BPlatformDataSource	bi_cluster	Global	
Multi Data Source	Generic	jdbc/LocalSvcTbiDataSource	AdminServer	Global	
Proxy Data Source	Generic	jdbc/mds/ovsm	AdminServer, bi_cluster	Global	
UCP Data Source	Generic	jdbc/AuditAppendDataSource	AdminServer, bi_cluster	Global	
opss-audit-DBDS	Generic	jdbc/AuditViewDataSource	AdminServer, bi_cluster	Global	
opss-audit-viewDS	Generic	jdbc/AuditViewDataSource	AdminServer, bi_cluster	Global	
opss-data-source	Generic	jdbc/OpssDataSource	AdminServer, bi_cluster	Global	
wlsservices_datasource	Generic	jdbc/WLSServicesDataSource	bi_cluster	Global	

2) Enter the **Name, JNDI Name**. Choose Database Driver as Oracle's Driver (Thin) for GridLink Connection. Click on **Next**

JDBC GridLink Data Source Properties
The following properties will be used to identify your new JDBC GridLink data source.
* Indicates required fields

What would you like to name your new JDBC GridLink data source?
* **Name:** jdbc/fc/devDS

What scope do you want to create your data source in?
Scope: Global

What JNDI name would you like to assign to your new JDBC GridLink data source?
* **JNDI Name:** jdbc/fc/devDS

What database type would you like to select?
Database Type: Oracle

What database driver would you like to use to create database connections? Note: * indicates that the driver is explicitly supported by Oracle WebLogic Server.
Database Driver: *Oracle's Driver (Thin) for GridLink Connections; Versions: Any

Back Next Finish Cancel

3) Uncheck the **“Supports Global Transactions”** and click on **Next**

ORACLE WebLogic Server Administration Console 12c

Home Log Out Preferences Record Help Welcome, weblogic Connected to: bifoundation_domain

Home > Summary of JDBC Data Sources

Create a New JDBC GridLink Data Source

Back Next Finish Cancel

Transaction Options
You have selected non-XA JDBC driver to create database connection in your new data source.
Does this data source support global transactions? If yes, please choose the transaction protocol for this data source.

Supports Global Transactions

Select this option if you want to enable non-XA JDBC connections from the data source to participate in global transactions using the *Logging Last Resource* (LLR) transaction optimization. Recommended in place of Emulate Two-Phase Commit.

Logging Last Resource

Select this option if you want to enable non-XA JDBC connections from the data source to emulate participation in global transactions using JTA. Select this option only if your application can tolerate heuristic conditions.

Emulate Two-Phase Commit

Select this option if you want to enable non-XA JDBC connections from the data source to participate in global transactions using the one-phase commit transaction processing. With this option, no other resources can participate in the global transaction.

One-Phase Commit

Back Next Finish Cancel

4) Select first option **“Enter individual listener information”** and click **Next**

ORACLE WebLogic Server Administration Console 12c

Home Log Out Preferences Record Help Welcome, weblogic Connected to: bifoundation_domain

Home > Summary of JDBC Data Sources

Create a New JDBC GridLink Data Source

Back Next Finish Cancel

GridLink data source connection Properties Options
You can either enter the complete JDBC URL or enter individual host and port pair and let the assistant generate the JDBC URL.

Enter individual listener information

Enter complete JDBC URL

Back Next Finish Cancel

5) Enter the Database Name, Host Name, Port, User Name, Password, Confirm Password and Click on **Next**

Define Connection Properties.

What is the service name of the database you would like to connect to?

Service Name:

Enter host and port of each listener separated by colon and click the add button. In the case of a RAC DB listener, specify the SCAN address.

Host and Port: **Add**

Remove

What database account user name do you want to use to create database connections?

Database User Name:

What is the database account password to use to create database connections?

Password:

Confirm Password:

Additional Connection Properties:

Protocol:

oracle.jdbc.DRCPConnectionClass:

Back **Next** **Finish** **Cancel**

6) Click “Test All Listeners” and check the connection is established properly with the database and Click **Next**

Change Center

View changes and restarts

No pending changes exist. Click the Release Configuration button to allow others to edit the domain.

Lock & Edit

Release Configuration

Domain Structure

Home > Summary of JDBC Data Sources

Messages

Connection test for jdbc:oracle:thin:@(DESCRIPTION=(ADDRESS_LIST=(ADDRESS=(PROTOCOL=TCP)(HOST=blrgw6117.in.oracle.com)(PORT=1521)))(CONNECT_DATA=(SERVICE_NAME=FCUBS11G))) succeeded.

Create a New JDBC GridLink Data Source

Test All Listeners **Back** **Next** **Finish** **Cancel**

Test GridLink Database Connection

Test the database availability and the connection properties you provided.

What is the full package name of JDBC driver class used to create database connections in the connection pool?

(Note that this driver class must be in the classpath of any server to which it is deployed.)

Driver Class Name: oracle.jdbc.OracleDriver

What is the URL of the database to connect to? The format of the URL varies by JDBC driver.

URL: jdbc:oracle:thin:@(DESCRIPTION=(ADDRESS_LIST=(ADDRESS=(PROTOCOL=TCP)(HOST=blrgw6117.in.oracle.com)(PORT=1521)))(CONNECT_DATA=(SERVICE_NAME=FCUBS11G))))

Click the test button to test each listener.

Test Listener jdbc:oracle:thin:@(DESCRIPTION=(ADDRESS_LIST=(ADDRESS=(PROTOCOL=TCP)(HOST=blrgw6117.in.oracle.com)(PORT=1521)))(CONNECT_DATA=(SERVICE_NAME=FCUBS11G)))

What database account user name do you want to use to create database connections?

Database User Name: FCUBSNBESUP

What is the database account password to use to create database connections?

7) Enter the ONS host:port details which has already been configured in database

no pending changes exist. Click the Release Configuration button to allow others to edit the domain.

Lock & Edit
Release Configuration

Domain Structure
bifoundation_domain
- Domain Partitions
- Environment
- Deployments
- Services
 - Messaging
 - Data Sources
 - Persistent Stores
 - Foreign JNDI Providers
 - Work Contexts
 - XML Registries
 - XML Entity Caches
 - JCOPI
 - Mail Sessions

How do I...?
• Create JDBC GridLink data sources

System Status
Health of Running Servers
Failed (0)
Critical (0)
Overloaded (0)
Warning (0)
OK (2)

ONS Client Configuration
Define ONS Client Configuration
Check to enable the data source to subscribe to and process Oracle FAN events
 FAN Enabled
Enter host and port of each ONS node separated by colon and click the add button.
ONS host and port:
mc13dbzg1-zone-1-mc13-n1:6200
mc13dbzg1-zone-1-mc13-n2:6200

The location of the Oracle wallet file in which the SSL certificates are stored.
ONS Wallet File Directory:

The wallet password attribute that is included as part of the ONS client configuration string. This attribute is only required when ONS is configured to use the SSL protocol.
ONS Wallet Password:
Confirm ONS Wallet Password:

Back Next Finish Cancel

8) Click "Test ONS Nodes" to check the connection with ONS.

Oracle WebLogic Server Administration Console 12c

Change Center
View changes and restarts
No pending changes exist. Click the Release Configuration button to allow others to edit the domain.
Lock & Edit
Release Configuration

Domain Structure
bifoundation_domain
- Domain Partitions
- Environment
- Deployments
- Services
 - Messaging
 - Data Sources
 - Persistent Stores
 - Foreign JNDI Providers
 - Work Contexts
 - XML Registries
 - XML Entity Caches
 - JCOPI
 - Mail Sessions

How do I...?
• Create JDBC GridLink data sources

System Status
Health of Running Servers
Failed (0)
Critical (0)
Overloaded (0)
Warning (0)
OK (2)

Home Log Out Preferences Record Help
Welcome, weblogic | Connected to: bifoundation_domain
Home > Summary of JDBC Data Sources
Messages
✔ Connection test for mc13dbzg1-zone-1-mc13-n1:6200 succeeded.

Create a New JDBC GridLink Data Source
Test All ONS Nodes Back Next Finish Cancel

Test ONS client configuration
Test the ONS client configuration properties you provided
Check to enable the data source to subscribe to and process Oracle FAN events
 FAN Enabled
Enter host and port of each ONS node separated by colon and click the add button.
ONS host and port:
mc13dbzg1-zone-1-mc13-n1:6200, mc13dbzg1-zone-1-mc13-n2:6200

Click the test button to test ONS node.
 mc13dbzg1-zone-1-mc13-n1:6200
 mc13dbzg1-zone-1-mc13-n2:6200

The location of the Oracle wallet file in which the SSL certificates are stored.
ONS Wallet File Directory:

The wallet password attribute that is included as part of the ONS client configuration string. This attribute is only required when ONS is configured to use the SSL protocol.

9) Select Target and click on **Finish**

The screenshot shows the Oracle WebLogic Server Administration Console interface. The main window displays the 'Create a New JDBC GridLink Data Source' wizard. The 'Select Targets' step is active, showing a list of servers and clusters. The 'AdminServer' is selected under the 'Servers' section, and 'All servers in the cluster' is selected under the 'Clusters' section. The 'Finish' button is highlighted, indicating the next step in the process.

1.6.2 XA Gridlink Datasource

1) Navigate to Domain → Services → Data Sources → select New > **GridLink data source**

The screenshot shows the Oracle WebLogic Server Administration Console interface. The main window displays the 'Summary of JDBC Data Sources' page. A table lists existing data sources, with 'GridLink Data Source' highlighted in red. The table columns include Name, Type, JNDI Name, Targets, Scope, and Domain Partitions.

Name	Type	JNDI Name	Targets	Scope	Domain Partitions
Generic Data Source					
GridLink Data Source					
Multi Data Source	Generic	jdbc/BIPPlatformDataSource	bi_cluster	Global	
Proxy Data Source	Generic	jdbc/LocalSvcTBIDataSource	AdminServer	Global	
UCP Data Source	Generic	jdbc/mds/ovsm	AdminServer, bi_cluster	Global	
opss-audit-DBOS	Generic	jdbc/AuditAppendDataSource	AdminServer, bi_cluster	Global	
opss-audit-viewDS	Generic	jdbc/AuditViewDataSource	AdminServer, bi_cluster	Global	
opss-data-source	Generic	jdbc/OpssDataSource	AdminServer, bi_cluster	Global	
wfsservices_datasource	Generic	jdbc/WfsservicesDataSource	bi_cluster	Global	

2) Enter the **Name, JNDI Name**. Choose Database Driver as Oracle's Driver (XA Thin) for GridLink Connection. Click on **Next**

The following properties will be used to identify your new JDBC GridLink data source.
* Indicates required fields

What would you like to name your new JDBC GridLink data source?

What scope do you want to create your data source in?
 Scope:

What JNDI name would you like to assign to your new JDBC GridLink data source?

What database type would you like to select?
 Database Type:

What database driver would you like to use to create database connections? Note: * indicates that the driver is explicitly supported by Oracle WebLogic Server.
 Database Driver:

3) Click **Next**

ORACLE WebLogic Server Administration Console 12c

Home Log Out Preferences Record Help Welcome, weblogic Connected to: bifoundation_domain

Home -> Summary of JDBC Data Sources

Create a New JDBC GridLink Data Source

Transaction Options

You have selected an XA JDBC driver to use to create database connection in your new data source. The data source will support global transactions and use the 'Two-Phase Commit' global transaction protocol. No other transaction configuration options are available.

4) Choose first option "Enter individual listener information" and Click **Next**

ORACLE WebLogic Server Administration Console 12c

Home Log Out Preferences Record Help Welcome, weblogic Connected to: bifoundation_domain

Home -> Summary of JDBC Data Sources

Create a New JDBC GridLink Data Source

GridLink data source connection Properties Options

You can either enter the complete JDBC URL or enter individual host and port pair and let the assistant generate the JDBC URL.

Enter individual listener information
 Enter complete JDBC URL

5) Enter the Database Name, Host Name, Port, User Name, Password, Confirm Password and Click on **Next**

6) Click “Test All Listeners” and check the connection is established properly with the database and Click **Next**

7) Enter the ONS host:port details which has already been configured in database

ONS Client Configuration
Define ONS Client Configuration

Check to enable the data source to subscribe to and process Oracle FAN events

FAN Enabled

Enter host and port of each ONS node separated by colon and click the add button.

ONS host and port:

mc13dbzg1-zone-1-mc13-n1:6200
mc13dbzg1-zone-1-mc13-n2:6200

The location of the Oracle wallet file in which the SSL certificates are stored.

ONS Wallet File Directory:

The wallet password attribute that is included as part of the ONS client configuration string. This attribute is only required when ONS is configured to use the SSL protocol.

ONS Wallet Password:

Confirm ONS Wallet Password:

8) Click "Test ONS Nodes" to check the connection with ONS.

Change Center

View changes and restarts

No pending changes exist. Click the Release Configuration button to allow others to edit the domain.

Domain Structure

System Status

Health of Running Servers

Failed (0)
Critical (0)
Overloaded (0)
Warning (0)
OK (2)

Home Log Out Preferences Record Help

Welcome, weblogic Connected to: bifoundation_domai

Summary of JDBC Data Sources

Messages

Connection test for mc13dbzg1-zone-1-mc13-n1:6200 succeeded.

Create a New JDBC GridLink Data Source

Test All ONS Nodes

Test ONS client configuration

Test the ONS client configuration properties you provided

Check to enable the data source to subscribe to and process Oracle FAN events

FAN Enabled

Enter host and port of each ONS node separated by colon and click the add button.

ONS host and port:

mc13dbzg1-zone-1-mc13-n1:6200,mc13dbzg1-zone-1-mc13-n2:6200

Click the test button to test ONS node.

Test ONS Node mc13dbzg1-zone-1-mc13-n1:6200
Test ONS Node mc13dbzg1-zone-1-mc13-n2:6200

The location of the Oracle wallet file in which the SSL certificates are stored.

ONS Wallet File Directory:

The wallet password attribute that is included as part of the ONS client configuration string. This attribute is only required when ONS is configured to use the SSL protocol.

9) Select Target and click on **Finish**

The screenshot displays the Oracle WebLogic Server Administration Console interface. The main window title is "ORACLE WebLogic Server Administration Console 12c". The breadcrumb navigation shows "Home > Summary of JDBC Data Sources". The user is logged in as "weblogic" and is connected to the "bifoundation_domain".

The "Change Center" panel on the left indicates "No pending changes exist. Click the Release Configuration button to allow others to edit the domain." and provides buttons for "Lock & Edit" and "Release Configuration".

The "Domain Structure" tree on the left shows the following hierarchy:

- bifoundation_domain
 - Domain Partitions
 - Environment
 - Deployments
 - Services
 - Messaging
 - Data Sources
 - Persistent Stores
 - Foreign JNDI Providers
 - Work Contexts
 - XML Registries
 - XML Entity Caches
 - JCOM
 - Mail Sessions

The "How do I..." panel shows a link to "Create JDBC GridLink data sources".

The "System Status" panel is visible at the bottom left.

The main content area is titled "Create a New JDBC GridLink Data Source". It includes navigation buttons: "Back", "Next", "Finish", and "Cancel".

The "Select Targets" section contains the following text: "You can select one or more targets to deploy your new JDBC data source. If you don't select a target, the data source will be created but not deployed. You will need to deploy the data source at a later time."

The "Servers" section has a checked checkbox for "AdminServer".

The "Clusters" section has a checked checkbox for "bi_server1" under the "Part of the cluster" option.

Navigation buttons "Back", "Next", "Finish", and "Cancel" are located at the bottom of the wizard.



FCUBS Gridlink Datasource Configuration
[December] [2018]
Version 14.2.0.0.0

Oracle Financial Services Software Limited
Oracle Park
Off Western Express Highway
Goregaon (East)
Mumbai, Maharashtra 400 063
India

Worldwide Inquiries:
Phone: +91 22 6718 3000
Fax: +91 22 6718 3001
<https://www.oracle.com/industries/financial-services/index.html>

Copyright © [2007], [2018], Oracle and/or its affiliates. All rights reserved.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate failsafe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.