

FCUBS-OBPM Integration Setup Guide

Oracle Banking Payments

Release 14.2.0.0.0

Part No. F11932-01

November 2018

Oracle Banking Payments FCUBS-OBPM Integration Setup Guide
Oracle Financial Services Software Limited

Oracle Park

Off Western Express Highway
Goregaon (East)
Mumbai, Maharashtra 400 063
India

Worldwide Inquiries:

Phone: +91 22 6718 3000

Fax: +91 22 6718 3001

www.oracle.com/financialservices/

Copyright © 2007, 2019, Oracle and/or its affiliates. All rights reserved.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate failsafe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.

Table of Contents

1. Introduction	1
1.1 About This Manual	1
1.2 Audience	1
1.3 Documentation Accessibility	1
1.4 Organization	1
1.5 Glossary	1
2. Integration Guide	2
2.1 Introduction	2
2.2 Installation guide	2
2.3 Maintenances to be done in FCUBS	4
2.3.1 Branch Maintenance	4
2.3.2 External Payments System Maintenance.....	5
2.3.3 External System Functions Maintenance	5
2.3.4 Upload Source Preference Maintenance	6
2.3.5 BIC Maintenance	7
2.3.6 Other Common Maintenances.....	7
2.4 Maintenances to be done in OBPM	7
2.4.1 Source Maintenance	7
2.4.2 Source Network Preference Maintenance.....	9
2.4.3 Network Rule maintenance.....	9
2.4.4 Notification maintenance.....	10
2.4.5 ECA System Maintenance	11
2.4.6 Accounting System Maintenance.....	12
2.4.7 Customer Maintenance.....	13
2.4.8 Account Maintenance	13
2.4.9 General Ledger Maintenance.....	13
2.4.10 Transaction code Maintenance.....	14
2.4.11 OBPM to use FCUBS Dates	14
2.4.12 Other Payments Maintenances.....	14
2.5 FAQ's	14

1. Introduction

1.1 About This Manual

This manual is designed to help with Integration for a Co-deployed Set-up of Oracle Banking Payments with Oracle FLEXCUBE Universal Banking.

1.2 Audience

This manual is intended for the following User/User Roles:

Role	Function
Implementation & IT Staff	Implementation & Maintenance of the Software

1.3 Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

1.4 Organization

This manual is organized into the following chapters:

Chapter	Description
Chapter 1	Information about this Manual is specified in this section
Chapter 2	This chapter helps you co-deploy Oracle FLEXCUBE Universal Banking & Oracle Banking Payments product in a single instance.

1.5 Glossary

This User Manual may refer to the following terms:

Abbreviation	Description
FCUBS	Oracle FLEXCUBE Universal Banking
OBPM	Oracle Banking Payments

2. Integration Guide

2.1 Introduction

You can integrate Oracle Banking Payments product (OBPM) with Oracle FLEXCUBE Universal Banking product (FCUBS). The specific steps needed on the co-deployed installation of these two products and specific maintenances needed are briefed on this document.

2.2 Installation guide

Refer to Installation guide for understanding the property file and installation bat files used for integration between FCUBS and OBPM.

Web-logic set-up

Deployments:

Following ears to be deployed for the FCUBS Gateway support through JMS:

- GWEJB
- GWMDB

Queue Maintenance:

- MDB_QUEUE
- MDB_QUEUE_RESPONSE -with Expiry Policy as redirect and error destination as jms/ACC_ENTRY_RES_BKP_IN in Delivery Failure. Keep Redelivery Limit as zero and “Time-to-Live Override” value as 2000.

To set the “Time-to-Live Override” property, navigate to MDB_QUEUE_RESPONSE -> Configuration-> Overrides Tab

Home > Summary of JMS Modules > PMJMSMODULES > MDB_QUEUE_RESPONSE

Settings for MDB_QUEUE_RESPONSE

Configuration | Monitoring | Control | Security | Subdeployment | Notes

General | Thresholds and Quotas | **Overrides** | Logging | Delivery Failure

Click the *Lock & Edit* button in the Change Center to modify the settings on this page.

Destinations can override some of the settings (such as priority) that a message producer includes with its messages. Use this page to configure such overrides for this queue.

Priority Override:	<input type="text" value="-1"/>	The priority assigned to all messages that arrive at this destination, regardless of the Priority specified by the message producer. The default value (-1) specifies that the destination will not override the Priority set by the message producer. More Info...
Time-to-Live Override:	<input type="text" value="2000"/>	The time-to-live assigned to all messages that arrive at this destination, regardless of the TimeToLive value specified by the message producer. The default value (-1) specifies that this setting will not override the TimeToLive setting specified by the message producer. More Info...
Time-to-Deliver Override:	<input type="text" value="-1"/>	The default delay, either in milliseconds or as a schedule, between when a message is produced and when it is made visible on its target destination, regardless of the delivery time specified by the producer and/or connection factory. The default value (-1) specifies that the destination will not override the TimeToDeliver setting specified by the producer and/or connection factory. The TimeToDeliver override can be specified either as a long or as a schedule. More Info...
Delivery Mode Override:	<input type="text" value="No-Delivery"/>	The delivery mode assigned to all messages that arrive at the destination regardless of the DeliveryMode specified by the message producer. More Info...

Click the *Lock & Edit* button in the Change Center to modify the settings on this page.



To set the “Error Destination”, “Expiration Policy” and “Redelivery Limit” properties, navigate to MDB_QUEUE_RESPONSE Configuration Delivery Failure tab.

The screenshot shows the Oracle WebLogic Server Administration Console. The main content area is titled "Settings for MDB_QUEUE_RESPONSE" and has several tabs: Configuration, Monitoring, Control, Security, Subdeployment, and Notes. The "Configuration" tab is active, and the "Delivery Failure" sub-tab is selected. The configuration includes:

- Redelivery Delay Override:** -1
- Redelivery Limit:** 0
- Expiration Policy:** Redirect (highlighted with a red box)
- Expiration Logging Format:** (empty)
- Error Destination:** jms/ACC_ENTRY_RES_BKP_IN (highlighted with a red box)

 There are "Save" buttons at the top and bottom of the configuration area. On the left side, there are panels for "Change Center", "Domain Structure", "How do I...", and "System Status".

Maintenance for Gateway:

GWDEFUN - Gateway External system function maintenance



Ensure the Gateway setup for following services are maintained in FCUBS for external source system as FCUBS:

Service Name	Operation Code(s)
FCUBSAccService	QueryCustAccVal
FCUBSCAService	CreateEcablk CloseEcablk
FCUBSIFService	CreateExtAccEcaEntries

Source: FCUBS and User: SYSTEM

CODUPLDM - Upload Source Preferences maintenance



Ensure Upload Source preference setup for following modules are maintained in FCUBS for external source system as FCUBS:

Module	Post Upload Status
IF	Authorized
CA	Authorized



2.3 Maintenances to be done in FCUBS

This section describes the specific maintenances, needed in Oracle FLEXCUBE Universal Banking (FCUBS) to install & integrate the same with Oracle Banking Payments (OBPM).

2.3.1 Branch Maintenance

Create branch in STDCRBRN screen in FCUBS.

Specify a host for every branch created. (To maintain Host time zone, refer OPBM Payments Core User Manual).



A pair of branches which could transact inter-branch payments, should be maintained under the same host.

In addition, map the branch code created above, in STDBRANC screen, and maintain the branch parameters.

ORACLE

2.3.2 External Payments System Maintenance

Maintain an active record in External System Maintenance screen (IFDEPSMT) with field external system type as "Payments" for different service codes with all required fields in the detailed section of this screen

- For outgoing payments, maintain the service code as "GenPayMessage" with OBPM Single Payment Service details as below:
 - Service Name – PMSinglePaymentService
 - Operation Code – CreateSinglePayment
 - Web Service User Option - Choose the preferred option
 - Web Service User – Provide the User to be used in Gateway request
 - Web Service URL Service – Provide the WSDL URL of OBPM Single Payment Service

- For MT110 - Advice of Cheque(s), maintain the service code as 'GenInstrIssue' with OBPM Instrument Issuance Service details as below:
 - Service Name - PMInstrumentIssueService
 - Operation Code - CreateInstrumentIssue
 - Web Service User Option - Choose the preferred option
 - Web Service User - Provide the User to be used in Gateway request
 - Web Service URL - Provide the WDSL URL of OBPM Instrument Issuance Service.

- For MT111 - Request for Stop Payment of a Cheque, maintain the service code as 'GenInstrStop' with OBPM Instrument stop Service details as below:
 - Service Name - PMInsStopPayService
 - Operation Code - CreateInsStopPay
 - Web Service User Option - Choose the preferred option
 - Web Service User - Provide the User to be used in Gateway request
 - Web Service URL - Provide the WDSL URL of OBPM Instrument Stop Service

- For Outgoing Collections - Request for DD Creation, maintain the service code as 'CreateDDOutService' as below:
 - Service Name - PMDDOutService
 - Operation Code - CreateDDOutService
 - Web Service User Option - Choose the preferred option
 - Web Service User - Provide the User to be used in Gateway request
 - Web Service URL - Provide the WDSL URL of OBPM

External System Maintenance

New Copy Close Unlock Enter Query

External System * OBPM
 Description External Payment System
 Inter System Bridge GL * 261100005
 Source System * FCUBS
 Entity ID * ENTITY_ID1

External System Type * Payments
 Read Time Out (In Seconds) 70
 Connection Time Out (In Seconds) 50
 Archival Days 3

Service Code	Service Name	Operation Code	Web Service User Option	Web Service User	
<input type="checkbox"/> CreateDDOutService	PMDDOutService	CreateDDOutService	Contract User		http:
<input type="checkbox"/> GenInstrIssue	PMInstrumentIssueService	CreateInstrumentIssue	Predefined User	FCUSER1	http:
<input type="checkbox"/> GenInstrStop	PMInsStopPayService	CreateInsStopPay	Predefined User	FCUSER2	http:
<input checked="" type="checkbox"/> GenPayMessage	PMSinglePaymentService	CreateSinglePayment	Contract User		http:

Maker PERURAJ Date Time: 2019-03-22 14:39:47 Mod No 7 Record Status Open
 Checker PERURAJ Date Time: 2019-03-22 14:39:50 Authorization Authorized Status

Exit

2.3.3 External System Functions Maintenance

Maintain the gateway preferences for the below Source codes for the service name “FCUBSEPSService” with operation code “CreateEPSNotification” to receive the notifications from OBPM

- FCUBSCL
- FCUBSRT
- FCUBSTD

For all FCUBS corporate modules where outgoing payment is initiated, the source code will be “FCUBS<Module-ID>”. For example, the source code for FX module will be “FCUBSFX”.

External System Functions

New Copy Close Print Enter Query

External System * FCUBSCL
 Function * IFGEPSNO
 Action * NEW
 Service Name FCUBSEPSService
 Operation Code CreateEPSNotification

Description Notif Test
 Bulk SMS Check

Fields

Maker RAMYA_A Date Time: 2018-03-16 18:30:26 Mod No 1 Record Status Open
 Checker RAMYA_A Date Time: 2018-03-16 18:30:26 Authorization Authorized Status

Exit



2.3.4 Upload Source Preference Maintenance

In Upload Source Preference Maintenance screen (CODUPLDM), Post Upload Status field value should be selected as “Authorized”.

Upload Source Preferences Maintenance

New Copy Close Unlock Print Enter Query

Source Code * FCUBSCL
Module Code * IF

Error Handling

On Error *

On Override *

On Repairable Exception

On Queue Exception

Post Upload

Status *

Purge Days

Allow Deferred Processing

Allow EOD with Deferred

Deletion Allowed

Function ID Preference

Maker RAMYA_A	Date Time: 2014-05-20 17:53:03	Mod No	1	Record Status	Open
Checker RAMYA_A	Date Time: 2014-05-20 17:53:03			Authorization	Authorized Status



Below are the scheduler jobs configured for the integration. Make sure that these jobs are running.

- ✓ EPSGENPAYMENT - Scheduler job for processing Payment request
- ✓ EPS_NOTIFICATION - Scheduler job for processing OBPM notifications

2.3.5 BIC Maintenance

Upload BIC directory & ensure that the same are listed at ISDBICDE, which UBS will use, to transact payments.

2.3.6 Other Common Maintenances

Refer FCUBS Core User Manual, for the other Day0 maintenances to be done in FCUBS.

2.4 Maintenances to done in OBPM

This section describes the specific maintenances needed in Oracle Banking Payments (OBPM) to install & integrate the same with Oracle FLEXCUBE Universal Banking (FCUBS).

2.4.1 Source Maintenance

Maintain the Source code with which FCUBS will handoff payment requests at PMDSORCE- Source maintenance screen.

Following are the source codes FCUBS uses to initiate payment request:

- FCUBSCL
- FCUBSRT
- FCUBSTD

For all FCUBS corporate modules where outgoing payment is initiated, the source code will be "FCUBS<Module-ID>". For example, the source code for FX module will be "FCUBSFX".

Each record maintained in Source Maintenance Detailed screen (PMDSORCE) should have the below preferences:

- Prefunded Payments GL should match Inter System Bridge GL maintained in External Payment System Maintenance screen (IFDEPSMT) of FCUBS.
- To initiate a payment for Loan disbursement/ Deposit maturity etc. FCUBS will credit the funds in an intersystem bridge GL. This is needs to be maintained as Prefunded GL in OBPM.



This GL should be maintained in FCUBS & replicated to OBPM.

2.4.2 Source Network Preference Maintenance

Maintain the FCUBS Source specific preferences for each network at PMDSORNW screen.

Source Network Preferences Detailed

New Copy Close Unlock Print Enter Query

Host Code * LIEGE
Source Code * FCUBSRT
Network Code * SWIFT
Transaction Type * Outgoing

Description: FCUBS RT
Network Description: Cross Border
Payment Type: Cross Border

Preferences

Authorization Rekey Required

Sanctions System

Sanction Check Required

Pricing

External Pricing Applicable

Authorization Limit

Authorization Limit Currency: _____
Authorization 1 Limit: _____
Authorization 2 Limit: _____
Network Release Limit: _____

Authorization Rekey Fields

1 Of 1

Rekey Field Name	Description
------------------	-------------

Maker: FCUSER1 Date Time: 2014-01-01 23:26:09 Mod No: 1 Record Status: Open
Checker: FCUSER1 Date Time: 2014-01-01 23:26:09 Authorization Status: Authorized

Exit

The preference for various payment networks via which FCUBS will initiate a payment request needs to be maintained on this screen for the same Source codes as in the previous Section.

2.4.3 Network Rule maintenance

OBPM should maintain appropriate Network Rule maintenance (PMDNW RLE) to route the FCUBS request to the respective network.

- ✓ Based on the Payment type, FCUBS system will send one of the values (LCL, SWIFT, RTGS) in Service Level Proprietary field, which further will be used to build the network rules,
 - LCL - Local clearing payments
 - SWIFT - SWIFT Payment messages
 - RTGS - RTGS Payment messages

Network Rule Detailed

New Copy Close Unlock Print Enter Query

Host Code * LIEGE Channel Type * Single Payment

Rule Name *	Rule Expression	Network Code *
<input checked="" type="checkbox"/> ACH	ValueOf {'SERVICE_LEVEL'} EQUAL 'LCL'	ACH
<input type="checkbox"/> BOOK	ValueOf {'SERVICE_LEVEL'} EQUAL 'BOOK'	BOOK
<input type="checkbox"/> RTGS	ValueOf {'SERVICE_LEVEL'} EQUAL 'RTGS'	RTGS
<input type="checkbox"/> SWIFT	ValueOf {'SERVICE_LEVEL'} EQUAL 'SWIFT'	SWIFT
<input type="checkbox"/> STEP2	ValueOf {'SERVICE_LEVEL'} EQUAL 'SEPA'	STEP2

Expression Details

Scope	LOP Operand	Operator	ROP Type	ROP Data Type	ROP Operand
	SERVICE_LEVEL	Equal To	Constant	String	LCL

Maker DEEPIKA19 Date Time: 2014-01-01 00:50:09 Mod No 3 Record Status Open
 Checker DEEPIKA19 Date Time: 2014-01-01 00:50:09 Authorization Status Authorized

Exit

2.4.4 Notification maintenance

Maintain the FCUBS Source specific notification preferences for each network at PMDEXTNT screen.

External Notification Queue Detailed

New Copy Close Unlock Print Enter Query

Host Code * LIEGE Communication Type Web Service
 Source Code * FCUBSTD Timeout in Seconds
 Notification System Class FCUBS


JMS Preferences
 Outqueue JNDI Name Q Profile

WebService Preferences
 WebService URL http://10.184.158.19:7843/FCUBSEPPService/FCUBSEPPService Service FCUBSEPPService

ReST Preferences
 ReST URL

Maker FCUSER4 Date Time: 2018-04-27 12:36:04 Mod No 1 Record Status Open
 Checker FCUSER4 Date Time: 2018-04-27 12:36:04 Authorization Status Authorized

Exit

 The notification is a call from OBPM to the FCUBS Webservice – FCUBSEPPService that needs to be deployed. The gateway external system setup is required to be done for source code mentioned in the above screen shot. It is important to give the Notification System class as FCUBS and communication mode as Web Service.

2.4.5 External System Functions Maintenance

Maintain the gateway preferences for the Source System which is maintained in the Source system field of External System Maintenance screen (IFDEPSMT) in FCUBS, for the service names “PMSinglePaymentService”, “FCUBSDDServices”, “PMInstrumentIssueService” and “PMInsStopPayService” with their respective operation codes

External System Functions

Enter Query

External System * FCUBS

Function * PIDINSIS

Action * NEW

Service Name PMInstrumentIssueService

Operation Code CreateInstrumentIssue

Fields

Maker RAMYA03	Date Time: 2018-03-22 08:19:19	Mod No 1	Record Status Open
Checker RAMYA03	Date Time: 2018-03-22 08:19:19		Authorization Authorized Status

Exit

2.4.6 ECA System Maintenance

Create External Credit Approval Check system as 'FCUBS' in STDECAMT screen.

External Credit Approval System

New Copy Close Unlock Print Enter Query

Source System FCUBS

Description FLEXCUBE

Maker VANDIT04	Date Time: 2014-01-01 12:39:38	Mod No 1	Record Status Open
Checker VANDIT04	Date Time: 2014-01-01 12:39:38		Authorization Status Authorized

Map the ECA system 'FCUBS' in the PMDECAMT.

External Credit Approval System Detailed

New Copy Close Unlock Print Enter Query

External Credit Approval System * FCUBS

Description Flexcube system

Communication Type JMS Queue

Other Preferences

ECA System Class FCUBS

Inter System Bridge GL 261100005

JMS Preferences | WebService Preferences | ReST Preferences

Preferences

Inqueue JNDI Name MDB_QUEUE_RESPONSE

Outqueue JNDI Name MDB_QUEUE

Q Profile QPROFILE

Faster Payment Preferences

Inqueue JNDI Name MDB_QUEUE_RESPONSE

Outqueue JNDI Name MDB_QUEUE

Status Mapping

Maker DEEPIKA19 Date Time: 2017-11-09 12:40:47 Mod No 395 Record Status Open

Checker DEEPIKA19 Date Time: 2017-11-09 12:40:47 Authorization Status Authorized

Exit

Maintain the In queue JNDI Name as MDB_QUEUE_RESPONSE, Outqueue JNDI Name as MDB_QUEUE & Q Profile – as per the MDB Queue created on the App Server as in Section 2.2. Q Profile should be the IP Address where the JMS Queue has been created. The OBPM System will post the ECA request to UBS via these MDB queues. Maintain Queue Profile in

‘PMDQPROF’

Queue Connection Profile Maintenance Detailed

New Copy Unlock Enter Query

Profile ID * QPROFILE Queue Authentication Required

Profile Description Queue Profile

User ID

Password

Context Provider URL 13://10.184.155.74:9010

Initial Context Factory Class weblogic.jndi.WLInitialContextFactory

Queue Factory JNDI jms/PSQCF

Maker SUBIT2 Date Time: 2017-09-06 12:55:18 Mod No 1 Record Status Open

Checker SUBIT4 Date Time: 2017-09-06 12:58:38 Authorization Status Authorized

Exit

Queue profile requires the context provider URL of the Application Server where the queue is created. All other parameters are same as mentioned above.

STOP OBPM build the ECA request with details mentioned in section 2.2 and post to MDB_QUEUE. FCUBS via GW MDB pulls the gateway request and calls internally the ECA block process to create or undo the ECA block. Once the process is completed, the FCUBS posts the response via gateway infra to MDB_QUEUE_RESPONSE.

MDB_QUEUE_RESPONSE is configured with a redelivery Queue as jms/ACC_ENTRY_RES_BKP_IN mentioned in section 2.2. This Queue is internally pull the response via OBPM MDB to complete ECA processing in OBPM.

Following are the Services and Operations used by OBPM to post in to

- FCUBS: FCUBSAccService – QueryCustAccVal (Operation)
- FCUBSCASService – CreateEcabl, CloseEcabl (Operation)

2.4.7 Accounting System Maintenance

Maintain the accounting system as 'FCUBS' in PMDACMCT.

External Accounting System Detailed

New Copy Close Unlock Print Enter Query

External Accounting System * FCUBS Description * External accounting handoff interface

Preferences

Outqueue JNDI Name MDB_QUEUE

Inqueue JNDI Name MDB_QUEUE_RESPONSE

Q Profile

Maker DEEPIKA19 Date Time: 2017-11-06 14:21:22 Mod No 4 Record Status Open

Checker DEEPIKA19 Date Time: 2017-11-06 14:21:22 Authorization Status Authorized

Exit

Maintain the In queue JNDI Name as MDB_QUEUE_RESPONSE, Outqueue JNDI Name as MDB_QUEUE & Q Profile (refer section 2.4.5). The OBPM system will post the Accounting handoff request to FCUBS via these MDB queues.

Maintain Account System Mapping for the Accounting System and Networks (PMDACMAP)

Accounting System Mapping

New Copy Close Unlock Print Enter Query

Host Code * FINLAND Default External Accounting System Code FCUBS


Network Specific Maintenance

Network Code *	External Accounting System Code
<input checked="" type="checkbox"/> SWIFT	FCUBS

Maker SUBIT4 Date Time: 2017-09-06 15:02:43 Mod No 2 Record Status Open

Checker SUBIT4 Date Time: 2017-09-06 15:02:43 Authorization Status Authorized

Exit

 OBPM build the Accounting Handoff request with details mentioned in section 2.2 and post to MDB_QUEUE. FCUBS via GW MDB pulls the gateway request and calls internally the External Accounting request. Once the process is completed, FCUBS posts the response via gateway infra to MDB_QUEUE_RESPONSE.

MDB_QUEUE_RESPONSE is configured with a redelivery Queue as jms/ACC_ENTRY_RES_BKP_IN mentioned in section 2.2. This Queue internally pulls the response via OBPM MDB to complete Accounting Handoff processing in OBPM.

Following is the Service and Operation used by OBPM to post in to FCUBS:

FCUBSIFService - CreateExtAccEcaEntries (Operation)

2.4.8 Customer Maintenance

Create the customers in FCUBS system, which will be automatically replicated and displayed at STDCIFCR in OBPM.

Creation of CIF, its amendments, closure & re-open status will get auto replicated to OBPM, with the latest data.

2.4.9 Account Maintenance

Create the accounts (Normal / Nostro type) in FCUBS system which will be automatically replicated and displayed at STDCRACC in OBPM.

Creation of accounts, its amendments, closure & re-open status will get auto replicated to OBPM with the latest data.

2.4.10 General Ledger Maintenance

Create the General Ledger in FCUBS system which will be automatically replicated and displayed at STDCRGLM in OBPM.

Creation of General Ledgers, its amendments, closure & re-open status will get auto replicated to OBPM with the latest data.

2.4.11 Transaction code Maintenance

Create the transaction code in FCUBS system which will be automatically replicated and displayed at STDCRTRN in OBPM.

Creation of transaction codes, its amendments, closure & re-open status will get auto replicated to OBPM with the latest data.

2.4.12 OBPM to use FCUBS Dates

Maintain IS_CUSTOM_DATE parameters as 'Y' in cspb_param table. By this, OBPM will use the 'Today' from sttm_dates as the transaction booking date.

This parameter value should be modified to N in Production environment.

2.4.13 Other Payments Maintenances

Refer OPBM Payments Core User Manual, for the other Day 0 maintenances to be done.

2.5 FAQ's

This section describes the FAQ's for the scenarios noticed on accounting handoff between Oracle Banking Payments & Oracle FLEXCUBE Universal Banking systems, on the Co-deployed set-up.

1. Accounting handoff is in Pending status:

OBPM isn't able to post the accounting entries to UBS accounting jms queue. If in the PM debugs, shows failed to initialize jndi factory, check the following in PMSSYSPPM – System parameters:

- PM.CTX.FACTORY - weblogic.jndi.WLInitialContextFactory
 - PM_CTX_PROVIDER – Provider URL** of the app server
- a. (** Provider URL will be the http URL of the app URL. E.g.: if Application URL is https://hostname:9011/FCJNeoWeb/, then provider URL will be t3://hostname:9010)
 - b. In PMDQPROF screen – Q profile – Specify the correct Initial factory & provider URL (same as above). QCF should be MDBQCF. Ensure this MBDQCF is configured in WebLogic.
 - c. Update the Provider URL in Pmtm_job_param & pmtm_system_parameters tables.
 - d. Do restart the application after the above changes.

2. Accounting handoff is in Requested status:

The accounting is passed successfully by OBPM, but response from UBS system is not received yet.

- a. Check the MDB settings as indicated above & MDB gateway log.
- b. Check gwtm_in_log & gwtm_out_log tables for the exception details & message clob. The correlation ID in the accounting request XML of the transaction will be key between the two systems.

3. Accounting handoff is in Rejected status:

Accounting entries handed off by OBPM has been rejected by UBS.

- a. In OBPM application front end, go to the view transaction (PXDOVIEW / PBDOVIEW / PADOVIEW), query the transaction. Click on View Q action. In Queue action log the sub screen, selecting the Accounting Response row, Click View response. Check the error & take corrective action as below:
- b. If error is “No data found for source combination” - > Maintain in GWDEFUN a record for source code FCUBS & CreateExtAccEcaEntries (NEW) combination
- c. If error is “User doesn't have rights to perform operation” - > Maintain in SMDUSRDF, for SYSTEM user, add roles for the respective branch.
- d. Additionally, ensure the below maintenance are done:
 - i. Maintain Source as FCUBS in CODSORCE
 - ii. Maintain Source Preference for FCUBS Source and IF Module in CODUPLDM
 - iii. Set Correlation pattern in GWDETSYS as Correlation ID. Not Message ID.

Relevant debugs to be analyzed:

MDB_Kernel11.1_gwlog_<Date>.log: GW MDB Log

SYSTEM<Branchcode>: Db Dbg