

Oracle Banking Digital Experience

FCUBS Setup and Configuration Guide

Release 18.3.0.0.0

Part No. F12056-01

December 2018

ORACLE®

FCUBS Setup and Configuration Guide

December 2018

Oracle Financial Services Software Limited

Oracle Park

Off Western Express Highway

Goregaon (East)

Mumbai, Maharashtra 400 063

India

Worldwide Inquiries:

Phone: +91 22 6718 3000

Fax: +91 22 6718 3001

www.oracle.com/financialservices/

Copyright © 2018, Oracle and/or its affiliates. All rights reserved.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate failsafe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.

Table of Contents

1. Preface	4
1.1 Intended Audience	4
1.2 Documentation Accessibility	4
1.3 Access to OFSS Support	4
1.4 Structure	4
2. Introduction	5
3. Security credential mapping for connector.ear	6
4. Database Configuration	10
4.1 System Configuration	10
4.2 Additional (functional) Configurations	10
4.3 Dealer Maintenance	11
4.4 Social Media Integration	11
5. Product Configuration	12
6. Admin Maintenance	13
6.1 Income Type maintenance	13
6.2 Liability Type maintenance	13
6.3 Accommodation Type maintenance	14
6.4 Financial Parameters maintenance	14

1. Preface

1.1 Intended Audience

This document is intended for the following audience:

- Customers
- Partners

1.2 Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

1.3 Access to OFSS Support

Oracle customers have access to electronic support through My Oracle Support. For information, visit

<http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

1.4 Structure

This manual is organized into the following categories:

Preface gives information on the intended audience. It also describes the overall structure of the User Manual.

The subsequent chapters describes following details:

- Introduction
- Preferences & Database
- Configuration / Installation.

1.5 Related Information Sources

For more information on Oracle Banking Digital Experience Release 18.3.0.0.0, refer to the following documents:

- User Manual Oracle Banking Digital Experience Installation Guide

2. Introduction


This document is intended for setting up OBDX 18.3.0.0.0 originations with FCUBS 12.4.0.0.0 and FCUBS 14.0.0.0.0 releases.

[Home](#)

3. Security credential mapping for connector.ear

Please follow following steps

1. Login into Weblogic console.
2. Click on **Deployments**.
3. Expand by clicking '+' icon present in front of **com.ofss.digx.app.connector** application as shown below.



4. Click **com.ofss.digx.connector.rar** as shown below.

<input type="checkbox"/>	<input type="checkbox"/> com.ofss.digx.app.connector	Active
	<input type="checkbox"/> Modules	
	<input checked="" type="checkbox"/> com.ofss.digx.connector.rar	
	<input type="checkbox"/> EJBs com.ofss.digx.connector.rar, Level 3, 1 of 1	
	None to display	
	<input type="checkbox"/> Web Services	
	None to display	

- Click **'Security'** tab and then click **'Outbound Credential Mappings'** sub tab as shown below.

Settings for com.ofss.digx.connector.rar

Overview Configuration **Security** Control Testing Monitoring

Roles Policies **Outbound Credential Mappings** Inbound Principal Mappings Principals

Outbound credential mappings let you map WebLogic Server usernames to usernames in the Enterprise Information System (EIS) to which you want to map. You can specify outbound credential mappings for all outbound connection pools in the resource adapter, or specify particular outbound credential mappings for this resource adapter.

[Customize this table](#)

Outbound Credential Mappings

New Delete

<input type="checkbox"/>	WLS User ↕	EIS User	Outbound Connection Pool
There are no items to display			

New Delete

- Click on **'New'** Button. Following screen will be appearing.

Back Next Finish Cancel

Outbound Connection Pool

Which Outbound Connection Pool would you like the credential map to be associated with? Each Outbound Connection Pool can then configure themselves to use the credential map.

[Customize this table](#)

Create a New Security Credential Map Entry for:

<input type="checkbox"/>	Outbound Connection Pool ↕
<input type="checkbox"/>	ra/DIGXConnectorAES
<input type="checkbox"/>	ra/DIGXConnectorBIREPORTS
<input type="checkbox"/>	ra/DIGXConnectorFILEUPLOAD
<input type="checkbox"/>	ra/DIGXConnectorMERCHANT
<input type="checkbox"/>	Resource Adapter Default

Back Next Finish Cancel

7. Select '**ra/DIGXConnectorAES**' and click then '**Next**' button. Following screen will be appearing.

Back Next Finish Cancel

WebLogic Server User

Select the WebLogic Server User that you would like to map an EIS resource adapter is first started. Selecting 'Default User' will configure them. Selecting 'User for unauthenticated user' will configure the user that you are configuring. This user must be a configured WebLogic user.

User for creating initial connections

Default User

Unauthenticated WLS User

Configured User Name

WebLogic Server User Name:

Back Next Finish Cancel

8. Select '**Default User**' and then click '**Next**' button. Following screen will be appearing.

Back Next Finish Cancel

EIS User Name and Password

Configure the EIS User Name and Password that you would like to map the WebLogic Server User to:

* Indicates required fields

Enter the EIS User Name:

* **EIS User Name::**

Enter the EIS Password:

* **EIS Password::**

* **Confirm Password::**

Back Next Finish Cancel

9. Enter following details and then click '**Finish**' button.
 - EIS User Name → AES_KEY
 - EIS Password → OBDX_PASSWORD123
 - Confirm Password → OBDX_PASSWORD123

10. Restart the manage server to activate the changes.

[Home](#)

4. Database Configuration

Following configurations need to be done post installation

4.1 System Configuration

Please complete day one maintenance from admin screen. Please refer 'User Manual Oracle Banking Digital Experience System Configuration.docx' document for day one maintenance. These are mandatory configurations for application to work. It should be completed before using the application.

4.2 Additional (functional) Configurations

These are non-mandatory configurations. Default values for these configurations are available through day 0 scripts. Bank can change these values as per their business need.

Table 'digx_fw_config_var_b'

Category Id	Property Id	Description
OriginationUserRole	USER_ROLE_CUSTOM ER	Default roles for Origination user creation. The prop_id does not matter. All roles for category_id 'OriginationUserRole' would be assigned to the created user.
OriginationConfig	ORG_DOB_AGE_LIMIT_ CHECK	Whether DOB check is local or to be done remotely. Possible values are LOCAL or REMOTE. For this setup it will be LOCAL
OriginationConfig	ORG_DOB_AGE_LIMIT	DOB Age Limit Value. In case the above property value is LOCAL, the age limit in number is to be specified for this property.
OriginationConfig	USERNAME_TYPE	Username type while registering the prospect. Possible values EMAIL/OTHERS
OriginationConfig	LIST_CANCELLATION_ DAYS	Submission Cancellation List Range. This value will be used in Report Generation for Cancelled Applications. This property indicates the number of days for which the cancellation report will be generated.
OriginationConfig	ORIG_PI_EMAIL_VERIFI CATION_REQUIRED	If Email Verification via OTP is required.
OriginationConfig	CONTENT_UPLOAD_AL LOWED_TYPE_LIST	File types allowed for document uploading. Example:- .txt,.png,.xlsx,.doc,.pdf,.jpeg,.jpg
OriginationConfig	CONTENT_UPLOAD_MI ME_TYPES_WHITE_LIS T	Allowed MIME types for file uploading. Example:- application/pdf,image/jpeg,image/png

Category Id	Property Id	Description
OriginationConfig	CONTENT_UPLOAD_MIME_TYPES_ZIP_LIST	Allowed MIME types for uploading zip document. Example:- application/x-compressed
OriginationConfig	IS_REGISTRATION_MANDATORY	This flag used to force mandatory channel registration while submitting application.
OriginationConfig	MAX_ALLOWED_VEHICLE_AGE	Maximum age allowed for vehicle in number of years
OriginationConfig	ORIGINATION_WORKFLOW_LOADER	Workflow loader configuration
OriginationConfig	VEHICLE_MILEAGE_MAX_LIMIT	Maximum mileage of used vehicle needs to be captured
OriginationConfig	VEHICLE_YEAR_MAX_LIMIT	Maximum duration of used vehicle needs to be captured

4.3 Dealer Maintenance

Dealer details can be maintained in OBDX database at table 'digx_or_dealer_details'

4.4 Social Media Integration

Please refer 'User Manual Oracle Banking Digital Experience Origination Social Media Integration.docx' document to have social media integration.

[Home](#)

5. Product Configuration

To enable the products execute the following script.

```
Update DIGX_OR_PRODUCT_TYPE set STATUS = 'ACTIVE' where ID IN ('SAVINGSH3','CHECKINGH3','AUTOLOANH3','PERSONALLOANH3') and DETERMINANT_VALUE='OBDX_BU';
```

Where 'OBDX_BU' is the entity id for which the system is configured.

This will enable the savings, current accounts, auto loans, and personal loans products.

[Home](#)

6. Admin Maintenance

6.1 Income Type maintenance

Execute the following scripts to add income type maintenance.

Where OBDX_BU is the entity id for which the FCUBS host is configured.

```
Insert into DIGX_OR_FIN_INC_TYPE (CODE, DESCRIPTION, ORDINAL,
DETERMINANT_VALUE, CREATED_BY, CREATION_DATE, LAST_UPDATED_BY,
LAST_UPDATE_DATE, OBJECT_STATUS, OBJECT_VERSION_NUMBER) values ('B',
'Business', 30, 'OBDX_BU', 'superadmin', sysdate, 'superadmin', sysdate, null, 1);
```

```
Insert into DIGX_OR_FIN_INC_TYPE (CODE, DESCRIPTION, ORDINAL,
DETERMINANT_VALUE, CREATED_BY, CREATION_DATE, LAST_UPDATED_BY,
LAST_UPDATE_DATE, OBJECT_STATUS, OBJECT_VERSION_NUMBER) values
```

```
('S', 'Salary', 10, 'OBDX_BU', 'superadmin', sysdate, 'superadmin', sysdate, null, 1);
```

```
Insert into DIGX_OR_FIN_INC_TYPE (CODE, DESCRIPTION, ORDINAL,
DETERMINANT_VALUE, CREATED_BY, CREATION_DATE, LAST_UPDATED_BY,
LAST_UPDATE_DATE, OBJECT_STATUS, OBJECT_VERSION_NUMBER) values
```

```
('R', 'Rent', 20, 'OBDX_BU', 'superadmin', sysdate, 'superadmin', sysdate, null, 1);
```

```
Insert into DIGX_OR_FIN_INC_TYPE (CODE, DESCRIPTION, ORDINAL,
DETERMINANT_VALUE, CREATED_BY, CREATION_DATE, LAST_UPDATED_BY,
LAST_UPDATE_DATE, OBJECT_STATUS, OBJECT_VERSION_NUMBER) values
```

```
('O', 'Others', 40, 'OBDX_BU', 'superadmin', sysdate, 'superadmin', sysdate, null, 1);
```

6.2 Liability Type maintenance

Execute the following scripts to add liability type maintenance.

Where OBDX_BU is the entity id for which the FCUBS host is configured.

```
Insert into DIGX_OR_FIN_LIAB_TYPE (CODE, DESCRIPTION, ORDINAL,
DETERMINANT_VALUE, CREATED_BY, CREATION_DATE, LAST_UPDATED_BY,
LAST_UPDATE_DATE, OBJECT_STATUS, OBJECT_VERSION_NUMBER) values
```

```
('E', 'Lease', 10, 'OBDX_BU', 'superadmin', sysdate, 'superadmin', sysdate, null, 1);
```

```
Insert into DIGX_OR_FIN_LIAB_TYPE (CODE, DESCRIPTION, ORDINAL,
DETERMINANT_VALUE, CREATED_BY, CREATION_DATE, LAST_UPDATED_BY,
LAST_UPDATE_DATE, OBJECT_STATUS, OBJECT_VERSION_NUMBER) values
```

```
('R', 'Rent', 20, 'OBDX_BU', 'superadmin', sysdate, 'superadmin', sysdate, null, 1);
```

```
Insert into DIGX_OR_FIN_LIAB_TYPE (CODE, DESCRIPTION, ORDINAL,
DETERMINANT_VALUE, CREATED_BY, CREATION_DATE, LAST_UPDATED_BY,
LAST_UPDATE_DATE, OBJECT_STATUS, OBJECT_VERSION_NUMBER) values
```

```
('L', 'Loan', 30, 'OBDX_BU', 'superadmin', sysdate, 'superadmin', sysdate, null, 1);
```

```

Insert into DIGX_OR_FIN_LIAB_TYPE (CODE, DESCRIPTION, ORDINAL,
DETERMINANT_VALUE, CREATED_BY, CREATION_DATE, LAST_UPDATED_BY,
LAST_UPDATE_DATE, OBJECT_STATUS, OBJECT_VERSION_NUMBER) values
('O', 'Others', 40, 'OBDX_BU', 'superadmin', sysdate, 'superadmin', sysdate, null, 1);

```

6.3 Accommodation Type maintenance

Execute the following scripts to add accommodation type maintenance.

Where OBDX_BU is the entity id for which the FCUBS host is configured.

```

Insert into DIGX_OR_ACC_TYPE (CODE, DESCRIPTION, ORDINAL,
DETERMINANT_VALUE, CREATED_BY, CREATION_DATE, LAST_UPDATED_BY,
LAST_UPDATE_DATE, OBJECT_STATUS, OBJECT_VERSION_NUMBER) values ('O',
'Other', 30, 'OBDX_BU', 'superadmin', sysdate, 'superadmin', sysdate, null, 1);

```

```

Insert into DIGX_OR_ACC_TYPE (CODE, DESCRIPTION, ORDINAL,
DETERMINANT_VALUE, CREATED_BY, CREATION_DATE, LAST_UPDATED_BY,
LAST_UPDATE_DATE, OBJECT_STATUS, OBJECT_VERSION_NUMBER) values ('S', 'Self
Owned', 20, 'OBDX_BU', 'superadmin', sysdate, 'superadmin', sysdate, null, 1);

```

```

Insert into DIGX_OR_ACC_TYPE (CODE, DESCRIPTION, ORDINAL,
DETERMINANT_VALUE, CREATED_BY, CREATION_DATE, LAST_UPDATED_BY,
LAST_UPDATE_DATE, OBJECT_STATUS, OBJECT_VERSION_NUMBER) values
('C', 'Company Provided', 10, 'OBDX_BU', 'superadmin', sysdate, 'superadmin', sysdate, null,
1);

```

6.4 Financial Parameters maintenance

```

Insert into DIGX_OR_FINANCIAL_PARAMETERS
(CODE,DETERMINANT_VALUE,DESCRIPTION,FIN_PARAM_TYPE,ORDINAL,PRODUCT_
SUB_CLASS) values ('RT','OBDX_BU','Rent','Expense',10,'PERSONAL_LOAN');

```

```

Insert into DIGX_OR_FINANCIAL_PARAMETERS
(CODE,DETERMINANT_VALUE,DESCRIPTION,FIN_PARAM_TYPE,ORDINAL,PRODUCT_
SUB_CLASS) values ('FD','OBDX_BU','Food','Expense',20,'PERSONAL_LOAN');

```

```

Insert into DIGX_OR_FINANCIAL_PARAMETERS
(CODE,DETERMINANT_VALUE,DESCRIPTION,FIN_PARAM_TYPE,ORDINAL,PRODUCT_
SUB_CLASS) values ('TR','OBDX_BU','Transport','Expense',40,'PERSONAL_LOAN');

```

```

Insert into DIGX_OR_FINANCIAL_PARAMETERS
(CODE,DETERMINANT_VALUE,DESCRIPTION,FIN_PARAM_TYPE,ORDINAL,PRODUCT_
SUB_CLASS) values ('HC','OBDX_BU','Healthcare','Expense',50,'PERSONAL_LOAN');

```

```

Insert into DIGX_OR_FINANCIAL_PARAMETERS
(CODE,DETERMINANT_VALUE,DESCRIPTION,FIN_PARAM_TYPE,ORDINAL,PRODUCT_
SUB_CLASS) values ('CH','OBDX_BU','Childcare','Expense',70,'PERSONAL_LOAN');

```

```

Insert into DIGX_OR_FINANCIAL_PARAMETERS
(CODE,DETERMINANT_VALUE,DESCRIPTION,FIN_PARAM_TYPE,ORDINAL,PRODUCT_
SUB_CLASS) values ('EDU','OBDX_BU','Education','Expense',80,'PERSONAL_LOAN');

```

```

Insert into DIGX_OR_FINANCIAL_PARAMETERS
(CODE,DETERMINANT_VALUE,DESCRIPTION,FIN_PARAM_TYPE,ORDINAL,PRODUCT_
SUB_CLASS) values ('OTH','OBDX_BU','Other','Expense',90,'PERSONAL_LOAN');

```

```
Insert into DIGX_OR_FINANCIAL_PARAMETERS  
(CODE,DETERMINANT_VALUE,DESCRIPTION,FIN_PARAM_TYPE,ORDINAL,PRODUCT_  
SUB_CLASS) values ('LN','OBDX_BU','Loan','Liability',10,'PERSONAL_LOAN');
```

```
Insert into DIGX_OR_FINANCIAL_PARAMETERS  
(CODE,DETERMINANT_VALUE,DESCRIPTION,FIN_PARAM_TYPE,ORDINAL,PRODUCT_  
SUB_CLASS) values ('LS','OBDX_BU','Lease','Liability',20,'PERSONAL_LOAN');
```

```
Insert into DIGX_OR_FINANCIAL_PARAMETERS  
(CODE,DETERMINANT_VALUE,DESCRIPTION,FIN_PARAM_TYPE,ORDINAL,PRODUCT_  
SUB_CLASS) values ('OTH','OBDX_BU','Other','Liability',40,'PERSONAL_LOAN');
```

```
Insert into DIGX_OR_FINANCIAL_PARAMETERS  
(CODE,DETERMINANT_VALUE,DESCRIPTION,FIN_PARAM_TYPE,ORDINAL,PRODUCT_  
SUB_CLASS) values ('EM','OBDX_BU','Salary','Income',10,'PERSONAL_LOAN');
```

```
Insert into DIGX_OR_FINANCIAL_PARAMETERS  
(CODE,DETERMINANT_VALUE,DESCRIPTION,FIN_PARAM_TYPE,ORDINAL,PRODUCT_  
SUB_CLASS) values ('RE','OBDX_BU','Rental Income','Income',20,'PERSONAL_LOAN');
```

```
Insert into DIGX_OR_FINANCIAL_PARAMETERS  
(CODE,DETERMINANT_VALUE,DESCRIPTION,FIN_PARAM_TYPE,ORDINAL,PRODUCT_  
SUB_CLASS) values ('EM','OBDX_BU','Salary','Income',10,'AUTOMOBILE');
```

```
Insert into DIGX_OR_FINANCIAL_PARAMETERS  
(CODE,DETERMINANT_VALUE,DESCRIPTION,FIN_PARAM_TYPE,ORDINAL,PRODUCT_  
SUB_CLASS) values ('RE','OBDX_BU','Rental Income','Income',20,'AUTOMOBILE');
```

```
Insert into DIGX_OR_FINANCIAL_PARAMETERS  
(CODE,DETERMINANT_VALUE,DESCRIPTION,FIN_PARAM_TYPE,ORDINAL,PRODUCT_  
SUB_CLASS) values ('RT','OBDX_BU','Rent','Expense',10,'AUTOMOBILE');
```

```
Insert into DIGX_OR_FINANCIAL_PARAMETERS  
(CODE,DETERMINANT_VALUE,DESCRIPTION,FIN_PARAM_TYPE,ORDINAL,PRODUCT_  
SUB_CLASS) values ('FD','OBDX_BU','Food','Expense',20,'AUTOMOBILE');
```

```
Insert into DIGX_OR_FINANCIAL_PARAMETERS  
(CODE,DETERMINANT_VALUE,DESCRIPTION,FIN_PARAM_TYPE,ORDINAL,PRODUCT_  
SUB_CLASS) values ('TR','OBDX_BU','Transport','Expense',40,'AUTOMOBILE');
```

```
Insert into DIGX_OR_FINANCIAL_PARAMETERS  
(CODE,DETERMINANT_VALUE,DESCRIPTION,FIN_PARAM_TYPE,ORDINAL,PRODUCT_  
SUB_CLASS) values ('HC','OBDX_BU','Healthcare','Expense',50,'AUTOMOBILE');
```

```
Insert into DIGX_OR_FINANCIAL_PARAMETERS  
(CODE,DETERMINANT_VALUE,DESCRIPTION,FIN_PARAM_TYPE,ORDINAL,PRODUCT_  
SUB_CLASS) values ('CH','OBDX_BU','Childcare','Expense',70,'AUTOMOBILE');
```

```
Insert into DIGX_OR_FINANCIAL_PARAMETERS  
(CODE,DETERMINANT_VALUE,DESCRIPTION,FIN_PARAM_TYPE,ORDINAL,PRODUCT_  
SUB_CLASS) values ('EDU','OBDX_BU','Education','Expense',80,'AUTOMOBILE');
```

```
Insert into DIGX_OR_FINANCIAL_PARAMETERS  
(CODE,DETERMINANT_VALUE,DESCRIPTION,FIN_PARAM_TYPE,ORDINAL,PRODUCT_  
SUB_CLASS) values ('OTH','OBDX_BU','Other','Expense',90,'AUTOMOBILE');
```

```
Insert into DIGX_OR_FINANCIAL_PARAMETERS  
(CODE,DETERMINANT_VALUE,DESCRIPTION,FIN_PARAM_TYPE,ORDINAL,PRODUCT_  
SUB_CLASS) values ('LN','OBDX_BU','Loan','Liability',10,'AUTOMOBILE');
```

```
Insert into DIGX_OR_FINANCIAL_PARAMETERS  
(CODE,DETERMINANT_VALUE,DESCRIPTION,FIN_PARAM_TYPE,ORDINAL,PRODUCT_  
SUB_CLASS) values ('LS','OBDX_BU','Lease','Liability',20,'AUTOMOBILE');
```

```
Insert into DIGX_OR_FINANCIAL_PARAMETERS  
(CODE,DETERMINANT_VALUE,DESCRIPTION,FIN_PARAM_TYPE,ORDINAL,PRODUCT_  
SUB_CLASS) values ('OTH','OBDX_BU','Other','Liability',40,'AUTOMOBILE');
```

```
Insert into DIGX_OR_FINANCIAL_PARAMETERS  
(CODE,DETERMINANT_VALUE,DESCRIPTION,FIN_PARAM_TYPE,ORDINAL,PRODUCT_  
SUB_CLASS) values ('L','OBDX_BU','Land','Assets',10,'PERSONAL_LOAN');
```

```
Insert into DIGX_OR_FINANCIAL_PARAMETERS  
(CODE,DETERMINANT_VALUE,DESCRIPTION,FIN_PARAM_TYPE,ORDINAL,PRODUCT_  
SUB_CLASS) values ('P','OBDX_BU','Property','Assets',20,'PERSONAL_LOAN');
```

```
Insert into DIGX_OR_FINANCIAL_PARAMETERS  
(CODE,DETERMINANT_VALUE,DESCRIPTION,FIN_PARAM_TYPE,ORDINAL,PRODUCT_  
SUB_CLASS) values ('L','OBDX_BU','Land','Assets',10,'AUTOMOBILE');
```

```
Insert into DIGX_OR_FINANCIAL_PARAMETERS  
(CODE,DETERMINANT_VALUE,DESCRIPTION,FIN_PARAM_TYPE,ORDINAL,PRODUCT_  
SUB_CLASS) values ('P','OBDX_BU','Property','Assets',20,'AUTOMOBILE');
```

[Home](#)