

Oracle Financial Services Investigation Hub

Administration and Configuration Guide

Release 8.0.7.4.0

April 2020

F28095-01

ORACLE
Financial Services

Oracle Financial Services Investigation Hub Administration and Configuration Guide

Copyright © 2020 Oracle and/or its affiliates. All rights reserved.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are “commercial computer software” pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

For information on third party licenses, click [here](#).

Document Control

Table 1: Document Control

Version Number	Revision Date	Changes Done
8.0.7.4.0	Updated: April 2020	The Investigation Hub application is integrated with the ECM application to investigate the ECM cases using Investigation Hub. For more information, see Integrating Investigation Hub with ECM
8.0.7.3.0	Created: March 2020	Created the first version of the Investigation Hub Administration Guide for 8.0.7.3.0 Release.

This document provides functional information about the Investigation Hub application and enables you to navigate through the various sections of the application. The latest copy of this guide can be accessed from the Oracle Help Center ([OHC](#)) Documentation Library.

Table of Contents

1	About this Guide	5
1.1	Who Should Use This Guide	5
1.2	Scope of This Guide	5
1.3	How this Guide is Organized	5
1.4	Where to Find More Information	5
1.5	Conventions Used in this Guide	6
1.6	Abbreviations Used in this Guide	6
2	About Oracle Financial Services Investigation Hub	7
2.1	Introduction	7
2.1.1	<i>Key Features</i>	7
2.2	Administration and Configuration Activities	7
2.3	Providing Permissions to a Notebook	8
3	Managing User Administration	10
3.1	Managing Identity and Authorization	10
3.1.1	<i>Identity and Authorization Process</i>	10
3.1.2	<i>Creating and Authorizing User</i>	10
3.2	Granting Permissions	11
4	Configuring the Notebook Parameters	12
4.1	Configuring the Investigation Recommendation Score	12
4.2	Configuring the Red Flag	13
4.3	Configuring the Risk Factors	14
4.4	Configuring the Network Disposition Score	15
4.5	Adding a New Search Criteria	16
5	Integrating Investigation Hub with ECM	17
5.1	Prerequisites	17
5.2	Updating the Database Tables in ECM	17
5.3	Mapping IH Entity/Tab in ECM Case Designer	19
6	Additional Configuration	20
6.1	Configuring Interpreters	20
6.2	Managing Graphs.....	20

6.3	Managing Templates	20
7	Appendix - Generating Correlation Networks	21
8	Appendix - API for Running All Paragraphs.....	22
9	OFSAA Support Contact Details	23
10	Send Us Your Comments.....	24

1 About this Guide

This guide gives comprehensive instructions for system administration, daily operations, and maintenance of Oracle Financial Services Investigation Hub application.

Topics:

- [Who Should Use This Guide](#)
- [Scope of This Guide](#)
- [How this Guide is Organized](#)
- [Where to Find More Information](#)
- [Conventions Used in this Guide](#)
- [Abbreviations Used in this Guide](#)

1.1 Who Should Use This Guide

This guide is intended for administrators and implementation consultants. Their roles and responsibilities, as they operate within Investigation Hub, include the following:

- **Implementation Consultant:** Installs and configures the Investigation Hub application at a deployment site. The consultant also installs and upgrades any additional Oracle Financial Services solution sets, and requires access to deployment-specific configuration information. For example, machine names and port numbers.
- **System Administrator:** Configures and maintains the system. The System Administrator maintains user accounts and roles, monitors data management, archives data, loads data feeds, and performs post-processing tasks. Also, the System Administrator reloads the cache.

1.2 Scope of This Guide

This guide describes the physical and logical architecture of the Investigation Hub application. It also provides instructions for maintaining and configuring Investigation Hub, its subsystem components, and any third-party software required for operations.

1.3 How this Guide is Organized

The Administration Guide includes the following chapters:

- [About Oracle Financial Services Investigation Hub](#) provides a brief overview of the Investigation Hub and its components.
- [Managing User Administration](#) provides details about user roles.
- [Configuring the Notebook Parameters](#) describes the configurable notebook parameters.
- [Additional Configuration](#) details the additional configurations.

1.4 Where to Find More Information

This section identifies additional documents related to the Investigation Hub application. You can access the following documents from the Oracle Help Center (OHC) Documentation Library:

- *Oracle Financial Services Investigation Hub Release Notes Guide*
- *Oracle Financial Services Investigation Hub Installation Guide*

- *Oracle Financial Services Investigation Hub User Guide*

1.5 Conventions Used in this Guide

Conventions used in this guide and their associated meanings are listed in the following table.

Table 1: Conventions Used in this Guide

Convention	Meaning
Boldface	Boldface type indicates graphical user interface elements associated with an action (menu names, field names, options, button names) or terms defined in text or glossary.
<i>Italic</i>	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.
monospace	Monospace type indicates the following: <ul style="list-style-type: none"> • Directories and subdirectories • File names and extensions • Process names • Code sample, that includes keywords, variables, and user-defined program elements within the text
<variable>	Substitute input value

1.6 Abbreviations Used in this Guide

The following abbreviations are used in this guide.

Table 2: Abbreviations and Their Meaning

Abbreviation	Meaning
OFS	Oracle Financial Services
T2T	Table to Table
AAI	Analytical Applications Infrastructure
PGX	Parallel Graph AnalytiX
PGQL	Property Graph Query Language
LHS	Left Hand Side
IH	Investigation Hub

2 About Oracle Financial Services Investigation Hub

This chapter provides a brief overview of the Oracle Financial Services Investigation Hub (OFS IH) application.

Topics:

- [Introduction](#)
- [Administration and Configuration Activities](#)
- [Providing Permissions to a Notebook](#)

2.1 Introduction

Oracle Financial Services Crime and Compliance Investigation Hub is an application built on FCC Studio which allows investigators to rapidly view the case and Adhoc information within the Financial Crime and Compliance Graph. The in-built scoring, matching, and correlation engines create meaningful units of investigation, and pre-configured red flags and risk factors target investigative effort effectively. The Financial Crime and Compliance Graph on which it is built accelerates investigations by bringing relevant information sources together, preventing the need for the manual collation of information from disparate sources for ad hoc investigations. Oracle Financial Services Crime and Compliance Investigation automatically generate case narratives and insights, highlights risk factors, and red flags which are meaningful to the investigation and recommend actions based on graph scoring algorithms.

2.1.1 Key Features

- Pre-built user interfaces for case investigation, special and Adhoc investigations, and sanctions.
- Configurable red flags and risk factors to highlight key areas for investigation.
- Case summary in narrative format and case recommendation.
- In-built correlation and scoring algorithms.
- Exploration of the financial crimes global-graph using an interactive and visual graph explorer tool.
- Integrates fully with Oracle Financial Crimes Application Data and external data sources such as watchlist and company hierarchy data and is readily usable across the Enterprise Financial Crimes data lake.
- Built on Oracle Financial Service Crime and Compliance Studio which includes a highly scalable in-memory Oracle Graph Analytics Engine (PGX), AI, and machine learning.
- Utilizes proven Enterprise Financial Crimes Graph model which accelerates financial crime investigation use cases.

2.2 Administration and Configuration Activities

An administrator should configure the following Notebooks:

- **Special Investigation:** Enables the investigator to search for one or multiple names and/or addresses to examine the network, red flags, and risk factors
- **Level 2 Case Investigations:** Allows the investigator to explore a case - including graph, risk factors, and red flags.

- **ECM Integration:** Enable Case Investigators to access additional rich information about a case such as, case summary, a detailed narrative about case entities, graph view of a case, and so on, which is otherwise not available in ECM.

NOTE

Administrator must share only the **Special Investigation** notebook to users (investigators) and users will clone the notebook for their investigation.

Adminstrator loads the graph into memory and publishes it so other notebooks can access and use it.


2.3 Providing Permissions to a Notebook

The Share button allows you to share a notebook with another user, user group, or role. This option helps you to provide the permission of a notebook to a specific user.


For more information on permissions, see the [Oracle Financial Services Crime and Compliance Studio Administration and Configuration Guide](#).

To share a note, perform the following steps:

1. Navigate to Investigation Hub application home page.
2. Navigate to any notebook of application.
3. Click **Share**.



4. Click **Add** icon.



5. Select the required permissions and click Save.

After sharing the notebook, an Investigator must clone the notebook and start using that notebook for investigation. For more information, see the Cloning of Notebook in the *Oracle Financial Services Investigation Hub User Guide*.

3 Managing User Administration

This chapter provides information about creating users who can access the Investigation Hub application and execute batches required for Investigation Hub. You must create users and execute batches in the OFSAA environment.

User administration involves creating and managing users and providing access to Investigation Hub based on assigned roles.

Topics:

- [Managing Identity and Authorization](#)
- [Granting Permissions](#)

3.1 Managing Identity and Authorization

This section provides information on creating, mapping, and authorizing users, and providing access to the Investigation Hub application.

Topics:

- [Identity and Authorization Process](#)
- [Creating and Authorizing User](#)

3.1.1 Identity and Authorization Process

The following figure shows the process flow of identity management and authorization.




Table 3 lists the various actions involved in the user administration process flow:

Table 1: User Administration Process Flow

Action	Description
Creating and Authorizing User	Create a user by providing the user name, user designation, and the date during which the user is active in Investigation Hub.
Mapping user with user group	Map the user with a user group that provides the user with the privileges of the mapped user group.

3.1.2 Creating and Authorizing User

Users with SYSADMN and SYSAUTH functional roles can create and authorize users in Investigation Hub, respectively. For more information on creating and authorizing users, see the *Oracle Financial Services Analytical Applications Infrastructure User Guide*.

3.2 Granting Permissions

To grant permission, follow these steps:

1. Log in to Oracle Database from sys as a SYSDBA user.
2. Execute the following command:

```
grant execute dbms_ols to <Studio DB Username>
```

The Execute permission is granted to VPD.

3. Execute the following command:

```
grant create any context to <STUDIO_DB_USER_NAME>;
```

The Create permission is granted to context.

4 Configuring the Notebook Parameters

This chapter provides information on configuring the notebook parameters for the following seeded notebooks of the Investigation Hub application:

- Special Investigation Notebook
- Level 1 Case Investigation
- Level 2 Case Investigation

NOTE: In an Investigation Hub notebook, the graph is lost whenever a session is reset and this occurs as part of the session clean-up. You must execute the Graph_Alive notebook to retain the link to the graph even when a session is reset. For more information, see the *Appendix - Executing Graph_Alive Notebook* in the *Oracle Financial Services Crime and Compliance Studio Installation and Configuration Guide*.

Topics:

- [Configuring the Investigation Recommendation Score](#)
- [Configuring the Red Flag](#)
- [Configuring the Risk Factors](#)
- [Configuring the Network Disposition Score](#)
- [Adding a New Search Criteria](#)

4.1 Configuring the Investigation Recommendation Score

Scoring is a methodology to calculate the score of events, correlation, and entity (for example, customer). You can define the score range based on which a case can be recommended for investigation. The investigation recommendation will be displayed in the **Recommendation** paragraph of the **Special Investigation** notebook.

For example:

If you have defined the investigation score range as 10-25 and case status as “Further Investigation”, then the case investigation recommendation will be set to “Further Investigation” when a case score falls in the 10-25 range.

To define the investigation recommendation, follow these steps:

1. Click the **Investigation Hub** folder.
2. Navigate to the **Special Investigation** notebook.
3. Open the codes of **Initialization - I** paragraph and edit it as required. The following figure shows an example.

```
public String get_recommendation(int case_disp_system, int case_disp_analyst, int red_flags, int risk_factors, int external_data, int internal_data, boolean initial) {
    String color = "seagreen";
    String ret = "Close Case (Reason: False Positive)";

    int disposition_score = (case_disp_analyst > 0 ? case_disp_analyst : case_disp_system);

    // TODO: Improve case recommendation logic
    if (disposition_score > 25 && disposition_score < 51) {
        ret = "Unknown - Further Investigation Needed";
        color = "gold";
    } else if (disposition_score > 50 && disposition_score < 76) {
        ret = "Special Investigation Needed";
        color = "darkorange";
    } else if (disposition_score > 76) {
        ret = "Consider Escalation";
        color = "crimson";
    }
}
```

4. Execute the paragraph.

An Investigator can view the investigation status based on this recommendation scoring.

4.2 Configuring the Red Flag

The Red Flag indicator suggests a potential problem with a business entity. When you see a red flag indication, you must view the investigation recommendation and take the appropriate action. The Red Flag details will be displayed on the **Red Flag** paragraph of the **Special Investigation** notebook. An Investigator can view these details during the investigation process.

To configure the Red Flag indicator, follow these steps:

1. Navigate to the **Special Investigation** notebook.
2. Open the codes of **Initialization - I** paragraph notebook. The following figure shows an example.

```
/*
 * RED FLAGS
 */
/*Red Flags:
1. *Count of entities with SARs filed related to FRTH*: Property status on event = SAR
2. *Entities who are Oligarchs and political figures*: isPep = true and list = SDN
3. *Shell companies owned/controlled by a Russian UBODs*: source = BvD (for now Panama Papers), edge from company to individual to where address.country = RU*/
Workload<Long> sar_wl = new Workload<> (
    "select count(*) match (v) where v.Status = 'SAR' and %s",
    singlevertex,
    get_long_scala
);
Workload<List<String>> sar_list_wl = new Workload<> (
    "select v.Name match (v) where v.Status = 'SAR' and %s",
    singlevertex,
    get_string_list
);
Workload<Long> oligarchs_and_political_figures_wl = new Workload<> (
    "select count(*) match (v) where java_regexp_like(v.\"Is PEP\", 'PEP') or java_regexp_like(v.List, 'sar') and %s",
    singlevertex,
    get_long_scala
);
Workload<List<String>> oligarchs_and_political_figures_list_wl = new Workload<> (
    "select v.Name match (v) where java_regexp_like(v.\"Is PEP\", 'PEP') or java_regexp_like(v.List, 'sar') and %s",
    singlevertex,
    get_string_list
);
Workload<Long> ru_ubo_wl = new Workload<> (
    "select count(*)
+ \"match (v) -[e1]- (external) -[e2]- (ubo) -[e3]- (address) \"
+ \"where e1.Label = 'match name' and external.Label = 'External Source' and e3.Label = 'address of' and address.Country = 'RU' and external.Source = 'BvD' and %s\",
    singlevertex,
    get_long_scala
);
Workload<List<String>> ru_ubo_list_wl = new Workload<> (
```

3. If required, edit the codes to add a query for the red flag parameter and execute the paragraph.
4. Navigate to the Red Flags paragraph.

Red Flags

```

#pgx-java
Map<String, Workload<Long>> red_flag_workloads = new HashMap<>() {{
    put("Entities with SARs filed related to FRTH", sar_wl);
    put("Entities who are Oligarchs or political figures", oligarchs_and_political_figures_wl);
    put("Shell companies owned/controlled by Russian UBOs", ru_ubo_wl);
    put("Transactions with payer in risky country and beneficiary in tax haven", transaction_wl);
    put("Accounts interacting with sanctioned Russian banks and entities", interaction_sanctioned_ru_banks_wl);
}};

out.println(get_table(resultgraph, red_flag_workloads, "Red Flags"));
    
```

Type to search

Red Flags	Hits (Initial)	Hits (Investigator)
Shell companies owned/controlled by Russian UBOs	0	0
Entities with SARs filed related to FRTH	0	0
Entities who are Oligarchs or political figures	0	0
Transactions with payer in risky country and beneficiary in tax haven	0	0
Accounts interacting with sanctioned Russian banks and entities	0	0

Page 1 of 1 (1-5 of 5 items) | K < 1 > X

5. Enter the Red Flag names (for example, "Accounts interacting with sanctioned Russian banks and entities") and the query details. This query name should be the same as given in the **Initialization - I** paragraph. This is used for calling the red flag query defined in **Initialization - I** paragraph.

4.3 Configuring the Risk Factors

You can configure the risk factor of a business entity. The risk factor can lower organization profits or lead it to fail. Based on risk factor details, you should view the investigation recommendation and take the appropriate action. The risk factor details will be displayed on the Risk Factors paragraph of the Special Investigation notebook.

To configure the risk factors, follow these steps:

1. Navigate to the **Special Investigation** notebook.
2. Open the codes of the **Initialization - I** paragraph notebook. The following figure shows an example.

```

/*****
 * RISK FACTORS
 *****/
// count number of high risk countries (>3) in case -- update this w/ udf
Workload<Long> country_risk_w1 = new Workload<> (
    "select count(distinct v) match (v) <-[e]- (v2) where "
    + "(v2.Country = 'RU' or v2.Country = 'CY' or v2.Country = 'EE' or java_regexp_like(v2.Country, 'IVOIRE')) and "
    + "(e.Label = 'address of' or e.Label = 'match name') and %s",
    singleVertex,
    get_long_scala
);
// Count where list = regex SDN
Workload<Long> sanction_hit_risk_w1 = new Workload<> (
    "select count(*) match (v) where java_regexp_like(v.List, 'sdn') and %s",
    singleVertex,
    get_long_scala
);
Workload<List<String>> sanction_hit_risk_list_w1 = new Workload<> (
    "select v.Name match (v) where java_regexp_like(v.List, 'sdn') and %s",
    singleVertex,
    get_string_list
);
Workload<Long> terrorism_risk_w1 = new Workload<> (
    "select count(*) match (v) where v.Category = 'TERRORISM' and %s",
    singleVertex,
    get_long_scala
);
Workload<List<String>> terrorism_risk_list_w1 = new Workload<> (
    "select v.Name match (v) where v.Label = 'Customer' and v.Category = 'TERRORISM' and %s",
    singleVertex,
    get_string_list
);
Workload<Long> prohibited_business_risk_w1 = new Workload<> (
    "select count(*) match (v) where v.\"Customer Type\" = 'IND' and (v.Industry = 'NAVY' or v.Industry = 'WHL') and %s",
    singleVertex,
    get_long_scala
);

```

3. If required, edit the codes to add a query for the risk factors parameter and execute the paragraph.
4. Navigate to the Risk Factors paragraph.

Risk Factors

```

%%gx -java
Map<String, Workload<Long>> high_risk_workloads = new HashMap<>() {{
    put("Country/Region Hits", country_risk_w1);
    put("Sanction Hits", sanction_hit_risk_w1);
    put("Terrorism List Match", terrorism_risk_w1);
    put("Prohibited Business List Match", prohibited_business_risk_w1);
    put("High Risk Transaction Present", high_risk_transaction_w1);
    put("Political Exposed Figures", pep_w1);
}};

out.println(get_table(resultGraph, high_risk_workloads, "Risk Factors"));

```

Type to search

Risk Factors	Hits (Initial)	Hits (Investigator)
Country/Region Hits	0	0
Political Exposed Figures	0	0
Prohibited Business List Match	0	0
Sanction Hits	0	0
Terrorism List Match	0	0
High Risk Transaction Present	0	0

Page 1 of 1 (1-6 of 6 items) | < 1 >

5. Enter the Risk Factor names (for example, "Sanction Hits") and the query details. This query name should be the same as mentioned in the **Initialization - I** paragraph. This is used for calling the risk factor query defined in **Initialization - I** paragraph.

4.4 Configuring the Network Disposition Score

Network disposition is calculated using the following formula:

Sum of Node Risk/Node Count

To configure the Network Disposition Score, follow these steps:

1. Navigate to the **Special Investigation** notebook.
2. Open the codes of the **Initialization - I** paragraph notebook.

```

public int get_disp_score(boolean isSystemScore){
    int cond = isSystemScore ? CASE_ID_COND : VISIBLE_GRAPH_COND;

    float disposition_score = 0;
    try {
        PgsqlResultSet rs = prep_and_run_query(global_graph, "select sum(v.Risk) match (v) where %s", singlevertex, cond);
        rs.next();
        float node_risk = rs.getFloat(1);
        rs.close();

        rs = prep_and_run_query(global_graph, "select sum(e.\"Activity Risk\") match (v1)-[e]->(v2) where %s and %s", twovertices, cond);
        rs.next();
        float edge_risk = rs.getFloat(1);
        //edge_risk = 0
        rs.close();

        rs = prep_and_run_query(global_graph, "select count(v) match (v) where v.Label = 'Event' and %s", singlevertex, cond);
        rs.next();
        float event_count = rs.getFloat(1) * 5;
        rs.close();

        rs = prep_and_run_query(global_graph, "select count(v) match (v) where v.Label = 'External Entity' and java_regexp_like(v.Source, '\" + negative_external_sources_regex + '\" and %s",
        rs.next();
        float bad_external_entities_count = rs.getFloat(1) * 10;
        rs.close();

        disposition_score = node_risk + edge_risk + event_count + bad_external_entities_count;
    } catch (PgsqlException e) {
        // TODO error msg
        out.println("Something went wrong.");
    }
}

```

3. If required, edit the codes and execute the paragraph.

4.5 Adding a New Search Criteria

The default search criteria available to search a business entity are Tax ID, Name, Address, and Date.

You can add new search criteria. For example, if you want to add customer DOB as a new search criterion, use the following format:

```
givenDOB = "@{Date=}"
```

To add a new search criterion, follow these steps:

1. Navigate to the **Special Investigation** notebook.
2. Open the codes of the **Input Search Results** paragraph notebook.

```

Input Search Results

@pgx-java
import java.net.*;
import java.util.*;

public String cleanString(String input) {
    return input.replaceAll("[\r|\n|\\t|'", "");
}

String givenTaxId = cleanString("${Tax ID}");
String givenName = cleanString("${Name}");
String givenAddress = cleanString("${Address}");
String givenDate = "${date(M/d/yyyy)}Date";
String useDate = "${useDate(Use date)=yes,yes(Yes)}no(No)";
String actualDate = useDate.equals("yes") ? givenDate : "";
String givenEmptyList = "${givenEmptyList(Empty the existing entities list)=no,yes(Yes)}no(No)";
String searchType = "${searchType(searchType)=fuzzy,fuzzy(fuzzy)}exact(exact)";
String searchMethod = "${searchMethod(searchMethod)=jarowinkler,jarowinkler(jarowinkler)}default(default)";
String overallThreshold = "0.0";

List<SearchEntry> blacklist;
if (blacklist == null || givenEmptyList.equals("yes")) {
    blacklist = new ArrayList<SearchEntry>();
}

if (!givenTaxId.isEmpty() || !givenName.isEmpty() || !givenAddress.isEmpty() || !actualDate.isEmpty()) {
    SearchEntry newEntry = new SearchEntry(givenTaxId, givenName, givenAddress, actualDate);
    blacklist.add(newEntry);

    String blacklistContent = "Tax ID\\Name\\Address\\Date\\n";
    for (SearchEntry entry : blacklist) {
        blacklistContent += entry.toString() + "\\n";
    }

    out.println(blacklistContent);
} else {
    out.println("<p>Please enter at least one of the following: Tax ID, name, address, or date.</p>");
}

```

3. If required, edit the codes and execute the paragraph.

5 Integrating Investigation Hub with ECM

Investigation Hub (IH) is integrated with Enterprise Case Management (ECM) to enable Case Investigators to access additional rich information about a case such as, case summary, a detailed narrative about case entities, graph view of a case, and so on, which is otherwise not available in ECM.

Topics:

- [Prerequisites](#)
- [Updating the Database Tables in ECM](#)
- [Mapping IH Entity/Tab in ECM Case Designer](#)

5.1 Prerequisites

Download and apply the patch **31185239** on the Oracle Financial Services Enterprise Case Management 8.0.8.0.0 application. For more information, see the Readme file packaged with the `OFS_ECM_8.0.8.0.4` Patch Installer Archive File.

5.2 Updating the Database Tables in ECM

Update the following database tables in ECM by replacing the placeholders with the user-specified values to integrate IH with ECM.

- Replace the following placeholders in the FCC_CM_STUDIO Table as follows:

Table 1: FCC_CM_STUDIO Table

Placeholder	Description
##URL##	Replace the placeholder with the FCC Studio URL. For example: http://<Host_Name>:7008
##SSOHEADER##	Replace the placeholder with the SSOHEADER to access FCC Studio For example: oam_remote_user NOTE: If SSO is enabled for Studio and ECM, ensure to replace the ##SSOHEADER## placeholder value with the relevant SSOHEADER, and provide null for ##PASSWORD##.

- Replace the placeholders in the FCC_CM_CTYPE_NB_MAPPING Table as follows:
 - Replace the placeholder values in the existing entries in the table to provide access to the Investigation Hub tab in ECM to the default out-of-the-box ECM user roles, CMANALYST1, CMANALYST2, and CMSUPRVISR.

Table 2: FCC_CM_CTYPE_NB_MAPPING Table

Placeholder	Description
For the ECM user roles: CMANALYST1 and CMANALYST2	

Table 2: FCC_CM_CTYPE_NB_MAPPING Table

Placeholder	Description
##CASE_TYPE##	Replace the placeholder with the case type for which you want to enable the IH tab. For example: AML_SURV
##notebookId##	Replace the placeholder with the notebook ID of the IH notebook that must be cloned for all the cases of the specified case type. NOTE: You must provide the notebook ID of the ECM_Integration_L1 notebook for the Analyst role.
For the ECM user role: CMSUPRVISR	
##CASE_TYPE##	Replace the placeholder with the case type for which you want to enable the IH tab. For example: AML_SURV
##notebookId##	Replace the placeholder with the notebook ID of the IH notebook that must be cloned for all the cases of the specified case type. NOTE: You must provide the Notebook ID of the ECM_Integration_L2 notebook for the Supervisor role.

- You can modify the permissions granted to a user role by changing the default assigned values, 'Y' or 'N' in the FCC_CM_CTYPE_NB_MAPPING table. By modifying the permission, you can restrict the actions that a user role can perform in the Investigation Hub tab.

Table 3: FCC_CM_CTYPE_NB_MAPPING Table

Table Entry	Description
V_NB_TOOLBAR	<ul style="list-style-type: none"> • 'Y' indicates to grant permission to the user role for the actions that can be performed on a notebook such as Publish Notebook, Clear Result, Share Notebook, and so on • 'N' indicates to deny the permission.
V_ADD_PARA	<ul style="list-style-type: none"> • 'Y' indicates to grant permission to the user role to add new paragraphs to a notebook. • 'N' indicates to deny the permission. The Interpreter toolbar is not visible for the user.
V_PARA_ACTIONS	<ul style="list-style-type: none"> • 'Y' indicates to grant permission to the user role for the actions that can be performed in a paragraph such as Execute Paragraph, Enter Dependency Mode, Comment, and so on. • 'N' indicates to deny the permission.

Table 3: FCC_CM_CTYPE_NB_MAPPING Table

Table Entry	Description
V_PARA_CODE	<ul style="list-style-type: none"> • 'Y' indicates to grant permission to the user role to view the paragraph code in the IH notebook. • 'N' indicates to deny the permission.

- To add a new user role who needs access to the Investigation Hub tab in ECM, you must insert new entries for that user role, case type, and notebook ID in the FCC_CM_CTYPE_NB_MAPPING table as follows:

```

— Insert into FCC_CM_CTYPE_NB_MAPPING (V_USERROLE,V_CASE-
TYPE,V_NOTEBOOK_ID,V_CREATED_DATE,V_CREATED_BY,V_UPDATED_BY,V_UP-
DATED_DATE,V_NB_TOOLBAR,V_ADD_PARA,V_PARA_ACTIONS,V_PARA_CODE)
values ('<User_Role>', '##CASE_TYPE##', '##note-
bookId##', null, null, null, null, 'Y/N', 'Y/N', 'Y/N', 'Y/N')

```

5.3 Mapping IH Entity/Tab in ECM Case Designer

Using the Case Designer component in ECM, you must add the "Investigation Hub" entity to the Case Type for which you want the Investigation Hub tab to be enabled. For more information, see *Adding Optional Entities to the Case Type* section in the *Managing Case Designer* chapter in the *OFS Enterprise Case Management Administration Guide*.

6 Additional Configuration

This chapter provides information about additional configuration for Investigation Hub.

Topics:

- [Configuring Interpreters](#)
- [Managing Graphs](#)
- [Managing Templates](#)

6.1 Configuring Interpreters

An interpreter is a program that directly reads and executes the instructions written in a programming or scripting language without previously compiling the high-level language code into a machine language program.

Interpreters supported by Investigation Hub are PGX, PGQL, OFSAA Interpreter, OFSAA SQL Interpreter, Markdown, and so on.

For more information, see the Configuring Interpreters section in the *Oracle Financial Services Crime and Compliance Studio Administration and Configuration Guide*.

6.2 Managing Graphs

You can view the graphs that are created using Investigation Hub data in the Investigation Hub interface.

To create custom graphs, you must manually configure the Data Store. For more information on configuring graphs, see the *Oracle Financial Services Crime and Compliance Studio Administration and Configuration Guide*.

6.3 Managing Templates

Investigation Hub offers various formats using which you can view the result after the execution of a paragraph. Templates enable you to define parameters and use these parameters to customize the result formats. You can customize the visualization of the result by defining parameters in a template and then applying the template to a Notebook. The customized parameters in the template are applied to the result format in the Notebook.

For more information, see the Managing Template section in the *Oracle Financial Services Crime and Compliance Studio User Guide*.

7 Appendix - Generating Correlation Networks

After event data is loaded from different applications into Investigation Hub, you can correlate events based on business entities using configurable rule sets. This functionality is performed by the Event Correlation process. The group of events is identified for correlation-based on business entities in the application.

NOTE

This correlation is applicable only if you are not using the ECM application.

The Generate Correlation Network notebook creates the correlated networks of related events (alerts) for next-level investigators as a starting point of the investigation. It can be mapped to existing cases or used to generate new cases. These generated correlation networks are used in Special Investigation and Level 2 Case Investigations notebooks. To generate the correlation network, follow these steps:

1. Navigate to the Investigation Hub Home page.
2. Navigate to the **Generate Correlated Networks** notebook.
3. Execute the notebook.
4. After executing the notebook, the correlation network will be generated for loaded data.

8 Appendix - API for Running All Paragraphs

The following methods are available in the REST API for running all paragraphs at once:

Run all notebook paragraphs:

```
/v2/notebooks/run with {notebookId: notebookId, paragraphs: [{paragraphId:  
paragraphId , params: {}}]}
```

For more information, see the API documentation of Data Studio.

NOTE

Before running the API, values must be defined in notebooks.

OFSAA Support Contact Details

Raise a Service Request (SR) in [My Oracle Support \(MOS\)](#) for queries related to OFSAA applications.

Send Us Your Comments

Oracle welcomes your comments and suggestions on the quality and usefulness of this publication. Your input is an important part of the information used for revision.

- Did you find any errors?
- Is the information clearly presented?
- Do you need more information? If so, where?
- Are the examples correct? Do you need more examples?
- What features did you like most about this manual?

If you find any errors or have any other suggestions for improvement, indicate the title and part number of the documentation along with the chapter/section/page number (if available) and contact the Oracle Support.

Before sending us your comments, you might like to ensure that you have the latest version of the document wherein any of your concerns have already been addressed. You can access My Oracle Support site which has all the revised/recently released documents.

