

Oracle Banking Digital Experience

**Development Guide for Alert Configuration
Release 19.1.0.0.0**

Part No. F18558-01

May 2019

ORACLE®

Alert Configuration Developer Guide

May 2019

Oracle Financial Services Software Limited

Oracle Park

Off Western Express Highway

Goregaon (East)

Mumbai, Maharashtra 400 063

India

Worldwide Inquiries:

Phone: +91 22 6718 3000

Fax:+91 22 6718 3001

www.oracle.com/financialservices/

Copyright © 2019, Oracle and/or its affiliates. All rights reserved.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate failsafe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.

Table of Contents

1. Preface.....	4
1.1 Intended Audience	4
1.2 Documentation Accessibility	4
1.3 Access to Oracle Support	4
1.4 Structure.....	4
1.5 Related Information Sources.....	4
2. Context	5
3. Database Configurations	6
3.1 API for Raising an EVENT	19
3.2 Custom Fields For Push notifications	19
3.3 Multi-Entity Specific templates	20

1. Preface

1.1 Intended Audience

This document is intended for the following audience:

- Customers
- Partners

1.2 Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

1.3 Access to Oracle Support

Oracle customers have access to electronic support through My Oracle Support. For information, visit

<http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit

<http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

1.4 Structure

This manual is organized into the following categories:

Preface gives information on the intended audience. It also describes the overall structure of the User Manual.

Introduction provides brief information on the overall functionality covered in the User Manual.

The subsequent chapters provide information on transactions covered in the User Manual.

Each transaction is explained in the following manner:

- Introduction to the transaction
- Screenshots of the transaction
- The images of screens used in this user manual are for illustrative purpose only, to provide improved understanding of the functionality; actual screens that appear in the application may vary based on selected browser, theme, and mobile devices.
- Procedure containing steps to complete the transaction- The mandatory and conditional fields of the transaction are explained in the procedure.

If a transaction contains multiple procedures, each procedure is explained. If some functionality is present in many transactions, this functionality is explained separately.

1.5 Related Information Sources

For more information on Oracle Banking Digital Experience Release 19.1.0.0.0, refer to the following documents:

- Oracle Banking Digital Experience Licensing Guide
- Oracle Banking Digital Experience Installation Manuals

2. Context

This alert configuration contains step to configure alerts for any event in the system. Alerts are configured against the pre configured activity event .Any alert is identified by 3 properties as follows:

1. Activity Id: An identifier for the activity being performed .It is the combination of the fully qualified name for the class and the method name.
E.g. - Request fund activity in the Wallet.
The activity id would be "**com.ofss.digx.app.wallet.service.core. Wallet.requestFunds**"
2. Event Id: An identifier for the event occurred while performing the activity. An activity can have multiple events. It should start from the module name followed by the logical name for the event.
E.g. – Request fund success is an event in the wallet module.
The Event Id can be "**WA_REQUEST_FUNDS_SUCCESS**"
3. Action Id: An identifier for the action to be executed during event processing .The action can be of 3 types.
 - a. Alerts: Raise a message alert for the specified destination type like EMAIL, SMS etc. This is the default action performed while alerts processing.
 - b. Notifications: The notifications to be generated for the dashboard etc.
 - c. Business Logic: Any business Logic to be performed while alerts processing.

3. Database Configurations

All the configurations are explained with respect to Wallets request fund activity.

1. The Activity entry is added in the **DIGX_EP_ACT_B** table.

```
Insert into digx_ep_act_b
(COD_ACT_ID,
TXT_ACT_NAME,
TXT_ACT_DESC,
MODULE_TYPE,
CREATED_BY,
CREATION_DATE,
LAST_UPDATED_BY,
LAST_UPDATE_DATE,
OBJECT_VERSION_NUMBER,
OBJECT_STATUS)
values
('com.ofss.digx.app.wallet.service.core.Wallet.requestFunds',
'Wallet.requestFunds',
'Wallet Request Funds',
'WA',
'SYSTEPPER',
sysdate,
'SYSTEPPER',
sysdate,
1,
'A');
```

COLUMN NAME	DESCRIPTION
COD_ACT_ID	Primary key of the table. An identifier for the activity raising the event. It is the combination of the fully qualified name for the class and the method name.
TXT_ACT_NAME	Name of the activity. As a convention it is '.' separated combination of class name and method name.
TXT_ACT_DESC	Description of the activity.
MODULE_TYPE	Module type of the activity. It maps to the ModuleType enumeration.

SVN Location for Seed Data Script :

http://obcpsvn.oraclecorp.com:8080/svn/clip/trunk/core/seed/oracle/alerts/DIGX_EP_ACT_B.sql

2. The event is added in the table **DIGX_PM_EVENT_ALL_B** table.

```
Insert into digx_pm_event_all_b
  (EVENT_CODE, EVENT_DESC, ALERTS_FLAG)
values
  ('WA_REQUEST_FUNDS_SUCCESS',
  'Wallet Request Funds Successful',
  'Y');
```

COLUMN NAME	DESCRIPTION
EVENT_CODE	Primary key of the table. An identifier for the event occurred. It should start from the module type followed by the logical name for the event.
EVENT_DESC	Description of the event.
ALERTS_FLAG	Identifies whether the alert is required for this event or not. Possible values : 'Y' or 'N'.

SVN Location for Seed Data Script :

http://obcpsvn.oraclecorp.com:8080/svn/clip/trunk/core/seed/oracle/alerts/DIGX_PM_EVENT_ALL_B.sql

3. The activity Event combination is added in **DIGX_EP_ACT_EVT_B** table. Separate entries are required for all the events of the activity i.e. Suppose activity '**com.ofss.digx.app.wallet.service.core.Wallet.requestFunds**' has two events one for success and other for failure, 2 entries will go in the table for both of them.

```
insert into DIGX_EP_ACT_EVT_B
  (COD_ACT_ID,
  COD_EVENT_ID,
  TXT_ACT_EVT_DESC,
  TXT_EVT_TYP,
  TXT_ACT_EVT_TYP)
values
  ('com.ofss.digx.app.wallet.service.core.Wallet.requestFunds',
  'WA_REQUEST_FUNDS_SUCCESS',
  'Wallet Request Funds Successful',
  'OTHER',
  'ONLINE');
```

```

insert into DIGX_EP_ACT_EVT_B
(COD_ACT_ID,
 COD_EVENT_ID,
 TXT_ACT_EVT_DESC,
 TXT_EVT_TYP,
 TXT_ACT_EVT_TYP)
values
('com.ofss.digx.app.wallet.service.core.Wallet.requestFunds',
 'WA_REQUEST_FUNDS_FAILURE',
 'Wallet Request Funds Failure',
 'OTHER',
 'ONLINE');

```

COLUMN NAME	DESCRIPTION
COD_ACT_ID	Activity Id. It must match to the COD_ACT_ID column of DIGX_EP_ACT_B table.
COD_EVENT_ID	Event Id. It must match to the EVENT_CODE column of DIGX_PM_EVENT_ALL_B table.
TXT_ACT_EVT_DESC	Description of the activity event combination.
TXT_EVT_TYP	Event type. It maps to EventType enumeration.
TXT_ACT_EVT_TYP	Activity Event type. It maps to ActivityEventType enumeration. Possible values : ' BULK ' or ' ONLINE '.

SVN Location for Seed Data Script :

http://obcpsvn.oraclecorp.com:8080/svn/clip/trunk/core/seed/oracle/alerts/DIGX_EP_ACT_EVT_B.sql

4. Message templates are added based on the destination types to the table **DIGX_EP_MSG_TMPL_B** table.

```
insert into digx_ep_msg_tmpl_b
(COD_TMPL_ID,
DESTINATION_TYPE,
MSG_TMPL_NAME,
MSG_TMPL_DESC,
TXT_MSG_TMPL,
CREATED_BY,
CREATION_DATE,
LAST_UPDATED_BY,
LAST_UPDATE_DATE,
OBJECT_VERSION_NUMBER,
OBJECT_STATUS,
TXT SUBJECT_TMPL,
DETERMINANT_VALUE)
values
('WA_REQUEST_FUNDS_EMAIL',
'EMAIL',
'Wallet Request Funds EMAIL',
 '',
 '<p>Dear #WalletId#,</p><br><p>Please fund my wallet by
#Amount#.</p><br><br><p>Regards</p><br>#SenderName#',
 'SYSTELLER',
 sysdate, 'SYSTELLER',
 sysdate,
 1,
 'A',
 'Fund Wallet Request',
 'OBDX_BU');
```

COLUMN NAME	DESCRIPTION
COD_TMPL_ID	Primary key of the table. Uniquely identifies a message template. It should start from the module type followed by the logical name for the template.
DESTINATION_TYPE	Destination type of the template. It maps to DestinationType enumeration.
MSG_TMPL_NAME	Logical name of the message template.
MSG_TMPL_DESC	Description of the message template.
TXT_MSG_TMPL	It contains the format for the message body. It is stored as CLOB in the table.
TXT SUBJECT_TMPL	It contains the subject for the message. It is also stored as CLOB in the table.
DETERMINANT_VALUE	It determines the entity code for the template.

SVN Location for Seed Data Script :

http://obcpsvn.oraclecorp.com:8080/svn/clip/trunk/core/seed/oracle/alerts/DIGX_EP_MSG_TMPL_B.sql

As you can see in the above example, the data elements like wallet id, amount and sender name are defined in between '#'. The entry for those data elements(or attributes) is done in the following tables.

5. Message attributes are added in the table **DIGX_EP_MSG_ATTR_B** table.

```
insert into digx_ep_msg_attr_b
  (COD_MESS_TMPL_ID, COD_ATTR_ID, ATTR_MASK, DETERMINANT_VALUE)
values
  ('WA_REQUEST_FUNDS_EMAIL', 'Amount', 'D', 'OBDX_BU');

insert into digx_ep_msg_attr_b
  (COD_MESS_TMPL_ID, COD_ATTR_ID, ATTR_MASK, DETERMINANT_VALUE)
values
  ('WA_REQUEST_FUNDS_EMAIL', 'WalletId', 'D', 'OBDX_BU');
```

COLUMN NAME	DESCRIPTION
COD_MESS_TMPL_ID	Message template Id. It must match to the COD_TMPL_ID column of DIGX_EP_MSG_TMPL_B table.
COD_ATTR_ID	Name of the attribute. It must match to the one defined inside TXT_MSG_TMPL of DIGX_EP_MSG_TMPL_B table.
ATTR_MASK	Masking format for the attribute value. Characters given as 'X' will be masked and the ones given as 'D' will be displayed as it is.
DETERMINANT_VALUE	It determines the entity code for the template.

SVN Location for Seed Data Script :

http://obcpsvn.oraclecorp.com:8080/svn/clip/trunk/core/seed/oracle/metadata/DIGX_MD_SERVICE_ATTR.sql

6. Service attributes are added in **DIGX_MD_SERVICE_ATTR** table.

```
insert into digx_md_service_attr
(COD_SERVICE_ATTR_ID,
TYP_DATA_AVAIL,
TYP_DATA_SRC,
COD_ATTR_ID,
COD_SERVICE_ID,
PARAMETER_NAME,
CREATED_BY, CREATION_DATE,
LAST_UPDATED_BY, LAST_UPDATE_DATE,
OBJECT_VERSION_NUMBER,
OBJECT_STATUS,
REF_FIELD_DEFN_ID)
values
('com.ofss.digx.app.wallet.service.core.Wallet.requestFunds.WalletId.INPUT',
'INDIRECT',
'INPUT',
'WalletId',
'com.ofss.digx.app.wallet.service.core.Wallet.requestFunds',
'requestFundDTO',
'SETUP', sysdate,
'SETUP', sysdate,
1,
'A',
'com.ofss.digx.app.wallet.dto.transfer.RequestFundDTO.WalletId.Value');
```

```
insert into digx_md_service_attr
(COD_SERVICE_ATTR_ID,
TYP_DATA_AVAIL,
TYP_DATA_SRC,
COD_ATTR_ID,
COD_SERVICE_ID,
PARAMETER_NAME,
CREATED_BY, CREATION_DATE,
LAST_UPDATED_BY, LAST_UPDATE_DATE,
OBJECT_VERSION_NUMBER,
OBJECT_STATUS,
REF_FIELD_DEFN_ID)
values
('com.ofss.digx.app.wallet.service.core.Wallet.requestFunds.Amount.INPUT',
'INDIRECT',
'INPUT',
'Amount',
'com.ofss.digx.app.wallet.service.core.Wallet.requestFunds',
'requestFundDTO',
'SETUP', sysdate,
'SETUP', sysdate,
1,
'A',
'com.ofss.digx.app.wallet.dto.transfer.RequestFundDTO.Amount.Amount');
```

COLUMN NAME	DESCRIPTION
COD_SERVICE_ATTR_ID	Primary key of the table. As a convention, ‘.’ separated combination of COD_SERVICE_ID , COD_ATTR_ID and TYP_DATA_SRC .
TYP_DATA_AVAIL	Possible values : ‘DIRECT’ or ‘INDIRECT’. ‘DIRECT’ only when ‘TYP_DATA_SRC’ is ‘INPUT’ and the attribute value is one of the arguments passed to the activity. Otherwise ‘INDIRECT’.
TYP_DATA_SRC	Possible values : ‘INPUT’ or ‘DTO’. ‘INPUT’ when the attribute value can be obtained from the arguments passed to the activity. ‘DTO’ when the attribute value cannot be obtained from the arguments and is generated/fetched within the activity.
COD_ATTR_ID	Name of the attribute.
COD_SERVICE_ID	Activity Id. It must match to COD_ACT_ID column of DIGX_EP_ACT_B table.
PARAMETER_NAME	The name of the argument passed to the activity. Its value will be null when TYP_DATA_SRC is ‘DTO’.
REF_FIELD_DEFN_ID	Fully qualified path from which the attribute value can be obtained.

Here , in case of **TYP_DATA_SRC** as ‘INPUT’, there can be 2 cases :

- The attribute value is passed directly to the activity i.e. the attribute value is one of the arguments passed to the activity. In this case, **TYP_DATA_AVAIL** will be ‘DIRECT’.
- The attribute value is not passed directly to the activity , but it can be obtained from one of the arguments passed to the activity i.e. it is part of one of the DTOs which is passed to the activity. In this case, **TYP_DATA_AVAIL** will be ‘INDIRECT’.

SVN Location for Seed Data Script :

http://obcpsvn.oraclecorp.com:8080/svn/clip/trunk/core/seed/oracle/metadata/DIGX_MD_SERVICE_ATTR.sql

7. Source of the message attributes are added in **DIGX_EP_MSG_SRC_B** table.

```

INSERT INTO digx_ep_msg_src_b
  (COD_MESS_TMPL_ID, COD_ATTR_ID, COD_ACT_ID, COD_SERVICE_ATTR_ID,
DETERMINANT_VALUE)
VALUES
  ('WA_REQUEST_FUNDS_EMAIL',
  'WalletId',
  'com.ofss.digx.app.wallet.service.core.Wallet.requestFunds',
  'com.ofss.digx.app.wallet.service.core.Wallet.requestFunds.WalletId.INPUT',
  'OBDX_BU');

```

```

INSERT INTO digx_ep_msg_src_b
  (COD_MESS_TMPL_ID, COD_ATTR_ID, COD_ACT_ID, COD_SERVICE_ATTR_ID,
DETERMINANT_VALUE)
VALUES
  ('WA_REQUEST_FUNDS_EMAIL',
  'Amount',
  'com.ofss.digx.app.wallet.service.core.Wallet.requestFunds',
  'com.ofss.digx.app.wallet.service.core.Wallet.requestFunds.Amount.INPUT',
  'OBDX_BU');

```

COLUMN NAME	DESCRIPTION
COD_MESS_TMPL_ID	Message template Id. It must match to the COD_TMPL_ID column of DIGX_EP_MSG_TMPL_B table.
COD_ATTR_ID	Name of the attribute. It must match to the one defined inside TXT_MSG_TMPL of DIGX_EP_MSG_TMPL_B table.
COD_ACT_ID	Activity Id. It must match to COD_ACT_ID column of DIGX_EP_ACT_B table.
COD_SERVICE_ATTR_ID	Service attribute id. It must match to COD_SERVICE_ATTR_ID of DIGX_MD_SERVICE_ATTR table.
DETERMINANT_VALUE	It determines the entity code for the template.

SVN Location for Seed Data Script :

http://obcpsvn.oraclecorp.com:8080/svn/clip/trunk/core/seed/oracle/alerts/DIGX_EP_MSG_SRC_B.sql

8. The attributes which are input to the activity are added in **DIGX_MD_SERVICE_INPUTS** table.

```
insert into digx_md_service_inputs
(COD_SERVICE_ID,
PARAMETER_NAME,
PARAMETER_INDEX,
DATA_TYPE,
CREATED_BY,
CREATION_DATE,
LAST_UPDATED_BY,
LAST_UPDATE_DATE,
OBJECT_VERSION_NUMBER,
OBJECT_STATUS)
values
('com.ofss.digx.app.wallet.service.core.Wallet.requestFunds',
'requestFundDTO',
1,
'com.ofss.digx.app.wallet.dto.transfer.RequestFundDTO',
'SETUP',
'sysdate',
'SETUP',
'sysdate',
1,
'A');
```

COLUMN NAME	DESCRIPTION
COD_SERVICE_ID	Activity Id. It must match to COD_ACT_ID column of DIGX_EP_ACT_B table.
PARAMETER_NAME	The name of the argument passed to the activity.
PARAMETER_INDEX	Unique index of the argument for an activity. It starts from 0 for a particular activity.
DATA_TYPE	Data type of the argument passed to the activity.

SVN Location for Seed Data Script :

http://obcpsvn.oraclecorp.com:8080/svn/clip/trunk/core/seed/oracle/alerts/DIGX_EP_MSG_SRC_B.sql

9. The generic attributes along with their datatypes are added in **DIGX_MD_GEN_ATTR_LEGACY_B** table.

```
insert into DIGX_MD_GEN_ATTR_LEGACY_B
(cod_constraint_attr_id,
txt_constraint_attr_name,
data_type,
CREATED_BY,
CREATION_DATE,
LAST_UPDATED_BY,
LAST_UPDATE_DATE,
OBJECT_VERSION_NUMBER,
OBJECT_STATUS)
values
('WALLET_ID',
'UniqueWalletIdentifier',
'java.lang.String',
'SETUP',
sysdate,
'SETUP',
sysdate,
1,
'A');
```

```
insert into DIGX_MD_GEN_ATTR_LEGACY_B
(cod_constraint_attr_id,
txt_constraint_attr_name,
data_type,
CREATED_BY,
CREATION_DATE,
LAST_UPDATED_BY,
LAST_UPDATE_DATE,
OBJECT_VERSION_NUMBER,
OBJECT_STATUS)
values
('AMOUNT',
'TransactionAmount',
'java.lang.String',
'SETUP',
sysdate,
'SETUP',
sysdate,
1,
'A');
```

COLUMN NAME	DESCRIPTION
COD_CONSTRAINT_ATTR_ID	Attribute Id.
TXT_CONSTRAINT_ATTR_NAME	Name or description of the attribute.
DATA_TYPE	Data type of the attribute to format the attribute value.

SVN Location for Seed Data Script :

http://obcpsvn.oraclecorp.com:8080/svn/clip/trunk/core/seed/oracle/metadata/DIGX_MD_GEN_ATTR_LEGACY_B.sql

10. Entry for alert is added in **DIGX_EP_ACT_EVT_ACN_B** table.

```
insert into digx_ep_act_evt_Acn_b
(COD_ACT_ID,
 COD_EVENT_ID,
 COD_ACTION_ID,
 FLG_TRANSACTIONAL,
 COD_DEC_ID,
 FLG_CONDITIONAL,
 COD_ACN_TMPL_ID,
 ALERT_NAME,
 CREATED_BY,
 CREATION_DATE,
 LAST_UPDATED_BY,
 LAST_UPDATE_DATE,
 OBJECT_VERSION_NUMBER,
 EXPIRY_DATE,
 ALERT_TYPE,
 ALERT_DISPATCH_TYPE,
 OBJECT_STATUS)
values
('com.ofss.digx.app.wallet.service.core.Wallet.requestFunds',
 'WA_REQUEST_FUNDS_SUCCESS',
 'A',
 'Y',
 '0',
 'N',
 '1',
 'Wallet Request Funds',
 'OFSSUser',
 sysdate,
 'OFSSUser',
 sysdate,
 1,
 to_date('23-02-2018', 'dd-mm-yyyy'),
 'S',
 'I',
 'A');
```

COLUMN NAME	DESCRIPTION
COD_ACT_ID	Activity Id.
COD_EVENT_ID	Event Id.
COD_ACTION_ID	Action Id. Possible value : 'A' (means Alert)
FLG_TRANSACTIONAL	Possible values : 'Y' or 'N'. This flag indicates whether events under this event category are transactional events or not. A Transactional event is an event which get processed within the same session of manager API.
COD_DEC_ID	Possible Value : 0
FLG_CONDITIONAL	Possible value : 'N'.

COLUMN NAME	DESCRIPTION
COD_ACN_TMPL_ID	Possible values : 1 or 2 . 1 indicates the importance of alert is critical. 2 indicates the importance of alert is informational.
ALERT_NAME	Unique name for the alert.
EXPIRY_DATE	Expiry Date of the alert.
ALERT_TYPE	Alert Type. Possible values: ' M ' or ' S '. 'M' indicates the alert is of mandatory type and cannot be subscribed/unsubscribed by the user. 'S' indicates the alert is of subscribed type which can be subscribed/unsubscribed by the user.
ALERT_DISPATCH_TYPE	Alert Dispatch Type. Possible values: ' I ' or ' D '. 'I' indicates immediate i.e. the alert needs to be send immediately. 'D' indicates deferred i.e. the alert will be sent later.

SVN Location for Seed Data Script :

http://obcpsvn.oraclecorp.com:8080/svn/clip/trunk/core/seed/oracle/alerts/DIGX_EP_ACT_EVT_ACN_B.sql

11. Entry for recipient message templates is added in **DIGX_EP_EVT_REC_B** table. Separate entries are required for all the destination types of the alert i.e. Suppose activity '**'com.ofss.digx.app.wallet.service.core.Wallet.requestFunds'** has two destination types, EMAIL and SMS, 2 entries will go in this table.

```
insert into digx_ep_evt_rec_b
(COD_ACT_ID,
COD_EVENT_ID,
COD_ACTION_ID,
COD_MSG_TMPL_ID,
TXT_DEST_TYP,
SUBSCRIBER_TYPE,
SUBSCRIBER_VALUE,
ALERT_TYPE,
LOCALE)
values
('com.ofss.digx.app.wallet.service.core.Wallet.requestFunds',
'WA_REQUEST_FUNDS_SUCCESS',
'A',
'WA_RequestFunds_EMAIL',
'EMAIL',
'PARTY',
'CUSTOMER',
'S',
'en');
```

```

insert into digx_ep_evt_rec_b
(COD_ACT_ID,
COD_EVENT_ID,
COD_ACTION_ID,
COD_MSG_TMPL_ID,
TXT_DEST_TYP,
SUBSCRIBER_TYPE,
SUBSCRIBER_VALUE,
ALERT_TYPE,
LOCALE)
values
('com.ofss.digx.app.wallet.service.core.Wallet.requestFunds',
'WA_REQUEST_FUNDS_SUCCESS',
'A',
'WA_RequestFunds_SMS',
'SMS',
'PARTY',
'CUSTOMER',
'S',
'en');

```

COLUMN NAME	DESCRIPTION
COD_ACT_ID	Activity Id.
COD_EVENT_ID	Event Id.
COD_ACTION_ID	Action Id. Possible value : 'A' (means Alert)
COD_MSG_TMPL_ID	Message Template Id. Foreign key to COD_TMPL_ID of DIGX_EP_MSG_TMPL_B .
TXT_DEST_TYP	Destination Type. Possible value : 'EMAIL' , 'SMS', 'SECURE_MAIL_BOX', 'PUSH_NOTIFICATION'
'SUBSCRIBER_TYPE	Possible value : 'PARTY'.
SUBSCRIBER_VALUE	Possible value : 'CUSTOMER'.
ALERT_TYPE	Alert Type. Possible values: 'M' or 'S'. 'M' indicates the alert is of mandatory type and cannot be subscribed/unsubscribed by the user. 'S' indicates the alert is of subscribed type which can be subscribed/unsubscribed by the user.
LOCALE	Locale to pick the location/language specific template for.

SVN Location for Seed Data Script :

http://obcpsvn.oraclecorp.com:8080/svn/clip/trunk/core/seed/oracle/alerts/DIGX_EP_EVT_REC_B.sql

Note: Entries for most of the activities, events, corresponding activity events , message templates, message attributes are already added. Please check for the entries in the table to avoid repetition.

3.1 API for Raising an EVENT

For raising an event, `registerActivityAndGenerateEvent` API has been provided in the **AbstractApplication** class.

It takes 4 parameters:

- Session Context
- EventId
- ActivityLog

Alerts can be either Account based or Party based.

If it is Account based, populating 2 attributes(`accountId` and `accountType`) of `ActivityLog` is bare minimum requirement.

Similarly, if it is Party based, populating 1 attribute(`customerId`) of `ActivityLog` is bare minimum requirement.

For the other attributes, In case the attribute is already present in **com.ofss.digx.app.alerts.dto.eventgen.ActivityLog** class use the existing `ActivityLog` instance.

Else create a subclass of `ActivityLog` having your attribute. Set the attribute value in the `ActivityLog` child class and pass its instance as an argument to `registerActivityAndGenerateEvent` method.

```
ActivityLog activityLog = new ActivityLog();
// if it is a party based alert setCustomerId
    activityLog.setCustomerId(sessionContext.getTransactingPartyCode());
// if it is a account based alert setAccountId and setAccountType
    activityLog.setAccountId("{{AccountNumber}}");
    activityLog.setAccountType("{{AccountType}}");
//If required, set other attributes in activityLog

super.registerActivityAndGenerateEvent(sessionContext, {{EventId}}, activityLog);
```

3.2 Custom Fields For Push notifications

Following Keys can be used to customize Push Notifications.

KEY NAME	VALUE
SOUND_IOS	File name of custom sound file added to OBDX IOS App
SOUND_ANDROID	File name of custom sound file added to OBDX Android App
LARGE_ICON_ANDROID	URL of icon image to be displayed as large icon in Big Style Push Notification of OBDX Android App.
LARGE_IMAGE_ANDROID	URL of image to be displayed in Big Style Push Notification of OBDX Android App.

These custom keys are to be added to the value of “`TXT_MSG_TMPL`” column of **DIGX_EP_MSG_TMPL_B** table.

If alerts are being created through front end UI, add following keys to "Notification Message" section.

Syntax for adding custom keys to Push Notification alert messages

[customfield1Name~customfield1Value|customfield2Name~customfield2Value]

Example 1:

You have requested for #NoOfChequeBook# cheque book with #ChequeBookOption# leaves on Account #AccountNo#.

[SOUND_ANDROID~isntit|LARGE_IMAGE_ANDROID~http://static1.squarespace.com/static/54a6f9ae4b0cf1d82a4b59e/t/587f9e52cd0f68e84c5548fd/1484758653422/?format=300w|SOUND_OS~chime.m4a]

Example 2:

You have requested for #NoOfChequeBook# cheque book with #ChequeBookOption# leaves on Account #AccountNo#.

[SOUND_ANDROID~isntit|LARGE_ICON_ANDROID~http://static1.squarespace.com/static/54ac6f9ae4b0cf1d82a4b59e/t/587f9e52cd0f68e84c5548fd/1484758653422/?format=300w|SOUND_OS~chime.m4a]

3.3 Multi-Entity Specific templates

Entity specific templates can be created by following ways :

1. Creation of a new alert and template before the entity creation.

If a new alert has to be maintained before the creation of any new entity, the data for the same has to be inserted in the following tables twice.

One for DETERMINANT_VALUE '*' and the other for DETERMINANT_VALUE 'OBDX_BU', which is the default entity.

Tables :

DIGX_EP_MSG_TMPL_B

DIGX_EP_MSG_ATTR_B

DIGX_EP_MSG_SRC_B

2. Creation of a new alert and template after the entity creation.

If a new alert has to be maintained after the creation of entity/entities, the same can be replicated for the different entities using the below queries.

First insert the templates for DETERMINANT_VALUE '*' and DETERMINANT_VALUE 'OBDX_BU' and then execute the below queries for the respective entities.

```
insert into DIGX_EP_MSG_TMPL_B (DETERMINANT_VALUE, CREATION_DATE,
LAST_UPDATED_DATE, OBJECT_VERSION_NUMBER, COD_TMPL_ID, DESTINATION_TYPE,
MSG_TMPL_NAME, MSG_TMPL_DESC, TXT_MSG_TMPL, CREATED_BY, LAST_UPDATED_BY,
OBJECT_STATUS, TXT_SUBJECT_TMPL, DOMAIN_OBJECT_EXTN)
  (select '<ENTITY CODE TO BE REPLICATED>', sysdate, sysdate, 1,
COD_TMPL_ID, DESTINATION_TYPE, MSG_TMPL_NAME, MSG_TMPL_DESC, TXT_MSG_TMPL,
CREATED_BY, LAST_UPDATED_BY, OBJECT_STATUS, TXT_SUBJECT_TMPL,
DOMAIN_OBJECT_EXTN  from DIGX_EP_MSG_TMPL_B where DETERMINANT_VALUE = ''*');

insert into DIGX_EP_MSG_ATTR_B (DETERMINANT_VALUE, COD_MESS_TMPL_ID,
COD_ATTR_ID, ATTR_MASK, DATA_ATTR_ORDER, DOMAIN_OBJECT_EXTN)
  (select '<ENTITY CODE TO BE REPLICATED>', COD_MESS_TMPL_ID, COD_ATTR_ID,
ATTR_MASK, DATA_ATTR_ORDER, DOMAIN_OBJECT_EXTN  from DIGX_EP_MSG_ATTR_B where
DETERMINANT_VALUE = ''*');

insert into DIGX_EP_MSG_SRC_B (DETERMINANT_VALUE, COD_MESS_TMPL_ID,
COD_ATTR_ID, COD_ACT_ID, COD_SERVICE_ATTR_ID)
  (select '<ENTITY CODE TO BE REPLICATED>', COD_MESS_TMPL_ID, COD_ATTR_ID,
COD_ACT_ID, COD_SERVICE_ATTR_ID  from DIGX_EP_MSG_SRC_B where
DETERMINANT_VALUE = ''*');
```