

# **Oracle® Service Bus**

MQ Transport User Guide

10g Release 3 Maintenance Pack 1 (10.3.1)

June 2009

**ORACLE®**

Copyright © 2007, 2008, Oracle and/or its affiliates. All rights reserved.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this software or related documentation is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, the following notice is applicable:

U.S. GOVERNMENT RIGHTS Programs, software, databases, and related documentation and technical data delivered to U.S. Government customers are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, duplication, disclosure, modification, and adaptation shall be subject to the restrictions and license terms set forth in the applicable Government contract, and, to the extent applicable by the terms of the Government contract, the additional rights set forth in FAR 52.227-19, Commercial Computer Software License (December 2007). Oracle USA, Inc., 500 Oracle Parkway, Redwood City, CA 94065.

This software is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications which may create a risk of personal injury. If you use this software in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure the safe use of this software. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software in dangerous applications.

Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

This software and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.

# Contents

## Introduction to the MQ Transport

Messaging Patterns .....	1-3
Environment Values .....	1-4
Quality of Service .....	1-5
MQ Clusters and the MQ Transport .....	1-5

## Using the MQ Transport

Adding MQ Client Libraries to Your Environment .....	2-2
MQ Connection Resources .....	2-2
Creating an MQ Connection Resource .....	2-3
Configuring Proxy Services to Use the MQ Transport .....	2-4
Configuring Business Services to Use the MQ Transport .....	2-8
Transport Headers .....	2-11
Configuring Transport Headers .....	2-21
About RFH2 Headers .....	2-22
Error Handling .....	2-22
Limitations of the MQ Transport .....	2-24

## Using the WebSphere JMS MQ Interface

Using the WebSphere MQ JMS Interface .....	3-1
Messaging Types .....	3-2
Non-Persistent Messaging .....	3-3
Non-XA Persistent Messaging .....	3-3

XA Messaging .....	3-3
Tuning WebSphere MQ .....	3-4

# Introduction to the MQ Transport

Oracle Service Bus supports access to IBM WebSphere MQ using the MQ Transport. This transport supports both inbound and outbound connectivity. MQ proxy services can receive messages from WebSphere MQ and MQ business services can route messages to WebSphere MQ.

## Key Features

The following key features are supported for the MQ transport:

- Inbound and outbound connectivity. MQ proxy services can receive messages from WebSphere MQ and MQ business services can route messages to WebSphere MQ.
- Access to WebSphere MQ. For more information, see [Adding MQ Client Libraries to Your Environment](#). See [Product Support Information](#) for supported versions of WebSphere MQ.
- Sending and receiving messages of Any XML, Binary, XML, Text and MFL types.
- Processing of all the MQMD (MQ message descriptor) headers. A message descriptor is an attribute representing a property of the message that is either being sent or received.

For a list of MQ headers that can be configured for outbound response and inbound requests, see [Transport Headers](#).

- TCP/IP and bindings mode for connecting to queue managers.

Use the bindings mode to connect to WebSphere MQ that is located on the same physical machine as Oracle Service Bus. Use TCP/IP to connect to WebSphere MQ that does not reside on the same machine as Oracle Service Bus.

- One-way and two-way SSL on inbound and outbound transport.

SSL is supported only when TCP/IP is used to connect to WebSphere MQ from Oracle Service Bus.

## Advantages of Using the MQ Transport

Because the WebSphere MQ for Java APIs do not support XA transactions, Oracle Service Bus does not support XA transactions for the MQ transport. If XA is required, JMS transport with WebSphere MQ JMS interface should be used. For more information, see [Chapter 3, “Using the WebSphere JMS MQ Interface”](#).

Using the MQ transport has the following advantages over using the WebSphere MQ JMS interface:

- Faster connection to WebSphere MQ through the MQ transport than through the WebSphere MQ JMS interface.
- Ability to read and generate MQ messages. Using the JMS interface, it is not possible to set certain headers.
- Support for sending and receiving MQ receipt messages.
- No explicit binding of MQ Connection Factory and MQ Queue to WebLogic’s JNDI is required.
- Configuration of resources like a JMS provider, outside of Oracle Service Bus, is not required.
- Performance improvement because messages are sent directly using the transport instead of channeling them through the JMS transport.

## Supported Service Types

The MQ transport is available for the Message Service and XML Service service types.

For more information, see [Business Services: Creating and Managing](#) and [Proxy Services: Creating and Managing](#) in *Using the Oracle Service Bus Console*.

# Messaging Patterns

The Native MQ transport supports one-way and request-response messaging patterns for both inbound and outbound connectivity. By default, one-way messaging is supported. A proxy or business service supports request-response messaging when you set the `is-response-required` option while configuring the service.

The inbound and outbound transports support the asynchronous request-response pattern using `messageID` or `correlationID` for correlation between the request and the response. You can set the response correlation pattern during service configuration. For more information, see “CorrelationID” and “MessageID” in [Transport Headers](#).

The outbound transport provides an option to auto-generate the correlation ID / messageID or use the one specified by you in the message flow. Select the `Auto-generate Correlation Value` option, to indicate that the correlation ID / message ID should be auto-generated by the transport. If the option is not selected, the value specified by you in the message flow is used.

If the correlation value (`messageID` / `correlationID`) is not auto-generated and if the managed server goes down, the remaining response messages may never get removed when the server is restarted. Oracle recommends that the `Expiry` header on the request is configured to a finite value and that the `Report` header contains the `MQC.MQRO_PASS_DISCARD_AND_EXPIRY` option.

The `MQC.MQRO_PASS_DISCARD_AND_EXPIRY` option serves as a directive to the receiving client that the message descriptor of the reply should inherit the `Expiry` header value of the request message. This ensures that the response messages are removed by the MQ server after the configured expiry period has elapsed. When the correlation value is automatically generated, the Oracle Service Bus server is responsible for cleaning up any remaining response messages.

For more information about configuring **Is Response Required, Response Correlation Pattern, Auto Generate Correlation Value** for a service, see [Configuring Proxy Services to Use the MQ Transport](#) and [Configuring Business Services to Use the MQ Transport](#).

## Environment Values

Environment values are certain predefined fields in the configuration data whose values are very likely to change when you move your configuration from one domain to another (for example, from test to production). For information about updating environment values, see [Finding and Replacing Environment Values](#) in *Using the Oracle Service Bus Console*. The following sections provide a list of environment values for the Native MQ transport services and the MQ connection resource.

Services based on the MQ transport support the `Work Manager` (Inbound and Outbound) environment value.

MQ connections are sharable resources that can be reused across multiple MQ proxy and business services. MQ Connection resources provide the connection parameters required for connecting to a MQ queue manager. The MQ connection resource supports the following environment and operational values:

- MQ Connection Host Name
- MQ Connection Port
- MQ Queue Manager Name
- MQ Channel Name
- MQ Connection Pool Size
- MQ Connection Timeout

For information about updating environment values, see [Customization](#) in *Using the Oracle Service Bus Console*.



## Quality of Service

When the inbound transport is MQ and the Quality of Service (QoS) on the outbound transport is *exactly-once*, the resultant QoS will be *at-least-once*. By default, the QoS on the outbound transport is *exactly-once*.

**Note:** You must create error handling logic (including any retry logic) in the pipeline error handler. For information about configuring error handling, see [Proxy Services: Error Handlers](#) in *Using the Oracle Service Bus Console*.

When the outbound is request-response, the QoS is *at-least-once* only if the outbound transport is configured to support *exactly-once* QoS.

For more information about QoS in Oracle Service Bus messaging, see “Quality of Service” in [Modeling Message Flow in Oracle Service Bus](#) in the *Oracle Service Bus User Guide*.

## MQ Clusters and the MQ Transport

The cluster support in WebSphere MQ is that of store-and-forward messaging and not of load-balancing and fail over. The cluster queues in WebSphere MQ are created locally on one of the queue managers and shared with other cluster members that act as remote forwarders to the shared queue.

Requests from the MQ transport are load balanced by sending messages using the load balancing algorithm to the members of the cluster. However, the transport receives messages by accessing only the MQ server node that holds the reference to the local queue.

## Introduction to the MQ Transport

# Using the MQ Transport

You can use the Oracle Service Bus MQ transport to enable MQ proxy services to get messages from WebSphere MQ and MQ business services to send messages to WebSphere MQ. This document describes how to add WebSphere MQ to your Oracle Service Bus environment, characteristics of the Oracle Service Bus MQ transport, and how to configure MQ proxy and business services.

**Note:** See [Product Support Information](#) for supported versions of WebSphere MQ on Oracle Service Bus.

This section contains the following topics:

- [Adding MQ Client Libraries to Your Environment](#)
- [MQ Connection Resources](#)
- [Configuring Proxy Services to Use the MQ Transport](#)
- [Configuring Business Services to Use the MQ Transport](#)
- [Transport Headers](#)
- [Error Handling](#)

## Adding MQ Client Libraries to Your Environment

Oracle Service Bus is a client for WebSphere MQ, and although Oracle Service Bus supports run-time server compatibility for the versions of WebSphere MQ listed in [Product Support Information](#), these MQ libraries are not bundled with the Oracle Service Bus installer. You need to ensure that the MQ client library, `com.ibm.mq.jar`, is available in your environment.

For information about the system requirements for WebSphere MQ, see <http://www-306.ibm.com/software/integration/wmq/requirements/index.html>

To add the MQ client libraries to your environment:

1. Stop the domain server.
2. From your WebSphere MQ installation, copy the `com.ibm.mq.jar` file to the `BEA_HOME\user_projects\domains\<domain_name>\lib` directory.  
  
BEA\_HOME is the Oracle Service Bus installation directory. Replace `<domain_name>` with the actual name of your domain.
3. Restart the domain server.

If you use bindings mode to connect MQ Queue Manager located on the same machine as Oracle Service Bus, add `<MQ_install_directory>/bin` and `<MQ_install_directory>/java/lib` to the PATH environment variable.

## MQ Connection Resources

MQ connections are sharable resources that can be reused across multiple MQ proxy and business services. MQ proxy and business services must connect to a MQ queue manager before accessing the MQ queue. MQ connection resources provide the connection parameters required for connecting to a MQ queue manager.

Each MQ connection resource has a connection pool. Multiple business services and proxy services using the same queue manager share a connection pool. Any business or proxy service using a given MQ connection resource to connect to a given queue manager uses the same connection pool that was created for that MQ connection resource.

For information about managing MQ connection resources, see [MQ Connections](#) in *Using the Oracle Service Bus Console*.

For information about queue managers, see <http://www.redbooks.ibm.com/redbooks/SG247128/wwhelp/wwhimpl/java/html/wwhelp.htm>.

## Creating an MQ Connection Resource

To create an MQ connection resource:

**Note:** The following instructions on creating an MQ Connection resource pertain to the Oracle Service Bus Console. In Workshop for WebLogic, using the Oracle Service Bus perspective, select **File > New > Custom Resource** to create the MQ Connection resource.

1. In the Project Explorer, select MQ Connection as the resource type. The Create a New MQ Connection Resource page appears.

2. Enter the name and description of the resource.

**Note:** Do not include spaces in the name.

3. Select the connection type as `tcp mode` or `bindings mode`.

Use `tcp mode` when the MQ Queue Manager is not available on the same machine as Oracle Service Bus. Use `bindings mode` to connect MQ Queue Manager located on the same machine as Oracle Service Bus.

4. If the connection type is `bindings mode`, enter the name of the MQ Queue Manager.

5. If the connection type is `tcp mode`,

- a. Enter the host name of the MQ Queue Manager.
- a. Enter the port number of the MQ Queue Manager Listener.
- b. Enter the name of the MQ Queue Manager.
- c. Enter the coded character set identifier (CCSID) to be used for connecting to the MQ Queue Manager for client connection mode.
- d. Enter the Queue Manager server connection channel name.
- e. Select the **SSL** option, if required, to use HTTPS protocol for sending the messages.

After you select this option, select the 2-way SSL Required option to enable 2-way SSL for both client-side and server-side authentication. Clear the 2-way SSL Required option for 1-way SSL for only server-side authentication.

**Note:** When you select 2-way SSL, you need to provide a reference to a service key provider. A service key provider contains Public Key Infrastructure (PKI) credentials that proxy services use for decrypting inbound SOAP messages and for outbound authentication and digital signatures. For more information about

using service providers, see [Service Key Providers](#) in *Using the Oracle Service Bus Console*.

- f. Specify the static service account.

A service account provides a user name and password that proxy services and business services use for outbound authentication or authentication to a local or remote resource. For more information about using service accounts, see [Service Accounts](#) in *Using the Oracle Service Bus Console*.

6. Select the version of WebSphere MQ.
7. Enter the size of the MQ connection pool. Default is 10.
8. For MQ Connection Timeout, enter the time interval in seconds after which unused connections are destroyed. The default is 1800 seconds.
9. Enter the Max Wait in seconds for the amount of time to wait for a connection to become available. If a connection is not made within that time interval, Oracle Service Bus throws an exception. The default is 3 seconds.
10. Click **Save**.

The MQ connection resource is created. You can use it across proxy and business services that use the MQ transport.

## Configuring Proxy Services to Use the MQ Transport

During service configuration, select either Message service or XML service as the service type in the General Configuration page. For more information, see [Supported Service Types](#) and [Proxy Services: Creating and Managing](#) in *Using the Oracle Service Bus Console*.

When you create an MQ service, select the transport protocol as `mq` and specify the Endpoint URI in the Transport Configuration page. Specify the Endpoint URI in

`mq://local-queue-name?conn=mq-connection-resource-ref` format where

`local-queue-name` is the name of the local queue configured on the MQ server

`mq-connection-resource-ref` points to the location of the MQ connection resource

For example, if you create a MQ connection resource, `mqConnection` in the `defaultMQ` folder and the queue name is `testQueue`, the URI would be

`mq://testQueue?conn=defaultMQ/mqConnection`

**Note:** The Endpoint URI cannot contain spaces, so do not create MQ Connection resources or projects/folders with spaces in the names.

Configure the MQ transport for a proxy service with values as described in the following table:

**Table 0-1 MQ Proxy Service Configuration**

Option	To create or edit...
Polling Interval	Enter a polling interval, in milliseconds. The default is 1000.
Is Response Required	Select this option to specify that a response is expected after an outbound message is sent.
Response Correlation Pattern	<p>This option is available only when the <b>Is Response Required</b> check box is selected.</p> <p>Specify whether the response correlation pattern should be based on <b>MessageID</b> or <b>CorrelationID</b>.</p>
MQ Response URI	<p>This option is available only when the <b>Is Response Required</b> check box is selected.</p> <p>The destination to which the response should be published. Enter a response URI in the same format as the endpoint URI:  mq://&lt;local-queue-name&gt;?conn=&lt;mq-connection-resource-ref&gt;</p>
Response Message Type	<p>This option is available only when the <b>Is Response Required</b> check box is selected.</p> <p>Select one of the following:</p> <ul style="list-style-type: none"> <li>• <b>Bytes</b> (for a stream of uninterpreted bytes)</li> <li>• <b>Text</b> (for text messages)</li> </ul>
Client Response Timeout	<p>This option is available only when the <b>Is Response Required</b> check box is selected.</p> <p>Enter the number of seconds to wait for a response before dropping the connection.</p>

**Table 0-1 MQ Proxy Service Configuration (Continued)**

Option	To create or edit...
Dispatch Policy	<p>This option is available only when the <b>Is Response Required</b> check box is selected.</p> <p>Select a dispatch policy for this endpoint.</p> <p>Dispatch policy refers to the instance of WLS Work Manager that you want to use for the service endpoint. For information about work managers, see <a href="#">Using Work Managers to Optimize Scheduled Work</a> and <a href="#">Create Work Manager</a> in the WebLogic Server Administration Console Online Help.</p>
Backout Threshold	<p>Enter a value representing the number of times the pipeline should retry a message before redirecting the message to the queue specified in the <b>Dead Letter URI</b> field.</p> <p>If you do not specify a value for this field, the message is redirected to the dead letter queue without attempting any retries.</p>
MQ Dead Letter URI	<p>Enter the URI of the dead letter queue to which request messages should be redirected after attempting the number of retries specified in the <b>Backout Threshold</b> field.</p> <p>If you do not specify a value for this field, the message is discarded after retrying the number of times specified in the <b>Backout Threshold</b> field.</p> <p>The Dead Letter URI uses the same format as the EndPoint URI.</p>



**Table 0-1 MQ Proxy Service Configuration (Continued)**

Option	To create or edit...
Endpoint URI 'GET' options	<p data-bbox="525 390 1137 416">Enter the MQ GET message options from among the following:</p> <ul data-bbox="525 428 1060 1315" style="list-style-type: none"> <li>• MQC.MQGMO_ACCEPT_TRUNCATED_MSG</li> <li>• MQC.MQGMO_ALL_MSGS_AVAILABLE</li> <li>• MQC.MQGMO_BROWSE_FIRST</li> <li>• MQC.MQGMO_BROWSE_NEXT</li> <li>• MQC.MQGMO_COMPLETE_MSG</li> <li>• MQC.MQGMO_CONVERT</li> <li>• MQC.MQGMO_FAIL_IF QUIESCING</li> <li>• MQC.MQGMO_LOCK</li> <li>• MQC.MQGMO_LOGICAL_ORDER</li> <li>• MQC.MQGMO_MARK_BROWSE_CO_OP</li> <li>• MQC.MQGMO_MARK_SKIP_BACKOUT</li> <li>• MQC.MQGMO_NO_SYNCPOINT</li> <li>• MQC.MQGMO_NONE</li> <li>• MQC.MQGMO_NO_WAIT</li> <li>• MQC.MQGMO_SYNCPOINT</li> <li>• MQC.MQGMO_SYNCPOINT_IF_PERSISTENT</li> <li>• MQC.MQGMO_UNLOCK</li> <li>• MQC.MQGMO_UNMARK_BROWSE_CO_OP</li> <li>• MQC.MQGMO_UNMARK_BROWSE_HANDLE</li> <li>• MQC.MQGMO_UNMARKED_BROWSE_MSG</li> <li>• MQC.MQGMO_VERSION_1</li> <li>• MQC.MQGMO_VERSION_2</li> <li>• MQC.MQGMO_VERSION_3</li> <li>• MQC.MQGMO_WAIT</li> </ul> <p data-bbox="525 1329 1213 1387">You can use either “ ” or “+” to separate multiple options. For example, you can specify the following:</p> <pre data-bbox="525 1400 1016 1454">MQC.MQGMO_ACCEPT_TRUNCATED_MSG   MQC.MQGMO_LOCK</pre> <p data-bbox="525 1468 1228 1525">The MQ GET message options are applied when reading a message from the inbound queue.</p>

Table 0-1 MQ Proxy Service Configuration (Continued)

Option	To create or edit...
Process RFH2 Headers	Select this option to parse WebSphere MQ RFH2 headers from a message payload and automatically generate an RFH2Headers transport header containing the RFH2 data.  If you do not select this option, the payload is passed through as received.

For more information about configuring proxy services using MQ transport, see MQ Transport Configuration Page in [Proxy Services: Creating and Managing](#) in *Using the Oracle Service Bus Console*.

# Configuring Business Services to Use the MQ Transport

During service configuration, select either Message service or XML service as the service type in the General Configuration page. For more information, see in [Business Services: Creating and Managing](#) in *Using the Oracle Service Bus Console*.

When you create an MQ service, select the transport protocol as `mq` and specify the Endpoint URI in the Transport Configuration page. Specify the Endpoint URI in

`mq://local-queue-name?conn=mq-connection-resource-ref` format where

`local-queue-name` is the name of the local queue configured on the MQ server

`mq-connection-resource-ref` points to the location of the MQ connection resource

For example, if you create a MQ connection resource, `mqConnection` in the `defaultMQ` folder and the queue name is `testQueue`, the URI would be

`mq://testQueue?conn=defaultMQ/mqConnection`

**Note:** The Endpoint URI cannot contain spaces, so do not create MQ Connection resources or projects/folders with spaces in the names.

To configure the MQ transport for a business service, specify the values as described in the following table:

**Table 0-2 MQ Business Service Configuration**

<b>Option</b>	<b>To create or edit...</b>
Message Type	<p>This option is available only when the <b>Is Response Required</b> check box is selected.</p> <p>Select one of the following:</p> <ul style="list-style-type: none"> <li>• <b>Bytes</b> (for a stream of uninterpreted bytes)</li> <li>• <b>Text</b> (for text messages)</li> </ul>
Is Response Required	<p>Select this option to specify that a response is expected after an outbound message is sent.</p>
Polling Interval	<p>This option is available only when the <b>Is Response Required</b> check box is selected.</p> <p>Enter a polling interval, in milliseconds. The default is 1000.</p>
Response Correlation Pattern	<p>This option is available only when the <b>Is Response Required</b> check box is selected.</p> <p>Specify whether the response correlation pattern should be based on <b>MessageID</b> or <b>CorrelationID</b>.</p>
Auto-generate Correlation Value	<p>Select this check box to automatically generate a CorrelationID or MessageID.</p>
MQ Response URI	<p>This option is available only when the <b>Is Response Required</b> check box is selected.</p> <p>The destination to which the response should be published. Enter a response URI in the same format as the endpoint URI:  mq://&lt;local-queue-name&gt;?conn=&lt;mq-connection-resource-ref&gt;</p>
Response Timeout	<p>This option is available only when the <b>Is Response Required</b> check box is selected.</p> <p>Enter the number of seconds to wait for a response before dropping the connection.</p>

**Table 0-2 MQ Business Service Configuration (Continued)**

Option	To create or edit...
Dispatch Policy	<p>This option is available only when the <b>Is Response Required</b> check box is selected.</p> <p>Select a dispatch policy for this endpoint.</p> <p>Dispatch policy refers to the instance of WLS Work Manager that you want to use for the service endpoint. For information about work managers, see <a href="#">Using Work Managers to Optimize Scheduled Work</a> and <a href="#">Create Work Manager</a> in the WebLogic Server Administration Console Online Help.</p>
Endpoint URI 'PUT' options	<p>Enter the MQ PUT message options from among the following:</p> <ul style="list-style-type: none"> <li>• MQC.MQPMO_ALTERNATE_USER_AUTHORITY</li> <li>• MQC.MQPMO_DEFAULT_CONTEXT</li> <li>• MQC.MQPMO_FAIL_IF QUIESCING</li> <li>• MQC.MQPMO_LOGICAL_ORDER</li> <li>• MQC.MQPMO_NEW_CORREL_ID</li> <li>• MQC.MQPMO_NEW_MSG_ID</li> <li>• MQC.MQPMO_NO_CONTEXT</li> <li>• MQC.MQPMO_NO_SYNCPOINT</li> <li>• MQC.MQPMO_NONE</li> <li>• MQC.MQPMO_PASS_ALL_CONTEXT</li> <li>• MQC.MQPMO_PASS_IDENTITY_CONTEXT</li> <li>• MQC.MQPMO_RESOLVE_LOCAL_Q</li> <li>• MQC.MQPMO_SET_ALL_CONTEXT</li> <li>• MQC.MQPMO_SET_IDENTITY_CONTEXT</li> <li>• MQC.MQPMO_SYNCPOINT</li> <li>• MQC.MQPMO_VERSION_1</li> <li>• MQC.MQPMO_VERSION_2</li> </ul> <p>You can use either “ ” or “+” to separate multiple options. For example, you can specify the following:</p> <p>MQC.MQPMO_LOGICAL_ORDER   MQC.MQPMO_NEW_MSG_ID</p> <p>The MQ PUT message options are applied when the message is placed in the outbound queue.</p>

**Table 0-2 MQ Business Service Configuration (Continued)**

Option	To create or edit...
MQ Unrecognized Response URI	<p>Enter the URI representing the queue to which unrecognized response messages should be sent. Note that this setting is enabled only when the <b>Auto-generate Correlation Value</b> check box is selected.</p> <p>If you do not specify a value for this field, unrecognized response messages are deleted.</p>
Process RFH2 Headers	<p>Select this option to parse WebSphere MQ RFH2 headers from a message payload and automatically generate an RFH2Headers transport header containing the RFH2 data.</p> <p>If you do not select this option, the payload is passed through as received.</p>

For more information about configuring business services using MQ transport, see MQ Transport Configuration Page in [Business Services: Creating and Managing](#) in *Using the Oracle Service Bus Console*.

## Transport Headers

The various headers used by the MQ transport are listed in [Table 1-3](#). Most of the headers are common to both outbound requests and inbound response. The Reply To Queue Name, Reply To Queue Manager Name, User ID and Version headers can be edited only for the inbound response.

When you configure a proxy service, you can use a Transport Header action to set the header values in messages.

**Table 0-3 Transport Headers**

Header	Description	Inbound Response / Outbound Request
Accounting Token	<p>Accounting token is part of the identity context of the message.</p> <p><b>Inbound Transport Action:</b> No explicit processing is done by the transport. The header is copied to the transport header in the pipeline.</p> <p><b>Outbound Transport Action:</b> No explicit processing is done by the transport. If the corresponding transport header is set in the pipeline, it is copied to the request message.</p>	Both
Application ID Data	<p>Application ID data is part of the identity context of the message. This value can be used to provide additional information about the message or its originator.</p> <p><b>Inbound Transport Action:</b> No explicit processing is done by the transport. The header is copied to the transport header in the pipeline.</p> <p><b>Outbound Transport Action:</b> No explicit processing is done by the transport. If the corresponding transport header is set in the pipeline, it is copied to the request message.</p>	Both
Application Origin Data	<p>Data about the originating application. This value can be used by the application to provide additional information about the origin of the message.</p> <p><b>Inbound Transport Action:</b> No explicit processing is done by the transport. The header is copied to the transport header in the pipeline.</p> <p><b>Outbound Transport Action:</b> No explicit processing is done by the transport. If the corresponding transport header is set in the pipeline, it is copied to the request message.</p>	Both

Table 0-3 Transport Headers

Header	Description	Inbound Response / Outbound Request
Backout Count	<p>The number of times the message was returned by the MQ Queue, as part of a unit of work, and subsequently backed out.</p> <p><b>Inbound Transport Action:</b> No explicit processing is done by the transport. The header is copied to the transport header in the pipeline.</p> <p><b>Outbound Transport Action:</b> No explicit processing is done by the transport. If the corresponding transport header is set in the pipeline, it is copied to the request message.</p>	Both
Character Set	<p>The coded character set identifier of character data in the application message data.</p> <p><b>Inbound Transport Action:</b> This field is used by the inbound transport to convert data in a specific representation. For request-response messaging, the characterSet header from the request message is copied to the response. When this header is not configured on the incoming request, default value of the <code>MQC.MQCCSI_Q_MGR</code> field is assumed.</p> <p><b>Outbound Transport Action:</b> This header can be set in the pipeline for the outbound transport. If this header value is not set, the default <code>MQC.MQCCSI_Q_MGR</code> value is assumed.</p>	Both
Correlation ID	<p>The correlation-id of the message that should be retrieved.</p> <p><b>Inbound Transport Action:</b> For correlationID-based response correlation pattern, the correlationID from the request is echoed on the response. The user can override the correlationID in the response pipeline.</p> <p><b>Outbound Transport Action:</b> When the <b>Auto-generate correlationID</b> option is selected during service configuration, the outbound transport will automatically generate a correlationID and overwrite the correlationID from the transport header. If this value is not specified, the correlationID specified in the pipeline is used.</p> <p>For one-way messaging, the correlationID specified in the pipeline is used in the (outbound) request.</p>	Both

**Table 0-3 Transport Headers**

Header	Description	Inbound Response / Outbound Request
Encoding	<p>The representation used for numeric values in the application message data.</p> <p><b>Inbound Transport Action:</b> The inbound transport uses this header to interpret the incoming message data. If this header is not configured in the response pipeline, the default value of <code>MQC.MQENC_NATIVE</code> is used.</p> <p><b>Outbound Transport Action:</b> If this header is not set in the pipeline for the outbound transport, the default value of <code>MQC.MQENC_NATIVE</code> is used.</p>	Both
Expiry	<p>The expiry time (in tenths of a second) is set by the application that puts the message. After a message's expiry time has elapsed, it is eligible to be discarded by the queue manager.</p> <p><b>Inbound Transport Action:</b> For request-response messaging, the inbound transport copies the expiry header of the request to the response.</p> <p><b>Outbound Transport Action:</b> If the corresponding transport header is set in the pipeline, it is copied to the outbound request message.</p> <p><b>Note:</b> The report header will always contain the <code>MQC.MQRO_PASS_DISCARD_AND_EXPIRY</code> option (in addition to others). This option is a directive to the receiving client that the expiry time of the original message should be copied to the report or reply message.</p>	Both
Feedback	<p>The nature of the feedback report. This value is used with a message of type <code>MQC.MQMT_REPORT</code> to indicate the nature of the report.</p> <p><b>Inbound Transport Action:</b> No explicit processing is done by the transport. The header is copied to the transport header in the pipeline.</p> <p><b>Outbound Transport Action:</b> No explicit processing is done by the transport. If the corresponding transport header is set in the pipeline, it is copied to the request message.</p>	Both



Table 0-3 Transport Headers

Header	Description	Inbound Response / Outbound Request
Format	<p>Format name of the message data. The format name is used by the sender of the message to indicate the nature of the data in the message to the receiver.</p> <p><b>Inbound Transport Action:</b> When the field is set to <code>MQC.MQFMT_MD_EXTENSION</code>, the inbound transport will read the extended MQMD object.</p> <p><b>Outbound Transport Action:</b> No explicit processing is done by the transport. If the corresponding transport header is set in the pipeline, it is copied to the request message.</p>	Both
Group ID	<p>The value that identifies the message group to which the physical message belongs.</p> <p><b>Inbound Transport Action:</b> No explicit processing is done by the transport. The header is copied to the transport header in the pipeline.</p> <p><b>Outbound Transport Action:</b> No explicit processing is done by the transport. If the corresponding transport header is set in the pipeline, it is copied to the request message.</p>	Both
Offset	<p>In a segmented message, offset of data in the physical message from the start of the logical message.</p> <p><b>Inbound Transport Action:</b> No explicit processing is done by the transport. The header is copied to the transport header in the pipeline.</p> <p><b>Outbound Transport Action:</b> No explicit processing is done by the transport. If the corresponding transport header is set in the pipeline, it is copied to the request message.</p>	Both
Original Length	<p>Original length of a segmented message.</p> <p><b>Inbound Transport Action:</b> No explicit processing is done by the transport. The header is copied to the transport header in the pipeline.</p> <p><b>Outbound Transport Action:</b> No explicit processing is done by the transport. If the corresponding transport header is set in the pipeline, it is copied to the request message.</p>	Both

**Table 0-3 Transport Headers**

Header	Description	Inbound Response / Outbound Request
Message Flags	<p>Flags that control the segmentation and status of a message.</p> <p><b>Inbound Transport Action:</b> No explicit processing is done by the transport. The header is copied to the transport header in the pipeline.</p> <p><b>Outbound Transport Action:</b> No explicit processing is done by the transport. If the corresponding transport header is set in the pipeline, it is copied to the request message.</p>	Both
Message ID	<p>ID of the message to be retrieved.</p> <p><b>Inbound Transport Action:</b> If messageID is not specified in the response pipeline, the messageID header is set to <code>MQC.MQMI_NONE</code>.</p> <p>For messageID-based correlation, the inbound transport copies the messageID from the request to the correlationID header of the response. MessageID-based correlation is assumed when the report header contains the <code>MQC.MQRO_COPY_MSG_ID_TO_CORREL_ID</code> option.</p> <p><b>Outbound Transport Action:</b> When the Auto-generate messageID option is specified during service configuration, the outbound transport automatically generates the messageID and overwrites the messageID from the transport header. If this value is not specified, the messageID transport header is used.</p> <p>For one-way messaging, the messageID specified in the pipeline is used in the outbound request. If this value is not specified, the messageID is automatically generated by the transport.</p>	Both
Message Sequence Number	<p>Sequence number of a logical message within group.</p> <p><b>Inbound Transport Action:</b> No explicit processing is done by the transport. The header is copied to the transport header in the pipeline.</p> <p><b>Outbound Transport Action:</b> No explicit processing is done by the transport. If the corresponding transport header is set in the pipeline, it is copied to the request message.</p>	Both

Table 0-3 Transport Headers

Header	Description	Inbound Response / Outbound Request
Message Type	<p>Message type of the message.</p> <p><b>Inbound Transport Action:</b> The inbound transport reads and processes messages of any type including <code>MQC.MQMT_REQUEST</code>, <code>MQC.MQMT_DATAGRAM</code>, <code>MQC.MQMT_REPLY</code> and <code>MQC.MQMT_REPORT</code>. The inbound transport does not generate report messages.</p> <p><b>Outbound Transport Action:</b> The outbound transport generates messages of any type including <code>MQC.MQMT_DATAGRAM</code>, <code>MQC.MQMT_REQUEST</code>, <code>MQC.MQMT_REPLY</code> and <code>MQC.MQMT_REPORT</code>. When the <code>messageType</code> header is not configured in the pipeline, the transport generates messages of type <code>MQC.MQMT_DATAGRAM</code> when the messaging pattern is one-way and <code>MQC.MQMT_REQUEST</code> when the messaging pattern is request-reply.</p>	Both
Persistence	<p>The message persistence.</p> <p><b>Inbound Transport Action:</b> No explicit processing is done by the transport. The header is copied to the transport header in the pipeline.</p> <p><b>Outbound Transport Action:</b> No explicit processing is done by the transport. If the corresponding transport header is set in the pipeline, it is copied to the request message.</p>	Both
Priority	<p>Priority of the message</p> <p><b>Inbound Transport Action:</b> No explicit processing is done by the transport. The header is copied to the transport header in the pipeline.</p> <p><b>Outbound Transport Action:</b> No explicit processing is done by the transport. If the corresponding transport header is set in the pipeline, it is copied to the request message.</p>	Both

**Table 0-3 Transport Headers**

Header	Description	Inbound Response / Outbound Request
Put Application Name	<p>The name of the application that put the message.</p> <p><b>Inbound Transport Action:</b> No explicit processing is done by the transport. The header is copied to the transport header in the pipeline.</p> <p><b>Outbound Transport Action:</b> No explicit processing is done by the transport. If the corresponding transport header is set in the pipeline, it is copied to the request message.</p>	Both
Put Application Type	<p>The type of the application that put the message.</p> <p><b>Inbound Transport Action:</b> No explicit processing is done by the transport. The header is copied to the transport header in the pipeline.</p> <p><b>Outbound Transport Action:</b> No explicit processing is done by the transport. If the corresponding transport header is set in the pipeline, it is copied to the request message.</p>	Both
Put Date Time	<p>The time and date when the message was put.</p> <p><b>Inbound Transport Action:</b> No explicit processing is done by the transport. The header is copied to the transport header in the pipeline.</p> <p><b>Outbound Transport Action:</b> No explicit processing is done by the transport. If the corresponding transport header is set in the pipeline, it is copied to the request message.</p>	Both

Table 0-3 Transport Headers

Header	Description	Inbound Response / Outbound Request
Reply To Queue Name	<p>The name of the queue to which a reply should be sent.</p> <p>The application that issued the get request for the message can send <code>MQC.MQFMT_REPLY</code> and <code>MQC.MQFMT_REPORT</code> messages to this queue.</p> <p><b>Inbound Transport Action:</b> The inbound transport uses the <code>replyToQueueName</code> as the response queue name when this field is set. If this values is not set, the queue name is derived from the default destination URI.</p> <p><b>Outbound Transport Action:</b> In request/response message pattern, <code>replyToQueueName</code> set in the message flow is ignored. In one way message pattern, <code>replyToQueueName</code> set in the message flow is used in the outbound messages.</p>	Inbound Response
Reply To Queue Manager Name	<p>The name of the queue manager to which reply or report messages can be sent.</p> <p><b>Inbound Transport Action:</b> In request/response message pattern, if the inbound message <code>replyToQueueManager</code> header value does not match the configured value for the queue manager in the response URI, the response message is dropped and a transport error is logged.</p> <p><b>Outbound Transport Action:</b> In request/response message pattern, <code>replyToQueueManager</code> set in the message flow is ignored. In one way message pattern, <code>replyToQueueManager</code> set in the message flow is used in the outbound messages.</p>	Inbound Response

**Table 0-3 Transport Headers**

Header	Description	Inbound Response / Outbound Request
Report	<p>A report is a message about another message. This field enables the application sending the original message to specify which report messages are required, whether the application message data is to be included in them, and also how the message and correlation ID in the report or reply are to be set. It comprises one or more constants from the MQC class combined by means of the '+' or ' ' operators.</p> <p><b>Inbound Transport Action:</b> No explicit processing is done by the transport. The header is copied to the transport header in the pipeline. For request-response messaging, this header can be configured in the response pipeline.</p> <p><b>Outbound Transport Action:</b> The transport always sets a combination of the following options in the report field.</p> <p>Set <code>MQC.MQRO_COPY_MSG_ID_TO_CORREL_ID</code> if messageID-based correlation pattern is used and <code>MQC.MQRO_PASS_CORREL_ID</code> if correlationID-based correlation pattern is used. Always set <code>MQC.MQRO_PASS_DISCARD_AND_EXPIRY</code>.</p> <p><b>Note:</b> These options are set in addition to the options specified on the corresponding transport header in the pipeline.</p>	Both
User ID	<p>It is part of the identity of the message and identifies the user who originated the message.</p> <p><b>Inbound Transport Action:</b> No explicit processing is done by the transport. The header is copied to the transport header in the pipeline.</p> <p><b>Outbound Transport Action:</b> No explicit processing is done by the transport. If the corresponding transport header is set in the pipeline, it is copied to the request message.</p>	Inbound Response

**Table 0-3 Transport Headers**

Header	Description	Inbound Response / Outbound Request
Version	<p>The version number of the message descriptor.</p> <p><b>Inbound Transport Action:</b> The inbound transport supports both version 1 and version 2 message descriptors.</p> <p><b>Outbound Transport Action:</b> By default, the outbound transport generates version 2 headers. However, this field can be overridden in the pipeline.</p>	Inbound Response
RFH2Headers	<p>The RFH2 headers in the payload when the Process RFH2 Headers option is set in the transport configuration. The RFH2Headers header is a String.</p> <p><b>Inbound Transport Action:</b> RFH2 headers are extracted from the MQ payload to construct the corresponding transport metadata header.</p> <p><b>Outbound Transport Action:</b> RFH2Headers data are parsed to extract the RFH2 headers, which are inserted (along with the content length for each header) into the outbound MQ payload.</p>	Both

## Configuring Transport Headers

You can configure the transport headers for both inbound and outbound requests in the Message Flow. For information about the transport headers related to the MQ transport, see [Transport Headers](#).

In the message flow, use a Transport Header action to set the header values in messages. For more information, see [Adding Transport Header Actions](#) in *Using the Oracle Service Bus Console*.

When the transport header is explicitly set in the message flow, this value overrides the header value except in the following scenarios:

- For the outbound request-response pattern, when the `Auto-generate Correlation Value` option is selected for a outbound request with a request-response message pattern, the correlation ID is always generated even if this value is set in the message flow.
- When the report header is set in the message flow, the combination of multiple directives associated with the report header are merged with the default directives.

- When the `replyToQueueManagerName` or `replyToQueueName` headers are set in the message flow for an outbound request with a request/response message pattern, these values are ignored. Instead, these transport header values are derived from the response URI configured for the business service.
- For the inbound response, when the value in the `replyToQueueManagerName` header does not match the queue manager name specified in the response URI, an error message is generated and the response message is not sent.
- The `replyToQueueName` set in the inbound request header overrides the value configured in the reply to URI for the proxy service.
- For a one-way business service, when the message type header is configured to be of type request in the message flow, the `replyToQueueName` header must be specified. If this value is not specified, an error is generated on the MQ server and the message is rolled back.

### About RFH2 Headers

RFH2Header headers can contain multiple `<RFH2Header>` blocks, each of which can contain multiple folders. For example:

```
<RFH2Header>
  <mcd><Msd>jms_bytes</Msd></mcd>
</RFH2Header>
<RFH2Header>
  <usr><clientId>DASHBOARD</clientId></usr>
</RFH2Header>
```

## Error Handling

You can configure MQ-transport business services to handle application and communications errors as follows:

- Application errors – You can specify whether or not to retry business service endpoint URIs when application errors occur. For more information, see [Retry Application Errors](#) in “Creating and Configuring Business Services - Transport Configuration page” in *Using the Oracle Service Bus Console*.
- Communication errors – You can configure business service URIs to be taken offline when communication errors occur. For more information, see Enable business service endpoint URIs to be taken offline in Table 23-8 in [Configuring Operational Settings for Business](#)



[Services](#) and [Viewing Business Services Endpoint URIs Metrics](#) in *Using the Oracle Service Bus Console*.

For more information on error messages, see [Index of Error Messages by Range](#).

## Limitations of the MQ Transport

The following are the limitations of the MQ transport:

- MQ transport does not support
  - XA for the MQ transport. For more information, see [Using the WebSphere JMS MQ Interface](#).
  - Defining MQ exits.
- You cannot call a request-response proxy service based on MQ proxy service:
  - From a proxy service that has been configured with a route action or dynamic routing and routing table actions).
  - Using the service callout action.
- You cannot call a proxy service with a service callout where the target is a request-response proxy service based on MQ transport.
- You cannot use an indirect call to a request-response MQ proxy service in the Oracle Service Bus test console.

# Using the WebSphere JMS MQ Interface

The WebSphere MQ for Java APIs do not support XA transactions. Consequently, Oracle Service Bus does not support XA transactions for the MQ transport. If XA is required, you can use the WebSphere MQ JMS interface.

The following sections outline how Oracle Service Bus connects to WebSphere MQ and presents an overview of some message types used in communication between WebSphere MQ and Oracle Service Bus.

- [Using the WebSphere MQ JMS Interface](#)
- [Messaging Types](#)
- [Tuning WebSphere MQ](#)

## Using the WebSphere MQ JMS Interface

Oracle Service Bus connects to WebSphere MQ via the WebSphere MQ JMS interface. That is, Oracle Service Bus is a WebSphere MQ JMS client.

The foreign JMS server in WLS specifies the initial context factory, connection factory, and queue to the WebSphere MQ server. For more information, see [Configuring Foreign Server Resources to Access Third-Party JMS Providers](#) in *Configuring and Managing WebLogic JMS*.

WebSphere MQ JMS supports two transport types:

- BINDINGS
- CLIENT

If the WebSphere MQ JMS client is running on the same physical machine as the queue manager, it is possible to set the transport type to BINDINGS. Otherwise, you can use only the CLIENT type.

WebSphere MQ can interface with Oracle Service Bus in two ways:

- Oracle Service Bus acts as the front-end of WebSphere MQ to accept service requests from other applications and converts them to WebSphere MQ requests. See [Figure 3-1](#).
- WebSphere MQ sends messages to other applications through Oracle Service Bus. See [Figure 3-2](#).

**Figure 3-1 Oracle Service Bus Front End**



**Figure 3-2 Messages sent through Oracle Service Bus**



Oracle Service Bus is configured in the Oracle Service Bus Console, which is described in [Using the Oracle Service Bus Console](#).

## Messaging Types

Oracle Service Bus supports the following messaging types:

- [Non-Persistent Messaging](#)
- [Non-XA Persistent Messaging](#)
- [XA Messaging](#)

## Non-Persistent Messaging

If you decide to accept an unreliable delivery, such as some missing requests, you can use non-persistent messages where appropriate. WebSphere MQ logging and WebLogic JMS message persistence are only performed for persistent messages; therefore, the use of non-persistent messages eliminates any related I/O activity.

**Note:** Non-persistent message throughput is usually limited by the processor speed of the machine. However, in case of a shortage of physical memory, the server system may consume CPU cycles on a paging I/O.

## Non-XA Persistent Messaging

WebSphere MQ persistent message throughput is usually limited by the queue manager and the I/O latency writing to the log.

## XA Messaging

To enable support for transactional (XA) access to queues, use:

- **BINDINGS** to access the queue manager when Oracle Service Bus is co-located with IBM WebSphere MQ
- **CLIENT** when Oracle Service Bus and IBM WebSphere MQ are on different machines. However, with **CLIENT**, you need a special version of the IBM WebSphere MQ client that supports XA transactions, called the WebSphere MQ Extended Transaction Client.

---

**Tip:** For the deployment descriptors to be set appropriately for XA capable resources (JMS, TUXEDO, EJB), you must set the XA attribute on the referenced connection factory before creating a proxy service.

---

## Tuning WebSphere MQ

The following guidelines help you tune WebSphere MQ when you are working with Oracle Service Bus. For detailed WebSphere MQ information, refer to relevant WebSphere MQ documentation.

- Use the BINDINGS transport type if Oracle Service Bus and the queue manager are deployed on the same machine.
- If you need XA for only a small section of application requests, create a separate connection object and disable XA.
- Distribute active logs across many volumes. If your system is required to handle high persistent message throughput, you must place the log files on a fast Direct Access Storage Device (DASD) with a minimum of contention from other data set usage. Ideally, you can allocate each of the active logs on separate, low-usage volumes.
- To reduce buffer overflow, tune the buffer pools and pagesets. Buffer overflow results in flushing of the hard disk.
- To avoid broken Oracle Service Bus JMS connections to MQ queues, increase the number of active channels to more than 100. By default, the number of active channels is 10.