

Oracle
Primavera
P6 EPPM Database Administration Guide for On-Premises

Version 20
December 2020

Contents

About This Guide.....	7
About Database Users	7
Migrating Databases and Database Schema	9
Using the Migrate Database Wizard.....	9
Running a Schema Validation on the Database	9
Running the Migrate Database Wizard.....	10
Running the Migrate Database Wizard From the Command Line	11
Migrating Database Schema	12
Prerequisites for Schema Migration	12
Migrating P6 EPPM Schema to P6 Professional with Oracle	12
Migrating P6 EPPM Schema to P6 Professional with Microsoft SQL Server.....	13
Creating and Updating P6 EPPM Configurations.....	15
Creating P6 EPPM Configurations.....	15
Updating P6 EPPM Configurations	16
Setting Up the P6 EPPM Database.....	17
Installing a P6 EPPM Database with Oracle	17
Installing a P6 EPPM Database with Microsoft SQL Server.....	18
Upgrading a P6 EPPM Database with Oracle Database	19
Upgrading a P6 EPPM Database with Microsoft SQL Server.....	20
Changing the Database Base Currency.....	21
The Base Currency	21
Reviewing Currency Choices.....	21
Changing the Base Currency	21
Private Database Credentials for P6 EPPM.....	22
Resetting Private Database Passwords	22
Adding Private Database Logins for P6 EPPM.....	23
Modifying Private Database Logins for P6 EPPM.....	23
Deleting Private Database Logins for P6 EPPM	24
Setting Up Cloud Sync	27
Synchronizing data from P6 EPPM to Oracle Primavera Cloud	27
Synchronizing data from Oracle Primavera Cloud to P6 EPPM.....	33
Configuring Background Processes and Jobs.....	39
RDBMS Scheduler Configuration	39
Database Settings Table.....	39
Reading Setting Values	40
Using Code to Read Setting Values with Oracle.....	40

Using Code to Read Setting Values with Microsoft SQL Server	41
Writing Setting Values	41
Using Code to Write Setting Values with Oracle	41
Using Code to Write Setting Values with Microsoft SQL Server	41
Tracking Background Job Execution	42
High Level Status Settings	42
The BGPLOG Table	42
Monitoring Processes and Procedures	45
PAUDIT Auditing	45
Auditing Level Configuration	45
Simple Configuration	45
Detailed Configuration	46
Auditing Status	46
Options Setting	47
SETTINGS_WRITE_STRING Procedure	48
The Audit Table	48
Session Auditing	50
Column Audit Data	50
Tuning the P6 EPPM Database	51
Oracle Database Tuning	51
Partitioning Oracle Database Tables for P6 EPPM Schema	51
Gathering Statistics for Cost Based Optimizations	53
Viewing the USESSION Table for GET_SAFETY_DATE	53
Rebuilding the P6 EPPM Index Table	54
Where to Find Additional Oracle Database Tuning Information	54
Microsoft SQL Server Database Tuning	55
Where to Find Additional Microsoft SQL Server Database Tuning Information	55
Isolating Snapshots	55
Rebuilding the P6 EPPM Index	55
Gathering Statistics	56
General Tuning	57
Background Processes and Clean Up in P6 EPPM	57
SYMON (System Monitor) Procedures	57
OBSPROJ_PROCESS_QUEUE Procedure	58
USESSION_CLEANUP_EXPIRED Procedure	58
Tracking Concurrent Usage of P6 EPPM	60
DAMON (Data Monitor) Procedures	61
BGPLOG_CLEANUP Procedure	61
CLEANUP_DBERRLOG Procedure	62
REFRDEL_CLEANUP Procedure	62
REFRDEL Bypass Procedure	63
CLEANUP_PRMQQUEUE Procedure	63
USESSION_CLEAR_LOGICAL_DELETES Procedure	65

CLEANUP_LOGICAL_DELETES Procedure	65
PAUDIT_CLEANUP Procedure.....	66
CLEANUP_USESSAUD Procedure	67
USER_DEFINED_BACKGROUND Procedure.....	68
PX Tables Clean Up Procedure	68
Safe Deletes	69
Turning Off Safe Deletes	69
Copyright.....	71

About This Guide

Scope

This guide describes how to:

- ▶ Migrate your P6 EPPM databases between Microsoft SQL Server database and Oracle database or your database schema between P6 EPPM and P6 Professional.
- ▶ Create or update configurations for the Primavera P6 Administrator using dbconfig.
- ▶ Configure database settings and the scheduler for background processes and jobs.
- ▶ Monitor processes and procedures using PAUDIT audit, BGPLOG table, or high level statuses.
- ▶ Perform database maintenance tasks using the SYMON and DAMON utilities.

Audience

Database administrators should use this guide.

Using This Guide

This guide assumes you can perform common database administration procedures and have experience using the command line.

About Database Users

Schema User (Oracle database only)

Default: ADMUSER

Description: The administrative user owns most database objects within the schema including tables, indexes and constraints, procedures, triggers, and functions, and is primarily used during database creation and upgrades.

Privileged User

Default: PRIVUSER

Description: The following is true for the privileged user:

- ▶ Owns views to most of the schema user tables that filter out logically deleted data.
- ▶ Has SELECT, INSERT, UPDATE, and DELETE privileges on all of the tables owned by the schema user.
- ▶ Has EXECUTE privileges on all schema procedures.
- ▶ Is used to facilitate communication between P6 EPPM and P6 Professional.
- ▶ Owns the synonyms for objects that do not have a view, which means that references to tables that are owned by the schema owner do not have to be fully qualified (Oracle database only).

Public User

Default: PUBUSER

Description: The public user has few permissions in the P6 EPPM database. It has SELECT privileges on the PUBUSER table, which is used to connect a P6 EPPM to the database.

Background Job User (Oracle database only)

Default: BGJOBUSER

Description: The background job user initiates and runs P6 EPPM background jobs.

Reporting User

Default: PXRPTUSER

Description: The reporting user owns views to the P6 EPPM extended schema for enterprise reporting.

Read-Only Administrative User (Oracle database only)

Default: ROADMUSER

Description: The read-only user has read-only access to the tables owned by the schema user. The read-only user has the same views as reporting user.

Migrating Databases and Database Schema

Migrate.bat is a java-based tool that enables you to migrate data between Microsoft SQL Server database and Oracle database as well as database schema between P6 EPPM and P6 Professional. Migrate.bat launches the Migrate Database wizard.

For more information about migrating data between databases, see **Using the Migrate Database Wizard** (on page 9).

For more information about migrating database schema from P6 EPPM to P6 Professional, see **Migrating Database Schema** (on page 12).

In This Section

Using the Migrate Database Wizard	9
Migrating Database Schema	12

Using the Migrate Database Wizard

The Migrate Database wizard is a java-based tool that enables you to migrate data from a Microsoft SQL Server database to an Oracle database.

Use the Migrate Database wizard to:

- ▶ Import data into a newly created database.
- ▶ Repair a damaged database to correct database object issues (such as constraints or views).

Do **not** use the Migrate Database wizard to:

- ▶ Convert the database type from EPPM to PPM or from PPM to EPPM.
- ▶ Upgrade from one database version to another.
- ▶ Import data into an existing database.
- ▶ Correct data-specific issues.
- ▶ Correct schema-related issues. It is not ideal for large databases (more than 10 GB) due to the performance of the wizard. For larger databases, try first to manually resolve schema-related issues.

Before running the Migrate Database wizard, you must first run a schema validation on the database. See **Running a Schema Validation on the Database** (on page 9) for details.

Running a Schema Validation on the Database

The schema validation utility finds missing, extra, and modified schema objects for a P6 database.

To run a schema validation, complete the following steps:

- 1) In the software download, locate the utility in the **Database Download** folder.

2) Edit the utility similar to the following:

```
@echo off
REM -----
REM Run the Primavera Schema Validation Tool
REM -----

SET JAR_FILE_DIR=lib
SET JAR_FILE_NAME=dbmt.jar
SET DB_SCHEMA=ppm

SET JVM_PROPERTIES=-Ddbmt.dbschema.package.location=%JAR_FILE_DIR%
-Dprimavera.db.schema=%DB_SCHEMA%
-Dcom.primavera.database logfile=SchemaValidation.log
SET DBMT_ACTION=application/ppmschemaaval
SET DBMT_COMMAND=schemaavalpm
set JAVA_HOME=C:\Program Files\Java\jre6
IF NOT EXIST "%JAVA_HOME%\bin\java.exe" (
    echo JAVA_HOME IS NOT SET
    pause
    goto :EXIT
)
```

3) Run `validate.bat` (with Windows) or `validate.sh` (with UNIX or Linux).

4) With an Oracle database in an Enterprise environment, enter values for the following:

- ▶ **Username:** Use the appropriate ADMUSER username and password.
- ▶ **Database host address:** Database server name or IP address.
- ▶ **Database host port:** The port your Oracle listener is listening on. The default port is 1521.
- ▶ **Database name (SID):** Enter the Oracle SID for your database.

With a Microsoft SQL Server database, enter values for the following:

- ▶ **Database host address:** Database server name or IP address.
- ▶ **Database host port:** The SQL port.
- ▶ **Database name:** pmdb\$primavera (default)

Note: When running for an Enterprise version of the database, you will be prompted for the appropriate privileged and public usernames.

5) Review the results of the schema validation utility that display in the browser.

Running the Migrate Database Wizard

To run the migrate database wizard, complete the following steps:

Note: Skip the first two steps if you are using a Microsoft SQL Server Database.

1) From the command line, run the following and provide the password when prompted:

```
sqlplus sys@<db_tns_names_entry> as sysdba
```

- 2) Go to p6suite\database\scripts\install\PM_<release_level>, and run **manual_script_before_install.sql**.
- 3) Go to the <P6_EPPM_Home>\database folder.
- 4) Run migrate.bat (with Windows) or migrate.sh (with UNIX or Linux).
- 5) Follow the prompts on each screen to provide connection information for the source database and the target database.

Note: When using an Oracle schema, the migrate database wizard allows you to create new tables or use existing tables in the target instance, but new schema users must be created through the migration process. The ability to map to existing schema users is not currently available through the migration process.

Running the Migrate Database Wizard From the Command Line

Note: Do not use the migrate database wizard to convert the database type from EPPM to PPM or from PPM to EPPM.

To run the migrate database wizard from the command line, complete the following steps:

- 1) Open a new command line console.
- 2) Go to \install\database.
- 3) Run the command with the following parameters to define the migration:

With Windows

```
migrate.bat -source sa/sa@sqlserver:rcgsrv:1433:vader_pmdb -target
system/manager@oracle:rcgsrv:1521:rcg02 -db PM
```

With Windows (Creating Non-Default Oracle Users)

```
migrate.bat -source sa/sa@sqlserver:rcgsrv:1433:vader_pmdb -target
system/manager@oracle:rcgsrv:1521:rcg02 -db PM -<admuser> <admuser password>
-<privuser> <privuser password> -<pubuser> <pubuser password>
```

With UNIX or Linux

```
sh migrate.sh -source sa/sa@sqlserver:saumverm-lap\primavera:1433:PMDB -dattbsp
<Name of data tblspc at target> -ndxtbsp <Name of index tblspc at target> -pxtbsp
<Name of px tblspc at target> -lobtbsp <Name of LOB tblspc at target> -<admuser>
<admuser at target> -<admuser password> <admuser password at target> -<privuser>
<privuser at target> -<privuser password> <privuser password at target> -pubuser
<pubuser at target> -<pubuser password> <pubuser password at target> -<pxrptuser>
<pxrptuser at target> -<pxrptuser password> <pxrptuser password at target>
-<bgjobuser> <bgjobuser at target> -<bgjobuser password> <bgjobuser password at
target> -target system/admin@oracle:oldb-orcl:1521:PMDB
```

For example:

```
sh migrate.sh -source sa/sa@sqlserver:saumverm-lap\primavera:1433:PMDB -dattbsp
PMDB_DAT1 -ndxtbsp PMDB_NDX1 -pxtbsp PMDB_PX_DAT1 -lobtbsp PMDB_LOB1 -admuser
admuser -admpass admuser -privuser privuser -privpass privuser -pubuser pubuser
-pubpass pubuser -pxrptuser pxrptuser -pxrptpass pxrptuser -bgjobuser bgjobuser
-bgjobpass bgjobuser -target system/admin@oracle:oldb-orcl:1521:PMDB
```

Migrating Database Schema

The schema migration process creates a copy of an existing source P6 EPPM or P6 Professional database and then modifies the database objects for the target database. Because the source database is not being modified, you do not need to backup your database before attempting to migrate your schema.

Tip: You should migrate your schema at a time when no database transactions occur.

Prerequisites for Schema Migration

In order to migrate schema between P6 EPPM and P6 Professional, you must be on the same version of both applications.

If you are using an Oracle database, ensure that you have completed the following prerequisites before attempting to migrate your schema:

- ▶ Create an empty Oracle database for your target database.
- ▶ Set the `open_cursors` system parameter to a value of 1000 or greater depending on the size of your source database.
- ▶ Run the `manual_script_before_install.sql` script from the P6 EPPM or P6 Professional installation folder on your target database. Alternatively, if you are migrating your schema to P6 Professional, you can run the following script on the P6 Professional database:

```
GRANT SELECT ON sys.DBA_EXTENTS
TO SYSTEM with grant option;
```

If you are using Microsoft SQL Server, you must enable FILESTREAM.

Migrating P6 EPPM Schema to P6 Professional with Oracle

To migrate your P6 EPPM schema to P6 Professional:

- 1) Open the **Migrate Database** wizard by completing the following:
 - a. Navigate to the database folder of your P6 EPPM installation. For example, `C:\P6EPPM_1\database\` (with Windows) or `/u01/P6EPPM_1/database/` (with UNIX or Linux).
 - b. Run **migrate.bat** (with Windows) or **migrate.sh** (with UNIX or Linux).

Note: After each step, click **Next**.

- 2) On the **Select Migration Type** screen, select **Schema Migration**.
- 3) On the **Select Source** screen, select **Oracle**.
- 4) On the **Connection Information** screen, enter the connection details for the source database and private database user.
- 5) On the **Select Target** screen, select **Oracle**.
- 6) On the **Connection Information** screen, enter the connection details for the target database and system database user.
- 7) On the **Configure Oracle Tablespaces** screen, complete one of the following steps:
 - ▶ If you want to use the existing P6 EPPM tablespaces for P6 Professional, select **Use existing tablespaces** and then select the tablespace names from the lists.
 - ▶ If you want to create new tablespaces for P6 Professional, enter the tablespace names and sizes in the **tablespace name** and **tablespaces size (M)** fields.

Note: If you chose to use an existing tablespace, skip the next step.

- 8) On the **Specify Oracle Tablespace Location** screen, enter the location at which you want to create each tablespace and then click **Create**.
- 9) On the **Create Oracle Users** screen, in the **User Name**, **Password**, and **Confirm Password** fields, enter the credentials for each database user.
- 10) On the **Migrate Options** screen, enter the size of the batch that will be used for the SQL insert of P6 data into the P6 Professional database.

Migrating P6 EPPM Schema to P6 Professional with Microsoft SQL Server

To migrate your P6 EPPM schema to P6 Professional:

- 1) Open the **Migrate Database** wizard by completing the following:
 - a. Navigate to the database folder of your P6 EPPM installation. For example, C:\P6EPPM_1\database\ (with Windows) or /u01/P6EPPM_1/database/ (with UNIX or Linux).
 - b. Run **migrate.bat** (with Windows) or **migrate.sh** (with UNIX or Linux).

Note: After each step, click **Next**.

- 2) On the **Select Migration Type** screen, select **Schema Migration**.
- 3) On the **Select Source** screen, select **Microsoft SQL Server**.
- 4) On the **Connection Information** screen, enter the connection details for the source SQL Server database and the administrative database user.
- 5) On the **Select Target** screen, select **Microsoft SQL Server**.
- 6) On the **Connection Information** screen, enter the connection details for the target SQL Server database and the sys admin database user.
- 7) On the **Configure Database Users** screen, complete one of the following steps:

- ▶ If you want to use the existing P6 EPPM users for P6 Professional, complete the following:
 - a. Select the **Use Existing** check box.
 - b. In each **User Name** list, select the username of the database user.
 - c. In each **Password** field, enter the password for each database user.
 - ▶ If you want to create database users for P6 Professional, enter the login credentials for each database user in the **User Name**, **Password**, and **Confirm Password** fields.
- 8) On the **Configure Microsoft SQL Server/SQL Express Database** screen, enter the required information in the **Database name**, **Data file**, **Log file**, and **Database code page** for the P6 Professional schema.
- 9) On the **Migrate Options** screen, enter the size of the batch that will be used for the SQL insert of P6 data into the P6 Professional database.

Creating and Updating P6 EPPM Configurations

The utility that you can use to create or update the configuration settings for P6 EPPM in Primavera P6 Administrator is the Database Configuration Wizard.

When either creating or updating P6 EPPM configurations, the Database Configuration Wizard updates the `admin_config` table in the P6 EPPM database and modifies the `BREBootStrap.xml` file.

The Database Configuration Wizard can be accessed by running `dbconfigpv.bat` (with Windows) `dbconfigpv.sh` (with UNIX or Linux) at `<P6_EPPM_Home>/p6`.

Where: `<P6_EPPM_Home>` is the P6 EPPM home directory that was set during installation.

For more information about creating configurations, refer to ***Creating P6 EPPM Configurations*** (on page 15).

For more information about updating configurations, refer to ***Updating P6 EPPM Configurations*** (on page 16).

In This Section

Creating P6 EPPM Configurations	15
Updating P6 EPPM Configurations.....	16

Creating P6 EPPM Configurations

You would want to create a configuration if you are manually installing and configuring P6 EPPM for the first time, or if you want to create additional configurations other than the one created by the P6 EPPM Configuration Wizard. The default name of the configuration created by the P6 EPPM Configuration Wizard is "Primavera P6 Configuration".

To create a P6 EPPM configuration:

- 1) Run **`dbconfigpv.bat`** (with Windows) **`dbconfigpv.sh`** (with UNIX or Linux) at `<P6_EPPM_Home>/p6`. The **Database Configuration Wizard** opens.

Where: `<P6_EPPM_Home>` is the P6 EPPM home directory that was set during installation.

Note: Click **Next** after each of the following steps.

- 2) On the **Setup and Configuration of the Primavera P6 Database** screen, select Microsoft SQL Server.
- 3) On the **Please enter the following information...** screen, enter the public user credentials and the connection details for your database. The default public username is `pubuser`.

- 4) On the **What would you like to do?** screen, select **Create a new configuration** and enter a name for the configuration in the field.
- 5) On the **Configuration of the Primavera P6 database completed successfully** screen, click **OK**.

Updating P6 EPPM Configurations

You would want to update your P6 EPPM configurations using the Database Configuration Wizard if you are manually upgrading P6 EPPM from an earlier release to the current release.

To update an existing P6 EPPM configuration:

- 1) Run **dbconfigpv.bat** (with Windows) **dbconfigpv.sh** (with UNIX or Linux) at `<P6_EPPM_Home>/p6`. The **Database Configuration Wizard** opens.

Where: `<P6_EPPM_Home>` is the P6 EPPM home directory that was set during installation.

Note: Click **Next** after each of the following steps.

- 2) On the **Setup and Configuration of the Primavera P6 Database** screen, select your database.
- 3) On the **Please enter the following information...** screen, enter the public user credentials and the connection details for your database. The default public username is `pubuser`.
- 4) On the **What would you like to do?** screen, select **Use an Existing configuration** and then select a configuration from the drop down list.
- 5) On the **Configuration of the Primavera P6 database completed successfully** screen, click **OK**.
- 6) Repeat the previous steps to update other configurations to the current release.

Setting Up the P6 EPPM Database

Use the Primavera Database Setup Wizard to install or upgrade the P6 EPPM database.

For more information about installing a P6 EPPM database, see ***Installing a P6 EPPM Database with Oracle*** (on page 17) or ***Installing a P6 EPPM Database with Microsoft SQL Server*** (on page 18).

For more information about upgrading a P6 EPPM database, see ***Upgrading a P6 EPPM Database with Oracle Database*** (on page 19) or ***Upgrading a P6 EPPM Database with Microsoft SQL Server*** (on page 20).

In This Section

Installing a P6 EPPM Database with Oracle	17
Installing a P6 EPPM Database with Microsoft SQL Server.....	18
Upgrading a P6 EPPM Database with Oracle Database.....	19
Upgrading a P6 EPPM Database with Microsoft SQL Server	20

Installing a P6 EPPM Database with Oracle

If you want to manually install P6 EPPM, you should install a P6 EPPM database using the Primavera Database Setup Wizard.

To install a P6 EPPM database using the Primavera Database Setup Wizard:

- 1) To open the Primavera Database Setup Wizard, run **dbsetup.bat** (with Windows) **dbsetup.sh** (with UNIX or Linux) at `<P6_EPPM_Home>/database` where `<P6_EPPM_Home>` is the P6 EPPM home directory that was set during installation.

Note: Click **Next** after each of the following steps.

- 2) On the **Primavera P6** screen, complete the following:

- a. Select **Install a new database**.
- b. Select **Oracle**.

Note: **Create Read Only User** is only intended for use with cloud installations of the application.

- 3) On the **Connection Information** screen, enter the connection details for an Oracle database using system credentials.
- 4) On the **Create New Keystore** screen, complete one of the following:
 - ▶ If you want to use an existing keystore, enter the password in the **Existing Keystore Password** field.
 - ▶ If you are creating a new keystore, do the following:
 - a. Select **Create New Keystore**.

- b. In the **Enter Keystore Password** field, enter a password for the new keystore.
 - c. In the **Confirm Keystore Password** field, enter the new password again for verification.
 - ▶ If you do not want to create a keystore and you do not have an existing keystore, ensure all fields are clear.
- 5) On the **Configure Oracle Tablespaces** screen, enter a name for each tablespace and modify the tablespace size (M) if necessary.
- 6) On the **Specify Oracle Tablespace Location** screen, enter the location at which you want to create each tablespace and then click **Create**.
- 7) On the **Create Oracle Users** screen in the **User Name**, **Password**, and **Confirm Password** fields, modify the database user names and enter the credentials for each database user.
- 8) On the **Configuration Options** screen, complete the following:
 - a. Enter a name and password for an administrative application user.
 - b. Choose whether or not you want to load sample data.
 - c. Select your currency from the **Currency** list.
 - d. If synchronizing P6 EPPM and Oracle Primavera Cloud select **Use Oracle Database Partitioning Option(separately licensed)** to improve synchronization performance.
 - e. Click **Install**.

Installing a P6 EPPM Database with Microsoft SQL Server

If you want to manually install P6 EPPM, you should install a P6 EPPM database using the Primavera Database Setup Wizard.

To install a P6 EPPM database using the Primavera Database Setup Wizard:

- 1) To open the Primavera Database Setup Wizard, run **dbsetup.bat** (with Windows) **dbsetup.sh** (with UNIX or Linux) at <P6_EPPM_Home>/database where <P6_EPPM_Home> is the P6 EPPM home directory that was set during installation.

Note: Click **Next** after each of the following steps.

- 2) On the **Primavera P6** screen, complete the following:
 - a. Select **Install a new database**.
 - b. Select **Microsoft SQL Server**.
- 3) On the **Connection Information** screen, enter the connection details for a Microsoft SQL Server database and the administrative database user.
- 4) On the **Configure Microsoft SQL Server** screen, complete the following:
 - a. Enter the name of the P6 EPPM database.
 - b. Enter the location of the Data and Log files.
 - c. Select the database code page. The default is Database default.
 - d. Enter the location of the keystore.
- 5) On the **Create New Keystore** screen, complete one of the following:
 - ▶ If you want to use an existing keystore, enter the password in the **Existing Keystore Password** field.

- ▶ If you are creating a new keystore, do the following:
 - a. Select **Create New Keystore**.
 - b. In the **Enter Keystore Password** field, enter a password for the new keystore.
 - c. In the **Confirm Keystore Password** field, enter the new password again for verification.
 - ▶ If you do not want to create a keystore and you do not have an existing keystore, ensure all fields are clear.
- 6) On the **Create SQL Server Users** screen, complete one of the following steps:
 - ▶ If you want to use the existing P6 EPPM users for P6 Professional, complete the following:
 - a. Select the **Use Existing** check box.
 - b. In each **User Name** list, select the username of the database user.
 - c. In each **Password** field, enter the password for each database user.
 - ▶ If you want to create database users for P6 Professional, enter the login credentials for each database user in the **User Name**, **Password**, and **Confirm Password** fields.
- 7) On the **Configuration Options** screen, complete the following:
 - a. Enter a name and password for an administrative application user.
 - b. Choose whether or not you want to load sample data.
 - c. Select your currency from the **Currency** list.
 - d. Click **Install**.

Upgrading a P6 EPPM Database with Oracle Database

If you want to manually upgrade P6 EPPM, you should upgrade your P6 EPPM database using the Primavera Database Setup Wizard.

To upgrade a P6 EPPM database using the Primavera Database Setup Wizard:

- 1) To open the Primavera Database Setup Wizard, run **dbsetup.bat** (with Windows) **dbsetup.sh** (with UNIX or Linux) at <P6_EPPM_Home>/database where <P6_EPPM_Home> is the P6 EPPM home directory that was set during installation.

Note: Click **Next** after each of the following steps.

- 2) On the **Primavera P6** screen, complete the following:
 - a. Select **Upgrade an existing database**.
 - b. Select **Oracle**.
- 3) On the **Connection Information** screen, enter the connection details for an Oracle database using system credentials.
- 4) On the **Create New Keystore** screen, do one of the following:
 - ▶ If you want to use an existing keystore, enter the password in the **Existing Keystore Password** field.
 - ▶ If you are creating a new keystore, do the following:
 - a. Select **Create New Keystore**.
 - b. In the **Enter Keystore Password** field, enter a password for the new keystore.

- c. In the **Confirm Keystore Password** field, enter the new password again for verification.
 - ▶ If you do not want to create a keystore and you do not have an existing keystore, ensure all fields are clear.
- 5) On the **Configure Oracle Tablespaces** screen, enter the credentials for the administrative user. The default is admuser.
- 6) On the **Upgrade Options** screen, enter the credentials for the privileged, public, and background user. The defaults are privuser, pubuser, and bgjobuser.
- 7) On the **Ready to Begin Upgrading Data** screen, select **Yes, upgrade my database**.

Upgrading a P6 EPPM Database with Microsoft SQL Server

If you want to manually upgrade P6 EPPM, you should upgrade your P6 EPPM database using the Primavera Database Setup Wizard.

To upgrade a P6 EPPM database using the Primavera Database Setup Wizard:

- 1) To open the Primavera Database Setup Wizard, run **dbsetup.bat** (with Windows) **dbsetup.sh** (with UNIX or Linux) at <P6_EPPM_Home>/database where <P6_EPPM_Home> is the P6 EPPM home directory that was set during installation.

Note: Click **Next** after each of the following steps.

- 2) On the **Primavera P6** screen, complete the following:
 - a. Select **Upgrade an existing database**.
 - b. Select **Microsoft SQL Server**.
- 3) On the **Connection Information** screen, enter the connection details for a Microsoft SQL Server database and the administrative database user.
- 4) On the **Create New Keystore** screen, do one of the following:
 - ▶ If a you want to use an existing keystore, enter the password in the **Existing Keystore Password** field.
 - ▶ If you are creating a new keystore, do the following:
 - a. Select **Create New Keystore**.
 - b. In the **Enter Keystore Password** field, enter a password for the new keystore.
 - c. In the **Confirm Keystore Password** field, enter the new password again for verification.
 - ▶ If you do not want to create a keystore and you do not have an existing keystore, ensure all fields are clear.
- 5) On the **Upgrade Option** screen, enter the credentials for the Px Reporting user. The default is pxrptuser.
- 6) On the **Ready to Begin Upgrading Data** screen, select **Yes, upgrade my database**.

Changing the Database Base Currency

Caution: You cannot change the base currency once projects begin.

After manually creating and configuring the P6 EPPM database, you must change the base currency if you do not want the databases to use US dollars (\$) as the base currency.

The Base Currency

The base currency is the monetary unit used to store cost data for all projects in the database and is controlled by a global administrative setting. The default base currency for P6 EPPM is US dollars (\$). The view currency is the monetary unit used to display cost data in P6 EPPM and is controlled by a user preference.

The exchange rate for the base currency is always 1.0. When a user selects a different currency than the base currency to view cost data, the base currency value is multiplied times the current exchange rate for the view currency to calculate the values displayed in cost and price fields.

For example, if the base currency is US Dollars, the view currency is Euros, and the exchange rate for Euros is \$1 = €0.75, a value of \$10 stored in the database is displayed as €7.5 in cost and price fields. Similarly, if you enter €7.5 in a cost or price field, it is stored in the database as \$10.

When data is displayed in a view currency that is different than the base currency, some cost and price values can vary slightly (e.g., due to rounding). As long as the correct base currency is selected during database installation, a user can view completely accurate cost and price data by changing the view currency to match the base currency.

Reviewing Currency Choices

To change the base currency you need to edit and run the P6 EPPM script provided. By default, US dollars is the base currency, and USD is the short name used in the script. To know which short name to use, review the list of available short names for P6 EPPM by running the following query on the P6 EPPM database:

```
select curr_type, curr_short_name from currtype;
```

Changing the Base Currency

To change the base currency:

- 1) On the P6 EPPM physical media or download:
 - a. Browse to \Database\scripts\common.
 - b. Copy this script to a local drive:
or_set_currency.sql
- 2) If you copied the script from the physical media, turn off the script's read-only attribute.

Since files on physical media are read-only, this attribute turns on when you copy a file from a CD or DVD.

- a. In Windows Explorer, right-click the file.
 - b. Choose **Properties**.
 - c. Clear the **Read-Only** option.
- 3) Open the script for editing and locate the line containing **v_new_base_currency: = 'USD'**
 - 4) Replace USD with the currency short name of your choice.
 - 5) Save your changes and run the modified script.

Private Database Credentials for P6 EPPM

The P6 server and P6 Professional components obtain their run-time database connection credentials from a credential configuration table in the P6 EPPM database. The P6 run-time database credentials (known as privuser or P6 private database login) are stored in an encrypted format in this special P6 configuration table. Any time that you change or rotate the privuser password credentials in your Oracle or MS SQL Server database, you must re-synchronize the stored credentials in the P6 credential table by using the Database Login tool.

Because encryption algorithms are often enhanced in newer releases, Oracle highly recommends that you reset these stored privuser credentials when you perform a major version upgrade of P6 EPPM. By resetting the stored credentials, the new encryption algorithm can be applied to other stored credentials (for example, pubuser) in the P6 EPPM credential table. For information about resetting private database passwords, see **Resetting Private Database Passwords** (on page 22).

Note: This tool does not reset database user logins or passwords. Administrators should use SQL Developer or other DBA consoles to set or reset database user passwords.

Resetting Private Database Passwords

Password encryption algorithms are frequently improved in new releases of P6 Professional and P6 Professional. You should reset private database passwords in order to use improved password encryption algorithms.

To reset private database passwords to use the new encryption algorithm:

- 1) Go to **P6 EPPM <release_level>\database** or **P6 Professional <release_level>\database**.
- 2) Run **databaselogins.bat** (with Windows) **databaselogins.sh** (with UNIX or Linux).
- 3) In the **Database Connection** dialog box:
 - a. Select the database.
 - b. Type the user name and password of a privileged database user (for example, privuser). This login should have administrative rights on the database.

- c. Enter the host address, host port, and database/instance name specific to your installation. The Port field displays the default port for the database type you selected.
 - d. Click **Next**.
- 4) In the **Private Database Logins** dialog box:
- a. Select the private database user name that you wish to reset.
 - b. Highlight the password and change it (or re-enter the existing password).
 - c. Click **Update Password**.
 - d. Click **Save**.
 - e. Click **OK**.

Adding Private Database Logins for P6 EPPM

You can add private database users to your P6 EPPM database.

To add private database logins for P6 EPPM:

- 1) Go to **P6 EPPM <release_level>\database** and run **databaselogins.bat** (with Windows) **databaselogins.sh** (with UNIX or Linux).
- 2) On the **Database Connection** dialog box:
 - a. Select the database.
 - b. Type the user name and password of a privileged database user (for example, privuser). This login should have administrative rights on the database.
 - c. Enter the host address, host port, and database/instance name specific to your installation. The Port field displays the default port for the database type you selected.
 - d. Click **Next**.
- 3) On the **Private Database Logins** dialog box:
 - a. Click **Add**.
 - b. Enter a user name.
 - c. Enter a password.

Note: To reverse a change, click **Undo**. Undo will reverse any changes made during the current session.

- d. Click **Save**.
- e. Click **OK** to exit.

Modifying Private Database Logins for P6 EPPM

You can update the passwords and usernames of the private database users on your P6 EPPM database.

To modify private database logins:

- 1) Go to **P6 EPPM <release_level>\database** and run **databaselogins.bat** (with Windows) **databaselogins.sh** (with UNIX or Linux).
- 2) On the **Database Connection** dialog box:

- a. Select the database.
 - b. Type the user name and password of a privileged database user (for example, privuser). This login should have administrative rights on the database.
 - c. Enter the host address, host port, and database/instance name specific to your installation. The Port field displays the default port for the database type you selected.
 - d. Click **Next**.
- 3) On the **Private Database Logins** dialog box:
- a. Select the private database user name that you wish to modify.
 - b. Enter a new user name.
 - c. Highlight the password, and change it.
 - d. Click the **Update Password** button.
-
- Note:** To reverse a change, click **Undo**. Undo will reverse any changes made during the current session.
-
- e. Click **Save**.
 - f. Click **OK** to exit the Database Logins tool.

Deleting Private Database Logins for P6 EPPM

If you no longer need your private database users you can delete them.

To delete private database logins for P6 EPPM:

- 1) Go to **P6 EPPM <release_level>\database** and run **databaselogins.bat** (with Windows) **databaselogins.sh** (with UNIX or Linux).
- 2) On the **Database Connection** dialog box:
 - a. Select the database.
 - b. Type the user name and password of a privileged database user (for example, privuser). This login should have administrative rights on the database.
 - c. Enter the host address, host port, and database/instance name specific to your installation. The Port field displays the default port for the database type you selected.
 - d. Click **Next**.
- 3) On the **Private Database Logins** dialog box:
 - a. Select the private database user name that you wish to remove.

Note: You must have at least one private user name for the P6 EPPM database at all times.

- b. Click **Delete**.

Note: To reverse a change, click **Undo**. Undo will reverse any changes made during the current session.

- c. Click **Save**.
- d. Click **OK** to exit the Database Logins tool.

Setting Up Cloud Sync

You can setup Cloud Sync to share project data between your P6 EPPM and Oracle Primavera Cloud applications. P6 EPPM and Oracle Primavera Cloud utilize the REST protocol to transfer data to and from local installations of P6 EPPM. Enable project table auditing to track changes committed to projects across synchronization. Contact your Oracle Primavera Cloud administrators to ensure Oracle Primavera Cloud is configured for Cloud Sync.

For more information on establishing Cloud Sync, see **Synchronizing data from P6 EPPM to Oracle Primavera Cloud** (on page 27).

For more information on project table auditing, see **PAUDIT Auditing** (on page 45). Alternatively the application administrator can establish project table auditing using the Audit Page. For more information on the Audit Page, see the "Audit Page" topic in the *Application Administration Guide*.

Note: If you are using an Oracle database, select **Use Oracle Database Partitioning Option(separately licensed)** during database installation to improve synchronization performance.

In This Section

Synchronizing data from P6 EPPM to Oracle Primavera Cloud	27
Synchronizing data from Oracle Primavera Cloud to P6 EPPM	33

Synchronizing data from P6 EPPM to Oracle Primavera Cloud

You can send project data from local installations of P6 EPPM to cloud based installations of Oracle Primavera Cloud using Cloud Sync. To configure synchronization between your products, you must modify synchronization properties. Refer to the **Synchronization Properties** table for descriptions of synchronization property fields and values.

To setup your P6 EPPM database for synchronization with Oracle Primavera Cloud:

- 1) Navigate to the folder in which P6 EPPM is installed, then navigate to the **/cloudsync** folder.
- 2) Open **client_send.properties** in a text editor of your choice and modify the following properties:

Sync Properties

sync.mode=**CLIENT**

sync.type=**SENDER**

sync.name=<**Sync name**>

sync.number=<**Sync number**>

Note: Contact your cloud administrator to request appropriate values for the **sync.number** property.

Source Database Properties

source.db.host=<P6 EPPM database host address>
source.db.port=<P6 EPPM database port number>
source.db.service=<P6 EPPM database service name>
source.db.type=P6

Source Credential Properties

source.db.syncuser=<P6 EPPM database sync user>
source.db.schema=<P6 EPPM database administrative user>
source.db.sysuser=<P6 EPPM database SYSDBA user>

Note: The database sync user is automatically created upon running the **syncsetup** script.

Server Properties

server.base_url=http://<HOST>:<PORT>/sync/rest
server.connectuser=<USER>
optin.project_mode=PRIME
optin.project_value=Y

Notes:

- Contact your cloud administrator to request appropriate values for the **server.base_url** and **server.connectuser** properties.
 - Leave password properties fields, such as **source.db.syncuserpwd** blank. The value of these properties are populated and encrypted when you run the **syncsetup** script.
-

- 3) From the command line, navigate to the **/prime-sync** folder and run the **syncsetup** script:

Note: If you wish to sync Oracle Primavera Cloud data back to P6 EPPM complete the steps in ***Synchronizing data from Oracle Primavera Cloud to P6 EPPM*** (on page 33) before running the **syncsetup** script.

On Windows, run:

```
syncsetup.cmd client_send.properties
```

On UNIX, run:

```
./syncsetup.sh client_send.properties
```

- 4) When prompted, enter the **password** for the database sync manager, database administrative manager, database SYS user, web user, and syncadmin.
- 5) From the command line, run the **startserver** script to initialize synchronization:
On Windows, run:

```
startserver.cmd
```

On UNIX, run:

```
./startserver.sh
```

- 6) Once the server has started, run the **commander** script to load the configuration:
On Windows, run:

```
commander.cmd LOAD client_send.properties
```

On UNIX, run:

```
./commander.sh LOAD client_send.properties
```

Synchronization Properties

Property	Description	Value	Example Value
sync.mode	The application's role in the configured synchronization. The application sending data acts as a client, the other application acts as a server.	CLIENT	CLIENT
sync.type	Specifies whether the application is sending or receiving synchronization requests. The client application typically sends requests, the server application typically receives requests.	SENDER	SENDER

sync.name	The name used to identify the sync process.	Sync Name	receive1
sync.number	The unique synchronization number to connect to the hosted server application. Contact your cloud administrator to request the appropriate value for this property.	Sync Number	1
source.db.host	The host name of the database that acts as the source of data in the synchronization. Data from the application's source database is shared to the target database of the other application.	Database Host Name	localhost
source.db.port	The port number of the database that acts as the source of data in the synchronization. Data from the application's source database is shared to the target database of the other application.	Database Port Number	1521

source.db.service	The service name of the database that acts as the source of data in the synchronization. Data from the application's source database is shared to the target database of the other application.	Database Service Name	pmdb
source.db.type	The name of the application related to the source database. For example, P6 or PRIME.	Application Name	P6
source.db.syncuser	The name of the synchronization user of the specified source database. This user is created upon running the syncsetup script.	Database Synchronization User Name	syncmgr
source.db.schema	The name of the administrative user of the source database. The default administrative user for P6 EPPM installations is admuser.	Database Administrative User Name	admuser
source.db.sysuser	The name of the system user of the source database. The default SYSDBA user on an Oracle database is SYS.	Database SYSDBA User Name	SYS

source.db.userts	The tablespace in the source database in which user data is stored. The default value for P6 EPPM installations is PMDB_DAT1	Database User Tablespace Name	PMDB_DAT1
source.db.tempts	The tablespace in the source database in which temporary data is stored. The default value for P6 EPPM installations is TEMP.	Database Temporary Tablespace Name	TEMP
server.base_url	The URL used to establish connection to the target server application for synchronization. Specified host and port values vary depending on your setup. Contact your cloud administrator to request the appropriate value for this property.	Server Application URL	http://localhost:4000/p6sync/sync
server.connectuser	The user name of the user used to connect to the hosted server application. Contact your cloud administrator to request the appropriate value for this property.	Server Connection User Name	WebLogic
file.size	The maximum file size in bytes which can be sent across the synchronization.	File Size	100M

file.send.timeout	The amount of time in seconds after which attempts at sending data across the synchronization will timeout.	Time in Seconds	15
optin.project_mode	The method the applications uses to determine what project data will be synchronized. For P6 EPPM-Oracle Primavera Cloud synchronizations this value should only be PRIME.	PRIME	PRIME
optin.project_value	Specifies whether the application is using optin.project_mode.	Y	Y

Synchronizing data from Oracle Primavera Cloud to P6 EPPM

You can send project data from cloud installations of Oracle Primavera Cloud to local installations of P6 EPPM using Cloud Sync. To configure synchronization between your products, you must modify synchronization properties. Refer to the **Synchronization Properties** table for descriptions of synchronization property fields and values.

To synchronize data from Oracle Primavera Cloud to P6 EPPM:

- 1) Navigate to the folder in which P6 EPPM is installed, then navigate to the **/cloudsync** folder.
- 2) Open **client_send.properties** in a text editor of your choice and modify the following properties:

Sync Properties

sync.mode=**CLIENT**

sync.type=**RECEIVER**

sync.name=<**Sync Name**>

sync.number=<**Sync Number**>

- **Note:** Contact your cloud administrator to request the appropriate value for the **sync.number** property.

Target Database Properties

target.db.host=<**P6 EPPM database schema host**>

target.db.port=<P6 EPPM database port number>

target.db.service=<P6 EPPM database service>

target.db.type=P6

Target Database User Properties

target.db.syncuser=<P6 EPPM database sync user>

target.db.schema=<P6 EPPM database administrative user>

target.db.sysuser=<P6 EPPM database SYSDBA user>

Note: The database sync user is automatically created upon running the **syncsetup** script.

Server Properties

server.base_url=http://<HOST>:<PORT>/p6sync/sync

server.connectuser=<USER>

Notes:

- Contact your cloud administrator to request appropriate values for the **server.base_url** and **server.connectuser** properties.
 - Leave password properties fields, such as **source.db.syncuserpwd** blank. The values of these properties are set when you run the **syncsetup** script.
-

- 3) From the command line, navigate to the **/prime-sync** folder and run the **syncsetup** script:

On Windows, run:

```
syncsetup.cmd client_send.properties
```

On UNIX, run:

```
./syncsetup.sh client_send.properties
```

- 4) When prompted, enter the **password** for the database sync manager, database administrative manager, database SYS user, web user, and syncadmin.

- 5) From the command line, run the **startserver** script to initialize synchronization:

On Windows, run:

```
startserver.cmd
```

On UNIX, run:

```
./startserver.sh
```

- 6) Once the server has started, run the startserver script to load the configuration:

On Windows, run:

```
commander.cmd LOAD client_send.properties
```

On UNIX, run:

```
./commander.sh LOAD client_send.properties
```

Synchronization Properties

Property	Description	Value	Example Value
sync.mode	The application's role in the configured synchronization. The application sending data acts as a client, the other application acts as a server.	CLIENT	CLIENT
sync.type	Specifies whether the application is sending or receiving synchronization requests. The client application typically sends requests, the server application typically receives requests.	RECEIVER	RECEIVER
sync.name	The name used to identify the sync process.	Sync Name	receive1
sync.number	The unique synchronization number to connect to the hosted server application. Contact your cloud administrator to request the appropriate value for this property.	Sync Number	1

target.db.host	The host name of the database that acts as the target of data in the synchronization. Data from the synchronization source database is shared to the target database.	Database Host Name	localhost
target.db.port	The port number of the database that acts as the target of data in the synchronization. Data from the synchronization source database is shared to the target database.	Database Port Number	1521
target.db.service	The service name of the database that acts as the target of data in the synchronization. Data from the synchronization source database is shared to the target database.	Database Service Name	pmdb
target.db.type	The name of the application related to the target database. For example, P6 or PRIME.	Application Name	P6
target.db.syncuser	The name of the synchronization user of the specified target database. This user is created upon running the syncsetup script.	Database Synchronization User	syncmgr

target.db.schema	The name of the administrative user of the target database. The default administrative user for P6 EPPM installations is admuser.	Database Administrative User	admuser
target.db.sysuser	The name of the SYSDBA user of the target database. The default SYSDBA user on an Oracle database is SYS.	Database System User	SYS
target.db.userts	The tablespace in the source database in which user data is stored. The default value for P6 EPPM installations is PMDB_DAT1	Database User Tablespace Name	PMDB_DAT1
target.db.tempts	The tablespace in the source database in which temporary data is stored. The default value for P6 EPPM installations is TEMP.	Database Temporary Tablespace Name	TEMP
server.base_url	The URL used to establish connection to the target server application for synchronization. Specified host and port values vary depending on your setup. Contact your cloud administrator to request the appropriate value for this property.	Server Application URL	http://localhost:4000/p6sync/sync

server.connectuser	The user name of the user used to connect to the hosted server application. Contact your cloud administrator to request the appropriate value for this property.	Server Connection User Name	WebLogic
optin.project_mode	The method the applications uses to determine what project data will be synchronized. For P6 EPPM-Oracle Primavera Cloud synchronizations this value should only be PRIME.	PRIME	PRIME
optin.project_value	Specifies whether the application is using optin.project_mode.	Y	Y

Configuring Background Processes and Jobs

In This Section

RDBMS Scheduler Configuration	39
Database Settings Table	39
Reading Setting Values	40
Writing Setting Values	41
Tracking Background Job Execution	42

RDBMS Scheduler Configuration

Since background jobs are initiated by the job scheduler supplied by the RDBMS, you need to ensure that the scheduler for your specific RDBMS is properly configured.

With Oracle: P6 EPPM uses DBMS_SCHEDULER to schedule background jobs with Oracle.

With Microsoft SQL Server: P6 EPPM uses the SQL Agent service to automatically schedule background job execution with Microsoft SQL Server. Background jobs handle the maintenance of the utilities tables (for example, USESSION and REFRDEL). As a part of background jobs, the agent runs the SYMON and DAMON stored procedures at specific intervals.

Database Settings Table

Settings Table Overview

The settings table contains name-value pairs that configure the behavior of the background processes.

Namespace

The namespace component is a dot-notation string representing a formal path to the parameter.

Setting Name

The setting name identifies the name of the setting.

Value

Values in the SETTINGS table are case-sensitive. The value portion of the pair can be:

- ▶ **String:** The string data type is a free text value. The most common string sub-type is interval which represents an interval of time by combining a numeric portion with a unit portion as depicted in the table below.

Interval Subtype Table

		Unit portion	Example	Meaning
Numeric portion	+	d	'30d'	Thirty day interval
		h	'2h'	Two hour interval
		m	'10m'	Ten minute interval
		s	'30s'	Thirty second interval

- ▶ **Numeric:** The numeric data type consists of any number.
- ▶ **Boolean:** The Boolean data type can have one of two values: true or false, where zero represents false and any non-zero number represents true.
- ▶ **Date:** The date data type consists of dates.

Setting Example

The following is an example of a setting:

- ▶ Namespace: database.cleanup.Usession
- ▶ Setting Name: ExpiredSessionTimeout
- ▶ Value: 2h (two hour interval)

Reading Setting Values

You can configure settings through the Settings API Procedures. These procedures are similar to registry or INI file procedure calls.

Reading Settings Values

Use the following SETTINGS_READ_* procedures to determine the current value of specific settings:

- ▶ SETTINGS_READ_STRING(ret_val,namespace,settings_name,default)
- ▶ SETTINGS_READ_DATE(ret_val,namespace,settings_name,default)
- ▶ SETTINGS_READ_NUMBER(ret_val,namespace,settings_name,default)
- ▶ SETTINGS_READ_BOOL(ret_val,namespace,settings_name,default)

Using Code to Read Setting Values with Oracle

The following code snippets demonstrate how the SETTINGS_READ_* procedures read the setting values with Oracle.

To retrieve the value of the KeepInterval setting:

1) Use the following code:

```
SQL> variable vset varchar2(255)
```

```
SQL> exec settings_read_string(:vset,'database.cleanup.Usession',
'ExpiredSessionTimeout');
```

2. The following message should appear:

PL/SQL procedure successfully completed.

SQL> print vset

Using Code to Read Setting Values with Microsoft SQL Server

The following code snippets demonstrate how the SETTINGS_READ_* procedures read the setting values with Microsoft SQL Server.

To retrieve the value of the KeepInterval setting:

1) Use the following code:

```
declare @vset varchar(255)
exec settings_read_string @vset
OUTPUT, 'database.cleanup.Usession', 'ExpiredSessionTimeout'
print @vset
```

2) The following message should appear:

PL/SQL procedure successfully completed.

SQL> print vset

Writing Setting Values

Use the SETTINGS_WRITE_STRING procedure to set the value of a specific setting:

```
SETTINGS_WRITE_STRING(new value, namespace, settings_name);
```

Using Code to Write Setting Values with Oracle

The following code snippets demonstrate how the SETTINGS_WRITE_STRING procedure sets the value of the ExpiredSessionTimeout setting to 12 hours with Oracle.

To set the value of the ExpiredSessionTimeout setting to 12 hours:

1) Log in to SQL*Plus with your privuser credentials.

2) Run the following statement:

```
SQL > exec SETTINGS_WRITE_STRING
('12h', 'database.cleanup.Usession', 'ExpiredSessionTimeout');
```

Using Code to Write Setting Values with Microsoft SQL Server

The following code snippets demonstrate how the SETTINGS_WRITE_STRING procedure sets the value of the ExpiredSessionTimeout setting to 12 hours with Microsoft SQL Server.

To set the value of the ExpiredSessionTimeout setting to 12 hours:

1) Open the Query Analyzer/SSMS and connect as privuser.

- 2) Select the P6 EPPM database, then run the following statement (using 12 hours as an example):

```
exec SETTINGS_WRITE_STRING '12h','database.cleanup.Usession',  
'ExpiredSessionTimeout'
```

Tracking Background Job Execution

You can track the execution of background jobs by monitoring the high level status settings or by inspecting the BGPLOG table.

High Level Status Settings

Each time a job runs, it will update the SETTINGS table for the setting_name = 'HeartBeatTime.' The job can update this value multiple times during the execution. You can monitor the maximum difference between this time and the current date to ensure that the job is running promptly. Refer to the High Level Status Settings table below for information about the HeartBeatTime setting.

High Level Status Settings	
Last date and time background job SYMON ran.	
Namespace	database.background.Symon
Setting Name	HeartBeatTime
Default Setting	N/A
Last date and time background job DAMON ran.	
Namespace	database.background.Damon
Setting Name	HeartBeatTime
Default Setting	N/A

The BGPLOG Table

You can also track the execution of background jobs by inspecting the BGPLOG table. The BGPLOG table holds detailed entries from the background processes including informational, elapsed time, and error entries. Refer to the BGPLOG Table Descriptions for information about what this table contains.

BGPLOG Table Descriptions		
Column	Description	Value
Log_time	Time when background process made a log entry	Datetime
Source	Program generating log entry	"system_monitor", "data_monitor"
Type	Type of message	INFORMATION, ELAPSED TIME, ERROR
Description	Message from the background process	A variable message followed by a number in parenthesis that represents the number of rows that processed. As an example, the message "Complete BGPLOG (40)" indicates that forty rows processed.

Monitoring Processes and Procedures

In This Section

PAUDIT Auditing	45
-----------------------	----

PAUDIT Auditing

PAUDIT auditing permits you to log the edits, additions, and deletions made by users of P6 EPPM applications. When users make changes, they create a Data Manipulation Language (DML) INSERT, UPDATE, or DELETE statement. PAUDIT auditing uses the Data Manipulation Language (DML) INSERT, UPDATE, or DELETE statement being processed against tables in the database schema. Since every application table in the schema has its own auditing trigger, you can log changes made to each table regardless of who made the change or when the change was made. The database schema owner owns the auditing trigger: you can bypass trigger execution.

Auditing Level Configuration

You can adjust the amount of information that is logged by adjusting the audit level for each table. You can refine the audit further by setting the audit level individually for insert, updates, and deletes within each table.

Auditing Levels

Level	Description
Level 0	No audit.
Level 1	Row-level audit. Audit only the operation without column details
Level 2	Column-level Audit without blobs. Audit changes to the data at the column level but without blob changes
Level 3	Full Audit. Audit changes to the data at the column level. With Oracle, column level changes to blobs are audited. With Microsoft SQL Server, column level changes to blobs are not included.

Simple Configuration

You can use two configuration procedures to provide simple control of the auditing feature:

- ▶ `auditing_enable(table_name, level)`

- ▶ `auditing_disable(table_name)`

You can set the audit level on an individual table or the same audit level for all of the tables. However, the simple configuration procedures do not allow for setting individual auditing levels for insert, update, or delete operations within a table.

Oracle Database Examples:

Use the following examples as a guide to use the simple audit configuration procedures to control the auditing feature.

- ▶ The following code snippet enables full auditing on all tables:

```
exec auditing_enable(null,3);
```

- ▶ The following code snippet enables level one auditing on the task table:

```
exec auditing_enable('TASK',1);
```

- ▶ The following code snippet disables auditing on PROJWBS:

```
exec auditing_disable('PROJWBS');
```

- ▶ The following code snippet completely disables auditing across the entire database:

```
exec auditing_disable(null);
```

Detailed Configuration

You can configure auditing trigger behavior by changing values in the settings table that either enable or disable:

- ▶ The auditing feature itself
- ▶ The auditing of specific tables
- ▶ The auditing of table insert, update, or delete operations within each table

Auditing Status

You can enable or disable the auditing feature by using the `database.audit.Enable` setting. Use the `settings_write_bool` procedure to enable/disable the auditing feature.

Oracle Example:

To enable the auditing feature in Oracle, use the following code:

```
exec settings_write_bool(1,'database.audit','Enabled');
```

Microsoft SQL Server Example:

To enable the auditing feature in Microsoft SQL Server, use the following code:

```
exec settings_write_bool 1,'database.audit','Enabled'
```

Options Setting

Each table's auditing settings are controlled by the Options setting in each table's auditing namespace (for example, database.audit.TASK). The Options setting is a three character string with a numeric value in each character position representing the audit level for insert, update, and delete.

Auditing Level Options Setting by Table Operation				
	Operation			
	Insert	Update	Delete	Description
Level	0	0	0	No audit.
	1	1	1	Row-level audit. Audit only the operation without column details.
	2	2	2	Column-level audit without blobs. Audit changes to the data at the column level but without blob changes.
	3	3	3	Full Audit. Audit changes to the data at the column level. With Oracle, column level changes to blobs are audited. With Microsoft SQL Server, column level changes to blobs are not included.

The following table provides examples of the options setting:

Setting the Auditing Level Options Setting by Table Operation Examples			
Namespace	Setting	Value	Description
database.audit.TASK	Options	330	Fully audit any insert and update operations. Do not audit any delete operations.
database.audit.PROJWBS		001	Row-level audit on deletes only.

database.audit.TASKRSRC		333	Fully audit.
-------------------------	--	-----	--------------

SETTINGS_WRITE_STRING Procedure

You can change table audit settings using the settings_write_string procedure.

Oracle Example:

To set the table settings to fully audit insert and update operations but ignore any delete operations, use the following code with Oracle:

```
exec settings_write_string('330','database.audit.TASK','Options');
```

Microsoft SQL Server Example:

To set the table settings to fully audit insert and update operations but ignore any delete operations, use the following code with Microsoft SQL Server:

```
exec settings_write_string '330','database.audit.TASK','Options'
```

Note: Changes to auditing settings will not appear immediately in the application. The program will need to close the database connection and then reconnect to the database to get the new settings.

The Audit Table

Audit records are inserted into the PAUDIT table. One record is inserted into the audit table for each row changed in the database.

PAUDIT Table		
Column	Type	Description
AUDIT_TS	TIMESTAMP (6)	Date and time of change
TABLE_NAME	STRING (30)	Table Name
PK1, PK2, PK3, PK4	STRING (255)	Primary key values for audited record
PROJ_ID	NUMBER	Unique object id of the audited project.
OPER	STRING (1)	I=Insert, U=Update, D=Delete
PRM_USER_NAME	STRING (32)	P6 EPPM user name if the change was made in P6 EPPM applications

AUDIT_OLD	STRING(4000)	Column changes up to 4000 characters (Level 2 and 3 only)
AUDIT_NEW	STRING(4000)	Column changes up to 4000 characters (Level 2 and 3 only)
AUDIT_EXT_OLD	BLOB	Blob changes and overflow from audit_old (Level 2 and 3 only)
AUDIT_EXT_NEW	BLOB	Blob changes and overflow from audit_new (Level 2 and 3 only)
LOGICAL_DELETE_FLAG	STRING(1)	Flag for deletes that are logical (marked) rather than a physical delete
RDBMS_USER_NAME*	STRING(255)	Database user name (usually privuser)
OS_USER_NAME*	STRING(255)	<p>Operating system user name of connected session</p> <p>Note: When auditing is enabled against a SQL Server database, PAUDIT.os_user_name will always return a null value. This is because the value for os_user_name in PAUDIT table is taken from the nt_username column in master.sys.sysprocesses view and the nt_username value in master.sys.sysprocesses view is empty for the P6 Professional program because P6 is connected to SQL DB using SQL authentication. The nt_username field is filled only when we connect to SQL DB using Windows authentication.</p>
PROGRAM*	STRING(255)	Name of program connecting to the database
HOST_NAME*	STRING(255)	Computer name of connected session
APP_NAME*	STRING(25)	Name of application connected to the database

NETADDRESS*	STRING (24)	IP or MAC address of connected session
-------------	---------------	--

Note: Grant select privileges to the administrative user on V_\$SESSION to ensure correct values for several auditing table values.

Session Auditing

Activity for the USESSION table is audited with its own trigger and table. When an application user logs out of the system they logically delete or mark their session record in the USESSION table. One record is written to the USESSAUD table for each logout. The format of the USESSAUD table mirrors that of the USESSION table. This audit can be enabled using the usessaud_enable procedure and disabled using the usessaud_disable procedure.

Column Audit Data

The data changes for each audit are stored in the audit_info and audit_info_extended columns. The audit_info column contains all the row changes as long as they do not exceed 4000 characters. Changes over 4000 characters or any edit to a blob will be written to the audit_info_extended BLOB column.

Data in the two audit_info columns has a specific format. Each column audit within the data begins with either ":O" (old data) or ":N" (new data) to distinguish between the audit of the previous (old) or the changed (new) value (for BLOB columns the data starts with :BLOBO or :BLOBN). Directly after this is the name of the column in lowercase. Following the column name is the length of the audited value in a fixed four character field. Finally, the actual data is placed in the audit record. Updates will have both an old and new value for each change. Inserts will have only a new value and deletes only an old value.

The following is an example of the audit record for TASK to change the task_code from 'A1010' to 'B102':

```
audit_info =>:Otask_code: 5:A1010:Ntask_code: 4:B102
```

Tuning the P6 EPPM Database

The performance of the P6 EPPM database depends on an effective configuration of physical design structures, such as indexes or hints, in the database.

Both Oracle and SQL Server have different tools which can be used to diagnose the need for database design performance tuning and is discussed in detail below.

In This Section

Oracle Database Tuning.....	51
Microsoft SQL Server Database Tuning	55
General Tuning	57

Oracle Database Tuning

The responsibility for maintaining performance of the Oracle database is a task of the Oracle database administrator (DBA). This section describes how to tune an Oracle database for the P6 EPPM database.

Partitioning Oracle Database Tables for P6 EPPM Schema

Partitioning addresses key issues in supporting very large tables and indexes by letting you decompose them into smaller and more manageable pieces called partitions. SQL queries and DML statements do not need to be modified in order to access partitioned tables. However, after partitions are defined, DDL statements can access and manipulate individual partitions rather than entire tables or indexes. This is how partitioning can simplify the manageability of large database objects. Also, partitioning is entirely transparent to applications.

Each partition of a table or index must have the same logical attributes (for example, column names, datatypes, and constraints); however, each partition can have separate physical attributes such as `pctfree`, `pctused`, and `tablespaces`.

Partitioning is useful for applications that manage large volumes of data.

Table partitioning is a manual process that can be performed after you set up the P6 EPPM Database. Oracle Primavera does not provide any tools or utilities to configure table partitioning. Partitioning of an Oracle table within a schema should be performed by the Oracle DBA.

For more information about Oracle Database partitioning, refer to the *Database Performance Tuning Guide* and *Database Administrator's Guide*.

For more information about partitioning a non-partitioned table, refer to *How to Partition a Non-partitioned / Regular / Normal Table (Doc ID 1070693.6)* on My Oracle Support.

Supported Tables for Partitioning

The following tables are supported for partitioning:

- ▶ CALENDAR
- ▶ PAUDIT
- ▶ PROJWBS
- ▶ PROJECT
- ▶ REFRDEL
- ▶ RSRROLEASGNMENTSPREAD
- ▶ UDFVALUE

Supported Partitioning Type

The `LIST` and `RANGE` partitioning types are supported. List partitioning enables you to explicitly control how rows map to partitions by specifying a list of discrete values for the partitioning key in the description for each partition. Range partitioning enables you to specify a range of values for the partitioning key in the description of each partition. Rows with values matching the specified partition range map to the partition.

Table Partition Keys

The partitioning key is comprised of one or more columns that determine the partition where each row will be stored. Oracle automatically directs insert, update, and delete operations to the appropriate partition through the use of the partitioning key. The following list includes the partition key for each table:

- ▶ The partition key for `CALENDAR` is `CLNDR_TYPE`. The partition is by list `CA_BASE`, `CA_PROJECT`, and `CA_RSRC`.
- ▶ The partition key for `PAUDIT` is `AUSIT_TS`. The partition is by range `INTERVAL` of `(1, 'day')`.
- ▶ The partition key for `PROJWBS` is `PROJ_NODE_FLAG`. The partition is by list `Y` or `N`.
- ▶ The partition key for `PROJECT` is `ORIG_PROJ_ID`. The partition is by list `null` or `default` (`not null`).
- ▶ The partition key for `REFERDEL` is `DELETE_DATE`. The partition is by range `INTERVAL` of `(1, 'day')`.
- ▶ The partition key for `RSRCROLEASGNMENTSPREAD` is `ROLLEDUP_RECORD`. The partition is by list `Y` or `N`.
- ▶ The partition key for `UDFVALUE` is `TABLE_NAME`.

`TABLE_NAME` is a de-normalized column and duplicates values from the `UDFTYPE` table. You can create a trigger to sync `UDFVALUE.TABLE_NAME` values with `UDFTYPE.TABLE_NAME`. The following script can be used to create a new trigger when partitioning `UDFVALUE`:

```
-- new trigger
CREATE OR REPLACE TRIGGER "DN_TABLE_NAME_UDFVALUE"
BEFORE INSERT OR UPDATE OF UDF_TYPE_ID ON UDFVALUE
FOR EACH ROW
DECLARE
BEGIN
select TABLE_NAME into :new.TABLE_NAME from UDFTYPE where udf_type_id =
:new.udf_type_id;
```

```
end;
```

You can also enhance the login process and open project queries by changing the `SETTINGS.SETTING_VALUE` from N to Y in the `SETTINGS` table where `SETTINGS.SETTINGS_NAME= 'UDFVALUE_DENORM'`.

Gathering Statistics for Cost Based Optimizations

Oracle Databases only support cost-based optimization, which relies on accurate statistics to determine the optimal access path for a query. Gathering the appropriate statistics helps the optimizer, which will improve database performance. To gather statistics that optimize specifically for P6, use the custom P6 stored procedure `gather_statistics()` which is owned by the `ADMUSER` schema. Calling this procedure is the preferred method for gathering table statistics for P6 EPPM tables.

To call the stored procedure, run the following four lines in SQL Developer or SQLPlus:

- ▶ `var ret number`
- ▶ `var retmsg varchar2(200)`
- ▶ `exec gather_statistics(:ret, :retmsg);`
- ▶ `select :retmsg from dual;`

Note: The `ORPM_STATS_GATHER.sql` script located in the `\Database\scripts\common` folder of the P6 EPPM physical media is also supported and performs the same function.

Viewing the USESSION Table for GET_SAFETY_DATE

`V_$TRANSACTION` is a system view in Oracle that lists the active transactions in the system.

`GET_SAFETY_DATE` (a procedure in the Project Management schema) accesses this view to get the oldest start time of an active transaction. If the schema owner does not have privileges to this view, then it returns a safety date using the `USESSION` table. `V_$Transaction` tunes performance during a refresh action. `USESSION` records the login time of the logged in user, whereas data in the `V_$Transaction` view is recorded at a system level. The logged in user could be logged in for more than an hour (as seen from the `USESSION` table), but the `V_$Transaction` view has the current transaction datetime, regardless of the time the user logged in.

Note: Access to the `V_$TRANSACTION` view was built into the procedure to tune performance with refreshing operations; however, third party functions could impact performance with database refresh operations that use an older time in the `V_$TRANSACTION` view.

To grant access to this view, connect to Oracle as `SYS`. Run the `RUN_AS_SYS.SQL` script located in the `\Database\scripts\common` folder of the P6 EPPM physical media or download.

Rebuilding the P6 EPPM Index Table

Indexes can become skewed if you frequently access parts of the index and not others. As a result, disk contention may occur and create a bottleneck in SQL performance. To prevent this performance degradation, you should monitor your P6 EPPM indexes and rebuild if necessary.

You can use the `analyze_P6EPPM_indexes.sql` script to compute statistics on the P6 EPPM index, validate the index structure, and return a report that includes the following information:

- ▶ The number of values in the index that exceed 100.
- ▶ Deleted entries in the index that represents 20% or more of the current entries or the index depth is more than four levels based on `index_stats` result

The indexes that are returned from this report should be considered for a rebuild as they could represent a skewed tree structure and can lead to unnecessary database block reads of the index.

To run `analyze_P6EPPM_indexes.sql`:

- 1) Download `analyze_P6EPPM_indexes.sql` from https://support.oracle.com/epmos/main/downloadattachmentprocessor?parent=DOCUMENT&sourceId=1327603.1&attachid=1327603.1:ANALYZE_INDEXES&clickstream=yes.
- 2) Save the script to your local database server.
- 3) Open a command prompt and then change the directory to the location of the script.
- 4) From the command line, run the following scripts and provide the password when prompted:

```
sqlplus <admsuser>@<db_tns_names_entry>  
@analyze_P6EPPM_indexes.sql
```

If you need to rebuild an index, you can run the following script:

```
ALTER INDEX <Index_Name> REBUILD ONLINE;
```

Where: <Index_Name> is the name of the index returned in the report.

Where to Find Additional Oracle Database Tuning Information

The *Oracle Database 2 Day + Performance Tuning Guide* is intended for Oracle database administrators (DBAs) who want to tune and optimize the performance of their Oracle database. It is meant as a quick start guide that teaches you how to perform day-to-day database performance tuning tasks using features provided by Oracle Diagnostics Pack, Oracle Tuning Pack, and Oracle Enterprise Manager (Enterprise Manager). In particular, this document is targeted toward the following groups of users:

- ▶ Oracle DBAs who want to acquire database performance tuning skills.
- ▶ DBAs who are new to Oracle Database.

The *Oracle Database Performance Tuning Guide* is an aid for people responsible for the operation, maintenance, and performance of Oracle database. This book describes detailed ways to enhance Oracle database performance by using performance tools, and optimizing instance performance. It also explains how to create an initial database for good performance and includes performance-related reference information. This book could be useful for database administrators, application designers, and programmers.

Microsoft SQL Server Database Tuning

The responsibility for maintaining performance of the Microsoft SQL Server Database is a task of the SQL administrator (sa). This section describes how to tune a Microsoft SQL Server database for the P6 EPPM database.

Where to Find Additional Microsoft SQL Server Database Tuning Information

Monitoring the performance of a database requires a periodic review of the performance of processes that the database uses. As you collect data, you can isolate processes that cause problems or you can track performance trends.

For more information about how to effectively monitor a Microsoft SQL Server database for performance, refer to the following topics in the Microsoft documentation library:

- ▶ *Monitor and Tune for Performance*
- ▶ *Monitor SQL Server Components*
- ▶ *Performance Monitoring and Tuning Tools*
- ▶ *Establish a Performance Baseline*
- ▶ *Isolate Performance Problems*
- ▶ *Identify Bottlenecks*

Isolating Snapshots

When you enable snapshots and create a transaction in your SQL Server Database, a transaction is created (with a unique sequence number before your intended transaction) in `tempdb`. Your transaction then relies on all of the rows that have a lower sequence number than the rows in `tempdb` which ensures that your transaction is run against your database as it appeared at the time the query was performed. This prevents rows that were created after a transaction begins from being utilized by current transactions.

For more information about snapshot isolation as well as instructions to enable it, refer to the *Snapshot Isolation in SQL Server* topic in the Microsoft documentation library.

Rebuilding the P6 EPPM Index

Indexes become fragmented if you frequently create, modify, or delete data within a database. When indexes become fragmented, performance degrades. You can prevent the performance of your database from degrading as a result of fragmentation by monitoring your P6 EPPM indexes and rebuilding them if necessary.

For more information about detecting fragmentation within your database and rebuilding your indexes, refer to the *Reorganize and Rebuild Indexes* topic in the Microsoft documentation library.

Gathering Statistics

Statistics are an option that you can enable for your Microsoft SQL Server Database that automatically collections information about data distribution within tables and indexes, query patterns, query results, and the like. You should gather statistics so that you can optimize your interactions with your P6 EPPM database.

For example, gathering statistics can help you recognize and resolve the following issues:

- ▶ Loading data that hangs at 98%
- ▶ Performance issues
- ▶ Projects that open slowly
- ▶ Windows that disappear after loading data

For more information about enabling statistics gathering in your Microsoft SQL Server Database, refer to Introduction to the *Statistics in SQL Server* article in the Microsoft documentation library.

To gather statistics for all of the P6 EPPM tables:

- 1) Log in to your Microsoft SQL Server Database as a system administrator (sa) user.
- 2) Run the following query:

```
exec sp_updatestats
```

To gather statistics for the PROJECTS and TASKS tables:

- 1) Log in to your Microsoft SQL Server Database as a system administrator (sa) user.
- 2) Run the following queries:

```
update statistics project with fullscan ,all  
update statistics task with fullscan ,all
```

To determine the last time statistics were gathered per index and table:

- 1) Log in to your Microsoft SQL Server Database as a system administrator (sa) user.
- 2) Run the following query:

```
SELECT OBJECT_NAME(A.object_id) AS Object_Name, A.name AS index_name,  
STATS_DATE(A.OBJECT_ID, index_id) AS StatsUpdated,  
DATEDIFF(d,STATS_DATE(A.OBJECT_ID, index_id),getdate()) DaysOld  
FROM sys.indexes A  
INNER JOIN sys.tables B ON A.object_id = B.object_id  
WHERE A.name IS NOT NULL  
ORDER BY DATEDIFF(d,STATS_DATE(A.OBJECT_ID, index_id),getdate()) DESC
```


General Tuning

In This Section

Background Processes and Clean Up in P6 EPPM	57
PX Tables Clean Up Procedure.....	68
Safe Deletes.....	69

Background Processes and Clean Up in P6 EPPM

Because clean up tasks can be resource intensive and time consuming, these tasks are initiated in P6 EPPM by two background jobs that run on the database server using the background job processes user name:

- ▶ SYMON (System Monitor), responsible for running procedures that take less than a few seconds to complete.
- ▶ DAMON (Data Monitor), responsible for running procedures that take longer than a few seconds to complete.

Both of these jobs are pre-configured with default settings. Since the default settings are optimal for most environments, you generally do not need to tune them. However, if you need to optimize your background process further, you can use the background job processes user to change the settings to tune the behavior of the background jobs for specific environments.

The background process will:

- ▶ Update the settings table with a record each time a job runs.
- ▶ Update the settings table with a HeartBeatTime record for both the SYMON and DAMON processes. The background processes regularly refresh the record to indicate that they are still running.

When you initiate background jobs:

- ▶ Run the stored procedure **INITIALIZE_BACKGROUND_PROCS**.
- ▶ Locate the logs of background process activity in **BPLOGS** and **SETTINGS** tables within the Primavera database.

SYMON (System Monitor) Procedures

SYMON runs simple P6 EPPM tasks on a quick schedule. By default, the job runs every minute; the tasks assigned to this job should take only a few seconds to complete on each run. Do not change the scheduled run time (every minute) for this procedure.

Procedures performed by SYMON

The procedures run by SYMON perform these tasks:

- ▶ Processing the PRMQUEUE entries for Project Security by queuing OBSPROJ updates to the PRMQUEUE table.
- ▶ Marking expired USESSION records as logically deleted.

Note: You can manually run queries to assist you with tracking concurrent usage of P6 EPPM.

OBSPROJ_PROCESS_QUEUE Procedure

OBSPROJ_PROCESS_QUEUE processes the PRMQUEUE entries for Project Security. It defers processing of OBSPROJ updates by queuing the updates to the PRMQUEUE table.

Refer to the following table for information about the settings associated with the OBSPROJ_PROCESS_QUEUE procedure.

OBSPROJ_PROCESS_QUEUE Settings

Setting Description: Maximum project-level queue records to process on each run.	
Namespace	database.obsproj.queue
Setting Name	MaxProjectUpdates
Default Setting	1000
Type	Numeric
Setting Description: Maximum EPS-level queue records to process on each run.	
Namespace	database.obsproj.queue
Setting Name	MaxEpsUpdate
Default Setting	25
Type	Numeric
Setting Description: Maximum times to re-process a failed entry before marking it as an error.	
Namespace	database.obsproj.queue
Setting Name	MaxRetries
Default Setting	50
Type	Numeric

USESSION_CLEANUP_EXPIRED Procedure

USESSION_CLEANUP_EXPIRED logically deletes USESSION records that have not updated their last_active_time based on the Expired Session settings. Marking expired USESSION records as logically deleted maximizes the number of module access logins that are available. Since it is not cleaning up the underlying data (physically deleting rows), the task completes quickly.

Values in the SETTINGS table control the clean up of expired sessions. By default, although the clean up of expired sessions occurs every two hours, the SETTINGS table does not contain a value for this setting. Use the SETTINGS_WRITE_STRING (*value, namespace, setting*) stored procedure to change the default clean up value.

For example, setting the value to "2d" deletes expired sessions older than two days.

Note: Oracle recommends that you set the ExpiredLongSessionTimeout sessions to at least one hour longer than your longest job. For example, if your longest job is a summarizer job that usually takes 12 hours, you should set the value in the SETTINGS table to at least 13.

Refer to the table below for information about the USESSION_CLEANUP_EXPIRED Settings.

USESSION_CLEANUP_EXPIRED Settings

Setting Description: ExpiredSessionTimeout determines how long an inactive user session will remain in the records before it is marked deleted. User sessions are created when a P6 user logs into P6.	
Namespace	database.cleanup.Usession
Setting Name	ExpiredSessionTimeout
Default Setting	2h
Type	Interval
Setting Description: ExpiredLongSessionTimeout determines how long a session that is running a job-like operation (that is still processing) will remain in the records before it is marked deleted. Job-like operations are processed by job services and some are performed by logged in P6 users. Operations that are considered job-like are: <ul style="list-style-type: none"> ▶ Scheduling ▶ Leveling ▶ Apply Actuals ▶ Update Progress ▶ Copy/Paste Project ▶ Create Project from Template ▶ Maintain Baselines (create new baseline) ▶ Approve Timesheets ▶ Summarize ▶ PX Publish ▶ Export ▶ Import 	
Namespace	database.cleanup.Usession
Setting Name	ExpiredLongSessionTimeout

Default Setting	12h
Type	Interval

Tracking Concurrent Usage of P6 EPPM

To track concurrent usage of P6 EPPM, you can run queries against the USESSION and USESSAUD tables to perform self-audits. See sample queries below.

Note: See ***DAMON (Data Monitor) Procedures*** (on page 61) for information on how to set up the USESSAUD procedure. To ensure accuracy of these queries, run them before physically deleting remaining USESSION records and cleaning up the USESSAUD table.

- ▶ Against the USESSION table, run the following query to determine how many users are logged in at a given time:

```
select count(*) from usession where delete_session_id is null
```

- ▶ Against the USESSION table, run the following query to determine how many users are logged into a specific P6 EPPM product at a given time:

```
select count (*) from usession where delete_session_id is null and  
app_name= 'P6 EPPM product name'
```

where *P6 EPPM product name* is the application abbreviation.

Note: You can view all available application abbreviations by running the following query as an administrative database user: `select distinct(db_engine_type) from usereng`

- ▶ Against the USESSAUD table, run a query similar to the following to determine how many users logged into P6 EPPM on a specific date during a specified time range. You can alter the date, time range, and P6 EPPM product as needed. The following example will search for all users who logged into P6 Professional on February 17, 2010 between 9am and 10am:

For an Oracle database:

```
select * from usessaud where login_date between to_date('17-FEB-10  
09:00:00','DD-MON-YY HH:MI:SS') and to_date('17-FEB-10  
10:00:00','DD-MON-YY HH:MI:SS') and app_name='Project Management'
```

For a Microsoft SQL Server database:

```
select * from usessaud where login_date between  
'2010-02-17 09:00' and '2011-02-17 10:00' and app_name='Project  
Management'
```

Tips

See "Counting Users" in the *P6 EPPM System Administration Guide* for information on counting users and how to view the total number of licenses assigned for each module.

DAMON (Data Monitor) Procedures

The second database job is the DAMON data monitor job. The DAMON job runs the majority of the background processing and is responsible for running background clean up processes required by the application that can potentially take a relatively long time to run.

Oracle and DAMON

By default, DAMON runs every Saturday. It uses the Oracle DBMS_SCHEDULER package to schedule the jobs. An Interval setting controls the schedule and accepts the same parameters as the DBMS_SCHEDULER interval. For more information, refer to your Oracle database documentation.

Microsoft SQL Server and DAMON

By default, DAMON runs every Saturday. You can set it to run every two weeks or on a specific day. To run DAMON every two weeks, use the following command to set the interval: `-eg 2W`

To set DAMON to run on a specific day, use the following setting under namespace:

`Database.background.Damon DayOfWeek`

DAMON Procedures

DAMON cleans the following:

- ▶ BGPLOG table containing the background logs
- ▶ DBERRLOG table containing details of database related errors
- ▶ Logically deleted records
- ▶ PAUDIT table
- ▶ PRMQUEUE table
- ▶ REFRDEL table
- ▶ Remaining USESSION records
- ▶ USESSAUD, the USESSION audit table

You can also dynamically extend DAMON functionality via the user-defined procedure, `USER_DEFINED_BACKGROUND`.

BGPLOG_CLEANUP Procedure

This procedure keeps the BGPLOG table at a reasonable size. The default cleanup interval is 5 days which will result in a table size of about 54,000 records.

Refer to the following table for information about the settings associated with the BGPLOG_CLEANUP procedure.

BGPLOG_CLEANUP Settings

Setting Description: The oldest records to keep in the BGPLOG table.	
Namespace	database.cleanup.BackGroundProcessLog
Setting Name	KeepInterval

Default Setting	5d
Type	Interval

CLEANUP_DBERRLOG Procedure

deletes records from the DBERRLOG table based on the KeepInterval parameter setting. All other settings are similar to the REFRDEL_CLEANUP procedure. The following table describes the settings associated with the CLEANUP_DBERRLOG procedure.

Refer to the following table for information about the settings associated with the CLEANUP_DBERRLOG procedure..

CLEANUP_DBERRLOG Settings

Setting Description: Identifies the number of days that records are stored in the DBERRLOG table before they can be removed.	
Namespace	database.cleanup.Dberrlog
Setting Name	KeepInterval
Default Setting	30d
Type	Interval

REFRDEL_CLEANUP Procedure

This procedure deletes records from the REFRDEL table. REFRDEL_CLEANUP runs based on the frequency of data_monitor_job, which has a default frequency of one week. Alternatively, you can run REFRDEL_CLEANUP by itself if needed.

Refer to the following table for information about the settings associated with the REFRDEL_CLEANUP procedure:

REFRDEL_CLEANUP Settings

Setting Description: Identifies the number of days that records are stored in the REFRDEL table before they can be removed. For example, the default setting keeps the REFRDEL records from the last five days.	
Namespace	database.cleanup.Refrdel
Setting Name	KeepInterval
Default Setting	5d
Type	Interval

Setting Description: Identifies the number of days that are set to be removed from the REFRDEL table starting with the oldest record in the table.	
Namespace	database.cleanup.Refrdel
Setting Name	DaysToDelete
Default Setting	1
Type	Numeric
Setting Description: Determines the intervals of time (in minutes) in which data is grouped and removed from the REFRDEL table. The number of IntervalSteps is equal to DaysToDelete (in minutes) divided by IntervalStep.	
Namespace	database.cleanup.Refrdel
Setting Name	IntervalStep
Default Setting	15
Type	Numeric

REFRDEL Bypass Procedure

The REFRDEL table maintains a list of deleted records from P6 database tables. However, when an entire project is deleted, a large amount of detailed delete records can be inserted into the REFRDEL table resulting in the potential for downstream performance degradation when joins are made to the REFRDEL table.

The REFRDEL Bypass procedure is an alternative to inserting REFRDEL records for tracking delete records on a large scale. This procedure bypasses the REFRDEL table and simply adds a single delete record for a deleted project and project ID.

By default, the REFRDEL BYPASS procedure is set to 0 (zero).

To enable REFRDEL Bypass, run the following procedure and set to a non-zero value:

```
SQL> exec SET_REFRDEL_PROJECT_BYPASS(1);
```

Database triggers check for the value of the REFRDEL BYPASS value and process accordingly.

Note: The bypass procedure is meant only for a PROJECT DELETE operations.

CLEANUP_PRMQUEUE Procedure

This procedure deletes records from the PRMQUEUE table based on the value of the KeepInterval setting. The remaining settings are similar to the REFRDEL_CLEANUP.

Refer to the following table for information about the settings associated with the CLEANUP_PRMQUEUE procedure:

CLEANUP_PRMQUEUE Settings

Setting Description: The oldest records to keep in the PRMQUEUE table. Default is five days.	
Namespace	database.cleanup.Prmqueue
Setting Name	KeepInterval
Default Setting	5d
Type	Interval
Setting Description: Determines whether the procedure will delete all of the PRMQUEUE records possible on each pass.	
Namespace	database.cleanup.Prmqueue
Setting Name	DeleteAll
Default Setting	0 (false)
Type	Boolean
Setting Description: Determines whether all of the records are cleaned. If the total record count is less than this number then all the records are cleaned.	
Namespace	database.cleanup.Prmqueue
Setting Name	DeleteAllThreshold
Default Setting	1,000
Type	Numeric
Setting Description: Percentage of records to delete on each pass.	
Namespace	database.cleanup.Prmqueue
Setting Name	DeletePercentage
Default Setting	10(%)
Type	Numeric
Setting Description: Maximum rows to delete on each pass.	

Namespace	database.cleanup.Prmqueue
Setting Name	MaxRowsToDelete
Default Setting	10,000
Type	Numeric

USESSION_CLEAR_LOGICAL_DELETES Procedure

This procedure physically deletes all logically deleted USESSION records. This procedure does not have settings associated with it: All logically deleted USESSION records are cleared.

CLEANUP_LOGICAL_DELETES Procedure

This procedure removes logically deleted rows based on the value of the KeepInterval setting. Records in the database can be marked as deleted (logically deleted) by setting the DELETE_SESSION_ID column to a non-null value. By default, records that were deleted more than 5 days ago will be deleted by this procedure.

Notes:

- The CLEANUP_LOGICAL_DELETES procedure will not delete records whose DELETE_SESSION_ID column is set to a negative value.
- This procedure will not delete records older than the earliest user session in USESSION, as determined by the minimum value in the login_date column.

Refer to the following table for information about the settings associated with the CLEANUP_LOGICAL_DELETES procedure:

CLEANUP_LOGICAL_DELETES Settings

Setting Description: The oldest logically deleted records to keep in tables.	
Namespace	database.cleanup.LogicalDelete
Setting Name	KeepInterval
Default Setting	5d
Type	Interval
Setting Description: Determines whether the procedure will delete all of the logically deleted records possible on each pass.	
Namespace	database.cleanup.LogicalDelete
Setting Name	DeleteAll

Default Setting	0 (false)
Type	Boolean
Setting Description: Maximum rows to delete on each pass.	
Namespace	database.cleanup.LogicalDelete
Setting Name	MaxRowsToDelete
Default Setting	10,000
Type	Numeric

PAUDIT_CLEANUP Procedure

If the auditing feature is enabled, this procedure will physically delete records from the table based on the value of the KeepInterval setting.

Refer to the following table for information about the settings associated with the PAUDIT_CLEANUP procedure:

PAUDIT_CLEANUP Settings

Setting Description: Should the procedure attempt PAUDIT records cleanup.	
Namespace	database.cleanup.auditing
Setting Name	Enabled
Default Setting	1 (true)
Type	Boolean
Setting Description: The oldest audit records to keep in PAUDIT.	
Namespace	database.cleanup.auditing
Setting Name	KeepInterval
Default Setting	30d
Type	Interval

CLEANUP_USESSAUD Procedure

The CLEANUP_USESSAUD procedure deletes records from the USESSAUD table based on the KeepInterval parameter setting. All other settings are similar to the REFRDEL_CLEANUP procedure. The following table describes the settings associated with the CLEANUP_USESSAUD procedure.

CLEANUP_USESSAUD Settings

Setting Description: Determines the oldest records to keep in the USESSAUD table. Based on the logout time, data beyond the KeepInterval parameter value will not be deleted. The KeepInterval parameter setting overrides all other CLEANUP_USESSAUD settings.	
Namespace	database.cleanup.Usessaud
Setting Name	KeepInterval
Default Setting	5d
Type	Interval
Setting Description: Deletes all the REFRDEL records that satisfy the KeepInterval setting on each pass. The DeleteAll parameter setting overrides the settings of DeleteAllThreshold, DeletePercentage, and MaxRowsToDelete parameters.	
Namespace	database.cleanup.Usessaud
Setting Name	DeleteAll
Default Setting	0 (false)
Type	Boolean
Setting Description: Determines the minimum number of records to delete after satisfying the KeepInterval parameter setting. By default, a minimum of 1000 records are deleted. If the total record count is less than this setting, all records are deleted. The DeleteAllThreshold parameter setting overrides the settings of the DeletePercentage and MaxRowsToDelete parameters.	
Namespace	database.cleanup.Usessaud
Setting Name	DeleteAllThreshold
Default Setting	1,000
Type	Numeric
Setting Description: Determines the maximum rows to delete on each pass after satisfying the KeepInterval parameter setting. The MaxRowsToDelete parameter setting overrides the DeletePercentage parameter setting.	
Namespace	database.cleanup.Usessaud
Setting Name	MaxRowsToDelete
Default Setting	10,000

Type	Numeric
Setting Description: Determines the percentage of records to delete on each pass after satisfying the DeleteAllThreshold and MaxRowsToDelete settings. However, the percentage of records deleted is limited to the default value of the MaxRowsToDelete setting.	
Namespace	database.cleanup.Usessaud
Setting Name	DeletePercentage
Default Setting	10 (%)
Type	Numeric

USER_DEFINED_BACKGROUND Procedure

This procedure is an optional customer procedure that DAMON runs. This procedure does not have settings associated with it.

PX Tables Clean Up Procedure

To avoid operational problems for P6, PX table entries are not automatically deleted when you delete data from P6 tables. You can use the following clean up procedure to clear the obsolete entries in PX tables.

- 1) Run the CLEAN_PX_DELETE stored procedure to purge obsolete entries in the PX tables:
With Oracle:

```
BEGIN  
CLEAN_PX_DELETE ( ) ;  
END;
```

With Microsoft SQL Server:

```
USE [ddname]  
GO  
DECLARE @return_value int  
EXEC @return_value = [dbo].[CLEAN_PX_DELETE]  
SELECT 'Return Value' = @return_value  
GO
```

where *ddname* is the is your admin user name.

Note: You can run this procedure any time you want. You can also run it as a database background job and schedule a specific time for it to run.

- 2) To delete batch size and max delete from each table in a single run, run the following queries:

Note: You can specify the delete batch size and max delete from each table in a single run. Delete batch size is the number of rows deleted before a commit. Max delete is the max number of rows that will be deleted from a table in a single run. They have default values if you do not provide your own. They're used to avoid resource problems with the P6 operations.

- ▶ `insert into settings (namespace, setting_name, setting_value) values ('PxService.Cleanup', 'DeleteMaxSize', '100000');`
- ▶ `insert into settings (namespace, setting_name, setting_value) values ('PxService.Cleanup', 'DeleteBatchSize', '5000');`

Safe Deletes

The P6 EPPM database normally handles restoring select deleted data using a safe delete setting. While using P6 Professional, the Undo command (Edit, Undo) allows users to restore certain types of data that have been deleted. Deleted data remains in the P6 EPPM database until the `CLEANUP_LOGICAL_DELETES` procedure clears it (after 5 days, by default).

See the *P6 Professional Help* for more information about using undo.

Turning Off Safe Deletes

You can turn off safe deletes to save storage space. Turning off safe deletes disables undo functionality and instantly clears deleted data from the P6 EPPM database.

To turn off safe deletes:

- 1) Verify the current state of your safe deletes setting. In the database, if the table `ADMIN_CONFIG` has the following row, a `CONFIG_VALUE` of 'N' means turn off safe deletes.

```
CONFIG_NAME = 'SAFEDELETE.ACTIVE' and CONFIG_TYPE = 'SETTINGS'
```

Note: This is only loaded at startup. If you change `CONFIG_VALUE` while a user is running P6 Professional, the setting will not apply until the user restarts the P6 Professional session.

- 2) Once you have determined the current state of your safe deletes setting, run one of the following statements.

- ▶ To turn off safe deletes for the first time:

```
INSERT INTO ADMIN_CONFIG (CONFIG_NAME, CONFIG_TYPE, CONFIG_VALUE)
VALUES ('SAFEDELETE.ACTIVE', 'SETTINGS', 'N')
```

- ▶ To turn on safe deletes after it has been turned off:

```
UPDATE ADMIN_CONFIG SET CONFIG_VALUE = 'Y' WHERE CONFIG_NAME =
'SAFEDELETE.ACTIVE' AND CONFIG_TYPE = 'SETTINGS'
```

- ▶ To turn off safe deletes after it has been turned on:

```
UPDATE ADMIN_CONFIG SET CONFIG_VALUE = 'N' WHERE CONFIG_NAME =
'SAFEDELETE.ACTIVE' AND CONFIG_TYPE = 'SETTINGS'
```

3) Restart the P6 server.

Copyright

Oracle Primavera P6 EPPM Database Administration Guide for On-Premises

Copyright © 1999, 2020, Oracle and/or its affiliates.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Inside are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate failsafe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software or hardware and documentation may provide access to or information on content, products and services from third-parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.