

Cluster Creation on Websphere Application Server
Oracle Banking Corporate Lending
Release 14.4.0.0.0
[May] [2020]



Table of Contents

1. PURPOSE.....	1-1
2. INTRODUCTION TO WEBSPHERE.....	2-1
3. PRE-REQUISITES:	3-1
4. STEPS INVOLVED FOR CLUSTERING	4-1
4.1 CREATE PROFILE	4-1
4.1.1 Create Deployment Manager Profile.....	4-5
4.2 CREATE NODE	4-13
4.2.1 Start Node Agents	4-16
4.3 CREATE CLUSTER.....	4-16
4.3.1 Add Cluster Members	4-18
4.3.2 Start Cluster.....	4-20
4.4 CREATE PROXY SERVER.....	4-21
4.4.1 Start Proxy Server.....	4-24
4.5 CONFIGURE VIRTUAL HOST.....	4-25
4.5.1 Virtual Host Setup.....	4-26
5. CREATE RESOURCES IN CLUSTER SCOPE	5-1
6. DEPLOY APPLICATION TO CLUSTER	6-1
6.1.1 Test the application.....	6-2

1. Purpose


This document explains steps to create Cluster on Websphere Application Server 8.5 and also setup the proxy.

2. Introduction to Websphere

IBM websphere application server cluster deployment contains the below key elements

- Cell
- Nodes
 - Deployment Manager Node- “DMGR”
 - Node- “NodeXX”
 - Node Agent- “NAXX”
- Profiles
- Cluster
- Cluster Members
- Data Sources

Profile



- **Cell:** A cell is a grouping of nodes into a single administrative domain. In a Network Deployment environment, a cell can consist of multiple nodes (and node groups), which are all administered from a single point, the deployment manager.
- **Node:** A node is an administrative grouping of application servers for configuration and operational management within one operating system instance
- **Node Agent:** In distributed server configurations, each node has a node agent that works with the deployment manager to manage administration processes. A node agent is created automatically when you add (federate) a stand-alone node to a cell.
- **Cluster:** A cluster is a logical collection of application server processes that provides workload balancing and high availability. Application servers that belong to a cluster are members of that cluster and must all have identical application components deployed on them.
- **A profile** is a Websphere runtime environment formed by collection of User data and Product files. Product Files are shared application binaries for Websphere. User data is set of user customizations for a specific runtime environment.

Prominent profile types are:

- **Stand-alone Application Server:** An application server environment runs Enterprise Application. Application server is managed from its own administrative console and functions independently from other application server.
- **Deployment Manager:** A Deployment Manager manages operations for a logical group or cell of other servers. It is the central administration point of a cell that consists of multiple nodes and node groups in a distributed server configuration. The deployment manager uses the node agent to manage the application servers within one node. A deployment manager provides management capability for multiple federated nodes and can manage nodes that span multiple systems and platforms. A node can only be managed by a single deployment manager and must be federated to the cell of that deployment manager.

Note ** Deployment Manager is part of Network Deployment Edition of Websphere.

3. Pre-requisites:

Before proceeding with the cluster setup ensure that the below resources are created

- JDBC Provider
- Datasource
- Queue Connection Factory
- JMS Queue

The instructions for resource creation are available in document

<installer>\Docs\WEBSPPHERE\Resource_Creation_WAS.doc


- For SSL configuration in Websphere, refer to the document SSL_Configuration_WAS.doc
- For application deployment, refer to document FCUBS_Application_WAS.doc
- For deployment of Gateway applications, refer to document GATEWAY_Applications_WAS.doc

4. Steps involved for Clustering


4.1 Create Profile

Go to Profile Management Tool


Navigation: IBM WebSphere > *IBM WebSphere Application Server V8.5* > *Tools* > *Profile Management Tool*



Navigation : *Profile Management Tool* > *Create*



Navigation : *Application Server > Next*



Navigation : *Typical profile creation > Next*

Profile Creation Options

Choose the profile creation process that meets your needs. Pick the Typical option to allow the Profile Management Tool to assign a set of default configuration values to the profile. Pick the Advanced option to specify your own configuration values for the profile.

☒ **Typical profile creation**

Create an application server profile that uses default configuration settings. The Profile Management Tool assigns unique names to the profile, node, and host. The tool also assigns unique port values. The administrative console and the default application will be installed. You can optionally select whether to enable administrative security. The tool might create a system service to run the application server depending on the operating system of your machine and the privileges assigned to your user account.

Note: Default personal certificates expire in one year. Select Advanced profile creation to create a personal certificate with a different expiration.

☐ **Advanced profile creation**

Create an application server using default configuration settings or specify your own values for settings such as the location of the profile and names of the profile, node, and host. You can assign your own port values. You can optionally choose whether to deploy the administrative console and Sample applications, and create a Web server definition. You might have the option to run the application server as a system service depending on the operating system of your machine and the privileges assigned to your user account.

< Back **Next >** Cancel Finish

Navigation: *Enable administrative security > Next*

Administrative Security

Choose whether to enable administrative security. To enable security, supply a user name and password for logging into administrative tools. This administrative user is created in a repository within the application server. After profile creation finishes, you can add more users, groups, or external repositories.

☒ **Enable administrative security**

User name:
websphere

Password:

Confirm password:

See the information center for more information about administrative security.
[View the online information center](#)

< Back **Next >** Cancel Finish

Navigation : *Create Summary*

Profile Management Tool 8.5

Profile Creation Summary

Review the information in the summary for correctness. If the information is correct, click **Create** to start creating a new profile. Click **Back** to change values on the previous panels.

Application server environment to create: Application server
 Location: /opt/IBM/WebSphere/AppServer/profiles/AppSrv06
 Disk space required: 200 MB

Profile name: AppSrv06
 Make this profile the default: True
 Performance tuning setting: Standard

Node name: ofss220367Node01
 Server name: server1
 Host name: ofss220367.in.oracle.com

Deploy the administrative console (recommended): True
 Deploy the default application: True

Enable administrative security (recommended): True

Administrative console port: 9060
 Administrative console secure port: 9043
 HTTP transport port: 9080
 HTTPS transport port: 9443
 Bootstrap port: 2809
 SOAP connector port: 8880

Run application server as a service: False

< Back Create Cancel Finish

Navigation : *Finish*

Profile Management Tool 8.5

Profile Creation Complete

The Profile Management Tool created the profile successfully.

The next step is to decide whether to federate the application server into a deployment manager cell.

To federate the application server, use either the **addNode** command or the administrative console of the deployment manager. Using the administrative console requires the application server to be running.

You can start and stop the application server from the command line or the First steps console. The First steps console also has links to an installation verification test and other information and features that relate to the application server.


☒ Launch the First steps console.

To start the Profile Management Tool later, use the **PMT** command in the `app_server_root/bin/ProfileManagement` directory or the option in the First steps console.


< Back Next > Cancel Finish

4.1.1 Create Deployment Manager Profile


Navigation : *Profile Management Tool > Create*




Navigation : *Management >Next*



Navigation : *Deployment Manager > Next*



Navigation: *Typical profile creation > Next*



Navigation: *Enable administrative security > Next*

Profile Management Tool 8.5

Administrative Security

Choose whether to enable administrative security. To enable security, supply a user name and password for logging into administrative tools. This administrative user is created in a repository within the application server. After profile creation finishes, you can add more users, groups, or external repositories.

☒ Enable administrative security

User name:
admin


Password:

Confirm password:

See the information center for more information about administrative security.
[View the online information center](#)

< Back **Next >** Cancel Finish


Navigation : Create



The screenshot shows a window titled "Profile Management Tool 8.5" with a sub-header "Profile Creation Summary". Below the header is a message: "Review the information in the summary for correctness. If the information is correct, click **Create** to start creating a new profile. Click **Back** to change values on the previous panels." The main area contains the following configuration details:


- Application server environment to create: Management
- Server type: Deployment manager
- Location: /opt/IBM/WebSphere/AppServer/profiles/Dmgr04
- Disk space required: 30 MB
- Profile name: Dmgr04
- Make this profile the default: False
- Cell name: ofss220367Cell01
- Node name: ofss220367CellManager01
- Host name: ofss220367.in.oracle.com
- Deploy the administrative console (recommended): True
- Enable administrative security (recommended): True
- Administrative console port: 9061
- Administrative console secure port: 9044
- Deployment manager bootstrap port: 9809
- Deployment manager SOAP connector port: 8879
- Run deployment manager as a service: False

At the bottom right, there are four buttons: "< Back", "Create", "Cancel", and "Finish".



Start Deployment Manager & Open Administrative Console


Navigation : IBM WebSphere > IBM WebSphere Application Server V8.5 > Profiles > Dmgr[i]>Start the deployment *manager* > *Administrative console*



Log into Deployment Manager Console




Navigation : System administration > Nodes > Add Node



4.2 Create Node

Navigation : *System administration > Nodes > Add Node*



Provide the following field information and Click 'OK'

Host	: Host Machine with running Application Server
JMX Connector type	: SOAP
JMX Connector Port	: SOAP_CONNECTOR_ADDRESS of Application Server
Application server user name	: Application server user id
Application server password	: Application server password
Deployment manager user name	: Deployment manager user id
Deployment manager password	: Deployment manager password

WebSphere software

Welcome admin Help Logout IBM

Views: All tasks

- Welcome
- Guided Activities
- Servers
- Applications
- Jobs
- Services
- Resources
- Runtime Operations
- Security
- Operational policies
- Environment
- System administration
 - Cell
 - Job manager
 - Extended Repository Service
 - Save changes to master repository
 - Deployment manager
 - Nodes
 - Middleware nodes
 - Node agents
 - Middleware descriptors
 - Node groups
- Centralized Installation Manager
- Task Management
 - Console Preferences
 - Job scheduler
 - Visualization Data Service
 - Console Identity
- Users and Groups
- Monitoring and Tuning
- Troubleshooting
- Service integration
- UDDI

Nodes

Add Managed Node

Use this page to identify a stand-alone application server process that is running. Start the application server, if necessary, or add the node from the command line by running the addnode command from the bin directory of the stopped application server profile.

Node connection

Host
ofss220367

JMX connector type
SOAP

JMX connector port
8880

Application server user name
webosphere

Application server password

Deployment manager user name
admin

Deployment manager password

Config URL
file:///C:/USER_INSTALL_ROOT/properties/sas.dll

Options

☐ Include applications

☐ Include buses

Starting port

☒ Use default

☐ Specify

Port number

OK Cancel

Field help
For field help information, select a field label or list marker when the help cursor is displayed.

Page help
[More information about this page](#)

Oracle.com https://ofss220367.in.oracle.com:9544/evm/console/login.do?act&en=secure

WebSphere software

Welcome admin Help Logout IBM

- Generic server clusters
- Cluster topology
- On Demand Router clusters
- Dynamic clusters
- DataPower
- Core Group
- Applications
- Jobs
- Services
- Resources
- Runtime Operations
- Security
- Operational policies
- Environment
- System administration
 - Cell
 - Job manager
 - Extended Repository Service
 - Save changes to master repository
 - Deployment manager
 - Nodes
 - Middleware nodes
 - Node agents
 - Middleware descriptors
 - Node groups
- Task Management
 - Console Preferences
 - Job scheduler
 - Visualization Data Service

Adding node

ADMU0001: Begin federation of node ofss220367Node01 with Deployment Manager at ofss220367.in.oracle.com:8879.

ADMU0006: Successfully connected to Deployment Manager Server: ofss220367.in.oracle.com:8879

ADMU0505: Servers found in configuration:

ADMU0506: Server name: server1

ADMU0104: Stopping all server processes for node ofss220367Node01

ADMU0510: Server server1 is now STOPPED

ADMU0024: Deleting the old backup directory.

ADMU0015: Backing up the original cell. Please Wait...

ADMU0012: Creating Node Agent config. Node01

ADMU0014: Adding node ofss220367Node01 configuration to cell: ofss220367Cell01

ADMU0016: Synchronizing configuration between node and cell.

Transferring data from ofss220367.in.oracle.com...

Nodes

Use this page to manage nodes in the application server environment. A node corresponds to a physical computer system with a distinct IP host address. The following table lists the managed and unmanaged nodes in this cell. The first node is the deployment manager. Add new nodes to the cell and to this list by clicking Add Node.

Preferences

Add Node Remove Node Force Delete Synchronize Pull Resynchronize Stop

Select	Name	Host Name	Version	Discovery Protocol	Status
☒	ofss220367CellManager01	ofss220367.in.oracle.com	ND 8.5.0.0	TCP	+
☐	ofss220367Node01	ofss220367.in.oracle.com	ND 8.5.0.0	TCP	+
Total: 2					

Create necessary number of nodes following same instructions above:

Messages

Your workspace has been auto-refreshed from the master configuration. You can disable auto-refresh in your user preferences.

Nodes

Use this page to manage nodes in the application server environment. A node corresponds to a physical computer system with a distinct IP host address. The following table lists the managed and unmanaged nodes in this cell. The first node is the deployment manager. Add new nodes to the cell and to this list by clicking Add Node.

Preferences

Add Node Remove Node Force Delete Synchronize Pull Resynchronize Stop

Select	Name	Host Name	Version	Discovery Protocol	Status
☒	ofss220367CellManager01	ofss220367.in.oracle.com	ND 8.5.0.0	TCP	+
☐	ofss220367Node01	ofss220367.in.oracle.com	ND 8.5.0.0	TCP	+
☐	ofss222555Node01	ofss222555.in.oracle.com	ND 8.5.0.0	TCP	+
Total: 3					

4.2.1 Start Node Agents

Navigation : *System administration> Node agents>Restart*

The screenshot shows the WebSphere Administration Console interface. The left-hand navigation pane is expanded to 'System administration' > 'Node agents'. The main content area is titled 'Node agents' and contains a description of the node agent process. Below the description are buttons for 'Stop', 'Restart', and 'Restart all Servers on Node'. A table lists the resources managed by the node agents:

Select	Name	Node	Host Name	Version	Status
☐	nodeagent	ots222555Node01	ots222555.in.oracle.com	ND 8.5.0.0	+
☐	nodeagent	ots220367Node01	ots220367.in.oracle.com	ND 8.5.0.0	+

The table indicates a total of 2 resources. On the right side of the console, there are links for 'Field help' and 'Page help'.

4.3 Create Cluster


Navigation: *Servers>Clusters> WebSphere application server clusters > New*

The screenshot shows the WebSphere Administration Console interface. The left-hand navigation pane is expanded to 'Servers' > 'Clusters'. The main content area is titled 'WebSphere application server clusters' and contains a description of a server cluster. Below the description are buttons for 'New...', 'Delete', 'Start', 'Stop', 'Ripplestart', and 'ImmediateStop'. A table lists the clusters:

Select	Name	Status
☐	None	

The table indicates a total of 0 clusters. On the right side of the console, there are links for 'Field help', 'Page help', and 'Command Assistant'.

Navigation : *Uncheck [Prefer Local] > Next*



4.3.1 Add Cluster Members

WebSphere software

Welcome admin Help Logout IBM

Cell=ofas220367/Cell01, Profile=OmniGr04

Create a new cluster

Step 1: Enter basic cluster information

Step 2: Create first cluster member

Step 3: Create additional cluster members

Step 4: Summary

Create first cluster member

The first cluster member determines the server settings for the cluster members. A server configuration template is created from the first member and stored as part of the cluster data. Additional cluster members are copied from this template.

Member name: MS_1

Select node: ofas220367Node01 (ND 8.5.0.0)

Weight: 2 (0..100)

☒ Generate unique HTTP ports

Select how the server resources are promoted in the cluster: Cluster

Select basis for first cluster member:

- ☒ Create the member using an application server template.
default
- ☐ Create the member using an existing application server as a template.
ofas220367Cell01/ofas220367Node01 (ND 8.5.0.0)/MS_1
- ☐ Create the member by converting an existing application server.
ofas220367Cell01/ofas220367Node01 (ND 8.5.0.0)/MS_1
- ☐ None. Create an empty cluster.

Previous Next Cancel

Field help: For field help information, select a field label or list marker when the help cursor is displayed.

Page help: More information about this page

Add required number of cluster members

Navigation : Add Member > Next

WebSphere software

Welcome admin Help Logout IBM

Cell=ofas220367/Cell01, Profile=OmniGr04

Create a new cluster

Step 1: Enter basic cluster information

Step 2: Create first cluster member

Step 3: Create additional cluster members

Step 4: Summary

Create additional cluster members

Enter information about this new cluster member, and click Add Member to add this cluster member to the member list. A server configuration template is created from the first member, and stored as part of the cluster data. Additional cluster members are copied from this template.

Member name: MS_2

Select node: ofas220367Node01 (ND 8.5.0.0)

Weight: 2 (0..100)

☒ Generate unique HTTP ports

Add Member

Use the Edit function to modify the properties of a cluster member in this list. Use the Delete function to remove a cluster member from this list. You are not allowed to edit or remove the first cluster member.

Select	Member name	Nodes	Version	Weight
☐	MS_1	ofas220367Node01	ND 8.5.0.0	2
Total 1				

Previous Next Cancel

Field help: For field help information, select a field label or list marker when the help cursor is displayed.

Page help: More information about this page

Navigation : Next

Create a new cluster

Step 1: Enter basic cluster information
Step 2: Create first cluster member
→ **Step 3: Create additional cluster members**
Step 4: Summary

Create additional cluster members

Enter information about this new cluster member, and click Add Member to add this cluster member to the member list. A server configuration template is created from the first member, and stored as part of the cluster data. Additional cluster members are copied from this template.

Member name:

Select node:

Weight: (0..100)

☒ Generate unique HTTP ports

Add Member

Use the Edit function to modify the properties of a cluster member in this list. Use the Delete function to remove a cluster member from this list. You are not allowed to edit or remove the first cluster member.

Edit Delete

Select	Member name	Nodes	Version	Weight
☐	MS_1	ofss220367Node01	ND 8.5.0.0	2
☐	MS_2	ofss22555Node01	ND 8.5.0.0	2

Total 2

Previous Next Cancel

Field help
For field help information, select a field label or list marker when the help cursor is displayed.

Page help
[More information about this page](#)

Navigation : Finish

Create a new cluster

Step 1: Enter basic cluster information
Step 2: Create first cluster member
Step 3: Create additional cluster members
→ **Step 4: Summary**

Summary

Summary of actions:

Options	Values
Cluster Name	CLUSTER_1
Core Group	DefaultCoreGroup
Node group	DefaultNodeGroup
Prefer local	false
Configure HTTP session memory-to-memory replication	false
Server name	MS_1
Node	ofss220367Node01(ND 8.5.0.0)
Weight	2
Clone Template	default
Clone Basis	Create the member using an application server template.
Select how the server resources are promoted in the cluster.	cluster
Generate unique HTTP ports	true
Server name	MS_2
Node	ofss220367Node01(ND 8.5.0.0)
Weight	2
Clone Template	Version 8.5 member template
Generate unique HTTP ports	true

Previous Finish Cancel

Field help
For field help information, select a field label or list marker when the help cursor is displayed.

Page help
[More information about this page](#)

4.3.2 Start Cluster

WebSphere application server clusters

Use this page to change the configuration settings for a cluster. A server cluster consists of a group of application servers. If one of the member servers fails, requests will be routed to other members of the cluster. Learn more about this task in a [guided activity](#). A guided activity provides a list of task steps and more general information about the topic.

Preferences

New... Delete Start Stop Ripplestart ImmediateStop

Select	Name	Status
☒	CLUSTER_1	X

You can administer the following resources:

Total 1

Field help
For field help information, select field label or list item when the help is displayed.

Page help
[More information, this page](#)

Command Assistant
[View administrative scripting command list action](#)

WebSphere application server clusters

Use this page to change the configuration settings for a cluster. A server cluster consists of a group of application servers. If one of the member servers fails, requests will be routed to other members of the cluster. Learn more about this task in a [guided activity](#). A guided activity provides a list of task steps and more general information about the topic.

Preferences

New... Delete Start Stop Ripplestart ImmediateStop

Select	Name	Status
☐	CLUSTER_1	→

You can administer the following resources:

Total 1


Field help
For field help information, select field label or list item when the help is displayed.

Page help
[More information, this page](#)


Command Assistant
[View administrative scripting command list action](#)



4.4 Create Proxy Server



Navigation : Servers > Server Types > WebSphere proxy servers > New




Navigation : [Select appropriate Node] > Next







4.4.1 Start Proxy Server



WebSphere proxy servers


A server that acts as an intermediary for HTTP requests that are serviced by application servers or web servers. The proxy server acts as a surrogate for the application servers in the enterprise and can enhance the overall experience by providing services such as workload management, cross-cell routing, and other services that offload the application server.

Preferences

new... Delete Templates... Start Stop

Select	Name	Node	Host Name	Version	Current security level	Protocol	Status
☒	proxy_server_1	otss220367Node01	otss220367.in.oracle.com	ND 8.5.0.0	Not applicable	HTTP, SIP	Start

Total 1



WebSphere proxy servers

Messages

Server otss220367Node01:proxy_server_1 started successfully. The collection may need to be refreshed to show the current server status. [View JVM logs](#) for further details.

WebSphere proxy servers

A server that acts as an intermediary for HTTP requests that are serviced by application servers or web servers. The proxy server acts as a surrogate for the application servers in the enterprise and can enhance the overall experience by providing services such as workload management, cross-cell routing, and other services that offload the application server.

Preferences

new... Delete Templates... Start Stop

Select	Name	Node	Host Name	Version	Current security level	Protocol	Status
☐	proxy_server_1	otss220367Node01	otss220367.in.oracle.com	ND 8.5.0.0	Not applicable	HTTP, SIP	Stop

Total 1


4.5 Configure Virtual Host

Make a note of “WC_defaulthost”/“WS_defaulthost_secure” port for server MS1 : 9081/9444

The screenshot shows the Oracle WebLogic Server Administration Console. The left sidebar contains a tree view of the console's structure, including 'Home', 'Servers', 'Clusters', 'Applications', 'Services', 'Permissions', 'Runtime Operations', 'Security', 'Operational Policies', 'Environment', and 'System Administration'. The main content area is titled 'Virtual Hosts' and displays a table of virtual hosts for the server 'MS1'. The table has columns for 'Name', 'Host', 'Port', and 'Transport Details'. The following table represents the data shown in the screenshot:


Name	Host	Port	Transport Details
☐ WC_defaulthost_secure	+	9444	Not associated to a protocol
☐ WC_defaulthost	+	9081	Not associated to a protocol
☐ WC_defaulthost_secure	+	9043	Not associated to a protocol
☐ WC_defaulthost	+	9042	Not associated to a protocol
☐ HTTP_CONNECTOR_ADDRESS	oracle20067.oracle.com	8881	Not associated to a protocol
☐ HTTP_DEFAULTHOST_SECURE	+	9082	Not associated to a protocol
☐ HTTP_DEFAULTHOST	+	9081	Not associated to a protocol
☐ HTTP_HTTPINJECT_SECURE_ADDRESS	+	9079	Not associated to a protocol
☐ HTTP_HTTPINJECT_ADDRESS	+	9080	Not associated to a protocol
☐ HTTP_INJECTOR_SECURE_ADDRESS	+	9087	Not associated to a protocol
☐ HTTP_INJECTOR_ADDRESS	+	9086	Not associated to a protocol
☐ HTTP_SERVERS_LISTENER_ADDRESS	oracle20067.oracle.com	9407	Not associated to a protocol
☐ OVERLAY_VPN_LISTENER_ADDRESS	+	11009	Not associated to a protocol
☐ OVERLAY_TCP_LISTENER_ADDRESS	+	11010	Not associated to a protocol
☐ JMS_LISTENER_ADDRESS	oracle20067.oracle.com	9102	Not associated to a protocol

Make a note of “WC_defaulthost”/“WS_defaulthost_secure” for MS2 : 9082/9445




4.5.1 Virtual Host Setup


Navigation : *Environment>Virtual hosts>proxy_host*





Navigation : Host Aliases



Navigation : Environment>Virtual hosts>proxy_host>Host Aliases > New



Create New Alias for default port in managed server <<9081>>:



Similarly create proxy alias for all cluster related server default ports


The screenshot displays the WebSphere Admin Console interface. On the left is a navigation tree with categories like Welcome, Global Actions, Servers, Applications, and Monitoring. The main content area is titled 'Virtual Hosts > proxy_host > Host Aliases'. Below the title, there's a description: 'Use this page to edit, create, or delete a domain name system (DNS) alias by which the virtual host is known.' and a 'Refresh' button. A table lists the host aliases:

Select	Host Name	Port
☐		8080
☐		8888
☐		9082
☐		9448
		Total 4


On the right side of the console, there are links for 'Field help', 'Page help', and 'Command Reference'.



5. Create Resources in Cluster Scope

JDBC Provider :




Datasource :





Create Message Listeners for individual Servers in Cluster


Navigation : *Middleware servers > MS_1 > Message listener service > Listener Ports*




Navigation : *Middleware servers > MS_2 > Message listener service > Listener Ports*

6. Deploy Application to Cluster

While deploying ensure the application is installed to Cluster



Start FCUBS application



6.1.1 Test the application

Make a note of the ports `PROXY_HTTPS_ADDRESS/PROXY_HTTP_ADDRESS` to access the application.


Navigation : Servers > Server Types > WebSphere proxy servers > [proxy_server_1] > Ports

The screenshot shows the WebSphere Administration Console interface. On the left is a navigation tree with categories like Servers, Clusters, Applications, and more. The main pane displays the 'Ports' configuration for 'proxy_server_1'. It includes a table with columns: Name, Host, Port, and Transport Details. Two rows are highlighted with a red rectangle: 'PROXY_HTTPS_ADDRESS' on port 443 and 'PROXY_HTTP_ADDRESS' on port 80. Both are marked as 'Not associated transports'. Other ports listed include PROXY_TCP, PROXY_UDP, and various listener ports.

Name	Host	Port	Transport Details
PROXY_TCP_ADDRESS	afex223567.in.oracle.com	8013	No associated transports
PROXY_UDP_ADDRESS	afex223567.in.oracle.com	0	No associated transports
PROXY_HTTPS_ADDRESS	*	443	Not associated transports
PROXY_HTTP_ADDRESS	*	80	Not associated transports
PROXY_TCP_ADDRESS	*	8081	No associated transports
PROXY_UDP_ADDRESS	*	5090	No associated transports
PROXY_HTTPS_ADDRESS	afex223567.in.oracle.com	0	No associated transports
PROXY_HTTP_ADDRESS	afex223567.in.oracle.com	8883	No associated transports

Launch Application:

URL : `http://<host>:<PROXY_HTTP_ADDRESS>/FCJNeoWeb` or
`https://<host>:<PROXY_HTTPS_ADDRESS>/FCJNeoWeb`



ORACLE®

ORACLE®



Cluster Creation on Websphere
[May] [2020]
Version 14.4.0.0.0

Oracle Financial Services Software Limited
Oracle Park
Off Western Express Highway
Goregaon (East)
Mumbai, Maharashtra 400 063
India

Worldwide Inquiries:
Phone: +91 22 6718 3000
Fax: +91 22 6718 3001
<https://www.oracle.com/industries/financial-services/index.html>

Copyright © [2007], [2020], Oracle and/or its affiliates. All rights reserved.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate failsafe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.