

Configuring JMS on Weblogic Server 12c
Oracle Banking Corporate Lending
Release 14.4.0.0.0
[May] [2020]



Table of Contents

1. INTRODUCTION	1-1
1.1 PURPOSE	1-1
1.2 INTRODUCTION	1-1
1.3 WEBLOGIC 12C NEW FEATURES	1-2
1.4 COMPONENTS DIAGRAM & DATA FLOW	1-3
2. PRE-REQUISITES	1-1
2.1 MACHINES	1-1
2.2 DYNAMIC CLUSTERS AND MANAGED SERVERS	1-1
2.3 DATASOURCE	1-2
2.4 SHARED FOLDER.....	1-2
3. JMS CONFIGURATION	1-1
3.1 PERSISTENCE STORE CREATION	1-1
3.2 JMS SERVER CREATION	1-3
3.3 CLUSTER CONFIGURATION FOR SERVICE MIGRATION.....	1-5
4. JMS MODULE CREATION	1-2
4.1 MODULE CREATION.....	1-2
4.2 SUB DEPLOYMENT CREATION	1-4
4.3 RESOURCE CREATION	1-6
4.3.1 Queue Creation	1-6
4.3.2 Connection Factory Creation.....	1-9
5. SERVER RESTART.....	1-2
6. FOREIGN SERVER CREATION.....	1-1
6.1 MODULE CREATION.....	1-1
6.2 FOREIGN SERVER CREATION	1-3
6.3 FOREIGN SERVER CONFIGURATION	1-7
7. APPLICATION DEPLOYMENT.....	1-1
8. FREQUENTLY ASKED QUESTIONS	1-2
8.1 APPLICATION AND JMS CLUSTER DEPLOYED ON SAME CLUSTER	1-2
8.2 APPLICATION SHOWS WARNING UPON RESTART OF MANAGED SERVERS.....	1-2
8.3 SECURING FILE STORE DATA	1-3
8.4 T3S PROTOCOL	1-3
8.5 HOW TO TEST THE DEPLOYMENT	1-3
8.6 INCREASE MAXIMUM NUMBER OF MESSAGE-DRIVEN BEAN THREADS.....	1-5
8.6.1 Modify weblogic-ejb-jar.xml	1-5
8.6.2 Work Manager Creation.....	1-6
8.7 HOW HIGH AVAILABILITY IS ACHIEVED.....	1-9
8.8 HOW TO SETUP FOR SCHEDULER/NOTIFICATIONS.....	1-10
8.9 WHAT OTHER MODULES USES JMS QUEUE'S.....	1-10
8.10 REFERENCES	1-10

1 Introduction

1.1 Purpose

The purpose of this document is to explain the steps required for JMS Configuration in cluster mode for

- 1) FCUBS 12.1
- 2) WebLogic Server 12.1.3.0.0

1.2 Introduction

Below is brief description on major components in Weblogic JMS Server architecture

JMS Server

JMS server acts as management container for JMS queue and topic resources defined within JMS modules that are targeted to specific that JMS server. A JMS server's main responsibility is to maintain persistent storage for these resources, maintain the state of durable subscriber and etc. JMS servers can host a defined set of modules and any associated persistent storage that reside on a WebLogic Server instance

JMS Module

JMS modules are application-related definitions that are independent of the domain environment. JMS modules group JMS configuration resources (such as queues, topics, and connections factories). These are outside domain configuration. JMS modules are globally available for targeting to servers and clusters configured in the domain and therefore are available to all the applications deployed on the same targeted. JMS modules contain configuration resources, such as standalone queue and topic destinations, distributed destinations, and connection factories.

Subdeployment

Subdeployment is also known as Advanced Targeting. Subdeployment resource is a bridge between the group of JMS resources and JMS Servers. When you create a JMS resource you need to choose one Subdeployment.

JMS Resources

- 1) **Queue** defines a point-to-point destination type, which are used for asynchronous peer communications. A message delivered to queue is distributed to only one customer.
- 2) **Topic** defines a publish/subscribe destination type, which are used for asynchronous peer communication. A message delivered to topic is distributed to all topic consumers
- 3) **Distributed queue** defines a set of queues that are distributed on multiple JMS servers, but are accessible as a single, logical queue to JMS clients
- 4) **Distributed topic** defines a set of topics that are distributed on multiple JMS servers, but which as accessible as a single, logical topic to JMS clients.

- 5) **Uniform Distributed Queue:** queue members are created uniformly from a common configuration.

Persistence store

A persistent store provides a built-in, high-performance storage solution for weblogic server subsystems and services that required persistence. There are two type of mechanism to store the message


- 1) File based persistence store → Message is stored in a file
- 2) DB based persistence store → Message is stored in Database.

1.3 Weblogic 12c New Features


Before weblogic 12c JMS Servers and stores are targeted to individual WLS Servers. Scaling up requires configure the JMS server, the store and target it to new WLS Server

In 12c JMS Servers and stores are targeted to WLS cluster. Scaling up requires to add a WLS server to the cluster.

Architecture previous to 12c




Architecture in 12c



1.4 Components Diagram & Data Flow

Below is the flow diagram which indicates various components that are used and the document explain steps to create.




2. Pre-Requisites

The document assumes that the below are created before proceeding JMS creation.

2.1 Machines

MAC-1 & MAC-2



ORACLE WebLogic Server Administration Console 12c

Home > Summary of Servers > Summary of Machines

Summary of Machines

A machine is the logical representation of the computer that hosts one or more WebLogic Server instances (servers). WebLogic Server uses configured machine names to determine the optimum server in a cluster to which certain tasks, such as HTTP session replication, are delegated. The Administration Server uses the machine definition in conjunction with Node Manager to start remote servers.

This page displays key information about each machine that has been configured in the current WebLogic Server domain.

Customize this table


Machines

Name	Type
MAC-1	Machine
MAC-2	Machine

Showing 1 to 2 of 2 Previous | Next

2.2 Dynamic Clusters and Managed Servers

Ensure Dynamic cluster for FCUBS (4 Managed Servers) and Dynamic cluster for JMS Deployment (2 Managed Servers)



ORACLE WebLogic Server Administration Console 12c

Home > Summary of Servers > Summary of Clusters > Summary of Server Templates > Summary of Clusters > Summary of Servers > Summary of Clusters > Summary of Server Templates > Summary of Clusters > Summary of Servers > Summary of Clusters

Summary of Clusters

This page summarizes the clusters that have been configured in the current WebLogic Server domain.

A cluster defines groups of WebLogic Server servers that work together to increase scalability and reliability.

Customize this table

Clusters (Filtered - More Columns Exist)

Click the **Lock & Edit** button in the Change Center to activate all the buttons on this page.

Name	Cluster Address	Cluster Messaging Mode	Migration Basis	Default Load Algorithm	Replication Type	Cluster Broadcast Channel	Servers
Cluster-App		Unicast	Database	Round Robin	(None)		DC_FCUBS_1, DC_FCUBS_2, DC_FCUBS_3, DC_FCUBS_4
Cluster-JMS		Unicast	Database	Round Robin	(None)		DC_JMS_1, DC_JMS_2

Showing 1 to 2 of 2 Previous | Next

ORACLE WebLogic Server Administration Console 12c

Home Log Out Preferences Record Help Welcome, weblogic Connected to: FCUBSDomain

Home > Summary of Server Templates > Summary of Clusters > Summary of Servers > Summary of Clusters > Summary of Servers > Summary of Clusters > Cluster-JMS > Summary of Servers > Summary of Servers

Summary of Servers

Configuration Control

A server is an instance of WebLogic Server that runs in its own Java Virtual Machine (JVM) and has its own configuration. This page summarizes each server that has been configured in the current WebLogic Server domain.

[Customize this table](#)

Servers (Filtered - More Columns Exist)

Click the **Lock & Edit** button in the Change Center to activate all the buttons on this page.

New Clone Delete Showing 1 to 7 of 7 Previous | Next

☐	Name	Type	Cluster	Machine	State	Health	Listen Port
☐	AdminServer(admin)	Configured			RUNNING	OK	7001
☐	DC_FCUBS_1	Dynamic	Cluster-App	MAC-1	SHUTDOWN	Not reachable	7101
☐	DC_FCUBS_2	Dynamic	Cluster-App	MAC-2	SHUTDOWN	Not reachable	7102
☐	DC_FCUBS_3	Dynamic	Cluster-App	MAC-1	SHUTDOWN	Not reachable	7103
☐	DC_FCUBS_4	Dynamic	Cluster-App	MAC-2	SHUTDOWN	Not reachable	7104
☐	DC_JMS_1	Dynamic	Cluster-JMS	MAC-1	SHUTDOWN	Not reachable	7106
☐	DC_JMS_2	Dynamic	Cluster-JMS	MAC-2	SHUTDOWN	Not reachable	7107

New Clone Delete Showing 1 to 7 of 7 Previous | Next

Change Center

View changes and restarts

Click the Lock & Edit button to modify, add or delete items in this domain.

Lock & Edit

Release Configuration

Domain Structure

- Environment
 - Servers
 - Clusters
 - Server Templates
 - Migratable Targets
 - Coherence Clusters
 - Machines
 - Virtual Hosts
 - Work Managers
 - Startup and Shutdown Classes
 - Deployments
 - Services
 - Security Realms

How do I...

- Create Managed Servers
- Clone servers
- Delete Managed Servers
- Delete the Administration Server
- Start and stop servers

System Status

Health of Running Servers

Failed (0)

2.3 DataSource

Ensure that DataSource required for the MDB ear is created with Target as Cluster-App

ORACLE WebLogic Server Administration Console

Home Log Out Preferences Record Help Welcome, weblogic Connected to: base_domain

Home > JMS Modules > JMS_MODULE > MDB_QUEUE > Summary of JMS Messages > JMS Modules > JMS_MODULE > MDB_QUEUE > Summary of JMS Messages > Summary of Deployments > Summary of JDBC Data Sources

Summary of JDBC Data Sources

Configuration Monitoring

A JDBC data source is an object bound to the JNDI tree that provides database connectivity through a pool of JDBC connections. Applications can look up a data source on the JNDI tree and then borrow a database connection from a data source. This page summarizes the JDBC data source objects that have been created in this domain.

[Customize this table](#)

Data Sources (Filtered - More Columns Exist)

New Delete Showing 1 to 3 of 3 Previous | Next

☐	Name	Type	JNDI Name	Targets
☐	FLEXTST.WORLD	Generic	FLEXTST.WORLD	Cluster-App
☐	...	...	...	...

Change Center

View changes and restarts

Configuration editing is enabled. Future changes will automatically be activated as you modify, add or delete items in this domain.

Domain Structure

- Services
 - Messaging
 - JMS Servers
 - Store-and-Forward Agents
 - JMS Modules
 - Path Services
 - Bridges
 - Data Sources**
 - Persistent Stores
 - Foreign JNDI Providers
 - Work Contexts
 - XML Registries
 - XML Entity Caches
 - JCOM



2.4 Shared Folder

A shared folder for File Store Creation is required and this folder should be accessible across both the servers (eg, NFS mount).

3. JMS Configuration

3.1 Persistence Store Creation

1) Navigate to Services → Persistent Stores → New → Create FileStore



2) Select **Cluster-JMS** under target dropdown and Click on OK

The screenshot shows the Oracle WebLogic Server Administration Console. On the left, the 'Change Center' panel indicates 'No pending changes exist' and provides 'Lock & Edit' and 'Release Configuration' buttons. Below it, the 'Domain Structure' tree shows the hierarchy from Environment to Services, with 'Messaging' expanded. The 'How do I...' panel lists 'Create File Stores' and 'Monitor persistent stores'. The main content area displays the breadcrumb path: Home > Summary of Clusters > Summary of Servers > Summary of Clusters > Summary of Servers > Summary of Clusters > Cluster-JMS > Summary of Servers > Summary of Clusters > Summary of Servers > Summary of Persistent Stores. The 'Create a New File Store' dialog is open, showing 'File Store Properties'. It includes a 'Name' field with 'FileStore-1', a 'Target' dropdown set to 'Cluster-JMS', and a 'Directory' field with '/scratch/work_area/JMS_FILESTORE'. The dialog has 'OK' and 'Cancel' buttons.


3) **FileStore-1** is created

The screenshot shows the Oracle WebLogic Server Administration Console after the file store has been created. The 'Change Center' panel now shows 'Click the Lock & Edit button to modify, add or delete items in this domain.' The 'Domain Structure' tree shows 'Persistent Stores' under 'Services'. The main content area displays the breadcrumb path: Home > Summary of Clusters > Summary of Servers > Summary of Clusters > Summary of Servers > Summary of Clusters > Cluster-JMS > Summary of Servers > Summary of Clusters > Summary of Servers > Summary of Persistent Stores. A green message states: 'All changes have been activated. No restarts are necessary.' Below this, the 'Summary of Persistent Stores' section provides a description of persistent stores and a 'Customize this table' link. A table titled 'Persistent Stores' is shown with columns 'Name', 'Type', and 'Target'. The table contains one entry: 'FileStore-1' of type 'FileStore' with target 'Cluster-JMS'. The table has 'New' and 'Delete' buttons at the top and bottom. The page indicates 'Showing 1 to 1 of 1' items.


Name	Type	Target
FileStore-1	FileStore	Cluster-JMS

3.2 JMS Server Creation


1) Navigate to Services → Messaging → JMS Servers → Click on **New**



2) .Select FileStore-1 , Click **Next**



3) Select Target as Cluster-JMS and click on **Finish**



ORACLE WebLogic Server Administration Console 12c

Welcome, weblogic | Connected to: FCUBSDomain

Home > Summary of Servers > Summary of Clusters > Summary of Servers > Summary of Clusters > Cluster-JMS > Summary of Servers > Summary of Clusters > Summary of Servers > Summary of Persistent Stores > Summary of JMS Servers

Change Center
View changes and restarts
No pending changes exist. Click the Release Configuration button to allow others to edit the domain.
Lock & Edit
Release Configuration

Domain Structure
Environment
Servers
Clusters
Server Templates
Migratable Targets

Create a New JMS Server
Back Next Finish Cancel

Select targets
Select the server instance or migratable target on which you would like to deploy this JMS Server.

Target: Cluster-JMS
Back Next Finish Cancel

4) JMS-Server-1 is created

ORACLE WebLogic Server Administration Console 12c

Welcome, weblogic | Connected to: FCUBSDomain

Home > Summary of Servers > Summary of Clusters > Summary of Servers > Summary of Clusters > Cluster-JMS > Summary of Servers > Summary of Clusters > Summary of Servers > Summary of Persistent Stores > Summary of JMS Servers

Change Center
View changes and restarts
Click the Lock & Edit button to modify, add or delete items in this domain.
Lock & Edit
Release Configuration

Domain Structure
Environment
Servers
Clusters
Server Templates
Migratable Targets
Coherence Clusters
Machines
Virtual Hosts
Work Managers
Startup and Shutdown Classes
Deployments
Services
Messaging
JMS Servers

How do I...
Configure JMS servers
Configure JMS system modules

Messages
All changes have been activated. No restarts are necessary.

Summary of JMS Servers
JMS servers act as management containers for the queues and topics in JMS modules that are targeted to them.
This page summarizes the JMS servers that have been created in the current WebLogic Server domain.

Customize this table
JMS Servers (Filtered - More Columns Exist)
Click the **Lock & Edit** button in the Change Center to activate all the buttons on this page.

Name	Persistent Store	Target	Current Target	Health
JMS-Server-1	FileStore-1	Cluster-JMS	Cluster-JMS	

New Delete Showing 1 to 1 of 1 Previous Next

5) In NFS below filestores can be seen

```
[root@JMS_FILESTORE]# ll
total 2056
-rw-r----- 1 wll2c oinstall 1049088 Jun 16 14:10 FILESTORE-1@DC_JMS_1000000.DAT
-rw-r----- 1 wll2c oinstall 1049088 Jun 16 14:10 FILESTORE-1@DC_JMS_2000000.DAT
[root@JMS_FILESTORE]# pwd
/scratch/work_area/JMS_FILESTORE
[root@JMS_FILESTORE]#
```

3.3 Cluster Configuration for Service Migration

- 1) Click on Environment → Clusters → Cluster-JMS

The screenshot shows the Oracle WebLogic Server Administration Console. On the left, the 'Domain Structure' tree is expanded to 'Clusters'. The main content area is titled 'Summary of Clusters' and contains a table of clusters. The table has columns: Name, Cluster Address, Cluster Messaging Mode, Migration Basis, Default Load Algorithm, Replication Type, and Cluster ID. Two clusters are listed: 'Cluster-App' and 'Cluster-JMS'. The 'Cluster-JMS' row is highlighted with a red box.

Name	Cluster Address	Cluster Messaging Mode	Migration Basis	Default Load Algorithm	Replication Type	Cluster ID
Cluster-App		Unicast	Database	Round Robin	(None)	
Cluster-JMS		Unicast	Database	Round Robin	(None)	

- 2) Click on **Migration** Tab

The screenshot shows the 'Settings for Cluster-JMS' page. The 'Configuration' tab is selected, and the 'Migration' sub-tab is highlighted with a red box. The 'Migration' sub-tab contains a 'Coherence' section with a 'Save' button.

- 3) Change Migration Basis to Consensus and Click on **Save**

View changes and restarts

Configuration editing is enabled. Future changes will automatically be activated as you modify, add or delete items in this domain.

Domain Structure

- Environment
 - Servers
 - Clusters
 - Coherence Clusters
 - Machines
 - Virtual Hosts
 - Work Managers
 - Startup and Shutdown Classes
- Deployments
- Services
 - Security Realms
 - Interoperability
 - Diagnostics

How do I...

- Configure clusters
- Configure server migration in a cluster
- Create JDBC generic data sources
- Configure cross-cluster replication

System Status

Health of Running Servers

Home > Summary of Servers > Summary of Persistent Stores > Summary of JMS Servers > Summary of Clusters > Summary of Migratable Targets > Summary of Clusters > Cluster-JMS > Summary of Migratable Targets > Summary of Clusters > Cluster-JMS

Settings for Cluster-JMS

Configuration

Monitoring

Control

Deployments

Services

Notes

General

JTA

Messaging

Servers

Replication

Migration

Singleton Services

Scheduling

Overload

Health Monitoring

HTTP

Coherence

Save

If a clustered server fails, Node Manager can automatically restart the server and its services on another machine. This page allows you to specify the machines where Node Manager can restart migratable servers and to specify the data source used during server migration.

Candidate Machines For Migratable Servers:

The set of machines (and order of preference) on which Node Manager will restart failed servers. (Requires you to enable each server for automatic migration.) [More Info...](#)

Available:

Chosen:

☐ HSAC-1

☐ HSAC-2

Migration Basic:

Database

Database

Consensus

(None)

None

Controls the mechanism used for server and service migration. [More Info...](#)


Data Source For Automatic Migration:

The data source used by servers in the cluster during


4. JMS Module Creation

4.1 Module Creation


- 1) Navigate to Services → Messaging → JMS Modules and Click on **New**.




- 2) Enter name as JMS_MODULE and Click on **Next**




- 3) Select Target as Cluster-JMS and Click on **Next**



4) Select the checkbox and Click on **Finish**



5) JMS_MODULE is created



4.2 Sub Deployment Creation

- 1) In JMS_MODULE, Click on Sub Deployment tab , Click on **New**

The screenshot shows the Oracle WebLogic Server Administration Console. On the left, the 'Domain Structure' tree is expanded to 'JMS Modules', with 'JMS_MODULE' selected. The main area displays the 'Settings for JMS_MODULE' page, with the 'Subdeployments' tab selected. The 'Subdeployments-Tab' section contains a table with columns: Name, Type, JNDI Name, Subdeployment, and Targets. The table is currently empty, showing 'There are no items to display'. A red arrow points to the 'New' button at the bottom left of the table. The top navigation bar shows the path: Home > MS-JMS1 (migratable) > Summary of Migratable Targets > MS-JMS2 (migratable) > Summary of Clusters > Summary of Migratable Targets > MS-JMS1 (migratable) > Summary of Clusters > Summary of Migratable Targets > Summary of JMS Modules > JMS_MODULE.

- 2) Enter name as JMS_SUB and click on **Next**

The screenshot shows the 'Create a New Subdeployment' dialog box. The 'Next' button is highlighted with a red box and a red arrow. The 'Subdeployment Properties' section contains a text field for 'Subdeployment Name' with the value 'JMS_SUB' entered. A red arrow points to the 'Next' button. The top navigation bar shows the path: Home > MS-JMS1 (migratable) > Summary of Migratable Targets > MS-JMS2 (migratable) > Summary of Clusters > Summary of Migratable Targets > MS-JMS1 (migratable) > Summary of Clusters > Summary of Migratable Targets > Summary of JMS Modules > JMS_MODULE.

3) Select Target as Cluster-JMS and Click on **Finish**

The screenshot shows the Oracle WebLogic Server Administration Console. On the left, the 'Domain Structure' tree is visible. The main pane displays the 'Create a New Subdeployment' dialog. The 'Targets' section is active, showing a list of targets. Under 'Clusters', 'Cluster-JMS' is selected with the radio button 'All servers in the cluster'.

Change Center
View changes and restarts
No pending changes exist. Click the Release Configuration button to allow others to edit the domain.
Lock & Edit
Release Configuration

Domain Structure
Environment
Servers
Clusters
Server Templates
Migratable Targets
Coherence Clusters
Machines
Virtual Hosts
Work Managers
Startup and Shutdown Classes
Deployments
Services
Messaging

How do I...
• Configure subdeployments in JMS system modules

Create a New Subdeployment
Back Next Finish Cancel

Targets
Please select targets for the Subdeployment

Servers
☐ AdminServer

Clusters
☒ Cluster-JMS
☐ All servers in the cluster

JMS Servers
☐ JMSServer-1

Back Next Finish Cancel

4) Sub-Deployment is created

The screenshot shows the Oracle WebLogic Server Administration Console. The 'Messages' section displays two green success messages: 'All changes have been activated. However 1 items must be restarted for the changes to take effect.' and 'Subdeployment created successfully.' The 'Settings for JMS_Module' page is active, showing the 'Subdeployments' tab. A table lists the subdeployments, with 'JMS_SUB' listed under the 'Name' column and 'Cluster-JMS' under the 'Targets' column. A red arrow points to the 'JMS_SUB' entry in the table.

Change Center
View changes and restarts
Configuration editing is enabled. Future changes will automatically be activated as you modify, add or delete items in this domain.

Domain Structure
Environment
Deployments
Services
Messaging
JMS Servers
Store-and-Forward Agents
JMS Modules
Path Services
Bridges
Data Sources
Persistent Stores
Foreign JNDI Providers
Work Contexts

How do I...
• Configure subdeployments in JMS system modules
• Configure JMS system modules

System Status

Messages
All changes have been activated. However 1 items must be restarted for the changes to take effect.
Subdeployment created successfully.

Settings for JMS_Module
Configuration Subdeployments Targets Security Notes

This page displays subdeployments created for a JMS system module. A subdeployment is a mechanism by which JMS module resources (such as queues, topics, and connection factories) are grouped and targeted to a server resource (such as JMS servers, server instances, or cluster).

Customize this table

Subdeployments
New Delete Showing 1 to 1 of 1 Previous Next

Name	Resources	Targets
JMS_SUB		Cluster-JMS

New Delete Showing 1 to 1 of 1 Previous Next

4.3 Resource Creation

4.3.1 Queue Creation

1) In JMS_MODULE Click on **New**

ORACLE WebLogic Server Administration Console 12c

Home > MS-JMS1 (migratable) > Summary of Migratable Targets > MS-JMS2 (migratable) > Summary of Clusters > Summary of Migratable Targets > MS-JMS1 (migratable) > Summary of Clusters > Summary of Migratable Targets > Summary of JMS Modules > JMS_Module

Settings for JMS_Module

Configuration Subdeployments Targets Security Notes

This page displays general information about a JMS system module and its resources. It also allows you to configure new resources and access existing resources.

Name: JMS_Module The name of this JMS system module. [More Info...](#)

Descriptor File Name: jms/jms_module-jms.xml The name of the JMS module descriptor file. [More Info...](#)

This page summarizes the JMS resources that have been created for this JMS system module, including queue and topic destinations, connection factories, JMS templates, destination sort keys, destination quota, distributed destinations, foreign servers, and store-and-forward parameters.

[Customize this table](#)

Summary of Resources

New Delete Showing 0 to 0 of 0 Previous | Next

Name	Type	JNDI Name	Subdeployment	Targets
There are no items to display				

New Delete Showing 0 to 0 of 0 Previous | Next

2) Select Distributed Queue and Click on **Next**

ORACLE WebLogic Server Administration Console 12c

Home > MS-JMS1 (migratable) > Summary of Migratable Targets > MS-JMS2 (migratable) > Summary of Clusters > Summary of Migratable Targets > MS-JMS1 (migratable) > Summary of Clusters > Summary of Migratable Targets > Summary of JMS Modules > JMS_Module

Create a New JMS System Module Resource

Back **Next** Finish Cancel

Choose the type of resource you want to create.

Use these pages to create resources in a JMS system module, such as queues, topics, templates, and connection factories.

Depending on the type of resource you select, you are prompted to enter basic information for creating the resource. For targetable resources, like stand-alone queues and topics, connection factories, distributed queues and topics, foreign servers, and JMS SAF destinations, you can also proceed to targeting pages for selecting appropriate server targets. You can also associate targetable resources with subdeployments, which is an advanced mechanism for grouping JMS module resources and the members to server resources.


☐ **Connection Factory** Defines a set of connection configuration parameters that are used to create connections for JMS clients. [More Info...](#)

☐ **Queue** Defines a point-to-point destination type, which are used for asynchronous peer communications. A message delivered to a queue is distributed to only one consumer. [More Info...](#)


☐ **Topic** Defines a publish/subscribe destination type, which are used for asynchronous peer communications. A message delivered to a topic is distributed to all topic consumers. [More Info...](#)

☒ **Distributed Queue** Defines a set of queues that are distributed on multiple JMS servers, but which are accessible as a single, logical queue to JMS clients. [More Info...](#)


3) Enter the queue name and Click on **Next**



4) Click on **Advance Targeting**



5) Select Subdeployment as JMS_SUB and Click on **Finish**



6) MDB_QUEUE is created

ORACLE WebLogic Server Administration Console 12c

Home Log Out Preferences Record Help

Welcome, weblogic Connected to: pegjms

Home > MS-JMS1 (migratable) > Summary of Migratable Targets > MS-JMS2 (migratable) > Summary of Clusters > Summary of Migratable Targets > MS-JMS1 (migratable) > Summary of Clusters > Summary of Migratable Targets > Summary of JMS Modules > JMS_Module

Change Center
View changes and restarts
Configuration editing is enabled. Future changes will automatically be activated as you modify, add or delete items in this domain.

Domain Structure
Environment
Deployments
Services
Messaging
JMS Servers
Store-and-Forward Agents
JMS Modules
Path Services
Bridges
Data Sources
Persistent Stores
Foreign JNDI Providers
Work Contexts

How do I...
No task help found.

System Status
Health of Running Servers
Failed (0)
Critical (0)
Overloaded (0)
Warning (0)
OK (1)

Messages
All changes have been activated. However 1 items must be restarted for the changes to take effect.
The JMS distributed queue was created successfully.

Settings for JMS_Module
Configuration Subdeployments Targets Security Notes

This page displays general information about a JMS system module and its resources. It also allows you to configure new resources and access existing resources.

Name: JMS_Module The name of this JMS system module. [More Info...](#)

Descriptor File Name: jms/jms_module-jms.xml The name of the JMS module descriptor file. [More Info...](#)

This page summarizes the JMS resources that have been created for this JMS system module, including queue and topic destinations, connection factories, JMS templates, destination sort keys, destination quota, distributed destinations, foreign servers, and store-and-forward parameters.

[Customize this table](#)

Summary of Resources
New Delete Showing 1 to 1 of 1 Previous Next

Name	Type	JNDI Name	Subdeployment	Targets
☐ MDB_QUEUE	Uniform Distributed Queue	MDB_QUEUE	JMS_SUB	Cluster-JMS

New Delete Showing 1 to 1 of 1 Previous Next

7) Similarly Create MDB_QUEUE_RESPONSE and MDB_QUEUE_DLQ

ORACLE WebLogic Server Administration Console 12c

Home Log Out Preferences Record Help

Welcome, weblogic Connected to: FCUBSDomain

Home > DC_JMS_Template-0 > Summary of Servers > Summary of Migratable Targets > Summary of JMS Servers > JMSServer-1 > Summary of JMS Servers > JMSServer-1 > Summary of Migratable Targets > Summary of JMS Modules > JMS_MODULE

Change Center
View changes and restarts
Click the Lock & Edit button to modify, add or delete items in this domain.
Lock & Edit
Release Configuration

Domain Structure
Environment
Servers
Clusters
Server Templates
Migratable Targets
Coherence Clusters
Machines
Virtual Hosts
Work Managers
Startup and Shutdown Classes
Deployments
Services
Messaging

How do I...
No task help found.

System Status
Health of Running Servers
Failed (0)
Critical (0)
Overloaded (0)
Warning (0)
OK (5)

Messages
All changes have been activated. No restarts are necessary.

Settings for JMS_MODULE
Configuration Subdeployments Targets Security Notes

This page displays general information about a JMS system module and its resources. It also allows you to configure new resources and access existing resources.

Name: JMS_MODULE The name of this JMS system module. [More Info...](#)

Descriptor File Name: jms/jms_module-jms.xml The name of the JMS module descriptor file. [More Info...](#)

This page summarizes the JMS resources that have been created for this JMS system module, including queue and topic destinations, connection factories, JMS templates, destination sort keys, destination quota, distributed destinations, foreign servers, and store-and-forward parameters.

[Customize this table](#)

Summary of Resources
Click the **Lock & Edit** button in the Change Center to activate all the buttons on this page.
New Delete Showing 1 to 3 of 3 Previous Next

Name	Type	JNDI Name	Subdeployment	Targets
☐ MDB_QUEUE	Uniform Distributed Queue	MDB_QUEUE	JMS_SUB	Cluster-JMS
☐ MDB_QUEUE_DLQ	Uniform Distributed Queue	MDB_QUEUE_DLQ	JMS_SUB	Cluster-JMS
☐ MDB_QUEUE_RESPONSE	Uniform Distributed Queue	MDB_QUEUE_RESPONSE	JMS_SUB	Cluster-JMS

New Delete Showing 1 to 3 of 3 Previous Next

4.3.2 Connection Factory Creation

1) In JMS_MODULE, Click on **New**

ORACLE WebLogic Server Administration Console 12c

Home > MS-JMS1 (migratable) > Summary of Migratable Targets > MS-JMS2 (migratable) > Summary of Clusters > Summary of Migratable Targets > MS-JMS1 (migratable) > Summary of Clusters > Summary of Migratable Targets > Summary of JMS Modules > **JMS_Module**

Messages

- ✓ All changes have been activated. However 1 items must be restarted for the changes to take effect.
- ✓ The JMS distributed queue was created successfully.

Settings for JMS_Module

Configuration Subdeployments Targets Security Notes

This page displays general information about a JMS system module and its resources. It also allows you to configure new resources and access existing resources.

Name: JMS_Module The name of this JMS system module. [More Info...](#)

Descriptor File Name: jms/jms_module-jms.xml The name of the JMS module descriptor file. [More Info...](#)

This page summarizes the JMS resources that have been created for this JMS system module, including queue and topic destinations, connection factories, JMS templates, destination sort keys, destination quota, distributed destinations, foreign servers, and store-and-forward parameters.

[Customize this table](#)

Summary of Resources

New Delete Showing 1 to 3 of 3 Previous | Next

Name	Type	JNDI Name	Subdeployment	Targets
MDB_QUEUE	Uniform Distributed Queue	MDB_QUEUE	JMS_SUB	Cluster-JMS
MDB_QUEUE_DLQ	Uniform Distributed Queue	MDB_QUEUE_DLQ	JMS_SUB	Cluster-JMS
MDB_QUEUE_RESPONSE	Uniform Distributed Queue	MDB_QUEUE_RESPONSE	JMS_SUB	Cluster-JMS

New Delete Showing 1 to 3 of 3 Previous | Next

WebLogic Server Version: 12.1.3.0.0
Copyright (c) 1996,2014, Oracle and/or its affiliates. All rights reserved.
Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

2) Select Connection Factory and click on **Next**

ORACLE WebLogic Server Administration Console 12c

Home > MS-JMS1 (migratable) > Summary of Migratable Targets > MS-JMS2 (migratable) > Summary of Clusters > Summary of Migratable Targets > MS-JMS1 (migratable) > Summary of Clusters > Summary of Migratable Targets > Summary of JMS Modules > **JMS_Module**

Create a New JMS System Module Resource

Back **Next** Finish Cancel

Choose the type of resource you want to create.

Use these pages to create resources in a JMS system module, such as queues, topics, templates, and connection factories.

Depending on the type of resource you select, you are prompted to enter basic information for creating the resource. For targetable resources, like stand-alone queues and topics, connection factories, distributed queues and topics, foreign servers, and JMS SAF destinations, you can also proceed to targeting pages for selecting appropriate server targets. You can also associate targetable resources with subdeployments, which is an advanced mechanism for grouping JMS module resources and the members to server resources.

☒ **Connection Factory** Defines a set of connection configuration parameters that are used to create connections for JMS clients. [More Info...](#)

☐ Queue Defines a point-to-point destination type, which are used for asynchronous peer communications. A message

3) Enter the Name and Click on **Next**

ORACLE WebLogic Server Administration Console 12c

Home Log Out Preferences Record Help

Welcome, weblogic Connected to: pegjms

Home > MS-JMS1 (migratable) > Summary of Migratable Targets > MS-JMS2 (migratable) > Summary of Clusters > Summary of Migratable Targets > MS-JMS1 (migratable) > Summary of Clusters > Summary of Migratable Targets > Summary of JMS Modules > JMS_Module

Create a New JMS System Module Resource

Back **Next** Finish Cancel

Connection Factory Properties

The following properties will be used to identify your new connection factory. The current module is JMS_Module.

* Indicates required fields

What would you like to name your new connection factory?

* Name:

What JNDI Name would you like to use to look up your new connection factory?

JNDI Name:

4) Click on **Advance Targeting**

ORACLE WebLogic Server Administration Console 12c

Home Log Out Preferences Record Help

Welcome, weblogic Connected to: FCUBSDomain

Home > DC_JMS_Template-0 > Summary of Servers > Summary of Migratable Targets > Summary of JMS Servers > JMS-Server-1 > Summary of JMS Servers > JMS-Server-1 > Summary of Migratable Targets > Summary of JMS Modules > JMS_MODULE

Create a New JMS System Module Resource

Back Next Finish **Advanced Targeting** Cancel

The following properties will be used to target your new JMS system module resource

Use this page to view and accept the default targets where this JMS resource will be targeted. The default targets are based on the parent JMS system module targets. If you do not want to accept the default targets, then click **Advanced Targeting** to use the subdeployment mechanism for targeting this resource.

The following JMS module targets will be used as the default targets for your new JMS system module resource. If the module's targets are changed, this resource will also be retargeted appropriately.

Targets :

Clusters
☒ Cluster-JMS
☐ All servers in the cluster

Back Next Finish **Advanced Targeting** Cancel

5) Select JMS_SUB and Click on **Finish**

ORACLE WebLogic Server Administration Console 12c

Home Log Out Preferences Record Help Welcome, weblogic Connected to: FCUBSDomain

Home > DC_JMS_Template-0 > Summary of Servers > Summary of Migratable Targets > Summary of JMS Servers > JMSServer-1 > Summary of JMS Servers > JMSServer-1 > Summary of Migratable Targets > Summary of JMS Modules > JMS_MODULE

Create a New JMS System Module Resource

Back Next Finish Cancel

The following properties will be used to target your new JMS system module resource

Use this page to select a subdeployment to assign this system module resource. A subdeployment is a mechanism by which JMS resources are grouped and targeted to a server instance, cluster, or SAF agent. If necessary, you can create a new subdeployment by clicking the **Create a New Subdeployment** button. You can also reconfigure subdeployment targets later by using the parent module's subdeployment management page.

Select the subdeployment you want to use. If you select (none), no targeting will occur.

Subdeployments: JMS_SUB Create a New Subdeployment

What targets do you want to assign to this subdeployment?

Targets :

Servers

☐ AdminServer

Clusters

☒ Cluster-JMS
All servers in the cluster

JMS Servers

☐ JMSServer-1

Back Next Finish Cancel

Change Center

View changes and restarts

No pending changes exist. Click the Release Configuration button to allow others to edit the domain.

Lock & Edit
Release Configuration

Domain Structure

- Environment
 - Servers
 - Clusters
 - Server Templates
 - Migratable Targets
 - Coherence Clusters
 - Machines
 - Virtual Hosts
 - Work Managers
 - Startup and Shutdown Classes
 - Deployments
 - Services
 - Messaging

How do I...

- Configure quotas for destinations
- Configure JMS templates
- Configure destination keys
- Configure topics
- Configure queues
- Configure connection factories
- Configure uniform distributed topics
- Configure uniform distributed queues
- Configure foreign servers
- Configure JMS SAF

System Status

6) Connection Factory is **Created**

ORACLE WebLogic Server Administration Console 12c

Home Log Out Preferences Record Help

Welcome, weblogic Connected to: pegjms

Change Center

View changes and restarts

Configuration editing is enabled. Future changes will automatically be activated as you modify, add or delete items in this domain.

Domain Structure

Environment
Deployments
Services
Messaging
JMS Servers
Store-and-Forward Agents
JMS Modules
Path Services
Bridges
Data Sources
Persistent Stores
Foreign JNDI Providers
Work Contexts

How do I...

No task help found.

System Status

Health of Running Servers

Failed (0)

Critical (0)

Overloaded (0)

Warning (0)

OK (1)

Home > MS-JMS1 (migratable) > Summary of Migratable Targets > MS-JMS2 (migratable) > Summary of Clusters > Summary of Migratable Targets > MS-JMS1 (migratable) > Summary of Clusters > Summary of Migratable Targets > Summary of JMS Modules > JMS_Module

Messages

All changes have been activated. However 1 items must be restarted for the changes to take effect.
Connection factory created successfully.

Settings for JMS_Module

Configuration Subdeployments Targets Security Notes

This page displays general information about a JMS system module and its resources. It also allows you to configure new resources and access existing resources.

Name:

JMS_Module

The name of this JMS system module. More Info...

Descriptor File Name:

jms/jms_module-jms.xml

The name of the JMS module descriptor file. More Info...

This page summarizes the JMS resources that have been created for this JMS system module, including queue and topic destinations, connection factories, JMS templates, destination sort keys, destination quota, distributed destinations, foreign servers, and store-and-forward parameters.

Customize this table

Summary of Resources

New Delete

Showing 1 to 4 of 4 Previous | Next

Name	Type	JNDI Name	Subdeployment	Targets
MDBQCF	Connection Factory	MDBQCF	JMS_SUB	Cluster-JMS
MDB_QUEUE	Uniform Distributed Queue	MDB_QUEUE	JMS_SUB	Cluster-JMS
MDB_QUEUE_DLQ	Uniform Distributed Queue	MDB_QUEUE_DLQ	JMS_SUB	Cluster-JMS
MDB_QUEUE_RESPONSE	Uniform Distributed Queue	MDB_QUEUE_RESPONSE	JMS_SUB	Cluster-JMS

New Delete

Showing 1 to 4 of 4 Previous | Next

ORACLE

5. Server Restart

- 1) Increase the heap size of both DC_JMS_1 and DC_JMS_2 cluster

The screenshot shows the Oracle WebLogic Server Administration Console. The left sidebar contains the 'Change Center' and 'Domain Structure' panels. The 'Domain Structure' panel shows a tree view with 'Servers' expanded, and 'DC_JMS_1' and 'DC_JMS_2' selected. The main content area displays the 'Summary of Servers' page, which includes a table of servers and their configurations.

Name	Type	Cluster	Machine	State	Health	Listen Port
AdminServer(admin)	Configured			RUNNING	OK	7001
DC_FCUBS_1	Dynamic	Cluster-App	MAC-1	SHUTDOWN	Not reachable	7101
DC_FCUBS_2	Dynamic	Cluster-App	MAC-2	SHUTDOWN	Not reachable	7102
DC_FCUBS_3	Dynamic	Cluster-App	MAC-1	SHUTDOWN	Not reachable	7103
DC_FCUBS_4	Dynamic	Cluster-App	MAC-2	SHUTDOWN	Not reachable	7104
DC_JMS_1	Dynamic	Cluster-JMS	MAC-1	SHUTDOWN	Not reachable	7106
DC_JMS_2	Dynamic	Cluster-JMS	MAC-2	SHUTDOWN	Not reachable	7107

- 2) Select the cluster 'DC_JMS_Template-0' and

The screenshot shows the Oracle WebLogic Server Administration Console. The left sidebar contains the 'Change Center' and 'Domain Structure' panels. The 'Domain Structure' panel shows a tree view with 'Server Templates' expanded, and 'DC_JMS_Template-0' selected. The main content area displays the 'Summary of Server Templates' page, which includes a table of server templates and their configurations.

Name	Cluster	Machine	Listen Port	Listen Address
DC_FCUBS_Template	Cluster-App		7100	
DC_JMS_Template-0	Cluster-JMS		7105	

3) Click on Server Start Tab and in Arguments Section enter **-XX:MaxPermSize=512m**

The screenshot displays the Oracle WebLogic Server Administration Console. The left sidebar contains the 'Change Center' with a 'View changes and restarts' section, a 'Domain Structure' tree, and a 'System Status' section. The main content area is titled 'Settings for DC_JMS_Template-0' and features a 'Configuration' tab. Within this tab, the 'Server Start' sub-tab is selected. The 'Server Start' section includes fields for 'Java Home', 'Java Vendor', 'BEA Home', and 'Root Directory', each with a description and a 'More Info...' link. Below these fields is a 'Class Path' section. At the bottom, the 'Arguments' field is highlighted with a red box and contains the text **-XX:MaxPermSize=512m**. The console's top navigation bar shows the user is logged in as 'weblogic' and connected to 'FCUBSDomain'.

4) **Restart** the AdminServer and DC_JMS_1 and DC_JMS_2 managed servers.

6. Foreign Server Creation

6.1 Module Creation

1) JMS_Modules and Click on New

ORACLE WebLogic Server Administration Console 12c

Home Log Out Preferences Record Help

Welcome, weblogic Connected to: pegjms

Home > Summary of Servers > MS-JMS2 > Summary of Virtual Hosts > Summary of Servers > Summary of Clusters > Summary of Migratable Targets > Summary of Servers > Summary of Deployments > Summary of JMS Modules

Summary of JMS Modules

JMS system resources are configured and stored as modules similar to standard J2EE modules. Such resources include queues, topics, connection factories, templates, destination keys, quota, distributed queues, distributed topics, foreign servers, and JMS store-and-forward (SAF) parameters. You can administratively configure and manage JMS system modules as global system resources.

This page summarizes the JMS system modules that have been created for this domain.

Customize this table

JMS Modules

Name	Type
JMS_Module	System

New Delete

Showing 1 to 1 of 1 Previous | Next

New Delete

Showing 1 to 1 of 1 Previous | Next

How do I...
• Configure JMS system modules
• Configure resources for JMS system modules

2) Enter name as MDB_MODULE and click on Next

ORACLE WebLogic Server Administration Console 12c

Home Log Out Preferences Record Help

Welcome, weblogic Connected to: pegjms

Home > Summary of Migratable Targets > MS-JMS1 (migratable) > Summary of Migratable Targets > MS-JMS2 (migratable) > Summary of Migratable Targets > MS-JMS1 (migratable) > S

Create JMS System Module

Back Next Finish Cancel

The following properties will be used to identify your new module.

JMS system resources are configured and stored as modules similar to standard J2EE modules. Such resources include queues, topics, connection factories, templates, destination keys, quota, distributed queues, distributed topics, foreign servers, and JMS store-and-forward (SAF) parameters. You can administratively configure and manage JMS system modules as global system resources.

* Indicates required fields

What would you like to name your System Module?

* Name: MDB_MODULE

What would you like to name the descriptor file name? If you do not provide a name, a default will be assigned.

Descriptor File Name:

Where would like to place the descriptor for this System Module, relative to the jms configuration sub-directory of your domain?


Location In Domain:

Back Next Finish Cancel


How do I...
• Configure JMS system modules
• Configure JMS servers

System Status
Health of Running Servers
Failed (0)


3) Select target as Cluster-App and click on **Next**



4) Select CheckBox and Click on **Finish**



5) MDB_MODULE is created



6.2 Foreign Server Creation

In MDB_MODULE, Click on New Resource, Select **Foreign Server**

Change Center
View changes and restarts
Configuration editing is enabled. Future changes will automatically be activated as you modify, add or delete items in this domain.

Domain Structure
Clusters
Server Templates
Migratable Targets
Coherence Clusters
Machines
Virtual Hosts
Work Managers
Startup and Shutdown Classes
Deployments
Services
Messaging
JMS Servers
Store-and-Forward Agents
JMS Modules

How do I...
Configure JMS system modules
Configure resources for JMS system modules

Home > Summary of Servers > Summary of Deployments > Summary of JMS Modules > MDB_MODULE > Summary of Migratable Targets > Summary of Clusters > Summary of JMS Servers > Summary of JMS Modules > MDB_MODULE > Summary of JMS Modules

Welcome, weblogic | Connected to: pegjms

Summary of JMS Modules

JMS system resources are configured and stored as modules similar to standard J2EE modules. Such resources include queues, topics, connection factories, templates, destination keys, quota, distributed queues, distributed topics, foreign servers, and JMS store-and-forward (SAF) parameters. You can administratively configure and manage JMS system modules as global system resources.

This page summarizes the JMS system modules that have been created for this domain.

[Customize this table](#)

JMS Modules

New Delete Showing 1 to 2 of 2 Previous | Next

Name	Type
JMS_Module	System
MDB_MODULE	System

New Delete Showing 1 to 2 of 2 Previous | Next

1) Click on Configuration → New

Change Center
View changes and restarts
Configuration editing is enabled. Future changes will automatically be activated as you modify, add or delete items in this domain.

Domain Structure
Environment
Servers
Clusters
Server Templates
Migratable Targets
Coherence Clusters
Machines
Virtual Hosts
Work Managers
Startup and Shutdown Classes
Deployments
Services
Messaging

How do I...
No task help found.

System Status
Health of Running Servers
Failed (1)
Critical (0)

Home > Summary of Deployments > Summary of JMS Modules > MDB_MODULE > Summary of Migratable Targets > Summary of Clusters > Summary of JMS Servers > Summary of JMS Modules > MDB_MODULE > Summary of JMS Modules > MDB_MODULE

Welcome, weblogic | Connected to: pegjms

Settings for MDB_MODULE

Configuration Subdeployments Targets Security Notes

This page displays general information about a JMS system module and its resources. It also allows you to configure new resources and access existing resources.

Name: MDB_MODULE The name of this JMS system module. [More Info...](#)

Descriptor File Name: jms/mdb_module-jms.xml The name of the JMS module descriptor file. [More Info...](#)

This page summarizes the JMS resources that have been created for this JMS system module, including queue and topic destinations, connection factories, JMS templates, destination sort keys, destination quota, distributed destinations, foreign servers, and store-and-forward parameters.

[Customize this table](#)

Summary of Resources

New Delete Showing 0 to 0 of 0 Previous | Next

Name	Type	JNDI Name	Subdeployment	Targets
There are no items to display				

New Delete Showing 0 to 0 of 0 Previous | Next

2) Select Foreign Server and Click on Next

ORACLE WebLogic Server Administration Console 12c

Home Log Out Preferences Record Help

Welcome, weblogic Connected to: pegjms

Home > Summary of Deployments > Summary of JMS Modules > MDB_MODULE > Summary of Migratable Targets > Summary of Clusters > Summary of JMS Servers > Summary of JMS Modules > MDB_MODULE > Summary of JMS Modules > MDB_MODULE

Create a New JMS System Module Resource

Back **Next** Finish Cancel

Choose the type of resource you want to create.

Use these pages to create resources in a JMS system module, such as queues, topics, templates, and connection factories.

Depending on the type of resource you select, you are prompted to enter basic information for creating the resource. For targetable resources, like stand-alone queues and topics, connection factories, distributed queues and topics, foreign servers, and JMS SAF destinations, you can also proceed to targeting pages for selecting appropriate server targets. You can also associate targetable resources with subdeployments, which is an advanced mechanism for grouping JMS module resources and the members to server resources.

- ☐ **Connection Factory** Defines a set of connection configuration parameters that are used to create connections for JMS clients. [More Info...](#)
- ☐ **Queue** Defines a point-to-point destination type, which are used for asynchronous peer communications. A message delivered to a queue is distributed to only one consumer. [More Info...](#)
- ☐ **Topic** Defines a publish/subscribe destination type, which are used for asynchronous peer communications. A message delivered to a topic is distributed to all topic consumers. [More Info...](#)
- ☐ **Distributed Queue** Defines a set of queues that are distributed on multiple JMS servers, but which are accessible as a single, logical queue to JMS clients. [More Info...](#)
- ☐ **Distributed Topic** Defines a set of topics that are distributed on multiple JMS servers, but which are accessible as a single, logical topic to JMS clients. [More Info...](#)
- ☒ **Foreign Server** Defines foreign messaging providers or remote WebLogic Server instances that are not part of the current domain. [More Info...](#)

3) Enter name and Click on Next

ORACLE WebLogic Server Administration Console 12c

Home Log Out Preferences Record Help

Welcome, weblogic Connected to: pegjms

Home > Summary of Deployments > Summary of JMS Modules > MDB_MODULE > Summary of Migratable Targets > Summary of Clusters > Summary of JMS Servers > Summary of JMS Modules > MDB_MODULE > Summary of JMS Modules > MDB_MODULE

Create a New JMS System Module Resource

Back Next Finish Cancel

Foreign Server Properties

The following properties will be used to identify your new foreign server. The current module is MDB_MODULE.

* Indicates required fields

* **Name:** ForeignServer-1

Back **Next** Finish Cancel

4) Click on Advanced Targeting

The screenshot shows the Oracle WebLogic Server Administration Console 12c. On the left, the 'Change Center' tab is active, showing 'View changes and restarts' and 'Domain Structure'. The 'Domain Structure' tree on the left includes Environment, Servers, Clusters, Server Templates, Migratable Targets, Coherence Clusters, Machines, Virtual Hosts, Work Managers, Startup and Shutdown Classes, Deployments, Services, and Messaging. The main pane displays the 'Create a New JMS System Module Resource' dialog. The 'Advanced Targeting' button is selected. The dialog text states: 'The following properties will be used to target your new JMS system module resource'. It explains that default targets are based on parent JMS system module targets and that 'Advanced Targeting' can be used for subdeployment targeting. A 'Targets' section shows a table with 'Cluster-App' and 'All servers in the cluster' selected. Navigation buttons (Back, Next, Finish, Advanced Targeting, Cancel) are at the bottom.

5) Click on Create New SubDeployment

The screenshot shows the Oracle WebLogic Server Administration Console 12c. The 'Create a New JMS System Module Resource' dialog is open. The 'Create a New SubDeployment' button is highlighted with a red arrow. The dialog text explains that a subdeployment is a mechanism for grouping JMS resources and targeting them to a server instance, cluster, or SAF agent. It instructs the user to select a subdeployment from a dropdown menu, which currently shows '(none)'. The 'Create a New SubDeployment' button is highlighted with a red arrow. The dialog also asks 'What targets do you want to assign to this subdeployment?'. Navigation buttons (Back, Next, Finish, Cancel) are at the bottom.

6) Enter Name as MDB_SUB and Click on OK

The screenshot shows the Oracle WebLogic Server Administration Console 12c. The 'Create a New SubDeployment' dialog is open. The 'Subdeployment Name' field is set to 'MDB_SUB', highlighted with a red arrow. The 'OK' button is highlighted with a red arrow. The dialog text states: 'The following properties will be used to identify your new subdeployment.' Navigation buttons (OK, Cancel) are at the bottom.

7) Select Target as Cluster-App and Click on Finish

ORACLE WebLogic Server Administration Console 12c

Home Log Out Preferences Record Help

Welcome, weblogic Connected to: FCUBSDomain

Home > DC_JMS_Template-0 > Summary of Server Templates > DC_JMS_Template-0 > Summary of Servers > Summary of JMS Modules > JMS_MODULE > Summary of JMS Modules > MDB_MODULE

Create a New JMS System Module Resource

Back Next Finish Cancel

The following properties will be used to target your new JMS system module resource

Use this page to select a subdeployment to assign this system module resource. A subdeployment is a mechanism by which JMS resources are grouped and targeted to a server instance, cluster, or SAF agent. If necessary, you can create a new subdeployment by clicking the **Create a New Subdeployment** button. You can also reconfigure subdeployment targets later by using the parent module's subdeployment management page.

Select the subdeployment you want to use. If you select (none), no targeting will occur.

Subdeployments: MDB_SUB Create a New Subdeployment

What targets do you want to assign to this subdeployment?

Targets :

Servers

☐ AdminServer

Clusters

☒ Cluster-App
All servers in the cluster

JMS Servers

☐ JMSServer-1

Back Next Finish Cancel

8) Foreign Server is created

ORACLE WebLogic Server Administration Console 12c

Home Log Out Preferences Record Help

Welcome, weblogic Connected to: pegjms

Home > Summary of Deployments > Summary of JMS Modules > MDB_MODULE > Summary of Migratable Targets > Summary of Clusters > Summary of JMS Servers > Summary of JMS Modules > MDB_MODULE

Messages

All changes have been activated. No restarts are necessary.
The foreign server was created successfully.

Settings for MDB_MODULE

Configuration Subdeployments Targets Security Notes

This page displays general information about a JMS system module and its resources. It also allows you to configure new resources and access existing resources.

Name: MDB_MODULE The name of this JMS system module. [More Info...](#)

Descriptor File Name: jms/mdb_module-jms.xml The name of the JMS module descriptor file. [More Info...](#)

This page summarizes the JMS resources that have been created for this JMS system module, including queue and topic destinations, connection factories, JMS templates, destination sort keys, destination quota, distributed destinations, foreign servers, and store-and-forward parameters.

[Customize this table](#)

Summary of Resources

New Delete Showing 1 to 1 of 1 Previous | Next

Name	Type	JNDI Name	Subdeployment	Targets
ForeignServer-1	Foreign Server	N/A	MDB_SUB	Cluster-App

New Delete Showing 1 to 1 of 1 Previous | Next

3) Click on Connection Factories

ORACLE WebLogic Server Administration Console 12c

Home Log Out Preferences Record Help

Welcome, weblogic Connected to: pegjms

Home > MDB_MODULE > Summary of Migratable Targets > Summary of Clusters > Summary of JMS Servers > Summary of JMS Modules > MDB_MODULE > Summary of JMS Modules > MDB_MODULE > ForeignServer-1 > Configuration

Settings for ForeignServer-1

Configuration Subdeployment Notes

General Destinations **Connection Factories**

A foreign connection factory represents a connection factory that resides on another server, and which is accessible via JNDI. A remote connection factory can be used to refer to another instance of WebLogic Server running in a different cluster or server, or a foreign provider, as long as that provider supports JNDI.

This page summarizes the foreign connection factories that have been created for this domain.

Customize this table

Foreign Connection Factories (Filtered - More Columns Exist)

New Delete Showing 0 to 0 of 0 Previous | Next

Name	Local JNDI Name	Remote JNDI Name
There are no items to display		

New Delete Showing 0 to 0 of 0 Previous | Next

4) Create MDBQCF Connection Factory

ORACLE WebLogic Server Administration Console 12c

Home Log Out Preferences Record Help

Welcome, weblogic Connected to: pegjms

Home > MDB_MODULE > Summary of Migratable Targets > Summary of Clusters > Summary of JMS Servers > Summary of JMS Modules > MDB_MODULE > Summary of JMS Modules > MDB_MODULE > ForeignServer-1 > Configuration

Create a New Foreign JMS Connection Factory

OK Cancel

Foreign Connection Factory Properties

The following properties will be used to identify your new foreign connection factory.

* Indicates required fields

* Name: MDBQCF

Local JNDI Name: MDBQCF

Remote JNDI Name: MDBQCF

OK Cancel

5) Click on Destination

ORACLE WebLogic Server Administration Console 12c

Home Log Out Preferences Record Help

Welcome, weblogic Connected to: pegjms

Home > MDB_MODULE > Summary of Migratable Targets > Summary of Clusters > Summary of JMS Servers > Summary of JMS Modules > MDB_MODULE > Summary of JMS Modules > MDB_MODULE > ForeignServer-1 > Configuration

Messages

All changes have been activated. However, 1 item must be restarted for the changes to take effect.

Settings for ForeignServer-1

Configuration Subdeployment Notes

General **Destinations** Connection Factories

A foreign connection factory represents a connection factory that resides on another server, and which is accessible via JNDI. A remote connection factory can be used to refer to another instance of WebLogic Server running in a different cluster or server, or a foreign provider, as long as that provider supports JNDI.

This page summarizes the foreign connection factories that have been created for this domain.

Customize this table

Foreign Connection Factories (Filtered - More Columns Exist)

New Delete Showing 1 to 1 of 1 Previous | Next

Name	Local JNDI Name	Remote JNDI Name
MDBQCF	MDBQCF	MDBQCF

New Delete Showing 1 to 1 of 1 Previous | Next

6) Create MDB_QUEUE

The screenshot shows the Oracle WebLogic Server Administration Console. On the left, the 'Domain Structure' tree is visible, showing the hierarchy from Environment to Servers to Clusters to Migratable Targets to Coherence Servers to Coherence Clusters to Machines to Work Managers to Startup and Shutdown Classes to Deployments to Services to Messaging. The 'How do I...' section lists 'Configure foreign servers' and 'Create foreign connection factories'. The 'System Status' section shows 'Health of Running Servers'. The main content area is titled 'Settings for ForeignServer-1' and has tabs for 'Configuration', 'Subdeployment', and 'Notes'. The 'Configuration' tab is active, and the 'Destinations' sub-tab is selected. A text block explains that a foreign destination can be found on a remote server and that this page summarizes the foreign destinations created for this domain. Below this, there is a 'Customize this table' link and a table titled 'Foreign Destinations'. The table has columns for 'Name', 'Local JNDI Name', and 'Remote JNDI Name'. The table is currently empty, showing 'Showing 0 to 0 of 0' items.

The screenshot shows the 'Create a New Foreign JMS Destination' dialog box in the Oracle WebLogic Server Administration Console. The dialog box has 'OK' and 'Cancel' buttons. Below the buttons, the 'Foreign Destination Properties' section is visible. It states: 'The following properties will be used to identify your new foreign destination.' Below this, there is a list of properties with asterisks indicating required fields. The properties are: 'Name' (value: MDB_QUEUE), 'Local JNDI Name' (value: MDB_QUEUE), and 'Remote JNDI Name' (value: MDB_QUEUE). The 'OK' button is highlighted with a red box.

7) Similarly Create MDB_QUEUE_RESPONSE, MDB_QUEUE_DLQ

The screenshot shows the 'Create a New Foreign JMS Destination' dialog box in the Oracle WebLogic Server Administration Console. The dialog box has 'OK' and 'Cancel' buttons. Below the buttons, the 'Foreign Destination Properties' section is visible. It states: 'The following properties will be used to identify your new foreign destination.' Below this, there is a list of properties with asterisks indicating required fields. The properties are: 'Name' (value: MDB_QUEUE_RESPC), 'Local JNDI Name' (value: MDB_QUEUE_RESPONSE), and 'Remote JNDI Name' (value: MDB_QUEUE_RESPONSE). The 'OK' button is highlighted with a red box.

ORACLE WebLogic Server Administration Console 12c

Welcome, weblogic | Connected to: pegjms

Home > MDB_MODULE > Summary of Migratable Targets > Summary of Clusters > Summary of JMS Servers > Summary of JMS Modules > MDB_MODULE > Summary of JMS Modules > MDB_MODULE > ForeignServer-1 > Configuration

Messages

✓ All changes have been activated. However 1 items must be restarted for the changes to take effect.

Settings for ForeignServer-1

Configuration Subdeployment Notes

General Destinations Connection Factories

A foreign destination (topic or queue) can be found on a remote server. When this destination is looked up on the local server, a look-up will be performed automatically on the remote JNDI directory, and the object will be returned from that directory.

This page summarizes the foreign destinations that have been created for this domain.

Customize this table

Foreign Destinations

New Delete Showing 1 to 2 of 2 Previous | Next

Name	Local JNDI Name	Remote JNDI Name
MDB_QUEUE	MDB_QUEUE	MDB_QUEUE
MDB_QUEUE_RESPONSE	MDB_QUEUE_RESPONSE	MDB_QUEUE_RESPONSE

New Delete Showing 1 to 2 of 2 Previous | Next

ORACLE WebLogic Server Administration Console 12c

Welcome, weblogic | Connected to: pegjms

Home > MDB_MODULE > Summary of Migratable Targets > Summary of Clusters > Summary of JMS Servers > Summary of JMS Modules > MDB_MODULE > Summary of JMS Modules > MDB_MODULE > ForeignServer-1 > Configuration

Messages

✓ All changes have been activated. However 1 items must be restarted for the changes to take effect.

Create a New Foreign JMS Destination

OK Cancel

Foreign Destination Properties

The following properties will be used to identify your new foreign destination.

* Indicates required fields

* Name: MDB_QUEUE_DLQ

Local JNDI Name: MDB_QUEUE_DLQ

Remote JNDI Name: MDB_QUEUE_DLQ

OK Cancel

ORACLE WebLogic Server Administration Console 12c

Welcome, weblogic | Connected to: pegjms

Home > MDB_MODULE > Summary of Migratable Targets > Summary of Clusters > Summary of JMS Servers > Summary of JMS Modules > MDB_MODULE > Summary of JMS Modules > MDB_MODULE > ForeignServer-1 > Configuration

Messages

✓ All changes have been activated. However 1 items must be restarted for the changes to take effect.

Settings for ForeignServer-1

Configuration Subdeployment Notes

General Destinations Connection Factories

A foreign destination (topic or queue) can be found on a remote server. When this destination is looked up on the local server, a look-up will be performed automatically on the remote JNDI directory, and the object will be returned from that directory.

This page summarizes the foreign destinations that have been created for this domain.

Customize this table

Foreign Destinations

New Delete Showing 1 to 3 of 3 Previous | Next

Name	Local JNDI Name	Remote JNDI Name
MDB_QUEUE	MDB_QUEUE	MDB_QUEUE
MDB_QUEUE_DLQ	MDB_QUEUE_DLQ	MDB_QUEUE_DLQ
MDB_QUEUE_RESPONSE	MDB_QUEUE_RESPONSE	MDB_QUEUE_RESPONSE

New Delete Showing 1 to 3 of 3 Previous | Next

8) After all the resources are created, **Restart** the Admin and Managed Servers.

7. Application Deployment

1) Deploy the EAR with Target as Cluster-App

The screenshot shows the Oracle WebLogic Administration Console interface. On the left is a 'Change Center' sidebar with a 'View changes and restarts' section and a 'Domain Structure' tree. The main area is titled 'Settings for GWMDB' and includes a breadcrumb trail: Home > JMS Modules > MDB_MODULE > ForeignServer-1 > JMS Modules > Summary of Deployments > Summary of Servers > Summary of Deployments > Summary of Servers > Summary of Deployments > GWMDB. The 'Targets' tab is selected, showing instructions to specify WebLogic Server instances and clusters. Below this is a 'Target Assignments' table with columns for Component, Type, and Current Targets. The table lists two components: GWMDB (Enterprise Application) and GW_MDB_Bean.jar (EJB). The GWMDB component has 'Cluster-App' as its current target, while GW_MDB_Bean.jar has '(None specified)'. Navigation links like 'Change Targets' and 'Showing 1 to 1 of 1' are present.

Change Center
View changes and restarts
Configuration editing is enabled. Future changes will automatically be activated as you modify, add or delete items in this domain.

Domain Structure

- Environment
 - Servers
 - Clusters
 - Virtual Hosts
 - Migratable Targets
 - Coherence Servers
 - Coherence Clusters
 - Machines
 - Work Managers
 - Startup and Shutdown Classes
- Deployments
- Services
 - Messaging

How do I...

- Start and stop a deployed Enterprise application

Home Log Out Preferences Record Help Welcome, weblogic Connected to: base_domain

Home > JMS Modules > MDB_MODULE > ForeignServer-1 > JMS Modules > Summary of Deployments > Summary of Servers > Summary of Deployments > Summary of Servers > Summary of Deployments > GWMDB

Settings for GWMDB

Overview Deployment Plan Configuration Security **Targets** Control Testing Monitoring Notes

Use this page to specify the WebLogic Server instances and clusters to which you want to deploy this Enterprise application. These settings determine where the application is deployed at server startup time.

Target Assignments

Change Targets Showing 1 to 1 of 1 Previous Next

Component	Type	Current Targets
☐ GWMDB	Enterprise Application	Cluster-App
☐ GW_MDB_Bean.jar	EJB	(None specified)

Change Targets Showing 1 to 1 of 1 Previous Next

2) Health Should be OK if JMS is configured properly, otherwise Warning will be displayed

Change Center

View changes and restarts

Configuration editing is enabled. Future changes will automatically be activated as you modify, add or delete items in this domain.

Domain Structure

Environment

Deployments

Services

Messaging

JMS Servers

Store-and-Forward Agents

JMS Modules

Path Services

Bridges

Data Sources

Persistent Stores

Foreign JNDI Providers

Work Contexts

How do I...

- Install an Enterprise application
- Configure an Enterprise application
- Update (redeploy) an Enterprise application
- Start and stop a deployed Enterprise application
- Monitor the modules of an Enterprise application

Home Log Out Preferences Record Help

Welcome, weblogic | Connected to: base_domain

Home > Summary of Environment > Summary of Servers > Summary of Deployments > JMS Modules > MDB_MODULE > Summary of Environment > Summary of Servers > Summary of Deployments > GWMDB > Summary of Deployments

Summary of Deployments

Control Monitoring

This page displays a list of Java EE applications and stand-alone application modules that have been installed to this domain. Installed applications and modules can be started, stopped, updated (redeployed), or deleted from the domain by first selecting the application name and using the controls on this page.

To install a new application or module for deployment to targets in this domain, click the Install button.

Customize this table

Deployments

Install Update Delete Start Stop

Showing 1 to 5 of 5 Previous Next

☐	Name	State	Health	Type	Deployment Order
☐	FCUBSApp	Active	OK	Enterprise Application	100
☐	GWEEJB	Active	OK	Enterprise Application	100
☐	GWMDB	Active	OK	Enterprise Application	100
☐	jax-rs(1.1.1.9)	Active		Library	100
☐	SWEJB	Active	OK	Enterprise Application	100

Install Update Delete Start Stop

Showing 1 to 5 of 5 Previous Next

8. Frequently Asked Questions

8.1 Application and JMS Cluster Deployed on Same Cluster

Application and JMS Module can be deployed on the same cluster. In this document both are on different clusters, however it is possible to deploy on the one cluster. When it is deployed on same cluster then

- 1) Foreign Server Creation is not required
- 2) Targets should be given accordingly during SubDeployment Creation

8.2 Application Shows Warning upon Restart of Managed Servers

Managed Servers Start Order

- 1) Stop all managed servers.
- 2) Start only the JMS Cluster managed servers.
- 3) After these are started then start the App Cluster managed servers.

Even after proper JMS setup when the managed servers are restarted Health of the Application is Warning

The screenshot shows the Oracle WebLogic Server Administration Console. On the left, there is a 'Domain Structure' tree with 'Deployments' selected. Below it, a 'How do I...' section lists various tasks. The main area is titled 'Summary of Deployments' and contains a table of deployments. The table has columns for Name, State, Health, Type, and Deployment Order. The deployment 'GWMDB' is highlighted with a red box and shows a 'Warning' health status. The deployment 'GWEDB' also shows a 'Warning' health status. The deployment 'FCUBSApp (12.0.3.0)' shows 'OK' health. The deployment 'JAX-WS (1.1.1.9)' shows 'OK' health. The deployment 'SWEJB' shows 'OK' health.

Name	State	Health	Type	Deployment Order
FCUBSApp (12.0.3.0)	Active	OK	Enterprise Application	100
GWEDB	Active	OK	Enterprise Application	100
GWMDB	Active	Warning	Enterprise Application	100
JAX-WS (1.1.1.9)	Active	OK	Library	100
SWEJB	Active	OK	Enterprise Application	100

- 1) Force Stop the Application
- 2) Then Start the Application, this would resolve the Warning and the Health of Deployment is changed to OK.

8.3 Securing File Store Data

In order to properly secure file store data, set appropriate directory permissions on all file store directories. If data encryption is required, use appropriate third-party encryption software.

8.4 t3s Protocol

To secure the communication with the JMS Server use t3s protocol instead of t3. This is applicable when connecting to the connection factory to send or receive messages and also in the JNDI Connection URL provided in foreign server creation.

NOTE: when using the t3s protocol SSL Listen Port Enabled should be checked in server template and the port number used in the URL should be secure port.

8.5 How to Test the Deployment

1) Navigate to Services → JMS Modules → JMS_MODULE → MDB_QUEUE → MONITORING

View changes and restarts

Configuration editing is enabled. Future changes will automatically be activated as you modify, add or delete items in this domain.

Domain Structure

- Environment
 - Servers
 - Clusters
 - Virtual Hosts
 - Migratable Targets
 - Coherence Servers
 - Coherence Clusters
 - Machines
 - Work Managers
 - Startup and Shutdown Classes
- Deployments
- Services
- Messaging

How do I...

- Manage distributed queue messages
- Configure uniform distributed queues

Settings for MDB_QUEUE

Configuration Security **Monitoring** Subdeployment Notes

Use this page to view statistics about all of the members of a uniform distributed queue. Click on the individual member destination name in the table below to manage the messages on that destination.

To access the uniform distributed queue's message management page, select the check box next to its name, and then click the **Show Messages** button.

Customize this table

Destinations (Filtered - More Columns Exist)

Name	Consumers Current	Consumers High	Consumers Total
☐ JMS_MODULE/JMServer-1@MDB_QUEUE	64	64	64
☐ JMS_MODULE/JMServer-2@MDB_QUEUE	64	64	64

Show Messages Showing 1 to 2 of 2 Previous | Next

2) Select any one Server and Click on Show Messages

Configuration editing is enabled. Future changes will automatically be activated as you modify, add or delete items in this domain.

Domain Structure

- Environment
 - Servers
 - Clusters
 - Virtual Hosts
 - Migratable Targets
 - Coherence Servers
 - Coherence Clusters
 - Machines
 - Work Managers
 - Startup and Shutdown Classes
- Deployments
- Services
- Messaging

How do I...

- Manage queue messages
- Manage distributed queue messages
- Manage topic durable subscribers

System Status

Summary of JMS Messages

This page summarizes the available messages for a stand-alone queue, a distributed queue, or a topic durable subscriber. Use this page to view message details, create new messages, delete selected messages, move messages to another destination, export message contents in XML format to another file, import XML formatted message contents from another file, or drain all the messages from a destination.

Click on a message to view its contents.

Message Selector:

Customize this table

JMS Messages (Filtered - More Columns Exist)

ID	Corrid	Time Stamp	State String	JMS Delivery Mode	Message Size
There are no items to display					

New Delete Move Import Export Showing 1 to 0 of 0 Previous | Next

3) Click on New and enter the Message in Body and Click on OK

Change Center
View changes and restarts
Configuration editing is enabled. Future changes will automatically be activated as you modify, add or delete items in this domain.

Domain Structure

- Environment
 - Servers
 - Clusters
 - Virtual Hosts
 - Migratable Targets
 - Coherence Servers
 - Coherence Clusters
 - Machines
 - Work Managers
 - Startup and Shutdown Classes
- Deployments
- Services
 - Messaging

How do I...

- Manage queue messages
- Manage distributed queue messages
- Manage topic durable subscribers

System Status
Health of Running Servers

Failed (0)
Critical (0)
Overloaded (0)

Produce JMS Message
OK Cancel

JMS Message
The following properties will be used to produce a JMS message.

Type:

Correlation ID:

Expiration:

Priority:

Delivery Mode:

Delivery Time:

Redelivery Limit:

Body:

4) Message is Sent

Change Center
View changes and restarts
Configuration editing is enabled. Future changes will automatically be activated as you modify, add or delete items in this domain.

Domain Structure

- Environment
 - Servers
 - Clusters
 - Virtual Hosts
 - Migratable Targets
 - Coherence Servers
 - Coherence Clusters
 - Machines
 - Work Managers
 - Startup and Shutdown Classes
- Deployments
- Services
 - Messaging

How do I...

- Manage queue messages
- Manage distributed queue messages
- Manage topic durable subscribers

System Status
Health of Running Servers

Failed (0)
Critical (0)
Overloaded (0)

Summary of JMS Messages

Messages
JMS message sent successfully.

This page summarizes the available messages for a stand-alone queue, a distributed queue, or a topic durable subscriber. Use this page to view message details, create new messages, delete selected messages, move messages to another destination, export message contents in XML format to another file, import XML formatted message contents from another file, or drain all the messages from a destination.

Click on a message to view its contents.

Message Selector: Apply

[Customize this table](#)

JMS Messages (Filtered - More Columns Exist)

ID	CorrId	Time Stamp	State String	JMS Delivery Mode	Message Size
ID:<257876.1411126889162.0>		Fri Sep 19 17:11:29 IST 2014	receive transaction	Persistent	472

Showing 1 to 1 of 1 Previous | Next

5) Verify at backend or in the MDB log if the message is processed successfully.

8.6 Increase maximum number of message-driven bean threads

Default number of consumers for an MDB is 16. To increase or restrict this number create Custom Work Manager with a Max Threads Constraint in conjunction with MDBs.


The solution is to create a work manager with a max threads constraint and assign the proxy services dispatch policy to this work manager.

Steps to create custom work manager

- 1) Modify the MDB deployment descriptor and redploy the EAR
- 2) Create Custom Workmanager and add constraints to limit the number of the max MDB threads

8.6.1 Modify weblogic-ejb-jar.xml

- 1) Add below line to the weblogic-ejb-jar.xml of the MDB Ear
<dispatch-policy>GWMDBWM</dispatch-policy>



```
<?xml version="1.0" encoding="UTF-8"?>
<weblogic-ejb-jar
  xmlns="http://xmlns.oracle.com/weblogic/weblogic-ejb-jar"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xsi:schemaLocation="http://xmlns.oracle.com/weblogic/weblogic-ejb-jar http://xmlns.oracle.com/weblogic/weblogic-ejb-jar.xsd">
  <weblogic-enterprise-bean>
    <ejb-name>GWMDB</ejb-name>
    <!-- EJB Reference Descriptions STARTS-->
    <!-- EJB Resource Reference Descriptions STARTS-->
    <resource-description>
      <res-ref-name>FLEXTEST.WORLD</res-ref-name>
      <jndi-name>FLEXTEST.WORLD</jndi-name>
    </resource-description>
    <resource-description>
      <res-ref-name>MDBQCF</res-ref-name>
      <jndi-name>MDBQCF</jndi-name>
    </resource-description>
    <!-- EJB Resource Reference Descriptions ENDS-->
    <!-- EJB Resource environment Reference Descriptions STARTS-->
    <resource-env-description>
      <resource-env-ref-name>MDB_QUEUE_RESPONSE</resource-env-ref-name>
      <jndi-name>MDB_QUEUE_RESPONSE</jndi-name>
    </resource-env-description>
    <resource-env-description>
      <resource-env-ref-name>MDB_QUEUE_DLQ</resource-env-ref-name>
      <jndi-name>MDB_QUEUE_DLQ</jndi-name>
    </resource-env-description>
    <resource-env-description>
      <resource-env-ref-name>SW_MDB_QUEUE_RESPONSE</resource-env-ref-name>
      <jndi-name>SW_MDB_QUEUE_RESPONSE</jndi-name>
    </resource-env-description>
    <!-- EJB Resource environment Reference Descriptions ENDS-->
    <dispatch-policy>GWMDBWM</dispatch-policy>
  </weblogic-enterprise-bean>
</weblogic-ejb-jar>
```

- 2) Remove if any of the below tags present in weblogic-ejb-jar.xml
max-beans-in-free-pool and initial-beans-in-free-pool
- 3) Save the ear file and redeploy the EAR file.

8.6.2 Work Manager Creation

- 1) Login into weblogic console, navigate to Domain → Environment → WorkManager
Create new workmanager with the name GWMDBWM(as mentioned in property file) by following below steps

Oracle WebLogic Server Administration Console 12c

Home Log Out Preferences Record Help

Welcome, weblogic Connected to: FCUBSDomain

Home > Summary of Work Managers > MaxThreadsConstraint-0 > Summary of Work Managers > WorkManager-0 > Summary of Work Managers > MaxThreadsConstraint-0 > Summary of Servers > Summary of Environment > Summary of Servers > Summary of Work Managers

Create a New Work Manager Component

Back Next Finish Cancel

Select Work Manager Definition type

What type of Work Manager, Request Class or Constraint do you want to create?

- ☒ **Work Manager**
- ☐ Response Time Request Class
- ☐ Fair Share Request Class
- ☐ Context Request Class
- ☐ Maximum Threads Constraint
- ☐ Minimum Threads Constraint
- ☐ Capacity Constraint

Back Next Finish Cancel

Oracle WebLogic Server Administration Console 12c

Home Log Out Preferences Record Help

Welcome, weblogic Connected to: FCUBSDomain

Home > Summary of Work Managers > MaxThreadsConstraint-0 > Summary of Work Managers > WorkManager-0 > Summary of Work Managers > MaxThreadsConstraint-0 > Summary of Servers > Summary of Environment > Summary of Servers > Summary of Work Managers

Create a New Work Manager Component

Back Next Finish Cancel

Work Manager Properties

The following properties will be used to identify your new Work Manager.

* Indicates required fields

What would you like to name your new Work Manager?

* Name: GWMDBWM

Back Next Finish Cancel

Oracle WebLogic Server Administration Console 12c

Home Log Out Preferences Record Help

Welcome, weblogic Connected to: FCUBSDomain

Home > Summary of Work Managers > MaxThreadsConstraint-0 > Summary of Work Managers > WorkManager-0 > Summary of Work Managers > MaxThreadsConstraint-0 > Summary of Servers > Summary of Environment > Summary of Servers > Summary of Work Managers

Create a New Work Manager Component

Back Next Finish Cancel

Select deployment targets

You can target the Work Manager to any of these WebLogic Server instances or Clusters. Select the same targets on which you will deploy applications that reference the Work Manager.

Available targets :

Servers	
☐	AdminServer

Clusters	
☒	Cluster-App
☐	All servers in the cluster
☐	Cluster-JMS
☐	All servers in the cluster

Back Next Finish Cancel

ORACLE WebLogic Server Administration Console 12c

Home Log Out Preferences Record Help Welcome, weblogic Connected to: FCUBSDomain

Change Center
View changes and restarts
Pending changes exist. They must be activated to take effect.
[Activate Changes] [Undo All Changes]

Domain Structure
FCUBSDomain
Environment
Servers
Clusters
Coherence Clusters
Machines
Virtual Hosts
Work Managers
Startup and Shutdown Classes
Deployments
Services
Security Realms
Interoperability
Diagnostics

How do I...
• Create application-scoped constraints

Home > Summary of Work Managers > MaxThreadsConstraint-0 > Summary of Work Managers > WorkManager-0 > Summary of Work Managers > MaxThreadsConstraint-0 > Summary of Servers > Summary of Environment > Summary of Servers > Summary of Work Managers

Messages
Work Manager created successfully

Summary of Work Managers
A Work Manager defines a set of request classes and thread constraints that manage work performed by WebLogic Server instances. This page displays the global Work Managers, request classes and thread constraints defined for this domain.
Global Work Managers are defined at the domain level. You can also define application-level and module-level Work Managers.

Customize this table
Global Work Managers, Request Classes and Constraints
Showing 1 to 1 of 1 Previous | Next

Name	Type	Targets
GWMDBMW	Work Manager	Cluster-App

Showing 1 to 1 of 1 Previous | Next

2) Create new Max Thread Constraint and in the Count field give the desired thread count

ORACLE webLogic Server Administration Console 12c

Home Log Out Preferences Record Help Welcome, weblogic Connected to: FCUBSDomain

Change Center
View changes and restarts
Pending changes exist. They must be activated to take effect.
[Activate Changes] [Undo All Changes]

Domain Structure
FCUBSDomain
Environment
Servers
Clusters
Coherence Clusters
Machines
Virtual Hosts
Work Managers
Startup and Shutdown Classes
Deployments
Services
Security Realms
Interoperability
Diagnostics

How do I...
• Create application-scoped constraints
• Create application-scoped request classes
• Create application-scoped Work Managers

Home > Summary of Work Managers > MaxThreadsConstraint-0 > Summary of Work Managers > WorkManager-0 > Summary of Work Managers > MaxThreadsConstraint-0 > Summary of Servers > Summary of Environment > Summary of Servers > Summary of Work Managers

Create a New Work Manager Component
[Back] [Next] [Finish] [Cancel]

Select Work Manager Definition type
What type of Work Manager, Request Class or Constraint do you want to create?

- Work Manager
- Response Time Request Class
- Fair Share Request Class
- Context Request Class
- Maximum Threads Constraint**
- Minimum Threads Constraint
- Capacity Constraint

[Back] [Next] [Finish] [Cancel]

ORACLE webLogic Server Administration Console 12c

Home Log Out Preferences Record Help Welcome, weblogic Connected to: FCUBSDomain

Change Center
View changes and restarts
Pending changes exist. They must be activated to take effect.
[Activate Changes] [Undo All Changes]

Domain Structure
FCUBSDomain
Environment
Servers
Clusters
Coherence Clusters
Machines
Virtual Hosts
Work Managers
Startup and Shutdown Classes
Deployments
Services
Security Realms
Interoperability
Diagnostics

How do I...
• Create application-scoped constraints

Home > Summary of Work Managers > MaxThreadsConstraint-0 > Summary of Work Managers > WorkManager-0 > Summary of Work Managers > MaxThreadsConstraint-0 > Summary of Servers > Summary of Environment > Summary of Servers > Summary of Work Managers

Create a New Work Manager Component
[Back] [Next] [Finish] [Cancel]

Maximum Threads Constraint Properties
The following properties will be used to identify your new Max Threads Request Class.
* Indicates required fields

What would you like to name the new Maximum Threads Constraint?

* Name: MaxThreadsConstraint-0

What is the maximum number of concurrent threads to allocate for requests? Enter either a fixed thread count or the name of a Data Source whose size will be used for the constraint.

Count: 25

Data Source:

[Back] [Next] [Finish] [Cancel]

Change Center
View changes and restarts
Pending changes exist. They must be activated to take effect.
[Activate Changes] [Undo All Changes]

Domain Structure
FCUBSDomain
Environment
Servers
Clusters
Coherence Clusters
Machines
Virtual Hosts
Work Managers
Startup and Shutdown Classes
Deployments
Services
Security Realms
Interoperability
Diagnostics

How do I...
• Create application-scoped constraints
• Create application-scoped request classes
• Create application-scoped Work Managers

Home Log Out Preferences Record Help
Welcome, weblogic Connected to: FCUBSDomain
Home > Summary of Work Managers > MaxThreadsConstraint-0 > Summary of Work Managers > WorkManager-0 > Summary of Work Managers > MaxThreadsConstraint-0 > Summary of Servers > Summary of Environment > Summary of Servers > Summary of Work Managers

Create a New Work Manager Component
[Back] [Next] [Finish] [Cancel]

Select deployment targets
You can target the Work Manager to any of these WebLogic Server instances or Clusters. Select the same targets on which you will deploy applications that reference the Work Manager.

Available targets :

Servers
☐ AdminServer

Clusters
☒ Cluster-App
All servers in the cluster
☐ Cluster-JMS
All servers in the cluster

[Back] [Next] [Finish] [Cancel]

Change Center
View changes and restarts
Pending changes exist. They must be activated to take effect.
[Activate Changes] [Undo All Changes]

Domain Structure
FCUBSDomain
Environment
Servers
Clusters
Coherence Clusters
Machines
Virtual Hosts
Work Managers
Startup and Shutdown Classes
Deployments
Services
Security Realms
Interoperability
Diagnostics

How do I...
• Create application-scoped constraints
• Create application-scoped request classes
• Create application-scoped Work Managers

Home Log Out Preferences Record Help
Welcome, weblogic Connected to: FCUBSDomain
Home > Summary of Work Managers > MaxThreadsConstraint-0 > Summary of Work Managers > WorkManager-0 > Summary of Work Managers > MaxThreadsConstraint-0 > Summary of Servers > Summary of Environment > Summary of Servers > Summary of Work Managers

Messages
Maximum Threads Constraint created successfully

Summary of Work Managers
A Work Manager defines a set of request classes and thread constraints that manage work performed by WebLogic Server instances. This page displays the global Work Managers, request classes and thread constraints defined for this domain.
Global Work Managers are defined at the domain level. You can also define application-level and module-level Work Managers.

Customize this table

Global Work Managers, Request Classes and Constraints
[New] [Clone] [Delete] Showing 1 to 2 of 2 Previous | Next

Name	Type	Targets
GWMDBWM	Work Manager	Cluster-App
MaxThreadsConstraint-0	Maximum Threads Constraint	Cluster-App

[New] [Clone] [Delete] Showing 1 to 2 of 2 Previous | Next

3) Modify the newly created workmanager and assign the Maximum Thread Constraint that is created in above step.

View changes and restarts
Pending changes exist. They must be activated to take effect.
[Activate Changes] [Undo All Changes]

Domain Structure
FCUBSDomain
Environment
Servers
Clusters
Coherence Clusters
Machines
Virtual Hosts
Work Managers
Startup and Shutdown Classes
Deployments
Services
Security Realms
Interoperability
Diagnostics

How do I...
• Create application-scoped constraints
• Create application-scoped request classes
• Create application-scoped Work Managers
• Create global constraints
• Create global request classes
• Create global Work Managers

System States
Health of Running Servers

Home > MaxThreadsConstraint-0 > Summary of Work Managers > WorkManager-0 > Summary of Work Managers > MaxThreadsConstraint-0 > Summary of Servers > Summary of Environment > Summary of Servers > Summary of Work Managers > GWMDBWM

Settings for GWMDBWM
[Configuration] [Targets] [Notes]
[Save]

Use this page to define the request classes and constraints for the selected global Work Manager.

Name: (No value specified) The user-specified name of this MBean instance. [More Info...](#)

Request Class: (None configured) [New](#) A request class associated with this Work Manager. This may be a FairShareRequestClass, ResponseTimeRequestClass, or a ContentRequestClass. [More Info...](#)

Minimum Threads Constraint: (None configured) [New](#) The minimum number of threads allocated to resolve deadlocks. [More Info...](#)

Maximum Threads Constraint: (None configured) [New](#) The maximum number of concurrent threads that can be allocated to execute requests. [More Info...](#)

Capacity Constraint: (None configured) [New](#) The total number of requests that can be queued or executing before WebLogic Server begins rejecting requests. [More Info...](#)


Stuck Thread Action: Use server default behavior Specify how stuck threads should be detected, and what action to take should they occur. [More Info...](#)

Max Stuck Thread Time: 0 Time after which a executing thread is declared as stuck. [More Info...](#)

Stuck Thread Count: 0 Number of stuck threads after which the WorkManager is shutdown. [More Info...](#)

☒ Resume When Unstuck Whether to resume work manager once the stuck threads were cleared. [More Info...](#)

[Save]



- 4) Restart managed servers and notice the change in the number of consumers for the QUEUE's.

8.7 How High Availability is achieved

- 1) Application Server:
MDB_MODULE and the GWEJB ear are deployed in a cluster. Cluster has 4 managed servers, if any server goes down then the messages are processed by other managed servers.
- 2) JMS Provider:
JMS is deployed on 2 managed servers, JMSServer1 and JMSServer2, if any one goes down other will handle the messages.
- 3) FileStore:
File store is a cluster file system or database where if one node goes down then other will handle the requests.
- 4) DB Server:
Database is installed in RAC mode where it has more than 1 node, if a node goes down then other nodes will handle messages.

8.8 How to setup for Scheduler/Notifications

The above document can be used for setting up JMS for scheduler/notifications but additional queues and connection factory needs to be created.

8.9 What other modules uses JMS Queue's

JMS is used by following modules, relevant queues and factories needs to be created additionally

- 1) EMS for swift messages
- 2) GI for upload
- 3) ELCM
- 4) BIP

8.10 References

- 1) FCUBS_12.1_Weblogic12c_Middleware_Practices.doc
- 2) GATEWAY_Applications_WL.doc
- 3) Resource_Creation_WL.doc



FCUBS JMS Cluster Configuration 12c
[May] [2020]
Version 14.4.0.0.0

Oracle Financial Services Software Limited
Oracle Park
Off Western Express Highway
Goregaon (East)
Mumbai, Maharashtra 400 063
India

Worldwide Inquiries:
Phone: +91 22 6718 3000
Fax: +91 22 6718 3001
<https://www.oracle.com/industries/financial-services/index.html>

Copyright © [2007], [2020], Oracle and/or its affiliates. All rights reserved.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate failsafe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.