

**Oracle® Retail Pricing**

Operations Guide

Release 19.1.000

**F33060-01**

August 2020

Primary Author:

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

#### **Value-Added Reseller (VAR) Language**

##### **Oracle Retail VAR Applications**

The following restrictions and provisions only apply to the programs referred to in this section and licensed to you. You acknowledge that the programs may contain third party software (VAR applications) licensed to Oracle. Depending upon your product and its version number, the VAR applications may include:

- (i) the **MicroStrategy** Components developed and licensed by MicroStrategy Services Corporation (MicroStrategy) of McLean, Virginia to Oracle and imbedded in the MicroStrategy for Oracle Retail Data Warehouse and MicroStrategy for Oracle Retail Planning & Optimization applications.
- (ii) the **Wavelink** component developed and licensed by Wavelink Corporation (Wavelink) of Kirkland, Washington, to Oracle and imbedded in Oracle Retail Mobile Store Inventory Management.
- (iii) the software component known as **Access Via**<sup>™</sup> licensed by Access Via of Seattle, Washington, and imbedded in Oracle Retail Signs and Oracle Retail Labels and Tags.
- (iv) the software component known as **Adobe Flex**<sup>™</sup> licensed by Adobe Systems Incorporated of San Jose, California, and imbedded in Oracle Retail Promotion Planning & Optimization application.

You acknowledge and confirm that Oracle grants you use of only the object code of the VAR Applications. Oracle will not deliver source code to the VAR Applications to you. Notwithstanding any other term or condition of the agreement and this ordering document, you shall not cause or permit alteration of any VAR Applications. For purposes of this section, "alteration" refers to all alterations, translations, upgrades, enhancements, customizations or modifications of all or any portion of the VAR Applications including all

reconfigurations, reassembly or reverse assembly, re-engineering or reverse engineering and recompilations or reverse compilations of the VAR Applications or any derivatives of the VAR Applications. You acknowledge that it shall be a breach of the agreement to utilize the relationship, and/or confidential information of the VAR Applications for purposes of competitive discovery.

The VAR Applications contain trade secrets of Oracle and Oracle's licensors and Customer shall not attempt, cause, or permit the alteration, decompilation, reverse engineering, disassembly or other reduction of the VAR Applications to a human perceivable form. Oracle reserves the right to replace, with functional equivalent software, any of the VAR Applications in future releases of the applicable program.



---

---

# Contents

<b>Send Us Your Comments</b> .....	xi
<b>Preface</b> .....	xiii
Audience .....	xiii
Documentation Accessibility .....	xiii
Customer Support .....	xiii
Improved Process for Oracle Retail Documentation Corrections .....	xiv
Oracle Help Center (docs.oracle.com) .....	xiv
Conventions .....	xiv
<b>1 Introduction</b>	
<b>2 Pricing Batch Processes</b>	
<b>BDI Clearance Publishing (BDI_PRICING_CLR_TX_JOB)</b> .....	2-2
Scheduling Constraints .....	2-2
Restart/Recovery .....	2-2
Key Tables Affected .....	2-2
Design Assumptions .....	2-3
Output .....	2-3
<b>BDI Price Change Publishing (BDI_PRICING_PC_TX_CYCLE_JOB)</b> .....	2-3
Scheduling Constraints .....	2-3
Restart/Recovery .....	2-4
Key Tables Affected .....	2-4
Design Assumptions .....	2-4
Output .....	2-4
<b>Promotion Publishing (BDI_PRICING_PROMO_OFFER_TX_CYCLE_JOB)</b> .....	2-5
Scheduling Constraints .....	2-5
Restart/Recovery .....	2-5
Promotions Integration .....	2-5
Payload Tables .....	2-6
Payload Population Logic .....	2-7
BDI Tables .....	2-9
Key Tables Affected .....	2-9
Output .....	2-10
PRC_PAYLD_MSG_HDR_OUT .....	2-10

PROMO_OFFER_OUT .....	2-10
PROMO_OFFER_COND_OUT .....	2-11
PROMO_OFR_REWARD_OUT.....	2-11
PROM_OFR_CND_MRCH_OUT.....	2-12
PROMO_OFFER_LOC_OUT .....	2-13
PROMO_OFR_CANCEL_OUT.....	2-13
PROM_OFR_CNCL_ITM_OUT.....	2-13
PROM_OFR_CNCL_LOC_OUT.....	2-14
<b>ClearanceInductionBatch (Clearance Induction Batch) .....</b>	<b>2-14</b>
Design Overview.....	2-15
Scheduling Constraints .....	2-16
Restart/Recovery .....	2-16
Key Tables Affected .....	2-16
Design Assumptions.....	2-16
<b>ClearancePriceChangePublishBatch (Clearance Price Change Publish Batch) .....</b>	<b>2-16</b>
Design Overview.....	2-17
Scheduling Constraints .....	2-17
Restart/Recovery .....	2-17
Key Tables Affected .....	2-17
Output File .....	2-17
Output File Layout .....	2-18
Design Assumptions.....	2-19
<b>FutureRetailPurgeBatch Design .....</b>	<b>2-19</b>
Design Overview.....	2-19
Scheduling Constraints .....	2-19
Restart/Recovery .....	2-19
Key Tables Affected .....	2-19
Design Assumptions.....	2-20
<b>FutureRetailRollUpBatch (Future Retail Roll Up Batch) .....</b>	<b>2-20</b>
Design Overview.....	2-20
Scheduling Constraints .....	2-20
Restart/Recovery .....	2-20
Key Tables Affected .....	2-20
Design Assumptions.....	2-21
<b>ItemReclassBatch (Item Reclass Batch) .....</b>	<b>2-21</b>
Design Overview.....	2-21
Scheduling Constraints .....	2-21
Restart/Recovery .....	2-21
Key Tables Affected .....	2-21
Design Assumptions.....	2-22
<b>NewItemLocationBatch (New Item Location Batch Batch) .....</b>	<b>2-22</b>
Design Overview.....	2-22
Scheduling Constraints .....	2-22
Restart/Recovery .....	2-23
Key Tables Affected .....	2-23
Design Assumptions.....	2-24
<b>NightlyBatchCleanup (Nightly Cleanup Batch) .....</b>	<b>2-24</b>

Design Overview .....	2-24
Scheduling Constraints .....	2-24
Restart/Recovery .....	2-24
Key Tables Affected .....	2-25
Design Assumptions .....	2-25
<b>PriceChangeInductionBatch (Price Change Induction Batch)</b> .....	2-25
Design Overview .....	2-26
Scheduling Constraints .....	2-26
Restart/Recovery .....	2-26
Key Tables Affected .....	2-26
Design Assumptions .....	2-27
<b>PriceEventExecutionBatch (Price Event Execution Batch)</b> .....	2-27
Design Overview .....	2-27
Scheduling Constraints .....	2-27
Restart/Recovery .....	2-28
Key Tables Affected .....	2-28
Design Assumptions .....	2-28
PriceEventExecutionForChunkCCEmergencyEvents Batch Design .....	2-28
Usage .....	2-28
Detail .....	2-28
Primary Tables Involved .....	2-28
Threading .....	2-29
ProcessPendingChunkBatch Batch Design .....	2-29
Usage .....	2-29
Details .....	2-29
Assumptions and Scheduling Notes .....	2-29
Primary Tables Involved .....	2-30
Threading .....	2-30
<b>PromotionInductionBatch (Promotion Induction Batch)</b> .....	2-30
Design Overview .....	2-31
Scheduling Constraints .....	2-31
Key Tables Affected .....	2-31
<b>Purge Batch (PurgeBatch)</b> .....	2-32
System Options .....	2-33
Usage .....	2-33
Scheduling Constraints .....	2-33
Restart/Recovery .....	2-33
Key Tables Affected .....	2-33
<b>PurgeGTTCaptureBatch (Purge GTT Capture Batch)</b> .....	2-36
Design Overview .....	2-36
Scheduling Constraints .....	2-36
Restart/Recovery .....	2-36
Key Tables Affected .....	2-37
Design Assumptions .....	2-37
<b>RegularPriceChangePublishBatch (Regular Price Change Publish Batch)</b> .....	2-37
Design Overview .....	2-37
Scheduling Constraints .....	2-38

Restart/Recovery .....	2-38
Key Tables Affected .....	2-38
Output Files.....	2-38
Output File Layout .....	2-39
Design Assumptions.....	2-40

### 3 ReST Services

<b>Price Inquiry</b> .....	3-1
Business Overview .....	3-1
Service Type.....	3-1
REST URL.....	3-1
Roles Allowed.....	3-1
Request Headers.....	3-1
URL Query Parameters .....	3-1
Request Body .....	3-2
Response Body.....	3-2
<b>Initial Retail</b> .....	3-3
Business Overview .....	3-3
Service Type.....	3-3
REST URL.....	3-3
Roles Allowed.....	3-3
Request Headers.....	3-3
URL Query Parameters .....	3-3
Request Body .....	3-3
Response Body.....	3-3
<b>Price Change Induction</b> .....	3-4
Business Overview .....	3-4
Service Type.....	3-4
REST URL.....	3-4
Roles Allowed.....	3-4
Request Headers.....	3-4
URL Query Parameters .....	3-5
Request Body .....	3-5
Response Body.....	3-6
<b>Clearance Induction</b> .....	3-6
Business Overview .....	3-6
Service Type.....	3-6
REST URL.....	3-6
Roles Allowed.....	3-6
Request Headers.....	3-7
URL Query Parameters .....	3-7
Request Body .....	3-7
Response Body.....	3-8
<b>Promotion Create</b> .....	3-8
Business Overview .....	3-8
Service Type.....	3-8
REST URL.....	3-8



Roles Allowed.....	3-8
Request Headers.....	3-9
URL Query Parameters .....	3-9
Request Body .....	3-9
Response Body.....	3-13

## **4 Backend System Administration and Configuration**

<b>Supported Environments</b> .....	4-1
<b>Exception Handling</b> .....	4-1
<b>Logging Configuration</b> .....	4-1
ADF Logging .....	4-2
Batch Client Logging .....	4-2
Batch_logging Properties .....	4-2
<b>Configurable GTTCapture</b> .....	4-3



---

---

## Send Us Your Comments

Oracle welcomes customers' comments and suggestions on the quality and usefulness of this document.

Your feedback is important, and helps us to best meet your needs as a user of our products. For example:

- Are the implementation steps correct and complete?
- Did you understand the context of the procedures?
- Did you find any errors in the information?
- Does the structure of the information help you with your tasks?
- Do you need different information or graphics? If so, where, and in what format?
- Are the examples correct? Do you need more examples?

If you find any errors or have any other suggestions for improvement, then please tell us your name, the name of the company who has licensed our products, the title and part number of the documentation and the chapter, section, and page number (if available).

---

---

**Note:** Before sending us your comments, you might like to check that you have the latest version of the document and if any concerns are already addressed. To do this, access the Online Documentation available on the Oracle Technology Network Web site. It contains the most current Documentation Library plus all documents revised or released recently.

---

---

Send your comments to us using the electronic mail address: [retail-doc\\_us@oracle.com](mailto:retail-doc_us@oracle.com)

Please give your name, address, electronic mail address, and telephone number (optional).

If you need assistance with Oracle software, then please contact your support representative or Oracle Support Services.

If you require training or instruction in using Oracle software, then please contact your Oracle local office and inquire about our Oracle University offerings. A list of Oracle offices is available on our Web site at <http://www.oracle.com>.



---

---

# Preface

This *Oracle Retail Pricing Cloud Service Operations Guide* provides critical information about the processing and operating details of Product, including the following:

## Audience

This guide is for:

- Systems administration and operations personnel
- Systems analysts
- Integrators and implementers
- Business analysts who need information about Product processes and interfaces

## Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at

<http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

### Access to Oracle Support

Oracle customers that have purchased support have access to electronic support through My Oracle Support. For information, visit

<http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit

<http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

## Customer Support

To contact Oracle Customer Support, access My Oracle Support at the following URL:

<https://support.oracle.com>

When contacting Customer Support, please provide the following:

- Product version and program/module name
- Functional and technical description of the problem (include business impact)
- Detailed step-by-step instructions to re-create
- Exact error message received
- Screen shots of each step you take

## Improved Process for Oracle Retail Documentation Corrections

To more quickly address critical corrections to Oracle Retail documentation content, Oracle Retail documentation may be republished whenever a critical correction is needed. For critical corrections, the republication of an Oracle Retail document may at times not be attached to a numbered software release; instead, the Oracle Retail document will simply be replaced on the Oracle Technology Network Web site, or, in the case of Data Models, to the applicable My Oracle Support Documentation container where they reside.

Oracle Retail product documentation is available on the following web site:

<https://docs.oracle.com/en/industries/retail/index.html>

An updated version of the applicable Oracle Retail document is indicated by Oracle part number, as well as print date (month and year). An updated version uses the same part number, with a higher-numbered suffix. For example, part number E123456-02 is an updated version of a document with part number E123456-01.

If a more recent version of a document is available, that version supersedes all previous versions.

## Oracle Help Center (docs.oracle.com)

Oracle Retail product documentation is available on the following web site:

<https://docs.oracle.com/en/industries/retail/index.html>

(Data Model documents can be obtained through My Oracle Support.)

## Conventions

The following text conventions are used in this document:

Convention	Meaning
<b>boldface</b>	Boldface type indicates graphical user interface elements associated with an action, or terms defined in text or the glossary.
<i>italic</i>	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.
monospace	Monospace type indicates commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter.

---

---

## Introduction

Oracle Retail Pricing provides the ability to define, maintain, and review price changes, clearances, and promotions as well as provides the ability to pass approved price events onto downstream selling systems.

Pricing functionality provides support for initial pricing, regular price changes, clearance markdowns, and promotions. It also offers the ability to upload price changes and clearance events in multiple ways including spreadsheet induction, bulk upload, or web service. The user interface supports price change or clearance wizards for entering multiple price events at once as well as a quick entry panel for quickly adding these types of price events.

Pricing also supports an offer wizard for entering and maintaining offers within a promotion. Offers can be at the item or transaction level and Pricing supports multiple templates for different offer types.

Pricing functionality provides support for initial pricing, regular price changes, clearance markdowns, and promotions. It also provides for the execution of these price events to update the selling systems, such as Xstore POS, and to update the item/location price and stock ledger when the price changes go into effect.

---

---

**Note:** Users should not access Oracle Retail Pricing during the Retail Merchandising System (Merchandising) batch window as it may cause some unpredictable results.

---

---





## Pricing Batch Processes

This chapter discusses Java-based batch processing within Oracle Retail Pricing.

**Table 2–1 Functional Descriptions and Dependencies**

Batch processes	Details
BDI Clearance Publishing	This batch process utilizes BDI (Bulk Data Integration) to facilitate the bulk data movement to stage clearance data. The batch job BDI_PRICING_CLR_TX_JOB stages clearance data.
BDI Price Change Publishing	This batch process utilizes BDI (Bulk Data Integration) to facilitate the bulk data movement to stage clearance data. The batch job BDI_PRICING_PC_TX_JOB stages price change data.
Promotion Publishing	This batch process utilizes BDI (Bulk Data Integration) to facilitate the bulk data movement to target applications. The batch job BDI_PRICING_PROMO_OFFER_TX_CYCLE_JOB stages promotion data.
ClearanceInductionBatch	This batch program allows the user to upload clearance events in bulk.
ClearancePriceChangePublishBatch	This batch process formats and stages output of clearance price change price events to be published via a flat file format.
futureRetailPurgeBatch	This timed multi-threaded batch deletes records from future retail tables that are past the retention period of the associated price events.
FutureRetailRollUpBatch.sh	This batch attempts to roll up timelines at a lower level by comparing lower level timelines to higher levels and removing any lower level timelines that match higher level timelines exactly.
itemReclassBatch	When items are moved from one department/class/subclass to another in the merchandising system, this batch process accordingly sets the correct department/class/subclass for these items in the Future Retail table.
NewItemLocationBatch	This batch ranges item locations by putting them into the future retail table and Pricing item/location. Item and locations are fed to this program via the RPM_ITEM_LOC_WS table, which is populated by a Merchandising process.
NightlyBatchCleanup	This batch performs "clean up" logic against Pricing database objects.
PriceChangeInductionBatch	This batch program allows the user to upload regular price changes in bulk.
PriceEventExecutionBatch	This batch process performs the necessary work to start (regular price change, clearance price change, promotions) and end (price clearances, promotions) pricing events.
priceEventExecutionForChunkCCEmergencyEvents	This batch process performs the work to start and end pricing events which were processed in chunk conflict checking.

**Table 2–1 (Cont.) Functional Descriptions and Dependencies**

Batch processes	Details
ProcessPendingChunkBatch	The batch looks for any events from the chunk conflict checking process that need additional processing due to errors, and reprocesses them using regular conflict checking.
PromotionInductionBatch	This batch program allows the user to upload promotions in bulk.
PurgeBatch	This generic purge batch calls most of the purge batches into one purge process.
PurgeGttCaptureBatch	This batch process deletes records from gtt data capture tables.
RegularPriceChangePublishBatch	This batch process formats and stages output of regular price change price events.
RefreshPosDataBatch	The RefreshPosDataBatch program deletes the contents of the payload tables.

## BDI Clearance Publishing (BDI\_PRICING\_CLR\_TX\_JOB)

This program utilizes BDI (Bulk Data Integration) to facilitate the bulk data movement to target applications. The batch job BDI\_PRICING\_CLR\_TX\_JOB is defined in the Merchandising JOS batch job admin to stage clearance data.

The program can be scheduled ad hoc, recurring, and nightly depending on the needs of each retailer. Each run of the program will include changes for approved clearances since the previous run.

## Scheduling Constraints

**Table 2–2 BDI\_PRICING\_CLR\_TX\_JOB Scheduling Constraints**

Schedule Information	Description
Frequency	Ad hoc, Recurring, Nightly
Scheduling Considerations	not applicable
Pre-Processing	not applicable
Post-Processing	not applicable
Threading Scheme	not applicable

## Restart/Recovery

N/A

## Key Tables Affected

**Table 2–3 Key Tables Affected**

Table	Select	Insert	Update	Delete
RPM_CLR_BDL_HELPER_WS	Yes	No	No	No
RPM_CLEARANCE	Yes	No	No	No
RPM_PRICE_EVENT_PAYLOAD	Yes	No	No	No

## Design Assumptions

N/A

## Output

BDI extractor jobs call respective BDI functions to extract data from Pricing tables to BDI outbound staging table CLEARANCE\_OUT.

**Table 2–4 BDI Outbound Staging Table CLEARANCE\_OUT**

Name	Null	Type	Description
BDI_SEQ_ID	No	NUMBER	BDI Internal Column
BDI_APP_NAME	No	VARCHAR2(50)	BDI Internal Column
BDI_DATASET_TYPE	Yes	VARCHAR2(20)	BDI Internal Column
BDI_DATASET_ACTION	Yes	VARCHAR2(20)	BDI Internal Column
REC_ID	No	NUMBER(10,0)	The ID of the record
RECORD_TYPE	No	VARCHAR2(50)	The record type. Valid values (Create/Update/Delete)
CLEARANCE_ID	No	NUMBER(15,0)	The clearance ID
ITEM	Yes	VARCHAR2(25)	The item ID
LOCATION	Yes	NUMBER(10,0)	The location ID
LOCATION_TYPE	Yes	VARCHAR2(30)	The location Type. Valid values (S 'Store' or W 'Warehouse').
EFFECTIVE_DATE	Yes	TIMESTAMP(2)	Effective date of the clearance
RETAIL	Yes	NUMBER(20,4)	The clearance retail for the item location
UOM	Yes	VARCHAR2(25)	The retail unit of measure
CURRENCY	Yes	VARCHAR2(25)	The currency for the location
RESET_INDICATOR	No	NUMBER(1,0)	Indicates if the clearance event is a reset. Valid values: 0- The record is not a reset; 1 – The record is a reset.

## BDI Price Change Publishing (BDI\_PRICING\_PC\_TX\_CYCLE\_JOB)

This program utilizes BDI (Bulk Data Integration) to facilitate the bulk data movement to target applications. The batch job BDI\_PRICING\_PC\_TX\_JOB is defined in the Merchandising JOS batch job admin to stage clearance data.

The program can be scheduled ad hoc, recurring, and nightly depending on the needs of each retailer. Each run of the program will include changes for approved price changes since the previous run.

## Scheduling Constraints

**Table 2–5 BDI\_PRICING\_PC\_TX\_CYCLE\_JOB Scheduling Constraints**

Schedule Information	Description
Frequency	Ad hoc, Recurring, Nightly
Scheduling Considerations	not applicable

**Table 2–5 (Cont.) BDI\_PRICING\_PC\_TX\_CYCLE\_JOB Scheduling Constraints**

Schedule Information	Description
Pre-Processing	not applicable
Post-Processing	not applicable
Threading Scheme	not applicable

## Restart/Recovery

N/A

## Key Tables Affected

**Table 2–6 Key Tables Affected**

Table	Select	Insert	Update	Delete
RPM_PC_BDI_HELPER_WS	Yes	No	No	No
RPM_PRICE_EVENT_PAYLOAD	Yes	No	No	No
RPM_PRICE_CHANGE	Yes	No	No	No

## Design Assumptions

N/A

## Output

BDI extractor jobs call respective BDI functions to extract data from Pricing tables to BDI outbound staging table PRICE\_CHANGE\_OUT.

**Table 2–7 BDI Outbound Staging Table PRICE\_CHANGE\_OUT**

Name	Null	Type	Description
BDI_SEQ_ID	No	NUMBER	BDI Internal Column
BDI_APP_NAME	No	VARCHAR2(50)	BDI Internal Column
BDI_DATASET_TYPE	Yes	VARCHAR2(20)	BDI Internal Column
BDI_DATASET_ACTION	Yes	VARCHAR2(20)	BDI Internal Column
REC_ID	No	NUMBER(10,0)	The ID of the record
RECORD_TYPE	No	VARCHAR2(50)	The record type. Valid values (Create/Update/Delete)
PRICE_CHANGE_ID	No	NUMBER(15,0)	The price change ID
ITEM	Yes	VARCHAR2(25)	The item ID
LOCATION	Yes	NUMBER(10,0)	The location ID
LOCATION_TYPE	Yes	VARCHAR2(30)	The location Type. Valid values (S 'Store' or W 'Warehouse')
EFFECTIVE_DATE	Yes	TIMESTAMP(2)	Effective date of the price change
RETAIL	Yes	NUMBER(20,4)	The new regular retail for the item location

**Table 2–7 (Cont.) BDI Outbound Staging Table PRICE\_CHANGE\_OUT**

Name	Null	Type	Description
UOM	Yes	VARCHAR2(25)	The retail unit of measure
CURRENCY	Yes	VARCHAR2(25)	The currency for the location
RETAIL_CHANGE_IND	No	NUMBER(6,0)	Indicates whether the retail changed with this price change

## Promotion Publishing (BDI\_PRICING\_PROMO\_OFFER\_TX\_CYCLE\_JOB)

This program utilizes BDI (Bulk Data Integration) to facilitate the bulk data movement to target applications. The batch job BDI\_PRICING\_PROMO\_OFFER\_TX\_CYCLE\_JOB is defined in the Merchandising JOS batch job admin to stage promotions data.

The program can be scheduled ad hoc, recurring, and nightly depending on the needs of each retailer. Each run of the program will include changes for approved price changes since the previous run.

## Scheduling Constraints

**Table 2–8 BDI\_PRICING\_CLR\_TX\_JOB Scheduling Constraints**

Schedule Information	Description
Frequency	Ad hoc, Recurring, Nightly
Scheduling Considerations	not applicable
Pre-Processing	not applicable
Post-Processing	not applicable
Threading Scheme	not applicable

## Restart/Recovery

N/A

## Promotions Integration

The Pricing Cloud Service will communicate promotional offers at a rule criteria level instead of the item/location level, where applicable. Offers in an approved or active state and candidates for integration when edited.

[Table 2–9](#) has some examples of message types that are created when certain activities are being triggered by user:

**Table 2–9 Promotions Integration Examples**

Message Type	Activities in Promotion UI
OfferCreate	This message type is generated when the user changes the state of an Offer to Approved state.
OfferDelete	This message type is generated when the following action happen: <ul style="list-style-type: none"> <li>■ The user changes the state of an Offer to Delete state</li> <li>■ The user deletes an Offer</li> </ul>
OfferHeaderUpdate	This message type is generated when the user updates the Promotion Offer Header information that is already in Approved state, for example, changing the start date, end date, comments, or coupon code of the promotion.
OfferCondUpdate	This message type is generated when the user updates the Condition information of an Offer, for example, changing the spending type or the spending value.
OfferRwdUpdate	This message type is generated when the user updates the Reward information of an Offer, for example, the reward value (change_type, change_amount, change_percent, etc.) of a promotion.
OfferRwdMerchAdd	This message type is generated when the user adds merchandise hierarchy to a promotion Reward list.
OfferCondMerchAdd	This message type is generated when the user adds merchandise hierarchy to a promotion Condition list.
OfferCondMerchDel	This message type is generated when the user deletes merchandise hierarchy from Promotion Condition list.
OfferRwdMerchDel	This message type is generated when the user deletes merchandise hierarchy from Promotion Reward list.
OfferLocAdd	This message type is generated when the user adds a location to a promotion.
OfferLocDel	This message type is generated when the user deletes a location to a promotion.
OfferCancel	This message type is generated when the user cancel a Promotion Offer.
OfferCondMerchCancel	This message type is generated when the user cancel a merchandise hierarchy from the Condition List of Promotion Offer.
OfferRwdMerchCancel	This message type is generated when the user cancel a merchandise hierarchy from the Reward List of Promotion Offer.
OfferLocCancel	This message type is generated when the user cancel a location of Promotion Offer.

## Payload Tables

Table 2–10 lists Payload tables are used to hold staged data for BDI population:

**Table 2–10 Payload Tables that Hold Staged Data for BDI population**

Table	Description
RPM_PRICE_EVENT_PAYLOAD	oMessage header level data - shared with PC and CLR Payload data. For promotion offers, the RIB_TYPE field will hold the same values as what is staged in the RPM_PROMO_OFFER_PUB_WS.PUB_TYPE_CODE table.
RPM_PROMO_OFFER_PUB_WS.PUB_TYPE_CODE	This table is populated for all promotion offer messages.
RPM_PROMO_OFFER_PAYLOAD	Offer header level data. This table is populated for all promotion offer messages.

**Table 2–10 (Cont.) Payload Tables that Hold Staged Data for BDI population**

Table	Description
RPM_PROMO_OFR_CND_MRCH_PAYLOAD	This table holds the payload information of the merchandise nodes associated with a promotion offer condition.  This table is only populated when the condition for an approved offer has new merchandise data added to it or deleted from it.
RPM_PROMO_OFR_RWD_MRCH_PAYLOAD	This table holds the payload information of the merchandise nodes associated with a promotion offer reward.  This table is only populated when the reward for an approved offer has new merchandise data added to it or deleted from it.
RPM_PROMO_OFFER_LOC_PAYLOAD	This table holds the payload information of the location nodes associated with a promotion offer. Only store data will be on this table – any zones associated with an offer will be exploded out to store level.  This table is only populated when an approved offer has new zone/loc data added to it or deleted from it.
RPM_PROM_OFR_CNCL_ITEM_PAYLOAD	This table holds the payload information for items cancelled from active promotion offers.  This table is only populated for active offers when merchandise is cancelled from a reward or condition.
RPM_PROM_OFR_CNCL_LOC_PAYLOAD	This table holds the payload information for locations cancelled from active promotion offers.
RPM_PROMO_OFFER_CANCEL_PAYLOAD	This table holds the payload information for when active promotion offers are cancelled as a whole.

### Payload Population Logic

In many situations, the payload population logic will only populate a small piece of data about an offer (the action along with the promotion and offer ids). In these situations, the BDI extraction logic will use the promotion offer operational tables as the main source of data to stage in the BDI tables rather than the payload tables. In all scenarios, the RPM\_PRICE\_EVENT\_PAYLOAD and RPM\_PROMO\_OFFER\_PAYLOAD tables will be utilized.

BDI data population retrieves the data from both the Payload tables and also Promotion Operational tables depending on the message type.

In order to populate the data into BDI tables more efficiently, a workspace tables called RPM\_PROMO\_BDI\_HELPER\_WS is used. This workspace table will be inserted with the data from the two main payload tables that drives the whole processes, rpm\_price\_event\_payload and rpm\_promo\_offer\_payload tables.

Once the workspace table is populated, the system will perform some cleanup activities so that if the same promotions are being updated more than once, it will only write one Update message with the latest information into BDI tables. If the Promotion is being created and then Deleted, it will not get written into BDI tables at all. In order to avoid multiple update messages under the same promotion as mentioned previously, the system will retrieve the data from the Promotion Operational tables itself in order to get the latest data set of a promotion. The only time that payload tables records any activities is when a Promotion is deleted from the system, any merchandise hierarchy is deleted from a Promotion Condition or Reward, location is deleted from promotion and Canceling Promotion. Once the cleanup processed is done, the data will be inserted into BDI tables.

Table 2–11 maps what message structures use which payload or operational tables to build the BDI data.

**Table 2-11 Message Structures to Build the BDI data**

Message Type	Source Tables	Target Tables
OfferCreate	RPM_PRICE_EVENT_PAYLOAD, RPM_PROMO_OFFER_PAYLOAD, RPM_PROMO_OFFER, RPM_PROMO_OFFER_COND, RPM_PROMO_OFFER_COND_MERCH, RPM_PROMO_OFFER_REWARD, RPM_PROMO_OFFER_REWARD_MERCH, RPM_PROMO_OFFER_ZONE_LOC	PRC_PAYLD_MSG_HDR_OUT, PROMO_OFFER_OUT, PROMO_OFFER_COND_OUT, PROM_OFR_CND_MRCH_OUT, PROMO_OFR_REWARD_OUT, PROM_OFR_RWD_MRCH_OUT, PROMO_OFFER_LOC_OUT
OfferDelete	RPM_PRICE_EVENT_PAYLOAD, RPM_PROMO_OFFER_PAYLOAD	PRC_PAYLD_MSG_HDR_OUT, PROMO_OFFER_OUT
OfferUpdate	RPM_PRICE_EVENT_PAYLOAD, RPM_PROMO_OFFER_PAYLOAD, RPM_PROMO_OFFER	PRC_PAYLD_MSG_HDR_OUT, PROMO_OFFER_OUT
OfferCondUpdate	RPM_PRICE_EVENT_PAYLOAD, RPM_PROMO_OFFER_PAYLOAD, RPM_PROMO_OFFER_COND	PRC_PAYLD_MSG_HDR_OUT, PROMO_OFFER_COND_OUT
OfferCondMerchAdd	RPM_PRICE_EVENT_PAYLOAD, RPM_PROMO_OFFER_PAYLOAD, RPM_PROMO_OFFER_COND_MERCH	PRC_PAYLD_MSG_HDR_OUT, PROM_OFR_CND_MRCH_OUT
OfferRwdUpdate	RPM_PRICE_EVENT_PAYLOAD, RPM_PROMO_OFFER_PAYLOAD, RPM_PROMO_OFFER_REWARD	PRC_PAYLD_MSG_HDR_OUT, PROMO_OFR_REWARD_OUT
OfferRwdMerchAdd	RPM_PRICE_EVENT_PAYLOAD, RPM_PROMO_OFFER_PAYLOAD, RPM_PROMO_OFFER_REWARD_MERCH	PRC_PAYLD_MSG_HDR_OUT, PROM_OFR_RWD_MRCH_OUT
OfferCondMerchDel	RPM_PRICE_EVENT_PAYLOAD, RPM_PROMO_OFFER_PAYLOAD, RPM_PROMO_OFR_CND_MRCH_PAYLOAD	PRC_PAYLD_MSG_HDR_OUT, PROM_OFR_CND_MRCH_OUT
OfferRwdMerchDel	RPM_PRICE_EVENT_PAYLOAD, RPM_PROMO_OFFER_PAYLOAD, RPM_PROMO_OFR_CND_MRCH_PAYLOAD	PRC_PAYLD_MSG_HDR_OUT, PROM_OFR_RWD_MRCH_OUT
OfferLocAdd	RPM_PRICE_EVENT_PAYLOAD, RPM_PROMO_OFFER_PAYLOAD, RPM_PROMO_OFFER_LOC_PAYLOAD	PRC_PAYLD_MSG_HDR_OUT, PROMO_OFFER_LOC_OUT
OfferLocDel	RPM_PRICE_EVENT_PAYLOAD, RPM_PROMO_OFFER_PAYLOAD, RPM_PROMO_OFFER_LOC_PAYLOAD	PRC_PAYLD_MSG_HDR_OUT, PROMO_OFFER_LOC_OUT
OfferCancel	RPM_PRICE_EVENT_PAYLOAD, RPM_PROMO_OFFER_PAYLOAD, RPM_PROMO_OFFER_CANCEL_PAYLOAD	PRC_PAYLD_MSG_HDR_OUT, PROMO_OFR_CANCEL_OUT
OfferCondMerchCancel	RPM_PRICE_EVENT_PAYLOAD, RPM_PROMO_OFFER_PAYLOAD, RPM_PROM_OFR_CNCL_ITEM_PAYLOAD	PRC_PAYLD_MSG_HDR_OUT, PROM_OFR_CNCL_ITM_OUT
OfferRwdMerchCancel	RPM_PRICE_EVENT_PAYLOAD, RPM_PROMO_OFFER_PAYLOAD, RPM_PROM_OFR_CNCL_ITEM_PAYLOAD	PRC_PAYLD_MSG_HDR_OUT, PROM_OFR_CNCL_ITM_OUT
OfferLocCancel	RPM_PRICE_EVENT_PAYLOAD, RPM_PROMO_OFFER_PAYLOAD, RPM_PROM_OFR_CNCL_LOC_PAYLOAD	PRC_PAYLD_MSG_HDR_OUT, PROM_OFR_CNCL_LOC_OUT



## BDI Tables

The message structure in the BDI tables will that even though there is a hierarchical relationship between tables, each table will not reference an ID for the entity above it. Rather, each full message will be identified by a unique ID that is stored on all tables – the PAYLOAD\_ID column on each BDI table. Thus, for an OfferCreate message, each of the seven BDI tables populated will have data with the same PAYLOAD\_ID value and the consuming system will need to understand the structure of the tables in relation to each other for that specific message type.

Table 2–12 lists the BDI tables and its parent table from a high level perspective

**Table 2–12 BDI Tables**

BDI Table	Parent Table
PRC_PAYLD_MSG_HDR_OUT	none
PROMO_OFFER_OUT	PRC_PAYLD_MSG_HDR_OUT
PROMO_OFFER_COND_OUT	PROMO_OFFER_OUT
PROMO_OFR_REWARD_OUT	PROMO_OFFER_OUT
PROM_OFR_CND_MRCH_OUT	PROMO_OFFER_COND_OUT
PROM_OFR_RWD_MRCH_OUT	PROMO_OFR_REWARD_OUT
PROMO_OFFER_LOC_OUT	PROMO_OFFER_OUT
PROMO_OFR_CANCEL_OUT	PRC_PAYLD_MSG_HDR_OUT
PROM_OFR_CNCL_ITM_OUT	PRC_PAYLD_MSG_HDR_OUT
PROM_OFR_CNCL_LOC_OUT	PRC_PAYLD_MSG_HDR_OUT

## Key Tables Affected

**Table 2–13 BDI Key Tables Affected**

Table	Select	Insert	Update	Delete
PRC_PAYLD_MSG_HDR_OUT	Yes	No	No	No
PROMO_OFFER_OUT	Yes	No	No	No
PROMO_OFFER_OUT	Yes	No	No	No
PROMO_OFFER_COND_OUT	Yes	No	No	No
PROMO_OFR_REWARD_OUT	Yes	No	No	No
PROMO_OFFER_OUT	Yes	No	No	No
PRC_PAYLD_MSG_HDR_OUT	Yes	No	No	No
PROMO_OFFER_OUT	No	Yes	No	No
PROMO_OFFER_COND_OUT	No	Yes	No	No
PROMO_OFR_REWARD_OUT	No	Yes	No	No
PROM_OFR_CND_MRCH_OUT	No	Yes	No	No
PROM_OFR_RWD_MRCH_OUT	No	Yes	No	No
PROMO_OFFER_LOC_OUT	No	Yes	No	No

**Table 2–13 (Cont.) BDI Key Tables Affected**

Table	Select	Insert	Update	Delete
PROMO_OFR_CANCEL_OUT	No	Yes	No	No
PROM_OFR_CNCL_ITM_OUT	No	Yes	No	No
PROM_OFR_CNCL_LOC_OUT	No	Yes	No	No

## Output

BDI extractor jobs call respective BDI functions to extract data from Pricing tables to BDI outbound staging tables which mirror the structure of the Pricing promotions tables.

### PRC\_PAYLD\_MSG\_HDR\_OUT

**Table 2–14 PRC\_PAYLD\_MSG\_HDR\_OUT**

COLUMN	TYPE	NULLABLE	COMMENT
BDI_SEQ_ID	NUMBER	No	bdi internal column
BDI_APP_NAME	VARCHAR2(50)	No	bdi internal column
BDI_DATASET_TYPE	VARCHAR2(20)	Yes	bdi internal column
BDI_DATASET_ACTION	VARCHAR2(20)	Yes	bdi internal column
PRC_PAYLD_MSG_HDR_ID	NUMBER(10)	No	The unique payload ID for the message.
MESSAGE_TYPE	VARCHAR2(50)	No	The type of message associated to the payload_id.

### PROMO\_OFFER\_OUT

**Table 2–15 PROMO\_OFFER\_OUT**

COLUMN	TYPE	NULLABLE	COMMENT
BDI_SEQ_ID	NUMBER	No	bdi internal column
BDI_APP_NAME	VARCHAR2(50)	No	bdi internal column
BDI_DATASET_TYPE	VARCHAR2(20)	Yes	bdi internal column
BDI_DATASET_ACTION	VARCHAR2(20)	Yes	bdi internal column
PROMO_OFFER_ID	NUMBER(10)	No	The payload ID of the promotion offer.
PAYLOAD_ID	NUMBER(10)	No	The message payload ID.
PROMO_ID	NUMBER(10)	No	The promo ID.
OFFER_ID	NUMBER(10)	No	The offer ID.
OFFER_DESC	VARCHAR2(1000)	Yes	Offer description.
OFFER_CUST_DESC	VARCHAR2(1000)	Yes	The customer description of the offer.
LEVEL_CODE	NUMBER(2)	Yes	The level of the offer. Valid values are: 0 - Item, 1 - Transaction.
TYPE_CODE	NUMBER(2)	Yes	The type of the offer. Valid values are: 0 - Item Simple, 1 - Transaction Simple, 2 - Transaction Buy Get

**Table 2-15 (Cont.) PROMO\_OFFER\_OUT**

COLUMN	TYPE	NULLABLE	COMMENT
TEMPLATE_ID	NUMBER(2)	Yes	The template of the offer. Valid values are: 0 - Get Discount, 1 - Buy X Get Discount, 2 - Spend X Get Discount, 4 - Get Y For Discount
START_DATE	TIMESTAMP(6)	Yes	The start date and time of the offer.
END_DATE	TIMESTAMP(6)	Yes	The end date and time of the offer.
COMMENTS	VARCHAR2(4000)	Yes	The comments for the offer.
COUPON_CODE	VARCHAR2(160)	Yes	The coupon code for the offer.

**PROMO\_OFFER\_COND\_OUT****Table 2-16 PROMO\_OFFER\_COND\_OUT**

COLUMN	TYPE	NULLABLE	COMMENT
BDI_SEQ_ID	NUMBER	No	bdi internal column
BDI_APP_NAME	VARCHAR2(50)	No	bdi internal column
BDI_DATASET_TYPE	VARCHAR2(20)	Yes	bdi internal column
BDI_DATASET_ACTION	VARCHAR2(20)	Yes	bdi internal column
PROMO_OFFER_COND_ID	NUMBER(10)	No	The payload ID of the condition of a promotion offer.
PAYLOAD_ID	NUMBER(10)	No	The message payload ID.
PROMO_ID	NUMBER(10)	No	The promo ID.
OFFER_ID	NUMBER(10)	No	The offer ID.
COND_ID	NUMBER(15)	No	Condition ID.
BUY_SPEND_TYPE	NUMBER(1)		The buy spend type of the condition. Valid values are: 0 - Quantity, 1 - Amount
BUY_SPEND_VALUE	NUMBER(20, 4)	No	The buy spend value of the condition.
BUY_UOM	VARCHAR2(4)	Yes	The buy UOM of the condition.

**PROMO\_OFR\_REWARD\_OUT****Table 2-17 PROMO\_OFR\_REWARD\_OUT**

COLUMN	TYPE	NULLABLE	COMMENT
BDI_SEQ_ID	NUMBER	No	bdi internal column
BDI_APP_NAME	VARCHAR2(50)	No	bdi internal column
BDI_DATASET_TYPE	VARCHAR2(20)	Yes	bdi internal column
BDI_DATASET_ACTION	VARCHAR2(20)	Yes	bdi internal column
PROMO_OFR_REWARD_ID	NUMBER(10)	No	The payload ID of the reward of a promotion offer.
PAYLOAD_ID	NUMBER(10)	No	The message payload ID.
PROMO_ID	NUMBER(10)	No	The promo ID.
OFFER_ID	NUMBER(10)	No	The offer ID.

**Table 2-17 (Cont.) PROMO\_OFR\_REWARD\_OUT**

<b>COLUMN</b>	<b>TYPE</b>	<b>NULLABLE</b>	<b>COMMENT</b>
REWARD_ID	NUMBER(15)	No	Reward ID.
CHANGE_TYPE	NUMBER(1)	No	Type of change for the reward. Valid values: change by amount (1), change by percent (0), fixed price (2)
CHANGE_AMOUNT	NUMBER(20,4)	Yes	The change by amount or fixed price amount.
CHANGE_PERCENT	NUMBER(7,4)	Yes	Percentage value when change type is change by percent.
QTY_TO_DISC	NUMBER(7,4)	Yes	The quantity to discount.
QTY_TO_DISC_UOM	VARCHAR2(4)	Yes	UOM of the discount quantity.
APPLY_TO_IND	NUMBER(1)	No	The apply to indicator of the reward. Valid values: Regular only - 0; Clearance only - 1; Regular and Clearance - 2

**PROM\_OFR\_CND\_MRCH\_OUT****Table 2-18 PROM\_OFR\_CND\_MRCH\_OUT**

<b>COLUMN</b>	<b>TYPE</b>	<b>NULLABLE</b>	<b>COMMENT</b>
BDI_SEQ_ID	NUMBER	No	bdi internal column
BDI_APP_NAME	VARCHAR2(50)	No	bdi internal column
BDI_DATASET_TYPE	VARCHAR2(20)	Yes	bdi internal column
BDI_DATASET_ACTION	VARCHAR2(20)	Yes	bdi internal column
PROM_OFR_CND_MRCH_ID	NUMBER(10)	No	The payload ID of the condition of a promotion offer.
PAYLOAD_ID	NUMBER(10)	No	The message payload ID.
PROMO_ID	NUMBER(10)	No	The promo ID.
OFFER_ID	NUMBER(10)	No	The offer ID.
COND_ID	NUMBER(15)	No	Condition ID.
MERCH_LVL	NUMBER(2)	No	The merchandise level. Valid values are: 1 - Department; 2 - Class; 3 - Subclass; 4 - Parent Item; 5 - Parent/Diff Item; 6 - Transaction Item; 8 - All Departments
DEPT	NUMBER(4)	Yes	Department ID.
CLASS	NUMBER(4)	Yes	Class ID.
SUBCLASS	NUMBER(4)	Yes	Subclass ID.
ITEM	VARCHAR2(25)	Yes	Item.
DIFF_ID	VARCHAR2(10)	Yes	Differentiator ID.
EXCLUDE_IND	NUMBER(1)	No	The exclude indicator.

**PROMO\_OFFER\_LOC\_OUT****Table 2-19** *PROMO\_OFFER\_LOC\_OUT*

<b>COLUMN</b>	<b>TYPE</b>	<b>NULLABLE</b>	<b>COMMENT</b>
BDI_SEQ_ID	NUMBER	No	bdi internal column
BDI_APP_NAME	VARCHAR2(50)	No	bdi internal column
BDI_DATASET_TYPE	VARCHAR2(20)	Yes	bdi internal column
BDI_DATASET_ACTION	VARCHAR2(20)	Yes	bdi internal column
PROMO_OFFER_LOC_ID	NUMBER(10)	No	The payload ID of the location node associated with the promotion offer.
PAYLOAD_ID	NUMBER(10)	No	The message payload ID.
PROMO_ID	NUMBER(10)	No	The promo ID.
OFFER_ID	NUMBER(10)	No	The offer ID.
LOCATION	NUMBER(10)	Yes	Location for the offer.
EXCLUDE_IND	NUMBER(1)	No	The exclude indicator.

**PROMO\_OFR\_CANCEL\_OUT****Table 2-20** *PROMO\_OFR\_CANCEL\_OUT*

<b>COLUMN</b>	<b>TYPE</b>	<b>NULLABLE</b>	<b>COMMENT</b>
BDI_SEQ_ID	NUMBER	No	bdi internal column
BDI_APP_NAME	VARCHAR2(50)	No	bdi internal column
BDI_DATASET_TYPE	VARCHAR2(20)	Yes	bdi internal column
BDI_DATASET_ACTION	VARCHAR2(20)	Yes	bdi internal column
PROMO_OFR_CANCEL_ID	NUMBER(10)	No	The payload ID of the offer cancellation.
PAYLOAD_ID	NUMBER(10)	No	The message payload ID.
PROMO_ID	NUMBER(10)	No	The promo ID.
OFFER_ID	NUMBER(10)	No	The offer ID.
CANCEL_DATETIME	TIMESTAMP(6)	No	The date and time that the offer cancellation takes effect.

**PROM\_OFR\_CNCL\_ITM\_OUT****Table 2-21** *PROM\_OFR\_CNCL\_ITM\_OUT*

<b>COLUMN</b>	<b>TYPE</b>	<b>NULLABLE</b>	<b>COMMENT</b>
BDI_SEQ_ID	NUMBER	No	bdi internal column
BDI_APP_NAME	VARCHAR2(50)	No	bdi internal column
BDI_DATASET_TYPE	VARCHAR2(20)	Yes	bdi internal column
BDI_DATASET_ACTION	VARCHAR2(20)	Yes	bdi internal column
PROM_OFR_CNCL_ITM_ID	NUMBER(10)	No	The payload ID of the item cancellation from the offer.
PAYLOAD_ID	NUMBER(10)	No	The message payload ID.

**Table 2–21 (Cont.) PROM\_OFR\_CNCL\_ITM\_OUT**

COLUMN	TYPE	NULLABLE	COMMENT
PROMO_ID	NUMBER(10)	No	The promo ID.
OFFER_ID	NUMBER(10)	No	The offer ID.
REWARD_COND_IND	VARCHAR2(1)	No	The date and time that the offer cancellation takes effect.
COND_ID	NUMBER(15)	Yes	Condition ID.
REWARD_ID	NUMBER(15)	Yes	Reward ID.
MERCH_LVL	NUMBER(2)	No	The merchandise level. Valid values are: 1 - Department; 2 - Class; 3 - Subclass; 4 - Parent Item; 5 - Parent/Diff Item; 6 - Transaction Item; 8 - All Departments
DEPT	NUMBER(4)	Yes	Department ID.
CLASS	NUMBER(4)	Yes	Class ID.
SUBCLASS	NUMBER(4)	Yes	Subclass ID.
ITEM	VARCHAR2(25)	Yes	Item.
DIFF_ID	VARCHAR2(10)	Yes	Differentiator ID.
CANCEL_DATETIME	TIMESTAMP(6)	No	The date and time that the offer cancellation takes effect.

**PROM\_OFR\_CNCL\_LOC\_OUT****Table 2–22 PROM\_OFR\_CNCL\_LOC\_OUT**

COLUMN	TYPE	NULLABLE	COMMENT
BDI_SEQ_ID	NUMBER	No	bdi internal column
BDI_APP_NAME	VARCHAR2(50)	No	bdi internal column
BDI_DATASET_TYPE	VARCHAR2(20)	Yes	bdi internal column
BDI_DATASET_ACTION	VARCHAR2(20)	Yes	bdi internal column
PROM_OFR_CNCL_LOC_ID	NUMBER(10)	No	The payload ID of the location cancellation from the offer.
PAYLOAD_ID	NUMBER(10)	No	The message payload ID.
PROMO_ID	NUMBER(10)	No	The promo ID.
OFFER_ID	NUMBER(10)	No	The offer ID.
LOCATION	NUMBER(10)	Yes	Location cancelled from the offer.
CANCEL_DATETIME	TIMESTAMP(6)	No	The date and time that the offer cancellation takes effect.

**ClearanceInductionBatch (Clearance Induction Batch)****Table 2–23 ClearanceInductionBatch Details**

<b>Module Name</b>	ClearanceInductionBatch.sh
<b>Description</b>	Clearance bulk upload process
<b>Functional Area</b>	Clearance

**Table 2–23 (Cont.) ClearanceInductionBatch Details**

<b>Module Type</b>	Business Processing
<b>Module Technology</b>	Java
<b>Catalog ID</b>	
<b>Runtime Parameters</b>	<p>ClearanceInductionBatch.sh &lt;user alias&gt; &lt;incoming-dir-path&gt; &lt;Template_Key&gt; [filter_Str ]</p> <ol style="list-style-type: none"> <li>1. The first argument is the user alias name which mandatory and is mapped to an authorized user in the system.</li> <li>2. The second argument is the path where the induction input files are placed.</li> <li>3. Third argument is the name of the standard clearance template key. This is a mandatory argument.</li> <li>4. The fourth argument is an optional and when provided accepts the following values: <ol style="list-style-type: none"> <li>a. XML - indicates that the batch has to look for xml files in the given incoming-dir-path and process them.</li> <li>b. ZIP - This is the default value when nothing is provided. The process will look for zip files containing xml files and process them sequentially.</li> </ol> </li> </ol>

**Note: File naming standards**

XML file:

The file should have a prefix of CLIND. Ex: CLIND\_ABC-10.10.18.xml

The file should contain the data in the format suggested by standard clearance upload template.

ZIP file:

The file should have a prefix of CLIND. Ex: CLIND\_ABC.ZIP

The xml files with in the zip file should also have the prefix of CLIND.

**Design Overview**

The clearance induction batch process perform the necessary work to upload clearances in bulk. For the bulk upload, clearance data will be present in XML format with the data formatted in the standard clearance upload template. This batch accepts the clearance data present in XML format and also as zip files of xml files formatted in the standard template.

## Scheduling Constraints

**Table 2–24 ClearanceInductionBatch Scheduling Constraints**

Schedule Information	Description
Frequency	Ad hoc, Recurring
Scheduling Considerations	N/A
Pre-Processing	N/A
Post-Processing	N/A
Threading Scheme	N/A

## Restart/Recovery

N/A

## Key Tables Affected

**Table 2–25 ClearanceInductionBatch Key Tables Affected**

Table	Select	Insert	Update	Delete
S9T_TEMPLATE	Yes	No	No	No
SVC_PROCESS_TRACKER	Yes	Yes	Yes	No
S9T_ERRORS	Yes	Yes	No	No
RPM_CORESVC_CLEARANCE_ERR	Yes	Yes	No	No
RPM_SVC_CLEARANCE	Yes	Yes	Yes	No
RPM_CLEARANCE	Yes	Yes	Yes	Yes
RPM_CLEARANCE_GROUP	Yes	Yes	Yes	Yes

## Design Assumptions

N/A

## ClearancePriceChangePublishBatch (Clearance Price Change Publish Batch)

**Table 2–26 ClearancePriceChangePublishBatch Details**

Module Name	ClearancePriceChangePublishBatch.sh
Description	Clearance events are exported
Functional Area	Clearance
Module Type	Business Processing
Module Technology	Java
Catalog ID	
Runtime Parameters	ClearancePriceChangePublishBatch.sh <user_alias> <outgoing-dir-path>



## Design Overview

The ClearancePriceChangePublishBatch program formats and stages output of clearance price change price events.

The corresponding clearancePriceChangePublishExport shell script produces a pipe ("|") delimited flat-file export based on the output of the ClearancePriceChangePublishBatch.

The batch looks for price events in the RPM\_PRICE\_EVENT\_PAYLOAD table with a RIB\_FAMILY of 'ClrPrcChg' and distributes those events to multiple threads based on the settings in the RPM\_BATCH\_CONTROL table. Each thread reads in its set of clearance price change events from tables RPM\_PRICE\_EVENT\_PAYLOAD and RPM\_CLEARANCE\_PAYLOAD and generates output in RPM\_PRICE\_PUBLISH\_DATA. After the flat file is successfully generated by the Export script (see the following format), the associated records in the payload tables are deleted.

Then the flat-files per location based on the data from payload table that need to be published/processed will be created and zipped and copied to the outgoing-dir-path provided as a batch parameter.

## Scheduling Constraints

**Table 2–27 ClearancePriceChangePublishBatch Scheduling Constraints**

Schedule Information	Description
Frequency	Ad hoc, Recurring
Scheduling Considerations	N/A
Pre-Processing	N/A
Post-Processing	N/A
Threading Scheme	The ClearancePriceChangePublishBatch program is threaded, using RPM_BATCH_CONTROL. The LUW is a single clearance price change event.

## Restart/Recovery

N/A

## Key Tables Affected

**Table 2–28 ClearancePriceChangePublishBatch Key Tables Affected**

Table	Select	Insert	Update	Delete
RPM_PRICE_EVENT_PAYLOAD	Yes	No	No	No
RPM_CLEARANCE_PAYLOAD	Yes	No	No	No

## Output File

FHEAD - REQUIRED: File identification, one line per file.

FDETL - OPTIONAL: Price Change Event (Create or Modify).

FDELE - OPTIONAL: Price Change Event (Delete).

FTAIL - REQUIRED: End of file marker, one line per file.

**Note: File naming standards**

The naming convention for the flat file will be (CLRPC\_<timestamp>\_<location>\_<loc\_type>.dat), where <timestamp> is the current system time stamp, <location> is the location ID and <loc\_type> is the type of the location where 'S' is for Store and 'W' is for Warehouse. The zip file naming convention will be (CLRPC\_<timestamp>.zip).

**Output File Layout****Table 2–29 Output File Layout**

Record Name	Field Name	Field Type	Default Value	Description
FHEAD	Record Descriptor	Char(5)	FHEAD	File head marker
	Line ID	Number(10)	1	Unique line identification
	File Type	Char(5)	CLRPC	Clearance Price Changes
	Export timestamp	Timestamp		System clock timestamp (YYYYMMDDHHMISS)
	Location	Number(10)		Location identifier
	Location Type	Char(1)		S = Store, W = Warehouse
FDETL	Record Descriptor	Char(5)	FDETL	File Detail Marker (1 per clearance create or modify)
	Line ID	Number(10)		Unique line identification
	Event Type	Char(3)		CRE = Create, MOD = Modify
	Id	Number(15)		Clearance identifier
	Item	Char(25)		Item identifier
	Effective Date	Date		Clearance Effective Date (YYYYMMDDHH24MISS)
	Selling Retail	Number(20,4)		Selling retail with price change applied
	Selling Retail UOM	Char(4)		Selling retail unit of measure
	Selling Retail Currency	Char(3)		Selling retail currency
	Reset Clearance Id	Number(15)		Clearance reset identification
FDELE	Record Descriptor	Char(5)	FDELE	File Detail Delete Marker (1 per clearance delete)
	Line ID	Number(10)		Unique line identification
	Id	Number(15)		Clearance identifier
	Item	Char(25)		Item identifier
FTAIL	Record Descriptor	Char(5)	FTAIL	File tail marker
	Line ID	Number(10)		Unique line identification
	Number of lines	Number(10)		Number of lines in file not counting FHEAD and FTAIL

## Design Assumptions

N/A

## FutureRetailPurgeBatch Design

**Table 2–30 FutureRetailPurgeBatch Details**

<b>Module Name</b>	FutureRetailPurgeBatch.sh
<b>Description</b>	Purges future retail data that are past the retention period.
<b>Functional Area</b>	Future Retail
<b>Module Type</b>	Business Processing
<b>Module Technology</b>	Java
<b>Catalog ID</b>	
<b>Runtime Parameters</b>	futureRetailPurgeBatch.sh <user alias>

## Design Overview

This batch is a timed multi-threaded process that purges future retail data that are past the retention periods of their corresponding price events.

## Scheduling Constraints

**Table 2–31 FutureRetailPurgeBatch Scheduling Constraints**

<b>Schedule Information</b>	<b>Description</b>
Frequency	Ad hoc
Scheduling Considerations	This process must be executed during the batch window. As it runs, other processes must not access the future retail tables. This batch can be run ad-hoc.
Pre-Processing	N/A
Post-Processing	N/A
Threading Scheme	The batch uses bookmark logic to process merchandise hierarchies in a round robin fashion and running for a specific timeframe depending on the value of BATCH_TIME_LIMIT_HOURS in RPM_BATCH_CONTROL.

## Restart/Recovery

Restart/Recovery is inherent in the design of this program, as records are deleted after processing they would not be picked up if the program is run again.

## Key Tables Affected

**Table 2–32 FutureRetailPurgeBatch Key Tables Affected**

<b>Table</b>	<b>Select</b>	<b>Insert</b>	<b>Update</b>	<b>Delete</b>
RPM_FUTURE_RETAIL	Yes	No	No	Yes

## Design Assumptions

N/A

## FutureRetailRollUpBatch (Future Retail Roll Up Batch)

**Table 2–33 FutureRetailRollUpBatch Details**

<b>Module Name</b>	FutureRetailRollUpBatch.sh
<b>Description</b>	Attempts to roll up timelines on future retail if lower level timelines match higher levels.
<b>Functional Area</b>	Future Retail
<b>Module Type</b>	Business Processing
<b>Module Technology</b>	Java
<b>Catalog ID</b>	
<b>Runtime Parameters</b>	futureRetailRollUpBatch.sh <user alias>

## Design Overview

This batch attempts to roll up lower level timelines to existing higher level timelines (for example, from Item/Location to Parent/Location) by comparing two related timelines and removing the lower level timelines if the two match exactly for all records.

## Scheduling Constraints

**Table 2–34 FutureRetailRollUpBatch Scheduling Constraints**

Schedule Information	Description
Frequency	Ad hoc
Scheduling Considerations	This process must be executed during the batch window. As it runs, other processes must not access the future retail tables. This batch can be run ad-hoc.
Pre-Processing	N/A
Post-Processing	N/A
Threading Scheme	This batch is threaded by item.

## Restart/Recovery

The batch uses bookmark logic to process merchandise hierarchies in a round robin fashion and running for a specific timeframe depending on the value of BATCH\_TIME\_LIMIT\_HOURS in RPM\_BATCH\_CONTROL.

## Key Tables Affected

**Table 2–35 FutureRetailRollUpBatch Key Tables Affected**

Table	Select	Insert	Update	Delete
RPM_FUTURE_RETAIL	Yes	No	Yes	No

## Design Assumptions

N/A

## ItemReclassBatch (Item Reclass Batch)

**Table 2–36** *ItemReclassBatch Details*

<b>Module Name</b>	ItemReclassBatch.sh
<b>Description</b>	Updates Pricing tables when a merchandise hierarchy change is made in RMS.
<b>Functional Area</b>	Future Retail
<b>Module Type</b>	Business Processing
<b>Module Technology</b>	Java
<b>Catalog ID</b>	
<b>Runtime Parameters</b>	ItemReclassBatch.sh <user alias>

## Design Overview

When items are moved from one department/class/subclass to another in the merchandising system, this batch process accordingly sets the correct department/class/subclass for these items in the Future Retail table and the Pricing Item/Location table if the item has move departments.

## Scheduling Constraints

**Table 2–37** *ItemReclassBatch Scheduling Constraints*

Schedule Information	Description
Frequency	Ad hoc
Scheduling Considerations	Must be run during the batch window.
Pre-Processing	The RPM_ITEM_MODIFICATION table has been populated by the RMS reclassification batch process.
Post-Processing	N/A
Threading Scheme	N/A

## Restart/Recovery

N/A

## Key Tables Affected

**Table 2–38** *ItemReclassBatch Key Tables Affected*

Table	Select	Insert	Update	Delete
RPM_FUTURE_RETAIL	Yes	No	Yes	No
RPM_ITEM_MODIFICATION	Yes	No	No	No

## Design Assumptions

N/A

## NewItemLocationBatch (New Item Location Batch Batch)

**Table 2–39** *NewItemLocationBatch Details*

<b>Module Name</b>	ItemReclassBatch.sh
<b>Description</b>	Updates Pricing tables for new item/locations in RMS
<b>Functional Area</b>	Future Retail
<b>Module Type</b>	Business Processing
<b>Module Technology</b>	Java
<b>Catalog ID</b>	
<b>Runtime Parameters</b>	<p>NewItemLocationBatch.sh &lt;user alias&gt; [N / {E &lt;error commit count&gt;} / {R [&lt;process ID&gt;}}]</p> <p>Where</p> <p>The 'status' argument (N/E/R) is optional and directs the application as to what "status" to process. If it's not specified, the batch will default it to 'N'ew mode. The last argument can be optional or required depending upon the status argument as describe in the section below:</p> <p>Valid values for the status argument are:</p> <p>'N'ew: This will process records with status of N (New) from the staging table. When the batch is run in this mode, the last argument is not needed.</p> <p>'E'rror: This will process records with status of E (Error) from the staging table. When the batch is run in this mode, the batch can have the error commit count argument as an optional argument. Error commit count is optional and is used only when the status argument is 'E'. If not specified, the batch will use the logical unit of work for processing</p> <p>'R'estart: When the batch is run in this mode, then the process_id argument is required. This mode will only restart the rolling up functionality that is part of location move. It will call the RPM_NEW_ITEM_LOC_SQL.ROLLUP_NIL_DATA for the threads that are not in completed status in RPM_NIL_ROLLUP_THREAD. A required valid process ID parameter will also need to be passed in as well to indicate what process ID the batch should restart.</p>

## Design Overview

The NewItemLocationBatch program ranges item locations by putting them into the future retail table. Item locations are fed to this program via the RPM\_ITEM\_LOC\_WS table, which is populated by an RMS process.

## Scheduling Constraints

**Table 2–40** *NewItemLocationBatch Scheduling Constraints*

<b>Schedule Information</b>	<b>Description</b>
Frequency	Ad hoc
Scheduling Considerations	Must not have more than one instance running at a time.

**Table 2–40 (Cont.) NewItemLocationBatch Scheduling Constraints**

Schedule Information	Description
Pre-Processing	N/A
Post-Processing	N/A
Threading Scheme	<p>The NewItemLocationBatch is a multi-step and multi-threaded batch, meaning each of the two steps (inheritance process and rollup process) has its own independent threading. The first part, which is the insert to future retail and item loc tables and inheritance process, is threaded by related item-locations where "related" means transaction items under a single parent items and locations within a zone that is part of a primary zone group.</p> <p>If there are price events, then it chooses a path based on batch control settings similar to the ones for a price event approval from UI, and it chooses to go to chunking or bulking based on setting and the volume of data.</p>

## Restart/Recovery

### Processing Stage Rows in Error Status

This program is set up to re-process (re-attempt) rows that end up in error status. In the event that an error occurs during the processing of new status rows, the program should update the status on the stage table with E along with an error message. Once the error has been fixed, you can re-run this program with status E in an attempt to get the item/loc into Pricing.

### Processing Stage Rows in Restart Status

When running in Restart mode, the batch will attempt to re-process the future retail roll up functionality and to clean up item location staging tables. It will delete the records that were completely processed from the staging tables.

This mode has to be executed when there are threads/process ID that have errors or did not complete the roll-up process and clean-up of staging tables. This should be part of the business process. For example, clients can do this ad-hoc when no one is using the application. They also have to establish how they are going to retrieve process ID and threads that need reprocessing. If there won't be an established process for running NIL Batch in restart mode, the NIL thread status and staging tables data will increase and won't be cleaned up.

## Key Tables Affected

**Table 2–41 NewItemLocationBatch Key Tables Affected**

Table	Select	Insert	Update	Delete
RPM_FUTURE_RETAIL	Yes	No	Yes	No
RPM_ITEM_LOC	Yes	No	No	No
RPM_STAGE_ITEM_LOC	Yes	No	Yes	No

**Table 2–41 (Cont.) NewItemLocationBatch Key Tables Affected**

Table	Select	Insert	Update	Delete
RPM_STAGE_ITEM_LOC_CLEAN	Yes	No	No	No
RPM_NIL_ROLLUP_THREAD	Yes	No	Yes	No
RPM_NIL_BULKCCPE_PROCESS_ID	Yes	No	No	No

## Design Assumptions

N/A

## NightlyBatchCleanup (Nightly Cleanup Batch)

**Table 2–42 NightlyBatchCleanup Details**

Module Name	NightlyBatchCleanup.sh
Description	Nightly clean up on pricing tables
Functional Area	All
Module Type	Business Processing
Module Technology	Java
Catalog ID	
Runtime Parameters	NightlyBatchCleanupBatch.sh <user_alias> PRE/POST

## Design Overview

The nightlyBatchCleanup batch program performs "clean up" logic against certain database structures.

## Scheduling Constraints

**Table 2–43 NightlyBatchCleanup Scheduling Constraints**

Schedule Information	Description
Frequency	Nightly batch cycle
Scheduling Considerations	This batch should be run before the nightly batch window in "pre" mode and after the nightly batch window in "post" mode.
Pre-Processing	N/A
Post-Processing	N/A
Threading Scheme	N/A

## Restart/Recovery

N/A



## Key Tables Affected

**Table 2–44 NightlyBatchCleanup Key Tables Affected**

Table	Select	Insert	Update	Delete
S9T_TEMPLATE	Yes	No	No	No
SVC_PROCESS_TRACKER	Yes	No	No	No
S9T_ERRORS	Yes	Yes	Yes	No
RPM_CORESVC_PRICE_CHANGE_ERR	Yes	No	No	No
RPM_SVC_PRICE_CHANGE	Yes	No	Yes	No
RPM_PRICE_CHANGE	Yes	No	No	No
RPM_PRICE_CHANGE_GROUP	No	Yes	No	No

## Design Assumptions

N/A

## PriceChangeInductionBatch (Price Change Induction Batch)

**Table 2–45 PriceChangeInductionBatch Details**

<b>Module Name</b>	PriceChangeInductionBatch.sh
<b>Description</b>	Price Change bulk upload process
<b>Functional Area</b>	Price Change
<b>Module Type</b>	Business Processing
<b>Module Technology</b>	Java
<b>Catalog ID</b>	
<b>Runtime Parameters</b>	<p>PriceChangeInductionBatch .sh &lt;user alias&gt; &lt;incoming-dir-path&gt; &lt;Template_Key&gt; [filter_Str ]</p> <ol style="list-style-type: none"> <li>1. The first argument is the user alias name which mandatory and is mapped to an authorized user in the system.</li> <li>2. The second argument is the path where the induction input files are placed.</li> <li>3. Third argument is the name of the standard price change template key. This is a mandatory argument.</li> <li>4. The fourth argument is an optional and when provided accepts the following values: <ol style="list-style-type: none"> <li>a. XML - indicates that the batch has to look for xml files in the given incoming-dir-path and process them.</li> <li>b. ZIP - This is the default value when nothing is provided. The process will look for zip files containing xml files and process them sequentially.</li> </ol> </li> </ol>

**Note: File naming standards**

XML file:

The file should have a prefix of PCIND. Ex: PCIND\_ABC-10.10.18.xml

The file should contain the data in the format suggested by standard price change upload template.

ZIP file:

The file should have a prefix of PCIND. Ex: PCIND\_ABC.ZIP

The xml files with in the zip file should also have the prefix of PCIND

**Design Overview**

PriceChangeInductionBatch uploads regular price changes in bulk. For the bulk upload, price change data will be present in XML format with the data formatted in the standard price change upload template. This batch accepts the price change data present in XML format and also as zip files of xml files formatted in the standard template.

**Scheduling Constraints****Table 2–46 PriceChangeInductionBatch Scheduling Constraints**

Schedule Information	Description
Frequency	Ad hoc, Recurring
Scheduling Considerations	N/A
Pre-Processing	N/A
Post-Processing	N/A
Threading Scheme	N/A

**Restart/Recovery**

N/A

**Key Tables Affected****Table 2–47 PriceChangeInductionBatch Key Tables Affected**

Table	Select	Insert	Update	Delete
S9T_TEMPLATE	Yes	No	No	No
SVC_PROCESS_TRACKER	Yes	Yes	Yes	No
S9T_ERRORS	Yes	Yes	No	No
RPM_CORESVC_PRICE_CHANGE_ERR	Yes	No	No	No
RPM_SVC_PRICE_CHANGE	Yes	No	Yes	No
RPM_PRICE_CHANGE	Yes	No	No	No
RPM_PRICE_CHANGE_GROUP	No	Yes	No	No

## Design Assumptions

N/A

## PriceEventExecutionBatch (Price Event Execution Batch)

**Table 2–48 PriceEventExecutionBatch Details**

<b>Module Name</b>	PriceEventExecution.sh
<b>Description</b>	Starts events that need to be executed on a given date.
<b>Functional Area</b>	Price Change
<b>Module Type</b>	Business Processing
<b>Module Technology</b>	Java
<b>Catalog ID</b>	
<b>Runtime Parameters</b>	<p><b>PriceEventExecutionBatch.sh &lt;user_alias&gt; [restartInd Y N]</b></p> <p>Where the last argument of the PriceEventExecutionBatch indicates if the run should start over (use a value of N) or pick up where the previous run left off (use a value of Y).</p>

## Design Overview

The price event execution batch process performs the necessary work to start (regular price change and clearance price change) and end (reset) clearance pricing events.

The batch programs process regular price change and clearance price change events that are scheduled for the run date. Restartability features allow events missed in past runs of the batch to be picked up in later runs. When posting information in the ITEM\_LOC and PRICE\_HIST table, the batch process respects the active dates of their associated price events.

Clearances

- Clearance markdowns that are scheduled to take place are executed. These include all clearances whose effective dates are  $\leq$  VDATE+1.
- Clearances that are scheduled to be completed (reset) are completed.

Regular price changes

- Regular price changes that are scheduled to take place are executed. These include all price changes whose effective dates are  $\leq$  VDATE+1.

## Scheduling Constraints

**Table 2–49 PriceEventExecutionBatch Scheduling Constraints**

<b>Schedule Information</b>	<b>Description</b>
Frequency	Ad hoc, Recurring
Scheduling Considerations	Salstage (Merchandising) should run before Price Event Execution. Price Event Execution should run before the Storadd (Merchandising) batch.

**Table 2–49 (Cont.) PriceEventExecutionBatch Scheduling Constraints**

Schedule Information	Description
Pre-Processing	N/A
Post-Processing	N/A
Threading Scheme	N/A

## Restart/Recovery

The program is restartable and will pick up any events remaining to be processed in a given run.

## Key Tables Affected

**Table 2–50 PriceEventExecutionBatch Key Tables Affected**

Table	Select	Insert	Update	Delete
RPM_PRICE_CHANGE	Yes	No	Yes	No
RPM_CLEARANCE	Yes	No	Yes	No
ITEM_LOC	Yes	No	Yes	No
PRICE_HIST	Yes	Yes	No	No
TRAN_DATA	Yes	Yes	No	No

## Design Assumptions

N/A

## PriceEventExecutionForChunkCCEmergencyEvents Batch Design

The priceEventExecutionForChunkCCEmergencyEvents process performs the necessary work to start and end Emergency Price Events that are processed through chunk conflict checking. For more details on chunk conflict checking, see the ProcessPendingChunkBatch batch design.

### Usage

The following command runs the priceEventExecutionForChunkCCEmergencyEvents job:

```
priceEventExecutionForChunkCCEmergencyEvents.sh userAlias
```

### Detail

The priceEventExecutionForChunkCCEmergencyEvents batch program process Emergency regular price changes and clearance price changes that are scheduled to run on vdate or less than vdate. All processes for the emergency batch are similar to the priceEventExecutionBatch in the above that it is also update Merchandising tables in one batch. It is calling the same function with different parameter so that the system knows to process an Emergency Price Events or Non-Emergency Price Events.

### Primary Tables Involved

- RPM\_CHUNK\_CC\_STAGE\_PEE
- RPM\_PRICE\_CHANGE

- RPM\_CLEARANCE

### Threading

The threading for priceEventExecutionForChunkCCEmergencyEvents batch is similar to the priceEventExecutionBatch. It utilizes concurrent processing and is threaded by a number of item-locations affected by the pricing events to be executed. For more detail, please see the PriceEventExecutionBatch process in the Threading section.

## ProcessPendingChunkBatch Batch Design

Pricing can utilize chunk processing for conflict checking of price events, to optimize performance for large events.

To determine if a price event should be processed through chunking, there is a row on the RPM\_BATCH\_CONTROL table with PROGRAM\_NAME column equal to "Bulk Conflict Check App Service".

- The value of the THREAD\_LUW\_COUNT column of a row on the RPM\_BATCH\_CONTROL table with PROGRAM\_NAME column equal to "Bulk Conflict Check App Service".

The conflict checking process utilizes chunking if the number of item/locations for a price event is greater than or equal to the THREAD\_LUW\_COUNT times a factor of 2.5.

Pricing then uses the value of the THREAD\_LUW\_COUNT column of a row on the RPM\_BATCH\_CONTROL table with PROGRAM\_NAME column equal to "Bulk Conflict Check App Service" as the chunk size. If this is NULL, the chunk size will be 10,000.

---

**Example:** This can be best illustrated by considering a price change set up for a style with 10,000 items and a zone with five locations.

The above mentioned bulk conflict checking process would be able to have only one thread that could process all 50,000 item/locations involved with one price event as suggested above. By chunking those 50,000 item/locations into smaller groupings, multiple threads can be utilized to execute the conflict checking process.

---

The ProcessPendingChunkBatch program attempts to reprocess push-back logic for threads that encountered errors in chunk conflict checking.

### Usage

The following command runs the ProcessPendingChunkBatch job:

```
ProcessPendingChunkBatch.sh userAlias
```

### Details

The batch looks for any push-back threads that completed with error and any price events that encountered errors in the post-push-back logic and attempts to reprocess them using the same logic that is used during the regular conflict checking processing.

### Assumptions and Scheduling Notes

The ProcessPendingChunkBatch process can be run ad-hoc - the event of a price event moving to a pending status triggering the need to run this batch. Prior to running this

batch, a DBA needs to verify what issues were encountered that caused a price event to be moved to a pending status (issues like unable to extend table space). These issues need to be rectified prior to running this batch. If no action is taken to resolve these issues, the batch will likely encounter the same issues and the price events will be left in a pending status.

### Primary Tables Involved

- RPM\_BULK\_CC\_PE\_CHUNK
- RPM\_BULK\_CC\_PE\_THREAD
- RPM\_FUTURE\_RETAIL\_WS
- RPM\_FUTURE\_RETAIL

### Threading

The ProcessPendingChunkBatch program is threaded in that it will reuse the same threading logic used by the conflict checking engine when attempting to reprocess push-back threads.

## PromotionInductionBatch (Promotion Induction Batch)

**Table 2–51 PromotionInductionBatch Details**

<b>Module Name</b>	PromotionInductionBatch.sh
<b>Description</b>	Promotion bulk upload process
<b>Functional Area</b>	Promotion
<b>Module Type</b>	Business Processing
<b>Module Technology</b>	Java
<b>Catalog ID</b>	
<b>Runtime Parameters</b>	<p>PromotionInductionBatch.sh &lt;user alias&gt; &lt;incoming-dir-path&gt; &lt;Template_Key&gt; [filter_Str]</p> <ol style="list-style-type: none"><li>1. The first argument is the user alias name which mandatory and is mapped to an authorized user in the system.</li><li>2. The second argument is the path where the induction input file(s) are located. It can be a file or a directory.</li><li>3. Third argument is the name of a promotion template key. This is a mandatory argument.</li><li>4. The fourth argument is an optional and when provided accepts the following values:<ul style="list-style-type: none"><li>■ XML - indicates that the batch has to look for xml files in the given incom-ing-dir-path and process them.</li><li>■ ZIP - This is the default value when nothing is provided. The process will look for zip files containing xml files and process them.</li></ul></li></ol>

---

**Note: File naming standards**

XML file:

The files should have a prefix of PMIND. Files without this prefix are ignored. Ex: PMIND\_ABC-10.10.18.xml

The file should contain the data in the format suggested by the given promotion upload template key argument.

ZIP file:

The file should have a prefix of PMIND. Files without this prefix are ignored. Ex: PMIND\_ABC.zip

The xml files with in the zip file should also have the prefix of PMIND otherwise they will be ignored.

## Design Overview

The promotion induction batch process perform the necessary work to upload promotions in bulk. For the bulk upload, promotion data will be present in XML format with the data formatted in a promotion upload template matching the given template key argument. This batch accepts the promotion data present in XML format and also as zip files of xml files.

## Scheduling Constraints

**Table 2–52 PromotionInductionBatch Scheduling Constraints**

Schedule Information	Description
Frequency	Ad hoc, Recurring
Scheduling Considerations	N/A
Pre-Processing	N/A
Post-Processing	N/A
Threading Scheme	N/A

## Key Tables Affected

**Table 2–53 PromotionInductionBatch Key Tables Affected**

Table	Select	Insert	Update	Delete
S9T_TEMPLATE	Yes	No	No	No
SVC_PROCESS_TRACKER	Yes	Yes	Yes	No
S9T_ERRORS	Yes	Yes	No	No
RPM_CORESVC_PROMO_ERR	Yes	Yes	No	No
RPM_SVC_PROMO	Yes	Yes	Yes	No
RPM_SVC_PROMO_OFFER	Yes	Yes	Yes	No
RPM_SVC_PROMO_OFFER_COND	Yes	Yes	Yes	No

**Table 2–53 (Cont.) PromotionInductionBatch Key Tables Affected**

Table	Select	Insert	Update	Delete
RPM_SVC_PROMO_OFFER_COND_MERCH	Yes	Yes	Yes	No
RPM_SVC_PROMO_OFFER_RWD	Yes	Yes	Yes	No
RPM_SVC_PROMO_OFFER_RWD_MERCH	Yes	Yes	Yes	No
RPM_SVC_PROMO_OFFER_ZONE_LOC	Yes	Yes	Yes	No
RPM_PROMO	Yes	Yes	Yes	Yes
RPM_PROMO_OFFER	Yes	Yes	Yes	Yes
RPM_PROMO_OFFER_COND	Yes	Yes	Yes	Yes
RPM_PROMO_OFFER_COND_MERCH	Yes	Yes	Yes	Yes
RPM_PROMO_OFFER_REWARD	Yes	Yes	Yes	Yes
RPM_PROMO_OFFER_REWARD_MERCH	Yes	Yes	Yes	Yes
RPM_PROMO_OFFER_ZONE_LOC	Yes	Yes	Yes	Yes

## Purge Batch (PurgeBatch)

Here are the steps in the purge process:

- Delete items and item/locations which were already deleted in the merchandising system from the pricing system.
- Delete price changes which are in worksheet, rejected, or submitted status with an effective date beyond the reject hold days.
- Remove price changes with effective dates beyond the price change history months retention setting. This is completed by dropping partitions which meet the date criteria.
- Delete clearances which are in worksheet, rejected, or submitted status with an effective date beyond the reject hold days.
- Remove clearances with effective dates beyond the clearance history months retention setting. This is completed by dropping partitions which meet the date criteria.
- Delete all but the most recent zone future retail entry with an effective date before vdate.
- Delete price change induction data for successful upload processes and those with an action date beyond the process retention days.
- Delete clearance induction data for successful upload processes and those with an action date beyond the process retention days.
- Delete published payload data from price changes, clearances, and promotions that is older than 7 days.
- Truncate all the Bulk CC processing tables.



- Delete conflict check error results for price changes and clearances which no longer exist.
- Truncate all UI, item creation, and item/location ranging workspace tables.

## System Options

System options used for purge configuration:

- RPM\_PURGE\_CONFIG\_OPTIONS.PRICE\_EVENTS\_REJECT\_HOLD\_DAYS
- RPM\_PURGE\_CONFIG\_OPTIONS.PRICE\_CHANGE\_HIST\_MONTHS
- RPM\_PURGE\_CONFIG\_OPTIONS.CLEARANCE\_HIST\_MONTHS
- SYSTEM\_OPTIONS.PROC\_DATA\_RETENTION\_DAYS

## Usage

```
PurgeBatch.sh <user_alias>PurgeBatch.sh <user_alias> <export_purge
ALL/BDI/FLAT_FILE>
```

Where ALL is used if the customer is using both BDI integration and flat file integration, BDI for BDI only, or FLAT\_FILE for flat file only.

## Scheduling Constraints

**Table 2–54** *PurgeBatch Scheduling Constraints*

Schedule Information	Description
Frequency	Nightly
Scheduling Considerations	not applicable
Pre-Processing	not applicable
Post-Processing	not applicable
Threading Scheme	not applicable

## Restart/Recovery

N/A

## Key Tables Affected

**Table 2–55** *PurgeGTTCaptureBatch Key Tables Affected*

Table	Select	Insert	Update	Delete
RPM_ZONE_FUTURE_RETAIL	Yes	No	No	Yes
RPM_ITEM_LOC	Yes	No	No	Yes
RPM_ZONE_LOCATION	Yes	No	No	Yes
RPM_ITEM_ZONE_PRICE	Yes	No	No	Yes
RPM_PRICE_CHANGE	Yes	No	No	Yes
RPM_CLEARANCE	Yes	No	No	Yes
RPM_STAGE_DELETED_ITEM_MASTER	Yes	No	No	Yes

**Table 2–55 (Cont.) PurgeGTTCaptureBatch Key Tables Affected**

<b>Table</b>	<b>Select</b>	<b>Insert</b>	<b>Update</b>	<b>Delete</b>
RPM_STAGE_DELETED_ITEM_LO	Yes	No	No	Yes
RPM_PRICE_CHANGE	Yes	No	No	Yes
RPM_PRICE_CHANGE_GROUP	Yes	No	No	Yes
RPM_CLEARANCE	Yes	No	No	Yes
RPM_CLEARANCE_GROUP	Yes	No	No	Yes
RPM_ZONE_FUTURE_RETAIL	Yes	No	No	Yes
SVC_PROCESS_TRACKER	Yes	No	No	Yes
S9T_FOLDER	Yes	No	No	Yes
S9T_ERRORS	Yes	No	No	Yes
RPM_SVC_PRICE_CHANGE	Yes	No	No	Yes
RPM_CORESVC_PRICE_CHANGE_ERR	Yes	No	No	Yes
SVC_PROCESS_TRACKER	Yes	No	No	Yes
S9T_FOLDER	Yes	No	No	Yes
S9T_ERRORS	Yes	No	No	Yes
RPM_SVC_CLEARANCE	Yes	No	No	Yes
RPM_CORESVC_CLEARANCE_ERR	Yes	No	No	Yes
RPM_PROMO_OFFER_CANCEL_PAYLOAD	Yes	No	No	Yes
RPM_PROM_OFR_CNCL_LOC_PAYLOAD	Yes	No	No	Yes
RPM_PROM_OFR_CNCL_ITEM_PAYLOAD	Yes	No	No	Yes
RPM_PROMO_OFFER_LOC_PAYLOAD	Yes	No	No	Yes
RPM_PROMO_OFR_RWD_MRCH_PAYLOAD	Yes	No	No	Yes
RPM_PROMO_OFR_CND_MRCH_PAYLOAD	Yes	No	No	Yes
RPM_PROMO_OFFER_PAYLOAD	Yes	No	No	Yes
RPM_PRICE_CHG_PAYLOAD	Yes	No	No	Yes
RPM_CLEARANCE_PAYLOAD	Yes	No	No	Yes
RPM_PRICE_EVENT_PAYLOAD	Yes	No	No	Yes
RPM_BULK_CC_PE_ITEM	Yes	No	No	Yes
RPM_BULK_CC_PE_LOCATION	Yes	No	No	Yes
RPM_BULK_CC_PE_CHUNK	Yes	No	No	Yes
RPM_BULK_CC_PE_THREAD	Yes	No	No	Yes
RPM_BULK_CC_PE_SEQUENCE	Yes	No	No	Yes

**Table 2–55 (Cont.) PurgeGTTCCaptureBatch Key Tables Affected**

<b>Table</b>	<b>Select</b>	<b>Insert</b>	<b>Update</b>	<b>Delete</b>
RPM_BULK_CC_PE	Yes	No	No	Yes
RPM_PE_CC_LOCK	Yes	No	No	Yes
RPM_CONFLICT_CHECK_RESULT	Yes	No	No	Yes
RPM_CON_CHECK_ERR	Yes	No	No	Yes
RPM_CON_CHECK_ERR_DETAIL	Yes	No	No	Yes
RPM_PC_MAINT_LOC_WS	Yes	No	No	Yes
RPM_PC_MAINT_ITEM_WS	Yes	No	No	Yes
RPM_PC_MAINT_WS	Yes	No	No	Yes
RPM_PC_GROUP_SEARCH_WS	Yes	No	No	Yes
RPM_CLR_MAINT_LOC_WS	Yes	No	No	Yes
RPM_CLR_MAINT_ITEM_WS	Yes	No	No	Yes
RPM_CLR_MAINT_WS	Yes	No	No	Yes
RPM_CLR_GROUP_SEARCH_WS	Yes	No	No	Yes
RPM_OFFER_ZONE_LOC_WS	Yes	No	No	Yes
RPM_OFFER_CON_RWD_MERCH_WS	Yes	No	No	Yes
RPM_OFFER_REWARD_WS	Yes	No	No	Yes
RPM_OFFER_COND_WS	Yes	No	No	Yes
RPM_OFFER_WS	Yes	No	No	Yes
RPM_PROMO_WS	Yes	No	No	Yes
RPM_PROMO_OFFER_SEARCH_WS	Yes	No	No	Yes
RPM_PROMO_CANCEL_MERCH_WS	Yes	No	No	Yes
RPM_PROMO_CANCEL_ZONE_NODE_WS	Yes	No	No	Yes
RPM_PROMO_OFFER_PUB_WS	Yes	No	No	Yes
RPM_PE_CREATE_ITEM_WS	Yes	No	No	Yes
RPM_PE_CREATE_LOC_WS	Yes	No	No	Yes
RPM_PE_CREATE_WS	Yes	No	No	Yes
RPM_PE_CREATE_SUMMARY_WS	Yes	No	No	Yes
RPM_OI_PC_PEND_APPRV_EOW	Yes	No	No	Yes
RPM_OI_PC_PEND_APPRV_DAY	Yes	No	No	Yes
RPM_OI_CLR_PEND_APPRV_EOW	Yes	No	No	Yes

**Table 2–55 (Cont.) PurgeGTTCaptureBatch Key Tables Affected**

Table	Select	Insert	Update	Delete
RPM_OI_CLR_PEND_APPRV_DAY	Yes	No	No	Yes
RPM_OI_UPCOMING_OFFER_WS	Yes	No	No	Yes
RPM_ROWID_TEMP	Yes	No	No	Yes
RPM_STAGE_ITEM_LOC_RETAIL_TEMP	Yes	No	No	Yes

## PurgeGTTCaptureBatch (Purge GTT Capture Batch)

**Table 2–56 PurgeGTTCaptureBatch Details**

Module Name	PurgeGttCaptureBatch.sh
Description	Truncates data from the GTT capture related tables.
Functional Area	Various
Module Type	Business Processing
Module Technology	Java
Catalog ID	
Runtime Parameters	<b>PurgeGttCaptureBatch.sh</b> <user_alias>

### Design Overview

This batch truncates data from the GTT capture related tables.

### Scheduling Constraints

**Table 2–57 PurgeGTTCaptureBatch Scheduling Constraints**

Schedule Information	Description
Frequency	Ad hoc
Scheduling Considerations	Should be run during batch window.
Pre-Processing	N/A
Post-Processing	N/A
Threading Scheme	N/A

### Restart/Recovery

N/A

## Key Tables Affected

**Table 2–58 PurgeGTTCaptureBatch Key Tables Affected**

Table	Select	Insert	Update	Delete
RPM_RFR_GTT_DATA_CAPTURE	Yes	No	No	No
RPM_RPILE_GTT_DATA_CAPTURE	Yes	No	No	No
RPM_CSPFR_GTT_DATA_CAPTURE	Yes	Yes	Yes	No
RPM_CLR_GTT_DATA_CAPTURE	Yes	No	No	No
RPM_FRILE_GTT_DATA_CAPTURE	Yes	No	Yes	No

## Design Assumptions

N/A

## RegularPriceChangePublishBatch (Regular Price Change Publish Batch)

**Table 2–59 RegularPriceChangePublishBatch Details**

Module Name	RegularPriceChangePublishBatch.sh
Description	Price Change events are exported for integration to other systems.
Functional Area	Price Changes
Module Type	Business Processing
Module Technology	Java
Catalog ID	
Runtime Parameters	<b>RegularPriceChangePublishBatch.sh &lt;user_alias&gt; &lt;outgoing-dir-path&gt;</b>

## Design Overview

The RegularPriceChangePublishBatch program formats and stages output of regular price change price events.

The corresponding regularPriceChangePublishExport shell script produces a pipe ("|") delimited flat-file export based on the output of the RegularPriceChangePublishBatch.

The batch looks for price events in the RPM\_PRICE\_EVENT\_PAYLOAD table with a RIB\_FAMILY of "REGPRCCHG" and distributes those events to multiple threads based on the settings in the RPM\_BATCH\_CONTROL table. Each thread reads in its set of regular price change events from tables RPM\_PRICE\_EVENT\_PAYLOAD and RPM\_PRICE\_CHG\_PAYLOAD and generates output in RPM\_PRICE\_PUBLISH\_DATA.

A flat-file per location based on the data from payload table that need to be published/processed will be created. The naming convention for the flat file will be (REGPC\_<timestamp>\_<location>\_<loc\_type>.dat), where <timestamp> is the

current system time stamp, <location> is the location ID and <loc\_type> is the type of the location where 'S' is for Store and 'W' is for Warehouse.

## Scheduling Constraints

**Table 2–60 RegularPriceChangePublishBatch Scheduling Constraints**

Schedule Information	Description
Frequency	Ad hoc, Recurring
Scheduling Considerations	N/A
Pre-Processing	N/A
Post-Processing	N/A
Threading Scheme	The RegularPriceChangePublishBatch program is threaded, using RPM_BATCH_CONTROL. The LUW is a single price change event.

## Restart/Recovery

N/A

## Key Tables Affected

**Table 2–61 RegularPriceChangePublishBatch Key Tables Affected**

Table	Select	Insert	Update	Delete
RPM_PRICE_EVENT_PAYLOAD	Yes	No	No	No
RPM_PRICE_CHG_PAYLOAD	Yes	No	No	No

## Output Files

FHEAD (required): File identification, one line per file.

FDETL (optional): Price Change Event (Create or Modify).

FDELE (optional): Price Change Event (Delete).

FTAIL (required): End of file marker, one line per file.

---



---

### **Note:** File naming standards

The naming convention for the flat file will be (REGPC\_<timestamp>\_<location>\_<loc\_type>.dat), where <timestamp> is the current system time stamp, <location> is the location ID and <loc\_type> is the type of the location where 'S' is for Store and 'W' is for Warehouse. The zip file naming convention will be (REGPC\_<timestamp>.zip).

---



---

## Output File Layout

**Table 2–62 Output File Layout**

Record Name	Field Name	Field Type	Default Value	Description
FHEAD	Record Descriptor	Char(5)	FHEAD	File head marker
	Line ID	Number(10)	1	Unique line identifier
	File Type	Char(5)	REGPC	Regular Price Changes
	Export timestamp	Timestamp		System clock timestamp (YYYYMMDDHHMISS)
	Location	Number(10)		Location identifier
	Location Type	Char(1)		S = Store, W = Warehouse
FDETL	Record Descriptor	Char(5)	FDETL	File Detail Marker (1 per price change create or modify)
	Line ID	Number(10)		Unique line identifier
	Event Type	Char(3)		CRE = Create, MOD = Modify
	Id	Number(15)		Price Change identifier
	Item	Char(25)		Item identifier
	Effective Date	Date		Effective Date of price change (YYYYMMDDHH24MISS)
	Selling Unit Change Ind	Number(1)		Did selling unit retail change with this price event (0 = no change, 1 = changed)
	Selling Retail	Number(20,4)		Selling retail with price change applied
	Selling Retail UOM	Char(4)		Selling retail unit of measure
	Selling Retail Currency	Char(3)		Selling retail currency
	Multi-Unit Change Ind	Number(1)		Did multi-unit retail change with this price event (0 = no change, 1 = changed)
	Multi-Units	Number(12,4)		Number of multi-units
		Multi-Unit Retail	Number(20,4)	
Multi-Unit UOM		Char(4)		Multi-Unit Retail Unit Of Measure
Multi-Unit Currency		Char(3)		Multi-Unit Retail Currency
FDELE	Record Descriptor	Char(5)	FDELE	File Detail Delete Marker (1 per price change delete)
	Line ID	Number(10)		Unique line identifier
	Id	Number(15)		Price Change identifier
	Item	Char(25)		Item identifier

**Table 2–62 (Cont.) Output File Layout**

<b>Record Name</b>	<b>Field Name</b>	<b>Field Type</b>	<b>Default Value</b>	<b>Description</b>
FTAIL	Record Descriptor	Char(5)	FTAIL	File tail marker
	Line ID	Number(10)		Unique line identifier
	Number of lines	Number(10)		Number of lines in file not counting FHEAD and FTAIL

**Design Assumptions**

N/A



---

---

## ReST Services

This chapter describes ReST services available in Pricing.

### Price Inquiry

#### Business Overview

This service provides the ability to query the selling price of item/locations for a given date.

#### Service Type

POST

#### REST URL

/priceInquiry

#### Roles Allowed

PRICING\_APPLICATION\_ADMINISTRATOR\_JOB, PRICING\_DATA\_STEWARD\_JOB, PRICING\_MANAGER\_JOB, PRICING\_ANALYST\_JOB, PROMOTION\_MANAGER\_JOB, PROMOTION\_PLANNER\_JOB

#### Request Headers

```
Accept: <application/json or application/xml>
Accept-Language: <locale>
Accept-Version: <application_version>
Content-Type: <application/json or application/xml>
```

For Example:

```
Accept: application/json
Accept-Language: en-US
Accept-Version: 19.0
Content-Type: application/json
```

#### URL Query Parameters

N/A

## Request Body

```
{
  "itemLocations": [
    {
      "item": null,
      "location": null
    }, ... (Possible list, comma separated for multiple)
  ],
  "date": null,
  "pageNumber": null,
  "pageSize": null,
  "sortOrder": null
}
```

Entity	Key	Type	Value
price inquiry	itemLocations	entity list	Item locations for inquiry
price inquiry	date	varchar	Date in the format YYYY-MM-DD
price inquiry	pageNumber	numeric	Page number to return
price inquiry	pageSize	numeric	Total number of results per page
price inquiry	sortOrder	varchar	ASC (ascending) or DESC (descending)
item location	item	varchar	Item ID (parent, transaction, or reference)
item location	location	numeric	Location ID (store or virtual warehouse)

## Response Body

```
[
  {
    "requestedItem": null,
    "transactionItem": null,
    "location": null,
    "date": null,
    "onClearance": null,
    "sellingPrice": null,
    "sellingUom": null,
    "currency": null
  }
]
```

Entity	Key	Type	Value
price	requestedItem	varchar	Item ID (parent, transaction, or reference)
price	transactionItem	varchar	Transaction Item ID
price	location	numeric	Location ID (store or virtual warehouse)
price	date	varchar	Date in the format YYYY-MM-DD
price	onClearance	varchar	Y (yes) or N (no)
price	sellingPrice	numeric	Decimal selling price
price	sellingUom	varchar	Selling unit of measure
price	currency	varchar	Location's currency

# Initial Retail

## Business Overview

This service provides the ability to query the initial retail of an item/location.

## Service Type

GET

## REST URL

/initialRetail?item=<item>&location=<location>

## Roles Allowed

PRICING\_APPLICATION\_ADMINISTRATOR\_JOB, PRICING\_DATA\_STEWARD\_JOB, PRICING\_MANAGER\_JOB, PRICING\_ANALYST\_JOB, PROMOTION\_MANAGER\_JOB, PROMOTION\_PLANNER\_JOB

## Request Headers

```

    Accept: <application/json or application/xml>
  Accept-Language: <locale>
  Accept-Version: <application_version>
  Content-Type: <application/json or application/xml>

```

For Example:

```

    Accept: application/json
  Accept-Language: en-US
  Accept-Version: 19.0
  Content-Type: application/json

```

## URL Query Parameters

Key	Type	Value
item	varchar	Item ID (transaction or reference)
location	numeric	Location ID (store or virtual warehouse)

## Request Body

N/A

## Response Body

```

[
  {
    "item": null,
    "location": null,
    "currentDate": null,
    "onClearance": null,
  }
]

```

```

    "sellingPrice": null,
    "sellingUom": null,
    "currency": null
  }
}

```

Entity	Key	Type	Value
price	item	varchar	Item ID (transaction or reference)
price	location	numeric	Location ID (store or virtual warehouse)
price	currentDate	varchar	Date in the format YYYY-MM-DD
price	onClearance	varchar	Y (yes) or N (no)
price	sellingPrice	numeric	Decimal selling price
price	sellingUom	varchar	Selling unit of measure
price	currency	varchar	Location's currency

## Price Change Induction

### Business Overview

This service provides the ability to create, modify, and delete price changes via the induction process.

### Service Type

POST

### REST URL

/priceChange/induction

### Roles Allowed

PRICING\_APPLICATION\_ADMINISTRATOR\_JOB, PRICING\_MANAGER\_JOB,  
PRICING\_DATA\_STEWARD\_JOB

### Request Headers

```

    Accept: <application/json or application/xml>
Accept-Language: <locale>
Accept-Version: <application_version>
Content-Type: <application/json or application/xml>

```

For Example:

```

    Accept: application/json
Accept-Language: en-US
Accept-Version: 19.0
Content-Type: application/json

```

## URL Query Parameters

N/A

## Request Body

```
[
  {
    "action": null,
    "newGroupBatch": null,
    "priceChangeGroup": null,
    "priceChangeGroupDesc": null,
    "priceChange": null,
    "item": null,
    "diff": null,
    "locationType": null,
    "location": null,
    "effectiveDate": null,
    "updatedEffectiveDate": null,
    "changeType": null,
    "changeValue": null,
    "sellingUom": null,
    "multiUnitImpact": null,
    "multiUnitRetail": null,
    "multiUnits": null,
    "multiUnitSellingUom": null,
    "roundingRule": null,
    "reason": null,
    "status": null,
    "ignoreConstraints": null
  }, ... (Possible list, comma separated for multiple)
]
```

Key	Type	Value
action	varchar	"NEW", "MOD", or "DEL"
newGroupBatch	numeric	Transient numeric identifier to group related clearances together in the same clearance group upon creation.
priceChangeGroup	numeric	Price change group display ID
priceChangeGroupDesc	varchar	Price change group description
priceChange	numeric	Price change display ID
item	varchar	Item identifier (parent or transaction)
diff	varchar	Differentiator ID
locationType	numeric	0: Store, 1: Zone, 2: Warehouse
location	numeric	Location ID (either store, warehouse, or zone)
effectiveDate	varchar	Effective date in the format YYYY-MM-DD
updatedEffectiveDate	varchar	Updated effective date in the format YYYY-MM-DD
changeType	numeric	0: Change by Percent, 1: Change by Amount, 2: Fixed Price, 3: Reset POS Price
changeValue	numeric	Decimal change value
sellingUom	varchar	Selling unit of measure for Fixed Price change type

Key	Type	Value
multiUnitImpact	varchar	AU: Add or Update, R: Remove, N: No Change
multiUnitRetail	numeric	Decimal multi unit fixed price change value
multiUnits	numeric	Multi unit quantity
multiUnitSellingUom	varchar	Selling unit of measure for multi unit price change
roundingRule	varchar	Rounding rule ID (technically name column RPM_ROUNDING_RULE.NAME)
reason	varchar	Reason code ID (CODE_DETAIL.CODE)
status	numeric	1: Worksheet, 2: Submitted, 3: Rejected, 4: Approved, 5: Executed, 10: Processing
ignoreConstraints	varchar	"Y" or "N"

## Response Body

```
{
  "statusMsg": null,
  "failPcTable": [
    {
      "priceChange": null,
      "item": null,
      "diff": null,
      "locationType": null,
      "location": null,
      "effectiveDate": null,
      "errorMsg": null
    }, ... (Possible list, comma separated for multiple)
  ]
}
```

## Clearance Induction

### Business Overview

This service provides the ability to create, modify, and delete clearance markdowns and clearance resets via the induction process.

### Service Type

POST

### REST URL

/clearance/induction

### Roles Allowed

PRICING\_APPLICATION\_ADMINISTRATOR\_JOB, PRICING\_MANAGER\_JOB,  
PRICING\_DATA\_STEWARD\_JOB

## Request Headers

```

    Accept: <application/json or application/xml>
Accept-Language: <locale>
    Accept-Version: <application_version>
    Content-Type: <application/json or application/xml>

```

For Example:

```

    Accept: application/json
Accept-Language: en-US
    Accept-Version: 19.0
    Content-Type: application/json

```

## URL Query Parameters

N/A

## Request Body

```

[
  {
    "action": null,
    "newGroupBatch": null,
    "clearanceGroup": null,
    "clearanceGroupDesc": null,
    "clearance": null,
    "markdown": null,
    "item": null,
    "diff": null,
    "locationType": null,
    "location": null,
    "effectiveDate": null,
    "updatedEffectiveDate": null,
    "changeType": null,
    "changeValue": null,
    "roundingRule": null,
    "reason": null,
    "status": null
  }, ... (Possible list, comma separated for multiple)
]

```

Key	Type	Value
action	varchar	"NEW", "MOD", or "DEL"
newGroupBatch	numeric	Transient numeric identifier to group related clearances together in the same clearance group upon creation.
clearanceGroup	numeric	Clearance group display ID
clearanceGroupDesc	varchar	Clearance group description
clearance	numeric	Clearance display ID
markdown	varchar	Markdown code ID (CODE_DETAIL.CODE)
item	varchar	Item identifier (parent or transaction)
diff	varchar	Differentiator ID
locationType	numeric	0: Store, 1: Zone, 2: Warehouse

Key	Type	Value
location	numeric	Location ID (either store, warehouse, or zone)
effectiveDate	varchar	Effective date in the format YYYY-MM-DD
updatedEffectiveDate	varchar	Updated effective date in the format YYYY-MM-DD
changeType	numeric	0: Change by Percent, 1: Change by Amount, 2: Fixed Price, 3: Reset POS Price
changeValue	numeric	Decimal change value
roundingRule	varchar	Rounding rule ID (technically name column RPM_ROUNDING_RULE.NAME)
reason	varchar	Reason code ID (CODE_DETAIL.CODE)
status	numeric	1: Worksheet, 2: Submitted, 3: Rejected, 4: Approved, 5: Executed, 10: Processing

## Response Body

```
{
  "statusMsg": null,
  "failClrTable": [
    {
      "clearance": null,
      "item": null,
      "diff": null,
      "locationType": null,
      "location": null,
      "effectiveDate": null,
      "errorMsg": null
    }
  ], ... (Possible list, comma separated for multiple)
}
```

## Promotion Create

### Business Overview

This service provides the ability to create promotions via the induction process.

### Service Type

POST

### REST URL

/promotion

### Roles Allowed

PRICING\_APPLICATION\_ADMINISTRATOR\_JOB, PRICING\_DATA\_STEWARD\_JOB, PROMOTION\_MANAGER\_JOB, PROMOTION\_PLANNER\_JOB



## Request Headers

```

    Accept: <application/json or application/xml>
Accept-Language: <locale>
    Accept-Version: <application_version>
    Content-Type: <application/json or application/xml>

```

For Example:

```

    Accept: application/json
Accept-Language: en-US
    Accept-Version: 19.0
    Content-Type: application/json

```

## URL Query Parameters

N/A

## Request Body

```

[
  {
    "newPromotionBatch": null,
    "promotionDescription": null,
    "campaign": null,
    "offers": [
      {
        "newOfferBatch": null,
        "offerDescription": null,
        "template": null,
        "startDate": null,
        "startTime": null,
        "endDate": null,
        "endTime": null,
        "couponCode": null,
        "couponCodeRequired": null,
        "distributionRule": null,
        "exclusiveDiscount": null,
        "currency": null,
        "comments": null,
        "customerDescription": null,
        "status": null,
        "offerConditions": [
          {
            "buyXAndYConditionNumber": null,
            "buySpendValue": null,
            "buyQuantityUom": null,
            "priceRestrictionOperator": null,
            "priceRestrictionValue1": null,
            "priceRestrictionValue2": null,
            "items": [
              {
                "itemLevel": null,
                "department": null,
                "clazz": null,
                "subclass": null,
                "supplierSite": null,
                "brand": null,
                "item": null,

```

```

        "diff": null,
        "excluded": null
    }
  ]
}
],
"offerReward": {
  "discountType": null,
  "discountValue": null,
  "applyTo": null,
  "applyDiscountNumberOfTimes": null,
  "priceRestrictionOperator": null,
  "priceRestrictionValue1": null,
  "priceRestrictionValue2": null,
  "items": [
    {
      "itemLevel": null,
      "department": null,
      "clazz": null,
      "subclass": null,
      "supplierSite": null,
      "brand": null,
      "item": null,
      "diff": null,
      "excluded": null
    }
  ]
},
"offerLocations": [
  {
    "locationType": null,
    "location": null,
    "excluded": null
  }
]
}
]
}, ... (Possible list, comma separated for multiple)
]

```

Entity	Key	Type	Value
promotion	newPromotionBatch	numeric	Transient numeric identifier to group related offers together in the same promotion upon creation.
promotion	promotionDescription	varchar	Promotion description
promotion	campaign	varchar	Promotion campaign name
promotion	offers	entity list	Offers for promotion
offer	newOfferBatch	numeric	Transient numeric identifier to group related offer details together upon creation.
offer	offerDescription	varchar	Offer description
offer	template	numeric	Offer template code (SELECT CODE FROM CODE_DETAIL WHERE CODE_TYPE IN ('TSOT', 'ISOT', 'TBOT', 'IBOT', 'IGOT'))

Entity	Key	Type	Value
offer	startDate	varchar	Start date in the format YYYY-MM-DD
offer	startTime	varchar	Start time in the format hh:mm a
offer	endDate	varchar	End date in the format YYYY-MM-DD
offer	endTime	varchar	End time in the format hh:mm a
offer	couponCode	varchar	Coupon code
offer	couponCodeRequired	numeric	0: No, 1: Yes
offer	distributionRule	varchar	Offer distribution code (SELECT CODE FROM CODE_DETAIL WHERE CODE_TYPE = 'OFDR')
offer	exclusiveDiscount	numeric	0: No, 1: Yes
offer condition	currency	varchar	Offer currency code
offer	comments	varchar	Comments
offer	customerDescription	varchar	Customer description
offer	status	numeric	1: Worksheet, 2: Submitted, 3: Rejected, 4: Approved, 6: Active, 9: Cancelled (SELECT CODE FROM CODE_DETAIL WHERE CODE_TYPE = 'PRST')
offer	offerConditions	entity list	Conditions for offer
offer	offerReward	entity	Reward for offer
offer	offerLocations	entity list	Locations for offer
offer condition	buyXAndYCondition Number	numeric	Positive number when template is "Buy X and Y Get Discount" or "Buy X and Y Get Z for Discount"
offer condition	buySpendValue	numeric	Decimal buy/spend value
offer condition	buyQuantityUom	varchar	Buy quantity unit of measure
offer condition	priceRestrictionOperator	varchar	Price restriction operator code (SELECT CODE FROM CODE_DETAIL WHERE CODE_TYPE = 'OPRO')
offer condition	priceRestrictionValue1	numeric	Decimal price restriction value
offer condition	priceRestrictionValue2	numeric	Decimal price restriction value (for second between value)
offer condition	items	entity list	Items for offer condition
offer condition merchandise	itemLevel	numeric	Merchandise level (SELECT CODE FROM CODE_DETAIL WHERE CODE_TYPE = 'OFII')
offer condition merchandise	department	numeric	Merchandise department
offer condition merchandise	clazz	numeric	Merchandise class

Entity	Key	Type	Value
offer condition merchandise	subclass	numeric	Merchandise subclass
offer condition merchandise	supplierSite	numeric	Merchandise supplier site
offer condition merchandise	brand	varchar	Merchandise brand
offer condition merchandise	item	varchar	Item ID (parent or transaction)
offer condition merchandise	diff	varchar	Differentiator ID
offer condition merchandise	excluded	numeric	0: No, 1: Yes
offer reward	discountType	numeric	0: Percent Off, 1: Amount Off, 2: Fixed Price (SELECT CODE FROM CODE_DETAIL WHERE CODE_TYPE = 'OFCT')
offer reward	discountValue	numeric	Decimal discount value
offer reward	applyTo	numeric	0: Regular, 1: Clearance, 2: Regular and Clearance (SELECT CODE FROM CODE_DETAIL WHERE CODE_TYPE = 'PRAT')
offer reward	applyDiscountNumberOfTimes	numeric	Number of times the discount can be applied to individual item
offer reward	priceRestrictionOperator	varchar	Price restriction operator code (SELECT CODE FROM CODE_DETAIL WHERE CODE_TYPE = 'OPRO')
offer reward	priceRestrictionValue1	numeric	Decimal price restriction value
offer reward	priceRestrictionValue2	numeric	Decimal price restriction value (for second between value)
offer reward	items	entity list	Items for offer reward
offer reward merchandise	itemLevel	numeric	Merchandise level (SELECT CODE FROM CODE_DETAIL WHERE CODE_TYPE = 'OFII')
offer reward merchandise	department	numeric	Merchandise department
offer reward merchandise	clazz	numeric	Merchandise class
offer reward merchandise	subclass	numeric	Merchandise subclass
offer reward merchandise	supplierSite	numeric	Merchandise supplier site
offer reward merchandise	brand	varchar	Merchandise brand

Entity	Key	Type	Value
offer reward merchandise	item	varchar	Item ID (parent or transaction)
offer reward merchandise	diff	varchar	Differentiator ID
offer reward merchandise	excluded	numeric	0: No, 1: Yes
offer location	locationType	numeric	0: Store, 1: Zone (SELECT CODE FROM CODE_DETAIL WHERE CODE_TYPE = 'OFLI')
offer location	location	numeric	Location ID (store or zone display ID)
offer location	excluded	numeric	0: No, 1: Yes

## Response Body

```
{
  "statusMsg": null,
  "successes": [
    {
      "newPromotionBatch": null,
      "promotion": null,
      "offers": [
        {
          "newOfferBatch": null,
          "offer": null,
        }
      ]
    }
  ],
  "errors": [
    {
      "newPromotionBatch": null,
      "offers": [
        {
          "newOfferBatch": null,
          "conditions": [
            {
              "buyXAndYConditionNumber": null,
              "items": [
                {
                  "itemLevel": null,
                  "department": null,
                  "clazz": null,
                  "subclass": null,
                  "supplierSite": null,
                  "brand": null,
                  "item": null,
                  "diff": null,
                  "excluded": null,
                  "errors": [
                    {
                      "type": null,
                      "field": null,
                      "message": null
                    }
                  ]
                }
              ]
            }
          ]
        }
      ]
    }
  ]
}
```

```
    ],
    "errors": [
      {
        "type": null,
        "field": null,
        "message": null
      }
    ]
  }
],
"reward": {
  "items": [
    {
      "itemLevel": null,
      "department": null,
      "clazz": null,
      "subclass": null,
      "supplierSite": null,
      "brand": null,
      "item": null,
      "diff": null,
      "excluded": null,
      "errors": [
        {
          "type": null,
          "field": null,
          "message": null
        }
      ]
    }
  ]
},
"errors": [
  {
    "type": null,
    "field": null,
    "message": null
  }
],
"locations": [
  {
    "locationType": null,
    "location": null,
    "excluded": null,
    "errors": [
      {
        "type": null,
        "field": null,
        "message": null
      }
    ]
  }
],
"errors": [
  {
    "type": null,
    "field": null,
    "message": null
  }
]
```

```

    }
  ],
  "errors": [
    {
      "type": null,
      "field": null,
      "message": null
    }
  ]
}
]
}
}

```

Entity	Key	Type	Value
status	statusMsg	varchar	Status of the promotions create request
status	successes	entity list	Promotion successes
status	errors	entity list	Promotion errors
promotion success	newPromotionBatch	numeric	Transient numeric identifier to map back to the request promotion entity
promotion success	promotion	numeric	Created promotion display ID
promotion success	offers	entity list	Offer successes for promotion
offer success	newOfferBatch	numeric	Transient numeric identifier to map back to the request offer entity
offer success	offer	numeric	Created offer display ID
promotion error	newPromotionBatch	numeric	Transient numeric identifier to map back to the request promotion entity
promotion error	offers	entity list	Offer errors for promotion
promotion error	errors	entity list	Error details for promotion
offer error	newOfferBatch	numeric	Transient numeric identifier to map back to the request offer entity
offer error	conditions	entity list	Condition errors for offer
offer error	reward	entity	Reward error for offer
offer error	locations	entity list	Location errors for offer
offer error	errors	entity list	Error details for offer
offer condition error	buyXAndYCondition Number	numeric	Numeric identifier to map back to the request condition entity
offer condition error	items	entity list	Item errors for offer condition
offer condition error	errors	entity list	Error details for offer condition

Entity	Key	Type	Value
offer condition merchandise error	itemLevel	numeric	Merchandise level to map back to the request condition merchandise entity
offer condition merchandise error	department	numeric	Merchandise department to map back to the request condition merchandise entity
offer condition merchandise error	clazz	numeric	Merchandise class to map back to the request condition merchandise entity
offer condition merchandise error	subclass	numeric	Merchandise subclass to map back to the request condition merchandise entity
offer condition merchandise error	supplierSite	numeric	Merchandise supplier site to map back to the request condition merchandise entity
offer condition merchandise error	brand	varchar	Merchandise brand to map back to the request condition merchandise entity
offer condition merchandise error	item	varchar	Item ID (parent or transaction) to map back to the request condition merchandise entity
offer condition merchandise error	diff	varchar	Differentiator ID to map back to the request condition merchandise entity
offer condition merchandise error	excluded	numeric	Excluded value to map back to the request condition merchandise entity
offer condition merchandise error	errors	entity list	Error details for offer condition merchandise
offer reward error	items	entity list	Item errors for offer reward
offer reward error	errors	entity list	Error details for offer reward
offer reward error	itemLevel	numeric	Merchandise level to map back to the request reward merchandise entity
offer reward error	department	numeric	Merchandise department to map back to the request reward merchandise entity
offer reward error	clazz	numeric	Merchandise class to map back to the request reward merchandise entity
offer reward error	subclass	numeric	Merchandise subclass to map back to the request reward merchandise entity



<b>Entity</b>	<b>Key</b>	<b>Type</b>	<b>Value</b>
offer reward error	supplierSite	numeric	Merchandise supplier site to map back to the request reward merchandise entity
offer reward error	brand	varchar	Merchandise brand to map back to the request reward merchandise entity
offer reward error	item	varchar	Item ID (parent or transaction) to map back to the request reward merchandise entity
offer reward error	diff	varchar	Differentiator ID to map back to the request reward merchandise entity
offer reward error	excluded	numeric	Excluded value to map back to the request reward merchandise entity
offer reward error	errors	entity list	Error details for offer reward merchandise
offer location error	locationType	numeric	Location type value to map back to the request location entity
offer location error	location	numeric	Location ID to map back to the request location entity
offer location error	excluded	numeric	Excluded value to map back to the request location entity
offer location error	errors	entity list	Error details for offer location
error	type	varchar	E: Error, W: Warning
error	field	varchar	Entity attribute, field, or column in error
error	message	varchar	Error message



---

---

# Backend System Administration and Configuration

This chapter of the operations guide is intended for administrators who provide support and monitor the running system.

## Supported Environments

See the *Oracle Retail Price Management Installation Guide* for information about requirements for the following:

- RDBMS operating system
- RDBMS version
- Middle tier server operating system
- Middle tier
- Compiler

## Exception Handling

The two primary types of exceptions within the Pricing system are the following:

- System exceptions  
For example, server connection and/or database issues are system exceptions. System exceptions can bring the system to a halt. For example, the connection to the server is lost.
- Business exceptions  
This exception indicates that a business rule has been violated. Most exceptions that arise in the system are business exceptions. For example, a user tries to approve a price change that causes a negative retail.

## Logging Configuration

Logging within Pricing utilizes the ADF built-in logging framework to log system messages and exceptions. This framework is embedded in the application code to allow for configurable logging to suit the needs of the retailer.

Please note that batch client programs log the messages, errors to a log file configured in `batch_logging.properties`. Server logging is done using standard WebLogic logging infra structure.

## ADF Logging

This is a wrapper class of java logger class. It adds ADF convenience methods. All other java logger methods as well are available for user. The following are the different logging levels possible.

- SEVERE (highest value)
- WARNING
- INFO
- CONFIG
- FINE
- FINER
- FINEST (lowest value)

---



---

**Note:** In a production environment, the logging setting should be set to Severe or Warning, so that system performance is not adversely impacted.

---



---

## Batch Client Logging

The pricing batch client java programs write error messages, warnings to a log file configured in batch\_logging.properties. The logging mechanism is based on FileHandler java API.

By default, the log file is configured to be created in the logs folder under user home directory (%h) with the name batch\_log appended with a random number (%u). See below batch\_logging.properties file more details.

## Batch\_logging Properties

The batch\_logging.properties file holds all of the information relevant to logging for batch clients.

**Table 4-1**

Parameter	Description
Handlers	A comma-delimited list of handler class names that are added to the root Logger. The default handlers are java.util.logging.FileHandler and java.util.logging.ConsoleHandler (with a default level of INFO).
.level	Sets the log level for all FileHandler instances. The default log level is INFO.
java.util.logging.FileHandler.pattern	The log file name pattern. The default is %h/ ../logs/batch_log%u.log which means that the file is named batch_log%u.log where: %h the value of the "user.home" system property %u is a unique number to resolve conflicts between simultaneous Java processes

**Table 4–1 (Cont.)**

Parameter	Description
java.util.logging.FileHandler.limit	The maximum size of the file, in bytes. If this is 0, there is no limit. The default is 1000000 (which is 1 MB). Logs larger than 1MB roll over to the next log file.
java.util.logging.FileHandler.count	The number of log files to use in the log file rotation. The default is 365 (which produces a maximum of 365 log files).
java.util.logging.FileHandler.level	Sets the log level for all FileHandler instances. The default log level is FINEST.
java.util.logging.ConsoleHandler.level	Sets the default log level for all ConsoleHandler instances. The default log level is FINEST..
java.util.logging.FileHandler.append	Specifies whether the FileHandler should append onto any existing files (defaults to true)

## Configurable GTTCapture

The conflict checking engine within Pricing utilizes Global Temporary Tables (GTT) extensively which allow for a performance gain, but means that transactional data is lost when the process completes. When attempting to troubleshoot issues within the conflict checking engine around GTT data, this leads to difficulty researching and recreating issues.

A configuration within Pricing allows for capturing this GTT data while processing through the conflict checking engine in an autonomous fashion so that the data is available for review after the process has completed. Data can be captured from the following set of tables:

- RPM\_FUTURE\_RETAIL\_GTT
- RPM\_PROMO\_ITEM\_LOC\_EXPL\_GTT
- RPM\_CUST\_SEGMENT\_PROMO\_FR\_GTT
- RPM\_CLEARANCE\_GTT
- RPM\_FR\_ITEM\_LOC\_EXPL\_GTT

The system is designed to capture data from any of these GTTs based on configuration. Data can be captured from one or more of these tables during conflict checking and can be captured at a configurable start point and optionally beyond the starting point. There are five options for starting points when capturing GTT data:

- GTT Initial Population
- Merge Price Event into Timelines
- Roll Forward
- Payload Population
- Future Retail Purge

The system will also allow for specifying if GTT data should be captured for a specific user in the system or for any user. When specifying a user id to capture data for, the user id needs to match with the user defined within LDAP and should have matching case between LDAP and the GTT capture configuration.

All configuration is handled via the RPM\_CONFIG\_GTT\_CAPTURE table by direct table updates. It is possible to set up all the necessary configurations (starting point, specific user, capture data beyond start point and what tables to capture data from) and disable the capturing of this data all together by setting the ENABLE\_GTT\_CAPTURE field to 'N'. Once the GTT capture configurations are established and enabled on the RPM\_CONFIG\_GTT\_CAPTURE table, nothing more needs to be done other than to process a price event through conflict checking.

When the system does capture data from the GTT tables, it will always capture all data on the specified tables at the "starting point" and then only capture updated or newly created data for each statement beyond that point when data is being captured beyond the starting point. In such a scenario, the evolution of a record will be easily available for viewing and troubleshooting efforts with the impact of every statement being identified easily.

A batch process (PurgeGttCaptureBatch.sh) will purge all data captured from the GTT tables to allow for only pertinent data to be in place at any given time. This purge process does not have to run prior to capturing GTT data in conflict checking, however it is expected that capturing this data will produce a large volume of data in many scenario. By purging this data before running the conflict checking process again for new data to be captured, it will be easier to examine the data.