Resources to be created Oracle FLEXCUBE Investor Servicing Release 14.4.0.0.0 [July] [2020]





Table of Contents

1.	RES	OURCES TO BE CREATED ON APPLICATION SERVER	1-3
1	1	INTRODUCTION	1-
1	.2	RESOURCE TYPES	1-1
		RESOURCE PRE-REQUISITES FOR PLUG-INS	
		Oracle FLEXCUBE IS	
1	.4	GATEWAY	1-3
1	.5	SCHEDITI ER	1-3



1. Resources to be created on Application Server

1.1 Introduction

This chapter explains list of resources to be created for FCIS application.

1.2 Resource Types

Configure the application server for Oracle FLEXCUBE Application. Ensure that the following resources are available before deployment:

- Data source
- JMS resources
- Debug paths for host and branch

1.3 Resource Pre-requisites for Plug-ins

Resource prerequisites for different plug-ins are explained below. In case you wish to include a plug-in, ensure that the corresponding resources are created.

1.3.1 Oracle FLEXCUBE IS

FCIS needs below resources before deployment. Create the following queues and connection factories in the application server.

JMS Connection Factories

QCF Label	QCF	
Notify Destination QCF	NotifyDestQCF	
Deferred QCF	DefferedDestQCF	
Notify QCF	NOTIFY_MDB_QCF	
Incoming QCF	EmsQcf	
BIP QCF	BIPQCF	
GI Upload QCF	GI_UPLOAD_QCF	
<internally referred=""></internally>	ELMDBQCF	
<internally referred=""></internally>	EL_NOTIFY_QCF	



Queues

Create the following queues:

QUEUE Label	QUEUE
Notify Destination Queue Name	NOTIFY_DEST_QUEUE
Deferred Queue Name	DEFFERED_DEST_QUEUE
Notify Queue Name	NOTIFY_QUEUE
Dead Letter Queue name	NOTIFY_QUEUE_DLQ
Incoming BackupQueue name	EMS_QUEUE_BACK
Incoming Dead Letter Queue name	EMS_QUEUE_DLQ
Incoming Queue Name	EMS_INQUEUE
Outgoing Queue Name	EMS_OUTQUEUE
SFMS Incoming Queue	SFMS_INQUEUE
RTGS Incoming Queue	RTGS_INQUEUE
BIP Queue Name	INTERNAL_BIPREPORT_QUEUE
BIP Dead Letter Queue Name	INTERNAL_BIP_QUEUE_DLQ
BIPadvice Queue Name	INTERNAL_BIPADVREPORT_QUEUE
BIPadvice Dead Letter Queue Name	INTERNAL_BIP_ADVICE_QUEUE_DLQ
GI Upload Queue Name	INTERNAL_GI_UPLOAD_QUEUE
GI Upload Dead Letter Queue Name	INTERNAL_GI_UPLOAD_DLQ
<internally referred=""></internally>	ELMDB_REQ_Q
<internally referred=""></internally>	ELMDB_RES_Q
<internally referred=""></internally>	ELMDB_DLQ
<internally referred=""></internally>	EL_NOTIFY_REQ_Q
<internally referred=""></internally>	EL_NOTIFY_RES_Q
<internally referred=""></internally>	EL_NOTIFY_DLQ

Data source

Datasource Name	Datasource Label	Туре	Default Value
INIT_DATASOURCE	Data Source	NON-XA	jdbc/fcjdevDS
SCHEDULER_DS	Scheduler Datasource	XA	jdbc/fcjSchedulerDS



Note the following:

- You need to create XA data source for Oracle FCIS with the JNDI name '_XA' for Scheduler.
 For example, if the Oracle FCIS HOST Non XA data source JNDI name is 'jdbc/fcjdevIS',
 then you need to create another data source for FCIS with the JNDI name 'jdbc/fcjdevIS_XA'.
- In addition to above mentioned data sources, for each LOB schema, data source configuration need to be created.



1.4 **Gateway**

If scheduler is included in the property file, create the following queues and connection factories in the application server.

Connection Factories

Create the following connection factories:

QCF Label	QCF
MDB QCF	MDBQCF

All these must be XA enabled.

Queues

Create the following queues:

QUEUE Label	QUEUE	
MDB Request Queue	MDB_QUEUE	
MDB Response Queue	MDB_QUEUE_RESPONSE	
MDB DL Queue	MDB_QUEUE_DLQ	

DataSource

Datasource Name	Datasource Label	Туре	Default Value
FCUBS MSG SCHEMA CON		XA for MDB	FLEXTEST.WORLD
POOLNAME	DataSource	and	
		NON-XA for	
		others	

In addition to above mentioned data sources, for each LOB schema, data source configuration need to be created.

1.5 Scheduler

If scheduler is included in the property file, create the following queues and connection factories in the application server.

Connection Factories

Create the following connection factories:

QCF Label	QCF	
Notify Destination QCF	NotifyDestQCF	
Deferred QCF	DefferedDestQCF	
Notify QCF	NOTIFY_MDB_QCF	
Incoming QCF	EmsQcf	
BIP QCF	BIPQCF	
GI Upload QCF	GI_UPLOAD_QCF	



All these must be XA enabled.

Queues

Create the following queues:

QUEUE Label	QUEUE	
Notify Destination Queue Name	NOTIFY_DEST_QUEUE	
Deferred Queue Name	DEFFERED_DEST_QUEUE	
Notify Queue Name	NOTIFY_QUEUE	
Dead Letter Queue name	NOTIFY_QUEUE_DLQ	
Incoming BackupQueue name	EMS_QUEUE_BACK	
Incoming Dead Letter Queue name	EMS_QUEUE_DLQ	
Incoming Queue Name	EMS_INQUEUE	
Outgoing Queue Name	EMS_OUTQUEUE	
SFMS Incoming Queue	SFMS_INQUEUE	
RTGS Incoming Queue	RTGS_INQUEUE	
BIP Queue Name	INTERNAL_BIPREPORT_QUEUE	
BIP Dead Letter Queue Name	INTERNAL_BIP_QUEUE_DLQ	
BIPadvice Queue Name	INTERNAL_BIPADVREPORT_QUEUE	
BIPadvice Dead Letter Queue Name	INTERNAL_BIP_ADVICE_QUEUE_DLQ	
GI Upload Queue Name	INTERNAL_GI_UPLOAD_QUEUE	
GI Upload Dead Letter Queue Name	INTERNAL_GI_UPLOAD_DLQ	

Topic Connection Factory

NotifyDestTCF

Topic

NOTIFY_DEST_TOPIC

Datasource Name	Datasource Label	Туре	Default Value
INIT_DATASOURCE	Data Source	NON-XA	jdbc/fcjdevDS
SCHEDULER_DS	Scheduler Datasource	XA	jdbc/fcjSchedulerDS

You need to create XA data source for Oracle FCIS with the JNDI name _XA for scheduler. For example, if the Oracle FCIS HOST Non XA data source JNDI name is 'jdbc/fcjdevDS', then you need to create another data source for FCIS with the JNDI name 'jdbc/fcjdevDS_XA'.

To configure scheduler and EMS with MQ series, follow the steps given below.

- Create queues in MQ Series
- Create binding file
- Copy the MQ series JAR files to Oracle WebLogic domain library folder

Security Provider Libraries

If you wish to include signing process for SFMS messages, you need to set the following library.



File Name	Download Location	Instructions
bcprov- jdk(Latest Qualified Version).jar	http://www.bouncycastle.org/latest_releases.html	Copy the file 'bcprov- jdk(Latest Qualified Version).jar' to the directory '{WL_JAVA_HOME}/jre/lib/ext'
		Here, 'WL_JAVA_HOME' is the Java root directory from which WebLogic server is running.
		Restart Oracle WebLogic server.

For details on latest version of the software qualified with Oracle FLEXCUBE, refer to the release certificate.





Resources to be created [July] [2020] Version 14.4.0.0.0

Oracle Financial Services Software Limited Oracle Park Off Western Express Highway Goregaon (East) Mumbai, Maharashtra 400 063 India

Worldwide Inquiries: Phone: +91 22 6718 3000 Fax:+91 22 6718 3001 www.oracle.com/financialservices/

Copyright © [2007], [2020], Oracle and/or its affiliates.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software" or "commercial computer software documentation" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate failsafe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.

