

Gateway Application Deployment in WebLogic  
Oracle FLEXCUBE Investor Servicing  
Release 14.4.0.0.0  
[July] [2020]



---

# Table of Contents


- 1. GATEWAY APPLICATION FULL DEPLOYMENT ..... 1-1
  - 1.1 GATEWAY EJB APPLICATION FULL DEPLOYMENT ..... 1-1
  - 1.2 GATEWAY MDB APPLICATION FULL DEPLOYMENT ..... 1-10
  - 1.3 GATEWAY HTTP SERVLET APPLICATION FULL DEPLOYMENT ..... 1-19
  - 1.4 GATEWAY WEBSERVICES APPLICATION FULL DEPLOYMENT..... 1-25

---

# 1. Gateway Application Full Deployment


## 1.1 Gateway EJB Application Full Deployment

1. Launch Oracle FLEXCUBE Investor Servicing Installer.
2. Click on “Next” to display the screen below.




3. Select “Gateway”.

- Click on “Next” to display the screen below.



- Select “Deploy Application”.
- Choose the appropriate Server’s Operating System from the drop-down.
- Choose “Weblogic” from the Application Server drop-down.
- Click on “Next” to display the screen below.



9. Select 'Gateway EJB' and click 'next', the following screen will be displayed.

Oracle FLEXCUBE Universal Installer

**Oracle FLEXCUBE Investor Servicing** ORACLE

**Application Deployment**  
Provide server details for connecting to the server.

Name	Value
Admin IP	10.10.10.10
Admin Port	1111
Admin Username	<user_name>
Server Admin Password	*****

Test Connection

Type of Deployment: Full Deployment ▼

Log Back Next Exit

10. Provide the following details

**Admin IP**

Provide host address of admin server.

**Admin Port**

Provide port number of weblogic server.

**Admin UserName**

Please provide the appropriate Admin Username of the weblogic application server.


**Admin Password**

Please provide the appropriate Admin Password of the weblogic application server.


**Type of Deployment**

Choose "Full Deployment".

11. Click on “Test Connection” to test the connection with the application server. On successful connection, the following message will be displayed.



12. Click on “OK” and click on “Next” to display the screen below.



13. Provide the following details

### **EAR Path**

Select the application EAR to be deployed using the browse button.

Note: The Application EAR path cannot be copied and pasted on to the text box, thereby demanding the use of the browse button to the select the EAR.

### **Property File Path**

Please select the appropriate path to the external properties file.

If the properties file is internal to the application EAR, it would be fetched on selection of the EAR and will be in a non-editable state.

### **Application Name**

Application Name would be fetched on selection of the EAR and will be in a non-editable state.


## Application Context

Application Context would be fetched on selection of the EAR and will be in a non-editable state.

## Manage Resources

Select this box if resources are to be created along with deployment.

- Click on “Next”. If “Manage Resources” is checked then below screen shown otherwise skip to “Server Environment details for Deployment”.



- The current screen shows a list of resources that will be created and their type.

The screen provides a read only list of resources.

16. Click on Next. The following screen will be displayed.

S.No.	Property Name	Property Value
1	DataSource Driver	oracle.jdbc.OracleDriver
2	DataSource Type	INIT_DATASOURCE
3	Schema UserName	abc
4	Schema PAssword	...
5	IP Address	10.184.86.27
6	Port Number	1522
7	Service Name	avast1
8	Initial Capacity	15

17. Provide the following details

**Resource ID:** Contains a list of data sources that are to be created.

The below table provides an option to take some basic values for the data source.

**DataSource Driver:** specified the jdbc driver url with which the connection is established.

Ex: oracle.jdbc.OracleDriver for Non-XA datasources

**DataSource Type:** specifies the type of datasource that is to be created, XA or Non-XA.

**Schema Username:** specified the username of the schema to which the connection is established.

**Schema Paasword:** specifies the password of the schema.

**IP Address:** specifies to provide the host address of the scema.

**Port Number:** provide the port number of schema.

**Service Name:** provide the schema name.

**Initial Capacity:** The number of physical connections to create when creating the connection pool in the data source

**Maximum Capacity:** The maximum number of physical connections that this connection pool can contain.

**Capacity Increment:** The increment by which this JDBC connection pool's capacity is expanded.

**Shrink Frequency:** The number of seconds to wait before shrinking a connection pool that has incrementally increased to meet demand.


**Connection Reserve Timeout:** The number of seconds after which a call to reserve a connection from the connection pool will timeout.

- **Save changes:** On click of this saves the values provided In the table against corresponding value of Resource ID.
- **Test Connection:** On click of this it will try to establish connection with required details provided in the table.

Click on 'Next' to get the following screen.

- **Modify JDBC URL:** Select modify JDBC URL for modifying the JDBC URL.

If 'Modify JDBC URL' is selected, the following screen will be displayed.



**Resource ID:** It provides the list of all the data sources created. Select the data source for which the JDBC url needs to be modified.

**Note:** The URL generated from the previous screen will be displayed here. If the user wants to change the URL, it can be changed in the present screen.

**Test Connection:** Click 'Test Connection' to check the connection using the changed URL, If the URL changed is correct the connection will be success.

**Save Changes:** Click on 'Save Changes' fo4r saving the changed JDBC URL

Click 'Next', the following screen will be displayed.

Oracle FLEXCUBE Universal Installer

Oracle FLEXCUBE Investor Servicing ORACLE

**Application Full Deployment**  
Specify Server environment details for deployment

Domain Name

S.No.	Server Name	Deploy
1	AdminServer	<input type="checkbox"/>
2	ManagedServer	<input type="checkbox"/>
3	ClusterTest	<input type="checkbox"/>
4	AVAST	<input type="checkbox"/>

The **Domain Name** shows the weblogic domains name.

- On click of '**Get Details**', the list of available servers are displayed in the table.

**Atleast one** server should be selected to proceed to next screen.

- Click on "Next" to display the screen below.



Oracle FLEXCUBE Universal Installer

Oracle FLEXCUBE Investor Servicing ORACLE


**Application Full Deployment**  
Current screen Displays the status of Applications being deployed.

- Click on **“Start Deployment”** to begin the process of application deployment.

On successful deployment, you will get the following message and the screen is expected to look like below.




If the deployment is not successful, the 'Undeploy' button will be enabled.



18. Click 'Undeploy' for undeploying the partially deployed EAR from the server.


## 1.2 Gateway MDB Application Full Deployment

1. Launch Oracle FLEXCUBE Investor Servicing Installer.
2. Click on "Next" to display the screen below.




3. Select "Gateway".


- Click on “Next” to display the screen below.



- Select “Deploy Application”.
- Choose the appropriate Server’s Operating System from the drop down.
- Choose “Weblogic” from the Application Server drop-down.
- Click on “Next” to display the screen below.



9. Select 'Gateway MDB' and click 'next', the following screen will be displayed.



The screenshot shows the 'Oracle FLEXCUBE Universal Installer' window. The title bar says 'Oracle FLEXCUBE Universal Installer'. The main window has a red header with 'Oracle FLEXCUBE Investor Servicing' and the 'ORACLE' logo. Below the header, the section is titled 'Application Deployment' with the instruction 'Provide server details for connecting to the server.' There is a table with two columns: 'Name' and 'Value'. The table contains four rows: 'Admin IP' with value '10.10.10.10', 'Admin Port' with value '1111', 'Admin Username' with value '<user\_name>', and 'Server Admin Password' with value '\*\*\*\*\*'. Below the table is a 'Test Connection' button. Underneath that is a 'Type of Deployment' label and a dropdown menu currently showing 'Full Deployment'. At the bottom of the window are three buttons: 'Log', 'Back', and 'Next', and an 'Exit' button.

Name	Value
Admin IP	10.10.10.10
Admin Port	1111
Admin Username	<user_name>
Server Admin Password	*****

Test Connection

Type of Deployment: Full Deployment

Log Back Next Exit

10. Provide the following details

**Admin IP**

Provide host address of admin server.

**Admin Port**

Provide port number of weblogic server.

**Admin UserName**

Please provide the appropriate Admin Username of the weblogic application server.


**Admin Password**

Please provide the appropriate Admin Password of the weblogic application server.


**Type of Deployment**

Choose "Full Deployment".

11. Click on "Test Connection" to test the connection with the application server. On successful connection, the following message will be displayed.



12. Click on “OK” and click on “Next” to display the screen below.



13. Provide the following details

### **EAR Path**

select the application EAR to be deployed using the browse button.

Note: The Application EAR path cannot be copied and pasted on to the text box, thereby demanding the use of the browse button to select the EAR.

### **Property File Path**

Please select the appropriate path to the external properties file.

If the properties file is internal to the application EAR, it would be fetched on selection of the EAR and will be in a non-editable state.

### **Application Name**

Application Name would be fetched on selection of the EAR and will be in a non-editable state.


### **Application Context**

Application Context would be fetched on selection of the EAR and will be in a non-editable state.

### **Manage Resources**

Select this box if resources are to be created along with deployment.


14. Click on “Next”. If “Manage Resources” is checked then below screen is shown otherwise skip to “Server Environment details for Deployment”.



The current screen shows a list of resources that will be created and their type.

The screen provides a read only list of resources.

15. Click on Next. The following screen will be displayed.



16. Provide the following details

**Resource ID:** Contains a list of data sources that are to be created.

The below table provides an option to take some basic values for the data source.

**DataSource Driver:** specified the jdbc driver URL with which the connection is established.

Ex: oracle.jdbc.OracleDriver for Non-XA datasources

**DataSource Type:** specifies the type of data source that is to be created, XA or Non-XA.

**Schema Username:** specified the username of the schema to which the connection is established.

**Schema Password:** specifies the password of the schema.

**IP Address:** specifies to provide the host address of the schema.

**Port Number:** provide the port number of schema.

**Service Name:** provide the schema name.

**Initial Capacity:** The number of physical connections to create when creating the connection pool in the data source

**Maximum Capacity:** The maximum number of physical connections that this connection pool can contain.

**Capacity Increment:** The increment by which this JDBC connection pool's capacity is expanded.

**Shrink Frequency:** The number of seconds to wait before shrinking a connection pool that has incrementally increased to meet demand.


**Connection Reserve Timeout:** The number of seconds after which a call to reserve a connection from the connection pool will timeout.

- **Save changes:** On click of this saves the values provided in the table against corresponding value of Resource ID.
- **Test Connection:** On click of this it will try to establish connection with required details provided in the table.

Click on 'Next' to get the following screen.

17. **Modify JDBC URL:** Select modify JDBC URL for modifying the JDBC URL.

If 'Modify JDBC URL' is selected, the following screen will be displayed.



**Resource ID:** It provides the list of all the data sources created. Select the data source for which the JDBC URL needs to be modified.

**Note:** The URL generated from the previous screen will be displayed here. If the user wants to change the URL, it can be changed in the present screen.

**Test Connection:** Click 'Test Connection' to check the connection using the changed URL, If the URL changed is correct the connection will be success.

**Save Changes:** Click on 'Save Changes' for saving the changed JDBC URL

Click 'Next', the following screen will be displayed.

S.No.	Server Name	Deploy
1	AdminServer	<input type="checkbox"/>
2	ManagedServer	<input type="checkbox"/>
3	ClusterTest	<input type="checkbox"/>
4	AVAST	<input type="checkbox"/>

The **Domain Name** shows the weblogic domains name.

- On click of '**Get Details**', the list of available servers are displayed in the table.



**Atleast one** server should be selected to proceed to next screen.

- Click on "Next" to display the screen below.


Start Deployment

- Click on "**Start Deployment**" to begin the process of application deployment.

On successful deployment, you will get the following message and the screen is expected to look like below.




If the deployment is not successful, the 'Undeploy' button will be enabled.



18. Click 'Undeploy' for undeploying the partially deployed EAR from the server.


### 1.3 **Gateway HTTP Servlet Application Full Deployment**

1. Launch Oracle FLEXCUBE Investor Servicing Installer.
2. Click on "Next" to display the screen below.




3. Select "Gateway".

- Click on “Next” to display the screen below.



- Select “Deploy Application”.
- Choose the appropriate Server’s Operating System from the drop down.
- Choose “Weblogic” from the Application Server drop down.
- Click on “Next” to display the screen below.



9. Select 'Gateway MDB' and click 'Next', the following screen will be displayed.

Name	Value
Admin IP	10.10.10.10
Admin Port	1111
Admin Username	<user_name>
Server Admin Password	*****

10. Provide the following details

**Admin IP**

Provide host address of admin server.

**Admin Port**

Provide port number of weblogic server.

**Admin UserName**

Please provide the appropriate Admin Username of the weblogic application server.


**Admin Password**

Please provide the appropriate Admin Password of the weblogic application server.


**Type of Deployment**

Choose "Full Deployment".

Click on "Test Connection" to test the connection with the application server. On successful connection, the following message will be displayed.



11. Click on “OK” and click on “Next” to display the screen below.



The screenshot shows the Oracle FLEXCUBE Universal Installer window. The title bar reads "Oracle FLEXCUBE Universal Installer". The window has a red header bar with "Oracle FLEXCUBE Investor Servicing" on the left and the "ORACLE" logo on the right. Below the header, the section is titled "Application deployment" with the instruction "Provide the Application Details For the Deployment of EAR". There are four text input fields: "EAR Path" with the value "D:\12.0.3\DEST\FCUBSAppins.ear", "Property File Path" with the value "2.0.3\12.0.3\_Installer\_Finalized\_Sources\fcubs.properties", "Application Name" with the value "FCUBSAppins", and "Application Context" which is empty. To the right of the first two fields are yellow folder icons. Below the fields is a checkbox labeled "Manage Resources" which is unchecked. At the bottom of the window are four buttons: "Log", "Back", "Next", and "Exit".

12. Provide the following details

### EAR Path

select the application EAR to be deployed using the browse button.

Note: The Application EAR path cannot be copied and pasted on to the text box, thereby demanding the use of the browse button to select the EAR.

### Property File Path

Please select the appropriate path to the external properties file.

If the properties file is internal to the application EAR, it would be fetched on selection of the EAR and will be in a non-editable state.

### Application Name

Not applicable

### Application Context

Not applicable

### Manage Resources

Not supported.

13. Click on “Next” to display the screen below.

Oracle FLEXCUBE Universal Installer

Oracle FLEXCUBE Investor Servicing ORACLE

**Application Full Deployment**  
Specify Server environment details for deployment

Domain Name

S.No.	Server Name	Deploy
1	AdminServer	<input type="checkbox"/>
2	ManagedServer	<input type="checkbox"/>
3	ClusterTest	<input type="checkbox"/>
4	AVAST	<input type="checkbox"/>

The **Domain Name** shows the weblogic domains name.

14. On click of ‘**Get Details**’, the list of available servers are displayed in the table.

**Atleast one** server should be selected to proceed to next screen.

15. Click on “Next” to display the screen below.


Oracle FLEXCUBE Universal Installer

Oracle FLEXCUBE Investor Servicing ORACLE


**Application Full Deployment**  
Current screen Displays the status of Applications being deployed.

16. Click on “**Start Deployment**” to begin the process of application deployment.

On successful deployment, you will get the following message and the screen is expected to look like below.




If the deployment is not successful, the 'Undeploy' button will be enabled




17. Click 'Undeploy' for undeploying the partially deployed EAR from the server.

## 1.4 Gateway Webservices Application Full Deployment


1. Launch Oracle FLEXCUBE Investor Servicing Installer.
2. Click on "Next" to display the screen below.



3. Select “Gateway”.
4. Click on “Next” to display the screen below.



5. Select “Deploy Application”.
6. Choose the appropriate Server’s Operating System from the drop down.
7. Choose “Weblogic” from the Application Server drop down.
8. Click on “Next” to display the screen below.



9. Select 'Gateway MDB' and click 'next', the following screen will be displayed.

The screenshot shows the 'Oracle FLEXCUBE Universal Installer' window. The title bar says 'Oracle FLEXCUBE Universal Installer'. The main window has a red header with 'Oracle FLEXCUBE Investor Servicing' and the 'ORACLE' logo. Below the header, the section is titled 'Application Deployment' with the instruction 'Provide server details for connecting to the server.' There is a table with two columns: 'Name' and 'Value'. The table contains the following rows: 'Admin IP' with value '10.10.10.10', 'Admin Port' with value '1111', 'Admin Username' with value '<user\_name>', and 'Server Admin Password' with value '\*\*\*\*\*'. Below the table is a 'Test Connection' button. Underneath that is a 'Type of Deployment' label and a dropdown menu currently showing 'Full Deployment'. At the bottom of the window are four buttons: 'Log', 'Back', 'Next', and 'Exit'.

Name	Value
Admin IP	10.10.10.10
Admin Port	1111
Admin Username	<user_name>
Server Admin Password	*****

Test Connection

Type of Deployment: Full Deployment

Log Back Next Exit

10. Provide the following details

**Admin IP**

Provide host address of admin server.

**Admin Port**

Provide port number of weblogic server.

**Admin UserName**

Please provide the appropriate Admin Username of the weblogic application server.


**Admin Password**

Please provide the appropriate Admin Password of the weblogic application server.


**Type of Deployment**

Choose "Full Deployment".

11. Click on “Test Connection” to test the connection with the application server. On successful connection, the following message will be displayed.



12. Click on “OK” and click on “Next” to display the screen below.



13. Provide the following details

Provide the EAR path for the applications to be deployed.

**Note:** Use '+' and '-' buttons for adding and removing the paths.

14. Click on “Next” to display the screen below.

Oracle FLEXCUBE Universal Installer

Oracle FLEXCUBE Investor Servicing ORACLE

**Application Full Deployment**  
Specify Server environment details for deployment

Domain Name:

S.No.	Server Name	Deploy
1	AdminServer	<input type="checkbox"/>
2	ManagedServer	<input type="checkbox"/>
3	ClusterTest	<input type="checkbox"/>
4	AVAST	<input type="checkbox"/>

The **Domain Name** shows the weblogic domains name.

15. On click of ‘**Get Details**’, the list of available servers are displayed in the table.

**Atleast one** server should be selected to proceed to next screen.

16. Click on “Next” to display the screen below.



Oracle FLEXCUBE Universal Installer

Oracle FLEXCUBE Investor Servicing ORACLE


**Application Full Deployment**  
Current screen Displays the status of Applications being deployed.

17. Click on “**Start Deployment**” to begin the process of application deployment.

On successful deployment, you will get the following message and the screen is expected to look like below.



If the deployment is not successful, the 'Undeploy' button will be enabled



Click 'Undeploy' for undeploying the partially deployed EAR from the server.



Setting up Database  
[July] [2020]  
Version 14.4.0.0.0

Oracle Financial Services Software Limited  
Oracle Park  
Off Western Express Highway  
Goregaon (East)  
Mumbai, Maharashtra 400 063  
India

Worldwide Inquiries:  
Phone: +91 22 6718 3000  
Fax: +91 22 6718 3001  
[www.oracle.com/financialservices/](http://www.oracle.com/financialservices/)

Copyright © [2007], [2020], Oracle and/or its affiliates.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

**U.S. GOVERNMENT END USERS:** Oracle programs (including any operating system, integrated software, any programs embedded, installed or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software" or "commercial computer software documentation" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate failsafe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.