ORACLE
PEOPLESOFT

PeopleTools 8.54: PeopleCode API Reference

November 2016

ORACLE

PeopleTools 8.54: PeopleCode API Reference
CDSKU
Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

License Restrictions Warranty/Consequential Damages Disclaimer

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

Warranty Disclaimer

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

Restricted Rights Notice

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

Hazardous Applications Notice

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Trademark Notice

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

Third Party Content, Products, and Services Disclaimer

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc.

Access to Oracle Support

Oracle customers that have purchased support have access to electronic support through My Oracle Support. For information, visit http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info or visit http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs if you are hearing impaired.

Contents

Preface ..... **cxv**
Understanding the PeopleSoft Online Help and PeopleBooks cxv
PeopleSoft Hosted Documentation cxv
Locally Installed Help cxv
Downloadable PeopleBook PDF Files cxv
Common Help Documentation cxvi
Field and Control Definitions cxvi
Typographical Conventions cxvi
ISO Country and Currency Codes cxvii
Region and Industry Identifiers cxvii
Using and Managing the PeopleSoft Online Help cxviii
PeopleTools Related Links cxviii
Contact Us cxviii
Follow Us cxviii
Chapter 1: Activity Guide Classes **121**
Understanding the Activity Guide Classes 121
Importing Activity Guide Classes 121
Activity Guide Classes Reference 121
List Class 122
List Class Methods 122
createInstance 122
getActionItems 123
GetContext 124
getMembers 124
GetPgltBtn 125
getRootItems 125
new 126
open 126
save 127
SaveContext 127
saveMembers 127
SavePgltBtn 128
List Class Properties 128
AppClassID 128
AppClassMethod 129
DescrLong 129
Field1 129
Field10 130
Field2 130
Field3 130
Field4 130
Field5 131
Field6 131
Field7 131
Field8 131
Field9 132
HomeUrl 132

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

isActive.... 132
IsTemplate.... 132
Label.... 133
ListId.... 133
PackageRoot.... 133
ParentTemplate.... 134
pgltAppClass.... 134
pgltPackageRoot.... 134
pgltProgressBarVisible.... 135
pgltQualifyPath.... 135
QualifyPath.... 135
Status.... 136
ActionItem Class.... 136
ActionItem Class Methods.... 137
delete.... 137
new.... 137
nextAction.... 138
open.... 138
prevAction.... 139
save.... 139
ActionItem Class Properties.... 139
AppClassID.... 140
AssignedToOprid.... 140
AssignType.... 140
CurrentStep.... 141
DescrLong.... 141
DueDate.... 141
DueTm.... 141
Field1.... 142
Field10.... 142
Field2.... 142
Field3.... 142
Field4.... 143
Field5.... 143
Field6.... 143
Field7.... 143
Field8.... 144
Field9.... 144
ItemId.... 144
Label.... 144
ListId.... 145
PackageRoot.... 145
ParentId.... 145
PercCompl.... 145
Priority.... 146
QualifyPath.... 146
Remarks.... 146
Required.... 147
Sequence.... 147
ServiceId.... 147
StartDt.... 147

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

StartTm.... 148
Status.... 148
Summary.... 148
Type.... 149
Member Class.... 149
Member Class Methods.... 150
IsEqual.... 150
Member.... 150
Member Class Properties.... 151
Name.... 151
PrivilegeSetID.... 151
Type.... 151
ContextData Class.... 152
ContextData Class Methods.... 152
ContextData.... 152
IsEqual.... 153
ContextData Class Properties.... 153
ctxKey.... 153
ctxVisible.... 154
fieldname.... 154
keyLabel.... 154
keyValue.... 154
recname.... 154
Chapter 2: AESection Class.... 155
Understanding the AESection Class.... 155
How an AESection is Accessed.... 156
AESection Example.... 157
Data Type of an AESection Object.... 158
Scope of an AESection Object.... 158
AESection Class Built-in Function.... 158
AESection Class Methods.... 159
AddStep.... 159
Close.... 160
Open.... 160
Save.... 161
SetSQL.... 162
SetTemplate.... 163
AESection Class Property.... 164
IsOpen.... 164
Chapter 3: Analytic Calculation Engine Classes.... 165
Understanding the Analytic Calculation Engine Classes.... 165
Using the Analytic Calculation Engine Classes with Application Engine.... 165
Running Synchronously.... 166
Using Trees.... 166
Error Handling.... 167
Data Types for Analytic Calculation Engine Classes.... 167
Scope of Analytic Calculation Engine Classes.... 167
Analytic Calculation Engine Classes Built-in Functions.... 168
AnalyticInstance Class Methods.... 168
CheckAsyncStatus.... 168
CheckStatus.... 169

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Copy....169
Delete....170
GetAnalyticModel....171
Load....171
RunAsync....173
RunSync....173
Terminate....174
Unload....174
AnalyticInstance Class Properties....175
AnalyticType....175
ID....175
Messages....175
AnalyticModel Class Methods....176
AddMember....176
AttachTree....176
CalculateCube....178
DetachTree....178
GetCubeCollection....179
GetCellProperties....179
GetMembers....180
GetTree....182
Recalculate....183
RenameMember....183
AnalyticModel Class Property....184
Messages....184
CubeCollection Class....184
CubeCollection Class Methods....185
CollapseNode....185
DrillIntoNode....185
DrillOutOfNode....186
ExpandNode....186
GetData....188
GetDimFilter....189
GetDimSort....189
GetLayout....190
GetRowCount....190
GetSlice....191
SetData....191
SetDimensionOrder....192
SetDimFilter....192
SetDimSort....193
SetSlice....194
ShowHierarchy....194
UnsetDimFilter....196
UnsetDimSort....196
CubeCollection Class Property....197
Messages....197
Chapter 4: Analytic Calculation Engine Metadata Classes....199
Understanding the PeopleSoft Analytic Calculation Engine Metadata Classes....199
Using the Analytic Calculation Engine Metadata Classes....199
Inserting and Deleting Objects....200

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Building a Rule as an Object....200
Error Handling....200
Data Types of the Analytic Calculation Engine Metadata Objects....201
Scope of Analytic Calculation Engine Metadata Objects....201
How to Import the Analytic Calculation Engine Metadata Classes....201
How to Create an Analytic Calculation Engine Metadata Class Object....202
Analytic Calculation Engine Metadata Classes Constructor....203
AnalyticModelDefn....203
AnalyticModelDefn Class....203
AnalyticModelDefn Class Methods....204
AddCube....204
AddCubeCollection....204
AddDimension....205
AddExplicitDimensionSet....205
AddOrganizer....206
AddUserFunction....206
CopyCube....207
CopyCubeCollection....208
CopyDimension....208
CopyExplicitDimensionSet....209
CopyTo....209
CopyUserFunction....210
Create....211
Delete....211
DeleteCube....212
DeleteCubeCollection....212
DeleteDimension....213
DeleteExplicitDimensionSet....214
DeleteOrganizer....214
DeleteUserFunction....215
Get....216
GetCube....216
GetCubeCollection....217
GetCubeCollectionNames....217
GetCubeNames....218
GetDimension....218
GetDimensionNames....219
GetExplicitDimensionSet....220
GetExplicitDimensionSetNames....220
GetOrganizer....221
GetOrganizerNames....221
GetUserFunction....222
GetUserFunctionNames....222
Rename....223
RenameCube....223
RenameCubeCollection....224
RenameDimension....225
RenameExplicitDimensionSet....225
RenameOrganizer....226
RenameUserFunction....227
Save....227

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Validate....228
AnalyticModelDefn Properties....229
CircularFormulaWarn....229
Description....229
IsValid....229
LongDescription....229
MaxDelta....230
MaxIterations....230
Messages....230
Name....230
ResolveCircularDeps....231
DimensionDefn Class....231
DimensionDefn Class Properties....231
AggregateSequence....231
AggregationUserFunction....231
Comments....232
Name....232
TotalMemberName....232
ExplicitDimensionSet Class....232
ExplicitDimensionSet Methods....233
AttachDimension....233
DetachDimension....233
GetDimensionNames....234
ExplicitDimensionSet Properties....234
Name....234
SequenceNumber....234
CubeDefn Class....235
CubeDefn Class Methods....235
AttachDimension....235
DetachDimension....235
GetCauses....236
GetCircularDeps....237
GetDimensionAggregate....237
GetEffects....238
GetDimensionNames....238
GetRule....239
SetDimensionAggregate....239
SetRule....240
UsesDimension....240
CubeDefn Class Properties....241
CalcAggregates....241
Comments....241
DimensionCount....241
FormatType....241
IsVirtual....242
Name....242
ValueDimensionName....242
CubeCollectionDefn Class....242
CubeCollectionDefn Class Methods....243
AttachCube....243
DetachCube....243

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GetAggregateMapping....244
GetCubeNames....244
GetDimensionNames....245
GetDimSort....246
GetFieldMapping....246
GetFilter....247
GetPersistAggregate....248
SetAggregateMapping....248
SetDimSort....249
SetFieldMapping....250
SetFilter....251
SetPersistAggregate....251
UsesCube....252
UsesDimension....253
CubeCollectionDefn Class Properties....253
AggregateRecName....253
Comments....253
CubeCount....254
DimensionCount....254
Name....254
RecordName....254
UserFunctionDefn Class....254
UserFunctionDefn Class Methods....254
GetRule....255
SetRule....255
UserFunctionDefn Class Properties....255
Comments....256
Name....256
OrganizerDefn Class....256
OrganizerDefn Class Methods....256
AttachPart....256
DetachPart....257
GetPartNames....258
UsesPart....258
OrganizerDefn Class Properties....259
Comments....259
Name....259
RuleDefn Class....259
RuleDefn Class Methods....260
AddRuleExpression....260
GenerateRule....260
RuleDefn Class Property....261
RuleString....261
RuleExpressions Classes....261
Using the Constants Class....262
Assignment Class....262
Assignment Class Method....262
GenerateRule....262
Assignment Class Properties....263
Expression....263
Variable....263

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Comparison Class....263
Comparison Class Method....264
GenerateRule....264
Comparison Class Properties....265
Operand1....265
Operand2....265
Type....265
Constant Class....266
Constant Class Method....267
GenerateRule....267
Constant Class Properties....267
Type....267
Value....268
Constants Class....268
Cube Class....268
Cube Class Methods....268
AddIndex....268
GenerateRule....269
GetIndexes....269
Cube Class Property....270
Name....270
ExpressionBlock Class....270
ExpressionBlock Methods....270
AddRuleExpression....270
GetRuleExpressions....271
FunctionCall Class....271
FunctionCall Class Methods....275
AddArgument....275
GenerateRule....276
GetArguments....276
FunctionCall Class Properties....277
Name....277
Type....277
MemberReference Class....277
MemberReference Class Method....277
GenerateRule....277
MemberReference Class Properties....278
Dimension....278
Member....278
Operation Class....278
Operation Class Method....279
GenerateRule....279
Operation Class Properties....280
Operand1....280
Operand2....280
Type....280
Variable Class....281
Variable Class Method....281
GenerateRule....281
Variable Class Properties....282
Name....282

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Type....282
Analytic Model Metadata Classes Examples....282
Creating an Analytic Model Code Example....282
Chapter 5: Analytic Grid Classes....287
Understanding the Analytic Calculation Engine Classes....287
Using the Analytic Grid in PeopleCode....287
Using Freeze Column Mode....288
Error Handling....289
Data Types of the Analytic Grid Objects....289
Scope of Analytic Grid Objects....289
AnalyticGrid Class Reference....290
AnalyticGrid Class Built-in Function....290
AnalyticGrid Class Methods....290
GetColumn....290
GetCubeCollection....291
LoadData....291
SetAnalyticInstance....292
SetLayout....292
AnalyticGrid Class Properties....293
Inactive....293
Label....293
ShowGridLines....294
SlicerVisible....294
SummaryText....294
Chapter 6: Analytic Type Classes....295
Understanding the Analytic Calculation Engine Classes....295
Using the Analytic Type Classes....295
Error Handling....296
Data Types of the Analytic Type Objects....296
Scope of Analytic Type Objects....296
How to Import the Analytic Type Classes....296
How to Create an Analytic Type Class Object....297
Analytic Type Classes Constructor....297
AnalyticTypeDefn....297
AnalyticTypeDefn Class Methods....298
AddModel....298
AddRecord....299
Create....299
CopyTo....300
Delete....300
DeleteModel....301
DeleteRecord....301
Get....302
GetModel....302
GetModelNames....303
GetRecord....303
GetRecordNames....304
Rename....304
Save....305
AnalyticTypeDefn Class Properties....305
AppClassPath....305

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Comments.... 305
Description.... 306
Name.... 306
OwnerID.... 306
AnalyticTypeModelDefn Class Properties.... 306
Name.... 306
Type.... 306
AnalyticTypeRecordDefn Class Methods.... 307
GetSelectedField.... 307
SetSelectedField.... 307
UnsetSelectedField.... 308
AnalyticTypeRecordDefn Class Properties.... 308
Callback.... 308
Description.... 309
Name.... 309
Readable.... 309
ReadOnce.... 309
ScenarioManaged.... 309
SyncOrder.... 309
Writeable.... 310
AnalyticType Classes Example.... 310
Chapter 7: Application Classes.... 311
Understanding Application Classes.... 311
When Would You Use Application Classes?.... 311
Application Classes General Structure.... 312
Class Name.... 312
Class Extension.... 313
Declaration of Public External Interface.... 314
Access Control and the Declaration of Protected Properties and Methods.... 315
Declaration of Private Instance Variables and Methods.... 317
Definition of Methods.... 318
Declaration of Abstract Methods and Properties.... 321
Interfaces.... 322
Constructors.... 322
External Function Declarations.... 324
Naming Standards.... 326
Naming Packages.... 326
Naming Classes.... 326
Naming Methods.... 326
Naming Properties.... 326
Import Declarations.... 327
Self-Reference.... 328
Using %This with Constructors.... 329
Properties and Constants.... 330
Differentiating Between Properties and Methods.... 330
Overriding Properties.... 331
Using Get and Set with Properties.... 332
Using Read-Only Properties.... 332
Using Methods and Properties for Collections.... 333
Declaring Constants.... 333
Using Variables in Application Classes.... 333

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Placement of Variable Declarations.... 334
Declaring Private Instance Variables.... 334
Global Variables.... 334
Overriding Variables and Properties.... 334
Superclass Reference.... 334
Downcasting.... 335
Exception Handling.... 336
Commenting and Documenting Application Classes.... 337
Understanding Comments and Documentation.... 337
Method Header Comments.... 338
Class Header Comments.... 339
Designing Base Classes.... 339
Base Classes.... 339
Abstract Base Classes.... 339
Generic Base Classes.... 340
Utility Classes.... 340
Declaration of Application Classes.... 340
Declaring Application Classes.... 341
Importing Class Names.... 341
Referencing Superclasses.... 341
Declaring Private Methods.... 341
Scope of an Application Class.... 341
Application Classes Built-in Functions and Language Constructs.... 341
Class.... 342
Get.... 343
Import.... 344
Interface.... 345
Method.... 346
Set.... 346
Chapter 8: Application Data Set Classes.... 349
Understanding the Application Data Set Classes.... 349
Importing Application Data Set Classes.... 350
AdsValidationBase Class.... 350
AdsValidationBase Class Methods.... 351
AdsValidationBase.... 351
DoADSValidations.... 351
OnPreCopyCompare.... 353
OnPreUpdate.... 354
OnPostCopy.... 355
ReportErrorModified.... 357
Chapter 9: API Repository.... 363
Understanding the PeopleSoft API Repository.... 363
The PeopleSoft API Repository.... 363
Example of Accessing the Repository Using PeopleCode.... 364
Example of Accessing the Repository by Using Visual Basic.... 367
Repository Properties.... 369
Bindings.... 369
Namespaces.... 369
Bindings Collection Properties.... 369
Count.... 369
Bindings Collection Methods.... 369

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Item.... 370
Bindings Properties.... 370
Name.... 370
Bindings Methods.... 370
Generate.... 370
Namespaces Collection Properties.... 371
Count.... 371
Namespaces Collection Methods.... 371
Item.... 371
ItemByName.... 372
Namespaces Properties.... 372
Classes.... 372
Name.... 373
Namespaces Methods.... 373
CreateObject.... 373
ClassInfo Collection Properties.... 373
Count.... 373
ClassInfo Collection Methods.... 374
Item.... 374
ItemByName.... 374
ClassInfo Properties.... 375
Documentation.... 375
Methods.... 375
Name.... 375
Properties.... 375
MethodInfo Collection Properties.... 376
Count.... 376
MethodInfo Collection Methods.... 376
Item.... 376
ItemByName.... 377
MethodInfo Properties.... 377
Arguments.... 377
Documentation.... 377
Name.... 378
Type.... 378
PropertyInfo Collection Properties.... 378
Count.... 378
PropertyInfo Collection Methods.... 379
Item.... 379
ItemByName.... 379
PropertyInfo Properties.... 380
Documentation.... 380
Name.... 380
Type.... 380
Usage.... 381
Chapter 10: Array Class.... 383
Understanding Arrays.... 383
Creating Arrays.... 383
Populating an Array.... 384
Removing Items From an Array.... 385
Creating Empty Arrays.... 386

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Creating and Populating Multi-Dimensional Arrays....386
Using Flattening and Promotion....388
Declaring Array Objects....389
Understanding the Scope of an Array Object....389
Array Class Built-in Functions....389
Array Class Methods....389
Clone....389
Find....390
Get....391
Join....392
Next....394
Pop....395
Push....396
Replace....397
Reverse....399
Set....399
Shift....400
Sort....401
Subarray....403
Substitute....403
Unshift....404
Array Class Properties....405
Dimension....405
Len....406
Chapter 11: BI Publisher Classes....407
Understanding BI Publisher and the BI Publisher Classes....407
BI Publisher Terms....408
BI Publisher Flow Diagram....409
Error Handling....409
Data Type and Scope of BI Publisher Objects....410
Instantiating BI Publisher Objects....410
Search Operator Values....410
BI Publisher Classes Reference....411
BI Publisher Report Manager Definition Classes....411
ReportDefn Class....411
ReportDefn Class Constructor....412
ReportDefn....412
ReportDefn Class Methods....412
Close....412
DisplayOutput....413
Get....413
GetOutDestFormatString....414
GetPSQueryPromptRecord....415
PrintOutput....415
ProcessReport....416
Publish....417
SetPSQueryPromptRecord....418
SetRuntimeDataXMLFile....418
SetRuntimeProperties....419
ReportDefn Class Properties....420
Description....420

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

DestinationPrinter.... 421
FolderName....421
OutDestination.... 421
OutDestinationType.... 421
ProcessInstance.... 422
ReportFileName.... 422
Status....422
UseBurstValueAsOutputFileName.... 423
BI Publisher Report Manager Search Classes....423
Report Class.... 423
Report Class Constructor.... 423
Report....423
Report Class Properties....424
contentId.... 425
CreatedDateTime.... 425
DatabaseName.... 425
Description.... 425
ExpireDate.... 425
FileURL.... 425
FolderName....426
ProcessInstanceID.... 426
ReportInstanceID.... 426
ReportName.... 426
ReportURL....426
ReportManager Class.... 427
ReportManager Class Constructor.... 427
ReportManager....427
ReportManager Class Methods....427
AddSearchFieldCriteria.... 428
GetReportList....428
SetBurstFieldCriteria.... 429
SetCaseSensitive.... 429
SetDateCriteria....430
SetFolderCriteria....430
SetProcessInstanceCriteria....431
SetReportIDCriteria.... 431
SetUserIdCriteria.... 432
SearchAttribute Class....432
SearchAttribute Class Constructor....432
SearchAttribute.... 432
SearchAttribute Class Properties.... 433
attrName....433
attrValue.... 433
compareOp....433
BI Publisher Engine Classes....434
PageNumber Class.... 434
PageNumber Class Constructor.... 434
PageNumber....434
PageNumber Class Properties....435
BackgroundFile....435
FontName....435

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

FontSize.... 436
PositionX....436
PositionY....436
StartFromPageNum....437
StartNum.... 437
PDFMerger Class....437
PDFMerger Class Constructor....437
PDFMerger....438
PDFMerger Class Method.... 438
MergePDFs.... 438
PDFMerger Class Properties....439
ConfProp.... 439
Locale....439
PageNumber....440
Watermark.... 440
Properties Class....441
Properties Class Constructor....441
Properties.... 441
Properties Class Methods....441
GetProperty.... 442
SetProperty....442
Watermark Class.... 443
Watermark Class Constructor.... 443
Watermark.... 444
Watermark Class Properties....444
ImageFile.... 444
ImageFileLowerLeftX.... 444
ImageFileLowerLeftY.... 445
ImageFileUpperRightX....445
ImageFileUpperRightY....445
PageIndex....445
Text....445
TextAngle....445
TextFontName....446
TextFontSize.... 446
TextStartPosX.... 446
TextStartPosY.... 446
Understanding the DigitalCertStore Class....446
DigitalCertStore Class Methods.... 447
DigitalCertStore.... 447
ExtractCertificateByAuthorizedRole.... 447
ExtractCertificateByAuthorizedUser.... 448
ExtractCertificateByDigitalID.... 449
getDigitalCertFileNameByDigitalID....450
getDigitalIdBySigner.... 451
getEncPassword.... 452
getListOfAuthorizedRoleNames....453
getListOfAuthorizedUsers.... 453
getListOfDigitalId....454
getListOfSigner....454
getSignerByDigitalId.... 455

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

isDigitalCertValid....456
DigitalCertStore Class Properties....456
ErrorMessageDetail....456
ErrorMessageSet....456
Understanding the IPDFSignature Interface Class....456
IPDFSignature Class Methods....458
getErrorString....458
getSignatureId....459
IPDFSignature Class Properties....461
KeyFieldNames....461
KeyFieldValues....462
OperatorId....462
ProcessInstance....462
ReportId....462
secStore....462
UseSameSignatureForBursting....463
BI Publisher Classes Example....464
Generating and Publishing a Report....464
Chapter 12: BPEL Classes....467
Understanding the BPEL Classes....467
Scope of the BPEL Classes....467
Data Types of the BPEL Classes....467
How to Import the BPEL Classes....468
How to Create a BPEL Object....468
BPEL Classes Constructors....468
AsyncFFSend....469
BPELUtil....469
IBUtil....469
AsyncFFSend Class....470
AsyncFFSend Class Method....470
OnRequestSend....470
BPELUtil Class....471
BPELUtil Class Methods....471
GetASyncBPELProcessInstanceUrl....471
GetBPELProcessBrowserUrl....471
GetOperationType....472
GetSyncBPELProcessInstanceUrl....472
LaunchASyncBPELProcess....473
LaunchSyncBPELProcess....474
UpdateConnectorResponseProperties....474
IBUtil Class....475
IBUtil Class Methods....476
GetBPELConsoleUrl....476
GetBPELDomain....476
GetMessageId....477
GetNode....477
GetNumberOfRoutings....478
GetStatus....478
GetTransactionId....478
Chapter 13: Business Interlink Class....481
Understanding Business Interlink Class....481

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Using the Interlink Object.... 481
Deciding Which Methods to Use.... 482
Executing the Business Interlink Object.... 482
Supporting Batch Input and Output.... 482
Supporting Rowsets.... 483
Using the Flat Table Methods.... 483
Supporting Dynamic Output.... 483
Using Hierarchical Data (BIDocs).... 483
Using the Incoming Business Interlink Methods and Properties.... 487
Understanding the State of an Interlink Object.... 487
Using Business Interlink with Application Engine.... 488
Using the Data Type of a Business Interlink Object.... 488
Understanding the Scope of a Business Interlink Object.... 488
Business Interlink Class Built-in Functions.... 489
Business Interlink Class Methods.... 489
AddDoc.... 489
AddInputRow.... 490
AddNextDoc.... 491
AddValue.... 493
BulkExecute.... 495
Clear.... 500
Execute.... 501
FetchIntoRecord.... 503
FetchIntoRowset.... 505
FetchNextRow.... 508
GetCount.... 509
GetDoc.... 510
GetFieldCount.... 512
GetFieldType.... 513
GetFieldValue.... 514
GetInputDocs.... 515
GetNextDoc.... 516
GetOutputDocs.... 518
GetPreviousDoc.... 519
GetStatus.... 521
GetValue.... 522
InputRowset.... 524
MoveFirst.... 526
MoveNext.... 527
MoveToDoc.... 528
ResetCursor.... 529
Incoming Business Interlink Methods.... 530
AddAttribute.... 530
AddComment.... 531
AddProcessInstruction.... 532
AddText.... 533
CreateElement.... 534
GenXMLString.... 534
GetAttributeName.... 535
GetAttributeValue.... 536
GetNode.... 537

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ParseXMLString.... 538
Incoming Business Interlink Properties....539
AttributeCount.... 539
ChildNodeCount.... 539
NodeName.... 540
NodeType....541
NodeValue....541
Business Interlink Class Property....542
StopAtError....542
Configuration Parameters....542
Interlink Plug-in Configuration Parameters....543
URL Configuration Parameter.... 543
BIDocValidate Configuration Parameter....544
Chapter 14: Charting Classes....545
Understanding the Charting Classes....545
Creating PeopleSoft Charts....549
Creating a Chart on a Page....550
Creating a Chart Using an iScript....552
Special Considerations for Charts.... 552
Component Processor Considerations....553
Translation Considerations.... 553
Text Considerations for the Chart Class.... 553
Text Considerations for the Gantt Class.... 562
Text Considerations for the Gauge Classes.... 562
Considerations for Using Touch-Friendly Mobile Devices.... 563
Styling PeopleSoft Charts.... 563
Accessibility Settings for Charts....565
WSRP Considerations.... 567
Using the Chart Class....567
Understanding Chart Class Terms....567
Creating Charts Using the Chart Class....568
Chart Class Chart Types....569
Chart Class Design Guidelines.... 570
Using the ReferenceArea Class....588
Using the ReferenceLine Class....590
Scope and Data Type of a Chart Object....591
Error Handling....591
Chart Class Methods and Properties by Category.... 591
Using the Gauge Classes.... 593
Understanding Gauge Terms....593
Gauge Types.... 593
Creating Gauges Using the Gauge Classes....596
Design Guidelines....596
Using the Threshold Class.... 600
Scope and Data Type of Gauge Objects....604
Error Handling....604
Properties of the Gauge Classes.... 604
Using the Gantt Class.... 605
Understanding Gantt Chart Terms.... 606
Using Gantt Charts in the PeopleSoft Pure Internet Architecture.... 607
Creating Gantt Charts Using the Gantt Class....608

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Specifying Time Line Axis Formats....609
Working with Start and End Dates....612
Using Gantt Glyphs....612
Scope and Data Type of a Gantt Object....613
Error Handling....614
Using the OrgChart Class....614
Understanding Organization Chart Terms....615
Using Organization Charts in the PeopleSoft Pure Internet Architecture....617
Creating Organization Charts Using the OrgChart Class....620
Overview of Creating an Organization Chart....621
Creating an Organization Chart....621
Displaying Breadcrumbs (Optional)....622
Defining Descriptors....623
Implementing Menus and Drop-Down Lists (Optional)....626
Configuring Related Action Menus....629
Configuring the Node Record for Drop-Downs....630
Configuring Drop-Downs....630
Populating the Drop-Down Rowset....631
Setting Drop-Down Styles....632
Configuring IM Presence (Optional)....633
Designing Organization Chart Nodes....635
Implementing Node Views (Optional)....641
Implementing Zoom Schemas (Optional)....643
Specifying Scroll Types....647
Configuring Connector Lines and Node Borders....648
Organization Chart Actions and Events....649
Organization Chart Subrecord Definitions....650
Minimum Methods and Properties....662
Scope and Data Type of an OrgChart Object....663
Using the RatingBoxChart Class....664
Understanding Rating Box Chart Terms....665
Using Rating Box Charts in PeopleSoft Applications....665
Creating Rating Box Charts Using the RatingBoxChart Class....666
Rating Box Chart Subrecord Definition....667
Minimum Methods....668
Minimum Properties....668
Using the QuadrantSchema Class....669
Data Type of a RatingBoxChart Object....670
Scope of a RatingBoxChart Object....671
Charting Classes Reference....671
Charting Classes Built-in Functions....672
Chart Class Methods....672
Refresh....672
Reset....673
SetColorArray....673
SetData....675
SetDataAnnotations....676
SetDataColor....677
SetDataGlyphScale....677
SetDataHints....678
SetDataSeries....682

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SetDataURLs.... 683
SetDataXAxis....684
SetDataYAxis....685
SetExplodedSectorsArray.... 686
SetFunnelDataActual.... 687
SetFunnelDataTarget....688
SetGlyphArray.... 688
SetLegend....689
SetOLData....690
SetOLDataAnnotations.... 691
SetOLDataGlyphScale.... 691
SetOLDataSeries....691
SetOLDataXAxis.... 692
SetOLDataYAxis....692
SetReferenceArea....693
SetReferenceLine.... 693
SetXAxisLabels.... 694
SetYAxisLabels....694
Chart Class Properties....695
AdditionalStyleSuffix.... 695
AnimationDuration.... 695
AnimationType....696
DataStartRow.... 697
DataWidth.... 697
FootNote.... 698
FunnelPercentMeasure....698
GridLines.... 698
GridLineType....698
HasLegend.... 699
Height....699
HighlightSelectedDataPoint....699
ImageMap.... 700
IsChartDrillable....700
IsDrillable....700
IsLineChartLineSmoothing....701
IsPlainImage....701
IsTrueXY....701
IsXAxisInteger....702
IsYAxisInteger.... 702
LegendMaxEntries.... 702
LegendPosition....703
LegendStyle.... 703
LineChartDataGlyphSize.... 703
LineType.... 704
MainTitle....704
MainTitleOrient....704
MainTitleStyle....704
OLLineType.... 704
OLType....704
RevertToPre850.... 705
RotationAngle.... 705

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SetChartURL....705
ShowCrossHair....705
Style....705
StyleSheet....706
SubTitle....706
Type....706
Width....707
XAxisCross....707
XAxisCrossPoint....708
XAxisLabelOrient....708
XAxisMax....708
XAxisMin....708
XAxisPrecision....709
XAxisScaleResolution....709
XAxisStyle....709
XAxisTicks....709
XAxisTitle....709
XAxisTitleOrient....710
XAxisTitleStyle....710
XRotationAngle....710
YAxisCrossPoint....710
YAxisLabelOrient....711
YAxisMax....711
YAxisMin....711
YAxisPrecision....712
YAxisScaleResolution....712
YAxisStyle....712
YAxisTicks....712
YAxisTitle....712
YAxisTitleOrient....712
YAxisTitleStyle....713
YRotationAngle....713
ZRotationAngle....713
ReferenceArea Class Properties....713
Association....713
Description....714
IsDisplayedTextInLegend....714
ReferenceAreaColor....714
ReferenceAreaLocation....716
ReferenceAreaValues....716
ShortText....716
ReferenceLine Class Properties....716
Association....717
Description....717
IsDisplayedTextInLegend....717
ReferenceLineColor....717
ReferenceLineLocation....719
ReferenceLineValue....719
ShortText....719
DialGauge Class Methods....719
Refresh....719

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SetThreshold.... 720
DialGauge Class Properties.... 720
AdditionalStyleSuffix.... 720
AnimationDuration.... 721
AnimationType.... 721
BottomLabel.... 722
BottomLabelPosition.... 722
GaugeDecimalDigit.... 723
GaugeMaximum.... 723
GaugeMinimum.... 723
GaugeURL.... 723
Height.... 724
IsDrillable.... 724
LegendPosition.... 724
MajorTickIncrement.... 725
MetricLabelPosition.... 725
MetricLabelType.... 726
MinorTickIncrement.... 726
TickLabelPosition.... 727
TopLabel.... 727
TopLabelPosition.... 727
Type.... 728
Width.... 729
LEDGauge Class Methods.... 729
Refresh.... 729
SetThreshold.... 730
LEDGauge Class Properties.... 730
AdditionalStyleSuffix.... 730
AnimationDuration.... 731
AnimationType.... 731
BottomLabel.... 732
BottomLabelPosition.... 732
GaugeDecimalDigit.... 732
GaugeURL.... 733
Height.... 733
IsDrillable.... 733
LegendPosition.... 734
MetricLabelPosition.... 734
MetricLabelType.... 735
TopLabel.... 735
TopLabelPosition.... 735
Type.... 736
Width.... 737
StatusMeterGauge Class Methods.... 737
Refresh.... 737
SetThreshold.... 738
StatusMeterGauge Class Properties.... 738
AdditionalStyleSuffix.... 738
AnimationDuration.... 739
AnimationType.... 739
BottomLabel.... 740

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

BottomLabelPosition.... 740
GaugeDecimalDigit.... 741
GaugeMaximum.... 741
GaugeMinimum.... 741
GaugeURL.... 741
Height.... 742
IsDrillable.... 742
LegendPosition.... 742
MajorTickIncrement.... 743
MetricLabelPosition.... 743
MetricLabelType.... 744
MinorTickIncrement.... 744
TopLabel.... 745
TopLabelPosition.... 745
Type.... 745
Width.... 746
Threshold Class Properties.... 746
Colors.... 746
Descriptions.... 748
Id.... 748
Values.... 748
Gantt Class Methods.... 749
Refresh.... 749
Reset.... 750
SetActualEndDate.... 750
SetActualStartDate.... 751
SetActualTaskBarColor.... 751
SetChartArea.... 752
SetDayFormat.... 752
SetHourFormat.... 753
SetMinuteFormat.... 753
SetMonthFormat.... 754
SetPlannedEndDate.... 755
SetPlannedStartDate.... 755
SetPlannedTaskBarColor.... 756
SetSecondFormat.... 756
SetTableXScrollbar.... 757
SetTaskAppData.... 757
SetTaskAppDataTitles.... 758
SetTaskBarURL.... 758
SetTaskData.... 759
SetTaskDependencyChildID.... 759
SetTaskDependencyData.... 760
SetTaskDependencyParentID.... 761
SetTaskDependencyType.... 761
SetTaskDependencyURL.... 762
SetTaskDrill.... 763
SetTaskExpanded.... 764
SetTaskID.... 764
SetTaskLabel.... 764
SetTaskLevel.... 765

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SetTaskMilestone....766
SetTaskName....767
SetTaskProgress....767
SetTaskProgressBarColor....768
SetWBSNumbering....768
SetYearFormat....769
Gantt Class Properties....770
AxisEndDateTime....770
AxisStartDateTime....770
DataStartRow....770
DataWidth....770
GridLines....770
GridLineType....771
Height....772
ImageMap....772
InteractiveEnd....772
InteractiveMove....772
InteractiveProgress....773
InteractiveStart....773
IsDrillable....773
IsPlainImage....774
PixelsPerRow....774
RevertToPre850....774
ShowTaskLabels....774
Style....774
StyleSheet....775
TaskDependencyLineType....775
TaskMilestoneGlyph....775
TaskTitle....776
Width....776
OrgChart Class Methods....776
SetCrumbData....776
SetCrumbRecord....777
SetDropdownData....777
SetDropdownRecord....777
SetIMData....778
SetIMRecord....778
SetLegend....779
SetLegendImg....780
SetNodeData....780
SetNodeDisplayDataRecord....780
SetNodeDisplayData....781
SetNodeRecord....781
SetNodeViewEntries....782
SetNodeViewText....783
SetPopUpNodeData....783
SetPopUpNodeRecord....784
SetSchemaLevels....784
OrgChart Class Properties....785
CenterFocusNode....785
ChartCurrentSchemaLevel....786

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ChartScrollType.... 786
Collapsed_Msg.... 787
CollapsedImage.... 787
CollapseMainIconSpace.... 787
CrumbDescrStyle.... 788
CrumbMaxDisplayLength.... 788
CrumbSeparatorImage.... 788
DefaultImage.... 788
Direction.... 789
DropDownBoxStyle.... 789
Expanded_Msg.... 789
ExpandedImage.... 790
FocusNodeStyle.... 790
HasLegend.... 790
Height.... 790
ImageHeight.... 791
ImageLocation.... 791
ImageMouseoverMagnificationFactor.... 791
IMPresence.... 792
IMRefreshInterval.... 792
InitialView.... 792
LegendPosition.... 793
LegendStyle.... 793
LegendTopSpace.... 793
MainTitle.... 793
MainTitleStyle.... 794
MaxDropdownDisplayItem.... 794
MaxPopupDisplayNode.... 794
NodeDescr1Style.... 794
NodeDescr2Style.... 795
NodeDescr3Style.... 795
NodeDescr4Style.... 795
NodeDescr5Style.... 796
NodeDescr6Style.... 796
NodeDescr7Style.... 796
NodeMaxDisplayDescLength.... 797
NodeProportion.... 797
OptimizeHorizontalSpace.... 798
OptimizeVerticalSpace.... 798
PopupHeaderStyle.... 799
PopupNodeDescr1Style.... 799
PopupNodeDescr2Style.... 799
PopupNodeDescr3Style.... 799
PopupNodeDescr4Style.... 800
PopupNodeDescr5Style.... 800
PopupNodeDescr6Style.... 800
PopupNodeDescr7Style.... 801
PopupNodeDescr8Style.... 801
Style.... 801
SuppressPeopleCodeOnNode.... 801
SuppressPeopleCodeOnImage.... 802

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

UnlinkCrumbDescrStyle....802
VerticalSpace....802
Width....803
SchemaLevel Class Properties....803
ID....803
ImageHeight....803
RatingBoxChart Class Methods....803
SetLegend....803
SetLegendImg....804
SetQuadrantSchemas....804
SetRBNodeData....805
SetRBNodeRecord....806
SetXAxisLabels....806
SetYAxisLabels....806
RatingBoxChart Class Properties....807
BoxMaxDisplayItems....807
DraggedNodeStyle....807
EnableRelatedActions....808
GridLineType....808
HasLegend....809
Height....809
IconOnlySelectedQuadrantStyle....809
IsDragable....810
LegendPosition....810
MainTitle....810
MainTitleStyle....810
NDMaxDisplayDescLength....811
PopUpHeaderStyle....811
PopUpHeight....812
PopUpStyle....812
PopUpWidth....812
SelectedQuadrantStyle....813
ShowAxisLabels....813
ShowNodeDescription....813
Style....814
ViewAllStyle....814
Width....814
XAxisBoxNum....814
XAxisLabelStyle....815
XAxisTitle....815
XAxisTitleStyle....815
YAxisBoxNum....816
YAxisLabelStyle....816
YAxisTitle....816
YAxisTitleStyle....816
QuadrantSchema Class Properties....817
LabelPosition....817
LabelStyle....817
LabelText....818
XRating....818
YRating....818

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Charting Examples....818
Creating a Chart Using the Chart Class....819
Creating a Gantt Chart....845
Creating an Organization Chart....848
Creating a Rating Box Chart....852
Creating a Chart Using an iScript....854
Chapter 15: Component Interface Classes....857
Understanding Component Interface Class....857
Life Cycle of a Component Interface....858
Setting Component Interface Keys....859
Standard and User-Defined Component Interface Methods....860
Accessing Component Interface Standard Properties....861
Accessing User-Defined Component Interface Properties....862
Data Type of a Component Interface Object....862
Scope of a Component Interface Object....863
Implementing a Component Interface....863
Component Interface Methods and Timeouts....864
Traversing a Component Interface and Using Data Collections....864
Working With Effective-Dated Data....866
How a Developer Uses GetEffectiveItem....866
Reusing Existing Code....867
Differences in Search Dialog Processing....867
Differences in PeopleCode Event and Function Behavior....867
Using %Menu Conditions....868
Session Class Methods....868
FindCompIntfcs....868
GetCompIntfc....869
ValidateCompIntfc....869
Component Interface Collection Methods....870
First....870
Item....871
Next....871
Component Interface Collection Property....871
Count....872
Component Interface Class Methods....872
Cancel....872
CopyRowset....872
CopyRowsetDelta....874
CopySetupRowset....876
CopySetupRowsetDelta....878
Create....880
Find....881
Get....881
GetPropertyByName....882
Save....883
SetPropertyByName....884
Component Interface Class Properties....885
ComponentName....885
CreateKeyInfoCollection....885
EditHistoryItems....885
FindKeyInfoCollection....886

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GetDummyRows....886
GetHistoryItems....886
GetKeyInfoCollection....887
InteractiveMode....887
PropertyInfoCollection....888
StopOnFirstError....888
Data Collection Methods....888
CurrentItem....888
DeleteItem....889
GetEffectiveItem....891
GetEffectiveItemNum....891
InsertItem....892
Item....893
ItemByKeys....893
Data Collection Properties....894
Count....895
CurrentItemNumber....895
Data Item Class Property....895
ItemNum....895
Accessing the Structure of a Component Interface....896
CompIntfPropInfoCollection Collection....896
CompIntfPropInfoCollection Collection Methods....898
First....898
Item....898
Next....899
CompIntfPropInfoCollection Collection Properties....899
Count....899
CompIntfPropInfoCollection Object Properties....899
Format....900
IsCollection....900
IsReadOnly....901
Key....901
LabelLong....901
LabelShort....901
Length....901
Name....902
Prompt....902
PropertyInfoCollection....902
Required....902
Type....903
Xlat....903
YesNo....903
Component Interface Examples....904
Create a New Instance of Data Example....904
Getting an Existing Instance of Data Example....906
Retrieving a List of Instance of Data Example....908
Inserting Effective-Dated Data Example....910
Inserting Effective-Dated Data Example Using Visual Basic....912
Inserting or Deleting a Row of Data Example....913
Chapter 16: Connected Query Classes....919
Understanding the Connected Query Classes....919

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Importing Connected Query Classes....919
CONQRSMGR Class....920
CONQRSMGR Class Constructor....920
CONQRSMGR....920
CONQRSMGR Class Methods....920
CleanOutputFile....920
Close....921
CopyDefn....921
DeleteDefn....922
ExistsByName....922
GetSampleXMLString....922
Open....923
ResetQueriesPrompt....923
Run....924
RunToWindow....925
RunToXMLFormattedString....925
Save....926
SaveRunControlParms....926
SetRunControlData....927
Validate....927
ValidateIfFieldsMapped....928
ValidateRunControlParms....928
CONQRSMGR Class Properties....929
Const....929
Description....929
Details....929
ErrString....929
ExecutionLog....930
IgnoreRelFldOutput....930
IsChanged....930
IsDebugMode....930
IsInit....931
IsPublic....931
LastUpdatedBy....931
LastUpdateDTTM....931
MaxRowsPerQuery....932
Name....932
ObjectRowset....932
OprID....932
OutProcessFileName....933
PropertyArray....933
QueriesPromptsArray....935
QueryArray....935
RegisteredBy....935
RegisteredDTTM....935
RunCntlId....935
RunControlParArray....936
RunMode....936
SchedInfo....938
SchedRequestType....939
SecProfile....939

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ShowFormattedXML.....939
Status.....940
XMLDataFileName.....940
XMLDataFullName.....940
CONQRSPROPERTY Class.....940
CONQRSPROPERTY Class Properties.....941
PROPDEFAULT.....941
PROPNAME.....941
PROPVALUE.....941
PROPVALUEARRAY.....941
PROPVALUEARRAYDESC.....941
CONQRS_CONST Class.....942
CONQRS_CONST Class Properties.....942
InitExisting.....942
InitNew.....942
MsgSet.....943
RunCntlId_Auto.....943
RunMode_Prev.....943
RunMode_Prev_DefRowNumber.....944
RunMode_Sample.....944
RunMode_Sched_File.....944
RunMode_Sched_Web.....944
RunMode_Window.....945
RunMode_XMLFormattedString.....945
SchedRequest_CQR.....945
SchedRequest_XMLP.....946
Stat_Active.....946
Stat_InActive.....946
Stat_InProgress.....946
QUERYITEMPROMPT Class.....946
QUERYITEMPROMPT Class Properties.....947
QueryName.....947
QueryPromptRecord.....947
SCHED_INFO Class.....947
SCHED_INFO Class Properties.....947
AE_ID.....948
DIRLOCATION.....948
OPRID.....948
OUTDESTTYPE.....948
PRCSFILENAME.....949
PROCESS_INSTANCE.....949
RUN_CNTL_ID.....949
SEC_PROFILE Class.....949
SEC_PROFILE Class Constructor.....949
SEC_PROFILE.....950
SEC_PROFILE Class Properties.....950
CanCreatePublic.....950
CanModify.....950
CanRunQuery.....950
UTILITY Class.....950
UTILITY Class Constructor.....951

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

UTILITY....951
UTILITY Class Methods....951
CheckQryForTreePrompt....951
CheckQrySecurity....952
GetQueryScopeByName....952
ValidateObjectID....953
Connected Query Classes Examples....953
Running a Connected Query in Scheduled Mode....953
Running a Connected Query in Preview Mode or Background Mode....955
Iterating Through a Connected Query Opened for Editing....956
Chapter 17: Crypt Class....959
Understanding the Crypt Class....959
Creating a Crypt Object....959
Declaring Crypt Objects....959
Scope of a Crypt Object....959
Crypt Class Methods....959
FirstStep....960
GoToStep....960
LoadLibrary....961
NextStep....961
Open....962
SetParameter....962
UpdateData....963
Crypt Class Properties....963
Result....963
Verified....963
Chapter 18: Document Classes....965
Understanding the Document Classes....965
Data Type and Scope of the Document Classes....965
Document Classes Built-in Functions....965
Document Class....966
Document Class Methods....966
GenJsonString....966
GenXmlString....967
GetDocumentKey....967
GetElement....968
GetRowset....968
GetSchema....969
ParseJsonString....970
ParseXmlFromFile....970
ParseXmlFromURL....971
ParseXmlString....971
UpdateFromRowset....972
ValidateData....972
Document Class Properties....973
DocumentElement....973
DocumentKey Class....973
DocumentKey Class Methods....973
SetDocumentKey....973
DocumentKey Class Properties....974
GetDocumentName....974

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GetVersion....975
PackageName....975
Primitive Class....975
Primitive Class Methods....975
GetEnumName....975
GetParent....976
GetPath....976
Primitive Class Properties....977
ElementType....977
EnumCount....977
IsChanged....977
IsInitialized....977
IsRequired....978
MaxDefinedDecimalLength....978
MaxDefinedLength....978
Name....978
OrigValue....978
PrimitiveSubType....979
PrimitiveType....980
SequenceNumber....981
Value....981
Compound Class....981
Compound Class Methods....981
GetParent....981
GetPath....982
GetPropertyByIndex....982
GetPropertyByName....983
GetUniqueKey....983
Compound Class Properties....984
ElementType....984
IsChanged....984
IsInitialized....984
IsRequired....984
Name....984
PropertyCount....985
SequenceNumber....985
Collection Class....985
Collection Class Methods....985
AppendItem....985
CreateItem....986
DeleteItem....987
GetItem....987
GetParent....988
GetPath....988
InsertItem....989
Collection Class Properties....989
CollectionElementType....989
Count....990
DefinedMaxOccurs....990
DefinedMinOccurs....990
ElementType....990

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

IsChanged.... 990
IsInitialized....991
IsRequired.... 991
Name.... 991
SequenceNumber.... 991
Chapter 19: Exception Class....993
Understanding Exception Class.... 993
How Exceptions Are Thrown....993
When to Use Exceptions.... 993
Try-Catch Blocks.... 995
Data Type for Exception Class Objects.... 996
Scope of Exception Class Objects....996
Exception Class Built-in Functions.... 996
Exception Class Methods....996
GetSubstitution....996
Output.... 997
SetSubstitution.... 998
ToString....998
Exception Class Properties.... 999
Context....999
DefaultText....999
MessageNumber....999
MessageSetNumber.... 1000
MessageSeverity.... 1000
StackTrace....1000
SubstitutionCount.... 1001
Chapter 20: Feed Classes.... 1003
Understanding the Feed Classes....1003
Importing Feed Classes....1005
Feed Class.... 1005
Feed Class Constructor.... 1005
Feed....1005
Feed Class Methods....1006
delete.... 1006
equals.... 1007
execute.... 1007
getAttribute.... 1008
load....1009
loadFromTemplate.... 1010
PopulateDSParamsWithDefaults.... 1010
populatePrefData....1011
publishToSites....1011
resetFeedAttributes.... 1012
resetFeedSecurities....1013
save.... 1013
saveAs....1014
saveAsTemplate.... 1014
setAttribute....1015
setDataSourceById....1016
unpublishFromSites.... 1017
Feed Class Properties....1017

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Authorized....1017
CategoryID....1018
CreateDTTM....1018
CreateNode....1018
CreateOprID....1018
CreatePortal....1018
DataSource....1018
DataTypeID....1019
Description....1019
FeedAttributes....1019
FeedAuthorizationOprID....1019
FeedAuthorizationOprPWD....1019
FeedAuthorizationType....1020
FeedCacheTime....1020
FeedCacheType....1020
FeedContentUrl....1020
FeedFactory....1020
FeedFormat....1021
FeedSecurities....1021
FeedSecurityType....1021
FeedTemplate....1022
FeedUrl....1022
HasAdminParams....1022
HasUserParams....1022
IBOperationName....1022
ID....1023
LastPubDTTM....1023
LastUpdDTTM....1023
LastUpdOprID....1023
NameSpaceID....1023
ObjectType....1024
OperatingMode....1024
OwnerID....1024
PublishedInSites....1025
Title....1025
Utility....1025
FeedFactory Class....1025
FeedFactory Class Constructor....1026
FeedFactory....1026
FeedFactory Class Methods....1026
convertFeedLinksToHoverMenu....1026
convertFeedLinksToOPML....1027
createFeed....1028
deleteFeed....1028
genFeedUrl....1029
genUniqueFeedId....1029
getAllPagedFeedLinks....1030
getCategory....1031
getDataSource....1031
getFeed....1032
getFeedDoc....1034

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

getFeedLink.... 1034
getFeedLinks.... 1035
getFeedTemplates.... 1035
getRelatedFeedsHoverMenu.... 1036
getRelativePageLinkForFeed.... 1037
FeedFactory Class Properties.... 1038
DataSources.... 1038
Feeds.... 1038
Utility.... 1039
DataSource Class.... 1039
DataSource Class Constructor.... 1039
DataSource.... 1039
DataSource Class Methods.... 1040
addParameter.... 1040
equals.... 1041
getAttributeById.... 1041
getContentUrl.... 1042
getDataSecurity.... 1043
getParameterById.... 1043
getParameterDetail.... 1044
getSettingById.... 1044
getSettingDetail.... 1045
isCurrentUserAdmin.... 1045
isCurrentUserAuthorized.... 1046
onDelete.... 1046
onSave.... 1047
resetParameters.... 1047
DataSource Class Properties.... 1047
AdminPersonalizationPage.... 1048
AllowCustomParameters.... 1048
AllowRealTimeFeedSecurity.... 1048
DataSourceType.... 1048
DefaultFeedAttributes.... 1048
DefaultIBOperationName.... 1048
Description.... 1049
HasParameters.... 1049
HasSettings.... 1049
IBOperations.... 1049
ID.... 1049
LongDescription.... 1049
ObjectType.... 1050
Parameters.... 1050
ParametersCompleted.... 1050
Parent.... 1050
PortalSpecificPersonalization.... 1050
Settings.... 1050
SettingsCompleted.... 1051
UserPersonalizationPage.... 1051
Utility.... 1051
DataSourceParameter Class.... 1051
DataSourceParameter Class Constructor.... 1052

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

DataSourceParameter....1052
DataSourceParameter Class Methods....1052
addUserValue....1052
clone....1053
equals....1053
resetUserValues....1053
setRangeFromFieldTranslates....1054
validateValue....1054
DataSourceParameter Class Properties....1055
AllowChangesToRequired....1055
DefaultValue....1055
DefaultValueForDisplay....1055
Description....1055
EditType....1056
EvaluatedValue....1056
FieldType....1056
ID....1057
Name....1057
ObjectType....1057
Parent....1057
PromptTable....1058
Range....1058
Required....1058
SkipValidityChecks....1058
UsageType....1058
UserValues....1059
Utility....1059
Value....1060
ValueForDisplay....1060
DataSourceParameterValue Class....1060
DataSourceParameterValue Class Constructor....1060
DataSourceParameterValue....1060
DataSourceParameterValue Class Methods....1061
clone....1061
equals....1061
DataSourceParameterValue Class Properties....1062
Description....1062
ID....1062
Name....1062
ObjectType....1062
OrderNumber....1062
Parent....1063
Value....1063
DataSourceSetting Class....1063
DataSourceSetting Class Constructor....1063
DataSourceSetting....1063
DataSourceSetting Class Methods....1064
clone....1064
equals....1064
setRangeFromFieldTranslates....1065
DataSourceSetting Class Properties....1065

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

DefaultValue....1065
DisplayOnly....1065
EditType....1065
Enabled....1066
FieldType....1066
ID....1067
LongName....1067
Name....1067
ObjectType....1067
Parent....1067
PromptTable....1068
Range....1068
RefreshOnChange....1068
RelatedFieldValue....1068
Required....1068
ShowRelatedField....1068
Utility....1069
Value....1069
Visible....1069
Utility Class....1070
Utility Class Constructor....1070
Utility....1070
Utility Class Methods....1070
dateStringToUserPref....1070
datetimeToString....1071
dateToString....1071
decodeXML....1071
encodeXML....1072
evaluateSysVar....1073
genNameSpaceID....1074
getExceptionText....1074
getFeedDoc....1074
getFeedMimeType....1075
getFieldTranslates....1076
getNodeValue....1076
getUserDateFormat....1077
getUserDatetimeFormat....1077
getUserInfo....1078
httpStringToDatetime....1078
join....1078
join2D....1079
setMessageHeadersAndMimeType....1080
setNodeValue....1080
showException....1081
showInvalidValueException....1081
split....1082
split2D....1083
stringToDate....1083
stringToDatetime....1084
validateSysVar....1084
viewStringAsAttachment....1085

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Utility Class Properties....1085
ATTACHMENT_URL....1085
AUTHTYPE_PERM....1086
AUTHTYPE_ROLE....1086
DSPARAMETER_INCREMENTAL....1086
DSPARAMETER_MAXROW....1086
DSPARAMETER_SF_MAXMINUTES....1087
DSPARAMETER_SF_PAGING....1087
EDITTYPE_NOTABLEEDIT....1087
EDITTYPE_PROMPTTABLE....1087
EDITTYPE_TRANSLATETABLE....1088
EDITTYPE_YESNO....1088
FEEDATTRIBUTE_AUTHOR....1088
FEEDATTRIBUTE_CLOUD....1088
FEEDATTRIBUTE_COMPLETE....1088
FEEDATTRIBUTE_CONTRIBUTOR....1089
FEEDATTRIBUTE_COPYRIGHT....1089
FEEDATTRIBUTE_EXPIRES....1089
FEEDATTRIBUTE_ICONURL....1089
FEEDATTRIBUTE_LOGOURL....1089
FEEDATTRIBUTE_MANAGINGEDITOR....1089
FEEDATTRIBUTE_MAXAGE....1090
FEEDATTRIBUTE_PERSINSTRUCTION....1090
FEEDATTRIBUTE_RATING....1090
FEEDATTRIBUTE_SKIPDAYS....1090
FEEDATTRIBUTE_SKIPHOURS....1090
FEEDATTRIBUTE_TEXTINPUT....1090
FEEDATTRIBUTE_TTL....1091
FEEDATTRIBUTE_WEBMASTER....1091
FEEDATTRIBUTE_XSL....1091
FEEDAUTHTYPE_ALL....1091
FEEDAUTHTYPE_ANONYMOUS....1091
FEEDAUTHTYPE_DEFAULT....1091
FEEDCACHETYPE_NONE....1092
FEEDCACHETYPE_PRIVATE....1092
FEEDCACHETYPE_PUBLIC....1092
FEEDCACHETYPE_ROLE....1092
FEEDFORMAT_ATOM10....1092
FEEDSECUTYPE_PUBLIC....1092
FEEDSECUTYPE_REALTIME....1093
FEEDSECUTYPE_SELECTED....1093
FEEDTEMPLATE_NO....1093
FEEDTEMPLATE_YES....1093
FEEDTYPE_DYNAMIC....1093
FEEDTYPE_PREPUBLISHED....1094
FIELDTYPE_CHARACTER....1094
FIELDTYPE_DATE....1094
FIELDTYPE_DATETIME....1094
FIELDTYPE_LONGCHARACTER....1094
FIELDTYPE_NUMBER....1094
FIELDTYPE_SIGNEDNUMBER....1095

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

FIELDTYPE_TIME....1095
IBSOTYPE_ASYNC....1095
IBSOTYPE_SYNC....1095
IBSOTYPE_UNKNOWN....1095
ICONURL_FEED_A....1095
ICONURL_FEED_IA....1096
INCREMENTALOPTION_NO....1096
INCREMENTALOPTION_YES....1096
LINKTYPE_FIRST....1096
LINKTYPE_LAST....1097
LINKTYPE_NEXT....1097
LINKTYPE_PREVIOUS....1097
MIMETYPE_ATOM....1097
MIMETYPE_OPML....1098
MIMETYPE_XML....1098
OPERATINGMODE_AUTHORIZATION....1098
OPERATINGMODE_DEFAULT....1098
OPERATINGMODE_DELETION....1098
OPERATINGMODE_EXECUTION....1099
OPERATINGMODE_EXECUTION_NOENTRY....1099
QUERYPARAMETER_CHILDFEEDID....1099
QUERYPARAMETER_DATATYPEID....1099
QUERYPARAMETER_DEFLOCALNODE....1099
QUERYPARAMETER_DSSCOUNT....1100
QUERYPARAMETER_DSSNAME....1100
QUERYPARAMETER_DSSVALUE....1100
QUERYPARAMETER_FEEDFORMAT....1100
QUERYPARAMETER_FEEDID....1100
QUERYPARAMETER_FEEDLIST....1100
QUERYPARAMETER_FEEDTYPE....1101
QUERYPARAMETER_IBTRANSID....1101
QUERYPARAMETER_IFMODIFIEDSINCE....1101
QUERYPARAMETER_IFNONEMATCH....1101
QUERYPARAMETER_KEYWORD....1101
QUERYPARAMETER_LANGUAGE....1101
QUERYPARAMETER_NODENAME....1102
QUERYPARAMETER_PAGENUM....1102
QUERYPARAMETER_PORTALNAME....1102
QUERYPARAMETER_PTPPB_SEARCH_MODE....1102
QUERYPARAMETER_PTPPB_SEARCH_TEXT....1102
RequestInfo....1102
SF_MAXMINUTES_ALLMSGS....1103
SF_MAXROWOPTION_ALLMSGS....1103
SF_MAXROWOPTION_LATESTMSG....1103
SF_PAGINGOPTION_NOPAGING....1104
SF_PAGINGOPTION_SEGMENTED....1104
SYSVAR_INVALID....1104
USAGETYPE_ADMINSPECIFIED....1105
USAGETYPE_FIXED....1105
USAGETYPE_INTERNAL....1105
USAGETYPE_NOTUSED....1105

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

USAGETYPE_SYSVAR....1105
USAGETYPE_USERSPECIFIED....1105
XMLCHILDELEMENTS_CLOUD....1106
XMLCHILDELEMENTS_PERSON....1106
XMLCHILDELEMENTS_TEXTINPUT....1106
XMLELEMENT_DAY....1106
XMLELEMENT_DESCRIPTION....1107
XMLELEMENT_DOMAIN....1107
XMLELEMENT_EMAIL....1107
XMLELEMENT_HOUR....1107
XMLELEMENT_LINK....1107
XMLELEMENT_NAME....1107
XMLELEMENT_PATH....1108
XMLELEMENT_PORT....1108
XMLELEMENT_PROTOCOL....1108
XMLELEMENT_REGISTERPROCEDURE....1108
XMLELEMENT_TITLE....1108
FeedDoc Class....1108
FeedDoc Class Constructor....1109
FeedDoc....1109
FeedDoc Class Methods....1109
addCategory....1109
addEntry....1110
datetimeToString....1111
deleteCategory....1111
deleteEntry....1112
equals....1112
getEntry....1113
resetEntries....1113
stringToDatetime....1113
FeedDoc Class Properties....1114
AllowMoreEntries....1114
ApplicationRelease....1114
Categories....1114
ContentUrl....1115
Copyright....1115
Description....1115
Entries....1116
Expires....1116
FeedFormat....1116
FeedUrl....1116
FirstUrl....1117
Generator....1117
ID....1117
LastUrl....1117
Logo....1118
MaxAge....1118
MaxEntries....1118
NextUrl....1119
ObjectType....1119
PreviousUrl....1119

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

RootElement....1119
Title....1120
Updated....1120
FeedEntry Class....1120
FeedEntry Class Constructor....1120
FeedEntry....1121
FeedEntry Class Methods....1121
addCategory....1121
addContributor....1122
addEnclosure....1122
delete....1123
deleteCategory....1123
deleteContributor....1124
deleteEnclosure....1124
equals....1125
FeedEntry Class Properties....1125
Author....1125
Categories....1126
Comments....1126
ContentUrl....1126
Contributors....1126
Copyright....1127
Description....1127
Enclosures....1127
Expires....1127
FeedDoc....1128
FullContent....1128
GUID....1128
ID....1128
MaxAge....1129
ObjectType....1129
Published....1129
Title....1129
Updated....1130
Additional Feed Examples....1130
Implementing a Real-Time Feed Request Handler....1130
Chapter 21: Field Class....1133
Understanding the Field Class....1133
Considerations Using User Interface Properties....1133
Shortcut Considerations....1133
Data Type for a Field Object....1134
Scope of a Field Object....1134
Field Class Built-in Functions....1134
Field Class Methods....1134
AddDropDownItem....1134
AddFFClass....1136
ClearDropDownList....1136
GetAuxFlag....1137
GetDNDField....1137
GetDNDRow....1138
GetDNDRowset....1139

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GetDNDTargetField....1139
GetDNDTargetRow....1140
GetDNDTargetRowset....1141
GetLongLabel....1141
GetRelated....1142
GetShortLabel....1143
ReplaceFFClass....1144
SearchClear....1145
SetCursorPos....1146
SetDefault....1146
SetGroupletActionUrl....1147
SetGroupletDisplayIn....1148
SetGroupletID....1148
SetGroupletImage....1149
SetGroupletMOptions....1149
SetGroupletTargetID....1150
SetGroupletTimer....1150
SetGroupletType....1151
SetGroupletUrl....1152
Field Class Properties....1152
DataAreaCollapsed....1152
DecimalPosition....1153
DisplayFormat....1154
DisplayOnly....1155
DisplayZero....1155
DisplayZeroChanged....1155
Draggable....1156
Droppable....1156
EditError....1157
Enabled....1157
FieldLength....1157
FormatLength....1158
FormattedValue....1158
FreeFormStyleName....1159
HoverText....1159
HtmlAttributes....1160
HtmlInputType....1160
IsAltKey....1161
IsAuditFieldAdd....1161
IsAuditFieldChg....1161
IsAuditFieldDel....1161
IsAutoUpdate....1162
IsChanged....1162
IsDateRangeEdit....1162
IsDescKey....1162
IsDuplKey....1162
IsEditTable....1163
IsEditXlat....1163
IsFromSearchField....1163
IsHyperlink....1163
IsInBuf....1163

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

IsKey....1164
IsListItem....1164
IsNotUsed....1164
IsRequired....1165
IsRichTextEnabled....1165
IsSearchItem....1165
IsSystem....1165
IsThroughSearchField....1165
IsUseDefaultLabel....1166
IsYesNo....1166
JavaScriptEvents....1166
Label....1166
LabelImage....1167
LongTranslateValue....1168
MessageNumber....1168
MessageSetNumber....1169
MouseOverMsgNum....1169
MouseOverMsgSet....1170
Name....1170
OriginalValue....1170
ParentRecord....1171
PlaceholderText....1171
PromptTableName....1171
SearchDefault....1171
SearchEdit....1172
SetComponentChanged....1173
ShortTranslateValue....1173
ShowRequiredFieldCue....1174
SmartZero....1174
SqlText....1175
StoredFormat....1175
Style....1176
Type....1177
Value....1177
Visible....1178
Chapter 22: File Class....1181
Understanding File Layout....1181
Data Type of a File Object....1181
Scope of a File Object....1181
File Security Considerations....1182
File Access Interruption Recovery....1182
Plain Text Files....1183
Automatic PeopleCode Generation....1184
End Of Line Considerations....1185
File Layout Error Processing....1185
Working With Relative Paths....1186
File Class Built-in Functions....1187
File Class Methods....1187
Close....1187
CreateRowset....1188
Delete....1189

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GetBase64StringFromBinary....1190
GetPosition....1190
GetString....1191
Open....1192
ReadLine....1197
ReadRowset....1198
SetFileId....1200
SetFileLayout....1202
SetPosition....1203
SetRecTerminator....1204
WriteBase64StringToBinary....1204
WriteLine....1205
WriteRaw....1206
WriteRecord....1207
WriteRowset....1209
WriteString....1211
File Class Properties....1211
CurrentRecord....1212
IgnoreInvalidId....1212
IsError....1213
IsNewFileId....1213
IsOpen....1214
Name....1214
TerminateLines....1214
UseSpaceForNull....1215
ZeroExtend....1217
File Layout Examples....1218
WriteRecord Example....1219
ReadRecord Example....1221
WriteRowset Example....1223
ReadRowset Example....1225
File Rowset Considerations....1226
Application Engine Example....1227
Multiple File Layouts....1229
Reading Multiple File Layouts....1230
Writing Multiple File Layouts....1232
Chapter 23: Grid Classes....1235
Understanding Grid and GridColumn Classes....1235
Shortcut Considerations....1235
The Grid Class in PeopleCode....1236
Data Type for a Grid or Grid Column Object....1237
Scope of a Grid or Grid Column Object....1237
Grid Class Built-in Function....1237
Grid Class Methods....1237
EnableColumns....1237
GetColumn....1238
LabelColumns....1240
SetProperties....1240
SetRowHeader....1241
ShowColumns....1242
Grid Class Properties....1243

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

FreeFormStyleName.... 1243
gridcolumn.... 1244
Label.... 1244
Layout.... 1244
PersistMenuOption.... 1245
RowHighlight.... 1246
SummaryText.... 1246
GridColumn Class.... 1247
GridColumn Class Properties.... 1247
Enabled.... 1247
Label.... 1248
Name.... 1248
RowHeader.... 1248
Visible.... 1249
Chapter 24: Internet Script Classes (iScript).... 1251
Understanding Internet Script Classes.... 1251
URL vs. URI.... 1252
Web Libraries.... 1252
iScript Security.... 1254
When to Use an iScript.... 1254
Style Sheets and Styles.... 1255
Other Considerations.... 1255
Details of an iScript URL.... 1256
The Generate Functions.... 1256
Error Handling.... 1258
Scope of the Internet Script Classes.... 1258
Data Types of the iScript Classes.... 1258
Internet Script Classes.... 1259
Request Class.... 1259
Response.... 1259
Cookies.... 1259
Internet Script Classes Built-in Functions.... 1260
Request Class Methods.... 1260
FormFactor.... 1261
GetContentBody.... 1261
GetCookieNames.... 1262
GetCookieValue.... 1262
GetDeviceInfo.... 1262
GetHeader.... 1265
GetHeaderNames.... 1265
GetHelpURL.... 1265
GetParameter.... 1266
GetParameterNames.... 1266
GetParameterValues.... 1266
Request Class Properties.... 1266
AuthTokenDomain.... 1267
AuthType.... 1267
BrowserDeviceFormFactor.... 1267
BrowserDeviceType.... 1268
BrowserFluidCapable.... 1269
BrowserPlatform.... 1269

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

BrowserPlatformClass.... 1269
BrowserType.... 1270
BrowserTypeClass.... 1270
BrowserVersion.... 1270
ByPassSignOn.... 1270
ContentURI.... 1271
ExpireMeta.... 1271
ExtraLarge.... 1271
FullURI.... 1272
HTTPMethod.... 1272
Large.... 1272
LogoutURL.... 1273
Medium.... 1273
PathInfo.... 1273
Protocol.... 1274
QueryString.... 1274
RelativeURL.... 1274
RemoteAddr.... 1274
RemoteHost.... 1274
RequestURI.... 1275
RemoteUser.... 1275
Scheme.... 1276
ServerName.... 1276
ServerPort.... 1276
ServletPath.... 1277
Small.... 1277
Timeout.... 1277
Response Class.... 1277
Response Class Methods.... 1278
Clear.... 1278
CreateCookie.... 1278
GetCookie.... 1278
GetCookieNames.... 1279
GetHeader.... 1279
GetHeaderNames.... 1279
GetImageURL.... 1279
GetJavaScriptURL.... 1280
GetStyleSheetURL.... 1281
RedirectURL.... 1281
SetContentType.... 1282
SetHeader.... 1282
UseSimpleURL.... 1282
Write.... 1283
WriteLine.... 1283
Response Class Properties.... 1284
Charset.... 1284
DefaultStyleSheetName.... 1284
Cookie Class.... 1284
Cookie Class Properties.... 1284
Domain.... 1284
MaxAge.... 1285

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Name....1285
Path....1285
Secure....1285
Value....1286
Chapter 25: Java Class....1287
Understanding Java Class....1287
Supported Versions of Java....1287
Java Packages and Classes Delivered with PeopleTools....1287
System Setup for Java Classes....1288
From PeopleCode to Java....1289
State Management Concerns....1289
CreateJavaObject Example....1290
CreateJavaArray Example....1291
GetJavaClass Example....1291
From Java to PeopleCode....1291
SysVar Java Class....1292
SysCon Java Class....1292
Func Java Class....1292
Name Java Class....1292
Accessing PeopleCode Objects....1292
Using Application Classes From Java to PeopleCode....1294
PeopleCode and Java Data Types Mapping....1295
Considerations When Using the PeopleCode Java Functions....1296
Copying Arrays of Data Between PeopleCode and Java....1296
Considerations Working with the Java Garbage Collector....1297
Error Handling and the PeopleCode Java Functions....1297
The Java Debugging Environment....1298
Data Type of a Java Object....1298
Scope of a Java Object....1299
PeopleCode Java Built-in Functions....1299
Chapter 26: Mail Classes....1301
Understanding PeopleSoft MultiChannel Framework Mail Classes....1301
PeopleSoft MultiChannel Framework Mail Classes....1301
Scope of the Mail Classes....1301
Data Types of the Mail Classes....1302
Importing Mail Classes....1302
Creating a Mail Object....1303
Using the Mail Classes....1303
General Lifecycle of an Outbound Email....1303
Delivery Status Notification and Return Receipts....1304
Priority....1304
MCFBodyPart and MCFEmail Considerations....1305
Retrieving Email From a Mail Server With the MCFGetMail Class....1307
Structure of Rowset Used for Email Information....1307
Error Messages Returned by MCFGetMail Class Methods....1312
Mail Classes Constructors....1314
MCFBodyPart....1314
MCFGetMail....1314
MCFOutboundEmail....1314
MCFMailStore....1314
SMTPSession....1314

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

MCFBodyPart Class....1314
MCFBodyPart Class Methods....1315
AddHeader....1315
GetHeader....1316
GetHeaderCount....1316
GetHeaderName....1317
GetHeaderNames....1317
GetHeaderValues....1318
GetUnparsedHeaders....1318
SetAttachmentContent....1319
MCFBodyPart Class Properties....1320
AttachmentURL....1321
Charset....1321
ContentType....1321
Description....1321
Disposition....1322
Filename....1322
FilePath....1322
FilePathType....1323
IsAttachment....1323
MultiPart....1323
Text....1324
MCFEmail Class....1324
MCFEmail Class Properties....1324
BCC....1324
BounceTo....1324
CC....1325
From....1325
Importance....1325
Priority....1325
Recipients....1326
RefIDs....1326
ReplyIDs....1326
ReplyTo....1326
Sender....1327
Sensitivity....1327
Subject....1327
Text....1327
MCFGetMail Class Methods....1328
CreateQuarantineFolder....1328
GetCount....1328
GetEmailCount....1329
ReadAllEmailHeadersWithAttach....1330
ReadEmails....1331
ReadEmailsWithAttach....1331
ReadEmailsWithUID....1332
ReadEmailWithAttach....1333
ReadHeaders....1334
RemoveEmail....1334
RemoveEmails....1335
SetMCFEmail....1336

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

MCFGetMail Class Properties....1336
AttachmentRoot....1337
ContentTypes....1337
ErrorCount....1337
IBNode....1338
MailServer....1338
Password....1338
QuarantineCount....1339
QuarantineFolder....1339
Status....1340
UserID....1340
MCFInboundEmail Class....1340
MCFInboundEmail Class Methods....1340
DumpToFile....1340
GetAttachments....1342
GetFrom....1342
GetParts....1342
GetSender....1343
ReadFromDatabase....1343
SaveToDatabase....1344
MCFInboundEmail Class Properties....1344
AttachList....1344
AttachSizes....1345
DttmReceived....1345
DttmSaved....1345
DttmSent....1346
IBNode....1346
Language....1346
MessageID....1346
NotifyCC....1347
NotifyTo....1347
OffsetReceived....1347
OffsetSent....1347
Server....1347
Size....1348
Status....1348
UID....1348
User....1348
MCFMailStore Class....1348
MCFMailStore Import Statements....1349
MCFMailStore Methods....1349
AuthorizeEmailAttach....1349
DeleteEmail....1350
RetrieveEmail....1350
StoreEmail....1351
MCFMailUtil Class....1352
MCFMailUtil Class Methods....1352
DecodeText....1352
DecodeWord....1353
EncodeText....1354
EncodeWord....1356

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GetErrorMsgParam.... 1357
IsDomainNameValid.... 1358
IsEmailServerAvailable.... 1359
ParseRichTextHtml.... 1360
ValidateAddress.... 1360
MCFMailUtil Class Properties.... 1362
badaddresses.... 1362
ErrorDescription.... 1362
ErrorDetails.... 1362
ErrorMsgParamsCount.... 1363
imagesLocation.... 1363
MessageNumber.... 1363
MessageSetNumber.... 1364
MCFMultiPart Class.... 1364
MCFMultiPart Class Methods.... 1364
AddBodyPart.... 1364
GetBodyPart.... 1365
GetContentType.... 1365
GetCount.... 1365
MCFMultiPart Class Property.... 1366
SubType.... 1366
MCFOutboundEmail Class.... 1366
MCFOutboundEmail Class Methods.... 1366
AddAttachment.... 1366
AddHeader.... 1368
GetErrorMsgParam.... 1369
GetHeader.... 1369
GetHeaderCount.... 1370
GetHeaderName.... 1370
GetHeaderNames.... 1371
GetHeaderValues.... 1371
Send.... 1372
SetSMTPParam.... 1373
MCFOutboundEmail Class Properties.... 1374
BackupSMTPPort.... 1374
BackupSMTPServer.... 1374
BackupSMTPSSLClientCertAlias.... 1374
BackupSMTPSSLPort.... 1375
BackupSMTPUserName.... 1375
BackupSMTPUserPassword.... 1375
BackupSMTPUseSSL.... 1375
BCC.... 1376
BounceTo.... 1376
CC.... 1376
Charset.... 1376
ContentLanguage.... 1377
ContentType.... 1377
DefaultCharSet.... 1377
Description.... 1377
Disposition.... 1378
ErrorDescription.... 1378

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ErrorDetails....1378
ErrorMsgParamsCount....1379
Filename....1379
FilePath....1379
FilePathType....1379
From....1380
Importance....1380
InvalidAddresses....1381
IsAuthenticationReqd....1381
IsOkToSendPartial....1381
IsReturnReceiptReqd....1382
MessageNumber....1382
MessageSetNumber....1382
MultiPart....1382
Priority....1383
Recipients....1383
RefIDs....1383
ReplyIDs....1384
ReplyTo....1384
ResultOfSend....1384
Sender....1385
Sensitivity....1385
SMTPPort....1385
SMTPServer....1385
SMTPSSLClientCertAlias....1386
SMTPSSLPort....1386
SMTPUserName....1386
SMTPUserPassword....1386
SMTPUseSSL....1387
StatusNotifyOptions....1387
StatusNotifyReturn....1387
Subject....1388
Text....1388
TimeToWaitForResult....1388
UsedDefaultConfig....1388
UsedPrimaryServer....1389
ValidSentAddresses....1389
ValidUnsentAddresses....1389
SMTPSession Class....1389
SMTPSession Class Methods....1390
Send....1390
SendAll....1391
SetSMTPParam....1391
SMTPSession Class Properties....1392
BackupPort....1392
BackupServer....1392
BackupSSLClientCertAlias....1392
BackupSSLPort....1393
BackupUserName....1393
BackupUserPassword....1393
BackupUseSSL....1393

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

IsAuthenticationReqd....1394
Port....1394
Server....1394
SSLClientCertAlias....1394
SSLPort....1395
UsedDefaultConfig....1395
UsedPrimaryServer....1395
UserName....1395
UserPassword....1396
UseSSL....1396
Mail Classes Examples....1396
Creating a Text Email....1397
Creating Email and Overriding SMTP Settings....1398
Creating an HTML Email....1399
Creating a Multipart Email with Text and HTML Parts....1399
Creating an HTML Email with Images....1400
Creating an Email from Rich Text Editor Output....1402
Creating an Email with Attachments....1407
Creating Email Attachments by Specifying URLs....1409
Creating and Sending Multiple Email Messages....1410
Sending an Email With Authentication....1410
Using an SSL Connection to Send Email....1411
Chapter 27: MCF IM Classes....1413
Understanding the MCFIMInfo Class....1413
Using the MCFIMInfo Class....1413
Data Type for MCFIMInfo Objects....1413
Scope of MCFIMInfo Objects....1414
Understanding the MCFIMSingleButton Class....1414
Importing the MCFIMSingleButton Class....1414
MCFIMInfo Class Built-in Functions....1414
MCFIMInfo Class Methods....1414
AddUser....1414
CheckAll....1415
GetAdditionalUserInfo....1415
GetErrorImageName....1415
GetOffLineImageName....1416
GetOnlineImageName....1416
GetUnknownImageName....1416
GetLaunchURL....1417
GetStatus....1417
RemoveUser....1418
MCFIMSingleButton Class Methods....1418
generateHTML....1418
generateJavaScript....1420
insertXMPPServerUserData....1420
MCFIMSingleButton....1421
updateXMPPServerUserData....1421
MCFIMSingleButton Class Properties....1422
hideDelay....1422
Chapter 28: Message Classes....1423
Understanding Message Classes....1423

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Messages, Service Operations and Handlers.... 1423
Integration Broker Application Classes.... 1424
Data Types of Message Objects.... 1424
Scope of Message Objects.... 1425
Message Object Population.... 1425
Considerations When Populating a Rowset From a Message.... 1426
Considerations for Publishing and Subscribing to Partial Records.... 1428
Considerations When Subscribing to Character Fields.... 1428
Message Segments.... 1428
Content-Based Routing.... 1430
Error Handling.... 1432
Message Classes Reference.... 1433
Message Class Built-In Functions.... 1433
Message Class Methods.... 1433
Clone.... 1434
CopyPartRowset.... 1435
CopyRowset.... 1435
CopyRowsetDelta.... 1437
CopyRowsetDeltaOriginal.... 1438
CreateNextSegment.... 1441
DeleteSegment.... 1442
ExecuteEdits.... 1442
FirstCorrelation.... 1445
GenXMLPartString.... 1446
GenXMLString.... 1446
GetContentString.... 1447
GetDocument.... 1447
GetPartAliasName.... 1448
GetPartName.... 1449
GetPartRowset.... 1449
GetPartVersion.... 1450
GetPartXMLDoc.... 1450
GetQueryString.... 1451
GetRowset.... 1452
GetSegment.... 1453
GetURIDocument.... 1453
GetURIResource.... 1454
GetXmlDoc.... 1454
InBoundPublish.... 1455
LoadXMLPartString.... 1456
LoadXMLString.... 1456
OverrideURIResource.... 1457
Publish.... 1457
SegmentRestart.... 1459
SetContentString.... 1460
SetEditTable.... 1460
SetQueryString.... 1462
SetRESTCache.... 1462
SetStatus.... 1463
SetXmlDoc.... 1464
SyncRequest.... 1465

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Update....1466
UpdateSegment....1467
Message Class Properties....1468
ActionName....1468
AliasName....1468
ChannelName....1468
Cookies....1469
CurrentSegment....1470
DefaultMessageVersion....1470
DoNotPubToNodeName....1470
GUID....1471
HTTPMethod....1471
HTTPResponseCode....1472
IBException....1472
IBInfo....1472
InitializeConversationId....1473
IsActive....1473
IsBulkLoadTruncation....1474
IsDelta....1474
IsEditError....1475
IsLocal....1475
IsOperationActive....1476
IsParts....1476
IsPartsStructured....1476
IsRequest....1477
IsSourceNodeExternal....1477
IsStructure....1477
MessageDetail....1477
Name....1478
NRId....1478
OperationName....1478
OperationVersion....1478
ParentTransactionId....1478
PartCount....1479
PubID....1479
PubNodeName....1479
QueueName....1480
QueueSeqId....1480
ResponseStatus....1480
SegmentContentTransfer....1480
SegmentContentType....1481
SegmentCount....1482
SegmentsByDatabase....1482
Size....1482
SubName....1483
SubQueueName....1484
SubscriptionProcessId....1484
TransactionId....1485
URIResourceIndex....1485
Version....1485
IntBroker Class....1486

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

IntBroker Class Methods.... 1486
Cancel....1486
ConnectorRequest.... 1487
ConnectorRequestUrl....1488
DefaultLocalNode....1489
DefaultPortalName....1490
DeleteLayoutCache....1490
DeleteOrphanedSegments....1491
DeleteRESTCache.... 1491
GenLayoutHTML.... 1492
GetImageURL....1493
GetArchData.... 1494
GetArchIBInfoData....1494
GetIBInfoData....1495
GetIBTransactionIDforAE....1496
GetMessage....1496
GetMessageErrors....1497
GetMsgSchema.... 1498
GetSyncIBInfoData....1498
GetSyncLogData....1499
GetURL....1500
InBoundPublish....1502
IsOperationActive.... 1502
MAPLogout.... 1503
MsgSchemaExists.... 1503
Publish....1504
Resubmit.... 1505
SetMessageError.... 1506
SetStatus....1507
SwitchAsyncEventUserContext....1508
SyncRequest....1509
Update.... 1510
UpdateDocument.... 1511
UpdateXmlDoc.... 1511
IBInfo Class.... 1512
IBInfo Class Methods.... 1512
AddAEAttribute.... 1513
AddAttachment.... 1514
AddAttribute.... 1515
AddContainerAttribute....1515
ClearAEAttributes....1516
ClearAttachments....1517
ClearAttributes....1517
ClearContainerAttributes.... 1518
DeleteAEAttribute.... 1518
DeleteAttachment....1519
DeleteAttribute....1519
DeleteContainerAttribute....1520
GetAEAttributeName....1520
GetAEAttributeValue.... 1521
GetAttachmentContentID.... 1521

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GetAttachmentProperty.... 1522
GetAttributeName.... 1524
GetAttributeValue.... 1524
GetContainerAttributeName.... 1525
GetContainerAttributeValue.... 1526
GetNumberofAEAttributes.... 1526
GetNumberOfAttributes.... 1527
GetNumberOfContainerAttributes.... 1527
GetTransactionIDforAE.... 1528
InsertAEResponseAttributes.... 1528
LoadConnectorProp.... 1529
LoadConnectorPropFromNode.... 1530
LoadConnectorPropFromRouting.... 1530
LoadConnectorPropFromTrx.... 1531
LoadRESTHeaders.... 1531
SetAttachmentProperty.... 1532
IBInfo Class Properties.... 1533
AppServerDomain.... 1533
CompressionOverride.... 1534
ConnectorOverride.... 1534
ConversationID.... 1535
DeliveryMode.... 1535
DestinationNode.... 1535
ExternalMessageID.... 1536
ExternalOperationName.... 1536
ExternalUserName.... 1536
ExternalUserPassword.... 1536
FinalDestinationNode.... 1536
FuturePublicationDateTime.... 1537
HTTPSessionId.... 1537
IBConnectorInfo.... 1537
InReplyToID.... 1537
MessageChannel.... 1537
MessageName.... 1538
MessageQueue.... 1538
MessageType.... 1538
MessageVersion.... 1539
NodeDN.... 1539
NonRepudiationID.... 1539
NumberOfAttachments.... 1539
OperationType.... 1539
OperationVersion.... 1540
OrigNode.... 1540
OrigProcess.... 1540
OrigTimeStamp.... 1540
OrigUser.... 1540
PublicationID.... 1541
RequestingNodeName.... 1541
RequestingNodeDescription.... 1541
ResponseAsAttachment.... 1541
SegmentsUnOrder.... 1541

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SourceNode....1542
SyncServiceTimeout....1542
TransactionID....1543
UserName....1543
VisitedNodes....1543
WSA_Action....1543
WSA_FaultTo....1543
WSA_MessageID....1543
WSA_ReplyTo....1544
WSA_To....1544
IBConnectorInfo Collection....1544
IBConnectorInfo Collection Methods....1544
AddConnectorProperties....1544
AddQueryStringArg....1545
ClearConnectorProperties....1546
ClearQueryStringArgs....1546
DeleteConnectorProperties....1547
DeleteQueryStringArg....1547
GetConnectorPropertiesName....1548
GetConnectorPropertiesType....1548
GetConnectorPropertiesValue....1549
GetNumberOfConnectorProperties....1549
GetNumberOfQueryStringArgs....1549
GetQueryStringArgName....1550
GetQueryStringArgValue....1550
IBConnectorInfo Collection Properties....1550
ConnectorClassName....1551
ConnectorName....1551
Cookies....1551
PathInfo....1552
RemoteFrameworkURL....1552
Chapter 29: Mobile Application Platform (MAP) Classes....1553
Understanding Mobile Application Platform Classes....1553
Map Class Methods....1554
AddMetaTag....1554
DeleteMetaTag....1555
GetAJAXName....1555
GetAJAXNonSerializedData....1556
GetAJAXValue....1556
GetAJAXValueByName....1556
GetAuthToken....1557
GetAuthTokenDomain....1557
GetCSS....1558
GetDocument....1558
GetElement....1559
GetJavaScript....1559
GetMetaTagName....1560
GetNumberofAJAXParms....1560
GetNumberOfMetaTags....1561
GetPage....1561
GetPortaName....1562

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GetPortalNodeName.... 1562
GetURIDocument.... 1563
LoadState.... 1563
SetCSS.... 1564
SetJavaScript.... 1564
SetOvrdAJAXDocument.... 1565
StateExists.... 1565
ValidateSessionID.... 1566
Map Class Properties.... 1566
BrowserDeviceType.... 1567
BrowserPlatform.... 1567
LayoutName.... 1567
PSBackLabel.... 1567
PSBackOrigin.... 1568
PSBackURL.... 1568
RequestNodeFromToken.... 1568
StateEnabled.... 1569
StateID.... 1569
StateLoaded.... 1569
SystemStatus.... 1570
Title.... 1570
URIResourceIndex.... 1570
Validation.... 1571
MapPage Class Methods.... 1571
GetElement.... 1571
MapPage Class Properties.... 1572
BackButtonTheme.... 1572
Cache.... 1573
ContentClassName.... 1573
ContentStyle.... 1573
ContentTheme.... 1573
FormTransition.... 1574
ID.... 1575
IsExternalPage.... 1575
MainClassName.... 1575
MainStyle.... 1575
MainTheme.... 1576
Name.... 1576
PreLoad.... 1577
TemplateName.... 1577
Transition.... 1577
VisualBackButton.... 1578
MapElement Class Methods.... 1578
GetJavaScript.... 1578
GetListviewDefinedItemClass.... 1579
GetListviewDefinedItemHidden.... 1579
GetListviewDefinedItemStyle.... 1580
GetListviewItemClass.... 1581
GetListviewItemHidden.... 1581
GetListviewItemStyle.... 1582
GetMobileGridClass.... 1582

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GetMobileGridStyle....1583
SetJavaScript....1583
SetListviewDefinedItemClass....1584
SetListviewDefinedItemHidden....1585
SetListviewDefinedItemRowControl....1586
SetListviewDefinedItemStyle....1587
SetListviewDisableURL....1588
SetListviewItemClass....1588
SetListviewItemHidden....1588
SetListviewItemRowControl....1589
SetListviewItemStyle....1590
SetListviewRowControl....1590
SetMobileGridClass....1591
SetMobileGridStyle....1592
SetTableColumnProperty....1592
MapElement Class Properties....1593
AccessibilityText....1594
ActionSheetCloseButton....1594
AjaxURL....1594
ButtonAlternativeURL....1595
ButtonGroupControl....1595
ButtonIcon....1595
ButtonIconLocation....1596
ButtonInline....1596
ButtonLocation....1597
ButtonMini....1597
ButtonRemoveCorner....1597
ButtonRemoveIconShadow....1598
ButtonRemoveShadow....1598
ClassName....1598
ContClassName....1599
ContPopup....1599
ContPopupBtnTheme....1599
ContPopupButtonPos....1600
ContPopupIcon....1600
ContPopupIconLocation....1601
ContPopupOverlyTheme....1602
ContPopupPos....1602
ContPopupType....1603
Controls....1603
ContStyle....1604
ContTheme....1604
DialogCloseOption....1605
DialogOverlayTheme....1605
ElementType....1606
FixedDisplayFormat....1607
FlipToggleHighlight....1607
FlipToggleMini....1608
FlipToggleTrackTheme....1608
FullScreen....1608
GridOption....1609

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GridScroll....1609
GroupLabelText....1609
HideListviewSplitButton....1610
ImageOvrd....1610
InputMini....1610
InputRequired....1610
LabelID....1610
LabelText....1611
ListviewAlternativeURL....1611
ListviewCollapsed....1611
ListViewCollapsible....1611
ListviewCountTheme....1612
ListviewDividerDisplay....1612
ListViewDividerMsgCat....1613
ListviewFilterTheme....1613
ListviewHeaderTheme....1614
ListviewInset....1614
ListviewSplitIcon....1614
ListviewSplitTheme....1615
ListviewType....1616
ListviewURLJavaScript....1616
MenuIcon....1617
MenuIconLocation....1618
MenuInline....1618
MenuMini....1618
MenuMultiple....1618
MenuNonNative....1619
MenuOverlayTheme....1619
MenuRemoveCorner....1620
MenuRemoveShadow....1620
NoGridAutoWidth....1620
NoGridFilter....1620
NoGridInfo....1621
NoGridPageinate....1621
NoGridPageLengthChange....1621
NoGridSort....1621
PlugIn....1622
SaveNoPopup....1622
SaveRedirect....1622
SecureURL....1622
SideBarAnimationOff....1623
SideBarDisplay....1623
SideBarNoSwipeClose....1623
SideBarNotDismissible....1624
SideBarPosFixed....1624
SideBarPosRight....1624
SliderDefaultTrack....1624
SliderDisable....1625
SliderHighlight....1625
SliderMaximum....1625
SliderMini....1625

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SliderMinimum.....1625
SliderStep.....1626
SliderTrackTheme.....1626
Style.....1626
TableColumnHide.....1627
TableColumnPopupTheme.....1627
TableColumnTheme.....1628
TableColumnToggle.....1629
TableResponsive.....1629
TableStripe.....1629
TextSize.....1629
Theme.....1630
ThemeDivider.....1630
URLAlternativeURL.....1631
URLPost.....1631
URLSameWindow.....1631
URLType.....1632
MapFluid Class Methods.....1632
AddMenuItemToActionMenu.....1632
RemoveAction.....1633
RenderActionMenuHTML.....1634
UpdateSignOutURL.....1635
Chapter 30: Notification Classes.....1637
Understanding Notification Classes.....1637
Scope of the Notification Classes.....1637
Data Types of the Notification Classes.....1637
How to Import the Notification Classes.....1638
How to Create a Notification Object.....1638
Notification Classes Constructors.....1639
Notification.....1639
NotificationAddress.....1640
NotificationTemplate.....1641
Worklist.....1642
WorklistEntry.....1642
WSWorklistEntry.....1643
Notification Class.....1643
Notification Class Import Statements.....1643
Notification Class Method.....1644
Send.....1644
Notification Class Properties.....1644
ContentType.....1644
dttmCreated.....1645
EmailReplyTo.....1645
FileNames.....1645
FileTitles.....1645
language_cd.....1646
Message.....1646
NotifyBCC.....1646
NotifyCC.....1646
NotifyFrom.....1647
NotifyGuid.....1647

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

NotifyTo....1647
Rte....1647
SourceComponent....1647
SourceMarket....1648
SourceMenu....1648
Subject....1648
Template....1648
NotificationAddress Class....1648
NotificationAddress Class Properties....1649
Channel....1649
Description....1649
EmailId....1649
Language....1649
Oprid....1650
NotificationTemplate Class....1650
NotificationTemplate Class Methods....1650
GetAndExpandTemplate....1650
SetupCompVarsAndRcpts....1651
SetupGenericVars....1652
NotificationTemplate Class Properties....1652
ComponentId....1653
Instruction....1653
Language....1653
Market....1653
Priority....1653
Responses....1653
Subject....1654
TemplateId....1654
TemplateType....1654
Text....1654
Worklist Class....1654
Worklist Class Method....1655
Reassign....1655
WorklistEntry Class....1655
WorklistEntry Class Methods....1655
Create....1656
GetResponseStatus....1657
Reassign....1658
Save....1658
SaveWithCustomData....1659
SelectByKey....1660
SelectByMessageId....1661
Update....1662
WorklistEntry Class Properties....1662
actiondttm....1662
busactivity....1663
buseventname....1663
busprocname....1663
commentshort....1663
do_replicate_flag....1663
instanceid....1664

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

instselecteddttm....1664
inststatus....1664
insttimeoutddttm....1664
instworkeddttm....1665
IsCreatedViaWebService....1665
oprid....1665
originatorid....1665
prevoprid....1665
requestmessageid....1665
ResponseStatus....1666
syncid....1666
timedout....1666
transactionid....1667
url....1667
wl_priority....1667
wldaystoselect....1667
wldaystowork....1667
worklistname....1668
WSWorklistEntry Class....1668
WSWorklistEntry Class Methods....1668
OnError....1668
OnNotify....1669
WSWorklistEntry Class Properties....1669
InstanceID....1669
TransactionID....1669
Notification Classes Examples....1670
Creating a WorklistEntry....1670
Updating a WorklistEntry....1671
Chapter 31: Optimization PeopleCode....1673
Using Optimization PeopleCode on the Application Server....1673
Using Optimization PeopleCode in an Application Engine Program....1673
Performing Optimization in PeopleCode....1674
Creating New Analytic Instances....1674
Loading Analytic Instances Into an Analytic Server....1675
Running Optimization Transactions....1676
Invoking the Optimization PeopleCode Plug-In....1677
Shutting Down Optimization Engines....1677
Deleting Existing Analytic Instances....1678
Programming for Database Updates....1678
Using Lights-Out Mode with Optimization....1678
Understanding Lights-out Mode....1679
Creating a Request Message....1680
Creating a Response Message....1684
Editing the Request PeopleCode....1685
Editing the Response PeopleCode....1688
Optimization Built-in Functions....1690
CreateOptEngine....1690
CreateOptInterface....1692
DeleteOptProbInst....1693
GetOptEngine....1694
GetOptProbInstList....1695

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

InsertOptProbInst....1696
IsValidOptProbInst....1698
OptEngine Class Methods....1699
CheckOptEngineStatus....1699
FillRowset....1700
GetDate....1702
GetDateArray....1703
GetDateTime....1704
GetDateTimeArray....1704
GetNumber....1705
GetNumberArray....1706
GetString....1707
GetStringArray....1708
GetTime....1709
GetTimeArray....1710
GetTraceLevel....1711
RunAsynch....1712
RunSynch....1713
SetTraceLevel....1715
ShutDown....1716
OptEngine Class Properties....1718
DetailMsgs....1718
DetailedStatus....1719
OptBase Application Class....1719
OptBase Class Methods....1721
GetParmDate....1721
GetParmDateArray....1721
GetParmDateTime....1722
GetParmDateTimeArray....1722
GetParmNumber....1723
GetParmNumberArray....1723
GetParmInt....1724
GetParmIntArray....1724
GetParmString....1725
GetParmStringArray....1725
GetParmTime....1726
GetParmTimeArray....1726
Init....1727
OptDeleteCallback....1727
OptInsertCallback....1728
OptPostUpdateCallback....1729
OptPreUpdateCallback....1729
OptRefreshCallback....1730
SetOutputParmDate....1730
SetOutputParmDateArray....1731
SetOutputParmDateTime....1731
SetOutputParmDateTimeArray....1732
SetOutputParmNumber....1732
SetOutputParmNumberArray....1733
SetOutputParmInt....1733
SetOutputParmIntArray....1734

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SetOutputParmString....1734
SetOutputParmStringArray....1735
SetOutputParmTime....1735
SetOutputParmTimeArray....1736
OptInterface Class Methods....1736
ActivateModel....1737
ActivateObjective....1737
DeactivateModel....1738
DumpMsgToLog....1739
FindRowNum....1739
GetSolution....1740
GetSolutionDetail....1742
IsModelActive....1743
RestoreBounds....1743
SetVariableBounds....1744
SetVariableType....1746
Solve....1747
Chapter 32: Page Class....1749
Understanding Page Class....1749
Shortcut Considerations....1749
Data Type of a Page Object....1749
Scope of a Page Object....1749
Page Class Built-in Function....1750
Page Class Properties....1750
CopyURLLink....1750
CustomizePageLink....1750
DisplayOnly....1751
HelpLink....1751
Name....1751
NewWindowLink....1752
Visible....1752
Chapter 33: PeopleSoft Search Framework Classes....1753
Understanding the PeopleSoft Search Framework Classes....1753
Differences Between the PeopleSoft Search Framework Classes and Verity Search Classes....1753
Instantiating a SearchQuery Object....1754
Importing PeopleSoft Search Framework Classes....1754
Performing a Simple Search....1754
Exception Handling....1756
PeopleSoft Search Framework Classes Reference....1758
PeopleSoft Search Framework Classes Built-in Functions....1758
AssociatedFacet Class....1759
AssociatedFacet Class Methods....1759
getAssociatedFacetValue....1759
FacetFilter Class....1759
FacetFilter Class Methods....1760
clearFacetSorting....1760
FacetFilter....1760
getFacetSortings....1761
getFacetValuesSortType....1762
hasCustomFacetSorting....1762
sortFacetValuesAlphabetically....1762

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

sortFacetValuesByDocumentCount.... 1763
sortFacetValuesByType.... 1763
sortFacetValuesNumerically.... 1764
FacetFilter Class Properties.... 1764
AssociationValue.... 1765
FacetLabel.... 1765
FacetName.... 1765
Path.... 1765
FacetNode Class.... 1765
FacetNode Class Methods.... 1766
addChild.... 1766
FacetNode.... 1766
getChildNodes.... 1767
FacetNode Class Properties.... 1767
DisplayValue.... 1767
DocumentCount.... 1768
FacetValue.... 1768
HasChildren.... 1768
SearchAttribute Class.... 1768
SearchAttribute Class Methods.... 1769
SearchAttribute.... 1769
SearchAttribute Class Properties.... 1769
Display.... 1770
Name.... 1770
Type.... 1770
SearchCategory Class.... 1770
SearchCategory Class Methods.... 1770
GetAllAttributes.... 1771
GetConfiguredFilterAttributes.... 1771
GetFacetFilters.... 1771
GetLastIndexedDateTime.... 1772
GetNonConfiguredFilterAttributes.... 1772
GetRequestedAttributes.... 1773
GetRequestedFields.... 1773
SearchCategory.... 1774
SearchCategory Class Properties.... 1774
DataSourceNames.... 1775
Displayname.... 1775
Duplicates.... 1775
IsDeployed.... 1775
Name.... 1776
ServiceName.... 1776
SearchFactory Class.... 1776
SearchFactory Class Methods.... 1776
CreateQueryService.... 1776
SearchFactory.... 1777
SearchFactory Class Properties.... 1777
DEFAULTSERVICE.... 1778
SearchField Class.... 1778
SearchField Class Methods.... 1778
getAsDate.... 1778

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

getAsDateTime.... 1779
getAsInteger.... 1779
getAsNumber.... 1780
SearchField Class Properties.... 1780
Name.... 1780
Type.... 1780
Value.... 1781
SearchFieldCollection Class.... 1781
SearchFieldCollection Class Methods.... 1781
Count.... 1781
First.... 1782
Item.... 1782
ItemByName.... 1783
Next.... 1783
SearchFilter Class.... 1784
SearchFilter Class Methods.... 1784
setDateFilter.... 1784
setDateTimeFilter.... 1785
SearchFilter Class Properties.... 1785
Field.... 1785
FilterConnector.... 1786
Filters.... 1786
Operator.... 1786
Value.... 1787
SearchFilterGenerator Class.... 1787
SearchFilterGenerator Class Methods.... 1787
AddQueryFilter.... 1788
AfterDate.... 1788
BeforeDate.... 1789
ContainsPartialWord.... 1789
ContainsPhrase.... 1790
ContainsWord.... 1790
DateToDatetime.... 1791
EndMatchAll.... 1792
EndMatchAny.... 1792
EqualsDate.... 1793
EqualsNumber.... 1793
EqualsString.... 1794
GreaterThanEqualsNumber.... 1794
GreaterThanNumber.... 1795
LessThanEqualsNumber.... 1795
LessThanNumber.... 1796
MatchAll.... 1797
MatchAllReturnTrue.... 1797
MatchAny.... 1798
MatchAnyReturnTrue.... 1798
NotEqualsDate.... 1799
NotEqualsNumber.... 1800
NotEqualsString.... 1800
OnOrAfterDate.... 1801
OnOrBeforeDate.... 1801

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SearchFilterGenerator.....1802
SetQueryFilter.....1803
StringDateToDatetime.....1803
Search Filter Generator Examples.....1804
Creating Complex Filters.....1804
SearchQuery Class.....1806
SearchQuery Class Methods.....1806
BrowseFacetNodes.....1806
Execute.....1807
FormatDateFilter.....1809
FormatDateTimeFilter.....1809
SearchQuery Class Properties.....1810
Categories.....1810
ContainsAnyWords.....1810
ContainsExactPhrase.....1811
ClusteringSpecs.....1811
DocsRequested.....1811
EnableExtendedFilterOperators.....1812
FacetFilters.....1812
FilterConnector.....1812
Filters.....1813
GroupingSpec.....1813
IncludeImages.....1813
Language.....1814
MarkDuplicates.....1814
MaximumNumberOfFacetValues.....1814
MinimumDocumentsPerFacetValue.....1815
ProgrammaticSearchString.....1815
QueryText.....1815
RemoveDuplicates.....1815
RequestedFields.....1816
ReturnFacetValueCounts.....1816
SearchWithIn.....1816
SortFacetValuesBy.....1816
SortSpecs.....1817
StartIndex.....1817
TopN.....1817
WithoutWords.....1818
SearchQueryCollection Class.....1818
SearchQueryCollection Class Methods.....1818
addQuery.....1818
Count.....1819
ExecuteQuerys.....1819
First.....1820
Item.....1820
Next.....1820
SearchQueryService Class.....1821
SearchQueryService Class Methods.....1821
CreateQuery.....1821
CreateQueryCollection.....1822
ExecuteQuery.....1822

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ExecuteQuerys.... 1823
SearchResult Class.... 1823
SearchResult Class Methods.... 1824
GetCategoryNames.... 1824
GetContentLength.... 1824
GetCustomAttributes.... 1825
GetImageUrl.... 1825
GetLanguage.... 1826
GetLastModified.... 1826
GetScore.... 1827
GetSignature.... 1827
GetSummary.... 1828
GetTitle.... 1828
GetUrlLink.... 1828
HasDuplicate.... 1829
IsDuplicate.... 1829
SearchResultCollection Class.... 1830
SearchResultCollection Class Methods.... 1830
First.... 1830
GetDocumentCount.... 1831
GetDuplicatesMarked.... 1831
GetDuplicatesRemoved.... 1832
GetEstimatedHitCount.... 1832
GetFacetNodes.... 1833
GetQueryObject.... 1833
GetQueryText.... 1833
GetStartIndex.... 1834
Item.... 1834
Next.... 1835
SearchAuthnQueryFilter Class.... 1835
SearchAuthnQueryFilter Class Methods.... 1836
evaluateAttrValues.... 1836
Additional Search Examples.... 1837
Searching Using Facets.... 1837
Chapter 34: Portal Registry Classes.... 1841
Understanding the Portal Registry.... 1841
Folders.... 1841
Content References.... 1842
Nodes.... 1842
Security.... 1843
Attributes.... 1843
Additional Portal Objects.... 1843
Using the Portal Registry API.... 1844
Using Security.... 1844
Using Object Properties.... 1844
Accessing Objects.... 1845
Using PermissionValue, RolePermissionValue, Cascading Permissions and CascadingRolePermissions.... 1845
Working With ValidFrom and ValidTo.... 1848
Doing Error Handling.... 1848
Understanding the Life Cycle of a PortalRegistry Object.... 1849

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Viewing the PortalRegistry Class Hierarchy....1851
Using Content References....1856
UsageType....1857
TemplateType....1859
URLType....1859
Nodes and URL....1860
Naming Conventions....1861
Deleting Content Considerations....1861
Saving Content Considerations....1862
Data Type of a PortalRegistry Object....1863
Scope of a PortalRegistry Object....1863
PortalRegistry Reference....1863
Session Class Methods....1863
FindPortalRegistries....1864
GetActualRemoteNodes....1864
GetLocalNode....1865
GetNodes....1865
GetPortalRegistry....1866
GetRemoteNodes....1866
PortalRegistry Class....1867
PortalRegistry Class Methods....1867
Close....1867
CopyObject....1868
Create....1869
CreateContentRefLink....1870
CreateRemote....1871
Delete....1872
DeleteHomepage....1873
FindCRefByName....1873
FindCRefByURL....1874
FindCRefForURL....1875
FindCRefLinkByName....1876
FindFolderByName....1877
FindPgltByName....1878
GetAbsoluteContentURL....1879
GetDefaultHPTabOID....1879
GetQualifiedURL....1880
GrantPermissionForComponent....1880
GrantPermissionForScript....1881
Open....1882
PermissionListDelete....1883
PermissionListSaveAs....1883
RevokePermissionForComponent....1884
RevokePermissionForScript....1885
Save....1886
PortalRegistry Class Properties....1886
DefaultTemplate....1886
Description....1887
Favorites....1887
FolderNavObject....1887
Homepage....1888

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

IsFolderNavigation....1888
Name....1888
NodeTemplates....1888
OwnerId....1888
PageletCategories....1889
Portals....1889
RootFolder....1889
TabDefinitions....1889
TemplateObject....1890
PortalRegistry Collection....1890
PortalRegistry Collection Methods....1890
First....1890
Item....1890
Next....1891
PortalRegistry Collection Property....1891
Count....1891
Node Class....1892
Node Class Properties....1892
ActiveNode....1892
AppsRelease....1892
ContentURI....1892
DefaultPortalName....1893
Description....1893
IsDefault....1893
IsLocal....1893
Name....1894
NodePassword....1894
NodeType....1894
PortalURI....1894
ToolsRelease....1895
Node Collection....1895
Node Collection Methods....1895
First....1895
ItemByName....1896
Next....1896
Node Collection Property....1896
Count....1897
RemoteNode Collection....1897
RemoteNode Collection Methods....1897
First....1897
ItemByName....1898
Next....1898
RemoteNode Collection Property....1898
Count....1899
Portal Class....1899
Portal Class Method....1899
Save....1899
Portal Class Properties....1899
HostNodeName....1900
IsLocal....1900
Name....1900

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Portal Collection....1900
Portal Collection Methods....1900
First....1900
ItemByName....1901
Next....1901
Portal Collection Properties....1902
Count....1902
NodeTemplate Class....1902
NodeTemplate Class Properties....1902
DefaultTemplate....1902
Name....1903
TemplateObject....1903
NodeTemplate Collection....1903
NodeTemplate Collection Methods....1903
DeleteItem....1903
First....1904
InsertItem....1904
ItemByName....1905
Next....1905
NodeTemplate Collection Properties....1906
Count....1906
Folder Class....1906
Folder Class Method....1906
Save....1906
Folder Class Properties....1907
AbnContentProvider....1907
AbnDataSource....1907
AbnPeopleCode....1908
Attributes....1908
Author....1909
AuthorAccess....1909
Authorized....1909
CascadedPermissions....1909
CascadedRolePermissions....1910
ContentRefs....1910
CreationDate....1910
DefaultChartNavigation....1911
Description....1911
Folders....1911
IsMobile....1912
IsVisible....1912
Label....1912
Name....1912
OwnerId....1913
ParentName....1913
Path....1913
Permissions....1913
Product....1914
PublicAccess....1914
RolePermissions....1914
SequenceNumber....1914

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

TreeEffectiveDate.... 1915
TreeName.... 1915
TreeSetId.... 1916
TreeStructureName.... 1917
TreeUserKeyValue.... 1918
ValidFrom.... 1919
ValidTo.... 1919
Folder Collection.... 1919
Folder Collection Methods.... 1920
DeleteItem.... 1920
First.... 1920
InsertItem.... 1921
ItemByName.... 1921
Next.... 1922
Folder Collection Property.... 1922
Count.... 1923
Content Reference Class.... 1923
Content Reference Class Methods.... 1923
CreateLink.... 1923
Save.... 1924
Content Reference Class Properties.... 1925
AbsoluteContentURL.... 1925
AbsolutePortalURL.... 1925
AssignedPagelets.... 1925
Attributes.... 1925
Author.... 1926
AuthorAccess.... 1926
Authorized.... 1926
CascadedPermissions.... 1926
CascadedRolePermissions.... 1927
ContentProvider.... 1927
CreationDate.... 1928
Data.... 1928
Description.... 1928
HtmlText.... 1928
IsMobile.... 1929
IsVisible.... 1929
Label.... 1929
Links.... 1930
Name.... 1930
OwnerId.... 1930
ParentName.... 1930
Path.... 1931
Permissions.... 1931
Product.... 1931
PublicAccess.... 1931
QualifiedURL.... 1932
RelativeURL.... 1932
RolePermissions.... 1932
SequenceNumber.... 1933
StorageType.... 1933

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Template....1934
TemplateObject....1934
TemplateType....1935
URL....1935
URLType....1936
UsageType....1937
ValidFrom....1937
ValidTo....1937
Content Reference Collection....1938
Content Reference Collection Methods....1938
DeleteItem....1938
First....1939
InsertItem....1939
ItemByName....1940
Next....1941
Content Reference Collection Property....1941
Count....1941
AttributeValue Class....1941
AttributeValue Class Properties....1942
Label....1942
Name....1942
Translatable....1943
Value....1943
Attribute Collection....1943
Attribute Collection Methods....1944
DeleteItem....1944
First....1944
InsertItem....1945
ItemByName....1945
Next....1946
Attribute Collection Property....1946
Count....1946
PermissionValue Class....1947
PermissionValue Class Properties....1947
Cascade....1947
Name....1947
PermType....1948
PermissionValue Collection....1948
PermissionValue Collection Methods....1948
DeleteItem....1949
First....1949
InsertItem....1950
ItemByName....1950
Next....1951
PermissionValue Collection Property....1951
Count....1951
RolePermissionValue Collection....1951
RolePermissionValue Collection Methods....1952
DeleteItem....1952
First....1953
InsertItem....1953

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ItemByName....1954
Next....1954
RolePermissionValue Collection Property....1955
Count....1955
ContentReference Links....1955
ContentReference Links Methods....1955
Delete....1955
Save....1956
ContentReference Links Properties....1957
AbsoluteContentURL....1957
AbsolutePortalURL....1957
Attributes....1957
Author....1958
AuthorAccess....1958
Authorized....1958
CascadedPermissions....1958
CascadedRolePermissions....1959
ContentProvider....1959
CreationDate....1959
Data....1959
Description....1960
IsMobile....1960
IsVisible....1960
Label....1961
Name....1961
OwnerId....1961
ParentName....1961
Path....1962
Permissions....1962
Product....1962
PublicAccess....1962
RelativeURL....1963
RolePermissions....1963
SequenceNumber....1963
Template....1963
TemplateObject....1964
TemplateType....1964
URL....1965
URLType....1965
UsageType....1965
ValidFrom....1966
ValidTo....1966
Link Collection....1966
Link Collection Methods....1966
First....1966
Next....1967
Link Collection Property....1967
Count....1967
Link Class....1967
Link Properties....1967
LinksObjectName....1968

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

LinksObjectType....1968
LinksPortalName....1968
TabDefinition Class....1968
TabDefinition Class Methods....1968
Save....1968
TabDefinition Class Properties....1969
AssignedPagelets....1969
AvailableCategories....1969
AvailablePagelets....1970
Attributes....1970
Author....1970
AuthorAccess....1970
ColumnLayout....1970
CreationDate....1971
Description....1971
DynamicCategories....1971
HelpID....1971
HtmlText....1972
IsHideActionBar....1972
IsLayoutLocked....1972
IsRenameable....1972
Label....1972
LayoutBehavior....1973
Name....1973
OwnerId....1973
Product....1973
PublicAccess....1974
QualifiedURL....1974
SequenceNumber....1974
StyleSheet....1974
ValidFrom....1975
ValidTo....1975
TabDefinition Collection....1975
TabDefinition Collection Methods....1975
DeleteItem....1975
First....1976
InsertItem....1976
ItemByName....1977
Next....1977
TabDefinition Collection Property....1978
Count....1978
AssignedPagelet Class....1978
AssignedPagelet Class Properties....1978
Column....1979
LayoutBehavior....1979
PageletName....1979
Row....1979
AssignedPagelet Collection....1980
AssignedPagelet Collection Methods....1980
DeleteItem....1980
First....1980

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

InsertItem.... 1981
ItemByName.... 1982
Next.... 1982
AssignedPagelet Collection Property.... 1983
Count.... 1983
AvailableCategory Class.... 1983
AvailableCategory Class Properties.... 1983
AvailablePagelets.... 1984
CategoryName.... 1984
AvailableCategory Collection.... 1984
AvailableCategory Collection Methods.... 1984
First.... 1984
ItemByName.... 1985
Next.... 1985
AvailableCategory Collection Property.... 1986
Count.... 1986
AvailablePagelet Class.... 1986
AvailablePagelet Class Properties.... 1986
CategoryLabel.... 1986
CategoryName.... 1987
Column.... 1987
LayoutBehavior.... 1987
PageletLabel.... 1987
PageletName.... 1988
Row.... 1988
AvailablePagelet Collection.... 1988
AvailablePagelet Collection Methods.... 1988
First.... 1988
ItemByName.... 1989
Next.... 1989
AvailablePagelet Collection Property.... 1990
Count.... 1990
DynamicCategory Collection.... 1990
DynamicCategory Collection Methods.... 1990
DeleteItem.... 1990
First.... 1991
InsertItem.... 1992
ItemByName.... 1992
Next.... 1993
DynamicCategory Collection Property.... 1993
Count.... 1993
PageletCategory Class.... 1993
PageletCategory Class Method.... 1994
Save.... 1994
PageletCategory Class Properties.... 1994
Attributes.... 1994
Author.... 1995
AuthorAccess.... 1995
Authorized.... 1995
CascadedPermissions.... 1995
CreationDate.... 1996

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description....1996
Label....1996
Name....1996
OwnerId....1997
Pagelets....1997
Permissions....1997
Product....1997
PublicAccess....1998
SequenceNumber....1998
PageletCategory Collection....1998
PageletCategory Collection Methods....1998
DeleteItem....1998
First....1999
InsertItem....1999
ItemByName....2000
Next....2000
PageletCategory Collection Property....2001
Count....2001
Pagelet Class....2001
Pagelet Class Method....2001
Save....2002
Pagelet Class Properties....2002
Attributes....2002
Author....2002
AuthorAccess....2003
Authorized....2003
CascadedPermissions....2003
ContentProvider....2003
CreationDate....2004
DefaultColumn....2004
Description....2004
EditPageContentProvider....2004
EditPageQueryString....2004
HelpID....2005
IsHideMinimize....2005
Label....2005
Name....2005
OwnerId....2005
ParentName....2006
Permissions....2006
Product....2006
PublicAccess....2006
QualifiedURL....2006
SequenceNumber....2007
URL....2007
URLType....2007
Pagelet Collection....2008
Pagelet Collection Methods....2008
DeleteItem....2008
First....2009
InsertItem....2009

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ItemByName....2010
Next....2010
Pagelet Collection Property....2011
Count....2011
UserHomepage Class....2011
UserHomepage Class Method....2011
Save....2011
UserHomepage Class Properties....2012
Greeting....2012
UserId....2012
UserTab....2012
UserTab Class....2013
UserTab Class Properties....2013
ColumnLayout....2013
Label....2013
QualifiedURL....2014
SelectedPagelets....2014
SequenceNumber....2014
TabName....2014
UserTab Collection....2014
UserTab Collection Methods....2015
DeleteItem....2015
First....2015
InsertItem....2016
ItemByName....2016
Next....2017
UserTab Collection Property....2017
Count....2017
SelectedPagelet Class....2017
SelectedPagelet Class Properties....2018
CategoryName....2018
Column....2018
IsMinimized....2018
PageletName....2018
Row....2019
SelectedPagelet Collection....2019
SelectedPagelet Collection Methods....2019
DeleteItem....2019
First....2020
InsertItem....2020
ItemByName....2021
Next....2021
SelectedPagelet Collection Property....2021
Count....2022
Favorite Class....2022
Favorite Class Properties....2022
CRefName....2022
IsFolder....2022
Label....2023
QualifiedURL....2023
SequenceNumber....2023

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

URL....2023
Favorite Collection....2023
Favorite Collection Methods....2024
DeleteItem....2024
First....2024
InsertFolderItem....2025
InsertItem....2025
ItemByLabel....2026
Next....2026
Save....2027
Favorite Collection Property....2027
Count....2027
Portal Registry Classes Example....2027
Changing PortalRegistry Properties....2028
Adding a ContentProvider....2029
Adding a Folder....2030
Adding a Content Reference....2033
Setting Permissions Using the PermissionValue Object....2035
Using Attributes....2037
Visual Basic Example....2038
C/C++ Example....2038
Chapter 35: PostReport Class....2043
PostReport Class Overview....2043
Determining the Distribution List....2043
Data Type of a PostReport Object....2043
Scope of a PostReport Object....2044
PostReport Class Built-in Function....2044
PostReport Class Methods....2044
AddDistributionOption....2044
Put....2045
PostReport Class Properties....2045
ExpirationDate....2046
OutDestFormat....2046
ProcessInstance....2046
ProcessName....2047
ProcessType....2047
ReportDescr....2047
ReportFolder....2048
ReportId....2048
ServerName....2048
SourceReportPath....2049
PostReport Class Examples....2049
Chapter 36: Process Request Classes....2051
Understanding Process Request Classes....2051
Data Type of a ProcessRequest Object....2051
Scope of a ProcessRequest Object....2051
Options for Items In Jobs and Jobsets....2052
Values for Output Type and Format....2055
Alternative Options to Specify Email or Web Attributes....2058
File Dependant Processing....2059
ProcessRequest Class Built-in Functions....2059

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ProcessRequest Class Methods....2059
AddDistributionOption.... 2059
AddNotifyInfo....2060
PrintJobHTMLRpt.... 2061
PrintJobRqstRpt.... 2062
PrintSchdlHTMLRpt....2065
RunJobSetNow.... 2068
Schedule....2068
SetEmailOption....2069
SetItemFolder....2070
SetNotifyAppMethod....2071
SetNotifyService.... 2074
SetOutputOption.... 2075
UpdateRunStatus....2076
ProcessRequest Class Properties....2076
EmailAttachLog....2077
EmailSubject....2077
EmailText....2077
EmailWebReport....2077
FileName....2078
JobName.... 2078
LanguageCd.... 2079
NotifyTextMsgNum.... 2079
NotifyTextMsgSet....2079
OutDest.... 2080
OutDestFormat....2081
OutDestType.... 2081
PortalFolder....2082
ProcessInstance.... 2082
ProcessName....2082
ProcessType.... 2083
RunControlID.... 2084
RunDateTime.... 2084
RunLocation....2084
RunRecurrence....2085
RunStatus.... 2085
Status....2086
TimeZone.... 2087
ProcessRequest Class Examples....2087
Scheduling a Single Process.... 2087
Scheduling a Job Where Job Item Changes Are Not Made.... 2088
Scheduling a Job Where Job Item Changes Are Made.... 2088
PrcsApi Class.... 2089
Scope of a PrcsApi Object.... 2089
Data Type of a PrcsApi Object.... 2089
How to Import the PrcsApi Class.... 2089
How to Create a PrcsApi Object....2090
PrcsApi Class Constructor....2090
PrcsApi....2090
PrcsApi Class Methods....2090
getAllFileNames.... 2090

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

notifyToWindow ... 2091
Chapter 37: PSEvent Class ... 2093
Understanding the PSEvent Class ... 2093
Instantiating the PSEvent Class ... 2093
PSEvent Class Methods ... 2093
AddRecipient ... 2094
AddRecipients ... 2094
GetRecipients ... 2095
GetRowSetData ... 2096
GetValueOfKey ... 2096
Publish ... 2097
RemoveRecipients ... 2098
SetKeyValuePair ... 2098
SetRowSetData ... 2099
Subscribe ... 2100
Unsubscribe ... 2101
Chapter 38: Query Classes ... 2103
Understanding Query Classes ... 2103
Collections in the Query Classes ... 2103
Life Cycle of a Query ... 2104
Query Classes Hierarchy ... 2106
Query API Overview ... 2108
Query ... 2109
QuerySelect ... 2109
QueryRecords ... 2110
QueryOutputFields ... 2110
QuerySelectedFields ... 2110
QueryCriteria ... 2110
QueryDBRecords and QueryDBRecordFields ... 2111
Working With Query Criteria and Expressions ... 2111
Setting the Expression Type ... 2111
Adding New Expressions ... 2112
Adding an Operator and Expression 2 Dependencies ... 2112
Setting a Drilling URL ... 2113
Query Monitor ... 2114
Using Query Metadata ... 2114
Running a Query ... 2116
Specifying the User's Language ... 2117
Query Security ... 2117
Error Handling With Query Classes ... 2117
Understanding QueryOutputFields and QuerySelectedFields ... 2118
Understanding Having Criteria ... 2119
Data Type of Query Objects ... 2119
Scope of Query Objects ... 2119
Query Classes Reference ... 2120
Session Class Methods in the Query API ... 2121
AdvancedSearchQueries ... 2121
AdvancedSearchRecords ... 2123
FindQueryDBRecords ... 2125
FindQueries ... 2126
FindQueriesDateRange ... 2127

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GetQuery....2127
GetQuerySecurityProfile....2128
SearchQueryDBRecords....2129
SearchPrivateQueries....2130
SearchPublicQueries....2131
Query Collection....2133
Query Collection Methods....2133
First....2133
Item....2134
ItemByName....2134
Next....2135
Query Collection Property....2135
Count....2135
Query Class....2136
Query Class Methods....2136
AddPrompt....2136
AddQuerySelect....2137
AddTrackingURL....2137
Close....2138
CopyPrivateQuery....2139
Create....2140
Delete....2141
DeletePrompt....2142
FindExpression....2142
FormatBinaryResultString....2143
FormatResultString....2144
GetTreePromptCount....2145
Open....2145
Rename....2146
RunToFile....2147
RunToRowset....2149
RunToString....2151
Save....2154
SetTrackingURL....2155
Query Class Properties....2155
Approved....2156
ApproveOprId....2156
ApproveUserId....2156
ApproveDtTm....2156
CreateOprId....2157
CreateDtTm....2157
CreateUserId....2157
Description....2157
Disabled....2158
ExecAppName....2158
ExecLogging....2158
Folder....2159
LastSQLErrorCode....2159
LastUpdDttm....2159
LastUpdOprId....2159
LongDescription....2159

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Metadata....2159
MetaSQL....2160
MoreRowsAvailable....2160
Name....2160
OutputUnicode....2161
PDFFont....2161
Prompts....2162
PromptRecord....2162
PublicPrivate....2162
QuerySelect....2163
QueryStatistics....2163
RunTimePrompts....2163
SQL....2164
Type....2164
QuerySelect Collection....2164
QuerySelect Collection Methods....2165
AddUnion....2165
DeleteQuerySelect....2165
First....2166
Item....2166
ItemBySelNum....2167
Next....2167
QuerySelect Collection Property....2167
Count....2168
QuerySelect Class....2168
QuerySelect Methods....2169
AddAllFields....2169
AddCriteria....2169
AddExpression....2170
AddHavingCriteria....2171
AddQueryOutputField....2171
AddQueryRecord....2172
AddQuerySelectedField....2172
DeleteCriteria....2173
DeleteExpression....2173
DeleteField....2174
DeleteHavingCriteria....2174
DeleteRecord....2175
QuerySelect Properties....2175
Criteria....2176
Distinct....2176
Expressions....2176
HavingCriteria....2176
ParentSelectNum....2177
QueryOutputFields....2177
QueryRecords....2177
QuerySelectedFields....2177
QuerySelects....2178
SelectNum....2178
SelectType....2178
QueryRecord Collection....2179

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

QueryRecord Collection Methods.... 2179
First.... 2179
Item.... 2179
ItemByAlias.... 2180
Next.... 2180
QueryRecord Collection Property.... 2181
Count.... 2181
QueryRecord Class.... 2181
QueryRecord Class Method.... 2181
GetField.... 2181
QueryRecord Class Properties.... 2182
Description.... 2182
JoinAlias.... 2182
JoinFieldName.... 2182
JoinType.... 2183
Name.... 2183
QueryFields.... 2183
RecordAlias.... 2184
QueryField Collection.... 2184
QueryField Collection Methods.... 2184
First.... 2184
Item.... 2185
ItemByNameAndAlias.... 2185
ItemByExpNum.... 2186
Next.... 2186
QueryField Collection Property.... 2187
Count.... 2187
QueryField Class.... 2187
QueryField Class Methods.... 2187
AddTranslateExpression.... 2188
AddTranslateField.... 2188
GetImageFormat.... 2189
QueryField Class Properties.... 2189
Aggregate.... 2189
ColumnNumber.... 2190
Description.... 2190
Decimal.... 2190
ExpNum.... 2190
Flag.... 2191
Format.... 2191
HeadingText.... 2191
HeadingType.... 2192
HeadingUniqueFieldName.... 2192
Length.... 2192
LongName.... 2192
Name.... 2193
OrderByDirection.... 2193
OrderByNumber.... 2193
QueryRecord.... 2194
RecordAlias.... 2194
ShortName.... 2194

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

TranslateEffDtLogic....2194
TranslateExpression....2195
TranslateField....2195
TranslateOption....2195
Type....2196
QueryCriteria Collection....2196
QueryCriteria Collection Methods....2197
First....2197
Item....2197
ItemByName....2198
Next....2198
QueryCriteria Collection Property....2199
Count....2199
QueryCriteria Class....2199
QueryCriteria Class Methods....2199
AddExpr1Expression....2199
AddExpr1Field....2200
AddExpr2Expression....2201
AddExpr2Field1....2201
AddExpr2Field2....2202
AddExpr2List....2202
AddExpr2Subquery....2203
QueryCriteria Class Properties....2203
Expr1Expression....2203
Expr1Field....2204
Expr1Type....2204
Expr2Constant1....2205
Expr2Constant2....2205
Expr2Expression1....2205
Expr2Expression2....2206
Expr2Field1....2206
Expr2Field2....2206
Expr2List....2207
Expr2Subquery....2207
Expr2Type....2207
Logical....2210
LParenLvl....2211
Name....2211
Negation....2211
Operator....2211
R1ExprNum....2213
R2ExprNum....2213
R1ExprType....2214
R2ExprType....2214
RParenLvl....2214
QueryExpression Collection....2214
QueryExpression Collection Methods....2214
First....2215
Item....2215
ItemByName....2216
Next....2216

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

QueryExpression Collection Property.... 2216
Count.... 2217
QueryExpression Class.... 2217
QueryExpression Class Properties.... 2217
Aggregate.... 2217
BindFlag.... 2218
Decimal.... 2218
ExpNum.... 2218
IsXlatExpression.... 2218
Length.... 2218
Name.... 2219
OutputField.... 2219
RightExprFlag.... 2219
SelectedField.... 2219
Text.... 2220
Type.... 2220
QueryList Class.... 2221
QueryList Class Methods.... 2221
AddListValue.... 2221
First.... 2221
Item.... 2222
Next.... 2222
QueryList Class Property.... 2223
Count.... 2223
QueryListValue Class.... 2223
QueryListValue Class Properties.... 2223
IsPrompt.... 2223
Value.... 2224
QueryRecordHierarchy Collection.... 2224
QueryRecordHierarchy Collection Methods.... 2224
First.... 2224
Item.... 2224
ItemByName.... 2225
Next.... 2225
QueryRecordHierarchy Collection Property.... 2226
Count.... 2226
QueryRecordHierarchy Class.... 2226
QueryRecordHierarchy Class Properties.... 2227
Description.... 2227
Level.... 2227
Name.... 2227
ParentFlag.... 2227
Query Metadata Collection.... 2227
Query Metadata Collection Methods.... 2228
First.... 2228
Item.... 2228
ItemByName.... 2229
Next.... 2229
Query Metadata Collection Property.... 2230
Count.... 2230
Query Metadata Class.... 2230

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Query Metadata Class Properties.... 2230
Name.... 2230
Value.... 2231
QueryStatistics Class.... 2231
QueryStatistics Class Properties.... 2231
AvgExecTime.... 2232
AvgFetchTime.... 2232
AvgNumRows.... 2232
ExecCount.... 2232
LastExecDtTm.... 2232
QuerySecurityProfile Class.... 2232
QuerySecurityProfile Class Properties.... 2233
AllowAnyJoin.... 2233
AllowDistinct.... 2233
AllowExpressions.... 2233
AllowSubqueries.... 2233
AllowUnions.... 2233
ApprovePrivateQuery.... 2234
ApprovePublicQuery.... 2234
CanCreatePublic.... 2234
CanCreateWorkFlow.... 2234
CanModifyQuery.... 2234
CanRunQuery.... 2235
CanRunToCrystal.... 2235
CanRunToExcel.... 2235
LimitUnapproved.... 2235
MaxInTreeCriteria.... 2235
MaxJoins.... 2236
MaxRowsToFetch.... 2236
MaxUnapprovedRows.... 2236
QueryDBRecord Collection.... 2236
QueryDBRecord Collection Methods.... 2236
First.... 2236
Item.... 2237
ItemByName.... 2237
Next.... 2238
QueryDBRecord Collection Property.... 2238
Count.... 2238
QueryDBRecord Class.... 2239
QueryDBRecord Class Methods.... 2239
QueryDBRecordFieldByIndex.... 2239
QueryDBRecordFieldByName.... 2239
QueryDBRecord Class Properties.... 2240
Description.... 2240
Name.... 2240
QueryDBRecordFields.... 2240
RecordHierachy.... 2241
QueryDBRecordField Collection.... 2241
QueryDBRecordField Collection Methods.... 2241
First.... 2241
Item.... 2242

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ItemByName....2242
Next....2243
Sort....2243
QueryDBRecordField Collection Property....2244
Count....2244
QueryDBRecordField Class....2244
QueryDBRecordField Class Method....2244
GetImageFormat....2244
QueryDBRecordField Class Properties....2245
Decimal....2245
Description....2245
Flag....2246
Format....2247
Length....2248
LongName....2248
LookupTableName....2248
LookupTableRecord....2248
Name....2248
Shortname....2248
Type....2249
QueryPrompt Collection....2249
QueryPrompt Collection Methods....2250
First....2250
Item....2250
ItemByName....2251
Next....2251
QueryPrompt Collection Property....2252
Count....2252
QueryPrompt Class....2252
QueryPrompt Properties....2252
EditType....2252
FieldDecimal....2253
FieldFormat....2253
FieldLength....2254
FieldName....2254
FieldType....2254
HeadingText....2255
HeadingType....2255
LangCount....2255
Name....2256
PromptRecordFieldName....2256
PromptTable....2256
UniquePromptName....2256
UseCount....2256
Query Classes Examples....2256
Creating a New Query....2257
Adding Criteria....2259
Using Outer Joins....2263
Chapter 39: Record Class....2265
Understanding Record Class....2265
Shortcut Considerations....2265

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Record Methods Used to Create SQL Statements.... 2266
Data Type of a Record Object....2267
Scope of a Record Object....2267
Record Class Built-in Functions....2267
Record Class Methods.... 2267
CompareFields.... 2267
CopyChangedFieldsTo....2268
CopyFieldsTo....2269
Delete.... 2271
ExecuteEdits....2272
GetField....2274
Insert.... 2276
Save....2277
SearchClear.... 2280
SelectByKey....2281
SelectByKeyEffDt.... 2283
SetDefault....2284
SetEditTable....2285
Update.... 2287
Record Class Properties....2288
FieldCount....2288
fieldname....2288
IsChanged.... 2289
IsDeleted.... 2289
IsEditError....2290
Name.... 2290
ParentRow....2291
RelLangRecName.... 2291
SystemIDFieldName....2291
TimeStampFieldName.... 2292
Chapter 40: Row Class....2293
Understanding Row Class....2293
Shortcut Considerations.... 2293
Data Type of a Row Object....2294
Scope of a Row Object....2294
Row Class Built-in Function.... 2294
Row Class Methods.... 2294
CopyTo....2294
GetNextEffRow.... 2295
GetPriorEffRow.... 2296
GetRecord.... 2296
GetRowset....2298
scrollname.... 2298
Row Class Properties....2299
ChildCount....2299
DeleteEnabled....2299
IsChanged.... 2300
IsDeleted.... 2301
IsEditError....2301
IsNew.... 2302
ParentRowset.... 2302

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

recname....2302
RecordCount....2303
RowNumber....2303
Selected....2303
Style....2304
Visible....2304
Chapter 41: Rowset Class....2307
Understanding Rowset Class....2307
Shortcut Considerations....2307
Data Type of a Rowset Object....2308
Scope of a Rowset Object....2308
Rowset Class Built-In Functions....2308
Rowset Class Methods....2308
ClearDeletesChanges....2309
CopyTo....2310
DeleteRow....2312
Fill....2313
FillAppend....2316
Flush....2317
FlushRow....2319
GetCurrEffRow....2320
GetFirstUserSortedRow....2320
GetLastUserSortedRow....2321
GetNewEffRow....2322
GetRow....2322
HideAllRows....2323
InsertRow....2324
IsUserSorted....2325
MapBufRowToUserSortRow....2326
MapUserSortRowToBufRow....2327
Refresh....2328
Select....2329
SelectNew....2331
SetDefault....2333
ShowAllRows....2334
Sort....2334
Rowset Class Properties....2336
ActiveRowCount....2336
ChangeOnInit....2336
DataAreaCollapsed....2337
DBRecordName....2337
DeleteEnabled....2338
EffDt....2338
EffSeq....2339
InsertEnabled....2339
IsEditError....2340
Level....2340
Name....2341
ParentRow....2341
ParentRowset....2341
RowCount....2342

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SetComponentChanged....2342
TopRowNumber....2342
Chapter 42: RowsetCache Class....2343
Understanding a Rowset Cache....2343
Using the RowsetCache Class....2343
Error Handling....2344
Data Type of a RowsetCache Object....2344
Scope of a RowsetCache Object....2344
RowsetCache Class Built-in Functions....2345
RowsetCache Class Methods....2345
Delete....2345
Get....2346
Save....2346
RowsetCache Class Properties....2348
Content....2348
Description....2348
Chapter 43: Security Authorization Classes....2349
Understanding the Security Authorization Classes....2349
Importing the Security Authorization Classes....2349
AuthRequest Class....2349
AuthRequest Class Methods....2350
GetParameterValue....2351
AuthRequest Class Properties....2351
Access....2351
UserId....2351
SecurityHandler Class....2352
SecurityHandler Class Methods....2352
GetAuthorization....2352
Implementing a Security Authorization Handler....2353
Chapter 44: Session Class....2357
Understanding Session Class....2357
Security and Access to the PeopleSoft System....2358
Error Handling....2358
Displaying Error Messages....2359
Regional Settings....2359
Trace Settings....2359
Session Object Declaration....2360
State Considerations....2361
Considerations for Declaring Collections....2361
Scope of a Session Object....2361
Session Class Built-in Function....2361
Session Class Methods....2362
Connect....2362
Disconnect....2363
API Instantiation Methods....2364
Session Class Properties....2365
ErrorPending....2365
PSMessages....2365
PSMessagesMode....2366
RegionalSettings....2366
Repository....2367

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SuspendFormatting.... 2367
TraceSettings.... 2367
WarningPending.... 2367
Accessing a PSMessages Collection.... 2368
PSMessages Collection Methods.... 2368
DeleteAll.... 2368
DeleteItem.... 2369
First.... 2369
Item.... 2369
Next.... 2370
PSMessages Collection Property.... 2370
Count.... 2370
PSMessage Class Properties.... 2371
ExplainText.... 2371
MessageNumber.... 2371
MessageSetNumber.... 2371
MessageType.... 2371
Source.... 2372
Text.... 2373
Regional Settings Class Properties.... 2374
ClientTimeZone.... 2374
CurrencyFormat.... 2374
CurrencySymbol.... 2375
DateFormat.... 2375
DateSeparator.... 2375
DecimalSymbol.... 2376
DigitGroupingSymbol.... 2376
LanguageCD.... 2376
UseLocalTime.... 2377
1159Separator.... 2377
2359Separator.... 2378
Trace Setting Class Properties.... 2378
API.... 2378
COBOLStmtTimings.... 2379
ConnDisRollbackCommit.... 2379
DBSpecificCalls.... 2379
ManagerInfo.... 2379
NetworkServices.... 2379
NonSSBs.... 2380
OutputUNICODE.... 2380
PCExtFcnCalls.... 2380
PCFcnReturnValues.... 2380
PCFetchedValues.... 2380
PCIntFcnCalls.... 2381
PCListProgram.... 2381
PCParameterValues.... 2381
PCProgramStatements.... 2381
PCStack.... 2381
PCStartOfPrograms.... 2382
PCTraceProgram.... 2382
PCVariableAssignments.... 2382

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

RowFetch.... 2382
SQLStatement.... 2382
SQLStatementVariables.... 2383
SSBs.... 2383
SybBindInfo.... 2383
SybFetchInfo.... 2383
TraceFile.... 2383
Chapter 45: SOAPDoc Class.... 2385
Understanding theSOAPDoc Class.... 2385
SOAP Message Exchange Model.... 2385
SOAP Message Document.... 2386
The SOAPDoc Class.... 2387
SOAPDoc Object Creation.... 2388
SOAP Header Section.... 2388
SOAP Envelope Section.... 2388
SOAP Body Section.... 2388
SOAP Method Section.... 2389
SOAPDoc Section Access.... 2389
PeopleCode to Create a SOAPDoc.... 2390
SOAPDoc Fault Section.... 2390
The ValidateSOAPDoc Method.... 2390
SOAPDoc Objects and Messages.... 2391
Data Type of a SOAPDoc Object.... 2391
Scope of a SOAPDoc Object.... 2391
SOAPDoc Built-In Functions.... 2392
SOAPDoc Class Methods.... 2392
AddBody.... 2392
AddEnvelope.... 2393
AddFault.... 2395
AddHeader.... 2396
AddMethod.... 2398
AddParm.... 2399
GetParmName.... 2399
GetParmValue.... 2400
ValidateSOAPDoc.... 2401
SOAPDoc Class Properties.... 2402
BodyNode.... 2402
EnvelopeNode.... 2402
FaultCode.... 2402
FaultCodeS.... 2403
FaultString.... 2403
HeaderNode.... 2404
MethodName.... 2404
MethodNode.... 2405
ParmCount.... 2405
XmlDoc.... 2405
SOAPDoc Class Examples.... 2406
Creating a SOAP Document.... 2406
Reading an Existing SOAP Document.... 2406
Using SOAP XML Text.... 2407
Chapter 46: SQL Class.... 2409

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Understanding SQL Class....2409
Using Record Class SQL....2410
Creating a SQL Definition....2410
Binding and Executing of SQL Statements....2410
Fetching From a SELECT....2412
Using Array of Any for Bind Values or Fetch Results....2412
Reusing a Cursor....2412
Using the ReuseCursor Property....2413
Reusing a Cursor Without the ReuseCursor Property....2413
Understanding SQL Objects and Application Engine Programs....2415
Declaring a SQL Object....2415
Scope of an SQL Object....2415
SQL Class Built-in Functions....2416
SQL Class Methods....2416
Close....2416
Execute....2417
Fetch....2418
Open....2420
SQL Class Properties....2421
BulkMode....2421
IsOpen....2422
LTrim....2422
ReuseCursor....2423
RowsAffected....2424
Status....2424
TraceName....2425
Value....2426
Chapter 47: TransformData Class....2427
Understanding the TransformData Class....2427
Creating a TransformData Object....2427
TransformData Class Properties....2427
DestMsgName....2428
DestMsgVersion....2428
DestNode....2428
RejectTransform....2428
RoutingDefnName....2428
SourceMsgName....2429
SourceMsgVersion....2429
SourceNode....2429
Status....2429
XmlDoc....2430
Chapter 48: Tree Classes....2431
Understanding Tree Classes....2431
Relationships Between Different Tree Classes....2433
Collections in the Tree Classes....2434
Error Handling With Trees....2434
Leaves and Nodes Insert Verification....2435
Restrictions on Trees When Used as a SmartNavigation Data Source....2436
Data Types for Tree Objects....2437
Scope of the Tree Objects....2437
Tree Classes Implementation....2437

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Tree Classes Reference....2440
Session Class Methods....2440
GetTree....2440
GetTreeStructure....2441
Branch Collection....2441
Branch Collection Property....2441
Count....2441
Leaf Class....2441
Leaf Class Methods....2442
Cut....2442
Delete....2442
DeleteByRange....2443
GenABNMenuElement....2443
GenABNMenuElementWithImage....2444
InsertDynSib....2445
InsertSib....2445
LoadABNChart....2446
LoadABNChartOrdered....2447
MoveAsChild....2447
MoveAsChildByName....2448
MoveAsSib....2449
MoveAsSibByRange....2450
PasteSib....2450
RefreshDescription....2451
UpdateRanges....2451
Leaf Class Properties....2452
Description....2452
DisplayLevelNumber....2452
Dynamic....2452
HasNextSib....2453
HasPrevSib....2453
ImageName....2453
IsChanged....2453
IsCut....2453
IsDeleted....2454
IsInserted....2454
NextSib....2454
Parent....2454
PrevSib....2455
RangeFrom....2455
RangeTo....2455
TreeBranchName....2455
TreeEffDt....2455
TreeName....2456
TreeSetId....2456
TreeUserKeyValue....2456
Level Collection....2456
Level Collection Methods....2456
Add....2456
Item....2457
Remove....2457

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Level Collection Properties.... 2458
Count.... 2458
First.... 2458
Last.... 2458
Next.... 2458
Level Class.... 2458
Level Class Methods.... 2459
Create.... 2459
Level Class Properties.... 2459
AllValuesAudit.... 2459
Description.... 2459
Name.... 2460
Number.... 2460
TreeBranchName.... 2460
TreeEffDt.... 2460
TreeName.... 2460
TreeSetId.... 2461
TreeUserKeyValue.... 2461
Node Class.... 2461
Node Class Methods.... 2461
Branch.... 2461
Cut.... 2462
Delete.... 2462
DeleteByName.... 2463
Expand.... 2463
GenABNMenuElement.... 2464
GenABNMenuElementWithImage.... 2464
GenBreadCrumbs.... 2465
GenRelatedActions.... 2466
InsertChildLeaf.... 2467
InsertChildNode.... 2468
InsertChildRecord.... 2468
InsertDynChildLeaf.... 2469
InsertSib.... 2470
InsertSibRecord.... 2470
LoadABNChart.... 2471
LoadABNChartOrdered.... 2472
MoveAsChild.... 2473
MoveAsChildByName.... 2473
MoveAsSib.... 2474
MoveAsSibByName.... 2475
PasteChild.... 2475
PasteSib.... 2476
RefreshDescription.... 2476
Rename.... 2477
SwitchLevel.... 2477
Unbranch.... 2477
Node Class Properties.... 2478
AllChildCount.... 2478
AllChildNodeCount.... 2478
ChildLeafCount.... 2479

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ChildNodeCount.... 2479
ColImageName.... 2479
Description.... 2479
DisplayLevelNumber.... 2479
ExpImageName.... 2480
FirstChildLeaf.... 2480
FirstChildNode.... 2480
HasChildLeaves.... 2480
HasChildNodes.... 2480
HasChildren.... 2481
HasNextSib.... 2481
HasPrevSib.... 2481
IsBranched.... 2481
IsChanged.... 2481
IsCut.... 2482
IsDeleted.... 2482
IsInserted.... 2482
IsRoot.... 2482
LastChildLeaf.... 2482
LastChildNode.... 2483
LevelNumber.... 2483
Name.... 2483
NextSib.... 2484
Parent.... 2484
PrevSib.... 2484
State.... 2484
TreeBranchName.... 2485
TreeEffDt.... 2485
TreeName.... 2485
TreeSetId.... 2485
TreeUserKeyValue.... 2486
Type.... 2486
Tree Class.... 2486
Tree Class Methods.... 2487
Audit.... 2487
AuditByName.... 2487
Close.... 2488
Copy.... 2489
Create.... 2490
Delete.... 2492
Exists.... 2493
FindLeaf.... 2494
FindNode.... 2495
FindRoot.... 2496
InsertRoot.... 2496
LeafExists.... 2497
LockTree.... 2498
Open.... 2498
OpenAsOfDate.... 2500
OpenForExport.... 2502
OpenWholeTree.... 2503

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

NodeExists.... 2504
Rename.... 2504
Save.... 2506
SaveAs.... 2506
SaveAsDraft.... 2508
SaveDraft.... 2509
SetImportMode.... 2510
TreeLocksNumber.... 2510
UnlockTree.... 2511
UpdateLock.... 2512
Tree Class Properties.... 2513
AllValues.... 2513
AuditDetails.... 2513
Branches.... 2513
BranchImageName.... 2514
BranchLevel.... 2514
BranchName.... 2514
Category.... 2514
Description.... 2515
DuplicateLeaves.... 2515
EffDt.... 2515
HasDetailRanges.... 2516
HasLockedBranches.... 2516
IsBranched.... 2516
IsChanged.... 2517
IsOpen.... 2517
IsQueryTree.... 2517
IsValid.... 2517
IsVersionChanged.... 2518
IsWholeTree.... 2518
KeyBranchName.... 2518
KeyEffDt.... 2519
KeyName.... 2519
KeySetId.... 2519
KeyUserKeyValue.... 2519
LeafCount.... 2520
LeafImageName.... 2520
LeafOnClipboard.... 2520
LevelCount.... 2520
Levels.... 2521
LevelUse.... 2521
LockOwner.... 2521
LockStatus.... 2522
Name.... 2522
NodeColImageName.... 2523
NodeCount.... 2523
NodeExpImageName.... 2523
NodeOnClipboard.... 2523
ParentLevel.... 2523
ParentName.... 2524
PerformanceMethod.... 2524

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

PerformanceSelector....2524
PerformanceSelectorOption....2525
SetID....2526
Status....2526
Structure....2526
StructureName....2527
TreeImageName....2527
UserKeyValue....2527
UseUpdateReservation....2528
Tree Structure Class....2528
Tree Structure Class Methods....2528
Close....2528
Copy....2528
Create....2529
Delete....2530
Open....2530
Rename....2531
Save....2531
Tree Structure Class Properties....2531
Description....2532
DetailComponent....2532
DetailField....2532
DetailMenu....2533
DetailMenuBar....2533
DetailMenuItem....2533
DetailMultiNavigate....2533
DetailPage....2534
DetailRecord....2534
IndirectionMethod....2535
KeyName....2536
LevelComponent....2536
LevelMenu....2536
LevelMenuBar....2536
LevelMenuItem....2537
LevelPage....2537
LevelRecord....2537
Name....2537
NodeComponent....2538
NodeField....2538
NodeMenu....2538
NodeMenuBar....2539
NodeMenuItem....2539
NodeMultiNavigate....2539
NodePage....2539
NodeRecord....2540
NodeUserKeyField....2540
SummarySetId....2540
SummaryLevelNumber....2541
SummaryTreeName....2541
SummaryUserKeyValue....2541
Type....2542

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Traverse Tree Hierarchy Example....2542
Chapter 49: Universal Queue Classes....2545
Understanding Universal Queue Classes....2545
MCFFactory Class Hierarchy....2546
Scope of the Universal Queue Classes....2546
Data Types of the Universal Queue Classes....2547
How to Import Universal Queue Classes....2547
How to Create a Universal Queue Object....2548
Universal Queue Classes Built-in Functions....2548
Universal Queue Classes Constructors....2549
Agent....2549
AgentPhysQueueProps....2549
AgentPhysQueueTasks....2550
Broadcast....2550
LogicalQueue....2551
MCFFactory....2551
PhysicalQueue....2552
Task....2552
TaskList....2553
Util....2555
Agent Class....2555
Agent Methods....2555
Delete....2555
Refresh....2556
RefreshQTaskList....2557
Agent Properties....2557
AgentID....2558
AgentProps....2558
AgentTasks....2558
Buddy....2559
Language....2559
Name....2559
NickName....2559
PhysicalQueueID....2560
TotalPhysicalQueues....2560
AgentPhysQueueProps Class....2560
AgentPhysQueueProps Properties....2560
AgentID....2560
PhysicalQueueID....2561
SkillLevel....2561
WorkLoad....2561
AgentPhysQueueTasks Class....2561
AgentPhysQueueTasks Method....2562
Refresh....2562
AgentPhysQueueTasks Properties....2562
AcceptedTaskList....2562
AssignedTaskList....2563
AgentID....2563
PhysicalQueueID....2563
Broadcast Class....2563
Broadcast Class Method....2563

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Broadcast....2564
LogicalQueue Class....2565
LogicalQueue Properties....2565
LogicalQueueID....2565
PhysicalQueueID....2566
MCFFactory Class....2566
MCFFactory Property....2566
LogicalQueue....2566
PhysicalQueue Class....2567
PhysicalQueue Methods....2567
Refresh....2567
RefreshTaskList....2567
PhysicalQueue Properties....2568
AcceptedTaskList....2568
AssignedTaskList....2568
Agent....2568
BrowserURL....2569
EnqueuedTaskList....2569
EscalatedTaskList....2569
InternalURL....2570
IsActive....2570
LogicalQueueID....2570
OverflowedTaskList....2570
PhysicalQueueID....2571
RENURLID....2571
TotalAgents....2571
Task Class....2571
Task Methods....2571
Close....2571
Enqueue....2572
Refresh....2574
RefreshStatus....2574
Task Properties....2575
AgentID....2575
ApplicationData....2575
Comments....2575
EnqueueTime....2575
EscalationTime....2576
Language....2576
OriginalTime....2576
OverFlowTime....2576
PhysicalQueueID....2576
TiedAgentID....2576
TaskList Class....2577
TaskList Method....2577
Refresh....2577
TaskList Properties....2577
AgentID....2577
PhysicalQueueID....2578
Task....2578
TaskType....2578

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Total.... 2578
Util Class....2579
Util Methods....2579
GetLogicalQueue.... 2579
GetTimeDiff....2579
MCFFactory Example....2580
Chapter 50: Verity Search Classes....2583
Understanding the Verity Search Classes....2583
Using the SearchResult Collection....2584
Understanding Search Results....2584
Understanding the Differences Between Verity Search Classes and the PeopleTools Search Framework Classes....2585
Verity Search Classes Hierarchy....2587
Error Handling with the Verity Search Classes....2588
Data Type and Scope of Verity Search Objects.... 2590
Verity Search Classes Reference.... 2590
Session Class Methods....2591
GetSearchIndexes....2591
GetSearchQuery....2592
PortalRegistry Class Methods....2592
BuildSearchIndex....2592
GetSearchQuery....2593
SearchQuery Class.... 2594
SearchQuery Class Methods....2594
Execute....2594
Parse....2595
SearchQuery Class Properties....2595
HitCount....2596
Indexes.... 2596
IndexName....2597
KnowledgeBase.... 2597
Language....2597
ProcessedCount....2597
QueryText....2598
RequestedFields.... 2598
ScorePrecision....2598
SortSpecifications.... 2598
ParseResult Collection.... 2599
ParseResult Collection Methods....2599
First.... 2599
Next....2600
ParseResult Collection Properties....2600
ErrorCount.... 2600
WarningCount.... 2601
ParseResult Class.... 2601
ParseResult Class Properties....2601
Message....2601
Severity.... 2601
SearchResult Collection.... 2601
SearchResult Collection Methods....2602
First.... 2602

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Item.... 2602
Next.... 2603
SearchResult Collection Property.... 2603
Count.... 2603
SearchResult Class.... 2603
SearchResult Class Properties.... 2603
Key.... 2604
Score.... 2604
ScoreAsNumber.... 2604
SearchFields.... 2604
SearchField Collection.... 2605
SearchField Collection Methods.... 2605
First.... 2605
ItemByName.... 2605
Next.... 2606
SearchField Collection Property.... 2606
Count.... 2606
SearchField Class.... 2606
SearchField Class Properties.... 2606
Name.... 2607
Value.... 2607
SearchIndex Collection.... 2607
SearchIndex Collection Methods.... 2607
First.... 2607
ItemByName.... 2608
Next.... 2608
SearchIndex Collection Property.... 2608
Count.... 2608
SearchIndex Class.... 2609
SearchIndex Class Method.... 2609
Save.... 2609
SearchIndex Class Properties.... 2609
ExtraOptions.... 2610
FSOpts.... 2610
HTTPOpts.... 2610
Languages.... 2610
Location.... 2610
Name.... 2611
RecOpts.... 2611
Schedules.... 2611
Type.... 2611
SearchRecord Options Class.... 2612
SearchRecord Options Class Properties.... 2612
Fields.... 2612
Filter.... 2612
IncrementalView.... 2613
RecName.... 2613
VeggieKey.... 2613
ZoneOptions.... 2614
SearchRecordField Collection.... 2615
SearchRecordField Collection Methods.... 2615

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

DeleteItem....2615
First....2615
InsertItem....2616
ItemByName....2616
Next....2617
SearchRecordField Collection Property....2617
Count....2617
SearchRecordField Class....2617
SearchRecordField Class Properties....2617
FieldName....2618
IsAttachment....2618
IsVerityField....2618
IsWordIndex....2618
RecordName....2618
Search Language Collection....2619
Search Language Collection Methods....2619
DeleteItem....2619
First....2619
InsertItem....2620
ItemByName....2620
Next....2621
Search Language Collection Property....2621
Count....2621
Search Language Class....2621
Search Language Class Properties....2621
LanguageCd....2622
MapLanguageCd....2622
Search Schedule Collection....2622
Search Schedule Collection Methods....2622
DeleteItem....2622
First....2623
InsertItem....2623
ItemByName....2623
Next....2624
Search Schedule Collection Property....2624
Count....2624
Search Schedule Class....2624
Search Schedule Class Properties....2625
BuildType....2625
RunCntlId....2625
RunRecurrence....2625
ServerName....2626
Search HTTP Options Class....2626
Search HTTP Options Class Properties....2626
AllowHTTPS....2626
DomainLimit....2626
GlobList....2627
GlobListType....2627
LinkDepth....2627
MIMEList....2628
MIMEListType....2628

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ProxyHost.... 2628
ProxyPort.... 2629
StartOpts.... 2629
Search FS Options Class.... 2629
Search FS Options Class Properties.... 2629
GlobList.... 2629
GlobListType.... 2630
MIMEList.... 2630
MIMEListType.... 2630
StartOpts.... 2631
Search Start Options Collection.... 2631
Search Start Options Collection Methods.... 2631
DeleteItem.... 2631
First.... 2632
InsertItem.... 2632
ItemByName.... 2633
Next.... 2633
Search Start Options Collection Property.... 2633
Count.... 2634
Search Start Options Class.... 2634
Search Start Options Class Properties.... 2634
IsDomainRestricted.... 2634
IsHostRestricted.... 2634
Value.... 2635
Verity Search Classes Examples.... 2635
General Purpose Example.... 2635
Portal Search Example.... 2635
Chapter 51: XmlDoc Classes.... 2637
Understanding XmlDoc Classes.... 2637
When to Use an XmlDoc Object.... 2637
XmlDoc Object Creation.... 2638
Considerations Using a Unique Namespace.... 2638
Considerations Using Rowsets.... 2639
XmlNode Class Considerations.... 2640
Accessing and Traversing an XmlNode Object.... 2640
Error Handling.... 2641
SOAPDoc Object Considerations.... 2641
Scope of XmlDoc and XmlNode Objects.... 2642
Data Type of an XmlDoc or XmlNode Object.... 2642
XmlDoc Classes Built-in Functions.... 2642
XmlDoc Class Methods.... 2642
CopyRowset.... 2643
CopyToPSFTMessage.... 2643
CopyToRowset.... 2645
CreateDocumentElement.... 2647
CreateDocumentType.... 2648
GenFormattedXmlString.... 2649
GenXmlFile.... 2650
GenXmlString.... 2650
GetElementsByTagName.... 2651
LoadIBContent.... 2652

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ParseXmlFromURL.... 2653
ParseXmlString.... 2655
XmlDoc Properties.... 2656
DocumentElement.... 2656
IsNull.... 2656
XmlNode Class.... 2656
XmlNode Class Methods.... 2656
AddAttribute.... 2656
AddAttributeNS.... 2658
AddCDataSection.... 2659
AddComment.... 2660
AddElement.... 2660
AddElementNS.... 2661
AddEntityReference.... 2662
AddNode.... 2663
AddProcessInstruction.... 2664
AddText.... 2665
CopyNode.... 2665
FindNode.... 2667
FindNodes.... 2667
GenXmlString.... 2669
GetAttributeName.... 2669
GetAttributeValue.... 2670
GetCDataValue.... 2670
GetCDataValues.... 2671
GetChildNode.... 2672
GetElement.... 2672
GetElements.... 2673
GetElementsByTagName.... 2674
GetElementsByTagNameNS.... 2675
InsertCDataSection.... 2676
InsertComment.... 2677
InsertElement.... 2678
InsertElementNS.... 2679
InsertEntityReference.... 2680
InsertNode.... 2681
InsertProcessInstruction.... 2682
InsertText.... 2683
RemoveAllChildNode.... 2684
RemoveChildNode.... 2685
XmlNode Class Properties.... 2686
AttributesCount.... 2687
ChildNodeCount.... 2687
Index.... 2687
IsNull.... 2687
LocalName.... 2688
NamespaceURI.... 2688
NextSibling.... 2688
NodeName.... 2688
NodePath.... 2689
NodeType.... 2689

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

NodeValue....2689
ParentNode....2690
Prefix....2690
PreviousSibling....2690
Appendix A: Quick Reference for PeopleCode Classes....2691
PeopleCode Syntax Quick Reference....2691
PeopleCode Classes Alphabetical Reference....2695
Typographical Conventions and Visual Cues....2695
Activity Guide Classes....2695
AESection Class....2700
Analytic Calculation Engine Classes....2700
Analytic Calculation Engine Metadata Classes....2703
Analytic Grid Classes....2713
Analytic Type Classes....2714
Application Classes....2715
Application Data Set Classes....2717
Array Class....2717
BI Publisher Classes....2719
BPEL Classes....2723
Charting Classes....2724
Component Interface Class....2740
Connected Query Classes....2740
Crypt Class....2744
Document Classes....2745
Exception Class....2749
Feed Classes....2750
Field Class....2767
File Class....2771
Grid Classes....2772
Internet Script Classes....2773
Java Class....2776
Mail Classes....2777
MCF IM Classes....2787
Message Classes....2788
Notification Classes....2797
Optimization PeopleCode Classes....2802
Page Class....2806
PeopleSoft Search Framework Classes....2806
Portal Registry Classes....2815
PostReport Class....2815
Process Request Classes....2816
Query Classes....2819
Record Class....2819
Row Class....2820
Rowset Class....2821
RowsetCache Class....2823
Search Classes....2824
Security Authorization Classes....2824
Session Classes....2825
SOAPDoc Class....2825
SQL Class....2826

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

TransformData Class.... 2827
Tree Classes.... 2828
Universal Queue Classes.... 2828
XmlDoc Classes.... 2833
Session Classes.... 2836
Session Classes Methods and Properties.... 2837
API Repository Classes Methods and Properties.... 2841
Component Interface Class Methods and Properties.... 2844
Verity Search Classes Methods and Properties.... 2847
Portal Registry Classes Methods and Properties.... 2854
Query Classes Methods and Properties.... 2877
Tree Classes Methods and Properties.... 2893
Deprecated Items and PeopleCode No Longer Supported.... 2903
Mapping of Old Objects to New Objects.... 2904
Deprecated Products and Classes.... 2905
Deprecated Functions.... 2913
Deprecated Methods and Properties.... 2916
Deprecated BI Publisher Items.... 2919
BI Publisher Items No Longer Supported.... 2920
Deprecated Messaging PeopleCode Functions, Methods and Properties.... 2928
Functions No Longer Supported.... 2931

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Preface

Understanding the PeopleSoft Online Help and PeopleBooks

The PeopleSoft Online Help is a website that enables you to view all help content for PeopleSoft Applications and PeopleTools. The help provides standard navigation and full-text searching, as well as context-sensitive online help for PeopleSoft users.

PeopleSoft Hosted Documentation

You access the PeopleSoft Online Help on Oracle's PeopleSoft Hosted Documentation website, which enables you to access the full help website and context-sensitive help directly from an Oracle hosted server. The hosted documentation is updated on a regular schedule, ensuring that you have access to the most current documentation. This reduces the need to view separate documentation posts for application maintenance on My Oracle Support, because that documentation is now incorporated into the hosted website content. The Hosted Documentation website is available in English only.

Note: Only the most current release of hosted documentation is updated regularly. After a new release is posted, previous releases remain available but are no longer updated.

Locally Installed Help

If your organization has firewall restrictions that prevent you from using the Hosted Documentation website, you can install the PeopleSoft Online Help locally. If you install the help locally, you have more control over which documents users can access and you can include links to your organization's custom documentation on help pages.

In addition, if you locally install the PeopleSoft Online Help, you can use any search engine for full-text searching. Your installation documentation includes instructions about how to set up Oracle Secure Enterprise Search for full-text searching.

See *PeopleTools Installation* for your database platform, "Installing PeopleSoft Online Help." If you do not use Secure Enterprise Search, see the documentation for your chosen search engine.

Note: Before users can access the search engine on a locally installed help website, you must enable the Search portlet and link. Click the Help link on any page in the PeopleSoft Online Help for instructions.

Downloadable PeopleBook PDF Files

You can access downloadable PDF versions of the help content in the traditional PeopleBook format. The content in the PeopleBook PDFs is the same as the content in the PeopleSoft Online Help, but it has a different structure and it does not include the interactive navigation features that are available in the online help.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Common Help Documentation

Common help documentation contains information that applies to multiple applications. The two main types of common help are:

- Application Fundamentals
- Using PeopleSoft Applications

Most product families provide a set of application fundamentals help topics that discuss essential information about the setup and design of your system. This information applies to many or all applications in the PeopleSoft product family. Whether you are implementing a single application, some combination of applications within the product family, or the entire product family, you should be familiar with the contents of the appropriate application fundamentals help. They provide the starting points for fundamental implementation tasks.

In addition, the *PeopleTools: Applications User's Guide* introduces you to the various elements of the PeopleSoft Pure Internet Architecture. It also explains how to use the navigational hierarchy, components, and pages to perform basic functions as you navigate through the system. While your application or implementation may differ, the topics in this user's guide provide general information about using PeopleSoft Applications.

Field and Control Definitions

PeopleSoft documentation includes definitions for most fields and controls that appear on application pages. These definitions describe how to use a field or control, where populated values come from, the effects of selecting certain values, and so on. If a field or control is not defined, then it either requires no additional explanation or is documented in a common elements section earlier in the documentation. For example, the Date field rarely requires additional explanation and may not be defined in the documentation for some pages.

Typographical Conventions

The following table describes the typographical conventions that are used in the online help.

Typographical Convention	***Description***
Key+Key	Indicates a key combination action. For example, a plus sign (+) between keys means that you must hold down the first key while you press the second key. For Alt+W, hold down the Alt key while you press the W key.
. . . (ellipses)	Indicate that the preceding item or series can be repeated any number of times in PeopleCode syntax.
{ } (curly braces)	Indicate a choice between two options in PeopleCode syntax. Options are separated by a pipe (|).
[ ] (square brackets)	Indicate optional items in PeopleCode syntax.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Typographical Convention	*Description*
& (ampersand)	When placed before a parameter in PeopleCode syntax, an ampersand indicates that the parameter is an already instantiated object. Ampersands also precede all PeopleCode variables.
⇒	This continuation character has been inserted at the end of a line of code that has been wrapped at the page margin. The code should be viewed or entered as a single, continuous line of code without the continuation character.

ISO Country and Currency Codes

PeopleSoft Online Help topics use International Organization for Standardization (ISO) country and currency codes to identify country-specific information and monetary amounts.

ISO country codes may appear as country identifiers, and ISO currency codes may appear as currency identifiers in your PeopleSoft documentation. Reference to an ISO country code in your documentation does not imply that your application includes every ISO country code. The following example is a country-specific heading: "(FRA) Hiring an Employee."

The PeopleSoft Currency Code table (CURRENCY_CD_TBL) contains sample currency code data. The Currency Code table is based on ISO Standard 4217, "Codes for the representation of currencies," and also relies on ISO country codes in the Country table (COUNTRY_TBL). The navigation to the pages where you maintain currency code and country information depends on which PeopleSoft applications you are using. To access the pages for maintaining the Currency Code and Country tables, consult the online help for your applications for more information.

Region and Industry Identifiers

Information that applies only to a specific region or industry is preceded by a standard identifier in parentheses. This identifier typically appears at the beginning of a section heading, but it may also appear at the beginning of a note or other text.

Example of a region-specific heading: "(Latin America) Setting Up Depreciation"

Region Identifiers

Regions are identified by the region name. The following region identifiers may appear in the PeopleSoft Online Help:

- Asia Pacific
- Europe
- Latin America
- North America

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Industry Identifiers

Industries are identified by the industry name or by an abbreviation for that industry. The following industry identifiers may appear in the PeopleSoft Online Help:

- USF (U.S. Federal)
- E&G (Education and Government)

Using and Managing the PeopleSoft Online Help

Click the Help link in the universal navigation header of any page in the PeopleSoft Online Help to see information on the following topics:

- What's new in the PeopleSoft Online Help.
- PeopleSoft Online Help acessibility.
- Accessing, navigating, and searching the PeopleSoft Online Help.
- Managing a locally installed PeopleSoft Online Help website.

PeopleTools Related Links

Oracle's PeopleSoft PeopleTools 8.54 Documentation Home Page (Doc ID 1664613.1)

"PeopleTools Product/Feature PeopleBook Index" (PeopleTools 8.54: Getting Started with PeopleTools)

PeopleSoft Information Portal

My Oracle Support

PeopleSoft Training from Oracle University

PeopleSoft Video Feature Overviews on YouTube

Contact Us

Send us your suggestions Please include release numbers for the PeopleTools and applications that you are using.

Follow Us

Get the latest PeopleSoft updates on Facebook.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Follow PeopleSoft on Twitter@PeopleSoft_Info.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Chapter 1

Activity Guide Classes

Understanding the Activity Guide Classes

Activity guides are a PeopleTools feature that allow you to define guided procedures for a user or group of users to complete. Users are presented with a list of actions, or tasks, that need to be completed to finish the procedure. The activity guide classes documented in these topics provide you with a programmatic interface to manage and manipulate activity guide templates, activity guide instances, action items, participants, and so on. In addition, some of these activity guide classes can be used to customize and extend your implementation of activity guides.

Related Links

"Understanding Activity Guides" (PeopleTools 8.54: Portal Technology)

"Enhancing Activity Guides" (PeopleTools 8.54: Portal Technology)

Importing Activity Guide Classes

The activity guide classes are application classes, not built-in classes, like Rowset, Field, Record, and so on. Before you can use these classes in your PeopleCode program, you must import them into your program.

An import statement either names a particular application class or imports all the classes in a package.

Using the asterisks after the package name makes all the application classes directly contained in the named package available. Application classes contained in subpackages of the named package are not made available.

Activity Guide Classes Reference

This reference section documents the following classes from the PTAI_ACTION_ITEMS application package:

- List class
- ActionItem class
- Member class
- ContextData class

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

List Class

This section provides an overview of the List class and discusses:

- List class methods.
- List class properties.

The List class is used to manage an activity guide template or an activity guide instance.

Typically, activity guides are defined by the properties and characteristics of activity guide templates. An *activity guide template* provides a reusable definition of the important aspects of an activity guide: its properties, participants, contextual data, list of action items and to whom they are assigned, and so on. Then, at run time, an *activity guide instance* can be created from the definitions stored in the template. The instance will be generated with the contextual data that uniquely differentiates one instance from another. For example, for a benefits enrollment activity guide, the contextual data would likely include the employee ID, the country and locale (state, province, and so on) where the employee works, and any other key data required to initiate the benefits process.

Related Links

"Activity Guide Templates and Instances" (PeopleTools 8.54: Portal Technology)

"Creating and Maintaining Activity Guide Templates" (PeopleTools 8.54: Portal Technology)

"Managing Activity Guide Instances" (PeopleTools 8.54: Portal Technology)

List Class Methods

In this section, the List class methods are presented in alphabetical order.

createInstance

Syntax

`createInstance``(`*`instance_ID, title, &context_data`*`)`

Description

Use this method to create an activity guide instance by cloning the current activity guide template including its action items, participants, and so on.

Parameters

instance_ID Specifies the ID for the activity guide instance as a string.

title Specifies the title for the activity guide instance as a string.

Note: The title is also referred to as the Label property.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

&context_data Specifies the contextual data for the activity guide instance as a PTAI_COLLECTION:Collection object.

Returns

A List object.

Example

This is a code example of the CreateInstance method:

```
method CreateInstFromCtxtData
   /+ &oCtxt as PTAI_COLLECTION:Collection +/
   /+ Returns String +/
   Local PTAI_ACTION_ITEMS:ContextData &ctxData;
   Local PTAI_ACTION_ITEMS:List &newList = create PTAI_ACTION_ITEMS:List();
   Local PTAI_COLLECTION:Collection &ctxDataColl = create PTAI_COLLECTION:Collectio⇒
n();
   Local integer &i, &nbr;
   Local string &label, &descr, &InstanceId;
   try
      For &i = 1 To &oCtxt.Count
         &ctxData = (&oCtxt.Item(&i) As PTAI_ACTION_ITEMS:ContextData);
         If &ctxData.ctxKey And
               &ctxData.keyValue = "" Then
            Return "";
         End-If;
         &ctxDataColl.InsertItem(&ctxData);
      End-For;

      &newList.open(&Template_Id);
      SQLExec(SQL.PTAI_GET_INSTANCES, &newList.ListId, &nbr);
      &nbr = &nbr + 1;
      &label = &newList.Label | "-" | &nbr;
      &InstanceId = &newList.createInstance(&label, &newList.DescrLong, &ctxDataCol⇒
l).ListId;
      Return &InstanceId;
   catch Exception &e
      Return "";
   end-try;

end-method;
```

Related Links

Label

ListId

ContextData Class

getActionItems

Syntax

getActionItems()

Description

Use this method to return an array of *all* action item IDs for the current activity guide. This method returns IDs for both summary and detail action items.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

None.

Returns

An array of string.

Related Links

getRootItems
ActionItem Class

GetContext

Syntax

GetContext()

Description

Use this method to get the contextual data for the current activity guide.

Parameters

None.

Returns

A PTAI_COLLECTION:Collection object.

Related Links

ContextData Class

getMembers

Syntax

getMembers()

Description

Use this method to return a PTAI_COLLECTION:Collection object representing participants for the current activity guide.

Parameters

None.

Returns

A PTAI_COLLECTION:Collection object.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

Member Class

GetPgltBtn

Syntax

```
GetPgltBtn()
```

Description

Use this method to return a PTAI_COLLECTION:Collection representing the definitions for custom navigation frame buttons for the current activity guide.

Parameters

None.

Returns

A PTAI_COLLECTION:Collection object.

getRootItems

Syntax

```
getRootItems()
```

Description

Use this method to return an array of action item IDs for summary action items for the current activity guide.

Note: This method does not return IDs for detail action items.

Parameters

None.

Returns

An array of string.

Related Links

getActionItems

ActionItem Class

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

new

Syntax

new(*ID*, *portal*, *title*)

Description

Use this method to generate a new activity guide.

Parameters

ID	Specifies the ID for the new activity guide as a string.
portal	Specifies a portal for the activity guide as a string.
title	Specifies the title for the activity guide as a string.

Note: The title is also referred to as the Label property.

Returns

None.

Related Links

Label
ListId

open

Syntax

open(*ID*)

Description

Use this method to retrieve an activity guide definition from the database and sets all the properties.

Parameters

ID	Specifies the activity guide ID as a string.

Returns

None.

Related Links

ListId

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

save

Syntax

save()

Description

Use this method to save the current activity guide definition to the database. If this is a new activity guide, then the definition is inserted into the database; otherwise, an existing definition is updated in the database.

Parameters

None.

Returns

A Boolean value: True if the save is successful, False otherwise.

SaveContext

Syntax

SaveContext(*&context_data*)

Description

Use this method to save the contextual data for the current activity guide to the database. Any existing contextual data for this activity guide definition is deleted from the database first.

Parameters

&context_data	Specifies the contextual data for the activity guide as a PTAI_COLLECTION:Collection object.

Returns

None.

Related Links

ContextData Class

saveMembers

Syntax

saveMembers(*&members*)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use this method to save the participants (members) for the current activity guide to the database. Any existing participants for this activity guide definition are deleted from the database first.

Parameters

&members	Specifies the participants for the activity guide as a PTAI_COLLECTION:Collection object.

Returns

None.

Related Links

Member Class

SavePgltBtn

Syntax

SavePgltBtn(*&pgltBtns*)

Description

Use this method to save the definitions for the custom navigation frame buttons for the current activity guide to the database. Any existing custom button definitions for this activity guide are deleted from the database first.

Parameters

&pgltBtns	Specifies the custom navigation frame buttons for the activity guide as a PTAI_COLLECTION:Collection object.

Returns

A PTAI_COLLECTION:Collection object.

List Class Properties

In this section, the List class properties are presented in alphabetical order.

AppClassID

Description

Use this property to set or return a string value representing the name of the application class that contains the method to be invoked at activity guide instance creation.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Note: The full path to the method is constructed from four properties: PackageRoot, QualifyPath, AppClassID, and AppClassMethod

This property is read-write.

Related Links

AppClassMethod
PackageRoot
QualifyPath
"Defining Advanced Options" (PeopleTools 8.54: Portal Technology)
"Initializing an Activity Guide Instance" (PeopleTools 8.54: Portal Technology)

AppClassMethod

Description

Use this property to set or return a string value representing the name of the method to be invoked at activity guide instance creation.

Note: The full path to the method is constructed from four properties: PackageRoot, QualifyPath, AppClassID, and AppClassMethod

This property is read-write.

Related Links

AppClassID
PackageRoot
QualifyPath
"Defining Advanced Options" (PeopleTools 8.54: Portal Technology)
"Initializing an Activity Guide Instance" (PeopleTools 8.54: Portal Technology)

DescrLong

Description

Use this property to set or return the description for the activity guide as a string value.

This property is read-write.

Related Links

"Defining Activity Guide Template Properties" (PeopleTools 8.54: Portal Technology)

Field1

Description

Use this property to set or return a string value representing the label for the first configurable text field.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-write.

Related Links

"Defining Advanced Options" (PeopleTools 8.54: Portal Technology)

Field10

Description

Use this property to set or return a string value representing the label for the fifth configurable yes/no field.

This property is read-write.

Related Links

"Defining Advanced Options" (PeopleTools 8.54: Portal Technology)

Field2

Description

Use this property to set or return a string value representing the label for the second configurable text field.

This property is read-write.

Related Links

"Defining Advanced Options" (PeopleTools 8.54: Portal Technology)

Field3

Description

Use this property to set or return a string value representing the label for the third configurable text field.

This property is read-write.

Related Links

"Defining Advanced Options" (PeopleTools 8.54: Portal Technology)

Field4

Description

Use this property to set or return a string value representing the label for the fourth configurable text field.

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

"Defining Advanced Options" (PeopleTools 8.54: Portal Technology)

Field5

Description

Use this property to set or return a string value representing the label for the fifth configurable text field.

This property is read-write.

Related Links

"Defining Advanced Options" (PeopleTools 8.54: Portal Technology)

Field6

Description

Use this property to set or return a string value representing the label for the first configurable yes/no field.

This property is read-write.

Related Links

"Defining Advanced Options" (PeopleTools 8.54: Portal Technology)

Field7

Description

Use this property to set or return a string value representing the label for the second configurable yes/no field.

This property is read-write.

Related Links

"Defining Advanced Options" (PeopleTools 8.54: Portal Technology)

Field8

Description

Use this property to set or return a string value representing the label for the third configurable yes/no field.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

"Defining Advanced Options" (PeopleTools 8.54: Portal Technology)

Field9

Description

Use this property to set or return a string value representing the label for the fourth configurable yes/no field.

This property is read-write.

Related Links

"Defining Advanced Options" (PeopleTools 8.54: Portal Technology)

HomeUrl

Description

Use this property to set or return a string value representing the URL for the WorkCenter page (or starting page) that incorporates this activity guide. This URL provides access from the Activity Guides - In Progress homepage pagelet to the WorkCenter page.

This property is read-write.

Related Links

"Defining Activity Guide Template Properties" (PeopleTools 8.54: Portal Technology)

"Working With the Activity Guides - In Progress Pagelet" (PeopleTools 8.54: Portal Technology)

isActive

Description

Use this property to set or return a Boolean value indicating whether the activity guide is active.

This property is read-write.

Related Links

"Defining Activity Guide Template Properties" (PeopleTools 8.54: Portal Technology)

IsTemplate

Description

Use this property to set or return a Boolean value indicating whether the activity guide is a template. When this property is False, the List object is an activity guide instance.

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

"Defining Activity Guide Template Properties" (PeopleTools 8.54: Portal Technology)

Label

Description

Use this property to set or return a string representing the descriptive name (or title) of the activity guide.

This property is read-write.

Related Links

"Defining Activity Guide Template Properties" (PeopleTools 8.54: Portal Technology)

ListId

Description

Use this property to return a string representing the ID for this activity guide.

This property is read-only.

Related Links

"Defining Activity Guide Template Properties" (PeopleTools 8.54: Portal Technology)

PackageRoot

Description

Use this property to set or return a string value representing the name of the application package that contains the method to be invoked at activity guide instance creation.

Note: The full path to the method is constructed from four properties: PackageRoot, QualifyPath, AppClassID, and AppClassMethod

---

This property is read-write.

Related Links

AppClassID
AppClassMethod
QualifyPath
"Defining Advanced Options" (PeopleTools 8.54: Portal Technology)
"Initializing an Activity Guide Instance" (PeopleTools 8.54: Portal Technology)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ParentTemplate

Description

Use this property to set or return a string representing the ID of the template used to generate the activity guide instance. If the List object represents an activity guide template, then this property will be Null.

Related Links

"Creating New Activity Guide Instances Manually" (PeopleTools 8.54: Portal Technology)

pgltAppClass

Description

Use this property to set or return a string representing the name of the application class that contains the method (or methods) to be invoked to create custom navigation frame buttons.

Note: The full path to the method is constructed from three properties: pgltPackageRoot, pgltQualifyPath, and pgltAppClass.

This property is read-write.

Related Links

GetPgltBtn
SavePgltBtn
pgltPackageRoot
pgltQualifyPath
"Defining Pagelet and Navigation Options" (PeopleTools 8.54: Portal Technology)

pgltPackageRoot

Description

Use this property to set or return a string representing the name of the application package that contains the method (or methods) to be invoked to create custom navigation frame buttons.

Note: The full path to the method is constructed from three properties: pgltPackageRoot, pgltQualifyPath, and pgltAppClass.

This property is read-write.

Related Links

GetPgltBtn
SavePgltBtn
pgltAppClass
pgltQualifyPath
"Defining Pagelet and Navigation Options" (PeopleTools 8.54: Portal Technology)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

pgltProgressBarVisible

Description

Use this property to set or return a Boolean value indicating whether the progress bar will be displayed in the activity guide pagelet on the WorkCenter page.

This property is read-write.

Related Links

"Defining Pagelet and Navigation Options" (PeopleTools 8.54: Portal Technology)

pgltQualifyPath

Description

Use this property to set or return a string representing the names of each subpackage in the application class hierarchy that define the location of the application class. Separate subpackage names by a colon. If the class is defined in the top-level application package, use a colon only.

Note: The full path to the method is constructed from three properties: pgltPackageRoot, pgltQualifyPath, and pgltAppClass.

This property is read-write.

Related Links

GetPgltBtn
SavePgltBtn
pgltAppClass
pgltPackageRoot
"Defining Pagelet and Navigation Options" (PeopleTools 8.54: Portal Technology)

QualifyPath

Description

Use this property to set or return a string value representing the names of each subpackage in the application class hierarchy that define the location of the application class. Separate subpackage names by a colon. If the class is defined in the top-level application package, use a colon only.

Note: The full path to the method is constructed from four properties: PackageRoot, QualifyPath, AppClassID, and AppClassMethod

---

This property is read-write.

Related Links

AppClassID
AppClassMethod

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

PackageRoot
"Defining Advanced Options" (PeopleTools 8.54: Portal Technology)
"Initializing an Activity Guide Instance" (PeopleTools 8.54: Portal Technology)

Status

Description

Use this property to set or return the status of the instance, which determines whether the activity guide is displayed in the Activity Guides - In Progress pagelet. The valid values are:

Value	*Description*
CA	Cancelled
CP	Complete
IP	In progress

This property is read-write.

Example

In the following example, the method sets the activity guide status to complete:

```
method CompleteStatus
   /+ &list_id as String +/

   Local PTAI_ACTION_ITEMS:List &ObjList;

   &ObjList = create PTAI_ACTION_ITEMS:List();
   &ObjList.open(&list_id);

   Rem set the status of the template to Complete;

   &ObjList.Status = "CP";
   &return = &ObjList.save();

end-method;
```

ActionItem Class

This section provides an overview of the ActionItem class and discusses:

- ActionItem class methods.
- ActionItem class properties.

The ActionItem class is used to manage action items.

Action items are the tasks that are assigned for completion within an activity guide. These tasks can be linked to specific local or remote components, PeopleSoft queries, PeopleCode programs (an application class or an iScript), self-service process definitions, or external URLs. Within an activity guide, action items are organized into an ordered list; however, in many simple activity guides, action items can

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

be completed in a non-sequential order. Action items can be organized hierarchically with a parent (summary) action item composed of child (detail) action items. Furthermore, an action item can be set to be dependent on the status of another action item.

Action items can be created and maintained within activity guide templates or within activity guide instances. However, typically you will define action items and their details at the template level only. Once an activity guide instance is created, updates to the action items themselves occur programmatically or through actions of the user.

Related Links

"Creating and Maintaining Action Items" (PeopleTools 8.54: Portal Technology)

ActionItem Class Methods

In this section, the ActionItem class methods are presented in alphabetical order.

delete

Syntax

```
delete()
```

Description

Use this method to delete the current action item.

Parameters

None.

Returns

A Boolean value: True if the deletion was successful, False otherwise.

new

Syntax

```
new(item_ID, title, list_ID)
```

Description

Use this method to create and initialize a new action item.

Parameters

item_ID	Specifies the ID for the new action item as a string.
title	Specifies the title for the new action item as a string.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Note: The title is also referred to as the Label property.

list_ID Specifies the activity guide to which the action item belongs as a string.

Returns

None.

Related Links

ItemId
Label
ListId

nextAction

Syntax

```
nextAction()
```

Description

Use this method to return the next *detail* action item in the activity guide that is assigned and is not cancelled or on hold.

Parameters

None.

Returns

An ActionItem object.

open

Syntax

```
open(item_ID)
```

Description

Use this method to retrieve the specified action item definition from the database and set the properties.

Parameters

item_ID Specifies the action item ID as a string.

Returns

None.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

ItemId

prevAction

Syntax

```
prevAction()
```

Description

Use this method to return the previous *detail* action item in the activity guide that is assigned and is not cancelled or on hold.

Parameters

None.

Returns

An ActionItem object.

save

Syntax

```
save()
```

Description

Use this method to save the current action item definition to the database. If this is a new activity guide, then the definition is inserted into the database; otherwise, an existing definition is updated in the database.

Parameters

None.

Returns

A Boolean value: True if the save is successful, False otherwise.

ActionItem Class Properties

In this section, the ActionItem class properties are presented in alphabetical order.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

AppClassID

Description

Use this property to set or return a string value representing the name of the application class that contains the ItemPostProcess method to be invoked for post-processing of this action item.

Note: The full path to the ItemPostProcess method is constructed from three properties: PackageRoot, QualifyPath, and AppClassID

This property is read-write.

Related Links

PackageRoot

QualifyPath

"Configuring Related Data" (PeopleTools 8.54: Portal Technology)

"Performing Pre-Processing for Action Items" (PeopleTools 8.54: Portal Technology)

AssignedToOprid

Description

Use this property to set or return a string value representing the user ID or role to which this action item has been assigned.

Note: While you can specify any user ID or role, only a user or role that has also been assigned Contributor privileges on the template or instance Security page will be allowed to complete the action item. The system will not validate your selection against the users or roles defined on the Security page.

This property is read-write.

Related Links

AssignType

"Defining Action Item Details" (PeopleTools 8.54: Portal Technology)

"Defining Activity Guide Template Security" (PeopleTools 8.54: Portal Technology)

AssignType

Description

Use this property to set or return a string value representing the participant type (user or role) for this action item.

This property is read-write.

Related Links

AssignedToOprid

"Defining Action Item Details" (PeopleTools 8.54: Portal Technology)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

"Defining Activity Guide Template Security" (PeopleTools 8.54: Portal Technology)

CurrentStep

Description

Use this property to set or return a Boolean value indicating whether the current step is the active step currently being worked in the activity guide.

This property is read-write.

DescrLong

Description

Use this property to set or return the description for the action item as a string value.

This property is read-write.

Related Links

"Defining Action Item Details" (PeopleTools 8.54: Portal Technology)

DueDate

Description

Use this property to set or return a Date value representing the date portion of the due date and time.

This property is read-write.

Related Links

DueTm
"Defining Action Item Details" (PeopleTools 8.54: Portal Technology)

DueTm

Description

Use this property to set or return a Time value representing the time portion of the due date and time.

This property is read-write.

Related Links

DueDate
"Defining Action Item Details" (PeopleTools 8.54: Portal Technology)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Field1

Description

Use this property to set or return a string value representing the application data for the first configurable text field to be used in execution of the transaction.

This property is read-write.

Related Links

"Configuring Related Data" (PeopleTools 8.54: Portal Technology)

Field10

Description

Use this property to set or return a string value representing the application data for the fifth configurable yes/no field to be used in execution of the transaction.

This property is read-write.

Related Links

"Configuring Related Data" (PeopleTools 8.54: Portal Technology)

Field2

Description

Use this property to set or return a string value representing the application data for the second configurable text field to be used in execution of the transaction.

This property is read-write.

Related Links

"Configuring Related Data" (PeopleTools 8.54: Portal Technology)

Field3

Description

Use this property to set or return a string value representing the application data for the third configurable text field to be used in execution of the transaction.

This property is read-write.

Related Links

"Configuring Related Data" (PeopleTools 8.54: Portal Technology)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Field4

Description

Use this property to set or return a string value representing the application data for the fourth configurable text field to be used in execution of the transaction.

This property is read-write.

Related Links

"Configuring Related Data" (PeopleTools 8.54: Portal Technology)

Field5

Description

Use this property to set or return a string value representing the application data for the fifth configurable text field to be used in execution of the transaction.

This property is read-write.

Related Links

"Configuring Related Data" (PeopleTools 8.54: Portal Technology)

Field6

Description

Use this property to set or return a string value representing the application data for the first configurable yes/no field to be used in execution of the transaction.

This property is read-write.

Related Links

"Configuring Related Data" (PeopleTools 8.54: Portal Technology)

Field7

Description

Use this property to set or return a string value representing the application data for the second configurable yes/no field to be used in execution of the transaction.

This property is read-write.

Related Links

"Configuring Related Data" (PeopleTools 8.54: Portal Technology)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Field8

Description

Use this property to set or return a string value representing the application data for the third configurable yes/no field to be used in execution of the transaction.

This property is read-write.

Related Links

"Configuring Related Data" (PeopleTools 8.54: Portal Technology)

Field9

Description

Use this property to set or return a string value representing the application data for the fourth configurable yes/no field to be used in execution of the transaction.

This property is read-write.

Related Links

"Configuring Related Data" (PeopleTools 8.54: Portal Technology)

ItemId

Description

Use this property to return a string representing the ID for this action item.

This property is read-only.

Related Links

"Defining Action Item Details" (PeopleTools 8.54: Portal Technology)

Label

Description

Use this property to set or return a string representing the descriptive name (or title) of the action item.

This property is read-write.

Related Links

"Defining Action Item Details" (PeopleTools 8.54: Portal Technology)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ListId

Description

Use this property to set or return a string value representing the ID for the activity guide containing the current action item.

This property is read-write.

Related Links

ListId

PackageRoot

Description

Use this property to set or return a string value representing the name of the application package that contains the ItemPostProcess method to be invoked for post-processing of this action item.

Note: The full path to the ItemPostProcess method is constructed from three properties: PackageRoot, QualifyPath, and AppClassID

This property is read-write.

Related Links

AppClassID

QualifyPath

"Configuring Related Data" (PeopleTools 8.54: Portal Technology)

"Performing Pre-Processing for Action Items" (PeopleTools 8.54: Portal Technology)

ParentId

Description

Use this property to set or return the ID of the summary (or parent) action item. If there is no parent action item, the value returned is ROOT.

This property is read-write.

PercCompl

Description

Use this property to set or return a Number value indicating the percentage completion for this action item.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

"Defining Action Item Details" (PeopleTools 8.54: Portal Technology)

Priority

Description

Use this property to set or return a string value representing the priority for this action item. The valid values are:

Value	*Description*
1	Low
2	Medium
3	High

This property is read-write.

QualifyPath

Description

Use this property to set or return a string value representing the names of each subpackage in the application class hierarchy that define the location of the application class. Separate subpackage names by a colon. If the class is defined in the top-level application package, use a colon only.

Note: The full path to the ItemPostProcess method is constructed from three properties: PackageRoot, QualifyPath, and AppClassID

This property is read-write.

Related Links

AppClassID

PackageRoot

"Configuring Related Data" (PeopleTools 8.54: Portal Technology)

"Performing Pre-Processing for Action Items" (PeopleTools 8.54: Portal Technology)

Remarks

Description

Use this property to set or return the progress remarks for this action item.

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

"Configuring Related Data" (PeopleTools 8.54: Portal Technology)

Required

Description

Use this property to set or return a Boolean value indicating whether the action item is required.

This property is read-write.

Related Links

"Defining Action Item Details" (PeopleTools 8.54: Portal Technology)

Sequence

Description

Use this property to set or return a Number value representing the sequence number for the action item.

This property is read-write.

Related Links

"Creating and Maintaining Action Items" (PeopleTools 8.54: Portal Technology)
"Defining Action Item Details" (PeopleTools 8.54: Portal Technology)

ServiceId

Description

Use this property to set or return a string value representing the ID for the related content service that will be executed when the user clicks this action item in the activity guide pagelet.

This property is read-write.

Related Links

Type
"Defining Action Item Details" (PeopleTools 8.54: Portal Technology)

StartDt

Description

Use this property to set or return a Date value representing the date portion of the start date and time.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

StartTm

"Defining Action Item Details" (PeopleTools 8.54: Portal Technology)

StartTm

Description

Use this property to set or return a Time value representing the time portion of the start date and time.

This property is read-write.

Related Links

StartDt

"Defining Action Item Details" (PeopleTools 8.54: Portal Technology)

Status

Description

Use this property to set or return a string value representing the status of the current action item. Valid values are:

Value	*Description*
0	Not assigned
1	Assigned
2	In progress
3	On hold
4	Completed
5	Cancelled

This property is read-write.

Related Links

"Defining Action Item Details" (PeopleTools 8.54: Portal Technology)

Summary

Description

Use this property to set or return a Boolean value indicating whether the action item is a summary action item. When this property is False, the action item is a detail action item.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-write.

Related Links

"Defining Action Item Details" (PeopleTools 8.54: Portal Technology)

Type

Description

Use this property to set or return a string value representing the type of the related content service that will be executed when the user clicks this action item in the activity guide pagelet. The valid values are:

Value	*Description*
A	Application class URL
C	PeopleSoft component
N	Non-PeopleSoft URL
Q	PeopleSoft query
S	PeopleSoft script

This property is read-write.

Related Links

ServiceId
"Defining Action Item Details" (PeopleTools 8.54: Portal Technology)

Member Class

This section provides an overview of the Member class and discusses:

- Member class methods.
- Member class properties.

The Member class is used to manage activity guide participants.

Related Links

"Defining Activity Guide Template Security" (PeopleTools 8.54: Portal Technology)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Member Class Methods

In this section, the Member class methods are presented in alphabetical order.

IsEqual

Syntax

IsEqual(*&object*)

Description

Use this method to evaluate the equivalency of an object with the current member. Equivalency is established based on the value of two properties: the object's Name and the Type.

Parameters

&object	Specifies the object to be compared as a PTAI_COLLECTION:Collectable object.

Returns

A Boolean value: True if the objects are equivalent, False otherwise.

Related Links

Name
Type

Member

Syntax

Member(*name, type*)

Description

Use this constructor method to initialize a Member object with the specified name and type.

Parameters

name	Specifies the participant’s name as a string value.
type	Specifies the participant type (role or user) as a string value.

Returns

None.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Member Class Properties

In this section, the Member class properties are presented in alphabetical order.

Name

Description

Use this property to return the participant's name as a string value.

This property is read-only.

PrivilegeSetID

Description

Use this property to set or return the privilege level assigned to this participant as a string value.

This property is read-write.

Example

Set or return a value for the PrivilegeSetID property using the Constants class:

Constant Value	*Description*
&PTAI_CONSTANTS.PRIVSET_ADMIN	Administrator
&PTAI_CONSTANTS.PRIVSET_CONTRIBUTOR	Contributor
&PTAI_CONSTANTS.PRIVSET_VIEWER	Viewer

For example:

```
import PTAI_ACTION_ITEMS:*;

Local PTAI_ACTION_ITEMS:Constants &PTAI_CONSTANTS;
Local PTAI_ACTION_ITEMS:Member &member;

&PTAI_CONSTANTS = create PTAI_ACTION_ITEMS:Constants();
&member = create PTAI_ACTION_ITEMS:Member(&name, &type);

&member.PrivilegeSetID = &PTAI_CONSTANTS.PRIVSET_ADMIN;
```

Type

Description

Use this property to return the participant type (user or role) as a string value.

This property is read-only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ContextData Class

This section provides an overview of the ContextData class and discusses:

- ContextData class methods.
- ContextData class properties.

The ContextData class is used to manage contextual data for activity guide templates and instances.

You can define contextual data that will be passed to the activity guide instance when it is created. Contextual data defined as key fields will be used to uniquely identify each activity guide instance. For example, if the employee ID were defined as a key contextual field, then each activity guide instance will be created for a specific employee ID. Contextual data defined as non-key fields is not used to differentiate an instance, but can be passed to the instance nevertheless. For example, non-key data can be displayed in the activity guide pagelet by specifying the Context Visible option for the field. In this way, instead of displaying the employee ID, you could display the employee name in the pagelet.

Related Links

"Defining Advanced Options" (PeopleTools 8.54: Portal Technology)

ContextData Class Methods

In this section, the ContextData class methods are presented in alphabetical order.

ContextData

Syntax

ContextData(*rec_name*, *field_name*, *label*, *value*, *isKey*, *isVisible*)

Description

Use this constructor method to initialize one row of contextual data for an activity guide.

Parameters

rec_name	Specifies the record name that is the source for the contextual field as a string value.
field_name	Specifies the name of the source contextual field as a string value.
label	Specifies an optional label for the contextual field as a string value. This label can be displayed along with the data value in the activity guide pagelet on the WorkCenter page.
value	Specifies the contextual data value as a string.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

isKey	Specifies a Boolean value indicating whether the contextual field is a key field.
isVisible	Specifies a Boolean value indicating whether to display the contextual data and labels in the activity guide pagelet on the WorkCenter page.

Returns

None.

IsEqual

Syntax

```
IsEqual(&object)
```

Description

Use this method to evaluate the equivalency of an object with the current ContextData object. Equivalency is established based on the value of five properties: recname, fieldname, keyLabel, keyValue, and ctxKey.

Parameters

&object	Specifies the object to be compared as a PTAI_COLLECTION:Collectable object.

Returns

A Boolean value: True if the objects are equivalent, False otherwise.

ContextData Class Properties

In this section, the ContextData class properties are presented in alphabetical order.

ctxKey

Description

Use this property to set or return a Boolean value indicating whether the contextual field is a key field.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ctxVisible

Description

Use this property to set or return a Boolean value indicating whether to display the contextual data and labels in the activity guide pagelet on the WorkCenter page.

This property is read-write.

fieldname

Description

Use this property to set or return the name of the source contextual field as a string value.

This property is read-write.

keyLabel

Description

Use this property to set or return an optional label for the contextual field as a string value. This label can be displayed along with the data value in the activity guide pagelet on the WorkCenter page.

This property is read-write.

keyValue

Description

Use this property to set or return the contextual data value as a string.

This property is read-write.

recname

Description

Use this property to set or return the record name that is the source for the contextual field as a string value.

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Chapter 2

AESection Class

Understanding the AESection Class

Before PeopleTools 8, users could perform SQL directly on the Application Engine tables, thereby changing their SQL and Application Engine "flow" in a dynamic manner, prior to running their applications. Some applications, for example, let the user input their "rules" in a user-friendly application, then convert these rules, at save time, into Application Engine constructs.

With PeopleTools 8, Application Engine programs should not perform SQL directly on the Application Engine tables, as they are system tables, and are cached. SQL on the Application Engine tables may not be accurately reflected when the applications are executed, because of the caching mechanism.

To overcome this problem, developers have two basic operations that let them modify their Application Engine programs from their online pages:

- Ability to modify SQL definitions, which are referenced within Application Engine SQL using the PeopleCode SQL class and the meta-SQL function %SQL.
- Ability to dynamically change the execution flow of a given Application Engine section.

Use the AESection class to do the latter. This section object is used to modify the steps and SQL associated with a given section by using PeopleCode.

Before describing the specifics of the AESection class, the following are some general terms to understand:

- *base* section

  The *base* section represents the Application Engine section you are working on. This is the section that you are changing in PeopleCode. In other words, it’s the target section.

- *template* section

  The *template* section represents the Application Engine section that is the source, or "model" for the section you're building. You copy *from* the template section *to* the base section.

The template must exist in the database before you can use it.

If the base section you specify doesn’t exist, a *new* base section is created. This enables you to dynamically create sections as needed.

You can copy steps (and their attributes) from the template to the base. The only attribute of the step you can modify is the SQL statement that gets executed.

Warning! When you open or get an AESection object, (that is, the base section) any existing steps in the section are deleted. You must add a new step to the section before you can modify it.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The main assumption for this class is that your rules are dynamic primarily in the SQL that they execute, but that the structure of the rules are static, or at least defined well enough that a standard template can be applied.

Note that you can't update the Application Engine *actions* that are not SQL-related (that is, PeopleCode, Call Section, or Log Message). In other words, you can't change the PeopleCode associated with a PeopleCode action within a step. You can add a step containing a PeopleCode action to your new section, but you can't change the PeopleCode dynamically.

Related Links

Understanding SQL Class

"%SQL" (PeopleTools 8.54: PeopleCode Language Reference)

"Adding Steps" (PeopleTools 8.54: Application Engine)

How an AESection is Accessed

When an AESection is opened (or accessed), the system first checks if it exists with the given input parameters.

If the base section you specify doesn't exist, a *new* base section is created. This enables you to dynamically create sections as needed. In addition, if the target section doesn't exist, all section-level attributes are copied from the template to the target section. If the target exists, it retains its attribute settings.

If an effective date is specified (with EffDt), but there is no match using that effective date, the AESection is opened using the base effective date of '1900-01-01'.

The market defined for the current component is used for the section to be open. If no section with this market exists, the default GBL is used.

If you open an AESection object from within a running Application Engine program, the market value is set to the value of the current process.

The database platform you're currently running is used as the database platform for the section to be opened. If no section with this database platform exists, the default "none" is used.

To find the correct section to open, the precedence is:

1. Market
2. Database platform
3. Effective date

When a section is closed and its changes are saved, the market and database platform from the system that performed the changes is used as the market and database platform for the modified section.

Let's take an example. Assume that you're running on DB2 UDB for OS/390 and z/OS, and your current market is set to 'MKT'. Assume that you want to open a section called Sect1 in an Application Engine program called TestAppl, and that your data looks something like this:

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Number	Application Engine Program	Application Engine Section	Market	Platform	Effective Date
1	TestAppl	Sect1	USA	DB2	1990-01-01
2	TestAppl	Sect1	USA	None	1900-01-01
3	TestAppl	Sect1	GBL	None	1900-01-01

If you use:

```
&SECTION.Open("TestAppl", "Sect1", "1998-12-14");
```

Then the third section in the previous list is used, because the market takes highest precedence. When the section is saved, the values for market and platform are updated to the current system values.

Warning! When you open or get an AESection object, (that is, any base section) any existing steps in the section are deleted. You must add a new step to the section before you can modify it.
The other attributes of the section, however, are retained, with the exceptions noted previously.

AESection Example

Assume that you have a template section called TEMPLATE in the Application Engine program called MY_APPL. The template looks like this:

Steps	Actions
NewStep1	DO When DO Select SQL
NewStep2	DO Select CallSection

Also, assume that you have a base section called DYN_SECT in the Application Engine program called RULES. When you start, this section looks like this:

Steps	Actions
Step1	DO Select Call Section DO Unit
Step2	Call Section

Here's the PeopleCode:

```
Local AESection &Section;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
&Section = GetAESection("RULES", "DYN_SECT");
/* Open the base section */
&Section.SetTemplate("MY_APPL", "TEMPLATE");
/* Set the template section */
&Section.AddStep("NewStep2");
/* Insert NewStep2     */
/* Do some SQL stuff here  */
&Section.SetSQL("DO_SELECT", &MySql);
/* Modify the SQL in the added step */
&Section.Save();
&Section.Close();
/* Save and close   */
```

The base section looks like this after execution:

Steps	***Actions***
NewStep2	DO Select Call Section

Note: The existing steps in the base section have been *overwritten* by the new step from the template section.

Data Type of an AESection Object

You should declare an AESection object as type AESection. For example:

```
Local AESection &SECTION;
```

Scope of an AESection Object

An AESection object can only be instantiated from PeopleCode.

The AESection Object is designed for use within online pages. Typically, dynamic sections should be constructed in response to an end-user action.

Note: Do not call an AESection object from an Application Engine PeopleCode Action. If you need to access another section, use CallSection Actions instead.

Related Links

"Specifying Actions" (PeopleTools 8.54: Application Engine)

AESection Class Built-in Function

"GetAESection" (PeopleTools 8.54: PeopleCode Language Reference)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

AESection Class Methods

In this section, we discuss each AESection class method, in alphabetical order.

AddStep

Syntax

AddStep(*ae_step_name* [, *NewStepName*])

Description

The given step name from the template section is added as the next step into the base section, and named the existing step name.

Note: When you open or get a section, all the existing steps are deleted. The first time you execute AddStep, you add the first step. The second time you execute AddStep, you add the second step, and so on.

All attributes of the step are copied, including all of its actions. The only changeable attribute of a step are its SQL statements, which can be modified using the SetSQL method. SetSQL is run on the *current* step, that is, the step most recently added.

You can also change the name of the step by using the optional parameter *NewStepName*.

If the step named does not exist in the template, an error occurs. Likewise, if you have not opened or set the template for the section, you receive an error.

Parameters

ae_step_name	Specify the step name from the template to be added as the *next* step in the base section. This parameter takes a string value.
NewStepName	Specify a new name for the step to be added. This parameter is optional, and takes a string value.

Returns

None.

Example

See AESection Example.

Related Links

SetSQL

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Close

Syntax

```
Close()
```

Description

Close closes the AESection object. Any unsaved changes to the section are discarded.

Parameters

None.

Returns

None.

Example

See AESection Example.

Related Links

Save
Open
"GetAESection" (PeopleTools 8.54: PeopleCode Language Reference)

Open

Syntax

```
Open(ae_applid, ae_section, [effdt])
```

Description

The Open method associates the AESection object with the given Application Engine section, based on the *ae_applid* and *ae_section*. If the *effdt* is specified, this is also used to get the section object. In other words, the Open method sets the base section.

Warning! When you open or get an AESection object, (that is, the base section) any existing steps in the section are deleted.

Note: If the base section you specify doesn't exist, a *new* base section is created. This enables you to dynamically create sections as needed. In addition, if the target section doesn't exist, all section-level attributes are copied from the template to the target section. If the target exists, it retains its attribute settings.

If the AESection is still open when you issue the Open method, the previously opened object is discarded and none of the changes saved. To prevent accidentally discarding your changes, you can use the IsOpen property to verify if a section is already open.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The AESection is open based on the Market and database type of your current system.

Parameters

ae_applid	Specify the application ID of the section you want to access. This parameter takes a string value.
ae_section	Specify the section name of the section you want to access. This parameter takes a string value.
effdt	Specify the effective date of the section you want to access (optional). This parameter takes a string value.

Returns

An AESection object.

Example

```
Local AESection &SECTION;

&SECTION = GetAESection("RULES1", "DYN_SECT");

/* do some processing */

&SECTION.Close();

&SECTION.Open("RULES2", "DYN_SECT");

/* do additional processing */
```

Related Links

IsOpen
"GetAESection" (PeopleTools 8.54: PeopleCode Language Reference)

Save

Syntax

```
Save()
```

Description

The Save method saves the section to the database. The AESection object remains open after you use this method. To close the object, you must use the Close method.

You must commit all database changes prior to using this method. This is to avoid locking critical Tools tables and hence freezing all other users. You receive a runtime error message if you try to use this method when there are pending database updates, and your PeopleCode program terminates. You need to commit any database updates prior to using this method. Use the CommitWork function to commit database updates.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

None.

Returns

None.

Example

See AESection Example.

Related Links

Close
Open
"CommitWork" (PeopleTools 8.54: PeopleCode Language Reference)

SetSQL

Syntax

SetSQL(*action_type_string*, *string*)

Description

The SetSQL method replaces the SQL associated with the given action type in the current step in the base section with the SQL in *string*. The *current* step is the latest step that was added using AddStep. The action types are:

- DO_WHEN
- DO_WHILE
- DO_SELECT
- SQL
- DO_UNTIL

Note: All action types must be passed in as strings with quotation marks.

If the action specified does not exist in the current step, an error occurs.

You can use a SQL object as *string*.

```
&SECTION.SetSQL("SQL", &SQL);
```

Parameters

action_type	Specifies the action type of the current step that should be changed. This parameter takes a string value.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

string	Specifies the SQL to be used to replace the SQL in the current step.

Returns

None.

Example

See AESection Example.

Related Links

AddStep
Understanding SQL Class

SetTemplate

Syntax

```
SetTemplate(ae_applid, ae_section)
```

Description

The SetTemplate method sets the template to be used with an AESection object, as identified by *ae_applid* and *ae_section*.

The rules for assigning a template section are similar to the rules for selecting a base section. The selection of market and database platform are done exactly the same. However, the effective date of the template is always set based on the effective date of '1900-01-01'.

You must set the template before you can use any of the other methods.

Parameters

ae_applid	Specify the name of the Application Engine program that contains the section to be used as the template.
ae_section	Specify the name of the Application Engine section in the program to be used as the section template.

Returns

None.

Example

See AESection Example.

Related Links

Open

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

How an AESection is Accessed
"GetAESection" (PeopleTools 8.54: PeopleCode Language Reference)

AESection Class Property

In this section, we discuss the IsOpen AESection property.

IsOpen

Description

If this property is True, the section object is already open. If you try to open a section object that is already open, the open section object is closed and all the changes that haven't been saved are discarded before the object is re-opened.

Example

```
If Not(&MYSECTION.IsOpen) Then
   &MYSECTION.Open(MYAPPLID, SECTION2);
End-If;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Chapter 3

Analytic Calculation Engine Classes

Understanding the Analytic Calculation Engine Classes

PeopleSoft Analytic Calculation Engine comprises a calculation engine plus several PeopleTools features which enable application developers to define both the calculation rules and the display of calculated data within PeopleSoft applications for the purposes of multi-dimensional reporting, data editing and analysis.

More specifically, developers create *analytic models* in order to define the rules which are used to calculate data. Developers also create PeopleSoft Pure Internet Architecture pages with *analytic grids* in order to display the data within PeopleSoft applications. End users view, analyze and make changes to this data. When end users save their changes, PeopleSoft Analytic Calculation Engine recalculates the data and saves the calculated data to the database.

PeopleCode enables developers to manipulate analytic calculation data as follows:

- Use the Analytic Calculation Engine classes to either retrieve or specify data in an instance of an analytic model loaded into the system, and also to calculate (or recalculate) cube values.
- Use the Analytic Calculation Engine metadata classes to manipulate an analytic model definition. For example, you can add cubes to a cube collection or rename an existing user function for a model.
- Use the Analytic Grid classes to manipulate the display of analytic calculation data on a page.
- Use the Analytic Type classes to manipulate an analytic type definition. For example, you can specify a new analytic model for an analytic type definition.

Important! The Analytic Calculation Engine classes are not supported on IBM z/OS and Linux for IBM System z platforms.

Related Links

Understanding the Analytic Calculation Engine Classes
AnalyticGrid Class Reference
AnalyticType Classes Example
Understanding the Analytic Calculation Engine Classes

Using the Analytic Calculation Engine Classes with Application Engine

All Application Engine programs run on the application engine server. This means your program runs on the application engine server, not the analytic server.

PeopleSoft recommends that you put each of the following methods into its own step when you're creating an analytic calculation using a Application Engine program:

- AnalyticInstance Load method

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- AnalyticInstance Unload method
- AnalyticInstance Copy method
- AnalyticInstance Delete method (in case of any readable/writable records in the analytic type)
- AnalyticModel Recalculate method
- CubeCollection SetData method

Also, with the Recalculate method, you should use the Commit after step option.

Running Synchronously

Some of the methods and functions associated with these classes have the option of being run asynchronously. When you run these asynchronously, and not from a Application Engine program, these methods and functions have additional functionality, that is, if the RenServer is configured, a window displays the PeopleSoft Analytic Calculation Engine execution status.

Using Trees

PeopleSoft Analytic Calculation Engine uses trees to establish hierarchies of a dimension's parent-child relationships. PeopleSoft Analytic Calculation Engine uses these hierarchies to:

- Calculate and display aggregated data to end users.
- Enable end users to navigate through data by performing such actions as expanding and collapsing nodes.
- Enable end users to drill down and drill up through data.

It is important to understand that PeopleSoft trees and hierarchies differ in the following manner: You create one tree for each dimension that requires a hierarchy. The analytic model uses that tree to create one hierarchy for one dimension.

Use the AttachTree method to attach a tree to a dimension, and use the DetachTree method to detach the tree from the dimension.

You should be aware of the following restrictions:

- Because the AttachTree method attaches a specific tree to an analytic instance, the system throws an error if the tree's name, setID or effective date is incorrect.
- You can attach only one tree to one dimension at a time.
- If the analytic instance is already loaded into the analytic server, the tree isn't attached until the analytic model is loaded.
- No aggregate data is displayed to the user after you use the DetachTree method.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- If your application loads the analytic model after the tree has been detached, the analytic model doesn't create a hierarchy for the dimension.
- If the analytic instance is already loaded into the analytic server, the DetachTree method isn't applied to the tree until the next time your application loads the analytic instance.

You can only attach a tree to an analytic model before the analytic instance

No aggregate data displayed to user after detach tree.

Related Links

"Understanding the Relationship of PeopleSoft Trees to Analytic Models" (PeopleTools 8.54: Analytic Calculation Engine)

Error Handling

All the Analytic Calculation Engine classes throw PeopleCode exceptions for any fatal error that occurs in the execution of the operation. PeopleSoft recommends enclosing your analytic model programs in try-catch statements. This way, if your program catches the exception, the message set and message number that are associated with the exception object indicate the error.

Using the Messages Property

Use the Messages property to determine whether any errors occurred. The Messages property returns a multi-dimensional array. You can use the Len property of the array class to determine the length of the array. If the array has a length of 0, there are no errors.

Data Types for Analytic Calculation Engine Classes

Every PeopleSoft Analytic Calculation Engine object is declared as its own data type, that is, AnalyticModel objects are declared as type AnalyticModel, CubeCollection objects are declared as type CubeCollection, and so on.

The following are the data types for the PeopleSoft Analytic Calculation Engine classes:

- AnalyticInstance
- AnalyticModel
- CubeCollection

Scope of Analytic Calculation Engine Classes

The Analytic Calculation Engine objects can only be instantiated from PeopleCode.

These objects can be used anywhere you have PeopleCode, that is, in a Application Engine program, an application class, record field PeopleCode, and so on.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Analytic Calculation Engine objects can be of scope Local, Component, or Global.

Analytic Calculation Engine Classes Built-in Functions

"CreateAnalyticInstance" (PeopleTools 8.54: PeopleCode Language Reference)

"GetAnalyticInstance" (PeopleTools 8.54: PeopleCode Language Reference)

AnalyticInstance Class Methods

In this section, we discuss the AnalyticInstance methods. The methods are discussed in alphabetical order.

CheckAsyncStatus

Syntax

CheckAsyncStatus(*OperationID*)

Description

Use the CheckAsyncStatus method to determine the current state of the asynchronous methods, as well as the Load method when executed asynchronously.

Parameters

OperationID Specify the operation ID of the asynchronous operation. This operation ID is returned when one of the asynchronous operations is executed.

Returns

This method returns one of the following values:

Value	*Description*
Less than 0	The operation completed with errors.
0	The operation has not completed yet.
Greater than 0	The operation completed successfully.

Related Links

CheckStatus
Load
Unload

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

CheckStatus

Syntax

CheckStatus()

Description

Use the CheckStatus method to determine the current state of the analytic calculation engine.

Parameters

None.

Returns

This method returns one of the following values:

Value	*Description*
%AnalyticInstance_NotLoaded	The analytic instance has not been loaded into the application server.
%AnalyticInstance_Loading	The analytic instance is being loaded.
%AnalyticInstance_Idle	The analytic instance is idle, that is, not currently running.
%AnalyticInstance_Busy	The analytic instance is currently running.
%AnalyticInstance_ Inaccessible	The analytic instance is currently inaccessible.
%AnalyticInstance_ Terminating	The analytic instance is currently ending.

Related Links

Load
Unload

Copy

Syntax

Copy(*NewID, ForceDelete&Record*)

Description

Use the Copy method to copy all the data and metadata to a new analytic instance from the current analytic instance.

If the specified *NewID* exists, or any data for *NewID* exists, the data is not copied unless *ForceDelete* has been specified as true.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

If a tree is attached to the existing analytic instance, all tree data is also copied to the new analytic instance.

In addition, the analytic instance and the tree information are not copied unless the record specified with the *&Record* parameter is populated with the existing analytic instance ID.

Parameters

NewID	Specify the new analytic instance ID as a string.
ForceDelete	If the specified *NewID* exists, and *ForceDelete* is specified as false, the copy is cancelled. If the specified *NewID* exists, and *ForceDelete* is specified as true, the analytic instance specified by *NewID* is deleted, and a new analytic instance is created from the current ID.
&Record	Specify an already instantiated record object to pass in values to the Copy application package method that's defined with the specified analytic type definition.

Returns

None.

Example

```
&ai.Copy("MYTESTCOPY", True, &MyRecord);
```

Related Links

Delete
Load
Unload
"Understanding Analytic Type Definitions" (PeopleTools 8.54: Optimization Framework)

Delete

Syntax

Delete(*ForceUnload*, *&RecordRef*)

Description

Use the Delete method to remove all the metadata related to the given analytic instance.

Every analytic type definition is defined with an application package that contains three methods: Create, Delete, and Copy. The values in *&RecordRef* are passed to the Delete method.

This method does not delete the analytic instance if the analytic instance is currently loaded. Specify *ForceUnload* as true to unload the analytic instance before deleting it.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

ForceUnload	Specify whether to force the deletion of the analytic instance. This parameter takes a Boolean value. If the analytic instance is currently loaded, specifying true for this parameter forces the analytic instance to be unloaded before it is deleted.
&RecordRef	Specify a record to pass in values to the application package Delete class that's associated with the analytic type definition.

Returns

None.

Example

```
&ai.Delete(TRUE, &Record);
```

Related Links

Unload

"Understanding Analytic Type Definitions" (PeopleTools 8.54: Optimization Framework)

GetAnalyticModel

Syntax

GetAnalyticModel(**Model.***ModelName*)

Description

Use the GetAnalyticModel method to return a reference to an AnalyticModel object.

Parameters

ModelName	Specify the name of the analytic model for which you want to return a reference. The model definition must already exist in Application Designer.

Returns

A reference to an AnalyticModel object or Null.

Related Links

AnalyticModel Class Methods

Load

Syntax

Load(*Sync*, *IdleTimeOut*, **Message.***messagename*)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the Load method to load the AnalyticInstance object executing the method into the analytic server.

If this analytic instance is already loaded, this method fails.

When the analytic instance is loaded, if there are fields in the analytic type definition that haven't been selected but are mapped to a cube or dimension, an error message is logged to the analytic server log and the analytic instance load fails.

If there is a record in the analytic type definition that has none of its fields mapped to a cube or dimension, a warning message is logged to the analytic server log.

Parameters

Sync

Specify whether the analytic instance should be run synchronously or asynchronously. This parameter takes a Boolean value: true if it should be run synchronously, false otherwise.

See Running Synchronously.

IdleTimeOut

Specify, in minutes, the idle time out value. A value of 0 is an infinite time out. A value of -1 indicates that it should use the value specified in the default configuration for the analytic server.

Note: When loading an analytic grid, you should always specify a value of -1.

See "Loading and Unloading Analytic Instances" (PeopleTools 8.54: Analytic Calculation Engine).

Message. ***MessageName***

Specify an application message that should be sent if the analytic server crashes while the analytic instance is loaded.

Note: The message is sent when the analytic server process restarts itself after crashing.

Returns

A string. For asynchronous loads, this string is passed to the CheckAsyncStatus method.

This method returns one of the following values:

Value	*Description*
%AnalyticInstance_NotLoaded	The analytic instance has not been loaded into the analytic server.
%AnalyticInstance_Loading	The analytic instance is being loaded.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Value	*Description*
%AnalyticInstance_Idle	The analytic instance is idle, that is, not currently running.
%AnalyticInstance_Busy	The analytic instance is currently running.
%AnalyticInstance_ Inaccessible	The analytic instance is currently inaccessible.
%AnalyticInstance_ Terminating	The analytic instance is currently terminating.

Related Links

CheckAsyncStatus
Unload

RunAsync

Syntax

RunAsync()

Description

Use the RunAsync method to specify if the analytic instance executing the method should be run in an asynchronous manner.

This method is used only to define the transaction in the analytic type definition in optimization. PeopleSoft Analytic Calculation Engine programs uses the Load method for defining synchronous or asynchronous operation.

Parameters

None.

Returns

None.

Related Links

"Creating Analytic Type Definitions" (PeopleTools 8.54: Optimization Framework)

RunSync

Syntax

RunSync()

Description

Use the RunSync method to specify if the analytic instance executing the method should be run in a synchronous manner.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This method is used only to define the transaction in the analytic type definition in optimization. PeopleSoft Analytic Calculation Engine programs uses the Load method for defining synchronous or asynchronous operation.

Parameters

None.

Returns

None.

Related Links

"Creating Analytic Type Definitions" (PeopleTools 8.54: Optimization Framework)

Terminate

Syntax

```
Terminate()
```

Description

Use the Terminate method to force the termination of an analytic instance loaded in an analytic server.

This method should only be used from PeopleCode running in a Application Engine program to cause an analytic instance loaded in an analytic server to be terminated.

Attempting to terminate an analytic instance that is not loaded or is loaded in a Application Engine process results in a PeopleCode exception.

Although the Terminate method returns instantly, it may take up to a minute before the analytic instance is actually terminated.

Parameters

None.

Returns

None.

Related Links

Load
Unload

Unload

Syntax

```
Unload()
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the Unload method to unload the analytic instance executing the method from the analytic server. After unloading the analytic instance, the analytic server process is restarted.

Parameters

None.

Returns

None.

Example

```
&ai.UnLoad();
```

Related Links

Load

AnalyticInstance Class Properties

In this section, we discuss the AnalyticInstance properties. The properties are discussed in alphabetical order.

AnalyticType

Description

This property returns the name of the analytic type definition for this AnalyticInstance object as a string.

This property is read-only.

ID

Description

This property returns the analytic instance ID of this AnalyticInstance object as an integer.

This property is read-only.

Messages

Description

This property returns a multi-dimensional array of any, containing the messages that occurred.

The first dimension contains the message set number. The second dimension contains the message number. The third dimension contains the number of parameters in that message. The subsequent dimensions contain the values for the parameters. The maximum number of possible dimensions is 8.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

After you access this property, only new messages are returned, that is, messages are only returned once.

This property is read-only.

Related Links

RunSync

AnalyticModel Class Methods

In this section, we discuss the AnalyticModel methods. The methods are discussed in alphabetical order.

AddMember

Syntax

```
AddMember(DimName, MemberName)
```

Description

Use the AddMember method to add the specified dimension member to the specified dimension.

Parameters

DimName	Specify the dimension to which you want to add the member.
MemberName	Specify the name of the member that you want to add to the specified dimension.

Returns

None.

Related Links

GetMembers

RenameMember

AttachTree

Syntax

```
AttachTree(DimName, TreeName, SetID, UserKeyValue, EffDt, NodeName, OverrideRecord,
DetailStartLvl, TreeDiscardLvl)
```

Description

Use the AttachTree method to attach a tree to a dimension. Only one tree can be attached to a dimension at a time. You can only attach a tree before the analytic instance is loaded.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

DimName

Specify the name of the dimension that you want to attach a tree to.

TreeName

Specify the name of the tree that you want to attach to the dimension.

SetId

Specify the table indirection key for the tree. This parameter takes a string value. If the tree structure the tree is based on has its IndirectionMethod specified as "S", you must specify a SetID.

If the tree structure doesn’t have its IndirectionMethod specified as "S", you must enter a Null string (that is, two quotation marks with no blank space between them ("")) for this parameter.

UserKeyValue

Specify the User Key Value for the tree. This parameter takes a string value. If the tree structure the tree is based on has its IndirectionMethod specified as "U" or "B", you must specify a User Key Value.

If the tree structure doesn’t have its IndirectionMethod specified as "U" or "B", you must enter a Null string (that is, two quotation marks with no blank space between them ("")) for this parameter

EffDt

Specify an effective date for this tree. This parameter takes a string value.

NodeName

Specify the tree node used as the dimension hierarchy root. This can be different from the tree root, that is, you can pick a subtree.

OverrideRecord

Specify the name of a record to be used for overriding the aggregate.

See "Working with Overrides" (PeopleTools 8.54: Analytic Calculation Engine).

DetailStartLvl

Specify the tree level number (such as 1 for the node hierarchy root specified by the *NodeName* parameter) at which detail nodes start.

If you specify a value other than 0, any nodes at this level or greater than this level are considered details node, and any nodes with levels less than the start level are considered aggregate nodes

If you specify 0, detail nodes are nodes that don't have parents (a node can be a parent either by having children or by having child ranges).

TreeDiscardLvl

Specify the tree level number (such as 1 for the node hierarchy root specified by the *NodeName* parameter) at which to stop

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

loading the tree. Nodes at this level or at levels greater are discarded. This parameter is only used if it has a value other than 0, and if it has a value greater than *DetailStartLvl*.

Returns

None.

Related Links

DetachTree

GetTree

Understanding Tree Classes

"Understanding the Relationship of PeopleSoft Trees to Analytic Models" (PeopleTools 8.54: Analytic Calculation Engine)

CalculateCube

Syntax

```
CalculateCube(CubeName[, Sync])
```

Description

Use the CalculateCube method to calculate the named cube in synchronous mode.

Parameters

CubeName Specify the name of the cube that you want to calculate.

Sync This parameter is optional and is not used. It is only being included for previous releases. This parameter takes a Boolean value. The value of this parameter is ignored. The cube is always calculated in synchronous mode.

Returns

None.

Related Links

Running Synchronously

Recalculate

DetachTree

Syntax

```
DetachTree(DimName)
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the DetachTree method to detach a tree from the specified dimension.

You can only attach a tree when the analytic instance is not loaded. This method fails if you try to detach a tree while the analytic instance is loaded.

Parameters

DimName	Specify the name of the dimension from which you want to detach a tree.

Returns

None.

Related Links

AttachTree
GetTree
Understanding Tree Classes

GetCubeCollection

Syntax

GetCubeCollection(*CubeCollName*)

Description

Use the GetCubeCollection method to return a reference to a CubeCollection object.

Parameters

CubeCollName	Specify the name of the cube collection to which you want a reference.

Returns

A CubeCollection object if successful.

Related Links

CubeCollection Class

GetCellProperties

Syntax

GetCellProperties(*CubeName, &Node*)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the GetCellProperties method to get information about a cell.

Parameters

CubeName	Specify the name of the cube that contains the cell you want information about.
&Node	Specify an already instantiated array of array of string (a two-dimensional array of string) containing name-value pairs of the node name and the node detail.

Returns

An array of string.

The four strings returned in the array are:

1. Cell type. Values are “Aggregate” or “Detail”
2. User function.
3. Dimension for aggregation, the dimension name.
4. Aggregation reason. Values are: “Dimension Level Override”, “Member Level Override”, “Cube Dimension Level Override”, “None.”

Related Links

Understanding Arrays

GetMembers

Syntax

GetMembers(*DimName, DimFilter*)

Description

Use the GetMembers method to return the names of the members in the specified dimension. You can specify a user function to be used as a filter for the dimension using *DimFilter*.

When filtering hierarchy nodes, if the parent member is filtered, all the child nodes are also filtered.

In order to filter the parent member if all of its children are filtered, the user function should be written such that for the parent node, apply the condition on all of its children, using the FORCHILDREN built-in function. If none of the children satisfy the condition, return zero from the user function, which filters the parent node.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

DimName Specify the name of the dimension from which you want to get the members.

DimFilter Specify a user function that you want to use to filter the dimension.

Returns

A two-dimensional array of any.

The first dimension contains the member names. The second dimension contains the parent of the member. The members are sorted in the hierarchy order.

If the dimension does not have a hierarchy, all members are returned as level one.

For example, if the dimension has the following members:

```
ALLREGIONS
   NORTH AMERICA
      USA
      CANADA
      MEXICO
   EUROPE
      FRANCE
      GERMANY
      ENGLAND
   ASIA
      JAPAN
      CHINA
```

The GetMembers method returns the following:

Member Name	***Level***
ALLREGIONS	Null
NORTHAMERICA	ALLREGIONS
USA	NORTHAMERICA
CANADA	NORTHAMERICA
MEXICO	NORTHAMERICA
EUROPE	ALLREGIONS
FRANCE	EUROPE
ENGLAND	EUROPE
GERMANY	EUROPE
ASIA	ALLREGIONS

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Member Name	*Level*
JAPAN	ASIA
CHINA	ASIA

If the total member is present in the metadata, it is returned as level zero.

Related Links

AddMember
RenameMember

GetTree

Syntax

GetTree(*DimName*)

Description

Use the GetTree method to return an array of string that contains information about the tree that is attached to the specified dimension.

Parameters

DimName Specify the name of the dimension to which a tree is attached.

Returns

An array of string.

The array items have the following format:

1. TreeName
2. SetID
3. UserKeyValue
4. EffDt
5. BranchName
6. Override record name
7. DetailStartLvl
8. TreeDiscardLvl

Related Links

AttachTree

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

DetachTree
Understanding Tree Classes

Recalculate

Syntax

Recalculate(*Sync*)

Description

Use the Recalculate method to recalculates the loaded analytic model. If *Sync* is true, the transaction is synchronous, else it is performed asynchronously.

The Recalculate method always writes any changes to readable, readable and writable, as well as writable records to the database as specified by the analytic type definition.

If you are running in asynchronous mode, this method returns an optional string that contains the operation ID to be used with the CheckAsyncStatus property.

Parameters

Sync	Specify whether the recalculation should be run synchronously or asynchronously. This parameter takes a Boolean value: true if it should be run synchronously, false otherwise.

Returns

A string.

Related Links

CalculateCube
CheckAsyncStatus
AnalyticModelDefn

RenameMember

Syntax

RenameMember(*DimName*, *OrigMemberName*, *NewMemberName*)

Description

Use the RenameMember method to rename a member in the specified dimension.

Parameters

DimName	Specify the dimension that contains the member you want to rename.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

OrigMemberName	Specify the name of the member that you want to rename.
NewMemberName	Specify the new name for the member specified by *OrigMemberName*.

Returns

None.

Related Links

AddMember
GetMembers

AnalyticModel Class Property

In this section, we discuss the AnalyticModel class property.

Messages

Description

This property returns a multi-dimensional array of any containing the messages that occurred during execution of the Recalculate method.

The first dimension contains the message set number. The second dimension contains the message number. The third dimension contains the number of parameters in that message. The subsequent dimensions contain the values for the parameters. The maximum number of possible dimensions is 8.

After you access this property, only new messages are returned, that is, messages are only returned once.

This property is read only.

Related Links

Recalculate

CubeCollection Class

Instantiate a CubeCollection object using the AnalyticModel class GetCubeCollection method.

In cube collections, the total member behaves just as the root of the hierarchy. If it's present, it's displayed first in the list.

Filtering of members in a dimension in the cube collection is similar to filtering members using the AnalyticModel class GetMembers method. If you filter the parent node, the children of that node are filtered as well.

See GetCubeCollection.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

CubeCollection Class Methods

In this section we discuss the CubeCollection class methods. The methods are described in alphabetical order.

CollapseNode

Syntax

CollapseNode(*DimName, &Node*)

Description

Use the CollapseNode method to collapse a node in the dimension specified by *DimName*.

Parameters

DimName Specify the name of the dimension that contains the node you want to collapse.

&Node Specify an already instantiated array of array of string (a two-dimensional array of string) containing name-value pairs of the node name and the node detail. For example:

```
PRODUCTS     Fax Modem
REGION       East
```

Returns

None.

Related Links

ExpandNode

DrillIntoNode

Syntax

DrillIntoNode(*DimName, &Node*)

Description

Use the DrillIntoNode method to display more data for the specified node and dimension. This is very similar to expanding, except that when you expand a node, the top level (node) is still present. When you drill into a node, the top level or levels are no longer displayed.

Parameters

DimName Specify the name of the dimension that contains the node that you want to drill into.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

&Node

Specify an already instantiated array of array of string (a two-dimensional array of string) containing name-value pairs of the node name and the node detail. For example:

```
PRODUCTS   Fax Modem
REGION     East
```

Returns

None.

Related Links

DrillOutOfNode

DrillOutOfNode

Syntax

DrillOutOfNode(*DimName, &Node*)

Description

Use the DrillOutOfNode method to collapse the data that you just expanded.

Parameters

DimName

Specify the name of the dimension that contains the node you want to drill out of.

&Node

Specify an already instantiated array of array of string (a two-dimensional array of string) containing name-value pairs of the node name and the node detail. For example:

```
PRODUCTS     Fax Modem
REGION       East
```

Returns

None.

Related Links

DrillIntoNode

ExpandNode

Syntax

ExpandNode(*DimName, &Nodes, ExpandAll*)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the ExpandNode method to expand the nodes in the specified dimension.

Parameters

DimName	Specify the name of the dimension contains the node that you want to expand.
&Nodes	Specify an already instantiated array of array of string (a two-dimensional array of string) containing name-value pairs of the node name and the node detail.
ExpandAll	Specify whether to expand the sub-nodes or not. This parameter takes a Boolean value; true to expand the nodes, false to not expand the nodes.

Returns

None.

Example

In the following example, both the Accounts and Dept dimensions have hierarchies.

```
Account             Dept

All Acoounts            All Depts
         | ---- 100                |  - ---- A
         |                         |
                | ---- 200                |------   B -| ---D
         |                     |
                |                     | --- E
                | ---- 300
```

When the data is displayed, it will be as follows:

```
All Accounts
          All Depts
     100
          All Depts
     200
          All Depts
     300
          All Depts
```

When you want to expand All Depts under Account 100 , use the following PeopleSoft Analytic Calculation Engine code:

```
BAMCoordinate coord;
coord.SetValue( "Account", "100");
coord.SetValue("Dept" , "All Depts")
ExpandNode("Dept", coord, false)
```

The result of this will have the following:

```
All Accounts
          All Depts
     100
          All Depts
                   A
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
                B
200
     All Depts
300
     All Depts
```

Related Links

CollapseNode

GetData

Syntax

GetData(*&DataRowset*, *StartRow*, *EndRow*[, *NetChanges*])

Description

Use the GetData method to populate a rowset with data from the cube collection.

DataRowset is the rowset into which is put the data. If you specify an already instantiated rowset, the given rowset is populated with the data. If you specify a rowset that has not been instantiated, a new rowset is created, with the record field definition of the desired cube collection.

Parameters

&DataRowset	Specify the rowset into which to put the data. If you specify an already instantiated rowset, the given rowset is populated with the data. If you specify a rowset that has not been instantiated, a new rowset is created, with the record field definition of the desired cube collection.
StartRow	Specify the first row of data to be retrieved, as an integer.
EndRow	Specify the last row of data to be retrieved, as an integer. If you specify a zero for this parameter, all rows are retrieved.
NetChanges	Specify whether all values within the range are returned, or whether just values changed since the last time the Recalculate method was used. This parameter takes a Boolean value: true, return all values, false, return just the changed values. The default value is false.

Returns

None.

Related Links

SetData
Messages
Understanding Rowset Class

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GetDimFilter

Syntax

GetDimFilter(*DimName*)

Description

Use the GetDimFilter method to return the name of the current user function (filter) used with the specified dimension.

Parameters

DimName Specify the name of the dimension for which you want the associated user function (filter).

Returns

A string containing the name of the user function. If there is no filter applied to the dimension, this method returns an empty string.

Related Links

SetDimFilter

GetDimSort

Syntax

GetDimSort(*DimName*)

Description

Use the GetDimSort to return the current sort settings on the specified dimension.

Parameters

DimName Specify the name of the dimension for which you'd like the sort settings.

Returns

An array of any. The array contains the same structure as the signature for the SetDimSort method.

Value	*Description*
Array index 1	IsAscending as Boolean
Array index 2	Key1 as string
Array index 3	IsAscending2 as Boolean

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Value	*Description*
Array index 4	Key2 as string
Array index 5	IsAscending3 as Boolean
Array index 6	Key3 as string

Related Links

SetDimSort

GetLayout

Syntax

```
GetLayout(&SlicerArray, &RowAxisArray, &ColumnAxisArray)
```

Description

Use the GetLayout method to return the current layout for the three axes, (slice, row, and column) on the specified dimension.

Parameters

&SlicerArray Specify an already instantiated array of string containing the list of fields used on the slice axis.

&RowAxisArray Specify an already instantiated array of string containing the list of fields used on the row axis.

&ColumnAxisArray Specify an already instantiated array of string containing the list of fields used on the column axis.

Returns

None.

GetRowCount

Syntax

```
GetRowCount()
```

Description

Use the GetRowCount method to return the total number of rows in the cube collection.

The number of rows is a function of the hierarchy, that is, what is shown or not shown, and filtered values.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

None.

Returns

An integer.

Related Links

GetDimension

GetSlice

Syntax

GetSlice(*&SliceRecord*)

Description

Use the GetSlice method to return the current slice values of all the dimensions.

Parameters

&SliceRecord	Specify an already instantiated record object to hold the values of the slicer record.

Returns

None.

Related Links

SetSlice

SetData

Syntax

SetData(*&DataRowset*)

Description

Use the SetData method to populate the data in the cube collection with the data in the specified rowset.

The system extracts only changed values from the rowset, that is, values marked as updated. .

SetData method also writes the changes to the database for any record marked as writable or readable and writable in the analytic type definition, and mapped to the specified cube collection.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

&DataRowset	Specify the rowset object that contains the data you want to use to populate the cube collection.

Returns

None.

Related Links

GetData
IsChanged
Understanding Rowset Class

SetDimensionOrder

Syntax

```
SetDimensionOrder(&FieldNames)
```

Description

Use the SetDimensionOrder method to specify the order of dimensions for this cube collection.

Parameters

&FieldNames	Specify an already instantiated array of string containing the field names that are the dimensions in the cube collection, in the order you want the dimensions.

Returns

None.

Related Links

SetDimSort

SetDimFilter

Syntax

```
SetDimFilter(DimName, DimFilter)
```

Description

Use the SetDimFilter method to set a dimension filter for the specified dimension in the cube collection.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

DimName	Specify the name of the dimension for which you want to specify a dimension filter.
DimFilter	Specify the name of the dimension filter (user function) that you want to use the dimension.

Returns

None.

Related Links

"Understanding Dimensions" (PeopleTools 8.54: Analytic Calculation Engine)

SetDimSort

Syntax

```
SetDimSort(DimName, IsAscending [, Key1, IsAscending2, Key2, IsAscending3, Key3])
```

Description

Use the SetDimSort method to specify the sorting order for the cube collection.

*Key1, Key2*and *Key3* are optional parameters. If they are not specified, the sorting works as a name sort, that is, it sorts by the name of members in the given dimension, either in ascending or descending order.

If keys are specified, the keys values refer to the names of the cubes to be used as they key. The method orders the members of the dimension based on the value of the cubes for each member. The Boolean parameter *IsAscending* defines whether sorting should be in ascending or descending order. Up to three sort keys may be specified. *Key1* is the primary sort key. *Key2* is used to sub-sort any members that have the same key value under *Key1*, and so on.

The scope of this method is the same as the scope of the AnalyticModel object created in PeopleCode, that is, if the AnalyticModel object was declared with scope Global, this method would have a global scope as well, if it was declared as Local, it would have Local, and so on.

Specifying a null string for *DimName* or for keys one through three removes the current value as a sort value.

Parameters

DimName	Specify the dimension name that you would like sorted.
IsAscending	Specify if the sort order is ascending or descending. This parameter takes a Boolean value: true if the sort is ascending, false if it's descending.
Key1	Specify the name of a key field by which the sort should be ordered. If you do not specify keys, the sort is ordered by the

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

	names of the members in the given dimensions. If you do specify keys, the sort is order by the keys.
IsAscending2	Specify if the sort order for *Key1*is ascending or descending. This parameter takes a Boolean value: true if the sort is ascending, false if it's descending.
Key2	Specify the name of a key field to be used to sub-sort the primary key field *Key1*.
IsAscending3	Specify if the sort order for *Key2*is ascending or descending. This parameter takes a Boolean value: true if the sort is ascending, false if it's descending.
Key3	Specify the name of a key field to be used to sub-sort the primary key field *Key2*.

Returns

None.

SetSlice

Syntax

SetSlice(*&SliceRecord*)

Description

Use the SetSlice method to specify a slice record for this cube collection.

Parameters

&SliceRecord	Specify an already instantiated record as the record to be used for the slice for the cube collection.

Returns

None.

Related Links

GetSlice

ShowHierarchy

Syntax

ShowHierarchy(*DimName, Show, ExpandToLevel*)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the ShowHierarchy method to either hide or display the cube collection hierarchy.

If there is a tree attached to the dimension, and *Show* is false, only the detail level members are shown in the Analytic grid. If *Show* is true, all members including nodes are shown.

When the hierarchy is hidden, the GetData method returns only leaf values. When the hierarchy is displayed, GetData returns node values and leaf values.

The *ExpandToLevel* parameter expands the hierarchy to the level specified. Level indexes start from 0 , the root level.

For example, if you specify *ExpandToLevel* as 1, the grid displays the total (root member) and all the detail members in a dimension with no tree attached.

In the following example, if you specify *ExandToLevel* as 2, the hierarchy would be displayed only to the quarter level, and not to the month level.

```
ALL_TIME
     2003
          Q1
               Jan
               Feb
               Mar
          Q2
               Apr
               May
               Jun
          Q3
               . . .
               . . .
          Q4
     2004
          Q1
          Q2
          Q3
          Q4
```

Parameters

DimName	Specify the name of the dimension for which you want to either display or hide the hierarchy.
Show	Specify whether to display or hide the hierarchy. This parameter takes a Boolean value; true to display the hierarchy, false to hide it.
ExpandToLevel	Specify to what level to expand the hierarchy, as a number.

Returns

None.

Related Links

CollapseNode
ExpandNode
GetData

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

UnsetDimFilter

Syntax

UnsetDimFilter(*DimName*)

Description

Use the UnsetDimFilter method to remove the filter on the specified dimension for the cube collection.

Parameters

DimName	Specify the name of the dimension from which you want to remove the filter.

Returns

None.

Related Links

SetDimFilter

UnsetDimSort

Syntax

UnsetDimSort(*DimName*)

Description

Use the UnsetDimSort method to remove the sorting on the specified dimension for a cube collection. After using this method, the members are returned in the global member order as specified in the analytic model definition.

Parameters

DimName	Specify the name of the dimension from which you want to remove sorting.

Returns

None.

Related Links

SetDimSort

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

CubeCollection Class Property

In this section we discuss the CubeCollection class property.

Messages

Description

This property returns a multi-dimensional array of any containing the messages that occurred during execution of the GetData, SetData, and CalculateCube methods.

The first dimension contains the message set number. The second dimension contains the message number. The third dimension contains the number of parameters in that message. The subsequent dimensions contain the values for the parameters. The maximum number of possible dimensions is 8.

After you access this property, only new messages are returned, that is, messages are only returned once.

This property is read-only.

Related Links

GetData
SetData
CalculateCube

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Chapter 4

Analytic Calculation Engine Metadata Classes

Understanding the PeopleSoft Analytic Calculation Engine Metadata Classes

PeopleSoft Analytic Calculation Engine comprises a calculation engine plus several PeopleTools features which enable application developers to define both the calculation rules and the display of calculated data within PeopleSoft applications for the purposes of multi-dimensional reporting, data editing and analysis.

More specifically, developers create *analytic models* in order to define the rules which are used to calculate data. Developers also create PeopleSoft Pure Internet Architecture pages with *analytic grids* in order to display the data within PeopleSoft applications. End users view, analyze and make changes to this data. When end users save their changes, PeopleSoft Analytic Calculation Engine recalculates the data and saves the calculated data to the database.

PeopleCode enables developers to manipulate analytic calculation data as follows:

- Use the Analytic Calculation Engine classes to either retrieve or specify data in an instance of an analytic model loaded into the system, and also to calculate (or recalculate) cube values.
- Use the Analytic Calculation Engine metadata classes to manipulate an analytic model definition. For example, you can add cubes to a cube collection or rename an existing user function for a model.
- Use the Analytic Grid classes to manipulate the display of analytic calculation data on a page.
- Use the Analytic Type classes to manipulate an analytic type definition. For example, you can specify a new analytic model for an analytic type definition.

Important! The Analytic Calculation Engine Metadata classes are not supported on IBM z/OS and Linux for IBM System z platforms.

Related Links

Understanding the Analytic Calculation Engine Classes
AnalyticGrid Class Methods
Using the Analytic Type Classes

Using the Analytic Calculation Engine Metadata Classes

You can create analytic model definitions using Application Designer. PeopleSoft provides the Analytic Calculation Engine Metadata classes for accessing these definitions at runtime.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

You can also create an analytic model definition in PeopleCode, using the Create method, then saving it to the database using the Save method. After you save the definition, you can access it using Application Designer.

All of the primary objects (dimensions, cube collections, cubes, and so on) are instantiated from an analytic model object, so you only need to create an instance of the analytic model. You can also build a rule as an object instead of as a string.

Inserting and Deleting Objects

If you insert or delete an object from a group of objects, any existing object references are no longer valid. For example, if you use the DeleteCube method, any existing references to cube objects are no longer valid. You need to create any object references after using any insert or delete method.

Building a Rule as an Object

The RuleExpressions sub-package contains several classes. Each of these classes represents the different parts of the analytic calculation engine rule grammar. These objects are created using the Create built-in function and the constructor for that class, then added to the RuleDefn object with the AddRuleExpression method.

The following example creates a cube that uses the Analytic Calculation Engine built-in function AT.

```
Function AT_Cube
   /** AT Cube Rule **/
   &Expected = "AT(GENERAL2, [GENERAL2:4], LOOKUPVALUES)";
   &CubeName = "AT";

   &FunCall = create PT_ANALYTICMODELDEFN:RuleExpressions:FunctionCall(&Constants.F⇒
uncCall_Type_Builtin, &Constants.FuncCall_Builtin_AT);

   &Constant = create PT_ANALYTICMODELDEFN:RuleExpressions:Constant(&Constants.Cons⇒
tant_Type_Literal, "GENERAL2");
   &FunCall.AddArgument(&Constant);

   &MemberRefArgument = create PT_ANALYTICMODELDEFN:RuleExpressions:MemberReference⇒
("GENERAL2", "4");
   &FunCall.AddArgument(&MemberRefArgument);

   &CubeArgument = create PT_ANALYTICMODELDEFN:RuleExpressions:Cube("LOOKUPVALUES")⇒
;
   &FunCall.AddArgument(&CubeArgument);

   &RuleDefn = create PT_ANALYTICMODELDEFN:RuleDefn("");
   &CubeDefn = &Model.GetCube(&CubeName);
   &RuleDefn.AddRuleExpression(&FunCall);
   &RuleDefn.GenerateRule();
   &CubeDefn.SetRule(&RuleDefn);
   If ( Not (Exact(&RuleDefn.RuleString, &Expected))) Then
      &Model.Save();
      Error ("Rule Experession API Failed [Cube " | &CubeName | " Rule]");
   End-If;
End-Function;
```

Error Handling

All the Analytic Calculation Engine Metadata classes throw PeopleCode exceptions for any fatal error that occurs in the execution of the operation. PeopleSoft recommends enclosing your analytic model

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

programs in try-catch statements. This way, if your program catches the exception, the message set and message number that are associated with the exception object indicate the error.

Related Links

Try-Catch Blocks

Data Types of the Analytic Calculation Engine Metadata Objects

Every PeopleSoft Analytic Calculation Engine metadata object is declared as its own data type, that is, AnalyticModelDefn objects are declared as type AnalyticModelDefn, CubeDefn objects are declared as type CubeDefn, and so on.

Scope of Analytic Calculation Engine Metadata Objects

The Analytic Calculation Engine Metadata objects can only be instantiated from PeopleCode.

These objects can be used anywhere you have PeopleCode, that is, in a Application Engine program, an application class, record field PeopleCode, and so on.

Analytic Calculation Engine Metadata objects can be of scope Local, Component or Global.

How to Import the Analytic Calculation Engine Metadata Classes

The Analytic Calculation Engine metadata classes are *not* built-in classes, like Rowset, Field, Record, and so on. They are application classes. Before you can use these classes in your PeopleCode program, you must import them to your program.

An import statement names either all the classes in a package or one particular application class. For importing the Analytic Calculation Engine metadata classes, PeopleSoft recommends that you import all the classes in the application package.

The application package PT_ANALYTICMODELDEFN contains the following subclasses:

- AnalyticModelDefn
- CubeCollectionDefn
- CubeDefn
- DimensionDefn
- ExplicitDimSet
- OrganizerDefn
- RuleDefn

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- UserFunctionDefn

Additionally, there is a sub-application package, RuleExpressions, that contains classes used to build a rule as object instead of as a simple string. This package contains the following classes:

- Assignment
- Comparison
- Constant
- Constants
- Cube
- ExpressionBlock
- FunctionCall
- MemberReference
- Operation
- RuleExpression
- Variable

The import statements that you should use should be as follows:

```
import PT_ANALYTICMODELDEFN:*;
import PT_ANALYTICMODELDEFN:RuleExpressions:*;
```

Using the asterisks after the package name makes all the application classes directly contained in the named package available.

Related Links

Understanding Application Classes

How to Create an Analytic Calculation Engine Metadata Class Object

After you've imported the Analytic Calculation Engine metadata classes, you need to instantiate an instance of the AnalyticModelDefn class, using the constructor for that class and the Create function. After you create the object, you must populate it using either the Get or Create method.

The following example creates an AnalyticModelDefn object from the QE_ALLFUNCTION analytic model definition.

```
import PT_ANALYTICMODELDEFN:*;

Local AnalyticModelDefn &Model;

&Model = create AnalyticModelDefn("QE_ALLFUNCTION");
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

Analytic Calculation Engine Metadata Classes Constructor

Analytic Calculation Engine Metadata Classes Constructor

You must use the constructor for the AnalyticModelDefn class to instantiate an instance of that class. All other metadata objects are instantiated from this class.

AnalyticModelDefn

Syntax

AnalyticModelDefn(*ModelName*)

Description

Use the AnalyticModelDefn constructor to create an AnalyticModelDefn object.

Once the AnalyticModelDefn object is created, you can then execute either the Get or Create methods to ‘instantiate’ the model.

Note: The Delete and Rename methods can only be executed before a model is ‘instantiated’.

Parameters

ModelName	Specify the name of an analytic model definition.

Returns

An AnalyticModelDefn object.

Example

```
&Model = create AnalyticModelDefn("QE_ALLFUNCTION");
```

Related Links

AnalyticModelDefn Class

AnalyticModelDefn Class

Use the AnalyticModelDefn class to view or manipulate an analytic model definition that's already been created in Application Designer, or to create a new definition.

Related Links

AnalyticModel Class Methods

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

AnalyticModelDefn Class Methods

The following section discusses the AnalyticModelDefn class methods. The methods are discussed in alphabetical order.

AddCube

Syntax

AddCube(*CubeName*)

Description

Use the AddCube method to add a new cube to the analytic model definition. This method fails if the cube specified by *CubeName* already exists.

Parameters

CubeName	Specify the name of a new cube that you want to add to the analytic model.

Returns

A CubeDefn object.

Related Links

CopyCube
DeleteCube
GetCube
GetCubeNames
RenameCube
CubeDefn Class

AddCubeCollection

Syntax

AddCubeCollection(*CubeCollectionName*)

Description

Use the AddCubeCollection method to add a new cube collection to the analytic model definition. This method fails if *CubeCollectionName* already exists.

Parameters

CubeCollectionName	Specify the name of a new cube collection that you want to add to the analytic model definition.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

A CubeCollectionDefn object.

Related Links

CopyCubeCollection
DeleteCubeCollection
GetCubeCollection
RenameCubeCollection

AddDimension

Syntax

AddDimension(*DimName*)

Description

Use the AddDimension method to add a new dimension to the analytic model. This method fails if the specified dimension already exists.

When you add a dimension to a cube, the dimension is also automatically added to any cube collections that already contain the cube.

Parameters

DimName	Specify the name of the dimension you want to add. This must be a new dimension.

Returns

A DimensionDef object.

Related Links

CopyDimension
DeleteDimension
GetDimension
DimensionDefn Class

AddExplicitDimensionSet

Syntax

AddExplicitDimensionSet(*ExplicitDimSetName*)

Description

Use the AddExplicitDimensionSet method to add a new explicit dimension set to the analytic model. This method fails if the specified explicit dimension set already exists.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

ExplicitDimSetName	Specify the name of the explicit dimension you want to add. This must be a new explicit dimension.

Returns

An ExplicitDimensionSet object.

Related Links

GetExplicitDimensionSet
DeleteExplicitDimensionSet
CopyExplicitDimensionSet
GetExplicitDimensionSetNames
RenameExplicitDimensionSet

AddOrganizer

Syntax

AddOrganizer(*OrganizerName*)

Description

Use the AddOrganizer method to add a new organizer to the analytic model. This method fails if the organizer specified by *OrganizerName* already exists.

Parameters

OrganizerName	Specify the name of the organizer you want to add.

Returns

An OrganizerDefn object.

Related Links

DeleteOrganizer
GetOrganizer
GetOrganizerNames
RenameOrganizer
OrganizerDefn Class

AddUserFunction

Syntax

AddUserFunction(*UserFunctionName*)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the AddUserFunction method to add a new user function to the analytic model. This method fails if the user function specified by *UserFunction* already exists.

Parameters

UserFunctionName	Specify the name of the new user function that you want to add.

Returns

A UserFunction object.

Related Links

CopyUserFunction
DeleteUserFunction
GetUserFunction
GetUserFunctionNames
RenameUserFunction
UserFunctionDefn Class

CopyCube

Syntax

```
CopyCube(CubeName, NewCubeName)
```

Description

Use the CopyCube method to copy the specified cube to the new cube. This method fails if the cube specified by *CubeName* already exists.

Parameters

CubeName	Specify the name of the cube that you want to copy.
NewCubeName	Specify the name of the new cube that you want to create.

Returns

A CubeDefn object.

Related Links

AddCube
AddCube
GetCube
GetCubeNames
RenameCube
CubeDefn Class

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

CopyCubeCollection

Syntax

CopyCubeCollection(*CubeCollectionName, NewCubeCollectionName*)

Description

Use the CopyCubeCollection method to copy the specified cube collection to a new collection. If the new cube collection specified by *NewCubeCollectionName* already exists, this method fails.

Parameters

CubeCollectionName	Specify the name of the cube collection that you want to copy.
NewCubeCollectionName	Specify the name you want for the new cube collection.

Returns

A CubeCollectionDefn object.

Related Links

AddCubeCollection
DeleteCubeCollection
GetCubeCollection
GetCubeCollectionNames
RenameCubeCollection
CubeCollectionDefn Class

CopyDimension

Syntax

CopyDimension(*DimName, NewDimName*)

Description

Use the CopyDimension method to copy the dimension specified by *DimName* to a new dimension. If the dimension specified by *NewDimName* already exists, this method fails.

Parameters

DimName	Specify the name of the dimension that you want to copy.
NewDimName	Specify the name of the new dimension that you want the data copied to.

Returns

A DimensionDefn object.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

AddDimension
DeleteDimension
RenameDimension

CopyExplicitDimensionSet

Syntax

CopyExplicitDimensionSet(*ExplicitDimSetName, NewExplicitDimSetName*)

Description

Use the CopyExplicitDimensionSet method to copy the explicit dimension set specified by *ExplicitDimSetName* to a new explicit dimension set. If the explicit dimension set specified by *NewExplicitDimSetName* already exists, this method fails.

Parameters

ExplicitDimSetName	Specify the name of the explicit dimension set that you want to copy.
NewExplicitDimSetName	Specify the name of the new explicit dimension set that you want the data copied to.

Returns

An ExplicitDimensionSet object.

Related Links

RenameExplicitDimensionSet
AddExplicitDimensionSet
DeleteExplicitDimensionSet
GetExplicitDimensionSet
GetExplicitDimensionSetNames

CopyTo

Syntax

CopyTo(*NewModelName*)

Description

Use the CopyTo method to copy the AnalyticModelDefn object to a new analytic model specified by *NewModelName*. If the model set specified by *NewModelName* already exists, this method fails.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

NewModelName	Specify the name of a new analytic model definition that you want to create.

Returns

An AnalyticModelDefn object.

Related Links

Create
Delete
Get
Rename
Save

CopyUserFunction

Syntax

```
CopyUserFunction(UserFunctionName, NewUserFunctionName)
```

Description

Use the CopyUserFunction method to copy the user function specified by *UserFunctionName* to a new user function. If the user function specified by *NewUserFunctionName* already exists, this method fails.

Parameters

UserFunctionName	Specify the name of the user function that you want to copy.
NewUserFunctionName	Specify the name of the new user function that you want to add.

Returns

A UserFunctionDefn object.

Related Links

AddUserFunction
DeleteUserFunction
GetUserFunction
GetUserFunctionNames
RenameUserFunction
UserFunctionDefn Class

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Create

Syntax

```
Create()
```

Description

Use the Create method to create, and instantiate, a new model. If you save the new model after you create it, you can then access it in Application Designer as an analytic model definition.

If the model already exists, an exception is thrown.

Parameters

None.

Returns

None.

Related Links

CopyTo
Delete
Get
Rename

Delete

Syntax

```
Delete()
```

Description

Use the Delete method to delete the analytic model executing the method.

You can only use this method on a *closed* analytic model definition, that is, before you use a Get or Create method.

Warning! The delete occurs immediately, that is, the analytic model definition is removed from the database. Only use this method if you're certain you want to delete the definition.

If this model is used by any existing analytic type definition, this method fails.

Parameters

None.

Returns

None.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

CopyTo
Create
Get
Rename
Save

DeleteCube

Syntax

DeleteCube(*CubeName*, *ForceDelete*)

Description

Use the DeleteCube method to delete the cube specified by *CubeName*.

Parameters

CubeName	Specify the name of the cube you want to delete from the analytic model.
ForceDelete	Specify if the cube should always be deleted. This parameter takes a Boolean value. If you specify *ForceDelete* as false, and the cube is used by another part (such as a cube collection) this method fails. If you specify *ForceDelete* as true, and the cube is used by another part, the cube is still deleted.

Returns

None.

Related Links

AddCube
GetCube
GetCubeNames
RenameCube
CubeCollectionDefn Class

DeleteCubeCollection

Syntax

DeleteCubeCollection(*CubeCollectionName*, *ForceDelete*)

Description

Use the DeleteCubeCollection method to delete the cube collection specified by *CubeCollectionName*.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

CubeCollectionName Specify the name of the cube collection that you want to delete from the analytic model.

ForceDelete Specify if the cube collection should always be deleted. This parameter takes a Boolean value. If you specify *ForceDelete* as false, and the cube collection is used by another part (such as an Organizer), this method fails. If you specify *ForceDelete* as true, and the cube collection is used by another part, the cube collection is still deleted.

Returns

None.

Related Links

AddCubeCollection
GetCubeCollection
GetCubeCollectionNames
RenameCubeCollection
CubeCollectionDefn Class

DeleteDimension

Syntax

DeleteDimension(*DimensionName*, *ForceDelete*)

Description

Use the DeleteDimension method to delete the dimension specified by *DimensionName*.

Parameters

DimensionName Specify the name of the dimension you want to delete.

ForceDelete Specify if the dimension should always be deleted. This parameter takes a Boolean value. If you specify *ForceDelete* as false, and the dimension is used by another part (such as a cube), this method fails. If you specify *ForceDelete* as true, and the dimension is used by another part, the dimension is still deleted.

Returns

None.

Related Links

AddDimension

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

CopyDimension
GetDimension
GetDimensionNames
RenameDimension
DimensionDefn Class

DeleteExplicitDimensionSet

Syntax

DeleteExplicitDimensionSet(*ExplicitDimensionSetName*, *ForceDelete*)

Description

Use the DeleteExplicitDimensionSet method to delete the explicit dimension set specified by *ExplicitDimensionSetName*.

Parameters

ExplicitDimensionSetName	Specify the name of the explicit dimension set you want to delete.
ForceDelete	The value of this parameter is ignored in the current release.

Returns

None.

Related Links

AddExplicitDimensionSet
CopyExplicitDimensionSet
GetExplicitDimensionSet
GetExplicitDimensionSetNames
RenameExplicitDimensionSet

DeleteOrganizer

Syntax

DeleteOrganizer(*OrganizerName*, *ForceDelete*)

Description

Use the DeleteOrganizer method to delete the organizer specified by *OrganizerName*.

Parameters

OrganizerName	Specify the name of the organizer you want to delete.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ForceDelete This value is ignored in the current release.

Returns

None.

Related Links

AddOrganizer
GetOrganizer
GetOrganizerNames
RenameOrganizer
OrganizerDefn Class

DeleteUserFunction

Syntax

`DeleteUserFunction``(`*`UserFunctionName, ForceDelete`*`)`

Description

Use the DeleteUserFunction method to delete the user function specified by *UserFunctionName*.

Parameters

UserFunctionName Specify the name of the user function you want to delete.

ForceDelete Specify if the user function should always be deleted. This parameter takes a Boolean value. If you specify *ForceDelete* as false, and the user function is used by another part, this method fails. If you specify *ForceDelete* as true, and the user function is used by another part, the user function is still deleted.

Returns

None.

Related Links

AddUserFunction
CopyUserFunction
GetUserFunction
GetUserFunctionNames
RenameUserFunction
UserFunctionDefn Class

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Get

Syntax

```
Get()
```

Description

Use the Get method to instantiate an instance of the analytic model.

If the model doesn't exist, an exception is thrown.

Parameters

None.

Returns

None.

Related Links

CopyTo
Create
Delete
Rename
Save

GetCube

Syntax

```
GetCube(CubeName)
```

Description

Use the GetCube method to return a reference to the cube specified by *CubeName*. This method fails if the cube specified by *CubeName* doesn't exist.

Parameters

CubeName	Specify the name of the cube that you want a reference to.

Returns

A CubeDefn object.

Related Links

AddCube
CopyCube
DeleteCube

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GetCubeNames
RenameCube
CubeCollectionDefn Class

GetCubeCollection

Syntax

GetCubeCollection(*CubeCollectionName*)

Description

Use the GetCubeCollection method to return a reference to a cube collection. This method fails if the cube collection specified by *CubeCollectionName* doesn't exist.

Parameters

CubeCollection	Specify the name of the cube collection you want a reference to.

Returns

A CubeCollectionDefn object.

Related Links

AddCubeCollection
CopyCubeCollection
DeleteCubeCollection
GetCubeCollection
GetCubeCollectionNames
RenameCubeCollection
CubeCollectionDefn Class

GetCubeCollectionNames

Syntax

GetCubeCollectionNames()

Description

Use the GetCubeCollectionNames method to return an array of strings containing all the names of the cube collections associated with this analytic model.

Parameters

None.

Returns

An array of string.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

AddCubeCollection
CopyCubeCollection
DeleteCubeCollection
GetCubeCollection
RenameCubeCollection
CubeCollectionDefn Class
Understanding Arrays

GetCubeNames

Syntax

GetCubeNames()

Description

Use the GetCubeNames method to return an array of strings containing all the names of the cubes associated with this analytic model.

Parameters

None.

Returns

An array of string.

Related Links

AddCube
CopyCube
DeleteCube
GetCube
RenameCube
CubeCollectionDefn Class
Understanding Arrays

GetDimension

Syntax

GetDimension(*DimName*)

Description

Use the GetDimension method to return a reference to the dimension specified by *DimName*. This method fails if the dimension specified by *DimName* doesn't exist.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

DimName	Specify the name of the dimension that you want a reference to.

Returns

A DimensionDefn object.

Related Links

AddDimension
CopyDimension
DeleteDimension
GetDimensionNames
RenameDimension
DimensionDefn Class

GetDimensionNames

Syntax

```
GetDimensionNames()
```

Description

Use the GetDimensionNames method to return an array of string containing the names of all the dimensions associated with the analytic model.

Parameters

None.

Returns

An array of string.

Related Links

AddDimension
CopyDimension
DeleteDimension
DeleteDimension
GetDimension
RenameDimension
DimensionDefn Class
Understanding Arrays

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GetExplicitDimensionSet

Syntax

GetExplicitDimensionSet(*ExplicitDimSetName*)

Description

Use the GetExplicitDimensionSet method to return a reference to the explicit dimension set specified by *ExplicitDimSetName*. This method fails if the explicit dimension set specified by *ExplicitDimSetName* doesn't exist.

Parameters

ExplicitDimSetName	Specify the name of the explicit dimension set that you want a reference to.

Returns

An ExplicitDimensionSet object.

Related Links

AddExplicitDimensionSet
CopyExplicitDimensionSet
DeleteExplicitDimensionSet
GetExplicitDimensionSetNames

GetExplicitDimensionSetNames

Syntax

GetExplicitDimensionSetNames()

Description

Use the GetExplicitDimensionSetNames method to return an array of string containing the names of all the explicit dimension sets associated with the analytic model.

Parameters

None.

Returns

An array of strings.

Related Links

ExplicitDimensionSet Class

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GetOrganizer

Syntax

GetOrganizer(*OrganizerName*)

Description

Use the GetOrganizer method to return a reference to the organizer specified by *OrganizerName*. This method fails if the organizer specified by *OrganizerName* doesn't exist.

Parameters

OrganizerName	Specify the name of the organizer you want a reference to.

Returns

An OrganizerDefn object.

Related Links

AddOrganizer
DeleteOrganizer
GetOrganizerNames
RenameOrganizer
OrganizerDefn Class

GetOrganizerNames

Syntax

GetOrganizerNames()

Description

Use the GetOrganizerNames method to return an array of string containing the names of all the organizers associated with the analytic model.

Parameters

None.

Returns

An array of string.

Related Links

AddOrganizer
DeleteOrganizer
GetOrganizer
RenameOrganizer

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

OrganizerDefn Class
Understanding Arrays

GetUserFunction

Syntax

GetUserFunction(*UserFunctionName*)

Description

Use the GetUserFunction method to return a reference to the user function specified by *UserFunctionName*. This method fails if the user function specified by *UserFunctionName* doesn't exist.

Parameters

UserFunctionName	Specify the name of a user function that you want a reference to.

Returns

A UserFunctionDefn object

Related Links

AddUserFunction
CopyUserFunction
DeleteUserFunction
GetUserFunctionNames
RenameUserFunction
UserFunctionDefn Class

GetUserFunctionNames

Syntax

GetUserFunctionNames()

Description

Use the GetUserFunctionNames method to return an array of string containing the names of all the user functions associated with the analytic model.

Parameters

None.

Returns

An array of string.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

AddUserFunction
CopyUserFunction
DeleteUserFunction
GetUserFunction
RenameUserFunction
UserFunctionDefn Class
Understanding Arrays

Rename

Syntax

Rename(*NewModelName*)

Description

Use the Rename method to rename the analytic model.

You can only use this method on a *closed* analytic model definition, that is, before you use a Get or Create method.

Parameters

NewModelName	Specify the new name of the model.

Returns

None.

Related Links

Create
Get
Save

RenameCube

Syntax

RenameCube(*CubeName*, *NewCubeName*, *ForceRename*)

Description

Use the RenameCube method to rename the cube specified by *CubeName* to *NewCubeName*.

Parameters

CubeName	Specify the name of the cube you want to rename.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

NewCubeName Specify the new name for the cube.

ForceRename Specify if the cube should always be renamed. This parameter takes a Boolean value. If you specify *ForceRename* as false, and the cube is used by another part (such as a cube collection) this method fails. If you specify *ForceRename* as true, and the cube is used by another part, the cube is still renamed.

Returns

None.

Related Links

AddCube
CopyCube
DeleteCube
GetCube
GetCubeNames
CubeDefn Class

RenameCubeCollection

Syntax

```
RenameCubeCollection(CubeCollectionName, NewCubeCollectionName, ForceRename
```

Description

Use the RenameCubeCollection method to rename the cube collection specified by *CubeCollectionName* to the new name *NewCubeCollectionName*

Parameters

CubeCollectionName Specify the name of the cube collection that you want to rename.

NewCubeCollectionName Specify the new name of the cube collection.

ForceRename Specify if the cube collection should always be renamed. This parameter takes a Boolean value. If you specify *ForceRename* as false, and the cube collection is used by another part (such as an organizer) this method fails. If you specify *ForceRename* as true, and the cube collection is used by another part, the cube collection is still renamed.

Returns

None.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

AddCubeCollection
CopyCubeCollection
DeleteCubeCollection
GetCubeCollection
GetCubeCollectionNames
GetCubeCollectionNames

RenameDimension

Syntax

RenameDimension(*DimName*, *NewDimName*, *ForceRename*)

Description

Use the RenameDimension method to rename the dimension specified by *DimName* to the new name *NewDimName*.

Parameters

DimName	Specify the name of the dimension you want to rename.
NewDimName	Specify the new name of the dimension.
ForceRename	Specify if the dimension should always be renamed. This parameter takes a Boolean value. If you specify *ForceRename* as false, and the dimension is used by another part (such as a cube) this method fails. If you specify *ForceRename* as true, and the dimension is used by another part, the dimension is still renamed.

Returns

None.

Related Links

AddDimension
CopyDimension
DeleteDimension
GetDimension
GetDimensionNames
DimensionDefn Class

RenameExplicitDimensionSet

Syntax

RenameExplicitDimensionSet(*ExplicitDimSetName*, *NewExplicitDimSetName*, *ForceRename*)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the RenameExplicitDimensionSet method to rename the explicit dimension set specified by *ExplicitDimSetName* to the new name *NewExplicitDimSetName*.

Parameters

ExplicitDimSetName	Specify the name of the explicit dimension set you want to rename.
NewExplicitDimSetName	Specify the new name of the explicit dimension set.
ForceRename	The value for this parameter is ignored in the current release.

Returns

None.

Related Links

AddExplicitDimensionSet
CopyExplicitDimensionSet
DeleteExplicitDimensionSet
GetExplicitDimensionSet
RenameExplicitDimensionSet

RenameOrganizer

Syntax

```
RenameOrganizer(OrganizerName, NewOrganizerName, ForceRename)
```

Description

Use the RenameOrganizer method to rename the organizer specified by *OrganizerName* to the new name *NewOrganizerName*.

Parameters

OrganizerName	Specify the name of the organizer you want to rename.
NewOrganizerName	Specify the new name for the organizer.
ForceRename	The value for this parameter is ignored in the current release.

Returns

None.

Related Links

AddOrganizer

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

DeleteOrganizer
GetOrganizer
GetOrganizerNames
OrganizerDefn Class

RenameUserFunction

Syntax

RenameUserFunction(*UserFunctionName*, *NewUserFunctionName*, *ForceRename*)

Description

Use the RenameUserFunction method to rename the user function specified by *UserFunctionName* to the new name *NewUserFunctionName*.

Parameters

UserFunctionName	Specify the name of the user function you want to rename.
NewUserFunctionName	Specify the new name for the user function.
ForceRename	Specify if the user function should always be renamed. This parameter takes a Boolean value. If you specify *ForceRename* as false, and the user function is used by another part this method fails. If you specify *ForceRename* as true, and the user function is used by another part, the user function is still renamed.

Returns

None.

Related Links

AddUserFunction
CopyUserFunction
DeleteUserFunction
GetUserFunction
GetUserFunctionNames
UserFunctionDefn Class

Save

Syntax

Save()

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the Save method to save any changes to the analytic model definition to the database. If the saved model is valid, the value of the IsValid property is set to true, if it is not valid, it is set to false.

The Messages property is populate with messages from the validation that occurs with the save.

Parameters

None.

Returns

None.

Related Links

Create
Validate
IsValid
Messages

Validate

Syntax

```
Validate()
```

Description

Use the Validate method to validate the analytic model definition. This method returns true if the model successfully validates. If this method returns false, the detailed error messages are available through the Messages property.

The IsValid property is not set with this method. The Save method sets the IsValid property.

Parameters

None.

Returns

A Boolean value: true if the analytic model definition validates successfully, false otherwise.

Related Links

Create
Save
Messages
IsValid

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

AnalyticModelDefn Properties

The following section discusses the AnalyticModelDefn class properties. The properties are discussed in alphabetical order.

CircularFormulaWarn

Description

Use this property to specify whether warnings occur when there are circular dependencies as rules are added. This property takes a Boolean value: true if warnings should occur, false otherwise. The default value for this property is false.

This property is read-write.

Description

Description

Use this property to specify the description of the analytic model. This property takes a string value.

This property is read-write.

IsValid

Description

This property indicates if the analytic model is valid, that is, if it would successfully load.

This property is read-only.

Related Links

Validate
Save
"Validating Analytic Models" (PeopleTools 8.54: Analytic Calculation Engine)

LongDescription

Description

Use this property to specify the long description of the analytic model definition. This property takes a string value.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

MaxDelta

Description

This property specifies the maximum number of value changes for the analytic model

This property takes a float value. The default value is 0.

This property is read-write.

Related Links

"Understanding the Analytic Model Definition Creation Process" (PeopleTools 8.54: Analytic Calculation Engine)

MaxIterations

Description

Use this property to specify the maximum number of iterations for the analytic model.

This property take an integer value. The default value is 100.

This property is read-write.

Related Links

Understanding the Analytic Calculation Engine Classes

Messages

Description

This property returns a multi-dimensional array of any that contains the messages that occurred during execution of the Validate or Save methods. This array is only populated after the Validate or Save method has completed successfully.

The first dimension contains the message set number. The second dimension contains the message number. The third dimension contains the number of parameters in that message. The subsequent dimensions contain the values for the parameters. The maximum number of possible dimensions is 8.

This property is read-only.

Related Links

Validate

Save

Name

Description

This property indicates the name of the analytic model.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-only.

Related Links

Rename

ResolveCircularDeps

Description

Use this property to specify if the analytic model should resolve circular dependencies through iteration. This property takes a Boolean value: true if the dependencies should be resolved, false otherwise. The default value is false.

This property is read-write.

DimensionDefn Class

Use the DimensionDefn class to access a dimension that's associated with an analytic model. You instantiate an object of this class using the following AnalyticModelDefn methods:

- AddDimension
- CopyDimension
- GetDimension

DimensionDefn Class Properties

The following section discusses the DimensionDefn class properties. The properties are discussed in alphabetical order.

AggregateSequence

Description

This property indicates the sequence number of this dimension used during aggregation of the analytic model

This property is read-only..

AggregationUserFunction

Description

Use this property to specify the name of a user function that can be used to override the default aggregation for this dimension.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-write.

Comments

Description

Use this property to specify additional notes about the dimension.

This property is read-write.

Name

Description

This property indicates the name of the dimension.

This property is read-only.

Related Links

GetDimensionNames
RenameDimension

TotalMemberName

Description

Use this property to specify a field value that is used at runtime to host the total value for this dimension. If a total isn't applicable, this property has no value.

This property is read-write.

ExplicitDimensionSet Class

Use the ExplicitDimensionSet class to access an explicit dimension set associated with an analytic model. You instantiate an object of this class using one of the following AnalyticModelDefn methods:

- AddExplicitDimensionSet
- CopyExplicitDimensionSet
- GetExplicitDimensionSet

You can also use the GetExplicitDimensionSetNames to return an array containing the names of all the explicit dimension sets associated with the analytic model.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ExplicitDimensionSet Methods

The following section discusses the ExplicitDimensionSet class methods. The methods are discussed in alphabetical order.

AttachDimension

Syntax

AttachDimension(*DimName*)

Description

Use the AttachDimension method to attach a dimension to an explicit dimension set.

Parameters

DimName	Specify the name of the dimension you want to attach.

Returns

None.

Related Links

DetachDimension

DetachDimension

Syntax

DetachDimension(*DimName*)

Description

Use the DetachDimension method to detach a dimension from an explicit dimension set.

Parameters

DimName	Specify the name of the dimension that you want to detach.

Returns

None.

Related Links

AttachDimension

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GetDimensionNames

Syntax

```
GetDimensionNames()
```

Description

Use the GetDimensionNames method to return an array of string that contains the names of all the dimensions associated with the ExplicitDimensionSet.

Parameters

None.

Returns

An array of string.

Related Links

AttachDimension
DetachDimension

ExplicitDimensionSet Properties

The following section discusses the ExplicitDimensionSet class properties. The properties are discussed in alphabetical order.

Name

Description

The Name property returns the name of the explicit dimension set as a string.

This property is read-only.

SequenceNumber

Description

This property returns the sequence number of the explicit dimension set.

This property is read-only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

CubeDefn Class

Use the CubeDefn class to access a cube associated with an analytic model. You instantiate an object of this class using the following AnalyticModelDefn methods:

- AddCubeDefn
- CopyCubeDefn
- GetCubeDefn

CubeDefn Class Methods

The following section discusses the CubeDefn class methods. The methods are discussed in alphabetical order.

AttachDimension

Syntax

`AttachDimension``(`*`DimName`*`)`

Description

Use the AttachDimension method to attach an existing dimension specified by *DimName* to the cube.

Parameters

DimName	Specify the name of the dimension that you want to add.

Returns

None.

Related Links

DetachDimension
GetDimensionNames
UsesDimension
AddDimension
DimensionDefn Class

DetachDimension

Syntax

`DetatchDimension``(`*`DimName`*`)`

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the DetachDimension method to detach the dimension specified by *DimName* from the cube.

Parameters

DimName Specify the name of the dimension that you want to detach from the cube.

Returns

None.

Related Links

AttachDimension
GetDimensionNames
UsesDimension
AddDimension
DimensionDefn Class

GetCauses

Syntax

GetCauses(*CauseType*)

Description

Any cube that affects another cube is a *cause* of that cube. Use the GetCauses method to return a list of all the other cubes that are the causes for this cube.

The cube names are returned in an array of string.

Parameters

CauseType Specify the type of causes you want returned.

Value	*Description*
AnalyticModel_DirectCauses	Only return direct causes.
AnalyticModel_AllCauses	Return all cubes that are causes for this cube, both direct and indirect.
AnalyticModel_AllInputs	Return all cubes that have input to this cube.

Returns

An array of string.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

GetEffects
GetCircularDeps
"Auditing Data Cubes at Design Time" (PeopleTools 8.54: Analytic Calculation Engine)

GetCircularDeps

Syntax

GetCircularDeps(*DimName*)

Description

Use the GetCircularDeps method to return all cubes that have circular dependencies based on the dimension specified by *DimName*.

The cube names are returned in an array of string.

Parameters

DimName	Specify the name of the dimension that you want to find circular dependencies for.

Returns

An array of string.

Related Links

GetCauses
GetEffects

GetDimensionAggregate

Syntax

GetDimensionAggregate(*DimName*)

Description

Use the GetDimensionAggregate method to return the name of the user function used for the aggregate for the dimension specified by *DimName*.

Parameters

DimName	Specify the name of the dimension that you want the aggregate user function.

Returns

A string.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

SetDimensionAggregate
GetUserFunctionNames
UserFunctionDefn Class

GetEffects

Syntax

GetEffects(*EffectType*)

Description

Any cube that is affected by another cube is an *effect* of that cube. Use the GetEffects method to return a list of all the cubes affected by this cube.

The list of cubes is returned as an array of string.

Parameters

EffectType Specify the type of effects you want returned.

Value	*Description*
AnalyticModel_DirectEffects	Only return cubes that are a direct effect on this cube.
AnalyticModel_AllEffects	Return all cubes that are an effect on this cube.

Returns

An array of string.

Related Links

GetCauses
GetCircularDeps
CubeDefn Class Properties

GetDimensionNames

Syntax

GetDimensionNames()

Description

Use the GetDimensionNames method to return an array of string containing the names of all the dimensions associated with the cube.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

None.

Returns

An array of string.

Related Links

AttachDimension
DetachDimension
Understanding Arrays

GetRule

Syntax

```
GetRule()
```

Description

Use the GetRule method to get a reference to a RuleDefn object that represents the rule for this cube.

Parameters

None.

Returns

A RuleDefn object.

Related Links

RuleDefn Class
SetRule

SetDimensionAggregate

Syntax

```
SetDimensionAggregate(DimName, UserFunctionName)
```

Description

Use the SetDimensionAggregate method to specify the user function to be used for the aggregate for the dimension *DimName*.

Parameters

DimName	Specify the name of the dimension for which you want to set the aggregate.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

UserFunctionName	Specify the name of the user function to be used as the aggregate function.

Returns

None.

Related Links

GetDimensionAggregate

SetRule

Syntax

SetRule(*&RuleDefn*)

Description

Use the SetRule method to specify a RuleDefn object to be used as the rule for this cube.

Parameters

&RuleDefn	Specify an already instantiated RuleDefn object that you want to associate with this cube.

Returns

None.

Related Links

GetRule
RuleDefn Class

UsesDimension

Syntax

UsesDimension(*DimName*)

Description

Use the UsesDimension method to determine if the dimension specified by *DimName* is used by this cube.

Parameters

DimName	Specify the name of the dimension that you want to check for.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

A Boolean value: true if the dimension is used, false otherwise.

Related Links

AttachDimension
DetachDimension
GetDimensionNames

CubeDefn Class Properties

The following section discusses the CubeDefn class properties. The properties are discussed in alphabetical order.

CalcAggregates

Description

Use this property to specify if the aggregate is calculated for this cube. This property takes a Boolean value: true if the aggregate is calculated, false otherwise.

This property is read-write.

Comments

Description

Use this property to specify additional notes about the cube.

This property is read-write.

DimensionCount

Description

This property indicates the number of dimensions associated with this cube.

This property is read-only.

FormatType

Description

Use this property to specify the format of the cube. The values are:

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Value	*Description*
AnalyticModel_Format_Number	The format is of type number.
AnalyticModel_Format_Date	The format is of type date.
AnalyticModel_Format_ Member	The format is of type member.
AnalyticModel_Format_Text	The format is of type text.

This property is read-write.

IsVirtual

Description

Use this property to specify if the cube is a virtual cube, that is, if it doesn't store data. This property takes a Boolean value: true if the cube is a virtual cube, false otherwise.

This property is read-write.

Name

Description

This property specifies the name of the cube.

This property is read-only.

ValueDimensionName

Description

Use this property to specify the dimension name for cubes that have a format of member.

This property is only valid when a cube has a format of member.

This property is read-write.

Related Links

FormatType
AnalyticModelDefn Properties

CubeCollectionDefn Class

Use the CubeCollectionDefn class to access cube collections associated with an analytic model. You instantiate an object of this class using the following AnalyticModelDefn class methods:

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- AddCubeCollection
- CopyCubeCollection
- GetCubeCollection

CubeCollectionDefn Class Methods

The following section discusses the CubeCollectionDefn class methods. The methods are discussed in alphabetical order.

AttachCube

Syntax

AttachCube(*CubeName*)

Description

Use the AttachCube method to attach the existing cube specified by *CubeName* to the cube collection.

You should only specify cube collections comprised of derived/work records as the main record for a presentation cube collection.

Parameters

CubeName	Specify the name of the cube you want to attach.

Returns

None.

Related Links

DetachCube
GetCubeNames
CubeDefn Class

DetachCube

Syntax

DetachCube(*CubeName*)

Description

Use the DetachCube to detach the cube specified by *CubeName* from the cube collection.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

CubeName	Specify the name of the cube that you want to detach.

Returns

None.

Related Links

CubeDefn Class
GetCubeNames
CubeDefn Class

GetAggregateMapping

Syntax

GetAggregateMapping(*PartName, IsCube*)

Description

Use the GetAggregateMapping method to return the aggregate mapping field specified by the part *PartName*.

Parameters

PartName	Specify the part name for which you want the aggregate mapping field name.
IsCube	Specify whether the part is a cube or not. This parameter takes a Boolean value, true if the part is a cube, false otherwise.

Returns

A string.

Related Links

GetFieldMapping
GetPersistAggregate
SetAggregateMapping
SetFieldMapping
SetPersistAggregate

GetCubeNames

Syntax

GetCubeNames()

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the GetCubeNames method to return an array of strings containing all the names of the cubes associated with this cube collection.

Parameters

None.

Returns

An array of string.

Related Links

AddCube
CopyCube
DeleteCube
GetCube
RenameCube
CubeDefn Class
Understanding Arrays

GetDimensionNames

Syntax

```
GetDimensionNames()
```

Description

Use the GetDimensionNames method to return an array of string containing the names of all the dimensions associated with the cube collection.

The dimension names are returned in an array of string.

Parameters

None.

Returns

An array of string.

Related Links

AttachDimension
DetachDimension
DimensionDefn Class

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GetDimSort

Syntax

GetDimSort(*DimensionName*)

Description

Use the GetDimSort method return the sorting keys used for the dimension.

The sorting keys are returned as an array of any.

The first string is either true or false. If the first string is true it indicates that the dimension is sorted by the names of the members in the dimension.

The second string then is either true or false, indicating whether the sort is ascending (or descending). If the first string is false it indicates that the dimension is sorted by keys, which are the specified by the other strings in the array. The keys are names of cubes. The strings are as follows:

- Ascend1
- CubeName1
- Ascend2
- CubeName2
- Ascend3
- CubeName3

Parameters

DimensionName	Specify the name of the dimension for which you want the sorting keys.

Returns

An array of any.

Related Links

SetDimSort
GetDimSort
SetDimSort

GetFieldMapping

Syntax

GetFieldMapping(*PartName, IsCube*)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the GetFieldMapping method to return the name of the mapped field name for the part specified by *PartName*.

Parameters

PartName	Specify the name of the part for which you want the mapped field name.
IsCube	Specify whether this part is a cube or not. This parameter takes a Boolean value: true if the part is a cube, false otherwise.

Returns

A string.

Related Links

GetAggregateMapping
SetFieldMapping
SetAggregateMapping

GetFilter

Syntax

`GetFilter``(`*`DimensionName`*`)`

Description

Use the GetFilter method to return the name of the user function used as a filter for the dimension specified by *DimensionName*.

Parameters

DimensionName	Specify the name of the dimension for which you want the filter name.

Returns

A string.

Related Links

SetAggregateMapping
"Filter User Functions" (PeopleTools 8.54: Analytic Calculation Engine)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GetPersistAggregate

Syntax

GetPersistAggregate(*DimensionName*)

Description

Use the GetPersistAggregate method to return the value for the persist aggregate for the dimension specified by *DimensionName.*

Parameters

DimensionName Specify the name of the dimension for which you want to find the persist aggregate value.

Returns

An integer, which is one of the following values:

Value	*Description*
AnalyticModel_AggrType_Root	The persist aggregate type is *Root*, that is, only the root node's data is saved to the database.
AnalyticModel_AggrType_All	The persist aggregate type is *All*, that is, save all of the dimension's aggregate data to the database.
AnalyticModel_AggrType_ None	The persist aggregate type is *None*, that is, do not save any of the dimension's aggregate data to the database.

Related Links

GetAggregateMapping
GetFieldMapping
SetAggregateMapping
SetFieldMapping
SetPersistAggregate

SetAggregateMapping

Syntax

SetAggregateMapping(*PartName, IsCube, AggregateFieldName*)

Description

Use the SetAggregateMapping method to specify an aggregate field for the part specified by *PartName.*

You can map a field to only one data cube or dimension within one cube collection.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

PartName	Specify the name of the part for which you want to add an aggregate field.
IsCube	Specify whether the part is a cube. This parameter takes a Boolean value, true if the part is a cube, false otherwise.
AggregateFieldName	Specify the name of the field to be used to hold the aggregate value.

Returns

A string containing the name of the field that contains the aggregate value.

Related Links

SetPersistAggregate
GetFieldMapping
GetPersistAggregate
SetFieldMapping
SetPersistAggregate

SetDimSort

Syntax

```
SetDimSort(DimName, IsAscending [, CubeName1, IsAscending2, CubeName2, IsAscending3,
CubeName3])
```

Description

Use the SetDimSort method to specify the sorting order for the dimension.

If *CubeName1* is an empty string, the dimension is sorted by the names of the members of the dimension, and the other parameters are not used.

If *CubeName1* is not an empty string, the dimension is sorted by cubes, as specified by the other parameters.

The Boolean parameter *IsAscending* defines whether sorting should be in ascending or descending order. Up to three sort keys may be specified. *CubeName1* is the primary sort key. *CubeName2* is used to sub-sort any members that have the same key value under *CubeName1*, and so on.

Parameters

DimensionName	Specify the name of the dimension that you would like to specify a sort order for.
IsAscending	Specify if the dimension should be sorted in ascending or descending order. This parameter takes a Boolean value: true if the sort should be ascending, false if it should be descending.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

CubeName1	Specify whether the dimension is to be sorted by members or by cubes. If the dimension is to be sorted by members, specify a null string for this parameter. If the dimension is to be sorted by cubes, specify a cube name.
IsAscending2	Specify if the sort for *CubeName1* is in ascending or descending order. This parameter takes a Boolean value: true if the sort is ascending, false if its descending.
CubeName2	Specify the name of a cube to be used to sub-sort the primary sort specified by *CubeName1*.
IsAscending3	Specify if the sort for *CubeName2* is in ascending or descending order. This parameter takes a Boolean value: true if the sort is ascending, false if its descending.
CubeName3	Specify the name of a cube to be used to sub-sort the primary sort specified by *CubeName2*.

Returns

None.

Related Links

SetPersistAggregate
GetDimSort

SetFieldMapping

Syntax

```
SetFieldMapping(PartName, FieldName, IsCube)
```

Description

Use the SetFieldMapping method to specify the name of the main field used for mapping the part specified by *PartName*.

You can map a field to only one data cube or dimension within one cube collection.

Parameters

PartName	Specify the name of the part for which you want to assign a mapping field.
FieldName	Specify the name of the field to be used for the field mapping.
IsCube	Specify whether or not the part is a cube. This parameter takes a Boolean value: true if the part is a cube, false otherwise.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

None.

Related Links

GetAggregateMapping
GetFieldMapping
GetPersistAggregate
SetAggregateMapping
SetPersistAggregate

SetFilter

Syntax

SetFilter(*DimensionName*, *UserFunctionName*)

Description

Use the SetFilter method to specify the user function to be used as a filter for the dimension specified by *DimensionName*.

Parameters

DimensionName	Specify the name of the dimension for which you want to set a filter.
UserFunctionName	Specify the name of a user function to be used as a filter for this dimension.

Returns

None.

Related Links

GetFilter
"Filter User Functions" (PeopleTools 8.54: Analytic Calculation Engine)

SetPersistAggregate

Syntax

SetPersistAggregate(*DimensionName*, *AggregateType*)

Description

Use the SetPersistAggregate to specify the value for the persist aggregate for the dimension specified by *DimensionName*.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

DimensionName Specify the name of the dimension for which you want to set the persist aggregate.

AggregateType Specify the aggregate type. Values are:

Value	*Description*
AnalyticModel_AggrType_Root	The persist aggregate type is *Root*, that is, only the root node's data is saved to the database.
AnalyticModel_AggrType_All	The persist aggregate type is *All*, that is, save all of the dimension's aggregate data to the database.
AnalyticModel_AggrType_ None	The persist aggregate type is *None*, that is, do not save any of the dimension's aggregate data to the database.

Returns

None.

Related Links

GetAggregateMapping
GetFieldMapping
GetPersistAggregate
SetAggregateMapping
SetFieldMapping

UsesCube

Syntax

`UsesCube``(`*`CubeName`*`)`

Description

Use the UsesCube method to determine if the cube collection uses the cube specified by *CubeName*.

Parameters

CubeName Specify the name of the cube that you want to verify.

Returns

A Boolean value, true if the specified cube is part of the cube collection, false otherwise.

Related Links

AttachCube

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

DetachCube
GetCubeNames
CubeDefn Class

UsesDimension

Syntax

UsesDimension(*DimensionName*)

Description

Use the UsesDimension method to determine if the cube collection uses the dimension specified by *DimensionName*.

Parameters

DimensionName	Specify the name of the dimension that you want to verify.

Returns

A Boolean value: true if the dimension is part of the cube collection, false otherwise.

Related Links

CubeDefn Class
DimensionDefn Class

CubeCollectionDefn Class Properties

The following section discusses the CubeCollectionDefn class properties. The properties are discussed in alphabetical order.

AggregateRecName

Description

Use this property to specify the name of the aggregate record associated with this cube collection. This property takes a string value.

This property is read-write.

Comments

Description

Use this property to specify additional notes about the cube collection.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

CubeCount

Description

This property returns the number of cubes in the cube collection.

This property is read-only.

DimensionCount

Description

This property returns the number of dimensions associated with this cube collection.

This property is read-only.

Name

Description

This property returns the name of the cube collection as a string.

This property is read-only.

RecordName

Description

Use this property to specify the name of the main record associated with the cube collection. This property takes a string value.

This property is read-write.

UserFunctionDefn Class

Use the UserFunctionDefn class to access the user functions that are associated with an analytic model. You instantiate an object of this class using the following AnalyticModelDefn class methods:

- AddUserFunction
- CopyUserFunction
- GetUserFunction

UserFunctionDefn Class Methods

In this section we discuss the UserFunctionDefn class methods. They are described in alphabetical order.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GetRule

Syntax

GetRule()

Description

Use the GetRule method to return a RuleDefn object that represents the rule associated with this user function.

Parameters

None.

Returns

A RuleDefn object.

Related Links

RuleDefn Class

SetRule

Syntax

SetRule(*&Rule*)

Description

Use the SetRule method to specify a rule defined by a RuleDefn object to be the rule for this user function.

Parameters

&Rule	Specify an already instantiated RuleDefn object that you want to use as the rule for this user function.

Returns

None.

UserFunctionDefn Class Properties

The following section discusses the UserFunctionDefn class properties. The properties are discussed in alphabetical order.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Comments

Description

Use this property to specify additional notes about the user function.

This property is read-write.

Name

Description

This property specifies the name of the user function.

This property is read-only.

OrganizerDefn Class

Use the OrganizerDefn class to access the organizers that are associated with an analytic model. You instantiate an object of this class using the following AnalyticModelDefn class methods:

- AddOrganizer
- CopyOrganizer
- GetOrganizer

OrganizerDefn Class Methods

The following section discusses the OrganizerDefn class methods. The methods are discussed in alphabetical order.

AttachPart

Syntax

AttachPart(*PartName*, *PartType*)

Description

Use the AttachPart method to attach the part specified by *PartName* to the organizer. The part must exist in the analytic model.

Parameters

PartName	Specify the name of the part that you want to attach.
PartType	Specify the type of part that you want to attach. Values are:

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Value	*Description*
AnalyticModel_Dimension	Attach a dimension.
AnalyticModel_Cube	Attach a cube.
AnalyticModel_ CubeCollection	Attach a cube collection.
AnalyticModel_UserFunction	Attach a user function.

Returns

None.

Related Links

DetachPart
GetPartNames
UsesPart

DetachPart

Syntax

DetachPart(*PartName*, *PartType*)

Description

Use the DetachPart method to detach the part specified by *PartName* from the organizer.

Parameters

PartName Specify the name of the part that you want to detach.

PartType Specify the type of the part that you want to detach. Valid values are:

Value	*Description*
AnalyticModel_Dimension	Detach a dimension.
AnalyticModel_Cube	Detach a cube.
AnalyticModel_ CubeCollection	Detach a cube collection.
AnalyticModel_UserFunction	Detach a user function.

Returns

None.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

AttachPart
GetPartNames
UsesPart

GetPartNames

Syntax

```
GetPartNames()
```

Description

Use the GetPartNames method to return a list of the names of the parts used by the organizer. The names are returned as an array of string.

Parameters

None.

Returns

An array of string.

Related Links

AttachPart
DetachPart
UsesPart

UsesPart

Syntax

```
UsesPart(PartName, PartType)
```

Description

Use the UsesPart method to determine if the organizer uses the part specified by *PartName*.

Parameters

PartName Specify the name of the part that you want to verify.

PartType Specify the type of the part that you want to verify. Valid values are:

Value	*Description*
AnalyticModel_Dimension	A dimension.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Value	*Description*
AnalyticModel_Cube	A cube.
AnalyticModel_ CubeCollection	A cube collection.
AnalyticModel_UserFunction	A user function.

Returns

A Boolean value: true if the part is associated with the organizer, false otherwise.

Related Links

AttachPart
DetachPart
GetPartNames

OrganizerDefn Class Properties

The following section discusses the OrganizerDefn class properties. The properties are discussed in alphabetical order.

Comments

Description

Use this property to specify additional notes about the organizer.

This property is read-write.

Name

Description

This property specifies the name of the organizer.

This property is read-only.

RuleDefn Class

Use the RuleDefn class to access a rule that is associated with an analytic model. You instantiate an object of this class using the GetRule method for both the CubeDefn and UserFunctionDefn classes.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

RuleDefn Class Methods

In this section, we discuss the RuleDefn class methods. The methods are described in alphabetical order.

AddRuleExpression

Syntax

AddRuleExpression(*&Expr*)

Description

Use the AddRuleExpression method to add a rule expression to the rule. Use the classes in the RuleExpression subpackage to create the expression specified by *&Expr*.

After you have finished adding rule expressions to the rule, you need to use the GenerateRule method to generate the rule.

Parameters

&Expr	Specify the rule expression that you want added to the rule definition.

Returns

None.

Related Links

GenerateRule
RuleExpressions Classes

GenerateRule

Syntax

GenerateRule()

Description

Use the GenerateRule method to create the rule string for the rule that represents the current rule expressions that have been added using AddRuleExpression.

Parameters

None.

Returns

None.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

AddRuleExpression
RuleExpressions Classes

RuleDefn Class Property

The following describes the RuleDefn class property.

RuleString

Description

This property specifies a string representation of the rule.

After the rule is returned using the GetRule method, this string represents the existing rule cube or user function.

After AddRuleExpression and GenerateRule are called, this is the string representation of the rule.

This property is read-only.

RuleExpressions Classes

The RuleExpressions classes represents the different parts of the analytic calculation engine rule grammar. These objects are created using the Create built-in function and the constructor for that class, then added to the RuleDefn object with the AddRuleExpression method.

The following are the RuleExpressions classes:

- Assignment
- Comparison
- Constant
- Constants
- Cube
- ExpressionBlock
- FunctionCall
- MemberReference
- Operation
- RuleExpression
- Variable

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Note: The RuleExpression object is the object that the other objects are derived from. You should not create or use this object directly.

Using the Constants Class

All of the constants used with the RuleExpression classes, such as FunctionCall, comparison, operation, and so on, are actually properties of the constants class. You must always instantiate an object of the constants class to use any constants in your program.

For example, the comparison class uses a constant to test whether two operands are equal. Use the following code to create a comparison testing this:

```
&Comparison = create Comparison(&Constants.Comparison_Type_Equal);
```

All of the properties for the constants class are listed with the classes that use them.

Assignment Class

An assignment object represents an assignment statement in an analytic calculation rule.

Use the following to create an assignment object:

```
&Assignment = create Assignment();
```

Assignment Class Method

The following is the method for the assignment class.

GenerateRule

Syntax

GenerateRule()

Description

Use the GenerateRule method to return a string that contains the rule for this object.

Generally you wouldn’t use this method on the individual RuleExpression objects, but instead would use the GenerateRule method on the RuleDefn object.

Parameters

None.

Returns

A string.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

AddRuleExpression
RuleExpressions Classes

Assignment Class Properties

In this section we discuss the assignment class properties. The properties are described in alphabetical order.

Expression

Description

Use the Expression property to specify the right-hand side of the assignment statement.

This property is read-write.

Variable

Description

Use the Variable property to specify the left-hand side of the assignment statement.

This property is read-write.

Comparison Class

A comparison object represents a comparison statement in an analytic calculation rule.

Use the following to create a comparison class object:

```
&Comparison = create Comparison(&Constants.Comparison_Type);
```

Where *Comparison_Type* is one of the following:

Value	*Description*
Comparison_Type_Equal	Compare if the value of Operand1 equals Operand2.
Comparison_Type_Greater	Compare if the value of Operand1 is greater than the value of Operand2.
Comparison_Type_Less	Compare if the value of Operand1 is less than the value of Operand2.
Comparison_Type_GreaterEq	Compare if the value of Operand1 is greater or equal to the value of Operand2.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Value	*Description*
Comparison_Type_LessEq	Compare if the value of Operand1 is less than or equal to the value of Operand2.
Comparison_Type_NotEq	Compare if the value of Operand1 is not equal to the value of Operand2.

Specify Operand1 and Operand2 with the Operand1 and Operand2 comparison class properties.

The following code example creates a rule that compares if the first operand is greater than or equal to the second operand, then adds the rule using the AddArgument method.

```
&Comparison = create Comparison(&Constants.Comparison_Type_GreaterEq);
&Constant = create Constant(&Constants.Constant_Type_Literal, "1000");
&Comparison.Operand1 = &Constant;
&Constant = create Constant(&Constants.Constant_Type_Literal, "100");
&Comparison.Operand2 = &Constant;
&FunCall.AddArgument(&Comparison);
```

Comparison Class Method

The following is the comparison class method.

GenerateRule

Syntax

GenerateRule()

Description

Use the GenerateRule method to return a string that contains the rule for this object.

Generally you wouldn't use this method on the individual RuleExpression objects, but instead would use the GenerateRule method on the RuleDefn object.

Parameters

None.

Returns

A string.

Related Links

AddRuleExpression
RuleExpressions Classes

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Comparison Class Properties

In this section we discuss the comparison class properties. The properties are described in alphabetical order.

Operand1

Description

Use this property to specify the RuleExpression object that is the first operand to be used in the comparison.

This property is read-write.

Operand2

Description

Use this property to specify the RuleExpression object that is the second operand to be used in the comparison.

This property is read-write.

Type

Description

This property returns the type of the comparison that was used to instantiate the comparison object.

The values are:

Value	*Description*
Comparison_Type_Equal	Compare if the value of Operand1 equals Operand2.
Comparison_Type_Greater	Compare if the value of Operand1 is greater than the value of Operand2.
Comparison_Type_Less	Compare if the value of Operand1 is less than the value of Operand2.
Comparison_Type_GreaterEq	Compare if the value of Operand1 is greater than or equal to the value of Operand2.
Comparison_Type_LessEq	Compare if the value of Operand1 is less than or equal to the value of Operand2.
Comparison_Type_NotEq	Compare if the value of Operand1 is not equal to the value of Operand1.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-only.

Constant Class

A constant object represents a constant statement in an analytic calculation rule.

Note: This is not the same as the constants class.

A constant object exposes all the constants that are passed to the constructors of the various RuleExpression objects.

Use the following to create a constant class object:

```
&Constant = create Constant(&Constants.Constant_Type, [&Constants.]Constant_Value);
```

where *Constant_Type* is one of the following:

Value	***Description***
Constant_Type_Builtin	The *Constant_Value*is an analytic calculation engine built-in function. In this instance, the constant value must be prefaced with an already instantiated constants object. For possible values, see below.
Constant_Type_Number	The *Constant_Value* is a number.
Constant_Type_Literal	The *Constant_Value* is a string.

When the *Constant_Type* is Constant_Type_Builtin, the *Constant_Value* is one of the following:

- Constant_Builtin_ALL
- Constant_Builtin_BASE_E
- Constant_Builtin_DEFAULT
- Constant_Builtin_DETAILS
- Constant_Builtin_DIRECT
- Constant_Builtin_FALSE
- Constant_Builtin_FORWARD
- Constant_Builtin_PI
- Constant_Builtin_REVERSE
- Constant_Builtin_TRUE

The following code creates a PeopleSoft Analytic Calculation Engine built-in function to be used as a constant:

```
&Constant = create Constant(&Constants.Constant_Type_Builtin, &Constants.Constan⇒
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
t_Builtin_REVERSE);
```

The following code creates a literal (string) constant:

```
&Constant = create Constant(&Constants.Constant_Type_Literal, "GENERAL");
```

The following code creates a number constant:

```
&Constant = create Constant(&Constants.Constant_Type_Number, "-1");
```

Constant Class Method

The following is the constant class method.

GenerateRule

Syntax

GenerateRule()

Description

Use the GenerateRule method to return a string that contains the rule for this object.

Generally you wouldn't use this method on the individual RuleExpression objects, but instead would use the GenerateRule method on the RuleDefn object.

Parameters

None.

Returns

A string.

Constant Class Properties

In this section we discuss the constant class properties. The properties are described in alphabetical order.

Type

Description

This property returns the value of the *Constant Type* that was used to instantiate the constant class object.

This property is read-only.

Related Links

Constant Class

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Value

Description

This property returns the value of the *Constant Value* that was used to instantiate the constant class object.

This property is read-only.

Related Links

Constant Class

Constants Class

All of the constants used with the RuleExpression classes, such as FunctionCall, comparison, operation, and so on, are actually properties of the constants class. You must always instantiate an object of the constants class to use any constants in your program.

For example, the comparison class uses a constant to test whether two operands are equal. Use the following code to create a comparison testing this:

```
&Comparison = create Comparison(&Constants.Comparison_Type_Equal);
```

All of the properties for the constants class are listed with the classes that use them.

Cube Class

A cube object represents a cube statement in an analytic calculate engine rule.

Use the following to create a cube object.

```
&Assignment = create Cube("CubeName");
```

Cube Class Methods

In the following section, we discuss the cube class methods. The methods are described in alphabetical order.

AddIndex

Syntax

AddIndex(*&MemberReference*)

Description

Use the AddIndex method to add a MemberReference object to the cube.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

&MemberReference	Specify an already instantiated MemberReference object to be added to the cube.

Returns

None.

Related Links

MemberReference Class

GenerateRule

Syntax

`GenerateRule``()`

Description

Use the GenerateRule method to return a string that contains the rule for this object.

Generally you wouldn't use this method on the individual RuleExpression objects, but instead would use the GenerateRule method on the RuleDefn object.

Parameters

None.

Returns

A string.

GetIndexes

Syntax

`GetIndexes``()`

Description

Use the GetIndexes method to return an array of MemberReference's (indexes) for this cube. These MemberReferences are the MemberReferences that were added with the AddIndex method.

Parameters

None.

Returns

An array of MemberReference objects.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

MemberReference Class

AddIndex

Cube Class Property

The following is the cube class property.

Name

Description

This property indicates the name of the cube that was used to instantiate the cube object.

This property is read-only.

ExpressionBlock Class

For some function, you need multi-statement nested expressions. You need to use the ExpressionBlock class to group these expressions. For example, all the statements inside of a FOR statement should be included in an expression block.

```
FOR(&Index, 1, PERIOD,
   SET(&Value, &Value + 1);
   SET(&countPl4, &countPl4 + 4);
);
```

Use the following code to create an ExpressionBlock object:

```
&ExpressionBlock = create ExpressionBlock();
```

ExpressionBlock Methods

In the following section we discuss the ExpressionBlock class methods. The methods are described in alphabetical order.

AddRuleExpression

Syntax

AddRuleExpression(*&Expr*)

Description

Use the AddRuleExpression method to add an expression to the expression block and the rule. Use the classes in the RuleExpression subpackage to create the expression specified by *&Expr*.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Note: As the rule string is generated, the system adds a ";" after each RuleExpression, except the last.

Parameters

&Expr	Specify the rule expression that you want added to the expression block.

Returns

None.

GetRuleExpressions

Syntax

`GetRuleExpressions``()`

Description

Use the GetRuleExpressions to return an array of rule expression objects that have been added using the AddRuleExpression method.

Parameters

None.

Returns

An array of RuleExpression objects.

FunctionCall Class

A FunctionCall object represents a function call statement in an analytic calculation engine rule.

Use the following code to create a FunctionCall object:

```
&Assignment = create FunctionCall(&Constants.Function_Call_Type, [&Constants.]Funct⇒
ion_Call_Name);
```

Where *Function_Call_Type* can be one of the following:

Value	***Description***
FunctionCall_Type_Builtin	Specifies that the function call is a PeopleSoft Analytic Calculation Engine built-in functions. In this instance, the function name must be prefaced with an already instantiated constants object. For the built-in function values used with *Function_Call_Name*, see below.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Value	*Description*
FunctionCall_Type_UserFunc	Specifies that the function call is a user function. The value specified for *Function_Call_Name* must be an already created user function defined in this analytic model. Specify this value as a string.

When the *Function_Call_Type* is specified as Function_Call_Type_Builtin, the *Function_Call_Name* must be one of the following:

- FunctionCall_Builtin_ABS
- FunctionCall_Builtin_ACOS
- FunctionCall_Builtin_ARGUMENTS
- FunctionCall_Builtin_ASC
- FunctionCall_Builtin_ASIN
- FunctionCall_Builtin_AT
- FunctionCall_Builtin_ATAN
- FunctionCall_Builtin_BREAK
- FunctionCall_Builtin_CASE
- FunctionCall_Builtin_CHANGE
- FunctionCall_Builtin_CHILDCOUNT
- FunctionCall_Builtin_CHR
- FunctionCall_Builtin_CONSOL
- FunctionCall_Builtin_COS
- FunctionCall_Builtin_CUBEID
- FunctionCall_Builtin_CUBSUM
- FunctionCall_Builtin_CUMAVG
- FunctionCall_Builtin_DAVG
- FunctionCall_Builtin_DAY
- FunctionCall_Builtin_DCOUNT
- FunctionCall_Builtin_DDB
- FunctionCall_Builtin_DEC
- FunctionCall_Builtin_DLOOKUP
- FunctionCall_Builtin_DMAX

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- FunctionCall_Builtin_DMIN
- FunctionCall_Builtin_DSUM
- FunctionCall_Builtin_E
- FunctionCall_Builtin_FIRST
- FunctionCall_Builtin_FOR
- FunctionCall_Builtin_FORCHILDREN
- FunctionCall_Builtin_FORMEMBERS
- FunctionCall_Builtin_FV
- FunctionCall_Builtin_GROUPAVG
- FunctionCall_Builtin_GROUPBY
- FunctionCall_Builtin_GROUPMAX
- FunctionCall_Builtin_GROUPMIN
- FunctionCall_Builtin_GROUPSUM
- FunctionCall_Builtin_GROW
- FunctionCall_Builtin_IF
- FunctionCall_Builtin_IFNPV
- FunctionCall_Builtin_INC
- FunctionCall_Builtin_INDICATE
- FunctionCall_Builtin_INPUT
- FunctionCall_Builtin_INSUBTREE
- FunctionCall_Builtin_INTERCEPT
- FunctionCall_Builtin_IRR
- FunctionCall_Builtin_ISINPUT
- FunctionCall_Builtin_LEFT
- FunctionCall_Builtin_LEN
- FunctionCall_Builtin_LN
- FunctionCall_Builtin_LOWER
- FunctionCall_Builtin_MATCH
- FunctionCall_Builtin_MAX

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- FunctionCall_Builtin_MBR2TEXT
- FunctionCall_Builtin_MEDIAN
- FunctionCall_Builtin_MEMBER
- FunctionCall_Builtin_MID
- FunctionCall_Builtin_MIN
- FunctionCall_Builtin_MOD
- FunctionCall_Builtin_MONTH
- FunctionCall_Builtin_NEXT
- FunctionCall_Builtin_NPER
- FunctionCall_Builtin_NUM2TEXT
- FunctionCall_Builtin_NUMMEMBERS
- FunctionCall_Builtin_NPV
- FunctionCall_Builtin_PARAMETER
- FunctionCall_Builtin_PARENT
- FunctionCall_Builtin_PCT
- FunctionCall_Builtin_PERCENTILE
- FunctionCall_Builtin_PI
- FunctionCall_Builtin_PMT
- FunctionCall_Builtin_PREV
- FunctionCall_Builtin_PREVSELF
- FunctionCall_Builtin_PV
- FunctionCall_Builtin_QUARTILE
- FunctionCall_Builtin_RAND
- FunctionCall_Builtin_RATE
- FunctionCall_Builtin_REPLACE
- FunctionCall_Builtin_RETURN
- FunctionCall_Builtin_RIGHT
- FunctionCall_Builtin_ROUND
- FunctionCall_Builtin_SELF

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- FunctionCall_Builtin_SET
- FunctionCall_Builtin_SIN
- FunctionCall_Builtin_SLN
- FunctionCall_Builtin_SLOPE
- FunctionCall_Builtin_SQRT
- FunctionCall_Builtin_STDEV
- FunctionCall_Builtin_SYD
- FunctionCall_Builtin_TAN
- FunctionCall_Builtin_TEXT2MBR
- FunctionCall_Builtin_TEXT2NUM
- FunctionCall_Builtin_THIS
- FunctionCall_Builtin_THISCUBE
- FunctionCall_Builtin_TRUNC
- FunctionCall_Builtin_UPPER
- FunctionCall_Builtin_VAR
- FunctionCall_Builtin_WHILE
- FunctionCall_Builtin_YEAR

The following code creates a function call using a PeopleSoft Analytic Calculation Engine built-in function.

```
   &FunCall = create FunctionCall(&Constants.FuncCall_Type_Builtin, &Constants.Func⇒
Call_Builtin_ABS);
```

Related Links

"Built-in Function Reference" (PeopleTools 8.54: Analytic Calculation Engine)

FunctionCall Class Methods

In this section we discuss the FunctionCall class methods. The methods are described in alphabetical order.

AddArgument

Syntax

AddArgument(*&RuleExpression*)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the AddArgument method to add an argument to this function call.

Parameters

&RuleExpression	Specify an already instantiated rule expression object, such as a cube object.

Returns

None.

GenerateRule

Syntax

`GenerateRule``()`

Description

Use the GenerateRule method to return a string that contains the rule for this object.

Generally you wouldn't use this method on the individual RuleExpression objects, but instead would use the GenerateRule method on the RuleDefn object.

Parameters

None.

Returns

A string.

GetArguments

Syntax

`GetArguments``()`

Description

Use the GetArguments method to return an array of RuleExpression objects associated with this FunctionCall. These are the RuleExpression objects that were added using the AddArgument method.

Parameters

None.

Returns

An array of RuleExpression objects.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

AddArgument

FunctionCall Class Properties

In this section we discuss the FunctionCall class properties. The properties are described in alphabetical order.

Name

Description

This property specifies the name of the function call used to instantiate the FunctionCall object.

This property is read-only.

Type

Description

This property specifies the type of the function call used to instantiate the FunctionCall object.

This property is read-only.

MemberReference Class

A MemberReference object represents a member in an analytic calculation engine rule.

Use the following code to create a MemberReference object:

```
&Member = create MemberReference(DimensionName, MemberName);
```

MemberReference Class Method

This section discusses the MemberReference class method.

GenerateRule

Syntax

GenerateRule()

Description

Use the GenerateRule method to return a string that contains the rule for this object.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Generally you wouldn't use this method on the individual RuleExpression objects, but instead would use the GenerateRule method on the RuleDefn object.

Parameters

None.

Returns

A string.

MemberReference Class Properties

In this section we discuss MemberReference class properties. The properties are described in alphabetical order.

Dimension

Description

This property specifies the name of the dimension used to create the MemberReference object.

This property is read-only.

Member

Description

This property specifies the name of the member used to create the MemberReference object.

This property is read-only.

Operation Class

An operation object represents an operation in an analytic calculation engine rule. The operation is generally some type of mathematical function performed between two operands. Specify the operands for the operation using the Operand1 and Operand2 operation class properties.

Use the following code to create an operation object:

```
&Comparison = create Operation(&Constants.Operation_Type);
```

Where *Operation_Type* has a value of one of the following:

Value	***Description***
Operation_Type_Plus	The operation is addition.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Value	*Description*
Operation_Type_Minus	The operation is subtraction.
Operation_Type_Mult	The operation is multiplication.
Operation_Type_Div	The operation is division.
Operation_Type_And	Use a logical AND with the operation.
Operation_Type_Or	Use a logical OR with the operation.
Operation_Type_Not	Use a logical NOT with the operation.
Operation_Type_Neg	Use a mathmatical negate with the operation.
Operation_Type_Exp	Use a mathmatical exponent with the operation.

The following code creates an operations that is a multiplication between two operands.

```
&operation = create Operation(&Constants.Operation_Type_Mult);
&Constant = create Constant(&Constants.Constant_Type_Literal, "PI");
&operation.Operand1 = &Constant;
&Constant = create Constant(&Constants.Constant_Type_Literal, "SLOPE");
&operation.Operand2 = &Constant;
&FunCall.AddArgument(&operation);
```

Operation Class Method

The following is the operation class method.

GenerateRule

Syntax

GenerateRule()

Description

Use the GenerateRule method to return a string that contains the rule for this object.

Generally you wouldn't use this method on the individual RuleExpression objects, but instead would use the GenerateRule method on the RuleDefn object.

Parameters

None.

Returns

A string.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Operation Class Properties

In this section we discuss the operation class properties. The properties are described in alphabetical order.

Operand1

Description

Use this property to specify the RuleExpression object that is the first operand to be used in the operation.

This property is read-write.

Operand2

Description

Use this property to specify the RuleExpression object that is the second operand to be used in the operation.

This property is read-write.

Type

Description

This property returns the type of the operation used to instantiate the operation object.

The values for this property are:

Value	*Description*
Operation_Type_Plus	The operation is addition.
Operation_Type_Minus	The operation is subtraction.
Operation_Type_Mult	The operation is multiplication.
Operation_Type_Div	The operation is division.
Operation_Type_And	Use a logical AND for the operation.
Operation_Type_OR	Use a logical OR for the operation.
Operation_Type_Not	Use a logical NOT for the operation.
Operation_Type_Neg	Use a mathmatical negate for the operation.
Operation_Type_Exp	Use a mathmatical exponent for the operation.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Variable Class

A variable object represents a variable in an analytic calculation engine rule.

Use the following code to create a variable object:

```
&Variable = create Variable(&Constants.Variable_Type, "Variable_Name");
```

Where *Variable_Type* is one of the following:

Value	***Description***
Variable_Type_Auto	Use a local variable.
Variable_Type_Expression	The variable is in an expression. Specify an already instantiated rule expression object for the *Variable_Name.*
Variable_Type_Dimension	The variable is a dimension name. Specify a dimension name for the *Variable_Name*.

The following code example creates a variable, then adds it to the rule.

```
&Variable = create Variable(&Constants.Variable_Type_Auto, "StartVal");
&FunCall.AddArgument(&Variable);
```

Variable Class Method

The following is the variable class method.

GenerateRule

Syntax

GenerateRule()

Description

Use the GenerateRule method to return a string that contains the rule for this object.

Generally you wouldn’t use this method on the individual RuleExpression objects, but instead would use the GenerateRule method on the RuleDefn object.

Parameters

None.

Returns

A string.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Variable Class Properties

In this section we discuss the variable class properties. The properties are described in alphabetical order.

Name

Description

This property specifies the name of the variable that was used to create the variable object, passed in the constructor.

This property is read-only.

Type

Description

This property specifies the type of the variable, passed in the constructor. The possible values are:

Value	*Description*
Variable_Type_Auto	A local variable.
Variable_Type_Expression	The variable is an expression. Specify an already instantiated rule expression object for the *Variable_Name.*
Variable_Type_Dimension	The variable is a dimension name. Specify a dimension name for the *Variable_Name*.

This property is read-only.

Analytic Model Metadata Classes Examples

The following are some examples of the most general cases of using the Analytic Model Metadata classes.

Creating an Analytic Model Code Example

The following code creates an analytic model definition “from scratch” without retrieving an existing definition from the Application Designer, adds parts such as dimensions, cubes, and cube collections, then saves the definition.

```
import PT_ANALYTICMODELDEFN:*;

Function CreateGENXModel

   Local PT_ANALYTICMODELDEFN:AnalyticModelDefn &Model;
   Local PT_ANALYTICMODELDEFN:UserFunctionDefn &UserFunc;
   Local PT_ANALYTICMODELDEFN:DimensionDefn &Dim;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
   Local PT_ANALYTICMODELDEFN:CubeDefn &Cube;
   Local PT_ANALYTICMODELDEFN:CubeCollectionDefn &CubeColl;
   Local array of string &arr;

   &ACEMODELID = QE_ACE_META_WK.QE_ACE_MODELID.Value;

   &Model = create PT_ANALYTICMODELDEFN:AnalyticModelDefn(&ACEMODELID);

   &Model.Create();

   /* Model Properties */


   &Model.Description = QE_ACE_META_WK.DESCR;
   &Model.LongDescription = QE_ACE_META_WK.DESCR200;
   &Model.MaxDelta = QE_ACE_META_WK.QE_ACE_MAXDELTA_FL;
   &Model.MaxIterations = QE_ACE_META_WK.QE_ACE_MAXITER_FLD;

   If (QE_ACE_META_WK.QE_ACE_CIRCWARN_FL.Value = 0) Then
      &Circ = True;
   Else
      &Circ = False;
   End-If;

   If (QE_ACE_META_WK.QE_ACE_RESOLVE_FLD.Value = 0) Then
      &Resolve = True;
   Else
      &Resolve = False;
   End-If;

   &Model.ResolveCircularDeps = &Resolve;
   &Model.CircularFormulaWarn = &Circ;


   /* Add User Functions */

   &UserFunction = &Model.AddUserFunction("FILTERPRODUCTS");
   &Rule = &UserFunction.GetRule();
   &Rule.RuleString = "IF( ((UNIT_COST = 0) .AND. (UNITS_SOLD = 0) .AND. (PROD_SALE⇒
S =0 )) , RETURN(0), RETURN(1))";
   &UserFunction.SetRule(&Rule);


   /* Add the Dimensions */
   &Dim = &Model.AddDimension("MONTH");

   &Dim = &Model.AddDimension("PRODUCTS");
   &Dim.TotalMemberName = "TOTAL";

   &Dim = &Model.AddDimension("PROD_CAT");

   &Dim = &Model.AddDimension("REGION");

   /* Add the cubes */
   &Cube = &Model.AddCube("PROD_SALES");
   &Cube.FormatType = &Cube.AnalyticModel_Format_Number;
   &Cube.IsVirtual = False;
   &Cube.CalcAggregates = False;
   &Cube.Rule = "UNIT_COST * UNITS_SOLD";
   &Cube.AttachDimension("MONTH");
   &Cube.AttachDimension("PRODUCTS");
   &Cube.AttachDimension("REGION");

   &Cube = &Model.AddCube("SALES");
   &Cube.FormatType = &Cube.AnalyticModel_Format_Number;
   &Cube.IsVirtual = False;
   &Cube.CalcAggregates = False;

   &Cube = &Model.AddCube("TGT_COST");
   &Cube.FormatType = &Cube.AnalyticModel_Format_Number;
   &Cube.IsVirtual = False;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
   &Cube.CalcAggregates = False;
   &Cube.AttachDimension("PRODUCTS");

   &Cube = &Model.AddCube("UNITS_SOLD");
   &Cube.FormatType = &Cube.AnalyticModel_Format_Number;
   &Cube.IsVirtual = False;
   &Cube.CalcAggregates = False;
   &Cube.AttachDimension("MONTH");
   &Cube.AttachDimension("PRODUCTS");
   &Cube.AttachDimension("REGION");

   &Cube = &Model.AddCube("UNIT_COST");
   &Cube.FormatType = &Cube.AnalyticModel_Format_Number;
   &Cube.IsVirtual = False;
   &Cube.CalcAggregates = False;
   &Cube.AttachDimension("MONTH");
   &Cube.AttachDimension("PRODUCTS");
   &Cube.AttachDimension("REGION");

   /* Add Cube Collections */
   &CubeColl = &Model.AddCubeCollection("REG_SALES_IN");
   &CubeColl.RecordName = "QE_BAM_FACT_TBL";
   &CubeColl.AttachCube("PROD_SALES");
   &CubeColl.AttachCube("UNITS_SOLD");
   &CubeColl.AttachCube("UNIT_COST");
   &CubeColl.SetFieldMapping("MONTH", "QE_BAM_MONTH_FLD", False);
   &CubeColl.SetPersistAggregate("MONTH", &CubeColl.AnalyticModel_AggrType_None);
   &CubeColl.SetDimSort("MONTH", False, "", False, "", False, "");
   &CubeColl.SetFieldMapping("PRODUCTS", "QE_BAM_PRODUCT_FLD", False);
   &CubeColl.SetPersistAggregate("PRODUCTS", &CubeColl.AnalyticModel_AggrType_None)⇒
;
   &CubeColl.SetDimSort("PRODUCTS", False, "", False, "", False, "");
   &CubeColl.SetFieldMapping("REGION", "QE_BAM_REGION_FLD", False);
   &CubeColl.SetPersistAggregate("REGION", &CubeColl.AnalyticModel_AggrType_None);
   &CubeColl.SetDimSort("REGION", False, "", False, "", False, "");
   &CubeColl.SetFieldMapping("PROD_SALES", "QE_BAM_PRDSALES_FL", True);
   &CubeColl.SetFieldMapping("UNITS_SOLD", "QE_BAM_SALES_FLD", True);
   &CubeColl.SetFieldMapping("UNIT_COST", "QE_BAM_UNIT_FLD", True);

   &CubeColl = &Model.AddCubeCollection("REG_SALES_PROD");
   &CubeColl.RecordName = "QE_BAM_CCSMOKE";
   &CubeColl.AttachCube("PROD_SALES");
   &CubeColl.AttachCube("UNITS_SOLD");
   &CubeColl.AttachCube("UNIT_COST");
   &CubeColl.SetFieldMapping("MONTH", "QE_BAM_MONTH_FLD", False);
   &CubeColl.SetPersistAggregate("MONTH", &CubeColl.AnalyticModel_AggrType_None);
   &CubeColl.SetDimSort("MONTH", False, "", False, "", False, "");
   &CubeColl.SetFieldMapping("PRODUCTS", "QE_BAM_PRODUCT_FLD", False);
   &CubeColl.SetPersistAggregate("PRODUCTS", &CubeColl.AnalyticModel_AggrType_None)⇒
;
   &CubeColl.SetFilter("PRODUCTS", "FILTERPRODUCTS");
   &CubeColl.SetDimSort("PRODUCTS", False, "", False, "", False, "");
   &CubeColl.SetFieldMapping("REGION", "QE_BAM_REGION_FLD", False);
   &CubeColl.SetPersistAggregate("REGION", &CubeColl.AnalyticModel_AggrType_None);
   &CubeColl.SetDimSort("REGION", False, "", False, "", False, "");
   &CubeColl.SetFieldMapping("PROD_SALES", "QE_BAM_PRDSALES_FL", True);
   &CubeColl.SetFieldMapping("UNITS_SOLD", "QE_BAM_SALES_FLD", True);
   &CubeColl.SetFieldMapping("UNIT_COST", "QE_BAM_UNIT_FLD", True);

   &CubeColl = &Model.AddCubeCollection("TGT_COST_PROD");
   &CubeColl.RecordName = "QE_BAM_CC_TRGT";
   &CubeColl.AttachCube("TGT_COST");
   &CubeColl.SetFieldMapping("PRODUCTS", "QE_BAM_PRODUCT_FLD", False);
   &CubeColl.SetPersistAggregate("PRODUCTS", &CubeColl.AnalyticModel_AggrType_None)⇒
;
   &CubeColl.SetDimSort("PRODUCTS", False, "", False, "", False, "");
   &CubeColl.SetFieldMapping("TGT_COST", "QE_BAM_TARGET_FLD", True);

   &Model.Save();
   /* &Valid = &Model.Validate(); */
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
   QE_ACE_META_WK.QE_BAM_PCSTATUS = "The Model " | &ACEMODELID | " was created and ⇒
saved.";

End-Function;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Chapter 5

Analytic Grid Classes

Understanding the Analytic Calculation Engine Classes

PeopleSoft Analytic Calculation Engine comprises a calculation engine plus several PeopleTools features which enable application developers to define both the calculation rules and the display of calculated data within PeopleSoft applications for the purposes of multi-dimensional reporting, data editing, and analysis.

More specifically, developers create *analytic models* in order to define the rules which are used to calculate data. Developers also create PeopleSoft Pure Internet Architecture pages with *analytic grids* in order to display the data within PeopleSoft applications. End users view, analyze, and make changes to this data. When end users save their changes, PeopleSoft Analytic Calculation Engine recalculates the data and saves the calculated data to the database.

PeopleCode enables developers to manipulate analytic calculation data as follows:

- Use the Analytic Calculation Engine classes to either retrieve or specify data in an instance of an analytic model loaded into the system, and also to calculate (or recalculate) cube values.
- Use the Analytic Calculation Engine metadata classes to manipulate an analytic model definition. For example, you can add cubes to a cube collection or rename an existing user function for a model.
- Use the Analytic Grid classes to manipulate the display of analytic calculation data on a page.
- Use the Analytic Type classes to manipulate an analytic type definition. For example, you can specify a new analytic model for an analytic type definition.

Important! The analytic grid classes are not supported on IBM z/OS and Linux for IBM System z platforms.

Related Links

Understanding the PeopleSoft Analytic Calculation Engine Metadata Classes
Understanding the Analytic Calculation Engine Classes
Understanding the Analytic Calculation Engine Classes

Using the Analytic Grid in PeopleCode

The PeopleCode AnalyticGrid object is a reference to a page runtime object for the analytic grid. These particular page runtime objects aren't present until the component is started.

Note: PeopleSoft builds a page grid one row at a time. Because the AnalyticGrid class applies to a complete grid, you can't attach PeopleCode that uses the AnalyticGrid class to events that occur before the grid is built; the earliest event you can use is the page Activate Event.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

If you're using the analytic grid within a secondary page, the runtime object for the grid isn't created until the secondary page is run. The grid object can't be obtained until then, which means that the earliest PeopleCode event you can use to activate a grid that's on a secondary page is the Activate event for the secondary page.

The attributes you set for displaying an analytic grid remain in effect only while the page is active. When you switch between pages in a component, you have to reapply those changes *every time* the page is displayed.

In addition, the Activate event associated with a page fires every time the page is displayed. Any PeopleCode associated with that Activate event runs, which may undo the changes you made when the page was last active. For example, if you hide a grid column in the Activate event, then display it as part of a user action, when the user tabs to another page in the component, then tabs back, the Activate event runs again, hiding the grid column again.

If a user at runtime hides a column of a grid, tabs to another page in the component, then tabs back to the first page, the page is refreshed and the grid column is displayed again.

You can use the rowset class methods and properties on analytic grid data. You can access the data loaded by the analytic grid by accessing a rowset object after the grid is populated.

Use the analytic grid classes to manipulate the display of an analytic grid—that is, one associated with PeopleSoft Analytic Calculation Engine data. If you want to manipulate a grid control, use the grid classes.

Related Links

Grid Class Methods

GetRowset

"CreateRowset" (PeopleTools 8.54: PeopleCode Language Reference)

"GetRowset" (PeopleTools 8.54: PeopleCode Language Reference)

"PeopleCode Events" (PeopleTools 8.54: PeopleCode Developer's Guide)

Using Freeze Column Mode

If you specify Freeze Column Mode for an analytic grid in Application Designer, the analytic grid isn't populated from the component buffer by default. It is your responsibility to write your application code so that it populates the rowset bound to the analytic grid.

Note: You should not be adding and deleting data from the analytic grid when you are not in Freeze Column Mode; this is an unsupported feature and might cause unexpected behavior.

In addition, no layout information is available, and there is no slicer, row, or column axis.

The following is an example of populating the analytic grid with data from a normal grid in Freeze Column Mode.

```
Local Rowset &RSAGRID;
Local Rowset &RSGrid;


/* Get the rowset associated with normal grid whose primary record is */
/* QE_BAM_FACTTBL */
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
&RSGRID = GetLevel0()(1).GetRowset(Scroll.QE_BAM_FACTTBL);


/* Get the rowset associated with Analytic grid whose primary record is */
/* QE_BAM_CCSMOKE */
&RSAGRID = GetLevel0()(1).GetRowset(Scroll.QE_BAM_CCSMOKE);

/* Flush out existing Data from the Analytic Grid */
&RSAGRID.Flush();

/* Copy data from Normal Grid to Analytic Grid in Freeze Column Mode*/
&RSGRID.CopyTo(&RSAGRID, Record.QE_BAM_FACTTBL, Record. QE_BAM_CCSMOKE);
```

Do not use the following methods with an analytic grid that is in Freeze Column Mode:

- Analytic grid GetCubeCollection method
- Analytic grid LoadData method
- Analytic grid SetAnalyticInstance method
- Analytic grid SetLayout method
- Analytic grid SlicerVisible property

Error Handling

All the analytic type classes throw PeopleCode exceptions for any fatal error that occurs in the execution of the operation. PeopleSoft recommends enclosing your analytic model programs in try-catch statements. This way, if your program catches the exception, the message set and message number that are associated with the exception object indicate the error.

Related Links

Try-Catch Blocks

Data Types of the Analytic Grid Objects

Analytic grids are declared using the AnalyticGrid data type. For example,

```
Local AnalyticGrid &MyAnalyticGrid;
```

Analytic grid columns are declared using the AnalyticGridColumn data type. For example:

```
Local AnalyticGridColumn &MYGRIDCOL;
```

Scope of Analytic Grid Objects

Both the AnalyticGrid and AnalyticGridColumn objects can be instantiated from PeopleCode only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

An AnalyticGrid is a control on a page. You generally use these objects only in PeopleCode programs that are associated with an online process, not in an Application Engine program, a message notification, a Component Interface, and so on.

AnalyticGrid objects can be of scope local, component or global.

AnalyticGrid Class Reference

This reference for the AnalyticGrid class includes:

- AnalyticGrid class built-in function.
- AnalyticGrid class methods.
- AnalyticGrid class properties.

AnalyticGrid Class Built-in Function

"GetAnalyticGrid" (PeopleTools 8.54: PeopleCode Language Reference)

AnalyticGrid Class Methods

In this section, we discuss the AnalyticGrid class methods. The methods are described in alphabetic order.

GetColumn

Syntax

GetColumn(*ColumnName*)

Description

Use the GetColumn method to instantiate an AnalyticGridColumn object.

Note: The properties for an AnalyticGridColumn and a GridColumn are the same. Any differences are indicated in the description for the GridColumn property.

Specify the grid column name in the page field properties for that field, consisting of any combination of uppercase letters, digits and "#", "$", "@", and "_".

To specify a grid column name:

1. Open the page in Application Designer, select the analytic grid and access the Analytic Grid control properties.
2. On the General tab, type the new grid name in Page Field Name.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

ColumnName	Specify the name of the column that you want to access.

Returns

An AnalyticGridColumn object.

Note: The properties for an AnalyticGridColumn and a GridColumn are the same. Any differences are indicated in the description for the GridColumn property.

Related Links

GridColumn Class

GetCubeCollection

Syntax

```
GetCubeCollection()
```

Description

Use the GetCubeCollection method to return a reference to the cube collection associated with the analytic grid.

Note: Do not use this method with an analytic grid that is in Freeze Column Mode.

Parameters

None.

Returns

A CubeCollection object.

Related Links

Understanding the Analytic Calculation Engine Classes
CubeCollection Class

LoadData

Syntax

```
LoadData()
```

Description

Use the LoadData method to cause the system to get fresh data for the grid from the analytic calculation engine. Generally, you would use this method after you perform some operation, such as SetLayout, that might change the value or layout of the data.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Note: Do not use this method with an analytic grid that is in Freeze Column Mode.

Parameters

None.

Returns

None.

SetAnalyticInstance

Syntax

SetAnalyticInstance(*ID*)

Description

Use the SetAnalyticInstance method to specify the analytic instance to be associated with this analytic grid.

An AnalyticGrid object can be bound only once to an analytic instance. If the SetAnalyticInstance method is called after the analytic grid is bound to an instance, the method call has no effect.

Note: Do not use this method with an analytic grid that is in Freeze Column Mode.

Parameters

ID	Specify the analytic instance ID as a string.

Returns

None.

Related Links

Understanding the Analytic Calculation Engine Classes
Understanding the Analytic Calculation Engine Classes
AnalyticInstance Class Methods

SetLayout

Syntax

SetLayout(*&SlicerArray*, *&RowAxisArray*, *&ColumnAxisArray*)

Description

Use the SetLayout method to set the layout for the three axes, slice, row, and column.

Note: Do not use this method with an analytic grid that is in Freeze Column Mode.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

If you specify No Drag drop mode for an analytic grid in Application Designer, the analytic grid has the column axis, row axis and slicer axis, but the end user isn't allowed to change the layout by dragging and dropping elements between axes. However, you can still change the layout using the SetLayout method.

Note: You can specify a null value ("") for all the required parameters for this method.

Parameters

&SlicerArray	Specify an already instantiated array of string containing the list of fields to be put on the slice axis.
&RowAxisArray	Specify an already instantiated array of string containing the list of fields to be put on the row axis.
&ColumnAxisArray	Specify an already instantiated array of string containing the list of fields to be put on the column axis. **Note:** The maximum number of columns that can be displayed in an analytic grid is four.

Returns

None.

AnalyticGrid Class Properties

In this section we discuss the AnalyticGrid properties. The properties are described in alphabetic order.

Inactive

Description

Use this property to specify whether the analytic grid is inactive or active. This property takes a Boolean value, true if the grid is inactive, false otherwise.

If you specify this property as true, the analytic grid is not displayed to the user and no data is fetched from the database.

This property is read-write.

Label

Description

Use this property to specify the label that appears as the title of the grid.

Note: You can't use this property to set labels longer than 100 characters. If you try to set a label of more than 100 characters, the label is truncated to 100 characters. Always put any changes to labels in the Activate event for the page. This way the label is set every time the page is accessed.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-write.

ShowGridLines

Description

Use this property to specify whether grid lines are displayed with the analytic grid. This property takes a Boolean value, true to show the lines, false otherwise.

This property is read-write.

SlicerVisible

Description

Use this property to specify whether the slicer is displayed with the analytic grid. This property takes a Boolean value, true to show the slicer, false otherwise.

Note: Do not use this method with an analytic grid that is in Freeze Column Mode.

This property is read-write.

SummaryText

Description

Use this property to set or return a string representing the summary text for the analytic grid.

Summary text enables you to provide a brief description of the functionality and content of the grid area. This property is pertinent for users who access the application in accessibility mode using screen readers.

This property is read-write.

Example

```
&MyAnGrid = GetAnalyticGrid(Page.PSMYPAGE, "PSMYPAGE");
&MyAnGrid.SummaryText = "This is the new summary text through PeopleCode";
```

Related Links

"Setting Analytic Grid Label Properties" (PeopleTools 8.54: Analytic Calculation Engine)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Chapter 6

Analytic Type Classes

Understanding the Analytic Calculation Engine Classes

PeopleSoft Analytic Calculation Engine comprises a calculation engine plus several PeopleTools features which enable application developers to define both the calculation rules and the display of calculated data within PeopleSoft applications for the purposes of multi-dimensional reporting, data editing, and analysis.

More specifically, developers create *analytic models* in order to define the rules which are used to calculate data. Developers also create PeopleSoft Pure Internet Architecture pages with *analytic grids* in order to display the data within PeopleSoft applications. End users view, analyze and make changes to this data. When end users save their changes, PeopleSoft Analytic Calculation Engine recalculates the data and saves the calculated data to the database.

PeopleCode enables developers to manipulate analytic calculation data as follows:

- Use the Analytic Calculation Engine classes to either retrieve or specify data in an instance of an analytic model loaded into the system, and also to calculate (or recalculate) cube values.
- Use the Analytic Calculation Engine metadata classes to manipulate an analytic model definition. For example, you can add cubes to a cube collection or rename an existing user function for a model.
- Use the analytic grid classes to manipulate the display of analytic calculation data on a page.
- Use the analytic type metadata classes to manipulate an analytic type definition. For example, you can specify a new analytic model for an analytic type definition.

Important! The analytic type classes are not supported on IBM z/OS and Linux for IBM System z platforms.

Related Links

Understanding the Analytic Calculation Engine Classes
AnalyticGrid Class Reference
Understanding the Analytic Calculation Engine Classes

Using the Analytic Type Classes

You can create analytic type definitions using Application Designer. PeopleSoft provides the analytic type classes for accessing these definitions at runtime.

You can also create an analytic type definition in PeopleCode, using the Create method, then saving it to the database using the Save method. After you save the definition, you can access it using Application Designer.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

You only need to create an instance of the analytic type. All other objects are instantiated from the analytic type object.

Once the AnalyticTypeDefn object is created, you can then execute either the Get or Create methods to "instantiate" the analytic type object.

Error Handling

All the analytic type classes throw PeopleCode exceptions for any fatal error that occurs in the execution of the operation. PeopleSoft recommends enclosing your analytic model programs in try-catch statements. This way, if your program catches the exception, the message set and message number that are associated with the exception object indicate the error.

Related Links

Try-Catch Blocks

Data Types of the Analytic Type Objects

Every PeopleSoft analytic type object is declared as its own data type, that is, AnalyticTypeDefn objects are declared as type AnalyticTypeDefn, AnalyticTypeModelDefn objects are declared as type AnalyticTypeModelDefn, and so on.

The following are the data types for the PeopleSoft analytic type classes:

- AnalyticTypeDefn
- AnalyticTypeModelDefn
- AnalyticTypeRecordDefn

Scope of Analytic Type Objects

The analytic type objects can only be instantiated from PeopleCode.

These objects can be used anywhere you have PeopleCode, that is, in a Application Engine program, an application class, record field PeopleCode, and so on.

Analytic type objects can be of scope Local, Component or Global.

How to Import the Analytic Type Classes

The analytic type classes are *not* built-in classes, like Rowset, Field, Record, and so on. They are application classes. Before you can use these classes in your PeopleCode program, you must import them to your program.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

An import statement names either all the classes in a package or one particular application class. For importing the analytic type classes, PeopleSoft recommends that you import all the classes in the application package.

The application package PT_ANALYTICTYPEDEFN contains the following subclasses:

- AnalyticTypeDefn
- AnalyticTypeModelDefn
- AnalyticTypeRecordDefn

The import statement you should use should be as follows:

```
import PT_ANALYTICTYPEDEFN:*;
```

Using the asterisks after the package name makes all the application classes directly contained in the named package available.

Related Links

Understanding Application Classes

How to Create an Analytic Type Class Object

After you've imported the analytic type classes, you need to instantiate an instance of the AnalyticTypeDefn class, using the constructor for that class and the Create function. After you create the object, you must populate it using either the Get or Create method.

The following example creates an AnalyticTypeDefn object from the QE_ACE_ALLFUNCTION analytic type definition.

```
Local PT_ANALYTICTYPEDEFN:AnalyticTypeDefn &AnalyticType;

&AnalyticType = create PT_ ANALYTICTYPEDEFN:AnalyticTypeDefn("QE_ACE_ALLFUNCTION");
```

Related Links

Analytic Calculation Engine Metadata Classes Constructor

Analytic Type Classes Constructor

You must use the constructor for the AnalyticTypeDefn class to instantiate an instance of that class. All other objects are instantiated from this class.

AnalyticTypeDefn

Syntax

AnalyticTypeDefn(*TypeName*)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the AnalyticTypeDefn constructor to create an AnalyticTypeDefn.

Once the AnalyticTypeDefn object is created, you can then execute either the Get or Create methods to instantiate the model.

Note: The Delete and Rename methods can only be executed before a model is instantiated.

Parameters

TypeName Specify the name of an analytic type definition.

Returns

An AnalyticTypeDefn object.

Example

```
&Model = create AnalyticTypeDefn("QE_ACE_ALLFUNCTION");
```

AnalyticTypeDefn Class Methods

This section describes the analytic type definition class methods. The methods are discussed in alphabetical order.

AddModel

Syntax

AddModel(*ModelName*, *ModelType*)

Description

Use the AddModel method to add either an analytic model or optimization model to the analytic type definition. If the model doesn't exist, this method fails.

Parameters

ModelName Specify the name of an existing model.

ModelType Specify the model type. Values are:

Value	*Description*
%ModelType_ACE	The model is an Analytic Calculation Engine.
%ModelType_OPT	The model is an optimization.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

The new AnalyticTypeModelDefn object.

Related Links

DeleteModel
GetModelNames
AnalyticTypeModelDefn Class Properties

AddRecord

Syntax

AddRecord(*RecordName*)

Description

Use the AddRecord method to add a record to the analytic type definition. If the record definition doesn't exist in Application Designer, or if the record already exists in this analytic type definition, this method fails.

Parameters

RecordName	Specify the name of the record that you want to add.

Returns

An AnalyticTypeRecordDefn object that represents the record.

Related Links

DeleteRecord
GetRecordNames
AnalyticTypeRecordDefn Class Methods

Create

Syntax

Create()

Description

Use the Create method to create, and instantiate, a new analytic type. If the analytic type already exists, an exception is thrown.

Parameters

None.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

None.

Related Links

Save
Try-Catch Blocks

CopyTo

Syntax

CopyTo(*NewAnalyticTypeName*)

Description

Use the CopyTo method to copy the current AnalyticTypeDefn object to the AnalyticTypeDefn object with the specified name. This method fails if the analytic type specified with *NewAnalyticTypeName* already exists.

Parameters

NewAnalyticTypeName	Specify the name of the new analytic type definition that you want to create.

Returns

The new AnalyticTypeDefn object.

Related Links

Create
Save

Delete

Syntax

Delete()

Description

Use the Delete method to delete the analytic type definition. You must use this method immediately after you create the AnalyticType object, before you instantiate it, that is, before you use either the Get or Create method.

Note: This method executes immediately, and deletes the definition from Application Designer.

Parameters

None.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

None.

Related Links

Create
Get
Save

DeleteModel

Syntax

DeleteModel(*ModelName*)

Description

Use the DeleteModel method to delete the specified model from the analytic type definition.

Note: The model is not deleted from the analytic type definition until you use the Save method.

Parameters

ModelName	Specify the name of a model that exists in the analytic type definition.

Returns

None.

Related Links

AddModel
GetModelNames
AnalyticTypeModelDefn Class Properties

DeleteRecord

Syntax

DeleteRecord(*RecordName*)

Description

Use the DeleteRecord method to delete a record from the analytic type definition.

Note: The record deleted from the analytic type definition until you use the Save method.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

RecordName	Specify the name of the record that you want to remove from the analytic type definition.

Returns

None.

Related Links

AddRecord
GetRecordNames
AnalyticTypeRecordDefn Class Methods

Get

Syntax

```
Get()
```

Description

Use the Get method to instantiate an existing analytic type definition as an AnalyticTypeDefn object. If the analytic type doesn't exist, this method throws an exception.

Parameters

None.

Returns

None.

Related Links

Create
Save

GetModel

Syntax

```
GetModel(ModelName)
```

Description

Use the GetModel method to return a reference to an AnalyticTypeModelDefn object.

This method fails if the model specified by *ModelName* doesn't exist.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

ModelName	Specify the name of the analytic type model definition that you want to access.

Returns

An AnalyticTypeModelDefn object.

Related Links

AnalyticTypeModelDefn Class Properties

GetModelNames

Syntax

```
GetModelNames()
```

Description

Use the GetModelNames method to return an array of string containing all the model names in this analytic type definition.

Parameters

None.

Returns

An array of string.

Related Links

AddModel
DeleteModel
AnalyticTypeModelDefn Class Properties

GetRecord

Syntax

```
GetRecord(RecordName)
```

Description

Use the GetRecord method to return a reference to an AnalyticTypeRecordDefn object.

This method fails if the record specified by *RecordName* doesn't exist.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

RecordName Specify the name of the record that you want to access.

Returns

An AnalyticTypeRecordDefn object.

Related Links

AnalyticTypeRecordDefn Class Methods

GetRecordNames

Syntax

GetRecordNames()

Description

Use the GetRecordNames method to return an array of string containing the names of all the records associated with the analytic type definition.

Parameters

None.

Returns

An array of string.

Related Links

AddRecord
DeleteRecord
AnalyticTypeRecordDefn Class Methods

Rename

Syntax

Rename(*NewAnalyticTypeName*)

Description

Use the Rename method to rename an existing analytic type definition to a new name. You must use this method immediately after you create the AnalyticType object, before you instantiate it, that is, before you use either the Get or Create method. The new name is not saved to the database until you use the Save method.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

NewAnalyticTypeName	Specify the new name for the analytic type definition.

Returns

None.

Related Links

Save

Save

Syntax

Save()

Description

Use the Save method to save any changes that were made to the AnalyticTypeDefn object to the database.

Parameters

None.

Returns

None.

AnalyticTypeDefn Class Properties

In this section we discuss the AnalyticTypeDefn class properties. The properties are described in alphabetic order.

AppClassPath

Description

Use this property to specify the full name of the application package that contains the Create, Copy and Delete methods used with this analytic type definition.

This property is read-write.

Comments

Description

Use this property to specify comments for the analytic type.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-write.

Description

Description

Use this property to specify a description for the analytic type.

This property is read-write.

Name

Description

This property specifies the name of the AnalyticTypeDefn.

This property is read-only.

OwnerID

Description

This property specifies the owner ID for this AnalyticTypeDefn.

This property is read-write.

AnalyticTypeModelDefn Class Properties

In this section we discuss the AnalyticTypeModelDefn class properties. The properties are described in alphabetic order.

Name

Description

This property specifies the name of the analytic type model.

This property is read-only.

Type

Description

This property specifies the type of the analytic type model. Values are:

Value	*Description*
%ModelType_ACE	The model is an Analytic Calculation Engine.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Value	*Description*
%ModelType_OPT	The model is an optimization.

This property is read-only.

AnalyticTypeRecordDefn Class Methods

In this section we describe the AnalyticTypeRecordDefn class methods. The methods are discussed in alphabetic order.

GetSelectedField

Syntax

GetSelectedField()

Description

Use the GetSelectedField to return an array of string containing the names of the fields that are selected for this record.

Parameters

None.

Returns

An array of string.

Related Links

SetSelectedField

SetSelectedField

Syntax

SetSelectedFields(*FieldName*)

Description

Use the SetSelectedField method to specify the name of the field that is selected for this record.

Parameters

FieldName Specify the name of the field that you want to select.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

None.

Related Links

GetSelectedField

UnsetSelectedField

Syntax

UnsetSelectedField(*FieldName*)

Description

Use the UnsetSelectedField method to unselect the selected field.

This method throws an exception if the field specified by *FieldName* isn't selected.

Parameters

FieldName	Specify the name of the field that you want to deselect.

Returns

None.

AnalyticTypeRecordDefn Class Properties

In this section we discuss the AnalyticTypeRecordDefn class properties. The properties are described in alphabetic order.

All of the properties listed here can also be set for the analytic type definition using Application Designer.

Related Links

"Viewing Analytic Model Properties" (PeopleTools 8.54: Analytic Calculation Engine)

Callback

Description

Use this property to specify whether this record has a callback. This property takes a Boolean value, true if the record has a callback, false otherwise.

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Description

Use this property to specify a description for the record.

This property is read-write.

Name

Description

This property specifies the name of the record.

This property is read-only.

Readable

Description

Use this property to specify whether this record is readable. This property takes a Boolean value, true if the record is readable, false otherwise.

This record is read-write.

ReadOnce

Description

Use this property to specify whether this record is specified as read once. This property takes a Boolean value, true if the record is only read once, false otherwise.

This property is read-write.

ScenarioManaged

Description

Use this property to specify if the record is specified as scenario managed. This property takes a Boolean value, true if the record is scenario managed, false otherwise.

This property is read-write.

SyncOrder

Description

This property specifies the synchronization order for the record. It returns an integer value.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Writeable

Description

Use this property to specify if a record is specified as writeable. This property takes a Boolean value, true if the record is writeable, false otherwise.

This property is read-write.

AnalyticType Classes Example

The following is a typical example of using the AnalyticType classes.

```
import PT_ANALYTICTYPEDEFN:*;

Local PT_ANALYTICTYPEDEFN:AnalyticTypeDefn &AnalyticType;

Local PT_ANALYTICTYPEDEFN:AnalyticTypeRecordDefn &AnalyticTypeRecordDefn;

&AnalyticType = create PT_ ANALYTICTYPEDEFN:AnalyticTypeDefn("BB_TEST");

&AnalyticType.Create();

&AnalyticType.AddModel("QE_BAM_GENX", %ModelType_ACE);

&AnalyticTypeRecordDefn = &AnalyticType.AddRecordl("QE_BAM_CCSMOKE");

&AnalyticTypeRecordDefn = &AnalyticType.AddRecordl("QE_BAM_FACTTBL");

&AnalyticType.Save();
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Chapter 7

Application Classes

Understanding Application Classes

You can create Application Packages in Application Designer. These *packages* contain application classes (and may contain other packages also). An application class, at its base level, is just a PeopleCode program. However, using the Application Packages, you can create your own classes, and extend the functionality of the existing PeopleCode classes.

The application classes provide capability beyond that offered by the existing PeopleCode classes. Unlike the existing classes, a subclass can inherit all the properties and methods of the class it extends. This provides all the advantages of true object-oriented programming:

- easier to debug because all the pieces are separate
- easier to maintain because functionality is gathered into a single place
- extensible by subclass

In addition, the application classes provide more structure. Using the Application Packages, you have a clear definition of each class, as well as its listed properties and methods. This makes it easier to create a complex program that uses many functions.

Related Links

"Creating Application Packages" (PeopleTools 8.54: PeopleCode Developer's Guide)

When Would You Use Application Classes?

Use Application classes to help structure your existing PeopleCode functions. For example, prior to Application classes, most PeopleCode functions were put into FUNCLIB records. However, in larger, more complex programs, it is sometimes difficult to find (let alone maintain) a function. You could make every function a class in a package with very little reworking of your PeopleCode (as well as making the different fields in a record a package, and combining them into a single larger package.) This provides a better visual interface for grouping your functions.

In addition, use Application classes when you have to do generic processing, and just the details are different. For example, suppose one of the processes for your application is reading a file object and doing bulk insert. The process could all be contained in a single package, with the classes and subclasses providing all the details, different kinds of reading for different types of files, different inserts based on the record, and so on.

One of the main differences between a class and a function call is that the call to the class is dynamic, like a function variable, but more closely controlled. All the calls to the class (methods) must have the same signature.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

For example, suppose you want to provide a more generic sort, with comparison function at the end of it. You want to use the array class Sort method, but your process has to be generic: you aren't certain if you're comparing two records or two strings. You could define a class that had as its main method a comparison, and return a -1, 0, or 1. Then write your personalized sort, extending the array class method Sort.

Another use is for business processing. Think in terms of core functionality, with vertical product solutions that extend the basic processing by providing specifics, in other words, by extending the general classes with subclasses. This could be appropriate for sales force automation or order entry.

Generally, use application classes where you can extract the common functionality.

Note: Do not extend a SOAPDoc with an application class. This is currently not supported.

Application Classes General Structure

All application classes are contained in a package. All application classes are composed of PeopleCode. In this section, we discuss the general form of an application class, which is:

- Class name
- Class extensions
- Declaration of public external interface
- Declaration of protected instance variables and methods
- Declaration of private instance variables and methods
- Definition of methods
- Constructors

This division enables a separation of the following:

- what the class provides to other classes
- what is applicable to the entire class
- what is applicable to the definition of a method

The data types used in an application class (for methods parameters, return values, and so on) can be any PeopleCode types, including application classes. Likewise, application classes can be used anywhere in a PeopleCode program where a general data type can be used.

Related Links

"Data Types" (PeopleTools 8.54: PeopleCode Developer’s Guide)

Class Name

Application classes have a fully qualified name that is formed hierarchically by the name of the top-level package that contains them, the package that contains that package, and so on down to the short class

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

name, that is, the one specified when the class was created in Application Designer, using a colon for the separator between names.

The fully qualified name of the class must be unique, as this is what identifies the class. The short name of the class does not have to be unique.

Image: Application classes example

For example, suppose package CRM contains the application classes Address and Customer as well as the package Utilities, which in turn contains the application classes Address and Incident:

There are four distinct application classes in this example:

- CRM:Address
- CRM:Customer
- CRM:Utilities:Address
- CRM:Utilities:Incident

Note: If you change the name of a package or an application class, that name change is *not* automatically propagated through all your PeopleCode programs. You must make the change manually in your programs. If you specify an incorrect name for a package or application class, you receive a warning when you try to save the PeopleCode.

Class Extension

Extension represents the "is-a" relationship. When a class extends another class, it's called a *subclass* of that class. Conversely, the class being extended is called a *superclass* of that subclass.

A subclass inherits all of the public methods and properties (collectively called *members*) of the class it extends. These members can be overridden by declarations of methods and properties in the subclass.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Note: Application classes have no multiple inheritance (that is, being able to extend more than one class.)

Type checking in PeopleCode (both at design time and runtime) does strong type checking of application classes, tracking each application class as a separate type. A subclass can be used as the class it extends, because it implements the public interfaces of its superclass. This is called *subtyping*.

In the following example, the class Banana extends the class Fruit. Banana is the *subclass* of Fruit. From Fruit, you can extend to Bananas. However, from Bananas you can't extend to Fruit. Another way to think about this is you can only extend from the general to the specific, not the other way around.

```
class Fruit
   method DoFruit();
   property number FruitNum instance;
end-class;

class Banana extends Fruit
   method DoBanana();
   property number BananaNum instance;
end-class;
```

The following code shows a correct way to assign a class object, because Banana is a *subtype* of Fruit.

```
local Fruit &Bref = Create Banana();
```

The following is *not* correct. Banana is a subtype of Fruit. Fruit is *not* a subtype of Banana. This assignment causes an error at design time.

```
local Banana &Fref = Create Fruit();
```

Before you can extend a class, you must first import it. You must import all class names you use in a PeopleCode program before you use them.

Related Links

Import Declarations

Declaration of Public External Interface

The names of the members (that is, all the methods and properties of a class) must be unique only within that class. Different classes can have members with the same name. As members are used only with objects, and each object knows its class, the member that's accessed is the one associated with that class.

For example, more than one class has the property Name which returns the name of the object executing the property. There isn't any confusion, because the field Name property returns the name of a field, while the record name property returns the name of a record. No class has more than one property called Name.

Note: Within a class, each member name *must* be unique.

The public part of a class declaration specifies the methods and properties that the class provides to other PeopleCode programs. These methods and properties are *dynamically bound*, that is, the actual method that is called depends on the actual class of the object, as it might be an overridden method or property from a subclass.

In the following code example, the text in bold indicates the public part of the class declaration.

```
/* generic building class */
class BuildingAsset
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
   method Acquire ();
   method DisasterPrep();
end-class;
```

Access Control and the Declaration of Protected Properties and Methods

Application class objects have private and public access control. Properties or methods that are declared outside the “private” declaration section have public access control. This means that they can be referenced and used by any PeopleCode. This access is of course subject to access controls such as “readonly”. Private properties and methods are private to the class, not instance, and can only be referenced by objects of this application class.

Between these two access control schemes of public and private, lies the concept of protected methods and properties. Protected methods and properties can be accessed only by objects of this application class and those derived from this application class. Use protected methods or properties when you want to hide them from outside use, but allow the flexibility of using them in derived classes.

The declarations of protected variables and methods are done within the class declaration, before the declaration of private variables and methods. You can use protected instance variables in interface classes. Protected methods and properties can be overridden by subclasses.

Most of the time your design can be implemented through the use of private methods and properties without resorting to the use of protected methods and properties. The following examples demonstrates the rules and some of the subtleties about when to use protected methods and properties.

```
class A;
   method A();
   property string Q;
protected
   method MP() Returns string;
   property string p;
end-class;

method A;
   &p = "Class A: property p";
end-method;

method MP
   /+ Returns String +/
   Return "Class A: method MP";
end-method;

====================

class B extends A;
   method B();
   method M(&X As C);
   method m2(&Aobj As A);
   /* property string P; */
protected
   property string Q;
   method MP() Returns string;
end-class;

method B;
   %Super = (create A());
   &Q = "Class B: property Q";
   /* &P = "Class B: property P";*/
end-method;

method M
/+ &X as FOXTEST:C +/;

   MessageBox(0, "", 0, 0, "In B:M %This.P=" | %This.p);
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
/* %This.p is class A property P */
   MessageBox(0, "", 0, 0, "In B:M %This.Q=" | %This.Q);
/* %This.q is class B property Q */
   MessageBox(0, "", 0, 0, %This.MP());
/* %This.MP() calls class B method MP */

   if &X.p = "Error" then
   end-if;
/* error: cannot reference &X.p since class B is
not involved in the implementation of class C */
end-method;

method m2
/+ &Aobj as FOXTEST:A +/
/* MessageBox(0, "", 0, 0, "In B:M2 &Aobj.P=" | &Aobj.p);
/* Error: cannot reference &Aobj.p from class B
since class B is not involved in its implementation */

End-method;

method MP
   /+ Returns String +/
   Return "Class B: method MP";
end-method;

========================

class C extends A;
   method C();
protected
   property string P;
end-class;

method C;
   %Super = (create A());
   &P = "Class C: property P";
end-method;
==========================

/* AE program */
import FOXTEST:*;

Local A &A = (create A());

Local object &obj = &A;
MessageBox(0, "", 0, 0, "In AEMINITEST: &Obj.p=" | &obj.P);
/* run time error: anonymous access through type
object not allowed*/
```

The following example also illustrates some of the rules surrounding protected access control.

```
import FOXTEST:Point3d;

class Point
   method Point(&X1 As integer, &Y1 As integer);
   method Warp(&A As Point3d);
protected
   property integer x;
   property integer y;
end-class;

method Point
   /+ &X1 as Integer, +/
   /+ &Y1 as Integer +/;

   %This.x = &X1;
   %This.y = &Y1;
end-method;

method Warp
   /+ &A as FOXTEST:Point3d +/
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
   /* Local Integer &temp = &A.Z;  ERROR cannot access &A.Z */
end-method;
================================
import FOXTEST:Point;

class Point3d extends Point
   method Point3d(&X1 As integer, &Y1 As integer, &Z1 As integer);
   method Delta(&P As Point);
   method Delta3d(&Q As Point3d);
protected
   property integer z;
end-class;

method Point3d
   /+ &X1 as Integer, +/
   /+ &Y1 as Integer, +/
   /+ &Z1 as Integer +/;
   %Super = (create Point(&X1, &Y1));
   %This.z = &Z1;
end-method;

method Delta
   /+ &P as FOXTEST:Point +/
   /* &P.x = %This.x;
ERROR cannot access &P.x since while Point3d
(the class in which references to fields x and y occur)
is a subclass of Point (the class in which x and y are declared),
it is not involved in the implementation of Point (the type of parameter p)*/
   /* &P.y = %This.y;
ERROR cannot access &P.y. Same reason as above */
end-method;

method Delta3d
/+ &Q as FOXTEST:Point3d +/
/* The protected members of Q can be accessed because the class point3d is a subcla⇒
ss of Point and is involved in the implementation of Point3d */
&Q.x = %This.x;
&Q.y = %This.y;
   &Q.z = %This.z;

end-method;
```

Declaration of Private Instance Variables and Methods

The private part of a class declaration gives the declaration of any private methods, instance variables, and private class constants. Private methods *cannot* be overridden by subclasses, because they are completely private to the declaring class. Likewise, the instance variables can't be overridden.

The declarations of private variables and methods are done within the class declaration.

Note: You cannot have private methods or instance variables in an interface type of class.

In the following example, there are both public as well as private methods and properties. Any method that is declared before the keyword Private in the initial class declaration is public. Any method declared after the keyword Private is private. Properties are only declared in Public. Instances and Constants are only declared in Private

In the following example, the class Example extends the class ExampleBase. It has both public as well as private methods and properties. It also defines the private method in the definition of methods section of the code (the private definitions are marked **like this**.)

```
import PWWPACK:ExampleBase;

class Example extends ExampleBase
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
   method Example();
   method NumToStr(&Num As number) Returns string;
   method AppendSlash();
   property number SlashCount get;
   property number ImportantDayOfWeek get set;
   property string SlashString readonly;
   property date ImportantDate;
private
   method NextDayOfWeek(&Dow As number) Returns date;
   Constant &Sunday = 1;
   instance string &BaseString;
end-class;

Global string &CurrentBaseString;

/* Method declarations */
method NumToStr
   return String(&num);
end-method;

method AppendSlash
   &SlashString = &SlashString | "/";
end-method;

get SlashCount
   Return Len(&SlashString) - Len(&BaseString);
end-get;

get ImportantDayOfWeek
   Return Weekday(&ImportantDate);
end-get;

set ImportantDayOfWeek
   &importantdate = %This.nextdayofweek(&newvalue);
end-set;/* Private method. */
method nextdayofweek
   Return &ImportantDate + (&dow - Weekday(&ImportantDate));
end-method;

/* Constructor. */
method Example
   &BaseString = &CurrentBaseString;
   &SlashString = &BaseString;
   &ImportantDate = Date(19970322);
end-method;
```

Definition of Methods

After the declaration of any global or component variables and external functions needed by the methods, comes the actual definition of the methods. This section discusses some of the differences in how application programs are processed by the system, and how application class method parameters are processed.

- The system *never* skips to the next top-level statement.
- Application programs generally pass parameters by value, which is not the same as for existing functions.
- Parameter passing with object data types is by reference.
- Application programs use the out specifier to pass a parameter by reference.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Not Skipping to The Next Top-Level Statement

For existing functions and programs, the system skips to the next top-level statement in some circumstances, such as a field not found error. This never happens in an application class program. The code is always executed or an error is produced.

Passing Parameters in Application Class Methods

The parameters to a method are passed by value in the absence of an *out* specification in the parameter list. However, if a parameter list has an out specification, that argument (when used in the call of a method) must be a value that can be assigned something, and is passed by *reference*. In particular this means you cannot pass an object property to a method which requires the parameter to be an "out" parameter. Application class properties are always passed by value.

For example:

```
/* argument passed by reference */
method increment(&value as number out);


/* argument passed by value */
method increment(&value as number);
```

This is in contrast with existing PeopleCode functions that pass *all* parameters by reference when they can be assigned something. This means the method signature is a specification of which parameters can be updated by the method. This makes the code easier to debug and maintain because it's easy to see what can be updated and what can't.

The following is an example of code that increments a variable by one.

```
local Number &Mine;

&Mine = 1;

&obj.Increment(&Mine);
```

&Mine now has the value 2.

You cannot pass properties by reference. For example, supposed MyProp is a property of class Xan, a statement that requires a reference doesn't work if you supply the property. The following code will always fail because &Xan.MyProp is always passed by value and the MySqlExec method requires it to be passed by reference (so a value can be returned.)

```
MySqlExec("select from bar", &Xan.MyProp)
```

This makes sense because the semantics of an object require that you can only change a property with standard property references, not as a side affect of some other action.

Passing Parameters with Object Data Types

Parameters with object data types are always passed by reference:

```
/* argument passed by reference  */
method storeInfo(&f as File);
```

If you specify the out modifier for a method parameter with an object data type, it becomes a *reference parameter*. This means that the parameter variable is passed by reference instead of the object that it is pointing at when passed.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

For example, if you pass an object parameter with the out modifier:

```
method myMethod(&arg as MyObjectClass);

Local MyObjectClass &o1 = create MyObjectClass("A");
Local MyOtherObjectClass &o2 = create MyOtherObjectClass();

&o2.myMethod(&o1);
```

And inside myMethod this occurs:

```
Method myMethod
   &arg  =  create MyObjectClass("B");
end-method;
```

Since the method argument is reassigned within the body of myMethod, &o1 does not point at the new instance of MyObjectClass (initialized with "B") after the method call completes. This is because &o1 still references the original instance of MyObjectClass.

However, if &o1 had been passed with the out modifier, after the method call completes, &o1 points at whatever the parameter was last assigned to; in this case, the new instance of MyObjectClass. The parameter, rather than the object, is passed by reference.

Using the Out Specification for a Parameter

In the following example, a class, AddStuff, has a single public method, DoAdd. This adds two numbers together, then assigns them as different numbers. In the signature of the method declaration, the first parameter is *not* declared with an out statement, while the second one is.

```
class AddStuff
   method DoAdd(&P1 as number, &P2 as number out);
end-class;

method DoAdd
   &X = &P1 + &P2;
   &P1 = 1;
   &P2 = 2;
end-method;
```

In the following PeopleCode example, an object named &Aref is instantiated from the class AddStuff. Two parameters, &I and &J are also defined.

```
local AddStuff &Aref = Create AddStuff();
local number &I = 10;
local number &J = 20;
```

The following code example is correct. &J is changed, because of the *out*statement in the method signature, and because the value is being passed by reference. The value of &I is *not* updated.

```
&Aref.DoAdd(&I, &J); /* changes &J but not &I */
```

The following code example causes a design time error. The second parameter must be passed *by reference*, not by value.

```
&Aref.DoAdd(10, 20); /* error - second argument not variable */
```

Related Links

"PeopleCode Language Structure" (PeopleTools 8.54: PeopleCode Developer’s Guide)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Declaration of Abstract Methods and Properties

You can declare methods and properties as abstract, that is, a method or property that has a signature which specifies the parameters and results, but has no implementation in the class that defines it. The implementation may occur in one of the classes that extend the class where the method or property is initially defined.

Abstract methods and properties could be used, for example, when your application wants to provide a means for in-field customization. Your application might deliver a base class specifying the abstract methods and properties and you would allow the customization to complete those methods and properties by using a class that would extend the base class and provide implementations for some or all of the abstract methods and properties.

For a class that only contains abstract methods and properties, that is, a pure interface class, you would define a PeopleCode interface, instead of a class. You define a PeopleCode interface by using the keyword Interface instead of Class. In an interface, all the methods and properties are abstract by default.

The following example illustrates the use of abstract methods and properties. Class MyInterface is the base class which has mostly abstract methods and properties. However it is fully specified by the class MyImplementation which provides and implementation for all the methods and properties.

```
class MyInterface
   method MyMethod1() abstract;
method MyMethod2() Returns string abstract;
method MyMethod3();
   property string myproperty1 abstract readonly;
   property number myproperty2 abstract;
property number myproperty3 abstract;
end-class;
method MyMethod3
end-method;
-------------------------------------------------------------------
import FOXTEST:MyInterface;

class MyImplementation extends MyInterface;
   method MyImplementation();
   method MyMethod1();
   method MyMethod2() Returns string;
   property string myproperty1 readonly;
   property number myproperty2;
   property number myproperty3;
end-class;

method MyImplementation
   %Super = Create MyInterface();[Ugh.]
end-method;

method MyMethod1
   /* dummy */
end-method;

method MyMethod2
   /+ Returns String +/
   Return "MyMethod2's implementation is this";
end-method;
```

Considerations Using Abstract Methods and Properties

Be aware of the following considerations when using abstract methods or properties.

- You cannot have private abstract methods.
- You will receive an error if you try to provide a method body for an abstract method.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- The method signatures must be identical between the abstract method definition and the method implementation in the derived subclass.
- You will receive an error if you try to provide a Get or Set body with an abstract property.
- You will receive an error and your PeopleCode program will be terminated if you try to call an abstract method or property at runtime, unless caught in a try-catch block.
- The class that implements an interface must still assign %Super in its constructor.

Interfaces

The concept of an interface class is purely a syntactic assist when you are defining an application class which is totally composed of abstract methods and properties. In this case by simply specify the keyword **interface** you are indicating that all the methods and properties are abstract. The following two definitions are semantically equivalent.

```
class MyInterface
   method MyMethod1() abstract;
method MyMethod2() Returns string abstract;
   property string myproperty1 abstract readonly;
   property number myproperty2 abstract;
property number myproperty3 abstract;
end-class;

Interface MyInterface
   method MyMethod1();
method MyMethod2() Returns string;
   property string myproperty1 readonly;
   property number myproperty2;
property number myproperty3;
end-class;
```

When you provide an implementation for an Interface you can also use the keyword **Implements** instead of **Extends.** While this is not mandatory, specifying **Implements** describes more accurately what your application class is doing.

If your class implements an interface, you don't need to create a super object interface since the system does that automatically for you.

In addition if your constructor takes no parameters and simply exists to assign to the created instance to %super (that is, there is only one statement such as `%Super = create mySuper();` then you don't need to use a constructor at all.

Constructors

The constructor for a class is the public method with the same name as the (short name of the) class. The statements contained in this method (if any) provide the initialization of the class.

This constructor is *always* executed when an object of the class is instantiated.

Note: Before a constructor runs, the instance variables for the class are set by default based on their declared types.

Instantiate new objects of an application class by using the Create function. This function takes the name of the class, and any parameters needed for the constructor method.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

If the short class name is unambiguous, that is, only one class by that short name has been imported, you can use just the short class name.

The following code instantiates an object of the class Fruit:

```
&Fref = Create Fruit();
```

If there's a possibility that the name is ambiguous, you can use the full class name to instantiate the object.

The following code instantiates an object of the Invoice class:

```
&InvObj = Create pt:examples:Invoice();
```

If the Create function is used in the context of further object expressions, that is, with a reference to members by a dot operation, the function call must be enclosed in parentheses. This is to emphasize that the creation happens before the member reference. For example:

```
&InvCust = (Create Invoice()).Cust();
```

If necessary, the constructor is supplied its parameters by the call-list after the class name in the create statement. For example:

```
&Example = create Example(&ConstructorParameter1, 2, "Third");
```

A class that does not extend some other class does not need any constructor.

A class that extends another class must have a constructor, and in the constructor, it must initialize its super class. This restriction is relaxed if the super class constructor takes no parameters, and all the constructor does is assign it to %Super. In this case, the runtime creates the super object and runs its constructor automatically. The benefit of this is two-fold: at design time you do not need to provide a constructor since the runtime automatically does the equivalent of `%Super = Create MySuperObject();` Also, at runtime, you may notice a performance increase since the super class object creation and construction are done without any PeopleCode. This latter benefit can be compounded in the case where there are multiple levels of inheritance.

To the general case, to initialize a superobject, an instance of the superclass is assigned to the keyword %Super in the constructor for the subclass. This assignment is allowed only in the constructor for the subclass.

The following example shows this type of assignment:

```
class Example extends ExampleBase
   method Example();
   ...
end-class;

Global string &CurrentBaseString;

method Example
   %Super = create ExampleBase();
   &BaseString = &CurrentBaseString;
   &SlashString = &BaseString;
   &ImportantDate = Date(19970322);
end-method
```

If your subclass' constructor only exists to create the superclass object and assign that to your %Super, you can dispense with providing a constructor completely as the following example illustrates.

```
class A
   ...
end-class;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
Class B extends A
...
end-class;

Class C extends B
...
end-class;

...
Local C &c = Create C();

...
```

Classes A, B and C have no constructors and the one call to `Create C` creates objects of class C, B and A and run their constructors. PeopleSoft recommends that unless your constructors take parameters and need to do more than be assigned to their %Super, that you do not provide constructors since that simplifies design time as well as may improve runtime performance significantly.

The above example is semantically equivalent to the following, except that it may run much faster, since it does not have to run PeopleCode at each step of the construction process.

```
class A
   ...
end-class;

Class B extends A
   Method B();
...
end-class;

method B
%Super = Create A();
end-method;

Class C extends B
   Method C();
...
end-class;

method C
%Super = Create B();
end-method;
```

Note: Application classes don't have destructors, that is, a method called just before an object is destroyed. The PeopleCode runtime environment generally cleans up any held resources, so they're not as necessary as they are in other languages.

Related Links

Superclass Reference

External Function Declarations

External function declarations are allowed in application classes, in the global and component variable declarations, after the class declaration (after the end-class statement), and before the method definitions. For example:

```
import SP:Record;

class Person extends SP:Record
   method Person(&pid As string);
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
   method getPerson() Returns Record;
   method getUserName() Returns string;

private
   instance Record &recPerson;

end-class;

Declare Function getUserName PeopleCode FUNCLIB_PP.STRING_FUNCTIONS FieldFormula;

method Person
   /+ &pid as String +/

   %Super = create SP:Record(Record.SPB_PERSON_TBL);
   &recPerson = %Super.getRecord();
   &recPerson.PERSON_ID.Value = &pid;

end-method;

method getPerson
   /+ Returns Record +/

   Return &recPerson;

end-method;

method getUserName
   /+ Returns String +/
   Local string &formattedName;

   &formattedName = getUserName(&recPerson.PERSON_ID);
   Return &formattedName;
end-method;
```

When application class properties and instance variables are used as the argument to functions or methods, they are always passed by value, never by reference. This means that the called function or method cannot change the value of the property or instance variable. If you want a function call to change a property or instance variable, use a local variable in the call and then assign the property or instance variable after the call.

Suppose you have the following class and you want to call Meth2 in the body of Meth1, passing it MyProp:

```
class MyClass
   property number MyProp;
   method Meth1();
   method Meth2(&i as number out);
end-class;
```

The following PeopleCode *fails* with a compile-time error:

```
method Meth1
   Meth2(%This.MyProp);   /* error - field or temp name required. */
   Meth2(&MyProp);   /* error - field or temp name required. */
end-method;
```

The following PeopleCode is valid:

```
method Meth1
/* Assignment needed if &i is input as well as output in Meth2. */
   local number &Var = %This.MyProp;
   Meth2(&Var);
   %This.MyProp = &Var;
end-method;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Note: You call a Java program from an Application Class the same way you do using any other PeopleCode program, that is, by using one of the existing Java class built-in functions.

See From Java to PeopleCode.

Naming Standards

This section describes the naming standards for:

- Packages.
- Classes.
- Methods.
- Properties.

Naming Packages

The naming standard for application packages is in the following format.

```
CC_XXX[_YYY]
```

Where CC is the company name (for example, PS is PeopleSoft), XXX is the product line, and YYY is the product code.

Examples are PS_CRM and PS_CRM_RB.

Naming Classes

Use a constructor to be the same name as the short name for the class. PeopleSoft recommends that you do not name classes to be GetXxx.

Naming Methods

Make method names simple verb or verb object words, spelled out, first letter of each word capitalized. Examples: GetField, Save, SetDefault, WriteRecord

Naming Properties

Make property names nouns, likewise spelled out, first letter of each word capitalized. Examples: Dimension, HTTPMethod, PathInfo, SubscriptionProcessId.

For Boolean read-only properties, sometimes IsXxx is appropriate. Examples: IsOpen, IsNewFieldID, IsChanged, IsDeleted

State Boolean properties positively, that is, IsChanged, as opposed to negatively, IsUnChanged. This avoids double negatives when testing (If Not &MyField.IsUnChanged Then. . . .)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Import Declarations

Before you can use a class name in a PeopleCode program (either a class definition program or an ordinary PeopleCode program), you must first import it using an import statement at the beginning of your program.

An import statement names either all the classes in a package or one particular application class.

If you're importing all the classes in a package, the syntax for the import statement ends with the following:

```
:*
```

This makes all the application classes directly contained in the named package available. Application classes contained in subpackages of the named package are *not* made available.

If you're importing one particular application class, the syntax of the import statement ends with the short name of the class. Only that class is made available.

For example, the following imports all the classes of the package named Fruit:

```
Import Fruit:*;
```

The following imports only the application classes Banana and Kiwi. If the package named Fruit contains other classes, those are not made available to the PeopleCode program:

```
Import Fruit:Banana;

Import Fruit:Kiwi;
```

If you had a subpackage in Fruit named Drinks, you could access all the classes in that subpackage like this:

```
Import Fruit:Drinks:*;
```

A PeopleCode program (either a separate program or one contained within a class definition) can use only application class names that have been imported. However, a class definition can use its own name without having to import it.

It's possible to import two packages which contain application classes with the same short name. For example, suppose my package Fruit contained classes Apple and Banana. Suppose a second package, Drinks, contained Apple and Cherry.

```
Import Fruit:*;

Import Drinks:*;
```

You could refer to the Banana and Cherry classes using just the short name of the class. However, you couldn't refer to the Apple class by the short name. You must always use the full name reference (that is, the name of the package and the name of the class) when referring to Apple.

```
Global Banana &MyBanana;

Local Cherry &CherryTree;

Component Fruit:Apple &GreenApple;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The following line produces an error, because the program doesn't know which Apple class you're referring to:

```
Component Apple &GreenApple;
```

Note: Single class imports (such as, Import Fruit:Banana) are checked for existence when you save your PeopleCode.

Self-Reference

A method can refer to the current object using the %This system variable.

Due to subtyping, %This is an object of either the method's class or a subclass of the method's class.

In PeopleCode, the methods and properties of the class *cannot* be used without an object qualification.

In the following code example, the line in bold indicates an error. You can't call the class this way: you must use %This.

```
class FactorialClass
   method factorial(&I as number) returns number;
end-class;

method factorial
   if &I <= 1 then
      return 1;
   end-if;

   return &I * factorial(&I - 1); /* error - factorial undefined */

   return &I * %This.factorial(&I - 1); /* okay */
end-method;
```

One of the implications of this is that when you're writing a method, there isn't any way to guarantee you'll access your own class' version of a public method (rather then a subclass') as it might be overridden by a subclass. The only way to make sure that you can access your own method is to make it private.

If you have some action that you also want to make public, and you want guaranteed access to it, you can make the action a private method, then define a public method for it that calls the private one.

In the following example, factorial is the public method that can be used by other classes. myFactorial is the private action.

```
class FactorialClass
   method factorial(&I as number) returns number;
private
   method myFactorial(&I as number) returns number;
end-class;

method factorial
   return myFactorial(&I);
end-method;

method myFactorial
   if &I <= 1 then
      return 1;
   end-if;

   return &I * %This.myFactorial(&I - 1);
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
end-method;
```

If you declare an instance variable as private you can still access it as a private property in another instance of the same class. For example, given the following declaration:

```
class Example

   private

      instance number &Num;

end-class;
```

A method of Example could reference another Example instance's &Num instance variable as follows:

```
&X = &SomeOtherExample.Num;
```

Using %This with Constructors

%This when used in application class constructor code refers to the object currently being constructed. It does not refer to the dynamic this pointer of some object under construction. Given these two application classes, the PeopleCode `%This.Test()` in the Base constructor *always* refers to the Test method in the Base class.

```
class Base
   method Base();
   method Test();
   method CallTest();
   property string sTestResult;
end-class;

method Base
   %This.Test();
end-method;

method Test
   &sTestResult = "BASE_METHOD_CALLED";
end-method;

method CallTest
   %This.Test();
end-method;

import PACKAGE:Base;

class Extend extends PACKAGE:Base;
   method Extend();

   method Test();
end-class;

method Extend
   %Super = create PACKAGE:Base();
end-method;

method Test
   /+ Extends/implements PACKAGE:Base.Test +/
   %This.sTestResult = "EXTENSION_METHOD_CALLED";
end-method;
```

Even though the Extend class method provides its own Test method which overrides Base's Test method, in PeopleCode `create Extend()` which ultimately runs Base's constructor, the `%This.Test()` call in Base's constructor still references Base's Test method, not Extend's Test method, because %This always refers to the object under construction

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Properties and Constants

This section discusses the following ways to use properties and constants with application classes:

- Differentiating between properties and methods.
- Overriding properties.
- Using the Get and Set keywords.
- Using read-only properties.
- Using methods and properties for collections.
- Declaring constants.

Differentiating Between Properties and Methods

A method is a procedure or routine, associated with one or more classes, that acts on an object.

A property is an attribute of an object.

PeopleSoft recommends that you use read-write or read-only properties instead of creating methods named GetXxx and SetXxx. For example, instead of creating a method GetName, that takes no parameter, just to return the name of an object, create a read-only property Name.

If your properties simply set or return the value of an instance variable, it is far more efficient to declare the property that way than have a get and set method. The overhead of having a get and set method means that each time the property is reference some PeopleCode has to be run.

Application classes can have read-only properties, but no indexed properties.

Considerations Creating Public Properties

There are two implementations of (public) properties:

- as instance variables.
- as get-set methods.

From outside the class, you cannot tell the difference between them (for example, both are dynamically bound). However, if you just want to expose an instance variable to users of the class, you can declare a property of that name and type, which declares the instance variable too:

```
class xxx
     property string StringProp;
end-class
```

If you want the property to be read-only outside the class, use the following code:

```
class xxx
     property string StringProp readonly;
end-class
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Both of these code examples declare an instance variable called &StringProp and provide its value for getting and change its value for setting (if not readonly). You can think of this as shorthand for the usual implementation of get-set methods.

If you want to implement the same with code (perhaps deriving the property from other instance variables or other data), use the following sort of PeopleCode program:

```
class xxx
   property string StringProp get set;

private
   instance string &inst_str;

end-class;

get StringProp
   /+ Returns String +/
   Return &inst_str; /* Get the value from somewhere. */
end-get;

set StringProp
   /+ &NewValue as String +/
   /* Do something with &NewValue. */
   &inst_str = &NewValue;
end-set;
```

To specify a read-only property, omit the set portions of the code example.

Overriding Properties

A property of a superclass can be overridden by a subclass by providing a different implementation.

The properties of a class are implemented by the keywords Get and Set, or by access to an otherwise private instance variable.

To access the property, you do not have to specify Get or Set: the context tells the processor which task you're doing. To create read-only properties, specify only a Get method, with no Set method, or for instance variable properties, specify Readonly.

For an instance variable property, there are two different ways for method code in the class itself to refer to the property:

- %This.*PropertyName*
- *&PropertyName*

The first way is dynamically bound, as it uses whatever (possibly overridden by a subclass) implementation of *PropertyName* that the current object provides.

The second way always accesses the private instance variable of the class that the method is declared in.

The following example returns strings, by converting the property. It also demonstrates overriding.

```
class A
   property number Anum;
   property string Astring get;
   property string Astring2 get;
end-class;

/* The following is a dynamic reference to the Anum property of the current object,⇒
 which might be a subclass of A, so this might not access the A class's implementat⇒
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
ion of Anum as an instance variable. */
Get Astring
   return String(%This.Anum);
end-get;

/* The following is a static reference to our &Anum instance variable. Since it doe⇒
s not use %This, it will not be overridden even if the current object is a subclass⇒
 of A. */
Get Astring2
   return String(&Anum);
end-get;

/* The following overrides the Anum property of our superclass,
in this case by providing another instance variable implementation.
This gives us our own &Anum instance variable. */
class B extends A
   property number Anum;
end-class;
. . .
/* Set the Anum property in B. Because of the above definitions, this sets
the &Anum instance variable in the B object, but not the &Anum instance
variable in its superobject. In the absence of other setting, the latter will
be defaulted to 0. */

local B &B = Create B();
&B.Anum = 2;

&MyValue = &B.Astring; /* &MyValue is "2" */
&MyValue = &B.Astring2; /* &MyValue is now "0" */
```

Using Get and Set with Properties

PeopleSoft recommends against defining properties that are public and mutable in application classes (similar to public instance variables) because this allows external code to read and change the internal state of the object without any controls. Instead, modify the property declarations with the Get and Set keywords.

There is a slight performance advantage, and you write less code, if you use the Get and Set keywords over using get and set methods.

If you define a property with the Get and Set keywords, you also must define a get or set block in the same part of the code that contains the method bodies.

Using Read-Only Properties

PeopleCode read-only properties are functionally similar to static variables, as long as the class that defines the properties initializes them and does not change them. The difference is that you need an instance of the class to access them.

For example, consider a Category object that has a CategoryType member that can have one of the following values:

- ‘R’ for Regular
- ‘B’ for Browse
- ‘N’ for News

You can define three read-only properties corresponding to each of these values, REGULAR, BROWSE, and NEWS, then initialize them to the appropriate values in the constructor of the class.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

When you write code to evaluate the CategoryType of the Category object, perform a test like this:

```
If (&category.getCategoryType() = &constants.NEWS) then...
```

PeopleSoft recommends referring to the read-only properties, rather than their literal values, for the following reasons:

- If you spell a literal value incorrectly, the PeopleCode editor does not catch it; if you spell a read-only property wrong, it does.
- If you ever need to change the value of a read-only property, you only have to do it in one place.
- It makes the code more maintainable and reusable (because NEWS is more intelligible than ‘N’).

Using Methods and Properties for Collections

Application classes can contain collections. Collections of objects generally have at least the following methods and properties.

- First()
- Item(*Index*)
- Next()
- Count (as a property)

All numeric indexes in PeopleCode are one-origin, that is, start all indexes at 1, not 0.

Declaring Constants

PeopleSoft recommends that if constants are inextricably linked to a class, you should define them within that class. If the constants are more general, potentially used by multiple classes, consolidate the constants into a constants class at application-level or package-level.

Message catalog set and message numbers are good candidates to centralize into a single constants class. It can improve the readability of code and make it easier to maintain these values.

For example, you can define a constant MSG_SET_NBR, and then define constant values for each message that explain a little about what the message represents (like REQUIRED_VALUE_MISSING, UNIMPLEMENTED_METHOD, or INSUFFICIENT_PRIVILEGES).

Using Variables in Application Classes

This section discusses how to use the following variables in application classes:

- Instance variables.
- Global variables.
- Overriding variables and properties.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Placement of Variable Declarations

Variables are declared after the class definition (the end-class statement) before anything else. After you have declared a variable, you can use it anywhere in your program.

```
class Example
   method Example_M1(&par As string);
end-class;

Global boolean &b;

method Example_M1
   /+ &par as String +/
   &b = False;
end-method;
```

Declaring Private Instance Variables

A private instance variable is private to the class, not just to the object instance. For example, consider a linked-list class where one instance needs to update the pointer in another instance. Another example is the following class declaration:

```
class Example private instance number &Num; end-class;
```

A method of Example could reference another instance of the Example &Num instance variable as:

```
&X = &SomeOtherExample.Num;
```

Avoid making every instance-scoped variable a public property. You should consider each variable individually and decide if it belongs in the public interface or not. If it does, decide if the variable warrants get or set modifiers and therefore should be a public property. If the variable only serves internal purposes to the class, it should be declared as a private instance variable.

Global Variables

PeopleSoft recommends avoiding global variables in application classes unless there is a situation where no other code works. Generally, an application class should not know about anything scoped outside of its instance. There are exceptions, since not all application classes should be standalone. For example, an application class that interacts with the Component Buffer must know about the Component Buffer objects.

Overriding Variables and Properties

PeopleSoft recommends against overriding of variables and of properties.

Since instance variables are private in scope, you cannot access them in subclasses, but you can redeclare them in subclasses. The same is true of public properties; you can even explicitly access the overridden or overriding property. However, overriding is not recommended.

Superclass Reference

A method can refer to a member of its superclass by using the %Super system variable. This construction is needed only to access superclass members that are hidden by overriding members in the current class.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

In the following example, the classes that extend the general BuildingAsset class each have their own method DisasterPrep, that does the specific processing, then calls the superclass (generic) version of DisasterPrep.

```
/* generic building class */
class BuildingAsset
   method Acquire();
   method DisasterPrep();
end-class;

method Acquire
   %This.DisasterPrep();
end-method;method DisasterPrep
   PrepareForFire();
end-method;

/* building in Vancouver */
class VancouverBuilding extends BuildingAssetmethod DisasterPrep();
end-class;

method DisasterPrep
   PrepareForEarthquake();%Super.DisasterPrep(); /* call superclass method */
end-method;

/* building in Edmonton */
class EdmontonBuilding extends BuildingAssetmethod DisasterPrep();
end-class;

method DisasterPrep
   PrepareForFreezing();%Super.DisasterPrep(); /* call superclass method */
end-method;

local BuildingAsset &Building = Create VancouverBuilding();

&Building.Acquire(); /* calls PrepareForEarthquake then PrepareForFire */

&Building = Create EdmontonBuilding();

&Building.Acquire(); /* calls PrepareForFreezing then PrepareForFire */
```

Downcasting

Downcasting is the process of determining if an object is of a particular subclass type. If the object has that subtype (either the object is of that subtype, or is a subtype of it), a reference to the subobject is returned, otherwise Null is returned. In either case, the type of the resulting value is compatible with the named subclass type.

This downcast inquiry into the actual type of an object can be used when the object has been passed to some general facility, then passed back to more specific code. For example, the general facility might be a dispatch mechanism, or a new storage structure such as a binary balanced tree. These general facilities won't know about specific types, but it might be necessary for the specific program using the general facility to recover the actual type of an object that is returned to it by the general facility.

A downcast should *not* be used when you could add members to a common base class to provide the same functionality. In other words, if you find yourself using the downcast to test whether the object is one or another of several related types, you should add members to the common base class to provide the operations or properties that you are trying to access, then provide separate implementations of those actions or properties in each specific class.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

If the downcast operator is to be used in the context of further object expressions (such as references to other members using dot notation) then the downcast must be enclosed in parentheses to emphasize that the downcast happens before the member reference.

```
class Fruit
   property number FruitCount;
end-class;

class Banana extends Fruit
   property number BananaCount;
end-class;
```

In the following code example, first the variables are assigned. All the variable assignments are legal, for Banana is a subtype of Fruit.

```
local Banana &MyBanana = Create Banana();
local Fruit &MyFruit = &MyBanana;  /* okay, Banana is a subtype of Fruit */
local number &Num = &MyBanana.BananaCount;
```

The next two lines of code don't produce an error, as &MyFruit is currently a Banana at runtime.

```
&MyBanana = &MyFruit as Banana;

&Num = (&MyFruit as Banana).BananaCount; /* same as &MyBanana.BananaCount */
```

In the next lines of code, we're reassigning &MyFruit to be of type Fruit, that is, of the superclass Fruit. When you try to reassign &MyFruit as Banana, &MyBanana is assigned as Null, because &MyFruit is no longer of type Banana.

```
&MyFruit = Create Fruit();

&MyBanana = &MyFruit as Banana; /* assigns Null - &MyFruit isn't a Banana */
```

Exception Handling

Use the Exception class to do exception handling in your PeopleCode. This class provides a try, catch, and throw mechanism so you don't need to check after each operation for errors. Instead, by the structure of the try-catch blocks, you can declare when you are interested in handling exceptions, and how you want to handle them.

Exceptions are instances or subclasses of the PeopleCode Exception class. Oracle recommends that when applicable, application class methods should throw exceptions instead of communicating back to the calling code with return values. You can create exceptions by:

- Creating an Exception base class that encapsulates the built-in function call and handles its function parameters consistently. This is the preferred way.
- Calling the built-in function CreateException.

Since a method can throw exceptions for several different reasons, Oracle recommends that you:

- Create Exception subclasses often.
- Throw strongly typed exceptions.

This allows the calling code to make decisions based on the exception type.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

For example, a method that retrieves customer data from a database might throw an exception named SQLException if a database error occurs, or an exception named PrivilegeException if the current user doesn't have the appropriate permissions to perform the operation. There could be different errors causing either of these exception types to be thrown in this method; if necessary, you can write the calling code to examine the specific message numbers and react accordingly.

Oracle recommends that you always catch an exception; if it is not caught, it causes a runtime error. Use a try-catch block.

Not catching an exception causes a runtime error and can cause PeopleTools to display a dialog box with the message catalog entry and information about the technical context of the exception. The reasons for avoiding this by using try-catch blocks are:

- Application code often continues some form of processing even in the event of an exception; you should not assume that the script stops all processing if an exception occurs.
- The error message that PeopleTools displays might not be appropriate for end-users because of its technical information.

Related Links

Exception Class Built-in Functions

"CreateException" (PeopleTools 8.54: PeopleCode Language Reference)

"throw" (PeopleTools 8.54: PeopleCode Language Reference)

"try" (PeopleTools 8.54: PeopleCode Language Reference)

Commenting and Documenting Application Classes

This section contains guidelines for writing method header comments, class header comments, and tags inside the comments. It discusses:

- Comments and documentation
- Method header comments
- Class header comments

Understanding Comments and Documentation

Documentation is important in all code, but even more so in application class code, which aims at, and incurs certain overhead in the name of, higher levels of reuse.

There are two types of inline comments:

- Internal comments, which start with /* and end with */.
- Comments which can potentially be used to generate API documentation, which start with /* and end with */. You can write method header and class header comments for application classes, and you can use the comment tags, with this type of comment.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Warning! In application classes you will see the use of /+ +/ style comments. *Do not use these in your PeopleCode.* These annotations are generated by the compiler. If you use them, they will be removed the next time you validate, compile, or save your PeopleCode. They are used to provide signature information on application class methods and properties, and are regenerated each time the compiler compiles your application class PeopleCode. Instead, use the standard commenting mechanisms listed above.

PeopleSoft recommends keeping a running line of asterisks along one side of an extensive comment to help the readability of the code by making the entire comment stand out from the surrounding code.

Method Header Comments

The following is an example of documentation conventions for method header comments, which are also suitable for PeopleCode. It contains comment tags, which are explained below the example.

```
/**
  * Description of what method does
  *
  * @param a optional description of param a
  * @param b optional descriptions of param b
  * @exception PrivilegeException thrown if etc, etc
  * @exception SQLException thrown if etc., etc.
  * @return String  -  description of potential values
  */
Method myMethod
   ...
End-method;
```

Method Comment Tags

The following are the suggested tags for commenting methods.

Tag	***Description***
@param *N*	Specify a description for each method parameter. The name of the parameter is specified after the keyword @param.
@exception *name*	Specify a description of each exception class. The name of the exception is specified after the keyword @exception. For example, the descriptions can explain what causes certain exceptions to be thrown.
@return *Type*	Specify a description of the return value. The type of data that is returned is specified after the keyword @return. For example, explain the potential values a method may return, whether it returns null in some circumstances, and so on.

Not all methods require documentation. For example, some simple set or get methods have method signatures that are descriptive enough. In other cases, it may suffice to include a brief sentence in the header explaining what the method does.

As with methods, PeopleCode get or set blocks should also carry method header comments.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Class Header Comments

Header comments for the class should provide descriptive information about the class, and may optionally include additional tags, indicating version and author:

```
/**
* class description
*
* @version 1.0
* @author amachado
*/
```

Class Header Comment Tags

The following are the suggested tags for commenting class headers.

Tag	*Description*
@version *number*	Specify a version number for a class.
@author *name*	Specify an author for a class.

Designing Base Classes

This section discusses some ways you can design application classes.

- Base data classes
- Abstract base classes
- Generic base classes
- Utility classes

Base Classes

Base classes contain a representation of data elements, such as documents, categories, users, and miscellaneous security-related entities.

To design the document data element to be integration-friendly, PeopleSoft recommends you start with a relatively basic base class. Then use more specialized types of documents to create a subclass from that base class, adding the necessary specialized attributes.

Even if you think of ways to use data to drive the business rules, PeopleSoft recommends that you do not place them into your data objects. Replicating business rules for every instance of a data element can be detrimental to performance.

Abstract Base Classes

Abstract base classes contain reusable logic for PeopleCode classes; you do not instantiate them directly. Instead, you instantiate classes that are subclasses of the abstract base class. Abstract base classes use

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

placeholder methods for specialized logic, and its subclasses override those methods to provide the specialized logic.

An example of a candidate for an abstract base class is a class that is used for administering a data entity, such as an invoice. Such a class has a Save method. A Save method can use normal methods to call generic validation routines, talk to the database, and handle errors; it can use the placeholder methods for specialized logic, such as mapping a given data class to a particular database table.

PeopleSoft recommends that you program an active validation check into your placeholder method that causes a runtime error, such as throwing an UnimplementedMethodException, if an abstract base class placeholder method hasn't been overridden.

Generic Base Classes

Generic base classes contain reusable logic for PeopleCode classes; you write them to be self-contained, fully implemented, and capable of being instantiated directly. This differs from abstract base classes, which are not instantiated directly and need subclasses that override methods to provide specialized logic.

Some examples of classes that are good candidates for creating generic base classes are:

- Service classes, which typically extend a class that provides infrastructure services, such as configurable application logging.
- Data classes, which typically extend a class that enables you to plug in adapters to support sorting their instances with custom sort algorithms.

Even when a class does not seem generic because it only has a couple of subclasses, you can still define it in your design as a generic base class rather than cloning common code across different classes. The main reason is maintainability: it's easier to maintain a single class than trying to keep track of the same code scattered across your database.

Utility Classes

Some reusable code is the kind you typically don't want to inherit, but you just want to use here and there. Utility classes can serve this purpose.

String parsing, data type conversion, and formatting routines are all good candidates for utility classes. PeopleSoft recommends that anytime you code something that's more than just a line or two, and that seems to be reusable, write it as a utility class.

Declaration of Application Classes

This section discusses instructions for declaring application classes, such as:

- Declaring application classes.
- Importing class names.
- Referencing Superclasses.
- Declaring private methods.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Declaring Application Classes

Application object references are declared in your PeopleCode programs by either the short name of the class (if the short name is unambiguous amongst all the imported classes), or by the full name of the class. Like all uses of class names, to use the name in a variable declaration, you must have imported the class. Application objects can be of Local, Global, or Component scope.

Every application class is a definition of a new data type in PeopleCode, like the record, rowset, or field data types. The application class includes both the definition of its external interface, its data (properties and instance variables), and its actions (methods), just like the PeopleSoft delivered classes.

Importing Class Names

When you import a class name, fully-qualifying it is optional. The syntax is:

```
<package>:<subpackage>:<...>:<classname or wildcard>
```

PeopleSoft recommends that you individually import each class when you import multiple classes from the same package, instead of using wildcards.

Referencing Superclasses

PeopleSoft recommends that you do not set %Super to a new instance of the current class you are defining because this would start an infinite loop.

```
/* Do not do this! */
%Super = %This;
```

Declaring Private Methods

PeopleSoft recommends that you use private methods for succinct operations, even if they aren't reused, to improve the readability and maintainability of the code. You can also do this by using many inline comments.

Scope of an Application Class

Application classes can be instantiated only from PeopleCode. These classes can be used anywhere you have PeopleCode, that is, in message notifcation PeopleCode, Component Interface PeopleCode, record field PeopleCode, and so on.

Application Classes Built-in Functions and Language Constructs

In this section, we discuss the Application classes built-in functions and language constructs, in alphabetical order.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Class

Syntax

```
Class classname [{Extends | Implements} Classname]    [Method_declarations]
[Property_declarations] [Protected    [Method_declarations]    [Instance_declarations]
[Constant_declaration]] [Private    [Method_declarations]    [Instance_declarations]
[Constant_declaration]] End-Class
```

Where Method_declarations are of the form:

```
Method methodname([MethodParam1 [, MethodParam2. . .] [Returns Datatype]] [abstract])
```

Where Property_declarations are of the form:

```
Property DataType PropertyName {{[Get] | [Set]} | [abstract] | [readonly]}
```

Where Instance_declarations are of the form:

```
Instance DataType &Variable1 [, &Variable2.
. .]
```

Where Constant_declarations are of the form:

```
Constant &Constant = {Number  | String | True | False | Null }
```

Description

Use the Class language construct to build application classes in an application package. All classes within a package must be uniquely named, however, classes contained in different packages do not have to be named uniquely.

External function declarations are allowed in application classes, in the global and component variable declarations, after the class declaration (after the end-class statement), and before the method definitions.

Parameters

classname	Specify the name of the class that you are creating. All classes within a package must be uniquely named, however, classes contained in different packages do not have to be named uniquely.
Extends | Implements *classname*	For a regular class, specify the name of the class that this class extends. If the class is an interface type of class, specify the name of the interface that this class implements. You must import the class to extend it.
Method_declarations	Specify the methods (and their signature) as used in this class.
Property_declarations	Specify the properties, and their usage, in this class.
Protected	Use this keyword to declare any methods, constants, or instance variables as protected to the class, that is, are only visible to the declaring class and subclasses.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Private	Use this keyword to declare any methods, constants, or instance variables as private to the class, that is, they can't be accessed by any other classes.
Instance_declarations	Specify any variables that should be in any instance (object) of the class.
Constant_declarations	Specify any constants that should be used with this class.

Returns

None.

Example

```
class Example extends ExampleBase
   method NumToStr(&Num as number) returns string;
   method AppendSlash();
   property number SlashCount get;
   property number ImportantDayOfWeek get set;
   property string SlashString readonly;
   property date ImportantDate;
private
   method NextDayOfWeek(&DoW as number) returns date;
   constant &Sunday = 1;
   instance number &BaseString;
end-class;
```

Related Links

Method

Get

Set

Get

Syntax

Get *PropertyNameStatementList* **End-Get**

Description

Use the Get language construct when defining properties in an application class that are implemented by methods rather than an instance variable. All properties within an application class must be uniquely named.

Parameters

Get *PropertyName*	Specify the name of the property that you're implementing.
StatementList	Returns the value of the property. In other words, this is a method which has no parameters and must return the value of the property.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

Depends on the assignment within *StatementList*

Example

```
Get FruitCount
  Return &MyFruit.Number();
End-Get;
```

Related Links

Method

Set

"Return" (PeopleTools 8.54: PeopleCode Language Reference)

Import

Syntax

Import *PackageName*:[*PackageName. . .*:]{*Classname* | *****}

Description

Before you can use a class name, you must first import it using an import declaration statement at the beginning of your program.

An import declaration statement names either all the classes in a package or a single application class.

Parameters

Import *PackageName*	Specify the name of the package that you want to import.
*****	Import all the classes of the specified package.
Classname	Import only this class of the specified package. You won't have access to any other classes in the specified package, only this one.

Returns

None.

Example

The following gives you access to all the classes in the package Fruit:

```
Import Fruit:*;
```

The following only gives you access to the class Banana in the package Fruit:

```
Import Fruit:Banana;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The following gives you access to the class Apple, in the package Drinks, which contains the package Fruit:

```
Import Drinks:Fruit:Apple;
```

Related Links

Class

Interface

Syntax

```
Interface classname [{Extends  | Implements} Classname]    [Method_declarations]
[Property_declarations] [Protected    [Method_declarations]    [Instance_declarations]
[Constant_declaration]] ] End-Interface
```

Where Method_declarations are of the form:

```
Method methodname([MethodParam1 [, MethodParam2. . .] [Returns Datatype]] [abstract])
```

Where Property_declarations are of the form:

```
Property DataType PropertyName {{[Get] | [Set]} | [abstract] | [readonly]}
```

Where Instance_declarations are of the form:

```
Instance DataType &Variable1 [, &Variable2.
. .]
```

Where Constant_declarations are of the form:

```
Constant &Constant = {Number  | String | True | False | Null }
```

Description

Use the Interface language construct to create classes of type interface in an application package. An interface class is a purely abstract class.

Parameters

An interface does not have Private methods or properties, but all the other parameters are identical to the Class language construct.

See Class.

Returns

None.

Related Links

Class

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Method

Syntax

Method *MethodNameStatementList***End-Method**

Description

Use the Method statement to define the methods of your application class.

Parameters

Method *methodname*	Specify the name of the method that you are creating.
StatementList	Specify the program of the method, what it does.

Returns

Depends on the method.

Example

```
method NumToStr
   return String(&Num);
end-method;

method AppendSlash
   &SlashString = &SlashString | "/";
end-method;
```

Related Links

Get

Set

"Return" (PeopleTools 8.54: PeopleCode Language Reference)

Set

Syntax

Set*PropertyNameStatementList***End-Set**

Description

Use the Set language construct when implementing properties in an application class. All properties within an application class must be uniquely named. The new value for the property is available in the &NewValue parameter of the Set method.

Note: You cannot create a set-only property. You can create only get-set properties.

Parameters

Set *PropertyName*	Specify the name of the property that you're implementing.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

StatementList Change the value of the property to be &NewValue.

Returns

None.

Example

```
Set FruitCount

   &Fruitcount = &MyFruit[&NewValue].ActiveRowCount();

End-Set;
```

Related Links

Get
Method

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Chapter 8

Application Data Set Classes

Understanding the Application Data Set Classes

The Data Migration Workbench is designed to manage the complexity of migrating configuration data across multiple PeopleSoft systems. Data Migration Workbench uses Application Data Sets (ADSs) as its underlying infrastructure. There are five main parts to the Data Migration Workbench:

- The ADS definition designer is used to define ADS definitions, which define the data sets that can be migrated. Each ADS definition includes a record hierarchy. An ADS definition has associated validation PeopleCode specified by an application class, which is the main subject of these topics.
- The Project Editor allows you to interactively create projects containing ADS instance data (that is, the data defined by ADS definitions) and edit their content.
- The Project Manager allows ADS projects to be exported to a file, compared from a file, or copied from a file.
- The Project Reviewer is used to view the results of compares, including validation.
- The Project Approver invokes the approval framework to assure that the each project has been properly reviewed and approved before it is copied.

PeopleTools supplies the base class application class, PTADSDEFN:AdsValidationBase, that provides the basic validation described in the following sections.

Prescribed methods described in the following sections of the validation application class are automatically invoked when ADS projects are compared or copied. If you wish to provide additional validation, or to override the base validation, you can implement an application class derived from PTADSDEFN:AdsValidationBase and register that class in the ADS definition designer part of the Data Migration Workbench. The derived class should override one or more of the automatically invoked methods.

Basic Validation

The DoADSValidations method provides basic validation by validating static prompts, translate values, Y/N values, and required fields. Because basic validation is always triggered for any copy or compare, you do not need to explicitly call DoADSValidations. Therefore, even when you do not define an extended application class for a specific ADS definition, basic validations are performed by this method. If a validation error is detected, DoADSValidations returns false and information about the error is written to the target database.

Extended Validation

You can extend the AdsValidationBase base class to define specific validation logic for your data sets. To provide data set-specific validation or transformation logic, you can extend three methods from

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

the base class and define any additional methods and properties as necessary. The following three AdsValidationBase class methods can be extended in your custom application class:

- OnPreCopyCompare
- OnPreUpdate
- OnPostCopy

Related Links

"Data Migration Workbench Overview" (PeopleTools 8.54: Data Migration Workbench)
"Defining Validation" (PeopleTools 8.54: Data Migration Workbench)

Importing Application Data Set Classes

The Application Data Set classes are application classes, not built-in classes, like Rowset, Field, Record, and so on. Before you can use these classes in your PeopleCode program, you must import them into your program.

An import statement either names a particular application class or imports all the classes in a package.

Using the asterisks after the package name makes all the application classes directly contained in the named package available. Application classes contained in subpackages of the named package are not made available.

Related Links

Import Declarations

AdsValidationBase Class

This section provides an overview of the AdsValidationBase class and discusses: AdsValidationBase class methods.

PeopleTools supplies the base class application class, PTADSDEFN:AdsValidationBase, that provides the basic validation described in the following sections. If you wish to provide additional validation, or to override the base validation, you can implement an application class derived from PTADSDEFN:AdsValidationBase and register that class in the ADS definition designer part of the Data Migration Workbench. The derived class should override one or more of the automatically invoked methods.

Related Links

"Defining Validation" (PeopleTools 8.54: Data Migration Workbench)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

AdsValidationBase Class Methods

In this section, the AdsValidationBase class methods are presented in alphabetical order.

AdsValidationBase

Syntax

AdsValidationBase(*project_name*)

Description

This is the base class constructor supplied by Oracle. If the ADS definition does not specify an application class, this constructor will be automatically invoked when ADS projects are copied or compared. If the ADS definition *does* specify an application class, the constructor of the specified class will be automatically invoked when ADS projects are copied or compared. In the latter case, the derived class constructor must invoke this constructor as a %Super.

Parameters

project_name	Specifies the data migration project name as a string.

Returns

None.

Example

Use this methodology to instantiate a subclass to perform extended validations:

```
import PTADSDEFN:AdsValidationBase;

class ADSValidations1 implements PTADSDEFN:AdsValidationBase;
   method ADSValidations1(&ProjectName As string);
end-class;

/* constructor */

method ADSValidations1
   /+ &ProjectName as String +/
   %Super = create PTADSDEFN:AdsValidationBase(&ProjectName);
end-method;
```

Related Links

Constructors

DoADSValidations

Syntax

DoADSValidations(*&ADS_rowset, ADS_name*)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

In the base class supplied by Oracle, this method provides basic validation of static prompts, translate values, Y/N values, and required fields.

The base class method will be automatically invoked for each ADS instance when ADS projects are copied or compared unless the method is overridden in the derived application class for the current ADS definition. If the method is overridden, then the overriding method from the derived class will be automatically invoked. During copy, this method is called for all objects in the project before any objects are copied so that a single validation error anywhere in the project will prevent any objects from being copied.

When this method encounters a validation error, it invokes the ReportErrorModified method to store the error in the database so that it can be reviewed later on the Validation page.

Parameters

&ADS_rowset	Specifies the current ADS rowset instance as a rowset object. The rowset contains the data from the source project file.
ADS_name	Specifies the name of the current ADS definition as a string.

Returns

A Boolean value: True if all basic validations succeeded, False if any errors were encountered.

Example

```
import PTADSDEFN:AdsValidationBase;

class AdsValidationSample extends PTADSDEFN:AdsValidationBase
   method AdsValidationSample(&ProjectName As string);
   method DoADSValidations(&ADSRowset As Rowset, &ADSName As string,) Returns boole⇒
an;

end-class;

method AdsValidationSample
   /+ &ProjectName as String +/

   %Super = create PTADSDEFN:AdsValidationBase(&ProjectName);

end-method;

method DoADSValidations
   /+ &ADSRowset as Rowset, +/
   /+ &ADSName as String +/
   /+ Returns Boolean +/

   /* delegate to the base class DoADSValidations method */
   Return %Super.DoADSValidations(&ADSRowset, &ADSName);

end-method;
```

Related Links

ReportErrorModified

Understanding Rowset Class

"Defining Validation" (PeopleTools 8.54: Data Migration Workbench)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

OnPreCopyCompare

Syntax

OnPreCopyCompare(*&ADS_rowset, ADS_name*)

Description

This method will be automatically invoked for each ADS instance when ADS projects are copied or compared unless the method is overridden in the derived application class for the current ADS definition. If the method is overridden, then the overriding method from the derived class will be automatically invoked. During copy, this method is called for all objects in the project before any objects are copied so that a single validation error anywhere in the project will prevent any objects from being copied.

The definition of this method in the base class is an “empty implementation.”

If this method encounters a validation error, it should invoke the ReportErrorModified method to store the error in the database so that it can be reviewed later on the Validation page.

Parameters

&ADS_rowset	Specifies the current ADS rowset instance as a rowset object. The rowset contains the data from the source project file.
ADS_name	Specifies the name of the current ADS definition as a string.

Returns

A Boolean value: True if pre-copy compare validations succeeded, False if any errors were encountered.

Example

```
import PTADSDEFN:AdsValidationBase;

class AdsValidationSample extends PTADSDEFN:AdsValidationBase
   method AdsValidationSample(&ProjectName As string);
   method OnPreCopyCompare(&ADSRowset As Rowset, &ADSName As string,) Returns boole⇒
an;

end-class;

method AdsValidationSample
   /+ &ProjectName as String +/

   %Super = create PTADSDEFN:AdsValidationBase(&ProjectName);

end-method;

method OnPreCopyCompare
   /+ &ADSRowset as Rowset, +/
   /+ &ADSName as String +/
   /+ Returns Boolean +/

   /* place code to validate the input rowset here */

end-method;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

ReportErrorModified

Understanding Rowset Class

"Defining Validation" (PeopleTools 8.54: Data Migration Workbench)

OnPreUpdate

Syntax

OnPreUpdate(*&ADS_rowset, ADS_name*)

Description

This method will be automatically invoked after all data in each distinct ADS name in the project has been copied.

The definition of this method in the base class is an “empty implementation.”

If this method encounters a validation error, it should invoke the ReportErrorModified method to store the error in the database so that it can be reviewed later on the Validation page.

If errors are detected by this method, subsequent data will not be copied, but any data already copied to the database will not be rolled back.

Parameters

&ADS_rowset	Specifies the current ADS rowset instance as a rowset object. The rowset contains the data from the source project file.
ADS_name	Specifies the name of the current ADS definition as a string.

Returns

A Boolean value: True if pre-copy compare validations succeeded, False if any errors were encountered.

Example

```
import PTADSDEFN:AdsValidationBase;

class AdsValidationSample extends PTADSDEFN:AdsValidationBase
   method AdsValidationSample(&ProjectName As string);
   method OnPreUpdate(&ADSRowset As Rowset, &ADSName As string,) Returns boolean;

end-class;

method AdsValidationSample
   /+ &ProjectName as String +/

   %Super = create PTADSDEFN:AdsValidationBase(&ProjectName);

end-method;

method OnPreUpdate
   /+ &ADSRowset as Rowset, +/
   /+ &ADSName as String +/
   /+ Returns Boolean +/
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
   /* place code to validate the input rowset here */
end-method;
```

Related Links

ReportErrorModified
Understanding Rowset Class
"Defining Validation" (PeopleTools 8.54: Data Migration Workbench)

OnPostCopy

Syntax

OnPostCopy(*ADS_name*, *&content_list*)

Description

This method will be automatically invoked for each ADS instance when ADS projects are copied or compared unless the method is overridden in the derived application class for the current ADS definition. If the method is overridden, then the overriding method from the derived class will be automatically invoked. During copy, this method is called for each object in the project immediately prior to copying the object to the database. This occurs only after OnPreCopyCompare has been called for all objects with no validation errors.

The definition of this method in the base class is an “empty implementation.”

This method should be used for validations that require SQL access to all the data that was in the project and in the target database simultaneously. If any errors are encountered and cleanup is required, updates can be performed by this method.

If this method encounters a validation error, it should invoke the ReportErrorModified method to store the error in the database so that it can be reviewed later on the Validation page.

In addition, the OnPreUpdate method can perform database updates. If severe errors are detected by this method, the current data set will not be copied and subsequent data sets will not be copied; however, any data sets already copied to the database will not be rolled back.

Parameters

ADS_name Specifies the name of the current ADS definition as a string.

&content_list Specifies an array of integers that identify the keys of the objects in the current project for the current ADS name.

To translate this array into the keys of objects, one can query the project definition tables in the target database as follows:

```
SELECT PTADSCONTENTID, SEQNBR, PTBINDSYMBOL,
 PTADSBINDEXPR
     FROM PSPROJBINDITEM
     WHERE PROJECTNAME = :1 AND PTADSNAME = :2 AND
 PTADSCONTENTID IN (:3, :4, ...)
     ORDER BY SEQNBR, PTADSCONTENTID");
```

The fields and bind variables are defined as follows:

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- `:1` – The project name (which is stored in the AdsValidationBase property called strProjectName).
- `:2` – TheADS definition name.
- `:3, :4, ...` – The integers in the *&content_list* array.
- `PTBINDSYMBOL` – The ADS key name.
- `PTADSBINDEXPR` – The ADS key value.
- `SEQNBR` – The key sequence number.

The keys thus retrieved are the unique keys of the top-level record in the ADS definition. They are also keys, but generally not unique keys, of the child records in the ADS definition.

Once the keys are retrieved, you can use the rowset API to validate the data. The records in the rowset can be determined from the ADS definition with the following query:

```
SELECT RECNAME, PTPARENTRECNAME
     FROM PSADSDEFNITEM
     WHERE PTADSNAME = :1
```

The fields and bind variables are defined as follows:

- `:1` – The ADS definition name.
- `RECNAME` – The child record name.
- `PTPARENTRECNAME` – The parent record name or blank when RECNAME is the root record.

Returns

A Boolean value: True if post-copy compare validations succeeded, False if any errors were encountered.

Example

```
import PTADSDEFN:AdsValidationBase;

class AdsValidationSample extends PTADSDEFN:AdsValidationBase
   method AdsValidationSample(&ProjectName As string);
   method OnPostCopy(&AdsName As string, &ContentList As array of integer) Returns ⇒
boolean;

end-class;

method AdsValidationSample
   /+ &ProjectName as String +/
   %Super = create PTADSDEFN:AdsValidationBase(&ProjectName);
end-method;

method OnPostCopy
   /+ &AdsName As string +/
   /+ &ContentList As array of integer +/

   /* place code to validate the data just copied here */

end-method;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

ReportErrorModified

Understanding Rowset Class

"Defining Validation" (PeopleTools 8.54: Data Migration Workbench)

ReportErrorModified

Syntax

ReportErrorModified(*&recReportKey*, *&recReportError*)

Description

Invoke the ReportErrorModified method to write validation errors to the database to be reviewed later on the Validation page.

Invocation of the ReportErrorModified method is optional and can be skipped if error reporting in the validation report is not a requirement for your custom validation.

Important! ReportErrorModified is a protected method and *must not be* extended in your custom application class.

Parameters

&recReportKey	Specifies a record based on the PSCOMPOBJKEY record definition.
&recReportError	Specifies a record based on the PSCOMPOBJERR record definition.

Returns

None.

Example

Example 1

The following pseudo-code excerpt demonstrates how to invoke the ReportErrorModified method:

```
Local Record &recReportKey, &recReportError, &recParent;

&recReportKey = CreateRecord(Record.PSCOMPOBJKEY);
&recReportError = CreateRecord(Record.PSCOMPOBJERR);

*** error processing ***

If * error type 1 *
/* Set error record field values */
   &recReportError.PTADSVALIDTYPE.Value = "*";
   ***
   Else
   If * error type 2 *
   /* Set error record field values */
      &recReportError.PTADSVALIDTYPE.Value = "*";
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
      ***
   End-If;
End-If;

ReportErrorModified(&recReportKey, &recReportError);
```

Example 2

The PTADSDEFN:AdsValidationBase:ProcessValidationError method provides a complete example of how to invoke ReportErrorModified:

```
method ProcessValidationError
   /+ &RecError as Record +/

   Local number &i, &j, &k, &m, &n, &p, &q, &r, &s, &u, &nCtr, &x, &nBegin;
   Local Field &fldError;
   Local Record &recReportKey, &recReportError, &recParent;
   Local string &strPTRecName, &strPTRecValue, &strKeyColName, &strKeyColValue, &st⇒
rFieldType, &strType;
   Local Rowset &rsParent;
   Local array of string &arrRecHierarchy;
   Local %metadata:RecordDefn:RecordDefn_Manager &mgr = create %metadata:RecordDefn⇒
:RecordDefn_Manager();
   Local %metadata:Key &key;
   Local %metadata:RecordDefn:RecordDefn &defn;
   Local string &strTableName;

   &arrRecHierarchy = CreateArrayRept("", 0);

   &recReportKey = CreateRecord(Record.PSCOMPOBJKEY);
   &recReportError = CreateRecord(Record.PSCOMPOBJERR);

   &i = 1;
   &r = Value(&arrRecName [&arrRecName.Find(&RecError.Name)][2]);
   &q = 1;
   /* Logic to Populate the PTRECNAMEs and PTNUMKEYS */
   For &s = &r To 1 Step - 1
      &strPTRecName = "PTRECNAME" | String(&s);
      If &s = &r Then
         &strPTRecValue = &RecError.Name;
         &recParent = &RecError;
      Else
         &rsParent = &recParent.ParentRow.ParentRowset.ParentRowset;
         &strPTRecValue = &rsParent.DBRecordName;
         &recParent = &rsParent.GetRow(1).GetRecord(@("Record." | &strPTRecValue));
      End-If;
      &recReportKey.GetField(@("Field." | &strPTRecName)).Value = &strPTRecValue;
      &m = &arrRecName.Find(&strPTRecValue);
      &key = create %metadata:Key(Key:Class_Record, &strPTRecValue);
      &defn = &mgr.GetDefn(&key);
      &strTableName = &defn.TableName;
      &recReportKey.GetField(@("Field." | "PTTABLENAME" | String(&s))).Value = &str⇒
TableName;
      &recReportKey.GetField(@("Field." | "PTNUMKEYS" | String(&s))).Value = &arrKe⇒
yFieldNameType [&m].Len;
      &arrRecHierarchy.Push(&strPTRecValue);
   End-For;

   /* Logic to Populate the PTKEYCOLs and PTKEYTYPEs */
   For &u = &arrRecHierarchy.Len To 1 Step - 1
      &strPTRecValue = &arrRecHierarchy [&u];
      &m = &arrRecName.Find(&strPTRecValue);
      For &p = 1 To &arrKeyFieldNameType [&m].Len
         &strKeyColName = "PTKEYCOL" | String(&q);

         &strKeyColValue = &arrKeyFieldNameType [&m][&p][1];
         &strType = &arrKeyFieldNameType [&m][&p][2];
         Evaluate &strType
         When "CHAR"
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
            &strFieldType = "0";
            Break;
         When "LONGCHAR"
            &strFieldType = "1";
            Break;
         When "NUMBER"
            &strFieldType = "2";
            Break;
         When "SIGNEDNUMBER"
            &strFieldType = "3";
            Break;
         When "DATE"
            &strFieldType = "4";
            Break;
         When "TIME"
            &strFieldType = "5";
            Break;
         When "DATETIME"
            &strFieldType = "6";
            Break;
         When "IMAGE"
            &strFieldType = "8";
            Break;
         When "IMAGEREFERENCE"
            &strFieldType = "9";
            Break;
         End-Evaluate;
         &recReportKey.GetField(@("Field." | &strKeyColName)).Value = &strKeyColVal⇒
ue;
         &recReportKey.GetField(@("Field.PTKEYTYPE" | String(&q))).Value = &strFiel⇒
dType;
         &q = &q + 1;
      End-For;
   End-For;

   /* Logic to Populate the PTKEYVALUEs */
   &nCtr = 0;
   For &u = &r To 1 Step - 1
      &nCtr = &nCtr + &recReportKey.GetField(@("Field.PTNUMKEYS" | String(&u))).Val⇒
ue;
   End-For;
   For &x = &r To 1 Step - 1
      &nBegin = &nCtr - (&recReportKey.GetField(@("Field.PTNUMKEYS" | String(&x))).⇒
Value) + 1;
      If &x = &r Then
         &recParent = &RecError;
      Else
         &rsParent = &recParent.ParentRow.ParentRowset.ParentRowset;
         &recParent = &rsParent.GetRow(1).GetRecord(@("Record." | &rsParent.DBRecor⇒
dName));
      End-If;
      For &j = 1 To &recReportKey.GetField(@("Field.PTNUMKEYS" | String(&x))).Value
         If &x = &r Then
            &recReportKey.GetField(@("Field.PTKEYVALUE" | String(&nBegin))).Value =⇒
 &RecError.GetField(@("Field." | &recReportKey.GetField(@("Field.PTKEYCOL" | String⇒
(&nBegin))).Value)).Value;
         Else
            &recReportKey.GetField(@("Field.PTKEYVALUE" | String(&nBegin))).Value =⇒
 &recParent.GetField(@("Field." | &recReportKey.GetField(@("Field.PTKEYCOL" | Strin⇒
g(&nBegin))).Value)).Value;
         End-If;
         &nBegin = &nBegin + 1;
         &nCtr = &nCtr - 1;
      End-For;
   End-For;

   /* Logic to actually populate the PSPRJVALIDERR main fields and then insert into⇒
 the table */
   For &k = 1 To &RecError.FieldCount
      &fldError = &RecError.GetField(&k);
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
      If &fldError.EditError And
            &arrFieldNamesOfDynamicPrompts.Find(&fldError.Name) = 0 Then
         &recReportError.PTADSVALIDTYPE.Value = " ";
         &recReportError.PTPARAMETERVAL1.Value = " ";
         &recReportError.PTPARAMETERVAL2.Value = " ";
         &recReportError.PTPARAMETERVAL3.Value = " ";
         &recReportError.PTPARAMETERVAL4.Value = " ";
         &recReportError.MESSAGE_SET_NBR.Value = 0;
         &recReportError.MESSAGE_NBR.Value = 0;
         &recReportError.MESSAGE_TEXT_254.Value = " ";
         &recReportError.MESSAGE_TEXT_LONG.Value = " ";
         &recReportError.MSG_SEVERITY.Value = " ";
         If &fldError.IsEditTable Then
            &recReportError.PTADSVALIDTYPE.Value = "S";
            &recReportError.PTPARAMETERVAL1.Value = &RecError.Name;
            &recReportError.PTPARAMETERVAL2.Value = &fldError.Name;
            &recReportError.PTPARAMETERVAL3.Value = &fldError.Value;
            &recReportError.PTPARAMETERVAL4.Value = &fldError.PromptTableName;
            &recReportError.MESSAGE_SET_NBR.Value = "257";
            &recReportError.MESSAGE_NBR.Value = "501";
            &recReportError.MESSAGE_TEXT_254.Value = MsgGet(257, 501, "Message Not ⇒
Found", &fldError.Value, &fldError.Name, &RecError.Name, &fldError.PromptTableName)⇒
;
            &recReportError.MESSAGE_TEXT_LONG.Value = MsgGetExplainText(257, 501, "⇒
Message Not Found");
            &recReportError.MSG_SEVERITY.Value = "E";
            &bValidationError = True;
         Else
            If &fldError.IsEditXlat Then
               &recReportError.PTADSVALIDTYPE.Value = "X";
               &recReportError.PTPARAMETERVAL1.Value = &RecError.Name;
               &recReportError.PTPARAMETERVAL2.Value = &fldError.Name;
               &recReportError.PTPARAMETERVAL3.Value = &fldError.Value;
               &recReportError.MESSAGE_SET_NBR.Value = "257";
               &recReportError.MESSAGE_NBR.Value = "503";
               &recReportError.MESSAGE_TEXT_254.Value = MsgGet(257, 503, "Message N⇒
ot Found", &fldError.Value, &fldError.Name, &RecError.Name);
               &recReportError.MESSAGE_TEXT_LONG.Value = MsgGetExplainText(257, 503⇒
, "Message Not Found");
               &recReportError.MSG_SEVERITY.Value = "E";
               &bValidationError = True;
            Else
               If &fldError.IsYesNo Then
                  &recReportError.PTADSVALIDTYPE.Value = "Y";
                  &recReportError.PTPARAMETERVAL1.Value = &RecError.Name;
                  &recReportError.PTPARAMETERVAL2.Value = &fldError.Name;
                  &recReportError.PTPARAMETERVAL3.Value = &fldError.Value;
                  &recReportError.MESSAGE_SET_NBR.Value = "257";
                  &recReportError.MESSAGE_NBR.Value = "504";
                  &recReportError.MESSAGE_TEXT_254.Value = MsgGet(257, 504, "Messag⇒
e Not Found", &fldError.Value, &fldError.Name, &RecError.Name);
                  &recReportError.MESSAGE_TEXT_LONG.Value = MsgGetExplainText(257, ⇒
504, "Message Not Found");
                  &recReportError.MSG_SEVERITY.Value = "E";
                  &bValidationError = True;
               Else
                  If &fldError.IsRequired Then
                     &recReportError.PTADSVALIDTYPE.Value = "R";
                     &recReportError.PTPARAMETERVAL1.Value = &RecError.Name;
                     &recReportError.PTPARAMETERVAL2.Value = &fldError.Name;
                     &recReportError.MESSAGE_SET_NBR.Value = "257";
                     &recReportError.MESSAGE_NBR.Value = "502";
                     &recReportError.MESSAGE_TEXT_254.Value = MsgGet(257, 502, "Mes⇒
sage Not Found", &fldError.Name, &RecError.Name);
                     &recReportError.MESSAGE_TEXT_LONG.Value = MsgGetExplainText(25⇒
7, 502, "Message Not Found");
                     &recReportError.MSG_SEVERITY.Value = "E";
                     &bValidationError = True;
                  Else
                  End-If;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
                End-If;
             End-If;
          End-If;
          %This.ReportErrorModified(&recReportKey, &recReportError);
       End-If;
    End-For;
end-method;
```

Related Links

"Defining Validation" (PeopleTools 8.54: Data Migration Workbench)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Chapter 9

API Repository

Understanding the PeopleSoft API Repository

This section discusses:

- The PeopleSoft API Repository.
- Accessing the repository by using PeopleCode.
- Accessing the repository by using Visual Basic.

The PeopleSoft API Repository

The PeopleSoft API Repository enables PeopleCode and third-party integrators to discover the internally available classes, methods, and properties that are provided by PeopleSoft for integration. The repository is useful to third-party integrators who integrate in a generic fashion: middleware providers, testing tool providers, and automated documentation providers.

The PeopleSoft API Repository is *not*a necessary interface for integrators who integrate at the business-rule level, such as integration with an expense report, and so on. Those integrators should use component interfaces.

The repository describes available PeopleSoft APIs and provides mechanisms to determine the classes that are available in the API, the properties of each class, the methods of a class (along with the required parameters), and information concerning which group a class belongs to (known as a namespace).

The process of determining information about the API is known as *discovery.* Third-party integrators use information found through discovery to drive generic integration tools.

The repository is divided into namespaces. Each namespace contains a collection of related classes. Example namespaces include "PeopleSoft," "ComponentInterface," "Trees," and "BusinessInterlinks".

A *class* defines a related set of methods and properties. Using the repository, you can determine the methods and properties that are available and that can be used on any object returned by a call to the PeopleSoft API. An instance of a class is known as an object.

A *property* is a data item of an object that has both a name and type (string, number, Boolean, and so on are examples of types). Some properties are used for inputting data to a class, some are used for getting data from a class, and some are used for both. Whether a property is used for input or output or both is known as usage.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

A *method* is a function that you can call on an object. Methods have a name and a return type (string, number, Boolean, and so on). Methods also have a collection of arguments that must be set prior to invoking the method. Methods arguments have identical attributes to properties.

Image: Repository class hierarchy

This diagram shows the different types of objects and collections instantiated from the repository:

Example of Accessing the Repository Using PeopleCode

This example gets information for the class ABS_HIST from the Namespace component interface and writes it to the file BC.TXT:

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This is the complete code sample, followed by the flat file. The next section presents steps that explain each line.

```
Local ApiObject &MYSESSION;
Local ApiObject &MYCI;
Local string &OutTEXT;
Local File &MYFILE;

&MYSESSION = %Session;

&MYFILE = GetFile("CI.txt", "A");

&NAMESPACES = &MYSESSION.Repository.Namespaces;
&NAMESPACE = &NAMESPACES.ItemByName("CompIntfc");

&OutTEXT = "Namespace = " | &NAMESPACE.Name;
&MYFILE.WriteLine(&OutTEXT);

&CLASSES = &NAMESPACE.classes;
&CLASS = &CLASSES.ItemByName("ABS_HIST");

&OutTEXT = "  Class: " | &CLASS.Name;
&MYFILE.WriteLine(&OutTEXT);

&OutTEXT = "     Methods";
&MYFILE.WriteLine(&OutTEXT);

&METHODS = &CLASS.methods;
For &K = 0 To &METHODS.Count - 1
   &METHOD = &METHODS.item(&K);
   &OutTEXT = "             " | &METHOD.name | ":  " | &METHOD.Type

   &MYFILE.WriteLine(&OutTEXT);
   &ARGUMENTS = &METHOD.arguments;
   For &M = 0 To &ARGUMENTS.count - 1
      &ARGUMENT = &ARGUMENTS.item(&M);
      &OutTEXT = "           " | &ARGUMENT.name | ": " | &ARGUMENT.type;
      &MYFILE.WriteLine(&OutTEXT);
   End-For;
End-For;

&OutTEXT = "     Properties";
&MYFILE.WriteLine(&OutTEXT);

&PROPERTIES = &CLASS.properties;
For &I = 0 To &PROPERTIES.count - 1
   &PROPERTY = &PROPERTIES.item(&I);
   &OutTEXT = "              " | &PROPERTY.name | ": " | &PROPERTY.type;
   &MYFILE.WriteLine(&OutTEXT);
End-For;
&MYFILE.Close();
```

The previous code produces the following flat file:

```
Namespace = CompIntfc
  Class: ABS_HIST
     Methods
             Get:  Boolean
             Save:  Boolean
             Cancel:  Boolean
             Find:  ABS_HIST
             GetPropertyByName:  Variant
           Name: String
             SetPropertyByName:  Number
           Name: String
           Value: Variant
             GetPropertyInfoByName:  CompIntfcPropertyInfo
           Name: String
     Properties
              EMPLID: String
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
LAST_NAME_SRCH: String
NAME: String
ABSENCE_HIST: ABS_HIST_ABSENCE_HISTCollection
interactiveMode: Boolean
getHistoryItems: Boolean
componentName: String
compIntfcName: String
stopOnFirstError: Boolean
propertyInfoCollection: CompIntfcPropertyInfoCollection
createKeyInfoCollection: CompIntfcPropertyInfoCollection
getKeyInfoCollection: CompIntfcPropertyInfoCollection
findKeyInfoCollection: CompIntfcPropertyInfoCollection
```

The PeopleCode Example Explanation

This procedure goes through the PeopleCode example line by line.

To retrieve information from the API Repository:

1. Get a session object.

   Before you can access the PeopleSoft API Repository, you have to get a session object. The session controls access to PeopleSoft, provides error tracing, enables you to set the runtime environment, and so on.

   ```
   &MYSESSION = %Session;
   ```

2. Open the file.

   As this text will be written to a flat file, the next step is to open the file. If the file is already created, the new text is appended to the end of it. If the file hasn't been created, the GetFile built-in function creates the file.

   ```
   &MYFILE = GetFile("CI.txt", "A");
   ```

3. Get the namespace you want.

   Use the Namespaces property on the repository object to get a collection of available namespaces. We want to discover information about a component interface, so we specify CompIntfc in the ItemByName method to get that namespace. With ItemByName, you must specify a namespace that already exists. You'll receive a runtime error if you specify one that doesn't exist.

   ```
   &NAMESPACES = &MYSESSION.Repository.Namespaces;
   &NAMESPACE = &NAMESPACES.ItemByName("CompIntfc");
   ```

4. Write the text to the file.

   Because all of the information discovered is being written to a file, the next step is to write text to the file. This code writes the string "Namespace", followed by the name of the namespace, to the file.

   ```
   &OutTEXT = "Namespace = " | &NAMESPACE.Name;
   &MYFILE.WriteLine(&OutTEXT);
   ```

5. Get the class that you want and write text to the file.

   Use the Classes property on the Namespace object to get a collection of all the available classes. We want to discover information about the component interface named ABS_HIST, so we specify that using ItemByName. Then we write that information to the file.

   ```
   &CLASSES = &NAMESPACE.classes;
   &CLASS = &CLASSES.ItemByName("ABS_HIST");
   ```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
&OutTEXT = "  Class: " | &CLASS.Name;
&MYFILE.WriteLine(&OutTEXT);
```

6. Get the methods and arguments, and write the information to the file.

   Use the Methods property on the Class object to get a collection of all the available methods. After you get each method and write the information to the file, loop through and find all of the arguments for the method, then write that information to the file.

```
&OutTEXT = "     Methods";
&MYFILE.WriteLine(&OutTEXT);

&METHODS = &CLASS.methods;
For &K = 0 To &METHODS.Count - 1
   &METHOD = &METHODS.item(&K);
   &OutTEXT = "             " | &METHOD.name | ":  " | &METHOD.Type;
   &MYFILE.WriteLine(&OutTEXT);
   &ARGUMENTS = &METHOD.arguments;
   For &M = 0 To &ARGUMENTS.count - 1
      &ARGUMENT = &ARGUMENTS.item(&M);
      &OutTEXT = "           " | &ARGUMENT.name | ": " | &ARGUMENT.type;
      &MYFILE.WriteLine(&OutTEXT);
   End-For;
End-For;
```

7. Get the properties and write the information to the file.

   Use the Properties property on the Class object to get a collection of all the available properties. Write each property, with its type, to the file. At the end of the program, close the file.

```
&OutTEXT = "     Properties";
&MYFILE.WriteLine(&OutTEXT);

&PROPERTIES = &CLASS.properties;
For &I = 0 To &PROPERTIES.count - 1
   &PROPERTY = &PROPERTIES.item(&I);
   &OutTEXT = "              " | &PROPERTY.name | ": " | &PROPERTY.type;
   &MYFILE.WriteLine(&OutTEXT);
End-For;
&MYFILE.Close();
```

Example of Accessing the Repository by Using Visual Basic

This example gets information for the class ABS_HIST from the Namespace component interface.

```
Private Sub Command1_Click()
    '*************************************************************
    '* TacDemo: Example Repository Usage from Visual Basic
    '*
    '* Copyright (c) 1999 PeopleSoft, Inc.  All rights reserved

    '*************************************************************

    ' Declare variables
    Dim oSession As New PeopleSoft_PeopleSoft.Session
    Dim oPSMessages As PSMessageCollection
    Dim oPSMessage As PSMessage

    ' Establish a PeopleSoft Session
    nStatus = oSession.Connect(1, "//PSOFTO070698:9001", "PTDMO", "PTDMO", 0)

    ' Enable error-handler
    On Error GoTo ErrorHandler

    ' Get a Component Interface "shell"
    Dim oNamespaces As NamespaceCollection
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
    Dim oNamespace As Namespace
    Dim oClasses As ClassInfoCollection
    Dim oClass As ClassInfo
    Dim oMethods As MethodInfoCollection
    Dim oMethod As MethodInfo
    Dim oArguments As PropertyInfoCollection
    Dim oArgument As PropertyInfo
    Dim oProperties As PropertyInfoCollection
    Dim oProperty As PropertyInfo

    Set oNamespaces = oSession.Repository.namespaces
    Set oNamespace = oNamespaces.ItemByName("ComponentInterface")

    Dim outText As String

    outText = "Namespace = " & oNamespace.Name & vbNewLine

    Set oClasses = oNamespace.classes
    Set oClass = oClasses.ItemByName("ABS_HIST")

    outText = outText & "   Class: " & oClass.Name & vbNewLine

    outText = outText & "       Methods" & vbNewLine

    Set oMethods = oClass.methods
    For k = 0 To oMethods.Count - 1
        Set oMethod = oMethods.Item(k)        outText = outText & "           "
& oMethod.Name & ":  " & oMethod.Type & vbNewLine
        Set oArguments = oMethod.arguments
        For m = 0 To oArguments.Count - 1
            Set oArgument = oArguments.Item(m)
            outText = outText & "                 "
& oArgument.Name & ":  " & oArgument.Type & vbNewLine
        Next
    Next

    outText = outText & "       Properties" & vbNewLine

    Set oProperties = oClass.properties
    For k = 0 To oProperties.Count - 1
        Set oProperty = oProperties.Item(k)
        outText = outText & "            " & oProperty.Name & ":  "
& oProperty.Type & vbNewLine
    Next

 txtResults = outText

' Leave before we encounter the error handler
Exit Sub

ErrorHandler:
    If Err.Number = 1001 Then                ' PeopleSoft Error
        Set oPSMessages = oSession.PSMessages
        If oPSMessages.Count > 0 Then
            For i = 1 To oPSMessages.Count
               Set oPSMessage = oPSMessages.Item(i)
               MsgBox (oPSMessage.Text)
            Next i
            oPSMessages.DeleteAll
        Else
            MsgBox ("PS Api Error. No additional information
available from Session log")
        End If
    Else                                    ' VB Error
        MsgBox ("VB Error: " & Err.Description)
    End If

End Sub
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Repository Properties

This section discusses the Repository properties in alphabetical order.

Bindings

Description

The Bindings property returns a reference to a Bindings collection.

This property is read-only.

Namespaces

Description

The Namespaces property returns a reference to a Namespaces collection.

This property is read-only.

Bindings Collection Properties

This section discusses the Bindings collection properties in alphabetical order.

Count

Description

This property returns the number of Bindings Properties objects in the Bindings collection object.

Note: All repository counts begin at zero, not one.

This property is read-only.

Example

```
&COUNT = &BINDINGS.Count;
```

Related Links

Bindings Properties

Bindings Collection Methods

This section discusses the Bindings collection methods in alphabetical order.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Item

Syntax

Item(*number*)

Description

The Item method returns a Bindings object that exists at the number position in the Bindings collection executing the method

Parameters

number	Specify the position number in the collection of the Bindings object that you want returned.

Returns

A reference to a Bindings object or NULL.

Example

```
For &N = 0 to &BINDINGS.Count - 1
   &BINDING = &BINDINGS.Item(&N);
   /* do processing */
End-For;
```

Bindings Properties

This section discusses the Bindings properties in alphabetical order.

Name

Description

This property returns the name of the object as a string.

This property is read-only.

Bindings Methods

This section discusses the Bindings methods in alphabetical order.

Generate

Syntax

Generate()

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

This method is a reserved internal function and shouldn't be used at this time.

Namespaces Collection Properties

This section discusses the Namespaces collection properties in alphabetical order.

Count

Description

This property returns the number of Namespaces Properties objects in the Namespaces collection object.

Note: All repository counts begin at zero, not one.

This property is read-only.

Example

```
&COUNT = &NameC.Count;
```

Related Links

Namespaces Properties

Namespaces Collection Methods

This section discusses the Namespaces collection methods in alphabetical order.

Item

Syntax

Item(*number*)

Description

The Item method returns a Namespaces object that exists at the *number* position in the Namespaces collection executing the method.

Parameters

number	Specify the position number in the collection of the Namespaces object that you want returned.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

A reference to a Namespaces object or NULL.

Example

```
For &N = 0 to &NAMESPACES.Count - 1
   &NAMESPACE = &NAMESPACES.Item(&N);
   /* do processing */
End-For;
```

ItemByName

Syntax

ItemByName(*name*)

Description

The ItemByName method returns the item specified by *name. Name* is not case-sensitive.

Parameters

name	Specify the name of the Namespaces object that you want returned. This parameter takes a string value.

Returns

A reference to a Namespaces object or NULL.

Example

```
&NAMESPACE = &NAMESPACES.ItemByName("BusinessComponent");
```

Namespaces Properties

This section discusses the Namespaces properties in alphabetical order.

Classes

Description

This property returns a reference to a ClassInfo collection object.

This property is read-only.

Example

```
&CLASSC = &NAME.Classes;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

ClassInfo Collection Properties

Name

Description

This property returns the name of the object as a string.

This property is read-only.

Namespaces Methods

This section discusses the Namespaces methods in alphabetical order.

CreateObject

Syntax

CreateObject(*classname*)

Description

This method is a reserved internal function and shouldn't be used at this time.

ClassInfo Collection Properties

This section discusses the ClassInfo collection properties in alphabetical order.

Count

Description

This property returns the number of ClassInfo Properties objects in the ClassInfo collection object.

Note: All repository counts begin at zero, not one.

This property is read-only.

Example

```
&COUNT = &InfoC.Count;
```

Related Links

ClassInfo Properties

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ClassInfo Collection Methods

This section discusses the ClassInfo collection methods in alphabetical order.

Item

Syntax

Item(*number*)

Description

The Item method returns a ClassInfo object that exists at the *number* position in the ClassInfo collection executing the method.

Parameters

number Specify the position number in the collection of the ClassInfo object that you want returned.

Returns

A reference to a ClassInfo object or NULL.

Example

```
For &N = 0 to &CLASSES.Count - 1
   &CLASS = &CLASSES.Item(&N);
   /* do processing */
End-For;
```

ItemByName

Syntax

ItemByName(*name*)

Description

The ItemByName method returns the item specified by *name*. *Name* is not case-sensitive.

Parameters

name Specify the name of the ClassInfo object that you want returned. This parameter takes a string value.

Returns

A reference to a ClassInfo object or NULL.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

```
&CLASS = &CLASSES.ItemByName("ABS_HIST");
```

ClassInfo Properties

This section discusses the ClassInfo properties in alphabetical order.

Documentation

Description

This property doesn't actually return all the documentation for the class, just a brief description of the class as a string.

This property is read-only.

Methods

Description

This property returns a reference to a MethodInfo collection object.

This property is read-only.

Related Links

MethodInfo Collection Methods

Name

Description

This property returns the name of the object as a string.

This property is read-only.

Properties

Description

This property returns a reference to a PropertyInfo collection object.

This property is read-only.

Related Links

PropertyInfo Collection Methods

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

MethodInfo Collection Properties

This section discusses the MethodInfo collection properties in alphabetical order.

Count

Description

This property returns the number of MethodInfo Properties objects in the MethodInfo collection object.

Note: All repository counts begin at zero, not one.

This property is read-only.

Example

```
&COUNT = &MethC.Count;
```

Related Links

MethodInfo Properties

MethodInfo Collection Methods

This section discusses the MethodInfo collection methods in alphabetical order.

Item

Syntax

Item(*number*)

Description

The Item method returns a MethodInfo object that exists at the *number* position in the MethodInfo collection executing the method.

Parameters

number	Specify the position number in the collection of the MethodInfo object that you want returned.

Returns

A reference to a MethodInfo object or NULL.

Example

```
For &K = 0 To &METHODS.Count - 1
```


Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
   &METHOD = &METHODS.item(&K);
   &OutTEXT = "             " | &METHOD.name | ":  " | &METHOD.Type;
   &MYFILE.WriteLine(&OutTEXT);
End-For;
```

ItemByName

Syntax

ItemByName(*name*)

Description

The ItemByName method returns the item specified by *name*. *Name* is not case-sensitive.

Parameters

name	Specify the name of the MethodInfo object that you want returned. This parameter takes a string value.

Returns

A reference to a MethodInfo object or NULL.

Example

```
&METHOD = &METHODS.ItemByName("Save");
```

MethodInfo Properties

This section discusses the MethodInfo properties in alphabetical order.

Arguments

Description

This property returns a reference to a PropertyInfo collection object.

This property is read-only.

Related Links

PropertyInfo Collection Methods

Documentation

Description

This property doesn’t actually return all the documentation for the class, just a brief description of the class, as a string.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-only.

Name

Description

This property returns the name of the object as a string.

This property is read-only.

Type

Description

This property returns the type of the method. Values include:

- Bool (Boolean).
- Number.
- Float.
- String.
- Variant.
- Blob (binary large object).
- Any API class name.

This property is read-only.

PropertyInfo Collection Properties

This section discusses the PropertyInfo collection properties in alphabetical order.

Count

Description

This property returns the number of PropertyInfo Properties objects in the PropertyInfo collection object.

Note: All repository counts begin at zero, not one.

This property is read-only.

Example

```
&COUNT = &PropC.Count;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

PropertyInfo Properties

PropertyInfo Collection Methods

This section discusses the PropertyInfo collection methods in alphabetical order.

Item

Syntax

Item(*number*)

Description

The Item method returns a PropertyInfo object that exists at the *number* position in the PropertyInfo collection executing the method.

Parameters

number	Specify the position number in the collection of the PropertyInfo object that you want returned.

Returns

A reference to a PropertyInfo object or NULL.

Example

```
For &K = 0 To &PROPERTIES.Count - 1
   &PROPERTY = &PROPERTIES.item(&K);
   &OutTEXT = "             " | &PROPERTY.name | ":  " | &PROPERTY.Type;
   &MYFILE.WriteLine(&OutTEXT);
End-For;
```

ItemByName

Syntax

ItemByName(*name*)

Description

The ItemByName method returns the item specified by *name. Name* is not case-sensitive.

Parameters

name	Specify the name of the PropertyInfo object that you want returned. This parameter takes a string value.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

A reference to a PropertyInfo object or NULL.

Example

```
&PROPERTY = &PROPERTIES.ItemByName(&ldquo;GetHistoryItems&rdquo;);
```

PropertyInfo Properties

This section discusses the PropertyInfo properties in alphabetical order.

Documentation

Description

This property doesn't actually return all the documentation for the class, just a brief description of the class, as a string. This property is read-only.

Name

Description

This property returns the name of the object as a string.

This property is read-only.

Type

Description

This property returns the data type. Values are:

- Bool (Boolean).
- Number.
- Float.
- String.
- Variant.
- Blob (binary large object).
- Any API class name.

This property is read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Usage

Description

This property returns a number that describes in which direction the specified property (or argument) can be passed. The following table describes the valid values.

Value	*Description*
0	Can be passed into PeopleSoft API.
1	Can be passed out of PeopleSoft API.
2	Can be passed either into or out of PeopleSoft API.

This property is read-only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Chapter 10

Array Class

Understanding Arrays

An array is a collection of data storage locations, each of which holds the same type of data. Each storage location is called an element of the array. When you create an array, you don't have to declare the size of the array at declaration time. Arrays grow and shrink dynamically as you add (or remove) data. The size of an array is limited by the available memory. You can't access past the end of an array, but you can assign outside the existing boundaries, thereby growing the array.

Creating Arrays

Arrays are declared by using the Array type name, optionally followed by "of" and the type of the elements. If the element type is omitted, it is set by default to ANY.

```
Local Array of Number &MYARRAY;
Local Array &ARRAYANY;
```

Arrays can be composed of any valid PeopleCode data type, such as string, record, number, date, and so on.

PeopleSoft recommends you declare every object you use in PeopleCode. This provides some syntax checking when you save PeopleCode. It's better to find out that you misspelled the name of a method or property at design time, rather than at runtime!

Arrays can be declared as Local, Global, or Component, just like any other PeopleTools object.

Arrays can be created with one or more dimensions. An array with more than one dimension is called an array of arrays. The *dimension* of an array is the number of Array type names in the declaration. This is also called the *depth* of an array. The maximum depth of a PeopleCode array is 15 dimensions.

In the following example, &MYARRAY has three dimensions, and &MYA2 has two dimensions.

```
Local Array of Array of Array of Number &MYARRAY;
Local Array of Array &MYA2;
```

An array must always have a consistent dimension. This means that in a one-dimensional array *none* of the elements can be an array, in a two-dimensional array *all* of the elements must be one-dimensional arrays, and so on.

After you declare an array, use one of the built-in array functions to instantiate it and return an object reference to it. For example, the following creates an array containing one element of type &TEMP, whatever data type &TEMP may be.

```
&MYARRAY = CreateArray(&TEMP);
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Or you can use the CreateArrayRept function to instantiate an array. The Rept stands for *repeat*. CreateArrayRept creates an array that contains the number of copies you specify of a particular value. The following code creates an array with three copies of the string &MYSTRING. This does *not* create a three-dimensional array, but rather creates an array that's already populated with three elements of data (`Len = 3`), each of which contain the same string (&MYSTRING).

```
&MYARRAY = CreateArrayRept(&MYSTRING, 3);
```

An array *object* can be assigned to an array *variable*. Array objects can be passed from and returned to any kind of PeopleCode function:

```
ANewFunc (&myarray);
MyFunc (&myarray);
&MyArray = YourFunc("something");
```

For example, the ReturnToServer function returns an array of nodes to which a message can be published.

Elements in an array are specified by providing a bracketed subscript after the array object reference:

```
&MyArray[1] = 123;
&temp = &memory[1][2][3];
&temp = &memory[1, 2, 3]; /* Same as preceding line.  */
MyFunc(&MyArray[7]);
MyFunc(10)[15] = "a string";
```

To access data in a two-dimensional array, you must specify both indexes. The following accesses the second item in the first subarray:

```
&VALUE  = &DOUBLE[1][2];
```

You receive an error if you use a zero or negative index in an array. Accessing an array element whose index is larger than the last array element is also an error, but storing to such an index extends the array. Any intervening elements between the former last element and the new last element are assigned a value based on the element type of the array. This is the same value as an unassigned variable of that type.

An array is an object, which means that assignments to an array are the same as for any other object. An array variable can be assigned the distinguished value NULL, which indicates the absence of any array value.

Array variables are supported for all scopes. This means that you can have local, global, and Component array variables.

Related Links

"ReturnToServer" (PeopleTools 8.54: PeopleCode Language Reference)

"Assigning Objects" (PeopleTools 8.54: PeopleCode Developer's Guide)

Populating an Array

There are several ways to populate an array. The example code following each of these methods creates the exact same array, with the same elements:

- Use CreateArray when you initially create the array:

  ```
  Local Array of Number &MyArray;
  ```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
&MyArray = CreateArray(100, 200, 300);
```

- Assign values to the elements of the array:

```
Local Array of Any &MYARRAY;

&MYARRAY = CreateArray();
&MYARRAY[1] = 100;
&MYARRAY[2] = 200;
&MYARRAY[3] = 300;
```

Note: Using CreateArray without any parameters creates an array of Any.

- Use the Push method to add items to the end of the array:

```
Local Array of Number &MYARRAY;
Local Number &MYNUM;

&MYARRAY = CreateArrayRept(&MYNUM, 0);
/* this creates an empty array of number */
&MYARRAY.Push(100);
&MYARRAY.Push(200);
&MYARRAY.Push(300);
```

- Use the Unshift method to add items to the beginning of the array:

```
Local Array of Number &MYARRAY;
Local Number &MYNUM;

&MYARRAY = CreateArrayRept(&MYNUM, 0);
/* this creates an empty array of number */
&MYARRAY.Unshift(300);
&MYARRAY.Unshift(200);
&MYARRAY.Unshift(100);
```

You can also use CreateArrayRept (repeat) when you initially create the array. The following example creates an array with three elements: all three elements have the same data, that is, 100:

```
Local Array of Number &MYARRAY;

&MYARRAY = CreateArrayRept(100, 3);
```

Removing Items From an Array

You can remove elements from either the start or the end of the array:

- Use the POP method to select and remove an element from the end of an array

```
Local Array of Number &MYARRAY;

&MYARRAY = CreateArray();
&MYARRAY[1] = 100;
&MYARRAY[2] = 200;
&MYARRAY[3] = 300;

&ANSWER = &MYARRAY.Pop();
```

&ANSWER will equal 300.

- Use the SHIFT method to select and remove an element from the beginning of an array

```
Local Array of Number &MYARRAY;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
&MYARRAY = CreateArray();
&MYARRAY[1] = 100;
&MYARRAY[2] = 200;
&MYARRAY[3] = 300;

&ANSWER = &MYARRAY.Shift();
```

&ANSWER equals 100.

Creating Empty Arrays

If you create an array using CreateArray of any data type other than ANY, the new array is *not* empty: it contains one item. If you need to create a completely empty array that contains 0 elements, use one of the following:

```
Local Array of Number &AN;
Local Array of String &AS;
Local Array of Record &AR;
Local Array of Array of Number &AAN;
Local Record &REC;

&AN = CreateArrayRept(0,0); /* creates an empty array of number */
&AS = CreateArrayRept("", 0); /* creates an empty array of string */
&AR = CreateArrayRept(&REC, 0); /*create empty array of records */
&AAN = CreateArrayRept(&AN, 0); /*creates empty array of array of number */
&BOTH = CreateArray(CreateArrayRept("", 0), CreateArrayRept("", 0)); /* creates an ⇒
empty array of array of string */
```

Creating and Populating Multi-Dimensional Arrays

You can create arrays with more than one dimension. Each element in a multi-dimensional array is itself an array. For example, a two-dimensional array is really an array of arrays. Each subarray has to be created and populated as an array.

Each subarray in a multi-dimensional array must be of the same type. For example, you can't create a two dimensional array that has one subarray of type string and a second subarray of type number.

The following example creates an array of array of string, then reads two files, one into each "column" of the array. The CreateArrayRept function call creates an empty array of string (that is, the Len property is 0) but with two dimensions (that is, with two subarrays, Dimension is 2). The first Push method adds elements into the first subarray, so at the end of that WHILE loop in the example, &BOTH has Len larger than 0. The other Push methods add elements to the second subarray.

```
Local array of array of string &BOTH;
Local File &MYFILE;
Local string &HOLDER;

/* Create empty &BOTH array */
&BOTH = CreateArrayRept(CreateArrayRept("", 0), 0);

/* Read first file into first column */

&MYFILE = GetFile("names.txt", "R");
While &MYFILE.ReadLine(&HOLDER);
   &BOTH.Push(&HOLDER);
End-While;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
/* read second file into second column */

&MYFILE = GetFile("numbers.txt", "R");
&LINENO = 1;
While &MYFILE.ReadLine(&HOLDER);
   If &LINENO > &BOTH.Len Then
      /* more number lines than names, use a null name */
      &BOTH.Push(CreateArray("", &HOLDER));
   Else
      &BOTH[&LINENO].Push(&HOLDER);
   End-If;
   &LINENO = &LINENO + 1;
End-While;

/* if more names than numbers, add null numbers */
for &LINENO = &LINENO to &BOTH.Len
      &BOTH[&LINENO].Push("");
End-For;
```

Image: &BOTH array expanded in PeopleCode debugger at program end

This example illustrates the fields and controls on the &BOTH array expanded in PeopleCode debugger at program end. You can find definitions for the fields and controls later on this page.

Local Name	Local Value
⊟ &BOTH	Array
Dimension	2
Len	3
⊟ [1]	
Dimension	1
Len	2
[1]	Pete
[2]	100
⊟ [2]	
Dimension	1
Len	2
[1]	Sue
[2]	200
⊟ [3]	
Dimension	1
Len	2
[1]	Laszlo
[2]	400
⊞ &MYFILE	File
&HOLDER	400
&LINENO	4

The following code reads from a two-dimensional array and writes the data from the each subarray into a separate file.

```
Local File &MYFILE1, &MYFILE2;
Local string &STRING1, &STRING2;
Local array of array of string &BOTH;
.
/* code to load data into array would be here */
.
/* open files to be written to */

&MYFILE1 = GetFile("names.txt", "A");
&MYFILE2 = GetFile("numbers.txt", "A");

/* loop through array and write to files */

For &I = 1 To &BOTH.Len
   &J = 1;
   &STRING1 = &BOTH[&I][&J];
   &MYFILE1.writeline(&STRING1);
   &J = &J + 1;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
   &STRING2 = &BOTH[&I][&J];
   &MYFILE2.writeline(&STRING2);
End-For;

&MYFILE1.Close();
&MYFILE2.Close();
```

The following example populates a multi-dimensional string array using SQL. This could be used for reading small tables.

```
Component array of array of string &ArrRunStatus;

&ArrRunStatus = CreateArrayRept(CreateArrayRept("", 0), 0);
&ArrRunStatusDescr = CreateArrayRept("", 0);

&SQL = CreateSQL("SELECT FIELDVALUE, XLATSHORTNAME FROM XLATTABLE WHERE FIELDNAME =⇒
 'RUNSTATUS'");

&LineNo = 1;
While &SQL.Fetch(&FieldValue, &XlatShortName)
      &ArrRunStatus.Push(&FieldValue);
      &ArrRunStatus[&LineNo].Push(&XlatShortName);
      &LineNo = &LineNo + 1;
End-While;
```

To search for a particular element in this array, use the following:

```
&iIndex = &ArrRunStatus.Find(&RunStatusToGet);

&RunStatusDescr = &ArrRunStatus[&iIndex][2];
```

The following example shows how to create a two-dimension array using CreateArrayRept and Push. In addition, it shows how to randomly assigns values to the cells in a two-dimension array.

```
Local array of array of string &ValueArray;

&Dim1 = 10;
&Dim2 = 5;
&ValueArray = CreateArrayRept(CreateArrayRept("", 0), 0);
For &I = 1 To &Dim1
   &ValueArray.Push(CreateArrayRept("", &Dim2));
End-For;

&ValueArray[1][1] = "V11";
&ValueArray[2][1] = "V21";

WinMessage("&ValueArray[1][1] = " | &ValueArray[1][1] | " " | "&ValueArray[2][1] = ⇒
" | &ValueArray[2][1], 0);
```

Using Flattening and Promotion

Several of the functions and methods that support arrays in PeopleCode use flattening and promotion to convert their operands to the correct dimension for the array.

Flattening converts an array into its elements. For example, the CreateArray built-in function constructs an array from its parameters. If it is constructing a one-dimensional array and is given an array as a parameter, then it flattens that array into its elements and adds each of them to the array that it is building, rather than adding a reference to the array (which would be a dimension error) or reporting an error.

Likewise, for functions that operate on multiple-dimension arrays, if they are given a non-array parameter, they use *promotion* to convert it into an array of suitable dimension. For example, the Push

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

method appends elements onto the end of an array. If it is operating with a two-dimensional array of Array of Number, and is given a numeric argument, it will convert the argument into a one-dimensional array of Number with the given number as its only element, and then append that to the two-dimensional array.

An array value can only be assigned to an array variable if the value and variable have both the same dimension and base type. This means you cannot assign an Array of Any to an Array of Number variable or vice-versa. You can, however, assign an Array of Number to an Any variable, as long as you do not break the rule that the base element of an array cannot be an array reference value.

Declaring Array Objects

Arrays are declared by using the Array type name, optionally followed by "of" and the type of the elements. If the element type is omitted, it is set by default to ANY.

```
Local Array of Number &MYARRAY;
Local Array &ARRAYANY;
```

Arrays can be composed of any valid PeopleCode data type, such as string, record, number, date, and so on.

Understanding the Scope of an Array Object

An array object can only be instantiated from PeopleCode. This object can be used anywhere you have PeopleCode, that is, in an application class, Component Interface PeopleCode, record field PeopleCode, and so on.

Array Class Built-in Functions

"CreateArray" (PeopleTools 8.54: PeopleCode Language Reference)

"CreateArrayAny" (PeopleTools 8.54: PeopleCode Language Reference)

"CreateArrayRept" (PeopleTools 8.54: PeopleCode Language Reference)

"Split" (PeopleTools 8.54: PeopleCode Language Reference)

Array Class Methods

In this section, we discuss the array class methods.

Clone

Syntax

Clone()

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

The Clone method returns a reference to a new array, which is a copy of the given array. It copies all levels of the array, meaning, if the array contains elements which are themselves arrays (actually references to arrays), then the copy contains references to copies of the subarrays. Furthermore, if the array contains elements that are references to the same subarray, then the copy contains references to *different* subarrays (which of course have the same value).

Parameters

None. The array object that the clone method is executed against is the array to be cloned. Assigning the result of this method assigns a reference to the new array.

Returns

An array object copied from the original.

Example

In the following example, &AAN2 contains the three elements like &AAN, but they are distinct arrays. The last line changes only &AAN2[1][1], *not* &AAN[1][1].

```
Local Array of Array of String &AAN, &AAN2;

&AAN = CreateArray(CreateArray("A", "B"), CreateArray("C", "D"), "E");
&AAN2 = &AAN.Clone();
&AAN2[1][1] = "Z";
```

After the following example, &AAN contains three elements: two references to the subarray that was &AAN[2] (with elements C and D), and a reference to a subarray with element E.

```
&AAN[1] = &AAN[2];
```

After the following example, &AAN2 contains three elements: references to two different subarrays both with elements C and D, and a subarray with element E.

```
&AAN2 = &AAN.Clone();
```

Related Links

Subarray

Find

Syntax

Find(*value*)

Description

For a one-dimensional array, the Find method returns the lowest index of an element in the array that is equal to the given value. If the value is not found in the array, it returns zero.

For a two-dimensional array, the Find method returns the lowest index of a subarray which has its first element equal to the given value. If such a subarray is not found in the array, it returns zero.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Note: This method works with arrays that have only one or two dimensions. You receive a runtime error if you try to use this method with an array that has more than two dimensions.

Parameters

value The string or subarray to search for.

Returns

An index of an element or zero.

Example

Given an array &AS containing (A, B, C, D, E), the following code sets &IND to the index of D, that is, &IND has the value 4:

```
Local array of string &AS;

&AS = CreateArrayRept("", 0);
&AS.Push("A");
&AS.Push("B");
&AS.Push("C");
&AS.Push("D");
&AS.Push("E");
&IND = &AS.Find("D");
```

Given an array of array of string &AABYNAME containing (("John", "July"), ("Jane", "June"), ("Norm", "November"), the following code sets &IND to the index of the subarray starting with "Jane", that is, &IND has the value 2:

```
&NAME = "Jane";
&IND = &AABYNAME.Find(&NAME);
```

Related Links

Replace
Substitute

Get

Syntax

Get(*index*)

Description

Use the Get method to return the *index* element of an array. This method is used with the Java PeopleCode functions, instead of using subscripts (which aren't available in Java.)

Using this method is the same as using a subscript to return an item of an array. In the following example, the two lines of code are identical:

```
&Value = &MyArray[8];

&value = &MyArray.Get(8);
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

index	The array element to be accessed.

Returns

An element in an array.

Related Links

Set
Understanding Application Classes

Join

Syntax

```
Join([separator [, arraystart, arrayend  [,stringsizehint]]])
```

Description

The Join method *converts* the array that is executing the method into a string by converting each element into a string and *joining* these strings together, separated by *separator*.

Note: Join does *not* join two arrays together.

Each array or subarray to be joined is preceded by the string given by *arraystart* and followed by the string given by *arrayend*. If the given array is multi-dimensional, then (logically) each subarray is first joined, then the resulting strings are joined together.

Parameters

separator	Specifies what the elements in the resulting string should be separated with in the resulting string. *Separator* is set by default to a comma (",").
arraystart	Specifies what each array or subarray to be joined should be preceded with in the resulting string. *arraystart* is set by default to a left parenthesis ("(").
arrayend	Specifies what each array or subarray to be joined should be followed by in the resulting string. a*rrayend* is set by default to a right parenthesis (")").
stringsizehint	Specify a hint to the Join method about the resulting size of the string. This can improve performance if your application is concatenating a large number of string. See the Example section below.

Returns

A string containing the converted elements of the array.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

The following example:

```
Local array of array of number &AAN;

&AAN = CreateArray(CreateArray(1, 2), CreateArray(3, 4), 5);
&STR = &AAN.Join(", ");
```

produces in &STR the string:

```
((1, 2), (3, 4), 5)
```

The following example makes use of the *stringsizehint* parameter. The following application class passes the resulting string size hint in the Value property.

```
class StringBuffer
   method StringBuffer(&InitialValue As string, &MaxSize As integer);
   method Append(&New As string);
   method Reset();
   property string Value get set;
   property integer Length readonly;
private
   instance array of string &Pieces;
   instance integer &MaxLength;
end-class;

method StringBuffer
   /+ &InitialValue as String, +/
   /+ &MaxSize as Integer +/
   &Pieces = CreateArray(&InitialValue);
   &MaxLength = &MaxSize;
   &Length = 0;
end-method;

method Reset
   &Pieces = CreateArrayRept("", 0);
   &Length = 0;
end-method;

method Append
   /+ &New as String +/
   Local integer &TempLength = &Length + Len(&New);
   If &Length > &MaxLength Then
      throw CreateException(0, 0, "Maximum size of StringBuffer exceeded(" | &MaxLe⇒
ngth | ")");
   End-If;
   &Length = &TempLength;
   &Pieces.Push(&New);
end-method;

get Value
   /+ Returns String +/
   Local string &Temp = &Pieces.Join("", "", "", &Length);
   /* collapse array now */
   &Pieces = CreateArrayRept("", 0);
   &Pieces.Push(&Temp); /* start out with this combo string */
   Return &Temp;
end-get;

set Value
   /+ &NewValue as String +/
   /* Ditch our current value */
   %This.Reset();
   &Pieces.Push(&NewValue);
end-set;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The following code concatenates strings.

```
While &file.ReadLine(&line)
   &S.Append(&line);
   &S.Append(&separator);
```

Related Links

"Split" (PeopleTools 8.54: PeopleCode Language Reference)

Next

Syntax

Next(&*index*)

Description

The Next method increments the given index variable. It returns true if and only if the resulting index variable refers to an existing element of the array. Next is typically used in the condition of a WHILE clause to process a series of array elements up to the end of the array.

&index must be a variable of type integer, or of type Any initialized to an integer, as Next attempts to update it.

If you want to start from the first element of the array, start Next with an index variable with the value zero. The first thing Next does is to increment the value by one.

Parameters

&index	The array element where processing should start. *&index* must be a variable of type integer, or of type Any initialized to an integer, as Next attempts to update it.

Returns

True if the resulting index refers to an existing element of the array, False otherwise.

Example

Next can be used in a While loop to iterate through an array in the following manner:

```
&INDEX = 0;
While &A.Next(&INDEX)
   /* Process &A[&INDEX] */
End-While;
```

In the following code example, &BOTH is a two-dimensional array. This example writes the data from each subarray in &BOTH into a different file.

```
&I = 0;
While &BOTH.Next(&I)
   &J = 1;
   &STRING1 = &BOTH[&I][&J];
   &MYFILE1.writeline(&STRING1);
   &J = &J + 1;
   &STRING2 = &BOTH[&I][&J];
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
   &MYFILE2.writeline(&STRING2);
End-While;
```

Related Links

Len

Pop

Syntax

Pop()

Description

The Pop method removes the last element from the array and returns its value.

Parameters

None.

Returns

The value of the last element of the array. If the last element is a subarray, the subarray is returned.

Example

The Pop method can be used with the Push method to use an array as a stack. To put values on the end of the array, use Push. To take the values back off the end of the array, use Pop.

Suppose we have a two-dimensional array &SUBPARTS which gives the subparts of each part of some assemblies. Each row (subarray) of &SUBPARTS starts with the name of the part, and then has the names of the subparts. Assuming there are no "loops" in this data, the following code puts all the subparts, subsubparts, and so on, of the part given by &PNAME into the array &ALLSUBPARTS, in "depth first order" (that is, subpart1, subparts of subpart1, …, subpart2, subparts of subpart2, …). We stack the indexes into &SUBPARTS when we want to go down to the subsubparts of the current subpart.

```
Local array of array of string &SUBPARTS;
Local array of string &ALLSUBPARTS;
Local array of array of number &STACK;
Local array of number &CUR;
Local string &SUBNAME;

/* Set the ALLSUBPARTS array to an empty array of string.  */

&ALLSUBPARTS = CreateArrayRept("dummy", 0);

/* Start with the part name.  */

&STACK = CreateArray(CreateArray(&SUBPARTS.Find(&PNAME), 2));
While &STACK.Len > 0
   &CUR = &STACK.Pop();
   If &CUR[1] <> 0 And
         &CUR[2] <= &SUBPARTS[&CUR[1]].Len Then

      /* There is a subpart here.  Add it.  */
      &SUBNAME = &SUBPARTS[&CUR[1], &CUR[2]];
      &ALLSUBPARTS.Push(&SUBNAME);

      /* Tour its fellow subparts later.  */
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
      &STACK.Push(CreateArray(&CUR[1], &CUR[2] + 1));

      /* Now tour its subsubparts.  */
      &STACK.Push(CreateArray(&SUBPARTS.Find(&SUBNAME), 2));

   End-If;
End-While;
```

Related Links

Push

Replace

Shift

Unshift

Push

Syntax

Push(*paramlist*)

Where *paramlist* is an arbitrary-length list of values in the form:

value1 [, *value2*] ...

Description

The Push method adds the values in *paramlist* onto the end of the array executing the method. If a value is not the correct dimension, it is flattened or promoted to the correct dimension first, then the resulting values are added to the end of the array.

Considerations Using Arrays With Object References

This method only adds an element to the end of an array. It does not clone or otherwise deep-copy the parameters. For example, if you are adding a reference to an object, Push just adds a reference to the object at the end of the array. This is similar to an assignment. It is *not* making a copy of the object. The following code snippet only puts a reference to the same record onto the end of the array.

```
While &SQL.Fetch(&Rec);
&MYARRAY.Push(&Rec);
...
End-While;
```

Even though the array is growing, all the elements point to the same record. You have only as many standalone record objects as you create. The following code snippet creates new standalone records, so each element in the array points to a new object:

```
local Record &FetchedRec = CreateRecord(Record.PERSONAL_DATA);

While &SQL.Fetch(&FetchedRec)
     &MYARRAY.Push(&FetchedRec);
     &FetchedRec = CreateRecord(Record.PERSONAL_DATA);
End-While;
```

Parameters

paramlist An arbitrary-length list of values, separated by commas.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

None.

Example

The following example loads an array with data from a database table.

```
Local array of record &MYARRAY;
Local SQL &SQL;

&I = 1;
&SQL = CreateSQL("Select(:1) from %Table(:1) where EMPLID like &lsquo;8%&rsquo;", &⇒
REC);
While &SQL.Fetch(&REC);
   &MYARRAY.Push(CreateRecord(RECORD.PERSONAL_DATA));
   &I = &I + 1;
   &REC.CopyFieldsTo(&MYARRAY[&I]);
End-While;
```

Related Links

Pop
Replace
Shift
Unshift
Using Flattening and Promotion
"Assigning Objects" (PeopleTools 8.54: PeopleCode Developer's Guide)

Replace

Syntax

Replace(*start*, *length*[, *paramlist*])

Where *paramlist* is an arbitrary-length list of values in the form:

value1 [, *value2*] ...

Description

Replace replaces the *length* elements starting at *start* with the given values, if any. If *length* is zero, the insertion takes place *before* the element indicated by *start*. Otherwise, the replacement starts with *start* and continues up to and including *length*, replacing the existing values with *paramlist*.

If a negative number is used for *start*, it indicates the starting position relative to the last element in the array, such that −1 indicates the position just *after* the end of the array. To insert at the end of the array (equivalent to the Push method), use a *start* of −1 and a *length* of 0.

If a negative number is used for *length*, it indicates a length measuring downward to lower indexes. Both flattening and promotion can be applied to change the dimension of the supplied parameters to match the elements of the given array.

Similar to how the built-in function Replace is used to update a string, the Replace method is a general way to update an array, and can cause the array to grow or shrink.

See Using Flattening and Promotion.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Using Replace to Remove an Element

You can use the Replace method to remove an element from an array. Just specify the item you want replaces, with *length* equal to one.

The following example removes the item from &Index:

```
&Array.Replace(&Index, 1);
```

Parameters

start	Specifies where to start replacing the given elements in the array. If a negative number is used for *start*, it indicates the starting position relative to the last element in the array.
length	Specifies the number of elements in the array to be replaced.
paramlist	Specifies values to be used to replace existing values in the array. This parameter is optional.

Returns

None.

Example

For example, given the following array:

```
Local array of string &AS;

&AS = CreateArray("AA", "BB", "CC");
```

After executing the next code, the array &AN will contain four elements, ZZ, YY, BB, CC:

```
&AS.Replace(1, 1, "ZZ", "YY");
```

After executing the next code, the array &AN will contain three elements, ZZ, MM, CC:

```
&AS.Replace(2, 2, "MM");
```

After executing the next code, the array &AN will contain three elements, ZZ, OO, CC.

```
&AS.Replace( - 2, - 1, "OO");
```

Image: &AS expanded in PeopleCode debugger

The following image is an example of &AS expanded in PeopleCode debugger.

Local Name	Local Value
⊟ &AS	Array
└Dimension	1
└Len	3
└[1]	ZZ
└[2]	OO
└[3]	CC

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

Substitute

Find

Reverse

Syntax

Reverse()

Description

The Reverse method reverses the order of the elements in the array.

If the array is composed of subarrays, the Reverse method reverses only the elements in the super-array, it doesn't reverse all the elements in the subarrays. For example, the following:

```
&AN = CreateArray(CreateArray(1, 2), CreateArray(3, 4), CreateArray(5, 6)).reverse(⇒
);
```

results in &AN containing:

```
((5,6), (3,4), (1,2)
```

Parameters

None.

Returns

None.

Example

Suppose you had the following array.

```
Local Array of Sting &AS;

&AS = CreateArray("R", "O", "S", "E");
```

If you executed the Reverse method on this array, the elements would be ESOR.

Related Links

Sort

Set

Syntax

Set(*index*)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the Set method to set the value of the *index* element of an array. This method is used with the Java PeopleCode functions, instead of using subscripts (which aren't available in Java.)

Using this method is the same as using a subscript to reference an item of an array. In the following example, the two lines of code are identical:

```
&MyArray[8] = &MyValue;
```

```
&MyArray.Set(8) = &MyValue;
```

Parameters

index	The array element to be accessed.

Returns

None.

Related Links

Get
Understanding Java Class

Shift

Syntax

```
Shift()
```

Description

Use the Shift method to remove the first element from the array and return it. Any following elements are "shifted" to an index of one less than they had.

Parameters

None.

Returns

Returns the value of the first element of the array. If the first element is a subarray, the subarray is returned.

Example

```
For &I = 1 to &ARRAY.Len;
   &ITEM = &ARRAY.Shift;
   /* do processing */
End-For;
```

Related Links

Pop

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Push
Replace
Unshift

Sort

Syntax

Sort(*order*)

Description

The Sort method rearranges the elements of the array executing the method into an order.

The type of sort done by this function, that is, whether it is a linguistic or binary sort, is determined by the Sort Order Option on the PeopleTools Options page.

If the array is one-dimensional, the elements are arranged in either ascending or descending order.

The type of the first element is used to determine the kind of comparison to be made. Any attempt to sort an array whose elements are not all of the same type results in an error.

If *order* is "A", the order is ascending; if it is "D", the order is descending. The comparison between elements is the same one as if done using the PeopleCode comparison operators (<, >, =, and so on.)

Note: If you execute this method on a server, the string sorting order is determined by the character set and localization of the server.

If the array is two-dimensional, the subarrays are arranged in order by the first element of each subarray. Sorting an array whose subarrays have different types of first elements will result in an error. The comparison is done by using the PeopleCode comparison operators (<, >, =, and so on.)

Note: This method works with arrays that have only one or two dimensions. You receive a runtime error if you try to use this method with an array that has more than two dimensions.

Parameters

order Specifies whether the array should be sorted in ascending or descending order. Values for *order* are:

Value	*Description*
A	Ascending
D	Descending

Returns

None.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

The following example changes the order of the elements in array &A to be ("Frank", "Harry", "John").

```
&A = CreateArray("John", "Frank", "Harry");

&A.Sort();

&A = CreateArray(CreateArray("John", 1952), CreateArray("Frank", 1957), CreateArray⇒
("Harry", 1928));
```

Image: &A expanded in PeopleCode debugger

The following example changes the order of the elements in array &A to be (("Frank", 1957), ("Harry", 1928), ("John", 1952)).

Local Name	Local Value
⊟ &A	Array
└Dimension	2
└Len	3
⊟ [1]	
└Dimension	1
└Len	2
└[1]	John
└[2]	1952
⊟ [2]	
└Dimension	1
└Len	2
└[1]	Frank
└[2]	1957
⊟ [3]	
└Dimension	1
└Len	2
└[1]	Harry
└[2]	1928

```
&A.Sort("A");
```

Image: &A expanded in PeopleCode debugger, showing code results

The following image is an example of &A expanded in PeopleCode debugger, showing code results.

Local Name	Local Value
⊟ &A	Array
└Dimension	2
└Len	3
⊟ [1]	
└Dimension	1
└Len	2
└[1]	Frank
└[2]	1957
⊟ [2]	
└Dimension	1
└Len	2
└[1]	Harry
└[2]	1928
⊟ [3]	
└Dimension	1
└Len	2
└[1]	John
└[2]	1952

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

Reverse

"Using Administration Utilities" (PeopleTools 8.54: System and Server Administration)

Subarray

Syntax

```
Subarray(start, length)
```

Description

The Subarray method creates a new array from an existing one, taking the elements from *start* for a total of *length*. If *length* if omitted, all elements from *start* to the end of the array are used.

If the array is multi-dimensional, the subarrays of the created array are *references* to the same subarrays from the existing array. This means if you make changes to the original subarrays, the referenced subarrays are also changed. To make distinct subarrays, use the Clone method.

Parameters

start	Specifies where in the array to begin the subarray.
length	Specifies the number of elements in the array to be part of the subarray.

Returns

An array object.

Example

To make a distinct array from a multi-dimensional array, use the following:

```
&A = &AAN.Subarray(1, 2).Clone();
```

Related Links

Clone

Substitute

Syntax

```
Substitute(old_val, new_val)
```

Description

The Substitute method replaces every occurrence of a value found in an array with a new value. To replace an element that occurs in a specific location in an array, use Replace.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

If the array is one-dimensional, Substitute replaces every occurrence of the *old_val* in the array with *new_val*.

If the array is two-dimensional, Substitute replaces every subarray whose first element is equal to *old_val*, with the subarray given by *new_val*.

Note: This method works with arrays that have only one or two dimensions. You receive a runtime error if you try to use this method with an array that has more than two dimensions.

Parameters

old_val	Specifies the existing value in the array to be replaced.
new_val	Specifies the value with which to replace occurrences of *old_val.*

Returns

None

Example

The following example changes the array &A to be ("John", "Jane", "Hamilton").

```
&A = CreateArray();
&A[1] = "John";
&A[2] = "Jane";
&A[3] = "Henry";
&A.Substitute("Henry", "Hamilton");
```

The following example changes the array &A to be (("John", 1952), ("Jane", 1957), ("Hamilton", 1971), ("Frank", 1961)).

```
&A = CreateArray(CreateArray("John", 1952), CreateArray("Jane", 1957), CreateArray(⇒
"Henry", 1928), CreateArray("Frank", 1961));

&A.Substitute("Henry", CreateArray("Hamilton", 1971));
```

Related Links

Find

Replace

Unshift

Syntax

Unshift(*paramlist*)

Where *paramlist* is an arbitrary-length list of values in the form:

value1 [, *value2*] ...

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

The Unshift method adds the given elements to the *start* of the array. Any following elements are moved up to indexes that are larger by the number of values moved. Flattening and Promotion are used to change the dimension of the supplied parameters to be one less than that of the given array.

Parameters

paramlist	Specifies values to be added to the start of the array.

Returns

None.

Example

The following code changes &A to be ("x", "Y", "a", "B", "c").

```
&A = CreateArray("a", "B", "c");

&A.Unshift("x", "Y");
```

Related Links

Pop
Push
Replace
Shift
Using Flattening and Promotion

Array Class Properties

In this section, we discuss the array class properties.

Dimension

Description

The Dimension property is the number of "Array" type names from the declaration of the array, also called subarrays. This property returns a number.

This property is read-only.

Example

The following example sets &DIM to 2.

```
Local Array of Array of Number &AAN;

&DIM = &AAN.Dimension;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Len

Description

The Len property is the current number of elements in the array. This property can be updated. Setting it to a negative value results in an error.

If this property is set to a smaller (nonnegative) number than its current value, the array is truncated to that length, discarding any elements whose indexes are larger than the given new length.

If this property is set to a number larger than its current value, the array is extended to the new length. Any new elements are set to a default value based on the element type of the array.

This property is read-write.

Example

The following is a test of whether an array is empty:

```
If &ARR.Len = 0 then

/* &ARR is empty.  */

End-If;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Chapter 11

BI Publisher Classes

Understanding BI Publisher and the BI Publisher Classes

Oracle Business Intelligence Publisher (BI Publisher, formerly XML Publisher) enables you to separate the data, layout, and translation layers of a report from each other. This can improve flexibility, as well as reduce maintenance. You need to create report definitions, define templates, and so on, using BI Publisher. The BI Publisher classes enable you to access the runtime portions of the XML publishing process programmatically—that is, after the templates and reports have been created.

The BI Publisher classes are divided into the following categories:

- Report manager definition classes
- Report manager search classes
- Engine classes

BI Publisher Report Manager Definition Classes

To create a report with BI Publisher, you first create a report definition using the Report Definition page. The report definition includes report properties, output formats, templates to be used, report security, and so on. At run time, the ReportDefn class uses these attributes to process the report. The ReportDefn class itself can be invoked from a batch process or a page PeopleCode. For example, the report can be scheduled from the Query Report Scheduler page, or viewed from Query Report Viewer page.

See ReportDefn Class.

BI Publisher Report Manager Search Classes

After you've published a report, it is stored in the report repository. Using the report manager search classes, you can search for a report based on defined search keys, or even add additional search keys for searching.

See Report Class.

See ReportManager Class.

See SearchAttribute Class.

BI Publisher Engine Classes

Use the BI Publisher engine classes to combine PDF files into a single PDF file, and to specify page numbers and watermarks on merged PDF reports.

See PageNumber Class.

See PDFMerger Class.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

See Properties Class.

See Watermark Class.

Related Links

"BI Publisher Overview" (PeopleTools 8.54: BI Publisher for PeopleSoft)

BI Publisher Terms

The following is a list of general BI Publisher terms and their definitions.

EFT	Electronic Funds Transfer, a format used by the banking industry.
eText	Electronic text, specifically, files in ASCII text format.
FO	Formatting objects, an XML markup language for document formatting.
HTML	Hyper Text Markup Language, a markup language designed for the creation of web pages.
PDF	Portable Document Format, a file format developed by Adobe Systems for representing documents in an independent format.
RTF	Rich Text Format, a document file format used for cross-platform document interchange.
XML	Extendable Markup Language, a general purpose markup language for many types of data.
SMS	Short messaging service, a short alphanumeric (160 characters) that is generally sent to a mobile device, such as a mobile phone.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

BI Publisher Flow Diagram

The following diagram presents the general flow of an XML report showing how and when certain BI Publisher classes are used in the publishing process.

Image: BI Publisher flow diagram

BI Publisher prepares the report data from the data source: a PS Query, a connected query, or an XML file. Then, BI Publisher uses the PSXP_RPTDEFNMANAGER report definition classes to generate and route the report. Optionally, BI Publisher uses the PSXP_REPORTMGR search classes to search for a report in the reports repository.

Error Handling

Different BI Publisher classes handle errors differently.

Use of report manager definition and report manager search classes should be wrapped in a try-catch statement to handle any errors. The BI Publisher engine class methods typically contain an error parameter as part of their signature that you can check for any errors. Other BI Publisher classes generally return a populated object that can be checked for a null value to determine any errors.

Related Links

"try" (PeopleTools 8.54: PeopleCode Language Reference)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Data Type and Scope of BI Publisher Objects

Each BI Publisher class is its own data type—that is, report definitions are declared as the ReportDefn data type, a report manager is declared as the ReportManager type, and so on.

An BI Publisher object can be declared of type local, component, or global and instantiated from PeopleCode only.

Instantiating BI Publisher Objects

The BI Publisher classes are not built-in classes, like Rowset, Field, Record, and so on. They are application classes. Before you can use these classes in your PeopleCode program, you must import them into your program.

Your import statements should look similar to the following:

```
import PSXP_RPTDEFNMANAGER:*;
```

Note: Using the asterisks after the package name makes all the application classes directly contained in the named package available. Application classes contained in subpackages of the named package are not made available.

After you've imported the appropriate BI Publisher classes, you instantiate an object of one of those classes using the constructor for the class and the create method.

The following example declares the variable &rptDefn and creates a new instance of the ReportDefn class:

```
Local PSXP_RPTDEFNMANAGER:ReportDefn &rptDefn = create PSXP_RPTDEFNMANAGER:ReportDe⇒
fn(&rptDefnId);
```

Related Links

Constructors

Import Declarations

Search Operator Values

Methods in the report manager definition and report search manager classes enable you to search for existing definitions. Many of the parameters for these methods should be specified in pairs, that is, a value specified with a search operator. All the search operator parameters use the same values.

Value	*Description*
%PSXP_SrchBegins	The name to search for begins with the specified value.
%PSXP_SrchContains	The name to search for contains the specified value.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Value	*Description*
%PSXP_SrchEquals	The name to search for equals the specified value.
%PSXP_SrchNotEquals	The name to search for does not equal the specified value.
%PSXP_SrchLessThan	The name to search for is less than the specified value.
%PSXP_SrchLessEquals	The name to search for is less than or equal to the specified value.
%PSXP_SrchGreaterThan	The name to search for is greater than the specified value.
%PSXP_SrchGreaterEquals	The name to search for is greater than or equal to the specified value.
%PSXP_SrchBetween	The name to search for is between two values. Separate the values by a comma. Do not use quotation marks. For example, `ACCT1,ACCT9`.
%PSXP_SrchIn	The name to search for is in the specified list. Separate the values with commas. Do not use quotation marks. For example, `ACCT1, ACCT2, ACCT3`.

BI Publisher Classes Reference

The BI Publisher classes reference includes the *public* subset of BI Publisher classes divided into the following sections:

- BI Publisher report manager definition classes.
- BI Publisher report manager search classes.
- BI Publisher engine classes.

BI Publisher Report Manager Definition Classes

The following report manager definition classes are described in this chapter: ReportDefn class.

ReportDefn Class

This section provides an overview of the ReportDefn class and discusses:

- ReportDefn class constructor
- ReportDefn class methods
- ReportDefn class properties

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Use the ReportDefn class to process a report definition created through the Report Definition component Use this class to generate and publish report output.

ReportDefn Class Constructor

This section describes the constructor for the ReportDefn class.

ReportDefn

Syntax

ReportDefn(*ReportId*)

Description

Use the ReportDefn constructor to instantiate a ReportDefn object. You must then use the Get method to initialize the object.

Parameters

ReportId	Specify a unique ID to be associated with the report definition.

Returns

A reference to a ReportDefn object.

Example

```
import PSXP_RPTDEFNMANAGER:ReportDefn;

Local PSXP_RPTDEFNMANAGER:ReportDefn &rptDefn = create PSXP_RPTDEFNMANAGER:ReportDe⇒
fn(&rptDefnId);
&rptDefn.Get();
```

ReportDefn Class Methods

In this section, the ReportDefn class methods are presented in alphabetical order.

Close

Syntax

Close()

Description

Use this method when there is an exception or error calling the ProcessReport method or any other output method (Publish, PrintOutout or DisplayOutput) of the ReportDefn class. Calling this method cleans up all temporary files, folders, and resources.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

None.

Returns

None.

Related Links

DisplayOutput
PrintOutput
ProcessReport
Publish

DisplayOutput

Syntax

```
DisplayOutput()
```

Description

Use the DisplayOutput method to display the report generated by the ProcessReport method in a separate browser window.

You must successfully call the ProcessReport method prior to calling this method.

This method displays a single report. Therefore, the report definition must not be set for bursting.

Parameters

None.

Returns

None.

Related Links

Close
ProcessReport

Get

Syntax

```
Get()
```

Description

Use the Get method to return a reference to the existing ReportDefn object.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

None.

Returns

A reference to the newly instantiated and populated ReportDefn object.

GetOutDestFormatString

Syntax

GetOutDestFormatString(*OutDestFormat*)

Description

Use the GetOutDestFormatString method to convert the output format returned from system variable %OutDestFormat to a BI Publisher output format string that can be passed to the output type parameter of the ProcessReport method. This method is useful when processing reports generated by application engine programs that are run process scheduler.

Parameters

OutDestFormat Specify the output destination format as a number. If you specify something other than a valid value, the method throws an exception. Valid values are:

Value	*Description*
2	PDF format
5	HTM format
8	XLS format
12	RTF format

Returns

A string if successful. Valid values are:

- PDF
- HTM
- XLS
- RTF

Related Links

ProcessReport

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GetPSQueryPromptRecord

Syntax

GetPSQueryPromptRecord()

Description

Use the GetPSQueryPromptRecord method to return the runtime prompts of a query as a record object. This method should only be used when the data source type associated with the report definition is a PeopleSoft query. This method returns a null when the data source type isn't a PeopleSoft Query.

Parameters

None.

Returns

A record object populated with the query prompts if the data source definition is a PeopleSoft query, null otherwise.

Related Links

SetPSQueryPromptRecord

PrintOutput

Syntax

PrintOutput(*DestPrinter*)

Description

Use the PrintOutput method to print the report definition object executing the method. The ProcessReport method must be called successfully before you use this method.

Parameters

DestPrinter	Specify the printer you want to use for printing the report, as a string.

Returns

None.

Related Links

Close

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ProcessReport

Syntax

```
ProcessReport(TemplateId, LanguageCD, AsOfDate, OutputFormat)
```

Description

Use the ProcessReport method to generate a report and store the information.

Before you generate the report, you must:

- Set the report output destination with the OutDestination property if the output type is a file.
- Specify the data source using the SetRuntimeDataXMLFile method if you are using a data source other than a PeopleSoft query.

After you use the ProcessReport method, you can use the Publish method to post the report, the DisplayOutput method to display the report in a browser window, or the PrintOutput method to print the report.

Parameters

TemplateId

Specify the template to be used for processing this report, as a string. You can specify a null value for this parameter, that is, ("""). When you specify a null value, the default template associated with the report definition is used.

LanguageCD

Specify the three-letter language code for the report definition, such as ENG, FRA, ESP and so on.

This parameter controls both the translation and the language specific output details such as font selection and right-to-left page orientation for Arabic/Hebrew.

You can specify a null value for this parameter, that is, ("""). If you specify a null value, the current language of the session is used.

AsOfDate

Specify the as of date for the report, as a date.

OutputFormat

Specify the output format, as a string.

See GetOutDestFormatString.

You can specify a null value for this parameter, that is, ("""). When you specify a null value, the default output format associated with the report definition is used.

Returns

None.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

GetOutDestFormatString
DisplayOutput
PrintOutput
SetPSQueryPromptRecord
SetRuntimeDataXMLFile
SetRuntimeProperties
OutDestination

Publish

Syntax

```
Publish(ServerName, ReportPath, FolderName, ProcessInstanceId)
```

Description

Use the Publish method to publish the current report definition

You must have successfully completed a call to the ProcessReport method before you can use this method.

Parameters

ServerName	Specify the server to use for publishing the report, as a string. You can specify a null value for this parameter—that is, (""").
ReportPath	Always specify a null value only for this parameter—that is, (""").
FolderName	Specify the name of the report folder that the report should be posted to. You can specify a null value for this parameter—that is, ("""). If you do not provide a value for this parameter, the default folder is used to post reports.
ProcessInstanceId	Specify the process instance of the calling process, such as the calling application engine program. If you specify a 0, a new process instance is generated to track the report posting process.

Returns

None.

Related Links

Close
ProcessReport

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SetPSQueryPromptRecord

Syntax

SetPSQueryPromptRecord(*&Record*)

Description

Use the SetPSQueryPromptRecord method to specify an already instantiated record object that contains the prompt values for the query to be used to populate the report.

This method can only be used with reports that have a PeopleSoft query defined as the data source.

You must use this method before using the ProcessReport method.

Parameters

&Record Specify an already instantiated and populated record object that contains the values for the query to be used to populate the report.

Returns

None.

Related Links

ProcessReport
GetPSQueryPromptRecord
Understanding Query Classes

SetRuntimeDataXMLFile

Syntax

SetRuntimeDataXMLFile(*FilePath*)

Description

Use the SetRuntimeDataXMLFile method to specify an existing XML file as the data source for the report.

Note: Because the SetRuntimeDataRowset and SetRuntimeDataXMLDoc methods have been deprecated, use this SetRuntimeDataXMLFile method instead.

Report definitions that use a data source other than a PeopleSoft query must set that data source before generating the report using the ProcessReport method.

Forward or back slashes are used in the path according to the operating system of the application server or process scheduler server—that is, on Unix servers, the directory separator is a forward slash, while Windows servers use back slashes.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

FilePath

Specify an absolute path to the file that you want to use. You must include the file name and file extension in the parameter.

Forward or back slashes are used in the path according to the operating system of the application server or process scheduler server. That is, on Unix servers, the directory separator is a forward slash, while a Windows server use a path with back slashes.

Returns

None.

Related Links

ProcessReport
Understanding File Layout

SetRuntimeProperties

Syntax

```
SetRuntimeProperties(&NameArray, &ValueArray)
```

Description

Use the SetRuntimeProperties method to set additional runtime values and properties required for generating this report.

Note: BI Publisher's properties are defined at three different levels. Global properties are defined on the Global Properties page, and system properties are defined in the xdo.cfg file. At the report definition level, properties are defined on the Report Definition - Properties page. The runtime properties defined using this method override both global and report definition properties. However, system properties defined in the xdo.cfg file cannot be overridden using this method.

Parameters

&NameArray

Specify an already instantiated and populated array of string containing the names of the additional properties or variables that you need for this report.

&ValueArray

Specify an already instantiated and populated array of string containing the values of the additional properties or variables that you need for this report. The values should be in the same order as the names listed in *&NameArray*.

Returns

None.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

The following example sets extra parameters for securing a document.

```
&asPropName = CreateArrayRept("", 0);
&asPropValue = CreateArrayRept("", 0);
&asPropName.Push("pdf-compression");
&asPropValue.Push("false");
&asPropName.Push("pdf-hide-menubar");
&asPropValue.Push("true");
&oRptDefn.SetRuntimeProperties(&asPropName, &asPropValue);
```

Setting Custom Runtime Parameters

The SetRuntimeProperties method can also be used to set custom runtime parameters. When setting custom runtime parameters with the SetRuntimeProperties method, the parameter names need to be prefixed with *xslt*, and the values need to be surrounded by single quotes (for example, 'xyz'). For example, the following code creates a custom runtime parameter named xslt.ReportOwner:

```
&asPropName = CreateArrayRept("", 0);
&asPropValue = CreateArrayRept("", 0);
&asPropName.Push("xslt.ReportOwner");

/* Note the single quotes around the parameter value */
&asPropValue.Push(" 'John Smith' ");

&oRptDefn.SetRuntimeProperties(&asPropName, &asPropValue);
```

The custom parameter may now be used in the template via the tag <?$ReportOwner?>. Before using it, it does need to be declared in a form field on the report template using the following tag:

```
<xsl:param name="ReportOwner" xdofo:ctx="begin"/>
```

Related Links

"Running Reports Using PeopleCode" (PeopleTools 8.54: BI Publisher for PeopleSoft)

"Setting Up BI Publisher" (PeopleTools 8.54: BI Publisher for PeopleSoft)

"Creating Report Definitions" (PeopleTools 8.54: BI Publisher for PeopleSoft)

"Defining System Properties" (PeopleTools 8.54: BI Publisher for PeopleSoft)

ReportDefn Class Properties

In this section, the ReportDefn class properties are presented in alphabetical order.

Description

Description

Use the Description property to return a description for the report definition.

This property is effectively read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

DestinationPrinter

Description

Use the DestinationPrinter property to specify a printer for the generated report.

This property is read-write.

FolderName

Description

Use the FolderName property to specify a folder name for the generated report to be posted to.

This property is read-write.

OutDestination

Description

This property sets the report output destination as a string. This property must be set before calling the ProcessReport method. When ProcessReport is called, it places the generated report files in the directory specified by this property.

If this property is not set prior to calling the ProcessReport method, the report processing directory and the value returned by the OutDestination property depends on the setting of the psxp_usedefaultoutdestination property. The psxp_usedefaultoutdestination property, which is set on the Report Definition - Properties page, is used to set a compatibility mode with pre-8.50 PeopleTools versions.

See "Setting Report Properties" (PeopleTools 8.54: BI Publisher for PeopleSoft).

This property is effectively write-only.

Important! While this property is read-write, your PeopleCode program should read this property only if the program set the property first. Reading the property before it has been explicitly set produces unexpected results.

Related Links

ProcessReport

OutDestinationType

Description

This property returns the type of device specified for the output of the report definition, as a string.

This property returns the output destination value set on the Report Definition-Output page; it is not used internally to determine the output type. It can be used in a PeopleCode program to determine how to process and produce report output (for example, whether to call Publish, how to set OutDestination).

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is effectively read-only.

ProcessInstance

Description

Use this property to specify a number representing a process instance for running the report.

In certain circumstances—for example, when running report using a Process Scheduler server—a process instance number is required for setting drilling URLs in the report output. In these cases, you must set the ProcessInstance property prior to calling the ProcessReport method.

This property is read-write.

Example

```
&ProcessInstance=PSXPQRYRPT_AET.PROCESS_INSTANCE;
&oRptDefn.ProcessInstance = &ProcessInstance;
&oRptDefn.ProcessReport("", "", %Date, "");
```

ReportFileName

Description

Use the ReportFileName property to specify the file name for the generated report as a string. When this property is set, it overrides the setting of the UseBurstValueAsOutputFileName property.

This property is read-write.

Related Links

UseBurstValueAsOutputFileName

Status

Description

This property returns the status of the report definition as a string. Valid values are:

Value	*Description*
A	The report definition is active and can be run.
I	The report definition is inactive and cannot be run.
P	The report definition is in progress and cannot be run. This is the default value.

This property is read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

UseBurstValueAsOutputFileName

Description

Use the UseBurstValueAsOutputFileName property to specify different names for all the files that result from bursting. This property takes a Boolean value: true, the report output files are named *BurstValue.Extention.* False is the default value.

Note: If the ReportFileName property is set, it overrides the setting of this property.

This property is read-write.

Related Links

ReportFileName

BI Publisher Report Manager Search Classes

The following report manager search classes are described in this chapter:

- Report class
- ReportManager class
- SearchAttribute class

Report Class

This section provides an overview of the Report class and discusses:

- Report class constructor
- Report class properties

The Report class is one of the report manager search classes. Use the Report class to access individual reports that have already been published to the report repository.

Report Class Constructor

This section describes the constructor for the Report class.

Report

Syntax

```
Report(RptId, Prcsinstance, Contentid, Dbname, RptName, RptDescr, RptURL,
RptCreateDttm, RptExpireDt, FldrName)
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the Report constructor to instantiate and populate a Report object with the data of an already published report.

Parameters

RptId	Specify the report ID of the report you want to access, as a string.
Prcsinstance	Specify the process instance of the report you want to access, as a number.
Contentid	Specify the content ID number of the report you want to access, as a number.
Dbname	Specify the data base name, as a string.
RptName	Specify the name of the report you want to access, as a string.
RptDescr	Specify the description of the report you want to access, as a string.
RptURL	Specify the URL to the report details page, as a string.
RptCreateDttm	Specify the date and time of the report you want to access, as a date time value.
RptExpireDt	Specify the date when the report will be archived, and no longer considered active, as a date.
FldName	Specify the name of the folder the report was published to, as a string. You must specify an absolute path name, using forward and back slashes as required by the operating system of the application server or process scheduler.

Returns

A reference to a Report object.

Example

```
import PSXP_REPORTMGR:Report;

Local PSXP_REPORTMGR:Report &oRpt = create PSXP_REPORTMGR:Report(String(&nRptId), &⇒
prcsinstance, &contentid, &sdbname, &sRptName, &sRptDescr, &sRptURL, &sFileURL, &dR⇒
ptCreateDttm, &dRptExpireDt, &sFldrName);
```

Report Class Properties

In this section, the Report class properties are presented in alphabetical order.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

contentId

Description

This property returns the content ID of the report, as a number.

This property is read-only.

CreatedDateTime

Description

This property returns the date time when the report was created, as a date time.

This property is read-only.

DatabaseName

Description

This property returns the data base name associated with the report, as a string.

This property is read-only.

Description

Description

This property returns the description of the report definition, as a string.

This property is read-only.

ExpireDate

Description

This property returns the date when the report will be archived, as a date value.

This property is read-only.

FileURL

Description

This property returns a URL to the actual report file in the report repository.

Use the ReportURL property to access the report detail page instead.

This property is read-only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

ReportURL

FolderName

Description

This property returns the full path name of the folder where the report is stored, as a string.

This property is read-only.

ProcessInstanceID

Description

This property returns the process instance ID associated with the report when it was posted, as a number.

This property is read-only.

Related Links

ReportInstanceID

ReportInstanceID

Description

This property returns the report instance ID, that was populated when the report was run, as a number.

This property is read-only.

Related Links

ProcessInstanceID

ReportName

Description

This property returns the name of the report, as a string.

This property is read-only.

ReportURL

Description

This property returns a URL as a string, that points to the report detail page.

Use the FileURL to access a URL to the actual file containing the report in the report repository.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-only.

Related Links

FileURL

ReportManager Class

This section provides an overview of the ReportManager class and discusses:

- ReportManager class constructor
- ReportManager class methods

The ReportManager class is one of the report manager search classes. Use the ReportManager class to set the search criteria for reports that have already been published to the report repository.

ReportManager Class Constructor

This section describes the constructor for the ReportManager class.

ReportManager

Syntax

ReportManager()

Description

Use the ReportManager constructor to instantiate an instance of the ReportManager class.

Parameters

None.

Returns

A ReportManager object.

Example

```
import PSXP_REPORTMGR:ReportManager;

Local REPORTMGR:ReportManager &rptMgr = create REPORTMGR:ReportManager();
```

ReportManager Class Methods

In this section, the ReportManager class methods are presented in alphabetical order.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

AddSearchFieldCriteria

Syntax

AddSearchFieldCriteria(*&SearchAttribute*)

Description

Use the AddSearchFieldCriteria method to add an already instantiated and populated SearchAttribute object to the search.

Parameters

&SearchAttribute	Specify an already instantiated and populated SearchAttribute object.

Returns

A Boolean, true if the criteria was added successfully, false otherwise.

Example

```
Local PSXP_REPORTMGR:SearchAttribute &oSearch;
Local integer &compOpSrch;

&CompOpSrch = oRptMgr.PSXP_SrchBegins;

&oSearch = create PSXP_REPORTMGR:SearchAttribute(&sAttrname, &sAttrVal, &compOpSrch⇒
);

&bResult = &oRptMgr.addSearchFieldCriteria(&oSearch);
```

Related Links

SearchAttribute Class

GetReportList

Syntax

GetReportList()

Description

Use the GetReportList method to return a list of the report objects that satisfy all the criteria you specified with the other methods associated with the ReportManager object.

Parameters

None.

Returns

An array of Report objects.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

Report Class

SetBurstFieldCriteria

Syntax

SetBurstFieldCriteria(*BurstFld*, *BurstOp*, *BurstValue*)

Description

Use the SetBurstFieldCriteria method to specify the burst criteria to be used with searching report definitions.

Parameters

BurstField	Specify the name of the burst field used to generate the report, as a string.
BusrtOp	Specify the search operator to be used *BurstField*, as a string. See Search Operator Values.
BurstValue	Specify the pattern string to be matched with burst field value using *BurstOp*.

Returns

A Boolean value, true if the method completes successfully, false otherwise.

SetCaseSensitive

Syntax

SetCaseSensitive(*IsCaseSensitive*)

Description

Use the SetCaseSensitive method to specify the case sensitivity flag applicable to search field and bursting criteria for searching reports.

Parameters

IsCaseSensitive	Specify a Boolean value: true to make the search case sensitive, false to make it case insensitive.

Returns

None.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SetDateCriteria

Syntax

SetDateCriteria(*createdDate, createdLastVal, createdUnit*)

Description

Use the SetDateCriteria method to specify the creation date criteria for searching reports.

Parameters

createdDate Specify a date used to search for reports generated on and after this date. You should specify a null value (" ") for this parameter if using *createdLastVal* and *createdUnit*.

createdLastVal Specify a value to be used n conjunction with *createdUnit*, as a number. If you specify a value, it is used and any value given for *createdDate*is ignored. If you are not using this search criteria, you should specify a null value (" ") for this parameter.

createdUnit Specify a value to be used for reports generated during last *n* number of periodic units. This value is used with *createdLasVal*. For example, if *createdLastVal* is set to 10, and *createdUnit* is set to 1, the reports generated in the last ten days are returned. Valid values are:

Value	*Description*
1	Days
2	Hours
3	Minutes

Returns

None.

SetFolderCriteria

Syntax

SetFolderCriteria(*FolderName*)

Description

Use the SetFolderCriteria method to specify the folder criteria for searching reports.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

FolderName	Specify the name of the folder the report is posted in, as a string.

Returns

A Boolean value, true if the search criteria is added successfully, false otherwise.

SetProcessInstanceCriteria

Syntax

`SetProcessInstanceCriteria``(`*`FromPID, ToPID`*`)`

Description

Use the SetProcessInstanceCriteria method to specify the process instance range criteria for searching reports.

Parameters

FromPID	Specify a process instance ID to be used as the starting range from which to search, as a number. This value must be less than or equal to *ToPID*. You can specify a null value for this parameter, that is, (" ").
ToPID	Specify a process instance ID to be used as the ending range from which to search, as a number. This value must be greater than or equal to *FromPID*. You can specify a null value for this parameter, that is, (" ").

Returns

A Boolean value: true if the search criteria is added successfully, false otherwise.

SetReportIDCriteria

Syntax

`SetReportIDCriteria``(`*`ReportId`*`)`

Description

Use the SetReportIDCriteria method to specify a report ID for searching reports.

Parameters

ReportId	Specify a report ID to be used for searching for report definitions.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

A Boolean value: true if the search criteria was set successfully, false otherwise.

SetUserIdCriteria

Syntax

SetUserIdCriteria(*UserId*)

Description

Use the SetUserIdCriteria method to specify a user ID to be used for searching reports intended to be accessed by that recipient.

Parameters

UserId	Specify the user ID to be matched with the intended recipient of the report.

Returns

A Boolean: true if the search criteria is set successfully, false otherwise.

SearchAttribute Class

This section provides an overview of the SearchAttribute class and discusses:

- SearchAttribute class constructor
- SearchAttribute class properties

The SearchAttribute class is one of the report manager search classes. Use the SearchAttribute class to discover name-value pairs for the search criteria for reports that have already been published to the report repository. In addition, you can also specify a comparison operator to be used with the name-value pairs.

SearchAttribute Class Constructor

This section describes the constructor for the SearchAttribute class.

SearchAttribute

Syntax

SearchAttribute(*AttrName*, *AttrValue*, *CompareOperator*)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the SearchAttribute constructor to instantiate an instance of a SearchAttribute object.

Parameters

AttrName	Specify the attribute name, as a string.
AttrValue	Specify the attribute value, as a string.
CompareOperator	Specify a comparison operator. See Search Operator Values.

Returns

A SearchAttribute object.

Example

```
import PSXP_REPORTMGR:SearchAttribute;

Local PSXP_REPORTMGR:SearchAttribute &oSearch = create PSXP_REPORTMGR:SearchAttribu⇒
te(&sAttrname, &sAttrVal, &compOpSrch);
```

SearchAttribute Class Properties

In this section, the SearchAttribute class properties are presented in alphabetical order.

attrName

Description

This property returns the attribute name used with search.

This property is read-only.

attrValue

Description

This property returns the attribute value used with search???

This property is read-only.

compareOp

Description

This property returns the comparison operator used with search.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-only.

BI Publisher Engine Classes

The following engine classes are described in this chapter:

- PageNumber class
- PDFMerger class
- Properties class
- Watermark class

PageNumber Class

This section provides an overview of the PageNumber class and discusses:

- PageNumber class constructor
- PageNumber class properties

Use the PageNumber class to set the page number for a merged PDF file. Objects in this class are used with the PageNumber property of the PDFMerger class.

Related Links

PageNumber

PageNumber Class Constructor

This section describes the constructor for the PageNumber class.

PageNumber

Syntax

```
PageNumber()
```

Description

Use the PageNumber constructor to instantiate a PageNumber object.

Parameters

None.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

A PageNumber object.

Example

```
import PSXP_ENGINE:PageNumber;

Local PSXP_ENGINE:PageNumber &pNum = create PSXP_ENGINE:PageNumber();
```

PageNumber Class Properties

In this section, the PageNumber class properties are presented in alphabetical order.

BackgroundFile

Description

Use the BackgroundFile property to specify a file to be used for the page number, as a string.

You must specify an absolute file name.

This property is read-write.

Considerations Using the BackgroundFile Property

You should either use the BackgroundFile property, or you should use the other properties associated with this class, like position or font. You cannot use both.

The file you specify must be a PDF file. The page size of the background PDF must be the same as the target PDF document, otherwise the page numbering doesn't work properly. All page numbering starts on the first page of the target document.

FontName

Description

Use the FontName property to specify the name of the font to be used for the page number, as a string. Valid values are:

- Courier
- Courier-Bold
- Courier-BoldOblique
- Helvetica (this is the default value)
- Helvetica-Bold
- Helvetica-BoldOblique
- Helvetica-Oblique

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- Symbol
- Times-Bold
- Time-BoldItalic
- Time-Italic
- Time-Roman
- ZapfDingbats

If you specify an invalid font name, the default (Helvetica) is used.

This property is read-write.

Related Links

FontSize

FontSize

Description

Use the FontSize property to specify the size of the page number, as a number.

The default value is 8.

This property is read-write.

Related Links

FontName

PositionX

Description

Use the PositionX property to specify the X axis position of the text page number in the merged document.

This property is read-write.

Related Links

PositionY

PositionY

Description

Use the PositionY property to specify the Yaxis position of the text page number in the merged document.

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

PositionX

StartFromPageNum

Description

Use the StartFromPageNum property to specify the page index from which you'd like to start the page numbering.

For example, if you have a PDF document which has two cover pages, and you want to start printing page numbers on the document from the third page, specify a three for this property.

This property is read-write.

Related Links

StartNum

StartNum

Description

Use the StartNum property to specify the page number to use as the first page number in the merged document. If you don't specify a starting number, the pages are numbered starting from 1.

This property is read-write.

Related Links

StartFromPageNum

PDFMerger Class

This section provides an overview of the PDFMerger class and discusses:

- PDFMerger class constructor
- PDFMerger class method
- PDFMerger class properties

Use the PDFMerger class to combine two or more PDF files into a single PDF file.

PDFMerger Class Constructor

This section describes the constructor for the PDFMerger class.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

PDFMerger

Syntax

PDFMerger()

Description

Use the PDFMerger constructor to instantiate a PDFMerger object.

Parameters

None.

Returns

A reference to a PDFMerger object.

Example

```
import PSXP_ENGINE:PDFMerger;

Local PSXP_ENGINE:PDFMerger &oMerger = create PSXP_ENGINE:PDFMerger();
```

PDFMerger Class Method

In this section, the PDFMerger class method is presented.

MergePDFs

Syntax

MergePDFs(*PDFFileArray*, *PDFOutputFile*, *Error*)

Description

Use the MergePDFs method to merge the specified PDF files into a single output file.

The order of the files specified in the array are the order in which the files are merged.

Parameters

PDFFileArray Specify an already instantiated and populated array of string containing the names of the PDF files that you want to merge together.

PDFOutputFile Specify the full path name of the file you want populated with the merged PDF file.

Forward or back slashes are used in the path according to the operating system of the application server or process scheduler server. That is, on Unix servers, the directory separator is a

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

forward slash, while a Windows server returns a path with back slashes.

Error If any errors occur during processing, this parameter is populated with the text of the error message after processing.

Returns

A Boolean: true if the method completed successfully, false otherwise. If this method returns false, the *Error* parameter is populated with the text of the error message that occurred.

Example

```
Local PSXP_ENGINE:PDFMerger &oMerger;

&sErr = "";
&asNames = CreateArray(&sPdfFile1);
&asNames.Push(&sPdfFile2);
&bResult = &oMerger.mergePDFs(&asNames, &sOutputPdfFile, &sErr);
```

PDFMerger Class Properties

In this section, the PDFMerger class properties are presented in alphabetical order.

ConfProp

Description

Use the ConfProp property to specify an already instantiated and populated Properties object that contains the configuration to be used for processing the document. This property enables you to accommodate different system configurations.

Related Links

Properties Class

Locale

Description

Use the Locale property to specify the locale for the processing. If no value is specified for this property, the default system locale will be used.

The locale is specified using a two character ISO language code and a two character ISO country code (LC-CC). When you don't need to reflect country specific formatting, the locale code is made up of just the language code.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

PageNumber

Description

Use this property to specify an already instantiated and populated PageNumber object to be used with the merged document.

This property is read-write.

Example

```
Local PSXP_ENGINE:PDFMerger &oMerger;
Local PSXP_ENGINE:PageNumber &oPageNumber;

&oMerger = create PSXP_ENGINE:PDFMerger();
&oPageNumber = create PSXP_ENGINE:PageNumber();

&oPageNumber.FontName = "Symbol";
&oPageNumber.FontSize = 16;
&oPageNumber.PositionX = 300;
&oPageNumber.PositionY = 20;
&oMerger.oPageNumber = &oPageNumber;

&sErr = "";
&asNames = CreateArray(&sPdfFile1);
&asNames.Push(&sPdfFile2);
&bResult = &oMerger.mergePDFs(&asNames, &sOutputPdfFile, &sErr);
```

Related Links

PageNumber Class

Watermark

Description

Use this property to specify an already instantiated and populated Watermark object to be used with the merged object.

This property is read-write.

Example

```
Local PSXP_ENGINE:PDFMerger &oMerger;
Local PSXP_ENGINE:Watermark &oWatermark;

&oMerger = create PSXP_ENGINE:PDFMerger();
&oWatermark = create PSXP_ENGINE:Watermark();

&oWatermark.Text = "DEMO";
&oWatermark.TextStartPosX = 200;
&oWatermark.TextStartPosY = 400;
&oMerger.oWatermark = &oWatermark;

&sErr = "";
&asNames = CreateArray(&sPdfFile1);
&bResult = &oMerger.mergePDFs(&asNames, &sOutputPdfFile, &sErr);
```

Related Links

Watermark Class

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Properties Class

This section provides an overview of the Properties class and discusses:

- Properties class constructor
- Properties class methods

Use the Properties class to specify the properties for setting up the processor configuration. This class is used with the PDFMerger class.

Related Links

ConfProp

Properties Class Constructor

This section describes the constructor for the Properties class.

Properties

Syntax

Properties()

Description

Use the Properties constructor to instantiate a Properties object.

Parameters

None.

Returns

A Properties object.

Example

```
import PSXP_ENGINE:Properties;

Local PSXP_ENGINE:Properties &rProps = create PSXP_ENGINE:Properties();
```

Properties Class Methods

In this section, the Properties class methods are presented in alphabetical order.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GetProperty

Syntax

GetProperty(*Name*, *OutValue*)

Description

Use the GetProperty method to return the value of the specified property.

Parameters

Name	Specify the name of the property that you want to access the value.
OutValue	Specify a string to contain the value of the property you want to access.

Returns

A Boolean: true if the method completed successfully, false otherwise. If this method returns false, the *Error* parameter is populated with the text of the error message that occurred.

Example

```
Local PSXP_ENGINE:Properties &oProp;

&oProp = create PSXP_ENGINE:Properties();
%sValue = "";
&bResult = &oProp.getProperty("pdf-security", %sValue);
```

SetProperty

Syntax

SetProperty(*Name*, *Value*)

Description

Use the SetProperty method to specify the value of the specified property.

Parameters

Name	Specify the name of the property that you want to set.
Value	Specify the value of the property that you want to set.

Returns

A Boolean: true if the method completed successfully, false otherwise. If this method returns false, the *Error* parameter is populated with the text of the error message that occurred.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

```
Local PSXP_ENGINE:Properties &oProp;

&oProp = create PSXP_ENGINE:Properties();
&bResult = &oProp.setProperty("pdf-security", "true");
```

Watermark Class

This section provides an overview of the Watermark class and discusses:

- Watermark class constructor
- Watermark class properties

Use the Watermark class to specify a watermark for a merged PDF file. Objects in this class are used with the Watermark property of the PDFMerger class. You can generate a watermark either using text or an image. You can either use the text properties or the image properties. You cannot use both.

The following are the image properties of the Watermark class:

- ImageFile
- ImageLowerLeftX
- ImageLowerLeftY
- ImageUpperRightX
- ImageUpperRightY

The following are the text properties of the Watermark class:

- Text
- TextAngle
- TextFontName
- TextFontSize
- TextStartPosX
- TextStartPosY

Related Links

Watermark

Watermark Class Constructor

This section describes the constructor for the Watermark class.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Watermark

Syntax

```
Watermark()
```

Description

Use the Watermark constructor to instantiate a Watermark object.

Parameters

None.

Returns

A Watermark object.

Example

```
import PSXP_ENGINE:Watermark;

Local PSXP_ENGINE:Watermark &rProps = create PSXP_ENGINE:Watermark();
```

Watermark Class Properties

In this section, the Watermark class properties are presented in alphabetical order.

ImageFile

Description

Use the ImageFile property to specify the full path name of an image file to be used for the watermark.

Forward or back slashes are used in the path according to the operating system of the application server or process scheduler server. That is, on Unix servers, the directory separator is a forward slash, while a Windows server returns a path with back slashes.

This property is read-write.

ImageFileLowerLeftX

Description

Use the ImageFileLowerLeftX property to specify the lower left, X-axis position for the watermark, as a number.

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ImageFileLowerLeftY

Description

Use the ImageFileLowerLeftY property to specify the lower left, Y-axis position for the watermark, as a number.

This property is read-write.

ImageFileUpperRightX

Description

Use the ImageFileUpperRightX property to specify the upper right, X-axis position for the watermark, as a number.

This property is read-write.

ImageFileUpperRightY

Description

Use the ImageFileUpperRightY property to specify the upper right, Y-axis position for the watermark, as a number.

This property is read-write.

PageIndex

Description

Use the PageIndex property to specify the page where the watermark begins. For example, you might not want a watermark to display on a cover page. The default value is 0, which sets the watermark on all pages (page index starts at 1.)

This property is read-write.

Text

Description

Use the Text property to specify the text for the watermark, as a string.

This property is read-write.

TextAngle

Description

Use the TextAngle property to specify the angle of the watermark text across the page. You must specify a number between 1 and 360.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-write.

TextFontName

Description

Use the TextFontName property to specify the name of the font to be used for the text for the watermark.

This property is read-write.

TextFontSize

Description

Use the TextFontSize property to specify the size of the text font. The default value is 8.

This property is read-write.

TextStartPosX

Description

Use the TextStartPosX property to specify the starting position, X-axis location for the text to be used as the watermark.

This property is read-write.

TextStartPosY

Description

Use the TextStartPosY property to specify the starting position, Y-axis location for the text to be used as the watermark.

This property is read-write.

Understanding the DigitalCertStore Class

The DigitalCertStore class defines the available methods that can be invoked by a custom implementation of the IPT_PDFSIGNATURE_INT:IPDFSignature interface class to retrieve digital certificates and passwords for PDF reports produced with BI Publisher for PeopleSoft. The DigitalCertStore class is also used internally by BI Publisher for PeopleSoft for similar purposes.

Related Links

Understanding the IPDFSignature Interface Class

"Using the External Digital Certificates Page" (PeopleTools 8.54: Security Administration)

"Understanding Digital Signature in BI Publisher Reports" (PeopleTools 8.54: BI Publisher for PeopleSoft)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

DigitalCertStore Class Methods

The methods in this section are described in alphabetical order.

DigitalCertStore

Syntax

DigitalCertStore()

Description

Use the DigitalCertStore constructor method to instantiate a DigitalCertStore object.

Parameters

None.

Returns

A DigitalCertStore object.

Example

Use the create built-in function to instantiate a DigitalCertStore object:

```
import PT_SECURITY_DIGITALCERTSTORE:DigitalCertStore;

&oStore = create PT_SECURITY_DIGITALCERTSTORE:DigitalCertStore();
```

ExtractCertificateByAuthorizedRole

Syntax

ExtractCertificateByAuthorizedRole(*digital_ID*, *auth_role*, *dest_location*, *&keystore_pwd*)

Description

Use the ExtractCertificateByAuthorizedRole method to retrieve a digital certificate file to the specified location on the application server based on the specified digital ID and whether the current user has the specified role. This method also returns the encrypted password for the certificate file.

Important! Do not use this method in an implementation of the IPT_PDFSIGNATURE_INT:IPDFSignature interface class. Oracle reserves the right to modify this method in the future.

Parameters

digital_ID Specifies the digital ID for the certificate as a string value.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

auth_role Specifies a role name as a string value.

dest_location Specifies the absolute URL to store the certificate file on the application server as a string value.

&keystore_pwd Specifies an already instantiated string variable to store the returned encrypted password.

Returns

A return code as a numeric value:

Numeric Value	*Description*
0	The method executed successfully.
58	The digital ID, role name, or the destination location is invalid due to being specified as an empty string.
59	There is no certificate file or password available to the specified role name.
60	The role name is not authorized or cannot be found.
61	There was an error downloading the certificate file from the database.
79	The current user does not have the specified role.

ExtractCertificateByAuthorizedUser

Syntax

```
ExtractCertificateByAuthorizedUser(digital_ID, auth_user, dest_location,
&keystore_pwd)
```

Description

Use the ExtractCertificateByAuthorizedUser method to retrieve a digital certificate file to the specified location on the application server based on the specified digital ID and whether the current user is the specified user. This method also returns the encrypted password for the certificate file.

Important! Do not use this method in an implementation of the IPT_PDFSIGNATURE_INT:IPDFSignature interface class. Oracle reserves the right to modify this method in the future.

Parameters

digital_ID Specifies the digital ID for the certificate as a string value.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

auth_user Specifies a user ID as a string value.

dest_location Specifies the absolute URL to store the certificate file on the application server as a string value.

&keystore_pwd Specifies an already instantiated string variable to store the returned encrypted password.

Returns

A return code as a numeric value:

Numeric Value	*Description*
0	The method executed successfully.
54	The digital ID, user ID, or the destination location is invalid due to being specified as an empty string.
55	There is no certificate file or password available to the specified user ID.
56	The specified user ID is not authorized or cannot be found.
57	There was an error downloading the certificate file from the database.
78	The specified user ID is not the current user.

ExtractCertificateByDigitalID

Syntax

`ExtractCertificateByDigitalID``(`*`digital_ID, dest_location, &keystore_pwd`*`)`

Description

Use the ExtractCertificateByDigitalID method to retrieve a digital certificate file to the specified location on the application server based on the specified digital ID. This method also returns the encrypted password for the certificate file.

Important! Do not use this method in an implementation of the IPT_PDFSIGNATURE_INT:IPDFSignature interface class. Oracle reserves the right to modify this method in the future.

Parameters

digital_ID Specifies the digital ID for the certificate as a string value.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

dest_location Specifies the absolute URL to store the certificate file on the application server as a string value.

&keystore_pwd Specifies an already instantiated string variable to store the returned encrypted password.

Returns

A return code as a numeric value:

Numeric Value	*Description*
0	The method executed successfully.
50	The digital ID or the destination location is invalid due to being specified as an empty string.
51	There is no certificate file or password for the specified digital ID
52	The digital ID is inactive or cannot be found.
53	There was an error downloading the certificate file from the database.
56	The specified user ID is not authorized or cannot be found.
79	The current user does not have the specified role.

Example

```
&errCode = &oStore.ExtractCertificateByDigitalID(&digitalID, &sOutDestination, &psw⇒
);
&keystorePswd = &psw;

If &errCode > 0 Then
   &m_sError = &oStore.ErrorMessageDetail;
End-If;
```

getDigitalCertFileNameByDigitalID

Syntax

getDigitalCertFileNameByDigitalID(*digital_ID, &file_name*)

Description

Use the getDigitalCertFileNameByDigitalID method to return the name of the digital certificate file based on the specified digital ID.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Important! Do not use this method in an implementation of the IPT_PDFSIGNATURE_INT:IPDFSignature interface class. Oracle reserves the right to modify this method in the future.

Parameters

digital_ID Specifies the digital ID for the certificate as a string value.

&file_name Specifies an already instantiated string variable to store the returned certificate file name.

Returns

A return code as a numeric value:

Numeric Value	*Description*
0	The method executed successfully.
65	The digital ID was specified as the empty string.
70	No file name is defined for this digital ID.

Example

```
&errCode = &oStore.getDigitalCertFileNameByDigitalID(&digitalID, &tmpStr);
If &errCode > 0 Then /* failure */
   &m_sError = &oStore.ErrorMessageDetail;
Else /* success */
   ...
End-If;
```

getDigitalIdBySigner

Syntax

getDigitalIdBySigner(*signer*, *&array_digitalIDs*)

Description

Use the getDigitalIdBySigner method to return a list of digital IDs that are available to the specified signer.

Parameters

signer Specifies the ID of the signer as a string value.

&array_digitalIDs Specifies an already instantiated array of string to store the returned list of digital IDs.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

A return code as a numeric value:

Numeric Value	*Description*
0	The method executed successfully.
62	The signer was specified as the empty string.
63	No digital IDs are defined for this signer.

getEncPassword

Syntax

```
getEncPassword(digital_ID, &keystore_pwd )
```

Description

Use the getEncPassword method to return the encrypted password for the specified digital ID.

Important! Do not use this method in an implementation of the IPT_PDFSIGNATURE_INT:IPDFSignature interface class. Oracle reserves the right to modify this method in the future.

Parameters

digital_ID Specifies the digital ID of the certificate as a string value.

&keystore_pwd Specifies an already instantiated string variable to store the returned encrypted password.

Note: Currently, the encrypted password is not returned by this method.

Returns

A return code as a numeric value:

Numeric Value	*Description*
0	The method executed successfully.
65	The digital ID was specified as the empty string.
73	No password is defined for this digital ID.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

getListOfAuthorizedRoleNames

Syntax

getListOfAuthorizedRoleNames(*digital_ID, &array_auth_roles*)

Description

Use the getListOfAuthorizedRoleNames method to return the list of authorized roles for the specified digital ID.

Parameters

digital_ID Specifies the digital ID for the certificate as a string value.

&array_auth_roles Specifies an already instantiated array of string to store the returned list of authorized roles names.

Returns

A return code as a numeric value:

Numeric Value	*Description*
65	The digital ID was specified as the empty string.
68	No authorized roles are defined for this digital ID.
69	The method executed successfully. There are *n* authorized roles for the specified digital ID.

getListOfAuthorizedUsers

Syntax

getListOfAuthorizedUsers(*digital_ID, &array_auth_users*)

Description

Use the getListOfAuthorizedUsers method to return the list of authorized users for the specified digital ID.

Parameters

digital_ID Specifies the digital ID for the certificate as a string value.

&array_auth_users Specifies an already instantiated array of string to store the returned list of authorized user IDs.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

A return code as a numeric value:

Numeric Value	*Description*
65	The digital ID was specified as the empty string.
66	No authorized users are defined for this digital ID.
67	The method executed successfully. There are *n* authorized users for the specified digital ID.

getListOfDigitalId

Syntax

getListOfDigitalId(*&array_digitalIDs*)

Description

Use the getListOfDigitalId method to return the list of all digital IDs defined in the certification store.

Parameters

&array_digitalIDs Specifies an already instantiated array of string to store the returned list of digital IDs.

Returns

A return code as a numeric value:

Numeric Value	*Description*
0	The method executed successfully.
64	No digital IDs are defined in the certification store.

Example

```
&arrIds = CreateArrayRept("", 0);
&errCode = &secStore.getListOfDigitalId(&arrIds);
```

getListOfSigner

Syntax

getListOfSigner(*&array_signers*)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the getListOfSigner method to return the list of all signers defined in the certification store.

Parameters

&array_signers Specifies an already instantiated array of string to store the returned list of signers.

Returns

A return code as a numeric value:

Numeric Value	*Description*
0	The method executed successfully.
72	No signers are defined in the certification store.

getSignerByDigitalId

Syntax

getSignerByDigitalId(*digital_ID, &signer*)

Description

Use the getSignerByDigitalId method to return the ID of the signer for the specified digital ID.

Parameters

digital_ID Specifies the digital ID for the certificate as a string value.

&signer Specifies an already instantiated string variable to store the returned signer's ID.

Returns

A return code as a numeric value:

Numeric Value	*Description*
0	The method executed successfully.
65	The digital ID was specified as the empty string.
71	No signer is defined for this digital ID.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

isDigitalCertValid

Syntax

isDigitalCertValid(*digital_ID*)

Description

Use the isDigitalCertValid to determine whether the digital ID is valid.

Parameters

digital_ID	Specifies the digital ID as a string value.

Returns

A Boolean value.

DigitalCertStore Class Properties

The properties in this section are described in alphabetical order.

ErrorMessageDetail

Description

Use this property to return the detailed error message as a string.

Note: This property is effectively read-only.

ErrorMessageSet

Description

Use this property to return the defined message set number as a number value. This property should always return the value: 136.

Note: This property is effectively read-only.

Understanding the IPDFSignature Interface Class

If the signer of the report needs to be determined dynamically at report run time (for example, the signer is to be determined based on the report data), then a custom application class based on the IPT_PDFSIGNATURE_INT:IPDFSignature interface must be used. However, if the report signer and digital certificate are known at report design time, then the certificate ID (referred to as the digital ID or

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

signature ID) can be specified in the psxp_signature_digitalID field in the report definition. In this case, there is no need to implement a custom application class.

Consider these situations when determining whether to create a custom implementation of the IPT_PDFSIGNATURE_INT:IPDFSignature interface class:

- If the psxp_signature_digitalID field has a value, BI Publisher for PeopleSoft can use this value as the digital ID; therefore, you do not need to implement a custom application class.
- If a digital signature will be applied to the PDF report and the psxp_signature_digitalID field has no value, you must specify a a custom implementation of the IPT_PDFSIGNATURE_INT:IPDFSignature interface class in the psxp_signature_appclass field.
- If you specify a value for both psxp_signature_digitalID and psxp_signature_appclass, the value of psxp_signature_digitalID is ignored and your application class will be used to determine the digital ID.

When you create an implementation of the IPT_PDFSIGNATURE_INT:IPDFSignature interface, you need your application class to return which digital ID is to be used for signing a specific report. When you implement this interface:

1. You must not set any of the four properties that are set for you by BI Publisher for PeopleSoft. These are: OperatorId, ProcessInstance, ReportId, and secStore.
2. In addition, you must not set two other properties that BI Publisher for PeopleSoft may set for you: KeyFieldNames and KeyFieldValues.

   Those properties are populated from XML report file data as arrays of string when the report's psxp_signature_mapfields field has a value. Use those arrays to determine the signer for the specified report or report instance. In the case of a bursted report with a different signer for each instance, BI Publisher for PeopleSoft will call your application class separately for each report instance with these properties set to values specific to the report instance.
3. You must complete implementations of the interface's two abstract methods:
   - Implement getSignatureId to return the digital ID for the certificate that is to be used to sign a specific report.

     See getSignatureIdfor an example implementation.
   - Implement getErrorString to return a detailed error message to BI Publisher for PeopleSoft.

     See getErrorString for more information and an example.
4. You must provide a value for the UseSameSignatureForBursting read-only property to indicate whether to use the same signer for bursted instances of this report.

   See UseSameSignatureForBursting for an example of a technique to implement this.
5. You must provide the full path to your application class by specifying the psxp_signature_appclass field on the Global Properties page—for example:

   ```
   MY_CUSTOM_PACKAGE:MY_SignedPDF
   ```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Important! If both the psxp_signature_appclass field and the psxp_signature_digitalID field are set, the psxp_signature_digitalID field is ignored.

The following example shows just the class definition block of an example implementation of an application class named My_SignedPDF:

```
class My_SignedPDF implements IPT_PDFSIGNATURE_INT:IPDFSignature
   /* inputs */
   property string ReportId; /* report Id that requires digital signature */
   property string OperatorId; /* operator ID who runs a report */
   property number ProcessInstance; /* Process Scheduler Process Instance */
   property array of string KeyFieldNames; /* an array of field names that contain ⇒
key data */
   property array of string KeyFieldValues; /* an array of field values that contai⇒
n key data */
   property PT_SECURITY_DIGITALCERTSTORE:DigitalCertStore secStore; /* Security App⇒
 class used to get Digital Certificates info from Security storage */

   /* outputs */
   property boolean UseSameSignatureForBursting get; /* If true the same signature ⇒
 will be reused for all bursted instances */
   method My_SignedPDF(); /* Constructor */
   method getSignatureId() Returns string; /* Signature Authority ID to be used for⇒
 signing a report */
   method getErrorString() Returns string; /* An error string, if any */

private
   instance string &m_errorStr;
   instance number &m_ErrorMessageSet;
   instance Boolean &mb_ReuseSignature;
end-class;
```

Related Links

"Defining Global Properties" (PeopleTools 8.54: BI Publisher for PeopleSoft)

"Understanding Applying Digital Signatures to PDF Report Output" (PeopleTools 8.54: Security Administration)

IPDFSignature Class Methods

The methods in this section are described in alphabetical order.

getErrorString

Syntax

getErrorString()

Description

Implement the getErrorString method to return a detailed error message to BI Publisher for PeopleSoft. A detailed error message can be internal to your implementation of the getSignatureId method or one that is passed back from an invocation of a PT_SECURITY_DIGITALCERTSTORE:DigitalCertStore method.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Note: This is an abstract method.

Parameters

None.

Returns

A String value.

Example

During execution of the getSignatureId method, the &m_errorStr instance variable is set to the message catalog entry corresponding to any error returned from invocations of DigitalCertStore methods. For example:

```
If ... Then
   &m_errorStr = MsgGet(&m_ErrorMessageSet, 64, "### Not able to retrieve a list of⇒
 digital IDs.");
End-If;
```

Then, this &m_errorStr instance variable is set as the return value for the getErrorString method:

```
method getErrorString
   /+ Returns String +/
   /+ Extends/implements IPT_PDFSIGNATURE_INT:IPDFSignature.getErrorString +/
   Return &m_errorStr;
end-method;
```

Related Links

ErrorMessageSet

ErrorMessageDetail

getSignatureId

Syntax

getSignatureId()

Description

Implement the getSignatureId method to return the digital ID for the certificate that is to be used to sign a specific report. In this context, the certificate's digital ID is also referred to as the *signature ID*.

Note: This is an abstract method.

Use the six input properties set by BI Publisher for PeopleSoft to determine who is the signer of the specific report instance. In particular, the KeyFieldNames and KeyFieldValues arrays contain values that pertain to the specific report instance. Use methods of PT_SECURITY_DIGITALCERTSTORE:DigitalCertStore (accessed through the secStore property) to obtain information on certificates, signers, digital IDs, and authorized users defined in the certification store.

For example, use the following methods to determine digital IDs and signers:

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- getDigitalIdBySigner
- getListOfDigitalId
- getListOfSigner

Use the OperatorId property and the following methods to determine whether the current user (the operator) is authorized to produce a report signed by this signer:

- getListOfAuthorizedUsers
- getListOfAuthorizedRoleNames

Finally, use the isDigitalCertValid method to determine whether a specific certificate in the certification store is valid.

Parameters

None.

Returns

A String value.

Example

The following example implementation is incomplete in that it does not include the application logic that would determine the actual report signer, the digital IDs that can be used by that signer, or which of those digital IDs to use to sign this report. These determinations depend on specific business rules and requirements. However, once the signer and a digital ID are determined, this example invokes the getListOfDigitalId method to determine whether the specified digital ID exists in the certification store. If that check is successful, then this digital ID is returned as the ID for the certificate to be used to sign the report.

```
method getSignatureId
   /+ Returns String +/
   /+ Extends/implements IPT_PDFSIGNATURE_INT:IPDFSignature.getSignatureId +/

  /* DigitalCertStore instance (&secStore) is provided by BI Publisher, so this part
 is not required */
  If &secStore = Null Then
      &secStore = create PT_SECURITY_DIGITALCERTSTORE:DigitalCertStore();
      If &secStore = Null Then
         &m_errorStr = "Cannot create an instance of
 PT_SECURITY_DIGITALCERTSTORE:DigitalCertStore.";
         Return "";
      End-If;
   End-If;
   &m_ErrorMessageSet = &secStore.ErrorMessageSet;

   Local string &psw, &digitalID, &retrievedID, &sOutDestination, &certPath;
   Local array of string &arrIds;
   Local number &errCode, &i;

   &digitalID = "";

   /* Insert the application logic to determine the report signer and his or her  */
   /* certificate IDs (digital IDs) here. For this example, the signer is assumed */
   /* to be Joe Doe, and the digital ID retrieved for this user is "JoeDoe".      */

   &retrievedID = "JoeDoe";
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
   /* Determine whether this digital ID is in the digital certification store. */
   &arrIds = CreateArrayRept("", 0);
   &errCode = &secStore.getListOfDigitalId(&arrIds);
   If &errCode > 0 Then
      &m_errorStr = &secStore.ErrorMessageDetail;
      Return "";
   End-If;

   If &arrIds.Len = 0 Then
      &m_errorStr = MsgGet(&m_ErrorMessageSet, 64, "### Not able to retrieve a list of
 digital IDs.");
      Return "";
   End-If;

   For &i = 1 To &arrIds.Len
      If &arrIds [&i] = &retrievedID Then
         &digitalID = &retrievedID;
         Return &digitalID;
      End-If;
   End-For;

   &m_errorStr = MsgGet(&m_ErrorMessageSet, 71, "### Not able to retrieve signer fo⇒
r this digital ID", &retrievedID);
   Return "";
end-method;
```

Related Links

DigitalCertStore Class Methods

IPDFSignature Class Properties

IPDFSignature Class Properties

The properties in this section are described in alphabetical order.

KeyFieldNames

Description

Use this property to retrieve an array of string representing key field names to be used to determine the signing authority for the report. These key field names are set by BI Publisher for PeopleSoft.

Note: This property is effectively read-only.

Example

```
For &i = 1 To &KeyFieldNames.Len
   WriteToLog(%ApplicationLogFence_Level1, "&KeyFieldNames[ " | String(&i) | "]: " ⇒
| &KeyFieldNames [&i]);
End-For;
For &i = 1 To &KeyFieldValues.Len
   WriteToLog(%ApplicationLogFence_Level1, "&KeyFieldValues[ " | String(&i) | "]: "⇒
 | &KeyFieldValues [&i]);
End-For;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

KeyFieldValues

Description

Use this property to retrieve an array of string representing key field values to be used to determine the signing authority for the report. These key field values are set by BI Publisher for PeopleSoft.

Note: This property is effectively read-only.

Example

```
For &i = 1 To &KeyFieldNames.Len
   WriteToLog(%ApplicationLogFence_Level1, "&KeyFieldNames[ " | String(&i) | "]: " ⇒
| &KeyFieldNames [&i]);
End-For;
For &i = 1 To &KeyFieldValues.Len
   WriteToLog(%ApplicationLogFence_Level1, "&KeyFieldValues[ " | String(&i) | "]: "⇒
 | &KeyFieldValues [&i]);
End-For;
```

OperatorId

Description

Use this property to retrieve a string representing the current user ID as set by BI Publisher for PeopleSoft.

Note: This property is effectively read-only.

ProcessInstance

Description

Use this property to retrieve a number representing the process ID as set by BI Publisher for PeopleSoft.

Note: This property is effectively read-only.

ReportId

Description

Use this property to retieve a string representing the report ID as set by BI Publisher for PeopleSoft.

Note: This property is effectively read-only.

secStore

Description

Use this property to retrieve the DigitalCertStore object instantiated by BI Publisher for PeopleSoft.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Note: This property is effectively read-only.

UseSameSignatureForBursting

Description

Use this property to return a Boolean value indicating whether to use the same signature if this is a bursted report.

Important! This property has been identified as one of the values to be output by your implementation of the interface. However, the property is also defined as read-only, and therefore cannot be set or assigned directly. See the following code excerpt on how to set the value of a private instance variable to be returned as the value of this property.

Example

UseSameSignatureForBursting is defined as read-only, and therefor cannot be set directly. However, as demonstrated in the following code excerpt, you can define a private instance variable. In the following example, &mb_ReuseSignature is set to True or False as needed within the application logic. Then, a **get** definition is used to return the value of &mb_ReuseSignature as the value for the UseSameSignatureForBursting property.

```
class My_SignedPDF implements IPT_PDFSIGNATURE_INT:IPDFSignature
...

   property boolean UseSameSignatureForBursting get; /* If true the same signature ⇒
 will be reused for all bursted instances */
...

private
...

   instance Boolean &mb_ReuseSignature;
end-class;
...

/**************** Application logic ****************/
Rem if signer is the same for all bursted instances;
If <some_condition> Then
   &mb_ReuseSignature = True;
Else
   Rem if signer is different and depends on some bursted reports values;
   &mb_ReuseSignature = False;
End-If;
/**************** Application logic ****************/
...

get UseSameSignatureForBursting
   /+ Returns Boolean +/
   /+ Extends/implements IPT_PDFSIGNATURE_INT:IPDFSignature.UseSameSignatureForBurs⇒
ting +/
   Return &mb_ReuseSignature;
end-get;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

BI Publisher Classes Example

The following example provides a complete example of the code first, then goes through the program line by line.

Generating and Publishing a Report

In the following example, a report is created from an existing report definition. It is populated with an already instantiated and populated XmlDoc object, then published.

The following is the complete code sample: the steps explain each line.

```
import PSXP_RPTDEFNMANAGER:ReportDefn;

Local string &sFileName = "c:\path\filename.xml";
Local string &rptDefnId = "Financial";
Local string &LanguageCode = "ENG";
Local date &effdt = Date(20090821);
Local string &outputfmt = "HTM";

Local string &folderName = "General";
Local string &serverName = "PSNT";
Local PSXP_RPTDEFNMANAGER:ReportDefn &rptDefn;

&rptDefn = create PSXP_RPTDEFNMANAGER:ReportDefn(&rptDefnId);
&rptDefn.Get();
&rptDefn.SetRuntimeDataXMLFile(&sFileName);
&rptDefn.ProcessReport("", &languageCd, &effdt, &outputfmt);

&rptDefn.Publish(&serverName, "", &folderName, &PID);
```

To generate and publish a report:

1. Import the appropriate application class.

   Because this program generates and publishes a report, you need to import the report manager definition class.

   ```
   import PSXP_RPTDEFNMANAGER:ReportDefn;
   ```

2. Initialize variables.

   The variable declaration strings not only specify values for the variables, but give them type and scope as well. This can be very useful when debugging.

   ```
   Local string &sFileName = "c:\path\filename.xml";
   Local string &rptDefnId = "Financial";
   Local string &LanguageCode = "ENG";
   Local date &effdt = Date(20090821);
   Local string &outputfmt = "HTM";

   Local string &folderName = "General";
   Local string &serverName = "PSNT";
   Local PSXP_RPTDEFNMANAGER:ReportDefn &rptDefn;
   ```

3. Instantiate the report definition object and initialize it.

   After you instantiate a report definition object, you must initialize it and populate it using the Get method.

   ```
   &rptDefn = create PSXP_RPTDEFNMANAGER:ReportDefn(&rptDefnId);
   ```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
&rptDefn.Get();
```

4. Specify the data for the report.

   This report uses an XML file as the data source, so you must specify the runtime data source for the report before you process it.

```
&rptDefn.SetRuntimeDataXMLFile(&sFileName);
```

5. Process the report.

   You must process the report, generate a version of it for the report repository, before you can distribute the report.

```
&rptDefn.ProcessReport("", &languageCd, &effdt, &outputfmt);
```

6. Publish the report.

   After you've generated the report, you may want to publish it to another location.

```
&rptDefn.Publish(&serverName, "", &folderName, &PID);
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Chapter 12

BPEL Classes

Understanding the BPEL Classes

Use the Business Process Execution Language (BPEL) classes for launching, as well as controlling, a BPEL process instance. A BPEL process instance is associated with a service operation, that is, a message transaction, such as an outbound asynchronous message. You must have first created the service operation using PeopleSoft Pure Internet Architecture pages. When you define the service operation you specify the node used for connecting to the third-party system, as well as the routings used by the messages, and so on.

Related Links

"Integrating with Third-Party Systems" (PeopleTools 8.54: Integration Broker)

"Understanding Integrating with BPEL Processes" (PeopleTools 8.54: Integration Broker)

Scope of the BPEL Classes

The BPEL classes can be instantiated only from PeopleCode.

The BPEL classes can be called from a component, an internet script, Integration Broker, or an Application Engine program.

BPEL classes can be of Local, Global, or Component scope.

Data Types of the BPEL Classes

Every BPEL class is its own data type. That is, the class of BPELUtil is declared as type BPELUtil, and so on.

The following are the data types of the BPEL classes:

- AsyncFFSend
- BPELUtil
- IBUtil

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

How to Import the BPEL Classes

The BPEL classes are *not* built-in classes, like rowset, field, record, and so on. They are application classes. Before you can use these classes in your PeopleCode program, you must import them to your program.

An import statement names either all the classes in a package or one particular application class. For importing the BPEL classes, PeopleSoft recommends that you import all the classes in the application package.

The application package PT_BPEL contains the BPEL classes that you will use:

- AsyncFFSend
- BPELUtil
- IBUtil

The import statement you should use is as follows:

```
import PT_BPEL:*;
```

Using the asterisks after the package name makes all the application classes directly contained in the named package available. Application classes contained in subpackages of the named package are *not* made available.

Related Links

Understanding Application Classes

How to Create a BPEL Object

After you've imported the BPEL classes, you instantiate an object of one of those classes using the constructor for the class and the Create function.

The following example creates a new instance of the BPELUtil class, as the variable &MyBU, with local scope:

```
import PT_BPEL:*;

Local BPELUtil &MyBU = Create BPELUtil();
```

Related Links

BPEL Classes Constructors

BPEL Classes Constructors

You must use the constructor for each class to instantiate an instance of that class. The following are the constructors for the BPEL classes.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

AsyncFFSend

Syntax

AsyncFFSend()

Description

Use the AsyncFFSend constructor to instantiate an AsyncFFSend object.

Parameters

None.

Returns

A reference to an AsyncFFSend object.

Related Links

AsyncFFSend Class

BPELUtil

Syntax

BPELUtil()

Description

Use the BPELUtil constructor to instantiate a BPELUtil object.

Parameters

None.

Returns

A reference to a BPELUtil object.

Related Links

BPELUtil Class

IBUtil

Syntax

IBUtil()

Description

Use the IBUtil constructor to instantiate an IBUtil object.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

None.

Returns

A reference to an IBUtil object.

Related Links

IBUtil Class

AsyncFFSend Class

This class provides the application handler used when an asynchronous one way operation is called from the local system. This class extends the integration broker ISend class OnRequestSend method.

Related Links

"Understanding Sending and Receiving Messages" (PeopleTools 8.54: Integration Broker)

AsyncFFSend Class Method

This section describes the AsyncFFSend class method OnRequestSend.

OnRequestSend

Syntax

OnRequestSend(*&Msg*)

Description

Use the OnRequestSend method to implement the integration broker ISend class OnRequestSend method.

This method is generally used to associate the WSA_MessageID when making an asynchronous one way request to the BPEL process so that it can be tracked.

Parameters

&Msg	Specify an already populated and instantiated message object.

Returns

A message object.

Related Links

"Understanding Sending and Receiving Messages" (PeopleTools 8.54: Integration Broker)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

BPELUtil Class

This class provides the utility methods to interact with BPEL processes.

BPELUtil Class Methods

This section discusses the BPELUtil class methods, in alphabetical order.

GetASyncBPELProcessInstanceUrl

Syntax

GetASyncBPELProcessInstanceUrl(*TransactionID*)

Description

Use the GetASyncBPELProcessInstanceUrl method to return the complete URL that can be used to monitor an asynchronous BPEL process instance. The URL can be used to access the BPEL monitor for this particular BPEL process instance.

Parameters

TransactionID	Specify the transaction ID for the asynchronous BPEL process instance that you want to monitor.

Returns

A string containing a complete URL if successful, a Null or invalid string otherwise.

Related Links

GetSyncBPELProcessInstanceUrl

GetBPELProcessBrowserUrl

Syntax

GetBPELProcessBrowserUrl(*NodeName*)

Description

Use the GetBPELProcessBrowserUrl to return a complete URL of the WSIL process browser. It can be used to discover all the web services that are being hosted by the given BPEL domain.

Parameters

NodeName	Specify the name of the node associated with the BPEL process that you want to access, as a string.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

A string containing the complete URL if successful, an invalid URL string otherwise.

GetOperationType

Syntax

GetOperationType(*OperationName*)

Description

Use the GetOperationType method to return the type of the specified operation.

Parameters

OperationName Specify the name of the operation for which you want to determine the type, as a string.

Returns

A string containing the operation type. Valid values are:

Value	*Description*
S	The operation type is synchronous.
A	The operation type is asynchronous.
Null	There is an error in the method execution.

GetSyncBPELProcessInstanceUrl

Syntax

GetSyncBPELProcessInstanceUrl(*NodeName, MessageID*)

Description

Use the GetSyncBPELProcessInstanceUrl method to return the complete URL that can be used to monitor the specified synchronous BPEL process instance.

Parameters

NodeName Specify the node name associated with the synchronous BPEL process instance, as a string.

MessageID Specify the message ID associated with the external system for this BPEL process instance, as a string.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

A string containing a complete URL if successful, an invalid URL otherwise.

Related Links

GetASyncBPELProcessInstanceUrl

LaunchASyncBPELProcess

Syntax

LaunchASyncBPELProcess(*operationName*, *&Msg*, *Username*, *Password*)

Description

Use the LaunchASyncBPELProcess method to invoke an asynchronous BPEL process.

Parameters

OperationName	Specify the name of the operation associated with the asynchronous BPEL process that you want to start, as a string.
&Msg	Specify an already instantiated and populated message object that is created from the message definition that is associated with the asynchronous BPEL process.
Username	*Username* and *Password* are used to override the security credentials that are sent by default by Integration Broker when invoking a secure BPEL process (a web service.) If you specify an empty string, the Integration Broker credentials are used. If you specify a value, it's sent as part of the security credentials of the BPEL process.
Password	*Username* and *Password* are used to override the security credentials that are sent by default by Integration Broker when invoking a secure BPEL process (a web service.) If you specify an empty string, the Integration Broker credentials are used. If you specify a value, it's sent as part of the security credentials of the BPEL process.

Returns

A string that contains the transaction ID of the published message if successful, a Null string otherwise.

Related Links

LaunchSyncBPELProcess

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

LaunchSyncBPELProcess

Syntax

LaunchSyncBPELProcess(*operationName, &Msg, Username, Password*)

Description

Use the LaunchSyncBPELProcess method to invoke a synchronous BPEL process.

Parameters

OperationName	Specify the name of the operation associated with the synchronous BPEL process that you want to start, as a string.
&Msg	Specify an already instantiated and populated message object that is created from the message definition that is associated with the synchronous BPEL process.
Username	*Username* and *Password* are used to override the security credentials that are sent by default by Integration Broker when invoking a secure BPEL process (a web service.) If you specify an empty string, the Integration Broker credentials are used. If you specify a value, it's sent as part of the security credentials of the BPEL process.
Password	*Username* and *Password* are used to override the security credentials that are sent by default by Integration Broker when invoking a secure BPEL process (a web service.) If you specify an empty string, the Integration Broker credentials are used. If you specify a value, it's sent as part of the security credentials of the BPEL process.

Returns

A message object populated with the reply message if successful, a Null object otherwise.

Related Links

LaunchASyncBPELProcess

UpdateConnectorResponseProperties

Syntax

UpdateConnectorResponseProperties(*&Msg*)

Description

Prior to sending the response message, use this method to update the connector properties for an asynchronous PeopleSoft request/response web service that is consumed by a BPEL process. Among several connector property changes that it makes, this method adds a “content-type” connector property of “text/xml.”

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Note: The UpdateConnectorResponseProperties method is not required with Oracle BPEL Process Manager 10.1.2 or earlier supported versions of Oracle BPEL Process Manager; however, it can be used with those versions.

Parameters

&Msg The message object to be sent to the BPEL process as the response of an asynchronous PeopleSoft request/response web service.

Returns

None

Example

The following sample handler PeopleCode program processes requests for an asynchronous PeopleSoft request/response web service. A call is made to UpdateConnectorResponseProperties just before sending the response.

```
import PS_PT:Integration:INotificationHandler;
import PT_BPEL:BPELUtil;

class InboundASyncResponseHandler implements PS_PT:Integration:INotificationHandler
   method OnNotify(&MSG As Message);
end-class;

method OnNotify
   /+ &MSG as Message +/
   /+ Extends/implements PS_PT:Integration:INotificationHandler.OnNotify +/
   Local PT_BPEL:BPELUtil &bpel;
   Local Message &response;
   Local string &payload;
   Local XmlDoc &xml;
   Local File &MYFILE;
   &bpel = create PT_BPEL:BPELUtil();
   &payload = "<?xml version='1.0'?><PSFTCalcResponseMessage  xmlns='http://xmlns.o⇒
racle.com/Enterprise/Tools/schemas/PSFTCALCRESPONSEMESSAGE.V1'><result xmlns='' >9</⇒
result></PSFTCalcResponseMessage>";
   &xml = CreateXmlDoc(&payload);
   &response = CreateMessage(Operation.PSFTASYNCCALCULATE, %IntBroker_Response);
   &response.SetXmlDoc(&xml);
   &response.IBInfo.WSA_MessageID = &MSG.IBInfo.WSA_MessageID;
   &response.IBInfo.WSA_ReplyTo = &MSG.IBInfo.WSA_ReplyTo;
   &bpel.UpdateConnectorResponseProperties(&response);
   %IntBroker.Publish(&response);
end-method;
```

IBUtil Class

The IBUtil class provides the utility methods to access integration broker metadata.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

IBUtil Class Methods

This section discusses the BPELUtil class methods, in alphabetical order.

GetBPELConsoleUrl

Syntax

GetBPELConsoleUrl(*NodeName*)

Description

Use the GetBPELConsoleUrl method to return the BPEL console URL.

A transaction ID is an internal identifier for the message that is published. A message ID is the external ID that is used by the external system for identifying the transaction. The transaction ID is appended to the URL generated by this method. This concatenated URL is used to monitor the BPEL process instance.

Use the GetMessageId method to return the message ID.

Parameters

NodeName	Specify the name of the node associated with the BPEL process that you want to monitor.

Returns

A string containing a complete URL if successful, Null otherwise.

Related Links

GetMessageId

GetBPELDomain

Syntax

GetBPELDomain(*Nodename*)

Description

Use the GetBPELDomain method to determine the name of the domain of the specified node. This is used to construct the URL for accessing a BPEL process instance.

Parameters

Nodename	Specify the name of the node that you want to determine the domain for, as a string.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

A string containing the domain if successful, Null otherwise.

GetMessageId

Syntax

GetMessageId(*TransactionId*)

Description

Use the GetmessageId method to return the message ID used to monitor a BPEL process instance.

A transaction ID is an internal identifier for the message that is published. A message ID is the external ID that is used by the external system for identifying the transaction.

Parameters

TransactionId	Specify the transaction ID associated with the BPEL process instance that you want to monitor, as a string.

Returns

A string containing the message ID, Null otherwise.

Related Links

GetBPELConsoleUrl

GetNode

Syntax

GetNode(*MessageId*)

Description

Use the GetNode method to return the node name of the node involved in processing of the message.

Parameters

MessageId	Specify the message ID associated with the BPEL process instance that you want to get the node for, as a string.

Returns

A string containing the node name if successful, Null otherwise.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GetNumberOfRoutings

Syntax

GetNumberOfRoutings(*ServiceOperationName*)

Description

Use the GetNumberOfRoutings method to return the number of routings for the specified service operation.

Parameters

ServiceOperationName	Specify the name of the service operation that you want to discover the number of routings for, as a string.

Returns

A number.

GetStatus

Syntax

GetStatus(*TransactionId*)

Description

Use the GetStatus method to return the status of the Integration Broker process specified by the transaction Id.

Parameters

TransactionId	Specify the transaction ID for the BPEL process instance that you want to check the status of, as a string.

Returns

A string containing the status, Null otherwise.

GetTransactionId

Syntax

GetTransactionId(*MessageID*)

Description

Use the GetTransactionId method to return the transaction ID from the message. You must use the Publish or SyncRequest method on the message before you use this method.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

MessageID	Specify the message ID associated with the BPEL process instance, as a string.

Returns

A string containing the transaction ID associated with the published message, Null otherwise.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Chapter 13

Business Interlink Class

Understanding Business Interlink Class

The PeopleSoft Business Interlink framework provides a gateway for PeopleSoft applications to the services of any external system. This framework enables any PeopleSoft component (that is, a page, an Application Engine program, and so on) to integrate with any external system in near real-time and batch modes.

This framework enables a PeopleCode program to map the input and outputs of a Business Interlink definition to PeopleCode variables and record fields, then, using an Interlink object, call the Interlink plug-in, which in turn calls the external system, passes the information to the external system, and returns values to the PeopleCode program.

This documentation describes only the Interlink object portion of the PeopleSoft Business Interlink framework.

Each Interlink object is based on a Business Interlink definition, which is created in Application Designer. An Interlink object can be based on only a single Business Interlink definition.

Note: PeopleSoft Business Interlinks is a deprecated product. The Business Interlinks class currently exists for backward compatibility only. For new integrations, use Integration Broker instead.

Related Links

Understanding Message Classes

Using the Interlink Object

After you instantiate an Interlink object, use the Interlink object to:

- Populate the input buffer
- Send the data to the Interlink plug-in (by using the Execute method)
- Fetch the outputs from the buffer
- Check for status and error messages

After the Business Interlink object is instantiated, you can assign values from constants, PeopleSoft variables, or record fields to the inputs of that Business Interlink object.

When you execute the Business Interlink object, it loads the appropriate Business Interlink Plug-in and passes itself to that Business Interlink Plug-in. The Business Interlink Plug-in processes the input data,

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

passing the input values of the Business Interlink object to the external system and then fills the output values of the Business Interlink object (if there are outputs).

Deciding Which Methods to Use

After you create your Business Interlink definition, you must use PeopleCode to instantiate an Interlink object and execute the Business Interlink plug-in. This PeopleCode can be long and complex. Rather than write it directly, you can drag and drop the Business Interlink definition from the Application Designer Project View into an open PeopleCode edit pane. Application Designer analyzes the definition and generates initial PeopleCode as a template, which you can modify.

In this section, we discuss how to:

- Execute the Business Interlink object.
- Support batch input and output.
- Support rowsets.
- Use the flat table methods.
- Support dynamic output.
- Use hierarchical data (BIDocs).

Related Links

Understanding Business Interlink Class

Executing the Business Interlink Object

In most cases, you must use the Execute method to execute the Business Interlink object. However, for bulk input, you can use the BulkExecute method instead.

The Execute and BulkExecute methods return a value you can use for status and error checking.

Supporting Batch Input and Output

The methods discussed in this section, except for BulkExecute, add input values to the Business Interlink object one set, or row, at a time. The call to the Business Interlink Plug-in occurs only once. All the input data is passed with the single Execute. All output is returned as batch as well. The methods then get the output values one set, or row, at a time.

If you're sending a large amount of data to the input buffers, instead of adding one input row at a time, you might write the data to a staging table, then use the BulkExecute method. This method automatically executes; that is, you don't have to use the Execute method. It also automatically fills the output record specified with the method with all the output values in every row in the output buffer if you've specified an output record.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Supporting Rowsets

If your data is mapped into rowsets, you may want to use the InputRowset method. This method takes a standard rowset object to populate the inputs for the Business Interlink object. You can use the FetchIntoRowset method to repopulate the rowset with new data.

Using the Flat Table Methods

If your data is in a flat table structure, you can use the flat table methods. AddInputRow adds rows of input to the Business Interlink object; FetchNextRow fetches rows of output from the Business Interlink object.

Supporting Dynamic Output

A Business Interlink can have dynamic output, meaning that the outputs for a Business Interlink object are changeable in data type or number of outputs.

Business Interlinks supplies a set of methods to support dynamic output. These methods enable you to interrogate the output buffer programmatically to determine the number of fields (columns), their types, and their values.

The following methods support dynamic output:

- GetFieldCount
- GetFieldType
- GetFieldValue
- MoveFirst
- MoveNext

Use the MoveFirst method to move to the first column, first row of the output buffer, and within a loop, use the MoveNext method to move to each row on the output buffer.

Within a MoveFirst (or MoveNext) loop, use the GetFieldCount method to get the number of columns in the output buffer, which is also the number of outputs for this Business Interlink object. Then you can extract the outputs from the buffer in a loop.

Within the GetFieldCount loop, use GetFieldName to get the name of the output, GetFieldValue to get the value of the output (which will be returned as a string), and GetFieldType to get the type of the output (if the output is not a string type, you will convert it to this type).

See GetFieldCount, GetFieldType, GetFieldValue, MoveFirst, MoveNext.

Using Hierarchical Data (BIDocs)

A Business Interlink can have hierarchical data. Think of the structure as a tree, with a root doc, node docs, and values. The hierarchical data methods and objects are also referred to as BIDocs.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Input Structures

The following shows an example of an input structure:

Image: Example input structure

This example illustrates the fields and controls on the Example input structure. You can find definitions for the fields and controls later on this page.

The *root doc* is Calculate Cost(Domestic). A root doc can contain both values and node docs.

The *node docs* are From, To, Package_Info and Account_Info_List. Each node can contain both values and child nodes. Node docs can be further described as either:

- *Simple node docs* have only one set of values for a single instance of a root doc. From, To, Package_Info are all simple node docs.
- *List node docs* can contain more than one set of values for a single instance of a root doc. Account_Info_List is a list node doc.

The values in the From node are OriginCountry, OriginPostal_Code, and Ship_Date. The value within the root node is input_param1. Notice that there are values both within the root doc and within node docs.

Business Interlinks support hierarchical input structures with the following methods:

- GetInputDocs
- AddDoc
- AddValue
- AddNextDoc

The GetInputDocs method returns a reference to the root doc of an input structure. From the previous example, it returns a reference to Calculate Cost(Domestic).

Use the AddDoc method to access the node docs. From the previous example, you would use AddDoc to access the From, To, Package_Info, and Account_Info_List node docs. If any of these nodes contained nodes, you could use AddDoc to access those as well.

Use the AddValue method to set values. From the previous example, you would use AddValue to set the value for input_param1, OriginCountry, OriginPosta_Code, and Ship_date. You must call AddDoc on a node before you can call AddValue for its values.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Use the AddNextDoc method to access the following:

- If a node doc is a list, that is, it can contain more than one set of values, use AddNextDoc to reference the next set of values.
- To add another copy of the entire input structure, use AddNextDoc to return a reference to the next root doc.

The following code example sets values for the node doc From, which is a simple node doc. It also sets the values for Account_Info_List, which is a list node doc.

```
&Calc_Input = &QE_COST.GetInputDocs("");

&FromDoc = &Calc_Input.AddDoc("From");
&ret = &FromDoc.AddValue("OriginCountry", "United States");
&ret = &FromDoc.AddValue("OriginPostal_Code", &ORIGIN);
&ret = &FromDoc.AddValue("Ship_Date", &SHIPDATE);

&Account_Doc = &Calc_Input.AddDoc("Account_Info_List");
&ret = &Account_Doc.AddValue("Account_Number", "CT-8001");
&ret = &Account_Doc.AddValue("Meter_Number", &METER);
&ret = & Account_Doc.AddValue("Service_Type", &MODE);

/* add next set of values in list */

&ret = &Calc_Input.AddNextDoc();
&ret = &Account_Doc.AddValue("Account_Number", "CT-8002");
&ret = &Account_Doc.AddValue("Meter_Number", &METER);
&ret = &Account_Doc.AddValue("Service_Type", &MODE);
```

Output Structures

The following shows an example of an output structure:

Image: Example output structure

This example illustrates the fields and controls on the Example output structure. You can find definitions for the fields and controls later on this page.

The *root doc* is Calculate Cost(Domestic).

The *node docs* are Service_Rate and output_param2_List. Each node can contain both values and child nodes. Node docs can be further be described as either:

- *Simple node docs* have only one set of values for a single instance of a root doc. Service_Rate is a simple node doc.
- *List node docs* can contain more than one set of values for a single instance of a root doc. output_param2_List is a list node doc.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The values in the Service_Rate node are Service_Type, Rate, and in the output_param2_List node, output_member1 and output_member2, and within the root node, output_param1.

Business Interlinks support hierarchical output structures with the following methods:

- GetOutputDocs
- GetDoc
- GetNextDoc
- GetPreviousDoc
- GetStatus
- GetValue
- GetCount
- MoveToDoc

The GetOutputDocs method returns a reference to the root doc of an output structure. From the previous example, it returns a reference to Calculate Cost(Domestic).

Use the GetDoc method to access node docs. From the previous example, you would use GetDoc to access the Service_Rate or output_param2_List node docs. If any of these nodes contain nodes, you use GetDoc to access those as well.

Use the GetValue method to retrieve the values. From the previous example, you would use GetValue to retrieve the values for output_param1, and for the Service_Rate node, to get the values Service_Type, Rate, output_member1, and output_member2. You must call GetDoc on a node before you can call GetValue for its values.

Use the GetNextDoc (or GetPreviousDoc) method to access the following:

- A reference to the next (or previous, respectively) root doc.
- If a node doc is a list, that is, can contain more than one set of values, use GetNextDoc to reference the next node doc in the list (or GetPreviousDoc to access the previous node doc in the list.)

Use the GetCount method to return either the number of docs in a list node doc, or the number of root docs. In the example, you can count the number of Calculate Cost(Domestic) nodes or the number of output_param2_list nodes.

Use the MoveToDoc method to move to a particular doc at the root level or to a list node doc. In the example, you can move to a Calculate Cost(Domestic) node or to an output_param2_list_node.

The following code example gets values for the node docs Service Rate, which is a simple node doc. It also sets the values for output_param2_List, which is a list node doc.

```
&Calc_Input = &QE_COST.GetOutputDocs("");

&Service_Rate_Doc = &Calc_Input.GetDoc("Service_Rate");
&ret = &Service_Rate_Doc.GetValue("Service_Type", "Overnight");
&ret = &Service_Rate_Doc.GetValue("Rate", "50.00");

&Out_Param_Doc = &Calc_Input.GetDoc("output_param2_List");
&ret = &Out_Param_Doc.GetValue("output_member1", "value1");
&ret = &Out_Param_Doc.GetValue("output_member2", "value2");
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
/* get next set of values in list */

&Account_Doc = &Out_Param_Doc.AddNextDoc();
&ret = &Out_Param_Doc.GetValue("output_member1", "value3");
&ret = &Out_Param_Doc.GetValue("output_member2", "value4");
```

Using the Incoming Business Interlink Methods and Properties

The incoming Business Interlink methods enable you to parse an XML request and build an XML response.

The incoming Business Interlink uses a set of methods and functions.

The GetContentBody Request object method converts the request content into an XML string. You can then use this string with the GetBiDoc function to create a BiDocs structure from it that is the same shape and contains the same data as the XML document contained in the XML string.

After you have the BiDocs structure containing the XML request, you can:

- Use the GetNode method to get one of the XML elements.
- Use the NodeType method to get the type of the node (element, processing instruction, comment).
- Use the NodeName property to get the name of the element.
- Use the NodeValue property to get the value of the element.

You can also use the standard BiDocs methods (such as GetDoc, GetValue) to retrieve information from this BiDocs object.

When an XML element contains attributes, the AttributeCount property gets the number of attributes, the GetAttributeName method gets the name of an attribute, and the GetAttributeValue method gets the value of an attribute.

To build an XML response, you can use the GetBiDocs function to create a blank BiDocs structure. To create the XML structure within that BiDocs, use CreateElement to create an XML tag, AddComment to add an XML comment, AddAttribute to add an attribute to an XML tag, and AddProcessInstruction to add a processing instruction (the first tag of the XML response).

Use the GenXMLString method to create an XML string from the BiDocs structure. Then you can use the Write Response method to write the response to the HTTP response string.

Related Links

Understanding Business Interlink Class

Understanding the State of an Interlink Object

PeopleSoft Business Interlink API that are run on the application server should be stateless, that is, if you want to save information from one call of the Interlink object to the next, you have to do it yourself by writing the relevant information to the database. If you use the Execute method more than once within

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

a single PeopleCode event (that is, if you have the Execute method in some sort of loop) the state is preserved. After you leave the event, any state associated with the Interlink object is lost.

You should create only one Business Interlink object, that is, you should only use the GetInterlink function once. After that, you can load it with data, pass the data to the Interlink plug-in (using Execute) and fetch output data as many times as you need.

Using Business Interlink with Application Engine

In a regular PeopleCode program, you can only declare a Business Interlink object as local. However, in an Application Engine program, you can declare a Business Interlink object as global. Instantiating a Business Interlink object once as a global saves on the significant overhead of reinstantiating a local object for every iteration of PeopleCode called in a loop.

- Global Business Interlink objects can only be used in Application Engine PeopleCode programs because PeopleCode that runs on an application server must be stateless.
- When a restartable Application Engine program abends, global Business Interlink objects that were instantiated before the last checkpoint are automatically reinstantiated at restart. So the object will be available, even though no call has been made to GetInterlink in the restarted process. However, the associated Business Interlink data buffers are *not* recovered, so the Application Engine program must be written such that these buffers are empty whenever a checkpoint is taken.
- Business Interlink objects should *not* be declared as global unless they are used in several PeopleCode actions, or in a PeopleCode action that is called in a loop. Only in these instances is the overhead of doing a checkpoint worthwhile.

Using the Data Type of a Business Interlink Object

You should declare a Business Interlink object using the data type Interlink. For example,

```
Local Interlink &MYBI;
```

Declare hierarchical data as type BIDocs. For example:

```
Local BIDocs &OutlistDoc;
```

Note: BIDocs and Interlink objects used in PeopleCode programs run on the application server can be declared only as type Local. You can declare Interlinks as Global only in an Application Engine program.

Understanding the Scope of a Business Interlink Object

A Business Interlink object can be instantiated from PeopleCode.

This object can be used anywhere you have PeopleCode, that is, in an application class, Application Engine PeopleCode, record field PeopleCode, and so on.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Business Interlink Class Built-in Functions

"GetBiDoc" (PeopleTools 8.54: PeopleCode Language Reference)

"GetInterlink" (PeopleTools 8.54: PeopleCode Language Reference)

Business Interlink Class Methods

In this section, we discuss the Business Interlink class methods. The methods are discussed in alphabetical order.

AddDoc

Syntax

AddDoc(*docname*)

Description

The AddDoc method adds a document to an input structure. The added document is an input parameter for a Business Interlink object that is not of simple type (such as integer or string). You must add the document to the input structure before you can add values to its members with AddValue.

Parameters

docname	The name of the document that AddDoc adds to the structure.

Returns

The document added to the BIDocs input document.

Example

In the following example, the input structure for Calculate Cost, or the root level document, is created with the GetInputDocs method. (To create, or add, more input structures, use AddNextDoc.) The Calculate Cost input parameter From is a document, so the AddDoc method adds it to the input document.

```
Local Interlink &QE_COST;
Local BIDocs &CalcCostIn;
Local BIDocs &FromDoc, &ToDoc, &PackageDoc, &AccountDoc;
Local number &ret, &retinput;


&QE_COST = GetInterlink(Interlink.QE_COST_EX);

&CalcCostIn = &QE_COST.GetInputDocs("");

&ret = &CalcCostIn.AddValue("input_param1","value");
&FromDoc = &CalcCostIn.AddDoc("From");
&ret = &FromDoc.AddValue("OriginCountry", "United States");
&ret = &FromDoc.AddValue("OriginPostal_Code", &ORIGIN);
&ret = &FromDoc.AddValue("Ship_Date", &SHIPDATE);
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
/* Call AddDoc and AddValue for To, Package_Info, and Account_Info_List (code not s⇒
hown) */
```

Image: Example input structure

The following shows the input structure for this example. It contains five input parameters: input_param1, From, To, Package_Info, and Account_Info_List. This is a version of the Federal Express plug-in that was modified for this example (input_param1 was added, Account_Info was modified to be a list).

Related Links

GetInputDocs
AddValue
AddNextDoc

AddInputRow

Syntax

AddInputRow(*inputname, value*)

where *inputname* and *value* are in matched pairs, in the form:

inputname1, *value1* [*, inputname2, value2*] . . .

Description

The AddInputRow method adds a row of input data (*value*) from PeopleCode variables or record fields for the Business Interlink object executing the method. These must be entered in matched pairs, that is, every input name must be followed by its matching value.

Note: The input *name*, not the input path, of the interface definition is used for this method.

There must be an input name for every input parameter defined in the interface definition used to instantiate the Business Interlink object.

If you specify a record field that is not part of the record the PeopleCode program is associated with, you must use *recname..fieldname* for that value.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

You can specify default values for every input name in the interface definition (created in Application Designer.) These values are used if you create a PeopleCode "template" by dragging the interface definition from the Project window in Application Designer to an open PeopleCode editor window.

Parameters

inputname Specify the input name. There must be one *inputname* for every input name defined in the interface definition used to instantiate the Business Interlink object.

value Specify the value for the input name. This can be a constant, a variable, or a record field. Each *value* must be paired with an *inputname*.

Returns

A Boolean value: True if the input values were successfully added. Otherwise, it returns False.

Example

In the following example, the Business Interlink object name is SRA_ALL_1, and the input name, such as ship_site_name, are being bound to record fields, such as QE_RP_SITENAME or VENDOR_INFO.QE_RP_PROMISEDATE, to variables like &PARTNAME, or to literals, like 10 for quantity.

```
&SRA_ALL_1.AddInputRow("ship_site_name", QE_RP_SITENAME,
   "promise_date", VENDOR_INFO.QE_RP_PROMISEDATE,
   "request_date", QE_RP_ORDERREQDATE,
   "subline_site_name", QE_RP_SITENAME,
   "quantity", 10,
   "part_name", &PARTNAME,
   "site_name", INV_LOCATIONS.QE_RP_SITENAME);
```

Related Links

Execute

"GetInterlink" (PeopleTools 8.54: PeopleCode Language Reference)

AddNextDoc

Syntax

AddNextDoc()

Description

The AddNextDoc method adds a document to one of the following levels:

- The root level of the input structure for a Business Interlink object. You create a reference to this level with the GetInputDocs method.
- When a document within the input structure is a list, AddNextDoc adds another document to the list. If you use AddNextDoc on a document that is not a list, AddNextDoc fails and returns an error.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

None.

Returns

This method returns an integer. The values are:

Value	*Description*
0	eNoError. The method succeeded.
1	eNO_DOCUMENT. The document referenced by this method does not exist.
2	eDOCLIST_OUT_RANGE. You tried to access a document in a list, but the document list is out of range. For example, if a document list contains five documents, and then you call GetDoc/GetOutputDocs once, you can call GetNextDoc four times; the fifth time results in this error.
3	eDOCUMENT_UNINITIALIZED. Internal error.
4	eNOT_DOCUMENTTYPE. You tried to perform an operation upon a parameter that is not a document type.
5	eNOT_LISTTYPE. You tried to perform a GetNextDoc or AddNextDoc upon a document that is not a list.
7	eNOT_BASICTYPE. You tried to perform a GetValue or AddValue upon a parameter that is not of basic type: Integer, Float, String, Time, Date, DateTime.
8	eNO_DATA. You tried to retrieve data from a document that contained no data.

Example

In this example, the input structure for Calculate Cost, or the root level document, is accessed with the GetInputDocs method. The AddNextDoc method adds another BIDocs input document. The Calculate Cost input parameter Account_Info_List is a document, so the AddDoc method adds it to the BIDocs input document. Account_Info_List is also a document list, so AddNextDoc method adds another Account_Info_List document.

```
Local Interlink &QE_COST;
Local BIDocs &CalcCostIn;
Local BIDocs &FromDoc, &ToDoc, &PackageDoc, &AccountDoc;
Local number &ret, &retinput;


&QE_COST = GetInterlink(Interlink.QE_COST_EX);

&CalcCostIn = &QE_COST.GetInputDocs("");

For &n = 1 to &number_of_input_sets
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
/* Get values for inputs, such as &ORIGIN (code not shown) */

   &ret = &CalcCostIn.AddValue("input_param1","value");
   &FromDoc = &CalcCostIn.AddDoc("From");
   &ret = &FromDoc.AddValue("OriginCountry", "United States");
   &ret = &FromDoc.AddValue("OriginPostal_Code", &ORIGIN);
   &ret = &FromDoc.AddValue("Ship_Date", &SHIPDATE);

   /* Call AddDoc and AddValue for To and Package_Info
      (code not shown) */

   /* Call AddDoc and AddNextDoc for the AccountDoc document list */
   &AccountDoc = &CalcCostIn.AddDoc("Account_Info_List");
   For &m = 1 to &number_of_AccountDocs
      &ret = &AccountDoc.AddValue("Account_Number", &ACCOUNT);
      &ret = &AccountDoc.AddValue("Meter_Number", &METER);
      &ret = &AccountDoc.AddValue("Service_Type", &SVCTYPE);
      &retinput = &AccountDoc.AddNextDoc();
   End-For; &retinput = &CalcCostIn.AddNextDoc();

End-For;

&retinput = &To.AddNextDoc();
```

Image: Example input structure

The following shows the input structure for this example. It contains five input parameters: input_param1, From, To, Package_Info, and Account_Info_List.

From, To, and Package_Info are not lists, so if you try to use AddNextDoc with these parameters, such as the following line of code, AddNextDoc will fail and return an error message.

Related Links

GetInputDocs
AddDoc
AddValue

AddValue

Syntax

AddValue(*paramname, value*)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

The AddValue method adds a value to a member of a document within the input structure for a Business Interlink object.

Parameters

paramname The name of the member of the document that is having a value added to it.

value The value that is added. This can be a constant, a variable, or a record field. The data type can be String, Integer, Double, Float, Time, Date, or DateTime.

Returns

This method returns an integer. The values are:

Value	*Description*
0	eNoError. The method succeeded.
1	eNO_DOCUMENT. The document referenced by this method does not exist.
2	eDOCLIST_OUT_RANGE. You tried to access a document in a list, but the document list is out of range. For example, if a document list contains five documents, and then you call GetDoc/GetOutputDocs once, you can call GetNextDoc four times; the fifth time results in this error.
3	eDOCUMENT_UNINITIALIZED. Internal error.
4	eNOT_DOCUMENTTYPE. You tried to perform an operation upon a parameter that is not a document type.
5	eNOT_LISTTYPE. You tried to perform a GetNextDoc or AddNextDoc upon a document that is not a list.
7	eNOT_BASICTYPE. You tried to perform a GetValue or AddValue upon a parameter that is not of basic type: Integer, Float, String, Time, Date, DateTime.
8	eNO_DATA. You tried to retrieve data from a document that contained no data.

Example

In the following example, the Business Interlink object name is QE_COST.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

In the following example, the input structure for Calculate Cost, or the root level document, is accessed with the GetInputDocs method. (To create, or add, more input structures, use AddNextDoc.) The Calculate Cost input parameter From is a document, so the AddDoc method adds it to the input structure. Then the AddValue method adds values to each of the From document members.

```
Local Interlink &QE_COST;
Local BIDocs &CalcCostIn;
Local BIDocs &FromDoc, &ToDoc, &PackageDoc, &AccountDoc;
Local number &ret;

&QE_COST = GetInterlink(Interlink.QE_COST_EX);

/* Get some values for input, such as &ORIGIN (code not shown) */

&CalcCostIn = &QE_COST.GetInputDocs("");
&ret = &CalcCostIn.AddValue("input_param1","value");

&FromDoc = &CalcCostIn.AddDoc("From");
&ret = &FromDoc.AddValue("OriginCountry", "United States");
&ret = &FromDoc.AddValue("OriginPostal_Code", &ORIGIN);
&ret = &FromDoc.AddValue("Ship_Date", &SHIPDATE);

/* Call AddDoc, AddValue for Package, Account_Info_List, and also call AddNextDoc f⇒
or Account_Info_List (code not shown) */
```

Image: Example input structure

The following shows the input structure for this example. It contains five input parameters: input_param1, From, To, Package_Info, and Account_Info_List.

Related Links

GetInputDocs

AddDoc

AddNextDoc

BulkExecute

Syntax

BulkExecute(**RECORD.***inputrecname* [, **RECORD.***outputrecname*] [, {*user_process_inst* | *user_operid*}])

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

The BulkExecute method uses the data in the specified record to populate the input buffer, copying like-named fields. Then the method executes, and, optionally, fills the record specified by outputrecname with data from the Business Interlink output buffer. BulkExecute results in significantly faster performance for transactions that process large amounts of data. Instead of adding one input row at a time, then fetching the values one at a time, you might write the data to a staging table, use the BulkExecute method and then read the data from the output table. This would be especially effective in Application Engine programs that process sets of data rather than individual rows.

This method assumes that the names of the fields in the record match the names of the inputs (or outputs) defined in the Business Interlink Definition. If there is no field in the *inputrecname* for a Business Interlink input parameter, the parameter's default value is used. If no default is specified, an empty string is passed. You must ensure that this default value is legitimate.

Fields in the output buffer are matched against the fields specified in the output record. You do not have to specify an output record. If you don't specify an output record, the output buffers are not be populated.

If you specify an output record, and if you have fields in the output record that are not specified as output parameters, they aren't populated with the BulkExecute method. In addition, they shouldn't be set as NOT NULL, otherwise inserts fail.

Note: Before you use this method, you should flush the record used for output and remove any residual data that might exist in it.

If you specify an output record, and you want to use the output record for error checking, you must add the following fields to your output record:

- RETURN_STATUS
- RETURN_STATUS_MSG

Note: The field names in the output record must match these names exactly.

Then you must mark one or more input parameters as "key fields" in the Business Interlink definition (using the BulkExecute ID check box.) The value of these key fields are copied to the output record, and you can use these fields to match error messages with input (or output) rows.

To order your input (and output) rows, you must add the BI_SEQ_NUM column to both the input and output table:

Note: The field name in your input and output records must match this name exactly.

The input rows are read in the order of numbers in BI_SEQ_NUM, and the output rows are generated using the same order number.

This method automatically executes, so you don't need to use the Execute method with this method.

Whether this method halts on execution depends on the setting of the StopAtError configuration parameter. The default value is True, that is, stop if the error number returned is something other than a 1 or 2. This configuration parameter must be set before using the BulkExecute method.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

RECORD.*inputrecname*

Specify a record (SQL table) that contains the data to populate the input buffer of the Business Interlink.

RECORD .*outputrecname*

Specify a record (SQL table) that will hold the data that populates the output buffer of the Business Interlink. This is optional; it is often used to error check the input.

user_process_inst* | *user_operid

This is an optional parameter that allows either different Application Engine programs or different clients to populate the same **RECORD.** *outputrecname* at the same time.

For *user_process_inst*, the parameter takes an integer. **RECORD.** *outputrecname* must have a PROCESS_INSTANCE field. The PROCESS_INSTANCE field is used to identify the Application Engine program that is using this Business Interlink. You can use the %PROCESS_INSTANCE variable to populate *user_process_inst*.

For *user_operid*, the parameter takes a string.**RECORD.** *outputrecname* must have an OPERID field. The OPERID field is used to identify the client who is using this Business Interlink. You can use the %OPERID variable to populate *user_operid*.

Returns

The following are the valid returns:

Value	*Description*
1	The Business Interlink object executes successfully
2	The Business Interlink object failed to execute
3	Transaction failed
4	Query failed
5	Missing criteria
6	Input mismatch
7	Output mismatch
8	No response from server
9	Missing parameter
10	Invalid username
11	Invalid password

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Value	*Description*
12	Invalid server name
13	Connection error
14	Connection refused
15	Timeout reached
16	Unequal lists
17	No data for output
18	Output parameters empty
19	Driver not found
20	Internet connect error
21	XML parser error
22	XML deserialize

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

Image: Example input record for BulkExecute

This image is an example of input record for BulkExecute. Here are two PeopleSoft records that could be used as input and output records for BulkExecute. The key fields in the input record, which need to have the BulkExecute ID check box checked in Application Designer, are QE_RP_PO_NUMBER and QE_RP_SITENAME. These key fields are used both for input and output.

Num	Field Name	Type	Len	Format	H	Short Name	Long Name
1	QE_RP_PO_NUMBER	Char	40	Mixed		QE_RP_PONUMBER	QE_RP_PONUMBER
2	QE_RP_PODATE	DtTm	26			QE_RP_PODATE	QE_RP_PODATE
3	QE_RP_SITENAME	Char	15	Mixed		SITE_NAME	SITE_NAME
4	QE_RP_VENDORNAME	Char	30	Mixed		QE_RP_VENDORNAM	QE_RP_VENDORNAME

Image: Example output record for BulkExecute

This image is an example of output record for BulkExecute.

Num	Field Name	Type	Len	Format	H	Short Name	Long Name
1	QE_RP_PO_NUMBER	Char	40	Mixed		QE_RP_PONUMBER	QE_RP_PONUMBER
2	QE_RP_SITENAME	Char	15	Mixed		SITE_NAME	SITE_NAME
3	RETURN_STATUS	Sign	3			RETURN_STATUS	RETURN_STATUS
4	RETURN_STATUS_MSG	Char	254	Mixed		RETURN_STAT_MSG	RETURN_STATUS_MSG

Image: Example Business Interlink inputs for BulkExecute

The following is an example of Business Interlink inputs for BulkExecute. Here are the corresponding inputs and outputs for a Business Interlink that has had its inputs and outputs renamed to match the field names in the records. The inputs and outputs have been renamed where necessary to match the record field names.

	Input Name	Input Path	Default	Data Typ	Attribute	BulkExec Id	Path Ir
1	class_name	class_name	Purchase_Or	string	required	☐	string
2	QE_RP_PODATE	order_date		string	required	☐	string
3	QE_RP_VENDORNAME	vendor_name		string	required	☐	string
4	QE_RP_PO_NUMBER	po_number		string	required	☒	string
5	QE_RP_SITENAME	site_name		string	required	☒	string

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Image: Example Business Interlink inputs for BulkExecute

The following image is an example of Business Interlink inputs for BulkExecute.

The PeopleCode program using these records could contain the following code to run BulkExecute.

```
Local Interlink &CREATE_PO;
Local number &EXECRSLT;

&CREATE_PO = GetInterlink(INTERLINK.QE_RP_CREATEPO1);

/* The next three lines set configuration parameters, which are not shown in the pr⇒
evious examples. */
&CREATE_PO.SERVER_NAME = "bc1";
&CREATE_PO.RSERVER_HOST = "4.3.4.3";
&CREATE_PO.RSERVER_PORT = "2200";

&EXECRSLT = &CREATE_PO.BulkExecute(RECORD.QE_RP_PO, RECORD.QE_RP_PO_OUT1);
```

Related Links

StopAtError

Clear

Syntax

Clear()

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

The Clear method clears the input and output buffers. If you're using Business Interlinks in a batch program, every time after you use the Execute method, use the Clear method to flush out the input and output buffers.

Parameters

None.

Returns

None.

Example

```
For &n = 1 to x
   &myinterlink.AddInputRow("input1", value1, "input2", value2);
   &myinterlink.Execute();
   &myinterlink.FetchNextRow("output1", value1, "output2", value2);
      /* do processing on data */
   &myinterlink.Clear();
   &n = &n + 1;
End-for;
```

Related Links

Execute

BulkExecute

Execute

Syntax

Execute()

Description

When an Interlink object executes the Execute method, the transaction associated with the Interlink object is executed.

If there is only one row, after appropriate substitution is made, the transaction is executed only once. Otherwise, the data is "batched up" and sent once. You have to call Execute only once to execute all the rows of the input buffer.

Generally, you would only use the Execute method after using the AddInputRow method. If you create a PeopleCode "template" by dragging the Business Interlink definition from the Project window in Application Designer to an open PeopleCode editor window, the usual order of the execution of methods is shown in the template.

If you're using Business Interlinks in a batch program, every time after you use the Execute method, use the Clear method to flush out the input and output buffers.

Whether this method halts on execution depends on the setting of the StopAtError configuration parameter. The default value is True, that is, stop if the error number returned is something other than a 1 or 2. This configuration parameter must be set *before* using the Execute method.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

None.

Returns

The following are the valid returns:

Value	*Description*
1	The Business Interlink object executes successfully
2	The Business Interlink object failed to execute
3	Transaction failed
4	Query failed
5	Missing criteria
6	Input mismatch
7	Output mismatch
8	No response from server
9	Missing parameter
10	Invalid username
11	Invalid password
12	Invalid server name
13	Connection error
14	Connection refused
15	Timeout reached
16	Unequal lists
17	No data for output
18	Output parameters empty
19	Driver not found
20	Internet connect error
21	XML parser error

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Value	*Description*
22	XML deserialize

Example

```
Local number &EXECRSLT;
.  .  .
&EXECRSLT = &SRA_ALL_1.Execute();
If (&EXECRSLT <> 1) Then
/* The instance failed to execute */
/* Do Error Processing */
End-If;
```

Related Links

BulkExecute

Clear

"GetInterlink" (PeopleTools 8.54: PeopleCode Language Reference)

FetchIntoRecord

Syntax

FetchIntoRecord(**RECORD.***recname*, [, {*user_process_inst* | *user_operid*}])

Description

The FetchIntoRecord method copies the data from the output buffer into the specified record (SQL table) copying *like-named* fields. This method assumes that the names of the fields in the record match the names of the outputs defined in the Business Interlink definition.

You can use the FetchIntoRecord method to perform a transaction on a large amount of data that you want to receive from your system. Instead of executing your Business Interlink and then fetching one output row at a time, you might execute your Business Interlink, then use the FetchIntoRecord method to write the data returned from the Business Interlink to a staging table.

Note: Before you use this method, you should flush the record used for output and remove any residual data that might exist in it.

If your data is hierarchical, that is, in a rowset, and you want to preserve the hierarchy, use FetchIntoRowset instead of this method.

To order your output rows, you must add the BI_SEQ_NUM column to the record.

This column is populated with a sequence number that corresponds to the order in which each row of the record was written to by the method.

Parameters

RECORD. ***recname*** Specify a record (SQL table) that you want to populate with data from the output buffers.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

user_process_inst* | *user_operid

This is an optional parameter that enables either different Application Engine programs or different clients to populate the same **RECORD.** *outputrecname* at the same time.

For *user_process_inst*, the parameter takes an integer. **RECORD.** *outputrecname* must have a PROCESS_INSTANCE field. The PROCESS_INSTANCE field is used to identify the Application Engine program that is using this Business Interlink. You can use the %PROCESS_INSTANCE variable to populate *user_process_inst*.

For *user_operid*, the parameter takes a string.**RECORD.** *outputrecname* must have an OPERID field. The OPERID field is used to identify the client who is using this Business Interlink. You can use the %OPERID variable to populate *user_operid*.

Returns

Number of rows fetched if one or more non-empty rows are returned.

If an empty row is returned, that is, every if field is empty except the return_status and return_status_msg fields, this method returns one of the following error messages:

Number	***Meaning***
0	No error
1	NoInterfaceObject
2	ParamCountError
3	IncorrectParameterType
4	NoColumnForOutputParm
5	NoColumnForInputParm
6	BulkInsertStartFailed
7	BulkInsertStopFailed
8	CouldNotCreateSelectCursor
9	CouldNotCreateInsertCursor
10	CouldNotDestroySelectCursor
11	CouldNotDestroyInsertCursor
12	InputRecordDoesNotExist

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Number	*Meaning*
13	OutputRecordDoesNotExist
14	ContainEmptyRow
15	SQLExecError
201	FieldTooLarge
202	IgnoreSignNumber
203	ConvertFloatToInt

Example

```
&RSLT = &QE_SM_CONCAT.FetchIntoRecord(RECORD.PERSONAL__VENDR_DATA);

If &RSLT = 0 Then
/* no rows fetched */
Else
   /* do processing */
End-If;
```

Related Links

BulkExecute

FetchIntoRowset

Syntax

FetchIntoRowset(*&Rowset*)

Description

The FetchIntoRowset method copies the data from the output buffer into the specified rowset, copying *like-named* fields. This method assumes that the names of the fields in the rowset match the names of the outputs defined in the Business Interlink definition, and that the structure is the same.

Note: Before you use this method, you should flush the rowset used for output and remove any residual data that might exist in it.

Use this method only if you have a hierarchical data structure and you want to preserve the hierarchy. Otherwise, use BulkExecute or FetchIntoRecord.

Parameters

&Rowset Specify rowset object that you want to populate with data from the output buffers. This must be an existing, instantiated rowset.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

Number of rows fetched if one or more non-empty rows are returned.

If an empty row is returned, that is, every if field is empty except the return_status and return_status_msg fields, this method returns one of the following error messages:

Value	*Description*
0	No error
1	NoInterfaceObject
2	ParamCountError
3	IncorrectParameterType
4	NoColumnForOutputParm
5	NoColumnForInputParm
6	BulkInsertStartFailed
7	BulkInsertStopFailed
8	CouldNotCreateSelectCursor
9	CouldNotCreateInsertCursor
10	CouldNotDestroySelectCursor
11	CouldNotDestroyInsertCursor
12	InputRecordDoesNotExist
13	OutputRecordDoesNotExist
14	ContainEmptyRow
15	SQLExecError
201	FieldTooLarge
202	IgnoreSignNumber
203	ConvertFloatToInt

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

Image: EMPLOYEE_CHECKLIST Page order

The following an image of EMPLOYEE_CHECKLIST Page order. The example uses the rowset on level one from the EMPLOYEE_CHECKLIST page. A PeopleCode program running in a field on level zero in that page can access the level one (child rowset).

	Lvl	Label	Type	Field	Record	Display Control	Related Display	Related Control
1	0	Frame	Frame			■	■	
2	0	Frame	Frame			☐	☐	
3	0	Frame	Frame			☐	☐	
4	0	Employee Name	Edit Box	NAME	PERSONAL_DATA	☐	☐	
5	0	ID	Edit Box	EMPLID	PERSONAL_DATA	☐	☐	
6	1	Checklist Item Tbl	Scroll Bar			☐	☐	
7	1	Checklist Sequen	Edit Box	CHECKLIST_SEQ	CHECKLIST_ITEM	☐	☐	
8	1	Scroll Bar 1	Scroll Bar			☐	☐	
9	1	Checklist Date	Edit Box	CHECKLIST_DT	EMPL_CHECKLIST	☐	☐	
10	1	derived_hr.effdt	Edit Box	EFFDT	DERIVED_HR	☐	☐	
11	1	Checklist	Edit Box	CHECKLIST_CD	EMPL_CHECKLIST	☑	☐	
12	1	Checklist Descript	Edit Box	DESCR	CHECKLIST_TBL	☐	☑	11
13	1	Responsible ID	Edit Box	RESPONSIBLE_ID	EMPL_CHECKLIST	☑	☐	
14	1	Responsible Nam	Edit Box	NAME	PERSONAL_DATA	☐	☑	13
15	1	Comment	Long Edit Box	COMMENTS	EMPL_CHECKLIST	☐	☐	
16	2	Scroll Bar 2	Scroll Bar			☐	☐	
17	2	Chklst Seq	Edit Box	CHECKLIST_SEQ	EMPL_CHKLST_ITM	☐	☐	
18	2	Chklst Itm	Edit Box	CHKLST_ITEM_CD	EMPL_CHKLST_ITM	☑	☐	
19	2	Briefing Descripti	Edit Box	DESCR	CHKLST_ITEM_TBL	☐	☑	18
20	2	Briefing Status	Drop Down List	BRIEFING_STATUS	EMPL_CHKLST_ITM	☐	☐	
21	2	Status Date	Edit Box	STATUS_DT	EMPL_CHKLST_ITM	☐	☐	

EMPL_CHECKLIST is the primary database record for the level one scrollbar on the EMPLOYEE_CHECKLIST page. The following PeopleCode accesses the level one rowset using EMPL_CHECKLIST. The Business Interlink object name is QE_BI_EMPL_CHECKLIST. This Business Interlink object uses the level one rowset as its input and its output.

The InputRowset method uses this rowset as input for QE_BI_EMPL_CHECKLIST. Then a blank duplicate of the rowset is created with CreateRowset, and then the output of QE_BI_EMPL_CHECKLIST is fetched into the blank rowset with FetchIntoRowset.

```
&MYROWSET = GetRowset(SCROLL.EMPL_CHECKLIST);
&ROWCOUNT = &QE_BI_EMPL_CHECKLIST.InputRowset(&MYROWSET);
&RSLT = &QE_BI_EMPL_CHECKLIST.Execute();
/* do some error processing */
&WorkRowset = CreateRowset(&MYROWSET);
&ROWCOUNT = &QE_BI_EMPL_CHECKLIST.FetchIntoRowset(&WorkRowset);

If &ROWCOUNT = 0 Then
/* do some error processing */
Else
   /* Process the rowset from QE_BI_EMPL_CHECKLIST. Check it for errors. */
   For &I = 1 to &WorkRowset.RowCount
      For &K = 1 to &WorkRowset(&I).RecordCount
         &REC = &WorkRowset(&I).GetRecord(&K);
         &REC.ExecuteEdits();
         For &M = 1 to &REC.FieldCount
            If &REC.GetField(&M).EditError Then
            /* there are errors */
            /* do other processing */
            End-If;
         End-For;
      End-For;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
   End-for;
End-if;
```

Related Links

InputRowset

"Understanding Data Buffer Access" (PeopleTools 8.54: PeopleCode Developer's Guide)

FetchNextRow

Syntax

FetchNextRow(*outputname, value*)

where *outputname* and *value* are in matched pairs, in the form:

outputname1, value1 [*, outputname2, value2*] . . .

Description

After the Business Interlink object executes the method Execute, the FetchNextRow method can be used to retrieve a row of output and store the values of the output name (*outputname*) *to* PeopleCode variables or record fields (*value*). These must be entered in matched pairs, that is, every output name must be followed by its matching value.

Note: The output *name,* not the output path of the interface definition is used for this method.

There must be an *outputname* for every output name defined in the interface definition used to instantiate the Business Interlink object.

If you specify a record field that is not part of the record the PeopleCode program is associated with, you must use *recname.fieldname* for that *value*.

You can specify default values for every output name in the interface definition (created in Application Designer.) These values are used if you create a PeopleCode "template" by dragging the interface definition from the Project window in Application Designer to an open PeopleCode Editor window.

Parameters

outputname	Specify the output name. There must be one *outputname* for every output name defined in the interface definition used to instantiate the Business Interlink object.
value	Specify the value for the output name. This can be a constant, a variable, or a record field. Each *value* must be paired with an *outputname*.

Returns

A Boolean value: True if the row of output parameters was fetched. Otherwise, it returns False.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

In the following example, the Business Interlink object name is SRA_ALL_1, and the output names, such as costs, are being bound to record fields, such as STR_COST.

```
&RSLT = &SRA_ALL_1.FetchNextRow("costs", &STR_COST,
          "unit_costs", &STR_UNIT_COST,
          "customer_ship_dates", &STR_SHIP_DATE,
          "quantities", &STR_QUANTITY,
          "so_numbers", &STR_SO_NUM,
          "so_names", &STR_SO_NAME,
          "line_numbers", &STR_LINE_NUM,
          "ship_sets", &STR_SHIP_SET,
          "customer_receipt_dates", &STR_RECPT_DATE);
```

Related Links

Execute

"GetInterlink" (PeopleTools 8.54: PeopleCode Language Reference)

GetCount

Syntax

GetCount(*docname*)

Description

The GetCount method returns the number of documents within a document list contained within an output structure for a Business Interlink object.

Parameters

docname	The name of the document list.

Returns

The number of documents in the list.

Example

In the following example, the output structure for Calculate Cost, or the root level document, is accessed with the GetOutputDocs method. The Calculate Cost output parameter output_param2_List is a document, so the GetDoc method gets it from the output structure. Because output_param2_List is a document list, GetCount gets the number of documents in the list.

```
Local Interlink &QE_COST;
Local number &count;
Local BIDocs &CalcCostOut;
Local BIDocs &OutlistDoc;
Local number &ret;

&QE_COST = GetInterlink(Interlink.QE_COST_EX);
/* Get inputs, execute. (code not shown) */

&CalcCostOut = &QE_COST.GetOutputDocs("");

/* Call GetValue for output_param1, call GetDoc, GetValue for
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
Service_Rate (code not shown) */

&OutlistDoc = &CalcCostOut.GetDoc("output_param2_List");
&count = &CalcCostOut.GetCount("output_param2_List");

&I = 0;
While (&I < &count)
   &ret = &OutlistDoc.GetValue("output_member1", &VALUE1);
   &ret = &OutlistDoc.GetValue("output_member2", &VALUE2);
   If &ret = 0 Then
      /* Process output values */
      &I = &I + 1;
      &retoutput = &OutlistDoc.GetNextDoc();
   End-If;
End-While;
```

Image: Example output structure

The following example shows the output structure for this example. It contains three output parameters: output_param1, Service_Rate, and output_param2_List.

GetDoc

Syntax

GetDoc(*docname*)

Description

The GetDoc method gets a document from an output structure. The document is an output parameter for a Business Interlink object that is not of simple type (such as integer or string). You must get the document from the output structure before you can get values from its members with GetValue.

You can call GetDoc using dot notation, to access documents that are "nested" within other documents. For example, the following accesses a document nested three levels deep:

```
&Docs3 = &CalcCostOut.GetDoc("Doc1.Doc2.Doc3");
```

Parameters

docname	The name of the document that GetDoc should get from the output structure.

Returns

A reference to the document received from the output structure.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

In the following example, the Output structure for Calculate Cost(Domestic), or the root level document, is created with the GetOutputDocs method. (To create, or get, more Output structures, call GetNextDoc.) The Calculate Cost output parameter Service_Rate is a document, so the GetDoc method gets it from the Output structure.

```
Local Interlink &QE_COST;
Local number &count;
Local BIDocs &CalcCostOut;
Local BIDocs &ServiceRateDoc;
Local number &ret;

&QE_COST = GetInterlink(Interlink.QE_COST_EX);
// Get inputs, execute. (code not shown)

&CalcCostOut = &QE_COST.GetOutputDocs("");
&ret = &CalcCostOut.GetValue("output_param1",&VALUE);
&ServiceRateDoc = &CalcCostOut.GetDoc("Service_Rate");
&ret = &ServiceRateDoc.GetValue("Service_Type", &SERVICE_TYPE);
&ret = &ServiceRateDoc.GetValue("Rate", &RATE);
/* Call GetDoc, GetValue, GetNextDoc for output_param2_List (code not shown) */
If &ret = 0 Then
   /* Process output values */
End-If;
```

Image: Example output structure

The following illustration shows the Output structure for this example. It contains three output parameters: output_param1, Service_Rate, and output_param2_List. This is a version of the Federal Express plug-in that was modified for this example (output_param1 and output_param2_List were added).

In the following example, GetDoc is used to access a document that is nested more deeply. To access a document that is more deeply nested, you can either call GetDoc for each nesting, or you can call GetDoc once using the nesting feature.

Calling GetDoc with the nesting feature:

```
Local Interlink &QE_4GETDOC;
Local BIDocs &CalcCostOut, &Docs3;
Local number &ret;

&QE_4GETDOC = GetInterlink(Interlink.QE_4GETDOC_EX);
// Get inputs, execute. (code not shown)

&CalcCostOut = &QE_4GETDOC.GetOutputDocs("");
&Docs3 = &CalcCostOut.GetDoc("Doc1.Doc2.Doc3");
&ret = &Docs3.GetValue("output_member3", &VALUE);
```

Calling GetDoc without the nesting feature:

```
Local Interlink &QE_4GETDOC;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
Local BIDocs &CalcCostOut, &Docs1, &Docs2, &Docs3;
Local number &ret;

&QE_4GETDOC = GetInterlink(Interlink.QE_4GETDOC_EX);
// Get inputs, execute. (code not shown)

&CalcCostOut = &QE_4GETDOC.GetOutputDocs("");
&Docs1 = &CalcCostOut.GetDoc("Doc1");
&Docs2 = &Docs1.GetDoc("Doc2");
&Docs3 = &Docs2.GetDoc("Doc3");
&ret = &Docs3.GetValue("output_member3", &VALUE);
```

Image: Example output structure with nested documents

The following image is an example of output structure with nested documents.

GetFieldCount

Syntax

GetFieldCount()

Description

Use the GetFieldCount method to support dynamic output. It returns the number of columns in the output buffer, which is the same as the number of outputs in each row of the output buffer.

Note: This method can also be used with hierarchical doc data.

Parameters

None.

Returns

The number of columns in the output buffer, which is the same as the number of outputs in each row of the output buffer.

Example

The following example moves to the first column, first field of the output buffer. The Repeat loop goes through every row in the output buffer. The For loop processes every field in every row.

```
If (&MYBI.MoveFirst()) Then
   Repeat
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
      For &I = 1 to &MYBI.GetFieldCount
         &TYPE = &MYBI.GetFieldType(&I);
         Evaluate &TYPE
         Where = 1
            /* do processing */
         .  .  .
         End-Evaluate;
      End-For;
   Until Not (&MYBI.MoveNext());
Else
   /* do error processing - output buffer not returned */
End-If;
```

Related Links

GetFieldType
GetFieldValue
MoveFirst
MoveNext
Using Hierarchical Data (BIDocs)

GetFieldType

Syntax

GetFieldType(*index*)

Description

Use the GetFieldType method to support dynamic output. It returns the type of field specified by *index*. You can use this method only after you have used the MoveFirst method: otherwise the system doesn't know where to start.

Note: This method can also be used with hierarchical doc data.

Parameters

index Specify the number of the field you want to find the type of.

Returns

A number indicating the type of the field. The values are:

Value	*Description*
1	String
2	Integer
3	Float
4	Boolean

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Value	*Description*
5	Date
6	Time
7	DateTime
8	Binary
9	Object

Example

In the following example, the Business Interlink object name is &MYBI. The example uses MoveFirst to move to the first row of the output buffer, and to the first column, or first field, in that row. The Repeat loop uses MoveNext to go through every row in the output buffer. The For loop processes every field in every row, using the GetFieldCount method to get the number of fields, or outputs, in the row. Within the For loop, GetFieldType gets the type of the field data (string, integer, and so on.)

```
/* Add inputs to the Business Interlink object, then call Execute
to execute the Business Interlink object.
You are then ready to get the outputs using the following code. */

If (&MYBI.MoveFirst()) Then
   Repeat
      For &I = 1 to &MYBI.GetFieldCount
         &TYPE = &MYBI.GetFieldType(&I);
         Evaluate &TYPE
         Where = 1
            &STRING_VARIABLE = &MYBI.GetFieldValue(&I);
         /* test for and process other field types */
         End-Evaluate;
      End-For;
   Until Not(&MYBI.MoveNext());
Else
   /* Process error - no output buffer */
End-If;
```

Related Links

GetFieldCount

GetFieldValue

MoveFirst

MoveNext

GetFieldValue

Syntax

GetFieldValue(*index*)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the GetFieldValue method to support dynamic output. It returns the value of the field specified by index. You can use this method only after you have used the MoveFirst method: otherwise the system doesn't know where to start.

Note: This method can also be used with hierarchical doc data.

Parameters

index	Specify the number of the field you want to find the value of.

Returns

A string containing the value of the field.

Example

In the following example, the Business Interlink object name is &MYBI. The example uses MoveFirst to move to the first row of the output buffer, and to the first column, or first field, in that row. The Repeat loop uses MoveNext to go through every row in the output buffer. The For loop processes every field in every row, using the GetFieldCount method to get the number of fields, or outputs, in the row. Within the For loop, GetFieldValue gets the value of the field data.

```
/* Add inputs to the Business Interlink object, then call Execute to execute
the Business Interlink object. You are then ready to get the
outputs using the following code. */

If (&MYBI.MoveFirst()) Then
   Repeat
      For &I = 1 to &MYBI.GetFieldCount
         &TYPE = &MYBI.GetFieldType(&I);
         Evaluate &TYPE
         Where = 1
            &STRING_VARIABLE = &MYBI.GetFieldValue(&I);
         /* test for and process other field types */
         End-Evaluate;
      End-For;
   Until Not(&MYBI.MoveNext());
Else
   /* Process error - no output buffer */
End-If;
```

Related Links

GetFieldCount

GetFieldType

MoveFirst

MoveNext

GetInputDocs

Syntax

```
GetInputDocs("")
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

The GetInputDocs method gets the top input document at the root level for a Business Interlink object. This is a hierarchical structure that contains the values for the inputs for this Business Interlink object. The methods that you use to put the input values into this document are the hierarchical data methods.

Parameters

A null string.

Returns

An input document. This is the document at the top of the root level of the input document for a Business Interlink object.

Example

```
Local Interlink &QE_COST;
Local BIDocs &CalcCostOut, &CalcCostIn;

&QE_COST = GetInterlink(Interlink.QE_COST_EX);
&CalcCostIn = &QE_COST.GetInputDocs("");

/* You can now insert the input values and execute the BI object */
```

Related Links

Using Hierarchical Data (BIDocs)

GetNextDoc

Syntax

GetNextDoc()

Description

The GetNextDoc method gets a document from one of the following levels:

- The root level of the Output structure for a Business Interlink object. This level was accessed with the GetOutputDocs method.
- When a document within the Output structure is a list, GetNextDoc gets another document from the list. If you use GetNextDoc on a document that is not a list, GetNextDoc fails and returns an error.

Parameters

None.

Returns

The following are the valid returns:

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Number	*Enum Value*	*Description*
0	eNoError	The method succeeded.
1	eNO_DOCUMENT	The document referenced by this method does not exist.
2	eDOCLIST_OUT_RANGE	You tried to access a document in a list, but the document list is out of range. For example, if a document list contains five documents, and then you call GetDoc/ GetOutputDocs once, you can call GetNextDoc four times; the fifth time results in this error.
3	eDOCUMENT_UNINITIALIZED	Internal error
4	eNOT_DOCUMENTTYPE	You tried to perform an operation upon a parameter that is not a document type.
5	eNOT_LISTTYPE	You tried to perform a GetNextDoc or AddNextDoc upon a document that is not a list.
7	eNOT_BASICTYPE	You tried to perform a GetValue or AddValue upon a parameter that is not of basic type: Integer, Float, String, Time, Date, DateTime.
8	eNO_DATA	You tried to retrieve data from a document that contained no data.

Example

In this example, the Output structure for Calculate Cost, or the root level document, is accessed with the GetOutputDocs method. The GetNextDoc method gets another Output structure, assuming that there is more than one of them. The Calculate Cost output parameter output_param2_List is a document, so the GetDoc method gets it to the Output structure. output_param2_List is also a document list, so GetNextDoc method gets the next output_param2_List document.

```
Local Interlink &QE_COST;
Local number &count1, &count2;
Local BIDocs &CalcCostOut;
Local BIDocs &OutlistDoc;
Local number &ret1, &ret2;

&QE_COST = GetInterlink(Interlink.QE_COST_EX);
// Get inputs, execute. (code not shown)

&CalcCostOut = &QE_COST.GetOutputDocs("");

&ret1 = 0;
While (&ret1)
   &ret1 = &CalcCostOut.GetValue("output_param1",&VALUE);
   &ServiceRateDoc = &CalcCostOut.GetDoc("Service_Rate");
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
   &ret1 = &ServiceRateDoc.GetValue("Service_Type", &SERVICE_TYPE);
   &ret1 = &ServiceRateDoc.GetValue("Rate", &RATE);
   /* Process output values */

   &OutlistDoc = &CalcCostOut.GetDoc("output_param2_List");
   &count2 = &CalcCostOut.GetCount("output_param2_List");
   While (&I < &count2)
      &ret2 = &OutlistDoc.GetValue("output_member1", &VALUE1);
      &ret2 = &OutlistDoc.GetValue("output_member2", &VALUE2);
      If &ret2 = 0 Then
         /* Process output values */
         &I = &I + 1;
         &ret2 = &OutlistDoc.GetNextDoc();
      End-If; &ret1 = &CalcCostOut.GetNextDoc();
End-While;
```

Image: Example output structure

The following shows the Output structure for this example. It contains three output parameters: output_param1, Service_Rate, and output_param2_List.

GetOutputDocs

Syntax

```
GetOutputDocs("")
```

Description

The GetOutputDocs method gets the top output document at the root level for a Business Interlink object. This is a hierarchical structure that contains the values for the outputs for this Business Interlink object. The methods that you use to get output values from this document are the hierarchical data methods.

Parameters

A null string.

Returns

An output document. This is the document at the top of the root level of the output document for a Business Interlink object.

Example

```
Local Interlink &QE_COST;
Local BIDocs &CalcCostIn, &CalcCostOut;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
&QE_COST = GetInterlink(Interlink.QE_COST_EX);

&CalcCostOut = &QE_COST.GetOutputDocs("");

/* You can now execute the Business Interlink object and get the output values. */
```

Related Links

Using Hierarchical Data (BIDocs)

GetPreviousDoc

Syntax

GetPreviousDoc()

Description

The GetPreviousDoc method gets the previous document from either the root level of the Output structure for a Business Interlink object, or from a document within the Output structure. When these documents are in a list, GetPreviousDoc gets the previous document in the list. You must get the document before you can get its values with GetValue.

Parameters

None.

Returns

The following are the possible returns:

Number	*Enum Value*	*Description*
0	eNoError	The method succeeded
1	eNO_DOCUMENT	The document referenced by this method does not exist.
2	eDOCLIST_OUT_RANGE	You tried to access a document in a list, but the document list is out of range. For example, if a document list contains five documents, and then you call GetDoc/GetOutputDocs once, you can call GetNextDoc four times; the fifth time results in this error.
3	eDOCUMENT_UNINITIALIZED	Internal error
4	eNOT_DOCUMENTTYPE	You tried to perform an operation upon a parameter that is not a document type.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Number	Enum Value	Description
5	eNOT_LISTTYPE	You tried to perform a GetNextDoc or AddNextDoc upon a document that is not a list.
7	eNOT_BASICTYPE	You tried to perform a GetValue or AddValue upon a parameter that is not of basic type: Integer, Float, String, Time, Date, DateTime.
8	eNO_DATA	You tried to retrieve data from a document that contained no data.

Example

In this example, the Output structure for Calculate Cost, or the root level document, is accessed with the GetOutputDocs method. It contains one output parameter, output_param2_List, which is also a list. The GetCount and MoveToDoc methods point to the last output_param2_List document in the list. The GetPreviousDoc method is used in a loop to cycle through the output_param2_List list, starting with the last and ending with the first in the list, and get each output_param2_List document and its values.

```
Local Interlink &QE_COST;
Local number &count;
Local BIDocs &CalcCostOut;
Local BIDocs &OutlistDoc;
Local number &ret;

&QE_COST = GetInterlink(Interlink.QE_COST_EX);
// Get inputs, execute. (code not shown)

&CalcCostOut = &QE_COST.GetOutputDocs("");

/* Call GetValue for output_param1, call GetDoc, GetValue for Service_Rate (code no⇒
t shown) */

&OutlistDoc = &CalcCostOut.GetDoc("output_param2_List");
&count = &CalcCostOut.GetCount("output_param2_List");
&ret = &OutlistDoc.MoveToDoc(&count-1);
&I = &count;
While (&I > 0)
   &ret = &OutlistDoc.GetValue("output_member1", &VALUE1);
   &ret = &OutlistDoc.GetValue("output_member2", &VALUE2);
   If &ret = 0 Then
      /* Process output values */
      &I = &I - 1;
      &retoutput = &OutlistDoc.GetPreviousDoc("");
   End-If;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
End-While;
```

Image: Example output structure

The following shows the Output structure for this example. It contains three output parameters: output_param1, Service_Rate, and output_param2_List.

GetStatus

Syntax

GetStatus()

Description

The GetStatus method tests the BIDocs document. To find the status for any BIDocs method that does not return a status value, call GetStatus just after you call that BIDocs method.

Parameters

None.

Returns

The following are the possible returns:

Number	*Enum Value*	*Description*
0	NoError	The method succeeded.
1	NO_DOCUMENT	The document referenced by this method does not exist.
2	LIST_OUT_RANGE	You tried to access a document in a list, but the document list is out of range. For example, if a document list contains five documents, and then you call GetDoc/GetOutputDocs once, you can call GetNextDoc four times; the fifth time results in this error.
3	DOCUMENT_UNINITIALIZED	Internal error.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Number	Enum Value	Description
4	NOT_DOCUMENTTYPE	You tried to perform an operation upon a parameter that is not a document type.
5	NOT_DOCUMENTLISTTYPE	You tried to perform a GetNextDoc or AddNextDoc upon a document that is not a list.
6	NOT_LISTTYPE	You tried to perform a list operation using GetValue, AddValue, on a non-list.
7	NOT_SINGLEBASICTYPE	You tried to perform a GetValue or AddValue upon a list that does not use a single basic type: Integer, Float, String, Time, Date, DateTime.
9	NO_DATA	You tried to retrieve data from a document that contained no data.
10	GENERIC_ERROR	There was an error with the transaction.

GetValue

Syntax

GetValue(*paramname, value*)

Description

The GetValue method gets a value from an output parameter within a document of the Output structure for a Business Interlink object.

Parameters

Paramname The name of the member of the document that is having a value retrieved from it.

Value The value that is retrieved. This can be a variable or a record field. The data type can be String, Integer, Double, Float, Time, Date, or DateTime.

Returns

The following are the possible return values:

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Return Status for Integer

Number	*Enum value and Meaning*
0	NoError. The method succeeded.
1	NO_DOCUMENT. The document referenced by this method does not exist.
9	NO_DATA. You tried to retrieve data from a document that contained no data.
10	GENERIC_ERROR. There was an error with the transaction.

Example

In the following example, the Business Interlink object name is QE_COST.

In the following example, the Output structure for Calculate Cost, or the root level document, is created with the GetOutputDocs method. (If you wanted to create, or get, more Output structures, you would call GetNextDoc.) The Calculate Cost output parameter Service_Rate is a document, so the GetDoc method gets it from the Output structure. Then the GetValue method gets values from each of the Service_Rate document members.

```
Local Interlink &QE_COST;
Local BIDocs &CalcCostOut;
Local BIDocs &ServiceRateDoc;
Local number &ret;

&QE_COST = GetInterlink(Interlink.QE_COST_EX);

// Get inputs, execute. (code not shown)

&CalcCostOut = &QE_COST.GetOutputDocs("");
&ret = &CalcCostOut.GetValue("output_param1",&PARAM1);

&ServiceRateDoc = &CalcCostOut.GetDoc("Service_Rate");
&ret = &ServiceRateDoc.GetValue("Service_Type", &SERVICE_TYPE);
&ret = &ServiceRateDoc.GetValue("Rate", &RATE);
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
/* Call GetDoc, GetValue, GetNextDoc for output_param2_List (code not shown) */
```

Image: Example output structure

The following illustration shows the Output structure for this example. It contains three output parameters: output_param1, Service_Rate, and output_param2_List. This is a version of the Federal Express plug-in that was modified for this example (output_param1 and output_param2_List were added).

InputRowset

Syntax

InputRowset(*&Rowset*)

Description

The InputRowset method uses the data in the specified rowset to populate the input buffer, copying *like-named* fields in the appropriate structure. This method assumes that the names of the fields in the rowset match the names of the inputs defined in the Business Interlink definition, and that the structure of both rowsets are the same.

Use this method only if you have a hierarchical data structure and you want to preserve the hierarchy. Otherwise, use BulkExecute or AddInputRow.

Parameters

&Rowset	Specify an existing, instantiated rowset object.

Returns

An optional value: the number of rows inserted into the output buffer.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

Image: EMPLOYEE_CHECKLIST Page structure

The example uses the rowset on level one from the EMPLOYEE_CHECKLIST page. A PeopleCode program running in a field on level zero in that panel can access the child rowset (level one), shown below from Scroll Bar 1 to Scroll Bar 2.

EMPLOYEE_CHECKLIST.ENG (Panel)

Panel Designer | Order

	Lvl	Label	Type	Field	Record	Display Control	Related Display	Related Control
1	0	Frame	Frame			■	■	
2	0	Frame	Frame			☐	☐	
3	0	Frame	Frame			☐	☐	
4	0	Employee Name	Edit Box	NAME	PERSONAL_DATA	☐	☐	
5	0	ID	Edit Box	EMPLID	PERSONAL_DATA	☐	☐	
6	1	Checklist Item Tbl	Scroll Bar			☐	☐	
7	1	Checklist Sequen	Edit Box	CHECKLIST_SEQ	CHECKLIST_ITEM	☐	☐	
8	1	Scroll Bar 1	Scroll Bar			☐	☐	
9	1	Checklist Date	Edit Box	CHECKLIST_DT	EMPL_CHECKLIST	☐	☐	
10	1	derived_hr.effdt	Edit Box	EFFDT	DERIVED_HR	☐	☐	
11	1	Checklist	Edit Box	CHECKLIST_CD	EMPL_CHECKLIST	☑	☐	
12	1	Checklist Descript	Edit Box	DESCR	CHECKLIST_TBL	☐	☑	11
13	1	Responsible ID	Edit Box	RESPONSIBLE_ID	EMPL_CHECKLIST	☑	☐	
14	1	Responsible Nam	Edit Box	NAME	PERSONAL_DATA	☐	☑	13
15	1	Comment	Long Edit Box	COMMENTS	EMPL_CHECKLIST	☐	☐	
16	2	Scroll Bar 2	Scroll Bar			☐	☐	
17	2	Chklst Seq	Edit Box	CHECKLIST_SEQ	EMPL_CHKLST_ITM	☐	☐	
18	2	Chklst Itm	Edit Box	CHKLST_ITEM_CD	EMPL_CHKLST_ITM	☑	☐	
19	2	Briefing Descripti	Edit Box	DESCR	CHKLST_ITEM_TBL	☐	☑	18
20	2	Briefing Status	Drop Down List	BRIEFING_STATUS	EMPL_CHKLST_ITM	☐	☐	
21	2	Status Date	Edit Box	STATUS_DT	EMPL_CHKLST_ITM	☐	☐	

EMPL_CHECKLIST is the primary database record for the level one scrollbar on the EMPLOYEE_CHECKLIST page. The following PeopleCode access the level one rowset using EMPL_CHECKLIST. The Business Interlink object name is QE_BI_EMPL_CHECKLIST. This Business Interlink object uses the level one rowset as its input and its output.

The InputRowset method uses this rowset as input for QE_BI_EMPL_CHECKLIST. Then a blank duplicate of the rowset is created with CreateRowset, and then the output of QE_BI_EMPL_CHECKLIST is fetched into the blank rowset with FetchIntoRowset.

```
&MYROWSET = GetRowset(SCROLL.EMPL_CHECKLIST);
&ROWCOUNT = &QE_BI_EMPL_CHECKLIST.InputRowset(&MYROWSET);
&RSLT = &QE_BI_EMPL_CHECKLIST.Execute();
/* do some error processing */
&WorkRowset = CreateRowset(&MYROWSET);
&ROWCOUNT = &QE_BI_EMPL_CHECKLIST.FetchIntoRowset(&WorkRowset);

If &ROWCOUNT = 0 Then
/* do some error processing */
Else
   /* Process the rowset from QE_BI_EMPL_CHECKLIST. Check it for errors. */
   For &I = 1 to &WorkRowset.RowCount
      For &K = 1 to &WorkRowset(&I).RecordCount
         &REC = &WorkRowset(&I).GetRecord(&K);
         &REC.ExecuteEdits();
         For &M = 1 to &REC.FieldCount
            If &REC.GetField(&M).EditError Then
            /* there are errors */
            /* do other processing */
            End-If;
         End-For;
      End-For;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
   End-for;
End-if;
```

Related Links

"Understanding Data Buffer Access" (PeopleTools 8.54: PeopleCode Developer's Guide)

FetchIntoRowset

MoveFirst

Syntax

MoveFirst()

Description

Use the MoveFirst method to support dynamic output. This method moves your cursor to the first column, first row of the output buffer. You must use this method before you try to access any data.

Parameters

None.

Returns

Boolean: True if successfully positioned cursor at the first column, first row of the output buffer, False otherwise.

Example

In the following example, the Business Interlink object name is &MYBI. The example uses MoveFirst to move to the first row of the output buffer, and to the first column, or first field, in that row. The Repeat loop uses MoveNext to go through every row in the output buffer. The For loop processes every field in every row, using the GetFieldCount method to get the number of fields, or outputs, in the row.

```
/* Add inputs to the Business Interlink object, then call Execute to execute the Bu⇒
siness Interlink object. You are then ready to get the outputs using the following ⇒
code. */

If (&MYBI.MoveFirst()) Then
   Repeat
      For &I = 1 to &MYBI.GetFieldCount
         &TYPE = &MYBI.GetFieldType(&I);
         Evaluate &TYPE
         Where = 1
            &STRING_VARIABLE = &MYBI.GetFieldValue(&I);
         /* test for and process other field types */
         End-Evaluate;
      End-For;
   Until Not(&MYBI.MoveNext());
Else
   /* Process error - no output buffer */
End-If;
```

Related Links

GetFieldCount

GetFieldType

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GetFieldValue
MoveNext

MoveNext

Syntax

MoveNext()

Description

Use the MoveNext method to support dynamic output. This method moves your cursor to the first column of the next row of the output buffer. You can use this method only after you have used the MoveFirst method: otherwise, the system doesn't know where to start.

Parameters

None.

Returns

Boolean: True if successfully positioned cursor at the next row of the output buffer, False otherwise.

Example

In the following example, the Business Interlink object name is &MYBI. The example uses MoveFirst to move to the first row of the output buffer, and to the first column, or first field, in that row. The Repeat loop uses MoveNext to go through every row in the output buffer. The For loop processes every field in every row, using the GetFieldCount method to get the number of fields, or outputs, in the row.

```
/* Add inputs to the Business Interlink object, then call Execute to execute the Bu⇒
siness Interlink object. You are then ready to get the outputs using the following ⇒
code. */

If (&MYBI.MoveFirst()) Then
   Repeat
      For &I = 1 to &MYBI.GetFieldCount
         &TYPE = &MYBI.GetFieldType(&I);
         Evaluate &TYPE
         Where = 1
            &STRING_VARIABLE = &MYBI.GetFieldValue(&I);
         /* test for and process other field types */
         End-Evaluate;
      End-For;
   Until Not(&MYBI.MoveNext());
Else
   /* Process error - no output buffer */
End-If;
```

Related Links

GetFieldCount
GetFieldType
GetFieldValue
MoveFirst

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

MoveToDoc

Syntax

MoveToDoc(*list_number*)

Description

Within a list of documents in the Output structure, the MoveToDoc method moves to the documents given by the parameter *list_number*. After using MoveToDoc, the GetValue method gets the values of the document that is in the *list_number*+1 location in the list.

Parameters

list_number The number indicating the document that MoveToDoc moves to. After using MoveToDoc, the GetValue method gets the values of the document that is in the *list_number*+1 location in the list. For example, if *list_number* is zero, then MoveToDoc moves to the first document in the list.

Returns

This method returns an integer. The values are:

Value	*Description*
0	eNoError. The method succeeded.
1	eNO_DOCUMENT. The document referenced by this method does not exist.
2	eDOCLIST_OUT_RANGE. You tried to access a document in a list, but the document list is out of range. For example, if a document list contains five documents, and then you call GetDoc/GetOutputDocs once, you can call GetNextDoc four times; the fifth time results in this error.
3	eDOCUMENT_UNINITIALIZED. Internal error.
4	eNOT_DOCUMENTTYPE. You tried to perform an operation upon a parameter that is not a document type.
5	eNOT_LISTTYPE. You tried to perform a GetNextDoc or AddNextDoc upon a document that is not a list.
7	eNOT_BASICTYPE. You tried to perform a GetValue or AddValue upon a parameter that is not of basic type: Integer, Float, String, Time, Date, DateTime.
8	eNO_DATA. You tried to retrieve data from a document that contained no data.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

The following example gets the values of the last document in the output_param2_List list. It uses GetCount to get the number of documents in the list, and then uses MoveToDoc to move to the last document in the list.

```
Local Interlink &QE_COST;
Local number &count;
Local BIDocs &CalcCostOut;
Local BIDocs &OutlistDoc;
Local number &ret;

&QE_COST = GetInterlink(Interlink.QE_COST_EX);
// Get inputs, execute. (code not shown)

&CalcCostOut = &QE_COST.GetOutputDocs("");
&OutlistDoc = &CalcCostOut.GetDoc("output_param2_List");
&count = &CalcCostOut.GetCount("output_param2_List");
&ret = &OutlistDoc.MoveToDoc(&count-1);
&ret = &OutlistDoc.GetValue("output_member1", &VALUE1);
&ret = &OutlistDoc.GetValue("output_member2", &VALUE2);
```

Image: Example output structure

The following illustration shows the Output structure for this example. It contains three output parameters: output_param1, Service_Rate, and output_param2_List. This is a version of the Federal Express plug-in that was modified for this example (output_param1 and output_param2_List were added).

ResetCursor

Syntax

ResetCursor()

Description

The ResetCursor method resets the cursor in the Output structure for a Business Interlink object to the top. After you call this method, the next time you call GetValue, you get an output value from the first document of the Output structures for a Business Interlink object.

Parameters

None.

Returns

None.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

The following code uses ResetCursor to reset the cursor in the Output structure to the top.

```
Local Interlink &QE_COST;
Local BIDocs &CalcCostOut;

&QE_COST = GetInterlink(Interlink.QE_COST_EX);

// Get inputs, execute. (code not shown)

&CalcCostOut = &QE_COST.GetOutputDocs("");

// Perform actions on the output documents (code not shown)

&CalcCostOut.ResetCursor();
```

Incoming Business Interlink Methods

This section describes the PeopleCode methods you use with Incoming Business Interlinks.

AddAttribute

Syntax

AddAttribute(*attributename*, *attributevalue*)

Description

The AddAttribute method adds an attribute name and its value to an XML element referenced by a BiDocs object.

Parameters

attributename	String. The name of the attribute.
attributevalue	String. The value of the attribute.

Returns

Number. The return status. NoError, or 0, means the method succeeded.

Example

Here is a set of XML response code.

```
<?xml version="1.0"?>
   <postreqresponse>
      <candidate>
         <user>
            <location scenery="great" density="low" blank="eh?">
            </location>
         </user>
      </candidate>
   </postreqresponse>
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Here is the PeopleCode that builds it.

```
Local BIDocs &rootDoc, &postreqresponse;
Local BIDocs &candidates, &location, &user;
Local number &ret;

&rootDoc = GetBiDoc("");
&ret = &rootDoc.AddProcessInstruction("<?xml version=""1.0""?>");
&postreqresponse = &rootDoc.CreateElement("postreqresponse");
&candidates = &postreqresponse.CreateElement("candidates");
&user = &candidates.CreateElement("user");
&location = &user.CreateElement("location");
&ret = &location.AddAttribute("scenery", "great");
&ret = &location.AddAttribute("density", "low");
&ret = &location.AddAttribute("blank", "eh?");
```

Related Links

GetStatus

AddComment

Syntax

AddComment(*comment*)

Description

The AddComment method adds an XML comment after the beginning tag of an XML element referenced by a BiDoc object.

Parameters

comment String. The comment.

Returns

Number. The return status. NoError, or 0, means the method succeeded.

Example

Here is a set of XML response code.

```
<?xml version="1.0"?>
   <postreqresponse>
      <error>
         <!--this is a comment line-->
         <errorcode>1</errorcode>
         <errortext></errortext>
      </error>
   </postreqresponse>
```

Here is the PeopleCode that builds it.

```
Local BIDocs &rootDoc, &postreqresponse, &error, &errorcode, &errortext;
Local string &blob;
Local number &ret;
&rootDoc = GetBiDoc("");

/* add a processing instruction*/
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
&ret = &rootDoc.AddProcessInstruction("<?xml version=""1.0""?>");
/* create an element and add text*/
&postreqresponse = &rootDoc.CreateElement("postreqresponse");
&error = &postreqresponse.CreateElement("error");
&ret = &error.AddComment("this is a comment line");
&errorcode = &error.CreateElement("errorcode");
&ret = &errorcode.AddText("1");
&errortext = &error.CreateElement("errortext");
```

Related Links

GetStatus

AddProcessInstruction

Syntax

AddProcessInstruction(*instruction*)

Description

The AddProcessInstruction method adds an XML processing instruction to a BiDocs object. Use this method at the root level of the BiDocs object for Incoming Business Interlinks before you add anything else to the BiDocs object.

Parameters

instruction	String. The processing instruction.

Returns

Number. The return status. NoError, or 0, means the method succeeded.

Example

Here is a set of XML response code.

```
<?xml version="1.0"?>
   <postreqresponse>
      <error>
         <!--this is a comment line-->
         <errorcode>1</errorcode>
         <errortext></errortext>
      </error>
   </postreqresponse>
```

Here is the PeopleCode that builds it.

```
Local BIDocs &rootDoc, &postreqresponse;
Local BIDocs &error, &errorcode, &errortext;
Local number &ret;
&rootDoc = GetBiDoc("");

/* add a processing instruction*/
&ret = &rootDoc.AddProcessInstruction("<?xml version=""1.0""?>");
/* create an element and add text*/
&postreqresponse = &rootDoc.CreateElement("postreqresponse");
&error = &postreqresponse.CreateElement("error");
&ret = &error.AddComment("this is a comment line");
&errorcode = &error.CreateElement("errorcode");
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
&ret = &errorcode.AddText("1");
&errortext = &error.CreateElement("errortext");
```

Related Links

GetStatus

AddText

Syntax

AddText(*text*)

Description

The AddText method adds text to an XML element referenced by a BiDocs object.

Parameters

text	String. The text.

Returns

Number. The return status. NoError, or 0, means the method succeeded.

Example

Here is a set of XML response code.

```
<?xml version="1.0"?>
   <postreqresponse>
      <error>
         <!--this is a comment line-->
         <errorcode>1</errorcode>
         <errortext></errortext>
      </error>
   </postreqresponse>
```

Here is the PeopleCode that builds it.

```
Local BIDocs &rootDoc, &postreqresponse;
Local BIDocs &error, &errorcode, &errortext;
Local number &ret;
&rootDoc = GetBiDoc("");

/* add a processing instruction*/
&ret = &rootDoc.AddProcessInstruction("<?xml version=""1.0""?>");
/* create an element and add text*/
&postreqresponse = &rootDoc.CreateElement("postreqresponse");
&error = &postreqresponse.CreateElement("error");
&ret = &error.AddComment("this is a comment line");
&errorcode = &error.CreateElement("errorcode");
&ret = &errorcode.AddText("1");
&errortext = &error.CreateElement("errortext");
```

Related Links

GetStatus

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

CreateElement

Syntax

CreateElement(*elementname*)

Description

The CreateElement method creates an XML element with the given name within a BiDoc object.

Parameters

elementname String. The XML element name.

Returns

BiDocs. The reference to the created element.

Example

Here is a set of XML response code.

```
<?xml version="1.0"?>
   <postreqresponse>
      <error>
         <errorcode>1</errorcode>
         <errortext></errortext>
      </error>
   </postreqresponse>
```

Here is the PeopleCode that builds it.

```
Local BIDocs &rootDoc, &postreqresponse;
Local BIDocs &error, &errorcode, &errortext;
Local number &ret;

&rootDoc = GetBiDoc("");

/* add a processing instruction*/
&ret = &rootDoc.AddProcessInstruction("<?xml version=""1.0""?>");
/* create an element and add text*/
&postreqresponse = &rootDoc.CreateElement("postreqresponse");
&error = &postreqresponse.CreateElement("error");
&errorcode = &error.CreateElement("errorcode");
&ret = &errorcode.AddText("1");
&errortext = &error.CreateElement("errortext");
```

GenXMLString

Syntax

GenXMLString()

Description

The GenXMLString method creates an XML string from a BiDocs object. The BiDocs object must contain the shape and data needed for an XML string. This is part of the Incoming Business Interlink functionality, which enables PeopleCode to receive an XML request and return an XML response.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

None.

Returns

String. The XML string containing the shape and data of the BiDocs object. For example, you can use this method to create an XML string containing an XML response.

Example

The following example takes a BiDocs structure that contains an XML response and puts that into a text string. After this is done, the %Response.Write function can send this as an XML response.

```
Local BIDocs &rootDoc;
Local string &xmlString;

/* Create a BiDoc structure containing the data and shape of your XML response (cod⇒
e not shown) */

/* Generate the XML string containing the data and shape of your XML response from ⇒
the BiDoc structure */
&xmlString = &rootDoc.GenXMLString();
%Response.Write(&xmlString);
```

GetAttributeName

Syntax

GetAttributeName(*attributenumber*)

Description

The GetAttributeName method gets the name of an attribute within an XML element referenced by a BiDocs object.

Parameters

attributenumber	Number. The index number of the attribute.

Returns

String. The name of the attribute.

Example

Here is a set of XML request code.

```
<?xml version="1.0"?>
   <postreq>
      <email>joe_blow@peoplesoft.com</email>
      <location scenery="great" density="low" blank="eh?">
         <city>San Rafael</city>
         <state>CA</state>
         <zip>94522</zip>
         <country>US</country>
      </location>
   </postreq>
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Here is the PeopleCode that gets the name of the second attribute in the location node. &attrName is density.

```
Local BIDocs &rootInDoc, postreqDoc, &locationDoc;
Local string &blob, &attrName;
&blob = %Request.GetContentBody();

&rootInDoc = GetBiDoc(&blob);
&postreqDoc = &rootInDoc.GetNode("postreq");
&locationDoc = &postreqDoc.GetNode("location");
&attrName = &locationDoc.GetAttributeName(2);
```

GetAttributeValue

Syntax

GetAttributeValue({*attributename* | *attributenumber*})

Description

The GetAttributeValue method gets the value of an attribute within an XML element referenced by a BiDocs object.

Parameters

attributenumber* | *attributename

Specify the attribute that you want to get the value for. You can specify either the attribute number (1 for the first attribute, 2 for the second, and so on) or the attribute name (an XML tag.)

Returns

String. The value of the attribute.

Example

Here is a set of XML request code.

```
<?xml version="1.0"?>
   <postreq>
      <email>joe_blow@peoplesoft.com</email>
      <location scenery="great" density="low" blank="eh?">
         <city>San Rafael</city>
         <state>CA</state>
         <zip>94522</zip>
         <country>US</country>
      </location>
   </postreq>
```

Here is the PeopleCode that gets the value of the second attribute in the location node. &attrValue is low.

```
Local BIDocs &rootInDoc, &postreqDoc, &locationDoc;
Local string &blob, &attrValue;
&blob = %Request.GetContentBody();

&rootInDoc = GetBiDoc(&blob);
&postreqDoc = &rootInDoc.GetNode("postreq");
&locationDoc = &postreqDoc.GetNode("location");
&attrValue = &locationDoc.GetAttributeValue(2);
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GetNode

Syntax

GetNode({*nodename* | *nodenumber*})

Description

The GetNode method returns a BiDocs reference to a child XML node (element or comment). Use the GetNode method upon a BiDocs reference to an XML element to access the child nodes for that element.

Parameters

nodenumber* | *nodename

Specify the node that you want to reference. You can specify either a node number (the first node is 1, the second 2, and so on) or a node name (that is, the XML tag.)

Returns

BiDocs. The returned XML element within a BiDocs object.

Example

Here is a set of XML request code.

```
<?xml version="1.0"?>
   <postreq>
      <email>joe_blow@peoplesoft.com</email> <projtitle>
         <projsubtitle>first_subtitle</projsubtitle>
         <projsubtitle>second_subtitle</projsubtitle> <projsubtitle>third_subtitle<⇨
/projsubtitle>
      </projtitle>
   </postreq>
```

Here is the PeopleCode that gets the postreqDoc element and the projtitle element.

```
Local BIDocs &rootInDoc, &postreqDoc, &projtitleDoc;
Local string &name, &blob;
&blob = %Request.GetContentBody();

&rootInDoc = GetBiDoc(&blob);
&postreqDoc = &rootInDoc.GetNode("postreq");
&projtitleDoc = &postreqDoc.GetNode("projtitle");
```

Here is the PeopleCode that gets the postreqDoc element, the projtitle element, and the third projsubtitle element.

```
Local BIDocs &rootInDoc, &postreqDoc, &projtitleDoc, &projsubtitleDoc;
Local string &name, &blob;
&blob = %Request.GetContentBody();

&rootInDoc = GetBiDoc(&blob);
&postreqDoc = &rootInDoc.GetNode(1);
&projtitleDoc = &postreqDoc.GetNode(2);
&projsubtitleDoc = &projtitleDoc.GetNode(3);
```

To parse a list of elements like <projsubtitle>, where elements have the same name, you must call GetNode using an index number rather than the element name.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ParseXMLString

Syntax

ParseXMLString(*XMLstring* [, *DTDValidation*])

Description

The ParseXMLString methods fills an existing BiDocs object with the data and shape from an XML string. This is part of the Incoming Business Interlink functionality, which enables PeopleCode to receive an XML request and return an XML response.

Parameters

XMLstring A string containing an XML document.

DTDValidation Specify whether to validate a document type definition (DTD.) This parameter takes a Boolean value. If you specify true, the DTD validation occurs if a DTD is provided. If you specify false, and if a DTD is provided, it is ignored and the XML isn't validated against the DTD. The default value for this parameter is false.

In the case of application messaging, if a DTD is provided, it's always ignored and the XML isn't validated against the DTD.

If the XML cannot be validated against a DTD, an error is thrown saying that there was an XML parse error.

Returns

Number. The return status. NoError, or 0, means the method succeeded.

Example

The following example gets an XML request, creates an empty BiDoc, and then fills the BiDoc with the data and shape contained in the XML string. After this is done, the GetDoc method and the GetValue method can get the value of the skills XML element, which is contained within the postreq element in the XML request.

```
Local BIDocs &rootInDoc, &postreqDoc;
Local string &blob;
Local number &ret;

&blob = %Request.GetContentBody();
/* process the incoming xml(request)- Create a BiDoc and fill with the request*/
&rootInDoc = GetBiDoc("");
&ret = &rootInDoc.ParseXMLString(&blob);
&postreqDoc = &rootInDoc.GetDoc("postreq");
&ret = &postreqDoc.GetValue("skills", &skills);
```

Related Links

GetStatus

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Incoming Business Interlink Properties

This section describes the PeopleCode properties you use with Incoming Business Interlinks.

AttributeCount

Description

The AttributeCount property gets the number of attributes within an XML element referenced by a BiDocs object.

This property is read-only.

Example

Here is a set of XML request code.

```
<?xml version="1.0"?>
   <postreq>
      <email>joe_blow@peoplesoft.com</email>
      <location scenery="great" density="low" blank="eh?">
         <city>San Rafael</city>
         <state>CA</state>
         <zip>94522</zip>
         <country>US</country>
      </location>
   </postreq>
```

Here is the PeopleCode that gets the number of attributes in the location XML element. &count should be 3, for scenery, density, and blank.

```
Local BIDocs &rootInDoc, &postreqDoc, &locationDoc;
Local string &blob;
Local number &count;
&blob = %Request.GetContentBody();

&rootInDoc = GetBiDoc(&blob);
&postreqDoc = &rootInDoc.GetNode("postreq");
&locationDoc = &postreqDoc.GetNode("location");
&count = &locationDoc.AttributeCount;
```

ChildNodeCount

Description

The ChildNodeCount property returns the number of XML child nodes within the element referenced by the BiDocs object. Child nodes include XML elements, comments, and processing instructions.

This property is read-only.

Example

Here is a set of XML request code.

```
<?xml version="1.0"?>
   <postreq>
      <email>joe_blow@peoplesoft.com</email>
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
      <projtitle>
         <!--this is a comment line-->
         <projsubtitle>first_subtitle</projsubtitle>
         <projsubtitle>second_subtitle</projsubtitle>
         <projsubtitle>third_subtitle</projsubtitle>
      </projtitle>
   </postreq>
```

Here is the XML code that gets the number of nodes within <postreq> and <projtitle>. &count1 is 2, for <email> and <projtitle>, and &count2 is 4, for the three <projsubtitle> nodes and the comment node.

```
Local BIDocs &rootInDoc, &projtitleDoc;
Local string &blob;
Local number &count1, &count2;
&blob = %Request.GetContentBody();

&rootInDoc = GetBiDoc(&blob);
&postreqDoc = &rootInDoc.GetNode("postreq");
&count1 = &postreqDoc.ChildNodeCount;
&projtitleDoc = &postreqDoc.GetNode("projtitle");
&count2 = &projtitleDoc.ChildNodeCount;
```

NodeName

Description

The NodeName property gets the name of an XML element referenced by a BiDocs object. Use this to get the name of an XML element when you used GetNode with an index number to retrieve it (meaning that you did not have the name of the XML element when you used GetNode).

This property is read-only.

Example

Here is a set of XML request code.

```
<?xml version="1.0"?>
   <postreq>
      <email>joe_blow@peoplesoft.com</email>
      <projtitle>
         <projsubtitle>first_subtitle</projsubtitle>
         <projsubtitle>second_subtitle</projsubtitle>
         <projsubtitle>third_subtitle</projsubtitle>
      </projtitle>
   </postreq>
```

Here is the PeopleCode that gets the name of the <email> element, email.

```
Local BIDocs &rootInDoc, &postreqDoc, &emailDoc;
Local string &emailName, &blob;
&blob = %Request.GetContentBody();

&rootInDoc = GetBiDoc(&blob);
&postreqDoc = &rootInDoc.GetNode(1);
&emailDoc = &postreqDoc.GetNode(1);
&emailName = &emailDoc.NodeName;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

NodeType

Description

The NodeType property returns the type of an XML tag within a BiDocs object as an integer. The values are:

Value	*Description*
1	Element (a normal XML tag)
7	Processing instruction
8	Comment

This property is read-only.

Example

Here is a set of XML request code.

```
<?xml version="1.0"?>
   <postreq>
      <email>joe_blow@peoplesoft.com</email> <!--this is a comment-->
      <projtitle>
         <projsubtitle>first_subtitle</projsubtitle>
         <projsubtitle>second_subtitle</projsubtitle>
         <projsubtitle>third_subtitle</projsubtitle>
      </projtitle>
   </postreq>
```

Here is the PeopleCode that gets types: &xmlprocType is 7 for processing instruction, postreqDoc is 1 for element, and commentType is 8 for comment.

```
Local BIDocs &rootInDoc, &postreqDoc, &commentDoc;
Local number &xmlprocType, &postreqType, &commentDoc;
Local string &blob;
&blob = %Request.GetContentBody();

/* <?xml version="1.0"?> */
&rootInDoc = GetBiDoc(&blob);
&xmlprocType = &rootInDoc.NodeType;

/* <postreq> */
&postreqDoc = &rootInDoc.GetNode(1);
&postreqType = &postreqDoc.NodeType;

/* <!--this is a comment--> */
&commentDoc = &postreqDoc.GetNode(2);
&commentType = &commentDoc.NodeType;
```

NodeValue

Description

The NodeValue property returns the value of a node within an XML document as a string.

This property is read-only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

Here is a set of XML request code.

```
<?xml version="1.0"?>
   <postreq>
      <email>joe_blow@peoplesoft.com</email>
      <projtitle>
         <projsubtitle>first_subtitle</projsubtitle>
         <projsubtitle>second_subtitle</projsubtitle>
         <projsubtitle>third_subtitle</projsubtitle>
      </projtitle>
   </postreq>
```

Here is the PeopleCode that gets the value of the third <projsubtitle> element, third_subtitle.

```
Local BIDocs &rootInDoc, &postreqDoc, &projtitleDoc, &projsubtitleDoc;
Local string &name, &blob;
&blob = %Request.GetContentBody();

&rootInDoc = GetBiDoc(&blob);
&postreqDoc = &rootInDoc.GetNode(1);
&projtitleDoc = &postreqDoc.GetNode(2);
&projsubtitleDoc = &projtitleDoc.GetNode(3);
&projsubtitleName = &projsubtitleDoc.NodeValue;
```

Business Interlink Class Property

This section explains the StopAtError property.

StopAtError

Description

The StopAtError property specifies whether the execution of the PeopleCode program stops when there's an error, or if the PeopleCode program tries to capture the errors.

This property takes a Boolean value: True to halt execution of your PeopleCode program at an error, False to continue executing. The default value is True.

This property is read-write.

Example

```
&QE_RP_SRAALL_1.StopAtError = False;
```

Configuration Parameters

There are two types of configuration parameters: the ones defined by the Interlink plug-in the Business Interlink definition is based on, and the ones that are standard, that is, defined for every Business Interlink object.

All configuration parameters must be set before you add any data to the input buffers.

In this section, we discuss the following parameters:

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- Interlink plug-in configuration parameters
- URL configuration parameter
- BIDocValidate configuration parameter

Interlink Plug-in Configuration Parameters

The configuration parameters defined by the Interlink plug-in are accessed as if they were properties on the Business Interlink object. That is, in PeopleCode, you assign the value of a configuration parameter by using the Business Interlink object followed by a dot and the configuration parameter, in this format:

```
&MYINTERLINK.parameter = value;
```

You can also return the value of a configuration parameter:

```
&MYVALUE = &MYINTERLINK.parameter;
```

Each Business Interlink plug-in has its own set of configuration parameters. For example, the email project uses configuration parameters of SMTP_MAIL_SERVER, POP3MAIL_SERVER, LOGIN_NAME, PASSWORD, SENDERS_EMAIL_ADDRESS and REPLY_EMAIL_ADDRESS, while the Red Pepper transaction driver uses SERVER_NAME, RSERVER_HOST, RSERVER_PORT, and TIMEOUT.

You can specify default values for every configuration parameter in the Business Interlink definition (created in Application Designer.) These values are used if you create a PeopleCode "template" by dragging the Business Interlink definition from the Project window in Application Designer to an open PeopleCode editor window.

In the following example, the Interlink object name is QE_RP_SRAALL_1, and the driver is the Red Pepper driver:

```
&QE_RP_SRAALL_1.SERVER_NAME = "server";
&QE_RP_SRAALL_1.RSERVER_HOST = "pt-sun02.peoplesoft.com";
&QE_RP_SRAALL_1.RSERVER_PORT = "9884";
&QE_RP_SRAALL_1.TIMEOUT = 999;
&QE_RP_SRAALL_1.URL = "HTTP://www.PeopleSoft.com";
&QE_RP_SRAALL_1.StopAtError = False;
```

URL Configuration Parameter

Specifies the location and name of the Business Interlink plug-in to be used to connect to the external system. This configuration parameter takes a string value.

If the plug-in is located on a web server, you have to specify the name of the web server.

If you specify a file, you can specify either a relative or an absolute path:

- If you specify an absolute path, you must specify the drive letter:

  ```
  &MYBI.URL = "File://D:\TEMP.MYDLL";
  ```

- If you specify a relative path, just use the file name:

  ```
  &MYBI.URL = "File://TEMP.MYDLL";
  ```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

If you specify a relative path, the system firsts looks for the file in the Location directory (specified by the user when the Business Interlink was first created), then it looks in the directory where PeopleTools is installed, in the PSTOOLS/Interface Drivers directory.

BIDocValidate Configuration Parameter

Specifies whether the system should verify whether the hierarchical data object (BIDoc) exists before adding or getting values from it. This configuration parameter takes a Boolean value: True if the system should verify before accessing the object, False otherwise.

The default value is True.

If this configuration parameter is specified as True, and the object specified doesn't exist, the PeopleCode program halts execution and an error is displayed.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Chapter 14

Charting Classes

Understanding the Charting Classes

PeopleTools delivers four charting classes. One general charting class supports a range of standard chart types, and three specialized charting classes address specific charting needs. Each charting class is discussed in detail in following sections.

The charting classes are:

- Chart classes:
  - Chart class

    Use the Chart class to visually display data series in common formats, including bar charts, line charts, pie charts, bubble charts, and funnel charts.
  - ReferenceArea class

    The ReferenceArea class is used in conjunction with the Chart class to display bands of color to be drawn with the chart based on numeric values along a chart axis. For each band of color, you would create a separate instance of the ReferenceArea class.
  - ReferenceLine class

    The ReferenceLine class is used in conjunction with the Chart class to display colored lines to be drawn with the chart based on numeric values along a chart axis. For each reference line, you would create a separate instance of the ReferenceLine class.
- Gantt class

  Use the Gantt class to create interactive Gantt charts that enable you to display and edit project and task information.
- Gauge classes:
  - DialGauge class
  - LEDGauge class
  - StatusMeterGauge class
  - Threshold class

  Use the gauge classes to create gauges that display metrics in several common formats, including dials, status meters, and LEDs.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The Threshold class is used in conjunction with the three gauge classes: DialGauge, LEDGauge, and StatusMeterGauge. The Threshold class provides a way to add reference areas and color coding to your gauges.

- OrgChart class

  Use the OrgChart class to create interactive organization charts that enable you to visually represent a hierarchy of information as a series of connected nodes.

- RatingBoxChart class

  Use the RatingBoxChart class to create rating box charts that enable you to display and manipulate points of information in two-dimensional bins.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The following examples show five chart examples.

Image: Example of a two-dimensional bar chart

This chart was created from the Chart class with a chart type of 2D bar:

Image: Example of a dial gauge with thresholds

This chart was created from the DialGauge class that includes thresholds defined by the Threshold class:

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Image: Example of a Gantt chart

This chart created from the Gantt class shows both the task area and chart area of a Gantt chart:

Image: Example of an organization chart

This chart created from the OrgChart class shows an organization chart:

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Image: Example of a rating box chart

This chart created from the RatingBoxChart class shows a rating box chart:

Related Links

Creating PeopleSoft Charts
Using the Chart Class
Using the Gantt Class
Using the OrgChart Class
Using the RatingBoxChart Class

Creating PeopleSoft Charts

This section discusses the process of creating charts using any of the PeopleSoft charting classes. Further details can be found in the specific section for each chart class.

These topics relate to all of the charting classes:

- Creating a chart on a page.
- Creating a chart using an iScript.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Creating a Chart on a Page

This section summarizes the basic steps to create a chart. The basic steps are essentially the same for all four charting classes.

At the end of this chapter are examples of charts with step-by-step instructions and complete PeopleCode programs.

The Chart class section has fundamental, detailed instructions for creating a chart using the Chart class. Each specialized class – Gantt class, OrgChart class, and RatingBoxChart class – has detailed instructions that build on the Chart class instructions.

See Creating a Chart Using the Chart Class, Using the Chart Class, Using the Gantt Class, Using the OrgChart Class, Using the RatingBoxChart Class.

Note: The following steps are for creating a chart on a PeopleSoft Pure Internet Architecture page. You can also create a chart for a web page using an iScript. Only Chart class charts can be created using an iScript.

See Creating a Chart Using an iScript.

To create a chart on a page:

1. In Application Designer, place a chart control on a page and associate the chart with a record field.

2. Create a record to hold your chart data.

   For charts made using the OrgChart class and the RatingBoxChart class, you also create a record that controls the appearance of the chart. Place each record on a level-1 grid on the page so the chart records are present in the component buffer at runtime. You can optionally hide the grid. You can also optionally place the grid on another page on the same component.

   Place the page on a component and register the component.

3. Add PeopleCode, probably on the page Activate event, to instantiate the chart object and associate it with the page control.

   For example, this is the minimum PeopleCode to create a bar chart using the Chart class.

```
/* Declare a chart object */

Component Chart &cChart;

/* Instantiate the chart object and associate the chart
** with the chart page control */

&cChart = GetChart(DOC_CHRT_WRK.QE_CHART_FIELD);

/* Specify the chart data record and specify the record
**  fields for the x-axis data and y-axis data*/

&cChart.SetData(Record.DOC_CHRT_SLSREC);
&cChart.SetDataXAxis(DOC_CHRT_SLSREC.SC_PRODUCT);
&cChart.SetDataYAxis(DOC_CHRT_SLSREC.SC_SALES);
```

4. View the chart in the browser.

   Suppose you have this data in DOC_CHRT_SLSREC:

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Region	***Sales***
Arizona	62
California	50
Oregon	42
Washington	50

This is the bar chart generated by the example code and data. The default chart type for the Chart class is a bar chart. Since no colors are specified, the chart uses the default colors.

Image: A simple bar chart

This example illustrates a simple bar chart:

5. Add PeopleCode to control the behavior of the chart or to modify its appearance at runtime. For example, for a bar chart you might add FieldChange PeopleCode to the y-axis field on your data record to display information when a user clicks a data point.

   See “Adding Drilldown” in Creating a Chart Using the Chart Class.

   You can also add FieldChange PeopleCode to a Gantt chart, organization chart, or rating box chart to enable the user to interact with the chart.

Related Links

Creating a Chart Using the Chart Class
Using the Chart Class
Using the Gantt Class
Using the OrgChart Class
Using the RatingBoxChart Class

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Creating a Chart Using an iScript

If possible, you should put a chart on a page definition. If not possible, then you can build a chart at runtime using an iScript and call the chart using a URL. Use the CreateObject function in the iScript instead of the GetChart function. You can then use the GetChartURL Response class method to use the URL in your application.

Note: You can create only Chart class charts using an iScript. Any charts created using an iScript have limited functionality as compared to charts defined using the Application Designer chart control. Notably, neither interactivity (the charts will be static) nor animations are available.
Gauge chart classes, Gantt class, OrgChart class, and RatingBoxChart class charts cannot be created with an iScript.

For example, this PeopleCode would build a chart using a standalone rowset:

```
Function IScript_GetChartURL()
local object &MYCHART;
local string &MYURL;

&MYCHART = CreateObject("Chart");
&MYCHART.SetData(xx);

/* xx will be a data row set */

&MYURL = %Response.GetChartURL(&MYCHART);

/* use &MYURL in your application */
...
End-Function;
```

Related Links

Creating a Chart Using an iScript

Special Considerations for Charts

This section discusses the following special considerations for using any of the PeopleSoft charting classes:

- Component Processor considerations.
- Translation considerations.
- Text considerations for the Chart class.
- Text considerations for the Gantt class.
- Text considerations for the gauge classes.
- Considerations for using touch-friendly mobile devices.
- Styling PeopleSoft charts.
- Accessibility settings for charts.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- WSRP considerations.

Component Processor Considerations

Sometimes, records at level zero on a page are considered *work* records, even when they are not specified as such in Application Designer. Work records are not updated by the database and are skipped when the component is run.

A level-zero record is marked as a work record when any of these conditions is true:

- The record is designated as a work record in Application Designer.
- All fields for the record are used as read-only fields.
- All values for these fields can be read from the input keys.

When a chart area is attached to a level-zero record field of a record considered to be a work record, it is also skipped when the system determines that record's 'work' status.

Related Links

"Understanding Component Buffer Structure and Contents" (PeopleTools 8.54: PeopleCode Developer's Guide)

Translation Considerations

If you hard code a value for a label, a title, a data hint, and so on, then that value is *not* translated. Be sure to specify field values as message catalog entries that will be translated.

Text Considerations for the Chart Class

Text can be found at the following locations in a Chart class chart:

- Chart title.
- Chart subtitle.
- Chart footnote.
- X-axis and y-axis titles.
- X-axis and y-axis labels.
- Legend descriptions.
- Pie chart segment labels.
- Data hints (hover or mouse over text).

Fonts and point sizes for chart titles, subtitles, footnotes, axis titles, and axis labels in charts are defined as style classes in PeopleSoft style sheets. The delivered style classes are designed to work with the overall theme of the PeopleSoft user interface. The delivered style classes apply to all charts in the system. Although they are changeable in the Application Designer, Oracle recommends that you keep them as delivered unless you have a good reason to change them.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Note: Line breaks in text such as the chart title, axis titles, axis labels, and so on are not supported and are now ignored. (Prior to PeopleTools 8.53, a line break could be designated in text using </br>.)

Axis labels are positioned by the charting engine as part of the overall rendering of the chart graphic. The general pattern for axis and pie chart segment label display is this:

- The point size of the label text remains constant.
- The charting engine will try to maximize the size of the chart graphic while fitting all label text around the graphic.
- The chart graphic area will shrink to a minimum threshold size as the text for labels grows longer.
- After the minimum chart graphic area threshold size is reached, the chart graphic no longer shrinks and labels are displayed in an unpredictable fashion.

There are special considerations depending on whether the type of label is for an x-axis, a y-axis, or a pie chart segment.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

X-Axis Labels

Image: X-axis showing short labels in a single row

As an example, note how the x-axis labels on the following bar chart are positioned as the label sizes increase. First the labels are short enough that they fit horizontally all on one row:

Image: X-axis showing short labels in two rows

As the labels get longer, the labels appear staggered on two rows and the height of the chart itself decreases:

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Image: X-axis showing vertical labels

As the labels continue to increase in length, they become positioned vertically and the height of the chart decreases more:

Image: X-axis showing that some labels are not displayed at the minimum chart height

As the labels become longer still, a minimum chart height threshold is reached. The labels now cannot all fit horizontally or vertically. The result is that some of the labels do not appear at all.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Y-Axis Labels

Image: Y-axis showing short labels in a single row

Similarly, text on y-axis labels is subject to size constraints. Here are some examples of what happens as labels along the y-axis increase in length:

Image: Y-axis showing wrapped labels

If a label has a space the label may be wrapped (note that this does not happen to the x-axis labels).

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Image: Y-axis showing maximum length labels at the minimum chart width

Otherwise, the label area will grow and the chart width will shrink to a limit:

Image: Y-axis showing that some labels are not displayed at the minimum chart width

Once a minimum chart width threshold is met, not all labels are displayed. Here, one more “M” is prepended to “Maggie May” with the result that some labels are not displayed:

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Pie Chart Segment Labels

Image: Pie chart showing short labels

Segments on the pie chart follow the general pattern—as the labels get longer, the chart graphic (that is, the pie) shrinks:

Image: Pie chart showing wrapped labels

If a label has a space, the label text might be wrapped by the charting engine:

Image: Pie chart showing long labels with missing characters

Additionally, in a pie chart once the minimum size threshold for the chart graphic is reached, a long label that exceeds the amount of space available has an ellipsis substituted for the missing characters:

Best Practices for Managing Chart Text

The best ways to minimize the chance of unpredictable text are:

- Use the smallest font that is readable for text labels. PeopleTools is delivered with a small point size for axis labels in order to allow more characters to be rendered.
- The larger the chart area is defined, the more room will be available for labels.
- Try to build your charts using short (but descriptive) fields for axis labels.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- Make sure that data hints are always used in your charts to compensate when labels cannot be displayed.

Data Hints (Hover or Mouse Over Text)

The default data hint text that appears is constructed from information about the composition of the chart that you have defined and the row of data being charted. Specifically, its structure depends on whether the chart has a data series or not:

Chart Composition	***Default Hint***	***Example***
SetDataSeries not set	Value [*y*] for point [*x*]	Value 50 for point California

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Chart Composition	*Default Hint*	*Example*
SetDataSeries set	Value [*y*] for point [*x*] of series [*series*]	Value 40 for point Rackets of series Oregon

Image: Default hint when SetDataSeries is not set

If you do not specify SetDataHints and do not specify SetDataSeries, then the value of the y-axis and the value of the x-axis appear in the data hint:

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Image: Default hint when SetDataSeries is set

If you do not specify SetDataHints but do specify SetDataSeries, then the value of the y-axis, the x-axis, and the series appear in the data hint::

Use the SetDataHints method to override the default text that appears as a caption when you mouse over data in a chart (that is, a bar, a pie slice, or a data point).

Related Links

SetDataHints

Text Considerations for the Gantt Class

For Gantt charts, use double quotes to correctly display the use of single quotes in your label, if applicable.

Text Considerations for the Gauge Classes

Text can be found at the following locations in gauges:

- Gauge title
- Bottom label
- Top label
- Metric label
- Legend descriptions

Fonts and point sizes for all gauge text are specified in style class definitions in PeopleSoft style sheets. The delivered style class values are designed to work with the overall theme of the PeopleSoft user interface. The delivered style classes apply to all charts in the system.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Although they are changeable in the Application Designer, Oracle recommends that you keep them as delivered unless you have a good reason to change them.

The gauge rendering engine will automatically truncate text to fit into the area allotted for it. Thus, it is a good idea to minimize as much as possible the use of text in your gauge and if you do use text, be sure to use it in an economical fashion.

Considerations for Using Touch-Friendly Mobile Devices

Because touch-friendly mobile devices such as the Apple iPad do not use a mouse, you interact with charts differently on mobile devices. To click a button, link, or chart object, tap the touch screen with one finger. To display data hints for a chart, tap the touch screen twice (double-tap). Data hints disappear after five seconds or when you tap another object with a data hint.

To move a node in a rating box chart, tap once to select the node. Then, tap once in a different grid box to move the node to that box.

Note: Drag-and-drop on Gantt charts is not supported on mobile devices.

See Using Rating Box Charts in PeopleSoft Applications.

Styling PeopleSoft Charts

PeopleSoft charts are flexible in terms of styling. Styling covers colors and fonts that you see when you look at a chart. Style specifications are generally defined in Application Designer style sheets so that they are accessible to application developers. Specifically, they are defined in sub style sheets that are then attached to high-level system style sheets such as PSSTYLEDEF_TANGERINE which are used throughout a system ensuring consistent look and feel.

Charting Sub Style Sheet Organization

The organization of the charting sub style sheets is straightforward. Each chart class has its own set of styles. These styles are in one or more sub style sheets that have a naming convention as shown in the table below.

Charting Class	*Sub Style Sheet Begins With*
Chart DialGauge LEDGauge ReferenceArea ReferenceLine StatusMeterGauge Threshold	PSCHARTSTYLE
Gantt	PSCHARTGANTT

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Charting Class	*Sub Style Sheet Begins With*
OrgChart	PSORGCHART
RatingBoxChart	PSRATEBOX

Different specifications of the styles will be in sub style sheets that are appended with a underscore ("_") followed by an identifier, which is usually the name of the theme.

For instance, PSCHARTSTYLE and PSCHARTSTYLE_TANGERINE have the same styles but the specifications for these styles differ because PSCHARTSTYLE is used for the Swan user interface theme while PSCHARTSTYLE_TANGERINE is used for the Tangerine user interface theme.

See "Administering System Branding" (PeopleTools 8.54: Portal Technology) for more information on how to specify the theme and default style sheet for your system..

Altering Style Specifications

The styles delivered for charting are designed to work harmoniously with the branding theme that they are associated with. There may be times, however, when you want a different look and feel from the delivered one. Scenarios may include:

- You want to implement a system-wide change in theme (including not only charts but other visual elements such as headers, grids, and so on.
- You want to implement a system-wide change in chart style specification within the context of one of the PeopleSoft delivered themes. An example might be to change the sequence in which colors appear on charts or to change the font size of one of the chart text elements such as the axis titles.
- You want to implement a style modification on a particular chart or particular family of charts. For instance, there may be certain charts that appear on pagelets in which you want the main title to have a large font and be bold.

Different approaches lend themselves to these different scenarios.

Scenario 1: Implement system-wide change in theme

In this scenario you would most likely be creating a new system style sheet for your implementation probably by cloning one of the high level style sheets that PeopleSoft delivers. Once you have done this, follow the steps in Scenario 2 for the charting sub style sheets.

Scenario 2: System-wide change in chart style specifications

1. Identify the charting style classes that you want to change.
2. Identify the charting sub style sheet in which those style classes reside.
3. Clone those sub style sheets.
4. In the cloned sub style sheets, update the values of the style classes that you want to change.
5. Attach the cloned sub style sheets to the default style sheet for your PeopleSoft system.
6. Detach the delivered sub style sheets from the same default style sheet.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

7. Test the results.

Important! Do not change the delivered style sheets and sub style sheets. The best practice is to clone them and make changes to the clones.

Important! Do not delete style classes from original or cloned style sheets or sub style sheets. Doing so may compromise chart creation.

There is no guarantee that the style sheet value changes that you make will work as expected in the application, as style class specification changes may impact chart creation. You must test the results of your changes to verify that they are working. If changes are not working as expected, you need to try a different style class value.

Scenario 3: Minor style modification

PeopleSoft charting provides a means to override delivered styles on a granular basis on the Chart class and gauge classes. If you need to override one or more delivered style class definitions found in a PSCHARTSTYLE* sub style sheet, do the following:

1. Create a new free form sub style sheet in Application Designer.
2. Open up the PSCHARTSTYLE* sub style sheet that contains the style class definitions.
3. Copy the specific style class definitions and paste them into the new free form sub style sheet.

   Note: Putting the style class definitions into a new free form sub style sheet will simplify your future PeopleTools upgrades.

   ---

4. Append an underscore ("_") to the end of the copied style class names followed by an identifier of your own choosing. These new style class definitions are the overriding styles. For example, an overriding style class name for the PSCHARTLEGEND style class could be PSCHARTLEGEND_NEW.
5. Edit the new style class definitions that you have created to suit your needs and save the sub style sheet.
6. Insert the new free form sub style sheet into the default system style sheet that your environment is using.
7. For any chart that you want to use your custom styles, set the AdditionalStyleSuffix property to the identifier you used in step 4.

When the chart is generated at runtime, it will first use any styles that have your override identifier. If such a style class definition is not found, the chart will use the base style that you copied instead.

See AdditionalStyleSuffix, AdditionalStyleSuffix, AdditionalStyleSuffix, and AdditionalStyleSuffix.

Accessibility Settings for Charts

Use the Chart Options page to specify system-wide accessibility settings by chart type. When accessibility is enabled for a chart type and the signed in user has enable accessible layout mode in My Personalizations, the system generates the chart data in an HTML table that is in an accessible format for assistive technologies. For some chart types, this "accessible table" is in addition to the graphical rendering of the chart; in other cases, the accessible table is the only output generated:

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- For the Chart class and the gauge classes, the accessible table is in addition to the graphical rendering of the chart.
- For the Gantt class, the accessible table is the only output generated.

Navigation

PeopleTools, Utilities, Administration, Chart Options

Image: Chart Options Page

This example illustrates the fields and controls on the Chart Options page.

VARIABLE

Specify the chart type by variable name:

- *PTACCSBLCHRT* – Chart class charts and gauge charts.
- *PTACCSBLCHRTGNT* – Gantt class charts.
- *PTACCSBLCHRTORG* – OrgChart class charts.
- *PTACCSBLCHRTRB* – RatingBoxChart class charts.

VALUE

Specify the system accessibility setting:

- *0* – Accessibility is disabled for this chart type.
- *1* – Accessibility is enabled for this chart type

Note: The delivered setting is for accessibility to be enabled.

Related Links

"Enabling Accessibility Features to Support Assistive Technology" (PeopleTools 8.54: Accessibility Guide)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

WSRP Considerations

Web Services for Remote Portlets (WSRP) is a standard for communicating with remote portlets. For example, a PeopleSoft pagelet can be displayed as content within a non-PeopleSoft portal in the style of that portal.

While chart objects generated from the Chart class can be displayed in WSRP environments, chart objects generated from the Gantt class, OrgChart class, and RatingBoxChart class are not available for consumption in WSRP environments

Related Links

"Producing Remote Portlets (Producer)" (PeopleTools 8.54: Portal Technology)

Using the Chart Class

Use the Chart class to create charts that display data series in several common formats, including bar charts, line charts, pie charts, and others.

This section provides an overview of Chart class terms and discusses:

- Creating charts using the Chart class.
- Chart class chart types.
- Chart class design guidelines.
- Using the ReferenceArea class.
- Using the ReferenceLine class.
- Scope and data type of a Chart object.
- Error handling.
- Chart class methods and properties by category.

Understanding Chart Class Terms

The following is a list of Chart class terms and their descriptions:

Label	Text that identifies the data on one of the axes.
Legend	Text that identifies the different series in the chart.
Series	A grouping of related information. For example, if you were tracking sales for several divisions over many years, each division could be a series. Generally, every series in a chart has a distinct color. You can have more than one series in a chart for comparison. Each line in a line chart represents one series.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Title	The three titles are main, x-axis, and y-axis. Each title identifies a portion of the chart.
Subtitle	The subtitle appears beneath the main title.
Footnote	The footnote appears at the bottom left of the chart.
True XY	A type of chart that uses a numeric x-axis instead of a categorical x-axis. The numeric x-axis supports non-uniform data, that is, each series need not have the same number of points, and those points along the x-axis need not match up across the series. Line charts, histograms, scatter charts, and bubble charts can be specified as true XY charts.
X-axis	The axis that data is measured against.
Y-axis	The axis that contains the data. In most charts, this is the vertical axis. In a horizontal bar chart, this is the horizontal axis.
Overlay	Related data represented by a line chart drawn over a 2D bar chart.
Reference area	A reference area is displayed in conjunction with a chart as a band of color drawn based on numeric values along a chart axis. For each band of color, you would create a separate instance of the ReferenceArea class.
Reference line	A reference line is displayed in conjunction with a chart as a colored line drawn based on a numeric value along a chart axis. For each line, you would create a separate instance of the ReferenceLine class.

Creating Charts Using the Chart Class

You can specify a rowset and have it graphed using a chart object with minimal PeopleCode. Within this rowset, one column must contain data for the x-axis and another column must contain data for the y-axis. If more than one series of data is used, an additional column is required for each series. You can also set color and data hint text for each point in this rowset using additional columns.

The following distinguishable types of data can be included in a chart:

- Primary data.
- Secondary or overlay data (available for 2D bar charts and funnel charts only).

  Overlay data might be quite different from primary data in a bar chart, so an additional rowset is needed.

The only object used with the Chart class is a Chart object. Sub-objects do not exist. All methods and properties are used with the Chart object.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

For a conceptual overview, a chart is easier to view in parts; however, these parts do *not* represent sub-objects. A chart contains the following major parts:

- X-axis.
- Y-axis.
- Overlay (available for a 2D bar chart only).
- Legend.
- Data .
- Title.
- Subtitle.
- Footnote

The x, y, and overlay axes have access to titles and labels associated with their data.

Chart Class Chart Types

The following chart types are available for the Chart class:

- 2D bar.
- 3D bar.
- 2D bubble.
- 2D funnel.
- 2D histogram.
- 2D horizontal bar.
- 2D horizontal percent bar.
- 2D horizontal stacked bar.
- 2D line.
- 2D percent bar.
- 3D percent bar.
- 2D pie.
- 3D pie.
- 2D ring.
- 3D ring.
- 2D scatter.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- 2D stacked bar.
- 3D stacked bar.

Related Links

Creating a Chart Using the Chart Class

Chart Class Design Guidelines

These topics provide an overview of how charts represent data and discuss:

- Charting numeric data sets.
- Determining the appropriate chart type.
- Setting chart colors.
- Setting chart legends.

Understanding How Charts Represent Data

PeopleSoft charts are an alternative means of visualizing tabular data.

For example, here is an example data table (with column headings):

Product	***Color***	***Month***	***Year***	***Salesperson***	***Salesperson Height in Inches****	***Units****	***Revenue****
Bicycle	Red	01	2012	Terry	72	5	600
Tricycle	Blue	01	2012	Jim	84	3	360
Unicycle	Silver	02	2012	Terry	72	1	150

* Numeric data

Some of the columns carry numeric measures (in our example, Units, Revenue, and Salesperson Height in Inches) and other columns have values that describe the data (for example, Product, Color, Month, Year, and Salesperson). Some of the data columns are numeric; others are not.

To create a chart you need to determine which fields you want to see in the chart. Then, you pass those into certain Chart class methods:

- SetDataXAxis.
- SetDataYAxis.
- SetDataSeries.
- SetDataGlyphScale.
- SetFunnelDataActual (for funnel charts only).

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- SetFunnelDataTarget (for funnel charts only).

Each of these methods takes as a parameter a RECORD.FIELD.

Charting Numeric Data Sets

These sections discuss:

- Charting one set of numeric data.
- Charting two sets of numeric data.
- Charting three sets of numeric data.

Charting One Set of Numeric Data

In general, you pass a numeric data field to SetDataYAxis and a non-numeric field to SetDataXAxis . These two methods are required.

Here's a simple example. Suppose you want to show revenue by product as a chart. Essentially, this is the rowset that you'll be working with, a subset of the rowset introduced previously:

Product	***Revenue****
Product	Revenue*
Bicycle	600
Tricycle	360
Unicycle	150

* Numeric data

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

In this case, choose the Revenue field to be passed to SetDataYAxis and the Product field to be passed to SetDataXAxis .

Image: A pie chart showing product sales data

If you choose to display this as a pie chart, you end up with this:

Image: A bar chart showing product sales data

Or, you could display the data as a bar chart:

Alternatively, you could display the data with any chart type that can display one dimension of data, such as a horizontal bar, a line, a histogram, or other chart type.

What if you also wanted to show the same information but with additional month information? The table of data that you would be interested in is:

Product	***Month***	***Revenue****
Bicycle	01	600
Tricycle	01	360
Unicycle	02	150

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

* Numeric data

In that case, choose the Revenue field to be passed to SetDataYAxis , the Product field to be passed to SetDataXAxis , and the month field to be passed to SetDataSeries .

Image: A bar chart showing product sales data by month

You would need to use a chart type that can display two dimensions along with the data. This rules out the pie chart, but you can still use a bar chart:

Image: A bar chart showing monthly sales data by product

To get a different view of the same data, you can change the method assignments, so that Month is passed in SetDataXAxis and Product is passed in SetDataSeries . The chart that results is this:

Charting Two Sets of Numeric Data

Charting Two Sets of Numeric Data

The following chart types allow you to plot two sets of numeric data:

- Scatter chart
- Line chart

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- Histogram
- Funnel chart
- Overlay chart

The scatter and line charts let you plot one set of numeric data vertically along the y-axis and one set of data horizontally along the x-axis.

The funnel and overlay charts let you plot both sets of numeric data vertically on the y-axis.

Here's an example of a scatter chart representing the following table of data:

Units*	***Revenue****
5	600
3	360
1	150

* Numeric data

Image: A scatter chart showing revenue versus units sold

The preceding table of data produces this scatter chart:

You can also use a line chart to represent the same data. Whereas the scatter chart requires both x- and y-axes to be numeric, the line chart x-axis can be either numeric or non-numeric. Therefore, you would have to set the IsTrueXY property to True to plot two sets of numeric data against each other.

If you want to see this data by product, add the Product column to the rowset:

Product	***Units****	***Revenue****
Bicycle	5	600
Tricycle	3	360

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Product	*Units**	*Revenue**
Unicycle	1	150

* Numeric data

Image: A scatter chart showing revenue versus units sold by product

If you set the data series to be Product, you get this scatter chart:

In a funnel chart one set of data is specified using the SetFunnelDataActual method and the other set of data is specified using the SetFunnelDataTarget method.

Image: A funnel chart plotting actual as a percentage of target

Here's an example of a funnel chart that graphs two sets of data, a target amount and an actual amount:

For funnel charts, these additional considerations apply:

- SetData and SetDataXAxis are required.
- SetFunnelChartDataActual can be used instead of SetDataYAxis; either are valid.
- SetFunnelChartDataTarget is optional. When used, SetFunnelChartDataTarget must specify the same record as SetFunnelChartDataActual.

Note: Legends are not available for funnel charts. The use of Chart class methods and properties for legends has no effect on a funnel chart.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

In an overlay chart, the data for the bar chart is specified using the SetDataYAxis method and the data for the line chart is specified using the SetOLDataYAxis method.

Image: An example of an overlay chart

In this example of an overlay chart, US sales overlay worldwide sales:

Charting Three Sets of Numeric Data

You can use the bubble chart to display three sets of numeric data. The first two sets are along the x- and y-axes just as if you were plotting two sets of numeric data. The third set of numeric data is displayed as the size of the bubble positioned at the (x,y) coordinate in the chart and is set by passing the field in the SetDataGlyphScale method.

Here's an example, albeit a far-fetched one, which includes three sets of numeric data:

Salesperson Height in Inches*	***Units****	***Revenue****
72	5	600
84	3	360
72	1	150

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

* Numeric data

Image: A bubble chart showing three sets of numeric data

Here's a bubble chart that represents this data. Note that the size of the bubble on the right is larger than the two other bubbles, which are the same size.

If you want to see this data by product, add the Product column to the rowset:

Product	***Salesperson Height in Inches***	***Units***	***Revenue***
Bicycle	72	5	600
Tricycle	84	3	360
Unicycle	72	1	150

Image: A bubble chart showing three sets of numeric data by product

You can set the data series to a dimension, such as Product, to end up with this bubble chart:

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Determining the Appropriate Chart Type

Use the following procedures to determine the chart types that are appropriate for your data set:

- One set of numeric data.
- Two sets of numeric data.
- Three sets of numeric data.

Care should be taken when using the line chart with non-numeric data on the x-axis. You should only use it when the data along the x-axis suggests some sort of progression. For example, using a line chart when

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

the x-axis represents a sequence of months is appropriate; using a line chart when the x-axis represents a list of people in alphabetical order probably is not.

Image: Flowchart for determining the appropriate chart types

Use the following flowchart to determine which chart types are appropriate to your data. In addition, the flowchart visually presents the methods and properties to use with your chart:

Determining the Chart Type for One Set of Numeric Data

Use the following procedure to determine the chart type and methods and properties to use for one set of numeric data:

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

1. Pass numeric data to SetDataYAxis.
2. Pass non-numeric data to SetDataXAxis.
3. Set the IsTrueXY property to False.
4. Does the numeric data include 0 or negative values? If yes, finish by selecting one of these appropriate chart types:
   - Bar (2D and 3D)
   - Stacked bar (2D and 3D)
   - Horizontal bar
   - Horizontal stacked bar
   - Line
   - Histogram

   Note: Negative values cannot be displayed in any type of percent bar chart.

5. Otherwise, do you have other non-numeric data to display? If no, finish by selecting one of these appropriate chart types:
   - Pie (2D and 3D)
   - Ring (2D and 3D)
   - Bar (2D and 3D)
   - Stacked bar (2D and 3D)
   - Percent bar (2D and 3D)
   - Horizontal bar
   - Horizontal stacked bar
   - Horizontal percent bar
   - Line
   - Histogram

6. Otherwise, select one of these appropriate chart types:
   - Bar (2D and 3D)
   - Stacked bar (2D and 3D)
   - Percent bar (2D and 3D)
   - Horizontal bar
   - Horizontal stacked bar

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- Horizontal percent bar
- Line
- Histogram

7. (Optional) Finish by passing non-numeric data to SetDataSeries.

Determining the Chart Type for Two Sets of Numeric Data

Use the following procedure to determine the chart type and methods and properties to use for two sets of numeric data:

1. Do you have other non-numeric data to display? If no, complete steps 2 and 3:
2. Select one of these appropriate chart types:
   - Line.
   - Histogram.
   - Scatter.
   - Funnel (with both actual and target data).
   - Overlay.
3. Use these methods and properties for scatter, line, and histogram charts:
   a. Pass numeric data to SetDataYAxis.
   b. Pass numeric data to SetDataXAxis.

   Note: For a trueXY line chart, be sure to sort the data on the field that you pass into the SetDataXAxis method. You can use the Sort method of the Rowset class to sort the data.

   c. Set the IsTrueXY property to True.
4. Otherwise, if you have non-numeric data to display in a funnel chart, complete the following:
   a. Pass the non-numeric data to SetDataXAxis.
   b. Pass numeric data to SetFunnelDataActual. (Alternatively, pass the numeric data to SetDataYAxis).
   c. (Optional) Pass numeric data to SetFunnelDataTarget.
   d. Set the IsTrueXY property to False.
5. Otherwise, if you have non-numeric data to display in an overlay chart, complete the following:
   a. Pass numeric data to SetDataYAxis.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

b. Pass the non-numeric data to SetDataXAxis.

c. Pass the record containing the overlay data to SetOLData.

d. Pass numeric data to SetOLDataYAxis.

e. Pass non-numeric data to SetOLDataXAxis.

f. Set the OLType property to %ChartType_2DLine.

g. Set the IsTrueXY property to False.

Determining the Chart Type for Three Sets of Numeric Data

Use the following procedure to determine the chart type and methods and properties to use for three sets of numeric data:

1. Select the appropriate chart type: Bubble.
2. Pass numeric data to SetDataYAxis.
3. Pass numeric data to SetDataXAxis.
4. Pass numeric data to SetDataGlyphScale.
5. Set the IsTrueXY property to True.
6. (Optional) Pass non-numeric data to SetDataSeries.

Setting Chart Colors

Chart colors are determined in the following ways:

- Automatically.
- By using the SetColorArray method to specify an array of color choices.
- By using the SetDataColor method to specify a field on a record that holds a color value.

Automatic color determination occurs when neither of the other two methods is used. For all charts except pie charts, each data series is assigned a color; all data points within a series share that color. For pie charts each data point is assigned its own color. In that way it's easier to distinguish pie segments from one another. Here is an example of the base data that will be charted:

Year	***Review Rating***	***Percent***	***Color***
2011	1-POOR	2.00	0
2011	2-FAIR	5.00	1
2011	3-GOOD	50.00	2
2011	4-VERY GOOD	20.00	3

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Year	*Review Rating*	*Percent*	*Color*
2011	5-OUTSTANDING	10.00	4
2011	6-NONE	13.00	5
2012	1-POOR	5.00	6
2012	2-FAIR	10.00	7
2012	3-GOOD	15.00	8
2012	4-VERY GOOD	20.00	9
2012	5-OUTSTANDING	10.00	10
2012	6-NONE	40.00	11

The Review Rating field is assigned to the x-axis, Percent is assigned to the y-axis, and Year is assigned to the data series:

```
&cChart.SetData(Record.CJY_RVW_DSTRBTN);
&cChart.SetDataXAxis(CJY_RVW_DSTRBTN.CJY_RVW_RTG);
&cChart.SetDataYAxis(CJY_RVW_DSTRBTN.CJY_DSTRBTN_PCT);
&cChart.SetDataSeries(CJY_RVW_DSTRBTN.CJY_YR);
```

Note: In the following examples, because pie charts can display one series of numeric data only, the pie charts reflect data from the first six rows only (the first data series). The bar charts reflect both series of data.

Image: Bar and pie charts using automatic color generation

Automatic color generation results in the following bar and pie charts:

SetColorArray allows you to create an array of color values in PeopleCode and pass that to the charting engine for use in rendering the chart. It works the same way as using automatic color assignment, except that it allows you to pass in a color sequence that differs from the style sheet's default sequence. For bar charts, each data series is assigned a color; all data points within a series share that color. In the preceding example, all data for the year 2011 is displayed in blue bars; for the year 2012, in red bars. For pie charts each data point is assigned its own color.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Using the same data as before, the SetColorArray method can be used to specify a color array:

```
&clr_array = CreateArray(%ChartColor_Black,%ChartColor_Blue,%ChartColor_Cyan,%Chart⇒
Color_DarkGray,%ChartColor_Gray, %ChartColor_Green);

rem The preceding is equivalent to CreateArray(0,1,2,3,4,5);

&cChart.SetColorArray(&clr_array);
```

Image: Bar and pie charts using the specified color array

Specifying the color array results in these charts:

SetDataColor works a bit differently from SetColorArray. By using the value of a record field, SetDataColor provides more granular control of bar chart colors, in that you can vary bar color data point by data point and not by the higher level data series:

```
&cChart.SetDataColor(CJY_RVW_DSTRBTN.CJY_COLOR);
```

Image: Bar and pie charts using the specified data color values

Note that in the preceding data grid, each row of data also includes a color value. The charts that result are:

If both SetColorArray and SetDataColor are set for a chart, SetDataColor takes precedence and SetColorArray is ignored.

Setting Chart Legends

The chart property HasLegend must be set to true for a legend to appear.

```
&cChart.HasLegend = True;
```

Legend entries are determined in two ways:

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- Automatically
- By using the SetLegend method to specify an array of legend entries

Image: Bar and pie charts using automatic legend generation

Here are charts that have automatically generated legend entries:

The default position for the legend is to the left of the chart. Set the chart property LegendPosition to move the legend to other locations next to the chart.

A legend entry provides a text description that explains what a color in the chart represents. The colors in the legend are sequenced in the same order as the data and colors are sequenced in the chart.

In all chart types except pie charts, the default legend entries describe the data series. In a pie chart, the default legend entries describe the data points (that is, the pie segments). In a pie chart if you have a legend, each pie chart segment is automatically labeled with the percentage it contributes to the whole.

If you use SetLegend to create legend entries, as an application developer you must ensure that the number of entries in the legend array matches exactly the number of data points that appear in your chart.

```
&LegendArray = CreateArray("Entry 1", "Entry 2");
&cChart.SetLegend(&LegendArray);
```

Image: Bar and pie charts using the specified legend array

These charts use the specified legend array:

Note that in the case of the pie chart, there were not enough legend entries in the array to account for all the segments in the pie chart. Therefore, for the pie chart, the default legend was used.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

If the number of entries in the array is increased to match the number of pie slices, there are more entries than are needed for the bar chart, which produces several undesirable results.

```
&LegendArray = CreateArray("Entry 1", "Entry 2", "Entry 3", "Entry 4", "Entry 5", "⇒
Entry 6");
&cChart.SetLegend(&LegendArray);
```

Image: Bar and pie charts using a legend array that matches the number of pie segments

The bar chart displays one data series only (for 2011), and no legend is displayed:

If the number of entries is increased to be larger than needed for either the bar chart or the pie chart, similar undesirable results are displayed for the bar chart.

```
&LegendArray = CreateArray("Entry 1", "Entry 2", "Entry 3", "Entry 4", "Entry 5", "⇒
Entry 6", "Entry 7");
&cChart.SetLegend(&LegendArray);
```

Image: Bar and pie charts using a legend array that is greater than the number of pie segments

In this case, the pie chart reverts to the automatically generated legend:

If color is set by SetDataColor and the default legend is chosen, the bar chart only shows legend entries for the data series.

```
&cChart.SetDataColor(CJY_RVW_DSTRBTN.CJY_COLOR);
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
&cChart.HasLegend = True;
```

Image: Bar and pie charts using default legends and set data colors

However, since the series is not by color, the legend for the bar chart is meaningless. The pie chart appears correct.

If color is set by SetDataColor and the legend array is larger than needed for either chart type, the results are also undesirable.

```
&cChart.SetDataColor(CJY_RVW_DSTRBTN.CJY_COLOR);
&cChart.HasLegend = True;
&LegendArray = CreateArray("Entry 1", "Entry 2", "Entry 3", "Entry 4", "Entry 5", "⇒
Entry 6", "Entry 7", "Entry 8", "Entry 9", "Entry 10", "Entry 11", "Entry 12");
```

Image: Bar and pie charts with a legend array larger than needed by either chart

The bar chart shows only one series of data (2011) and the legend iis not correct. The pie chart uses the default legend.

If color is set by SetDataColor and the legend array is the size required by the pie chart, the results are also undesirable.

```
&cChart.SetDataColor(CJY_RVW_DSTRBTN.CJY_COLOR);
&cChart.HasLegend = True;
&LegendArray = CreateArray("Entry 1", "Entry 2", "Entry 3", "Entry 4", "Entry 5", "⇒
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
Entry 6");
```

Image: Bar and pie charts with a legend array the size required by the pie chart

The legend for the bar chart is not correct. The pie chart uses the specified legend array.

If color is set by SetDataColor and the legend array is the size required by the bar chart, the desired results are produced for both charts.

```
&cChart.SetDataColor(CJY_RVW_DSTRBTN.CJY_COLOR);
&cChart.HasLegend = True;
&LegendArray = CreateArray("Entry 1", "Entry 2");
```

Image: Bar and pie charts with a legend array the size required by the bar chart

The legends for both charts are correct. The bar chart uses the specified legend array; the pie chart uses the default legend.

Using the ReferenceArea Class

The ReferenceArea class is used in conjunction with the Chart class to display bands of color to be drawn with the chart based on numeric values along a chart axis. For each band of color, you would create a separate instance of the ReferenceArea class.

Creating Reference Areas Using the ReferenceArea Class

The essential steps to use the ReferenceArea class are:

1. Create an instance of the ReferenceArea class in PeopleCode by using the GetReferenceArea built-in function:

   ```
   &ref1 = GetReferenceArea();
   ```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

2. Set the properties on the instance of ReferenceArea class that you created.

3. Add the instance to an array of ReferenceArea instances:

```
&ref_areas = CreateArray(&ref1);
```

Note: For each band of color, you would add a separate instance of the ReferenceArea class to this array.

4. Pass the array into the SetReferenceArea method of the Chart class:

```
&cChart.SetReferenceArea(&ref_areas);
```

Using Reference Areas with Charts

Image: A reference area on a bar chart

To produce a bar chart similar to the following example that displays a reference area, you would create an instance of the ReferenceArea class:

While it is not required, you could create a user-defined PeopleCode function that returns the array of reference areas.

```
Function bld_ref_areas Returns array;
   &ref1 = GetReferenceArea();
   &ref1.Association = %Ref_Association_Y1;
   &ref1.Description = "1 STD from Mean";
   &ref1.ShortText = "Ref Area1";
   &ref1.IsDisplayedTextInLegend = True;
   &ref1.ReferenceAreaColor = %ChartColor_Yellow;
   &ref1.ReferenceAreaValues = CreateArray(50000, 30000);
   &ref_areas = CreateArray(&ref1);
   Return &ref_areas;
End-Function;
```

Then, you associate the array returned by this function to the instance of Chart class using the SetReferenceArea method:

```
&cChart.SetReferenceArea(bld_ref_areas());
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

ReferenceArea Class Properties

Using the ReferenceLine Class

The ReferenceLine class is used in conjunction with the Chart class to display colored lines to be drawn with the chart based on numeric values along a chart axis. For each reference line, you would create a separate instance of the ReferenceLine class.

Creating Reference Lines Using the ReferenceLine Class

The essential steps to use the ReferenceLine class are:

1. Create an instance of the ReferenceLine class in PeopleCode by using the GetReferenceLine built-in function:

   ```
   &refln1 = GetReferenceLine();
   ```

2. Set the properties on the instance of ReferenceLine class that you created.

3. Add the instance to an array of ReferenceLine instances:

   ```
   &ref_lines = CreateArray(&refln1);
   ```

   Note: For each reference line, you would add a separate instance of the ReferenceLine class to this array.

4. Pass the array into the SetReferenceLine method of the Chart class:

   ```
   &cChart.SetReferenceLine(&ref_lines);
   ```

Using Reference Lines with Charts

Image: A reference line on a bar chart

To produce a chart similar to the following example that displays a reference line, you would create an instance of the ReferenceLine class:

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

While it is not required, you could create a user-defined PeopleCode function that returns the array of reference lines.

```
Function bld_ref_lines() Returns array;
   &refln1 = GetReferenceLine();
   &refln1.Association = %Ref_Association_Y1;
   &refln1.Description = "Average";
   &refln1.ShortText = "Avg";
   &refln1.IsDisplayedTextInLegend = False;
   &refln1.ReferenceLineLocation = %Ref_Back;
   &refln1.ReferenceLineColor = %ChartColor_Red;
   &refln1.ReferenceLineValue = CJY_CHRT_REF_WK.CJY_AMT;
   &reflines = CreateArray(&refln1);
   Return &reflines;
End-Function;
```

Then, you associate the array returned by this function to the instance of Chart class using the SetReferenceLine method:

```
Function bld_chrt();
   &cChart = GetChart(CJY_CHRT_REF_WK.CJY_CHRT1);
   &cChart.Reset();
   &cChart.SetData(Record.CJY_SLRY);
   &cChart.SetDataXAxis(CJY_SLRY.CJY_NM);
   &cChart.setDataYAxis(CJY_SLRY.CJY_SLRY);
   &cChart.SetReferenceLine(bld_ref_lines());
End-Function;
```

Related Links

ReferenceLine Class Properties

Scope and Data Type of a Chart Object

A Chart object can be instantiated only from PeopleCode. You can use this object only in PeopleCode programs that are associated with an online process, not in an Application Engine program, a message notification, a Component Interface, and so on.

Chart objects are declared using the Chart data type. For example:

```
Local Chart &MyChart;
```

```
Component Chart &Abs_Hist_Chart;
```

Error Handling

The PeopleCode program is terminated if a field or record is missing at runtime.

If a valid record is specified but no data is found, or for any other error, the chart is replaced by the message "Image creation failed."

If the Java Runtime Environment (JRE) is missing, an error appears and is logged.

Chart Class Methods and Properties by Category

The following topics subdivide the Chart class methods and properties by functional category.

The categories are divided among the different parts of a chart. However, all methods and properties are used with the chart object; a chart has no sub-objects.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Chart Data Methods and Properties

Use chart data methods and properties to set x and y axes data.

See Reset, SetData, SetDataHints, SetDataSeries, SetDataURLs, SetDataXAxis, SetDataYAxis, DataStartRow, SetFunnelDataActualSetFunnelDataTargetDataWidth, ImageMap, IsTrueXY.

Chart Appearance Properties

Use chart appearance properties to set the type of graph, the line style, and so on.

See Height, IsDrillable, IsPlainImage, Type, Width.

Chart Color Methods

Use chart color methods to set and manipulate colors for either a series or for each point.

See SetColorArray, SetDataColor.

Chart Axis Methods and Properties

Use chart axis methods and properties to further control the appearance of axes.

See SetXAxisLabels, SetYAxisLabels, XAxisLabelOrient, XAxisTicks, YAxisLabelOrient, YAxisMax, YAxisMin, YAxisTicks.

Chart Title Properties

Use chart title properties to set the text and style of titles for the graph and the axes.

See MainTitle, XAxisTitle, XAxisTitleOrient, YAxisTitle, YAxisTitleOrient.

Chart Legend Methods and Properties

Use chart legend methods and properties for each series legend.

See SetLegend, HasLegend, LegendMaxEntries, LegendPosition.

Chart Overlay Methods and Properties

Use chart overlay methods and properties to set and manipulate overlay data.

See SetOLData, SetOLDataSeries, SetOLDataXAxis, SetOLDataYAxis, OLType.

Scatter Chart Methods and Properties

Use scatter chart methods and properties to set and manipulate scatter charts and bubble charts.

See SetDataAnnotations, SetDataGlyphScale, ShowCrossHair.

TrueXY Line Chart Properties

Use trueXY line chart properties to set and manipulate trueXY line charts.

See XAxisMax, XAxisMin, XAxisPrecision, YAxisCrossPoint, YAxisMax, YAxisMin, YAxisPrecision.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Using the Gauge Classes

This section provides an overview of gauge terms and discusses:

- Gauge types.
- Creating gauges using the gauge classes.
- Design guidelines.
- Scope and data type of gauge objects.
- Using the Threshold class.
- Error handling.
- Properties by category.

Understanding Gauge Terms

The following is a list of terms pertaining to the gauge classes and their descriptions:

Metric	Refers to the actual numeric data point that you want to display in the gauge.
Tick marks	Refers to the major and minor markings along the value axis of the gauge.
Threshold values	(Optional) Provide additional context about the metric that you display in your gauge. On dial and status meter gauges you can add bands of color to the background by associating an instance of the Threshold class, typically to help indicate whether the metric is low, medium, or high.

Gauge Types

Use the gauge classes to create gauges that display metrics in several common formats, including dials, status meters, and LEDs.

Three gauge classes are available: DialGauge, LEDGauge, and StatusMeterGauge. Even though each of these gauges must be implemented and instantiated as different classes, these gauges share many common characteristics, including the methods you can invoke and the properties you can set.

The following examples use the same value, 54.5, as the gauge metric. In addition, an instance of the Threshold class is used to specify the color shading on the dial gauge and the status meter gauge, as well as the color of the LED.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example of a Dial Gauge

Image: Example of a dial gauge

The following example displays a dial gauge:

Example of an LED Gauge

Image: Example of an LED gauge

The following example displays an LED gauge:

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example of a Status Meter Gauge

Image: Example of a status meter gauge

The following example displays a status gauge:

Characteristics of a Gauge

Image: Features of a gauge

The following example displays features of gauges on a dial gauge:

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Creating Gauges Using the Gauge Classes

You can specify a field in a rowset and have it depicted graphically as a gauge with minimal PeopleCode. The data in the field must be numeric. You can also choose to make the gauge interactive.

The high-level steps involved in creating any gauge are:

1. Identify a field on a record that has a numeric value that you want to show in a gauge.
2. Add a chart area to a page in Application Designer. Associate the record and field in Step 1 with that chart area.
3. In PeopleCode instantiate a gauge object using one of the built-in functions available for gauges:
   - GetDialGauge
   - GetStatusMeterGauge
   - GetLEDGauge
4. Set property values for the gauge object as needed, keeping in mind the design guidelines below. Most properties have default values, so you can start by reviewing your gauge with no properties set and then set those that you need to in order to tailor the appearance and functionality of the gauge.
5. Optionally, create an instance of the Threshold class and associate it with your instance of the gauge.

Design Guidelines

Sizing

You determine the height and width of the gauge area. If height and width properties are not specified in PeopleCode, then the dimensions of the gauge area will be determined by the dimensions of the chart area that is defined in the page definition in Application Designer.

The overall dimensions of the gauge area will be used and will need to hold all the elements that you choose to have along with the gauge graphic itself. This includes:

- Top labels
- Bottom labels
- Metric labels
- Legends

The more elements that you want to include in the gauge area, the smaller the gauge graphic will become. The gauge rendering software will try to make a best fit.

As you design your gauge, it's important to carefully consider what you want your gauge to contain and to review the results of your gauge as you use edge cases of small and large values and labels as well as most likely cases. Also, consider the design of your gauge in the context of the rest of the page in which the gauge will appear. For example, do other elements on the page provide enough context so that you can reduce or eliminate the use of labels and legends in the gauge area?

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Scaling

You can use the GaugeMinimum and GaugeMaximum properties to provide the low and high points of your dial or status meter gauge. Knowledge of the nature of your data will help you determine an appropriate scale.

You'll also want to consider for a gauge whether you want the gauge minimums and maximums to be static (for example, minimum of 0 and maximum of 100 because test results can only fall within that range), or whether you want them to be dynamic (for example, make the minimum half of the metric value and make the maximum 50% greater than the metric value.

Labels

Three types of labels can be placed in the gauge – a top label, a bottom label, and a label for the metric. The top and bottom labels are customizable – they can be any text you desire. The metric label will always be the numeric value of the gauge metric.

The labels can be positioned in different locations along with the gauge. Any label can be placed inside the gauge. Additionally, top labels can appear above the gauge, bottom labels can appear below the gauge, and metric labels can be positioned with the bottom label or below it.

Generally, it's better to constrain the use of labels to the minimum needed. Labels will take up space from the gauge itself, making the gauge smaller, and too much text in a label can result in ellipses that don't look good and can be difficult to read.

Reference Areas and Legends

You can provide additional context about the metric that you display in your gauge by associating an instance of the Threshold class to the gauge using the SetThreshold method (available with all gauge classes). On dial and status meter gauges, you can add bands of color to the gauge background, typically to help indicate whether the metric is low, medium, or high. On LED gauges the values in the threshold instance determine the color and direction of the LED.

For more information on using the Threshold class, see Using the Threshold Class.

A legend is available if you use thresholds. The legend will show the colors and descriptions of all reference areas on your gauge.

Tick Marks

Tick marks on dial and status meter gauges can often provide useful context information but possibly at the cost of making the gauge appear busy and cluttered. You should try them to see if they work for your situation.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Interactivity

You can make your gauges interactive. You can either run FieldChange PeopleCode or redirect users to a URL. Interactivity will be initiated when a user clicks on (or touches) the gauge.

Image: Gauge interactivity flowchart

As illustrated in the following flowchart, in order to have your gauge be interactive, you must set the IsDrillable property to True. Then, if you have set the GaugeURL property to a valid URL, a click will redirect the user to that URL. If GaugeURL is not set, but there is FieldChange PeopleCode on the field that defines the gauge's metric (that is, the field you passed into the GetDialGauge, GetStatusMeterGauge, or GetLEDGauge function), then that PeopleCode will run. Otherwise, if neither

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GaugeURL is set nor FieldChange PeopleCode is present, then there is no interactivity even if IsDrillable is True.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Using the Threshold Class

The Threshold class is used in conjunction with the three gauge classes: DialGauge, LEDGauge, and StatusMeterGauge. The Threshold class provides a way to add reference areas and color coding to your gauges.

Image: A dial gauge with color banding from a Threshold object

On dial and status meter gauges, the Threshold class can be used to display “reference areas” on the gauge.

Image: An LED gauge colored by a Threshold object

On the LED gauge, the Threshold class can be used to color the LED gauge according to the defined threshold values.

Creating Thresholds Using the Threshold Class

To use the Threshold class, follow these basic steps:

1. Create an instance of the Threshold class in PeopleCode by using the GetThreshold built-in function:

   ```
   &thrshld = GetThreshold();
   ```

2. Set the properties on the instance of Threshold class that you created.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

3. Associate the instance of the Threshold class to an instance of one of the gauge classes.

```
&gauge.SetThreshold(&thrshld);
```

Using Thresholds with Gauges

Image: A simple dial gauge

The following example presents a simple dial gauge with color banding from the Threshold class:

To render the gauge in this way, you would create an instance of the Threshold class. Each property of the Threshold class is an array that you would populate as follows:

Values array	***Colors array***
Value of first threshold	Yellow
Value of the second threshold	Green
NA	Red

A user-defined PeopleCode function that instantiates this instance of the Threshold class looks like this:

```
Function bld_thrshld Returns Threshold;
   Local Threshold &thrshld;
   &thrshld = GetThreshold();
   &thrshld.Values = CreateArray(CJY_SLRY.CJY_SLRY_MIN, CJY_SLRY.CJY_SLRY_MAX);
   &thrshld.Colors = CreateArray(%ChartColor_Yellow, %ChartColor_Green, %ChartColor⇒
_Red);
   Return &thrshld;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
End-Function;
```

Image: A dial gauge with automatically generated data hints

The data hints for the gauge are automatically created based on the values defined in the Values array. For example, 59K was specified as the minimum and 88K as the maximum:

Image: A dial gauge with an automatically generated legend

Moreover, if you decided to display a legend for the gauge, legend entries are automatically generated as well:

However, you can add a Descriptions array to control what is displayed in data hints and in the legend:

Values array	*Descriptions array*	*Colors array*
Value of first threshold	Below Range	Yellow
Value of the second threshold	Within Range	Green

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Values array	*Descriptions array*	*Colors array*
NA	Above Range	Red

Image: Data hints from the Descriptions array

Now, the data hints will look like this:

Image: A legend from the Descriptions array

If you want a legend, it will look like this:

The Descriptions array is added to the same user-defined PeopleCode function:

```
Function bld_thrshld Returns Threshold;
   Local Threshold &thrshld;
   &thrshld = GetThreshold();
   &thrshld.Values = CreateArray(CJY_SLRY.CJY_SLRY_MIN, CJY_SLRY.CJY_SLRY_MAX);
   &thrshld.Descriptions = CreateArray("Below Range", "Within Range", "Above Range"⇒
);
   &thrshld.Colors = CreateArray(%ChartColor_Yellow, %ChartColor_Green, %ChartColor⇒
_Red);
   Return &thrshld;
End-Function;
```

Related Links

Threshold Class Properties

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Scope and Data Type of Gauge Objects

Any gauge and threshold objects can be instantiated from PeopleCode only. You can use these objects only in PeopleCode programs that are associated with an online process, not in an Application Engine program, a message notification, a component interface, and so on.

Gauge objects are declared using the one of the three gauge classes data types. For example:

```
Component DialGauge &oDial;
Component LedGauge &oLED;
Component StatusMeterGauge &oSM;
```

In addition, threshold objects are declared using the Threshold class:

```
Component Threshold &oThrshld;
```

Error Handling

The PeopleCode program is terminated if a field or record is missing at runtime.

If a valid record is specified but no data is found, or for any other error, the chart is replaced by the message "Image creation failed."

If the Java Runtime Environment (JRE) is missing, an error appears and is logged.

Properties of the Gauge Classes

The properties can be grouped as follows:

- Gauge type - You can select different visual representations for each gauge class
- Minimums and maximums – You can specify the range of values that you want the gauge to cover
- Labels - You can determine which, if any, labels, you want to accompany the gauge
- Tick marks - Tick marks can be added if more numeric context is needed.
- Legend- A legend can be displayed to help users interpret the reference areas.
- Animation – You can choose the type and duration of animation for the gauge display.
- Interactivity – You can choose to have an event occur if the user clicks (or touches) the gauge.

Category	***DialGauge***	***LEDGauge***	***StatusMeterGauge***
Gauge type	Type	Type	Type
Minimums and maximums	Height	Height	Height
	Width	Width	Width
	GaugeMinimum	NA	GaugeMinimum
	GaugeMaximum	NA	GaugeMaximum
	GaugeDecimalDigit	GaugeDecimalDigit	GaugeDecimalDigit

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Category	*DialGauge*	*LEDGauge*	*StatusMeterGauge*
Labels	TopLabel	TopLabel	TopLabel
	BottomLabel	BottomLabel	BottomLabel
	TopLabelPosition	TopLabelPosition	TopLabelPosition
	BottomLabelPosition	BottomLabelPosition	BottomLabelPosition
	MetricLabelType	MetricLabelType	MetricLabelType
	MetricLabelPosition	MetricLabelPosition	MetricLabelPosition
Tick marks	MajorTickIncrement	NA	MajorTickIncrement
	MinorTickIncrement	NA	MinorTickIncrement
	TickLabelPosition	NA	NA
Legends	LegendPosition	LegendPosition	LegendPosition
Animation	AnimationType	AnimationType	AnimationType
	AnimationDuration	AnimationDuration	AnimationDuration
Interactivity	IsDrillable	IsDrillable	IsDrillable
	GaugeURL	GaugeURL	GaugeURL
Miscellaneous	AdditionalStyleSuffix	AdditionalStyleSuffix	AdditionalStyleSuffix

Using the Gantt Class

Use the Gantt class to create Gantt charts. A Gantt chart displays tasks and milestones along a time line. Gantt charts are frequently used in project management because they provide a graphical illustration of a schedule, which helps in planning, coordinating, and tracking project tasks.

This section provides an overview of Gantt chart terminology and discusses:

- Using Gantt charts in the PeopleSoft Pure Internet Architecture.
- Creating Gantt charts using the Gantt class.
- Specifying time line axis formats.
- Working with start and end dates.
- Using Gantt glyphs.
- Scope and data type of a Gantt object.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- Error handling.

Understanding Gantt Chart Terms

Many of the elements, such as titles and labels, available on conventional chart like the bar chart are also available on the Gantt chart. The following terms apply specifically to Gantt charts:

Activity or Task	See Task.
Baseline	A point-in-time snapshot of the project plan that allows the user to identify how the project plan has changed since that point in time.
Data area	The part of the chart that graphically shows the span of dates that each task (or activity) covers. (This area is the right side of the displayed chart.)
Dependencies	A relationship between one task and other tasks that drives when tasks can begin and end. A dependent task cannot start before the task it is dependent on is either started or completed (depending on business rules defined in the application).
Milestone	A specialized mark on the chart that names a meaningful point in time.
Resource	A source of supply or support that is assigned to work on an activity or task.
Task or Activity	In a Gantt chart, each row (task or activity), is represented in the y-axis of the chart, and the span of dates for each row is displayed on the x-axis.
X-axis	The x-axis displays dates that are spanned by items in the y-axis.
X-axis labels	The part of the chart that lists the time scale. The x-axis labels support multiple levels of granularity: second, minute, hour, day, week, month, year.
Y-axis	The y-axis is the display of tasks or activities, and is displayed as rows.
Y-axis labels	The part of the chart that lists activities and their attributes. Activities are shown hierarchically, and subtasks can be hidden or displayed by expanding or collapsing higher level tasks.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Using Gantt Charts in the PeopleSoft Pure Internet Architecture

Image: Example Gantt chart

The Gantt chart consists of two sections: a table section and a chart section.

The left side of the chart, where you see the table, is the table section. The other side, where you see the bars, is the chart section. Horizontal scroll bars below the table section support scrolling through the task-related columns; below the task section, they support scrolling through the charted tasks. Vertical scroll bars (when present) support scrolling through the task list.

Table Section

The table section contains all of the tasks and associated subtasks, and displays them in a hierarchy. Tasks that contain subtasks are called *parent tasks,* and subtasks are called *child tasks*. You can click on the expand (collapse) image to the left of the task name (Baby, above) to expand or collapse the subtask hierarchy. Note that subtasks may also act as parent tasks to other subtasks.

Each task has a name (Born, Baby, Childhood, and so on). It also has a level. Parent tasks have a higher level than child tasks.

Chart Section

The chart section displays the tasks, task dependencies, and milestones graphically.

In the previous example, each horizontal bar represents a single task. The progress bar (that is, the percentage complete for a particular task) is indicated with a bar of a different color above the task bar. The milestone date (Graduate in the previous example) is represented with a circle.

You can also have dependencies between tasks. These are represented as lines connecting the task bars.

You can execute custom FieldChange PeopleCode when a user clicks a task bar or a task dependency line.

User Interaction

A user can interact directly with a chart to change the underlying chart data.

These user actions are supported:

- Resize the task bar.
- Reposition the task bar.
- Reposition a milestone glyph.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- Move the separator between the table section and the chart section.
- Update task details, task start time and end time, and the progress bar.

When a user changes values in the chart section by dragging and dropping bars, the Planned Start, Planned End, and Progress values in the grid column will also be updated if the grid and the chart section use the same record and fields.

Note: Drag-and-drop is not supported on an Apple iPad.

You can control the level the user is able to interact with the chart using the Gantt class properties InteractiveStart, InteractiveEnd, InteractiveProgress, and InteractiveMove.

See InteractiveStart, InteractiveEnd, InteractiveProgress, InteractiveMove.

Creating Gantt Charts Using the Gantt Class

Every Gantt chart has at least one data set used to define the tasks and the information related to each task, such as start date, end date, milestones, percent finished, and so on.

A second data set can be used to describe dependencies between tasks.

The following methods are required for using the Gantt chart:

- SetTaskData

  Use this method to specify where most of the information for the Gantt chart is stored. You can specify either a rowset or a record.

- SetTaskID

  Use this method to specify the task ID, or name, of the task. Every task must have a unique task identifier. The task ID is used to support task linking and dependencies.

- SetPlannedStartDate

  Use this method to specify the planned starting date of the task. Each task must have its own planned starting date.

- SetPlannedEndDate

  Use this method to specify the planned ending date of the task. Each task must have its own planned ending date.

Though not required, Oracle recommends using the SetTaskName method to display meaningful information in the table section of the Gantt chart.

If you only use the required methods and do not use the SetTaskAppData method, Oracle recommends that you also use the SetChartArea method and dedicate most, if not all, of the entire area to the chart, and not the table.

If you specify one actual date, either for start or end, then you must specify the other (SetActualStartDate, SetActualEndDate).

In addition, if you want to use dependency data, the following methods are required:

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- SetTaskDependencyData

  Use this method to specify where most of the information for the dependency data is stored. You can specify either a rowset or a record.

- SetTaskDependencyParentID

  In a dependency, one task depends on another. Use this method to specify the parent task, that is, the one that the other (child) task depends upon.

- SetTaskDependencyChildID

  In a dependency, one task depends on another. Use this method to specify the child task, that is, the one that depends on another.

Specifying Time Line Axis Formats

The date-time axis (the x-axis) of a Gantt chart is referred to as the “time line” axis. You can control the display label format for the time line through a combination of user personalization settings and various Gantt class methods for setting date entity formats. These settings and methods are described in this documentation. The time line’s start and end can also be adjusted by using the Timeline Range picker or by using the AxisStartDateTime and AxisEndDateTime methods. If none of the properties or methods is set for controlling the time line, then the charting engine plots the time line based on the time difference between the earliest start date and latest end date of all tasks in the Gantt chart.

The time line axis can display the following units of measure: years, months, days, hours, minutes, and seconds. The time line does not support the following units: centuries, quarter years (such as Q1, Q2, and so on), weeks, and milliseconds.

Depending on the time difference between the earliest start date/time and latest end date/time of the data displayed in the Gantt chart, the chart is displayed with a minor axis only, or with major and minor axes.

Image: Time line with minor axis only (years)

The following Gantt chart displays a minor axis only due to the wide range between the start and end dates of the displayed data:

Valid pairs of major and minor axes include:

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- Year and month
- Month and day
- Day and hour

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- Hour and second

Image: Time line with a major axis (year) and minor axis (months)

The following Gantt chart displays both a major and a minor axis:

Image: Timeline Range picker

The Timeline Range picker is activated by a clicking a date on the time line. Use the Timeline Range picker to specify the start and end date and time for the data to be displayed in the Gantt chart:

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Image: Timeline Range picker with date slider

The date slider is activated by clicking a time in the Timeline Range picker. Click AM or PM to toggle between these two settings.

Working with Start and End Dates

You must set the end date to be after the start date, for both the planned as well as actual dates, or else you will receive an error.

Both the start and end dates you specify for a task must fall within the axis dates, that is, the dates specified by the AxisEndDateTime and AxisStartDateTime properties. If you specify task dates that fall outside of the axis dates, the task appears in the table section of the Gantt chart, but no bar appears in the chart section of the Gantt chart, even if one of the dates falls *inside* the axis dates.

Using Gantt Glyphs

You can use all of the following glyphs with a Gantt chart. You can use either the numeric or constant value.

Note: For values that have been deprecated, the new value is substituted automatically.

Numeric Value	*Constant Value*	*Glyph*	*Notes*
1	%ChartGlyph_Axe	NA	This constant has been deprecated; use %ChartGlyph_X (17) instead.
2	%ChartGlyph_Bar	NA	This constant has been deprecated; use %ChartGlyph_ Exclamation (13) instead.
3	%ChartGlyph_Box	NA	This constant has been deprecated; use %ChartGlyph_ Fisheye (25) instead.
4	%ChartGlyph_Circle	●	NA

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Numeric Value	*Constant Value*	*Glyph*	*Notes*
5	%ChartGlyph_Cross	NA	This constant has been deprecated; use %ChartGlyph_Dagger (20) instead.
6	%ChartGlyph_Diamond	◆	NA
7	%ChartGlyph_Dodecahedron	NA	This constant has been deprecated; use %ChartGlyph_Triangle_Inverted (18) instead.
8	%ChartGlyph_Icosahedron	NA	This constant has been deprecated; use %ChartGlyph_Star (11) instead.
9	%ChartGlyph_Sphere	NA	This constant has been deprecated; use %ChartGlyph_CrossHairs (21) instead.
10	%ChartGlyph_Square	■	NA
11	%ChartGlyph_Star	★	NA
13	%ChartGlyph_Exclamation	!	NA
14	%ChartGlyph_QuestionMark	?	NA
15	%ChartGlyph_Asterisk	✻	NA
16	%ChartGlyph_Check	✓	NA
17	%ChartGlyph_X	×	NA
18	%ChartGlyph_Triangle_Inverted	▼	NA
19	%ChartGlyph_Dollar	$	NA
20	%ChartGlyph_Dagger	†	NA
21	%ChartGlyph_CrossHairs	⊕	NA
22	%ChartGlyph_Euro	€	NA
23	%ChartGlyph_Yen	¥	NA
24	%ChartGlyph_PoundSterling	£	NA
25	%ChartGlyph_Fisheye	◉	NA

Scope and Data Type of a Gantt Object

A Gantt object can be instantiated only from PeopleCode. You can use this object only in PeopleCode programs that are associated with an online process, not in an Application Engine program, a message notification, a Component Interface, and so on.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Gantt objects are declared using the Gantt data type. For example:

```
Local Gantt &MyGantt;
```

Error Handling

The PeopleCode program is terminated if a field or record is missing at runtime.

If a valid record is specified but no data is found, or for any other error, the chart is replaced by the message "Image creation failed."

Using the OrgChart Class

Use the OrgChart class to create organization charts. An organization chart represents hierarchical data as boxes arrayed in levels, which can be oriented top to bottom, with horizontal rows, or left to right, with vertical rows. Connectors show parent and child relationships between boxes on adjacent levels.

You can use this chart type to display many different types of hierarchical relationships, including, but not limited to:

- People in organizations
- Positions in organizations
- Departments in organizations
- Components in bills of materials

This section provides an overview of organization chart terminology and discusses:

- Using organization charts in the PeopleSoft Pure Internet Architecture.
- Creating organization charts using the OrgChart class:
  - Overview of creating an organization chart.
  - Creating an organization chart.
  - Displaying breadcrumbs (optional).
  - Defining descriptors.
  - Implementing menus and drop-down lists (optional).
  - Configuring related action menus.
  - Configuring the node record for drop-downs.
  - Configuring drop-downs.
  - Populating the drop-down rowset.
  - Setting drop-down styles.
  - Configuring IM presence (optional).

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

  - Designing organization chart nodes.
  - Implementing node views (optional).
  - Implementing zoom schemas (optional).
  - Specifying scroll types.
  - Configuring connector lines and node borders.

- Organization chart actions and events.
- Organization chart subrecord definitions.
- Minimum methods and properties.
- Scope and data type of an OrgChart object.

Understanding Organization Chart Terms

Organization charts can be composed of many different elements, such as the main chart, nodes, connectors, pop-up nodes, and so on. These terms apply specifically to organization charts:

Breadcrumbs

You can configure an organization chart to optionally display links at the top of an organization chart. Typically, these are the names of people in an organization hierarchy.

Child node

A node that is one level below its parent node (except for the top-level node).

Every node except the top-level node has one parent node.

Connector

Lines that link the boxes in an organization chart. Connectors denote parent and child relationships. A connector also shows the relationship between a pop-up node and the predecessor node of the pop-up.

Descriptor

A text string that conveys information about a node. A main chart node has up to seven descriptors by default, and can be configured with up to 99 descriptors. A pop-up node has up to eight descriptors. Each descriptor can have an image associated with it and can be configured as a link. On the main chart, a descriptor can also be configured as an IM presence icon, a related actions menu, or a button that is associated with a drop-down list box.

FieldChange PeopleCode associated with a descriptor can invoke a pop-up, change the display characteristics of the chart, and perform other processing logic.

Drop-down

You can configure a descriptor as a link associated with a drop-downmenu or a drop down list box. A drop-down can be

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

linkable or read-only. If the drop-down is linkable, PeopleCode related to the descriptor executes when a user clicks a list item.

Header Information that appears at the top of a pop-up.

Level An organization chart is made up of boxes, representing nodes, at different levels. The position of a node in a chart is determined by its parent node (PTPARENT_CHART_ND) and display order (PTND_DISPLAY_ORDER).

Main chart The primary chart in an organization chart showing individual entities, such as employees, in boxes related to one another hierarchically. A user can invoke PeopleCode that displays a pop-up node by clicking a link in a box, or node, of the main chart or by clicking a link in a pop-up node.

Node A representation of a single entity, an individual instance of data, in an organization chart. A node is represented as a box with vertical lines connecting it to its parent node and to its child nodes, if any.

Node record A derived/work record that contains the properties and data values for each node on the main chart.

The node record is created using a clone of the PTORGNODE_SBR subrecord.

Parent node A node that has one or more subordinate nodes, or child nodes, one level below it. Each node can be a parent for other nodes.

Pop-up A new window that displays information specifically related to a node on the main chart or another pop-up.

A pop-up can be invoked from a link on a main chart node or from a link on a pop-up node. FieldChange PeopleCode controls the appearance and content of a pop-up.

Pop-up node A single instance of data on a pop-up. A pop-up can have one or more nodes, all related to one node of the main chart or one node of another pop-up.

Pop-up node record A derived/work record that contains the properties and data values for each pop-up node on the main chart.

The node record is created using a clone of the PTORGPOPUPNODE_SBR subrecord.

Related-actions menu You can configure a descriptor as a related actions menu. A user can select a link from a cascading drop down menu that invokes a related action from the related content framework.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Using Organization Charts in the PeopleSoft Pure Internet Architecture

A PeopleSoft organization chart consists of two parts: the main hierarchical chart and pop-ups that enable the user to access additional related data for each node.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

An organization chart can be oriented vertically or horizontally. Use the Direction to set the orientation of an organization chart.

Image: Vertically oriented organization chart

The following example shows a vertically oriented organization chart:

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Image: Horizontally oriented organization chart

The following example shows a horizontally oriented organization chart:

Main Chart

The main chart can have multiple levels. Each level consists of one or more nodes. Each node represents an individual entity, such as an employee, in the organization. A node has one parent node (except the top-level node, which does not have a parent node) and zero, one, or more child nodes. Each node in the main chart has up to 99 descriptors and each descriptor can be configured as a link or as a button associated with a drop-down list box. Application developers can associate FieldChange PeopleCode with each descriptor link or button associated with a linkable drop-down list box.

Pop-up Chart

A pop-up displays a pop-up chart with information specifically related to the node from which it was invoked. A connector line visually links the pop-up chart to the predecessor node, the node in the chart from which the pop-up was invoked.

If the pop-up contains more nodes than can be displayed (that is, if MaxPopupDisplayNode is set to a number that is less than the total number of nodes) then a scroll bar appears in the pop-up. In some circumstances when a pop-up has a scroll bar and has more than one level, when a user clicks a link on a level other than the top level the new pop-up may not appear in the display area. If this occurs, the user can scroll down using the scroll bar in the initial pop-up to view the new pop-up node.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Note: The amount of time it takes for a pop-up to appear is proportional to the number of nodes in the pop-up. A pop-up with hundreds of nodes may take a long time to appear. An hourglass appears to let the use know the system is working to retrieve the nodes.

A pop-up is invoked through PeopleCode associated with the FieldChange event for a descriptor link on a main chart node or another pop-up node.

A pop-up consists of a header and one or more nodes with each node having up to eight descriptors. Each descriptor can be configured as a link.

The user can drag-and-drop a pop-up node to reposition it but the new position will not be retained after any action that requires a server trip that reloads the chart.

Creating Organization Charts Using the OrgChart Class

When you add an organization chart to a page in Application Designer, you use the chart properties to associate the chart control with a chart record field. You will use this field name to identify the chart in PeopleCode.

You will need to create a record that will be the organization chart node record. The organization chart node record holds the values for the properties and data for each of the nodes of the main chart. If your chart uses pop-ups, you will also need a pop-up node record that holds the values for the properties and data for each of the pop-up nodes.

The organization chart node records must be in the component buffer at runtime. This means that you will have to place them on a page at level one in the component. You can hide them.

The maximum number of nodes you can create is limited according to browser, as shown in the following table:

Browser	***Maximum Nodes***
Google Chrome	600
Microsoft Internet Explorer	250
Mozilla Firefox	1000
Apple Safari	600

The records can have any name, but they must include clones of the PeopleTools-delivered subrecords PTORGNODE_SBR and PTORGPOPUPNODE_SBR. Since the subrecords will carry the FieldChange PeopleCode for the chart, in most cases you should create unique subrecords for each chart.

Your PeopleCode will create and populate two rowsets . These must be component rowsets, linked to the node records of the chart, not standalone rowsets. The organization chart node rowset has one row for each node in the organization chart, and the pop-up node rowset has one row for each pop-up node.

You place FieldChange PeopleCode on the fields of the node records to invoke pop-up charts, update displayed data, process application logic, and refresh the chart.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Overview of Creating an Organization Chart

To create an organization chart you will develop an application that comprises these elements:

- A chart page control that displays the chart on a page.

  You can place more than one chart control on a page. Each chart control must be associated with a different field.

  If more than one pagelet with organization charts appear simultaneously, each chart must be associated with a unique chart record field.

- A chart data record, or organization chart node record, based on the PTORGNODE_SBR subrecord, that contains the data for the chart.

- A PeopleCode program, usually in the page Activate event, that instantiates the chart, links the chart to the chart control, defines the chart attributes, and populates the chart data rowset.

- FieldChange PeopleCode programs associated with the chart data record fields.

  See Organization Chart Actions and Events.

Depending on which organization chart features your chart implements, you may need to include these elements in your application:

- A pop-up chart data record, based on the PTORGPOPUPNODE_SBR subrecord.

- A breadcrumb record, based on the PTORGCRMB_SBR subrecord.

- Drop-down list records, based on the PTORGBOXLIST_SBR and PTORGBOXFLD_SBR subrecords.

- A node display record, based on the PTNODE_DISP_SBR subrecord.

- An IM data record, based on the PTORGIM_SBR subrecord.

- Additional PeopleCode to manage the corresponding record data and set attributes for the chart features.

- FieldChange PeopleCode programs associated with the corresponding record fields.

  See Organization Chart Actions and Events.

The chart data record and all of the records you use to implement organization chart features, such as the pop-up data record, drop down list records, node display record, must be in the component buffer at runtime.

If your application implements zooming, or schema levels, you will need to incorporate PeopleCode to manage the schema levels.

See Implementing Zoom Schemas (Optional).

Creating an Organization Chart

This section presents the steps to create a full-featured organization chart. Some aspects of an organization chart are optional, and not required. The following sections explain how to:

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- Display breadcrumbs (optional).
- Define descriptors.
- Configure menus and drop-down lists (optional).
- Define drop down lists.
- Configure IM presence (optional).
- Design organization chart nodes.
- Implement zooming (optional).
- Configure connector lines and borders.

Displaying Breadcrumbs (Optional)

You can configure an organization chart to display breadcrumbs. Typically, breadcrumbs display the names of people in an organization hierarchy.

Image: Organization chart with breadcrumbs

The following example shows an organization chart with breadcrumbs:

An organization chart can have only one set of breadcrumbs. The breadcrumbs appear horizontally at the top of an organization chart, above the chart legend if the legend is set. The breadcrumbs string wraps automatically if it is wider than the organization chart. If a breadcrumb contains a space, the breadcrumb string may wrap at the space, causing the breadcrumb to appear on two lines.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Style classes control the formatting of breadcrumbs. The default style classes are PT_ORGCHART_BRDCRM and PT_ORGCHART_UNLINK_BRDCRM. You can specify your own style classes using the CrumbDescrStyle and UnlinkCrumbDescrStyle properties.

You can specify an image to separate breadcrumb entries. If an image is not specified, the breadcrumbs are separated by three spaces. Each breadcrumb entry can be configured to be linkable. This configuration is similar to linkable text on organization chart nodes.

To implement breadcrumbs in an organization chart, you:

- Clone the breadcrumb subrecord PTORGCRMB_SBR.
- Add the clone of PTORGCRMB_SBR to a work record.
- Add the work record to a page such that it is available in the component buffer so that PeopleCode can be invoked from the record fields.

  One way to accomplish this is to include the record in a level 1 grid on the same page as the organization chart, and hide the grid.
- To make a breadcrumb linkable, set the corresponding PTORGCRMBLINKABLE field to “Y”, in much the same way as you make a descriptor linkable in an organization chart node.
- Add PeopleCode to provide application-specific processing when a linkable breadcrumb is selected.

  When a user clicks a linkable breadcrumb, any FieldEdit and FieldChange PeopleCode in the PTORGCRMBID field executes.

At runtime, your PeopleCode will add rows to the work record that holds the information for each breadcrumb (person).

Each breadcrumb in a chart is defined by a row in the record.

See Organization Chart Subrecord Definitions, CrumbDescrStyle.

Breadcrumb Methods and Properties

The following OrgChart class methods and properties control the appearance of breadcrumbs:

- SetCrumbData
- SetCrumbRecord
- UnlinkCrumbDescrStyle
- CrumbDescrStyle
- CrumbMaxDisplayLength
- CrumbSeparatorImage

Defining Descriptors

An organization chart node contains a set of descriptors. Each descriptor represents one element of data related to the node.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The descriptors for a node are defined in the organization chart node data record, which includes a clone of the PTORGNODE_SBR subrecord. The organization chart node record can define up to 99 descriptors. One row in the organization chart node record defines one node in the organization chart.

See “PTORGNODE_SBR” in Organization Chart Subrecord Definitions.

These fields on the PTORGNODE_SBR define the descriptors for a node (where *n* is a number from 1 to 99; for example, PTNODE_DESCR1):

- PTNODE_DESCR*n*
- PTNDDESC*n*LINKABLE
- PTDESCR*n*_ICON_IMG
- PTDESCR*n*_ICON_POS

PTORGNODE_SBR is delivered with fields for seven descriptors. If you are using a node display template and need additional descriptors, you will need to add sets of descriptor fields, to a maximum of 99 descriptors.

Use the PTNODE_DISPLAY_ID field to optionally designate a node display template, which defines other display characteristics for nodes.

See “Using Node Display Templates” in Designing Organization Chart Nodes.

Descriptor Fields

The PTNODE_DESCRn field specifies the text for a descriptor, where *n* is a number from 1 to 99 (for example, PTNODE_DESCR1).

The PTNDDESC*n*LINKABLE field specifies the descriptor type. A descriptor can be one of the following types:

- Y - Linkable text
- N - Static text
- A - Related action menu
- D - Linkable drop-down menu
- R - Read-only (non-linkable) drop-down menu
- L - Linkable drop-down list box
- I - Linkable Icon
- O - Icon only
- M - IM icon

When a user clicks a linkable descriptor, a linkable drop-down menu item, or a drop-down list box item, FieldChange PeopleCode associated with the PTNDDESCnLINKABLE field executes.

See Organization Chart Actions and Events.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

When a user selects a related action menu item, the corresponding action executes. PeopleSoft Related Content Framework must be configured for related action menus.

If the descriptor includes an icon, specify the image name and position using the PTDESCRn_ICON_IMG and PTDESCRn_ICON_POS fields.

Suppose your application includes a node row with this data (some fields in the PTORGNODE_SBR subrecord are omitted for simplicity):

Field	***Value***
PTCHART_NODE	ADIAZ
PTPARENT_CHART_ND	TMONT
PTORGCHRTIMG	(BLOB)
PTNODE_DESCR1	Arron Diaz
PTNDDESC1LINKABLE	Y
PTDESCR1_ICON_IMG	
PTDESCR1_ICON_POS	
PTNODE_DESCR2	Director, Upgrade
PTNDDESC2LINKABLE	
PTDESCR2_ICON_IMG	STATUS_COMP_ICN
PTDESCR2_ICON_POS	L
PTNODE_DESCR3	Experience: Low
PTNDDESC3LINKABLE	Y
PTDESCR3_ICON_IMG	EXP_ICN

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Field	*Value*
PTDESCR3_ICON_POS	R

Image: Example of a node with a node image and descriptors

The following example shows the node that is created using the previous attributes:

Drop-down lists and IM presence icons require additional configuration.

See Configuring IM Presence (Optional).

See Designing Organization Chart Nodes.

See Configuring Drop-Downs.

Using Images with Organization Charts

If your organization chart uses images, such as photographs, then the scroll area or grid with the fields that contain the images must have unlimited occurs count enabled. That is, the Unlimited Occurs Count check box must be selected on any scroll area or grid that includes a record with the fields from PTORGNODE_SBR or PTORGPOPUPNODE_SBR, but only when images are used.

See Implementing Menus and Drop-Down Lists (Optional).

Implementing Menus and Drop-Down Lists (Optional)

You can configure an organization chart to include menus and drop-down lists for any of the node descriptors.

Understanding Menus and Drop-Down Lists

This section discusses the following types of drop-downs:

- Related action menu.
- Drop-down menu.
- Drop-down list box.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Action Menu

A related action menu is dynamically generated based on a related service configuration that has been defined in the PeopleSoft Related Content Framework. Related action links in the menu take the user directly to the target, using related values supplied by the node. Because the menu structure and links are defined by the related service configuration, the developer does not need to populate the drop-down rowset or to write PeopleCode for related action drop-down menus. You do need to verify that the related action services mapping page fields are included in the node record.

Image: Example of a related action drop-down menu

The following example shows a node configured with a related action menu.

Drop-Down Menu

A drop-down menu presents list items in a foldered menu structure.

Drop-down menus can contain folders and menu items. Folders can be nested.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

A drop-down menu can be linkable or read-only. If the drop-down menu is linkable, FieldChange PeopleCode associated with the descriptor field PTNDDESC*n*LINKABLE executes when a user clicks on a menu item. If the drop-down menu is read-only, FieldChange PeopleCode does not execute.

Image: Example of a linkable drop-down menu

The following example shows a node configured with a drop-down menu.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Drop-Down List Box

A drop-down list box presents a list of linkable items.

Image: Example of a linkable drop-down list box

The following example shows a node with a drop-down list box.

The width of a drop-down list box is the width of the widest list item that the box contains.

Configuring Related Action Menus

A related action menu is dynamically rendered based on related content configuration that is mapped to the level 1 chart node record field PTCHART_NODE on the chart page. The services that make up the related content configuration are rendered as links on the related actions menu. The related content layout defines the hierarchical structure of the related actions menu. A related content menu consists of folders and menu items. Folders can be nested.

Important! An Actions folder can also be configured to display in drop-down SmartNavigation menus (that is, the portal breadcrumb menu). The Actions folder displays depending on the configuration of related actions for SmartNavigation. If the related actions are attached at the chart component level, the Actions folder will not appear in the drown down menu. If the related actions are attached to the data source's detail component, the Actions folder will appear in the drop down menu.

Related content services are defined using the Define Related Content Service component. Then, related actions are assigned using the Manage Related Content Service component. Both components are part of the PeopleSoft Related Content Framework.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

See "Defining Related Content Services" (PeopleTools 8.54: Portal Technology) and "Assigning Related Content and Related Actions" (PeopleTools 8.54: Portal Technology).

To configure a descriptor as a related action menu, set the corresponding PTNDDESC*n*LINKABLE value to "A". Using the Manage Related Content Service component, associate the related actions as *page level* related content to the chart node record field PTCHART_NODE on the chart page at level 1.

Configuring the Node Record for Drop-Downs

For each drop-down, add the fields PTDESCR*n*_DD_ID and PTDESCR*n*_SI_ID to your node data record, where *n* represents the number of the descriptor. For example, to configure PTNODE_DESCR7 as a dropdown, add the fields PTDESCR7_DD_ID and PTDESCR7_SI_ID. Add one set of PTDESCR*n*_DD_ID and PTDESCR*n*_SI_ID for each descriptor you configure as a drop-down (PTNDDESC*n*LINKABLE="D", "R", or "L").

You will populate PTDESCR*n*_DD_ID with a unique identifer for the drop-down.

When the user clicks on a list item in the drop-down, the system sets the PTDESCR*n*_SI_ID field to the value of the list item ID, making it available for use by FieldChange PeopleCode.

Configuring the Node Record Without a Display Template

Oracle recommends using a display template to configure your organization chart. Organization charts created with PeopleTools version 8.51 do not use display templates. If your organization chart does not use a display template, you need to configure the node record differently.

Add the fields in the PTORGBOXFLD_SBR subrecord to your node record. The subrecord contains the fields PTDESCR*n*_DROPDOWN_ID and PTDES*n*_SLCT_ITM_ID, where n is an integer from 1 to 7, for example PTDESCR1_DROPDOWN_ID and PTDES1_SLCT_ITM_ID, and so on.

You will populate PTDESCR*n*_DROPDOWN_ID with a unique identifer for the drop-down.

See “PTORGBOXFLD_SBR” in Organization Chart Subrecord Definitions.

Configuring Drop-Downs

To configure a descriptor as a drop-down menu or drop-down list box:

1. Set the PTNDDESC*n*LINKABLE field to “D” for a linkable drop-down menu.

   Set the field to “R” for a read-only (non-linkable) drop-down menu.

   Set the field to “L” for a linkable drop-down list box.

2. Populate the PTDESCRn_DD_ID field (or the PTDESCRn_DROPDOWN_ID if your chart does not use a display template) with the drop-down ID.

3. Create a derived/work record that contains the fields in the subrecord PTORGBOXLST_SBR.

4. Add PeopleCode to set the drop-down data record and the drop-down rowset.

   For example:

```
&ocPBOrg.SetDropDownRecord(Record.DropDown);
&ocPBOrg.SetDropDownData(&rsDropDown);
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

5. Populate the drop-down data rowset with the list information for each of the drop-down list IDs.

   See Populating the Drop-Down Rowset.

6. Place FieldChange PeopleCode on the PTNODE_DESCRn field to perform corresponding logic when a list item is selected in a linkable drop-down.

Related Links

Organization Chart Subrecord Definitions
SetDropdownRecord
SetDropdownData

Populating the Drop-Down Rowset

The drop-down rowset defines the content for drop-down listboxes and defines the menu structure as well as the content for drop-down menus.

Populate the drop-down ID field (PTDESCRn_DD_ID using a display template, or PTDESCR*n*_DROPDOWN_ID if not using a display template) on the node record with a unique identifier, such as EMPL.

Populate the drop-down data rowset according to these rules:

- Each list item in the menu is either a folder or a menu item.

  Assign a unique value in PTORGDRPLSTITM_ID for each item.

- Populate PTNODE LISTDESCR with a label for each item.
- Folders have children.
- Menu items have no children.
- Determine the parent for each item. This is the group ID.

  Set PTORGDRPLS_ GRP_ID to the parent ID, PTORG DRPLSTITM_ID.

- Top-level list items have no parent. Set the group ID to blank.
- Drop-down list box items have no parent. Set the group ID to blank.
- Determine the display order of each list item within its group.

For example, suppose you want to create a drop-down menu with the following structure:

Level 1	***Level 2***	***Level 3***
Talent	Teamwork	
	Planning	
Compensation	Objectives	Objective A
		Objective B

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Level 1	Level 2	Level 3
	Performance	Self Appraisal
		Peer Appraisal
Time		
Absence		

For this example, the drop-down data rowset contains these rows:

PTDESCR_ DRP DWN_ID	PTORG DRPLST ITM_ID	PTORG DRPLS_ GRP_ID	PTND_ DISPLAY_ ORDER	PTNODE LISTDESCR
EMPL	TALENT		1	Talent
EMPL	COMP		2	Competency
EMPL	TIME		3	Time
EMPL	ABS		4	Absence
EMPL	TEAM	TALENT	1	Teamwork
EMPL	PLAN	TALENT	2	Planning
EMPL	OBJ	COMP	1	Objectives
EMPL	PERF	COMP	2	Performance
EMPL	OBJA	OBJ	1	Objective A
EMPL	OBJB	OBJ	2	Objective B
EMPL	SELF	PERF	1	Self Appraisal
EMPL	PEER	PERF	2	Peer Appraisal

Setting Drop-Down Styles

Set the style sheet for the drop down descriptor using the PT_CNT_STYLE field on the node display record.

The default style sheet for the drop down depends on the display type of the descriptor.

The following list shows the default style sheet for each drop down type:

- A – PT_ORGNODE_DESC7
- D - PT_ORGNODE_DESC7
- R - PT_ORGNODE_DESC7

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- L – PT_ORG_DDLIST

The style class for the drop down list item is set using the PTORGLISTDESCSTYLE field in the drop down record. If no style is specified, the default style class is used.

The default style sheet for the drop down list item is:

- A - PT_ACTION_LIST_ITEM
- D - PT_ACTION_LIST_ITEM
- R - PT_READONLY_LIST_ITEM

Configuring IM Presence (Optional)

If an organization chart displays people, you can configure the chart to show a person's IM presence as part of their node. A user could then start a chat session in a chat client with the person from the organization chart.

Image: Example of a node with an IM presence icon

The following example shows a node with an IM presence icon showing that the person is offline:

The following icons indicate a person's IM presence:

Online

Offline

Error

You can specify the position of the IM icon using a node display template. If your chart does not use a node display template then the IM icon appears at top left corner of the node.

If a person's IM indicator shows that the person is available, a user can click on the indicator to start a chat session. The chat session opens in the standard chat client for the domain. For example, if the IM is a Yahoo domain, then Yahoo Messenger launches.

When a user hovers over an IM icon, the data hint text that is specified in the subrecord is displayed along with the IM status. For example, abc@domain.com is available or abc@domain is offline.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

For domains that support offline messages, if a person's IM indicator shows that the person is offline, the user can click on the indicator and leave offline messages.

Retrieving XMPP presence requires MCF IM to be configured. If MCF IM is not correctly configured, an Offline icon is displayed with the data hint: 'MCF IM is not configured'.

If there is an error, an Error icon is displayed and 'Unable get IM status for <user>' is displayed as the data hint.

Note: With the XMPP protocol, a user can get presence information for their buddies only. The status appears as offline for a person who is not the user's buddy.

Organization chart IM supports the following IM protocols:

- XMPP
- MSN
- Yahoo

Implementing IM Presence

The organization chart IM feature uses PeopleTools Multi Channel Framework (MCF) to detect a person's IM presence and start a chat.

Instant messaging must be configured in MCF before you can implement organization chart IM presence.

Note: IM presence behavior may vary depending on which IM domain is used. Refer to the MCF documentation for current details regarding IM presence for each of the domains.

See "Using Node Display Templates" in Designing Organization Chart Nodes, "Configuring Instant Messaging Server Details" (PeopleTools 8.54: MultiChannel Framework).

To implement IM presence:

- Create a derived/work record that includes a clone of the PTORGIM_SBR subrecord definition. The IM information record should not be in the component buffer.
- Populate the work record with the IM data.
- Create a standalone rowset and populate it with the data from the IM record.

  Note: An organization chart displays IM presence for only one IM user ID for each person (node). If more than one IM user ID is defined for a node, only the first one fetched is used.

  Example:

  ```
  &rsIM = CreateRowset(Record.QE_ORG_IM);
  &rsIM.Fill("Where QE_ORG_TC=:1", QE_ORG_TESTCASE.QE_ORG_TC.Value);
  ```

- Set the OrgChart class IM properties.

  Example:

  ```
  &oOrgChart.IMPresence = True;
  &oOrgChart.SetIMRecord(Record.QE_ORG_IM);
  ```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
&oOrgChart.SetIMData(&rsIMData);
&oOrgChart.IMRefreshInterval = 60;
```

- Set the PTNDDESC*n*LINKABLE field to “M” for the corresponding nodes.

See “PTORGIM_SBR” in Organization Chart Subrecord Definitions.

PTORGIM_SBR Data Example

The following table shows sample data for the PTORGIM_SBR fields:

PTCHART_NODE	***MCF_IMUSERID***	***MCF_IM_ PROTOCOL***	***MCFIMDOMAIN***	***MCF_ IMUSERANDNET***
STOMPER	barry.stomper@oracle.com	XMPP	BEEHIVE	barry.stomper@oracle.com
LEBARON	hlebaron216	YAHOO	YAHOO	hlebaron216@yahoo.com
ROBERTS	F2a66c8e51870b5	MSN	MSN	blueskies@hotmail.com

Chatback Badges

MSN requires a chatback badge in order for organization chart IM to initiate a chat. See the *MultiChannel Framework* subject area for details on how to configure instant messaging .

Related Links

Organization Chart Subrecord Definitions
SetIMRecord
SetIMData
IMPresence
IMRefreshInterval
"Configuring Instant Messaging Server Details" (PeopleTools 8.54: MultiChannel Framework)

Designing Organization Chart Nodes

This section describes the basic design of an organization chart node and explains how to use node display templates to configure more complex organization chart nodes.

Using Node Display Templates

You can optionally define node display templates for more precise control over the display characteristics of descriptors on a node.

A node display template is keyed to a single organization chart node row, using the PTNODE_DISPLAY_ID field. A node display template comprises the set of rows that share a value in PTNODE_DISPLAY_ID. Conversely, an organization chart node is associated with a single node display template.

Each row in the node display template defines one descriptor.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Using a node display template, you control:

- Which descriptors appear on the node. Only descriptors included in the node display template and that have PT_DISPLAY_FLAG set to “Y” will appear in the node.
- Display type of descriptors (this overrides display types set in PTNDDESCnLINKABLE).
- Line position and display order of a descriptor.
- Number of display items on a node line.
- Spacing between descriptors.

You can associate a node display template with one or more schemas, or zoom levels. Each schema level assigns different display characteristics to the descriptors.

See Implementing Zoom Schemas (Optional).

You can define your chart to use different node display templates for different nodes by assigning different values to PTNODE_DISPLAY_ID. For example, you might choose to configure the nodes for executive management to display names and photos, but no telephone numbers, locations, emails, or IM presence, while nodes for everyone else display telephone numbers, locations, and emails, but not photos.

Implementing Node Display Templates

To implement node display templates:

1. Create a node display record that includes a clone of the PTNODE_DISP_SBR.
2. Add PeopleCode to set the node display record and the node display rowset.
3. For example:

   ```
   &ocPBOrg.SetNodeDisplayDataRecord(Record.&recDisplay);
   &ocPBOrg.SetNodeDisplayData(&rsDisplay);
   ```

   See “PTNODE_DISP_SBR” in Organization Chart Subrecord Definitions.

   See SetNodeDisplayDataRecord.

   See SetNodeDisplayData.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example: Designing a Node

Image: Example of a node with complex layout

This section demonstrates how to lay out a node that looks like the following example:

Node Descriptors

The organization chart node (PTORGNODE_SBR) sample data in the following table generates the descriptors in the previous node example (for simplicity, not all fields are shown):

Field	*Data*
PTCHART_NODE	CROBE
PTPARENT_CHART_ND	BSTOM
PTND_DISPLAY_ORDER	3
PTNODE_DESCR1	Chase Roberts
PTNDDESC1LINKABLE	Y
PTNODE_DESCR2	Sr. Manager
PTNODE_DESCR3	My Teams
PTNDDESC3LINKABLE	D
PTNODE_DESCR4	KU0035
PTNODE_DESCR5	2/8/1998
PTDESCR5_ICON_POS	L
PTNODE_DESCR6	$125,000
PTNDDESC6LINKABLE	N

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Field	*Data*
PTNODE_DESCR7	Actions
PTNDDESC7LINKABLE	A
PTDESCR7_ICON_POS	L
PTADJUSTFORNULLS	Y
PTNODE_DISPLAY_ID	DEMO17
PTPHOTO_START	2
PTNODE_DESCR8	Org Chart
PTDESCR8_ICON_IMG	QE_ORG_CHART_ICON
PTDESCR8_ICON_POS	L
PTNDDESC8LINKABLE	Y
PTNODE_DESCR9	Person ID:
PTNODE_DESCR10	Hire Date:
PTNODE_DESCR11	Comp Rate:
PTNODE_DESCR12	
PTNDDESC12LINKABLE	
PTNODE_DESCR13	Org chart
PTDESCR13_ICON_IMG	QE_SUCCSORGCHART
PTDESCR3_DD_ID	DEMO17B
PTDESCR7_DD_ID	DEMO17

Node Display Template

The organization chart node display (PTNODE_DISP_SBR) data looks like this:

PTNODE _DISPLAY _ID	*PT_ SCHEMA_ LEVEL_ID*	*PT_CNT_ ID*	*PT_NODE _VIEW*	*PT_LINE_ NUM*	*PTND_ DISPLAY_ ORDER*	*PT_ DISPLAY_ TYPE*	*PT_ PADDING _ LEFT*	*PT_ PADDING _ RIGHT*
DEMO17	3	PTNODE_ DESCR12	VIEW1	1	1	M	Y	0

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

PTNODE _DISPLAY _ID	PT_ SCHEMA_ LEVEL_ID	PT_CNT_ ID	PT_NODE _VIEW	PT_LINE_ NUM	PTND_ DISPLAY_ ORDER	PT_ DISPLAY_ TYPE	PT_ PADDING _ LEFT	PT_ PADDING _ RIGHT
DEMO17	3	PTNODE_ DESCR13	VIEW1	1	2	I	Y	0
DEMO17	3	PTNODE_ DESCR1	VIEW1	2	1	Y	Y	0
DEMO17	3	PTNODE_ DESCR2	VIEW1	3	1	N	Y	0
DEMO17	3	PTNODE_ DESCR8	VIEW1	4	1	Y	Y	0
DEMO17	3	PTNODE_ DESCR9	VIEW1	5	1	N	Y	0
DEMO17	3	PTNODE_ DESCR4	VIEW1	5	2	N	Y	0
DEMO17	3	PTNODE_ DESCR10	VIEW1	6	1	N	Y	0
DEMO17	3	PTNODE_ DESCR5	VIEW1	6	2	N	Y	0
DEMO17	3	PTNODE_ DESCR11	VIEW1	7	1	N	Y	0
DEMO17	3	PTNODE_ DESCR6	VIEW1	7	2	N	Y	0
DEMO17	3	PTNODE_ DESCR3	VIEW1	8	2	D	Y	0
DEMO17	3	PTNODE_ DESCR7	VIEW1	8	1	A	Y	0

Default Node Design

Node display templates are a feature of PeopleTools Release 8.52. Organization charts created prior to PeopleTools Release 8.52 continue to be supported using the default node design.

Oracle recommends using node display templates for PeopleTools Release 8.52 and later organization charts. If you choose not to implement the optional node display templates, your organization chart will follow the default node design. An organization chart that is defined using the default node design has the following characteristics:

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- If an icon image is specified in the PTNDMAINICON_IMAGE field, it appears on the first line, at the right.
- If a node image, such as a photo, is specified (PTORGCHRTIMG), it appears by default on the left, beginning on line two. You can use the ImageLocation property to specify left or right position.
- Each descriptor appears on a separate line. The node displays the first seven descriptors, ordered by the descriptor number.
- PTDESCR_UNDER_IMG specifies the first line that appears under the image. Previous lines appear beside the image.

Adjusting Node Sizing

By default, organization chart nodes are sized dynamically based on the contents of the node and can vary from node to node.

For a vertical organization chart, the width of each node is based on the width of the data in the node. Width can vary from node to node. All the nodes in a given row are the same height, based on height of the tallest node, but node height can vary from row to row.

For a horizontal organization chart, the height of each node is based on the height of the data in the node. Height can vary from node to node. All the nodes in a given column are the same width, based on width of the widest node, but node width can vary from column to column.

You can use the NodeProportion property to control how nodes are sized on a chart. NodeProportion takes the following values:

0 = Variable node sizing. (Default.)

1 = Uniform node height.

2 = Uniform node width.

3 = Uniform node height and width.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

4 = Square nodes.

Image: Vertical organization chart with uniform node sizes

The following example shows a vertical organization chart with uniform node height and width (NodeProportion = 3):

Applying constant node widths can create nodes with extra blank space in the node. You can reduce the node width by reducing value of the NodeMaxDisplayDescLength property.

See NodeProportion.

See NodeMaxDisplayDescLength.

Implementing Node Views (Optional)

Node views allow you to display alternate information on a node. Using node views, you can determine which attributes to show in the node based on the organization chart's node display template. For instance, one node view might show a person's name, photo, and job information, while another view might show that person's name and contact information.

Users are able to select different node views of the organization chart to see less or more data in the nodes. When node views are implemented for an organization chart, the chart displays a view controller that enables a user to select a node view.

You can define multiple node views for an organization chart. A node view definition would include a full definition of the node contents defined by the following attributes:

- Which icons are displayed.
- Which descriptors are displayed.
- The style of the node descriptor.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- The position of the descriptors on the node.

Node View Controller

The node view controller appears in the top part of the chart above the nodes but below any chart breadcrumbs or legend. The node view controller is made up of push buttons without text where each button represents a view. A data hint is used to provide the text description of the view.

Image: Node view controller with a data hint

The node view controller in this example displays the "Personal" node view data hint:

Creating Node Views

To set up the node view controller to enable node views, use the following two organization chart methods:

```
&oOrgChart.SetNodeViewEntries(&NodeViewArray);
&oOrgChart.SetNodeViewText(&NodeViewText);
```

NodeViewArray represents an array of node view IDs. NodeViewText is an array of data hints for each corresponding node view ID.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Additionally, the organization chart property, InitialView, must be set to indicate which view is initially displayed in the chart. For example, the property might be set as follows to show the view that is labeled "Personal."

```
&OrgChart.InitialView="VIEW1";
```

Image: Organization chart with three node views

The following example shows an organization chart with three node views defined:

Transitioning between node views will be done without a server trip. Therefore, it's not possible to have a field change event when changing between views. Also, once the user navigates away from the chart or the chart is refreshed, the current view state is not saved. Therefore, the chart will always show the initial view set in the chart property whenever the chart is viewed again.

Related Links

Designing Organization Chart Nodes
SetNodeViewEntries
SetNodeViewText
InitialView

Implementing Zoom Schemas (Optional)

Zoom schemas enable you to define different visual schemas for organization charts.

Although schemas are designed to give the appearance of zooming in or out on the organization chart, in fact they are predefined views of the organization chart at different levels. Using schemas, you define what attributes to show on the node, and which nodes are displayed in each schema level. Users are able to select different views of the organization chart to see more or fewer nodes, and to see less or more data in the nodes.

You can define up to ten schema levels for an organization chart.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

When zoom schemas are implemented for an organization chart, the chart displays a zoom control that enables a user to select a schema level.

Image: Example of an organization chart displaying schema level 3

The following example shows an organization chart with a zoom control and four schemas defined. The chart in this example displays schema level 3.

Image: Example of an organization chart displaying schema level 1

The chart in the following example displays schema level 1, which displays less data on each node, allowing the chart to display more nodes in the same area.

Each schema level defines the following attributes, based on the organization chart's node display template:

- Which icons are displayed.
- Which descriptors are displayed.
- The style of the node descriptor.
- The position of the descriptors on the node.

See "Using Node Display Templates" in Designing Organization Chart Nodes.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

In addition, you can place FieldChange PeopleCode on the PTCHART_SCHEMA_ID field of the node record to control which nodes are displayed.

When the user changes schema levels, FieldChange PeopleCode on the PTCHART_SCHEMA_ID field of the node record executes. You can set the DISPLAYED_FLAG field on the node data rowset to control whether a node is displayed at the new schema level, or you can use PeopleCode to populate the organization chart node data rowset with only the nodes you want available at the new schema level.

Use the SchemaLevel object ImageHeight property to define whether the image (photo) is displayed in the node and the height of the image.

The size of the chart nodes is determined dynamically based on the subset of data within the node and the corresponding style properties for the schema level.

SchemaLevel Class

The SchemaLevel PeopleCode class provides methods and properties to set organization chart display information for each schema level.

SchemaLevel objects are declared using the SchemaLevel data type.

For example:

```
Local SchemaLevel &SchemaLevel1;
Component Chart &Abs_Hist_Chart;
```

Instantiate SchemaLevel objects using the CreateObject(“SchemaLevel”) PeopleCode function.

Implementing Schema Zooming

To implement schema zooming:

1. Add PeopleCode to specify the intial schema level.

   Example:

   ```
   &oOrgChart.ChartCurrentSchemaLevel=4;
   ```

2. Instantiate a SchemaLevel object for each schema level your chart will use.

   Example:

   ```
   SchemaLevel &oSchemaLevel1 = Createobject("SchemaLevel");
   ```

3. Add PeopleCode to define each schema level.

   Example:

   ```
   /*** Create an instance of of schema zoom level 1 class and instantiate it ***⇒
   /
   SchemaLevel &oSchemaLevel1 =Createobject("SchemaLevel");
   &oSchemaLevel1.ID=1;
   & oSchemaLevel1.ImageHeight=0;
   /*** Create an instance of of schema zoom level 2 class and instantiate it  **⇒
   */
   SchemaLevel &oSchemaLevel2 =Createobject("SchemaLevel");
   &oSchemaLevel2.ID=2;
   & oSchemaLevel2.ImageHeight=40;
   /*** Create an instance of of schema zoom level 3 class and instantiate it ***
   SchemaLevel &oSchemaLevel3 =Createobject("SchemaLevel");
   ```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
& oSchemaLevel3.ID=3;
& oSchemaLevel3.ImageHeight=45;

/*** Create an instance of of schema zoom level 4 class and instantiate it  **⇒
*/
SchemaLevel &oSchemaLevel4 =Createobject("SchemaLevel");
&oSchemaLevel4.ID=4;
& oSchemaLevel4.ImageHeight=50;
```

4. Assign the SchemaLevel instances to the OrgChart object.

   Example:

```
/***   Assign the 4 schema level instance to the org chart object ***/
&SchemaLevls=CreateArray(&oSchemaLevel1, &oSchemaLevel2, &oSchemaLevel3,
&oSchemaLevel4)
&oOrgChart.SetZoomSchemaLevels(&SchemaLevls)
```

5. Write FieldChange PeopleCode on the PTCHART_SCHEMA_ID field to execute when the user clicks on the schema zoom control to change the schema level.

   Example:

```
Component Rowset &rs, &rsGrid;
Component object &oOrgChart;
rem WinMessage("value =" | &oOrgChart.ChartCurrentSchemaLevel);
&currentZoom = &oOrgChart.ChartCurrentSchemaLevel;
   If &currentZoom = 1 Then
      /* display all records and no image */
      For &i = 1 To &rsGrid.ActiveRowCount
         &RecGrid = &rsGrid.GetRow(&i).GetRecord(Record.QE_ORG_Z2_DRV);
         &RecGrid.GetField(Field.PTDESCR_UNDER_IMG).value = 0;
         /* show all records */
         &RecGrid.GetField(Field.DISPLAYED_FLAG).value = "Y"
      End-For;
   Else
      If &currentZoom = 2 Then
         &limit = 6;
      Else
         If &currentZoom = 3 Then
            &limit = 4;
         Else
            &limit = 3;
         End-If;
      End-If;
      For &i = 1 To &rsGrid.ActiveRowCount
         &RecGrid = &rsGrid.GetRow(&i).GetRecord(Record.QE_ORG_Z2_DRV);
         &RecGrid.GetField(Field.PTDESCR_UNDER_IMG).value = 3;
         If &RecGrid.GetField(Field.QE_ORG_SCHEMA_ROW).value < &limit Then
            &RecGrid.GetField(Field.DISPLAYED_FLAG).value = "Y";
         Else
            &RecGrid.GetField(Field.DISPLAYED_FLAG).value = "N";
         End-If;
      End-For;
   End-If;
```

Schema Events

When a user selects a different schema level using the zoom control, the following events take place:

- The system sets the value in the CurrentSchemaLevel property to the new schema value.
- The systems sets the value in the PTCHART_SCHEMA_ID to the new schema value.
- FieldChange PeopleCode on the PTCHART_SCHEMA_ID field executes.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- The system displays the organization chart at the new schema level.

You can also set the CurrentSchemaLevel property using PeopleCode.

Related Links

SetSchemaLevels
ChartCurrentSchemaLevel
ID
ImageHeight

Specifying Scroll Types

If an organization chart is larger than the viewable area, the user needs to scroll to view other areas of the chart. You can specify whether the organization chart will use scroll bars or alternative scrolling.

Image: Example of an organization chart using alternative scrolling

If you specify alternative scrolling, a scroll navigator and a hand cursor appear instead of vertical and horizontal scroll bars.

Note: On an Apple iPad a user navigates using two fingers on a touch screen, so scroll bars, the scroll navigator, and mouse hand features are not displayed on an Apple iPad.

The arrows on the scroll navigator enable the user to quickly position the right, left, top, or bottom of the chart in the viewable area.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

If the user scrolls the chart, the center button of the scroll navigator returns the chart to its initial display position. If the user changes focus by selecting a different node, the chart centers on that node. The center button then returns the chart to display centered on the focus node.

If alternative scrolling is implemented, the user can dismiss a dropdown menu only by clicking within the node areas in the chart unless no scrolling is needed, in which case the user can click on the background or on a node to dismiss the menu.

Note: If the breadcrumbs and chart legend are so large that there is not sufficient room to display the scroll navigator in the upper left portion of the chart, it will appear in the lower left corner.

The hand cursor enables the user to grab the background of the chart and move it within the viewable area.

Note: When using the hand cursor to scroll, you must position the hand cursor in the chart area outside the chart nodes and popup nodes. Scrolling does not work if the hand cursor is positioned within a chart node or pop-up node.

Use the ChartScrollType property to specify which type of scrolling to use. The default is scroll bars.

Configuring Connector Lines and Node Borders

Use the PTCONNECTLINESTYLE field on the organization chart node record to specify the style sheet that defines the following characteristics of the connector lines:

- Line style (unbroken, broken, pattern)
- Line weight
- Line color

The PSORGCHART style sheet includes these style classes for connector lines:

Style Class	*Connector Style*
PT_ORGCHART_CONNECT1	Solid gray
PT_ORGCHART_CONNECT2	Solid black
PT_ORGCHART_CONNECT3	Dotted red
PT_ORGCHART_CONNECT4	Dashed gray

The default connector line style class is PT_ORGCHART_CONNECT1 (solid gray).

Use the PTNODESTYLENAME field on the organization chart node record to specify the style sheet that defines the following characteristics of the node border:

- Line style (unbroken, broken, pattern)
- Line weight
- Line color

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- Shading
- Shading color

The PSORGCHART style sheet includes these style classes for connector lines:

Style Class	*Connector Style*
PT_ORGNODE	Solid gray
PT_PT_ORGNODE_DASH	Dashed gray

The default node border style class is PT_ORGNODE.

Note: We recommend using the default line weight, 1 pixel, for connector lines and node borders. Thicker line weights may cause inconsistencies between connector lines and node borders.

Organization Chart Actions and Events

An organization chart can execute FieldEdit or FieldChange PeopleCode in response to these user actions:

- Select an expand/collapse icon.
- Click a descriptor link.
- Select a linkable drop-down menu item or drop-down list box item.
- Close a pop-up node.
- Select a breadcrumb.
- Click on a node image.
- Click on a node.

Selecting Expand/Collapse Icons

When the user clicks an expand/collapse icon, the system toggles the EXPANDED_FLAG field value from “Y” to “N” or from “N” to “Y” and changes the icon on the node to collapsed or expanded, correspondingly. This action triggers field change processing (FieldEdit and FieldChange events) on EXPANDED_FLAG. Typically, FieldChange PeopleCode checks the EXPANDED_FLAG and PARENT_FLAG of the node and performs these actions:

- If `EXPANDED_FLAG="Y"` and `PARENT_FLAG="X"`, loads the child rows into the rowset and sets `PARENT_FLAG="Y"`. The updates appear when the chart is refreshed.
- If `EXPAND_FLAG="N"` (collapse action), it does nothing.
- If `EXPAND_FLAG="Y"` (expand action) and `PARENT_FLAG="Y"` (child data is already in rowset), it does nothing.

Note: If your PeopleCode doesn’t populate the CollapsedImage and ExpandedImage properties of the organization chart, then no expand/collapse icon appears on any nodes in the chart, and the expand/collapse action is disabled for the chart.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Clicking a Descriptor Link

When the user clicks a descriptor link or linkable drop-down list item, field change processing is triggered on the PTNODE_DESCR*n* field in the node record.

For instance, suppose descriptor 2 is linked to a pop-up chart. When the user clicks the descriptor 2 link, FieldChange PeopleCode on the PTNODE_DESCR2 field in the node record performs the following actions:

- Sets the node's`PTPOPUPEXPAND_FLAG ="Y"`.
- Sets the node's `PTPOPUPHDRMAINDESC`.
- Sets the node's `PTPOPUPHDRMAINICON`.
- If the node's `PTHASPOPUP_FLAG ="X"`, then populates the pop-up node rowset and sets `PTHASPOPUP_FLAG ="Y"` to indicate that the node's descriptor was clicked for the first time.
- Refresh the chart with the pop-up displayed.

Closing a Pop-up Node

When the user closes a pop-up node it triggers field change processing on the PTPOPUPEXPAND_FLAG field.

FieldChange PeopleCode on the PTPOPUPEXPAND_FLAG field would need to restore any changes that were made to the originating node's display characteristics and reset the node's `PTPOPUPEXPAND_FLAG ="N"` .

Selecting a Linkable Menu Item or Drop-Down List Box Item

When a user selects a linkable menu item or drop-down list box item, the system sets the PTDESCR*n*_SI_ID (PTDES*n*_SLCT_ITM_ID if not using a node display record) field value to the value of the list item ID and FieldChange PeopleCode associated with the PTNDDESC*n*LINKABLE field executes.

Selecting a Breadcrumb

When a user clicks on a linkable breadcrumb, any FieldEdit and FieldChange PeopleCode in the PTORGCRMBID field executes. Typically PeopleCode is used to redraw the organization giving focus to the node that was clicked.

Clicking on a Photograph

When a user clicks on a node image, field change PeopleCode on the PTNDMAINICON_IMAGE field executes.

Clicking on a Node

When a user clicks on the body of a node – not on a link, linkable drop-down list, or image – field change PeopleCode on the PTCHART_NODE field executes.

Organization Chart Subrecord Definitions

This section describes the following organization chart subrecord definitions:

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- PTORGNODE_SBR
- PTORGGPOPUP_SBR
- PTORGCRMB_SBR
- PTORGBOXLST_SBR
- PTORGBOXFLD_SBR
- PTORGIM_SBR
- PTNODE_DISP_SBR

PTORGNODE_SBR

This table describes the fields in PTORGNODE_SBR:

Field	*Description*
PTCHART_NODE	Specifies the node name. This is a key field.
PTPARENT_CHART_ND	Specifies the parent of the current chart node. This is a key field. If a node does not have a parent node defined, then the node is placed on the first level.
PTND_DISPLAY_ORDER	Specifies the display order of the sibling nodes for the same parent node. Nodes display left to right according to display order. By default, the nodes are ordered as they appear in the rowset.
PTCONNECTLINESTYLE	Specifies the style class name for connection line style. The default style class is PT_ORGCHART_CONNECT1.
PTNDMAINICON_IMAGE	Specifies the main icon image name for the node.
PTNODESTYLENAME	Specifies the style class name for the node to control node background color, border, style, and so on. The default style class is PT_ORGNODE.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Field	*Description*
PTFOCUS_FLAG	Specifies a focused node (that is, the node that has focus). Y – Focused node. N – Not a focused node. If more than one node is set to focused, only the first focused node in the rowset will be recognized as the focused node. The default is *"N"*.
PARENT_FLAG	Indicates whether a node is a parent. Y – The node is a parent and its direct children are already loaded into the rowset. X – The node is a parent and its direct children are not loaded in the rowset (that is, they will be loaded on demand). N – The node is not a parent. The default value is *"N"*. An expanded/collapsed icon is only displayed on the parent node. If your PeopleCode does not set the CollapsedImage and ExpandedImage properties of the organization chart, no expanded/collapsed icon is displayed on any of the nodes and all expand/collapse actions are disabled.
EXPANDED_FLAG	Indicates whether the node is expanded or collapsed. Y – The chart shows the node expanded with the expanded image icon and its immediate children displayed. N – The chart shows the node collapsed with the collapsed image icon.
DISPLAYED_FLAG	Specifies whether the node displays in the chart. Y – The node displays if the parent node's `EXPANDED_FLAG ="Y"` (the parent node is not collapsed). N – This node and its child nodes do not display in the chart's display area. The default is *"Y"*.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Field	***Description***
PTHASPOPUP_FLAG	Indicates whether the node has a pop-up. Y – This node has a link that invokes a pop-up and the data for the pop-up is already loaded into the pop-up node rowset. X – This node has a link that invokes a pop-up and the data for the pop-up is not loaded in the rowset. The data will be loaded on demand. N – This node does not have a link to invoke a pop-up chart. The default value is *"N"*.
PTPOPUPEXPAND_FLAG	Indicates whether a node's pop-up nodes display. Y – Pop-up nodes display. N – No pop-up nodes display. If the user clicks the close icon in the pop-up node, the FieldChange event for PTPOPUPEXPAND_FLAG executes. The application sets the value of PTPOPUPEXPAND_FLAG to "N" when the pop-up node is closed.
PTNODE_DESCR*n*	Specifies the text for descriptor*n* of the node, where*n* is an integer that starts at 1 and increments by one for each descriptor used by the chart; for example, PTNODE_DESCR2. The PTORGNODE_SBR subrecord is delivered with fields for descriptors 1 – 7. If you need more than seven descriptors, add a set of descriptor fields (PTNODE_DESCRn, PTNDDESCnLINKABLE, PTDESCRn_ICON_IMG, and PTDESCRn_ICON_POS) for each additional descriptor, to a maximum of 99 descriptors. If this is an icon-only descriptor (PTNDDESCnLINKABLE = "I" or "O"), the text in this field is used as the data hint for the icon. The maximum length is 50 characters.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Field	*Description*
PTNDDESC*n*LINKABLE	Specifies the descriptor type for descriptor *n*, where n is an integer from 1 to 99; for example, PTNDDESC2LINKABLE. Y - Linkable text N - Static text I - Linkable Icon O - Icon only A -Related action menu D - Linkable drop-down menu R - Read-only (non-linkable) drop-down menu L - Linkable drop-down list box M - IM icon The default value is *"N"*. The value in this field is overridden by the node display template, if one is implemented.
PTDESCR*n*_ICON_IMG	Specifies the name of the image associated with descriptor *n*, where *n* is an integer from 1 to 99; for example, PTDESCR2_ICON_IMG. For icon-only descriptors ("I" or "O"), the text in PTNODE_DESCR*n* is the data hint text. **Note:** If PTDESCR*n*_ICON_IMG is set to a valid image, the image is only displayed if PTNDDESC*n*LINKABLE is set to "Y", "N", "I", or "O"..
PTDESCR*n*_ICON_POS	Indicates the position of the icon relative to descriptor *n*, where *n* is an integer from 1 to 7; for example, PTDESCR2_ICON_POS. L – To the left of the description. R – To the right of the description. The default value is based on user language. For instance, *"L"* for English and *"R"* for Hebrew.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Field	*Description*
PTADJUSTFORNULLS	Indicate whether to collapse empty attributes to conserve vertical space within the nodes. Y – Collapse. N – Do not collapse. The default value is *"N"*.
PTPOPUPHDRMAINDESC	Specifies the main descriptor of the pop-up chart header for this node
PTPOPUPHDRMAINICON	Specifies the name of the image to place on the top left of the pop-up chart header.
PTORGCHRTIMG	Specifies the node image. The maximum image size depends on your database platform. **Note:** If this field is placed on a grid on the page and the column is hidden (Visible = False), the node images do not appear on the chart.
PSIMAGEVER	A unique number that is assigned to each image. This is a system-maintained value.
PTDESCR_UNDER_IMG	If you are using a node display template, this specifies the first node line number that appears under the node image. The specified line number and all following lines appear below the image. All lines prior to the specified line appear to the side of the image. If you are not using a node display template, specify an integer from 1 to 7. The corresponding descriptor and all following descriptors appear below the image. All descriptors prior to the one specified appear to the side of the image. If no value is specified, the node lines all appear to the side. If no image is displayed, this field is ignored. This field takes an integer value.
PTPHOTO_START	Specifies the node line number on which the photo starts. This field only applies if you are using a node display template.
PTNODE_DISPLAY_ID	Specifies which display template ID to use with this node.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Field	Description
PTCHART_SCHEMA_ID	Specifies the current schema value. The system sets this value using the ChartCurrentSchemaLevel OrgChart property value. When the user selects a different schema value, the system sets field to the new value, sets the ChartCurrentSchemaLevel OrgChart property value to the new value, and redraws the chart using the new schema level. If the application changes the ChartCurrentSchemaLevel OrgChart property value, the system sets this field to the new value and redraws the chart using the new schema level.

PTORGPOPUP_SBR

This table describes the fields in PTORGPOPUP_SBR.

Field	Description
PTCHART_NODE	Specifies the name of the node that invoked this pop-up chart. This is a key field.
PT_POP_UP_ID	The unique ID for the pop-up. This is a key field.
PTPREDECESSOR_NODE	Specifies the name of the predecessor node to the current chart node. The predecessor node is the node that invoked this node. Your application PeopleCode must set this value when the link is clicked on the predecessor node.
PTND_DISPLAY_ORDER	Sets the display order of the nodes within the same pop-up. By default the nodes are ordered as they appear in the rowset.
PTNDMAINICON_IMAGE	Specifies the main icon image name for the node.
PTNODESTYLENAME	Specifies the style class name for the node to control node background color, border, style, and so on. If no style class name is specified the PeopleTools default style class is used.
PT_POPUP_PARENT_ID	Set to the ID of the parent pop-up chart to which the PT_POP_UP_ID is attached. If the chart ID PT_POP_UP_ID is connected from the organization node, then its corresponding PT_POPUP_PARENT_ID value is NULL.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Field	***Description***
PTHASPOPUP_FLAG	Indicates whether the node has a pop-up. Y – This node has a link that invokes a pop-up and the data for the pop-up is already loaded into the pop-up node rowset. X – This node has a link that invokes a pop-up and the data for the pop-up is not loaded in the rowset. The data will be loaded on demand. N – This node does not have a link to invoke a pop-up chart. The default value is *"N"*.
PTPOPUPEXPAND_FLAG	Indicates whether a node's pop-up nodes display. Y – Pop-up nodes display. N – No pop-up nodes display. If the user clicks the close icon in the pop-up node, the FieldChange event for PTPOPUPEXPAND_FLAG executes. The application sets the value of PTPOPUPEXPAND_FLAG to *"N"* when the pop-up node is closed.
DISPLAYED_FLAG	Indicates whether the node will appear in the pop-up chart. Y = The node appears in the pop-up chart. N = The node never appears in the pop-up chart, including its pop-up nodes. Default is *"Y"*.
PTNODE_DESCR*n*	Specifies the descriptor *n* of the node, where *n* is an integer from 1 to 8; for example, PTNODE_DESCR2. Maximum length is 50 characters.
PTNDDESC*n*LINKABLE	Specifies whether the descriptor *n* is linkable, where *n* is an integer from 1 to 8; for example, PTNDDESC2LINKABLE. Y – Linkable N – Not linkable
PTDESCR*n*_ICON_IMG	Specifies the name of the image associated with descriptor *n*, where *n* is an integer from 1 to 8; for example, PTDESCR2_ICON_IMG.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Field	*Description*
PTDESCR*n*_ICON_POS	Indicates the position of the icon relative to descriptor *n*, where *n* is an integer from 1 to 8; for example, PTDESCR2_ICON_POS. L – To the left of the description. R – To the right of the description. The default value is based on user language. For instance, *"L"* for English and *"R"* for Hebrew.
PTADJUSTFORNULLS	Indicates whether to collapse empty attributes to conserve vertical space within the nodes. Y – Collapse N – Do not collapse
PTPOPUPHDRMAINDESC	Specifies the main descriptor of the pop-up chart header for this node.
PTPOPUPHDRMAINICON	Specifies the name of the image to place on the top left of the pop-up chart header.

PTORGCRMB_SBR

This table describes the fields in PTORGCRMB_SBR:

Field	*Description*
PTORGCRMBID	Assigns the breadcrumb ID. PTORGCRMBID is a key field.
PTPARENT_ORGCRMBID	Specifies the breadcrumb ID of Parent node. Only one row, which will be the first breadcrumb, can have this field blank or there will be a runtime error.
PTORGCRMBDESCR	Sets the breadcrumb description. In an organization chart this is generally a name.
DISPLAYED_FLAG	The displayed flag, Y = Displayed. N = Not displayed. The default is *"N"*.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Field	Description
PTORGCRMBLINKABLE	The linkable flag. Y = Linkable N = Not linkable The default is *"Y"*.

PTORGBOXLST_SBR

This table describes the fields in PTORGBOXLST_SBR:

Field	Description
PTDESCR_DRPDWN_ID	Specifies the node description drop-down list box ID. PTDESCR_DRPDWN_ID is a key field.
PTORGDRPLSTITM_ID	The drop down list item ID for the specified drop down list. PTORGDRPLSTITM_ID is a key field.
PTORGDRPLS_GRP_ID	Specify the group ID for the drop down list item in the drop-down box. For a folder menu, set this value to the list item ID (PTORGDRPLSTITM_ID) of the parent folder. For a top-level folder, set this value to blank. For a flat (single-level) drop-down list box, set this value to blank.
PTND_DISPLAY_ORDER	Set the display order of the list item within the same dropdown box. By default, the list will display in the order the list items appear in the rowset.
PTNODELISTDESCR	The text that will appear for the drop down list item. The maximum length is 60 characters.
PTORGLISTDESCSTYLE	Specify the style class for the list item. The default style class for drop down list items depends on the type of drop down. See Setting Drop-Down Styles.

PTORGBOXFLD_SBR

This table describes the fields in PTORGBOXFLD_SBR:

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Note: This subrecord is retained for backward compatibility. With PeopleTools version 8.52 and later, Oracle recommends using node display templates. The PTORGBOXFLD_SBR is not used with a chart that implements node display templates.

See Configuring the Node Record for Drop-Downs.

Field	*Description*
PTDESCR*n*_DROPDOWN	The drop down list ID for descriptor *n*, where *n* is an integer from 1 to 7; for example, PTDESCR2_DROPDOWN.
PTDES*n*_SLCT_ITM_ID	The selected list Item ID in the drop-down box for descriptor *n*, where *n* is an integer from 1 to 7; for example, PTDES2_SLCT_ITM_ID. The system sets this field to the value of the list item ID when the user clicks on a list item in the drop-down list box for descriptor *n*. You can add PeopleCode to the PTNODE_DESCR*n* field that performs business logic using the value in this field.

PTORGIM_SBR

This table describes the fields in PTORGIM_SBR:

Field	*Description*
PTCHART_NODE	Specifies the node name. This is a key field.
MCF_IMUSERID	Specifies the user ID used to get presence information for the user. This is a key field. **Note:** Using the PTORGIM_SBR record structure, you can configure multiple IM user IDs for a node. PeopleTools 8.52 organization chart IM feature does not support multiple presences. If more than one IM user ID is defined for a node, only the first one fetched is used.
MCF_IM_PROTOCOL	Specifies the instant messaging protocol. This is a key field.
MCFIMDOMAIN	Specifies the instant messaging domain. This is a key field.
MCF_IMUSERANDNET	Specifies the data hint text on mouse over the IM status icon.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

PTNODE_DISP_SBR

This table describes the fields in PTNODE_DISP_SBR:

Field	*Description*
PTNODE_DISPLAY_ID	Specifies the ID of a display template. The PTNODE_DISPLAY_ID field on the organization chart node record specifies the node display template to be used for the node.
PT_SCHEMA_LEVEL_ID	Specifies the schema level. Specify a numeric value 1-10.
PT_CNT_ID	Specifies the descriptor. For example, PTNODE_DESCR1.
PT_NODE_VIEW	Specifies the name of the node view.
PT_LINE_NUM	Specifies the node line number on which the descriptor will appear.
PT_DISPLAY_TYPE	Specifies the display item type. Y - Linkable text N - Static text I - Linkable Icon O - Icon only A -Related action menu D - Linkable drop-down menu R - Read-only (non-linkable) drop-down menu L - Linkable drop-down list box M - IM icon If this field is set to *"M"* but no rows are defined in the PT_ORGIM_SBR for the node, no IM icon will be shown. The value in this field overrides the value in PTNDDESCnLINKABLE in the organization chart node record.
PT_DISPLAY_FLAG	Specifies whether the descriptor will be displayed in the node. The default value is *"Y"*.
PTND_DISPLAY_ORDER	Sets the display order of the descriptor/icon within the line number.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Field	*Description*
PT_PADDING_RIGHT	Specifies the padding, in pixels, to the right of the descriptor. If PT_COL_ALIGN is set to centered or left aligned, this field is ignored.
PT_PADDING_LEFT	Specifies the padding, in pixels, to maintain to the left of the descriptor. If PT_COL_ALIGN is set to centered or right aligned, this field is ignored.
PT_CNT_STYLE	Specifies the style class name that will be used to control the style of the descriptor. The default style class for drop downs depends on the type of drop down. See Setting Drop-Down Styles.
PT_DESCR_MAX	Specifies the maximum length for the descriptor. If the full descriptor text is longer than PT_DESCR_MAX, then an ellipsis ("…") is appended to the displayed text. The entire text appears in a data hint. The default value is 50 characters. This value overrides any value set in the NodeMaxDisplayDescLength OrgChart property.

Minimum Methods and Properties

At a minimum, these methods are needed to create an organization chart:

- SetNodeData
- SetNodeRecord

These methods are required if your organization chart uses pop-ups:

- SetPopUpNodeData
- SetPopUpNodeRecord

These methods and properties are required if your organization chart uses IM presence:

- SetIMRecord
- SetIMData
- IMPresence

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

These methods are required if your organization chart uses node display templates:

- SetNodeDisplayDataRecord
- SetNodeDisplayData

These methods and properties are required if your organization chart uses zooming schemas:

- SetSchemaLevels
- ChartCurrentSchemaLevel
- ID SchemaLevel class property
- ImageHeight SchemaLevel class property

These methods are required if your organization chart uses breadcrumbs:

- SetCrumbData
- SetCrumbRecord

These methods are required if your organization chart uses drop-down list boxes:

- SetDropdownData
- SetDropdownRecord

Scope and Data Type of an OrgChart Object

Chart objects are declared using the Chart data type. For example,

```
Local OrgChart &MyOrgChart;
```

A chart object can be instantiated only from PeopleCode.

You can use this object only in PeopleCode programs that are associated with an online process, not in an Application Engine program, a message notification, a Component Interface, and so on.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Using the RatingBoxChart Class

A rating box chart is an interactive chart that displays nodes on a two-dimensional grid. If drag-and-drop is enabled for the chart, a user can move the nodes from one quadrant to another on the grid. When the user moves a node, the underlying data is updated automatically.

Image: Rating box chart used to graph performance and potential

The rating box chart in this example displays ratings on the dimensions of potential and performance. The nine combinations of ratings produces a grid with nine quadrants:

This section provides an overview of rating box chart terminology and discusses:

- Using rating box charts in PeopleSoft applications.
- Creating rating box charts using the RatingBoxChart class.
- Rating box chart subrecord definition.
- Minimum methods.
- Minimum properties.
- Using the QuadrantSchema class.
- Data type of a RatingBoxChart object

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- Scope of a RatingBoxChart object.

Understanding Rating Box Chart Terms

The following is a list of terms that apply specifically to rating box charts.

Box	A rating box chart is an array of boxes (referred to as quadrants) arranged in a grid along the x and y axes. See *Quadrant* for more information.
Description	A text string that is associated with a node. The node description optionally displays with the node icon.
Icon	An image associated with a node that displays in a quadrant on the rating box chart.
Node	A single data point on a rating box chart. A node represents an individual entity, such as an employee, customer, or product. You can drag-and-drop a node to other quadrants in the rating box chart grid.
Node record	A record that contains the properties and data values for each node on the rating box chart. The node record must include a copy of the subrecord PTRATINGBIX_SBR.
Quadrant	A rating box chart is an array of quadrants arranged in a grid along the x and y axes. Each quadrant represents a pair of ratings, one for the x value and one for the y value. Each quadrant can display a custom label as defined by an instance of the QuadrantSchema class. See Using the QuadrantSchema Class.
Rating	A text string that is assigned to each quadrant in the rating chart. Each quadrant has an x rating, based on its position on the horizontal axis, and a y rating, based on its position on the vertical axis.
Title	There are three titles: Main title, x-axis title, and y-axis title. A title is text that identifies that portion of the chart.

Using Rating Box Charts in PeopleSoft Applications

A rating box chart displays nodes on a chart that is divided into two or more quadrants arrayed in a grid.

An application can correlate nodes, represented by icons, with various entities, such as employees, customers, or products, and various attribute pairs, such as potential/performance, cost/benefit, or opportunity/risk.

A user interacts with the rating box by dragging nodes to different quadrants. When a node is moved, its underlying x (horizontal) and y (vertical) values are updated. A user can also interact with the rating box by changing a node's x or y values in the grid that contains the rating box values if the application makes the grid visible and editable.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

To drag and drop a node using an Apple iPad, tap the node's description. A copy of the node with a red dashed border appears. Then tap the quadrant to which you want to move the node. The node appears in the new location.

The View all pop-up automatically closes if the user moves a node to another quadrant.

Using PeopleCode, you can associate each node with an image, or icon, and a description. You can configure a rating box to display nodes with icons and descriptions or with only icons.

Image: Rating box chart with a pop-up displaying all nodes for a quadrant

If a quadrant contains more nodes than the number set in the RatingBoxChart property BoxMaxDisplayItems, the user can click a link at the bottom of the quadrant to launch a pop-up that contains all the nodes. The quadrant border changes color to indicate that the quadrant has a pop-up open. A vertical scrollbar enables the user to scroll through all the nodes in the list as shown in this example:

Related Links

BoxMaxDisplayItems

Creating Rating Box Charts Using the RatingBoxChart Class

When you add a rating box chart to a page in Application Designer, you use the chart properties to associate the chart control with a record field. You will use this field name to identify the chart in PeopleCode.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

You will need to create a record that will be the rating box chart node record. The record can be a standard database record or a derived/work record. The node record holds the values for the properties and data for each of the rating box chart nodes.

The record can have any name, but it must include a clone of the PeopleTools-delivered subrecord PTRATINGBOX_SBR. Since the subrecord will carry the FieldChange PeopleCode for the chart, in most cases you should create a unique subrecord for each chart. The node record must be placed on a page at level one on the component so that its PeopleCode will be loaded into the component buffer. It can be hidden.

In your chart PeopleCode, typically in the Activate event, you will create and populate a rowset linked to the chart's node record. This must be a component rowset, linked to the chart's node record, not a standalone rowset. The rowset has one row for each node in the chart.

Actions and Events

When the IsDragable property is set to True, drag-and-drop is allowed for the rating box chart. Otherwise, drag-and-drop is not allowed.

When a user drags the node from one quadrant to another, PeopleTools updates the values for the node's PTXAXISRATINGS and PTYAXISRATINGS values, changing the node's x and y values to the new values. This change invokes field change processing on the PTXAXISRATINGS and PTYAXISRATINGS fields on the rating box node record. Typically, FieldChange PeopleCode performs business logic and refreshes the chart display.

Text Orientation

The orientation of the main title in a rating box chart is always horizontal.

The orientation of the x-axis title and x-axis labels is always horizontal.

The orientation of the y-axis title and y-axis labels is always vertical.

Rating Box Chart Subrecord Definition

These are the fields in PTRATINGBOX_SBR:

Field	*Description*
PTCHART_NODE	Specifies the node name. This is the key to the record.
PTND_DISPLAY_ORDER	Specifies the display order of the nodes within the chart. By default nodes will display in the same order as in the rowset. You must provide a unique value for display order for each node in the rating box rowset so that the nodes will display in the correct order in the chart. A runtime error message is thrown when the display order is not unique for each node in the rating box rowset.
PTNODE_DESCR1	Specifies the main description for the node.
PTNODEDESCRSTYLE	Specifies the style class that defines the description's text font, type, color, size, and so on.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Field	*Description*
PTNDDESC1LINKABLE	Reserved for future use.
PTDESCR1_ICON_IMG	Specifies the image name for the main description.
PTDESCR1_ICON_POS	Indicates where to place the icon relative to the description. L – Left of the description R – Right of the description
PTXAXISRATINGS	Specifies the x-axis rating for the current node.
PTYAXISRATINGS	Specifies the y-axis rating for the current node.
DISPLAYED_FLAG	Indicates whether the node will display in the chart area. Y – The node will display in the chart area. N – The node will not display in the chart area. The default value is *"Y"*.

Minimum Methods

At a minimum these methods are needed to create a rating box chart.

- SetRBNodeData
- SetRBNodeRecord
- SetXAxisLabels
- SetYAxisLabels

Minimum Properties

At a minimum, these properties are needed to create a rating box chart.

- XAxisBoxNum
- YAxisBoxNum

These properties are required if the chart includes a view all pop-up:

- PopUpWidth
- PopUpHeight

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Using the QuadrantSchema Class

You can attach instances of the QuadrantSchema class to your rating box chart to provide additional information to users. Specifically, you can label quadrants in the rating box chart.

Image: Rating box chart with quadrant labels

In the following example, six of the nine available quadrants in the rating box chart are associated with a QuadrantSchema object and have custom labels; the other three quadrants are unlabeled.

Each label is defined by an instance of QuadrantSchema. These instances are created independently in PeopleCode and then attached as an array to your instance of RatingBoxChart.

For each instance of QuadrantSchema you must specify the x-value/y-value pair that defines the quadrant for the text. You can also specify the location of the text within the quadrant.

The following PeopleCode example demonstrates how to create unique instances of QuadrantSchema, set their properties, and assign them to a rating box chart in order to display a custom label in six rating box quadrants.

```
/***************** Create Quadrant Schema  1****************/
&oQuadrantSchema1 = CreateObject("QuadrantSchema");
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
&oQuadrantSchema1.XRating = "Low";
&oQuadrantSchema1.YRating = "Low";
&oQuadrantSchema1.LabelText = "Lowest";
&oQuadrantSchema1.LabelPosition = %Bottom_Left;

/****************** Create Quadrant Schema  2*****************/
&oQuadrantSchema2 = CreateObject("QuadrantSchema");
&oQuadrantSchema2.XRating = "High";
&oQuadrantSchema2.YRating = "High";
&oQuadrantSchema2.LabelText = "Highest";
&oQuadrantSchema2.LabelPosition = %Top_Right;

/****************** Create Quadrant Schema  3*****************/
&oQuadrantSchema3 = CreateObject("QuadrantSchema");
&oQuadrantSchema3.XRating = "Medium";
&oQuadrantSchema3.YRating = "Medium";
&oQuadrantSchema3.LabelText = "This label should not overflow the quadrant!";
&oQuadrantSchema3.LabelPosition = %Bottom_Right;

/****************** Create Quadrant Schema  4*****************/
&oQuadrantSchema4 = CreateObject("QuadrantSchema");
&oQuadrantSchema4.XRating = "High";
&oQuadrantSchema4.YRating = "Low";
&oQuadrantSchema4.LabelText = "High-Low";
&oQuadrantSchema4.LabelPosition = %Bottom_Right;

/****************** Create Quadrant Schema  5*****************/
&oQuadrantSchema5 = CreateObject("QuadrantSchema");
&oQuadrantSchema5.XRating = "Low";
&oQuadrantSchema5.YRating = "High";
&oQuadrantSchema5.LabelText = "Low-High";
&oQuadrantSchema5.LabelPosition = %Top_Left;
rem &oQuadrantSchema5.LabelPosition = 4;

/****************** Create Quadrant Schema  6*****************/
&oQuadrantSchema6 = CreateObject("QuadrantSchema");
&oQuadrantSchema6.XRating = "Medium";
&oQuadrantSchema6.YRating = "Low";
&oQuadrantSchema6.LabelText = "Overlapped?";
&oQuadrantSchema6.LabelPosition = %Bottom_Right;
```

Then, the following portion of the program builds an array of these instances and that then associates that array to the instance of RatingBoxChart:

```
&QuadrantSchemas = CreateArray(&oQuadrantSchema1, &oQuadrantSchema2, &oQuadrantSche⇒
ma3, &oQuadrantSchema4, &oQuadrantSchema5, &oQuadrantSchema6);

&oRatingBoxChart.SetQuadrantSchemas(&QuadrantSchemas);

/* Reduce clutter in the chart by hiding the axis labels */
&oRatingBoxChart.ShowAxisLabels = False;
```

Related Links

SetQuadrantSchemas

QuadrantSchema Class Properties

Data Type of a RatingBoxChart Object

Chart objects are declared using the Chart data type. For example,

```
Local RatingBoxChart &RatingBoxChart;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Scope of a RatingBoxChart Object

A chart object can be instantiated only from PeopleCode.

You can use this object only in PeopleCode programs that are associated with an online process, not in an Application Engine program, a message notification, a Component Interface, and so on.

Charting Classes Reference

The charting classes reference contains these sections:

- Charting classes built-in functions.
- Chart class methods.
- Chart class properties.
- ReferenceArea class properties.
- ReferenceLine class properties.
- DialGauge class methods.
- DialGauge class properties.
- LEDGauge class methods.
- LEDGauge class properties.
- StatusMeterGauge class methods.
- StatusMeterGauge class properties.
- Threshold class properties.
- Gantt class methods.
- Gantt class properties.
- OrgChart class methods.
- OrgChart class properties.
- SchemaLevel class properties.
- RatingBoxChart class methods.
- RatingBoxChart class properties.
- QuadrantSchema class properties

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Charting Classes Built-in Functions

Chart Classes

"GetChart" (PeopleTools 8.54: PeopleCode Language Reference)

"GetChartURL" (PeopleTools 8.54: PeopleCode Language Reference)

"GetReferenceArea" (PeopleTools 8.54: PeopleCode Language Reference)

"GetReferenceLine" (PeopleTools 8.54: PeopleCode Language Reference)

Gauge Classes

"GetDialGauge" (PeopleTools 8.54: PeopleCode Language Reference)

"GetLEDGauge" (PeopleTools 8.54: PeopleCode Language Reference)

"GetStatusMeterGauge" (PeopleTools 8.54: PeopleCode Language Reference)

"GetThreshold" (PeopleTools 8.54: PeopleCode Language Reference)

Gantt Class

"GetGanttChart" (PeopleTools 8.54: PeopleCode Language Reference)

OrgChart Class

"GetOrgChart" (PeopleTools 8.54: PeopleCode Language Reference)

RatingBoxChart Class

"GetRatingBoxChart" (PeopleTools 8.54: PeopleCode Language Reference)

Chart Class Methods

These methods are used by the Chart class. The methods are listed in alphabetical order.

Refresh

Syntax

```
Refresh()
```

Description

Note: This method has been deprecated and remains for backward compatibility only. Use the SetData method or SetOLData method instead.
If you make a change to the underlying data of a chart, call the SetData method again to update the chart.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

You don't need to refresh after setting a property or method of the chart itself, such as setting the starting point or changing colors. When a method or property is used, the chart is automatically refreshed.

Parameters

None.

Returns

None.

Example

```
&MyChart.Refresh();
```

Related Links

SetData
SetOLData

Reset

Syntax

Reset()

Description

Use the Reset method to clear all existing chart settings and data.

Parameters

None.

Returns

None.

Related Links

Refresh

SetColorArray

Syntax

SetColorArray(*&Array_of_Color*)

Description

PeopleSoft charts are delivered with a default color sequence. If you want to specify a different sequence, use the SetColorArray method to set the colors for a series. You can specify only a one-dimensional array for the parameter.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This method applies to the base chart and to the overlay chart. Color values are applied first to the base chart, then to the overlay chart. For example, if the base chart contains four series, then the fifth color value is applied to the first series in the overlay chart, and so on.

The type of array can be any of the following:

- String
- Number
- Integer
- Decimal

Use the SetColorArray method for line charts instead of SetDataColor because SetDataColor does not work with line charts. Individual line segments cannot be colored because there are fewer line segments than points. Use SetColorArray instead to color each complete line (series).

Parameters

&Array_of_Color Specify an already instantiated array that contains the color values that you want for the series. You can specify either a constant or a number.

The following lists all the values you can specify. You can use either the numeric or constant value.

Numeric Value	*Constant Value*	*Description*
-1	%ChartColor_Series_Default	Default series color. When a data point is set to this, the default series color or the color that has been set by the programmer for that series is used instead. This value works only with the SetColorArray method of the Chart class.
0	%ChartColor_Black	Black
1	%ChartColor_Blue	Blue
2	%ChartColor_Cyan	Cyan
3	%ChartColor_DarkGray	Dark gray
4	%ChartColor_Gray	Gray
5	%ChartColor_Green	Green
6	%ChartColor_LightGray	Light gray
7	%ChartColor_Magenta	Magenta
8	%ChartColor_Orange	Orange

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Numeric Value	*Constant Value*	*Description*
9	%ChartColor_Pink	Pink
10	%ChartColor_Red	Red
11	%ChartColor_White	White
12	%ChartColor_Yellow	Yellow
13	%ChartColor_Red_Orange	Red-orange
14	%ChartColor_Yellow_Green	Yellow-green
15	%ChartColor_Blue_Violet	Blue-violet
16	%ChartColor_Purple	Purple
17	%ChartColor_Yellow_Orange	Yellow-orange

Returns

None.

Example

The following example sets the four series in the chart:

```
&NumArray = CreateArray(1, 3, 6, 9);

&oChart.SetColorArray(&NumArray);
```

SetData

Syntax

SetData({*Record_Name* | *&Rowset*})

Description

Use the SetData method to specify where the data from the chart is coming from.

You can use either a record name or an already instantiated, populated rowset. In general, specify a record when building a chart from page data and a rowset when building a chart from a standalone rowset.

If you make a change to the underlying data of a chart, call the SetData method again to update the chart.

Parameters

Record_Name Specify the name of a record to be used to populate the chart with data.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

&Rowset Specify the name of an already instantiated rowset to populate the chart with data. This is generally a standalone rowset.

Returns

None.

Example

The following is the minimum code you need to create a PeopleSoft chart.

```
Local Chart &MyChart;

&MyChart = GetChart(ABS_HIST.CHART);
&MyChart.SetData(ABS_HIST);
&MyChart.SetDataYAxis(ABS_HIST.Reason);
&MyChart.SetDataXAxis(ABS_HIST.Duration);
```

The following example creates a chart using a standalone rowset.

```
Function IScript_GetChartURL()
local object &MYCHART;
local string &MYURL;
local rowset &MYROWSET;

&MYCHART = CreateObject("Chart");

&MYROWSET = CreateRowset(Record.ABS_HIST);

&EmplID = %Emplid;

&MYROWSET.Fill("Where EMPLID :=1", &EmplID);

&MYCHART.SetData(&MYROWSET);
&MYCHART.SetDataXAxis(ABS_HIST.ABSENCE_TYPE);
&MYCHART.SetDataYAxis(ABS_HIST.DURATION_DAYS);

&MYURL = %Response.GetChartURL(&MYCHART);

/* use &MYURL in your application */
...
End-Function;
```

Related Links

SetDataXAxis

SetDataYAxis

SetDataAnnotations

Syntax

SetDataAnnotations(*Record_Name.Field_Name*)

Description

Use the SetDataAnnotations method to specify an optional text label that can be associated with each point in the chart.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Note: This method is applicable for scatter and bubble charts only; it is ignored for all other chart types.

Parameters

Record_Name.Field_Name	Specify the field name (and the record it's associated with) that contains the text for the optional label.

Returns

None.

SetDataColor

Syntax

SetDataColor(*Record_Name.Field_Name*)

Description

Use the SetDataColor method to specify a field that contains the color for each data point. Each field for each data point must contain either a number or a constant that specifies the color you want to use.

Use the SetColorArray method for line charts instead of SetDataColor because SetDataColor does not work with line charts. Individual line segments cannot be colored because fewer line segments exist than points. Use SetColorArray instead to color each complete line (series).

Note: This method has no effect when used with an overlay.

Parameters

Record_Name.Field_Name	Specify the name of the record, and the field on that record, that contains the colors for each data point. You can specify either a constant or a number.

See SetColorArray.

Returns

None.

SetDataGlyphScale

Syntax

SetDataGlyphScale(*Record_Name.Field_Name*)

Description

Use the SetDataGlyphScale method to specify a field that contains numerical data defining the size of each glyph for bubble charts (scatter charts). These values are mapped to a range of size values between a predefined minimum and maximum.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This method affects bubble charts only (%ChartType_2DBubble).

Parameters

Record_Name.Field_Name Specify the field (and the record associated with it) that contains numerical data used to define the size of each glyph.

Returns

None.

SetDataHints

Syntax

SetDataHints(*Record_Name.Field_Name*)

Description

Use the SetDataHints method to override the default text that appears as a caption when you mouse over data in a chart (that is, a bar, a pie slice, or a data point).

The default data hint text that appears is constructed from information about the composition of the chart that you have defined and the row of data being charted. Specifically, its structure depends on whether the chart has a data series or not:

Chart Composition	***Default Hint***	***Example***
SetDataSeries not set	Value [*y*] for point [*x*]	Value 50 for point California

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Chart Composition	*Default Hint*	*Example*
SetDataSeries set	Value [*y*] for point [*x*] of series [*series*]	Value 40 for point Rackets of series Oregon

Image: Default hint when SetDataSeries is not set

If you do not specify SetDataHints and do not specify SetDataSeries, then the value of the y-axis and the value of the x-axis appear in the data hint:

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Image: Default hint when SetDataSeries is set

If you do not specify SetDataHints but do specify SetDataSeries, then the value of the y-axis, the x-axis, and the series appear in the data hint::

If you use SetDataHints, the text that appears as a caption when you mouse over data will be precisely that which is in the RECORD.FIELD for that row of data. This is true whether a data series is present or not.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

For example, SetDataHints is set as follows:

```
&cChart12.SetDataHints(DOC_CHRT_SLS_2.DOC_CHRT_MASCOT);
```

Image: Hint set by SetDataHints without a data series

Mousing over the bar representing California reveals *Golden Bears* as the value of the DOC_CHRT_MASCOT field for that row in the DOC_CHRT_SLS_2 rowset:

Hint set by SetDataHints without a data series

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

In the following example, SetDataSeries is already set, and SetDataHints is set as follows:

```
&cChart13.SetDataHints(DOC_CHRT_SLSREC.DOC_CHRT_RGN);
```

Image: Hint set by SetDataHints with a data series

Mousing over any bar in the bar chart will display the region represented by the bar.

Parameters

Record_Name.Field_Name	Specify the name of the record and field that contains the data hints for the chart.

Returns

None.

Example

```
&cChart13.SetDataHints(DOC_CHRT_SLSREC.DOC_CHRT_RGN);
```

Related Links

SetDataXAxis
SetDataSeries

SetDataSeries

Syntax

SetDataSeries(*Record_Name.Field_Name*)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the SetDataSeries method to specify the name of the field containing the series values. Every distinct value in this field is considered a unique series.

The series is plotted in the order given by the record.

By default, the legend is populated by the value of this field.

If this value is Null, the system assumes there is only one series to plot.

Parameters

Record_Name.Field_Name	Specify the name of the record, and the field on that record, that contains the series values for the chart.

Returns

None.

Example

```
&MYCHART.SetDataSeries(MYRECORD.MYSERIES);
```

Related Links

SetDataXAxis
SetDataYAxis

SetDataURLs

Syntax

SetDataURLs(*Record_Name.Field_Name*)

Description

Use the SetDataURLs method to specify a URL to be launched when a data point is clicked in the chart. The URL for each point must be a fully formed URL specified as a string. For example:

```
http://example.org/index.htm
```

The IsDrillable property must be set to True to enable clicking on data points within the chart.

Parameters

Record_Name.Field_Name	Specify a record field name to be used to populate the URL for each data point.

Returns

None.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

```
&oChart.IsDrillable = True;
&oChart.SetDataURLs(PB_CHART_RECORD.PB_CHART_DESC);
```

Related Links

IsDrillable

SetDataXAxis

Syntax

SetDataXAxis(*Record_Name.Field_Name*)

Description

Use the SetDataXAxis method to specify the groups along the x-axis.

If this value is not set or Null, the y values are plotted along the x-axis in groups labeled by their order number.

The order of the data is plotted in the order of the data in the record.

By default, the labels along the x-axis are populated by the value of this field.

Parameters

Record_Name.Field_Name	Specify the name of the record, and the field on that record, that contains the data for the x-axis for the chart.

Returns

None.

Example

```
&cChart = GetChart(PB_CHART_DUMREC.PB_CHART_FIELD);

&cChart.SetData(Record.PB_CHART_RECORD);
&cChart.SetDataSeries(PB_CHART_RECORD.PB_CHART_PRODUCT);
&cChart.SetDataXAxis(PB_CHART_RECORD.PB_CHART_REGION);
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
&cChart.SetDataYAxis(PB_CHART_RECORD.PB_CHART_SALES);
```

Image: X-axis set with region data

In the following example, the y-axis is set to a numeric amount, while the x-axis is set to the region:

Related Links

SetDataYAxis

SetData

SetDataYAxis

Syntax

SetDataYAxis(*Record_Name.Field_Name*)

Description

Use the SetDataYAxis to specify the data to plot in the chart. The y-axis is always considered the data axis.

Note: For a funnel chart, you can alternatively use the SetFunnelDataActual method to specify this data.

Parameters

Record_Name.Field_Name	Specify the name of the record, and the field on that record, that contains the data for the y-axis for the chart.

Returns

None.

Example

```
&oChart.SetDataYAxis(QE_CHART_RECORD.QE_CHART_SALES);
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

SetDataXAxis
SetData
SetFunnelDataActual

SetExplodedSectorsArray

Syntax

SetExplodedSectorsArray*(&Array)*

Description

Use the SetExplodedSectorsArray method to specify the sectors in a pie chart that you want exploded. Specify a one-dimensional array of type integer to specify which sectors to explode. This is an optional method. The default is no sectors are exploded.

Sector numbers correspond to the rows of data used to generate the chart.

The PIECHARTSEGMENTEXPLOSIONDISTANCE style class in the PSCHARTSTYLE_FREEFORM and in the PSCHARTSTYLE_TANGERINE_FREEFM style sheets controls the explode offset for all pie chart sectors. The explode offset is expressed as a proportion of the pie radius. This style class is delivered with a default value. If you want exploded segments displayed farther from the pie chart center, adjust the value up; if you want segments displayed closer to the center of the pie chart, adjust the value down. We recommend using a value for PIECHARTSEGMENTEXPLOSIONDISTANCE between 0 and 100. The default in PSCHARTSTYLE_FREEFORM is 40 and in PSCHARTSTYLE_TANGERINE_FREEFM it is 100.

This method applies only to 2D and 3D pie charts.

Parameter	***Description***
&Array	Specify an already instantiated one-dimensional array of number. This array lists the sector numbers that will be exploded. Sector numbers must be integer values. The default is no sectors are exploded.

Returns

None.

Example

```
Local array of number &ExplodedArray;
&ExplodedArray = CreateArray(1,2,3,4,5)
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
&cChart.SetExplodedSectorsArray(&ExplodedArray);
```

Image: Exploded pie chart

The following example shows an exploded 3D pie chart:

SetFunnelDataActual

Syntax

SetFunnelDataActual(*Record_Name.Field_Name*)

Description

Use the SetFunnelDataActual method to specify a field that contains the actual numeric data for the funnel chart. Alternatively, this data can be specified using the SetDataYAxis method. This data is required for a funnel chart, and must be specified by one of these two methods.

The target data for a funnel chart can be specified in either of these ways:

- Using the SetFunnelDataTarget method to specify a field. In this way, the target data can vary for each data point.
- Using the FunnelPercentMeasure property. When this property is True, a default target value of 100.00 is used (which overrides any target data is specified by the SetFunnelDataTarget method).

Parameters

Record_Name.Field_Name	Specify the name of the record, and the field on that record, that contains the data for the y-axis for the funnel chart.

Returns

None.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

SetDataYAxis
SetFunnelDataTarget
FunnelPercentMeasure

SetFunnelDataTarget

Syntax

SetFunnelDataTarget(*Record_Name.Field_Name*)

Description

Use the SetFunnelDataTarget method to specify a field that contains the target numeric data for the funnel chart. Target data is optional. However, when it is specified, the field must reside on the same record definition as specified with the SetFunnelDataActual method.

Note: If the FunnelPercentMeasure property is True, then any specified target data is ignored.

Parameters

Record_Name.Field_Name	Specify the name of the record, and the field on that record, that contains the optional target data for the funnel chart.

Returns

None.

Example

In the following example, the actual and target data for the funnel chart come from the same record definition, which is a required condition for using the SetFunnelDataTarget method:

```
&oChart.SetFunnelDataActual(CHART_RECORD.CHART_SALES);
&oChart.SetFunnelDataTarget(CHART_RECORD.CHART_X_NUMERIC);
rem &oChart.FunnelPercentMeasure = True;
```

Related Links

FunnelPercentMeasure

SetGlyphArray

Syntax

SetGlyphArray(*&Array_of_String*)

Description

Use the SetGlyphArray method to set the glyph for all data points. You can specify a one-dimensional array only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Note: This method only affects line charts and scatter charts.

Parameters

&Array_of_String

Specify an already instantiated, one-dimensional array that contains the glyph type that you want for all data points.

The default value is an array with a single element: %ChartGlyph_Diamond.

The possible values are: %ChartGlyph_Diamond, %ChartGlyph_Circle, %ChartGlyph_Square, and %ChartGlyph_Triangle.

Returns

None

Example

```
&oChart.SetGlyphArray(CreateArray(%ChartGlyph_Triangle, %ChartGlyph_Circle, %ChartG⇒
lyph_Square, %ChartGlyph_Diamond));
```

SetLegend

Syntax

SetLegend(*&Array_of_String*)

Description

Use the SetLegend method to specify alternative legends. By default, the legends are populated from the record field specified with SetDataSeries.

This method is used to write both the overlay legend and the series legend. The labels are overwritten in the order of elements in the array, that is, the first element overwrites the first series, the second overwrites the second, and so on, with the last element in the array overwriting the overlay legend. There can be more than one series in an overlay.

If you do not specify an element for an array (that is, a blank or a null) then no legend is listed for that series.

Note: Default label text is not automatically translated. If you set your own labels, be sure to use translated text, such as message catalog entries.

Note: Legends are not available for funnel charts. Therefore, this method is not applicable for a funnel chart.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

&Array_of_String	Specify an already instantiated array of string, containing the text that you want to use for the legend.

Returns

None.

Example

The following example displays a legend containing only the overlay.

```
&LegendArray = CreateArray("", "", "Revenue");

&MyChart.SetLegend(&LegendArray);
```

Related Links

SetDataSeries

SetOLData

Syntax

SetOLData({*Record_Name* | *&Rowset*})

Description

Use the SetOLData method to specify where the data for the overlay is coming from.

If you make a change to the underlying data of a chart, call the SetOLData method again to update the chart.

There are no default values for the overlay data. You must specify the data.

You can specify two different y-axis fields, but you must make certain that different data plotted against the same axis makes sense. For example, while plotting two currency amounts would work technically —plotting currency amounts against number of units sold and sharing the same axis— would not look correct.

Parameters

Record_Name	Specify the name of a record to be used to populate the overlay of the chart with data.
&Rowset	Specify the name of an already instantiated rowset to populate the overlay of the chart with data.

Returns

None.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

SetDataXAxis
SetDataYAxis
SetData

SetOLDataAnnotations

Syntax

SetOLDataAnnotation(*Record_Name.Field_Name*)

Description

This method has been deprecated and is ignored.

SetOLDataGlyphScale

Syntax

SetOLDataGlyphScale(*Record_Name.Field_Name*)

Description

This method has been deprecated and is ignored.

SetOLDataSeries

Syntax

SetOLDataSeries(*Record_Name.Field_Name*)

Description

Use the SetOLDataSeries method to specify the name of the field containing the overlay series values. Every distinct value in this field is considered a unique series.

The series is plotted in the order given by the rows in the record.

If this value is Null, the system assumes there is only one series to plot.

Parameters

Record_Name.Field_Name	Specify the name of the record, and the field on that record, that contains the series values of the overlay for the chart.

Returns

None.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

SetDataSeries

SetOLDataXAxis

Syntax

SetOLDataXAxis(*Record_Name.Field_Name*)

Description

Use the SetOLDataXAxis method to specify the groups along the x-axis if the axis is non-numeric for the overlay.

If the x-axis is numeric, this method is used to give the position of the points along the axis. Only discrete values are supported for the x-axis.

If this value is Null, the y values are plotted along the x-axis in groups labeled by their order number.

The order of the data is plotted in the order of rows in the record.

Parameters

Record_Name.Field_Name	Specify the name of the record, and the field on that record, that contains the data for the x-axis for the overlay of the chart.

Returns

None.

SetOLDataYAxis

Syntax

SetOLDataYAxis(*Record_Name.Field_Name*)

Description

Use the SetOLDataYAxis to specify the data to plot for the overlay of the chart.

This value must always be numeric.

This method has no default value.

Parameters

Record_Name.Field_Name	Specify the name of the record, and the field on that record, that contains the data for the overlay of the chart.

Returns

None.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

SetDataXAxis
SetDataYAxis

SetReferenceArea

Syntax

SetReferenceArea(*&Array_of_RefAreas*)

Description

Use the SetReferenceArea method to specify one or more reference areas for the chart.

Parameters

&Array_of_RefAreas	Specify an already instantiated array of ReferenceArea objects as the reference areas for this chart.

Returns

None.

Related Links

Using the ReferenceArea Class
ReferenceArea Class Properties

SetReferenceLine

Syntax

SetReferenceLine(*&Array_of_RefLines*)

Description

Use the SetReferenceLine method to specify one or more reference lines for the chart.

Parameters

&Array_of_RefLines	Specify an already instantiated array of ReferenceLine objects as the reference lines for this chart.

Returns

None.

Related Links

Using the ReferenceLine Class
ReferenceLine Class Properties

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SetXAxisLabels

Syntax

SetXAxisLabels(*&Array_of_String*)

Description

Use the SetXAxisLabels method to specify an array of labels for the x-axis. By default, the labels are populated from the record field specified by SetDataXAxis. Labels specified with SetXAxisLabels overwrite the default labels.

Note: Default label text is not automatically translated. If you set your own labels, be sure to use translated text, such as message catalog entries.

Parameters

&Array_of_String	Specify an already instantiated array of string that contain the labels that you want to use for the x-axis.

Returns

None.

Related Links

SetDataXAxis
Creating a Chart Using the Chart Class
Understanding Arrays

SetYAxisLabels

Syntax

SetYAxisLabels(*&Array_of_String*)

Description

Use the SetYAxisLabels method to specify an array of labels for the y-axis. Labels specified with SetYAxisLabels overwrite the default labels.

If the greatest y-axis value is less than ten, the default y-axis labels are given a decimal place. If the greatest y-axis value is greater than or equal to ten, the default y-axis labels are displayed as integers.

Note: Default label text is not automatically translated. If you set your own labels, be sure to use translated text, such as message catalog entries.

If you set the labels yourself, you may need to set the YAxisTicks and YAxisMax because you no longer have numbers that correlate to the data points.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

&Array_of_String	Specify an already instantiated array of string that contain the labels that you want to use for the y-axis.

Returns

None.

Related Links

SetDataXAxis
YAxisTicks
YAxisMax
Creating a Chart Using the Chart Class
Understanding Arrays

Chart Class Properties

These properties are used by the Chart class. The properties are described in alphabetic order.

AdditionalStyleSuffix

Description

Use this property to specify a style class name suffix as a String value.

Then, in Application Designer, create custom style class definitions by append this style class name suffix to style class names. These custom style class definitions will override delivered style class definitions found in any of the PSCHARTSTYLE* sub style sheets.

For example, if the value of this property is set to MY_OVRD, then create the PSCHARTTITLE_MY_OVRD custom style class to override the PSCHARTTITLE style class.

This property is read-write.

Related Links

Styling PeopleSoft Charts

AnimationDuration

Description

Use this property to specify an Integer value (0 or greater) indicating how long (in milliseconds) the gauge animation should last.

If this property is not specified, it defaults to the value of the GAnimationDuration property of the PT_CHART_GAUGE style class, which is 500 milliseconds.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-write.

AnimationType

Description

Use this property to specify the animation type for the gauge. You can specify either an Integer or constant value for this property.

If this property is not specified, it defaults to the value of the GAnimationDefType property of the PT_CHART_GAUGE style class, which is TransitionToLeft.

The values are:

Numeric Value	*Constant Value*
0	%Animation_None
1	%Animation_Auto **Note:** The automatic animation is determined by the charting engine and varies by chart type.
2	%Animation_AlphaFade
3	%Animation_ConveyorFromRight
4	%Animation_ConveyorFromLeft
5	%Animation_CubeToLeft
6	%Animation_CubeToRight
7	%Animation_FlipRight
8	%Animation_FlipLeft
9	%Animation_SlideToLeft
10	%Animation_SlideToRight
11	%Animation_TransitionToLeft
12	%Animation_TransitionToRight
13	%Animation_Zoom

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

DataStartRow

Description

This property sets or returns the row number (after any preprocessing) at which to start plotting. This is useful when you have many rows of data in a rowset, and you want to start at a particular row. This can also be useful for creating your own 'scrolling' effect, by specifying both the start row and how many rows to be displayed (by using the DataWidth property).

If this property is not set, then the value is 1.

This property is read-write.

Related Links

DataWidth

DataWidth

Description

This property returns or sets the number of rows to plot for a series. The starting point for the number of rows is set with the DataStartRow property. If the DataWidth property value is not set, then the width is from the DataStartRow to the last element in the rowset. If the property value is less than zero, then it will automatically be set to one.

This property is read-write.

Example

Suppose your rowset returned 400 rows. You wouldn't want all 400 to display in your chart. Instead, you'd pick a subset of those rows. The row to start with is set with DataStartRow, while how many rows to display is set with DataWidth.

The following code could be used with a push button connected with a chart. The push button enables the next set of data to appear with the chart.

You do not need to refresh after setting this property. When a method or property is used, the chart is automatically refreshed.

```
Local Chart &MyChart;

&MyChart = GetChart(ChartRec.DisplayField);
&Start = &MyChart.DataStartRow;
/* display the next 20 rows of data */
&MyChart.DataStartRow = &Start + 20;
&MyChart.DataWidth = 20;
```

Related Links

DataStartRow

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

FootNote

Description

Use this property to specify the text for the footnote for the chart. The footnote appears at the bottom left of the chart.

This property takes a string value.

This property is read-write.

FunnelPercentMeasure

Description

Use this property to set a Boolean value indicating whether to display the funnel chart data as a percentage of the default target value: 100.00.

Note: If this property is True, then any target data specified by the SetFunnelDataTarget method is ignored.

This property is read-write.

Example

```
&oChart.SetFunnelDataActual(CHART_RECORD.CHART_SALES);
&oChart.FunnelPercentMeasure = True;
```

Related Links

SetFunnelDataActual

SetFunnelDataTarget

GridLines

Description

This property has been deprecated and is ignored. Use the PSVERTICALGRIDLINES and PSHORIZONTALGRIDLINES style classes instead to control grid line visibility and style.

GridLineType

Description

This property has been deprecated and is ignored. Use the PSVERTICALGRIDLINES and PSHORIZONTALGRIDLINES style classes instead to control grid line visibility and style.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

HasLegend

Description

Use this property to specify if a legend is displayed with the chart. This property takes a Boolean value: True, if the legend is displayed with the chart, False otherwise.

The default value is False.

This property is read-write.

Note: Legends are not available for funnel charts. Therefore, this property is not applicable for a funnel chart.

Height

Description

Use this property to specify a Number value indicating the height of the chart in pixels.

Generally this property is used with charts created for iScripts, to specify the height of the image, before generating the image map. You can also use it to overwrite the height set in Application Designer.

If you try to read this property before setting it, the value returned is zero.

Note: The Height and Width properties must be set to the same value to change the size of a 2D Scatter chart, that is, a chart with the Type property set to %ChartType_2DScatter.

This property is read-write.

Related Links

Width

HighlightSelectedDataPoint

Description

Use this property to specify a Boolean value indicating whether a data point selected by a user is highlighted on a chart or not. The default value is False.

This property is read-write.

Example

```
&oChart.HighlightSelectedDataPoint = True;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ImageMap

Description

This property returns the HTML client-side image map. The image map is what makes the chart interactive.

This property is read-only.

Related Links

Creating a Chart Using an iScript

IsChartDrillable

Description

Use this property to specify a Boolean value indicating whether the chart background (that is, the entire chart control) is interactive.

If both IsChartDrillable and IsDrillable are set to True, the interactivity depends on where the user clicks on the chart. If the user clicks on a data point within the chart (for example, a bar, a pie segment, a dot, and so on), the interactivity specified by IsDrillable is triggered. If the user clicks anywhere else on the chart, the interactivity is specified by either of these two conditions:

- Any FieldChange PeopleCode that is defined on the record field of the chart control.
- The URL specified by the SetChartURL property.

This property is read-write.

Related Links

SetChartURL
IsDrillable

IsDrillable

Description

Use this property to specify a Boolean value indicating whether the chart is interactive—that is, whether the user can click on (or touch) the chart to trigger an action. The default value is False.

If both IsChartDrillable and IsDrillable are set to True, the interactivity depends on where the user clicks on the chart. If the user clicks on a data point within the chart (for example, a bar, a pie segment, a dot, and so on), the interactivity specified by IsDrillable is triggered. If the user clicks anywhere else on the chart, the interactivity specified by IsChartDrillable is triggered. When IsDrillable is triggered, the source of interactivity on a chart can come from one of two places:

- A URL passed through the chart's SetDataURLs method
- FieldChange PeopleCode on the y-axis data field.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

If both a URL is passed through SetDataURLs and FieldChange PeopleCode exists on the y-axis data field, the URL will take precedence over the PeopleCode.

Note: The record that contains the PeopleCode must be in the component buffer at runtime.

See Creating a Chart Using the Chart Class.

Note: Setting this property has no effect if the IsPlainImage property is set as True.

This property is read-write.

Related Links

SetDataURLsIsPlainImage IsChartDrillable

IsLineChartLineSmoothing

Description

Use this property to specify a Boolean value indicating whether to display the line chart with smoothed lines. If this property is set to True, the lines that connect the data points on the line chart are smoothed, resulting in curved lines. If this property is set to False, the lines between the data points are drawn straight.

This property is read-write.

IsPlainImage

Description

Use this property to specify whether the chart is built without interactivity features, such as data hints or drill capability.

If this property is specified as True, you will not be able to click on the chart to trigger an event. In addition, the pop-up data hints will not appear when you pass a mouse over the chart. However, you may see a performance improvement if your chart has an extremely complicated image map and you specify this property as True.

This property takes a Boolean value: True if the chart is built without interactivity, False otherwise.

The default value of this property is False.

This property is read-write.

IsTrueXY

Description

Use this property to enable a true XY chart. This causes the x-axis data to be loaded as ordered numeric data, rather than discrete data as is used in bar charts for example. This property is only applicable to scatter, bubble, line, and histogram charts.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Note: You must programmatically sort the chart data rowset on the x-axis value in ascending order to produce a numerically ordered true XY chart.

This property is read-write.

Related Links

Creating a Chart Using the Chart Class

IsXAxisInteger

Description

Specify whether the x-axis will display integers. Set IsXAxisInteger to True if the x-axis represents integer data, such as the number of people or the number of tasks.

Setting IsXAxisInteger to True is only applicable to line charts, scatter charts, and bubble charts.

This property takes a Boolean value.

The default value of this property is False.

This property is read-write.

IsYAxisInteger

Description

Specify whether the y-axis will display integers. Set IsYAxisInteger to True if the y-axis represents integer data, such as the number of people or the number of tasks.

IsYAxisInteger is not used with pie charts and percentage bar charts.

This property takes a Boolean value.

The default value of this property is False.

This property is read-write.

LegendMaxEntries

Description

Use this property to specify the number of legend entries before a new column (or row) is created.

When the legend position is specified as left or right, the legend is drawn vertically so a new column is created when this property is exceeded.

When the legend position is specified as top or bottom, the legend is drawn horizontally and a new row is created when this property is exceeded.

The default value of this property is five.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-write.

LegendPosition

Description

Use this property to specify where the legend should appear, in relationship to the chart. You can specify either a numeric or constant value for this property.

Note: ChartLegend_Separate generates a legend without a chart. The legend takes over the entire charting area.

The values are:

Numeric Value	*Constant Value*	*Description*
0	%ChartLegend_Left	Display legend to the left of the chart.
1	%ChartLegend_Right	Display legend to the right of the chart.
2	%ChartLegend_Top	Display legend on top of the chart.
3	%ChartLegend_Bottom	Display legend below the chart.
4	%ChartLegend_Separate	Generate a legend without a chart.

This property is read-write.

LegendStyle

Description

This property has been deprecated and is ignored.

LineChartDataGlyphSize

Description

Use this property to specify an integer from 0–100 that indicates the glyph size for a line chart.

If this property is set to a valid value, that will be used for the glyph size. If the property is not set or is set to an invalid value, determine whether the LineChartDataGlyphSize style class has been defined. If the style class is not defined or is set to an invalid value, then the default value, 80, is used.

This property is read-write.

Related Links

SetGlyphArray

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

LineType

Description

This property has been deprecated and is ignored.

MainTitle

Description

Use this property to specify the text for the main title of the chart.

This property takes a string value.

This property is read-write.

MainTitleOrient

Description

This property has been deprecated and is ignored.

MainTitleStyle

Description

This property has been deprecated and is ignored.

OLLineType

Description

This property has been deprecated and is ignored.

OLType

Description

Use this property to specify that you want an overlay line chart to be displayed on the chart.

Note: Only charts with the property Type set to 0 (or %ChartType_2DBar) can have an overlay chart. If you specify any other chart type while specifying a value for the OLType property, no overlay chart will be displayed.

You can specify either a numeric or a constant value for this property. The value is:

Numeric Value	*Constant Value*	*Description*
4	%ChartType_2DLine	Overlay is drawn as a 2D line.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-write.

RevertToPre850

Description

This property has been deprecated and is ignored.

RotationAngle

Description

This property has been deprecated and is ignored.

SetChartURL

Description

Use this property to specify a URL to be launched when the chart background is clicked. The URL must be a fully formed URL specified as a string. For example:

```
http://example.org/index.htm
```

The IsChartDrillable property must be set to True to enable clicking on the chart background.

Example

```
&oChart.IsChartDrillable = True;
&oChart.SetChartURL = "http://example.org/index.htm";
```

Related Links

IsChartDrillable

ShowCrossHair

Description

Use the ShowCrossHair property to specify whether the chart should be split into quadrants.

This property takes a boolean value. If you specify true, two lines are drawn, one from the middle of the x-axis and one from the middle of the y-axis.

This property is read-write.

Style

Description

This property has been deprecated and is ignored.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

StyleSheet

Description

This property has been deprecated and is ignored.

Related Links

Styling PeopleSoft Charts

SubTitle

Description

Use this property to specify the text for a subtitle for the chart. The subtitle appears beneath the main title.

This property takes a string value.

This property is read-write.

Type

Description

Use this property to specify the type of chart that you want. You can specify either a numeric or constant value for this property. The valid values are:

Numeric Value	*Constant Value*	*Description*
0	%ChartType_2DBar	Two-dimensional bar chart
1	%ChartType_2DStackedBar	Two-dimensional stacked bar chart
2	%ChartType_2DPercentBar	Two-dimensional percent bar chart
3	%ChartType_2DHorizStackedBar	Two-dimensional stacked horizontal bar chart
4	%ChartType_2DLine	Two-dimensional line chart
5	%ChartType_2DHistogram	Two-dimensional histogram chart
6	%ChartType_2DPie	Two-dimensional pie chart
7	%ChartType_3DBar	Three-dimensional bar chart
8	%ChartType_3DStackedBar	Three-dimensional stacked bar chart
9	%ChartType_3DPie	Three-dimensional pie chart

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Numeric Value	*Constant Value*	*Description*
10	%ChartType_2DHorizPercentBar	Two-dimensional horizontal percent chart
11	%ChartType_3DPercentBar	Three-dimensional percent bar char
13	%ChartType_2DHorizBar	Two-dimensional horizontal bar chart
14	%ChartType_2DScatter	Scatter chart
18	%ChartType_2DBubble	Bubble chart
31	%ChartType_Funnel	Funnel chart
32	%ChartType_2DRing	Two-dimensional ring chart
33	%ChartType_3DRing	Three-dimensional ring chart

This property is read-write.

Related Links

Chart Class Chart Types

Width

Description

Use this property to specify a Number value indicating the width of the chart in pixels.

Generally this property is used with charts created for iScripts, to specify the width of the image, before generating the image map. You can also use it to overwrite the width set in Application Designer.

If you try to read this property before setting it, the value returned is zero.

Note: The Height and Width properties must be set to the same value to change the size of a 2D Scatter chart, that is, a chart with the Type property set to %ChartType_2DScatter.

This property is read-write.

Related Links

Height

XAxisCross

Description

This property has been deprecated and is ignored.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

XAxisCrossPoint

Description

Use the XAxisCrossPoint property to specify the point at which the x-axis intersects a numeric y-axis. The value is in the coordinate system of the y-axis scale.

This property is read-write.

Note: This property is not applicable to scatter and bubble charts.

Related Links

YAxisCrossPoint

XAxisLabelOrient

Description

Use this property to specify whether the x-axis label is displayed horizontally or vertically. If you do not specify this value, PeopleTools will determine the label orientation automatically.

You can specify either a numeric value or a constant for this property. Values are:

Numeric Value	*Constant Value*	*Description*
0	%ChartText_Horizontal	The x-axis label is displayed horizontally.
90	%ChartText_Vertical	The x-axis label is displayed vertically

This property is read-write.

XAxisMax

Description

The maximum value of the x-axis.

This property is applicable only if the IsTrueXY property has been set to True.

This property is read-write.

XAxisMin

Description

The minimum value of the x-axis.

This property is applicable only if the IsTrueXY property has been set to True.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-write.

XAxisPrecision

Description

Use the XAxisPrecision property to control the number of decimal places displayed in the labels of a numeric x-axis.

This property is applicable only if the IsTrueXY property has been set to True.

This property is read-write.

Related Links

YAxisPrecision

XAxisScaleResolution

Description

This property has been deprecated and is ignored.

XAxisStyle

Description

This property has been deprecated and is ignored.

XAxisTicks

Description

Use this property to specify the number of minor tick marks along the x-axis. This property takes a numeric value.

Note: This property is applicable only if for numeric data on the x-axis.

This property is read-write.

Related Links

Creating a Chart Using the Chart Class

XAxisTitle

Description

Use this property to specify the text for the x-axis title.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

XAxisTitleOrient

Description

Use this property to specify the orientation of the text for the x-axis title.

You can specify either a number or a constant for this property. The values are:

Numeric Value	*Constant Value*	*Description*
0	%ChartText_Horizontal	Title text is displayed horizontally.
90	%ChartText_Vertical	Title text is displayed vertically. This property is read-write.

XAxisTitleStyle

Description

This property has been deprecated and is ignored.

XRotationAngle

Description

This property has been deprecated and is ignored.

YAxisCrossPoint

Description

Use the YAxisCrossPoint property to specify the point at which the y-axis intersects a numeric x-axis. The value is in the coordinate system of the x-axis scale.

This property is applicable only if the IsTrueXY property has been set to True.

This property is read-write.

Note: This property is not applicable to scatter and bubble charts.

Related Links

XAxisCrossPoint

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

YAxisLabelOrient

Description

Use this property to specify whether the y-axis label is displayed horizontally or vertically. If you do not specify this value, PeopleTools will determine the label orientation automatically.

You can specify either a numeric value or a constant for this property. Valid values are:

Numeric Value	*Constant Value*	*Description*
0	%ChartText_Horizontal	The y-axis label is displayed horizontally.
90	%ChartText_Vertical	The y-axis label is displayed vertically

This property is read-write.

YAxisMax

Description

Use this property to specify the maximum value of the y (data) axis. This property takes a numeric value.

The maximum value sets the largest value that is displayed on the axis.

Note: If the YAxisMax and YAxisMin properties are not set, or are set to too narrow a range, ticks may not appear on the y-axis.

This property is read-write.

YAxisMin

Description

Use this property to specify the minimum value of the y-axis. This property takes a numeric value.

The minimum value sets the point at which the chart plots in positive and negative directions.

The default minimum value is the default value of the y-axis.

Note: If the YAxisMax and YAxisMin properties are not set, or are set to too narrow a range, ticks may not appear on the y-axis.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

YAxisPrecision

Description

Use the YAxisPrecision property to control the number of decimal places displayed in the labels of a numeric y-axis.

This property is read-write.

Related Links

XAxisPrecision

YAxisScaleResolution

Description

This property has been deprecated and is ignored.

YAxisStyle

Description

This property has been deprecated and is ignored.

YAxisTicks

Description

Use this property to specify the number of minor tick marks along the y (data) axis. This property takes a numeric value.

This property is read-write.

Related Links

Creating a Chart Using the Chart Class

YAxisTitle

Description

Use this property to specify text of the title for the y-axis.

This property is read-write.

YAxisTitleOrient

Description

Use this property to specify the orientation of the text for the y-axis title.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

You can specify either a number or a constant for this property. The values are:

Numeric Value	*Constant Value*	*Description*
0	%ChartText_Horizontal	Title text is displayed horizontally.
90	%ChartText_Vertical	Title text is displayed vertically. This property is read-write.

YAxisTitleStyle

Description

This property has been deprecated and is ignored.

YRotationAngle

Description

This property has been deprecated and is ignored.

ZRotationAngle

Description

This property has been deprecated and is ignored.

ReferenceArea Class Properties

These properties are used by the ReferenceArea class. The properties are described in alphabetic order.

Related Links

Using the ReferenceArea Class

Association

Description

Use this property to specify which chart axis the reference area will be associated with. There is no default value; you must explicitly set the value of this property or the reference area will not appear in the chart. You can specify either an Integer or constant value for this property.

The values are:

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Numeric Value	*Constant Value*	*Description*
1	%Ref_Association_Y1	Associate the reference area with the y-axis.
2	%Ref_Association_X1	Associate the reference area with the x-axis. **Note:** This association can be made only if the x-axis is numeric.

This property is read-write.

Description

Description

Use this property to specify a description of the reference area as a String value. This text will appear in the chart legend and should describe what the reference area represents in the chart. The text will be displayed only when the IsDisplayedTextInLegend property is True.

See “Setting Chart Legends” in the Chart class design guidelines for more information on creating chart legends.

This property is read-write.

Related Links

Chart Class Design Guidelines

IsDisplayedTextInLegend

Description

Use this property to specify a Boolean value indicating whether the Description property is displayed in the chart legend. The default value is True.

This property is read-write.

ReferenceAreaColor

Description

Use this property to specify the color of the reference area as an Integer or constant value.

The following lists all the values you can specify. You can use either the numeric or constant value.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Numeric Value	*Constant Value*	*Description*
-1	%ChartColor_Series_Default	Default series color. When a data point is set to this, the default series color or the color that has been set by the programmer for that series is used instead. This value works only with the SetColorArray method of the Chart class.
0	%ChartColor_Black	Black
1	%ChartColor_Blue	Blue
2	%ChartColor_Cyan	Cyan
3	%ChartColor_DarkGray	Dark gray
4	%ChartColor_Gray	Gray
5	%ChartColor_Green	Green
6	%ChartColor_LightGray	Light gray
7	%ChartColor_Magenta	Magenta
8	%ChartColor_Orange	Orange
9	%ChartColor_Pink	Pink
10	%ChartColor_Red	Red
11	%ChartColor_White	White
12	%ChartColor_Yellow	Yellow
13	%ChartColor_Red_Orange	Red-orange
14	%ChartColor_Yellow_Green	Yellow-green
15	%ChartColor_Blue_Violet	Blue-violet
16	%ChartColor_Purple	Purple
17	%ChartColor_Yellow_Orange	Yellow-orange

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ReferenceAreaLocation

Description

Use this property to specify whether the reference area is displayed in front of or behind the chart. You can specify either an Integer or constant value for this property.

The values are:

Numeric Value	*Constant Value*	*Description*
2	%Ref_Back	Display the reference area behind the chart. **Note:** %Ref_Back is the default value.
1	%Ref_Front	Display the reference area on top of the chart.

This property is read-write.

ReferenceAreaValues

Description

Use this property to specify an array of two numeric values. The values indicate the minimum and maximum for the reference area. The order of the values does not matter.

This property is read-write.

ShortText

Description

Use this property to specify a short description for the reference area as a String value. This text will be displayed as the data hint for the reference area.

This property is read-write.

ReferenceLine Class Properties

These properties are used by the ReferenceLine class. The properties are described in alphabetic order.

Related Links

Using the ReferenceLine Class

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Association

Description

Use this property to specify which chart axis the reference line will be associated with. There is no default value; you must explicitly set the value of this property or the reference line will not appear in the chart. You can specify either an Integer or constant value for this property.

The values are:

Numeric Value	*Constant Value*	*Description*
1	%Ref_Association_Y1	Associate the reference line with the y-axis.
2	%Ref_Association_X1	Associate the reference line with the x-axis. **Note:** This association can be made only if the x-axis is numeric.

This property is read-write.

Description

Description

Use this property to specify a description of the reference line as a String value. This text will appear in the chart legend and should describe what the reference line represents in the chart. The text will be displayed only when the IsDisplayedTextInLegend property is True.

See “Setting Chart Legends” in the Chart class design guidelines for more information on creating chart legends.

This property is read-write.

Related Links

Chart Class Design Guidelines

IsDisplayedTextInLegend

Description

Use this property to specify a Boolean value indicating whether the Description property is displayed in the chart legend. The default value is True.

This property is read-write.

ReferenceLineColor

Description

Use this property to specify the color of the reference line as an Integer or constant value.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The following lists all the values you can specify. You can use either the numeric or constant value.

Numeric Value	***Constant Value***	***Description***
-1	%ChartColor_Series_Default	Default series color. When a data point is set to this, the default series color or the color that has been set by the programmer for that series is used instead. This value works only with the SetColorArray method of the Chart class.
0	%ChartColor_Black	Black
1	%ChartColor_Blue	Blue
2	%ChartColor_Cyan	Cyan
3	%ChartColor_DarkGray	Dark gray
4	%ChartColor_Gray	Gray
5	%ChartColor_Green	Green
6	%ChartColor_LightGray	Light gray
7	%ChartColor_Magenta	Magenta
8	%ChartColor_Orange	Orange
9	%ChartColor_Pink	Pink
10	%ChartColor_Red	Red
11	%ChartColor_White	White
12	%ChartColor_Yellow	Yellow
13	%ChartColor_Red_Orange	Red-orange
14	%ChartColor_Yellow_Green	Yellow-green
15	%ChartColor_Blue_Violet	Blue-violet
16	%ChartColor_Purple	Purple
17	%ChartColor_Yellow_Orange	Yellow-orange

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ReferenceLineLocation

Description

Use this property to specify whether the reference line is displayed in front of or behind the chart. You can specify either an Integer or constant value for this property.

The values are:

Numeric Value	*Constant Value*	*Description*
2	%Ref_Back	Display the reference line behind the chart. **Note:** %Ref_Back is the default value.
1	%Ref_Front	Display the reference line on top of the chart.

This property is read-write.

ReferenceLineValue

Description

Use this property to specify the axis value for the reference line as a Number. If this property is not specified, no reference line is displayed.

This property is read-write.

ShortText

Description

Use this property to specify a short description for the reference line as a String value. This text will be displayed as the data hint for the reference line.

This property is read-write.

DialGauge Class Methods

These methods are used by the DialGauge class. The methods are described in alphabetic order.

Refresh

Syntax

```
Refresh()
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the Refresh method to clear all existing gauge settings and data.

Parameters

None.

Returns

None.

SetThreshold

Syntax

SetThreshold(*&threshold*)

Description

Use the SetThreshold method to associate a Threshold object with the gauge.

Parameters

&threshold	Specify an already instantiated object of the Threshold class.

Returns

None.

Related Links

Using the Threshold Class
Threshold Class Properties

DialGauge Class Properties

These properties are used by the DialGauge class. The properties are described in alphabetic order.

AdditionalStyleSuffix

Description

Use this property to specify a style class name suffix as a String value.

Then, in Application Designer, create custom style class definitions by append this style class name suffix to style class names. These custom style class definitions will override delivered style class definitions found in any of the PSCHARTSTYLE* sub style sheets.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

For example, if the value of this property is set to MY_OVRD, then create the PSCHARTTITLE_MY_OVRD custom style class to override the PSCHARTTITLE style class.

This property is read-write.

Related Links

Styling PeopleSoft Charts

AnimationDuration

Description

Use this property to specify an Integer value (0 or greater) indicating how long (in milliseconds) the gauge animation should last.

If this property is not specified, it defaults to the value of the GAnimationDuration property of the PT_CHART_GAUGE style class, which is 500 milliseconds.

This property is read-write.

AnimationType

Description

Use this property to specify the animation type for the gauge. You can specify either an Integer or constant value for this property.

If this property is not specified, it defaults to the value of the GAnimationDefType property of the PT_CHART_GAUGE style class, which is TransitionToLeft.

The values are:

Numeric Value	*Constant Value*
0	%Animation_None
1	%Animation_Auto **Note:** The automatic animation is determined by the charting engine and varies by chart type.
2	%Animation_AlphaFade
3	%Animation_ConveyorFromRight
4	%Animation_ConveyorFromLeft
5	%Animation_CubeToLeft
6	%Animation_CubeToRight

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Numeric Value	*Constant Value*
7	%Animation_FlipRight
8	%Animation_FlipLeft
9	%Animation_SlideToLeft
10	%Animation_SlideToRight
11	%Animation_TransitionToLeft
12	%Animation_TransitionToRight
13	%Animation_Zoom

This property is read-write.

BottomLabel

Description

Use this property to specify the text of the bottom label as a String value.

This property is read-write.

BottomLabelPosition

Description

Use this property to specify the position of the bottom label. You can specify either an Integer or constant value for this property.

The values are:

Numeric Value	*Constant Value*	*Description*
1	%BelowGauge	Display the bottom label below the gauge. **Note:** %BelowGauge is the default value.
2	%InsideGauge	Display the bottom label inside the gauge.
5	%Label_None	Do not display a bottom label for the gauge.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GaugeDecimalDigit

Description

Use this property to specify an Integer indicating the number of decimal places to display for the metric label. The default value: 0.

This property is read-write.

GaugeMaximum

Description

Use this property to specify the highest value for the gauge as a Float value. If this property is not set, it will be automatically determined.

This property is read-write.

Example

In the following example, the maximum for the gauge is set to 100.

```
&cGauge.GaugeMaximum = 100;
```

Related Links

GaugeMinimum

GaugeMinimum

Description

Use this property to specify the lowest value for the gauge as a Float value. If this property is not set, it will be automatically determined.

This property is read-write.

Example

In the following example, the minimum for the gauge is set to 0.

```
&cGauge.GaugeMinimum = 0;
```

Related Links

GaugeMaximum

GaugeURL

Description

Use this property to specify a valid URL as a String value. If IsDrillable is true, then the user is redirected to this URL after clicking on (or touching) the gauge.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-write.

Related Links

IsDrillable

Height

Description

Use this property to specify a Number value indicating the height of the gauge in pixels. You can use this property to overwrite the height set in Application Designer. If you try to read this property before setting it, the value returned is zero.

This property is read-write.

Related Links

Width

IsDrillable

Description

Use this property to specify a Boolean value indicating whether the gauge is interactive—that is, whether the user can click on (or touch) the gauge to trigger an action. The default value is False.

The source of interactivity on a gauge can come from one of two places:

- A URL set in the gauge's GaugeURL property.
- FieldChange PeopleCode on the record field that holds the gauge area (that is, the Application Designer chart control).

If both a URL is set in the GaugeURL property and FieldChange PeopleCode exists on the record field of the gauge control, the URL will take precedence over the PeopleCode.

This property is read-write.

Related Links

GaugeURL

LegendPosition

Description

Use this property to specify where the legend should appear, in relationship to the gauge. You can specify either an Integer or constant value for this property.

The legend will only appear if you have used the SetThreshold method and you have set this property to something other than %ChartLegend_None.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The values are:

Numeric Value	*Constant Value*	*Description*
0	%ChartLegend_Left	Display the legend to the left of the gauge.
1	%ChartLegend_Right	Display the legend to the right of the gauge.
2	%ChartLegend_Top	Display the legend above the gauge.
3	%ChartLegend_Bottom	Display the legend beneath the gauge.
5	%ChartLegend_None	Don't display a legend. **Note:** %ChartLegend_None is the default value.

This property is read-write.

Related Links

SetThreshold

MajorTickIncrement

Description

Use this property to specify a Float value that indicates at what interval major tick marks appear. The default value is 0, which means that no major or minor tick marks will appear.

This property is read-write.

Related Links

MinorTickIncrement
TickLabelPosition

MetricLabelPosition

Description

Use this property to specify the label position for the gauge's metric value. You can specify either an Integer or constant value for this property.

The values are:

Numeric Value	*Constant Value*	*Description**
1	%BelowGauge	Display the label for the metric below the gauge.
2	%InsideGauge	Display the label for the metric inside the gauge.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Numeric Value	*Constant Value*	*Description**
5	%Label_None	Don't display a label for the metric. **Note:** %Label_None is the default value.
6	%WithBottomGauge	Display the metric label together with the bottom label.

* The positions described are when the Type property is set to %GaugeType_Dial_Standard. For other dial gauge types, the positions can vary from the ones described.

This property is read-write.

Related Links

BottomLabelPosition

MetricLabelType

Description

Use this property to specify the label type for the gauge's metric value. You can specify either an Integer or constant value for this property.

The values are:

Numeric Value	*Constant Value*	*Description*
1	%Number	Display the metric as a number.
2	%Percent	Display the metric as a percentage, which is calculated as follows: `((Metric - Gauge Minimum) / (Gauge Maximum - Gauge Minimum)) * 100`

This property is read-write.

MinorTickIncrement

Description

Use this property to specify a Float value that indicates at what interval minor tick marks appear. Minor tick marks will not appear unless major tick marks also appear.

This property is read-write.

Related Links

MajorTickIncrement

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

TickLabelPosition

Description

Use this property to specify the position of the labels for the major tick marks on the gauge. You can specify either an Integer or constant value for this property.

The values are:

Numeric Value	*Constant Value*	*Description*
0	%TickLabel_ Interior	Display the labels on the interior of the gauge. **Note:** %TickLabel_Interior is the default value.
1	%TickLabel_ Exterior	Display the labels on the exterior of the gauge.

This property is read-write.

Related Links

MajorTickIncrement

TopLabel

Description

Use this property to specify the text of the top label as a String value.

This property is read-write.

TopLabelPosition

Description

Use this property to specify the position of the top label. You can specify either an Integer or constant value for this property.

The values are:

Numeric Value	*Constant Value*	*Description*
0	%AboveGauge	Display the top label above the gauge. **Note:** %AboveGauge is the default value.
2	%InsideGauge	Display the top label inside the gauge.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Numeric Value	Constant Value	Description
5	%Label_None	Do not display a top label for the gauge.

This property is read-write.

Type

Description

Use this property to specify the visual representation of the gauge. You can specify either an Integer or constant value for this property.

The values are:

Numeric Value	Constant Value	Description
20	%GaugeType_Dial_Standard	Display a standard dial gauge, which is a semi-circle: **Note:** %GaugeType_Dial_Standard is the default value.
21	%GaugeType_Dial_ BeveledCircle	Display a dial gauge as a beveled circle:
22	%GaugeType_Dial_FullCircle	Display a dial gauge as a full circle:

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Numeric Value	*Constant Value*	*Description*
23	%GaugeType_Dial_ RoundedRect	Display a dial gauge as a rectangle with rounded corners:

This property is read-write.

Example

In the following example, the dial gauge is displayed as a full circle.

```
&cDialGauge.Type = %GaugeType_Dial_FullCircle;
```

Width

Description

Use this property to specify a Number value indicating the height of the gauge in pixels. You can use this property to overwrite the height set in Application Designer. If you try to read this property before setting it, the value returned is zero.

This property is read-write.

Related Links

Height

LEDGauge Class Methods

These methods are used by the LEDGauge class. The methods are described in alphabetic order.

Refresh

Syntax

Refresh()

Description

Use the Refresh method to clear all existing gauge settings and data.

Parameters

None.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

None.

SetThreshold

Syntax

SetThreshold(*&threshold*)

Description

Use the SetThreshold method to associate a Threshold object with the gauge.

Parameters

&threshold	Specify an already instantiated object of the Threshold class.

Returns

None.

Related Links

Using the Threshold Class
Threshold Class Properties

LEDGauge Class Properties

These properties are used by the LEDGauge class. The properties are described in alphabetic order.

AdditionalStyleSuffix

Description

Use this property to specify a style class name suffix as a String value.

Then, in Application Designer, create custom style class definitions by append this style class name suffix to style class names. These custom style class definitions will override delivered style class definitions found in any of the PSCHARTSTYLE* sub style sheets.

For example, if the value of this property is set to MY_OVRD, then create the PSCHARTTITLE_MY_OVRD custom style class to override the PSCHARTTITLE style class.

This property is read-write.

Related Links

Styling PeopleSoft Charts

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

AnimationDuration

Description

Use this property to specify an Integer value (0 or greater) indicating how long (in milliseconds) the gauge animation should last.

If this property is not specified, it defaults to the value of the GAnimationDuration property of the PT_CHART_GAUGE style class, which is 500 milliseconds.

This property is read-write.

AnimationType

Description

Use this property to specify the animation type for the gauge. You can specify either an Integer or constant value for this property.

If this property is not specified, it defaults to the value of the GAnimationDefType property of the PT_CHART_GAUGE style class, which is TransitionToLeft.

The values are:

Numeric Value	*Constant Value*
0	%Animation_None
1	%Animation_Auto **Note:** The automatic animation is determined by the charting engine and varies by chart type.
2	%Animation_AlphaFade
3	%Animation_ConveyorFromRight
4	%Animation_ConveyorFromLeft
5	%Animation_CubeToLeft
6	%Animation_CubeToRight
7	%Animation_FlipRight
8	%Animation_FlipLeft
9	%Animation_SlideToLeft
10	%Animation_SlideToRight
11	%Animation_TransitionToLeft

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Numeric Value	*Constant Value*
12	%Animation_TransitionToRight
13	%Animation_Zoom

This property is read-write.

BottomLabel

Description

Use this property to specify the text of the bottom label as a String value.

This property is read-write.

BottomLabelPosition

Description

Use this property to specify the position of the bottom label. You can specify either an Integer or constant value for this property.

The values are:

Numeric Value	*Constant Value*	*Description*
1	%BelowGauge	Display the bottom label below the gauge. **Note:** %BelowGauge is the default value.
2	%InsideGauge	Display the bottom label inside the gauge.
5	%Label_None	Do not display a bottom label for the gauge.

This property is read-write.

GaugeDecimalDigit

Description

Use this property to specify an Integer indicating the number of decimal places to display for the metric label. The default value: 0.

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GaugeURL

Description

Use this property to specify a valid URL as a String value. If IsDrillable is true, then the user is redirected to this URL after clicking on (or touching) the gauge.

This property is read-write.

Related Links

IsDrillable

Height

Description

Use this property to specify a Number value indicating the height of the gauge in pixels. You can use this property to overwrite the height set in Application Designer. If you try to read this property before setting it, the value returned is zero.

This property is read-write.

Related Links

Width

IsDrillable

Description

Use this property to specify a Boolean value indicating whether the gauge is interactive—that is, whether the user can click on (or touch) the gauge to trigger an action. The default value is False.

The source of interactivity on a gauge can come from one of two places:

- A URL set in the gauge's GaugeURL property.
- FieldChange PeopleCode on the record field that holds the gauge area (that is, the Application Designer chart control).

If both a URL is set in the GaugeURL property and FieldChange PeopleCode exists on the record field of the gauge control, the URL will take precedence over the PeopleCode.

This property is read-write.

Related Links

GaugeURL

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

LegendPosition

Description

Use this property to specify where the legend should appear, in relationship to the gauge. You can specify either an Integer or constant value for this property.

The legend will only appear if you have used the SetThreshold method and you have set this property to something other than %ChartLegend_None.

The values are:

Numeric Value	*Constant Value*	*Description*
0	%ChartLegend_Left	Display the legend to the left of the gauge.
1	%ChartLegend_Right	Display the legend to the right of the gauge.
2	%ChartLegend_Top	Display the legend above the gauge.
3	%ChartLegend_Bottom	Display the legend beneath the gauge.
5	%ChartLegend_None	Don't display a legend. **Note:** %ChartLegend_None is the default value.

This property is read-write.

Related Links

SetThreshold

MetricLabelPosition

Description

Use this property to specify the label position for the gauge's metric value. You can specify either an Integer or constant value for this property.

The values are:

Numeric Value	*Constant Value*	*Description**
1	%BelowGauge	Display the label for the metric below the gauge.
2	%InsideGauge	Display the label for the metric inside the gauge.
5	%Label_None	Don't display a label for the metric. **Note:** %Label_None is the default value.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Numeric Value	Constant Value	Description*
6	%WithBottomGauge	Display the metric label together with the bottom label.

* The positions described are when the Type property is set to %GaugeType_Dial_Standard. For other dial gauge types, the positions can vary from the ones described.

This property is read-write.

Related Links

BottomLabelPosition

MetricLabelType

Description

Use this property to specify the label type for the gauge's metric value. You can specify either an Integer or constant value for this property.

The values are:

Numeric Value	Constant Value	Description
1	%Number	Display the metric as a number.
2	%Percent	Display the metric as a percentage, which is calculated as follows: `((Metric - Gauge Minimum) / (Gauge Maximum - Gauge Minimum)) * 100`

This property is read-write.

TopLabel

Description

Use this property to specify the text of the top label as a String value.

This property is read-write.

TopLabelPosition

Description

Use this property to specify the position of the top label. You can specify either an Integer or constant value for this property.

The values are:

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Numeric Value	Constant Value	Description
0	%AboveGauge	Display the top label above the gauge. **Note:** %AboveGauge is the default value.
2	%InsideGauge	Display the top label inside the gauge.
5	%Label_None	Do not display a top label for the gauge.

This property is read-write.

Type

Description

Use this property to specify the visual representation of the gauge. You can specify either an Integer or constant value for this property.

The values are:

Numeric Value	Constant Value	Description
26	%GaugeType_LED_Dot	Display an LED gauge as a dot: **Note:** %GaugeType_LED_Dot is the default value.
27	%GaugeType_LED_Arrow	Display an LED gauge as an arrow:
28	%GaugeType_LED_Triangle	Display an LED gauge as a triangle:

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Numeric Value	*Constant Value*	*Description*
29	%GaugeType_LED_Rectangle	Display an LED gauge as a rectangle:
30	%GaugeType_LED_Square	Display an LED gauge as a square:

This property is read-write.

Example

In the following example, the status meter gauge is displayed horizontally.

```
&cLEDGauge.Type = %GaugeType_StatusMeter_Horiz;
```

Width

Description

Use this property to specify a Number value indicating the height of the gauge in pixels. You can use this property to overwrite the height set in Application Designer. If you try to read this property before setting it, the value returned is zero.

This property is read-write.

Related Links

Height

StatusMeterGauge Class Methods

These methods are used by the StatusMeterGauge class. The methods are described in alphabetic order.

Refresh

Syntax

Refresh()

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the Refresh method to clear all existing gauge settings and data.

Parameters

None.

Returns

None.

SetThreshold

Syntax

SetThreshold(*&threshold*)

Description

Use the SetThreshold method to associate a Threshold object with the gauge.

Parameters

&threshold	Specify an already instantiated object of the Threshold class.

Returns

None.

Related Links

Using the Threshold Class
Threshold Class Properties

StatusMeterGauge Class Properties

These properties are used by the StatusMeterGauge class. The properties are described in alphabetic order.

AdditionalStyleSuffix

Description

Use this property to specify a style class name suffix as a String value.

Then, in Application Designer, create custom style class definitions by append this style class name suffix to style class names. These custom style class definitions will override delivered style class definitions found in any of the PSCHARTSTYLE* sub style sheets.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

For example, if the value of this property is set to MY_OVRD, then create the PSCHARTTITLE_MY_OVRD custom style class to override the PSCHARTTITLE style class.

This property is read-write.

Related Links

Styling PeopleSoft Charts

AnimationDuration

Description

Use this property to specify an Integer value (0 or greater) indicating how long (in milliseconds) the gauge animation should last.

If this property is not specified, it defaults to the value of the GAnimationDuration property of the PT_CHART_GAUGE style class, which is 500 milliseconds.

This property is read-write.

AnimationType

Description

Use this property to specify the animation type for the gauge. You can specify either an Integer or constant value for this property.

If this property is not specified, it defaults to the value of the GAnimationDefType property of the PT_CHART_GAUGE style class, which is TransitionToLeft.

The values are:

Numeric Value	*Constant Value*
0	%Animation_None
1	%Animation_Auto **Note:** The automatic animation is determined by the charting engine and varies by chart type.
2	%Animation_AlphaFade
3	%Animation_ConveyorFromRight
4	%Animation_ConveyorFromLeft
5	%Animation_CubeToLeft
6	%Animation_CubeToRight

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Numeric Value	*Constant Value*
7	%Animation_FlipRight
8	%Animation_FlipLeft
9	%Animation_SlideToLeft
10	%Animation_SlideToRight
11	%Animation_TransitionToLeft
12	%Animation_TransitionToRight
13	%Animation_Zoom

This property is read-write.

BottomLabel

Description

Use this property to specify the text of the bottom label as a String value.

This property is read-write.

BottomLabelPosition

Description

Use this property to specify the position of the bottom label. You can specify either an Integer or constant value for this property.

The values are:

Numeric Value	*Constant Value*	*Description*
1	%BelowGauge	Display the bottom label below the gauge. **Note:** %BelowGauge is the default value.
2	%InsideGauge	Display the bottom label inside the gauge.
5	%Label_None	Do not display a bottom label for the gauge.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GaugeDecimalDigit

Description

Use this property to specify an Integer indicating the number of decimal places to display for the metric label. The default value: 0.

This property is read-write.

GaugeMaximum

Description

Use this property to specify the highest value for the gauge as a Float value. If this property is not set, it will be automatically determined.

This property is read-write.

Example

In the following example, the maximum for the gauge is set to 100.

```
&cGauge.GaugeMaximum = 100;
```

Related Links

GaugeMinimum

GaugeMinimum

Description

Use this property to specify the lowest value for the gauge as a Float value. If this property is not set, it will be automatically determined.

This property is read-write.

Example

In the following example, the minimum for the gauge is set to 0.

```
&cGauge.GaugeMinimum = 0;
```

Related Links

GaugeMaximum

GaugeURL

Description

Use this property to specify a valid URL as a String value. If IsDrillable is true, then the user is redirected to this URL after clicking on (or touching) the gauge.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-write.

Related Links

IsDrillable

Height

Description

Use this property to specify a Number value indicating the height of the gauge in pixels. You can use this property to overwrite the height set in Application Designer. If you try to read this property before setting it, the value returned is zero.

This property is read-write.

Related Links

Width

IsDrillable

Description

Use this property to specify a Boolean value indicating whether the gauge is interactive—that is, whether the user can click on (or touch) the gauge to trigger an action. The default value is False.

The source of interactivity on a gauge can come from one of two places:

- A URL set in the gauge's GaugeURL property.
- FieldChange PeopleCode on the record field that holds the gauge area (that is, the Application Designer chart control).

If both a URL is set in the GaugeURL property and FieldChange PeopleCode exists on the record field of the gauge control, the URL will take precedence over the PeopleCode.

This property is read-write.

Related Links

GaugeURL

LegendPosition

Description

Use this property to specify where the legend should appear, in relationship to the gauge. You can specify either an Integer or constant value for this property.

The legend will only appear if you have used the SetThreshold method and you have set this property to something other than %ChartLegend_None.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The values are:

Numeric Value	*Constant Value*	*Description*
0	%ChartLegend_Left	Display the legend to the left of the gauge.
1	%ChartLegend_Right	Display the legend to the right of the gauge.
2	%ChartLegend_Top	Display the legend above the gauge.
3	%ChartLegend_Bottom	Display the legend beneath the gauge.
5	%ChartLegend_None	Don't display a legend. **Note:** %ChartLegend_None is the default value.

This property is read-write.

Related Links

SetThreshold

MajorTickIncrement

Description

Use this property to specify a Float value that indicates at what interval major tick marks appear. The default value is 0, which means that no major or minor tick marks will appear.

This property is read-write.

Related Links

MinorTickIncrement

MetricLabelPosition

Description

Use this property to specify the label position for the gauge's metric value. You can specify either an Integer or constant value for this property.

The values are:

Numeric Value	*Constant Value*	*Description**
1	%BelowGauge	Display the label for the metric below the gauge.
2	%InsideGauge	Display the label for the metric inside the gauge.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Numeric Value	*Constant Value*	*Description**
5	%Label_None	Don't display a label for the metric. **Note:** %Label_None is the default value.
6	%WithBottomGauge	Display the metric label together with the bottom label.

* The positions described are when the Type property is set to %GaugeType_Dial_Standard. For other dial gauge types, the positions can vary from the ones described.

This property is read-write.

Related Links

BottomLabelPosition

MetricLabelType

Description

Use this property to specify the label type for the gauge's metric value. You can specify either an Integer or constant value for this property.

The values are:

Numeric Value	*Constant Value*	*Description*
1	%Number	Display the metric as a number.
2	%Percent	Display the metric as a percentage, which is calculated as follows: `((Metric - Gauge Minimum) / (Gauge Maximum - Gauge Minimum)) * 100`

This property is read-write.

MinorTickIncrement

Description

Use this property to specify a Float value that indicates at what interval minor tick marks appear. Minor tick marks will not appear unless major tick marks also appear.

This property is read-write.

Related Links

MajorTickIncrement

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

TopLabel

Description

Use this property to specify the text of the top label as a String value.

This property is read-write.

TopLabelPosition

Description

Use this property to specify the position of the top label. You can specify either an Integer or constant value for this property.

The values are:

Numeric Value	*Constant Value*	*Description*
0	%AboveGauge	Display the top label above the gauge. **Note:** %AboveGauge is the default value.
2	%InsideGauge	Display the top label inside the gauge.
5	%Label_None	Do not display a top label for the gauge.

This property is read-write.

Type

Description

Use this property to specify the visual representation of the gauge. You can specify either an Integer or constant value for this property.

The values are:

Numeric Value	*Constant Value*	*Description*
24	%GaugeType_StatusMeter_Horiz	Display a horizontal status meter gauge:

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Numeric Value	*Constant Value*	*Description*
25	%GaugeType_StatusMeter_Vert	Display a vertical status meter gauge: **Note:** %GaugeType_StatusMeter_Vert is the default value.

This property is read-write.

Example

In the following example, the status meter gauge is displayed horizontally.

```
&cStatusMeterGauge.Type = %GaugeType_StatusMeter_Horiz;
```

Width

Description

Use this property to specify a Number value indicating the height of the gauge in pixels. You can use this property to overwrite the height set in Application Designer. If you try to read this property before setting it, the value returned is zero.

This property is read-write.

Related Links

Height

Threshold Class Properties

These properties are used by the Threshold class. The properties are described in alphabetic order.

Related Links

Using the Threshold Class
SetThreshold
SetThreshold
SetThreshold

Colors

Description

Use this property to specify the color values as an Array of Number. Choose a color for each reference area on the gauge.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The following lists all the values you can specify. You can use either the numeric or constant value.

Numeric Value	***Constant Value***	***Description***
-1	%ChartColor_Series_Default	Default series color. When a data point is set to this, the default series color or the color that has been set by the programmer for that series is used instead. This value works only with the SetColorArray method of the Chart class.
0	%ChartColor_Black	Black
1	%ChartColor_Blue	Blue
2	%ChartColor_Cyan	Cyan
3	%ChartColor_DarkGray	Dark gray
4	%ChartColor_Gray	Gray
5	%ChartColor_Green	Green
6	%ChartColor_LightGray	Light gray
7	%ChartColor_Magenta	Magenta
8	%ChartColor_Orange	Orange
9	%ChartColor_Pink	Pink
10	%ChartColor_Red	Red
11	%ChartColor_White	White
12	%ChartColor_Yellow	Yellow
13	%ChartColor_Red_Orange	Red-orange
14	%ChartColor_Yellow_Green	Yellow-green
15	%ChartColor_Blue_Violet	Blue-violet
16	%ChartColor_Purple	Purple
17	%ChartColor_Yellow_Orange	Yellow-orange

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

In the following example, the colors red, yellow, and green are specified by numeric value rather than by constant:

```
&Colors = CreateArray(10, 12, 5);
&oThr1.Colors = &Colors;
```

Related Links

Descriptions

Descriptions

Description

Use this property to specify the descriptions as an Array of String. The number of descriptions in the Descriptions array should match the number of colors that you have defined in the Colors array.

This property is read-write.

Example

The Descriptions array provides descriptions for the color values:

```
&Descr = CreateArray("Low", "Med", "High");
&oThr1.Descriptions = &Descr;
```

Related Links

Colors

Id

Description

Use this property to optionally specify an identifier for the Threshold object as a Number.

This property is read-write.

Values

Description

Use this property to specify the values as an Array of Number. Since the values mark the boundaries between the colors in the threshold, the number of entries in the Values array should be one less than the number of colors in the Colors array.

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

In this example, the number items in the Values array is one less than the number items in the Colors array:

```
&Values = CreateArray(30, 75);
&Colors = CreateArray(%ChartColor_Red, %ChartColor_Yellow, %ChartColor_Green);
&Descr = CreateArray("Low", "Med", "High");
&oThr1.Values = &Values;
&oThr1.Colors = &Colors;
&oThr1.Descriptions = &Descr;
```

Related Links

Colors

Gantt Class Methods

These methods are used by the Gantt class. The methods are described in alphabetic order.

Refresh

Syntax

Refresh()

Description

Use the Refresh method if the underlying data of the chart has changed, and you want to update the chart.

Note: This method has been deprecated and remains for backward compatibility only. Use the SetTaskAppData method or SetTaskData method instead.

You don't need to refresh after setting a property or method of the chart itself, such as setting the starting point or changing colors. When a method or property is used, the chart is automatically refreshed.

Parameters

None.

Returns

None.

Example

```
&MyChart.Refresh();
```

Related Links

SetTaskAppData

SetTaskData

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Reset

Syntax

Reset()

Description

Use the Reset method to clear all existing chart settings and data.

Parameters

None.

Returns

None.

Related Links

Refresh

SetActualEndDate

Syntax

SetActualEndDate(*RecordName.FieldName*)

Description

Use the SetActualEndDate method to specify the field in the record that defines the actual end date. This is an optional method, and is used in conjunction with the SetPlannedEndDate method. If an actual end date is specified, then an actual start date must also be specified. When defined, the actual or baseline tasks are visually shown as a separate task bar and are layered beneath the planned task if the two overlap.

Note: For any task that has a bad date format (from either SetActualEndDate or SetActualStartDate), any overlaid baseline information is not displayed in the chart section.

Parameters

RecordName.FieldName	Specify the field and its associated record that contains the value used to define the actual end date. This field must be of DateTime or Date type.

Returns

None.

Related Links

SetActualStartDate
SetPlannedEndDate

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SetPlannedStartDate

SetActualStartDate

Syntax

SetActualStartDate(*RecordName.FieldName*)

Description

Use the SetActualStartDate method to specify the field in the record that defines the actual start date. This is an optional method, and is used in conjunction with the SetPlannedStartDate method. If an actual start date is specified, then an actual end date must also be specified. When defined, the actual or baseline tasks are visually shown as a separate task bar and are layered beneath the planned task if the two overlap.

Note: For any task that has a bad date format (from either SetActualEndDate or SetActualStartDate), any overlaid baseline information is not displayed in the chart section.

Parameters

RecordName.FieldName Specify the field and its associated record that contains the value used to define the actual start date. This field must be of DateTime or Date type.

Returns

None.

Related Links

SetActualEndDate
SetPlannedEndDate
SetPlannedStartDate

SetActualTaskBarColor

Syntax

SetActualTaskBarColor(*RecordName.FieldName*)

Description

Use the SetActualTaskBarColor method to specify the field in the record that defines the colors for either the actual task bar or the actual milestone glyph.

Parameters

RecordName.FieldName Specify the field, and its associated record, that defines the task bar color. This field must be of type number, which means you can only use the numeric value for the color.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

None.

Related Links

SetPlannedTaskBarColor
TaskMilestoneGlyph

SetChartArea

Syntax

SetChartArea(*Percentage*)

Description

Use the SetChartArea method to specify what percentage of the Gantt chart is allocated to displaying the chart section. By default, both the task and chart sections are allocated 50% of the available space provided by the Gantt chart.

Parameters

Percentage

Specify the percentage of the page space for a Gantt chart that is allocated for displaying the chart area. Oracle recommends setting this value above .20 or 20%. Any point below .20 may cause the task bars and task dependency lines to become compressed and hard to read. If the percentage is set less than 0, this method uses a value of 0, enabling the table area to occupy the entire Gantt chart area.

This parameter takes a float value.

Returns

None.

SetDayFormat

Syntax

SetDayFormat(*Format*)

Description

Use the SetDayFormat method to specify the format of the day on a time line axis.

Parameters

Format

Specify the format the day should display in. The values are:

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Value	*Description*
%Chart_DayFormat	Display the day in a one- or two-digit format. **Note:** This is the default format.
%Chart_DayFormat_2Digit	**Note:** This constant has been deprecated; if specified, it defaults to %Chart_DayFormat.
%Chart_DayFormat_Name	Display the day using the full name, such as Monday, Tuesday, and so on.
%Chart_DayFormat_DOY	Display the day of the year in a numeric format, that is 1–366.
%Chart_DayFormat_DOY_ 2Digit	**Note:** This constant has been deprecated; if specified, it defaults to %Chart_DayFormat.
%Chart_DayFormat_ShortName	Display the day using the short name, such as Mon, Tue, and so on.

Returns

None.

Related Links

SetMonthFormat

SetHourFormat

Syntax

SetHourFormat(*Format*)

Description

This method has been deprecated and is ignored. The hour format is determined by a user's personalization settings.

Related Links

"Setting User Personalizations" (PeopleTools 8.54: Applications User's Guide)

SetMinuteFormat

Syntax

SetMinuteFormat(*Format*)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

This method has been deprecated and is ignored. The minute format is determined by a user's personalization settings.

Returns

None.

Related Links

"Setting User Personalizations" (PeopleTools 8.54: Applications User's Guide)

SetMonthFormat

Syntax

SetMonthFormat(*Format*)

Description

Use the SetMonthFormat method to specify the format of months on a time line axis.

Parameters

Format Specify the format of how the month should be displayed. Values are:

Value	*Description*
%Chart_MonthFormat	Display the month using a one- or two-digit number. **Note:** This is the default format.
%Chart_MonthFormat_2Digit	**Note:** This constant has been deprecated; if specified, it defaults to %Chart_MonthFormat.
%Chart_MonthFormat_ FullName	Display the month using the full name.
%Chart_MonthFormat_ShortName	Display the month using the short name, such as Jan, Feb, and so on.

Returns

None.

Related Links

SetDayFormat
SetYearFormat

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SetPlannedEndDate

Syntax

SetPlannedEndDate(*RecordName.FieldName*)

Description

Use the SetPlannedEndDate method to specify the field in the record that defines the planned end date. If planned versus actual dates are not used, this method specifies the end date of the task.

This method is required when creating a Gantt chart.

Note: For any task that has a bad date format (from either SetPlannedEndDate or SetPlannedStartDate), any overlaid baseline information is not displayed in the chart section.

Parameters

RecordName.FieldName	Specify the field and its associated record that contains the value used to define the planned end date. This field must be of DateTime or Date type.

Returns

None.

Related Links

SetActualEndDate
SetActualStartDate
SetPlannedStartDate

SetPlannedStartDate

Syntax

SetPlannedStartDate(*RecordName.FieldName*)

Description

Use the SetPlannedStartDate method to specify the field in the record that defines the planned start date. If planned versus actual dates are not used, this method specifies the start date of the task.

This method is required when creating a Gantt chart.

Note: For any task that has a bad date format (from either SetPlannedEndDate or SetPlannedStartDate), any overlaid baseline information is not displayed in the chart section.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

RecordName.FieldName	Specify the field and its associated record that contains the value used to define the planned start date. This field must be of DateTime or Date type.

Returns

None.

Related Links

SetActualEndDate
SetPlannedEndDate
SetPlannedStartDate

SetPlannedTaskBarColor

Syntax

SetPlannedTaskBarColor(*RecordName.FieldName*)

Description

Use the SetPlannedTaskBarColor method to specify the field in the record that defines the colors for either the planned task bar or the planned milestone glyph.

Parameters

RecordName.FieldName	Specify the field, and its associated record, that defines the task bar color. This field must be of type number, which mean you can only use the numeric values for specifying color.

Returns

None.

Related Links

SetActualTaskBarColor
TaskMilestoneGlyph

SetSecondFormat

Syntax

SetSecondFormat(*Format*)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

This method has been deprecated and is ignored. The second format is determined by a user's personalization settings.

Related Links

"Setting User Personalizations" (PeopleTools 8.54: Applications User's Guide)

SetTableXScrollbar

Syntax

```
SetTableXScrollbar(Scroll_ArrowAmount)
```

Description

This method has been deprecated and is ignored.

SetTaskAppData

Syntax

```
SetTaskAppData(RecordName.FieldName1 [, RecordName.FieldName2
[,RecordName.FieldName3. . .]])
```

Description

Use the SetTaskAppData method to specify the fields in the record that define the application data to be viewed in the table section.

In the table section, column one (or the left-most column) always displays the work breakdown structure (WBS) numbering (if given) and name of the task (or task ID if the name is not given). This method allows applications to define additional task data columns to be displayed in the right-most columns of the table section.

Parameters

RecordName.FieldNames	Specify the fields and their associated record that defines one or more application specific fields to be displayed as a column in the table section. The order in which the fields are given as parameters defines their column order in the table section. Because the task name (or task ID if the name is not given) is always shown in column one, the first record field value is displayed in column two.

Returns

None.

Related Links

SetTaskAppDataTitles

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SetTaskData
SetTaskDependencyData

SetTaskAppDataTitles

Syntax

SetTaskAppDataTitles(*&TitleArray*)

Description

Use the SetTaskAppDataTitles method to specify the column titles to be displayed in the table section, starting with column two. The title for column one (that is, the left-most column) in the table section is set using the SetTaskTitle method.

The length of the array should match the number of application data fields specified with the SetTaskAppData method. Additional strings beyond the number of application data fields are not displayed. If the number of strings in the array specified by this method is less than the number of application data fields, the blanks are displayed in these title columns.

Parameters

&TitleArray	Specify an array of strings containing the column titles to be displayed in the table section.

Returns

None.

Related Links

SetTaskAppData
TaskTitle

SetTaskBarURL

Syntax

SetTaskBarURL(*RecordName.FieldName*)

Description

Use the SetTaskBarURL method to specify the field in the record which defines the URL the browser redirects to when the user clicks on a task bar.

By default, the FieldChange event on the planned end date field of the Gantt task data record is triggered if the image map based interactivity is turned on (using the IsDrillable property). This can be overridden by specifying a URL that is triggered when the task bar is clicked.

Use the SetTaskDependencyURL method to specify the URL to be used when the user clicks on a dependency line in the chart section.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

Record.Fieldname	Specify the field, and its associated record, that defines the URL the browser is redirected to when the task bar is clicked. This field must be of type character. The URL must be an absolute URL.

Returns

None.

Related Links

SetTaskDependencyURL
IsDrillable

SetTaskData

Syntax

```
SetTaskData({Record.RecordName | &Rowset})
```

Description

Use the SetTaskData method to specify from where the task data is to be populated, either from a record or an already instantiated rowset.

Note: If you specify a rowset, the data in the rowset must be provided in the correct display order.

This method is required when you're creating a Gantt chart.

Parameters

***RecordName*	*&Rowset***	Specify the record or rowset that contains the task data. If you specify a record, you must prefix the record name with the keyword **Record.**

Returns

None.

Related Links

SetTaskDependencyData

SetTaskDependencyChildID

Syntax

```
SetTaskDependencyChildID(RecordName.FieldName)
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

The *dependent* task is the task where the dependency arrow ends. Use the SetTaskDependencyChildID method to specify the field in the record that defines the task ID for the dependent task.

The ID must match up to an ID in the Task data set.

This method is required if you specify dependency data.

Parameters

RecordName.FieldName	Specify the field, and its associated record, that defines the task ID for the dependant task. This field must be of type number.

Returns

None.

Related Links

SetTaskDependencyData
SetTaskDependencyURL
SetTaskDependencyParentID

SetTaskDependencyData

Syntax

```
SetTaskDependencyData({RecordName | &Rowset})
```

Description

Use the SetTaskDependencyData method to specify either a record, or an already instantiated rowset, that contains the dependency data.

Note: If you specify a rowset, the data in the rowset must be provided in the correct display order.

Parameters

RecordName* | *&Rowset	Specify the record or rowset that contains the task data. If you specify a record, you must prefix the record name with the keyword **Record.**

Returns

None.

Related Links

SetTaskData
SetTaskDependencyChildID
SetTaskDependencyURL

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SetTaskDependencyParentID

SetTaskDependencyParentID

Syntax

SetTaskDependencyParentID(*RecordName.FieldName*)

Description

The *depender* task is the task where the dependency arrow originates. Use the SetTaskDependencyParentID method to specify the field in the record that defines the task ID for the depender task.

The ID must match up to an ID in the Task data set.

This method is required if you specify dependency data.

Parameters

RecordName.FieldName Specify the field and its associated record that defines the task ID for the depender task. This field must be of type number.

Returns

None.

Related Links

SetTaskDependencyChildID
SetTaskDependencyData

SetTaskDependencyType

Syntax

SetTaskDependencyType(*RecordName.FieldName*)

Description

Use the SetTaskDependencyType method to specify the type of dependency relationship between predecessor and successor tasks.

The values for type are as follows:

Type	*Description*
Finish-to-Start	The arrow starts at the end of the predecessor task bar and ends at the start of the successor task bar. This is the default value

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Type	*Description*
Finish-to-Finish	The arrow starts at the end of the predecessor task bar and ends at the end of the successor task bar.
Start-to-Start	The arrow starts at the start of the predecessor task bar and ends at the start of the successor task bar.
Start-to-Finish	The arrow starts at the start of the predecessor task bar and ends at the end of the successor task bar.

Parameters

RecordName.FieldName Specify the field, and its associated record, that defines the type of dependencies between predecessor and successor tasks. This field must be of type integer, and one of the following values:

Value	*Description*
0 or any value greater than 3	Finish-to-Start
1	Finish-to-Finish
2	Start-to-Start
3	Start-to-Finish

Returns

None.

Related Links

SetTaskDependencyChildID
SetTaskDependencyData
SetTaskDependencyParentID

SetTaskDependencyURL

Syntax

`SetTaskDependencyURL``(`*`RecordName.FieldName`*`)`

Description

Use the SetTaskDependencyURL method to specify the field in the record that defines the URL the browser redirects to when the user clicks on a task bar.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

By default, the FieldChange event on the child ID field of the task dependency record is triggered if the image map based interactivity is turned on (using the IsDrillable property). This can be overridden by specifying a URL that is triggered when the task bar is clicked.

Use the SetTaskBarURL method to specify the URL to be used when the user clicks on a task bar in the chart section.

Parameters

RecordName.FieldName	Specify the field, and its associated record, that defines the URL the browser is redirected to when the dependency arrow is clicked. This field must be of type character. The URL must be an absolute URL.

Returns

None.

Related Links

SetTaskBarURL
SetTaskDependencyChildID
SetTaskDependencyData
SetTaskDependencyParentID

SetTaskDrill

Syntax

SetTaskDrill(*Recordname.FieldName*)

Description

Use the SetTaskDrill method to specify for which field PeopleCode FieldEdit and FieldChange events will execute when the user clicks the task bar.

The field can be any field that is loaded in the component buffer.

The system does not change the value in the field when the user clicks the field. Any changes or other processing for the field must be done within the PeopleCode program.

Parameters

RecordName.FieldName	Specify the record name and the field name of the field to be used for field change processing. The field must be available in the component buffer.

Returns

None.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SetTaskExpanded

Syntax

SetTaskExpanded((*RecordName.FieldName*)

Description

This method has been deprecated and is ignored.

SetTaskID

Syntax

SetTaskID(*RecordName.FieldName*)

Description

Use the SetTaskID method to specify the field that defines the unique task identifier. The task ID is used to support task linking and dependencies.

Note: The field must be of type number.

This method is required when you're creating a Gantt chart.

Parameters

RecordName.FieldName	Specify the record name and the field name of the field that defines the unique task identifier. **Note:** The field must be of type number.

Returns

None.

Related Links

SetTaskName

SetTaskLabel

Syntax

SetTaskLabel(*RecordName.FieldName*)

Description

Use the SetTaskLabel method to specify the field in the record that defines the task label. The label is displayed alongside its corresponding task bar in the chart area. If a task label is not provided, the task name is used instead. If a task name is not provided, the task id is used.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

RecordName.FieldName Specify the field, and its associated record, that contains the task label. This field must be of type character.

Returns

None.

Related Links

SetTaskID
SetTaskName

SetTaskLevel

Syntax

`SetTaskLevel``(`*`RecordName.FieldName`*`)`

Description

Use the SetTaskLevel method to specify the field in the record that defines the level for the task. The outermost summary tasks are always defined as task level one. Tasks with task levels greater than one are subtasks. Subtasks may also contain other subtasks.

If a field is not provided to define the level, all tasks are defined at level 1. A maximum of 32 levels are supported.

The following table shows an example of the different levels that could be used, as well as what the parent task level is.

Note: The parent task is not actually part of the data.

Task Name	*Task Level*	*Parent Level*
Phase I	1	None
Evaluation	2	Phase I
Research	3	Evaluation
Report Findings	3	Evaluation
Create Budget	2	Phase I
Approve Budget	3	Create Budget
Phase II	1	None
Code and Test	2	Phase II

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Task Name	*Task Level*	*Parent Level*
Phase III	1	None
Training	2	Phase III

Parameters

RecordName.FieldName Specify the field, and its associated record, that contains the information about the task level. This field must be of type number. Up to 32 levels are supported.

Returns

None.

Related Links

SetTaskID

SetTaskMilestone

Syntax

SetTaskMilestone(*RecordName.FieldName*)

Description

Use the SetTaskMilestone method to specify the field in the record that defines whether the task should be treated as a milestone.

The fields specified by the SetPlannedStartDate and SetActualStartDate methods are used for determining the dates for the planned and actual milestones. The other date fields in the rowset are ignored

Parameters

RecordName.FieldName Specify the field and its associated record that defines whether the task should be treated as a milestone. The field must be of type Character, and be one character long. The possible values for this field are Y, used to specify that this task is a milestone, or N, if not.

Returns

None.

Related Links

SetActualStartDate
SetTaskMilestone
SetPlannedStartDate

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SetTaskName

Syntax

SetTaskName(*RecordName.FieldName*)

Description

Use the SetTaskName method to specify the field in the record that defines the task name. If you do not specify a task name, the task ID is used in the table section of the Gantt chart.

Although this method is not required, Oracle recommends using it to display meaningful information in the table section of the Gantt chart.

Parameters

RecordName.FieldName	Specify the field name and its associated record that defines the task name. The field must be of type character.

Returns

None.

Related Links

SetTaskID

SetTaskProgress

Syntax

SetTaskProgress(*RecordName.FieldName*)

Description

Use the SetTaskProgress method to specify the field in the record that defines the length of the progress bar for this task as shown in the chart area of the Gantt chart.

The value in the field must be between 0 and 100, inclusive. Zero indicates no progress bar is shown, 100 indicates that the progress bar should cover the entire length of the task bar. Values greater than 100 are automatically converted to 100.

Parameters

RecordName.FieldName	Specify the field, and its associated record, that defines the length of the progress bar for this task. This field must be of type number. The value in the field must be between 0 and 100, inclusive. You must not specify a value greater than 100.

Returns

None.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

SetTaskProgressBarColor

SetTaskProgressBarColor

Syntax

SetTaskProgressBarColor(*RecordName.FieldName*)

Description

Use the SetTaskProgressBarColor method to specify the field in the record that defines the color for the progress bar.

For the progress bar to be visible, its color must contrast with the task bar color. No borders are drawn around the progress bar.

Parameters

RecordName.FieldName	Specify the field, and its associated record, that defines the task progress bar color. This field must be of type numeric, which means that you can only use the numeric value for the chart colors, not the constant.

Returns

None.

Related Links

SetActualTaskBarColor

SetTaskProgress

SetWBSNumbering

Syntax

SetWBSNumbering(*RecordName.FieldName*)

Description

Use the SetWBSNumbering method to specify the field in the record that defines the WBS numbering to be displayed for each task row in the table section of the Gantt chart.

A WBS is very similar in structure and layout to a document outline. Each item at a specific level of a WBS is numbered consecutively (that is, 10, 20, 30, 40, 50). Each item at the next level is numbered within the number of its parent item (that is, 10.1, 10.2, 10.3, 10.4). For example:

```
1.
   1.1
      1.1.1
      1.1.2
      1.1.3
   1.2
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
      1.2.1
      1.2.2
2.
. . .
```

If no field name is provided, WBS numbering is not displayed along with the tasks.

Regardless if WBS numbering is provided, child tasks are indented to the right of their parent task.

Parameters

RecordName.FieldName Specify the field name and its associated record that defines the WBS numbering to be displayed. The field must be of type character.

Returns

None.

SetYearFormat

Syntax

SetYearFormat(*Format*)

Description

Use the SetYearFormat method to specify the format of years on the time line axis.

Parameters

Format Specify the format of how the year should be displayed. Values are:

Value	*Description*
%Chart_YearFormat	Display the year in a numeric one- or two-digit format.
%Chart_YearFormat_2Digit	**Note:** This constant has been deprecated; if specified, it defaults to %Chart_YearFormat _4Digit.
%Chart_YearFormat_4Digit	Display the year in a numeric four-digit format. **Note:** This is the default format.

Returns

None.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

SetDayFormat

SetMonthFormat

Gantt Class Properties

These properties are used by the Gantt class. The properties are described in alphabetic order.

AxisEndDateTime

Description

Use this property to specify the date and time where the time line should end. The value must be of type Date or DateTime.

This property is read-write.

AxisStartDateTime

Description

Use this property to specify the date and time where the time line should begin. The value must be of type Date or DateTime.

This property is read-write.

DataStartRow

Description

This property has been deprecated and is ignored.

DataWidth

Description

This property has been deprecated and is ignored.

GridLines

Description

Use this property to specify whether to show grid lines with the chart.

Gantt charts only support the %ChartGrid_Vertical and %ChartGrid_None values.

Grid lines are shown within the chart section of the Gantt chart, if enabled, and are tied to the major tick mark. The major tick mark is associated with the smallest time increment displayed on the time line axis.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

For example, if both years and months are displayed on the time line axis, the major tick marks denote the months.

If you do not specify a value, no grid lines are shown (%ChartGrid_None).

This property controls only the display of grid lines. If you want to specify the style of the grid lines, use the GridLineType property.

The values are:

Numeric Value	*Constant Value*	*Description*
0	%ChartGrid_None	Don't show grid lines (default)
2	%ChartGrid_Vertical	Show vertical grid lines

This property is read-write.

Related Links

GridLineType

GridLineType

Description

Use this property to specify the style of the grid lines when vertical grid lines are turned on—that is, the GridLines property must be set to %ChartGrid_Vertical.

The default value is %ChartLine_Dash. The possible values are:

Numeric Value	*Value*	*Description*
0	%ChartLine_Solid	Draw grid lines with solid lines.
1	%ChartLine_Dash	Draw grid lines with lines composed of dashes (default).
2	%ChartLine_Dot	Draw grid lines with lines composed of dots.

This property is read-write.

Related Links

GridLines

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Height

Description

Use this property to specify the height of the chart. This property takes a numeric value. The unit of measurement is pixels.

You can use this property to overwrite the height set in Application Designer.

If you try to read this property before setting it, the value returned is zero.

This property is read-write.

ImageMap

Description

This property has been deprecated and is ignored.

InteractiveEnd

Description

Use this property to specify whether the user can change the end date of a task by dragging and dropping.

Note: Drag-and-drop is not supported on touch-friendly mobile devices such as an Apple iPad.

This property takes a Boolean value: True if the user can change the end date, False otherwise.

The default value of this property is False.

This property is read-write.

InteractiveMove

Description

Use this property to specify whether the user can move a task bar by dragging and dropping.

Note: Drag-and-drop is not supported on an Apple iPad.

This property takes a Boolean value: True if the user can move the bar, False otherwise.

The default value of this property is False.

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

InteractiveProgress

Description

Use this property to specify whether the user can change the progress value of a task by dragging and dropping.

Note: Drag-and-drop is not supported on an Apple iPad.

This property takes a Boolean value: True if the user can change the progress value, False otherwise.

The default value of this property is False.

This property is read-write.

InteractiveStart

Description

Use this property to specify whether the user can change the start date of a task by dragging and dropping.

Note: Drag-and-drop is not supported on an Apple iPad.

This property takes a Boolean value: True if the user can change the start date, False otherwise.

The default value of this property is False.

This property is read-write.

IsDrillable

Description

The IsDrillable property is used with the task bars as well as the task dependency lines in the chart section of a Gantt chart. Where the user is directed depends on whether a URL is provided or not, as detailed in this table:

User Action	***If URL is not provided:***	***If URL is provided:***
Clicks a task bar.	FieldChange event is associated with the field that is set with SetTaskDrill.	Redirects to URL provided by field identified using the SetTaskBarURL method.
Clicks a task dependency line.	FieldChange event is associated with the Child ID field in the Task Dependency table.	Redirects to URL provided by field identified using the SetTaskDependencyURL method.

This property takes a Boolean value: True if the end-user can click the chart to initiate an action, and False otherwise.

The default value for this property is False.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-write.

IsPlainImage

Description

This property has been deprecated and is ignored.

PixelsPerRow

Description

Use this property to set or return the row height for each row in the Gantt chart as Number value representing pixels. The default value is 25 pixels.

This property is read-write.

RevertToPre850

Description

This property has been deprecated and is ignored.

ShowTaskLabels

Description

Use this property to specify whether or not task labels are displayed alongside the corresponding task bar in the chart area. This property takes a boolean value; true to display the labels, false to not display the labels. The default is to display the labels.

This property is read-write.

Style

Description

Use this property to specify the style class that defines the overall appearance attributes of the chart . The value must be a valid style class within the style sheet specified for the chart.

This property is read-write.

Related Links

Styling PeopleSoft Charts

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

StyleSheet

Description

This property has been deprecated and is ignored.

Related Links

Styling PeopleSoft Charts

TaskDependencyLineType

Description

Use this property to specify an integer value that specifies the line type of the line connecting dependent tasks. This value affects all the dependency lines for the entire Gantt chart, not just for a specific set of tasks.

This property is read-write.

See Styling PeopleSoft Charts.

Numeric Value	*Constant Value*	*Description*
0	%ChartLine_Solid	Solid line
1	%ChartLine_Dashed	Dashed line
2	%ChartLine_Dotted	Dotted line
3	%ChartLine_Mixed	Mixture of dashes and dots

TaskMilestoneGlyph

Description

Use this property of type integer to specify which field in the record defines the glyph to represent a task milestone (for both planned and actual milestones). This glyph is used for the entire chart, not just for a specific task.

By default a diamond shaped glyph will be used.

Milestones associated with planned dates use colors defined by the SetPlannedTaskBarColor method. Milestones associated with actual dates use colors defined by the SetActualTaskBarColor method.

This property is read-write.

Related Links

Using Gantt Glyphs

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

TaskTitle

Description

Use this property to specify the column title to be displayed in column one (that is, the left-most column) in the table section of the Gantt chart. Use the SetTaskAppDataTitles method to specify the column titles for the application specific data fields (that is, column two and beyond).

This property is read-write.

Related Links

SetTaskAppDataTitles

Width

Description

Use this property to specify the width of the chart. This property takes a numeric value. The unit of measurement is pixels.

Generally this property is used with charts created for iScripts, to specify the width of the image, before generating the image map. You can also use it to overwrite the width set in Application Designer.

If you try to read this property before setting it, the value returned is zero.

This property is read-write.

OrgChart Class Methods

These methods are used by the OrgChart class. The methods are described in alphabetic order.

SetCrumbData

Syntax

SetCrumbData(*&Rowset*)

Description

Use the SetCrumbData method to specify the source for the data for the organization chart breadcrumbs. Use an already instantiated and populated level-1 component rowset that contains the breadcrumb data.

Parameters

&Rowset	A level-1 rowset populated with the breadcrumbs data.

Returns

None.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SetCrumbRecord

Syntax

SetCrumbRecord(**Record.***Record_Name*)

Description

Use the SetCrumbRecord method to specify the derived/working record name that contains the information about the breadcrumbs.

The breadcrumb record is an application-specific derived/work record created using a clone of the PTORGCRMB_SBR subrecord definition.

Parameters

Record.*Record_Name*	Specify the name of the derived/work record that contains the data for the breadcrumbs. You must include the **Record** keyword.

Returns

None.

SetDropdownData

Syntax

SetDropdownData (*&Rowset*)

Description

Use the SetDropdownData method to specify the source for the data for the organization chart drop-down menus/lists. Use an already instantiated and populated level-1 component rowset that contains the drop-down list data.

Parameters

&Rowset	A level-1 rowset populated with the drop-down list data.

Returns

None

SetDropdownRecord

Syntax

SetDropDownRecord(**Record**.*RecordName*)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the SetDropdownRecord method to specify the derived/working record name that contains the information about the dropdown menus/lists.

The dropdown record is an application-specific derived/work record created using a clone of the PTORGBOXLST_SBR subrecord definition.

Parameters

Record_Name Specify the name of the derived/work record that contains the data for the drop down lists.

You must include the **Record** keyword.

Returns

None

SetIMData

Syntax

SetIMData (*&rsRowset*)

Description

Use the SetIMData method to specify the source for the IM data for the organization chart. Use a standalone rowset that contains the IM data.

This method is required for an organization chart that implements IM presence.

Parameters

&rsRowset A standalone rowset populated with the node display data. This rowset references the IM record of the organization chart.

Returns

None.

SetIMRecord

Syntax

SetIMRecord(**Record**.*Record_Name*)

Description

Use the SetIMRecord method to specify the IM data record.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The IM data record is an application-specific derived/work record created using a clone of the PTORGIM_SBR subrecord definition.

This method is required for an organization chart that implements IM presence.

Parameters

Record.*Record_Name*	Specify the name of the derived/work record that contains the IM data for the organization chart. You must include the Record keyword.

Returns

None.

SetLegend

Syntax

SetLegend(*&Array_of_String*)

Description

Use the SetLegend method to specify legend text. Legend text labels the images set using SetLegendImg.

If you do not specify an element for an array (that is, a blank or a null) then no legend is listed for that node.

Note: Legend text is not automatically translated. If you set your own labels, be sure to use translated text, such as message catalog entries.

Parameters

&Array_of_String	Specify an already instantiated array of string, containing the text that you want to use for the legend.

Returns

None.

Example

```
&LegendArray = CreateArray("A", "B", C", "D ");
&ocOrgChart.SetLegend (&LegendArray);
```

Related Links

SetDataSeries

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SetLegendImg

Syntax

SetLegendImg(*&Array_of_String*)

Description

Use the SetLegendImg method to specify the legend image names.

Parameters

&Array_of_String	An already instantiated array containing the names of the images that you want to use with the legend.

Returns

None.

SetNodeData

Syntax

SetNodeData(*&Rowset*)

Description

Use the SetNodeData method to specify the source for the node data for the organization chart. Use an already instantiated and populated level-1 component rowset that contains the node data.

This is a required method to build an organization chart.

If you make a change to the underlying data of a chart, call the SetNodeData method again to update the chart.

Parameters

&Rowset	A level-1 component rowset populated with the node data. This rowset references the node record of the chart.

Returns

None.

SetNodeDisplayDataRecord

Syntax

SetNodeDisplayDataRecord(**Record**.*Record_Name*)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the SetNodeDisplayDataRecord method to specify the node display record.

The node display record is an application-specific derived/work record created using a clone of the PTNODE_DISP_SBR subrecord definition.

This method is required for an organization chart that implements node display templates.

Parameters

Record.*Record_Name*	Specify the name of the derived/work record that contains the node display data for the organization chart. You must include the Record keyword.

Returns

None.

SetNodeDisplayData

Syntax

SetNodeDisplayData(*&rsRowset*)

Description

Use the SetNodeDisplayData method to specify the source for the node display data for the organization chart. Use an already instantiated and populated level-1 standalone rowset that contains the node display data.

This method is required for an organization chart that implements node display templates.

If you make a change to the node display data of a chart, call the SetNodeDisplayData method again to update the chart.

Parameters

&rsRowset	A level-1 component rowset populated with the node display data. This rowset references the node display record of the organization chart.

Returns

None.

SetNodeRecord

Syntax

SetNodeRecord(**Record.***Record_Name*)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the SetNodeRecord method to specify the organization node record.

The node record is an application-specific derived/work record created using a clone of the PTORGNODE_SBR subrecord definition.

This method is required to build an organization chart.

Parameters

Record.*Record_Name*	Specify the name of the derived/work record that contains the data for the organization node. You must include the **Record** keyword.

Returns

None.

SetNodeViewEntries

Syntax

`SetNodeViewEntries``(`*`&NodeViewArray`*`)`

Description

Use this method to specify the array of string representing the node view IDs.

Parameters

&NodeViewArray	Specifies an array of string representing the node view IDs.

Returns

None.

Example

```
&OrgChart.SetNodeViewEntries(&NodeViewArray);
&OrgChart.SetNodeViewText(&DataHintArray);

&OrgChart.InitialView="VIEW1";
```

Related Links

SetNodeViewText
InitialView
Implementing Node Views (Optional)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SetNodeViewText

Syntax

SetNodeViewText(*&DataHintArray*)

Description

Use this method to specify the array of string representing the data hint (mouse-over text) for each node view.

Parameters

&DataHintArray	Specifies an array of string representing the data hint (mouse-over text) for each node view.

Returns

None.

Example

```
&OrgChart.SetNodeViewEntries(&NodeViewArray);
&OrgChart.SetNodeViewText(&DataHintArray);

&OrgChart.InitialView="VIEW1";
```

Related Links

SetNodeViewEntries

Implementing Node Views (Optional)

SetPopUpNodeData

Syntax

SetPopUpNodeData(*&Rowset*)

Description

Use the SetPopUpNodeData method to specify the source for the pop-up node data for the organization chart. Use an already instantiated and populated level-1 component rowset that contains the pop-up node data.

This method is not required if no pop-up chart is available to be displayed in the organization chart.

If you make a change to the underlying data of a pop-up chart, call the SetPopUpNodeData method again to update the chart.

Parameters

&Rowset	A level-1 rowset populated with the pop-up node data. This rowset references the pop-up node record of the chart.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

None.

SetPopUpNodeRecord

Syntax

SetPopUpNodeRecord(**Record.***Record_Name*)

Description

Use the SetNodeRecord method to specify the pop-up node record.

The node record is an application-specific derived/work record created using a clone of the PTORGPOPUP_SBR subrecord definition.

This method is not required if no pop-up chart is available to be displayed in the organization chart.

Parameters

Record.*Record_Name*	Specify the name of the derived/work record that contains the data for the pop-up node. You must include the **Record** keyword.

Returns

None.

SetSchemaLevels

Syntax

SetSchemaLevels(*&Array*) ;

Description

Use this method to specify the schema levels for an organization chart. Use an array of instantiated SchemalLevel instances. The size of the array is the total number of the schemas defined for this organization chart.

Parameters

&Array	An array of instantiated SchemalLevel instances.

Returns

None.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

```
SchemaLevel &oSchemaLevel1 = Createobject("SchemaLevel");
SchemaLevel &oSchemaLevel2 = Createobject("SchemaLevel");
SchemaLevel &oSchemaLevel3 = Createobject("SchemaLevel");
SchemaLevel &oSchemaLevel4 = Createobject("SchemaLevel");

/***     Create an instance of of schema zoom level 1 class and instantiate it ***/
SchemaLevel &oSchemaLevel1 =Createobject("SchemaLevel");
&oSchemaLevel1.ID=1;
& oSchemaLevel1.ImageHeight=0;
.... (add code to instantiate &oSchemaLevel1, &oSchemaLevel2,
      &oSchemaLevel3, &oSchemaLevel4 instances).
&SchemaLevels=CreateArray(&oSchemaLevel1, &oSchemaLevel2, &oSchemaLevel3, &oSchemaL⇒
evel4)
&ocOrgChart.SetZoomSchemaLevels(&SchemaLevls)
```

Related Links

SchemaLevel Class Properties

OrgChart Class Properties

These properties are used by the OrgChart class. The properties are described in alphabetic order.

CenterFocusNode

Description

Specify whether the node with focus displays centered in the chart area.

Value	*Direction*
0	Center the focus node
2	Do not center the focus node

The focus node is not centered if the chart fits in the chart area without a horiztonal scroll, even if CenterFocusNode = 0.

The focus node is not centered if any pop-ups are opened. The display of pop-ups in the visible chart area takes priority over focus node centering.

Note: If multiple pop-ups are opened, the last popup opened is not necessarily set to the visible area. This is determined by the position of the pop-up in the rowset.

The default is 0.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ChartCurrentSchemaLevel

Description

Set this property to specify the initial schema zoom level.

Valid values are 1 to the number of total schema instances set in the PeopleCode for the organization chart.

When a user selects a different schema level using the zoom control the systems sets the value in the PTCHART_SCHEMA_ID field to the new schema value and sets the value in the CurrentSchemaLevel property to the new schema value, then displays the chart using the new schema level.

If this property is changed to a new value by PeopleCode, the chart is displayed with the new schema level view.

The default value is 1.

Related Links

Implementing Zoom Schemas (Optional)

ChartScrollType

Description

Specify whether to use scroll bars or alternative scrolling to move the chart within the visible chart area.

Value	*Direction*
0	Use scroll bars
1	Use alternative scrolling. This allows the user to use the scroll navigator or to grab the surface of the organization chart background to move the chart in any direction.

Note: To use the mouse hand feature, the chart background color must be specified in the PSORGCHART style sheet. By default, the background color is white.

Note: On an Apple iPad a user navigates using a finger on a touch screen, so scroll bars, the scroll navigator, and mouse hand features are not displayed on an Apple iPad. For an Apple iPad the behavior is the same for both ChartScrollType= 1 and ChartScrollType = 0.

This property takes an integer value.

The default is 0.

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Collapsed_Msg

Description

Specify the data hint for the collapsed icon image.

An error message is issued if Collapsed_Msg is set but CollapsedImage is not set.

The default is “Expand”.

This property is read-write.

CollapsedImage

Description

Specify a string value for the name of the image that represents a collapsed node. When a user clicks on the collapsed image, the node will be *expanded.*

If the CollapsedImage and ExpandedImage properties are not specified, then no expanded/collapsed icon appears on the node and the expand/collapse actions are disabled.

This property is read-write.

Example

```
&ocOrgChart.CollapsedImage ="PT_COLLAPSED_NODE";
```

CollapseMainIconSpace

Description

Specify whether to reduce the space at the top of the node reserved for the main icon. This property is ignored for charts that use a display template.

See “Using Node Display Templates” in Designing Organization Chart Nodes.

Value	***Direction***
0	Reserve space at the top of the node for the main icon.
1	Reduce the space at the top of the node reserved for the main icon.

This property takes an integer value.

The default is 0.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

CrumbDescrStyle

Description

Use this property to specify the style class name that will be used to control the style of linkable breadcrumbs.

The default style class is PT_ORGCHART_BRDCRM.

Oracle recommends that you use the default breadcrumb style.

This property is read-write.

CrumbMaxDisplayLength

Description

Use this property to set the maximum description length that will appear for the breadcrumb.

A breadcrumb description has a maximum of 50 characters in length. If CrumbMaxDisplayLength is set to 30, then only the first 30 characters of the description appear and an ellipsis (“…”) is appended.

On mouse-over, the whole text of the breadcrumb appears.

The default is to show the full description.

This property takes a number value.

This property is read-write.

CrumbSeparatorImage

Description

Use this property to specify the image name for the image that appears between breadcrumb entries.

If this property is not set, then no image appears between breadcrumb entries. Instead, breadcrumb entries are separated by three spaces.

This property takes a string value.

This property is read-write.

DefaultImage

Description

Use this property to set the default image name for the image that will appear if ImageLocation is not 0 and no image is set in the work record.

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Direction

Description

Use this property to specify organization chart orientation.

Value	*Orientation*
0	Horizontal
2	Vertical

The default is 2 (vertical).

This property is read-write.

DropDownBoxStyle

Description

This property is retained for backward compatibility. PeopleTools version 8.52 and later do not use this property.

Specify the style for the drop-down list box header for the organization chart.

Value	*Description*
PT_ACTION_POSITION	The button appears to left, aligned with the other descriptors.
PT_ACTION_POSITION_RIGHT	The button appears to right.
PT_ACTION_POSITION_CENTER	The button appears in the center of the node.

The default style class is PT_ACTION_POSITION.

This property is read-write.

Expanded_Msg

Description

Specify the data hint for the expanded icon image.

An error message is issued if Expanded_Msg is set but ExpandedImage is not set.

The default is “Collapse”.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ExpandedImage

Description

Specify a string value for the name of the image that represents an expanded node. When a user clicks on the expanded image, the node will be *collapsed.*

If the CollapsedImage and ExpandedImage properties are not specified, then no expanded/collapsed icon appears on the node and the expand/collapse actions are disabled.

This property is read-write.

Example

```
&ocOrgChart.ExpandedImage ="PT_EXPANDED_NODE";
```

FocusNodeStyle

Description

Use this property to specify the style class name that will be used to control the focus node.

The default style class is PT_ORGNODE_SELECT.

This property is read-write.

HasLegend

Description

Use this property to specify if a legend appears with the chart. This property takes a Boolean value: True if the legend appears with the chart, and False otherwise.

The default value is False.

This property is read-write.

Height

Description

Use this property to specify the height of the chart. This property takes a numeric value. The unit of measurement is pixels.

If you try to read this property before setting it, the value returned is 0.

This property is read-write.

Related Links

Height

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ImageHeight

Description

Use this property to specify the height of the node image. This property takes a numeric value. The unit of measurement is pixels.

Note: If ImageHeight is very large relative to the chart, data hints may not have room to display properly. If this occurs, you need to reduce ImageHeight or increase chart size.

The default is 0.

This property is read-write.

Related Links

Height

ImageLocation

Description

Use this property to specify chart node image location:

Value	*Direction*
0	No image
1	Image on the left
2	Image on the right

The default is 0 (No image).

This property is read-write.

ImageMouseoverMagnificationFactor

Description

Use this property to specify the mouse-over magnification factor on the node image. This property takes a numeric value. A value of 100 produces a mouse-over image the same size as the node image. If the value is set to 0 or 100, no image magnification will occur.

Note: ImageMouseoverMagnificationFactor is ignored on the Apple iPad. On an Apple iPad the user is able to zoom the entire page to enlarge the image.

Valid values are 0 to 1000.

The default is 0.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-write.

Related Links

Height

IMPresence

Description

The IMPresence property indicates whether the organziation chart should display IM presence data.

Valid values are ‘True’ and ‘False’.

True – the organization chart contains IM presence data and displays IM presence icons.

False – the organization chart does not display IM presence icons.

The default value is ‘False’.

This property is read-write.

IMRefreshInterval

Description

The IMRefreshInterval property sets the interval, in seconds, for polling for IM status.

This property takes an integer value.

The default is 60 seconds.

This property is read-write.

InitialView

Description

Use this property to set or return the initial node view ID as a string.

This property is read-write.

Example

```
&OrgChart.InitialView="VIEW1";
```

Related Links

SetNodeViewEntries
Implementing Zoom Schemas (Optional)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

LegendPosition

Description

The OrgChart class only supports %ChartLegend_Top, which is to display the legend on top of the chart.

This property is read-write.

LegendStyle

Description

Use this property to specify the style of the legend. The values for this property are the style classes contained in the style sheet associated with the chart.

The values for this property are controlled by the specified style class in the style sheet associated with the chart.

The default style class is PT_ORGCHART_LEGEND.

This property is read-write.

Related Links

Styling PeopleSoft Charts

LegendTopSpace

Description

Use this property to set the space between the breadcrumb and legend.

The default is no space between the legend and the breadcrumbs.

This property is read-write.

Related Links

Styling PeopleSoft Charts

MainTitle

Description

Use this property to specify the text for the main title of the chart.

This property takes a string value.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

MainTitleStyle

Description

Use this property to specify the style of the main title. The values for this property are the style classes contained in the style sheet associated with the chart.

The values for this property are controlled by the specified style class in the style sheet associated with the chart.

The default value is “PT_ORGCHART_TITLE”.

This property is read-write.

MaxDropdownDisplayItem

Description

Specify the maximum number of list items that will appear in the drop down box before the up-and-down arrow vertical scrolling is implemented.

This property is retained for backward compatibility. PeopleTools version 8.52 and later charts do not use this property.

This property takes an integer value.

The default value is 7.

This property is read-write.

MaxPopupDisplayNode

Description

The maximum number of nodes to be displayed in the pop-up before a vertical scrollbar appears in the pop-up.

For instance, if MaxPopupDisplayNode is set to 3 and the pop-up has more than 3 nodes, then the pop-up will only display the first 3 nodes with a scrollbar in the pop-up so the user can scroll down to see the other nodes.

The default value is 3.

This property is read-write.

NodeDescr1Style

Description

The style class name that will be used to control the style of the main chart node descriptor number 1.

NodeDescr*n*Style properties are ignored with charts that use a node display template. Instead, use the PT_CNT_STYLE field in the display template.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Each node can have up to seven descriptors, each with its own style.

The values for this property are controlled by the specified style class in the style sheet associated with the chart.

The default style class is PT_ORGNODE_DESC1.

This property is read-write.

NodeDescr2Style

Description

The style class name that will be used to control the style of the main chart node descriptor number 2.

NodeDescr*n*Style properties are ignored with charts that use a node display template. Instead, use the PT_CNT_STYLE field in the display template.

Each node can have up to seven descriptors, each with its own style.

The values for this property are controlled by the specified style class in the style sheet associated with the chart.

The default style class is PT_ORGNODE_DESC2.

This property is read-write.

NodeDescr3Style

Description

The style class name that will be used to control the style of the main chart node descriptor number 3.

NodeDescr*n*Style properties are ignored with charts that use a node display template. Instead, use the PT_CNT_STYLE field in the display template.

Each node can have up to seven descriptors, each with its own style.

The values for this property are controlled by the specified style class in the style sheet associated with the chart.

The default style class is PT_ORGNODE_DESC3.

This property is read-write.

NodeDescr4Style

Description

The style class name that will be used to control the style of the main chart node descriptor number 4.

NodeDescr*n*Style properties are ignored with charts that use a node display template. Instead, use the PT_CNT_STYLE field in the display template.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Each node can have up to seven descriptors, each with its own style.

The values for this property are controlled by the specified style class in the style sheet associated with the chart.

The default style class is PT_ORGNODE_DESC4.

This property is read-write.

NodeDescr5Style

Description

The style class name that will be used to control the style of the main chart node descriptor number 5.

NodeDescr*n*Style properties are ignored with charts that use a node display template. Instead, use the PT_CNT_STYLE field in the display template.

Each node can have up to seven descriptors, each with its own style.

The values for this property are controlled by the specified style class in the style sheet associated with the chart.

The default style class is PT_ORGNODE_DESC5.

This property is read-write.

NodeDescr6Style

Description

The style class name that will be used to control the style of the main chart node descriptor number 6.

NodeDescr*n*Style properties are ignored with charts that use a node display template. Instead, use the PT_CNT_STYLE field in the display template.

Each node can have up to seven descriptors, each with its own style.

The values for this property are controlled by the specified style class in the style sheet associated with the chart.

The default style class is PT_ORGNODE_DESC6.

This property is read-write.

NodeDescr7Style

Description

The style class name that will be used to control the style of the main chart node descriptor number 7.

NodeDescr*n*Style properties are ignored with charts that use a node display template. Instead, use the PT_CNT_STYLE field in the display template.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Each node can have up to seven descriptors, each with its own style.

The values for this property are controlled by the specified style class in the style sheet associated with the chart.

The default style class is PT_ORGNODE_DESC7.

This property is read-write.

NodeMaxDisplayDescLength

Description

Set the maximum descriptor length that will appear in the node.

This property is ignored on charts that use a display template. Instead use the PT_DESCR_MAX display template field to limit descriptor length.

If the full descriptor text is longer than NodeMaxDisplayDescLength, then an ellipsis ("…") is appended to the displayed text. The entire text appears in a data hint.

The default value is 50 characters.

This property is read-write.

NodeProportion

Description

Use the NodeProportion property to control whether nodes can have varying sizes or are sized uniformly.

Value	*Direction*
0	Node size is variable, based on the content of each node.
1	Node height is uniform, based on the tallest node.
2	Node width is uniform, based on the widest node.
3	Node height and width are uniform.
4	Nodes are square, based on the largest node height or width.

This property takes an integer value.

The default is 0.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

OptimizeHorizontalSpace

Description

Set this property to automatically maximize or minimize the chart area horizontally.

Value	*Direction*
0	Use the specified size.
1	Expand horizontally to the right edge of the browser page. This option should only be used when there is only blank space to the right of the chart. Otherwise, any objects in that area will be pushed off the viewable area.
2	Contract horizontally to just to the right of the node furthest to the right.
3	Fit the chart area to the chart horizontally.

This property takes an integer value.

The default is 0.

This property is read-write.

OptimizeVerticalSpace

Description

Set this property to automatically maximize or minimize the chart area vertically.

Value	*Direction*
0	Use the specified size.
1	Expand vertically to the bottom edge of the browser page. This option should only be used when there is only blank space at the bottom of the chart. Otherwise, any objects in that area will be pushed off the viewable area.
2	Contract vertically to just below the bottom of the last visible chart node.
3	Fit the chart area to the chart vertically.

This property takes an integer value.

The default is 0.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-write.

PopupHeaderStyle

Description

The style class that will be used to control the style of the pop-up header and the header descriptor.

The values for this property are controlled by the specified style class in the style sheet associated with the chart.

The default style class is PT_POPUPNODE_HEADER.

This property is read-write.

PopupNodeDescr1Style

Description

The style class name that will be used to control the style of the pop-up node descriptor number 1.

Each node can have up to eight descriptors, each with its own style.

The values for this property are controlled by the specified style class in the style sheet associated with the chart.

The default style class is PT_POPUPNODE_DESC1.

This property is read-write.

PopupNodeDescr2Style

Description

The style class name that will be used to control the style of the pop-up node descriptor number 2.

Each node can have up to eight descriptors, each with its own style.

The values for this property are controlled by the specified style class in the style sheet associated with the chart.

The default style class is PT_POPUPNODE_DESC2.

This property is read-write.

PopupNodeDescr3Style

Description

The style class name that will be used to control the style of the pop-up node descriptor number 3.

Each node can have up to eight descriptors, each with its own style.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The values for this property are controlled by the specified style class in the style sheet associated with the chart.

The default style class is PT_POPUPNODE_DESC3.

This property is read-write.

PopupNodeDescr4Style

Description

The style class name that will be used to control the style of the pop-up node descriptor number 4.

Each node can have up to eight descriptors, each with its own style.

The values for this property are controlled by the specified style class in the style sheet associated with the chart.

The default style class is PT_POPUPNODE_DESC4.

This property is read-write.

PopupNodeDescr5Style

Description

The style class name that will be used to control the style of the pop-up node descriptor number 5.

Each node can have up to eight descriptors, each with its own style.

The values for this property are controlled by the specified style class in the style sheet associated with the chart.

The default style class is PT_POPUPNODE_DESC5.

This property is read-write.

PopupNodeDescr6Style

Description

The style class name that will be used to control the style of the pop-up node descriptor number 6.

Each node can have up to eight descriptors, each with its own style.

The values for this property are controlled by the specified style class in the style sheet associated with the chart.

The default style class is PT_POPUPNODE_DESC6.

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

PopupNodeDescr7Style

Description

The style class name that will be used to control the style of the pop-up node descriptor number 7.

Each node can have up to eight descriptors, each with its own style.

The values for this property are controlled by the specified style class in the style sheet associated with the chart.

The default style class is PT_POPUPNODE_DESC7.

This property is read-write.

PopupNodeDescr8Style

Description

The style class name that will be used to control the style of the pop-up node descriptor number 8.

Each node can have up to eight descriptors, each with its own style.

The values for this property are controlled by the specified style class in the style sheet associated with the chart.

The default style class is PT_POPUPNODE_DESC8.

This property is read-write.

Style

Description

Use this property to specify the style class that defines the overall appearance attributes of the chart . The value must be a valid style class within the style sheet specified for the chart.

This property is read-write.

Related Links

Styling PeopleSoft Charts

SuppressPeopleCodeOnNode

Description

Specify whether to suppress processing, such as re-centering the chart, when a user clicks on a chart node if no PeopleCode is associated with the node.

This property takes a Boolean value: True to suppress a click on a chart node, and False otherwise.

The default value is False.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-write.

SuppressPeopleCodeOnImage

Description

Specify whether to suppress a processing, such as re-centering the chart, when a user clicks on a chart image if no PeopleCode is associated with the image.

This property takes a Boolean value: True to suppress a click on a chart image, and False otherwise.

The default value is False.

This property is read-write.

UnlinkCrumbDescrStyle

Description

Use this property to specify the style class name that will be used to control the style of the unlinkable breadcrumb.

The values for this property are controlled by the specified style class in the style sheet associated with the chart.

The default style class is PT_ORGCHART_UNLINK_BRDCRM.

Oracle recommends that you use the default breadcrumb unlinkable style.

This property is read-write.

VerticalSpace

Description

Use this property to specify the amount of space above the first level of nodes in an organization chart. If the chart has a legend, the vertical space is measured as the distance from the top of the first level of nodes to the bottom of the legend. If the chart has no legend, the vertical space is the distance from the top of the first level of nodes to the top of the chart area.

This property only applies to charts with a vertical orientation (Direction = 2).

This property takes a numeric value. The unit of measurement is pixels.

The default value is 10 pixels.

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Width

Description

Use this property to specify the width of the chart. This property takes a numeric value. The unit of measurement is pixels.

If you try to read this property before setting it, the value returned is 0.

This property is read-write.

SchemaLevel Class Properties

These properties are used by the SchemaLevel class. The properties are described in alphabetic order.

ID

Description

Use this property to specify the ID for the schema level.

Specify a number from 1 – *n*, where *n* is the number of schema levels defined for the chart. *n* must be in the range 1 – 10.

This property is read-write.

ImageHeight

Description

Use this property to specify the the height of the node image (photo) displayedfor the schema level.

Specify the height of the node image (photo) displayed, in pixels, for this schema level.

This property is read-write.

RatingBoxChart Class Methods

These methods are used by the RatingBoxChart class. The methods are described in alphabetic order.

SetLegend

Syntax

SetLegend(*&Array_of_String*)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the SetLegend method to specify legend text. Legend text labels the images set in the RatingBoxChart class method SetLegendImg.

Note: Legend text is not automatically translated. Be sure to use translated text, such as message catalog entries.

Parameters

&Array_of_String	Specify an already instantiated array of string, containing the text that you want to use for the legend.

Returns

None.

Example

```
&LegendArray = CreateArray("A","B", C","D");
&oRatingBoxChart.SetLegend(&LegendArray);
```

Related Links

SetDataSeries

SetLegendImg

SetLegendImg

Syntax

SetLegendImg(*&Array_of_String*)

Description

Use the SetLegendImg method to specify the legend image names.

Parameters

&Array_of_String	An already instantiated array containing the names of the images that you want to use with the legend.

Returns

None.

SetQuadrantSchemas

Syntax

SetQuadrantSchemas(*&Quadrant_Array*)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the SetQuadrantSchemas method to specify an array of QuadrantSchema objects to be used with this rating box chart.

Not all quadrants within the rating box chart require a QuadrantSchema object. Moreover, the QuadrantSchema objects in the array can be specified in any order.

Parameters

&Quadrant_Array	An already instantiated array of QuadrantSchema objects.

Returns

None.

Example

```
&QuadrantSchemas = CreateArray(&q_schema1, &q_schema2, &q_schema3, &q_schema4, &q_s⇒
chema5, &q_schema6);

&oRatingBoxChart.SetQuadrantSchemas(&QuadrantSchemas);
```

Related Links

Using the QuadrantSchema Class

QuadrantSchema Class Properties

SetRBNodeData

Syntax

SetRBNodeData(*&Rowset*)

Description

Use the SetRBNodeData method to specify the level 1 component rowset that is the source for the node data for the rating box chart.

If you make a change to the underlying data of a chart, call the SetRBNodeData method again to update the chart.

Parameters

&Rowset	An already instantiated and populated component rowset object that references the rating chart node record.

Returns

None.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SetRBNodeRecord

Syntax

SetRBNodeRecord(**Record.***RecordName*)

Description

Use the SetRBNodeRecord method to specify the record that is to contain the node data for the rating box chart.

Parameters

Record.*RecordName*	Specify the name of the record to be used as the node record.

Returns

None.

SetXAxisLabels

Syntax

SetXAxisLabels(*&Array_of_String*)

Description

Use the SetXAxisLabels method to specify an array of labels for the x-axis.

Note: The labels will not be displayed if the ShowAxisLabels property is explicitly set to False.

Parameters

&Array_of_String	Specify an already instantiated array of string that contain the labels that you want to use for the x-axis. The array size must match the value in the XAxisBoxNum property. If they do not match, the system throws a runtime error.

Returns

None.

Related Links

ShowAxisLabels

SetYAxisLabels

Syntax

SetYAxisLabels(*&Array_of_String*)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the SetYAxisLabels method to specify an array of labels for the y-axis.

Note: The labels will not be displayed if the ShowAxisLabels property is explicitly set to False.

Parameters

&Array_of_String	Specify an already instantiated array of string that contain the labels that you want to use for the y-axis. The array size must match the value in the YAxisBoxNum property. If they do not match, the system throws a runtime error.

Returns

None.

Related Links

ShowAxisLabels

RatingBoxChart Class Properties

These properties are used by the RatingBoxChart class. The properties are described in alphabetic order.

BoxMaxDisplayItems

Description

Specify how many nodes are to be shown in the displayable area of the quadrant. When the number of nodes to be shown exceeds BoxMaxDisplayItems, a link labeled “View all (N)” appears at the bottom right of the quadrant, where *N* is the total number of nodes in the quadrant. The user can click the link to launch a pop-up that contains all the nodes. A scrollbar enables the user to scroll through all the nodes in the list.

Only one pop-up window will appear in the rating box chart, so when the user clicks another “View all (*N*)” link in another quadrant, the previous pop-up window closes and the new pop-up window opens at the center of the quadrant.

If an invalid (negative) value is specified, an error will be thrown at runtime.

The default value is 1.

This property is read-write.

DraggedNodeStyle

Description

Use this property to specify the style class that controls the appearance of a node as it is being dragged.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The values for this property are controlled by the specified style class in the style sheet associated with the chart.

The default style class is PT_RATBOX_DRAGGED_NODE.

This property is read-write.

Related Links

Styling PeopleSoft Charts

EnableRelatedActions

Description

Specify a Boolean value indicating whether a user can click on a node in the rating box chart to invoke related actions on the node. The default value is False.

To enable related actions on a rating box chart, you must do the following:

- Set the IsDragable property to False.
- Set the EnableRelatedActions property to True.
- Use the Manage Related Content Service component to configure related actions on the PTCHART_NODE page field of the page displaying the rating box chart.

Related Links

IsDragable

"Managing Related Content for Content References" (PeopleTools 8.54: Portal Technology)

GridLineType

Description

Use this property to specify the style of the grid lines.

The default value is %ChartLine_Solid. The possible values are:

Value	*Description*
%ChartLine_Solid	Draw grid lines with solid lines.
%ChartLine_Dash	Draw grid lines with lines composed of dashes.
%ChartLine_Dot	Draw grid lines with lines composed of dots.

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

HasLegend

Description

Use this property to specify if a legend appears with the chart. This property takes a Boolean value: True if the legend appears with the chart, and False otherwise.

The default value is False.

This property is read-write.

Height

Description

Use this property to specify the height of the chart. This property takes a numeric value. The unit of measurement is pixels.

The default value is the height of the chart control on the page definition.

If you set a chart height value that cannot fit the x-axis and label areas of the chart, a runtime error is thrown and the chart is not rendered.

If you set a negative value, a runtime error is thrown and the chart is not rendered.

If you try to read this property before setting it, the value returned is 0.

This property is read-write.

Related Links

Height

IconOnlySelectedQuadrantStyle

Description

Use this property to specify the style class that controls the appearance of border properties of the selected quadrant of an icon-only rating box chart when the system displays the view all pop-up.

The values for this property are controlled by the specified style class in the style sheet associated with the chart.

The default is PT_RATBOX_ICONONLY_BOX.

This property is read-write.

Related Links

Styling PeopleSoft Charts

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

IsDragable

Description

Specify whether nodes in the rating box chart can be dragged and dropped. If the property is specified as *True*, then user will be able to drag a node in the rating box chart and drop it to another quadrant. If the property is *False*, then the drag and drop action is disabled.

The default value is *True*.

This property is read-write.

Related Links

Height

LegendPosition

Description

Use this property to specify where the legend should appear in relationship to the chart. You can specify either a numeric or constant value for this property.

The values are:

Numeric Value	***Constant Value***	***Description***
2	%ChartLegend_Top	Display legend at the top of the chart.
3	%ChartLegend_Bottom	Display legend below the chart.

If you set a value other than *2* or *3*, a runtime error is thrown and the chart is not rendered.

This property is read-write.

MainTitle

Description

Use this property to specify the text for the main title of the chart.

This property takes a string value.

This property is read-write.

MainTitleStyle

Description

Use this property to specify the style of the main title. The values for this property are the style classes contained in the style sheet associated with the chart.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The values for this property are controlled by the specified style class in the style sheet associated with the chart.

The default style class is PT_RATBOX_TITLE.

This property is read-write.

NDMaxDisplayDescLength

Description

Specify the maximum number of characters that will display for the description.

When the ShowNodeDescription chart property is set to True, then both the icon and the description of the node will appear in the quadrant.

If the description is larger than NDMaxDisplayDescLength then the node displays the number of characters specified in NDMaxDisplayDescLength, followed by an ellipsis.

If the full node description or the number of characters specified in NDMaxDisplayDescLength cannot fit in a quadrant at runtime the description is automatically truncated. An ellipsis (...) follows the truncated text.

You only need to set this property if you want the truncated text to be less than the automatically truncated text.

When the user mouses over the truncated node description, the whole text displays in a data hint.

If an invalid (negative) value is specified, an error will be thrown at runtime.

The default value is 50.

This property is read-write.

PopUpHeaderStyle

Description

Use this property to specify the style class that controls the appearance of the pop-up header.

The values for this property are controlled by the specified style class in the style sheet associated with the chart.

The default style class is PT_RATBOX_POPUP_HEADER.

This property is read-write.

Related Links

Styling PeopleSoft Charts

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

PopUpHeight

Description

Specify the height of the pop-up chart in pixels.

This parameter takes a number value.

The recommended value is half of the rating box chart height.

If you set a pop-up chart height value that cannot fit the x-axis area of the popup chart, a runtime error is thrown.

The default value is 0. If a negative value is specified, an error will be thrown at runtime.

This property is read-write.

PopUpStyle

Description

Use this property to specify the style class that controls the appearance of the pop-up.

The values for this property are controlled by the specified style class in the style sheet associated with the chart.

The default style class is PT_RATBOX_POPUP.

This property is read-write.

Related Links

Styling PeopleSoft Charts

PopUpWidth

Description

Specify the width of the pop-up chart in pixels.

This parameter takes a number value.

The recommended value is half of the rating box chart width.

If you set a pop-up chart width value that cannot fit the y-axis area of the popup chart, a runtime error is thrown.

The default value is 0. If a negative value is specified, an error will be thrown at runtime.

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SelectedQuadrantStyle

Description

Use this property to specify the style class that controls the appearance of the quadrant when it is selected.

The values for this property are controlled by the specified style class in the style sheet associated with the chart.

The default style class is PT_RATBOX_SELECTED_BOX.

This property is read-write.

Related Links

Styling PeopleSoft Charts

ShowAxisLabels

Description

Specify a Boolean value indicating whether the rating box chart should show the x- and y-axis labels. The default value is True.

This property is read-write.

Related Links

SetXAxisLabels
SetYAxisLabels

ShowNodeDescription

Description

Specify whether the chart should show the node description. This property takes a Boolean value.

Value	*Description*
True	Both the icon and description for the node appear.
False	Only the icon for the node appears.

The default value is True.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Style

Description

Use this property to specify the style class that defines the overall appearance attributes of the chart . The value must be a valid style class within the style sheet specified for the chart.

This property is read-write.

Related Links

Styling PeopleSoft Charts

ViewAllStyle

Description

Use this property to specify the style class that controls the appearance of the View All link.

The values for this property are controlled by the specified style class in the style sheet associated with the chart.

The default style class is PT_RATBOX_VIEWALL_DESCR.

This property is read-write.

Related Links

Styling PeopleSoft Charts

Width

Description

Use this property to specify the width of the chart. This property takes a numeric value. The unit of measurement is pixels.

The default value is the width of the chart control on the page definition.

If you set a chart width value that cannot fit the y-axis and label areas of the chart, a runtime error is thrown.

If a negative value is specified, an error will be thrown at runtime and the chart will not be rendered.

If you try to read this property before setting it, the value returned is 0.

This property is read-write.

XAxisBoxNum

Description

Specify the number of quadrants in the x-axis.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is required. The value must be equal to or greater than 1.

If a value less than 1 is specified, an error will be thrown at runtime.

This property is read-write.

XAxisLabelStyle

Description

Use this property to specify the style of the x-axis label. The values for this property are the style classes contained in the style sheet associated with the chart.

The values for this property are controlled by the specified style class in the style sheet associated with the chart.

The default style class is PT_RATBOX_XAXIS.

This property is read-write.

Related Links

Styling PeopleSoft Charts

XAxisTitle

Description

Use this property to specify the text for the x-axis title.

This property is read-write.

XAxisTitleStyle

Description

Use this property to specify the style of the x-axis title. The values for this property are the style classes contained in the style sheet associated with the chart.

The values for this property are controlled by the specified style class in the style sheet associated with the chart.

The default style class is PT_RATBOX_XTTL.

This property is read-write.

Related Links

Styling PeopleSoft Charts

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

YAxisBoxNum

Description

Specify the number of quadrants in the y-axis.

This property is required. The value must be equal to or greater than 1.

If a value less than 1 is specified, an error will be thrown at runtime.

This property is read-write.

YAxisLabelStyle

Description

Use this property to specify the style of the y-axis label. The values for this property are the style classes contained in the style sheet associated with the chart.

The values for this property are controlled by the specified style class in the style sheet associated with the chart.

The default style class is PT_RATBOX_YAXS.

This property is read-write.

Related Links

Styling PeopleSoft Charts

YAxisTitle

Description

Use this property to specify text of the title for the y-axis.

This property is read-write.

YAxisTitleStyle

Description

Use this property to specify the style of the y-axis title. The values for this property are the style classes contained in the style sheet associated with the chart.

The values for this property are controlled by the specified style class in the style sheet associated with the chart.

The default style class is PT_RATBOX_YTITL.

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

Styling PeopleSoft Charts

QuadrantSchema Class Properties

These properties are used by the QuadrantSchema class. The properties are described in alphabetic order.

Related Links

Using the QuadrantSchema Class
SetQuadrantSchemas

LabelPosition

Description

Use this property to specify the position for the label for this quadrant as a Integer. You can specify either an Integer or constant value for this property.

The values are:

Numeric Value	*Constant Value*	*Description*
0	%Top_Left	Position the label in the top left corner of the quadrant. **Note:** %Top_Left is the default value.
1	%Top_Right	Position the label in the top right corner of the quadrant.
2	%Bottom_Left	Position the label in the bottom left corner of the quadrant.
3	%Bottom_Right	Position the label in the bottom right corner of the quadrant.

This property is read-write.

LabelStyle

Description

Use this property to specify a style class for the label for this quadrant as a String. The default value is PT_RATBOX_LABEL.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

LabelText

Description

Use this property to specify a label for this quadrant as a String.

This property is read-write.

XRating

Description

Use this property to specify the x rating for this quadrant as a String. The value for this property needs to be in the array of values for the x-axis specified by the SetXAxisLabels method; otherwise, a runtime error occurs.

This property is read-write.

Related Links

SetXAxisLabels

YRating

Description

Use this property to specify the y rating for this quadrant as a String. The value for this property needs to be in the array of values for the y-axis specified by the SetYAxisLabels method; otherwise, a runtime error occurs.

This property is read-write.

Related Links

SetYAxisLabels

Charting Examples

The following are some example of charts, with the PeopleCode used to create them:

- Creating a chart using the Chart chart.
- Creating a Gantt chart.
- Creating an organization chart.
- Creating a rating box chart.
- Creating a chart using an iScript.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Creating a Chart Using the Chart Class

This section demonstrates how to create a simple chart based on the Chart class. This chart is meant to be used to demonstrate basic principles of creating charts and give an opportunity to experiment with different chart types. It is not typical of how a chart is used in PeopleSoft applications.

The first six steps also apply to creating charts using the Gantt class, the OrgChart class, and the RatingBoxChart class.

The steps to create a chart are:

1. Place a chart control on a page.
2. Associate the chart control with a record field.
3. Create the chart data record.
4. Add PeopleCode to instantiate a chart object.
5. Set the data source.
6. View the page in the browser.
7. Add data for the chart.
8. Specify the series data.
9. Specify chart colors.
10. Add text elements.
11. Review the complete program.

Placing a Chart Control on a Page

In Application Designer, create a new page.

Select Insert, Chart and draw a rectangle to represent the area the chart will occupy. The chart can be any size, and you can have more than one chart on a page.

Place the page on a component and register the component.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Associating the Chart Control with a Record Field

Image: Chart Properties dialog box

Each chart on a component must be associated with a unique field. Double-click the chart control to access the Chart Properties dialog box and enter a record name and field name.

The chart field has no special requirements. Its only purpose is to provide a reference to the field in PeopleCode.

This sample chart uses a derived/work record named DOC_CHRT_WRK that is dedicated to this purpose.

Creating the Chart Data Record

The chart needs either a record or a rowset to serve as the data source. This sample chart uses a record. See the Chart class SetData method for details about using a rowset.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

See SetData.

Image: Example of a chart data record

At a minimum, the record must have fields for the x-axis data and the y-axis data. Optionally, the record can have fields for series data, chart color, and glyph size.

Num	Field Name	Type	Key	Ordr	Dir	CurD	Srch	List	Sys	Audt	InTy	EnTypA	Default
1	PB_CHART_PRODUCT	Char	Key	1	Asc		No	No	No		No	No	
2	PB_CHART_REGION	Char	Key	2	Asc		No	No	No		No	No	
3	PB_CHART_SALES	Sign					No	No	No		No	No	
4	PB_CHART_DESC	Char					No	No	No		No	No	
5	PB_CHART_COLOR	Nbr					No	No	No		No	No	
6	PB_CHART_X_NUMERIC	Sign					No	No	No		No	No	
7	PB_CHART_GLYPHSCLE	Sign					No	No	No		No	No	

The record must be available in the component buffer at runtime. You can use a database record that is already part of your application or you can use a derived/work record or a component rowset that you populate at runtime. For greatest control, you will normally populate your record or rowset at runtime.

For the sample chart, place the record on a grid on a second page on the sample component. This placement gives you the opportunity to experiment with the data.

Image: Example of a page definition with chart data grid

Your chart data record must be placed at level 1 on the same component as the chart so that the data is available in the component buffer at runtime. In your application, you can hide the grids or scroll areas that hold the records. For the sample chart, you will keep the grid visible so you can enter sample data.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Adding PeopleCode to Instantiate a Chart Object

This example instantiates a chart object using the Chart class, so it can be used to create bar charts, line charts, pie charts, and so on. Other examples in this section demonstrate how to create charts based on the Gantt class, OrgChart class, and RatingBoxChart class.

See Creating a Gantt ChartCreating a Gantt Chart, Creating a Rating Box Chart.

Add this PeopleCode to the Activate event on the page:

```
/* Declare and instantiate a chart object */
Component Chart &cChart;

&cChart = GetChart(DOC_CHRT_WRK.DOC_CHRT_FLD);
```

Chart PeopleCode is commonly placed on the Activate event, but it can be placed on any appropriate event. You could, for instance, execute the chart PeopleCode from a FieldChange event associated with a push button.

Setting the Data Source

The SetData method takes either a record or a rowset as an argument. In general, specify a record or component rowset when building a chart from page data and a standalone rowset when building a chart using an iScript.

In this example, the PeopleCode sets Product as the series data and sets Region to the x-axis, so that in a bar chart products will be grouped along the x-axis by region. In a line chart, each series is represented by a line. Sales figures are charted on the y-axis.

Note: SetData, SetDataXAxis, and SetDataYAxis are Chart class methods. The other charting classes provide equivalent methods to specify data sources.

```
/* Set the chart data record and specify x-axis, y-axis, and series data */

&cChart.SetData(Record.DOC_CHRT_SLSREC);
&cChart.SetDataXAxis(DOC_CHRT_SLSREC.DOC_CHRT_RGN);
&cChart.SetDataYAxis(DOC_CHRT_SLSREC.DOC_CHRT_SALES);
```

See SetData, SetDataSeries, SetDataXAxis, SetDataYAxis, Creating a Chart Using an iScript.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Viewing the Page in the Browser

Image: Chart class chart with no data

This is the most basic Chart class chart. It has no data and only the default y-axis.

Adding Data for the Chart

Add the following data to the chart:

Region	***Sales***
Arizona	60
California	50
Oregon	42

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Region	*Sales*
Washington	50

Image: A simple bar chart

This bar chart is generated by the example code and data:

This chart graphs sales on the y-axis (the vertical axis) and regions on the x-axis (the horizontal axis).

When the data for the chart is grouped according to values, a set of data representing a single value is called a *series*. For instance, if a chart shows sales for different products in each region, then the set of data for each product is a series.

At this point, the chart has only one series, so you do not need to set the series record field.

Specify the Series Data

If you want to graph more than one product on your chart, you need to specify the source of the series data.

For example, add the products shown in this table to your data:

Product	*Region*	*Sales*
Footballs	Arizona	60
Rackets	Arizona	50
Shoes	Arizona	42
Tents	Arizona	35
Footballs	California	55

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Product	***Region***	***Sales***
Rackets	California	46
Shoes	California	30
Tents	California	35
Footballs	Oregon	50
Rackets	Oregon	40
Shoes	Oregon	30
Tents	Oregon	25
Footballs	Washington	45
Rackets	Washington	30
Shoes	Washington	20
Tents	Washington	15

Add this PeopleCode to set the series record field:

```
&cChart.SetDataSeries(DOC_CHRT_SLSREC.DOC_CHRT_PRDCT);
```

Image: Default 2D bar chart with products as series

The resulting chart is a default 2D bar chart with bars for each region grouped by series:

The chart has four series:

- Footballs

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- Rackets
- Shoes
- Tents

Each series shows four regions along the x-axis:

- Arizona
- California
- Oregon
- Washington

Sales values appear against the y-axis as bar height.

The chart uses the default colors.

Specifying Chart Colors

If you do not want to use the default colors, you need a column containing the colors for each bar. Typically, the bars in a series are colored alike.

Product	***Region***	***Sales***	***Chart Color***
Footballs	Arizona	60	1
Rackets	Arizona	50	13
Shoes	Arizona	42	5
Tents	Arizona	35	15
Footballs	California	55	1
Rackets	California	46	13
Shoes	California	30	5
Tents	California	35	15
Footballs	Oregon	50	1
Rackets	Oregon	40	13
Shoes	Oregon	30	5
Tents	Oregon	25	15
Footballs	Washington	45	1

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Product	*Region*	*Sales*	*Chart Color*
Rackets	Washington	30	13
Shoes	Washington	20	5
Tents	Washington	15	15

Add the following PeopleCode to your program to set the colors for your chart:

```
/* Associate color field with chart */
&cChart.SetDataColor(DOC_CHRT_SLSREC.DOC_CHRT_COLOR);
```

Adding Text Elements

The following PeopleCode adds these elements to your chart:

- Title
- Legend
- Y-axis title
- X-axis title

```
/* Set title and legend properties */
&cChart.MainTitle = "Recreational Product Sales by Region";
&cChart.HasLegend = True;
&cChart.LegendPosition = %ChartLegend_Right;

/* Set axis text properties */
&cChart.XAxisLabelOrient = %ChartText_Horizontal;
&cChart.XAxisTitle = "Region";
&cChart.YAxisTitle = "Sales";
```

Image: Sample bar chart with custom colors, a main title, axis titles, and a legend

This is the resulting chart:

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Reviewing the Complete Program

The PeopleCode for this bar chart has been presented in snippets. Here is the complete program that produced the chart:

```
/* Declare and instantiate a chart object */
Component Chart &cChart;

&cChart = GetChart(DOC_CHRT_WRK.DOC_CHRT_FLD);

/* Set the chart data record and specify x-axis, y-axis, and series
data */

&cChart.SetData(Record.DOC_CHRT_SLSREC);
&cChart.SetDataXAxis(DOC_CHRT_SLSREC.DOC_CHRT_RGN);
&cChart.SetDataYAxis(DOC_CHRT_SLSREC.DOC_CHRT_SALES);
&cChart.SetDataSeries(DOC_CHRT_SLSREC.DOC_CHRT_PRDCT);

/* Associate color field with chart */
&cChart.SetDataColor(DOC_CHRT_SLSREC.DOC_CHRT_COLOR);

/* Set title and legend properties */
&cChart.MainTitle = "Recreational Product Sales by Region";
&cChart.HasLegend = True;
&cChart.LegendPosition = %ChartLegend_Right;

/* Set axis text properties */
&cChart.XAxisLabelOrient = %ChartText_Horizontal;
&cChart.XAxisTitle = "Region";
&cChart.YAxisTitle = "Sales";
```

Other Modifications

The remainder of this section shows the effects of modifying other aspects of your chart.

Changing X-Axis and Series Values

```
&cChart2.SetDataXAxis(DOC_CHRT_SLSREC.DOC_CHRT_PRDCT);
&cChart2.SetDataSeries(DOC_CHRT_SLSREC.DOC_CHRT_RGN);

&cChart2.MainTitle = "Recreational Product Sales by Product";
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
&cChart2.XAxisTitle = "Product";
```

Image: Bar chart with series set to region

To group sales by product instead of by region, switch the series and the x-axis. You will also need to reorder colors to correspond to regions instead of products:

Axis Properties

Image: Bar chart with negative values

If your chart has negative values, the bars automatically extend below the x-axis:

If you want to remove the tick marks from the x- or y-axis, you need to specify an empty array for the SetXAxisLabels or SetYAxisLabels methods.

The following example removes the tick marks from the y-axis:

```
Local array of string &Arr;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
&Arr = CreateArray("");
&Chart.SetYAxisLabels(&Arr);
```

If you set the x-axis labels to an empty array to remove the ticks, you must be plotting a single series on the chart because labels are automatically generated for each series if you do not provide them.

See SetXAxisLabels, SetYAxisLabels.

You can also use the XAxisMin, XAxisMax, YAxisMin, YAxisMax, and other axis properties to control the appearance of the axes.

See XAxisCross, XAxisLabelOrient, XAxisTicks, YAxisLabelOrient, YAxisMax, YAxisMin, YAxisTicks.

Chart Class Chart Types

Use the Type property to set the chart type.

2D Bar Chart

```
&cChart.Type=%ChartType_2DBar;
```

Image: 2D bar chart

The default Chart class chart type is a 2D bar chart:

The following examples show the various chart types using the same data. Each example gives the PeopleCode snippet that creates that chart type.

For a complete list of all Chart class chart types, see Chart class Type property.

See Type.

The Charting Examples section provides other examples of PeopleCode for charts using Gantt class, OrgChart class, and RatingBoxChart class at the end of the chapter.

See Creating a Gantt ChartCreating a Gantt Chart, Creating a Rating Box Chart.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

3D Bar Chart

A visual 3D effect can add interest to a chart.

Add this code to make your bar chart a 3D bar chart:

```
&cChart.Type = %ChartType_3DBar;
&cChart.XAxisLabelOrient = 90;
```

Image: 3D bar chart

This PeopleCode also turns the x-axis labels 90 degrees for better readability. Valid values for XAxisLabelOrient are 0 and 90.

See the XAxisLabelOrient property.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Horizontal Bar Chart

Use this line of code to specify a horizontal bar chart:

```
&cChart.Type = %ChartType_2DHorizBar;
```

Image: Horizontal bar chart

This example illustrates a horizontal bar chart:

Stacked Bar Chart

With a the stacked bar chart, you can place a different emphasis on the same data. The stacked column shows total sales per region as well as the product segments that contribute to the total.

Use this line of code to specify a stacked bar chart:

```
&cChart.Type = %ChartType_2DStackedBar;
```

Image: Stacked bar chart

This example illustrates a stacked bar chart:

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

3D Stacked Bar Chart

Use this line of code to specify a 3D stacked bar chart:

```
&cChart.Type = %ChartType_3DStackedBar;
```

Image: 3D stacked bar chart

This example illustrates a 3D stacked bar chart:

Horizontal Stacked Bar Chart

Use this line of code to specify a horizontal stacked bar chart:

```
&cChart.Type = %ChartType_2DHorizStackedBar;
```

Image: Horizontal stacked bar chart

This example illustrates a horizontal stacked bar chart:

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Percent Bar Chart

A percent bar is similar to a stacked bar, but the segments of each bar add up to 100. The segments show the proportional contribution of each product to total sales.

Note: Negative values cannot be displayed in any type of percent bar chart.

Use this line of code to specify a stacked percent bar chart:

```
&cChart.Type = %ChartType_2DPercentBar;
```

Image: Percent bar chart

This example illustrates a percent bar chart:

3D Percent Bar Chart

Note: Negative values cannot be displayed in any type of percent bar chart.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Use this line of code to specify a 3D percent bar chart:

```
&cChart.Type = %ChartType_3DPercentBar;
```

Image: 3D percent bar chart

This example illustrates a 3D percent bar chart:

Horizontal Percent Bar Chart

Note: Negative values cannot be displayed in any type of percent bar chart.

Use this line of code to specify a horizontal percent bar chart:

```
&cChart.Type = %ChartType_2DHorizPercentBar;
```

Image: Horizontal percent bar chart

This example illustrates the fields and controls on a horizontal percent bar chart:

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Line Chart

A line chart is useful for showing changes and trends over time or across categories.

Use this line of code to specify a line chart:

```
&cChart.Type = %ChartType_2DLine;
```

Image: Line chart

This example illustrates a line chart:

Overlay Chart

You can overlay one chart on top of another to compare two different but related sets of data. The following chart uses a second set of data, showing average temperature for each region.

Use the OLType property to specify whether the overlay is a line chart or a histogram.

Add this PeopleCode to the PeopleCode for your bar chart to create 2D line chart overlay:

```
/* Create Overlay */
&cChart3.SetOLData(Record.DOC_CHRT_OLREC);
rem &cChart.SetOLDataSeries(DOC_CHRT_OLREC.SC_CHART_SERIES);
&cChart3.SetOLDataXAxis(DOC_CHRT_OLREC.DOC_CHRT_RGN);
&cChart3.SetOLDataYAxis(DOC_CHRT_OLREC.DOC_CHRT_SALES);
```


Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
&cChart3.OLType = %ChartType_2DLine;
```

Image: Overlay chart

This example illustrates a 2D line chart overlay on a vertical bar chart:

True XY Line Chart

A true XY chart has a numeric x-axis—that is, the numeric XY pairs can be plotted in numerical order. Conversely, a default line chart plots x-axis values ordered by record position.

Use the IsTrueXY property to create a true XY line chart; by default, IsTrueXY is False. See IsTrueXY for more information.

For example, you have the following data:

X-axis	***Y-axis***
11	88000
12.2	96200
4.6	101300
6.6	83000
14	111200
8.5	118000

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The following example shows a default line chart using the previous data:

Image: Line chart with IsTrueXY = False

This example illustrates a line chart without ordered, numerical x-axis data:

A line chart with IsTrueXY = True orders the x-axis values numerically on a continuous scale.

Note: You must programmatically sort the chart data rowset on the x-axis value in ascending order to produce a numerically ordered true XY chart.

Image: Line chart with IsTrueXY = True

The following chart is a true XY line chart plotted with the same data.

Scatter Chart

Use this line of code to specify a scatter chart:

```
&cChart.Type = %ChartType_2DScatter;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

A scatter chart compares number pairs. Each pair is plotted against the horizontal x-axis and the vertical y-axis. The data values are scattered across the chart. XY scatter charts are good for showing comparisons of numbers, such as scientific or statistical data, where several measurements need to be plotted on a single chart.

A scatter chart is a true XY chart, meaning that the x-axis is numeric. The IsTrueXY property is automatically set to True.

For example, this sample data could be used to make an XY scatter chart:

Tenure	***Salary***
11	88000
12.2	96200
4.6	101300
6.6	83000
14	111200
8.5	118000

You use this code snippet to make a scatter chart:

```
&cChart5.Type = %ChartType_2DScatter;
&cChart5.SetData(Record.DOC_CHRT_XYDATA);
&cChart5.SetDataXAxis(DOC_CHRT_XYDATA.DOC_CHRT_X);
&cChart5.SetDataYAxis(DOC_CHRT_XYDATA.DOC_CHRT_Y);
```

Image: Scatter chart

This example illustrates a scatter chart:

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Note: If you have only one point of data, that is, only one x and y pair, use a scatter chart. You may have unexpected results if you use a line chart with only one point.

Bubble Chart

A bubble chart is a special type of scatter chart.

If you add a third data set, glyph size, to a scatter chart, you can create a bubble chart, which uses the size of the markers to represent a third dimension of numeric data.

You can also set annotations for scatter charts and bubble charts.

This chart example uses Age to determine the size of the bubble markers, or glyphs, on the chart and Name to set the annotations:

Tenure	***Salary***	***Age***	***Name***
11	88000	39	Joyce
12.2	96200	55	Tolstoy
4.6	101300	32	Shelley
6.6	83000	48	Tolkien
14	111200	59	Dickens
8.5	118000	49	Hemingway

```
&cChart6.Type = %ChartType_2DBubble;
&cChart6.SetData(Record.DOC_CHRT_XYDATA);
&cChart6.SetDataXAxis(DOC_CHRT_XYDATA.DOC_CHRT_X);
&cChart6.SetDataYAxis(DOC_CHRT_XYDATA.DOC_CHRT_Y);
&cChart6.SetDataGlyphScale(DOC_CHRT_XYDATA.DOC_CHRT_AGE);
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
&cChart6.SetDataAnnotations(DOC_CHRT_XYDATA.DOC_CHRT_LASTNAME);
```

Image: Bubble chart

This example illustrates a bubble chart:

Pie Chart

A pie chart shows comparisons within a single set of values, and it shows how parts contribute to a whole. It is an ideal chart type to display the contribution of each region to an annual sales total.

A pie chart ignores the series and only plots x-axis data against y-axis values. Our original bar chart has four regions times four products, resulting in 16 XY pairs. A pie chart with all of those slices would be confusing and not helpful. Instead, suppose you want to show just the data for tents, which are in rows 13–16. You can use a combination of the DataWidth and DataStartRow properties to select which rows to display.

You can make a pie chart showing only rows 13–16 by adding this snippet of code:

```
&cChart.DataWidth = 4;
&cChart.DataStartRow = 13;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
&cChart.Type = %ChartType_2DPie;
```

Image: 2D pie chart

This example illustrates a 2D pie chart generated from a portion of the rowset:

Exploded Pie Chart

Use the SetExplodedSectorsArray Chart class method to specify the sectors to explode. Sectors correspond to rows of data used by the pie chart. Sector 1 is the first row of data, or the row specified with the DataStartRow chart class property, if it is used, and so on.

The following snippet of code explodes sectors 1 and 3:

```
Local array of number &ExplodedArray;
&ExplodedArray = CreateArray(1,3);
&cChart.SetExplodedSectorsArray(&ExplodedArray);
```

Image: Exploded pie chart

This example illustrates an exploded pie chart:

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

See the SetExplodedSectorsArray property.

3D Pie Chart

Use this line of code to specify a 3D pie chart:

```
&cChart.Type = %ChartType_3DPie;
```

Image: 3D pie chart

This example illustrates a 3D pie chart:

Tick Mark Considerations

If you want to remove the tick marks from the x- or y-axis, you need to specify an empty array for the SetXAxisLabels or SetYAxisLabels methods.

The following example removes the tick marks from the y-axis:

```
Local array of string &Arr;

&Arr = CreateArray("");
&Chart.SetYAxisLabels(&Arr);
```

If you set the x-axis labels to an empty array to remove the ticks, you must be plotting a single series on the chart because labels are automatically generated for each series if you do not provide them.

See SetXAxisLabels, SetYAxisLabels.

Adding Drilldown

If you set the property IsDrillable to True and add FieldChange PeopleCode to your chart, your user can get more information by clicking a chart data element—a bar, line segment, data point, or pie slice.

For a simple example, add this PeopleCode to the FieldChange event on the y-axis field:

```
MessageBox(0, "", 0, 0, "Sales for " | DOC_CHRT_SLSREC.DOC_CHRT_PRDCT | " in " | DO⇒
C_CHRT_SLSREC.DOC_CHRT_RGN | " = " | DOC_CHRT_SLSREC.DOC_CHRT_SALES | "");
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

And add this code to the page Activate event for your pie chart:

```
&cChart.IsDrillable = True;
```

Image: Example of drill-down triggering PeopleCode with MessageBox

When the user clicks the Oregon slice of the pie chart, this message appears:

Current context provides the values for fields in the current row in the component buffer. You can use drilldown with your chart data fields along with any other data in the component buffer to accomplish anything FieldChange PeopleCode is capable of.

If the bars on a bar chart are too narrow, a user may not be able to click them. Sometimes, a few bars on a chart are affected, sometimes all of the bars cannot be clicked. The workaround is to put fewer bars on your chart or to make your chart bigger so that each bar is wider.

See IsDrillable.

Using the Other Charting Classes

In addition to the all the charts you can create with the Chart class, you can create specialized charts using the Gantt class, the OrgChart class, and the RatingBoxChart class.

You follow the same initial steps to create these specialized charts as you do for the Chart class chart types. The PeopleCode programs to set the data and properties are similar as well, but Gantt charts, organization charts, and rating box charts use data differently and interact with the user in different ways than do the Chart class charts.

See Creating a Gantt ChartCreating a Gantt Chart, Creating a Rating Box Chart.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Creating a Gantt Chart

Image: Gantt chart

The PeopleCode and data used in this example create the following Gantt chart:

This example uses the following data in the record QE_GANTT_TASK:

Image: Example of Gantt task data

This example illustrates Gantt task data:

Tasks

*Task ID	*Level	TASK NAME	*PLANNED START DATE	*PLANNED END DATE
1	1	Birth	01/01/1963 12:00:00AM	01/01/1963 12:00:00AM
2	1	Baby	01/01/1963 12:00:00AM	06/30/1964 12:00:00AM
3	2	Toddler	07/01/1964 12:00:00AM	07/01/1966 12:00:00AM
4	1	Childhood	07/01/1966 12:00:00AM	09/01/1980 12:00:00AM
5	2	Elementary School	09/01/1968 12:00:00AM	06/01/1973 12:00:00AM
6	2	Middle School	09/01/1973 12:00:00AM	06/01/1976 12:00:00AM
7	2	High School	09/01/1976 12:00:00AM	06/01/1980 12:00:00AM
8	2	Graduate	06/20/1980 12:00:00AM	06/20/1980 12:00:00AM
9	1	Adult	09/02/1980 12:00:00AM	12/31/1983 12:00:00AM
10	1	End of Life	01/01/1987 12:00:00AM	01/01/1987 12:00:00AM

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The chart also uses the following dependency data in the record QE_GANTT_TASKD:

Image: Example of Gantt dependency data

This example illustrates Gantt dependency data:

Dependencies

Task ID	Parent Task ID	Dependency Type	URL
2	1		
5	3		http://www.google.com
6	5		
7	6		
8	7		
9	8		

To create a Gantt chart:

1. In Application Designer, add a chart control to a page and associate the chart control with a record name and a field name.

   See Creating a Chart Using the Chart Class.

2. Initialize a Gantt chart object.

   Initialize the chart using the GetGanttChart function. The arguments of the function are the record and field name specified for the chart definition in Application Designer.

```
Local Gantt &gGantt;
&gGantt = GetGanttChart(QE_CHART_DUMREC.QE_CHART_FIELD);
```

3. Specify values for the required methods.

   At a minimum, specify the source of the task data and which fields contain task ID, start date, and end date.

```
&gGantt.SetTaskData(Record.QE_GANTT_TASK);
&gGantt.SetTaskID(QE_GANTT_TASK.QE_TASK_ID);
&gGantt.SetPlannedStartDate(QE_GANTT_TASK.QE_PLANNED_START);
&gGantt.SetPlannedEndDate(QE_GANTT_TASK.QE_PLANNED_END);
```

4. Specify values for the additional methods controlling the appearance of the data.

   After setting the required methods, you can set additional methods to control the appearance of the chart. The following code specifies the percentage of the entire chart that is taken up by the chart area, the width and height of the chart, if the user can click the chart area of the Gantt chart and either execute a function or a URL, and whether labels should appear with the tasks in the task section.

```
&gGantt.SetChartArea(50);
&gGantt.Width = 700;
&gGantt.Height = 380;
&gGantt.IsDrillable = True;
&gGantt.ShowTaskLabels = True;
```

5. Specify the appearance of grid lines.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Depending on the type of data that you are using, you can specify the type of grid lines that should appear in the chart section of the Gantt chart.

```
&gGantt.GridLineType = %ChartLine_Solid;
&gGantt.GridLines = %ChartGrid_Vertical;
```

6. Specify the appearance of data.

   The following methods control the appearance of the different parts of the task data, such as the label, which hints appear when you pass the mouse over the task data, and so on.

```
&gGantt.SetTaskName(QE_GANTT_TASK.QE_TASK_NAME);
&gGantt.SetWBSNumbering(QE_GANTT_TASK.QE_HINTS);
&gGantt.SetTaskLevel(QE_GANTT_TASK.QE_LEVEL);
&gGantt.SetTaskLabel(QE_GANTT_TASK.QE_TASK_LABEL);
&gGantt.SetTaskProgress(QE_GANTT_TASK.QE_TASK_PROGRESS);
&gGantt.SetTaskBarURL(QE_GANTT_TASK.QE_URL);
&gGantt.SetTaskMilestone(QE_GANTT_TASK.QE_TASK_MILESTONE);
&gGantt.TaskMilestoneGlyph = QE_GANTT_PROJ.QE_MILESTONE_GLYPH;

&gGantt.SetPlannedTaskBarColor(QE_GANTT_TASK.QE_PLANNED_COLOR);
&gGantt.SetActualTaskBarColor(QE_GANTT_TASK.QE_ACTUAL_COLOR);
&gGantt.SetTaskProgressBarColor(QE_GANTT_TASK.QE_PROGRESS_COLOR);
```

7. Specify the additional fields that will appear in the table section.

   You can also specify application data that will appear with the task data.

```
&gGantt.SetTaskAppData(QE_GANTT_TASK.QE_PLANNED_START,
   QE_GANTT_TASK.QE_PLANNED_END, QE_GANTT_TASK.QE_TASK_PROGRESS,
   QE_GANTT_TASK.QE_TASK_NAME);
```

8. Specify titles for the task bars.

```
&gGantt.TaskTitle = "Tasks";
 &appDataArray = CreateArray("Start", "End", "Progress", "Name");
 &gGantt.SetTaskAppDataTitles(&appDataArray);
```

9. Specify the fields for task dependency data.

   You do not need to specify dependency data. However, if you do, you must also specify the parent ID and the child ID (where the dependency data starts and ends). You can also specify the type of line used between dependencies and a URL that the browser will open to if the user clicks a dependency line.

```
&gGantt.SetTaskDepenencyData(Record.QE_GANTT_TASKD);
&gGantt.SetTaskDependencyParentID(QE_GANTT_TASKD.QE_PARENT_TASK_ID);
&gGantt.SetTaskDependencyChildID(QE_GANTT_TASKD.QE_TASK_ID);
&gGantt.TaskDependencyLineType = %ChartLine_Solid;
&gGantt.SetTaskDependencyURL(QE_GANTT_TASKD.URL);
```

10. Specify the actual dates for the project.

    If you know the actual start and end dates, in addition to the planned date, you can add those to your chart.

```
&gGantt.SetActualStartDate(QE_GANTT_TASK.QE_ACTUAL_START);
&gGantt.SetActualEndDate(QE_GANTT_TASK.QE_ACTUAL_END);
```

11. Specify the time line axis values.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

You can specify values for where the time line axis starts and ends.

```
&gGantt.AxisStartDateTime = DateTimeValue("01/01/1963 8:00:00");
&gGantt.AxisEndDateTime = DateTimeValue("01/01/1987 8:00:00");
```

12. Specify the format of the time line axis values.

    You can specify the format of the time line elements, such as the appearance of the days of the week, whether as a number or using the full name, and so on.

```
&gGantt.SetMonthFormat(%Chart_MonthFormat_FullName);
&gGantt.SetDayFormat(%Chart_DayFormat_2Digit);
```

Creating an Organization Chart

Image: Organization chart

The PeopleCode used in this example creates the following organization chart:

To create an organization chart:

1. Add a chart control to a page in Application Designer.

   Associate the chart control with a record name and field name.

   See Creating a Chart Using the Chart Class.

2. Add the organization node record and the pop-up node record to the component.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

These records are derived/work records that contain clones of the subrecords PTORGNODE_SBR and PTPOPUPNODE_SBR. These records must be in the component buffer. You can add them to a hidden grid on the page, or you can place them on another page in the same component.

3. If the chart will have breadcrumbs, add the breadcrumb node record to the component.

   This derived/work record contains a clone of the subrecord PTORGCRMB_SBR. The record must be in the component buffer.

4. Prepare the organization chart data.

   In an event such as PreBuild, instantiate two rowset objects and populate them with the organization node data and the pop-up node data.

   This example shows one possible way. How you do it depends on how your data is stored and how you intend to present it.

```
Component Rowset &rs, &rsP, &rsBC, &rsOrgNode, &rsOrgPopupND, &rsBreadCrumbs;
Component OrgChart &ocOrgChart;

Local Rowset &RSGridDR;
Local Rowset &RSAGRID;

/* The record QE_ORG_NODEDATA has the data for the org chart **
** You will probably fill the rowset with some subset of the data**
** in the database. This example uses all the rows. */
&rs = CreateRowset(Record.QE_ORG_NODEDATA);
&rs.Fill();

/* Get the grid on the page for the node data and initalize to nulls */
& rsOrgNode = GetLevel0()(1).GetRowset(Scroll.QE_ORG_NODE);
& rsOrgNode.Flush();

/* Copy data from database table, QE_ORG_NODEDATA to the derived/work
** record QE_ORG_NODE_DR */
&rs.CopyTo(&rsOrgNode, Record.QE_ORG_NODEDATA, Record.QE_ORG_NODE_DR);

/* The record QE_ORG_POPDATA has the data for the popup chart */
&rsP = CreateRowset(Record.QE_ORG_POPDATA);
&rsP.Fill();

/* Get the grid on the page for the popup data and initalize to nulls */
& rsOrgPopupND = GetLevel0()(1).GetRowset(Scroll.QE_ORG_POPUP);
& rsOrgPopupND.Flush();

/* Copy data from database table, QE_ORG_POPDATA to the derived/work
** record QE_ORG_POP_DR */
&rsP.CopyTo(&rsOrgPopupND, Record.QE_ORG_POPDATA, Record.QE_ORG_POP_DR);

/* Fill in the breadcrumb information for this chart if the chart **
** uses breadcrumbs. */
&rsBC = CreateRowset(Record.QE_ORG_CRMB);
&rsBC.Fill();

/* Get the grid on the page for the pop data and initalize to nulls */
&rsBreadCrumbs = GetLevel0()(1).GetRowset(Scroll.QE_ORG_BCRMB);
&rsBreadCrumbs.Flush();

/* Copy data from database table, QE_ORG_CRMB to the derived/work
** record QE_ORG_CRMB_DR */
&rsBC.CopyTo(&rsBreadCrumbs, Record.QE_ORG_CRMB, Record.QE_ORG_CRMB_DR);
```

5. Instantiate an OrgChart object.

   In an event such as Activate, add PeopleCode to instantiate and define your organization chart.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Get the chart using the GetOrgChart function. The argument for this function is the record name and field name specified on the Records tab of the Chart Properties dialog box in Application Designer.

```
Component Rowset & rsOrgNode, & rsOrgPopupND, &rsBreadCrumbs;
Component OrgChart &ocOrgChart;
&ocOrgChart= GetOrgChart(QE_CHART_DUMREC.QE_CHART_FIELD);
```

6. Specify the organization node record and the pop-up node record.

   These records contain the clones of the subrecords PTORGNODE_SBR and PTORGPOPUP_SBR, respectively.

```
&ocOrgChart.SetNodeRecord(Record.QE_ORG_NODE_DR);
&ocOrgChart.SetPopUpNodeRecord(Record.QE_ORG_POP_DR);
```

7. Specify the node data and pop-up node data rowset objects.

```
/*&RSORGND and &RSORGPOPUPND are level 1 component rowsets that contain the
** organization node data and pop-up node data respectively.*/

&ocOrgChart.SetNodeData(&rsOrgNode);
&ocOrgChart.SetPopUpNodeData(&RSORGPOPUPND);
```

8. (Optional) Specify values for the chart display properties.

```
&ocOrgChart.MainTitle = "Application Development";
&ocOrgChart.MainTitleStyle = "PT_ORGCHART_TITLE";
&ocOrgChart.Direction = 2;
&ocOrgChart.Height = 380;
&ocOrgChart.Width = 700;
&ocOrgChart.VerticalSpace = 15;
&ocOrgChart.ImageLocation = 1;
&ocOrgChart.Style= "PTORGCHART";
&ocOrgChart.HasLegend = True;
&ocOrgChart.NodeMaxDisplayDescLength =30;
&ocOrgChart.CollapsedImage ="PT_COLLAPSED_NODE";
&ocOrgChart.ExpandedImage ="PT_EXPANDED_NODE";
&Expanded_Msg=MsgGetText(110, 100);
&Collapsed_Msg=MsgGetText(110, 101);
&ocOrgChart.Expanded_Msg =&Expanded_Msg
&ocOrgChart.Collapsed_Msg =&Collapsed_Msg
```

9. Specify values for the legend. This is required only if the chart has a legend.

```
&ocOrgChart.LegendStyle = PT_ORGCHART_LEGEND;
&LegendArray = CreateArray("Main", "1-2yrs", "3-5yrs", "Emergency",
"Retirement", "Key", "Successors");
&LegendImgArray = CreateArray("QE_NOWORGCHART", "QE_12ORGCHART",
"QE_34ORGCHART", "QE_EMRORGCHART", "QE_RETIRORG", "QE_KPERSON",
"QE_SUCCSORGCHART");

&ocOrgChart.SetLegend(&LegendArray);
&ocOrgChart.SetLegendImg(&LegendImgArray);
&ocOrgChart.LegendPosition = %ChartLegend_Top;
&ocOrgChart.LegendStyle = "PT_ORGCHART_LEGEND";
```

10. (Optional) Specify image values.

```
&ocOrgChart.ImageLocation =1;
&ocOrgChart.ImageHeight =150;
&ocOrgChart.ImageMouseoverMagnificationFactor =150;
&ocOrgChart.DefaultImage=PT_CHART_DEFAULTIMG;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

11. Specify the breadcrumb data and the rowset and display properties. These are required only if your chart uses breadcrumbs.

```
&ocOrgChart.SetCrumbRecord(Record.QE_ORG_CRMB_DR);
&ocOrgChart.SetCrumbData(&rsBreadCrumbs);
&ocOrgChart.CrumbMaxDisplayLength = 24;
&ocOrgChart.CrumbSeparatorImage = "PT_ORG_BRCRM_SEP";
&ocOrgChart.CrumbDescrStyle = "PT_ORGCHART_BRDCRM";
```

12. (Optional) Specify the maximum number of nodes that will appear in the pop-up without a vertical scroll bar.

```
&ocOrgChart.MaxPopUpDisplayNode = 2;
```

13. (Optional) Assign style class names to control the styles of each node descriptor.

    If you do not specify a style class name, then the PeopleTools default style class is used.

    This example uses the default style class names, so this segment of code could be omitted. It is shown for demonstration purposes only.

```
&ocOrgChart.NodeDescr1Style = "PT_ORGNODE_DESC1";
&ocOrgChart.NodeDescr2Style = "PT_ORGNODE_DESC2";
&ocOrgChart.NodeDescr3Style = "PT_ORGNODE_DESC3";
&ocOrgChart.NodeDescr4Style = "PT_ORGNODE_DESC4";
&ocOrgChart.NodeDescr5Style = "PT_ORGNODE_DESC5";
&ocOrgChart.NodeDescr6Style = "PT_ORGNODE_DESC6";
&ocOrgChart.NodeDescr7Style = "PT_ORGNODE_DESC7";
```

14. (Optional) Assign style class names to control the styles of each pop-up node descriptor.

    If you do not specify a style class name, then the PeopleTools default style sheet is used.

    This example uses the default style class names, so this segment of code could be omitted. It is shown for demonstration purposes only.

```
&ocOrgChart.PopupNodeDescr1Style = "PT_POPNODE_DESC1";
&ocOrgChart.PopupNodeDescr2Style = "PT_POPNODE_DESC2";
&ocOrgChart.PopupNodeDescr3Style = "PT_POPNODE_DESC3";
&ocOrgChart.PopupNodeDescr4Style = "PT_POPNODE_DESC4";
&ocOrgChart.PopupNodeDescr5Style = "PT_POPNODE_DESC5";
&ocOrgChart.PopupNodeDescr6Style = "PT_POPNODE_DESC6";
&ocOrgChart.PopupNodeDescr7Style = "PT_POPNODE_DESC7";
&ocOrgChart.PopupNodeDescr8Style = "PT_POPNODE_DESC8";
&ocOrgChart.PopupHeaderStyle = "PT_POPNODE_HEADER";
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Creating a Rating Box Chart

Image: Rating box chart

The PeopleCode used in the following example creates this rating box chart:

Follow these steps to create a rating box chart.

1. Create the rating box chart node record.

   a. Clone the PTRATINGBOX_SBR subrecord to create an application-specific subrecord.

   b. Create a new application-specific record and insert the new subrecord.

2. Add a chart control to a page in Application Designer.

   See Creating a Chart Using the Chart Class.

3. Add the rating box chart node record to the component.

   This record must be in the component buffer. If you do not want to give the user access to the data you can add the record to a hidden grid on the page. Alternatively, you can place it on another page in the same component.

4. Add PeopleCode.

   - In an event such as PreBuild, add PeopleCode to create a component buffer rowset that references the rating box chart node record.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- Add PeopleCode, probably in the page Activate event, to populate the rowset and define the chart.
- Add FieldChange PeopleCode that will execute when drag-and-drop events occur.

PeopleCode for the Rating Box Chart Example

Complete these steps to create a rating box chart:

1. Prepare the data for the chart.

   Typically, write PeopleCode in an event such as PreBuild to populate a rowset with the data you want to display in the rating box chart.

```
Component Rowset &rs, &rsRatingBox;
Component RatingBoxChart &rbRatingBoxChart;

/* the record QE_RATEBOX_DATA has the data for the RATING BOX  chart */
&rs = CreateRowset(Record.QE_RATEBOX_DATA);
&rs.Fill("Where QE_RATEBOX_TC=:1", QE_RATEBOX_TC.QE_RATEBOX_TC.Value);

/* Get the grid on the page for the node data and initalize to nulls */
&rsGrid = GetLevel0()(1).GetRowset(Scroll.QE_RATEBOX_TC);
&rsGrid.Flush();

/* Copy data from database table, QE_RATEBOX_DATA, to the
level 1 component rowset associated with the component derived working
record QE_RATEBOX_DR */

&rs.CopyTo(&rsGrid, Record.QE_RATEBOX_DATA, Record.QE_RATEBOX_DR);
```

2. Define the RatingBoxChart.

   Add PeopleCode in an event such as Activate.

   Instantiate a RatingBoxChart object using the GetRatingBoxChart built-in function to reference the page control field of the chart.

```
Component Rowset &rs, &rsGrid;
Component RatingBoxChart &rbRatingBoxChart;

&rbRatingBoxChart = GetRatingBoxChart(QE_CHART_DUMREC.QE_CHART_FIELD);
```

3. Set the required display properties for the chart.

```
&rbRatingBoxChart.XaxisBoxNum = 3;
&rbRatingBoxChart.YaxisBoxNum = 3;
&rbRatingBoxChart.PopUpWidth = 200;
&rbRatingBoxChart.PopUpHeight = 200;
&XAxisArray = CreateArray("Low", "Medium", "High");
&YAxisArray = CreateArray("Low", "Medium", "High");

&rbRatingBoxChart.SetXAxisLabels(&XAxisArray);
&rbRatingBoxChart.SetYAxisLabels(&YAxisArray);
```

4. (Optional) Specify other values for the chart display properties.

   If you do not specify these properties, the following default value will be used:

```
&rbRatingBoxChart.IsDragable = True;
&rbRatingBoxChart.BoxMaxDisplayItems = 3;
&rbRatingBoxChart.NDMaxDisplayDescLength = 25;
&rbRatingBoxChart.ShowNodeDescription = True;
&rbRatingBoxChart.GridLineType = %ChartLine_Solid;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
&rbRatingBoxChart.XAxisTitle = "Performance";
&rbRatingBoxChart.YAxisTitle = "Potential";
&rbRatingBoxChart.NDMaxDisplayDescLength = 15;
&rbRatingBoxChart.BoxMaxDisplayItems = 5;

&rbRatingBoxChart.Height = 400;
&rbRatingBoxChart.Width = 400;
&rbRatingBoxChart.ShowNodeDescription = true;
&rbRatingBoxChart.GridLineType=%ChartLine_Solid;
&rbRatingBoxChart.IsDragable = True;
&rbRatingBoxChart. BoxMaxDisplayItems= 1;
&rbRatingBoxChart. NDMaxDisplayDescLength = 50;
```

5. (Optional) Assign style class names for the chart and x- and y-axis title and labels.

   If you do not specify a style class name, the PeopleTools default style sheet is used.

```
&rbRatingBoxChart.Style = "PSCHARTDEFAULT";
&rbRatingBoxChart.XAxisTitleStyle = "PT_RATBOX_XTTL";
&rbRatingBoxChart.YAxisTitleStyle = "PT_RATBOY_YTTL";
&rbRatingBoxChart.XAxisLabelStyle = "PT_RATBOX_XAXIS";
&rbRatingBoxChart.YAxisLabelStyle = "PT_RATBOX_YAXIS";
```

6. (Optional) Specify title and legend properties.

```
&rbRatingBoxChart.MainTitle = "Development Division";
&rbRatingBoxChart.MainTitleStyle="PT_RATBOX_TITLE"
&rbRatingBoxChart.HasLegend = True;
&rbRatingBoxChart.LegendPosition = %ChartLegend_Bottom;
&LegendArray = CreateArray("Architect", "Engineer", "Director", "Manager",
   "Senior Director", "Vice-President");
&LegendImgArray = CreateArray("PT_ACECUBE", "PT_WF_PERSON","PT_STATUS_ALERT_IC⇒
N",
   "PT_STATUS_ASSIGNED_ICN", "QE_SUCCSORGCHART", "QE_KPERSON");
&rbRatingBoxChart.SetLegend(&LegendArray);
&rbRatingBoxChart.SetLegendImg(&LegendImgArray);
```

7. Set the node data rowset and record.

   The chart refreshes when the SetRBNodeData method is called.

```
/* Set the node data rowset and the node record. */
&rbRatingBoxChart.SetRBNodeData(&rsGrid);
&rbRatingBoxChart.SetRBNodeRecord(Record.QE_RATEBOX_DR);
```

8. Add FieldChange PeopleCode on the fields PTXASISRATINGS and PTYAXISRATINGS if you want to perform other logic after the drag and drop operation.

   This example shows a call to the SetRBNodeData function to redraw the chart the user changes the values in either of these two fields in the component:

```
/* FieldChange PeopleCode for fields PTXAXISRATINGS and PTYAXISRATINGS*/
&rbRatingBoxChart.SetRBNodeData(&rsGrid);
```

Creating a Chart Using an iScript

You can also create a Chart class chart using an iScript. The following example creates a chart, populates it, and then sends the chart URL to a Response object. The complete code sample is shown.

Note: You cannot create a chart from gauge classes, the Gantt class, the OrgChart class, or the RatingBoxChart class using an iScript.

```
Function IScript_GetChartURL()
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
   Local Chart &cChart;
   Local Rowset &rsRowset;
   Local string &sMap;
   Local string &sURL;

   &cChart = CreateObject("Chart");

   &rsRowset = CreateRowset(Record.QE_CHART_RECORD);
   &rsRowset.Fill("where QE_CHART_REGION= :1", "MIDWEST");
   &cChart.SetData(&rsRowset);

   &cChart.Width = 400;
   &cChart.Height = 300;

   &cChart.SetDataYAxis(QE_CHART_RECORD.QE_CHART_SALES);
   &cChart.SetDataXAxis(QE_CHART_RECORD.QE_CHART_PRODUCT);
   &cChart.SetDataSeries(QE_CHART_RECORD.QE_CHART_REGION);

   &cChart.HasLegend = True;
   &cChart.LegendPosition = %ChartLegend_Right;

   &sURL = %Response.GetChartURL(&cChart);
   &sMap = &cChart.ImageMap;

   %Response.Write("<HTML><IMG SRC=");
   %Response.Write(&sURL);
   %Response.Write("  USEMAP=#THEMAP></IMG><MAP NAME=THEMAP>");
   %Response.Write(&sMap);
   %Response.Write("</MAP></HTML>");

End-Function;
```

See "CreateObject" (PeopleTools 8.54: PeopleCode Language Reference).

Complete these steps to create a chart using an iScript:

1. Create the chart object.

   For this example, no chart control is available on a page to be referenced. To create the chart object, use the CreateObject function. The string passed in to the function must be the name of the class you are instantiating. For instance, to instantiate a chart from the Chart class, pass the string “Chart”.

   ```
   &cChart = CreateObject("Chart");
   ```

2. Create a rowset for the chart data and set the chart data.

   The CreateRowset function creates a standalone rowset data structure. Use the Fill method to populate the empty rowset with data. The SetData method associates the rowset data with the chart.

   ```
   &rsRowset = CreateRowset(Record.QE_CHART_RECORD);
   &rsRowset.Fill("where QE_CHART_REGION= :1", "MIDWEST");
   &cChart.SetData(&rsRowset);
   ```

3. Set the height and width of the chart.

   Because the chart is not associated with a chart control on a page, you have to specify the size of the chart image to be generated using the Height and Width properties. The unit of measurement for both of these properties is pixels.

   ```
   &cChart.Width = 400;
   &cChart.Height = 300;
   ```

4. Set the data axes, series, and legend for the chart.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

As with all charts, you must set the data axes. If necessary for your data, also set the data series and the legend.

```
&cChart.SetDataYAxis(QE_CHART_RECORD.QE_CHART_SALES);
&cChart.SetDataXAxis(QE_CHART_RECORD.QE_CHART_PRODUCT);
&cChart.SetDataSeries(QE_CHART_RECORD.QE_CHART_REGION);

&cChart.HasLegend = True;
&cChart.LegendPosition = %ChartLegend_Right;
```

5. Generate the URL for the chart.

   Use the GetChartURL method of the Response class to generate the URL that will reference the chart data.

```
&sURL = %Response.GetChartURL(&cChart);
```

6. Generate the image map.

   Use the ImageMap property to generate the image map for the chart. The Response object uses this value to draw the map.

```
&sMap = &cChart.ImageMap;
```

7. Create the response chart.

   Use the Write Response class method to generate the chart. Note that first, the data is set using the URL generated with GetChartURL, and then the image map is used.

```
%Response.Write("<HTML><IMG SRC=");
%Response.Write(&sURL);
%Response.Write("  USEMAP=#THEMAP></IMG><MAP NAME=THEMAP>");
%Response.Write(&sMap);
%Response.Write("</MAP></HTML>");
```

Note: If one or more labels does not render in the chart, increase the width of the chart, use shorter label text, or reduce the data set being charted.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Chapter 15

Component Interface Classes

Understanding Component Interface Class

Component Interfaces are the focal points for externalizing access to existing PeopleSoft components. They provide realtime synchronous access to the PeopleSoft business rules and data associated with a component outside the PeopleSoft online system. Component Interfaces can be viewed as "black boxes" that encapsulate PeopleSoft data and business processes, and hide the details of the structure and implementation of the underlying page and data.

Component Interfaces are one of the many APIs that PeopleSoft provides for enabling integration with other systems.

A Component Interface maps to one, and only one, PeopleSoft component. The *Component Interface object*, instantiated from a session object, is created at runtime to access the data specified by the Component Interface.

When you instantiate a Component Interface object:

- All the PeopleCode programs associated with the record fields, pages, component, and so on, and
- The runtime component processor still perform all of the work that they do in the online environment.

The exceptions are any GUI manipulation found in a PeopleCode program, and search dialog specific processing.

Component Interfaces are programmable through a C interface, an OLE/COM or C/C++ interface, and through PeopleCode. Application Engine programs, message notification programs, or any other PeopleCode programs are able to use Component Interfaces.

Like a component, you create the structure of a Component Interface in Application Designer, then at runtime, you populate the structure with data. This document is concerned with the runtime portion of a Component Interface.

When you populate a Component Interface with data, the first thing you fill out are its keys, as you would in a component. These can be keys for getting an existing instance of the data or for creating a new instance of the data.

In addition to keys, a Component Interface is composed of *properties* and *methods*.

- Component Interface *properties* provide access to the data in a component buffer.
- Component Interface *methods* are functions that can be called to perform operations on a Component Interface.

There are two types of both methods and properties: standard and user-defined. Standard properties and methods are provided automatically when you create a Component Interface. They perform operations common to all Component Interfaces, such as indicating what mode to operate the Component Interface,

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

saving, or creating a Component Interface. User-defined properties are the specific record fields that an application developer has chosen to expose to an external system with the Component Interface. User-defined methods are PeopleCode programs that an application developer can write to perform operations on a Component Interface. Each is specific to that Component Interface.

You can instantiate a Component Interface object only from a session object. Through the session object you can control access to the Component Interface, check for errors, control the runtime environment, and so on.

Related Links

Reusing Existing Code
Understanding Session Class
Understanding Component Interface Class

Life Cycle of a Component Interface

At runtime, there are certain things you want to do with a Component Interface, such as getting an instance of it, populating it with data, and so on. The following is an overview of this process. These steps are expanded in other sections.

1. Execute the GetCompIntfc method on the PeopleSoft session object to get a Component Interface.
2. Set the key values for the Component Interface object. If the keys you specify don't uniquely describe a component (partial keys), proceed to step 3. If the keys uniquely describe a component, skip to step 4.
3. Do *one* of the following:
   - Execute the Find standard method on the Component Interface. This returns a collection of Component Interfaces with their key values filled out. The user can then select the unique Component Interface they want.
   - Execute either the Get or Create standard method to instantiate the Component Interface (populate it with data.)
4. Get property values, set property values, or execute user-defined methods. Setting a property value will fire the standard PeopleSoft business rules for the field associated with the property (any PeopleCode program associated with FieldChange, RowInsert, and so on.)
5. Execute the Save standard method to fire the standard PeopleSoft save business rules (any PeopleCode programs associated with SavePreChange, WorkFlow, and so on.) and commit any changes to the database.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

6. At any point, the standard method Cancel can be executed to reset the Component Interface to its state in step 1.

Image: Component interface life cycle

The following is a flow chart diagram of Component interface life cycle such as getting an instance of it, populating it with data, and so on.

Setting Component Interface Keys

The keys for a Component Interface are based on the key fields of the underlying component. There can be different types of keys for a Component Interface.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- CREATEKEYS: A list of the primary key fields of the search record specified to be used in Add mode for the component. This list is automatically generated.
- GETKEYS: A list of the primary (required) key fields on the search record. This list is automatically generated.
- FINDKEYS: A list of primary and alternate key fields on the primary search record for the component.

If the Component Interface has CREATEKEYS, these are the keys you must set before you execute the Create() method to create a new instance of the data. If the Component Interface doesn't have CREATEKEYS, use the GETKEYS to specify a new instance of the data.

Use either the GETKEYS or FINDKEYS to specify an existing instance of the data.

To set key values, use the field names listed under GETKEYS, CREATEKEYS or FINDKEYS like properties on the Component Interface object. The following example sets the CREATEKEYS values to create a new instance of the data.

```
&MYCI = GetCompIntfc(CompIntfc.EXPRESS_ISSUE);
&MYCI.BUSINESS_UNIT = "H01B";
&MYCI.INTERNAL_FLG = "Y";
&MYCI.ORDER_NO = "NEXT&rsquo;;
&MYCI.Create();
```

Standard and User-Defined Component Interface Methods

Every Component Interface comes with a standard set of methods:

- Cancel()
- Create()
- Find()
- Get()
- Save()

Use these methods during runtime to affect the data of the Component Interface.

The application developer can, at design time, disable any of these methods for the Component Interface.

In addition, an application developer can write their own methods. These methods are written as Functions using Component Interface PeopleCode. For example, suppose you wanted to be able to copy an instance of Component Interface data. You might write your own Clone method.

Note: User-defined method names must *not* be named *GetPropertyName*. The C header for Component Interfaces creates functions with that name so you can access each property. If you create your own *GetPropertyName* functions, you receive errors at runtime. User-defined methods can take only simple types of arguments (such as number, character, and so on) because user-defined methods can be called from C/C++ or COM as well as from PeopleCode. PeopleCode can use more complex types (like rowset, array, record, and so on), but these types of arguments are unknown to C/C++ or COM.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

Component Interface Class Methods

Component Interface Class Properties

"Creating User-Defined Methods" (PeopleTools 8.54: Component Interfaces)

Accessing Component Interface Standard Properties

Every Component Interface comes with a standard set of properties. These properties can be divided as follows:

Properties that affect how the Component Interface is executed

The following properties affect how a component interface is executed:

- EditHistoryItems
- GetHistoryItems
- InteractiveMode

These properties must be set before the Component Interface is populated with data. That is, you must set these properties before you use the Get or Create methods.

EditHistoryItems and GetHistoryItems work together to determine how data is accessed:

- If EditHistoryItems is False (the default) and GetHistoryItems is True, you access the data in the Component Interface in a similar manner as if you were accessing a component in update/display All mode. This means all history rows are returned, however, you can edit rows only with a date set in the future.
- If EditHistoryItems is True and GetHistoryItems is True, you access the data in the Component Interface in a similar manner as if you were accessing a component in correction mode. This means all history rows are returned, and you can edit them.
- If GetHistoryItems is False, you access the data in the Component Interface in a similar manner as if you were accessing a component in update mode. The EditHistoryItems has no effect when GetHistoryItems is False.

  InteractiveMode causes the Component Interface to emulate an online component. For example, if you set a value for a field in a Component Interface and you have set InteractiveMode to True, then any FieldChange PeopleCode programs associated with that field fire as soon as you set that value.

Properties that return information about the structure of the Component Interface

The following properties return information about the structure of the Component Interface:

- CreateKeyInfoCollection
- FindKeyInfoCollection
- GetKeyInfoCollection
- PropertyInfoCollection

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

Component Interface Class Properties

Accessing User-Defined Component Interface Properties

Every user-defined property in a Component Interface *definition* can be used like a property on the *object* instantiated from that Component Interface at runtime.

For example, the following Component Interface definition has RETURN_DT defined as one of its properties.

Image: RETURN_DT Component Interface property highlighted

This example illustrates the fields and controls on the RETURN_DT Component Interface property highlighted. You can find definitions for the fields and controls later on this page.

At runtime, you can use PeopleCode to assign a value to that property (field), or to access the value of that field.

```
&MYCI.RETURN_DT = "05/05/2000";

/*  OR  */

&DATE = &MYCI.RETURN_DT;
```

Data Type of a Component Interface Object

Component Interfaces are declared as type ApiObject. For example,

```
Local ApiObject &MYCI;
```

Note: Component Interface objects can be declared only as Local.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Scope of a Component Interface Object

A Component Interface can be instantiated from PeopleCode, from a Visual Basic program, from Java, COM and C/C++.

This object can be used anywhere you have PeopleCode, that is, in an application class, Application Engine PeopleCode, record field PeopleCode, and so on.

If you're instantiating a Component Interface from an online page, after you finish working with the component, you may want to refresh your page. The Refresh method, on a rowset object, reloads the rowset (scroll) using the current page keys. This causes the page to be redrawn. GetLevel0().Refresh() refreshes the entire page. If you want a particular scroll only to be redrawn, you can refresh just that part.

Considerations Using Component Interfaces and Related Languages

If you update a field using a Component Interface through an external program (such as Java, VB, and so on) the Related Language Table gets updated, even if they are using a base language of ENG.

Considerations Using Component Variables With Component Interfaces

A component variable is scoped locally to its component or its Component Interface. This means that you cannot use a component variable to share data between a component and a Component Interface. In order to share information between components, use global variables.

If your page (component) calls a Component Interface (using the existing session), that in turn initializes a component variable, that component variable is shared with the calling component. When the Component Interface is closed, the component variable is no longer in scope.

When the calling component is closed, any component scoped variables created by it or by the Component Interface go out of scope.

Related Links

Refresh

CompIntfPropInfoCollection Object Properties

Implementing a Component Interface

After you create your Component Interface definition, you can use PeopleCode to access it. This PeopleCode can be long and complex. Rather than write it directly, you can drag and drop the Component Interface definition from Application Designer Project View into an open PeopleCode edit pane. Application Designer analyzes the definition and generates initial PeopleCode as a template, which you can modify.

You can also access your Component Interface using COM. You can automatically generate a Visual Basic or a C template, similar to the PeopleCode template, to get you started.

The following are the usual actions that you perform with a Component Interface:

- Create a new instance of data

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- Get an existing instance of data
- Retrieve a list of instances of data

The following procedures cover each of these actions in more detail.

Another standard action is inserting or deleting a row of data (an item). This involves traversing a Component Interface (going from level zero to level one, from level one to level two, and so on) and accessing data collections.

You may want to work with effective-dated information. There are several properties you can set to allow you to do this.

In addition to these standard actions, you can also look at the structure of a Component Interface.

Related Links

Create a New Instance of Data Example
Getting an Existing Instance of Data Example
Retrieving a List of Instance of Data Example
Traversing a Component Interface and Using Data Collections
Working With Effective-Dated Data
Accessing the Structure of a Component Interface

Component Interface Methods and Timeouts

The file pstools.properties controls when a Component Interface method times out. If you're having problems with methods timing out, you may want to change the values in this file. This file is located in the default directory for the application you're running. If this file isn't in this directory, copy it into the directory before you make your changes to it.

Traversing a Component Interface and Using Data Collections

The data in a Component Interface can be contained in a hierarchy: like the page it's built on, there may be data at level zero, level one, level two, and so on.

Each level of data in a Component Interface is known as a collection, such as:

```
level zero

  -- level one (Collection)

    -- Level 2 (Collection)
```

A *collection* is a set of similar things, like a group of already existing Component Interfaces. Most collections have the same standard properties and methods, with some additional ones specific to that collection. For example, all collections have the property *Count*, which indicates how many items are in that collection, but only a data collection has the method *ItemByKeys*.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

A *data collection* is the collection of data, available at runtime or during test mode, associated with a particular scroll (or record.) The data collection object returns information about every *row of data* (item) that is returned for that record at runtime.

To access the level two collection, in general, you could use the following:

```
&Level_1 = &CI.Level_1;
&Level_1_Item = &Level_1.Item(ItemNumber);

&Level_2 = &Level_1_Item.Level_2;
```

Image: Sample Component Interface with collection highlighted

This example illustrates the fields and controls on the Sample Component Interface with collection highlighted. You can find definitions for the fields and controls later on this page.

This example shows a Component Interface with a two-level hierarchy, that is, *two* data collections: EMPL_CHECKLIST and EMPL_CHKLST_ITM. To get a data collection for the first level, use the following code:

```
&Level1 = &MYCI.EMPL_CHECKLIST;
```

To access the secondary scroll (EMPL_CHKLST_ITM) you have to get the appropriate row (item) of the upper level scroll first:

```
&Level1 = &MYCI.EMPL_CHECKLIST;
&Item = &Level1.Item(1);
&Level2 = &Item.EMPL_CHKLST_ITM;
```

Note: Scrolls represent a hierarchical order. You must get the first level row that contains the secondary scroll *before* you can access the secondary scroll.

Every data collection has a set of methods and standard properties.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

Inserting or Deleting a Row of Data Example
Data Collection Methods
Data Collection Properties
"Understanding Data Buffer Access" (PeopleTools 8.54: PeopleCode Developer's Guide)

Working With Effective-Dated Data

When you work with effective-dated data, use some combination of the following methods:

- CurrentItem
- GetEffectiveItem

Both these methods return an item, however, there are some differences:

- The CurrentItem method takes no parameters, so it bases the item it returns on the *current system date.*
- The GetEffectiveItem method bases the item it returns on a *user-provided date*. They all perform the same logic, they just use a different date.

Note: To show all history for an effective-dated collection, you must set GetHistoryItems to True before you populate the Component Interface.

Related Links

CurrentItem
GetEffectiveItem
GetHistoryItems
Inserting Effective-Dated Data Example
Inserting Effective-Dated Data Example Using Visual Basic

How a Developer Uses GetEffectiveItem

If a user is making an update to an effective-dated record, they don't always want to insert a row at the end.

Suppose the database contained the following data:

EMPLID	*EFFDT*	*SEQNO*
8000	3/1/99	0
8000	7/1/99	0
8000	9/1/99	0
8000	12/1/99	0

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Now suppose the user wants to enter info with EFFDT of 11/1/99. If they were looking at a PeopleSoft component, they would visually scan to see where that date falls and then press ALT+7 and ENTER at the row that they want to insert after.

GetEffectiveItem enables you to pass in the correct effective date, instead of having to loop through every item in the collection doing a comparison, looking for the correct item.

Why Can't it Just Go at the End?

The InsertItem method simulates pressing ALT+7 and ENTER online to insert a row in a scroll. Part of the logic that occurs in the Component Processor is that if the scroll is effective-dated, the ALT+7 and ENTER carries the values forward from the previous row. This functionality is still there if you use InsertItem at the end of the collection, but the values may be incorrect.

Reusing Existing Code

One of the advantages of using a Component Interface is that it enables you to reuse existing PeopleCode and business logic. However, a Component Interface isn't exactly equivalent to a component, which means there are a few key areas in which you should expect differences in behavior between a Component Interface and the component it's based on. This section discusses the differences in:

- Search dialog processing
- Event and function behavior

Differences in Search Dialog Processing

When you run a Component Interface, the *SearchInit*, *SearchSave*, and *RowSelect* events don't fire. This means that any PeopleCode associated with these events won't run. The first event to run is *RowInit*.

Differences in PeopleCode Event and Function Behavior

PeopleCode events and functions that relate exclusively to the page interface (the GUI) and online processing can't be used by Component Interfaces. These include:

- Menu PeopleCode and pop-up menus.

  The ItemSelected and PrePopup PeopleCode events are not supported. In addition, the DisableMenuItem, EnableMenuItem, and HideMenuItem functions aren't supported.

- Transfers between components, including modal transfers.

  The DoModal, EndModal, IsModal, Transfer, TransferPage, DoModalComponent, TransferNode, TransferPortal, and IsModalComponent functions cannot be used.

- Cursor position.

  SetControlValue cannot be used.

- WinMessage cannot be used.
- Save in the middle of a transaction.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

DoSave cannot be used.

- The page Activate event cannot be used.

When executed using a component interface, these functions do nothing and return a default value. In addition, using the Transfer function terminates the current PeopleCode program.

For the unsupported functions, you should put a condition around them, testing whether there's an existing Component Interface.

```
If %ComponentName Then
   /* process is being called from a Component Interface */
   /* do CI specific processing */
Else
   /* do regular processing */
   .  .  .
End-if;
```

Using %Menu Conditions

If you associate a Component Interface definition with a menu in Application Designer, a PeopleCode program that conditionally checks for that menu runs when the Component Interface is executed. For example, suppose you associate a Component Interface with the MP_HR_MENU. The following PeopleCode program, if called from that Component Interface, executes:

```
If %Menu = MP_HR_MENU Then
```

Related Links

"Associating Component Interfaces with Menus" (PeopleTools 8.54: Component Interfaces)

Session Class Methods

Component Interfaces don't have any built-in functions. They are instantiated from the Session class.

This section discusses the Session class methods used to instantiate Component Interfaces. The methods are discussed in alphabetical order.

FindCompIntfcs

Syntax

FindCompIntfcs([*ComponentName*])

Description

The FindCompIntfcs method, used with the Session object, returns a reference to a Component Interface collection, filled with zero or more Component Interfaces. The *ComponentName* parameter takes a string value. You can use a partial value to limit the set of Component Interfaces returned. You can also specify a null value, that is, two quotation marks with no space between them, ("") to return the entire list of Component Interfaces available.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Using the FindCompIntfcs method is equivalent to using File, Open, and selecting Component Interface in Application Designer.

Example

In the following example, a partial key was used to open all components starting with "APP".

```
Local ApiObject &MYSESSION;
Local ApiObject &MYCI;

&MYSESSION = %Session;
&MYCICOLL = &MYSESSION.FindCompIntfcs("APP");
&MYCI = &MYCICOLL.First();
```

GetCompIntfc

Syntax

GetCompIntfc([**COMPINTFC.**]*ComponentName*)

Description

The GetCompIntfc method, used with the session object, returns a reference to a Component Interface. *ComponentName* when used by itself takes a string value. If you use COMPINTFC.*componentname* it isn't a string value: it's a constant that automatically is renamed in your code if the Component Interface definition is ever renamed. You must specify an existing Component Interface, otherwise you receive a runtime error.

Example

```
Local ApiObject &MYSESSION;
Local ApiObject &MYCI;

&MYSESSION = %Session;
&MYCI = &MYSESSION.GetCompIntfc(COMPINTFC.PERSONAL_DATA_BC);
```

The following example uses the '@' operator to dynamically call a Component Interface from PeopleCode.

```
&MYCI = &MYSESSION.GetCompIntfc(@("CompIntfc." | &CIname));
```

ValidateCompIntfc

Syntax

ValidateCompIntfc(*ComponentInterfaceName*)

Description

The ValidateCompIntfc method, used with the Session object, returns an integer value indicating whether the validation is successful. The validation fails if no component interface exists with the given name. The primary purpose of this method is to validate the successful compilation of all PeopleCode programs associated with both the component and the component interface. In addition, this method verifies other relationships of the component interface to the component, such as, but not limited to checking whether the component interface:

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- Contains a reference to an invalid component.
- Is defined with CREATEKEYS, but the component does not allow the add action.
- Is defined with CREATEKEYS, but the specified field is not a search key.
- Has a reference to an invalid field.
- Has a reference to an invalid record.
- Is defined with FINDKEYS, but the specified field is not a search key or an alternate search key.
- Is defined with GETKEYS, but the specified field is not a search key.
- Has references to a search or add record that is invalid.

Parameters

ComponentInterfaceName Specify the component interface name as a string.

Returns

An integer value indicating whether the validation is successful: 0 indicates success; any non-zero value indicates failure.

Example

In the following example, a component interface with name "DEMOAPP_CI" is validated.

```
Local ApiObject &MYSESSION;
Local integer &nRet;

&MYSESSION = %Session;
&nRet = &MYSESSION.ValidateCompIntfc("DEMOAPP_CI");

If &nRet <> 0 Then
   /* Failure Case */
Else
   /* Success Case */
End-If;
```

Component Interface Collection Methods

A Component Interface collection is a list of the available Component Interfaces. An equivalent list is generated by starting Application Designer, selecting File, Open, Component Interface.

You get a Component Interface collection by using the FindCompIntfcs method with a session object.

First

Syntax

First()

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

The First method returns the first Component Interface in the Component Interface collection object executing the method. This returns the structure of the Component Interface with only the key fields filled in. The rest of the data is not present. To populate the Component Interface with data, you must set the key values and use the Get method.

Example

```
&MYCI = &CICOLLECTION.First();
```

Item

Syntax

Item(*number*)

Description

The Item returns the Component Interface that exists at the number position in the Component Interface collection executing the method. This returns the structure of the Component Interface with only the key fields filled in. The rest of the data is not present. To populate the Component Interface with data, you must set the key values and use the Get method. *number* takes a number value.

Example

```
For &I = 1 to &COLLECTION.Count;
&MYCI = &COLLECTION.Item(&I);
/* do processing */
End-For;
```

Next

Syntax

Next()

Description

The Next method returns the next Component Interface in the Component Interface collection object executing the method. You can use this method only after you have used either the First or Item methods: otherwise the system doesn't know where to start. This returns the structure of the Component Interface with only the key fields filled in. To populate the Component Interface with data, you must set the key values and use the Get method.

Example

```
&MYCI = &COLLECTION.Next();
```

Component Interface Collection Property

This section discusses the Count property.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Count

Description

This property returns the number of Component Interfaces in the Component Interface collection, as a number.

This property is read-only.

Example

```
&COUNT = &MYCI_COLLECTION.Count;
```

Component Interface Class Methods

This section discusses the Component Interface class methods. The methods are discussed in alphabetical order.

Cancel

Syntax

Cancel()

Description

The Cancel method cancels the instance of the Component Interface object executing the method, rolling back any changes that were made. This sets the Component Interface state to the same state it was in immediately after it was created by GetCompIntfc. This closes the Component Interface.

Parameters

None.

Returns

A Boolean value: True if component was successfully cancelled, False otherwise.

CopyRowset

Syntax

CopyRowset(*&Rowset* [, *InitialRow*] [, *record_list*]);

Where *record_list* is a list of record names in the form:

```
[RECORD.source_recname1, RECORD.target_recname1
[, RECORD.source_recname2, RECORD.target_recname2]].  .  .
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

The CopyRowset method copies the specified rowset object to the Component Interface executing the method, copying like-named record fields and data collections (child rowsets) at corresponding levels. If pairs of source and destination record names are given, these are used to pair up the records and data collections *before* checking for like-named record fields.

CopyRowset uses the Page Field order when copying properties. This helps ensure that dependent fields are set in the required order.

Note: This method works in PeopleCode only. This method uses the names of the records in the collection, *not* the name you may give the collection when you create the Component Interface.

If there are blanks in *source* rowset or record, they are copied over to the Component Interface only if the field's IsChanged property is set to True. Otherwise blanks are *not* copied.

Use this method when you are using a Component Interface to verify the data in your application message.

Note: The structure of the rowset you're copying data from must exactly match the existing rowset structure, with the same records at level zero, 1, 2, and so on. CopyRowset is intended to be used with a notification process, that is, with message data. As all notifications work only in two-tier mode, CopyRowset works only in two-tier mode.

Parameters

&Rowset Specify an existing, instantiated rowset object that contains data.

InitialRow Specify the initial transaction row to begin with. This parameter provides a quick way to loop through a rowset that has multiple level zero rows. The default value for this parameter is 1.

record_list Specify a list of source and target record names. All *source_recnames* are records being copied *from*, in the rowset object being copied from. All *target_recnames* are records being copied *to*, in the Component Interface being copied to.

Returns

None.

Example

The following example would be in your notification PeopleCode. The Exit(1) causes all changes to be rolled back, and the message is marked with the status ERROR so you can correct it.

```
Local message &MSG;
Local ApiObject &SESSION;
Local ApiObject &PO;
Local rowset &ROWSET;

&MSG = %IntBroker.GetMessage();
&ROWSET = &MSG.GetRowset();

&SESSION = %Session;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
If &SESSION <> NULL Then
/* Session connected correctly */
/* Set key values to create component */
&PO = &SESSION.GetCompIntfc(COMPINTFC.PO);
&PO.BU = &MSG(&I).PO_HDR.BU.Value;
&PO.PO_ID = &MSG(&I).PO_HDR.PO_ID.Value;
&PO.Create();

&PO.CopyRowset(&ROWSET);
If NOT (&PO.Save()) Then
   Exit(1);
End-if;
Else
/* do error processing */
End-If;
```

The following example loops through all the transactions of a message rowset.

```
Local message &MSG;
Local ApiObject &SESSION;
Local ApiObject &CI;
Local rowset &ROWSET;

&MSG = %IntBroker.GetMessage();
&ROWSET = &MSG.GetRowset();


&SESSION = %Session;
If &SESSION <> Null Then)
   &CI = &SESSION.GetCompIntfc(CompIntfc.VOL_ORG);
   &I = 0;
   While (&I < &ROWSET.RowCount)
      &I = &I + 1;
      &CI.VOLUNTEER_ORG = &ROWSET.GetRow(&I).VOLNTER_ORG_2.  VOLUNTEER_ORG.Value;
      If &CI.Create() Then
         If &CI.CopyRowset(&ROWSET, &I, Record.VOLNTER_ORG_TBL, Record.VOLNTER_ORG_⇒
TBL) Then

         /* App specific processing */

            If Not &CI.Save() Then
               Winmessage("Save Failed");
               /* Other app specific processing */
            End-If;
         End-If;
      End-If;
   &CI.Cancel();
   End-While;
End-If;
```

CopyRowsetDelta

Syntax

CopyRowsetDelta(*&Rowset* [, *InitialRow*] [, *record_list*]);

Where *record_list* is a list of record names in the form:

```
[RECORD.source_recname1, RECORD.target_recname1
[, RECORD.source_recname2, RECORD.target_recname2]].  .  .
```

Description

The CopyRowsetDelta method copies the changed rows in the specified rowset object to the Component Interface executing the method, copying like-named record fields and data collections (child rowsets) at

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

corresponding levels. If pairs of source and destination record names are given, these are used to pair up the records and data collections *before* checking for like-named record fields.

Note: This method works in PeopleCode only. This method uses the names of the records in the collection, *not* the name you give the collection when you create the Component Interface.

If there are blanks in *source* rowset or record, they are copied over to the Component Interface only if the field's IsChanged property is set to True. Otherwise blanks are *not*copied.

You will generally use this method with a Component Interface to verify data from a message.

Note: CopyRowsetDelta is intended for a notification process, that is, with message data. As all notifications work only in two-tier mode, CopyRowsetDelta works only in two-tier mode.

If the rowset you're copying from is a message rowset, the CopyRowsetDelta method uses the AUDIT_ACTN field in the PSCAMA table in the message to know whether the row is to be inserted, updated, or deleted inside the Component Interface.

If the rowset you're copying from *is not* a message rowset, that rowset must have the same structure as a message, that is, it must have a PSCAMA record with an AUDIT_ACTN field on every level of the rowset.

Warning! CopyRowsetDelta uses a record's keys to locate the target row to change for all audit actions other than Add. CopyRowsetDelta actions (other than Add) therefore work only on rowsets that have keys *that uniquely identify all rows in the rowset*. Rowsets that do *not*distinguish between rows using a key field will be updated in an unpredictable fashion.

Considerations Using CopyRowsetDelta with Effective-Dated Rowsets

If a message data row inserted using a PSCAMA Audit action of "A" belongs to an effective dated scroll containing child scrolls, the insertion of the parent row causes child rows of the previous effective-dated row to be copied over, and their effective date is updated with that of the inserted parent.

If the message also contains a child row being inserted with a PSCAMA Audit action of "A", the component interface being populated will end up having two child rows: the one inserted as part of the Effective-dated processing and the one inserted using the PSCAMA Audit action "A" in the message.

Parameters

&Rowset	Specify an existing, instantiated rowset object that contains data.
InitialRow	Specify the initial transaction row to begin with. This parameter provides a quick way to loop through a rowset that has multiple level zero rows. The default value for this parameter is 1.
record_list	Specify a list of source and target record names. All *source_recnames* are records being copied *from*, in the rowset object being copied from. All *target_recnames* are records being copied *to*, in the Component Interface being copied to.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

None.

Example

The following PeopleCode would exist in your notification process. The Exit(1) causes all changes to be rolled back, and the message is marked with the status ERROR so you can correct it.

```
Local Message &MSG;
Local ApiObject &SESSION;
Local ApiObject &PO;
Local Rowset &ROWSET;

&MSG = %IntBroker.GetMessage();
&ROWSET = &MSG.GetRowset();

&SESSION = %Session;

If &SESSION <> Null Then
/* Session connected correctly */
/* Set key values to get component */
&PO = &SESSION.GetCompIntfc(COMPINTFC.PO);
&PO.BU = &MSG(&I).PO_HDR.BU.Value;
&PO.PO_ID = &MSG(&I).PO_HDR.PO_ID.Value;
&PO.Get();


&PO.CopyRowsetDelta(&ROWSET);
If NOT (&PO.Save()) Then
   Exit(1);
End-if;
Else
   /* do error processing */
End-If;
```

Related Links

"PSCAMA" (PeopleTools 8.54: Integration Broker)

CopySetupRowset

Syntax

CopySetupRowset(*&Rowset* [, *InitialRow*] [, *record_list*]);

Where *record_list* is a list of record names in the form:

RECORD.*source_recname*, RECORD.*target_recname*

Description

The CopySetupRowset method is used to copy a setup table application message to a Component Interface. A setup table has the same record at level zero and level one, while a Component Interface has only a single copy of a record. This method copies the contents of the message (at level zero) to the first level collection (level one) of the Component Interface.

The CopySetupRowset method copies *like-named* record fields. If a pair of source and destination record names are given, these are used to pair up the records and data collections *before* checking for like-named record fields.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Note: This method works in PeopleCode only. This method uses the names of the records in the collection, *not* the name you may give the collection when you create the Component Interface.

If there are blanks in *source* rowset or record, they are copied over to the Component Interface only if the field's IsChanged property is set to True. Otherwise blanks are *not* copied.

Note: CopySetupRowset is for a notification process, that is, with message data. As all notifications work only in two-tier mode, CopySetupRowset works only in two-tier mode.

Parameters

&Rowset Specify an existing, instantiated rowset object that contains data.

InitialRow Specify the initial transaction row to begin with. This parameter provides a quick way to loop through a rowset that has multiple level zero rows. The default value for this parameter is 1.

record_list Specify source and target record names. The *source_recname* is the record being copied *from*, in the rowset object being copied from. The *target_recname* is the record being copied *to*, in the Component Interface being copied to.

Returns

None.

Example

The following example would be in your Notification PeopleCode.

```
Local ApiObject &SESSION;
Local ApiObject &PSMESSAGES;

Local ApiObject &CI;

Local Message &MSG;
Local Rowset &RS;

&SESSION = %Session;
&PSMESSAGES = &SESSION.psmessages;

&MSG = %IntBroker.GetMessage();
&RS = &MSG.GetRowset();

&CI = &SESSION.getcomponent(Component.VOL);

/** Set Business Component Properties **/
&CI.gethistoryitems = True;
/*&CI.InteractiveMode = True;*/
/*&CI.stoponfirsterror = True;*/

For &TRANSACTION = 1 To &RS.RowCount

   &CI.VOLUNTEER_ORG = &RS(&TRANSACTION).VOLNTER_ORG_TBL.VOLUNTEER_ORG.Value;

   /* note: You can achieve better performance if you add code here to check  if th⇒
e keys are the same L0 keys as the last time  through the loop and, if so,skip the ⇒
Get/Create section. */

   If Not &CI.create() Then
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
      &PSMESSAGES.DeleteAll();
      If Not &CI.get() Then
         /** Check Error Messages **/
         For &I = 1 To &PSMESSAGES.count
            &TYPE = &PSMESSAGES.item(&I).type;
            &TEXT = &PSMESSAGES.item(&I).text;
         End-For;
         Exit(1);

      End-If;
   End-If;

   If Not &CI.CopySetupRowset(&RS, &TRANSACTION) Then
      /** Check Error Messages **/
      For &I = 1 To &PSMESSAGES.count
         &TYPE = &PSMESSAGES.item(&I).type;
         &TEXT = &PSMESSAGES.item(&I).text;
      End-For;
      Exit(1);
   End-If;

   If Not &CI.Save() Then
      /** Check Error Messages **/
      For &I = 1 To &PSMESSAGES.count
         &TYPE = &PSMESSAGES.item(&I).type;
         &TEXT = &PSMESSAGES.item(&I).text;
      End-For;
      Exit(1);
   End-If;

   &CI.Cancel();
End-For;
```

Related Links

CopySetupRowsetDelta

CopyRowset

CopySetupRowsetDelta

Syntax

CopySetupRowsetDelta(*&Rowset* [, *InitialRow*] [, *record_list*]);

Where *record_list* is a list of record names in the form:

RECORD.*source_recname*, RECORD.*target_recname*

Description

The CopySetupRowsetDelta method is used to copy a setup table with *changed* rows in an application message to a Component Interface. A setup table has the same record at level zero and level one, while a Component Interface has only a single copy of a record. This method copies the contents of the message (at level zero) to the first level collection (level one) of the Component Interface.

Note: This method works in PeopleCode only. CopySetupRowsetDelta copies all the like-named fields from the changed *row* into the message. It is *not* copying only the changed fields.

The CopySetupRowsetDelta method copies *like-named* record fields, in those rows where the IsChanged property is True. If a pair of source and destination record names are given, these are used to pair up the records and data collections *before* checking for like-named record fields.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Note: This method uses the names of the records in the collection, *not*the name you may give the collection when you create the Component Interface.

If there are blanks in *source* rowset or record, they are copied over to the Component Interface only if the field's IsChanged property is set to True. Otherwise blanks are *not*copied.

Note: CopySetupRowsetDelta is for a notification process, that is, with message data. As all notifications work only in two-tier mode, CopySetupRowsetDelta works only in two-tier mode.

Warning! CopySetupRowsetDelta uses a record's keys to locate the target row to change for all audit actions other than Add. CopySetupRowsetDelta actions (other than Add) therefore work only on rowsets that have keys that *uniquely identify all rows in the rowset*. Rowsets that do *not*distinguish between rows using a key field will be updated in an unpredictable fashion.

Parameters

&Rowset Specify an existing, instantiated rowset object that contains data.

InitialRow Specify the initial transaction row to begin with. This parameter provides a quick way to loop through a rowset that has multiple level zero rows. The default value for this parameter is 1.

record_list Specify source and target record names. The *source_recname* is the record being copied *from*, in the rowset object being copied from. The *target_recname* is the record being copied *to*, in the Component Interface being copied to.

Returns

None.

Example

```
Local ApiObject &SESSION;
Local ApiObject &PSMESSAGES;

Local ApiObject &CI;

Local Message &MSG;
Local Rowset &RS;

&SESSION = %Session;
&PSMESSAGES = &SESSION.psmessages;

&MSG = %IntBroker.GetMessage();
&RS = &MSG.GetRowset();

&CI = &SESSION.getcomponent(Component.VOL);

/** Set Business Component Properties **/
&CI.gethistoryitems = True;
/*&CI.InteractiveMode = True;*/
/*&CI.stoponfirsterror = True;*/

For &TRANSACTION = 1 To &RS.RowCount

   &CI.VOLUNTEER_ORG = &RS(&TRANSACTION).VOLNTER_ORG_TBL.VOLUNTEER_ORG.Value;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
   /* note: You can achieve much better performance if you add code here to check  ⇒
if the keys are the same L0 keys as the last time through the loop and, if so, skip⇒
 the Get/Create section. */

   If Not &CI.create() Then
      &PSMESSAGES.DeleteAll();
      If Not &CI.get() Then
         /** Check Error Messages **/
         For &I = 1 To &PSMESSAGES.count
            &TYPE = &PSMESSAGES.item(&I).type;
            &TEXT = &PSMESSAGES.item(&I).text;
         End-For;
         Exit(1);

      End-If;
   End-If;

   If Not &CI.CopySetupRowsetDelta(&RS, &TRANSACTION) Then
      /** Check Error Messages **/
      For &I = 1 To &PSMESSAGES.count
         &TYPE = &PSMESSAGES.item(&I).type;
         &TEXT = &PSMESSAGES.item(&I).text;
      End-For;
      Exit(1);
   End-If;

   If Not &CI.Save() Then
      /** Check Error Messages **/
      For &I = 1 To &PSMESSAGES.count
         &TYPE = &PSMESSAGES.item(&I).type;
         &TEXT = &PSMESSAGES.item(&I).text;
      End-For;
      Exit(1);
   End-If;

   &CI.Cancel();
```

Related Links

CopySetupRowset

CopyRowsetDelta

Create

Syntax

Create()

Description

The Create method associates the Component Interface object executing the method with a new, open Component Interface that matches the key values that were set prior to using the Create method. If there are CREATEKEYS values associated with the Component Interface, these are the values you must set. If there are no CREATEKEYS values, you must set the required GETKEYS values instead. All keys required for creating a new Component Interface must be set before using the Create method, otherwise you receive a runtime error. If you do not use unique key values, (that is, you try to set the keys to values that already exist in the database) you receive a runtime error.

Setting the key values prior to using the Create method is analogous to filling in the key values in the Add dialog for a component when you access it in add mode.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

None.

Returns

A Boolean value: True if component was successfully created, False otherwise.

Example

```
&MYCI = &MYSESSION.GetCompIntfc(COMPINTFC.ACTION_REASON);
&MYCI.ACTION = "Additional Job";
&MYCI.ACTION_REASON = "0001";
&MYCI.Create();
```

Find

Syntax

Find()

Description

Note: Find can be used only at level zero within the Component Interface.

You do not have to set values for all the key values. You can use the same wildcards in your Find that you can use in the search dialog, that is, % for one or more characters in a search pattern, and _ (underscore) for exactly one character. In addition, you can use partial values. For example, the following code finds all the data items where the employee ID starts with an "8":

```
&MYCI.Emplid = "8";
&MYDC = &MYCI.Find();
```

This is analogous to using a partial key from the search dialog, opening a component.

After you have a data collection, you can use one of the data collection methods to open the Component Interface.

Parameters

None.

Returns

A collection of Component Interfaces.

Related Links

Data Collection Methods

Get

Syntax

Get()

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

The Get method associates the Component Interface object executing the method with an open Component Interface that matches the key values that were set prior to using the Get method. The key values you must set are the required GETKEYS values for the Component Interface.

Note: To retrieve all the history data for a Component Interface, you must specify the GetHistoryItems property as True *before* you use the Get method. If you want any PeopleCode programs associated with the fields to fire immediately after a value is changed, you must set the InteractiveMode property as True *before*you use the Get method.

After any execution of Get, you should check if there are any errors pending on the session object. In some special circumstances (involving failure of previously cached operations failing after the Get has executed) Get returns True even though the component wasn't retrieved.

Parameters

None.

Returns

A Boolean value: True if component was successfully retrieved, False otherwise.

Example

```
&MYCI.EMPLID = "8001";
&MYCI.Get();
If %Session.ErrorPending Then
   /* Get Unsuccessful, do error processing */
Else
   /* do regular processing */
End-if;
```

GetPropertyByName

Syntax

GetPropertyByName(*string*)

Description

The GetPropertyByName method returns the value of the property specified by *string*. For a collection, it returns a reference to the collection. Generally this function is used only in applications that cannot get the names of the component interface properties until runtime.

Parameters

string	The name of the property.

Returns

String. The value of the property.

ApiObject. For a collection. The value of the property.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

```
Local ApiObject &oSession, &oCI;
Local array of string &Keys_Arr, &Temp_Arr, &Prop_Arr;
Local string &strCIName, &PropertyValue;
Local number &I, &J, &K;

Function getPropertyValue(&oDataColl As ApiObject, &PropertyName As string) Returns⇒
 string
rem ***** Return property value
   Return &oDataColl.GetPropertyByName(&PropertyName);
End-Function;

Function getCollection1(&collectionName As string)
   Local ApiObject &oL1_DataColl, &oL1_DataItem;
rem ***** Return collection
   &oL1_DataColl = &oCI.GetPropertyByName(&collectionName);
   For &J = 1 To &oL1_DataColl.Count
      &oL1_DataItem = &oL1_DataColl.Item(&J);
      For &K = 1 To &Prop_Arr.Len
         &Temp_Arr = Split(&Prop_Arr [&K], "|");
         If &Temp_Arr [1] = "1" Then
            If &Temp_Arr [3] = "Property" Then
               &PropertyValue = getPropertyValue(&oL1_DataItem,
                   &Temp_Arr [2]);
            Else
               rem ***** Code to Get Collection 2 goes here *****;
            End-If;
         End-If;
      End-For;
   End-For;
End-Function;
```

Related Links

SetPropertyByName

Save

Syntax

Save()

Description

Saves any changes that have been made to the data of the Component Interface executing the method. You must save any new Component Interfaces you create before they are added to the database.

The standard PeopleSoft save business rules (that is, any PeopleCode programs associated with SaveEdit, SavePreChange, WorkFlow, and so on.) is executed after you execute this method. If you didn't specify the Component Interface to run in interactive mode, FieldEdit, FieldChange, and so on, also run at this time.

If there are multiple errors, all errors are logged to the PSMessages collection, not just the first occurrence of an error. As you correct each error, you may want to delete it from the PSMessages collection.

Note: If you're running a Component Interface from an Application Engine program, the data won't actually be committed to the database until the Application Engine program performs a COMMIT.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

None.

Returns

A Boolean value: True if component was successfully saved, False otherwise.

Example

```
&MYCI.Emplid = "8001";
&MYCI.Get();
&MYCI.CHECKLIST_CD = "00001";
&MYCI.Save;
```

Related Links

InteractiveMode

ErrorPending

SetPropertyByName

Syntax

SetPropertyByName(*string, value***)**

Description

The SetPropertyByName method sets the value of the property specified by *string*. Generally this function is used only in applications that cannot set the names of the component interface properties until runtime.

Parameters

string	The name of the property.
value	The value to which the property is to be set.

Returns

None.

Example

```
Local ApiObject &oSession, &oCI;
Local array of string &Keys_Arr, &Temp_Arr, &Prop_Arr;
Local string &strCIName, &PropertyValue;
Local number &I, &J, &K;

&strCIName = "SDK_BUS_EXP";
&Keys_Arr = CreateArrayRept("", 0);
&Keys_Arr.Push("SDK_EMPLID|" | "8001");

&oSession = %Session;
&oCI = &oSession.GetCompIntfc(@("CompIntfc." | &strCIName));

For &I = 1 To &Keys_Arr.Len
   &Temp_Arr = Split(&Keys_Arr [1], "|");
   &oCI.SetPropertyByName(&Temp_Arr [1], &Temp_Arr [2]);
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
End-For;
```

Related Links

GetPropertyByName

Component Interface Class Properties

In this section, we discuss the Component Interface class properties. The properties are discussed in alphabetical order.

ComponentName

Description

This property returns the name of the Component Interface, as defined in Application Designer, as a string.

This property is read-only.

CreateKeyInfoCollection

Description

This property returns a CompIntfPropInfoCollection collection that contains a CompIntfPropInfoCollection object for every key in CREATEKEYS.

This property is read-only.

Example

```
&CREATEKEYS = &CI.CreateKeyInfoCollection;
```

Related Links

Accessing the Structure of a Component Interface

EditHistoryItems

Description

This property works with the GetHistoryItems property to specify what data is accessed, and whether you can edit that data:

- If EditHistoryItems is False (the default) and GetHistoryItems is True, you access the data in the Component Interface in a similar manner as if you were accessing a component in Update/Display All mode. This means all history rows are returned, however, you can edit only rows with a date set in the future.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- If EditHistoryItems is True and GetHistoryItems is True, you access the data in the Component Interface in a similar manner as if you were accessing a component in Correction mode. This means all history rows are returned, and you can edit them.
- If GetHistoryItems is False, you access the data in the Component Interface in a similar manner as if you were accessing a component in Update mode. The EditHistoryItems has no effect when GetHistoryItems is False.

You must set this property to True *before* you execute the Get method.

This property is read-write.

Related Links

GetHistoryItems

FindKeyInfoCollection

Description

This property returns a CompIntfPropInfoCollection collection that contains a CompIntfPropInfoCollection object for every key in FINDKEYS.

This property is read-only.

Related Links

Accessing the Structure of a Component Interface

GetDummyRows

Description

When a new scroll is inserted on a page, that scroll is displayed even though it has no underlying data. Any scroll that is empty has one dummy row displayed with only the defaults set.

This property is True if the dummy row is to be displayed, False if you do not want to display the dummy row. The default value for this property is True.

This property is read-write.

Example

```
&MyCI.GetDummyRows = False;
```

GetHistoryItems

Description

This property works with the EditHistoryItems property to specify what data is accessed, and whether you can edit that data:

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- If EditHistoryItems is False (the default) and GetHistoryItems is True, you access the data in the Component Interface in a similar manner as if you were accessing a component in Update/Display All mode. This means all history rows are returned, however, you can edit only rows with a date set in the future.
- If EditHistoryItems is True and GetHistoryItems is True, you access the data in the Component Interface in a similar manner as if you were accessing a component in Correction mode. This means all history rows are returned, and you can edit them.
- If GetHistoryItems is False, you access the data in the Component Interface in a similar manner as if you were accessing a component in Update mode. The EditHistoryItems has no effect when GetHistoryItems is False.

You must set this property to True *before* you execute the Get method.

This property is read-write.

Example

The following example checks the current status of the mode, then sets the GetHistoryItems and EditHistoryItems properties to True if the mode is Correction mode.

```
If %Mode = "C" Then
   &CI.EditHistoryItems = True;
   &CI.GetHistoryItems = True;
End-if;
```

Related Links

EditHistoryItems

GetKeyInfoCollection

Description

This property returns a CompIntfPropInfoCollection collection that contains a CompIntfPropInfoCollection object for every key in GETKEYS.

This property is read-only.

Related Links

Accessing the Structure of a Component Interface

InteractiveMode

Description

When this property is set as True, the Component Interface runs the same as a component: that is, any PeopleCode programs associated with FieldChange, RowInsert, and so on, run immediately after you make a change. If this property is set to False, these programs won't run until you execute the Save method.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

ErrorPending

PropertyInfoCollection

Description

This property returns a CompIntfPropInfoCollection object for every property that isn't a collection (that is, a scroll.) If the property is a collection (scroll), use the PropertyInfoCollection property to get another collection.

This property is read-only.

Related Links

Accessing the Structure of a Component Interface

StopOnFirstError

Description

When this property is set as True, the CopyRowset (or CopyRowsetDelta) method currently executing halts its processing at the first error generated by the Component Interface.

When this property is set as True and InteractiveMode is set as False, processing of queued operations at save time is halted at the first error.

The default value is False.

This property is read-write.

Data Collection Methods

A *data collection* is the collection of data, available at runtime or during test mode, associated with a particular scroll (or record.) The data collection object returns information about every *row of data* (item) that is returned for that record at runtime.

To access a data collection, use the name of the record (scroll) as a property on a Component Interface.

Related Links

Traversing a Component Interface and Using Data Collections

CurrentItem

Syntax

```
CurrentItem()
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

If the component associated with the Component Interface is effective-dated, CurrentItem returns a reference to the current effective-dated item (row of data). To get a specific item based on a date, use GetEffectiveItem.

If there is no current item, a Null is returned.

Example

```
&MYCD = &MYCI.EMPL_CHKLST_ITM;
&ITEM = &MYDC.CurrentItem();
```

DeleteItem

Syntax

DeleteItem(*number*)

Description

The DeleteItem method deletes the item (row of data) at the position specified by *number*. This parameter takes a number value.

When the DeleteItem method is executed, if there are any RowDelete PeopleCode programs associated with any of the fields, they fire as well, as if the user pressed ALT+8 and ENTER or clicked the DeleteRow icon. However, the programs are executed as if turbo mode was selected. (In turbo mode default processing is performed *only* for the row being deleted.)

If you set the InteractiveMode property to True, any RowDelete PeopleCode runs immediately after you execute DeleteItem. If this property is set to False, any RowDelete PeopleCode runs after you execute the Save method.

The deleted item is not actually deleted from the database until after you use the Save method.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

Image: EMPL_CHK_BC in Component Interface Tester

Here is an example of EMPL_CHK_BC in Component Interface Tester where in , suppose your Component Interface had two scrolls: EMPL_CHECKLIST and EMPL_CHKLST_ITM. The data collection EMPL_CHECKLIST has four items (rows of data.) The data collection EMPL_CHKLST_ITM (under the third item) has five items (rows of data.) If you run this component in the Component Interface Tester, it would look as follows:

To delete the third row in the third item, use the following:

```
Local ApiObject &MYSESSION;
Local ApiObject &MYCI;

&MYSESSION = %Session;
&MYCI = &MYSESSION.GetCompIntfc(COMPINTFC.EMPL_CHK_BC);
&MYLVL1 = &MYCI.EMPL_CHECKLIST;
&ITEM2 = &MYLVL1.Item(3);
&MYLVL2 = &ITEM2.EMPL_CHKLST_ITM;
&MYLVL2.DeleteItem(3);
&MYCI.Save();
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GetEffectiveItem

Syntax

GetEffectiveItem(*DateString, SeqNo*)

Description

If the component associated with the Component Interface is effective-dated, GetEffectiveItem returns a reference to the closest effective-dated item (row of data) that is less than or equal to the date specified by the *DateString*. To get an item based on the current effective date, use CurrentItem.

Note: *DateString* takes only a string value. You must convert a date variable into a string before you can use it for *DateString*. You can use the String function to do this.

Parameters

DateString Specify the year, month, and day of the effective date that you want to look for. This parameter takes a string value. You can specify the date either as YYYY-MM-DD *or*MM/DD/YY.

SeqNo Specify the sequence number of the effective date that you want to look for. This parameter takes a number value.

Returns

A reference to an effective-dated item.

Example

```
&MYCD = &MYCI.EMPL_CHKLST_ITM;
&DSTRING = String(&MYDATE);
&ITEM = &MYDC.GetEffectiveItem(&DSTRING, 1);
```

Related Links

"String" (PeopleTools 8.54: PeopleCode Language Reference)

GetEffectiveItemNum

Syntax

GetEffectiveItemNum(*DateString, SeqNo*)

Description

If the component associated with the Component Interface is effective-dated, GetEffectiveItemNum returns a reference to the number of the closest effective-dated item (row of data) that is less than or equal to the date specified by the *DateString*. To get an item number based on the current effective date, use CurrentItemNum.

Note: *DateString* takes only a string value. You must convert a date variable into a string before you can use it for *DateString*. You can use the String function to do this.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Considerations for Returning Rows

GetEffectiveItemNum returns a valid row number only when EFFDT is less than or equal to *DateString*. If the value you use for *DateString* pre-dates all the rows in the data collection, this method returns a zero and logs a message in the PSMessages collection.

For example, if 12/01/1990 was the earliest date in the collection, the following would return zero:

```
&NUM = &MYDC.GetEffectiveItemNum("01/01/1900", 1);
```

Parameters

DateString	Specify the year, month, and day of the effective date that you want to look for. This parameter takes a string value. You can specify the date either as YYYY-MM-DD *or*MM/DD/YYYY.
SeqNo	Specify the sequence number of the effective date that you want to look for. This parameter takes a number value.

Returns

A number. This method returns 0 if no row matching the criteria is found.

Example

```
&MYCD = &MYCI.EMPL_CHKLST_ITM;
&DSTRING = String(&MYDATE);
&ITEMNUM = &MYDC.GetEffectiveItemNum(&DSTRING, 1);
```

Related Links

"String" (PeopleTools 8.54: PeopleCode Language Reference)

InsertItem

Syntax

InsertItem(*number*)

Description

The InsertItem method inserts the item (row of data) at the position specified by *number*. This parameter takes a number value. You can insert items below only the zero level scroll. If you need to add a new data item, use the Create method instead.

InsertItem adds the new row *after* the current row. If the row has an effective date (EFFDT) or an effective sequence (EFFSEQ), these values are copied into the new row.

If a collection has *n* items and you specify *n* as the value for *number,* InsertItem inserts a new item (row) after the *last row.*

The InsertItem method returns a reference to the newly created item (row of data).

When the InsertItem method is executed, if there are any RowInsert PeopleCode programs associated with any of the fields, they fire also, as if the user pressed ALT+7 and ENTER or clicked the InsertRow

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

icon. However, the programs are executed as if turbo mode was selected. (In turbo mode default processing is performed *only* for the row being inserted.)

If you set the InteractiveMode property to True, any RowInsert PeopleCode runs immediately after you execute InsertItem. If this property is set to False, any RowInsert PeopleCode runs after you execute the Save method.

The inserted item is not added to the database until after you use the Save method.

Example

In the following example a new item (row of data) is added at the *end* of the current collection.

```
&MYDC = &MYCI.EMPL_CHECKLIST;
&COUNT = &MYDC.Count;
&ITEM = &MYDC.InsertItem(&COUNT);
&ITEM.CHECKLIST_CD = "00001";
&ITEM.RESPONSIBLE_ID = "6609";
&RSLT = &MYCI.Save();
```

Item

Syntax

Item(*number*)

Description

The Item returns the item (row of data) that exists at the *number* position in the data collection executing the method. The parameter takes a number value.

ItemByKeys

Syntax

ItemByKeys(*key_values*)

Description

The ItemByKeys method returns the item specified by the parameters. The number and type of keys are unique to each specific collection. Each key must be separated by a comma.

The collection reference must be the name of the Component Interface, followed by the record name. This method won't work on a collection reference (that is, &CI.RECNAME.ItemByKeys, not &MYCOLLECTION.ItemByKeys).

After you've returned an item, use the ItemNum property to determine the number of the item.

The keys must be in the *exact* order as in the Component Interface. A second level data collection also contains the keys of the parent data collection.

An easy way to determine the keys and their order in PeopleCode is to open the Component Interface in Application Designer, and use the Test Component. To determine the keys in Visual Basic, use the Object Browser.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

See ItemNum.

To see the signature for ItemByKeys:

1. Open the Component Interface in Application Designer.
2. Start the Component Interface Tester.

   Select the open Component Interface, then right-click, and select Test Component Interface from the pop-up menu.
3. Instantiate an object.

   Add data to the Get or Create keys and click Get Existing or Create New, respectively.
4. Expand the instantiated component until you find the collection in which you're interested.
5. Right-click on the collection and select ItemByKeys from the resulting pop-up menu.
6. The dialog that follows shows you the specific parameters, types, and order in which you should call ItemByKeys.

Returns

An item (row) of data from a data collection.

Example

```
Local ApiObject &MYSESSION;
Local ApiObject &CI;
Local ApiObject &CI_COLLECTION;
Local ApiObject &CI_ITEM;

&MYSESSION = %Session;
&CI = &MYSESSION.GetCompIntfc(COMPINTFC.CM_EVAL);
&CI.EMPLID = "8001";
If &CI.Get() <> 1 Then
   Exit;
End-If;

&CI_COLLECTION = &CI.CM_EVALUATIONS;
&COUNT = &CI_COLLECTION.Count;

&CI_ITEM = &CI.CM_EVALUATIONS.itembykeys("01");
&CI_ITEM.DESCR50 = "TEST";
If &CI.Save() <> 1 Then
   Exit;
End-If;
```

Related Links

"Testing Component Interfaces" (PeopleTools 8.54: Component Interfaces)

Data Collection Properties

This section explains the following Data Collection properties:

- Count

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- CurrentItemNumber

Count

Description

This property returns the number of data items (rows of data) in the data collection.

This property is read-only.

Example

```
&CI = &MYSESSION.GetCompIntfc(COMPINTFC.CM_EVAL_BC);
&CI.EMPLID = "8001";
&CI.Get()

&CI_COLLECTION = &CI.CM_EVALUATIONS;
&COUNT = &CI_COLLECTION.Count;
```

CurrentItemNumber

Description

If the component associated with the Component Interface is effective-dated, this property returns the item number for the current effective-dated item (row of data).

This property is read-only.

Data Item Class Property

This section discusses the ItemNum property.

ItemNum

Description

This property returns the number of the data item (row) in the collection. For example, many of the data collection methods takes a number as a parameter. Use this property to determine the item number (row number) of an item in a collection, then use that number in another method.

This property is read-only.

Example

```
Evaluate USER_ACTION

.  .  .

When = "D"
   &CI_ITEM = &CI_LVL1_NAMES.ItemByKeys(&NAME_TYPE, &NAME_PART);
   If &CI_ITEM <> Null then
      &I = &CI_LVL1_NAMES.ItemNum;
      &CI_LVL1_NAMES.DeleteItem(&I);
   End-if;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
. . .
End-Evaluate;
```

Accessing the Structure of a Component Interface

The structure of a Component Interface can be accessed using a CompIntfPropInfoCollection object. You access a CompIntfPropInfoCollection object from a CompIntfPropInfoCollection collection. There is more than one way to instantiate a CompIntfPropInfoCollection collection.

Note: You don't have to populate a Component Interface with data before you access the structure. You can access the structure of a Component Interface immediately after you use the GetCompIntfc method with a session object. Accessing the structure of a Component Interface before you populate it with data may increase your performance.

See GetCompIntfc.

CompIntfPropInfoCollection Collection

There are two types of CompIntfPropInfoCollection object properties: *field* properties and *collection* properties.

A *field* property maps to a specific record field. You can access structural information about the field using a CompIntfPropInfoCollection object. This information includes the name of the field, whether it's required, is it based on a prompt table, and so on.

A *collection* property is just that, a collection of properties. And before you can access a CompIntfPropInfoCollection object, you must first get a CompIntfPropInfoCollection *collection.* The following are the valid types of CompIntfPropInfoCollection collections:

- CREATEKEYS, GETKEYS and FINDKEYS

  When you create a component, you must specify the search record to be used with that component. You can also specify an alternate search record to be used when the component is accessed in Add mode. The key fields from those records make up the GETKEYS, FINDKEYS, and CREATEKEYS collections.

  Note: In order for a component interface to validate a key against a prompt table, both the Search Edit and List Box Item options must be selected in the record field properties for the key.

  - CREATEKEYS: A collection containing the key fields of the search record specified to be used in Add mode. Use the CreateKeyInfoCollection property to instantiate the CompIntfPropInfoCollection collection.
  - GETKEYS: A collection containing the primary required key fields from the primary search record. Use the GetKeyInfoCollection property to instantiate the CompIntfPropertInfo collection.
  - FINDKEYS: A collection containing the key fields and the alternate key fields from the primary search record. Use the FindKeyInfoCollection property to instantiate the CompIntfPropertInfo collection.

- A page scroll

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The fields associated with a page scroll are in this type of collection. This may or may not be all the fields associated with the record. Use the PropertyInfoCollection property to instantiate this kind of collection.

If the page the Component Interface is based on contains a secondary scroll, you can check the Type property to determine if the object is a CompIntfPropInfoCollection object (that is, a field), or a scroll. Then, to get the properties of the fields associated with that secondary scroll, you can use the PropertyInfoCollection property on the CompIntfPropInfoCollection object.

For example, the following Component Interface has a level zero and level one scroll.

Image: Component Interface with secondary scroll

This example illustrates the fields and controls on the Component Interface with secondary scroll. You can find definitions for the fields and controls later on this page.

The level zero scroll is made up of three fields: CHECKLIST_CD, RESPONSIBLE_ID, COMMENTS, and a level one scroll, EMPL_CHKLST_ITM. The CompIntfPropInfoCollection collection for this Component Interface would have four items in it. Three would be CompIntfPropInfoCollection objects (the three fields.) The last item, EMPL_CHKLST_ITM would *not* be a valid CompIntfPropInfoCollection object. You can use the IsCollection property to verify if an item in a collection is itself a collection or a valid CompIntfPropInfoCollection object.

To access the fields in a lower level scroll, you must use the PropertyInfoCollection property first, to return a collection of those fields.

The following example loops through a Component Interface. It pulls out the names of the properties in the first three levels of a Component Interface. If the property is a nested collection, it prefixes the ancestor collection name to the property name.

```
&MYSESSION = %Session;
&CI = &MYSESSION.GetCompIntfc(COMPINTFC.VOLNEW);
&PROPINFO_0 = &CI.PropertyInfoCollection;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
For &I = 1 To &PROPINFO_0.Count;
   &PROPITEM_0 = &PROPINFO_0.Item(&I);
   Warning (&PROPITEM_0.Name);
   If (&PROPITEM_0.IsCollection) Then
      &PROPINFO_1 = &PROPITEM_0.PropertyInfoCollection;
      For &J = 1 To &PROPINFO_1.Count;
         &PROPITEM_1 = &PROPINFO_1.Item(&J);
         &S1 = &PROPITEM_0.Name | "." | &PROPITEM_1.Name;
         Warning (&S1);
         If (&PROPITEM_1.IsCollection) Then
            &PROPINFO_2 = &PROPITEM_1.PropertyInfoCollection;
            For &K = 1 To &PROPINFO_2.Count;
               &PROPITEM_2 = &PROPINFO_2.Item(&K);
               &S1 = &PROPITEM_0.Name | "." | &PROPITEM_1.Name | "." | &PROPITEM_2.⇒
Name;
               Warning (&S1);
            End-For;
         End-If
      End-For;
   End-If;
End-For;
```

CompIntfPropInfoCollection Collection Methods

This section explains the CompIntfPropInfoCollection collection methods.

First

Syntax

First()

Description

The First method returns the first CompIntfPropInfoCollection object in the CompIntfPropInfoCollection collection object executing the method.

Example

```
&CIINFO = &CIPROPCOLL.First();
```

Item

Syntax

Item(*number*)

Description

The Item method returns a CompIntfPropInfoCollection object that exists at the *number* position in the CompIntfPropInfoCollection collection executing the method

If the specified item is *itself* a collection, the CompIntfPropInfoCollection object that gets returned is invalid (set to NULL). You can use the PropertyInfoCollection property to return a collection of CompIntfPropInfoCollection objects for the collection.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

```
&SCROLL1 = &MYCI.PropertyInfoCollection;
For &I = 1 to &SCROLL1.Count;
&PROPERTY = &SCROLL1.Item(&I);
If &PROPERTY.IsCollection Then
&SCROLL2 = &PROPERTY.PropertyInfoCollection;
/*do scroll 2 processing */
Else
/* do scroll 1 processing */
End-If;
End-For;
```

Next

Syntax

```
Next()
```

Description

The Next method returns the next CompIntfPropInfoCollection object in the CompIntfPropInfoCollection collection object executing the method. You can use this method only after you have used either the First or Item methods: otherwise the system doesn't know where to start.

CompIntfPropInfoCollection Collection Properties

This section explains the Count property.

Count

Description

This property returns the number of CompIntfPropInfoCollection objects in the CompIntfPropInfoCollection collection object executing the method.

This property is read-only.

Example

```
&COUNT = &MYCIPROPINFOC.Count;
```

CompIntfPropInfoCollection Object Properties

This section explains the CompIntfPropInfoCollection Object properties.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Format

Description

This property returns the field format for the object executing the property (that is, name, phone, zip, SSN, and so on) as a number. The values are:

Value	*Description*
0	No Format
1	Name
2	Phone
3	Zip
4	SSN
5	Routine
6	Mixed Case
7	Raw Binary
8	Number only
9	SIN
10	Phone International
11	Zip International
12	Seconds
13	Microseconds
14	Custom

This property is read-only.

IsCollection

Description

This property returns True if the object executing the property is a data collection, False otherwise. If IsCollection is True, other field-oriented properties like Required, Type, Xlat, YesNo, Prompt and Format are undefined. If IsCollection is False, the object represents a field and all the previous properties are defined as described.

This property is read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

IsReadOnly

Description

This property returns True if the property marked Read Only in the Component Interface Definition; False otherwise.

This property is read-only.

Key

Description

This property returns True if the object executing the property is a key, False otherwise.

This property is read-only.

LabelLong

Description

This property returns the record field LongName value as a string. If there is a component override for this value, it is *not* included.

This property is read-only.

LabelShort

Description

This property returns the record field ShortName value as a string. If there is a component override for this value, it is *not* included.

This property is read-only.

Length

Description

This property returns the length of the field property as a number. If the property is a collection, this property returns a zero.

The length of the field is calculated by converting it to a string then getting the length of the string. This means that *everything* in the field is counted as a character, including spaces, date time separation characters, decimal points, sign indicators, and so on.

For example, the following string has 10 characters:

```
01/01/2001
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The following string has five characters:

```
10.10
```

The following string has six characters:

```
-10.10
```

This property is read-only.

Name

Description

This property returns the name of the object executing the property as a string.

This property is read-only.

Prompt

Description

This property returns True if the object executing the property is associated with a prompt table, False otherwise.

This property is read-only.

PropertyInfoCollection

Description

This property returns another CompIntfPropInfoCollection collection if the object executing the property is a collection.

This property is read-only.

Example

```
&SCROLL1 = &MYCI.PropertyInfoCollection;
For &I = 1 to &SCROLL1.Count;
   &PROPERTY = &SCROLL1.Item(&I);
   If &PROPERTY.IsCollection Then
   &SCROLL2 = &PROPERTY.PropertyInfoCollection;
   /*do scroll 2 processing */
   Else
/* do scroll 1 processing */
   End-If;
End-For;
```

Required

Description

This property returns True if the object executing the property is a required property, False otherwise.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-only.

Type

Description

This property returns the field type, as a number, of the object. The values are:

Value	*Description*
0	Character
1	Long Character
2	Number
3	Signed Number
4	Date
5	Time
6	DateTime
7	SubRecord (Not supported with Component Interfaces)
8	Image (Limited support with Component Interfaces)
9	ImageReference (Not supported with Component Interfaces)

This property is read-only.

Xlat

Description

This property returns True if the object executing the property is associated with an XLAT table, False otherwise.

This property is read-only.

YesNo

Description

This property returns True if the object executing the property is associated with the Yes/No table, False otherwise.

This property is read-only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Component Interface Examples

The following are examples of some of the most usual actions you're likely to perform using a Component Interface.

Create a New Instance of Data Example

The following is an example of how to create a new instance of a Component Interface.

To create a new instance of data:

In this example, you are creating a new instance of data for the EXPRESS Component Interface, which is based on the EXPRESS_ISSUE_INV component. The following is the complete code sample: the steps explain each line.

```
Local ApiObject &MYSESSION;
Local ApiObject &MYCI;


&MYSESSION = %Session;
&MYCI = &MYSESSION.GetCompIntfc(COMPINTFC.EXPRESS);
&MYCI.BUSINESS_UNIT = "H01B";
&MYCI.INTERNAL_FLG = "Y";
&MYCI.ORDER_NO = "NEXT&rsquo;;
&MYCI.Create();
&MYCI.CUSTOMER = "John&rsquo;s Chicken Shack";
&MYCI.LOCATION = "H10B6987";
.
.
.
If NOT(&MYCI.Save()) Then
   /* save didn&rsquo;t complete */
   &COLL = &MYSESSION.PSMessages;
   For &I = 1 to &COLL.Count
      &ERROR = &COLL.Item(&I);
      &TEXT = &ERROR.Text;
      /* do error processing */
   End-For;
   &COLL.DeleteAll();
End-if;
```

1. Get a session object.

   Before you can get a Component Interface, you have to get a session object. The session controls access to the Component Interface, provides error tracing, enables you to set the runtime environment, and so on.

   ```
   &MYSESSION = %Session;
   ```

2. Get a Component Interface.

   Use the GetCompIntfc method with a session object to get the Component Interface. You must specify a Component Interface definition that has already been created. You receive a runtime error if you specify a Component Interface that doesn’t exist.

   ```
   &MYCI = &MYSESSION.GetCompIntfc(COMPINTFC.EXPRESS);
   ```

   After you execute the GetCompIntfc method, you have only the *structure* of the Component Interface. You haven’t populated the Component Interface with data yet.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

3. Set the CREATEKEYS.

   These key values are required to open a new instance of the data. If the values you specify aren't unique, that is, if an instance of the data already exists in the database with those key values, you receive a runtime error.

```
&MYCI.BUSINESS_UNIT = "H01B";
&MYCI.INTERNAL_FLG = "Y";
&MYCI.ORDER_NO = "NEXT&rsquo;;
```

4. Create the instance of data for the Component Interface.

   After you set the key values, you must use the Create method to populate the Component Interface with the key values you set.

```
&MYCI.Create();
```

   This creates an instance of this data. However, it hasn't been saved to the database. You must use the Save method before the instance of data is committed to the database.

5. Set the rest of the fields.

   Assign values to the other fields.

```
&MYCI.CUSTOMER = "John&rsquo;s Chicken Shack";
&MYCI.LOCATION = "H10B6987";
.
.
.
```

   If you have specified InteractiveMode as True, every time you assign a value or use the InsertItem or DeleteItem methods, any PeopleCode programs associated with that field (either with record field or the component record field) fires (FieldEdit, FieldChange, RowInsert, and so on.)

6. Save the data.

   When you execute the Save method, the new instance of the data is saved to the database.

```
If NOT(&MYCI.Save()) Then
```

   The Save method returns a Boolean value: True if the save was successful, False otherwise. You can use this value to do error checking.

   The standard PeopleSoft save business rules (that is, any PeopleCode programs associated with SaveEdit, SavePreChange, WorkFlow, and so on.) are executed. If you didn't specify the Component Interface to run in interactive mode, FieldEdit, FieldChange, and so on, also run at this time for all fields that had values set.

   Note: If you're running a Component Interface from an Application Engine program, the data won't actually be committed to the database until the Application Engine program performs a COMMIT.

7. Check Errors.

   You can check if there were any errors using the PSMessages property on the session object.

```
If NOT(&MYCI.Save()) Then
   /* save didn&rsquo;t complete */
   &COLL = &MYSESSION.PSMessages;
   For &I = 1 to &COLL.Count
      &ERROR = &COLL.Item(&I);
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
      &TEXT = &ERROR.Text;
      /* do error processing */
   End-For;
   &COLL.DeleteAll();
End-if;
```

If there are multiple errors, all errors are logged to the PSMessages collection, not just the first occurrence of an error. As you correct each error, delete it from the PSMessages collection.

The Text property of the PSMessage returns the text of the error message. At the end of this text is a contextual string that contains the name of the field that generated the error. The contextual string has the following syntax:

```
{BusinessComponentName.[CollectionName(Row).[CollectionName(Row).[CollectionNa⇒
me(Row)]]].PropertyName}
```

For example, if you specified the incorrect format for a date field of the Component Interface named ABS_HIST, the Text property would contain the following string:

```
Invalid Date {ABS_HIST.BEGIN_DT} (90), (1)
```

The contextual string (by itself) is available using the Source property of the PSMessage.

Note: If you've called your Component Interface from an Application Engine program, all errors are also logged in the Application Engine error log tables.

See Error Handling, Source.

Getting an Existing Instance of Data Example

The following is an example of how to get an existing instance of a Component Interface.

In this example, you are getting an existing instance of data for the EMPL_CHKLST_BC Component Interface, which is based on the EMPLOYEE_CHECKLIST component. The following is the complete code sample: the steps explain each line.

```
Local ApiObject &MYSESSION;
Local ApiObject &MYCI;

&MYSESSION = %Session;
&MYCI = &MYSESSION.GetCompIntfc(COMPINTFC.EMPL_CHKLST_BC);
&MYCI.EMPLID= "8001";
&MYCI.Get();

/* Get checklist Code */

&CHECKLIST_CD = &MYCI.CHECKLIST_CD;

/* Set Effective date */

&MYCI.EFFDT = "05-01-1990";
.
.
.
If NOT(&MYCI.Save()) Then
   /* save didn&rsquo;t complete */
   &COLL = &MYSESSION.PSMessages;
   For &I = 1 to &COLL.Count
      &ERROR = &COLL.Item(&I);
      &TEXT = &ERROR.Text;
      /* do error processing */
   End-For;
   &COLL.DeleteAll();
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
End-if;
```

1. Get a session object.

   Before you can get a Component Interface, you have to get a session object. The session controls access to the Component Interface, provides error tracing, enables you to set the runtime environment, and so on.

   ```
   &MYSESSION = %Session;
   ```

2. Get a Component Interface.

   Use the GetCompIntfc method with a session object to get the Component Interface. You must specify a Component Interface definition that has already been created. You receive a runtime error if you specify a Component Interface that doesn't exist.

   ```
   &MYCI = &MYSESSION.GetCompIntfc(COMPINTFC.EMPL_CHKLST_BC);
   ```

   After you execute the GetCompIntfc method, you have only the *structure* of the Component Interface. You haven't populated the Component Interface with data yet.

3. Set the GETKEYS.

   These are the key values required to return a unique instance of existing data. If the keys you specify allow for more than one instance of the data to be returned, or if no instance of the data matching the key values is found, you receive a runtime error.

   ```
   &MYCI.EMPLID = "8001";
   ```

4. Get the instance of data for the Component Interface.

   After you set the key values, you have to use the Get method.

   ```
   &MYCI.Get();
   ```

   This populates the Component Interface with data, based on the key values you set.

5. Get field values or set field values.

   At this point, you can either get values or set values.

   ```
   &CHECKLIST_CD = &MYCI.CHECKLIST_CD;

   /* OR */
   &MYCI.EFFDT = "05-01-1990";
   ```

   If you have specified InteractiveMode as True, every time you assign a value, any PeopleCode programs associated with that field (either with record field or the component record field) fires (FieldEdit, FieldChange, and so on.)

6. Save or Cancel the Component Interface, as appropriate.

   If you've changed values and you want to save your changes to the database, you must use the Save method.

   ```
   If NOT(&MYCI.Save()) Then
   ```

   The Save method returns a Boolean value: True if the save was successful, False otherwise. Use this value to do error checking.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The standard PeopleSoft save business rules (that is, any PeopleCode programs associated with SaveEdit, SavePreChange, WorkFlow, and so on.) are executed. If you didn't specify the Component Interface to run in interactive mode, FieldEdit, FieldChange, and so on, also run at this time.

Note: If you're running a Component Interface from an Application Engine program, the data won't actually be committed to the database until the Application Engine program performs a COMMIT.

If you don't want to save any changes to the data, use the Cancel method. The Component Interface is reset to the state it was in just after you used the GetCompIntfc method.

```
&MYCI.Cancel();
```

This is similar to a user pressing ESC while in a component, and choosing to not save any of their changes.

7. Check Errors.

   You can check if there were any errors using the PSMessages property on the session object.

```
If NOT(&MYCI.Save()) Then
   /* save didn&rsquo;t complete */
   &COLL = &MYSESSION.PSMessages;
   For &I = 1 to &COLL.Count
      &ERROR = &COLL.Item(&I);
      &TEXT = &ERROR.Text;
      /* do error processing */
   End-For;
   &COLL.DeleteAll();
End-if;
```

   If there are multiple errors, all errors are logged to the PSMessages collection, not just the first occurrence of an error. As you correct each error, delete it from the PSMessages collection.

   The Text property of the PSMessage returns the text of the error message. At the end of this text is a contextual string that contains the name of the field that generated the error. The contextual string has the following syntax:

```
{ComponentInterfaceName.[CollectionName(Row).[CollectionName(Row).[CollectionN⇒
ame(Row)]]].PropertyName}
```

   For example, if you specified the incorrect format for a date field of the Component Interface named ABS_HIST, the Text property would contain the following string:

```
Invalid Date {ABS_HIST.BEGIN_DT} (90), (1)
```

   The contextual string (by itself) is available using the Source property of the PSMessage.

Note: If you've called your Component Interface from an Application Engine program, all errors are also logged in the Application Engine error log tables.

See Error Handling, Source.

Retrieving a List of Instance of Data Example

The following is an example of how to retrieve a list of instances of data.

To retrieve a list of instances of data:

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

In this example, you are getting a list of existing instances of data for the EMPL_CHKLST_CI Component Interface, which is based on the EMPLOYEE_CHECKLIST component. The following is the complete code sample: the steps break it up and explain each line.

```
Local ApiObject &MYSESSION;
Local ApiObject &MYCI;
Local ApiObject &MYNEWCI;


&MYSESSION = %Session;
&MYCI = &MYSESSION.GetCompIntfc(COMPINTFC.EMPL_CHKLST_CI);
&MYCI.EMPLID= "8";
&MYCI.LAST_NAME_SRCH = "S";
&MYLIST = &MYCI.Find();
For &I = 1 to &MYLIST.Count;

   /* note: do not reuse the CI used to create the list, or the list will be destro⇒
yed */

&MYNEWCI = &MYLIST.Item(&I);

/* CI from list still must be instantiated to use it */

&MYNEWCI.Get();

/* do some processing */

End-For;
```

1. Get a session object.

   Before you can get a Component Interface, you have to get a session object. The session controls access to the Component Interface, provides error tracing, enables you to set the runtime environment, and so on.

   ```
   &MYSESSION = %Session;
   ```

2. Get a Component Interface.

   Use the GetCompIntfc method with a session object to get the Component Interface. You must specify a Component Interface definition that has already been created. You receive a runtime error if you specify a Component Interface that doesn't exist.

   ```
   &MYCI = &MYSESSION.GetCompIntfc(COMPINTFC.EMPL_CHKLST_CI);
   ```

   After you execute the GetCompIntfc method, you have only the *structure* of the Component Interface. You haven't populated the Component Interface with data yet.

3. Set the FINDKEYS values.

   These can be alternate key values or partial key values. If no instance of the data matching the key values is found, you receive a runtime error.

   ```
   &MYCI.EMPLID = "8";
   &MYCI.LAST_NAME_SRCH = "S";
   ```

4. Get a list of data instances for the Component Interface.

   After you set the alternate or partial key values, use the Find method to return a list of data instances for the Component Interface.

   ```
   &MYLIST = &MYCI.Find();
   ```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Note: The Find method can be executed only at level zero in a Component Interface.

5. Select an instance of the data.

   To select an instance of the data, you can use any of the following standard data collection methods:

   - First
   - Item
   - Next

For example, you could loop through every instance of the data to do some processing:

```
For &I = 1 to &MYLIST.Count;
   /* note: do not reuse the Component Interface used to */
   /* create the list here, or the list will be destroyed */
&MYNEWCI = &MYLIST.Item(&I);
/* CI from list must still be instantiated to use it */
&MYNEWCI.Get();
/* do some processing */
End-For;
```

After you have a specific instance of the data, you can get values, set values, and so on.

See Data Collection Methods.

Inserting Effective-Dated Data Example

You can rename a collection in a Component Interface. For example, suppose you had the same record at level zero and at level one. You may want to rename the level one data collection to reflect this. The data in a data collection is associated with the primary database record of a scroll, *not* with the name you supply.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Here is an example of using a Component Interface that has the same record at level zero and level one. The Component Interface is based on the CURRENCY_CD_TBL component.

Image: Example of CI with same record at level zero and level one

This example illustrates the fields and controls on the Example of CI with same record at level zero and level one. You can find definitions for the fields and controls later on this page.

The following code example is based on this Component Interface and does the following:

1. Gets an existing Component Interface.
2. Finds the current effective-dated item index.
3. Inserts a new row before the current effective-dated item using the InsertItem method.

```
Local ApiObject &Session;
Local ApiObject &CURRENCY_CD;
Local ApiObject &CURRENCY_CD_TBLCol;
Local ApiObject &CURRENCY_CD_TBLItm;
Local ApiObject &PSMessages;
Local string &ErrorText, &ErrorType;
Local number &ErrorCount;
Local Boolean &Error;

Function CheckErrorCodes()

   &PSMessages = &Session.PSMessages;
   &ErrorCount = &PSMessages.Count;
   For &i = 1 To &ErrorCount
      &ErrorText = &PSMessages.Item(&i).Text;
      &ErrorType = &PSMessages.Item(&i).Type;
   End-For;

End-Function;

/* Initialize Flags */
&Error = False;

&Session = %Session;

If &Session <> Null Then
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
      CheckErrorCodes();
      /* Application Specific Error Processing */

   Else

      &CURRENCY_CD = &Session.GetCompIntfc(CompIntfc.CURRENCY_CD);

      If &CURRENCY_CD = Null Then

         CheckErrorCodes();
         /* Application Specific Error Processing */

      Else

         /* Set Component Interface Get Keys */
         &CURRENCY_CD.CURRENCY_CD = "USD";

         If Not &CURRENCY_CD.Get() Then

            CheckErrorCodes();
            /* Application Specific Error Processing */
            &Error = True;

         End-If;

         If Not &Error Then

            &CURRENCY_CD_TBLCol = &CURRENCY_CD.CURRENCY_CD_TBL;
            &CURRENCY_CD_TBLItm = &CURRENCY_CD_TBLCol.InsertItem(&CURRENCY_CD_TBL⇒
   Col.CurrentItemNum());
            &CURRENCY_CD_TBLItm.EFFDT = %Date;
            &CURRENCY_CD_TBLItm.EFF_STATUS = "A";
            &CURRENCY_CD_TBLItm.DESCR = "NewCurrencyCode";
            &CURRENCY_CD_TBLItm.DESCRSHORT = "New";
            &CURRENCY_CD_TBLItm.COUNTRY = "USA";
            &CURRENCY_CD_TBLItm.CUR_SYMBOL = "?";
            &CURRENCY_CD_TBLItm.DECIMAL_POSITIONS = 4;
            &CURRENCY_CD_TBLItm.SCALE_POSITIONS = 0;

            /* Save Instance of Component Interface */
            If Not &CURRENCY_CD.Save() Then

               CheckErrorCodes();
               /* Application Specific Error Processing */

            End-If;

         End-If;
         /* End: Set Component Interface Properties */

         /* Cancel Instance of Component Interface */
         &CURRENCY_CD.Cancel();

      End-If;

End-If;
```

Inserting Effective-Dated Data Example Using Visual Basic

Here's a code example in Visual Basic that does the same thing as the previous code example.

```
Private Sub CURRENCY_CD()

        On Error GoTo eMessage

        '***** Set Object References *****
        Dim oCISession As Object
        Dim oCURRENCY_CD As Object
        Dim oCURRENCY_CD_TBL As Object
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
        Dim oCURRENCY_CD_TBLItem As Object

        '***** Set Connect Parameters *****
        strAppSeverPath = "//PSOFT101999:9000"
        strOperatorID = "PTDMO"
        strPassword = "PTDMO"

        '***** Create PeopleSoft Session Object *****
        Set oCISession = CreateObject("PeopleSoft.Session")

        '***** Connect to the App Sever *****
        oCISession.Connect 1, strAppSeverPath, strOperatorID, strPassword, 0

        '***** Get the Component *****
        Set oCURRENCY_CD = oCISession.GetCompIntfc("CURRENCY_CD")

        '***** Set the Component Interface Mode *****
        oCURRENCY_CD.InteractiveMode = False
        oCURRENCY_CD.GetHistoryItems = True

        '***** Set Component Get/Create Keys *****
        oCURRENCY_CD.CURRENCY_CD = "USD"

        '***** Execute Create *****
        oCURRENCY_CD.Get

        'Set CURRENCY_CD_TBL Collection Field Properties --
        'Parent: PS_ROOT Collection
        Set oCURRENCY_CD_TBL = oCURRENCY_CD.CURRENCY_CD_TBL
        Set oCURRENCY_CD_TBLItem = oCURRENCY_CD_TBL.InsertItem(oCURRENCY_CD_TBL.Cur⇒
rentItemNum())

        oCURRENCY_CD_TBLItem.EFFDT = Date
        oCURRENCY_CD_TBLItem.EFF_STATUS = "A"
        oCURRENCY_CD_TBLItem.DESCR = "NewCurrencyCode"
        oCURRENCY_CD_TBLItem.DESCRSHORT = "New"
        oCURRENCY_CD_TBLItem.COUNTRY = "USA"
        oCURRENCY_CD_TBLItem.CUR_SYMBOL = "?"
        oCURRENCY_CD_TBLItem.DECIMAL_POSITIONS = 4
        oCURRENCY_CD_TBLItem.SCALE_POSITIONS = 0

        '***** Save Component Interface *****
        oCURRENCY_CD.Save
        oCURRENCY_CD.Cancel

        Exit Sub

eMessage:
        '***** Display VB Runtime Errors *****
        MsgBox Err.Description

        '***** Display PeopleSoft Error Messages *****
        If oCISession.PSMessages.Count > 0 Then
                For i = 1 To oCISession.PSMessages.Count
                        MsgBox oCISession.PSMessages.Item(i).Text
                Next i
        End If

End Sub

Sub MAIN()
    CURRENCY_CD
End Sub
```

Inserting or Deleting a Row of Data Example

The CopyRowset and CopyRowsetDelta methods use the primary database name of a scroll, not the name you may give a collection.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

A data collection represents a row of data. You often insert or delete a row of data.

To insert or delete a row of data:

In this example, you are getting a existing instance of data for the BUS_EXP Component Interface, which is based on the BUSINESS_EXPENSES component, then inserting (or deleting) a row of data in the second level scroll.

Image: BUS_EXP Component Interface definition

This example illustrates the fields and controls on the BUS_EXP Component Interface definition. You can find definitions for the fields and controls later on this page.

The following is the complete code sample: the steps explain each line.

```
Local ApiObject &MYSESSION;
Local ApiObject &MYCI;

&MYSESSION = %Session;
&MYCI = &MYSESSION.GetCompIntfc(COMPINTFC.BUS_EXP);
&MYCI.EMPLID= "8001";
&MYCI.Get();
&MYLEVEL1 = &MYCI.BUS_EXPENSE_PER;
/* get appropriate item in lvl1 collection */
For &I = 1 to &MYLEVEL1.Count
&ITEM = &MYLEVEL1.Item(&I);
&MYLEVEL2 = &ITEM.BUS_EXPENSE_DTL;
&COUNT = &MYLEVEL2.Count
/* get appropriate item in lvl2 collection */
For &J = 1 to &COUNT
&LVL2ITEM = &MYLEVEL2.Item(&J);
&CIDATE = &LVL2ITEM.CHARGE_DT;
If &CIDATE <> %Date Then
      /* insert row */
&NEWITEM = &MYLEVEL2.InsertItem(&COUNT);
   /* set values for &NEWITEM */
Else
      /* delete last row */
   &MYLEVEL2.DeleteItem(&COUNT);
End-If;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
   End-For;
End-For;

If NOT(&MYCI.Save()) Then
   /* save didn&rsquo;t complete */
   &COLL = &MYSESSION.PSMessages;
   For &I = 1 to &COLL.Count
      &ERROR = &COLL.Item(&I);
      &TEXT = &ERROR.Text;
      /* do error processing */
   End-For;
   &COLL.DeleteAll();
End-if;
```

1. Get a session object.

   Before you can get a Component Interface, you have to get a session object. The session controls access to the Component Interface, provides error tracing, enables you to set the runtime environment, and so on.

   ```
   &MYSESSION = %Session;
   ```

2. Get a Component Interface.

   Use the GetCompIntfc method with a session object to get the Component Interface. You must specify a Component Interface definition that has already been created. You receive a runtime error if you specify a Component Interface that doesn't exist.

   ```
   &MYCI = &MYSESSION.GetCompIntfc(COMPINTFC.BUS_EXP);
   ```

   After you execute the GetCompIntfc method, you have only the *structure* of the Component Interface. You haven't populated the Component Interface with data yet.

3. Set the GETKEYS.

   These are the key values required to return a unique instance of existing data. If the keys you specify allow for more than one instance of the data to be returned, or if no instance of the data matching the key values is found, you receive a runtime error.

   ```
   &MYCI.EMPLID = "8001";
   ```

4. Get the instance of data for the Component Interface.

   After you set the key values, you must use the Get method.

   ```
   &MYCI.Get();
   ```

   This populates the Component Interface with data, based on the key values you set.

5. Get the level one scroll.

   The name of the scroll can be treated like a property. It returns a data collection that contains all the level one data.

   ```
   &MYLEVEL1 = &MYCI.BUS_EXPENSE_PER
   ```

6. Get the appropriate item in the level one data collection.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Remember, scroll data is hierarchical. You must get the appropriate level one row before you can access the level two data.

```
For &I = 1 to &MYLEVEL1.Count
&ITEM = &MYLEVEL1.Item(&I);
```

7. Get the level two scroll.

   This is done the same way as you accessed the level one scroll, by using the scroll name as a property.

```
&MYLEVEL2 = &ITEM.BUS_EXPENSE_DTL;
```

8. Get the appropriate item in the level two data collection.

   A data collection is made up of a series of items (rows of data.) You have to access the appropriate item (row) in this level also.

```
&COUNT = &MYLEVEL2.Count
/* get appropriate item in lvl2 collection */
For &J = 1 to &COUNT
&LVL2ITEM = &MYLEVEL2.Item(&J);
```

9. Insert or delete a row of data.

   You can insert or delete a row of data from a data collection. The following example finds the last item (row of data) in the second level scroll. If it matches the value of %Date, the last item is deleted. If it doesn't match, a new row is inserted.

```
&CIDATE = &LVL2ITEM.CHARGE_DT;
If &CIDATE <> %Date Then
   /* insert row */
&NEWITEM = &MYLEVEL2.InsertItem(&COUNT);
/* set values for &NEWITEM */
Else
   /* delete last row */
&MYLEVEL2.DeleteItem(&COUNT);
End-If;
```

10. Save the data.

    When you execute the Save method, the new instance of the data is saved to the database.

```
If NOT(&MYCI.Save()) Then
```

    The Save method returns a Boolean value: True if the save was successful, False otherwise. Use this value to do error checking.

    The standard PeopleSoft save business rules (that is, any PeopleCode programs associated with SaveEdit, SavePreChange, WorkFlow, and so on) are executed. If you did not specify the Component Interface to run in interactive mode, FieldEdit, FieldChange, and so on, also run at this time.

Note: If you're running a Component Interface from an Application Engine program, the data won't actually be committed to the database until the Application Engine program performs a COMMIT.

---

11. Check Errors.

    You can check if there were any errors using the PSMessages property on the session object.

```
If NOT(&MYCI.Save()) Then
   /* save didn&rsquo;t complete */
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
   &COLL = &SESSION.PSMessages;
   For &I = 1 to &COLL.Count
      &ERROR = &COLL.Item(&I);
      &TEXT = &ERROR.Text;
      /* do error processing */
   End-For;
   &COLL.DeleteAll();
End-if;
```

If there are multiple errors, all errors are logged to the PSMessages collection, not just the first occurrence of an error. As you correct each error, delete it from the PSMessages collection.

The Text property of the PSMessage returns the text of the error message. At the end of this text is a contextual string that contains the name of the field that generated the error. The contextual string has the following syntax:

```
{BusinessComponentName.[CollectionName(Row).[CollectionName(Row).[CollectionNa⇒
me(Row)]]].PropertyName}
```

For example, if you specified the incorrect format for a date field of the Component Interface named ABS_HIST, the Text property contains the following string:

```
Invalid Date {ABS_HIST.BEGIN_DT} (90), (1)
```

The contextual string (by itself) is available using the Source property of the PSMessage.

Note: If you've called the Component Interface from an Application Engine program, all errors are also logged in the Application Engine error log tables.

See Error Handling, Source.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Chapter 16

Connected Query Classes

Understanding the Connected Query Classes

Connected query is a PeopleTools managed object that supports typical managed object functionality such as:

- Creating a new object.
- Editing an existing object.
- Deleting an object.
- Copying an object.
- Renaming an object.[1]
- Caching an object.
- Adding an object to a project.
- Using project compare functionality.
- Copying to or restoring from a file.
- Upgrading to the database.

[1] Renaming a connected query object is supported on a managed object level, but is not exposed as a function in PeopleCode.

A connected query object is exposed to the report developer through the public methods and properties of the PT_CONQRS application package. The remainder of this chapter provides reference on those classes, methods, and properties.

Connected queries are described in more detail in the PeopleSoft Query PeopleBook.

Related Links

"Understanding Connected Query" (PeopleTools 8.54: Query)

Importing Connected Query Classes

The connected query classes are application classes, not built-in classes, like Rowset, Field, Record, and so on. Before you can use these classes in your PeopleCode program, you must import them into your program.

An import statement either names a particular application class or imports all the classes in a package.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Using the asterisks after the package name makes all the application classes directly contained in the named package available. Application classes contained in subpackages of the named package are not made available.

CONQRSMGR Class

This section provides an overview of the CONQRSMGR class and discusses:

- CONQRSMGR class constructor.
- CONQRSMGR class methods.
- CONQRSMGR class properties.

CONQRSMGR Class Constructor

This section presents the constructor for the CONQRSMGR class.

CONQRSMGR

Example

```
import PT_CONQRS:CONQRSMGR;

Local PT_CONQRS:CONQRSMGR &objConQrsInst = create PT_CONQRS:CONQRSMGR(&sOprId, &sCO⇒
NQRSNAME);
```

Note: The first parameter is not required; an empty string can be specified instead.

Related Links

Constructors
Import Declarations

CONQRSMGR Class Methods

In this section, the CONQRSMGR class methods are presented in alphabetical order.

CleanOutputFile

Syntax

CleanOutputFile()

Description

Use this method to delete the connected query output file.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Note: This method is valid only for a connected query scheduled for running to a file—that is, when the run mode is equal to RunMode_Sched_File.

Parameters

None.

Returns

None.

Close

Syntax

```
Close()
```

Description

Use this method to clean up connected query resources.

Parameters

None.

Returns

None.

CopyDefn

Syntax

```
CopyDefn(target_UserID, target_ID)
```

Description

Use this method to copy the connected query definition to a new ID. The user's query access security is checked prior to the copy.

Parameters

target_UserID	Specifies the user ID of the owner of the new connected query as a string. An empty string indicates that the new connected query is public.
target_ID	Specifies the ID for the new connected query as a string.

Returns

A Boolean value: True if the copy is successful, False otherwise.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

DeleteDefn

Syntax

DeleteDefn()

Description

Use this method to delete the current connected query definition.

Parameters

None.

Returns

A Boolean value: True if the delete was successful, False otherwise.

ExistsByName

Syntax

ExistsByName(*ObjName*)

Description

Use this method to for the existence of a connected query definition based on the specified definition name.

Parameters

ObjName	Specifies the connected query definition name as a string.

Returns

A Boolean value: True if connected query definition exists, False otherwise.

GetSampleXMLString

Syntax

GetSampleXMLString(*RowNum*)

Description

Use this method to generate and return a sample XML string. Use this string with BI Publisher data sources based on a connected query.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

RowNum	Sets number of rows of sample data to generate for each member query.

Returns

A string representing the sample XML data.

Open

Syntax

```
Open(IsNew)
```

Description

Use this method to open a new or existing connected query definition.

This method should be called after a connected query object constructor. It initializes a new or existed connected query object.

Parameters

IsNew	Specifies as a Boolean value whether the connected query object represents a new connected query definition (True), or an existing definition (False).

Returns

A Boolean value: True if the open was successful, False otherwise.

ResetQueriesPrompt

Syntax

```
ResetQueriesPrompt()
```

Description

Use this method after a user clicks Cancel in a query prompt dialog.

Parameters

None.

Returns

None.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Run

Syntax

Run(*Prompts, runProcessInfo*)

Description

Use this method to run the connected query. The Run method is valid for the following run modes only:

- RunMode_Prev — Referred to as *preview mode.*
- RunMode_Sched_Web or RunMode_Sched_File — Referred to as *scheduled mode.*

If an error results, the Run method populates an error string with error details.

Preview Mode

In preview mode, the connected query is run immediately on the application sever. The output data is displayed in a separate browser window. In preview mode, the *Prompts* parameter is required; the *runProcessInfo* parameter *must* be set to Null. The *Prompts* parameter should be retrieved using the QueriesPromptsArray property. If this array length is greater than 0, this array must be populated.

Note: If both parameters are not null, the scheduling information is used to run the connected query by Process Scheduler.

Scheduled Mode

In scheduled mode, the connected query is run by Process Scheduler. In the case of RunMode_Sched_File, the output data is written to an XML file. In the case of RunMode_Sched_Web, the output data is accessible via a hyperlink in Process Monitor. In scheduled mode, the *runProcessInfo* parameter is required; the *Prompts* parameter should be set to Null.

Note: If both parameters are not null, the scheduling information is used to run the connected query by Process Scheduler.

Parameters

Prompts	Specifies the prompts for execution of the queries as an array of QUERYITEMPROMPT objects. This parameter should be set to null when running in scheduled mode.
runProcessInfo	Specifies the scheduling information for running the queries as a SCHED_INFO object. This parameter *must* be null when running in preview mode.

Returns

A Boolean value: True if the connected query was run successfully, False otherwise.

Related Links

RunToWindow

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

RunToXMLFormattedString
QueriesPromptsArray
RunMode
QUERYITEMPROMPT Class
SCHED_INFO Class
Running a Connected Query in Scheduled Mode
Running a Connected Query in Preview Mode or Background Mode

RunToWindow

Syntax

RunToWindow()

Description

Use this method to run a connected query in *background mode.* Similar to preview mode, running a connected query in background mode results in the output data being displayed in a separate browser window. However, in background mode, the connected query is run through Process Scheduler with a REN server. Running a connected query in this manner prevents blocking on the application server. While the report file is generated, the user can continue working with the PeopleSoft application and the application server environment.

To specify the scheduling information, prior to invoking the RunToWindow method, you must invoke the SetRunControlData method as follows:

```
&res = &objConQrsInst.SetRunControlData(&objConQrsInst.Const.RunCntlId_Auto, False)⇒
;
```

The RunToWindow method is valid for the RunMode_Window run mode only.

Parameters

None.

Returns

The process ID as a number.

Related Links

Run
RunToXMLFormattedString
RunMode
Running a Connected Query in Preview Mode or Background Mode

RunToXMLFormattedString

Syntax

RunToXMLFormattedString(*Prompts*)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use this method to run the connected query immediately on the application server with output to an XML formatted string instead of an XML file.

The RunToXMLFormattedString method is valid for the RunMode_XMLFormattedString run mode only.

Parameters

Prompts Specifies the prompts for execution of the queries as an array of QUERYITEMPROMPT objects. This parameter should be retrieved using the QueriesPromptsArray property. If this array length is greater than 0, this array must be populated.

Returns

The formatted XML as a string.

Related Links

Run
RunToWindow
QueriesPromptsArray
RunMode
QUERYITEMPROMPT Class

Save

Syntax

Save()

Description

Use this method to save the connected query object to the database as a connected query definition. If the connected query does not pass validation, it is saved with an inactive status.

Parameters

None.

Returns

A Boolean value: True if the save was successful, False otherwise.

SaveRunControlParms

Syntax

SaveRunControlParms(*runCntlID*)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use this method to save the in-memory process request parameter array to the database. This method is also called internally from the SetRunControlData method when *IsChangeDB* is true.

Parameters

runCntlID	Specifies the run control ID as a string.

Returns

A Boolean value: True if the save was successful, False otherwise.

Related Links

SetRunControlData

SetRunControlData

Syntax

```
SetRunControlData(runCntlID, IsNewCtrl, IsChangeDB)
```

Description

Use this as an interactive method to prompt the user if member queries have prompts. This method saves prompt data to the database using the PSCONQRSRUNPRM or PSCONQRSRUNPRMX records if the *IsChangeDB* parameter is passed as true. Call this method prior to scheduling a connected query to run in scheduled mode.

Parameters

runCntlID	Specifies the run control ID as a string.
IsNewCtrl	Specifies as a Boolean value whether the run control is new.
IsChangeDB	Specifies as a Boolean value whether to write the run control information to the database.

Returns

A Boolean value: True if the run control parameters were set successfully, False otherwise.

Validate

Syntax

```
Validate()
```

Description

Use this method to validate the following:

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- The existence of each query used in the connected query.
- Whether mapped fields used in the connected query object are still part of the QueryOutputFields collection for each query.
- The user security access for each query.

If validation fails, Validate populates an error string with the error details.

Parameters

None.

Returns

A Boolean value: True if the connected query passes all the validation checks, False otherwise.

Related Links

QueryOutputFields

ValidateIfFieldsMapped

Syntax

ValidateIfFieldsMapped()

Description

Use this method to check whether all queries have mapped fields. Use this method to confirm that it is the report developer's intention to have unmapped fields in the queries.

If validation fails, ValidateIfFieldsMapped populates an error string with the names of the unlinked queries.

Parameters

None.

Returns

A Boolean value: True if all the queries have mapped fields, False otherwise.

ValidateRunControlParms

Syntax

ValidateRunControlParms(*runCntlID*)

Description

Use this method to determine whether sufficient populated records exist in the or PSCONQRSRUNPRMX tables for the specified run control ID. ValidateRunControlParms compares the number of entries in the parameter tables with the number of prompts required for the connected query.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

If validation fails, ValidateRunControlParms populates an error string with the error details.

Parameters

runCntlID Specifies the run control ID as a string.

Returns

A Boolean value: True if the validation is successful, False otherwise.

CONQRSMGR Class Properties

In this section, the CONQRSMGR class properties are presented in alphabetical order.

Const

Description

This property returns a CONQRS_CONST object.

This property is read-only.

Related Links

CONQRS_CONST Class

Description

Description

Use this property to set or return a description for the connected query as a string.

This property is read-write.

Details

Description

Use this property to set or return a long description for the connected query as a string.

This property is read-write.

ErrString

Description

This property returns the error message as a string if an error occurs during processing.

This property is read-only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ExecutionLog

Description

Use this property to return a Boolean value indicating whether to perform execution logging while executing the connected query.

This property is read-only.

Note: While this property is read-only, it can be set through the PropertyArray property.

The default value is False.

Related Links

IsDebugMode
PropertyArray

IgnoreRelFldOutput

Description

Use this property to return a Boolean value indicating whether to create XML output without related field nodes.

This property is read-only.

Note: While this property is read-only, it can be set through the PropertyArray property.

The default value is False.

Related Links

PropertyArray

IsChanged

Description

This property returns a Boolean value indicating whether the connected query has been changed.

Note: When an existing connected query is opened, IsChanged is initialized to False.

This property is read-only.

IsDebugMode

Description

Use this property to return a Boolean value indicating whether to perform logging while executing the connected query. In addition, in debug mode, temporary files generated during execution of the connected

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

query are not deleted after execution is complete. The log also contains SQL statements generated by each member query as well as values for the related fields used to link the parent query to its children.

This property is read-only.

Note: While this property is read-only, it can be set through the PropertyArray property.

The default value is False.

Related Links

ExecutionLog
PropertyArray

IsInit

Description

This property returns a Boolean value indicating whether the connected query object has been initialized (opened) after object instance was created.

This property is read-only.

IsPublic

Description

This property returns a Boolean value indicating whether the connected query is public.

This property is read-only.

LastUpdatedBy

Description

This property returns the user ID of the user to have last updated the connected query, as a string.

This property is read-only.

LastUpdateDTTM

Description

This property returns the last update date and time for the connected query, as a DateTime value.

This property is read-only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

MaxRowsPerQuery

Description

Use this property to set or return a number representing the maximum number of rows returned by each query in preview mode. If set to 0, no maximum is set.

This property is read-write.

Name

Description

This property returns the name of the connected query as a string.

This property is read-only.

ObjectRowset

Description

Use this property to set or return a Rowset object. The parent record for this rowset is PSCONQRSMAPVW; its child record is PSCONQRSFLDRLVW. Use of the ObjectRowset property and its associated rowset prevents the report developer from directly manipulating the managed object itself.

Getting the ObjectRowset property returns a Rowset object with the following structure, populated with Connected Query Manager data:

```
ObjectRowset = CreateRowset(Record.PSCONQRSMAPVW, CreateRowset(Record.PSCONQRSFLDRL⇒
VW));
```

Setting the ObjectRowset property returns the rowset data back to the Connected Query Manager.

This property is read-write.

Related Links

Iterating Through a Connected Query Opened for Editing

OprID

Description

This property returns a string representing the user ID to which the connected query belongs to for private queries. For public queries, an empty string is returned.

This property is read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

OutProcessFileName

Description

This property returns a string representing the output file name as an absolute path.

Note: This property is valid only for a connected query scheduled for running to a file—that is, when the run mode is equal to RunMode_Sched_File.

This property is read-only.

PropertyArray

Description

Use this property to set or return an array of CONQRSPROPERTY objects (properties) for the connected query. If no properties exist, this array returns the default set of properties.

This property is read-write.

The following read-only properties of the CONQRSMGR class are dynamically synchronized whenever the PropertyArray property is set or returned:

- ExecutionLog
- IgnoreRelFldOutput
- IsDebugMode
- ShowFormattedXML

Example

The first example retrieves a set of properties from the database and populates the page grid using the Page Activate event:

```
import PT_CONQRS:CONQRSMGR;
import PT_CONQRS:CONQRSPROPERTY;

Component PT_CONQRS:CONQRSMGR &cConQrsInst;

Local array of PT_CONQRS:CONQRSPROPERTY &propArr;
Local Rowset &rsProp;
Local number &i, &j;

&propArr = &cConQrsInst.PropertyArray;
If &propArr.Len = 0 Then
   Return;
End-If;
Local Record &recProp, &recWrk;
&rsProp = GetLevel0()(1).GetRowset(Scroll.PSCONQRSPROP);
&rsProp.Flush();
For &i = 1 To &propArr.Len
   If &i > 1 Then
      &rsProp.InsertRow(&i - 1);
   End-If;
   &recProp = &rsProp(&i).PSCONQRSPROP;
   &recProp.PROPVALUEOPTION.ClearDropDownList();
   For &j = 1 To &propArr [&i].PROPVALUEARRAY.Len
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
      &recProp.PROPVALUEOPTION.AddDropDownItem(&propArr [&i].PROPVALUEARRAY [&j], &⇒
propArr [&i].PROPVALUEARRAYDESC [&j]);
   End-For;
   &recProp.PROPNAME.Value = &propArr [&i].PROPNAME;
   &recProp.PROPVALUEOPTION.Value = &propArr [&i].PROPVALUE;
   &recProp.OPRID.Value = &cConQrsInst.OprID;
   &recProp.CONQRSNAME.Value = &cConQrsInst.Name;

   &recWrk = &rsProp(&i).PSCONQRS_WRK;
   &recWrk.PROPVALUEOPTION.Value = &propArr [&i].PROPDEFAULT;
End-For;
```

The second example populates a property array from a page grid. This program is executed when a user hits the OK button on a secondary page, PSCONQRSPROPS:

```
import PT_CONQRS:CONQRSMGR;
import PT_CONQRS:CONQRSPROPERTY;

Component PT_CONQRS:CONQRSMGR &cConQrsInst;

If %Page = Page.PSCONQRSPROPS Then
   Local array of PT_CONQRS:CONQRSPROPERTY &propArr;
   Local Rowset &rsProp;
   Local number &i;
   Local Record &recProp, &recWrk;

   /* Get the property array from the database.            */
   &propArr = &cConQrsInst.PropertyArray;
   If &propArr.Len = 0 Then
      Return;
   End-If;

   &rsProp = GetLevel0()(1).GetRowset(Scroll.PSCONQRSPROP);
   If &propArr.Len <> &rsProp.ActiveRowCount Then
      Return;
   End-If;

   For &i = 1 To &rsProp.ActiveRowCount
      &recProp = &rsProp(&i).PSCONQRSPROP;
      &recWrk = &rsProp(&i).PSCONQRS_WRK;
      If None(&recProp.PROPNAME.Value) Then
         &recProp.PROPNAME.Value = &recWrk.PROPVALUEOPTION.Value;
      End-If;
      &propArr [&i].PROPNAME = &recProp.PROPNAME.Value;
      &propArr [&i].PROPVALUE = &recProp.PROPVALUEOPTION.Value;
      &propArr [&i].PROPDEFAULT = &recWrk.PROPVALUEOPTION.Value;
   End-For;

   /* Return the modified property array to the database.  */
   &cConQrsInst.PropertyArray = &propArr;
End-If;
```

Related Links

ExecutionLog

IgnoreRelFldOutput

IsDebugMode

ShowFormattedXML

CONQRSPROPERTY Class

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

QueriesPromptsArray

Description

This property returns an array of QUERYITEMPROMPT objects. This array is used by the connected query object as a parameter to the Run method in preview mode.

This property is read-only.

Related Links

QUERYITEMPROMPT Class

QueryArray

Description

This property returns an array of string representing the query names that constitute the connected query object.

This property is read-only.

RegisteredBy

Description

This property returns a string representing the user ID of the user who created the connected query object.

This property is read-only.

RegisteredDTTM

Description

This property returns the creation date and time for the connected query, as a DateTime value.

This property is read-only.

RunCntlId

Description

This property returns a string representing the run control ID for scheduling the connected query.

This property is read-only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

RunControlParArray

Description

This property returns an array of PSCONQRSRUNPRM records to be used for displaying and updating the set of scheduling parameters for the queries.

This property is read-only.

RunMode

Description

This property returns a number representing the run mode for a connected query instance. The values are:

Numeric Value	*Constant Value*	*Description*
1	RunMode_Window	Run the connected query in background mode with output to a separate browser window. The connected query runs via Process Scheduler and uses a REN server for delivering the output XML to the user. The XML result file is delivered to both the REN server window and the Report Manager.
2	RunMode_Sched_Web	Run the connected query at a scheduled time with output to web. The connected query is scheduled to output the XML result file to the Report Manager. It can be accessed by the user via a Report Manager link.
3	RunMode_Sched_File	Run the connected query at a scheduled time with output to a file name and location specified by the user.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Numeric Value	*Constant Value*	*Description*
4	RunMode_Prev	Run the connected query immediately in preview mode with output to a separate browser window. The connected query is executed immediately on the application server with output to a separate browser window. The output XML is not formatted internally; the only formatting that occurs is performed by the browser. Because results only exist for the browser session and are not preserved, this mode should be used during connected query creation, debugging, and tuning only. **Important!** When using the preview mode, set a limit on the number of rows returned from each query. See MaxRowsPerQuery, RunMode_Prev_DefRowNumber.
5	RunMode_Sample	Run the connected query immediately with output to a file that is suitable as a BI Publisher data source.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Numeric Value	*Constant Value*	*Description*
6	RunMode_XMLFormattedString	Run the connected query immediately with output to a formatted XML string. This formatted XML string is larger than the unformatted XML of the RunMode_Prev mode. The connected query is executed immediately on the application server with output to a formatted XML string. This string is formatted according to the XML DOM object and is suitable for displaying in a long edit box. This mode is used by the Connected Query Quick Start wizard in which XML results are previewed on the application page in a long edit box. **Important!** When using the formatted XML string preview mode, set a limit on the number of rows returned from each query. See MaxRowsPerQuery, RunMode_Prev_DefRowNumber.

This property is read-only.

Related Links

Run
RunToWindow
RunToXMLFormattedString
RunMode_Prev
RunMode_Sample
RunMode_Sched_File
RunMode_Sched_Web
RunMode_Window
RunMode_XMLFormattedString

SchedInfo

Description

Use this property to set or return a SCHED_INFO object to be populated with scheduling details. Use the property as a parameter to the Run method for scheduling connected query execution when the run mode is RunMode_Window, RunMode_Sched_Web, or RunMode_Sched_File.

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

SCHED_INFO Class

SchedRequestType

Description

Use this property to set or return a string indicating which application scheduled the connected query process. The values are:

Value	*Description*
CQR	Connected Query Manager
XMLP	BI Publisher

Separate run control parameter records (PSCONQRSRUNPRM or PSCONQRSRUNPRMX) are used for different values of this property.

This property is read-write.

SecProfile

Description

This property returns a SEC_PROFILE object, which shows the user's query access level as defined for the query.

This property is read-only.

Related Links

SEC_PROFILE Class

ShowFormattedXML

Description

Use this property to return a Boolean value indicating whether to retain indentation when generating XML output.

This property is read-only.

Note: While this property is read-only, it can be set through the PropertyArray property.

The default value is False.

Related Links

PropertyArray

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Status

Description

Use this property to set or return a string representing the status of the connected query. The values are:

Value	*Description*
A	Active
I	Inactive

Value	*Description*
P	In progress.

This property is read-write.

XMLDataFileName

Description

This property returns the short name for the XML data file as a string.

This property is read-only.

XMLDataFullName

Description

This property returns the long name for the XML data file as a string.

This property is read-only.

CONQRSPROPERTY Class

The CONQRSPROPERTY class is a data structure that exposes connected query properties. Individual members of the CONQRSPROPERTY class should be retrieved and set through the CONQRSMGR class, PropertyArray property, which is an array of CONQRSPROPERTY objects.

Related Links

PropertyArray

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

CONQRSPROPERTY Class Properties

In this section, the CONQRSPROPERTY class properties are presented in alphabetical order.

PROPDEFAULT

Description

Use this property to set or return the default property value as a string.

This property is read-write.

PROPNAME

Description

Use this property to set or return the property name as a string.

This property returns a Boolean value indicating that the specified connected query already exists. The value is False.

This property is read-write.

PROPVALUE

Description

Use this property to set or return the current property value as a string.

This property is read-write.

PROPVALUEARRAY

Description

Use this property to set or return an array of string representing the valid property values.

This property is read-write.

PROPVALUEARRAYDESC

Description

Use this property to set or return an array of string representing the descriptions for the valid property values.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

CONQRS_CONST Class

This section provides an overview of the CONQRS_CONST class and discusses CONQRS_CONST class properties.

The CONQRS_CONST class is a data structure that exposes read-only properties representing constant values. An instance of the CONQRS_CONST class is created through the Const property of the CONQRSMR class.

Related Links

Const

CONQRS_CONST Class Properties

In this section, the CONQRS_CONST class properties are presented in alphabetical order.

InitExisting

Description

This property returns a Boolean value indicating that the specified connected query already exists. The value is False.

Use InitExisting as an argument to the Open method.

This property is read-only.

Related Links

Open

InitNew

Description

This property returns a Boolean value indicating that the specified connected query is new. The value is True.

Use InitNew as an argument to the Open method.

This property is read-only.

Related Links

Open

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

MsgSet

Description

This property returns the number 241 as the message set number for connected query.

This property is read-only.

RunCntlId_Auto

Description

This property returns the string PSCONQRS_AUTORUN.

Use this property with the SetRunControlData method for the RunMode_Window mode. It indicates that the run control ID for the connected query process should be generated automatically.

This property is read-only.

Related Links

SetRunControlData
RunMode_Window

RunMode_Prev

Description

This property returns the number 4, which represents the preview run mode with output to a separate browser window.

The connected query is executed immediately on the application server with output to a separate browser window. The output XML is not formatted internally; the only formatting that occurs is performed by the browser. Because results only exist for the browser session and are not preserved, this mode should be used during connected query creation, debugging, and tuning only.

Note: When using the preview mode, set a limit on the number of rows returned from each query.

This property is read-only.

Related Links

Run
RunMode
MaxRowsPerQuery
RunMode_Prev_DefRowNumber

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

RunMode_Prev_DefRowNumber

Description

This property returns the number 6, which represents the default number of rows returned for connected queries running in the RunMode_Prev or RunMode_XMLFormattedString modes.

This property is read-only.

Related Links

MaxRowsPerQuery
RunMode_Prev
RunMode_XMLFormattedString

RunMode_Sample

Description

This property returns the number 5, which represents a run mode that produces a sample XML string that can be used by a BI Publisher data source as a sample XML string.

This property is read-only.

Related Links

RunMode

RunMode_Sched_File

Description

This property returns the number 3, which represents the scheduled run mode with output to a file name and location specified by the user.

This property is read-only.

Related Links

Run
RunMode

RunMode_Sched_Web

Description

This property returns the number 2, which represents the scheduled run mode with output to the web (that is, Report Manager).

The output can be accessed by the user via a Report Manager link.

This property is read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

Run
RunMode

RunMode_Window

Description

This property returns the number 1, which represents the background run mode with output to a separate browser window.

The connected query runs via Process Scheduler and uses a REN server for delivering the output XML to the user. The XML result file is delivered to both the REN server window and the Report Manager.

This property is read-only.

Related Links

RunToWindow
RunMode

RunMode_XMLFormattedString

Description

This property returns the number 6, which represents the run mode that produces an formatted XML string. This formatted XML string is larger than the unformatted XML of the RunMode_Prev mode.

The connected query is executed immediately on the application server with output to a formatted XML string. This string is formatted according to the XML DOM object and is suitable for displaying in a long edit box. This mode is used by the Connected Query Quick Start wizard in which XML results are shown on the application page in a long edit box.

Note: When using the preview mode, set a limit on the number of rows returned from each query.

This property is read-only.

Related Links

RunToXMLFormattedString
RunMode
MaxRowsPerQuery
RunMode_Prev_DefRowNumber

SchedRequest_CQR

Description

This property returns the string CQR representing that connected query execution was invoked by the Connected Query Manager. The value of this property is used as a part of the SCHED_INFO data structure.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-only.

SchedRequest_XMLP

Description

This property returns the string XMLP, representing that connected query execution was invoked by BI Publisher. The value of this property is used as a part of the SCHED_INFO data structure.

This property is read-only.

Stat_Active

Description

This property returns the string A indicating that the connected query definition is active.

This property is read-only.

Stat_InActive

Description

This property returns the string I indicating that the connected query definition is inactive. A connected query can be set to inactive if it did not pass a validation.

This property is read-only.

Stat_InProgress

Description

This property returns the string P indicating that the connected query definition is in progress. A connected query that is “in process” be run in preview mode only. It cannot be scheduled, and it is not be visible to BI Publisher.

This property is read-only.

QUERYITEMPROMPT Class

This section provides an overview of the QUERYITEMPROMPT class and discusses QUERYITEMPROMPT class properties.

The QUERYITEMPROMPT class is a data structure that exposes read-only properties representing query prompts. An array of instances of this class is exposed via the QueriesPromptsArray property of the CONQRSMR class. Therefore, only an import statement is required, and no constructor:

```
import PT_CONQRS:QUERYITEMPROMPT;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

QueriesPromptsArray
Import Declarations

QUERYITEMPROMPT Class Properties

In this section, the QUERYITEMPROMPT class properties are presented in alphabetical order.

QueryName

Description

This property returns as string representing the name of a query that participates in the connected query.

This property is read-only.

QueryPromptRecord

Description

This property returns a Record object with the runtime prompts for the query.

This property is read-only.

SCHED_INFO Class

This section provides an overview of the SCHED_INFO class and discusses SCHED_INFO class properties.

The SCHED_INFO class is a data structure that exposes the class constructor and read-write properties representing run controls and scheduling information. An instance of this class is exposed via the SchedInfo property of the CONQRSMR class. Therefore, only an import statement is required, and no constructor:

```
import PT_CONQRS:SCHED_INFO;
```

Related Links

SchedInfo
Import Declarations

SCHED_INFO Class Properties

In this section, the SCHED_INFO class properties are presented in alphabetical order.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

AE_ID

Description

Use this property to set or return a string indicating which application scheduled execution of the connected query. The values are:

Value	*Description*
CQR (the default)	Connected Query Manager
XMLP	BI Publisher

This property is read-write.

DIRLOCATION

Description

Use this property to set or return a string representing the directory location for temporary files generated during processing of a scheduled connected query. This directory should be the same as the log/output directory specified in the psprcs.cfg file, allowing the connected query to use the distribution features of Process Scheduler.

This property is read-write.

OPRID

Description

Use this property to set or return a string representing the ID of the user who initiated the process.

This property is read-write.

OUTDESTTYPE

Description

Use this property to set or return the Process Scheduler output destination type as a number. The values are:

Value	*Description*
2	File
4	Window
6	Web

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

PRCSFILENAME

Description

Use this property to set or return the output file name as a string. This property is required when OUTDESTTYPE equals 2 (file). Specify an absolute path and file name that is accessible by the Process Scheduler server.

This property is read-write.

PROCESS_INSTANCE

Description

Use this property to set or return the process instance as a string.

This property is read-write.

RUN_CNTL_ID

Description

Use this property to set or return the run control ID as a string.

This property is read-write.

SEC_PROFILE Class

This section provides an overview of the SEC_PROFILE class and discusses:

- SEC_PROFILE class constructor.
- SEC_PROFILE class properties.

The SEC_PROFILE class is a data structure that exposes the class constructor and read-only properties representing the security access to the connected query for this user's session.

Related Links

SecProfile

SEC_PROFILE Class Constructor

This section presents the constructor for the SEC_PROFILE class.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SEC_PROFILE

Example

```
import PT_CONQRS:SEC_PROFILE;
```

```
Local PT_CONQRS:SEC_PROFILE &SecProfile = create PT_CONQRS:SEC_PROFILE();
```

Related Links

Constructors
Import Declarations

SEC_PROFILE Class Properties

In this section, the SEC_PROFILE class properties are presented in alphabetical order.

CanCreatePublic

Description

This property returns a Boolean value indicating whether the user can create a public connected query.

This property is read-only.

CanModify

Description

This property returns a Boolean value indicating whether the user can modify the connected query.

This property is read-only.

CanRunQuery

Description

This property returns a Boolean value indicating whether the user can run the connected query.

This property is read-only.

UTILITY Class

This section provides an overview of the UTILITY class and discusses:

- UTILITY class constructor.
- UTILITY class methods.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The UTILITY class is a data structure that exposes the class constructor and utility methods used for validation. The UTILITY class does not require that a connected query be opened first.

UTILITY Class Constructor

This section presents the constructor for the UTILITY class.

UTILITY

Example

```
import PT_CONQRS:UTILITY;
```

```
Local PT_CONQRS:UTILITY &Utility = create PT_CONQRS:UTILITY();
```

Related Links

Constructors
Import Declarations

UTILITY Class Methods

In this section, the UTILITY class methods are presented in alphabetical order.

CheckQryForTreePrompt

Syntax

CheckQryForTreePrompt(*QryName*, *scope*)

Description

Use this method to checks if a specific query uses tree prompts.

Important! Connected query does not support queries with tree prompts.

Parameters

QryName Specifies the query name as a string.

scope Specifies the query scope as a string. If a valid value is not specified, CheckQryForTreePrompt searches to determine the scope. The values are:

- R — Private
- U — Public

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

The empty string if the query does not use tree prompts; otherwise, an error string.

CheckQrySecurity

Syntax

CheckQrySecurity(*QryName*, *IsPublicObject*)

Description

Use this method to check user access security for a single query. CheckQrySecurity performs the following checks:

- Whether the query is public for public connected queries (*IsPublicObject* is True).
- Whether the query is disabled.
- Whether the query has tree prompts by invoking CheckQryForTreePrompt.
- Whether there are query prompt security violations.

Parameters

QryName	Specifies the query name as a string.
IsPublicObject	Specifies a Boolean value indicating whether the connected query is public.

Returns

A Boolean value: True if the security validation was successful, False otherwise.

GetQueryScopeByName

Syntax

GetQueryScopeByName(*QryName*)

Description

Use this method to check whether the specified query has a public or private scope.

Parameters

QryName	Specifies the query name as a string.

Returns

A number:

- 0 — Private query.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- 1 — Public query.
- 2 — Query not found.

ValidateObjectID

Syntax

ValidateObjectID(*ID*)

Description

Use this method to check whether the specified ID (connected query ID or run control ID) contains special characters. Valid characters for IDs include A-Z, 0–9, and _.

Parameters

ID	Specifies the ID to be validated as a string.

Returns

An empty string if the validation was successful; otherwise, an error string.

Connected Query Classes Examples

This section includes examples of:

- Running a connected query in scheduled mode.
- Running a connected query in preview mode or background mode.
- Iterating through a connected query opened for editing.

Running a Connected Query in Scheduled Mode

In scheduled mode, the connected query is run by Process Scheduler. In the case of RunMode_Sched_File, the output data is written to an XML file. In the case of RunMode_Sched_Web, the output data is accessible via a hyperlink in Process Monitor. In scheduled mode, the *runProcessInfo* parameter is required; the *Prompts* parameter should be set to Null.

The following example represents a PeopleCode step to be run via Application Engine:

```
import PT_CONQRS:CONQRSMGR;
import PT_CONQRS:SCHED_INFO;

Local PT_CONQRS:CONQRSMGR &cConQrsInst;
Local boolean &result;
Local string &PRCSFILENAME;
Local string &sPrcsName = "PSCONQRS";
Local string &sPrcsType = "Application Engine";
Local number &nOrigPSMessagesMode = %Session.PSMessagesMode;
%Session.PSMessagesMode = 1;

/* While working with connected queries, it is recommended to use a try- */
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
/* catch block                                                          */

try

   /* Create and open an object. System tries to find a connected query  */
   /* with private ownership first for current user. If not found, it    */
   /* uses a public ownership                                            */

   &ConQrsInst = create PT_CONQRS:CONQRSMGR("", PSCONQRS_AET.CONQRSNAME);

   &result = &ConQrsInst.Open(&ConQrsInst.Const.InitExisting);

   &str = &ConQrsInst.ErrString;
   If &str <> "" Then
      WriteToLog(%ApplicationLogFence_Error, &ConQrsInst.ErrString);
      %Session.PSMessagesMode = &nOrigPSMessagesMode;
      Exit (1);
   End-If;


   If &result Then

      /* Get an empty SCHEDINFO structure and populate it.               */
      &schedInfo = &ConQrsInst.SchedInfo;
      &schedInfo.DIRLOCATION = %FilePath;
      &schedInfo.OUTDESTTYPE = String(%OutDestType);
      &schedInfo.RUN_CNTL_ID = PSCONQRS_AET.RUN_CNTL_ID;
      &schedInfo.PROCESS_INSTANCE = PSCONQRS_AET.PROCESS_INSTANCE;
      &schedInfo.OPRID = PSCONQRS_AET.OPRID;
      If %OutDestType = 2 Then /* FILE */
         Local string &sqlFile = "SELECT OUTDEST FROM PS_PRCSRUNCNTLDTL WHERE OPRID⇒
=:1 and RUNCNTLID =:2 and PRCSTYPE =:3 and PRCSNAME =:4";
         SQLExec(&sqlFile, PSCONQRS_AET.OPRID, PSCONQRS_AET.RUN_CNTL_ID, &sPrcsType⇒
, &sPrcsName, &PRCSFILENAME);
      End-If;
      &schedInfo.PRCSFILENAME = &PRCSFILENAME;

      /* Indicate the source of the scheduled request as CQR.            */
      &schedInfo.AE_ID = &ConQrsInst.Const.SchedRequest_CQR;

      /* Schedule the query to run. Note that for scheduled connected    */
      /* queries, the Prompts parameter is Null.                         */
      &result = &ConQrsInst.Run( Null, &schedInfo);
   End-If;
   If &result Then
      %Session.PSMessagesMode = &nOrigPSMessagesMode;
      Exit (0);
   Else

      /* Check for errors  */
      &str = &ConQrsInst.ErrString;
      If &str <> "" Then
         WriteToLog(%ApplicationLogFence_Error, &ConQrsInst.ErrString);
      End-If;
      /* check session message for errors */
      If %Session.PSmessages.Count > 0 Then
         &PSMessages = %Session.PSmessages;
         For &i = 1 To &PSMessages.Count
            If (&PSMessages.Item(&i).MessageType <= 1) Then
               &MsgSetNbr = &PSMessages.Item(&i).MessageSetNumber;
               &MsgNbr = &PSMessages.Item(&i).MessageNumber;
               WriteToLog(%ApplicationLogFence_Error, MsgGet(&MsgSetNbr, &MsgNbr, "⇒
Message Not Found : " | &MsgSetNbr | "," | &MsgNbr));
            End-If;
         End-For;
      End-If;
   End-If;

   %Session.PSMessagesMode = &nOrigPSMessagesMode;

catch Exception &Err
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
   WriteToLog(%ApplicationLogFence_Error, &Err.ToString());
end-try;
```

Running a Connected Query in Preview Mode or Background Mode

In preview mode, the connected query is run immediately on the application sever. The output data is displayed in a separate browser window. In preview mode, the *Prompts* parameter is required; the *runProcessInfo* parameter *must* be set to Null. The *Prompts* parameter should be retrieved using the QueriesPromptsArray property. If this array length is greater than 0, this array must be populated.

Similar to preview mode, running a connected query in background mode results in the output data being displayed in a separate browser window. However, in background mode, the connected query is run through Process Scheduler with a REN server. Running a connected query in this manner prevents blocking on the application server. While the report file is generated, the user can continue working with the PeopleSoft application.

In the following example, assume that an application calls the RunConnectedQuery function with all required parameters. The function returns an error string if any error occurs.

```
import PT_CONQRS:CONQRSMGR;
import PT_CONQRS:QUERYITEMPROMPT;

Function ShowException(&errString As Exception);

   /* Perform exception processing  */

End-Function;

Function RunConnectedQuery(&sOprId As string, &sCONQRSNAME As string, &RunMode As n⇒
umber) Returns string

   Local boolean &result;
   Local array of PT_CONQRS:QUERYITEMPROMPT &aPrompts;
   Local string &str;
   Local number &processID;
   Local boolean &IsChangeDB, &IsNewCnt;
   Local PT_CONQRS:CONQRSMGR &cConQrsInst;

   /* While working with connected queries, it is recommended to use a try- */
   /* catch block                                                           */

   try

      /* Create and open an object. System tries to find a connected query  */
      /* with private ownership first for current user. If not found, it    */
      /* uses a public ownership                                            */

      &cConQrsInst = create PT_CONQRS:CONQRSMGR("", &sCONQRSNAME);
      &result = &cConQrsInst.Open(&cConQrsInst.Const.InitExisting);

      /* Check for errors  */
      &str = &cConQrsInst.ErrString;
      If &str <> "" Then
         Error &cConQrsInst.ErrString;
      End-If;

      /* Validate the previously opened connected query object              */
      If Not &cConQrsInst.Validate() Then
         &str = &cConQrsInst.ErrString;
         If &str <> "" Then
            Error &cConQrsInst.ErrString;
         End-If;
      End-If;

      /* Preview Mode- AppServer execution */
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
      /* Populate prompts. NOTE: It is required for 'interactive' execution */
      /* using an application server. In the case of scheduled execution,   */
      /* prompts are read from the database                                 */
      If &RunMode = &cConQrsInst.Const.RunMode_Prev Then
         &aPrompts = FillQueriesPrompts();
         If None(&aPrompts) Then
            /* User hit Cancel on a Prompt dialog */
            &cConQrsInst.ResetQueriesPrompt();
            Return &cErrIndicator;
         End-If;

         /* Restrict number of rows being displayed for each member query.  */
         /* If user does not set this value, the default number is used     */
         If All(PSCONQRS_WRK.QRY_MAX_FETCH) Then
            &cConQrsInst.MaxRowsPerQuery = &numRows;
         Else
            &cConQrsInst.MaxRowsPerQuery = &cConQrsInst.Const.RunMode_Prev_DefRowNu⇒
mber;
         End-If;

         /* Run the connected query. NOTE: The runProcessInfo parameter is Null */
         &result = &cConQrsInst.Run(&aPrompts, Null);

      End-If; /* end of Mode selection */


      /* 'Run to Window' mode */
      If &RunMode = &cConQrsInst.Const.RunMode_Window Then
         &IsChangeDB = True;
         &IsNewCnt = False;

         /* You are required to set run control parameters for immediate    */
         /* execution using Process Scheduler                               */
         &result = &cConQrsInst.SetRunControlData(&cConQrsInst.Const.RunCntlId_Auto⇒
, &IsNewCnt, &IsChangeDB);
         If &result Then
            &processID = &cConQrsInst.RunToWindow();
            If All(&processID) Then
               &result = True;;
            End-If;
         End-If;
      End-If; /* end of Mode selection */

      /* Check for errors  */
      &str = &cConQrsInst.ErrString;
      If &str <> "" Then
         Error &cConQrsInst.ErrString;
      End-If;
      Return &str;

   catch Exception &Err
      ShowException(&Err);
   end-try;

End-Function;
```

Iterating Through a Connected Query Opened for Editing

This example demonstrates usage of the connected query ObjectRowset property. The program opens an instance from an existing connected query definition. The program retrieves the rowset from the ObjectRowset property, and changes some of its properties. It saves the rowset back to ObjectRowset property, and then saves the modified connected query definition back to the database.

```
import PT_CONQRS:CONQRSMGR;

Local PT_CONQRS:CONQRSMGR &cConQrsInst;
Local string &sOprId, &sCONQRSNAME, &str, &sQryParentName, &sQryChildName, &sFldNam⇒
ePar, &sFldNameChild;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
Local Rowset &rsObjectRowset, &rsObjectFields;
Local Record &rMapObjRec, &rFldObjRec;
Local number &i, &j, &seqNum, &fldNum;

Function ShowException(&errString As Exception);

End-Function;

/* While working with connected queries, it is recommended to use a try- */
/* catch block                                                           */

try

   /* Create and open an object. System tries to find a connected query  */
   /* with private ownership first for current user. If not found, it    */
   /* uses a public ownership                                            */

   &sCONQRSNAME = "MyConQuery";
   &cConQrsInst = create PT_CONQRS:CONQRSMGR("", &sCONQRSNAME);

   &res = &cConQrsInst.Open(&cConQrsInst.Const.InitExisting);
   &str = &cConQrsInst.ErrString;

   If &str <> "" Then
      Error &cConQrsInst.ErrString;
   End-If;

   /* Validate the previously opened connected query object              */
   If Not &cConQrsInst.Validate() Then
      &str = &cConQrsInst.ErrString;
      If &str <> "" Then
         Error &cConQrsInst.ErrString;
      End-If;
   End-If;

   /* Rowset retrieved from a connected query has the following          */
   /* structure: ObjectRowset = CreateRowset(Record.PSCONQRSMAPVW,       */
   /* CreateRowset(Record.PSCONQRSFLDRLVW));                             */

   &rsObjectRowset = &cConQrsInst.ObjectRowset;

   /* The rowset contains the internal connected query structure. The    */
   /* user can iterate the rowset, retrieve and modify member query      */
   /* names, list the related fields, list object properties, etc.       */

   For &i = 1 To &rsObjectRowset.ActiveRowCount
      &rMapObjRec = &rsObjectRowset(&i).PSCONQRSMAPVW;
      &sQryParentName = &rMapRec.GetField(Field.QRYNAMEPARENT).Value;
      &sQryChildName = &rMapRec.GetField(Field.QRYNAMECHILD).Value;
      &seqNum = &rsObjectRowset(&i).PSCONQRSMAPVW.SEQNUM.Value;

      &rsObjectFields = &rsObjectRowset(&i).GetRowset(Scroll.PSCONQRSFLDRLVW);
      For &j = 1 To &rsObjectFields.ActiveRowCount
         &rFldObjRec = &rsObjectFields(&j).PSCONQRSFLDRLVW;
         &fldNum = &rFldObjRec.SELCOUNT.Value;
         &sFldNamePar = &rFldObjRec.QRYFLDNAMEPAR.Value;
         &sFldNameChild = &rFldObjRec.QRYFLDNAMECHILD.Value;;
      End-For;
   End-For;

   /* The preceding for loop shows how to navigate a connected query's   */
   /* internal structure. It allows a report developer to change a       */
   /* connected query definition by modifying existing query members or  */
   /* by adding new ones -- queries or related fields.                   */


   /* Need to set the connected query's rowset to the retrieved rowset   */
   /* after any changes are made to the retrieved rowset.                */

   &cConQrsInst.ObjectRowset = &rsObjectRowset;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
      &Errstr = &cConQrsInst.ErrString;
      If &Errstr <> "" Then
         Error &cConQrsInst.ErrString;
      End-If;

      /* Set the connected query properties. Set the object's status to     */
      /* active, so it will be available for reporting use                  */

      &cConQrsInst.Description = "My Connected Query";
      &cConQrsInst.Details = "Includes QryA, QryA1, and QryC";
      &cConQrsInst.Status = "A";

      /* Save the connected query instance                                  */
      If Not &cConQrsInst.Save() Then
         If &cConQrsInst.ErrString <> "" Then
            Error &cConQrsInst.ErrString;
         End-If;
      End-If;

   catch Exception &Err
      ShowException(&Err);
   end-try;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Chapter 17

Crypt Class

Understanding the Crypt Class

The crypt class is used with pluggable cryptography. After you create an encryption profile, use PeopleCode to invoke the encryption profile for encrypting, decrypting, or signing a field, depending on the profile

Related Links

"Understanding Data Security" (PeopleTools 8.54: Security Administration)

Creating a Crypt Object

The crypt class does not have a separate function for instantiating an object (such as CreateCrypt.) Instead, you instantiate a crypt object using the CreateObject function, using the keyword **Crypt**.

```
&cry = CreateObject("Crypt");
```

See "CreateObject" (PeopleTools 8.54: PeopleCode Language Reference).

Declaring Crypt Objects

Crypt objects are declared by using the Crypt type name.

```
Local Crypt &MyCrypt;
```

Note: Crypt objects cannot be serialized, and so can only be declared as Local.

Scope of a Crypt Object

A crypt object can only be instantiated from PeopleCode. This object can be used anywhere you have PeopleCode, that is, in an application class, Component Interface PeopleCode, record field PeopleCode, and so on.

Crypt Class Methods

In this section, we discuss the crypt class methods. The methods are discussed in alphabetical order.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

FirstStep

Syntax

FirstStep()

Description

Use the FirstStep method to access the first step in the encryption chain.

You must use either the FirstStep or GoToStep methods before you use the NextStep or SetParameter methods.

Parameters

None.

Returns

None.

Related Links

GoToStep
NextStep
SetParameter

GoToStep

Syntax

GoToStep(*StepNum*)

Description

Use the GoToStep method to access a specific step in the encryption chain.

You must use either the GoToStep or FirstStep methods before you use the NextStep or SetParameter method.

Parameters

StepNum	Specify the step number that you want to access, as a number.

Returns

None.

Related Links

FirstStep
NextStep
SetParameter

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

LoadLibrary

Syntax

LoadLibrary(*LibraryFile, LibraryID*)

Description

Use the LoadLibrary method to specify the encryption library to be used. This method is generally used when either your underlying library changes (such as, a new version, added algorithms, and so on) or you have your written own library and you need to load the metadata into the PeopleSoft system.

Parameters

LibraryFile	Specify the name of the file containing the encryption library as a string. You do not have to specify a full path name. The delivered OpenSSL library is pspetssl.dll. The delivered PGP library is pspetpgp.dll.
LibraryID	Specify the name of the library, as a string.

Returns

None.

NextStep

Syntax

NextStep()

Description

Use the NextStep method to access the next step in the encryption chain.

You must use the FirstStep or GoToStep method before using NextStep.

Your program terminates if you call NextStep when you are already at the last step in the encryption chain.

Parameters

None.

Returns

None.

Related Links

FirstStep
GoToStep

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Open

Syntax

Open(*ProfileName*)

Description

Use the Open method to open the encryption profile identified by *ProfileName*. You must open an encryption profile before you can add data to the encryption profile. Your program terminates if you specify an encryption profile that doesn't exist.

Parameters

ProfileName Specify the name of the encryption profile you want to access, as a string. You can store the name of the encryption profile in a field, and specify a *fieldname.recordname*.

Returns

None.

Example

```
Local Crypt &cry;

&cry = CreateObject("Crypt");
&bar = QE_CRYPT_WRK.CRYPT_PRFL_ID;
&cry.Open(&bar);
&cry.UpdateData(QE_CRYPT_WRK.DESCRLONG);
QE_CRYPT_WRK.LARGECHAR = &cry.Result;
```

SetParameter

Syntax

SetParameter(*Name*, *Value*)

Description

Use the SetParameter method to set the parameter specified by *Name* to a value specified by *Value.*

You must have already used the FirstStep, NextStep, or GoToStep methods to specify a step before using this method.

Parameters

Name Specify the name of the parameter that you want to change, as a string.

Value Specify the value for the parameter that you want to change.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

None.

Related Links

FirstStep
GoToStep
NextStep

UpdateData

Syntax

UpdateData(*Data*)

Description

Use the UpdateData method to add data to the encryption chain. This method can be called multiple times after opening a profile to add data.

Parameters

Data	Specify the data you want to add to the encryption chain, as a string.

Returns

None.

Crypt Class Properties

This section describes the crypt class properties. The properties are described in alphabetical order.

Result

Description

After updating the encryption chain, the Result property contains the end result of the encryption chain. Once the result has been retrieved, it is no longer possible to update the object anymore.

This property is read-only.

Verified

Description

For algorithms that check a signature, the system sets the Verified property to true if the signature is valid, and false if the signature is invalid. For algorithms that do not check a signature, it always returns false.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Chapter 18

Document Classes

Understanding the Document Classes

A PeopleSoft document is a managed object that has two representations. The logical document depicts the document's structure. The physical document is the rendering of the document in a specific format—either in XML or as a relational record (or records).

PeopleCode provides document classes that contain built-in functions and methods that enable you to populate data into and retrieve data from logical documents. However, you should already have knowledge of the logical document structure in order to effectively write PeopleCode to work with a specific document.

Related Links

"Understanding PeopleSoft Documents Technology" (PeopleTools 8.54: Documents Technology)

Data Type and Scope of the Document Classes

Every document class is its own data type—that is, documents are declared as the Document data type, primitive objects are declared as the Primitive type, and so on. For example:

```
Local Document &Doc;
```

The following are the data types of the document classes:

- Document
- DocumentKey
- Primitive
- Compound
- Collection

Document objects can only be instantiated from PeopleCode. These objects can be used anywhere you have PeopleCode—that is, in Component Interface PeopleCode, record field PeopleCode, Application Engine PeopleCode, and so on.

Document Classes Built-in Functions

"CreateDocument" (PeopleTools 8.54: PeopleCode Language Reference)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

"CreateDocumentKey" (PeopleTools 8.54: PeopleCode Language Reference)

Document Class

This section provides an overview of the Document class and discusses:

- Document class methods.
- Document class properties.

The Document class provides the ability to manipulate a PeopleSoft document as a Document object.

Document Class Methods

In this section, the Document class methods are presented in alphabetical order.

GenJsonString

Syntax

GenJsonString()

Description

Use the GenJsonString method to generate a JSON (JavaScript Object Notation) structure from the Document object.

Parameters

None.

Returns

A String value.

Example

```
Local Document &DOC;
Local string &JSONdata;

&string = &DOC.GenJsonString();
&b_ret = &DOC.ParseJsonString(&JSONdata, False);
```

Related Links

ParseJsonString

"Managing JSON-Formatted Documents" (PeopleTools 8.54: Documents Technology)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GenXmlString

Syntax

GenXmlString([*validate*])

Description

Use this method to generate an XML string representing the logical document populated with data.

Note: The Generate button on the Document Tester page uses this method to generate a test XML document.

Parameters

validate	Specifies a Boolean value indicating whether to validate the XML document before it is generated.

Returns

An XML string.

Related Links

"Generating and Viewing Test Documents" (PeopleTools 8.54: Documents Technology)

GetDocumentKey

Syntax

GetDocumentKey()

Description

Use this method to generate the document keys for the document as a DocumentKey object.

Parameters

None.

Returns

A DocumentKey object.

Example

```
Local Document &Doc;

&Doc = CreateDocument("Purchasing", "PurchaseOrder", "v1");
&DocKey = &Doc.GetDocumentKey();
```

Related Links

DocumentKey Class

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GetElement

Syntax

GetElement(*ElementName*)

Description

Use this method to retrieve a document element by name. The object returned will be a Collection, Compound, or Primitive object.

Note: Use the object's ElementType property to determine which object type is returned.

Parameters

ElementName Specifies the name of the document element as a string.

Returns

A Collection object, a Compound object, or a Primitive object.

Example

```
&Doc = CreateDocument(&DocKey);
&DocElem = &Doc.GetElement("BillTo");

Evaluate &DocElem.ElementType

When = %Document_Compound
   ...

When = %Document_Collection
   ...

When = %Document_Primitive
   ...

When-Other
   Error ...

End-Evaluate;
```

Related Links

ElementType
ElementType
ElementType

GetRowset

Syntax

GetRowset()

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use this method to generate a standalone rowset for a relational-formatted document. The structure of the rowset matches the structure of the record mapped to the document. If the document is populated with data when GetRowset is called, then the rowset is populated with that data; otherwise, the rowset is empty.

Parameters

None.

Returns

A Rowset object.

Example

```
Local Document &Doc;
Local Rowset &Doc_RS;

&Doc = CreateDocument(&DocKey);
&Doc_RS = &Doc.GetRowset();
```

Related Links

UpdateFromRowset

Understanding Rowset Class

GetSchema

Syntax

GetSchema()

Description

Use this method to generate the XML schema definition for the document.

Parameters

None.

Returns

A string containing the XML schema definition.

Example

```
Local Document &Doc;
Local DocumentKey &DocKey;

&DocKey = CreateDocumentKey("Purchasing", "PurchaseOrder", "v1");
&Doc = CreateDocument(&DocKey);
&str = &Doc.GetSchema();
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ParseJsonString

Syntax

ParseJsonString(*JSON_data*[, *validate*])

Description

Use the ParseJsonString method to generate a document from the JSON data provided as string.

Parameters

JSON_data	Specifies the JSON data as a string.
validate	Specifies a Boolean value indicating whether to validate the JSON data based on the XML schema.

Returns

A Boolean value: True if a document (or a valid document) was generated, False otherwise.

Example

```
Local Document &DOC;
Local string &JSONdata;

&string = &DOC.GenJsonString();
&b_ret = &DOC.ParseJsonString(&JSONdata, True);
```

Related Links

GenJsonString

"Managing JSON-Formatted Documents" (PeopleTools 8.54: Documents Technology)

ParseXmlFromFile

Syntax

ParseXmlFromFile(*file_name* [, *validate*])

Description

Use this method to generate a document from the XML schema definition provided in a file.

Parameters

file_name	Specifies the name of the file as a string.
validate	Specifies a Boolean value indicating whether to validate the XML document as it is generated.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

A Boolean value: True if a document (or a valid document) was generated, False otherwise.

Related Links

ParseXmlFromURL
ParseXmlString

ParseXmlFromURL

Syntax

```
ParseXmlFromURL(URL [, validate])
```

Description

Use this method to generate a document from the XML schema definition provided at the specified URL.

Parameters

URL	Specifies the URL as a string.
validate	Specifies a Boolean value indicating whether to validate the XML document as it is generated.

Returns

A Boolean value: True if a document (or a valid document) was generated, False otherwise.

Related Links

ParseXmlFromFile
ParseXmlString

ParseXmlString

Syntax

```
ParseXmlString(XML_string [, validate])
```

Description

Use this method to generate a document from the XML schema definition provided as an XML string.

Parameters

XML_string	Specifies the XML as a string.
validate	Specifies a Boolean value indicating whether to validate the XML document as it is generated.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

A Boolean value: True if a document (or a valid document) was generated, False otherwise.

Related Links

ParseXmlFromFile
ParseXmlFromURL

UpdateFromRowset

Syntax

UpdateFromRowset(*&Doc_RS*)

Description

Use this method to update the document data with data from a stand-alone rowset.

Important! Any existing data in the document is erased and replaced by the data from the rowset.

Parameters

&Doc_RS	Specifies the stand-alone rowset as a Rowset object.

Returns

A Boolean value: True if the update was successful, False otherwise.

Related Links

GetRowset
Understanding Rowset Class

ValidateData

Syntax

ValidateData()

Description

Use this method to validate the data in a document.

Parameters

None.

Returns

A Boolean value: True if the document data is valid, False otherwise.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Document Class Properties

In this section, the Document class properties are presented in alphabetical order.

DocumentElement

Description

Use this property to return the root element for this document as a Compound object.

This property is read-only.

Example

```
Local Document &Doc;
Local DocumentKey &DocKey;
Local Compount &Root


/* Instatiate the Document object */
&DocKey = CreateDocumentKey("Purchasing", "PurchaseOrder", "v1");
&Doc = CreateDocument(&DocKey);

&Root = &Doc.DocumentElement;
```

Related Links

Compound Class

DocumentKey Class

This section provides an overview of the DocumentKey class and discusses:

- DocumentKey class methods.
- DocumentKey class properties.

The DocumentKey class provides the ability to pass a document's keys as a single object.

DocumentKey Class Methods

In this section, the DocumentKey class methods are presented in alphabetical order.

SetDocumentKey

Syntax

SetDocumentKey(*Package*, *DocumentName*, *Version*)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use this method to change the document keys for a DocumentKey object.

Parameters

Package Specifies a document package as a string.

DocumentName Specifies the name of the document as a string.

Note: The document name also becomes the root element name for the document.

Version Specifies the document version as a string.

Returns

A Boolean value: True if the document keys were set successfully, False otherwise.

Example

```
Local Document &Doc;
Local DocumentKey &DocKey;

/* Instatiate the Document object */
&DocKey = CreateDocumentKey("Purchasing", "PurchaseOrder", "v1");

   ...

&ret = &DocKey.SetDocumentKey("Purchasing", "PurchaseOrder", "v1.1");
&Doc = CreateDocument(&DocKey);
```

Related Links

"CreateDocumentKey" (PeopleTools 8.54: PeopleCode Language Reference)

DocumentKey Class Properties

In this section, the DocumentKey class properties are presented in alphabetical order.

GetDocumentName

Description

Use this property to return the document name from the document keys as a string.

This property is read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GetVersion

Description

Use this property to return the version from the document keys as a string.

This property is read-only.

PackageName

Description

Use this property to return the package name from the document keys as a string.

This property is read-only.

Primitive Class

This section provides an overview of the Primitive class and discusses:

- Primitive class methods.
- Primitive class properties.

The Primitive class provides the ability to work with a primitive document element.

Primitive Class Methods

In this section, the Primitive class methods are presented in alphabetical order.

GetEnumName

Syntax

GetEnumName(*index*)

Description

Use this method to return the name of the enumerated value.

Parameters

index	Specifies the index of the enumerated value.

Returns

A string representing the enumerated value.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

EnumCount

GetParent

Syntax

```
GetParent()
```

Description

Use this method to return the parent object of the primitive element.

Parameters

None.

Returns

A Collection object or a Compound object.

Related Links

Collection Class
Compound Class

GetPath

Syntax

```
GetPath()
```

Description

Use this method to return the absolute path to the primitive within the document's structure.

For example, for the Name primitive of the ShipTo compound of the PuchaseOrder document, GetPath would return the following absolute path:

```
PurchaseOrder/ShipTo/Name
```

Parameters

None.

Returns

A string representing the absolute path to the primitive.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Primitive Class Properties

In this section, the Primitive class properties are presented in alphabetical order.

ElementType

Description

Use this property to return the type of this document element as an integer constant: %Document_Primitive,

This property is read-only.

EnumCount

Description

Use this property to return the number of enumerated values for this primitive element as an integer.

This property is read-only.

Related Links

GetEnumName

IsChanged

Description

Use this property to return a Boolean value indicating whether the value of this primitive element has been changed.

This property is read-only.

Related Links

OrigValue
Value

IsInitialized

Description

Use this property to return a Boolean value indicating whether this primitive element has an initial value.

This property is read-only.

Related Links

OrigValue

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Value

IsRequired

Description

Use this property return a Boolean value indicating whether this primitive element is required.

This property is read-only.

MaxDefinedDecimalLength

Description

Use this property to return the number of allowed spaces to the right of the decimal point as an integer.

Note: This property is available and valid for a decimal primitive type only.

This property is read-only.

Related Links

MaxDefinedLength
PrimitiveType

MaxDefinedLength

Description

Use this property to return the length of the primitive element as an integer.

This property is read-only.

Related Links

MaxDefinedDecimalLength

Name

Description

Use this property to return the name of this element as a string.

This property is read-only.

OrigValue

Description

Use this property to set or return the original value for this element as a string.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-write.

Related Links

IsChanged
IsInitialized
Value

PrimitiveSubType

Description

Use this property to return the subtype for this primitive element as an integer. Only certain primitive types have defined subtypes.

For the %Document_Integer primitive type, the values are:

Numeric Value	*Constant Value*	*Description*
—	*none*	No subtype (default).
1	%DocumentSubType_NonNegInteger	Non-negative integer

For the %Document_String and %Document_Text primitive types, the values are:

Numeric Value	*Constant Value*	*Description*
—	*none*	No subtype (default).
1	%DocumentSubType_AnyURI	anyURI XML schema data type.
5	%DocumentSubType_gDay	gDay XML schema data type.
6	%DocumentSubType_gMonth	gMonth XML schema data type.
7	%DocumentSubType_gYear	gYear XML schema data type.
8	%DocumentSubType_gYearMonth	gYearMonth XML schema data type.
2	%DocumentSubType_NormString	Normalized string XML schema data type.
4	%DocumentSubType_QName	QName XML schema data type.
3	%DocumentSubType_Token	Token XML schema data type.

This property is read-only.

Related Links

PrimitiveType

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

PrimitiveType

Description

Use this property to return the type for this primitive element as an integer. The values are:

Numeric Value	*Constant Value*	*Description*
11	%Document_Binary	Binary primitive type.
1	%Document_Boolean	Boolean primitive type.
2	%Document_Char	Character primitive type. The Character primitive type allows a single-character string only.
7	%Document_Date	Date primitive type.
9	%Document_DateTime	DateTime primitive type.
6	%Document_Decimal	Decimal primitive type.
4	%Document_Integer	Integer primitive type. The Integer primitive type includes subtypes.
3	%Document_String	String primitive type. The String primitive type requires a length. The String primitive type also includes subtypes.
10	%Document_Text	Text primitive type. The Text primitive type is unbounded and does not require a length. The Text primitive type also includes subtypes.
8	%Document_Time	Time primitive type.

This property is read-only.

Related Links

PrimitiveSubType

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SequenceNumber

Description

Use this property to return the system-assigned sequence number for this element as an integer.

This property is read-only.

Value

Description

Use this property to set or return the value for this primitive element as a string.

This property is read-write.

Related Links

IsChanged
IsInitialized
OrigValue

Compound Class

This section provides an overview of the Compound class and discusses:

- Compound class methods.
- Compound class properties.

The Compound class provides the ability to work with a compound document element.

Compound Class Methods

In this section, the Compound class methods are presented in alphabetical order.

GetParent

Syntax

```
GetParent()
```

Description

Use this method to return the parent object of the compound element.

Parameters

None.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

A Collection object or a Compound object.

Related Links

Collection Class
Compound Class

GetPath

Syntax

GetPath()

Description

Use this method to return the absolute path to the compound element within the document's structure.

For example, for the Items compound of the PuchaseOrder document, GetPath would return the following absolute path:

```
PurchaseOrder/Item_Collection/Items
```

Parameters

None.

Returns

A string representing the absolute path to the compound element.

GetPropertyByIndex

Syntax

GetPropertyByIndex(*index*)

Description

Use this method to return a property of the compound element as an object.

Parameters

None.

index	Specifies the index number of the property as an integer.

Returns

A Collection object, a Compound object, or a Primitive object.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

GetPropertyByName
PropertyCount
Collection Class
Compound Class
Primitive Class

GetPropertyByName

Syntax

GetPropertyByName(*prop_name*)

Description

Use this method to return a property of the compound element as an object.

Parameters

prop_name	Specifies the name of the property as a string.

Returns

A Collection object, a Compound object, or a Primitive object.

Related Links

GetPropertyByIndex
Collection Class
Compound Class
Primitive Class

GetUniqueKey

Syntax

GetUniqueKey()

Description

Use this method to return the key information for this compound—that is, the package name, document name, and document version.

Parameters

None.

Returns

An array of string with three elements: package name, document name, and document version.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Compound Class Properties

In this section, the Compound class properties are presented in alphabetical order.

ElementType

Description

Use this property to return the type of this document element as an integer constant: %Document_Compound.

This property is read-only.

IsChanged

Description

Use this property to return a Boolean value indicating whether this compound element has been changed.

This property is read-only.

IsInitialized

Description

Use this property to return a Boolean value indicating whether this compound element included initial data when the document was loaded from the XML source.

This property is read-only.

IsRequired

Description

Use this property return a Boolean value indicating whether this compound element is required.

This property is read-only.

Name

Description

Use this property to return the name of this element as a string.

This property is read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

PropertyCount

Description

Use this property to return the number of existing properties for this compound element as an integer.

This property is read-only.

Related Links

GetPropertyByIndex

SequenceNumber

Description

Use this property to return the system-assigned sequence number for this element as an integer.

This property is read-only.

Collection Class

This section provides an overview of the Collection class and discusses:

- Collection class methods.
- Collection class properties.

The Collection class provides the ability to work with a collection document element.

Collection Class Methods

In this section, the Collection class methods are presented in alphabetical order.

AppendItem

Syntax

AppendItem(*&Elem*)

Description

Use this method to append an element as the last element of the collection. The item must be instantiated first by using the CreateItem method.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

&Elem Specifies the element to be appended as an object: a Collection object, a Compound object, or a Primitive object.

Returns

A Boolean value: True if the append was completed successfully, False otherwise.

Example

The following example demonstrates how to use Collection and Compound methods to create, populate, and append a compound item within a collection:

```
Local DocumentKey &DOCKEY;
Local Document &DOC;
Local Compound &COM, &Com_Rdr;
Local Collection &Coll_Rdr;
Local Primitive &PRIM;

&DOCKEY = CreateDocumentKey("FlightStatus", "FlightData", "v1");
&DOC = CreateDocument(&DOCKEY);

&COM = &DOC.DocumentElement;

&Coll_Rdr = &COM.GetPropertyByName("RdrCollection");

&Com_Rdr = &Coll_Rdr.CreateItem();

&PRIM = &Com_Rdr.GetPropertyByName("QE_ACNUMBER");
&PRIM.Value = 105;
&PRIM = &Com_Rdr.GetPropertyByName("QE_AZIMUTH");
&PRIM.Value = "40";
&PRIM = &Com_Rdr.GetPropertyByIndex(3);
&PRIM.Value = "4B";

&nRet = &Coll_Rdr.AppendItem(&Com_Rdr);
```

Related Links

CreateItem

CollectionElementType

CreateItem

Syntax

CreateItem()

Description

Use this method to instantiate an empty object for this collection as defined by the CollectionElementType property.

Parameters

None.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

A Collection object, a Compound object, or a Primitive object as defined by the CollectionElementType property.

Related Links

AppendItem
InsertItem
CollectionElementType

DeleteItem

Syntax

DeleteItem(*index*)

Description

Use this method to delete the specified element from the collection.

Parameters

index	Specifies the sequence number of the element to be deleted as an integer.

Returns

A Boolean value: True if the delete was successful, False otherwise.

GetItem

Syntax

GetItem(*index*)

Description

Use this method to return the specified element from the collection.

Parameters

index	Specifies the sequence number of the element to be retrieved as an integer.

Returns

A Collection object, a Compound object, or a Primitive object as defined by the CollectionElementType property.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

CollectionElementType

GetParent

Syntax

```
GetParent()
```

Description

Use this method to return the parent object of the collection element.

Parameters

None.

Returns

A Collection object or a Compound object.

Related Links

Collection Class
Compound Class

GetPath

Syntax

```
GetPath()
```

Description

Use this method to return the absolute path to the collection element within the document's structure.

For example, for the Item_Collection collection of the PuchaseOrder document, GetPath would return the following absolute path:

```
PurchaseOrder/Item_Collection
```

Parameters

None.

Returns

A string representing the absolute path to the collection element.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

InsertItem

Syntax

InsertItem(*&Elem, index*)

Description

Use this method to insert an element at the specified location in the collection. The item must be instantiated first by using the CreateItem method.

Parameters

&Elem	Specifies the element to be inserted as an object: a Collection object, a Compound object, or a Primitive object.
index	Specifies the sequence number for the element to be inserted as an integer.

Returns

A Boolean value : True if the insertion was completed successfully, False otherwise.

Example

For example, for a collection with four items (a, b, c, d), the following call to insert item f would result in a collection with five items (a, f, b, c, d):

```
&ret = &Coll.InsertItem(&f, 2);
```

Related Links

CreateItem
CollectionElementType

Collection Class Properties

In this section, the Collection class properties are presented in alphabetical order.

CollectionElementType

Description

Use this property to return the element type for the collection items as an integer constant. The values are:

Numeric Value	*Constant Value*	*Description*
2	%Document_Collection	A Collection object.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Numeric Value	*Constant Value*	*Description*
1	%Document_Compound	A compound object.
0	%Document_Primitive	A primitive object.

This property is read-only.

Count

Description

Use this property to return the count of items in the collection as an integer.

This property is read-only.

DefinedMaxOccurs

Description

Use this property to return an integer indicating the maximum number of items in the collection. The integer constant %Document_OccursUnbounded indicates that there is no maximum.

This property is read-only.

DefinedMinOccurs

Description

Use this property to return an integer indicating the minimum number of items in the collection.

This property is read-only.

ElementType

Description

Use this property to return the type of this document element as an integer constant: %Document_Collection.

This property is read-only.

IsChanged

Description

Use this property to return a Boolean value indicating whether this collection element has been changed.

This property is read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

IsInitialized

Description

Use this property to return a Boolean value indicating whether this collection included initial data when the document was loaded from the XML source.

This property is read-only.

IsRequired

Description

Use this property return a Boolean value indicating whether this collection element is required.

This property is read-only.

Name

Description

Use this property to return the name of this element as a string.

This property is read-only.

SequenceNumber

Description

Use this property to return the system-assigned sequence number for this element as an integer.

This property is read-only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Chapter 19

Exception Class

Understanding Exception Class

An *exception* can be defined as any unusual event that requires special handling in your PeopleCode program. This could include some kind of hardware failure, such as trying to write to a printer that's been turned off, or a software failure, such as trying to divide by zero. You can also detect your own errors, and use the Throw statement to construct an exception.

Exception handling is the processing you initiate when an exception occurs. You can handle errors in PeopleCode using the Catch statement. The places in your code where you want exceptions handled must be enclosed by the Try and End-Try statements.

The Exception class encapsulates exceptional runtime conditions. It can be used with most PeopleCode programs.

Note: The Exception class does *not* work with any of the PeopleSoft APIs, that is, the classes whose objects are declared as type ApiObject. This includes the Tree classes, the Query classes, Search classes, and so on.

The process of error handling can be broken down as follows:

- An error occurs (either a hardware or software error).
- The error is detected and an exception is thrown (either by the system or by your program).
- Your exception handler provides the response.

How Exceptions Are Thrown

Exceptions get thrown either by the runtime system or by your program.

In general, the kinds of errors that cause the runtime system to throw an exception are errors that terminate your PeopleCode program. For example, dividing by zero, referencing a method or property that doesn't exist, or trying to use a method or property on a null object.

To throw your own exceptions, you can use the Throw statement.

When to Use Exceptions

If the error is something that you can easily check, you shouldn't use exceptions. For example, suppose your page had begin and end date fields. In your SavePreChange PeopleCode program, you would want to check to verify that the end date was after the begin date. This kind of error produces incorrect data. It

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

doesn't terminate your PeopleCode program. This is a simple check, one that you don't need to throw an exception for.

Errors that you might want to use exceptions for are the kinds that you are going to check for often. If you do not want to catch a specific exception, but any general exception, then a simple try-catch block is all that is required. Just write code to catch the general Exception object. For example:

```
try
  &RETCODE = GetAttachment(&IB_ATTACH_REC, &SOURCEFILENAME, &SOURCEFILENAME, "PS_FI⇒
LEDIR");
catch Exception &err
  &RETCODE = GetAttachment(&IB_ATTACH_REC, &SOURCEFILENAME, "/files/" | &SOURCEFILE⇒
NAME, "PS_SERVDIR");
end-try;
```

However, it might make more sense to have a single exception class for that kind of error, so you'd only have to write your error handling code once. For example, suppose that a function you called was supposed to return an array object that you'd then manipulate using the array class methods and properties. When the function fails and doesn't return an array object, you can either check for null, or check for an exception (as this kind of error terminates your PeopleCode program). If you must often check for nulls, perhaps instead of constantly checking, you could rely on the runtime system throwing exceptions for you.

The following provides a pseudo-code example:

```
import MYAPP:Exception;
/* This subpackage contains all the exception classes for your app */

try
   &MyArray = GetArrayData(&Param1, &Param2, &Param3);
   /* Code to manipulate &MyArray here */

catch ExceptionNull &Ex1
   if &Ex1.MessageSetNumber = 2
      and &Ex1.MessageNumber = 236 Then

   /* This is the message set and message number for &MyArray being Null */

   /* do data error handling */

   end-if;
end-try;
```

Considerations Using Exceptions and Transfer Functions

Using functions that transfer the end user to a new component, such as the DoModal, DoModalComponent, or Transfer functions (in some cases) inside a try-catch block do *not* catch PeopleCode exceptions thrown in the new component. Starting a new component starts a brand new PeopleCode evaluation context. Exceptions are caught only when exceptions thrown within the *current* component.

In the following code example, the catch statement only catches exceptions thrown in the code *prior to* using the DoModal function, but not any exceptions that are thrown within the new component.

```
/* Set up transaction */
If %CompIntfcName = "" Then
   try
      &oTrans = &g_ERMS_TransactionCollection.GetTransactionByName(RB_EM_WRK.DESCR)⇒
;
      &sSearchPage = &oTrans.SearchPage;
      &sSearchRecord = &oTrans.SearchRecord;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
      &sSearchTitle = &oTrans.GetSearchPageTitle();
      If Not All(&sSearchPage, &sSearchRecord, &sSearchTitle) Then
         Error (MsgGetText(17834, 8081, "Message Not Found"));
      End-If;
      &c_ERMS_SearchTransaction = &oTrans;

      /* Attempt to transfer to hidden search page with configurable filter */
      &nModalReturn = DoModal(@("Page." | &sSearchPage), &sSearchTitle, - 1, - 1);
   catch Exception &e
      Error (MsgGetText(17834, 8082, "Message Not Found"));
   end-try;
```

Related Links

Exception Handling

Try-Catch Blocks

The statements that immediately follow the **try** statement are called the *protected statements.*. These are the only statements that are “protected” by the catch clauses in the try-catch blocks. The catch clauses in a try-catch block can be executed only if an exception is thrown by the protected statements. In addition, a catch clause is executed only when handling an exception that matches the type given on the catch. Any exceptions thrown by the catch clauses are not caught by their own try-catch block.

The execution of the try-catch block starts by executing the protected statements. If none of these statements—as well as none of the statements called by them—causes an exception to be thrown, the try-catch block is done. The statements in the catch clauses are not executed.

Each catch clause in the try-catch section declares a local variable of class Exception or a subclass of Exception. A catch clause local variable has the same scope and lifetime as a local variable declared at the start of the catch clause.

The following is the general order of exception execution and handling in try-catch blocks:

1. The exception is thrown.
2. The exception is considered by the first enclosing try-catch block.

   Try-catch blocks can be nested.

   This is a dynamic enclosure—that is, tracking back through method and function callers. Any intervening non-try-catch blocks are skipped.
3. Within this try-catch block, the catch clauses are considered in program text order—that is, first the first catch clause is considered, then the next, and so on to the last. At each consideration, the type (class) of the exception being thrown is compared to the type of the local variable declared by the catch clause. If the exception being thrown is the same as the catch type or is a subtype of it (so the exception could be assigned to the catch's local variable), the catch clause matches the exception being thrown.
4. If a matching catch clause is found, that catch clause handles the exception. The exception is considered “caught,” which means that it does not propagate further. Execution proceeds by assigning the thrown object to the catch clause’s local variable and executing the statements in the catch clause. When one of the catch clauses handles the exception (and the statements in the catch clause don’t throw any further exceptions), execution continues normally after the try-catch block.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

If a statement in the catch clause throws another exception, that exception begins to propagate from the point of the throw.

5. If a matching catch clause is not found—that is, if no catch clauses can accept the thrown object—then the thrown object is still uncaught. The thrown object is considered by the next dynamically enclosing try-catch block (return to step 3).

6. If a thrown object is not caught by any catch clause in any dynamically enclosing try-catch blocks, a fatal PeopleCode evaluation error is produced.

Data Type for Exception Class Objects

Exception Class objects are declared as type Exception. For example:

```
Local Exception &Ex1;
```

Scope of Exception Class Objects

Exception objects can be instantiated only from PeopleCode. This object can be used anywhere you have PeopleCode, that is, in an application class, Component Interface PeopleCode, record field PeopleCode, and so on.

Exception Class Built-in Functions

"CreateException" (PeopleTools 8.54: PeopleCode Language Reference)

"throw" (PeopleTools 8.54: PeopleCode Language Reference)

"try" (PeopleTools 8.54: PeopleCode Language Reference)

Exception Class Methods

In this section, we discuss the Exception class methods, in alphabetical order.

GetSubstitution

Syntax

GetSubstitution(*Index*)

Description

When you create a message in the message catalog, you can specify values in the message text, such as %1, %2, and so on, that are replaced with values by the system at runtime. The value that gets put into the message text value is called the *substitution string*. The GetSubstitution method returns the substitution

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

string in the error message specified by *Index*, with 1 being the first substitution string, 2 being the second, and so on.

Parameters

Index Specify the substitution string number that you'd like to return. The first one is 1, the second is 2, and so on. You must specify a valid substitution string number, that is, you can't specify a 4 if there are only three substitution strings.

Returns

The substitution text as a string.

Example

```
If &Ex1.MessageSetNumber = 2 and &Ex1.MessageNumber = 170 Then
   /* Get Sendmail error */
      &String = &Ex1.GetSubstitution(1);
   /* do processing according to type of Sendmail error */
   . . . .
End-if;
```

Related Links

SetSubstitution

"Using Administration Utilities" (PeopleTools 8.54: System and Server Administration)

Output

Syntax

Output()

Description

Use the Output method if you want to display the message associated with the exception to the user (in an online context), or have it logged (if offline). This is analogous to using the MessageBox function to log a message.

Parameters

None.

Returns

If called in an online context, display the message associated with the exception to the user. If called offline, record the exception for later display or analysis.

Example

```
catch Except2 &Ex2
   &Ex2.Output(); /* tell about it */
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

"throw" (PeopleTools 8.54: PeopleCode Language Reference)

SetSubstitution

Syntax

SetSubstitution(*Index*, *String*)

Description

When you create a message in the message catalog, you can specify values in the message text, such as %1, %2, and so on, that are replaced with values by the system at runtime. The value that gets put into the message text value is called the *substitution string*. The SetSubstitution method sets the substitution string in the error message specified by *Index*, with 1 being the first substitution string, 2 being the second, and so on.

Parameters

Index	Specify the substitution string number that you'd like to replace. The first one is 1, the second is 2, and so on. You must specify a valid substitution string number, that is, you can't specify a 4 if there are only three substitution strings.
String	Specify the text of the substitution string.

Returns

None.

Related Links

GetSubstitution

"Using Administration Utilities" (PeopleTools 8.54: System and Server Administration)

ToString

Syntax

ToString([*AddContext*])

Description

The ToString method returns the expanded message text associated with the exception in the current user's current language. The string returned is the message text (in the current user's language) with the substitution string replacing the substitution markers (%1 and so on) in the text. It always returns the context information about where the error occurred at the end of the message. To suppress this, specify *AddContext* as false.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

AddContext	Specify whether to have the context information about where the error occurred added at the end of the message. This parameter takes a Boolean value. The default is true, that is, to add the context information.

Returns

A string.

Related Links

Output

Exception Class Properties

In this section, we discuss the Exception class properties, in alphabetical order.

Context

Description

This property returns a string description of the location of the condition in PeopleCode or other processing. This might contain a stack backtrace at the point of the exceptional condition.

This property is read-only.

Example

This is the “At” part of the error message display. For example, for an exception thrown in Record.Field Event QE_31DIGREC1.QE_31DIGFLD5 FieldChange function EachComp at PeopleCode program counter 671, statement 11 of the source program, the Context would be:

```
At QE_31DIGREC1.QE_31DIGFLD5.FieldChange EachComp   PCPC:671  Statement:11
```

DefaultText

Description

This property sets a string to use as the basic message text for the exception when the message can't be found in the message catalog.

This property is read-write.

MessageNumber

Description

This property is the message number for a message describing the exceptional condition.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-only.

MessageSetNumber

Description

This property is the message set number for a message describing the exceptional condition.

This property is read-only.

MessageSeverity

Description

This property is the message severity as a string for a message describing the exceptional condition. The message severity is set for the message when it's created in the message catalog. The values are:

Numeric Value	*Constant Value*	*Description*
C	%MsgSeverity_Cancel	Message severity is Cancel.
E	%MsgSeverity_Error	Message severity is Error.
M	%MsgSeverity_Message	Message severity is Message.
W	%MsgSeverity_Warning	Message severity is Warning.

This property is read-only.

StackTrace

Description

This property returns a string with the complete stack trace. This includes the whole context, (that is, current location + called from X + called from. . .)

You can process the returned string by breaking it into pieces using the Split function, and using "Called from" as the value to use for separating the string. For example,

```
Local Array of String &Pieces;

/* get exception */

&Pieces = Split(&E.StackTrace, "Called from:");
```

This property is read-only.

Example

The following is an example of a trace stack.

```
In C (0,0) AEMINITEST.MAIN.GBL.default.1900-01-01.Step02.OnExecute  Name:C  PCPC
:136  Statement:2
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
Called from:AEMINITEST.MAIN.GBL.default.1900-01-01.Step02.OnExecute  Name:B  Sta
tement:6
Called from:AEMINITEST.MAIN.GBL.default.1900-01-01.Step02.OnExecute  Name:A  Sta
tement:13
Called from:AEMINITEST.MAIN.GBL.default.1900-01-01.Step02.OnExecute  Statement:1
8
```

SubstitutionCount

Description

This property returns the number of substitution strings in the message text as a number.

The number of substitutions comes from the *subslist* of the CreateException function.

This property is read-only.

Related Links

"CreateException" (PeopleTools 8.54: PeopleCode Language Reference)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Chapter 20

Feed Classes

Understanding the Feed Classes

This chapter documents the following feed classes from the PTFP_FEED application package:

- Feed class
- FeedFactory class
- DataSource subpackage:
  - DataSource class
  - DataSourceParameter class
  - DataSourceParameterValue class
  - DataSourceSetting class
- UTILITY subpackage: Utility class
- XML_FEED subpackage
  - FeedDoc class
  - FeedEntry class

The subpackages and classes not documented in this chapter include:

- DataSource subpackage:
  - FeedDataSource
  - GenericDataSource
  - PSQueryDataSource
  - WorklistDataSource
- EXCEPTION subpackage:
  - DuplicateIDException class
  - FeedException class
  - ImmutableException class

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

    - InitializationException class
    - InvalidMethodException class
    - InvalidTypeException class
    - InvalidValueException class
    - NotAllowedException class
    - NotFoundException class
    - PrivilegeException class
    - PropertyNotSetException class

- Interface subpackage:
    - IBGetFeed class
    - IBGetFeedList class
    - IBGetPrePubFeed class

- UTILITY subpackage
    - Attribute class
    - Authorization class
    - Collection class
    - FeedRequest class
    - HoverMenu class
    - IBOperation class
    - Link class
    - PSComponent class
    - PublishAsRequest class
    - RelatedFeedsRequest class
    - SearchRequest class

- XML_ATOM10 subpackage
    - A10_FeedDoc class
    - A10_FeedEntry class

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- XML_OPML subpackage
  - OPMLDoc class
  - OPMLEntry class
  - OPMLFolder class

Related Links

"Feed Publishing Framework" (PeopleTools 8.54: Feed Publishing Framework)
"Understanding PeopleSoft Integration Broker" (PeopleTools 8.54: Integration Broker)

Importing Feed Classes

The feed classes are application classes, not built-in classes, like Rowset, Field, Record, and so on. Before you can use these classes in your PeopleCode program, you must import them into your program.

An import statement either names a particular application class or imports all the classes in a package.

Using the asterisks after the package name makes all the application classes directly contained in the named package available. Application classes contained in subpackages of the named package are not made available.

Feed Class

This section provides an overview of the Feed class and discusses:

- Feed class constructor.
- Feed class methods.
- Feed class properties.

The Feed class provides the object representation of a feed. The class provides all the basic services for the feed definition and execution of a feed.

Feed Class Constructor

This section presents the constructor for the Feed class. Use the FeedFactory class to create an instance of the Feed class.

Feed

Example

```
import PTFP_FEED:FeedFactory;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
import PTFP_FEED:Feed;

Local PTFP_FEED:FeedFactory &thisFeedFactory = create PTFP_FEED:FeedFactory();
Local PTFP_FEED:Feed &thisFeed = &thisFeedFactory.createFeed("feed_ID");
```

Related Links

createFeed

Constructors

Import Declarations

Feed Class Methods

In this section, the Feed class methods are presented in alphabetical order.

delete

Syntax

delete()

Description

Use this method to delete a feed definition from the database.

Parameters

None.

Returns

A Boolean value: True if the deletion was successful, False otherwise.

Example

```
import PTFP_FEED:FeedFactory;
import PTFP_FEED:Feed;

Local boolean &succeed;
Local PTFP_FEED:FeedFactory &thisFeedFactory = create PTFP_FEED:FeedFactory();
Local PTFP_FEED:Feed &thisFeed = &thisFeedFactory.getFeed("feed_ID", &thisFeedFacto⇒
ry.Utility.OPERATINGMODE_DELETION);

If &thisFeed <> Null And
      &thisFeed.Authorized Then
   &succeed = &thisFeed.delete();
End-If;
```

Related Links

deleteFeed

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

equals

Syntax

equals(*&Object*)

Description

Use this method to evaluate the equivalency of an object with the current feed. Equivalency is established based on the value of two properties: the object's ID and the ObjectType.

Parameters

&Object	Specifies the object to be compared to the current Feed object.

Returns

A Boolean value: True if the items are equivalent, False otherwise.

Example

```
import PTFP_FEED:FeedFactory;
import PTFP_FEED:Feed;

Local PTFP_FEED:FeedFactory &thisFeedFactory = create PTFP_FEED:FeedFactory();
Local PTFP_FEED:Feed &thisFeed1 = &thisFeedFactory.getFeed("feed_ID", &thisFeedFact⇒
ory.Utility.OPERATINGMODE_DEFAULT);
Local PTFP_FEED:Feed &thisFeed2 = &thisFeedFactory.getFeed("feed_ID", &thisFeedFact⇒
ory.Utility.OPERATINGMODE_DEFAULT);

If &thisFeed1.equals(&thisFeed2) Then
   /* Do some process */
End-If;
```

Related Links

ID

ObjectType

execute

Syntax

execute()

Description

Use this method to execute the current feed definition to get a FeedDoc object.

Parameters

None.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

A FeedDoc object.

Example

```
import PTFP_FEED:FeedFactory;
import PTFP_FEED:Feed;
import PTFP_FEED:XML_FEED:FeedDoc;

Local PTFP_FEED:FeedFactory &thisFeedFactory = create PTFP_FEED:FeedFactory();
Local PTFP_FEED:Feed &thisFeed = &thisFeedFactory.getFeed("feed_ID", &thisFeedFacto⇒
ry.Utility.OPERATINGMODE_EXECUTION);
Local PTFP_FEED:XML_FEED:FeedDoc &thisFeedDoc;

If &thisFeed <> Null Then
   &thisFeed.populatePrefData( Null);
   &thisFeedDoc = &thisFeed.execute();
End-If;
```

Related Links

getFeedDoc

FeedDoc Class

getAttribute

Syntax

getAttribute(*attribute_ID*)

Description

Use this method to get a feed attribute by ID.

Parameters

attribute_ID	Specifies the ID of the Attribute object as a string.

Returns

A feed Attribute object.

Example

```
import PTFP_FEED:FeedFactory;
import PTFP_FEED:Feed;
import PTFP_FEED:UTILITY:Attribute;

Local PTFP_FEED:FeedFactory &thisFeedFactory = create PTFP_FEED:FeedFactory();
Local PTFP_FEED:Feed &thisFeed = &thisFeedFactory.getFeed("feed_ID", &thisFeedFacto⇒
ry.Utility.OPERATINGMODE_DEFAULT);
Local PTFP_FEED:UTILITY:Attribute &logo;

If &thisFeed <> Null Then
   &logo = &thisFeed.getAttribute(&thisFeedFactory.Utility.FEEDATTRIBUTE_LOGOURL);
End-If;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

FEEDATTRIBUTE_AUTHOR
FEEDATTRIBUTE_CLOUD
FEEDATTRIBUTE_COMPLETE
FEEDATTRIBUTE_CONTRIBUTOR
FEEDATTRIBUTE_COPYRIGHT
FEEDATTRIBUTE_EXPIRES
FEEDATTRIBUTE_ICONURL
FEEDATTRIBUTE_LOGOURL
FEEDATTRIBUTE_MANAGINGEDITOR
FEEDATTRIBUTE_MAXAGE
FEEDATTRIBUTE_PERSINSTRUCTION
FEEDATTRIBUTE_RATING
FEEDATTRIBUTE_SKIPDAYS
FEEDATTRIBUTE_SKIPHOURS
FEEDATTRIBUTE_TEXTINPUT
FEEDATTRIBUTE_TTL
FEEDATTRIBUTE_WEBMASTER
FEEDATTRIBUTE_XSL

load

Syntax

load()

Description

Use this method to load the feed definition from the database.

Parameters

None.

Returns

A Boolean value: True if the feed definition was loaded successfully, False otherwise.

Example

```
import PTFP_FEED:FeedFactory;
import PTFP_FEED:Feed;

Local PTFP_FEED:FeedFactory &thisFeedFactory = create PTFP_FEED:FeedFactory();
Local PTFP_FEED:Feed &thisFeed = &thisFeedFactory.getFeed("feed_ID", &thisFeedFacto⇒
ry.Utility.OPERATINGMODE_DEFAULT);

If &thisFeed <> Null Then
   &succeed = &thisFeed.load();
End-If;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

loadFromTemplate

Syntax

loadFromTemplate(*template_ID*)

Description

Use this method to load the specified feed template definition from the database.

Parameters

template_ID	Specifies the feed template ID as a string.

Returns

A Boolean value: True if the feed template definition was loaded successfully, False otherwise.

Example

```
import PTFP_FEED:FeedFactory;
import PTFP_FEED:Feed;

Local PTFP_FEED:FeedFactory &thisFeedFactory = create PTFP_FEED:FeedFactory();
Local PTFP_FEED:Feed &thisFeed = &thisFeedFactory.getFeed("feed_ID", &thisFeedFacto⇒
ry.Utility.OPERATINGMODE_DEFAULT);
If &thisFeed <> Null Then
   &succeed = &thisFeed.loadFromTemplate("template_ID");
End-If;
```

PopulateDSParamsWithDefaults

Syntax

PopulateDSParamsWithDefaults()

Description

Use this method to populate the data source parameter collection for this feed with default values only.

Parameters

None.

Returns

None.

Example

```
import PTFP_FEED:FeedFactory;
import PTFP_FEED:Feed;
import PTFP_FEED:EXCEPTION:FeedException;

Local PTFP_FEED:FeedFactory &thisFeedFactory = create PTFP_FEED:FeedFactory();
Local PTFP_FEED:Feed &thisFeed = &thisFeedFactory.getFeed("feed_ID", &thisFeedFacto⇒
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
ry.Utility.OPERATINGMODE_DEFAULT);

/* Reset the Data Source Parameters of the Feed to their defaults. */
try
   &thisFeed.PopulateDSParamsWithDefaults();
catch PTFP_FEED:EXCEPTION:FeedException &ex;
end-try;
```

Related Links

DataSourceParameter Class

populatePrefData

Syntax

populatePrefData(*&FeedRequest*)

Description

Use this method to populate the administrator- or user-specified data source parameter values from the feed definition or from the feed request if parameters are specified there.

Parameters

&FeedRequest	Specifies a FeedRequest object.

Returns

None.

Example

```
import PTFP_FEED:FeedFactory;
import PTFP_FEED:Feed;
import PTFP_FEED:XML_FEED:FeedDoc;

Local PTFP_FEED:FeedFactory &thisFeedFactory = create PTFP_FEED:FeedFactory();
Local PTFP_FEED:Feed &thisFeed = &thisFeedFactory.getFeed("feed_ID", &thisFeedFacto⇒
ry.Utility.OPERATINGMODE_EXECUTION);
Local PTFP_FEED:XML_FEED:FeedDoc &thisFeedDoc;

If &thisFeed <> Null Then
   &thisFeed.populatePrefData( Null);
   &thisFeedDoc = &thisFeed.execute();
End-If;
```

publishToSites

Syntax

publishToSites(*Sites*)

Description

Use this method to publish the feed definition to the specified sites.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

Sites Specifies as an array of string the list of sites to which to publish the feed definition.

Returns

None.

Example

```
import PTFP_FEED:FeedFactory;
import PTFP_FEED:Feed;

Local PTFP_FEED:FeedFactory &thisFeedFactory = create PTFP_FEED:FeedFactory();
Local PTFP_FEED:Feed &thisFeed = &thisFeedFactory.getFeed("feed_ID", &thisFeedFacto⇒
ry.Utility.OPERATINGMODE_DEFAULT);

If &thisFeed <> Null Then
   &thisFeed.publishToSites(CreateArray("EMPLOYEE", "CUSTOMER"));
End-If;
```

resetFeedAttributes

Syntax

resetFeedAttributes()

Description

Use this method to reset the FeedAttributes collection.

Parameters

None.

Returns

An empty FeedAttributes collection.

Example

```
import PTFP_FEED:FeedFactory;
import PTFP_FEED:Feed;
import PTFP_FEED:UTILITY:Collection;

Local PTFP_FEED:FeedFactory &thisFeedFactory = create PTFP_FEED:FeedFactory();
Local PTFP_FEED:Feed &thisFeed = &thisFeedFactory.getFeed("feed_ID", &thisFeedFacto⇒
ry.Utility.OPERATINGMODE_DEFAULT);
Local PTFP_FEED:UTILITY:Collection &coll;

If &thisFeed <> Null Then
   &coll = &thisFeed.resetFeedAttributes();
End-If;
```

Related Links

FeedAttributes

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

resetFeedSecurities

Syntax

resetFeedSecurities()

Description

Use this method to reset the FeedSecurities collection.

Parameters

None.

Returns

An empty FeedSecurities collection.

Example

```
import PTFP_FEED:FeedFactory;
import PTFP_FEED:Feed;
import PTFP_FEED:UTILITY:Collection;

Local PTFP_FEED:FeedFactory &thisFeedFactory = create PTFP_FEED:FeedFactory();
Local PTFP_FEED:Feed &thisFeed = &thisFeedFactory.getFeed("feed_ID", &thisFeedFacto⇒
ry.Utility.OPERATINGMODE_DEFAULT);
Local PTFP_FEED:UTILITY:Collection &coll;

If &thisFeed <> Null Then
   &coll = &thisFeed.resetFeedSecurities();
End-If;
```

Related Links

FeedSecurities

save

Syntax

save()

Description

Use this method to save the feed definition to the database.

Parameters

None.

Returns

A Boolean value: True if the save was successful, False otherwise.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

```
import PTFP_FEED:FeedFactory;
import PTFP_FEED:Feed;
import PTFP_FEED:UTILITY:Attribute;

Local boolean &succeed;
Local PTFP_FEED:FeedFactory &thisFeedFactory = create PTFP_FEED:FeedFactory();
Local PTFP_FEED:Feed &thisFeed = &thisFeedFactory.getFeed("feed_ID", &thisFeedFacto⇒
ry.Utility.OPERATINGMODE_DEFAULT);
Local PTFP_FEED:UTILITY:Attribute &logo;

If &thisFeed <> Null Then
   &logo = &thisFeed.setAttribute(&thisFeedFactory.Utility.FEEDATTRIBUTE_LOGOURL, "⇒
", "http://myserver.com/logo.jpg");
   &succeed = &thisFeed.save();
End-If;
```

saveAs

Syntax

saveAs(*new_ID*, *CopyPrefData*)

Description

Use this method to save the feed definition to the database using the given new ID.

Parameters

new_ID	Specifies the new feed ID as a string.
CopyPrefData	Specifies as a Boolean value whether to copy administrator and user personalization data.

Returns

A new Feed object.

Example

```
import PTFP_FEED:FeedFactory;
import PTFP_FEED:Feed;

Local boolean &succeed;
Local PTFP_FEED:FeedFactory &thisFeedFactory = create PTFP_FEED:FeedFactory();
Local PTFP_FEED:Feed &thisFeed = &thisFeedFactory.getFeed("feed_ID", &thisFeedFacto⇒
ry.Utility.OPERATINGMODE_DEFAULT);
Local PTFP_FEED:Feed &newFeed;

If &thisFeed <> Null Then
   &newFeed = &thisFeed.saveAs("new_feed_id", True);
End-If;
```

saveAsTemplate

Syntax

saveAsTemplate(*new_ID*, *CopyPrefData*)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use this method to save the feed definition to the database as a feed template definition using the given new ID.

Parameters

new_ID	Specifies the new feed template ID as a string.
CopyPrefData	Specifies as a Boolean value whether to copy administrator and user personalization data.

Returns

A Boolean value: True if the save was successful, False otherwise.

Example

```
import PTFP_FEED:FeedFactory;
import PTFP_FEED:Feed;

Local boolean &succeed;
Local PTFP_FEED:FeedFactory &thisFeedFactory = create PTFP_FEED:FeedFactory();
Local PTFP_FEED:Feed &thisFeed = &thisFeedFactory.getFeed("feed_ID",  &thisFeedFact⇒
ory.Utility.OPERATINGMODE_DEFAULT);
Local PTFP_FEED:Feed &newFeed;

If &thisFeed <> Null Then
   &newFeed = &thisFeed.saveAsTemplate("new_feed_template_id", True);
End-If;
```

setAttribute

Syntax

setAttribute(*attribute_ID*, *Value*, *XML*)

Description

Use this method to set the properties of a feed attribute. If the attribute ID does not exist, then a new attribute is created. If both *Value* and *XML* are empty, the attribute is deleted.

Parameters

attribute_ID	Specifies the ID of the attribute as a string.
Value	Specifies the value of the attribute as a string. Use *Value* for translatable values such as the copyright and so on.
XML	Specifies the XML value of the attribute as a string. Use *XML* for nontranslatable values or values longer than 254 characters such as a URL.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

An Attribute object.

Example

```
import PTFP_FEED:FeedFactory;
import PTFP_FEED:Feed;
import PTFP_FEED:UTILITY:Attribute;

Local boolean &succeed;
Local PTFP_FEED:FeedFactory &thisFeedFactory = create PTFP_FEED:FeedFactory();
Local PTFP_FEED:Feed &thisFeed = &thisFeedFactory.getFeed("feed_ID", &thisFeedFacto⇒
ry.Utility.OPERATINGMODE_DEFAULT);
Local PTFP_FEED:UTILITY:Attribute &logo;

If &thisFeed <> Null Then
   &logo = &thisFeed.setAttribute(&thisFeedFactory.Utility.FEEDATTRIBUTE_LOGOURL, "⇒
", "http://myserver.com/logo.jpg");
   &succeed = &thisFeed.save();
End-If;
```

setDataSourceById

Syntax

setDataSourceById(*DataType_ID*)

Description

Use this method to set the data source for the Feed object by data type ID.

Parameters

DataType_ID	Specifies the data type ID to set as the data source.

Returns

A DataSource object if successful, null otherwise.

Example

```
import PTFP_FEED:FeedFactory;
import PTFP_FEED:Feed;
import PTFP_FEED:DataSource:DataSource;

Local PTFP_FEED:FeedFactory &thisFeedFactory = create PTFP_FEED:FeedFactory();
Local PTFP_FEED:Feed &thisFeed = &thisFeedFactory.createFeed("feed_ID");
Local PTFP_FEED:DataSource:DataSource &thisDS;

&thisDS = &thisFeed.setDataSourceByID("FEED");
```

Related Links

DataSource Class

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

unpublishFromSites

Syntax

unpublishFromSites(*Sites*)

Description

Use this method to remove the published feed definition from the specified sites.

Parameters

Sites	Specifies as an array of string the list of sites from which the feed definition is to be removed.

Returns

None.

Example

```
import PTFP_FEED:FeedFactory;
import PTFP_FEED:Feed;

Local PTFP_FEED:FeedFactory &thisFeedFactory = create PTFP_FEED:FeedFactory();
Local PTFP_FEED:Feed &thisFeed = &thisFeedFactory.getFeed("feed_ID", &thisFeedFacto⇒
ry.Utility.OPERATINGMODE_DEFAULT);

If &thisFeed <> Null Then
   &thisFeed.unpublishFromSites(CreateArray("EMPLOYEE", "CUSTOMER"));
End-If;
```

Feed Class Properties

In this section, the Feed class properties are presented in alphabetical order.

Authorized

Description

This property returns a Boolean value indicating whether the current user is authorized to view the feed definition.

This property is read-only.

Example

```
import PTFP_FEED:FeedFactory;
import PTFP_FEED:Feed;

Local boolean &succeed;
Local PTFP_FEED:FeedFactory &thisFeedFactory = create PTFP_FEED:FeedFactory();
Local PTFP_FEED:Feed &thisFeed = &thisFeedFactory.getFeed("feed_ID", &thisFeedFacto⇒
ry.Utility.OPERATINGMODE_DELETION);
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
If &thisFeed <> Null And
      &thisFeed.Authorized Then
   &succeed = &thisFeed.delete();
End-If;
```

CategoryID

Description

Use this property to set or return the category ID for the feed definition as a string.

This property is read-write.

CreateDTTM

Description

This property returns the date and time the feed definition was created as a DateTime value.

This property is read-only.

CreateNode

Description

Use this property to set or return the node on which the feed definition was created, as a string.

This property is read-write.

CreateOprID

Description

This property returns user ID of the user who created the feed definition, as a string.

This property is read-only.

CreatePortal

Description

Use this property to set or return the portal on which the feed definition was created, as a string.

This property is read-write.

DataSource

Description

Use this property to set or return a DataSource object for the feed definition.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-write.

Related Links

DataSource Class

DataTypeID

Description

This property returns the data type ID for the feed definition's data source, as a string.

This property is read-only.

Description

Description

Use this property to set or return the description of the feed definition as a string.

This property is read-write.

FeedAttributes

Description

Use this property to set or return a FeedAttributes collection.

This property is read-write.

FeedAuthorizationOprID

Description

Use this property to set or return the user ID to be used to execute the Feed object, as a string. This value overrides the current user ID depending on the authorization type.

This property is read-write.

FeedAuthorizationOprPWD

Description

Use this property to set or return the password to be used to execute the Feed object, as a string. This value overrides the password for the current user ID depending on the authorization type.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

FeedAuthorizationType

Description

Use this property to set or return the authorization type to be used to execute the Feed object, as a string. This value overrides the current authorization type. The values are:

Value	*Description*
&utility.FEEDAUTHTYPE_DEFAULT	The current authenticated user is used to execute the Feed object.
&utility.FEEDAUTHTYPE_ANONYMOUS	The specified user is used to execute the Feed object for anonymous requests.
&utility.FEEDAUTHTYPE_ALL	The specified user is used to execute the Feed object for all requests.

This property is read-write.

FeedCacheTime

Description

This property is not used currently.

This property is read-write.

FeedCacheType

Description

This property is not used currently.

This property is read-write.

FeedContentUrl

Description

This property returns a string representing the content URL to open the content page of the feed.

This property is read-only.

FeedFactory

Description

Use this property to set or return the FeedFactory object used by this Feed object.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-write.

Related Links

FeedFactory Class

FeedFormat

Description

Use this property to set or return the feed format as a string. The values are:

Value	*Description*
&utility.FEEDFORMAT_ATOM10	Specifies the Atom 1.0 format.

This property is read-write.

FeedSecurities

Description

Use this property to set or return a FeedSecurities collection.

This property is read-write.

FeedSecurityType

Description

Use this property to set or return the security type for the feed as a string. The values are

Value	*Description*
&utility.FEEDSECUTYPE_PUBLIC	Specifies public access to the feed.
&utility.FEEDSECUTYPE_SELECTED	Specifies role or permission list based access to the feed. The role or permission list is stored with the feed definition
&utility.FEEDSECUTYPE_REALTIME	Specifies real-time security in which the DataSource object is used to validate user access when the feed is requested.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

FeedTemplate

Description

Use this property to set or return a Boolean value indicating whether the current feed definition is a feed template definition.

This property is read-write.

Related Links

FeedTemplate

FEEDTEMPLATE_YES

"Feed Templates" (PeopleTools 8.54: Feed Publishing Framework)

FeedUrl

Description

This property returns a string representing the feed URL to open the feed document.

This property is read-only.

HasAdminParams

Description

This property returns a Boolean value indicating whether the feed definition has administrator-specified data source parameters.

This property is read-only.

HasUserParams

Description

This property returns a Boolean value indicating whether the feed definition has user-specified data source parameters.

This property is read-only.

IBOperationName

Description

Use this property to set or return a string representing the Integration Broker service operation name that handles requests for this feed.

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ID

Description

This property returns the ID for the feed definition as a string.

This property is read-only.

LastPubDTTM

Description

This property returns the DateTime value at which the data source's execute method was called to publish feed messages to the Integration Broker queues—that is, the last publication date and time for the feed. The initial value for this property is set to 01-01-1900 12:00AM.

This property is not valid for real-time feeds or for scheduled, generic Integration Broker feeds. It is updated for all other types of scheduled feeds.

This property is read-only.

LastUpdDTTM

Description

This property returns the last update date and time for the feed definition, as a DateTime value.

This property is read-only.

LastUpdOprID

Description

This property returns the user ID of the user to have last updated the feed definition, as string.

This property is read-only.

NameSpaceID

Description

Use this property to set or return the name space ID for the feed definition, as a string. The default name space ID is based on the feed ID as follows: PTFP_*node_name_feed_ID*.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ObjectType

Description

This property returns the object type for the feed definition as a string. For a feed, this is a constant value: Feed.

This property is read-only.

OperatingMode

Description

This property returns the operating mode for the Feed object as a number. The values are:

Numeric Value	*Constant Value*	*Description*
0	&utility.OPERATINGMODE_ DEFAULT	A Feed object in this mode allows all operations such as save, delete, and so on.
10	&utility.OPERATINGMODE_ EXECUTION	A Feed object in this mode is for execution to get the feed document. Other operations such as save and delete are not allowed.
11	&utility.OPERATINGMODE_ EXECUTION_NOENTRY	A Feed object in this mode is for execution to get a feed document with no feed entries. Otherwise, this mode is the same as the OPERATINGMODE_ EXECUTION mode.
100	&utility.OPERATINGMODE_ AUTHORIZATION	A Feed object in this mode is for validating user access to the feed. Most other operations such as execute, save, and delete are not allowed.
1000	&utility.OPERATINGMODE_ DELETION	A Feed object in this mode is to delete the feed definition. Most other operations such as execute and save are not allowed.

This property is read-only.

OwnerID

Description

Use this property to set or return object owner ID as a string. For example, for delivered feed definitions, the owner ID is set to PT, CPA, and so on.

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

PublishedInSites

Description

This property returns the list of sites in which this feed has been published as an array of string.

This property is read-only.

Title

Description

Use this property to set or return the title of the feed definition as a string.

This property is read-write.

Utility

Description

Use this property to set or return the Utility object used by the Feed object.

This property is read-write.

Example

```
import PTFP_FEED:FeedFactory;
import PTFP_FEED:Feed;
import PTFP_FEED:UTILITY:Utility;

Local PTFP_FEED:FeedFactory &thisFeedFactory = create PTFP_FEED:FeedFactory();
Local PTFP_FEED:Feed &thisFeed = &thisFeedFactory.getFeed("feed_ID", &thisFeedFacto⇒
ry.Utility.OPERATINGMODE_DEFAULT);
Local PTFP_FEED:UTILITY:Utility &utility;

If &thisFeed <> Null Then
   &utility = &thisFeed.Utility;
End-If;
```

Related Links

Utility Class

FeedFactory Class

This section provides an overview of the FeedFactory class and discusses:

- FeedFactory class constructor.
- FeedFactory class methods.
- FeedFactory class properties.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The FeedFactory class provides methods for instantiating objects—such as, Feed objects, DataSource objects, Link objects, and Link collections—rather than instantiating these objects directly. Using the methods of the FeedFactory class avoids creating invalid objects. The FeedFactory class also provides methods to search feed definitions and return the search results as a feed HoverMenu object or OPML file

FeedFactory Class Constructor

This section presents the constructor for the FeedFactory class.

FeedFactory

Example

```
import PTFP_FEED:FeedFactory;
```

```
Local PTFP_FEED:FeedFactory &PTFP_FEED_FACTORY = create PTFP_FEED:FeedFactory();
```

Related Links

Constructors
Import Declarations

FeedFactory Class Methods

In this section, the FeedFactory class methods are presented in alphabetical order.

convertFeedLinksToHoverMenu

Syntax

convertFeedLinksToHoverMenu(*&Links*, *Flat*)

Description

Use this method to convert a feed Link collection to a HoverMenu object.

Parameters

&Links	Specifies the feed links as a Link collection.
Flat	A Boolean value that indicates whether to organize links in subfolders based on their categories (False), or into a root folder if there are no categories (True). The default value is False.

Returns

A HoverMenu object if successful.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

```
import PTFP_FEED:FeedFactory;
import PTFP_FEED:UTILITY:SearchRequest;
import PTFP_FEED:UTILITY:Collection;
import PTFP_FEED:UTILITY:HoverMenu;

Local PTFP_FEED:FeedFactory &thisFeedFactory = create PTFP_FEED:FeedFactory();
Local PTFP_FEED:UTILITY:Collection &results;
Local PTFP_FEED:UTILITY:SearchRequest &request;
Local PTFP_FEED:UTILITY:HoverMenu &menu;

&request = create PTFP_FEED:UTILITY:SearchRequest("SearchResults");
&request.PortalName = %Portal;
&results = &thisFeedFactory.getFeedLinks(&request);
&menu = &thisFeedFactory.convertFeedLinksToHoverMenu(&results, True);
```

convertFeedLinksToOPML

Syntax

convertFeedLinksToOPML(*&Links*, *Flat*)

Description

Use this method to convert a feed Link collection to an OPMLDoc object.

Parameters

&Links	Specifies the feed links as a Link collection.
Flat	A Boolean value that indicates whether to organize links in subfolders based on their categories (False), or into a root folder if there are no categories (True). The default value is False.

Returns

An OPMLDoc object if successful.

Example

```
import PTFP_FEED:FeedFactory;
import PTFP_FEED:UTILITY:SearchRequest;
import PTFP_FEED:UTILITY:Collection;
import PTFP_FEED:XML_OPML:OPMLDoc;

Local PTFP_FEED:FeedFactory &thisFeedFactory = create PTFP_FEED:FeedFactory();
Local PTFP_FEED:UTILITY:Collection &results;
Local PTFP_FEED:UTILITY:SearchRequest &request;
Local PTFP_FEED:XML_OPML:OPMLDoc &opmlDoc;

&request = create PTFP_FEED:UTILITY:SearchRequest("SearchResults");
&request.PortalName = %Portal;
&results = &thisFeedFactory.getFeedLinks(&request);
&opmlDoc = &thisFeedFactory.convertFeedLinksToOPML(&results, True);
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

createFeed

Syntax

createFeed(*feed_ID*)

Description

Use this method to create a new Feed object with the given ID.

Parameters

feed_ID	Specifies the feed ID of the new feed definition.

Returns

A Feed object if successful, null otherwise.

Example

```
import PTFP_FEED:FeedFactory;
import PTFP_FEED:Feed;

Local PTFP_FEED:FeedFactory &thisFeedFactory = create PTFP_FEED:FeedFactory();
Local PTFP_FEED:Feed &thisFeed = &thisFeedFactory.createFeed("feed_ID");
```

Related Links

Feed Class

deleteFeed

Syntax

deleteFeed(*feed_ID*)

Description

Use this method to delete the feed definition.

Parameters

feed_ID	Specifies the feed definition to be deleted.

Returns

A Boolean value: True if the feed deletion was successful, False otherwise.

Example

```
import PTFP_FEED:FeedFactory;

Local PTFP_FEED:FeedFactory &thisFeedFactory = create PTFP_FEED:FeedFactory();
Local boolean &succeed = &thisFeedFactory.deleteFeed("feed_ID");
```


Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

delete

genFeedUrl

Syntax

genFeedUrl(*feed_ID*, *OperationName*, *SecurityType*)

Description

Use this method to generate the feed URL based on the feed ID and Integration Broker service operation name. If the service operation name is empty, the default service operation, PTFP_GETFEED, is used.

Parameters

feed_ID	Specifies the ID for the feed definition as a string.
OperationName	Specifies the Integration Broker service operation name as a string. The default service operation is PTFP_GETFEED.
SecurityType	Specifies the security type for the feed as a string.

Returns

A feed URL as a string.

Example

```
import PTFP_FEED:FeedFactory;

Local PTFP_FEED:FeedFactory &thisFeedFactory = create PTFP_FEED:FeedFactory();
Local string &url = &thisFeedFactory.genFeedUrl("feed_ID", "PTFP_GETFEED", &thisFee⇒
dFactory.Utility.FEEDSECUTYPE_PUBLIC);
```

Related Links

FEEDSECUTYPE_PUBLIC
FEEDSECUTYPE_REALTIME
FEEDSECUTYPE_SELECTED

genUniqueFeedId

Syntax

genUniqueFeedId(*seed*)

Description

Use this method to generate an unique feed ID from the specified seed string.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

seed	Specifies the seed as a string.

Returns

A feed ID as a string.

Example

```
import PTFP_FEED:FeedFactory;

Local PTFP_FEED:FeedFactory &thisFeedFactory = create PTFP_FEED:FeedFactory();
Local string &id = &thisFeedFactory.genUniqueFeedId("feed_ID");
```

getAllPagedFeedLinks

Syntax

getAllPagedFeedLinks(*feed_ID*, *fromDTTM*, *allLanguages*)

Description

Use this method to get all the paged feed URLs for the specified scheduled feed definition starting from the specified date and time. If *allLanguages* is set to True, then feed URLs corresponding to all languages are also provided.

This method returns an array of paged feed URLs; each URL represents a specific page (message segment) of the paged feed.

Note: This method is supported for scheduled feeds only.

Related Links

"Paged Feeds" (PeopleTools 8.54: Feed Publishing Framework)

Parameters

feed_ID	Specifies the ID for the scheduled feed definition as a string.
fromDTTM	Specifies the start date and time as a DateTime value.
allLanguages	A Boolean value that indicates whether to provide paged feed URLs for all languages.

Returns

An array of string.

Example

```
import PTFP_FEED:FeedFactory;

Local PTFP_FEED:FeedFactory &feedFactory_inst;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
Local datetime &fromDttm;
Local array of string &feedLinks;

&feedFactory_inst = create PTFP_FEED:FeedFactory();
&fromDttm = DateTimeValue("01/01/1900 00:00:00");
&feedLinks = &feedFactory_inst.getAllPagedFeedLinks("ADMN_USER_PROFILE", &fromDttm,⇒
 True);
```

Related Links

getRelativePageLinkForFeed

getCategory

Syntax

getCategory(*category_ID*, *ActiveOnly*)

Description

Use this method to retrieve all of the category information for a category ID. The information is returned as an array of string with four elements.

Parameters

category_ID	Specifies the category ID as a string.
ActiveOnly	Indicates as a Boolean value whether to retrieve the description only if the category is active.

Returns

An array of string with four elements:

- Category ID
- Short description
- Long description
- Status

Example

```
import PTFP_FEED:FeedFactory;

Local PTFP_FEED:FeedFactory &thisFeedFactory = create PTFP_FEED:FeedFactory();
Local array of string &catagories = &thisFeedFactory.getCategory("category_ID", Tru⇒
e);
```

getDataSource

Syntax

getDataSource(*DataType_ID*)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use this method to create a DataSource object with the given data type ID.

Parameters

None.

DataType_ID Specifies the data type ID for the data source, as a string.

Returns

A DataSource object if successful, null otherwise.

Example

```
import PTFP_FEED:FeedFactory;
import PTFP_FEED:DataSource:DataSource;

Local PTFP_FEED:FeedFactory &thisFeedFactory = create PTFP_FEED:FeedFactory();
Local PTFP_FEED:DataSource:DataSource &thisDS;

&thisDS = &thisFeedFactory.getDataSource("FEED");
```

Related Links

DataSource Class Constructor

getFeed

Syntax

getFeed(*feed_ID, mode*)

Description

Use this method to create a Feed object with the given feed ID.

Parameters

feed_ID Specifies the feed ID as a string.

mode Specifies the operating mode for the feed as a number. See the values below.

The values for the *mode* parameter are:

Numeric Value	*Constant Value*	*Description*
0	&utility.OPERATINGMODE_DEFAULT	A Feed object in this mode allows all operations such as save, delete, and so on.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Numeric Value	*Constant Value*	*Description*
10	&utility.OPERATINGMODE_ EXECUTION	A Feed object in this mode is for execution to get the feed document. Other operations such as save and delete are not allowed.
11	&utility.OPERATINGMODE_ EXECUTION_NOENTRY	A Feed object in this mode is for execution to get a feed document with just an empty feed header (that is, without feed entries). Otherwise, this mode is the same as the OPERATINGMODE_EXECUTION mode.
100	&utility.OPERATINGMODE_ AUTHORIZATION	A Feed object in this mode is for validating user access to the feed. Most other operations such as execute, save, and delete are not allowed.
1000	&utility.OPERATINGMODE_ DELETION	A Feed object in this mode is to delete the feed definition. Most other operations such as execute and save are not allowed.

Returns

A Feed object if successful, null otherwise.

Example

```
import PTFP_FEED:FeedFactory;
import PTFP_FEED:Feed;

Local PTFP_FEED:FeedFactory &thisFeedFactory = create PTFP_FEED:FeedFactory();
Local PTFP_FEED:Feed &thisFeed;

&thisFeed = &thisFeedFactory.getFeed("feed_ID", &thisFeedFactory.Utility.OPERATINGM⇒
ODE_DEFAULT);
```

Related Links

Feed Class Constructor
OPERATINGMODE_AUTHORIZATION
OPERATINGMODE_DEFAULT
OPERATINGMODE_DELETION
OPERATINGMODE_EXECUTION
OPERATINGMODE_EXECUTION_NOENTRY

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

getFeedDoc

Syntax

getFeedDoc(*&feedRequest*)

Description

Use this method to get the feed document of the feed specified by the FeedRequest object.

Parameters

&feedRequest Specifies the feed request as a FeedRequest object.

Returns

A FeedDoc object if successful, null otherwise.

Example

```
import PTFP_FEED:FeedFactory;
import PTFP_FEED:XML_FEED:FeedDoc;
import PTFP_FEED:UTILITY:FeedRequest;

Local PTFP_FEED:FeedFactory &thisFeedFactory = create PTFP_FEED:FeedFactory();
Local PTFP_FEED:UTILITY:FeedRequest &request;
Local PTFP_FEED:XML_FEED:FeedDoc &thisFeedDoc;

&request = create PTFP_FEED:UTILITY:FeedRequest("FeedRequest");
&request.FeedID = "feed_ID";
&thisFeedDoc = &thisFeedFactory.getFeedDoc(&request);
```

Related Links

execute

FeedDoc Class

getFeedLink

Syntax

getFeedLink(*feed_ID*)

Description

Use this method to create a Link object for the specified feed ID.

Parameters

feed_ID Specifies the feed ID as a string.

Returns

A Link object if successful, null otherwise.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

```
import PTFP_FEED:FeedFactory;
import PTFP_FEED:UTILITY:Link;

Local PTFP_FEED:FeedFactory &thisFeedFactory = create PTFP_FEED:FeedFactory();
Local PTFP_FEED:UTILITY:Link &thisFeedLink;

&thisFeedLink = &thisFeedFactory.getFeedLink("feed_ID");
```

getFeedLinks

Syntax

getFeedLinks(*&searchRequest*)

Description

Use this method to search feed definitions based on user permissions and the search criteria specified in the SearchRequest object. The method returns a collection of feed Link objects. The list is sorted by the feed definition's last updated time by default.

Parameters

&searchRequest	Specifies the search criteria as a SearchRequest object.

Returns

A Link collection.

Example

```
import PTFP_FEED:FeedFactory;
import PTFP_FEED:UTILITY:SearchRequest;
import PTFP_FEED:UTILITY:Collection;

Local PTFP_FEED:FeedFactory &thisFeedFactory = create PTFP_FEED:FeedFactory();
Local PTFP_FEED:UTILITY:Collection &results;
Local PTFP_FEED:UTILITY:SearchRequest &request;

&request = create PTFP_FEED:UTILITY:SearchRequest("SearchResults");
&request.PortalName = %Portal;
&results = &thisFeedFactory.getFeedLinks(&request);
```

getFeedTemplates

Syntax

getFeedTemplates(*&searchRequest*)

Description

Use this method to search feed template definitions based on user permissions and the search criteria specified in the SearchRequest object. The method returns a collection of feed template definitions. The list is sorted by the feed template definition's last updated time by default.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

&searchRequest	Specifies the search criteria as a SearchRequest object.

Returns

A collection of Feed objects.

Example

```
import PTFP_FEED:FeedFactory;
import PTFP_FEED:UTILITY:SearchRequest;
import PTFP_FEED:UTILITY:Collection;

Local PTFP_FEED:FeedFactory &thisFeedFactory = create PTFP_FEED:FeedFactory();
Local PTFP_FEED:UTILITY:SearchRequest &request;
Local PTFP_FEED:UTILITY:Collection &feedTemplates;
Local array of string &thisDSS;

&request = create PTFP_FEED:UTILITY:SearchRequest("SearchResults");
&request.DataTypeID = "datatype_id";
&thisDSS = CreateArray("datasourcesetting_name", "datasourcesetting_value");
&request.DataSourceSettings.Push(&thisDSS);
&feedTemplates = &PTFP_FEED_FACTORY.getFeedTemplates(&request);
```

getRelatedFeedsHoverMenu

Syntax

getRelatedFeedsHoverMenu(*&Requests*)

Description

Use this method to create a related feeds HoverMenu object from the specified FeedRequest objects.

Parameters

&Requests	Specifies the related feeds requests as an array of RelatedFeedsRequest objects.

Returns

A HoverMenu object.

Example

```
import PTFP_FEED:FeedFactory;
import PTFP_FEED:UTILITY:RelatedFeedsRequest;
import PTFP_FEED:UTILITY:HoverMenu;
import PTFP_FEED:UTILITY:Collection;

Local PTFP_FEED:FeedFactory &thisFeedFactory = create PTFP_FEED:FeedFactory();
Local PTFP_FEED:UTILITY:Collection &results;
Local PTFP_FEED:UTILITY:RelatedFeedsRequest &request;
Local PTFP_FEED:UTILITY:HoverMenu &menu;

&request = create PTFP_FEED:UTILITY:RelatedFeedsRequest("FEED");
&request.DataTypeID = "FEED";
&menu = &thisFeedFactory.getRelatedFeedsHoverMenu(CreateArray(&request));
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

getRelativePageLinkForFeed

Syntax

getRelativePageLinkForFeed(*feed_ID*, *currentFeedURL*, *linkOption*, *fromDTTM*)

Description

Use this method to get the specified relative paged feed URL (first, previous, next or last) for the current paged feed URL.

This method returns a paged feed URL as a string.

Note: This method is supported for scheduled feeds only.

Related Links

"Paged Feeds" (PeopleTools 8.54: Feed Publishing Framework)

Parameters

feed_ID Specifies the ID for the scheduled feed definition as a string.

currentFeedURL Specifies the paged feed URL for the current page as a string.

linkOption Specifies which page link as a string. See the values below.

fromDTTM Specifies the start date and time as a DateTime value.

Value	*Description*
&utlity.LINKTYPE_FIRST	Indicates the first page of the paged feed.
&utlity.LINKTYPE_PREVIOUS	Indicates the previous page of the paged feed.
&utlity.LINKTYPE_NEXT	Indicates the next page of the paged feed.
&utlity.LINKTYPE_LAST	Indicates the last page of the paged feed.

Returns

A string.

Example

```
import PTFP_FEED:FeedFactory;
import PTFP_FEED:UTILITY:Utility;
import PTFP_FEED:UTILITY:Link;

Local PTFP_FEED:FeedFactory &feedFactory_inst;
Local PTFP_FEED:UTILITY:Utility &utility;
Local PTFP_FEED:UTILITY:Link &link;

Local datetime &fromDttm;
Local string &feedLink, &nextFeedLink, &prevFeedLink, &firstFeedLink, &lastFeedLink⇒
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
;

&feedFactory_inst = create PTFP_FEED:FeedFactory();
&utility = &feedFactory_inst.Utility;
&fromDttm = DateTimeValue("01/01/1900 00:00:00");
&link = &feedFactory_inst.getFeedLink("ADMN_USER_PROFILE");
If All(&link) Then
   &feedLink = &link.Href;

   &nextFeedLink = &feedFactory_inst.getRelativePageLinkForFeed("ADMN_USER_PROFILE"⇒
, &feedLink, &utility.LINKTYPE_NEXT, &fromDttm);
   &prevFeedLink = &feedFactory_inst.getRelativePageLinkForFeed("ADMN_USER_PROFILE"⇒
, &feedLink, &utility.LINKTYPE_PREVIOUS, &fromDttm);
   &firstFeedLink = &feedFactory_inst.getRelativePageLinkForFeed("ADMN_USER_PROFILE⇒
", &feedLink, &utility.LINKTYPE_FIRST, &fromDttm);
   &lastFeedLink = &feedFactory_inst.getRelativePageLinkForFeed("ADMN_USER_PROFILE"⇒
, &feedLink, &utility.LINKTYPE_LAST, &fromDttm);
End-If;
```

Related Links

getAllPagedFeedLinks

FeedFactory Class Properties

In this section, the FeedFactory class properties are presented in alphabetical order.

DataSources

Description

This property returns a collection of all data source definitions (a collection of DataSource objects).

This property is read-only.

Related Links

DataSource Class

Feeds

Description

This property returns a collection of all feed definitions (a collection of Feed objects).

This property is read-only.

Related Links

Feed Class

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Utility

Description

This property returns the Utility object used by this FeedFactory object.

This property is read-only.

Example

```
import PTFP_FEED:FeedFactory;
import PTFP_FEED:UTILITY:Utility;

Local PTFP_FEED:FeedFactory &thisFeedFactory = create PTFP_FEED:FeedFactory();
Local PTFP_FEED:UTILITY:Utility &utility;

&utility = &thisFeedFactory.Utility;
```

Related Links

Utility Class

DataSource Class

This section provides an overview of the DataSource class and discusses:

- DataSource class constructor.
- DataSource class methods.
- DataSource class properties.

The DataSource class is an abstract base class and should not be used directly. All feed data sources should extend this class.

DataSource Class Constructor

This section presents the constructor for the DataSource class. Use the FeedFactory class to create an instance of the DataSource class.

DataSource

Example

```
import PTFP_FEED:FeedFactory;
import PTFP_FEED:DataSource:DataSource;

Local PTFP_FEED:FeedFactory &thisFeedFactory = create PTFP_FEED:FeedFactory();
Local PTFP_FEED:DataSource:DataSource &thisDS = &thisFeedFactory.getDataSource("DS_⇒
ID");
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

getDataSource
Constructors
Import Declarations

DataSource Class Methods

In this section, the DataSource class methods are presented in alphabetical order.

addParameter

Syntax

addParameter(*DSparam_ID*, *Value*)

Description

Use this method to create a DataSourceParameter object with the given ID and value.

Parameters

DSparam_ID	Specifies the ID of the data source parameter as a string.
Value	Specifies the value of the data source parameter as a string.

Returns

A DataSourceParameter object if successful, false otherwise.

Example

```
import PTFP_FEED:FeedFactory;
import PTFP_FEED:DataSource:DataSource;
import PTFP_FEED:DataSource:DataSourceParameter;
import PTFP_FEED:UTILITY:Utility;

Local PTFP_FEED:FeedFactory &thisFeedFactory = create PTFP_FEED:FeedFactory();
Local PTFP_FEED:DataSource:DataSource &thisDS = &thisFeedFactory.getDataSource("DS_⇒
ID");
Local PTFP_FEED:DataSource:DataSourceParameter &thisDSP;
If (&thisDS <> Null) Then
   Local PTFP_FEED:UTILITY:Utility &utility = &thisDS.Utility;

   &thisDSP = &thisDS.addParameter(&utility.DSPARAMETER_MAXROW, "0");
   If (&thisDSP <> Null) Then
      &thisDSP.Name = &thisDSP.ID;
      &thisDSP.Description = "Description";
      &thisDSP.FieldType = &utility.FIELDTYPE_NUMBER;
      &thisDSP.DefaultValue = "10";
      &thisDSP.Value = &thisDSP.DefaultValue;
      &thisDSP.Required = True;
   End-If;
End-If;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

DataSourceParameter Class
DSPARAMETER_MAXROW
DSPARAMETER_SF_MAXMINUTES
DSPARAMETER_SF_PAGING

equals

Syntax

equals(*&Object*)

Description

Use this method to evaluate the equivalency of an object with the current data source. Equivalency is established based on the value of two properties: the object's ID and the ObjectType.

Parameters

&Object	Specifies the object to be compared to the current DataSource object.

Returns

A Boolean value: True if the items are equivalent, False otherwise.

Related Links

ID
ObjectType

getAttributeById

Syntax

getAttributeById(*attribute_ID*)

Description

Use this method to return the default feed attribute value of this data type by ID.

Parameters

attribute_ID	Specifies the ID of the attribute as a string.

Returns

An Attribute object if successful, null otherwise.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

FEEDATTRIBUTE_AUTHOR
FEEDATTRIBUTE_CLOUD
FEEDATTRIBUTE_COMPLETE
FEEDATTRIBUTE_CONTRIBUTOR
FEEDATTRIBUTE_COPYRIGHT
FEEDATTRIBUTE_EXPIRES
FEEDATTRIBUTE_ICONURL
FEEDATTRIBUTE_LOGOURL
FEEDATTRIBUTE_MANAGINGEDITOR
FEEDATTRIBUTE_MAXAGE
FEEDATTRIBUTE_PERSINSTRUCTION
FEEDATTRIBUTE_RATING
FEEDATTRIBUTE_SKIPDAYS
FEEDATTRIBUTE_SKIPHOURS
FEEDATTRIBUTE_TEXTINPUT
FEEDATTRIBUTE_TTL
FEEDATTRIBUTE_WEBMASTER
FEEDATTRIBUTE_XSL

getContentUrl

Syntax

getContentUrl()

Description

Use this method to return the content URL of the feed as a string.

Parameters

None.

Returns

The content URL of the feed as a string.

Example

```
import PTFP_FEED:FeedFactory;
import PTFP_FEED:DataSource:DataSource;

Local PTFP_FEED:FeedFactory &thisFeedFactory = create PTFP_FEED:FeedFactory();
Local PTFP_FEED:DataSource:DataSource &thisDS = &thisFeedFactory.getDataSource("DS_⇒
ID");
Local string &FeedContentUrl = "";
If (&thisDS <> Null) Then
   &FeedContentUrl = &thisDS.getContentUrl();
End-If;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

getDataSecurity

Syntax

getDataSecurity()

Description

Use this method to return the role- and permission list-based data security as a collection of Authorization objects.

Parameters

None.

Returns

Null if the data security type is public, otherwise a collection of Authorization objects. Each Authorization object represents a role or permission list that has access to the data.

getParameterById

Syntax

getParameterById(*DSP_ID*)

Description

Use this method to return the DataSourceParameter object with the given ID.

Parameters

DSP_ID	Specifies the ID of the data source parameter as a string.

Returns

A DataSourceParameter object, null if the data source parameter with the specified ID does not exist.

Example

```
import PTFP_FEED:FeedFactory;
import PTFP_FEED:DataSource:DataSource;
import PTFP_FEED:DataSource:DataSourceParameter;
import PTFP_FEED:UTILITY:Utility;

Local PTFP_FEED:FeedFactory &thisFeedFactory = create PTFP_FEED:FeedFactory();
Local PTFP_FEED:DataSource:DataSource &thisDS = &thisFeedFactory.getDataSource("DS_⇒
ID");
Local PTFP_FEED:DataSource:DataSourceParameter &thisDSP;
If (&thisDS <> Null) Then
   Local PTFP_FEED:UTILITY:Utility &utility = &thisDS.Utility;

   &thisDSP = &thisDS.getParameterById(&utility.DSPARAMETER_MAXROW);
   /* Do some processing with the data source parameter here */
End-If;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

DataSourceParameter Class
DSPARAMETER_MAXROW
DSPARAMETER_SF_MAXMINUTES
DSPARAMETER_SF_PAGING

getParameterDetail

Syntax

getParameterDetail()

Description

Use this method to return the detailed explanation text of all data source parameters for the specific combination of data source settings.

Parameters

None.

Returns

A string with the detailed explanation text in HTML.

getSettingById

Syntax

getSettingById(*DSS_ID*)

Description

Use this method to return a DataSourceSetting object for the given ID.

Parameters

DSS_ID	Specifies the ID of the data source setting as a string.

Returns

A DataSourceSetting object if successful, null if the data source setting with the specified ID does not exist.

Example

```
import PTFP_FEED:FeedFactory;
import PTFP_FEED:DataSource:DataSource;
import PTFP_FEED:DataSource:DataSourceSetting;

Local PTFP_FEED:FeedFactory &thisFeedFactory = create PTFP_FEED:FeedFactory();
Local PTFP_FEED:DataSource:DataSource &thisDS = &thisFeedFactory.getDataSource("DS_⇒
ID");
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
Local PTFP_FEED:DataSource:DataSourceSetting &thisDSS;
If (&thisDS <> Null) Then
   &thisDSS = &thisDS.getSettingById("DSS_ID");
   /* Do some processing with the data source setting here */
End-If;
```

Related Links

DataSourceSetting Class

getSettingDetail

Syntax

getSettingDetail()

Description

Use this method to return the detailed explanation text of all data source settings.

Parameters

None.

Returns

A string with the detailed explanation text in HTML.

isCurrentUserAdmin

Syntax

isCurrentUserAdmin()

Description

Use this method to determine whether the current user has administrator access to the feed data.

Parameters

None.

Returns

A Boolean value: True if the user has administrator access, False otherwise.

Example

```
import PTFP_FEED:FeedFactory;
import PTFP_FEED:DataSource:DataSource;

Local PTFP_FEED:FeedFactory &thisFeedFactory = create PTFP_FEED:FeedFactory();
Local PTFP_FEED:DataSource:DataSource &thisDS = &thisFeedFactory.getDataSource("DS_⇒
ID");
Local boolean &authorized = False;
If (&thisDS <> Null) Then
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
   &authorized = &thisDS.isCurrentUserAdmin();
   /* Do some processing here */
End-If;
```

isCurrentUserAuthorized

Syntax

isCurrentUserAuthorized()

Description

Use this method to determine whether the current user is authorized to view the feed data.

Parameters

None.

Returns

A Boolean value: True if the user is authorized to view the feed data, False otherwise.

Example

```
import PTFP_FEED:FeedFactory;
import PTFP_FEED:DataSource:DataSource;

Local PTFP_FEED:FeedFactory &thisFeedFactory = create PTFP_FEED:FeedFactory();
Local PTFP_FEED:DataSource:DataSource &thisDS = &thisFeedFactory.getDataSource("DS_⇒
ID");
Local boolean &authorized = False;
If (&thisDS <> Null) Then
   &authorized = &thisDS.isCurrentUserAuthorized();
   /* Do some processing here */
End-If;
```

onDelete

Syntax

onDelete()

Description

Use this method to update related data prior to deleting a feed definition. Raise an exception to stop the deleting action.

Parameters

None.

Returns

None.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

onSave

Syntax

onSave()

Description

Use this method to update related data after a feed definition has been saved.

Parameters

None.

resetParameters

Syntax

resetParameters()

Description

Use this method to reset the Parameters collection.

Parameters

None.

Returns

An empty DataSourceParameter collection.

Example

```
import PTFP_FEED:FeedFactory;
import PTFP_FEED:DataSource:DataSource;
import PTFP_FEED:UTILITY:Collection;

Local PTFP_FEED:FeedFactory &thisFeedFactory = create PTFP_FEED:FeedFactory();
Local PTFP_FEED:DataSource:DataSource &thisDS = &thisFeedFactory.getDataSource("DS_⇒
ID");
Local PTFP_FEED:UTILITY:Collection &thisList;

If (&thisDS <> Null) Then
   &thisList = &thisDS.resetParameters();
End-If;
```

Related Links

Parameters

DataSource Class Properties

In this section, the DataSource class properties are presented in alphabetical order.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

AdminPersonalizationPage

Description

Use this property to set or return a PSComponent object representing a data type-specific administrator personalization page for entering administrator-specified data source parameter values.

This property is read-write.

AllowCustomParameters

Description

This property indicates whether to allow user add or delete data source parameters, as a Boolean value. The default false, custom parameters are not allowed.

This property is read-only.

AllowRealTimeFeedSecurity

Description

This property indicates whether to allow real-time feed security, as a Boolean value. The default false, real-time feed security is not allowed.

This property is read-only.

DataSourceType

Description

This property returns the data source type as a string. The default value is a constant: BaseDataSource.

This property is read-only.

DefaultFeedAttributes

Description

Use this property to set or return the default feed attributes of this data type as an Attribute collection.

This property is read-write.

DefaultIBOperationName

Description

This property returns a string representing the name of the default service operation that handles feed requests of this data type.

This property is read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Description

Use this property to set or return the description of the data type as a string.

This property is read-write.

HasParameters

Description

This property whether the data source has parameters, as a Boolean value.

This property is read-only.

HasSettings

Description

This property whether the data source has settings, as a Boolean value.

This property is read-only.

IBOperations

Description

Use this property to set or return an IBOperation collection with the service operation names that could be used to handle feed requests of this feed type.

This property is read-write.

ID

Description

This property returns the ID for the data type as a string.

This property is read-only.

LongDescription

Description

Use this property to set or return the long description of the data type as a string.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ObjectType

Description

This property returns the object type for the data source as a string. For a data source, this is a constant value: DataSource.

This property is read-only.

Parameters

Description

This property returns the DataSoureParameter collection of this data source.

This property is read-only.

ParametersCompleted

Description

This property indicates whether all required data source parameters have values, as a Boolean value.

This property is read-only.

Parent

Description

Use this property to set or return the Feed object that use this DataSource object to collect data.

This property is read-write.

Related Links

Feed Class

PortalSpecificPersonalization

Description

This property returns a Boolean value indicating whether the personalization data is portal specific. The default is False, personalization data is not portal specific.

This property is read-only.

Settings

Description

This property returns the DataSourceSetting collection.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-only.

Related Links

DataSourceSetting Class

SettingsCompleted

Description

This property returns a Boolean value indicating whether all required data source settings are selected.

This property is read-only.

UserPersonalizationPage

Description

Use this property to set or return a PSComponent object representing a data type-specific user personalization page for entering user specified data source parameter values.

This property is read-write.

Utility

Description

Use this property to set or return the Utility object that used by this DataSource object. By default, the parent's (that is, the feed's) Utility object is used.

This property is read-write.

Related Links

Utility Class

DataSourceParameter Class

This section provides an overview of the DataSourceParameter class and discusses:

- DataSourceParameter class constructor.
- DataSourceParameter class methods.
- DataSourceParameter class properties.

The DataSourceParameter class represent a data source parameter that used by the DataSource object to refine the feed data selection.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

DataSourceParameter Class Constructor

This section presents the constructor for the DataSourceParameter class.

DataSourceParameter

Example

```
import PTFP_FEED:DataSource:DataSourceParameter;

Local PTFP_FEED:DataSource:DataSourceParameter &DSP = create PTFP_FEED:DataSource:D⇒
ataSourceParameter("DSP_ID", &Parent_DS);
```

Related Links

Constructors
Import Declarations

DataSourceParameter Class Methods

In this section, the DataSourceParameter class methods are presented in alphabetical order.

addUserValue

Syntax

addUserValue(*DSPValue_ID*, *Value*)

Description

Use this method to add a user value to this data source parameter.

Parameters

DSPValue_ID	Specifies the ID of the user value as a string.
Value	Specifies the value of the user value as a string.

Returns

A DataSourceParameterValue object if successful, false otherwise.

Related Links

DataSourceParameterValue Class Constructor

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

clone

Syntax

```
clone()
```

Description

Use this method to make a copy of this DataSourceParameter object.

Parameters

None.

Returns

A DataSourceParameter object exactly matching the current object.

equals

Syntax

```
equals(&Object)
```

Description

Use this method to evaluate the equivalency of an object with the current data source parameter. Equivalency is established based on the value of two properties: the object's ID and the ObjectType.

Parameters

&Object	Specifies the object to be compared to the current DataSourceParameter object.

Returns

A Boolean value: True if the items are equivalent, False otherwise.

Related Links

ID
ObjectType

resetUserValues

Syntax

```
resetUserValues()
```

Description

Use this method to reset the UserValues collection.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

None.

Returns

An empty UserValues collection if successful, null otherwise.

Related Links

UserValues

setRangeFromFieldTranslates

Syntax

setRangeFromFieldTranslates(*FieldName*)

Description

Use this method to auto-populate the range values based on the translate values for the specified field.

Parameters

FieldName	Specifies the name of the field as a string.

Returns

None.

validateValue

Syntax

validateValue(*Value, CheckPrompt*)

Description

Use this method to validate the value according to its field type, the edit type, and the usage type. Date or date time values are translated to the standard format as a string. Exceptions or errors are raised for invalid values.

Parameters

Value	Specifies the value to be validated as a string.
CheckPrompt	Specifies a Boolean value indicating whether the value should be checked against the valid values list of this data source parameter. The type of check depends on the edit type of this data source parameter, the valid values list could be a user-specified values list, translate values of a field, or values in a

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

prompt table. When *CheckPrompt* is True, check the value; when False, check the data type of the value only.

Returns

A string with the validated value.

DataSourceParameter Class Properties

In this section, the DataSourceParameter class properties are presented in alphabetical order.

AllowChangesToRequired

Description

Use this property to set or return a Boolean value indicating whether it is allowed to change the required flag of this parameter.

This property is read-write.

DefaultValue

Description

Use this property to set or return a string representing the default value for this data source parameter.

This property is read-write.

DefaultValueForDisplay

Description

This property returns a string representing the default value for a data source parameter for display purposes. This is the same as the DefaultValue property except that a date value is in the user-preferred format.

This property is read-only.

Description

Description

Use this property to set or return the description of the data source parameter as a string.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

EditType

Description

Use this property to set or return the table edit type of the data source parameter, as a number. The values are:

Numeric Value	*Constant Value*	*Description*
1	&utility.EDITTYPE_NOTABLEEDIT	This is the default edit type. A valid values list can be specified using the UserValues collection.
2	&utility.EDITTYPE_PROMPTTABLE	This data source parameter takes value from a prompt table. Only a SQL table or SQL view can be used as the prompt table.
3	&utility.EDITTYPE_ TRANSLATETABLE	This data source parameter only takes values specific in the Range array of this data source parameter
4	&utility.EDITTYPE_YESNO	This data source parameter only takes a Yes or No value.

This property is read-write.

EvaluatedValue

Description

This property returns a string representing the evaluated value of the data source parameter. This is the same as the Value property except that a system variable is evaluated to its current runtime value.

This property is read-only.

FieldType

Description

Use this property to set or return the field type as a number. The values are:

Numeric Value	*Constant Value*	*Description*
0	&utility.FIELDTYPE_CHARACTER	Character field
1	&utility.FIELDTYPE_ LONGCHARACTER	Long character field
2	&utility.FIELDTYPE_NUMBER	Number field

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Numeric Value	*Constant Value*	*Description*
3	&utility.FIELDTYPE_ SIGNEDNUMBER	Signed number field
4	&utility.FIELDTYPE_DATE	Date field
5	&utility.FIELDTYPE_TIME	Time field
6	&utility.FIELDTYPE_DATETIME	DateTime field

This property is read-write.

ID

Description

This property returns the ID for this data source parameter as a string.

This property is read-only.

Name

Description

Use this property to set or return the name of this data source parameter as a string.

This property is read-write.

ObjectType

Description

This property returns the object type for the data source parameter as a string. For a DataSourceParameter object, this is a constant value: DataSourceParameter.

This property is read-only.

Parent

Description

Use this property to set or return a pointer to the DataSource object to which this parameter belongs.

This property is read-write.

Related Links

DataSource Class

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

PromptTable

Description

Use this property to set or return the name of the prompt table as a string. Only a SQL table or SQL view should be used as the prompt table.

This property is read-write.

Range

Description

Use this property to set or return the list of valid values as an array of array of string.

This property is read-write.

Required

Description

Use this property to set or return whether this data source parameter is required, as a Boolean value.

This property is read-write.

SkipValidityChecks

Description

Use this property to set or return whether to skip validity checks of the values for this data source parameter, as a Boolean value.

This property is read-write.

UsageType

Description

Use this property to set or return the usage type for this data source parameter as a string. The values are:

Value	*Description*
&utility.USAGETYPE_FIXED	This parameter takes a fixed value.
&utility.USAGETYPE_NOTUSED	This parameter is not used.
&utility.USAGETYPE_SYSVAR	This parameter gets its value from a system variable.
&utility.USAGETYPE_USERSPECIFIED	The value of this parameter can be specified by the user.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Value	*Description*
&utility.USAGETYPE_INTERNAL	This parameter is for internal use.
&utility.USAGETYPE_ADMINSPECIFIED	The value of this parameter can be changed only by users having administrator access to the data.

This property is read-write.

UserValues

Description

This property returns the valid values (that is, the UserValues collection).

This property is read-only.

Utility

Description

Use this property to set or return the Utility object used by the DataSourceParameter object. By default, the parent's (that is, the data source's) Utility object is used.

This property is read-write.

Example

```
import PTFP_FEED:DataSource:DataSourceParameter;
import PTFP_FEED:UTILITY:Utility;

Local PTFP_FEED:DataSource:DataSourceParameter &thisDSP;
Local PTFP_FEED:UTILITY:Utility &utility;

&thisDSP = create PTFP_FEED:DataSource:DataSourceParameter("dsp_ID", Null);
&utility = &thisDSP.Utility;
&thisDSP.Name = &thisDSP.ID;
&thisDSP.Description = MsgGetText(219, 3005, "Message Not Found - Max Entries");
&thisDSP.FieldType = &utility.FIELDTYPE_NUMBER;
&thisDSP.DefaultValue = "10";
&thisDSP.Value = &thisDSP.DefaultValue;
&thisDSP.Required = True;
&thisDSP.EditType = &utility.EDITTYPE_NOTABLEEDIT;
&thisDSP.PromptTable = ""; /* Should only use SQL Table or View */
&thisDSP.Range = Null; /* Only set the range if the edit type is translatable */
&thisDSP.UsageType = &utility.USAGETYPE_FIXED;
&thisDSP.UserValues = Null;
&thisDSP.AllowChangesToRequired = False;
```

Related Links

Utility Class

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Value

Description

Use this property to set or return the value of the data source parameter as a string.

This property is read-write.

ValueForDisplay

Description

This property returns a string representing the value for a data source parameter for display purposes. This is the same as the Value property except that a date value is in the user-preferred format.

This property is read-only.

DataSourceParameterValue Class

This section provides an overview of the DataSourceParameterValue class and discusses:

- DataSourceParameterValue class constructor.
- DataSourceParameterValue class methods.
- DataSourceParameterValue class properties.

The DataSourceParameterValue class represents a valid value for a data source parameter.

DataSourceParameterValue Class Constructor

This section presents the constructor for the DataSourceParameterValue class.

DataSourceParameterValue

Example

```
Local PTFP_FEED:DataSource:DataSourceParameterValue &DSP_Value = create PTFP_FEED:D⇒
ataSource:DataSourceParameterValue("ID", &Parent_DSP);
```

Related Links

Constructors
Import Declarations

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

DataSourceParameterValue Class Methods

In this section, the DataSourceParameterValue class methods are presented in alphabetical order.

clone

Syntax

clone()

Description

Use this method to make a copy of this DataSourceParameterValue object.

Parameters

None.

Returns

A DataSourceParameterValue object exactly matching the current object.

equals

Syntax

equals(*&Object*)

Description

Use this method to evaluate the equivalency of an object with the current data source parameter value. Equivalency is established based on the value of two properties: the object's ID and the ObjectType.

Parameters

&Object	Specifies the object to be compared to the current DataSourceParameterValue object.

Returns

A Boolean value: True if the items are equivalent, False otherwise.

Related Links

ID
ObjectType

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

DataSourceParameterValue Class Properties

In this section, the DataSourceParameterValue class properties are presented in alphabetical order.

Description

Description

Use this property to set or return the description of this data source parameter value as a string.

This property is read-write.

ID

Description

This property returns the ID for this data source parameter value as a string.

This property is read-only.

Name

Description

Use this property to set or return the name of this data source parameter value as a string.

This property is read-write.

ObjectType

Description

This property returns the object type for the data source parameter value as a string. For a DataSourceParameterValue object, this is a constant value: DataSourceParameterValue.

This property is read-only.

OrderNumber

Description

Use this property to set or return the order number for this data source parameter value as a number.

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parent

Description

Use this property to set or return a pointer to the DataSourceParameter object to which this value belongs.

This property is read-write.

Related Links

DataSourceParameter Class

Value

Description

Use this property to set or return the value of the data source parameter value as a string.

This property is read-write.

DataSourceSetting Class

This section provides an overview of the DataSourceSetting class and discusses:

- DataSourceSetting class constructor.
- DataSourceSetting class methods.
- DataSourceSetting class properties.

The DataSourceSetting class represents a data source setting that is used to uniquely define a feed's data source of a given type.

DataSourceSetting Class Constructor

This section presents the constructor for the DataSourceSetting class.

DataSourceSetting

Example

```
import PTFP_FEED:DataSource:DataSourceSetting;

Local PTFP_FEED:DataSource:DataSourceSetting &this_DSS = create PTFP_FEED:DataSourc⇒
e:DataSourceSetting("DSS_ID", &DS);
```

Related Links

Constructors

Import Declarations

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

DataSourceSetting Class Methods

In this section, the DataSourceSetting class methods are presented in alphabetical order.

clone

Syntax

clone()

Description

Use this method to make a copy of this DataSourceSetting object.

Parameters

None.

Returns

A DataSourceSetting object exactly matching the current object.

equals

Syntax

equals(*&Object*)

Description

Use this method to evaluate the equivalency of an object with the current data source setting. Equivalency is established based on the value of two properties: the object's ID and the ObjectType.

Parameters

&Object	Specifies the object to be compared to the current DataSourceSetting object.

Returns

A Boolean value: True if the items are equivalent, False otherwise.

Related Links

ID
ObjectType

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

setRangeFromFieldTranslates

Syntax

setRangeFromFieldTranslates(*FieldName*)

Description

Use this method to auto-populate the range values based on the valid translate values for the field.

Parameters

FieldName	Specifies the name of the field as a string.

Returns

None.

DataSourceSetting Class Properties

In this section, the DataSourceSetting class properties are presented in alphabetical order.

DefaultValue

Description

Use this property to set or return a string representing the default value for a data source setting.

This property is read-write.

DisplayOnly

Description

Use this property to set or return a Boolean value indicating whether the Value property is displayed as display only.

This property is read-write.

EditType

Description

Use this property to set or return the table edit type of the data source setting, as a number. The values are:

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Numeric Value	Constant Value	Description
1	&utility.EDITTYPE_NOTABLEEDIT	This is the default edit type. A valid values list can be specified using the UserValues collection.
2	&utility.EDITTYPE_PROMPTTABLE	This data source parameter takes value from a prompt table. Only a SQL table or SQL view can be used as the prompt table.
3	&utility.EDITTYPE_ TRANSLATETABLE	This data source parameter only takes values specific in the Range array of this data source parameter
4	&utility.EDITTYPE_YESNO	This data source parameter only takes a Yes or No value.

This property is read-write.

Enabled

Description

Use this property to set or return a Boolean value indicating whether the setting is enabled.

This property is read-write.

FieldType

Description

Use this property to set or return the field type as a number. The values are:

Numeric Value	Constant Value	Description
0	&utility.FIELDTYPE_CHARACTER	Character field
1	&utility.FIELDTYPE_ LONGCHARACTER	Long character field
2	&utility.FIELDTYPE_NUMBER	Number field
3	&utility.FIELDTYPE_ SIGNEDNUMBER	Signed number field
4	&utility.FIELDTYPE_DATE	Date field
5	&utility.FIELDTYPE_TIME	Time field

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Numeric Value	*Constant Value*	*Description*
6	&utility.FIELDTYPE_DATETIME	DateTime field

This property is read-write.

ID

Description

This property returns the ID for the data source setting as a string.

This property is read-only.

LongName

Description

Use this property to set or return the label of the name as a string.

This property is read-write.

Name

Description

Use this property to set or return the name of the data source setting as a string.

This property is read-write.

ObjectType

Description

This property returns the object type for the data source setting as a string. For a DataSourceSetting object, this is a constant value: DataSourceSetting.

This property is read-only.

Parent

Description

Use this property to set or return a pointer to the DataSource object to which this setting belongs.

This property is read-write.

Related Links

DataSource Class

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

PromptTable

Description

Use this property to set or return the name of the prompt table as a string. Only a SQL table or SQL view should be used.

This property is read-write.

Range

Description

Use this property to set or return the list of valid values as an array of array of string.

This property is read-write.

RefreshOnChange

Description

Use this property to set or return a Boolean value indicating whether to call the parent DataSource object's processSettingsChange method when the value changes.

This property is read-write.

RelatedFieldValue

Description

Use this property to set or return the related display field value as a string.

This property is read-write.

Required

Description

Use this property to set or return a Boolean value indicating whether this data source setting is required.

This property is read-write.

ShowRelatedField

Description

Use this property to set or return a Boolean value indicating whether to show the related display field.

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Utility

Description

Use this property to set or return the Utility object used by the DataSourceSetting object. By default, the parent's (that is, the data source's) Utility object is used.

This property is read-write.

Example

```
import PTFP_FEED:DataSource:DataSourceSetting;
import PTFP_FEED:UTILITY:Utility;

Local PTFP_FEED:DataSource:DataSourceSetting &thisDSS;
Local PTFP_FEED:UTILITY:Utility &utility;

&thisDSS = create PTFP_FEED:DataSource:DataSourceSetting("dss_ID", Null);
&utility = &thisDSS.Utility;
&thisDSS.Name = &thisDSS.ID;
&thisDSS.LongName = "Data Type Name";
&thisDSS.FieldType = &utility.FIELDTYPE_CHARACTER;
&thisDSS.DefaultValue = "";
&thisDSS.RelatedFieldValue = "";
&thisDSS.EditType = &utility.EDITTYPE_PROMPTTABLE;
&thisDSS.PromptTable = Record.PTFP_DTYPE_PVW; /* Only use SQL Table or View */
&thisDSS.Range = Null; /* Only set the range if the edit type is translatable */
&thisDSS.Required = True;
&thisDSS.Enabled = True;
&thisDSS.Visible = True;
&thisDSS.DisplayOnly = False;
&thisDSS.ShowRelatedField = True;
&thisDSS.RefreshOnChange = True;
```

Related Links

Utility Class

Value

Description

Use this property to set or return the value of the data source setting as a string.

This property is read-write.

Visible

Description

Use this property to set or return a Boolean value indicating whether to show the Value field when it’s enabled.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Utility Class

This section provides an overview of the Utility class and discusses:

- Utility class constructor.
- Utility class methods.
- Utility class properties.

The Utility class provides methods and constants used by other classes of the Feed Publishing Framework

Utility Class Constructor

This section presents the constructor for the Utility class.

Utility

Example

```
import PTFP_FEED:UTILITY:Utility;
```

```
Local PTFP_FEED:UTILITY:Utility &utility = create PTFP_FEED:UTILITY:Utility();
```

Related Links

Constructors
Import Declarations

Utility Class Methods

In this section, the Utility class methods are presented in alphabetical order.

dateStringToUserPref

Syntax

dateStringToUserPref(*DateString*)

Description

Use this method to transform a date string from the "yyyy-MM-dd" format to the user-preferred date format.

Parameters

DateString	Specifies the date string to be transformed.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

A string containing the date in the user-preferred date format.

datetimeToString

Syntax

datetimeToString(*Datetime*)

Description

Use this method to transform a DateTime value to a string in “yyyy-MM-dd HH:mm:ss” format.

Parameters

Datetime	Specifies the DateTime value to be transformed.

Returns

A string in “yyyy-MM-dd HH:mm:ss” format or an empty string if the DateTime value is empty.

dateToString

Syntax

dateToString(*Date*)

Description

Use this method to transform a date value to a string in “yyyy-MM-dd” format.

Parameters

Date	Specifies the date value to be transformed.

Returns

A string in “yyyy-MM-dd” format or an empty string if the date value is empty.

decodeXML

Syntax

decodeXML(*String*)

Description

Use this method to decode the following encoded XML characters in the source string:

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Encoded Character	*Decoded Character*
<	< (less than)
>	> (greater than)
&	& (ampersand)
'	' (apostrophe)
"	" (quotation mark)

Parameters

String Specifies the source XML string with encoded characters to be decoded.

Returns

A string containing the source XML string with encoded characters decoded.

Example

```
For &i = 1 To &elementList.Len
   &valueList = CreateArrayRept("", &pChildTags.Len);
   For &j = 1 To &pChildTags.Len
      &thisValue = %This.getNodeValue(&elementList [&i], &pChildTags [&j]);
      &valueList [&j] = %This.decodeXML(&thisValue);
   End-For;
   &return_value.Push(&valueList);
End-For;
```

Related Links

encodeXML

split2D

encodeXML

Syntax

encodeXML(*String*)

Description

Use this method to encode the following special characters in the source string as encoded XML characters:

Character	*Encoded Character*
< (less than)	<

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Character	*Encoded Character*
> (greater than)	>
& (ampersand)	&
' (apostrophe)	'
" (quotation mark)	"

Parameters

String Specifies the source string with special characters to be encoded.

Returns

A string containing the source string with the special characters encoded.

Example

```
If (&pValues [&i] <> Null) And
      (&pChildTags <> Null) Then
   /* get the children */
   For &j = 1 To &pValues [&i].Len
      If &j > &pChildTags.Len Then
         Break;
      End-If;

      &thisElement = &thisElement | %This.setNodeValue(%This.encodeXML(&pValues [&i⇒
][&j]), &pChildTags [&j]);
   End-For;
End-If;
```

Related Links

decodeXML

join2D

evaluateSysVar

Syntax

evaluateSysVar(*SysVar*)

Description

Use this method to evaluate and return the value of a system variable.

Parameters

SysVar Specifies the system variable to be evaluated as a string.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

A string representation of the evaluated system variable, or the system variable name if it cannot be evaluated.

genNameSpaceID

Syntax

genNameSpaceID(*NameSpace_ID*)

Description

Use this method to replace special characters in the original ID string with "_", so that it only contains "A–Z", "0–9" and "_".

Parameters

NameSpace_ID	Specifies the name space ID to be converted as a string.

Returns

A string containing the generated name space ID using only "A–Z", "0–9" and "_".

getExceptionText

Syntax

getExceptionText(*&Exception*)

Description

Use this method to return the exception error message.

Parameters

&Exception	Specifies the exception as an Exception object.

Returns

The exception error message as a string.

getFeedDoc

Syntax

getFeedDoc(*feed_ID*, *Format*, *&Attributes*)

Description

Use this method to create a FeedDoc object of the given feed format.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

feed_ID Specifies the ID of the feed definition as a string.

Format Specifies the feed format as a string. The values are:

Value	*Description*
&utility.FEEDFORMAT_ATOM10	An Atom 1.0 format feed.

&Attributes Specifies the feed-level properties as an Attribute collection.

Returns

A FeedDoc object of the given feed format with properties filled in from the Attribute collection.

Example

```
import PTFP_FEED:FeedFactory;
import PTFP_FEED:XML_FEED:FeedDoc;
import PTFP_FEED:XML_FEED:FeedEntry;

Local PTFP_FEED:FeedFactory &thisFeedFactory = create PTFP_FEED:FeedFactory();
Local PTFP_FEED:XML_FEED:FeedDoc &this_FeedDoc = &thisFeedFactory.Utility.getFeedDo⇒
c("feed_ID", &thisFeedFactory.Utility.FEEDFORMAT_ATOM10, Null);
Local PTFP_FEED:XML_FEED:FeedEntry &this_Entry = &this_FeedDoc.addEntry("entry_ID")⇒
;
```

Related Links

FeedDoc Class

getFeedMimeType

Syntax

getFeedMimeType(*Format*)

Description

Use this method to return the MIME type of the given feed format.

Parameters

Format Specifies the feed format as a string. The values are:

Value	*Description*
&utility.FEEDFORMAT_ATOM10	An Atom 1.0 format feed.

Returns

A string containing the MIME type as follows:

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Feed Format Constant	*MIME Type Constant*	*MIME Type*
&utility.FEEDFORMAT_ATOM10	MIMETYPE_ATOM	application/atom+xml
undefined	MIMETYPE_XML	application/xml

getFieldTranslates

Syntax

getFieldTranslates(*FieldName*)

Description

Use this method to return the valid translate values of a field.

Parameters

FieldName Specifies the field name for which to retrieve translate values, as a string.

Returns

An array of array of string.

getNodeValue

Syntax

getNodeValue(*String*, *Tag*)

Description

Use this method to extract the value from the first element enclosed by the given tag in the source string.

Parameters

String Specifies the string to check.

Tag Specifies the tag to search for as a string.

Returns

A string containing the value from the first element enclosed by the specified tag.

Example

```
import PTFP_FEED:UTILITY:Utility;

Local PTFP_FEED:UTILITY:Utility &utility = create PTFP_FEED:UTILITY:Utility();
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
&str = "<div><p>value1</p><p>value2</p></div>";

&str1 = &utility.getNodeValue(&str, "p");

/* &str1="value1" */
```

Related Links

setNodeValue
split
split2D

getUserDateFormat

Syntax

getUserDateFormat()

Description

Use this method to construct and return the date format string based on the user's personalization settings.

Parameters

None.

Returns

A string containing the format mask representing the user's preferred date format—for example: MM-dd-yyyy.

getUserDatetimeFormat

Syntax

getUserDatetimeFormat()

Description

Use this method to construct and return the date/time format string based on the user's personalization settings.

Parameters

None.

Returns

A string containing the format mask representing the user's preferred date/time format—for example: MM-dd-yyyy hh:mm a.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

getUserInfo

Syntax

getUserInfo(*user_ID*)

Description

Use this method to return the user name and email address of the given user ID.

Parameters

user_ID	Specifies the user ID for which to retrieve the user information, as a string.

Returns

An array of string containing two elements:

- User name (or the user ID if this is empty).
- Email address (or an empty string if this is empty).

httpStringToDatetime

Syntax

httpStringToDatetime(*string*)

Description

Use this method to convert an HTTP date/time string in the "dow, dd mmm yyyy hh:mm:ss GMT" format to a DateTime value.

Parameters

string	Specifies the HTTP date/time string in the "dow, dd mmm yyyy hh:mm:ss GMT" format.

Returns

A DateTime value.

join

Syntax

join(*&Array, Tag*)

Description

Use this method to concatenate the string array together enclosing each string element in the specified tag.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

&Array	Specifies the array of string to be concatenated together.
Tag	Specifies the tag to enclose each string element.

Returns

A string containing the concatenation of each of the string elements enclosed by the specified tag.

Example

```
import PTFP_FEED:UTILITY:Utility;

Local PTFP_FEED:UTILITY:Utility &utility = create PTFP_FEED:UTILITY:Utility();

&str = &utility.join(CreateArray("value1", "value2"), "p");

/* &str="<p>value1</p><p>value2</p>" */
```

Related Links

setNodeValue
split

join2D

Syntax

join2D(*&Array*, *Tag*, *ChildTags*)

Description

Use this method to concatenate the array of array of string together enclosing each element in the specified tag. Each child element is XML encoded and enclosed in the child tag.

Parameters

&Array	Specifies the array of array of string to be concatenated together.
Tag	Specifies the tag to enclose each string element, as a string.
ChildTags	Specifies the tags to enclose each child element, as an array of string.

Returns

A string containing the concatenation of each of the string elements enclosed by the specified tag. Each child element is XML encoded and enclosed in the child tag.

Example

```
import PTFP_FEED:UTILITY:Utility;

Local PTFP_FEED:UTILITY:Utility &utility = create PTFP_FEED:UTILITY:Utility();
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
&str = &utility.join2D(CreateArray(CreateArray("value1", "value2")), "div", CreateA⇒
rray("b", "i"));

/* &str="<div><b>value1</b><i>value2</i></div>" */
```

Related Links

encodeXML

setNodeValue

split

setMessageHeadersAndMimeType

Syntax

setMessageHeadersAndMimeType(*&Message*, *&feeddoc*, *&FeedRequest*)

Description

Use this method to return the specified Message object with the MIME type set, and populated with the specified FeedDoc. If the feed is an incremental feed, then incremental feed information is set as connector properties for the message.

Parameters

&Message	Specifies the Message object to be returned.
&feeddoc	Specifies the feed document to be returned specified as an XmlDoc object.
&FeedRequest	Specifies the feed as a FeedRequest object.

Returns

A Message object.

Related Links

httpStringToDatetime

Implementing a Real-Time Feed Request Handler

"Incremental Feeds" (PeopleTools 8.54: Feed Publishing Framework)

setNodeValue

Syntax

setNodeValue(*Value*, *Tag*)

Description

Use this method to form an element using the given value and tag name.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

Value	Specifies the string value to enclose in the tags.
Tag	Specifies the tag to enclose the value within, as a string.

Returns

A string element containing the value enclosed within the given tag.

Example

```
import PTFP_FEED:UTILITY:Utility;

Local PTFP_FEED:UTILITY:Utility &utility = create PTFP_FEED:UTILITY:Utility();

&str1 = &utility.setNodeValue("value", "p");

/* &str="<p>value</p>" */
```

Related Links

getNodeValue
join
join2D

showException

Syntax

showException(*Exception*)

Description

Use this method to raise an error when the component variable &PTFP_THROWPAGELETEXCEPTIONS is false, otherwise throw the exception.

Parameters

Exception	Specifies the exception as an Exception.

Returns

None.

showInvalidValueException

Syntax

showInvalidValueException(*Name*, *Value*)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use this method to show an invalid value exception using the showException method.

Parameters

Name	Specifies the name of the property as a string.
Value	Specifies the value that is invalid as a string.

Returns

None

Related Links

showException

split

Syntax

split()

Description

Use this method to extract the elements from the string that are enclosed in the specified tag.

Parameters

String	Specifies the string to check.
Tag	Specifies the tag to search for as a string.

Returns

An array of string containing the string elements enclosed by the specified tag.

Example

```
import PTFP_FEED:UTILITY:Utility;

Local PTFP_FEED:UTILITY:Utility &utility = create PTFP_FEED:UTILITY:Utility();

&str = "<p>value1</p><p>value2</p>";

&arr = &utility.split(&str, "p");

/* &arr[1]="value1", &arr[2]="value2" */
```

Related Links

getNodeValue
join

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

split2D

Syntax

split2D()

Description

Use this method to extract the elements from the string that are enclosed in the specified tag. Child elements enclosed by the child tags are also extracted. All elements are XML decoded.

Parameters

String	Specifies the string to check.
Tag	Specifies the tag that encloses each string element, as a string. This tag can be an empty string.
ChildTags	Specifies the tags that enclose each child element, as an array of string.

Returns

An array of array of string containing the extracted string elements enclosed by the specified tags. Child elements are enclosed by the child tags. All elements are XML decoded.

Example

```
import PTFP_FEED:UTILITY:Utility;

Local PTFP_FEED:UTILITY:Utility &utility = create PTFP_FEED:UTILITY:Utility();

&str = "<div><b>value1</b><i>value2</i></div>";

&arr = &utility.split2D(&str, "div", CreateArray("b", "i"));

/* &arr[1][1]="value1", &arr[1][2]="value2" */
```

Related Links

decodeXML
getNodeValue
join2D
split

stringToDate

Syntax

stringToDate(*DateString*)

Description

Use this method to convert a date string in the "yyyy-MM-dd" format to a date.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

DateString	Specifies the string to be converted to a date.

Returns

A date.

stringToDatetime

Syntax

stringToDatetime(*DatetimeString*)

Description

Use this method to convert a date string in the "yyyy-MM-dd HH:mm:ss" format to a DateTime value.

Parameters

DatetimeString	Specifies the string to be converted to a DateTime value.

Returns

A DateTime value.

validateSysVar

Syntax

validateSysVar(*SysVar*)

Description

Use this method to return the valid, correctly capitalized name of a system variable.

Parameters

SysVar	Specifies the system variable name to be validated as a string.

Returns

A string containing the validated and correctly capitalized system variable name, INVALID SYSVAR if the system variable does not exist.

Example

In the following example, %AuthenticationToken is returned as the validated system variable name.

```
import PTFP_FEED:UTILITY:Utility;

Local PTFP_FEED:UTILITY:Utility &utility = create PTFP_FEED:UTILITY:Utility();
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
&str = &utility.validateSysVar("%AUTHENTICATIONtoken");

/* &str="%AUTHENTICATIONTOKEN" */
```

viewStringAsAttachment

Syntax

viewStringAsAttachment(*String*, *FileName*, *ViewAttachment*)

Description

Use this method to transform the given string into an attachment file that is sent to the browser.

Parameters

String	Specifies the specifies the contents of the attachment file as a string.
FileName	Specifies the attachment file name as a string.
ViewAttachment	Specifies the as a Boolean value whether the attachment is to be viewed directly or detached for download.

Returns

None.

Utility Class Properties

In this section, the Utility class properties are presented in alphabetical order.

Note: Properties in this class with capitalized names—such as, ATTACHMENT_URL, AUTHTYPE_PERM, and so on—are constants.

Some properties of the Utility class—such as, QUERYPARAMETER_FEEDID , QUERYPARAMETER_FEEDFORMAT, and so on—are referred to as query parameters. Typically, these query parameters are used in the implementation of a feed request handler. An example of a feed request handler that uses query parameters is provided at the end of this chapter.

Related Links

Implementing a Real-Time Feed Request Handler

ATTACHMENT_URL

Description

Use this property to return the attachment location from the PTFP_DOCINDB URL definition, as a string.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-only.

AUTHTYPE_PERM

Description

Use this property to return the value that represents the permission list-based authentication type, as a string.

This property is read-only.

AUTHTYPE_ROLE

Description

Use this property to return the value that represents the role-based authentication type, as a string.

This property is read-only.

DSPARAMETER_INCREMENTAL

Description

Use this property to return a string representing the name of the incremental feed data source parameter.

This property is read-only.

Related Links

INCREMENTALOPTION_NO
INCREMENTALOPTION_YES

DSPARAMETER_MAXROW

Description

Use this property to return a string representing the name of the maximum rows data source parameter for scheduled feeds.

Note: Use either the SF_MAXROWOPTION_ALLMSGS property or the SF_MAXROWOPTION_LATESTMSG property to return the *value* of the maximum rows data source parameter for scheduled feeds.

This property is read-only.

Related Links

SF_MAXROWOPTION_ALLMSGS
SF_MAXROWOPTION_LATESTMSG

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

DSPARAMETER_SF_MAXMINUTES

Description

Use this property to return a string representing the name of the maximum minutes data source parameter for scheduled feeds.

Note: Use the SF_MAXMINUTES_ALLMSGS property to return the *value* of the maximum minutes data source parameter for scheduled feeds.

This property is read-only.

Related Links

SF_MAXMINUTES_ALLMSGS

DSPARAMETER_SF_PAGING

Description

Use this property to return a string representing the name of the paging data source parameter for scheduled feeds.

Note: Use either the SF_PAGINGOPTION_NOPAGING property or the SF_PAGINGOPTION_SEGMENTED property to return the *value* of the paging data source parameter for scheduled feeds.

This property is read-only.

Related Links

SF_PAGINGOPTION_NOPAGING
SF_PAGINGOPTION_SEGMENTED

EDITTYPE_NOTABLEEDIT

Description

Use this property to return a number representing the field edit type as no prompt table edit.

This property is read-only.

EDITTYPE_PROMPTTABLE

Description

Use this property to return a number representing the field edit type as prompt table edit.

This property is read-only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

EDITTYPE_TRANSLATETABLE

Description

Use this property to return a number representing the field edit type as translate table edit.

This property is read-only.

EDITTYPE_YESNO

Description

Use this property to return a number representing the field edit type as a Yes/No edit.

This property is read-only.

FEEDATTRIBUTE_AUTHOR

Description

Use this property to return the AUTHOR feed attribute name as a string.

This property is read-only.

Related Links

XMLCHILDELEMENTS_PERSON

FEEDATTRIBUTE_CLOUD

Description

Use this property to return the CLOUD feed attribute name as a string.

This property is read-only.

Related Links

XMLCHILDELEMENTS_CLOUD

FEEDATTRIBUTE_COMPLETE

Description

Use this property to return the COMPLETE feed attribute name as a string.

This property is read-only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

FEEDATTRIBUTE_CONTRIBUTOR

Description

Use this property to return the CONTRIBUTOR feed attribute name as a string.

This property is read-only.

Related Links

XMLCHILDELEMENTS_PERSON

FEEDATTRIBUTE_COPYRIGHT

Description

Use this property to return the COPYRIGHT feed attribute name as a string.

This property is read-only.

FEEDATTRIBUTE_EXPIRES

Description

Use this property to return the EXPIRES feed attribute name as a string.

This property is read-only.

FEEDATTRIBUTE_ICONURL

Description

Use this property to return the ICONURL feed attribute name as a string.

This property is read-only.

FEEDATTRIBUTE_LOGOURL

Description

Use this property to return the LOGOURL feed attribute name as a string.

This property is read-only.

FEEDATTRIBUTE_MANAGINGEDITOR

Description

Use this property to return the MANAGINGEDITOR feed attribute name as a string.

This property is read-only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

FEEDATTRIBUTE_MAXAGE

Description

Use this property to return the MAXAGE feed attribute name as a string.

This property is read-only.

FEEDATTRIBUTE_PERSINSTRUCTION

Description

Use this property to return the PERSINSTRUCTION feed attribute name as a string.

This property is read-only.

FEEDATTRIBUTE_RATING

Description

Use this property to return the RATING feed attribute name as a string.

This property is read-only.

FEEDATTRIBUTE_SKIPDAYS

Description

Use this property to return the SKIPDAYS feed attribute name as a string.

This property is read-only.

FEEDATTRIBUTE_SKIPHOURS

Description

Use this property to return the SKIPHOURS feed attribute name as a string.

This property is read-only.

FEEDATTRIBUTE_TEXTINPUT

Description

Use this property to return the TEXTINPUT feed attribute name as a string.

This property is read-only.

Related Links

XMLCHILDELEMENTS_TEXTINPUT

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

FEEDATTRIBUTE_TTL

Description

Use this property to return the TTL feed attribute name as a string.

This property is read-only.

FEEDATTRIBUTE_WEBMASTER

Description

Use this property to return the WEBMASTER feed attribute name as a string.

This property is read-only.

FEEDATTRIBUTE_XSL

Description

Use this property to return the XSL feed attribute name as a string.

This property is read-only.

FEEDAUTHTYPE_ALL

Description

Use this property to return a string representing the feed authorization type as all.

This property is read-only.

FEEDAUTHTYPE_ANONYMOUS

Description

Use this property to return a string representing the feed authorization type as anonymous.

This property is read-only.

FEEDAUTHTYPE_DEFAULT

Description

Use this property to return a string representing the feed authorization type as default.

This property is read-only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

FEEDCACHETYPE_NONE

Description

Use this property to return a string representing the feed cache type as none.

This property is read-only.

FEEDCACHETYPE_PRIVATE

Description

Use this property to return a string representing the feed cache type as private.

This property is read-only.

FEEDCACHETYPE_PUBLIC

Description

Use this property to return a string representing the feed cache type as public.

This property is read-only.

FEEDCACHETYPE_ROLE

Description

Use this property to return a string representing the feed cache type as role-based.

This property is read-only.

FEEDFORMAT_ATOM10

Description

Use this property to return a string representing the feed format as Atom 1.0.

This property is read-only.

FEEDSECUTYPE_PUBLIC

Description

Use this property to return a string representing the feed security type as public access.

This property is read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

FEEDSECUTYPE_REALTIME

Description

Use this property to return a string representing the feed security type as real-time security.

This property is read-only.

FEEDSECUTYPE_SELECTED

Description

Use this property to return a string representing the feed security type as select security access.

This property is read-only.

FEEDTEMPLATE_NO

Description

Use this property to return a string indicating that the feed definition is not a feed template definition—that is, it is the definition for a feed.

This property is read-only.

Related Links

FeedTemplate

"Feed Templates" (PeopleTools 8.54: Feed Publishing Framework)

FEEDTEMPLATE_YES

Description

Use this property to return a string indicating that the feed definition is a feed template definition.

This property is read-only.

Related Links

FeedTemplate

"Feed Templates" (PeopleTools 8.54: Feed Publishing Framework)

FEEDTYPE_DYNAMIC

Description

Use this property to return a string representing the feed type as real time (formerly known as dynamic).

This property is read-only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

FEEDTYPE_PREPUBLISHED

Description

Use this property to return a string representing the feed type as scheduled (formerly known as prepublished).

This property is read-only.

FIELDTYPE_CHARACTER

Description

Use this property to return a number representing the field type as character.

This property is read-only.

FIELDTYPE_DATE

Description

Use this property to return a number representing the field type as date.

This property is read-only.

FIELDTYPE_DATETIME

Description

Use this property to return a number representing the field type as DateTime.

This property is read-only.

FIELDTYPE_LONGCHARACTER

Description

Use this property to return a number representing the field type as long character.

This property is read-only.

FIELDTYPE_NUMBER

Description

Use this property to return a number representing the field type as number.

This property is read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

FIELDTYPE_SIGNEDNUMBER

Description

Use this property to return a number representing the field type as signed number.

This property is read-only.

FIELDTYPE_TIME

Description

Use this property to return a number representing the field type as time.

This property is read-only.

IBSOTYPE_ASYNC

Description

Use this property to return a string representing the Integration Broker service operation type as asynchronous.

This property is read-only.

IBSOTYPE_SYNC

Description

Use this property to return a string representing the Integration Broker service operation type as synchronous.

This property is read-only.

IBSOTYPE_UNKNOWN

Description

Use this property to return a string representing the Integration Broker service operation type as unknown.

This property is read-only.

ICONURL_FEED_A

Description

Use this property to return the active feed icon URL for PTFP_FEED_ACTIVE, as a string.

This property is read-only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ICONURL_FEED_IA

Description

Use this property to return the inactive feed icon URL for PTFP_FEED_INACTIVE, as a string.

This property is read-only.

INCREMENTALOPTION_NO

Description

Use this property to return an integer indicating that the feed is not an incremental feed.

This property is read-only.

Related Links

DSPARAMETER_INCREMENTAL
"Incremental Feeds" (PeopleTools 8.54: Feed Publishing Framework)

INCREMENTALOPTION_YES

Description

Use this property to return an integer indicating that the feed is an incremental feed.

This property is read-only.

Related Links

DSPARAMETER_INCREMENTAL, "Incremental Feeds" (PeopleTools 8.54: Feed Publishing Framework)

LINKTYPE_FIRST

Description

Use this property for a paged feed to return a string indicating that link type is first.

This property is read-only.

Related Links

getRelativePageLinkForFeed
"Paged Feeds" (PeopleTools 8.54: Feed Publishing Framework)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

LINKTYPE_LAST

Description

Use this property for a paged feed to return a string indicating that link type is last.

This property is read-only.

Related Links

getRelativePageLinkForFeed
"Paged Feeds" (PeopleTools 8.54: Feed Publishing Framework)

LINKTYPE_NEXT

Description

Use this property for a paged feed to return a string indicating that link type is next.

This property is read-only.

Related Links

getRelativePageLinkForFeed
"Paged Feeds" (PeopleTools 8.54: Feed Publishing Framework)

LINKTYPE_PREVIOUS

Description

Use this property for a paged feed to return a string indicating that link type is previous.

This property is read-only.

Related Links

getRelativePageLinkForFeed
"Paged Feeds" (PeopleTools 8.54: Feed Publishing Framework)

MIMETYPE_ATOM

Description

Use this property to return a string containing the MIME type for Atom feed format data.

This property is read-only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

MIMETYPE_OPML

Description

Use this property to return a string containing the MIME type for OPML format data.

This property is read-only.

MIMETYPE_XML

Description

Use this property to return a string containing the MIME type as XML for unknown feed format data.

This property is read-only.

OPERATINGMODE_AUTHORIZATION

Description

Use this property to return a number representing the Feed object operating mode as for user authorization only.

Note: Most other operations such as execute, save, and delete are not allowed.

This property is read-only.

OPERATINGMODE_DEFAULT

Description

Use this property to return a number representing the Feed object operating mode as default.

Note: A Feed object in this mode allows all operations such as save, delete, and so on.

This property is read-only.

OPERATINGMODE_DELETION

Description

Use this property to return a number representing the Feed object operating mode as for feed deletion only.

Note: Most other operations such as execute and save are not allowed.

This property is read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

OPERATINGMODE_EXECUTION

Description

Use this property to return a number representing the Feed object operating mode as for feed execution only.

Note: Other operations such as save and delete are not allowed.

This property is read-only.

OPERATINGMODE_EXECUTION_NOENTRY

Description

Use this property to return a number representing the Feed object operating mode as for feed execution only to return just an empty feed header (that is, without feed entries).

Note: Otherwise, this mode is the same as the OPERATINGMODE_EXECUTION mode.

This property is read-only.

QUERYPARAMETER_CHILDFEEDID

Description

Use this property to return the ChildFeedID query parameter name as a string.

This property is read-only.

QUERYPARAMETER_DATATYPEID

Description

Use this property to return the PTFP_DATA_TYPE query parameter as a string.

This property is read-only.

QUERYPARAMETER_DEFLOCALNODE

Description

Use this property to return the To query parameter as a string.

This property is read-only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

QUERYPARAMETER_DSSCOUNT

Description

Use this property to return the PTFP_DSS_COUNT query parameter as a string.

This property is read-only.

QUERYPARAMETER_DSSNAME

Description

Use this property to return the PTFP_DSS_NAME query parameter as a string.

This property is read-only.

QUERYPARAMETER_DSSVALUE

Description

Use this property to return the PTFP_DSS_VALUE query parameter as a string.

This property is read-only.

QUERYPARAMETER_FEEDFORMAT

Description

Use this property to return the FeedFormat query parameter as a string.

This property is read-only.

QUERYPARAMETER_FEEDID

Description

Use this property to return the FEED_ID query parameter as a string.

This property is read-only.

QUERYPARAMETER_FEEDLIST

Description

Use this property to return the FEEDLIST query parameter as a string.

This property is read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

QUERYPARAMETER_FEEDTYPE

Description

Use this property to return the PTFP_FEED_TYPE query parameter as a string.

This property is read-only.

QUERYPARAMETER_IBTRANSID

Description

Use this property to return the IB_TRANS_ID query parameter as a string.

This property is read-only.

QUERYPARAMETER_IFMODIFIEDSINCE

Description

Use this property to return the If-None-Match query parameter as a string.

This property is read-only.

QUERYPARAMETER_IFNONEMATCH

Description

Use this property to return the PAGE_NUM query parameter as a string.

This property is read-only.

QUERYPARAMETER_KEYWORD

Description

Use this property to return the PTFP_FEED_KEYWORD query parameter as a string.

This property is read-only.

QUERYPARAMETER_LANGUAGE

Description

Use this property to return the languageCd query parameter as a string.

This property is read-only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

QUERYPARAMETER_NODENAME

Description

Use this property to return the NODE_NAME query parameter as a string.

This property is read-only.

QUERYPARAMETER_PAGENUM

Description

Use this property to return this query parameter as a string.

This property is read-only.

QUERYPARAMETER_PORTALNAME

Description

Use this property to return the PORTAL_NAME query parameter as a string.

This property is read-only.

QUERYPARAMETER_PTPPB_SEARCH_MODE

Description

Use this property to return the PTPPB_SEARCH_MODE query parameter as a string.

This property is read-only.

QUERYPARAMETER_PTPPB_SEARCH_TEXT

Description

Use this property to return the SEARCH_TEXT query parameter as a string.

This property is read-only.

RequestInfo

Description

Use this property to set or return a FeedRequest object.

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SF_MAXMINUTES_ALLMSGS

Description

Use this property to return a number representing *all messages* as the value for the maximum minutes data source parameter for scheduled feeds.

Note: Use the DSPARAMETER_SF_MAXMINUTES property to return the *name* of the maximum minutes data source parameter for scheduled feeds.

This property is read-only.

Related Links

DSPARAMETER_SF_MAXMINUTES

SF_MAXROWOPTION_ALLMSGS

Description

Use this property to return a number representing *all messages* as the value for the maximum row data source parameter for scheduled feeds.

Note: Use the DSPARAMETER_MAXROW property to return the *name* of the maximum row data source parameter for scheduled feeds.

This property is read-only.

Related Links

DSPARAMETER_MAXROW

SF_MAXROWOPTION_LATESTMSG

Description

Use this property to return a number representing *latest message* as the value for the maximum row data source parameter for scheduled feeds.

Note: Use the DSPARAMETER_MAXROW property to return the *name* of the maximum row data source parameter for scheduled feeds.

This property is read-only.

Related Links

DSPARAMETER_MAXROW

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SF_PAGINGOPTION_NOPAGING

Description

Use this property to return a number representing *no paging* as the value for the paging data source parameter for scheduled feeds.

Note: Use the DSPARAMETER_SF_PAGING property to return the *name* of the paging data source parameter for scheduled feeds.

This property is read-only.

Related Links

DSPARAMETER_SF_PAGING

SF_PAGINGOPTION_SEGMENTED

Description

Use this property to return a number representing *segmented message* as the value for the paging data source parameter for scheduled feeds.

Note: Use the DSPARAMETER_SF_PAGING property to return the *name* of the paging data source parameter for scheduled feeds.

Important! Using SF_PAGINGOPTION_SEGMENTED returns the oldest page (message segment) as the initial page of the feed. The links to the other pages (next, previous, first, and last) are available in the FeedDoc wherever applicable.
This option is best suited for when the feed output is large and the feed itself is to be consumed by a crawler or a feed reader application that understand these links.

This property is read-only.

Related Links

DSPARAMETER_SF_PAGING

SYSVAR_INVALID

Description

Use this property to return the string that indicates that a system variable is invalid.

This property is read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

USAGETYPE_ADMINSPECIFIED

Description

Use this property to return a string indicating that the data source parameter usage type is administrator specified.

This property is read-only.

USAGETYPE_FIXED

Description

Use this property to return a string indicating that the data source parameter usage type is fixed.

This property is read-only.

USAGETYPE_INTERNAL

Description

Use this property to return a string indicating that the data source parameter usage type is internal.

This property is read-only.

USAGETYPE_NOTUSED

Description

Use this property to return a string indicating that the data source parameter usage type is not used.

This property is read-only.

USAGETYPE_SYSVAR

Description

Use this property to return a string indicating that the data source parameter usage type is system variable.

This property is read-only.

USAGETYPE_USERSPECIFIED

Description

Use this property to return a string indicating that the data source parameter usage type is user specified.

This property is read-only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

XMLCHILDELEMENTS_CLOUD

Description

Use this property to return an array of string containing the list of children XML tags used by the FEEDATTRIBUTE_CLOUD feed attribute.

This property is read-only.

Related Links

FEEDATTRIBUTE_CLOUD

XMLCHILDELEMENTS_PERSON

Description

Use this property to return an array of string containing the list of children XML tags used by the FEEDATTRIBUTE_AUTHOR and FEEDATTRIBUTE_CONTRIBUTOR feed attributes.

This property is read-only.

Related Links

FEEDATTRIBUTE_AUTHOR
FEEDATTRIBUTE_CONTRIBUTOR

XMLCHILDELEMENTS_TEXTINPUT

Description

Use this property to return an array of string containing the list of children XML tags used by the FEEDATTRIBUTE_TEXTINPUT feed attribute.

This property is read-only.

Related Links

FEEDATTRIBUTE_TEXTINPUT

XMLELEMENT_DAY

Description

Use this property to return as a string the representing the day XML element.

This property is read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

XMLELEMENT_DESCRIPTION

Description

Use this property to return as a string the representing the description XML element.

This property is read-only.

XMLELEMENT_DOMAIN

Description

Use this property to return as a string the representing the domain XML element.

This property is read-only.

XMLELEMENT_EMAIL

Description

Use this property to return as a string the representing the email XML element.

This property is read-only.

XMLELEMENT_HOUR

Description

Use this property to return as a string the representing the hour XML element.

This property is read-only.

XMLELEMENT_LINK

Description

Use this property to return as a string the representing the link XML element.

This property is read-only.

XMLELEMENT_NAME

Description

Use this property to return as a string the representing the name XML element.

This property is read-only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

XMLELEMENT_PATH

Description

Use this property to return as a string the representing the path XML element.

This property is read-only.

XMLELEMENT_PORT

Description

Use this property to return as a string the representing the port XML element.

This property is read-only.

XMLELEMENT_PROTOCOL

Description

Use this property to return as a string the representing the protocol XML element.

This property is read-only.

XMLELEMENT_REGISTERPROCEDURE

Description

Use this property to return as a string the representing the register protocol XML element.

This property is read-only.

XMLELEMENT_TITLE

Description

Use this property to return as a string the representing the title XML element.

This property is read-only.

FeedDoc Class

This section provides an overview of the FeedDoc class and discusses:

- FeedDoc class constructor.
- FeedDoc class methods.
- FeedDoc class properties.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The FeedDoc class extends the XmlDoc base class to provide a generic interface class for feed documents. Therefore, for each feed format type, a format-specific feed document class is required to extend the base FeedDoc class. As a base class, the FeedDoc class has abstract methods and properties, which are identified as such in the following sections.

FeedDoc Class Constructor

This section presents the constructor for the FeedDoc class.

FeedDoc

Example

```
import PTFP_FEED:FeedFactory;
import PTFP_FEED:XML_FEED:FeedDoc;

Local PTFP_FEED:FeedFactory &thisFeedFactory = create PTFP_FEED:FeedFactory();
Local PTFP_FEED:XML_FEED:FeedDoc &this_FeedDoc = &thisFeedFactory.getFeedDoc("feed_⇒
ID", &thisFeedFactory.Utility.FEEDFORMAT_ATOM10, Null);
```

Related Links

getFeedDoc

Constructors

Import Declarations

FeedDoc Class Methods

In this section, the FeedDoc class methods are presented in alphabetical order.

addCategory

Syntax

addCategory(*category*)

Description

Use this method to add a category attribute to the feed document as a string.

Note: This is an abstract method.

Parameters

category	Specifies the category as a string.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

A Boolean value: True if the add was successful, False otherwise.

Related Links

deleteCategory
Categories

addEntry

Syntax

addEntry(*entry_ID*)

Description

Use this method to create a FeedEntry object with the given ID.

Note: This is an abstract method.

Parameters

entry_ID	Specifies the ID of the feed entry as a string.

Returns

A FeedEntry object if successful, False otherwise.

Example

```
import PTFP_FEED:FeedFactory;
import PTFP_FEED:XML_FEED:FeedDoc;
import PTFP_FEED:XML_FEED:FeedEntry;

Local boolean &succeeded;
Local array of string &tempArray;

Local PTFP_FEED:FeedFactory &thisFeedFactory = create PTFP_FEED:FeedFactory();
Local PTFP_FEED:XML_FEED:FeedDoc &thisFeedDoc = &thisFeedFactory.Utility.getFeedDoc⇒
("feed_ID", &thisFeedFactory.Utility.FEEDFORMAT_ATOM10, Null);
Local PTFP_FEED:XML_FEED:FeedEntry &thisEntry = &thisFeedDoc.addEntry("entry_ID");

&thisEntry.Title = &contentTitle;
&thisEntry.Description = &contentEntryDesc;
&succeeded = &thisEntry.addCategory(&contentFolderTitle);
&thisEntry.ContentUrl = &contentUrl;
&thisEntry.GUID = &contentUrl;
&thisEntry.Published = &contentCreatedDateTime;
&thisEntry.Updated = &contentLastUpdatedDateTime;
&thisEntry.Author = &thisFeedFactory.Utility.getUserInfo(&contentCreatedByOprid);
&tempArray = &thisFeedFactory.Utility.getUserInfo(&contentLastUpdatedByOprid);
&succeeded = &thisEntry.addContributor(&tempArray [1], &tempArray [2]);
&succeeded = &thisEntry.addEnclosure(&contentAttachmentUrl, "application/octet-stre⇒
am", 123456);
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

deleteEntry
getEntry
resetEntries
Entries
FeedEntry Class

datetimeToString

Syntax

`datetimeToString`(*`Datetime`*)

Description

Use this method to transform a DateTime value to a string in a feed-specific format— for example, in the "yyyy-MM-dd HH:mm:ss.SSS" format.

Note: This is an abstract method.

Parameters

Datetime	Specifies the DateTime value to be transformed.

Returns

A string in a feed-specific format or an empty string if the DateTime value is empty.

deleteCategory

Syntax

`deleteCategory`(*`category`*)

Description

Use this method to delete a category attribute from a FeedDoc object.

Note: This is an abstract method.

Parameters

category	Specifies the category as a string.

Returns

A Boolean value: True if the delete was successful, False otherwise.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

addCategory

deleteEntry

Syntax

deleteEntry(*entry_ID*)

Description

Use this method to delete the feed entry and the FeedEntry object with the given ID.

Parameters

entry_ID	Specifies the ID of the feed entry as a string.

Returns

A Boolean value: True if the delete was successful, False otherwise.

Related Links

addEntry
FeedEntry Class
delete

equals

Syntax

equals(*&Object*)

Description

Use this method to evaluate the equivalency of an object with the current feed document. Equivalency is established based on the value of two properties: the object's ID and the ObjectType.

Parameters

&Object	Specifies the object to be compared to the current FeedDoc object.

Returns

A Boolean value: True if the items are equivalent, False otherwise.

Related Links

ID
ObjectType

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

getEntry

Syntax

getEntry(*entry_ID*)

Description

Use this method to return a FeedEntry object with the given ID.

Parameters

entry_ID	Specifies the ID of the feed entry as a string.

Returns

A FeedEntry object if successful, Null otherwise.

Related Links

addEntry
FeedEntry Class

resetEntries

Syntax

resetEntries()

Description

Use this method to reset the FeedEntry collection.

Parameters

None.

Returns

An empty FeedEntry collection.

Related Links

addEntry
Entries
FeedEntry Class

stringToDatetime

Syntax

stringToDatetime(*DatetimeString*)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use this method to covert a date/time string of a feed-specific format to a DateTime value.

Note: This is an abstract method.

Parameters

DatetimeString Specifies the string to be converted to a DateTime value.

Returns

A DateTime value.

FeedDoc Class Properties

In this section, the FeedDoc class properties are presented in alphabetical order.

AllowMoreEntries

Description

Use this property to return a Boolean value indicating whether more feed entries are allowed for this FeedDoc object.

This property is read-only.

Related Links

addEntry
MaxEntries
FeedEntry Class

ApplicationRelease

Description

Use this property to return the release label from the PSRELEASE table as a string.

This property is read-only.

Categories

Description

Use this property to return the categories for the FeedDoc object as an array of string.

This property is read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Note: This is an abstract property.

Related Links

addCategory

ContentUrl

Description

Use this property to set or return the content URL for the feed document as a string.

This property is read-write.

Note: This is an abstract property.

Example

```
&newDoc.ContentUrl = %This.FeedContentUrl;
```

Related Links

FeedContentUrl

Copyright

Description

Use this property to set or return the copyright for the feed document as a string.

This property is read-write.

Note: This is an abstract property.

Description

Description

Use this property to set or return the description for the feed document as a string.

This property is read-write.

Note: This is an abstract property.

Example

```
&newDoc.Description = %This.Description;
```

Related Links

Description

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Entries

Description

Use this property to return a collection of FeedEntry objects.

This property is read-only.

Related Links

addEntry
deleteEntry
resetEntries

Expires

Description

Use this property to set or return the expiration date and time for the feed document as a DateTime value.

This property is read-write.

Related Links

datetimeToString
stringToDatetime

FeedFormat

Description

Use this property to return the feed format for the feed document as a string.

This property is read-only.

Related Links

FeedFormat

FeedUrl

Description

Use this property to set or return feed URL as a string.

This property is read-write.

Note: This is an abstract property.

Example

```
&newDoc.FeedUrl = &feedUrl;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

FeedUrl

FirstUrl

Description

Use this property to set or return the URL for the first page of a paged feed as a string.

This property is read-write.

Related Links

LastUrl
NextUrl
PreviousUrl
"Paged Feeds" (PeopleTools 8.54: Feed Publishing Framework)

Generator

Description

Use this property to set or return the generator of this feed document as a string.

This property is read-write.

Note: This is an abstract property.

Related Links

ApplicationRelease

ID

Description

Use this property to return the ID for this feed document as a string.

This property is read-only.

Related Links

FeedDoc

LastUrl

Description

Use this property to set or return the URL for the last page of a paged feed as a string.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

FirstUrl
NextUrl
PreviousUrl
"Paged Feeds" (PeopleTools 8.54: Feed Publishing Framework)

Logo

Description

Use this property to set or return the logo for this feed document as a string.

This property is read-write.

Note: This is an abstract property.

MaxAge

Description

Use this property to set or return the maximum age (in milliseconds) of the feed document as a number.

Note: This property can be defined for scheduled feeds only if the DSPARAMETER_SF_MAXMINUTES data source parameter is set. This property is not enforced by all feed readers.

This property is read-write.

Related Links

DSPARAMETER_SF_MAXMINUTES

MaxEntries

Description

Use this property to set or return the maximum number of feed entries for the feed document as a number.

This property is read-write.

The default value is 0, which is an unlimited number of entries.

Related Links

AllowMoreEntries
FeedEntry Class

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

NextUrl

Description

Use this property to set or return the URL for the next page of a paged feed as a string.

This property is read-write.

Related Links

FirstUrl
LastUrl
PreviousUrl
"Paged Feeds" (PeopleTools 8.54: Feed Publishing Framework)

ObjectType

Description

Use this property to return the object type for the feed document as a string. For a feed document, this is a constant value: FeedDoc.

This property is read-only.

PreviousUrl

Description

Use this property to set or return the URL for the previous page of a paged feed as a string.

This property is read-write.

Related Links

FirstUrl
LastUrl
NextUrl
"Paged Feeds" (PeopleTools 8.54: Feed Publishing Framework)

RootElement

Description

Use this property to return the root element for this feed document as an XmlNode object.

This property is read-only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Title

Description

Use this property to set or return the title for the feed document as a string.

This property is read-write.

Note: This is an abstract property.

Example

```
&newDoc.Title = %This.Title;
```

Related Links

Title

Updated

Description

Use this property to set or return the date and time the feed document was last updated as a DateTime value.

This property is read-write.

Note: This is an abstract property.

FeedEntry Class

This section provides an overview of the FeedEntry class and discusses:

- FeedEntry class constructor.
- FeedEntry class methods.
- FeedEntry class properties.

The FeedEntry class provides a generic interface class for feed entries. Therefore, for each feed format type, a format-specific feed entry class is required to extend the base FeedEntry class. As a base class, the FeedEntry class has abstract methods and properties, which are identified as such in the following sections.

FeedEntry Class Constructor

This section presents the constructor for the FeedEntry class.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

FeedEntry

Example

```
import PTFP_FEED:FeedFactory;
import PTFP_FEED:XML_FEED:FeedDoc;
import PTFP_FEED:XML_FEED:FeedEntry;

Local PTFP_FEED:FeedFactory &thisFeedFactory = create PTFP_FEED:FeedFactory();
Local PTFP_FEED:XML_FEED:FeedDoc &this_FeedDoc = &thisFeedFactory.Utility.getFeedDo⇒
c("feed_ID", &thisFeedFactory.Utility.FEEDFORMAT_ATOM10, Null);
Local PTFP_FEED:XML_FEED:FeedEntry &this_Entry = &this_FeedDoc.addEntry("entry_ID")⇒
;
```

Related Links

getFeedDoc
addEntry
Constructors
Import Declarations

FeedEntry Class Methods

In this section, the FeedEntry class methods are presented in alphabetical order.

addCategory

Syntax

addCategory(*category*)

Description

Use this method to add a category attribute to the feed entry as a string.

Note: This is an abstract method.

Parameters

category	Specifies the category as a string.

Returns

A Boolean value: True if the add was successful, False otherwise.

Related Links

deleteCategory
Categories

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

addContributor

Syntax

addContributor(*name*, *email*)

Description

Use this method to add a contributor attribute to the feed entry.

Note: This is an abstract method.

Parameters

name	Specifies the name of the contributor as a string.
email	Specifies the email address for the contributor as a string.

Returns

A Boolean value: True if the add was successful, False otherwise.

Related Links

deleteContributor
Contributors

addEnclosure

Syntax

addEnclosure(*URL*, *type*, *length*)

Description

Use this method to add an enclosure attribute to the feed entry.

Note: This is an abstract method.

Parameters

URL	Specifies the URL for the enclosure as a string.
type	Specifies the type of the enclosure as a string.
length	Specifies the length for the enclosure in bytes as a number.

Returns

A Boolean value: True if the add was successful, False otherwise.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

deleteEnclosure

Enclosures

delete

Syntax

delete()

Description

Use this method to delete the feed entry from a feed document.

Parameters

None.

Returns

None.

Example

```
Local boolean &deleted = False;
Local PTFP_FEED:UTILITY:Collection &Entries = %This.Entries;
Local PTFP_FEED:XML_FEED:FeedEntry &thisEntry = %This.getEntry(&pId);

If (&thisEntry <> Null) And
      ( Not &Entries.Immutable) Then
   &deleted = &Entries.deleteById(&pId);
   If &deleted Then
      &thisEntry.delete();
   End-If;
End-If;
```

Related Links

deleteEntry

deleteCategory

Syntax

deleteCategory(*category*)

Description

Use this method to delete a category attribute from a FeedEntry object.

Note: This is an abstract method.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

category	Specifies the category as a string.

Returns

A Boolean value: True if the delete was successful, False otherwise.

Related Links

addCategory

deleteContributor

Syntax

deleteContributor(*name*)

Description

Use this method to delete a contributor attribute from a feed entry.

Note: This is an abstract method.

Parameters

name	Specifies the name of the contributor as a string.

Returns

A Boolean value: True if the delete was successful, False otherwise.

Related Links

addContributor

deleteEnclosure

Syntax

deleteEnclosure(*URL*)

Description

Use this method to delete an enclosure attribute from a feed entry.

Note: This is an abstract method.

Parameters

URL	Specifies the URL for the enclosure as a string.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

A Boolean value: True if the delete was successful, False otherwise.

Related Links

addEnclosure

equals

Syntax

equals(*&Object*)

Description

Use this method to evaluate the equivalency of an object with the current feed entry. Equivalency is established based on the value of two properties: the object's ID and the ObjectType.

Parameters

&Object	Specifies the object to be compared to the current FeedEntry object.

Returns

A Boolean value: True if the objects are equivalent, False otherwise.

Related Links

ID
ObjectType

FeedEntry Class Properties

In this section, the FeedEntry class properties are presented in alphabetical order.

Author

Description

Use this property to set or return the author attribute for the feed entry as an array of string. The first element of the array is the author's name; the second element is the author's email address.

This property is read-write.

Note: This is an abstract property.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Categories

Description

Use this property to return the categories for the feed entry as an array of string.

This property is read-only.

Note: This is an abstract property.

Related Links

addCategory

Comments

Description

Use this property to set or return a comments attribute for the feed entry as a string.

This property is read-write.

Note: This is an abstract property.

ContentUrl

Description

Use this property to set or return the content URL for the feed entry as a string.

This property is read-write.

Note: This is an abstract property.

Contributors

Description

Use this property to return the contributors for the feed entry as an array of array of string. The first element of the subarray is the contributor's name; the second element is the contributor's email address.

This property is read-only.

Note: This is an abstract property.

Related Links

addContributor

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Copyright

Description

Use this property to set or return the copyright for the feed entry as a string.

This property is read-write.

Note: This is an abstract property.

Description

Description

Use this property to set or return the description for the feed entry as a string.

This property is read-write.

Note: This is an abstract property.

Enclosures

Description

Use this property to return the enclosures for the feed entry as an array of array of string. The first element of the subarray is the enclosure's URL; the second element is the enclosure's type; and the third element is the enclosure's length.

This property is read-only.

Note: This is an abstract property.

Related Links

addEnclosure

Expires

Description

Use this property to set or return the expiration date and time for the feed entry as a DateTime value.

This property is read-write.

Related Links

datetimeToString
stringToDatetime

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

FeedDoc

Description

Use this property to return the FeedDoc object that is the parent of this feed entry.

This property is read-only.

Example

```
&return_value = %This.FeedDoc.stringToDatetime(&expires_inst.NodeValue);
```

Related Links

FeedDoc Class

FullContent

Description

Use this property to set or return the content for the feed entry as a string.

This property is read-write.

Note: This is an abstract property.

GUID

Description

Use this property to set or return a globally unique ID (GUID) for the feed entry.

This property is read-write.

Note: This is an abstract property. For some feed formats, GUID is set to be the content URL for the feed entry.

Related Links

ContentUrl

ID

Description

Use this property to return the ID for this feed entry as a string.

This property is read-only.

Related Links

FeedEntry

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

MaxAge

Description

Use this property to set or return the maximum age (in milliseconds) of the feed entry as a number.

Note: This property can be defined for scheduled feeds only if the DSPARAMETER_SF_MAXMINUTES data source parameter is set. This property is not enforced by all feed readers.

This property is read-write.

Related Links

DSPARAMETER_SF_MAXMINUTES

ObjectType

Description

Use this property to return the object type for the feed entry as a string. For a feed entry, this is a constant value: FeedEntry .

This property is read-only.

Published

Description

Use this property to set or return the initial publication date and time for this feed entry as a DateTime value.

This property is read-write.

Note: This is an abstract property.

Title

Description

Use this property to set or return the title for the feed entry as a string.

This property is read-write.

Note: This is an abstract property.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Updated

Description

Use this property to set or return the date and time the feed entry was last updated as a DateTime value. Initially, the Updated and Published properties have equivalent values. However, if the feed entry is changed, then Updated is different from Published.

This property is read-write.

Note: This is an abstract property.

Additional Feed Examples

This section provides examples of the following: Implementing a real-time feed request handler.

Implementing a Real-Time Feed Request Handler

The following example implements a real-time feed request handler from the IRequestHandler superclass.

Important! For typical real-time feed requests, the default feed service operation (PTFP_GETFEED) and feed request handler should be sufficient. Unless there is specific functionality that is needed for a real-time feed request, use the default feed service operation. For scheduled feeds, the default service operation and hence the request handler cannot be modified.

```
import PS_PT:Integration:IRequestHandler;
import PTFP_FEED:UTILITY:Utility;
import PTFP_FEED:XML_FEED:FeedDoc;
import PTFP_FEED:UTILITY:FeedRequest;
import PTFP_FEED:Interface:IBGetFeedList;
import PTFP_FEED:FeedFactory;
import PTFP_FEED:EXCEPTION:*;


class MyFeedHandler implements PS_PT:Integration:IRequestHandler
   /* --- Properties --- */

   /* --- Methods --- */
   method MyFeedHandler();
   method OnRequest(&pRequestMsg As Message) Returns Message;
   method OnError(&pRequestMsg As Message) Returns string;
end-class;


/** onRequest is defined. Other methods shown as stubs. **/


method MyFeedHandler

   /* method stub */

end-method;


method OnError
   /+ &pRequestMsg as Message +/
   /+ Returns String +/
   /+ Extends/implements PS_PT:Integration:IRequestHandler.OnError +/
   Local string &errstring;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
   /* method stub */
   Return &errstring;
end-method;


/**
  * onRequest
  *
  * @param pRequestMsg Request Message.
  *
  * @exception FeedException thrown if switch user failed.
  *
  * @return Message Feed Document.
  *
  */
method OnRequest
   /+ &pRequestMsg as Message +/
   /+ Returns Message +/
   /+ Extends/implements PS_PT:Integration:IRequestHandler.OnRequest +/

   Local boolean &succeeded;
   Local integer &i;
   Local string &temp, &name, &value;
   Local string &errorText;
   Local string &ibTransID, &pageNum, &HTTP_IfNoneMatch, &HTTP_IfModifiedSince, &De⇒
faultLocalNode;

   Local Message &responseMsg;
   Local XmlDoc &xmlDoc;

   Local PTFP_FEED:FeedFactory &feedFactory_inst;
   Local PTFP_FEED:UTILITY:Utility &utility = &feedFactory_inst.Utility;
   Local PTFP_FEED:XML_FEED:FeedDoc &feedDoc;
   Local PTFP_FEED:UTILITY:FeedRequest &request;
   Local PTFP_FEED:Interface:IBGetFeedList &feedListObj;


   /* Ccreate the Search Request object */
   &request = create PTFP_FEED:UTILITY:FeedRequest("FeedRequest");


   /* Get the search criteria */
   For &i = 1 To &pRequestMsg.IBInfo.IBConnectorInfo.GetNumberOfQueryStringArgs()

      &name = &pRequestMsg.IBInfo.IBConnectorInfo.GetQueryStringArgName(&i);
      &value = &pRequestMsg.IBInfo.IBConnectorInfo.GetQueryStringArgValue(&i);
      &succeeded = &request.addParameter(&name, &value);


      Evaluate Upper(&name)
      When Upper(&utility.QUERYPARAMETER_FEEDLIST)
         /* Feed List Request, forward the call */
         &feedListObj = create PTFP_FEED:Interface:IBGetFeedList();
         Return &feedListObj.OnRequest(&pRequestMsg);

      When Upper(&utility.QUERYPARAMETER_PORTALNAME)
         &request.PortalName = &value;
         Break;

      When Upper(&utility.QUERYPARAMETER_NODENAME)
         &request.NodeName = &value;
         Break;

      When Upper(&utility.QUERYPARAMETER_DATATYPEID)
         &request.DataTypeID = &value;
         Break;

      When Upper(&utility.QUERYPARAMETER_FEEDID)
         &request.FeedID = &value;
         Break;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
      When Upper(&utility.QUERYPARAMETER_LANGUAGE)
         &request.LanguageCode = &value;
         Break;

      When Upper(&utility.QUERYPARAMETER_IBTRANSID)
         &ibTransID = &value;
         Break;

      When Upper(&utility.QUERYPARAMETER_PAGENUM)
         &pageNum = &value;
         Break;

      When Upper(&utility.QUERYPARAMETER_DEFLOCALNODE)
         &DefaultLocalNode = &value;
         Break;

         /* HTTP Conditonal Headers */
      When Upper(&utility.QUERYPARAMETER_IFNONEMATCH)
         &HTTP_IfNoneMatch = &value;
         Break;

      When Upper(&utility.QUERYPARAMETER_IFMODIFIEDSINCE)
         &HTTP_IfModifiedSince = &value;
         Break;

      End-Evaluate;
   End-For;


   /* Get the current user PS_TOKEN */
   &request.PS_TOKEN = GenToken();


   /* Get the FeedDoc */
   &errorText = "";

   try

      &feedDoc = &feedFactory_inst.getFeedDoc(&request);

   catch PTFP_FEED:EXCEPTION:NotFoundException &ex1
      &errorText = MsgGetExplainText(219, 3112, "(Message not found) Not Found");

   catch PTFP_FEED:EXCEPTION:PrivilegeException &ex2
      &errorText = MsgGetExplainText(219, 3113, "(Message not found) Not Authorized⇒
");

   catch PTFP_FEED:EXCEPTION:FeedException &ex3
      &errorText = &utility.getExceptionText(&ex3);

   end-try;


   /* Create the response message */
   &responseMsg = CreateMessage(Operation.PTFP_GETFEED, %IntBroker_Response);

   If None(&errorText) Then
      &responseMsg = &utility.setMessageHeadersAndMimeType(&responseMsg, &feedDoc, ⇒
&request);
   Else
      &temp = "<?xml version='1.0' encoding='UTF-8'?><ErrorMessage>" | &errorText |⇒
 "</ErrorMessage>";
      &xmlDoc = CreateXmlDoc(&temp);
      &responseMsg.SetXmlDoc(&xmlDoc);
      &responseMsg.SegmentContentType = &utility.MIMETYPE_XML;
   End-If;

   Return &responseMsg;

end-method;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Chapter 21

Field Class

Understanding the Field Class

A *field* object, instantiated from the field class, is a single instance of data within a record object, and is based on a field definition.

Accessing or changing the value of a field using the Value property is a common action.

SetDefault is a frequently used method. Name, Enabled, and Type are several commonly used field properties. If you are working with message objects, EditError is also a commonly used field property.

The field class is one of the data buffer access classes.

Related Links

"Understanding Data Buffer Access" (PeopleTools 8.54: PeopleCode Developer's Guide)

Considerations Using User Interface Properties

All of the field properties related to the user interface, such as the Label property, only return the value previously set in PeopleCode (false, or blank if nothing was set). They do not return the values set for the field in Application Designer.

Shortcut Considerations

An expression of the form

`FIELD.`*`fieldname.property`*

or

`FIELD.`*`fieldname.method`*`(. . .)`

is converted to an object expression by using `GetField(`**`FIELD.`***`fieldname`*`)`. For example, the next two lines of code are identical:

```
FIELD.CHECKLIST_DT.Enabled = False;
```

```
GetField(FIELD.CHECKLIST_DT).Enabled = False;
```

An expression of the form

`recname.fieldname.property`

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

or

```
recname.fieldname.method(.  .  .)
```

is converted to an object expression by using `GetField(recname.fieldname)`. For example, the next two lines of code are identical:

```
EMPL_CHECKLINST.CHECKLIST_DT.Enabled = False;
```

```
GetField(EMPL_CHECKLIST.CHECKLIST_DT).Enabled = False;
```

Data Type for a Field Object

Field objects are declared as type Field. For example,

```
Local Field &MyField;
```

Scope of a Field Object

A field can only be instantiated from PeopleCode.

This object can be used anywhere you have PeopleCode, that is, in an application class, Application Engine PeopleCode, record field PeopleCode, and so on.

Field Class Built-in Functions

"GetField" (PeopleTools 8.54: PeopleCode Language Reference)

"GetPageField" (PeopleTools 8.54: PeopleCode Language Reference)

Field Class Methods

In this section, we discuss the Field class methods in alphabetical order.

AddDropDownItem

Syntax

AddDropDownItem(*CodeString*, *DescriptionString*)

Description

The AddDropDownItem method adds an item to the dropdown list in the control for the field. The first time this method is called, it overrides the prompt table or translate table used to populate the list. Those items no longer appear in the list. Only the items added using this method display.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Subsequent calls to this method adds additional items to the dropdown list. The items added with the first call to the method also display.

If there is an existing value and the dropdown list is changed with these functions, the selection shows as (Invalid value) unless the new list contains an entry with the same code as the existing value.

Considerations Using AddDropDownItem

If the data for the dropdown is language sensitive, the values for the dropdown should come from the message catalog or from a database field that has a related language record, and should not be hard-coded.

A good place for your PeopleCode program to populate a dropdown list is in the RowInit event. This event executes before the page is shown for the first time, so it prevents unnecessary SQL.

Parameters

CodeString	Specify the value used to set the field value if this item is selected. Codes longer than the size of the field are truncated.
DescriptionString	Specify the value the end-user sees in the dropdown list.

Returns

None.

Example

Using a hardcoded list is not appropriate for this function because translations do not work. The data must come from the Translate Table (or other record) directly so that the data is translated correctly.

```
Local Rowset &Xlat;

&FLD = GetRecord(Record.JOB).GetField(Field.ACTION);
&FLD.ClearDropDownList();

Evaluate %Component
When Component.JOB_DATA_CONCUR
   &Xlat = CreateRowset(Record.PSXLATITEM);
   &Xlat.Fill("WHERE FILL.FIELDNAME = 'ACTION' AND Fill.FIELDVALUE in ('ADL','HIR')⇒
 and EFFDT = (select max(EFFDT) from PSXLATITEM B where B.FIELDNAME = 'ACTION' and ⇒
B.FIELDVALUE in ('ADL','HIR') and EFFDT <= JOB.EFFDT)");

   &Xlat_cnt = &Xlat.ActiveRowCount;
   For &I = 1 To &Xlat_cnt
      &CodeIn = &Xlat.GetRow(&I).GetRecord(1).FIELDVALUE.Value;
      &DescIn = &Xlat.GetRow(&I).GetRecord(1).XLATLONGNAME.Value;

      &FLD.AddDropDownItem(&CodeIn, &DescIn);
   End-For;

   Break;
When-Other
End-Evaluate;
```

Related Links

ClearDropDownList

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

AddFFClass

Syntax

AddFFClass(*style_names*)

Description

Use the AddFFClass method to update the value of the FreeFormStyleName property. This method appends free form style classes to any existing styles defined by the FreeFormStyleName property for this field.

Important! Use this method within fluid applications only.

Parameters

style_names	Specifies the style names as a string value.

Returns

None.

Example

```
&fld1.AddFFClass("active color_red");
```

Related Links

ReplaceFFClass
FreeFormStyleName

ClearDropDownList

Syntax

ClearDropDownList()

Description

The ClearDropDownList method clears all items added to the dropdown list using the AddDropDownItem method. In addition, this method causes the prompt table or translate table values defined for the list to come back into effect again (unless they're subsequently overridden again with AddDropDownItem.)

Parameters

None.

Returns

None.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

```
&FLD = GetRecord(Record.ABSENCE_HIST).GetField(Field.ABSENCE_TYPE);
&FLD.AddDropDownItem("CNF", "Conference");
&FLD.AddDropDownItem("VAC", "Vacation");
&FLD.AddDropDownItem("SCK", "Sick");
. . . .
&FLD.ClearDropDownList();
```

Related Links

AddDropDownItem

GetAuxFlag

Syntax

GetAuxFlag(*FlagNumber*)

Description

Use the GetAuxFlag method to determine whether the Auxiliary Flag Mask specified by *FlagNumber* has been set for a field.

Currently, only one flag comes preset from PeopleSoft: a 1 indicates a ChartField.

Parameters

FlagNumber	Specify the flag number. 1 is a ChartField. Valid values are between 1 and 32.

Returns

A Boolean value: True, the flag is set, False if the flag hasn't been set.

Example

```
&field = GetField(Field.RC_TEST_PB);
&ret = &field.GetAuxFlag(1);
If (&ret = True) Then
   MessageBox(0, "Metadata Fn Status", 0, 0, "Aux Flag 1 is SET - ChartField");
Else
   MessageBox(0, "Metadata Fn Status", 0, 0, "Aux Flag 1 is NOT SET - Not a ChartFi⇒
eld");
End-If;
```

Related Links

"SetDBFieldAuxFlag" (PeopleTools 8.54: PeopleCode Language Reference)

GetDNDField

Syntax

GetDNDField()

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the GetDNDField method to return the field from which the drag started—that is, the source field.

Important! Use this method within fluid applications only.

Parameters

None.

Returns

A Field object.

Example

```
Local Field &field1 = GetDNDField();
```

Related Links

GetDNDRow
GetDNDRowset
Draggable
"Setting Group Box Properties" (PeopleTools 8.54: Fluid User Interface Developer's Guide)

GetDNDRow

Syntax

GetDNDRow()

Description

Use the GetDNDRow method to return the row from which the drag started—that is, the source row.

Important! Use this method within fluid applications only.

Parameters

None.

Returns

A Row object.

Example

```
Local Row &dragRow = GetDNDRow();
Local integer &fromRowNum = &dragRow.RowNumber;
```

Related Links

GetDNDField

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GetDNDRowset
Draggable
"Setting Group Box Properties" (PeopleTools 8.54: Fluid User Interface Developer's Guide)

GetDNDRowset

Syntax

GetDNDRowset()

Description

Use the GetDNDRowset method to return the rowset from which the drag started—that is, the source rowset.

Important! Use this method within fluid applications only.

Parameters

None.

Returns

A Rowset object.

Example

```
Local Rowset &rs = GetDNDRowset();
```

Related Links

GetDNDField
GetDNDRow
Draggable
"Setting Group Box Properties" (PeopleTools 8.54: Fluid User Interface Developer's Guide)

GetDNDTargetField

Syntax

GetDNDTargetField()

Description

Use the GetDNDTargetField method to return the field on which the drop occurred—that is, the target field.

Important! Use this method within fluid applications only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

None.

Returns

A Field object.

Example

```
Local Field &field2 = GetDNDTargetField();
```

Related Links

GetDNDTargetRow
GetDNDTargetRowset
Droppable
"Setting Group Box Properties" (PeopleTools 8.54: Fluid User Interface Developer's Guide)

GetDNDTargetRow

Syntax

GetDNDTargetRow()

Description

Use the GetDNDTargetRow method to return the row on which the drop occurred—that is, the target row.

Important! Use this method within fluid applications only.

Parameters

None.

Returns

A Row object.

Example

```
Local Row &toRow = GetDNDTargetRow();
Local integer &toRowNum = &toRow.RowNumber;
```

Related Links

GetDNDTargetField
GetDNDTargetRowset
Droppable
"Setting Group Box Properties" (PeopleTools 8.54: Fluid User Interface Developer's Guide)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GetDNDTargetRowset

Syntax

GetDNDTargetRowset()

Description

Use the GetDNDTargetRowset method to return the rowset on which the drop occurred—that is, the target rowset.

Important! Use this method within fluid applications only.

Parameters

None.

Returns

A Rowset value.

Example

```
Local Rowset &rs2 = GetDNDTargetRowset();
```

Related Links

GetDNDTargetField
GetDNDTargetRow
Droppable
"Setting Group Box Properties" (PeopleTools 8.54: Fluid User Interface Developer's Guide)

GetLongLabel

Syntax

GetLongLabel(*LabelID*)

Description

The GetLongLabel method returns the long name for a field given a label ID. If the given label ID isn't found, a null string is returned. *LabelID* takes a string value.

Note: If a button is defined as an HTML button or hyperlink, and if it has an associated record field, the label associated with it is only the text of the button. The mouse-over text can only be changed by the lable if the button is defined as a button with an Image label.

Returns

A text string containing the long name of the field for the specified label ID.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

The following code sets the label for a field to one of two different texts, based on the page.

```
Local Field &FIELD;

&FIELD = GetField(RECORD.MYFIELD);
   If %Page = PAGE.PAGE1 Then
      &FIELD.Label = &FIELD.GetLongLabel("LABEL1");
   Else If %Page = PAGE.PAGE2 Then
      &FIELD.Label = &FIELD.GetLongLabel("LABEL2");
End-If;
```

If the Label ID is the same as the name of the field, you could use the following:

```
&LABELID = &FIELD.Name;
&FIELD.Label = &FIELD.GetLongLabel(&LABELID);
```

Related Links

GetShortLabel

Label

"SetLabel" (PeopleTools 8.54: PeopleCode Language Reference)

GetRelated

Syntax

GetRelated(*recname.fieldname*)

Description

The GetRelated method returns a field object for a related field *recname.fieldname* that has the field executing the method as its control field.

This method is similar to the GetRelField built-in function, however, the built-in works only in the current context, while this method can be applied to a field from any position in the buffer structure.

Using GetRelated With a Control Field

PeopleCode events on the Control Field can be triggered by the Related Edit field. When this happens, there can be different behavior than with other types of fields:

- If the events are called from FieldEdit of the Control Field, and that FieldEdit is triggered by a change in the Related Edit field, the functions return the previous value.
- If the events are called from FieldChange of the Control Field, and that FieldChange is triggered by a change in the Related Edit field, the functions return the value entered into the Related Edit. This may be a partial value, that will subsequently be expanded to a complete value when the processing is complete.

Parameters

recname.fieldname	Specifies a field in the same row as the current field object, that has the field executing the method as its control field.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

The field object for the field with the specified name that is related to the field executing the method.

Example

In the following example, the field object is instantiated, then the related display field object. The Value property for the related display is changed, it is disabled, and another variable is assigned its value.

```
Local Field &FIELD, &REL_FIELD;

&FIELD = GetField(OPC_9A2FIELDS.COMPANY);
/* control field object  */
&REL_FIELD = &FIELD.GetRelated(COMPANY_TBL.DESCR);
/* related display object */
&REL_FIELD.Value = "Change";
&REL_FIELD.Enabled = False;
&TMP = &REL_FIELD.Name;
&REL_FIELD.Value = &TMP;
```

If you were not going to use the &FIELD variable later, the first two lines of code in the previous example could be combined:

```
&REL_FIELD = GetField(OPC_9A2FIELDS.COMPANY).GetRelated(COMPANY_TBL.DESCR);
```

Suppose you had two control fields, EMPLID and MANAGER_ID, and both use the NAME field on the PERSONAL_DATA table as their related display. If you need to access both related display fields, you could do the following:

```
&NAME_EMPLID = GetField(PERSONAL_DATA.EMPLID).GetRelated(PERSONAL_DATA.NAME);

&NAME_MANAGER = GetField(PERSONAL_DATA.MANAGER_ID).GetRelated(PERSONAL_DATA.NAME);
```

Related Links

"GetField" (PeopleTools 8.54: PeopleCode Language Reference)

GetShortLabel

Syntax

GetShortLabel(*LabelID*)

Description

The GetShortLabel method returns the short name for a field given a label ID. If the given label ID isn't found, a null string is returned. *LabelID* takes a string value.

Note: If a button is defined as an HTML button or hyperlink, and if it has an associated record field, the label associated with it is only the text of the button. The mouse-over text can only be changed by the lable if the button is defined as a button with an Image label.

Returns

A text string containing the short name of the field for the specified label ID.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

The following code sets the label for a field to one of two different texts, based on the page.

```
Local Field &FIELD;

&FIELD = GetField(RECORD.MYFIELD);
   If %Page = PAGE.PAGE1 Then
      &FIELD.Label = &FIELD.GetShortLabel("LABEL1");
   Else If %Page = PAGE.PAGE2 Then
      &FIELD.Label = &FIELD.GetShortLabel("LABEL2");
End-If;
```

If the Label ID is the same as the name of the field, you could use the following:

```
&LABELID = &FIELD.Name;
&FIELD.Label = &FIELD.GetShortLabel(&LABELID);
```

Related Links

GetLongLabel

Label

"SetLabel" (PeopleTools 8.54: PeopleCode Language Reference)

ReplaceFFClass

Syntax

ReplaceFFClass(*from_style*, *to_style*, *append*)

Description

Use the ReplaceFFClass method to update the value of the FreeFormStyleName property. This method replaces the *from_style* with the *to_style*. If the *from_style* does not exist, the *to_style* is added to the style list, only if the optional *append* parameter is True.

Note: ReplaceFFStyle can only replace the styles set through PeopleCode using the AddFFClass method or the FreeFormStyleName property and the not those set through Application Designer.

Important! Use this method within fluid applications only.

Parameters

from_style	Specifies the style (or list of styles) to be replaced as a string value.
to_style	Specifies the replacement style (or list of styles) as a string value.
append	Specifies a Boolean value indicating whether the *to_style* value is to be appended when the *form_style* does not exist. The default value is False.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

None.

Example

```
&field1.ReplaceFFClass("dateStyle", "emphasis");
&field2.ReplaceFFClass("hidden", "");
```

Related Links

AddFFClass

FreeFormStyleName

SearchClear

Syntax

SearchClear()

Description

The SearchClear method clears the field values if the field is a search key.

Considerations Using SearchClear and SetDefault

The SetDefault method causes a field to be set to its default value (if there is one) immediately after SearchInit PeopleCode finishes. SetDefault overrides SearchClear. If you call SearchClear for a record, then use SetDefault for a field, the field is set to its default value and the search key values for the rest of the record are cleared.

Parameters

None.

Returns

None.

Example

```
Local Field &FIELD;

&FIELD = GetField(PERSONAL_DATA.EMPLID);
&FIELD.SearchClear();
```

Related Links

SetDefault

SearchClear

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SetCursorPos

Syntax

SetCursorPos(**Page.***page_name* | **%Page**)

Description

The SetCursorPos method enables you to set the focus to the page field corresponding to the current Field object (on the specified page). The current page may be specified as **%Page**.

Restrictions on Use with a Component Interface

This method is ignored (has no effect) when used by a PeopleCode program that's been called by a component interface.

Parameters

Page.*page_name*	The name of the page, preceded by the keyword **Page**. The *page_name* page must be in the current component. You can also pass the **%Page** system variable in this parameter (without the **Page** reserved word).

Returns

None.

Example

The following pseudo-code enables you to set the focus to a related field:

```
GetField(ControlRec.ControlField).GetRelated(RelatedRec.RelatedField).SetCursorPos(⇒
Page.pagename);
```

The following example places the cursor in the current field if a SaveEdit validation fails. Note the use of the **%Page** system variable to get the page name. Note also that SetCursorPos is called before Error.

```
If None(DERIVED_SECURTY.OPERPSWD) Then
   GetField(DERIVED_SECURTY.OPERPSWD).SetCursorPos(%Page);
   Error MsgGet(48, 268, "Message Not Found");
End-If;
```

Related Links

SetDefault

"SetCursorPos" (PeopleTools 8.54: PeopleCode Language Reference)

SetDefault

Syntax

SetDefault()

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

SetDefault sets the value of the field to a null value, or to a default, depending on the type of field.

- If this method is used against data from the component buffers, the next time default processing occurs, it is set to its default value: either a default specified in its record field definition or one set programmatically by PeopleCode located in a FieldDefault event. If neither of these defaults exist, the Component Processor leaves the field blank.
- If this method is used with a field that isn't part of the data buffer (for example, a field in a record object instantiated with CreateRecord) the field is automatically set to its default value if one is set for the *field*, not for the record field. Any FieldDefault PeopleCode will not be run on these types of fields. If you want to set the default values for all the fields in a record, use the SetDefault record class method.

Blank numbers correspond to zero on the database. Blank characters correspond to a space on the database. Blank dates and long characters correspond to NULL on the database. SetDefault gives each field data type its proper value.

Parameters

None.

Returns

None.

Example

```
&CHARACTER.SetDefault();
```

Related Links

SetDefault
"Default Processing" (PeopleTools 8.54: PeopleCode Developer's Guide)

SetGroupletActionUrl

Syntax

SetGroupletActionUrl(*URL*)

Description

Use the SetGroupletActionUrl method to set the URL to which the user is transferred when the user clicks the tile (also referred to as a grouplet).

Important! Use this method within fluid applications only.

Parameters

URL	Specifies the URL as a string value.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

None.

Example

```
PT_AG_LAYOUT.PT_AG_GROUPBOX3.SetGroupletActionUrl("http://example.com:8080/psc/ps5/⇒
EMPLOYEE/HRMS/s/WEBLIB_PTAI.ISCRIPT1.FieldFormula.IScript_LoadSubpageButtons?PTAI_L⇒
IST_ID=PTIB_IBCFG1001&fmode=1");
```

SetGroupletDisplayIn

Syntax

SetGroupletDisplayIn(*display_in*)

Description

Use the SetGroupletDisplayIn method to set the location where the tile (also referred to as a grouplet) will be displayed.

Important! Use this method within fluid applications only.

Parameters

display_in Specifies the display location as an integer value:

- 0 – Current window
- 1 – New window
- 2 – Modal
- 3 – NavBar

Returns

None.

Example

```
PT_AG_LAYOUT.PT_AG_GROUPBOX3.SetGroupletDisplayIn(0);
```

SetGroupletID

Syntax

SetGroupletID(*field_ID*)

Description

Use the SetGroupletID method to set the ID of the group box (HTML ID of the record field) from which the content is rendered.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Important! Use this method within fluid applications only.

Parameters

field_ID Specifies the HTML ID of the record field as a string value.

Returns

None.

Example

In the following example, PT_AG_LAYOUT_PT_AG_GROUPBOX5 is the HTML field ID of the group box on the page:

```
PT_AG_LAYOUT.PT_AG_GROUPBOX3.SetGroupletID("PT_AG_LAYOUT_PT_AG_GROUPBOX5");
```

SetGroupletImage

Syntax

SetGroupletImage(*image_ID*)

Description

Use the SetGroupletImage method to specify the database ID for the tile's preload image—that is, the image that is displayed while the content for the tile (also referred to as a grouplet) is being retrieved and loaded.

Important! Use this method within fluid applications only.

Parameters

image_ID Specifies the database ID for the image as a string value.

Returns

None.

Example

```
&rec.GROUPLET.SetGroupletImage("ORG_CHART_128");
```

SetGroupletMOptions

Syntax

SetGroupletMOptions(*grouplet_modal_options*)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the SetGroupletMOptions method to set the modal options for the tile (also referred to as a grouplet).

Important! Use this method within fluid applications only.

Parameters

grouplet_modal_options Specifies the modal option for the tile as a string value.

Returns

None.

Example

```
/* Action Menu */
Local string &sMenuTitle = MsgGetText(124, 524, "Message Not Found: Action Menu");
PTLAYOUT.HEADER_ACTIONGROUP.SetGroupletMOptions("sStyle@ps_popup-menu ps_menutype-a⇒
ct;sTitle@" | &sMenuTitle | ";bAutoClose@1;bMask@1;sMaskStyle@ps_masktrans;bVertica⇒
l@1;bHeader@0;");
```

SetGroupletTargetID

Syntax

SetGroupletTargetID(*target_ID*)

Description

Use the SetGroupletTargetID method to set the target ID attribute of the tile (also referred to as a grouplet) used in the NavBar.

Important! Use this method within fluid applications only.

Parameters

target_ID Specifies the target ID attribute as a string value.

Returns

None.

Example

```
&rec.GROUPLET.SetGroupletTargetID("NB_CONTENT_TGT"); /* NEW TARGET ID*/
```

SetGroupletTimer

Syntax

SetGroupletTimer(*time_in_seconds*)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the SetGroupletTimer method to set the time in seconds after which the tile (also referred to as a grouplet) will be refreshed with the data.

Important! Use this method within fluid applications only.

Parameters

time_in_seconds Specifies the time in seconds after which the tile is refreshed with data, as an integer value.

Returns

None.

Example

```
&rec.GROUPLET.SetGroupletTimer(0);
```

SetGroupletType

Syntax

SetGroupletType(*type*)

Description

Use the SetGroupletType method to set the type for the group box as follows:

Value	*Description*
0	Not a tile (also referred to as a grouplet). This is a regular group box with its content coming from the same page records.
1	Tile with style. This producer tile includes its own style sheets, JavaScript, or both. **Important!** Be aware that this setting can inject style settings or JavaScript code that conflicts with those defined for the page.
2	Tile without style. This producer tile does not include style sheets or JavaScript. This is the recommended settings.

Important! Use this method within fluid applications only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

type	Specifies the type for the group box as an integer value.

Returns

None.

Example

```
&rec.GROUPLET.SetGroupletType(2); /* 1 with style, 2 no style */
```

SetGroupletUrl

Syntax

SetGroupletUrl(*URL*)

Description

Use the SetGroupletUrl method to set the URL from which the tile (also referred to as a grouplet) content is rendered.

Important! Use this method within fluid applications only.

Parameters

URL	Specifies the URL as a string value.

Returns

None.

Example

```
PT_AG_LAYOUT.PT_AG_GROUPBOX3.SetGroupletUrl("http://example.com:8080/psc/ps5/EMPLOY⇒
EE/HRMS/s/WEBLIB_PTAI.ISCRIPT1.FieldFormula.IScript_LoadSubpageButtons?PTAI_LIST_ID⇒
=PTIB_IBCFG1001&fmode=1");
```

Field Class Properties

In this section, we discuss the Field class properties. The properties are discussed in alphabetical order.

DataAreaCollapsed

Description

This property specifies whether the default initial view of the data area of a group box is collapsed or expanded.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Note: You must set the Collapsible Data Area on the properties for the group box in Application Designer for this property to have any effect.

This property changes to reflect the current state of the data area, according to whether the user has collapsed or expanded it. Changing the value collapses or expands the data area, but it does *not* prevent the user from collapsing (or expanding) it themselves.

Note: Because the user can change the value of this property, whatever value is set in PeopleCode isn't guaranteed to be still set the next time it is checked, because the user may have collapsed or expanded the data area in the meantime.

This property overwrites the value of the Default Initial View to Expanded field set in Application Designer. For example, if Default Initial View to Expanded is selected in Application Designer, then the value for the DataAreaCollapsed property is set to True, the control initially displays collapsed.

This property takes a Boolean value: True, initially display the data area collapsed, False, initially display the data area expanded.

This property is read-write.

Note: If you want to collapse an entire level-based control, such as a scroll area or a grid, use the DataAreaCollapsed Rowset method.

Related Links

DataAreaCollapsed

DecimalPosition

Description

Use this property to specify the number of digits after the decimal point to be displayed for a field defined as number or signed number.

This property *overwrites* the Decimal Positions value defined for a field in Application Designer.

Setting the DecimalPosition property to a smaller number than the record field's decimal position causes the displayed data to be truncated. For example, suppose a numeric field in the database has a value 0.005. Setting DecimalPosition to 2 displays 0.00 on page.

This property takes an integer value. The default value is -1, which indicates that the property is not set.

This property is read-write.

Related Links

"Specifying Number Field Attributes" (PeopleTools 8.54: Application Designer Developer's Guide)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

DisplayFormat

Description

Image: PHONE-INTL format

The following image is an example of PHONE-INTL format.

Use this property to specify a custom format to use for the field.

This property is read-write.

The custom format for a field is specified in the field definition. This property enables you to switch between display formats that are defined as part of a custom format. For example, suppose your field used the PHONE-INTL custom format:

Both the LONG and the SHORT stored formats have two display formats: STANDARD and UNFORMATTED.

Using this property, you could select either of the display formats. For example:

```
If %Component = PAGE.INTERNATIONAL
   &CHAR.DisplayFormat = "STANDARD";
Else
   &CHAR.DisplayFormat = "UNFORMATTED";
End-If;
```

Note: You *cannot* change the Stored format, but you can find its value using the StoredFormat property.

Example

```
&CHARACTER.DisplayFormat = "STANDARD";

/* this assumes that &CHARACTER is a custom formatted field,
and a display format option is STANDARD */
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

StoredFormat

DisplayOnly

Description

This property is set to true if the field property DisplayOnly in the Application Designer is set. May be set to false to change how the field displays.

Note: This property *overwrites* whatever value is set in Application Designer.

This property is read-write.

DisplayZero

Description

Use this property to specify if, in a numeric field, zeros or blank are displayed on a page.

This property *overwrites* the Display Zero value on the page field properties dialog box in Application Designer.

This property takes a Boolean value: true, display zeros, false, display blank. The default values is false.

The value of the DisplayZero property can be changed by the SmartZero property.

If SmartZero is set to true, and your application sets DisplayZero to false in a PeopleCode program, the application server changes the value of DisplayZero to true to display zeros, not blanks. When this occurs, the DisplayZeroChanged property is set to true.

This property is read-write.

Related Links

DisplayZeroChanged

SmartZero

"Specifying Attributes for a New Field Definition" (PeopleTools 8.54: Application Designer Developer's Guide)

DisplayZeroChanged

Description

Use this property to determine if the original DisplayZero property has been changed from its original setting.

The DisplayZeroChanged property is only relevant when the SmartZero property has been set to true. When SmartZero equals true, the application server adjusts the DisplayZero property to display a blank or zero based on the user's input. You can then check the DisplayZeroChanged property to find out if the application server has changed the DisplayZero property.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property takes a Boolean value: true, the application server has changed the field's DisplayZero property, false otherwise.

For example, suppose you have a PeopleCode program in the RowInit event that sets the DisplayZero property for a field to True, and also sets the SmartZero property to True. When a user deletes the numeric zero in that field on the page, and the page is submitted to the application server, the application server sets the field's DisplayZero property to False so that the new page displays a blank, not a numeric zero. The DisplayZeroChanged property is set to true in this example.

This property is read-only.

Related Links

DisplayZero
SmartZero

Draggable

Description

Use this property to set or return a Boolean value indicating whether the Draggable property for the group box field has been enabled (on the Fluid tab), which allows content to be dragged from this group box.

This property is read-write.

Important! Use this property within fluid applications only.

Example

```
&field1.Draggable = True;
```

Related Links

"Setting Group Box Properties" (PeopleTools 8.54: Fluid User Interface Developer’s Guide)

Droppable

Description

Use this property to set or return a Boolean value indicating whether the Droppable property for the group box field has been enabled (on the Fluid tab), which allows content to be dropped into this group box.

This property is read-write.

Important! Use this property within fluid applications only.

Example

```
&field2.Droppable = True;
```

Related Links

"Setting Group Box Properties" (PeopleTools 8.54: Fluid User Interface Developer’s Guide)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

EditError

Description

This property is True if an error for this field has been found after executing the ExecuteEdits method with either a message object or a record object. This property can be used with the MessageSetNumber and MessageNumber properties to find the error message set number and error message number.

The EditError property returns True if a Null value was encountered for this field.

This property is read-write. After you have fixed the errors, you must set this property to False before running ExecuteEdits again.

Example

The following is an example showing how EditError, along with the ExecuteEdits method could be used:

```
&REC.ExecuteEdits();
If &REC.IsEditError Then
   For &I = 1 to &REC.FieldCount
      If &REC.GetField(&I).EditError Then
         LOG_ERROR();  /* application specific pgm */
      End-If;
   End-For;
End-If;
```

Related Links

ExecuteEdits

ExecuteEdits

MessageNumber

MessageSetNumber

Enabled

Description

This property is True if this field is enabled. May be set False to disable any control that displays this field.

This property is read-write.

Example

```
&CHARACTER.Enabled = True;

&CHARACTER.Enabled = False;
```

FieldLength

Description

This property returns the length of the field as a number.

This property is read-only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

```
&MyRec = CreateRecord(Record.BKREC1);
&MyField = &MyRec.GetField(Field.BKNAME);
&length = &MyField.FieldLength;
MessageBox(0, "Field Length", 0, 0, "The field BKREC1.BKNAME is length " | &length)⇒
;
```

FormatLength

Description

This property returns the length of the format for the field as a number.

This property is read-only.

Example

```
&field = GetField(Field.BKTEST);
&formatlength = &field.FormatLength;
&length = &field.FieldLength;
&mymsg = "Field.BKTEST length is " | &length | " and format length is " | &formatle⇒
ngth;
MessageBox(0, "MetaData Fn Status", 0, 0, &mymsg);
```

FormattedValue

Description

This property returns the value of a field as a string, formatted exactly as it would be displayed on an edit field on a page. This is useful when you're using a prompt field for the label of another field.

Because a record field can be bound to more than one page field, FormattedValue takes the first associated page field, looking first on the current page, then through all the pages in the component. This property returns a null string ("") if used with an Image or ContentReference field. It also returns a null string if no associated page field is found.

This property is read-write.

Example

This property could be used to set up a hyperlink labeled by data generated on a page. To do this, do the following:

1. Define a work field.
2. Associate the work field with the hyperlink page field.
3. Define a hidden page field with the formatting that you want.
4. Associate the hidden page field with the data field.
5. Write PeopleCode (probably for RowInit) to set the label on the work field to be the FormattedValue of the data field.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

For example, suppose you wanted a hyperlink labeled by the QE_POSITION_ID field on the QE_PLYR_POSITN record. This field is a prompt table field, edited by table QE_POSITION.

You want to display the DESCRSHORT field from the prompt table, instead of the QE_POSITION_ID code value. Create a work field, POS_LINK on the WORK_REC record, and create a hyperlink page field associated with the DESCRSHORT field. For the label, create an invisible drop-down list page field, associated with QE_PLYR_POSITN.QE_POSITION_ID. Set its Prompt Table Field to DESCRSHORT. Then put a PeopleCode program on the component RowInit for either the QE_PLYR_POSITN record or the WORK_REC.

```
WORKREC.POS_LINK.Label = QE_PLYR_POSITN.QE_POSITION_ID.FormattedValue;
```

FreeFormStyleName

Description

Use this property to set or return a String representing the free form style (or styles) for the field as previously set by FreeFormStyleName or modified by AddFFStyle or ReplaceFFStyle.

Note: Styles for this field set in Application Designer are not accessible through the FreeFormStyleName property.

This property is read-write.

Important! Use this property within fluid applications only.

Example

```
GetLevel0()(1).QE_WORK_REC1.OPTION_CD.FreeFormStyleName = "psc_border psc_margin-le⇒
ft05em";
```

Related Links

AddFFClass

ReplaceFFClass

HoverText

Description

Use this property to override the hover text for any push buttons or hyperlinks associated with the field. The maximum length of hover text is 100 characters. If the hover text is identical to the push button or hyperlink label, the hover text will not be shown.

Important! Even if the hover text has been set in Application Designer, this property returns a blank string if you use the property before you've explicitly set it in PeopleCode. This property overrides the existing value only. When a user navigates away from the component, and then back to the page again, the original value is used until it's changed again through PeopleCode.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

```
QE_ABSENCE_HIST.QE_ABSENCE_TYPE.HoverText = MsgGetText(95, 5037, "Personalize Layou⇒
t");
```

Related Links

Label

HtmlAttributes

Description

Use this property to set or return a String representing HTML attributes on the field.

Warning! This is a free form field and does not check for any HTML or JavaScript errors.

This property is read-write.

Important! Use this property within fluid applications only.

Example

```
&sLabel = MsgGetText(280, 18, "Bulk Mode");
PTS_SRCH.PTS_BULKMODE.HtmlAttributes = "title='" | &sLabel | "' alt='" | &sLabel | ⇒
"'";
```

HtmlInputType

Description

Use this property to set or return an Integer representing the HTML field type. The value can be one of the following constants:

Numeric Value	*Constant Value*
0	%text
2	%date
3	%datetime
5	%email
7	%number
8	%range
9	%search
10	%tel

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Numeric Value	*Constant Value*
11	%time
12	%url

This property is read-write.

Important! Use this property within fluid applications only.

Example

```
GetLevel0()(1).QE_WORK_REC1.OPTION_CD.HtmlInputType = %date;
```

IsAltKey

Description

This property is True if this field references a field definition that is defined as an Alternate Search key in the associated record definition.

This property is read-only.

IsAuditFieldAdd

Description

This property is True if this field references a field definition that is defined as an audit field in the associated record definition, and the field is audited whenever new data is added.

This property is read-only.

IsAuditFieldChg

Description

This property is True if this field references a field definition that is defined as an audit field in the associated record definition, and the field is audited whenever data is changed.

This property is read-only.

IsAuditFieldDel

Description

This property is True if this field references a field definition that is defined as an audit field in the associated record definition, and the field is audited whenever data is deleted.

This property is read-only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

IsAutoUpdate

Description

This property is True if this field references a field definition that is defined as an Auto-Update field in the associated record definition.

This property is read-only.

IsChanged

Description

This property returns True if the value for the field has been changed.

Note: Use this property with the primary database record only. It will not return valid results if used with a work record.

This property is read-only.

Example

```
If &CHARACTER.IsChanged Then

     Warning ("The character field has been changed");

End-If;
```

IsDateRangeEdit

Description

This property is True if this field references a field definition that is defined as requiring a Reasonable Date in the associated record definition.

This property is read-only.

IsDescKey

Description

This property is True if this field references a field definition that is defined as a descending key in the associated record definition.

This property is read-only.

IsDuplKey

Description

This property is True if this field references a field definition that is defined as a duplicate key in the associated record definition.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-only.

IsEditTable

Description

This property is True if this field references a field definition that has a table edit type of a Prompt Table with Edit.

This property is read-only.

IsEditXlat

Description

This property is True if this field references a field definition that has a table edit type of a Translate Table Edit.

This property is read-only.

IsFromSearchField

Description

This property is True if this field references a field definition that is defined as a From Search Field in the associated record definition.

This property is read-only.

IsHyperlink

Description

Use this property to set or return a Boolean value indicating wether the field is a hyperlink.

This property is read-write.

Important! Use this property within fluid applications only.

Example

```
GetLevel0()(1).QE_WORK_REC1.OPTION_CD.isHyperLink = True;
```

IsInBuf

Description

This property returns True if the data of the field is present in the data buffers. For example, all of the fields of a derived record are not present in the data buffer.

This property is read-only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

The following example iterates over all the fields in a record. The code verifies that the data for the field is accessible before it tries to assign the value to a variable.

```
For &I = 1 to &REC.FieldCount
   &FIELD = &REC.GetField(&I);
   If &FIELD.IsInBuf Then
      &VALUE = &FIELD.Value;
      /* do other processing */
   End-If;
End-For;
```

Related Links

"Record Fields and the Component Buffer" (PeopleTools 8.54: PeopleCode Developer's Guide)

IsKey

Description

This property is True if this field references a field definition that is defined as a primary key of the associated record definition.

This property is read-only.

Example

```
If &CHARACTER.IsKey Then

     Warning ("The field " | &Character.Name | " is a key");

End-If;
```

IsListItem

Description

This property is True if this field references a field definition that is defined as a List Box item of the associated record definition.

This property is read-only.

IsNotUsed

Description

This property is True if this field has been set as NotUsed with the SetDBFieldNotUsed function.

This property is read-only.

Example

```
&field = GetField(Field.RC_TEST_PB);
&ret = &field.IsNotUsed;
If (&ret = True) Then
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
   MessageBox(0, "MetaData Fn Status", 0, 0, "Field is NOTUSED");
Else
   MessageBox(0, "MetaData Fn Status", 0, 0, "Field is used.");
End-If;
```

IsRequired

Description

This property is True if this field references a field definition that is defined as Required in the associated record definition.

This property is read-only.

IsRichTextEnabled

Description

This property is True if this field is a long edit box with the rich text editor enabled.

This property is read-only.

IsSearchItem

Description

This property is True if this field references a field definition that is defined as a Search key in the associated record definition.

This property is read-only.

IsSystem

Description

This property is True if this field references a field definition that is defined as System Maintained field in the associated record definition.

This property is read-only.

IsThroughSearchField

Description

This property is True if this field references a field definition that is defined as a Through Search Field in the associated record definition.

This property is read-only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

IsUseDefaultLabel

Description

This property is True if this field references a field definition that has its label defined as Use Default Label in the associated record definition.

This property is read-only.

IsYesNo

Description

This property is True if this field references a field definition that has a table edit type of a Yes/No Table Edit.

This property is read-only.

JavaScriptEvents

Description

Use this property to set or return a String representing JavaScript code for the field.

Warning! This is a free form field and no validation is performed to check for any JavaScript errors.

This property is read-write.

Important! Use this property within fluid applications only.

Example

```
PTS_SRCH.PTS_CANCEL.JavaScriptEvents = "onclick='javascript:DoSearchCancel();' href⇒
='javascript:void(0);'";
```

Label

Description

Use this property to override the label text for the field when it’s displayed on a page.

Important! Even if the label text has been set in Application Designer, this property returns a blank string if you use the property before you’ve explicitly set it in PeopleCode. This property overrides the existing value only. When a user navigates away from the component, and then back to the page again, the original value is used until it's changed again through PeopleCode.

To set the label in PeopleCode, use this property or the SetLabel built-in function. To return the text of a label before you set it, use the GetShortLabel or GetLongLabel methods.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Note: You can't use this property to set labels longer than 100 characters. If you try to set a label of more than 100 characters, the label is truncated to 100 characters.
The “tool tip,” or mouse over text, that appears with a hyperlink at runtime comes from the RFT long label assigned to the record field. However, the RFT long label displays only if it is different from the assigned display value of the hyperlink and it is not null. If the link is an image button, the tool tip is derived from the label text if there is any. Otherwise, the RFT long label is used.

This property is read-write.

Example

The following code sample changes all the field labels for a record to the short label. It assumes that there is a label with the same name as the name of the field for all fields in the record.

```
Local Field &FLD;
Local Record &REC;

If CHECK_FIELD Then
   &REC = GetRecord();
   For &I = 1 to &REC.FieldCount
      &FLD = &REC.GetField(&I);
      &LABELID = &FLD.Name;
      &FLD.Label = &FLD.GetShortLabel(&LABELID);
   End-For;
End-If;
```

Related Links

GetShortLabel

GetLongLabel

LabelImage

Description

Use this property to override the image for a button. This property is only valid for button controls. This property can be set even when the button is disabled or display-only.

Important! Even if the image has been set in Application Designer, this property returns a blank string if you use the property before you’ve explicitly set it in PeopleCode. This property overrides the existing value only. When a user navigates away from the component, and then back to the page again, the original value is used until it's changed again through PeopleCode.

The value for this property can be either of the following:

Image.*imagename*

or

"Imagename"

Oracle strongly recommends that if the PeopleCode program sets the LabelImage for an active button, it also sets the image appropriately if the button is disabled.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

```
Local Field &MyField;

&MyField = GetField(BUTTON_BOTTOM);
&MyField.LabelImage = Image.BTN_REFRESH;
```

LongTranslateValue

Description

This property returns a string that contains the Long translate (XLAT) value of the field if the field is based on a translate table.

If the field has a null value, a null string is returned. If the field isn't based on a translate table, or the value isn't in the translate table, the field's current value is returned. Because the current value can be of any type, this property has a type of Any.

Note: If you're accessing a field based on the Translate table, the Value property returns only the one or two letter XLAT value.

Use the ShortTranslateValue property to return the short translate value of a field.

This property is read-only.

Example

```
Local Any &VALUE;
Local Field &MYFIELD;

&MYFIELD = GetField();
&VALUE = &MYFIELD.LongTranslateValue;
If ALL(&VALUE) Then
   /* do processing */
End-if;
```

Related Links

Value

ShortTranslateValue

MessageNumber

Description

This property returns the error message number (as a number) if an error for this field is found after executing ExecuteEdits method. You can use this property in conjunction with the EditError property (which can be used to determine whether there are any errors) and the MessageSetNumber property (which contains the error message set number if an error is found.)

This property is read-only.

Example

```
For &I = 1 to &RECORD.FieldCount
   &MYFIELD = &RECORD.GetField(&I);
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
   If &MYFIELD.EditError Then
      &MSGNUM = &MYFIELD.MessageNumber;
      &MSGSET = &MYFIELD.MessageSetNumber;
      /* Do processing */
   End-If;
End-For;
```

MessageSetNumber

Description

This property returns the error message set number (as a number) if an error for this field is found after executing ExecuteEdits method. You can use this property in conjunction with the EditError property (which can be used to determine whether there are any errors) and the MessageNumber property (which contains the error message number if an error is found.)

This property is read-only.

Example

```
For &I = 1 to &RECORD.FieldCount
   &MYFIELD = &RECORD.GetField(&I);
   If &MYFIELD.EditError Then
      &MSGNUM = &MYFIELD.MessageNumber;
      &MSGSET = &MYFIELD.MessageSetNumber;
      /* Do processing */
   End-If;
End-For;
```

MouseOverMsgNum

Description

Use this property to override the message number for a message catalog mouse over popup page. Together with the MouseOverMsgSet property, this property uniquely identifies a Message Catalog entry to be used as the mouse over popup page.

The Message Text field from that Message Catalog entry becomes the title of the mouse over popup page; the Explanation field becomes the body of the mouse over popup page.

Important! For this property to have an effect, the page field definition must first be set as a message catalog mouse over popup in Application Designer. This property overrides the existing message number value only. When a user navigates away from the component, and then back to the page again, the original value is used until it's changed again through PeopleCode.

This property is read-write.

Example

For example, the following code could be added to the page Activate event to override the message set and number defined in Application Designer for the popup page associated with the DEBUG_PEOPLECD.DEBUG_CODE field.

```
GetField(DEBUG_PEOPLECD.DEBUG_CODE).MouseOverMsgSet = 2;
GetField(DEBUG_PEOPLECD.DEBUG_CODE).MouseOverMsgNum = 13;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

MouseOverMsgSet

"Enabling Message Catalog Pop-up Pages" (PeopleTools 8.54: Application Designer Developer's Guide)

MouseOverMsgSet

Description

Use this property to override the message set number for a message catalog mouse over popup page. Together with the MouseOverMsgNum field property, this property uniquely identifies a Message Catalog entry to be used as the mouse over popup page.

Important! For this property to have an effect, the page field definition must first be set as a message catalog mouse over popup in Application Designer. This property overrides the existing message set value only. When a user navigates away from the component, and then back to the page again, the original value is used until it's changed again through PeopleCode.

This property is read-write.

Related Links

MouseOverMsgNum

Name

Description

This property returns the name of the field definition that the field object is based on as a string value.

This property is read-only.

Example

```
WinMessage("The character field's name is : " | &CHARACTER.Name);
```

OriginalValue

Description

This property returns the value of a field, that is, the value that from the database. If the value hasn't been changed and saved by the user, it is the original value from the database. If the value has been changed and saved by the user, it is the existing value in the database.

Note: This property does *not* work for derived records. Original values are the database values, and derived records do not have a corresponding database value.

This property is read-only.

Example

```
&Orig = &MyField.OriginalValue;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
If &Orig = &Date Then
   /* do current day processing */
Else
   /* do other processing */
End-If;
```

ParentRecord

Description

This property returns a reference to the record object for the record containing the field.

This property is read-only.

Example

```
&NUMBER_OF_FIELDS = &CHARACTER.ParentRecord.Fieldcount;

/* note that FieldCount is a property of the Record class */
```

PlaceholderText

Description

Use this property to set or return a String representing the placeholder text for the field.

This property is read-write.

Important! Use this property within fluid applications only.

Example

```
DERIVEDNUI_SRCH.NUI_SEARCH.PlaceholderText = "Search ";
```

PromptTableName

Description

This property returns the name of the prompt table (if any) associated with this field. This property returns a string value. This property returns Null if no prompt table is associated with the field.

This property is read-only.

SearchDefault

Description

If this property is set to True, system defaults (the default values set in the record field definitions) are enabled on search dialogs for the field. Setting this property to True *does not* cause the FieldDefault event to fire.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The system default is done only once, when the search dialog first starts, immediately after any SearchInit PeopleCode. If the user subsequently blanks out a field, the field isn't reset to the default value. Setting SearchDefault to False disables default processing for the field executing the property.

SearchDefault is effective only when used in SearchInit PeopleCode programs.

This property is read-write.

Example

```
&CHARACTER.SearchDefault = True;

/* assuming &CHARACTER is a search key, and has a default value */
```

This example turns on edits and system defaults for the SETID field in the search dialog box:

```
&SETID = GetField(INV_ITEMS.SETID);
&SETID.SeachDefault = True;
&SETID.SearchEdit = True;
```

SearchEdit

Description

If this property is set to True, SearchEdit enables system edits (edits specified in the record field definition) for the field, for the life of the search dialog box. Setting SearchEdit to False disables system edits. In the Add mode search dialog box, the following edits are performed when the end-user clicks the Add button. In any other mode, the following edits are performed when the end-user clicks the Search button:

- Formatting
- Required Field
- Yes/No Table
- 1/0 Table
- Translate Table
- Prompt Table

SearchEdit does not cause the FieldEdit, FieldChange, or SaveEdit PeopleCode events to fire during the search dialog.

You might use SearchEdit to control access to the system. For example, you can apply this function to the SETID field of a dialog box and require the user to enter a valid SETID before they are able to click OK on the search dialog box.

This property is read-write.

Considerations Using SearchEdit

If you use this method in the SearchInit event, the search page options are limited to the "=" and "IN" operators.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

```
&CHARCTER.SearchEdit = True;

/* assuming &CHARACTER is a search key, and contains an edit table
such as translate table defined in its field properties.  */
```

This example turns on edits and system defaults for the SETID field in the search dialog box:

```
&SETID = GetField(INV_ITEMS.SETID);
&SETID.SeachDefault = True;
&SETID.SearchEdit = True;
```

SetComponentChanged

Description

This property determines whether a change to a field (using PeopleCode) marks the component as changed and the data written to the database if the field is a database field.

This property takes a Boolean value: true, changes to the field mark the component as changed, false, the component is treated as if unchanged. The default value is true for database fields and false for derived fields.

The Set Component Changed checkbox for a page field in Application Designer determines if a user's action on a page marks the component as changed. For example, if Set Component Changedfor an edit box control is cleared in Application Designer, then user's editing on the edit box does not mark the component as changed and no save warning message is displayed if the user leaves the page without saving. The SetComponentChanged property for a field determines if a change on the field value using PeopleCode marks the component as changed and a save warning is issued when the user tries to exit the page without saving.

This property is only applicable after the Page Activate event has run. If you try to use this property before or during Page Activate, the user does not receive a warning if data has been changed.

This property is read-write.

Related Links

"Setting Use Properties" (PeopleTools 8.54: Application Designer Developer's Guide)

SetComponentChanged

ShortTranslateValue

Description

This property returns a string that contains the Short translate (XLAT) value of the field if the field is based on a translate table.

If the field has a null value, a null string is returned. If the field isn’t based on a translate table, or the value isn’t in the translate table, the field’s current value is returned. Because the current value can be of any type, this property has a type of Any.

Note: If you’re accessing a field based on the translate table, the Value property returns only the one or two letter XLAT value.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Use the LongTranslateValue property to return the long translate value of a field.

This property is read-only.

Example

```
Local Any &VALUE;
Local Field &MYFIELD;

&MYFIELD = GetField();
&VALUE = &MYFIELD.ShortTranslateValue;
If ALL(&VALUE) Then
   /* do processing */
End-if;
```

Related Links

Value

LongTranslateValue

ShowRequiredFieldCue

Description

With PeopleTools 8, an asterisk (*) is displayed on pages beside fields that are defined as Required in Application Designer. You can use this property to specify whether this asterisk, also called the *required field cue*, is displayed for a particular field.

For example, many fields are made required or non-required either procedurally or through PeopleCode. This means they aren't defined as Required in Application Designer, and the end-user may be confused. For these fields, you can use this property.

Note: This property affects only fields where a required field cue is otherwise permissible. That is, regardless of the setting of the property, no cue is ever shown on a pushbutton, a display-only field, and so on.

This property is read-write.

SmartZero

Description

Use this property to specify if FieldChange PeopleCode programs are run when a user changes a zero to a blank, or a blank to a zero, for a field on a page.

This property takes a Boolean value: true, run FieldChange PeopleCode programs, false, do not. The default value is false.

When you set this property to true, in addition to treating a user change of blank-to-zero and zero-to-blank as a field change, the application server also adjusts the DisplayZero property for the runtime field object to display a blank or zero as entered by the user.

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

DisplayZero
DisplayZeroChanged

SqlText

Description

This property is valid only for fields that have a dynamic view as their prompt record. If you set SqlText to a non-null value, that text is used instead of the dynamic view's normal text used for prompting.

Important! Even if the SQL text has been set in Application Designer, this property returns a blank string if you use the property before you've explicitly set it in PeopleCode. This property overrides the existing value only. When a user navigates away from the component, and then back to the page again, the original value is used until it's changed again through PeopleCode.

Suppose you wanted to have a different prompt table depending on the settings of other fields in the row. Normally you could use %EDITTABLE to dynamically specify the prompt table you want. However in this case there are too many possible combinations of values, which would require too many views. Furthermore, the values are customizable by the end-user or the application, which means even if you, the developer, wanted to, you couldn't provide all the combinations of views necessary. However you can generate the desired SQL text for the view in PeopleCode based on what the user enters.

If you use a dynamic view as the prompt table, and have the dynamic view contain a SQL object that is updated from PeopleCode, you could achieve this functionality. However, a SQL object is a shared object, so if multiple users used the same page, they overwrite each other's settings and the SQL object contains the SQL for the most recent user. Similarly if a single user had multiple rows on a page, the SQL object is valid only for the most recent row. This means if the user went to another row and did a prompt, they would get the wrong values again.

The purpose of this property is to enable you to specify the generated SQL text independently for each occurrence in each transaction. It enables you to override the text of a dynamic view being used as a prompt table on a field by field basis.

It is up to the developer to verify that the text specified for this property is valid, that is, that it selects the correct number of fields for the record definition, and so on.

This property is read-write.

StoredFormat

Description

This property returns the custom character format (as a string) for the field executing the property.

If the field doesn't have a custom format associated with it, the user receives a runtime error message.

If the field has a display format associated with it, you can change that using the DisplayFormat property.

This property is read-only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

```
WinMessage("The character field's custom stored format is : " | &CHARACTER.StoredFo⇒
rmat);

/* this assumes that &CHARACTER is a custom formatted */
/* field */
```

Related Links

DisplayFormat

Style

Description

If a page has a style sheet associated with it, this property can be used to specify a different style class with a field. Use this property to override the existing style class for a field.

Important! Even if the style class has been set in Application Designer, this property returns a blank string if you use the property before you've explicitly set it in PeopleCode. This property overrides the existing value only. When a user navigates away from the component, and then back to the page again, the original value is used until it's changed again through PeopleCode.

This property takes a string value.

This property is read-write.

Example: Field with PSHYPERLINK style

```
Local Field &field;

&field = GetField();

If TESTFIELD1 = 1 Then;
   &field.Style = "PSHYPERLINK";
End-If;

If TESTFIELD1 = 2 Then;
   &field.Style = "PSIMAGE";
End-If;
```

Image: Field with PSHYPERLINK style

The following example associates a test field first with a style class depending on the value of the field.

Image: Field with PSIMAGE style

Another example showing an association of a test field first with a style class depending on the value of the field

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Type

Description

This property returns the type of field. The values can be one of the following strings:

- CHAR
- DATE
- DATETIME
- IMAGE (for static images)
- IMAGEREFERENCE
- LONGCHAR
- NUMBER
- SIGNEDNUMBER
- TIME

Note: Fields of type Attachment have a type of IMAGE.

This property is read-only.

Example

```
If &CHARACTER.Type = "NUMBER" Then
   /* perform processing */
Else
   /* error processing */
End-If;
```

Value

Description

This property contains the current value of the field, converted to an appropriate PeopleCode data type.

In most contexts, the Value property can be used to assign a new value to the field. However, there are some restrictions:

- You cannot assign the Value property in any RowSelect PeopleCode program.
- You cannot assign the current record field value to the Value property in any FieldEdit PeopleCode program.

Note: If you're accessing a field based on the translate table, Value returns only the one letter XLAT value. To get the full XLAT value, use the LongTranslateValue or ShortTranslateValue properties.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Considerations Using INSTALLATION or OPTIONS Tables

When using the INSTALLATION or OPTIONS table, you cannot use the Value property. You must use the old style format, not the field object format. For example, the following code is invalid:

```
If %Page = Page.GP_RUN_TYPE And
      INSTALLATION.TL.Value = "N" Then
   &RS2.HideAllRows();
```

While the following code is valid:

```
If %Page = Page.GP_RUN_TYPE And
      INSTALLATION.TL = "N" Then
   &RS2.HideAllRows();
```

Considerations Using Character Values

Previously, if you had an edit-box field, and if the end-user selected the value in it and deleted the value, leaving the field empty, the value of the field in PeopleCode was not an empty (zero-length) string.

Now, the value of such a field *is* an empty (zero-length) string.

In addition, if the user adds one or more space characters to a field, the field still returns a Null string.

The following is how to check for this:

```
If (fieldname.Value = "") Then
```

Example

```
&CHARACTER.Value = "Hello";
```

Related Links

LongTranslateValue
ShortTranslateValue

Visible

Description

This property is True if this field is visible in the page displaying it. Setting this property to False hides the field. Because every field is implicitly associated with a rowset, row, and record, setting the Visible property for a field on the first page of a component hides only that field. If that field is repeated on other pages in the component, the other occurrences of the field aren't hidden.

This property is read-write.

Example

The following code hides the field &ROUND_OPTION based on the value of AVG_DFLT_OPTION:

```
Local field &ROUND_OPTION;

&ROUND_OPTION = GetField();

If AVG_DFLT_OPTION = "Y" Then
   &ROUND_OPTION.SetDefault();
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
   &ROUND_OPTION.Visible = True;
Else
   &ROUND_OPTION.Visible = False;
End-If;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Chapter 22

File Class

Understanding File Layout

PeopleTools supports reading and writing to plain text files, and to files that have a format based on a File Layout definition that has been created in Application Designer.

- If the file is a plain text file, data is read or written using text strings.
- If the file is based on a File Layout, you can use text strings, rowset, or record objects.

This simplifies reading, writing, and manipulating hierarchical transaction data with PeopleCode.

File layout methods and properties are noted as such in their descriptions.

Related Links

Plain Text Files
File Layout Examples
"Understanding File Layouts" (PeopleTools 8.54: Application Designer Developer's Guide)

Data Type of a File Object

The File Object is an instance of the File class. A file object is declared using the File data type. For example,

```
Local File &MYFILE;
```

This creates an object &MYFILE of the class File.

Scope of a File Object

A file object can only be instantiated from PeopleCode. This object can be used anywhere you have PeopleCode, that is, in an application class, Component Interface PeopleCode, record field PeopleCode, and so on.

A file object is passed to and returned from PeopleCode functions and methods as a reference, so the file object is never copied; rather, alternate identifiers are used to refer to the same object. Any change made to a file using one identifier has the same effect as it would with any other identifier for that file.

In the following code example, two variables, &F1 and F2, are declared by using the data type File. The file is opened using the GetFile built-in function. Next, &F1 is assigned to &F2. This does *not* copy &F1

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

to &F2. Instead, &F1 and &F2 both refer to the same object. Therefore, in the last step when &F2 is closed, &F1 is closed too.

```
Local File &F1, &F2;

&F1 = GetFile("somefile.txt", "R");
If &F1.IsOpen Then
   &F2 = &F1;
   &F2.Close();  /* Now &F1 is also closed. */
End-if;
```

Related Links

"GetFile" (PeopleTools 8.54: PeopleCode Language Reference)

"Assigning Objects" (PeopleTools 8.54: PeopleCode Developer's Guide)

File Security Considerations

When you're using file objects in PeopleCode that might run on a server, you must be aware of some security concerns. The underlying system doesn't provide security checks on access to the files. Instead, the PeopleCode programs use whatever authority the server process has, and *not* that of the user. This means you must write your PeopleCode program to prevent the user from reading or writing files that they should not. In particular, be especially wary of opening files where any part of the filename is derived from user input.

File Access Interruption Recovery

You can use the GetPosition or SetPosition methods to minimize the loss of work in the event of a system failure during file access. To use them and recover from access interruptions, you must access the file in Update mode using the GetFile built-in function or the Open method, specifying the mode parameter "U". You need to use this mode in anticipation of possible interruptions if you want to recover from them later.

To start reading or writing from the beginning of a file, use SetPosition to set a read/write position of 0, immediately after you open the file in Update mode.

Warning! In Update mode, any write operation clears the file of all data that follows the position you set.

When reading from or writing to a file, use GetPosition periodically to determine your current byte position in the file. This establishes a checkpoint to which you can return after a failure. You must save the checkpoint value in a separate file or a database so you can retrieve it later. How often you save a checkpoint depends on your requirements: the less work you want to redo, the more frequent your checkpoints should be. You may also want to save information identifying the data you're reading or writing at the time.

After a failure interrupts your file access, reopen the file in Update mode. You can then retrieve the last checkpoint value you saved, and use SetPosition to apply that value. Your read/write position in the file is the position of the last checkpoint, and you can continue reading or writing from there.

Use the Update mode with GetPosition and SetPosition only for recovering from interruptions as described here, or for starting at the beginning of the file again.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Note: For fixed-width file layouts, the field start positions and lengths are computed in 8-bit bytes, except in the case of UCS2 or UTF-16 where they are computed in 16-bit double-bytes. This may create complications when using variable width encodings (for example, UTF-8 or Shift-JIS), when the data is elsewhere calculated in characters (rather than bytes), because the data involved may contain characters of varying byte-width.

Related Links

Open
SetPosition
GetPosition
"GetFile" (PeopleTools 8.54: PeopleCode Language Reference)

Plain Text Files

To read and write from plain text files involves reading and writing strings of data. These text strings can be manipulated with built-in string functions, like RTrim, Find, Replace, and so on.

Note: If your data is hierarchical in nature, or based on existing PeopleSoft records or pages, use a File Layout definition for reading and writing your data, rather than doing it line by line (or field by field.)

The following example creates an array of array of string, then reads in two files, one into each "column" of the array. The Names file contains names; the Numbers file contains employee numbers. The ReadLine method reads each successive line in a file, until it reaches the end of the file.

Notice that the first file is opened using the GetFile function. The second file is not opened using GetFile, but rather with the Open method. After the data is read into the array, you can do processing on the data. The end of the program writes the changes back to the files, using the WriteLine method, which includes a system end of line character at the end of every line.

```
Local array of array of string &BOTH;
Local File &MYFILE;
Local string &HOLDER;

/* Create empty &BOTH array */
&BOTH = CreateArrayRept(CreateArrayRept("", 0), 0);

/* Read first file into first column */

&MYFILE = GetFile("names.txt", "R");
While &MYFILE.ReadLine(&HOLDER);
   &BOTH.Push(&HOLDER);
End-While;

/* read second file into second column */

&MYFILE.Open("numbers.txt", "R");
&LINENO = 1;
While &MYFILE.ReadLine(&HOLDER);
   If &LINENO > &BOTH.Len Then
      /* more number lines than names, use a null name */
      &BOTH.Push(CreateArray("", &HOLDER));
   Else
      &BOTH[&LINENO].Push(&HOLDER);
   End-If;
   &LINENO = &LINENO + 1;
End-While;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
/* if more names than numbers, add null numbers */
For &LINENO = &LINENO to &BOTH.Len
      &BOTH[&LINENO].Push("");
End-For;
&MYFILE.Close();
/* do processing with array */
/* write data back to files */

&MYFILE1 = GetFile("names.txt", "A");
&MYFILE2 = GetFile("numbers.txt", "A");

/* loop through array and write to files */

For &I = 1 To &BOTH.Len
   &STRING1 = &BOTH[&I][1];
   &MYFILE1.writeline(&STRING1);
   &STRING2 = &BOTH[&I][2];
   &MYFILE2.writeline(&STRING2);
End-For;

&MYFILE1.Close();
&MYFILE2.Close();
```

Related Links

File Layout Examples

Automatic PeopleCode Generation

After you create a File Layout definition, you can use PeopleCode to access it. This PeopleCode can be long and complex. Rather than write it directly, you can drag and drop the File Layout definition from Application Designer Project View into an open PeopleCode edit pane. This is primarily used for importing data. Application Designer analyzes the definition and generates initial PeopleCode as a template, which you can modify to meet your requirements.

The following is just a snippet of the code that is generated:

```
Function EditRecord(&REC As Record) Returns boolean ;
   Local integer &E;
REM   &REC.ExecuteEdits(%Edit_Required + %Edit_DateRange + %Edit_YesNo + %Edit_Tran⇒
slateTable + %Edit_PromptTable + %Edit_OneZero);
   &REC.ExecuteEdits(%Edit_Required + %Edit_DateRange + %Edit_YesNo + %Edit_OneZero⇒
);
   If &REC.IsEditError Then
      For &E = 1 To &REC.FieldCount
         &MYFIELD = &REC.GetField(&E);
         If &MYFIELD.EditError Then
            &MSGNUM = &MYFIELD.MessageNumber;
            &MSGSET = &MYFIELD.MessageSetNumber;
            &LOGFILE.WriteLine("****Record:" | &REC.Name | ", Field:" | &MYFIELD.Na⇒
me );
            &LOGFILE.WriteLine("****" | MsgGet(&MSGSET, &MSGNUM, ""));
         End-If;
      End-For;
      Return False;
   Else
      Return True;
   End-If;
End-Function;
.
.
.
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

"Understanding File Layouts" (PeopleTools 8.54: Application Designer Developer's Guide)

End Of Line Considerations

The file format of the input file should be appropriate to the operating system of the process reading the file (Windows format on Windows systems, UNIX format on UNIX systems).

Input files for file layouts of type fixed or CSV must not contain embedded CR/LF within the field data. However, input files for file layouts of type XML can contain embedded CR/LF within field data for a character type file field that is the associated with a long-character type database field that has unlimited length—that is, the maximum length specified as 0.

File Layout Error Processing

If an error occurs on any field in any record of a rowset object populated with the ReadRowset method, the rowset object's property IsEditError returns True. For example, you can use the method ExecuteEdits on a record, to verify that the data in the record is valid (has the correct format, the right data type, and so on.) This type of error is indicated by the IsEditError.

In some instances, however, the rowset object won't receive the error; in that case the file object's IsError property returns True. To discover all field errors, check both properties after executing ReadRowset.

To determine which field has the error, you must examine the EditError property of every field in the rowset to find the one returning True. You can then examine that field's MessageSetNumber and MessageNumber properties to determine the relevant error message. The following example shows how this might be done:

```
&MYFILE.Open(&SOMENAME, "R");
&MYFILE.SetFileLayout(FILELAYOUT.SOMELAYOUT);
&MYROWSET = &MYFILE.ReadRowset();
If &MYFILE.IsError Then
  For &I = 1 to &MYROWSET.ActiveRowCount
    If &MYROWSET.GetRow(&I).IsEditError Then
      &ROW = &MYROWSET.GetRow(&I);
      For &J = 1 to &ROW.RecordCount
        If &ROW.GetRecord(&J).IsEditError Then
          &REC = &ROW.GetRecord(&J);
          For &K = 1 to &REC.FieldCount
            If &REC.GetField(&K).EditError Then
              /* Examine the field&rsquo;s
                 MessageSetNumber and MessageNumber properties,
                 and respond accordingly */
         End-If;
          End-For;
      End-If;
      End-For;
    End-If;
  End-For;
End-If;

&MYFILE.Close();
```

Note: Only field errors set the IsError, IsEditError, or EditError properties. All other errors triggered by File class methods terminate the PeopleCode program.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

IsError
ReadRowset
IgnoreInvalidId
IsEditError
ExecuteEdits
ExecuteEdits
MessageNumber
MessageSetNumber

Working With Relative Paths

Relative paths apply to the following PeopleCode operations: the Open method of the File class and the CreateDirectory, FileExists, FindFiles, GetFile, GetTempFile, and RemoveDirectory built-in functions

If you specify a relative path, that path is appended to the path constructed from a system-chosen environment variable. Environment variables are checked in a particular order to find one that is set. This means if the first environment variable in order is found to be set, that's the one that is used. If the environment variable isn't found to be set, the next one is checked, and if found, is used, and so on.

If the PeopleCode operation is called from a program running in an environment started through psadmin (for example, within an application server domain), the PeopleCode operation checks in the following order to determine whether an environment variable is set:

1. *PS_FILEDIR*
2. *PS_SERVDIR*

If the PeopleCode operation is called from an environment *not* started through psadmin (for example, a stand-alone call to Application Engine), the PeopleCode operation checks in the following order to determine whether an environment variable is set:

1. *PS_FILEDIR*
2. *PS_SERVDIR*
3. *TEMP*

In both cases, the PeopleCode operation then uses the value of the first environment variable that is found to be set and appends the specified relative path to it in order to determine the resulting full path that will be used to locate the file. The resulting path is shown in the following table:

Environment Variable	***Resulting Path***
PS_FILEDIR	*PS_FILEDIR\relative_path*
PS_SERVDIR	*PS_SERVDIR***files***\relative_path*
TEMP	*TEMP\relative_path*

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

If the PeopleCode operation is not successful at the specified location, it will return Null or False (as appropriate for the invoking operation) and it will *not* attempt to use the value of one of the other environment variables.

Note: In the preceding examples, the Windows directory separator, a backslash, was used. For UNIX directories, the directory separator is a forward slash.

Note: The PS_FILEDIR environment variable is *not* initialized and set to a path automatically. If you want to use this environment variable, you must set it yourself.

Note: Your system security should verify if a user has the correct permissions before allowing access to a drive. (For example, if a user changes their TEMP environment variable to a network drive they don't normally have access to, your system security should detect this.)

File Class Built-in Functions

"CreateDirectory" (PeopleTools 8.54: PeopleCode Language Reference)

"FileExists" (PeopleTools 8.54: PeopleCode Language Reference)

"FindFiles" (PeopleTools 8.54: PeopleCode Language Reference)

"GetFile" (PeopleTools 8.54: PeopleCode Language Reference)

"GetTempFile" (PeopleTools 8.54: PeopleCode Language Reference)

"RemoveDirectory" (PeopleTools 8.54: PeopleCode Language Reference)

File Class Methods

In this section, we discuss the File class methods. The methods are discussed in alphabetical order.

Close

Syntax

```
Close()
```

Description

The Close method discards any changes that haven't been written to the external file, disassociates the file object from the external file, releases all resources connected with the file object, and causes the file object to go out of scope.

You cannot use any methods or properties on the object after it is closed. You must get another file object (using the GetFile function) and instantiate another file object after you use Close.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

None.

Returns

None.

Example

```
&MYFILE.Open("somefile.txt", "W", %FilePath_Relative);
&MYFILE.WriteLine("Some text.");
&MYFILE.Close();
```

Related Links

Open

IsOpen

"GetFile" (PeopleTools 8.54: PeopleCode Language Reference)

CreateRowset

Syntax

```
CreateRowset()
```

Description

The CreateRowset method is a file layout method. It instantiates a PeopleCode rowset object containing one unpopulated row, based on the file layout definition specified with SetFileLayout.

Note: You must specify a file layout using the SetFileLayout method before using CreateRowset, otherwise it returns NULL.

See SetFileLayout.

After the empty rowset object has been created, you can use Rowset class methods such as Select or Fill, and built-in functions such as GetLevel0 or GetRowset, to populate the rowset with data. After the rowset contains data, you can use the method WriteRowset to write the data to a file.

Don’t use CreateRowset when reading from a file. Instead, use the ReadRowset method to instantiate and populate rowsets with data from the file.

Parameters

None.

Returns

An empty rowset object.

Example

```
&SOMEROWSET = &MYFILE.CreateRowset();
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The following rowset is created from a file object, then populated with data using the GetLevel0 function:

```
&FILEROWSET = &MYFILE.CreateRowset();
&FILEROWSET = GetLevel0();
&MYFILE.WriteRowset(&FILEROWSET, True);
```

The following rowset is created from a file object, then populated with data using Fill method:

```
&FILEROWSET = &MYFILE.CreateRowset();
&NUM_READ = &FILEROWSET.Fill("where MYRECORD = :1", &UVAL);
```

Related Links

ReadRowset
SetFileLayout
WriteRowset
Understanding Rowset Class

Delete

Syntax

Delete()

Description

Use the Delete method to delete an open file. You cannot delete a closed file.

Parameters

None.

Returns

None.

Example

```
/* Open a temporary file. Use the "N" parameter to ensure
the file is new. */

&MyFile = GetFile("temp.txt", "N");

/* verify the file was instantiated successfully */

/* do processing using the temporary file */

/* delete the temporary file */

&MyFile.Delete();
```

Related Links

Open
Close
"GetFile" (PeopleTools 8.54: PeopleCode Language Reference)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GetBase64StringFromBinary

Syntax

GetBase64StringFromBinary()

Description

Use this method to read the complete contents of the binary file associated with the current File object, encode the data using Base64, and return the result as a Base64-encoded string.

Parameters

None.

Returns

A string containing the contents of the binary file encoded in Base64.

Example

```
Local File &F1;
Local string &base64string;

&F1 = GetFile("D:\image.jpg", "R", %FilePath_Absolute);
If &F1.IsOpen Then
   &base64string = &F1.GetBase64StringFromBinary();
   &F1.Close();
End-If;
```

Related Links

WriteBase64StringToBinary

GetPosition

Syntax

GetPosition()

Description

The GetPosition method returns the current read or write position in the external file. GetPosition works only with a file that was opened in Update mode. This method is designed to be used in combination with the SetPosition method to establish checkpoints for restarting during file access.

Note: Currently, the effect of the Update mode and the GetPosition and SetPosition methods is not well defined for Unicode files. Use the Update mode only on files stored with a non-Unicode character set.

Parameters

None.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

A number representing the current read or write position in the file.

Note: When you use ReadRowset to read from a file in Update mode, the CurrentRecord property returns, the entire record just read. The current read/write position is at the *end* of the CurrentRecord, that is, just past the end of the rowset.

Example

The following example opens a file in Update mode, and saves the current position after each read operation:

```
&MYFILE.Open(&SOMENAME, "U");
If &MYFILE.IsOpen Then
   while &MYFILE.ReadLine(&SOMESTRING)
      &CURPOS = &MYFILE.GetPosition();
      /* Save the value of &CURPOS after each read,
         and process the contents of each &SOMESTRING */
   End-While;
End-If;
&MYFILE.Close();
```

Related Links

Open

SetPosition

File Access Interruption Recovery

"GetFile" (PeopleTools 8.54: PeopleCode Language Reference)

GetString

Syntax

GetString([*Strip_Line_Terminator*])

Description

Use the GetString method to return the entire file as a single string.

Note: After this method completes successfully, the original file is deleted.

You can specify whether the resulting string is to include the line terminator characters or not by using the *Strip_Line_Terminator* parameter. The default value for this parameter is false, which means the resulting string includes the line terminator characters at the end of each line.

For example on a Unix system, with a line terminator of a LF, the resulting string includes not only the data for each line, but the LF character as well.

Parameters

Strip_Line_Terminator	Specify whether the line terminators are to be stripped or not.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

A single string containing the entire contents of the file.

Example

The following example creates a file on a Windows system, then retrieves it as a single line of text.

Note: The file is destroyed on successful completion of this method.

```
Local File &File = GetFile("c:\temp\junk\something.txt", "W", %FilePath_Absolute)
/* write a bunch of > 2048 length lines */

Local string &piece, &input;
Local integer &I;

&piece = "123456789-";
While Len(&piece) < 2048
   &piece = &piece | &piece;
End-While;

&File.WriteString(&piece);
&File.WriteString(&piece);
&File.WriteString(&piece);
&input = &File.GetString( True);
&File.Close();
Local string &pieces = &piece | &piece | &piece;

/* Note that the result of this message should indicate &pieces is the same as &inp⇒
ut */
MessageBox(0, "", 0, 0, "&piece = &input: Len(&pieces)=" | Len(&pieces) | " Len(&in⇒
put)=" | Len(&input) | " Same? " | (&pieces = &input));
```

Related Links

ReadLine

WriteLine

WriteRaw

Open

Syntax

Open(*filespec*, *mode* [, *charset*] [, *pathtype*])

Description

The Open method associates the file object with an external file for input or output.

If the File object is currently associated with a file, that file is closed first. In addition, any file opened for writing (by a call to the GetFile function or the Open method) by a PeopleCode program that runs in the Process Scheduler is automatically managed by the Report Repository.

You can use the GetFile or GetTempFile functions to access an external file, but each execution of GetFile or GetTempFile instantiates a new file object. If you plan to access only one file at a time, you need only one file object. Use GetFile or GetTempFile to instantiate a file object for the first external file you access. Then, use Open to associate the same file object with as many different external files as you want.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

However, if you expect to have multiple files open at the same time, you need to instantiate multiple file objects with GetFile or GetTempFile.

GetFile and Open both perform implicit commits. Therefore, the GetTempFile function has been introduced specifically to avoid these implicit database commits. GetTempFile differs from GetFile in two respects:

- GetTempFile does not perform an implicit commit.
- GetTempFile does not make the associated file available through the Report Repository even when the calling PeopleCode program is run through the Process Scheduler.

Therefore, GetTempFile can be a good choice when you wish to avoid implicit database commits and when you do not need to have the file managed through the Report Repository. Otherwise, GetTempFile operates exactly the same as GetFile.

Parameters

filespec

Specify the name, and optionally, the path, of the file you want to open.

mode

A string indicating the manner in which you want to access the file. The mode can be one of the following:

- "R" (Read mode): opens the file for reading, starting at the beginning.
- "W" (Write mode): opens the file for writing.

  Warning! When you specify Write mode, any existing content in the file is discarded.

- "A" (Append mode): opens the file for writing, starting at the end. Any existing content is retained.
- "U" (Update mode): opens the file for reading or writing, starting at the beginning of the file. Any existing content is retained. Use this mode and the GetPosition and SetPosition methods to maintain checkpoints of the current read/write position in the file.

  In Update mode, any write operation clears the file of all data that follows the position you set.

  Note: Currently, the effect of the Update mode and the GetPosition and SetPosition methods is not well defined for Unicode files. Use the Update mode only on files stored with a non-Unicode character set.

- "E" (Conditional "exist" read mode): opens the file for reading only if it exists, starting at the beginning. If it doesn’t exist, the Open method has no effect. Before attempting to read from the file, use the IsOpen property to confirm that it’s open.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- "N" (Conditional "new" write mode): opens the file for writing, only if it doesn't already exist. If a file by the same name already exists, the Open method has no effect. Before attempting to write to the file, use the IsOpen property to confirm that it's open. You can insert an asterisk (*) in the file name to ensure that a new file is created. The system replaces the asterisk with numbers starting at 1 and incrementing by 1, and checks for the existence of a file by each resulting name in turn. It uses the first name for which a file *doesn't* exist. In this way you can generate a set of automatically numbered files. If you insert more than one asterisk, all but the first one are discarded.

charset

A string indicating the character set you expect when you read the file, or the character set you want to use when you write to the file. You can abbreviate Unicode UCS-2 to "U" and the host operating system's default non-Unicode (sometimes referred to as the ANSI character set) to "A". All other character sets must be spelled out in full, for example, ASCII, Big5, Shift-JIS, UTF8, or UTF8BOM.

If "A" is specified as the character set, or you do not specify a character set, the character set used is dependent on the application server configuration. On a Windows application server, the default non-Unicode character set is dependent on the Windows ANSI Codepage (ACP) which can be checked using the DOS command chcp. On a Unix application server, the default non-Unicode character set is specified in the application server configuration file, psappsrv.cfg, and can be modified using PSADMIN. You can also use a record field value to specify the character set (for example, RECORD.CHARSET.)

A list of supported character set names valid for this argument can be found in *PeopleTools: Global Technology*.

See "Character Sets Across the Tiers of the PeopleSoft Architecture" (PeopleTools 8.54: Global Technology).

Note: If you attempt to read data from a file using a different character set than was used to write that data to the file, the methods used generate a runtime error or the data returned is unusable.

When a file is opened for reading using the "U" *charset* argument, GetFile expects the file to begin with a Unicode byte order mark (BOM). This mark indicates whether the file is written in big endian order or little endian order. A BOM consisting of the hex value 0xFEFF indicates a big endian file, a BOM consisting of the hex value 0xFFEF indicates a little endian file. If the Unicode UCS-2 file being opened does not start with a BOM, an error is returned. The BOM is automatically stripped from the file when it is read into the buffers by GetFile.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

When a file is opened for writing using the “U” *charset* argument, the appropriate Unicode BOM is automatically written to the start of the file depending on whether the application server hardware platform operates in little endian or big endian mode.

BOMs are only expected or supported for files in Unicode character sets such as UTF8, UTF8BOM, and UCS2. For consuming applications that do expect the BOM for UTF-8 files, the UTF8BOM character set is to create UTF-8 files with the BOM.

Note: For example, the UTF-8 BOM is represented by the sequence 0xEF BB BF. This sequence can be misinterpreted by a non-Unicode character set such as ISO-8859-1 and appears as ISO characters ï»¿.

When working with XML documents, specify UTF8 or UTF8BOM for *charset*. If you are writing an XML file using a different character set, you must remember to include a character set declaration in the XML file.

In some cases, a Unicode file (UCS-2 or UTF-8) cannot be opened. An error message is displayed, when one of the following error conditions is encountered:

- If the character set is U (that is, UCS2) and the mode is:
  - A: The file is empty or the BOM is missing or incorrect.
  - R: The BOM is missing or incorrect.
  - W: The file does not exist, or adding the BOM failed.
- If the character set is UTF8 or UTF8BOM and the mode is:
  - R: For UTF8BOM, the BOM is missing or the file is empty; for UTF8, the file is empty.
  - A or W: For UTF8BOM only, the file does not exist or adding the BOM failed.

pathtype

If you have prepended a path to the file name, use this parameter to specify whether the path is an absolute or relative path. The valid values for this parameter are:

- %FilePath_Relative (default)
- %FilePath_Absolute

If you don’t specify *pathtype* the default is %FilePath_Relative.

If you specify a relative path, that path is appended to the path constructed from a system-chosen environment variable. A

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

complete discussion of relative paths and environment variables is provided in documentation on the File class.

See Working With Relative Paths.

If the path is an absolute path, whatever path you specify is used verbatim. You must specify a drive letter and the complete path. You can't use any wildcards when specifying a path.

The Component Processor automatically converts platform-specific separator characters to the appropriate form for where your PeopleCode program is executing. On a Windows system, UNIX "/" separators are converted to "\", and on a UNIX system, Windows "\" separators are converted to "/".

Note: The syntax of the file path does *not* depend on the file system of the platform where the file is actually stored; it depends only on the platform where your PeopleCode is executing.

Returns

None.

Example

The following example opens an existing UCS-2 file for reading:

```
&MYFILE.Open(&SOMENAME, "E", "U");
If &MYFILE.IsOpen Then
   while &MYFILE.ReadLine(&SOMESTRING)
      /* Process the contents of each &SOMESTRING */
   End-While;
   &MYFILE.Close();
End-If;
```

The following example opens a numbered file for writing in ANSI format, without overwriting any existing files:

```
&MYFILE.Open("C:\temp\item*.txt", "N", %FilePath_Absolute);
If &MYFILE.IsOpen Then
   &MYFILE.WriteLine("Some text.");
   &MYFILE.Close();
End-If;
```

Related Links

IsOpen

SetPosition

GetPosition

Close

File Access Interruption Recovery

"GetFile" (PeopleTools 8.54: PeopleCode Language Reference)

"GetTempFile" (PeopleTools 8.54: PeopleCode Language Reference)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ReadLine

Syntax

ReadLine(*string*)

Description

The ReadLine method reads one line of text from the external file. The line includes the newline character, but ReadLine strips out the newline character and inserts the result into the string variable *string*.

When ReadLine is executed, it moves the starting point for the next read operation to the end of the text just retrieved, so each line in the file can be read in turn by subsequent ReadLine operations. When no more data remains to be read from the file, ReadLine returns False, and clears the string variable of any content.

When the file object has been instantiated using a Unicode character set (UTF8, UTF8BOM, or UCS2) and the file has a Unicode byte order mark (BOM), the BOM is recognized as file metadata and is not treated as text. However, when the file has been instantiated using a non-Unicode character set and the file has a Unicode BOM, this is likely a user error; the BOM *is* treated as text and is *not* recognized as file metadata.

Parameters

string	A string variable that receives the input text.

Returns

A Boolean value: True if the method succeeds, False otherwise. The return value is *not* optional, it is required.

Example

The following example reads a file called &MYFILE and puts each line as a separate element in an array.

```
Local File &MYFILE;
Local array of string &MYARRAY;
Local string &TEXT;

&MYFILE = GetFile("names.txt", "R", "UTF8BOM");
&MYARRAY = CreateArrayRept("", 0);
While &MYFILE.ReadLine(&TEXT);
   &MYARRAY.Push(&TEXT);
End-While;
&MYFILE.Close();
```

Related Links

GetString

ReadRowset

WriteString

WriteLine

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ReadRowset

Syntax

ReadRowset()

Description

The ReadRowset method is a file layout method. It instantiates a PeopleCode rowset object based on the file layout definition, then populates the rowset with one transaction from the file. A transaction is considered to be one instance of level zero data contained in a file record, plus all of its subordinate data. If you put more than one segment at level zero, each segment is read in sequence.

Note: You must specify a file layout using the SetFileLayout method before using ReadRowset, otherwise it will return NULL.

When ReadRowset is executed, it moves the starting point for the next read operation to the beginning of the next rowset, so each transaction in the file can be read in turn by subsequent ReadRowset operations. When no more data remains to be read from the file, ReadRowset returns NULL.

If you're using the SetFileId method with ReadRowset to process an input file based on multiple file layouts, ReadRowset returns NULL when it reads a FileId file record (line) between the rowsets.

When ReadRowset returns NULL, you can use the IsFileId property to determine if you've reached the end of the file or a FileId record.

Note: When using ReadRowset, if a value in the file exceeds the defined length in the file layout, it is ignored. The given record field is flagged with an edit error which can be programmatically checked.

If the ReadRowset encounters a line in the file containing the FileId, and the lines following this are *not* a new rowset, the process considers it to be an invalid FileId. You can specify whether to ignore the invalid record or terminate the PeopleCode with the IgnoreInvalidId property.

Note: If you're using the SetFileId method with ReadRowset to process an input file based on multiple layouts, FileId file records between the rowsets are considered to be valid file records, and won't generate any errors, regardless of the state of the IgnoreInvalidId property.

See SetFileLayout.

Considerations for Using Dates With ReadRowset

Single digits in dates in the form MMDDYY or MMDDYYYY must be padded with zeros. That is, if the date in your data is February 3, 2000, the form must be:

```
02/03/2000
```

or

```
02/03/00
```

The following is *not* valid.

```
2/3/00
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Considerations for Using XML With ReadRowset

If all of the fields in the file layout are not present in the XML, no data is written to the database. If there are additional tags in the XML, they are ignored.

Considerations for Using Nested Data with ReadRowset

If you are processing input files with a large amount of nested data, your application server may run out of memory before the system finishes processing all of the data.

This may happen because of the differences between processing a single-level rowset and a multi-level rowset. If you are reading the rows of a single-level (level 0) rowset from a file, the file is processed one row at a time, that is, only one row resides in memory at a time.

However, if you are reading the rows of a multi-level (parent-child) rowset from a file, then for each level 0 row, *all* of the associated child rows (and all of their associated child rows) simultaneously reside in memory. As a result, during the processing a large input data file that is associated with a multi-level rowset (through a multi-level file layout definition), your application server may run out of memory.

To work around this, consider doing one of the following:

- Retain your original file layout definition and split the original input file into smaller (but structurally unchanged) pieces
- Flatten out your original file layout definition (that is, split it up into several single-level definitions) as well as split the original input file into several single-level pieces.

Considerations for Using Default Values with ReadRowset

The system variables related to date and time (for example, %Date, %Time, and %DateTime) cannot be used to specify the value of the Default Value property of a file layout field. This topic is covered in detail in the Application Designer PeopleBook.

See "Specifying File Field Properties" (PeopleTools 8.54: Application Designer Developer's Guide)

Parameters

None.

Returns

A populated rowset.

Example

The following example reads and processes an entire file. The data in the file is based on a single File layout definition:

```
&MYFILE.GetFile(&SOMENAME, "R");
If &MYFILE.SetFileLayout(FILELAYOUT.SOMELAYOUT) then
   &SOMEROWSET = &MYFILE.ReadRowset();
   While &SOMEROWSET <> NULL
      /* Process the contents of each &SOMEROWSET */
      &SOMEROWSET = &MYFILE.ReadRowset();
   End-While;
End-If;
&MYFILE.Close();
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

CurrentRecord
IgnoreInvalidId
GetString
ReadLine
SetFileLayout
WriteRecord
WriteRowset
Multiple File Layouts
ReadRowset Example
IsEditError

SetFileId

Syntax

SetFileId(*fileid, position*)

Description

The SetFileId method is a file layout method. If your input file contains data based on more than one File Layout definition, you must use this method in combination with the CurrentRecord and IsNewFileId properties and the ReadRowset method to process the file correctly.

Note: SetFileId, CurrentRecord and IsNewFileId don't apply to CSV and XML format input files. You can use only fixed format files to implement multiple file layouts.

See CurrentRecord, IsNewFileId, ReadRowset.

At each point in the input file where the structure of the rowset changes, there must be an extra line in the file containing the file record (line), the FileId file record (line), that signifies that the change. Each FileId file record must have the following components:

- A value that designates it as a Fileid. Only one FileId value is necessary throughout the file, such as "999".
- A name field that identifies the file layout needed for the rowset that follows. This field could contain the name of the file layout as it's defined in Application Designer.

These lines containing the FileId are *not* part of any rowset. They can contain other information, which will be disregarded by the system. The FileId identifier and the file layout names aren't automatically stored anywhere; they exist only in the input file's FileId file records and in the PeopleCode.

To process an input file that requires multiple file layouts:

1. Use SetFileLayout to specify the file layout definition to use.

   If you're specifying the initial file layout for this file, it doesn't have to be the correct one. You can determine the correct file layout to use for the first rowset during a subsequent step.

2. Use SetFileId to specify the value of the FileId field, *fileid*, that's used throughout the file to designate FileId file records.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Note: After each execution of SetFileLayout, the SetFileId setting is disabled. Be sure to re-specify the FileId value if you expect the file layout to change, so the system continues looking for the next FileId file record.

3. Use ReadRowset to read the next rowset from the file.

   The current file record is also stored in the CurrentRecord property as a string. The PeopleCode process determines whether it's the beginning of a new rowset, or a FileId file record according to the *fileid* you specified. If it's a FileId file record, the process sets the IsNewFileId property to True; if not, it sets the IsNewFileId property to False.

   Note: If this is the first execution of ReadRowset on the file, it returns NULL upon encountering the initial FileId file record, but still stores that file record in CurrentRecord and sets IsNewFileId accordingly.

4. If the rowset returned isn't NULL, process that rowset as necessary.

5. If IsNewFileId is False, go back to step 3 to continue reading rowsets from the file. If IsNewFileId is True, examine CurrentRecord to determine which new file layout to use, and go back to step 1.

You can repeat this procedure one rowset at a time, proceeding through the remainder of the input file. When ReadRowset returns NULL, no more rowset data is available.

Parameters

fileid	Specify the value of the FileId field used in the current file.
position	Specify the column in the FileId file record where the FileId field starts. The default is 1.

Returns

None.

Example

```
&rsFile = &MYFILE.ReadRowset();
&CurrentRecord = &MYFILE.CurrentRecord;
&IsNewFileID = &MYFILE.IsNewFileId;
If &MYFILE.IsNewFileId Then
   &FILELAYOUT = FindFileID(&CurrentRecord);
   &MYFILE.SetFileLayout(@("FileLayout." | &FILELAYOUT));
   &MYFILE.SetFileId("999", 1);
End-If;
```

Related Links

CurrentRecord

IsNewFileId

ReadRowset

SetFileLayout

File Layout Examples

"Understanding File Layouts" (PeopleTools 8.54: Application Designer Developer's Guide)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SetFileLayout

Syntax

SetFileLayout(FILELAYOUT.*filelayoutname*)

Description

The SetFileLayout method is a file layout method. It associates a specific file layout definition with the file object executing this method, providing easy access to rowset data. The file object must be associated with an open file. With file layout definitions, you can read and write rowsets as easily as strings. If the file object isn't open or the definition doesn't exist, SetFileLayout fails.

You must execute SetFileLayout before you can use any other file layout methods or properties with a file object, otherwise those methods and properties return NULL or False.

Note: All provided PeopleTools records that have a prefix of PSFLD are related to file layout definitions.

Parameters

filelayoutname Specify as a string the name of an existing file layout definition created in Application Designer.

Returns

A Boolean value: True if the method succeeds, False otherwise.

Example

The following example opens a data file, associates a file layout definition with it, reads and processes the first rowset from it, and closes the file.

```
&MYFILE.Open(&SOMENAME, "E");
If &MYFILE.SetFileLayout(FILELAYOUT.SOMELAYOUT) then
   &SOMEROWSET = &MYFILE.ReadRowset();
   /* Process the contents of &SOMEROWSET */
Else
   /* Error - SetFileLayout failed */
End-If;
&MYFILE.Close();
```

Related Links

CurrentRecord

CreateRowset

ReadRowset

IgnoreInvalidId

WriteRowset

File Layout Examples

"Understanding File Layouts" (PeopleTools 8.54: Application Designer Developer's Guide)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SetPosition

Syntax

SetPosition(*position*)

Description

The SetPosition method sets the current read or write position in the external file associated with the file object executing this method. SetPosition works only with a file, which is opened in Update mode, and is designed to be used in combination with the GetPosition method to recover from interruptions during file access.

To start reading or writing from the beginning of a file, you must use SetPosition to set a read/write position of 0, immediately after you open the file in Update mode.

Parameters

position	The byte position in the file at which you want to continue reading or writing. This should either be 0 or a value you previously obtained with the GetPosition method and saved in a separate file or a database.

Warning! In Update mode, any write operation clears the file of all data that follows the position you set.

Note: Use SetPosition only for recovering from file access interruptions. Supplying your own value for SetPosition isn't recommended, except for position 0.

Returns

None.

Example

The following example reopens a file in Update mode, and sets the read position to the last saved checkpoint:

```
&MYFILE = GetFile(&SOMENAME, "U");
If &MYFILE.IsOpen Then
   /* Retrieve the value of the last saved checkpoint, &LASTPOS */
   &MYFILE.SetPosition(&LASTPOS);
   while &MYFILE.ReadLine(&SOMESTRING)
      /* Process the contents of each &SOMESTRING */
   End-While;
   &MYFILE.Close();
End-If;
```

Note: Currently, the effect of the Update mode and the GetPosition and SetPosition methods is not well defined for Unicode files. Use the Update mode only on files stored with a non-Unicode character set.

Related Links

GetPosition

Open

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

File Access Interruption Recovery
"GetFile" (PeopleTools 8.54: PeopleCode Language Reference)

SetRecTerminator

Syntax

SetRecTerminator(*Terminator*)

Description

The SetRecTerminator method is a file layout method.

Use this method to specify the string of characters that indicate the end of a file record. Read operations use the value of SetRecTerminator to determine where each file record ends and the next one starts, and write operations append the value of SetRecTerminator to each record written.

This value defaults to the newline character appropriate to the platform where the file is being stored:

- a linefeed on UNIX systems
- a carriage return/linefeed combination on Windows systems

You need to specify a different record terminators only if you anticipate that part of the data in a file field that includes the newline character used on the storage platform; you must assign the record terminator a unique string that you know does not appear in a file field.

If you set the record terminator to Null ("") you eliminate linefeeds or carriage returns.

Parameters

Terminator Specify the value you want used for the record terminator.

Returns

None.

Example

```
&File = GetFile(......);

if &File.IsOpen then
   /* set the terminator to be NULL */
   Local String &Term = "";
   &File.SetRecTerminator(&Term);
```

WriteBase64StringToBinary

Syntax

WriteBase64StringToBinary(*encoded_string*)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use this method to decode the input string using Base64 and write the resulting bytes to the output file associated with the current File object.

Parameters

encoded_string	Specifies a Base64-encoded string.

Returns

None.

Example

```
Local File &F1;
Local string &base64string;

/* Load the Base64 string data into &base64string */
&base64string = "...";

&F1 = GetFile("D:\anImage.jpg", "W", %FilePath_Absolute);
If &F1.IsOpen Then
   &F1.WriteBase64StringToBinary(&base64string);
   &F1.Close();
End-If;
```

Related Links

GetBase64StringFromBinary

WriteLine

Syntax

WriteLine(*string*)

Description

The WriteLine method writes one string of text, *string*, to the output file associated with the file object executing this method, followed by a newline character appropriate to the platform where the file is being written. To build a single line using multiple strings, use the WriteString method.

When the file object has been instantiated using a Unicode character set (UTF8, UTF8BOM, or UCS2) and the file has a Unicode byte order mark (BOM), the BOM is recognized as file metadata and is not treated as text. However, when the file has been instantiated using a non-Unicode character set and the file has a Unicode BOM, this is likely a user error; the BOM *is* treated as text and is *not* recognized as file metadata.

For writing UTF-8 files, use the UTF8BOM character set when instantiating the file object to include the Unicode BOM in output. Alternatively, use the UTF8 character set when instantiating the file object to exclude the BOM in output. Specify the character set depending on what the consuming application expects. When in doubt, use UTF8BOM to include the BOM. If the consuming application is the File class ReadLine method, either option will work. For clarity, always specify the *charset* parameter for calls to GetFile, GetTempFile, or Open, and match up *charset* with the character set used for writing and reading the file's content.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

string	The string of text to be written.

Returns

None.

Example

The following example adds a line of text to an existing file:

```
&MYFILE.Open("somefile.txt", "A", "UTF8BOM");
&MYFILE.WriteLine("This is the last line in the file.");
&MYFILE.Close();
```

The following example converts a file where the fields are separated with tabs into a file where the fields are separated with commas.

```
Local File &TABFILE, &CSVFILE;
Local string &FILE_NAME, &DATA, &NEWDATA;

&FILE_NAME = "Test.txt";
&TAB = Char(9);

&TABFILE = GetFile(&FILE_NAME, R", "UTF8BOM");
&FileName = &TABFILE.Name;
&POS = Find(".", &FileName);
&NEWFILE_NAME = Substring(&FileName, 1, &POS) | "dat";
&CSVFILE = GetFile(&NEWFILE_NAME, "N", %FilePath_Absolute);
If &TABFILE.IsOpen And
      &CSVFILE.IsOpen Then
   While &TABFILE.ReadLine(&DATA);
      &NEWDATA = Substitute(&DATA, &TAB, ",");
      &CSVFILE.WriteLine(&NEWDATA);
   End-While;
   &TABFILE.Close();
   &CSVFILE.Close();
End-If;
```

Related Links

GetString

ReadLine

WriteString

WriteRaw

WriteRaw

Syntax

WriteRaw(*RawBinary*)

Description

The WriteRaw method writes the contents of *RawBinary* to a file. This can be used for writing images, messages, or other types of raw binary data to a file.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

RawBinary	Specify the raw binary to be written to the file.

Returns

None.

Example

The following example writes employee photos (GIF files) from a record to a file.

```
Local File &FILE;
Local Record &REC;
Local SQL &SQL;

&REC = CreateRecord(Record.EMPL_PHOTO);
&SQL = CreateSQL("%SelectAll(:1)", Record.EMPL_PHOTO);

&FILE = GetFile("C:\temp\EMPL_PHOTO.GIF", "w", "a", %FilePath_Absolute);

While &SQL1.Fetch(&REC)
   &FILE.WriteRaw(&REC.EMPLOYEE_PHOTO.Value);
End-While;

&FILE.Close();
```

Related Links

WriteLine

WriteString

WriteRecord

Syntax

WriteRecord(*record*)

Description

The WriteRecord method is a file layout method. It writes the contents of the record object *record*, to the output file. (Remember, a record object contains only one row of data from an SQL table.)

You can use this method to build a transaction in the output file, one file record at a time, without having to instantiate and populate a rowset object. You can apply this method to any record whose structure and name matches that of a record defined in the current file layout.

Note: You must execute the SetFileId method from the file object before using WriteRecord, otherwise it returns False.

See SetFileLayout.

Note: When you're writing text to an XML file, special HTML characters, such as ampersands, lesser than or greater than symbols, and so on, are automatically converted to valid XML character string, such as &amp.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Considerations Using XML With File Definition Tags

File Definition Tags have no effect when importing data. However, generally, during export, the File Definition Tag is added at the start and end of the data to create a valid XML file.

The one exception is when the file to which the data is being written during export has been opened in append mode. At that time, the file definition tag is not taken into consideration.

Considerations Using XML with File Definitions

If your file layout is defined as XML, WriteRecord doesn't add the closing tag for the record. You must write it yourself using the WriteLine method. This is because the code has no way of knowing when you want to write children records following the record just written out.

The following code shows an example of using WriteLine:

```
Local File &MYFILE;

&MYFILE = GetFile("XMLrecord.txt", "A");

If &MYFILE.IsOpen Then
   If &MYFILE.SetFileLayout(FILELAYOUT.RECORDLAYOUT) Then
      &LN = CreateRecord(RECORD.QA_INVEST_LN);
      &SQL2 = CreateSQL("%Selectall(:1)", &LN);
      While &SQL2.Fetch(&LN)
         &MYFILE.WriteRecord(&LN);
         WriteLine("</QA_INVEST_LN>"); /* Add the closing tag */
      End-While;
   Else
   /* do error processing - filelayout not correct */
   End-If;
Else
/* do error processing - file not open */
End-If;

&MYFILE.Close();
```

Parameters

record Specify the name of an existing record object to be written. You can use Rowset class methods such as GetField and built-in functions such as GetRecord to populate the record with data before writing it to the file.

Returns

A Boolean value: True if the method succeeds, False otherwise. This value is optional.

Example

The following example appends all the data in a record to an existing file:

```
Local File &MYFILE;

&MYFILE = GetFile("record.txt", "A");

If &MYFILE.IsOpen Then
   If &MYFILE.SetFileLayout(FILELAYOUT.VOL_TEST) Then
      &LN = CreateRecord(RECORD.VOLNTER_ORG_TBL);
      &SQL2 = CreateSQL("%Selectall(:1)", &LN);
      While &SQL2.Fetch(&LN)
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
         &MYFILE.WriteRecord(&LN);
      End-While;
   Else
      /* do error processing - filelayout not correct */
   End-If;
Else
   /* do error processing -; file not open */
End-If;

&MYFILE.Close();
```

Related Links

CreateRowset

ReadRowset

SetFileLayout

WriteRowset

Understanding Record Class

"Understanding Data Buffer Access" (PeopleTools 8.54: PeopleCode Developer's Guide)

WriteRowset

Syntax

WriteRowset(*rowset* [, *Write_Data*])

Description

The WriteRowset method is a file layout method. It writes the contents of a rowset object, *rowset*, to the output file associated with the file object executing this method. Regardless of whether the rowset contains just one or more than one transaction (level zero row), executing this method once writes the entire contents of the rowset to the output file.

Note: You must execute the SetFileLayout method from the file object before using WriteRowset, otherwise it returns False.

See SetFileLayout.

WriteRowset writes a rowset to a file only if the data in the component buffer has changed. You must specify the *WriteData* parameter as True if you want the WriteRowset method to force the rowset to be written to the file even if the buffer has not been changed.

Note: When you're writing text to an XML file, special HTML characters, such as ampersands, lesser than or greater than symbols, and so on, are automatically converted to valid XML character string, such as &amp.

Considerations Using Fixed Length Files With Numeric Fields

All numeric fields are right-justified in when writing to fixed length files. In addition, zeros are padded to the right after the decimal point if required.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Considerations Using XML With File Definition Tags

File Definition Tags have no effect when importing data. However, generally, during export, the File Definition Tag is added at the starting and end of the data to create a valid XML file.

The one exception is when the file to which the data is being written during export has been opened in append mode. At that time, the file definition tag is not taken into consideration.

Parameters

rowset Specify the name of an existing rowset object that was instantiated with the File class CreateRowset or ReadRowset method. You can use Rowset class methods such as Select and built-in functions such as GetLevel0 to populate the rowset with data before writing it to the file.

WriteData Specify whether to write the rowset data to the file whether or not the data in the buffer has changed. This parameter takes a Boolean value: True, write the data to the buffer regardless, False, only write the data if changed. The default value for this parameter is False.

Returns

A Boolean value: True if the method succeeds, False otherwise.

Example

```
Local File &MYFILE;
Local Rowset &FILEROWSET;

&MYFILE = GetFile("c:\temp\EMP_CKLS.txt", "A", %FilePath_Absolute);
If &MYFILE.IsOpen Then
   If &MYFILE.SetFileLayout(FILELAYOUT.EMPL_CHECKLIST) Then
      &FILEROWSET = &MYFILE.CreateRowset();
      &FILEROWSET = GetLevel0();
      &MYFILE.WriteRowset(&FILEROWSET, True);
   Else
      /* file layout not found, do error processing */
   End-If;
Else
   /* file not opened, do error processing */
End-if;

&MYFILE.Close();
```

Related Links

CreateRowset

ReadRowset

SetFileLayout

WriteRecord

ZeroExtend

Understanding Record Class

"Understanding Data Buffer Access" (PeopleTools 8.54: PeopleCode Developer’s Guide)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

WriteString

Syntax

WriteString(*string*)

Description

The WriteString method writes one string of text to the output file associated with the file object executing this method, without any newline character. Each string written extends the current line in the file.

You can start a new line by using the WriteLine method to write the last part of the current line. WriteLine always adds a newline character appropriate to the platform where the file is being written, whether you supply a character string of any length, or a null string.

Parameters

string	A string variable containing the text to be written.

Returns

None.

Example

The following example opens an empty file, writes two lines of text to it without a final newline, and closes it:

```
&MYFILE.Open("somefile.txt", "W");
&MYFILE.WriteString("This is the first ");
&MYFILE.WriteString("line in the file.");
&MYFILE.WriteLine("");
&MYFILE.WriteString("This second line is not terminated.");
&MYFILE.Close();
```

Related Links

ReadLine

WriteLine

WriteRaw

File Class Properties

In this section, we discuss each File Class property.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

CurrentRecord

Description

This property is a file layout property. This property returns the current record as a string. The CurrentRecord property is used in combination with the SetFileId and ReadRowset methods and IsNewFileId property when reading files that contain data based on multiple file layouts.

If the ReadRowset method returns NULL, either the current record is a FileId record or the end of file has been reached. The IsNewFileId enables you to determine which. If it is a FileId, you can parse the string returned by CurrentRecord to determine the file layout definition to be used.

Note: SetFileId, CurrentRecord, and IsNewFileId don't apply to CSV and XML format input files. You can implement multiple file layouts only with fixed format files.

This property is read-only.

Example

```
&RECSTRING = &MYFILE.CurrentRecord;
```

Related Links

SetFileId
ReadRowset
IsNewFileId
Multiple File Layouts

IgnoreInvalidId

Description

This property is a file layout property that's used in combination with the ReadRowset method. It returns a Boolean value that specifies whether file records with invalid FileIds are ignored. Each time ReadRowset is executed, it may encounter a file record that doesn't qualify as part of the rowset because its File ID isn't part of the current file layout, or because it occurs in an invalid position in the rowset. If IgnoreInvalidId is False, the PeopleCode program terminates; if IgnoreInvalidId is True, ReadRowset ignores the invalid file record. The default value is True.

This property is read-write.

Example

```
&MYFILE.IgnoreInvalidId = False;
```

Related Links

ReadRowset

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

IsError

Description

This property is a file layout property. It returns a Boolean value indicating whether a field error condition was generated by the last file layout method executed. If an error condition was generated, IsError returns True; if not, IsError returns False. The default value is False.

This property is read-only.

Example

The following example shows where IsError would be used:

```
&MYFILE.Open(&SOMENAME, "R");
&MYFILE.SetFileLayout(FILELAYOUT.SOMELAYOUT);
&MYROWSET = &MYFILE.ReadRowset();
If &MYFILE.IsError Then
   /* Examine the EditError property of each field in the rowset
      to find the one with the error, and respond accordingly */
End-If;
&MYFILE.Close();
```

Related Links

Multiple File Layouts

IsNewFileId

Description

This property is a file layout property. It returns a Boolean value indicating whether a FileId file record has been encountered. When the ReadRowset method reads a transaction from an input file, it examines the current file record following the transaction. If that file record is a FileId file record, IsNewFileId returns True; if not, IsNewFileId returns False.

IsNewFileId is used in combination with the SetFileId method and CurrentRecord property when reading files that require multiple file layouts.

Note: SetFileId, CurrentRecord, and IsNewFileId don't apply to CSV and XML format input files. You can use only fixed format files to implement multiple file layouts.

This property is read-only.

Example

```
&MYFILE.SetFileLayout(FILELAYOUT.SOMELAYOUT) then  /* Set the first layout */
&MYFILE.SetFileId("999", 1);  /* Set the FileId */
&SOMEROWSET = &MYFILE.ReadRowset();  /* Read the first rowset */
While &SOMEROWSET <> NULL
   If &MYFILE.IsNewFileId Then
      /* Examine &MYFILE.CurrentRecord for the next layout */
      /* Set the next layout */
      &MYFILE.SetFileId("999", 1);  /* Set the FileId */
   End-If;
   /* Process the current &SOMEROWSET */
   &SOMEROWSET = &MYFILE.ReadRowset();  /* Read the next rowset */
End-While;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

ReadRowset
SetFileId
CurrentRecord

IsOpen

Description

This property returns a Boolean value indicating whether the file is open. If the file object is open, IsOpen returns True; if not, IsOpen returns False.

This property is read-only.

Example

The following example opens a file, writes a line to it, and closes it:

```
&MYFILE.Open("item.txt", "W");
If &MYFILE.IsOpen Then
   &MYFILE.WriteLine("Some text.");
   &MYFILE.Close();
End-If;
```

Name

Description

This property returns as a string the name of the external file. If no file is currently associated with the file object, Name returns a NULL string.

This property is read-only.

Example

```
&TMP = &MYFILE.Name;
```

TerminateLines

Description

Use the TerminateLines property to indicate whether all output data lines are to be terminated at the end of the defined data length. This property is a file layout property associated with fixed file layouts only.

This property takes a Boolean value: True to force output data lines to be terminated at the end of the defined data length; False to keep all lines all at the maximum of their own length or that of their children. The default value is false.

This property is read-write.

Example

```
If &FILE_CREATED = "N" Then
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
   &FILE_CREATED = "Y";
   &FILENAME = &MSGNAME | "_" | &PROCESS_INSTANCE | "_*.out";
   &FILE = GetFile(&FILENAME, "N", "U");
   &FILE.SetFileLayout(@("FILELAYOUT." | &MSGNAME));
   &FILE.TerminateLines = True;
   &RS_LVL0 = &FILE.CreateRowset();
   &REC_MSG_LVL0 = &RS_LVL0(&ROWCNT0).GetRecord(1);

   If EO_BATLIB_AET.CREATE_FILE_FLG = "C" Then
      &STRING = "998       " | &MSGNAME;
      &FILE.WriteLine(&STRING);
   End-If;
End-If;
```

UseSpaceForNull

Description

Use the UseSpaceForNull property to specify whether the WriteRowset method writes <qualifier><qualifier> (<qualifier>-space-<qualifier>) for all the Null or empty character fields of a CSV-type file layout, or if the method writes <qualifier><qualifier> (<qualifier>-<qualifier>).

This property takes a Boolean value: false if WriteRowset writes <qualifier>-<qualifier>, true if WriteRowset writes <qualifier>-space-<qualifier>. The default is False.

Note: The state of this property has no effect on the behavior of the ReadRowset method. It also has no effect when the associated file layout is of type fixed or XML.

This property is read-write.

Example

```
Local File &LOGFILE;
Local File &FILE1;
Local File &FILE2;
Local Record &REC1;
Local SQL &SQL1;
Local Rowset &RS1;
Local Row &ROW1;

&LOGFILE = GetFile("C:\Temp\currency.log", "W", "A", %FilePath_Absolute);
If (&LOGFILE = Null) Then
   Exit;
End-If;
If Not (&LOGFILE.SetFileLayout(FileLayout.CURRENCY_FL)) Then
   &LOGFILE.WriteLine("SetFileLayout() on LOGFILE failed.");
End-If;

&FILE1 = GetFile("C:\Temp\currency_nonspaced.csv", "W", "A", %FilePath_Absolute);
If (&FILE1 = Null) Then
   &LOGFILE.WriteLine("FATAL ERROR:  GetFile() on non-spaced output file failed.");
   &LOGFILE.Close();
   Exit;
End-If;
If Not (&FILE1.SetFileLayout(FileLayout.CURRENCY_FL)) Then
   &LOGFILE.WriteLine("FATAL ERROR:  SetFileLayout() on non-spaced output file fail⇒
ed.");
   &LOGFILE.Close();
   &FILE1.Close();
   Exit;
End-If;

&FILE2 = GetFile("C:\Temp\currency_spaced.csv", "W", "A", %FilePath_Absolute);
If (&FILE2 = Null) Then
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
   &LOGFILE.WriteLine("FATAL ERROR:  GetFile() on spaced output file failed.");
   &LOGFILE.Close();
   &FILE1.Close();
   Exit;
End-If;
If Not (&FILE2.SetFileLayout(FileLayout.CURRENCY_FL)) Then
   &LOGFILE.WriteLine("FATAL ERROR:  SetFileLayout() on spaced output file failed."⇒
);
   &LOGFILE.Close();
   &FILE1.Close();
   &FILE2.Close();
   Exit;
End-If;

&REC1 = CreateRecord(Record.CURRENCY_CD_TBL);
If (&REC1 = Null) Then
   &LOGFILE.WriteLine("FATAL ERROR:  CreateRecord() on record failed.");
   &LOGFILE.Close();
   &FILE1.Close();
   &FILE2.Close();
   Exit;
End-If;

&RS1 = CreateRowset(Record.CURRENCY_CD_TBL);
If (&RS1 = Null) Then
   &LOGFILE.WriteLine("FATAL ERROR:  CreateRowset() on record failed.");
   &LOGFILE.Close();
   &FILE1.Close();
   &FILE2.Close();
   Exit;
End-If;

&SQL1 = CreateSQL("%Selectall(:1)", &REC1);
If (&SQL1 = Null) Then
   &LOGFILE.WriteLine("FATAL ERROR:  CreateSQL() failed.");
   &LOGFILE.Close();
   &FILE1.Close();
   &FILE2.Close();
   Exit;
End-If;

If (&FILE1.UseSpaceForNull) Then
   &LOGFILE.WriteLine("UseSpaceForNull is True on non-spaced output, by default.");
Else
   &LOGFILE.WriteLine("UseSpaceForNull is False on non-spaced output, by default.")⇒
;
End-If;
If (&FILE2.UseSpaceForNull) Then
   &LOGFILE.WriteLine("UseSpaceForNull is True on spaced output, by default.");
Else
   &LOGFILE.WriteLine("UseSpaceForNull is False on spaced output, by default.");
End-If;

&FILE1.UseSpaceForNull = True;
If (&FILE1.UseSpaceForNull) Then
   &LOGFILE.WriteLine("Setting UseSpaceForNull to True succeeded on non-spaced outp⇒
ut.");
Else
   &LOGFILE.WriteLine("Setting UseSpaceForNull to True failed on non-spaced output.⇒
");
End-If;
&FILE2.UseSpaceForNull = True;
If (&FILE2.UseSpaceForNull) Then
   &LOGFILE.WriteLine("Setting UseSpaceForNull to True succeeded on spaced output."⇒
);
Else
   &LOGFILE.WriteLine("Setting UseSpaceForNull to True failed on spaced output.");
End-If;

&FILE1.UseSpaceForNull = False;
If (&FILE1.UseSpaceForNull) Then
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
   &LOGFILE.WriteLine("Setting UseSpaceForNull to False failed on non-spaced output⇒
.");
Else
   &LOGFILE.WriteLine("Setting UseSpaceForNull to False succeeded on non-spaced out⇒
put.");
End-If;
&FILE2.UseSpaceForNull = False;
If (&FILE2.UseSpaceForNull) Then
   &LOGFILE.WriteLine("Setting UseSpaceForNull to False failed on spaced output.");
Else
   &LOGFILE.WriteLine("Setting UseSpaceForNull to False succeeded on spaced output.⇒
");
End-If;

&FILE1.UseSpaceForNull = False;
&FILE2.UseSpaceForNull = True;
&I = 1;
While &SQL1.Fetch(&REC1)
   &ROW1 = &RS1.GetRow(1);
   &REC1.CopyFieldsTo(&ROW1.CURRENCY_CD_TBL);
   &FILE1.WriteRowset(&RS1, True);
   &FILE2.WriteRowset(&RS1, True);
   REM   &LOGFILE.WriteLine("Got row " | String(&I));
   &I = &I + 1;
End-While;

&FILE1.Close();
&FILE2.Close();
&LOGFILE.Close();
```

Related Links

WriteRowset

ZeroExtend

Description

Use this property to specify whether or not the WriteRowset method zero-extends the value it writes for decimal fields for CSV or XML format files.

For example, for a decimal field defined as 6.3, the value 1.12 will be written as follows depending on the value of ZeroExtend:

True: 1.120

False: 1.12

This property takes a Boolean value: true if WriteRowset zero-extends the value it writes; false otherwise. The default value is true.

Note: This property has no effect in the case of a fixed-position format file. In addition, it does not affect the behavior of the ReadRowset method.

This property is read-write.

Related Links

WriteRowset

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

File Layout Examples

If your data is hierarchical in nature, or based on existing PeopleSoft records or pages, you want to use a File Layout definition for reading and writing your data, rather than doing it line by line (or field by field.)

For example, suppose you wanted to write all the information from a record to a file. You can use the WriteRecord method to write all the data from the record, instead of having to loop through every field, find the value, and write it to the file.

In addition, you could write all the information from a transaction (or several transactions) from a page to a file. Each transaction can be considered a *rowset*. A rowset can contain more than one record and is generally composed in a hierarchical structure. You could create a File Layout definition that has the same structure as the page (or component), and use the WriteRowset method. If you have a file that contains data in the correct format, you can use the ReadRowset method to read the data from the file to the page.

Each file layout is associated with a *format*. This format specifies the type of data in the files. You specify the format as part of the File Layout Properties. You can only specify one format for a file layout. Available formats are:

- FIXED (default)
- CSV
- XML

The file layout methods and properties use this information to handle each file type in a transparent manner. Generally, you don't need to do anything different based on file type. Any exceptions are noted in the documentation.

Note: Unlike other PeopleTools definitions, records and field are *copied* to a File Layout definition. There are no pointers. This means if you change a record definition (add or remove a field) you must change the File Layout definition also. The changes are not automatically propagated. This is why the documentation refers to these elements as file records, file fields, and so on, to show that they are no longer part of the original definition they were created from.
PeopleSoft recommends regenerating all file layout definitions after any upgrade, to avoid any corruption caused by changes to the database.

See Using Standalone Rowsets for more examples of writing from and reading to files using File Layout and standalone rowsets.

Related Links

"Using Standalone Rowsets" (PeopleTools 8.54: PeopleCode Developer's Guide)
"Understanding Data Buffer Access" (PeopleTools 8.54: PeopleCode Developer's Guide)
"Understanding File Layouts" (PeopleTools 8.54: Application Designer Developer's Guide)
"Constructing File Layouts" (PeopleTools 8.54: Application Designer Developer's Guide)
"Performing Data Interchanges" (PeopleTools 8.54: Application Designer Developer's Guide)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

WriteRecord Example

Image: Example File Layout definition (ABS_HIST)

In the following example, the File Layout definition is based on the record ABSENCE_HISTORY, and looks like this:

You should note the following about the using the WriteRecord method:

- Not all the fields in the File Layout definition and the record have to match. The WriteRecord method, like all File Layout methods, applies only to the *like-named* fields. If there are additional fields in the record or in the File Layout definition, they are ignored.
- The WriteRecord method writes only to *like-named* records. If you rename a record after you use it to create a File Layout definition, you must rename it to the exact same name in your File Layout. Because WriteRecord writes like-named records, the same file layout definition can contain more than one record.
- The WriteRecord method takes a *record object* as its parameter. A populated record object references a *single row* of data in the SQL table. This is why a SQL Fetch statement is used in a condition around the WriteRecord method. This fetches every row of data from the SQL table, then writes it to the file.

The following code writes the ABSENCE_HIST record to the file record.txt.

```
Local Record &RecLine;
Local File &MYFILE;
Local SQL &SQL2;

&MYFILE = GetFile("record.txt", "A");

If &MYFILE.IsOpen Then
   If &MYFILE.SetFileLayout(FileLayout.ABS_HIST) Then
      &RecLine = CreateRecord(RECORD.ABSENCE_HIST);
      &SQL2 = CreateSQL("%Selectall(:1)", &RecLine);
      While &SQL2.Fetch(&RecLine)
         &MYFILE.WriteRecord(&RecLine);
      End-While;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
   Else
      /* do error processing -; filelayout not correct */
   End-If;
Else
   /* do error processing -; file not open */
End-If;

&MYFILE.Close();
```

If you wanted to write only changed records to the file, you could add the following code that is set in bold font:

```
While &SQL2.Fetch(&RecLine)
   If &RecLine.IsChanged Then
         &MYFILE.WriteRecord(&RecLine);End-If;
End-While;
```

The following is the first part of a sample data file created by the previous code. The field format is FIXED:

```
8001       VAC 09/12/1981 09/26/1981 14  0                                  P Y
8001       VAC 03/02/1983 03/07/1983 5   0                                  P Y
8001       VAC 08/26/1983 09/10/1983 13  0                                  P Y
8105       CNF 02/02/1995 ??/??/     0   0                                  U N
8516       MAT 06/06/1986 08/01/1986 56  0                                  P Y
8516       SCK 08/06/1988 08/07/1988 1   0                                  P Y
8516       VAC 07/14/1987 07/28/1987 14  0                                  P Y
8553       JUR 12/12/1990 12/17/1990 5   0   Local Jury Duty               P N
8553       MAT 02/20/1992 10/01/1992 224 0   Maternity Leave               U N
8553       MAT 08/19/1994 03/01/1995 194 0   Maternity-2nd child           U Y
8553       PER 04/15/1993 04/19/1993 4   0                                  U N Per⇒
sonal Day required
8553       SCK 01/28/1987 01/30/1987 2   0   Hong Kong Flu                 P N
8553       SCK 08/02/1988 08/03/1988 1   0   Sick                          P N
8553       SCK 09/12/1995 09/13/1995 1   0                                  P N
8641       VAC 06/01/1988 06/15/1988 14  0                                  P Y
8641       VAC 07/01/1989 07/15/1989 14  0                                  P Y
G001       MAT 07/02/1991 09/28/1991 88  0   3-month Maternity leave        P Y Mat⇒
ernity will be paid as 80% of Claudia's current salary.
```

If a record in the File Layout definition has a File Record ID, each line in the file referencing this record is prefaced with this number. The File Record ID is not a field in the data itself. It is also referred to as the *rowid*. File Record IDs can be useful when the file you're producing refers to more than one record.

File Record IDs can be used only with File Layout definitions that have a type of FIXED. If a File Layout definition has only one level then File Record IDs can be omitted. But for File Layout definitions with more than one level, you *must* use File Record IDs.

The following is sample file, produced with the same code, but with a File Record ID of 101 added:

```
101 8001       VAC 09/12/1981 09/26/1981 14  0                              P Y
101 8001       VAC 03/02/1983 03/07/1983 5   0                              P Y
101 8001       VAC 08/26/1983 09/10/1983 13  0                              P Y
101 8105       CNF 02/02/1995 ??/??/     0   0                              U N
101 8516       MAT 06/06/1986 08/01/1986 56  0                              P Y
101 8516       SCK 08/06/1988 08/07/1988 1   0                              P Y
101 8516       VAC 07/14/1987 07/28/1987 14  0                              P Y
101 8553       JUR 12/12/1990 12/17/1990 5   0   Local Jury Duty           P N
101 8553       MAT 02/20/1992 10/01/1992 224 0   Maternity Leave           U N
101 8553       MAT 08/19/1994 03/01/1995 194 0   Maternity-2nd child       U Y
101 8553       PER 04/15/1993 04/19/1993 4   0                              U N Per⇒
sonal Day required
101 8553       SCK 01/28/1987 01/30/1987 2   0   Hong Kong Flu             P N
101 8553       SCK 08/02/1988 08/03/1988 1   0   Sick                      P N
101 8553       SCK 09/12/1995 09/13/1995 1   0                              P N
101 8641       VAC 06/01/1988 06/15/1988 14  0                              P Y
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
101 8641       VAC 07/01/1989 07/15/1989 14  0                              P Y
101 G001       MAT 07/02/1991 09/28/1991 88  0   3-month Maternity leave    P Y Mat⇒
ernity will be paid as 80% of Claudia's current salary.
```

Note: File positions start at 1, not 0. When you specify a File Record ID, make sure that the starting position of the Record ID is greater than 0.

ReadRecord Example

This following example uses the same File Layout definition as the previous example. The file format is CSV. The fields are separated by commas and delimited by double-quotes.

```
"8001","VAC","09/12/1981","09/26/1981","14","0","","P","Y",""
"8001","VAC","03/02/1983","03/07/1983","5","0","","P","Y",""
"8001","VAC","08/26/1983","09/10/1983","13","0","","P","Y",""
"8105","CNF","02/02/1995","??/??/","0","0","","U","N",""
"8516","MAT","06/06/1986","08/01/1986","56","0","","P","Y",""
"8516","SCK","08/06/1988","08/07/1988","1","0","","P","Y",""
"8516","VAC","07/14/1987","07/28/1987","14","0","","P","Y",""
"8553","JUR","12/12/1990","12/17/1990","5","0","Local Jury Duty","P","N",""
"8553","MAT","02/20/1992","10/01/1992","224","0","Maternity Leave","U","N",""
"8553","MAT","08/19/1994","03/01/1995","194","0","Maternity-2nd child","U","Y",""
"8553","PER","04/15/1993","04/19/1993","4","0","","U","N","Personal Day required"
"8553","SCK","01/28/1987","01/30/1987","2","0","Hong Kong Flu","P","N",""
"8553","SCK","08/02/1988","08/03/1988","1","0","Sick","P","N",""
"8553","SCK","09/12/1995","09/13/1995","1","0","","P","N",""
"8641","VAC","06/01/1988","06/15/1988","14","0","","P","Y",""
"8641","VAC","07/01/1989","07/15/1989","14","0","","P","Y",""
"G001","MAT","07/02/1991","09/28/1991","88","0","3-month Maternity leave","P","Y","⇒
Maternity will be paid as 80% of Claudia's current salary."
```

To read in the previous CSV file we use the following PeopleCode. It reads the file into a temporary record. First each line of the file is read into a string. The string is split into an array, with the value of each field in the array becoming an element in the array. The value of each field in the record is assigned a value from the array. After additional processing (for example, converting strings into dates or numbers, verifying data, and so on) the record can be inserted into the database. To insert the final data into the database, this code must be associated with a PeopleCode event that allows database updates, that is, SavePreChange, WorkFlow, SavePostChange, and so on. This code could also be used as part of an Application Engine program.

```
Local File &MYFILE;
Local Record &REC;
Local array of string &ARRAY;

&MYFILE = GetFile("c:\temp\vendor.txt", "R", %FilePath_Absolute);
&REC = CreateRecord(RECORD.ABS_HIST_TEST);
&ARRAY = CreateArrayRept("", 0);

If &MYFILE.IsOpen Then
   If &MYFILE.SetFileLayout(FILELAYOUT.ABS_HIST) Then
      While &MYFILE.ReadLine(&STRING);
         &ARRAY = Split(&STRING, ",");
         For &I = 1 To &REC.FieldCount
            &REC.GetField(&I).Value = &ARRAY[&I];
         End-For;
      /* do additional processing here for converting values */
         &REC.Insert();
      End-While;
   Else
      /* do error processing - filelayout not correct */
   End-If;
Else
   /* do error processing - file not open */
End-If;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
&MYFILE.Close();
```

Note: You can't read a file that contains a thousands separator for numeric fields. You must strip out the separator before you try to read in the file.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

WriteRowset Example

Image: Example File Layout definition (EMPL_CHECKLIST)

In the following example, the File Layout definition is based on the component EMPL_CHECKLIST, and looks like this:

Image: EMPLOYEE_CHECKLIST Component structure

Here's the structure of the component EMPLOYEE_CHECKLIST:

Note that:

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- Every *field* in the two structures don't have to match (that is, every field or record that's in the file layout doesn't have to be in the component, and vice versa.)
- The two *structures* must be the same. That is, if the component has PERSONAL_DATA at level zero, and EMPL_CHECKLIST at level one, the file layout must have the same hierarchy.

The following example uses the previous File Layout definition to copy data from the EMPL_CHECKLIST page into a file.

The CreateRowset function creates an empty rowset that has the structure of the file layout definition. The GetRowset function is used to get all the data from the component and copy it into the rowset. The GetLevel0 function copies all *like-named* fields to *like-named* records. The WriteRowset method writes all the component data to the file. Because this code runs on the server, an absolute file path is used.

See "GetRowset" (PeopleTools 8.54: PeopleCode Language Reference).

Example

The following is the PeopleCode for this example.

```
Local File &MYFILE;
Local Rowset &FILEROWSET;

&MYFILE = GetFile("c:\temp\EMP_CKLS.txt", "A", %FilePath_Absolute);
If &MYFILE.IsOpen Then
   If &MYFILE.SetFileLayout(FILELAYOUT.EMPL_CHECKLIST) Then
      &FILEROWSET = &MYFILE.CreateRowset();
      &FILEROWSET = GetLevel0();
      &MYFILE.WriteRowset(&FILEROWSET, True);
   Else
      /* file layout not found, do error processing */
   End-If;
Else
   /* file not opened, do error processing */
End-if;

&MYFILE.Close();
```

The following is a sample data file created by the previous code:

```
8113       Frumman,Wolfgang
           08/06/1999 000001           8219        Going to London office
                     100     000015 I 08/06/1999
                     200     000030 I 08/06/1999
                     300     000009 I 08/06/1999
                     400     000001 I 08/06/1999
                     500     000011 I 08/06/1999
                     600     000002 I 08/06/1999
                     700     000021 I 08/06/1999
                     800     000024 I 08/06/1999
                     900     000004 I 08/06/1999
                     1000    000006 I 08/06/1999
           09/06/1999 000004           7707        What to do after he arrives
                     100     000022 I 08/06/1999
                     200     000008 I 08/06/1999
                     300     000018 I 08/06/1999
                     400     000019 I 08/06/1999
8101       Penrose,Steven
           07/06/1999 000006           8229        New hire
                     1       000033 I 08/06/1999
                     2       000034 I 08/06/1999
                     3       000035 I 08/06/1999
                     4       000036 I 08/06/1999
                     5       000037 I 08/06/1999
                     6       000038 I 08/06/1999
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
                    7       000039 I 08/06/1999
                    8       000040 I 08/06/1999
                    9       000041 I 08/06/1999
                    10      000042 I 08/06/1999
```

When you create the File Layout definition, you can choose for each field whether to inherit a value from a higher level record field. If a value is inherited, it is written only *once* to the file, the first time it's encountered.

In the previous data example, there are three records: PERSONAL_DATA, EMPL_CHECKLIST, and EMPL_CHKLST_ITM. The field EMPLID is on all three records, but is written to the file only the first time a new value is encountered. So, the value for EMPLID is inherited by EMPL_CHECKLIST, and the value for EMPL_CHKLST_ITM is inherited from PERSONAL_DATA. The field CHECKLIST_DT is on EMPL_CHECKLIST and EMPL_CHKLST_ITM. However, the field value appears only once, in the parent record, and not in the child record.

If a record in the File Layout definition has a File Record ID, each line in the file referencing this record will be prefaced with this number. The File Record ID is not a field in the data itself. It is also referred to as the *rowid*. File Record IDs can be useful when the file being created refers to more than one record. File Record IDs can be used only with File Layout definitions that have a type of FIXED.

The following is sample file, produced with the same code, but with a File Record IDs added to all the records. 001 was added to the first level, 002 to the second, and 003 to the third.

```
001 8113       Frumman,Wolfgang
002            08/06/1999      000001 8219        Going to London office
003                      100    000015 I 10/13/1999
003                      200    000030 I 10/13/1999
003                      300    000009 I 10/13/1999
003                      400    000001 I 10/13/1999
003                      500    000011 I 10/13/1999
003                      600    000002 I 10/13/1999
003                      700    000021 I 10/13/1999
003                      800    000024 I 10/13/1999
003                      900    000004 I 10/13/1999
003                      1000   000006 I 10/13/1999
002            09/06/1999      000004 7707        What to do after he arrives
003                      100    000022 I 10/13/1999
003                      200    000008 I 10/13/1999
003                      300    000018 I 10/13/1999
003                      400    000019 I 10/13/1999
001 8101       Penrose,Steven
002            10/13/1999      000006 8229        New hire
003                      1      000033 I 10/13/1999
003                      2      000034 I 10/13/1999
003                      3      000035 I 10/13/1999
003                      4      000036 I 10/13/1999
003                      5      000037 I 10/13/1999
003                      6      000038 I 10/13/1999
003                      7      000039 I 10/13/1999
003                      8      000040 I 10/13/1999
003                      9      000041 I 10/13/1999
003                      10     000042 I 10/13/1999
```

ReadRowset Example

The following program reads all the rowsets from a file and updates a work scroll with that data. The work scroll isn’t hidden on the page: it’s created in the Component buffer from existing records using CreateRowset. The structure of the work scroll and the file layout are identical: that is, they’re composed

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

of two records, and the names of the records in the file layout are exactly the same as the names of the record definitions.

```
Local File &CHARTINPUT_F;
Local Rowset &INPUT_ROWSET, &TEMP_RS, &WORK_DATA;
Local Record &WRK_DATA;

&filename = "c:\temp\test.txt";
If FileExists(&filename, %FilePath_Absolute) Then
   &CHARTINPUT_F = GetFile(&filename, "R", "A", %FilePath_Absolute);
Else
   Exit;
End-If;

&CHARTINPUT_F.SetFileLayout(FileLayout.CHART_INFO);

/* Create rowset to be read into
NOTE that you have to start at LOWEST level of rowset */

&TEMP_RS = CreateRowset(RECORD.CHART_ITEM);
&WORK_DATA = CreateRowset(RECORD.CHART_DATA, &TEMP_RS);
&INPUT_ROWSET = CreateRowset(RECORD.CHART, &WORK_DATA);

While &INPUT_ROWSET <> Null
   &INPUT_ROWSET = &CHARTINPUT_F.ReadRowset();
   &INPUT_ROWSET.CopyTo(&WORK_DATA);
   /* do processing -- Though file may contain more than one level zero
   Component processor only allows one level zero at a time */
End-While;
```

File Rowset Considerations

The following are considerations for when you use rowsets with files.

- Although you can create a File Layout definition with more than four levels of hierarchy, a rowset created from Component buffer data can contain only four levels (level zero through 3). Any additional levels of data are ignored.
- ReadRowset populates the rowset with one transaction from the file. (A transaction is considered to be one instance of level zero data contained in a file record, plus all of its subordinate data.) WriteRowset writes one transaction to a file.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Application Engine Example

Image: Application Engine example program

You can also use PeopleCode in an Application Engine program to either write to or read from files. This example isn't a proper Application Engine program: it contains the PeopleCode only for opening and reading from a file. However, it's included here as starting point for your own Application Engine programs.

Here is the Application Engine program:

Here is the PeopleCode in the step 1.

```
Local File &FILE;
Local Record &REC;
Local Rowset &FRS;

&FILE = GetFile("TEST.txt", "R");
&REC = CreateRecord(Record.QEPC_FILE_REC);
&SQL = CreateSQL("%Insert(:1)");

If Not &FILE.IsOpen Then
   Error ("TEST: failed file open");
Else
   If Not &FILE.SetFileLayout(FileLayout.QEPC_FILE_REC) Then
      Error ("TEST: failed SetFilelayout");
   Else
      &FRS = &FILE.ReadRowset();
      While &FRS <> Null
         &FRS.GetRow(1).QEPC_FILE_REC.CopyFieldsTo(&REC);
         &SQL.execute(&REC);
         &FRS = &FILE.ReadRowset();
      End-While;
   End-If;
   &FILE.Close();
End-If;
```

The example Application Engine program reads the following CSV file:

```
"TEST2","1ST","01/01/1901",10
"TEST2","2ND","01/01/1902",20
"TEST2","3RD","01/01/1903",30
"TEST2","4TH","01/01/1904",40
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Note that the last field has no qualifier.

Image: QEPC_FILE_REC File Layout

The File Layout used to read this record has the following form:

Image: File Layout Definition Properties

The properties for the QEPC_FILE_REC File Layout are as follows:

Note that the Definition Qualifier is double-quotes ("), while the separator is a comma.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Remember, the last field didn't have a qualifier. To account for that, the field properties for this field must be edited, and a blank must be put in the Field Qualifier property.

Image: File layout Field Properties

The following image illustrates the way properties can be defined for the fields in the File layout.

See "Application Engine Fundamentals" (PeopleTools 8.54: Application Engine)

Multiple File Layouts

In the previous examples, the input file contained rowsets based on a single File Layout definition. However, PeopleTools provides the functionality to process input files containing rowsets that require several *different* File Layouts.

Note: You can use only fixed format files to implement multiple file layouts.

See the SetFileId method for details about handling multiple file layouts.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

In this section, we discuss how to:

- Read multiple file layouts.
- Write multiple file layouts.

See SetFileId.

Reading Multiple File Layouts

If your input file contains data based on more than one File Layout, it must contain an indicator, called a FileId that specifies:

- When a different File Layout definition should be used.
- Which File Layout definition should be used.

The FileId must be specified on a separate line and must precede *every* rowset that requires a layout different from the previous rowset. It isn't considered part of the rowset.

In the following example, the file contains two FileId lines; they use a file record ID that distinguishes them from the rowset data—in this case, "999".

```
999 PRODUCT  /* The following rowset uses the PRODUCT layout */
001  /* Level 0 record data */
101  /* level 1 record data */
201  /* Level 2 record data */
201  /* Level 2 record data */
999 ORDER  /* The following two rowsets use the ORDER layout */
001  /* Level 0 record data */
111  /* Level 1 record data */
111  /* Level 1 record data */
001  /* Level 0 record data */
111  /* Level 1 record data */
111  /* Level 1 record data */
```

The FileId can contain any information you want that indicates which file layout to use; the "PRODUCT" and "ORDER" fields shown are just examples.

To read this file, you should do the following in your program:

1. Use the SetFileId method to specify the file record ID value.
2. Use the ReadRowset method to read the data.
3. Check if the rowset is NULL.

   NULL indicates you've reached either the end of the file or a new rowset.

4. Use the IsNewFileId property to check if the next line is a FileId file record (line).

- If IsNewFileId is False, you've reached the end of the file.
- If IsNewFileId is True, use the CurrentRecord property to determine which File Layout to use next.

The following example reads rowsets from a file. When it finds a new rowset (indicated by &IsNewFileId returning True) the value of &CurrentRecord is passed to a function that reads and evaluates the line, then

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

returns the name of the new file layout. (The code for the function FindFileId is included at the start of the example.)

```
Local File &MYFILE;
Local Rowset &rsFile;
Local Record &rSomeRec1, &rSomeRec2;
Local SQL &SQL1;

Function FindFileID(&CurrentRecord As string) Returns string ;
   Evaluate RTrim(Substring(&CurrentRecord, 5, 50))
   When "SOME_REC1"
      &FILELAYOUT = "SOME_REC1";
   When "SOME_REC2"
      &FILELAYOUT = "SOME_REC2";
   End-Evaluate;
   Return &FILELAYOUT;
End-Function;

&rSomeRec1 = CreateRecord(Record.SOME_REC1);
&rSomeRec2 = CreateRecord(Record.SOME_REC2);
&SQL1 = CreateSQL("%Insert(:1)");
&MYFILE = GetFile("c:\temp\MULTI_FILE.out", "R", %FilePath_Absolute);

rem Set temporary first file layout;
&MYFILE.SetFileLayout(FileLayout.SOME_REC1);
&MYFILE.SetFileId("999", 1);

rem Read rowset to find actual first file ID;
&rsFile = &MYFILE.ReadRowset();
&CurrentRecord = &MYFILE.CurrentRecord;
&IsNewFileID = &MYFILE.IsNewFileId;
If &MYFILE.IsNewFileId Then
   &FILELAYOUT = FindFileID(&CurrentRecord);
   &MYFILE.SetFileLayout(@("FileLayout." | &FILELAYOUT));
   &MYFILE.SetFileId("999", 1);
End-If;

rem Read first 'real' rowset;
&rsFile = &MYFILE.ReadRowset();
&CurrentRecord = &MYFILE.CurrentRecord;
&IsNewFileID = &MYFILE.IsNewFileId;
While &rsFile <> Null Or
      &IsNewFileID
   If &MYFILE.IsNewFileId Then
      &FILELAYOUT = FindFileID(&CurrentRecord);
      &MYFILE.SetFileLayout(@("FileLayout." | &FILELAYOUT));
      &MYFILE.SetFileId("999", 1);
      If &IsNewFileID Then
         &rsFile = &MYFILE.ReadRowset();
         &CurrentRecord = &MYFILE.CurrentRecord;
         &IsNewFileID = &MYFILE.IsNewFileId;
      End-If;
   End-If;

   Evaluate &FILELAYOUT

   When "SOME_REC1"
      &rsFile(1).SOME_REC1.CopyFieldsTo(&rSomeRec1);
      &rSomeRec1.ExecuteEdits(%Edit_Required);
      If Not &rSomeRec1.IsEditError Then
         &SQL1.Execute(&rSomeRec1);
      End-If;
      Break;
   When "SOME_REC2"
      &rsFile(1).SOME_REC2.CopyFieldsTo(&rSomeRec2);
      &rSomeRec2.ExecuteEdits(%Edit_Required);
      If Not &rSomeRec2.IsEditError Then
         &SQL1.Execute(&rSomeRec2);
      End-If;
   End-Evaluate;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
   &rsFile = &MYFILE.ReadRowset();
   &CurrentRecord = &MYFILE.CurrentRecord;
   &IsNewFileID = &MYFILE.IsNewFileId;
End-While;

&MYFILE.Close();
```

See SetFileId, ReadRowset, IsNewFileId.

Writing Multiple File Layouts

If you're writing files that contain data based on more than one File Layout definition, consider the following points:

- If the file is going to a third-party vendor, you should work with the third-party to determine what their requirements are for specifying the different data formats.
- If the file is going to be used by another PeopleSoft system, you must add the FileId between each rowset that requires a different layout. FileId file records are *not* part of any rowset. They should be designed so they won't be mistaken for part of a rowset. You can create and write them to the file in many ways. The following are suggestions:
  - Build each line as a string, using any of the built-in string manipulation functions, then write them to the file using the File class WriteLine or WriteString methods.
  - Design a file layout consisting of a single file record definition for the FileId file records, then build the records using Record Class methods and functions, and write them to the file using the WriteRecord method.

The following code example writes each record from the level one scroll on a page to the file using a different File Layout. Between each WriteRowset the File ID file record is written to the file, describing the new File Layout being used.

```
Local File &MYFILE;
Local Rowset &FILEROWSET;
Local Record &REC1, &REC2;
Local SQL &SQL;

&MYFILE = GetFile("c:\temp\Records.txt", "W", %FilePath_Absolute);
If &MYFILE.IsOpen Then
   If &MYFILE.SetFileLayout(FileLayout.TREE_LEVEL) Then
      &REC1 = CreateRecord(Record.PSTREELEVEL);
      &FILEROWSET = &MYFILE.CreateRowset();
      &SQL = CreateSQL("%Selectall(:1)", &REC1);
      /* write first File ID to file */
      &MYFILE.WriteLine("999 FILE LAYOUT 1");
      While &SQL.Fetch(&REC1)
         &REC1.CopyFieldsTo(&FILEROWSET.GetRow(1).PSTREELEVEL);
         &MYFILE.WriteRowset(&FILEROWSET, True);
      End-While;
   Else
      /* file layout not found, do error processing */
   End-If;

   If &MYFILE.SetFileLayout(FileLayout.TREE_USERLEVEL) Then
      &REC2 = CreateRecord(Record.TREE_LEVEL_TBL);
      &FILEROWSET = &MYFILE.CreateRowset();
      &SQL = CreateSQL("%Selectall(:1)", &REC2);
      /* write second File ID to file */
      &MYFILE.WriteLine("999 FILE LAYOUT 2");
      While &SQL.Fetch(&REC2)
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
         &REC2.CopyFieldsTo(&FILEROWSET.GetRow(1).TREE_LEVEL_TBL);
         &MYFILE.WriteRowset(&FILEROWSET);
      End-While;
   Else
      /* file layout not found, do error processing */
   End-If;
Else
   /* file not opened, do error processing */
End-If;
&MYFILE.Close();
```

See WriteLine, WriteString, WriteRecord.

See Understanding Record Class.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Chapter 23

Grid Classes

Understanding Grid and GridColumn Classes

A grid looks and behaves like a spreadsheet embedded in a page: it has column headings, row headings, cells, and horizontal and vertical scroll bars. It can be used instead of a single-level scroll. It is analogous to a scroll region on a page. Each row in a grid corresponds to a set of controls in a scroll occurrence. Each cell in a grid corresponds to a field on a page.

The grid class enables you to instantiate only GridColumn objects, which in turn enables you to change grid column attributes without having to write PeopleCode that loops through every row of the grid.

Note: PeopleSoft builds a page grid one row at a time. Because the grid class applies to a complete grid, you can't attach PeopleCode that uses the grid class to events that occur before the grid is built; the earliest event you can use is the page Activate Event.

Note: Use the grid classes to control the display of a grid control. If you want to manipulate an analytic grid, used with PeopleSoft Analytic Calculation Engine data, you must use the AnalyticGrid classes.

Related Links

GridColumn Class

"Using Grids" (PeopleTools 8.54: Application Designer Developer's Guide)

"PeopleCode Events" (PeopleTools 8.54: PeopleCode Developer's Guide)

Understanding the Analytic Calculation Engine Classes

Shortcut Considerations

An expression of the form

```
&MYGRID.columnname.property
```

is converted to an object expression by using **GetColumn**(*columnname*). The following examples are equivalent.

Using *columnname:*

```
&MYGRIDCOLUMN = &MYGRID.CHECKLIST_ITEMCODE;
```

Using the GetColumn method:

```
&MYGRIDCOLUMN = &MYGRID.GetColumn("CHECKLIST_ITEMCODE");
```

The following examples are equivalent.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Using *columnname*:

```
&MYGRID.CHECKLIST_ITEMCODE.Visible = False;
```

Using the GetColumn method:

```
&MYGRID.GetColumn("CHECKLIST_ITEMCODE").Visible = False;
```

The Grid Class in PeopleCode

The PeopleCode grid object is a reference to a page runtime object for the grid. These particular page runtime objects aren't present until the Component is started.

Note: PeopleSoft builds a page grid one row at a time. Because the Grid class applies to a complete grid, you can't attach PeopleCode that uses the Grid class to events that occur before the grid is built; the earliest event you can use is the page Activate Event.

If you're using the grid within a secondary page, the runtime object for the grid isn't created until the secondary page is run. The grid object can't be obtained until then, which means that the earliest PeopleCode event you can use to activate a grid that's on a secondary page is the Activate event for the secondary page.

The attributes you set for displaying a page grid remain in effect only while the page is active. When you switch between pages in a component, you have to reapply those changes *every time* the page is displayed.

In addition, the Activate event associated with a page fires every time the page is displayed. Any PeopleCode associated with that Activate event runs, which may undo the changes you made when the page was last active. For example, if you hide a grid column in the Activate event, then display it as part of a user action, when the user tabs to another page in the component, then tabs back, the Activate event runs again, hiding the grid column again.

If a user at runtime hides a column of a grid, tabs to another page in the component, then tabs back to the first page, the page is refreshed and the grid column is displayed again.

When you place a grid on a page, the grid is automatically named the same as the name of the primary record of the scroll for the grid. This is the name you use with the GetGrid function. You can change this name on the Record tab of the Grid properties.

Note: There is no visible property for a grid, just a grid column. However, you can still hide an entire grid. Remember, many of the Rowset methods and properties work on a grid. If you want to hide an entire grid, get the rowset for that grid by using the HideAllRows Rowset class method.

Use the grid classes to access an ordinary grid. Use the analytic grid classes to access an analytic grid.

Related Links

Understanding the Analytic Calculation Engine Classes

"PeopleCode Events" (PeopleTools 8.54: PeopleCode Developer's Guide)

HideAllRows

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Data Type for a Grid or Grid Column Object

Grids are declared using the Grid data type. For example,

```
Local Grid &MYGRID;
```

Grid Columns are declared using the GridColumn data type. For example:

```
Local GridColumn &MYGRIDCOL;
```

Scope of a Grid or Grid Column Object

Both the grid and grid column objects can be instantiated from PeopleCode only.

A grid is a control on a page. You generally use these objects only in PeopleCode programs that are associated with an online process, not in an Application Engine program, a message subscription, a Component Interface, and so on.

In addition, PeopleSoft builds a page grid one row at a time. Because the Grid class applies to a complete grid, you can't attach PeopleCode that uses the Grid class to events that occur before the grid is built; the earliest event you can use is the page Activate Event.

Grid Class Built-in Function

"GetGrid" (PeopleTools 8.54: PeopleCode Language Reference)

Grid Class Methods

In this section, we discuss each Grid class method.

EnableColumns

Syntax

EnableColumns(*&Array*)

Description

Use this method to enable or disable one or more columns in a grid. When a column is enabled, it is editable; when it's disabled, it is un-editable.

The EnableColumns method of the Grid class can provide a noticeable performance improvement over multiple calls to set the Enabled property of the GridColumn class. Each call manipulating a grid (either using a Grid class method or setting a GridColumn property) has a significant, and similar performance overhead. Therefore, one key to increasing the performance of PeopleCode programs manipulating grids is to reduce the number of these calls. Performance testing data suggests that if your program is changing three or more columns, use one of the Grid class methods, such as the EnableColumns method, instead of

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

setting the column properties directly. The single call to the Grid class method offsets the small overhead of creating and populating the required array.

Parameters

&Array	Specify a two-dimensional array containing the column name and a value (Y/N) indicating whether the column is enabled.

Returns

None.

Example

```
&AREnable = CreateArrayRept(CreateArrayRept("", 2), 0);
&AREnable.Push(CreateArray("JOB_DETAIL", "Y"));
&AREnable.Push(CreateArray("JOB_TIME", "Y"));
&myGrid.EnableColumns(&AREnable);
```

Related Links

Enabled

GetColumn

Syntax

GetColumn(*columnname*)

Description

The GetColumn method instantiates a grid column object from the Grid class, and populates it with a grid column from the grid object executing this method. Specify the grid column name in the page field properties for that field, consisting of any combination of uppercase letters, digits and "#", "$", "@", and "_".

To specify a grid column name:

1. Open the page in Application Designer, select the grid and access the page field properties.
2. Select the Columns tab on the grid properties.
3. Either double-click on the grid column you want to name, or select the column and click the Properties button.
4. On the General tab, type the grid column name in the Page Field Name field.

Note: Although it's possible to base multiple grid columns on the same record field, the Page Field Name you enter for each grid column must be unique, not just for that grid, but for that page. If you have two grids on a page, every page field name must be unique to the page.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

columnname Specify a string containing the value of the Page Field Name on the General tab of the grid column's properties. You must have previously entered a value for the Page Field Name for the grid column you want to work with.

Returns

A GridColumn object populated with the grid column specified as the parameter to this method.

Example

```
local Grid &MYGRID;
local GridColumn &MYGRIDCOLUMN;

&MYGRID = GetGrid(PAGE.EMPLOYEE_CHECKLIST, "EMPL_GRID");
&MYGRIDCOLUMN = &MYGRID.GetColumn("CHECKLIST_ITEMCODE");
```

The following function loops through rows on a grid. The function finds each row that is selected. It does this through the Selected property of the Row class of PeopleCode. Data is then moved from the selected row to a new row, on a different grid, in the same page. The way in which this function is written, data is moved from &SCROLL_SHELF to &SCROLL_CART. These are two different rowset objects, of two different grids, on the same page. Note that the two grids in this example are on the same occurs level.

```
/* Moving data between grids on the same occurs level */
/* of the same page */

Local Rowset &SCROLL_CART, &SCROLL_SHELF;

Function move_rows(&SCROLL_CART As Rowset, &SCROLL_SHELF As Rowset);

   &I = 1;
/* loop to find whether row is selected */
   Repeat
   If &SCROLL_SHELF.GetRow(&I).Selected = True Then

      If All(&SCROLL_CART(1).GetRecord(1).QEPC_ITEM.Value) Then

         &SCROLL_CART.InsertRow(&SCROLL_CART.ActiveRowCount);
      End-If;

   /* if it is selected move data to other grid   */

      &SCROLL_SHELF.GetRow(&I).GetRecord(1).CopyFieldsTo(&SCROLL_CART.GetRow(&SCROL⇒
L_CART.ActiveRowCount).GetRecord(1));

/* delete row from current grid so data disappears  */

      &SCROLL_SHELF.DeleteRow(&I);
      &I = &I - 1;
   End-If;

   &I = &I + 1;
   Until &I = &SCROLL_SHELF.ActiveRowCount + 1;

/* end of loop ****************************************/

End-Function;

/********* end of function ****************************/

/* Creating the rowset object */
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
&SCROLL_CART = GetLevel0()(1).GetRowset(SCROLL.QEPC_CART);
&SCROLL_SHELF = GetLevel0()(1).GetRowset(SCROLL.QEPC_SHELF);

/* calling the function   */

move_rows(&SCROLL_CART, &SCROLL_SHELF);
```

Related Links

"GetGrid" (PeopleTools 8.54: PeopleCode Language Reference)

LabelColumns

Syntax

LabelColumns(*&Array*)

Description

Use this method to set the display label for one or more columns in a grid.

The LabelColumns method of the Grid class can provide a noticeable performance improvement over multiple calls to set the Label property of the GridColumn class. Each call manipulating a grid (either using a Grid class method or setting a GridColumn property) has a significant, and similar performance overhead. Therefore, one key to increasing the performance of PeopleCode programs manipulating grids is to reduce the number of these calls. Performance testing data suggests that if your program is changing three or more columns, use one of the Grid class methods, such as the LabelColumns method, instead of setting the column properties directly. The single call to the Grid class method offsets the small overhead of creating and populating the required array.

Parameters

&Array	Specify a two-dimensional array containing the column name and a value for the column label.

Returns

None.

Example

```
&ARLabel= CreateArrayRept(CreateArrayRept("", 2), 0);
&ARLabel.Push(CreateArray("JOB_DETAIL", "Job Detail"));
&ARLabel.Push(CreateArray("JOB_TIME", "Job Time"));
&myGrid.LabelColumns(&ARLabel);
```

Related Links

Label

SetProperties

Syntax

SetProperties(*&Array*)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use this method to set multiple properties (column enabled, column visibility, and column label) for one or more columns in a grid.

The SetProperties method of the Grid class can provide a noticeable performance improvement over multiple calls to set individual properties of the GridColumn class. Each call manipulating a grid (either using a Grid class method or setting a GridColumn property) has a significant, and similar performance overhead. Therefore, one key to increasing the performance of PeopleCode programs manipulating grids is to reduce the number of these calls. Performance testing data suggests that if your program is changing three or more columns, use one of the Grid class methods, such as the SetProperties method, instead of setting the column properties directly. The single call to the Grid class method offsets the small overhead of creating and populating the required array.

Parameters

&Array Specify a four-dimensional array containing the column name, a value (Y/N) indicating whether the column is enabled, a value (Y/N) indicating whether the column is visible, and a value for the column label.

Returns

None.

Example

```
&ARProp= CreateArrayRept(CreateArrayRept("", 4), 0);
&ARProp.Push(CreateArray("JOB_DETAIL", "Y", "Y", "Job Detail"));
&ARProp.Push(CreateArray("JOB_TIME", "Y", "Y", "Job Time"));
&mygrid.SetProperties(&ARProp);
```

Related Links

Enabled

Label

Visible

SetRowHeader

Syntax

SetRowHeader(*&array_of_cols*)

Description

Use the SetRowHeader method to set grid column headers for accessibility mode (for the entire grid when there are no tab separators or for each tab separator when tab separators are present).

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

&array_of_cols

Specifies an array of string values containing the column names to be set as row headers. A column name is the Page Field Name of the field for the column.

In the case of a grid with no tab separators, this array must contain one column name only. In the case of a grid with tab separators, this array must contain one column name for each tab separator with the column name to be selected from the group of columns under control of that tab separator.

Returns

(Optional) A Boolean value: True if the method executed successfully; False otherwise.

Example 1

The following example is for a grid without tab separators:

```
Local Grid &MYGRID;

&MYGRID = GetGrid(Page.QE_GRID_API, "QE_ABSENCE_HIST");
&GridRowHeaders = CreateArrayRept("", 0);
&GridRowHeaders.Push("QE_ABSENCE_TYPE");
&MYGRID.SetRowHeader(&GridRowHeaders);
```

Example 2

The following example is for a grid with three tab separators:

```
Local Grid &MYGRID;

&MYGRID = GetGrid(Page.QE_GRID_PNL, "GRID1");
&GridRowHeaders = CreateArrayRept("", 0);
&GridRowHeaders.Push("DESCR1");
&GridRowHeaders.Push("DESCR2");
&GridRowHeaders.Push("NAME");
&MYGRID.SetRowHeader(&GridRowHeaders);
```

Related Links

RowHeader

"Setting Grid General Properties" (PeopleTools 8.54: Application Designer Developer's Guide)

"Creating Tabbed Grids" (PeopleTools 8.54: Application Designer Developer's Guide)

ShowColumns

Syntax

ShowColumns(*&Array*)

Description

Use this method to set the visibility for one or more columns in a grid.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The ShowColumns method of the Grid class can provide a noticeable performance improvement over multiple calls to set the Visible property of the GridColumn class. Each call manipulating a grid (either using a Grid class method or setting a GridColumn property) has a significant, and similar performance overhead. Therefore, one key to increasing the performance of PeopleCode programs manipulating grids is to reduce the number of these calls. Performance testing data suggests that if your program is changing three or more columns, use one of the Grid class methods, such as the ShowColumns method, instead of setting the column properties directly. The single call to the Grid class method offsets the small overhead of creating and populating the required array.

Parameters

&Array	Specify a two-dimensional array containing the column name and a value (Y/N) indicating whether the column is visible.

Returns

None.

Example

```
&ARShow= CreateArrayRept(CreateArrayRept("", 2), 0);
&ARShow.Push(CreateArray("JOB_DETAIL", "Y"));
&ARShow.Push(CreateArray("JOB_TIME", "Y"));
&myGrid.ShowColumns(&ARShow);
```

Related Links

Visible

Grid Class Properties

In this section, the Grid class properties are described in alphabetical order.

FreeFormStyleName

Description

Use this property to set or return a String representing the free form style (or styles) for the grid as previously set by this property.

This property is read-write.

Note: Styles for this grid set in Application Designer are not accessible through the FreeFormStyleName property.

Important! Use this property within fluid applications only.

Example

```
PTS_SRCH.PTS_RIGHTPNEL_RSLT.FreeFormStyleName = "psc_margin-left2em";
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

gridcolumn

Description

If a grid column name is used as a property, it accesses the grid column with that name. This means the following code:

```
&Mycolumn = &MyGrid.gridcolumnname;
```

acts the same as

```
&Mycolumn = &MyGrid.GetColumn(columnname);
```

This property is read-only.

Label

Description

This property returns a string specifying the label that appears as the title of the grid.

Note: You can't use this property to set labels longer than 100 characters. If you try to set a label of more than 100 characters, the label is truncated to 100 characters. Always put any changes to labels in the Activate event. This way the label is set every time the page is accessed.

This property is read-write.

Layout

Description

Use this property to set or return an Integer representing the grid layout type. The value can be one of the following constants:

Numeric Value	*Constant Value*	*Description*
0	%OriginalGrid	Original grids are the standard grid layout for classic pages in releases prior to PeopleTools 8.50.
1	%ScrollableGrid	Unlike original grids, scrollable grids take advantage of AJAX technology, which enables the user to change the grid structure and content directly on the transaction page without using the Personalize link.
2	%ListGrid	Used on fluid pages to contain a list grid.
3	%DataGrid	Used on fluid pages to contain a data grid.
4	%DivGrid	Used on fluid pages to contain a div grid.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Numeric Value	Constant Value	Description
5	%OriginalFlexGrid	Flex grids are the standard grid layout for classic pages in PeopleTools 8.50 and later releases.

This property is read-write.

Important! Use this property within fluid applications only.

Example

```
Local Grid &LGrid = GetGrid(Page.QE_NUI_GRIDLAYOUT, "PCODEGRID");
Local string &Devicetype;

&Devicetype = %Request.BrowserDeviceType;

Evaluate &Devicetype
When "pc"
   If %Request.BrowserTypeClass = "chrome" Then
      &LGrid.Layout = %DataGrid;
   Else
      &LGrid.Layout = %DivGrid;
   End-If;
When "phone"
   &LGrid.Layout = %OriginalFlexGrid;
When "tablet"
   &LGrid.Layout = %ListGrid;
End-Evaluate;
```

Related Links

"Setting Grid Use Properties" (PeopleTools 8.54: Application Designer Developer's Guide)

PersistMenuOption

Description

Use this property to set or return a Boolean value specifying the *persistent search* property for this grid. This corresponds to the "Persist In Menu" option for the grid that can be set in Application Designer. When this property is True, the most recent transaction search is stored and the search results are accessible through the drop-down navigation menu structure.

This property is read-write.

Example

```
&MyGrid = GetGrid(Page.GRIDCHECK, "GRIDNO");
&MyGrid.PersistMenuOption = True;

MessageBox(0, "", 0, 0, "Persist In Menu = " | &MyGrid.PersistMenuOption);
```

Related Links

"Setting Grid Use Properties" (PeopleTools 8.54: Application Designer Developer's Guide)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

RowHighlight

Description

Use this property to set or return a Boolean value indicating whether row highlighting has been enabled or disabled for the grid.

By default, when a grid has more than one row, and an end user hovers the mouse over a row or selects the row, the system highlights that row to indicate it is the row of current focus. However, this can be distracting or unnecessary for some interfaces for varying reasons, such as the number of rows in the grid, the form factor of the device displaying the page, and so on.

This property is read-write.

Example

In the following example, the first grid's row highlighting behavior is enabled; the second grid's row highlighting behavior is disabled.

```
*Within a page's Activate event */

Local Grid &MYGRID1;
Local Grid &MYGRID2;

&MYGRID1 = GetGrid(Page.USER_SELF_SERVICE, "PSUSEREMAIL");
&MYGRID1.RowHighlight = True;


&MYGRID2 = GetGrid(Page.USER_SELF_SERVICE, "MCF_IM_XMPP_CFG");
&MYGRID2.RowHighlight = False;
```

Related Links

"Setting Grid Use Properties" (PeopleTools 8.54: Application Designer Developer's Guide)

SummaryText

Description

Use this property to set or return a string representing the summary text for the grid.

Summary text enables you to provide a brief description of the functionality and content of the grid area. This property is pertinent for users who access the application in accessibility mode using screen readers.

This property is read-write.

Example

```
&MyGrid = GetGrid(Page.PSXLATMAINT, "PSXITMMNT_VW");
&MyGrid.SummaryText = "This is the new summary text through PeopleCode";
```

Related Links

"Setting Grid Label Properties" (PeopleTools 8.54: Application Designer Developer's Guide)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GridColumn Class

Grid columns are page fields that comprise a grid, which is itself a page field. Similarly, a group of GridColumn objects comprises a Grid object. The GridColumn class enables you to change grid column attributes without having to write PeopleCode that loops through every row of the grid.

This class has no methods or built-in functions, only properties.

Note: To use a GridColumn object, you must instantiate it from a grid object. This requires you to first instantiate a Grid object using the GetGrid built-in function.

You create an analytic grid column object from the analytic grid class. However, the analytic grid column class has the same properties as the grid column class. Any differences are noted in the documentation.

See "GetGrid" (PeopleTools 8.54: PeopleCode Language Reference).

GridColumn Class Properties

In this section, we discuss each GridColumn class property.

Enabled

Description

This property specifies whether the fields in the column are enabled (that is, can be edited) or if they are "disabled", that is, un-editable. All columns are enabled by default.

Note: For an analytic grid column, the Enabled property only works with cubes, not dimensions.

This property is read-write.

Example

```
If Not &ValidID Then
   &MYGRID = GetGrid(PAGE.EMPLOYEE_CHECKLIST, "EMPL_GRID");
   &MYGRIDCOLUMN = &MYGRID.GetColumn("CHECKLIST_ITEMCODE");
   &MYGRIDCOLUMN.Enabled = False;
End-If;
```

The EnableColumns and SetProperties methods of the Grid class can provide a noticeable performance improvement over multiple calls to set the Enabled property of the GridColumn class.

Related Links

EnableColumns

SetProperties

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Label

Description

This property specifies the display label for the GridColumn object , as distinct from the grid column's Record Field Name or Page Field Name. This property overrides the equivalent settings on the Label tab of the grid column's Page Field Properties.

Note: You can't use this property to set labels longer than 100 characters. If you try to set a label of more than 100 characters, the label is truncated to 100 characters. If you change the column label, then change the field label, you may overwrite the column label with the field label. The grid object is part of a page, *not* the data buffers, while the field is part of the data buffers. To avoid this problem, always put any changes to column labels in the Activate event. This way the label is set every time the page is accessed.

This property is read-write.

Example

```
&MYGRIDCOLUMN.Label = "Checklist Item";
```

The LabelColumns and SetProperties methods of the Grid class can provide a noticeable performance improvement over multiple calls to set the Label property of the GridColumn class.

Related Links

LabelColumns
SetProperties

Name

Description

This property returns the name of the grid column, as a string. This value comes from the Page Field Name on the General tab in the Page Field Properties of the GridColumn object executing the property. This property was the value used to instantiate the GridColumn object.

This property is read-only.

Example

```
&PF_NAME = &MYGRIDCOLUMN.Name;
```

RowHeader

Description

Use this property to return a Boolean value indicating whether the grid column field is row a header.

This property is read-only.

Example

```
Local Grid &MYGRID;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
Local GridColumn &MYGRIDTYPECOLUMN;

&MYGRID = GetGrid(Page.QE_GRID_API, "QE_ABSENCE_HIST");
&MYGRIDTYPECOLUMN = &MYGRID.GetColumn("QE_ABSENCE_TYPE");
If (&MYGRIDTYPECOLUMN.RowHeader) Then
   WinMessage("QE_ABSENCE_TYPE is a row header.");
Else
   WinMessage("QE_ABSENCE_TYPE is not a row header.");
End-If;
```

Related Links

SetRowHeader

"Setting Grid General Properties" (PeopleTools 8.54: Application Designer Developer's Guide)

Visible

Description

This property specifies whether a grid column is visible or hidden. Set this property to False to hide the grid column, and to True to unhide the grid column. This property defaults to True.

The Visible property also hides grid columns that are displayed as tabs in the PeopleSoft Pure Internet Architecture.

If you specify "Show Column on Hide Rows" in Application Designer, the column headers and labels of a grid display at runtime, even when the rest of the column is hidden. You can't override this value using PeopleCode.

Note: For an analytic grid column, this property is only valid if the column is bound to a dimension on a slicer, and bound to a cube that is on the column axis.

This property is read-write.

Note: In previous releases of PeopleTools, the methodology for hiding a grid column was to use the Hide function in a loop to hide each cell in the column, one row at a time. This method of hiding grid columns still works. However, your application will experience deteriorated performance if you continue to use this method.

Example

```
&MYGRIDCOLUMN.Visible = False;
```

The following example checks for the value of a field in every row of the grid. If that value is "N" for every row, the column is hidden.

```
&RS = GetRowset(Scroll.EX_SHEET_LINE);
&HIDE = True;
While (&HIDE)

   For &I = 1 To &RS.ActiveRowCount;
      &OUT_OF_POLICY = &RS(&I).EX_SHEET_LINE.OUT_OF_POLICY.Value;
      &NO_RECEIPT_FLG = &RS(&I).EX_SHEET_LINE.NO_RECEIPT_FLG.Value;
      If &OUT_OF_POLICY = "Y" Then
         &OUT_OF_POLICY_HIDE = False;
         &HIDE = False;
      End-If;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
      If &NO_RECEIPT_FLG = "Y" Then
         &NO_RECEIPT_HIDE = False;
         &HIDE = False;
      End-If;
   End-For;

   If &HIDE = True Then
      &HIDE = False;
   End-If;

End-While;

If Not (&OUT_OF_POLICY_HIDE) Then
   GetGrid(Page.EX_SHEET_LINE_APV1, "EX_SHEET_LINE").OUT_OF_POLICY.Visible = True;
Else
   GetGrid(Page.EX_SHEET_LINE_APV1, "EX_SHEET_LINE").OUT_OF_POLICY.Visible = False;
End-If;

If Not (&NO_RECEIPT_HIDE) Then
   GetGrid(Page.EX_SHEET_LINE_APV1, "EX_SHEET_LINE").NO_RECEIPT_FLG.Visible = True;
Else
   GetGrid(Page.EX_SHEET_LINE_APV1, "EX_SHEET_LINE").NO_RECEIPT_FLG.Visible = False⇒
;
End-If;
```

The ShowColumns and SetProperties methods of the Grid class can provide a noticeable performance improvement over multiple calls to set the Visible property of the GridColumn class.

Related Links

ShowColumns

SetProperties

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Chapter 24

Internet Script Classes (iScript)

Understanding Internet Script Classes

An Internet Script, also called an iScript, is a specialized PeopleCode function that generates dynamic web content. iScripts interact with web clients (browsers) using a request-response paradigm based on the behavior of the Hypertext Transfer Protocol.

iScripts work with PeopleSoft Pure Internet Architecture. You must have PeopleSoft Pure Internet Architecture set up correctly before you can run an iScript.

Image: Communication flow chart for Internet Scripts

The following flow chart shows the interaction of an iScript (PeopleCode) in a PeopleSoft Pure Internet Architecture application.

1. An HTTP request arrives at the web server specifying in its URL the Presentation Relay Servlet (psc). The path information included in the URL specifies which PeopleCode program to run. No

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

component is specified because none is needed. The PeopleCode program (iScript) runs directly. The following is an example of the URL:

```
http://serverx/Servlets/psp/ps84/e_procurement/fdm/s/WEBLIB_BEN_401k.PAGES.Fie⇒
ldFormula.IScript_Home401k
```

2. The psc servlet is invoked by the web server. It serializes all necessary information from the web server request and response objects, then makes a call through JOLT to the PeopleSoft application server service passing the serialized object information.

3. The application server unpacks all of the object information and creates PeopleSoft versions of the Request and Response objects. It then calls the function in the PeopleCode program specified in the URL. The PeopleCode Request and Response objects are available to the PeopleCode program through the system variables %Request and %Response.

4. The PeopleCode program is then responsible for generating every aspect of the HTML page that is to be returned to the browser. It has access to the Request object to view items such as query string parameters, cookies, and headers. It also has access to component interfaces, business interlinks, and Rowset objects to interact with applications. HTML definitions are available to include language sensitive blocks of HTML. They can also contain JavaScript. The message catalog is also available for language sensitive messages. The Response object is used to "write" the generated HTML back to the browser.

5. When the PeopleCode program is finished running, the headers, cookies, and HTML in the PeopleSoft Response object are serialized and returned through JOLT to the Presentation Relay Servlet.

6. The Presentation Relay Servlet then unpacks the Response information generated by the PeopleCode.

7. The servlet plays the information back to the web server response object, which in turn sends the response to the user's browser.

URL vs. URI

In this document, the term URL refers to the entire URL, that points to content. The following is an example of a URL:

```
http://someserver/servlets/psc/ps84/e_procurement/fdm/s/WEBLIB_Portal.FieldChange.I⇒
Script_DoSomething?page=view&key1=value1&key2=value2
```

A URI does not include the content information. Think of it as a subset of the URL that points to the location of the resource, but does not include any parameters passed to that resource. From the previous example, the URI portion of the URL is:

```
http://someserver/servlets/psc/ps84
```

Web Libraries

iScripts use the existing PeopleCode Function Library infrastructure. However, instead of naming your record FUNCLIB_xxx, all iScripts *must* be contained in records named WEBLIB_xxx. All of the existing

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

tools and techniques for working with function libraries (such as Upgrade, Find In, Rename, and so on) also apply to Web Libraries.

See "Accessing PeopleCode External Functions" (PeopleTools 8.54: PeopleCode Developer's Guide).

To create an iScript:

1. Create or extend a domain specific WEBLIB (funclib).

   WEBLIBs are derived/work record definitions that have their name prefixed with WEBLIB_.

2. Add a function to a WEBLIB.

   The name of your function *must* be prefaced with IScript_. For example:

   ```
   IScript_HelloWorld
   ```

   ```
   IScript_FuncHRPage
   ```

Note: iScript functions take no arguments, and do not return a value.

The following iScript writes data.

```
Function IScript_HPDefaultCategories()

   &ClearDotImage = %Response.GetImageURL(Image.PT_PORTAL_CLEAR_DOT);
   &CatHTML = GetHTMLText(HTML.PORTAL_HP_CATEGORY, &ClearDotImage, GetCategories())⇒
;
   %Response.Write(&CatHTML);

End-Function;
```

The following iScript uses both the request and response objects to echo what the user types into an edit control.

Image: Example iScript

This example illustrates the fields and controls on the Example iScript. You can find definitions for the fields and controls later on this page.

```
Function IScript_HelloWorld()

%Response.WriteLine("<html><head><title>Hello World</title></head><body>");
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
   %Response.WriteLine("<h1>Hello World</h1>");
   %Response.WriteLine("<form method=POST action = " | %Request.FullURI | "?" | %Re⇒
quest.QueryString | "><input type=submit value='Say this!'> <input type=edit na⇒
me=WhatYouSaid value=" | %Request.GetParameter("WhatYouSaid") | "></form>");

   rem echo back what the user typed into the edit box...;
   %Response.WriteLine("<p><font face='Arial, Helvetica' size='5' color='blue' >You⇒
 said: ");
   %Response.WriteLine(%Request.GetParameter("WhatYouSaid"));

   %Response.WriteLine("</body></html>");
   Return;
End-Function;
```

iScript Security

iScripts are secured on your system similar to Component Interfaces. After you create a WEBLIB record, and your functions, you must add them just as you would add a page to an application.

To add security to an iScript :

1. Navigate to the Maintain Security page and open the Permission List to which you want to give access.
2. Select Web Libraries.

   You may need to scroll through the tabs at the top of the page to access the Web Libraries tab.
3. (Optional) Add new WebLibrary for Permission List.

   If this is a new Web Library, you must add it to the permission list. Click the plus button to add a new Web Library, then select the library you want to add from the drop-down list box.
4. Select Edit for the Web Library you want to grant access for.
5. Select the access you want to give each function in the WEBLIB record.

   From the page that displays, you can choose to allow or disallow access on a per function basis. The buttons on the side of the page either grant or disallow access for all functions.

See*PeopleTools: Security Administration*.

When to Use an iScript

iScripts give you complete control over the HTML sent to the browser. This enables flexibility in creating a user interface. However, there are some responsibilities that you inherit when choosing to use iScripts.

- You are responsible for creating HTML and JavaScript that is cross-browser compatible.
- You are responsible for ensuring that all the text sent to the browser is stored in either the message catalog or in HTML definitions to enable translation of the text.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- iScripts aren't part of the regular Component Processor flow, so you are responsible for accessing the database in a multi-language, multi-market, and multi-currency sensitive way. (Do this by using a Component Interface to access the database.)

For these reasons, PeopleSoft recommends that you first try to build a page in Application Designer. This approach enables PeopleTools to generate all of the HTML in a cross-browser, multi-language, multi-market, and multi-currency sensitive way.

You don't have to use an iScript to generate an entire page. You can use the Request and Response objects with an HTML area, so you can develop a portion of your HTML using the iScript objects, while allowing the majority of it to be generated by the Component Processor. If you use this method, instead of using the Response object's Write and WriteLine methods to output your HTML, you set the value of the HTML area to the HTML that you want to display. Remember, that just as with an iScript, you must ensure that the HTML you generate is cross-browser compatible and multi-market sensitive.

So when *should* you use iScripts? Here are two scenarios where iScripts would be an appropriate choice:

- The page being developed *cannot* be built using Application Designer. An example of this is a page that requires more than one HTML form. PeopleSoft Pure Internet Architecture places the entire page inside of a single form tag, so no other HTML form tags can be added. In this case the requirements of the page can't be met by pages created in Application Designer, so use iScripts instead.

  Note: You should use Component Interfaces for all database access so you have multi-language and multi-currency sensitivity.

- The page being developed never accesses the database. Using a page and Component Processor for this type of page incurs unnecessary processing overhead. An example of this is a page that talks to another website and redisplays HTML from the remote site.

Style Sheets and Styles

PeopleSoft recommends that developers using the iScripts always use styles (also known as classes) defined in the style sheets to specify the attributes (that is, background color, font, size, alignment, borders, and so on) of objects referenced in the iScripts. The Response object provides access to Style Sheets stored in the PeopleSoft database.

Related Links

"Understanding Style Sheets and Style Classes" (PeopleTools 8.54: Application Designer Developer's Guide)

Other Considerations

PeopleSoft does not recommend using the following technologies in iScripts:

- Java applets
- Browser plug-ins

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Details of an iScript URL

Viewing an iScript requires the assembly of a URL with the following pieces:

Section	*Description*
http://Server/	The scheme (http / https) and web server name.
servlet_name/	The name of the physical servlet that the web server invokes to handle the request. This is either psp or psc.
SiteName/	The user-defined site name. This is defined during the installation of PIA. This enables you to set up multiple sites on one physical web server.
PortalName/	The name of the portal to use for this request. The portal object contains metadata that describes how to present the content (that is, template, pagelets and so on.)
NodeName/	The name of the node that contains the content for this request.
content_type/	The type of the content for this request. For iScripts, this is "s".
content_id	The identification of the content. This, and the type is the unique key to the content being retrieved.
?content_parm	The query string parameters (name value pairs) for the content.

For an iScript, the *content_id* has the following form:

```
Record.Field.Event.Function
```

The following is an example of the call to an iScript:

```
http://mlee2038//psp/PS84/e_procurement/fdm/s/WEBLIB_Portal.PORTAL_HEADER.FieldForm⇒
ula.IScript_UniHeader_PIA
```

The Generate Functions

There are many different types of content on the portal, such as components, iScripts, homepages, and so on. Sometimes you want to access this content directly, through the URL that points to this content. To do this, PeopleSoft provides several Generate functions that generate the URL for the specified content.

The Generate functions can be categorized as:

- Content type.
- Absolute or relative URL.
- Portal service or content servlet (psp or psc).

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The following is a list of the functions, plus a description of what to use them for. More information about a function is found under that function's description in the section PeopleCode Built-in Functions.

Function Name	*Content Type*	*Absolute or Relative URL*	*Portal service or content servlet*
GenerateActGuideContentUrl	Activity Guide	Absolute	psc
GenerateActGuidePortalUrl	Activity Guide	Absolute	psp
GenerateActGuideRelativeUrl	Activity Guide	Relative	NA
GenerateComponentContentURL	Component	Absolute	psc
GenerateComponentContentRelURL	Component	Relative	psc
GenerateComponentPortalURL	Component	Absolute	psp
GenerateComponentPortalRelURL	Component	Relative	NA
GenerateComponentRelativeURL	Component	Relative	NA
GenerateExternalPortalURL	External	Absolute	psp
GenerateExternalRelativeURL	External	Relative	NA
GenerateHomepagePortalURL	Homepage	Absolute	psp
GenerateHomepageRelativeURL	Homepage	Relative	NA
GenerateQueryContentURL	WQuery	Absolute	psc
GenerateQueryPortalURL	Query	Absolute	psp
GenerateQueryRelativeURL	Query	Relative	NA
GenerateScriptContentURL	IScript	Absolute	psc
GenerateScriptContentRelURL	IScript	Relative	psc
GenerateScriptPortalURL	Iscript	Absolute	psp
GenerateScriptPortalRelURL	IScript	Relative	psp
GenerateScriptRelativeURL	IScript	Relative	NA
GenerateWorklistPortalURL	Worklist	Absolute	psp
GenerateWorklistRelativeURL	Worklist	Relative	NA

Related Links

"Functions by Category" (PeopleTools 8.54: PeopleCode Language Reference)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Error Handling

All errors are handled through the session object. You should check the PSMessages collection to see if there are any errors in your code.

Note: `Exit(1)` does *not* rollback iScript transactions. To rollback in an iScript, you can use the SqlExec built-in function with the parameter of ROLLBACK (`SQLEXEC("ROLLBACK")`) or the MessageBox built-in function with a message error severity of error. You can also use the built-in function Error, but only if you are not sending HTML or XML in the error text itself.

Related Links

Error Handling

Scope of the Internet Script Classes

The Request, Response, and Cookie classes can be accessed only from PeopleCode. They can be used only as part of a PeopleSoft Pure Internet Architecture application—either as part of a page created in Application Designer or an iScript. An iScript is always contained in a WEBLIB record. You wouldn't use any of these objects in an Application Engine program, a Component Interface, and so on. However, an iScript could call and start a Component Interface, a Business Interlink, and so on.

To access the Request or Response object, use the %Request and %Response system variable. These variables are objects, so you use them with dot notation.

```
%Response.SetContentType("text/HTML");

If %Request.GetParameter("encode") <> "" Then
```

Data Types of the iScript Classes

Cookie objects are instantiated from Response object. You can declare the cookie object as data type cookie before any functions. You can also declare variables of type Response and Request, to assign the %Response and %Request system variables to local variables.

```
Local Cookie &Cookie;
Local Response &Resp;
Local Request &Req;

Function IScript_SetCookie()
    rem set a cookie called "MyCookie" to store my user id in it's value.
Make the cookie expire when the user's browser session expires;

   &Resp = %Response;
   &Req = %Request;
   &Cookie = &Resp.CreateCookie("MyCookie");
   &Cookie.Value = %UserId;
   &Cookie.MaxAge = -1;

End-Function;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Internet Script Classes

The following is a description of the PeopleCode classes, methods, and properties that you use to create an iScript.

Request Class

The Request object encapsulates all information from the request issued from the browser. This includes the URI, Query String, QueryString parameters, Cookies, and Headers. The properties for the Request object are read-only.

Parameters

Request parameters are name-value pairs sent by the client to the web server as part of an HTTP request. They include the pairs in the query string part of the URL, and data posted in a form, if the request was a post request. Multiple parameter values can exist for any given parameter name. The following methods are available to access parameters:

- GetParameter
- GetParameterNames
- GetParameterValues

The GetParameterValues method returns an array of String objects containing all the parameter values associated with a parameter name. The value returned from the GetParameter method equals the first value in the array of String objects returned by GetParameterValues.

All form data from both the query string and the post body are aggregated into the request parameter set. The order of this aggregation is that query string data appears before post body parameter data.

Response

The response object encapsulates all the information to be sent back to the browser. This includes the body of the response, content type, response headers, and cookies.

The response object also includes helper methods that retrieve HTML, Image, StyleSheet, and other objects from the database and move them to the web server, and returning strings that can be used to reference these objects in the response content.

The body of the response is created using the response object's Write and WriteLine methods. If the content type of the response is not explicitly set in the PeopleCode program, it defaults to "text/html".

Cookies

Cookies are data sent from the client to the server on every request that the client makes. Cookies are stored by the browser, either on disk or in memory, and returned to the server that originally set the cookie.

The Internet Script API makes available the name and value of each cookie that's sent with the request, through the Request object's GetCookieNames and GetCookieValue methods. The API also enables you

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

to set new cookies (or alter existing cookies) through the Response object's CreateCookie method and the Cookie object's properties.

Internet Script Classes Built-in Functions

"GenerateActGuideContentUrl" (PeopleTools 8.54: PeopleCode Language Reference)

"GenerateActGuidePortalUrl" (PeopleTools 8.54: PeopleCode Language Reference)

"GenerateActGuideRelativeUrl" (PeopleTools 8.54: PeopleCode Language Reference)

"GenerateComponentContentRelURL" (PeopleTools 8.54: PeopleCode Language Reference)

"GenerateComponentContentURL" (PeopleTools 8.54: PeopleCode Language Reference)

"GenerateComponentPortalRelURL" (PeopleTools 8.54: PeopleCode Language Reference)

"GenerateComponentPortalURL" (PeopleTools 8.54: PeopleCode Language Reference)

"GenerateComponentRelativeURL" (PeopleTools 8.54: PeopleCode Language Reference)

"GenerateExternalPortalURL" (PeopleTools 8.54: PeopleCode Language Reference)

"GenerateExternalRelativeURL" (PeopleTools 8.54: PeopleCode Language Reference)

"GenerateHomepagePortalURL" (PeopleTools 8.54: PeopleCode Language Reference)

"GenerateHomepageRelativeURL" (PeopleTools 8.54: PeopleCode Language Reference)

"GenerateQueryContentURL" (PeopleTools 8.54: PeopleCode Language Reference)

"GenerateQueryPortalURL" (PeopleTools 8.54: PeopleCode Language Reference)

"GenerateQueryRelativeURL" (PeopleTools 8.54: PeopleCode Language Reference)

"GenerateScriptContentRelURL" (PeopleTools 8.54: PeopleCode Language Reference)

"GenerateScriptContentURL" (PeopleTools 8.54: PeopleCode Language Reference)

"GenerateScriptPortalRelURL" (PeopleTools 8.54: PeopleCode Language Reference)

"GenerateScriptPortalURL" (PeopleTools 8.54: PeopleCode Language Reference)

"GenerateScriptRelativeURL" (PeopleTools 8.54: PeopleCode Language Reference)

"GenerateWorklistPortalURL" (PeopleTools 8.54: PeopleCode Language Reference)

"GenerateWorklistRelativeURL" (PeopleTools 8.54: PeopleCode Language Reference)

Request Class Methods

In this section, we discuss the Request class methods. The methods are discussed in alphabetical order.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

FormFactor

Syntax

FormFactor(*form_factor*)

Description

Use the FormFactor method to return the ceiling (the maximum device width in physical pixels) defined in the web server's configuration files for the specified form factor.

Important! Use this method within fluid applications only.

Parameters

form_factor Specifies the form factor as an integer. The value can be one of the following constants:

Numeric Value	*Constant Value*	*Default Ceiling (in physical pixels)*
0	%FormFactor_Small	519
1	%FormFactor_Medium	759
2	%FormFactor_Large	959
3	%FormFactor_Xlarge	999,999

Returns

An Integer value.

Example

```
If %Request.FormFactor(%FormFactor_Small) <= 400 Then
   ...
End-If;
```

GetContentBody

Syntax

GetContentBody()

Description

Note: PeopleSoft Business Interlinks is a deprecated product. This method currently exists for backward compatibility only.

This method retrieves the text content of an XML request. This is part of the incoming Business Interlink functionality, which enables PeopleCode to receive an XML request and return an XML response.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

None.

Returns

A string.

Example

The following example gets the XML text content of a request, then uses that as input to create a BiDoc. Then the BiDoc methods GetDoc and GetValue are used to access the value of the skills tag.

```
Local BIDocs &rootInDoc, &postreqDoc;
Local string &blob;
Local number &ret;

&blob = %Request.GetContentBody();
/* process the incoming xml(request)- Create a BiDoc */
&rootInDoc = GetBiDoc(&blob);
&postreqDoc = &rootInDoc.GetDoc("postreq");
&ret = &postreqDoc.GetValue("skills", &skills);
```

GetCookieNames

Syntax

GetCookieNames()

Description

This method returns an array containing names of all the cookies present in this request. If there are no cookies in the request, an empty array is returned. When cookies are present, this method returns an array of strings.

GetCookieValue

Syntax

GetCookieValue (*name*)

Description

This method returns a string containing value of the cookie identified *name*. The *name* parameter takes a string value. The NPmatch between *name* and the request cookie is case-insensitive. If there is no cookie in the request matching the name, an empty string is returned.

GetDeviceInfo

Syntax

GetDeviceInfo(*attribute*)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the GetDeviceInfo method to detect and return a value for the specified device attribute.

Important! Use this method within fluid applications only.

Parameters

attribute Specifies one of the listed device attributes as a string value:

Attribute	***Returns***
width	The device's width in physical pixels.
height	The device's height in physical pixels.
pixelratio	The ratio between physical pixels and device-independent pixels (dips) on the device.
touch	Whether the device supports touch events: • 1 – Supports • 0 – Does not support.
geolocation	Whether the device supports the geolocation API: • 1 – Supports • 0 – Does not support.
websockets	Whether the device supports the WebSockets API: • 1 – Supports • 0 – Does not support.
webworkers	Whether the device supports the Web Workers API: • 1 – Supports • 0 – Does not support.
datepicker	Whether the device supports the DatePicker widget: • 1 – Supports • 0 – Does not support.
dtpicker	Whether the device supports the DateTimePicker widget: • 1 – Supports • 0 – Does not support.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Attribute	***Returns***
timepicker	Whether the device supports the TimePicker widget: • 1 – Supports • 0 – Does not support.
dnd	Whether the device natively supports drag-and-drop: • 1 – Supports • 0 – Does not support.
sessionstorage	Whether the device supports the sessionStorage object: • 1 – Supports • 0 – Does not support.
localstorage	Whether the device supports the localStorage object: • 1 – Supports • 0 – Does not support.
history	Whether the device supports the history API: • 1 – Supports • 0 – Does not support.
canvas	Whether the device supports the <canvas> element: • 1 – Supports • 0 – Does not support.
svg	Whether the device supports the Scalable Vector Graphics (SVG) format: • 1 – Supports • 0 – Does not support.
postmessage	Whether the device supports the window.postMessage method: • 1 – Supports • 0 – Does not support.
hc	Whether the device supports a high contrast mode: • 1 – Supports • 0 – Does not support.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

An Integer value.

Example

```
&dev_info = %Request.GetDeviceInfo("width");
```

GetHeader

Syntax

GetHeader(*name*)

Description

This method returns the value of the header requested by the string *name*. The match between *name* and the request header is case-insensitive. If the header requested does not exist, an empty string is returned.

Example

The following example gets the "Referer" header to see where the request came from:

```
&Referer = %Request.GetHeader("Referer");
```

GetHeaderNames

Syntax

GetHeaderNames()

Description

This method returns an array of Strings representing the header names for this request.

GetHelpURL

Syntax

GetHelpURL(*HelpContext*)

Description

This method returns the help context path (as a string) to the help directory. It's used to construct a URL to a specific help page.

Example

```
&HelpURLString = %Request.GetHelpURL("hc0110");
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GetParameter

Syntax

GetParameter(*name*)

Description

This method returns the value of a specified query string parameter or posted form data parameter. The match between *name* and the request parameter is case-insensitive. If there are multiple parameter values for a single name, the value returned is the first value in the array returned by the GetParameterValues method. If the parameter has (or could have) multiple values, you should use the GetParameterValues method in your Internet scripts.

Related Links

GetParameterValues

GetParameterNames

Syntax

GetParameterNames()

Description

This method returns all the parameter names for this request as an array of Strings, or an empty array if there are no input parameters.

GetParameterValues

Syntax

GetParameterValues(*name*)

Description

This method returns the values of the specified parameter (*name*) as an array of Strings, or an empty array if the named parameter does not exist. The *name* parameter takes a string value.

Request Class Properties

In this section, we discuss the Request class properties. The properties are discussed in alphabetical order.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

AuthTokenDomain

Description

This property returns the web server domain as a string across which the single signon authentication token is valid. Use this property as the domain of any cookie which you want to apply across the same domain as the single signon token.

The value of this property is in the format:

```
".domain.com"
```

Note that it begins with a dot "." character. You can use this format as the value of a cookie's domain property.

However, sometimes you cannot use a value that is prefixed with a dot character. For example, the javascript document.docmain property should not begin with a dot. In this case, you must strip it off manually in your code.

Note: The value of this property is the domain across which the authentication token is valid, set in the AuthTokenDomain configuration property in the configuration properties file. The value of the system variable %AuthenticationToken is the authentication token itself.

This property is read-only.

Related Links

"%AuthenticationToken" (PeopleTools 8.54: PeopleCode Language Reference)

AuthType

Description

This property corresponds to the CGI variable AUTH_TYPE. This variable does not necessarily contain a value, and may require special web server configuration to obtain non-empty values.

This property is read-only.

Related Links

RemoteUser
ServletPath

BrowserDeviceFormFactor

Description

Use this property to return the form factor of the device as an integer, which corresponds to one of the following constants:

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Numeric Value	*Constant Value*
0	%FormFactor_Small
1	%FormFactor_Medium
2	%FormFactor_Large
3	%FormFactor_Xlarge

This property is read-only.

Important! Use this property within fluid applications only.

Example

```
If %Request.BrowserDeviceFormFactor = %FormFactor_Small Then
   PTNUI_LP_HEADER.PTNUI_LOGO.LabelImage = Image.PTNUI_ORACLE_LOGO_SFF;
   PTNUI_LAND_WRK.GROUPBOX15.FreeFormStyleName = "psc_hidden";
End-If;
```

BrowserDeviceType

Description

Use this property to return the device's type as a string value:

String Value	*Description*
pc	Desktop or laptop computer
phone	Phone
tablet	Tablet

This property is read-only.

Important! Use this property within fluid applications only.

Example

```
Local Grid &LGrid = GetGrid(Page.QE_NUI_GRIDLAYOUT, "PCODEGRID");
Local string &Devicetype;

&Devicetype = %Request.BrowserDeviceType;

Evaluate &Devicetype
When "pc"
   If %Request.BrowserTypeClass = "chrome" Then
      &LGrid.Layout = %DataGrid;
   Else
      &LGrid.Layout = %DivGrid;
   End-If;
When "phone"
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
   &LGrid.Layout = %OriginalFlexGrid;
When "tablet"
   &LGrid.Layout = %ListGrid;
End-Evaluate;
```

BrowserFluidCapable

Description

Use this property to return a string indicating whether the browser is defined as fluid capable in the web server's configuration files.

This property is read-only.

Important! Use this property within fluid applications only.

Example

```
If %Request.BrowserFluidCapable <> "Y" Then
   ...
End-If;
```

BrowserPlatform

Description

This property returns a string that represents the browser platform (WINXP, WIN8, WIN7, WINVISTA/WIN2008, WIN, MAC68K, MACPPC, MACIPAD, or MAC) that has been associated with the user agent as defined in the web server's configuration files.

This property is read-only.

BrowserPlatformClass

Description

Use this property to return a string value that represents the platform class (win, ios, mac, or android) that has been associated with the user agent as defined in the web server's configuration files.

This property is read-only.

Important! Use this property within fluid applications only.

Example

```
/* iPhone only to disable field zooming on focus */
If %Request.BrowserDeviceFormFactor = 0 And
      %Request.BrowserPlatformClass = "ios" Then
   &str = "width=device-width,initial-scale=1.0,minimum-scale=1.0,user-scalable=no"⇒
;
End-If;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

BrowserType

Description

This property returns a string that represents the browser type (CHROME, Safari, FIREFOX, or IE) that has been associated with the user agent as defined in the web server's configuration files.

This property is read-only.

BrowserTypeClass

Description

Use this property to return a string value that represents the browser type (chrome, safari, firefox, or ie) that has been associated with the user agent as defined in the web server's configuration files.

This property is read-only.

Important! Use this property within fluid applications only.

Example

```
Local Grid &LGrid = GetGrid(Page.QE_NUI_GRIDLAYOUT, "PCODEGRID");
Local string &Devicetype;

&Devicetype = %Request.BrowserDeviceType;

Evaluate &Devicetype
When "pc"
   If %Request.BrowserTypeClass = "chrome" Then
      &LGrid.Layout = %DataGrid;
   Else
      &LGrid.Layout = %DivGrid;
   End-If;
When "phone"
   &LGrid.Layout = %OriginalFlexGrid;
When "tablet"
   &LGrid.Layout = %ListGrid;
End-Evaluate;
```

BrowserVersion

Description

This property returns a string describing the version of the browser that sent the request.

This property is read-only.

ByPassSignOn

Description

This property returns a Boolean value, indicating what ByPassSignOn has been set to in the configuration properties file. If this value has been set to True, this property returns True, False otherwise.

This property is read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ContentURI

Description

This property returns a string containing the portion of the current URI before the portal name, and referencing the content servlet (psc).

For the URL:

```
http://localhost/psc/ps84/PORTAL/NODE/e_procurement/fdm/s/WEBLIB. . .
```

This property returns the following:

```
http://localhost/psc/ps84/
```

This property is read-only.

ExpireMeta

Description

This property returns the refresh meta-tag string that contains the cmd=expire parameter (the ExpireMeta string.)

The following is an example of the ExpireMeta string:

```
<meta HTTP-EQUIV='Refresh' Target='_top' CONTENT='10; URL=/servlets/psp/ps84/?cmd=e⇒
xpire'>
```

All Internet script pages should use this property to generate the meta tag to cause the page to expire. It is the same expiration tag used by pages originally created using Application Designer, unless the Internet script generates a menu link in a separate frame that is not supposed to expire.

This tag should be included in the <head> section of the HTML generated by the iScript.

This property is read-only.

Example

```
%Response.Write("<html><head>");
%Response.Write(%Request.ExpireMeta);
%Response.Write("</head><body>");
```

ExtraLarge

Description

Use this property to return a string value that represents the ceiling (the maximum device width in physical pixels) defined in the web server's configuration files for the extra large form factor. The default value is 999,999.

Note: You can use the FormFactor method instead to return an integer value.

This property is read-only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Important! Use this property within fluid applications only.

Related Links

FormFactor

FullURI

Description

This property returns the complete URI up to, but not including, the query string. This method returns a string value.

To return only the request URI (that is, without the scheme, server name or port) use the RequestURI method.

This property is read-only.

Example

From the following code

```
&FullURI = &Request.FullURI;
```

&FullURI might contain the following:

```
http://serverx/servlets/psp/ps84/Portal/Node/s/WEBLIB_TEST.SCRIPTS.FieldFormula.ISc⇒
ript_Test
```

Related Links

RequestURI

HTTPMethod

Description

This property returns the HTTP method as a string, (for example, GET, POST, PUT) by which this request was made.

This property is read-only.

Large

Description

Use this property to return a string value that represents the ceiling (the maximum device width in physical pixels) defined in the web server's configuration files for the large form factor. The default value is 959.

Note: You can use the FormFactor method instead to return an integer value.

This property is read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Important! Use this property within fluid applications only.

Related Links

FormFactor

LogoutURL

Description

This property returns the complete URL (as a string) to logout of the PeopleSoft session. Use this property to generate a link that causes a page to logout. You should normally not need to include this link on your page.

This property is read-only.

Medium

Description

Use this property to return a string value that represents the ceiling (the maximum device width in physical pixels) defined in the web server's configuration files for the medium form factor. The default value is 759.

Note: You can use the FormFactor method instead to return an integer value.

This property is read-only.

Important! Use this property within fluid applications only.

Related Links

FormFactor

PathInfo

Description

This property returns any path information following the servlet path, but prior to the query string. This property returns null if there is no path information following the servlet path.

This property is read-only.

Example

For the URL:

```
http:/localhost/psp/ps84/PORTAL/NODE/e_procurement/fdm/s/WEBLIB. . .
```

This property returns the following:

```
psp84/PORTAL/NODE/eprocurements/fdm/s/WEBLIB_. . .
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Protocol

Description

This property returns the protocol being used for this request as a string in the following form:

```
protocol/major_version.minor_version
```

An HTTP 1.0 request, as defined by the HTTP 1.0 specification, should return the string HTTP/1.0. Use the Scheme property instead of the Protocol property when generating hrefs (links).

This property is read-only.

QueryString

Description

This property returns the query string present in the request URL, if any. A query string is defined as any information following a ? character in the URL.

If there is no query string, this method returns null.

Use the request Parameters methods (GetParameterNames, GetParameterValues, GetParameter) to get the values of individual parameters on the query string.

This property is read-only.

RelativeURL

Description

This property returns whether a relative URL should be generated for PeopleSoft Pure Internet Architecture pages. This property is set in the configuration properties file. This property takes a Boolean value: True if a relative URL is generated for PeopleSoft Pure Internet Architecture pages, False otherwise.

This property is read-only.

RemoteAddr

Description

This property returns the IP address of the agent that sent the request.

This property is read-only.

RemoteHost

Description

This property returns the fully qualified host name of the agent that sent the request.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-only.

RequestURI

Description

This property returns the URI, without the protocol.

This property is read-only.

Example

This example uses the following URL:

```
http://serverx/servlets/psc/ps84/PORTAL/NODE/fdm/s/WEBLIB_Portal. . .
```

From the following code

```
&MyRequestURI = &Request.RequestURI;
```

&MyRequestURI contains the following:

```
/servlets/psc/ps84/PORTAL/NODE/fdm/s/WEBLIB_PORTAL . . .
```

Use the following to build an absolute URL:

```
&myURL = &Request.Scheme | "://" | &Request.ServerName | ":" | &Request.Port | &Req⇒
uest.RequestURI | "?" | &Request.QueryString;
```

RemoteUser

Description

This property corresponds to the CGI variable REMOTE_USER. It is not specific to your PeopleSoft implementation.

This variable does not necessarily contain a value, and may require special web server configuration to obtain non-empty values.

This value is generally populated when J2EE Authentication is enabled in the web-server configuration. The specific implementation of your web-server dictates how exactly this variable is populated. See your web-server specific documentation for more information.

This property is read-only.

Related Links

AuthType
ServletPath

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Scheme

Description

This property returns the scheme, also known as the protocol, used by the request. Common schemes include http, https, ftp, and telnet. This property returns a string value.

This property is read-only.

Example

For the URL

```
http://serverx/servlets/psp/ps84/eprocurement/fdm/s/WEBLIB. . . .
```

the Scheme property returns:

```
http
```

ServerName

Description

This property returns the host name of the server on which the servlet is running. This property returns a string value.

This property is read-only.

Example

For the URL

```
http://serverx/servlets/psp/ps84/eprocurement/fdm/s/WEBLIB. . . .
```

the ServerName property returns:

```
serverx
```

ServerPort

Description

This property returns an integer representing the port on which the browser's request was received (that is, the port on which the server is listening.)

This property is read-only.

Example

For the URL

```
http://servername:80/servlets/iclientservlet/peoplesoft8/?ICType=Panel. . .
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

the ServerPort property returns:

```
80
```

ServletPath

Description

This property corresponds to the CGI variable SCRIPT_NAME. This variable does not necessarily contain a value, and may require special web server configuration to obtain non-empty values.

This property is read-only.

Related Links

AuthType
RemoteUser

Small

Description

Use this property to return a string value that represents the ceiling (the maximum device width in physical pixels) defined in the web server's configuration files for the small form factor. The default value is 519.

Note: You can use the FormFactor method instead to return an integer value.

This property is read-only.

Important! Use this property within fluid applications only.

Related Links

FormFactor

Timeout

Description

This property returns an integer representing the timeout value, in seconds, set in the configuration.properties file.

This property is read-only.

Response Class

The response object encapsulates all information to be returned from the iScript to the browser.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Response Class Methods

In this section, we discuss the Response class methods. The methods are discussed in alphabetical order.

Clear

Syntax

Clear()

Description

This method removes all cookies and headers as well as deletes any HTML that has been written to the Response object. After using this method, the Response object appears as it did when the script was first called.

CreateCookie

Syntax

CreateCookie(*name*)

Description

This method adds a cookie to the response with the name specified by the string *name*. It returns a reference to the cookie object that is used to update the values of this cookie. If the cookie by the specified name already exists, a reference to the existing cookie is returned. This method can be called multiple times to set more than one cookie. Cookie names may not contain the "$" character.

Important! Certain browsers have limit of either 20 or 50 cookies per web server domain depending on the browser security update that the user has applied. The browser randomly discards some cookies when that number is exceeded.
PeopleTools uses eight cookies. In addition, the number of cookies used by PeopleTools can grow depending on the number of sites that the user visits within the same domain. Some PeopleSoft applications use additional cookies. Therefore, you might or might not be able to create your own cookies to modify an existing PeopleSoft application. If you do create your own cookies, keep the use conservative. Otherwise, your application might end up causing the browser to discard critical signon or authentication cookies.

More information about browser limitations can be found online.

See “Troubleshooting Browser Limitations” on My Oracle Support.

GetCookie

Syntax

GetCookie(*name*)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

This method returns the cookie object specified by the string *name*. If the cookie is not already present in this response, a null value is returned.

GetCookieNames

Syntax

```
GetCookieNames()
```

Description

This method returns an array of strings that contains the names of all the cookies present in this response. If there are no cookies in the response, an empty array is returned.

GetHeader

Syntax

```
GetHeader(name)
```

Description

This method returns the value of the response header requested by the string *name*. The match between *name* and the response header is case-insensitive. If the header requested does not exist, an empty string is returned.

GetHeaderNames

Syntax

```
GetHeaderNames()
```

Description

This method returns an array of Strings representing the header names for this response.

GetImageURL

Syntax

```
GetImageURL(IMAGE.ImageName | rowset.row.record)
```

Description

This method returns a string which represents the URL of the requested image for images stored in the database.

Because the image field is a long data type, you can have only one on a record. Therefore you need to specify the record only. The long field on the record is assumed to be the image.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Note: The GetImageURL method cannot be used with a derived work record.

Parameters

ImageName	Specify the name of an existing image. This name must be prefaced with the reserved word **IMAGE.**
rowset.row.record	Specify the path to the image, that is, the rowset, row, and record.

Example

The following example gets the URL to use for the image; and the second line uses the URL reference.

```
&image_URL = %Response.GetImageURL(Image.ARROW);

%Response.WriteLine("<img src=" | &strImage | ">");
```

The following gets an image from a record.

```
&image_URL = %Response.GetImageURL(&rs.GetRow(1).GetRecord(Record.EMPL_PHOTO));
```

GetJavaScriptURL

Syntax

GetJavaScriptURL(**HTML.***HTMLname*)

Description

This method returns a string which represents the URL of the requested HTML definition, for JavaScript HTML definitions stored in the database.

Example

This example assumes the existence in the database of an HTML definition called "HelloWorld_JS", that contains some JavaScript.

```
Function IScript_TestJavaScript()

   %Response.WriteLine("<script src= " | %Response.GetJavaScriptURL(HTML.HelloWorld⇒
_JS) | "></script>");

End-Function;
```

In this example, the HTML definition is called FOO. The following PeopleCode example:

```
%Response.GetJavaScriptURL(HTML.FOO)
```

Resolves to something similar to:

```
http://myserver/cache/js/FOO_ENG_1.js
```

Related Links

"Understanding HTML Definitions" (PeopleTools 8.54: Application Designer Developer's Guide)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GetStyleSheetURL

Syntax

GetStyleSheetURL(STYLESHEET.*stylename*)

Description

This method returns a URL string pointing to a style sheet created in Application Designer.

Example

In the following example, the first line gets the URL to use for the style sheet, and the second is the standard HTML to include the style sheet in the HTML document. The stylesheet link must be included in the HTML *before* any of the styles in the stylesheet are used. It should be included in the <head> section of the HTML document.

```
&strStyleSheet = %Response.GetStyleSheetURL(StyleSheet.BENEFITS_STYLE);

%Response.WriteLine("<link rel=stylesheet href=" | &strStyleSheet | " type=""text/c⇒
ss"">");
```

Now to use a style, assign the class attribute of your choice to your HTML tags, as follows:

```
%Response.WriteLine("<p class=PSTEXT>I am some classy text!!</p>");
```

RedirectURL

Syntax

RedirectURL(*location*)

Description

This method sends a temporary redirect response to the client using the location specified by the string location. The given location must be an absolute URL. No further output should be made by the iScript after calling this method.

Note: This function does not issue any kind of warning to the user about losing data. Your application should verify that all data is saved before launching a new page.

Note: If your URL string contains special characters (such as foreign characters) make sure you encode it first using the EncodeURL function, such as, `%Response.RedirectURL(EncodeUrl(&Url))`. In addition, while you can redirect relative URLs in certain circumstances, you *cannot* encode them.

Example

```
%Response.RedirectURL(&URL);
```

Related Links

"EncodeURL" (PeopleTools 8.54: PeopleCode Language Reference)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SetContentType

Syntax

SetContentType(*Type*)

Description

This method sets the content type for this response. The parameter *type* takes a string value. This type may later be implicitly modified by the addition of properties such as the MIME charset property if the service finds it necessary and the appropriate property has not been set.

The content type defaults to "text/html" if it is not set.

SetHeader

Syntax

SetHeader(*name, value*)

Description

This method sets a response header with the specified name and value. Both parameters take string values. If the field has already been set with a value, this new value overwrites the previous one.

Example

The PortalRegisteredURL response header identifies to the portal the registered URL of the current content, so that it can find the correct content reference to look at for the template.

You can override the value of the PortalRegisteredURL response header in a PIA Script or PIA Page by adding the header to the response yourself, like this:

```
%Response.SetHeader("PortalRegisteredURL", &myURL);
```

You can do this to register the content with additional parameters.

UseSimpleURL

Syntax

UseSimpleURL({True | False})

Description

The UseSimpleURL method sets the response header that informs the portal that the current content uses relative simple URLs, and does not have to be proxied.

By default, all PeopleSoft Pure Internet Architecture content sets the header to true. You must to call this method to specify that your content does not use the simple URL format, and therefore does need to be proxied.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

True | False	Specify a Boolean value, either True or False, to indicate whether simple URLs are used.

Returns

None.

Write

Syntax

Write(*String*)

Description

This method prints *String* to the HTTP output stream.

You can use an HTML string from Application Designer HTML catalog with the Write method if you also use the GetHTMLText function, as follows:

```
%Response.Write(GetHTMLTEXT(HTML.MY_HTML));
```

You can also use an XML string. The following example takes a BiDocs structure that contains an XML response and puts that into a text string. After this is done, the %Response.Write function can send this as an XML response.

```
Local BIDocs &rootDoc;
Local string &xmlString;

&xmlString = %Response.GetContentBody();
&rootDoc = GetBIDoc(&xmlString);

/* do processing */

&xmlString = &rootDoc.GenXMLString();
%Response.Write(&xmlString);
```

WriteLine

Syntax

WriteLine(*String*)

Description

This method adds a carriage control and line feed to the end of the string *String,* then prints the string to the HTTP output stream.

You can use an HTML string from Application Designer HTML catalog with the WriteLine method if you also use the GetHTMLText function, as follows:

```
%Response.WriteLine(GetHTMLTEXT(HTML.MY_HTML));
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Response Class Properties

In this section, we discuss the Response class properties.

Charset

Description

This property returns the character set used by the response object as a string.

This property is read-only.

DefaultStyleSheetName

Description

This property returns the name of the default style sheet defined on the PeopleTools Options page. If not defined, PSSTYLEDEF is returned.

This property is read-only.

Related Links

"Using Administration Utilities" (PeopleTools 8.54: System and Server Administration)

Cookie Class

The cookie class encapsulates all information to be sent to the browser for a single cookie. The cookie class is used by the response object to set new cookies. The request object uses a simple name-value pair mechanism for retrieving previously stored cookie values sent with the HTTP request.

Cookie Class Properties

In this section, we discuss the Cookie class properties. The properties are discussed in alphabetical order.

Domain

Description

This property returns the domain of this cookie, or null if not defined. This property is a string value.

This property is read-write.

Example

```
&cookie = &Response.AddCookie("My cookie", "My value");
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
&cookie.Domain = ".MyDomain.com";
```

MaxAge

Description

This property represents the maximum specified age of the cookie, as a signed number in seconds. The default value is -1. Setting the MaxAge property to a negative value ensures the cookie does not persist on the client when the client session ends. If the MaxAge property is set to zero, the cookie is deleted immediately from the client.

Value	*Description*
Non Negative Integer	Lifetime of the Cookie in seconds
0	Delete the cookie from the client immediately
-1	Default MaxAge property value (remove the cookie after the client exits)
Negative Integer	Remove the cookie after the client exits

This property is read-write.

Name

Description

This property returns the name of the cookie as a string.

This property is read-only.

Path

Description

This property returns the prefix of all the URL paths for which this cookie is valid, or an empty string if not defined.

This property is read-write.

Secure

Description

This property specifies whether the cookie is to be secured. This property takes a Boolean value. The default value is False. Secure cookies are sent only if the client has established a secure link (such as HTTPS) with the server. This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Value

Description

This property returns the value of the cookie (as a string), or an empty string if it isn't defined.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Chapter 25

Java Class

Understanding Java Class

Using the PeopleCode Java functions, you can access Java classes, or create instances of Java objects. Calling a Java program from PeopleCode can greatly extend your application. Also, the PeopleCode integration with Java enables you to pass parameters such as record, record fields, or rowsets into Java programs.

The PeopleCode Java functions are:

- CopyToJavaArray
- CopyFromJavaArray
- CreateJavaArray
- CreateJavaObject
- GetJavaClass

Supported Versions of Java

The supported platform database lists all supported versions of the Java Runtime Environment (JRE) for each version of PeopleTools on each supported operating system platform.

See My Oracle Support, "Platform Certifications."

Oracle also bundles a supported JRE version with PeopleTools for all supported operating system platforms except the z/OS platform. For z/OS, you will have to install a supported JRE. To determine which JRE is bundled with your version of PeopleTools, see the README file in the *PS_HOME*\jre directory.

Java Packages and Classes Delivered with PeopleTools

Java classes delivered with PeopleTools are located in the following directory:

```
PS_HOME\class
```

For PeopleSoft software, we typically use a standard package hierarchy:

```
com.peoplesoft.prodline.prodcode
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

In this hierarchy, *prodline* is the company standardized product line code (for example, hrms) and *prodcode* is the product code unique within the product line (for example, hr).

In addition, if there are any classes that are common across products, they are placed into the common package for that product line, that is:

`com.peoplesoft.prodline.common`

System Setup for Java Classes

If you access only the classes that come defined with PeopleTools, you don't need to do any additional setup.

If you want to access third-party Java classes or your own custom Java classes in the PeopleTools environment (that is, access these classes through PeopleCode), you must place the class files in specified locations or include the class files in JAR files in specified locations.

Note: Oracle recommends using the utility that comes with the Java SDK for creating JAR files.

When PeopleTools loads the Java Virtual Machine (JVM), PeopleTools builds a class path for the JVM from the following elements. The following numbering indicates the search order that the JVM would use for locating a specified Java class:

1. Class files in the *PS_HOME*\class directory.
2. Class files in JAR files in the *PS_HOME*\class directory.
3. Class files in the *PS_HOME*\appserv\classes directory.
4. Class files in JAR files in the *PS_HOME*\appserv\classes directory.
5. For each directory listed in the “Add To CLASSPATH” parameter of the psappsrv.cfg configuration file:
   a. Class files in the specified directory.
   b. Class files in JAR files in the specified directory.
6. For each directory listed in the PS_CLASSPATH environment variable:
   a. Class files in the specified directory.
   b. Class files in JAR files in the specified directory.

For example, if PS_CLASSPATH is “dir1;dir2”, the search order for item 6 described previously would be:

1. Class files in dir1.
2. Class files in JAR files in dir1.
3. Class files in dir2.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

4. Class files in JAR files in dir2.

Note: PeopleTools uses the -classpath option when it loads the JVM, which overrides the CLASSPATH environment variable. Therefore, do not use the CLASSPATH environment variable to identify third-party or custom Java classes that you want to access in the PeopleTools environment.

Note: PeopleTools does not guarantee the order in which JAR files within a directory will be added to the class path. If it is necessary to impose a search order on JAR files, then the JAR files must be in separate directories.

Like most environment variables, you can specify more than one entry in PS_CLASSPATH. On Windows, the PS_CLASSPATH entries are separated by semicolons. On Unix, they're separated by colons.

The following PS_CLASSPATH is for Windows:

```
c:\myjava;d:\myjava\com\mycompany\myproduct; . . .
```

The following PS_CLASSPATH would be for Unix:

```
/etc/myjava:/home/me/myjava/com/mycompany/myproduct: . . .
```

When developing your own classes you must be aware that most JVMs cache the class definitions. This means that even if you update the class files, a running JVM (inside an application server, for example) has already loaded and is referencing the old versions of the class files. The JVM won't pick up the new versions of the class files. You must restart the application server to make the JVM reload the updated classes.

See your system documentation for more information about setting an environment variable.

From PeopleCode to Java

In this section, we provide an overview of state management concerns and present the following examples:

- State Management Concerns.
- CreateJavaObject example.
- CreateJavaArray example.
- GetJavaClass example.

State Management Concerns

The application server is *stateless,* which means that it doesn't keep any information (state) for its clients between calls to it. For one reason, calls to the application server can use different actual servers for different calls. When you are using Java in the application server, be careful to not leave state in the JVM that would cause your application to fail if a different application server (which would use a different invocation of the JVM) was used for subsequent calls. One method to leave state in the virtual machine is to use static (class) variables.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Similar considerations to these apply using Java in Application Engine programs, though here the difficulty arises when you try to checkpoint and then restart the program. The restart starts with a JVM invocation that doesn't have any of the state you might have stored into the JVM before the checkpoint.

Variables of the type JavaObject cannot have global or component scope because of this lack of ability to save the state of these objects.

An example of this is issuing messages. When you're running with PeopleSoft Pure Internet Architecture and issue a message, the message is produced by an end-user action, so the Application Server gathers up its state to return it to the browser. This state saving attempts to save the current PeopleCode execution state, causing it to issue an error because of the JavaObject.

The solution is to not have any non-null JavaObject objects when the message is issued.

The following is a simple Java program:

```
public class PC_Java_Test{

public String pcTest(){

   String message;

   message = "PeopleCode is successfully executing Java.";

   return message;
   }
}
```

Here is the PeopleCode that calls this Java program. Note that the JavaObject is set to NULL before the message is issued.

```
&java_test = CreateJavaObject("PC_Java_Test");
&java_message = &java_test.pcTest();
&java_test = Null;
WinMessage(&java_message);
```

In SavePreChange, Workflow, or SavePostChange PeopleCode the situation is more complicated. Usually messages with a zero style parameter (no buttons other than OK and perhaps Explain, therefore no result possible except OK) are queued up by the Application Server. They are output by the browser when the service completes, so the serialization won't happen until after the PeopleCode has finished, so you won't have to set your JavaObject to null. With other kinds of messages, you must do this.

CreateJavaObject Example

The following is an example program creating a Java object from a sample program that generates a random password.

```
/* Example to return Random Passwords from a Java class */
Local JavaObject &oGpw;

/* Create an instance of the object */
&oGpw = CreateJavaObject("com.PeopleSoft.Random.Gpw_Demo");

&Q = "1";

/* Call the method within the class */
&NEW_VALUE = &oGpw.getNewPassword(&Q, PSRNDMPSWD.LENGTH);

/* This is just returning one value for now */
PSRNDMPSWD.PSWD = &NEW_VALUE;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

CreateJavaArray Example

Suppose we had a PeopleCode array of strings (&Parms) that we wanted to pass to a Java method xyz of class Abc. This example assumes that you don't know when you write the code just how many parameters you will have.

```
Local JavaObject &Abc, &RefArray;
Local array of String &Parms;

&Parms = CreateArray();

/* Populate array how ever you want to populate it */

&Abc = GetJavaObject("com.peoplesoft.def.Abc");

/* Create the java array object. */

&JavaParms = CreateJavaArray("java.lang.String[]", &Parms.Len);

/* Populate the java array from the PeopleCode array. */

&RefArray = GetJavaClass("java.lang.reflect.Array");

For &I = 1 to &Parms.Len
   &RefArray.set(&JavaParms, &I - 1, &Parms[&I]);
End-For;

/* Call the method. */
&Abc.xyz(&JavaParms);
```

GetJavaClass Example

The following example gets a system class.

```
&Sys = GetJavaClass("java.lang.System");
&Sys.setProperty("java.security.policy", "C:\java\policy");

WinMessage("The security property is: " | &Sys.getProperty("java.security.policy"))⇒
;

&Props = &Sys.getProperties();
&Props.put("java.security.policy", "C:\java\policy");
&Sys.setProperties(&Props);

WinMessage("The security property is: " | &Sys.getProperty("java.security.policy"))⇒
;
```

From Java to PeopleCode

The Java classes delivered with PeopleTools enable you to call PeopleCode from your Java program. Calling into PeopleCode works only from Java code that you have initially called from PeopleCode.

You must call PeopleCode facilities only from the same thread that was used for the call into Java. PeopleTools is not multithreaded.

You cannot call any PeopleCode facility that would cause the server to return to the browser for an end-user action, because the state of the Java computation cannot be saved and restored when the action is complete.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

Considerations When Using the PeopleCode Java Functions

SysVar Java Class

Use the SysVar Java Class to refer to System Variables, such as %Language or %DBType.

For example, %Session, becomes SysVar.Session()

Related Links

"Understanding System Variables" (PeopleTools 8.54: PeopleCode Language Reference)

SysCon Java Class

Use the SysCon Java Class to refer to system constants, such as %SQLStatus_OK or %FilePath_Absolute.

For example, %CharType_Matched becomes SysCon.CharType_Matched.

Func Java Class

Use the Func Java Class to refer to built-in functions, such as CreateRowset or GetFile.

For example, SetLanguage(LANG_CD) becomes Func.SetLanguage(LANG_CD)

Name Java Class

The Name Java Class enables you to use the PeopleSoft reserved item references. This enables you to reference pages, components, records, fieldnames, and so on.

For example, in PeopleCode you can refer to a record field using the following:

```
recname.fieldname
```

With the Name class, you can use a similar construct:

```
new PeopleSoft.PeopleCode.Name("RECNAME", "FIELDNAME");
```

Note that these must be in the exact case as the item. As all PeopleTools items are named in uppercase, that means you must use uppercase.

As another example, in PeopleCode you can refer to a page using the following:

```
PAGE.pagename
```

In Java, it would be:

```
new PeopleSoft.PeopleCode.Name("PAGE", "PAGENAME");
```

Accessing PeopleCode Objects

The existing PeopleCode classes (like Array, Rowset, and so on) have properties and methods you can access.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- PeopleCode classes have the same names, so Record becomes Record, SQL becomes SQL, and so on.
- Methods are accessed by the method name.
- The name of a property is pre-pended with either **get** or **set**, depending on whether you're reading or writing to the property.

  For example, to get the IsChanged property would be getIsChanged. To set the value for a field would be &MyField.setValue.

Here is an example of a Java program that uses PeopleCode objects to access the database:

```
/*
 * Class Test
 *
 * This code is used to test the Java/PeopleCode interface.
 *
 */

import PeopleSoft.PeopleCode.*;

public class Test {

/*
 * Test
 *
 * Add up and return the length of all the
 * item labels on the UTILITIES menu,
 * found two different ways.
 *
 */

public static int Test() {
/* Get a Rowset to hold all the menu item records. */
Rowset rs = Func.CreateRowset(new Name("RECORD", "PSMENUITEM"), new Object[]{});
String menuName = "UTILITIES";
int nRecs = rs.Fill(new Object[]{"WHERE FILL.MENUNAME = :1", menuName});

int i;
int nFillChars = 0;
for (i = 1; i <= rs.getActiveRowCount(); i++) {
String itemLabel = (String)rs.GetRow(i)
.GetRecord(new Name("RECORD", "PSMENUITEM"))
.GetField(new Name("FIELD", "ITEMLABEL"))
.getValue();
nFillChars += itemLabel.length();
}

/* Do this a different way - use the SQL object to read each menu
   item record. */

int nSQLChars = 0;
Record menuRec = Func.CreateRecord(new Name("RECORD", "PSMENUITEM"));
SQL menuSQL = Func.CreateSQL("%SelectAll(:1) WHERE MENUNAME = :2",
new Object[]{menuRec, menuName});

while (menuSQL.Fetch(new Object[]{menuRec})) {
String itemLabel = (String)menuRec
.GetField(new Name("FIELD", "ITEMLABEL"))
.getValue();
nSQLChars += itemLabel.length();
}

return nFillChars + 100000 * nSQLChars;
}
}

This can be run from PeopleCode like this:
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
Local JavaObject &Test;
Local number &chars;

&Test = GetJavaClass("Test");
&chars = &Test.Test();

&Test = Null;
WinMessage("The character counts found are: " | &chars, 0);
```

Using Application Classes From Java to PeopleCode

You call a Java program from an Application Class the same way you do using any other PeopleCode program, that is, by using one of the existing Java class built-in functions.

Calling an Application Class from a Java program has the following considerations:

- Application Classes must be accessed using the object built-in functions, such as CreateObject, ObjectDoMethod, ObjectGetProperty, and so on.
- You cannot declare a variable of type HR.Package.SomeClass in your Java program. The variable must be of type Object.
- There is no pre-pending the word ‘get’ or ‘set’ for properties. All classes, methods, and properties are passed as strings.

The following is an example of how to call an Application Class from a Java program.

This is the Java program:

```
package com.peoplesoft.pcode;
import PeopleSoft.PeopleCode.*;

public class foo {

  public foo() {
  }
  public String getString() {

    Object foo = Func.CreateObject("GTP:Foo", new Object[]{});
    return (String)Func.ObjectDoMethod((Peer)foo, "GetString", new Object[]{});
  }
}
```

The following is the Application Class Foo, in the Application Package Foo:

```
class Foo
   method GetString() Returns string;
end-class;

method GetString
   /+ Returns String +/
   Return "Hello";
end-method;
```

The following is the PeopleCode program that starts it all:

```
Local JavaObject &foo = CreateJavaObject("com.peoplesoft.pcode.foo");
GTP_PARSER.GTP_STR_RESULT = &foo.getString();
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

PeopleCode and Java Data Types Mapping

The following table describes the matching of types for resolution of overloaded Java methods and basic conversions. The first Java Type/Class is the one that is produced in the absence of any other type of information.

PeopleCode Type	***Java Type/Class***
Float	double, float
Number	double, float, byte, char, short, int, long
Integer	int, byte, char, short, long
Boolean	Boolean
String	java.lang.String
Date	java.sql.Date
Time	java.sql.Time
Date Time	java.util.Date
any kind of object	any kind of object

The following table represents the conversions done to produce the Java class java.lang.Object. In addition to these, the conversions (listed in the previous table) from String onwards are done to produce a java.lang.Object.

PeopleCode Type	***Java Type/Class***
Float, Number	java.lang.Double
Integer	java.lang.Integer
Boolean	java.lang.Boolean

The following table represents other conversions that are done as required by the signature of a Java method or constructor.

PeopleCode Type	***Java Class***
Integer, Number, Float	java.lang.Integer, java.lang.Byte, java.lang.Character, java.lang.Short, java.lang.Long, java.lang.Float, PeopleSoft.PeopleCode.intHolder, PeopleSoft.PeopleCode.doubleHolder
String	PeopleSoft.PeopleCode.StringHolder
peoplecode builtin class Xxx	PeopleSoft.PeopleCode.Xxx
JavaObject	corresponding Java object

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Considerations When Using the PeopleCode Java Functions

Some PeopleCode built-in functions can't be called from a Java program. Many of these restrictions arise because you can't serialize Java objects. Inside Java, you can't serialize and save the state of the JVM.

This means that you cannot call the following built-in functions:

- Think-time functions, such as DoCancel, Prompt, RevalidatePassword, and so on.
- Math functions, such as Abs, Cos, and Sin. Use the Java math functions instead.
- Java class functions, such as CreateJavaArray, CreateJavaObject, or GetJavaClass.
- Deprecated functions, such as SetNextPanel, PanelGroupChanged, and so on. Use the new function instead, like SetNextPage, ComponentChanged, and so on.
- PeopleCode language elements, such as Exit, Return, If, and so on.
- Cursor position, such as SetCursorPos.
- Functions that rely on specific character encoding, such as char, code, exact, codeb, and so on.
- Menu appearance functions, such as CheckMenuItem, HideMenuItem, and so on.
- Transfer functions such as Transfer or TransferPage.
- DoSaveNow isn't allowed. However, DoSave is.

When you're creating your Java program, keep the following points in mind:

- If you're starting from an online application, avoid calling anything that will wait a long time.
- If you use third-party Java that require third-party platforms, you are limiting your program to just those platforms.

When setting a null date in Java, use the following:

```
myField.SetValue("");
```

Related Links

"Understanding Restrictions on Method and Function Use" (PeopleTools 8.54: PeopleCode Developer’s Guide)

Copying Arrays of Data Between PeopleCode and Java

When PeopleCode is called from your Java program it executes what are called native methods. These methods looks like regular Java methods in their definition but are implemented in the PeopleTools layer. In order to go from Java into PeopleTools you have to use an interface called the Java Native Interface (JNI). There is a cost associated with each transition across the JNI. Using the CopyToJavaArray and the CopyFromJavaArray functions may improve your performance, as they act as a type of bulk data copy that minimizes the transition overhead.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

For example you could copy an array by copying each element using the array's Get method. However, that would require traversing the JNI twice for each element; once going into Tools and once coming back from Tools. Not only is there transition overhead but there is also conversion between object types. For example a PeopleCode string has to be converted to a Java String and vice-versa. While these two builtins do not eliminate the latter conversions, they minimize the number of transitions across the JNI.

These functions can be used when you are selecting data into a PeopleCode array and you want to copy that data into a Java array.

These functions also allow you to supply an optional parameter that specifies the list of items you want copied.

Related Links

"CopyFromJavaArray" (PeopleTools 8.54: PeopleCode Language Reference)

"CopyToJavaArray" (PeopleTools 8.54: PeopleCode Language Reference)

Considerations Working with the Java Garbage Collector

Memory is managed in the JRE by the Java garbage collector. Because PeopleTools has no control over when the Java garbage collector runs (apart from a user in their Java program calling it using `system.gc()`), PeopleTools interacts dynamically with the Java runtime garbage collector. In particular, PeopleCode objects created from a Java program (such as records, fields, and so on,) are in effect peer objects of real PeopleCode objects in PeopleTools. The release of these objects must be linked. Using the weak reference mechanism in Java, PeopleTools dynamically interracts with the Java garbage collector each time the execution thread passes through the JNI. This allows long-running Java applications in a PeopleTools context to function without having to wait for an "end of service" event for object cleanup.

There might be occasions where a Java application creates many application classes and wants to force the PeopleTools garbage collector to run. That can be achieved by calling the CollectGarbage function. This is not normally necessary.

Related Links

"CollectGarbage" (PeopleTools 8.54: PeopleCode Language Reference)

Error Handling and the PeopleCode Java Functions

Java functions throw exceptions to indicate something unusual has happened. However, all exceptions from Java called by PeopleCode are turned into fatal errors. You can catch these exception by enclosing the call to Java in a Try-Catch PeopleCode block. If you do not try to catch these exception, the PeopleCode program is terminated, and the user transaction must be canceled.

PeopleSoft recommends that you write a Java wrapper to handle errors.

Use either the All or None built-in functions to check values that are returned if you think you may call a Java method that is defined to return a string, but returns a Null object reference instead. Java Null object references are automatically converted into PeopleCode Null object references.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Accessing the Application Log File

For doing additional error handling in your application, you can access the application log file using the PeopleCode WriteToLog built-in function. For example:

```
Func.WriteToLog(SysCon.ApplicationLogFence_Level1, myLogString);
```

See "WriteToLog" (PeopleTools 8.54: PeopleCode Language Reference).

The Java Debugging Environment

To use the JPDA debugging architecture, you must do the following. These instructions are general: how you actually set up the debugger depends on your system.

To use the Java Debugging Environment (JDB):

1. Download and install a copy of JPDA.
2. Set the path for your system.

   Suppose you install JPDA in C:\jpda. Set your PATH environment variable to include C:\jpda\bin.
3. Set the path for the application server.

   For the application server, set the Domain Settings/Add to PATH to include C:\jpda\bin.
4. Set the JavaVM Options.

   Set the JavaVM Options to be something like the following (see the JPDA documentation for a more complete example):

   ```
   -Xdebug -Djava.compiler=NONE -Xnoagent -Xrunjdwp:transport=dt_socket,suspend=n⇒
   ,address=8765,server=y
   ```
5. Run the debugger.

   After starting the tools session and causing it to start the JVM, you can use the JDB command line debugger that comes with JPDA, using a command like the following:

   ```
   jdb -connect com.sun.jdi.SocketAttach:port=8765
   ```

   You can also use the (no cost) Forte for Java Community Edition IDE from Oracle or any of the Java IDEs noted on the JPDA pages.

Data Type of a Java Object

You should declare a Java object as type JavaObject. For example:

```
Local JavaObject &MyJavaClass;
```

Note: Java objects can be declared as type Local only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Scope of a Java Object

A Java object can be instantiated from PeopleCode only. This object can be used anywhere you have PeopleCode, that is, in an application class, Component Interface PeopleCode, record field PeopleCode, and so on.

PeopleCode Java Built-in Functions

"CopyFromJavaArray" (PeopleTools 8.54: PeopleCode Language Reference)

"CopyToJavaArray" (PeopleTools 8.54: PeopleCode Language Reference)

"CreateJavaArray" (PeopleTools 8.54: PeopleCode Language Reference)

"CreateJavaObject" (PeopleTools 8.54: PeopleCode Language Reference)

"GetJavaClass" (PeopleTools 8.54: PeopleCode Language Reference)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Chapter 26

Mail Classes

Understanding PeopleSoft MultiChannel Framework Mail Classes

This section discusses:

- PeopleSoft MultiChannel Framework mail classes.
- Scope of the mail classes.
- Data types of the mail classes.

PeopleSoft MultiChannel Framework Mail Classes

The PT_MCF_MAIL application package contains the following classes:

- MCFBodyPart
- MCFEmail
- MCFGetMail
- MCFHeaders
- MCFInboundEmail
- MCFMailStore
- MCFMultiPart
- MCFMailUtil
- MCFOutboundEmail
- MCFPart
- SMTPSession

Use the mail classes to develop applications to create and send emails, fetch and delete emails on the mail server, manage emails in your PeopleSoft database, and access attachments . By using the mail classes, you are not required to know the details of the GETMAILTARGET connector or the database schema.

Scope of the Mail Classes

The mail classes can be instantiated only from PeopleCode.

The mail classes can be called from a component, an internet script, or a Application Engine program.

Mail classes can be of local, global, or component scope.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Data Types of the Mail Classes

Every mail class is its own data type; that is, get mail objects are declared as data type MCFGetMail, store mail objects are declared as type MCFMailStore, and so on.

The following are the data types of the mail classes:

- MCFBodyPart
- MCFEmail
- MCFGetMail
- MCFHeaders
- MCFInboundEmail
- MCFMailStore
- MCFMailUtil
- MCFMultiPart
- MCFOutboundEmail
- MCFPart
- SMTPSession

Importing Mail Classes

The mail classes are *not* built-in classes, like Rowset, Field, Record, and so on. They are application classes. Before you can use these classes in your PeopleCode program, you must import them to your program.

An import statement names either all the classes in a package or a particular application class.

The application package PT_MCF_MAIL contains the following classes:

- MCFBodyPart
- MCFEmail
- MCFGetMail
- MCFHeaders
- MCFInboundEmail
- MCFMailStore
- MCFMailUtil
- MCFMultiPart

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- MCFOutboundEmail
- MCFPart
- SMTPSession

To import all the mail classes, use the following import statement:

```
import PT_MCF_MAIL:*;
```

Using an asterisk after the package name makes all the application classes directly contained in the named package available. Application classes contained in subpackages of the named package are *not* made available. The PT_MCF_MAIL application package contains no subpackages.

Related Links

Understanding Application Classes

Creating a Mail Object

After you've imported the mail classes, you instantiate an object of one of those classes using the constructor for the class and the Create function.

The following example creates a new instance of the MCFGetMail class, as the variable &gm, with local scope:

```
Local MCFGetMail &gm = create MCFGetMail();
```

Using the Mail Classes

This section discusses how to use the mail classes, and includes the following:

- General lifecycle of an outbound email
- Delivery status notifications and return receipts
- Priority
- MCFBodyPart and MCFEmail considerations

General Lifecycle of an Outbound Email

The following are the general steps used to create an outbound email:

1. Create an MCFOutboundEmail object
2. Set the usual properties for an email, such as the From, Subject, Recipients, and Text properties.
3. If necessary, set the parts of the email using MCFMultipart and MCFBodyPart classes.
4. Use the Send method to send the email.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The MCFPart and MCFEmail classes provide the common functionality for the MCFBodyPart and MCFOutboundEmail (and MCFInboundEmail) classes, respectively. In general, you never need to use the MCFPart or MCFEmail classes directly in your PeopleCode programs. However, in rare cases you may use these classes if you want to extend the application package.

The SMTPSession class encapsulates all the session parameters that can be set in a Simple Mail Transfer Protocol (SMTP) session. Each MCFOutboundEmail object points to one SMTPSession object. In most cases, the parameters for the SMTP session are set from values found in the application server configuration file (psappsrv.cfg). However, you can also set these parameters by creating an SMTPSession object, setting the desired parameters, then creating an MCFOutboundEmail object.

For convenience, all SMTP attributes are also directly accessible from the MCFOutboundEmail class, so you don't need to create an SMTPSession object when you're sending just one email.

When you want to send many emails in a single SMTP session, you don't have to set the SMTP session parameter in each and every email. For this case, you can create a single SMTPSession, using either the default settings or explicitly setting the desired parameters, then use the CreateOutboundEmail method of SMTPSession object to create all the MCFOutboundEmail objects. This way all the MCFOutboundEmail objects use the same SMTP session parameters. After specifying the value of all the parameters for all the MCFOutboundEmail objects, use the SendAll method of SMTPSession object to send all the emails in one SMTP session.

All the application classes mentioned above hold all the data until one of the Send methods is called. The Send methods connect to the mail server using a JavaMail API that sends the mail.

Since all communication to the mail server happens when a Send method is called, errors are only reported when the Send method returns. The return value indicates the success or the failure of the send process. In case of failure, you can query the MCFOutboundEmail application class for the details of the error. The error details are available in properties such as MessageSetNumber, MessageNumber, ErrorDescription, ErrorDetails, and so on.

Delivery Status Notification and Return Receipts

There is an SMTP extension that supports Delivery Status Notifications (DSN) defined in RFC 1891. This may or may not be supported by the user's Mail Transport Agent (MTA). The acknowledgements do not indicate whether the user reads the message, they only acknowledge receipt of the message by their mail server. It is possible that the mail server throws the message away as spam and the end user never actually receives the email. To get such notifications, set the StatusNotifyOptions and StatusNotifyReturn properties, as in the following example:

```
&email.StatusNotifyOptions  = "SUCCESS,FAILURE";
&email.StatusNotifyReturn = "HDRS";
```

You can use the IsReturnReceiptReqd property to specify if a return receipt should be sent when the mail server receives and opens the email. This property only works if the underlying SMTP server supports this feature. The following is an example of using this property:

```
&email.IsReturnReceiptReqd = True;
```

Priority

There is no SMTP standard for message priority. Most email applications use an X−Priority value of 3 for messages with "normal" priority. More important messages have lower values and less important

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

messages have higher values. In most cases, urgent messages have an X−Priority value of 1. The priority code used with the Mail classes, and set in the headers are as follows:

1. Highest Priority
2. High Priority
3. Normal
4. Low Priority
5. Lowest Priority

The default value is 3, that is, normal priority.

Different email programs render these different values in a variety of ways, usually using some kind of colored symbols or arrows.

Set the priority for an email using the Priority property. The following is an example:

```
&Email.Priority = 2;
```

MCFBodyPart and MCFEmail Considerations

Both MCFBodyPart and MCFEmail objects are used for both inbound and outbound email. The following sections specify which methods and properties are generally used for inbound, and which are used for outbound, for the different objects.

Inbound and Outbound MCFBodyPart Class Methods

All of the methods except the GetUnparsedHeaders method for the MCFBodyPart class are used with outbound email. The following methods are generally used with inbound email as well:

- GetHeader
- GetHeaderNames
- GetUnparsedHeaders

Inbound and Outbound MCFBodyPart Class Properties

The following properties are primarily used with inbound email. Note that some of these properties are also used with outbound email.

- AttachmentURL
- ContentType
- Filename
- IsAttachment
- Text

The following properties are primarily used with outbound email. Note that some of these properties are used with inbound email as well.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- ContentLanguage
- ContentType
- Description
- Disposition
- FileName
- FilePath
- FilePathType
- Multipart
- Text

Inbound and Outbound MCFEmail Class Properties

The following properties are used with inbound email. Note that most of these properties are also used with outbound email.

- From
- RefIDs
- ReplyIDs
- ReplyTo
- Sender
- Subject

The following properties are used with outbound email. Note that many of these properties are also used with inbound email.

- BCC
- BounceTo
- CC
- From
- Importance
- Priority
- Recipients
- RefIDs
- ReplyIDs
- ReplyTo

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- Sender
- Sensitivity
- Subject

Related Links

MCFBodyPart Class Methods
MCFBodyPart Class Properties
MCFEmail Class Properties

Retrieving Email From a Mail Server With the MCFGetMail Class

Use the MCFGetMail class to retrieve email from your mail server and load it in a rowset. After you have decided that an email needs to be saved to the PeopleSoft database, use MCFMailStore class.

This section covers the following topics:

- Rowset structure.
- Error messages common to all MCFGetMail methods.

Structure of Rowset Used for Email Information

The following list describes the different levels of the rowset that contains email information, and what each level contains.

Level 0

The first row at level zero is empty except for the number of rows contained within level zero and return status. The first row contains the return status for the entire batch of emails. Apart from the return status of the whole batch, each individual row has its own EMAIL_RET_STATUS. When a fatal error occurs, such as a connector size overflow, an IB overflow, or an error accessing attachments , the return status is copied to the first row. Subtle errors like unsupported encoding for a part of a individual email appear in the return status of that email only. Each row after the first row contains information about an individual email, such as the header information, the time received, and so on.

Level 1

Level one is where the parts of an email reside. The level one child rowsets are linked to the parent rowset in level zero by the MCF_EMAIL_ID, a unique ID assigned by PeopleSoft.

Note: Multipurpose Internet Mail Extensions (MIME) is an Internet standard for representing multipart and multimedia data in email. It enables email to be exchanged between different email systems. The parts may be nested. PeopleSoft embeds the JavaMail API to implement support for the MIME standard. However, all parts of an email are represented in PeopleSoft as level one rowsets, regardless of the hierarchy that existed in the original email.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The following table describes the fields within the rowset at level zero.

Field	***Description***
MCF_ATTACH_LIST	Contains a list of all the file names that are attachments for a particular email. Multiple items are separated by a semicolon (;).
MCF_IS_ATT_URL	This is a Boolean value indicating whether the email body is located in the MCF_EMAIL_TEXT or in the attachment directory. If this value is 1 (true), the email body is located in the attachment directory and can be accessed using the MCF_ATT_URL value. If this value is 0 (false), then the email body is located in MCF_EMAIL_TEXT.
MCF_ATT_URL	This URL enables you to view an attachment. This URL is viewable only if the corresponding email has been authorized for the current user. This value is a relative URL. The URL becomes fully qualified only after the rowset has been saved to the PeopleSoft database and then later retrieved using the MCFMailStore class. The following is a sample URL: http://sundance.peoplesoft.com/PSAttachServlet/ps/mcfdev1/39297_31030554591_1.gif?contentType=image/gif *mcfdev1* is the mail user name. *39297__31030554591_1.gif* is the file name in the attachment directory. *contentType* is used by the browser to open a viewer associated with this type. The filename of the downloaded attachment is constructed by using the email's unique ID and the part number. ***Warning!*** Downloading the same emails twice from the mail server overwrites the associated files in the directory. If the same email is stored twice in the PeopleSoft database, the system creates two separate rows. If you delete either one of these rows, the system deletes the associated files in the directory. To avoid this situation, delete emails from the mail server after you have retrieved them. See AuthorizeEmailAttach.
MCF_IBNODE_NAME	Identifies the name of the Integration Broker node that received the email, such as MCF_GetMail. The system uses this value to construct the fully qualified URL required for viewing attachments.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Field	*Description*
MCF_ATTACH_SIZES	Indicates the size of the attachments associated with an email. Multiple values are separated by a semicolon (;). The attachment sizes appear in the same order as the file names in MCF_ATTACH_LIST.
MCF_EMAIL_FROM	Indicates the email account that sent the email, such as jsmith@company.com.
MCF_DTTM_RECV	Indicates the time that the mail server received the email. ***Warning!*** If you are using a Post Office Protocol 3 (POP3) mail server, this field may not be populated.
MCF_OFFSET_RECV	Indicates the time zone of the mail server that received this email. **Note:** This field contains the time zone of the integration gateway used to fetch this email.
MCF_DTTM_SENT	Indicates the time that the email was sent.
MCF_OFFSET_SENT	Indicates the time zone of the mail server that sent this email. **Note:** Currently, this field contains the time zone of the integration gateway used to fetch this email.
MCF_DTTM_SAVED	Records the date and time that the PeopleSoft system saved an email to the PeopleSoft database. If you use a POP3 mail server, PeopleSoft recommends using this value as the base, or starting point, for any time-sensitive transactions.
MCF_EMAIL_SENDER	This is the reply to address. This supports a mail feature in which users can send an email from one account, but when the receiver chooses to reply, the system addresses the email to a different account. For instance, sales representatives may send an email from their personal email account, as in tom_sawyer@company.com, but when customers reply, the email is addressed to sales@company.com.
MCF_EMAIL_TEXT	Represents the text that was delivered in the body of the email. Before the email is downloaded, this field contains the body of the email. After the email has been downloaded, this field is blank. Check the MCF_IS_ATT_URL value to determine whether your email text resides in this field or the attachment directory. PeopleSoft relies on the originating email client embedding encoding information to determine character set. For example, Content-type: text/plain; charset=Big5

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Field	*Description*
MCF_NOTIFY_CC	Indicates the parties who were copied (carbon copied) on the email. Multiple addresses are separated by a semicolon (;).
MCF_NOTIFY_TO	Indicates the parties who received the email. Multiple addresses are separated by a semicolon (;).
MCF_UID_LIST	This contains a unique identifier created by POP3 or an IMAP4 mail server. It is guaranteed to be unique within a particular mail box. **Note:** The DeleteEmail method also uses this value when deleting a list of emails. When deleting emails, this field can contain multiple values separated by a space.
MCF_WL_SUBJECT	Contains the subject of the email. A maximum of 254 characters is allowed. PeopleSoft relies on the originating email client embedding encoding information to determine character set. For example: `Email Subject:  Subject: =?Big5?B?uvuqwLBPqsy67qZYs/i+yS+kpLDqqXik6Ldztdg=?= =?Big5?B?uvSlSKTOpEilwbr0MzCk6bVvqu2q+KTloUGkaqRP?==?Big5?B?scCxUqa/v0GlwQ==?=` where ?Big5? is the prefixed encoding information.
MCF_RET_STATUS	Represents where the system stores the return status of a particular mail class method.
MCF_EMAIL_STATUS	This field is not currently used.
MCF_NUMROWS	Indicates the number of rows (level one child rowsets) that contain parts of a particular email. For example, if an email has two child rowsets associated with it at level one, this value would be 2. **Note:** For row one of the level zero rowset, this field reflects the number of emails in this rowset. If you fetch 10 emails, the rowset contains 11 rows, but the MCF_NUMROWS value in row 1 equals 10. Row 1 of the level zero rowset never contains an email.
MCF_EMAIL_MSG_ID	This is the globally unique identifier for this email. This ID is generated by the mail server that sent this email.
MCF_REPY_TO	This is the reply to field.
MCF_REF_IDS	Use this field for the reference header fields of the message.
MCF_REPLY_IDS	This value contains the email address that the email can reply to.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Field	Description
MCF_MSG_SIZE	Represents the total size of the entire email. This value includes the sizes of attachments.
MCF_EMAIL_LANG_CD	This value reflects the language code of the Integration Broker node that received this email. **Note:** PeopleSoft recommends setting up email accounts that are dedicated to one language such as, support_french@company.com and support_english@company.com. This enables you to anticipate the language of the email you read into your system. In turn, configure separate Integration Broker nodes to handle each of the languages you support. There are no language recognition procedures within the PeopleSoft system.
MCF_USER	Represents the user account (mail box) on the mail server that received the email.
MCF_SERVER	Represents the mail server that received the email.
MCF_ERROR_COUNT	Used to return the number of messages that caused errors during processing on the target connector.
MCF_QUARANTINE_COUNT	Used to return the number of messages that caused errors during processing on the target connector and were successfully moved to the quarantine folder (This value is always 0 for POP3).
MCF_CONTENT_TYPE	This is the content type of the email itself. For example, a content type could be text/plain, text/html, or multipart/alternative.
MCF_EMAIL_HEADERS	This field is used to return the email message headers. It contains the raw headers in RFC 822 format. The MCFHeaders class can be used to parse the contents of this field.

The following table describes the fields within the rowset at level one. This rowset contains the parts of the email.

Field	Description
MCF_ATT_URL	This is the URL of an associated attachment in the attachment directory. This URL is a relative value when this rowset is first received from the mail server and stored in the database. It only becomes a fully qualified URL once you retrieve the rowset using the MCFMailStore class. Keeping the URL a relative value enables you to make changes within the system without breaking the URL.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Field	*Description*
MCF_IS_ATT_URL	This is a Boolean value indicating whether the email part is located in the MCF_EMAIL_TEXT or on the attachment directory. If this value is 1 (true), the email part can be accessed using the MCF_ATT_URL value. If this value is 0 (false), then the email part is located in MCF_EMAIL_TEXT.
MCF_FILENAME	Represents the file name for an attachment, such as revenue.xls or resume.doc. The file name can be used as a read-only label on the page used by end users to view attachments. For example, the file name may appear next to the link that opens the attachment. **Note:** Not all parts have file names.
MCF_FILE_DATA	This field is not currently used.
MCF_EMAIL_HEADERS	This field is used to return the email part headers. It contains the raw headers in RFC 822 format. The MCFHeaders class can be used to parse the contents of this field.
MCF_EMAIL_TEXT	Contains the text content of the email part.

Note: Although the same rowset structure is used for retrieving email from the mail server and for retrieving email from the PeopleSoft database, not all of the fields apply to each situation. For example, when you first retrieve email from the mail server, the rowset does not contain the fully qualified URL to any attachments.

Note: After an email is saved to the database, always use the methods in the MailStore application package class to access the email. Do not read directly from the mail tables.

Error Messages Returned by MCFGetMail Class Methods

The GetMail Integration Broker connector returns message codes denoting status. These return codes apply to all the methods within the MCFGetMail class. The following are returned in MCF_RET_STATUS field, and by the Status property.

0 Success.

1 Connector size overflow.

The size of the email requested exceeds the value in MCF_EmSz_Conn.

The system returns the header information for this email with the return status set to 1.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

	See "Configuring Email Channel in PeopleSoft Integration Broker" (PeopleTools 8.54: MultiChannel Framework).
2	Integration Broker threshold size overflow. The size of the email requested exceeds the value in MCF_EmSz_IB. This happens when the size of the XML message constructed to transfer emails from the mail server to the database exceeds the threshold value. If there are any more emails to be processed in the current batch, the system does not fetch them from the mail server. For example, suppose your program fetches 20 emails at a time from the mail server, and this error occurred on the tenth email. In this case, the system processes the tenth email, but emails 11–20 are still be on the mail server. See "Configuring Email Channel in PeopleSoft Integration Broker" (PeopleTools 8.54: MultiChannel Framework).
3	Cannot delete all the messages from the mail server.
4	Connecting to the mail server failed.
5	The attachments to be deleted were not found.
6	At least one attachment cannot be deleted.
7	Unsupported encoding.
8	Cannot write to the attachment directory.
9	Messages were downloaded to directory and deleted from mail server. This status code occurs when an exception occurs in Integration Broker while storing the emails to the database. The exception might occur due to invalid characters in the email. If the email is left on the mail server, the same exception will occur repeatedly, preventing you from fetching further emails. Because the header might contain these invalid characters also, only MCF_RET_STATUS, MCF_MSG_SIZE, MCF_UID_LIST, date time fields, MCF_IS_ATT_URL, MCF_ATT_URL are set. There is no way to determine which email caused the exception, so the system writes all the emails to the directory. All the emails in the batch are deleted from the mail server.
10	Email content error. One example of this is unsupported encoding.
11	Returned if attempting to create a mail server folder while using the POP3 protocol.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

12	Folder creation on mail server failed.
13	GetMail connector internal error.

See Status.

Mail Classes Constructors

The following section provides examples of the mail class constructors.

MCFBodyPart

Example

```
Local PT_MCF_MAIL:MCFBodyPart &text = create PT_MCF_MAIL:MCFBodyPart();
```

MCFGetMail

Example

```
Local MCFGetMail &gm = create MCFGetMail();
```

MCFOutboundEmail

Example

```
Local PT_MCF_MAIL:MCFOutboundEmail &eMail =
create PT_MCF_MAIL:MCFOutboundEmail();
```

MCFMailStore

Example

```
Local MCFGetMail &sm = create MCFMailStore();
```

SMTPSession

Example

```
Local PT_MCF_MAIL:SMTPSession &commonSession =
create PT_MCF_MAIL:SMTPSession();
```

MCFBodyPart Class

Use the MCFBodyPart class to send email with attachments, HTML, or other non-standard text information.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

MCFBodyPart Class Methods

In the following, we discuss the MCFBodyPart class methods. The methods are described in alphabetical order.

AddHeader

Syntax

AddHeader(*HeaderName*, *HeaderValue*)

Description

Use the AddHeader method to add a header to the body part. This method allows for email server customizations. Some commonly used headers are already exposed as properties, such as ContentType and ContentLanguage. Advanced applications can adapt this technique to meet their own requirements. These headers can be either standard SMTP headers or custom headers starting with "X-".

Parameters

HeaderName	Specify the name of the header that you want to add. This parameter takes a string value.
HeaderValue	Specify the actual text of the header, as a string.

Returns

None.

Example

```
   Local PT_MCF_MAIL:MCFOutboundEmail &email = create PT_MCF_MAIL:MCFOutboundEmail(⇒
);
   Local string &TestName = "Custom Header";

   &email.From = &def.From;
   &email.Recipients = &def.Recipients;
   &email.SMTPServer = &def.SMTPServer;
   &email.Subject = &TestName;
   &email.Text = &TestName;

   &email.AddHeader("X-Mailer", "CRM Sales Application 8.9 SP2");
   &email.AddHeader("X-Mailer", "CRM Sales Application 8.9 SP3");
   &email.AddHeader("X-Mailer", "CRM Sales Application 8.9 SP4");
   &res = &email.Send();
```

Related Links

GetHeader

GetHeaderCount

GetHeaderName

GetHeaderNames

GetHeaderValues

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GetUnparsedHeaders

GetHeader

Syntax

GetHeader(*HeaderName*)

Description

Use the GetHeader method to return the value of the specified header.

This method is primarily used with inbound email messages.

Parameters

HeaderName	Specify the name of the header that you want to access the values for, as a string. The matching of header names is case insensitive.

Returns

An array of string containing the header values. If the header is not present, returns an array of length zero.

Related Links

Understanding Arrays
AddHeader
GetHeaderCount
GetHeaderName
GetHeaderNames
GetHeaderValues
GetUnparsedHeaders

GetHeaderCount

Syntax

GetHeaderCount()

Description

Use the GetHeaderCount method to return the number of headers.

Parameters

None.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

An integer, representing the number of headers present.

Related Links

AddHeader
GetHeader
GetHeaderName
GetHeaderNames
GetHeaderValues
GetUnparsedHeaders

GetHeaderName

Syntax

```
GetHeaderName(Index)
```

Description

Use the GetHeaderName to return the name of the header that is located at *Index*.

Parameters

Index	Specify the numeric position of the header you want to access.

Returns

A string.

Related Links

AddHeader
GetHeader
GetHeaderCount
GetHeaderNames
GetHeaderValues
GetUnparsedHeaders

GetHeaderNames

Syntax

```
GetHeaderNames()
```

Description

Use the GetHeaderNames method to return an array containing the names of all the headers.

This method is primarily used with inbound email messages.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

None.

Returns

An array of string.

Related Links

AddHeader
GetHeader
GetHeaderCount
GetHeaderName
GetHeaderValues
GetUnparsedHeaders

GetHeaderValues

Syntax

GetHeaderValues(*Index*)

Description

Use the GetHeaderValues method to return the value for the header located at the position specified by *Index*.

Parameters

Index	Specify the numeric position of the header whose value you want to access.

Returns

An array of string.

Related Links

AddHeader
GetHeader
GetHeaderCount
GetHeaderName
GetHeaderNames
GetUnparsedHeaders

GetUnparsedHeaders

Syntax

GetUnparsedHeaders()

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the GetUnparsedHeaders method to return all of the headers in the body part without any formatting occurring.

Parameters

None.

Returns

A string containing the headers.

Related Links

AddHeader
GetHeader
GetHeaderCount
GetHeaderName
GetHeaderNames
GetHeaderValues

SetAttachmentContent

Syntax

```
SetAttachmentContent({FilePath | FileURL}, FilePathType, FileName, FileDescr,
OverrideContentType, OverrideCharset)
```

Description

Use the SetAttachmentContent method to specify the body (content) of this body part from a file.

Use the *FilePathType* parameter to specify if the file path is relative or absolute. If it's an absolute path, the file path could be a file on the local machine, a network folder, or a fully-qualified URL.

Parameters

FilePath | FileURL

You can either specify the file path to the file, or a URL to the file.

Depending on the *FilePathType* parameter, you may specify either a relative or absolute file path to the file.

This parameter should include the file name and extension of the file.

If you specify a URL address where the file is located, it must be an absolute URL. This URL should include the actual name of the file. If you specify a URL address, you must specify the *FilePathType* parameter as %FilePath_Absolute.

FilePathType

Specify the path type for the file, whether it is an absolute or relative path. The values are:

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- %FilePath_Absolute — the file path is an absolute path.
- %FilePath_Relative — the file path is a relative path.

FileName Specify the name of the file that you want to attach, as a string. You must include the file extension as well.

Description Specify a description of the file.

OverrideContentType The system detects the content type of the attachment using the file location and name. Specifying *OverrideContentType* overrides the system detected content type.

The character set can also be included in the ContentType. For example, “text/plain; charset=US-ASCII”

OverrideCharset Specify a character set to be used to override the existing character set.

Returns

None.

Example

The following uses an absolute path to set the content:

```
&image.SetAttachmentContent("///file:C:/User/Documentum/XML%20Applications/proddoc/⇒
peoplebook_upc/peoplebook_upc.dtd",
 %FilePath_Absolute, "sample.jpg", "This is a sample image!", "", "");
```

The following uses a relative path to set the content:

```
&attach1.SetAttachmentContent("Ocean Wave.jpg", %FilePath_Relative,
"Ocean Wave.jpg", "Ocean Wave", "", "");
```

The following uses a URL to set the content:

```
&attach1.SetAttachmentContent("http://www.yahoo.com/members_agreement",
 %FilePath_Absolute, "hotmail.htm", "Hotmail Home page", "", "");
```

Related Links

AddAttachment

MCFBodyPart Class Properties

In this section we discuss the MCFBodyPart class properties. The properties are described in alphabetical order.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

AttachmentURL

Description

Use this property to specify the URL for the attachment for this body part, as a string.

The URL must be an absolute URL.

This property is read-write.

Charset

Description

Use this property to specify the character set for the text or the attachment.

You can also specify this property using the SetAttachmentContent method, or the ContentType property.

This property is read-write.

Related Links

ContentType
SetAttachmentContent

ContentType

Description

Use this property to specify the content type of this body part.

You can specify the content type with the SetAttachmentContent method.

You can also use this property to specify the character set. For example, “text/plain; charset=US-ASCII”.

This property is read-write.

Related Links

SetAttachmentContent
Charset

Description

Description

Use this property to specify a description of the attachment. You should only use this property if the content is an attachment.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Disposition

Description

Use this property to specify how the body part is presented in the received mail.

Some email clients ignore the setting of this property and present body parts either inline or as file attachments.

Valid values for this property are:

Value	*Description*
Attachment	The body part is shown as a file attachment.
Inline	The body part is shown in the body itself.

This property is read-write.

Filename

Description

If you are adding an attachment to the email, use this property to specify the name of the file.

PeopleSoft recommends that you keep the file extension specified with this property the same as the original extension found in the file path, otherwise client applications may not be able to display it properly.

This property is read-write.

FilePath

Description

Specify the path for the file that contains the contents of this email.

Whether this is a relative or absolute path depends on the FilePathType property.

You can also specify a URL to the file using this property, if the FilePathType property is specified as %FilePath_Absolute.

If you specify a value for this property, the ‘Text’ content is ignored.

This property is read-write.

Related Links

FilePathType

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

FilePathType

Description

Use this property to specify whether the path specified with the FilePath property is a relative or absolute path. The values for this property are:

Value	*Description*
%FilePath_Relative	The file path specified with the FilePath property is a relative path.
%FilePath_Absolute	The file path specified with the FilePath property is either an absolute path to a file, or a URL to a file.

If you specify a relative path, the file must be available in the FILES folder of application server folder.

If you specify an absolute path, the file could be on the local machine, in any network folder, or a URL.

This property is read-write.

IsAttachment

Description

This property indicates if the body part is an attachment or not. This property returns a Boolean value: true if it is an attachment, false otherwise.

This property is read-only.

MultiPart

Description

A bodypart can contain simple text, one attachment, or a MultiPart object.

If you have assigned a MultiPart object using this property, the text and attachment related properties are ignored.

This property is read-write.

Example

```
Local PT_MCF_MAIL:MCFMultipart &mp = create PT_MCF_MAIL:MCFMultipart();
&mp.SubType = "alternative; differences=Content-type";

&mp.AddBodyPart(&text);
&mp.AddBodyPart(&html);

&email.MultiPart = &mp;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Text

Description

Use this property to specify the text for the email.

Use the SetAttachmentContent method to specify image or other types of attachments. For a more complex bodypart, build a multipart and set the Multipart property of MCFBodyPart.

This property is read-write.

Related Links

SetAttachmentContent

MCFEmail Class

This class inherits many properties from the MCFPart class, and is the superclass class for both the MCFOutboundEmail and MCFInboundEmail classes. Generally, you only use the MCFOutboundEmail and MCFInboundEmail classes. You should only use the MCFEmail class if you are extending the PT_MCF_MAIL application package.

MCFEmail Class Properties

In this section, we discuss the MCFEmail class properties. The properties are discussed in alphabetical order.

BCC

Description

Use this property to specify comma-separated list of addresses of all the blind carbon copy recipients of this email. (A blind carbon copy is a copy of the email that contains all of the text of the email, but does not show any of the other email addresses to which this email was sent.)

This property is read-write.

Related Links

CC

BounceTo

Description

Use this property to specify the email address the system should direct all bounced mail to.

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

CC

Description

Use this property to specify a comma-separated list of addresses that copies of this email are to be sent to (carbon copy.)

This property is read-write.

Related Links

BCC

From

Description

Use this property to specify the email address of the person sending the email.

You can specify more than one address as from in a comma-separated list.

This property is read-write.

Related Links

Recipients
ReplyTo
Sender

Importance

Description

Use this property to specify the value of the importance header field.

The importance can be set to the following:

- low
- normal
- high

If the Priority property is not set, the system automatically sets it to the corresponding values like 5, 3 and 1.

This property is read-write.

Priority

Description

Use this property to specify the priority of this email.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The values are:

1. Highest Priority
2. High Priority
3. Normal
4. Low Priority
5. Lowest Priority

The default value is 3, that is, normal priority.

This value set with this property is used to set to a header X-Priority field, as this is the most common but non-standard field to show priority. In addition, the corresponding values are set in two header fields: X-MSMail-Priority and Priority. The headers X-Priority or X-MSMail-Priority are set to the corresponding value only if the user does not specify a value.

This property is read-write.

Recipients

Description

Use this property to specify the email addresses of all the main recipients to whom the email is being sent. All the addresses are specified in a comma-separated string.

This property is read-write.

RefIDs

Description

Use this property to specify a value for the REFERENCES header field of the message.

This property is read-write.

ReplyIDs

Description

Use this property to specify a value for the IN-REPLY-TO header field of the message.

This property is read-write.

ReplyTo

Description

Use this property to specify the email address where the reply should be sent. You do not need to specify a value for this property if the value is the same as the From property.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-write.

Related Links

From

Sender

Description

Use this property to specify the address of the author of the message. You do not need to specify a value for this property if the value for the From property is the same.

This property is read-write.

Related Links

From

Sensitivity

Description

Use this property to specify the value of the sensitivity header field.

The values are:

- personal
- private
- company-confidential

This property is read-write.

Subject

Description

Use this property to specify the subject of the email. A subject can only contain 254 characters.

This property is read-write.

Text

Description

Use this property to specify the text of the email.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

MCFGetMail Class Methods

This section discusses MCFGetMail class methods.

CreateQuarantineFolder

Syntax

```
CreateQuarantineFolder()
```

Description

Use the CreateQuarantineFolder method to create a quarantine folder on the server. Specify the name of the folder using the QuarantineFolder property

Parameters

None.

Returns

A Boolean value; true if the folder is created, or if it already exists on the server, false otherwise.

Related Links

QuarantineFolder
QuarantineCount

GetCount

Syntax

```
GetCount()
```

Description

Use the GetCount method to determine the total number of emails currently stored in a particular email account.

This method does not distinguish between read and unread emails.

This method uses the connection properties set by SetMCFEmail.

If you want to determine the number of emails for an account, and to set your own connection properties, use the GetEmailCount method instead.

Parameters

None.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

Returns the total number of emails stored on the mail server for a particular email account. If the method returns –4, the system could not connect to the mail server using the user name and password passed in the parameter list.

Related Links

GetEmailCount
SetMCFEmail

GetEmailCount

Syntax

GetEmailCount(*user*, *password*, *server*, *node*)

Description

Use GetEmailCount to determine the number of emails currently stored in a particular email account. GetEmailCount does not distinguish between read and unread email. You can use this value to set limits on loops in your program.

If you want to determine the number of emails for an account using the connection properties set with SetMCFEmail, use the GetCount method instead.

Parameters

user	The user name on the mail server, such as “support” or “john_doe”.
password	The password associated with the specified user name.
server	The name of the mail server handling the specified user account.
node	The Integration Broker node on which the request runs.

Note: If the value of any of these parameters is null, the method uses default values stored on the specified node. If the node is not specified, Integration Broker returns an error.

Returns

Returns the total number of emails stored on the mail server for a particular email account. If the method returns –4, the system could not connect to the mail server using the user name and password passed in the parameter list.

Example

```
Local number &email_count;

&email_count = &gm.GetEmailCount(&username, &passwd, &mailserver,
&node);
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

GetCount

SetMCFEmail

ReadAllEmailHeadersWithAttach

Syntax

ReadAllEmailHeadersWithAttach(*user*, *password*, *server*, *node*)

Description

Use ReadAllEmailHeadersWithAttach to read the headers of all of the emails and a list of associated attachments that are currently stored on the mail server for a particular email account. The details about the emails are returned in the level zero rowset. The actual emails and any associated attachments *are not* returned.

Use this method as a screening method to determine whether to store an email in your PeopleSoft system. For example, if you determine that an email is junk mail, you could delete it from your mail server. After you determine the allowable email through header information, you can retrieve the physical email and attachments of the allowable emails.

Parameters

user	The user name on the mail server, such as “support” or “john_ doe”.
password	The password associated with the specified user name.
server	The name of the mail server handling the specified user account.
node	The Integration Broker node on which the request runs.

Note: If the value of any of these parameters is null, the method uses default values stored on the specified node. If the node is not specified, Integration Broker returns an error.

Returns

This method returns rowsets containing email headers.

Example

```
import PT_MCF_MAIL:*;

Local MCFGetMail &gm;

Local Rowset &emails_rs;

&emails_rs = &gm.ReadAllEmailHeadersWithAttach(&username, &passwd, &mailserver
&node);
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ReadEmails

Syntax

ReadEmails(*Count*)

Description

Use the ReadEmails method to read the specified number of emails for this mailbox.

This method uses the connection properties set by SetMCFEmail.

The overall status of the success of this method is available in the Status property.

Parameters

Count	Specify the number of emails you want to read.

Returns

An array of MCFInboundEmail.

Related Links

MCFInboundEmail Class Methods
Status

ReadEmailsWithAttach

Syntax

ReadEmailsWithAttach(*User*, *password*, *server*, *node*, *count*)

Description

The ReadEmailsWithAttach method reads the number of emails specified by *count* for a particular user account. If attachments are associated with an email, this method reads the attachments as well.

Parameters

User	Specify the user account that contains the emails you want to access, such as “support” or “john_doe”.
password	The password associated with the specified user name.
server	The name of the mail server handling the specified user account.
node	The Integration Broker node on which the request runs.
count	Specifies the number of emails to read. If count = 0, the method reads *all* the emails of the user account. If count > 0, the method reads the number specified. For example, if count = 10, the method reads 10 emails.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Note: If the value of any of these parameters is null, the method uses default values stored on the specified node. If the node is not specified, Integration Broker returns an error.

Returns

This method returns an email within a rowset. level one of the rowset contains the email parts. level zero row 1 only contains values for MCF_NUMROWS and MCF_RET_STATUS.

Example

```
import PT_MCF_MAIL:*;

Local MCFGetMail &gm;

Local Rowset &emails_rs;

&emails_rs = &gm.ReadEmailsWithAttach(&username, &passwd, &mailserver
&node, &email_count);
```

Related Links

ReadEmailWithAttach

ReadEmailsWithUID

Syntax

ReadEmailsWithUID(*UID*)

Description

Use the ReadEmailsWithUID method to read and return an email based on a unique identifier *UID*. This method uses the connection properties set by SetMCFEmail. Emails that have an attachment are also read.

Parameters

UID_List The UID is the unique identifier of the email. This parameter is only unique within a particular user account. POP3 and IMAP 4 mail servers automatically create a unique identifier for an email when the server receives the email. The list can contain multiple values, each separated by a space.

Returns

A reference to an array of MCFInboundEmail.

Related Links

MCFInboundEmail Class Methods

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ReadEmailWithAttach

Syntax

ReadEmailWithAttach(*User*, *password*, *server*, *node*, *UID*)

Description

Use the ReadEmailWithAttach method to read and return an email based on a unique identifier (*UID*) for the specific email to be read. If attachments are associated with this email, ReadEmailWithAttach fetches those as well.

Parameters

user The user name on the mail server, such as “support” or “john_doe”.

password The password associated with the specified user name.

server The name of the mail server handling the specified user account.

node The Integration Broker node on which the request runs.

UID The unique identifier of the email. This parameter is only unique within a particular user account. POP3 and IMAP 4 mail servers automatically create a unique identifier for an email when the server receives the email.

You may specify more than one UID, each separated by a space.

Note: If the value of any of these parameters is null, the method uses default values stored on the specified node. If the node is not specified, Integration Broker returns an error.

Returns

This method returns an email within a rowset. level one of the rowset contains the email parts. level zero row 1 only contains values for MCF_NUMROWS and MCF_RET_STATUS.

Example

```
import PT_MCF_MAIL:*;

Local MCFGetMail &gm;

Local Rowset &emails_rs;

&emails_rs = &gm.ReadEmailWithAttach(&username, &passwd, &mailserver, &node, &UID);
```

Related Links

ReadEmailsWithAttach

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ReadHeaders

Syntax

ReadHeaders()

Description

Use the ReadHeaders method to read the headers of all emails currently on the server. This method also returns the attachment information for all emails (names and sizes.)

This method uses the connection properties set by SetMCFEmail.

The overall success of the method is available using the Status property.

Parameters

None.

Returns

An array of MCFInboundEmail objects.

Related Links

MCFInboundEmail Class Methods
SetMCFEmail

RemoveEmail

Syntax

RemoveEmail(*user*, *password*, *server*, *node*, *UID list*)

Description

Based on values in the unique identifier list, RemoveEmail deletes emails from the user account on the mail server. It is important to delete emails from the mail server once they are read into PeopleSoft. If you do not delete emails from the mail server after they are read into PeopleSoft, the rowset contains the same collection of email the next time you retrieve email from the mail server.

Parameters

user	The user name on the mail server, such as “support” or “john_ doe”.
password	The password associated with the specified user name.
server	The name of the mail server handling the specified user account.
node	The Integration Broker node on which the request runs.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

UID list The UID list contains the unique identifier values for the emails that need to be deleted from the mail server. The list can contain multiple values separated by a space.

Note: If the value of any of these parameters is null, the method uses default values stored on the specified node. If the node is not specified, the Integration Broker returns an error.

Returns

A Boolean value, indicating the status of the deletion process. If the email has been successfully, this method returns True. Otherwise the method returns False.

Example

```
Local MCFGetMail &GM;
Local boolean &del_status;
Local string &uid_list = "";
Local string &msg_str;

   If (&uid_list <> "") Then
      &del_status = &GM.RemoveEmail(&user, &password, &server, &ibnode, &uid_list);
      &msg_str = "Email(s) deleted from the Mail Server with UID = " | &uid_list;
      MessageBox(0, "", 0, 0, &msg_str);
   End-If;
```

Related Links

RemoveEmails

RemoveEmails

Syntax

RemoveEmails(*UID_List*)

Description

Use the RemoveEmails method to delete emails from an account on the mail server, based on the *UID_list*. It is important to delete emails from the mail server once they are read into PeopleSoft. If you do not delete emails from the mail server after they are read into PeopleSoft, the rowset contains the same collection of email the next time you retrieve email from the mail server.

Parameters

UID_List The UID list contains the unique identifier values for the emails that need to be deleted from the mail server. The list can contain multiple values separated by a space.

Returns

An array of string containing UIDs of the messages that were successfully removed, separated by semicolons.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

RemoveEmail

SetMCFEmail

Syntax

SetMCFEmail(*user*, *password*, *server*, *node*)

Description

Use the SetMCFEmail method to set the connection properties for subsequent method calls.

This method is a shortcut for setting the UserId, Password, MailServer, and IBNode properties.

Parameters

user	The user name on the mail server, such as “support” or “john_ doe”.
password	The password associated with the specified user name.
server	The name of the mail server handling the specified user account.
node	The Integration Broker node on which the request runs.

Note: If the value of any of these parameters is null, the method uses default values stored on the specified node. If the node is not specified, the integration broker returns an error.

Returns

None.

Related Links

GetCount
ReadEmails
ReadEmailsWithUID
ReadHeaders

MCFGetMail Class Properties

In this section we discuss the MCFGetMail class properties. The properties are described in alphabetical order.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

AttachmentRoot

Description

Use this property to specify the root directory where the attachments are stored. If not specified, the value from the node is used.

Valid metastrings that can be included in the value for this property are:

%CURRDATE%	Current date in YYYYMMDD format
%CURRHOUR%	Current hour in 24–hour format (00-23)
%DBNAME%	Current value of %DbName system variable.
%OPRID%	Current value of %UserId system variable.

This property is read-write.

Example

To have the attachment root directory change hourly, you could use the following code example:

```
&MyEmail.AttachmentRoot = "c:\temp\%CURRDATE%\%CURRHOUR%\";
```

ContentTypes

Description

Use this property to specify content types that should be returned in the message or part text rather than stored in the directory that contains the attachments. Specify content types in a comma separated list. For example: `"text/html,text/xml"`.

Note: `"Text/plain"` is always returned in the text field and does not need to be included.

If not specified, the value from the node is used.

This property is read-write.

ErrorCount

Description

This property returns the number of messages that caused errors during processing on the target connector.

You should use this property after you use the ReadHeaders, ReadEmails, ReadEmailsWithUID, or RemoveEmails methods.

This property is read-only.

Related Links

ReadHeaders

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ReadEmails
ReadEmailsWithUID
RemoveEmails

IBNode

Description

This property returns the name of the Integration Broker node on which a request ran, such as MCF_GetMail.

This property is set by the SetMCFEmail method. It is used by ReadHeaders, ReadEmails, ReadEmailsWithUID, RemoveEmails, and CreateQuarantineFolder methods.

This property is read-write.

Related Links

ReadHeaders
ReadEmails
ReadEmailsWithUID
RemoveEmails
CreateQuarantineFolder

MailServer

Description

This property returns the name of the mail server that received the email.

This property is set by the SetMCFEmail method. It is used by ReadHeaders, ReadEmails, ReadEmailsWithUID, RemoveEmails, and CreateQuarantineFolder methods.

This property is read-write.

Related Links

ReadHeaders
ReadEmails
ReadEmailsWithUID
RemoveEmails
CreateQuarantineFolder

Password

Description

This property returns the password associated with the userID that was used to get the email.

This property is set by the SetMCFEmail method. It is used by ReadHeaders, ReadEmails, ReadEmailsWithUID, RemoveEmails, and CreateQuarantineFolder methods.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-write.

Related Links

ReadHeaders
ReadEmails
ReadEmailsWithUID
RemoveEmails
CreateQuarantineFolder

QuarantineCount

Description

This property returns the number of email messages that caused errors during processing on the target connector and were successfully moved to the quarantine folder.

This property is valid after calls to ReadHeaders, ReadEmails, ReadEmailsWithUID, and RemoveEmails.

This property is read-only.

Related Links

QuarantineFolder
ReadHeaders
ReadEmails
ReadEmailsWithUID
RemoveEmails

QuarantineFolder

Description

Use this property to specify the name of the quarantine folder. If not specified, the value from the node will be used.

The name must adhere to whatever naming restrictions are imposed by the mail server in use. There is no built-in validation of the folder name.

The following types of errors can cause an email to be moved to the quarantine folder:

- Connector size overflow.
- Unsupported encoding.
- Unknown Java exception.
- Javamail content error.
- No attachment directory.
- Mail parse exception.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-write.

Related Links

QuarantineCount

Status

Description

This property returns the status of the last mail server operation.

See Error Messages Returned by MCFGetMail Class Methods.

This property is valid after calls to ReadHeaders, ReadEmails, ReadEmailsWithUID, and RemoveEmails.

This property is read-only.

UserID

Description

This property returns the user ID (mail box) on the mail server that received the email.

This property is set by SetMCFEmail. It is used by ReadHeaders, ReadEmails, ReadEmailsWithUID,RemoveEmails, and CreateQuarantineFolder methods.

This property is read-write.

MCFInboundEmail Class

This class inherits many properties from the MCFEmail class, which in turn inherits many properties from the MCFPart class. Generally, you use only the subclasses, MCFInboundEmail and MCFOutboundEmail, and not the superclasses.

MCFInboundEmail Class Methods

In this section, we discuss the MCFInboundEmail class methods. The methods are described in alphabetical order.

DumpToFile

Syntax

DumpToFile(*&File*)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the DumpToFile method to write information from the email to an already instantiated file.

This method copies the information from the following email properties, placing each on a separate line:

- ContentType
- IsAttachment
- AttachmentURL
- Text

Whether the information is appended to the bottom of the file or if it overwrites the file depends on how you instantiated the file object.

Parameters

&File Specify an already instantiated file object that you want to write the email data to.

Returns

None.

Example

```
Local File &BI_FILE;
&BI_FILE = GetFile("mcfdata.out", "w", "a");

Local PT_MCF_MAIL:MCFGetMail &gm;
Local number &ret_status, &nemails, &i;
&gm = create PT_MCF_MAIL:MCFGetMail();

Local array of PT_MCF_MAIL:MCFInboundEmail &emails;
&gm.SetMCFEmail(&user, &password, &server, &ibnode);

&emails = &gm.ReadEmails(0);
If (&gm.StatusCheck(&BI_FILE) = False) Then
   Return;
End-If;

&nemails = &emails.Len;
&ret_status = &gm.Status;
If &nemails > 0 Then
   For &i = 1 To &nemails
      &BI_FILE.WriteLine(MsgGetText(162, 1615, "Message Not Found", &i));
      &emails [&i].DumpToFile(&BI_FILE);
   End-For;
End-If;
```

Related Links

Understanding File Layout

"GetFile" (PeopleTools 8.54: PeopleCode Language Reference)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GetAttachments

Syntax

```
GetAttachments()
```

Description

Use the GetAttachments method to return the attachments with this email.

Parameters

None.

Returns

An array of MCFBodyPart objects. The methods returns an array of length 0 if there are no attachments

Related Links

Understanding Arrays
MCFBodyPart Class Methods

GetFrom

Syntax

```
GetFrom()
```

Description

Use the GetFrom method to split the semicolon delimited list of addresses in the From property into an array of addresses.

Parameters

None.

Returns

An array of string. Each item in the array contains an email address.

Related Links

From

GetParts

Syntax

```
GetParts()
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the GetParts method to return all of this email's parts.

Parameters

None.

Returns

An array of MCFBodyPart objects.

Related Links

MCFBodyPart Class Methods

GetSender

Syntax

```
GetSender()
```

Description

Use the GetSender method to split the semicolon delimited list of addresses in the Sender property into an array of addresses.

Parameters

None.

Returns

An array of string.

Related Links

Sender
GetFrom

ReadFromDatabase

Syntax

```
ReadFromDatabase(Email_ID)
```

Description

Use the ReadFromDatabase method to load a saved email from the database into this instance of email.

Parameters

Email_ID	Specify the ID of the email, as a number.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

A Boolean: true if the email is restored successfully, false otherwise.

Related Links

SaveToDatabase

SaveToDatabase

Syntax

SaveToDatabase()

Description

Use the SaveToDatabase method to save this instance of email to the database.

Parameters

None.

Returns

A number, representing the email_ID of the saved email.

Related Links

ReadFromDatabase

MCFInboundEmail Class Properties

In this section, we discuss the MCFInboundEmail class properties. The properties are described in alphabetical order.

AttachList

Description

This property returns the list of all the file names that are attachments for a particular email.

Multiple items are separated by a semicolon (;).

This property is read-write.

Related Links

AttachSizes

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

AttachSizes

Description

This property returns the sizes of the attachments associated with an email.

This property takes a string value, *not* a numeric value. Multiple values are separated by a semicolon (;).

The attachment sizes appear in the same order as the file names in AttachList.

This property is read-write.

Related Links

AttachList

DttmReceived

Description

Use this property to return the date and time an email was received.

Warning! If you are using a Post Office Protocol 3 (POP3) mail server, this property may not be populated.

This property takes a DateTime value.

This property is read-write.

Related Links

DttmSaved
DttmSent

DttmSaved

Description

This property returns the date and time that the PeopleSoft system saved an email to the database.

If you use a POP3 mail server, PeopleSoft recommends using this value as the base, or starting point, for any time-sensitive transactions.

This property takes a DateTime value.

This property is read-write.

Related Links

DttmReceived
DttmSent

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

DttmSent

Description

This property returns the date time an email was sent.

This property takes a DateTime value.

This property is read-write.

Related Links

DttmReceived
DttmSent

IBNode

Description

This property returns the name of the Integration Broker node that received the email, such as MCF_GetMail.

The system uses this value to construct the fully qualified URL required for viewing attachments.

This property is read-write.

Language

Description

This value reflects the language code of the Integration Broker node that received this email.

Note: PeopleSoft recommends setting up email accounts that are dedicated to one language such as, support_french@company.com and support_english@company.com. This enables you to anticipate the language of the email you read into your system. In turn, configure separate Integration Broker nodes to handle each of the languages you support. There are no language recognition procedures within the PeopleSoft system.

This property is read-write.

MessageID

Description

Use this property to return the globally unique identifier for this email.

This ID is generated by the mail server that sent this email.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

NotifyCC

Description

This property returns a list of the parties who were copied (carbon copied) on the email. Multiple addresses are separated by a semicolon (;).

This property is read-write.

NotifyTo

Description

This property returns a list of the parties who received the email. Multiple addresses are separated by a semicolon (;).

This property is read-write.

OffsetReceived

Description

This property returns time zone of the mail server that received this email, as a number.

Note: This property contains the time zone of the integration gateway used to fetch this email.

This property is read-write.

Related Links

OffsetSent

OffsetSent

Description

This property returns the time zone of the mail server that sent this email, as a string.

Note: Currently, this property contains the time zone of the integration gateway used to fetch this email.

This property is read-write.

Related Links

OffsetReceived

Server

Description

This property specifies the name of the mail server that received the email.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-write.

Size

Description

This property returns the total size of the entire email. This value includes the sizes of attachments.

This property is read-write.

Status

Description

This property returns the status of an individual email.

This property is read-only.

UID

Description

This property returns the unique identifier of the email.

This property is only unique within a particular user account. POP3 and IMAP 4 mail servers automatically create a unique identifier for an email when the server receives the email.

This property is read-write.

User

Description

This property returns the user account (mail box) on the mail server that received the email.

This property is read-write.

MCFMailStore Class

Use the MCFMailStore class to write emails to the PeopleSoft database and to retrieve emails from the PeopleSoft database.

Note: When writing emails to the PeopleSoft database, it is assumed that you have previously used the MCFGetMail class to retrieve email into memory. You use the MCFMailStore class immediately after to save the rowsets to the database.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

MCFMailStore Import Statements

Here is the import statement:

```
import PT_MCF_MAIL:MCFMailStore;
```

MCFMailStore Methods

This section discusses MCFMailStore class methods.

AuthorizeEmailAttach

Syntax

AuthorizeEmailAttach(*email ID*, *authentication name*, *authentication type*, *operation*)

Description

Use AuthorizeEmailAttach to authorize a user or a PeopleSoft role to view attachments associated with an email. By default, no user or role is authorized to view an email; you must explicitly grant authorization with this method. This method authorizes email and the associated attachments one at a time.

Note: If you specify ALL as the user, *any* user can view the attachments for an email.

Parameters

email ID

The unique email ID for the email. This is the PeopleSoft email ID, not the ID issued by the mail server.

authentication name

The name of the PeopleSoft user profile or role that needs to be authorized to view the attachments.

authentication type

Specify the type security definition entered as the authentication name.

- Specify *2* to indicate a user profile.
- Specify*3* to indicate a role.

operation

Specify the type of authorization operation. The following list contains the supported operations. You either add or delete user or role authorization.

- 1 = ADD
- 2 = DELETE

Returns

Returns a Boolean value: True for success, False otherwise.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

```
&ms = create MCFMailStore();
&status = &ms.AuthorizeEmailAttach(&emailid, "MCFUser", 2, 1);
```

DeleteEmail

Syntax

DeleteEmail(*email ID*, *forced delete*)

Description

Deletes the specified email from the PeopleSoft database and corresponding attachments from the directory where they are stored.

Parameters

email ID

The ID used to uniquely identify each email within the PeopleSoft database.

forced delete

This parameter is used to set the forced delete flag. It is a Boolean value. A forced delete ensures that the deletion process continues even in cases where the process encounters issues or errors related to an email. For example, with forced delete enabled, the deletion process continues even though the attachments of the email cannot be found or do not exist.

True means “force delete” and False means “do not force delete if there is an error in deleting this email.”

Returns

Returns a Boolean value. True for success, False otherwise.

Example

```
Local MCFMailStore &ms;

&ms = create MCFMailStore();
&forcedel = True;
&status = &ms.DeleteEmail(&emailid, &forcedel);
```

RetrieveEmail

Syntax

RetrieveEmail(*email ID*)

Description

Use RetrieveEmail to read email from the PeopleSoft database.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

email ID The ID that uniquely identifies an email within the PeopleSoft database.

Returns

Returns a rowset.

Example

```
Local MCFMailStore &ms;
Local Rowset &EMAIL_ROWSET;

&ms = create MCFMailStore();
&EMAIL_ROWSET = &ms.RetrieveEmail(&emailid);
```

StoreEmail

Syntax

StoreEmail(*&rowset, row*)

Description

The StoreEmail method inserts an email retrieved from the mail server into the PeopleSoft database. PeopleSoft stores the contents or pieces of the email in rowsets and child rowsets.

Parameters

&rowset The rowset containing the contents of an email. The rowset should be the rowset used by the MCFGetMail class to retrieve emails from the mail server. The rowset should be an already instantiated rowset.

Note: The first row of the rowset is empty. The first email in the rowset has a row value of 2.

row The row number in which the email data is stored.

Note: The first row is always empty. Row 2 always contains the first email of the rowset.

Returns

Returns a PeopleSoft email ID to act as the unique key for a particular email within the PeopleSoft database.

Returns 0 if an error occurred.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

```
Local MCFGetMail &GM;
Local Rowset &rs;
Local number &nemails;
Local string &email_id;

&GM = create MCFGetMail();
&rs = &GM.ReadEmailsWithAttach(&user, &password, &server, &ibnode,
&count);

/* Get the number of emails in the recordset from MCF_NUMROWS field */

&nemails = &rs.GetRow(1).GetRecord(Record.MCFEM_RES_MAIN).GetField
(Field.MCF_NUMROWS).Value;

   If (&nemails > 0) Then

/* First row in the rowset is for header info only. Start writing from
 second row */

      For &i = 1 To &nemails
         &email_id = &ms.StoreEmail(&rs, &i + 1);
         If (&email_id <> 0) Then
            /* Store was successful - email ID returned = &email_id */
         Else
            /* Error in storing email */
         End-If;
      End-For;
   End-If;
```

MCFMailUtil Class

Use the MCFMailUtil class to perform utility operations including encoding and decoding text, validating the email address, validating the email domain name, and determining whether the SMTP email server is available.

MCFMailUtil Class Methods

In this section we discuss the MCFMailUtil class methods. The methods are described in alphabetical order.

DecodeText

Syntax

DecodeText(*TextToDecode*, *&DecodedText*)

Description

Use the DecodeText method to decode text. If you only want to decode a word, use the DecodeWord property.

The text is decoded based on the values used with the EncodeText method.

The decoded text is placed in the *&DecodedText* parameter.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This method returns true if successful. If the return value is false, the following MCFMailUtil properties are set accordingly:

- ErrorDescription
- ErrorDetails
- ErrorMsgParamsCount
- MessageNumber
- MessageSetNumber

In addition you can use the GetErrorMsgParam method to return each of the substitution strings used to format the error message.

Parameters

TextToDecode	Specify the text that is to be decoded, as a string.
&DecodedText	Specify a string variable, used to hold the decoded text.

Returns

A Boolean value: true if successful, false otherwise.

Related Links

DecodeWord
EncodeText
GetErrorMsgParam
ErrorDescription
ErrorDetails
MessageNumber
MessageSetNumber

DecodeWord

Syntax

```
DecodeWord(WordToDecode, &DecodedWord)
```

Description

Use the DecodeWord method to decode a word. If you want to decode a string, use the DecodeText method instead.

The word is decoded based on the values used with the EncodeWord method.

The decoded word is placed in the *&DecodedWord* parameter.

This method returns true if successful. If the return value is false, the following MCFMailUtil properties are set accordingly:

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- ErrorDescription
- ErrorDetails
- ErrorMsgParamsCount
- MessageNumber
- MessageSetNumber

In addition you can use the GetErrorMsgParam method to return each of the substitution strings used to format the error message.

Parameters

WordToDecode	Specify the word that is to be decoded, as a string.
&DecodedWord	Specify a string variable, used to hold the decoded word.

Returns

A Boolean value: true if successful, false otherwise.

Related Links

DecodeText
EncodeWord
GetErrorMsgParam
ErrorDescription
ErrorDetails
MessageNumber
MessageSetNumber

EncodeText

Syntax

```
EncodeText(TextToEncode, charset, EncodingStyle, &EncodedText)
```

Description

Use the EncodeText method to encode text. If you only want to encode a single word, use the EncodeWord method instead.

The encoded text is placed in the *&EncodedText* parameter.

This method returns true if successful. If the return value is false, the following MCFMailUtil properties are set accordingly:

- ErrorDescription
- ErrorDetails

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- ErrorMsgParamsCount
- MessageNumber
- MessageSetNumber

In addition you can use the GetErrorMsgParam method to return each of the substitution strings used to format the error message.

Using Encoding Styles

You can specify either “B” or “Q” for the *EncodingStyle* parameter, indicating either Base64 or “Quoted-Printable” content-transfer-encoding, respectively.

Oracle recommends using the “Q” encoding when most of the characters to be encoded are in the ASCII character set; otherwise, you should use the “B” encoding. However, a mail reader that claims to recognize encoded text must be able to accept either encoding for any character set that it supports.

Both Base64 and “Quoted-Printable” content-transfer-encoding are defined by RCF 1521. See RCF 1521: Base64 Content-Transfer-Encoding and Quoted-Printable Content-Transfer-Encoding.

Parameters

TextToEncode Specify the text that is to be encoded, as a string.

charset Specify the character set to be used for encoding the text, as a string.

See "Character Sets Across the Tiers of the PeopleSoft Architecture" (PeopleTools 8.54: Global Technology).

EncodingStyle Specify the encoding style. Valid values are:

- B — for Base64 encoding.
- Q — for "Quoted-Printable" content- transfer-encoding.

&EncodedText Specify a string variable used to hold the encoded text.

Returns

A Boolean value: true if successful, false otherwise.

Related Links

DecodeText
EncodeWord
GetErrorMsgParam
ErrorDescription
ErrorDetails
MessageNumber
MessageSetNumber

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

EncodeWord

Syntax

EncodeWord(*WordToEncode, charset, EncodingStyle, &EncodedWord*)

Description

Use the EncodeWord method to encode a word. If you want to encode more than a single word, use the EncodeText method.

The encoded word is placed in the *&EncodedWord* parameter.

This method returns true if successful. If the return value is false, the following MCFMailUtil properties are set accordingly:

- ErrorDescription
- ErrorDetails
- ErrorMsgParamsCount
- MessageNumber
- MessageSetNumber

In addition you can use the GetErrorMsgParam method to return each of the substitution strings used to format the error message.

Using Encoding Styles

You can specify either “B” or “Q” for the *EncodingStyle* parameter, indicating either Base64 or “Quoted-Printable” content-transfer-encoding, respectively.

PeopleSoft recommends using the “Q” encoding when most of the characters to be encoded are in the ASCII character set; otherwise, you should use the “B” encoding. However, a mail reader that claims to recognize encoded text must be able to accept either encoding for any character set that it supports.

Both Base64 and “Quoted-Printable” content-transfer-encoding are defined by RCF 1521. See RCF 1521: Base64 Content-Transfer-Encoding and Quoted-Printable Content-Transfer-Encoding.

Parameters

WordToEncode Specify the word that is to be encoded, as a string.

charset Specify the character set to be used for encoding the word, as a string.

See "Character Sets Across the Tiers of the PeopleSoft Architecture" (PeopleTools 8.54: Global Technology).

EncodingStyle Specify the encoding style. Valid values are:

- B — for Base64 encoding.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- Q — for "Quoted-Printable" content- transfer-encoding.

&EncodedWord Specify a string variable, used to hold the encoded word.

Returns

A Boolean value: true if successful, false otherwise.

Related Links

DecodeWord
EncodeText
GetErrorMsgParam
ErrorDescription
ErrorDetails
MessageNumber
MessageSetNumber

GetErrorMsgParam

Syntax

GetErrorMsgParam(*&index*)

Description

Use this method to return each of the substitution strings used in the error message.

Parameters

&index Specifies which substitution string to return from the array of substitution parameters.

Returns

A string containing the substitution parameter.

Example

```
Local PT_MCF_MAIL:MCFMailUtil &emailutil = create PT_MCF_MAIL:MCFMailUtil();
For &index = 1 To &emailutil.ErrorMsgParamsCount
   Local String &trace  = "Param" | &index | ": '" | &emailutil.GetErrorMsgParam(&i⇒
ndex) | "'";
End-For;
```

Related Links

ErrorMsgParamsCount

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

IsDomainNameValid

Syntax

IsDomainNameValid(*domainname*)

Description

Use this method to check whether a domain name is valid. The isDomainNameValid method queries your DNS server to check whether the domain name is listed in an "MX", or mailbox exchange, record. Please note that not all domains are properly listed by DNS servers.

Note: The number of retries for domain validation is set by the SMTPDNSTimeoutRetries parameter in psappsrv.cfg. The default number of retries is 1.

This method returns true if successful. If the return value is false, the following MCFMailUtil properties are set accordingly:

- ErrorDescription
- ErrorDetails
- ErrorMsgParamsCount
- MessageNumber
- MessageSetNumber

In addition you can use the GetErrorMsgParam method to return each of the substitution strings used to format the error message.

Parameters

domainname Specifies the domain name to be validated, as a string.

Returns

A Boolean value: true if the domain name is valid, false otherwise.

Example

```
Local PT_MCF_MAIL:MCFMailUtil &emailutil = create PT_MCF_MAIL:MCFMailUtil();
&result = &emailutil.IsDomainNameValid("oracle.com");
```

Related Links

"SMTPDNSTimeoutRetries" (PeopleTools 8.54: System and Server Administration)

GetErrorMsgParam

ErrorDescription

ErrorDetails

MessageNumber

MessageSetNumber

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

IsEmailServerAvailable

Syntax

IsEmailServerAvailable(*server*, *port*, *user*, *password*)

Description

Use the IsEmailServerAvailable method to check if the email server specified with the SMTP settings in the application server configuration file is available.

This method returns true if successful. If the return value is false, the following MCFMailUtil properties are set accordingly:

- ErrorDescription
- ErrorDetails
- ErrorMsgParamsCount
- MessageNumber
- MessageSetNumber

In addition you can use the GetErrorMsgParam method to return each of the substitution strings used to format the error message.

Parameters

server	Specify the name of the mail server handling the specified user account, as a string.
port	Specify the port of the mail server handling the specified user account, as an integer.
user	Specify the user name on the mail server, such as “support” or “john_doe”, as a string.
password	Specify the password associated with the specified user name, as a string.

Returns

A Boolean value: true if the server is available, false otherwise.

Related Links

GetErrorMsgParam
ErrorDescription
ErrorDetails
MessageNumber
MessageSetNumber

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ParseRichTextHtml

Syntax

ParseRichTextHtml(*richtext*)

Description

Use this method to split rich text content with images into an array of MCFBodyPart objects. Typically, this method is used with rich text produced by the rich text editor on a long edit box.

The first element in the array is the text of the email message. The remaining elements in the array represent each image in the message. The images are added as inline parts of the email, rather than as attachments, preserving the original formatting of the HTML content.

Prior to sending the email, the images are stored in a temporary directory. The default directory is *PS_SERVDIR*/images. Use the MCFMailUtil class imagesLocation property to specify a different directory location. Images in this temporary directory must be deleted manually after sending the email; these image files are not deleted automatically.

Parameters

richtext	Rich text with images that needs to be parsed.

Returns

An array of MCFBodyPart objects.

Example

See the example on creating an email from rich text editor output later in this topic.

Related Links

MCFBodyPart Class
imagesLocation
Creating an Email from Rich Text Editor Output

ValidateAddress

Syntax

ValidateAddress(*addresslist*)

In which *addresslist* is a list of email addresses in the form:

email_address1 [{,|;} *email_address2*] ...

Description

Use the ValidateAddress method to validate a comma- or semicolon-separated list of email addresses. This method checks the syntax of the email address. It does not verify the domain name or the validity of the user name.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This method returns true if successful. If the return value is false, the following MCFMailUtil properties are set accordingly:

- badaddresses
- ErrorDescription
- ErrorDetails
- ErrorMsgParamsCount
- MessageNumber
- MessageSetNumber

In addition you can use the GetErrorMsgParam method to return each of the substitution strings used to format the error message.

Parameters

addresslist Specify the email address (or addresses) you want to verify as a comma- or semicolon-separated list.

Returns

A Boolean value: true if the specified email addresses are valid, false otherwise. When ValidateAddress returns false, the badaddresses property will contain an array of all invalid addresses.

Example

```
import PT_MCF_MAIL:*;

Local PT_MCF_MAIL:MCFMailUtil &emailutil = create PT_MCF_MAIL:MCFMailUtil();
Local boolean &result = &emailutil.ValidateAddress(&email.Recipients);
Local array of string &bAddresses = &emailutil.badaddresses;

If (&result = False) Then
   If (&bAddresses <> Null) Then
      &i = 0;
      While &bAddresses.Next(&i)
         Warning ("Bad email address in input = " | &bAddresses [&i]);
      End-While;
   End-If;
End-If;
```

Related Links

GetErrorMsgParam
badaddresses
ErrorDescription
ErrorDetails
MessageNumber
MessageSetNumber

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

MCFMailUtil Class Properties

In this section we discuss the MCFMailUtil class properties. The properties are described in alphabetical order.

badaddresses

Description

When the ValidateAddress method returns false, use the badaddresses property to get an array of invalid email addresses.

This property is effectively read-only.

Note: While this property is actually read-write, from PeopleCode, it is meant to be used in a read-only manner. If this property has a user-specified value, that value will be overwritten automatically when there is an error condition.

Related Links

ValidateAddress

ErrorDescription

Description

If an error occurs, use the ErrorDescription property to get the description of the error.

This property is effectively read-only.

Note: While this property is actually read-write, from PeopleCode, it is meant to be used in a read-only manner. If this property has a user-specified value, that value will be overwritten automatically when there is an error condition.

Related Links

ErrorDetails

ErrorDetails

Description

If an error occurs, use the ErrorDetails property to get the details for the error.

This property is effectively read-only.

Note: While this property is actually read-write, from PeopleCode, it is meant to be used in a read-only manner. If this property has a user-specified value, that value will be overwritten automatically when there is an error condition.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

ErrorDescription

ErrorMsgParamsCount

Description

Use this property to return the number of substitution parameters as an integer.

This property is read-only.

Related Links

GetErrorMsgParam

imagesLocation

Description

Use this property to specify a string representing a temporary directory for image storage to be used by the ParseRichTextHtml method. Images in this temporary directory must be deleted manually after sending the email; these image files are not deleted automatically.

If this property is not specified, the default image directory is *PS_SERVDIR*/images.

This property is read-write.

Related Links

ParseRichTextHtml
Creating an Email from Rich Text Editor Output

MessageNumber

Description

This property returns the message number of the error message associated with the failed mail utility method. The message number is associated with messages in the PeopleTools message catalog.

This property is effectively read-only.

Note: While this property is actually read-write, from PeopleCode, it is meant to be used in a read-only manner. If this property has a user-specified value, that value will be overwritten automatically when there is an error condition.

Related Links

MessageSetNumber

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

MessageSetNumber

Description

This property returns the message set number of the error message associated with the failed mail utility method. The message set number is associated with messages in the PeopleTools message catalog.

This property is effectively read-only.

Note: While this property is actually read-write, from PeopleCode, it is meant to be used in a read-only manner. If this property has a user-specified value, that value will be overwritten automatically when there is an error condition.

Related Links

MessageNumber

MCFMultiPart Class

Use the MCFMultiPart class to create complex emails with attachments, HTML content, and so on.

MCFMultiPart Class Methods

In this section, we discuss the MCFMultiPart class methods. The methods are described in alphabetical order.

AddBodyPart

Syntax

AddBodyPart(*&bodyPart*)

Description

Use the AddBodyPart method to add the specified body part to this multipart email.

Parameters

&bodyPart	Specify an already instantiated MCFBodyPart object.

Returns

None.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GetBodyPart

Syntax

GetBodyPart(*Index*)

Description

Use the GetBodyPart method to return a reference to the body part specified by *Index*.

Parameters

Index	Specify the numeric position of the body part you want to access.

Returns

A reference to an MCFBodyPart object.

Related Links

MCFBodyPart Class Methods

GetContentType

Syntax

GetContentType()

Description

Use the GetContentType method to determine the content type.

Parameters

None.

Returns

A string.

GetCount

Syntax

GetCount()

Description

Use the GetCount method to return the number of parts in the MCFMultiPart object.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

None.

Returns

A number.

MCFMultiPart Class Property

In this section we discuss the MCFMultiPart class property.

SubType

Description

Use this property to specify the subtype of the MCFMultiPart object. The values are:

- alternative
- related
- mixed

The default value is mixed.

This property is read-write.

MCFOutboundEmail Class

This class inherits many properties from the MCFEmail class, which in turn inherits many properties from the MCFPart class. Generally, you use only the subclasses, MCFOutboundEmail and MCFInboundEmail, and not the superclasses.

MCFOutboundEmail Class Methods

In this section, we discuss the MCFOutboundEmail class methods. The methods are discussed in alphabetical order.

AddAttachment

Syntax

```
AddAttachment({FilePath | FileURL}, FilePathType, FileName, FileDescr,
OverrideContentType, OverrideCharset)
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the AddAttachment method to add an attachment to this email.

Use the *FilePathType* parameter to specify if the file path is relative or absolute. If it's an absolute path, the file path could be a file on the local machine, a network folder, or a fully-qualified URL.

You can also add an attachment by creating a multipart object, adding the attachments as bodyparts to the multipart object, and then setting the MultiPart property of the MCFOutbounEmail object. The AddAttachment method is provided for convenience.

Parameters

FilePath | FileURL

You can either specify the file path to the file, or a URL to the file.

Depending on the *FilePathType* parameter, you may specify either a relative or absolute file path to the file.

This parameter should include the file name and extension of the file.

If you specify a URL address where the file is located, it must be an absolute URL. This URL should include the actual name of the file. If you specify a URL address, you must specify the *FilePathType* parameter as %FilePath_Absolute.

FilePathType

Specify the path type for the file, whether it is an absolute or relative path. The values are:

- %FilePath_Absolute — the file path is an absolute path.
- %FilePath_Relative — the file path is a relative path.

FileName

Specify the name of the file that you want to attach, as a string. You must include the file extension as well.

Description

Specify a description of the file.

OverrideContentType

The system detects the content type of the attachment using the file location and name. Specifying *OverrideContentType* overrides the system detected content type.

The character set can also be included in the ContentType. For example, “text/plain; charset=US-ASCII”

OverrideCharset

Specify a character set to be used to override the existing character set.

Returns

None.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

AddHeader

Syntax

AddHeader(*HeaderName*, *HeaderValue*)

Description

Use the AddHeader method to add a header to the email. This method allows for email server customizations. Some commonly used headers are already exposed as properties, such as From, To, Subject, ContentType and ContentLanguage. Advanced applications can adapt this technique to meet their own requirements. These headers can be either standard SMTP headers or custom headers starting with "X-".

Parameters

HeaderName	Specify the name of the header that you want to add. This parameter takes a string value.
HeaderValue	Specify the actual text of the header, as a string.

Returns

None.

Example

```
   Local PT_MCF_MAIL:MCFOutboundEmail &email = create PT_MCF_MAIL:MCFOutboundEmail(⇒
);
   Local string &TestName = "Custom Header";

   &email.From = &def.From;
   &email.Recipients = &def.Recipients;
   &email.SMTPServer = &def.SMTPServer;
   &email.Subject = &TestName;
   &email.Text = &TestName;

   &email.AddHeader("X-Mailer", "CRM Sales Application 8.9 SP2");
   &email.AddHeader("X-Mailer", "CRM Sales Application 8.9 SP3");
   &email.AddHeader("X-Mailer", "CRM Sales Application 8.9 SP4");

   &res = &email.Send();
```

Related Links

GetHeader

GetHeaderCount

GetHeaderName

GetHeaderNames

GetHeaderValues

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GetErrorMsgParam

Syntax

GetErrorMsgParam(*&index*)

Description

Use this method to return each of the substitution strings used in the error message.

Parameters

&index Specifies which substitution string to return from the array of substitution parameters.

Returns

A string containing the substitution parameter.

Example

```
Local PT_MCF_MAIL:MCFOutboundEmail &email = create PT_MCF_MAIL:MCFOutboundEmail();
For &index = 1 To &email.ErrorMsgParamsCount
   Local String &trace  = "Param" | &index | ": '" | &email.GetErrorMsgParam(&index⇒
) | "'";
End-For;
```

Related Links

ErrorMsgParamsCount

GetHeader

Syntax

GetHeader(*HeaderName*)

Description

Use the GetHeader method to return the value of the specified header.

Parameters

HeaderName Specify the name of the header that you want to access the values for, as a string.

The matching of header names is case insensitive.

Returns

An array of string containing the header values. If the header is not present, returns an array of length zero.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

Understanding Arrays
AddHeader
GetHeaderCount
GetHeaderName
GetHeaderNames
GetHeaderValues

GetHeaderCount

Syntax

```
GetHeaderCount()
```

Description

Use the GetHeaderCount method to return the number of headers.

Parameters

None.

Returns

An integer, representing the number of headers present.

Related Links

AddHeader
GetHeader
GetHeaderName
GetHeaderNames
GetHeaderValues

GetHeaderName

Syntax

```
GetHeaderName(Index)
```

Description

Use the GetHeaderName to return the name of the header that is located at *Index*.

Parameters

Index	Specify the numeric position of the header you want to access.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

A string.

Related Links

AddHeader
GetHeader
GetHeaderCount
GetHeaderNames
GetHeaderValues

GetHeaderNames

Syntax

GetHeaderNames()

Description

Use the GetHeaderNames method to return an array containing the names of all the headers.

Parameters

None.

Returns

An array of string.

Related Links

AddHeader
GetHeader
GetHeaderCount
GetHeaderName
GetHeaderValues

GetHeaderValues

Syntax

GetHeaderValues(*Index*)

Description

Use the GetHeaderValues method to return the value for the header located at the position specified by *Index*.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

Index	Specify the numeric position of the header whose value you want to access.

Returns

An array of string.

Related Links

AddHeader
GetHeader
GetHeaderCount
GetHeaderName
GetHeaderNames

Send

Syntax

```
Send()
```

Description

Use the Send method to send the email.

When you call the Send method, the following properties might be set based on the type of error:

- InvalidAddresses
- MessageNumber (from the PeopleTools Message Catalog)
- MessageSetNumber (from the PeopleTools Message Catalog)
- ValidSentAddresses
- ValidUnsentAddresses

In addition, a list of substitution strings for the error message can be accessed bythe ErrorMsgParamsCount property and the GetErrorMsgParam method.

Parameters

None.

Returns

A number indicating the status of the send. Values are:

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Numeric Value	Constant Value	Description
0	%ObEmail_ FailedBeforeSending	Email failed before being sent.
1	%ObEmail_Delivered	Email was delivered.
2	%ObEmail_NotDelivered	Email delivery not attempted.
3	%ObEmail_PartiallyDelivered	Email has only been partially delivered. Only some of the addresses in the list of addresses were delivered to.
-1	%ObEmail_ SentButResultUnknown	Email was sent but whether it was successful or not is not known.

Related Links

InvalidAddresses
ValidSentAddresses
ValidUnsentAddresses
MessageNumber
MessageSetNumber

SetSMTPParam

Syntax

SetSMTPParam(*ParamName, ParamValue*)

Description

Use the SetSMTPParam method to set parameters for the SMTP session to be used for sending the email. If you are only sending out one email, use this method. If you are sending many emails, use the SMTPSession class and set the parameters once for all the emails you are sending out.

Note: You should use this method before you use the Send method.

Parameters

ParamName Specify the name of the parameter you want to overwrite.

ParamValue Specify the value for the named parameter that you want used instead of the existing value.

Returns

None.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

```
&email.setSMTPParam("mail.mime.decodetext.strict", "false");
&email.setSMTPParam("mail.mime.address.strict", "false");
&email.setSMTPParam("mail.debug, "true");
```

Related Links

SMTPSession Class

MCFOutboundEmail Class Properties

In this section we discuss the MCFOutboundEmail class properties. The properties are described in alphabetical order.

BackupSMTPPort

Description

Use this property to specify the port number of the backup SMTP server. This is an optional property when creating an email. If you don't specify a value, the default value is 25.

This property is read-write.

BackupSMTPServer

Description

Use this property to specify the server name of the backup SMTP server. The system tries to connect to the backup server if the primary SMTPserver is not available.

This property is read-write.

BackupSMTPSSLClientCertAlias

Description

Use this property to specify the alias for the certificate for Secure Sockets Layer (SSL) client authentication on the backup SMTP server.

This property is read-write.

Related Links

BackupSMTPSSLPort, BackupSMTPUseSSL

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

BackupSMTPSSLPort

Description

Use this property to specify the SSL port number for the backup SMTP server. This is an optional property. If you don't specify a value for this property, the default value is 465.

This property is read-write.

Related Links

BackupSMTPSSLClientCertAlias, BackupSMTPUseSSL

BackupSMTPUserName

Description

Use this property to specify the user name used to sign onto the backup SMTP server. This user name is used for authentication when sending mail using the backup mail server.

This property is read-write.

BackupSMTPUserPassword

Description

Use this property to specify the user password used for signing onto the backup SMTP server. The BackupSMTPUserName and password are used for the authentication when sending mail using the backup mail server.

This property is read-write.

BackupSMTPUseSSL

Description

Use this property to indicate whether the connection to the backup SMTP server will be attempted using SSL or not.

This property takes a Boolean value: true if an SSL connection is to be attempted, false if a non-SSL connection is to be attempted.

This property is read-write.

Related Links

BackupSMTPSSLClientCertAlias, BackupSMTPSSLPort

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

BCC

Description

Use this property to specify a comma- or semicolon-separated list of addresses that are sent a copy of this email. These blind carbon copy recipients won't appear on the list of recipients.

This property is read-write.

Related Links

CC

BounceTo

Description

Use this property to specify the email address the system should direct all bounced mail to.

This property is read-write.

CC

Description

Use this property to specify a comma- or semicolon-separated list of addresses that are sent a copy (carbon copy) of this message.

This property is read-write.

Related Links

BCC

Charset

Description

Use this property to specify the character set for the text or the attachment.

You can also specify this property using the SetAttachmentContent method, or the ContentType property.

This property is read-write.

Related Links

SetAttachmentContent
ContentType

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ContentLanguage

Description

Use this property to set the language of this email. More than one language can be set in a comma-separated list. Use the standard abbreviated language names, such as en, fr, de, da, and so on.

You can also include the country codes when you specify the language, such as en-us.

This property is read-write.

Related Links

ISO 3166 Codes (Countries)
ISO 639 Language Codes (Obsolete)

ContentType

Description

Use this property to specify the content type of this body part.

You can also specify the content type with the SetAttachmentConent method.

You can also use this property to specify the character set. For example, “text/plain; charset=US-ASCII”.

This property is read-write.

Related Links

SetAttachmentContent
Charset

DefaultCharSet

Description

Use this property to specify the character set to be applied to all the parts of the email.

This property is read-write.

Description

Description

Use this property to specify a description of the file attachment associated with this email. If there is no file attachment, this property is ignored.

This property is read-write.

Related Links

AddAttachment

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Disposition

Description

Use this property to specify how the body part is presented in the received mail.

Some email clients ignore the setting of this property and present body parts either inline or as file attachments.

Values for this property are:

Value	*Description*
Attachment	The body part is shown as a file attachment.
Inline	The body part is shown in the body itself.

This property is read-write.

ErrorDescription

Description

If an error occurs, use the ErrorDescription property to get the description of the error.

This property is effectively read-only.

Note: While this property is actually read-write, from PeopleCode, it is meant to be used in a read-only manner. If this property has a user-specified value, that value will be overwritten automatically when there is an error condition.

Related Links

ErrorDetails

ErrorDetails

Description

If an error occurs, use the ErrorDetails property to get the details of the error.

This property is effectively read-only.

Note: While this property is actually read-write, from PeopleCode, it is meant to be used in a read-only manner. If this property has a user-specified value, that value will be overwritten automatically when there is an error condition.

Related Links

ErrorDescription

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ErrorMsgParamsCount

Description

Use this property to the number of substitution parameters as an integer.

This property is read-only.

Related Links

GetErrorMsgParam

Filename

Description

If you are adding an attachment to the email, you can specify the name of the file using this property.

PeopleSoft recommends that you keep the file extension specified with this property the same as the original extension found in the file path, otherwise the client applications may not be able to display it properly.

This property is read-write.

FilePath

Description

Specify the path for the file that contains the contents of this email.

Whether this is a relative or absolute path depends on the FilePathType property.

You can also specify a URL to the file using this property, if the FilePathType property is specified as %FilePath_Absolute.

If you specify a value for this property, the ‘Text’ content is ignored (when used with the ContentType property.)

This property is read-write.

Related Links

FilePathType

FilePathType

Description

Use this property to specify whether the path specified with the FilePath property is a relative or absolute path. The values for this property are:

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Value	*Description*
%FilePath_Relative	The file path specified with the FilePath property is a relative path.
%FilePath_Absolute	The file path specified with the FilePath property is either an absolute path to a file, or a URL to a file.

If you specify a relative path, the file must be available in the FILES folder of application server folder.

If you specify an absolute path, the file could be on the local machine, in any network folder, or a URL.

If you specify a value for this property, the Text property is ignored.

This property is read-write.

From

Description

Use this property to specify the email address of the person sending the email.

You can specify more than one address as from in a comma-separated list.

This property is read-write.

Related Links

Recipients
ReplyTo
Sender

Importance

Description

Use this property to specify the value of the importance header field.

The importance can be set to the following:

- low
- normal
- high

If the Priority property is not set, the system automatically sets it to the corresponding values like 5, 3 and 1.

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

InvalidAddresses

Description

Use this property to get a partial list of email addresses to which the email could not be sent. The email addresses are in a string, separated by commas.

This property is read-only.

Related Links

ValidSentAddresses
ValidUnsentAddresses

IsAuthenticationReqd

Description

Use this property to specify if authentication is required or not. If the SMTP server does not support authentication or authentication is not enabled, this property is ignored.

This property takes a Boolean value: true if authentication is required, false otherwise.

This property is read-write.

IsOkToSendPartial

Description

Use this property to specify if the email can be sent to only some of the specified recipients or if it must be sent to all. This property takes a Boolean value: true if a partial list of addresses is acceptable, false otherwise. If the email must go out to all those listed, or to none at all, specify false.

This property is read-write.

Considerations Using IsOkToSendPartial

If the syntax of the email address is wrong, no mail is sent, regardless of the value of this property. The error is reported.

If the syntax of the email addresses is correct but the email server is unable to send mail to some addresses, the value of this property is used to either send or not send to the partial list of email addresses.

If the syntax of all the email addresses are correct and the email server is able to dispatch mail to all the addresses, no error is reported immediately. Later, if some addresses are found invalid by the recipient email server or gateway, the mail is sent back. In this case the source email server has no way to find the invalidity of the email address in advance.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

IsReturnReceiptReqd

Description

Use this property to specify if the receiver must send acknowledgement that the email was received when it's received. This property takes a Boolean value: true if the return receipt is required, false otherwise.

This property is read-write.

MessageNumber

Description

This property returns the message number of the error message associated with this email. The message number is associated with messages in the PeopleTools Message Catalog.

This property is effectively read-only.

Note: While this property is actually read-write, from PeopleCode, it is meant to be used in a read-only manner. If this property has a user-specified value, that value will be overwritten automatically when there is an error condition.

Related Links

MessageSetNumber

MessageSetNumber

Description

This property returns the message set number of the error message associated with the email.

This property is effectively read-only.

Note: While this property is actually read-write, from PeopleCode, it is meant to be used in a read-only manner. If this property has a user-specified value, that value will be overwritten automatically when there is an error condition.

Related Links

MessageNumber

MultiPart

Description

The email can contain simple text, one attachment, or a MultiPart object.

If you have assigned a MultiPart object using this property, the text and attachment related properties are ignored.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-write.

Example

```
Local PT_MCF_MAIL:MCFMultipart &mp = create PT_MCF_MAIL:MCFMultipart();
&mp.SubType = "alternative; differences=Content-type";

&mp.AddBodyPart(&text);
&mp.AddBodyPart(&html);

&email.MultiPart = &mp;
```

Priority

Description

Use this property to specify the priority of this email.

The values are:

1. Highest Priority
2. High Priority
3. Normal
4. Low Priority
5. Lowest Priority

The default value is 3, that is, normal priority.

This value set with this property is used to set to a header X-Priority field, as this is the most common but non-standard field to show priority. In addition, the corresponding values are set in two header fields: X-MSMail-Priority and Priority. The headers X-Priority or X-MSMail-Priority are set to the corresponding value only if the user does not specify a value.

This property is read-write.

Recipients

Description

Use this property to specify the email addresses of all the main recipients to whom the email is being sent. All the addresses are specified in a comma- or semicolon-separated string.

This property is read-write.

RefIDs

Description

Use this property to specify a value for the REFERENCES header field of the message.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ReplyIDs

Description

Use this property to specify a value for the IN-REPLY-TO header field of the message.

This property is read-write.

ReplyTo

Description

Use this property to specify the email address where the reply should be sent. You do not need to specify a value for this property if the value is the same as the From property.

This property is read-write.

Related Links

From

ResultOfSend

Description

This property returns the result of the Send method. The values are:

Numeric Value	*Constant Value*	*Description*
0	%ObEmail_ FailedBeforeSending	Email failed before being sent.
1	%ObEmail_Delivered	Email was delivered.
2	%ObEmail_NotDelivered	Email delivery not attempted.
3	%ObEmail_PartiallyDelivered	Email has only been partially delivered. Only some of the addresses in the list of addresses were delivered to.
-1	%ObEmail_ SentButResultUnknown	Email was sent but whether it was successful or not is not known.

This property is read-only.

Related Links

Send

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Sender

Description

Use this property to specify the address of the author of the message. You do not need to specify a value for this property if the value for the From property is the same.

This property is read-write.

Related Links

From

Sensitivity

Description

Use this property to specify the value of the sensitivity header field.

The values are:

- personal
- private
- company-confidential

This property is read-write.

SMTPPort

Description

Use this property to specify the port number of SMTP server. This is an optional property. If you don't specify a value for this property, the default value is 25.

This property is read-write.

SMTPServer

Description

Use this property to specify the SMTP server to be used when sending this email.

This property is read-write.

Related Links

SMTPPort
SMTPUserName
SMTPUserPassword
SMTPSession Class

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SMTPSSLClientCertAlias

Description

Use this property to specify the alias for the certificate for SSL client authentication on the SMTP server.

This property is read-write.

Related Links

SMTPSSLPort, SMTPUseSSL, Using an SSL Connection to Send Email

SMTPSSLPort

Description

Use this property to specify the SSL port number for the SMTP server. This is an optional property. If you don't specify a value for this property, the default value is 465.

This property is read-write.

Related Links

SMTPSSLClientCertAlias, SMTPSSLClientCertAlias, Using an SSL Connection to Send Email

SMTPUserName

Description

Use this property to specify the user name to be used for logging into the SMTP server.

You should only use this property if the SMTP server allows authentication. If the SMTP server does not allow authentication, setting this property has no effect.

This property is read-write.

Related Links

SMTPPort
SMTPServer
SMTPUserPassword

SMTPUserPassword

Description

Use this property to specify the password for the SMTP user. This property is used with the SMTPUserName property.

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

SMTPPort
SMTPServer
SMTPUserName

SMTPUseSSL

Description

Use this property to indicate whether the connection to the SMTP server will be attempted using SSL or not. If you don't specify a value for this property, the default value is N.

This property takes a Boolean value: true if an SSL connection is to be attempted, false if a non-SSL connection is to be attempted.

This property is read-write.

Related Links

SMTPSSLClientCertAlias, SMTPSSLClientCertAlias, Using an SSL Connection to Send Email

StatusNotifyOptions

Description

Use this property to specify when the system should notify the sender. The values are separated by commas in a string. The values are:

Value	*Description*
SUCCESS	Send notification if the email is delivered successfully.
FAILURE	Send notification if the email is not delivered successfully.
DELAY	Send notification if delivery of the email is delayed.

This property is read-write.

Related Links

StatusNotifyReturn
TimeToWaitForResult

StatusNotifyReturn

Description

Use this property to specify what should be returned as the status notification. You can return either the header or the full message. This option is meaningful only if StatusNotifyOptions property is set.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The values are:

Value	*Description*
HDRS	Return only the headers of the email.
FULL	Return the full email message.

This property is read-write.

Subject

Description

Use this property to specify the subject of the email. A subject can only contain 254 characters.

This property is read-write.

Text

Description

Use this property to specify the text for the email.

This property is read-write.

TimeToWaitForResult

Description

Use this property to specify the number of milliseconds to wait for the result of send email process. If the result comes back within this time, the returned value is a positive number. Otherwise, %ObEmail_SentButResultUnknown (or -1) is returned.

This property is read-write.

Related Links

StatusNotifyOptions
StatusNotifyReturn

UsedDefaultConfig

Description

Use this property to determine whether the default configuration as specified in application server configuration file was used or not.

This property returns a Boolean value: true if the default configuration was used, false if the value specified with the MCFOutboundEmail or the SMTPSession object was used.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-only.

UsedPrimaryServer

Description

Use this property to determine if the default SMTP server was used, or the backup server.

This property returns a Boolean value: true if the default SMTP server was used, false if the backup server was used.

This property is read-only.

ValidSentAddresses

Description

This property returns the list of addresses that were valid and that the email was sent to. The email addresses are in a string, separated by commas.

This property is read-only.

Related Links

InvalidAddresses
ValidUnsentAddresses

ValidUnsentAddresses

Description

Use this property to get a list of the email addresses that are valid, yet the system was unable to send to, due to system problems. The email addresses are separated by commas.

This property is read-only.

Related Links

InvalidAddresses
ValidSentAddresses

SMTPSession Class

Use the SMTPSession class to when you want to send more than one email using the same SMTP session. If you are only sending a single email, use the MCFOutboundEmail class instead.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SMTPSession Class Methods

In this section we describe the SMTPSession class methods. The methods are described in alphabetical order.

Send

Syntax

Send(*&Email*)

Description

Use the Send method to send an MCFOutboundEmail object as email.

By default, the system sends the email to the SMTP server using the properties set in the application server configuration file. You can specify different setup parameters by supplying values for the SMTPSession object properties, such as Server, BackupServer, and so on.

Parameters

&Email Specify an already instantiated MCFOutboundEMail object to be sent.

Returns

A constant indicating the status of the method. The values are:

Value	*Description*
%ObEmail_Delivered	The email was delivered.
%ObEmail_NotDelivered	Email delivery not attempted.
%ObEmail_PartiallyDelivered	The email was only partially delivered, that is, it was only delivered to some of the recipients.
%ObEmail_ FailedBeforeSending	The email wasn't delivered.
%ObEmail_ SentButResultUnknown	The email was sent but the result is unknown. The TimeToWaitForResult value was not sufficient to get the result of the send process.

Related Links

SendAll

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SendAll

Syntax

SendAll(*&Emails*)

Description

Use the SendAll method to send a number of emails, all using the same SMTP session and session properties.

Parameters

&Emails Specify an array of MCFOutboundEmail objects.

Returns

An array of number. Each item in the array indicates the status of an individual email object. Values are:

Value	*Description*
%ObEmail_Delivered	The email was delivered.
%ObEmail_NotDelivered	Email delivery not attempted.
%ObEmail_PartiallyDelivered	The email was only partially delivered, that is, it was only delivered to some of the recipients.
%ObEmail_ FailedBeforeSending	The email wasn't delivered.
%ObEmail_ SentButResultUnknown	The email was sent but the result is unknown. The TimeToWaitForResult value was not sufficient to get the result of the send process.

Related Links

Send

SetSMTPParam

Syntax

SetSMTPParam(*ParamName, ParamValue*)

Description

Use the SetSMTPParam method to set additional parameters for the SMTP session.

You must use this method before you use any Send method.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

ParamName	Specify the name of the parameter you want to overwrite.
ParamValue	Specify the value for the named parameter that you want used instead of the existing value.

Returns

None.

SMTPSession Class Properties

In this section we describe the SMTPSession class properties. The properties are described in alphabetical order.

BackupPort

Description

Use this property to specify the port number of backup SMTP server. This is an optional property. If you don't specify a value for this property, the default value is 25.

This property is read-write.

BackupServer

Description

Use this property to specify the name of the backup SMTP server. The system tries connecting to the backup server if the primary SMTP server is not available.

This property is read-write.

BackupSSLClientCertAlias

Description

Use this property to specify the alias for the certificate for SSL client authentication on the backup SMTP server.

This property is read-write.

Related Links

BackupSSLPort, BackupUseSSL

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

BackupSSLPort

Description

Use this property to specify the SSL port number for the backup SMTP server. This is an optional property. If you don't specify a value for this property, the default value is 465.

This property is read-write.

Related Links

BackupSSLClientCertAlias, BackupUseSSL

BackupUserName

Description

Use this property to specify the user name used to sign onto the backup SMTP server.

This user name is used for authentication when sending mail using the backup mail server.

This property is read-write.

BackupUserPassword

Description

Use this property to specify the user password used to sign onto the backup SMTP server.

This user name and password are used for authentication when sending mail using the backup mail server.

This property is read-write.

BackupUseSSL

Description

Use this property to indicate whether the connection to the backup SMTP server will be attempted using SSL or not.

This property takes a Boolean value: true if an SSL connection is to be attempted, false if a non-SSL connection is to be attempted.

This property is read-write.

Related Links

BackupSSLClientCertAlias, BackupSSLPort

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

IsAuthenticationReqd

Description

Use this property to specify if authentication is required or not. If the SMTP server does not support authentication or authentication is not enabled, this property is ignored.

This property takes a Boolean value: true if authentication is required, false otherwise.

This property is read-write.

Port

Description

Use this property to specify the SMTP port number to be used for sending this email. This property takes a numeric value. This property is optional. If you don't specify a value for this property, the default value of 25 is used.

This property is read-write.

Related Links

SMTPServer
SMTPUserName
SMTPUserPassword
SMTPSession Class

Server

Description

Use this property to specify the name of the SMTP server to be used when sending this email.

This property is read-write.

Related Links

SMTPPort
SMTPUserName
SMTPUserPassword
SMTPSession Class

SSLClientCertAlias

Description

Use this property to specify the alias for the certificate for SSL client authentication on the SMTP server.

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

SSLPort, UseSSL

SSLPort

Description

Use this property to specify the SSL port number for the SMTP server. This is an optional property. If you don't specify a value for this property, the default value is 465.

This property is read-write.

Related Links

SSLClientCertAlias, UseSSL

UsedDefaultConfig

Description

Use this property to determine whether the default configuration as specified in application server configuration file was used or not.

This property returns a Boolean value: true if the default configuration was used, false if the value specified with the MCFOutboundEmail or the SMTPSession object was used.

This property is read-only.

UsedPrimaryServer

Description

Use this property to determine if the default SMTP server was used, or the backup server.

This property returns a Boolean value: true if the default SMTP server was used, false if the backup server was used.

This property is read-only.

UserName

Description

Use this property to specify the user name to be used for logging into the SMTP server.

You should only use this property if the SMTP server allows authentication. If the SMTP server does not allow authentication, setting this property has no effect.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

SMTPPort
SMTPServer
SMTPUserPassword

UserPassword

Description

Use this property to specify the password for the SMTP user. This property is used with the SMTPUserName property.

This property is read-write.

Related Links

SMTPPort
SMTPServer
SMTPUserName

UseSSL

Description

Use this property to indicate whether the connection to the SMTP server will be attempted using SSL or not. If you don't specify a value for this property, the default value is N.

This property takes a Boolean value: true if an SSL connection is to be attempted, false if a non-SSL connection is to be attempted.

This property is read-write.

Related Links

SSLClientCertAlias, SSLPort

Mail Classes Examples

This section provides examples of the following:

- Creating a text email.
- Creating email and overriding SMTP settings.
- Creating an HTML email.
- Creating a multipart email with text and HTML parts.
- Creating an HTML email with images.
- Creating an email from rich text editor output.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- Creating an email with attachments.
- Creating email attachments by specifying URLs.
- Creating and sending multiple emails.
- Authenticating email while sending.
- Using an SSL connection to send email.

Creating a Text Email

The following code example creates and sends a very simple email, then tests the results.

```
import PT_MCF_MAIL:*;

/*-- Create an outbound email object --*/

Local PT_MCF_MAIL:MCFOutboundEmail &eMail =
create PT_MCF_MAIL:MCFOutboundEmail();

/*-- Initialize the usual fields of an email --*/

&eMail.From = &FromAddress;
&eMail.Recipients = &ToList;
&eMail.Subject = &Subject;
&eMail.Text = &MailBody;

/*-- The send method uses the default SMTP parameters as set in the app server conf⇒
iguration file.

This send method makes a connection to the SMTP server, sends the mail and then dis⇒
connects.

The result are returned as a number corresponding to the possible values.

The list of ValidSent, InvalidSent and Invalid addresses are returned in the email ⇒
object itself
----*/

Local integer &resp = &eMail.Send();
Local boolean &done;

Evaluate &resp
   When %ObEmail_Delivered
      /* every thing ok */
      &done = True;
      Break;

   When %ObEmail_NotDelivered
/*-- Check &email.InvalidAddresses, &email.ValidSentAddresses
and &email.ValidUnsentAddresses */
      &done = False;
      Break;

   When %ObEmail_PartiallyDelivered
/* Check &email.InvalidAddresses, &email.ValidSentAddresses
and &email.ValidUnsentAddresses; */
      &done = True;
      Break;

   When %ObEmail_FailedBeforeSending
/* Get the Message Set Number, message number;
Or just get the formatted messages from &email.ErrorDescription,
&email.ErrorDetails;*/

      &done = False;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
      Break;
   End-Evaluate;
```

Creating Email and Overriding SMTP Settings

The following code example creates a text email and overrides the SMTP settings as found in the application server configuration file.

```
import PT_MCF_MAIL:*;

/*-- Create an email object by setting individual parameters ---*/

Local PT_MCF_MAIL:MCFOutboundEmail &eMail =
create PT_MCF_MAIL:MCFOutboundEmail();

&eMail.Recipients = &ToList; /* comma separated list of email addresses */
&eMail.CC = &CCList; /* comma separated list of email addresses */
&eMail.BCC = &BCCList; /* comma separated list of email addresses */
&eMail.From = &FromAddress; /* from email address */
&eMail.ReplyTo = &ReplyToAddress; /* in case the reply is to be sent to a different⇒
 email address */
&eMail.Sender = &SenderAddress; /* If different from the "from" address */

&eMail.Subject = &Subject; /* email subject line */
&eMail.Text = &MailBody; /* email body text */


/*-- Override the default SMTP parameters specified in app server configuration fil⇒
e ----*/

&eMail.SMTPServer = "psp-smtpg-01";
&eMail.SMTPPort = 10266; /*-- Usually this is 25 by default */

Local integer &resp = &eMail.Send();

/* Now check the &resp for the result */

Local boolean &done;

Evaluate &resp
   When %ObEmail_Delivered
      /* every thing ok */
      &done = True;
      Break;

   When %ObEmail_NotDelivered
/*-- Check &email.InvalidAddresses, &email.ValidSentAddresses
and &email.ValidUnsentAddresses */
      &done = False;
      Break;

   When %ObEmail_PartiallyDelivered
/* Check &email.InvalidAddresses, &email.ValidSentAddresses
and &email.ValidUnsentAddresses; */
      &done = True;
      Break;

   When %ObEmail_FailedBeforeSending
/* Get the Message Set Number, message number;
Or just get the formatted messages from &email.ErrorDescription,
&email.ErrorDetails;*/

      &done = False;
      Break;
   End-Evaluate;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Creating an HTML Email

The following example creates an HTML email.

```
import PT_MCF_MAIL:*;

/*-- Create an email object by setting individual parameters
---*/


Local PT_MCF_MAIL:MCFOutboundEmail &email =
create PT_MCF_MAIL:MCFOutboundEmail();

   &email.From = &FromAddress;
   &email.Recipients = &ToList;
   &email.Subject = &Subject;

&email.Text =
"<html><body><H1><b>Hi there!</b></H1><P>We are ready.</body></html>";

   &email.ContentType = "text/html";

Local integer &res = &email.Send();

Local boolean &done;

Evaluate &resp
   When %ObEmail_Delivered
      /* every thing ok */
      &done = True;
      Break;

   When %ObEmail_NotDelivered
/*-- Check &email.InvalidAddresses, &email.ValidSentAddresses
and &email.ValidUnsentAddresses */
      &done = False;
      Break;

   When %ObEmail_PartiallyDelivered
/* Check &email.InvalidAddresses, &email.ValidSentAddresses
and &email.ValidUnsentAddresses; */
      &done = True;
      Break;

   When %ObEmail_FailedBeforeSending
/* Get the Message Set Number, message number;
Or just get the formatted messages from &email.ErrorDescription,
&email.ErrorDetails;*/

      &done = False;
      Break;
   End-Evaluate;
```

Creating a Multipart Email with Text and HTML Parts

The following code example creates an email with both HTML and text sections.

The email client on the target host must be able to detect the HTML and text parts in the email and display the part that the client is configured to display.

```
import PT_MCF_MAIL:*;

Local PT_MCF_MAIL:MCFOutboundEmail &email =
create PT_MCF_MAIL:MCFOutboundEmail();
Local string &TestName = "Text and its alternate html body";

&email.From = &FromAddress;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
&email.Recipients = &ToList;
&email.Subject = &Subject;

Local PT_MCF_MAIL:MCFBodyPart &text = create PT_MCF_MAIL:MCFBodyPart();
&text.Text = "Hi There";

Local PT_MCF_MAIL:MCFBodyPart &html = create PT_MCF_MAIL:MCFBodyPart();
&html.Text =
"<html><BODY><H1>EMail test with HTML content</H1><b>Hi There</b>" |
"<A href='http://www.peoplesoft.com'>Check this out!</A>" |
"<P></BODY></html>";
&html.ContentType = "text/html";

Local PT_MCF_MAIL:MCFMultipart &mp = create PT_MCF_MAIL:MCFMultipart();
&mp.SubType = "alternative; differences=Content-type";

&mp.AddBodyPart(&text);
&mp.AddBodyPart(&html);

&email.MultiPart = &mp;

Local integer &res = &email.Send();

Local boolean &done;

Evaluate &resp
   When %ObEmail_Delivered
      /* every thing ok */
      &done = True;
      Break;

   When %ObEmail_NotDelivered
/*-- Check &email.InvalidAddresses, &email.ValidSentAddresses
and &email.ValidUnsentAddresses */
      &done = False;
      Break;

   When %ObEmail_PartiallyDelivered
/* Check &email.InvalidAddresses, &email.ValidSentAddresses
and &email.ValidUnsentAddresses; */
      &done = True;
      Break;

   When %ObEmail_FailedBeforeSending
/* Get the Message Set Number, message number;
Or just get the formatted messages from &email.ErrorDescription,
&email.ErrorDetails;*/

      &done = False;
      Break;
   End-Evaluate;
```

Creating an HTML Email with Images

The following code example creates an HTML email with embedded images. The content ID for an image can be a reference to a part in the email. In the following code example, the images become a part of the email and are transmitted as attachments to the email.

```
import PT_MCF_MAIL:*;

Local PT_MCF_MAIL:MCFOutboundEmail &email =
create PT_MCF_MAIL:MCFOutboundEmail();

   &email.From = &FromAddress;
   &email.Recipients = &ToList;
   &email.Subject = &Subject;


Local string &htmlText =
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
"<html>" |
"  <head><title></title></head>" |
"  <body>" |
"    <b>A sample jpg</b><br>" |
"    <IMG SRC=cid:23abc@pc27 width=566 height=424><br>" |
"    <b>End of jpg</b>" |
"  </body>" |
"</html>";

/* In this sample, the htmlText is assembled using | operator
only for the readability.
Specifying just one string can be more efficient
*/

   Local PT_MCF_MAIL:MCFMultipart &mp = create PT_MCF_MAIL:MCFMultipart();
   &mp.SubType = "related";

   Local PT_MCF_MAIL:MCFBodyPart &html = create PT_MCF_MAIL:MCFBodyPart();
   &html.Text = &htmlText;
   &html.ContentType = "text/html";

   Local PT_MCF_MAIL:MCFBodyPart &image = create PT_MCF_MAIL:MCFBodyPart();

&image.SetAttachmentContent("///file:C:/User/Documentum/XML%20Applications/proddoc/⇒
peoplebook_upc/peoplebook_upc.dtd",
 %FilePath_Absolute, "sample.jpg", "This is a sample image!", "", "");

   &image.AddHeader("Content-ID", "<23abc@pc27>");

   &mp.AddBodyPart(&html);
   &mp.AddBodyPart(&image);

   &email.MultiPart = &mp;

   Local integer &res = &email.Send();

Local boolean &done;

Evaluate &resp
   When %ObEmail_Delivered
      /* every thing ok */
      &done = True;
      Break;

   When %ObEmail_NotDelivered
/*-- Check &email.InvalidAddresses, &email.ValidSentAddresses
and &email.ValidUnsentAddresses */
      &done = False;
      Break;

   When %ObEmail_PartiallyDelivered
/* Check &email.InvalidAddresses, &email.ValidSentAddresses
and &email.ValidUnsentAddresses; */
      &done = True;
      Break;

   When %ObEmail_FailedBeforeSending
/* Get the Message Set Number, message number;
Or just get the formatted messages from &email.ErrorDescription,
&email.ErrorDetails;*/

      &done = False;
      Break;
   End-Evaluate;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Creating an Email from Rich Text Editor Output

The following example creates an email message using output from a long edit box enabled with the rich text editor. Using the ParseRichTextHtml method, rich text output of the long edit box is split into an array of MCFBodyPart objects.

```
import PT_MCF_MAIL:*;

Local PT_MCF_MAIL:MCFOutboundEmail &email = create PT_MCF_MAIL:MCFOutboundEmail();
Local PT_MCF_MAIL:MCFMultipart &mp = create PT_MCF_MAIL:MCFMultipart();
Local PT_MCF_MAIL:MCFMailUtil &mu = create PT_MCF_MAIL:MCFMailUtil();

Local string &htmlText = RECORD_NAME.FIELD_NAME.Value;

&mp.SubType = "related";
&email.Recipients = &recipients;
&email.From = &from;
&email.Subject = "Your Order";

Local array of PT_MCF_MAIL:MCFBodyPart &bp;
&mu.imagesLocation = "c:\temp\images";
&bp = &mu.ParseRichTextHtml(&htmlText);

If (&bp = Null) Then
   MessageBox(0, "", 0, 0, &mu.ErrorDescription);
   Return;
End-If;

&mp.AddBodyPart(&bp [1]);

For &i = 2 To &bp.Len
   &mp.AddBodyPart(&bp [&i]);
End-For;

&email.MultiPart = &mp;
Local integer &resp = &email.Send();

/* Exec code to check the &resp for the result */

/* Exec code to delete temporary image files from the imagesLocation directory */
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

For example, the rich text editor is used to create a message containing text and two images as shown in this example:

Image: Rich text editor displaying an example email

This example illustrates the fields and controls on the Rich text editor displaying an example email. You can find definitions for the fields and controls later on this page.

The HTML for this email is as follows:

```
<p>Dear Customer,</p>
<p>Here are the details of your order:</p>
<ul>
<li> Item #1 - Ocean Sunset:
<br /> <img height="180" id="PT_RTE_IMG_DB_LOC###20091111142435187Sunset_thumbnail.⇒
jpg" src="/cs/QEDMO/cache/PTRTDB_JPG_GIYDAOJRGEYTCMJUGI1DGNJRHA2VG4LOONSXIX2UNB1W1Y⇒
TOMFUWYLTKOBTQ=_GA==_GE==_2000000000.JPG" width="240" /><br />  </li>
<li> Item #2 - Hazy Blue Mountains:
<br /> <img height="180" id="PT_RTE_IMG_DB_LOC###20091111142508395Mountains_thumbna⇒
il.jpg" src="/cs/QEDMO/cache/PTRTDB_JPG_GIYDAOJRGEYTCMJUGI1TAOBTHE1U122VNZ1GC1LOONP⇒
XI1DVNVRG3YLJNQXGU3DH_GA==_GE==_2000000000.JPG" width="240" /></li>
</ul>
<p>Thank you and regards,</p>
<p>Customer Service Department
<br /><a href="http://www.xyzcorp.com">http://www.xyzcorp.com</a></p>
```

When this HTML is parsed by the ParseRichTextHtml method, an array with three MCFBodyPart elements is created. The first MCFBodyPart is array element &bp [1] with the following properties:

- &bp [1].ContentType =

  `text/html`

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- &bp [1].Text =

```
<p>Dear Customer,</p>
<p>Here are the details of your order:</p>
<ul>
<li> Item #1 - Ocean Sunset:
<br /> <img height="180" id="PT_RTE_IMG_DB_LOC###20091111142435187Sunset_thumb⇒
nail.jpg" src="cid:2205@pc27" width="240" />
<br />  </li>
<li> Item #2 - Hazy Blue Mountains:
<br /> <img height="180" id="PT_RTE_IMG_DB_LOC###20091111142508395Mountains_th⇒
umbnail.jpg" src="cid:8160@pc27" width="240" /></li>
</ul>
<p>Thank you and regards,</p>
<p>Customer Service Department
<br /><a href="http://www.xyzcorp.com">http://www.xyzcorp.com</a></p>
```

The second MCFBodyPart is array element &bp [2] with the following properties:

- &bp [2].ContentType =

```
image/gif
```

- &bp [2].Description =

```
Image1
```

- &bp [2].Disposition =

```
inline
```

- &bp [2].AttachmentURL =

```
c:\temp\images/20091111142435187Sunset_thumbnail.jpg
```

The final MCFBodyPart is array element &bp [3] with the following properties:

- &bp [3].ContentType =

```
image/gif
```

- &bp [3].Description =

```
Image2
```

- &bp [3].Disposition =

```
inline
```

- &bp [3].AttachmentURL =

```
c:\temp\images/20091111142508395Mountains_thumbnail.jpg
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Observe that the email received by the recipient is formatted the way that it appeared in the rich text editor as shown in the following example:

Image: Email as received in Microsoft Outlook

This example illustrates the fields and controls on the Email as received in Microsoft Outlook. You can find definitions for the fields and controls later on this page.

Finally, the XML code that represents this email message is as follows:

```
<?xml version="1.0" encoding="UTF-8" standalone="no"?>
<SOAP-ENV:Envelope xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xmlns:cms=⇒
"http://cms.ocs.oracle/" xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"⇒
 xmlns:xs="http://www.w3.org/2001/XMLSchema">
   <SOAP-ENV:Body>
      <cms:GetEntitySnapshotResponse>
         <return xsi:type="EmailMessageType_DEBUG" SnapshotId="0000000000000010000⇒
09E2607E2B4200000124E528DD580000000000000001" CEN="334B:3BF0:emsg:38893C00F42F38A1E⇒
0404498C8A6612B0000FEE32642">
            <CreatedOn>2009-11-11T21:31:07Z</CreatedOn>
            <Creator EID="334B:3BF0:user:CB3F97695BD24114B65149D2E4CC842E0000000112⇒
AE"/>
            <Deleted>false</Deleted>
            <ModifiedBy EID="334B:3BF0:user:CB3F97695BD24114B65149D2E4CC842E0000000⇒
112AE"/>
            <ModifiedOn>2009-11-11T21:31:07Z</ModifiedOn>
            <Name>your order</Name>
            <Parent EID="334B:3BF0:afrh:38893C00F42F38A1E0404498C8A6612B00001EF9C00⇒
A"/>
            <New>false</New>
            <ReadFlag>true</ReadFlag>
            <UserCreatedOn>2009-11-11T21:31:06Z</UserCreatedOn>
            <Viewer EID="334B:3BF0:user:CB3F97695BD24114B65149D2E4CC842E0000000112A⇒
E"/>
            <Content>
               <ContentId>24316678.11257950022359.JavaMail.admin@XXXXX</ContentId>
               <MediaType>message/rfc822</MediaType>
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
                <Body xsi:type="MultiContentType">
                   <MediaType>multipart/related</MediaType>
                   <Parts>
                      <Item xsi:type="SimpleContentType">
                         <MediaType>text/html</MediaType>
                         <CharacterEncoding>us-ascii</CharacterEncoding>
                         <Language>en</Language>
                         <ContentStream>
                            <Id>T0RNMU5ESTFOVFpEUmtKQ05FWTJNemhETmpWQ1JqWXdRelZDT0VJ⇒
ek9EUXdNREF3TURBd01EWTVRVUU9JCQjIyQkN2JpdCQkIyMkJDg3NyQkIyMkJDU2Mg==</Id>
                            <Length>640</Length>
                         </ContentStream>
                      </Item>
                      <Item xsi:type="SimpleContentType">
                         <Disposition>INLINE</Disposition>
                         <ContentId>&lt;2205@pc27&gt;</ContentId>
                         <MediaType>image/gif</MediaType>
                         <CharacterEncoding>ascii</CharacterEncoding>
                         <Language>en</Language>
                         <ContentStream>
                            <Id>T0RNMU5ESTFOVFpEUmtKQ05FWTJNemhETmpWQ1JqWXdRelZDT0VJ⇒
ek9EUXdNREF3TURBd01EWTVRVUU9JCQjIyQkYmFzZTY0JCQjIyQkMTY3NCQkIyMkJDExNzI4</Id>
                            <Length>11923</Length>
                         </ContentStream>
                         <Name>20091111142435187Sunset_thumbnail.jpg</Name>
                      </Item>
                      <Item xsi:type="SimpleContentType">
                         <Disposition>INLINE</Disposition>
                         <ContentId>&lt;8160@pc27&gt;</ContentId>
                         <MediaType>image/gif</MediaType>
                         <CharacterEncoding>ascii</CharacterEncoding>
                         <Language>en</Language>
                         <ContentStream>
                            <Id>T0RNMU5ESTFOVFpEUmtKQ05FWTJNemhETmpWQ1JqWXdRelZDT0VJ⇒
ek9EUXdNREF3TURBd01EWTVRVUU9JCQjIyQkYmFzZTY0JCQjIyQkMTM2NDMkJCMjJCQ3MzUy</Id>
                            <Length>7553</Length>
                         </ContentStream>
                         <Name>20091111142508395Mountains_thumbnail.jpg</Name>
                      </Item>
                   </Parts>
                </Body>
                <From>
                   <Address>&lt;psft@peoplesoft.com&gt;</Address>
                </From>
                <Priority>NONE</Priority>
                <Sender>
                   <Address>&lt;psft@peoplesoft.com&gt;</Address>
                </Sender>
                <SentDate>2009-11-11T21:31:06Z</SentDate>
                <Size>21039</Size>
                <Subject>Your Order</Subject>
                <TOReceivers>
                   <Item>
                      <Address>&lt;&gt;</Address>
                      <Participant EID="334B:3BF0:user:CB3F97695BD24114B65149D2E4CC8⇒
42E0000000112AE"/>
                      <Directives/>
                      <Status>DELIVERED</Status>
                   </Item>
                </TOReceivers>
             </Content>
             <DeliveredTime>
                <DateOnly>false</DateOnly>
                <FloatingTime>false</FloatingTime>
                <Timestamp>2009-11-11T21:31:07Z</Timestamp>
             </DeliveredTime>
             <Modifiable>false</Modifiable>
             <ReceiptRequested>false</ReceiptRequested>
             <Type>EMAIL</Type>
             <MimeHeaders>
                <Item>
```


 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
                  <Name>X-AUTH-TYPE</Name>
                  <Value>SW50ZXJuYWwgSVA=</Value>
               </Item>
               <Item>
                  <Name>Received</Name>
                  <Value>ZnJvbSByZ21pbmV0MTMub3JhY2xlLmNvbSAoLzE0OC44Ny4xMTMuMTI1KS⇒
BieSBkZWZhdWx0IChPcmFjbGUgQmVlaGl2ZSBHYXRld2F5IHY0LjApIHdpdGggRVNNVFAgOyBXZWQsIDExI⇒
E5vdiAyMDA5IDEzOjMxOjA2IC0wODAw</Value>
               </Item>
               <Item>
                  <Name>Received</Name>
                  <Value>ZnJvbSBCVUZGWSAoYnVmZnkudXMub3JhY2xlLmNvbSBbMTAuMTM4LjIyOC⇒
4xMzNdKSBieSByZ21pbmV0MTMub3JhY2xlLmNvbSAoU3dpdGNoLTMuMy4xL1N3aXRjaC0zLjMuMSkgd2l0a⇒
CBFU01UUCBpZCBuQUJMVjZVSjAxMzk0NiBmb3IgPGRhdmUucGllcmNlQG9yYWNsZS5jb20+OyBXZWQsIDEx⇒
IE5vdiAyMDA5IDIxOjMxOjA2IEdNVA==</Value>
               </Item>
               <Item>
                  <Name>MIME-Version</Name>
                  <Value>MS4w</Value>
               </Item>
               <Item>
                  <Name>To</Name>
                  <Value>ZGF2ZS5waWVyY2VAb3JhY2xlLmNvbQ==</Value>
               </Item>
               <Item>
                  <Name>MESSAGE-ID</Name>
                  <Value>PDI0MzE2Njc4LjExMjU3OTUwMDIyMzU5LkphdmFNYWlsLmFkbWluQEJVRk⇒
ZZPg==</Value>
               </Item>
               <Item>
                  <Name>Content-Type</Name>
                  <Value>bXVsdGlwYXJ0L3JlbGF0ZWQ7ICBib3VuZGFyeT0iLS0tLT1fUGFydF8xXz⇒
IzNzUyMTguMTI1Nzk1MDAyMjEwOSI=</Value>
               </Item>
               <Item>
                  <Name>From</Name>
                  <Value>cHNmdEBwZW9wbGVzb2Z0LmNvbQ==</Value>
               </Item>
               <Item>
                  <Name>X-SOURCE-IP</Name>
                  <Value>YnVmZnkudXMub3JhY2xlLmNvbSBbMTAuMTM4LjIyOC4xMzNd</Value>
               </Item>
               <Item>
                  <Name>X-CT-REFID</Name>
                  <Value>c3RyPTAwMDEuMEEwOTAyMDQuNEFGQjJEMTkuMDBGQSxzcz0xLGZncz0w</⇒
Value>
               </Item>
               <Item>
                  <Name>Subject</Name>
                  <Value>WW91ciBPcmRlcg==</Value>
               </Item>
               <Item>
                  <Name>Date</Name>
                  <Value>V2VkLCAxMSBOb3YgMjAwOSAyMTozMTowNiBHTVQ=</Value>
               </Item>
            </MimeHeaders>
         </return>
      </cms:GetEntitySnapshotResponse>
   </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```


Creating an Email with Attachments

The following code example creates an email with an attachment.

PeopleSoft recommends that you always provide the proper extension in the file name, otherwise the receiving email client may not be able to associate it with the appropriate application.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Note: There is no automatic restriction of attachment size using the mail classes. To restrict an email based on attachment size, your application must check the size of an attachment before composing and sending the email.

```
import PT_MCF_MAIL:*;

Local PT_MCF_MAIL:MCFOutboundEmail &email =
create PT_MCF_MAIL:MCFOutboundEmail();

&email.From = &FromAddress;
&email.Recipients = &ToList;
&email.Subject = &Subject;

Local string &plain_text = "Hi there!";
Local PT_MCF_MAIL:MCFBodyPart &text = create PT_MCF_MAIL:MCFBodyPart();
&text.Text = &plain_text;

Local PT_MCF_MAIL:MCFBodyPart &attach1 = create PT_MCF_MAIL:MCFBodyPart();
&attach1.SetAttachmentContent("Ocean Wave.jpg", %FilePath_Relative,
"Ocean Wave.jpg", "Ocean Wave", "", "");
/* %FilePath_Relative indicates the file is available at Appserver's FILES dierctor⇒
y */

Local PT_MCF_MAIL:MCFBodyPart &attach2 = create PT_MCF_MAIL:MCFBodyPart();
&attach2.SetAttachmentContent("///file:C:/User/Documentum/XML%20Applications/proddo⇒
c/peoplebook_upc/peoplebook_upc.dtd",
 %FilePath_Absolute, "Sample.jpg", "Sample", "", "");
/* The Sample.jpg is available in the "public" folder of my-server machine*/


Local PT_MCF_MAIL:MCFMultipart &mp = create PT_MCF_MAIL:MCFMultipart();
&mp.AddBodyPart(&text);
&mp.AddBodyPart(&attach1);
&mp.AddBodyPart(&attach2);

&email.MultiPart = &mp;

Local integer &res = &email.Send();

Local boolean &done;

Evaluate &resp
   When %ObEmail_Delivered
      /* every thing ok */
      &done = True;
      Break;

   When %ObEmail_NotDelivered
/*-- Check &email.InvalidAddresses, &email.ValidSentAddresses
and &email.ValidUnsentAddresses */
      &done = False;
      Break;

   When %ObEmail_PartiallyDelivered
/* Check &email.InvalidAddresses, &email.ValidSentAddresses
and &email.ValidUnsentAddresses; */
      &done = True;
      Break;

   When %ObEmail_FailedBeforeSending
/* Get the Message Set Number, message number;
Or just get the formatted messages from &email.ErrorDescription,
&email.ErrorDetails;*/

      &done = False;
      Break;
   End-Evaluate;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Creating Email Attachments by Specifying URLs

The following code example creates an email attachment specifying a URL for the file location, instead of an absolute or relative path to the file.

```
Local PT_MCF_MAIL:MCFOutboundEmail &email =
create PT_MCF_MAIL:MCFOutboundEmail();

   &email.From = &FromAddress;
   &email.Recipients = &ToList;
   &email.Subject = &Subject;

   Local string &plain_text = "Hi there!";
   Local PT_MCF_MAIL:MCFBodyPart &text = create PT_MCF_MAIL:MCFBodyPart();

   &text.Text = &plain_text;

Local PT_MCF_MAIL:MCFBodyPart &attach1 = create PT_MCF_MAIL:MCFBodyPart();

&attach1.SetAttachmentContent("http://www.yahoo.com/members_agreement",
 %FilePath_Absolute, "hotmail.htm", "Hotmail Home page", "", "");

Local PT_MCF_MAIL:MCFBodyPart &attach2 = create PT_MCF_MAIL:MCFBodyPart();

&attach2.SetAttachmentContent("ftp://www.w3c/docs/somedoc",
 %FilePath_Absolute, "somedoc.htm", "somedoc from w3c", "", "");

   Local PT_MCF_MAIL:MCFMultipart &mp = create PT_MCF_MAIL:MCFMultipart();
   &mp.AddBodyPart(&text);
   &mp.AddBodyPart(&attach1);
   &mp.AddBodyPart(&attach2);

   &email.MultiPart = &mp;

Local integer &res = &email.Send();

Local boolean &done;

Evaluate &resp
   When %ObEmail_Delivered
      /* every thing ok */
      &done = True;
      Break;

   When %ObEmail_NotDelivered
/*-- Check &email.InvalidAddresses, &email.ValidSentAddresses
and &email.ValidUnsentAddresses */
      &done = False;
      Break;

   When %ObEmail_PartiallyDelivered
/* Check &email.InvalidAddresses, &email.ValidSentAddresses
and &email.ValidUnsentAddresses; */
      &done = True;
      Break;

   When %ObEmail_FailedBeforeSending
/* Get the Message Set Number, message number;
Or just get the formatted messages from &email.ErrorDescription,
&email.ErrorDetails;*/

      &done = False;
      Break;
   End-Evaluate;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Creating and Sending Multiple Email Messages

You can create several emails and send them all in a single connection to the SMTP server. However, your system administrator may also need to configure the SMTP server with longer connection time-outs if you are sending multiple emails.

```
import PT_MCF_MAIL:*;

/*-- Create an email object by setting individual parameters
---*/
 Local array of PT_MCF_MAIL:MCFOutboundEmail &mails;
 Local PT_MCF_MAIL:MCFOutboundEmail &email;

 Local PT_MCF_MAIL:SMTPSession &commonSession =
create PT_MCF_MAIL:SMTPSession();

   &email = &commonSession.CreateOutboundEmail();
   &email.From = &FromAddress;
   &email.Recipients = &ToList1;
   &email.Subject = &Subject;
   &email.Text = &MailBody1;

   &mails = CreateArray(&email);

   &email = &commonSession.CreateOutboundEmail();
   &email.From = &FromAddress;
   &email.Recipients = &ToList2;
   &email.Subject = &Subject;
   &email.Text = &MailBody2;
   &mails [2] = &email;

   &email = &commonSession.CreateOutboundEmail();
   &email.From = &FromAddress;
   &email.Recipients = &ToList3;
   &email.Subject = &Subject;
   &email.Text = &MailBody3;
   &mails [3] = &email;

   Local array of integer &allRes = &commonSession.SendAll(&mails);
```

Sending an Email With Authentication

The following code example includes a user name and password to be used by the SMTP server.

```
import PT_MCF_MAIL:*;

Local PT_MCF_MAIL:MCFOutboundEmail &email =
create PT_MCF_MAIL:MCFOutboundEmail();

   &email.From = &FromAddress;
   &email.Recipients = &ToList;
   &email.Subject = &Subject;
   &email.Text = &MailBody;

   &email.SMTPServer = "MySMTPServer";
   &email.IsAuthenticationReqd = True;

   &email.SMTPUserName = "SomeLoginName";
   &email.SMTPUserPassword = "SomeLoginPassword";

   Local integer &res = &email.Send();
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Using an SSL Connection to Send Email

The following code example uses an SSL connection to send an email message:

```
import PT_MCF_MAIL:*;

Local PT_MCF_MAIL:MCFOutboundEmail &email = create PT_MCF_MAIL:MCFOutboundEmail();

&email.From = &FromAddress;
&email.Recipients = &ToList;
&email.Subject = &Subject;
&email.Text = &MailBody;

&email.SMTPServer = "MySMTPServer";
&email.IsAuthenticationReqd = True;

&email.SMTPUserName = "SomeLoginName";
&email.SMTPUserPassword = "SomeLoginPassword";
&email.SMTPUseSSL = "Y";
&email.SMTPSSLClientCertAlias = &cAlias;
&email.SMTPSSLPort = &SSLPort;

Local integer &res = &email.Send();
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Chapter 27

MCF IM Classes

Understanding the MCFIMInfo Class

This section provides an overview of:

- Using the MCFIMInfo class.
- Data type for MCFIMInfo objects.
- Scope of MCFIMInfo objects.

Use the MCFIMInfo class to launch an instant messaging session from a PeopleSoft page and initiate a chat. A developer can use either the PeopleCode class or a push-button with specific characteristics in Application Designer to initiate an instant messaging session.

Note: PeopleSoft recommends using the Application Designer push-button rather than PeopleCode in most applications. The PeopleCode program determines user presence information from the application server, whereas the push-button determines user presence from the browser. The application server must wait until it has *all* the presence information for that page before it can render the page. Though this processing is multi-threaded, it can still be slower than the push-button.

Related Links

"Understanding Instant Messaging" (PeopleTools 8.54: MultiChannel Framework)

Using the MCFIMInfo Class

Only use the MCFIMInfo class if your application requires the flexibility the PeopleCode can provide. The only supported networks are AOL and Yahoo. SameTime is supported using the Application Designer push-button, but not in PeopleCode.

Instant messages are sent by using the native instant message clients. This means that you can only use this for Microsoft Windows.

The page from which you launch the instant messaging session must be refreshed in order to update presence status.

Data Type for MCFIMInfo Objects

MCFIMInfo objects are declared as type MCFIMInfo. For example:

```
Local MCFIMInfo &MyChat;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Scope of MCFIMInfo Objects

An MCFIMInfo object can be only instantiated from PeopleCode.

Use this object only in PeopleCode programs that are associated with an online process, not in an Application Engine program, a message subscription, a Component Interface, and so on.

Understanding the MCFIMSingleButton Class

Use the MCFIMSingleButton class to generate a single presence icon that displays all specified screen names. When a user moves the mouse pointer over a single presence icon, it will open a menu with all specified user screen names and their current online status.

Related Links

"Using Single Button Presence" (PeopleTools 8.54: MultiChannel Framework)

Importing the MCFIMSingleButton Class

The MCFIMSingleButton class is an application classes, not a built-in class, like Rowset, Field, Record, MCFIMInfo, and so on. Before you can use this class in your PeopleCode program, you must import it into your program. An import statement either names a particular application class or imports all the classes in a package. Using the asterisks after the package name makes all the application classes directly contained in the named package available. Application classes contained in subpackages of the named package are not made available.

To import the MCFIMSingleButton class, use the following import statement:

```
import PT_MCF_IM:*;
```

MCFIMInfo Class Built-in Functions

"CreateMCFIMInfo" (PeopleTools 8.54: PeopleCode Language Reference)

MCFIMInfo Class Methods

In this section, the MCFIMInfo class methods are presented in alphabetical order.

AddUser

Syntax

AddUser(*User*)

Description

Use the AddUser method to add a user to the instant messaging session.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

User	Specify the user that you want to add to the instant messaging session, as a string.

Returns

A Boolean value: True if the user was successfully added, False otherwise.

CheckAll

Syntax

`CheckAll``()`

Description

Use the CheckAll method to check the status of users on the instant messaging session.

This method makes the actual network requests to retrieve presence information.

Parameters

None.

Returns

A Boolean: True if the check is successful, False otherwise.

GetAdditionalUserInfo

Syntax

`GetAdditionalUserInfo``()`

Description

This method returns additional user information.

Parameters

None.

Returns

String.

GetErrorImageName

Syntax

`GetErrorImageName``()`

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use GetErrorImageName to return the name of the image used for errors.

Parameters

None.

Returns

String.

GetOffLineImageName

Syntax

GetOffLineImageName()

Description

Use GetOffLineImageName to return the name of the image used to indicate off line status.

Parameters

None.

Returns

String.

GetOnlineImageName

Syntax

GetOnlineImageName()

Description

Use GetOnlineImageName to return the name of the image used to indicate online status.

Parameters

None.

Returns

String.

GetUnknownImageName

Syntax

GetUnknownImageName()

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use GetUnknownImageName to return the image of unknown users.

Parameters

None.

Returns

String.

GetLaunchURL

Syntax

GetLaunchURL(*User*)

Description

Use the GetLaunchURL method to return the URL that launches the native client and contacts the user. This is a local URL of one of the following forms:

`aim:. . .`

or

`ymsgr:. . .`

Parameters

User	Specify the user that you want to contact via the launch URL.

Returns

A string representing the URL to launch the native client.

GetStatus

Syntax

GetStatus(*User*)

Description

Use the GetStatus method to return the current online status of the user specified by *User*. This is the status at the time of the last call to **CheckAll**.

Parameters

User	Specify the name of the user for whom you want to check the status of.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

An integer. The values are:

Value	*Description*
-1	Network Disabled
0	User offline
1	User online
2	User Unknown
3	Error

RemoveUser

Syntax

RemoveUser(*User*)

Description

Use the RemoveUser method to remove a user from the instant messaging session.

Parameters

User Specify the name of the user you want to remove from the session, as a string.

Returns

A Boolean value: True if the user was successfully removed, False otherwise.

MCFIMSingleButton Class Methods

In this section, the MCFIMSingleButton class methods are presented in alphabetical order.

Related Links

"Developing a Sample Application with Single Presence Button" (PeopleTools 8.54: MultiChannel Framework)

generateHTML

Syntax

generateHTML(*&RS*, *slide_dir*, *X_pos*, *Y_pos*, *width*, *height*, *seq_num*)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use this method to generate the HTML code as a string that is needed to display the single presence IM button on a page.

Parameters

&RS	Specifies the Rowset object that contains the IM user IDs, protocols, domains, and other IM information in the format of the MCF_IMSCRNNAMES record.
slide_dir	Specifies the direction of the sliding window as a string. Valid values are: left, right, up, down.
X_pos	Specifies the X coordinate (in pixels) of the sliding window's upper left corner as an Integer.
Y_pos	Specifies the Y coordinate (in pixels) of the sliding window's upper left corner as an Integer.
width	Specifies the minimum width of the sliding window as an Integer (in pixels)
height	Specifies the minimum height of the sliding window as an Integer (in pixels)
seq_num	Specifies a unique sequence number for this single presence button as an Integer. If there is more than one single presence button per page, each needs to be identified with a unique sequence number.

Returns

A string representing the HTML code for the single presence button.

Example

Use the page activate event to place the single presence button on a page:

```
import PT_MCF_IM:*;

Global PT_MCF_IM:MCFIMSingleButton &single;
Local Rowset &RS1;

&single = create PT_MCF_IM:MCFIMSingleButton();
/* Number of milliseconds that we want to show sliding window even after we   */
/* remove cursor from single presence button.                                 */

&single.hideDelay = 5325;
&RS1 = CreateRowset(Record.MCF_IMSCRNNAMES);
/* &RS1 have all screen names, right is direction of sliding window. 190 is   */
/* X coordinate of top left corner of sliding window, 200 is Y coordinate of  */
/* top left corner of sliding window, 350 is height of sliding window, 450    */
/* is width of sliding window,  1 is some unique no of sliding window on that */
/* page. If there are many single presence icons on page, then it would be    */
/* useful for uniqness.                                                       */

RECORDNAME.MCF_IM_HTMLAREA.Value = &single.generateHTML(&RS1, "right", 190, 200, 35⇒
0, 450, 1);
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
RECORDNAME.MCF_XMPPHEADER = &single.generateJavaScript();
```

Related Links

generateJavaScript

generateJavaScript

Syntax

generateJavaScript()

Description

Use this method to generate JavaScript code that will be used to show single button presence. Call this method only after calling generateHTML.

Parameters

None.

Returns

A string representing the JavaScript code.

Related Links

generateHTML

insertXMPPServerUserData

Syntax

insertXMPPServerUserData(*PS_user_ID*, *protocol*, *XMPP_domain*, *IM_user_ID*, *IM_pwd*)

Description

Use this method to insert a row of user data into the PS_MCF_USER_IM_CFG table.

Parameters

None.

PS_user_ID	Specifies the PeopleSoft user ID as a string.
protocol	Specifies the XMPP protocol as a string. The only valid value is: XMPP.
XMPP_domain	Specifies the XMPP domain name as a string.
IM_user_ID	Specifies the email user ID on the XMPP server as a string. For example, if the email ID is first.last@company.com, then the *IM_user_ID* parameter must be set to: first.last.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

IM_pwd	Specifies the password for the email user ID as a string.

Returns

A Boolean value: True if insert was successful, False otherwise.

MCFIMSingleButton

Syntax

MCFIMSingleButton()

Description

Use this constructor to instantiate a MCFIMSingleButton object.

Parameters

None.

Returns

A MCFIMSingleButton object.

updateXMPPServerUserData

Syntax

updateXMPPServerUserData(*PS_user_ID*, *protocol*, *XMPP_domain*, *IM_user_ID*, *IM_pwd*)

Description

Use this method to update a row of user data in the PS_MCF_USER_IM_CFG table.

Parameters

None.

PS_user_ID	Specifies the PeopleSoft user ID as a string.
protocol	Specifies the XMPP protocol as a string. The only valid value is: XMPP.
XMPP_domain	Specifies the XMPP domain name as a string.
IM_user_ID	Specifies the email user ID on the XMPP server as a string. For example, if the email ID is first.last@company.com, then the *IM_user_ID* parameter must be set to: first.last.
IM_pwd	Specifies the password for the email user ID as a string.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

A Boolean value: True if update was successful, False otherwise.

MCFIMSingleButton Class Properties

In this section, the MCFIMSingleButton class properties are presented in alphabetical order.

hideDelay

Description

Use this property to set or return an Integer value representing a delay in milliseconds. A user removes the mouse pointer from the single presence button, the delay determines the amount of time the menu remains displayed before it is hidden. The default value is 1,325 milliseconds.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Chapter 28

Message Classes

Understanding Message Classes

You can create the following types of messages using PeopleSoft Pure Internet Architecture::

- *Rowset-based* messages, which use record definitions to create a hierarchical structure for the data. These are generally used for data from applications, pages, components, and so on.
- *Nonrowset-based* messages, which do not use record definitions. These messages can have virtually any content or structure.
- *Container* messages, which are messages made up of one or more part messages.

Use the PeopleCode message classes to instantiate message objects based on existing message definitions, as well as to populate the objects with data and manipulate the data. You can also use PeopleCode to publish a message.

Rowset-based messages are built on top of the rowset, row, record, and field classes, so the PeopleCode written to populate or access those types of messages looks similar to PeopleCode written to populate or access the component buffer.

Nonrowset-based messages contain XML data, and can be accessed using the XmlDoc class methods and properties.

Container messages contain parts. Each part is a separate message. A container message can contain either all rowset-based messages, *or* all nonrowset-based messages.

Related Links

"Adding Message Definitions" (PeopleTools 8.54: Integration Broker)

"Understanding Data Buffer Access" (PeopleTools 8.54: PeopleCode Developer's Guide)

"Introduction to PeopleSoft Integration Broker" (PeopleTools 8.54: Integration Broker)

Messages, Service Operations and Handlers

Message definitions only define the shape of the data contained in a message. A message definition doesn't contain any other type of information, such as if the message is being used synchronously or if it's a response message.

After you create a message definition, you can use it in or more service operations. The service operation contains all the information about how the message is to be used, the routing, the queue if appropriate, and so on.

At least one handler is defined with every service operation. Handlers define additional programming to be used with processing the message associated with the service operation. The handlers can be thought of as corresponding to pre PeopleSoft 8.48 message events.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The PeopleCode for the various handlers is contained in the Integration Broker application classes.

Integration Broker Application Classes

The Integration Broker application classes house the processing logic for asynchronous and synchronous messages. By implementing the Integration Broker application classes, you can reuse code more easily and access the other benefits of using application classes.

The following application classes are defined for Integration Broker. To access these application classes, in PeopleTools Application Designer, open the PS_PT application package, then open the Integration subpackage.

All of the Integration Broker application classes are defined as interfaces. This means that there is no native implementation of them: you must import them to your program and implement them if you want to use them.

Application Class	***Methods Contained in Application Class***	***Comments***
INotificationHandler	OnNotify OnError	This interface is the equivalent of the Subscription event in releases prior to PeopleTools 8.48.
IPrePostNotification	OnPreNotify OnPostNotify OnError	This interface provides pre-processing and post-processing of segmented messages.
IReceiver	OnAckReceive OnError	This interface is the equivalent of the OnAckReceive Message event in releases prior to PeopleTools 8.48.
IRequestHandler	OnRequest OnError	This interface is the equivalent of the OnRequest Message event in releases prior to PeopleTools 8.48.
IRouter	OnRouteSend OnRouteReceive OnError	This interface is the equivalent of the OnRouteSend and OnRouteReceive Message events in releases prior to PeopleTools 8.48.
ISend	OnRequestSend OnError	This interface is the equivalent of the OnSend Message event in releases prior to PeopleTools 8.48.

Data Types of Message Objects

Every message class is its own data type, that is, messages are declared as data type Message, IntBroker objects are declared as type IntBroker, and so on.

The following are the data types of the message classes:

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- Message
- IntBroker
- IBInfo
- IBConnectorInfo

Scope of Message Objects

The message objects can only be instantiated from PeopleCode. These objects can be used anywhere you have PeopleCode, that is, in Component Interface PeopleCode, notification PeopleCode, record field PeopleCode, application engine PeopleCode, and so on.

Message Object Population

After you've declared and instantiated your message object, you want to populate it with data. If your data is coming from the component buffers, populating your message is easy.

A message definition can contain a hierarchy of records. A component buffer contains a hierarchy of records. If you want to copy data from a component buffer rowset to a message, the *structure* of the message and the component must be the same. That is, if you have a record at level two in your message and you want that data, you must have the same level zero and level one records in your message as in your component.

For example, suppose your component had the following structure (that is, that PO_INFO and PO_LINE are at the same level, and PO_DETAIL is the child of PO_INFO):

```
PO_HEADER
   PO_LINE
   PO_INFO
      PO_DETAIL
```

To include the information in the PO_DETAIL record, you must have *at least* the following record structure in your message:

```
PO_HEADER
   PO_INFO
      PO_DETAIL
```

Any records that are in the page that aren't in the message (and vice-versa) are ignored.

After you get your message object, you can create a rowset from it. This rowset has the same structure as the message. If the message is empty, the rowset has no data. If the message has data, the rowset is automatically populated.

The following example is the simplest way of populating a message with data. This assumes that the structure of the message is the same as the structure of the page.

```
         /* this gets all the data in the Component buffer */

&RS = GetLevel0();/* this instantiates a message object */
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
&MSG = CreateMessage(OPERATION.MY_MESSAGE);/* creates a rowset with the same struct⇒
ure as the message */

&MSG_RS = &MSG.GetRowset();/* this copies all the data from the page to the message⇒
 */

&RS.CopyTo(&MSG_RS);/* this publishes the message */

%IntBroker.Publish(&MSG_RS);
```

A message rowset is the same as a Component buffer rowset, or any other rowset. It is composed of rows, records, and fields. Suppose you didn't want to get all the data from the Component buffer, but instead wanted to populate just a particular record in your message.

To access a record in a message rowset is the same as accessing a record in a component buffer rowset. You must instantiate the rowset, then specify the row before you can access the record.

The following selects values into a record, then uses the record method CopyFieldTo to copy from the Component buffer record to the message record.

```
Local SQL &LN_SQL;
Local Message &MSG;
Local Rowset &HDR_RS, &LN_RS;
Local Record &LN_REC, &ln_rec_msg;

&MSG = CreateMessage(OPERATION.STOCK_REQUEST);
&HDR_RS = &MSG.GetRowset();
&LN_REC = CreateRecord(Record.DEMAND_INF_INV);

&LN_SQL = CreateSQL("Select * from PS_DEMAND_INF_INV where  BUSINESS_UNIT= :1 and O⇒
RDER_NO = :2", &BUSINESS_UNIT, &ORDER_NO);

&J = 1;
While &LN_SQL.Fetch(&LN_REC)

  /* copy data into the Level 1 of &MSG object */
  &LN_RS = &HDR_RS(&I).GetRowset(1);

  If &J > 1 Then
    &LN_RS.InsertRow(&J - 1);
  End-If;

  &ln_rec_msg = &LN_RS.GetRow(&J).GetRecord(Record.DEMAND_INF_INV);
  &LN_REC.CopyFieldsTo(&ln_rec_msg);
  &J = &J + 1;
End-While;
```

This section also discusses items to keep in mind when:

- Populating a rowset from a message.
- Publishing and subscribing to partial records.
- Subscribing to character fields.

Considerations When Populating a Rowset From a Message

Suppose your message had two rowsets, one at level zero, a second at level one. In the message, only the level zero rowset contains any data. When you use GetRowset to create a rowset for the entire message, the rowset at level one will contain an empty row, even if there isn't any data in it. (This is standard behavior for *all* rowsets.) However, you can use the IsChanged property on the record object to determine the status of the data.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The following notification PeopleCode example traverse the rowset. (Notice the use of ChildCount, ActiveRowCount, and IsChanged properties).

'. . .' is where application specific code would go.

```
&MSG_ROWSET = &MSG.GetRowset();
For &A0 = 1 To &MSG_ROWSET.ActiveRowCount

/****************************/
/* Process Level 1 Records */
/*--------------------------*/

  If &MSG_ROWSET(&A0).ChildCount > 0 Then
  For &B1 = 1 To &MSG_ROWSET(&A0).ChildCount

    &LEVEL1_ROWSET = &MSG_ROWSET(&A0).GetRowset(&B1);
      For &A1 = 1 To &LEVEL1_ROWSET.ActiveRowCount
        If &LEVEL1_ROWSET(&A1).GetRecord(1).IsChanged Then
          . . .

/****************************/
/* Process Level 2 Records */
/*--------------------------*/

          If &LEVEL1_ROWSET(&A1).ChildCount > 0 Then
          For &B2 = 1 To &LEVEL1_ROWSET(&A1).ChildCount
            &LEVEL2_ROWSET = &LEVEL1_ROWSET(&A1).GetRowset(&B2);
              For &A2 = 1 To &LEVEL2_ROWSET.ActiveRowCount
                If &LEVEL2_ROWSET(&A2).GetRecord(1).IsChanged Then
                .  .  .

/****************************/
/* Process Level 3 Records */
/*--------------------------*/

                If &LEVEL2_ROWSET(&A2).ChildCount > 0 Then
                  For &B3 = 1 To &LEVEL1_ROWSET(&A2).ChildCount
                    &LEVEL3_ROWSET = &LEVEL2_ROWSET(&A2).GetRowset(&B3);
                    For &A3 = 1 To &LEVEL3_ROWSET.ActiveRowCount
                      If &LEVEL3_ROWSET(&A3).GetRecord(1).IsChanged Then
                      .  .  .

                      End-If; /* A3 - IsChanged */
                    End-For; /* A3 - Loop */
                  End-For; /* B3 - Loop */
                End-If; /* A2 - ChildCount > 0 */

/*--------------------------------*/
/* End of Process Level 3 Records */
/**********************************/

              End-If; /* A2 - IsChanged */
            End-For; /* A2 - Loop */
          End-For; /* B2 - Loop */
        End-If; /* A1 - ChildCount > 0 */

/*--------------------------------*/
/* End of Process Level 2 Records */
/**********************************/

      End-If; /* A1 - IsChanged */
    End-For; /* A1 - Loop */
   End-For; /* B1 - Loop */
  End-If; /* A0 - ChildCount > 0 */

/*--------------------------------*/
/* End of Process Level 1 Records */
/**********************************/

End-For; /* A0 - Loop */
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Considerations for Publishing and Subscribing to Partial Records

If you've selected to not publish all the fields in the message, you must be careful when inserting that data into a record.

Deselecting the Include check box in the message definition means that the field is *excluded* from the message definition.

- The field won't be included when generating an XML document (when publishing a message.)
- If the field is present in the XML (that is, it wasn't excluded from the published message) it is ignored by the subscribing system.

When you insert the data from the message into the database, you *must* set the values for the fields that aren't in the message. You can use the SetDefault record class method to do this. You could also use a Component Interface based on the component the message was created from to leverage the component defaults.

Related Links

SetDefault

"Understanding Creating Component Interface-Based Services" (PeopleTools 8.54: Integration Broker)

Considerations When Subscribing to Character Fields

If a message definition has character fields that are defined as uppercase, when the message is subscribed to, character data for those fields is automatically converted to uppercase.

Message Segments

To make processing more efficient, you can divide a large message into pieces using message segments. Generally, you only divide asynchronous messages into segments.

Message nodes can be specified as “segment aware”. If a node is not segment aware and you send an asynchronous message that is segmented to it, you received an error message when viewing the error message log in message details on the message monitor. No publication contracts are created. If you send a synchronous message that is segmented to a node that is not segment aware, you receive an error.

There are several methods for creating, updating, and deleting segments. There are also two properties that you need to take into consideration when working with segments.

If you specify the SegmentsByDatabase property as false, you can only have the configured number defined in PSADMIN (Message Segment From DB). If you specify this property as true, you can have as many segments as you need.

The SegmentsByDatabase property also specifies whether the segments are kept in memory or written to the database when they are received. If you specify true, the segments are automatically written to the database. If you specify false, the segments are held in memory. If you specify true, then cancel out of the program processing the segments, the changes are not committed to the database.

The SegmentUnOrder property is only applicable for asynchronous messages. If you specify the SegmentUnOrder property as true, the receiving node processes the segments in parallel.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Note: You should use DeleteSegment and UpdateSegment only when writing to memory, or when SegmentsByDatabase is set to False. These methods do not work when writing to the database, or when SegmentsByDatabase is set to True.

The following is an example of how to use the segment properties and methods to send a segmented message. Note that there are only two CreateNextSegment calls. By default the first segment is automatically created. The first time you use CreateNextSegment, the message is split into two segments. The next time, you add a third segment. You don't need to call CreateNextSegment to access the third segment, it's automatically generated.

```
Local Message &MSG;
Local Rowset &FLIGHT_PROFILE, &RS;
Local boolean &Bo, &Stuff;
Local string &lip;

&nodes = CreateArray("");
&nodes[1] = "QE_YO";
&nodes[2] = "QE_STUFF";

QE_FLIGHTDATA.QE_ACNUMBER.Value = QE_FLIGHTDATA.QE_ACNUMBER + 1;

&FLIGHT_PROFILE = GetLevel0();

&MSG = CreateMessage(OPERATION.QE_FLIGHTPLAN);

/* the next lines copy the rowset into the first segment */

&MSG.CopyRowset(&FLIGHT_PROFILE);
&MSG.CreateNextSegment();

/* This copies the next portion of the rowset into the next segment */

&MSG.CopyRowset(&FLIGHT_PROFILE);
&MSG.CreateNextSegment();

/* This copies the last portion of the rowset into the third segment */

&MSG.CopyRowset(&FLIGHT_PROFILE);

/* This specifies that the message segments can be processed separately */

&MSG.IBInfo.SegmentsUnOrder = True;

%IntBroker.publish(&MSG);
```

The following is an example of receiving a segmented message. This would be found in a notification PeopleCode program:

```
Local Message &MSG;
Local Rowset &rs, &rs1;
Local Record &FLIGHTDATA, &REC;

Local string &acnumber_value, &msi_sensor_value, &ofp_value, &actype_value, &callsi⇒
gn_value, &squadron_value, &comm1_value, &comm2_value, &ecm_value;

Local XmlDoc &xmldoc;
Local string &yo;
Local boolean &bo;

&CRLF = Char(13) | Char(10);

&MSG = %IntBroker.GetMessage();

/* It is very important to set the rowset to null for every iteration */

/* Also, you may want to verify if the segment count is
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
greater than 10, and if it is, set the SegmentsByDatabase property to True */

For &i = 1 To &MSG.SegmentCount
   &rs = Null;
   &MSG.GetSegment(&i);

   &rs = &MSG.GetRowset();
   &REC = &rs(1).QE_FLIGHTDATA;

   &FLIGHTDATA = CreateRecord(Record.QE_FLIGHTDATA);
   &REC.CopyFieldsTo(&FLIGHTDATA);

   /* Parse out Message Data */
   &acnumber_value = &FLIGHTDATA.QE_ACNUMBER.Value;
   &msi_sensor_value = &FLIGHTDATA.QE_MSI_SENSOR.Value;
   &ofp_value = &FLIGHTDATA.QE_OFP.Value;
   &actype_value = &FLIGHTDATA.QE_ACTYPE.Value;
   &callsign_value = &FLIGHTDATA.QE_CALLSIGN.Value;
   &squadron_value = &FLIGHTDATA.QE_SQUADRON.Value;
   &comm1_value = &FLIGHTDATA.QE_COMM1.Value;
   &comm2_value = &FLIGHTDATA.QE_COMM2.Value;
   &ecm_value = &FLIGHTDATA.QE_ECM.Value;

   &outstring = "Send Async FLight test";

   /* Construct Output String */
   &outstring = &outstring | &acnumber_value | &CRLF | &msi_sensor_value | &CRLF | ⇒
&ofp_value | &CRLF | &actype_value | &CRLF | &callsign_value | &CRLF | &squadron_va⇒
lue | &CRLF | &comm1_value | &CRLF | &comm2_value | &CRLF | &ecm_value;

   /* Log Output String into page record */
   &FLIGHTDATA.GetField(Field.DESCRLONG).Value = &outstring;

   SQLExec("DELETE FROM PS_QE_FLIGHTDATA");
   &FLIGHTDATA.Insert();

End-For;
```

Related Links

CreateNextSegment

SegmentsByDatabase

SegmentsUnOrder

"Understanding Nodes" (PeopleTools 8.54: Integration Broker Administration)

Content-Based Routing

With PeopleSoft Integration Broker, you typically define the routing information separately from the message itself. This allows you to apply multiple routings to a message and change the routings independent of the message definition.

With content-based routing, attributes of the message are used to make routing decisions. The attributes are set before the message is published. Then, within your implementation of the IRouter.OnRouteSend method, these attributes can be examined and evaluated—for example, to send the message to a defined list of nodes instead of to all nodes. Because the attributes are separate from the message data, the Message object itself does not have to be parsed and loaded into a rowset and then searched to get the routing information. This separation of routing attributes from the message data provides a performance improvement over having those routing attributes within the message content.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

In the following example, the routing attributes are set with calls to the AddAttribute method of the IBInfo class:

```
Local Message &MSG;
Local Rowset &FLIGHT_PROFILE;
Local string &AC_Type, &Pilot;
Local boolean &bRet;

&FLIGHT_PROFILE = GetLevel0();

&MSG = CreateMessage(Operation.QE_FLIGHTPLAN);

&AC_Type = GetLevel0().GetRow(1).GetRecord(Record.QE_FLIGHTDATA).AC_TYPE.Value;
&Pilot = GetLevel0().GetRow(1).GetRecord(Record.QE_FLIGHTDATA).PILOT.Value;

&bRet = &MSG.IBInfo.AddAttribute("ACType", &AC_Type);
&bRet = &MSG.IBInfo.AddAttribute("Pilot", &Pilot);

&MSG.CopyRowset(&FLIGHT_PROFILE);

%IntBroker.Publish(&MSG);
```

Then, in the implementation-specific IRouter.OnRouteSend method, the message attributes are evaluated to make routing decisions. The OnRouteSend method does not load and examine the Message object itself, only the attributes:

```
import PS_PT:Integration:IRouter;

class RoutingHandler implements PS_PT:Integration:IRouter;
   method RoutingHandler();
   property array of any destinationNodes;
   method OnRouteSend(&MSG As Message) Returns integer;
   method GetDestinationList(&AC_Type As string, &Pilot As string) Returns any;

end-class;

/* constructor */
method RoutingHandler
end-method;

method OnRouteSend
   /+ &MSG as Message +/
   /+ Returns Integer +/
   /+ Extends/implements PS_PT:Integration:IRouter.OnRouteSend +/
   /* Variable Declaration */
   Local string &AC_Type;
   Local string &Pilot;
   Local any &aNodeList;
   Local integer &i;

   If &MSG.IBInfo.GetNumberOfAttributes() = 0 Then
      Return (%IntBroker_ROUTE_NONE);
   End-If;

   For &i = 1 To &MSG.IBInfo.GetNumberOfAttributes()

      If &MSG.IBInfo.GetAttributeName(&i) = "ACType" Then
         &AC_Type = &MSG.IBInfo.GetAttributeValue(&i);
      End-If;

      If &MSG.IBInfo.GetAttributeName(&i) = "Pilot" Then
         &Pilot = &MSG.IBInfo.GetAttributeValue(&i);
      End-If;

   End-For;
   /* method evaluates these strings and return NodeList */
   &aNodeList = %This.GetDestinationList(&AC_Type, &Pilot);
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
   Evaluate &aNodeList
   When "True"
      Return (%IntBroker_ROUTE_ALL);
      Break;
   When "False"
      Return (%IntBroker_ROUTE_NONE);
      Break;
   When-Other
      &destinationNodes = &aNodeList.Clone();
      Break;
   End-Evaluate;

end-method;

method GetDestinationList
   /+ &AC_Type as String, +/
   /+ &Pilot as String +/
   /+ Returns Any +/

   /* determine node list based on input data */

   Return Null;
end-method;
```

Related Links

AddAttribute

GetAttributeName

GetAttributeValue

GetNumberOfAttributes

Error Handling

In your notification PeopleCode, you may want to validate the information received in the message. If you find that the data isn't valid, use Exit(1) to end your PeopleCode program. This sets the status of the message to ERROR, logs any error messages to the Application Message Queues, and automatically rolls back any database changes you may have made.

There are many ways to validate the data and capture the error messages:

- Use ExecuteEdits on the message object
- Use ExecuteEdits on the record object
- Use a Component Interface

Write your own validation PeopleCode in the notification program:

The following example validates the Business Unit of a message against an array of valid BU's:

```
For &I = 1 To &ROWSET.RowCount;

  &POSITION = &BUArray.Find(&ROWSET(&I).GetRecord(1).BUSINESS_UNIT.Value);
  If &POSITION = 0 Then
    &Status = "ERROR: BU not Found or not Active";
    &ROWSET(&I).BCT_ADJS_MSG_VW.BUSINESS_UNIT.IsEditError = True;
    &ROWSET(&I).BCT_ADJS_MSG_VW.BUSINESS_UNIT.MessageSetNumber = 11100;
    &ROWSET(&I).BCT_ADJS_MSG_VW.BUSINESS_UNIT.MessageNumber = 1230;
/* The error message 11100-1230 reads: This Business Unit is */
/* not a valid, open, Inventory Business Unit */
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
  End-If;
End-For;
```

In the calling PeopleCode, the program calls Exit(1) based on the value of &Status.

Note: All errors for notification PeopleCode get logged to the application message error table, *not* to the PSMessages collection (on the session object.)

Related Links

ExecuteEdits
ExecuteEdits
"Processing Inbound Errors" (PeopleTools 8.54: Integration Broker)

Message Classes Reference

This reference section documents the following message classes and functions:

- Message class built-in functions.
- Message class.
- IntBroker class.
- IBInfo class.
- IBConnectorInfo collection.

Message Class Built-In Functions

"AddSystemPauseTimes" (PeopleTools 8.54: PeopleCode Language Reference)

"CreateMessage" (PeopleTools 8.54: PeopleCode Language Reference)

"DeleteSystemPauseTimes" (PeopleTools 8.54: PeopleCode Language Reference)

"PingNode" (PeopleTools 8.54: PeopleCode Language Reference)

"ReValidateNRXmlDoc" (PeopleTools 8.54: PeopleCode Language Reference)

Message Class Methods

In this section, we discuss the Message class methods. The methods are discussed in alphabetical order.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Clone

Syntax

Clone()

Description

The Clone method creates an identical copy of the message, copying the data tree of the message executing the method. The Clone function sets the following properties for the resulting message object, based on the values set for the message definition created in Pure PeopleSoft Internet Architecture:

- Name
- QueueName
- IsOperationActive

Other properties are set when the message is published or subscribed to (TransactionID, PubNodeName, and so on), or are dynamically generated at other times (Size, IsEditError, and so on.)

Clone creates a unique version of the message. If the original message changes, it is not reflected in the cloned object.

Parameters

None.

Returns

A message object.

Example

Clone could be used in a Hub and Spoke messaging environment. The Hub node uses this method during notification processing to publish a copy of the messages it receives from the Spokes.

```
&Msg = %IntBroker.GetMessage();
&Rowset = &Msg.GetRowset();
&Clone = &Msg.Clone();

%IntBroker.Publish(&Clone);
```

The hub's publication routing rules are then used to determine which spokes receive the message.

Related Links

CopyRowset

"CreateMessage" (PeopleTools 8.54: PeopleCode Language Reference)

"Assigning Objects" (PeopleTools 8.54: PeopleCode Developer’s Guide)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

CopyPartRowset

Syntax

CopyPartRowset(*PartIndex, &Rowset*)

Description

Use the CopyPartRowset to copy the rowset specified by *&Rowset* to the part of the message specified by *PartIndex*.

Note: This method only works with rowset-based container messages.
The primary record of the level zero rowset for both the specified message part and the specified rowset must be the same.

Parameters

PartIndex	Specify the number of the part you want to copy the rowset data to.
&Rowset	Specify an already instantiated rowset object that contains the data that you want to copy to the message part.

Returns

None.

Related Links

GetPartRowset
GetPartXMLDoc

CopyRowset

Syntax

CopyRowset(*source_rowset* [, *record_list*]);

Where *record_list* is a list of record names in the form:

RECORD.*source_recname1*, RECORD.*target_recname1*

[, RECORD.*source_recname2*, RECORD.*target_recname2*]. . .

Description

The CopyRowset method copies data from the source rowset to the like-named fields in the message object executing the method. This is an easy way to populate a message with data from a component.

Note: CopyRowset does not copy effective dated fields.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Note: CopyRowset copies the data, including rows that haven't been modified. If you want to copy only data that has changed in some way, use the CopyRowsetDelta method.

See CopyRowsetDelta.

When the record names in the message and component do not match exactly, use the optional *record_list* to specify the records to be copied from the component into the message.

When you use the CopyRowset method to copy the contents from the source rowset to the message object, you are creating a *unique* copy of the object. If you change the original rowset, the message object is not changed.

Note: You can execute CopyRowset against a message only once. After a message is populated, any other CopyRowsets are ignored. If you have to populate different levels of a message rowset separately, you can use the CreateRowset method to create a rowset that has the same structure as your message, populate the created rowset, then use CopyRowset to populate your message. You can also use the Rowset CopyTo method to populate a message rowset, then populate the PSCAMA record by hand.

Parameters

source_rowset	Specifies the name of the rowset to be copied into the message object.
record_list	Specifies specific source and target records to be copied into the message object.

Returns

None.

Example

The following example copies an entire component into a message object.

```
&Msg = %IntBroker.GetMessage();
&Rowset = &Msg.GetRowset()
&Component_Rowset = GetLevel0();
&Msg.CopyRowset(&Component_Rowset);
```

The following example copies a header/line page rowset into a header/line message object, using the *record_list* because the record names don't match:

```
&Msg = %IntBroker.GetMessage();
&Rowset= &Msg.GetRowset();
&Component_Rowset = GetLevel0();
&Msg.CopyRowset(&Component_Rowset, RECORD.PO_HDR_VW, RECORD.PO_HDR, RECORD.PO_LINE_⇒
VW, RECORD.PO_LINE);
```

Related Links

CopyRowsetDelta

"GetRowset" (PeopleTools 8.54: PeopleCode Language Reference)

Understanding Rowset Class

Fill

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

CopyRowsetDelta

Syntax

CopyRowsetDelta(*source_rowset* [, *record_list*]);

Where *record_list* is a list of record names in the form:

[RECORD.*source_recname1*, RECORD.*target_recname1*

[, RECORD.*source_recname2*, RECORD.*target_recname2*]]. . .

Description

The CopyRowsetDelta method copies rows of data that have changed from the source rowset to the like-named records and like-named fields in the message object executing the method.

Note: CopyRowsetDelta copies all the like-named fields from the changed *row*into the message. It is *not* copying just the changed like-named fields.

When the record names in the message and component do not match exactly, use the optional *record_list* to specify the records to be copied from the component into the message. The specified target records must be records in your message, while the specified source records must be records in a rowset that exists in the data buffer and is populated.

This is an easy way to populate a message when the records in the message match the records in the component that the message is published from.

In addition, the CopyRowsetDelta method sets the AUDIT_ACTN field in the PSCAMA table for every row in the message. The notification process can then use PSCAMA.AUDIT_ACTN to determine how to process every row that was published.

The set values match those used in audit trail processing, that is:

- A - Row inserted.
- D - Row deleted.
- C - Row changed (updated), but no key fields changed. The system copies the new value to the Message rowset.
- K - Row changed (updated), and at least one key field changed. The system copies the old value to the Message rowset and the new value (see "N").
- N - Row changed (updated), and at least one key field changed. The system copies the old value to the Message rowset and the new value (see "K").
- "" − blank value means that nothing on that row has changed. This is the default value, and is the value used to tag the parent rows of children that have changed.

Note: If a child row is inserted (or changed or deleted) CopyRowsetDelta also copies the parent row (and the parent row of that row, and so on, up to the top row) so the subscriber has a full picture of the transaction. A blank value is set in the AUDIT_ACTN field for these rows to let the subscriber know they don’t have to take action; the parent rows are there for reference only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The Audit_Action values "A", "C", "D" are set when a record is added, changed, or deleted, respectively. In some cases such as effective-dated records, the user may change a key field value, such as Effective Date. In response to such an user action, two records are created, one with an Audit_Action value of "N", and the other with Audit_Action value "K". The "N" record has all the new values, while the "K" record retains the old values.

When you use the CopyRowsetDelta method to copy the contents from the source rowset to the message object, you are creating a *unique* copy of the object. If you change the original rowset, the message object is not be changed.

Note: You can execute CopyRowsetDelta against a message only once. After a message is populated, any other CopyRowsetDeltas are ignored. If you have to populate different levels of a message rowset separately, you can use the CreateRowset method to create a rowset that has the same structure as your message, populate the created rowset, then use CopyRowsetDelta to populate your message. You can also use the Rowset CopyTo method to populate a message rowset, then populate the PSCAMA record by hand.

Parameters

source_rowset Specifies the name of the rowset to be copied into the message object.

record_list Specifies source and target records to be copied into the message object. The target records must be records in your message, while the source records must be records in a rowset that exists in the data buffer and is populated.

Returns

None.

Example

The following example copies all the changed rows of data from a component into a message object.

```
&Component_Rowset = GetLevel0();

&Msg.CopyRowsetDelta(&Component_Rowset);
```

Related Links

CopyRowset
"PSCAMA" (PeopleTools 8.54: Integration Broker)
"Assigning Objects" (PeopleTools 8.54: PeopleCode Developer's Guide)
Understanding Rowset Class
"GetRowset" (PeopleTools 8.54: PeopleCode Language Reference)

CopyRowsetDeltaOriginal

Syntax

CopyRowsetDeltaOriginal(*source_rowset* [, *record_list*]);

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Where *record_list* is a list of record names in the form:

```
[RECORD.source_recname1, RECORD.target_recname1

[, RECORD.source_recname2, RECORD.target_recname2]].
. .
```

Description

The CopyRowsetDeltaOriginal method copies rows of data that have changed from the source rowset to the like-named records and like-named fields in the message. It also copies the original value of the changed rows.

Note: CopyRowsetDeltaOriginal copies all the like-named fields from the changed and original *rows* into the message. It is not copying just the changed like-named fields.

When the record names in the message and component do not match exactly, use the optional *record_list* to specify the records to be copied from the component into the message. The specified target records must be records in your message, while the specified source records must be records in a rowset that exists in the data buffer and is populated.

The CopyRowsetDeltaOriginal method sets the AUDIT_ACTN field in the PSCAMA table for every row in the message. The notification process can then use PSCAMA.AUDIT_ACTN to determine how to process every row that was published.

The set values match those used in audit trail processing, that is:

- A - Row inserted.
- D - Row deleted.
- C - Row changed (updated), but no key fields changed. The system copies the new value to the Message rowset and the original value (see "O" below).
- O - Prior value of changed row. The system copies the new value to the Message rowset and the original value (see "C").
- K - Row changed (updated), and at least one key field changed. The system copies the original value to the Message rowset and the new value (see "N").
- N - Row changed (updated), and at least one key field changed. The system copies the original value to the Message rowset and the new value (see "K").
- "" − blank value means that nothing on that row has changed. This is the default value, and is the value used to tag the parent rows of children that have changed.

Note: If a child row is inserted (or changed or deleted) CopyRowsetDeltaOriginal also copies the parent row (and the parent row of that row, and so on, up to the top row) so the subscriber has a full picture of the transaction. A blank value is set in the AUDIT_ACTN field for these rows to let the subscriber know they don’t have to take action; the parent rows are there for reference only.

The Audit_Action values "A", "C", "D" are set when a record is added, changed or deleted, respectively. When a row is changed, two records are created, one with an Audit_Action of "C", the other with Audit_Action value of "O". The "C" record has all the new values, while the "O" record retains the original values. In some cases such as effective-dated records, a user may change a key field value, such

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

as Effective Date. In response to such an user action, two records are created, one with an Audit_Action value of "N", and the other with Audit_Action value "K". The "N" record has all the new values, while the "K" record retains the original values. The "N"/"K" combination is also created if both a key change and a non-key change is made on the same row of data.

The following table details the output from CopyRowsetDeltaOriginal:

User Action	***CopyRowsetDeltaOriginal Output***	***Comments***
Change a key.	"N" and "K" rows created.	The "K" row contains the original Key value, the "N" row, the new.
Change a Key + change a Non-Key.	"N" and "K" rows created only (that is: no "C"/"O" rows in that case).	The Key and Non-Key Original Values are both contained in the "K" row.
Change a Non-Key.	"C" and "O" rows created.	Original Value stored in "O" row.
Add non-effective dated row.	"A" row created.	No additional rows created.
Add effective-dated row and only 1 original effective-dated row exists.	"A" and "O" rows created.	"O" row contains the original effective dated row.
Add effective-dated row and more than 1 original effected dated rows exist.	"A" and "O" rows created.	"O" row contains data from row that cursor was on when the new row was added. For example: If a rowset contains two rows (01/01/1980 and 02/02/2000), the current row is the 01/01/1980 row and the user adds a new row with today's date. The original values contain the data from the 01/01/1980. Likewise, if a rowset contains two rows (01/01/1980 and 02/02/2000), the current row is the 02/02/2000 row and the user adds a new row with today's date. Then the original values contain the data from the 02/02/2000.
Delete a row	"D" row created.	No additional rows created.

When you use the CopyRowsetDeltaOriginal method to copy the contents from the source rowset to the message object, you are creating a unique copy of the object. If you change the original rowset, the message object is not changed.

Note: You can execute CopyRowsetDeltaOriginal against a message only once. After a message is populated, any other CopyRowsetDeltaOriginal PeopleCode statements are ignored. If you have to populate different levels of a message rowset separately, you can use the CreateRowset method to create a rowset that has the same structure as your message, populate the created rowset, then use CopyRowsetDeltaOriginal to populate your message. You can also use the Rowset CopyTo method to populate a message rowset, then populate the PSCAMA record manually.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

source_rowset	Specifies the name of the rowset to be copied into the message object.
record_list	Specifies source and target records to be copied into the message object. The target records must be records in your message, while the source records must be records in a rowset that exists in the data buffer and is populated.

Returns

None.

Example

```
Function Update_Dir(&MSGName As string)

  &MSGName = "OPERATION." | &MSGName;
  &MSG = CreateMessage(@(&MSGName));

  &PnlRowset = GetLevel0();
  &MSG.CopyRowsetDeltaOriginal(&PnlRowset);
  %IntBroker.Publish(&MSG);

End-Function;
```

Related Links

CopyRowset

CopyRowsetDelta

"PSCAMA" (PeopleTools 8.54: Integration Broker)

"Assigning Objects" (PeopleTools 8.54: PeopleCode Developer's Guide)

Understanding Rowset Class

CreateNextSegment

Syntax

`CreateNextSegment``()`

Description

Use the CreateNextSegment method to divide a message into segments. You generally only divide asynchronous messages that contain a large amount of data. This method is used only when creating a message for publication, not after a message has been published.

Parameters

None.

Returns

None.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

See Message Segments.

Related Links

CreateNextSegment
DeleteSegment
SegmentRestart
UpdateSegment
CurrentSegment
SegmentCount

DeleteSegment

Syntax

```
DeleteSegment(SegmentNumber)
```

Description

Use the DeleteSegment method to delete the specified segment. This method is used only when creating a message for publication, not after a message has been published.

Note: You should use DeleteSegment and UpdateSegment only when writing to memory, or when SegmentsByDatabase is set to False. These methods do not work when writing to the database, or when SegmentsByDatabase is set to True.

Parameters

SegmentNumber	Specify a number indicating which segment you want to delete from the unpublished message.

Returns

None.

Related Links

CreateNextSegment
GetSegment
UpdateSegment
CurrentSegment
SegmentCount

ExecuteEdits

Syntax

```
ExecuteEdits([editlevels]);
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

where *editlevels* is a list of values in the form:

```
editlevel1 [+ editlevel2] . . .]);
```

and where *editleveln* is one of the following system constants:

%Edit_DateRange

%Edit_OneZero

%Edit_PromptTable

%Edit_Required

%Edit_TranslateTable

%Edit_YesNo

Description

The ExecuteEdits method executes the standard system edits on every field for every record in the message executing the method. All edits are based on the record edits defined for the record that the message is based on. The types of edits performed depends on the *editlevel*. If no *editlevel* is specified, all system edits defined for the record definition are executed, that is:

- Reasonable Date Range (Is the date contained within plus or minus 30 days from the current date?)
- 1/0 (Do all 1/0 fields only contain 1 or 0?)
- Prompt Table (Is field data contained in the specified prompt table?)
- Required Field (Do all required fields contain data? For numeric or signed fields, it checks that they do not contain NULL or 0 values.)
- Translate Table (Is field data contained in the translate table?)
- Yes/No (Do all yes/no fields only contain only yes or no data?)

Note: ExecuteEdits does not perform any validation on DateTime fields.

If any of the edits fail, the status of the property IsEditError is set to True for the Message Object executing the method, and any Rowset, Row, Record, or Field Objects that could be instantiated from the same data as the Message Object. In addition, the Field class properties MessageNumber and MessageSetNumber are set to the number of the returned message and message set number of the returned message, for the field generating the error.

If you want to check the field values only for a particular record, you can use the ExecuteEdits method with a record object.

In addition, if you want to dynamically set the prompt tables used for a field (with the %EditTable function) you must use the SetEditTable method.

Considerations for ExecuteEdits and SetEditTable

If an effective date is a key on the prompt table, and the record being edited doesn't contain an effective-dated field, the current date/time is used as the key value.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

If a setID is a key on the prompt table, and the record being edited doesn't contain a setID field, the system looks for the setID on the other records in the current row first, then search parent rows.

Considerations for ExecuteEdits and Numeric Fields

A zero (0) might or might not be a valid value for a numeric field. ExecuteEdits processes numeric fields in different ways, depending on whether the field is required:

- If the numeric field is required: 0 is considered invalid.
- If the numeric field is not required: 0 is considered valid.

Parameters

editlevel

Specifies the standard system edits to be performed against every field on every record. If *editlevel* isn't specified, all system edits are performed. *editlevel* can be any of the following system constants:

- %Edit_DateRange
- %Edit_OneZero
- %Edit_PromptTable
- %Edit_Required
- %Edit_TranslateTable
- %Edit_YesNo

Returns

None.

Example

The following is an example of a call to execute Required Field and Prompt Table edits:

```
&MSG.ExecuteEdits(%Edit_Required + %Edit_PromptTable);
```

The following is an example showing how ExecuteEdits() could be used:

```
&MSG.ExecuteEdits();
If &MSG.IsEditError Then
  Exit(1);
End-If;
```

Related Links

SetEditTable
EditError
MessageNumber
MessageSetNumber
IsEditError

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ExecuteEdits
"Processing Inbound Errors" (PeopleTools 8.54: Integration Broker)

FirstCorrelation

Syntax

FirstCorrelation()

Description

Use this method within an Integration Broker OnPreNotify event on the subscribing node to determine if this is the first message with this correlation ID.

Parameters

None.

Returns

A Boolean value: True if this is the first message with this correlation ID, False if a previous message with the same correlation ID has already run the OnPreNotify event.

Example

To improve the performance of correlated messages with multiple segments, use the FirstCorrelation method to run the OnPreNotify event for the first correlated message only. On the first message to be published, set the InitializeConversationId property to True. After the message is published, retrieve the transaction ID from the message. This transaction ID should be used to set the conversation ID (that is, the correlation ID) for all subsequent messages to be published.

```
/* On the first message to be published */

&MSG.InitializeConversationId = True;
%IntBroker.Publish(&MSG);
&strCorrelationID = &MSG.TransactionId;

/* For all subsequent correlated messages */

&MSG.IBInfo.ConversationID = &strCorrelationID;
%IntBroker.Publish(&MSG);
```

Then, on the susbscribing node, use the FirstCorrelation method to run the OnPreNotify event one time only:

```
If &MSG.FirstCorrelation() = True Then

   /* process the OnPreNotify event logic */

End-If;
```

Related Links

InitializeConversationId
TransactionId
ConversationID

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

"Using the OnPreNotify and OnPostNotify PeopleCode Events" (PeopleTools 8.54: Integration Broker Administration)

GenXMLPartString

Syntax

GenXMLPartString(*PartIndex*)

Description

Use the GenXMLPartString to create an XML string based on the message part specified by *PartIndex*.

Note: This method only works with rowset-based container messages.

Parameters

PartIndex	Specify the number of the part that you want to generate an XML string for.

Returns

An XML string.

Related Links

GenXMLString
GetPartRowset
LoadXMLPartString

GenXMLString

Syntax

GenXMLString()

Description

The GenXMLString method creates an XML string based on the message after it's loaded from the message buffer.

Note: This method does not support nonrowset-based messages.

Parameters

None.

Returns

An XML string.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

In the following example, the first thee lines of code creates the message object and copies the data from a Component buffer into the message object. The last line creates an XML string based on that message object.

```
&MSG = CreateMessage(OPERATION.PO_INSERT);
&RS = GetLevel0();
&MSG.CopyRowset(&RS);
&XML_STRING = &MSG.GenXMLString();
```

Related Links

LoadXMLString

GetContentString

Syntax

GetContentString([*SegmentIndex*])

Description

Use the GetContentString to return a string populated with the content from the specified message segment. If you don't specify a segment, the data from the first segment is used.

Parameters

SegmentIndex	Specify the message segment that you want to access.

Returns

A string populated with the content of the specified segment if successful, null otherwise.

Related Links

CreateNextSegment
SetContentString

GetDocument

Syntax

GetDocument([*segmented_messsage*])

Description

Use these method to get a Document object associated with this message.

Note: If a fault occurs, continue to use GetContentString to read the fault message, and not GetDocument.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

segmented_messsage	Specify a Boolean value indicating whether the message is segmented.

Returns

A Document object.

Example

```
Local Message &Msg;
Local Document &Doc;

&Msg = CreateMessage(Operation.QEFLIGHTPLAN_DOC);

&Doc = &Msg.GetDocument( True);

/* populate the document */
...

&Msg.CreateNextSegment();

&Doc = Null;
&Doc = &Msg.GetDocument( True);

/* populate the document */

...
```

Related Links

GetContentString

Document Class

GetPartAliasName

Syntax

GetPartAliasName(*PartIndex*)

Description

Use the GetPartAliasName to access the alias of the specified message part.

Note: This method works only with container messages.

Parameters

PartIndex	Specify the message part that you want to access the alias.

Returns

A string containing the message part alias.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

AliasName

"Specifying Record Aliases" (PeopleTools 8.54: Integration Broker)

GetPartName

Syntax

GetPartName(*PartIndex*)

Description

Use the GetPartName method to return the message name of the message specified by *PartIndex*.

Note: This method works only with container messages.

Parameters

PartIndex	Specify the number of the message part that you want to get the name for.

Returns

A string.

Related Links

CopyPartRowset

GenXMLPartString

GetPartRowset

Syntax

GetPartRowset(*PartIndex*)

Description

Use the GetPartRowset to instantiate and populate a rowset object based on the specified message part in a container message.

Note: This method only works with rowset-based container messages.

Parameters

PartIndex	Specify the number of the message part that you want to instantiate and populate a rowset from.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

A reference to a rowset object if successful, Null otherwise.

Related Links

CopyPartRowset
GenXMLPartString

GetPartVersion

Syntax

GetPartVersion(*PartIndex*)

Description

Use the GetPartVersion method to return the version number of the message part specified by *PartIndex*.

Note: This method only works with container messages.

Parameters

PartIndex	Specify the number of the message part that you want to access the version of.

Returns

A string containing the version number.

Related Links

PartCount

GetPartXMLDoc

Syntax

GetPartXMLDoc(*PartIndex*)

Description

Use the GetPartXMLDoc to retrieve the message part data as an XmlDoc object.

Note: This method can only be used for a nonrowset-based message parts.

Parameters

PartIndex	Specify the message part that you want to access the data for as an XmlDoc object.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

An XmlDoc object populated with the message part data.

Related Links

GetXmlDoc
GetPartRowset

GetQueryString

Syntax

GetQueryString(*Parameter_Name*)

Description

Use the GetQueryString method to obtain the parameter values of a query string.

Note: This method has been deprecated and remains for backward compatibility only. Use the IBConnectorInfo collection GetQueryStringArg method instead.

Related Links

GetQueryStringArgName

Parameters

Parameter_Name	Specify the parameter name you want to obtain.

Returns

A string containing the value of the parameter.

Example

```
Local Message &request;
Local Rowset &Rowset;
Local String &emplid;

&request = %IntBroker.GetMessage();
&Rowset = &request.GetRowset();
&emplid = &request.GetQueryString("EMPLID");
```

Related Links

GetQueryStringArgName
GetQueryStringArgValue
SetQueryString

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GetRowset

Syntax

GetRowset([*version*])

Description

The GetRowset method returns a standard PeopleCode level zero rowset object for the specified message version. It creates an empty rowset for the specified message version if it doesn't already exist. If no message version is specified, the default message version is used.

When you use the GetRowset method, you are not creating a unique copy of the object. You are making only a copy of the reference. If you change the rowset, the original message is changed.

Parameters

version An optional parameter, specifying an existing message version as a string. If *version* isn't specified, the default message version is used.

Returns

A Rowset object if successful.

Example

The following gets all the SET_CNTRL_REC rows related to the row on the page, then updates the field SETID with the value from the page. GetRowset is used to create a rowset based on the message structure, that is, an unpopulated rowset. Because the rowset is unpopulated, you can use the Fill method to populate with data from the page.

```
Local Message &MSG;
Local Rowset &MSG_ROWSET;

If FieldChanged(SETID) Then
  &MSG = CreateMessage(OPERATION.SET_CNTRL_REC);
  &MSG_ROWSET = &MSG.GetRowset();
  &MSG_ROWSET.Fill("where SETCNTRLVALUE =:1 and REC_GROUP_ID =:2", SETCNTRLVALUE, R⇒
EC_GROUP_ID);

  For &I = 1 To &MSG_ROWSET.ActiveRowCount
    &MSG_ROWSET.GetRow(&I).SET_CNTRL_REC.SETID.Value = SETID;
    &MSG_ROWSET.GetRow(&I).PSCAMA.AUDIT_ACTN.Value = "C";
  End-For;

  %IntBroker.Publish(&MSG);

End-If;
```

Related Links

Clone

"CreateMessage" (PeopleTools 8.54: PeopleCode Language Reference)

Understanding Rowset Class

"Assigning Objects" (PeopleTools 8.54: PeopleCode Developer's Guide)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GetSegment

Syntax

GetSegment(*SegmentNumber*)

Description

Use the GetSegment method to return the specified segment. This method doesn't actually return anything, but populates the current message object with the specified segment's data.

Parameters

SegmentNumber	Specify the number of the segment you want to access.

Returns

None.

Related Links

CreateNextSegment
DeleteSegment
UpdateSegment
SegmentCount

GetURIDocument

Syntax

GetURIDocument()

Description

Use this method to retrieve the document template as defined on the service operation.

Parameters

None.

Returns

A Document object.

Example

```
&MSG = CreateMessage(Message.WEATHERSTATION_GET);
&DOC = &MSG.GetURIDocument();
&COM = &DOC.DocumentElement;

&COM.GetPropertyByName("state").Value = "Washington";
&COM.GetPropertyByName("city").Value = "Redmond";
&COM.GetPropertyByName("day").Value = "today";
&COM.GetPropertyByName("week").Value = "first";
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
&COM.GetPropertyByName("year").Value = "2010";
&COM.GetPropertyByName("country").Value = "USA";
&MSG.URIResourceIndex = 1;
&bRet = &MSG.IBInfo.LoadRESTHeaders();
&return_message = %IntBroker.SyncRequest(&MSG);
```

Related Links

"REST Resource Definitions" (PeopleTools 8.54: Integration Broker)

GetURIResource

Syntax

GetURIResource([*index*])

Description

Use this method to retrieve the URI for the representational state transfer (REST) resource based on the specified index.

Parameters

index	Corresponds to the row number in the URI grid of the REST Resource Definition section of the service operation definition.

Returns

A string.

Example

```
&MSG = CreateMessage(Message.WEATHERSTATION_GET);
&DOC = &MSG.GetURIDocument();

&STR = &MSG.GetURIResource(2);
```

Related Links

ConversationID

"REST Resource Definitions" (PeopleTools 8.54: Integration Broker)

GetXmlDoc

Syntax

GetXmlDoc()

Description

Use the GetXmlDoc method to retrieve the message data as an XmlDoc object.

Note: This method can only be used for a nonrowset-based message. If you use this method with a rowset-based message an error message is returned.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

None.

Returns

A XmlDoc object.

Related Links

SetXmlDoc
Understanding XmlDoc Classes

InBoundPublish

Syntax

InBoundPublish(*PubNodeName*)

Description

Use the InBoundPublish method to send an asynchronous message based on a message rowset to simulate an inbound asyncronous request from an external node.

Note: This method has been deprecated and remains for backward compatibility only. Use the IntBroker class InBoundPublish method instead.

Though you are sending a message to yourself, it goes through all the inbound message processing on *PubNodeName*.

Related Links

InBoundPublish

Parameters

PubNodeName	Specify the name of the node for which you want to test inbound message publishing.

Returns

None.

Related Links

"InboundPublishXmlDoc" (PeopleTools 8.54: PeopleCode Language Reference)
"Understanding Filtering, Transformation, and Translation" (PeopleTools 8.54: Integration Broker)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

LoadXMLPartString

Syntax

LoadXMLPartString(*PartIndex*, *XmlString*)

Description

Use the LoadXMLPartString method to populate the part of the container message specified by *PartIndex* with the XML string *XmlString*.

Note: This method works only with container messages.

Parameters

PartIndex	Specify the number of the part of the container message that you want to populate with XML data.
XmlString	Specify the XML string to be loaded into the message part.

Returns

None.

Related Links

GenXMLPartString
GenXMLString

LoadXMLString

Syntax

LoadXMLString(*XMLstring*)

Description

The LoadXMLString method loads the message object executing the method with the XML string *XMLstring*.

Parameters

XMLString	Specify the XML string to be loaded into the message object.

Returns

None.

Example

```
&MSG = CreateMessage(OPERATION.PO_HEADER);
&MSG.LoadXMLString(&XML_STRING);
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

GenXMLString

OverrideURIResource

Syntax

OverrideURIResource(*string*)

Description

Use this method on the subscribing node (the consumer) to override the URI template portion of the generated URL for a REST-based transaction.

Parameters

string	Specifies the full URL to the REST-based resource.

Returns

None.

Example

```
&MSG = CreateMessage(Operation.QE_WEATHERSTATION_CONSUME_GET);
&MSG.OverrideURIResource("http://10.111.141.248/PSIGW/RESTListeningConnector/AKTT/W⇒
eatherStation.v1/weather/Washington");
```

Publish

Syntax

Publish([*NodeName*] [, *Deferred_Mode*])

Description

The Publish method publishes a message to the application message queue for the default message version.

Note: This method has been deprecated and remains for backward compatibility only. Use the IntBroker class Publish method instead.

This method does not publish the message if the IsActive property is False.

This method publishes a message asynchronously, that is, a reply message is not automatically generated. To publish a message synchronously, use the SyncRequest method.

Note: This method supports nonrowset-based messages only if the data is populated using the SetXmlDoc method.
If the Publish method is called and the message isn't populated (either using SetXmlDoc or one of the rowset methods,) an empty message is published.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The Publish method can be called from any PeopleCode event, but is generally called from an Application Engine PeopleCode step or from a component.

When publishing from a component, you should publish messages only from the SavePostChange event, either from record field or component PeopleCode. This way, if there's an error in your publish code, the data isn't committed to the database. Also, since SavePostChange is the last Save event fired, you avoid locking the database while the other save processing is happening.

However, until the message is published, the tables involved with the component are locked and are not saved. To avoid problems with this, specify the *Deferred_Mode* property as true, so the message is published after the table data has been committed to the database.

Generally, if the message is successfully published, the PubID, and PubNodeName properties are set to the publication ID and publishing system node name, respectively. The only exception is when the Publish is performed as part of your notification PeopleCode. The notification process is always executed in deferred mode, due to performance considerations, and so the PubID is not populated.

Note: If you're publishing a message from within an Application Engine program, the message won't actually be published until the calling program performs a Commit.

Related Links

Publish

Parameters

NodeName Specify the node to which the message should be published.

Deferred_Mode Specify whether the message should be published immediately or at the end of the transaction. This parameter takes a Boolean value: False, publish the message immediately, or True, defer the publication. The default value is False.

Returns

None.

Example

The following copies all the data from a page into a message and publishes it.

```
Local Message &MSG;
Local Rowset &ROWSET;

&MSG = CreateMessage(OPERATION.MESSAGE_PO):
&ROWSET = GetLevel0();
&MSG.CopyRowset(&ROWSET);
&MSG.Publish;
```

The following is an example of putting the Incremental Publish PeopleCode on a Record at Level 1 (or 2, 3). If you just do the normal publishing PeopleCode, you get as many messages as there are records at that level (because the code fires for each record).

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

To make sure the code fires only once, use the following code.

```
/*NAMES.EMPLID.WORKFLOW */
Local Message &MSG;
Local Rowset &RS;

&LEVEL = CurrentLevelNumber();
&CURRENT_ROW = CurrentRowNumber(&LEVEL);
&TOT_ROW = ActiveRowCount(EMPLID);
/* Only Publish the message once for all records on */
/* this level */
If &CURRENT_ROW = &TOT_ROW Then
  &MSG = CreateMessage(OPERATION.NAMES);
  &RS = GetRowset();
  &MSG.CopyRowsetDelta(&RS);
  &MSG.Publish();
End-If;
```

Related Links

IsActive

InBoundPublish

"Adding Message Definitions" (PeopleTools 8.54: Integration Broker)

"InboundPublishXmlDoc" (PeopleTools 8.54: PeopleCode Language Reference)

SegmentRestart

Syntax

SegmentRestart(*TransactionID*, *Segment_index*, *segmentByDB*)

Description

Use the SegmentRestart method to restart a message segment. This is used only in a Application Engine program, and only if check point logic is used.

Parameters

Transaction_ID	Specify the transaction ID of the message you want to restart.
Segment_Index	Specify the number of the segment that you want to restart.
SegmentByDB	Specify the segments by database.

Returns

None.

Related Links

DeleteOrphanedSegments

"Working With Message Segments" (PeopleTools 8.54: Integration Broker)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SetContentString

Syntax

SetContentString(*string*)

Description

Use this method to set the content for the message segment for a non-rowset-based message only.

Note: An error will occur if SetContentString is used with other message types, such as rowset-based messages, document-based messages, and so on.

Parameters

string	Specifies the content of the message segment.

Returns

A Boolean value: True if the message segment was updated, False otherwise.

Example

```
Local Message &MSG;
Local Document &DOC;
Local Compound &COM, &COM1;

&MSG = CreateMessage(Message.QE_WEATHERSTATION_POST);

&DOC = &MSG.GetURIDocument();

&COM = &DOC.DocumentElement;

&COM.GetPropertyByName("state").Value = "Washington";
&COM.GetPropertyByName("city").Value = "Redmond";
&COM.GetPropertyByName("day").Value = "today";
&COM.GetPropertyByName("week").Value = "first";
&COM.GetPropertyByName("year").Value = "2010";
&COM.GetPropertyByName("country").Value = "USA";

&MSG.URIResourceIndex = QE_FLIGHTDATA.QE_ACNUMBER;

&DOC = CreateDocument("Weather", "WeatherData", "v1");
&COM1 = &DOC.DocumentElement;
&COM1.GetPropertyByName("city").Value = "Troutlake";
&STR1 = %IntBroker.GetURL("WEATHERSTATION_DATA", 2, &DOC);

&strHTML = GetHTMLText(HTML.WEATHER_CITIES, &STR1);
&bRet = &MSG.SetContentString(&strHTML);
```

Related Links

GetContentString

SetEditTable

Syntax

SetEditTable(*%PromptField*, **RECORD**.*recordname*)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

The SetEditTable method works with the ExecuteEdits method. It is used to set the value of a field on a record that has its prompt table defined as *%PromptField* value. *%PromptField* values are used to dynamically change the prompt record for a field.

There are several steps to setting up a field so that you can dynamically change its prompt table.

To set up a field with a dynamic prompt table:

1. Define a field in the DERIVED record called *fieldname*.
2. In the record definition for the field that you want to have a dynamic prompt table, define the prompt table for the field as *%PromptField*, where *PromptField* is the name of the field that you created in the DERIVED record.
3. Use SetEditTable to dynamically set the prompt table.

%PromptField is the name of the field on the DERIVED work record. **RECORD**.*recordname* is the name of the record to be used as the prompt table.

```
&MSG.SetEditTable("%EDITTABLE1", Record.DEPARTMENT);
&MSG.SetEditTable("%EDITTABLE2", Record.JOB_ID);
&MSG.SetEditTable("%EDITTABLE3", Record.EMPL_DATA);
&MSG.ExecuteEdits();
```

Every field on a record that has the prompt table field %EDITTABLE1 will have the same prompt table, such as, DEPARTMENT.

Parameters

%PromptField	Specifies the name of the field in the DERIVED record that has been defined as the prompt table for a field in a record definition.
RECORD.*recordname*	Specifies the name of the record definition that contains the correct standard system edits to be performed for that field in the message.

Returns

None.

Related Links

ExecuteEdits
EditError
MessageNumber
MessageSetNumber
IsEditError
SetEditTable
"Creating New Record Definitions" (PeopleTools 8.54: Application Designer Developer's Guide)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SetQueryString

Syntax

SetQueryString(*Parameter_Name, Value***)**

Description

Use the SetQueryString method to add a parameter value to the query string.

Note: This method has been deprecated and remains for backward compatibility only. Use the IBConnectorInfo class AddQueryStringArg method instead.

Related Links

AddQueryStringArg

Parameters

Parameter_Name Specify the name of the parameter that you want to add to the query string, as a string.

Value Specify the value of the parameter you are adding to the query string.

Returns

None.

Example

```
Local Message &request;
&request = CreateMessage(OPERATION.QE_SALES_ORDER);
. . .

. . .

&request.SetQueryString("BUYER", "12345");
```

Related Links

AddQueryStringArg
GetQueryString

SetRESTCache

Syntax

SetRESTCache(*&futureDT***)**

Description

Use the SetRESTCache method to set server-side caching for provider REST GET service operations the OnRequest PeopleCode event. When you set server-side caching, the system caches the entire

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

transactional data for the *specific URI resource.* Subsequent requests from a client with an identical resource will result in the data being pulled from the cache. The cache expires on the date and time specified by the *&futureDT* parameter.

You can delete the cache at any time by calling the DeleteRESTCache method.

Parameters

&futureDT Specifies a future date and time as a DateTime variable.

Returns

None.

Example

```
Local Message &MSG;
Local datetime &dt;
Local string &op, &ver;

&MSG.SetRESTCache(&dt);

&b_ret = %IntBroker.DeleteRESTCache(&op, &ver);
```

Related Links

DeleteRESTCache

SetStatus

Syntax

SetStatus(*Status*)

Description

Use the SetStatus method to set the status of a publication or subscription contract, much the same way you do in the message monitor.

Note: This method has been deprecated and remains for backward compatibility only. Use the IntBroker class SetStatus method instead.

You may want to use this method after an end-user has finished fixing any errors in the message data.

You can set the status of a contract to one of the following statuses:

- Cancel
- Done
- Error
- New

The method is available only when the message instance has one of the following statuses:

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- Cancel
- Done
- Error
- New

Related Links

SetStatus

Parameters

Status Specify the status that you want to set the message to. Value are:

- %Message_Error
- %Message_New
- %Message_Done
- %Message_Started
- %Message_Working
- %Message_Retry
- %Message_Timeout
- %Message_Edited
- %Message_Canceled

Returns

None.

Related Links

"Adding Message Definitions" (PeopleTools 8.54: Integration Broker)

SetXmlDoc

Syntax

SetXmlDoc(*&XmlDoc*)

Description

Use the SetXmlDoc method to load a nonrowset-based message with data from an XmlDoc object.

Note: This method can only be used for nonrowset-based message. If you use this method with a rowset-based message an error message is returned.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Considerations Using SetXmlDoc

In order to wrap non-XML data in cdata wraps as part of a message that would be automatically removed when posted to the gateway, the following cdata wraps are supported:

- `<?xml version="1.0"?> <data PsNonXml="Yes"><![CDATA..`
- `<?xml version="1.0"?> <data psnonxml="Yes"><![CDATA..`
- `<?xml version="1.0"?><add_some_root_tag> <data PsNonXml="Yes"><![CDATA...`
- `<?xml version="1.0"?><add_some_root_tag> <data psnonxml="Yes"><![CDATA...`

Parameters

&XmlDoc	Specify an already instantiated, populated XmlDoc object.

Returns

None.

Related Links

GetXmlDoc
Understanding XmlDoc Classes

SyncRequest

Syntax

`SyncRequest``([`*`NodeName`*`])`

Description

Use the SyncRequest method to send a synchronous message for the default message version.

Note: This method has been deprecated and remains for backward compatibility only. Use the IntBroker class SyncRequest method instead.

Use the IsActive property to determine if a message is active or not before using this method.

This method sends a single message synchronously, that is a reply message is returned as a result of this method.

If you want to publish a message asynchronously, use the Publish method.

If you want to publish more than one message at a time synchronously, use the IntBroker SyncRequest method.

Note: This method supports nonrowset-based messages only if the SetXmlDoc method is used to populate the message prior to using the SyncRequest method.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The SyncRequest method can be called from any PeopleCode event, but is generally called from an Application Engine PeopleCode step or from a component.

When sending a synchronous request from a component, you should send messages only from the SavePostChange event, either from record field or component PeopleCode. This way, if there's an error in your SyncRequest code, the data isn't committed to the database. Also, since SavePostChange is the last Save event fired, you avoid locking the database while the other save processing is happening.

If the message is successfully sent, a response message is returned. In addition, the GUID property is updated with a unique identifier.

Related Links

SyncRequest

Parameters

NodeName	Specify the name of the node that you want to send this message to.

Returns

A response message.

Example

```
Local Message &request, &response;
Local Rowset &sales_order;

&sales_order = GetLevel0();
&request = CreateMessage(OPERATION.QE_SALES_ORDER);
&request.CopyRowsetDelta(&sales_order);
&response = &request.SyncRequest();
If (&response.ResponseStatus = 0) Then
   /* do processing */
End-If;
```

Related Links

Publish

SyncRequest

Update

Syntax

Update([*versionlist*])

where *versionlist* is an arbitrary list of message versions in the following format:

version1 [, *version2*] . . .

Description

The Update method updates a message in the message queue with the specified message versions.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Note: This method has been deprecated and remains for backward compatibility only. Use the IntBroker class Update method instead.

If *versionlist* isn't specified, the default message version is used. This method is commonly used in the OnRouteSend and OnRouteReceive PeopleCode events.

Note: This method does not support nonrowset-based messages. The Update method can't be called from notification PeopleCode.

Related Links

Update

Parameters

versionlist	Specify an optional comma-separated list of message versions. If *versionlist* isn't specified, the default message version is used.

Returns

None.

Related Links

GetRowset

"Adding Message Definitions" (PeopleTools 8.54: Integration Broker)

UpdateSegment

Syntax

```
UpdateSegment()
```

Description

Use the UpdateSegment method to update the current segment with data from the message. This method is used only when creating a message for publication, not after a message has been published.

Note: You should use DeleteSegment and UpdateSegment only when writing to memory, or when SegmentsByDatabase is set to False. These methods do not work when writing to the database, or when SegmentsByDatabase is set to True.

Parameters

None.

Returns

None.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

CreateNextSegment
DeleteSegment
CurrentSegment
SegmentCount

Message Class Properties

In this section, we discuss the Message class properties. The properties are discussed in alphabetical order.

ActionName

Description

This property returns the name of the action associated with the message, as a string.

This property is read-only.

AliasName

Description

This property returns the name of the alias associated with the message part executing the property.

This property is read-only.

Related Links

GetPartAliasName
"Specifying Record Aliases" (PeopleTools 8.54: Integration Broker)

ChannelName

Description

This property references the name of the channel associated with the message definition.

Note: This property has been deprecated and remains for backward compatibility only. Use the Message class QueueName property instead.

See QueueName.

This property is set when the message is created. The message instance keys are a subset of the publication and subscription contract keys. This property is one of the message instance keys: the others are PubID and PubNodeName for asynchronous messages, GUID and PubNodeName for synchronous messages.

This property is valid for both synchronous and asynchronous messages.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-only.

Example

```
&CHANNEL = &MSG.ChannelName
```

Related Links

"Adding Message Definitions" (PeopleTools 8.54: Integration Broker)

Cookies

Description

This property returns or sets the cookies associated with a message.

Note: This property has been deprecated and remains for backward compatibility only. Use the IBInfo class Cookies property instead.

See Cookies.

You can accept a synchronous response message containing cookies, save those cookies in a global variable, and later return them to the target node in an outbound synchronous or asynchronous request message.

You can access this property only in an inbound synchronous response message or an outbound request message.

This property is read-write.

Example

The following is an example of receiving cookies:

```
Local Message &SalesRequest, &SalesResponse;
Local Rowset &SALES_ORDER;
Global string &SalesCookies;

&SALES_ORDER = GetLevel0();
&SalesRequest = CreateMessage(OPERATION.SALES_ORDER_SYNC);
&SalesRequest.CopyRowsetDelta(&SALES_ORDER);

/* send the synchronous request; the return value is */
/* the response message object */
&SalesResponse = &SalesRequest.SyncRequest();

/* Retrieve cookies from the response message */
&SalesCookies = &SalesResponse.Cookies;
```

The following is an example of returning cookies:

```
Local Message &SalesRequest, &SalesResponse;
Local Rowset &SALES_ORDER;
Global string &SalesCookies;

&SALES_ORDER = GetLevel0();
&SalesRequest = CreateMessage(OPERATION.SALES_ORDER_SYNC);
&SalesRequest.CopyRowsetDelta(&SALES_ORDER);

/* Insert the cookies in the request message */
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
&SalesRequest.Cookies = &SalesCookies;

/* Send the asynchronous request */
&SalesRequest.Publish();
```

CurrentSegment

Description

This property returns a number, indicating which segment is the current segment.

This property is read-only.

DefaultMessageVersion

Description

This property returns the default version of the message as a string.

Note: This property has been deprecated and remains for backward compatibility only. Use the Message class OperationVersion property instead.

See OperationVersion.

This is the message version from the pub/sub contract, not the default message version of the message defined in the current system.

This property is valid for both synchronous and asynchronous messages.

This property is read-only.

Example

```
Local Message &MSG;
Local String &VER;

&MSG = %IntBroker.GetMessage();
&VER = &MSG.DefaultMessageVersion;
```

DoNotPubToNodeName

Description

Use this property to set the node name of a node that you do not want to publish this message to. For example, a single node may publish and subscribe to the same message. You can use this property to prevent the system from subscribing to the same message it publishes. This can help prevent circular processing where the original publisher eventually receives the same message.

This property is only valid for asynchronous messages.

This property is read-write.

Example

```
&MSG.DoNotPubToNodeName = &MSG.PubNodeName;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
&MSG.Publish();
```

GUID

Description

This property returns a string representing a global unique identifier generated when the message was sent.

Note: This property has been deprecated and remains for backward compatibility only. Use the Message class TransactionId property instead.

See OperationVersion.

This property returns the unique identifier used with the message.

This property is valid only for synchronous messages.

This property is read-only.

Example

```
Local Message &request;
Local String &guid;

&request = %IntBroker.GetMessage();

&guid = &request.GUID;
```

HTTPMethod

Description

Use this property to return an integer constant representing the HTTP request method that was specified by the subscribing node (the consumer) in REST-based service operations. The request method determines the proper response message to send.

Value	*Description*
%IntBroker_HTTP_GET	HTTP GET method – Requests a representation of a resource.
%IntBroker_HTTP_POST	HTTP POST method – Submits data to be processed to the specified resource. This might result in the creation of a new resource or updates to an existing resource or both.
%IntBroker_HTTP_DELETE	HTTP DELETE method – Deletes the specified resource.
%IntBroker_HTTP_PUT	HTTP PUT method – Uploads a representation of the specified resource. This might result in the creation of a new resource or updates to an existing resource or both.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Value	*Description*
%IntBroker_HTTP_HEAD	HTTP HEAD method – Requests a representation of a resource without without the response body that would be returned in a GET request.

This property is read-only.

Example

```
If &MSG.HTTPMethod = %IntBroker_HTTP_POST Then

   /* populate the POST response data */

End-If;

If &MSG.HTTPMethod = %IntBroker_HTTP_GET Then

   /* populate the GET response data */

End-If;
```

HTTPResponseCode

Description

Use this property to return the HTTP response code for the transaction as an integer.

This property is read-only.

Example

```
&return_msg = %IntBroker.SyncRequest(&MSG);
If &return_msg.ResponseStatus = %IB_Status_Success Then
   &nRET = &return_msg.HTTPResponseCode;
End-If;
```

IBException

Description

Use the IBException property to return a reference to an exception object. The object is populated with information about the integration broker error.

This property is read-only.

Related Links

Understanding Exception Class

IBInfo

Description

Use this property to return a reference to an IBInfo object.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-only.

InitializeConversationId

Description

Use this property to set or return a Boolean value indicating whether this is the first of a set of correlated messages. On the first message to be published, set the InitializeConversationId property to True. After the message is published, retrieve the transaction ID from the message. This transaction ID should be used to set the conversation ID (that is, the correlation ID) for all subsequent messages to be published.

This property is read-write.

Related Links

FirstCorrelation

TransactionId

ConversationID

"Using the OnPreNotify and OnPostNotify PeopleCode Events" (PeopleTools 8.54: Integration Broker Administration)

IsActive

Description

Indicates whether the message definition has been set to inactive.

Note: This property has been deprecated and remains for backward compatibility only. Use the Message class IsOperationActive property instead.

See IsOperationActive.

This property is True if the message definition is active, False if it's been inactivated. If you have a lot of PeopleCode associated with publishing a message, you might use this property to check if the message is active before you publish it.

This property is valid for both asynchronous and synchronous messages.

This property is read-only.

Example

```
&MSG = CreateMessage(OPERATION.MY_MESSAGE)
If &MSG.IsActive Then
  /* do PeopleCode processing */
  &MSG.Publish();
Else
  /* do other processing */
End-if;
```

Related Links

"Adding Message Definitions" (PeopleTools 8.54: Integration Broker)

"IsMessageActive" (PeopleTools 8.54: PeopleCode Language Reference)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

IsBulkLoadTruncation

Description

Use this property to return a Boolean value indicating whether the table truncation option has been selected on the bulk loader handler.

This property is read-only.

Example

```
If &MSG.IsBulkLoadTruncation = False Then

   /* then any truncation of tables would have to be performed here */

End-If;
```

Related Links

"Implementing Handlers Using Bulk Load Processing" (PeopleTools 8.54: Integration Broker)

IsDelta

Description

This property indicates if any fields in a message populated from page data have been changed since they were first loaded into the component buffer.

This is generally used in the following scenario:

You want to publish a message only if the end-user has changed a value on a page. The problem is that if the end-user makes a change to a field in the level three rowset, the IsChanged property for the top level row remains False. If the rowset is large, and you don't want to iterate through it to find a single IsChanged, you can use this property to quickly determine if something has changed at a lower level and the message should be published.

Note: This property should be used only when the message and the component do not have the same structure (that is, the same records at the same levels). If the message and the component have the same structure use the CopyRowsetDelta method instead.

This property takes a Boolean value: True if there are changed fields in the message, False otherwise.

This property is valid for both asynchronous and synchronous messages.

This property is read-only.

Example

```
&Msg = CreateMessage(OPERATION.MY_MESSAGE);
&Msg_Rowset = &Msg.GetRowset(); /* get first level in Msg RS */
&Msg_Detail = &Msg_Rowset(1).GetRowset(); /* get detail in Msg */
&Page_Rowset = GetRowset(); /* get page */
For &I = &Page_Rowset.Rowcount
  &Page_Detail = &Page_Rowset.GetRow(&I).GetRowset();
  &Msg_Detail.CopyRowset(&Page_Detail);
End-For;
/* Find if any data changed and should publish message */
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
If &Msg.IsDelta Then
   &Msg.Publish();
Else
   /* don't publish message and do other processing */
End-If;
```

Related Links

CopyRowsetDelta

IsEditError

Description

This property is True if an error has been found on any field in any record of the current message after executing the ExecuteEdits method on either a message object or a record object. This property can be used with the Field Class properties MessageSetNumber and MessageNumber to find the error message set number and error message number.

You can use this property in notification PeopleCode with the Exit function with a value of 1. This automatically rolls back any changes that were made to the database, saves the message errors to the message queue, and marks the message status as ERROR.

This property is valid for both asynchronous and synchronous messages.

This property is read-only.

Example

```
&MSG = %IntBroker.GetMessage();
&Rowset = &MSG.GetRowset();
&MSG.ExecuteEdits();
If &MSG.IsEditError Then
  Exit(1);
End-If;
```

Related Links

ExecuteEdits

MessageNumber

MessageSetNumber

"Exit" (PeopleTools 8.54: PeopleCode Language Reference)

"Processing Inbound Errors" (PeopleTools 8.54: Integration Broker)

IsLocal

Description

This property is True if the message object that was just instantiated was published locally. This property takes a Boolean value.

This property is valid for both asynchronous and synchronous messages.

This property is read-only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

```
&MSG = %IntBroker.GetMessage();
If &MSG.IsLocal Then /*  LOCAL NODE */
  /* do processing specific to local node */
Else
  /* do processing specific to remote nodes */
End-If;
```

IsOperationActive

Description

Use the IsOperationActive property to determine if an operation is active or not.

This property returns a Boolean value: true if the operation is still active, false otherwise.

This property is read-only.

Related Links

"Adding Message Definitions" (PeopleTools 8.54: Integration Broker)

IsParts

Description

Use the IsParts property to determine if the message is a container message, that is, composed of parts.

This property only determines if a message is a container message. If you'd like to know if the message is a rowset-based message with parts, use the IsPartsStructured property instead.

This property returns a Boolean value: true if the message executing the property is a container message, false otherwise.

This property is read-only.

Related Links

IsPartsStructured

IsPartsStructured

Description

Use the IsPartsStructured property to determine if the message is a container message, that is, composed of parts, as well as a rowset-based message.

This property determines if a message is a container message as well as rowset-based. If you only want to know if the message is a container message, use the IsParts property instead.

This property returns a Boolean value: true if the message executing the property is a container message that is rowset-based, false otherwise.

This property is read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

IsParts

IsRequest

Description

Use the IsRequest property to determine whether a message is a request message (as opposed to a response message.)

This property returns a Boolean value: true if the message object executing the property is a request message, false otherwise.

This property is read-only.

IsSourceNodeExternal

Description

Use the IsSourceNodeExternal property to determine whether the message came from an internal system or a third-party system.

This property returns a Boolean value: true if the message originated from a third-party system, false otherwise.

This property is read-only.

IsStructure

Description

This property indicates whether the message is rowset-based, that is, based on a rowset, or nonrowset-based that is, based on an XmlDoc. This property returns a Boolean value, true if the message is rowset-based, false otherwise.

This property is read-only.

MessageDetail

Description

This property specifies the message detail, as a string. The message detail can be used to further identify a message.

Note: This property has been deprecated. It is no longer supported.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Name

Description

This property returns the name of the message as a string.

This property is valid with both asynchronous and synchronous messages.

This property is read-only.

NRId

Description

This property returns the non-repudiation ID as a string. This property is populated with a unique string when the message is published.

This property is only valid with messages that use non-repudiation.

This property is read-only.

Related Links

"Implementing Nonrepudiation" (PeopleTools 8.54: Integration Broker Administration)

OperationName

Description

Use the OperationName property to return the name of the operation associated with the message object executing the property, as a string.

This property is read-only.

OperationVersion

Description

Use the OperationVersion property to determine version for the operation associated with the message object executing the property, as a string.

This property is read-only.

ParentTransactionId

Description

Use the ParentTransactionId property to return the parent transaction ID, that is, the ID that is generated with the original request message from a third-party system.

This property is read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

TransactionId

PartCount

Syntax

Use the PartCount property to determine the number of parts in a container message. This property is only valid with container messages. You will receive an error if you try to use it on a message that isn't a container message.

This property is read-only.

PubID

Description

This property refers to the publication identifier, which is a number.

Note: This property has been deprecated and remains for backward compatibility only. Use the Message class QueueSeqId property instead.

See QueueSeqId.

It’s generated for asynchronous messages when the message is published, and is sequential, based on the number of messages published for that channel. The message instance keys are a subset of the publication and subscription contract keys. This property is one of the message instance keys: the others are ChannelName and PubNodeName.

Note: The PubID property is not populated when the message is published from a notification.

This property is valid only with asynchronous messages.

This property is read-only.

Example

```
&MSG.Publish();
&PUBID = &MSG.PubID;
```

PubNodeName

Description

This property refers to a string that contains the name of the publishing node. It is generated by the system when the message is published. The message instance keys are a subset of the publication and subscription contract keys.

This property is valid for both asynchronous and synchronous messages.

For a synchronous message, this property returns the name of the requesting node.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-only.

Example

```
&MSG = %IntBroker.GetMessage();
&PUBNODE = &MSG.PubNodeName;
```

QueueName

Description

Use the QueueName property to return the name of the queue associated with the message.

This property is read-only.

Related Links

"Understanding Service Operation Queues" (PeopleTools 8.54: Integration Broker)

QueueSeqId

Description

Use the QueueSeqId property to return the sequence number of the message in the message queue.

This property is read-only.

ResponseStatus

Description

This property is valid only for the returned response message from a synchronous request message.

This property indicates whether a response was successful or not.

Note: This is not the same as SetStatus, which is used only with the message monitor.

This property returns a numeric value: 0, the response was successful, any other number indicates an error.

This property is read-only.

SegmentContentTransfer

Description

Use this property to set or return a string constant indicating whether the message segment is binary or text data:

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Value	*Description*
%ContentTransfer_Binary	Transfer this segment as binary data. **Note:** Any binary data must be encoded as text, which increases its size by up to 33%.
%ContentTransfer_Default	Transfer this segment as text data.

The HTTP target connector has a property called MTOM. When this property is set to Y, the transaction uses the Message Transmission Optimization Mechanism (MTOM) protocol for message transmission, which is more efficient for binary attachments.

This property is read-write.

Example

```
Local Message &MSG;

&MSG = CreateMessage(Message.FLIGHTDATA);

&MSG.SetXmlDoc(&xmldoc);

&MSG.CreateNextSegment();
&bRet = &MSG.SetContentString("your encoded image data here");
&MSG.SegmentContentType = "image/gif";
&MSG.SegmentContentTransfer = %ContentTransfer_Binary;

&MSG.CreateNextSegment();
&bRet = &MSG.SetContentString("your encoded video here");
&MSG.SegmentContentType = "video/mp4";
&MSG.SegmentContentTransfer = %ContentTransfer_Binary;

%IntBroker.Publish(&MSG);
```

Related Links

SetContentString

SegmentContentType

"Sending and Receiving Binary Data" (PeopleTools 8.54: Integration Broker)

SegmentContentType

Description

Use this property to set or return a string representing the content (or MIME) type for the message segment—for example, application/pdf. This property is read-write.

Example

```
&MSG.SegmentContentType = "video/mp4";
```

Related Links

SetContentString

SegmentContentTransfer

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

"Sending and Receiving Binary Data" (PeopleTools 8.54: Integration Broker)

SegmentCount

Description

This property returns the total number of segments for the message.

This property is read-only.

SegmentsByDatabase

Description

Use this property to specify whether segments are stored in memory while being processed.

If you specify SegmentsByDatabase as false, you can only have the number of segments as specified in PSADMIN (Message Segment From DB). If you specify this property as true, you can have as many segments as you need.

The SegmentsByDatabase property also specifies whether the segments are kept in memory or written to the database when they are received. If you specify true, the segments are automatically written to the database. If you specify false, the segments are held in memory. If you specify true, then cancel out of the program processing the segments, the changes are not committed to the database.

This property is automatically set to true for message segments being processed using a Application Engine program.

This property is read-write.

Related Links

Message Segments

SegmentsUnOrder

Size

Description

The Size property is the approximate size of the uncompressed XML data generated when the message is published. The availability and meaning of the Size property depends on the message type as follows:

- For rowset-based message parts, the Size property is available and based on the estimated XML size.
- For non-rowset-based messages, the Size property is available and based on the XML data size.
- For container-based messages, the Size property is available on received messages only—that is for OnRequest or OnNotify PoepleCode events.
- For container-based message parts, the Size property is available and based on the estimated XML size.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- For document-based messages, the Size property is available and based on the XML data size.

The size is approximate for the following reasons:

- The maximum size of fields is used except for the case of long text and image fields.
- The active row count is used, without regard to whether the rows have been changed. In a CopyRowsetDelta, rows that are not changed, are not published.
- It doesn't include the size of the XML tags.

This property can be used with the system property %MaxMessageSize in a batch Application Engine program to prevent the application from publishing a message that is too large.

This property is valid for both asynchronous and synchronous messages.

This property is read-only.

Example

```
If &MSG.Size > %MaxMessageSize Then
  &MSG.Publish();
Else
  /*Move more data into the message object */
End-If;
```

Related Links

"%MaxMessageSize" (PeopleTools 8.54: PeopleCode Language Reference)

"Understanding Sending and Receiving Messages" (PeopleTools 8.54: Integration Broker)

SubName

Description

This property refers to a string that contains the name of the notification process currently processing the message.

Note: This property has been deprecated and remains for backward compatibility only. Use the Message class ActionName property instead.

See ActionName.

It is available only when GetMessage is used in a notification PeopleCode program.

This property is only valid for asynchronous messages.

This property is read-only.

Example

```
&MSG = %IntBroker.GetMessage();
&SUBNAME = &MSG.SubName
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SubQueueName

Description

Use the SubQueueName to return or specify the name of the sub-queue associated with the message, as a string.

This property is read-write.

Related Links

"Understanding Service Operation Queues" (PeopleTools 8.54: Integration Broker)

SubscriptionProcessId

Description

This property returns a string containing the subscription process identifier. This is a unique sequential number.

Note: This property has been deprecated and remains for backward compatibility only. Use the Message class TransactionId property instead.

See TransactionId.

This property is populated only if the “Generate Subscription Process Instance” option is turned on in the Subscription Process definition.

The subscription process identifier corresponds to the subscription process instance, not the message instance. If there are multiple subscription processes for the same message each subscription process will have a different, unique ID.

If the subscription process terminated abnormally, its process instance is lost, and a new one is generated on the next retry (that is, there will be a gap in the sequence.)

This property is valid only for asynchronous messages.

This property is read-only.

Considerations for Using SubscriptionProcessId

Consider the following when using SubscriptionProcessId:

- Using the Run PeopleCode option from Message Subscription does not generate the number. It is generated only if the Application Server is running the PeopleCode.
- If for some reason you have to rerun the subscription, a new number is assigned.
- Because generating the number is optional, your program must contain code to support the option being turned off. Here is a code example from ITEM_SYNC:

```
If All(&MSG.SubscriptionProcessId) Then
  &EIP_CTL_ID = Generate_EIP_CTL_ID(4, &MSG.SubscriptionProcessId);
Else
  &EIP_CTL_ID = Generate_EIP_CTL_ID(1, "Random");
End-If;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- If the flag is off, this property is blank. In this case, you may want to adopt a standard for generating a random number, as shown in the previous example.

Related Links

"Understanding Sending and Receiving Messages" (PeopleTools 8.54: Integration Broker)

TransactionId

Description

Use the TransactionId property to return the transaction ID for an already published message, as a string. This is a unique transaction identifier for the message.

This property is read-only.

URIResourceIndex

Description

Use this property to set or return the index for the URI as an integer. This index corresponds to the row number in the URI grid of the REST Resource Definition section of the service operation definition.

This property is read-write.

Example

```
&MSG = CreateMessage(Message.WEATHERSTATION_GET);
&DOC = &MSG.GetURIDocument();
&COM = &DOC.DocumentElement;

&COM.GetPropertyByName("state").Value = "Washington";
&COM.GetPropertyByName("city").Value = "Redmond";
&COM.GetPropertyByName("day").Value = "today";
&COM.GetPropertyByName("week").Value = "first";
&COM.GetPropertyByName("year").Value = "2010";
&COM.GetPropertyByName("country").Value = "USA";
&MSG.URIResourceIndex = 1;
```

Related Links

SegmentContentType

"REST Resource Definitions" (PeopleTools 8.54: Integration Broker)

Version

Description

Use the Version property to determine the version of the message executing the property, as a string.

This property is read-only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

IntBroker Class

An IntBroker object is returned from the system variable %IntBroker.

IntBroker Class Methods

In the following section, we discuss the IntBroker class methods. The methods are described in alphabetical order.

Cancel

Syntax

```
Cancel(TransactionId, QueueName, DataType, SegmentIndex | TransactionIdArray,
QueueNameArray, DataTypeArray, SegmentIndexArray)
```

Description

Use the Cancel method to programmatically cancel either a message, or a list of messages, from the message queue, much the same as you can do in the message monitor.

This method is only available when the message has one of the following statuses:

- Edited
- Error
- New
- Retry
- Timeout

If you are specifying an array of messages to be canceled, and any message in the array fails for any reason (for example, you specify a message that doesn't have the correct status) no messages are canceled and the method return value is false.

Parameters

TransactionId* | *TransactionIdArray	Specify either a single transaction ID as a string, or specify an array of string containing the transaction Ids of the messages you want to cancel.
QueueName* | *QueueNameArray	Specify either a single queue name as a string, or specify an array of string containing the queue names that contain the messages you want to cancel.
DataType* | *DataTypeArray	Specify either a single data type, or an array of string containing the data types. See below for valid data types.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SegmentIndex | SegmentIndexArray Specify either a specific segment, or an array of integer containing the segment numbers you want to cancel.

For the *DataType* or *DataTypeArray* parameters, the valid data types are:

Constant Value	***Description***
%IntBroker_BRK	Cancel the message for the web services gateway.
%IntBroker_PUB	Cancel the message for the publication contract.
%IntBroker_SUB	Cancel the message for the subscription contract.

Returns

A Boolean value: true if the message or messages are canceled successfully, false otherwise.

Related Links

Resubmit

ConnectorRequest

Syntax

ConnectorRequest(*&Message*[, *process_exceptions*])

Description

Use the ConnectorRequest method to return a response message from the connector based on the message passed in.

You would only use this method after you had set the connector information.

Parameters

&Message Specify an already instantiated message object to return a response message from the connector.

process_exceptions Specifies a Boolean value indicating whether the PeopleCode program will process exceptions.

Important! When this parameter is set to True, your program must read the response status property of the response message to determine if the call was successful. If there is an exception, then interrogate the IBException object within the Message object to get the details of the exception.

Returns

A Message object.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

```
   Local string &nonXmlData = "<?xml version=""1.0""?><data psnonxml=""yes""><![CDA⇒
TA[" | &encoded | "]]></data>";
   &soapMsg = CreateXmlDoc(&nonXmlData);

   &reqMsg.SetXmlDoc(&soapMsg);

   Local Message &respMsg;

   %This.SetConnectorProperties(&reqMsg, &url);

   &respMsg = %IntBroker.ConnectorRequest(&reqMsg);

   If &respMsg = Null Then /* Throw exception */
   %This.HandleNullSoapResponse(&soapMsg, &url);
   End-If;
```

This second example demonstrates how to evaluate the response message status when *process_exceptions* is True:

```
Local Message &MSG, &resp_MSG;

&resp_MSG = %IntBroker.ConnectorRequest(&MSG, True);

If &resp_MSG.ResponseStatus = %IB_Status_Success Then
   /* Perform processing of a successful response message */

Else
   /* Read the IBException object for exception specifics */
   &error = &resp_MSG.IBException.ToString();

End-If;
```

Related Links

ConnectorRequestUrl

IBException

ConnectorRequestUrl

Syntax

ConnectorRequestUrl(*URL*)

Description

Use the ConnectorRequestUrl method to return the URL for a connector.

You must have already set the connector parameters before executing this command.

Parameters

URL	Specify an absolute URL as a string.

Returns

A string.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

```
/**
 * Get XML Doc from URL
 *
 * @param String - Location
 * @return XmlDoc - retrieved XmlDoc
**/

method getXmlDocumentFromURL
   /+ &location as String +/
   /+ Returns XmlDoc +/
   Local XmlDoc &xmldoc;
   Local string &xmlstr;

   If Substring(LTrim(RTrim(Upper(&location))), 1, 4) = "HTTP" Then
   &xmlstr = %IntBroker.ConnectorRequestUrl(&location);
   Else
   &xmlstr = %This.getXmlContentFromFile(&location);
   End-If;

   &xmldoc = CreateXmlDoc("");

   If &xmldoc.ParseXmlString(&xmlstr) Then
   Return &xmldoc;
   End-If;

end-method;
```

Related Links

ConnectorRequest

DefaultLocalNode

Syntax

DefaultLocalNode()

Description

Use the DefaultLocalNode method to return the name of the default local node on this system.

Parameters

None.

Returns

String.

Example

In a Mobile Application Platform (MAP) application, use this method when generating a link to a classic component or to a fluid component. For example, the following PeopleCode generates a link to a fluid homepage.

```
&URL = GenerateComponentPortalURL(%IntBroker.DefaultPortalName(), %IntBroker.Defaul⇒
tLocalNode(), MenuName.NUI_FRAMEWORK, %MAP_Market, Component.PT_LANDINGPAGE, Page.P⇒
T_LANDINGPAGE, "U");
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

DefaultPortalName

"GenerateComponentPortalURL" (PeopleTools 8.54: PeopleCode Language Reference)

"%MAP_Market" (PeopleTools 8.54: PeopleCode Language Reference)

DefaultPortalName

Syntax

DefaultPortalName()

Description

Use the DefaultPortalName method to return the name of the default portal on this system.

Parameters

None.

Returns

None.

Example

In a MAP application, use this method when generating a link to a classic component or to a fluid component. For example, the following PeopleCode generates a link to a fluid homepage.

```
&URL = GenerateComponentPortalURL(%IntBroker.DefaultPortalName(), %IntBroker.Defaul⇒
tLocalNode(), MenuName.NUI_FRAMEWORK, %MAP_Market, Component.PT_LANDINGPAGE, Page.P⇒
T_LANDINGPAGE, "U");
```

Related Links

DefaultLocalNode

"GenerateComponentPortalURL" (PeopleTools 8.54: PeopleCode Language Reference)

"%MAP_Market" (PeopleTools 8.54: PeopleCode Language Reference)

DeleteLayoutCache

Syntax

DeleteLayoutCache(*MAP_layout*)

Description

Use this method to delete all cached copies of this Mobile Application Platform (MAP) application.

Parameters

MAP_layout	Specifies the name of the MAP application (layout) as a String.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

A Boolean value: True if the method completes successfully, False otherwise.

Example

Use the DeleteLayoutCache method in the OnInitEvent to clear any cached copies of this MAP application:

```
&b = %IntBroker.DeleteLayoutCache("MAP_APP_2");
```

DeleteOrphanedSegments

Syntax

DeleteOrphanedSegments(*TransactionId*)

Description

Use the DeleteOrphanedSegments method to delete segments that might have been orphaned if you were processing message segments using a Application Engine program that had to be restarted. Since each segment is committed to the database, if the application engine program is aborted, these segments need to be deleted from the database.

Parameters

TransactionId	Specify the transaction ID that identifies the message which contains the segments you want to delete.

Returns

A Boolean value: true if the method completes successfully, false otherwise.

Related Links

SegmentRestart

"Working With Message Segments" (PeopleTools 8.54: Integration Broker)

DeleteRESTCache

Syntax

DeleteRESTCache(*service_op, service_op_ver*

Description

Use the DeleteRESTCache method to delete a server-side REST cache created by the SetRESTCache method.

Parameters

service_op	Specifies the Integration Broker service operation as a string.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

service_op_ver Specify the version of the specified operation as a string.

Returns

A Boolean value: True if the cache was deleted successfully, False otherwise.

Example

```
Local Message &MSG;
Local datetime &dt;
Local string &op, &ver;

&MSG.SetRESTCache(&dt);

&b_ret = %IntBroker.DeleteRESTCache(&op, &ver);
```

Related Links

SetRESTCache

GenLayoutHTML

Syntax

GenLayoutHTML(*MAP_layout*, *URI_index*, *&doc* [, *element_ID*] [, *gen_JSON*])

Description

Use this method to generate all or a portion of the HTML for a specified Mobile Application Platform (MAP) application. Use this method when you want to invoke another MAP application as an external page from the calling MAP application

Parameters

MAP_layout Specifies the name of the MAP application (layout) as a String.

URI_index Specifies the URI index as an Integer.

Note: The URI index is the number on the Initialization page associated with each resource available within a MAP application. See "Using the Initialization Page for Defining Layout Initialization Parameters and Values" (PeopleTools 8.54: Mobile Application Platform) for more information on URI indexes.

&doc Specifies the document for the MAP application to be invoked as a Document object.

element_ID Specifies the ID for a specific element as a String, if only the HTML for that element is to be generated. Valid element types include containers, sidebars, headers, and footers. You can use either the system-generated ID or the developer-defined alternate ID for the element.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

gen_JSON Specifies a Boolean value indicating whether to also return the document data as a JSON string.

Returns

The return data type depends on the *gen_JSON* parameter:

- When *gen_JSON* is False or is omitted, the method returns a String that is the HTML.
- When *gen_JSON* is True, the method returns a two-dimensional Array of String:
  - The first element is the HTML.
  - The second element is the document data as a JSON string of attribute-value pairs.

Example

In the following example, the external MAP application is to be called from page 4 of the invoking MAP application. A Document object is created and populated with data from the current MAP application. Then, the GenLayoutHTML method is executed to return the portion of HTML corresponding to a specific container in the invoked MAP application. Finally, this returned HTML is assigned to a primitive that has been associated with an HTML area element in the invoking MAP application.

```
If &URICOM.GetPropertyByName("PAGE_ID").Value = 4 Then
   &Doc1 = CreateDocument("MAP_LAYOUT", "FLIGHTCARD1_MAP", "v1");
   &COM2 = &Doc1.DocumentElement;
   &COM2.GetPropertyByName("PAGE_ID").Value = "INIT";
   &COM2.GetPropertyByName("LAYOUT_ID").Value = - 1;
   &COM2.GetPropertyByName("Pilot").Value = &URICOM.GetPropertyByName("Pilot").Valu⇒
e;
   &COM2.GetPropertyByName("CardNbr").Value = &URICOM.GetPropertyByName("CardNbr").⇒
Value;
   &temp = %IntBroker.GenLayoutHTML("FLIGHTCARD", 2, &Doc1, "mapcont_start_1");

   &COM.GetPropertyByName("prim_text").Value = &temp;
end-if;
```

GetImageURL

Syntax

GetImageURL(*image_name*)

Description

Use this method to get the URL to an image that has been uploaded using the Layout Image Upload page.

Parameters

image_name Specifies the name of the image as a String.

Returns

A String value.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

Use the GetImageURL method in a Mobile Application Platform (MAP) application to return the image's URL to be assigned to the designated dynamic image's primitive.

```
&COM_NAV.GetPropertyByName("Altitude").Value = %IntBroker.GetImageURL("MAP_ACTIONS"⇒
);
```

GetArchData

Syntax

GetArchData(*TransactionId*, *SegmentIndex*)

Description

Use the GetArchData method to retrieve an archived message from the message queue.

Note: This method shouldn't be used in standard message processing. It should only be used when accessing archived messages.

Parameters

TransactionId	Specify the transaction ID of the archived message you want to retrieve.
SegmentIndex	Specify the number of the segment of the archived message that you want to retrieve.

Returns

An XML string containing the archived data.

Related Links

GetArchIBInfoData

GetArchIBInfoData

Syntax

GetArchIBInfoData(*TransactionId*, *ParentTransactionId*)

Description

Use the GetArchIBInfoData method to retrieve return archived IBInfo data.

Note: This method shouldn't be used in standard message processing. It should only be used when accessing archived messages.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

TransactionId Specify the transaction ID of the archived message you want to retrieve.

ParentTransactionId Specify the parent transaction ID, for the message.

Returns

An XML string containing the archived data.

Related Links

GetArchData

GetIBInfoData

Syntax

GetIBInfoData(*TransactionId*, *DataType*)

Description

Use the GetIBInfoData to return the specified IBInfo data.

Parameters

TransactionID Specify the transaction ID of the message that you want to access.

DataType Specify the data type of the message you want to access. The valid values are:

Constant Value	*Description*
%IntBroker_BRK	Get the message for the web services gateway.
%IntBroker_PUB	Get the message for the publication contract.
%IntBroker_SUB	Get the message for the subscription contract.

Returns

An XML string containing the message data.

Related Links

GetArchIBInfoData

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GetIBTransactionIDforAE

Syntax

GetIBTransactionIDforAE(*OperID*, *RunCtlID*)

Description

Use this method to get the Integration Broker transaction ID from within an Application Engine program. You can use this transaction ID to instantiate a message object and thereby retrieve the message content data.

Parameters

OperID Specifies the operator ID for the Application Engine program as a string.

RunCtlID Specifies the run control ID for the Application Engine program as a string.

Returns

A string representing the transaction ID.

Example

```
&TransID = %IntBroker.GetIBTransactionIDforAE(&opid, &runid);
&Msg = %IntBroker.GetMessage(&TransID, %IntBroker_SUB);
```

GetMessage

Syntax

GetMessage([*TransactionId*, *DataType*])

Description

Use the GetMessage method to return a message object.

If you specify a transaction ID and data type, the GetMessage method populates the message object with the data from that message.

If you do not specify any parameters, the GetMessage method doesn't populate the message with data. Instead, it creates a new instance of a message object. In this case, you must use another method, such as GetRowset, to populate the message object. You must always populate the message object with data before running any methods on it.

Parameters

TransactionId Specify the transaction ID for the message that you want returned.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

DataType Specify the type of message that you want returned. The valid values are:

Constant Value	*Description*
%IntBroker_BRK	Get the message for the web services gateway.
%IntBroker_PUB	Get the message for the publication contract.
%IntBroker_SUB	Get the message for the subscription contract.

Returns

A reference to a message object if successful, Null if not successful.

Example

The following example returns a populated message object:

```
Local Message &MSG;
Local string &TransactionId;

&TransactionId = "0f3617dl-c6f4-11d9-a4bd-c12cbalbc2f9"
&MSG = %IntBroker.GetMessage(&TransactionId, %IntBroker_BRK);
```

Related Links

GetRowset

TransactionId

GetMessageErrors

Syntax

GetMessageErrors(*TransactionId*)

Description

Use the GetMessageErrors method to return an array that contains the errors that an application has set for the message, and have been written to the error queue. This method is generally only used with asynchronous messages.

Parameters

TransactionId Specify the transaction ID for the message, as a string.

Returns

An array of string. If there are no error messages, the Len property of the array is 0.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

The following is an example of using the method for returning web services gateway error messages:

```
&MyErrors = %IntBroker.GetMessageErrors(&TransactionId);
```

Related Links

SetMessageError

"Processing Inbound Errors" (PeopleTools 8.54: Integration Broker)

GetMsgSchema

Syntax

GetMsgSchema(*MsgName, MsgVersion*)

Description

Use the GetMsgSchema method to access the saved schema for the specified message.

If you specify a message that does not have a saved schema, you receive a null value.

Parameters

MsgName	Specify the name of the message for which you want to access a schema. You can either specify the name of the message as a string, or preface the message name with the keyword **Message.**
MsgVersion	Specify the message version.

Returns

A string containing the message schema. If you try to get a schema for a message that does not have a saved schema, returns null.

Related Links

MsgSchemaExists

"Understanding the Message Schema Builder" (PeopleTools 8.54: Integration Broker)

GetSyncIBInfoData

Syntax

GetSyncIBInfoData(*TransactionId, %LogType* [, *Archive*])

Description

Use the GetSyncIBInfoData method to return a log containing information about synchronous transactions.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

TransactionId Specify the transaction ID of the published message.

LogType Specify the type of log you want returned, based on the type of message. See below for the valid values.

Archive Specify whether to retrieve any archived logs as well. This parameter takes a Boolean value: true to return archived logs, false otherwise. The default value is false.

For the *LogType* parameter, the valid values are:

Constant Value	***Description***
%Sync_RequestOrig	Gets the log for a sync request original data message.
%Sync_RequestTrans	Gets the log for a sync request transformed data message.
%Sync_ResponseOrig	Gets the log for a sync response original data message.
%Sync_ResponseTrans	Gets the log for a sync response transformed data message.

Returns

An XML string containing the log data.

Related Links

"Service Operations Monitor Features" (PeopleTools 8.54: Integration Broker Service Operations Monitor)

GetSyncLogData

Syntax

```
GetSyncLogData(TransactionId, %LogType [, Archive])
```

Description

Use the GetSyncLogData method to return a log containing information about the specified synchronous message.

You can use this information for debugging. Using this method, you can obtain the request and response data in a synchronous request, both pre- and post-transformation.

This function is used in the PeopleCode for the Message Monitor.

Parameters

TransactionId Specify the transaction ID of the published message.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

LogType Specify the type of log you want returned, based on the type of message. See below for the valid values.

Archive Specify whether to retrieve any archived logs as well. This parameter takes a Boolean value: true to return archived logs, false otherwise. The default value is false.

For the *LogType* parameter, the valid values are:

Constant Value	***Description***
%Sync_RequestOrig	Gets the log for a sync request original data message.
%Sync_RequestTrans	Gets the log for a sync request transformed data message.
%Sync_ResponseOrig	Gets the log for a sync response original data message.
%Sync_ResponseTrans	Gets the log for a sync response transformed data message.

Returns

An XML string containing the log data.

Related Links

"Service Operations Monitor Features" (PeopleTools 8.54: Integration Broker Service Operations Monitor)

GetURL

Syntax

```
GetURL(service_op_name, service_op_index, &doc_object, [secure_target],
[encode_unsafe])
```

Description

Use this method to generate a fully qualified URL for any REST-based service operation resource.

Parameters

service_op_name Specifies the Integration Broker service operation as a string.

service_op_index Specifies the the index for the URI as an integer. This index corresponds to the row number in the URI grid of the REST Resource Definition section of the service operation definition.

&doc_object Specifies the document template for the service operation as a Document object.

secure_target Specifies whether the REST location is a secure target location. The default value is the non-secure target location.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

encode_unsafe Specifies whether to encode unsafe characters as a Boolean value. The default is False (no encoding).

Returns

A string populated with the fully qualified URL.

Example

HTML is generated within the OnRequest event of a REST-based provider service using links defined from other REST-based service operations. Note that the REST-based service operation resources on either the publishing node (the provider) or the subscribing node (the consumer) can be used to generate the fully qualified links.

```
import PS_PT:Integration:IRequestHandler;

class RESThandler implements PS_PT:Integration:IRequestHandler
   method OnRequest(&message As Message) Returns Message;
   method OnError(&request As Message) Returns string;
end-class;

method OnRequest
   /+ &message as Message +/
   /+ Returns Message +/
   /+ Extends/implements PS_PT:Integration:IRequestHandler.OnRequest +/

   Local Document &Doc_Tmpl, &DOC;
   Local Compound &COM_Tmpl, &COM;
   Local Message &response;
   Local string &STR, &STR1, &STR2, &STR3, &STR4, &strHTML;
   Local boolean &bRet;

   &response = CreateMessage(Operation.WEATHERSTATION_GET, %IntBroker_Response);

   /* read URI Document to get parms out from the request*/
   &Doc_Tmpl = &message.GetURIDocument();
   &COM_Tmpl = &Doc_Tmpl.DocumentElement;

   /* Instantiate a Document object based on the REST-based service operations    d⇒
ocument template that you want to create a link for */

   &DOC = CreateDocument("Weather", "WeatherTemplate", "v1");
   &COM = &DOC.DocumentElement;

   /* based off the data from the request populate the Document object */

   If &COM_Tmpl.GetPropertyByName("state").Value = "Washington" Then

   &COM.GetPropertyByName("state").Value = "Washington";

   /* call new method to create fully qualified URL(s) */

   &COM.GetPropertyByName("city").Value = "WhiteSalmon";
   &STR = %IntBroker.GetURL("WEATHERSTATION_GET", 2, &DOC, true, true);

   &COM.GetPropertyByName("city").Value = "Troutlake";
   &STR1 = %IntBroker.GetURL("WEATHERSTATION_GET", 2, &DOC);

   &COM.GetPropertyByName("city").Value = "Yakima";
   &STR2 = %IntBroker.GetURL("WEATHERSTATION_GET", 2, &DOC);

   &COM.GetPropertyByName("city").Value = "Lyle";
   &STR3 = %IntBroker.GetURL("WEATHERSTATION_GET", 2, &DOC);
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
   /* use these URLs as bind variables for the HTML definition */
   &strHTML = GetHTMLText(HTML.WEATHER_CITIES, &STR, &STR1, &STR2, &STR3);

   /* set the data in the response message */
   &bRet = &response.SetContentString(&strHTML);

   End-If;

   Return &response;

end-method;
```

Related Links

GetURIDocument

InBoundPublish

Syntax

InBoundPublish(*&Message*)

Description

Use the InBoundPublish method to send an asynchronous message based on the specified message to simulate an inbound asynchronous request from an external node. Although you are sending a message to yourself, it goes through all the inbound message processing that the specified message would.

Prior to call the InBoundPublish method, the Message object needs to populated with the requesting node and external operation name.

See "Simulating Receiving Messages from External Nodes" (PeopleTools 8.54: Integration Broker).

Parameters

&Message	Specify an already instantiated message object that you want to use for the message simulation.

Returns

A Boolean value, true if the message is published successfully, false otherwise.

Related Links

Publish

SyncRequest

IsOperationActive

Syntax

IsOperationActive(*OperationName* [,*OperationVersion*])

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the IsOperationActive method to determine if an operation is active or not.

Parameters

OperationName	Specify the name of the operation that you want to check the status of.
OperationVersion	Specify the version of the specified operation that you want to check the status of, as a string.

Returns

A Boolean value: true if the operation is active, false otherwise.

MAPLogout

Syntax

MAPLogout(*MAP_layout*)

Description

Use this method to generate the logout URL for this Mobile Application Platform (MAP) application. This URL can be assigned to a button, link, or some other page element. When the user clicks this element, the user is signed out of the application.

Parameters

MAP_layout	Specifies the name of the MAP application (layout) as a String.

Returns

A String value.

Example

Use this method to return the URL that can be assigned to a button, which when clicked will sign the user out of the application.

```
&URL_str = %IntBroker.MAPLogout(&MAP.LayoutName);
```

MsgSchemaExists

Syntax

MsgSchemaExists(*MsgName*, *MsgVersion*)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the MsgSchemaExists method to determine if a schema has been created and saved for the specified message.

Parameters

MsgName	Specify the name of the message for which you want to access a schema. You can either specify the name of the message as a string, or preface the message name with the keyword **Message.**
MsgVersion	Specify the message version.

Returns

A Boolean value: true if the message schema exists, false otherwise.

Related Links

GetMsgSchema
"Understanding the Message Schema Builder" (PeopleTools 8.54: Integration Broker)

Publish

Syntax

```
Publish(&Message [, &ArrayofNodeNames] [,IsEnqueued])
```

Description

The Publish method publishes a message to the message queue for the default message version.

This method does not publish the message if the IsOperationActive property for the message is False.

This method publishes a message asynchronously, that is, a reply message is not automatically generated. To publish a message synchronously, use the SyncRequest method.

Note: This method supports nonrowset-based messages only if the data is populated using the SetXmlDoc method.
If the Publish method is called and the message isn't populated (either using SetXmlDoc or one of the rowset methods,) an empty message is published.

The Publish method can be called from any PeopleCode event, but is generally called from an Application Engine PeopleCode step or from a component.

When publishing from a component, you should publish messages only from the SavePostChange event, either from record field or component PeopleCode. This way, if there's an error in your publish code, the data isn't committed to the database. Also, since SavePostChange is the last Save event fired, you avoid locking the database while the other save processing is happening.

However, until the message is published, the tables involved with the component are locked and are not saved. To avoid problems with this, specify the *Deferred_Mode* property as true, so the message is published after the table data has been committed to the database.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Note: If you're publishing a message from within an Application Engine program, the message won't actually be published until the calling program performs a Commit.

Parameters

&Message	Specify an already instantiated message object to be published.
&ArrayofNodeNames	Specify an already instantiated array of string containing the names of the nodes that you want to publish to.
IsEnqueued	Specify whether the message is to be enqueued or not. This parameter takes a Boolean value: true if the message is to be enqueued, false otherwise. The default value is false.

Returns

None.

Example

```
Local Message &Msg;
Local Rowset &rs;
Local IntBroker &Ib;

&Flight_profile = GetLevel0();

&Msg = CreateMessage(Operation.ASYNC, %IntBroker_Request);

&Msg.CopyRowset(&FlightProfile);

&Ib = %IntBroker;

&Ib.Publish(&Msg);
```

Related Links

SyncRequest

Resubmit

Syntax

```
Resubmit({TransactionId, QueueName, DataType, SegmentIndex} | {TransactionIdArray,
QueueNameArray, DataTypeArray, SegmentIndexArray})
```

Description

Use the Resubmit method to programmatically resubmit either a message, or a list of messages, from the message queue, much the same as you can do in the message monitor.

You may want to use this method after an end-user has finished fixing any errors in the message data, and you want to resubmit the message, rerunning the PeopleCode.

This method is only available when the message has one of the following statuses:

- Canceled

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- Edited
- Error
- Timeout

If you are specifying an array of messages to be resubmitted, and any message in the array fails for any reason (for example, you specify a message that doesn't have the correct status) no messages are resubmitted and the method return value is false.

Parameters

TransactionId* | *TransactionIdArray Specify either a single transaction ID as a string, or specify an array of string containing the transaction Ids of the messages you want to resubmit.

QueueName* | *QueueNameArray Specify either a single queue name as a string, or specify an array of string containing the queue names that contain the messages you want to resubmit.

DataType* | *DataTypeArray Specify either a single data type, or an array of string containing the data types. See below for the valid data type values.

SegmentIndex* | *SegmentIndexArray Specify either a specific segment, or an array of integer containing the segment numbers you want to resubmit.

For the *DataType* or *DataTypeArray* parameters, the valid data types are:

Constant Value	*Description*
%IntBroker_BRK	Resubmit the message for the web services gateway.
%IntBroker_PUB	Resubmit the message for the publication contract.
%IntBroker_SUB	Resubmit the message for the subscription contract.

Returns

A Boolean value: true if the message or messages are resubmitted successfully, false otherwise.

Related Links

Cancel

SetMessageError

Syntax

```
SetMessageError(TransactionID, MsgSet, MsgNumber, Error_Location, ParamListCounter,
[Param] ...)
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the SetMessageError method to write messages to the error queue. This method is used with asynchronous messages only.

Parameters

TransactionID	Specify the transaction ID for the message as a string.
MsgSet	Specify the number of the message set that the message associated with the error is associated with.
MsgNumber	Specify the message number that you want to associate with this error.
Error_Location	Specify where the error occurred, or any additional information you want to give about the error. This is a string, and allows 254 characters.
ParamListCounter	An integer value from 0 to 4 specifying the number of *Param* substitution strings to be passed.
Param	Specify up to four *Param* values to be used as substitution strings in the message text. The first *Param* value is used in the first substitution (that is, for %1,) the second is used in the second (that is, for %2), and so on.

Returns

A Boolean value, true if the error message was associated correctly, false otherwise.

Example

The following is an example of setting an error message for the web services gateway:

```
&Rslt = %IntBroker.SetMessageError(&TransactionId, &msgset, &msgnum, "error locatio⇒
n", 4, &parm1, &parm2, &parm3, &parm4);
```

If you are passing just two parameters, then the call would be similar to this:

```
&Rslt = %IntBroker.SetMessageError(&TransactionId, &msgset, &msgnum, "error locatio⇒
n", 2, &parm1, &parm2);
```

Related Links

"Processing Inbound Errors" (PeopleTools 8.54: Integration Broker)

GetMessageErrors

SetStatus

Syntax

SetStatus(*&Message*, *Status*)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the SetStatus method to set the status of a publication or subscription contract, much the same way you do it in the message monitor.

You may want to use this method after an end-user has finished fixing any errors in the message data.

You can set the status of a contract to one of the following statuses:

- Canceled
- Done
- Error
- New

The method is available only when the message instance has one of the following statuses:

- Canceled
- Done
- Error
- New

Parameters

&Message Specify an already instantiated message object that you want to set the status for.

Status Specify the status that you want to set the message to. Valid status are:

Constant Value	*Description*
%Operation_Canceled	Cancel the message.
%Operation_Done	Set the message to done.
%Operation_Error	Set the message to be in error.
%Operation_New	Specify the message as new.

Returns

None.

SwitchAsyncEventUserContext

Syntax

SwitchAsyncEventUserContext(*UserID*, *LanguageCode*)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the SwitchAsyncEventUserContext method to switch the user context within an Integration Broker asynchronous event.

Parameters

UserID	Specify the user ID, as a string, to which you want to switch the context.
LanguageCode	Specify the language code, as a string, for the user ID.

Returns

A Boolean value: true if the switch user was successful, false otherwise.

Example

```
&returnValue = %IntBroker.SwitchAsyncEventUserContext("VP1", "ENG");
```

SyncRequest

Syntax

```
SyncRequest([&MsgArray, &NodeNames])
```

Description

Use the SyncRequest method to send multiple messages at the same time. You should only use this message with synchronous messages. You can also use this method to send a single synchronous message at a time, or you can use the SyncRequest Message class method.

If you want to publish messages asynchronously, use the Publish method.

Note: This method supports nonrowset-based messages only if the SetXmlDoc method is used to populate the message prior to using the SyncRequest method.

You must set the thread pool size of the application server on the receiving system to a value greater than 1 (the default) in order to process more than one message at a time.

How many threads you specify determines how many messages are worked on simultaneously. For example, if you have 10 messages in *&MsgArray*, and your thread pool size is 5, then only 5 messages are processed at a time.

The maximum number you can specify for your thread pool size is 10.

Parameters

&MsgArray	Specify an already instantiated array of messages that contains the messages you want to publish.
&NodeNames	Specify an already instantiated array of string containing the names of the nodes that you want to publish to. The first

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

message in the array of messages is published to the first node, the second message is published to the second node, and so on.

Returns

An array of messages. These are the corresponding messages returned for the published messages. The first message in the returned array corresponds to the first message in the published array, the second message with the second, and so on.

Example

The following is an example of how creating and receiving a series of messages:

```
Local Rowset &FLIGHTPLAN, &FLIGHTPLAN_RETURN;
Local Message &MSG;
Local File &BI_FILE;
Declare Function out_BI_results PeopleCode QE_FLIGHTDATA.QE_ACNUMBER FieldFormula;

Local array of Message &messages;
Local array of Message &return_mesages;

&messages = CreateArrayRept(&MSG, 0);
&return_mesages = CreateArrayRept(&MSG, 0);

&FLIGHT_PROFILE = GetLevel0();
&messages [1] = CreateMessage(OPERATION.QE_FLIGHTPLAN_SYNC);
&messages [1].CopyRowset(&FLIGHT_PROFILE);

&messages [2] = CreateMessage(OPERATION.QE_FLIGHTPLAN_SYNC);
&messages [2].CopyRowsetDelta(&FLIGHT_PROFILE);

&return_mesages = %IntBroker.SyncRequest(&messages);

&FLIGHTPLAN_RETURN = &return_mesages [1].GetRowset();
&temp = &return_mesages [1].GenXMLString();

out_BI_results(&temp);

&FLIGHTPLAN_RETURN = &return_mesages [2].GetRowset();
&temp = &return_mesages [2].GenXMLString();

out_BI_results(&temp);
```

Related Links

SyncRequest

Update

Syntax

Update(*&Message*)

Description

Use the Update method to update a message in the message queue with the specified message object.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

&Message Specify an already instantiated and populated message object to be used to update an existing message in the message queue.

Returns

A Boolean value, true if the message is updated successfully, false otherwise.

Related Links

UpdateXmlDoc

UpdateDocument

Syntax

UpdateDocument(*&doc, update_type*)

Description

Use this method to update the database based on the data in the specified Document object. The method can be used in a Mobile Application Platform (MAP) event only.

Important! To use this method, the document must be defined as a physical relational document.

Parameters

&doc Specifies the document as a Document object.

update_type Specifies the type of update to perform as an Integer. The constant values are:

Constant Value	*Description*
%Document_Update	Update the database by adding the keys and data from the specified document.
%Document_Replace	Update the database by first deleting data associated with any keys specified in the document, and then replacing them with the keys and data from the specified document.
%Document_Delete	Update the database by deleting data associated with any keys from the specified document.

Returns

A Boolean value: True if the update occurred successfully, False otherwise.

UpdateXmlDoc

Syntax

UpdateXmlDoc(*&XmlDoc, TransactionId, DataType*)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the UpdateXmlDoc method to update a message in the message queue with the specified message data.

Note: This method shouldn't be used in a subscription program.

Parameters

&XmlDoc Specify an already instantiated and populated XmlDoc object.

TransactionId Specify the transaction ID of the message you want to update.

DataType Specify the data type of the message that you want to update. Valid values are:

Constant Value	*Description*
%IntBroker_BRK	Update the message for the web services gateway.
%IntBroker_PUB	Update the message for the publication contract.
%IntBroker_SUB	Update the message for the subscription contract.

Returns

A Boolean value, true if the message was updated successfully, false otherwise.

Related Links

Update

IBInfo Class

An IBInfo object is returned from the IBInfo message class property.

Related Links

IBInfo

IBInfo Class Methods

In this section, we discuss the IBInfo class methods. The methods are discussed in alphabetical order.

All methods work with both asynchronous as well as synchronous messages unless specified

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

AddAEAttribute

Syntax

AddAEAttribute(*Name*, *value*)

Description

Use this method to add an attribute as a name-value pair to the Message object to be passed back to the response application class defined on the Application Engine handler.

Parameters

Name	Specifies the attribute name as a string.
value	Specifies the attribute value as a string.

Returns

A Boolean value: True if the attribute was added successfully, False otherwise.

Example

```
/* Add the name value pair data you want to pass to the response app class */
/* in the AE program */

&b = &MSG.IBInfo.AddAEAttribute("sail name", "NorthWave");
If &b <> True Then
   MessageBox(0, "", 0, 0, "error adding ae attribute");
End-If;

&b = &MSG.IBInfo.AddAEAttribute("size", "4.2");
If &b <> True Then
   MessageBox(0, "", 0, 0, "error adding ae attribute");
End-If;

&b = &MSG.IBInfo.AddAEAttribute("type", "Surflite");
If &b <> True Then
   MessageBox(0, "", 0, 0, "error adding ae attribute");
End-If;

/* Need to call this method for the attributes to be saved and transferred */
/* correctly */
&b = &MSG.IBInfo.InsertAEResponseAttributes();
If &b <> True Then
   MessageBox(0, "", 0, 0, "error inserting AE response attributes");
End-If;

/* ******************************************************************** */
/* In the response application class to retrieve the name-value pairs      */

For &i = 1 To &MSG.IBInfo.GetNumberOfAEAttributes()

   &name = &MSG.IBInfo.GetAEAttributeName(&i);
   &value = &MSG.IBInfo.GetAEAttributeValue(&i);

End-For;
```

Related Links

ClearAEAttributes

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

DeleteAEAttribute
GetAEAttributeName
GetAEAttributeValue
GetNumberofAEAttributes
GetTransactionIDforAE
InsertAEResponseAttributes

AddAttachment

Syntax

AddAttachment(*Path*)

Description

Use the AddAttachment method to add an attachment to a message.

Parameters

Path Specify an absolute path, including the file name and type, as a string, of the file you want to attach to the message.

Returns

A string containing a content ID, which can be used for accessing the attachment with other methods, such as DeleteAttachment or SetAttachmentProperty.

Example

The following example shows sending an attachment with an asynchronous message:

```
Local Message &MSG;
Local Rowset &FLIGHT_PROFILE;
Local String &Attachment_Id;
Local Boolean &Test;
Local IntBroker &IntBroker;

QE_FLIGHTDATA.QE_ACNUMBER.Value = QE_FLIGHTDATA.QE_ACNUMBER + 1;

&FLIGHT_PROFILE = GetLevel0();

&MSG = CreateMessage(Operation.ASYNC_RR);

&Attachment_Id = &MSG.IBInfo. AddAttachment("C:\\temp\\MyFile.txt");
&Test = &MSG.IBInfo.SetAttachmentProperty(&Attachment_Id, %Attachment_Encoding, "UT⇒
F-8");
&Test = &MSG.IBInfo.SetAttachmentProperty(&Attachment_Id, %Attachment_Base, "Standa⇒
rd");
&Test = &MSG.IBInfo.SetAttachmentProperty(&Attachment_Id, %Attachment_Disposition, ⇒
"Pending");
&Test = &MSG.IBInfo.SetAttachmentProperty(&Attachment_Id, %Attachment_Language, "En⇒
glish");
&Test = &MSG.IBInfo.SetAttachmentProperty(&Attachment_Id, %Attachment_Description, ⇒
"Parts data");

&MSG.CopyRowset(&FLIGHT_PROFILE);

&IntBroker = %IntBroker
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
&IntBroker.Publish(&MSG);
```

Related Links

ClearAttachments
DeleteAttachment
SetAttachmentProperty

AddAttribute

Syntax

AddAttribute(*name*, *value*)

Description

Use this method to add an attribute to an IBInfo object.

Note: This method can be used for content-based routing only, typically in your implementation of the IRouter.OnRouteSend or IRouter.OnRouteReceive methods.

The maximum length of the attribute name is 30 characters. The maximum length of the attribute value is 254 characters.

Parameters

name	Specifies the attribute name as a string.
value	Specifies the attribute value as a string.

Returns

A Boolean value: true if the addition of the attribute was successful, false otherwise.

Example

```
&bRet = &MSG.IBInfo.AddAttribute("employeeID", "123456");
```

Related Links

Content-Based Routing

AddContainerAttribute

Syntax

AddContainerAttribute(*Name*, *Value*)

Description

Use this method to add a container attribute by specifying an attribute name-value pair.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

You can add attributes to container messages that contain rowset-based message parts to provide integration partners with data and information, without adding the information to the message definition.

Parameters

Name	Specifies the container attribute name as a string.
Value	Specifies the container attribute value as a string.

Returns

A Boolean value: True if the container attribute was added successfully, False otherwise..

Example

```
Local Message &MSG;
Local Rowset &RS;
Local boolean &Bo;

&RS = GetLevel0();
&MSG = CreateMessage(Operation.QE_CONT_ATTRB);

&Bo = &MSG.IBInfo.AddContainerAttribute("Test1", "1");
&Bo = &MSG.IBInfo.AddContainerAttribute("Test2", "10");
&Bo = &MSG.IBInfo.AddContainerAttribute("Test3", "100");

&MSG.CopyPartRowset(1, &RS);

%IntBroker.Publish(&MSG);
```

Related Links

"Managing Container Messages" (PeopleTools 8.54: Integration Broker)

ClearContainerAttributes

DeleteContainerAttribute

GetContainerAttributeName

GetContainerAttributeValue

GetNumberOfContainerAttributes

ClearAEAttributes

Syntax

`ClearAEAttributes``()`

Description

Use this method to delete all Application Engine handler attributes from the Message object.

Parameters

None.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

None.

Related Links

AddAEAttribute
DeleteAEAttribute

ClearAttachments

Syntax

```
ClearAttachments()
```

Description

Use the ClearAttachments method to clear all attachments. If you want to delete a particular attachment, use DeleteAttachment instead.

Parameters

None.

Returns

None.

Related Links

AddAttachment
DeleteAttachment

ClearAttributes

Syntax

```
ClearAttributes()
```

Description

Use this method to delete all attributes from an IBInfo object.

Note: This method can be used for content-based routing only, typically in your implementation of the IRouter.OnRouteSend or IRouter.OnRouteReceive methods.

Parameters

None.

Returns

None.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

```
&MSG.IBInfo.ClearAttributes();
```

Related Links

Content-Based Routing

ClearContainerAttributes

Syntax

ClearContainerAttributes()

Description

Use this method to delete all container attributes in the IBInfo object.

Parameters

None

Returns

None

Example

```
&MSG.IBInfo.ClearContainerAttributes();
```

Related Links

AddContainerAttribute
DeleteContainerAttribute

DeleteAEAttribute

Syntax

DeleteAEAttribute(*Name*)

Description

Use this method to delete the Application Engine handler attribute specified by attribute name from the Message object.

Parameters

Name	Specifies the name of the attribute as a string.

Returns

A Boolean value: True if the deletion was successful, False otherwise.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

AddAEAttribute
ClearAEAttributes
GetAEAttributeName

DeleteAttachment

Syntax

DeleteAttachment(*Index | Content_ID*)

Description

Use the DeleteAttachment method to remove the specified attachment from the message. You can either specify the number of the attachment, or the content ID associated with the attachment (generated when the attachment was added to the message with AddAttachment.)

If you want to clear all attachments, instead of a particular one, use the ClearAttachments methods instead.

Parameters

Index* | *Content_ID	Specify either the number of the attachment, or the content ID associated with the attachment, for the attachment you want to delete.

Returns

A Boolean value: true if the attachment was deleted successfully, false otherwise.

Related Links

AddAttachment
ClearAttachments

DeleteAttribute

Syntax

DeleteAttribute(*name*)

Description

Use this method to delete an attribute from an IBInfo object by specifying the attribute's name as a string.

Note: This method can be used for content-based routing only, typically in your implementation of the IRouter.OnRouteSend or IRouter.OnRouteReceive methods.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

name	Specifies the attribute by name as a string.

Returns

A Boolean value: true if the deletion of the attribute was successful, false otherwise.

Example

```
&bRet = &MSG.IBInfo.DeleteAttribute("employeeID");
```

Related Links

Content-Based Routing
GetAttributeName

DeleteContainerAttribute

Syntax

DeleteContainerAttribute(*Name*)

Description

Use this method to delete a container attribute based on the attribute name.

Parameters

Name	Specifies the container attribute name as a string.

Returns

A Boolean value: True if the deletion was successful, False otherwise.

Example

```
&Ret = &MSG.IBInfo.DeleteContainerAttribute("MyAttribute");
```

Related Links

AddContainerAttribute
ClearContainerAttributes
GetContainerAttributeName

GetAEAttributeName

Syntax

GetAEAttributeName(*nIndex*)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use this method to return the name of the *nth* Application Engine handler attribute from the Message object. For example, the response application class can use this method to retrieve the attribute name.

Parameters

nIndex An integer specifying which attribute in the Message object.

Returns

A string populated with the attribute name.

Related Links

AddAEAttribute
GetAEAttributeValue
GetNumberofAEAttributes

GetAEAttributeValue

Syntax

GetAEAttributeValue(*nIndex*)

Description

Use this method to return the value of the *nth* Application Engine handler attribute from the Message object. For example, the response application class can use this method to retrieve the attribute value.

Parameters

nIndex An integer specifying which attribute in the Message object.

Returns

A string populated with the attribute value.

Related Links

AddAEAttribute
GetAEAttributeName
GetNumberofAEAttributes

GetAttachmentContentID

Syntax

GetAttachmentContentID(*Index*)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the GetAttachmentContentID to return the content ID for the specified attachment. The content ID is associated with an attachment when it is added to a message using AddAttachment.

You can use the content ID with other methods, such as AddAttachmentProperty and DeleteAttachment.

Parameters

Index Specify the number of the attachment that you want to access the content ID for.

Returns

A string containing the content ID.

Related Links

AddAttachment
GetAttachmentProperty

GetAttachmentProperty

Syntax

GetAttachmentProperty(*Content_ID*, *Property_Type*)

Description

Use the GetAttachmentProperty method to return the value of an attachment property.

Parameters

Content_ID Specify the content ID of the attachment that you want to access, as a string.

Property_Type Specify the type of property that you want to access. Valid values are:

Constant Value	*Description*
%Attachment_Base	Specifies the base name of the attachment, that is, if the actual document name you want is different, such as if it is zipped or otherwise compressed as part of other documents.
%Attachment_Description	Specifies the description of the attachment.
%Attachment_Disposition	Specifies the disposition of the attachment, whether it's displayed inline or as an attachment.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Constant Value	*Description*
%Attachment_Encoding	Specify the encoding of the attachment. For example, `Content-type: text/plain` or `charset=Big5`.
%Attachment_Language	Specify the language used in the attachment, as a string.
%Attachment_Location	Specify an additional location for the attachment.
%Attachment_Type	Specify the attachment type.
%Attachment_URL	Specifies the URL for the attachment. The URL must be an absolute URL.

Returns

A string containing the value of the specified property.

Example

The following example processes an attachment from a notification PeopleCode program:

```
Import PS_PT:Integration:INotificationHandler;

Class FLIGHTPROFILE implements PS_PT:Integration:INotificationHandler
   method FLIGHTPROFILE();
   method OnNotify(&MSG As Message);

end-class;

/* Constructor */
method FLIGHTPROFILE
   %Super = create PS_PT:Integration:INotificationHandler();
end-method;

method OnNotify
   /+ &MSG as Message +/
   /+ Extends/implements PS_PT:Integration:INotificationHandler.OnNotify +/

Local rowset &RS;
Local integer &Count;
Local string &Attachment_Id;
Local array of array of string &Result;

&RS = &MSG.GetRowset();

&Count = &MSG.IBInfo.NumberOfAttachments;
If &Count > 0 Then

   For &I = 1 to &Count
      &Attachment_ID = &MSG.IBInfo.GetAttachmentContentID(&I);
      &Result[&I][1] = &MSG.IBInfo.GetAttachmentProperty(&Attachment_Id, %Attachmen⇒
t_Encoding);
      &Result[&I][2] = &MSG.IBInfo.GetAttachmentProperty(&Attachment_Id, %Attachmen⇒
t_Type);
      &Result[&I][3] = &MSG.IBInfo.GetAttachmentProperty(&Attachment_Id, %Attachmen⇒
t_URL);
      &Result[&I][4] = &MSG.IBInfo.GetAttachmentProperty(&Attachment_Id, %Attachmen⇒
t_Base);
      &Result[&I][5] = &MSG.IBInfo.GetAttachmentProperty(&Attachment_Id, %Attachmen⇒
t_Location);
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
      &Result[&I][6] = &MSG.IBInfo.GetAttachmentProperty(&Attachment_Id, %Attachmen⇒
t_Disposition);
      &Result[&I][7] = &MSG.IBInfo.GetAttachmentProperty(&Attachment_Id, %Attachmen⇒
t_Description);

   End-For;

End-if;

/* process data from message */

end-method;
```

Related Links

SetAttachmentProperty

GetAttributeName

Syntax

GetAttributeName(*nIndex*)

Description

Use this method to return the attribute name for the *nth* attribute of the IBInfo object as a string.

Note: This method can be used for content-based routing only, typically in your implementation of the IRouter.OnRouteSend or IRouter.OnRouteReceive methods.

Parameters

nIndex	An integer specifying which attribute in the IBInfo object.

Returns

A string populated with the attribute name.

Example

```
&AttrName = &MSG.IBInfo.GetAttributeName(&i);
```

Related Links

Content-Based Routing
GetAttributeValue
GetNumberOfAttributes

GetAttributeValue

Syntax

GetAttributeValue(*nIndex*)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use this method to return the attribute value for the *nth* attribute of the IBInfo object as a string.

Note: This method can be used for content-based routing only, typically in your implementation of the IRouter.OnRouteSend or IRouter.OnRouteReceive methods.

Parameters

nIndex	An integer specifying which attribute in the IBInfo object.

Returns

A string populated with the attribute value.

Example

```
&AttrValue = &MSG.IBInfo.GetAttributeValue(&i);
```

Related Links

Content-Based Routing
GetAttributeName
GetNumberOfAttributes

GetContainerAttributeName

Syntax

GetContainerAttributeName(*nIndex*)

Description

Use this method to return the attribute name for the *n*th container attribute of the IBInfo object as a string.

Parameters

nIndex	An integer specifying which container attribute in the IBInfo object.

Returns

A string populated with the container attribute name.

Related Links

AddContainerAttribute
GetContainerAttributeValue
GetNumberOfContainerAttributes

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GetContainerAttributeValue

Syntax

GetContainerAttributeValue(*nIndex*)

Description

Use this method to return the attribute value for the *n*th container attribute of the IBInfo object as a string.

Parameters

nIndex	An integer specifying which container attribute in the IBInfo object.

Returns

A string populated with the container attribute value.

Related Links

AddContainerAttribute
GetContainerAttributeName
GetNumberOfContainerAttributes

GetNumberofAEAttributes

Syntax

GetNumberofAEAttributes()

Description

Use this method to return the number of Application Engine handler attributes in the Message object. For example, the response application class can use this method to retrieve the number of attributes before retrieving the attribute name-value pairs.

Parameters

None.

Returns

An integer representing the number of Application Engine handler attributes.

Related Links

AddAEAttribute
GetAEAttributeName
GetAEAttributeValue

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GetNumberOfAttributes

Syntax

GetNumberOfAttributes()

Description

Use this method to get the number of attributes for the IBInfo object as an integer.

Note: This method can be used for content-based routing only, typically in your implementation of the IRouter.OnRouteSend or IRouter.OnRouteReceive methods.

Parameters

None.

Returns

An integer representing the number of attributes for the IBInfo object.

Example

```
For &i = 1 To &MSG.IBInfo.GetNumberOfAttributes()
   &AttrName = &MSG.IBInfo.GetAttributeName(&i);
   &AttrValue = &MSG.IBInfo.GetAttributeValue(&i);
End-For;
```

Related Links

Content-Based Routing

GetAttributeName

GetAttributeValue

GetNumberOfContainerAttributes

Syntax

GetNumberOfContainerAttributes()

Description

Use this method to return the number of container attributes in the IBInfo object.

Parameters

None

Returns

An integer representing the number of container attributes.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

```
&MSG = CreateMessage(Operation.FLIGHTPLAN);

&ret = &MSG.IBInfo.AddContainerAttribute("MESSAGE_STATUS", "good");
&ret = &MSG.IBInfo.AddContainerAttribute("MyAttribute", "abcd");

/* When attempting to read these attributes within an IB event (OnNotify,  */
/* OnRequest etc.) one must first get a part rowset, this will load up the */
/* attributes into the message object from the xml. Here is an example of  */
/* how to read the attributes from a message.                               */

&RS = &MSG.GetPartRowset(1);
&index = &MSG.Ibinfo.GetNumberOfContainerAttributes();

For &i = 1 To &index

   &attrName = &MSG.Ibinfo.GetContainerAttributeName(&i);
   &attrValue = &MSG.Ibinfo.GetContainerAttributeValue(&i);

End-For;
```

Related Links

AddContainerAttribute

GetContainerAttributeName

GetContainerAttributeValue

GetTransactionIDforAE

Syntax

GetTransactionIDforAE()

Description

Use this method to get the transaction ID from within Application Engine program.

Parameters

None.

Returns

A number representing the transaction ID from within Application Engine program.

Related Links

AddAEAttribute

InsertAEResponseAttributes

Syntax

InsertAEResponseAttributes()

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use this method to save and transfer the Application Engine handler attributes to be read by the response application class.

Parameters

None.

Returns

A Boolean value: True if the save and insertion were successful, False otherwise.

Related Links

AddAEAttribute

LoadConnectorProp

Syntax

LoadConnectorProp(*ConnectorName*)

Description

Use the LoadConnectorProp method to load connector properties to the specified connector. The properties are contained in the message executing the method.

Note: Use this method in the message OnSend event.

Parameters

ConnectorName	Specify the name of the connector that you want to load properties for from the message.

Returns

A Boolean value: true if properties are loaded successfully, false otherwise.

Example

```
LOCAL MESSAGE &MSG;
&MSG = %IntBroker.GetMessage();
&Rowset = &MSG.GetRowset();
&MSG.IBInfo.LoadConnectorProp("HTTP TargetConnector");
/* add connector properties */
&MSG.IBInfo.ConnectorOverride= true;
ReturnToServer(&MSG);
```

Related Links

ConnectorOverride

"ReturnToServer" (PeopleTools 8.54: PeopleCode Language Reference)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

LoadConnectorPropFromNode

Syntax

LoadConnectorPropFromNode(*NodeName*)

Description

Use the LoadConnectorPropFromNode method to load connector properties into the message executing the method. Then you can use the LoadConnectorProp method to load the specified connector with the properties.

Note: Use this method in the message OnSend event.

Parameters

NodeName Specify the node that contains the connector properties you want to use. You can either specify the node name as a string, or prefix the node name with the reserved word **Node**.

Returns

A Boolean value: true if the properties are loaded successfully, false otherwise.

Related Links

ConnectorOverride

"ReturnToServer" (PeopleTools 8.54: PeopleCode Language Reference)

LoadConnectorPropFromRouting

Syntax

LoadConnectorPropFromRouting(*RoutingDefnName*)

Description

Use the LoadConnectorPropFromRouting method to load connector properties into the message executing the method. Then you can use the LoadConnectorProp method to load the specified connector with the properties.

Parameters

RoutingDefnName Specify the routing definition name that contains the connector properties you want to use, as a string.

Returns

A Boolean value: true if the method completes successfully, false otherwise.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

LoadConnectorProp
LoadConnectorPropFromNode

LoadConnectorPropFromTrx

Syntax

LoadConnectorPropFromTrx(*NodeName*, *TransactionType*, *MsgName*, *MsgVersion*)

Description

Note: This method is no longer supported.

LoadRESTHeaders

Syntax

LoadRESTHeaders()

Description

Use this method to load the headers defined on the appropriate routing for a REST-based service operation. Once loaded, the headers can be modified without specifying the connector override property.

Parameters

None.

Returns

A Boolean value: True if the method executed successfully, False otherwise.

Note: The connector override property does not need to be set when using LoadRESTHeaders.

Example

The following example demonstrates how you can modify HTTP headers through PeopleCode. In this example, the request on the subscribing node (the consumer) is modified.

Note: No HTTP properties are currently applicable for REST and will be removed by Integration Broker.

```
&request = CreateMessage(Operation.MAPS_GET);

&bRet = &request.IBInfo.LoadRESTHeaders();

/* Add any additional headers not defined on the routing */
&bRet = &request.IBInfo.IBConnectorInfo.AddConnectorProperties("Content-Language", ⇒
"eng", %HttpHeader);
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The following example demonstrates how you can add HTTP headers to a REST-based service operation response within an OnRequest event:

```
&response = CreateMessage(Operation.WEATHERSTATION_GET, %IntBroker_Response);

&bRet = &response.IBInfo.LoadRESTHeaders();

/* Add or modify additional headers not defined on the routing */
&bRet = &response.IBInfo.IBConnectorInfo.AddConnectorProperties("Content-Language",⇒
 "eng", %HttpHeader);

Return &response;
```

Related Links

ConnectorOverride

SetAttachmentProperty

Syntax

SetAttachmentProperty(*Content_ID*, *Property_Type*, *Value*)

Description

Use the SetAttachmentProperty to specify the value and type of a property associated with an attachment.

Parameters

Content_ID Specify the content ID associated with the attachment.

Property_Type Specify the type of property. See below for the valid values.

Value Specify the value associated with this property.

For the *Property_Type* parameter, the valid values are:

Constant Value	***Description***
%Attachment_Encoding	Specify the encoding type.
%Attachment_Type	Specify the attachment type.
%Attachment_URL	Specifies the URL for the attachment. The URL must be an absolute URL.
%Attachment_Base	Specify the attachment base.
%Attachment_Location	Specify an additional location for the attachment.
%Attachment_Disposition	Specifies the disposition of the attachment, whether it's displayed inline or as an attachment.
%Attachment_Description	Specifies the description of the attachment.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

A Boolean value: true if the property is set successfully, false otherwise.

Example

The following example shows sending an attachment with an asynchronous message:

```
Local Message &MSG;
Local Rowset &FLIGHT_PROFILE;
Local String &Attachment_Id;
Local Boolean &Test;
Local IntBroker &IntBroker;

QE_FLIGHTDATA.QE_ACNUMBER.Value = QE_FLIGHTDATA.QE_ACNUMBER + 1;

&FLIGHT_PROFILE = GetLevel0();

&MSG = CreateMessage(Operation.ASYNC_RR);

&Attachment_Id = &MSG.IBInfo. AddAttachment("C:\\temp\\MyFile.txt");
&Test = &MSG.IBInfo.SetAttachmentProperty(&Attachment_Id, %Attachment_Encoding, "UT⇒
F-8");
&Test = &MSG.IBInfo.SetAttachmentProperty(&Attachment_Id, %Attachment_Base, "Standa⇒
rd");
&Test = &MSG.IBInfo.SetAttachmentProperty(&Attachment_Id, %Attachment_Disposition, ⇒
"Pending");
&Test = &MSG.IBInfo.SetAttachmentProperty(&Attachment_Id, %Attachment_Language, "En⇒
glish");
&Test = &MSG.IBInfo.SetAttachmentProperty(&Attachment_Id, %Attachment_Description, ⇒
"Parts data");

&MSG.CopyRowset(&FLIGHT_PROFILE);

&IntBroker = %IntBroker

&IntBroker.Publish(&MSG);
```

Related Links

GetAttachmentProperty

IBInfo Class Properties

In this section, we discuss the IBInfo class properties. The properties are discussed in alphabetical order.

Important! Depending on the type of transaction and how it is executed by Integration Broker, certain properties may or may not be set on the IBInfo object. To determine which properties are available on the IBInfo object, check the Service Monitor first. If the information is not available there, it will not be available in the IBInfo object.

AppServerDomain

Description

This property can be used to set the application server domain for the connector, as a string.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

CompressionOverride

Description

This property can be used to set a compression override for the transaction. This property takes three system constants to set the compression override:

Constant Value	*Description*
%IntBroker_Compress	Turns compression on for this transaction.
%IntBroker_UnCompress	Turns compression off for this transaction.
%IntBroker_Compress_Reset	Resets compression to use the threshold specified by PSADMIN.

The integration engine compresses and base64-encodes messages destined for the PeopleSoft listening connector on its local integration gateway.

Asynchronous messages are always compressed and base64 encoded when sent to the integration gateway.

For synchronous messages, in PSADMIN you can set a threshold message size above which messages are compressed. With the CompressionOverride property, you can override the message compression setting specified in PSADMIN at the transaction level.

Warning! Turning compression off can negatively impact system performance when transporting synchronous messages greater than 1 MB. As a result, you should turn off compression only during integration development and testing.

Note: This property does not affect the compression of messages that the integration gateway sends using its target connectors.

This property is read-write.

Example

```
&MSG.IBInfo.CompressionOverride = %IntBroker_UnCompress;
```

ConnectorOverride

Description

This property specifies whether the connector override is specified for the transaction. This property takes a Boolean value: true, override the connector properties, false otherwise.

For REST-based service operations, the LoadRESTHeaders method can be used without the need to explicitly set this property.

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

LoadRESTHeaders

ConversationID

Description

This property returns the conversation ID associated with the request/response message transaction.

This property is read-write.

DeliveryMode

Description

This property sets or returns the delivery mode override for the connector as an integer. This property takes one of three system constants to set the delivery mode override:

Constant Value	*Description*
%IB_DM_BestEffort	Sets the delivery mode to best effort. If the delivery mode is set to best effort, then only one attempt is made to send the message to the destination; there is no attempt to retry the message.
%IB_DM_Guarantee	Sets the delivery mode to guaranteed. This mode automatically invokes retry logic to ensure that the message is successfully sent to a destination. This is the default delivery mode.
%IB_DM_Reset	Resets the delivery mode to the value defined outside the PeopleCode program.

This property is read-write.

Example

```
&int = &MSG.IBInfo.DeliveryMode = %IB_DM_BestEffort;
```

DestinationNode

Description

This property returns the name of the destination node that the request was sent to, as a string.

This property is read-only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ExternalMessageID

Description

This property returns the external ID of the message. This property is used in testing, and to resolve duplicate message issues from third-party systems.

This property is read-only.

Example

```
&str = &MSG.IBInfo.ExternalMessageID;
```

ExternalOperationName

Description

This property returns the external operation name of the message. This property is used in testing, and to resolve duplicate message issues from third-party systems.

This property is read-write.

ExternalUserName

Description

This property returns the external user name associated with the message. This property is used in testing, and to resolve duplicate message issues from third-party systems.

This property is read-write.

ExternalUserPassword

Description

This property returns the external user password associated with the message. This property is used in testing, and to resolve duplicate message issues from third-party systems.

This property is read-write.

FinalDestinationNode

Description

When the message is passed across several nodes, this property specifies the ultimate target of the message, as a string.

This property is read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

FuturePublicationDateTime

Description

Use this property to specify when, as a DateTime value, an actual publish of the transaction is to occur.

This property is for use with asynchronous transactions. If a null value or an invalid future date and time is specified, the publish will occur immediately.

This property is read-write.

HTTPSessionId

Description

Use the HTTPSessionId property to specify the HTTP session ID, as a string.

This property is read-write.

IBConnectorInfo

Description

This property returns a reference to a IBConnectorInfo collection object.

This property is read-only.

InReplyToID

Description

Use the InReplyToID property to specify the reply to ID contained in the message.

This property is read-write.

MessageChannel

Description

This property references the name of the channel associated with the message definition, as a string.

Note: This property has been deprecated and remains for backward compatibility only. Use the IBInfo class MessageQueue property instead.

This property is set in when the message is created.

This property is read-only.

Related Links

MessageQueue

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

ChannelName

MessageName

Description

This property returns the name of the message, as a string.

This property is read-only.

Related Links

Name

MessageQueue

Description

This property returns the name of the queue associated with the message, as a string.

This property is read-only.

MessageType

Description

This property returns the type of the message, as a string.

Note: This property has been deprecated and remains for backward compatibility only. Use the IBInfo class OperationType property instead.

See OperationType.

Valid types are:

Value	*Description*
Sync	Indicates that the message is synchronous.
Async	Indicates that the message is asynchronous.
Ping	Indicates that the message is used to test the application server to make sure it is available and accepting requests.

This property is read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

MessageVersion

Description

This property returns the message version as a number.

This property is read-only.

NodeDN

Description

For incoming requests, this property gives the distinguished name (DN) extracted from the certificate authentication process, as a string.

This property is read-write.

NonRepudiationID

Description

This property returns the non-repudiation ID as a string. This property is populated with a unique string when the message is published.

This property is only valid with messages that use non-repudiation.

This property is read-only.

Related Links

"Implementing Nonrepudiation" (PeopleTools 8.54: Integration Broker Administration)

NumberOfAttachments

Description

This property returns the number of attachments associated with a message.

This property is read-only.

Related Links

AddAttachment

OperationType

Description

This property returns the type of the operation, as a string.

This property is read-only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

OperationVersion

Description

This property returns the version of the operation, as a string.

This property is read-only.

OrigNode

Description

For requests that cross multiple nodes, this property identifies the node that initiated the request as a string.

The OrigNode property returns the originating node of the message. If the message is not going across nodes, the OrigNode and SoureNode properties return the same value. However, if the message is going across nodes, the source node is the node that most recently published the message.

For example, if A publishes to B, then B publishes the message to C, from C's perspective, A is the original node and B is the source node.

This property is read-only.

Related Links

SourceNode

OrigProcess

Description

This property returns the name of the process where the publish originated, as a string. For example, a message published from the Inventory definitions page would have a process name of INVENTORY DEFIN.

This property is read-only.

OrigTimeStamp

Description

This property returns the time stamp that corresponds to the time that the request was created, as a string. For requests that cross nodes, this is the time that the first request was created.

This property is read-only.

OrigUser

Description

This property returns the user ID login where the message was initially generated, as a string.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-only.

PublicationID

Description

This property returns the unique identifier for the message, as a string.

Note: This property has been deprecated. It is no longer supported.

RequestingNodeName

Description

This property returns the name of the node making the request, as a string.

This property is read-write.

RequestingNodeDescription

Description

This property returns the description of the node making the request, as a string.

This property is read-write.

ResponseAsAttachment

Description

Use the ResponseAsAttachment property to specify whether the response should be returned as an attachment or inline.

This property is read-write.

SegmentsUnOrder

Description

The SegmentUnOrder property is only applicable for asynchronous messages. If you specify the SegmentUnOrder property as true, the receiving node processes the segments in parallel.

This property is read-write.

Related Links

SegmentsByDatabase

Message Segments

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SourceNode

Description

This property returns the name of the publishing node as a string.

The OrigNode property returns the originating node of the message. If the message is not going across nodes, the OrigNode and SoureNode properties return the same value. However, if the message is going across nodes, the source node is the node that most recently published the message.

For example, if A publishes to B, then B publishes the message to C, from C's perspective, A is the original node and B is the source node.

This property is read-only.

Related Links

OrigNode

SyncServiceTimeout

Description

This property takes a time (in seconds). This time overrides the default HTTP timeout that is used for all requests. If you set this property, you can use this to read back the time, that is, set the time before the SyncRequest is executed, then see when it is changed in an implementation of the OnSend method.

Note: This property is only for synchronous requests.

Generally, you use SyncServiceTimeout to dynamically set the timeout value for a specific transaction. The http header file is modified to take this new parameter. In addition this value is sent to the gateway to be used for the http timeout. Use this so that a long running transaction will not timeout. In addition, you don't have to wait through the default period for a specific transaction to timeout.

The following is a typical example of using this property:

```
&MSG.SetXmlDoc(&xmlReq);
&MSG.IBInfo.LoadConnectorPropFromNode(Node.EAI)
&MSG.IBInfo.SyncServiceTimeout = 360000;
&MSG.IBInfo.ConnectorOverride = true;
&MSG_Resp = SyncRequest(&MSG, Node.EAI);
&xmlResponseDoc = &MSG.GetXmlDoc();
```

Setting the XML directly is not valid. You need to use the message object to set the value. In order for this to work you must override the connector properties, which means you must set up the connector properties for this transaction, using one of the load methods (such as LoadConnectorPropFromNode, LoadConnectorPropFromTrx, and so on.)

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

TransactionID

Description

This property returns the transaction ID as a string. This is used to uniquely identify a request.

This property is read-only.

UserName

Description

This property returns the user name associated with the message, as a string.

This property is read-only.

VisitedNodes

Description

This property returns an array of string containing the names of all the nodes visited by the message. This is useful when a message is being propagated across multiple nodes.

This property is read-only.

WSA_Action

Description

Use this property to specify the Web Services Addressing (WS-Addressing) action for the message. The WS-Addressing action is defined as a string.

This property is read-write.

WSA_FaultTo

Description

Use this property to specify the WS-Addressing fault end point for the message. The WS-Addressing fault end point is defined as a string.

If this property is not null, a message ID (the WSA_MessageID property) must also be defined.

This property is read-write.

WSA_MessageID

Description

Use this property to specify the WS-Addressing message ID for the message. The WS-Addressing message ID is defined as a string.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-write.

WSA_ReplyTo

Description

Use this property to specify the WS-Addressing reply-to address for the message. The WS-Addressing reply-to address is defined as a string.

This property is read-write.

WSA_To

Description

Use this property to specify the WS-Addressing destination for the message. The WS-Addressing destination is defined as a string.

This property is read-write.

IBConnectorInfo Collection

A IBConnectorInfo collection object is returned from the IBConnectorInfo IBInfo class property.

Related Links

IBConnectorInfo

IBConnectorInfo Collection Methods

In this section, we discuss the IBConnectorInfo collection methods. The methods are discussed in alphabetical order.

AddConnectorProperties

Syntax

AddConnectorProperties(*Name*, *Value*, *Type*)

Description

Use the AddConnectorProperties method to add a set of connector properties to a connector.

Parameters

Name Specify the name of the property as a string.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Value Specify the value of the property as a string.

Type Specify the type of the property as a string. The valid values are:

Constant Value	***Description***
%Property	Add a property type property.
%Header	Add a header type property.

Returns

A Boolean value: true if the connector properties are added successfully, false otherwise.

Example

The following are examples of typical name/value pairs.

```
&b1 = &MSG.IBInfo.IBConnectorInfo.AddConnectorProperties("URL", "http://finance.yah⇒
oo.com/d/quotes.txt/?symbols=PSFT&format=l1c1d1t1", %Property);

&b2 = &MSG.IBInfo.IBConnectorInfo.AddConnectorProperties("sendUncompressed", "Y", %⇒
Header);

&b3 = &MSG.IBInfo.IBConnectorInfo.AddConnectorProperties("FilePath", "C:\Temp", %Pr⇒
operty);
```

The following example demonstrates setting a passive connection for the FTP target connector:

```
&b4 = &MSG.IBInfo.IBConnectorInfo.AddConnectorProperties ("FTPMODE", "PASSIVE", %Pr⇒
operty);
```

Related Links

DeleteConnectorProperties
ClearConnectorProperties

AddQueryStringArg

Syntax

AddQueryStringArg(*Name*, *Value*)

Description

Use the AddQueryStringArg method to add query string arguments to the outbound request. The query string arguments are used by the HTTP connector to step parameters in the URL.

Parameters

Name Specify the name of the query string argument as a string.

Value Specify the value for the query string argument as a string.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

A Boolean value: true if the query string argument is added successfully, false otherwise.

Related Links

ClearQueryStringArgs
DeleteQueryStringArg
GetNumberOfQueryStringArgs
GetQueryStringArgName
GetQueryStringArgValue

ClearConnectorProperties

Syntax

```
ClearConnectorProperties()
```

Description

Use the ClearConnectorProperties method to clear all the properties in a connector before setting them.

Parameters

None.

Returns

None.

Related Links

AddConnectorProperties
DeleteConnectorProperties

ClearQueryStringArgs

Syntax

```
ClearQueryStringArgs()
```

Description

Use the ClearQueryStringArgs method to clear all of the existing query string arguments.

Use the DeleteQueryStringArg method if you want to remove a specific query string argument.

Parameters

None.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

None.

Related Links

DeleteQueryStringArg

DeleteConnectorProperties

Syntax

DeleteConectorProperties(*Name*)

Description

Use the DeleteConnectorProperties to delete a specific connector property.

Use the ClearConnectorProperties method to remove all the properties.

Parameters

Name	Specify the name of the connector property you want to delete.

Returns

A Boolean value: true if the property is deleted successfully, false otherwise.

Related Links

ClearConnectorProperties

DeleteQueryStringArg

Syntax

DeleteQueryStringArg(*Name*)

Description

Use the DeleteQueryStringArg method to delete a specific query string argument.

Use the ClearQueryStringArg method to delete all of the query string arguments.

Parameters

Name	Specify the name of the query string argument that you want to delete.

Returns

A Boolean value: true if the query string argument is deleted successfully, false otherwise.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

ClearQueryStringArgs

GetConnectorPropertiesName

Syntax

GetConnectorPropertiesName(*Index*)

Description

Use the GetConnectorPropertiesName to return the name of the connector property in the numeric position specified by *Index*.

Parameters

Index	Specify the numeric position of the connector property name that you want to access.

Returns

A string containing the name of a connector property.

Example

```
For &I = 1 to &Msg.IBInfo.IBConnectorInfo.GetNumberOfConnectorProperties();
  &PropName = &Msg.IBInfo.IBConnectorInfo.GetConnectorPropertiesName(&I)
  /* do processing */
End-For;
```

GetConnectorPropertiesType

Syntax

GetConnectorPropertiesType(*Index*)

Description

Use the GetConnectorPropertiesType method to return the type of the connector property specified by its numeric position by *Index*.

Parameters

Index	Specify the numeric position of the connector property type that you want to access.

Returns

A string containing the type of the specified connector.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GetConnectorPropertiesValue

Syntax

GetConnectorPropertiesValue(*Index*)

Description

Use the GetConnectorPropertiesValue method to return the value of the connector property specified by its numeric position by *Index*.

Parameters

Index	Specify the numeric position of the connector property type that you want to access.

Returns

A string containing the value of the specified connector.

GetNumberOfConnectorProperties

Syntax

GetNumberOfConnectorProperties()

Description

Use the GetNumberOfConnectorProperties method to determine the number of connector properties.

Parameters

None.

Returns

A number.

GetNumberOfQueryStringArgs

Syntax

GetNumberOfQueryStringArgs()

Description

Use the GetNumberOfQueryStringArgs method to determine the number of query string arguments.

Parameters

None.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

A number.

GetQueryStringArgName

Syntax

GetQueryStringArgName(*Index*)

Description

Use the GetQueryStringArgName method to access the name of the query string argument by its numeric position as specified by *Index*.

Parameters

Index	Specify the numeric position of the query string argument name that you want to access.

Returns

A string containing the name of a query string argument.

GetQueryStringArgValue

Syntax

GetQueryStringArgValue(*Index*)

Description

Use the GetQueryStringArgValue method to access the value of the query string argument by its numeric posistion as specified by *Index*.

Parameters

Index	Specify the numeric position of the query string argument value that you want to access.

Returns

A string containing the value of a query string argument.

IBConnectorInfo Collection Properties

In this section, we discuss the IBConnectorInfo collection properties. The properties are discussed in alphabetical order.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ConnectorClassName

Description

Use this property to identify the name of the target connector to invoke as a string.

This property is read-write.

ConnectorName

Description

Use this property to identify the target connector to invoke to send to the message, as a string.

This property is read-write.

Cookies

Description

Use this property to access the cookies associated with a message.

You can accept a synchronous response message containing cookies, save those cookies in a global variable, and later return them to the target node in an outbound synchronous or asynchronous request message.

You can access this property only in an inbound synchronous response message or an outbound request message.

This property is read-write.

Example

The following example retains the cookies from a response message to a global variable:

```
Local Message &SalesRequest, &SalesResponse;
Local Rowset &SALES_ORDER;
Global string &SalesCookies;

&SALES_ORDER = GetLevel0();
&SalesRequest = CreateMessage(OPERATION.SALES_ORDER_SYNC);
&SalesRequest.CopyRowsetDelta(&SALES_ORDER);

/* Send the synchronous request; the return value is the response
message object */
&SalesResponse = &SalesRequest.SyncRequest();

/* Retrieve cookies from the response message */
&SalesCookies = &SalesResponse.IBInfo.IBConnectorInfo.Cookies;
```

The following example retrieves the previously retained cookies from the global variable and inserts them into a new request message:

```
Local Message &SalesRequest, &SalesResponse;
Local Rowset &SALES_ORDER;
Global string &SalesCookies;

&SALES_ORDER = GetLevel0();
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
&SalesRequest = CreateMessage(Message.SALES_ORDER_SYNC);
&SalesRequest.CopyRowsetDelta(&SALES_ORDER);

/* Insert the cookies in the request message */
&SalesRequest.IBInfo.IBConnectorInfo.Cookies = &SalesCookies;

/* Send the asynchronous request */
%IntBroker.Publish(&SalesRequest);
```

PathInfo

Description

This property is specific to incoming HTTP requests. This is the path information extracted from the request, represented as a string.

This property is read-write.

RemoteFrameworkURL

Description

Use this property to identify the URL to which to send a message, as a string. This value overrides the server URL specified in the Project Definitions section.

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Chapter 29

Mobile Application Platform (MAP) Classes

Understanding Mobile Application Platform Classes

Implement your own custom application classes to initialize, add business logic, and dynamically change layouts for your Mobile Application Platform (MAP) applications.

The Mobile Application Platform framework completely separates the business logic from the presentation layer. All Mobile Application Platform metadata is available in your application class PeopleCode and is not tied to application pages or other metadata, allowing you to override the defaults defined on the actual layout. This means that you have complete control of the presentation layer for any transaction within the application class PeopleCode.

To manipulate pages, elements, and other aspects of your applications through PeopleCode, import the PS_PT:Integration:IDocLayoutHandler interface class and implement its two abstract methods. See "Examples: Mobile Application Platform PeopleCode " (PeopleTools 8.54: Mobile Application Platform) for an example.

Three built-in classes are delivered for the Mobile Application Platform framework. Additional operations can be performed by importing and using selected methods from the PT_MAP_ADMIN:MapFluid application class:

Map class	A Map object represents the MAP application (or layout); it is the highest level object in a MAP application. From the Map object, you can get the Document object (which defines the data structure for the MAP application), the URI document object, MapPage objects, and MapElement objects. See Map Class Methods and Map Class Properties.
MapPage class	Each page in a MAP application is represented as a MapPage object which can be retrieved from a Map object. See MapPage Class Methods and MapPage Class Properties.
MapElement class	Each element on a page is represented as a MapElement object. A MapElement object can be retrieved from a Map object or from MapPage object. See MapElement Class Methods and MapElement Class Properties.
PT_MAP_ADMIN:MapFluid	Import and use selected methods from the PT_MAP_ADMIN:MapFluid application class to perform certain operations on the fluid page header. See MapFluid Class Methods.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

In addition, the IntBroker class includes several methods to support the Mobile Application Platform framework.

Related Links

IntBroker Class Methods

Map Class Methods

In this section, the Map class methods are presented in alphabetical order.

AddMetaTag

Syntax

AddMetaTag(*name, value*)

Description

Use this method to add an HTML <meta> tag to the HTML document.

Parameters

name	Specifies the name of the <meta> tag as a String.
value	Specifies the value of the <meta> tag as a String.

Returns

A Boolean value: True if the method executes successfully, False otherwise.

Example

The following example adds an HTML <meta> tag:

```
&bret = &Map.AddMetaTag("apple-mobile-web-app-capable", "yes");
```

The resulting HTML code would include the tag as follows:

```
<meta apple-mobile-web-app-capable="yes">
```

Related Links

DeleteMetaTag
GetMetaTagName
GetNumberOfMetaTags

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

DeleteMetaTag

Syntax

DeleteMetaTag(*name*)

Description

Use this method to delete an HTML <meta> tag from the HTML document.

Parameters

name Specifies the name of the <meta> tag as a String.

Returns

A Boolean value: True if the method executes successfully, False otherwise.

Related Links

AddMetaTag
GetMetaTagName
GetNumberOfMetaTags

GetAJAXName

Syntax

GetAJAXName(*index*)

Description

Use this method to return the name of an AJAX parameter that has been parsed by the MAP framework.

Parameters

index Specifies which AJAX parameter as a Integer.

Returns

A String value.

Related Links

GetAJAXValue
GetAJAXValueByName
GetNumberofAJAXParms
"Defining Ajax Event Page Element Properties" (PeopleTools 8.54: Mobile Application Platform)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GetAJAXNonSerializedData

Syntax

GetAJAXNonSerializedData()

Description

Use this method to return the input to an AJAX event as non-serialized data (that is, as a data blob).

Parameters

None.

Returns

A String value.

Related Links

"Defining Ajax Event Page Element Properties" (PeopleTools 8.54: Mobile Application Platform)

GetAJAXValue

Syntax

GetAJAXValue(*index*)

Description

Use this method to return the value of an AJAX parameter that has been parsed by the MAP framework.

Parameters

index	Specifies which AJAX parameter as an Integer.

Returns

A String value.

Related Links

GetAJAXName
GetAJAXValueByName
GetNumberofAJAXParms
"Defining Ajax Event Page Element Properties" (PeopleTools 8.54: Mobile Application Platform)

GetAJAXValueByName

Syntax

GetAJAXValueByName(*name*)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use this method to return the value of an AJAX parameter that has been parsed by the MAP framework.

Parameters

name Specifies the name of the AJAX parameter as a String.

Returns

A String value.

Example

```
&A_Value = &Map.GetAJAXValueByName("SearchGroupName");
```

Related Links

GetAJAXName
GetAJAXValue
GetNumberofAJAXParms
"Defining Ajax Event Page Element Properties" (PeopleTools 8.54: Mobile Application Platform)

GetAuthToken

Syntax

GetAuthToken()

Description

Use this method to get the authentication token for the user signed into this MAP application.

Parameters

None.

Returns

A String value.

Related Links

GetAuthTokenDomain

GetAuthTokenDomain

Syntax

GetAuthTokenDomain()

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the GetAuthTokenDomain method to return as String value representing the authentication domain for the active web profile as defined on the Web Profile Configuration page.

Parameters

None.

Returns

A String value.

Example

```
&domain = &Map.GetAuthTokenDomain();
```

Related Links

GetAuthToken

"Configuring General Portal Properties" (PeopleTools 8.54: Portal Technology)

GetCSS

Syntax

```
GetCSS()
```

Description

Use this method to return the in-line CSS that has been set for the MAP layout.

Parameters

None.

Returns

A String value.

Related Links

SetCSS

GetDocument

Syntax

```
GetDocument()
```

Description

Use this method to return the Document object associated with this MAP layout.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

None.

Returns

A Document object.

Related Links

Document Class
"Adding Layout Definitions" (PeopleTools 8.54: Mobile Application Platform)

GetElement

Syntax

GetElement(*element_ID*)

Description

Use this method to return a MapElement object from this MAP layout.

Parameters

element_ID Specifies the element ID as a String.

Note: The *element_ID* must be valid for this MAP layout.

Returns

A MapElement object.

Example

In the following example, the label text for the back button in the application is set to the value of the PSBackLabel property:

```
&Map.GetElement("map_back_button").LabelText = &Map.PSBackLabel;
```

Related Links

MapElement Class Methods
MapElement Class Properties

GetJavaScript

Syntax

GetJavaScript()

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use this method to return the in-line JavaScript that has been set for the MAP layout.

Parameters

None.

Returns

A String value.

Related Links

SetJavaScript

GetMetaTagName

Syntax

GetMetaTagName(*index*)

Description

Use this method to get the name of an HTML <meta> tag.

Parameters

index	Specifies which <meta> tag as an Integer.

Returns

A String value.

Related Links

AddMetaTag
DeleteMetaTag
GetNumberOfMetaTags

GetNumberofAJAXParms

Syntax

GetNumberofAJAXParms()

Description

Use this method to return the number of parsed AJAX parameters.

Parameters

None.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

An Integer value.

Example

The following example loops through the parsed AJAX parameters:

```
For &i = 1 To &Map.GetNumberofAJAXParms()
   &A_Name = &Map.GetAJAXName(&i);
   &A_Value = &Map.GetAJAXValue(&i);
   ...
End-For;
```

Related Links

GetAJAXName
GetAJAXValue
GetAJAXValueByName
"Defining Ajax Event Page Element Properties" (PeopleTools 8.54: Mobile Application Platform)

GetNumberOfMetaTags

Syntax

GetNumberOfMetaTags()

Description

Use this method to return the number of HTML <meta> tags in the HTML document.

Parameters

None.

Returns

An Integer value.

Related Links

AddMetaTag
DeleteMetaTag
GetMetaTagName

GetPage

Syntax

GetPage(*page_number*)

Description

Use this method to return one of the MapPage objects associated with this MAP layout.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

page_number	Specifies the which MapPage as an Integer.

Returns

A MapPage object.

Example

The following example gets the first page of the MAP application:

```
&Page = &Map.GetPage(1);
```

Related Links

MapPage Class Methods
MapPage Class Properties

GetPortaName

Syntax

GetPortaName()

Description

Use the GetPortaName method to return the name of the current portal as a String value.

Parameters

None.

Returns

A String value.

Example

```
&PortalName = &Map.GetPortaName();
```

Related Links

GetPortaName

GetPortalNodeName

Syntax

GetPortalNodeName()

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the GetPortalNodeName method to return the name of the node from the current portal as a String value. If the portal host node name cannot be determined for the current portal, then the default local node name for the current system is returned.

Parameters

None.

Returns

A String value.

Example

Within a MAP application, you could use an invocation similar to the following to generate a URL for an absolute reference to a PeopleSoft component:

```
&URL = GenerateComponentPortalURL(&Map.GetPortaName(), &Map.GetPortalNodeName(), Me⇒
nuName.PORTAL_ADMIN, %MAP_Market, Component.PTSF_GBLSRCH_FLUID, Page.PTS_NUI_GBLSRC⇒
H, "U");
```

Related Links

GetPortalNodeName

GetURIDocument

Syntax

GetURIDocument()

Description

Use this method to return the URI document associated with the MAP layout.

Parameters

None.

Returns

A Document object.

Related Links

"Defining Layout Initialization Parameters and Values" (PeopleTools 8.54: Mobile Application Platform)

LoadState

Syntax

LoadState(*state_ID*)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use this method to re-load the Document object based on the state ID generated by the MAP framework.

The MAP framework automatically generates and saves the state ID for a layout when the “Retain State” check box has been selected in the Layout Details group box of the Layout page.

Parameters

state_ID	Specifies the automatically generated state ID as a String.

Returns

A Boolean value: True if the method executes successfully, False otherwise.

Related Links

StateExists
StateEnabled
StateID
StateLoaded
"Viewing and Defining Metadata and Details " (PeopleTools 8.54: Mobile Application Platform)

SetCSS

Syntax

SetCSS(*CSS_data*)

Description

Use this method to set in-line CSS data for this MAP layout.

Parameters

CSS_data	Specifies the in-line CSS as a String.

Returns

A Boolean value: True if the method executes successfully, False otherwise.

Related Links

GetCSS

SetJavaScript

Syntax

SetJavaScript(*JS_code*)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use this method to set in-line JavaScript for this MAP layout.

Parameters

JS_code	Specifies the in-line JavaScript as a String.

Returns

A Boolean value: True if the method executes successfully, False otherwise.

Related Links

GetJavaScript

SetOvrdAJAXDocument

Syntax

SetOvrdAJAXDocument(*&doc*)

Description

Use this method to specify an override Document object to be the non-serialized output for an AJAX event.

Parameters

&doc	Specifies the override as a Document object.

Returns

A Boolean value: True if the method executes successfully, False otherwise.

Example

```
&bSuccess = &Map.SetOvrdAJAXDocument(&responseDoc);
```

Related Links

"Defining Ajax Event Page Element Properties" (PeopleTools 8.54: Mobile Application Platform)

StateExists

Syntax

StateExists(*state_ID*)

Description

Use this method to determine whether the specified state ID exists for this MAP application.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The MAP framework automatically generates and saves the state ID for a layout when the “Retain State” check box has been selected in the Layout Details group box of the Layout page.

Parameters

state_ID	Specifies the state ID as a String.

Returns

A Boolean value: True if the method executes successfully, False otherwise.

Related Links

LoadState
StateEnabled
StateID
StateLoaded
"Viewing and Defining Metadata and Details " (PeopleTools 8.54: Mobile Application Platform)

ValidateSessionID

Syntax

ValidateSessionID(*session_ID*)

Description

Use this method to validate a session ID, which has been passed into the MAP framework from the client using a name/value pair. Use this method with events when the MAP framework does not perform input serialization—for example, with AJAX events. The method can be used to prevent cross-site request forgery attacks.

Parameters

session_ID	Specifies the session ID as a String.

Returns

A Boolean value: True if the method executes successfully, False otherwise.

Example

```
&b_ret = &Map.ValidateSessionID("Z9X16v2zja37ZUSTEwmp3PejmU");
```

Map Class Properties

In this section, the Map class properties are presented in alphabetical order.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

BrowserDeviceType

Description

Use this property to return a String representing browser device type in use by the user signed onto the MAP application.

The values can be one of the following constants:

- %MAP_Desktop
- %MAP_Phone
- %MAP_Tablet

This property is read-only.

Example

```
If &Map.BrowserDeviceType = %MAP_Phone Then
   ...
```

BrowserPlatform

Description

Use this property to return a String representing browser platform (operating system) in use by the user signed onto the MAP application.

This property is read-only.

LayoutName

Description

Use this property to return a String representing the name of the MAP layout.

This property is read-only.

PSBackLabel

Description

Use this property to set or return a String representing the label to be used on the back button for returning to the calling PeopleSoft application.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

In the following example, the label text for the back button in the application is set to the value of the PSBackLabel property:

```
&Map.GetElement("map_back_button").LabelText = &Map.PSBackLabel;
```

Related Links

PSBackOrigin
PSBackURL

PSBackOrigin

Description

Use this property to return a String representing the type of PeopleSoft application that called the current MAP application.

The values can be one of the following constants:

- %MAP_Back_MAP
- %MAP_Back_PIA

This property is read-only.

Related Links

PSBackLabel
PSBackURL

PSBackURL

Description

Use this property return a String representing the URL to return to the PeopleSoft application that called the current MAP application.

This property is read-only.

Related Links

PSBackLabel
PSBackOrigin

RequestNodeFromToken

Description

Use this property to return a String specifying the PeopleSoft node for the authentication token.

This property is read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

StateEnabled

Description

Use this property to return a Boolean indicating whether state is being maintained for this MAP application.

The MAP framework automatically generates and saves the state ID for a layout when the “Retain State” check box has been selected in the Layout Details group box of the Layout page.

This property is read-only.

Related Links

LoadState
StateExists
StateID
StateLoaded
"Viewing and Defining Metadata and Details " (PeopleTools 8.54: Mobile Application Platform)

StateID

Description

Use this property to set or return a String representing the current state ID for the MAP application.

The MAP framework automatically generates and saves the state ID for a layout when the “Retain State” check box has been selected in the Layout Details group box of the Layout page.

The state can also be specified as the %MAP_State_No_Update constant, which indicates that the state will not be updated for this event.

This property is read-write.

Related Links

LoadState
StateExists
StateEnabled
StateLoaded
"Viewing and Defining Metadata and Details " (PeopleTools 8.54: Mobile Application Platform)

StateLoaded

Description

Use this property to return a Boolean value indicating whether the state has been retrieved and loaded.

This property is read-only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

LoadState
StateExists
StateEnabled
StateID
"Viewing and Defining Metadata and Details " (PeopleTools 8.54: Mobile Application Platform)

SystemStatus

Description

Use this property to set or return an Integer representing the status of the MAP application.

The values can be one of the following constants:

- %MAP_Development
- %MAP_Production

This property is read-write.

Title

Description

Use this property to set or return a String representing title for the MAP application to be displayed in the browser's title bar. The default is the name of the MAP layout.

This property is read-write.

Related Links

LayoutName

URIResourceIndex

Description

Use this property to return an Integer representing which set of initialization parameters were used to invoke the MAP application.

This property is read-only.

Related Links

"Using the Initialization Page for Defining Layout Initialization Parameters and Values" (PeopleTools 8.54: Mobile Application Platform)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Validation

Description

Use this property to set or return an Integer representing the type of form validation to be performed for this MAP application.

The values can be one of the following constants:

- %MAP_Validate
- %MAP_No_Validate
- %MAP_Validate_Custom

This property is read-write.

Related Links

"Viewing and Defining Metadata and Details " (PeopleTools 8.54: Mobile Application Platform)

MapPage Class Methods

In this section, the MapPage class methods are presented in alphabetical order.

GetElement

Syntax

GetElement(*element_ID*)

Description

Use this method to return a MapElement object from this MAP page.

Parameters

element_ID Specifies the element ID as a String.

Note: The *element_ID* must be valid for the MAP layout that includes this MAP page.

Returns

A MapElement object.

Example

In the following example, the label text for a page heading element is set:

```
&ElementHeader = &Page.GetElement("mapheader_6");
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
&ElementHeader.LabelText = "Maintenance Data - Updated";
```

Related Links

MapElement Class Methods
MapElement Class Properties

MapPage Class Properties

In this section, the MapPage class properties are presented in alphabetical order.

Note: Many of these MapPage properties correspond to fields found on the Page Details page.

Related Links

"Using the Page Details Page" (PeopleTools 8.54: Mobile Application Platform)

BackButtonTheme

Description

Use this property to set or return a String representing the jQuery Mobile swatch assigned to the back button for this page.

Specify the value as one of the following constants:

Constant Value	*Swatch Description*	*Color (in the Default Theme)*
%MAP_Theme_a	Highest level of visual priority.	Black
%MAP_Theme_b	Secondary level of visual priority.	Blue
%MAP_Theme_c	Baseline level (default swatch).	Gray
%MAP_Theme_d	Alternate secondary level.	Gray
%MAP_Theme_e	Accent swatch.	Yellow

For more information on the default JQuery Mobile theme and its color swatches, see “Themes” in "Understanding Layout Template Container Terms and Concepts" (PeopleTools 8.54: Mobile Application Platform).

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Cache

Description

Use this property to set or return a Boolean value indicating whether caching has been enabled for this page. MAP pages are cached in the Document Object Model (DOM) using the jQuery framework instead of using the browser's cache.

This property is read-write.

ContentClassName

Description

Use this property to set or return a String specifying the class name to apply to the content container for this page.

If a layout template has been applied to the page, the default value of this property is the class defined for the template's content container, if one is defined.

This property is read-write.

ContentStyle

Description

Use this property to set or return a String specifying the styles to apply to the content container of the page. Specify styles in CSS3 format.

If a layout template has been applied to the page, the default value of this property are the styles defined for the template's content container, if one is defined.

This property is read-write.

Example

The following example specifies the styles to apply to the page content using CSS3 format:

```
&Page.ContentStyle = "margin-left:0px; padding-left:0px;";
```

ContentTheme

Description

Use this property to set or return a String representing the jQuery Mobile swatch assigned to the content container for this page.

Specify the value as one of the following constants:

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Constant Value	*Swatch Description*	*Color (in the Default Theme)*
%MAP_Theme_a	Highest level of visual priority.	Black
%MAP_Theme_b	Secondary level of visual priority.	Blue
%MAP_Theme_c	Baseline level (default swatch).	Gray
%MAP_Theme_d	Alternate secondary level.	Gray
%MAP_Theme_e	Accent swatch.	Yellow

For more information on the default JQuery Mobile theme and its color swatches, see “Themes” in "Understanding Layout Template Container Terms and Concepts" (PeopleTools 8.54: Mobile Application Platform).

This property is read-write.

Example

The following example sets the swatch for the page’s content container:

```
&Page.ContentTheme = %MAP_Theme_a;
```

FormTransition

Description

Use this property to set or return an Integer specifying the form transition for this page. A form transition occurs if a form control (such as a Save button) is defined for the page and the control is activated.

Specify the value as one of the following constants:

Constant Value	*Description*
%MAP_Fade	Fade the page or dialog in over the previous content.
%MAP_Flip	An animated page flip, rotating the current view out with the other view on the reverse side.
%MAP_Pop	The page springs into view from the center of the screen.
%MAP_Slide	Slide in from the left or right, pushing the previous content out of the way.
%MAP_SlideDown	Slide down from the top, over the top of the current container.
%MAP_SlideUp	Slide up to the top, revealing the next content below.
%MAP_Turn	The page turns as in turning a page in a book.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Constant Value	*Description*
%MAP_Flow	Throws the current page away and comes in with the next page.
%MAP_SlideFade	Slide in from the left or right then fade the page.

This property is read-write.

Related Links

Transition

ID

Description

Use this property return a String representing the page ID for this MAP page.

This property is read-only.

IsExternalPage

Description

Use this property to return a Boolean value indicating whether the page has been defined as an external page.

Note: You can define any page in a MAP layout an external page except for the first page of the layout.

This property is read-only.

MainClassName

Description

Use this property to set or return a String specifying the class name to apply to the main container for this page.

If a layout template has been applied to the page, the default value of this property is the class defined for the template's main container.

This property is read-write.

MainStyle

Description

Use this property to set or return a String specifying the styles to apply to the main container of the page. Specify styles in CSS3 format.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

If a layout template has been applied to the page, the default value of this property are the styles defined for the template's main container.

This property is read-write.

Example

The following example specifies the styles to apply to the page content using CSS3 format:

```
&Page.MainStyle = "margin-left:0px; padding-left:0px;";
```

MainTheme

Description

Use this property to set or return a String representing the jQuery Mobile swatch assigned to the main container for this page.

Specify the value as one of the following constants:

Constant Value	*Swatch Description*	*Color (in the Default Theme)*
%MAP_Theme_a	Highest level of visual priority.	Black
%MAP_Theme_b	Secondary level of visual priority.	Blue
%MAP_Theme_c	Baseline level (default swatch).	Gray
%MAP_Theme_d	Alternate secondary level.	Gray
%MAP_Theme_e	Accent swatch.	Yellow

For more information on the default JQuery Mobile theme and its color swatches, see "Themes" in "Understanding Layout Template Container Terms and Concepts" (PeopleTools 8.54: Mobile Application Platform).

This property is read-write.

Name

Description

Use this property to set or return a String specifying the name to display for a page.

This property is read-write.

Example

The following example sets the page name:

```
&Page.Name = "Dogs Flight Info";
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

PreLoad

Description

Use this property to set or return a Boolean value specifying whether to cache external pages referenced from this page, even before they are linked to or displayed to the user.

Important! The pre-load option presents a trade-off between initial performance and subsequent responsiveness. Each pre-loaded page creates additional HTTP requests, which uses more bandwidth. Therefore, it is important to use the pre-load option only when you think users are likely to view the external pages.

This property is read-write.

TemplateName

Description

Use this property to return a String representing the name of the template assigned to this page.

This property is read-only.

Transition

Description

Use this property to set or return an Integer specifying the transition for this page to other pages in the same MAP layout.

Specify the value as one of the following constants:

Constant Value	*Description*
%MAP_Fade	Fade the page or dialog in over the previous content.
%MAP_Flip	An animated page flip, rotating the current view out with the other view on the reverse side.
%MAP_Pop	The page springs into view from the center of the screen.
%MAP_Slide	Slide in from the left or right, pushing the previous content out of the way.
%MAP_SlideDown	Slide down from the top, over the top of the current container.
%MAP_SlideUp	Slide up to the top, revealing the next content below.
%MAP_Turn	The page turns as in turning a page in a book.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Constant Value	*Description*
%MAP_Flow	Throws the current page away and comes in with the next page.
%MAP_SlideFade	Slide in from the left or right then fade the page.

This property is read-write.

Related Links

FormTransition

VisualBackButton

Description

Use this property to set or return a Boolean specifying whether to display a back button in the header of the page, to the left of the page title.

This property is read-write.

MapElement Class Methods

In this section, the MapElement class methods are presented in alphabetical order.

GetJavaScript

Syntax

`GetJavaScript``(`*`JS_event`*`)`

Description

Use this method to return the JavaScript function call associated with the specified JavaScript event.

The JavaScript event and its associated function call are defined in the JavaScript Events group box on the page element's properties page. See "Defining JavaScript Events for Page Element Properties" (PeopleTools 8.54: Mobile Application Platform) for more information.

Parameters

JS_event Specifies the JavaScript event as a String.

Returns

A String value.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GetListviewDefinedItemClass

Syntax

GetListviewDefinedItemClass(*listview_item_type*)

Description

Use this method to return the class for the specified predefined list view item type.

Parameters

listview_item_type Indicates which predefined list view item type as an Integer constant. Specify the value as one of the following constants:

Constant Value
%MAP_LV_Title
%MAP_LV_Desc
%MAP_LV_Count
%MAP_LV_Aside
%MAP_LV_Attr
%MAP_LV_Divider
%MAP_LV_DynImage
%MAP_LV_DynUrl

Returns

A String value.

GetListviewDefinedItemHidden

Syntax

GetListviewDefinedItemHidden(*listview_item_type*)

Description

Use this method to return whether the specified predefined list view item type is hidden.

Parameters

listview_item_type Indicates which predefined list view item type as an Integer constant. Specify the value as one of the following constants:

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Constant Value
%MAP_LV_Title
%MAP_LV_Desc
%MAP_LV_Count
%MAP_LV_Aside
%MAP_LV_Attr
%MAP_LV_Divider
%MAP_LV_DynImage
%MAP_LV_DynUrl

Returns

A Boolean value: True if the predefined list view item type is hidden, False otherwise.

GetListviewDefinedItemStyle

Syntax

GetListviewDefinedItemStyle(*listview_item_type*)

Description

Use this method to return the style for the specified predefined list view item type.

Parameters

listview_item_type Indicates which predefined list view item type as an Integer constant. Specify the value as one of the following constants:

Constant Value
%MAP_LV_Title
%MAP_LV_Desc
%MAP_LV_Count
%MAP_LV_Aside
%MAP_LV_Attr
%MAP_LV_Divider

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Constant Value
%MAP_LV_DynImage
%MAP_LV_DynUrl

Returns

A String value.

GetListviewItemClass

Syntax

GetListviewItemClass(*index*)

Description

Use this method to return the class for the specified user-defined list view item column.

Parameters

index	Specifies which user-defined list view item column as an Integer.

Returns

A String value.

GetListviewItemHidden

Syntax

GetListviewItemHidden(*index*)

Description

Use this method to return whether the specified user-defined list view item column is hidden.

Parameters

index	Specifies which user-defined list view item column as an Integer.

Returns

A Boolean value: True if the user-defined list view item column is hidden, False otherwise.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GetListviewItemStyle

Syntax

GetListviewItemStyle(*index*)

Description

Use this method to return the style for the specified user-defined list view item column.

Parameters

index Specifies which user-defined list view item column as an Integer.

Returns

A String value.

GetMobileGridClass

Syntax

GetMobileGridClass(*grid_column*)

Description

Use this method to return the class for the specified mobile grid column.

Parameters

grid_column Indicates which mobile grid column as a String constant. Specify the value as one of the following constants:

Constant Value	*Description*
%MAP_MOBILE_CLASS_ONE	Mobile grid column 1.
%MAP_MOBILE_CLASS_TWO	Mobile grid column 2.
%MAP_MOBILE_CLASS_THREE	Mobile grid column 3.
%MAP_MOBILE_CLASS_FOUR	Mobile grid column 4.
%MAP_MOBILE_CLASS_FIVE	Mobile grid column 5.

Returns

A String value.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GetMobileGridStyle

Syntax

GetMobileGridStyle(*grid_column*)

Description

Use this method to return the style for the specified mobile grid column.

Parameters

grid_column Indicates which mobile grid column as a String constant. Specify the value as one of the following constants:

Constant Value	*Description*
%MAP_MOBILE_STYLE_ONE	Mobile grid column 1.
%MAP_MOBILE_STYLE_TWO	Mobile grid column 2.
%MAP_MOBILE_STYLE_THREE	Mobile grid column 3.
%MAP_MOBILE_STYLE_FOUR	Mobile grid column 4.
%MAP_MOBILE_STYLE_FIVE	Mobile grid column 5.

Returns

A String value.

SetJavaScript

Syntax

SetJavaScript(*JS_event, JS_function*)

Description

Use this method to set the JavaScript function name for the specified JavaScript event

The JavaScript event and its associated function call are defined in the JavaScript Events group box on the page element's properties page. See "Defining JavaScript Events for Page Element Properties" (PeopleTools 8.54: Mobile Application Platform) for more information.

Parameters

JS_event Specifies the JavaScript event as a String.

JS_function Specifies the JavaScript function to call as a String.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

None

Example

The following example sets the JavaScript function call to `UpdateField()`:

```
&Element.SetJavaScript("onclick", "UpdateField()");
```

SetListviewDefinedItemClass

Syntax

`SetListviewDefinedItemClass`(*`listview_item_type, class`*)

Description

Use this method to set the class for the specified predefined list view item type.

Parameters

listview_item_type Indicates which predefined list view item type as an Integer constant. Specify the value as one of the following constants:

Constant Value
%MAP_LV_Title
%MAP_LV_Desc
%MAP_LV_Count
%MAP_LV_Aside
%MAP_LV_Attr
%MAP_LV_Divider
%MAP_LV_DynImage
%MAP_LV_DynUrl

class Specifies the class as a String.

Returns

None.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SetListviewDefinedItemHidden

Syntax

SetListviewDefinedItemHidden(*listview_item_type, hidden*)

Description

Use this method to set whether the specified predefined list view item type is hidden.

Parameters

listview_item_type Indicates which predefined list view item type as an Integer constant. Specify the value as one of the following constants:

Constant Value
%MAP_LV_Title
%MAP_LV_Desc
%MAP_LV_Count
%MAP_LV_Aside
%MAP_LV_Attr
%MAP_LV_Divider
%MAP_LV_DynImage
%MAP_LV_DynUrl

hidden Specifies whether the predefined list view item type is hidden as a Boolean.

Returns

None.

Example

The following example hides the Description column in the list view.

```
&Element.SetListviewDefinedItemHidden(%MAP_LV_Desc, True);
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SetListviewDefinedItemRowControl

Syntax

SetListviewDefinedItemRowControl(*row_num*, *listview_item_type*, *listview_item_control*, *value*)

Description

Use this method to set the control value for a predefined list view item type in the specified row.

Parameters

row_num Specifies the row number as an Integer.

listview_item_type Indicates which predefined list view item type as an Integer constant. Specify the value as one of the following constants:

Constant Value
%MAP_LV_Title
%MAP_LV_Desc
%MAP_LV_Count
%MAP_LV_Aside
%MAP_LV_Attr
%MAP_LV_Divider
%MAP_LV_DynImage
%MAP_LV_DynUrl

listview_item_control Indicates which list view item control as an Integer constant. Specify the value as one of the following constants:

Constant Value	Description
%MAP_LV_Item_Class	Class for the list view item.
%MAP_LV_Item_Style	Style for the list view item.
%MAP_LV_Item_Access	Alternative text for the list view item (for accessibility).
%MAP_LV_Item_Attr	jQuery attributes for the list view item to override defaults.

value Specifies the value for the control as a string.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

None.

Example

The following example sets color for the Title column in the fifth row of the list view.

```
&Element.SetListviewDefinedItemRowControl(5, %MAP_LV_Title, %MAP_LV_Item_Style, "co⇒
lor:red");
```

SetListviewDefinedItemStyle

Syntax

SetListviewDefinedItemStyle(*listview_item_type*, *style*)

Description

Use this method to set the style for the specified predefined list view item type.

Parameters

listview_item_type Indicates which predefined list view item type as an Integer constant. Specify the value as one of the following constants:

Constant Value
%MAP_LV_Title
%MAP_LV_Desc
%MAP_LV_Count
%MAP_LV_Aside
%MAP_LV_Attr
%MAP_LV_Divider
%MAP_LV_DynImage
%MAP_LV_DynUrl

style Specifies the style as a String.

Returns

None.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

The following example sets color for the Aside column in the list view.

```
&Element.SetListviewDefinedItemStyle(%MAP_LV_Aside, "color:red");
```

SetListviewDisableURL

Syntax

SetListviewDisableURL(*row_num*)

Description

Use this method to disable the URL for the row if a URL has been defined.

Parameters

row_num	Specifies the row number as an Integer.

Returns

None.

SetListviewItemClass

Syntax

SetListviewItemClass(*index*, *class*)

Description

Use this method to set the class for the specified user-defined list view item column.

Parameters

index	Specifies which user-defined list view item column as an Integer.
class	Specifies the class as a String.

Returns

None.

SetListviewItemHidden

Syntax

SetListviewItemHidden(*index*, *hidden*)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use this method to specify whether the specified user-defined list view item column is hidden.

Parameters

index Specifies which user-defined list view item column as an Integer.

hidden Specifies whether the column is hidden as a Boolean.

Returns

None.

Example

The following example specifies that the first user-defined item column in the list view is visible:

```
&Element.SetListviewItemHidden(1, False);
```

SetListviewItemRowControl

Syntax

SetListviewItemRowControl(*row_num*, *index*, *listview_item_control*, *value*)

Description

Use this method to set the control value for a user-defined list view column in the specified row.

Parameters

row_num Specifies the row number as an Integer.

index Specifies which user-defined list view column as an Integer.

listview_item_control Indicates which list view item control as an Integer constant. Specify the value as one of the following constants:

Constant Value	*Description*
%MAP_LV_Item_Class	Class for the list view item.
%MAP_LV_Item_Style	Style for the list view item.
%MAP_LV_Item_Access	Alternative text for the list view item (for accessibility).
%MAP_LV_Item_Attr	jQuery attributes for the list view item to override defaults.

value Specifies the value for the control as a string.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

None.

Example

The following example sets color for the fifth user-defined column in the second row of the list view.

```
&Element.SetListviewItemRowControl(2, 5, %MAP_LV_Item_Style, "color:yellow");
```

SetListviewItemStyle

Syntax

SetListviewItemStyle(*index*, *style*)

Description

Use this method to set the class for the specified user-defined list view item column.

Parameters

index	Specifies which user-defined list view item column as an Integer.
style	Specifies the style as a String.

Returns

None.

Example

The following example sets the color for the second user-defined item column in the list view.

```
&Element.SetListviewItemStyle(2, "color:yellow");
```

SetListviewRowControl

Syntax

SetListviewRowControl(*row_num*, *listview_item_control*, *value*)

Description

Use this method to set the control value for all list view columns in the specified row.

Parameters

row_num	Specifies the row number as an Integer.
listview_item_control	Indicates which list view item control as an Integer constant. Specify the value as one of the following constants:

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Constant Value	Description
%MAP_LV_Item_Class	Class for the list view item.
%MAP_LV_Item_Style	Style for the list view item.
%MAP_LV_Item_Access	Alternative text for the list view item (for accessibility).
%MAP_LV_Item_Attr	jQuery attributes for the list view item to override defaults.

value Specifies the value for the control as a string.

Returns

None.

SetMobileGridClass

Syntax

SetMobileGridClass(*grid_column, class*)

Description

Use this method to set the class for the specified mobile grid column.

Parameters

grid_column Indicates which mobile grid column as a String constant. Specify the value as one of the following constants:

Constant Value	Description
%MAP_MOBILE_CLASS_ONE	Mobile grid column 1.
%MAP_MOBILE_CLASS_TWO	Mobile grid column 2.
%MAP_MOBILE_CLASS_THREE	Mobile grid column 3.
%MAP_MOBILE_CLASS_FOUR	Mobile grid column 4.
%MAP_MOBILE_CLASS_FIVE	Mobile grid column 5.

class Specifies the class as a String value.

Returns

None.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

The following example sets the class for the second column of a mobile grid:

```
&Element.SetMobileGridClass(%MAP_MOBILE_CLASS_TWO, "myClass");
```

SetMobileGridStyle

Syntax

SetMobileGridStyle(*grid_column, style*)

Description

Use this method to set the style for the specified mobile grid column.

Parameters

grid_column Indicates which mobile grid column as a String constant. Specify the value as one of the following constants:

Constant Value	*Description*
%MAP_MOBILE_STYLE_ONE	Mobile grid column 1.
%MAP_MOBILE_STYLE_TWO	Mobile grid column 2.
%MAP_MOBILE_STYLE_THREE	Mobile grid column 3.
%MAP_MOBILE_STYLE_FOUR	Mobile grid column 4.
%MAP_MOBILE_STYLE_FIVE	Mobile grid column 5.

style Specifies the style as a String value.

Returns

None.

SetTableColumnProperty

Syntax

SetTableColumnProperty(*tbl_col_control, value*)

Description

Use this method to set the value of the specified control (either class or style) for the table column.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

tbl_col_control Indicates which control as an Integer.

Constant Value	*Description*
%MAP_CLASS	Class for the table column.
%MAP_STYLE	Style for the table column.

value Specifies the value of the control as a String.

Returns

None.

MapElement Class Properties

In this section, the MapElement class properties are presented in alphabetical order.

Page Element Types

The MapElement class supports each of the 18 element types that can be added to a MAP page:

- Action sheet
- Check box
- Container
- Flip toggle
- HTML area
- Image/static text
- Input field
- List view
- Mobile grid
- Push button
- Radio button
- Select box
- Select menu
- Sidebar
- Slider

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- Static text
- Table
- URL

Some properties (such as, ClassName, Style, Theme, ElementType, and so on) apply to all elements, while many others apply to a specific element type only. Therefore, use care to ensure that the property is applicable to the element you are manipulating. Otherwise, a PeopleCode runtime error similar to the following can occur:

```
Property prop_name not Applicable for Element ID element_ID
```

If necessary, use the ElementType property to identify the type of element you are manipulating. See ElementType.

Related Links

"Using the Layout Toolbar and Layout Grid" (PeopleTools 8.54: Mobile Application Platform)

AccessibilityText

Description

Note: This property applies to list view elements only.

Use this property to set or return a String representing the alternative text (alt text) for a list view item. You define alternative text for images for accessibility purposes.

This property is read-write.

ActionSheetCloseButton

Description

Note: This property applies to action sheet elements only.

Use this property to set or return a Boolean representing whether to include a Close button on the action sheet.

This property is read-write.

AjaxURL

Description

Note: This property applies to all element types.

Use this property to return a String representing the system-generated AJAX URL for this element.

This property is read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ButtonAlternativeURL

Description

Note: This property applies to push button elements only.

Use this property to set or return a Boolean value indicating whether to use the defined alternate URL instead of the button's standard URL. Use this property when you want to dynamically change the element's mapped URL due to a form factor change.

This property is read-write.

ButtonGroupControl

Description

Note: This property applies to push button elements only.

Use this property to set or return an Integer representing the orientation of a button group.

The values can be one of the following constants:

- %MAP_BG_Vertical
- %MAP_BG_Horizontal

This property is read-write.

ButtonIcon

Description

Note: This property applies to push button elements only.

Use this property to set or return an Integer representing the jQuery Mobile icon to appear on this button.

The values can be one of the following constants:

- %MAP_Icon_Alert
- %MAP_Icon_D
- %MAP_Icon_L
- %MAP_Icon_R
- %MAP_Icon_U
- %MAP_Icon_Back
- %MAP_Icon_Check
- %MAP_Icon_Delete

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- %MAP_Icon_Forward
- %MAP_Icon_Gear
- %MAP_Icon_Grid
- %MAP_Icon_Home
- %MAP_Icon_Info
- %MAP_Icon_Minus
- %MAP_Icon_Plus
- %MAP_Icon_Refresh
- %MAP_Icon_Search
- %MAP_Icon_Star
- %MAP_Icon_Bars
- %MAP_Icon_Edit

This property is read-write.

ButtonIconLocation

Description

Note: This property applies to push button elements only.

Use this property to set or return an Integer indicating the position of the button's icon. The default value is %MAP_Icon_Loc_Left.

The values can be one of the following constants:

- %MAP_Icon_Loc_Left
- %MAP_Icon_Loc_Bottom
- %MAP_Icon_Loc_None — No text.
- %MAP_Icon_Loc_Right
- %MAP_Icon_Loc_Top

This property is read-write.

ButtonInline

Description

Note: This property applies to push button elements only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Use this property to set or return a Boolean value indicating whether the button is to be generated as an in-line button. For in-line buttons, the width of the button is determined by the text and icon displayed on the button. For non-in-line buttons, the width is the full width of the screen.

This property is read-write.

ButtonLocation

Description

Note: This property applies to push button elements only.

Use this property to set or return an Integer representing the location of the button with respect to the title. This property applies to buttons defined within the header container only.

The values can be one of the following constants:

- %MAP_Btn_Loc_Right
- %MAP_Btn_Loc_Left

This property is read-write.

ButtonMini

Description

Note: This property applies to push button elements only.

Use this property to set or return a Boolean value indicating whether to display a compact version of the button.

This property is read-write.

ButtonRemoveCorner

Description

Note: This property applies to push button elements only.

Use this property to set or return a Boolean value indicating whether to remove the rounded corners from the button. Buttons are displayed with rounded corners by default. When this property is set to True, the button is displayed with rectangular corners.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ButtonRemoveIconShadow

Description

Note: This property applies to push button elements only.

Use this property to set or return a Boolean value indicating whether to remove the shadow from the button's icon. Icons are displayed on buttons with shadows by default.

This property is read-write.

ButtonRemoveShadow

Description

Note: This property applies to push button elements only.

Use this property to set or return a Boolean value indicating whether to remove the button's shadow. Buttons are displayed with shadows by default.

This property is read-write.

ClassName

Description

Note: This property applies to all element types.

Use this property to set or return a String representing the class for the *label* for this element. This property corresponds to the Class Name field in the Layout grid. See "Using the Layout Grid" (PeopleTools 8.54: Mobile Application Platform) for more information.

Note: Use the ContClassName property to set or return the class for the data for this element.

This property is read-write.

Related Links

LabelText

ContClassName

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ContClassName

Description

Note: This property applies to the following element types only:
Check box: Applies to the element's div wrapper.
Container: Applies to the container's image (if defined).
Image/static text: Applies to the image.
Input field: Applies to the input data.
List view: Applies to the list view's image (if defined).
Push button: Applies to the button's image (if defined).
Radio button: Applies to the element's div wrapper.
Static text: Applies to the text (data) itself.
URL: Applies to the URL's image (if defined).

Use this property to set or return a String representing the class name for the *data* for this element. This property corresponds to the Class field on the page element's properties page.

Note: Use the ClassName property to set or return the class for the label for this element.

This property is read-write.

Related Links

ClassName

ContPopup

Description

Note: This property applies to container elements only.

Use this property to set or return a Boolean value indicating whether this container element acts as a popup.

This property is read-write.

ContPopupBtnTheme

Description

Note: This property applies to container elements only.

Use this property to set or return a String representing the jQuery Mobile swatch assigned to the button used to pop up the container.

Specify the value as one of the following constants:

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Constant Value	*Swatch Description*	*Color (in the Default Theme)*
%MAP_Theme_a	Highest level of visual priority.	Black
%MAP_Theme_b	Secondary level of visual priority.	Blue
%MAP_Theme_c	Baseline level (default swatch).	Gray
%MAP_Theme_d	Alternate secondary level.	Gray
%MAP_Theme_e	Accent swatch.	Yellow

For more information on the default JQuery Mobile theme and its color swatches, see “Themes” in "Understanding Layout Template Container Terms and Concepts" (PeopleTools 8.54: Mobile Application Platform).

This property is read-write.

ContPopupButtonPos

Description

Note: This property applies to container elements only.

Use this property to set or return an Integer representing the position of the Close button only if the container element has been configured as a popup and if the Close button has been enabled.

The values can be one of the following constants:

- %MAP_Cont_BtnPopupPos_Left
- %MAP_Cont_BtnPopupPos_Right

This property is read-write.

Related Links

ContPopup

ContPopupIcon

Description

Note: This property applies to container elements only.

Use this property to set or return an Integer representing the jQuery Mobile icon to appear on this button.

The values can be one of the following constants:

- %MAP_Icon_Alert

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- %MAP_Icon_D
- %MAP_Icon_L
- %MAP_Icon_R
- %MAP_Icon_U
- %MAP_Icon_Back
- %MAP_Icon_Check
- %MAP_Icon_Delete
- %MAP_Icon_Forward
- %MAP_Icon_Gear
- %MAP_Icon_Grid
- %MAP_Icon_Home
- %MAP_Icon_Info
- %MAP_Icon_Minus
- %MAP_Icon_Plus
- %MAP_Icon_Refresh
- %MAP_Icon_Search
- %MAP_Icon_Star
- %MAP_Icon_Bars
- %MAP_Icon_Edit

This property is read-write.

ContPopupIconLocation

Description

Note: This property applies to container elements only.

Use this property to set or return an Integer indicating the position of the button's icon. The default value is %MAP_Icon_Loc_Left.

The values can be one of the following constants:

- %MAP_Icon_Loc_Left
- %MAP_Icon_Loc_Bottom
- %MAP_Icon_Loc_None — No text.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- %MAP_Icon_Loc_Right
- %MAP_Icon_Loc_Top

This property is read-write.

ContPopupOverlyTheme

Description

Note: This property applies to container elements only.

Use this property to set or return a String representing the jQuery Mobile swatch assigned to the overlay layer for the container's popup.

Specify the value as one of the following constants:

Constant Value	*Swatch Description*	*Color (in the Default Theme)*
%MAP_Theme_a	Highest level of visual priority.	Black
%MAP_Theme_b	Secondary level of visual priority.	Blue
%MAP_Theme_c	Baseline level (default swatch).	Gray
%MAP_Theme_d	Alternate secondary level.	Gray
%MAP_Theme_e	Accent swatch.	Yellow

For more information on the default JQuery Mobile theme and its color swatches, see "Themes" in "Understanding Layout Template Container Terms and Concepts" (PeopleTools 8.54: Mobile Application Platform).

This property is read-write.

ContPopupPos

Description

Note: This property applies to container elements only.

Use this property to set or return an Integer representing the location of the popup window.

The values can be one of the following constants:

- %MAP_Cont_PopupPos_Window
- %MAP_Cont_PopupPos_Origin

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ContPopupType

Description

Note: This property applies to container elements only.

Use this property to set or return an Integer representing the control used to activate the popup: button or link.

The values can be one of the following constants:

- %MAP_Cont_PopupType_Button
- %MAP_Cont_PopupType_Link

This property is read-write.

Controls

Description

Note: This property applies to the following element types only: check boxes, flip toggles, input fields, push buttons, radio buttons, select boxes, select menus, and sliders.

Use this property to set or return an Integer representing state for this element.

The values can be one of the following constants:

- %MAP_Disable — In addition to being read-only, the element cannot be used in any way. For example, it cannot be selected, highlighted, submitted, copied, and so on.
- %MAP_Enable — The element is enabled for normal interaction.
- %MAP_DisplayOnly — The element is read-only; no changes can be made.

This property is read-write.

Use the Style property to hide an element.

Related Links

Style

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ContStyle

Description

Note: This property applies to the following element types only:
Check box: Applies to the element's div wrapper.
Container: Applies to the container's image (if defined).
Image/static text: Applies to the image.
Input field: Applies to the input data.
List view: Applies to the list view's image (if defined).
Push button: Applies to the button's image (if defined).
Radio button: Applies to the element's div wrapper.
Static text: Applies to the text (data) itself.
URL: Applies to the URL's image (if defined).

Use this property to set or return a String representing the style for the *data* for this element. This property corresponds to the Style field on the page element's properties page.

Note: Use the Style property to set or return the style for the label for this element.

This property is read-write.

Related Links

Style

ContTheme

Description

Note: This property applies to the following element types only:
Check box: Applies to the element's div wrapper.
Container: Applies to the container's image (if defined).
Image/static text: Applies to the image.
Input field: Applies to the input data.
List view: Applies to the list view's image (if defined).
Push button: Applies to the button's image (if defined).
Radio button: Applies to the element's div wrapper.
Static text: Applies to the text (data) itself.
URL: Applies to the URL's image (if defined).

Use this property to set or return a String representing the jQuery Mobile swatch assigned to the *data* for this element. This property corresponds to the Theme field on the page element's properties page.

Specify the value as one of the following constants:

Constant Value	***Swatch Description***	***Color (in the Default Theme)***
%MAP_Theme_a	Highest level of visual priority.	Black

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Constant Value	*Swatch Description*	*Color (in the Default Theme)*
%MAP_Theme_b	Secondary level of visual priority.	Blue
%MAP_Theme_c	Baseline level (default swatch).	Gray
%MAP_Theme_d	Alternate secondary level.	Gray
%MAP_Theme_e	Accent swatch.	Yellow

For more information on the default JQuery Mobile theme and its color swatches, see “Themes” in "Understanding Layout Template Container Terms and Concepts" (PeopleTools 8.54: Mobile Application Platform).

This property is read-write.

Note: Use the Theme property to set or return the theme for the label for this element.

Related Links

Theme

DialogCloseOption

Description

Note: This property applies to URL elements only.

Use this property to set or return an Integer representing the position of the close button for a URL element designated to open as a dialog.

The values can be one of the following constants:

- %MAP_Dialog_Close_Left
- %MAP_Dialog_Close_Right
- %MAP_Dialog_Close_None

This property is read-write.

DialogOverlayTheme

Description

Note: This property applies to URL elements only.

Use this property to set or return a String representing the jQuery Mobile swatch assigned to the overlay layer for a URL element designated to open as a dialog.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Specify the value as one of the following constants:

Constant Value	*Swatch Description*	*Color (in the Default Theme)*
%MAP_Theme_a	Highest level of visual priority.	Black
%MAP_Theme_b	Secondary level of visual priority.	Blue
%MAP_Theme_c	Baseline level (default swatch).	Gray
%MAP_Theme_d	Alternate secondary level.	Gray
%MAP_Theme_e	Accent swatch.	Yellow

For more information on the default JQuery Mobile theme and its color swatches, see “Themes” in "Understanding Layout Template Container Terms and Concepts" (PeopleTools 8.54: Mobile Application Platform).

This property is read-write.

ElementType

Description

Note: This property applies to all element types.

Use this property to return an Integer representing the type of the current element.

Specify this value as one of the following constants:

- %MAP_Element_ActionSheet
- %MAP_Element_Button
- %MAP_Element_CheckBox
- %MAP_Element_Container
- %MAP_Element_FlipToggle
- %MAP_Element_HTMLArea
- %MAP_Element_ImageStaticText
- %MAP_Element_Input
- %MAP_Element_Listview
- %MAP_Element_MobileGrid
- %MAP_Element_Radio
- %MAP_Element_SelectBox

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- %MAP_Element_SelectMenu
- %MAP_Element_SideBar
- %MAP_Element_Slider
- %MAP_Element_StaticText
- %MAP_Element_Table
- %MAP_Element_URL

This property is read-only.

Example

You can use the ElementType property to determine the type of the current element:

```
If &Element.ElementType = %MAP_Element_Button Then
   /* Manipulate the push button's properties */
   ...
End-If;
```

FixedDisplayFormat

Description

Note: This property applies to header and footer elements only.

Use this property to set or return a Boolean value indicating whether the header or footer element remains fixed in position in the display window. While the user scrolls through content, the header or footer element remains affixed on top and the page content scrolls underneath.

This property is read-write.

Related Links

FullScreen

FlipToggleHighlight

Description

Note: This property applies to flip toggle elements only.

Use this property to set or return a Boolean value indicating whether highlight the fill of the toggle track.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

FlipToggleMini

Description

Note: This property applies to flip toggle elements only.

Use this property to set or return a Boolean value indicating whether to display a compact version of the flip toggle.

This property is read-write.

FlipToggleTrackTheme

Description

Note: This property applies to flip toggle elements only.

Use this property to set or return a String representing the jQuery Mobile swatch assigned to the toggle switch's track.

Specify the value as one of the following constants:

Constant Value	*Swatch Description*	*Color (in the Default Theme)*
%MAP_Theme_a	Highest level of visual priority.	Black
%MAP_Theme_b	Secondary level of visual priority.	Blue
%MAP_Theme_c	Baseline level (default swatch).	Gray
%MAP_Theme_d	Alternate secondary level.	Gray
%MAP_Theme_e	Accent swatch.	Yellow

For more information on the default JQuery Mobile theme and its color swatches, see "Themes" in "Understanding Layout Template Container Terms and Concepts" (PeopleTools 8.54: Mobile Application Platform).

This property is read-write.

FullScreen

Description

Note: This property applies to header and footer elements only.

Use this property to set or return a Boolean value indicating whether the header or footer element is to disappear (and then reappear) when the page is clicked, allowing the page content to be displayed using

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

the full screen. Common scenarios for viewing page content on the full screen include photo and video viewers. To allow the page content to be displayed on the full screen, set FixedDisplayFormat to True and set this property to True.

This property is read-write.

Related Links

FixedDisplayFormat

GridOption

Description

Important! Grid elements have not been implemented in this release. This property is not currently used.

Note: This property applies to grid elements only.

Use this property to set or return an Integer.

This property is read-write.

GridScroll

Description

Important! Grid elements have not been implemented in this release. This property is not currently used.

Note: This property applies to grid elements only.

Use this property to set or return a Integer representing ...

This property is read-write.

GroupLabelText

Description

Note: This property applies to groups only.

Use this property to set or return a String representing the label for a group of elements. You can group together certain element types (for example, push buttons, check boxes, select menus, and others) to achieve specific behaviors.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

HideListviewSplitButton

Description

Note: This property applies to list view elements only.

Use this property to set or return a Boolean value indicating whether to hide the split button if it has been enabled for this list view element.

This property is read-write.

ImageOvrd

Description

Note: This property applies to push button and URL elements only.

Use this property to set or return a String representing the name of the override image for the element.

This property is read-write.

InputMini

Description

Note: This property applies to input field elements only.

Use this property to set or return a Boolean value indicating whether to display a compact version of the input field.

This property is read-write.

InputRequired

Description

Note: This property applies to input field elements only.

Use this property to set or return a Boolean value indicating whether this input field is required.

This property is read-write.

LabelID

Description

Note: This property applies to all element types.

Use this property to return a String representing the element's ID.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-only.

LabelText

Description

Note: This property applies to all element types.

Use this property to set or return a String representing the user-visible label that is displayed on the element.

This property is read-write.

ListviewAlternativeURL

Description

Note: This property applies to list view elements only.

Use this property to set or return a Boolean value indicating whether to use the defined alternate URL instead of the list view's standard URL. Use this property when you want to dynamically change the element's mapped URL due to a form factor change.

This property is read-write.

ListviewCollapsed

Description

Note: This property applies to list view elements only.

Use this property to set or return a Boolean value indicating whether a collapsible list view is initially collapsed.

This property is read-write.

ListViewCollapsible

Description

Note: This property applies to list view elements only.

Use this property to set or return a Boolean value indicating whether a list view is collapsible.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ListviewCountTheme

Description

Note: This property applies to list view elements only.

Use this property to set or return a String representing the jQuery Mobile swatch assigned to the count bubble for the list view element.

Specify the value as one of the following constants:

Constant Value	*Swatch Description*	*Color (in the Default Theme)*
%MAP_Theme_a	Highest level of visual priority.	Black
%MAP_Theme_b	Secondary level of visual priority.	Blue
%MAP_Theme_c	Baseline level (default swatch).	Gray
%MAP_Theme_d	Alternate secondary level.	Gray
%MAP_Theme_e	Accent swatch.	Yellow

For more information on the default JQuery Mobile theme and its color swatches, see “Themes” in "Understanding Layout Template Container Terms and Concepts" (PeopleTools 8.54: Mobile Application Platform).

This property is read-write.

ListviewDividerDisplay

Description

Note: This property applies to list view elements only.

Use this property to set or return an Integer representing the location of the divider between rows in the list view.

The values can be one of the following constants:

- %MAP_LV_Divider_Above
- %MAP_LV_Divider_Below

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ListViewDividerMsgCat

Description

Note: This property applies to list view elements only.

Use this property to set or return a String that is the concatenation of the message set number and message number. Use the `|` character to separate the message set number from the message number.

This property is read-write.

Example

To set a message catalog entry as the list view divider:

```
&Element.ListViewDividerMsgCat = "158|300";
```

ListviewFilterTheme

Description

Note: This property applies to list view elements only.

Use this property to set or return a String representing the jQuery Mobile swatch assigned to the filter for the list view element.

Specify the value as one of the following constants:

Constant Value	***Swatch Description***	***Color (in the Default Theme)***
%MAP_Theme_a	Highest level of visual priority.	Black
%MAP_Theme_b	Secondary level of visual priority.	Blue
%MAP_Theme_c	Baseline level (default swatch).	Gray
%MAP_Theme_d	Alternate secondary level.	Gray
%MAP_Theme_e	Accent swatch.	Yellow

For more information on the default JQuery Mobile theme and its color swatches, see “Themes” in "Understanding Layout Template Container Terms and Concepts" (PeopleTools 8.54: Mobile Application Platform).

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ListviewHeaderTheme

Description

Note: This property applies to list view elements only.

Use this property to set or return a String representing the jQuery Mobile swatch assigned to the header for the list view element.

Specify the value as one of the following constants:

Constant Value	*Swatch Description*	*Color (in the Default Theme)*
%MAP_Theme_a	Highest level of visual priority.	Black
%MAP_Theme_b	Secondary level of visual priority.	Blue
%MAP_Theme_c	Baseline level (default swatch).	Gray
%MAP_Theme_d	Alternate secondary level.	Gray
%MAP_Theme_e	Accent swatch.	Yellow

For more information on the default JQuery Mobile theme and its color swatches, see “Themes” in "Understanding Layout Template Container Terms and Concepts" (PeopleTools 8.54: Mobile Application Platform).

This property is read-write.

ListviewInset

Description

Note: This property applies to list view elements only.

Use this property to set or return a Boolean value indicating whether to display the list as inset from the full page width. When the value of this property is False, the list displays the full width of the page.

This property is read-write.

ListviewSplitIcon

Description

Note: This property applies to list view elements only.

Use this property to set or return an Integer representing the jQuery Mobile icon to appear on the split button for this list view element.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The values can be one of the following constants:

- %MAP_Icon_Alert
- %MAP_Icon_D
- %MAP_Icon_L
- %MAP_Icon_R
- %MAP_Icon_U
- %MAP_Icon_Back
- %MAP_Icon_Check
- %MAP_Icon_Delete
- %MAP_Icon_Forward
- %MAP_Icon_Gear
- %MAP_Icon_Grid
- %MAP_Icon_Home
- %MAP_Icon_Info
- %MAP_Icon_Minus
- %MAP_Icon_Plus
- %MAP_Icon_Refresh
- %MAP_Icon_Search
- %MAP_Icon_Star
- %MAP_Icon_Bars
- %MAP_Icon_Edit

This property is read-write.

ListviewSplitTheme

Description

Note: This property applies to list view elements only.

Use this property to set or return a String representing the jQuery Mobile swatch assigned to the split button for this list view element.

Specify the value as one of the following constants:

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Constant Value	*Swatch Description*	*Color (in the Default Theme)*
%MAP_Theme_a	Highest level of visual priority.	Black
%MAP_Theme_b	Secondary level of visual priority.	Blue
%MAP_Theme_c	Baseline level (default swatch).	Gray
%MAP_Theme_d	Alternate secondary level.	Gray
%MAP_Theme_e	Accent swatch.	Yellow

For more information on the default JQuery Mobile theme and its color swatches, see “Themes” in "Understanding Layout Template Container Terms and Concepts" (PeopleTools 8.54: Mobile Application Platform).

This property is read-write.

ListviewType

Description

Note: This property applies to list view elements only.

Use this property to set or return an Integer representing indicating the type of list view: ordered or unordered.

The values can be one of the following constants:

- %MAP_LV_Ordered
- %MAP_LV_UnOrdered

This property is read-write.

ListviewURLJavaScript

Description

Note: This property applies to list view elements only.

Use this property to set or return a String representing the JavaScript function to be called by the list view instead of invoking a URL.

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

MenuIcon

Description

Note: This property applies to select menu elements only.

Use this property to set or return an Integer representing the jQuery Mobile icon to appear on the button for a select menu.

The values can be one of the following constants:

- %MAP_Icon_Alert
- %MAP_Icon_D
- %MAP_Icon_L
- %MAP_Icon_R
- %MAP_Icon_U
- %MAP_Icon_Back
- %MAP_Icon_Check
- %MAP_Icon_Delete
- %MAP_Icon_Forward
- %MAP_Icon_Gear
- %MAP_Icon_Grid
- %MAP_Icon_Home
- %MAP_Icon_Info
- %MAP_Icon_Minus
- %MAP_Icon_Plus
- %MAP_Icon_Refresh
- %MAP_Icon_Search
- %MAP_Icon_Star
- %MAP_Icon_Bars
- %MAP_Icon_Edit

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

MenuIconLocation

Description

Note: This property applies to select menu elements only.

Use this property to set or return an Integer indicating the position of the button's icon. The default value is %MAP_Icon_Loc_Left.

The values can be one of the following constants:

- %MAP_Icon_Loc_Left
- %MAP_Icon_Loc_Bottom
- %MAP_Icon_Loc_None — No text.
- %MAP_Icon_Loc_Right
- %MAP_Icon_Loc_Top

This property is read-write.

MenuInline

Description

Note: This property applies to select menu elements only.

Use this property to set or return a Boolean value indicating whether to display the select menu's button as if it were an in-line element; the button's width is determined by the text displayed on the button.

This property is read-write.

MenuMini

Description

Note: This property applies to select menu elements only.

Use this property to set or return a Boolean value indicating whether to display the select menu's button as a compact version.

This property is read-write.

MenuMultiple

Description

Note: This property applies to select menu elements only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Use this property to set or return a Boolean value indicating whether to allow multiple selections from the select menu.

This property is read-write.

MenuNonNative

Description

Note: This property applies to select menu elements only.

Use this property to set or return a Boolean value indicating whether to display the select menu in an alternative user interface rather than relying on the native select element of the mobile browser.

Note: In the Layout Designer, this check box provides additional options: Multiple check box, Placeholder Text fields, and Optional Label fields.

This property is read-write.

MenuOverlayTheme

Description

Note: This property applies to select menu elements only.

Use this property to set or return a String representing the jQuery Mobile swatch assigned to the overlay layer for the select menu.

Specify the value as one of the following constants:

Constant Value	*Swatch Description*	*Color (in the Default Theme)*
%MAP_Theme_a	Highest level of visual priority.	Black
%MAP_Theme_b	Secondary level of visual priority.	Blue
%MAP_Theme_c	Baseline level (default swatch).	Gray
%MAP_Theme_d	Alternate secondary level.	Gray
%MAP_Theme_e	Accent swatch.	Yellow

For more information on the default JQuery Mobile theme and its color swatches, see “Themes” in "Understanding Layout Template Container Terms and Concepts" (PeopleTools 8.54: Mobile Application Platform).

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

MenuRemoveCorner

Description

Note: This property applies to select menu elements only.

Use this property to set or return a Boolean value indicating whether to remove the rounded corners from the button for the select menu. Buttons are displayed with rounded corners by default. When this property is set to True, the button is displayed with rectangular corners.

This property is read-write.

MenuRemoveShadow

Description

Use this property to set or return a Boolean value indicating whether to remove the shadow from the select menu's button. Buttons are displayed with shadows by default.

This property is read-write.

NoGridAutoWidth

Description

Important! Grid elements have not been implemented in this release. This property is not currently used.

Note: This property applies to grid elements only.

Use this property to set or return a Boolean value.

This property is read-write.

NoGridFilter

Description

Important! Grid elements have not been implemented in this release. This property is not currently used.

Note: This property applies to grid elements only.

Use this property to set or return a Boolean value.

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

NoGridInfo

Description

Important! Grid elements have not been implemented in this release. This property is not currently used.

Note: This property applies to grid elements only.

Use this property to set or return a Boolean value.

This property is read-write.

NoGridPageinate

Description

Important! Grid elements have not been implemented in this release. This property is not currently used.

Note: This property applies to grid elements only.

Use this property to set or return a Boolean value.

This property is read-write.

NoGridPageLengthChange

Description

Important! Grid elements have not been implemented in this release. This property is not currently used.

Note: This property applies to grid elements only.

Use this property to set or return a Boolean value.

This property is read-write.

NoGridSort

Description

Important! Grid elements have not been implemented in this release. This property is not currently used.

Note: This property applies to grid elements only.

Use this property to set or return a Boolean value.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

PlugIn

Description

Note: This property applies to all element types.

Use this property to specify additional plug-in attributes for the element.

This property is read-write.

Example

For the case in which a JavaScript program adds new behavior to current jQuery Mobile widgets or to core functionality, you can add appropriate attributes through this property. For example:

```
&Element.PlugIn = 'data-rel="back"'
```

SaveNoPopup

Description

Note: This property applies to push button elements only.

For a push button defined with a button type of Save, use this property to set or return a Boolean value indicating whether to suppress the pop-up message indicating save results.

This property is read-write.

SaveRedirect

Description

Note: This property applies to push button elements only.

For a push button defined with a button type of Save, use this property to set or return a Boolean value indicating whether to redirect to another page (or update the same page) instead of displaying the pop-up message indicating save results.

This property is read-write.

SecureURL

Description

Note: This property applies to URL elements only.

Use this property to set or return a Boolean value indicating whether the URL is constructed from a REST provider service operation or layout if applicable (secure REST target location defined).

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SideBarAnimationOff

Description

Note: This property applies to sidebar elements only.

Use this property to set or return a Boolean value indicating whether animation for the sidebar is off.

This property is read-write.

SideBarDisplay

Description

Note: This property applies to sidebar elements only.

Use this property to set or return an Integer representing how to animate the sidebar with respect to the page.

The values can be one of the following constants:

Constant Value	*Description*
%MAP_Display_Reveal	The sidebar sits under the page and is revealed as the page slides away. **Note:** %MAP_Display_Reveal is the default value.
%MAP_Display_Overlay	The sidebar appears on top of the page contents.
%MAP_Display_Push	The sidebar and page are both animated at the same time.

This property is read-write.

SideBarNoSwipeClose

Description

Note: This property applies to sidebar elements only.

Use this property to set or return a Boolean value indicating whether to turn off the swipe-to-close behavior. By default, swiping left or right or pressing the Esc key will close the sidebar.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SideBarNotDismissible

Description

Note: This property applies to sidebar elements only.

Use this property to set or return a Boolean value indicating whether to prevent closing the sidebar by clicking outside the sidebar. By default, sidebars can also be closed by clicking outside the sidebar in the page contents.

This property is read-write.

SideBarPosFixed

Description

Note: This property applies to sidebar elements only.

Use this property to set or return a Boolean value indicating whether to display the sidebar no matter how far down the page the user has scrolled.

This property is read-write.

SideBarPosRight

Description

Note: This property applies to sidebar elements only.

Use this property to set or return a Boolean value indicating whether to display the sidebar on the right side of the screen. The default position of the sidebar is on the left side of the screen.

This property is read-write.

SliderDefaultTrack

Description

Note: This property applies to slider elements only.

Use this property to set or return an Integer representing the default value for the slider.

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SliderDisable

Description

Note: This property applies to slider elements only.

Use this property to set or return a Boolean value indicating whether to disable the slider so that users cannot interact with it.

This property is read-write.

SliderHighlight

Description

Note: This property applies to slider elements only.

Use this property to set or return a Boolean value indicating whether to highlight the slider track to the left of the handle.

This property is read-write.

SliderMaximum

Description

Note: This property applies to slider elements only.

Use this property to set or return an Integer representing maximum value for the slider.

This property is read-write.

SliderMini

Description

Note: This property applies to slider elements only.

Use this property to set or return a Boolean value indicating whether to display a compact version of the slider.

This property is read-write.

SliderMinimum

Description

Note: This property applies to slider elements only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Use this property to set or return an Integer representing the minimum value for the slider.

This property is read-write.

SliderStep

Description

Note: This property applies to slider elements only.

Use this property to set or return an Integer representing the step increment for the slider.

This property is read-write.

SliderTrackTheme

Description

Note: This property applies to slider elements only.

Use this property to set or return a String representing the jQuery Mobile swatch assigned to the track for the slider.

Specify the value as one of the following constants:

Constant Value	*Swatch Description*	*Color (in the Default Theme)*
%MAP_Theme_a	Highest level of visual priority.	Black
%MAP_Theme_b	Secondary level of visual priority.	Blue
%MAP_Theme_c	Baseline level (default swatch).	Gray
%MAP_Theme_d	Alternate secondary level.	Gray
%MAP_Theme_e	Accent swatch.	Yellow

For more information on the default JQuery Mobile theme and its color swatches, see “Themes” in "Understanding Layout Template Container Terms and Concepts" (PeopleTools 8.54: Mobile Application Platform).

This property is read-write.

Style

Description

Note: This property applies to all element types.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Use this property to set or return a String representing the style for the *label* for this element. This property corresponds to the Style field in the Layout grid. See "Using the Layout Grid" (PeopleTools 8.54: Mobile Application Platform) for more information.

Note: Use the ContStyle property to set or return the style for the data for this element.

This property is read-write.

Example

For example, use the Style property to hide *both* the label and the data for an element so that the element is not displayed on the MAP page:

```
&Element.Style = "display:none";
```

Related Links

LabelText
ContStyle

TableColumnHide

Description

Note: This property applies to table element (column) elements only.

Use this property to set or return a Boolean value indicating whether this table column is hidden from display regardless of table size or column priority.

This property is read-write.

TableColumnPopupTheme

Description

Note: This property applies to table elements only.

Use this property to set or return a String representing the jQuery Mobile swatch assigned to the Columns... popup for this table.

Specify the value as one of the following constants:

Constant Value	***Swatch Description***	***Color (in the Default Theme)***
%MAP_Theme_a	Highest level of visual priority.	Black
%MAP_Theme_b	Secondary level of visual priority.	Blue
%MAP_Theme_c	Baseline level (default swatch).	Gray

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Constant Value	*Swatch Description*	*Color (in the Default Theme)*
%MAP_Theme_d	Alternate secondary level.	Gray
%MAP_Theme_e	Accent swatch.	Yellow

For more information on the default JQuery Mobile theme and its color swatches, see “Themes” in "Understanding Layout Template Container Terms and Concepts" (PeopleTools 8.54: Mobile Application Platform).

This property is read-write.

Related Links

TableColumnToggle

TableColumnTheme

Description

Note: This property applies to table elements only.

Use this property to set or return a String representing the jQuery Mobile swatch assigned to the Columns... button for the table.

Specify the value as one of the following constants:

Constant Value	*Swatch Description*	*Color (in the Default Theme)*
%MAP_Theme_a	Highest level of visual priority.	Black
%MAP_Theme_b	Secondary level of visual priority.	Blue
%MAP_Theme_c	Baseline level (default swatch).	Gray
%MAP_Theme_d	Alternate secondary level.	Gray
%MAP_Theme_e	Accent swatch.	Yellow

For more information on the default JQuery Mobile theme and its color swatches, see “Themes” in "Understanding Layout Template Container Terms and Concepts" (PeopleTools 8.54: Mobile Application Platform).

This property is read-write.

Related Links

TableColumnToggle

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

TableColumnToggle

Description

Note: This property applies to table elements only.

Use this property to set or return a Boolean value indicating whether to hide less important (lower priority) table columns at narrow screen widths. When this property is set to True, the Columns... button is displayed to allow the user to select which columns to be displayed.

This property is read-write.

TableResponsive

Description

Note: This property applies to table elements only.

Use this property to set or return a Boolean value indicating whether to allow the MAP application developer to add customizations through CSS or media queries.

This property is read-write.

TableStripe

Description

Note: This property applies to table elements only.

Use this property to set or return a Boolean value indicating whether to shade alternate rows in the table.

This property is read-write.

TextSize

Description

Note: This property applies to image/static text and static text elements only.

Use this property to set or return an Integer from 1–6 representing the text size. The integer values correspond to HTML heading tags (h1, h2, h3, ... h6).

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Theme

Description

Note: This property applies to all elements.

Use this property to set or return a String representing the jQuery Mobile swatch assigned to the *label* for this element. This property corresponds to the Theme field in the Layout grid. See "Using the Layout Grid" (PeopleTools 8.54: Mobile Application Platform) for more information.

Specify the value as one of the following constants:

Constant Value	***Swatch Description***	***Color (in the Default Theme)***
%MAP_Theme_a	Highest level of visual priority.	Black
%MAP_Theme_b	Secondary level of visual priority.	Blue
%MAP_Theme_c	Baseline level (default swatch).	Gray
%MAP_Theme_d	Alternate secondary level.	Gray
%MAP_Theme_e	Accent swatch.	Yellow

For more information on the default JQuery Mobile theme and its color swatches, see “Themes” in "Understanding Layout Template Container Terms and Concepts" (PeopleTools 8.54: Mobile Application Platform).

This property is read-write.

Note: Use the ContTheme property to set or return the theme for the data for this element.

Related Links

LabelText
ContTheme

ThemeDivider

Description

Note: This property applies to list view elements only.

Use this property to set or return a String representing the jQuery Mobile swatch assigned to the divider for this list view.

Specify the value as one of the following constants:

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Constant Value	*Swatch Description*	*Color (in the Default Theme)*
%MAP_Theme_a	Highest level of visual priority.	Black
%MAP_Theme_b	Secondary level of visual priority.	Blue
%MAP_Theme_c	Baseline level (default swatch).	Gray
%MAP_Theme_d	Alternate secondary level.	Gray
%MAP_Theme_e	Accent swatch.	Yellow

For more information on the default JQuery Mobile theme and its color swatches, see “Themes” in "Understanding Layout Template Container Terms and Concepts" (PeopleTools 8.54: Mobile Application Platform).

This property is read-write.

URLAlternativeURL

Description

Note: This property applies to URL elements only.

Use this property to set or return a Boolean value indicating whether to use the defined alternative URL instead of the URL element’s standard URL. Use this property when you want to dynamically change the element’s mapped URL due to a form factor change.

This property is read-write.

URLPost

Description

Note: This property applies to URL elements only.

Use this property to set or return a Boolean value indicating whether to access the new page through an HTTP POST operation. By default an external page is called though an HTTP GET operation. If the data to be passed as arguments needs to be secure, set the URLPost property to True to make the request through an HTTP POST.

This property is read-write.

URLSameWindow

Description

Note: This property applies to URL elements only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Use this property to set or return a Boolean value indicating whether to open the new page in the same window.

Note: Ensure that the new page has an appropriate back action so that the user can return to your MAP application.

This property is read-write.

URLType

Description

Note: This property applies to URL elements only.

Use this property to return an Integer representing the type defined for this URL element.

The values can be one of the following:

- %MAP_URL
- %MAP_LAYOUT
- %MAP_REST
- %MAP_Internal
- %MAP_External

This property is read-only.

MapFluid Class Methods

In this section, the MapFluid class methods are presented in alphabetical order.

AddMenuItemToActionMenu

Syntax

AddMenuItemToActionMenu(*&Map*, *index*, *key*, *label*, *URL*, *classes*, *JS_function*)

Description

Use this method to add a list item to the actions list that is displayed in the header for the PeopleSoft Fluid Interface.

Parameters

&Map	Specifies the MAP application as an already instantiated Map object.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

index Specifies the location of the new list item as a Number.

Note: An index of 1 is the top of the actions list.

key Specifies a unique key for the new list item as a String.

Note: PeopleTools has reserved the following list item keys: HOME, SRCH, NAVG, and LOGOUT.

label Specifies the label for the new list item as a String.

URL Specifies the target URL for the new list item as a String.

classes Specifies custom CSS style classes as a String.

JS_function Specifies a custom JavaScript function as a String.

Note: If no custom function is specified, then the delivered ChangeActionMenuSelection(this,true) function is invoked.

Returns

None.

Example

```
Local PT_MAP_ADMIN:MapFluid &oToolbar = create PT_MAP_ADMIN:MapFluid();

&oToolbar.AddMenuItemToActionMenu(&Map, 1, "PENDING", MsgGetText(18081, 25014, "No ⇒
message found: Pending Approvals."), &URL, "color:red;", "my_function(true)");
&oToolbar.RenderActionMenuHTML(&Map);
```

Related Links

RemoveAction

RenderActionMenuHTML

RemoveAction

Syntax

RemoveAction(*&Map*, *key*, *button*, *menu*)

Description

Use this method to remove an item from the actions list (which is displayed in the header for the PeopleSoft Fluid Interface), from the button tool bar, or both.

Parameters

&Map Specifies the MAP application as an already instantiated Map object.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

key Specifies a unique key for the list item to be removed as a String.

Note: PeopleTools has reserved the following list item keys: HOME, SRCH, NAVG, and LOGOUT.

button Specifies a Boolean value indicating whether to remove this item from the main fluid page header.

The default value is False.

menu Specifies a Boolean value indicating whether to remove this list item from the actions list.

The default value is False.

Returns

None

Example

In the following example, the Search button will be removed from the main fluid header and the Search list item will also be removed from the actions list:

```
Local PT_MAP_ADMIN:MapFluid &oToolbar = create PT_MAP_ADMIN:MapFluid();

&oToolbar.RemoveAction(&Map, "SRCH", False, True);
&oToolbar.RenderActionMenuHTML(&Map);
```

Related Links

AddMenuItemToActionMenu

RenderActionMenuHTML

RenderActionMenuHTML

Syntax

RenderActionMenuHTML(*&Map*)

Description

Use this method to render the HTML representing the complete actions list that is displayed in the header for the PeopleSoft Fluid Interface.

You must invoke this method after invoking AddMenuItemToActionMenu, RemoveAction, or UpdateSignOutURL to make changes to the structure of the actions list.

Parameters

&Map Specifies the MAP application as an already instantiated Map object.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

None

Example

```
&oToolbar.RenderActionMenuHTML(&Map);
```

UpdateSignOutURL

Syntax

UpdateSignOutURL(*&Map*, *URL*)

Description

Use this method to change the URL that is invoked when a user clicks Sign out in the actions list.

Parameters

&Map	Specifies the MAP application as an already instantiated Map object.
URL	Specifies the new URL as a String.

Returns

None.

Example

```
Local PT_MAP_ADMIN:MapFluid &oToolbar = create PT_MAP_ADMIN:MapFluid();

&oToolbar.UpdateSignOutURL(&Map, &URL | "/?cmd=logout&fmode=1");
&oToolbar.RenderActionMenuHTML(&Map);
```

Related Links

RenderActionMenuHTML

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Chapter 30

Notification Classes

Understanding Notification Classes

The Notification classes are used for ad-hoc notification. These classes enable you to create and send a notification to someone. The notifications can either be a Peoplesoft Worklist item or an SMTP email message. The Notification class also stores notifications in a table.

You can also use web services to create Worklist entries, then send notifications of completion using application messages.

The Notification classes can be called from a component, an internet script, or an Application Engine program. The WSWorklistEntry class can be used incase you are developing your own PT_WORKLIST notification handler. .

Most of the classes, as well as most of the properties and methods that make up the Notification classes have a GUI representation in Peoplesoft Workflow. This document assumes that the reader is familiar with PeopleSoft Workflow.

Related Links

"Understanding PeopleSoft Workflow" (PeopleTools 8.54: Workflow Technology)

Scope of the Notification Classes

The Notification classes can be called from a component, an internet script, Integration Broker, or an Application Engine program.

Notification classes can be of Local, Global, or Component scope.

Data Types of the Notification Classes

Every Notification class is its own data type, that is, Notifications are declared as data type Notification, Notification addresses are declared as type NotificationAddress, and so on.

The following are the data types of the Notification classes:

- Notification
- NotificationAddress
- NotificationTemplate
- WorklistEntry

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- Worklist
- WSWorkListEntry

How to Import the Notification Classes

The Notification classes are *not* built-in classes, like Rowset, Field, Record, and so on. They are application classes. Before you can use these classes in your PeopleCode program, you must import them to your program.

An import statement names either all the classes in a package or one particular application class. For importing the Notification classes, PeopleSoft recommends that you import all the classes in the application package.

The application package PT_WF_NOTIFICATION contains the following classes:

- Notification
- NotificationAddress
- NotificationTemplate

The application package PT_WF_WORKLIST contains the following classes:

- Worklist
- WorklistEntry
- WSWorkListEntry

The import statements you should use are as follows:

```
import PT_WF_NOTIFICATION:*;
import PT_WF_WORKLIST:*;
```

Using the asterisks after the package name makes all the application classes directly contained in the named package available. Application classes contained in subpackages of the named package are *not* made available.

Related Links

Understanding Application Classes

How to Create a Notification Object

After you've imported the Notification classes, you instantiate an object of one of those classes using the constructor for the class and the Create function.

The following example creates a new instance of the WorklistEntry class, as the variable &MyWE, with local scope:

```
Local WorklistEntry &MyWE = Create WorklistEntry();
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

Notification Classes Constructors

Notification Classes Constructors

You must use the constructor for each class to instantiate an instance of that class. The following are the constructors for the Notification classes.

Notification

Syntax

Notification(*NotifyFrom*, *dttmCreated*, *language_cd*)

Description

Use Notification to instantiate a notification object.

Parameters

NotifyFrom

Specify the entity the notification is being sent from, as a string. Avoid overusing generic entities with this parameter, as this value, along with the value for *dttmCreated* are the key to understanding where notifications originated from.

dttmCreated

Specify the date and time the notification is being sent, as a DateTime value.

Important! To ensure a unique timestamp for each notification that is sent, you must pass a DateTime value that includes milliseconds. Because the %Datetime system variable always returns 0 for the milliseconds value, use the combination of %Date+%PerfTime instead.

language_cd

Specify the 3-character language code of the current user, as a string.

Returns

A Notification object.

Example

To ensure a unique timestamp for each notification that is sent, you must pass a DateTime value that includes milliseconds to the *dttmCreated* parameter. Because the %Datetime system variable always returns 0 for the milliseconds value, use the combination of %Date+%PerfTime instead.

```
import PT_WF_NOTIFICATION:*;
import PT_WF_WORKLIST:*;

Local PT_WF_NOTIFICATION:Notification &MyNotify;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
&MyNotify = create PT_WF_NOTIFICATION:Notification("Workflow_Admin", %Date + %PerfT⇒
ime, %Language);
```

Related Links

Notification Class

NotificationAddress

Syntax

NotificationAddress(*Oprid*, *Description*, *Language*, *EmailId*, *Channel*)

Description

Use NotificationAddress to instantiate a notification address.

This address is used to build a notification using the Notification class. This class is required if you want to use the Notification data type.

Parameters

Oprid Specify the user ID of the person receiving the notification, as a string.

Description Specify the description of the entity receiving the notification (distribution group names, people's names, and so on) as a string.

Language Specify the language code of the entity to be notified as a string.

EmailId Specify the email address as a string.

Channel Specify the 'channel' used for the notification, as a string. The values are:

Value	*Description*
Email	Notification is sent as email
Worklist	Notification is sent as a worklist

Returns

None.

Example

```
import PT_WF_NOTIFICATION:*;

import PT_WF_WORKLIST:*;

Local NotificationAddress &MyNotify_Addy;

&MyNotify_Addy = Create NotificationAddress(%UserID, &Description, %Language, &Emai⇒
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
lID, &Channel);
```

Related Links

NotificationAddress Class

NotificationTemplate

Syntax

NotificationTemplate(*ComponentId*, *Market*, *TemplateId*, *TemplateType*)

Description

Use NotificationTemplate to instantiate a notification template.

If you're specifying a generic template, the first two parameters do not have to have values, that is, you must specify a Null string ("") instead.

Parameters

ComponentId	Specify the name of the component the notification is coming from as a string. To specify a generic template, you must specify a Null string ("") for this value instead.
Market	Specify the name of the market of the component the notification is coming from as a string. To specify a generic template, you must specify a Null string ("") for this value instead.
TemplateId	Specify the template ID as a string.
TemplateType	Specify the type of template as a string. Values are: • G: generic template • C: component template

Returns

An instance of the NotificationTemplate class.

Example

```
import PT_WF_NOTIFICATION:*;

import PT_WF_WORKLIST:*;

Local NotificationTemplate &Notify_Temp;

/* create a generic template */

&Notify_Temp = Create NotificationTemplate("", "", "MyTemplate", "G");
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

NotificationTemplate Class

Worklist

Syntax

Worklist()

Description

Use the Worklist method to instantiate a Worklist object.

Parameters

None.

Returns

An instance of the Worklist class.

Example

The following example code creates a worklist.

```
import PT_WF_WORKLIST:*;

Local Worklist &theWorklist = Create Worklist();
```

Related Links

Worklist Class

WorklistEntry

Syntax

WorklistEntry()

Description

Use WorklistEntry to instantiate a WorklistEntry object.

Parameters

None.

Returns

An instance of the WorklistEntry class.

Example

```
import PT_WF_NOTIFICATION:*;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
import PT_WF_WORKLIST:*;

Local WorklistEntry &MyWorklistEntry = Create WorklistEntry();
```

Related Links

WorklistEntry Class

WSWorklistEntry

Syntax

WSWorklistEntry()

Description

Use the WSWorklistEntry constructor to instantiate a WSWorklistEntry object.

The WSWorklistEntry class is primarily used with web services.

Parameters

None.

Returns

A reference to a WSWorklistEntry object.

Related Links

WSWorklistEntry Class

Notification Class

This class is used to send a notification to people or people entities, as channel independent as possible. This enables functionality such as letting a user determine how to receive workflow notifications as a preference. It does not necessarily limit a person or entity to one channel.

See Notification Classes Examples.

See "Understanding Notification Templates" (PeopleTools 8.54: Workflow Technology).

Notification Class Import Statements

The Notification class imports the following classes:

- NotificationAddress
- WorklistEntry

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Here are the import statements:

```
import PT_WF_NOTIFICATION:NotificationAddress;

import PT_WF_WORKLIST:WorklistEntry;
```

Notification Class Method

In this section, we discuss the Notification class method Send.

Send

Syntax

```
Send()
```

Description

Use the Send method to send a notification to the entities defined in the NotifyTo, NotifyCC, and NotifyBCC, using the Subject and Message properties.

Parameters

None.

Returns

None.

Related Links

"Understanding PeopleSoft Workflow" (PeopleTools 8.54: Workflow Technology)

Notification Class Properties

In this section, we discuss the Notification class properties. The properties are discussed in alphabetical order.

ContentType

Description

This property returns the content type of the value specified by the Message property, as a string. This property is used only with email Notifications, that is, with SMTP email.

This property is read-write.

Related Links

Message

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

dttmCreated

Description

This property returns the date and time the notification was created as a DateTime value. Together with NotifyFrom this makes a notification unique.

Related Links

NotifyFrom

EmailReplyTo

Description

If an email is sent as a result of the Send method, this property returns the email reply that should be used, as a string. This property can have a different value from NotifyFrom. This property is valid only with notifications that have "email" specified as the channel.

This property is read-write.

Related Links

Send, NotifyFrom

FileNames

Description

This property returns an array of string, populated with the names of any file attachments sent with the notification. This property is valid only with notifications that have "email" specified as the channel.

This property is read-write.

FileTitles

Description

This property returns an array of string, populated with descriptions of any file attachments. The array order *must* be respective to the array order for FileNames, that is, file description matches file name one by using the same array index value. This property is valid only with notifications that have "email" specified as the channel.

This property is read-write.

Related Links

FileNames

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

language_cd

Description

This property returns the 3-character language code used for the notification, as a string. This is used for tracking purposes.

This property is read-write.

Message

Description

This property returns the text of the message sent with the notification as a string.

This property is read-write.

NotifyBCC

Description

This property returns an array of NotificationAddress objects, populated with the email addresses or worklist users of the people the notification is sent to. This list is used for notification information only, that is, the people on this list are generally not responsible for taking action specified by the notification. In addition, when you use the Notification Send method, other recipients cannot see the email addresses and or users that make up this array.

If you want to send a regular CC list, that is, one where the members of the list can see each other, use the NotifyCC property instead.

Related Links

NotifyCC

NotifyCC

Description

This property returns an array of NotificationAddress objects, populated with the email addresses of the people the notification is sent to. This list is used for notification information only, that is, the people on this list are generally not responsible for taking action specified by the notification. When using the Notification Send method, the email address or worklist users of this array are exposed to the recipients of the notification.

If you want to send a blind-CC list, that is, where the members of the list cannot see each other, use the NotifyBCC property instead.

Related Links

NotifyBCC

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

NotifyFrom

Description

This property returns the ID of the entity sending the notification as a string. For example, ad-hoc workflow uses the current user ID.

This property is read-write.

NotifyGuid

Description

This property returns the GUID of the notification. This is a unique identifier used for tracking purposes only.

This property is read-write.

NotifyTo

Description

This property returns an array of NotificationAddress objects, populated with the email addresses of the people the notification is sent to, and who are responsible for taking action if necessary.

To send the list to additional people, use the NotifyCC or NotifyBCC properties.

Related Links

NotifyCC, NotifyBCC

Rte

Description

Use this property to set or return a Boolean value indicating whether to use Rich Text formatting in the notification.

This property is read-write.

SourceComponent

Description

This property returns the name of the source component, that is, that initiated the notification process. This property is used for transaction tracking purposes only. This property is not required.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SourceMarket

Description

This property returns the name of the market of the source component, that is, that initiated the notification process. This property is used for transaction tracking purposes only. This property is not required.

This property is read-write.

SourceMenu

Description

This property returns the name of the menu of the source component, that is, that initiated the notification process. This property is used for transaction tracking purposes only. This property is not required.

This property is read-write.

Subject

Description

This property returns the subject used in the email notification as a string.

This property is read-write.

Template

Description

If the notification message originated from a template, this property returns the name of that template, as a string. This property is used for transaction tracking purposes only. This property is not required.

This property is read-write.

NotificationAddress Class

The main purpose of the NotificationAddress is to define an entity to a 'channel', it is concerned at a high level only that a notification was sent.

See Notification Classes Examples.

See "Understanding Notification Templates" (PeopleTools 8.54: Workflow Technology).

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

NotificationAddress Class Properties

In this section, we discuss the NotificationAddress class properties. The properties are discussed in alphabetical order.

Channel

Description

This property returns the 'channel' used for the notification, as a string. The values are:

Value	*Description*
Email	Notification is sent as email.
Worklist	Notification is sent as a worklist.

This property is read-write.

Description

Description

This property returns the description of the entity as a string. Entity descriptions include distribution group names or people's names.

This property is read-write.

EmailId

Description

This property returns the Email Address of the entity to be notified.

This property is read-write.

Language

Description

This property returns the language code of the entity to be notified.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Oprid

Description

This property returns the user ID of the person receiving the notification as a string.

This property is read-write.

NotificationTemplate Class

This class is useful for populating the message property of the Notification class.

See "Understanding Notification Templates" (PeopleTools 8.54: Workflow Technology).

NotificationTemplate Class Methods

In this section, we discuss the NotificationTemplate class methods. The methods are discussed in alphabetical order.

GetAndExpandTemplate

Syntax

GetAndExpandTemplate(*Language*, *Vars*)

Description

Use the GetAndExpandTemplate method to expand and map the variables into the Text property of the template.

If this is a component template, you must use the SetupCompVarsAndRcpts method first, before you use this method.

If this is a generic template, you must use the SetupGenericVars method first, before you use this method.

The value returned by the Setup methods must be used as the second parameter for this method.

Parameters

Language	Specify the 3-character language code used with the notification.
Vars	Specify the variable representing the XML string returned by either the SetupCompVarsAndRcpts method or the SetupGenericVars method.

Returns

Returns a Boolean value: True if the template expanded properly, False otherwise.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

```
import PT_WF_NOTIFICATION:NotificationTemplate;

Local NotificationTemplate & mynotifytemplate;

&mynotifytemplate = create NotificationTemplate(%Component, %Market, &templateName,⇒
 "C");

&xmlVars = &mynotifytemplate.SetupCompVarsAndRcpts(GetLevel0());

&mynotifytemplate.GetAndExpandTemplate(%Language, &xmlVars);
```

Related Links

SetupCompVarsAndRcpts
SetupGenericVars

SetupCompVarsAndRcpts

Syntax

SetupCompVarsAndRcpts(*&Rowset_Context*)

Description

Use the SetupCompVarsAndRcpts method to set up variables for the component from the provided rowset. This method also sets up any additional recipients defined in the component.

The rowset corresponds to the component that the notification template was instantiated with. For example, if you created a notification template for JOB, the rowset used with this method should be based on the JOB component.

If you want to expand a component template, you must use this method first, before expanding the template.

Parameters

&Rowset_Context	Specify an already instantiated and populated rowset containing the necessary variables.

Returns

A string containing XML that is used by the GetAndExpandTemplate method.

Example

```
import PT_WF_NOTIFICATION:NotificationTemplate;

Local NotificationTemplate & mynotifytemplate;

&mynotifytemplate = create NotificationTemplate(%Component, %Market, &templateName,⇒
 "C");

&xmlVars = &mynotifytemplate.SetupCompVarsAndRcpts(GetLevel0());

&mynotifytemplate.GetAndExpandTemplate(%Language, &xmlVars);
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

GetAndExpandTemplate

SetupGenericVars

Syntax

SetupGenericVars(*&AryValues*)

Description

Use the SetupGenericVars method to pass values to a generic template.

To expand a generic template, you must use this method first, before expanding the template.

Parameters

&AryValues	Specify an array of string containing values used with the expanded template.

Returns

A string containing XML that is used by the GetAndExpandTemplate method.

Example

```
import PT_WF_NOTIFICATION:NotificationTemplate;

. . .

&mynotifytemplate = create NotificationTemplate("","", "MYTEMPLATE", "G");

/* Populate an array to contain the values needed by */
/* the template */
&aryValues = CreateArrayRept("", 0);
&aryValues.Push("FIRST VALUE");
&aryValues.Push("SECOND VALUE");
&xmlVars = &mynotifytemplate.SetupGenericVars(&aryValues);
&mynotifytemplate.GetAndExpandTemplate(%Language, &xmlVars);
```

Related Links

GetAndExpandTemplate

NotificationTemplate Class Properties

In this section, we discuss the NotificationTemplate class properties. The properties are discussed in alphabetical order.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ComponentId

Description

This property returns a component for the component type notification template as a string. This is not required for generic templates.

This property is read-write.

Instruction

Description

This property returns the notification instructions as a string.

This property is read-write.

Language

Description

This property returns the language used to retrieve template descriptions, as a string.

This property is read-write.

Market

Description

This property returns the market for component type notification templates as a string. This is not required for generic templates.

This property is read-write.

Priority

Description

This property returns the priority of the notification template as a string.

This property is read-write.

Responses

Description

This property is populated only if there are any RIMM responses.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Subject

Description

This property returns the subject of the notification template as a string.

This property is read-write.

TemplateId

Description

This property returns the template ID as a string. If you are creating a notification template, this property is always required.

This property is read-write.

TemplateType

Description

This property returns the template type as a string. Values are:

Value	*Description*
C	Component
G	Generic

If you are creating a notification template, this property is always required.

This property is read-write.

Text

Description

This property returns the Template Text as a string.

This property is read-write.

Worklist Class

The Worklist class is used to make mass modifications to worklist instances. Modifications to one worklist instance should be performed through the WorklistEntry class.

See Worklist.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Worklist Class Method

In this section, we discuss the Worklist class method Reassign.

Reassign

Syntax

Reassign(*FromOperid, ToOperid*)

Description

Use the Reassign method to reassign all worklist items with a state less than “Worked” from one user to another.

If you only want to reassign a single worklist entry, use the Reassign WorklistEntry class method.

Parameters

FromOperid	Specify the user ID of the user from which you want to assign a worklist, as a string.
ToOperid	Specify the user ID of the user to which you want to assign a worklist, as a string.

Returns

A Boolean value: true if worklist was assigned successfully, false otherwise.

Related Links

Reassign

WorklistEntry Class

This class is used to create and or update a worklist entry.

See Creating a WorklistEntry.

See Updating a WorklistEntry.

See "Understanding PeopleSoft Workflow" (PeopleTools 8.54: Workflow Technology).

WorklistEntry Class Methods

In this section, we discuss the WorklistEntry class methods. The methods are discussed in alphabetical order.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Create

Syntax

Create()

Description

Use the Create method to create a new WorklistEntry object.

This method is *not* the same as the Create *constructor*. The Create constructor only creates an instance of the WorklistEntry class. To add the entry to the database, you must use this method.

The following properties must be set before calling this method:

- busactivity
- buseventname
- busprocname
- worklist

If this method completes successfully, the following properties are populated:

- instanceid
- transactionid

Parameters

None.

Returns

This method returns a numeric value: 0 if there is an error, nonzero if entry created successfully.

Example

```
import PT_WF_WORKLIST:*;

Local WorklistEntry &worklist;
Local Number &Rslt;

&worklist = create WorklistEntry();

&worklist.busprocname  = "Administer Workflow";
&worklist.busactivity  = "Send Note";
&worklist.buseventname = "Worklist Note";
&worklist.worklistname = "Worklist Note";

&Rslt = &worklist.Create();
```

Related Links

busactivity

buseventname

busprocname

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

instanceid
transactionid

GetResponseStatus

Syntax

```
GetResponseStatus()
```

Description

Use the GetResponseStatus method to return the response status of the callback method. This is useful only for entries that are created by web services.

The following properties must be set before calling this method:

- busactivity
- buseventname
- busprocname
- requestmessageid
- worklistname

Parameters

None.

Returns

A number. Valid values are:

Value	*Description*
0	CreateWorklistEntry message not received yet or this entry was not created by any web service.
1	Message received but not processed yet.
2	Message processed and sent to message queue.
3	Error while sending message to the caller of create worklist entry.
4	Message was sent to the originating web server and was received successfully.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Reassign

Syntax

Reassign(*Operid*)

Description

The Reassign method assigns the worklist in the data buffers to the user specified by *Operid*. This method commits the version of the worklist entry in the data buffer to the database using the Save method.

If you want to reassign an entire worklist, use the Reassign Worklist class method.

Note: You must use the SelectByKey method to populate data buffers with the worklist entry.

Parameters

Operid Specify the user ID to which you want to assign the worklist entry, as a string.

Returns

A Boolean value: true if the reassignment was successful, false otherwise.

Example

```
import PT_WF_WORKLIST:WorklistEntry;

       Local WorklistEntry &wl = create WorklistEntry();
       &wl.busprocname = WF_WORKLIST_VW2.BUSPROCNAME;
       &wl.busactivity = WF_WORKLIST_VW2.ACTIVITYNAME;
       &wl.buseventname = WF_WORKLIST_VW2.EVENTNAME;
       &wl.worklistname = WF_WORKLIST_VW2.WORKLISTNAME;
       &wl.instanceid = WF_WORKLIST_VW2.INSTANCEID;

       If (&wl.SelectByKey()) Then
          If Not (&wl.Reassign("TOPSUSER2")) Then
             /* Reassign error */
          End-If;
       Else
          /* SelectByKey error */
       End-If;
```

Related Links

Reassign

Save

Syntax

Save()

Description

Use the Save method to save a WorklistEntry to the database.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

PeopleCode Event Considerations

You must include this method within events that allow database updates. This includes the following PeopleCode events:

- SavePreChange (Page)
- SavePostChange (Page)
- Workflow
- FieldChange

If this method results in a failure, all database updates are rolled back. All information the user entered into the component is lost, as if the user pressed ESC.

Considerations Using Web Services

This method saves the instance of the worklist to the database. If the worklist entry is marked as worked, (that is, if inststatus property is set to 2) and the worklist entry was originally created by a web service, the originating requestor is sent a response when this method is executed. If the requestor is expecting additional data, use the SaveWithCustomData method instead.

Parameters

None.

Returns

A numeric value: 0 if save didn't complete successfully, nonzero if save completed successfully.

Example

```
If (&worklist.Save() <> 0) Then
   /* success */
Else
   /* handle error */
End-If;
```

Related Links

Update
SaveWithCustomData
inststatus

SaveWithCustomData

Syntax

SaveWithCustomData(*&Message*, *&FieldNameArray*, *&FieldValueArray*)

Description

Use the SaveWithCustomData method to save the worklist entry to the database, as well as to pass additional data back to the requestor that created this worklist entry. You should only use this method with

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

worklist entries that are created by web service. If you want to save a worklist entry without additional data, or a worklist entry that was not created using a web service, use the Save method instead.

If the worklist entry was not created by a web service, or if the worklist entry is not marked as worked (that is, if the inststatus property is not set to 2,) the additional data is ignored.

PeopleCode Event Considerations

You must include this method within events that allow database updates. This includes the following PeopleCode events:

- SavePreChange (Page)
- SavePostChange (Page)
- Workflow
- Message Subscription (the Integration Broker INotificationHandler interface)
- FieldChange

If this method results in a failure, all database updates are rolled back. All information the user entered into the component is lost, as if the user pressed ESC.

Parameters

&Message	Specify an already instantiated and populated response message containing the custom data to be sent back to the originating web service.
&FieldNameArray	Specify an already instantiated and populated array of string containing the field names to be used by the web service that created the worklist entry.
&FieldValueArray	Specify an already instantiated and populated array of string containing matching field values to be used by the web service that created the worklist entry.

Returns

A message object containing the final message that was sent to the web service if successful, a null object otherwise.

Related Links

Save
inststatus

SelectByKey

Syntax

`SelectByKey``()`

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

The SelectByKey method uses the key field values that have been assigned to build and execute a Select SQL statement. The field values are then fetched from the database SQL table into the worklist entry and the Select statement is closed.

If you don’t specify all the key fields, those you exclude are added to the Where clause with the condition equal to a blank value. If not all keys are set and more than one row is retrieved, you won't receive an error and SelectByKey won’t fetch any data.

For worklist entries that were created by web services, use the SelectByMessageId method instead.

Parameters

None.

Returns

A Boolean value: true if the properties are set based on the database values, false otherwise.

Related Links

SelectByMessageId

SelectByMessageId

Syntax

```
SelectByMessageId()
```

Description

Use the SelectByMessageId method to select a worklist entry by the message id. This is useful only for entries that are created by web services.

The following properties must be set before calling this method:

- busactivity
- buseventname
- busprocname
- requestmessageid
- worklistname

Parameters

None.

Returns

A Boolean value: true if this method completes successfully, false otherwise.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

SelectByKey

Update

Syntax

Update()

Description

Use the Update method to update the worklist entry with any property values that have changed, and assign values to the associated record in the database. However, this method does not commit the changes to the record in the database. You must use the Save method to update the database.

Parameters

None.

Returns

A numeric value: 0 if update didn't complete successfully, nonzero if update completed successfully.

Example

```
If (&worklist.Update() <> 0) Then
   &worklist.inststatus = "2"  /* mark entry worked */
   /* additional processing */
End-if;
```

Related Links

Save

WorklistEntry Class Properties

In this section, we discuss the WorklistEntry class properties. The properties are discussed in alphabetical order.

actiondttm

Description

This property returns the Worklist action date and time as a DateTime value.

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

busactivity

Description

This property returns the source activity name of the source business process as a string.

This property is read-write.

buseventname

Description

This property returns the source event name of the source activity as a string.

This property is read-write.

busprocname

Description

This property returns the source business process name as a string.

This property is read-write.

commentshort

Description

This property returns the short comment the previous user ID gave when reassigning a worklist as a string.

This property is read-write.

do_replicate_flag

Description

This property returns a flag that indicates if the worklist entry must be replicated. Values are:

Value	*Description*
Y	Worklist entry needs to be replicated
N	Worklist entry does not need to be replicated

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

instanceid

Description

This property returns the Instance Id. This property is used with the following properties to make the worklist entry a unique number:

- busprocname
- busactivity
- buseventname
- worklistname

This property is read-write.

instselecteddttm

Description

This property returns the date and time that the worklist was selected to be worked as a DateTime value.

This property is read-write.

inststatus

Description

This property returns the Worklist Entry status as a string. The values are:

Value	*Description*
0	new worklist entry
1	selected worklist entry
2	worked worklist entry
3	cancel string

This property is read-write.

insttimeoutddttm

Description

This property returns the date and time the worklist entry timed out as a DateTime value. Only some worklist types use this property.

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

instworkeddttm

Description

This property returns the date and time the worklist was worked as a DateTime value.

This property is read-write.

IsCreatedViaWebService

Description

This property returns a Boolean value: true if the WorklistEntry object was created from a web service, false otherwise.

This property is read-only.

oprid

Description

This property returns the user ID that is assigned the worklist as a string.

This property is read-write.

originatorid

Description

This property returns the user ID that caused the worklist to be created as a string.

This property is read-only.

prevoprid

Description

This property returns the previous user ID who used this worklist entry as a string.

This property is read-write.

requestmessageid

Description

This property is used with worklist entries that are created by web services. It contains the original message ID from the requesting party.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ResponseStatus

Description

This property returns the status of the response sent to the originating web service.

Valid values are:

Value	*Description*
0	CreateWorklistEntry message not received yet or this entry was not created by any web service.
1	Message received but not processed yet.
2	Message processed and sent to message queue.
3	Error while sending message to the caller of create worklist entry.
4	Message was sent to the originating web server and was received successfully.

This property is read-write.

syncid

Description

This property is reserved for future use.

This property is read-write.

timedout

Description

This property returns the status flag if the worklist has timed out. Values are:

Value	*Description*
Y	Worklist has timed out
N	Worklist has not timed out

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

transactionid

Description

This property returns the transaction Id as a number, which represents the unit of work. This can be useful for pooled worklists.

This property is read-write.

url

Description

This property returns the URL to work for the worklist as a string. This is used only for replicating worklist entries across PeopleSoft databases.

This property is read-write.

wl_priority

Description

This property returns the priority of the worklist as a string. The values are:

Value	*Description*
low	Worklist has low priority.
medium	Worklist has medium priority.
high	Worklist has high priority.

This property is read-write.

wldaystoselect

Description

This property returns the number of days to select worklist as a number.

This property is read-write.

wldaystowork

Description

This property returns the number of days to work the worklist as a number.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

worklistname

Description

This property returns the source worklist name for the source event string as a string.

This property is read-write.

WSWorklistEntry Class

This class is used by web services to create Worklist entries.

This class implements the Integration Broker class IRequestHandler.

Related Links

"Understanding Sending and Receiving Messages" (PeopleTools 8.54: Integration Broker)

WSWorklistEntry Class Methods

The following are the WSWorklistEntry class methods, in alphabetical order.

OnError

Syntax

OnError(*&Message*)

Description

Use the OnError method to do error handling. This method implements the Integration Broker IRequestHandler interface OnError method.

Parameters

&Message	Specify an already instantiated and populated message object. This would normally be the message that was used to generate the worklist entry from the web service.

Returns

Depends on implementation.

Related Links

Understanding Message Classes

Understanding theSOAPDoc Class

"Understanding Sending and Receiving Messages" (PeopleTools 8.54: Integration Broker)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

OnNotify

Syntax

OnNotify(*&Message*)

Description

Use the OnNotify method to creates the worklist entry and the application worklist record.

This method implements the Integration Broker INotificationHandler interface OnNotify method.

Parameters

&Message	Specify an already instantiated and populated message object. Generally this would be the originating message that created the worklist entry.

Returns

None.

Related Links

"Understanding Sending and Receiving Messages" (PeopleTools 8.54: Integration Broker)

WSWorklistEntry Class Properties

The following describes the WSWorklistEntry class properties, in alphabetical order.

InstanceID

Description

This property returns the instance ID for the worklist entry, as a string.

This property is read-only.

TransactionID

Description

This property returns the transaction ID for the worklist entry, as a string.

This property is read-only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Notification Classes Examples

The following are example of typical actions you perform using the notification classes.

See "Understanding Notification Templates" (PeopleTools 8.54: Workflow Technology).

Creating a WorklistEntry

The following example creates a WorklistEntry.

The following is the complete code sample: the steps explain each line.

```
import PT_WF_WORKLIST:*;

Local WorklistEntry &worklist;

&worklist = create WorklistEntry();

&worklist.busprocname  = "Administer Workflow";
&worklist.busactivity  = "Send Note";
&worklist.buseventname = "Worklist Note";
&worklist.worklistname = "Worklist Note";

If (&worklist.Create() <> 0) Then
   &worklist.oprid = %UserId;
Else
   /* handle error */
End-If;

If (&worklist.Save() <> 0) Then
   /* success, create a corresponding row in */
   /* application worklist record... */
Else
   /* handle error */
End-If;
```

To create a WorklistEntry:

1. Import the WorklistEntry class.

   You must import the WorklistEntry class before you can use it in your PeopleCode program. In addition, the second line declares the variable &worklist as type WorklistEntry.

   ```
   import PT_WF_WORKLIST:*;

   Local WorklistEntry &worklist;
   ```

2. Instantiate a WorklistEntry object.

   Using the constructor, create an instance of the WorklistEntry class. This does *not* create a WorklistEntry. This creates a WorklistEntry object only. You must use the Create method to actually create the WorklistEntry in the system.

   ```
   &worklist = create WorklistEntry();
   ```

3. Set the required parameters.

   Some of the WorklistEntry class properties are required for every WorklistEntry. You must set a value for these properties before you can update or save the WorklistEntry.

   ```
   &worklist.busprocname  = "Administer Workflow";
   ```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
&worklist.busactivity  = "Send Note";
&worklist.buseventname = "Worklist Note";
&worklist.worklistname = "Worklist Note";
```

4. Create the WorklistEntry.

   After you've set the required values, you need to create the WorklistEntry in the system. This does *not* update the database. This does, however, add values to the notification tables.

   If this method completes successfully, the following properties are populated: instanceid and transactionid.

   - instanceid
   - transactionid

```
If (&worklist.Create() <> 0) Then
   &worklist.oprid = %Userid;
Else
   /* handle error */
End-If;
```

5. Save the WorklistEntry.

   After you've created the WorklistEntry, save it. The Save method actually updates the database, and so can be used only in events that allow database updates.

```
If (&worklist.Save() <> 0) Then
   /* success, create a corresponding row in */
   /* application worklist record... */
Else
   /* handle error */
End-If;
```

Updating a WorklistEntry

The following example updates a WorklistEntry so that it is considered worked.

The following is the complete code sample: the steps explain each line.

```
import PT_WF_WORKLIST:*;

Local WorklistEntry &worklist;

&worklist = create WorklistEntry();
&worklist.busprocname = "Administer Workflow";
&worklist.busactivity = "Send Note";
&worklist.buseventname = "Worklist Note";
&worklist.worklistname = "Worklist Note";
&worklist.instanceid = 2;

&ret = &worklist.SelectByKey();

&worklist.inststatus = "2"; /* mark entry worked */
If (&worklist.Update() <> 0) Then
   If (&worklist.Save() <> 0) Then
      /* success */
   Else
      /* handle error */
   End-If;
Else
   /* handle error */
End-If;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

To update a WorklistEntry:

1. Import the WorklistEntry class.

   You must import the WorklistEntry class before you can use it in your PeopleCode program. In addition, the second line declares the variable &worklist as type WorklistEntry.

   ```
   import PT_WF_WORKLIST:*;

   Local WorklistEntry &worklist;
   ```

2. Instantiate a WorklistEntry object.

   Using the constructor, create an instance of the WorklistEntry class. This does *not* create a WorklistEntry. This creates a WorklistEntry object only. You must use the Create method to actually create the WorklistEntry in the database tables, and the Save method to update the tables.

   ```
   &worklist = create WorklistEntry();
   ```

3. Set the required parameters.

   Some of the WorklistEntry class properties are required for every WorklistEntry. You must set a value for these properties before you can update or save the WorklistEntry. The instanceid property, combined with the other properties, indicates a unique WorklistEntry. This value is populated after a WorklistEntry has already been created.

   ```
   &worklist.busprocname  = "Administer Workflow";
   &worklist.busactivity  = "Send Note";
   &worklist.buseventname = "Worklist Note";
   &worklist.worklistname = "Worklist Note";
   &worklist.instanceid = 2;
   ```

4. Populate the worklist entry with data.

   After you've set the keys, populate the worklist entry based on those keys using the SelectByKey method.

   ```
   &ret = &worklist.SelectByKey();
   ```

5. Update and save the WorklistEntry.

   After you've set the required parameters, try to update the WorklistEntry. If that is successful, mark the WorklistEntry as 'worked', and try to save the WorklistEntry. The Save method actually updates the database, and so can be used only in events that allow database updates.

   ```
   If (&worklist.Update() <> 0) Then
      &worklist.inststatus = "2"  /* mark entry worked */
      If (&worklist.Save() <> 0) Then
         /* success */
      Else
         /* handle error */
      End-If;
   Else
         /* handle error */
   End-if;
   ```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Chapter 31

Optimization PeopleCode

Using Optimization PeopleCode on the Application Server

While running optimization PeopleCode on the application server, ensure that changed data is committed to the database before calling the CreateOptEngine optimization function and the following OptEngine class methods:

- RunSynch
- RunAsynch
- CheckOptEngineStatus
- ShutDown
- SetTraceLevel
- GetTraceLevel
- InsertOptProbInst
- DeleteOptProbInst

Note: The PeopleCode functions CommitWork and DoSaveNow can be called within a step to save uncommitted data to the database before calling the listed functions and methods. Keep in mind that forcing a commit on pending database updates is a serious step; it prevents roll-back on error. CreateOptEngine, ShutDown, InsertOptProbInst, and DeleteOptProbInst calls modify the database, so take care when terminating the Application Engine program without committing the changes made by those calls.

Using Optimization PeopleCode in an Application Engine Program

When you write an optimization PeopleCode program in an Application Engine program and you schedule it in PeopleSoft Process Scheduler, you must set the process definition with a process type of *Optimization Engine.* Other process types do not allow optimization PeopleCode in Application Engine programs.

While using optimization PeopleCode in Application Engine programs, make sure data is committed before calling the CreateOptEngine optimization function and the following OptEngine class methods:

- RunSynch
- RunAsynch
- CheckOptEngineStatus

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- ShutDown
- SetTraceLevel
- GetTraceLevel
- InsertOptProbInst
- DeleteOptProbInst

Note: You can call the PeopleCode functions CommitWork and DoSaveNow within a step to save uncommitted data to the database before calling the listed functions and class methods. Keep in mind that forcing a commit on pending database updates is a serious step; it prevents roll-back on error. CreateOptEngine, ShutDown, InsertOptProbInst, and DeleteOptProbInst calls modify the database, so take care when terminating the Application Engine program without committing the changes made by those calls.

Performing Optimization in PeopleCode

This section discusses how to:

- Create new analytic instances.
- Load analytic instances into an analytic server.
- Run optimization transactions.
- Invoke the Optimization PeopleCode plug-in.
- Shut down optimization engines.
- Delete existing analytic instances.
- Program for database updates.

Important! The optimization PeopleCode classes are not supported on IBM z/OS and Linux for IBM System z platforms.

Creating New Analytic Instances

To create a new analytic instance for an analytic type:

1. Call the function InsertOptProbInst with the analytic type and analytic instance as parameters to create an analytic instance ID.
2. Use Application Engine or a similar mechanism to load the optimization application tables with data.

   Use the analytic instance ID as the key value in scenario-managed optimization application tables.

   The analytic instance is now ready to be loaded into an analytic server.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Note: You can load multiple copies of the same analytic instance into multiple instances of an analytic server, provided that each instance of the analytic server resides in a different application server domain. Each analytic instance loaded into a given domain must be unique. Within a given domain, you cannot have the same analytic instance in more than one analytic server. The analytic server maintains data integrity by checking to see if the data has been altered by another user (refer to the steps in the optimization system architecture description). Try to maintain data consistency when the same analytic instance uses the same database in different domains.

Related Links

"PeopleSoft Optimization Framework System Architecture" (PeopleTools 8.54: Optimization Framework)

InsertOptProbInst

Loading Analytic Instances Into an Analytic Server

Use the CreateOptEngine function to load an analytic server with an analytic instance. It takes analytic instance ID and a mode parameter with *%Synch* and *%Asynch* as possible values and returns a PeopleCode object of type *OptEngine.*

You can run the PeopleCode on the application server or from Application Engine.

Loading Analytic Instances by Running PeopleCode on the Application Server

To block PeopleCode from running on the application server until the load is done (synchronous mode), use the *%Synch* value for the mode parameter. An error is generated if the load isn't successful. The application server imposes a timeout beyond which the PeopleCode and optimization engine load are terminated. Here is a code example:

```
Local OptEngine &myopt;
&myopt = CreateOptEngine("PATSMITH", %Synch);
```

To load the analytic server without blocking the PeopleCode from running (asynchronous mode) on the application server, use the *%Asynch* value for the mode parameter. The analytic server performs a preliminary check of the load request and returns the OptEngine object if it is successful or an error if it is unsuccessful. A successful return does not mean that the load was successful. You must then use repeated CheckOptEngineStatus methods on the returned OptEngine object to determine whether the analytic engine is done with the load and whether it was successful. Here is a code example:

```
Local OptEngine &myopt;
&myopt = CreateOptEngine("PATSMITH", %Asynch);
```

Loading Analytic Instances by Running PeopleCode in Application Engine

Both synchronous *(%Synch)* and asynchronous *(%Asynch)* modes block the PeopleCode from running on Application Engine until the load is done. Use only *%Asynch* while loading an optimization engine.

The absolute number of optimization engine instances that may be loaded in a given domain is governed by a configuration file loaded by Tuxedo during its domain startup.

Related Links

CheckOptEngineStatus

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Running Optimization Transactions

You send an optimization transaction to the optimization engine using the RunSynch and RunAsynch methods. Both are methods on an OptEngine object. The OptEngine object can be created either by calling CreateOptEngine (if the optimization engine is not loaded already) or by calling GetOptEngine (if the optimization engine is already loaded). Both RunSynch and RunAsynch have the same signature, except that RunSynch runs the optimization transaction in synchronous mode and RunAsynch runs it in asynchronous mode. Both return an integer status code. You can run transactions either on the application server or with Application Engine.

To invoke an optimization transaction:

1. Use the GetOptEngine function to get the OptEngine object as a handle for the optimization engine that has loaded an analytic instance ID.

   Use the CreateOptEngine function to create the OptEngine object for a new optimization engine if the analytic instance has not been loaded.

2. Call RunSynch or RunAsynch to send an optimization transaction to the optimization engine to be run in synchronous or asynchronous mode.

3. If the transaction is run in synchronous mode (RunSynch), use the OptEngine methods GetString, GetNumber, and so on, to retrieve the output result from the optimization transaction.

   The transaction names, parameter names, and data types are viewable in the analytic type in Application Designer.

4. If the transaction is run in asynchronous mode, use the OptEngine method CheckOptEngineStatus to check the status of the optimization transaction in the optimization engine.

   After the transaction is done, result data is available in the database for retrieval using standard PeopleCode mechanisms.

Running Optimization Transactions from the Application Server

To block the PeopleCode from running on the application server until the optimization transaction is done (synchronous mode) and receives the results, use RunSynch to send an optimization transaction. An error status code is returned if the transaction isn't successful. If successful, you can use other methods to retrieve the results from the transaction call. The application server imposes a timeout beyond which the PeopleCode and optimization engine transaction are terminated.

To run a transaction without blocking PeopleCode from running (asynchronous mode) on the application server, use RunAsynch to send an optimization transaction. In this mode, the optimization engine performs a preliminary check of the transaction request and returns a success or failure status code. A successful return does not mean that the transaction is successful; it means only that the syntax is correct. You must then use repeated calls to the CheckOptEngineStatus method on the OptEngine object to determine whether the optimization engine is done with the transaction and whether it is successful.

RunAsynch does not allow transaction output results to be returned. Use this method for long-running transactions that return results entirely through the database.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Running Optimization Transactions from Application Engine

Both synchronous (RunSynch) and asynchronous (RunAsynch) methods block the PeopleCode from running on Application Engine until the optimization transaction is done. RunSynch allows output results to be returned, but it should be used for transactions that are fast (less than 10 seconds). RunAsynch does not have a time limit, but it does not return output results.

Related Links

RunAsynch

Invoking the Optimization PeopleCode Plug-In

If you're developing an optimization application that uses the Optimization PeopleCode plug-in, you must do the following to invoke the plug-in:

- Develop a PeopleCode application class that extends the PT_OPT_BASE:OptBase class.
- Define methods in your application class that use the PeopleCode OptInterface class to perform your optimization functions.
- Define an analytic type that specifies the Optimization PeopleCode plug-in, by selecting the PeopleCode Plugin check box in the analytic type properties.
- In the analytic type properties, specify the application package and application class that you developed.
- Define transactions in your analytic type definition that correspond to the methods you developed in your application class, with corresponding parameters.

Related Links

"Creating Analytic Type Definitions" (PeopleTools 8.54: Optimization Framework)

CreateOptInterface

OptBase Application Class

OptInterface Class Methods

Shutting Down Optimization Engines

Use the GetOptEngine function to get the OptEngine object as a handle for the optimization engine that loaded an analytic instance ID.

Use the OptEngine method named ShutDown to shut down the optimization engine. This ends the optimization engine process with the current analytic instance ID. Based on application server settings, the system restarts a new, unloaded optimization engine process that can be loaded with any other analytic instance.

Related Links

ShutDown

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Deleting Existing Analytic Instances

To delete an existing analytic instance for an analytic type:

1. Shut down any optimization engines that have this analytic instance currently loaded.
2. Using Application Engine or a similar mechanism, delete the data in the optimization application tables pertaining to that analytic instance.

   Use the analytic instance ID as the key value to find and delete analytic instance rows from scenario-managed optimization application tables.
3. Use the function DeleteOptProbInst with the analytic type and analytic instance as arguments to delete the analytic instance ID from PeopleTools metadata.

Note: If you try to delete an existing analytic instance that is loaded in a running optimization engine, DeleteOptProbInst returns *%OptEng_Fail,* and the optional status reference parameter is set to *%OptEng_Exists.*

Related Links

DeleteOptProbInst

Programming for Database Updates

You must plan for uncommitted database changes in your optimization PeopleCode. The PeopleSoft Optimization Framework detects pending database updates, and generates a failure status if data is not committed to the database before certain optimization methods are called.

This checking for database updates happens in runtime for the CreateOptEngine function and the following methods: RunSync, RunAsync, Shutdown, GetTraceLevel, and SetTraceLevel. Ensure that your PeopleCode performs proper database updates and commits before you execute these methods. If you use the optional parameter for detailed status that is available for these functions, or the DetailedStatus property that is available for the methods, you can check for the status of %OptEng_DB_Updates_Pending to see if there is a pending database update.

Note: The pending database update may have happened considerably earlier in the code. Forcing a commit within your PeopleCode to avoid this problem prevents roll-back on database error. Forcing a commit should be used with care.

The InsertOptProbInst and DeleteOptProbInst functions can be called only inside FieldChange, PreSaveChange and PostSaveChange PeopleCode events, and in Workflow.

This database update checking happens in compile time for the following functions: InsertOptProbInst and DeleteOptProbInst. Make sure that there are no pending database updates before you execute these methods.

Using Lights-Out Mode with Optimization

This section provides an overview of lights-out mode, and discusses how to:

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- Create a request message.
- Create a response message.
- Edit the request PeopleCode.
- Edit the response PeopleCode.

Understanding Lights-out Mode

Some optimization applications can take several hours to run. These are typically run as overnight batch jobs every night when the work load is small to regenerate the optimization solution and have it ready for end users to use in the morning hence the term *lights-out mode.*

In the current release, application messages communicate between the Application Engine batch job and the online optimization engine. After the Application Engine job completes and the optimization solution has been written to the database, an application message initiates the download of the data from the database batch job to the online optimization engine.

Lights-out mode uses an Application Engine PeopleCode program within PeopleSoft Process Scheduler to send requests to an application server and receive responses from it. Within the application server, the OnRequest PeopleCode runs an optimization engine process.

Image: Lights-out process

This diagram illustrates the lights-out process:

This request and response is in the form of a rowset as shown by the example supplied with optimization, the OPT_CALL message. Also supplied as an example is an Application Engine message publish PeopleCode program called PT_OPTCALL.

Important! Application Engine includes an action of type *Log Message.* which PeopleSoft Process Scheduler uses to record its activity in the PS_MESSAGE_LOG table. The PeopleCode MessageBox and WinMessage built-in functions also record their activity in the PS_MESSAGE_LOG table.
During lights-out optimization, these processes can conflict with each other or with the optimization engine when one process locks a row of the table, and another process tries to access the same row.
To prevent this conflict, pay close attention to where the MessageBox or WinMessage built-in functions are used in your Application Engine PeopleCode. In general, there can't be any outstanding database updates pending when communicating with the optimization engine using application messages.

The OPT_CALL Message

The OPT_CALL message is an example of what the lights-out process uses as the message for optimization. The OPT_CALL message has a structure using a record, PT_OPTPARMS, having the fields PARMKEY and VALUE which represent a name/value pair. These send requests and responses from the

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Application Engine PeopleCode in PeopleSoft Process Scheduler to and from the message OnRequest PeopleCode in the application server.

The OPT_CALL message also uses a record, PT_OPTDETMSGS, which contains the information needed for processing a detailed message.

This is an example of the Message Definition page (select PeopleTools, Integration Broker, Integration Setup, Messages) showing the OPT_CALL message definition:

Image: Message Definition page – OPT_CALL message definition

This example illustrates the fields and controls on the Message Definition page – OPT_CALL message definition. You can find definitions for the fields and controls later on this page.

The OPT_CALL message is associated with the OPT_CALL service operation. The OPT_CALL service operation defines the OPT_CALL application package as a handler. This application package implements the Integration Broker methods needed to handle any messaging PeopleCode.

Creating a Request Message

This section provides an overview of the request message and describes how to create messages that:

- Create an optimization engine.
- Check optimization engine status.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- Run an optimization engine transaction.
- Set the trace level.
- Get the trace level.
- Shutdown an optimization engine.

Understanding the Request Message

For optimization, the Application Engine PeopleCode in PeopleSoft Process Scheduler sends a request OPT_CALL message. The message uses rowsets built from PT_OPTPARMS records as the request. You can use the following rowset structures as an example of how to perform certain optimization actions, by sending them as requests from the application engine program in the process scheduler to the message notification PeopleCode in the application server.

Creating an Optimization Engine

To create an optimization engine, structure the rowset as follows, using the PT_OPTPARMS record. You set key values using the PARMKEY field, and then set a value for that key field in the VALUE field.

PARMKEY Field	***VALUE Field***
OPTCMD	CREATE Causes the PeopleCode program implementing the Integration Broker OnRequest method to load an optimization engine. The OPT_CALL example executes the CreateOptEngine function.
PROBINST	The name of the analytic instance.
PROCINSTANCE	The name of the process instance for this process scheduler job.
SYNCH	*Y* if this optimization engine load is to occur synchronously, *N* if asynchronously.

Checking Optimization Engine Status

To check optimization engine status (for example, to see when it finishes loading), structure the rowset as follows, using the PT_OPTPARMS record.

PARMKEY Field	***VALUE Field***
OPTCMD	CHECK_STATUS Causes the PeopleCode program implementing the Integration Broker OnRequest method to check the status of an optimization engine. The OPT_CALL example executes the CheckOptEngineStatus function.
PROBINST	The name of the analytic instance.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

PARMKEY Field	*VALUE Field*
PROCINSTANCE	The name of the process instance for this process scheduler job.

Running a Transaction

To run a transaction, structure the rowset as follows, using the PT_OPTPARMS record.

PARMKEY Field	*VALUE Field*
OPTCMD	RUN Causes the PeopleCode program implementing the Integration Broker OnRequest method to run an optimization transaction. The OPT_CALL example executes the GetOptEngine method and either the RunSynch or RunAsynch method.
PROBINST	The name of the analytic instance.
PROCINSTANCE	The name of the process instance for this process scheduler job.
SYNCH	*Y* for a synchronous transaction, *N* for asynchronous.
TRANSACTION	The name of the transaction to run.
The names of one or more transaction parameters.	The value of each named transaction parameter.

Setting the Trace Level

To set a trace level, structure the rowset as follows, using the PT_OPTPARMS record.

PARMKEY Field	*VALUE Field*
OPTCMD	SET_TRACE_LEVEL Causes the PeopleCode program implementing the OnRequest Integration Broker method to set the severity level at which events will be logged for an optimization engine. The OPT_CALL example executes the SetTraceLevel method.
PROBINST	The name of the analytic instance.
PROCINSTANCE	The name of the process instance for this process scheduler job.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

PARMKEY Field	***VALUE Field***
COMPONENT	One of the following values: • %Opt_Engine server activity of the running optimization engine. • %Opt_Utility low level elements that support the running optimization engine. • %Opt_Datacache the in-memory database cache. • %Opt_Plugin the plugin being used for the running optimization engine.
SEVERITY_LEVEL	The severity level to log. The following list starts with the most severe level; the level you specify includes all higher levels. For example, if you specify %Severity_Error, it logs %Severity_Fatal, %Severity _Status, and %Severity_Error messages and filters out the others. • %Severity_Fatal • %Severity_Status • %Severity_Error • %Severity_Warn • %Severity_Info • %Severity_Trace1 • %Severity_Trace2

Getting the Trace Level

To get a trace level, structure the rowset as follows, using the PT_OPTPARMS record.

PARMKEY Field	***VALUE Field***
OPTCMD	GET_TRACE_LEVEL Causes the PeopleCode program implementing the OnRequest Integration Broker method to get the severity level at which events will be logged for an optimization engine. The OPT_ CALL example executes the GetTraceLevel method.
PROBINST	Set to the name of the analytic instance.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

PARMKEY Field	*VALUE Field*
PROCINSTANCE	Set to the name of the process instance for this process scheduler job.
COMPONENT	One of the following values: • %Opt_Engine server activity of the running optimization engine. • %Opt_Utility low level elements that support the running optimization engine. • %Opt_Datacache the in-memory database cache. • %Opt_Plugin the plugin being used for the current opt engine.

Shutting Down an Optimization Engine

To shut down an optimization engine, structure the rowset as follows, using the PT_OPTPARMS record.

PARMKEY Field	*VALUE Field*
OPTCMD	SHUTDOWN Causes the PeopleCode program implementing the OnRequest Integration Broker method to shut down an optimization engine. The OPT_CALL example executes the Shutdown method.
PROBINST	The name of the analytic instance.
PROCINSTANCE	The name of the process instance for this process scheduler job.

Creating a Response Message

This section provides an overview of the response message and describes how to create messages that:

- Send optimization status.
- Send a detailed message.

Understanding the Response Message

For optimization, the message PeopleCode in application server receives the request messages, performs an optimization actions, and sends response OPT_CALL messages. One message uses rowsets built from PT_OPTPARMS records, the other uses rowsets from PT_DETMSGS records. You can use the rowset structures in the next section (Sending Optimization Status) as an example of how to send responses from the message notification PeopleCode in the application server to the application engine program in the process scheduler.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Sending Optimization Status

To send the status of the optimization functions and methods called within the PeopleCode program implementing the OnRequest Integration Broker method, structure the rowset as follows using the PT_OPTPARMS record. The optimization functions and messages are called in response to the request input message. You set key values using the PARMKEY field, and then set a value for that key field in the VALUE field.

PARMKEY Field	***VALUE Field***
STATUS	The return status of the optimization function or method that is called in the message PeopleCode.
DETAILED_STATUS	The optional detailed status returned by many of the optimization functions and methods.

Sending a Detailed Message

To send a detailed message, structure the rowset as follows, using the PT_DETMSGS record. You set key values using the PARMKEY field, and then set a value for that key field in the VALUE field.

PARMKEY Field	***VALUE Field***
MSGSET	The message set number. In the case of optimization, the message set number is 148.
MSGNUM	The name of the detailed message.
PARMCOUNT	The number of message parameters for the detailed message. There can be up to five parameters.
MSGPARM1	The first parameter value.
MSGPARM2	The second parameter value.
MSGPARM3	The third parameter value.
MSGPARM4	The fourth parameter value.
MSGPARM5	The fifth parameter value.

Editing the Request PeopleCode

The PT_OPTCALL Application Engine program serves as a template. It is delivered with all the sections marked as inactive. You can edit the program to suit your needs, then mark the appropriate sections active before running it. You can also use the program as a guide to creating your own Application Engine program.

The program uses these steps to send request messages to perform the following tasks:

1. Load the optimization engine.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

2. Wait for the optimization engine load to finish.
3. Run an optimization transaction against the loaded optimization engine.
4. Wait for the optimization transaction to finish running.
5. Set the trace level.
6. Get the trace level.
7. Shut down the optimization engine.

You can edit steps 1 and 3 to run an optimization transaction. You can also use the entire program as a template to create your own Application Engine program.

Loading an Optimization Engine

In step 1, enter the name of your analytic instance. In this example, the name of the analytic instance is *FEMALE1*.

If you have multiple domains, enter the local node name and the machine name and port number for your application server. In this case, the local node name is *%LocalNode* and the machine name and port number are *foo111111:9000.*

```
Local Message &MSG;
Local Message &response;

Component string &probid;
Component string &isSync;
Component string &procinst;
Local integer &nInst;
Local string &url;

Local Rowset &rs;
Local Row &row;
Local Record &rec;

Local string &stName;
Local integer &stVal;

&MSG = CreateMessage(OPERATION.OPT_CALL);
&rs = &MSG.GetRowset();

&row = &rs.GetRow(1);
&rec = &row.GetRecord(Record.PT_OPTPARMS);
&rec.PARMKEY.Value = "OPTCMD";
&rec.VALUE.Value = "CREATE";

&rs.InsertRow(1);
&rec = &rs.GetRow(2).PT_OPTPARMS;
&rec.PARMKEY.Value = "PROBINST";
&rec.VALUE.Value = "FEMALE1";
&probid = "FEMALE1";

&rs.InsertRow(2);
&rec = &rs.GetRow(3).PT_OPTPARMS;
&rec.PARMKEY.Value = "PROCINSTANCE";
&nInst = Record.PT_OPT_AET.PROCESS_INSTANCE.Value;
&rec.VALUE.Value = String(&nInst);
&procinst = String(&nInst);

&rs.InsertRow(3);
&rec = &rs.GetRow(4).PT_OPTPARMS;
&rec.PARMKEY.Value = "SYNCH";
&rec.VALUE.Value = "N";
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
&isSync = "N";


/* Specify the Application Server domain URL (foo111111:9000 in this example)
*/
&response = %IntBroker.SyncRequest(%LocalNode, "//foo111111:9000 e");

If &response.ResponseStatus = 0 Then
   &stName = &response.GetRowset().GetRow(1).GetRecord(Record.PT_OPTPARMS).Get
Field(Field.PARMKEY).Value;
   &stVal = Value(&response.GetRowset().GetRow(1).GetRecord(Record.PT_
OPTPARMS).GetField(Field.VALUE).Value);
   If &stName = "STATUS" And
         &stVal = %OptEng_Fail Then
      /* Check detailed message here */
      throw CreateException(148, 2, "Can not send to OptEngine");
   End-If;
End-If;
```

Running An Optimization Transaction

In step 3, enter the name of your optimization transaction and its parameter name/value pairs. In this example, the transaction name is *TEST_LONG_TRANS,* the first parameter name/value pair is *Delay_in_Secs* and *30,* and the second parameter name/value pair is *Sleep0_Work1* and *0.*

The parameter values are stored as strings. You may need to convert them in the OnRequest PeopleCode.

```
Local Message &MSG;
Local Message &response;

Local Rowset &rs, &respRS;
Local Row &row;
Local Record &rec, &msgRec;

Component string &probid;
Component string &procinst;
Component string &isSync;
Local string &url = "";
Local integer &parmCount, &msgSet, &msgNum;

&MSG = CreateMessage(OPERATION.OPT_CALL);
&rs = &MSG.GetRowset();

&row = &rs.GetRow(1);
&rec = &row.GetRecord(Record.PT_OPTPARMS);
&rec.PARMKEY.Value = "OPTCMD";
&rec.VALUE.Value = "RUN";

&rs.InsertRow(1);
&rec = &rs.GetRow(2).PT_OPTPARMS;
&rec.PARMKEY.Value = "PROBINST";
&rec.VALUE.Value = &probid;

&rs.InsertRow(2);
&rec = &rs.GetRow(3).PT_OPTPARMS;
&rec.PARMKEY.Value = "PROCINSTANCE";
&rec.VALUE.Value = &procinst;

&rs.InsertRow(3);
&rec = &rs.GetRow(4).PT_OPTPARMS;
&rec.PARMKEY.Value = "SYNCH";
&rec.VALUE.Value = &isSync;

&rs.InsertRow(4);
&rec = &rs.GetRow(5).PT_OPTPARMS;
&rec.PARMKEY.Value = "TRANSACTION";
&rec.VALUE.Value = "TEST_LONG_TRANS";

&rs.InsertRow(5);
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
&rec = &rs.GetRow(6).PT_OPTPARMS;
&rec.PARMKEY.Value = "Delay_in_Secs";
&rec.VALUE.Value = "30";

&rs.InsertRow(6);
&rec = &rs.GetRow(7).PT_OPTPARMS;
&rec.PARMKEY.Value = "Sleep0_Work1";
&rec.VALUE.Value = "0";

/* SyncRequest will carry a url */
SQLExec("select URL from PSOPTSTATUS where PROBINST=:1 AND URL NOT LIKE '%:0';",
 &probid, &url);
If &url = "" Then
   throw CreateException(148, 2, "Can not send to OptEngine");
End-If;

/* Specify the Application Server domain URL.
   (This was specified in Step 1 in this example.)
*/
&response = %IntBroker.SyncRequest(%LocalNode, &url);

If &response.ResponseStatus = 0 Then
   &stName = &response.GetRowset().GetRow(1).GetRecord(Record.PT_OPTPARMS).Get
Field(Field.PARMKEY).Value;
   &stVal = Value(&response.GetRowset().GetRow(1).GetRecord(Record.PT_
OPTPARMS).GetField(Field.VALUE).Value);

   If &stName = "STATUS" And
         &stVal = %OptEng_Fail Then
      throw CreateException(148, 2, "Can not send to OptEngine");
   End-If;

   /* Check Detailed msg here */
   If &isSync = "Y" And
         &stVal = %OptEng_Success Then

      &respRS = &response.GetRowset();
      &rowNum = &respRS.ActiveRowCount;
      For &iloop = 1 To &rowNum
         &msgRec = &respRS.GetRow(&iloop).GetRecord(Record.PT_OPTDETMSGS);
         If (&msgRec.GetField(Field.MSGSET).Value <> 0) Then
            &msgSet = Value(&msgRec.GetField(Field.MSGSET).Value);
            &msgNum = Value(&msgRec.GetField(Field.MSGNUM).Value);
            &parm1 = &msgRec.GetField(Field.MSGPARM1).Value;
            &parm2 = &msgRec.GetField(Field.MSGPARM2).Value;
            &parm3 = &msgRec.GetField(Field.MSGPARM3).Value;
            &parm4 = &msgRec.GetField(Field.MSGPARM4).Value;
            &parm5 = &msgRec.GetField(Field.MSGPARM5).Value;
            &string = MsgGetText(&msgSet, &msgNum, "Message Not Found", &parm1,
 &parm2, &parm3, &parm4, &parm5);

         End-If;
      End-For;

   End-If;

End-If;
```

Editing the Response PeopleCode

The OPT_CALL message definition serves as a template. It is delivered to work with the PT_OPTCALL Application Engine program. You can edit the program to suit your needs, or use it as a guide when creating your own response message program.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

OPT_CALL Message Program

The OPT_CALL application package implements the Integration Broker method OnRequest. The PeopleCode in this method shows application messages for lights-out mode.

Depending upon the request message, the OnRequest method PeopleCode calls appropriate optimization functions and methods to perform these tasks, and sends a response message containing the returned status and detailed messages from the optimization functions and methods.

You can use the OnRequest method PeopleCode as a template to create your own response message PeopleCode program. For example, you can edit it to run an optimization transaction, which is shown below as an example. This example is edited to match the examples for step 1 and step 3 in the PT_OPTCALL program.

Processing the Transaction Parameters

Edit the OPT_CALL application program OnRequest method to enter the name of your optimization transaction and the name/value pairs for its parameters. In this example, the transaction name is *TEST_LONG_TRANS,* the first parameter name/value pair is *&delayParm* and *&delay* (maps to *Delay_in_Secs* from the request message), and the second parameter name/value pair is *&sleepParm* and *&isSleep* (maps to *Sleep0_Work1* from the request message).

The parameter values are stored as strings in step 3 of the Application Engine program. You may need to convert them here to your desired format. Here is a section of the application program showing the places to edit.

```
If &trans = "TEST_LONG_TRANS" Then
   &REC = &rs.GetRow(6).PT_OPTPARMS;&delayParm = &REC.PARMKEY.Value;&delay = Value(⇒
&REC.VALUE.Value);

   &REC = &rs.GetRow(7).PT_OPTPARMS;&sleepParm = &REC.PARMKEY.Value;&isSleep = Valu⇒
e(&REC.VALUE.Value);

   &myopt = GetOptEngine(&inst, &detStatus);
   If (&myopt = Null) Then
      &optstatus = %OptEng_Fail;
   End-If;

   If &myopt <> Null And &isSync = "Y" Then
      &optstatus = &myopt.RunSynch(&trans, &delayParm, &delay, &sleepParm, &isSleep
);
      &detStatus = &myopt.DetailedStatus;
      End-If;

   If &myopt <> Null And &isSync = "N" Then
      &myopt.ProcessInstance = &procInst;
      &optstatus = &myopt.RunASynch(&trans, &delayParm, &delay, &sleepParm, &is
Sleep);
      &detStatus = &myopt.DetailedStatus;
   End-If; /* iif myopt=null */
End-If;
```

Building a Status Response Message

This section shows the a response message to send a status message for the OPT_CALL message in the application server.

```
/* Insert detailed status and detailed msgs into Response msg rowset */
&respRS = &response.GetRowset();
&respRS.GetRow(1).GetRecord(Record.PT_OPTPARMS).GetField(Field.PARMKEY).Value =
 "STATUS";
&respRS.GetRow(1).GetRecord(Record.PT_OPTPARMS).GetField(Field.VALUE).Value =
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
 String(&optstatus);

&respRS.InsertRow(1);
&respRS.GetRow(2).GetRecord(Record.PT_OPTPARMS).GetField(Field.PARMKEY).Value =
 "DETAILED_STATUS";
&respRS.GetRow(2).GetRecord(Record.PT_OPTPARMS).GetField(Field.VALUE).Value =
 String(&detStatus);
```

Building a Detailed Response Message

This section shows a response message to send a detailed message for the OPT_CALL message on the application server.

```
/*Either optcmd or inst is not passed in correctly, or optengine is not loaded
/created correctly */
If &myopt = Null Then
   &msgRec = &respRS.GetRow(1).GetRecord(Record.PT_OPTDETMSGS);
   If &isParmBad = True Then
      &msgRec.GetField(Field.MSGSET).Value = 148;
      &msgRec.GetField(Field.MSGNUM).Value = 505;
   End-If;
End-If;

/* If it is sync transaction, insert DetailMsg to response msg */
If &myopt <> Null And
      &isSync = "Y" And
      &optcmd = "RUN" And
      &optstatus = %OptEng_Success Then
   &arrArray = &myopt.DetailMsgs;
   For &iloop = 1 To &arrArray.Len
      /* First two rows have been inserted because of PT_OPTPARMS for two status
 codes */
      If &iloop > 2 Then
         &respRS.InsertRow(&iloop - 1);
      End-If;

      &msgRec = &respRS.GetRow(&iloop).GetRecord(Record.PT_OPTDETMSGS);
      &msgRec.GetField(Field.MSGSET).Value = String(&arrArray [&iloop][1]);
      &msgRec.GetField(Field.MSGNUM).Value = String(&arrArray [&iloop][2]);
      &msgRec.GetField(Field.PARMCOUNT).Value = String(&arrArray [&iloop][3]);
      &msgRec.GetField(Field.MSGPARM1).Value = String(&arrArray [&iloop][4]);
      &msgRec.GetField(Field.MSGPARM2).Value = String(&arrArray [&iloop][5]);
      &msgRec.GetField(Field.MSGPARM3).Value = String(&arrArray [&iloop][6]);
      &msgRec.GetField(Field.MSGPARM4).Value = String(&arrArray [&iloop][7]);
      &msgRec.GetField(Field.MSGPARM5).Value = String(&arrArray [&iloop][8]);
   End-For;

End-If;
```

Optimization Built-in Functions

This section discusses the optimization functions. The functions are discussed in alphabetical order.

CreateOptEngine

Syntax

CreateOptEngine(*analytic_inst*, {%Synch | %ASynch}[, *&detailedstatus*] [, *processinstance*])

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

The CreateOptEngine function instantiates an OptEngine object, loads an optimization engine with an analytic instance and returns a reference to it.

Parameters

Analytic_inst

Specify the analytic instance ID, which is a unique ID for this analytic instance in this optimization engine. This is supplied by users when they request that an optimization be run.

%Synch | %Asynch

Specify whether the optimization engine is synchronous or asynchronous. The values are:

- %Synch: run the optimization engine synchronously.
- %Asynch: run the optimization engine asynchronously.

&detailedstatus

Specify a variable that the engine uses to give further information about the evaluation of this function. The value returned is one of the following:

- %OptEng_Success: The function completed successfully.
- %OptEng_Fail: The function failed.
- %OptEng_Invalid_Aiid: The analytic instance ID passed to the function is invalid.
- %OptEng_Exists: An optimization engine instance already exists and is loaded.
- %OptEng_Method_Disabled: A method is disabled or not valid.
- %OptEng_DB_Updates_Pending: indicates that database updates are pending.

processinstance

Enter the process instance ID. You use this parameter only with lights-out processing, most likely with the subscription PeopleCode for application message.

Note: This optional parameter is positional. If you use it, you must also use the *&detailedstatus* parameter.

The state record that you use with Application Engine contains the process instance ID.

See Using Lights-Out Mode with Optimization.

See "Using State Records" (PeopleTools 8.54: Application Engine).

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

If successful, CreateOptEngine returns an OptEngine PeopleCode object. If the function fails, it returns a null value. Examine the optional status reference parameter in case of a Null return for additional information regarding the failure.

Example

An OptEngine object variable can be scoped as Local, Component, or Global.

You declare OptEngine objects as type OptEngine. For example:

```
Local OptEngine &MyOptEngine;
Component OptEngine &MyOpt;
Global OptEngine &MyOptEng;
```

The following example loads an optimization engine with the analytic instance:

```
Local OptEngine &myopt;
Local string &probinst;
Local string &transaction;
Local integer &detailedstatus;

&probinst = GetRecord(Record.PSOPTPRBINST).GetField(Field.PROBINST).Value;
&myopt = CreateOptEngine(&probinst, %Synch);
```

The following example shows the use of the optional status parameter:

```
&myopt = CreateOptEngine(&probinst, %Synch, &detailedstatus);
if &myopt = Null then
    if &detailedstatus = %OptEng_Invalid_Piid then
        /*perform some action */
    end_if;
end_if;
```

CreateOptInterface

Syntax

`CreateOptInterface`()

Description

The CreateOptInterface function instantiates an OptInterface object.

Note: You can use this function and the OptInterface methods only within an application class that you extend from the OptBase application class, or within PeopleCode that you call from that application class. This ensures that the OptInterface PeopleCode runs only on the optimization engine.

Parameters

None.

Returns

If successful, CreateOptInterface returns an OptInterface PeopleCode object. If the function fails, it returns a null value.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

You declare OptInterface objects as type OptInterface. For example:

```
Local OptInterface &MyOptInterface;
Component OptInterface &MyOptInt;
Global OptInterface &MyOptInt;
```

The following example instantiates an OptInterface object:

```
Local OptInterface &myInterface;
Int &status;

&myInterface = CreateOptInterface(&addtionalStatus);
if (&myInterface != NULL) then
    &status = &myInterface.ActivateModel("RMO_TEST");
        if (&status = %OptInter_Fail) then
            /* examine &myInterface.DetailedStatus for reason */
            ...
        end-if;
else
    /* CreateOptInterface has returned NULL */
    /* take some corrective action here */
        ...
end_if;
```

DeleteOptProbInst

Syntax

DeleteOptProbInst(*probinst*[, *&detailedstatus*])

Description

The DeleteOptProbInst function deletes the analytic instance ID from PeopleTools metadata. This function can be called only inside FieldChange, PreSaveChange and PostSaveChange PeopleCode events, and in Workflow.

Note: Use this function to delete the analytic instance ID after deleting data in optimization application tables for this analytic instance.

Parameters

probinst Enter the analytic instance ID to delete.

&detailedstatus (Optional) This status reference parameter returns an integer value giving further information about the evaluation of this function. The value returned is one of the following:

- %OptEng_Success: The function completed successfully.
- %OptEng_Fail: The function failed.
- %OptEng_Invalid_Piid: The analytic instance ID passed to the function is invalid.
- %OptEng_Sql_Exception: A SQLerror is encountered when access database.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- %OptEng_Exists: An analytic server loaded with this analytic instance still exists.

Returns

Returns %OptEng_Success if successful; otherwise returns %OptEng_Fail.

Example

The following example deletes the instance for an analytic type:

Note: Whenever you add records to an analytic type, you must call DeleteOptProbInst to delete the old analytic type instances and then call InsertOptProbInst to recreate them.

```
Local string &probinst;
Local string &probtype;
Local integer &ret;
&probinst = "PATSMITH";
&probtype = "QEOPT";
&ret = DeleteOptProbInst(&probinst, &probtype);
If &ret <> %OptEng_Success  Then
   QEOPT_WRK.MESSAGE_TEXT = "Delete of analytic instance " | &probinst | "
 failed.";
Else
   QEOPT_WRK.MESSAGE_TEXT = "Analytic Instance " | &probinst | " deleted.";
End-If;
```

The following example shows the use of the optional status parameter:

```
Local integer &detailedstatus;
&ret = DeleteOptProbInst(&probinst, &probtype, &detailedstatus);
If &ret <> %OptEng_Success  AND &detailedstatus=%OptEng_Invalid_Piid then
   QEOPT_WRK.MESSAGE_TEXT = "Delete of analytic instance " | &probinst | " failed
for bad piid.";
Else
   QEOPT_WRK.MESSAGE_TEXT = "Analytic Instance " | &probinst | deleted.";
End-If;
```

GetOptEngine

Syntax

GetOptEngine(*probinst*[,*&detailedstatus*])

Description

The GetOptEngine function returns a handle to an optimization engine that is already loaded with the analytic instance.

Note: You cannot call GetOptEngine from a domain other than the application server.

Parameters

probinst Enter the analytic instance ID, which is unique ID for this analytic instance in this optimization engine.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

&detailedstatus

(Optional) This status reference parameter returns an integer value giving further information about the evaluation of this function. The value returned is one of the following:

- %OptEng_Success: The function completed successfully.
- %OptEng_Fail: The function failed.
- %OptEng_Invalid_Piid: The analytic instance ID passed to the function is invalid.

Returns

Returns an OptEngine PeopleCode object if successful, a null value otherwise.

Example

The following example causes an optimization engine to shut down its analytic instance:

```
Global string &probinst;
Local OptEngine &myopt;
Local integer &status;

&myopt = GetOptEngine(&probinst);
If &myopt <> NULL then
&status = &myopt.ShutDown();
QEOPT_WRK.MESSAGE_TEXT = "Analytic Instance ID " | &probinst
 | " has been shutdown successfully.";
End-if;
```

Or, you can use the optional status parameter:

```
&myopt = GetOptEngine(&probinst, &detailedstatus);
if &myopt=NULL and &detailedstatus=%OptEng_Invalid_Piid then
     /* perform some action */
End-if;
```

GetOptProbInstList

Syntax

GetOptProbInstList(*ProblemType* , *OutputErrorCode* [, *Prefix*] [, *&detailedstatus*])

Description

The GetOptProbInstList function gets the list of all analytic instance IDs in an analytic type.

Parameters

ProblemType

Enter the name of the analytic type that you created in Application Designer.

OutputErrorCode

Future use. Always returns zero.

Prefix

(Optional) Enter a string. If used, this prefix causes the returned list to include only the analytic instance IDs that start with this

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

prefix. If not used, all the analytic instance IDs in the analytic type are returned.

&detailedstatus

(Optional) This status reference parameter returns an integer value giving further information about the evaluation of this function. The value returned is one of the following:

- %OptEng_Success: The function completed successfully.
- %OptEng_Fail: The function failed.
- %OptEng_Invalid_Piid: The analytic type name passed to the function is invalid.

Returns

Returns an array of strings containing the optimization analytic instance list.

Example

The following example shows the usage of GetOptProbInstList to fill the display field on a page:

```
Global string &probinst;
Local integer &detailedstatus;
Local integer &iloop;
Local array of string &instarray;

QEOPT.OPERATOR = %UserId;

&instarray = GetOptProbInstList(QEOPT.PROBTYPE, &ret, &detailedstatus);

If &ret <> %OptEng_Success Then
   QEOPT_WRK.MESSAGE_TEXT = "Could not get analytic instances
 for analytic type " | QEOPT.PROBTYPE ;
Else
   For &iloop = 1 To &instarray.Len
      QEOPT_WRK.MESSAGE_TEXT = QEOPT_WRK.MESSAGE_TEXT | &instarray[&iloop] | " ";
   End-For;
End-If;
```

The following example shows the use of the optional status parameter:

```
&instarray = GetOptProbInstList(QEOPT.PROBTYPE, &ret, &detailedstatus);
If &ret <> %OptEng_Success and &detailedstatus=%OptEng_Invalid_Piid Then
   QEOPT_WRK.MESSAGE_TEXT = "Could not get analytic instances for analytic type "
| QEOPT.PROBTYPE | "because bad piid" ;
End-If;
```

InsertOptProbInst

Syntax

InsertOptProbInst(*probinst, ProblemType*[, *&detailedstatus*] [,*Description*])

Description

The InsertOptProbInst function inserts a new analytic instance ID into the PeopleTools metadata.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The InsertOptProbInst function can be called only inside FieldChange, PreSave and PostSave PeopleCode events, and in Workflow.

Note: You must use this function to create the analytic instance ID before inserting data into optimization application tables for this analytic instance.

Parameters

probinst Enter the analytic instance ID to be inserted into the analytic type.

ProblemType Enter the name of the analytic type that you created in Application Designer.

&detailedstatus (Optional) This status reference parameter returns an integer value giving further information about the evaluation of this function. The value returned is one of the following:

- %OptEng_Success: The function completed successfully.
- %OptEng_Fail: The function failed.
- %OptEng_Invalid_Piid: The analytic instance ID passed to the function is invalid.

Description (Optional) Specify a description for the analytic instance. This parameter takes a string value.

Returns

This method returns a constant. Valid values are:

Value	*Description*
%OptEng_Success	Returned if method succeeds.
%OptEng_Fail	Returned if the method fails.

Example

```
Local string &probinst;
Local string &probtype;
Local integer &ret;
Local integer &detailedstatus;

&probinst = "PATSMITH";
&probtype = "QEOPT";
&probDescr = "New QEOPT instance";
&ret = InsertOptProbInst(&probinst, &probtype, &probDescr);
If &ret <> %OptEng_Success Then
   QEOPT_WRK.MESSAGE_TEXT = "Insert of analytic instance "
 | &probinst | " failed.";
Else
   QEOPT_WRK.MESSAGE_TEXT = "Analytic Instance " | &probinst | " created.";
End-If;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The following example shows the use of the optional status parameter:

```
&ret = InsertOptProbInst(&probinst, &probtype, &detailedstatus);
If &ret <> %OptEng_Success and &detailedstatus=%OptEng_Invalid_Piid Then
   QEOPT_WRK.MESSAGE_TEXT = "Insert of analytic instance "
 | &probinst | " failed for bad piid.";
End-if;
```

IsValidOptProbInst

Syntax

IsValidOptProbInst(*probinst* [, &*detailedstatus*])

Description

IsValidOptProbInst determines if a given analytic instance exists in the optimization metadata.

Parameters

probinst Enter the analytic instance ID to be validated.

&detailedstatus (Optional) This status reference parameter returns an integer value giving further information about the evaluation of this function. The value returned is one of the following:

- %OptEng_Success: The function completed successfully.
- %OptEng_Invalid_Piid: The analytic type name passed to the function is invalid.

Returns

This method returns a constant. Valid values are:

Value	*Description*
%OptEng_Success	Returned if method succeeds.
%OptEng_Fail	Returned if the method fails.

Example

```
Local string &probinst;
Local integer &detailedstatus;
Local integer &ret;

&probinst = "PATSMITH";
&ret = IsValidOptProbInst(&probinst, &detailedstatus);
If &ret <> %OptEng_Success and &detailedstatus=%OptEng_Invalid_Piid Then
   <perform some action>
End-if;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

OptEngine Class Methods

This section discusses the optimization methods for the OptEngine PeopleCode class. The methods are listed in alphabetical order.

CheckOptEngineStatus

Syntax

CheckOptEngineStatus()

Description

The CheckOptEngineStatus method returns the status of the optimization engine, using a combination of its return value and the DetailedStatus OptEngine class property. Keep the following in mind:

- The value returned by CheckOptEngineStatus is the operational status of the optimization engine.
- The DetailedStatus property indicates the completion status of the OptEngine method call CheckOptEngineStatus.

For example, CheckOptEngineStatus can return %OptEng_Idle and DetailedStatus is %OptEng_Success. For CheckOptEngineStatus, DetailedStatus can have the value:

- %OptEng_Success
- %OptEng_Fail
- %OptEng_Not_Available

Note: Before this method is called, the CreateOptEngine or GetOptEngine must be called.

Returns

Returns an integer for the status of the optimization engine. These numbers are message IDs belonging to message set 148 in the message catalog.

Numeric Value	*Constant Value*	*Description*
21	%OptEng_Not_Loaded	The optimization engine process is running, but is not currently loaded with an application problem.
22	%OptEng_Busy_Loading	The optimization engine is busy loading an application problem. It will not accept transaction requests until loading completes.
23	%OptEng_Idle	The optimization engine is loaded with an application problem and waiting for a transaction request.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Numeric Value	*Constant Value*	*Description*
24	%OptEng_Busy	The optimization engine is busy processing a transaction request for the loaded application problem. It will not accept additional transaction requests until the current one completes.
26	%OptEng_Unknown	An error has occurred. The optimization engine status cannot be determined.

Example

This PeopleCode example shows optimization engine status being checked:

```
Local OptEngine &myopt;
Local string &probinst;
Local integer &status;
&myopt = GetOptEngine("PATSMITH");
/* Initialize the DESCRLONG field in the QE_FUNCLIB_OPT record to null.  */
GetLevel0().GetRow(1).GetRecord(Record.QE_FUNCLIB_OPT).DESCRLONG.Value = "";
&status = &myopt.CheckOptEngineStatus();
GetLevel0().GetRow(1).GetRecord(Record.QE_FUNCLIB_OPT).DESCRLONG.Value = "Opt
Engine status = " | MsgGet(148, &status, "Could not send to the OptEngine.");
```

You can also retrieve the detailed status:

```
Local integer &detailedstatus
&status = &myopt.CheckOptEngineStatus();
&detailedstatus = &myopt.DetailedStatus;
```

FillRowset

Syntax

FillRowset(*PARAM_NAME, &Rowset*[, *&functionstatus*])

Description

This method gets the value of a transaction output parameter that is a rowset. This cannot be used with the RunAsynch method; RunSynch is needed to make the transaction output parameter values immediately available.

When using the OptEngine DetailedStatus property, keep the following in mind:

- The value returned by FillRowset is the operational status of the optimization engine.
- The OptEngine DetailedStatus property indicates the completion status of the OptEngine method call FillRowset.

For example, FillRowset returns %OptEng_Fail, and DetailedStatus is %OptEng_Method_Disabled.

For FillRowset, the DetailedStatus property can have the value:

- %OptEng_Success.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- %OptEng_Fail.
- %OptEng_Method_Disabled.

  This indicates that the method is disabled or not valid.
- %OptEng_Wrong_Parm_Type

Parameters

PARAM_NAME

Enter a string for the name of the output parameter to get from the transaction that was just performed with RunSynch. This parameter must be defined as an output or both (input and output) in the analytic type definition.

See "Configuring Analytic Type Transactions" (PeopleTools 8.54: Optimization Framework).

&Rowset

Enter the rowset containing the values. This rowset must be a single record rowset, and the record must match the record name associated with the transaction parameter in the analytic type definition.

&functionstatus

(Optional) This status reference parameter returns an integer value giving further information about the evaluation of this function. The value returned is one of the following:

- OptEng_Success: The function completed successfully.
- OptEng_Fail: The function failed.
- OptEng_Method_Disabled: A method is disabled or not valid.

Returns

This method returns a constant. Valid values are:

Value	*Description*
%OptEng_Success	Returned if method succeeds.
%OptEng_Fail	Returned if the method fails.

Example

The following PeopleCode example runs a synchronous optimization transaction named RETURN_MACHINE_UNAVAILABLE. It has these parameters:

- Input: MACHINE_NAME to specify the machine for which we need unavailable times.
- Output: RETURN_TIMES to specify a rowset and MACHINE_WRK record containing the BEGIN_DATE and END_DATE fields.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This PeopleCode example sets input parameter values and gets an output parameter value:

```
Local OptEngine &myopt;
Local integer &status;
Local string &machname;
Local Rowset &rs;
&myopt = GetOptEngine("PATSMITH");
&machname = QEOPT_WRK.MACHINE_NAME.Value;
/* Run the RETURN_MACHINE_UNAVAILABLE transaction synchronously with input values.
  */
&status = &myopt.RunSynch("RETURN_MACHINE_UNAVAILABLE", "MACHINE_NAME", &machname);
If Not &status Then
   QEOPT_WRK.MESSAGE_TEXT = " RETURN_MACHINE_UNAVAILABLE transaction failed.";
   Return;
End-If;
/* Get output value from the RETURN_MACHINE_UNAVAILABLE transaction.  */
&rs = CreateRowset(Record.MACHINE_WRK);
&status = &myopt.FillRowset("RETURN_TIMES", &rs);
```

You can also use the [new->] DetailedStatus property as follows:

```
&status = &myopt.FillRowset("RETURN_TIMES", &rs);
if &status=%OptEng_Fail and &myopt.DetailedStatus=%OptEng_Method_Disabled then
    /* perform some action */
End-if;
```

GetDate

Syntax

GetDate(*PARAM_NAME*[, *&status*])

Description

This method gets the value of a transaction output parameter with a data type of Date. This cannot be used with the RunAsynch method; RunSynch is needed to make the transaction output parameter values immediately available.

The OptEngine DetailedStatus property indicates the completion status of the OptEngine method call GetDate. For GetDate, DetailedStatus can have the value:

- %OptEng_Success.
- %OptEng_Fail.
- %OptEng_Method_Disabled: indicates that the method is disabled or not valid.

Parameters

PARAM_NAME

Enter a string for the name of the output parameter to get from the transaction that was just performed with RunSynch. This parameter must be defined as an output or both (input and output) in the analytic type definition.

See "Configuring Analytic Type Transactions" (PeopleTools 8.54: Optimization Framework).

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

Returns a Date object; use this method when that is the data type of the transaction output parameter value.

Example

See GetNumber.

GetDateArray

Syntax

GetDateArray(*PARAM_NAME*)

Description

This method gets the value of a transaction output parameter with a data type Array of Date. This cannot be used with the RunAsynch method; RunSynch is needed to make the transaction output parameter values immediately available.

The OptEngine DetailedStatus property indicates the completion status of the OptEngine method call GetDateArray. For GetDateArray, DetailedStatus can have the value:

- %OptEng_Success.
- %OptEng_Fail.
- %OptEng_Method_Disabled: indicates that the method is disabled or not valid.

Parameters

PARAM_NAME

Enter a string for the name of the output parameter to get from the transaction that was just performed with RunSynch. This parameter must be defined as an output or both (input and output) in the analytic type definition.

See "Configuring Analytic Type Transactions" (PeopleTools 8.54: Optimization Framework).

Returns

Returns an Array of Date object; use this method when that is the data type of the transaction output parameter value.

Example

See GetStringArray.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GetDateTime

Syntax

GetDateTime(*PARAM_NAME*)

Description

This method gets the value of a transaction output parameter with a data type of DateTime. This cannot be used with the RunAsynch method; RunSynch is needed to make the transaction output parameter values immediately available.

The DetailedStatus OptEngine property indicates the completion status of the OptEngine method call GetDateTime. For GetDateTime, DetailedStatus can have the value:

- %OptEng_Success.
- %OptEng_Fail.
- %OptEng_Method_Disabled: indicates that the method is disabled or not valid.

Parameters

PARAM_NAME

Enter a string for the name of the output parameter to get from the transaction that was just performed with RunSynch. This parameter must be defined as an output or both (input and output) in the analytic type definition.

See "Configuring Analytic Type Transactions" (PeopleTools 8.54: Optimization Framework).

Returns

Returns a DateTime object; use this method when that is the data type of the transaction output parameter value.

Example

See GetNumber.

GetDateTimeArray

Syntax

GetDateTimeArray(*PARAM_NAME*)

Description

This method gets the value of a transaction output parameter with a data type Array of DateTime. This cannot be used with the RunAsynch method; RunSynch is needed to make the transaction output parameter values immediately available.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The DetailedStatus OptEngine property indicates the completion status of the OptEngine method call GetDateTimeArray. For GetDateTimeArray, DetailedStatus can have the value:

- %OptEng_Success.
- %OptEng_Fail.
- %OptEng_Method_Disabled: indicates that the method is disabled or not valid.

Parameters

PARAM_NAME

Enter a string for the name of the output parameter to get from the transaction that was just performed with RunSynch. This parameter must be defined as an output or both (input and output) in the analytic type definition.

See "Configuring Analytic Type Transactions" (PeopleTools 8.54: Optimization Framework).

Returns

Returns an Array of DateTime object; use this method when that is the data type of the transaction output parameter value.

Example

See GetStringArray.

GetNumber

Syntax

GetNumber(*PARAM_NAME*)

Description

This method gets the value of a transaction output parameter with a data type of Number. This cannot be used with the RunAsynch method; RunSynch is needed to make the transaction output parameter values immediately available.

The DetailedStatus OptEngine property indicates the completion status of the OptEngine method call GetNumber. For GetNumber, DetailedStatus can have the value:

- %OptEng_Success.
- %OptEng_Fail.
- %OptEng_Method_Disabled: indicates that the method is disabled or not valid.

Parameters

PARAM_NAME

Enter a string for the name of the output parameter to get from the transaction that was just performed with RunSynch. This

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

parameter must be defined as an output or both (input and output) in the analytic type definition.

See "Configuring Analytic Type Transactions" (PeopleTools 8.54: Optimization Framework).

Returns

Returns a Number object; use this method when that is the data type of the transaction output parameter value.

Example

The following PeopleCode example runs a synchronous optimization transaction named IS_MACHINE_AVAILABLE. It has these parameters:

- Input MACHINE_NAME to specify the machine.
- Inputs BEGIN_DATE and END_DATE to specify the time slot.
- Output AVAILABLE_FLAG to specify whether the machine is available in that time slot.

This PeopleCode example sets input parameter values and gets an output parameter value:

```
Local OptEngine &myopt;
Local integer &status;
Local string &machname;
Local datetime &begindate;
Local datetime &enddate;
&myopt = GetOptEngine("PATSMITH");
&machname = QEOPT_WRK.MACHINE_NAME.Value;
&begindate = QEOPT_WRK.BEGIN_DATE.Value;
&enddate = QEOPT_WRK.END_DATE.Value;
/* Run the IS_MACHINE_AVAILABLE transaction synchronously with input values.  */
&status = &myopt.RunSynch("IS_MACHINE_AVAILABLE", "MACHINE_NAME",
 &machname, "BEGIN_DATE", &begindate, "END_DATE", &enddate);
If Not &status Then
   QEOPT_WRK.MESSAGE_TEXT = "IS_MACHINE_AVAILABLE transaction failed.";
   Return;
End-If;
/* Get output value from the IS_MACHINE_AVAILABLE transaction.  */
QEOPT_WRK.AVAILABLE_FLAG = &myopt.GetNumber("AVAILABLE_FLAG");
```

You can use the DetailedStatus property as follows:

```
QEOPT_WRK.AVAILABLE_FLAG = &myopt.GetNumber("AVAILABLE_FLAG");
if &myopt.DetailedStatus=%OptEng_Fail then
   /* perform some action */
End-if;
```

GetNumberArray

Syntax

GetNumberArray(*PARAM_NAME*)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

This method gets the value of a transaction output parameter with a data type Array of Number. This cannot be used with the RunAsynch method; RunSynch is needed to make the transaction output parameter values immediately available.

The DetailedStatus OptEngine property indicates the completion status of the OptEngine method call GetNumberArray. For GetNumberArray, DetailedStatus can have the value:

- %OptEng_Success.
- %OptEng_Fail.
- %OptEng_Method_Disabled: this indicates that the method is disabled or not valid.

Note: Do not pass an array of type Integer as a transaction parameter. Use an array of type Number instead.

Parameters

PARAM_NAME

Enter a string for the name of the output parameter to get from the transaction that was just performed with RunSynch. This parameter must be defined as an output or both (input and output) in the analytic type definition.

See "Configuring Analytic Type Transactions" (PeopleTools 8.54: Optimization Framework).

Returns

Returns an Array of Number object; use this method when that is the data type of the transaction output parameter value.

Example

See GetStringArray.

GetString

Syntax

GetString(*PARAM_NAME*)

Description

This method gets the value of a transaction output parameter with a data type of String. This cannot be used with the RunAsynch method; RunSynch is needed to make the transaction output parameter values immediately available.

The DetailedStatus OptEngine property indicates the completion status of the OptEngine method call GetString. For GetString, DetailedStatus can have the value:

- %OptEng_Success.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- %OptEng_Fail.
- %OptEng_Method_Disabled: indicates that the method is disabled or not valid.

Parameters

PARAM_NAME

Enter a string for the name of the output parameter to get from the transaction that was just performed with RunSynch. This parameter must be defined as an output or both (input and output) in the analytic type definition.

See "Configuring Analytic Type Transactions" (PeopleTools 8.54: Optimization Framework).

Returns

Returns a String object; use this method when that is the data type of the transaction output parameter value.

Example

See GetNumber.

GetStringArray

Syntax

GetStringArray(*PARAM_NAME*)

Description

This method gets the value of a transaction output parameter with a data type Array of String. This cannot be used with the RunAsynch method; RunSynch is needed to make the transaction output parameter values immediately available.

The DetailedStatus OptEngine property indicates the completion status of the OptEngine method call GetStringArray. For GetStringArray, DetailedStatus can have the value:

- %OptEng_Success.
- %OptEng_Fail.
- %OptEng_Method_Disabled: indicates that the method is disabled or not valid.

Parameters

PARAM_NAME

Enter a string for the name of the output parameter to get from the transaction that was just performed with RunSynch. This parameter must be defined as an output or both (input and output) in the analytic type definition.

See "Configuring Analytic Type Transactions" (PeopleTools 8.54: Optimization Framework).

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

Returns an Array of String object; use this method when that is the data type of the transaction output parameter value.

Example

The following PeopleCode example runs a synchronous optimization transaction named ARE_MACHINES_AVAILABLE. It has these parameters:

- Inputs BEGIN_DATE and END_DATE to specify the time slot.
- Output MACHINE_NAMES to specify the machines available in that time slot.

This PeopleCode example sets input parameter values and gets an output parameter value:

```
Local OptEngine &myopt;
Local integer &status;
Local array of string &machnames;
Local datetime &begindate;
Local datetime &enddate;
&myopt = GetOptEngine("PATSMITH");
&begindate = QEOPT_WRK.BEGIN_DATE.Value;
&enddate = QEOPT_WRK.END_DATE.Value;
/* Run the ARE_MACHINES_AVAILABLE transaction synchronously with input values.  */
&status = &myopt.RunSynch("ARE_MACHINES_AVAILABLE",
 "BEGIN_DATE", &begindate, "END_DATE", &enddate);
If &status=%OptEng_Fail Then
   QEOPT_WRK.MESSAGE_TEXT = "ARE_MACHINES_AVAILABLE transaction failed.";
   Return;
End-If;
/* Get output value from the ARE_MACHINES_AVAILABLE transaction.  */
&machnames = &myopt.GetStringArray("MACHINE_NAMES");
```

The following example shows the use of the DetailedStatus property:

```
Local array of string &machnames;
&machnames = &myopt.GetStringArray("MACHINE_NAMES");
if &myopt.DetailedStatus=%OptEng_Fail then
   /* perform some action */
End-if;
```

GetTime

Syntax

GetTime(*PARAM_NAME*)

Description

This method gets the value of a transaction output parameter with a data type of Time. This cannot be used with the RunAsynch method; RunSynch is needed to make the transaction output parameter values immediately available.

The DetailedStatus OptEngine property indicates the completion status of the OptEngine method call GetTime. For GetTime, DetailedStatus can have the value:

- %OptEng_Success.
- %OptEng_Fail.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- %OptEng_Method_Disabled: indicates that the method is disabled or not valid.

Parameters

PARAM_NAME

Enter a string for the name of the output parameter to get from the transaction that was just performed with RunSynch. This parameter must be defined as an output or both (input and output) in the analytic type definition.

See "Configuring Analytic Type Transactions" (PeopleTools 8.54: Optimization Framework).

Returns

Returns a Time object; use this method when that is the data type of the transaction output parameter value.

Example

See GetNumber.

GetTimeArray

Syntax

GetTimeArray(*PARAM_NAME*)

Description

This method gets the value of a transaction output parameter with a data type Array of Time. This cannot be used with the RunAsynch method; RunSynch is needed to make the transaction output parameter values immediately available.

The DetailedStatus OptEngine property indicates the completion status of the OptEngine method call GetTimeArray. For GetTimeArray, DetailedStatus can have the value:

- %OptEng_Success.
- %OptEng_Fail.
- %OptEng_Method_Disabled: indicates that the method is disabled or not valid.

Parameters

PARAM_NAME

Enter a string for the name of the output parameter to get from the transaction that was just performed with RunSynch. This parameter must be defined as an output or both (input and output) in the analytic type definition.

See "Configuring Analytic Type Transactions" (PeopleTools 8.54: Optimization Framework).

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

Returns an Array of Time object; use this method when that is the data type of the transaction output parameter value.

Example

See GetStringArray.

GetTraceLevel

Syntax

GetTraceLevel(*component*)

Description

GetTraceLevel gets the severity level at which events are logged for a given component.

The DetailedStatus OptEngine property indicates the completion status of the OptEngine method call GetTraceLevel. For GetTraceLevel, DetailedStatus can have the value:

- %OptEng_Success.

  This indicates that the function completed successfully.

- %OptEng_Fail.

  This indicates that the function failed.

- %OptEng_Method_Disabled.

  This indicates that the method is disabled or not valid.

- %OptEng_DB_Updates_Pending.

  This indicates that database updates are pending.

Parameters

component Enter one of the following PeopleCode constants: Opt_Engine, Opt_Utility, Opt_Datacache, or Opt_Plugin.

Returns

Returns one of the following.

- %Severity_Fatal
- %Severity_Status
- %Severity_Error
- %Severity_Warn

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- %Severity_Info
- %Severity_Trace1
- %Severity_Trace2

Example

```
Local OptEngine &myopt;
Local integer &tracelevel;

&myopt = GetOptEngine("PATSMITH");

&tracelevel = &myopt.GetTraceLevel(%Opt_Engine);
if &myopt.DetailedStatus = %OptEng_Success then

   if (&tracelevel = %Severity_Info_ then
      winmessage("Severity level for the OptEngine is 'Info'");
   End-if;
End-if;
```

RunAsynch

Syntax

RunAsynch(*TRANSACTION, PARM_PAIRS*)

Description

The RunAsynch method requests the optimization engine to run the transaction in asynchronous mode.

When using the DetailedStatus OptEngine property, keep the following in mind:

- The value returned by RunASynch is the operational status of the optimization engine.
- The DetailedStatus OptEngine property indicates the completion status of the OptEngine method call RunASynch.

For example, RunASynch can return %OptEng_Fail and DetailedStatus is %OptEng_DB_Updates_Pending. For RunASynch, DetailedStatus can have the value:

- %OptEng_Success: indicates that the function completed successfully.
- %OptEng_Fail: indicates that the function failed.
- %OptEng_Method_Disabled: indicates that the method is disabled or not valid.
- %OptEng_DB_Updates_Pending: indicates that database updates are pending.

Parameters

TRANSACTION	Enter a string for the name of the transaction to run.
PARAM_PAIRS	Enter the name and value pairs (string name and value) for this transaction. Not used if the transaction has no parameters. Parameters are defined in the analytic type definition.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

See "Configuring Analytic Type Transactions" (PeopleTools 8.54: Optimization Framework).

Returns

This method returns a constant. Valid values are:

Value	*Description*
%OptEng_Success	Returned if method succeeds.
%OptEng_Fail	Returned if the method fails.

Example

This PeopleCode example runs an asynchronous optimization transaction named SOLVE. It has no input or output parameters. The SOLVE transaction solves the exercise scheduling problem and puts the results into the QE_RWSM_EXERSCH table.

```
Local OptEngine &myopt;
Local integer &status;
&myopt = GetOptEngine("PATSMITH");
/* Run the SOLVE transaction asynchronously with input values.  */
&status = &myopt.RunAsynch("SOLVE");
If &status=%OptEng_Fail Then
   QEOPT_WRK.MESSAGE_TEXT = "SOLVE transaction failed.";
   Return;
End-If;
```

The following example shows the use of the DetailedStatus property.

```
Local integer &status;
&status = myopt.RunAsynch("SOLVE");
if &status=%OptEng_Fail and &myopt.DetailedStatus=%OptEng_Method_Disabled then
   <perform some action>
End-if;
```

RunSynch

Syntax

RunSynch(*TRANSACTION, PARM_PAIRS*)

Description

The RunSynch method requests the optimization engine to run the transaction in synchronous mode.

When using the DetailedStatus OptEngine property, keep the following in mind:

- The value returned by RunSynch is the operational status of the optimization engine.
- The DetailedStatus OptEngine property indicates the completion status of the OptEngine method call RunSynch.

For example, RunSynch can return %OptEng_Fail and DetailedStatus is %OptEng_DB_Updates_Pending. For RunSynch, DetailedStatus can have the value:

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- %OptEng_Success: indicates that the function completed successfully.
- %OptEng_Fail: indicates that the function failed.
- %OptEng_Method_Disabled: indicates that the method is disabled or not valid.
- %OptEng_DB_Updates_Pending: indicates that database updates are pending.

Parameters

TRANSACTION Enter a string for the name of the transaction to run.

PARAM_PAIRS Enter the name and value pairs (string name and value) for this transaction. Not used if the transaction has no parameters. Parameters are defined in the analytic type definition.

See "Configuring Analytic Type Transactions" (PeopleTools 8.54: Optimization Framework).

Returns

This method returns a constant. Valid values are:

Value	*Description*
%OptEng_Success	Returned if method succeeds.
%OptEng_Fail	Returned if the method fails.

Example

The following PeopleCode example runs a synchronous optimization transaction named IS_MACHINE_AVAILABLE. It has these parameters:

- Input MACHINE_NAME to specify the machine.
- Inputs BEGIN_DATE and END_DATE to specify the time slot.
- Output AVAILABLE_FLAG to specify whether the machine is available in that time slot.

This PeopleCode example sets input parameter values and gets an output parameter value:

```
Local OptEngine &myopt;
Local integer &status;
Local string &machname;
Local datetime &begindate;
Local datetime &enddate;
&myopt = GetOptEngine("PATSMITH");
&machname = QEOPT_WRK.MACHINE_NAME.Value;
&begindate = QEOPT_WRK.BEGIN_DATE.Value;
&enddate = QEOPT_WRK.END_DATE.Value;
/* Run the IS_MACHINE_AVAILABLE transaction synchronously with input values.  */
&status = &myopt.RunSynch("IS_MACHINE_AVAILABLE",
 "MACHINE_NAME", &machname, "BEGIN_DATE", &begindate, "END_DATE", &enddate);
If &status=%OptEng_Fail Then
   QEOPT_WRK.MESSAGE_TEXT = "IS_MACHINE_AVAILABLE transaction failed.";
   Return;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
End-If;
/* Get output value from the IS_MACHINE_AVAILABLE transaction.  */
QEOPT_WRK.AVAILABLE_FLAG = &myopt.GetNumber("AVAILABLE_FLAG");
```

Or, the following example shows the use of the DetailedStatus property.

```
Local integer &status;
&status = myopt.RunSynch("SOLVE");
if &status=%OptEng_Fail and &myopt.DetailedStatus=%OptEng_Method_Disabled then
   <perform some action>
End-if;
```

SetTraceLevel

Syntax

SetTraceLevel(*component*, *severity*)

Description

SetTraceLevel sets the severity level at which events are logged for a given component.

When using the DetailedStatus OptEngine property, keep the following in mind:

- The value returned by SetTraceLevel is the operational status of the optimization engine.
- The DetailedStatus OptEngine property indicates the completion status of the OptEngine method call SetTraceLevel.

For example, SetTraceLevel can return %OptEng_Fail and DetailedStatus is %OptEng_DB_Updates_Pending. For SetTraceLevel, DetailedStatus can have the value:

- %OptEng_Success: indicates that the function completed successfully.
- %OptEng_Fail: indicates that the function failed.
- %OptEng_Method_Disabled: indicates that the method is disabled or not valid.
- %OptEng_DB_Updates_Pending: indicates that database updates are pending.

Parameters

component

Use one of the following PeopleCode constants: Opt_Engine, Opt_Utility, Opt_Datacache, or Opt_Plugin.

severity

Use one of the following PeopleCode constants. These options set the degree to which errors are logged. You can set the tracing levels differently for various parts of your program. This enables you to control the amount of trace information that your program generates.

The following list shows the order of the severity, starting with the highest level. For example, %Severity_Error logs %Severity _Fatal, %Severity_Status, and %Severity_Error messages, while the system filters out other messages. Keep in mind that the higher the severity, the greater the performance overhead.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- %Severity_Fatal
- %Severity_Status
- %Severity_Error
- %Severity_Warn
- %Severity_Info
- %Severity_Trace1
- %Severity_Trace2

Returns

This method returns a constant. Valid values are:

Value	*Description*
%OptEng_Success	Returned if method succeeds.
%OptEng_Fail	Returned if the method fails.

Example

```
Local OptEngine &myopt;
Local integer &status;
Local string &machname;
Local datetime &begindate;
Local datetime &enddate;

&myopt = GetOptEngine("PATSMITH");

&status = &myopt.SetTraceLevel(%Opt_Engine, %Severity_Warn);
if &status = %OptEng_Fail then
   <example: notify user that set trace action has failed>
End-if;
```

ShutDown

Syntax

ShutDown()

Description

The ShutDown method requests the optimization engine to shut down.

If the optimization engine cannot be contacted for shutdown, the return status is %OptEng_Fail and the DetailedStatus property is OptEng_Not_Available.

When using the DetailedStatus OptEngine property, keep the following in mind:

- The value returned by Shutdown is the operational status of the optimization engine.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- The DetailedStatus OptEngine property indicates the completion status of the OptEngine method call Shutdown.

For example, Shutdown can return %OptEng_Fail and DetailedStatus is %OptEng_DB_Updates_Pending. For Shutdown, DetailedStatus can have the value:

- %OptEng_Success: indicates that the function completed successfully.
- %OptEng_Fail: indicates that the function failed.
- %OptEng_Method_Disabled: indicates that the method is disabled or not valid.
- %OptEng_DB_Updates_Pending: indicates that database updates are pending.

Note: Before this method is called, CreateOptEngine or GetOptEngine must be called. Call ShutDown to shut down optimization engines even when running in Application Engine.

Parameters

None.

Returns

This method returns a constant. Valid values are:

Value	*Description*
%OptEng_Success	Returned if method succeeds.
%OptEng_Fail	Returned if the method fails.

Example

This PeopleCode example shows an optimization engine being shut down:

```
Local OptEngine &myopt;
Local integer &status;
&myopt = GetOptEngine("PATSMITH");
/* Shut down the optimization engine */
&status = &myopt.ShutDown();
If &status=%OptEng_Fail Then
   QEOPT_WRK.MESSAGE_TEXT = "PATSMITH optimization engine shutdown failed.";
   Return;
Else
   QEOPT_WRK.MESSAGE_TEXT = "PATSMITH optimization engine shutdown successful.";
   Return;
End-If;
```

The following example shows the use of the DetailedStatus property:

```
Local integer &status;
&status = myopt.ShutDown();
if &status=%OptEng_Fail and &myopt.DetailedStatus=%OptEng_Method_Disabled then
   <perform some action>
End-if;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

OptEngine Class Properties

This section lists the optimization properties for the OptEngine PeopleCode class. The properties are listed in alphabetical order.

DetailMsgs

Description

The DetailMsgs property returns a list of messages generated by an optimization engine. Use DetailMsgs after you use the RunAsynch and RunSynch methods to check the status messages for an optimization transaction.

If the transaction fails, detailed messages are automatically shown to the user. If the transaction succeeds, warnings and informational messages may be generated by the transaction. Use this property to retrieve those messages and make them available to the user.

DetailMsgs provides a two-dimensional array containing the message set ID, the message number in the message catalog, and any arguments. Each row in the two-dimensional array has the following structure:

1. Message set ID.
2. Message number.
3. Number of message arguments.
4. Argument1.
5. Argument2.
6. Argument3.
7. Argument4.
8. Argument5.

A maximum of five arguments is supported for each message.

Note: To hold the property value returned, you need to declare an array of array of type *Any*.

Note: Before this method is called, you must call CreateOptEngine or GetOptEngine.

Example

```
Local OptEngine &myopt;
Local integer &status;
Local string &piid;

Local string &string;
Local array of array of any &arrArray;

&NEWLINE = Char(10);
&string = "";

&piid = GetRecord(Record.PSOPTPRBINST).GetField(Field.PROBINST).Value;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
&myopt = GetOptEngine(&piid);

&status = &myopt.RunSynch("TEST_TRANSACTION");

If (&status = %OptEng_Success) then

&arrArray = &myopt.DetailMsgs;
For &iloop = 1 To &arrArray.Len

   &string = &string | &NEWLINE | MsgGetText(&arrArray [&iloop][1] /*message set*
/,
   &arrArray [&iloop][2] /*message id*/, "Message Not Found",&arrArray[&iloop][4],
   &arrArray [&iloop][5],&arrArray [&iloop][6],
&arrArray [&iloop][7],&arrArray[&iloop][8]);

End-For;

GetLevel0().GetRow(1).GetRecord(Record.QE_FUNCLIB_OPT).DESCRLONG.Value = &string;
End-If;
```

DetailedStatus

Description

The DetailedStatus property contains the detailed execution status of an OptEngine method after the method is executed.

Example

```
Local integer &status;
&status = myopt.ShutDown();
if &status=%OptEng_Fail and &myopt.DetailedStatus=%OptEng_Method_Disabled then
   <perform some action>
End-if;
```

OptBase Application Class

This PeopleCode application class is part of the PT_OPT_BASE application package. It establishes the basic framework for developing PeopleCode that invokes the Optimization PeopleCode plug-in. To use the plug-in, you develop a application class that extends the OptBase application class. OptBase contains the following types of methods:

- A set of base methods that you can extend for the purpose of handling input and output parameters.

  You can use them within any method you develop that corresponds by name to a transaction in an analytic type definition. These methods apply to the parameters that are defined for the transaction in the analytic type.

- A set of abstract placeholder methods that you can use to implement callback capability.

  You must extend these if you designate one or more records as callback records in your analytic type definition, even if you don't add any functionality to the methods.

- An abstract placeholder method, Init, that you can extend if you want to do any preprocessing before your first Optimization PeopleCode plug-in transaction runs.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Note: The analytic type definition to which these methods apply is the one that specifies this derived application class.
The CreateOptInterface function is the only optimization built-in function that you can use within an application class that you extend from the OptBase application class, or within PeopleCode that you call from that application class.

Optbase Callback Methods

PeopleSoft Optimization Framework has a built-in callback functionality when the OptInterface PeopleCode calls an Optimization PeopleCode plug-in transaction, it first determines whether you designated one or more records in your analytic type definition as callback records. For each callback record, the framework determines if any the record's database rows have been inserted, deleted, or updated since the optimization datacache was populated. If any changes have occurred, the framework propagates those changes to the datacache before invoking the transaction.

PeopleSoft provides methods that the framework uses to apply its callback functionality. In combination with the framework's callback changes, you might want to perform additional processing for your own purposes, including updating any derived data structures that are used by your optimization application. You can accomplish this by extending the callback methods and adding your own PeopleCode. Each callback method launches under different circumstances.

Note: Don't call any of these methods in your own PeopleCode. They're called automatically at the appropriate moment by PeopleSoft Optimization Framework, which enables your added functionality to run within each method.

Following is a list of the abstract callback placeholder methods documented as part of the PT_OPT_BASE:OptBase application class:

- OptInsertCallback

  This method launches when the framework propagates to the datacache any database insertions encountered for a callback record.

- OptDeleteCallback

  This method launches when the framework propagates to the datacache any database deletions encountered for a callback record.

- OptPreUpdateCallback

  This method launches before the framework propagates each database update encountered for a callback record.

- OptPostUpdateCallback

  This method launches after the framework propagates each database update encountered for a callback record.

- OptRefreshCallback

  This method launches after the framework propagates all database deletions, insertions, and updates encountered for all callback records.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Important! If any record in your analytic type definition is designated a callback record, you must ensure that you extend all of the callback methods in your extended class, even if each extended method contains only a Return statement. Otherwise your Optimization PeopleCode plug-in will fail.

See "Configuring Analytic Type Records" (PeopleTools 8.54: Optimization Framework).

OptBase Class Methods

This section discusses the abstract base class placeholder methods for the PT_OPT_BASE:OptBase application class. The methods are listed in alphabetical order.

GetParmDate

Syntax

```
GetParmDate(parmName, &parmVal)
```

Description

The GetParmDate method retrieves a Date parameter value that passed as input by any method you develop that corresponds to an Optimization PeopleCode plug-in transaction. You develop the transaction method in an application class that you derive from the OptBase application class.

Parameters

parmName	Specify the name of the parameter as it's defined for the Optimization PeopleCode plug-in transaction.
&parmVal	Specify a Date variable to contain the value passed as input by the parameter.

Returns

A Boolean value: True if the method is successful, False otherwise.

GetParmDateArray

Syntax

```
GetParmDateArray(parmName, &parmVal)
```

Description

The GetParmDateArray method retrieves a Date array parameter value that passed as input by any method you develop that corresponds to an Optimization PeopleCode plug-in transaction. You develop the transaction method in an application class that you derive from the OptBase application class.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

parmName	Specify the name of the parameter as it's defined for the Optimization PeopleCode plug-in transaction.
&parmVal	Specify a Date array variable to contain the value passed as input by the parameter.

Returns

A Boolean value: True if the method is successful, False otherwise.

GetParmDateTime

Syntax

```
GetParmDateTime(parmName, &parmVal)
```

Description

The GetParmDateTime method retrieves a DateTime parameter value that passed as input by any method you develop that corresponds to an Optimization PeopleCode plug-in transaction. You develop the transaction method in an application class that you derive from the OptBase application class.

Parameters

parmName	Specify the name of the parameter as it's defined for the Optimization PeopleCode plug-in transaction.
&parmVal	Specify a DateTime variable to contain the value passed as input by the parameter.

Returns

A Boolean value: True if the method is successful, False otherwise.

GetParmDateTimeArray

Syntax

```
GetParmDateTimeArray(parmName, &parmVal)
```

Description

The GetParmDateTimeArray method retrieves a DateTime array parameter value that passed as input by any method you develop that corresponds to an Optimization PeopleCode plug-in transaction. You develop the transaction method in an application class that you derive from the OptBase application class.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

parmName	Specify the name of the parameter as it's defined for the Optimization PeopleCode plug-in transaction.
&parmVal	Specify a DateTime array variable to contain the value passed as input by the parameter.

Returns

A Boolean value: True if the method is successful, False otherwise.

GetParmNumber

Syntax

```
GetParmNumber(parmName, &parmVal)
```

Description

The GetParmNumber method retrieves a Number parameter value that passed as input by any method you develop that corresponds to an Optimization PeopleCode plug-in transaction. You develop the transaction method in an application class that you derive from the OptBase application class.

Parameters

parmName	Specify the name of the parameter as it's defined for the Optimization PeopleCode plug-in transaction.
&parmVal	Specify a Number variable to contain the value passed as input by the parameter.

Returns

A Boolean value: True if the method is successful, False otherwise.

GetParmNumberArray

Syntax

```
GetParmNumberArray(parmName, &parmVal)
```

Description

The GetParmNumberArray method retrieves a Number array parameter value that passed as input by any method you develop that corresponds to an Optimization PeopleCode plug-in transaction. You develop the transaction method in an application class that you derive from the OptBase application class.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

parmName	Specify the name of the parameter as it's defined for the Optimization PeopleCode plug-in transaction.
&parmVal	Specify a Number array variable to contain the value passed as input by the parameter.

Returns

A Boolean value: True if the method is successful, False otherwise.

GetParmInt

Syntax

```
GetParmInt(parmName, &parmVal)
```

Description

The GetParmInt method retrieves an Integer parameter value that passed as input by any method you develop that corresponds to an Optimization PeopleCode plug-in transaction. You develop the transaction method in an application class that you derive from the OptBase application class.

Parameters

parmName	Specify the name of the parameter as it's defined for the Optimization PeopleCode plug-in transaction.
&parmVal	Specify an Integer variable to contain the value passed as input by the parameter.

Returns

A Boolean value: True if the method is successful, False otherwise.

GetParmIntArray

Syntax

```
GetParmIntArray(parmName, &parmVal)
```

Description

The GetParmIntArray method retrieves a Number array parameter value that passed as input by any method you develop that corresponds to an Optimization PeopleCode plug-in transaction. You develop the transaction method in an application class that you derive from the OptBase application class.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

parmName	Specify the name of the parameter as it's defined for the Optimization PeopleCode plug-in transaction.
&parmVal	Specify a Number array variable to contain the value passed as input by the parameter.

Returns

A Boolean value: True if the method is successful, False otherwise.

GetParmString

Syntax

```
GetParmString(parmName, &parmVal)
```

Description

The GetParmString method retrieves a String parameter value that passed as input by any method you develop that corresponds to an Optimization PeopleCode plug-in transaction. You develop the transaction method in an application class that you derive from the OptBase application class.

Parameters

parmName	Specify the name of the parameter as it's defined for the Optimization PeopleCode plug-in transaction.
&parmVal	Specify a String variable to contain the value passed as input by the parameter.

Returns

A Boolean value: True if the method is successful, False otherwise.

GetParmStringArray

Syntax

```
GetParmStringArray(parmName, &parmVal)
```

Description

The GetParmStringArray method retrieves a String array parameter value that passed as input by any method you develop that corresponds to an Optimization PeopleCode plug-in transaction. You develop the transaction method in an application class that you derive from the OptBase application class.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

parmName	Specify the name of the parameter as it's defined for the Optimization PeopleCode plug-in transaction.
&parmVal	Specify a String array variable to contain the value passed as input by the parameter.

Returns

A Boolean value: True if the method is successful, False otherwise.

GetParmTime

Syntax

GetParmTime(*parmName, &parmVal*)

Description

The GetParmTime method retrieves a Time parameter value that passed as input by any method you develop that corresponds to an Optimization PeopleCode plug-in transaction. You develop the transaction method in an application class that you derive from the OptBase application class.

Parameters

parmName	Specify the name of the parameter as it's defined for the Optimization PeopleCode plug-in transaction.
&parmVal	Specify a Time variable to contain the value passed as input by the parameter.

Returns

A Boolean value: True if the method is successful, False otherwise.

GetParmTimeArray

Syntax

GetParmTimeArray(*parmName, &parmVal*)

Description

The GetParmTimeArray method retrieves a Time array parameter value that passed as input by any method you develop that corresponds to an Optimization PeopleCode plug-in transaction. You develop the transaction method in an application class that you derive from the OptBase application class.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

parmName	Specify the name of the parameter as it's defined for the Optimization PeopleCode plug-in transaction.
&parmVal	Specify a Time array variable to contain the value passed as input by the parameter.

Returns

A Boolean value: True if the method is successful, False otherwise.

Init

Syntax

```
Init()
```

Description

The Init method launches when the CreateOptEngine built-in function loads an analytic instance that uses the Optimization PeopleCode plug-in.

Use this method to perform additional processing for your own purposes, including checking table data, or any functionality you want to apply before any plug-in transactions run. You accomplish this by adding your own PeopleCode to the extended method.

Don't call this method in your own PeopleCode. It's called automatically at the appropriate moment by PeopleSoft Optimization Framework, which enables your added functionality to run before any other code in your extended class.

Note: If you don't extend this method, PeopleSoft Optimization Framework calls its base version from the OptBase application class.

Parameters

None.

Returns

A Boolean value: True if the method is successful, False otherwise.

OptDeleteCallback

Syntax

```
OptDeleteCallback(&Record)
```

Description

The OptDeleteCallback method launches when PeopleSoft Optimization Framework propagates to the datacache any database deletions that it encounters for a callback record.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Use this method to perform additional processing for your own purposes, including modifying any derived data structures that might be affected by the deletion. You accomplish this by adding your own PeopleCode to the extended method.

Don't call this method in your own PeopleCode. It's called automatically at the appropriate moment by PeopleSoft Optimization Framework, which enables your added functionality to run.

Important! If you designate any record in the analytic type definition as a callback record, you must ensure that you extend this callback method in your derived class, even if the extended method contains only a Return statement. Otherwise the Optimization PeopleCode plug-in will fail.

Parameters

&Record Specifies a record variable that contains the keys of the data row to be deleted.

Returns

A Boolean value: True if the method is successful, False otherwise.

OptInsertCallback

Syntax

`OptInsertCallback``(`*`&Record`*`)`

Description

The OptInsertCallback method launches when PeopleSoft Optimization Framework propagates to the datacache any database insertion that it encounters for a callback record.

Use this method to perform additional processing for your own purposes, including modifying any derived data structures that might be affected by the insertion. You accomplish this by adding your own PeopleCode to the extended method.

Don't call this method in your own PeopleCode. It's called automatically at the appropriate moment by PeopleSoft Optimization Framework, which enables your added functionality to run.

Important! If you designate any record in the analytic type definition as a callback record, you must ensure that you extend this callback method in your derived class, even if the extended method contains only a Return statement. Otherwise the Optimization PeopleCode plug-in will fail.

Parameters

&Record Specifies a record variable that contains the new data row to be inserted.

Returns

A Boolean value: True if the method is successful, False otherwise.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

OptPostUpdateCallback

Syntax

OptPostUpdateCallback(*&OldRecord*, *&NewRecord*)

Description

The OptPostUpdateCallback method launches after PeopleSoft Optimization Framework propagates to the datacache any database update that it encounters for a callback record.

Use this method to perform additional processing for your own purposes, including modifying any derived data structures that might have been affected by the update. You accomplish this by adding your own PeopleCode to the extended method. The parameters provide the previous and current content of the row.

Don't call this method in your own PeopleCode. It's called automatically at the appropriate moment by PeopleSoft Optimization Framework, which enables your added functionality to run.

Important! If you designate any record in the analytic type definition as a callback record, you must ensure that you extend this callback method in your derived class, even if the extended method contains only a Return statement. Otherwise the Optimization PeopleCode plug-in will fail.

Parameters

&OldRecord	Specifies a record variable that contains the pre-update content of the data row that was updated.
&NewRecord	Specifies a record variable that contains the post-update content of the data row that was updated.

Returns

A Boolean value: True if the method is successful, False otherwise.

OptPreUpdateCallback

Syntax

OptPreUpdateCallback(*&OldRecord*, *&NewRecord*)

Description

The OptPreUpdateCallback method launches before PeopleSoft Optimization Framework propagates to the datacache any database update that it encounters for a callback record.

Use this method to perform additional processing for your own purposes, including modifying any derived data structures that might be affected by the update. You accomplish this by adding your own PeopleCode to the extended method. The parameters provide the current and future content of the row.

Don't call this method in your own PeopleCode. It's called automatically at the appropriate moment by PeopleSoft Optimization Framework, which enables your added functionality to run.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Important! If you designate any record in the analytic type definition as a callback record, you must ensure that you extend this callback method in your derived class, even if the extended method contains only a Return statement. Otherwise the Optimization PeopleCode plug-in will fail.

Parameters

&OldRecord	Specifies a record variable that contains the pre-update content of the data row to be updated.
&NewRecord	Specifies a record variable that contains the post-update content of the data row to be updated.

Returns

A Boolean value: True if the method is successful, False otherwise.

OptRefreshCallback

Syntax

OptRefreshCallback()

Description

The OptRefreshCallback method launches after PeopleSoft Optimization Framework propagates to the datacache all database insertions, deletions, and updates that it encounters for all callback records.

Use this method to perform additional processing for your own purposes, including modifying any derived data structures that might be affected by the modifications. You accomplish this by adding your own PeopleCode to the extended method.

Don't call this method in your own PeopleCode. It's called automatically at the appropriate moment by PeopleSoft Optimization Framework, which enables your added functionality to run.

Important! If you designate any record in the analytic type definition as a callback record, you must ensure that you extend this callback method in your derived class, even if the extended method contains only a Return statement. Otherwise the Optimization PeopleCode plug-in will fail.

Parameters

None.

Returns

A Boolean value: True if the method is successful, False otherwise.

SetOutputParmDate

Syntax

SetOutputParmDate(*parmName*, *&parmVal*)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the SetOutputParmDate method to pass a Date parameter value as output from any method you develop that corresponds to an Optimization PeopleCode plug-in transaction. You develop the transaction method in an application class that you derive from the OptBase application class.

Parameters

parmName	Specify the name of the parameter as it's defined for the Optimization PeopleCode plug-in transaction.
&parmVal	Specify a Date variable that contains a value to be passed as output by the parameter.

Returns

A Boolean value: True if the method is successful, False otherwise.

SetOutputParmDateArray

Syntax

SetOutputParmDateArray(*parmName, &parmVal*)

Description

Use the SetOutputParmDateArray method to pass a Date array parameter value as output from any method you develop that corresponds to an Optimization PeopleCode plug-in transaction. You develop the transaction method in an application class that you derive from the OptBase application class.

Parameters

parmName	Specify the name of the parameter as it's defined for the Optimization PeopleCode plug-in transaction.
&parmVal	Specify a Date array variable that contains a value to be passed as output by the parameter.

Returns

A Boolean value: True if the method is successful, False otherwise.

SetOutputParmDateTime

Syntax

SetOutputParmDateTime(*parmName, &parmVal*)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the SetOutputParmDateTime method to pass a DateTime parameter value as output from any method you develop that corresponds to an Optimization PeopleCode plug-in transaction. You develop the transaction method in an application class that you derive from the OptBase application class.

Parameters

parmName	Specify the name of the parameter as it's defined for the Optimization PeopleCode plug-in transaction.
&parmVal	Specify a DateTime variable that contains a value to be passed as output by the parameter.

Returns

A Boolean value: True if the method is successful, False otherwise.

SetOutputParmDateTimeArray

Syntax

SetOutputParmDateTimeArray(*parmName, &parmVal*)

Description

Use the SetOutputParmDateTimeArray method to pass a DateTime array parameter value as output from any method you develop that corresponds to an Optimization PeopleCode plug-in transaction. You develop the transaction method in an application class that you derive from the OptBase application class.

Parameters

parmName	Specify the name of the parameter as it's defined for the Optimization PeopleCode plug-in transaction.
&parmVal	Specify a DateTime array variable that contains a value to be passed as output by the parameter.

Returns

A Boolean value: True if the method is successful, False otherwise.

SetOutputParmNumber

Syntax

SetOutputParmNumber(*parmName, &parmVal*)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the SetOutputParmNumber method to pass a Number parameter value as output from any method you develop that corresponds to an Optimization PeopleCode plug-in transaction. You develop the transaction method in an application class that you derive from the OptBase application class.

Parameters

parmName	Specify the name of the parameter as it's defined for the Optimization PeopleCode plug-in transaction.
&parmVal	Specify a Number variable that contains a value to be passed as output by the parameter.

Returns

A Boolean value: True if the method is successful, False otherwise.

SetOutputParmNumberArray

Syntax

SetOutputParmNumberArray(*parmName, &parmVal*)

Description

Use the SetOutputParmNumberArray method to pass a Number array parameter value as output from any method you develop that corresponds to an Optimization PeopleCode plug-in transaction. You develop the transaction method in an application class that you derive from the OptBase application class.

Parameters

parmName	Specify the name of the parameter as it's defined for the Optimization PeopleCode plug-in transaction.
&parmVal	Specify a Number array variable that contains a value to be passed as output by the parameter.

Returns

A Boolean value: True if the method is successful, False otherwise.

SetOutputParmInt

Syntax

SetOutputParmInt(*parmName, &parmVal*)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the SetOutputParmInt method to pass an Integer parameter value as output from any method you develop that corresponds to an Optimization PeopleCode plug-in transaction. You develop the transaction method in an application class that you derive from the OptBase application class.

Parameters

parmName	Specify the name of the parameter as it's defined for the Optimization PeopleCode plug-in transaction.
&parmVal	Specify an Integer variable that contains a value to be passed as output by the parameter.

Returns

A Boolean value: True if the method is successful, False otherwise.

SetOutputParmIntArray

Syntax

SetOutputParmIntArray(*parmName, &parmVal*)

Description

Use the SetOutputParmIntArray method to pass a Number array parameter value as output from any method you develop that corresponds to an Optimization PeopleCode plug-in transaction. You develop the transaction method in an application class that you derive from the OptBase application class.

Parameters

parmName	Specify the name of the parameter as it's defined for the Optimization PeopleCode plug-in transaction.
&parmVal	Specify a Number array variable that contains a value to be passed as output by the parameter.

Returns

A Boolean value: True if the method is successful, False otherwise.

SetOutputParmString

Syntax

SetOutputParmString(*parmName, &parmVal*)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the SetOutputParmString method to pass a String parameter value as output from any method you develop that corresponds to an Optimization PeopleCode plug-in transaction. You develop the transaction method in an application class that you derive from the OptBase application class.

Parameters

parmName	Specify the name of the parameter as it's defined for the Optimization PeopleCode plug-in transaction.
&parmVal	Specify a String variable that contains a value to be passed as output by the parameter.

Returns

A Boolean value: True if the method is successful, False otherwise.

SetOutputParmStringArray

Syntax

SetOutputParmStringArray(*parmName, &parmVal*)

Description

Use the SetOutputParmStringArray method to pass a String array parameter value as output from any method you develop that corresponds to an Optimization PeopleCode plug-in transaction. You develop the transaction method in an application class that you derive from the OptBase application class.

Parameters

parmName	Specify the name of the parameter as it's defined for the Optimization PeopleCode plug-in transaction.
&parmVal	Specify a String array variable that contains a value to be passed as output by the parameter.

Returns

A Boolean value: True if the method is successful, False otherwise.

SetOutputParmTime

Syntax

SetOutputParmTime(*parmName, &parmVal*)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the SetOutputParmTime method to pass a Time parameter value as output from any method you develop that corresponds to an Optimization PeopleCode plug-in transaction. You develop the transaction method in an application class that you derive from the OptBase application class.

Parameters

parmName	Specify the name of the parameter as it's defined for the Optimization PeopleCode plug-in transaction.
&parmVal	Specify a Time variable that contains a value to be passed as output by the parameter.

Returns

A Boolean value: True if the method is successful, False otherwise.

SetOutputParmTimeArray

Syntax

```
SetOutputParmTimeArray(parmName, &parmVal)
```

Description

Use the SetOutputParmTimeArray method to pass a Time array parameter value as output from any method you develop that corresponds to an Optimization PeopleCode plug-in transaction. You develop the transaction method in an application class that you derive from the OptBase application class.

Parameters

parmName	Specify the name of the parameter as it's defined for the Optimization PeopleCode plug-in transaction.
&parmVal	Specify a Time array variable that contains a value to be passed as output by the parameter.

Returns

A Boolean value: True if the method is successful, False otherwise.

OptInterface Class Methods

This section discusses the optimization methods for the OptInterface PeopleCode class. The methods are listed in alphabetical order.

Note: You can use the OptInterface class methods only within an application class that you extend from the OptBase application class, or within PeopleCode that you call from that application class. This ensures that the OptInterface PeopleCode runs only on the optimization engine.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ActivateModel

Syntax

ActivateModel(*ModelID*, *SolverSettingID*)

Description

The ActivateModel method designates the specified model and solver setting as active. The model and the solver are initialized and populated with data from the current analytic instance.

Note: This method fails if the specified model (and by extension, one of its solver settings) is already active. If you want to activate a different solver setting for the same model, you must first deactivate the model.

See DeactivateModel.

Parameters

ModelID Specify the name of the optimization model you want to activate. This must be the name of one of the models associated with the analytic type definition.

SolverSettingID Specify the name of the solver setting you want to activate. This is the name you specified for the solver setting in the analytic type definition.

Returns

This method returns a constant value. Valid values are:

Value	*Description*
%OptInter_Success	Returned if method succeeds.
%OptInter_Fail	Returned if the solver fails to solve the problem.

Example

```
Local integer &result;
Local OptInterface &oi = CreateOptInterface();

&result = &oi.ActivateModel("QE_PSA_MODEL", "abc");
```

ActivateObjective

Syntax

ActivateObjective(*Model_Name*, *Objective_Name*)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the ActivateObjective method to activate the specified objective for an optimization model.

Parameters

Model_Name Specify the name of the model.

Objective_Name Specify the name of the objective.

Returns

This method returns a constant value. Valid values are:

Value	*Description*
%OptInter_Success	Returned if method succeeds.
%OptInter_Fail	Returned if the solver fails to solve the problem.

DeactivateModel

Syntax

DeactivateModel(*ModelID*)

Description

The DeactivateModel method detaches the solver from the specified model.

Parameters

ModelID Specify the name of the optimization model you want to deactivate. This must be the name of one of the models associated with the analytic type definition.

Returns

This method returns a constant value. Valid values are:

Value	*Description*
%OptInter_Success	Returned if method succeeds.
%OptInter_Fail	Returned if the solver fails to solve the problem.

Example

```
Local integer &result;
Local OptInterface &oi = CreateOptInterface();
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
&result = &oi.DeactivateModel("QE_PSA_MODEL");
```

DumpMsgToLog

Syntax

DumpMsgToLog(*LogSeverity*, *Message*)

Description

The DumpMsgToLog method writes the specified status message to the optimization engine log file, with the specified severity.

Parameters

LogSeverity Specify the severity level of the message, as one of the following system constants:

- %Severity_Fatal
- %Severity_Status
- %Severity_Error
- %Severity_Warn
- %Severity_Info
- %Severity_Trace1
- %Severity_Trace2

Message Specify as a string the text of the log message.

Returns

None.

FindRowNum

Syntax

FindRowNum(*&Record* [, *startrow* [, *endrow* [, *field_list*]]])

Where *field_list* is a list of field names in the form:

[*fieldname1* [, *fieldname2*]]...

Description

The FindRowNum method determines the row number of a row in the datacache rowset. You provide a record with key values, and this method finds the row with the same key values and returns its row number.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

&Record Specify a record with the same structure as the records that comprise the rowset, with its key fields populated.

startrow Specify as an integer the starting row number of the search. Specify 0 to search from the first row in the rowset.

endrow Specify as an integer the ending row number of the search. Specify 0 to search through the last row in the rowset.

fieldname Specify the name of a field in the input record which contains a value to be matched. You can specify one or more field names, in any order.

Note: If you use this parameter, the fields specified here are used to search, instead of the record's key fields. Any value that doesn't correspond to a field name is ignored.

Returns

The row number of the row containing the specified key values, or 0 if no row is found.

Example

The following example searches the whole scroll to find the partial key OPT_SITE:

```
Local Record &rec = CreateRecord(Scroll.OPT_TRANSCOST);
Local Optineterface &oi;

&rec.OPT_SITE.value = "New York";
int nRowNum = &oi.FindRowNum(&rec, 0, 0, "OPT_SITE");
```

The following example searches from row 5 to row 15 with the full key values New York and San Jose:

```
Local Record &rec = CreateRecord(Scroll.OPT_TRANSCOST);
Local Optineterface &oi;

&rec.OPT_SITE.value = "New York";
&rec.OPT_STORE.value = "San Jose";
int nRowNum = &oi.FindRowNum(&rec, 5, 15);
```

GetSolution

Syntax

GetSolution(*ModelID*, *varArrayID*, *skipZero* [, *KeyFieldNames*, *KeyFieldValues* [, *&Solution*]])

Description

The GetSolution method retrieves the model solution values generated by the Solve method.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

ModelID

Specify as a string the name of the optimization model for which you want the solution. This is the name used for the model definition in Application Designer.

varArrayID

Specify as a string the name of the variable array being optimized. Your application documentation should provide this name.

skipZero

Indicate whether solutions with a value of zero should be fetched. This parameter takes a Boolean value:

- True: Don't fetch solutions with a zero value. This can increase the performance of the GetSolution method if zero values aren't meaningful.
- False: Do fetch solutions with a zero value.

KeyFieldNames* and *KeyFieldValues

Specify a set of key field names as an array of string and a set of key field values as an equal length array of ANY, with one key field value corresponding to each key field name. You use these arrays to restrict the set of returned solutions. Solutions are returned only for model variables with the specified key field values.

Note: If you provide either of these arrays, you must provide both. You can include each parameter from the variable array at most only once.

&Solution

Specify a rowset to contain the solutions.

Returns

This method returns a constant value. Valid values are:

Value	*Description*
%OptInter_Success	Returned if method succeeds.
%OptInter_Fail	Returned if the solver fails to solve the problem.

Example

```
Local array of string &strArray;
Local array of any &valArray;
Local integer &index;
Local Rowset &rowSet;
Local integer &result;
Local string &modelId = "QE_PSA_MODEL";
Local string &varArrayName = "X";
Local boolean &bSkipZero = True;

Local OptInterface &oi = CreateOptInterface();
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
&strArray = CreateArrayRept("", 0);
&valArray = CreateArrayAny();
&rowSet = CreateRowset(Record.QEOPT_VAL_X_WRK);

&strArray [1] = "EMPLID";
&valArray [1] = 1;
&strArray [2] = "ORDER_ID";
&valArray [2] = 23;

/* fetch only the part of the solution where  EMPLID = 1 and ORDER_ID = 23 */
&result = &oi.GetSolution(&modelId, &varArrayName,
 &bSkipZero, &strArray, &valArray, &rowSet);
```

GetSolutionDetail

Syntax

GetSolutionDetail(*ModelID*, *SolutionType*, *Name*, *&Solution*)

Description

The GetSolutionDetail method retrieves the model solution detail of the specified type generated by the Solve method. You can retrieve dual value, slack value, or reduced cost information.

Parameters

ModelID

Specify as a string the name of the optimization model for which you want the solution detail. This is the name used for the model definition in Application Designer.

SolutionType

Specify a system constant indicating the type of solution detail you want to retrieve. The value you specify here determines the content of the *Name* and *&Solution* parameters.

- %OPT_DUAL: Retrieve the dual value attributes of the specified constraint block.
- %OPT_SLACK: Retrieve the slack value attributes of the specified constraint block.
- %OPT_RCOST: Retrieve the reduced cost attributes of the specified variable array.

Name

If you specified a *SolutionType* of %OPT_DUAL or %OPT_SLACK, specify here the name of a constraint block from the active model.

If you specified a *SolutionType* of %OPT_RCOST, specify here the name of a variable array from the active model.

&Solution

Specify a rowset to contain the solution details. The rowset should have the same key fields as the constraint block or the variable array you specified with the *Name* parameter.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

This method returns a constant value. Valid values are:

Value	*Description*
%OptInter_Success	Returned if method succeeds.
%OptInter_Fail	Returned if solver fails to solve the problem.

Example

```
Local Rowset &dual_rowset;
Local integer &result;
Local OptInterface &oi = CreateOptInterface();
Local string &modelId = "QE_PSA_MODEL";
Local string &varArrayName = "X";
Local string &constrName = "Constraint_1";

/* fetch dual values for Contraint "Constraint_1"
 in a rowset based on the QEOPT_C1_WRK record */

&dual_rowset = CreateRowset(Record.QEOPT_C1_WRK);
&result = &oi.GetSolutionDetail(&modelId, %Opt_Dual, &constrName, &dual_rowset);
```

IsModelActive

Syntax

IsModelActive(*ModelID*)

Description

Use the IsModelActive method to determine if the model specified by *ModelId* is active before it is used.

Parameters

ModelID Specify the model ID as a string. This is the name used for the model definition in Application Designer.

Returns

A Boolean value: true if the model is active, false otherwise.

RestoreBounds

Syntax

RestoreBounds(*modelID* [,*varArrayID*])

Description

The RestoreBounds method returns the bounding values of the specified variable array or arrays to the current settings in the specified model.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

If you previously called the SetVariableBounds method with the *changeModelBounds* parameter set to true for any variable or variable array, those bounding values still apply.

Parameters

modelID Specify as a string the name of the optimization model for which you want to restore the bounding values. This is the name used for the model definition in Application Designer.

varArrayID Specify as a string the name of a variable array for which you want to restore the bounding values. Your application documentation should provide this name. If you don't specify a variable array name, the bounding values are restored for all variable arrays in the specified model.

Returns

%OptInter_Success if the method succeeds, %OptInter_Fail otherwise.

SetVariableBounds

Syntax

```
SetVariableBounds(modelID, varArrayID, boundType, lowerBound, upperBound, &keyRecord
[, changeModelBounds])
```

Description

The SetVariableBounds method overrides the bounding values specified for a model variable array, or for a variable within the array.

Parameters

modelID Specify as a string the name of the optimization model for which you want to override the bounding values. This is the name used for the model definition in Application Designer.

varArrayID Specify as a string the name of the variable array being optimized. Your application documentation should provide this name.

boundType Specify a system constant indicating which bounding values to override. The value you specify here determines how the *lowerBound* and *upperBound* parameters are applied to the specified model.

- %OPT_LOWER_BOUND: Override only the lower bound as specified by the *lowerBound* parameter. The *upperBound* parameter is ignored.
- %OPT_UPPER_BOUND: Override only the upper bound as specified by the *upperBound* parameter. The *lowerBound* parameter is ignored.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- %OPT_BOUND_BOTH: Override both the lower bound and the upper bound as specified by the *lowerBound* and *upperBound* parameters, respectively.

lowerBound

Specify as a number the lower bound that should be applied to a variable or a variable array if the *boundType* parameter permits the override. You can also set this parameter to one of the following system constants:

upperBound

Specify as a number the upper bound that should be applied to a variable or a variable array if the *boundType* parameter permits the override. You can also set this parameter to one of the following system constants:

&keyRecord

Specify a record with the same key fields as the variable array being optimized. To override the bounding values specified for a single variable within the array, populate the record's key fields to specify the variable. To override the bounding values specified for the entire variable array, set all of the record's fields to a null value.

Note: You must either provide values for all keys, or set them all to null values.

---

changeModelBounds

Specify a Boolean value:

- true: Indicates that the specified model should be updated in memory to reflect the specified variable bounds. Any analytic instance that invokes this model from the active optimization engine is affected by these settings, which are propagated to the solver in memory. This is the default value if you omit this parameter.
- false: Indicates that the specified model should not be updated in memory, and that the specified variable bounds apply only to the next time the Solve method is called.

Returns

%OptInter_Success if the method succeeds, %OptInter_Fail otherwise.

Example

```
Local Record &rec;
Local integer &result;
Local OptInterface &oi = CreateOptInterface();
Local float &objval = 0.0;
Local string &modelId = "QE_PSA_MODEL";
Local string &varArrayName = "X";
Local float &lb = 0.0;
Local float &ub = 0.0;

&rec = CreateRecord(Record.QEOPT_VAL_X_WRK);
&rec.QEOPT_RESINDEX.Value = 1;
&rec.QEOPT_SOLINDEX.Value = 2;
&rec.QEOPT_TIMEINDEX.Value = 3;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
&result = &oi.SetVariableBounds(&modelId, &varArrayName,
 %Opt_Upper_Bound, &lb, &ub, &rec, False);
```

SetVariableType

Syntax

SetVariableType(*modelID*, *varArrayID*, *varType*)

Description

Use the SetVariableType method to change the data type of a model variable array.

Parameters

ModelID

Specify as a string the name of the optimization model for which you want to change the variable type. This must be the name of one of the models associated with the analytic type definition.

varArrayID

Specify as a string the name of the variable array for which you want to change the variable type. Your application documentation should provide this name.

varType

Specify one of the following system constants representing the new variable type:

- %Opt_Var_Cont: Represents a continuous variable type, which can be any floating point value.
- %Opt_Var_Bin: Represents a binary variable type, for which the value can be only 0 or 1.
- %Opt_Var_Int: Represents an integer variable type, which can be any integer.

Returns

%OptInter_Success if the method succeeds, %OptInter_Fail otherwise.

Example

```
Local OptInterface &oi = CreateOptInterface();
Local string &varArrayName = "X";
Local integer &result;

&result = &oi.SetVariableType("QE_PSA_MODEL",  &varArrayName, %Opt_Var_Bin);

If (&result <> %OptInter_Success) Then
   &oi.DumpMsgToLog(%Severity_Status, "Failed to change variable type ");
End-If;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Solve

Syntax

```
Solve(modelID, SolutionType [, &objValue [, name-value_pairs]])
```

Where *name-value_pairs* is a list of solver setting parameter values in the form:

```
[parmname1, parmvalue1 [, parmname2, parmvalue2]]...
```

Description

The Solve method solves the specified model using the currently active solver settings, and provides an objective value as the solution output. You can override the solver setting parameters. The returned solution status is a predefined system constant.

Parameters

ModelID

Specify as a string the name of the optimization model you want to solve. This is the name used for the model definition in Application Designer.

SolutionType

Specify a system constant indicating the type of solution detail you want the model to be solved for.

- %OPT_DUAL: Generate dual value attributes.
- %OPT_SLACK: Generate slack value attributes.
- %OPT_RCOST: Generate reduced cost attributes.

You can also combine any or all of these system constants, by connecting them with a plus sign (+), for example: %OPT_DUAL + %OPT_RCOST.

&objValue

Specify a reference to a variable of type float. This variable contains the output objective value produced by the solver upon successfully solving the specified optimization model.

parmname* and *parmvalue

Specify a solver setting parameter ID and value to override the original value you specified for the solver setting in the analytic type definition. You can override any or all of the solver setting parameter values.

See "Configuring Models for Optimization" (PeopleTools 8.54: Optimization Framework).

Returns

One of the following system constants:

%OptInter_Fail: The solver fails to solve the problem.

%Opt_Optimal: The solution is optimal.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

%Opt_Infeasible: The solution is infeasible.

%Opt_Unbounded: The solution is unbounded.

%Opt_Timeup: The solver reached the time limit specified in the solver setting.

%Opt_Iterlimit: The solver reached the limit on the number of iterations specified in the solver setting.

%Opt_LP_Max_Sols: The solver generated maximum number of solutions without improvement.

%Opt_Idle: The solution shows no improvement in a specified time limit.

%Opt_Unknown: The solver status is unknown.

%Opt_MIP_NumSolutions: The specified number of solutions corresponding to an MIP solver reached.

%Opt_MIP_NumNodes: The specified number of nodes corresponding to an MIP solver reached.

%Opt_Aborted: The solver aborted.

%Opt_User_Exit: A user exit was encountered.

%Opt_First_LP_NoOpt: While solving an MIP, the first LP solution obtained was not optimal.

Example

Following is an example of the basic use of the Solve method:

```
Local OptInterface &oi = CreateOptInterface();

Local float &objval = 0.0;
Local integer &result;
Local string &modelId = "QE_PSA_MODEL";
Local string &varArrayName = "X";
Local integer &solType;

&solType = %Opt_RCost + %Opt_Dual + %Opt_Slack;

/* Solve the problem */
&result = &oi.Solve("QE_PSA_MODEL", &solType, &objval);

If & result = %Opt_Optimal Then
   &oi.DumpMsgToLog(%Severity_Warn, " Solution Status =  " Optimal !!!");
Else
   &oi.DumpMsgToLog(%Severity_Warn, " Solution Status =  " | &result );
End-If;
```

Following is an example of a solver setting parameter override:

```
Local OptInterface &oi = CreateOptInterface();
Local float &objval = 0.0;
Local integer &result;

/* This overrides the solver setting for MPS_Filename and generates
 an MPS file called myfile.mps instead of the name specified
 in the current solver setting parameter. */

&result = &oi.Solve("QE_PSA_MODEL", %Opt_Primal, &objval, "MPS_FileName",
 "myfile");
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Chapter 32

Page Class

Understanding Page Class

Use the page class to manipulate a page in a component. The most common use of this class is to hide or display a page in a component, either based on field values or the level of security of the user.

Generally, the PeopleCode used to manipulate a page object is associated with PeopleCode in the Activate event.

Note: The page object should not be used until after the page processor has loaded the page: do not instantiate this object in RowInit PeopleCode, use it in PreBuild, PostBuild or Activate instead.
In addition, if you need to hide the current page, PeopleSoft recommends using the PreBuild event for your program.

Related Links

"Component Build Processing in Update Modes" (PeopleTools 8.54: PeopleCode Developer's Guide)

Shortcut Considerations

An expression of the form

PAGE.*pagename.property*

is equivalent to `GetPage(`**PAGE.***name*`).`*property*. For example, the following two lines of code are equivalent:

```
PAGE.MANAGER_APPROV.DisplayOnly = False;
```

```
GetPage(PAGE.MANAGER_APPROV).DisplayOnly = False;
```

Data Type of a Page Object

Use the Page data type to declare Page objects. For example,

```
Local Page &MYPAGE;
```

Scope of a Page Object

A page object can be instantiated from PeopleCode only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Use this object only in PeopleCode programs that are associated with an online process, not in an Application Engine program, a message subscription, a Component Interface, and so on.

In addition, the page object should not be used until after the page processor has loaded the page: do not instantiate this object in RowInit PeopleCode. Use it in PostBuild or Activate instead.

Page Class Built-in Function

"GetPage" (PeopleTools 8.54: PeopleCode Language Reference)

Page Class Properties

In this section, we discuss each Page class properties.

CopyURLLink

Description

Use this property to enable the http link for a component. Clicking this link copies the address (URL) of the page to the clipboard. This is a Pagebar property.

Note: If you select the Disable Pagebar checkbox for the component in Application Designer, you cannot set any of the Pagebar properties using PeopleCode. If you deselect the Copy URL Link checkbox for the component in Application Designer, you can still set this option using this property.

This property is read-write.

Related Links

"Setting Use Properties" (PeopleTools 8.54: Application Designer Developer's Guide)

CustomizePageLink

Description

Use this property to enable Customize Page link for a component. Clicking this link enables the user to control the initial display of the component. This property takes a Boolean value, true, the user can control the display, false otherwise. This is a Pagebar property.

Note: If you select the Disable Pagebar checkbox for the component in the Application Designer, you cannot set any of the Pagebar properties using PeopleCode. If you deselect the Customize Page Link checkbox for the component in Application Designer, you can still set this option using this property.

This property is read-write.

Related Links

"Setting Use Properties" (PeopleTools 8.54: Application Designer Developer's Guide)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

DisplayOnly

Description

Use this property to make a page display-only, or to enable a page so the fields can be edited. This property takes a Boolean value: True if the page is display-only, False otherwise.

Note: You cannot enable or disable the current page.

The value of DisplayOnly for a page is restored to the value set in Application Designer when the user goes to another component. This means you must set DisplayOnly for the page each time a component is accessed.

This property is read-write.

Example

```
If &MYPAGE.DisplayOnly Then
   &MYPAGE.Visible = True;
Else
   &MYPAGE.Visible = False;
End-If;
```

HelpLink

Description

Use this property to enable the Help link for a component. Clicking this link accesses the online help PeopleBook entry for the current page. This is a Pagebar property.

Note: If you select the Disable Pagebar checkbox for the component in the Application Designer, you cannot set and of the Pagebar properties using PeopleCode. If you deselect the Help Link checkbox for the component in Application Designer, you can still set this option using this property.

This property is read-write.

Related Links

"Setting Use Properties" (PeopleTools 8.54: Application Designer Developer's Guide)

Name

Description

This property returns a reference to the page name definition (a string value.)

This property is read-only.

Example

```
&MYPAGENAME = &MYPAGE.Name;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

NewWindowLink

Description

Use this property to enable New Window link for a component. Clicking this link opens a new browser window with the search page for the current component. Users can view or enter data in the new window. This is a Pagebar property.

Note: If you select the Disable Pagebar checkbox for the component in the Application Designer, you cannot set any of the Pagebar properties using PeopleCode. If you deselect the New Window Link checkbox for the component in Application Designer, you can still set this option using this property.

This property is read-write.

Related Links

"Setting Use Properties" (PeopleTools 8.54: Application Designer Developer's Guide)

Visible

Description

Use this property to set the visibility of a page. If this property is set to True, the page is visible. If this property is set to False, the page is not visible. When the visibility is changed, the component tabs and menus are also automatically changed to reflect the new settings. Menus and tabs return to their original values when the user navigates to another component. In addition, if a page is set to be hidden in the component definition, you can change the value of the page to be visible at runtime.

Oracle recommends using the PreBuild event if you need to hide the current page.

Important! If the visibility of the current page is set to False in a PeopleCode program, then you must invoke the TransferPage function to transfer control to a visible page.

Note: Page visibility alone (as set by the Visible property) does not determine whether a user can see a page. Visibility plus the permissions to access the page together determine whether a specific page is displayed to a particular user.

Example

In the following example, a page is hidden based on the value of the current field.

```
If PAYROLE_TYPE = "Global" Then
   PAGE.JOB_EARNINGS.Visible = False;
End-If;
```

Related Links

"TransferPage" (PeopleTools 8.54: PeopleCode Language Reference)

"Setting Page Permissions" (PeopleTools 8.54: Security Administration)

"Setting Page Attributes" (PeopleTools 8.54: Application Designer Developer's Guide)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Chapter 33

PeopleSoft Search Framework Classes

Understanding the PeopleSoft Search Framework Classes

In previous PeopleTools releases, search functionality was provided in a non-declarative fashion in which search engine indexes were built using custom PeopleCode and Application Engine programs. Each PeopleSoft application used a unique method for creating and maintaining search artifacts like collections and indexes—all of which required search engine-specific calls, commands, syntax, and so on.

The PeopleSoft Search Framework enables application developers and implementation teams to create search artifacts in a declarative manner and to deploy and maintain search indexes using one standard interface, regardless of PeopleSoft application.

The PeopleSoft Search Framework consists of PeopleSoft components (pages and records provided by PeopleTools), which provide a centralized interface for configuring PeopleSoft integration with the search engine, creating search artifacts such as search definitions and search categories, and building and maintaining search indexes.

In addition to the user interface, the PeopleSoft Search Framework is supported by several PeopleCode application classes including PT_SEARCH and several PTSF application packages. The PT_SEARCH application package provides the administration and query service interfaces for integration with web service based free-text search engines. The root package comprises a factory class, interfaces, superclasses, and implementations for classes that are not dependent on a specific search engine.

Related Links

Search Technology

Differences Between the PeopleSoft Search Framework Classes and Verity Search Classes

The Verity search classes were implemented specifically to support PeopleTools integration with the Verity search engine. Conversely, the PeopleSoft Search Framework was developed to provide an interaction layer that is independent of any specific search engine. In particular, the PeopleSoft Search Framework classes documented in this chapter are general purpose classes not associated with any particular search engine.

The PeopleSoft Search Framework was designed to integrate with any number of free-text search solutions, each of which could be implemented as a subpackage under the PT_SEARCH application package. At this time, the only search solution supported by PeopleTools “as delivered” is Oracle Secure Enterprise Search (SES), which is implemented in the PT_SEARCH:SESIMPL subpackage.

The Verity search objects are implemented as PeopleCode built-in objects. PeopleSoft Search Framework objects are implemented through an open source PeopleCode application package. In both cases, the

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

primary interaction class is the SearchQuery class. With Verity, a SearchQuery object is instantiated using the PortalRegistry or Session built-in classes. With the PeopleSoft Search Framework, a SearchQuery object is instantiated from a SearchQueryService object. The SearchQueryService object itself is created using the SearchFactory class.

Related Links

Understanding the Verity Search Classes

Instantiating a SearchQuery Object

Instantiating a SearchQuery Object

With the PeopleSoft Search Framework, a SearchQuery object is instantiated by instantiating a SearchFactory object, which is used to create a SearchQueryService object. The SearchQuery object is then instantiated from the SearchQueryService.

The high-level program flow is as follows:

```
import PT_SEARCH:SearchFactory;
import PT_SEARCH:SearchQueryService;
import PT_SEARCH:SearchQuery;

Local PT_SEARCH:SearchFactory &factory = create PT_SEARCH:SearchFactory();
Local PT_SEARCH:SearchQueryService &svc = &factory.CreateQueryService("default");
Local PT_SEARCH:SearchQuery &srchQuery = &svc.CreateQuery();
```

Importing PeopleSoft Search Framework Classes

The PeopleSoft Search Framework classes are application classes, not built-in classes, like Rowset, Field, Record, and so on. Before you can use these classes in your PeopleCode program, you must import them into your program.

An import statement either names a particular application class or imports all the classes in a package.

Using the asterisks after the package name makes all the application classes directly contained in the named package available. Application classes contained in subpackages of the named package are not made available.

Performing a Simple Search

The following example code demonstrates how to retrieve properties of the SearchResultCollection and how to iterate over the results in the collection:

1. Import the application package.

   ```
   import PT_SEARCH:*;
   ```

2. Create an instance of SearchQueryService and SearchFactory.

   ```
   Local PT_SEARCH:SearchFactory &factory = create PT_SEARCH:SearchFactory();
   Local PT_SEARCH:SearchQueryService &svc = &factory.CreateQueryService("default⇒
   ");
   ```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

3. Instantiate the SearchQuery object.

```
Local PT_SEARCH:SearchQuery &srchQuery = &svc.CreateQuery();
```

4. Initialize the search query by setting properties.

```
&srchQuery.QueryText = "some text";
&srchQuery.Language = &lang_cd;
&srchQuery.MarkDuplicates = False;
&srchQuery.RemoveDuplicates = False;
```

5. Execute the search query.

   Use the Execute method and specify two integer parameters: *start* determines the index of the first document, *size* determines the number of search documents to return "page" of results.

```
Local number &start = 1;
Local number &size = 10;

Local PT_SEARCH:SearchResultCollection &results;
&results = &srchQuery.Execute(&start, &size);
```

6. Process the search query results

   The search query returns a SearchResultCollection. To process this collection: The SearchResultCollection contains SearchResult objects. Each SearchResult has its own methods to access its attributes such as Title, Summary, URL Link, and so on. Each SearchResult also optionally has custom attributes that can be accessed through the SearchFieldCollection object.

```
Local number &i, &j;
Local number &score;
Local string &title;
Local string &summary;
Local datetime &lastMod;
Local string &url;
Local string &name;
Local string &value;

Rem - Get a couple return properties;

Local number &docCount = &results.GetDocumentCount();
Local number &hitCount = &results.GetEstimatedHitCount();

Rem - Iterate through the search results;

Local PT_SEARCH:SearchResult &curResult;
Local PT_SEARCH:SearchFieldCollection &customs;
For &i = 1 To &results.GetDocumentCount()
   &curResult = &results.Item(&i);
   &score = &curResult.GetScore();
   &title = &curResult.GetTitle();
   &summary = &curResult.GetSummary();
   &lastMod = &curResult.GetLastModified();
   &url = &curResult.GetUrlLink();

   /* Do something with these result attributes       */

   Rem - Get the custom fields of the result if any;

   &customs = &curResult.GetCustomAttributes();
   If (&customs <> Null) Then

      Rem - Iterate through custom fields of the result;
      For &j = 1 To &customs.Count()
         &name = &customs.Item(&j).Name;
         &value = &customs.Item(&j).Value;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
            /* do something with the custom field       */

         End-For;
      End-If;
   End-For;

   Rem - Calculate the number of additional pages in the results;
   Local integer &pages;

   &pages = Idiv(&hitCount, &size);
   If Mod(&hitCount, &size) > 0 Then
      &pages = &pages + 1;
   End-If;

   Rem - Render the additional pages as links;
```

7. Get the page number for the next request.

   Re-execute the search query to retrieve the next page. Increment *start* to the next page; then invoke the Execute method.

```
Rem - Get the requested page from the link clicked by the user;
Rem - Store the value in the &req_page variable;
Local integer &req_page;

Rem - Calculate the new start value and re-execute the query;
&start = (&req_page - 1) * &size + 1;
&results = &srchQuery.Execute(&start, &size);
```

The preceding example returns the results in chunks, or pages, which provides better query performance than returning all results at once. However, you could elect to return all results in a single search query. In that case, you will need to consider the maximum number of results returned by the search engine. For example, when SES is the search provider, 200 is the default value for the maximum number of results. In this case, the Execute method would be invoked as follows to return all results at once:

```
Local number &start = 1;
Local number &size = 200;

Local PT_SEARCH:SearchResultCollection &results;
&results = &srchQuery.Execute(&start, &size);
```

Related Links

Exception Handling

Exception Handling

The PeopleSoft Search Framework uses the try/catch exception construct to handle special conditions that interrupt normal program execution. When special runtime conditions are encountered, the PeopleSoft Search Framework will construct and throw objects of the Exception class or some class derived from the Exception class. There are two main categories of PeopleSoft Search Framework exceptions:

- Those thrown when the PeopleSoft Search Framework detects a special condition.
- Those thrown when the search provider responds with anything other than what was expected for the given request.

The second category of exceptions is necessarily search engine specific since these are coming from the search provider. For example, there are two exception classes defined in the SESIMPL application

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

subpackage: SESQueryServiceException and SESAdminServiceException. As the names imply, the first can be thrown by calls to the SearchQueryService methods and the second can be thrown by calls to the SearchAdminService methods. Both of these exception classes expose SOAPFaultCode and SOAPFaultString properties that are returned by SES. The SESAdminServiceException exposes additional properties which are defined in Appendix B: Error Messages of the *Oracle® Secure Enterprise Search Administration API Guide 11g Release 1 (11.1.2.0.0).*

Virtually all methods of all classes in the PeopleSoft Search Framework can throw an exception; therefore, Oracle recommends that you put all calls to the PeopleSoft Search Framework classes within try-catch blocks.

The following example builds on the previous example that processed search results. In this example, the results processing is augmented by try-catch exception handling:

```
import PT_SEARCH:*;
import PT_SEARCH:SESIMPL:EXCEPTION:*;

/* instantiate and initialize the query object */
/* ...                                         */
/* execute the query */
Local PT_SEARCH:SearchResultCollection &results;

try
   &results = &qry.Execute(&start, &size);
catch PT_SEARCH:SESIMPL:EXCEPTION:SESQueryServiceException &sesEx
   MessageBox(0, "", 0, 0, "The search could not be perfomed.");
   MessageBox(0, "", 0, 0, "The Search Provider returned an error.");
   MessageBox(0, "", 0, 0, "SOAP fault: ", &sesEx.SoapFaultString);
   WriteToLog(0, &sesEx.SoapFaultCode);
   WriteToLog(0, &sesEx.SoapFaultString);
   Exit;
catch Exception &psEx
   MessageBox(0, "", 0, 0, "The search could not be perfomed.");
   MessageBox(0, "", 0, 0, "Exception: ", &psEx.DefaultText);
   WriteToLog(0, &psEx.DefaultText);
   Exit;
end-try;

/* process the results */
try
   Local number &docCount = &results.GetDocumentCount();
   Local number &hitCount = &results.GetEstimatedHitCount();

   Local PT_SEARCH:SearchResult &curResult;
   Local PT_SEARCH:SearchFieldCollection &customs;
   For &i = 1 To &results.GetDocumentCount()
      &curResult = &results.Item(&i);

      &score = &curResult.GetScore();
      &title = &curResult.GetTitle();
      &summary = &curResult.GetSummary();
      &lastMod = &curResult.GetLastModified();
      &url = &curResult.GetUrlLink();
      /* do something with the values */
      &customs = &curResult.GetCustomAttributes();
      If (&customs <> Null) Then
         /* iterate over custom fields of the result */
         For &j = 1 To &customs.Count()
            &name = &customs.Item(&j).Name;
            &value = &customs.Item(&j).Value;
            /* do something with the name/value pair */
         End-For;
      End-If;
   End-For;
catch Exception &ex
   /* encountered an exception while processing results */
   /* inspect the exception to determine appropriate action */
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
end-try;
```

Related Links

Understanding Exception Class

PeopleSoft Search Framework Classes Reference

This reference section documents the following classes from the PT_SEARCH application package:

- AssociatedFacet class
- FacetFilter class
- FacetNode class
- SearchAttribute class
- SearchCategory class
- SearchFactory class
- SearchField class
- SearchFieldCollection class
- SearchFilter class
- SearchFilterGenerator class
- SearchQuery class
- SearchQueryCollection class
- SearchQueryService class
- SearchResult class
- SearchResultCollection class

This reference section also documents the following classes from the PTSF_SECURITY application package: SearchAuthnQueryFilter class.

PeopleSoft Search Framework Classes Built-in Functions

"EncodeSearchCode" (PeopleTools 8.54: PeopleCode Language Reference)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

AssociatedFacet Class

This section provides an overview of the AssociatedFacet class and discusses AssociatedFacet class methods.

The AssociatedFacet class is used to extend the PeopleTools-delivered PeopleSoft Search Framework by allowing the use of application-specific association keys. This class must be implemented to return the value of the AssociationValue property of the FacetFilter class.

Related Links

AssociationValue

AssociatedFacet Class Methods

In this section, the AssociatedFacet class methods are presented in alphabetical order.

getAssociatedFacetValue

Syntax

getAssociatedFacetValue(*category, facet, user*)

Description

Use this method to return an application-specific association key for the specified user.

An application that requires an associated facet value must implement and extend the getAssociatedFacetValue abstract method.

Note: This is an abstract method.

Parameters

category	Specifies the search category name as a string.
facet	Specifies the facet name as a string.
user	Specifies the search user name as a string.

Returns

A String value.

FacetFilter Class

This section provides an overview of the FacetFilter class and discusses:

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- FacetFilter class methods.
- FacetFilter class properties.

The FacetFilter class is used to filter the search results on one or more facet values. Facets are aspects, properties, or characteristics of a piece of data. In a PeopleSoft application, this could be PeopleSoft metadata (for example, SETID or business unit), or it could be any other attribute of the data. For example, job openings could be classified (faceted) by location, department or job family, working hours, pay scale, posting date, business unit, SETID, and so on. Facets allow for “filtered search” or “filtered navigation” of search results.

Related Links

"Working with the Search Results" (PeopleTools 8.54: Search Technology)

"Working with Search Results" (PeopleTools 8.54: Applications User's Guide)

FacetFilter Class Methods

In this section, the FacetFilter class methods are presented in alphabetical order.

clearFacetSorting

Syntax

clearFacetSorting()

Description

Use this method to reset facet sorting on all levels to default sorting values.

Parameters

None.

Returns

None.

FacetFilter

Syntax

FacetFilter(*FacetName*, *Path*)

Description

Use this constructor to instantiate a FacetFilter object for a specific facet to indicate the facet and path.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

FacetName	Specifies the name of the facet as a string.
Path	Specifies the value of the facet as a string.

Returns

A FacetFilter object.

Example

The following examples demonstrate four ways to create a facet filter:

- Use the SearchCategory class to return the initial list of facet filters with empty paths as an array of FacetFilter objects:

```
Local PT_SEARCH:SearchCategory &srchCat = create PT_SEARCH:SearchCategory("MY_⇒
SRCH_CAT");
&qry.Categories = CreateArray(&srchCat);

&qry.FacetFilters = &srchCat.GetFacetFilters();
```

- When requesting a specific facet for the first time, specify an empty string for the path:

```
Local PT_SEARCH:FacetFilter &facetFilter = create PT_SEARCH:FacetFilter("LOCAT⇒
ION","")
```

- When the facet is hierarchical, specify the hierarchy in the path. For example, the LOCATION facet could have a hierarchy of country/state/city. To filter by country, use the following filter:

```
Local PT_SEARCH:FacetFilter &facetFilter = create PT_SEARCH:FacetFilter("LOCAT⇒
ION","USA")
```

- To filter by state, use the following filter:

```
Local PT_SEARCH:FacetFilter &facetFilter = create PT_SEARCH:FacetFilter("LOCAT⇒
ION","USA/CA")
```

Related Links

GetFacetFilters

getFacetSortings

Syntax

getFacetSortings()

Description

Use this method to return a map of facet sortings as a StringMap object. If no facet sorting is defined, the map will be of size 0.

Parameters

None.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

A StringMap Object.

getFacetValuesSortType

Syntax

getFacetValuesSortType(*level*)

Description

Use this method to return the sort type for the specified level.

Parameters

level Specifies the level in the facet path hierarchy as an integer. For facets without a path hierarchy, specify *1*.

Returns

A string value.

hasCustomFacetSorting

Syntax

hasCustomFacetSorting(*level*)

Description

Use this method to verify whether the default facet sorting has been overridden for the specified level.

Parameters

level Specifies the level in the facet path hierarchy as an integer. For facets without a path hierarchy, specify *1*.

Returns

A Boolean value. True if facet sorting has been overridden for the specified level, False otherwise.

sortFacetValuesAlphabetically

Syntax

sortFacetValuesAlphabetically(*level, sort_ascending*)

Description

Use this method to sort facet values for the specified level alphabetically.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

level Specifies the level in the facet path hierarchy as an integer. For facets without a path hierarchy, specify *1*.

sort_ascending Specifies the sorting order: True for ascending order and False for descending order sorting.

Returns

None.

sortFacetValuesByDocumentCount

Syntax

sortFacetValuesByDocumentCount(*level, sort_ascending*)

Description

Use this method to sort facet values for the specified level by the document count.

Parameters

level Specifies the level in the facet patch hierarchy as an integer. For facets without a path hierarchy, specify *1*.

sort_ascending Specifies the sorting order: True for ascending order and False for descending order sorting.

Returns

None.

sortFacetValuesByType

Syntax

sortFacetValuesByType(*level, sort_type*)

Description

Use this method to define the sort type by specifying a string value. This method can be used instead of sortFacetValuesByDocumentCount, sortFacetValuesAlphabetically, and sortFacetValuesNumericallyof methods.

Parameters

level Specify the level in the facet path hierarchy. For facets without a path hierarchy, specify *1*.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

sort_type Specifies the sort type as one of the following string values:

- *ALPHA_DES* – Sort alphabetically descending.
- *ALPHA_ASC* – Sort alphabetically ascending.
- *COUNT_DES* – Sort by document count descending.
- *COUNT_ASC* – Sort by document count ascending.
- *NUMBER_ASC* – Sort numerically ascending.
- *NUMBER_DES* – Sort numerically descending.

Returns

None.

sortFacetValuesNumerically

Syntax

sortFacetValuesNumerically(*level, sort_ascending*)

Description

Use this method to sort facet values numerically for the specified level. If the facet values are not numbers, this method will cause an error when it is executed at run time.

Parameters

level Specifies the level in the facet path hierarchy as an integer. For facets without a path hierarchy, specify *1*.

sort_ascending Specifies the sorting order as a Boolean value: True for ascending order and False for descending order sorting.

Returns

None.

FacetFilter Class Properties

In this section, the FacetFilter class properties are presented in alphabetical order.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

AssociationValue

Description

Use this property to set or return the association value for this facet as a string. The association value is used to select the first level of associated facets.

This property is read-write.

FacetLabel

Description

Use this property to set or return the long description for the facet as a string. This description appears as the label for the facet in the user interface.

This property is read-write.

FacetName

Description

Use this property to set or return the name of the facet as a string.

This property is read-write.

Path

Description

Use this property to set or return the value for facet as a path string.

This property is read-write.

Example

The Path property is implicitly set to the value of the *Path* parameter supplied in the constructor for the FacetFilter class. In this example, the Path property is set to USA/CA:

```
&facetFilter = create PT_SEARCH:FacetFilter("LOCATION","USA/CA")
```

However, the Path property can also be explicitly set as in the following example:

```
&facetFilter.Path = "USA/CO/Denver";
```

FacetNode Class

This section provides an overview of the FacetNode class and discusses:

- FacetNode class methods.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- FacetNode class properties.

The FacetNode class extends the FacetFilter class and is used to return the list of facet node values along with other information about the facet nodes.

Facet nodes are used to render the list of facet values of a particular facet for a given search. This list of facet nodes is retrieved using GetFacetNodes method of the SearchResultCollection. Since a facet node is constructed with a facet path, this information can be used to create a facet filter indicating that the user has chosen to filter the results further based on the facet node.

Related Links

FacetFilter Class

GetFacetNodes

FacetNode Class Methods

In this section, the FacetNode class methods are presented in alphabetical order.

addChild

Syntax

addChild(*&node*)

Description

Use this method to add a child facet node to the current facet node.

Parameters

&node	Specifies the child facet node as a FacetNode object.

Returns

None.

FacetNode

Syntax

FacetNode(*FacetName*, *NodeName*, *Path*, *DisplayValue*, *DocCount*)

Description

Use this constructor to instantiate a FacetNode object for a specific facet.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

FacetName	Specifies the name of the facet as a string and is used to refer to that member of the superclass.
NodeName	Specifies the name of this facet node as a string.
Path	Specifies the value of the facet as a string and is used to refer to that member of the superclass.
DisplayValue	Specifies the display value for this facet node as a string.
DocCount	Specifies an integer representing the number of documents that would be returned if this facet node were selected as a search filter.

Returns

A FacetNode object.

getChildNodes

Syntax

```
getChildNodes()
```

Description

Use this method to return an array of child nodes.

Parameters

None.

Returns

An array of FacetNode objects.

Related Links

addChild

FacetNode Class Properties

In this section, the FacetNode class properties are presented in alphabetical order.

DisplayValue

Description

Use this property to set or return the display value for this facet node as a string.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-write.

DocumentCount

Description

Use this property to set or return an integer representing the number of documents that would be returned if this facet node were selected as a search filter.

This property is read-write.

FacetValue

Description

Use this property to set or return the value of this facet node as a string.

This property is read-write.

The FacetName, FacetValue, and DisplayValue are all closely related. For example, consider the following facet filter: FacetFilter("LOCATION","USA"). These properties would have the following values:

- FacetName: LOCATION
- FacetValue: USA
- DisplayValue: United States

Related Links

DisplayValue
FacetName

HasChildren

Description

Use this property to set or return a Boolean value indicating whether this facet node has children.

This property is read-write.

SearchAttribute Class

This section provides an overview of the SearchAttribute class and discusses:

- SearchAttribute class methods.
- SearchAttribute class properties.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The SearchAttribute class represents a search attribute, which is an alias to a search query field. Search attributes enable you to hide the attribute name and query field name from the end user, who will see the search attribute display name.

An array of search attributes are returned using the GetAllAttributes, GetConfiguredFilterAttributes, GetNonConfiguredFilterAttributes, and GetRequestedAttributes methods of the SearchCategory class.

Related Links

GetAllAttributes
GetConfiguredFilterAttributes
GetNonConfiguredFilterAttributes
GetRequestedAttributes

SearchAttribute Class Methods

In this section, the SearchAttribute class methods are presented in alphabetical order.

SearchAttribute

Syntax

SearchAttribute(*Name, Type*)

Description

Use this constructor to instantiate a SearchAttribute object for a specific attribute.

Parameters

Name Specifies the name of the attribute as a string .

Type Specifies the type for this attribute as a one-character string. The values for *Type* can be as follows:

- D – Date
- N – Number
- S – String

Returns

A SearchAttribute object.

SearchAttribute Class Properties

In this section, the SearchAttribute class properties are presented in alphabetical order.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Display

Description

Use this property to set or return a string to be used as the display name for this attribute within the user interface.

This property is read-write.

Name

Description

Use this property to set or return a string representing the name of this search attribute.

This property is read-write.

Type

Description

Use this property to set or return a one-character sting indicating the type for this attribute. The values for this property can be as follows:

- D – Date
- N – Number
- S – String

This property is read-write.

SearchCategory Class

This section provides an overview of the SearchCategory class and discusses:

- SearchCategory class methods.
- SearchCategory class properties.

SearchCategory is the PeopleCode representation of a search category definition, which groups search data source definitions. A search category is a searchable collection of indexes. SearchCategory objects can only be constructed by giving the name of a search category definition that has already been saved to the database. In general SearchCategory objects are instantiated either to be assigned to the Categories property of a SearchQuery object or to be passed to methods of the SearchAdminService.

SearchCategory Class Methods

In this section, the SearchCategory class methods are presented in alphabetical order.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GetAllAttributes

Syntax

GetAllAttributes()

Description

Use this method to return the union of all the attributes available across all the search definitions assigned to this search category.

Parameters

None.

Returns

An array of SearchAttribute objects.

Related Links

SearchAttribute Class

GetConfiguredFilterAttributes

Syntax

GetConfiguredFilterAttributes()

Description

Use this method to return a list of advanced search filter attributes defined *and* configured for the advanced search for this search category. These are the attributes that have been configured on the Advanced Search Fields page.

Parameters

None.

Returns

An array of SearchAttribute objects.

Related Links

SearchAttribute Class

GetFacetFilters

Syntax

GetFacetFilters()

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use this method to return an array of facet filters for a specific search category. Dynamically building this array based on system metadata avoids the hard-coding of facet names in your PeopleCode programs. However, this means that this method can only be used for search categories defined on the local system (therefore, it cannot be used for universal search).

Parameters

None.

Returns

An array of FacetFilter objects.

Related Links

FacetFilter Class

GetLastIndexedDateTime

Syntax

```
GetLastIndexedDateTime()
```

Description

Use this method to return a DateTime value representing the oldest index that is current from all the indexed search definitions in this category. If no search definition in this category has ever been indexed, this method returns Null.

Parameters

None.

Returns

A DateTime value.

GetNonConfiguredFilterAttributes

Syntax

```
GetNonConfiguredFilterAttributes()
```

Description

Use this method to return a list of advanced search filter attributes defined *but not* configured for the advanced search for this search category. These are the attributes that have been defined for the search category but not configured on the Advanced Search Fields page.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

None.

Returns

An array of SearchAttribute objects.

Related Links

SearchAttribute Class

GetRequestedAttributes

Syntax

GetRequestedAttributes()

Description

Use this method to return the list of search attributes that have been configured as display-only attributes on the Display Fields page. Since this method returns the display label for these search attributes, you must also use the GetRequestedFields method to return the list of search fields to pass to the query API.

Parameters

None.

Returns

An array of SearchAttribute objects.

Related Links

SearchAttribute Class
GetRequestedFields

GetRequestedFields

Syntax

GetRequestedFields()

Description

Use this method to return the list of search fields that have been configured as display-only attributes on the Display Fields page. This array can then be passed to the RequestedFields method of the SearchQuery class. Since this method returns the query field names for the search attributes, you must also use the GetRequestedAttributes method to return the display labels to display in the user interface.

Parameters

None.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

An array of SearchField objects.

Example

```
PT_SEARCH:SearchCategory &cat = create PT_SEARCH:SearchCategory("MY_SRCH_CAT");
&qry.Categories = CreateArray(&cat);

&qry.RequestedFields = &cat.GetRequestedFields();
```

Related Links

GetRequestedAttributes
SearchField Class
RequestedFields

SearchCategory

Syntax

SearchCategory(*Name*)

Description

Use this constructor to instantiate a SearchCategory object populated with the data from the specified saved definition.

Parameters

Name	The name of the search category to instantiate as a string.

Returns

A SearchCategory object.

Example

```
import PT_SEARCH:SearchCategory;

Local PT_SEARCH:SearchCategory &SrchCat = create PT_SEARCH:SearchCategory("MySrchCa⇒
t");
```

Related Links

Categories
Constructors
Import Declarations

SearchCategory Class Properties

In this section, the SearchCategory class properties are presented in alphabetical order.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

DataSourceNames

Description

Use this property to return an array of string containing the names of the search definitions that have been assigned to this search category.

This property is effectively read-only.

Note: While this property is actually read-write, from PeopleCode, it is meant to be used in a read-only manner.

Displayname

Description

Use this property to return the long description (display) for the search category as a string.

This property is effectively read-only.

Note: While this property is actually read-write, from PeopleCode, it is meant to be used in a read-only manner.

Duplicates

Description

Use this property to return a string indicating whether duplicates have been set for this search category.

This property is effectively read-only.

Related Links

"Specifying General Search Category Settings" (PeopleTools 8.54: Search Technology)

IsDeployed

Description

Use this property to return a Boolean value indicating whether this search category has been deployed to a search provider.

This property is effectively read-only.

Note: While this property is actually read-write, from PeopleCode, it is meant to be used in a read-only manner.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Name

Description

Use this property to return the name of this SearchCategory object as a string.

This property is effectively read-only.

Note: While this property is actually read-write, from PeopleCode, it is meant to be used in a read-only manner.

ServiceName

Description

Use this property to return a string representing the name of the search engine instance to which this search category has been deployed.

This property is effectively read-only.

Note: While this property is actually read-write, from PeopleCode, it is meant to be used in a read-only manner.

SearchFactory Class

This section provides an overview of the SearchFactory class and discusses:

- SearchFactory class methods.
- SearchFactory class properties.

The SearchFactory class is a concrete factory class used to instantiate search engine-specific implementations of the SearchQueryService and other services.

SearchFactory Class Methods

In this section, the SearchFactory class methods are presented in alphabetical order.

CreateQueryService

Syntax

`CreateQueryService``(`*`name`*`)`

Description

Use this method to instantiate a search engine-specific SearchQueryService object. This search engine-specific search query service enables accessing search engine-specific attributes of a SearchQuery object

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

name Specifies the name of the search query service as a string.

Returns

A SearchQueryService object.

Example

```
import PT_SEARCH:SearchFactory;
import PT_SEARCH:SearchQueryService;

Local PT_SEARCH:SearchFactory &MySearchFactory = create PT_SEARCH:SearchFactory();

Local PT_SEARCH:SearchQueryService &MySrchQrySvc = &MySearchFactory.CreateQueryServ⇒
ice("default");
```

Related Links

SearchQueryService Class

SearchFactory

Syntax

SearchFactory()

Description

Use this constructor to instantiate a SearchFactory object, which allows you to instantiate a search-provider specific search query service.

Parameters

None.

Returns

A SearchFactory object.

Example

```
import PT_SEARCH:SearchFactory;

Local PT_SEARCH:SearchFactory &MySearchFactory = create PT_SEARCH:SearchFactory();
```

SearchFactory Class Properties

In this section, the SearchFactory class properties are presented in alphabetical order.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

DEFAULTSERVICE

Description

This property returns the name of the default search engine service as a string.

This property is read-only.

SearchField Class

This section provides an overview of the SearchField class and discusses: .

- SearchField class methods.
- SearchField class properties.

The SearchField class is a superclass that requires implementation of a search engine-specific subclass. A SearchField is returned by the First, Item, ItemByName, and Next methods of the SearchFieldCollection class.

Related Links

SearchFieldCollection Class

SearchField Class Methods

In this section, the SearchField class methods are presented in alphabetical order.

getAsDate

Syntax

```
getAsDate()
```

Description

Use this method to return the Value property as a Date value.

Note: This is an abstract method.

Parameters

None.

Returns

A Date value.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

Value

getAsDateTime

Syntax

getAsDateTime()

Description

Use this method to return the Value property as a DateTime value.

Note: This is an abstract method.

Parameters

None.

Returns

A DateTime value.

Related Links

Value

getAsInteger

Syntax

getAsInteger()

Description

Use this method to return the Value property as a Integer value.

Note: This is an abstract method.

Parameters

None.

Returns

An Integer value.

Related Links

Value

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

getAsNumber

Syntax

getAsNumber()

Description

Use this method to return the Value property as a Number value.

Note: This is an abstract method.

Parameters

None.

Returns

A Number value.

Related Links

Value

SearchField Class Properties

In this section, the SearchField class properties are presented in alphabetical order.

Name

Description

This property returns the name of the search field as a string.

This property is read-only.

Related Links

ItemByName

Type

Description

This property returns the data type of the search field as a one-character string as follows:

- D – Date
- N – Number

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- S – String

This property is read-only.

Value

Description

This property returns the value of the search field as a string. The Value property can be transformed from a String value to a Date, DateTime, Integer, or Number value using the methods of the SearchField class.

This property is read-only.

Related Links

getAsDate
getAsDateTime
getAsInteger
getAsNumber

SearchFieldCollection Class

This section provides an overview of the SearchFieldCollection class and discusses: SearchFieldCollection class methods.

The SearchFieldCollection class provides a collection of SearchField objects. Because the SearchFieldCollection class is a generic interface class, a search engine-specific subclass is required. A SearchFieldCollection is returned by the GetCustomAttributes method of the SearchResult class.

Related Links

SearchField Class
GetCustomAttributes

SearchFieldCollection Class Methods

In this section, the SearchFieldCollection class methods are presented in alphabetical order.

Count

Syntax

```
Count()
```

Description

Use this method to return the number of SearchField objects in the SearchField collection as an integer.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

None.

Returns

An integer.

First

Syntax

```
First()
```

Description

Use this method to return the first SearchField object in the SearchField collection. If the SearchField collection is empty, this method returns Null.

Parameters

None.

Returns

A SearchField object if successful, Null otherwise.

Related Links

SearchField Class

Item

Syntax

```
Item(index)
```

Description

Use this method to return the SearchField object at the position in the SearchField collection specified by the *index* parameter.

Parameters

index	Specifies the position of the SearchField object in the SearchField collection as an integer.

Returns

A SearchField object if successful, Null otherwise.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

SearchField Class

ItemByName

Syntax

ItemByName(*name*)

Description

Use this method to return the SearchField object specified by the *name* parameter.

Note: The ItemByName method does not set the index for the SearchField object returned. Therefore, the Next method cannot be used after a call to ItemByName.

Parameters

name	Specifies the name of the SearchField object as a string.

Returns

A SearchField object if successful, Null otherwise.

Related Links

SearchField Class

Next

Syntax

Next()

Description

Use this method to return the next SearchField object in the SearchField collection. This method can only be invoked after a successful invocation of the First, Item, or Next methods.

Note: The ItemByName method does not set the index for the SearchField object returned. Therefore, the Next method cannot be used after a call to ItemByName.

Parameters

None.

Returns

A SearchField object if successful, Null otherwise.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

First
Item
SearchField Class

SearchFilter Class

This section provides an overview of the SearchFilter class and discusses:

- SearchFilter class properties.
- SearchFilter class methods.

The SearchFilter class creates a filter for search results (similar to building a WHERE clause in a SQL statement) that is passed to the SearchQuery class.

SearchFilter Class Methods

In this section, the SearchFilter class methods are presented in alphabetical order.

setDateFilter

Syntax

setDateFilter(*date*)

Description

Use this method to set a Date value as the search filter.

Parameters

date	Specifies the search filter value as a Date value.

Returns

None.

Example

```
import PT_SEARCH:SearchFilter;

Local PT_SEARCH:SearchFilter &Srchflter;
Local date &Date = DateValue("10/09/11");

&Srchflter.setDateFilter(&Date);
```

Related Links

Value

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

FormatDateFilter

setDateTimeFilter

Syntax

setDateTimeFilter(*datetime*)

Description

Use this method to set a DateTime value as the search filter.

Parameters

datetime Specifies the search filter value as a DateTime value.

Returns

None.

Example

```
import PT_SEARCH:SearchFilter;

Local PT_SEARCH:SearchFilter &Srchflter;
Local datetime &Date_TIME = DateTimeValue("10/13/97 10:34:25 PM");

&Srchflter.setDateTimeFilter(&Date_TIME);
```

Related Links

Value
FormatDateTimeFilter

SearchFilter Class Properties

In this section, the SearchFilter class properties are presented in alphabetical order.

Field

Description

Use this property to set or return a SearchField object.

This property is read-write.

Related Links

SearchField Class

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

FilterConnector

Description

Use this property to return the filter connector (**&** or |) that is in effect when this search filter is a composite search filter. This property is set by the SearchFilterGenerator class.

This property is effectively read-only.

Related Links

Filters

SearchFilterGenerator Class

Filters

Description

Use this property to return an array of SearchFilter objects that define this search filter as a composite search filter. This property is set by the SearchFilterGenerator class

This property is effectively read-only.

Related Links

FilterConnector

SearchFilterGenerator Class

Operator

Description

Use this property to set or return the operator for the filter as a string. Depending on the type of the search attribute, the following operators can be used:

Operator	*String*	*Number*	*Date*
equals	X	X	X
notequals*	X	X	X
contains	X		
greaterthan		X	X
greaterthanequals		X	X
lessthan		X	X
lessthanequals		X	X

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

* The notequals operator can be used when EnableExtendedFilterOperators property is set to true.

This property is read-write.

Related Links

Type
EnableExtendedFilterOperators

Value

Description

Use this property to set or return the value for the filter as a string.

This property is read-write.

Use this property only when setting a string or a number (represented as a string) as a filter. If you wish to set a Date or a DateTime value as a filter, use the setDateFilter and setDateTimeFilter methods, respectively

Related Links

setDateFilter
SearchFilter Class Methods

SearchFilterGenerator Class

This section provides an overview of the SearchFilterGenerator class and discusses SearchFilterGenerator class methods.

The SearchFilterGenerator class is used to create composite search filters from different data types and operators. The SearchFilterGenerator class provides the flexibility to create a composite search filter by associating different filters using connectors such as **&** and |.

Note: The **&** is the default connector; therefore, for composite filters, MatchAll is implied and does not have to be explicitly specified.

Related Links

SearchFilter Class

SearchFilterGenerator Class Methods

In this section, the SearchFilterGenerator class methods are presented in alphabetical order.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

AddQueryFilter

Syntax

AddQueryFilter(*&srch_qry*)

Description

Use this method to push the composite query filter onto the array of filters in the SearchQuery object.

Parameters

&srch_qry	Specifies the query as a SearchQuery object.

Returns

None.

Related Links

SetQueryFilter
SearchQuery Class
Filters

AfterDate

Syntax

AfterDate(*srch_field, date*)

Description

Use this method to generate a date filter on the specified search field for dates after the specified value.

Parameters

srch_field	Specifies the search field name as a string.
date	Specifies the date as a DateTime value.

Returns

None.

Related Links

BeforeDate
EqualsDate
NotEqualsDate
OnOrAfterDate
OnOrBeforeDate

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

BeforeDate

Syntax

BeforeDate(*srch_field, date*)

Description

Use this method to generate a date filter on the specified search field for dates before the specified value.

Parameters

srch_field	Specifies the search field name as a string.
date	Specifies the date as a DateTime value.

Returns

None.

Related Links

AfterDate
EqualsDate
NotEqualsDate
OnOrAfterDate
OnOrBeforeDate

ContainsPartialWord

Syntax

ContainsPartialWord(*srch_field, fragment*)

Description

Use this method to generate a string filter that matches strings containing a word that begins with the specified partial word.

Parameters

srch_field	Specifies the search field name as a string.
fragment	Specifies the word fragment as a string.

Returns

None.

Related Links

ContainsPhrase

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ContainsWord
EqualsString
NotEqualsString

ContainsPhrase

Syntax

ContainsPhrase(*srch_field, phrase*)

Description

Use this method to generate a string filter that matches strings containing the exact phrase.

Parameters

srch_field	Specifies the search field name as a string.
phrase	Specifies the exact phrase as a string.

Returns

None.

Related Links

ContainsPartialWord
ContainsWord
EqualsString
NotEqualsString

ContainsWord

Syntax

ContainsWord(*srch_field, word*)

Description

Use the ContainsWord method to generate a string filter that matches strings containing the exact word or words. Words are separated by spaces and the logical *and* operator is implied; explicit logical operators are not supported between the words. This method forms the filter to find a match on all the words in the *word* parameter.

Note: While the *word* parameter can include one or more words, this method differs from the ContainsPhrase method.

Parameters

srch_field	Specifies the search field name as a string.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

word Specifies the exact word or words as a string.

Returns

None.

Example

Consider a document that includes the following sentence:

```
Apples are tastier than oranges.
```

The following use of ContainsWord will return a match.

```
&fg.ContainsWord("LONG_TEXT", "apples oranges");
```

However, the following use of ContainsPhrase will not return a match.

```
&fg.ContainsPhrase("LONG_TEXT", "apples oranges");
```

Related Links

ContainsPartialWord
ContainsPhrase
EqualsString
NotEqualsString

DateToDatetime

Syntax

DateToDatetime(*date*)

Description

Use this method to convert a Date value to DateTime value. The time portion of the value is set to 12:00:00.

Parameters

date Specifies the Date value to be converted.

Returns

A DateTime value.

Related Links

StringDateToDatetime

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

EndMatchAll

Syntax

EndMatchAll()

Description

Use this method to mark the end of a temporary composite search filter initiated by MatchAll or MatchAllReturnTrue. This temporary composite search filter is then pushed onto the array of filters for the preceding search filter.

Parameters

None.

Returns

None.

Related Links

MatchAll
MatchAllReturnTrue

EndMatchAny

Syntax

EndMatchAny()

Description

Use this method to mark the end of a temporary composite search filter initiated by MatchAny or MatchAnyReturnTrue. This temporary composite search filter is then pushed onto the array of filters for the preceding search filter.

Parameters

None.

Returns

None.

Related Links

MatchAny
MatchAnyReturnTrue

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

EqualsDate

Syntax

EqualsDate(*srch_field, date*)

Description

Use this method to generate a date filter on the specified search field for dates equal to the specified value.

Parameters

srch_field Specifies the search field name as a string.

date Specifies the date as a DateTime value.

Returns

None.

Related Links

AfterDate
BeforeDate
NotEqualsDate
OnOrAfterDate
OnOrBeforeDate

EqualsNumber

Syntax

EqualsNumber(*srch_field, number*)

Description

Use this method to generate a numeric filter on the specified search field for numbers equal to the specified value.

Parameters

srch_field Specifies the search field name as a string.

number Specifies the search value as a Number value.

Returns

None.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

GreaterThanEqualsNumber
GreaterThanNumber
LessThanEqualsNumber
LessThanNumber
NotEqualsNumber

EqualsString

Syntax

EqualsString(*srch_field, string*)

Description

Use this method to generate a string filter on the specified search field for strings equal to the specified value.

Parameters

srch_field	Specifies the search field name as a string.
string	Specifies the search string as a String value.

Returns

None.

Related Links

ContainsPartialWord
ContainsPhrase
ContainsWord
NotEqualsString

GreaterThanEqualsNumber

Syntax

GreaterThanEqualsNumber(*srch_field, number*)

Description

Use this method to generate a numeric filter on the specified search field for numbers greater than or equal to the specified value.

Parameters

srch_field	Specifies the search field name as a string.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

number Specifies the search value as a Number value.

Returns

None.

Related Links

EqualsNumber
GreaterThanNumber
LessThanEqualsNumber
LessThanNumber
NotEqualsNumber

GreaterThanNumber

Syntax

GreaterThanNumber(*srch_field, number*)

Description

Use this method to generate a numeric filter on the specified search field for numbers greater than the specified value.

Parameters

srch_field Specifies the search field name as a string.

number Specifies the search value as a Number value.

Returns

None.

Related Links

EqualsNumber
GreaterThanEqualsNumber
LessThanEqualsNumber
LessThanNumber
NotEqualsNumber

LessThanEqualsNumber

Syntax

LessThanEqualsNumber(*srch_field, number*)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use this method to generate a numeric filter on the specified search field for numbers less than or equal to the specified value.

Parameters

srch_field	Specifies the search field name as a string.
number	Specifies the search value as a Number value.

Returns

None.

Related Links

EqualsNumber
GreaterThanEqualsNumber
GreaterThanNumber
LessThanNumber
NotEqualsNumber

LessThanNumber

Syntax

LessThanNumber(*srch_field, number*)

Description

Use this method to generate a numeric filter on the specified search field for numbers less than the specified value.

Parameters

srch_field	Specifies the search field name as a string.
number	Specifies the search value as a Number value.

Returns

None.

Related Links

EqualsNumber
GreaterThanEqualsNumber
GreaterThanNumber
LessThanEqualsNumber
NotEqualsNumber

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

MatchAll

Syntax

MatchAll()

Description

Use this method to initiate a temporary composite search filter using the **&** filter connector between filters.

Parameters

None.

Returns

None.

Example

In the following example, the composite filter consists of two filters joined by the **&** filter connector:

```
&fg.MatchAll();
&fg.NotEqualsString("a", "x");
&fg.NotEqualsString("b", "y");
&fg.EndMatchAll();
```

Related Links

EndMatchAll

MatchAllReturnTrue

MatchAllReturnTrue

Syntax

MatchAllReturnTrue()

Description

Use this method to initiate a temporary composite search filter using the **&** filter connector between filters. Since successful execution of this method returns True, you can use this method in logical expressions.

Parameters

None.

Returns

A Boolean value.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

In the following example, the composite filter consists of two filters joined by the **&** filter connector:

```
If &fg.MatchAllReturnTrue() Then
   &fg.NotEqualsString("a", "x");
   &fg.NotEqualsString("b", "y");
   &fg.EndMatchAll();
End-If;
```

Related Links

EndMatchAll

MatchAll

MatchAny

Syntax

MatchAny( )

Description

Use this method to initiate a temporary composite search filter using the | filter connector between filters.

Parameters

None.

Returns

None.

Related Links

EndMatchAny

MatchAnyReturnTrue

MatchAnyReturnTrue

Syntax

MatchAnyReturnTrue( )

Description

Use this method to initiate a temporary composite search filter using the | filter connector between filters. Since successful execution of this method returns True, you can use this method in logical expressions.

Parameters

None.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

A Boolean value.

Example

In the following example, the final composite filter consists of two composite filters each consisting of two filters. The individual filters and the composite filters are all joined by the | filter connector:

```
If &fg.MatchAnyReturnTrue() Then

   If &fg.MatchAnyReturnTrue() Then
      &fg.LessThanNumber("c", 4);
      &fg.GreaterThanNumber("c", 5);
      &fg.EndMatchAny();
   End-If;

   If &fg.MatchAnyReturnTrue() Then
      &fg.ContainsWord("d", "x");
      &fg.EqualsString("e", "z");
      &fg.EndMatchAny();
   End-If;

   &fg.EndMatchAny();
```

Related Links

EndMatchAny

MatchAny

NotEqualsDate

Syntax

NotEqualsDate(*srch_field, date*)

Description

Use this method to generate a date filter on the specified search field for dates not equal to the specified value.

Parameters

srch_field	Specifies the search field name as a string.
date	Specifies the date as a DateTime value.

Returns

None.

Returns

None.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

AfterDate
BeforeDate
EqualsDate
OnOrAfterDate
OnOrBeforeDate

NotEqualsNumber

Syntax

NotEqualsNumber(*srch_field, number*)

Description

Use this method to generate a numeric filter on the specified search field for numbers not equal to the specified value.

Parameters

srch_field	Specifies the search field name as a string.
number	Specifies the search value as a Number value.

Returns

None.

Related Links

EqualsNumber
GreaterThanEqualsNumber
GreaterThanNumber
LessThanEqualsNumber
LessThanNumber

NotEqualsString

Syntax

NotEqualsString(*srch_field, string*)

Description

Use this method to generate a string filter on the specified search field for strings not equal to the specified value.

Parameters

srch_field	Specifies the search field name as a string.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

string	Specifies the search string as a String value.

Returns

None.

Related Links

ContainsPartialWord
ContainsPhrase
ContainsWord
EqualsString

OnOrAfterDate

Syntax

OnOrAfterDate(*srch_field, date*)

Description

Use this method to generate a date filter on the specified search field for dates on or after the specified value.

Parameters

srch_field	Specifies the search field name as a string.
date	Specifies the date as a DateTime value.

Returns

None.

Related Links

AfterDate
BeforeDate
EqualsDate
NotEqualsDate
OnOrBeforeDate

OnOrBeforeDate

Syntax

OnOrBeforeDate(*srch_field, date*)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use this method to generate a date filter on the specified search field for dates on or before the specified value.

Parameters

srch_field	Specifies the search field name as a string.
date	Specifies the date as a DateTime value.

Returns

None.

Related Links

AfterDate
BeforeDate
EqualsDate
NotEqualsDate
OnOrAfterDate

SearchFilterGenerator

Syntax

`SearchFilterGenerator``()`

Description

Use this constructor to instantiate a SearchFilterGenerator object. Similar to the MatchAll method, the composite filter is initialized with the & filter connector.

Parameters

None.

Returns

None.

Example

Instantiate the SearchFilterGenerator class as follows:

```
Local PT_SEARCH:SearchFilterGenerator &fg = create PT_SEARCH:SearchFilterGenerator(⇒
);
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SetQueryFilter

Syntax

SetQueryFilter(*&srch_qry*)

Description

Use this method to set the composite query filter as the array of filters for the SearchQuery object.

Parameters

&srch_qry	Specifies the query as a SearchQuery object.

Returns

None.

Related Links

AddQueryFilter
SearchQuery Class
Filters

StringDateToDatetime

Syntax

StringDateToDatetime(*str_date*)

Description

Use this method to convert a string value representing a date to DateTime value. The time portion of the value is set to 12:00:00.

Parameters

str_date	Specifies the string value representing a date to be converted.

Returns

A DateTime value.

Related Links

DateToDatetime

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Search Filter Generator Examples

This section provides additional code examples for generating search filters using the SearchFilterGenerator class.

Note: The **&** is the default connector; therefore, for composite filters, MatchAll is implied and does not have to be explicitly specified.

Creating Complex Filters

Example 1 — Using an Explicit Or

The following example generates a composite search filter with Field1 equal to string X or Field2 containing string Y:

```
import PT_SEARCH:SearchFilterGenerator;

Local PT_SEARCH:SearchFilterGenerator &fg = create PT_SEARCH:SearchFilterGenerator(⇒
);
&fg.MatchAny();
&fg.EqualsString("Field1", &str_X);
&fg.ContainsWord("Field2", &str_Y);
&fg.EndMatchAny();
&fg.SetQueryFilter(&qry);
```

See MatchAny for more information.

Example 2 — Using an Implicit And

The following example generates a composite search filter with Field1 equal to string X and Field2 containing string Y:

```
import PT_SEARCH:SearchFilterGenerator;

Local PT_SEARCH:SearchFilterGenerator &fg = create PT_SEARCH:SearchFilterGenerator(⇒
);
/* The & is the default connector; therefore, MatchAll is implied and does not */
/* have to be explicitly specified. */
&fg.EqualsString("Field1", &str_X);
&fg.ContainsWord("Field2", &str_Y);
&fg.SetQueryFilter(&qry);
```

See MatchAll for more information.

Example 3 — Specifying a Complex, Composite Filter

To generate the following composite search filter ((Field1 = string X & Field2 > number N1) & ((Field3 >= number N2 & Field3 <= number N3) | (Field4 = string A | Field4 = string B | Field4 = string C)))

```
import PT_SEARCH:SearchFilterGenerator;

Local PT_SEARCH:SearchFilterGenerator &fg = create PT_SEARCH:SearchFilterGenerator(⇒
);
If &fg.MatchAllReturnTrue() Then
   &fg.EqualsString("Field1", &str_X);
   &fg.GreaterThanNumber("Field2", &N1);
   &fg.EndMatchAll();
End-If;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
If &fg.MatchAnyReturnTrue() Then

   If &fg.MatchAllReturnTrue() Then
      &fg.GreaterThanEqualsNumber("Field3", &N2);
      &fg.LessThanEqualsNumber("Field3", &N3);
      &fg.EndMatchAll();
   End-If;

   If &fg.MatchAnyReturnTrue() Then
      &fg.EqualsString("Field4", &str_A);
      &fg.EqualsString("Field4", &str_B);
      &fg.EqualsString("Field4", &str_C);
      &fg.EndMatchAny();
   End-If;

   &fg.EndMatchAny();
End-If;

&fg.SetQueryFilter(&qry);
```

Example 4 — Specifying a Numeric Filter Between Two Values

The following example generates a composite search filter with BU equal to 001 and price between 10 and 200:

```
import PT_SEARCH:SearchFilterGenerator;

Local PT_SEARCH:SearchFilterGenerator &fg = create PT_SEARCH:SearchFilterGenerator(⇒
);

&fg.EqualsString("BU", "001");
If &fg.MatchAllReturnTrue() Then
   &fg.GreaterThanEqualsNumber("PRICE", 10);
   &fg.LessThanEqualsNumber("PRICE", 200);
   &fg.EndMatchAll();
End-If;
&fg.SetQueryFilter(&qry);
```

See GreaterThanEqualsNumber and LessThanEqualsNumber for more information.

Example 5 — Specifying a String Filter Within a Set of Values

The following example generates a composite search filter with BU equal to 001 and status in (Open, Pending, Approved):

```
import PT_SEARCH:SearchFilterGenerator;

Local PT_SEARCH:SearchFilterGenerator &fg = create PT_SEARCH:SearchFilterGenerator(⇒
);

&fg.EqualsString("BU", "001");
If &fg.MatchAnyReturnTrue() Then
   &fg.EqualsString("STATUS", "Open");
   &fg.EqualsString("STATUS", "Pending");
   &fg.EqualsString("STATUS", "Approved");
   &fg.EndMatchAny();
End-If;

&fg.SetQueryFilter(&qry);
```

See EqualsString for more information.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example 6 — Specifying a String Filter Not in a Set of Values

The following example generates a composite search filter with BU equal to 001 and status not in (Open, Pending, Approved):

```
import PT_SEARCH:SearchFilterGenerator;

Local PT_SEARCH:SearchFilterGenerator &fg = create PT_SEARCH:SearchFilterGenerator(⇒
);

&fg.EqualsString("BU", "001");
If &fg.MatchAllReturnTrue() Then
   &fg.NotEqualsString("STATUS", "Open");
   &fg.NotEqualsString("STATUS", "Pending");
   &fg.NotEqualsString("STATUS", "Approved");
   &fg.EndMatchAll();
End-If;

&fg.SetQueryFilter(&qry);
```

See NotEqualsString for more information.

SearchQuery Class

This section provides an overview of the SearchQuery class and discusses:

- SearchQuery class methods.
- SearchQuery class properties.

The SearchQuery object is used to define the attributes of a search query—such as its category or categories (index or indexes), facet filters, query text, and so on—and then execute that query on a search engine instance. The required properties of a SearchQuery must be initialized before invoking the Execute method. However, which properties are required depend on the specific search engine. Moreover, all properties are not necessarily used for every execution of a search query. For example, if no filters are to be applied to the search then it is not necessary to initialize the Filter property.

A SearchQuery object is returned by the CreateQuery method of the SearchQueryService class.

Related Links

CreateQuery

SearchQuery Class Methods

In this section, the SearchQuery class methods are presented in alphabetical order.

BrowseFacetNodes

Syntax

BrowseFacetNodes()

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use this method to return an array of facet nodes with out actually executing a search. Because this method does not execute the search query, it is lot faster than the Execute method. This method relies on the Language property only and ignores other SearchQuery class properties and settings, such as facet filters.

Note: This is an abstract method.

Parameters

None.

Returns

An array of FacetNode objects.

Related Links

FacetNode Class

Execute

Syntax

```
Execute(start, size)
```

Description

Use this method to execute the search query on the search engine. The Execute method returns search results beginning at the document number specified by *start,* and returns a maximum number of results specified by *size.*

The Execute method uses the following SearchQuery class properties:

- Categories

  Note: If this property is undefined, the query will be executed against *all* search categories.

- Language

  Note: If no value is specified, the query will be executed against *all* languages.

- QueryText

  Note: If no value is specified, then *all* documents in the index are returned.

Note: This is an abstract method.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

start Specifies an integer representing the first document of the returned results. This parameter must be greater than or equal to 1.

If *start* exceeds the total number of documents in the index or the search engine-specified maximum number of results, then zero results are returned.

size Specifies the maximum size of the result set as an integer. This parameter should be greater than or equal to 1.

If *size* is set to 0, then 10 documents are returned.

Returns

A SearchResultCollection object.

Example

```
import PT_SEARCH:SearchFactory;
import PT_SEARCH:SearchQueryService;
import PT_SEARCH:SearchQuery;
import PT_SEARCH:SearchResultCollection;

/* Instantiate the SearchQuery object           */

Local PT_SEARCH:SearchFactory &factory = create PT_SEARCH:SearchFactory();
Local PT_SEARCH:SearchQueryService &svc = &factory.CreateQueryService("default");
Local PT_SEARCH:SearchQuery &srchQuery = &svc.CreateQuery();

/* Initialize the search query                                          */

&srchQuery.QueryText = "some text";
&srchQuery.Language = &lang_cd;
&srchQuery.MarkDuplicates = False;
&srchQuery.RemoveDuplicates = False;

/* Execute the search query                                             */

Local number &start = 1;
Local number &size = 10;
Local PT_SEARCH:SearchResultCollection &results = &srchQuery.Execute(&start, &size)⇒
;

/* Re-execute the search query to return the next 10 results            */

&start = &start + &size;
&results = &srchQuery.Execute(&start, &size);
```

Related Links

Categories

Language

QueryText

SearchResultCollection Class

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

FormatDateFilter

Syntax

FormatDateFilter(*datefilter*)

Description

Use this method to convert dates from the internal PeopleSoft date format into a search engine-specific format. You must use this method when the query string is programmatically created.

Note: This is an abstract method.

Parameters

datefilter Specifies the search filter as a Date value.

Returns

A String value.

Related Links

setDateFilter

FormatDateTimeFilter

Syntax

FormatDateTimeFilter(*datetmfilter*)

Description

Use this method to convert dates from the internal PeopleSoft date/time format into a search engine-specific format. You must use this method when the query string is programmatically created.

Note: This is an abstract method.

Parameters

datetmfilter Specifies the search filter as a DateTime value.

Returns

A String value.

Related Links

setDateTimeFilter

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SearchQuery Class Properties

In this section, the SearchQuery class properties are presented in alphabetical order.

Categories

Description

Use this property to set or return the list of search categories (search indexes) you want to search as an array of SearchCategory objects. If this property is defined, the Execute method will run the query on all the search categories specified in this property.

Important! If this property is undefined, the query will be executed against *all* search categories in the search engine instance.

This property is read-write.

Example

The following example uses two search categories called cat1 and cat2.

```
import PT_SEARCH:SearchCategory;

Local array of PT_SEARCH:SearchCategory &cats;

&cats = CreateArray(create PT_SEARCH:SearchCategory("cat1"));
&cats.Push(create PT_SEARCH:SearchCategory("cat2"));

&searchQuery.Categories = &cats;
```

Related Links

SearchCategory Class

ContainsAnyWords

Description

Use this property to set a search string that contains one or more words. The search results include those documents that contain *any* of these words and whatever is defined by other search text properties (for example, ContainsExactPhrase, QueryText, or WithoutWords).

This property is not required.

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ContainsExactPhrase

Description

Use this property to set a search string that contains one or more words. The search results include those documents that this *exact phrase* and whatever is defined by other search text properties (for example, ContainsAnyWords, QueryText, or WithoutWords).

This property is not required.

This property is read-write.

ClusteringSpecs

Description

This property is reserved for future use.

DocsRequested

Description

Use this property to set or return the size of the result set as an integer. After invoking the Execute method, use this property to return the value of the *size* parameter passed to Execute. Alternatively, if the search query is to be executed by the ExecuteQuery method of the QueryService class, then use this property to specify the size of the result set.

Example

For example, one could compare DocsRequested to the GetDocumentCount method of the ResultCollection class to determine if there are possibly more documents to be retrieved.

The StartIndex and DocsRequested properties (that is, the *start* and *size* parameters to the Execute method) allow for “chunking” of search results. The idea is to repeatedly call Execute while increasing the *start* parameter by the increment specified by *size.* For example, the following psuedo-code will return the first 100 results the first time through the loop. The second time through the loop, it will return documents 101 through 200, and so on.

```
int start=1, size=100


,.// return results in chunks of 100 documents
while not done
   results = query.execute(start, size)
   if (results.GetDocumentCount() < query.DocsRequested)
      done = true
      // we got fewer documents than we asked for so we're done executing this     ⇒
  // query
   if (results.GetDocumentCount() = 0)
      done = true
      // no more documents being returned so we're done executing this query

   // do something with the results

   start = start + size
end-while
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

Execute
StartIndex
GetDocumentCount

EnableExtendedFilterOperators

Description

Use this property to set or return a Boolean value indicating whether to enable the set of extended filter operators (specifically, the notequals operator). In addition, when this property is set to True, all search filters are added to the QuerytText property and sent to the search engine in this manner. Otherwise, when this property is set to False, the search filters are handled by the Filters property as an array of SearchFilter objects. The default value is False.

This property is not required.

This property is read-write.

Related Links

Operator

FacetFilters

Description

Use this property to set or return an array of FacetFilter objects on which the search results are currently filtered.

Note: The SearchCategory class GetFacetFilters method can be used to get the initial list of facet filters.

This property is not required.

This property is read-write.

Related Links

FacetFilter Class
GetFacetFilters

FilterConnector

Description

Use this property to set or return a search filter connector as a string. A search filter connector is used to join search filters. The acceptable values are: AND and OR. The default value is AND.

This property is not required.

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

Filters
SearchFilter Class

Filters

Description

Use this property to set or return the list of search filters as an array of SearchFilter objects.

This property is not required.

This property is read-write.

Related Links

FilterConnector
SearchFilter Class

GroupingSpec

Description

This property is reserved for future use.

IncludeImages

Description

Use this property to set or return a Boolean value indicating whether to return images in the search results.

This property is read-write.

Example

```
Local PT_SEARCH:SearchQuery &qry;

...

If PTSF_QRY_CLIENT.PTSF_SHOW_IMAGE = "Y" Then
   &qry.IncludeImages = True;
End-If;
```

Related Links

GetImageUrl

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Language

Description

Use this property to set or return a three-character string representing the language code to which the search query results should be restricted. This property must be a PeopleSoft language code—for example, ENG for English, FRA for French, and so on.

Note: If no value is specified, the query will be executed against *all* languages.

This property is read-write.

Example

```
&SearchQuery.Language = "ENG";
```

Related Links

"Selecting Database Character Sets" (PeopleTools 8.54: Global Technology)

MarkDuplicates

Description

Use this property to set or return a Boolean value indicating whether duplicates in the result set should be marked as such. A search result can be identified by running the isDuplicate method.

This property is not required. However, it defaults to False if no value is specified.

This property is read-write.

Related Links

RemoveDuplicates
IsDuplicate

MaximumNumberOfFacetValues

Description

Use this property to set or return an Integer value representing the maximum number of child facet nodes. For example, if there are 100 facet values, setting this property to 10 will return the first ten facet values as determined by the sorting order. If this property is not set, the default value is -1, which indicates to return all child nodes.

This property is not required.

This property is read-write.

Related Links

FacetNode Class

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

MinimumDocumentsPerFacetValue

Description

Use this property to set or return an Integer value representing the minimum number of documents required for the child facet node to be returned. Child facet nodes with less than this document count are not returned. If this property is not set, the default value is 1, which indicates that a facet node must have at least one document to be returned.

This property is not required.

This property is read-write.

Related Links

DocumentCount

ProgrammaticSearchString

Description

Use this property to set or return the programmatically generated search string as a string. This search string is not displayed to the end user.

This property is not required.

This property is read-write.

QueryText

Description

Use this property to set or return a string representing the text to use in the search query. The search results include those documents that contain this text and whatever is defined by other search text properties (for example, ContainsAnyWords, ContainsExactPhrase, or WithoutWords).

Note: If no value is specified and none of the other search text properties are defined, then *all* documents in the index are returned.

This property is read-write.

RemoveDuplicates

Description

Use this property to set or return a Boolean value indicating whether duplicates should be removed from the result set.

This property is not required. However, it defaults to False if no value is specified.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

MarkDuplicates

RequestedFields

Description

Use this property to set or return the list of custom attributes to be included for each search result. The list is an array of SearchField objects.

This property is not required.

This property is read-write.

Related Links

GetRequestedFields
SearchField Class

ReturnFacetValueCounts

Description

Use this property to set or return a Boolean value indicating whether to compute and return document counts per facet node.

This property is not required. However, it defaults to True if no value is specified.

This property is read-write.

Related Links

DocumentCount

SearchWithIn

Description

Use this property to set or return a string of search terms as a string. This is used to search within the current results.

This property is not required.

This property is read-write.

SortFacetValuesBy

Description

Use this property to set or return a String value indicating the sort order by which facet nodes are sorted:

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Value	*Description*
ALPHA_ASC	Sort by node name alphabetically ascending.
ALPHA_DES	Sort by node name alphabetically descending.
COUNT_ASC	Sort by document count numerically ascending.
COUNT_DES	Sort by document count numerically descending. COUNT_DES is the default value, which means that facet nodes with highest document count are displayed first in the list.

This property is not required.

This property is read-write.

Related Links

DocumentCount

SortSpecs

Description

This property is reserved for future use.

StartIndex

Description

Use this property to set or return an integer representing the first document of the result set. After invoking the Execute method, use this property to return the value of the *start* parameter passed to Execute. Alternatively, if the search query is to be executed by the ExecuteQuery method of the QueryService class, then use this property to specify the first document of the result set.

Related Links

Execute

DocsRequested

TopN

Description

This is reserved for future use.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

WithoutWords

Description

Use this property to set a search string that contains one or more words. The search results include those documents that *do not include* any of these words and whatever is defined by other search text properties (for example, ContainsAnyWords, ContainsExactPhrase, or QueryText).

This property is not required.

This property is read-write.

SearchQueryCollection Class

This section provides an overview of the SearchQueryCollection class and discusses SearchQueryCollection class methods.

The SearchQueryCollection class provides a collection of SearchQuery objects. Because the SearchQueryCollection class is a generic interface class, a search engine-specific subclass is required.

Related Links

SearchQuery Class

SearchQueryCollection Class Methods

In this section, the SearchQueryCollection class methods are presented in alphabetical order.

addQuery

Syntax

addQuery(*&srch_qry*)

Description

Use this method to add a search query to the search query collection. The addQuery method can be called repeatedly to add multiple search queries to the collection.

Parameters

&srch_qry	Specifies the query as a SearchQuery object.

Returns

None.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

SearchQuery Class

Count

Syntax

Count()

Description

Use this method to return the number of SearchQuery objects in the search query collection as an integer.

Parameters

None.

Returns

An Integer value.

ExecuteQuerys

Syntax

ExecuteQuerys()

Description

Use this method to run multiple search queries in parallel. The ExecuteQuerys method returns an array of SearchResultCollection objects, one for each search query executed. If any of the search queries fails, ExecuteQuerys throws an exception.

Note: The number of parallel requests is determined by the thread pool size that is defined in the application server configuration file (psappsrv.cfg).

Parameters

None.

Returns

An array of SearchResultsCollection objects.

Related Links

SearchResultCollection Class

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

First

Syntax

First()

Description

Use this method to return the first SearchQuery object in the search query collection. If the search query collection is empty, this method returns Null.

Parameters

None.

Returns

A SearchQuery object if successful, Null otherwise.

Related Links

SearchQuery Class

Item

Syntax

Item(*index*)

Description

Use this method to return the SearchQuery object at the position in the search query collection specified by the *index* parameter.

Parameters

&index	Specifies the position of the SearchQuery object in the search query collection as an integer.

Returns

A SearchQuery object if successful, Null otherwise.

Related Links

SearchQuery Class

Next

Syntax

Next()

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use this method to return the next SearchQuery object in the search query collection. This method can only be invoked after a successful invocation of the First, Item, or Next methods.

Parameters

None.

Returns

A SearchQuery object if successful, Null otherwise.

Related Links

First
Item
SearchQuery Class

SearchQueryService Class

This section provides an overview of the SearchQueryService class and discusses: SearchQueryService class methods.

The SearchQueryService provides the ability to instantiate a SearchQuery object along with other interfaces. Because the SearchQueryService class is an interface class, it requires a search engine-specific search query service and search query class to instantiate a search engine-specific SearchQuery object.

A SearchQueryService object is created by the CreateQueryService method of the SearchFactory class.

Related Links

CreateQueryService

SearchQueryService Class Methods

In this section, the SearchQueryService class methods are presented in alphabetical order.

CreateQuery

Syntax

```
CreateQuery()
```

Description

Use this method to instantiate a SearchQuery object.

Note: This is an abstract method.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

None.

Returns

A SearchQuery object.

Related Links

SearchQuery Class

CreateQueryCollection

Syntax

CreateQueryCollection()

Description

Use this method to instantiate a search query collection.

Note: This is an abstract method.

Parameters

None.

Returns

A SearchQueryCollection object.

Related Links

SearchQueryCollection Class

ExecuteQuery

Syntax

ExecuteQuery(*&query*)

Description

Use this method to execute the specified search query on the search provider and return the collection of search results. This method is equivalent to invoking the Execute method of the SearchQuery class.

Note: This is an abstract method.

Parameters

&query	Specifies the search query as a SearchQuery object.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

A SearchResultCollection object.

Related Links

SearchQuery Class
Execute
SearchResultCollection Class

ExecuteQuerys

Syntax

ExecuteQuerys(*&srch_qry_coll*)

Description

Use this method to run multiple search requests in parallel. The number of parallel request is determined by the Thread Pool Size that is defined in the application server configuration file (psappsrv.cfg).

Use this method to run multiple search queries in parallel. The ExecuteQuerys method returns an array of SearchResultCollection objects, one for each search query executed. If any of the search queries fails, ExecuteQuerys throws an exception.

Note: The number of parallel requests is determined by the thread pool size that is defined in the application server configuration file (psappsrv.cfg).

Note: This is an abstract method.

Parameters

&srch_qry_coll Specifies the search queries as a SearchQueryCollection object.

Returns

An array of SearchResultCollection objects.

Related Links

SearchQueryCollection Class
SearchResultCollection Class

SearchResult Class

This section provides an overview of the SearchResult class and discusses: SearchResult class methods

The SearchResult object represents a specific search result (that is, a document) in a SearchResultCollection object. Because the SearchResult class is a generic interface class, a search engine-specific subclass is required. The SearchResult object is defined to comprise 10 standard attributes

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

(or “properties”)—for example, title, URL, summary, and so on. These private, read-only “properties” can be accessed only through the methods of the SearchResult class.

A SearchResult object is instantiated by the First, Item or Next methods of the SearchResultCollection.

Related Links

SearchResultCollection Class

SearchResult Class Methods

In this section, the SearchResult class methods are presented in alphabetical order.

GetCategoryNames

Syntax

GetCategoryNames()

Description

Use this method to return the list of search categories to which this search result belongs as an array of string.

Parameters

None.

Returns

An array of string.

Related Links

SearchCategory Class

GetContentLength

Syntax

GetContentLength()

Description

Use this method to return the content length for this search result as an integer. If the content length cannot be determined, this method returns -1.

The content length, signature, title, and other attributes are used to determine whether a search result is a duplicate.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

None.

Returns

An integer.

Related Links

IsDuplicate

GetCustomAttributes

Syntax

GetCustomAttributes()

Description

Use this method to return a SearchFieldCollection representing the custom attributes for this search result. A SearchFieldCollection is a collection of SearchField objects.

Parameters

None.

Returns

A SearchFieldCollection object.

Related Links

SearchFieldCollection Class
SearchField Class

GetImageUrl

Syntax

GetImageUrl()

Description

Use the GetImageUrlmethod to return the image URL for this search result.

Parameters

None.

Returns

A String value.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

```
Local PT_SEARCH:SearchResult &cur;

...

If PTSF_QRY_CLIENT.PTSF_SHOW_IMAGE = "Y" Then
   &rs(&i).PTSF_SRCHRESULT.PTSF_DISPIMAGEURL.Visible = True;
   &rs(&i).PTSF_SRCHRESULT.HTMLAREA.Visible = True;
   &imageUrl = &cur.GetImageUrl();
   &imageUrlHtml = GetHTMLText(HTML.HTML_IMAGE, &imageUrl);
   &rs(&i).PTSF_SRCHRESULT.PTSF_DISPIMAGEURL.Value = &imageUrl;
   &rs(&i).PTSF_SRCHRESULT.HTMLAREA.Value = &imageUrlHtml;
Else
   &rs(&i).PTSF_SRCHRESULT.PTSF_DISPIMAGEURL.Visible = False;
   &rs(&i).PTSF_SRCHRESULT.HTMLAREA.Visible = False;
End-If;
```

Related Links

IncludeImages

GetLanguage

Syntax

GetLanguage()

Description

Use this method to return a string representing the three-character PeopleSoft language code for this search result.

Parameters

None.

Returns

A string.

Related Links

Language

GetLastModified

Syntax

GetLastModified()

Description

Use this method to return the last modified date and time for this search result.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

None.

Returns

A DateTime value.

GetScore

Syntax

GetScore()

Description

Use this method to return the search engine-specific score for this search result as an integer.

Parameters

None.

Returns

An integer.

GetSignature

Syntax

GetSignature()

Description

Use this method to return the search engine-computed signature for this search result as an integer. If the signature cannot be determined, this method returns -1.

The signature, content length, title, and other attributes are used to determine whether a search result is a duplicate.

Parameters

None.

Returns

An integer.

Related Links

IsDuplicate

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GetSummary

Syntax

GetSummary()

Description

Use this method to return the summary for this search result as a string.

Parameters

None.

Returns

A string.

GetTitle

Syntax

GetTitle()

Description

Use this method to return the title for this search result as a string.

Parameters

None.

Returns

A string.

GetUrlLink

Syntax

GetUrlLink()

Description

Use this method to return the URL for this search result as a string.

Parameters

None.

Returns

A string.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

HasDuplicate

Syntax

HasDuplicate()

Description

Use this method to return a Boolean value indicating whether this search result has duplicates.

Parameters

None.

Returns

A Boolean value: True if the search result has duplicates, False otherwise.

Related Links

IsDuplicate
MarkDuplicates

IsDuplicate

Syntax

IsDuplicate()

Description

Use this method to return a Boolean value indicating whether this search result is a duplicate. *Exact duplicates* and *near duplicates* are both marked as duplicates by the PeopleSoft Search Framework.

An exact duplicate is a document that satisfies *all* of the following conditions exactly:

- Same signature
- Same content length
- Same title

A near duplicate (a similar document) is a document that satisfies *any* of the following conditions:

- Same signature and documents are not empty.
- Same (non-null) title and same 4K checksum.
- Same (non-null) title and URLs differ by not more than one element (an element is a folder name and doesn't include the HTML/JSP page name of the HTTP GET parameters).

Parameters

None.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

A Boolean value: True if this search result is a duplicate, False otherwise.

Related Links

GetContentLength
GetSignature
GetTitle
GetUrlLink
HasDuplicate
MarkDuplicates

SearchResultCollection Class

This section provides an overview of the SearchResultCollection class and discusses: SearchResultCollection class methods.

The SearchResultCollection class provides a collection of SearchResult objects. Because the SearchResultCollection class is a generic interface class, a search engine-specific subclass is required. A SearchResultCollection object is returned by the Execute method of the SearchQuery class.

Related Links

Execute

SearchResultCollection Class Methods

In this section, the SearchResultCollection class methods are presented in alphabetical order.

First

Syntax

```
First()
```

Description

Use this method to return the first SearchResult object in the SearchResult collection. If the SearchResult collection is empty, it returns Null.

Parameters

None.

Returns

A SearchResult object if successful, Null otherwise.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

SearchResult Class

GetDocumentCount

Syntax

GetDocumentCount()

Description

Use this method to return the actual number of SearchResult objects (documents) in the SearchResult collection.

Note: This is an abstract method.

Parameters

None.

Returns

An integer.

Related Links

DocsRequested

GetDuplicatesMarked

Syntax

GetDuplicatesMarked()

Description

Use this method to return a Boolean value indicating whether duplicate items in the collection are marked as duplicates—that is, whether the search query was executed with MarkDuplicates set to true.

Note: This is an abstract method.

Parameters

None.

Returns

A Boolean value: True if duplicates were marked, False otherwise.

Related Links

MarkDuplicates

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

IsDuplicate

GetDuplicatesRemoved

Syntax

GetDuplicatesRemoved()

Description

Use this method to return a Boolean value indicating whether duplicate items in the collection were removed—that is, whether the search query was executed with RemoveDuplicates set to true.

Note: This is an abstract method.

Parameters

None.

Returns

A Boolean value: True if duplicates were removed, False otherwise.

Related Links

RemoveDuplicates
IsDuplicate

GetEstimatedHitCount

Syntax

GetEstimatedHitCount()

Description

Use this method to return the estimated hit count for the search query as an integer. The estimated hit count can be used as a device for fetching search results on demand rather than retrieving all of the search results initially.

Note: This is an abstract method.

Parameters

None.

Returns

An integer.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GetFacetNodes

Syntax

GetFacetNodes()

Description

Use this method to return an array of facet nodes available for this search result collection.

Parameters

None.

Returns

An array of FacetNode objects if successful, Null otherwise.

Related Links

FacetNode Class

GetQueryObject

Syntax

GetQueryObject()

Description

Use this method to return the SearchQuery object that was used for the search.

Parameters

None.

Returns

A SearchQuery object.

Related Links

SearchQuery Class

GetQueryText

Syntax

GetQueryText()

Description

Use this method to return the search text that was used for the search query as a string.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Note: This is an abstract method.

Parameters

None.

Returns

A string.

Related Links

QueryText

GetStartIndex

Syntax

GetStartIndex()

Description

Use this method to return the value of the *&start* parameter that was used to execute this search query.

Note: This is an abstract method.

Parameters

None.

Returns

An integer.

Related Links

Execute
StartIndex

Item

Syntax

Item(*index*)

Description

Use this method to return the SearchResult object at the position in the SearchResult collection specified by the *index* parameter.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

index	Specifies the position of the SearchResult object in the SearchResult collection as an integer.

Returns

A SearchResult object if successful, Null otherwise.

Related Links

SearchResult Class

Next

Syntax

```
Next()
```

Description

Use this method to return the next SearchResult object in the SearchResult collection. This method can only be invoked after a successful invocation of the First, Item, or Next methods.

Parameters

None.

Returns

A SearchResult object if successful, Null otherwise.

Related Links

First
Item
SearchResult Class

SearchAuthnQueryFilter Class

This section provides an overview of the SearchAuthnQueryFilter class and discusses: SearchAuthnQueryFilter class methods.

The SearchAuthnQueryFilter class provides an abstract method to evaluate a list of values for a security attribute for a given search user. An application that requires document-level security in a searchable object must implement and extend the evaluateAttrValues abstract method.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SearchAuthnQueryFilter Class Methods

In this section, the SearchAuthnQueryFilter class methods are presented in alphabetical order.

evaluateAttrValues

Syntax

evaluateAttrValues(*SBO_name*, *attr*, *user_ID*)

Description

Use this method to return a list of values for a security attribute for a search user.

Note: This is an abstract method.

Parameters

SBO_name	Specifies a string representing a searchable object upon which the security attribute value needs to be evaluated
attr	Specifies a string representing the security attribute value as a document-level filtering attribute.
user_ID	Specifies user ID that executed the search query as a string.

Returns

An array of string.

Example

```
import PTSF_SECURITY:*;

class UserPermission implements PTSF_SECURITY:SearchAuthnQueryFilter
   method UserPermissionList();
   method evaluateAttrValues(&sboName As string, &secAttr As string, &searchUser As⇒
 string) Returns array of string;
end-class;

method UserPermissionList
end-method;

method evaluateAttrValues
   /+ &sboName as String, +/
   /+ &secAttr as String, +/
   /+ &searchUser as String +/
   /+ Returns Array of String +/
   /+ Extends/implements PTSF_SECURITY:SearchAuthnQueryFilter.evaluateAttrValues +/

   Local SQL &userPermissions_SQL;
   Local array of string &retvalues;
   Local string &isAdmin;
   &retvalues = CreateArrayRept("", 0);

   SQLExec("SELECT 'X' FROM PSROLEUSER WHERE ROLEUSER=:1 AND (ROLENAME=:2 OR ROLENA⇒
ME=:3)", &searchUser, "Portal Administrator", "PeopleSoft Administrator", &isAdmin)⇒
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
;

   If All(&isAdmin) Then
      &retvalues = CreateArray("R:Admin");
   Else
      &retvalues.Push("0"); /* Public */
      &retvalues.Push("1:" | &searchUser); /* Author */
      &userPermissions_SQL = CreateSQL("SELECT DISTINCT A.CLASSID FROM PSROLECLASS ⇒
A, PSROLEUSER B, PSOPRDEFN C WHERE A.ROLENAME = B.ROLENAME AND C.OPRID = B.ROLEUSER⇒
 AND C.OPRID = :1", &searchUser);
      Local string &classids;
      While &userPermissions_SQL.Fetch(&classids)
         &retvalues.Push(&classids);
      End-While;
   End-If;
   Return &retvalues;

end-method;
```

Additional Search Examples

This section provides additional code examples for the PeopleSoft Search Framework: Searching using facets.

Searching Using Facets

The following provides an example of searching using facets.

```
import PT_SEARCH:*;

/* The following 3 lines are same for any implementation */
Local PT_SEARCH:SearchFactory &factory = create PT_SEARCH:SearchFactory();
Local PT_SEARCH:SearchQueryService &svc = &factory.CreateQueryService("default");
Local PT_SEARCH:SearchQuery &qry = &svc.CreateQuery();

/* This is the keywords user is searching for; */
&qry.QueryText = "a";

/*
&qry.StartIndex , For the first request this is always 1
When using pagination to get the next set of results this can be changed to DocsReq⇒
uested + StartIndex ex: here 51 on next request is 101..
The maximum number of results that can come back is 200 which is configurable at SE⇒
S the max results for this query can be fetched from SearchResultCollection hit cou⇒
nt
*/
&qry.StartIndex = 1;

/*
&qry.DocsRequested , Number of results to be returned by the search , It is recomme⇒
nded to keep this default to 50 for performance reasons and show 10 results per pag⇒
e and if the end user is requesting for 6th page request with start index to 51;
*/
&qry.DocsRequested = 50;

/*
&qry.RemoveDuplicates ,&qry.MarkDuplicates Currently these two should always be set⇒
 to false as our we generate unique id for every search document.
&qry.RemoveDuplicates = False;
*/
&qry.MarkDuplicates = False;


/*
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
This should be set to empty value to search in documents from all languages .
&qry.Language This can be provided a value to search in language specific documents
Currently the frame work does not allow searching in selected languages , its eithe⇒
r all or one language
*/
&qry.Language = %Language_User;


/*
&qry.Categories , Array of categories on which the search can be performed on
If not specified we will search in all categories
*/
Local PT_SEARCH:SearchCategory &srchCat = create PT_SEARCH:SearchCategory("MY_SRCH_⇒
CAT");
&qry.Categories = CreateArray(&srchCat);

/*
&qry.RequestedFields , Array of custom attribute values in the search result
Optional , if not specified all the standard information like URL , body , title ar⇒
e still returned
*/
&qry.RequestedFields = &srchCat.GetRequestedFields();

/*
&qry.FacetFilters , Array of facets filter the search result by
Optional , If not specified No facets will be returned
Limitation : Only documents having this facet and path (If included) will be return⇒
ed in the search result.
FacetFilter constructor will take two arguments 1.Facet name , 2.Facet Path
FacetFilter is required when dealing with hierarchy facets Ex: Attribute LOCATION h⇒
as COUNTRY/STATE/CITY
To filter results for country USA the request will be FacetName: LOCATION , Facet F⇒
ilter: USA
To filter results for country USA and State CA the request will be FacetName: LOCAT⇒
ION , FacetFilter: USA/CA

&qry.FacetFilters = CreateArray(create PT_SEARCH:FacetFilter("SETID", ""));
&qry.FacetFilters.Push(create PT_SEARCH:FacetFilter("STATE", ""));
*/

&qry.FacetFilters = &srchCat.GetFacetFilters();

/*
The other optional facet request related query parameters that can be set when  sea⇒
rching for facets
 ReturnFacetValueCounts -- returns the counts only if this is set to true ,  defaul⇒
t is true , set this to false if we do not want to display counts.
 MinmumDocumentsPerFacetValue -- only return facet value whose document hit count  ⇒
is more that this , ex: only facets values which have hit count more than 5 or 1;
 MaximumNumberOfFacetValues -- the children facets can be huge list , this can  lim⇒
it the return list
 SortFacetValuesBy -- ALPHA_DES , ALPHA_ASC , COUNT_DES , COUNT_ASC
 the max fetch returns the only top few children this can be used to provide  which⇒
  top children to return
*/

/*
Execute the query and get back the results
*/
Local PT_SEARCH:SearchResultCollection &res = &qry.Execute(&qry.StartIndex, &qry.Do⇒
csRequested);

/*
Find the number of results returned by the search , this will always be less than o⇒
r equal to "&qry.DocsRequested"
*/
Local integer &resultSize = &res.GetDocumentCount();
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
/*
Find the number of potential results that can be returned;
This can be used to determine if we get the next set of results and how many pages ⇒
that can be shown to the user
*/
Local integer &estmatedResultCount = &res.GetEstimatedHitCount();

Local string &outHtml;

/*
FacetNode will have the facet values and the hit count for the results
GetFacetNodes will return array of the facet nodes in the result
*/
Local array of PT_SEARCH:FacetNode &facetNodes = &res.GetFacetNodes();

/*
Facet Node has various information which can be retrieved.
&facetNodes [&i].DocumentCount will return hit count
&facetNodes [&j].FacetValue , is the facet value before translation
&facetNodes [&i].DisplayValue , translated facet value (currently this is not yet s⇒
upported by SES)
&facetNodes [&i].Path , to which the facet value belongs to
&facetNodes [&i].getChildNodes() will return child facet nodes and will have all ab⇒
ove properties
*/

/*
loop through facet nodes and there children and render it in the UI
*/
If &facetNodes <> Null And
      &facetNodes.Len <> 0 Then
   &outHtml = &outHtml | "<table border='1'><tr><th>Name</th><th>Value</th><th>Disp⇒
layValue</th><th>DocCount</th><th>Path</th><th></th></tr>";
   For &i = 1 To &facetNodes.Len
      &outHtml = &outHtml | "<tr><td>" | &facetNodes [&i].FacetName | "</td><td>" |⇒
 &facetNodes [&i].FacetValue | "</td><td>";
      &outHtml = &outHtml | &facetNodes [&i].DisplayValue | "</td><td>";
      &outHtml = &outHtml | &facetNodes [&i].DocumentCount | "</td><td>" | &facetNo⇒
des [&i].Path | "</td></tr>";
      If &facetNodes [&i].HasChildren Then
         &outHtml = &outHtml | "<tr><th>Child</th><th>Name</th><th>Value</th><th>Di⇒
splayValue</th><th>DocCount</th><th>Path</th></tr>";
         Local array of PT_SEARCH:FacetNode &childFacetNodes = &facetNodes [&i].get⇒
ChildNodes();
         For &j = 1 To &childFacetNodes.Len
            &outHtml = &outHtml | "<tr><td></td><td>" | &childFacetNodes [&j].Facet⇒
Name | "</td><td>" | &childFacetNodes [&j].FacetValue;
            &outHtml = &outHtml | "</td><td>" | &childFacetNodes [&j].DisplayValue;
            &outHtml = &outHtml | "</td><td>" | &childFacetNodes [&j].DocumentCount⇒
 | "</td><td>" | &childFacetNodes [&j].Path | "</td></tr>";
         End-For;
      End-If;
   End-For;
   &outHtml = &outHtml | "</table>";
Else
   &outHtml = &outHtml | "<br><bold>No Facet Nodes</bold>";
End-If;


/*
&res.Item(&i) returns a PT_SEARCH:SearchResult for each search result document whic⇒
h has various information which can be retrieved for display purposes
&srchResult.GetUrlLink , returns the URL which can take the user to the transaction⇒
 page
&srchResult.GetTitle , returns the Title for the search result document
&srchResult.GetSummary , returns the body for the search result document
&srchResult.GetScore , returns the score for the search result document
&srchResult.GetCategoryNames , returns the search categories this search result doc⇒
ument belongs too
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
&srchResult.GetCustomAttributes , will return a SearchFieldCollection which has cus⇒
tom search attribute values
*/

/*
loop through each result and render it in the UI
*/
Local PT_SEARCH:SearchResult &srchResult;
For &i = 1 To &resultSize
   &srchResult = &res.Item(&i);
   &outHtml = &outHtml | "<font size=""2""><hr/>Title: <a href="" " | &srchResult.G⇒
etUrlLink() | """>" | &srchResult.GetTitle() | "</a>";
   rem &outHtml= &outHtml| "";
   &outHtml = &outHtml | "<br>Summary: " | &srchResult.GetSummary();
   &outHtml = &outHtml | "<br>Score: " | &srchResult.GetScore();
   &outHtml = &outHtml | " Source Group: ";
   If Not &srchResult.GetCategoryNames() = Null Then
      For &j = 1 To &srchResult.GetCategoryNames().Len
         &outHtml = &outHtml | " " | &srchResult.GetCategoryNames()[&j];
      End-For;
   End-If;
   &outHtml = &outHtml | "<font size=""2"" color=#009933><br>Url: " | &srchResult.G⇒
etUrlLink() | "</font>";
   &outHtml = &outHtml | "<font size=""2"" color=#097054><br>Signature: " | &srchRe⇒
sult.GetSignature() | "</font>";
   &outHtml = &outHtml | "<font size=""2"" color=#097054> / Content Length: " | &sr⇒
chResult.GetContentLength() | "</font>";
   &outHtml = &outHtml | "<font size=""2"" color=#097054> / Language: " | &srchResu⇒
lt.GetLanguage() | "</font>";
   &outHtml = &outHtml | "<font size=""2"" color=#000000><br>Last Modified: " | &sr⇒
chResult.GetLastModified() | "</font>";
   Local PT_SEARCH:SearchFieldCollection &customs = &srchResult.GetCustomAttributes⇒
();
   If (&customs <> Null) Then
      For &j = 1 To &customs.Count()
         &outHtml = &outHtml | "<br>" | &customs.Item(&j).Name | "=" | &customs.Ite⇒
m(&j).Value;
      End-For;
   End-If;
   &outHtml = &outHtml | "</font>";
End-For;
&outHtml = &outHtml | "</BODY></HTML>";
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Chapter 34

Portal Registry Classes

Understanding the Portal Registry

The portal registry is a tree structure in which content for a portal is organized, classified, and registered. The portal registry classes (API) are used to update the portal registry. The Portal Administration pages provide a GUI access to the portal registry API. You can also access them using a PeopleCode program you write yourself. How you access the portal registry depends on the type of updates required. Your organization will likely use both methods of updating the portal registry. This topic focuses on accessing the portal registry classes using PeopleCode.

A portal is a website that helps you navigate to other web-based applications and content. The PeopleSoft Portal is a *business portal*. It is similar to general purpose portals, except that its main purpose is to help end-users be more effective in accessing information to perform their jobs.

Each PeopleSoft Portal is defined by one PeopleSoft portal registry. The PeopleSoft portal registry consists of a number of system tables and associated data in a PeopleSoft database. The portal registry must reside within one PeopleSoft database. There can be more than one portal registry in a PeopleSoft database, but only one portal registry is associated with a PeopleSoft Portal.

The portal registry consists of the following primary parts:

- Folders
- Content references
- Nodes

Folders and content references make up the majority of the portal registry, and provide a hierarchical tree structure to describe various content that is *registered* as part of a PeopleSoft portal.

Nodes provide a logical name to a specific webserver and database, so content can be registered independent of specific webservers. It is used when the portal servlet attempts to retrieve content—both internal PeopleSoft content as well as external content—and to assemble pages.

The primary function of the portal is to take a target URL (generally a URL for a PeopleSoft component) that comes in from a user's browser, and assemble a page with that content and any other content. The layout and what content to assemble on the page is defined by the *node template*, which is composed of HTML. The portal attempts to find the content reference associated (that is, registered) with the target URL to get the template, or uses a series of default templates if it cannot get the template from a content reference.

Folders

Folders are how a hierarchical structure is created within a portal registry. Each folder has a parent, except the root folder, which is the top-level folder in a portal registry. Each folder can also contain child folders and content references. Folders are roughly analogous to directories within a file system. A folder can be

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

further defined by a number of attributes (description, security, when it expires, and so on) that are useful within the portal environment.

Related Links

Adding a Folder

Content References

A content reference is simply a reference to a URL. After you create an entry for a content reference in the portal registry, it's considered registered. A content reference can be further defined by a number of attributes (description, security, when it expires, and so on) that are useful within the portal environment.

There are a number of distinct types of content references that can be broken down into the following broad categories:

- Target
- Template
- Component

A *target* type of content reference describes a registered URL that a user might reference. Typically, these would be a PeopleSoft Pure Internet Architecture component, such as a page in a transaction. When a user references a URL, the URL is looked up in the registry to find the target content reference.

A *template* type of content reference describes what, if any, other content to put on the page, and where to place that content. The portal attempts to find a template for every URL that is requested.

A *component* type of content reference describes a component that is typically placed on a target page or homepage.

Related Links

ContentReference Links

Nodes

When a content reference is created to register some content (that is, a URL) the specific URI (that is, the scheme, webserver, and so on) can be specified in the content reference. However, this has the drawback that every time the URI for a content reference changes (the webserver name changes, and so on), the content reference must be changed. Nodes are a way to create a logical name for a specific webserver, scheme, and so on. When the content reference is created you can specify a node name.

For example, suppose the name of a webserver changed. If you don't use nodes, you must check all your content references and change them accordingly. If you use nodes, you have to change only the webserver name in one place, and all the content references that use that node now automatically reference the correct webserver.

Nodes can be optional for content where the specified URL is already a complete URL, such as for external content. Nodes can be categorized as:

- default local

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- local
- non-local (remote)

Related Links

Using Attributes

Security

The same security mechanism is used for folders, content references, content reference links, tab definitions, pagelets, and user homepages. All of these items can be marked as public, owner accessible, or can have explicit PeopleSoft permission values set, including cascading the permissions to its child objects (that is, the child objects have the same permissions as the parent objects, when applicable.)

When marked as public, the item is accessible by any user. Public access cannot be cascaded, that is, passed down, to child objects.

When marked as owner accessible, an item is accessible only by the same user that created that item. Owner accessible cannot be cascaded, that is, passed down, to child objects.

Items can be marked as accessible by PeopleSoft permissions. This means that if a user is a member of a role, and the role contains the permission list that the item is also associated with, the user has access to that item. Additionally, when applied to folder permissions the permission can be cascaded. This means that any child of that folder, including a content reference, automatically has that permission added to its permission list.

Role-based security can applied to the portal objects (folders, content references and content reference links) using the RolePermissions collection.

Note: You can only use role-based security for content references, folders, and content reference links that are not components or iScripts.

You can specify which roles are allowed to access the objects. This works similarly to permission lists. If a user has a specified role, authorization is granted.

A role collection is the same as the PermissionValue collection, though there are additional properties on PermissionValue.

Attributes

Folders, content references, content reference links, PageletCategory objects, and Pagelets can have any number of attributes added to them. Attributes are simply name/value pairs. These name/value pairs are defined and used by many portal-aware applications, such as the search engine, navigational display, and so on.

See Using Attributes.

Additional Portal Objects

Using the PortalRegistry, you can also add and customize other items in your portal, such as tabs, homepages, and favorites.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The TabDefinition is a homepage tab that has been defined to the portal. It is what an administrator creates when they want to define a new homepage tab. The TabDefinition is based on content references.

The User Homepage is a personalized homepage for a user. It contains all the tabs and pagelets the user has selected for their homepage. The User Homepage is based on folders.

A Favorite represents a content reference that the user wants to keep a shortcut to. It contains the name of the content reference, and the label the user wants displayed for this favorite.

A Pagelets is an area on a page that contains content, and the template used to specify the style for that content. Pagelets are a type of content reference.

Using the Portal Registry API

The portal registry API provides the entry point to a specific portal registry. Common administrative tasks include adding, deleting, and renaming the registry objects (that is, folders, content references, tabs, and so on.) Additionally, there are many properties associated with every registry object, and all of these properties can be accessed and modified.

You can use the portal registry API in batch mode to make many changes to a portal at once. For example, suppose something changed in your security system. You could write your own PeopleCode program, using the portal registry classes, in an Application Engine program and change the access for all your users at once.

You can also use the portal registry API to exchange data with an external system. For example, suppose an external merchant had an area on your company's portal, and the information there must be updated. One way to do this is for the merchant to use an Application Message to send the data to your system, then a subscription program would update the portal using the portal registry API.

Each PortalRegistry object represents one specific PortalRegistry in a system. An empty PortalRegistry object is initially gotten from the PeopleSoft Session object. You can then open an existing PortalRegistry to view or change existing content, create a new PortalRegistry, or delete an existing PortalRegistry.

Using Security

The PermissionValue object associated with a folder, content reference, and so on, as well as specific properties on the object, work together to form the security for an object. In this section, we discuss how to:

- Use object properties.
- Access objects.

Using Object Properties

The properties that set permissions for an object are:

- AuthorAccess

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- PublicAccess

The AuthorAccess property determines whether the author of the object has access to the object.

The PublicAccess property determines whether the object is generally accessible or not. If this property is set to True, all users have access to the object.

These properties apply only to an object. They *cannot* be cascaded, that is, passed down to child objects.

The other object property used with security, the Authorized property, indicates whether a user is authorized to access an object. The value of this property depends on whether the user has access.

Accessing Objects

When you get a folder, content reference, content reference link, PageletCategory or Pagelet collection, only the items that the end-user is authorized to access are in the collection.

An object is contained in a collection is based on the following algorithm.

- If the object is marked as PublicAccess it is automatically accessible.
- If the object is marked as AuthorAccess and the current UserId is the Author it is accessible.
- If the current user is in a permission list (class) that is in the Permissions collection for that object.
- If the current user is in a permission list (class) that is in the CascadedPermissions collection for that object.
- If the current user has the Portal Administrator role.

When you access a content reference or folder using a valid name and one of the Find methods (FindCRefByURL, FindCRefByName, FindCRefForURL, or FindFolderByName) a content reference or folder is returned whether the user is authorized to it. When you use these methods, always check the Authorized property. This is the only property you can view from an object that an end-user isn't authorized to.

In addition, if you know the specific URL for a tab, you could specify that in the FindCRefByURL. The tab is returned whether the user is authorized to it, so you should always check the Authorized property.

Using PermissionValue, RolePermissionValue, Cascading Permissions and CascadingRolePermissions

To set non role-based permissions for a folder, content reference, content reference link, PageletCategory object, or Pagelet, you must access the PermissionValue collection for that object using the Permissions property. The PermissionValue objects refer to permission list values that already exist on the system, such as ALLPANLS, CUSTOMER, EMPLOYEE, and so on.

To set role-based permissions for a folder, content reference, or a content reference link that are not component or iScript, you must access the RolePermissionValue collection for that object using the RolePermissions property. The PermissionValue objects refer to role-based permission values that already exist on the system.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Note: The PORTAL_PAGELETS folder is the parent folder for all PageletCategories. Its security is set to public. PeopleSoft does not recommend cascading any permissions from this folder object. Cascade permissions only from the pagelet category (folder).

Both the PermissionValue collection and the RolePermissionValue collection return PermissionValue objects. Use the PermType property to determin if a particular PermissionValue is role-based or not.

For every PermissionValue object, you can chose whether all the child folders and content references of this folder have the same permissions. This is called *cascading*. You cascade permissions by setting the Cascade property to True.

There are two types of PermissionList collections you can access. One is returned by the Permissions and RolePermissions properties, the other by the CascadedPermissions and CascadedRolePermissions properties.

Permissions and RolePermissions

The Permissions and RolePermissions properties return a collection containing the permissions set at the current level, that is, set with that folder or content reference. You can add PermissionValues to this list. Use the Cascade property to cascade the permission you add to child folders and content references.

Note: Folders can contain other folders, but the other objects that use the Permissions property can't contain themselves, that is, content references can't contain other content references, and so on. Therefore, the Cascade property is applicable only to folders, not to any other object.

CascadedPermissions and CascadedRolePermissions

The CascadedPermissions and CascadedRolePermissions properties return the a collection for *all* the permissions for an object. It contains any permission list values set in any parent folder.

Note: You *cannot* add any PermissionValues to a collection returned by the CascadedPermissions or CascadedRolePermissions property. You can add values only to the collection returned by the Permissions or RolePermissions property.

You can add PermissionValues for a child folder, but you *cannot* delete any of the existing ones that are cascaded. Permissions are augmented, not overwritten, that is, the permissions are the sum of both the parent permissions and whatever is set at the current level.

Therefore, keep the following in mind when working with PermissionValues:

- Set permissions only at the level where they're needed.
- Cascade permissions only when necessary.
- Generally, don't set cascaded PermissionValues for the root folder.
- Only the values in a PermissionValue object cascade. Properties on the folder itself (such as PublicAccess or AuthorAccess) do *not* cascade.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

For example, suppose your PortalRegistry had the following hierarchy:

Image: PortalRegistry hierarchy example

The following diagram illustrates PortalRegistry hierarchy example:

The following permission list values are assigned to the PermissionValue objects for the Employees folder, and both of them are cascaded:

- EMPLOYEE
- MANAGER

The Homepages and Benefits folders have the exact same permissions as the Employees folder, that is, all users associated with these two permission lists have access to these folders.

Suppose you decide that you don't want the permission list EMPLOYEE to access the Benefits folder. If you delete the EMPLOYEE PermissionValue from the Benefits PermissionValue collection, you have *not* altered the permissions. The permissions set at the parent folder, that is, at the Employees folder, can't be deleted, they can only be added to.

To make this change, you must:

- Change the Cascaded property for the EMPLOYEES PermissionValue in the Employees folder to False
- Add EMPLOYEES as a PermissionValue object to the Homepages folder.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

Cascade

Setting Permissions Using the PermissionValue Object

"Understanding Permission Lists" (PeopleTools 8.54: Security Administration)

Working With ValidFrom and ValidTo

Folders, content references, content reference links, and tab definitions have both ValidFrom and ValidTo dates. What's the difference and how are they used in the portal registry API?

- A ValidFrom date is when something begins.
- A ValidTo date is when something ends.

For example, suppose your HR department has a page describing the benefits for your employees, and that page changed every calendar year. This means the page for the year 2000 has a ValidFrom date of 01/01/2000 and a ValidTo date of 12/31/2000. The benefits page for the year 2001 has a ValidFrom date of 01/01/2001 and a ValidTo date of 12/31/2001.

Folders, content references, content reference links and tab definitions are returned in their collections regardless of the ValidTo and ValidFrom dates. You must take these dates into account and only display to the end-user those values that should be seen.

In addition, a ValidFrom should always come *before* a ValidTo date. If they are set incorrectly, you receive a runtime error.

For all newly created folders, content references, content reference links and tab definitions, the default value for both these properties is Null ("""), that is, they begin immediately and do not expire.

In addition, you can also check the IsVisible property to see if a portal object is viewable. IsVisible verifies if an object is Hidden, as well as if the ValidTo and ValidFrom dates are within the specified dates.

Doing Error Handling

All errors for the portal registry classes, like the other APIs, are logged in the PSMessages collection, instantiated from a session object.

The portal registry classes log errors that occur with methods immediately, and errors that occur with properties only after a method is executed.

For example, suppose you specified an invalid name when you were trying to delete a folder. The method (DeleteItem) returns False, and the error is logged in the PSMessages collection immediately.

Now suppose you created a new folder, and specified an invalid ValidTo date. The error won't be logged in the PSMessages collection until you tried to save your changes.

When you want to check for errors depends on your application. When users are entering data dynamically, and your program is registering their data in the portal, you may want to check for errors

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

often. If you're using a batch program, you may want to check for errors only after the Open, Save, Insert, and Delete methods.

Most methods return a Boolean value indicating success or failure. After the failure of a method, you may want to check the PSMessages collection to determine the exact error.

```
Local ApiObject &MySession;
Local ApiObject &ErrorCol;
Local ApiObject &FolderCol, &Folder, &Registry;
Local Boolean &Open;/* Access the current session */

&MySession = %Session;
If &MySession Then
   /* connection is good */

&Registry = &MySession.GetRegistry();

&Open = &Registry.Open("CUSTOMER");

If &Open Then
   /* Registry opened successfully */
   /* do processing */
Else
   /* Do error checking */

&ErrorCol = &MySession.PSMessages;
For &I = 1 to &ErrorCol.Count
   /* do processing */
End-For;

   End-If;
Else
   /* do processing for no connection */
End-If;
```

Related Links

Error Handling

Understanding the Life Cycle of a PortalRegistry Object

At runtime, there are certain things you want to do with a PortalRegistry object, like getting an instance of it, adding tabs, editing content references, and so on. The following is an overview of this process. These steps are expanded in other sections.

1. Perform one of these steps.
   a. Execute the GetPortalRegistry method on the PeopleSoft session object to get a PortalRegistry object, or
   b. Use the FindPortalRegistries method on a session object to get a collection of all PortalRegistries. Select a PortalRegistry from the collection.
2. Open the PortalRegistry, using the portal name.
3. After you have an open PortalRegistry object, you can do various actions such as:
   - Add content references to the existing folders.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- Add folders and the content references for them.
- Add or change Nodes.
- Modify the PortalRegistry properties.
- Modify the existing content references, folders, tabs, homepages, and so on.

4. After you make your changes, you must save your work. The Save method must be executed at the appropriate level, such as at the folder level for changes to a folder, at the PortalRegistry level for changes to the default template, and so on.

   A property value change isn't committed to the database until the parent object is saved.

   Some methods commit data to the database only when the parent object is saved. However, other methods cause data to be committed to the database as soon as they are executed, like DeleteItem on a folder. Methods that automatically make database changes are noted as such in their description.

   See Saving Content Considerations.

5. When you finish all operations for a PortalRegistry, close the object.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Note: PeopleSoft recommends that you open and close every PortalRegistry in a single PeopleCode event. You shouldn't open a PortalRegistry object and keep it open across multiple events. You should also keep only one PortalRegistry object open at a time.

Image: Life cycle of a PortalRegistry object

The following diagram provides an understanding of the Life Cycle of a PortalRegistry Object.

Examples of using the PortalRegistry objects are provided at the end of this topic.

Related Links

Portal Registry Classes Example

Viewing the PortalRegistry Class Hierarchy

There are many different classes used with the portal registry API. The following flowchart shows the different classes, and how they are interrelated.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Hierarchy Considerations

The following are considerations for the representation of the hierarchy:

- The flowchart shows only two levels of folders. In reality, you can embed as many levels of folders as you need.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- From a PortalRegistry object, you must access the root folder before you can access the sub-folders for that PortalRegistry.

Image: PortalRegistry class hierarchy (part 1 of 4)

The following flowchart illustrates considerations used to represent a hierarchy..

The diagram shows only two levels of folders. However, you can embed as many levels of folders as you would need.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Image: PortalRegistry class hierarchy (part 2 of 4)

The following diagram illustrates PortalRegistry class hierarchy.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Image: PortalRegistry class hierarchy (part 3 of 4)

The following diagram continues to illustrate PortalRegistry class hierarchy.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Image: PortalRegistry class hierarchy (part 4 of 4)

The following diagram continues to illustrate PortalRegistry class hierarchy.

Using Content References

Content references have a number of properties, but several properties work together to define the type of Content reference. The values of these properties are interdependent, that is, the value of one indicates the values of others. The properties are:

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- UsageType
- TemplateType
- URLType
- Nodes and URL

UsageType

This is the primary specifier for the type of content reference. There are a number of different types of content references, but all content references can be categorized into the following major types:

- Target
- Template
- Portal Component

Target

The *target* is the page referenced by a URL in the user's browser. This is the main transaction or page that the user wants, and the portal may place other content around this target page based on the template. The template describes any other content, and where to place it, on the page. The template is either gotten from the content reference or a set of default templates.

Content reference links can only be created for content references that have a type of target.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Template

A portal *template* defines how the portal creates a user's page. It's an HTML document that describes the content and where the content is placed. The template specifies one target and zero or more portal components.

Image: A portal template

The portal template in the following example is comprised of four separate template components: one for the navigation and search header, one for related links, one for the target content region, and one for the overall template which specifies where the other components should be placed. At runtime, the target content region would be filled by the HTML returned by the target page, as would the other template component regions.

See "Portal Templates and Template Pagelets" (PeopleTools 8.54: Portal Technology).

Portal Component

A *portal component* is an HTML document, or something that produces an HTML document. The portal component must be defined within a template.

A portal component could be one of a Homepage tab, component reference, or Homepage Pagelet.

UsageType Values

The following table matches the general types of target, template, and portal component to the actual values of the UsageType property.

General Type	*UsageType Value*
Target	Target (TARG)
Template	Frame template (FRMT) or HTML template (HTMT)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

General Type	*UsageType Value*
Pagelet	Pagelet (HPGC)
Homepage Tab	Homepage Tab (HPGT)

More specifically:

- A UsageType value of TARG specifies a content reference that is a target.
- A UsageType value of FRMT specifies a content reference that is an HTML frame template.
- A UsageType value of HTMP specifies a content reference that is an HTML template.
- A UsageType value of HPGC specifies a content reference that is a PeopleSoft homepage component (pagelet).
- A UsageType value of HPGT specifies a Homepage tab.
- A UsageType value of LINK specifies a content reference link.

TemplateType

This property is valid only when the UsageType property is a target. For target type content references (TARG) this controls whether the portal looks for and uses a template to wrap the target.

TemplateType	*Meaning*
NONE	There is no template for this target
HTML	There is some kind of HTML template for this target

URLType

This property gives information about what format the URL is in.

URLType Value	*Meaning*
UEXT	URL points to a non-PeopleSoft (external) URL
UMPG	URL points to a PeopleSoft mobile page
UPGE	URL points to a component
UPHP	URL points to a homepage tab
UPTM	URL points to a template
USCR	URL points to an iScript
UGEN	URL points to a generic PeopleSoft URL.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The URL property is always required (it's one of the parameters for the InsertItem method.) The format of this parameter (or property) depends on the other properties.

Related Links

"Portal Technology Overview" (PeopleTools 8.54: Portal Technology)

Nodes and URL

Nodes and the URL property work together and are interrelated. The node is how to ‘register’ a logical name for a webserver (the webserver name, on the servlet, and so on) not the actual details. This way, content references don’t change when a webserver changes.

For example, suppose you had content that you referenced on the HRMS webserver. However, the machine name for that server changed. You can change the URI of the Node, instead of changing every content reference that referred to that content.

At least one node must be specified as the default local node. Nodes are also required for PeopleSoft components and iScripts.

Considerations When Using Nodes and the URL Property

When a content reference is created it is ‘registered’ with its URL (the portal, and others, typically find a content reference by its URL). The node is used to create a logical name for the webserver, servlet, and so on, so these details are not included in a content reference’s URL. When details of a webserver change, such as at installation time, only the URI for the content provider must change. You don’t have to change the URL for any content references.

When the node is specified, the content provider’s URI is concatenated with the URL property.

The format of the URL property depends on the content it's pointing to.

Summary

The following table summarizes the interrelations between the different content reference properties.

UsageType	***TemplateType***	***StorageType***	***URLType***
Target (TARG)	HTML	Remote (RMTE)	Component (UPGE)
Target (TARG)	HTML	Remote (RMTE)	Internet Script (USCR)
Target (TARG)	HTML	Remote (RMTE)	External (UEXT)
Target (TARG)	NONE	Remote (RMTE)	Component (UPGE)
Target (TARG)	NONE	Remote (RMTE)	Internet Script (USCR)
Target (TARG)	NONE	Remote (RMTE)	External (UEXT)
Frame template (FRMT), HTMP template	NONE	Remote (RMTE)	Internet Script (USCR)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

UsageType	*TemplateType*	*StorageType*	*URLType*
Frame template (FRMT), HTMP template	NONE	Local (LOCL)	N/A
Homepage (HPGT)	NONE	Local (LOCL)	N/A
Template component (TMPC), Homepage component (HPGC)	N/A	Remote (RMTE)	Component (UPGE)
Template component (TMPC), Homepage component (HPGC)	N/A	Remote (RMTE)	Internet Script (USCR)
Template component (TMPC), Homepage component (HPGC)	N/A	Remote (RMTE)	External (UEXT)
Template component (TMPC), Homepage component (HPGC)	N/A	Local (LOCL)	N/A

Naming Conventions

If you create two content references or with the exact same URL, the second one fails.

For example, suppose you create an external content reference with a URL of www.peoplesoft.com. Then you create a second content reference that has a node of PeopleSoft, whose URI is www.peoplesoft.com. The creation of the second content reference fails because the URL already exists.

If you have multiple nodes with the same URI, FindCRefByURL looks for the specified content reference with all those nodes.

If you have multiple nodes with the same URI, but no registered content references, the system uses the template from the alphabetically first node it finds.

Pagelet, node, and portal registry names can consist of any combination of letters, digits and underscores, but they must not contain any spaces or begin with a digit.

Content reference link names cannot have start with numbers, and can not have special characters and spaces.

Deleting Content Considerations

Be extremely careful when you delete any content. There may be more than one object relying on the content you delete.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- If you try to delete a template currently used by a content reference, the node template is set as the default template for the portal, you receive an error when you try to save the item.
- If you delete a homepage template for a user, the system tries to use the default user's template first, before resorting to the portal default template.
- If you try to delete a content provider that is currently used by a content reference, you receive an error and cannot save the PortalRegistry object.

Warning! If you delete a folder, you delete *all* content in the folder. If you delete a folder that contains other folders, that is, a parent folder, all the child folders, and all the content references are deleted.If you delete a PortalRegistry, you delete *everything*. Your entire PortalRegistry is gone, all the folders, content references, templates, and so on. Do not delete a PortalRegistry object unless you are absolutely certain you want to.

Saving Content Considerations

The following portal registry classes have Save methods:

- PortalRegistry
- Folder
- Content reference
- Content reference links
- TabDefinition
- PageletCategory
- Pagelet
- Homepage
- Favorites collection

This means if you change a folder, you must save the folder. If you change a folder and only save at the PortalRegistry level, your changes are *not* saved.

Some classes do *not* have a Save method. For these classes, you must save the parent object.

- If you change a node, node template, or remote portal, you must use the PortalRegistry Save method.
- If you change an AttributeValue you must use the Save method with the item that contains the AttributeValue (folder, content reference, PageletCategory, or Pagelet).
- If you change a PermissionValue, you must use the Save method with the item that contains the PermissionValue (folder, content reference, PageletCategory or Pagelet).
- If you change a UserTab or a SelectedPagelet, you must use the Homepage Save method.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Data Type of a PortalRegistry Object

PortalRegistry objects, and all objects instantiated from a PortalRegistry object, are declared as data type ApiObject. For example,

```
Local ApiObject &MyRegistry;
```

```
Local ApiObject &MyFolder, &MyAttributeValue;
```

Note: PortalRegistry objects can only be declared as Local.

Considerations Using Local Variables

When a local variable has a reference to an object and the end-user clicks the Back button on a browser, the local variable is set to NULL. This is always logged in the trace file.

Considerations Using Global Variables

Global variables are not available to a portal or applications on separate databases. They are available only on applications and Portals in the *same* database.

Scope of a PortalRegistry Object

A PortalRegistry object can be instantiated from the following language environments:

- PeopleCode
- C/C++
- Java

Related Links

Portal Registry Classes Example

PortalRegistry Reference

The following sections provide more detail of the properties, methods, and other objects that you can use with a PortalRegistry object. If you don't want to programmatically change a portal registry, you can use the Portal Administration Tool pages instead.

Session Class Methods

PortalRegistry objects don’t have any built-in functions. They are instantiated from a session object. In this section, we discuss the Session Object methods. The methods are listed in alphabetical order.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

"GetSession" (PeopleTools 8.54: PeopleCode Language Reference)

"%Session" (PeopleTools 8.54: PeopleCode Language Reference)

FindPortalRegistries

Syntax

FindPortalRegistries(*Name*)

Description

The FindPortalRegistries method returns a reference to a PortalRegistry Collection filled with zero or more PortalRegistry objects matching the *Name* parameter. The *Name* parameter takes a string value.

You can use a partial key to get a smaller subset of the PortalRegistry collection. For example, to get a collection of all the PortalRegistry objects whose names start with the letter "B", specify just the letter B for *Name*:

```
&MyColl = &MySession.FindPortalRegistries("B");
```

Parameters

Name	Specify the name of the PortalRegistry object to find. This parameter takes a string value.

Returns

A PortalRegistry Collection object.

Example

The following example returns a collection with references to all PortalRegistry objects.

```
Local ApiObject &MySession;
Local ApiObject &MyColl;

&MySession = %Session;
&MyColl = &MySession.FindPortalRegistries("");
```

GetActualRemoteNodes

Syntax

GetActualRemoteNodes()

Description

Use the GetActualRemoteNodes method to return a collection of remote nodes for the session.

Note: This method will only return remote nodes.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

None.

Returns

A reference to a collection of remote nodes if successful, null otherwise.

Example

```
&remoteNodeColl = %Session.GetActualRemoteNodes();
```

Related Links

RemoteNode Collection

GetLocalNode

Syntax

GetLocalNode()

Description

Use the GetLocalNode method to return a reference to the node defined as the local node for this session.

Parameters

None.

Returns

A reference to a node object if successful, Null otherwise.

Example

```
&Node = %Session.GetLocalNode();
```

Related Links

Node Class

GetNodes

Syntax

GetNodes()

Description

Use the GetNodes method to return a collection of both local and remote nodes for the session.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

None.

Returns

A reference to a collection of nodes if successful, Null otherwise.

Example

```
&NodeColl = %Session.GetNodes();
```

Related Links

Node Collection

GetPortalRegistry

Syntax

GetPortalRegistry()

Description

The GetPortalRegistry method returns an empty PortalRegistry object. You can then open or delete an existing PortalRegistry, or create a new one.

Parameters

None.

Returns

An empty PortalRegistry object.

Example

```
Local ApiObject &MyPortal;

&MyPortal = %Session.GetPortalRegistry();
&PORTAL_NAME = %Request.GetParameter("PORTAL_NAME");
&Portal.Open(PORTAL_NAME);
```

GetRemoteNodes

Syntax

GetRemoteNodes()

Description

Use the GetRemoteNodes method to return a collection of nodes for the session.

Note: This method returns both local and remote nodes.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

None.

Returns

A reference to a collection of nodes if successful, Null otherwise.

Example

```
&NodeColl = %Session.GetNodes();
```

Related Links

RemoteNode Collection

PortalRegistry Class

A PortalRegistry object is returned from:

- The GetPortalRegistry session method.
- The PortalRegistry Collection Methods First, ItemByName, or Next.

Note: In addition to the following methods, the PortalRegistry class has methods used with the Search API.

Related Links

GetPortalRegistry
PortalRegistry Collection Methods
Changing PortalRegistry Properties
Understanding the Verity Search Classes

PortalRegistry Class Methods

In this section, we discuss the PortalRegistry class methods. The methods are discussed in alphabetical order.

Close

Syntax

Close()

Description

The Close method closes the PortalRegistry object, that is, this method sets the object to the state it was in immediately after the GetPortalRegistry was done on the PeopleSoft Session object. Any unsaved

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

changes are discarded. The Close method can be used only on an open PortalRegistry, not a closed one. This means you must have opened the PortalRegistry with the Open method before you can close it.

Parameters

None.

Returns

A Boolean value: True if the PortalRegistry object is successfully closed, False otherwise.

Example

```
&Rslt = &MyRegistry.Close();

If Not &Rslt Then
   /* registry not closed - do error processing */
End-if;
```

Related Links

Open
Save

CopyObject

Syntax

CopyObject(*sourcePortalName*, *sourceRefType*, *sourceObjName*, *targetPortalName*, *targetPrntFldrName*, *copyChildren*)

Description

Use the CopyObject method to copy folders and content references between portal registries.

If the object being copied has related HTML, the HTML is also copied and named according to the current portal naming convention for HTML objects, which is:

PR_<*portalname*>_<*objectname*>

where <*portalname*> is up to the first 8 characters of the portal name and <*objectname*> is up to the first 17 characters of the object name.

Considerations Using CopyObject

The source portal name and the target portal name cannot be the same name.

The *targetPrntFldrName* must be a folder that exists in the portal identified by the target portal name. It cannot be null (or empty). If you need to copy an entire portal, the portal must first be "created" using the Create method, before copying over all the folders and content references.

The *copyChildren* parameter is ignored for content references. However, it still must be set to "Yes" or "No".

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

sourcePortalName Specify the name of the portal from which the object is to be copied.

sourceRefType Specify the type of object to be copied. Values are:

- "C" for content references
- "F" for folders

This parameter is case-sensitive.

sourceObjName Specify the name of the object to be copied.

targetPortalName Specify the name of the portal to which the object will be copied.

targetPrntFldrName Specify the name of the folder that will be the parent folder for the source object.

copyChildren Specify whether to also copy the children of the source object. This parameter is valid only with folder objects. Values are:

- "Yes" copy child objects
- "No" do not copy child objects

This parameter is case-sensitive.

Returns

A Boolean value: True if object copied successfully, False otherwise.

Example

```
&Success = &Portal.CopyObject("PORTAL", "F", "PEOPLETOOLS_QUALITY", "BOGUS", "PORTA⇒
L_ROOT_OBJECT", "Yes");
If (&Success = False) Then
   WinMessage("portal copy failed");
   Exit;
End-If;
```

Create

Syntax

Create(*RegistryName*)

Description

The Create method creates a new PortalRegistry in the PortalRegistry object called *RegistryName*. The specified registry must be a new registry. The Create method returns False if the registry already exists.

The new PortalRegistry is immediately committed to the database. If you change any property of a PortalRegistry after you create the object, use the Save method to commit your changes to the database.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

When a registry is created, a folder called *Root* is automatically created. This is the root folder for the registry.

Note: If you're using Visual Basic, you must check that the PortalRegistry is actually created. If you use a duplicate name, a zero is returned, but no error results.

Parameters

RegistryName The name of the registry to create. This parameter takes a string value. If you specify a registry that already exists, this method returns a False value.

Returns

A Boolean value: True if the PortalRegistry object is successfully created, False otherwise.

Example

```
&PORTAL_NAME = MY_PORTAL_RECORD.PORTALNAME;
&MyPortal = %Session.GetPortalRegistry();

If NOT &MyPortal.Create(&PORTAL_NAME) Then;
   /* portal not created - do error processing */
End-If;
```

Related Links

Open
Save
Close
Delete

CreateContentRefLink

Syntax

CreateContentRefLink(*LinkName*, *LinkLabel*, *LinkParent*, *CRefPortalName*, *CRefObjectName*)

Description

Use the CreateContentRefLink method to create a link to any content reference in any portal in a local database.

For example, using this method, you can create a link to a content reference in the EMPLOYEE portal, to a content reference in the CUSTOMER portal, or to a content reference in the current portal.

Parameters

LinkName Specify the name of the link as a string. This is the ID of the link. The name is validated as that of the content reference name. It cannot start with a number, and can not have special characters and spaces. This property is not translated.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

LinkLabel Specify the label of the link as a string. This property can be translated. This is the label that appears on the left hand navigation menu If this value is blank, a linked content reference label is displayed instead.

LinkParent Specify the parent folder of the link, as a string.

CRefPortalName Specify the portal name of the content reference, to which the link is pointing, as a string.

CRefObjectName Specify the ID of the content reference to which the link is pointing, as a string.

Returns

A reference to a newly created ContentReference link object.

Example

```
Local ApiObject &Portal, &CRef, &CReflink;
&Portal = PortalOpen();
&CReflink = &Portal.CreateContentRefLink(<Unique Link Name> , <LinkLable>, "<Link's⇒
 Parent folder >", "<Cref Portal Name>", <Cref Object Name>);

/*... Use the link object */

&Portal.Close();
```

CreateRemote

Syntax

CreateRemote(*PortalName*, *RemoteNodeName*)

Description

Use the CreateRemote method to create a remote portal. Although you can have more than one portal on a node, they must all be uniquely named.

Parameters

PortalName Specify the name of the new portal to create on the remote node.

RemoteNodeName Specify the name of the remote node to create the new portal on.

Returns

A Boolean value: True if the PortalRegistry object is successfully created, False otherwise.

Related Links

Create
Portals

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Delete

Syntax

Delete(*RegistryName*)

Description

The Delete method deletes the PortalRegistry *from the database,* including any data and tables.

Warning! If you delete a PortalRegistry, you delete *everything*. Your entire PortalRegistry is gone, all the folders, content references, templates, and so on. Do not delete a PortalRegistry object unless you are absolutely certain that you want to.

Note: The portal registry classes execute some methods "interactively", that is, as they happen. The item won't be marked for deletion, then actually deleted later. The item is deleted from the database *as soon as* the method is executed.

The Delete method can only be used with a *closed* registry, it cannot be used on an open registry. Before you use the Delete method, you must explicitly close the PortalRegistry object (with the Close method.) The Delete method returns False if you try to delete an open PortalRegistry object.

Parameters

RegistryName The name of the registry to delete. This parameter takes a string value. If you specify a registry that doesn't exist, this method returns a False value.

Returns

A Boolean value: True if the PortalRegistry object is successfully deleted, False otherwise.

Example

The following example deletes all PortalRegistry objects that start with HRMS_99.

```
Local ApiObject &MySession;
Local ApiObject &MyPortal;

&MySession = %Session;

&MyPortal = &MySession.GetPortalRegistry();

&MyPortal.Delete("HRMS_99");
```

Related Links

Close

Open

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

DeleteHomepage

Syntax

DeleteHomepage()

Description

The DeleteHomepage method deletes the current user's homepage. This method is valid only after a user has opened a PortalRegistry object.

Parameters

None.

Returns

A Boolean value: True if the homepage is successfully deleted, False otherwise.

Related Links

UserHomepage Class

FindCRefByName

Syntax

FindCRefByName(*Name*)

Description

The FindCRefByName method returns the content reference object corresponding to *Name*. The name is a unique identifier for each content reference.

Considerations on Returned Content References

This method returns content reference objects that aren't yet valid as well as ones that are no longer valid. When you create your program, you must check for these invalid values if you don't want to use them. You can check using ValidTo, ValidFrom, or IsVisible.

This method returns content reference objects that you aren't authorized to. When you create your program, you should always check the Authorized property. This is the only property you can view from an object that you're not authorized to view.

Parameters

Name	A unique name within the registry that identifies the content reference. This parameter takes a string value. This parameter uses the name, not the label, of a content reference.

Returns

What this method returns depends on the condition of the content reference:

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- If the content reference name is valid and the end-user has access to the content reference, a content reference object is returned.
- If the content reference is valid but the end-user doesn't have access to it a content reference object is returned, however, the only property you can access is the Authorized property.
- If you specified an invalid name this method returns NULL.

Example

The following example returns a GLOBAL_PAYROLL content reference object:

```
&CRef = &Portal.FindCRefByName("GLOBAL_PAYROLL");
```

Related Links

Content Reference Class

FindCRefByURL

Syntax

FindCRefByURL(*URL*)

Description

The FindCRefByURL method returns the content reference object corresponding to *URL*. The URL specified by *URL* must be an absolute URL.

Note: The portal registry API needs the current URI of the local node to work. During runtime, it gets this information from the current webserver. For Application Engine programs, there isn't a current webserver, so it has to get this information from the database.

If you have multiple content providers with the same URI, FindCRefByURL looks for the specified content reference with all those content providers.

To access pagelet categories and their associated pagelets, use the PageletCategories collection from the PortalRegistry object, not FindCRefByURL.

Considerations on Returned Content References

This method returns content reference objects that aren't yet valid as well as ones that are no longer valid. When you create your program, check for these properties (ValidTo and ValidFrom) if you don't want to use them.

This method returns content reference objects that the end-user isn't authorized to. When you create your program, always check the Authorized property. This is the only property you can view from an object that the end-user isn't authorized to view.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

URL	A URL that represents the content. This parameter takes a string value. This URL must be an absolute URL. This parameter is case-insensitive.

Returns

What this method returns depends on the condition of the content reference:

- If the end-user has access to the URL, a content reference object is returned.
- If the content reference is registered, but the end-user doesn't have access to it, a content reference is returned, but the only property you can access is the Authorized property.
- If a URL isn't registered or is invalid, this method returns NULL.

Example

The following example finds a content reference from a URL:

```
&UserCRef = &Portal.FindCRefByURL("http://www.PeopleSoft.Com");
```

Related Links

GetQualifiedURL
QualifiedURL
Content Reference Class

FindCRefForURL

Syntax

FindCRefForURL(*URL*)

Description

The FindCRefForURL method returns the content reference object corresponding to *URL*. The URL specified by *URL* must be an absolute URL.

If the exact content reference is not found, this method tries to look for the content reference again, after stripping off the query portion of the URL.

If you don't want the system searched without the query string, use the FindCRefByURL method.

Note: The portal registry API needs the current URI of the local node to work. During runtime, it gets this information from the current webserver. For Application Engine programs, there isn't a current webserver, so it has to get this information from the database.

If you have multiple content providers with the same URI, FindCRefForURL looks for the specified content reference with all those content providers.

To access pagelet categories and their associated pagelets, use the PageletCategories collection from the PortalRegistry object, not FindCRefForURL.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Considerations on Returned Content References

This method returns content reference objects that aren't yet valid as well as ones that are no longer valid. When you create your program, check for these properties (ValidTo and ValidFrom) if you don't want to use them.

This method returns content reference objects that the end-user isn't authorized to. When you create your program, always check the Authorized property. This is the only property you can view from an object that the end-user isn't authorized to view.

Parameters

URL	A URL that represents the content. This parameter takes a string value. This URL must be an absolute URL. This parameter is case-insensitive.

Returns

What this method returns depends on the condition of the content reference:

- If the end-user has access to the URL, a content reference object is returned.
- If the content reference is registered, but the end-user doesn't have access to it, a content reference is returned, but the only property you can access is the Authorized property.
- If a URL isn't registered or is invalid, this method returns NULL.

Example

The following example finds a content reference from a URL. If the content reference isn't found from the full URL, the query string is stripped and the system searches again:

```
&UserCRef = &Portal.FindCRefForURL("http://www.peoplesoft.com/crefs/psportal/techno⇒
logies/?url=http%3a%2f%2faugust2004%2fipass.html");
```

Related Links

GetQualifiedURL
QualifiedURL
FindCRefByURL
Content Reference Class

FindCRefLinkByName

Syntax

FindCRefLinkByName(*LinkName*)

Description

Use the FindCRefLinkByName method to find the existing link in the current portal. If the link is found a reference to ContentReference link object is returned. A Null value is returned if the link is not found in the database, and the error message is added to message collection

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Considerations on Returned Links

This method returns links that aren't yet valid as well as ones that are no longer valid. When you create your program, you must check for these properties (ValidTo and ValidFrom) if you don't want to use them. This method may also return objects that you aren't authorized to. When you create your program, you should always check the Authorized property. This is the only property you can view from an object that you're not authorized to view.

Parameters

LinkName	Specify the name of the link as a string. This is the ID of the link.

Returns

A reference to an existing ContentReference link object. or a Null value if the link is not found.

FindFolderByName

Syntax

`FindFolderByName``(`*`Name`*`)`

Description

The FindFolderByName method returns the Folder object corresponding to *Name*. The name is a unique identifier for each folder.

Considerations on Returned Folders

This method returns Folder objects that aren't yet valid as well as ones that are no longer valid. When you create your program, check for these properties (ValidTo and ValidFrom) if you don't want to use them.

This method returns folder objects that you aren't authorized to. When you create your program, always check the Authorized property. This is the only property you can view from an object that you're not authorized to view.

Parameters

Name	A unique name within the registry that identifies the folder. This parameter takes a string value. This parameter takes the name of a folder, not the label.

Returns

What this method returns depends on the condition of the folder:

- If the folder name is valid and the end-user has access to the folder, a folder object is returned.
- If the folder is valid but the end-user doesn't have access to it a folder object is returned, however, the only property you can access is the Authorized property.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- If you specified an invalid name this method returns NULL.

Example

The following example returns a folder named ROOT:

```
&MyFolder = &MyPortal.FindFolderByName("ROOT");
```

The following example returns the folder object for an already instantiated content reference:

```
&Folder = &Portal.FindFolderByName(&CRef.ParentName);
```

Related Links

Folder Class

FindPgltByName

Syntax

FindPgltByName(*PageletName*)

Description

The FindPgltByName method returns the pagelet object corresponding to *PageletName*. The name is a unique identifier for each pagelet.

Considerations on Returned Pagelets

This method returns pagelet objects that aren't yet valid as well as ones that are no longer valid. When you create your program, check for these properties (ValidTo and ValidFrom) if you don't want to use them.

This method returns pagelet objects that you aren't authorized to. When you use create your program, always check the Authorized property. This is the only property you can view from an object that you're not authorized to view.

Parameters

PageletName	A unique name within the registry that identifies the Pagelet. This parameter takes a string value. This parameter takes the name of a Pagelet, not the label.

Returns

What this method returns depends on the condition of the Pagelet:

- If the Pagelet name is valid and the end-user has access to the Pagelet, a Pagelet object is returned.
- If the Pagelet is valid but the end-user doesn't have access to it a Pagelet object is returned, however, the only property you can access is the Authorized property.
- If you specified an invalid name this method returns NULL.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

The following example returns a pagelet named HomePg_Dictionary:

```
&MyPglt = &MyPortal.FindPgltByName("HomePg_Dictionary");
```

Related Links

Pagelet Class

GetAbsoluteContentURL

Syntax

GetAbsoluteContentURL(*NodeName*, *URL*)

Description

The GetAbsoluteContentURL method returns the absolute unwrapped simple URL of the content, in the context of the current portal. For example, if the PortalRegistry object accessed a portal called Employees, and the method were called like this:

```
&Registry.getAbsoluteContentURL(Node.CRM,  "/c/SERVICES.ORDERS.GBL");
```

It would return the following string:

```
http://crmserver/servlets/psc/crmHome/Employees/CRM/c/SERVICES.ORDERS.GBL
```

In the returned string, the portion of the string from server name through *portal_home* (crmHome in the example) are the ones associated with the content node (CRM in the example). The portal is the current portal, and the rest of the URL is the URL string passed in.

Parameters

NodeName	Specify the name of the node that contains the content. You can also use a string, such as %Node, for this value.
URL	Specify the relative URL pointing to the content that you want the absolute URL generated for.

Returns

A string containing the absolute URL.

GetDefaultHPTabOID

Syntax

GetDefaultHPTabOID()

Description

Use the GetDefaultHPTabOID method to return the name of the first homepage tab that is found and authorized for the current user ID.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The search order of the tabs depends on Sequence number of the tab name and is sorted alphabetically.

Parameters

None.

Returns

A string

GetQualifiedURL

Syntax

GetQualifiedURL(*ContentProvider, RelativeURL*)

Description

Note: This method is maintained only for backward compatibility. If your existing code uses this method, it actually returns the value from GetAbsoluteContentURL method. New applications should use the GetAbsoluteContentURL method.

Related Links

GetAbsoluteContentURL

GrantPermissionForComponent

Syntax

GrantPermissionForComponent(*MenuName, ComponentName, Market, PermListName, NodeName*)

Description

Use the GrantPermissionForComponent method to grant the specified permission and cascaded upwards on parent folders to the specified component. In addition, the specified permission is granted to any component references that point to the specified component, and any parent folders.

Components that have query strings are also searched and permissions are applied on them.

If you use the string "LOCAL_NODE" as *NodeName*, the system uses the node name currently defined as local.

All component entries in the portal registry are affected for all the portals. Not just the current portal.

Parameters

MenuName	Specify the menu name, as a string, that the component you want to grant permissions for is associated with.
ComponentName	Specify the component name, as a string, that you want to grant permissions for.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Market Specify the market, as a string, associated with the component that you want to grant permissions for.

PermListName Specify the name of the permission list, as a string, that you want to use.

NodeName Specify the node of the component reference, as a string, that points to the component reference that you want to grant permissions for. If you use the string "LOCAL_NODE", the system uses the node name currently defined as local.

Returns

A Boolean value: True if method completed successfully, False otherwise.

Example

The My Profile Component Reference points to the USERMAINT_SELF component. Using the following example, "ALLPANLS" permission is granted to the MY_PROFILE component reference, as well as "MY INFO", the parent folder.

```
&Portal.GrantPermissionForComponent("MAINTAIN_SECURITY", "USERMAINT_SELF", "GBL", "⇒
ALLPANLS", "LOCAL_NODE");
```

Related Links

GetAbsoluteContentURL

"Understanding Permission Lists" (PeopleTools 8.54: Security Administration)

GrantPermissionForScript

Syntax

GrantPermissionForScript(*RecordName*, *FieldName*, *EventName*, *FuncName*, *PermListName*, *NodeName*)

Description

Use the GrantPermissionForScript method to grant the specified permission to the specified iScript. In addition, the specified permission is granted to any component references that point to the specified iScript, and any parent folders.

If you use the string "LOCAL_NODE" as *NodeName*, the system uses the node name currently defined as local.

All iScript entries in the portal registry are affected for all the portals. Not just the current portal.

Parameters

RecordName Specify the record name, as a string, of the record containing the iScript. All iScripts are contained on records whose names start with "WEBLIB".

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

FieldName Specify the name of the field, as a string, containing the iScript.

EventName Specify the name of the event, as a string, containing the iScript. Generally iScripts are contained in the FieldFormula event.

FuncName Specify the name of the function, as a string, containing the iScript.

PermListName Specify the name of the permission list, as a string, that you want to use.

NodeName Specify the node of the component reference, as a string, that points to the component reference that you want to grant permissions for. If you use the string "LOCAL_NODE", the system uses the node name currently defined as local.

Returns

A Boolean value: True if method completed successfully, False otherwise.

Example

```
&Portal.GrantPermissionForScript("WEBLIB_ALERT", "ALERTCOUNT", "FieldFormula", "Con⇒
nect_Alert", "ALLPGS", "Local_Node");
```

Related Links

RevokePermissionForComponent

"Understanding Permission Lists" (PeopleTools 8.54: Security Administration)

Open

Syntax

Open(*RegistryName*)

Description

The Open method opens the PortalRegistry specified by the parameters. The registry must already exist. The Open method can be used only with a *closed* PortalRegistry, it cannot be used on an open registry.

Parameters

RegistryName The name of the registry to open. This parameter takes a string value. If you specify a registry that doesn't exist, this method returns a False value.

Returns

A Boolean value: True if the PortalRegistry object is successfully opened, False otherwise.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

In the following example, the name of the portal is stored as the value of a field in a record.

```
&PORTAL_NAME = EO_PE_REG_AET.PORTAL_NAME;
&Portal = %Session.GetPortalRegistry();

&Portal.Open(&PORTAL_NAME);
```

Related Links

Open
Save
Close
Delete

PermissionListDelete

Syntax

PermissionListDelete(*PermListName*)

Description

Use the PermissionListDelete method to delete the specified permission list from the PortalRegistry.

If you try to delete a permission list that is still in use, you receive an error when you try to save the object.

The permission list is deleted from all the portal objects for all the portal.

Parameters

PermListName	Specify the permission list to delete from the PortalRegistry.

Returns

A Boolean value: True if the permission list is successfully deleted, False otherwise.

PermissionListSaveAs

Syntax

PermissionListSaveAs(*PermListSourceName*, *PermListTargetName*)

Description

Use the PermissionListSaveAs method to copy the specified permission list in the PortalRegistry.

Parameters

PermListSourceName	Specify the name of the PermissionList to copy.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

PermListTargetName Specify the name that you want to give the new PermissionList.

Returns

A Boolean value: True if the permission list is successfully copied, False otherwise.

RevokePermissionForComponent

Syntax

RevokePermissionForComponent(*MenuName*, *ComponentName*, *Market*, *PermListName*, *NodeName*)

Description

Use the RevokePermissionForComponent method to revoke the specified permission to the specified component. In addition, the specified permission is revoked for any component references that point to the specified component.

If you use the string "LOCAL_NODE" as *NodeName*, the system uses the node name currently defined as local.

All component entries in the portal registry are affected for all the portals. Not just the current portal.

Parameters

MenuName Specify the menu name, as a string, that the component that you want to revoke permissions for is associated with.

ComponentName Specify the component name, as a string, that you want to revoke permissions for.

Market Specify the market, as a string, associated with the component that you want to revoke permissions for.

PermListName Specify the name of the permission list, as a string, that you want to use.

NodeName Specify the node of the component reference, as a string, that points to the component reference that you want to revoke permissions for. If you use the string "LOCAL_NODE", the system uses the node name currently defined as local.

Returns

A Boolean value: True if method completed successfully, False otherwise.

Example

The My Profile Component Reference points to the USERMAINT_SELF component. Using the following example, "ALLPANLS" permission is revoked to the MY_PROFILE component reference.

```
&Portal.RevokePermissionForComponent("MAINTAIN_SECURITY", "USERMAINT_SELF", "GBL", ⇒
"ALLPANLS", "LOCAL_NODE");
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

GrantPermissionForComponent

"Understanding Permission Lists" (PeopleTools 8.54: Security Administration)

RevokePermissionForScript

Syntax

RevokePermissionForScript(*RecordName*, *FieldName*, *EventName*, *FuncName*, *PermListName*, *NodeName*)

Description

Use the RevokePermissionForScript method to revoke the specified permission to the specified iScript. In addition, the specified permission is revoked for any component references that point to the specified iScript.

If you use the string "LOCAL_NODE" as *NodeName*, the system uses the node name currently defined as local.

All component entries in the portal registry are affected for all the portals. Not just the current portal.

Parameters

RecordName	Specify the record name, as a string, of the record containing the iScript. All iScripts are contained on records whose names start with "WEBLIB".
FieldName	Specify the name of the field, as a string, containing the iScript.
EventName	Specify the name of the event, as a string, containing the iScript.
FuncName	Specify the name of the function, as a string, containing the iScript. Generally iScripts are contained in the FieldFormula event.
PermListName	Specify the name of the permission list, as a string, that you want to use.
NodeName	Specify the node of the component reference, as a string, that points to the component reference that you want to revoke permissions for. If you use the string "LOCAL_NODE", the system uses the node name currently defined as local.

Returns

A Boolean value: True if method completed successfully, False otherwise.

Example

```
&Portal.RevokePermissionForScript("WEBLIB_ALERT", "ALERTCOUNT", "FieldFormula", "Co⇒
nnect_Alert", "ALLPGS", "Local_Node");
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

GrantPermissionForScript

"Understanding Permission Lists" (PeopleTools 8.54: Security Administration)

Save

Syntax

Save()

Description

The Save method saves changes that you made to the PortalRegistry or to a node template. It does *not* save any changes that you made to a folder, content reference, and so on.

Note: To save changes for a folder or content reference use the save method associated with that object.

Parameters

None.

Returns

A Boolean value: True if the PortalRegistry object is successfully saved, False otherwise.

Example

```
If Not(&MyPortal.Save()) Then
   /* do error checking */
End-if:
```

PortalRegistry Class Properties

In this section, we discuss the PortalRegistry class properties. The properties are discussed in alphabetical order.

DefaultTemplate

Description

This property returns or sets the name of the default template for this PortalRegistry object as a string.

If you delete a template for a content reference, and none of the other content references on a page have a template, the default template specified with the Node is used. If there's no template for the Node, the template specified with this property is used.

To return a reference to the content reference that contains the template specified by this property, use the TemplateObject property.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Note: If you change the Default Template for a portal, the template won't take effect until you close all the existing browser windows with the session and open a new browser window.

This property takes only the first 30 characters of a value. If you specify a value longer than 30 characters, the remaining characters are ignored.

This property is read-write.

Related Links

TemplateObject

Description

Description

This property returns or sets the description of this PortalRegistry object as a string

The length of this property is 256 characters.

This property is read-write.

Favorites

Description

This property returns a reference to the Favorites Collection for the current end-user.

This property is read-only.

Related Links

Favorite Collection

FolderNavObject

Description

This property specifies the content reference name to be used for the folder navigation object. When the folder navigation is tunred on, this content reference is displayed as the folder navigation homepage. This property takes a string value.

This property is read-write.

Related Links

IsFolderNavigation

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Homepage

Description

This property returns a reference to the Homepage for the current end-user.

This property is read-only.

IsFolderNavigation

Description

This property specifies if there is folder navigation. When the folder navigation is turned on, the user can see a folder homepage when clicked on the folder in the lefthand navigation menu. This property takes a Boolean value: true if folder navigation is on, false otherwise.

This property is read-write.

Related Links

FolderNavObject

Name

Description

This property returns the name of the PortalRegistry object as a string.

The length of this property is 30 characters.

This property is read-only.

NodeTemplates

Description

This property returns a reference to a NodeTemplate Collection. This property can be used with a *closed* portal registry, that is, before you open it with the Open method.

This property is read-only.

Related Links

NodeTemplate Collection

OwnerId

Description

This property returns or sets the owner ID of the PortalRegistry object as a string.

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

PageletCategories

Description

This property returns a reference to a PageletCategories Collection that contains all the PageletCategories for a portal.

This property is read-only.

Related Links

PageletCategory Collection

Portals

Description

This property returns a reference to a Portal collection that contains references to all the portals in the database.

This property is read-only.

Related Links

Portal Collection

RootFolder

Description

This property returns the root folder object for this PortalRegistry object.

This property is read-only.

TabDefinitions

Description

This property returns reference to a TabDefinitions Collection that contains all the TabDefinitions for a portal.

This property is read-only.

Related Links

TabDefinition Collection

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

TemplateObject

Description

This property returns a reference to a content reference object that contains the template specified by the DefaultTemplate property. If no template is specified with DefaultTemplate, this property returns Null.

This property is read-only.

Related Links

DefaultTemplate

PortalRegistry Collection

A PortalRegistry Collection is returned by the FindPortalRegistries session class method.

See FindPortalRegistries.

PortalRegistry Collection Methods

In this section, we discuss the PortalRegistry collection methods. The methods are discussed in alphabetical order.

First

Syntax

```
First()
```

Description

The First method returns the first PortalRegistry object in the PortalRegistry collection.

Example

```
&MyRegistry = &MyCollection.First();
```

Item

Syntax

```
Item(number)
```

Description

The Item method returns the PortalRegistry object with the position in the PortalRegistry collection specified by *number*.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

number	Specify the position number in the collection of the PortalRegistry object that you want returned.

Returns

A PortalRegistry object if successful, NULL otherwise.

Example

```
For &I = 1 to &MyCollection.Count
   &MyRegistry = &MyCollection.Item(&I);
   /* Do processing */
End-For;
```

Next

Syntax

Next()

Description

The Next method returns the next PortalRegistry object in the PortalRegistry collection. You can use this method only after you have used the First method: otherwise the system doesn't know where to start.

Example

```
&MyRegistry = &MyCollection.Next();
```

PortalRegistry Collection Property

This section discusses the Count property.

Count

Description

This property returns the number of PortalRegistry objects in the PortalRegistry collection, as a number.

This property is read-only.

Example

```
&COUNT = &MY_COLLECTION.Count;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Node Class

The node indicates the URI of the content server. If the node is a PeopleSoft content server, it has a PeopleSoft server URI. If the node has external content, the URI indicates the external content.

Use the IsLocal or IsDefault to determine if a node from a RemoteNode collection is remote or local.

Node objects are instantiated from the following:

- From a Session object with the GetLocalNode method.
- From a Node Collection with the First, InsertItem, ItemByName, and Next methods.
- From a RemoteNode Collection with the First, InsertItem, ItemByName, and Next methods.

See GetLocalNode, Node Collection, RemoteNode Collection.

Node Class Properties

In this section, we discuss the Node class properties. The properties are discussed in alphabetical order.

ActiveNode

Description

This property indicates whether the node has been specified as an active node. This property returns a Boolean value: True, the node is active, False otherwise.

This property is read-only.

AppsRelease

Description

This property returns the release of the PeopleSoft Applications hosted on this node as a string. This property is valid only when the NodeType property is set to PeopleSoft (PIA).

This property is read-only.

Related Links

NodeType

ContentURI

Description

This property returns the URI for the content webserver of this node as a string.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-only.

DefaultPortalName

Description

This property returns the name of the portal associated with the node as the default portal for the node.

This property is read-only.

Description

Description

This property returns the description for this node as a string.

The length of this property depends on your system database limit for LONG fields.

This property is read-only.

IsDefault

Description

This property indicates whether the node has been specified as the default local node. This property takes a Boolean value: True, this node has been specified as the default local node, False otherwise.

This property is valid only when the NodeType property is set to PeopleSoft (PIA).

This property is read-only.

Related Links

NodeType

IsLocal

Description

This property indicates whether this node has been specified as the local PeopleSoft node. This property takes a Boolean value: True, this node has been specified as a local node, False otherwise.

This property is valid only when the NodeType property is set to PeopleSoft (PIA).

This property is read-only.

Related Links

NodeType

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Name

Description

This property returns the name for this node object as a string. The name is a unique identifier for each node object.

Every node name must be unique in the database.

This property is read-only.

NodePassword

Description

This property returns the password for this node object as a string.

This property is read-only.

NodeType

Description

This property indicates what the node is used for. Nodes can either define PeopleSoft or external systems. PeopleSoft nodes have more capabilities than external nodes, therefore several other properties depend on this property.

Values are:

Value	*Description*
PIA	PIA (Peoplesoft 8.4 simple URL format)
EX	External Node
ICT	ICType (used for 8.1x content)

PIA is the default value on a new Node.

This property is read-only.

PortalURI

Description

This property returns the URI for the portal webserver of this node as a string. This property is valid only when the NodeType property is set to PeopleSoft (PIA).

This property is read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

NodeType

ToolsRelease

Description

This property returns the release of PeopleTools running on this node as a string. This property is valid only when the NodeType property is set to PeopleSoft (PIA).

This property is read-only.

Related Links

NodeType

Node Collection

A node collection contains a set of references to all nodes defined in the database.

Node Collection Methods

In this section, we discuss the Node collection methods. The methods are discussed in alphabetical order.

First

Syntax

```
First()
```

Description

The First method returns the first Node object in the Node collection.

Parameters

None.

Returns

A Node object.

Example

```
&MyNode = &MyCollection.First();
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ItemByName

Syntax

ItemByName(*NodeName*)

Description

The ItemByName method returns the Node object with the name specified by *NodeName*.

Parameters

NodeName	Specify the name of an existing node in the Node collection. If you specify an invalid name, the object returned is NULL.

Returns

A Node object if successful, NULL otherwise.

Example

```
&MyOldNode = &MyPortal.Nodes.ItemByName("HRMS");
```

Next

Syntax

Next()

Description

The Next method returns the next Node object in the Node collection. You can use this method only after you have used the First method: otherwise the system doesn't know where to start.

Parameters

None.

Returns

A Node object.

Example

```
&MyNode = &MyCollection.Next();
```

Node Collection Property

In this section, we discuss the Count property.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Count

Description

This property returns the number of Node objects in the Node Collection, as a number.

This property is read-only.

Example

```
&COUNT = &MY_COLLECTION.Count;
```

RemoteNode Collection

A remote node collection contains a set of references to all the nodes defined in the database, both local and remote.

Use the IsLocal property of the returned node object to determine if the node is remote or local.

RemoteNode Collection Methods

In this section, we discuss the RemoteNode collection methods. The methods are discussed in alphabetical order.

First

Syntax

```
First()
```

Description

The First method returns the first Node object in the RemoteNode collection.

Parameters

None.

Returns

A Node object.

Example

```
&MyNode = &MyCollection.First();
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ItemByName

Syntax

ItemByName(*NodeName*)

Description

The ItemByName method returns the Node object with the name specified by *NodeName*.

Parameters

NodeName	Specify the name of an existing node in the RemoteNode collection. If you specify an invalid name, the object returned is NULL.

Returns

A Node object if successful, NULL otherwise.

Example

```
&MyOldNode = &MyPortal.RemoteNodes.ItemByName("HRMS");
```

Next

Syntax

Next()

Description

The Next method returns the next Node object in the RemoteNode collection. You can use this method only after you have used the First method: otherwise the system doesn't know where to start.

Parameters

None.

Returns

A Node object.

Example

```
&MyNode = &MyCollection.Next();
```

RemoteNode Collection Property

In this section, we discuss the Count property.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Count

Description

This property returns the number of Node objects in the RemoteNode Collection, as a number.

This property is read-only.

Example

```
&COUNT = &MY_COLLECTION.Count;
```

Portal Class

The portal class provides access to portals declared in the session.

A portal object is instantiated by the First, InsertItem, ItemByName, and Next Portal Collection methods

See Portal Collection.

Portal Class Method

In this section, we discuss the Portal class methods. The methods are discussed in alphabetical order.

Save

Syntax

Save()

Description

Use the Save method to save changes you made to the portal object.

Parameters

None.

Returns

A Boolean value: True if the portal object is successfully saved, False otherwise.

Portal Class Properties

In this section, we discuss the Portal class properties. The properties are discussed in alphabetical order.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

HostNodeName

Description

This property sets or returns the name of the node hosting the portal as a string.

This property is read-write.

IsLocal

Description

This property indicates whether the portal is defined as local or remote. This property returns a Boolean value: True, the portal is defined as local, False otherwise.

This property is read-only.

Name

Description

This property returns the name of this portal as a string. This name exactly matches the portal name of the portal registry defined in the database.

This property is read-only.

Portal Collection

The portal collection contains a set of references to each portal defined in the database.

A portal collection is instantiated by the Portals PortalRegistry property.

See Portals.

Portal Collection Methods

In this section, we discuss the Portal collection methods. The methods are discussed in alphabetical order.

First

Syntax

```
First()
```

Description

The First method returns the first Portal object in the Portal collection.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

None.

Returns

A Portal object.

Example

```
&MyPortal = &MyCollection.First();
```

ItemByName

Syntax

ItemByName(*PortalName*)

Description

The ItemByName method returns the Portal object with the name *PortalName*.

Parameters

PortalName	Specify the name of an existing portal within the collection. If you specify an invalid name, the object returns NULL.

Returns

A Portal object if successful, NULL otherwise.

Example

```
&MyPortal = &MyPortal.Portals.ItemByName("HRMS");
```

Next

Syntax

Next()

Description

The Next method returns the next Portal object in the Portal collection. You can use this method only after you have used the First method: otherwise the system doesn't know where to start.

Parameters

None.

Returns

A Portal object.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

```
&MyPortal = &MyCollection.Next();
```

Portal Collection Properties

In this section, we discuss the Count property.

Count

Description

This property returns the number of Portal objects in the Portal Collection, as a number.

This property is read-only.

Example

```
&COUNT = &MY_COLLECTION.Count;
```

NodeTemplate Class

The NodeTemplate class provides access to the default template assigned to a node in this portal.

A NodeTemplate object is instantiated by the First, InsertItem, ItemByName, and Next NodeTemplate Collection methods.

See NodeTemplate Collection.

NodeTemplate Class Properties

In this section, we discuss the NodeTemplate class properties. The properties are discussed in alphabetical order.

DefaultTemplate

Description

This property specifies the name of the template to be applied to the node.

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Name

Description

This property specifies the name of node that the template is to be applied to.

This property is read-write.

TemplateObject

Description

This property returns a reference to the template object associated with this node as a content reference.

This property is read-only.

Related Links

Content Reference Class

NodeTemplate Collection

The NodeTemplate collection contains a set of references to each node template object in a portal.

A NodeTemplate collection is instantiated by the NodeTemplates PortalRegistry property.

See NodeTemplates.

NodeTemplate Collection Methods

In this section, we discuss the NodeTemplate collection methods. The methods are discussed in alphabetical order.

DeleteItem

Syntax

`DeleteItem`(*`NodeName`*)

Description

The DeleteItem method deletes the NodeTemplate object identified by *NodeName* from the NodeTemplate Collection.

This method is not executed automatically. It is executed only when the PortalRegistry is saved.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

NodeName	Specify the name of a NodeTemplate to delete.

Returns

A Boolean value: True if the NodeTemplate was deleted, False otherwise.

Example

```
If Not &MyNodeTemplates.DeleteItem("HRMS") Then
   /* Do error processing */
End-if
```

First

Syntax

First()

Description

The First method returns the first NodeTemplate object in the NodeTemplate collection.

Parameters

None.

Returns

A NodeTemplate object.

Example

```
&MyNodeTemplate = &MyCollection.First();
```

InsertItem

Syntax

InsertItem(*NodeName*)

Description

The InsertItem method inserts the NodeTemplate object identified by *NodeName* into the NodeTemplate Collection.

This method is not executed automatically. It is executed only when the PortalRegistry is saved.

Parameters

NodeName	Specify the name of the node template to insert.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

A reference to the new NodeTemplate object if the method executed successfully, NULL otherwise.

Example

```
&NewNodeTemplate = &MyPortal.NodeTemplates.InsertItem("CRM");
```

ItemByName

Syntax

ItemByName(*NodeName*)

Description

The ItemByName method returns the NodeTemplate object with the name *NodeName*.

Parameters

NodeName	Specify the name of an existing NodeTemplate object in the collection. If you specify an invalid name, the object is NULL.

Returns

A NodeTemplate object if successful, NULL otherwise.

Example

```
&MyNodeTemplate = &MyPortal.NodeTemplates.ItemByName("HRMS");
```

Next

Syntax

Next()

Description

The Next method returns the next NodeTemplate object in the NodeTemplate collection. You can use this method only after you have used the First method: otherwise the system doesn't know where to start.

Parameters

None.

Returns

A NodeTemplate object.

Example

```
&MyNodeTemplate = &MyCollection.Next();
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

NodeTemplate Collection Properties

In this section, we discuss the Count property.

Count

Description

This property returns the number of NodeTemplate objects in the NodeTemplate Collection, as a number.

This property is read-only.

Example

```
&COUNT = &MY_COLLECTION.Count;
```

Folder Class

Folder objects are instantiated from other classes as follows:

- From a PortalRegistry object with the RootFolder property or the FindFolderByName method.
- From a Folder Collection with the First, ItemByName, or Next methods

See RootFolder, FindFolderByName, Folder Collection.

See Adding a Folder.

Folder Class Method

In this section, we discuss the Folder class methods. The methods are discussed in alphabetical order.

Save

Syntax

```
Save()
```

Description

The Save method saves any changes you made to the folder, for example, a changed description or ValidFrom date.

Using this method also saves any changes you made to PermissionValue (both role-based and non role-based) and AttributeValue objects associated with this folder. Security permissions added are cascade upward until the root folder or first public folder. Removed security permissions are removed from all the parent folders until root or public folder in folder hierarchy.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

None.

Returns

A Boolean value: True if the Folder object is successfully saved, False otherwise.

Example

```
If Not(&MyFolder.Save()) Then
   /* do error checking */
End-If;
```

Folder Class Properties

In this section, we discuss the Folder class properties. The properties are discussed in alphabetical order.

AbnContentProvider

Description

Use this property to set or return a string representing the node on which the SmartNavigation content resides.

This property is read-write.

Related Links

AbnDataSource
AbnPeopleCode
DefaultChartNavigation
TreeEffectiveDate
TreeName
TreeSetId
TreeStructureName
TreeUserKeyValue
"Defining SmartNavigation Folders" (PeopleTools 8.54: Portal Technology)

AbnDataSource

Description

Use this property to set or return a string indicating whether the SmartNavigation data source is a tree ("T") or a rowset ("R").

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

AbnContentProvider
AbnPeopleCode
DefaultChartNavigation
TreeEffectiveDate
TreeName
TreeSetId
TreeStructureName
TreeUserKeyValue
"Defining SmartNavigation Folders" (PeopleTools 8.54: Portal Technology)

AbnPeopleCode

Description

Use this property to set or return a string representing the path and PeopleCode object to execute when processing this SmartNavigation folder.

For example, if the PeopleCode program to execute is a method, then AbnPeopleCode property would be constructed from these elements:

```
APP_PACKAGE_NAME.Class_Path.Method
```

For example, if the PeopleCode program to execute is an iScript, then AbnPeopleCode property would be constructed from these elements:

```
RECORD_NAME.FIELD_NAME.PC_Event.Function
```

This property is read-write.

Related Links

AbnContentProvider
AbnDataSource
DefaultChartNavigation
TreeEffectiveDate
TreeName
TreeSetId
TreeStructureName
TreeUserKeyValue
"Defining SmartNavigation Folders" (PeopleTools 8.54: Portal Technology)

Attributes

Description

This property returns an Attribute Collection containing the AttributeValue objects for this folder.

This property is read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

Attribute Collection

Author

Description

This property returns the author (PeopleSoft user ID) for this folder as a string.

This property is read-only.

AuthorAccess

Description

This property specifies whether the author of the folder has access to the folder. This property takes a Boolean value. The default value for this property for a newly created object is True. This property is not cascaded.

This property is read-write.

Authorized

Description

This property specifies whether the user is authorized to view this Folder.

This property is used when you access a particular Folder using FindFolderByName. If you've specified a valid Folder with this method, a Folder is always returned, whether you are authorized to view it or not. This is the only property you can view from an object that you are not authorized to.

The initial value of this property depends on the other permission properties (PublicAccess and AuthorAccess) and the permission list values in the PermissionValue object associated with this folder.

This property is read-only.

Related Links

FindFolderByName

CascadedPermissions

Description

This property returns a PermissionValue Collection. This collection contains the value of the non role-based permissions for all the child and parent objects (up to the root folder). To determine only the permissions of the object use the Permission property instead. To determine the role-based permissions of the object use the CascadedRolePermissions property instead.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Note: You *cannot* add any PermissionValue objects to a collection returned by the CascadedPermissions property. You can add values only to the collection returned by the Permissions or RolePermissions property.

This property is read-only.

Related Links

CascadedRolePermissions, PermissionValue Collection, Permissions

CascadedRolePermissions

Description

This property returns a RolePermissionValue Collection. This collection contains the value of the role-based permissions for all the child and parent objects (up to the root folder). To determine only the role-based permissions of the object use the RolePermission property instead. To determine the non role-based permissions of the object use the CascadedPermissions property.

Note: You *cannot* add any PermissionValue objects to a collection returned by the CascadedRolePermissions property. You can add values only to the collection returned by the Permissions or RolePermissions property.

This property is read-only.

Related Links

CascadedPermissions RolePermissions RolePermissionValue Collection

ContentRefs

Description

This property returns the ContentReference Collection for this folder.

This property is read-only.

Related Links

Content Reference Collection

CreationDate

Description

This property returns the creation date for this folder as a string.

This property is read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

DefaultChartNavigation

Description

Use this property to set or return a Boolean value indicating whether the default PeopleTools chart navigation page (PT_ABN_ORGCHART) is to be used for this folder: True, use the default PeopleTools chart navigation page; False, use the folder specified by the value Folder Navigation Object Name field (from the Folder Administration page) as the navigation object.

This property is read-write.

Related Links

AbnContentProvider
AbnDataSource
AbnPeopleCode
TreeEffectiveDate
TreeName
TreeSetId
TreeStructureName
TreeUserKeyValue
"Defining SmartNavigation Folders" (PeopleTools 8.54: Portal Technology)

Description

Description

This property returns or sets the description for this folder as a string.

The length of this property is 256 characters. This property is translatable.

This property is read-write.

Folders

Description

This property returns a reference to the Folder Collection for this folder.

This property is read-only.

Related Links

Folder Collection

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

IsMobile

Description

Note: PeopleSoft Mobile Agent is a deprecated product. This mobile property currently exists for backward compatibility only.

This property returns True if the folder is used with mobile applications, False otherwise.

This property is read-write.

IsVisible

Description

This property returns True if the Hide from Portal Navigation check box is *not* selected when the folder is created. If the folder is hidden from portal navigation, this property returns False.

Considerations Using IsVisible

If you do not specifically set this property on a new or copied folder, the IsVisible property is set as follows:

- If the ValidFrom date is less then or equal to that day's date, the IsVisible property is set to True.
- If there is no ValidTo date the IsVisible property is set to True.
- If the ValidTo date is greater then or equal to that day's date, the IsVisible property is set to True.

This property is read-only.

Related Links

ValidFrom, ValidTo

Label

Description

This property returns or sets the label for this folder as a string.

The length of this property is 30 characters.

This property is translatable.

This property is read-write.

Name

Description

This property returns the name for this folder as a sting. The name is a unique identifier for each folder.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Every folder name must be unique across the portal, not just in the parent folder.

This property is *not* translatable. However, the values for the Label and Description properties are translatable.

This property is read-only.

Related Links

Description, Label

OwnerId

Description

This property returns the name of the owner for this folder as a string.

This property is read-write.

ParentName

Description

This property returns the parent folder name for this folder as a string. This property is valid only if the folder is contained within another folder. If the folder using this property is the root folder, this property returns an empty string.

This property is read-only.

Path

Description

The Path property returns a path to this folder, with each element of the path separated by a period. The path has the following syntax:

```
FolderLabel{Name}.[ChildFolderLabel{Name}.]. . .
```

This property is read-only.

Example

```
Departments{PORTA_ROOT_OBJECT}.HR{EastCoast}.AdministerWorkforce{Global}
```

Permissions

Description

This property returns a PermissionValue Collection. This collection contains the value of the non role-based permissions for this folder. To determine the permissions for all the parent objects (up to the root folder) use the CascadedPermissions property. To access the role-based permissions, use the RolePermissions property.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-only.

Related Links

PermissionValue Collection, CascadedPermissions, RolePermissionValue Collection

Product

Description

This property returns or sets the PeopleSoft product for this folder as a string.

The length of this property is 4 characters.

This property is read-write.

PublicAccess

Description

This property indicates whether a folder is generally accessible, that is, if this property is set to True, any user can access the folder. This property is not cascaded.

This property takes a Boolean value.

The default value for this property for a newly created object is False.

This property is read-write.

RolePermissions

Description

This property returns a RolePermissionValue Collection. This collection contains the value of the role-based permissions for this folder. To determine the role-based permissions for all the parent objects (up to the root folder) use the CascadedRolePermissions property. To access the non role-based permissions, use the Permissions property.

This property is read-only.

Related Links

CascadedRolePermissions Permissions RolePermissionValue Collection

SequenceNumber

Description

The sequence number is used when returning a collection. The default order of the returned folders is based on the sequence number. Use this property to reorder folders.

If there are duplicates in the sequence number, the folders are returned alphabetically.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The length of this property is 4 characters.

This property is read-write.

TreeEffectiveDate

Description

Use this property to set or return the effective date for the tree to be used as the SmartNavigation data source as a string.

Note: If the SmartNavigation data source is a rowset, this property is set to the Null string.

This property is read-write.

Related Links

AbnContentProvider
AbnDataSource
AbnPeopleCode
DefaultChartNavigation
TreeName
TreeSetId
TreeStructureName
TreeUserKeyValue
"Defining SmartNavigation Folders" (PeopleTools 8.54: Portal Technology)

TreeName

Description

Use this property to set or return the name for the tree to be used as the SmartNavigation data source as a string.

Note: If the SmartNavigation data source is a rowset, this property is set to the Null string.

SmartNavigation passes the values of several tree-specific fields to the application via URL.
Certain characters are inappropriate for use in a URL and must be avoided. When using a tree as a SmartNavigation data source, do not use any of the following characters in the tree name, setID, user key value, and tree branch values:

pound (#)	percent (%)	dollar ($)
ampersand (&)	plus (+)	comma (,)
forward slash/virgule (/)	colon (:)	semi-colon (;)
equals (=)	question mark (?)	at symbol (@)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

space ( )	quotation marks(")	less than symbol (<)
greater than symbol (>)	left curly brace ({)	right curly brace (})
vertical bar/pipe (|)	backslash (\)	caret (^)
tilde (~)	left square bracket ([)	right square bracket (])
grave accent (`)		

This property is read-write.

Related Links

AbnContentProvider
AbnDataSource
AbnPeopleCode
DefaultChartNavigation
TreeEffectiveDate
TreeSetId
TreeStructureName
TreeUserKeyValue
"Defining SmartNavigation Folders" (PeopleTools 8.54: Portal Technology)

TreeSetId

Description

Use this property to set or return the setID for the tree to be used as the SmartNavigation data source as a string.

Note: If the SmartNavigation data source is a rowset, this property is set to the Null string.

SmartNavigation passes the values of several tree-specific fields to the application via URL.
Certain characters are inappropriate for use in a URL and must be avoided. When using a tree as a SmartNavigation data source, do not use any of the following characters in the tree name, setID, user key value, and tree branch values:

pound (#)	percent (%)	dollar ($)
ampersand (&)	plus (+)	comma (,)
forward slash/virgule (/)	colon (:)	semi-colon (;)
equals (=)	question mark (?)	at symbol (@)
space ( )	quotation marks(")	less than symbol (<)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

greater than symbol (>)	left curly brace ({)	right curly brace (})
vertical bar/pipe (|)	backslash (\)	caret (^)
tilde (~)	left square bracket ([)	right square bracket (])
grave accent (`)		

This property is read-write.

Related Links

AbnContentProvider
AbnDataSource
AbnPeopleCode
DefaultChartNavigation
TreeEffectiveDate
TreeName
TreeStructureName
TreeUserKeyValue
"Defining SmartNavigation Folders" (PeopleTools 8.54: Portal Technology)

TreeStructureName

Description

Use this property to set or return the branch for the tree to be used as the SmartNavigation data source as a string.

Note: If the SmartNavigation data source is a rowset, this property is set to the Null string.

SmartNavigation passes the values of several tree-specific fields to the application via URL.
Certain characters are inappropriate for use in a URL and must be avoided. When using a tree as a SmartNavigation data source, do not use any of the following characters in the tree name, setID, user key value, and tree branch values:

pound (#)	percent (%)	dollar ($)
ampersand (&)	plus (+)	comma (,)
forward slash/virgule (/)	colon (:)	semi-colon (;)
equals (=)	question mark (?)	at symbol (@)
space ( )	quotation marks(")	less than symbol (<)
greater than symbol (>)	left curly brace ({)	right curly brace (})

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

vertical bar/pipe (|)	backslash (\)	caret (^)
tilde (~)	left square bracket ([)	right square bracket (])
grave accent (`)		

This property is read-write.

Related Links

AbnContentProvider
AbnDataSource
AbnPeopleCode
DefaultChartNavigation
TreeEffectiveDate
TreeName
TreeSetId
TreeUserKeyValue
"Defining SmartNavigation Folders" (PeopleTools 8.54: Portal Technology)

TreeUserKeyValue

Description

Use this property to set or return the user key value (also known as the set control value) for the tree to be used as the SmartNavigation data source as a string.

Note: If the SmartNavigation data source is a rowset, this property is set to the Null string.

SmartNavigation passes the values of several tree-specific fields to the application via URL.
Certain characters are inappropriate for use in a URL and must be avoided. When using a tree as a SmartNavigation data source, do not use any of the following characters in the tree name, setID, user key value, and tree branch values:

pound (#)	percent (%)	dollar ($)
ampersand (&)	plus (+)	comma (,)
forward slash/virgule (/)	colon (:)	semi-colon (;)
equals (=)	question mark (?)	at symbol (@)
space ( )	quotation marks(")	less than symbol (<)
greater than symbol (>)	left curly brace ({)	right curly brace (})
vertical bar/pipe (|)	backslash (\)	caret (^)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

tilde (~)	left square bracket ([)	right square bracket (])
grave accent (`)		

This property is read-write.

Related Links

AbnContentProvider
AbnDataSource
AbnPeopleCode
DefaultChartNavigation
TreeEffectiveDate
TreeName
TreeSetId
TreeStructureName
"Defining SmartNavigation Folders" (PeopleTools 8.54: Portal Technology)

ValidFrom

Description

This property returns or sets the date this folder is valid from as a string.

This property is read-write.

ValidTo

Description

This property returns or sets the date this folder is valid until as a string.

This property is read-write.

Note: The portal registry API never uses the ValidTo and ValidFrom fields to determine what to return in a collection. You must check for these values in your application.

Folder Collection

The Folder Collection provides access to a collection of folders in a Folder object.

The Folder Collection is instantiated from the Folders Folder Class property.

See Folders.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Folder Collection Methods

In this section, we discuss the Folder collection methods. The methods are discussed in alphabetical order.

DeleteItem

Syntax

DeleteItem(*FolderName*)

Description

The DeleteItem method deletes the folder object identified by *FolderName* from the database. If the folder contains other folders, all child folders and their contents are also deleted.

Warning! If you delete a folder, you delete *all* content in the folder. If you delete a folder that contains other folders, that is, a parent folder, all the child folders, and all the content references are deleted.

Note: The portal registry classes execute some methods "interactively", that is, as they happen. The item won't be marked for deletion, then actually deleted later. The item is deleted from the database *as soon as* the method is executed.

Parameters

FolderName	Specify the name of a folder existing in the folder collection.

Returns

A Boolean value: True if the folder was deleted, False otherwise.

Example

```
If Not &MyFolderColl.DeleteItem("MYFOLDER") Then
   /* Folder not deleted. Do error checking */
End-If;
```

First

Syntax

First()

Description

The First method returns the first Folder object in the folder collection.

Parameters

None.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

Folder object.

Example

```
&MyFolder = &MyCollection.First();
```

InsertItem

Syntax

InsertItem(*FolderName*, *Label*)

Description

The InsertItem method inserts the folder object identified by *FolderName* from the Folder Collection. You must specify both a name and a label for all folders. This method returns a reference to the new folder object. You must specify a unique *FolderName*, or you receive an error.

Note: The portal registry classes execute some methods "interactively", that is, as they happen. The item won't be marked for insertion, then actually inserted later. The item is inserted into the database *as soon as* the method is executed.

Parameters

FolderName	Specify the name of a folder existing in the folder collection. This parameter takes a string value.
Label	Specify a label for the new folder. This parameter takes a string value.

Returns

A reference to the new Folder object if the method executed successfully, null otherwise.

Example

```
&DeptHPFldr = &MyPortal.Folders.InsertItem("PORT0145", "HR Folder for Department 01⇒
45");
```

ItemByName

Syntax

ItemByName(*Name*)

Description

The ItemByName method returns the Folder object with the name *Name*.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

Name	Specify the name of an existing folder within the folder collection. If you specify an invalid name, the object is NULL. You must specify a name, not a label.

Returns

A folder object if successful, NULL otherwise.

Example

```
&DeptFldr = &MyPortal.RootFolder.Folders.ItemByName(&Dept_Name);
```

Next

Syntax

```
Next()
```

Description

The Next method returns the next Folder object in the Folder collection. You can use this method only after you have used the First method: otherwise the system doesn't know where to start.

Parameters

None.

Returns

A folder object.

Example

```
Local ApiObject &MySession, &Root, &Folders, &MyFolder;

&MySession = %Session;
&MyPortal = &MySession.GetPortalRegistry("ADMIN");

&Root = &MyPortal.GetRoot();
&Folders = &Root.Folders;

&MyFolder = &Folders.First();

For &I = 1 to &Folders.Count
   /* Do processing on folders */
   If &I <> &Folders.Count
      &MyFolder = &Folders.Next();
   End-If;
End-For;
```

Folder Collection Property

In this section, we discuss the Count property.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Count

Description

This property returns the number of Folder objects in the Folder Collection, as a number.

This property is read-only.

Example

```
&COUNT = &MY_COLLECTION.Count;
```

Content Reference Class

The content reference class provides access to some kind of content. The type of content depends on the content reference.

The content reference objects are instantiated from other classes:

- From a PortalRegistry object with the FindCRefByURL, FindCRefForURL, or FindCRefByName properties.
- From a Content Reference Collection (instantiated from a folder) with the First, ItemByName or Next methods

See FindCRefByURL, FindCRefByName, FindCRefForURL, Content Reference Collection.

See Adding a Content Reference.

Content Reference Class Methods

In this section, we discuss the Content Reference class methods. The methods are discussed in alphabetical order.

CreateLink

Syntax

CreateLink(*LinkName, Label*)

Description

Use the CreateLink method to create a link quickly to the same content reference executing the method. The link by defaults assumes the parent folder is the same as the content reference's parent.

A CReflink object is returned if there is no error.

After you create a link you must use the Save method to save it to the database.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

LinkName	Specify the name of the link as a string. This parameter takes 30 characters. This is considered as ID of the link. It cannot start with number, and can not have special characters and spaces.
Label	Specify the label of the link as a string. This parameter takes 30 characters.

Returns

A reference to a ContentReference link object.

Example

```
&CRef = &Portal.FindCRefByName("MyCRef");
&Link = &CRef.CreateLink("Link Object");
&Link.Save();
```

Related Links

Link Class

Save

Save

Syntax

```
Save()
```

Description

The Save method saves any changes you made to the content reference, for example, a changed description. It also performs some validation.

Using this method also saves any changes you made to PermissionValue or AttributeValue objects associated with this content reference.

Parameters

None.

Returns

A Boolean value: True if the content reference and its associated objects saved successfully, False otherwise.

Example

```
If NOT(&MyCRef.Save()) Then
   /* save failed, do error processing */
End-If;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Content Reference Class Properties

In this section, we discuss the Content Reference class properties. The properties are discussed in alphabetical order.

AbsoluteContentURL

Description

This property returns the absolute content URL, that is, the content from the content servlet (psc).

This property is read-only.

Example

The following is an example absolute content URL:

```
http://serverx/psc/PS84/EMPLOYEEPORTAL/CRM/c/SFA.CUSTOMERINFO.GBL?page=CUST_DATA1&&⇒
Action=U&emplid=00001
```

AbsolutePortalURL

Description

This property returns the absolute content reference portal URL.

This property is read-only.

Example

```
http://serverx/psp/PS84/EMPLOYEEPORTAL/CRM/c/SFA.CUSTOMERINFO.GBL?page=CUST_DATA1&&⇒
Action=U&emplid=00001
```

AssignedPagelets

Description

This property returns an AssignedPagelet collection.

This property is read-only.

Related Links

AssignedPagelet Collection

Attributes

Description

This property returns an Attribute Collection containing the AttributeValues for this content reference object.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-only.

Related Links

Attribute Collection

Author

Description

This property returns the author (PeopleSoft user ID) for this content reference object as a string.

This property is read-only.

AuthorAccess

Description

This property specifies whether the author of the content reference has access to the content reference. This property takes a Boolean value. The default value for this property is True.

This property is read-write.

Authorized

Description

This property specifies whether the user is authorized to view this content reference.

This property is used when you access a particular content reference using FindCRefByURL, FindCRefForURL, or FindCRefByName. If you specified a valid content reference with either of these methods, a content reference is always returned, whether you are authorized to view it or not. This is the only property you can view from an object for which you are not authorized.

The initial value of this property depends on the other permission properties (PublicAccess and AuthorAccess) and the permission list values in the PermissionValue object associated with this content reference.

This property is read-only.

Related Links

FindCRefByURL, FindCRefForURL, FindCRefByName

CascadedPermissions

Description

This property returns a PermissionValue Collection. This collection contains the value of the non role-based permissions for all the parent objects (up to the root folder). To determine only the permissions

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

of the object use the Permissions property instead. To access the role-based permissions, use the CascadedRolePermissions property.

Note: You *cannot* add any PermissionValue objects to a collection returned by the CascadedPermissions property. You can add values only to the collection returned by the Permissions property.

This property is read-only.

Related Links

CascadedRolePermissions, PermissionValue Collection, Permissions

CascadedRolePermissions

Description

This property returns a RolePermissionValue Collection. This collection contains the value of the role-based permissions for all the parent objects (up to the root folder). To determine only the permissions of the object use the RolePermissions property instead. To determine non role-based permissions, use the CascadedPermissions property.

Note: You *cannot* add any RolePermissionValue objects to a collection returned by the CascadedRolePermissions property. You can add values only to the collection returned by the RolePermissions property.

This property is read-only.

Related Links

CascadedRolePermissions RolePermissions RolePermissionValue Collection

ContentProvider

Description

This property returns or sets the name of the node for the content reference as a string.

This property takes the following values:

Value	*Description*
Node name	Specify the exact name of the node.
LOCAL_NODE	Specify the node for the content reference as the node defined as the local node.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

CreationDate

Description

This property returns the creation date for this content reference object as a string.

This property is read-only.

Data

Description

This property returns the data for this content reference. This property is valid only when the StorageType property is LOCL.

The length of this property depends on your system database limit for LONG fields.

This property is read-write.

Example

```
&MyData = &MyCRef.Data;
```

Related Links

StorageType

Description

Description

This property returns or sets the description for this content reference object as a string.

The length of this property is 256 characters.

This property is translatable.

This property is read-write.

HtmlText

Description

This property returns the HTML text associated with this content reference as a string.

This property is read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

IsMobile

Description

Note: PeopleSoft Mobile Agent is a deprecated product. This mobile property currently exists for backward compatibility only.

This property returns True if this content reference is used with mobile applications, False otherwise.

This property is read-write.

IsVisible

Description

This property returns True if the Hide from Portal Navigation check box is not selected when the content reference is created. If the content reference is hidden from portal navigation, this property returns False.

Considerations Using IsVisible

If you do not specifically set this property on a new or copied content reference object, the IsVisible property is set as follows:

- If the ValidFrom date is less then or equal to that day's date, the IsVisible property is set to True.
- If there is no ValidTo date the IsVisible property is set to True.
- If the ValidTo date is greater then or equal to that day's date, the IsVisible property is set to True.

This property is read-only.

Related Links

ValidFrom, ValidTo

Label

Description

This property returns or sets the label for this content reference object as a string.

The length of this property is 30 characters.

This property is translatable.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Links

Description

This property returns a reference to a Link collection. This collection contains all the links that are associated with this content reference.

This property is read-only. However, a link collection is updated in realtime when a new link is created on the object.

Related Links

Link Collection

Name

Description

This property returns the name for this content reference object as a string. The name is a unique identifier for each content reference object.

Every content reference name must be unique in the portal, not just in the parent folder.

This property is read-only.

OwnerId

Description

This property returns or sets the owner ID of the content reference object as a string.

This property is read-write.

ParentName

Description

This property returns the parent folder name for this content reference object as a string.

This property is read-only.

Example

The following example uses the ParentName to return a folder object for the content reference.

```
&Folder = &Portal.FindFolderByName(&CRef.ParentName);
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Path

Description

The Path property returns a path to this content reference, with each element of the path separated by a period. The path has the following syntax:

```
ContentReferenceLabel{Name}.[ChildContentReferenceLabel{Name}.]. . .
```

This property is read-only.

Permissions

Description

This property returns a PermissionValue Collection. This collection contains the value of the non role-based permissions for this content reference. To determine the permissions for all the parent objects (up to the root folder) use the CascadedPermissions property.

If you want to find role-based permissions for the content reference, use the RolePermission property.

This property is read-only.

Related Links

PermissionValue Collection, CascadedPermissions, CascadedPermissions

Product

Description

This property returns or sets the PeopleSoft product for this content reference object as a string.

The length of this property is 4 characters.

This property is read-write.

PublicAccess

Description

This property indicates whether a content reference is generally accessible, that is, if it will always be included in the general content reference collection. This property takes a Boolean value.

The default value for this property is False.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

QualifiedURL

Description

Note: This property is being kept for backward compatibility only. If your code uses this property, the value returned is actually from the AbsoluteContentURL property. New applications should use the AbsoluteContentURL property instead.

Related Links

AbsoluteContentURL

RelativeURL

Description

This property returns the relative URL in the following format:

```
../../../Portal/Node/Content_Type/ContentID
```

For example, from the following URL:

```
http://mlee2038/servlets/psp/PS84/e_procurement/fdm/c/E_PRO.CheckOut.GBL?page=view&⇒
Setid=110&Custid=99
```

The RelativeURL returns the following:

```
e_procurement/fdm/c/E_PRO.CheckOut.GBL?page=view&Setid=110&Custid=99
```

This property is read-only.

RolePermissions

Description

This property returns a RolePermissionValue Collection. This collection contains the value of the role-based permissions for this content reference. To determine the permissions for all the parent objects (up to the root folder) use the CascadedRolePermissions property.

If you want to find non role-based permissions for the content reference, use the Permission property.

This property is read-only.

Related Links

CascadedRolePermissions Permissions RolePermissionValue Collection

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SequenceNumber

Description

The sequence number is used when returning a collection. The default order of the returned content references is based on the sequence number. Use this property to reorder content references. This property takes a number value.

If there are duplicates in the sequence number, the content references are returned alphabetically.

The length of this property is 4 characters.

This property is read-write.

StorageType

Description

In general, content references contain information about where to get the content, and do not store the content. However, content references that are template or portal component types can have their content accessible directly from the content reference. In these cases, the Data property is valid and can be read or written, and the data is stored locally in the portal database.

StorageType	***Meaning***
LOCL	Local: Data property on content reference is valid.
RMTE	Remote: Data property is not valid.

When UsageType is a target this property must be set to RMTE and the URLType property should specify what format the Node and URL are in.

When UsageType is either a template or a portal component this property can be set to either LOCL or RMTE.

Note that when StorageType is LOCL, it specifies a static template or portal component. But, when StorageType is RMTE it can specify either:

- a dynamically generated template or portal component
- a static template or portal component

In both cases, the Node and URL properties specifies how to get the template or portal component.

Only templates and homepage tab content references can have StorageType LOCL. The StorageType is always LOCL for homepage tabs. For templates LOCL means that corresponding URL is stored in database, not retrieved by URL.

The following table indicates the usage type, and what type of storage is available.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

UsageType	*RMTE*	*LOCL*
FRMT (Frame template)	X	X
HTMT (HTML template)	X	X
HPGT (Homepage tab)		X
HPGC (Pagelet)	X	
TARG (Target)	X	

RMTE is the default value for a new content reference.

The length of this property is 4 characters.

This property is read-write.

Related Links

Data

Template

Description

This property returns or sets the name of the template used with this content reference as a string. You must specify the name of an existing template.

This property uses the name *not* the label of a content reference.

This property is used only when the UsageType property is specified as Target (TARG) and the TemplateType property is specified as HTML.

To return a reference to the content reference that contains the template specified by this property, use the TemplateObject property.

The length of this property is 30 characters.

This property is read-write.

Related Links

UsageType, TemplateType, TemplateObject

TemplateObject

Description

This property returns a reference to a content reference object that contains the template specified by the Template property as a content reference. If no template is specified with Template, this property returns NULL.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-only.

Related Links

Template

TemplateType

Description

This property indicates whether a template should be used to wrap the content. This property takes a string value.

Values are:

Value	*Description*
HTML	An HTML template should wrap the data (URL) in the content reference.
NONE	No template should be used. The text should not be wrapped.

HTML is the default value on a new content reference.

Use the NONE value if the URL should not appear in the portal. An example is when the content reference is a template itself.

If the homepage template for the user is un-retrievable, the system tries to use the default user's template first, before resorting to the portal default template.

When the content reference describes content, this property should be set to HTML.

This property is read-write.

Related Links

Using Content References

URL

Description

This property returns or sets the URL for this content reference object as a string. The URL returns *exactly*as it appears in the database.

If you're setting a URL, you must use a unique URL.

The absolute URL, that is, the URL from the node concatenated with this URL must be unique.

You receive an error if the URL your use is already registered.

To retrieve a qualified URL, that is, one that contains the node URI, use the AbsoluteContentURL property.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The length of this property depends on your system database limit for LONG fields.

This property is read-write.

The format of the value for this property depends on the setting of other properties.

Related Links

AbsoluteContentURL, Using Content References

URLType

Description

This property indicates what kind of URL is used to retreive the content. This property takes a string value.

Note: This property is used only for content that has the StorageType property set as Remote.

Values are:

URLType Value	*Meaning*
UEXT	URL points to a non-PeopleSoft (external) URL
UMPG	URL points to a PeopleSoft mobile page
UPGE	URL points to a component.
UPHP	URL points to a homepage tab
UPTM	URL points to a template
USCR	URL points to an iScript
UGEN	URL points to a generic PeopleSoft URL
WRKL	URL points to a Worklist URL

UPGE is the default value on a new content reference.

This property is read-write.

Related Links

StorageType

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

UsageType

Description

This property indicates what the content reference is used for. Several other properties depend on this property.

This property takes a string value.

The length of this property is 4 characters.

Value	*Description*
FRMT	Frame template: the content reference is a frame-based template.
HTMT	HTML template: the content reference is an HTML template.
HPGT	Homepage tab: the content reference is a homepage tab.
HPGC	Pagelet: the content reference is a pagelet used in the homepage.
TARG	Target: the content reference is the target content its template determines what else must be loaded and how it will look.
LINK	Link: the content reference is a link.

TARG is the default value on a new content reference.

This property is read-write.

Related Links

Using Content References

ValidFrom

Description

This property returns or sets the date this content reference is valid from as a string.

This property is read-write.

ValidTo

Description

This property returns or sets the date this content reference is valid until as a string.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Note: The portal registry API never uses the ValidTo and ValidFrom fields to determine what to return in a collection. You must check for these values in your application.

Content Reference Collection

The Content Reference Collection provides access to the collection of content references in a Folder object.

The Content Reference Collection is instantiated from the ContentRefs Folder property.

See ContentRefs.

Content Reference Collection Methods

In this section, we discuss the Content Reference collection methods. The methods are discussed in alphabetical order.

DeleteItem

Syntax

DeleteItem(*ContentReferenceName*)

Description

The DeleteItem method deletes the content reference object identified by *ContentReferenceName* from the content reference Collection.

If you delete a template for a content reference, and none of the other content references on a page have a template, the default template specified with the ContentProvider is used. If there's no template for the ContentProvider, the template for the PortalRegistry is used. However, if you delete the template for the content reference, the ContentProvider, and the PortalRegistry, you receive a runtime error.

Note: The portal registry classes execute some methods "interactively", that is, as they happen. The item won't be marked for deletion, then actually deleted later. The item is deleted from the database *as soon as* the method is executed.

Parameters

ContentReferenceName	Specify the name of a content reference existing in the content reference collection.

Returns

A Boolean value: True if the content reference was deleted, False otherwise.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

```
If Not &MyCRef.DeleteItem("Test_CRef") Then
   /* can't delete test data. Do error processing */
End-if;
```

First

Syntax

```
First()
```

Description

The First method returns the first content reference object in the content reference collection.

Parameters

None.

Returns

A content reference object.

Example

```
&MyCRef = &MyCollection.First();
```

InsertItem

Syntax

```
InsertItem(ContentReferenceName, ContentReferenceLabel, Node, URL)
```

Description

The InsertItem method inserts the content reference object identified by *ContentReferenceName* into the content reference Collection.

Note: The portal registry classes execute some methods "interactively", that is, as they happen. The item won't be marked for insertion, then actually inserted later. The item is inserted into the database as soon as the method is executed.

Parameters

ContentReferenceName	Specify the name of a new content reference. This parameter takes a string value. If you specify a name that already exists in the collection, you get an error.
ContentReferenceLabel	Specify a description of the new content reference. This is the translated value. This parameter takes a string value.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Node Specify a node. This parameter takes a string value. If you specify a fully qualified value for *URL*, you can specify a NULL (that is, two quotation marks with no space between them ("")).

URL Specify a URL that contains the content. The format of this parameter depends on other properties, such as the type of content reference, where the data is stored, and so on.

Returns

A reference to the new content reference object if the method executed successfully, NULL otherwise.

Example

The following example inserts an external content reference that is a template:

```
&URL = "t/" | &ITEMNAME;
&MyCRef = &CRefColl.InsertItem(&ITEMNAME, &ITEMLABEL, "", &URL);
```

The following example inserts a content reference where URLType is iScript (USCR):

```
&URL = "s/WEBLIB_PORTAL.FieldFormula.Portal_Trans_Dyn"

&MyCRef = &CRefColl.InsertItem(&ITEMNAME, &ITEMLABEL, "HRMS", &URL);
```

Related Links

Using Content References

ItemByName

Syntax

ItemByName(*Name*)

Description

The ItemByName method returns the content reference object with the name *Name*.

Parameters

Name Specify the name of an existing content reference within the content reference collection. If you specify an invalid name, the object is NULL.

Returns

A content reference object if successful, NULL otherwise.

Example

```
&MyCRef = &CRefColl.ItemByName("PORTAL_ADMIN);
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Next

Syntax

```
Next()
```

Description

The Next method returns the next content reference object in the content reference collection. You can use this method only after you have used the First method: otherwise the system doesn't know where to start.

Parameters

None.

Returns

content reference object.

Example

```
&MyCRef = &MyCollection.Next();
```

Content Reference Collection Property

In this section, we discuss the Count property.

Count

Description

This property returns the number of content reference objects in the content reference Collection, as a number.

This property is read-only.

Example

```
&COUNT = &MY_COLLECTION.Count;
```

AttributeValue Class

The AttributeValue class provides access to attributes associated with either folders or content references.

AttributeValue objects are instantiated from an Attribute Collection Methods with the First, InsertItem, ItemByName, or Next methods.

See Attribute Collection Methods.

See Using Attributes.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

AttributeValue Class Properties

In this section, we discuss the AttributeValue class properties. The properties are discussed in alphabetical order.

Label

Description

This property returns the label of the AttributeValue as a string. This property works with the Translatable property. If Translatable is set to True, the value of Label can be translated.

The length of this property is 30 characters.

This property is read-write.

Related Links

Translatable

Name

Description

This property returns the name of the AttributeValue as a string.

The length of this property is 30 characters.

This property is read-only.

Example

```
&AttrColl = &Folder.Attributes;
&Attr = &AttrColl.First();

   &Scroll = GetLevel0().GetRow(1).GetRowset(Scroll.PORTAL_FLDR_ATR);

   &I = 1;
   While All(&Attr)
      &Record = &Scroll.GetRow(&I).GetRecord(Record.PORTAL_FLDR_ATR);
      &Record.PORTAL_ATTR_NAM.Value = &Attr.Name;
      &Record.PORTAL_ATTR_VAL.Value = &Attr.Value;
      &Attr = &AttrColl.Next();
      /* need this check so we don't insert extra blank row */
      If All(&Attr) Then
         &Scroll.InsertRow(&I);
         &I = &I + 1;
      End-If;
End-While;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Translatable

Description

This property specifies if the AttributeValue is translatable. This property takes a Boolean value: True if the AttributeValue can be translated, False otherwise.

If this property is set to True, the value of the Label property can be translated.

Note: Regardless of the order in which attributes were entered, they are ordered according to their translatable property, that is, attributes that have this property set as True come first, followed by attributes that have this property set as False.

This property is read-write.

Related Links

Label

Value

Description

This property returns the value of the AttributeValue as a string.

The length of this property depends on your system database limit for LONG fields.

This property is read-write.

Example

To specify more than a single value for an AttributeValue, you can specify several values separated by a semicolon. For example:

```
&MyAtt.value = "401k;benefits;dependants;HR";
```

Attribute Collection

The Attribute Collection provides access to the collection of Attribute in a Folder or a content reference object.

An Attribute Collection is instantiated from other classes as follows:

- From a content reference object with the Attributes property.

  See Attributes.

- From a Folder object with the Attributes property.

  See Attributes.

- From a PageletCategory object with the Attributes property.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

See Attributes.

- From a Pagelet object with the Attributes property.

  See Attributes.

Attribute Collection Methods

In this section, we discuss the Attribute collection methods. The methods are discussed in alphabetical order.

DeleteItem

Syntax

DeleteItem(*AttributeValueName*)

Description

The DeleteItem method deletes the AttributeValue object identified by *AttributeValueName* from the Attribute Collection.

This method is not executed automatically. It is executed only when the parent object is saved.

Parameters

AttributeValueName	Specify the name of an AttributeValue existing in the Attribute Collection.

Returns

A Boolean value: True if the AttributeValue was deleted, False otherwise.

First

Syntax

First()

Description

The First method returns the first AttributeValue object in the Attribute Collection.

Parameters

None.

Returns

An AttributeValue object.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

```
&MyAttributeValue = &MyCollection.First();
```

InsertItem

Syntax

InsertItem(*AttributeValueName*)

Description

The InsertItem method inserts the AttributeValue object identified by *AttributeValueName* from the Attribute Collection.

This method is not executed automatically. It is executed only when the parent object is saved.

Parameters

AttributeValueName	Specify the name of an AttributeValue existing in the Attribute Collection.

Returns

A reference to the new AttributeValue object if the method executed successfully, NULL otherwise.

Example

```
For &I = 1 To &Rowset.ActiveRowCount
    If &CompName = "PORTAL_CREF_ADM" Then
       &Record = &Rowset.GetRow(&I).GetRecord(Record.PORTAL_CATR_DV);
    Else
       &Record = &Rowset.GetRow(&I).GetRecord(Record.PORTAL_FATR_DV);
    End-If;

    If &Record.PORTAL_ATTR_NAM.Value <> "" Then
       &Attr = &AttrColl.InsertItem(&Record.PORTAL_ATTR_NAM.Value);
       &Attr.Value = &Record.PORTAL_ATTR_VAL.Value;
    End-If;
End-For;
```

ItemByName

Syntax

ItemByName(*Name*)

Description

The ItemByName method returns the AttributeValue object with the name *Name*.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

Name	Specify the name of an existing AttributeValue within the Attribute Collection. If you specify an invalid name, the object is NULL.

Returns

An AttributeValue object if successful, NULL otherwise.

Example

```
&Attr = &AttrColl.ItembyName("RELLINK");
```

Next

Syntax

```
Next()
```

Description

The Next method returns the next AttributeValue object in the Attribute Collection. You can use this method only after you have used the First method: otherwise the system doesn't know where to start.

Parameters

None.

Returns

AttributeValue object.

Example

```
&MyAttributeValue = &MyCollection.Next();
```

Attribute Collection Property

In this section, we discuss the Count property.

Count

Description

This property returns the number of AttributeValue objects in the Attribute Collection, as a number.

This property is read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

```
&COUNT = &MY_COLLECTION.Count;
```

PermissionValue Class

The PermissionValue provides access to permission lists associated with folders, content references, PageletCategory objects, or Pagelets.

Note: You *cannot* add any PermissionValue objects to a collection returned by the CascadedPermissions or CascadedRolePermissions property. You can add values only to the collection returned by the Permissions or RolePermissions property.

PermissionValue objects are instantiated from the following:

- A PermissionValue Collection with the First, InsertItem, ItemByName, or Next methods.
- A RolePermissionValue Collection with the First, InsertItem, ItemByName, or Next methods.

See PermissionValue Collection.

See Using Security.

See Setting Permissions Using the PermissionValue Object.

PermissionValue Class Properties

In this section we discuss the Cascade and Name properties.

Cascade

Description

This property indicates whether the current permission should be granted to all child folders.

This property is valid only with folders, not with content references.

This property takes a Boolean value. The default value for a new PermissionValue object is False.

This property is read-write.

Name

Description

Specify the name of a permission list as the name of this object. You must specify a permission list that has already been created. This property takes a string value.

The length of this property is 30 characters.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-write.

PermType

Description

Specify the type of the permission. Values are:

Value	*Description*
P	Specify a non role-based permission.
R	Specify a role-based permission.

This property is read-write.

Related Links

RolePermissionValue Collection
PermissionValue Collection

PermissionValue Collection

A PermissionValue collection is returned by the following:

- CascadedPermissions and Permissions folder property
- CascadedPermissions and Permissions content reference property
- CascadedPermissions and Permissions PageletCategory object property
- CascadedPermissions and Permissions Pagelet property

What is contained in the PermissionValue collection depends on the property that created it.

See CascadedPermissions, Permissions.

See CascadedPermissions, Permissions.

See CascadedPermissions, Permissions.

See CascadedPermissions, Permissions.

See Using Security.

PermissionValue Collection Methods

In this section, we discuss the PermissionValue collection methods. The methods are discussed in alphabetical order.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

DeleteItem

Syntax

DeleteItem(*PermissionValueName*)

Description

The DeleteItem method deletes the PermissionValue object identified by *PermissionValueName* from the PermissionValue Collection.

This method is not executed automatically. It is executed only when the parent object is saved.

Parameters

PermissionValueName	Specify the name of a PermissionValue existing in the PermissionValue collection.

Returns

A Boolean value: True if the PermissionValue was deleted, False otherwise.

Example

```
If Not &MyPValColl.DeleteItem("ALLPNLS") Then
   /* do error processing */
End-If;
```

First

Syntax

First()

Description

The First method returns the first PermissionValue object in the PermissionValue collection.

Parameters

None.

Returns

A PermissionValue object.

Example

```
&MyPermissionValue = &MyCollection.First();
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

InsertItem

Syntax

InsertItem(*PermissionValueName*)

Description

The InsertItem method inserts the PermissionValue object identified by *PermissionValueName* into the PermissionValue Collection.

This method is not executed automatically. It is executed only when the parent object is saved.

Note: You *cannot* add any PermissionValue objects to a collection returned by the CascadedPermissions property. You can only add values to the collection returned by the Permissions property.

Parameters

PermissionValueName Specify the name of an existing permission list.

Returns

A reference to the new PermissionValue object if the method executed successfully, NULL otherwise.

Example

```
&MyPermV = &MyPermVColl.InsertItem("ALLPNLS");

If Not &MyPermV Then
   /* do error processing */
End-If;
```

ItemByName

Syntax

ItemByName(*Name*)

Description

The ItemByName method returns the PermissionValue object with the name *Name*.

Parameters

Name Specify the name of an existing PermissionValue within the PermissionValue collection. If you specify an invalid name, the object is NULL.

Returns

A PermissionValue object if successful, NULL otherwise.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

```
&MyPVal = &MyPValColl.ItemByName("CUSTOMER");
```

Next

Syntax

```
Next()
```

Description

The Next method returns the next PermissionValue object in the PermissionValue collection. You can use this method only after you have used the First method: otherwise the system doesn't know where to start.

Parameters

None.

Returns

PermissionValue object.

Example

```
&MyPermissionValue = &MyCollection.Next();
```

PermissionValue Collection Property

In this section, we discuss the Count property.

Count

Description

This property returns the number of PermissionValue objects in the PermissionValue Collection, as a number.

This property is read-only.

Example

```
&COUNT = &MY_COLLECTION.Count;
```

RolePermissionValue Collection

A RolePermissionValue collection is returned by the following:

- CascadedRolePermissions and RolePermissions folder property

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

See CascadedRolePermissions.

See RolePermissions.

- CascadedRolePermissions and RolePermissions content reference property

  See CascadedRolePermissions.

  See RolePermissions.

- CascadedRolePermissions and RolePermissions content reference link property

  See CascadedRolePermissions.

  See RolePermissions.

What is contained in the RolePermissionValue collection depends on the property that created it.

RolePermissionValue Collection Methods

In this section, we discuss the RolePermissionValue collection methods. The methods are discussed in alphabetical order.

DeleteItem

Syntax

DeleteItem(*RolePermissionValueName*)

Description

The DeleteItem method deletes the RolePermissionValue object identified by *RolePermissionValueName* from the RolePermissionValue Collection.

This method is not executed automatically. It is executed only when the parent object is saved.

Parameters

RolePermissionValueName	Specify the name of a RolePermissionValue existing in the RolePermissionValue collection.

Returns

A Boolean value: True if the RolePermissionValue was deleted, False otherwise.

Example

```
If Not &MyPValColl.DeleteItem("ALLPNLS") Then
   /* do error processing */
End-If;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

First

Syntax

First()

Description

The First method returns the first RolePermissionValue object in the RolePermissionValue collection.

Parameters

None.

Returns

A RolePermissionValue object.

Example

```
&MyRolePermissionValue = &MyCollection.First();
```

InsertItem

Syntax

InsertItem(*RolePermissionValueName*)

Description

The InsertItem method inserts the RolePermissionValue object identified by *RolePermissionValueName* into the RolePermissionValue Collection.

This method is not executed automatically. It is executed only when the parent object is saved.

Note: You *cannot* add any RolePermissionValue objects to a collection returned by the CascadedRolePermissions property. You can only add values to the collection returned by the RolePermissions property.

Parameters

RolePermissionValueName Specify the name of an existing role permission list.

Returns

A reference to the new RolePermissionValue object if the method executed successfully, NULL otherwise.

Example

```
&MyPermV = &MyPermVColl.InsertItem("ALLPNLS");

If Not &MyPermV Then
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
   /* do error processing */
End-If;
```

ItemByName

Syntax

ItemByName(*Name*)

Description

The ItemByName method returns the RolePermissionValue object with the name *Name*.

Parameters

Name Specify the name of an existing RolePermissionValue within the RolePermissionValue collection. If you specify an invalid name, the object is NULL.

Returns

A RolePermissionValue object if successful, NULL otherwise.

Example

```
&MyPVal = &MyPValColl.ItemByName("CUSTOMER");
```

Next

Syntax

Next()

Description

The Next method returns the next RolePermissionValue object in the RolePermissionValue collection. You can use this method only after you have used the First method: otherwise the system doesn't know where to start.

Parameters

None.

Returns

RolePermissionValue object.

Example

```
&MyRolePermissionValue = &MyCollection.Next();
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

RolePermissionValue Collection Property

In this section, we discuss the Count property.

Count

Description

This property returns the number of RolePermissionValue objects in the RolePermissionValue Collection, as a number.

This property is read-only.

Example

```
&COUNT = &MY_COLLECTION.Count;
```

ContentReference Links

A content reference link is a ContentReference object that delegates most of its properties to another content reference. It has its own separate properties, as well as a reference to the linked cref.

A content reference link is instantiated from the following:

- CreateLink content reference method
- CreateContentRefLink PortalRegistry method

Note: The CreateLink method creates a new link. To instantiate an existing link use the FindLinkByName method.

Related Links

CreateContentRefLink
FindCRefLinkByName
CreateLink

ContentReference Links Methods

In this section, we discuss the ContentReference link methods. The methods are discussed in alphabetical order.

Delete

Syntax

```
Delete()
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the delete method to delete the link from the database.

Note: The portal registry classes execute some methods "interactively", that is, as they happen. The link is not marked for deletion, then actually deleted later. The link is deleted from the database as soon as the method is executed.

Parameters

None.

Returns

A Boolean value: True if the content reference link and its associated objects are deleted successfully, False otherwise.

Save

Syntax

Save()

Description

The Save method saves any changes you made to the content reference link, for example, a changed description or ValidFrom date.

After you create a link using either the CreateLink or CreateContentRefLink methods you must use the Save method to save the link to the database.

Using this method also saves any changes you made to PermissionValue or AttributeValue objects associated with this content reference link.

Parameters

None.

Returns

A Boolean value: True if the content reference link and its associated objects saved successfully, False otherwise. If False is returned, a message is also written to the PSMessage collection.

Example

```
If NOT(&MyCRefLink.Save()) Then
   /* save failed, do error processing */
End-If;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ContentReference Links Properties

In this section, we discuss the ContentReference link properties. The properties are discussed in alphabetical order.

AbsoluteContentURL

Description

This property returns the absolute content URL, that is, the content from the content servlet (psc). The content is displayed without any portal template.

This property is read-only.

Example

The following is an example absolute content URL:

```
http://serverx/psc/PS84/EMPLOYEEPORTAL/CRM/c/SFA.CUSTOMERINFO.GBL?page=CUST_DATA1&&⇒
Action=U&emplid=00001
```

AbsolutePortalURL

Description

This property returns the absolute content reference link portal URL. This URL also contains the content in the portal template.

This property is read-only.

Example

```
http://serverx/psp/PS84/EMPLOYEEPORTAL/CRM/c/SFA.CUSTOMERINFO.GBL?page=CUST_DATA1&&⇒
Action=U&emplid=00001
```

Attributes

Description

This property returns an Attribute Collection containing the AttributeValues for this content reference link object.

This property is read-write.

Related Links

Attribute Collection

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Author

Description

This property returns the author (PeopleSoft user ID) for this content reference link as a string.

This property is read-only.

AuthorAccess

Description

This property specifies whether the author of the content reference link has access to the content reference link. This property takes a Boolean value. The default value for this property is true.

This property is read-write.

Authorized

Description

This property specifies whether the user is authorized to view this content reference link.

This property is used when you access a particular content reference link using FindCRefLinkByURL. If you specified a valid content reference link, a content reference link is always returned, whether you are authorized to view it or not. This is the only property you can view from an object that you are not authorized tom and the content reference is empty.

The initial value of this property depends on the other permission properties (PublicAccess and AuthorAccess) and the permission list values in the PermissionValue object associated with this content reference link.

This property is read-only.

Related Links

FindCRefLinkByName

CascadedPermissions

Description

This property returns a PermissionValue Collection. This collection contains the value of the permissions for all the parent objects (up to the root folder). To determine only the permissions of the object use the Permissions property instead.

Note: You cannot add any PermissionValue objects to a collection returned by the CascadedPermissions property. You can add values only to the collection returned by the Permissions property.

This property is read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

PermissionValue Collection, Permissions

CascadedRolePermissions

Description

This property returns a RolePermissionValue Collection. This collection contains the value of the role-based permissions for all the parent objects (up to the root folder). To determine only the permissions of the object use the RolePermissions property instead. To determine the non role-based permissions of the object use the Permissions property instead.

Note: You cannot add any PermissionValue objects to a collection returned by the CascadedRolePermissions property. You can add values only to the collection returned by the RolePermissions property.

This property is read-only.

Related Links

CascadedRolePermissions RolePermissions RolePermissionValue Collection

ContentProvider

Description

This property returns the name of the node for the content reference link as a string.

This property is read-only.

CreationDate

Description

This property returns the creation date for this content reference link object as a string.

This property is read-only.

Data

Description

This property returns the data for this content reference link. This property is valid only when the StorageType property is LOCL.

The length of this property depends on your system database limit for LONG fields.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

```
&MyData = &MyCReflink.Data;
```

Related Links

StorageType

Description

Description

This property returns or sets the description for this content reference link object as a string.

The length of this property is 256 characters.

This property is translatable.

This property is read-write.

IsMobile

Description

Note: PeopleSoft Mobile Agent is a deprecated product. This mobile property currently exists for backward compatibility only.

This property returns True if this content reference link is used with mobile applications, False otherwise.

This property is read-write.

IsVisible

Description

This property returns True if the Hide from Portal Navigation check box is not selected when the content reference link is created. If the content reference link is hidden from portal navigation, this property returns False. Also, if the date associated with the link is not valid (is not within the valid to and valid from dates,) this property returns False.

Considerations Using IsVisible

If you do not specifically set this property on a new or copied content reference link, the IsVisible property is set as follows:

- If the ValidFrom date is less then or equal to that day's date, the IsVisible property is set to True.
- If there is no ValidTo date the IsVisible property is set to True.
- If the ValidTo date is greater then or equal to that day's date, the IsVisible property is set to True.

This property is read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

ValidFrom, ValidTo

Label

Description

This property returns or sets the label for this content reference link object as a string.

The length of this property is 30 characters.

This property is translatable.

This property is read-write.

Name

Description

This property returns the name for this content reference link object as a string. The name is a unique identifier for each content reference link object. The name cannot start with a number, and it cannot have spaces and special characters.

Every content reference link name must be unique in the portal, not just in the parent folder.

This property is read-write.

OwnerId

Description

This property returns or sets the owner ID of the content reference link object as a string.

This property is read-write.

ParentName

Description

This property returns the parent folder name for this content reference link object as a string.

You can use this property to move the content reference link to another folder.

This property is read-write.

Example

The following example uses the ParentName to return a folder object for the content reference link.

```
&Folder = &Portal.FindFolderByName(&CReflink.ParentName);
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Path

Description

The Path property returns a path to this content reference link, with each element of the path separated by a period. The path has the following syntax:

```
Root{PORTAL_ROOT_OBJECT}.LinkFolder {<Id of links folder>}.CrefLink {<Id of the cre⇒
f link> }
```

This property is read-only.

Permissions

Description

This property returns a PermissionValue Collection. This collection contains the value of the non role-based permissions for this content reference link. To access the role-based permissions, use the RolePermissions property.

This property is read-only.

Related Links

PermissionValue Collection, CascadedPermissions, RolePermissions

Product

Description

This property returns or sets the PeopleSoft product for this content reference link object as a string.

The length of this property is 4 characters.

This property is read-write.

PublicAccess

Description

This property specifies whether the link is public or private. This property takes a Boolean value: true if the content reference link is public and there are no permission lists associated with it. If it is false, the link uses permission list control.

For links, this values is same as that of the linked content reference. If the content reference is public, the link is public and can be viewed by anyone logged on to the system.

This property is read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

RelativeURL

Description

This property returns the relative URL in the following format:

../../../Portal/Node/Content_Type/ContentID

For example, from the following URL:

```
http://mlee2038/servlets/psp/PS84/e_procurement/fdm/c/E_PRO.CheckOut.GBL?page=view&⇒
Setid=110&Custid=99
```

The RelativeURL returns the following:

```
e_procurement/fdm/c/E_PRO.CheckOut.GBL?page=view&Setid=110&Custid=99
```

This property is read-only.

RolePermissions

Description

This property returns a RolePermissionValue Collection. This collection contains the value of the role-based permissions for this content reference link. To access the non role-based permissions, use the Permissions property.

This property is read-only.

Related Links

CascadedRolePermissions Permissions RolePermissionValue Collection

SequenceNumber

Description

The sequence number is used when returning a collection. The default order of the returned content reference links is based on the sequence number. Use this property to reorder content reference links. This property takes a number value.

If there are duplicates in the sequence number, the content reference links are returned alphabetically.

The length of this property is 4 characters.

This property is read-write.

Template

Description

This property returns or sets the name of the template used with this content reference link as a string. You must specify the name of an existing template.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property uses the name, not the label, of a content reference link.

This property is used only when the UsageType property is specified as Target (TARG) and the TemplateType property is specified as HTML.

To return a reference to the content reference link that contains the template specified by this property, use the TemplateObject property.

The length of this property is 30 characters.

This property is read-write.

Related Links

UsageType, TemplateType, TemplateObject

TemplateObject

Description

This property returns a reference to a content reference link object that contains the template specified by the Template property as a content reference link. If no template is specified with Template, this property returns a null value.

This property is read-only.

Related Links

Template

TemplateType

Description

This property indicates whether a template should be used to wrap the content. This property takes a string value.

Values are:

Value	*Description*
HTML	An HTML template should wrap the data (URL) in the content reference.
NONE	No template should be used. The text should not be wrapped.

HTML is the default value on a new content reference.

Use the NONE value if the URL should not appear in the portal. An example is when the content reference link is a template itself.

If the homepage template for the user is un-retrievable, the system tries to use the default user's template first, before resorting to the portal default template.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

When the content reference link describes content, this property should be set to HTML.

This property is read-write.

Related Links

Using Content References

URL

Description

This property returns the URL for this content reference link object as a string. The content reference link derives the URL from the content reference it is linked to. The URL of the link is same as that of the linked content reference.

A query string value is added on the content reference URL to make the link unique. If the URL of the linked content reference changes, this URL is changed.

This property is read-only.

Related Links

AbsoluteContentURL, Using Content References

URLType

Description

This property returns what kind of URL is used to retreive the content.

This property is read-only.

Related Links

StorageType

UsageType

Description

This property returns what the content reference link is used for.

The value for this property is same as that of the content reference when the link is vieved as a content reference.

The usage type of the link is LINK in the database.

A content reference link can be created only for content references that have a type of TARG.

This property is read-only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

Using Content References

ValidFrom

Description

This property returns or sets the date this content reference link is valid from as a string.

This property is read-write.

ValidTo

Description

This property returns or sets the date this content reference link is valid until as a string.

This property is read-write.

Note: The portal registry API never uses the ValidTo and ValidFrom fields to determine what to return in a collection. You must check for these values in your application.

Link Collection

A Links collection is returned by the Links content reference property.

Related Links

Links

Link Collection Methods

In this section, we discuss the link collection methods. The methods are discussed in alphabetical order.

First

Syntax

```
First()
```

Description

The First method returns the first link object in the link collection.

Parameters

None.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

A link object.

Next

Syntax

```
Next()
```

Description

The Next method returns the next link object in the collection. You can use this method only after you have used the First method: otherwise the system doesn't know where to start.

Parameters

None.

Returns

A link object.

Link Collection Property

In this section, we discuss the link collection property Count.

Count

Description

This property returns the number of link objects in the link collection, as a number.

This property is read-only.

Link Class

A Link object is returned by the First and Next Link collection methods.

Related Links

Link Collection Methods

Link Properties

In this section, we discuss the link properties. The properties are discussed in alphabetical order.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

LinksObjectName

Description

This property returns the object name of the link as a string.

This property is read-only.

LinksObjectType

Description

This property returns the object type as a string. Valid value is CONTENTREF.

This property is read-only.

LinksPortalName

Description

This property returns the name of the portal from which the link originated.

This property is read-only.

TabDefinition Class

The TabDefinition class provides access to the homepage tab defined for the portal.

TabDefinition objects are instantiated from a TabDefinition Collection with the First, InsertItem, ItemByName, or Next methods.

See TabDefinition Collection.

TabDefinition Class Methods

In this section, we discuss the Save method.

Save

Syntax

```
Save()
```

Description

The Save method saves any changes you made to the TabDefinition, for example, a changed description. It also performs some validation.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Using this method also saves any changes you made to DynamicCategories and AssignedPagelets objects associated with this TabDefinition.

Parameters

None.

Returns

A Boolean value: True if the TabDefinition and its associated object saved successfully, False otherwise.

Example

```
If NOT(&MyTabDefn.Save()) Then
   /* save failed, do error processing */
End-If;
```

TabDefinition Class Properties

In this section, we discuss the TabDefinition class properties. The properties are discussed in alphabetical order.

AssignedPagelets

Description

This property returns a reference to an AssignedPagelet Collection for this TabDefinition object.

This property is read-only.

Related Links

AssignedPagelet Collection

AvailableCategories

Description

This property returns a reference to an AvailableCategory Collection for this TabDefinition object.

This property is read-only.

Related Links

AvailableCategory Collection

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

AvailablePagelets

Description

This property returns a reference to an AvailablePagelet Collection for this TabDefinition object.

This property is read-only.

Related Links

AvailablePagelet Collection

Attributes

Description

This property returns an Attribute Collection containing the AttributeValues for this TabDefinition object.

This property is read-only.

Related Links

Attribute Collection

Author

Description

This property returns the author (PeopleSoft user ID) for this TabDefinition object as a string.

This property is read-only.

AuthorAccess

Description

This property specifies whether the author of the TabDefinition has access to the TabDefinition. This property takes a Boolean value. The default value for this property is True.

This property is read-write.

ColumnLayout

Description

This property indicates whether the tab layout is for two or three columns. This property takes a string value.

The values for this property are:

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Value	*Description*
2	Two-column table
3	Three-column table

This property is read-write.

CreationDate

Description

This property returns the creation date for this TabDefinition object as a string.

This property is read-only.

Description

Description

This property returns or sets the description for this TabDefinition object as a string.

The length of this property is 256 characters.

This property is translatable.

This property is read-write.

DynamicCategories

Description

This property returns a reference to a DynamicCategory Collection for this TabDefinition object.

This property is read-only.

Related Links

DynamicCategory Collection

HelpID

Description

This property returns the help system identifier for this tab. It enables the help system to provide tab-specific help. This property takes a string value.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

HtmlText

Description

This property returns the HTML text associated with this tab definition as a string.

This property is read-only.

IsHideActionBar

Description

This property hides all pagelet action bar images for all pagelets used on this tab. This property overrides any properties for the pagelets used on this tab. This property takes a Boolean value: True, hide images, False, display images

This property is read-write.

IsLayoutLocked

Description

This property indicates whether the user can change the tab's default number of columns. This property takes a Boolean value: True, the user can change the tab columns, False, the columns can't be changed by the user.

This property is read-write.

IsRenameable

Description

This property indicates whether the tab's label can be changed by the user. This property takes a Boolean value: True, the user can change the label, False, the user can't.

This property is read-write.

Label

Description

This property returns or sets the label for this TabDefinition object as a string.

The length of this property is 30 characters.

This property is translatable.

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

LayoutBehavior

Description

This property indicates whether the user can change when and how the tab displays. This property takes a string value.

The values are:

Value	*Description*
4OPT	The user can choose to add this tab to their homepage. It doesn't show up by default.
3DEF	The user sees this tab the first time they log in, however, they can remove this tab if they'd like.
2REQ	The user can't remove this tab from their homepage. However, they are allowed to change its sequence or order on the page.
1FIX	The user can't remove this tab or change its position on the page.

This property is read-write.

Name

Description

This property returns the name for this TabDefinition object as a string. The name is a unique identifier for each TabDefinition object.

Every TabDefinition name must be unique in the portal, not just in the parent folder.

This property is read-only.

OwnerId

Description

This property returns or sets the owner ID of the TabDefinition object as a string.

This property is read-write.

Product

Description

This property returns or sets the PeopleSoft product for this TabDefinition object as a string.

The length of this property is 4 characters.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-write.

PublicAccess

Description

This property indicates whether a TabDefinition is generally accessible, that is, if it is always included in the general TabDefinition collection. This property takes a Boolean value.

The default value for this property is False.

This property is read-write.

QualifiedURL

Description

This property returns an absolute URL. If the TabDefinition has a ContentProvider associated with it, the URI from the ContentProvider is concatenated with the URL from the TabDefinition. If there is no ContentProvider, this property returns the text in the URL property.

This property is read-only.

Related Links

URL

SequenceNumber

Description

The sequence number is used when returning a collection. The default order of the returned TabDefinitions is based on the sequence number. Use this property to reorder TabDefinitions. This property takes a number value.

If there are duplicates in the sequence number, the TabDefinitions are returned alphabetically.

The length of this property is 4 characters.

This property is read-write.

StyleSheet

Description

This property defines the style sheet to use for this tab. This property takes a string value. This property is 30 characters long.

If no style sheet is specified, the default style sheet PSSTYLEDEF is used.

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ValidFrom

Description

This property returns or sets the date this TabDefinition is valid from as a string.

This property is read-write.

ValidTo

Description

This property returns or sets the date this TabDefinition is valid until as a string.

This property is read-write.

Note: The portal registry API never uses the ValidTo and ValidFrom fields to determine what to return in a collection. You must check for these values in your application.

TabDefinition Collection

A TabDefinition collection is the collection of all TabDefinitions for a portal.

A TabDefinition collection is returned by the TabDefinitions PortalRegistry property.

See TabDefinitions.

TabDefinition Collection Methods

This section describes the TabDefinition collection methods in alphabetical order.

DeleteItem

Syntax

DeleteItem(*TabDefinitionName*)

Description

The DeleteItem method deletes the TabDefinition object identified by *TabDefinitionName* from the TabDefinition Collection.

Note: The portal registry classes execute some methods "interactively", that is, as they happen. The item won't be marked for deletion, then actually deleted later. The item is deleted from the database *as soon as* the method is executed.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

TabDefinitionName	Specify the name of a TabDefinition existing in the TabDefinition collection.

Returns

A Boolean value: True if the TabDefinition was deleted, False otherwise.

Example

```
If Not &MyColl.DeleteItem("TabDefnTest") Then
   /* do error processing */
End-If;
```

First

Syntax

First()

Description

The First method returns the first TabDefinition object in the TabDefinition collection.

Parameters

None.

Returns

A TabDefinition object.

Example

```
&MyTabDefinition = &MyCollection.First();
```

InsertItem

Syntax

InsertItem(*TabDefinitionName*)

Description

The InsertItem method inserts the TabDefinition object identified by *TabDefinitionName* into the TabDefinition Collection.

Note: The portal registry classes execute some methods "interactively", that is, as they happen. The item won't be marked for insertion, then actually inserted later. The item is inserted into the database *as soon as* the method is executed.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

TabDefinitionName	Specify the name of an existing permission list.

Returns

A reference to the new TabDefinition object if the method executed successfully, NULL otherwise.

Example

```
&MyTabDef = &MyColl.InsertItem("Empl_Homepage");

If Not &MyTabDef Then
   /* do error processing */
End-If;
```

ItemByName

Syntax

ItemByName(*Name*)

Description

The ItemByName method returns the TabDefinition object with the name *Name*.

Parameters

Name	Specify the name of an existing TabDefinition within the TabDefinition collection. If you specify an invalid name, the object is NULL.

Returns

A TabDefinition object if successful, NULL otherwise.

Example

```
&MyTebDefn = &MyColl.ItemByName("Empl_Homepage");
```

Next

Syntax

Next()

Description

The Next method returns the next TabDefinition object in the TabDefinition collection. You can use this method only after you have used the First method: otherwise the system doesn’t know where to start.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

None.

Returns

TabDefinition object.

Example

```
&MyTabDefinition = &MyCollection.Next();
```

TabDefinition Collection Property

In this section, we discuss the Count property.

Count

Description

This property returns the number of TabDefinition objects in the TabDefinition Collection, as a number.

This property is read-only.

Example

```
&COUNT = &MY_COLLECTION.Count;
```

AssignedPagelet Class

An AssignedPagelet is a pagelet object that has been assigned to a particular tab. This pagelet also contains the layout data that is specific to the pagelet and tab.

AssignedPagelet objects are instantiated from an AssignedPagelet Collection with the First, InsertItem, ItemByName, or Next methods.

See AssignedPagelet Collection.

AssignedPagelet Class Properties

In this section, we discuss the AssignedPagelet class properties. The properties are discussed in alphabetical order.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Column

Description

This property returns the column in which this pagelet is displayed, as a number.

This property is read-write.

LayoutBehavior

Description

This property indicates whether the user can change when and how the pagelet displays. This property takes a string value.

The values are:

Value	*Description*
4OPT	The user can choose to add this pagelet to their tab. It doesn't show up by default. The user can remove and reposition this pagelet on the tab.
3DEF	The user sees this pagelet the first time they log in, however, they can remove or reposition this pagelet if they'd like.
2REQ	The user can't remove this pagelet from the tab. However, they are allowed to reposition the pagelet on the tab.
1FIX	The user can't remove this pagelet or change its position on the tab.

This property is read-write.

PageletName

Description

This property returns the name for this Pagelet object as a string. The name is a unique identifier for each Pagelet object.

This property is read-only.

Row

Description

This property returns the row in which this pagelet is displayed, as a number.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

AssignedPagelet Collection

An AssignedPagelet collection is returned by the AssignedPagelet TabDefinition method.

It contains a collection of all the pagelets explicitly assigned to the tab.

See AssignedPagelets.

See AssignedPagelet Class.

AssignedPagelet Collection Methods

In this section, we discuss the AssignedPagelet collection methods. The methods are discussed in alphabetical order.

DeleteItem

Syntax

DeleteItem(*PageletName*)

Description

The DeleteItem method deletes the AssignedPagelet object identified by *PageletName* from the AssignedPagelet Collection.

This method is not executed automatically. It is executed only when the parent object is saved.

Parameters

PageletName	Specify the name of an AssignedPagelet existing in the AssignedPagelet collection.

Returns

A Boolean value: True if the AssignedPagelet was deleted, False otherwise.

Example

```
If Not &MyColl.DeleteItem("Weather_411") Then
   /* do error processing */
End-If;
```

First

Syntax

First()

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

The First method returns the first AssignedPagelet object in the AssignedPagelet collection.

Parameters

None.

Returns

An AssignedPagelet object.

Example

```
&MyAssignedPagelet = &MyCollection.First();
```

InsertItem

Syntax

InsertItem(*PageletName*, *Column*, *Row*, *LayoutBehavior*)

Description

The InsertItem method inserts the AssignedPagelet object identified by the parameters into the AssignedPagelet Collection.

This method is not executed automatically. It is executed only when the parent object is saved.

Parameters

PageletName Specify the name of the pagelet that you want to insert.

Column Specify the column that you want this pagelet to display in, as a number.

Row Specify the row that you want this pagelet to display in, as a number. You can specify a zero if you don't know which row.

LayoutBehavior Specify whether the user can change when and how the pagelet displays. This property takes a string value. The values are:

Value	*Description*
4OPT	The user can choose to add this pagelet to their tab. It doesn't show up by default. The user can remove and reposition this pagelet on the tab.
3DEF	The user sees this pagelet the first time they log in, however, they can remove or reposition this pagelet if they'd like.
2REQ	The user can't remove this pagelet from the tab. However, they are allowed to reposition the pagelet on the tab.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Value	*Description*
1FIX	The user can't remove this pagelet or change its position on the tab.

Returns

A reference to the new AssignedPagelet object if the method executed successfully, NULL otherwise.

Example

```
&MyPagelet = &MyColl.InsertItem("Weather_411");

If Not &MyPagelet Then
   /* do error processing */
End-If;
```

ItemByName

Syntax

ItemByName(*Name*)

Description

The ItemByName method returns the AssignedPagelet object with the name *Name*.

Parameters

Name Specify the name of an existing AssignedPagelet within the AssignedPagelet collection. If you specify an invalid name, the object is NULL.

Returns

An AssignedPagelet object if successful, NULL otherwise.

Example

```
&MyPagelet = &MyColl.ItemByName("Dictionary");
```

Next

Syntax

Next()

Description

The Next method returns the next AssignedPagelet object in the AssignedPagelet collection. You can use this method only after you have used the First method: otherwise the system doesn’t know where to start.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

None.

Returns

An AssignedPagelet object.

Example

```
&MyAssignedPagelet = &MyCollection.Next();
```

AssignedPagelet Collection Property

In this section, we discuss the Count property.

Count

Description

This property returns the number of AssignedPagelet objects in the AssignedPagelet Collection, as a number.

This property is read-only.

Example

```
&COUNT = &MY_COLLECTION.Count;
```

AvailableCategory Class

An AvailableCategory class is composed of a category name and an AvailablePagelet Collection, that is, a collection of all the available pagelets associated with that category.

AvailableCategory objects are instantiated from an AvailableCategory Collection with the First, ItemByName, or Next methods.

See AvailableCategory Collection.

AvailableCategory Class Properties

In this section, we discuss the AvailableCategory class properties. The properties are discussed in alphabetical order.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

AvailablePagelets

Description

This property returns a reference to an AvailablePagelet Collection associated with the specified CategoryName.

This property is read-only.

Related Links

AvailablePagelet Collection

CategoryName

Description

Use this property to return the name of a category to be associated with the TabDefinition, as a string.

This property is read-only.

AvailableCategory Collection

An AvailableCategory is composed of a category name and an AvailablePagelet Collection, that is, a collection of all the available pagelets associated with that category.

An AvailableCategory collection is returned by the AvailableCategories TabDefinition property.

See AvailableCategory Collection.

AvailableCategory Collection Methods

In this section, we discuss the AvailableCategory collection methods. The methods are discussed in alphabetical order.

First

Syntax

```
First()
```

Description

The First method returns the first AvailableCategory object in the AvailableCategory collection.

Parameters

None.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

An AvailableCategory object.

Example

```
&MyAvailableCategory = &MyCollection.First();
```

ItemByName

Syntax

ItemByName(*Name*)

Description

The ItemByName method returns the AvailableCategory object with the name *Name*.

Parameters

Name	Specify the name of an existing AvailableCategory within the AvailableCategory collection. If you specify an invalid name, the object is NULL.

Returns

An AvailableCategory object if successful, NULL otherwise.

Example

```
&MyCat = &MyColl.ItemByName("Dictionary");
```

Next

Syntax

Next()

Description

The Next method returns the next AvailableCategory object in the AvailableCategory collection. You can use this method only after you have used the First method: otherwise the system doesn't know where to start.

Parameters

None.

Returns

AvailableCategory object.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

```
&MyAvailableCategory = &MyCollection.Next();
```

AvailableCategory Collection Property

In this section, we discuss the Count property.

Count

Description

This property returns the number of AvailableCategory objects in the AvailableCategory Collection, as a number.

This property is read-only.

Example

```
&COUNT = &MY_COLLECTION.Count;
```

AvailablePagelet Class

An AvailablePagelet is a pagelet object can be assigned to a particular tab. This includes all pagelets from the dynamic categories, and assigned pagelets. Each pagelet also contains the layout data that is specific to that pagelet.

AvailablePagelet objects are instantiated from an AvailablePagelet Collection with the First, ItemByName, or Next methods.

See AvailablePagelet Collection.

AvailablePagelet Class Properties

In this section, we discuss the AvailablePagelet class properties. The properties are discussed in alphabetical order.

CategoryLabel

Description

This property turns the label of the category to which the pagelet is assigned, as a string.

This property is read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

CategoryName

Description

This property returns the name of the category to which the pagelet is assigned, as a string.

This property is read-only.

Column

Description

This property returns the column in which this pagelet is displayed, as a number.

This property is read-only.

LayoutBehavior

Description

This property indicates whether the user can change when and how the pagelet displays. This property takes a string value.

The values are:

Value	*Description*
4OPT	The user can choose to add this pagelet to their tab. It doesn't show up by default. The user can remove and reposition this pagelet on the tab.
3DEF	The user sees this pagelet the first time they log in, however, they can remove or reposition this pagelet if they'd like.
2REQ	The user can't remove this pagelet from the tab. However, they are allowed to reposition the pagelet on the tab.
1FIX	The user can't remove this pagelet or change its position on the tab.

This property is read only.

PageletLabel

Description

This property returns the label for this property as a string.

This property is read-only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

PageletName

Description

This property returns the name for this Pagelet object as a string. The name is a unique identifier for each Pagelet object.

This property is read-only.

Row

Description

This property returns the row in which this pagelet is displayed, as a number.

This property is read-only.

AvailablePagelet Collection

An AvailablePagelet collection is returned by the AvailablePagelet TabDefinition method.

It contains a collection of all the pagelets that could be assigned to the tab. It's an aggregation of the pagelets in the AssignedPagelets collection and all the pagelets in each of the categories in the DynamicCategories collection. Pagelet category sequence numbers, followed by pagelet sequence numbers, then name, sort this collection.

If you have two pagelets assigned with the same name (that is, an assigned pagelet and a dynamic category pagelet), the assigned pagelet takes precedence over the dynamic category one, and is the only one listed.

See AvailablePagelets.

See AvailablePagelet Class.

AvailablePagelet Collection Methods

In this section, we discuss the AvailablePagelet collection methods. The methods are discussed in alphabetical order.

First

Syntax

```
First()
```

Description

The First method returns the first AvailablePagelet object in the AvailablePagelet collection.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

None.

Returns

An AvailablePagelet object.

Example

```
&MyAvailablePagelet = &MyCollection.First();
```

ItemByName

Syntax

ItemByName(*Name*)

Description

The ItemByName method returns the AvailablePagelet object with the name *Name*.

Parameters

Name	Specify the name of an existing AvailablePagelet within the AvailablePagelet collection. If you specify an invalid name, the object is NULL.

Returns

An AvailablePagelet object if successful, NULL otherwise.

Example

```
&MyPagelet = &MyColl.ItemByName("DICTIONARY");
```

Next

Syntax

Next()

Description

The Next method returns the next AvailablePagelet object in the AvailablePagelet collection. You can use this method only after you have used the First method: otherwise the system doesn't know where to start.

Parameters

None.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

AvailablePagelet object.

Example

```
&MyAvailablePagelet = &MyCollection.Next();
```

AvailablePagelet Collection Property

In this section, we discuss the Count property.

Count

Description

This property returns the number of AvailablePagelet objects in the AvailablePagelet Collection, as a number.

This property is read-only.

Example

```
&COUNT = &MY_COLLECTION.Count;
```

DynamicCategory Collection

A DynamicCategory collection contains a collection of PageletCategory names associated with a TabDefinition. The collection is initially ordered by category name.

When a PageletCategory is dynamic, it is immediately available to an end-user.

A DynamicCategory Collection is instantiated by the DynamicCategories property of a TabDefinition.

See DynamicCategories.

DynamicCategory Collection Methods

In this section, we discuss the DynamicCategory collection methods. The methods are discussed in alphabetical order.

DeleteItem

Syntax

DeleteItem(*Name*)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

The DeleteItem method deletes the PageletCategory object identified by *Name* from the DynamicCategory Collection. This does *not* delete the PageletCategory from the database, just from the DynamicCategory collection.

This method is not executed automatically. It is executed only when the parent object is saved.

Note: If you delete a DynamicCategory, tabs with the attribute PORTAL_HPTAB_DYN lists must be searched for and updated (if necessary) to reflect the deleted category.

Parameters

Name	Specify the name of an existing category in the DynamicCategory collection.

Returns

A Boolean value: True if the PageletCategory was deleted from the DynamicCategory collection, False otherwise.

Example

```
If Not &MyColl.DeleteItem("Dictionaries") Then
   /* do error processing */
End-If;
```

First

Syntax

```
First()
```

Description

The First method returns the name of the first PageletCategory in the DynamicCategory collection.

Parameters

None.

Returns

A string.

Example

```
&MyDynamicCategory = &MyCollection.First();
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

InsertItem

Syntax

InsertItem(*Name*)

Description

The InsertItem method inserts the PageletCategory object identified by *Name* into the DynamicCategory Collection. This does *not* insert the PageletCategory into the database, just into the DynamicCategory collection. After a PageletCategory is marked as dynamic, it is immediately available to the end-user.

This method is not executed automatically. It is executed only when the parent object is saved.

Parameters

Name Specify the name of the DynamicCategory to insert.

Returns

A string containing the name of the new DynamicCategory object if the method executed successfully, Null otherwise.

Example

```
&MyCat = &MyColl.InsertItem("User_Info");
```

ItemByName

Syntax

ItemByName(*Name*)

Description

The ItemByName method returns the name of the PageletCategory object with the name *Name*.

Parameters

Name Specify the name of an existing DynamicCategory within the DynamicCategory collection. If you specify an invalid name, this method returns a Null string.

Returns

A string.

Example

```
&MyPagelet = &MyColl.ItemByName("Dictionary");
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Next

Syntax

```
Next()
```

Description

The Next method returns the name of the next PageletCategory object in the DynamicCategory collection. You can use this method only after you have used the First method: otherwise the system doesn't know where to start.

Parameters

None.

Returns

A string.

Example

```
&MyDynamicCategory = &MyCollection.Next();
```

DynamicCategory Collection Property

In this section, we discuss the Count property.

Count

Description

This property returns the number of PageletCategory names in the DynamicCategory Collection, as a number.

This property is read-only.

Example

```
&COUNT = &MY_COLLECTION.Count;
```

PageletCategory Class

A PageletCategory is a group of related pagelets, such as Weather, News, Reference, and so on. Each PageletCategory has a collection of pagelets associated with it.

A PageletCategory is instantiated from a PageletCategory Collection with the First, InsertItem, ItemByName, or Next methods.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

All PageletCategory objects that are dynamic are contained in the DynamicCategory collection. The methods from this collection return the names of the PageletCategory objects only, not references to the objects themselves.

See PageletCategory Collection.

PageletCategory Class Method

In this section, we discuss the Save method.

Save

Syntax

Save()

Description

The Save method saves any changes you made to the PageletCategory, for example, a changed description or sequence number.

Parameters

None.

Returns

A Boolean value: True if the PageletCategory object is successfully saved, False otherwise.

Example

```
If Not(&MyPageletCategory.Save()) Then
   /* do error checking */
End-If;
```

PageletCategory Class Properties

In this section, we discuss the PageletCategory class properties. The properties are discussed in alphabetical order.

Attributes

Description

This property returns an Attribute Collection containing the AttributeValues for this PageletCategory object.

This property is read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

Attribute Collection

Author

Description

This property returns the author (PeopleSoft user ID) for this PageletCategory as a string.

This property is read-only.

AuthorAccess

Description

This property specifies whether the author of the PageletCategory has access to the PageletCategory. This property takes a Boolean value. The default value for this property for a newly created object is True. This property is not cascaded.

This property is read-write.

Authorized

Description

This property specifies whether the user is authorized to view this PageletCategory.

The initial value of this property depends on the other permission properties (PublicAccess and AuthorAccess) and the permission list values in the PermissionValue object associated with this PageletCategory.

This property is read-only.

CascadedPermissions

Description

This property returns a PermissionValue Collection. This collection contains the value of the permissions for all the child and parent objects (up to the root PageletCategory). To determine only the permissions of the object use the Permission property instead.

Note: The PORTAL_PAGELETS folder is the parent folder for all PageletCategories. Its security is set to public. PeopleSoft does not recommend cascading any permissions from this folder object. Cascade permissions only from the pagelet category (folder). You *cannot* add any PermissionValue objects to a collection returned by the CascadedPermissions property. You can add values only to the collection returned by the Permissions property.

This property is read-only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

PermissionValue Collection, Permissions

CreationDate

Description

This property returns the creation date for this PageletCategory as a string.

This property is read-only.

Description

Description

This property returns or sets the description for this PageletCategory as a string.

The length of this property is 256 characters.

This property is translatable.

This property is read-write.

Label

Description

This property returns or sets the label for this PageletCategory as a string.

The length of this property is 30 characters.

This property is translatable.

This property is read-write.

Name

Description

This property returns the name for this PageletCategory as a sting. The name is a unique identifier for each PageletCategory.

Every PageletCategory name must be unique in across the portal, not just in the parent PageletCategory.

This property is *not* translatable. However, the values for the Label and Desrciption properties are translatable.

This property is read-only.

Related Links

Label

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

OwnerId

Description

This property returns or sets the owner ID of the PageletCategory object as a string.

This property is read-write.

Pagelets

Description

This property returns a reference to a Pagelet Collection for this PageletCategory.

This property is read-only.

Related Links

Pagelet Collection

Permissions

Description

This property returns a PermissionValue Collection. This collection contains the value of the permissions for this PageletCategory.

Note: The PORTAL_PAGELETS folder is the parent folder for all PageletCategories. Its security is set to public. PeopleSoft does not recommend cascading any permissions from this folder object. Cascade permissions only from the pagelet category (folder).

This property is read-only.

Related Links

PermissionValue Collection

Product

Description

This property returns or sets the PeopleSoft product for this PageletCategory as a string.

The length of this property is 4 characters.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

PublicAccess

Description

This property indicates whether a PageletCategory is generally accessible, that is, if this property is set to True, any user can access the PageletCategory. This property is not cascaded.

This property takes a Boolean value.

The default value for this property for a newly created object is False.

This property is read-write.

SequenceNumber

Description

The sequence number is used when returning a collection. The default order of the returned PageletCategory objects is based on the sequence number. Use this property to reorder PageletCategory objects.

If there are duplicates in the sequence number, the PageletCategory objects are returned in alphabetical order.

The length of this property is 4 characters.

This property is read-write.

PageletCategory Collection

The PageletCategory Collection provides access to a collection of PageletCategory objects in a PageletCategory object.

The PageletCategory Collection is instantiated from the PageletCategories PortalRegistry property.

See PageletCategories.

PageletCategory Collection Methods

In this section, we discuss the PageletCategory collection methods. The methods are discussed in alphabetical order.

DeleteItem

Syntax

DeleteItem(*PageletCategoryName*)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

The DeleteItem method deletes the PageletCategory object identified by *PageletCategoryName* from the database.

Note: The portal registry classes execute some methods "interactively", that is, as they happen. The item won't be marked for deletion, then actually deleted later. The item is deleted from the database *as soon as* the method is executed.

Parameters

PageletCategoryName	Specify the name of a PageletCategory existing in the PageletCategory collection.

Returns

A Boolean value: True if the PageletCategory was deleted, False otherwise.

Example

```
If Not &MyPageletCategoryColl.DeleteItem("MYPAGELETCATEGORY") Then
   /* PageletCategory not deleted. Do error checking */
End-If;
```

First

Syntax

First()

Description

The First method returns the first PageletCategory object in the PageletCategory collection.

Parameters

None.

Returns

PageletCategory object.

Example

```
&MyPageletCategory = &MyCollection.First();
```

InsertItem

Syntax

InsertItem(*PageletCategoryName*, *Label*)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

The InsertItem method inserts the PageletCategory object identified by *PageletCategoryName* from the PageletCategory Collection. You must specify both a name and a label for each PageletCategory. This method returns a reference to the new PageletCategory object. You must specify a unique *PageletCategoryName*, or you receive an error.

Note: The portal registry classes execute some methods "interactively", that is, as they happen. The item won't be marked for insertion, then actually inserted later. The item is inserted into the database *as soon as* the method is executed.

Parameters

PageletCategoryName	Specify the name of a PageletCategory existing in the PageletCategory collection. This parameter takes a string value.
Label	Specify a label for the new PageletCategory. This parameter takes a string value.

Returns

A reference to the new PageletCategory object if the method executed successfully, False otherwise.

ItemByName

Syntax

```
ItemByName(Name)
```

Description

The ItemByName method returns the PageletCategory object with the name *Name*.

Parameters

Name	Specify the name of an existing PageletCategory within the PageletCategory collection. If you specify an invalid name, the object is NULL. You must specify a name, not a label.

Returns

A PageletCategory object if successful, NULL otherwise.

Next

Syntax

```
Next()
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

The Next method returns the next PageletCategory object in the PageletCategory collection. You can use this method only after you have used the First method: otherwise the system doesn't know where to start.

Parameters

None.

Returns

A PageletCategory object.

PageletCategory Collection Property

In this section, we discuss the PageletCategory collection properties. The properties are discussed in alphabetical order.

Count

Description

This property returns the number of PageletCategory objects in the PageletCategory Collection, as a number.

This property is read-only.

Example

```
&COUNT = &MY_COLLECTION.Count;
```

Pagelet Class

A pagelet represents a URL that renders a section of content for a homepage. Pagelets are assigned to specific categories.

A pagelet is instantiated from the First, InsertItem, ItemByName, and Next Pagelet Collection methods.

See Pagelet Collection.

Pagelet Class Method

In this section, we discuss the Save method.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Save

Syntax

Save()

Description

The Save method saves any changes you made to the Pagelet, for example, a changed description or sequence number.

Parameters

None.

Returns

A Boolean value: True if the Pagelet object is successfully saved, False otherwise.

Example

```
If Not(&MyPagelet.Save()) Then
   /* do error checking */
End-If;
```

Pagelet Class Properties

In this section, we discuss the Pagelet class properties. The properties are discussed in alphabetical order.

Attributes

Description

This property returns an Attribute Collection containing the AttributeValues for this pagelet object.

This property is read-only.

Related Links

Attribute Collection

Author

Description

This property returns the author (PeopleSoft user ID) for this pagelet object as a string.

This property is read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

AuthorAccess

Description

This property specifies whether the author of the pagelet has access to the pagelet. This property takes a Boolean value. The default value for this property is True.

This property is read-write.

Authorized

Description

This property specifies whether the user is authorized to view this pagelet.

The initial value of this property depends on the other permission properties (PublicAccess and AuthorAccess) and the permission list values in the PermissionValue object associated with this pagelet.

This property is read-only.

CascadedPermissions

Description

This property returns a PermissionValue collection. This collection contains the value of the permissions for all the parent objects (up to the root folder). To determine only the permissions of the object use the Permission property instead.

Note: You *cannot* add any PermissionValue objects to a collection returned by the CascadedPermissions property. You can add values only to the collection returned by the Permissions property.

This property is read-only.

Related Links

PermissionValue Collection, Permissions

ContentProvider

Description

This property returns or sets the name of the node for the pagelet as a string.

If no node was specified when the pagelet was created, this property returns Null.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

CreationDate

Description

This property returns the creation date for this pagelet object as a string.

This property is read-only.

DefaultColumn

Description

This property returns or sets the default column this pagelet displays in. This property takes a number value.

The default value for this property is 1.

This property is read-write.

Description

Description

This property returns or sets the description for this pagelet object as a string.

The length of this property is 256 characters.

This property is translatable.

This property is read-write.

EditPageContentProvider

Description

This is the node part of the URL to the page that enables a user to personalize a page. The default value is an empty string.

This property is read-write.

EditPageQueryString

Description

This is the query string part of the URL to the page that enables a user to personalize a page. The default value for this property is an empty string.

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

HelpID

Description

This property returns the help system identifier for this pagelet. It enables the help system to provide pagelet specific help. This property takes a string value.

This property is read-write.

IsHideMinimize

Description

This property specifies if the minimize image icon displays. This property takes a Boolean value: True, display the icon, False, hide the icon. The default value is True.

This property is read-write.

Label

Description

This property returns or sets the label for this pagelet object as a string.

The length of this property is 30 characters.

This property is translatable.

This property is read-write.

Name

Description

This property returns the name for this pagelet object as a string. The name is a unique identifier for each pagelet object.

Every pagelet name must be unique in the portal, not just in the parent folder.

This property is not translatable. However, the values for the Label and Description properties are.

This property is read-only.

OwnerId

Description

This property returns or sets the owner ID of the pagelet object as a string.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ParentName

Description

This property returns the parent folder name for this pagelet object as a string.

This property is read-write.

Permissions

Description

This property returns a PermissionValue Collection. This collection contains the value of the permissions for this pagelet. To determine the permissions for all the parent objects (up to the root folder) use the CascadedPermissions property.

This property is read-only.

Related Links

PermissionValue Collection, CascadedPermissions

Product

Description

This property returns or sets the PeopleSoft product for this pagelet object as a string.

The length of this property is 4 characters.

This property is read-write.

PublicAccess

Description

This property indicates whether a pagelet is generally accessible, that is, if it will always be included in the general pagelet collection. This property takes a Boolean value.

The default value for this property is False.

This property is read-write.

QualifiedURL

Description

This property returns an absolute URL. If the pagelet has a node associated with it, the URI from the node is concatenated with the URL from the pagelet. If there is no ContentProvider, this property returns the text in the URL property.

This property is read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

URL

SequenceNumber

Description

The sequence number is used when returning a collection. The default order of the returned pagelets is based on the sequence number. Use this property to reorder pagelets. This property takes a number value.

If there are duplicates in the sequence number, the pagelets are returned alphabetically.

The length of this property is 4 characters.

This property is read-write.

URL

Description

This property returns or sets the URL for this pagelet object as a string. The URL returns *exactly* as it appears in the database.

If you're setting a URL, you must use a unique URL.

The absolute URL, that is, the URL from the ContentProvider concatenated with this URL must be unique.

You receive an error if the URL you use is already registered.

To retrieve a qualified URL, that is, one that contains the node URI, use the AbsoluteContentURL property.

The length of this property depends on your system database limit for LONG fields.

The format of the value for this property depends on the setting of other properties.

This property is read-write.

URLType

Description

This property indicates what kind of PeopleCode definition is used to retrieve the content of the pagelet. This property takes a string value.

Values are:

URLType Value	*Meaning*
UEXT	URL points to a non-PeopleSoft (external) URL

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

URLType Value	*Meaning*
UPGE	URL points to a component.
UGEN	URL points to a generic PeopleSoft URL
USCR	URL points to an iScript

UPGE is the default value on a new pagelet.

This property is read-write.

Pagelet Collection

The Pagelet Collection provides access to the collection of pagelets in a category.

The Pagelet Collection is instantiated from the Pagelets PageletCategory property.

See Pagelets.

Pagelet Collection Methods

In this section, we discuss the Pagelet collection methods. The methods are discussed in alphabetical order.

DeleteItem

Syntax

`DeleteItem``(`*`PageletName`*`)`

Description

The DeleteItem method deletes the pagelet object identified by *PageletName* from the pagelet Collection.

Note: The portal registry classes execute some methods "interactively", that is, as they happen. The item won't be marked for deletion, then actually deleted later. The item is deleted from the database as soon as the method is executed.

Parameters

PageletName Specify the name of a pagelet existing in the pagelet collection.

Returns

A Boolean value: True if the pagelet was deleted, False otherwise.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

```
If Not &MyColl.DeleteItem("Test_Pagelet") Then
   /* can't delete test data. Do error processing */
End-if;
```

First

Syntax

First()

Description

The First method returns the first pagelet object in the pagelet collection.

Parameters

None.

Returns

A reference to a pagelet object if successful, NULL otherwise.

Example

```
&MyCRef = &MyCollection.First();
```

InsertItem

Syntax

InsertItem(*PageletName*, *Label*, *NodeName*, *URL*)

Description

The InsertItem method inserts the pagelet object identified by *PageletName* into the pagelet Collection.

Note: The portal registry classes execute some methods "interactively", that is, as they happen. The item won't be marked for insertion, then actually inserted later. The item is inserted into the database *as soon as* the method is executed.

Parameters

PageletName	Specify the name of a new pagelet. This parameter takes a string value. If you specify a name that already exists in the collection, you receive an error.
Label	Specify the label for the new pagelet. This parameter takes a string value.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

NodeName Specify a node. This parameter takes a string value. If you specify a fully qualified URL, you can specify a Null (that is, two quotation marks with no space between them (("")).

URL Specify a URL that contains the content. The format of this parameter depends on other properties, such as the type of pagelet, where the data is stored, and so on.

Returns

A reference to the new pagelet object if the method executed successfully, NULL otherwise.

Related Links

Using Content References

ItemByName

Syntax

ItemByName(*Name*)

Description

The ItemByName method returns the pagelet object with the name *Name*.

Parameters

Name Specify the name of an existing pagelet within the pagelet collection. If you specify an invalid name, the object will be NULL.

Returns

A reference to a pagelet object if successful, NULL otherwise.

Example

```
&MyPagelet = &CRefColl.ItemByName("PORTAL_ADMIN);
```

Next

Syntax

Next()

Description

The Next method returns the next pagelet object in the pagelet collection. You can only use this method after you have used the First method: otherwise the system doesn't know where to start.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

None.

Returns

A reference to a pagelet object if successful, NULL otherwise.

Example

```
&MyPagelet = &MyCollection.Next();
```

Pagelet Collection Property

In this section, we discuss the Count property.

Count

Description

This property returns the number of pagelet objects in the pagelet Collection, as a number.

This property is read-only.

Example

```
&COUNT = &MY_COLLECTION.Count;
```

UserHomepage Class

The UserHomepage represents a homepage for a user. It contains all the tabs and pagelets the user has selected for their homepage.

A UserHomepage is instantiated from the Homepage PortalRegistry property.

See Homepage.

UserHomepage Class Method

In this section, we discuss the Save method.

Save

Syntax

Save()

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

The Save method saves any changes you made to the UserHomepage, for example, a changed greeting.

Using this method also saves any changes you've made to any UserTab or SelectedPagelet objects associated with this UserHomepage.

Parameters

None.

Returns

A Boolean value: True if the UserHomepage object is successfully saved, False otherwise.

Example

```
If Not(&MyHP.Save()) Then
   /* do error checking */
End-If;
```

UserHomepage Class Properties

In this section, we discuss the UserHomepage properties. The properties are discussed in alphabetical order.

Greeting

Description

This property is a user-definable message that appears on their homepage when they login, such as "My Homepage" or "Welcome." This property takes a text string. The length of this character is 254.

This property is read-write.

UserId

Description

This property returns the UserId for this UserHomepage as a string.

This property is read-only.

UserTab

Description

This property returns a reference to a UserTab collection.

This property is read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

UserTab Collection

UserTab Class

A UserTab is a personalized tab for a specific user. This user can potentially change the pagelets that appear on the tab, the name of the tab, and the order of the tab. All these changes can be allowed or denied on the TabDefinitions Class. The UserTab is used in place of the TabDefinition whenever a user has personalized a tab.

A UserTab object is instantiated from the First, ItemByName, InsertItem, or Next UserTab Collection methods.

See UserTab Collection.

UserTab Class Properties

In this section, we discuss the UserTab class properties. The properties are discussed in alphabetical order.

ColumnLayout

Description

This property specifies how many columns the UserTab contains. This property takes a numeric value. The values are:

Value	*Description*
2	Two-column layout
3	Three-column layout. This is the default value.

This property is read-write.

Label

Description

This property returns or sets the label for this UserTab object as a string. This value is initially set to the Label of the TabDefinition.

The length of this property is 30 characters.

This property is translatable.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

QualifiedURL

Description

This property returns an absolute URL as a string. This URL includes the URI from the TabDefinition's node and the URL that points to the actual content of the tab.

This property is read-only.

SelectedPagelets

Description

This property returns a SelectedPagelets Collection, containing the pagelets that have been selected by the user to appear on this tab.

This property is read-only.

Related Links

SelectedPagelet Collection

SequenceNumber

Description

This property specifies the order that this tab should appear as on the homepage. This property takes a number value. This value is initially set by the referenced TabDefinition.

This property is read-write.

TabName

Description

This property returns the tab name as a sting.

This property is read-only.

UserTab Collection

The UserTab collection is the collection of personalized tabs for a user.

The UserTab Collection is instantiated from the UserTabs UserHomepage property.

See UserTab.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

UserTab Collection Methods

In this section, we discuss the UserTab collection methods. The methods are discussed in alphabetical order.

DeleteItem

Syntax

DeleteItem(*UserTabName*)

Description

The DeleteItem method deletes the UserTab object identified by *UserTabName* from the UserTab Collection.

This method is not executed automatically. It is executed only when the parent object is saved.

Parameters

UserTabName	Specify the name of a UserTab existing in the UserTab collection.

Returns

A Boolean value: True if the UserTab was deleted, False otherwise.

Example

```
If Not &MyColl.DeleteItem("Test_UserTab") Then
   /* can't delete test data. Do error processing */
End-if;
```

First

Syntax

First()

Description

The First method returns the first UserTab object in the UserTab collection.

Parameters

None.

Returns

A UserTab object.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

```
&MyUserTab = &MyCollection.First();
```

InsertItem

Syntax

InsertItem(*UserTabName*)

Description

The InsertItem method inserts the UserTab object identified by *UserTabName* into the UserTab Collection.

This method is not executed automatically. It is executed only when the parent object is saved.

The new user tab must be unique within the portal.

Parameters

UserTabName	Specify the name of a new UserTab. This parameter takes a string value. If you specify a name that already exists in the collection, you get an error.

Returns

A reference to the new UserTab object if the method executed successfully, NULL otherwise.

ItemByName

Syntax

ItemByName(*Name*)

Description

The ItemByName method returns the UserTab object with the name *Name*.

Parameters

Name	Specify the name of an existing UserTab within the UserTab collection. If you specify an invalid name, the object is NULL.

Returns

A UserTab object if successful, NULL otherwise.

Example

```
&MyUserTab = &MyColl.ItemByName("PORTAL_ADMIN");
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Next

Syntax

```
Next()
```

Description

The Next method returns the next UserTab object in the UserTab collection. You can use this method only after you have used the First method: otherwise the system doesn't know where to start.

Parameters

None.

Returns

A UserTab object.

Example

```
&MyUserTab = &MyCollection.Next();
```

UserTab Collection Property

In this section, we discuss the Count property.

Count

Description

This property returns the number of UserTab objects in the UserTab Collection, as a number.

This property is read-only.

Example

```
&COUNT = &MY_COLLECTION.Count;
```

SelectedPagelet Class

The SelectedPagelet class contains data on pagelets selected by the user that display on this tab.

A SelectedPagelet object is instantiated by the First, InsertItem, ItemByName, and Next SelectedPagelet Collection methods.

See SelectedPagelet Collection.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SelectedPagelet Class Properties

In this section, we discuss the SelectedPagelet class properties. The properties are discussed in alphabetical order.

CategoryName

Description

This property returns the category of the pagelet as a string.

This property is read-only.

Column

Description

This property returns the number of the column the pagelet displays in, as a number.

The values are:

Value	*Description*
1	First column
2	Second column
3	Third column

This property is read-write.

IsMinimized

Description

This property specifies whether the pagelet is displayed minimized. This property takes a Boolean value: True, the pagelet is minimized, False otherwise.

This property is read-write.

PageletName

Description

This property returns the name of the pagelet as a string.

This property is read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Row

Description

This property specifies which row the pagelet is displayed in, as a number.

This property is read-write.

SelectedPagelet Collection

The SelectedPagelet collection contains a collection of all the selected pagelets for a tab.

A SelectedPagelet collection is instantiated by the SelectedPagelets UserTab property.

See SelectedPagelets.

SelectedPagelet Collection Methods

In this section, we discuss the SelectedPagelet collection methods. The methods are discussed in alphabetical order.

DeleteItem

Syntax

DeleteItem(*SelectedPageletName*)

Description

The DeleteItem method deletes the SelectedPagelet object identified by *SelectedPageletName* from the SelectedPagelet Collection.

This method is not executed automatically. It is executed only when the parent object is saved.

Parameters

SelectedPageletName	Specify the name of a SelectedPagelet existing in the SelectedPagelet collection.

Returns

A Boolean value: True if the SelectedPagelet was deleted, False otherwise.

Example

```
If Not &MyColl.DeleteItem("Test_SelectedPagelet") Then
   /* can't delete test data. Do error processing */
End-if;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

First

Syntax

```
First()
```

Description

The First method returns the first SelectedPagelet object in the SelectedPagelet collection.

Parameters

None.

Returns

A SelectedPagelet object.

Example

```
&MySelectedPagelet = &MyCollection.First();
```

InsertItem

Syntax

```
InsertItem(SelectedPageletName, Column, Row)
```

Description

The InsertItem method inserts the SelectedPagelet object identified by *SelectedPageletName* into the SelectedPagelet Collection.

This method is not executed automatically. It is executed only when the parent object is saved.

Parameters

SelectedPageletName	Specify the name of a new SelectedPagelet. This parameter takes a string value. If you specify a name that already exists in the collection, you get an error.
Column	Specify the column number for this pagelet.
Row	Specify the row number for this pagelet.

Returns

A reference to the new SelectedPagelet object if the method executed successfully, NULL otherwise.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ItemByName

Syntax

ItemByName(*Name*)

Description

The ItemByName method returns the SelectedPagelet object with the name *Name*.

Parameters

Name	Specify the name of an existing SelectedPagelet within the SelectedPagelet collection. If you specify an invalid name, the object is NULL.

Returns

A SelectedPagelet object if successful, NULL otherwise.

Example

```
&MySelectedPagelet = &MyColl.ItemByName("PORTAL_ADMIN");
```

Next

Syntax

Next()

Description

The Next method returns the next SelectedPagelet object in the SelectedPagelet collection. You can use this method only after you have used the First method: otherwise the system doesn't know where to start.

Parameters

None.

Returns

A SelectedPagelet object.

Example

```
&MySelectedPagelet = &MyCollection.Next();
```

SelectedPagelet Collection Property

In this section, we discuss the Count property.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Count

Description

This property returns the number of SelectedPagelet objects in the SelectedPagelet Collection, as a number.

This property is read-only.

Example

```
&COUNT = &MY_COLLECTION.Count;
```

Favorite Class

A favorite represents a content reference the user wants to keep a shortcut to. It contains the name of the content reference and the label the user wants to see displayed for this favorite. Labels must be unique in each favorite collection.

Use the Save method of the Favorite class to save any changes you made to any favorite objects.

A favorite object is instantiated by the First, InsertItem, ItemByName, and Next Favorite Collection methods.

See Favorite Collection.

Favorite Class Properties

In this section, we discuss the Favorite class properties. The properties are discussed in alphabetical order.

CRefName

Description

This property returns the name of the content reference as a string.

This property is read-only.

IsFolder

Description

This property specifies a Boolean value indicating whether the favorite is a folder object. True, the favorite is a folder, False otherwise.

This property is read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Label

Description

This property specifies the description of the favorite that's displayed to the user. This label must be unique for the favorite collection.

This property is read-write.

QualifiedURL

Description

This property returns the qualified URL for the content reference based on the Node and the URL for the name of the content reference, as a string.

This property is read-only.

SequenceNumber

Description

This property returns the sequence number used to order favorites.

This property is read-write.

URL

Description

This property returns the relative URL for this favorite as a string.

For example, the following code:

```
&URL = &MyFavorite.URL;
```

could return the following string:

```
c/PORTAL_PERS_HOMEPAGE.PORTAL_HOMEPAGE.GBL?PORTALPARAM_PAGE=CONTENT&tab=DEFAULT&Por⇒
talFavorite=QEDMO
```

This property is read-write.

Favorite Collection

The favorite collection provides access to the favorites for a particular user.

A favorite collection is instantiated by the Favorites PortalRegistry property.

See Favorites.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Favorite Collection Methods

In this section, we discuss the Favorite collection methods. The methods are discussed in alphabetical order.

DeleteItem

Syntax

DeleteItem(*FavoriteLabel*)

Description

The DeleteItem method deletes the Favorite object identified by *FavoriteLabel* from the Favorite Collection.

Note: The portal registry classes execute some methods "interactively", that is, as they happen. The item won't be marked for deletion, then actually deleted later. The item is deleted from the database *as soon as* the method is executed.

Parameters

FavoriteLabel	Specify the label of a Favorite existing in the Favorite collection, that is, the text used to identify the favorite to the end-user.

Returns

A Boolean value: True if the Favorite was deleted, False otherwise.

Example

```
If Not &MyColl.DeleteItem("My Local Test") Then
   /* can't delete test data. Do error processing */
End-if;
```

First

Syntax

First()

Description

The First method returns the first Favorite object in the Favorite collection.

Parameters

None.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

A Favorite object.

Example

```
&MyFav = &MyCollection.First();
```

InsertFolderItem

Syntax

InsertFolderItem(*FavoriteLabel, FavoriteName*)

Description

Use the InsertFolderItem method to insert the Favorite folder object identified by FavoriteName into the Favorite collection.

Note: The portal registry classes execute some methods "interactively", that is, as they happen. The item won't be marked for insertion, then actually inserted later. The item is inserted to the database as soon as the method is executed.

Parameters

FavoriteLabel	Specify a label for the new Favorite folder as a string. This is the text by which the favorite is identified to the end user.
FavoriteName	Specify the name for the new Favorite folder as a string. If you specify a name that already exists in the collection, you get an error.

Returns

A reference to the new Favorite object if the method executes successfully, Null otherwise.

InsertItem

Syntax

InsertItem(*FavoriteLabel, FavoriteName*)

Description

The InsertItem method inserts the Favorite object identified by *FavoriteName* into the Favorite Collection.

Note: The portal registry classes execute some methods "interactively", that is, as they happen. The item won't be marked for insertion, then actually inserted later. The item is inserted to the database *as soon as* the method is executed.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

FavoriteLabel Specify a label for the new Favorite. This is the text by which the favorite is identified to the end-user.

FavoriteName Specify the name of a new Favorite. This parameter takes a string value. If you specify a name that already exists in the collection, you get an error.

Returns

A reference to the new Favorite object if the method executed successfully, NULL otherwise.

ItemByLabel

Syntax

ItemByLabel(*FavoriteLabel*)

Description

The ItemByLabel method returns the Favorite object with the label *FavoriteLabel*. The label is the text used to identify the favorite to the end-user.

Parameters

FavoriteLabel Specify the label of an existing Favorite within the Favorite collection. If you specify an invalid favorite, the object returned is Null.

Returns

A Favorite object if successful, Null otherwise.

Example

```
&MyFavorite = &MyColl.ItemByLabel("My Local Login");
```

Next

Syntax

Next()

Description

The Next method returns the next Favorite object in the Favorite collection. You can use this method only after you have used the First method: otherwise the system doesn’t know where to start.

Parameters

None.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

A Favorite object.

Example

```
&MyFavorite = &MyCollection.Next();
```

Save

Syntax

```
Save()
```

Description

Use the Save method to save any changes you made to the Favorite collection.

Parameters

None.

Returns

A Boolean value: True, the collection saved successfully, False otherwise.

Favorite Collection Property

In this section, we discuss the Count property.

Count

Description

This property returns the number of Favorite objects in the Favorite Collection, as a number.

This property is read-only.

Example

```
&COUNT = &MY_COLLECTION.Count
```

Portal Registry Classes Example

There are several actions you may want to perform using a PortalRegistry, such as adding a folder, changing permissions, and so on. The following examples discuss the most common tasks. In addition, there are example programs of accessing the PortalRegistry classes using language environments other than PeopleCode.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Changing PortalRegistry Properties

This example shows how to change the default template used by a PortalRegistry. The following is the complete code sample: the steps explain each line.

```
Local ApiObject &MySession;
Local ApiObject &MyPortal, &MyPortalColl;

/* Access the current session */

&MySession = %Session;
If NOT &MySession Then
   /* do error processing */
End-if;

&MyPortalColl = &MySession.FindPortalRegistries();

For &I = 1 to &MyPortalColl.Count

   &MyPortal = &MyPortalColl.Item(&I);

   If &MyPortal.DefaultTemplate = "HR99" Then
      &MyPortal.DefaultTemplate = "HR00"
      &MyPortal.Save();
   End-If

End-For;
```

To change PortalRegistry properties:

1. Get a Session object.

   Before you can access a PortalRegistry object, you must get a session object. The session controls access to the registry, provides error tracing, enables you to set the runtime environment, and so on. Because you want to use the existing session, use the %Session system variable (instead of the GetSession function.)

   ```
   &MySession = %Session;
   ```

2. Get a PortalRegistry collection.

   Use the FindPortalRegistries method with no parameters to return a collection of all the PortalRegistries because you want to check all the registries for the invalid template.

   ```
   &MyPortalColl = &MySession.FindPortalRegistries();
   ```

   Use the Count property on the collection to loop through all the registries.

   ```
   For &I = 1 to &MyPortalColl.Count
   ```

3. Get a PortalRegistry object.

   You can access a PortalRegistry object from the PortalRegistry collection using the Item method.

   ```
   &MyPortal = &MyPortalColl.Item(&I);
   ```

4. Check for the invalid template and correct if necessary.

   Use the DefaultTemplate property both to check for the invalid template name, and to set the correct template. Save the PortalRegistry when you make a correction.

   ```
   If &MyPortal.DefaultTemplate = "HR99" Then
      &MyPortal.DefaultTemplate = "HR00"
   ```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
      &MyPortal.Save();
   End-If;
```

You may want to do error checking after you save the PortalRegistry.

Adding a ContentProvider

The following example adds a ContentProvider to an existing PortalRegistry. The following is the complete code sample: the steps explain each line.

```
Local ApiObject &MyPortal;
Local ApiObject &MyCPColl, &MyCProvider;

&MyPortal = %Session.GetPortalRegistry();

If NOT &MyPortal.Open(MYRECORD.PORTAL_NAME) Then
   /* Do error handling */
End-if;

/* Add a ContentProvider */

&MyCPColl = &MyPortal.ContentProviders;

&MyCProvider = &MyCPColl.InsertItem("HRMS_00");

&MyCProvider.URI = "http://MYMACHINE103100/servlets/iclientservlet/HRMS/";
&MyCProvider.DefaultTemplate = "MYPORTAL_HRMS";
&MyCProvider.Description = "Updated Content Provider for HRMS";

If NOT(&MyPortal.Save()) Then
   &ErrorCol = &MySession.PSMessages;
   For &I = 1 to &ErrorCol.Count
      &Error = &ErrorCol.Item(&I);
   /* do error processing */
   End-For;
&ErrorCol.DeleteAll();
End-If;
```

To add a ContentProvider:

1. Get a Session object and a PortalRegistry.

   Before you can access a PortalRegistry object, you must get a session object. The session controls access to the registry, provides error tracing, enables you to set the runtime environment, and so on. Because you want to use the existing session, use the %Session system variable (instead of the GetSession function.) In addition, you want to get a PortalRegistry. Using the GetPortalRegistry method returns a reference to an unpopulated PortalRegistry object.

   ```
   &MyPortal = %Session.GetPortalRegistry();
   ```

2. Open the PortalRegistry.

   After you get a PortalRegistry object, you want to open it, that is, populate it with data. Use the Open method to do this. The Open method returns a Boolean value, and this example uses that value to do error checking to make sure that the PortalRegistry is actually opened. In addition, the name of the PortalRegistry is kept in the record MYRECORD, in the field PORTAL_NAME.

   ```
   If NOT &MyPortal.Open(MYRECORD.PORTAL_NAME) Then
      /* Do error handling */
   End-if;
   ```

3. Access the ContentProvider collection.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

You can only add a ContentProvider to a ContentProvider collection. So you must access a ContentProvider collection first, using the ContentProviders property on a PortalRegistry.

```
&MyCPColl = &MyPortal.ContentProviders;
```

4. Add the ContentProvider.

   You must use the name of the ContentProvider with the InsertItem method. This example uses HRMS_00. This method does *not* execute automatically, that is, the ContentProvider isn't actually inserted into the database until the PortalRegistry is saved.

```
&MyCProvider = &MyCPColl.InsertItem("HRMS_00");
```

5. Further define the ContentProvider.

   The URI of a ContentProvider is used in conjunction with content references to define the location of content. So you should define the URI. If a template isn't found for any of the content references on a page at runtime, the system next tries to use the DefaultTemplate defined for a ContentProvider, so you should define a default template.

```
&MyCProvider.URI = "http://MYMACHINE103100/servlets/iclientservlet/HRMS/";
&MyCProvider.DefaultTemplate = "MYPORTAL_HRMS";
&MyCProvider.Description = "Updated Content Provider for HRMS";
```

6. Save the PortalRegistry and check for errors.

   Because there is no Save method with a ContentProvider, you must save the PortalRegistry to complete your changes.

   You can check if there were any errors using the PSMessages property on the session object.

```
If NOT(&MyPortal.Save()) Then
   /* save didn&rsquo;t complete */
   &ErrorCol = &MySession.PSMessages;
   For &I = 1 to &ErrorCol.Count
      &Error = &ErrorCol.Item(&I);
      /* do error processing */
   End-For;
   &ErrorCol.DeleteAll();
End-if;
```

   If there are multiple errors, all errors are logged to the PSMessages collection, not just the first occurrence of an error. As you correct each error, delete it from the PSMessages collection.

Note: If you've called the portal registry API from an Application Engine program, all errors are also logged in the Application Engine error log tables.

See Error Handling.

Adding a Folder

The following example checks to see if a folder for a user exists. If it doesn't, it creates one.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The folder hierarchy for this example is as follows. The Users folder is where the portal stores things such as user homepages:

```
Root folder

   Users folder

      UserId1 folder

      UserId2 folder

      UserId3 folder

      . . .
```

The following is the complete code sample: the steps explain each line.

```
Local ApiObject &MyPortal;
Local ApiObject &UserFldrColl, &UserFldr;

&MyPortal = %Session.GetPortalRegistry();

If NOT &MyPortal.Open(MYRECORD.PORTAL_NAME) Then
   /* Do error handling */
End-if;

&UserFldrColl = &MyPortal.RootFolder.Folders.ItemByName("Users").Folders;

&UserFldr = &UserFldrColl.ItemByName(%UserId);

If &UserFldr = Null Then

/* add Folder */

   &UserFldr = &UserFldrColl.InsertItem(%UserId, %UserId);
   &UserFldr.Description = %UserId;

/* Set dates */

   &UserFldr.ValidFrom = %Date;
   &ToDate = AddToDate(%Date, 1, 1, 0);
   &UserFldr.ValidTo = &ToDate;

/* Set properties */

   &UserFldr.PublicAccess = True;

/* save the folder */

   &UserFldr.Save();

End-If;
```

To add a folder:

1. Get a Session object and a PortalRegistry.

   Before you can access a PortalRegistry object, you must get a session object. The session controls access to the registry, provides error tracing, enables you to set the runtime environment, and so on. Because you want to use the existing session, use the %Session system variable (instead of the GetSession function.) In addition, you want to get a PortalRegistry. Using the GetPortalRegistry method returns a reference to an unpopulated PortalRegistry object.

   ```
   &MyPortal = %Session.GetPortalRegistry();
   ```

2. Open the PortalRegistry.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

After you get a PortalRegistry object, you want to open it, that is, populate it with data. Use the Open method to do this. The Open method returns a Boolean value, and this example uses that value to do error checking to make sure that the PortalRegistry is actually opened. In addition, the name of the PortalRegistry is kept in the record MYRECORD, in the field PORTAL_NAME.

```
If NOT &MyPortal.Open(MYRECORD.PORTAL_NAME) Then
   /* Do error handling */
End-if;
```

3. Access the User folder collection.

   One of the strengths of dot notation is being able to string together many methods and properties into a single line of code. The result of this single line of code is to return a reference to the folder collection within the Users folder.

```
&UserFldrColl = &MyPortal.RootFolder.Folders.ItemByName("Users").Folders;
```

   Note that in this kind of code, you must access the RootFolder for the PortalRegistry before you can access the folders collection.

   If there were additional folders in your hierarchy, you could continue in the same way, using ItemByName and Folders.

4. Check if the user already has a folder.

   The system variable %UserId returns the user ID of the current user. Then this example uses the ItemByName method on the folder collection to see if the user already has a folder. This assumes that the user folders are names according to the UserId. The ItemByName method returns a reference to the folder if it exists. If the folder does not exist, ItemByName returns NULL.

```
&UserFldr = &UserFldrColl.ItemByName(%UserId);

If &UserFldr = Null Then
```

5. Add a folder if one doesn't exist.

   Use the UserId as the name of the folder, as well as for the label and the description.

```
&UserFldr = &UserFldrColl.InsertItem(%UserId, %UserId);
&UserFldr.Description = %UserId;
```

6. Set the ValidFrom and ValidTo dates.

   For this example, the folder should be accessible from the date it's created, so the example sets the ValidFrom property to be today's date.

   When you first create a folder, the ValidTo date, that is, the date that this folder "expires", is set to null, that is an empty string. This means it never expires. In this example, we set the ValidTo date to one year and one day after the current date.

```
   &UserFldr.ValidFrom = %Date;
   &ToDate = AddToDate(%Date, 1, 1, 0);
   &UserFldr.ValidTo = &ToDate;
```

7. Set permissions for the folder.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

There are several properties that work together to determine the access of a folder or content reference. This example sets the PublicAccess property to True, which means that everyone has access to it, and it's included in all collections of folders.

```
&UserFldr.PublicAccess = True;
```

This example sets only the permission properties on the folder. It doesn't set all the possible permissions, such as the PermissionValue objects for the folder.

8. Save the folder.

   After you have finished your changes to the folder, save it.

```
&UserFldr.Save();
```

   You may want to check for errors after you save each folder.

See Using Security.

Adding a Content Reference

The following code example adds a content reference that's a target component to the Approve Expenses folder.

The folder hierarchy for this example is:

```
Root folder

   Expenses folder

      Create Expenses folder

      Review Expenses folder

      Approve Expenses folder
```

The following is the complete code sample: the steps explain each line.

```
Local ApiObject &MyPortal;
Local ApiObject &CRef, &CRefColl;
Local ApiObject &Fldr;

&MyPortal = %Session.GetPortalRegistry();

If NOT &MyPortal.Open(MYRECORD.PORTAL_NAME) Then
   /* Do error handling */
End-if;

&Fldr = &MyPortal.RootFolder.Folders.ItemByName("Expenses").Folders.ItemByName("App⇒
rove Expenses");

/* add content reference */

&CRef = &Fldr.ContentRefs.InsertItem(&CRefname, MYCP, MYRECORD.MYURL);
   &CRef.Description = &CRefname;

/* Set dates */
&CRef.ValidFrom = %Date;
&ToDate = AddToDate(%Date, 1, 1, 0);
&CRef.ValidTo = &ToDate;

/* Set content reference  types */
&CRef.UsageType = "TARG";   /* Target content reference */
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
&CRef.URLType = "UPGE";     /* Component type of content reference */
&CRef.StorageType = "RMTE";  /* Template is remote. */
&CRef.Template = "EXPENSES_TEMPLATE";      /* name of template */
&CRef.TemplateType = "HTML";   /* type of Template */
/* Set URL */
&CRef.URL = "ICType=Panel&Menu=MANAGE_EXPENSES&Market=GBL&Component=APPROVE_FINAL"

/* Save the content reference */

&CRef.Save();
```

To add a content reference:

1. Get a Session object and a PortalRegistry.

   Before you can access a PortalRegistry object, you must get a session object. The session controls access to the registry, provides error tracing, enables you to set the runtime environment, and so on. Because you want to use the existing session, use the %Session system variable (instead of the GetSession function.) In addition, you want to get a PortalRegistry. Using the GetPortalRegistry method returns a reference to an unpopulated PortalRegistry object.

   ```
   &MyPortal = %Session.GetPortalRegistry();
   ```

2. Open the PortalRegistry.

   After you get a PortalRegistry object, you want to open it, that is, populate it with data. Use the Open method to do this. The Open method returns a Boolean value, and this example uses that value to do error checking to make sure that the PortalRegistry is actually opened. In addition, the name of the PortalRegistry is kept in the record MYRECORD, in the field PORTAL_NAME.

   ```
   If NOT &MyPortal.Open(MYRECORD.PORTAL_NAME) Then
      /* Do error handling */
   End-if;
   ```

3. Access the folder collection.

   One of the strengths of dot notation is being able to string together many methods and properties into a single line of code. The result of this single line of code is to return a reference to the folder collection within the folder.

   ```
   &Fldr = &MyPortal.RootFolder.Folders.ItemByName("Expenses").Folders.ItemByName⇒
   ("Approve Expenses");
   ```

   The Adding a Folder example has more explanation on the break down of this line of code.

4. Add the content reference.

   You can only add content references from the collection of content references for the folder. After you have the content reference collection, use the InsertItem method to add the content reference. The ContentProvider for this content reference is named MYCP. The URL is stored in the record MYRECORD in the field MYURL.

   ```
   &CRef = &Fldr.ContentRefs.InsertItem(&CRefname, MYCP, MYRECORD.MYURL);
   &CRef.Description = &CRefname;
   ```

   Note that the InsertItem method adds the content reference to the database as soon as it's executed. You could check for errors at this point to see if the content reference was added correctly.

5. Set the ValidFrom and ValidTo dates.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

For this example, the content reference should be accessible from the date it's created, so the example sets the ValidFrom property to be today's date.

When you first create a content reference, the ValidTo date, that is, the date that this content reference "expires", is set to null, that is an empty string. This means it never expires. In this example, we set the ValidTo date to one year and one day after the current date.

```
&CRef.ValidFrom = %Date;
&ToDate = AddToDate(%Date, 1, 1, 0);
&CRef.ValidTo = &ToDate;
```

6. Set the type parameters.

   Many content reference properties work together to set the type of content reference.

   In this example, the content reference is a target. It's a component type of content reference, which means it's a PeopleSoft definition. The template to be used for displaying this content reference is stored remotely, its name is EXPENSES_TEMPLATE, and it's an HTML template.

```
&CRef.UsageType = "TARG"; /* Target content reference */
&CRef.URLType = "UPGE"; /* Component type of content reference */
&CRef.StorageType = "RMTE"; /* Template is remote. */
&CRef.Template = "EXPENSES_TEMPLATE"; /* name of template */
&CRef.TemplateType = "HTML"; /* type of Template */
```

7. Set the URL.

   The URL property of the content reference indicates where the content actually is. As this content reference is referencing a page, the URL has a specific format to indicate which page.

```
&CRef.URL = "ICType=Panel&Menu=MANAGE_EXPENSES&Market=GBL&Component=APPROVE_FI⇒
NAL"
```

8. Save the content reference.

   After you have finished adding the content reference, you should save it.

```
&CRef.Save();
```

   You may want to check for errors after you save each content reference.

See Adding a Folder.

Setting Permissions Using the PermissionValue Object

The following code example adds permissions for a folder through the PermissionValue object.

The following is the complete code sample: the steps explain each line.

```
Local ApiObject &MyPortal;
Local ApiObject &UserFldr;
Local ApiObject &PermV, &PermVColl;

&MyPortal = %Session.GetPortalRegistry();

If NOT &MyPortal.Open(MYRECORD.PORTAL_NAME) Then
   /* Do error handling */
End-if;

&UserFldr = &MyPortal.RootFolder.Folders.ItemByName("Users");
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
&CascadedColl = &UserFldr.CascadedPermissions;

&PermV = &CascadedColl.ItemByName("VENDOR1");

If NOT &PermV Then
   &PermVColl = &UserFldr.Permissions;
   &PermVColl.InsertItem("VENDOR1");
   &UserFldr.Save();
End-If;
```

To set permissions for a folder, using the PermissionValue object:

1. Get a Session object and a PortalRegistry.

   Before you can access a PortalRegistry object, you must get a session object. The session controls access to the registry, provides error tracing, enables you to set the runtime environment, and so on. Because you want to use the existing session, use the %Session system variable (instead of the GetSession function.) In addition, you want to get a PortalRegistry. Using the GetPortalRegistry method returns a reference to an unpopulated PortalRegistry object.

   ```
   &MyPortal = %Session.GetPortalRegistry();
   ```

2. Open the PortalRegistry.

   After you get a PortalRegistry object, you want to open it, that is, populate it with data. Use the Open method to do this. The Open method returns a Boolean value, and this example uses that value to do error checking to make sure that the PortalRegistry is actually opened. In addition, the name of the PortalRegistry is kept in the record MYRECORD, in the field PORTAL_NAME.

   ```
   If NOT &MyPortal.Open(MYRECORD.PORTAL_NAME) Then
      /* Do error handling */
   End-if;
   ```

3. Access the User folder.

   One of the strengths of dot notation is being able to string together many methods and properties into a single line of code. The result of this single line of code is to return a reference to the folder named Users.

   ```
   &UserFldr = &MyPortal.RootFolder.Folders.ItemByName("Users");
   ```

4. Access the entire, cascaded PermissionValue collection.

   There are two types of PermissionValue collections you can access for a folder.

   - One contains only the permission list values that are set at that folder. This collection is returned with the Permissions property.
   - The other contains all the permission list values for folder, that is, it contains any permission list values set in any parent folder and cascaded. This collection is returned with the CascadedPermissions property.

Note: You *cannot* add any PermissionValue objects to a collection returned by the CascadedPermissions property. You can add values only to the collection returned by the Permissions property.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This example uses the CascadedPermissions collection to check if the permission exists, because we don't want to add a permission if it already exists. Then it uses the Permissions collection to add the value.

```
&CascadedColl = &UserFldr.CascadedPermissions;
```

1. Check to see if the permission list value exits.

   Before adding the new PermissionValue object, you want to make sure one by that name doesn't already exist.

   ```
   &PermV = &CascadedColl.ItemByName("VENDOR1");
   ```

2. If the PermissionValue doesn't exist, add it.

   The ItemByName returns a reference to a PermissionValue object if it exists, or NULL if it doesn't. So this example checks for NULL, and adds the PermissionValue if it doesn't exist.

   Notice that this example is *not* changing the Cascaded property with the PermissionValue object. The default value for a new PermissionValue object is False. As this example does not want to cascade the permissions for this permission list, it retains the default value.

   In addition, if the PermissionValue object is added, the folder is saved. The InsertItem method executes only after the parent object, the folder, is saved.

   ```
   If NOT &PermV Then
      &PermVColl = &UserFldr.Permissions;
      &PermVColl.InsertItem("VENDOR1");
      &UserFldr.Save();
   End-If;
   ```

   You may want to check for errors after you save the folder.

See Permissions, CascadedPermissions.

See Using PermissionValue, RolePermissionValue, Cascading Permissions and CascadingRolePermissions.

Using Attributes

The following example uses attributes for a folder to determine what is displayed to an end-user. The end-user still has access to the content, however, it isn't displayed. This program doesn't discuss how to hide or display content: it just shows the function used to determine if a folder should be displayed.

The following is the complete code sample: the steps explain each line.

```
Function checkVisible(&FolderId As ApiObject) Returns Boolean
   &colAttrib = &FolderId.Attributes;

   If &colAttrib.ItemByName("PORTAL_HIDE_FROM_NAV") <> Null Then
      If &colAttrib.ItemByName("PORTAL_HIDE_FROM_NAV").value = "TRUE" Then
             &display = False;
      End-If;
   End-If;

    Return &display;

End-Function;
```

To use attributes for a folder:

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

1. Access the folder attribute collection.

   A reference to a folder is passed into the function. Then the example uses the Attributes property on the folder to access the attribute collection for the folder.

   ```
   &colAttrib = &FolderId.Attributes;
   ```

2. Check to see if the folder should be hidden.

   This step is actually two checks. The first check is to see if there is an attribute with the folder called PORTAL_HIDE_FROM_NAV. If the folder has such an attribute, the second check determines the value of this attribute. If both are true, the folder should be hidden, so the variable &display is set to True, and returned.

   ```
   If &colAttrib.ItemByName("PORTAL_HIDE_FROM_NAV") <> Null Then
         If &colAttrib.ItemByName("PORTAL_HIDE_FROM_NAV").value = "TRUE" Then
                &display = False;
         End-If;
      End-If;

       Return &display;
   ```

Visual Basic Example

The following is an example referencing a PortalRegistry object using Visual Basic.

```
Dim oCref As ContentRef
Dim oCrefColl As ContentRefCollection

Set oSession = CreateObject("PeopleSoft.Session")
iResult = oSession.Connect(1, AppServStr, OperID, OperPasswd, 0)

Set oPortal = oSession.GetPortalRegistry
iResult = oPortal.Open("PORTAL")

Set oCrefColl = oPortal.RootFolder.ContentRefs
Set oCref = oCrefColl.InsertItem("papi012")
iResult = oPortal.Close

iResult = oPortal.Open("PORTAL")

Set oCref = oPortal.FindCRefByName("papi012")

oPortal.Close
oSession.Disconnect
Exit Sub
```

C/C++ Example

The following is a C/C++ example.

```
/*********************************************************************
*                                                                    *
* psportal_test.cpp                                                  *
*                                                                    *
*********************************************************************
*                                                                    *
*               Confidentiality Information:                         *
*                                                                    *
* This module is the confidential and proprietary information of
* PeopleSoft, Inc.; it is not to be copied, reproduced, or
* transmitted in any form, by any means, in whole or in part,
* nor is it to be used for any purpose other than that for which it
* is expressly provided without the written
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
* permission of PeopleSoft.
*                                                                      *
* Copyright (c) 1988-1999 PeopleSoft, Inc.  All Rights Reserved.       *
*                                                                      *
************************************************************************
*                                                                      *
* SourceSafe Information:                                              *
*                                                                      *
* $Logfile::                                                          $*
* $Revision::                                                         $*
* $Date::                                                             $*
*                                                                      *
************************************************************************/
/***********************************************************************
*       includes                                                       *
***********************************************************************/

#ifdef PS_WIN32
#include "stdafx.h"
#endif

#include "bcdef.h"
#include "apiadapterdef.h"
#include "peoplesoft_peoplesoft_i.h"

#include <stdio.h>
#include <iostream.h>
#include <wchar.h>

/***********************************************************************
*       general defines and macros                                     *
***********************************************************************/

/***********************************************************************
*       globals                                                        *
***********************************************************************/
HPSAPI_SESSION                                                 hSession;


/***********************************************************************
*       function prototypes                                            *
***********************************************************************/
void DisconnectSession();
void GetFolder(HPSAPI_SESSION hSession, LPTSTR pszPortalName);
void OutError(HPSAPI_SESSION hSession);

/***********************************************************************
* Function:     main                                                   *
*                                                                      *
* Description:                                                         *
*                                                                      *
* Returns:                                                             *
************************************************************************/
void main(int argc, char* argv[])
{
    // Declare variables
    PSAPIVARBLOB    blobExtra;
    TCHAR szServer[80] = _T("//LCHE0110:900");
    TCHAR szUserid[30] = _T("PTMO");
    TCHAR szUserPswd[80] = _T("PT");
    TCHAR szPortalName[80] = _T("PORTAL");

    memset(&blobExtra, 0, sizeof(PSAPIVARBLOB));

    // Establish a PeopleSoft Session.
   HPSAPI_SESSION hSession = PeopleSoft_Session_Create();

    if (PeopleSoft_Session_Connect(hSession, 1, szServer, szUserid, szUserPswd, blo⇒
bExtra))
    {
        GetFolder(hSession, szPortalName);
```

```
    }
    else
     {
       // Connect to AppServer Failed. Error out.
         if (PeopleSoft_Session_GetErrorPending(hSession))
       {
          wprintf(L"\nConnect to AppServer Failed.\n");
          OutError(hSession);
       }
       else
          wprintf(L"No error pending from session.\n");
     }
     DisconnectSession();
}


/*********************************************************************
*       function implementations                                     *
*********************************************************************/
/*********************************************************************
* Function:     DisconnectSession                                    *
*                                                                    *
* Description:  Disconnects the Session object.                      *
*                                                                    *
* Returns:      None                                                 *
*********************************************************************/
void DisconnectSession()
{
    // Disconnect current session to free memory and session variables.
    if (hSession)
    {
        if (PeopleSoft_Session_Disconnect(hSession))
        {
            PeopleSoft_Session_Release(hSession);
        }
        else
        {
            wprintf(L"Disconnect to AppServer Failed.\n");
        }
    }
}


/*********************************************************************
* Function:     GetFolder                                            *
*                                                                    *
* Description:  Get root folder and display folder name              *
*                                                                    *
* Returns:      None                                                 *
*********************************************************************/
void GetFolder(HPSAPI_SESSION hSession, LPTSTR pszPortalName)
{
    LPTSTR                  szStr;
    HPSAPI_PORTALREGISTRY   hPortal;
    HPSAPI_FOLDER           hRootFolder;

    hPortal=(HPSAPI_PORTALREGISTRY) PeopleSoft_Session_GetPortalRegistry(hSession);
    PortalRegistry_PortalRegistry_Open(hPortal, pszPortalName);
    if (PortalRegistry_PortalRegistry_Open(hPortal, pszPortalName) == false)
        _tprintf(_T("Open portal failed\n"));
    else
    {
        hRootFolder = PortalRegistry_PortalRegistry_GetRootFolder(hPortal);
        szStr = PortalRegistry_Folder_GetName(hRootFolder);
        _tprintf(_T("root folder name = %s\n"), szStr);
    }
}


/*********************************************************************
* Function:     OutError                                             *
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
*                                                                    *
* Description:  Output error message from session psMessage object   *
*                                                                    *
* Returns:      None                                                 *
**********************************************************************/
void OutError(HPSAPI_SESSION hSession)
{
    LPTSTR                  szStr;
    HPSAPI_PSMESSAGECOLLECTION hMsgColl;
   HPSAPI_PSMESSAGE hMsg;


    hMsgColl=(HPSAPI_PSMESSAGECOLLECTION) PeopleSoft_Session_GetPSMessages(hSession⇒
);

   wprintf(L"Get psMessage collection ok.\n");

   int i;
   PSI32 count;
   count=(PSI32) PeopleSoft_PSMessageCollection_GetCount;
   wprintf(L"Count= %d\n", count);

   for (i=0; i<count; i++)
   {
      hMsg=(HPSAPI_PSMESSAGE) PeopleSoft_PSMessageCollection_Item(hMsgColl, i);
      szStr=PeopleSoft_PSMessage_GetText(hMsg);
      wprintf(L"\nMessage from session: %s\n",szStr);
   }

}
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Chapter 35

PostReport Class

PostReport Class Overview

The PostReport class provides properties and method for posting reports to the Report Repository. This class enables you to create reports outside of Process Scheduler and have them posted in the Report Repository.

The request to post reports creates an entry to the Report Manager table. The Distribution Agent polls the Report Manager table for any new requests and proceeds with any request it finds by transferring the files to the repository server. The report can then be accessed from the Report Manager after the Distribution Agent successfully processes the post request.

Related Links

"Understanding Report Manager" (PeopleTools 8.54: Process Scheduler)

Determining the Distribution List

Use the AddDistributionOption method to authorize users to view the report from the Report Manager. This function enables you to grant access to the report either specifying a User ID or Role. However, if no distribution list is specified in the request, the class queries the system for the distribution list as follows:

1. If the Process Instance is specified, the system checks for the distribution list in the Process Request table. The system assumes in this case that the request was scheduled through the Process Request Dialog, but was processed by a third-party scheduler.
2. If a Process Name and Process Type properties were specified, the system checks if a distribution list was predefined in the Process Definition table.
3. If no list was found using the above queries, the user who submitted the request has sole access to the report.

Data Type of a PostReport Object

A PostReport object is declared using the PostReport data type. For example:

```
Local PostReport &POSTRQST;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Scope of a PostReport Object

A PostReport object can only be instantiated from PeopleCode. However, if you need to access the Process Schedule Manger from outside of PeopleCode, like in a Visual Basic program, you can use the Process Schedule Manager API.

This object can be used anywhere you have PeopleCode, that is, in an application class, Component Interface PeopleCode, record field PeopleCode, and so on.

Related Links

"PeopleSoft Process Scheduler" (PeopleTools 8.54: Process Scheduler)

PostReport Class Built-in Function

"SetPostReport" (PeopleTools 8.54: PeopleCode Language Reference)

PostReport Class Methods

In this section, we discuss the PostReport class methods. The methods are discussed in alphabetical order.

AddDistributionOption

Syntax

AddDistributionOption(*DistIdType*, *DistId*)

Description

Use the AddDistributionOption method to specify the users authorized to view the report once it is available in the Report Manager.

Parameters

DistIdType Specify the distribution ID type as a string. This identifies if the value passed in the DistID is either a user or role. Values for this parameter are:

- User
- Role

DistID Specify the distribution ID as a string.

Returns

Returns a number: 0 if successful, 1 if the system detected an error in the parameter passed.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

The following example grants access to the VP1 user and all users associated with the MANAGERS role.

```
&POSTRQST.AddDistributionOption("User", "QEDMO" );
&POSTRQST.AddDistributionOption("Role", "MANAGERS");
```

Put

Syntax

Put()

Description

The Put method inserts a request in the Report Manager table which runs according to the values in the properties of the PostReport object. In order to successfully schedule a process or job, certain properties are required.

Parameters

None.

Returns

None. If you want to verify that the method executed successfully, check the value of the Status property.

Example

```
&POSTRQST.Put();
&RPTINSTANCE = &POSTRQST.ReportId;
If (&RPTINSTANCE > 0) Then
      MessageBox(0, "", 63, 119, "Successfully processed request with Rpt. ID %1 fo⇒
r Process %2 to post from directory %3", &RPTINSTANCE, &POSTRQST.ProcessName, &POST⇒
RQST.SourceReportPath);
   Else
      MessageBox(0, "", 63, 122, "Not successful for process request for Process %1⇒
 to post from directory %2", &POSTRQST.ProcessName, &POSTRQST.SourceReportPath);
End-If;
```

Related Links

"SetPostReport" (PeopleTools 8.54: PeopleCode Language Reference)

PostReport Class Properties

In this section, we discuss the PostReport class properties. The properties are discussed in alphabetical order.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ExpirationDate

Description

This property specifies the date the report will be deleted from the Report Manager table. If the expiration date is not specified, the system calculates the expiration date based on the Retention Days specified in the Process Scheduler's System Settings.

This property is read-write.

Example

```
&MYRQST.ExpirationDate = "2003/01/01";
```

Related Links

"Defining System Settings" (PeopleTools 8.54: Process Scheduler)

OutDestFormat

Description

This property specifies the output format of the file that is posted to the Report Repository. If format is not specified, the system determines the format based on the extension of the file being posted to the Report Repository.

This property is read-write.

Example

```
&MYRQST.OutDestFormat = "PDF";
```

Related Links

Values for Output Type and Format

ProcessInstance

Description

This property specifies the instance number assigned to request. This property is only required if the report was initially submitted through the Process Request Dialog, but was processed by a third-party scheduler.

This property is read-write.

Related Links

Determining the Distribution List

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ProcessName

Description

This property specifies the name of a predefined process as a string.

This property is read-write.

Example

```
&MYRQST.ProcessName = "XRFWIN";
```

Related Links

ProcessType
RunControlID

ProcessType

Description

This property specifies the name of a predefined process type as a string.

This property is read-write.

Example

Note that spaces are included in the string for ProcessType.

```
&MYRQST.ProcessType = "Application Engine";
```

Related Links

ProcessName
RunControlID

ReportDescr

Description

This property specifies the description as a string.

If the ReportDescr property is not specified, and both Process Name and Process Type are not null, the description is extracted from the Process Definition table.

This property is read-write.

Example

```
&MYRQST.ReportDescr = "Panel Cross Reference Report";
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ReportFolder

Description

This property specifies the name of the report folder as a string. If you specify a folder, the folder that you specify must have already been defined using Process Scheduler's Report Folders Administration.

This property is read-write.

Related Links

"Understanding Report Folders" (PeopleTools 8.54: Process Scheduler)

ReportId

Description

This property is a system-generated identification number. The system assigns a ReportId after the Put method processed the request.

This property is read-write.

Example

```
&MYRQST.Put();
if &MYRQST.ReportId > 0 then
     MessageBox(o, "", 63, 119, "Sucessfully processed request with Rpt. ID %1", &M⇒
YRQST.ReportId);
Else
    /* do error processing */
End-If;
```

ServerName

Description

This property specifies the Process Scheduler Server name that posts the report. This property takes a string value.

This property is read-write.

Example

```
&MYRQST.ServerName = "PSNT";
```

Related Links

"Defining System Settings" (PeopleTools 8.54: Process Scheduler)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SourceReportPath

Description

This property specifies the path that contains the source report. You need to specify an absolute path.

This property is read-write.

PostReport Class Examples

The following example posts files found in the directory ‘c:\temp\SQRDIR’ and can be accessed by VP1 and users in the MANAGERS role.

```
Local PostReport &RPTINFO;
   Local number &RPTINSTANCE

   /*******************************************************************
   * Construct a PostReport Object.                                   *
   *******************************************************************/
   &RPTINFO = SetPostReport();

   &RPTINFO.ProcessName = "GLS7009";
   &RPTINFO.ProcessType = "SQR Report";
   &RPTINFO.ReportFolder = "Financial";
   &RPTINFO.SourceReportPath = "c:\temp\SQRDIR";
   &RPTINFO.ExpirationDate = "2005/01/01";
   &RPTINFO.ReportDescr = "Journal Posting Summary Report";
   &RPTINFO.ServerName = "PSNT";

   &RPTINFO.AddDistributionOption("USER", "VP1");
   &RPTINFO.AddDistributionOption("ROLE", "MANAGERS");

   &RPTINFO.Put();
   &RPTINSTANCE = &RPTINFO.ReportId;

   If (&RPTINSTANCE > 0) Then
      MessageBox(0, "", 63, 119, "Successfully processed request with Rpt. ID %1 fo⇒
r Process %2 to post from directory %3", &RPTINSTANCE, &RPTINFO.ProcessName, &RPTIN⇒
FO.SourceReportPath);
   Else
      MessageBox(0, "", 63, 122, "Not successful for process request for Process %1⇒
 to post from directory %2", &RPTINFO.ProcessName, &RPTINFO.SourceReportPath);
   End-If;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Chapter 36

Process Request Classes

Understanding Process Request Classes

The ProcessRequest class provides properties and a method for scheduling a pre-defined process or job. You must define the process or the job (using Process Scheduler Manager) *before* you can schedule it using the ProcessRequest class.

The properties of this class contain the same values as those required by Process Scheduler Manager for scheduling a process or job. Values you provide for these properties may override the equivalent values set in Process Scheduler Manager, depending on the override settings you make in PeopleSoft Process Scheduler pages.

Starting with PeopleSoft 8.4, PeopleSoft supports only the ProcessRequest class to schedule a process or a job in PeopleCode. The ScheduleProcess PeopleCode function is no longer supported. Any existing PeopleCode functions containing this deprecated function must be modified to use the ProcessRequest class to schedule a request.

This topic assumes that the reader has working knowledge of PeopleSoft Process Scheduler.

Related Links

ProcessRequest Class Examples

Data Type of a ProcessRequest Object

A ProcessRequest object is declared using the ProcessRequest data type. For example:

```
Local ProcessRequest &RQST;
```

Scope of a ProcessRequest Object

A ProcessRequest object can be instantiated only from PeopleCode. However, if you need to access the Process Schedule Manager from outside of PeopleCode, for example, in a Visual Basic program, you can use the Process Schedule Manager API.

This object can be used anywhere you have PeopleCode, that is, in an application class, Component Interface PeopleCode, record field PeopleCode, and so on.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Options for Items In Jobs and Jobsets

A key feature of PeopleSoft Process Scheduler is the option to create a Job Definition consisting of other jobs. A job containing a job is called a *jobset*. Process Scheduler Server schedules the items within these jobs according to how the jobset is defined through the Process Scheduler Manager.

The ProcessRequest class requires the following properties to handle jobsets:

- JobName: indicates the name of the job that an item belongs to.
- PrcsItemLevel: indicates a job item's process item level within a jobset.
- JobSeqNo: indicates a job item's job sequence number within the Process Item Level.

The following is a simple example of a job containing only a single process:

Image: Sample job with single process

This example illustrates the fields and controls on the Sample job with single process. You can find definitions for the fields and controls later on this page.

Process	*PrcsItemLevel*	*JobName*	*JobSeqNo*
3SQR	0		0
XRFAPFL	1	3SQR	1
XRFPANEL	2	3SQR	2
XRFPCFL	3	3SQR	3

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The following is an example of a jobset containing multiple jobs:

Image: Sample jobset containing multiple jobs

This example illustrates the fields and controls on the Sample jobset containing multiple jobs. You can find definitions for the fields and controls later on this page.

Process	*PrcsItemLevel*	*JobName*	*JobSeqNo*
MULTIJOB	0		0
AP_APY2015	1	MULTIJOB	1
AP_PSTPYMNT	1	MULTIJOB	2
BI JOBS	1	MULTIJOB	3
BIJOB01	2	BI JOBS	1
BIIVC000	3	BIJOB01	1
BIIVCLN	3	BIJOB01	2

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Process	*PrcsItemLevel*	*JobName*	*JobSeqNo*
BIIVCPN	3	BIJOB01	3
BIIVCEN	3	BIJOB01	4
BIJOB02	2	MULTIJOB	2
BIIVC000	3	BIJOB02	1
BIIVCLC	3	BIJOB02	2
BIIVCPC	3	BIJOB02	3
BIIVCEN	3	BIJOB02	4
BIJOB03	2	MULTIJOB	3
BIIVC000	3	BIJOB03	1
BIIVCLN	3	BIJOB03	2
BIIVCPN	3	BIJOB03	3
BIIVCEN	3	BIJOB03	4
BICURCNV	3	BIJOB03	5
BILDAR01	3	BIJOB03	6
BILDGL01	3	BIJOB03	7
BIGNAP01	3	BIJOB03	8

All the class methods that are used to change options for items within a job or jobset, use these attributes as optional parameters.

If a method is used without specifying any of these parameters, the system assumes the changes apply to *all* items within a jobset.

If one or more of these attributes are specified, the method applies the changes to items matching the value of these attributes.

In the case where a JobName is specified, the changes apply to all items within the specified job.

Specific methods used to manipulate options within a job or jobset include:

- AddDistributionOption
- SetEmailOption
- SetItemFolder
- SetOutputOption

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

When manipulating the options within a job or jobset, you must specify the process type and process name in the CreateProcessRequest function when instantiating a ProcessRequest object. This is required as the class needs to retrieve the job item information from the job definition for a specific job or jobset. The class uses this information to alter items within the job or jobset based on subsequent method calls made prior to scheduling the request. If the process type and process name are not specified when instantiating the ProcessRequest object, all PeopleCode programs trying to use any of the methods return an error message:

```
The method can not be used because the ProcessRequest is not properly initialized
```

In the previous jobset example, the ProcessRequest must be instantiated as follows:

```
Local ProcessRequest &RQST;

&RQST = CreateProcessRequest("PSJob", "MULTIJOB");
```

The following code examples use the previous example MULTIJOB, and show how items can be altered within a job or jobset:

- Change all items in the Jobset to “Web” with reports generated in PDF format:

  ```
  &RQST.SetOutputOption("Web", "PDF", "", "MULTIJOB");
  ```

  Alternatively, this can also be coded as follows:

  ```
  &RQST.SetOutputOption("Web", "PDF", "");
  ```

- Change the output option for job BIJOB02 to “Email” with reports generated in HTM format:

  ```
  &RQST.SetOutputOption("Email", "HTM", ", "BIJOB02");
  ```

- Change the output option for BIIVCPN in job BIJOB01 to “File” in LP (LinePrinter) format:

  ```
  &RQST.SetOutputOption("File", "LP", "BIJOB01", 3, 3);
  ```

- Change all items in level three to “Web” in PS (PostScript) format:

  ```
  &RQST.SetOutputOption("Web", "PS", "", "", 3);
  ```

Values for Output Type and Format

The values for output type and format are based on the generic process type assigned to a process type definition. The following table provides a cross-reference listing for all delivered process type definitions.

Generic Process Type	***Process Type***
AppEngine	Application Engine, Optimization Engine
COBOL	COBOL SQL
Crystal	Crystal, Crystal Check
Cube	CubeBuilder, HyperCube Builder
SQR	SQR Process, SQR Report

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Generic Process Type	*Process Type*
Winword	Winword
nVision	nVision, nVision-Report, nVision-ReportBook
Data Mover	Data Mover
Other	Essbase

The following table lists all the values for OutDestType delivered with PeopleTools.

However, the values and defaults can be customized through Process Scheduler Manager. Please refer to the PeopleSoft Process Scheduler documentation for additional information on how to accurately determine the values for your system.

Generic ProcessType	*Valid OutDestTypes*	*Defaults*
AppEngine	FILE, WEB, WINDOW	WEB
COBOL	NONE, WINDOW, WEB	NONE
Crystal	WEB, WINDOW, EMAIL, FILE, PRINTER	WEB
Cube	NONE	NONE
nVision	WEB, WINDOW, EMAIL, FILE, PRINTER, DEFAULT	DEFAULT
SQR	WEB, WINDOW, EMAIL, FILE, PRINTER	WEB
WinWord	WINDOW, WEB	WEB
Data Mover	WEB,WINDOW, FILE	WEB
OTHER	WEB, WINDOW, EMAIL, FILE, PRINTER, NONE	NONE

Similar to the OutDestType, the formats and defaults for a generic process type can be customized through Process Scheduler Manager. The following table lists the values and defaults as delivered.

Generic ProcessType	*OutDestType*	*Valid OutDestFormats*	*Default*
AppEngine	WINDOW	PDF, XLS, TXT, HTM	TXT
AppEngine	FILE	PDF, XLS, TXT, HTM	TXT
AppEngine	WEB	PDF, XLS, TXT, HTM	TXT
COBOL	NONE	NONE	NONE
COBOL	WEB	TXT	TXT

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Generic ProcessType	*OutDestType*	*Valid OutDestFormats*	*Default*
COBOL	WINDOW	TXT	TXT
Crystal	PRINTER	RPT	RPT
Crystal	FILE	RPT, RTF, TXT, PDF, HTM, XLS, DOC	PDF
Crystal	WINDOW	RPT, RTF, TXT, PDF, HTM, XLS, DOC	PDF
Crystal	WEB	RPT, RTF, TXT, PDF, HTM, XLS, DOC	PDF
Crystal	EMAIL	RPT, RTF, TXT, PDF, HTM, XLS, DOC	PDF
Cube	NONE	NONE	NONE
Data Mover	FILE	TXT	TXT
Data Mover	WINDOW	TXT	TXT
Data Mover	WEB	TXT	TXT
nVision	EMAIL	HTM, XLS	XLS
nVision	FILE	HTM, XLS	XLS
nVision	PRINTER	HTM, XLS	XLS
nVision	WINDOW	HTM, XLS	XLS
nVision	WEB	HTM, XLS	XLS
nVision	DEFAULT	DEFAULT	DEFAULT
SQR	EMAIL	CSV, HP, HTM, LP, PDF, PS, SPF,OTHER	PDF
SQR	FILE	CSV, HP, HTM, LP, PDF, PS, SPF,OTHER	PDF
SQR	PRINTER	HP, LP, PS, WP	PS
SQR	WEB	CSV, HP, HTM, LP, PDF, PS, SPF,OTHER	WEB
SQR	WINDOW	CSV, HP, HTM, LP, PDF, PS, SPF,OTHER	WEB
WinWord	NONE	NONE	NONE
WinWord	WEB	DOC	DOC

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Generic ProcessType	*OutDestType*	*Valid OutDestFormats*	*Default*
WinWord	WINDOW	DOC	DOC
OTHER	NONE	NONE	NONE

Alternative Options to Specify Email or Web Attributes

To set the email or web attributes in PeopleTools versions prior to release 8.4, your PeopleCode program was similar to the following:

To Set Attributes for Web (Prior to 8.4)

The following example shows how to set web attributes in PeopleTools versions prior to release 8.4:

```
&RQST.OutDestType = "Web";
&RQST.OutDestFormat = "PDF";
&RQST.OutDest = "User : VP1,Role :Managers";
```

Set Attributes for Email (Prior to 8.4)

The following example shows how to set email attributes in PeopleTools versions prior to release 8.4:

```
Local string &Subject ;
Local string &Text;

&Subject = "SQR Report:  Cross Reference Listing";
&Text = "This text will be displayed as the text of this email ";
&RQST.OutDestType = "Email";
&RQST.OutDestFormat = "PDF";
&RQST.OutDest = "User : VP1,Role : MANAGERS";
&RQST.EmailSubject = &Subject;
&RQST.EmailText = &Text;
&RQST.EmailAttachLog = False;
```

Set Attribute for Web (8.4 and Later)

The following example shows how to set web attributes in PeopleTools versions release 8.4 and later:

```
&RQST.SetOutputOption("Web", "PDF", "");
&RQST.AddDistributionOption("User", "QEDMO");
&RQST.AddDistributionOption("Role", "MANAGERS");
```

Set Attribute for Email (8.4 and Later)

The following example shows how to set web attributes in PeopleTools versions release 8.4 and later:

```
Local string &Subject ;
Local string &Text;

&Subject = "SQR Report:  Cross Reference Listing";
&Text = "This text will be displayed as the text of this email ";
&RQST.SetOutputOption("Email", "PDF", "");
&RQST.SetEmailOption(&Subject, &Text, "abc@xyz.com", "False", "False");
&RQST.AddDistributionOption("User", "QEDMO");
&RQST.AddDistributionOption("Role", "MANAGERS");
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

File Dependant Processing

You can define a process to be file dependent, which means associating a file with a process that gets scheduled once the system detects the presence of the file.

You can use the PrcsApi class methods for detecting files associated with a process, as well as for displaying additional messages about the process as it's running.

The PrcsApi class is an Application Package class that you must import into your PeopleCode in order to use its methods.

For example, you could use the PrcsApi class with a Application Engine program. In the Application Engine process PROCESS_EDI, you could create a file dependency (using the FileName ProcessRequest property) and make the process dependent on the file /vendor/edi*.data.

On 10/23, the system detects the file /vendor/edi_1023.data and schedules the process PROCESS_EDI. In the Application Engine program, you can refer to the file that started the process using the getAllFileNames PrcsApi class method.

On 10/24, the system detects the file /vendor/edi_1024.data and schedules the process PROCESS_EDI. The process is started from a different file, and can access that file, so duplicate processing doesn't occur.

Related Links

PrcsApi Class

ProcessRequest Class Built-in Functions

"CreateProcessRequest" (PeopleTools 8.54: PeopleCode Language Reference)

"GetNextProcessInstance" (PeopleTools 8.54: PeopleCode Language Reference)

"SetupScheduleDefnItem" (PeopleTools 8.54: PeopleCode Language Reference)

ProcessRequest Class Methods

In this section, we discuss the ProcessRequest class methods. The methods are discussed in alphabetical order.

AddDistributionOption

Syntax

AddDistributionOption(*DistIdType*, *DistId* [, *JobName*] [, *PrcsItemLevel*] [, *JobSeqNo*] [, *ItemJobSeq*])

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the AddDistributionOption method to set the distribution options for any job item in the main job. Distribution options enable you to distribute output in different formats (HTML, PDF, Excel, and so on) to other users based on their user ID or role ID.

This function is valid only if the output destination for the request is routed either to Web or Email.

Parameters

DistIdType Specify the distribution ID type as a string. This identifies if the value passed in the DistID is either a user or role. Values for this parameter are:

- User
- Role

DistID Specify the distribution ID as a string.

JobName Specify the name of the job that this item belongs to as a string.

PrcsItemLevel Specify the job item's process item level within the main job as a number.

JobSeqNo Specify the job item's job sequence number within the process item level as a number.

ItemJobSeq Specify the job item’s sequence within its parent job as a number

Returns

Returns a number: 0 if successful, 1 if system detected an error in the parameter passed.

Example

The following example grants access to the QEDMO user all reports in MULTIJOB from the Web, while users with role of MANAGERS have access to reports created in the BIJOB03 job.

```
&RQST.SetOutputOption("Web", "PDF", "");
&RQST.AddDistributionOption("User", "QEDMO", "MULTIJOB" );
&RQST.AddDistributionOption("Role", "MANAGERS", "BIJOB03");
```

Related Links

SetEmailOption

SetOutputOption

AddNotifyInfo

Syntax

AddNotifyInfo(*field_name*, *field_value* [, *JobName*] [, *PrcsItemLevel*] [, *JobSeqNo*])

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the AddNotifyInfo method to specify name-value pair data to be included in the process status notification message.

Parameters

field_name	Specify the field name data as a string.
field_value	Specify the field value data as a string.
JobName	Specify the name of the job that this item belongs to as a string.
PrcsItemLevel	Specify the job item's process item level within the main job as a number.
JobSeqNo	Specify the job item's job sequence number within the process item level as a number.

Returns

None.

Example

```
&RQST.AddNotifyInfo("AEMINITEST Name", "Status");
&RQST.AddNotifyInfo("AEMINITEST Descr", "Status Notify");
&RQST.AddNotifyInfo("AEMINITEST OutType", "EMAIL");
```

Related Links

SetNotifyAppMethod

SetNotifyService

PrintJobHTMLRpt

Syntax

`PrintJobHTMLRpt``()`

Description

Use the PrintJobHTMLRpt method to generate an HTML report file displaying all items in a job or jobset in a tree as defined in the Job Definition component.

Parameters

None.

Returns

An HTML report as a string

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

The following code:

```
Local ProcessRequest &JobRQST;
Local string &sHTML;

&JobRQST = CreateProcessRequest("PSJob", "SQRXRF");
&sHTML = &JobRQST.PrintJobHTMLRpt();
```

generates the following HTML file:

Image: Example HTML file

The following image is an example of an HTML file generated after executing the above mentioned PeopleCode program:

Related Links

PrintJobRqstRpt
PrintSchdlHTMLRpt

PrintJobRqstRpt

Syntax

PrintJobRqstRpt(*ProcessInstance*, *ItemInstance* [, *PrintJobTree*] [, *PrintDistList*] [, *PrintNotifyList*] [, *PrintSystemMessage*] [, *PrintApplicationMessage*] [, *PrintParamList*])

Description

Use the PrintJobRqstRpt method to generate an HTML report file displaying the current status of a specific process, job, or jobset.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

ProcessInstance

Specify the ProcessInstance number assigned to the process, job, or jobset

ItemInstance

Specify either to display all items in a job or jobset, or just a specific item.

- To display all items, specify 0.
- To display a specific item, specify the ProcessInstance number assigned to that item.

  For a process, set this parameter to 0.

PrintJobTree

Specify whether to have the job tree displayed in the HTML report. This parameter takes a string value:

- "1" to display the tree.
- "0" to not display the tree.

  Default value is "1".

PrintDistList

Specify whether you want the list of Users and Roles who will be the recipient of a report generated for a job item displayed in the HTML report. This parameter takes a string value:

- "1" to display the list.
- "0" to not display the list.

  Default value is "0".

PrintSystemMessage

Specify whether you want to have the message specified from the Process Definition or Job Definition page displayed in the HTML report. This parameter takes a string value:

- "1" to display the system message.
- "0" to not display the system message.

  Default value is "0".

PrintApplicationMessage

Specify whether you want the application messages displayed in the HTML report. These are the application messages that can be viewed from the Message Log subpage of the Process Monitor Detail page. This parameter takes a string value:

- "1" to display application messages.
- "0" to not display application messages.

  Default value is "0".

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

PrintParamList

Specify whether you want the parameter list for a job item displayed in the HTML report. This parameter takes a string value:

- "1" to display the parameter list.
- "0" to display the parameter list.

  Default value is "0".

Returns

An HTML report as a string.

Example

The following PeopleCode program:

```
Local ProcessRequest &JobRQST;
Local string &sHTML;
Local string &sPRINT_JOBTREE;
Local string &sPRINT_DISTLIST;
Local string &sPRINT_SYSMESSAGE;
Local string &sPRINT_APPLMESSAGE;
Local string &sPRINT_PARAMLIST;

&sPRINT_JOBTREE = "0";
&sPRINT_DISTLIST = "1";
&sPRINT_SYSMESSAGE = "1";
&sPRINT_APPLMESSAGE = "1";
&sPRINT_PARAMLIST = "1";
&JobRQST = CreateProcessRequest();
&sHTML = &JobRQST.PrintJobRqstRpt(PMN_PRCSLIST.PRCSINSTANCE, 0, &sPRINT_JOBTREE, &s⇒
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
PRINT_DISTLIST, &sPRINT_SYSMESSAGE, &sPRINT_APPLMESSAGE, &sPRINT_PARAMLIST);
```

Image: Example HTML report

The following screen image is an example of a HTML report created after executing the above mentioned PeopleCode program:

Job Name: 3MIX - Mix Jobs

Mode: Parallel

Seq.	Instance	Process Name	Description	Process Type	Run Status	Run Control ID	Type	Output Format	Server Name	Begin Date/Time	End Date/Time
1	4200	XRFWIN	Cross Reference Window Listing	SQR Report	Error	TEST	Web	Acrobat (*.pdf)	PSNT2		2002 - 01 - 08 - 04.01.33.687000
		System Message: Contact John Smith at (555)999-1234 to review the errors **Parameter:** C:\pt840ic3\BIN\SERVERWINX86\PSSQR.EXE -CT MICROSFT -CS -CD FS840IC2 -CA ACCESSID -CAP ACCESSPSWD -RP XRFWIN -I 4200 -R TEST -CO VP1 -OT 6 -OP C:\pt840ic3\APPSERV\prcs\FS840IC2\log_output\SQR_XRFWIN_4200 -OF 2 **Distribution List:** Type: User, Name: VP1 **Application Messages:** Process Request shows status of 'INITIATED' or 'PROCESSING' but no longer running (65,70)								
2	4201	AEMINITEST	Simple AE test program	Application Engine	Success	TEST	Web	Text Files (*.txt)	PSNT2	2002 - 01 - 08 -	

Related Links

PrintJobHTMLRpt

PrintSchdlHTMLRpt

PrintSchdlHTMLRpt

Syntax

PrintSchdlHTMLRpt([*PrintJobTree*] [, *PrintDistList*] [, *PrintNotifyList*] [, *PrintMessageList*] [, *PrintParamList*])

Description

Use the PrintSchdlHTMLRpt method to generate an HTML report file displaying all items in a job or jobset as defined in the Scheduled Jobset Definition component.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

PrintJobTree

Specify whether to have the job tree displayed in the HTML report. This parameter takes a string value:

- "1" to display the tree.
- "0" to not display the tree.

Default value is "1".

PrintDistList

Specify whether you want the list of Users and Roles who will be the recipient of a report generated for a job item displayed in the HTML report. This parameter takes a string value:

- "1" to display the list.
- "0" to not display the list.

Default value is "0".

PrintNotifyList

Specify whether you want the list of Users and Roles who will be notified for the status of a job item displayed in the HTML report. This parameter takes a string value:

- "1" to display the list.
- "0" to not display the list.

Default value is "0".

PrintMessageList

Specify whether you want the messages that will be emailed upon completion of a job item displayed in the HTML report. This parameter takes a string value:

- "1" to display messages.
- "0" to not display messages.

Default value is "0".

PrintParamList

Specify whether you want the parameter list for a job item displayed in the HTML report. This parameter takes a string value:

- "1" to display the parameter list.
- "0" to display the parameter list.

Default value is "0".

Returns

An HTML report as a string

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

The following code:

```
Local string &sHTML;
Local string &sPRINT_JOBTREE;
Local string &sPRINT_DISTLIST;
Local string &sPRINT_NOTIFYLIST;
Local string &sPRINT_MESSAGELIST;
Local string &sPRINT_PARAMLIST;

&sPRINT_JOBTREE = "1";
&sPRINT_DISTLIST = "0";
&sPRINT_NOTIFYLIST = "0";
&sPRINT_MESSAGELIST = "0";
&sPRINT_PARAMLIST = "0";
&JobRQST = SetupScheduleDefnItem("Sample", "MULTIJOB");
&sHTML = &JobRQST.PrintSchdlHTMLRpt(&sPRINT_JOBTREE, &sPRINT_DISTLIST, &sPRINT_NOTI⇒
FYLIST, &sPRINT_MESSAGELIST, &sPRINT_PARAMLIST);
```

Creates the following HTML report:

Image: Example HTML report

The following screen image is an example of a HTML report created after executing the above mentioned PeopleCode program:

Job Name: MULTIJOB - Jobset Example

Mode: Serial

Seq.	Process Name	Description	Process Type	Run Control ID	Type	Output Format	Destination	Server Option	Run Time
1	AP_APY2015	Pay Cycle Process Request	Application Engine	RunCntlTest	Web	Text Files (*.txt)	Distribution List	Any Server	
2	AP_PSTPYMNT	PS/AP Payment Posting	Application Engine	RunCntlTest	Web	Text Files (*.txt)	Distribution List	Any Server	
3	BI JOBS	BI Multi Jobs	PSJob	RunCntlTest	(None)	(None)		Any Server	

Job Name: BI JOBS - BI Multi Jobs

Mode: Serial **Parent Job Name: MULTIJOB**

Seq.	Process Name	Description	Process Type	Run Control ID	Type	Output Format	Destination	Server Option	Run Time
1	BIJOB01	Finalize and Print	PSJob	RunCntlTest	(None)	(None)		Any Server	
2	BIJOB02	Consolidation Final & Print	PSJob	RunCntlTest	(None)	(None)		Any Server	
3	BIJOB03	Single Action Invoice	PSJob	RunCntlTest	(None)	(None)		Any Server	

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

PrintJobHTMLRpt

PrintJobRqstRpt

RunJobSetNow

Syntax

RunJobSetNow()

Description

Use the RunJobSetNow method to schedule a jobset based on settings defined in the Scheduled Jobset Definition component.

Parameters

None.

Returns

None. To verify that the method executed successfully, check the value of the Status property.

Example

```
/* Create the ProcessRequest Object & Run the Scheduled JobSet Now */
Local ProcessRequest &JobRQST;
Local integer &instanceList;

&JobRQST = SetupScheduleDefnItem("Sample","MULTIJOB");
&JobRQST.RunJobSetNow();
&instanceList = &JobRQST.ProcessInstance;
```

Related Links

Status

Schedule

Syntax

Schedule()

Description

Use the Schedule method to insert a request in the Process Request table which runs according to the values in the properties of the ProcessRequest object. To successfully schedule a process or job, certain properties are required.

- If you’re scheduling a single process, you must assign values to the following properties:
  - RunControlID
  - ProcessName

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- ProcessType

- If you're scheduling a job where job item changes are not made, you must assign values to the following properties:
  - RunControlID
  - JobName

- If you're scheduling a job where job item changes are made, you must assign values to the RunControlID.

  Note: You don't have to assign the JobName in this instance because it's set with the CreateProcessRequest function.

Parameters

None.

Returns

None. To verify that the method executed successfully, check the value of the Status property.

Example

```
&MYRQST.Schedule();
If &MYRQST.Status = 0 then
   /* Schedule succeeded. */
Else
   /* Process (job) not scheduled, do error processing */
End-If;
```

Related Links

RunControlID
JobName
ProcessName
ProcessType
Status
"CreateProcessRequest" (PeopleTools 8.54: PeopleCode Language Reference)

SetEmailOption

Syntax

SetEmailOption(*EmailSubject*, *EmailText*, *EmailAddress*, *EmailWebReport*, *EmailAttachLog* [, *JobName*] [, *PrcsItemLevel*] [, *JobSeqNo*] [, *ItemJobSeq*])

Description

Use the SetEmailOption method to set the email options for all job items in the main job.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

EmailSubject	Specify the text used in the subject of the email sent at completion of this job email subject as a string. You can specify a Null ("") for this parameter.
EmailText	Specify the email text sent at completion of this job as a string. You can specify a Null ("") for this parameter.
EmailAddress	Specify the email address of the person you want an email sent to at the completion of this job. To send more than one email address, separate the addresses with a semicolon.
EmailWebReport	Specify whether to attach the web report to the email sent at the completion of this job. This parameter takes a string value: "True", attach the web report, "False", don't attach the web report. This parameter can be set only to "True" when the OutDestType property for the request is "Web".
EmailAttachLog	Specify whether to attach the log file to the email sent at the completion of this job. This parameter takes a string value: "True", attach the log file, "False", don't attach the log file.
JobName	Specify the name of the job that this item belongs to as a string.
PrcsItemLevel	Specify the job item's process item level within the main job as a number.
JobSeqNo	Specify the job item's job sequence number within the process item level as a number.
ItemJobSeq	Specify the job item’s sequence within its parent job as a number

Returns

None.

Related Links

SetItemFolder
SetOutputOption
AddDistributionOption

SetItemFolder

Syntax

SetItemFolder(*PortalFolder* [, *JobName*] [, *PrcsItemLevel*] [, *JobSeqNo*] [, *ItemJobSeq*])

Description

Use the SetItemFolder method to associate a report folder with any job items jobset.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The folder that you specify must have already been created using the System Settings component in Process Scheduler Manager.

Parameters

PortalFolder	Specify the name of the report folder to use for the job item as a string. The folder that you specify must have already been created using Report Manager.
JobName	Specify the name of the job that this item belongs to as a string.
PrcsItemLevel	Specify the job item's process item level within the main job as a number.
JobSeqNo	Specify the job item's job sequence number within the process item level as a number.
ItemJobSeq	Specify the job item’s sequence within its parent job as a number

Returns

None.

Example

```
&RQST.SetItemFolder("GENERAL", "MULTIJOB", 1, 2);
```

Related Links

AddDistributionOption

SetNotifyAppMethod

Syntax

SetNotifyAppMethod(*app_class_name*, *app_class_method* [, *JobName*] [, *PrcsItemLevel*] [, *JobSeqNo*])

Description

Use the SetNotifyAppMethod method to invoke your own custom application class and method to handle process status notification and the information you want to send. This method triggers the delivered PRCS_STATUS_OPER service operation, which invokes the custom method.

Important! The constructor for the application class cannot require parameters.

Note: Alternatively, you can create a custom service operation and trigger that service operation using the SetNotifyService method. Your PeopleCode program should call only one of these methods: either SetNotifyAppMethod or SetNotifyService. If both methods are used, the last method called takes precedence over the former.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

app_class_name	Specify the fully qualified application class name to be invoked on the target system as a string.
app_class_method	Specify the name of the method to be invoked on the target system as a string.
JobName	Specify the name of the job that this item belongs to as a string.
PrcsItemLevel	Specify the job item's process item level within the main job as a number.
JobSeqNo	Specify the job item's job sequence number within the process item level as a number.

Returns

None.

Example

The following example contains two programs. The first program generates the process request setting process status notification through the SetNotifyAppMethod method. The second program defines the application class and method that does additional processing after the status notification has been received by the subscribing system.

Setting process status notification:

```
/*********************************************************************
* Construct a ProcessRequest Object. *
*********************************************************************/
&RQST = CreateProcessRequest();
&RQST.ProcessType = "Application Engine";
&RQST.Processname = "AEMINITEST";
&RQST.RunControlID = "AEMINI";
&RQST.OutDestType = "WEB";
&RQST.OutDestFormat = "PDF";
&RQST.NotifyTextMsgSet = 65;
&RQST.NotifyTextMsgNum = 237;
&RQST.RunDateTime = %Datetime;
&RQST.TimeZone = %ServerTimeZone;
&RQST.SetNotifyAppMethod("RECEIVE_NOTIFICATION:ProcessNotification", "ReceiveNotifi⇒
cation");
&RQST.AddNotifyInfo("AEMINITEST Name", "Status");
&RQST.AddNotifyInfo("AEMINITEST Descr", "Status Notify");
&RQST.AddNotifyInfo("AEMINITEST OutType", "EMAIL");
&RQST.Schedule();
&PRCSSTATUS = &RQST.Status;
&PRCSINSTANCE = &RQST.ProcessInstance;
If &PRCSSTATUS = 0 Then
   MessageBox(%MsgStyle_OK, "", 65, 366, "Process Instance", "AEMINITEST", &PRCSINS⇒
TANCE);
Else
   MessageBox(%MsgStyle_OK, "", 65, 0, "Process Instance", "Process Not submitted")⇒
;
End-If;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Application class and method definition:

```
class ProcessNotification
   method ProcessNotification();
   method ReceiveNotification(&_MSG As Message);
end-class;

/* Class constructor can have no parameters */
method ProcessNotification
end-method;

method ReceiveNotification
   /+ &_MSG as Message +/
   Local Rowset &rs_msg, &NotifyInfo;
   Local Message &message;
   Local string &sName, &sValue, &sName2, &sValue2;
   &rs_msg = &_MSG.GetRowset();
   /*********************************************************/
   /* Add logic you want to execute upon receiving notification */
   /* For example :                                             */
   /*  &RQST.SetNotifyAppMethod("RECEIVE_NOTIFICATION:          */
   /*  ProcessNotification", "ReceiveNotification");            */
   /*  &RQST.AddNotifyInfo("SQR Report", "XRFMENU");            */
   If &rs_msg(1).PRCS_STATUS.RUNSTATUS.Value = "9" Then
      /* process ran to success */

      &NotifyInfo = &rs_msg.GetRow(1).GetRowset(Scroll.PRCSNOTIFYATTR);

      /* if you have more name-value pairs                          */
      /* add code to traverse the rows from the PRCSNOTIFYATTR rowset*/

      /* e.g. Get the first name-value pair */
      &sName = &NotifyInfo(1).PRCSNOTIFYATTR.PRCS_ATTRIBUT_NAME.Value;
      &sValue = &NotifyInfo(1).PRCSNOTIFYATTR.PRCS_ATTRIBUT_VALU.Value;

      /* e.g. submit a process request */
      Local number &PrcsInstance;
      Local ProcessRequest &RQST;
      &RQST = CreateProcessRequest();
      &RQST.ProcessType = &sName;
      &RQST.ProcessName = &sValue;
      &RQST.RunControlID = "test";
      &RQST.RunLocation = "PSNT";
      &RQST.OutDestType = "WEB";
      &RQST.OutDestFormat = "PDF";
      &RQST.RunDateTime = %Datetime;
      &RQST.TimeZone = %ServerTimeZone;

      &RQST.Schedule();

   Else
      /* other processing */
   End-If;
   /*********************************************************/

end-method
```

Related Links

AddNotifyInfo

SetNotifyService

Understanding Application Classes

"Using Process Status Notifications" (PeopleTools 8.54: Process Scheduler)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SetNotifyService

Syntax

SetNotifyService(*srvc_op_name*[, *JobName*] [, *PrcsItemLevel*] [, *JobSeqNo*])

Description

Use the SetNotifyService method to invoke your own custom service operation to handle process status notification and the information you want to send. Your custom service operation must use the PRCS_STATUS_MSG message definition.

Note: Alternatively, you can create a custom application class and method and invoke that method using the SetNotifyAppMethod method. Your PeopleCode program should call only one of these methods: either SetNotifyAppMethod or SetNotifyService. If both methods are used, the last method called takes precedence over the former.

Parameters

srvc_op_name	Specify the name of the custom service operation as a string.
JobName	Specify the name of the job that this item belongs to as a string.
PrcsItemLevel	Specify the job item's process item level within the main job as a number.
JobSeqNo	Specify the job item's job sequence number within the process item level as a number.

Returns

None.

Example

```
/*********************************************************************
* Construct a ProcessRequest Object. *
*********************************************************************/
&RQST = CreateProcessRequest();
&RQST.ProcessType = "Application Engine";
&RQST.Processname = "AEMINITEST";
&RQST.RunControlID = "AEMINI";
&RQST.OutDestType = "WEB";
&RQST.OutDestFormat = "PDF";
&RQST.NotifyTextMsgSet = 65;
&RQST.NotifyTextMsgNum = 237;
&RQST.RunDateTime = %Datetime;
&RQST.TimeZone = %ServerTimeZone;
&RQST.SetNotifyService("PRCS_STATUS_OPER_TEST");
&RQST.AddNotifyInfo("AEMINITEST Name", "Status");
&RQST.AddNotifyInfo("AEMINITEST Descr", "Status Notify");
&RQST.AddNotifyInfo("AEMINITEST OutType", "EMAIL");
&RQST.Schedule();
&PRCSSTATUS = &RQST.Status;
&PRCSINSTANCE = &RQST.ProcessInstance;
If &PRCSSTATUS = 0 Then
   MessageBox(%MsgStyle_OK, "", 65, 366, "Process Instance", "AEMINITEST", &PRCSINS⇒
TANCE);
Else
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
   MessageBox(%MsgStyle_OK, "", 65, 0, "Process Instance", "Process Not submitted")⇒
;
End-If;
```

Related Links

AddNotifyInfo

SetNotifyAppMethod

"Implementing Handlers Using Application Classes" (PeopleTools 8.54: Integration Broker)

"Adding Service Operation Definitions" (PeopleTools 8.54: Integration Broker)

"Using Process Status Notifications" (PeopleTools 8.54: Process Scheduler)

SetOutputOption

Syntax

SetOutputOption(*OutputType*, *OutputFormat*, *OutputDest* [, *JobName*] [, *PrcsItemLevel*] [, *JobSeqNo*] [, *ItemJobSeq*])

Description

Use the SetOutputOption method to modify the output option of one or more job items in the main job.

Note: This method can also be used for a single process.

The job sequence number and job level are optional. They are required only when the same process name is referenced more than once in a job and the user intends to modify the output option of only one item.

If the ProcessRequest object contains an invalid output type for a process, you won't be able to successfully schedule a process or job.

The values for *OutputType*, *OutDestFormat,* and *OutputDestination* are dependent upon each other as well as on other values.

See Values for Output Type and Format.

Parameters

OutputType	Specify the output type as a string.
OutputFormat	Specify the output format as a string.
OutputDestination	Specify the output destination as a string.
JobName	Specify the name of the job that this item belongs to as a string.
PrcsItemLevel	Specify the job item's process item level within the main job as a number.
JobSeqNo	Specify the job item's job sequence number within the process item level as a number.
ItemJobSeq	Specify the job item’s sequence within its parent job as a number

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

None.

Example

```
&RQST.SetOutputOption("Email", "HTM", "", "MULTIJOB", 1, 2);
```

Related Links

OutDest
OutDestFormat
OutDestType

UpdateRunStatus

Syntax

UpdateRunStatus()

Description

Use the UpdateRunStatus method to change the RunStatus for a specific process, job, or jobset.

Parameters

None.

Returns

None.

Example

```
Local ProcessRequest &RQST;

&RQST = CreateProcessRequest();
&RQST.ProcessInstance = 5;
&RQST.RunStatus = 1; /* Cancel the request */
&RQST.UpdateRunSttus();
```

Related Links

RunStatus

ProcessRequest Class Properties

In this section, we discuss the ProcessRequest class properties. The properties are discussed in alphabetical order.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

EmailAttachLog

Description

This property specifies whether or not a log file is attached to the email sent at completion of this job (or process). This property takes a Boolean value.

This property is read-write.

Example

```
&RQST.EmailAttachLog = False;   /*  Do not attach Log File */
```

EmailSubject

Description

This property specifies the text used in the subject of the email sent at completion of this job (or process). This property takes a string value.

This property is read-write.

Example

```
&RQST.EmailSubject = "SQR Report:  Cross Reference Listing";
```

EmailText

Description

This property specifies the text of the email sent at the completion of this job (or process). This property takes a string value.

This property is read-write.

Example

```
&RQST.EmailText = "This text will be displayed as the text of this email ";
```

You can also use the text from a message in the message catalog for this property.

```
&RQST.EmailText = MsgGetText(65, 117, "Sample text for email with two parameters", ⇒
&MessageParm1, &MessageParm2);
```

EmailWebReport

Description

This property specifies whether an email is sent to recipients of the report after it is posted to the report repository. The URL for the report is included in the email. This option is applicable only when the OutDesType for the request is Web. This property takes a Boolean value: True, the web report should be attached, False otherwise.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-write.

FileName

Description

This property contains the name of a file to be used with file dependant processing, that is, processes which are initiated only after a file becomes available.

For a file dependent process, the FileName property is set to override the file name specified in the process definition. You must specify the complete file path and extension for the file, as a string.

This property works with the RunLocation property. If you don't specify a run location, any value assigned to this property is ignored.

This property is read-write.

Example

The following code example initiates QE_AETESTPRG once the c:\import\ediData.dat file becomes available on PSNT server.

```
Local ProcessRequest &rqst1;

&rqst1 = CreateProcessRequest();
&rqst1.RunControlId = "2";
&rqst1.ProcessType = "Application Engine";
&rqst1.ProcessName = "QE_AETESTPRG";
&rqst1.RunLocation = "PSNT";
&rqst1.FileName="c:\import\ediData.dat";
&rqst1.Schedule();
```

Related Links

RunLocation

"Setting Process Definition Options" (PeopleTools 8.54: Process Scheduler)

JobName

Description

This property contains the name of a job that you've defined in PeopleSoft Process Scheduler.

To schedule a job, you must assign values to JobName and RunControlID for the Schedule method to succeed.

If you're scheduling a job, you don't need to set the ProcessType property.

This property is read-write.

Example

```
&MYRQST.JobName = "3SQR";
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

RunControlID

LanguageCd

Description

This property enables you to specify a language code for the process or job. If you don't specify a language code, PeopleSoft Process Scheduler first looks in the process run control table to retrieve a language code. If there isn't a value there, PeopleSoft Process Scheduler uses the user's language code specified in the User Definition table.

This property takes a string value.

This property is read-write.

Example

```
&MYRQST.LanguageCd = "ESP" /* Spanish */
```

NotifyTextMsgNum

Description

Use the NotifyTextMsgNum property to specify the message that should be displayed to the end user in the Event Notification popup display. This property takes a numeric value.

Note: You must specify both the message set and message number for the message to be displayed to the end user.

This property is read-write.

Example

```
&RQST.NotifyTextMsgSet = 65;
&RQST.NotifyTextMsgNum = 237;
```

Related Links

NotifyTextMsgSet

NotifyTextMsgSet

Description

Use this property to specify the message set of the text message to be displayed to the end user in the Event Notification popup display. This property takes a numeric value.

Note: You must specify both the message set and message number for the message to be displayed to the end user.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

```
&RQST.NotifyTextMsgSet = 65;
&RQST.NotifyTextMsgNum = 237;
```

Related Links

NotifyTextMsgNum

OutDest

Description

This property specifies the output destination for the process or job to be scheduled as a string.

Values depend on the setting for the OutDestType property:

- If OutDestType is FILE, OutDest must be the name of a directory. If the OutDest property isn't set, it defaults to the setting in the Process profile. If the Process Profile was not updated with a default destination, the Process Scheduler server that picked up the request sets the directory based on the Log/Output Directory setting found in the Process Scheduler Configuration file.
- If OutDestType is PRINTER, OutDest must be the name of a printer. If the OutDest property isn't set, it defaults to the setting in the Process profile. If the Process Profile was not updated with a default printer, the Process Scheduler server that picked up the request sets the printer based on the Default Printer setting found in the Process Scheduler Configuration file.
- If OutDestType is WEB or EMAIL, OutDest should contain the list of User IDs, Role IDs, or email addresses (for email only). If you don't set this property, it's automatically assigned to the person who submitted the request.
- If OutDestType is WEB, PeopleSoft Process Scheduler uses the OutDest property to determine who has access to the output.
- If OutDestType is EMAIL, PeopleSoft Process Scheduler uses the OutDest property to determine who to send the report output to.

  In both these cases, to identify whether it's a User ID or a Role ID, the value has to be preceded by one of the following:

  U: *Username* or **User:** *Username* for a user ID

  R: *Rolename* or **Role:** *Rolename* for a role ID

  If the ID is not preceded by either of these identifiers, Process Scheduler assumes it's an email address.

  Note: Each ID must be separated by a semicolon (;).

  The following are two examples:

```
&RQST.OutDest = "U:PTDMO;R:Employee;robert_smith@peoplesoft.com"

&RQST.OutDest = "User:PS;Role:Employee;sue_line@XYZ.com;simon_gree@peoplesoft.⇒
com"
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- For any other value of OutDestType, this property has no effect.

You can specify directory and printer names using the UNC (Uniform Naming Convention) protocol.

This property is read-write.

Example

```
&MYRQST.OutDest = "C:\TEMP";
```

Related Links

OutDestType

"Understanding the Management of PeopleSoft Process Scheduler" (PeopleTools 8.54: Process Scheduler)

OutDestFormat

Description

This property specifies the output format for the process or job to be scheduled as a string. Values depend on your settings for the ProcessType and OutDestType properties:

The values for OutDestType, OutDestFormat, and OutDest are dependent upon each other as well as on other values.

See Values for Output Type and Format.

This property is read-write.

Example

```
&MYRQST.OutDestFormat = "RTF";
```

Related Links

ProcessType

OutDestType

OutDestType

Description

This property specifies the type of output for the process or job to be scheduled as a string.

If the ProcessRequest object contains an invalid output type for a process, you won't be able to able to successfully schedule a process or job.

The value specified for this property is used only if the Output Destination Type for the defined process or job defined in PeopleSoft Process Scheduler is specified as Any. Otherwise any value specified for this property is ignored.

The values for OutDestType, OutDestFormat, and OutDest are dependent upon each other as well as on other values.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

See Values for Output Type and Format.

This property is read-write.

Example

```
&MYRQST.OutDestType = "FILE";
```

Related Links

ProcessType
RunControlID

PortalFolder

Description

This property specifies the name of the report folder associated with a job item as a string. If you're specifying a folder, the folder that you specify must have already been created using Report Manager.

This property is read-write.

ProcessInstance

Description

This property is a system-generated identification number. PeopleSoft Process Scheduler assigns a ProcessInstance at runtime to each process or job it successfully schedules.

This property is read-write.

Example

```
&MYRQST.Schedule();
If &MYRQST.Status = 0 then
   /* process successfully scheduled */
   &ProcInst = &MYRQST.ProcessInstance;
Else
   /* do error processing */
End-If;
```

ProcessName

Description

This property specifies the name of a predefined process as a string.

To successfully schedule a process, you must assign values to ProcessName, ProcessType, and RunControlID (that is, for the Schedule method to succeed.)

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

```
&MYRQST.ProcessName = "XRFWIN";
```

Related Links

ProcessType
RunControlID

ProcessType

Description

This property specifies the name of a predefined process type as a string.

To successfully schedule a process, you must assign values to ProcessName, ProcessType, and RunControlID (that is, for the Schedule method to succeed.)

The values for ProcessType depend on the types of processes you have defined in your system. There are generic process types that are delivered with your installation of PeopleSoft. These process types may include the following:

- Application Engine
- COBOL
- Crystal
- Cube
- nVision
- SQR
- WinWord
- Other

If you define your own processes, you can use the name of that process with the ProcessType property. For example, suppose you create a custom process named "Custom CBL Programs." You could use this as follows:

```
&MyRqst.ProcessType = "Custom CBL Programs";
```

Note that spaces are included in the string for ProcessType.

This property is read-write.

Example

Note that spaces are included in the string for ProcessType.

```
&MYRQST.ProcessType = "Application Engine";
```

Related Links

ProcessName

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

RunControlID

RunControlID

Description

This property returns a string that serves, along with the user ID, as a key that identifies a predefined group of parameters to be used by a process or a job at runtime.

To successfully schedule a process, you must provide values for RunControlID, ProcessName, and ProcessType.

To successfully schedule a job, you must provide values for RunControlID and JobName.

This property is read-write.

Example

```
&MYRQST.RunControlID = "MYRUNCONTROLID";
or
&MYRQST.RunControlID = PRCSSAMPLEREC.RUN_CNTL_ID;
```

Related Links

JobName

ProcessName

ProcessType

RunDateTime

Description

This property contains a DateTime value that specifies when the scheduled process or job will run.

If you don't specify a value for this property, and there is no date time set for the pre-defined process or job, the process or job runs as soon as the Schedule method is executed.

This property is read-write.

Example

The following example schedules the process or job to run as soon as the Schedule method is executed:

```
&MYRQST.RunDateTime = %Datetime;
```

RunLocation

Description

This property specifies the Process Scheduler Server name the request should be scheduled on. This property takes a string value. Values for RunLocation is a specific server name, such as PSNT.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

If no RunLocation is specified, the request is scheduled based on both the default operating system and load balancing options set in the System Settings page.

This property is read-write.

Example

```
&MYRQST.RunLocation = "SERVER";
or
&MYRQST.RunLocation = "PSNT";
```

Related Links

"Viewing the Status of Processes" (PeopleTools 8.54: Process Scheduler)

RunRecurrence

Description

This property specifies the frequency with which a process or job is to be run as a string. The RunRecurrence value you use must be the name of a Recurrence Definition defined in Process Scheduler Manager to successfully schedule a job or process (that is, for the Schedule method to succeed.)

This property is read-write.

Example

```
&MYRQST.RunRecurrence = "M-F at 5pm";
```

RunStatus

Description

This property specifies the run status of a process request as a number. This property is used with the UpdateRunStatus method to change the status of a request. Values are:

RunStatus	***Description***
1	Cancel
2	Delete
3	Error
4	Hold
5	Queued
6	Initiated
7	Processing

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

RunStatus	*Description*
8	Cancelled
9	Success
10	Not Successful
11	Posted
12	Unable to post
13	Resend
14	Posting
15	Generated
16	Pending

This property is read-write.

Example

```
&MYRQST.RunStatus = 1;
```

Related Links

UpdateRunStatus

Status

Description

This property returns a number based on the result of the last execution of the Schedule method.

Valid returns are:

- Zero if the method succeeded
- Non-zero otherwise

This property is read-only.

Example

```
&MYRQST.Schedule();
If &MYRQST.Status = 0 then
   /* Schedule succeeded. */
Else
   /* Process (job) not scheduled, do error processing */
End-If;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

TimeZone

Description

This property contains a timezone value that specifies when the scheduled process or job will run. If no value is used for this property, the server timezone is used. This property takes a string value.

This property is read-write.

Example

```
&MyRqst.TimeZone = "EST";
```

ProcessRequest Class Examples

The following section contains the following examples:

- Scheduling a single process
- Scheduling a job where job item changes are not made
- Scheduling a job where job item changes are made

Scheduling a Single Process

The following example is when you're scheduling a single process:

```
Local ProcessRequest &RQST;

/* Create the ProcessRequest Object */
&RQST = CreateProcessRequest();

/* Set all the Required Properties */
&RQST.RunControlID = &sRunCntlId;
&RQST.ProcessType = &sProcessType;
&RQST.ProcessName = &sProcessName;

/* Set any Optional Properties for this Process */
&RQST.RunLocation = &sRunLocation;
&RQST.RunDateTime = &dttmRunDateTime;
&RQST.TimeZone = &sTimeZone;
&RQST.PortalFolder = &sPortalFolder;
&RQST.RunRecurrence = &sRecurrence;
&RQST.OutDestType = &sOutDestType;
&RQST.OutDestFormat = &sOutDestFormat;
&RQST.OutDest = &sOutputDirectory;
&RQST.EmailAttachLog = &bEmailAttachLog;
&RQST.EmailWebReport = &bEmailWebReport;
&RQST.EmailSubject = &sEmailSubject;
&RQST.EmailText = &sEmailText;

/* Schedule the Process */
&RQST.Schedule();
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Scheduling a Job Where Job Item Changes Are Not Made

The following example is when job item changes aren't made.

```
Local ProcessRequest &RQST;

/* Create the ProcessRequest Object */
&RQST = CreateProcessRequest();

/* Set all the Required Properties */
&RQST.RunControlID = &sRunCntlId;
&RQST.JobName = &sJobName;

/* Set any Optional Main Job Properties */
&RQST.RunLocation = &sRunLocation;
&RQST.RunDateTime = &dttmRunDateTime;
&RQST.TimeZone = &sTimeZone;
&RQST.PortalFolder = &sPortalFolder;
&RQST.RunRecurrence = &sRecurrence;
&RQST.OutDestType = &sOutDestType;
&RQST.OutDestFormat = &sOutDestFormat;
&RQST.OutDest = &sOutputDirectory;
&RQST.EmailAttachLog = &bEmailAttachLog;
&RQST.EmailWebReport = &bEmailWebReport;
&RQST.EmailSubject = &sEmailSubject;
&RQST.EmailText = &sEmailText;

/* Schedule the Job */
&RQST.Schedule();
```

Scheduling a Job Where Job Item Changes Are Made

The following example is when job item changes are made.

```
Local ProcessRequest &RQST;

/* Create the ProcessRequest Object */
&RQST = CreateProcessRequest("PSJob", &sJobName);

/* Set all the Required Properties */
/* Note: the JobName Property has already */
/* been set in the call above, so you don&rsquo;t */
/* have to set it here */
&RQST.RunControlID = &sRunCntlId;

/* Set any Optional Job Item Properties */
&RQST.SetOutputOption(&sOutputType, &sOutputFormat, &sOutputDest, &sJobName, &nPrcs⇒
ItemLevel, &nJobSeqNo);

&RQST.SetEmailOption(&sEmailSubject, &sEmailText, &sEmailAddress, &sEmailWebReport,⇒
 &sEmailAttachLog, &sJobName, &nPrcsItemLevel, &nJobSeqNo);
&RQST.SetItemFolder(&sPortalFolder, &sJobName, &nPrcsItemLevel, &nJobSeqNo);
&RQST.AddDistributionOption(&sDistIdType, &sDistId, &sJobName, &nPrcsItemLevel, &nJ⇒
obSeqNo);

/* Set any additional Optional Main Job Properties */
&RQST.RunLocation = &sRunLocation;
&RQST.RunDateTime = &dttmRunDateTime;
&RQST.TimeZone = &sTimeZone;
&RQST.PortalFolder = &sPortalFolder;
&RQST.RunRecurrence = &sRecurrence;
&RQST.OutDestType = &sOutDestType;
&RQST.OutDestFormat = &sOutDestFormat;
&RQST.OutDest = &sOutputDirectory;
&RQST.EmailAttachLog = &bEmailAttachLog;
&RQST.EmailWebReport = &bEmailWebReport;
&RQST.EmailSubject = &sEmailSubject;
&RQST.EmailText = &sEmailText;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
/* Schedule the Job */
&RQST.Schedule();
```

PrcsApi Class

Use the PrcsApi class with file dependant processing. This section includes:

- Scope of a PrcsApi object.
- Data type of PrcsApi object.
- How to import a PrcsApi object
- How to create a PrcsApi object
- PrcsApi reference

See File Dependant Processing.

Scope of a PrcsApi Object

A PrcsApi object can be instantiated only from PeopleCode.

A PrcsApi object can be called from a component, an internet script, or an Application Engine program.

PrcsApi class objects can be of Local, Global, or Component scope.

Data Type of a PrcsApi Object

PrcsApi objects are of type PrcsApi.

```
Local PrcsApi &api = create PrcsApi();
```

How to Import the PrcsApi Class

The PrcsApi class is *not* a built-in class, like Rowset, Field, Record, and so on. It is an Application Class. Before you can use this class in your PeopleCode program, you must import it to your program.

An import statement names either all the classes in a package or one particular application class. For importing the PrcsApi class, PeopleSoft recommends that you import the API class.

The import statement you should use is as follows:

```
import PT_PRCS:API:*;
```

Using the asterisks after the package name makes all the application classes directly contained in the named package available.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

Understanding Application Classes

How to Create a PrcsApi Object

After you've imported the PrcsApi class, you instantiate an object of that class using the constructor for the class and the *Create* function.

The following example creates a new instance of the PrcsApi class, as the variable &api, with local scope:

```
import PT_PRCS:API:*;

Local PrcsApi &api = create PrcsApi();
```

PrcsApi Class Constructor

You must use the constructor for the PrcsApi class to instantiate an instance of that class. The following is the constructor for the PrcsApi class.

PrcsApi

Syntax

PrcsApi()

Description

Use the PrcsApi constructor to create an instance of the PrcsApi class.

Parameters

None.

Returns

A reference to a PrcsApi object.

PrcsApi Class Methods

In this section, we discuss the PrcsApi class methods. The methods are discussed in alphabetical order.

getAllFileNames

Syntax

getAllFileNames(*PrcsInstance*)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the getAllFileNames method to return a list of all the files names detected by the scheduler to intiate this process. The names are returned in an array of string, as full path names.

Parameters

PrcsInstance Specify the process instance for which you want to get all the associated file names, as a number.

Returns

An array of string containing all the files names associated with the specified process.

Example

The following example returns a list of file names.

```
/* QE_OPT_AET is the state record for the application engine program in this exampl⇒
e */

import PT_PRCS:API:*;

Local PrcsApi &api = create PrcsApi();

Local File &FileIO, &FileLog;

Local array of string &strList = &api.getAllFileNames(QE_OPT_AET.PROCESS_INSTANCE);⇒

/* api call needs process instance as parameter */

/* the api returns list of file names matched by the scheduler for this instance */
For &i = 1 To &strList.Len
   &IOFilename = &strList [&i];

   &FileIO = GetFile(&IOFilename, "r", "a", %FilePath_Absolute);

   &FileIO.Delete();

   &FileIO.Close();
End-For;
```

notifyToWindow

Syntax

notifyToWindow(*PrcsInstance*, *Message*)

Description

Use the notifyToWindow method to display additional messages to the window.

If a process is not defined as going to Window, using this method has no effect. The purpose of this method is to display additional messages to the window when an Application Engine process (no other process type) is run to Window.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

PrcsInstance Specify the process instance for which you want to display messages, as a number.

Message Specify the message you want displayed, as a string.

Returns

A number: 0 if method failed.

Example

The following PeopleCode would be in a step in an application engine program.

```
import PT_PRCS:API:*;

Local PrcsApi &api = create PrcsApi();

/* QE_AESTATUS_AET is the sate record for this Application Engine program */

&nret = &api.notifyToWindow(QE_AESTATUS_AET.PROCESS_INSTANCE, "Hi There! this is Fi⇒
rst step.");

/* this displays the message on the window */
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Chapter 37

PSEvent Class

Understanding the PSEvent Class

The PSEvent class provides all of the methods for publishing and subscribing to notifications from the Push Notification Framework. This framework updates the user with real-time changes, known as events, that have occurred on the application server tier. The framework enables PeopleSoft applications to push data directly to the user's display.

Methods of the PSEvent class are used for publishing, subscribing to, and unsubscribing from notifications:

- Publishing a notification — Set*xxx* methods, Publish method.
- Subscribing to a notification:
  - Subscription — Subscribe method.
  - Callback method — Get*xxx* methods.
- Unsubscribing to a notification — Unsubscribe method.

Related Links

"Understanding the Push Notification Framework" (PeopleTools 8.54: System and Server Administration)

Instantiating the PSEvent Class

You must use the CreateObject built-in function to instantiate an object of the PSEvent class:

```
Local object &EventObject;
&EventObject = CreateObject("PSEvent");
```

Related Links

"CreateObject" (PeopleTools 8.54: PeopleCode Language Reference)

PSEvent Class Methods

In this section, the PSEvent class methods are presented in alphabetical order.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

AddRecipient

Syntax

AddRecipient(*name*, *type*)

Description

Use the AddRecipient method to set a specific recipient to receive the notification. Either a user ID or a role name can be specified, but not both.

Note: If no recipients are set for a notification, all the users who have subscribed for that notification will receive the notification.

Parameters

name A string representing the name of the recipient (user ID or role name).

type A number representing the type of the recipient:

- *1* — If the *name* parameter represents a user ID.
- *2* — If the *name* parameter represents a role name.

Returns

A Boolean value: True if the method completes successfully, False otherwise.

Example

The following example sets the user PTUSER as the recipient.

```
&name = "PTUSER";
&EventObject.AddRecipient(&name, 1);
```

Related Links

AddRecipients
GetRecipients
RemoveRecipients

AddRecipients

Syntax

AddRecipients(*names*, *type*)

Description

Use the AddRecipients method to set multiple recipients to receive the notification. Either user IDs or a role names can be specified, but not both.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

names A string array representing the name of the recipients (either user IDs or role names).

type A number representing the type of the recipients:

- *1* — If the *names* parameter represents user IDs.
- *2* — If the *names* parameter represents role names.

Returns

A Boolean value: True if the method completes successfully, False otherwise.

Example

The following example sets an array of user IDs as the recipients.

```
Local array of string &USERIDS;
Local string &ROLENAME;

&ROLENAME = "Portal Administrator";
Local Rowset &rs = CreateRowset(Record.PSROLEUSER);
&rs.Fill("WHERE ROLENAME=:1", &ROLENAME);
&USERIDS = CreateArrayRept("", 0);
For &i = 1 To &rs.RowCount
   &USERIDS.Push(&rs(&i).PSROLEUSER.ROLEUSER.Value);
End-For;

&EventObject.AddRecipients(&USERIDS, 1);
```

Related Links

AddRecipient
GetRecipients
RemoveRecipients

GetRecipients

Syntax

GetRecipients(*type*)

Description

Use the GetRecipients method to get all the recipients of a particular type from the notification.

Parameters

type A number representing the type of recipients:

- *1* — For user IDs.
- *2* — For role names.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

An array of string representing the recipients for the specified type.

Example

The following example retrieves all role-type recipients:

```
Local array of string &RoleNames;
&type = 2;
RoleNames= &EventObject.GetRecipients(&type);
```

GetRowSetData

Syntax

GetRowSetData()

Description

Use the GetRowSetData method to get the rowset data from the notification.

Parameters

None.

Returns

A Rowset object.

Example

The following example retrieves the rowset data.

```
Local Rowset &oRowset;
&oRowset = &EventObject.GetRowSetData();
```

Related Links

SetRowSetData
"Defining Events" (PeopleTools 8.54: System and Server Administration)

GetValueOfKey

Syntax

GetValueOfKey(*key*)

Description

Use the GetValueOfKey method to get the value for a key from the notification data.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

key Specify the string representing the name of the key. Key names are defined in the Data Structure field on the Define Server Side Events page.

Returns

A valid string representing the corresponding value for the key, if the key exists. An empty string if the key does not exist.

Example

The following example gets the value for the key named ID.

```
&Key = "ID";
&Value = &EventObject.GetValueOfKey(&Key);
```

Related Links

SetKeyValuePair

"Defining Events" (PeopleTools 8.54: System and Server Administration)

Publish

Syntax

Publish(*event_name*)

Description

Use the Publish method to publish a notification for an event.

Parameters

event_name A string representing the name of the event as defined on the Define Server Side Events page.

Returns

A Boolean value: True if the method completes successfully, False otherwise.

Example

The following example uses a method definition to set event data and then publish a notification named WORKFLOWAPPROVAL.

```
method SendApprovalNotification
 /+ &category as String, +/
 /+ &message as String, +/
 /+ &actionsLink as String, +/
 Local object &EventObject;

 &EventObject = CreateObject("PSEvent");
 &EventObject.SetKeyValuePair("CATEGORYNAME", &category);
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
 &EventObject.SetKeyValuePair("MESSAGE", &message);
 &EventObject.SetKeyValuePair("ACTIONSLINK", &actionsLink);
 &EventObject.Publish("WORKFLOWAPPROVAL");
end-method;
```

Related Links

Subscribe

Unsubscribe

"Defining Events" (PeopleTools 8.54: System and Server Administration)

RemoveRecipients

Syntax

RemoveRecipients(*type*)

Description

Use the RemoveRecipients method to remove all the recipients of a particular type from the notification.

Parameters

type A number representing the type of recipients:

- *1* — For user IDs.
- *2* — For role names.

Returns

None.

Example

The following example removes recipients of type "role names" from the notification.

```
&type = 2;
&EventObject.RemoveRecipients(&type);
```

Related Links

AddRecipient

AddRecipients

GetRecipients

SetKeyValuePair

Syntax

SetKeyValuePair(*key*, *value*)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the SetKeyValuePair method to add data in the form key-value pair to the notification.

Note: Notification data can be represented as either key-value pairs or as a rowset, not both. The event definition on the Define Server Side Events page determines the type of data for the notification and therefore the Set*xxx* method to be used.

Parameters

key	Specify the string representing the name of the key. Key names are defined in the Data Structure field on the Define Server Side Events page.
value	Specify the string representing the value.

Returns

A Boolean value: True if the method completes successfully, False otherwise.

Example

The following example sets the value for the key named "ID".

```
&Key = "ID";
&Value = "100";
&EventObject.SetKeyValuePair(&Key, &Value);
```

Related Links

GetValueOfKey

"Defining Events" (PeopleTools 8.54: System and Server Administration)

SetRowSetData

Syntax

SetRowSetData(*&rowset*)

Description

Use the SetRowSetData method to set a Rowset object as the data for the notification.

Note: Notification data can be represented as either key-value pairs or as a rowset, not both. The event definition on the Define Server Side Events page determines the type of data for the notification and therefore the Set*xxx* method to be used.

Parameters

&rowset	An already instantiated Rowset object, which acts as the notification data.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

A Boolean value: True if the method completes successfully, False otherwise.

Example

The following example sets rowset data from the QE_CHART_RECORD record.

```
Local Rowset &oRowset;
&oRowset = CreateRowset(Record.QE_CHART_RECORD);
&oRowset.Fill("where QE_CHART_REGION= :1", "MIDWEST");
&EventObject.SetRowSetData(&oRowset);
```

Related Links

GetRowSetData

"Defining Events" (PeopleTools 8.54: System and Server Administration)

Subscribe

Syntax

Subscribe(*event_name*, *callback_method*)

Description

Use the Subscribe method to have the PeopleCode program running on the application server subscribe to a notification for an event. Alternatively, JavaScript provides different mechanisms for subscribing to a notification for an event from a PeopleSoft page.

Parameters

event_name A string representing the name of the event as defined on the Define Server Side Events page.

callback_method A string value representing the method to be invoked when the notification is received by the subscriber.

The string must be a fully qualified method name in the form:

```
APP_PKG:App_Class:Method_Name
```

Returns

A Boolean value: True if the method completes successfully, False otherwise.

Example

The following example subscribes to a notification named PROCESSSTATUSCHANGE:

```
&EventObject.Subscribe("PROCESSSTATUSCHANGE", "PT_PRCS:ProcessMonitor:OnProcessStat⇒
usChange");
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This example requires the implementation of a callback method named OnProcessStatusChange in the PT_PRCS:ProcessMonitor application class:

```
class ProcessMonitor
 method OnProcessStatusChange(&EventObject As object);
end-class;
method OnProcessStatusChange
  /+ &EventObject as Object +/
  Local string &ID;
 Local string &PROCESSNAME;
 Local string &KEY;

 &KEY = "ID";
 &ID = &EventObject.GetValueOfKey(&KEY);

 &KEY = "PROCESSNAME";
 &PROCESSNAME = &EventObject.GetValueOfKey(&KEY);
end-method;
```

Related Links

Publish

Unsubscribe

"Defining Events" (PeopleTools 8.54: System and Server Administration)

"Subscribing to an Event Using JavaScript" (PeopleTools 8.54: System and Server Administration)

"Subscribing to an Event Collection" (PeopleTools 8.54: System and Server Administration)

Unsubscribe

Syntax

Unsubscribe(*event_name*)

Description

Use the Unsubscribe method to unsubscribes from a notification for an event..

Parameters

event_name	A string representing the name of the event as defined on the Define Server Side Events page.

Returns

None.

Example

The following example unsubscribes from a notification named PROCESSSTATUSCHANGE.

```
&eventName = "PROCESSSTATUSCHANGE";
&EventObject.Unsubscribe(&eventName);
```

Related Links

Publish

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Subscribe

"Defining Events" (PeopleTools 8.54: System and Server Administration)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Chapter 38

Query Classes

Understanding Query Classes

You create queries using PeopleSoft Query Manager to extract the data you need from the PeopleSoft database. You can use the query classes in PeopleCode to create a new query, or to modify or delete an existing query. You can also use methods in the Query class to execute the query and have the result set returned as either a rowset or have it format and write the result set to a file. You can also use the query classes to create a SQL statement to be used with the SQL object. In fact, the query classes expose all of the attributes and methods needed by the PeopleSoft Query Manager and Query Viewer applications.

Creating or deleting a query object does not create or delete query information. You must call the appropriate method for that query object directly to create or delete database information, that is, the Create or Delete method.

All of the classes, and most of the properties and methods that make up the query classes, have a GUI representation in PeopleSoft Query Manager. This document assumes that the reader has working knowledge of PeopleSoft Query Manager.

There aren't any external built-in functions for the query classes: objects are instantiated from other objects or from a session object.

Related Links

Understanding Session Class

"PeopleSoft Query Overview" (PeopleTools 8.54: Query)

Collections in the Query Classes

A *collection* is a set of similar things, like a group of already existing queries or QueryRecords. As with everything else in the query classes, collections have a GUI representation in PeopleSoft Query.

For example, when you want to open a query, the search page returns a list of all the available queries. This is equivalent to using the FindQueries session class method to get a Query collection.

The following collections are part of the query classes:

- QuerySelect collection
- QueryDBRecord collection
- QueryDBRecordField collection
- Query collection
- QueryRecord collection

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- QueryOutputField collection
- QuerySelectedField collection
- QueryCriteria collection
- QueryExpression collection
- QueryPrompt collection

Life Cycle of a Query

At runtime, there are certain things you want to do with a query, like creating one from scratch, updating the criteria for an existing query, running a query, and so on. The following is an overview of this process, and assumes the most common method to use the query API. These steps are expanded in other sections.

1. Invoke the GetQuery method on the PeopleSoft session object to get a query.
2. Either open the specific query you want using Open, or create a new query using Create.
3. Read the query statistics, or make changes as appropriate, adding records, field, criteria, and so on.
4. Save the changes.
5. (Optional) Use the RunToRowset method to run the query.

   Note: Be careful whenever you write a PeopleCode program that uses the RunToRowset method because this method could return a large amount of data that could potentially exceed the memory available. For this reason, RunToRowset should be used only when you know that the query being executed returns a reasonable amount of data, or be sure to use the MaxRows parameter to control the maximum amount of data that can be returned.

   Alternatively, you can:

   - Use the RunToFile method to execute a scheduled query.
   - Use the RunToString method to run a query and return the result as a formatted string.

6. Close the query.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

7. If you want, you can navigate to PeopleSoft Query Manager, Query Viewer or the Query Designer to run the query.

Image: Life cycle of a Query object

The following diagram is an overview of life cycle of a Query object , illustrates the most common method to use the query API.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Query Classes Hierarchy

Image: Query API class hierarchy (part 1 of 3)

There are many different classes used with the query API. The following flowcharts illustrate all the different classes and how they're interrelated.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Image: Query API class hierarchy (part 2 of 3)

The following flowchart continues to illustrate all the different classes and how they are interrelated.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Image: Query API class hierarchy (part 3 of 3)

Here is another flowchart that illustrates different classes and their correlation.

Query API Overview

The query API is made up of many classes. The following are the primary parts, generally used when updating a query:

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Query	The query definition.
QuerySelect	A query SELECT statement. There can be multiple QuerySelect objects for queries that involve unions or subqueries. Each select (or union or subquery) consists of QueryRecords, QueryOutputFields, QuerySelectedFields, and QueryCriteria.
QueryRecords	The records that are part of the existing QuerySelect definition.
QueryOutputFields	The fields that you've selected to be displayed when the results of the query are run.
QuerySelectedFields	All the fields that make up the QuerySelect Definition. These include the fields selected as output fields, and fields added as part of Query Expressions.
QueryCriteria	The criteria for the query.
QueryExpression	The Query expressions that can contain SQL functions or other SQL fragments.
QueryList	The lists used in the in-list functionality for criteria.
QueryPrompt	The prompts used in criteria.
QueryDBRecords and QueryDBRecordFields	All the records available to be used as QueryRecords, and all the fields available. This list is restricted based on a user's Query Access Security Groups.

Query

A database query. You must get a query before you can access any of the other query classes. You can then create a new query and save it to the database, or open an existing query and modify it.

QuerySelect

Each query is composed of one or more select statements:

Main Select	The instance of the first SELECT statement of the Query is the Main Select. There can only be one Main Select statement in the Query. This instance consists of the QueryOutputFIelds, QueryCriteria, and the QueryExpressions for the Main Select statement.
Union	In addition to the Main Select, a query can have one or more unions. The Unions are added by using the AddUnion method.
Sub-Select	A subquery used in the criteria of the Main Select or in a Union.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

QueryRecords

The records that are part of an existing query definition. In PeopleSoft Query, these are the records listed on the query tab. Each QuerySelect has its own set of QueryRecords.

QueryOutputFields

The fields that you've selected to be part of the query definition. They're called output fields because when you run the query, these are the fields that make up the output columns.

In PeopleSoft Query, these are the fields listed on the Fields tab.

The collection of QueryOutputFields does *not* necessarily include all columns returned in query resultset. This collection only includes columns that have been added to query output collection using the query classes or by an end-user designing a query.

PeopleSoft Query can also add additional columns for related language processing and also for translate labels on fields, and so you cannot use the Query Output Collections as a way to discover all of the columns that are returned in the resultset or by executing the SQL generated from a query.

QuerySelectedFields

All the fields that make up the query definition. These include the fields selected as output fields, and fields added as QueryExpressions.

QueryCriteria

The selection criteria for the query. Each QueryCriteria object is made up of the following:

Logical	Any criteria objects after the first must include have a Logical value, either AND or OR.
Expression 1	A field or value that you want to base the selection criterion on, that is, Expression1 is the left-hand side of the criterion's comparison.
Operator	A mathematical or other operator used to specify the relationship between Expression 1 and Expression 2.
Expression 2	A field or other value, also called a comparison value, used with Expression 1, that is, Expression2 is the right-hand side of the criterion's comparison.

In PeopleSoft Query, a QueryCriteria is under the Criteria tab.

Expression can be made up of constant values, fields, subqueries, and so on.

Related Links

Working With Query Criteria and Expressions

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

QueryDBRecords and QueryDBRecordFields

A QueryDBRecord is a record in the database that can be used as a QueryRecord. The list of records is controlled by security: the only records displayed as QueryDBRecords are records accessible by the user.

The QueryDBRecordFields are the fields that make up the QueryDBRecords.

In PeopleSoft Query, the QueryDBRecords are under the Record tab. After you click on the plus sign next to a record, the QueryDBRecordFields are displayed.

Working With Query Criteria and Expressions

If you run a query after selecting the QueryFields (which executes a SQL statement, such as SELECT EMPLID, DEPTID from PS_QE_EMPLOYEE), the system retrieves *all* the data in those columns; that is, it retrieves the data from every row in the QueryRecord or records because there is no filter limiting the number of rows.

You can select which *rows*of data you want by adding selection criteria to the query.

This document assumes that you know how to use selection criteria. This section discusses working with the QueryCriteria and QueryExpression objects in the query API only.

This section discusses how to:

- Set the expression type.
- Add new expressions.
- Add an operator and Expression 2 dependencies.
- Set a drilling URL.

Related Links

"Choosing Selection Criteria" (PeopleTools 8.54: Query)

Setting the Expression Type

Before you can add a new expression (either Expression 1 or Expression 2) to your QueryCriteria, you must set the type for the expression.

The following code example adds a new criteria, sets the type for the first expression, adds the first expression to the main select of the query definition, then does the same thing for the second expression.

```
&MyQuerySelect = &MyQuery.QuerySelect;
&MyCriteria = &MyQuerySelect.AddCriteria();

/* make expression 1 a field */
&MyCriteria.Expr1Type = %Query_ExprField;

/* add the ABSENCE_TYPE field */
&MyCriteria.AddExpr1Field("A", "ABSENCE_TYPE");

/* make it not equal to */
&MyCriteria.Operator = %Query_CondNotEqual;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
/* Make expression 2 a constant */
&MyCriteria.Expr2Type = %Query_ExprConstant;
&MyCriteriaExpr = &MyCriteria.AddExpr2Expression1();
&MyCriteriaExpr.Text = "VAC";
```

Adding New Expressions

When you use any of the QueryCriteria methods to add either a new Expression 1 or Expression 2, you destroy the existing value.

In general, you should use the QueryCriteria methods to add a new Expression 1 or Expression 2 only when you're adding a new criteria to a query.

Adding an Operator and Expression 2 Dependencies

Which values are valid for the Expression 2 type (Expr2Type property) depend on the value of the Operator property.

The following table describes which Expr2Type values are valid with which values of Operator.

Operator	***Expression 2***
equal to not equal to greater than not greater than less than not less than	Constant Field Expression Subquery Prompt
Exists not exists	Subquery
Like not like	Constant (with wildcards) Prompt
is null is not null	
in tree not in tree	Tree Option Tree Prompt Option
Eff Date <= Eff Date >= Eff Date < EffDate >	Field Expression Constant Current Date

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Operator	*Expression 2*
First Eff Date Last Eff Date	
in list not in list	In list Subquery
Between Not Between	Const-Const Const-Field Const-Expr Field-Const Field-Field Field-Expr Expr-Const Expr-Field Expr-Expr

Related Links

Operator

Setting a Drilling URL

A *drilling* URL provides a clickable link in query results allowing a user to drill from the query results to another query, to another component, or to an external site. A drilling URL is defined as a special type of query expression. Like other query expressions, the user can set the drilling URL on the Edit Expression Properties page, or the drilling URL can be set in a PeopleCode program as follows:

```
/* Setting a drilling URL */

&aQueryExpr = &aQuerySelect.AddExpression(&sExprName);

/* Set the expression type to drilling URL */
&aQueryExpr.Type = %FieldType_URL;

/* Set the expression text and number from record fields */
/* The Text property must conform to expected formats    */
&aQueryExpr.Text = &rRecordExpr.QRYCRIT1EXPRTEXT.Value;
&aQueryExpr.ExpNum = &rRecordExpr.QRYCRIT1EXPRNUM.Value;
```

Note: Run-time processing of drilling URLs is backward compatible. Therefore, drilling URLs that were defined in previous releases are expanded correctly in the current release without the need to redefine them.

For a drilling URL, the Text property of the QueryExpression object must conform to one of three expected formats. The value of the Text property is not validated; therefore, it is the calling program's responsibility to ensure that value is complete and correctly formatted. Each of the drilling URL types has a different format as follows:

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- The drilling URL for a component requires the following format:

  ```
  '/c/menu.component.market?Action=Usearch_key=unique_field:unique_field_URL_is_⇒
  mapped_to'
  ```

  For example:

  ```
  '/c/QE_SAMPLE_APPS.QE_DEPT_TBL.GBL?Action=U&DEPTID=A.DEPTID&SETID=A.SETID:A.SE⇒
  TID'
  ```

- The drilling URL for a query requires the following format:

  ```
  '/q/?ICAction=ICQryNameURL={PUBLIC|PRIVATE}.query_name&unique_prompt_key=uniqu⇒
  e_field:unique_field_URL_is_mapped_to'
  ```

  For example:

  ```
  '/q/?ICAction=ICQryNameURL=PUBLIC.DESTINATION&BIND1=A.DEPTID:B.DEPTID'
  ```

- The drilling URL for an external site requires the following format:

  ```
  '/e/?url=[full_external_URL]:unique_field_URL_is_mapped_to'
  ```

  For example:

  ```
  '/e/?url=[http://www.yahoo.com]:A.SETID'
  ```

Related Links

AddTrackingURL
SetTrackingURL
Text
Type
"Drilling URL in PeopleSoft Query" (PeopleTools 8.54: Query)

Query Monitor

The query classes provide many methods and properties for examining the QueryStatistics, which you can use to report on the average execution time, the last date and time the query was run, and so on.

You can view the statistics for a query before you save it to the database.

Related Links

"PeopleSoft Query Overview" (PeopleTools 8.54: Query)

Using Query Metadata

There are two ways of accessing information about a query:

- The query classes (QueryOutputField, QueryRecord, and so on).
- The Metadata property.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

If you use the Metadata property, the information is presented in a different format. It is also read-only. Using this property can be a quick and easy way to access information about a query.

Each Query Metadata object is a name-value pair. *Name* is an indicator of which Query Metadata property you're accessing, and *Value* is the value of that property.

While the value of each Query Metadata property is unique, the name may or may not be. For example, there is only one description (Descr) for each query, so there is only one Query Metadata property with *name* equal to Descr and *value* equal to the description for the query.

However, there may be more than one record for a query. A Query Metadata property exists for each record, with *name* equal to Record and *value* equal to one of the records in the query. The same is true for Input Param, Expression, Field, and Heading.

The following is a simple PeopleCode program to get the Query Metadata for a private query, ADDRESS_TEMP:

```
Local ApiObject &MyQuery, &MyMetacol, &MyMetadata;
Local File &MyFile;

&MyFile = GetFile("Metadata.Txt", "A");

&MyQuery = %Session.GetQuery();

&Rlst = &MyQuery.Open("ADDRESS_TEMP", False, 1);

If &Rlst = 0 Then
   &MyMetacol = &MyQuery.metadata;
   &MyFile.WriteLine("Name              Value");
   &MyFile.WriteLine("-----------------------");

   For &i = 1 To &MyMetacol.count
      &MyMetadata = &MyMetacol.item(&i);
      &Name = &MyMetadata.name;
      &Value = &MyMetadata.Value;
      &MyFile.WriteLine(&Name | "              " | &Value);
   End-For;

Else
   WinMessage("Open query not successful");
End-If;
```

Here is the sample output:

```
Name              Value
-----------------------
Descr             Temporary address query for testing
LongDescr
Public/Private    QEDMO
LastUpdDttm       2001-11-19-15.06.22.930000
LastUpdOprId      QEDMO
Record            QE_PERS_DATA
Field             QE_EMPLID
Field             QE_NAME
Field             ADDRESS1
Field             ADDRESS2
Field             ADDRESS3
Field             ADDRESS4
Field             CITY
Field             COUNTY
Field             STATE
Field             QE_ZIP
Field             QE_COUNTRY
Heading           ID
Heading           Name
Heading           Address 1
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
Heading           Address 2
Heading           Address 3
Heading           Address 4
Heading           City
Heading           County
Heading           St
Heading           QE_ZIP
Heading           QE_COUNTRY
```

Running a Query

With query API, you have the following options for running a query:

- Using the RunToRowset method.

  This method takes a QueryPrompt record as input and returns a PeopleCode rowset containing the query result. You should always use a standalone rowset (that is, one that was created using CreateRowset).

- Using the RunToFile method.

  This method takes a QueryPrompt record and a file name as input and writes the query result to the file.

- Using the RunToString method.

  This method takes a QueryPrompt record and writes the query result to a formatted string.

Note: For the query classes, all Date, Time, and DateTime fields that are part of a query are now required fields when running a query.

Considerations Using the RunTo Methods

RunToRowset may require a lot of memory for the Rowset object; therefore, it also takes more processing time. PeopleSoft recommends that RunToRowset not be used for retrieving large result sets, on the order of 50,000 or more items.

All of the RunTo methods can be called to run a query before saving it—that is, it isn't necessary to first save the query.

The last parameter of all of the RunTo methods is the maximum number of rows to fetch.

- -1 returns all rows regardless of the setting on the security profile.
- 0 returns the maximum number of rows allowed by the security profile.
- >0 is the limit on the number of rows.

Related Links

RunToFile
RunToRowset
RunToString

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Specifying the User's Language

For scheduled queries, the system uses the language specified in the user's profile. It does not use the language selected during signon. The system also uses the International and Regional settings the user specified using My Personalizations. If no personal setting have been specified, the system uses the default installation international settings.

Note: Most PeopleSoft components can default to international settings from the browser if the user has not set any user specific settings. However, this is not available for scheduled queries or any Process Scheduler processes.

Query Security

Security is critical for your business data. Typically, you don't want everyone in your company to have access to all the data. All the standard security features used with PeopleSoft applications are integrated in the PeopleSoft Query, as well as the query classes.

In addition, you can use the QuerySecurityProfile Class to view the current user's security profile for PeopleSoft Query. This class doesn't contain any methods, and all the properties are read-only.

Related Links

QuerySecurityProfile Class

"Security Basics" (PeopleTools 8.54: Security Administration)

Error Handling With Query Classes

All errors for the query classes, like the other APIs, are logged in the PSMessages collection, instantiated from a session object. In addition, some methods return error codes. See the individual method description to see if it returns anything.

The query classes log errors "interactively", that is, as they happen. For example, suppose you specified an invalid query name. The error would be logged in the PSMessages collection as soon as you executed the GetQuery method.

When to check for errors is application-specific. However, if you check for errors after every assignment, you may see a performance degradation.

PeopleSoft recommends that you check for invalid prompts after using any of the following methods or properties:

- Save, RunToRowset, or RunToFile Query class methods.
- SQL, RuntimePrompts, or Prompts Query class properties.
- Any of the methods or properties in the QueryPrompts collection.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The easiest way to check for errors is to check the number of messages in the PSMessages collection, using the Count property. If the Count is 0, there are no errors.

```
Local ApiObject &MySession;
Local ApiObject &ERRORCOL;
Local ApiObject &Query, &QueryList;

&MySession = %Session;

If &MySession Then
   /* connection is good */

   &QueryList = &MySession.SearchPublicQueries(%Query_ListQuery, %Query_FindName, "⇒
%", True);

   For &I = 1 to &QueryList.Count
      &Query = &QueryList.Item(&I);

      /* Do processing */

      /* Do error checking */

      &ERRORCOL = &MySession.PSMessages;
      If (&ERRORCOL.Count <> 0) Then
         /* errors occurred - do processing */
      Else
         /* no errors */
      End-If;

   End-For;
Else
   /* do processing for no connection */
End-If;
```

Related Links

Error Handling

Understanding QueryOutputFields and QuerySelectedFields

If you select a field from a Query Record, it becomes a QueryOutputField, that is, it becomes one of the columns in the SQL output. QuerySelectedFields consist of displayed fields and Query Expression Fields.

QuerySelectedFields and QueryOutputFields have all the same methods and properties, so in this documentation, they're described together under the heading QueryField.

The collection of QueryOutputFields does *not* necessarily include all columns returned in query resultset. This collection only includes columns that have been added to query output collection using the query classes or by an end-user designing a query.

PeopleSoft Query can also add additional columns for related language processing and also for translate labels on fields, and so you cannot use the Query Output Collections as a way to discover all of the columns that are returned in the resultset or by executing the SQL generated from a query.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Understanding Having Criteria

You can have where (simple) criteria or having criteria in a query. In most cases, you have a WHERE clause only—that is, simple criteria. Having criteria is only used in some special cases of aggregation queries. They represent the HAVING clause of the SQL statement, similar to the following:

```
select A.DEPTID, COUNT(A.EMPLID)

from PS_QE_EMPLOYEE A

group by A.DEPTID

having COUNT(A.EMPLID)>5
```

Having criteria are separated from simple criteria. They're accessed as follows:

- Having criteria are accessed using either the AddHavingCriteria QuerySelect method or HavingCriteria QuerySelect property
- Simple criteria are accessed using either the AddCriteria QuerySelect method or the Criteria QuerySelect property.
- However, the having criteria and the simple criteria have all the same methods and properties, so in this documentation, they're described together under the heading QueryCriteria.

Related Links

"Defining HAVING Criteria" (PeopleTools 8.54: Query)

Data Type of Query Objects

All query objects, like a query collection, a QueryDBRecord, a QueryExpression, and so on, are declared as type ApiObject. For example,

```
Global ApiObject &MyQuery;

Local ApiObject &MyExpression;
```

Scope of Query Objects

All query objects can be instantiated from PeopleCode only.

You can use this object anywhere you have PeopleCode—that is, in an application class, Application Engine PeopleCode, record field PeopleCode, and so on.

You can only instantiate a query object from a Session object. You *must* instantiate the Session object before you can instantiate a query object or query collection. Use the %Session system variable to connect to the existing session.

```
Local ApiObject &QueryList;
Local ApiObject &MySession;

&MySession = %Session;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
If &MySession <> Null Then
   /* connection is good */
   /* Search for public queries of type QUERY, search both the name and*/
   /* description for the pattern MyQ%, and do a case insensitive search */

   &QueryList = &MySession.SearchPublicQueries(1, 3, "MyQ%", False);
Else
   /* do error processing */
End-if;
```

Query Classes Reference

This section provides a reference to the following topics:

- Session class methods in the query API.
- Query collection.
- Query class.
- QuerySelect collection.
- QuerySelect class.
- QueryRecord collection.
- QueryRecord class.
- QueryField collection.
- QueryField class.
- QueryCriteria collection.
- QueryCriteria class.
- QueryExpression collection.
- QueryExpression class.
- QueryList class.
- QueryListValue class.
- QueryRecordHierarchy collection.
- QueryRecordHierarchy class.
- Query Metadata collection.
- Query Metadata class.
- QueryStatistics class.
- QuerySecurityProfile class.
- QueryDBRecord collection.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- QueryDBRecord class.
- QueryDBRecordField collection.
- QueryDBRecordField class.
- QueryPrompt collection.
- QueryPrompt class.

Session Class Methods in the Query API

The following methods are part of the query API. However, they're used with a Session object.

Related Links

Understanding Session Class

AdvancedSearchQueries

Syntax

```
AdvancedSearchQueries(GetFavorites, QueryName, QueryNameOp, Descr, DescrOp,
FolderName, FolderNameOp, RecordName, RecordNameOp, FieldName, FieldNameOp, TreeName,
TreeNameOp, QueryType, OwnerType, CaseSensitive)
```

Description

Use the AdvancedSearchQueries method to do more complex searches for queries.

Using Search Operators

All of the parameters for this method work in pairs, with the value in the first of the paired parameters further distinguished by the search operator used in the second parameter. For example, the value specified in *FieldName* is paired with the value specified in *FieldNameOp*.

All of the search operator parameters use the following values. Note that the format of the value of the first parameter is sometimes affected by the value of the search operator parameter.

Constant	*Description*
%Query_AdvSrchBegins	Name begins with the values specified.
%Query_AdvSrchContains	Name contains the value specified.
%Query_AdvSrchEquals	Name equals the value specified.
%Query_AdvSrchNotEquals	The name does not equal the value specified.
%Query_AdvSrchLessThan	The name is less than the value specified.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Constant	Description
%Query_AdvSrchLessEquals	The name is less than or equal to the value specified.
%Query_AdvSrchGreaterThan	The name is greater than the value specified.
%Query_AdvSrchGreaterEquals	The name is greater than or equal to the value specified.
%Query_AdvSrchBetween	The name is between two values specified by a comma. Do not use quotation marks. For example, ACCT1,ACCT9.
%Query_AdvSrchIn	The name is in the list specified list. The values are separated with commas. Do not use quotation marks. For example, ACCT1, ACCT2, ACCT3

Parameters

GetFavorites Specify whether to return only queries marked as favorites. This parameter takes a Boolean value: true if you only want favorite queries returned, false otherwise. If you specify true for this parameter, all other parameters are ignored.

QueryName Specify the name of the query you want returned, as a string. Use this parameter with the *QueryNameOp* parameter.

QueryNameOp Specify the operator to be used with the *QueryName* parameter. The valid values for this parameter are found in the Using Search Operators section, above.

Descr Specify the description you want returned, as a string. Use this parameter with the *DescrOp* parameter.

DescrOp Specify the operator to be used with the *Descr* parameter. The valid values for this parameter are found in the Using Search Operators section, above.

FolderName Specify the name of the folder of the query or queries you want returned, as a string. Use this parameter with the *FolderNameOp* parameter.

FolderNameOp Specify the operator to be used with the *FolderName* parameter. The valid values for this parameter are found in the Using Search Operators section, above.

RecordName Specify the name of the record used with the query (queries) you want returned, as a string. Use this parameter with the *RecordNameOp* parameter.

RecordNameOp Specify the operator to be used with the *RecordName* parameter. The valid values for this parameter are found in the Using Search Operators section, above.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

FieldName Specify the name of the field associated with the query (queries) you want returned, as a string. Use this parameter with the *FieldNameOp* parameter.

FieldNameOp Specify the operator to be used with the *FieldName* parameter. The valid values for this parameter are found in the Using Search Operators section, above.

TreeName Specify the name of the tree associated with the query (queries) you want returned, as a string. Use this parameter with the *TreeNameOp* parameter.

TreeNameOp Specify the operator to be used with the *TreeName* parameter. The valid values for this parameter are found in the Using Search Operators section, above.

QueryType Specify the type of query, as a string. See below.

OwnerType Specify the type of owner, whether the query is public or private.

CaseSensitive This parameter has not yet been implemented.

The values for *QueryType* can be as follows:

Numeric Value	*Constant Value*	*Description*
1	%Query_Query	Find queries of the type Query.
5	%Query_DBAgent	Find queries of the type Process.
4	%Query_Role	Find queries of the type Role
7	%Query_Archive	Find queries of the type Archive.

Returns

A reference to a Query collection containing zero or more queries.

Note: If the result set contains more than 300 rows, only the first 300 rows are returned.

AdvancedSearchRecords

Syntax

```
AdvancedSearchRecords(RecordName, RecordNameOp, Descr, DescrOp, FieldName,
FieldNameOp, TreeName, TreeNameOp, CaseSensitive)
```

Description

Use the AdvancedSearchRecords method to do more complex searches for records.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Security applies to the results of this list, that is, you have access to all the records your user ID (permission list) allows you to access.

Using Search Operators

All of the parameters for this method work in pairs, with the value in the first of the paired parameters further distinguished by the search operator used in the second parameter. For example, the value specified in *FieldName* is paired with the value specified in *FieldNameOp.*

All of the search operator paramerters use the following values. Note that the format of the value of the first parameter is sometimes affected by the value of the search operator parameter.

Constant	***Description***
%Query_AdvSrchBegins	Name begins with the values specified.
%Query_AdvSrchContains	Name contains the value specified.
%Query_AdvSrchEquals	Name equals the value specified.
%Query_AdvSrchNotEquals	The name does not equal the value specified.
%Query_AdvSrchLessThan	The name is less than the value specified.
%Query_AdvSrchLessEquals	The name is less than or equal to the value specified.
%Query_AdvSrchGreaterThan	The name is greater than the value specified.
%Query_AdvSrchGreaterEquals	The name is greater than or equal to the value specified.
%Query_AdvSrchBetween	The name is between two values specified by a comma. Do not use quotation marks. For example, ACCT1,ACCT9.
%Query_AdvSrchIn	The name is in the list specified list. The values are separated with commas. Do not use quotation marks. For example, ACCT1, ACCT2, ACCT3

Parameters

RecordName Specify the name of the record you want returned, as a string. Use this parameter with the *RecordNameOp* parameter.

RecordNameOp Specify the operator to be used with the *RecordName* parameter. The valid values for this parameter are found in the Using Search Operators section, above.

Descr Specify the description you want returned, as a string. Use this parameter with the *DescrOp* parameter.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

DescrOp

Specify the operator to be used with the *Descr* parameter. The valid values for this parameter are found in the Using Search Operators section, above.

FolderName

Specify the name of the folder of the records you want returned, as a string. Use this parameter with the *FolderNameOp* parameter.

FolderNameOp

Specify the operator to be used with the *FolderName* parameter. The valid values for this parameter are found in the Using Search Operators section, above.

FieldName

Specify the name of the field associated with the record you want returned, as a string. Use this parameter with the *FieldNameOp* parameter.

FieldNameOp

Specify the operator to be used with the *FieldName* parameter. The valid values for this parameter are found in the Using Search Operators section, above.

TreeName

Specify the name of the tree associated with the record you want returned, as a string. Use this parameter with the *TreeNameOp* parameter.

TreeNameOp

Specify the operator to be used with the *TreeName* parameter. The valid values for this parameter are found in the Using Search Operators section, above.

CaseSensitive

Note: This parameter has not been implemented yet.

Specify whether the search is case-sensitive. This parameter takes a Boolean value: True, the search is case-sensitive, False, it isn't.

Returns

A reference to a QueryDBRecord collection containing zero or more records.

Note: If the result set contains more than 300 rows, only the first 300 rows are returned.

FindQueryDBRecords

Syntax

`FindQueryDBRecords``()`

Description

The FindQueryDBRecords method returns a reference to a QueryDBRecord collection, filled with zero or more records.

Security applies to the results of this list, that is, you have access to all the records your user ID (permission list) allows you to access.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

None.

Returns

A reference to a QueryDBRecord collection containing zero or more records.

Related Links

QueryDBRecord Collection
QueryDBRecord Class

FindQueries

Syntax

FindQueries()

Description

The FindQueries method returns a reference to a Query collection, filled with zero or more queries.

FindQueries Considerations

FindQueries returns both public and private queries. It depends on your database whether the private query is returned first or the public query. If you have two queries with the same name, it depends on your database whether the first use of Item returns the private or the public query.

Parameters

None.

Returns

A reference to a Query collection containing zero or more queries.

Example

In the following example, all available queries are returned:

```
Local ApiObject &MySession;
Local ApiObject &MyList;

&MySession = %Session
&MyList = &MySession.FindQueries();
```

Related Links

Open
FindQueriesDateRange
FindQueriesDateRange
Query Collection

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

FindQueriesDateRange

Syntax

FindQueriesDateRange(*StartDateString*, *EndDateString*)

Description

The FindQueriesDateRange method returns a reference to a Query collection, filled with zero or more queries that match the specified date range.

FindQueriesDateRange Considerations

FindQueriesDateRange returns both public and private queries. It depends on your database whether the private query is returned first or the public query. If you have two queries with the same name, it depends on your database whether the first use of Item returns the private or the public query.

Parameters

StartDateString Specify the year, month, and day of the beginning date that you want to look for. This parameter takes a string value. You can specify the date either as YYYY-MM-DD *or* YYYY/MM/DD.

EndDateString Specify the year, month, and day of the end date. This parameter takes a string value. You can specify the date either as YYYY-MM-DD *or*YYYY/MM/DD.

Returns

A reference to a Query collection containing zero or more queries.

Example

```
Local ApiObject &MySession, &QueryList;

&MySession = %Session;

&Start = GetField(VOLUN_ACT_WRK.START_DT_STR).Value;
&End = GetField(VOLUN_ACT_WRK.END_DT_STR).Value;

&QueryList = &MySession.FindQueriesDateRange(&Start, &End);
```

Related Links

FindQueries
Open
Query Collection

GetQuery

Syntax

GetQuery()

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

The GetQuery method returns an empty query object. After you have an empty query object, you can use it to open an existing query (using the Open method) or to create a new query definition (using the Create method).

Parameters

None.

Returns

A reference to an empty query object if successful, NULL otherwise.

Example

```
&MyQuery = &MySession.GetQuery();

If &MyQuery.Open("PHONELIST") Then
```

Related Links

FindQueries
FindQueriesDateRange
Open
Create

GetQuerySecurityProfile

Syntax

GetQuerySecurityProfile()

Description

Use GetQuerySecurityProfile to return the current user's security profile for PeopleSoft Query. You can then use the QuerySecurityProfile properties to determine if the user can modify queries, the maximum number of rows to fetch for this user, and so on.

Parameters

None.

Returns

A reference to a QuerySecurityProfile if successful, NULL otherwise.

Example

```
&MySecProfile = %Session.GetQuerySecurityProfile();
If &MySecProfile.CanModifyQuery Then
   /* do some processing */
End-If;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

QuerySecurityProfile Class

SearchQueryDBRecords

Syntax

SearchQueryDBRecords(*SearchType*, *Pattern*, *CaseSensitive*)

Description

The SearchQueryDBRecords method returns a reference to a QueryDBRecord collection, filled with zero or more records.

Security applies to the results of this list, that is, you have access to all the records your user ID (permission list) allows you to access.

You can use wildcard characters % and _ when searching. % means find all characters, while _ means find a single character. For example, if you wanted to find all queries that started with the letter M, use "M%" for *Pattern*. To find either DATE or DATA, use "DAT_" for *Pattern*.

These characters can be escaped (that is, ignored) using a \. For example, to search for a query that contains the character %, use \% in *Pattern*.

If *Pattern* is an empty string, this method retrieves all queries of the specified type (that is, specifying "" for *Pattern* is the same as specifying "%").

Parameters

SearchType Specify the type of search to be used with the given pattern. You can use either a constant or a number value for this parameter. See below.

Pattern Specify the pattern to be used when searching for records.

CaseSensitive Specify whether the search is case-sensitive. This parameter takes a Boolean value: True, the search is case-sensitive, False, it isn't.

The values for *SearchType* can be as follows:

Numeric Value	*Constant Value*	*Description*
1	%Query_FindName	Search for records with the name matching the given pattern.
2	%Query_FindDescr	Search for records with the description matching the given pattern.
3	%Query_FindNameDescr	Search for records with either the name or the description matching the given pattern.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

A reference to a QueryDBRecord collection containing zero or more records.

Example

```
Local ApiObject &MySession, &DBRecList;

&MySession = %Session;

DBRecList = &MySession.SearchQueryDBRecords(%Query_FindName, "A%", False);
```

Related Links

FindQueryDBRecords

SearchPrivateQueries

Syntax

SearchPrivateQueries(*QueryType*, *UserId*, *SearchType*, *Pattern*, *CaseSensitive*)

Description

The SearchPrivateQueries method returns a reference to a Query collection, filled with zero or more Private queries that match the specified *SearchType*, *UserId*, *Pattern*, and *CaseSensitive* choice

Parameters

QueryType Specify the type of query to be searched for. You can specify either a constant or number value for this parameter. See below.

UserId Specify the user Id to be used to find currently signed-on user's private queries.

SearchType Specify the type of search to be used with the given pattern. You can use either a constant or a number value for this parameter. See below.

Pattern Specify the pattern to be used when searching for queries.

CaseSensitive Specify whether the search is case-sensitive. This parameter takes a Boolean value: True, the search is case-sensitive, False, it isn't.

The values for *QueryType* can be as follows:

Numeric Value	*Constant Value*	*Description*
1	%Query_Query	Find queries of the type Query.
3	%Query_DBAgent	Find queries of the type Process.
4	%Query_Role	Find queries of the type Role

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Numeric Value	Constant Value	Description
10	N/A	Find queries of the type Archive.

The values for *SearchType* can be as follows:

Numeric Value	Constant Value	Description
1	%Query_FindName	Search for queries with the name matching the given pattern.
2	%Query_FindDescr	Search for queries with the description matching the given pattern.
3	%Query_FindNameDescr	Search for queries with either the name or the description matching the given pattern.

Returns

A reference to a Query collection containing zero or more queries.

Example

The following example retrieves all private queries of type Query which start with A and do a case-insensitive search, that is, get all queries starting with A or a.

```
Local ApiObject &MySession, &DBRecList;

&MySession = %Session;

DBRecList = &MySession.SearchPrivateQueries(%Query_ListQuery, %UserId, %Query_FindN⇒
ame, "A%", False);
```

Related Links

FindQueries
FindQueriesDateRange
SearchPublicQueries

SearchPublicQueries

Syntax

SearchPublicQueries(*QueryType, SearchType, Pattern, CaseSensitive*)

Description

The SearchPublicQueries method returns a reference to a Query collection, filled with zero or more Public queries that match the specified *SearchType*, *Pattern,* and *CaseSensitive* choice.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

QueryType Specify the type of query to be searched for. You can specify either a constant or number value for this parameter. See below.

SearchType Specify the type of search to be used with the given pattern. You can use either a constant or a number value for this parameter. See below.

Pattern Specify the pattern to be used when searching for queries.

CaseSensitive Specify whether the search is case-sensitive. This parameter takes a Boolean value: True, the search is case-sensitive, False, it isn't.

The values for *QueryType* can be as follows:

Numeric Value	***Constant Value***	***Description***
1	%Query_ListQuery	Find queries of the type Query.
3	%Query_ListDBAgent	Find queries of the type Process
4	%Query_ListRole	Find queries of the type Role
10	N/A	Find queries of type Archive

The values for *SearchType* can be as follows:

Numeric Value	***Constant Value***	***Description***
1	%Query_FindName	Search for queries with the name matching the given pattern.
2	%Query_FindDescr	Search for queries with the description matching the given pattern.
3	%Query_FindNameDescr	Search for queries with either the name or the description matching the given pattern.

Returns

A reference to a Query collection containing zero or more queries.

Example

The following example retrieves all public queries of type Query that start with A and does a case-insensitive search, that is, get all queries starting with A or a.

```
Local ApiObject &MySession, &DBRecList;

&MySession = %Session;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
DBRecList = &MySession.SearchPublicQueries(%Query_ListQuery, %Query_FindName, "A%",⇒
 False);
```

Related Links

FindQueries
FindQueriesDateRange
SearchPrivateQueries

Query Collection

A query collection is returned from the following session methods:

- AdvancedSearchQueries
- FindQueries
- FindQueriesDateRange
- SearchPrivateQueries
- SearchPublicQueries

Related Links

AdvancedSearchQueries
FindQueries
FindQueriesDateRange
SearchPublicQueries
SearchPrivateQueries

Query Collection Methods

In this section, we discuss each query collection method.

First

Syntax

```
First()
```

Description

The First method returns the first Query object in the Query collection.

Parameters

None.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

A reference to a Query object if successful, NULL otherwise.

Example

```
&MyQuery = &MyCollection.First();
```

Item

Syntax

Item(*number*)

Description

The Item method returns the Query object that exists at the *number* position in the Query collection.

Item Considerations

FindQueries and FindQueriesDateRange return both public and private queries. It depends on your database whether the private query is returned first or the public query. If you have two queries with the same name, it depends on your database whether the first use of Item returns the private or the public query.

Parameters

Number	Specify the position number in the collection of the Query object that you want returned.

Returns

A reference to a Query object if successful, NULL otherwise.

Example

```
For &I = 1 to &QueryColl.Count;
   &MyQuery = &QueryColl.Item(&I);
   /* do processing */
End-For;
```

ItemByName

Syntax

ItemByName(*Name*)

Description

The ItemByName method returns the Query object with the name *Name*.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

Name	Specify the name of an existing Query within the Query collection. If you specify an invalid name, the object is NULL. The length of this parameter is 30 characters.

Returns

A reference to a Query object if successful, NULL otherwise.

Example

```
&MyQuery = &MyCollection.ItemByName("PHONELIST");
```

Next

Syntax

```
Next()
```

Description

The Next method returns the next Query object in the Query collection. You can use this method only after you have used the First method: otherwise the system doesn't know where to start.

Parameters

None.

Returns

A reference to a Query object if successful, NULL otherwise.

Example

```
&MyQuery = &MyCollection.Next();
```

Query Collection Property

In this section, we discuss the Count query collection property.

Count

Description

This property returns the number of Query objects in the Query collection, as a number.

This property is read-only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

```
&COUNT = &MY_COLLECTION.Count;
```

Query Class

A query object is returned from the following:

- The GetQuery session method.
- The Query collection methods First, Item, ItemByName, or Next.

See GetQuery.

See Query Collection.

Query Class Methods

In this section, we discuss each Query class method in alphabetical order.

AddPrompt

Syntax

AddPrompt(*PromptName*)

Description

The AddPrompt method adds a prompt with the given name to the query definition. This method returns a new QueryPrompt object that you can then use to specify details about the prompt.

Note: Prompt names are *not* checked for uniqueness. Each new prompt is just added to the list of prompts.

Parameters

PromptName	Specify the name of the new prompt with a string. The length of this parameter is 30 characters.

Returns

A reference to a QueryPrompt object.

Related Links

DeletePrompt
Prompts
QueryPrompt Class

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

AddQuerySelect

Syntax

AddQuerySelect()

Description

Use the AddQuerySelect method to add the first Query Select statement into the query definition. This method returns the instance of the newly created QuerySelect.

Parameters

None.

Returns

A reference to a QuerySelect object. If the query already contains the Main Select, it returns NULL.

Related Links

QuerySelect Collection

AddTrackingURL

Syntax

AddTrackingURL(*URLString*)

Description

Use this method to define the base URL used to construct a fully qualified drilling URL. A base URL consists of the following elements:

http://*server_name*/*servlet_name*/*site_name*/*portal_name*/*node_name*

For example:

http://server.mycompany.com:8080/psp/ps_2/EMPLOYEE/EMP_LOCAL

Because a base URL can be set or derived in several ways, the use of AddTrackingURL is required only when the calling program does not have current context to identify the site, portal, and node and the elements of the base URL (portal name, node name, and content type) were not defined when the drilling URL was defined. Specifically, the base URL can be set or derived as follows:

- The portal name, node name, and content type can be defined as optional elements of the query drilling URL definition.
- The portal name, node name, and content type can be derived from the current context (that is, from the URL of the logged in user who is executing the query).
- Finally, these elements can be defined programmatically through AddTrackingURL. If either of the first two bullets is true, then the value specified by AddTrackingURL is ignored.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Note: The string passed in as the base URL is not validated; therefore, it is the application developer's responsibility to ensure that the value is complete and correctly formatted.

Use this method for batch programs such as Application Engine programs do not operate in the context of a site, portal, and node. Consequently, prior to invoking an Application Engine program, the calling program needs to define and store the base URL so that the Application Engine program can use this stored value with the AddTrackingURL method.

Parameters

URLString	Specify the base URL as a string. The base URL is used to construct a fully qualified drilling URL.

Returns

None.

Example

The ExecQry step of the PSQUERY Application Engine program invokes the AddTrackingURL method using a value stored in the run control table prior to executing the query.

```
&aQry = %Session.GetQuery();
If &aQry.Open(PSQUERY_AET.QRYNAME, &bPublic, False) = 0 Then

   &aQry.AddTrackingURL(PSQUERY_AET.URL);
   ...
   &Result = &aQry.RunToFile(&rcdQryPrompts, &sOutFile, %OutDestFormat, 0);
End-if;
```

Related Links

SetTrackingURL

Setting a Drilling URL

"Drilling URL in PeopleSoft Query" (PeopleTools 8.54: Query)

Close

Syntax

Close()

Description

The Close method closes the query, freeing the memory associated with that object, and discarding any changes made to the query since the last save. The Close method can be used only on an open query, not a closed query. This means you must have opened the query with the Open or Create methods before you can close it. To save any changes, you must use the Save method before using Close.

It's very important to close your query when you're finished processing. Canceling out of a page does *not* close a query. You may receive error messages every other time you run your program if you haven't closed your queries.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

None.

Returns

None.

Related Links

Open
Save
Create

CopyPrivateQuery

Syntax

CopyPrivateQuery(*QueryName*, *QryType*, *TargetUserID*)

Description

The CopyPrivateQuery method copies the query from the current user to a user specified by the target user ID.

Parameters

QueryName Name of the query to be copied, as a string.

QryType Specify the type of query. This parameter takes either a numeric or constant value. See below.

TargetUserID The user ID to which the query is to be copied, as a string.

The values for *QryType* can be as follows:

Numeric Value	*Constant Value*	*Description*
1	%Query_Query	Find queries of the type Query.
4	%Query_Role	Find queries of the type Role.
5	%Query_DBAgent	Find queries of the type Process.
7	%Query_Archive	Find queries of the type Archive.

Returns

0 if successful.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Create

Syntax

Create(*QueryName, Public, Type, Description, LongDescription*)

Description

The Create method creates a new query, based on the parameters passed with the method. The specified query must be a *new* query.

Warning! If you specify the name of a query that already exists, the existing query is overwritten by the new query.

The Create method can be used only with a closed query, it cannot be used on an open query.

After you create a new query, you don't have to open it with the Open method. The existing query object points to the new query.

Creating a new query doesn't create the query in the database. You must save the query (with the Save method) to commit it to the database.

Parameters

QueryName Name of the query to be created. This parameter takes a string value. This parameter takes 30 characters. A query name can contain only US ASCII alphabetic and numeric characters, as well as underscores.

Public Specify if the query is public or private. This parameter takes a Boolean value: True if the query is public, False if it's a private query.

Type Specify the type of query. This parameter takes either a numeric or constant value. See below.

Description Specify a short description for the query. This parameter takes a string value. This parameter takes 30 characters.

LongDescription Specify a long description for the query. This parameter takes a string value. The length of this parameter depends on your system database limit for LONG fields.

The values for *Type* can be as follows:

Numeric Value	***Constant Value***	***Description***
1	%Query_Query	Query
3	%Query_View	View
4	%Query_Role	Role

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Numeric Value	*Constant Value*	*Description*
5	%Query_DBAgent	Process
7	%Query_Archive	Archive

Returns

An integer value: 0 means the query was created successfully.

Example

```
/* Use the existing session */

&MySession = %Session;

&MyQry = &MySession.GetQuery();

/* create a new query : public type-User */
&Rslt = &MyQry.Create("MYQUERY", True, %Query_Query, "My Query", "My first Query");⇒


If &Rslt = 0 Then
   /* Query created successfully */
Else
   /* do error processing */
End-If;
```

Related Links

GetQuery
Close
Save

Delete

Syntax

Delete()

Description

The Delete method deletes the specified query from the database. The Delete method can be used only with an open query, it cannot be used on a closed query. Before you use the Delete method, you must explicitly open the query object to be deleted (with either the Open or Create method.)

Parameters

None.

Returns

An integer value: 0 means the query was deleted successfully.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

Save

DeletePrompt

Syntax

DeletePrompt(*PromptNumber*)

Description

The DeletePrompt method deletes a prompt from a query definition.

Parameters

PromptNumber	Specify the numeric location in the query definition of the prompt that you want to delete.

Returns

An integer value: 0 means the query was deleted successfully.

Related Links

AddPrompt
Prompts
QueryPrompt Class

FindExpression

Syntax

FindExpression(*ExpressionNumber*)

Description

Use the FindExpression method to search the query definition for an expression with the given expression number. Although expressions are associated with the QuerySelect in which they are defined, PeopleSoft Query doesn't qualify expressions by Select number. Therefore, each expression has a unique number across all QuerySelect objects.

Parameters

ExpressionNumber	Specify the numeric value of the expression number to be searched for in the query definition.

Returns

A QueryExpression object if successful, NULL otherwise.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

AddPrompt
Prompts
QueryPrompt Class

FormatBinaryResultString

Syntax

```
FormatBinaryResultString(&Rowset, Output_Format, Start_Row, End_Row)
```

Description

Use the FormatBinaryResultString method to generate a string containing the content of the input (the rowset) in XLS format. You can specify the range of rows to be in the rowset to be used as input. The rowset object is created using the RunToRowset method.

Parameters

&Rowset Specify an already instantiated and populated rowset object containing the query result. This rowset is created using the RunToRowset method.

Output_Format Specify the format of the output. You can specify either a numeric or constant value. See below.

Start_Row Specify the first row in the rowset that you want to use for output. This parameter takes a numeric value.

End_Row Specify the last row in the rowset that you want to use for output. This parameter takes a numeric value.

The values for *Output_Format* can be as follows:

Numeric Value	*Constant Value*	*Description*
8	%Query_XLS	The output for Excel in HTML format.

Returns

A binary object containing the formatted output.

Example

```
/* Use RowCount, not ActiveRowCount, to get the total number of rows. */

&End = &MyRowset.RowCount;

&FormString = &MyQuery.FormatBinaryResultString (&MyRowset, %Query_XLS, 1, &End);
```

Related Links

RunToFile

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

RunToRowset

FormatResultString

Syntax

```
FormatResultString(&Rowset, Output_Format, StartRow, EndRow)
```

Description

Use the FormatResultString method to generate a string containing the content of the input (the rowset) in HTML, PDF, XLS, or CSV format. You can specify the range of rows to be in the rowset to be used as input. The rowset object is created using the RunToRowset method.

Parameters

&Rowset Specify an already instantiated and populated rowset object containing the query result. This rowset is created using the RunToRowset method.

Output_Format Specify the format of the output. You can specify either a numeric or constant value. See below.

Start_Row Specify the first row in the rowset that you want to use for output. This parameter takes a numeric value.

End_Row Specify the last row in the rowset that you want to use for output. This parameter takes a numeric value.

The values for *Output_Format* can be as follows:

Numeric Value	*Constant Value*	*Description*
2	%Query_PDF	The output is in PDF format.
5	%Query_HTML	The output is in HTML format.
8	%Query_XLS	The output for Excel in HTML format.
14	%Query_TXT	The output for text in CSV format.
20	%Query_XML_XmlP	The output is in XMLP format.

Returns

A string containing the formatted output.

Example

```
/* Use RowCount, not ActiveRowCount, to get the total number of rows. */

&End = &MyRowset.RowCount;

&FormString = &MyQuery.FormatResultString(&MyRowset, %Query_TXT, 1, &End);
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

RunToFile

RunToRowset

GetTreePromptCount

Syntax

GetTreePromptCount()

Description

Use the GetTreePromptCount method to get the number of tree prompts if available in the query.

Parameters

None.

Returns

A number that indicates the count of tree prompts used in the query. -1 in case of an error.

Example

In this example, the ExecQry step of the PSQUERY Application Engine program invokes the GetTreePromptCount() method using a value stored in the run control table prior to executing the query.

```
&aQry = %Session.GetQuery();
If &aQry.Open(PSQUERY_AET.QRYNAME, &bPublic, False) = 0 Then
   &nTreePromptCount = &aQry.GetTreePromptCount();
End-if;
```

Open

Syntax

Open(*QueryName*, *Public*, *Update*)

Description

The Open method opens the query object specified by the parameters. The Open method can be used only with a closed query, it cannot be used on an open query. You cannot read or set any properties of a query until after you open it.

Considerations for Opening Different Types of Queries

When you use the Open method, the system tries to open queries according to the type of query. The following is the order used for searching for the query to open:

1. Query (User)
2. View
3. Role

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

4. Process
5. Archive

All query names are unique. You can't have two queries with the same name, just of different types.

Parameters

QueryName	Specify the name of the query to be opened. You must specify an existing query. This parameter takes a string value.
Public	Specify if the query is public or private. This parameter takes a Boolean value: True if the query is public, False if it's a private query.
Update	This parameter is required, but is unused in this release. You must specify a either True or False.

Returns

An integer value: 0 means the query was opened successfully.

Related Links

GetQuery
Close
Save

Rename

Syntax

Rename(*NewQueryName*)

Description

The Rename method renames the existing query definition with *NewQueryName*. The Rename method can be used only with an open query, it cannot be used on a closed query. Before you use the Rename method, you must explicitly open the query object to be renamed (with either the Open or Create method.)

Note: The Rename method takes place immediately. You don't have to save the query for the rename to occur.

Parameters

NewQueryName	Specify the new name for the existing query. The maximum length of this parameter is 30 characters.

Returns

An integer value: 0 means the query was renamed successfully.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

Open
Close
Save

RunToFile

Syntax

```
RunToFile(&PromptRecord, Destination, OutputFormat, MaxRows)
```

Description

Use the RunToFile method to execute the Query and return the result to the file specified with *Destination*. The query should be an existing query in the database, or it should have been saved using the Save method.

Because a Query may have runtime prompts (that is, criteria defined using Prompt), this method requires those values to be passed in when you execute this method. *PromptRecord* is a PeopleCode record object containing the prompt values as fields in the record. You can use the PromptRecord property to obtain this object.

Destination must include the absolute path name of where the file is to be created.

If the specified subdirectory does not exist, this method does *not* automatically create them for you, and you receive an error.

If you specify HTML as the output format, the PeopleSoft Query style sheet PSQUERYSTYLEDEF is used for formatting the output.

Related Links

"Understanding Style Sheets and Style Classes" (PeopleTools 8.54: Application Designer Developer's Guide)

Parameters

&PromptRecord

Specify an instance of a PeopleCode record that contains the runtime prompts and values required for running the query.

Destination

Specify the absolute path name of where the files are to be created.

OutputFormat

Specify the format of the data being written to the file. You can use either a constant or a numeric value for this parameter. See below.

MaxRows

Specify the maximum number of rows to be fetched. This parameter takes a numeric value.

The values are:

- -1 returns all rows *regardless* of the setting on the Query security profile (MaxRowsFetched).

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- 0 returns the maximum number of rows allowed by the Query security profile.
- >0 is the limit on the number of rows.

The values for *OutputFormat* can be as follows:

Numeric Value	***Constant Value***	***Description***
2	%Query_PDF	The output is in PDF format.
5	%Query_HTML	The output is in HTML format.
8	%Query_XLS	The output for Excel in HTML format.
14	%Query_TXT	The output for txt in CSV format.
17	%Query_XML_WebRowset	The output is in web rowset XML format.
20	%Query_XML_XmlP	The output is in XMLP format.

Returns

Returns 0 if successful.

Example

To run a query using the query API RunToFile method:

1. Open the query.

```
&aRunQry = %Session.GetQuery();

&aRunQry.Open(&sQryName, False, False);
```

2. Obtain the PromptRecord for the query.

```
&aQryPromptRec = &aRunQry.PromptRecord;
```

   This instance of the PromptRecord can be passed to the PeopleCode Prompt function to prompt the user for the runtime values, as follows:

```
&nResult = Prompt(&strQryName | " Prompts", "", &aQryPromptRec);
```

3. Run the query.

   Now that you have the runtime values, the query can be run, as follows:

```
&aRowSet = &aRunQry.RunToFile(&aQryPromptRec, "c:\temp\QueryOutput.html", %Que⇒
ry_PDF, 0);
```

4. Access the data of the rowset.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

You can now manipulate the rowset using the data buffer access methods and properties:

```
&aRowSet(&i).GetRecord(1).GetField(&j).Value
```

The following is a complete sample code example:

```
Local Rowset &aRowSet;
   Local Row &aRow;
   Local Record &aQryPromptRec;
   Local Record &aRec;
   Local ApiObject &aRunQry;
   &strHTML = "";
   &aRunQry = %Session.GetQuery();
   If (&aRunQry.Open(&sQryName, False, False) <> 0) Then
      &strHTML = "Error in opening query";
   Else
      &aQryPromptRec = &aRunQry.PromptRecord;
      &strQryName = &aRunQry.Name;
   If &aQryPromptRec <> Null Then
      &nResult = Prompt(&strQryName | " Prompts", "", &aQryPromptRec);
   End-If;
   If (&aRunQry.RunToFile(&aQryPromptRec, "c:\temp\" | &aRunQry.Name, 3, 0) = 0) Th⇒
en
      &strHTML = "Resultset saved into file successfully.";
   Else
      &strHTML = "Failed to save Resultset into file.";
   End-If;
End-If;
```

Related Links

RunToRowset

PromptRecord

"Prompt" (PeopleTools 8.54: PeopleCode Language Reference)

"Understanding Data Buffer Access" (PeopleTools 8.54: PeopleCode Developer's Guide)

RunToRowset

Syntax

RunToRowset(*&PromptRecord*, *MaxRows*)

Description

Use the RunToRowset method to execute the Query and return the result to a rowset. The query should be an existing query in the database, or it should have been saved using the Save method.

Because a Query may have runtime prompts (that is, criteria defined using Prompt), this method requires those values to be passed in when you execute this method. *PromptRecord* is a PeopleCode record object containing the prompt values as fields in the record. The PromptRecord property can be used to obtain this object.

Parameters

&PromptRecord	Specify an instance of a PeopleCode record that contains the runtime prompts and values required for running the query.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

MaxRows

Specify the maximum number of rows to be fetched. This parameter takes a numeric value. The total number of rows fetched is the minimum value of this parameter's value, and the application server configuration parameter Max Fetch Size (which is specified in KB.)

The values are:

- -1 returns all rows *regardless* of the setting on the Query security profile (MaxRowsFetched).
- 0 returns the maximum number of rows allowed by the Query security profile.
- >0 is the limit on the number of rows.

Returns

If successful, the query result is returned as a populated PeopleCode rowset. If the query wasn't successful, the method returns NULL. If unsuccessful, check the PSMessages collection for errors.

Example

To run a query using the query API RunToRowset method:

1. Open the Query.

```
&aRunQry = %Session.GetQuery();

&aRunQry.Open(&sQryName, False, False);
```

2. Get the PromptRecord for the Query.

```
&aQryPromptRec = &aRunQry.PromptRecord;
```

   This instance of the PromptRecord can be passed to the PeopleCode Prompt function to prompt the user for the runtime values, as follows:

```
&nResult = Prompt(&strQryName | " Prompts", "", &aQryPromptRec);
```

3. Run the query.

   Now that you have the prompt values, you can run the query:

```
&aRowSet = &aRunQry.RunToRowset(&aQryPromptRec, 0);
```

4. Access the data of the rowset.

   You can now manipulate the rowset using the data buffer access methods and properties:

```
&aRowSet(&i).GetRecord(1).GetField(&j).Value
```

The following is a complete sample code example:

```
Local Rowset &aRowSet;
Local Row &aRow;
Local Record &aQryPromptRec;
Local Record &aRec;
Local ApiObject &aRunQry;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
   &strHTML = "";
   &aRunQry = %Session.GetQuery();
   If (&aRunQry.Open(&sQryName, False, False) <> 0) Then
      &strHTML = "Error in opening query";
   Else
      &aQryPromptRec = &aRunQry.PromptRecord;
      &strQryName = &aRunQry.Name;
   If &aQryPromptRec <> Null Then
      &nResult = Prompt(&strQryName | " Prompts", "", &aQryPromptRec);
      &aRowSet = &aRunQry.RunToRowset(&aQryPromptRec, 0);
         If &aRowSet <> Null Then
               &strHTML = &strHTML | "<table cellpadding='2' cellspacing='0' width=⇒
'90%'>";
               &aRec = &aRowSet(1).GetRecord(1);
               &QrySelOutputFldCol = &aRunQry.QuerySelect.QueryOutputFields;
               If &QrySelOutputFldCol <> Null Then
                  &strHTML = &strHTML | "<TR><TD>";
                  &strHTML = &strHTML | "<table border='1' cellpadding='2' cellspac⇒
ing='0' width='100%'>";
                  &strHTML = &strHTML | "<TR><TH> </TH>";
                  For &j = 1 To &QrySelOutputFldCol.count
                     &strHTML = &strHTML | "<TH><B>" | &QrySelOutputFldCol.Item(&j)⇒
.LongName | "</B></TH>";
                  End-For;
                  &strHTML = &strHTML | "</TR>";
                  &strHTML = &strHTML | "</TD></TR>";
               End-If;
               &strHTML = &strHTML | "<TR><TD>";
               If &aRowSet.RowCount > 0 Then
                  For &i = 1 To &aRowSet.RowCount
                     &aRow = &aRowSet(&i);
                     &strHTML = &strHTML | "<TR>" | "<TD>" | &i | "</TD>";
                     For &j = 1 To &aRow.GetRecord(1).FieldCount
                        &strHTML = &strHTML | "<TD>" | &aRow.GetRecord(1).GetField(⇒
&j).Value | "</TD>";
                     End-For;
                     &strHTML = &strHTML | "</TR>";
                  End-For;
               Else
                  &strHTML = &strHTML | "No records retrieved.";
               End-If;
               &strHTML = &strHTML | "</TD></TR>";
               &strHTML = &strHTML | "</TABLE>";
               &strHTML = &strHTML | "</TABLE>";
            Else
               &strHTML = "Failed to retrieve result set.";
            End-If;
      End-If;
   End-If;
```

Related Links

RunToFile

PromptRecord

"Prompt" (PeopleTools 8.54: PeopleCode Language Reference)

"Understanding Data Buffer Access" (PeopleTools 8.54: PeopleCode Developer’s Guide)

RunToString

Syntax

RunToString(*&PromptRecord*, *ChunkSize*, *OutputFormat*, *MaxRows*)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the RunToString method to execute the query and return the result as a formatted string.

When “chunking” is active, RunToString is intended to be called in a recursive fashion until the result set has been completely traversed. A Boolean property, MoreRowsAvailable, is included in the Query class to control recursive execution of this method.

See MoreRowsAvailable.

Parameters

&PromptRecord Specify an instance of a PeopleCode record that contains the runtime prompts and values required for running the query.

ChunkSize Specify the desired chunking size in characters as a number. 0 means no chunking.

OutputFormat Specify the format of the data being written to the file. You can use either a constant or a numeric value for this parameter. See below.

MaxRows Specify the maximum number of rows to be fetched. This parameter takes a numeric value. The values are:

- -1 returns all rows regardless of the setting on the query security profile (MaxRowsFetched).
- 0 returns the maximum number of rows allowed by the query security profile.
- >0 is the absolute limit on the number of rows.

The values for *Output_Format* can be as follows:

Numeric Value	*Constant Value*	*Description*
2	%Query_PDF	The output is in PDF format.
5	%Query_HTML	The output is in HTML format.
8	%Query_XLS	The output for Excel in HTML format.
14	%Query_TXT	The output for text in CSV format.
17	%Query_XML_WebRowset	The output is in web rowset XML format.
20	%Query_XML_XmlP	The output is in XMLP format.

Returns

A string containing the formatted output. If an error occurs, an empty string will be returned.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

If there are no errors, but no data is in the query result set, the string will have system-defined header and footer information, but no rows will be present.

Example

The following example runs a query without chunking.

```
&queryname = "XRFWIN";

rem &querytype = %Query_XLS;
rem &querytype = %Query_PDF;
rem &querytype = %Query_HTML;
rem &querytype = %Query_TXT;
&querytype = %Query_XML_XmlP;
rem &querytype = %Query_XML_WebRowset;


&aRunQry = %Session.GetQuery();
If (&aRunQry.Open(&queryname, False, False) <> 0) Then
   MessageBox(0, "", 0, 0, "Error opening query");
Else
   &aQryPromptRec = &aRunQry.PromptRecord;

   &chunksize = 0;

   &filename = "C:\QueryWork850\output\" | &querytype | "_runtostring.xml";

   &resultString = &aRunQry.RunToString(&aQryPromptRec, &chunksize, &querytype, 0);

   &myfile = GetFile(&filename, "w", %FilePath_Absolute);
   &myfile.writestring(&resultString);
   &myfile.close();

   MessageBox(0, "", 0, 0, "Success!");

End-If;
```

The following example runs a query with chunking.

```
&queryname = "XRFWIN";
rem &querytype = %Query_XLS;
rem &querytype = %Query_PDF;
rem &querytype = %Query_HTML;
rem &querytype = %Query_TXT;
&querytype = %Query_XML_XmlP;
rem &querytype = %Query_XML_WebRowset;


&aRunQry = %Session.GetQuery();
If (&aRunQry.Open(&queryname, False, False) <> 0) Then
   MessageBox(0, "", 0, 0, "Error opening query");
Else
   &aQryPromptRec = &aRunQry.PromptRecord;
   &counter = 0;

   &chunksize = 1000;

   Repeat
      &counter = &counter + 1;
      &filename = "C:\QueryWork850\output\" | &querytype | &counter | "_runtostring⇒
.xml";

      &resultString = &aRunQry.RunToString(&aQryPromptRec, &chunksize, &querytype, ⇒
0);

      If (Len(&resultString) > 0) Then

         &myfile = GetFile(&filename, "w", %FilePath_Absolute);
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
         &myfile.writestring(&resultString);
         &myfile.close();

      Else

         /* edge condition; if there are no more rows AND the */
         /* returned string is empty this is not an error.    */

         If (&aRunQry.MoreRowsAvailable) Then
            /* we have an error... Yikes! */
            MessageBox(0, "", 0, 0, "Something bad has happened!");
         Else
            /* no worries, just ignore it */
         End-If;

      End-If
   Until (Not &aRunQry.MoreRowsAvailable);

   MessageBox(0, "", 0, 0, "Success!");

End-If;
```

Related Links

MoreRowsAvailable

Save

Syntax

Save()

Description

The Save method writes any changes to the existing query to the database.

The Save method can be used only on an open query, not on a closed query. This means you must have opened the query with the Open method before you can save it.

The query object remains open after executing Save. You must execute the Close method on the object before it is closed and the memory freed.

Note: If you're calling the query API from an Application Engine program, the data won't actually be committed to the database until the Application Engine program performs a COMMIT.

Parameters

None.

Returns

An integer value: 0 means the query was saved successfully.

Related Links

Open

Close

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SetTrackingURL

Syntax

SetTrackingURL(*ExpressionText*, *ExpressionNumber*)

Description

Use the SetTrackingURL method to re-establish the drilling URL if the current execution context is different from the context in which the drilling URL was initially set.

For example, a drilling URL is set as a query expression by the program that executes the query. After query execution, a different program—an iScript program—allows the user to download the query results to an Excel spreadsheet. This iScript program needs to include the drilling URL in the spreadsheet data. In order for the iScript program to have access to the drilling URL query expression values, these values must be defined as global objects by the program that executes the query. Then, the iScript program can re-establish the drilling URL by calling the SetTrackingURL method.

Parameters

ExpressionText	Specify the drilling URL as a string by reference to an established query expression.
ExpressionNumber	Specify the drilling URL as a numeric value by reference to an established query expression.

Returns

None.

Example

```
If &rsURLList <> Null And
      &rsURLList.ActiveRowCount >= 1 And
      All(&rsURLList(1).QRY_URL_WRK.QRYCRIT1EXPRTEXT.Value) Then
   For &nCount = 1 To &rsURLList.ActiveRowCount;
      &rRecordExpr = &rsURLList(&nCount).QRY_URL_WRK;
      &QryObj.SetTrackingURL(&rRecordExpr.QRYCRIT1EXPRTEXT.Value, &rRecordExpr.QRYC⇒
RIT1EXPRNUM.Value);
   End-For;
End-If;
```

Related Links

AddTrackingURL

Setting a Drilling URL

"Drilling URL in PeopleSoft Query" (PeopleTools 8.54: Query)

Query Class Properties

In the following section, we discuss each Query class property.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Approved

Description

This property returns a string indicating whether a query is approved, unapproved, or modified. This is useful for query administration. The values are:

Value	*Description*
U	Query is unapproved. This is the default value. The query administrator can prevent execution of unapproved queries.
A	Query has been approved by the query administrator.
M	Query has been modified.

This property is read-write.

ApproveOprId

Description

Note: This property has been deprecated, and remains for backward compatibility only. Use the ApproveUserId property instead.

This property returns a string containing the user ID of the user who approved the query. This can be useful for query administration.

This property is read-write.

Related Links

ApproveUserId

ApproveUserId

Description

This property returns a string containing the user ID of the user who approved the query. This can be useful for query administration.

This property is read-write.

ApproveDtTm

Description

This property returns the date-time stamp when the query was most recently approved. This can be useful for query administration.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-only.

CreateOprId

Description

Note: This property has been deprecated, and remains for backward compatibility only. Use the CreateUserId property instead.

This property returns a string containing the User Id of the user who created the query. This can be useful for query administration.

This property is read-only.

Related Links

CreateUserId

CreateDtTm

Description

This property returns a string containing the date-time stamp indicating when the query was created. This property is set by the query runtime when a new query is saved. This can be useful for query administration.

This property is read-only.

CreateUserId

Description

This property returns a string containing the User Id of the user who created the query. This can be useful for query administration.

This property is read-only.

Description

Description

This property returns or sets the short description for the query.

The length of this property is 30 characters.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Disabled

Description

This property indicates if the query is active or not. This property returns a string value:

Value	*Description*
Y	This query is not active
Blank or any other value	This query is active

This property is read-write.

ExecAppName

Description

This property specifies the name of the application executing the query. This property isn't required. This means this property is used only if the query will be executed. This name is stored in the query execution log. This property returns a blank value when the query is opened.

When executing a query using the query API, this property should be set to the Application name that's executing it, so that the Query Monitor can track query execution. Doing this makes this property useful for query administration. If you try to read this property before setting it, you receive a NULL string.

This property should be set before using RunToRowset or RunToFile.

This property is read-write. However, this property is generally used only to set the name, rather than to read it.

ExecLogging

Description

This property indicates whether an execution log should be created when the query is executed. This can be useful for query administration. This property takes a Boolean value: True, create a log, False, don't create one.

The execution log, which is created by setting this property, can be viewed from the Query Monitor. The logging is done in a PeopleSoft Table. It stores, along with other relevant information, the Execution DateTime, Total Execution Time for the query, and Total Fetch Time for the query.

If you try to read this property before setting it, you receive a NULL string.

This property is read-write. However, this property is generally used only to set logging, rather than read.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Folder

Description

This property is used to group queries together. This parameter takes a string value, up to 18 characters.

This property is read-write.

LastSQLErrorCode

Description

This property returns the last SQL error code returned by the database as a number. The session object contains the error text and any other errors encountered while executing the query.

PeopleSoft recommends checking this value after using RunToRowset or RunToFile.

This property is read-only.

LastUpdDttm

Description

This property returns the most recent date-time when the query was updated as a string.

This property is read-only.

LastUpdOprId

Description

This property returns the User Id of the user who updated the query most recently as a string.

This property is read-only.

LongDescription

Description

This property returns or sets the long description for the query.

The length of this property is 256 characters.

This property is read-write.

Metadata

Description

This property returns a metadata collection.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-only.

Example

```
&MetadataList = &MyQuery.Metadata;
```

Related Links

Query Metadata Collection

MetaSQL

Description

This property returns the SQL that represents the query, unresolved for any platform.

For example, the MetaSQL property returns the following:

```
SELECT %DATEOUT(A.ASOF_DT)
 FROM PS_AEREQUESTTBL A
 WHERE A.ASOF_DT = %DATEIN('1900-01-01')
```

This property is read-only.

MoreRowsAvailable

Description

This property returns a Boolean value indicating whether “chunking” is turned on for the query.

This property is read-only.

Chunking Considerations

Every time a row is retrieved from the query result set, it is added to the internal output string managed by RunToString. At this point, the method can check to see if chunking is active. If so, and if the current size of the output string is larger than the ChunkSize parameter, then the query context is stored and the output string is returned. If not, then the next row is retrieved from the result set and the process continues.

When chunking is active, RunToString is intended to be called in a recursive fashion until the result set has been completely traversed. A Boolean property, MoreRowsAvailable, is included in the Query class to control recursive execution of these methods.

Related Links

RunToString

Name

Description

This property returns the name of the query as a string.

The length of this property is 30 characters.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-only.

OutputUnicode

Description

Use this property to set or return a Boolean value indicating whether the RunToFile method will create a Unicode-encoded CSV file as output. This property is applicable only if the output format is set to %Query_TXT. Because the default value is false, OutputUnicode must be set before calling RunToFile.

Note: Because Microsoft Excel does not support UTF-8 encoding, the CSV file is written in binary mode with UCS-2 encoded data. Moreover, Excel does not automatically recognize Unicode-encoded, comma-delimited files even if they have a .csv extension. Therefore, the user receiving the file will not be able to open it by double-clicking. Instead, he or she must open it with Excel's File, Open menu and choose the comma delimiter.

This property is read-write.

Example

```
&aQry.OutputUnicode = True;
&Result = &aQry.RunToFile(&rcdQryPrompts, &sOutFile, %Query_TXT, 0);
```

Related Links

RunToFile

PDFFont

Description

This property is used to set the PDF Font number required for generating PDF using RunToFile. This property takes either a numeric or constant value. The values are:

Numeric Value	*Constant Value*	*Description*
0	%PDFFont_None	Default value
2	%PDFFont_TraditionalChinese	The output must be written using the Traditional Chinese Font.
3	%PDFFont_SimplifiedChinese	The output must be written using the Simplified Chinese Font.
1	%PDFFont_Japanese	The output must be written using the Japanese Font
4	%PDFFont_Korean	The output must be written using the Korean Font

If you try to read this property before setting it, you receive a NULL string.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-write.

Related Links

RunToFile, RunToRowset

Prompts

Description

This property returns all the prompts defined for the Query in a QueryPrompt Collection. If you just want the prompts used in the criteria, use the RunTimePrompts property.

This property is read-only.

Related Links

RunTimePrompts, QueryPrompt Collection

PromptRecord

Description

This property returns the runtime prompts of a query as an instance of a PeopleCode record object. This can be used with the Prompt built-in function to prompt for bind values. This record instance can also be used as the first input parameter for the RunToRowset and RunToFile methods.

This property is read-only.

Related Links

RunToFile, RunToRowset

PublicPrivate

Description

This property specifies whether the query is public or private.

You can use either a constant or numeric value for this property. The values are:

Numeric Value	*Constant Value*	*Description*
0	%Query_Private	The query is a private query.
1	%Query_Public	The query is a public query.

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

```
If &QryObj.PublicPrivate = %Query_Public Then
   /* code when working with Public Query */
Else
   /* code when working with Private Query */
End-if;
```

QuerySelect

Description

This property returns the Main Select (that is, the first select) of the query definition as a QuerySelect object. For a new query which does not have any selects, it returns NULL.

The Query Records, Query Criteria, QueryOutput fields, and QuerySelected Fields can be obtained using the QuerySelect object only. Hence, after opening a query, this property serves as the starting point for getting the different components of the Select statement.

This property is read-only.

Related Links

QuerySelect Class

QueryStatistics

Description

This property returns statistical information pertaining to the query's execution as a QueryStatistics object.

This property is read-only.

Related Links

QueryStatistics Class

RunTimePrompts

Description

This property returns the prompts used in the Query Definition's criteria in a QueryPrompt Collection. To return all the prompts defined for the query, use the Prompts property.

This is property is read-only.

Related Links

Prompts, QueryPrompt Collection

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SQL

Description

This property returns the SQL statement as generated from the query definition as a character string.

Note: The value of the SQL property is never stored as part of the query definition. Instead, it's generated by the system whenever it's needed for one of the RunTo methods or for the SQL property.

In the PeopleSoft Query, this is located under the SQL tab.

This property is read-only.

Considerations Using the SQL Property

This property returns a basic SQL statement. This statement does not include logic for doing related language record transactions or translate descriptions. PeopleSoft does not recommend using this SQL for selecting data. Instead, PeopleSoft recommends using the RunToRowset method for selecting data.

Type

Description

This property specifies the type of query. This parameter takes either a constant or number value. Values are:

Numeric Value	*Constant Value*	*Description*
1	%Query_Query	Query of type Query
3	%Query_View	Query of type View
4	%Query_Role	Role
5	%Query_DBAgent	Process
7	%Query_Archive	Archive

This property is read-write.

QuerySelect Collection

A QuerySelect collection is returned from the QuerySelects property of each QuerySelect instance. It contains the unions and subqueries, which are children of the current select statement. PeopleSoft Query allows unions only for the main select. The QuerySelect instance for any subqueries cannot have any unions.

See QuerySelects.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

QuerySelect Collection Methods

In this section, we discuss the QuerySelect collection methods. The methods are discussed in alphabetical order.

AddUnion

Syntax

AddUnion()

Description

The AddUnion method adds a new QuerySelect object of type Union in the current QuerySelect collection. You can use AddUnion only with the first QuerySelect Collection because PeopleSoft Query doesn't' support Unions for subqueries. All unions are considered children of the Main Select.

Parameters

None.

Returns

A reference to a QuerySelect object if successful. If the current QuerySelect Collection does not belong to the first Select statement, it returns NULL. If it fails, it returns NULL.

Example

```
&QryMainSel = &Query.QuerySelect;
&QryMainSelCol = &QryMainSel.QuerySelects;
&QryUnion = &QryMainSelCol.AddUnion();
```

DeleteQuerySelect

Syntax

DeleteQuerySelect(*SelNumber*)

Description

The DeleteQuerySelect method deletes the QuerySelect instance represented *SelNumber*.

Parameters

SelNumber	Specify the numeric value containing the Select Number of the QuerySelect that you want to delete.

Returns

Returns 0 if successful.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

```
&QryMainSel = &Query.QuerySelect;
&QryMainSelCol = &QryMainSel.QuerySelects;
&QryMainSelCol.DeleteQuerySelect(3);
```

First

Syntax

First()

Description

The First method returns the first child QuerySelect object in the current QuerySelect's collection.

Parameters

None.

Returns

A reference to a QuerySelect object if successful, NULL otherwise.

Example

```
&MyChildQrySel = &MySelCollection.First();
```

Item

Syntax

Item(*number*)

Description

The Item method returns the QuerySelect object that exists at the *number* position in the current QuerySelect collection.

Parameters

Number	Specify the position number in the collection of the QuerySelect object that you want returned.

Returns

A reference to a QuerySelect object if successful, NULL otherwise.

Example

```
For &I = 1 to &QrySelCol.Count;
   &MyChildQrySel = &QrySelCol.Item(&I);
   /* do processing */
End-For;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ItemBySelNum

Syntax

ItemBySelNum(*SelNumber*)

Description

The ItemBySelNum method returns the QuerySelect object specified by *the Select Number*. Each Select Statement in a Query Definition is identified by a unique select number.

Parameters

SelNumber	Specify the numeric value of the Select Number.

Returns

A reference to a QuerySelect object if successful, NULL otherwise.

Example

```
&MyChildQuerySelect = &MySelCol.ItemBySelNum(3);
```

Next

Syntax

Next()

Description

The Next method returns the next QuerySelect object in the current QuerySelect collection. You can use this method only after you have used the First method: otherwise the system returns a NULL.

Parameters

None.

Returns

A reference to a QuerySelect object if successful, NULL otherwise.

Example

```
&MyChildQuerySelect = &MySelCol.Next();
```

QuerySelect Collection Property

In this section, we discuss the Count property.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Count

Description

This property returns the total number of QuerySelect objects in the current QuerySelect Collection, as a number.

This property is read-only.

Example

```
&COUNTCHILDSELS = &MYSELCOL.Count;
```

QuerySelect Class

The QuerySelect class represents the select statement of the SQL used in the query definition. This can be any of the following:

- The main select statement.
- The select statement in each union.
- The select statement in each subquery.

Consider the following SQL statement:

```
select ACCOUNT_NUM from GL_ACCOUNT_TBL_00

where PRODUCT_ID in (select DISTINCT PRODUCT_ID FROM ORDER_TBL)

union

select ACCOUNT_NUM from GL_ACCOUNT_TBL_01
```

In this example, there are three select statements. The first select statement is the main statement. The second select statement is a subquery, which is then used in the criterion for the first select statement. The union contains the third select statement. There are records and fields associated with each select statement. In the query API, the first select is accessible using Query.QuerySelect, which can be obtained as shown:

```
&MainSelect = &Qry.QuerySelect;
```

The union can be obtained from the main select, as shown:

```
/* There can be more than one union, hence there is collection of selects */
/* in the main select */

&Union1 = &MainSelect.QuerySelects.Item(1);
```

The subquery is obtained from the main select as shown:

```
/* belongs to first criteria of the select */

&SubQry1 = &MainSelect.Criteria.Item(1).Expr2SubQuery;
```

Therefore, there is one QuerySelect instance for the main select of the query, one instance per union defined in the query, and one instance per subquery.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

In PeopleSoft Query, the first select (that is, the main select) is the parent of all the unions and subqueries. The main select is obtained with the QuerySelect property. The unions and subqueries are obtained from the QuerySelects property of each QuerySelect instance.

A QuerySelect object is returned from the following:

- The QuerySelect collection methods AddUnion, First, Item, ItemBySelNum, or Next
- The QuerySelect Query property

See QuerySelect Collection, QuerySelects.

QuerySelect Methods

In this section, we discuss each QuerySelect method. The methods are arranged in alphabetical order.

AddAllFields

Syntax

AddAllFields(*QueryRecord*)

Description

The AddAllFields method adds all the fields in the specified query record to the query definition, that is, makes them all QueryOutputFields. The query record must already be a part of the query definition.

Parameters

QueryRecord	Specify the instance of an existing record in the query from which you want to add all the fields from to the query definition. This instance can be obtained from the QueryRecords collection of the QuerySelect.

Returns

An integer: 0 if successfully added.

Related Links

AddQueryOutputField
AddQueryRecord
AddQuerySelectedField

AddCriteria

Syntax

AddCriteria(*Name*)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

The AddCriteria method adds new criterion to the query definition. This method returns a reference to a new QueryCriteria object that you can then use to specify details about the criteria.

Note: If you do not specify a unique name for *Name* when adding a criteria, a criteria object referencing the new criteria is returned, not the existing criteria object.

Parameters

Name	Specify a string containing the name of the criteria that you want to add. The maximum length of this parameter is 30 characters.

Returns

A reference to a QueryCriteria object.

Related Links

DeleteCriteria
Criteria
QueryCriteria Class

AddExpression

Syntax

`AddExpression``(`*`Name`*`)`

Description

The AddExpression method adds an expression to the query definition. It returns a reference to a new QueryExpression object you can use to specify details about the expression.

Parameters

Name	Specify a string containing the name of the expression that you want to add. This maximum length of this parameter is 30 characters.

Returns

A reference to a QueryExpression object.

Related Links

FindExpression
DeleteExpression
Expressions
QueryExpression Class

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

AddHavingCriteria

Syntax

AddHavingCriteria(*Name*)

Description

The AddHavingCriteria method adds new criterion to the query definition, which is intended for use in the HAVING clause of the SELECT statement. This method returns a reference to a new QueryCriteria object that you can then use to specify details about the having criteria.

Note: If you do not specify a unique name for *Name* when adding a criterion, a criteria object referencing the new criteria is returned, not the existing criteria object.

Parameters

Name	Specify a string containing the name of the criteria that you want to add. The maximum length of this parameter is 30 characters.

Returns

A reference to a QueryCriteria object.

Related Links

DeleteHavingCriteria
HavingCriteria
QueryCriteria Class

AddQueryOutputField

Syntax

AddQueryOutputField(*QueryRecord*, *index*)

Description

The AddQueryOutputField method adds a query output field to the query definition. This method returns a reference to a new QueryOutputField object that you can then use to specify attributes for the query definition.

Parameters

QueryRecord	Specify the QueryRecord instance that contains the field that you want to include in the query definition. This instance can be obtained from the QueryRecords collection of the QuerySelect.
Index	Specify the numeric position in the QueryRecord of the field that you want to add.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

A reference to a QueryOutputField object.

Related Links

AddAllFields
QueryField Class

AddQueryRecord

Syntax

AddQueryRecord(*QueryRecordName*)

Description

The AddQueryRecord method adds a query record to the query definition. You must specify a valid record name in the string parameter *QueryRecordName*. This method returns a reference to the record as a QueryRecord.

Parameters

QueryRecordName	Specify a string containing the name of a record to be added to the query definition. You must specify a valid record name. The maximum allowed length for this parameter is 15 characters.

Returns

A reference to the record as a QueryRecord object.

Related Links

QueryRecord Class

AddQuerySelectedField

Syntax

AddQuerySelectedField(*QueryRecordName, RecordAlias, FieldName, Heading*)

Description

The AddQuerySelectedField method adds a query field to the query definition, as a QuerySelectedField. This method returns a reference to a new QuerySelectedField object that you can then use to specify attributes for the query definition. At the time it's added, it isn't an output field. This can be changed by setting the column number of the field to a value greater than zero.

Parameters

QueryRecordName	Specify the name of the query record to which the field that you want to add belongs.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

RecordAlias	Specify the alias of the record (such as A, B, C, and so on.) The length of this parameter is 1.
FieldName	Specify the name of the field that's being added. The maximum allowed length for a field name is 18 characters.
Heading	Specify the heading of the field that's being added. The maximum allowed length for a heading is 30 characters.

Returns

A reference to a QuerySelectedField object.

Related Links

AddAllFields
DeleteField
QueryField Class

DeleteCriteria

Syntax

DeleteCriteria(*index*)

Description

The DeleteCriteria method deletes the criteria specified by *index* from the query definition.

Parameters

Index	Specify the numeric position in the query definition of the criteria that you want to delete.

Returns

An integer: 0 if successfully deleted.

Related Links

AddCriteria
Criteria

DeleteExpression

Syntax

DeleteExpression(*index*)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

The DeleteExpression method deletes the specified expression from the query definition.

Parameters

Index	Specify the numeric position of the expression in the query definition that you want to delete.

Returns

An integer: 0 if successfully deleted.

Related Links

AddExpression
Expressions
QueryExpression Class

DeleteField

Syntax

DeleteField(*index*)

Description

The DeleteField method deletes the selected field from the query definition. This does *not* delete the field from the QueryRecord, just from the query definition, so it's no longer selected.

Parameters

Index	Specify the position number of the field that you want deleted from the query definition.

Returns

An integer: 0 if successfully deleted.

Related Links

AddAllFields
QueryField Class

DeleteHavingCriteria

Syntax

DeleteHavingCriteria(*index*)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

The DeleteHavingCriteria method deletes the having criteria specified by *index* from the query definition.

Parameters

Index	Specify the numeric position in the query definition of the having criteria that you want to delete.

Returns

An integer value: 0 means the having criteria was deleted successfully.

Related Links

AddHavingCriteria
HavingCriteria

DeleteRecord

Syntax

DeleteRecord(*index*)

Description

The DeleteRecord method deletes the selected record from the query definition. This does *not* delete the record from the database or the QueryDBRecord collection, just from the query definition, so it's no longer selected.

Parameters

Index	Specify the position number of the record you want deleted from the query definition.

Returns

An integer: 0 if successfully deleted.

Related Links

AddQueryRecord
QueryField Class

QuerySelect Properties

In this section, we discuss the QuerySelect properties. The properties are discussed in alphabetical order.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Criteria

Description

This property returns a reference to a QueryCriteria Collection for the simple criteria of the SELECT (that is, the criteria that are used in the where clause of the select statement.)

This property is read-only.

Related Links

QueryCriteria Collection

Distinct

Description

This property specifies if the Select is distinct or not.

This property takes a Boolean value: True if the query is distinct, False if the query isn't distinct.

This property is read-write.

Expressions

Description

This property returns a reference to a QueryExpression Collection.

This property is read-only.

Related Links

QueryExpression Collection

HavingCriteria

Description

This property returns a reference to a QueryCriteria collection populated with Having criteria.

This property is read-only.

Related Links

QueryCriteria Collection

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ParentSelectNum

Description

This property returns the select number of the parent select of the current select object. Every QuerySelect is assigned a unique number indicating its place in the hierarchy of select statements. For the Main Select, this number is zero. For unions, this number is 1 (unions aren't allowed in subqueries.)

This property is read-only.

QueryOutputFields

Description

This property returns a reference to a QueryField Collection made up of QueryOutputFields.

The collection of QueryOutputFields does *not* necessarily include all columns returned in query resultset. This collection only includes columns that have been added to query output collection using the query classes or by an end-user designing a query.

PeopleSoft Query can also add additional columns for related language processing and also for translate labels on fields, and so you cannot use the Query Output Collections as a way to discover all of the columns that are returned in the resultset or by executing the SQL generated from a query.

This is property is read-only.

Related Links

QueryField Collection

QueryRecords

Description

This property returns a reference to a QueryRecord Collection for the query.

This is property is read-only.

Related Links

QueryRecord Collection

QuerySelectedFields

Description

This property returns a reference to a QueryField Collection made up of QuerySelectedFields.

This is property is read-only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

QueryField Collection

QuerySelects

Description

This property returns all the QuerySelect objects that are children of the current select statement as a QuerySelect collection. If the query contains unions, this property contains unions and subqueries (if any criteria contain subqueries). For all other selects, this property contains only the subqueries (because PeopleSoft Query doesn't allow unions for sub-queries).

This is property is read-only.

Related Links

QuerySelect Collection

SelectNum

Description

This property returns the select number of the current select. Every QuerySelect is assigned a unique number indicating its place in the hierarchy of select statements. For the Main Select, this number would be 1.

This property is read-only.

SelectType

Description

This property specifies what type of select statement. You can check for either a numeric or a constant value. The values are:

Numeric Value	*Constant Value*	*Description*
1	%Query_SelectMain	This is the Main Select of the query definition.
2	%Query_SubQuery	This is a subquery in the query definition.
3	%Query_Union	This is a Union in the query definition.

This property is read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

QueryRecord Collection

A QueryRecord collection is returned from the QueryRecords QuerySelect class method.

See QueryRecords.

QueryRecord Collection Methods

In this section, we discuss each QueryRecord collection method. The methods are discussed in alphabetical order.

First

Syntax

```
First()
```

Description

The First method returns the first QueryRecord object in the QueryRecord collection.

Parameters

None.

Returns

A reference to a QueryRecord object if successful, NULL otherwise.

Example

```
&MyQueryRecord = &MyCollection.First();
```

Item

Syntax

```
Item(number)
```

Description

The Item method returns the QueryRecord object that exists at the *number* position in the QueryRecord collection.

Parameters

Number	Specify the position number in the collection of the QueryRecord object that you want returned.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

A reference to a QueryRecord object if successful, NULL otherwise.

Example

```
For &I = 1 to &QueryRecordColl.Count;
   &MyQueryRecord = &QueryRecordColl.Item(&I);
   /* do processing */
End-For;
```

ItemByAlias

Syntax

ItemByAlias(*Alias*)

Description

The ItemByAlias method returns the QueryRecord object specified by *Alias*.

Parameters

Alias	Specify the record alias (for example, A, B, C, and so on), used in the SQL statement as a TableName alias.

Returns

A reference to a QueryRecord object if successful, NULL otherwise.

Example

```
&MyQueryRecord = &MyCollection.ItemByAlias("A");
```

Next

Syntax

Next()

Description

The Next method returns the next QueryRecord object in the QueryRecord collection. You can use this method only after you have used the First method: otherwise the system doesn't know where to start.

Parameters

None.

Returns

A reference to a QueryRecord object if successful, NULL otherwise.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

```
&MyQueryRecord = &MyCollection.Next();
```

QueryRecord Collection Property

In this section, we discuss the Count property.

Count

Description

This property returns the number of QueryRecord objects in the QueryRecord Collection, as a number.

This property is read-only.

Example

```
&COUNT = &MY_COLLECTION.Count;
```

QueryRecord Class

A QueryRecord object is returned from the following:

- The QueryRecord Collection methods First, Item, ItemByName, or Next.
- The AddQueryRecord QuerySelect class method.
- The QueryRecord QueryField class method.

See QueryRecord Collection, AddQueryRecord, QueryRecord.

QueryRecord Class Method

In this section, we discuss the GetField method.

GetField

Syntax

GetField(*Index*)

Description

The GetField method returns the QueryField object specified by *index* from the QueryRecord collection.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

Index	Specify the number of the field to be accessed.

Returns

A reference to a QueryField object if successful, NULL otherwise.

Example

```
&QryFieldColl = &QryRec.QueryFields;

For &I = 1 to &QryFieldColl.Count
   &QryField = &QryRec.GetField(&I);
   /* do processing */
End-For;
```

QueryRecord Class Properties

In this section, we discuss each QueryRecord class property. The properties are discussed in alphabetical order.

Description

Description

This property returns the short description of the record as a string.

The length of this property is 30 characters.

This property is read-only.

JoinAlias

Description

This property returns or sets the join record's alias, that is, A, B, C, and so on.

This is applicable in any type of join. The value is a string. The length of this property is 1 character.

This property is read-write.

JoinFieldName

Description

This property returns or sets the join record's field used in the join criteria. This is applicable in lookup-table joins. The value is a string.

The length of this property is 18 characters.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-write.

JoinType

Description

This property returns or sets the join type. This is applicable in any type of join. You can use either a constant or numeric value.

The values for the join type are:

Numeric Value	*Constant Value*	*Description*
1	%Query_JoinNone	Query record isn't joined with any other record.
2	%Query_JoinHierarchy	Query record has a hierarchy join with another record.
3	%Query_JoinRelated	Query record has a lookup table join with another record.
4	%Query_JoinTree	Query record has a tree join with another record.
5	%Query_JoinLeftOuter	Query record has a left outer join with another record.

This property is read-write.

Name

Description

This property returns the name of the record as a string.

The length of this property is 15 characters.

This property is read-only.

QueryFields

Description

This property returns a reference to a QueryField Collection that contains instances of all the fields belonging to the record definition.

This property is read-only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

QueryField Collection

RecordAlias

Description

This property returns the alias used for the record in the query (that is, A, B, C, and so on.)

The length of this property is 1 character.

This property is read-write.

QueryField Collection

A QueryField collection is returned from the following:

- The QueryOutputFields of QuerySelect class method.
- The QuerySelectedFields of QuerySelect class method.
- The QueryFields QueryRecord class method.

The collection of QueryOutputFields does *not* necessarily include all columns returned in query resultset. This collection only includes columns that have been added to query output collection using the query classes or by an end-user designing a query.

PeopleSoft Query can also add additional columns for related language processing and also for translate labels on fields, and so you cannot use the Query Output Collections as a way to discover all of the columns that are returned in the resultset or by executing the SQL generated from a query.

See QueryOutputFields, QuerySelectedFields, QueryFields.

QueryField Collection Methods

In this section, we discuss each QueryField method. The methods are discussed in alphabetical order.

First

Syntax

```
First()
```

Description

The First method returns the first QueryField object in the QueryField collection.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

None.

Returns

A reference to a QueryField object if successful, NULL otherwise.

Example

```
&MyQueryField = &MyCollection.First();
```

Item

Syntax

Item(*number*)

Description

The Item method returns the QueryField object that exists at the *number* position in the QueryField collection.

Parameters

Number	Specify the position number in the collection of the QueryField object that you want returned.

Returns

A reference to a QueryField object if successful, NULL otherwise.

Example

```
For &I = 1 to &QueryFieldColl.Count;
   &MyQueryField = &QueryFieldColl.Item(&I);
   /* do processing */
End-For;
```

ItemByNameAndAlias

Syntax

ItemByNameAndAlias(*Name, RecordAlias*)

Description

The ItemByNameAndAlias method returns the QueryField object with the given *Name* and *Record Alias*.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

Name	Specify the name of an existing QueryField within the QueryField collection. If you specify an invalid name, the object is NULL.
RecordAlias	Alias of the record to which the field belongs

Returns

A reference to a QueryField object if successful, NULL otherwise.

Example

```
&MyQueryField = &MyCollection.ItemByNameAndAlias("PHONELIST", "A");
```

ItemByExpNum

Syntax

ItemByExpNum(*ExpNum*)

Description

The ItemByExpNum method returns the QueryField object with the given Expression Number, *ExpNum*.

Parameters

ExpNum	Expression Number for the given expression field. Non-expression fields have 0 value for the Expression Number.

Returns

A reference to a QueryField object if successful, NULL otherwise.

Example

```
&QryFld = &QryFldCol.ItemByExpNum(1);
```

Next

Syntax

Next()

Description

The Next method returns the next QueryField object in the QueryField collection. You can use this method only after you have used the First method: otherwise the system doesn't know where to start.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

None.

Returns

A reference to a QueryField object if successful, NULL otherwise.

Example

```
&MyQueryField = &MyCollection.Next();
```

QueryField Collection Property

In this section, we discuss the Count property.

Count

Description

This property returns the number of QueryField objects in the QueryField Collection, as a number.

This property is read-only.

Example

```
&COUNT = &MY_COLLECTION.Count;
```

QueryField Class

A QueryField object is returned by the following:

- The AddQuerySelectedField of QuerySelect class method.
- The AddQueryOutputField of QuerySelect class method.
- The QueryField collection methods First, Item, ItemByName or Next.

See AddQuerySelectedField, AddQueryOutputField.

See QueryField Collection.

QueryField Class Methods

In this section, we discuss each QueryField method. The methods are discussed in alphabetical order.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

AddTranslateExpression

Syntax

AddTranslateExpression(*ExpressionName*)

Description

Use the AddTranslateExpression method to add Translate Effective Date Logic expressions for translatable fields.

Parameters

ExpressionName Specify the name of the expression name that you want to add.

Returns

A reference to a QueryExpression object.

Related Links

Expressions
DeleteExpression
AddExpression
AddTranslateField
QueryExpression Class

AddTranslateField

Syntax

AddTranslateField(*FieldName*)

Description

Use the AddTranslateField method to add a Translate Effective Date Logic field for a translatable field.

Parameters

FieldName Specify the name of the translate field that you want to add. The maximum allowed length of this parameter is 18 characters.

Returns

A reference to a QueryField object.

Related Links

Expressions
DeleteExpression
AddExpression

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

AddTranslateExpression
QueryExpression Class

GetImageFormat

Syntax

```
GetImageFormat()
```

Description

Use the GetImageFormat method to differentiate between images and files, both stored as binary large objects (BLOBs) in the database.

Note: Because images and files share the field type value 8, this method is required to differentiate between the two types.

Parameters

None.

Returns

A number. A value 16 indicates that the field is of type file (or attachment).

Related Links

Type

QueryField Class Properties

In this section, we discuss the QueryField class properties. The properties are discussed in alphabetical order.

Aggregate

Description

This property returns or sets the aggregate type for the query field.

This property takes either a constant or numeric value. The values are:

Numeric Value	*Constant Value*	*Description*
1	%Query_TtlNone	Query field has no total
2	%Query_TtlSum	Query field is for Sum
3	%Query_TtlCount	Query field is for Count

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Numeric Value	*Constant Value*	*Description*
4	%Query_TtlMin	Query field is for Minimum
5	%Query_TtlMax	Query field is for Maximum
6	%Query_TtlAvg	Query field is for Average

This property is read-write.

ColumnNumber

Description

This property returns or sets the column number for the query field as a number. If the column number is greater than zero, the field is an output field.

This property is read-write.

Description

Description

This property returns the long description of the field as a string. This same value is returned by the Description property of the QueryDBRecordField class.

The length of this property is 30 characters.

This property is read-only.

Decimal

Description

This property returns the decimal positions QueryField as a number. This same value is returned by the Decimal property of the QueryDBRecordField class.

This property is read-only.

ExpNum

Description

This property returns or sets the Expression Number for the field. This value is 0 for non-expression fields. If the field is created for an expression, this value is the same as the expression number of the corresponding expression. This property takes a number value.

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Flag

Description

This property returns the Use Edit flag for the Query Field. It has the same values as returned by the Flag property of the QueryDBRecordField. This property takes a number value.

This property is read-only.

Format

Description

This property returns the field format for the query field. This property returns a string value. This property is useful for displaying the data type in a string format.

Values are:

Data Type	***Value Returned***
Character	“CHAR “
Long character	"LONG CHAR "
Number	"NUMBER "
Signed number	"SIGNED "
Date	"DATE "
Time	"TIME "
DateTime	"DATE/TIME "
Image	"IMAGE "

This property is read-only.

HeadingText

Description

This property returns or sets the heading text for the query field as a string.

The length of this property is 30 characters.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

HeadingType

Description

This property returns or sets the heading type for the query field. This property takes either a numeric or constant value. The values are:

Numeric Value	*Constant Value*	*Description*
1	%Query_HdgNone	Query field has no heading.
2	%Query_HdgText	Query field has a text heading.
3	%Query_HdgRftShort	Query field uses the short RFT heading.
4	%Query_HdgRftLong	Query fields uses the long RFT heading.

This property is read-write.

HeadingUniqueFieldName

Description

This property returns or sets the unique field name for the heading. The default value for this property is the record alias combined with the field name.

The length of this property is 30 characters.

This property is read-write.

Length

Description

This property returns the length of the Query Field. The same value is returned by the Length property of the QueryDBRecordField. This property takes a numeric value.

This property is read-only.

LongName

Description

This property returns the long name of the Query Field. The same value is returned by the Long Name property of the QueryDBRecordField. This property takes a string value.

The length of this property is 30 characters.

This property is read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Name

Description

This property returns the name of the query field as a string.

The length of this property is 18 characters.

This property is read-only.

OrderByDirection

Description

This property returns or sets the order by direction. This property takes a numeric value. The constants are the ASCII codes for space (" ") and "D".

Values are:

Numeric Value	*Constant Value*	*Description*
32	Code (" ")	Ascending
68	Code("D")	Descending

This property is read-write.

Example

The following sets the order by direction to be ascending.

```
&QueryField.OrderByDirection = Code(" ");
```

The following sets the order by direction to be descending.

```
&QueryField.OrderByDirection = Code("D");
```

OrderByNumber

Description

Use this property to specify whether a field is used as part of an 'Order By' statement in the SQL. The number value of this property indicates which is the first field in the order by statement, which is the second, and so on.

This property is read-write.

Example

To order a query by one field, you must set the OrderByNumber property for the other QueryFields as well, specifying the primary field as 1, the next field as 2, and so on.

```
&QryFld = &MainQrySel.AddQuerySelectedField("PSRECDEFN", "A", "RECNAME", "Record Na⇒
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
me");
&QryFld.ColumnNumber = 1;
&QryFld.OrderByNumber = 1;

&QryFld = &MainQrySel.AddQuerySelectedField("PSRECDEFN", "A", "RECDESCR", "Record D⇒
escr");
&QryFld.ColumnNumber = 2;
&QryFld.OrderByNumber = 2;

&QryFld = &MainQrySel.AddQuerySelectedField("PSRECDEFN", "A", "RELLANGRECNAME", "Re⇒
cord Lang Rec");
&QryFld.ColumnNumber = 3;
&QryFld.OrderByNumber = 3;
```

QueryRecord

Description

This property returns a reference to the QueryRecord containing this QueryField. If the field has no QueryRecord (that is, that this field is an expression field), this property returns NULL.

This property is read-only.

Example

```
&QryRcd = &QryFld.QueryRecord;
```

RecordAlias

Description

This property returns the record alias for the Query Field as a string. This value is usually a value like "A", "B", and so on. The same value is returned by the RecordAlias property for QueryRecord.

The length of this property is 1 character.

This property is read-only.

ShortName

Description

This property returns the short name of the Query Field. The same value is returned by the ShortName property for QueryDBRecordField. This property takes a string value.

The length of this property is 15 characters.

This property is read-only.

TranslateEffDtLogic

Description

This property returns or sets the effective date logic for the QueryField.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The values are:

Numeric Value	*Constant Value*	*Description*
1	%Query_ExprCurDt	Current Date
2	%Query_ExprField	Field
3	%Query_Expression	Expression

This property is read-write.

TranslateExpression

Description

This property returns a reference to an expression object based on a translate field if the Translate Effective Date option refers to an Expression

This property is read-only.

Related Links

QueryExpression Class

TranslateField

Description

This property returns a reference to a QueryField object for a translate field if the Translate Effective Date Option refers to a field.

This property is read-only.

Related Links

QueryField Class

TranslateOption

Description

This property returns or sets the translate value for the QueryField. This property takes a numeric or constant value. The values are:

Numeric Value	*Constant Value*	*Description*
1	%Query_XlatNone	None
2	%Query_XlatShort	Short

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Numeric Value	Constant Value	Description
3	%Query_XlatLong	Long

This property is read-write.

Type

Description

This property returns the type of the field. You can use either a numeric or constant value. The values are:

Numeric Value	Constant Value	Description
0	%FieldType_Char	Character
1	%FieldType_LongChar	Long Character
2	%FieldType_Number	Number
3	%FieldType_SignedNumber	Signed number
4	%FieldType_Date	Date
5	%FieldType_Time	Time
6	%FieldType_DateTime	DateTime
8	%FieldType_Image	Image
8	%FieldType_File	File
9	%FieldType_ImageRef	ImageReference

Note: The Image and File types can be differentiated using the GetImageFormat method of the QueryField class.

This property is read-only.

Related Links

GetImageFormat

QueryCriteria Collection

A QueryCriteria collection is returned from the Criteria QuerySelect class property.

See Criteria.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

QueryCriteria Collection Methods

In this section, we discuss the QueryCriteria collection methods. The methods are discussed in alphabetical order.

First

Syntax

First()

Description

The First method returns the first QueryCriteria object in the QueryCriteria collection.

Parameters

None.

Returns

A reference to a QueryCriteria object if successful, NULL otherwise.

Example

```
&MyQueryCriteria = &MyCollection.First();
```

Item

Syntax

Item(*number*)

Description

The Item method returns the QueryCriteria object that exists at the *number* position in the QueryCriteria collection.

Parameters

Number	Specify the position number in the collection of the QueryCriteria object that you want returned.

Returns

A reference to a QueryCriteria object if successful, NULL otherwise.

Example

```
For &I = 1 to &MyCollection.Count;
   &MyQueryCriteria = &MyCollection.Item(&I);
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
   /* do processing */
End-For;
```

ItemByName

Syntax

ItemByName(*CriteriaName*)

Description

The ItemByName method returns the QueryCriteria object that exists with the passed CriteriaName in the QueryCriteria collection.

Parameters

CriteriaName	Specify the name of the Criteria to be searched. This name is the same as the one used while creating the criteria using QuerySelect.AddCriteria(CriteriaName).

Returns

A reference to a QueryCriteria object if successful, NULL otherwise.

Example

```
&MyQueryCriteria = &MyCollection.ItemByName("PHONELIST");
```

Next

Syntax

Next()

Description

The Next method returns the next QueryCriteria object in the QueryCriteria collection. You can use this method only after you have used the First method: otherwise the system doesn’t know where to start.

Parameters

None.

Returns

A reference to a QueryCriteria object if successful, NULL otherwise.

Example

```
&MyQueryCriteria = &MyCollection.Next();
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

QueryCriteria Collection Property

In this section, we discuss the Count property.

Count

Description

This property returns the number of QueryCriteria objects in the QueryCriteria Collection, as a number.

This property is read-only.

Example

```
&COUNT = &MY_COLLECTION.Count;
```

QueryCriteria Class

A QueryCriteria object is returned from the following:

- The AddCriteria and AddHavingCriteria QuerySelect class method.
- The First, Item, and Next method of the QueryCriteria Collection.

See AddCriteria, AddHavingCriteria.

See QueryCriteria Collection.

See Working With Query Criteria and Expressions.

See "Choosing Selection Criteria" (PeopleTools 8.54: Query)"Defining Criteria" (PeopleTools 8.54: Query).

QueryCriteria Class Methods

In this section, we discuss the QueryCriteria class methods. The methods are discussed in alphabetical order.

AddExpr1Expression

Syntax

AddExpr1Expression()

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

The AddExpr1Expression method returns a reference to a new a QueryExpression object to be used as an expression for Expression 1. You can then use this object to specify details about the expression using the methods and properties of the QueryExpression Class.

Note: You must set the type for Expression 1 using the Expr1Type property before you can use this method.

Parameters

None.

Returns

A reference to a blank QueryExpression object.

Related Links

Expr1Expression
AddExpr1Field
Expr1Type
QueryExpression Class

AddExpr1Field

Syntax

AddExpr1Field(*QueryRecordAlias*, *FieldName*)

Description

The AddExpr1Field method returns a reference to a new a QueryField object to be used as a field for Expression 1. You can then use this object to specify details about the expression using the methods and properties of the QueryField Class.

Note: You must set the type for Expression 1 using the Expr1Type property before you can use this method.

Parameters

QueryRecordAlias	Specify the alias of the QueryRecord that contains the QueryField that you want to use.
FieldName	Specify the name of the QueryField in the QueryRecord that you want to use.

Returns

A reference to a blank QueryField object.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

Expr1Field
AddExpr1Expression
Expr1Type
QueryField Class

AddExpr2Expression

Syntax

AddExpr2Expression()

Description

The AddExpr2Expression method returns a reference to a new a QueryExpression object to be used as an expression for Expression 2. You can then use this object to specify details about the expression using the methods and properties of the QueryExpression Class.

Parameters

None.

Returns

A reference to a blank QueryExpression object.

Related Links

QueryExpression Class

AddExpr2Field1

Syntax

AddExpr2Field1(*QueryRecordAlias*, *FieldName*)

Description

Expression 2 has two field expressions because when the Between relational operator is used in a criteria, there can be two expression fields. The AddExpr2Field1 method returns a reference to a new QueryField object to be used as a *field 1* for Expression 2. You can then use this object to specify details about the expression using the methods and properties of the QueryField Class.

Parameters

QueryRecordAlias	Specify the alias of the QueryRecord that contains the QueryField that you want to use.
FieldName	Specify the name of the QueryField in the QueryRecord that you want to use.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

A reference to a blank QueryField object.

Related Links

QueryRecord Class
QueryField Class

AddExpr2Field2

Syntax

```
AddExpr2Field2(QueryRecordAlias, FieldName)
```

Description

Expression 2 has two field expressions because when the Between relational operator is used in a criteria, there can be two expression fields. The AddExpr2Field2 method returns a reference to a new a QueryField object to be used as a *field 2* for Expression 2. You can then use this object to specify details about the expression using the methods and properties of the QueryField Class.

Parameters

QueryRecordAlias	Specify the alias of the QueryRecord that contains the QueryField that you want to use.
FieldName	Specify the name of the QueryField in the QueryRecord that you want to use.

Returns

A reference to a blank QueryField object.

Related Links

QueryRecord Class
QueryField Class

AddExpr2List

Syntax

```
AddExpr2List()
```

Description

Expression 2 can have a list of values when the Operator is of type In List (or Not In List). The AddExpr2List method returns a reference to a new QueryList, which can be used to add a list of values to the criteria.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

None.

Returns

A reference to a blank QueryList object.

Related Links

QueryList Class

AddExpr2Subquery

Syntax

AddExpr2Subquery()

Description

The AddExpr2Subquery method is used to create a subquery for Expression2. This method returns a new QuerySelect object you can use to specify details about the new subquery.

Warning! The new subquery created with this method replaces any existing subquery (for this criteria), destroying any existing properties or values.

Parameters

None.

Returns

A reference to a new QuerySelect object.

Related Links

QuerySelect Class

QueryCriteria Class Properties

In this section, we discuss the QueryCriteria class properties. The properties are discussed in alphabetical order.

Expr1Expression

Description

This property returns a reference to the QueryExpression object that's used as Expression 1.

This property is valid only when Expression 1 exists as an expression. If you want to add an expression for Expression 1, use the AddExpr1Expression method.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-write.

Related Links

AddExpr1Expression

Expr1Field

Description

This property returns a reference to the QueryField object that's used as Expression 1.

This property is valid only when Expression 1 exists as a field. You can then use the QueryField Class methods and property to manipulate this object.

If you want to add a field for Expression 1, use the AddExpr1Field method.

This property is read-only.

Related Links

QueryField Class, AddExpr1Field

Expr1Type

Description

This property returns or sets the type for Expression 1.

Note: You *must* set the type of expression for every new criteria.

The values are:

Numeric Value	*Constant Value*	*Description*
2	%Query_ExprField	Field
3	%Query_Expression	Expression

This property is read-write.

Example

The following is used to test the expression to determine the property to use to retrieve it:

```
&MyExpr1 = &MyCrtColl.Next();
If &MyExpr1.Expr1Type = %Query_ExprField Then /* Expression is a Field */

   &OldExpr1Value = &MyExpr1.Expr1Field;
   /* do processing */

Else  /* Expression 1 is an expression */

   &OldExpr1Value = &MyExpr1.Expr1Expression;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
   /* Do processing */

End-if;
```

The following is an example showing how to add a field for Expression 1.

```
/* add a new criteria */
&MyCriteria = &MyQuery.AddCriteria();

/* set the type of the first expression to be a field */
&MyCriteria.Expr1Type = %Query_ExprField;

/* add the field EMPLID from the ABSENCE_HIST record */
&MyField = &MyCriteria.AddExpr1Field("A", "EMPLID");
```

Expr2Constant1

Description

If the Between relational operator is used in the criteria, there can be two constants for Expression 2. This property returns or sets the constant value for the first constant for Expression 2. This property takes a string value.

This property is valid only when Expression 2 is defined as a constant.

This property is read-write.

Expr2Constant2

Description

If the Between relational operator is used in the criteria, there can be two constants for Expression 2. This property returns or sets the constant value for the second constant for Expression 2. This property takes a string value.

This property is valid only when Expression 2 is defined as a constant.

This property is read-write.

Expr2Expression1

Description

If the Between relational operator is used in the criteria, there can be two expressions for Expression 2. This property returns a reference to the first QueryExpression object that's used as Expression 2.

This property is valid only when Expression 2 exists as an expression. To add an expression for Expression 2, use the AddExpr2Expression method.

This property is read-write.

Related Links

AddExpr2Expression

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Expr2Expression2

Description

If the Between relational operator is used in the criteria, there can be two expressions for Expression 2. This property returns a reference to the second QueryExpression object that's used as Expression 2.

This property is valid only when Expression 2 exists as an expression. To add an expression for Expression 2, use the AddExpr2Expression method.

This property is read-write.

Related Links

AddExpr2Expression

Expr2Field1

Description

If the Between relational operator is used in the criteria, there can be two fields for Expression 2. This property returns a reference to the first QueryField object that's used as Expression 2.

This property is only valid when Expression 2 exists as a field. You can then use the QueryField Class methods and property to manipulate this object.

To add a field for Expression 2, use the AddExpr2Field1 method.

This property is read-only.

Related Links

AddExpr2Field1, QueryField Class

Expr2Field2

Description

If the Between relational operator is used in the criteria, there can be two fields for Expression 2. This property returns a reference to the second QueryField object that's used as Expression 2.

This property is valid only when Expression 2 exists as a field. You can then use the QueryField Class methods and property to manipulate this object.

To add a field for Expression 2, use the AddExpr2Field2 method.

This property is read-only.

Related Links

AddExpr2Field2, QueryField Class

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Expr2List

Description

This property returns a reference to the QueryList object of Expression 2 that's used when the Operator is of type In List (or Not In List).

This property is read-only.

Expr2Subquery

Description

This property returns a reference to the QuerySelect object that's used as a subquery for Expression 2.

This property is valid only when Expression 2 exists as a subquery. To add a subquery for Expression 2, use the AddExpr2Subquery method.

This property is read-only.

Related Links

AddExpr2Subquery

Expr2Type

Description

This property returns or sets the type for Expression 2. The following table lists all of possible values for this property. However, the values for this property are dependent upon the Operator property.

This property is read-write.

See Operator, Working With Query Criteria and Expressions.

You can use either a constant or numeric value for this property. The values are:

Numeric Value	*Constant Value*	*Description*
1	%Query_ExprConstant	Constant
2	%Query_ExprField	Field
3	%Query_Exprression	Expression
4	%Query_ExprSubQuery	Subquery
5	%Query_ExprList	List
6	%Query_ExprCurDt	Current date

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Numeric Value	*Constant Value*	*Description*
7	%Query_ExprTree	Tree
8	%Query_ExprBind	Bind
9	%Query_ExprBothConst	The criterion's operator is Between and both values on the right-hand side are constants. (Const-Const)
10	%Query_ExprConstFld	The criterion's operator is Between, the first value on right-hand side is a constant and the second value is a field. (Const-Field)
11	%Query_ExprConstExpr	The criterion's operator is Between, the first value on right-hand side is a constant and the second value is an expression. (Const-Expr)
12	%Query_ExprFieldConst	The criterion's operator is Between, the first value on right-hand side is a field and the second value is a constant. (Field-Const)
13	%Query_ExprBothFld	The criterion's operator is Between and both values on the right-hand side are constants. (Field-Field)
14	%Query_ExprFldExpr	The criterion's operator is Between, the first value on right-hand side is a field and the second value is an expression. (Field-Expr)
15	%Query_ExprExprConst	The criterion's operator is Between, the first value on right-hand side is an expression and the second value is a constant. (Expr-Const)
16	%Query_ExprExprFld	The criterion's operator is Between, the first value on right-hand side is an expression and the second value is a field. (Expr-Field)
17	%Query_ExprBothExpr	The criterion's operator is Between and both values on the right-hand side are expressions. (Expr-Expr)
18	%Query_ExprTreePrompt	Tree prompt

The following table describes how to access or change Expression 2 depending on the Expression2 Type.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Expression2 Type	***Method or Property for Changing the Expression***	***Method or Property for Accessing the Expression***
Constant	Expr2Constant	Expr2Constant
Field	AddExpr2Field()	Expr2Field
Expression	AddExpr2Expression()	Expr2Expression
In List	AddExpr2List	Expr2List
In Tree	AddExpr2Expression	Expr2Expression
Subquery	AddExpr2Subquery()	Expr2Subquery
Const-Const	Expr2Constant, Expr2Constant	Expr2Constant, Expr2Constant
Const-Field	Expr2Constant, AddExpr2Field()	Expr2Constant, Expr2Field
Const-Expr	Expr2Constant, AddExpr2Expression()	Expr2Constant, Expr2Expression
Field-Const	AddExpr2Field(), Expr2Constant	Expr2Field, Expr2Constant
Field-Field	AddExpr2Field(), AddExpr2Field()	Expr2Field, Expr2Field
Field-Expr	AddExpr2Field(), AddExpr2Expression()	Expr2Field, Expr2Expression
Expr-Const	AddExpr2Expression(), Expr2Constant	Expr2Expression, Expr2Constant
Expr-Field	AddExpr2Expression(), AddExpr2Field()	Expr2Expression, Expr2Field
Expr-Expr	AddExpr2Expression(), AddExpr2Expression()	Expr2Expression, Expr2Expression

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

The following is used to test the expression to determine the property to use to retrieve it:

```
&MyExpr2 = &MyCriteria.Expr2Expression;

If &MyExpr2.Expr2Type = %Query_ExprConstant Then /* Expression is a constant */

   &OldValue = &MyExpr2.Expr2Constant;
   /* do processing */

End-if;
```

The following is an example showing how to add a field for Expression 2:

```
( )
/* After setting the first expression, set the operator for the criteria*/
&MyCriteria.Operator = %Query_CondEqual;

/* Set the type of the second expression to be a field */
&MyCriteria.Expr2Type = %Query_ExprField;

/* Add the EMPLID field from the ABSENCE_HIST record whose record alias is A */
&MyField = &MyCriteria.AddExpr2Field("A", "EMPLID" );
```

Logical

Description

This property returns or sets the logical portion of a criteria.

Note: This property is valid only when there are more than one criteria for a query. Also, this property is required when there is more than one criteria for a query.

The values are:

Numeric Value	*Constant Value*	*Description*
1	%Query_CombAnd	Logical And for non-having criteria
2	%Query_CombOr	Or for non-having criteria
3	%Query_CombNotUsed	No logical operator. Used for the first non-having criteria.
4	%Query_CombHaveAnd	Logical And for having criteria
5	%Query_CombHaveOr	Logical Or for having Criteria
6	%Query_CombHaveNotUsed	No logical operator. Used for the first having criteria.

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

LParenLvl

Description

This property returns or sets the left parenthesis level used for grouping criteria. This property takes a numeric value.

This property is read-write.

Name

Description

This property returns the name of the Query Criteria, as a string.

This property is read-only.

Negation

Description

This property returns a Boolean value, indicating whether a criterion is negated: True if the criterion is negated, False if it isn't.

This property is read-write.

Operator

Description

This property returns or sets the operator for the criteria.

The value of this property determines the valid types of the Expression 2, set with the Expr2Type property.

This property is read-write.

See Expr2Type, Working With Query Criteria and Expressions.

You can use either a constant or numeric value for this property. The values are:

Numeric Value	*Constant Value*	*Description*
1	%Query_CondNone	None (used for initializing a new criteria.)
2	%Query_CondEqual	Criteria's left-hand side is equal to right-hand side (= operator)
3	%Query_CondNotEqual	Criteria's left-hand side is not equal to right-hand side (<> operator)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Numeric Value	*Constant Value*	*Description*
4	%Query_CondGreaterThan	Criteria's left-hand side is greater than right-hand side (> operator)
5	%Query_CondNotGreaterThan	Criteria's left-hand side is not greater than right-hand side (<= operator)
6	%Query_CondLessThan	Criteria's left-hand side is less than right-hand side (< operator)
7	%Query_CondNotLessThan	Criteria's left-hand side is not less than right-hand side (>= operator)
8	%Query_CondInList	Criteria's left-hand side is in the given list (IN operator)
9	%Query_CondNotInList	Criteria's left-hand side is not in the given list (Not IN operator)
10	%Query_CondBetween	Criteria's left-hand side is between the two values of right-hand side (BETWEEN operator)
11	%Query_CondNotBetween	Criteria's left-hand side is not between the two values of right-hand side (BETWEEN operator)
12	%Query_CondExists	Criteria's left-hand side is the output of the subquery of right-hand side (EXISTS operator)
13	%Query_CondNotExists	Criteria's left-hand side doesn't exist in the output of the subquery of right-hand side (NOT EXISTS operator)
14	%Query_CondLike	Criteria's left-hand side is like (wildcard search) the right-hand side (LIKE operation)
15	%Query_CondNotLike	Criteria's left-hand side is not like (wildcard search) the right-hand side (NOT LIKE operation)
16	%Query_CondNull	Criteria's left-hand side is NULL (NULL operation)
17	%Query_CondNotNull	Criteria's left-hand side is not NULL (IS NOT NULL operation)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Numeric Value	*Constant Value*	*Description*
18	%Query_CondInTree	Criteria's left-hand side is from a list of nodes in Tree (IN operation)
19	%Query_CondNotInTree	Criteria's left-hand side is not from a list of nodes in Tree (NOT IN operation)
20	%Query_CondEffDtLessEqual	Criteria's left-hand side is an Effective Date and is less than or equal to the date on the right-hand side (<= operation)
21	%Query_CondEffDtGreaterEqual	Criteria's left-hand side is an Effective Date and is greater than or equal to the date on the right-hand side (>= operation)
22	%Query_CondEffDtLess	Criteria's left-hand side is an Effective Date and is less than the date on the right-hand side (< operation)
23	%Query_CondEffDtGreater	Criteria's left-hand side is an Effective Date and is greater than the date on the right-hand side (> operation)
24	%Query_CondFirstEffDt	Criteria's left-hand side is the first effective date (Function MIN())
25	%Query_CondLastEffDt	Criteria's left-hand side is the last effective date (Function MAX())
26	%Query_CondInTreeJoin	Criteria's left-hand side is an In Tree Join.

R1ExprNum

Description

This property returns or sets the expression number for the first expression of Expression 2. This property takes a numeric value.

This property is read-write.

R2ExprNum

Description

This property returns or sets the expression number for the second expression of Expression 2. This property takes a numeric value.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-write.

R1ExprType

Description

This property returns the expression type for the first expression of Expression 2. This property takes a numeric value and is the same range of values as the Expr2Type. It helps distinguish the type of an expression based on the value of Expr2Type. For instance, if the Expr2Type is Field-Expr, R1Expr2Type is of type Field and R2Expr2Type is of type Expression.

This property is read-only.

R2ExprType

Description

This property returns the expression type for the second expression of Expression 2. This property takes a numeric value and is the same range of values as the Expr2Type. It helps distinguish the type of an expression based on the value of Expr2Type. For instance, if the Expr2Type is Field-Expr, R1Expr2Type is of type Field and R2Expr2Type is of type Expression.

This property is read-only.

RParenLvl

Description

This property returns or sets the right parenthesis level used for grouping criteria. This property takes a numeric value.

This property is read-write.

QueryExpression Collection

A QueryExpression Collection is returned from the Expressions Query class property.

See Expressions.

QueryExpression Collection Methods

In this section, we discuss the QueryExpression collection methods. The methods are described in alphabetical order.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

First

Syntax

First()

Description

The First method returns the first QueryExpression object in the QueryExpression collection.

Parameters

None.

Returns

A reference to a QueryExpression object if successful, NULL otherwise.

Example

```
&MyQueryExpression = &MyCollection.First();
```

Item

Syntax

Item(*number*)

Description

The Item method returns the QueryExpression object that exists at the *number* position in the QueryExpression collection.

Parameters

Number	Specify the position number in the collection of the QueryExpression object that you want returned.

Returns

A reference to a QueryExpression object if successful, NULL otherwise.

Example

```
For &I = 1 to &QueryExpressionColl.Count;
   &MyQueryExpression = &QueryExpressionColl.Item(&I);
   /* do processing */
End-For;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ItemByName

Syntax

ItemByName(*ExpressionName*)

Description

The ItemByName method returns the QueryExpression object in the QueryExpressionCollection with the given expression name.

Parameters

ExpressionName	The name of the required expression.

Returns

A reference to a QueryExpression object if successful, NULL otherwise.

Example

```
&QryExpr = &QryExprCol.Item("Exp-6");
```

Next

Syntax

Next()

Description

The Next method returns the next QueryExpression object in the QueryExpression collection. You can use this method only after you have used the First method: otherwise the system doesn't know where to start.

Parameters

None.

Returns

A reference to a QueryExpression object if successful, NULL otherwise.

Example

```
&MyQueryExpression = &MyCollection.Next();
```

QueryExpression Collection Property

In this section, we discuss the Count property.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Count

Description

This property returns the number of QueryExpression objects in the QueryExpression Collection, as a number.

This property is read-only.

Example

```
&COUNT = &MY_COLLECTION.Count;
```

QueryExpression Class

A QueryExpression object is returned by the following:

- The AddExpression method of the Query class.
- The First, Item and Next methods of the QueryExpression collection.
- Some of the QueryCriteria class methods.
- The Expr1Expression and Expr2Expression1 properties of the QueryCriteria class.

See AddExpression, QueryExpression Collection, QueryCriteria Class Methods, Expr1Expression, Expr2Expression1.

See Working With Query Criteria and Expressions.

QueryExpression Class Properties

In this section, we discuss the QueryExpression class properties. The properties are discussed in alphabetical order.

Aggregate

Description

This property specifies whether the expression is an aggregate function.

This property takes a Boolean value: True if the expression is an aggregate function, False, otherwise.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

BindFlag

Description

This property specifies whether the expression contains a bind value, as Boolean value.

This property is mainly used while reading a query, to determine whether a Query Expression contains a bind value. It isn't necessary to set this value while saving a query to the database.

Values are:

Value	*Description*
False	Expression doesn't have a bind value
True	Expression has a bind value

This property is read-write.

Decimal

Description

This property returns or sets the decimal value of the expression.

This property is only valid with numeric fields.

This property is read-write.

ExpNum

Description

This property returns or sets the unique expression number, as a numeric value.

This property is read-write.

IsXlatExpression

Description

This property indicates whether the expression is for a translate field. This property takes a Boolean value: True, the expression is based on a translated field.

This property is read-only.

Length

Description

This property returns or sets the length of the expression, as a number.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-write.

Name

Description

This property returns the name of the expression, as a string.

This property is read-only.

OutputField

Description

This property returns the instance of the displayed expression field, as a QueryField. This property returns a NULL when the expression isn't used in a displayed (output) field.

This property is read-write.

RightExprFlag

Description

This property specifies whether an expression is used in the right-hand side of a criteria (that is, is it an Expr2 expression), as a Boolean value.

This property is typically used while reading a query to determine whether a Query Expression is used in the right-hand side of criteria. It's not necessary to set this value while saving a query to the database.

Values are:

Value	***Description***
False	Expression is not used in the right-hand side of the criteria
True	Expression is used in the right-hand side of the criteria

This property is read-write.

SelectedField

Description

This property returns the instance of the expression field, as a QueryField. This property returns a NULL when the expression is used only in the right-hand side of a criteria.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Text

Description

This property returns or sets the text of the expression, as a character string.

This property is read-write.

Using ORACLE Hints in Expressions

Oracle hints can be included in expressions using the following considerations:

- Expression containing a hint must begin with /*+.
- Expression can only contain one hint. For example, only one set of /* */ is allowed in each expression.
- Each /* must precede an */.
- Each expression must contain a complete hint. For example, an expression can't have only /* or */. Both must be in same expression.

Type

Description

This property returns or sets the field type of the expression.

You can specify either a constant or a numeric value. The values are:

Numeric Value	*Constant Value*	*Description*
0	%FieldType_Char	Character
1	%FieldType_LongChar	Long Character
2	%FieldType_Number	Number
3	%FieldType_SignedNumber	Signed number
4	%FieldType_Date	Date
5	%FieldType_Time	Time
6	%FieldType_DateTime	DateTime
7	%FieldType_Image	Image
11	%FieldType_URL	Drilling URL

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

QueryList Class

A QueryList Class is returned from the Expr2List property and AddExpr2List method of the QueryCriteria Class.

See Expr2List, AddExpr2List.

QueryList Class Methods

In this section, we discuss the QueryList class methods. The methods are discussed in alphabetical order.

AddListValue

Syntax

```
AddListValue(Value, IsPrompt)
```

Description

The AddListValue method adds a new List Value into the QueryList instance.

Parameters

Value	Specify the string value to be added to the list
IsPrompt	Specify whether the string specified by *Value* is a bind variable. This parameter takes a Boolean value: True, *Value* is a bind variable.

Returns

A reference to a QueryListValue object if successful, NULL otherwise.

Example

```
&MyListValue = &MyList.AddListValue("1", False);
```

First

Syntax

```
First()
```

Description

The First method returns the first QueryListValue object in the QueryList instance.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

None.

Returns

A reference to a QueryListValue object if successful, NULL otherwise.

Example

```
&MyListValue = &MyList.First();
```

Item

Syntax

Item(*number*)

Description

The Item method returns the QueryListValue object that exists at the *number* position in the QueryList instance.

Parameters

Number	Specify the position number in the QueryList object that you want returned.

Returns

A reference to a QueryListValue object if successful, NULL otherwise.

Example

```
For &I = 1 to &QueryList.Count;
   &QryListVal = & QueryList.Item(&I);
   /* do processing */
End-For;
```

Next

Syntax

Next()

Description

The Next method returns the next QueryListValue object in the QueryList instance. This method should be called after calling First, else it returns NULL.

Parameters

None.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

A reference to a QueryListValue object if successful, NULL otherwise.

Example

```
&MyNextListValue = &MyList.Next();
```

QueryList Class Property

In this section, we discuss the Count property.

Count

Description

This property returns the number of QueryListValue objects in the QueryList Collection, as a number.

This property is read-only.

Example

```
&ListValueCount = &MYList.Count;
```

QueryListValue Class

A QueryListValue instance is returned from the AddListValue, First, Item, or Next QueryList Class methods.

See QueryList Class Methods.

QueryListValue Class Properties

In this section, we discuss the QueryListValue class properties. These properties are discussed in alphabetical order.

IsPrompt

Description

This property indicates whether the value is a bind variable (such as :1). This property returns a Boolean value: True, this property is a bind variable.

This property is read-only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Value

Description

This property returns a string for the value stored in the list.

This property is read-only.

QueryRecordHierarchy Collection

A QueryRecordHierarchy collection is returned from the RecordHierarchy QueryDBRecord property.

The order of each QueryRecordHierarchy object in the collection maps to the order of each tree node as it appears in the tree hierarchy from top to bottom.

See RecordHieracHy.

QueryRecordHierarchy Collection Methods

In this section, we discuss the QueryRecordHierarchy collection methods. The methods are discussed in alphabetical order.

First

Syntax

First()

Description

The First method returns the first QueryRecordHierarchy object in the QueryRecordHierarchy collection.

Parameters

None.

Returns

A reference to a QueryRecordHierarchy object if successful, NULL otherwise.

Example

```
&MyQueryRecordHierarchy = &MyCollection.First();
```

Item

Syntax

Item(*number*)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

The Item method returns the QueryRecordHierarchy object that exists at the *number* position in the QueryRecordHierarchy collection.

Parameters

Number Specify the position number in the collection of the QueryRecordHierarchy object that you want returned.

Returns

A reference to a QueryRecordHierarchy object if successful, NULL otherwise.

Example

```
For &I = 1 to &QueryRecordHierarchyColl.Count;
   &MyQueryRecordHierarchy = &QueryRecordHierarchyColl.Item(&I);
   /* do processing */
End-For;
```

ItemByName

Syntax

ItemByName(*Name*)

Description

The ItemByName method returns the QueryRecordHierarchy object with the name *Name*.

Parameters

Name Specify the name of an existing QueryRecordHierarchy within the QueryRecordHierarchy collection. If you specify an invalid name, the object is NULL.

Returns

A reference to a QueryRecordHierarchy object if successful, NULL otherwise.

Example

```
&MyQueryRecordHierarchy = &MyCollection.ItemByName("PHONELIST");
```

Next

Syntax

Next()

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

The Next method returns the next QueryRecordHierarchy object in the QueryRecordHierarchy collection. You can use this method only after you have used the First method: otherwise the system doesn't know where to start.

Parameters

None.

Returns

A reference to a QueryRecordHierarchy object if successful, NULL otherwise.

Example

```
&MyQueryRecordHierarchy = &MyCollection.Next();
```

QueryRecordHierarchy Collection Property

In this section, we discuss the QueryRecordHierarchy properties. These properties are discussed in alphabetical order.

Count

Description

This property returns the number of QueryRecordHierarchy objects in the QueryRecordHierarchy Collection, as a number.

This property is read-only.

Example

```
&COUNT = &MY_COLLECTION.Count;
```

QueryRecordHierarchy Class

A reference to a QueryRecordHierarchy object is returned by the First, Item, ItemByName, and Next QueryRecordHierarchy Collection methods.

Every QueryRecordHierarchy object returned from a collection represents a record node in the Record Hierarchy tree in Query tab of PeopleSoft Query.

The QueryRecordHierarchy object returned from the QueryField represents the prompt table for the record field.

See QueryRecordHierarchy Collection.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

QueryRecordHierarchy Class Properties

In this section, we discuss the QueryRecordHierarchy class properties. The properties are discussed in alphabetical order.

Description

Description

This property returns a description of the record node as a string.

This property is read-only.

Level

Description

This property returns the level of the record node in the record hierarchy. 1 is the root node, 2 is a node beneath the root node, 3 is a child of that, and so on.

This property is read-only.

Name

Description

This property returns the name of the record node as a string.

This property is read-only.

ParentFlag

Description

This property returns the parent flag. The values are:

Value	*Description*
0	Record node contains no children nodes.
1	Record node contains children nodes

This property is read-only.

Query Metadata Collection

A Query Metadata collection is returned by the Metadata Query class property.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

See Metadata.

See Using Query Metadata.

Query Metadata Collection Methods

In this section, we discuss the Query Metadata collection methods. These methods are discussed in alphabetical order.

First

Syntax

```
First()
```

Description

The First method returns the first Query Metadata object in the Query Metadata collection.

Parameters

None.

Returns

A reference to a Query Metadata object if successful, NULL otherwise.

Example

```
&MyMetadata = &MyCollection.First();
```

Item

Syntax

```
Item(number)
```

Description

The Item method returns the Query Metadata object that exists at the *number* position in the Query Metadata collection.

Parameters

number	Specify the position number in the collection of the Query Metadata object that you want returned.

Returns

A reference to a Query Metadata object if successful, NULL otherwise.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

```
For &I = 1 to &MetadataColl.Count;
   &MyMetadata = &MetadataColl.Item(&I);
   /* do processing */
End-For;
```

ItemByName

Syntax

ItemByName(*Name*)

Description

The ItemByName method returns the Query Metadata object with the name *Name*.

Parameters

Name	Specify the name of an existing Query Metadata within the Query Metadata collection. If you specify an invalid name, the object is NULL.

Returns

A reference to a Query Metadata object if successful, NULL otherwise.

Example

```
&MyMetadata = &MyQuery.Metadata.ItemByName("Descr");
```

Next

Syntax

Next()

Description

The Next method returns the next Query Metadata object in the Query Metadata collection. You can use this method only after you have used the First method: otherwise the system doesn't know where to start.

Parameters

None.

Returns

A reference to a Query Metadata object if successful, NULL otherwise.

Example

```
&MyMetadata = &MyCollection.Next();
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Query Metadata Collection Property

In this section, we discuss the Count property.

Count

Description

This property returns the number of Query Metadata objects in the Query Metadata Collection, as a number.

This property is read-only.

Example

```
&COUNT = &MY_COLLECTION.Count;
```

Query Metadata Class

A Query Metadata object is returned from the Query Metadata Collection methods First, Item, ItemByName, or Next.

See Query Metadata Collection.

See Using Query Metadata.

Query Metadata Class Properties

In this section, we discuss the Query Metadata class properties. The properties are discussed in alphabetical order.

Name

Description

This property returns the name of each Query Metadata property as a string.

Values for this property are:

Value	*Description*
Descr	Description
LongDescr	Long description

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Value	*Description*
Public/Private	Specifies if the query is public or private. If the query is private, the name of the owner is listed in Value.
LastUpdDttm	Last updated date and time
LastUpdOprId	The UserId of the user who updated the value last
Record	Record name. May be more than one.
Input Param	Input parameter. May be more than one.
Expression	Expression. May be more than one.
Field	Record field name for the output column. May be more than one.
Heading	Heading name for the output column. May be more than one.

This property is read-only.

Value

Description

This property returns the value for the Query Metadata property as a string.

This property is read-only.

QueryStatistics Class

The QueryStatistics class is used to view statistical information about a query's execution. It can be useful for query administration. You can view query statistics for a query before you save it to the database.

A QueryStatistics Class is returned from the QueryStatistics Query property.

See QueryStatistics.

QueryStatistics Class Properties

In this section, we discuss the QueryStatistics properties. The properties are discussed in alphabetical order.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

AvgExecTime

Description

This property returns the average execution time for the query as a number.

This property is read-only.

AvgFetchTime

Description

This property returns the average fetch time for the query as a number.

This property is read-only.

AvgNumRows

Description

This property returns the average number of rows fetched for the query.

This property is read-only.

ExecCount

Description

This property returns the total number of times the query has been executed.

This property is read-only.

LastExecDtTm

Description

This property returns the last date and time the query was executed, as a string.

This property is read-only.

QuerySecurityProfile Class

The QuerySecurityProfile class is used to view the current user's security profile for PeopleSoft Query. This class doesn't contain any methods, and all the properties are read-only. An instance of this class is returned by the GetQuerySecurityProfile Session method.

See GetQuerySecurityProfile.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

QuerySecurityProfile Class Properties

In this section, we discuss the QuerySecurityProfile properties. The properties are discussed in alphabetical order.

AllowAnyJoin

Description

This property indicates whether the user is allowed to define queries with any join. This property takes a Boolean value: True, the user can define such queries.

This property is read-only.

AllowDistinct

Description

This property indicates whether the user can define queries with a Distinct clause in a SELECT statement. This property takes a Boolean value: True, the user can define such queries.

This property is read-only.

AllowExpressions

Description

This property indicates whether the user is allowed to define expressions in queries. This property takes a Boolean value: True, the user can define such queries.

This property is read-only.

AllowSubqueries

Description

This property indicates whether the user is allowed to define criteria containing subqueries. This property takes a Boolean value: True, the user can define such queries.

This property is read-only.

AllowUnions

Description

This property indicates whether the user is allowed to define queries containing unions. This property takes a Boolean value: True, the user can define such queries.

This property is read-only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ApprovePrivateQuery

Description

This property indicates whether the user is allowed to approve private queries. This property takes a Boolean value: True, the user can approve such queries. This property is meant for query administration.

This property is read-only.

ApprovePublicQuery

Description

This property indicates whether the user is allowed to approve public queries. This property takes a Boolean value: True, the user can approve such queries. This property is meant for query administration.

This property is read-only.

CanCreatePublic

Description

This property indicates whether the user can create public queries. This property takes a Boolean value: True, the user can create such queries.

This property is read-only.

CanCreateWorkFlow

Description

This property indicates whether the user can create or run any workflow queries. Workflow queries are of the following types:

- Archive
- Process
- Role

This property takes a Boolean value: True, the user can create such queries.

This property is read-only.

CanModifyQuery

Description

This property indicates whether the user can modify queries. This property takes a Boolean value: True, the user can modify queries.

This property is read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

CanRunQuery

Description

This property indicates whether the user can run queries. This property takes a Boolean value: True, the user can run queries.

This property is read-only.

CanRunToCrystal

Description

This property indicates whether the user can run queries to a Crystal report. This property takes a Boolean value: True, the user can run queries.

This property is read-only.

CanRunToExcel

Description

This property indicates whether the user can run queries to an Excel spreadsheet. This property takes a Boolean value: True, the user can run queries.

This property is read-only.

LimitUnapproved

Description

This property indicates whether there is a limit on the number of rows returned for unapproved queries. This property is meant for query administration. This property takes a Boolean value: True, limit the number of rows. The MaxUnapprovedRows property is active only if this property is specified as True.

This property is read-only.

Related Links

MaxUnapprovedRows

MaxInTreeCriteria

Description

This property indicates the maximum number of In Tree Criteria that can be used in the queries defined by the current user. This property takes a numeric value.

This property is read-only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

MaxJoins

Description

This property indicates the maximum number of joins allowed in the queries defined by the current user. This property takes a numeric value.

This property is read-only.

MaxRowsToFetch

Description

This property indicates the maximum number of rows to fetch for the current user when a query is executed. This property takes a numeric value.

This property is read-only.

MaxUnapprovedRows

Description

This property indicates the maximum number of rows that can be returned for unapproved queries. This property takes a numeric value. This property is meant for query administration. This property is active only if the property LimitUnapproved is True.

This property is read-only.

Related Links

LimitUnapproved

QueryDBRecord Collection

A QueryDBRecord collection is returned from the FindQueryDBRecords session method.

See FindQueryDBRecords.

QueryDBRecord Collection Methods

In this section, we discuss the QueryDBRecord collection methods. The methods are discussed in alphabetical order.

First

Syntax

```
First()
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

The First method returns the first QueryDBRecord object in the QueryDBRecord collection.

Parameters

None.

Returns

A reference to a QueryDBRecord object if successful, NULL otherwise.

Example

```
&MyQueryDBRecord = &MyCollection.First();
```

Item

Syntax

Item(*number*)

Description

The Item method returns the QueryDBRecord object that exists at the *number* position in the QueryDBRecord collection.

Parameters

Number	Specify the position number in the collection of the QueryDBRecord object that you want returned.

Returns

A reference to a QueryDBRecord object if successful, NULL otherwise.

Example

```
For &I = 1 to &QueryDBRecordColl.Count;
   &MyQueryDBRecord = &QueryDBRecordColl.Item(&I);
   /* do processing */
End-For;
```

ItemByName

Syntax

ItemByName(*Name*)

Description

The ItemByName method returns the QueryDBRecord object with the name *Name*.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

Name	Specify the name of an existing QueryDBRecord within the QueryDBRecord collection. If you specify an invalid name, the object is NULL.

Returns

A reference to a QueryDBRecord object if successful, NULL otherwise.

Example

```
&MyQueryDBRecord = &MyCollection.ItemByName("PHONELIST");
```

Next

Syntax

```
Next()
```

Description

The Next method returns the next QueryDBRecord object in the QueryDBRecord collection. You can use this method only after you have used the First method: otherwise the system doesn't know where to start.

Parameters

None.

Returns

A reference to a QueryDBRecord object if successful, NULL otherwise.

Example

```
&MyQueryDBRecord = &MyCollection.Next();
```

QueryDBRecord Collection Property

In this section, we discuss the Count property.

Count

Description

This property returns the number of QueryDBRecord objects in the QueryDBRecord Collection, as a number.

This property is read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

```
&COUNT = &MY_COLLECTION.Count;
```

QueryDBRecord Class

A QueryDBRecord object is returned from the QueryDBRecord Collection methods First, Item, ItemByName, or Next.

See QueryDBRecord Collection.

QueryDBRecord Class Methods

In this section, we discuss the QueryDBRecord class methods. The methods are discussed in alphabetical order.

QueryDBRecordFieldByIndex

Syntax

QueryDBRecordFieldByIndex(*Index*)

Description

The QueryDBRecordFieldByIndex method returns the QueryDBRecordField object that exists at the *index* position in the QueryDBRecordField collection.

Parameters

Index	Specify the position number in the collection of the QueryDBRecordField object that you want returned.

Returns

A reference to a QueryDBRecordField object if successful, NULL otherwise.

Related Links

QueryDBRecordFieldByName
QueryDBRecordField Class

QueryDBRecordFieldByName

Syntax

QueryDBRecordFieldByName(*Name*)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

The QueryDBRecordFieldByName method returns the QueryDBRecordField object with the name *Name*.

Parameters

Name	Specify the name of the QueryDBRecordField object that you want returned.

Returns

A reference to a QueryDBRecordField object if successful, NULL otherwise.

Related Links

QueryDBRecordFieldByIndex
QueryDBRecordField Class

QueryDBRecord Class Properties

In this section, we discuss the QueryDBRecord class properties. The properties are discussed in alphabetical order.

Description

Description

This property returns the description of the QueryDBRecord as a string.

This property is read-only.

Name

Description

This property returns the name of the QueryDBRecord as a string.

This property is read-only.

QueryDBRecordFields

Description

This property returns a reference to a QueryDBRecordField Collection.

This property is read-only.

Related Links

QueryDBRecordField Collection

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

RecordHierachy

Description

This property returns a reference to a QueryRecordHierarchy Collection.

The record hierarchy is not related to the query tree hierarchy shown when viewing access groups. Instead, it reflects an actual relationship between the record components, as defined in Application Designer using the Parent Record Name feature.

This property is read-only.

Related Links

QueryRecordHierarchy Collection "Understanding PeopleSoft Query" (PeopleTools 8.54: Query)

QueryDBRecordField Collection

A QueryDBRecordField collection is returned from the QueryDBRecordFields QueryDBRecord property.

See QueryDBRecordFields.

QueryDBRecordField Collection Methods

In this section, we discuss the QueryDBRecordField collection methods. The methods are discussed in alphabetical order.

First

Syntax

```
First()
```

Description

The First method returns the first QueryDBRecordField object in the QueryDBRecordField collection.

Parameters

None.

Returns

A reference to a QueryDBRecordField object if successful, NULL otherwise.

Example

```
&MyQueryDBRecordField = &MyCollection.First();
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Item

Syntax

Item(*number*)

Description

The Item method returns the QueryDBRecordField object that exists at the *number* position in the QueryDBRecordField collection.

Parameters

Number	Specify the position number in the collection of the QueryDBRecordField object that you want returned.

Returns

A reference to a QueryDBRecordField object if successful, NULL otherwise.

Example

```
For &I = 1 to &Coll.Count;
   &MyQueryDBRecordField = &Coll.Item(&I);
   /* do processing */
End-For;
```

ItemByName

Syntax

ItemByName(*Name*)

Description

The ItemByName method returns the QueryDBRecordField object with the name *Name*.

Parameters

Name	Specify the name of an existing QueryDBRecordField within the QueryDBRecordField collection. If you specify an invalid name, the object is NULL.

Returns

A reference to a QueryDBRecordField object if successful, NULL otherwise.

Example

```
&MyQueryDBRecordField = &MyCollection.ItemByName("PHONELIST");
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Next

Syntax

Next()

Description

The Next method returns the next QueryDBRecordField object in the QueryDBRecordField collection. You can use this method only after you have used the First method: otherwise the system doesn't know where to start.

Parameters

None.

Returns

A reference to a QueryDBRecordField object if successful, NULL otherwise.

Example

```
&MyQueryDBRecordField = &MyCollection.Next();
```

Sort

Syntax

Sort(*SortCriteria*)

Description

Use the Sort method to sort the fields within the QueryDBRecordField collection, based on the sort criteria specified with the method.

Parameters

SortCriteria Specify the sort order for the list. This parameter can take either a constant or numeric value. See below.

The values for *OutputFormat* can be as follows:

Numeric Value	***Constant Value***	***Description***
1	%Query_SortNameAsc	Sort database fields in ascending order based on field name.
2	%Query_SortNameDesc	Sort database fields in descending order based on field name.
3	%Query_SoftFldNumAsc	Sort database fields in ascending order based on field number.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Numeric Value	*Constant Value*	*Description*
4	%Query_SortFldNumDesc	Sort database fields in descending order based on field number.

Returns

0

QueryDBRecordField Collection Property

In this section, we discuss the Count property.

Count

Description

This property returns the number of QueryDBRecordField objects in the QueryDBRecordField Collection, as a number.

This property is read-only.

Example

```
&COUNT = &MY_COLLECTION.Count;
```

QueryDBRecordField Class

A QueryDBRecordField object is from the QueryDBRecord Collection methods First, Item, ItemByName or Next.

See QueryDBRecord Collection.

QueryDBRecordField Class Method

In this section, we discuss the QueryDBRecordField class methods in alphabetical order.

GetImageFormat

Syntax

GetImageFormat()

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the GetImageFormat method to differentiate between images and files, both stored as BLOBs in the database.

Note: Because images and files share the field type value 8, this method is required to differentiate between the two types.

Parameters

None.

Returns

A number. A value 16 indicates that the field is of type file (or attachment).

Related Links

Type

QueryDBRecordField Class Properties

In this section, we discuss the QueryDBRecordField class properties. The properties are discussed in alphabetical order.

Decimal

Description

This property returns the decimal positions for a field. This indicates how many numbers are allowed on the right side of the decimal.

This property is read-only.

Example

```
&FldDecs = &QryDBRcdFlds.Decimal;
```

Description

Description

This property returns the long description of the field as a string.

This is property is read-only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Flag

Description

This property returns the Use and Edit Flags of the field, which are set when the Field is defined in Application Designer, as a numeric value.

Values for Use Flags are:

Value	*Description*
1	Key
2	Duplicate Key
4	System
8	Audit Field Add
16	Alternate Key
32	List Item
64	Descending Key
128	Audit Field Change
1024	Audit Field Delete
2048	Search Item
32768	Auto Update

Values for Edit Flags are:

Value	*Description*
256	Required
512	Edit Translate
4096	Date Range Edit
8192	Yes/No Table Edit
16384	Edit Table
262144	From Search Field
524288	Through Search Field

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Value	*Description*
8388608	Use Default Label Flag
16777216	Default Search Field

This is a read-only property.

Format

Description

This property returns the field format for a field. Values are:

Value	*Description*
1	No format
2	Name
3	Phone Number North America
4	Zip/Postal Code North America
5	Social Security Number (SSN)
6	Uppercase
7	Mixed case
8	Raw binary
9	Numbers only
10	Canadian Social Insurance Number (SIN)
11	Phone Number International
12	Zip/Postal Code International
13	Seconds
14	Microseconds
15	Custom

This property is read-only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Length

Description

This property returns the length of the field as a number.

This property is read-only.

LongName

Description

This property returns the long name of the field as a string.

This property is read-only.

LookupTableName

Description

If the field has a lookup table associated with it, this property returns the name of that Lookup Table, else it returns an empty string.

This is a read-only property.

LookupTableRecord

Description

If the field has a lookup table associated with it, this property returns the instance of the QueryDBRecord for that Lookup Table, else it returns NULL.

This is a read-only property.

Name

Description

This property returns the name of the field as a string.

This property is read-only.

Shortname

Description

This property returns the short name of the field as a string.

This property is read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Type

Description

This property returns the type of the field. You can specify either a constant or a numeric value for this property. The values are:

Numeric Value	*Constant Value*	*Description*
0	%FieldType_Char	Character
1	%FieldType_LongChar	Long Character
2	%FieldType_Number	Number
3	%FieldType_SignedNumber	Signed number
4	%FieldType_Date	Date
5	%FieldType_Time	Time
6	%FieldType_DateTime	DateTime
8	%FieldType_Image	Image
8	%FieldType_File	File
9	%FieldType_ImageRef	ImageReference

Note: The Image and File types can be differentiated using the GetImageFormat method of the QueryField class.

This property is read-only.

Related Links

GetImageFormat

QueryPrompt Collection

A QueryPrompt collection is returned from the Prompts and RuntimePrompts Query class properties.

See Prompts, RunTimePrompts.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

QueryPrompt Collection Methods

In this section, we discuss the QueryPrompt collection methods. The methods are discussed in alphabetical order.

First

Syntax

First()

Description

The First method returns the first QueryPrompt object in the QueryPrompt collection.

Parameters

None.

Returns

A reference to a QueryPrompt object if successful, NULL otherwise.

Example

```
&MyQueryPrompt = &MyCollection.First();
```

Item

Syntax

Item(*number*)

Description

The Item method returns the QueryPrompt object that exists at the *number* position in the QueryPrompt collection.

Parameters

Number	Specify the position number in the collection of the QueryPrompt object that you want returned.

Returns

A reference to a QueryPrompt object if successful, NULL otherwise.

Example

```
For &I = 1 to &QueryPromptColl.Count;
   &MyQueryPrompt = &QueryPromptColl.Item(&I);
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
   /* do processing */
End-For;
```

ItemByName

Syntax

ItemByName(*Name*)

Description

The ItemByName method returns the QueryPrompt object with the name *Name*.

Parameters

Name	Specify the name of an existing QueryPrompt within the QueryPrompt collection. If you specify an invalid name, the object is NULL.

Returns

A reference to a QueryPrompt object if successful, NULL otherwise.

Example

```
&MyQueryPrompt = &MyCollection.ItemByName("PHONELIST");
```

Next

Syntax

Next()

Description

The Next method returns the next QueryPrompt object in the QueryPrompt collection. You can use this method only after you have used the First method: otherwise the system doesn't know where to start.

Parameters

None.

Returns

A reference to a QueryPrompt object if successful, NULL otherwise.

Example

```
&MyQueryPrompt = &MyCollection.Next();
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

QueryPrompt Collection Property

In this section, we discuss the QueryPrompt collection properties. The properties are discussed in alphabetical order.

Count

Description

This property returns the number of QueryPrompt objects in the QueryPrompt Collection, as a number.

This property is read-only.

Example

```
&COUNT = &MY_COLLECTION.Count;
```

QueryPrompt Class

A reference to a QueryPrompt is returned by the following:

- The First, Item, ItemByName, and Next methods of a QueryPrompt Collection.
- The AddPrompt Query class method.

See QueryPrompt Collection, AddPrompt.

See "Defining Prompts" (PeopleTools 8.54: Query).

QueryPrompt Properties

In this section, we discuss the QueryPrompt properties. The properties are discussed in alphabetical order.

EditType

Description

This property returns or sets the edit type for the field. This property takes a number value. The values are:

Value	*Description*
0	No table edit
16384	Prompt table

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Value	*Description*
512	Translate table
8192	Yes/No

This property is read-write.

FieldDecimal

Description

This property returns or sets the decimal value for the field.

This property is only valid with number fields.

This property is read-write.

FieldFormat

Description

This property returns the field format for a field. This property takes a number value. Values are:

Value	*Description*
0	None
1	Name
2	Phone
3	Zip Code
4	Social Security Number
5	Upper
6	Mixed Case
7	Century
8	Number Only
9	Social Insurance Number
10	International Phone Number
11	International Postal Code

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Value	*Description*
12	Seconds
13	Microseconds
14	Century/Seconds
15	Century/Microseconds

This property is read-only.

FieldLength

Description

This property returns or sets the field length.

This property is read-write.

FieldName

Description

This property returns or sets the field name used with the prompt.

This property is read-write.

FieldType

Description

This property returns or sets the field type of the field used with the prompt.

This property returns the type of the field. You can specify either a constant or a numeric value. The values are:

Numeric Value	*Constant Value*	*Description*
0	%FieldType_Char	Character
1	%FieldType_LongChar	Long Character
2	%FieldType_Number	Number
3	%FieldType_SignedNumber	Signed number
4	%FieldType_Date	Date

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Numeric Value	Constant Value	Description
5	%FieldType_Time	Time
6	%FieldType_DateTime	DateTime
7	%FieldType_Image	Image

This property is read-write.

HeadingText

Description

This property returns or sets the heading text for the prompt field.

This property is read-write.

HeadingType

Description

This property returns or sets the heading type for the query field. This property takes either a constant or numeric value. The values are:

Numeric Value	Constant Value	Description
1	%Query_HdgNone	Query field has no heading.
2	%Query_HdgText	Query field has a text heading.
3	%Query_HdgRftShort	Query field uses the short RFT heading.
4	%Query_HdgRftLong	Query fields uses the long RFT heading.

This property is read-write.

LangCount

Description

This property returns the total count of the language records for the current prompt.

This property is read-only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Name

Description

This property returns a string containing the Prompt name. When an existing query is read, this name is the same as the Field Name. When a new prompt is added using AddPrompt, this is the *Name* parameter used with that method.

This property is read-only.

PromptRecordFieldName

Description

When you have more than one field with the same name in the prompt collection, the system generates a unique prompt field name for each repeated field. The generated names are of the form Bind1, Bind2, and so on. This property returns the unique name for the prompt record field.

This property is read-only.

PromptTable

Description

This property returns or sets the prompt table name for the prompt field.

This property is read-write.

UniquePromptName

Description

This property returns or sets the unique prompt name for the prompt field.

This property is read-write.

UseCount

Description

This property returns the total count of the usage of the current prompt.

This property is read-only.

The following are examples of the usual actions that you perform using the query classes.

Query Classes Examples

The following are examples of the usual actions that you perform using the query classes.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Creating a New Query

In this example, you are creating a new query, adding a record and two fields. The following is the complete code sample: the steps explain each line.

```
Local ApiObject &aQuery, &aQrySelCol;
Local ApiObject &COLL, &ERROR;
Local String &TEXT;
Local Session &MySession;
Local Record &aQryRcd;
Local Field &aQryFld;

&MySession = %Session;

If &MySession <> Null Then

   &aQuery = &MySession.GetQuery();

   &aQuery.Create("TEST1", False, %Query_Query, "PIA Test 1", "Creating Test Query ⇒
1 from PIA Page");

   &aQrySel = &aQuery.AddQuerySelect();

   &aQryRcd = &aQrySel.AddQueryRecord("ABSENCE_HIST");
   &aQryFld = &aQrySel.AddQuerySelectedField("ABSENCE_HIST", "A", "EMPLID", "ID");

   If &aQryFld <> Null Then
         &aQryFld.ColumnNumber = 1;
         &aQryFld.HeadingType = %Query_HdgRftShort;
      End-If;

   &Rslt = &aQuery.Save();

   If &Rslt <> 0 Then
      /* save didn't complete */
      &COLL = &MySession.PSMessages;

      For &I = 1 to &COLL.Count
         &ERROR = &COLL.Item(&I);
         &TEXT = &ERROR.Text;
         /* do error processing */
      End-For;

      &COLL.DeleteAll();
   End-if;
    /* error processing for not getting a session */
End-if;
```

To create a new query:

1. Get a session object.

   Before you can create a query, you have to get a session object. The session controls access to the query, provides error tracing, enables you to set the runtime environment, and so on. Then this program checks to verify that the session object is valid.

   ```
   &MySession = %Session;

   &aQuery = &MySession.GetQuery();

   If &MySession <> Null Then
   ```

2. Create the query.

   Use the Create method to create the query. This query is a private query, of type query.

   ```
   &aQuery.Create("TEST1", False, %Query_Query, "Test 1", "Creating Test Query");
   ```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

3. Add a QuerySelect.

   The QuerySelect contains the main query statement for the query. There can be multiple QuerySelect objects for queries that involve unions or subqueries. Each select (or union or subquery) consists of QueryRecords, QueryOutputFields, QuerySelectedFields, and QueryCriteria and is treated as a child of the MAIN select statement.

```
&aQrySel = &aQuery.AddQuerySelect();
```

4. Add a record and a field.

   The AddQueryRecord method adds a query record to the query. The AddQuerySelectedField adds a field, using the record alias "A". The ID is what gets displayed in the heading for the query.

```
&aQryRcd = &aQrySel.AddQueryRecord("ABSENCE_HIST");
&aQryFld = &aQrySel.AddQuerySelectedField("ABSENCE_HIST", "A", "EMPLID", "ID")⇒
;
```

5. Make the field an output field.

   The field was added as a selected field. By setting the ColumnNumber to a number greater than one, the field is now an output field. The text that's displayed in the heading comes from the RFT short description of the field.

```
      If &aQryFld <> Null Then
         &aQryFld.ColumnNumber = 1;
         &aQryFld.HeadingType = %Query_HdgRftShort;
      End-If;
```

6. Save the data.

   When you execute the Save method, the new query is saved to the database.

```
&Rslt = &aQuery.Save();

If &Rslt <> 0 Then
```

   The Save method returns a numeric value: 0 if successful. You can use this value to do error checking.

7. Check Errors.

   You can check if there were any errors using the PSMessages property on the session object.

```
   /* save didn't complete */
   &COLL = &MySession.PSMessages;
   For &I = 1 to &COLL.Count
      &ERROR = &COLL.Item(&I);
      &TEXT = &ERROR.Text;
      /* do error processing */
   End-For;
   &COLL.DeleteAll();
End-if;
```

   If there are multiple errors, all errors are logged to the PSMessages collection, not just the first occurrence of an error. As you correct each error, you may want to delete it from the PSMessages collection.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Adding Criteria

In this example, you are accessing an existing query, then adding criteria both as part of the query as well as part of a subquery. The SQL statement created by this subquery is as follows:

```
SELECT RECNAME, RECDESCR, RELLANGRECNAME, PARENTRECNAME, DESCRLONG from PSRECDEFN w⇒
here RECNAME IN (select OBJECTVALUE1 from PSPROJECTITEM where PROJECTNAME = 'PPLTOO⇒
LS') AND RECTYPE = 0 order by RECNAME
```

The following is the complete code sample: the steps explain each line.

```
Local ApiObject &MyQuery, &MainQrySel, &Criteria1, &MyCrit2Expr2, &MyCriteria2;
Local ApiObject &SubQrySel, &SubQryCrit1, &SubQryExpr1, &MyCrit2Expr2;
Local Record &SubQryRec;
Local Session = &MySession;
Local ApiObject &COLL, &ERROR;
Local String &TEXT;

&MySession = %Session;

If &MySession <> Null Then

&MyQuery = &MySession.GetQuery();

&MyQuery.Open("Table", False, True);

&MainQrySel = &MyQuery.QuerySelect;

/* Add query record, add fields, then make selected fields output fields */

&MainRec = &MainQrySel.AddQueryRecord("PSRECDEFN");

&QryFld = &MainQrySel.AddQuerySelectedField(&MainRec.Name, &MainRec.RecordAlias, "R⇒
ECNAME", "Record Name");
&QryFld.ColumnNumber = 1;
&QryFld.OrderByNumber = 1;

&QryFld = &MainQrySel.AddQuerySelectedField(&MainRec.Name, &MainRec.RecordAlias, "R⇒
ECDESCR", "Record Descr");
&QryFld.ColumnNumber = 2;
&QryFld.OrderByNumber = 2;

&QryFld = &MainQrySel.AddQuerySelectedField(&MainRec.Name, &MainRec.RecordAlias, "R⇒
ELLANGRECNAME", "Record Lang Rec");
&QryFld.ColumnNumber = 3;
&QryFld.OrderByNumber = 3;

&QryFld = &MainQrySel.AddQuerySelectedField(&MainRec.Name, &MainRec.RecordAlias, "P⇒
ARENTRECNAME", "Parent Record Name");
&QryFld.ColumnNumber = 4;

&QryFld = &MainQrySel.AddQuerySelectedField(&MainRec.Name, &MainRec.RecordAlias, "D⇒
ESCRLONG", "Long Descr");
&QryFld.ColumnNumber = 5;

&QryFld = &MainQrySel.AddQuerySelectedField(&MainRec.Name, &MainRec.RecordAlias, "E⇒
MPLID", "ID");
&QryFld.ColumnNumber = 6;

/* adding first criteria */
&Criteria1 = &MainQrySel.AddCriteria("FirstCriteria");

/* First criteria will not have any logical AND/OR */
&Criteria1.Logical = %Query_CombNotUsed;

&Criteria1.Expr1Type = %Query_ExprField;
&Criteria1.AddExpr1Field(&MainRec.RecordAlias, "RECNAME");
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
/* So that the criteria is constructed as - RECNAME IN (...)*/
&Criteria1.Operator = %Query_CondInList;
&Criteria1.Expr2Type = %Query_ExprSubQuery;

&SubQrySel = &Criteria1.AddExpr2SubQuery();
&SubQryRec = AddQueryRecord("PSPROJECTITEM");
&SubQryFld1 = &SubQrySel.AddQuerySelectedField(&SubQryRec.Name, &SubQryRec.RecordAl⇒
ias, "OBJECTVALUE1", "Join Object")
&SubQryFld1.ColumnNumber = 1;

/* Need criteria - PROJECTNAME = 'PPLTOOLS'  - in the subquery */
&SubQryCrit1 = &SubQrySel.AddCriteria("FirstSubCrit");

/* First criteria will not have any logical AND/OR */
&SubQryCrit1.Logical = %Query_CombNotUsed;

&SubQryCrit1.Expr1Type = %Query_ExprField;
&SubQryCrit1.AddExpr1Field(&SubQryRec.RecordAlias, "PROJECTNAME");
&SubQryCrit1.Operator = %Query_CondEqual;

/* So that the criteria is constructed as - PROJECTNAME = 'PPLTOOLS'*/
&SubQryCrit1.Expr2Type = %Query_ExprConstant;
&SubQryExpr1 = &SubQryCrit1.AddExpr2Expression();
&SubQryExpr1.Text = "PPLTOOLS";
&SubQryCrit1.Expr2Expression1 = &SubQryExpr1;

/* Second Criteria, which is for RECTYPE = 0 */
&MyCriteria2 = &MainQrySel.AddCriteria("SecondCriteria");

&MyCriteria2.Expr1Type = %Query_ExprField;
&MyCriteria2.AddExpr1Field(&MainRec.RecordAlias, "RECTYPE");

/* Since this is second criteria, we need a logical AND to state that */
/* - AND RECTYPE = 0 */

&MyCriteria2.Logical = %Query_CombAnd;

&MyCriteria2.Operator = %Query_CondEqual;
&MyCriteria2.Expr2Type = %Query_ExprConstant;
&MyCrit2Expr2 = &MyCriteria2.AddExpr2Expression();
&MyCriteria2.Expr2Expression1 = &MyCrit2Expr2;
&MyCrit2Expr2.Text = "0";

&Rslt = &MyQuery.Save();

If &Rslt <> 0 Then
   /* save didn't complete */
   &COLL = &MySession.PSMessages;

      For &I = 1 to &COLL.Count
         &ERROR = &COLL.Item(&I);
         &TEXT = &ERROR.Text;
         /* do error processing */
      End-For;

      &COLL.DeleteAll();
   End-if;

Else

/* do error processing for not getting session */

End-if;
```

To add criteria to a query:

1. Get a session object.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Before you can create a query, you have to get a session object. The session controls access to the query, provides error tracing, enables you to set the runtime environment, and so on. Then this program checks to verify that the session object is valid.

```
&MySession = %Session;

&MyQuery = &MySession.GetQuery();

If &MySession <> Null Then
```

2. Access an existing query and get the main query select statement.

   Use the Open method to get the existing query. Then access the main select statement with the QuerySelect property.

```
&MyQuery.Open("Table", False, True);

&MainQrySel = &MyQuery.QuerySelect;
```

3. Add Query Record in the Main Select.

   Add the query record that you want to use.

```
&MainRec = &MainQrySel.AddQueryRecord("PSRECDEFN");
```

4. Add the displayed fields.

   You want to add the selected fields. Note instead of hardcoding the name of the record, this code example uses the Name property. Also, the code uses the RecordAlias property instead of hardcoding the alias. This makes the code easier to read, as well as easier to maintain. Specifying a column number also makes this an output field.

```
&QryFld = &MainQrySel.AddQuerySelectedField(&MainRec.Name, &MainRec.RecordAlia⇒
s, "RECNAME", "Record Name");
&QryFld.ColumnNumber = 1;
```

5. Specify the OrderBy value.

   Because we need to order by this field, the OrderByNumber of that field must be set also.

```
&QryFld.OrderByNumber = 1;
```

6. Add the first criteria.

   Add the first criteria. You don't want it added with any kind of operator, like an AND or an OR, so the Logical property of the first criteria is set with %Query_CombNotUsed. This is also used because it's the first non-having criteria of a query.

```
/* adding first criteria */
&Criteria1 = &MainQrySel.AddCriteria("FirstCriteria");

/* First criteria will not have any logical AND/OR */
   &Criteria1.Logical = %Query_CombNotUsed;
```

7. Add the first criteria field.

   The first field for the criteria is a QueryExpression type field. The type of the field *must* be set before the field is added.

```
   &Criteria1.Expr1Type = %Query_ExprField;
   &Criteria1.AddExpr1Field(&MainRec.RecordAlias, "RECNAME");
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

8. Add the condition for the first criteria and the subquery.

   The first criteria is the WHERE RECNAME IN portion of the SQL statement. The condition is considered 'in list', where the list is the result of the subquery. The expression is a subquery. Again, you have to set the type again before adding the subquery.

```
&Criteria1.Operator = %Query_CondInList;
&Criteria1.Expr2Type = %Query_ExprSubQuery;
&SubQrySel = &Criteria1.AddExpr2SubQuery();
```

9. Add the records for the subquery.

   Add the query record and the field from the query field, and make it an output field.

```
&SubQryRec = AddQueryRecord("PSPROJECTITEM");
&SubQryFld1 = &SubQrySel.AddQuerySelectedField(&SubQryRecName.Name, &SubQryRec⇒
.RecordAlias, "OBJECTVALUE1", "Join Object");
&SubQryFld1.ColumnNumber = 1;
```

10. Add the criteria in the subquery.

    The following code adds the criteria for the subquery. Because this is the first non-having criteria in a select statement, the Logical property is set as %Query_CombNotUsed. Then the first expression is added as a field, and set to be equal to the second expression, PPLTOOLS. This is the where PROJECTNAME = 'PPLTOOLS' portion of the SQL statement.

```
/* Need criteria - PROJECTNAME = 'PPLTOOLS'  - in the subquery */
&SubQryCrit1 = &SubQrySel.AddCriteria("FirstSubQryCrit");

/* First criteria will not have any logical AND/OR */
   &SubQryCrit1.Logical = %Query_CombNotUsed;

   &SubQryCrit1.Expr1Type = %Query_ExprField;
   &SubQryCrit1.AddExpr1Field(&SubQryRec.RecordAlias, "PROJECTNAME");
&SubQryCrit1.Operator = %Query_CondEqual;

/* So that the criteria is constructed as - PROJECTNAME = 'PPLTOOLS'*/
&SubQryCrit1.Expr2Type = %Query_ExprConstant;
&SubQryExpr1 = &SubQryCrit1.AddExpr2Expression();
&SubQryExpr1.Text = "PPLTOOLS";
   &SubQryCrit1.Expr2Expression1 = &SubQryExpr1;
```

11. Add the second criteria to the main select.

    Add the second criteria. Remember to set the type for the expression field first. Because this is the second criteria, we need a logical AND to state that this criteria is used with the first criteria.

```
/* Second Criteria, which is for RECTYPE = 0 */
&MyCriteria2 = &MainQrySel.AddCriteria("SecondCriteria");

&MyCriteria2.Expr1Type = %Query_ExprField;
&MyCriteria2.AddExpr1Field(&MainRec.RecordAlias, "RECTYPE");

/* Since this is second criteria, we need a logical AND to state that*/
/* - AND RECTYPE = 0 */

&MyCriteria2.Logical = %Query_CombAnd;

&MyCriteria2.Operator = %Query_CondEqual;
&MyCriteria2.Expr2Type = %Query_ExprConstant;

&MyCrit2Expr2 = &MyCriteria2.AddExpr2Expression();
&MyCriteria2.Expr2Expression1 = &MyCrit2Expr2;
&MyCrit2Expr2.Text = "0";
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

12. Save the data.

    When you execute the Save method, the new query is saved to the database.

    ```
    &Rslt = &MyQuery.Save();

    If &Rslt <> 0 Then
    ```

    The Save method returns a numeric value: 0 if successful. You can use this value to do error checking.

13. Check Errors

    You can check if there were any errors using the PSMessages property on the session object.

    ```
       /* save didn't complete */
       &COLL = &MySession.PSMessages;
       For &I = 1 to &COLL.Count
          &ERROR = &COLL.Item(&I);
          &TEXT = &ERROR.Text;
          /* do error processing */
       End-For;
       &COLL.DeleteAll();
    End-if;
    ```

    If there are multiple errors, all errors are logged to the PSMessages collection, not just the first occurrence of an error. As you correct each error, you may want to delete it from the PSMessages collection.

Using Outer Joins

The following PeopleCode query uses outer joins:

```
   Local ApiObject &aQuery, &aQrySelCol;
   Local ApiObject &aQryRcd, &aQryRcd2;
   Local ApiObject &aQryFld, &aQryFld2;
   Local ApiObject &aQrySel, &Criteria1;
   Local number &Rslt;

   &aQuery = %Session.GetQuery();
   &aQuery.Create("TEST1", False, %Query_Query, "PIA Test 1", "Creating Test Query1⇒
 from PIA Page");

   &aQrySel = &aQuery.AddQuerySelect();

   &aQryRcd = &aQrySel.AddQueryRecord("JOB");
   &aQryRcd.RecordAlias = "A";

   &aQryRcd2 = &aQrySel.AddQueryRecord("PERSONAL_DATA");
   &aQryRcd2.RecordAlias = "B";
   &aQryRcd2.JoinType = %Query_JoinLeftOuter;
   &aQryRcd2.JoinAlias = "A";

   &aQryFld = &aQrySel.AddQuerySelectedField("JOB", "A", "EMPLID", "EMPLID");
   &aQryFld.ColumnNumber = 1;
   &aQryFld.HeadingType = %Query_HdgRftShort;

   &aQryFld2 = &aQrySel.AddQuerySelectedField("PERSONAL_DATA", "B", "NAME", "NAME")⇒
;
   &aQryFld2.ColumnNumber = 2;
   &aQryFld.HeadingType = %Query_HdgRftShort;

   &Criteria1 = &aQrySel.AddCriteria("JoinCriteria");
   &Criteria1.Logical = %Query_CombNotUsed;
   &Criteria1.Expr1Type = %Query_ExprField;
   &Criteria1.AddExpr1Field("A", "EMPLID");
   &Criteria1.Operator = %Query_CondEqual;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
&Criteria1.Expr2Type = %Query_ExprField;
&Criteria1.AddExpr2Field1("B", "EMPLID");
&Criteria1.OJAlias = "B";

&Rslt = &aQuery.Save();
```

The above PeopleCode program produces the following SQL:

```
SELECT A.EMPLID, B.NAME
FROM (PS_JOB A LEFT OUTER JOIN PS_PERSONAL_DATA B ON A.EMPLID=B.EMPLID)
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Chapter 39

Record Class

Understanding Record Class

A record object, instantiated from the Record class, is a single instance of a data within a row and is based on a record definition. A record object consists of one to *n* fields.

If a record object is instantiated using GetRecord (either the function or the method), the record object that is instantiated references the record from the current row in the data buffers, and its associated data.

If a record object is instantiated using the CreateRecord function, the record object that's instantiated is a freestanding record definition with its component set of field objects in the data buffer. The fields created by this function are initialized to null values, that is, they do *not* contain any data. Default processing is not performed. You can select into this record object using the SelectByKey method. You can also select into this record object using SQLExec.

CopyFieldsTo is a commonly used method for the record class. Name, IsChanged, and FieldCount are commonly used properties.

The record class is one of the data buffer access classes.

Related Links

"Understanding Data Buffer Access" (PeopleTools 8.54: PeopleCode Developer's Guide)

Shortcut Considerations

An expression of the form

```
RECORD.recname.property
```

or

```
RECORD.recname.method(.  .  .)
```

is converted to an object expression by using **`GetRecord`**`(`**`RECORD.`***`recname`***`)`. For example, the following two lines of code are equivalent:

```
&MyRow = RECORD.EMPL_CHKLST_ITEM.ParentRow;
```

```
&MyRow = GetRecord(RECORD.EMPL_CHKLST_ITEM).ParentRow;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

In addition, the default method for the Record class is the GetField method. This means you can access a field by just specifying the field name, instead of using GetField. For example, the following two lines of code, which both disable the EMPLID field, are equivalent:

```
&MyRec.EMPLID.Enabled = False;
```

```
&MyRec.GetField(FIELD.EMPLID).Enabled = False;
```

Note: If the field you're accessing has the same name as a record property (such as, Name) you can't use this method for accessing the field. You must use the GetField method.

Record Methods Used to Create SQL Statements

You can use the following record object methods to build and execute SQL statements:

- Delete
- SelectByKey
- Insert
- Save
- Update

The methods that result in a database update (specifically, UPDATE, INSERT, and DELETE) can only be issued in the following events:

- SavePreChange
- WorkFlow
- SavePostChange
- FieldChange

Remember that record UPDATEs, INSERTs, and DELETEs go directly to the database server, not to the Component Processor (although you can *view* data in the buffer using the PeopleCode debugger and other data buffer access classes). If a record method assumes that the database has been updated based on changes made in the component, that record method can be issued only in the SavePostChange event, because before SavePostChange none of the changes made to page data has actually been written back to the database.

If your application is repeating the same instruction many times, such as doing a million INSERTs, you should use the SQL object with the BulkMode property set to True, rather than the record SQL methods.

Related Links

Delete
SelectByKey
Insert
Update
Understanding SQL Class

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Data Type of a Record Object

Record objects are declared as type Record. For example,

```
Local Record &MYRECORD;
```

Scope of a Record Object

A record can only be instantiated from PeopleCode.

This object can be used anywhere you have PeopleCode, that is, in an application class, Application Engine PeopleCode, Component Interface PeopleCode, and so on.

Record Class Built-in Functions

"CreateRecord" (PeopleTools 8.54: PeopleCode Language Reference)

"GetRecord" (PeopleTools 8.54: PeopleCode Language Reference)

Record Class Methods

In this section, we discuss each Record class method. The methods are discussed in alphabetical order.

CompareFields

Syntax

CompareFields(*recordobject*)

Description

The CompareFields method compares all like-named fields of the record object executing the method with the specified record object *recordobject*.

Parameters

recordobject	Specify a record object for use in the comparison. The specified record object does not have to refer to the same record as the record object executing the method.

Returns

A Boolean value; True if all like-named fields have the same value.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

```
&REC = GetRecord(RECORD.OP_METH_VW);
&REC2 = GetRecord(RECORD.OPC_METH);
If &REC2.CompareFields(&REC) Then
    WinMessage("All liked named fields have the same value");
End-If;
```

Related Links

CopyChangedFieldsTo

CopyFieldsTo

CopyChangedFieldsTo

Syntax

CopyChangedFieldsTo(*recordobject*)

Description

The CopyChangedFieldsTo method copies all like-named field values that have changed from the record object executing the method to the specified record object *recordobject.* This copies only changed field values. To copy all field values, use the CopyFieldsTo method.

Note: This method works only with database records. The Component Processor doesn't track the contents of work records, so there is no changed value to use for copying changed fields.

Parameters

recordobject	Specify a record object to be copied to. The specified record object does not have to refer to the same record as the record object executing the method.

Returns

None.

Example

```
Local Record &REC, &REC2;

&REC = GetRecord(RECORD.OPC_METH);

/* make changes to the values of fields in the record */

&REC2 = CreateRecord(RECORD.OPC_METH_WORK);

&REC.CopyChangedFieldsTo(&REC2);
```

Related Links

CompareFields

CopyFieldsTo

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

CopyFieldsTo

Syntax

```
CopyFieldsTo(recordobject[, DontCopyUnusedInSource [, DontCopyUnusedInDestination]]
[,IsBatch])
```

Description

The CopyFieldsTo method copies all like-named field values from the record object executing the method to the specified record object *recordobject.* This copies all field values.

To copy only changed field values, use the CopyChangedFieldsTo method.

To restrict the copy to fields that have been marked as unused (set using the SetDBFieldNotUsed function) you can specify either *DontCopyUnusedInSource* or *DontCopyUnusedInDestination.*

Note: If you are copying to a derived work record, the IsChanged flag for the record is not set. Copying fields to a database record does set the IsChanged flag to True.

Parameters

recordobject

Specify a record object to be copied to. The specified record object does not have to refer to the same record as the record object executing the method.

DontCopyUnusedInSource

Specify this parameter to be True if you want to restrict the copy of fields to not include fields marked as unused in the record of the object performing the CopyFieldsTo method. This is the source record. The default value for this parameter is False, which means that there are no restrictions on the copy of unused fields as defined in the source record.

DontCopyUnusedInDestination

Specify this parameter to be True if you want to restrict the copy of fields to not include fields marked as unused in the recordobject record which is the destination record.

Note: To specify this record to be true you must specify a value for *DontCopyUnusedInSource*.

The default value for this parameter is False meaning that there are no restrictions on the copy of unused fields as defined in the destination record.

IsBatch

Specify whether this method is being called from an online program or from a batch program (such as an Application Engine program.) The default is false. Using this method may improve batch performance. When set to true, the system uses the FieldNotUsed information directly from the field properties already in the memory

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

None.

Example

```
Local Record &REC, &REC2;

&REC = GetRecord(RECORD.OPC_METH);
&REC2 = CreateRecord(RECORD.OPC_METH_WORK);
&REC.CopyFieldsTo(&REC2);
```

In the following example, records are copied into a record after being fetched.

```
Component number &displayNum;
Local SQL &sql;
Local Rowset &rs, &rs2;

&level0 = GetLevel0();
&displayNum = WS_NUM_ORDERS;

&rs = GetRowset(Record.WS_ORD_HDR_VW);
&rs.Flush();
WinMessage("1");
&sql = CreateSQL("%selectall(:1) where BUSINESS_UNIT=:2", Record.WS_ORD_HDR_VW, "M0⇒
4");
WinMessage("2");
&rec = CreateRecord(Record.WS_ORD_HDR_VW);

For &i = 1 To &displayNum

   If &sql.Fetch(&rec) Then

      &rs.InsertRow(&i);

      &rec.copyfieldsto(&rs.GetRow(&i).WS_ORD_HDR_VW);

      &rs2 = &rs.GetRow(&i).GetRowset(1);
      &rs2.Select(Record.WS_ORD_LINE_VW, "where BUSINESS_UNIT=:1 and ORDER_NO=:2", ⇒
&rec.BUSINESS_UNIT.value, &rec.ORDER_NO.value);

      /* Hide rows that do not contain Products */
      If &rs2 = Null Or None(&rs2.GetRow(1).WS_ORD_LINE_VW.ORDER_INT_LINE_NO.Value)⇒
 Then
         For &j = 1 To &rs2.ActiveRowCount
            &rs2.GetRow(&j).Visible = False;
         End-For;
      End-If;
   End-If;
End-For;

&rs.GetRow(&i).Visible = False;
```

The following example is for unused record fields:

```
Local Record &From = CreateRecord(Record.QE_UPS_TIME);

/* setup the initial values */

&From.QE_FROM_ZIP.Value = "12345";
&From.QE_TO_ZIP.Value = "67890";
&From.QE_UPS_TIME_BUTTON.Value = "A";
&From.DESCRLONG.Value = "This is the from record.";

/* Now make one of the fields unused */
Local string &ToZip_Value = "77777";

/* start out clean with &To */
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
Local Record &To = CreateRecord(Record.QE_UPS_TIME);
&To.QE_TO_ZIP.Value = &ToZip_Value;
If SetDBFieldNotUsed(Field.QE_TO_ZIP, True) <> %MetaDataChange_Success Then
   MessageBox(0, "", 0, 0, "SSetDBFieldNotUsed(Field.QE_TO_ZIP, TRUE) fails??");
End-If;
/* Copy no unused fields from the source record */
&From.CopyFieldsTo(&To, True /* no unused fields from source */);

/* Copy to no unused fields in the destination */
&From.CopyFieldsTo(&To, False /* all fields from source */, True /* no unused field⇒
s in dest */);

/* Copy no unused fields either in source or destination */

&From.CopyFieldsTo(&To, True /* no unused fields from source */, True /* no unused ⇒
fields in dest */);

/* Now finally make that field good again */

If SetDBFieldNotUsed(Field.QE_TO_ZIP, False) <> %MetaDataChange_Success Then
   MessageBox(0, "", 0, 0, "SSetDBFieldNotUsed(Field.QE_TO_ZIP, False) fails??");
End-If;
```

Related Links

CompareFields

CopyChangedFieldsTo

IsChanged

"SetDBFieldNotUsed" (PeopleTools 8.54: PeopleCode Language Reference)

Delete

Syntax

Delete()

Description

The Delete method uses the key fields of the record and their values to build and execute a DELETE SQL statement which deletes the record (row of data) from the SQL data table.

This method, like the DeleteRow Rowset class method, initially marks the record or row as needing to be deleted. At save time the row is actually deleted from the database and cleared from the buffer.

Because this method results in a database change, it can be issued only in the following events:

- SavePreChange
- WorkFlow
- SavePostChange

If your application is repeating the same instruction multiple times, such as doing a million DELETEs, use the SQL object with the BulkMode property set to True, rather than the record SQL methods.

For every record deleted by the Delete method, if the set language is not the base language and the record has related language records, the Delete method tries to do related language processing.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

None.

Returns

The result is True on successful completion, False if the record was not found. Any other conditions cause termination.

Example

Suppose that KEYF1 and KEYF2 are the two key fields of record definition MYRECORD. The following code deletes the database record that has KEYF1 equal to "A" and KEYF2 equal to "X":

```
Local record &REC;
&REC = CreateRecord(RECORD.MYRECORD);
&REC.KEYF1.Value = "A";
&REC.KEYF2.Value = "B";
&REC.MYRF3.Value = "X";
&REC.MYRF4.Value = "Y";
&REC.Insert();
```

Related Links

SelectByKey
Insert
Update
DeleteRow
Understanding SQL Class
"Understanding Related Language Tables" (PeopleTools 8.54: Global Technology)

ExecuteEdits

Syntax

ExecuteEdits([*editlevel*]);

where *editlevels* is a list of values in the form:

editlevel1 [+ *editlevel2*] . . .]);

and where *editleveln* is one of the following constants:

%Edit_DateRange

%Edit_OneZero

%Edit_PromptTable

%Edit_Required

%Edit_TranslateTable

%Edit_YesNo

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

The ExecuteEdits method executes the standard system edits on every field in the record. The types of edits performed depends on the *editlevel*. If no *editlevel* is specified, all system edits are executed. All *editlevels* are already defined for the record definition or for the field definition, that is:

- Reasonable Date Range (Is the date contained within the specified reasonable date range?)
- 1/0 (Do all 1/0 fields contain only a 1 or 0?)
- Prompt Table (Is field data contained in the specified prompt table?)
- Required Field (Do all required fields contain data? For numeric or signed fields, it checks that they do not contain NULL or 0 values.)
- Translate Table (Is field data contained in the specified translate table?)
- Yes/No (Do all yes/no fields only contain only yes or no data?)

Note: ExecuteEdits does not perform any validation on DateTime fields.

If any of the edits fail, the status of the property IsEditError is set to False for the record. The field property EditError is set to True for any fields that are in error. In addition, the Field class properties MessageNumber and MessageSetNumber are set to the number of the returned message and message set number of the returned message, for each field in error.

You must use the SetEditTable method to set the prompt tables for fields that are defined with %EditTable in the record definition.

If you're running an Application Engine program, and you want to do set based ExecuteEdits (as opposed to row-by-row) consider using the meta-SQL construct %ExecuteEdits.

See SetEditTable, EditError, MessageNumber, MessageSetNumber, "Using Application Engine Meta-SQL" (PeopleTools 8.54: Application Engine).

Considerations for ExecuteEdits and SetEditTable

If an effective date is a key on the prompt table, and the record being edited doesn't contain an EFFDT field, the current date and time is used as the key value.

If a SETID is a key on the prompt table, and the record being edited doesn't contain a SETID field, the system looks for SETID on the other records in the current row first, then searches parent rows.

For all other keys, the value used to "select" the correct row in the prompt table record comes only from the record executing the method. No other records (or key field values) are used. You may get unexpected results if not all the keys for the prompt table are filled in (or filled in correctly.)

Considerations for ExecuteEdits and Numeric Fields

A zero (0) might or might not be a valid value for a numeric field. ExecuteEdits processes numeric fields in different ways, depending on whether the field is required:

- If the numeric field is required: 0 is considered invalid.
- If the numeric field is not required: 0 is considered valid.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

editlevel

Specifies the standard system edits to be performed against every field on every record. If *editlevel* isn't specified, all system edits are performed. *editlevel* can be any of the following system variables.

- %Edit_DateRange
- %Edit_OneZero
- %Edit_PromptTable
- %Edit_Required
- %Edit_TranslateTable
- %Edit_YesNo

Returns

None.

Example

The following is an example of a call to execute Required Field and Prompt Table edits:

```
&REC.ExecuteEdits(%Edit_Required + %Edit_PromptTable);
```

The following is an example showing how ExecuteEdits() could be used:

```
&REC.ExecuteEdits();
If &REC.IsEditError Then
   LogError();  /*application specific call */
End-If;
```

Related Links

SetEditTable
IsEditError
EditError
MessageNumber
MessageSetNumber

GetField

Syntax

GetField({*n* | FIELD.*fieldname*})

Description

The GetField method instantiates a field object for the specified field associated with the record. This is the default method for the record object. This means that any record object, followed by a parameter list, acts as if GetField is specified.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Note: If the field you're accessing has the same name as a record property (that is, Name or FieldCount) you can't use the default method for accessing the field. You must specify GetField.

For example, the following is invalid for accessing the value of a field called NAME:

```
&NUMBER = &REC.NAME.Value;
```

You must use the following code to get the value of a field called NAME:

```
&NUMBER= &REC.GetField(FIELD.NAME).Value;
```

Parameters

n* | FIELD.*fieldname

Specify a field to be used for instantiating the field object. You can specify either *n* or **FIELD.** *fieldname*. Specifying *n* creates a field object for the *nth* field in the record. This might be used if writing code that needs to examine all fields in a record without being aware of the name. Specifying **FIELD.** *fieldname* creates a field object for the field *fieldname*.

Note: There is no way to predict the order the fields will be accessed. Use the *n* option only if the order in which the fields are processed doesn't matter.

Returns

A field object.

Example

```
&REC.GetField(FIELD.CHARACTER).Value = "Hello";
```

As GetField is the default method for a record object, the following code is identical to the previous code:

```
&REC.CHARACTER.VALUE = "Hello";
```

The following code creates an array containing all the names of all the fields in a related language record.

```
Local array of string &FIELD_LIST_ARRAY;
&FIELD_LIST_ARRAY = CreateArray();
For &I = 1 to &REC_RELATED_LANG.FieldCount
   &FIELD_LIST_ARRAY.Push(&REC_RELATED_LANG.GetField(&I).Name);
End-For;
```

The GetField method requires either FIELD.fieldname or a number. It won't take a string field name. However, you can use the @ operator to convert the string field name into a **FIELD**.*fieldname* reference, as follows:

```
&REC = GetRecord();
&REC2 = GetLevel0(1).EMPL_CHECKLIST;
&FIELD2 = &REC.GetField(@ "FIELD." | &REC2.getfield(&I).Name);
```

The following code converts field name strings (using the @ symbol) to component names to get the value of all the fields in a subrecord. Note the code in **Keyword style**.

```
Function get_draft_dst_codes
   /* Load dst id codes into record structures */
   &DSTCODES = CreateRecord(RECORD.DR_DST_CODE_SBR);
   &DRAFTITEM = GetRecord(RECORD.DRAFT_ITEM);
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
   &DRAFTITEM.CopyFieldsTo(&DSTCODES);
   /* If any missing get from AR dist code, then Draft Type-BU, then BU */
   For &I = 1 To &DSTCODES.FieldCount
      If None(&DSTCODES.GetField(&I).Value) Then
         get_ar_dst_code();
         &NAME = &DSTCODES.GetField(&I).Name;
         If All(&DST.GetField(@ ("FIELD." | &NAME)).Value) Then
            &DSTCODES.GetField(&I).Value = &DST.GetField(@("FIELD." | &NAME)).Value⇒
;
         Else
            If All(&R_DRAFTBU.GetField(@("FIELD." | &NAME)).Value) Then
               &DSTCODES.GetField(&I).Value = &R_DRAFTBU.GetField(@("FIELD." | &NAM⇒
E)).Value;
            Else
               &DSTCODES.GetField(&I).Value = &R_ARBU.GetField(@("FIELD." | &NAME))⇒
.Value;

            End-If;
         End-If;
      End-If;
   End-For;
   /* Copy the defaulted values back to draft item */
   &DSTCODES.CopyFieldsTo(&DRAFTITEM);
End-Function;
```

Related Links

"GetField" (PeopleTools 8.54: PeopleCode Language Reference)

Insert

Syntax

Insert()

Description

The Insert method uses the field names of the record and their values to build and execute an Insert SQL statement which adds the given record (row of data) to the SQL table.

Because this method results in a database change, it can only be issued in the following events:

- SavePreChange
- WorkFlow
- SavePostChange

If your application is repeating the same instruction many times, such as doing a million INSERTs, use the SQL object with the BulkMode property set to True, rather than the record SQL methods.

If you're using a record created using CreateRecord, all fields are initially set to "", 0, or NULL, depending on the type of field. If you don't specify values for these fields, these initial values are written to the database when the insert is executed. If you want the default values for the fields inserted instead, use the SetDefault method prior to using the Insert method.

For every record inserted with the Insert method, if the set language is not the base language and the record has related language records, the Insert method tries to do related language processing.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

Understanding SQL Class, "Understanding Related Language Tables" (PeopleTools 8.54: Global Technology), SetDefault

Parameters

None.

Returns

The result is True on successful completion, False if there was a record with those keys already in the database, that is, if a duplicate record was found. Any other conditions cause termination.

Example

Suppose that KEYF1 and KEYF2 are the key fields of record definition MYRECORD, and that this record definition also contains the field definitions MYRF3, MYRF4. The following code adds a MYRECORD record (row of data) to the database, with KEYF1 set to "A", KEYF2 set to "B", MYRF3 set to "X", and MYRF4 set to "Y":

```
Local record &REC;
&REC = CreateRecord(RECORD.MYRECORD);
&REC.KEYF1.Value = "A";
&REC.KEYF2.Value = "B";
&REC.MYRF3.Value = "X";
&REC.MYRF4.Value = "Y";
&REC.Insert();
```

Related Links

Delete

SelectByKey

Update

Save

Syntax

Save([*CopyToOriginal*])

Description

The Save method saves the record to the database in two steps.

1. Check to see that it is safe to save this record to the database.
2. Either insert this record or update an existing record.

To accomplish the first step and determine that it is safe to save the record, this method uses similar logic to that used in the component processor when it saves a record. To do that a “select for update” SQL statement is executed. If, as a result of this statement, the record does not exist in the database, this method simply inserts the record into the database. All the processing that occurs for the insert method then occurs.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

If the result of the “select for update” statement returns a record, the values of all the fields in the database record are compared to the original values of the record executing this method. If they are equal, indicating that no other user has updated the record, the record in the database is updated. All the processing that occurs for the update method then occurs. If the result of the above comparison fails, indicating that there has been an update of the database record in the meantime, perhaps by some other user, the save method fails and returns a false result.

For the update process to succeed, the record object must contain both original and changed values of the data. It is crucial to get data loaded into the record object correctly. To do this, do one of the following:

- Derive the record object from the component buffers.
- Derive the record object from a rowset filled using the Fill method.
- Load the data using the record class SelectByKey and SelectByKeyEffdt methods specifying the optional Boolean parameter to be False.

See the note and example below.

Of course when you use Save to simply insert data you do not need load data into the record object this way.

Use this method when you are writing applications that do not use the facilities that come predelivered with the component processor and you must deal with issues of data contention.

For example, suppose you are writing an application that deals with course registration. You have to handle changing the number of students who are registered carefully if it is possible for more than one user to be registering for the same course at the same time. The normal way is to use the component processor to handle data contention by placing the record that deals with the number of students registering on some page. Then if two users try to update the same record one of them receives a message indicating that the page has been updated by another user.

If you write an application, outside the component processor, that relies on the record class to manage the number of students enrolled, it is not sufficient to use the record class Insert or Update methods to maintain data integrity. Suppose one user registers for the course and sees there are 10 other registrants. At the same time another user registers for the course and sees that there are also 10 registrants. Suppose the maximum is 11 students. Both users at this point believe they can register since at the point they accessed the data from the database there were only 10 students. So far, so good. The trouble comes when they save their registrations. If the application uses the update method, after simply adding one to the number of registrants, both updates will succeed indicating there are now 11 students in the course when in fact there are now 12. It is for cases such as these that the Save method applies since it guarantees that one of the save calls will fail. It is up to the application then to let the user know that while they were thinking about it someone else registered for the course and took the last spot.

The Save method is important to maintain data integrity. However, it can execute more slowly than saving within the component processor.

Since this method results in a database change, and does either insert or update processing, all the considerations and implications of using the Insert or Update methods apply. See the description of those methods for more detail.

The parameter *CopyToOriginal* indicates what action should occur on a successful save. If this parameter is true, the system copies the current changed buffers for the record into the original buffers for the record. This means that subsequent Saves, without reloading data from the database will run correctly. However

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

if there are database specific updates to this record occurring outside of this application's control (such as, using database specific triggers,) it is always advisable to reload the data from the database.

The default value for this optional parameter is false, indicating that no update of the original buffers for this record occurs. If you are certain that there are no database updates occuring outside of your application's on save processing, you can specify this optional parameter to be true and save the overhead of having to reload the data for this record from the database. If you are unsure you should always reload the record data after calling the Save method.

Note: This method does *not* update fields marked as System maintained in the record definition in Application Designer.
Since this save is done outside the component processor save processing, no save processing PeopleCode that is associated with this record is executed.
Use of this method that results in an update, and requires that the data in the record object is such that both a before and after image of the data is kept. When the system loads data into the component buffers there is a concept of the “original data” (data loaded from the database) and “changed data” (data changed by the user or the application). This allows the system to determine when saving, whether the data has been changed by another user. If you use this method with record objects not derived from the component buffers you need to make sure that the data in the record object has both a before and after image otherwise the save method fails. Record objects derived from rowsets that have been populated using the Fill method will not produce an error. However if you load data into a record object using either the SelectByKey or SelectByKeyEffdt record class methods, you need to specify the *CopyToOriginal* parameter so the system will load the data into the original data buffers, not the changed data buffers. To do that specify the optional parameter to be False. See the example below.

Related Links

Insert, Update "Understanding Data Editing in Related Language Tables and Base Tables" (PeopleTools 8.54: Global Technology)

Parameters

CopyToOriginal	Specify what action should occur on a successful save. This parameter takes a Boolean value: true, then the system copies the current changed buffers for the record into the original buffers for the record, false, the buffers are not copied. The default value is false.

Returns

The result is True on successful completion, False if there were no changed fields in the record or it was not safe to save this record (see above for details). Any other conditions cause termination.

Note: It is not possible to ignore the return code from the Save method in your PeopleCode.

Example

Suppose that KEYF1 and KEYF2 are the key fields of record definition MYRECORD, and that this record definition also contains the record field definitions MYRF3, MYRF4. The following code tries to save MYRECORD record in the database with KEYF1 set to "A", KEYF2 set to "B", setting MYRF3 to

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

"X" and MYRF4 to "Y". This example works with a brand new record object and results in an insert if successful.

```
/* First -- create a brand new record */
Local record &REC;
&REC = CreateRecord(RECORD.MYRECORD);
&REC.KEYF1.Value = "A";
&REC.KEYF2.Value = "B";

/* Second -- update values as needed */
&REC.MYRF3.Value = "X";
&REC.MYRF4.Value = "Y";
/* Finally save it */
if &REC.Save() then
    /* handle the successful return */
else
    /* handle the unsuccessful return message to user? Try again? */
end-if;
```

This example works with an existing record and results in an update if successful.

```
/* First - create the record and get the data from the db */
Local record &REC;
&REC = CreateRecord(RECORD.MYRECORD);
&REC.KEYF1.Value = "A";
&REC.KEYF2.Value = "B";
&REC.SelectByKey(False);
/* False retrieves data into the original, not changed buffers. */

/* Second - update values as needed */
&REC.MYRF3.Value = "X";
&REC.MYRF4.Value = "Y";
/* Finally save it */
if &REC.Save() then
    /* handle the successful return */
else
    /* handle the unsuccessful return - message to user? Try again? */
end-if;
```

Related Links

Insert

Delete

SelectByKey

Update

SelectByKeyEffDt

SearchClear

Syntax

SearchClear()

Description

The SearchClear method clears the field values for all search keys for a record.

Considerations Using SearchClear and SearchDefault

The field property SearchDefault sets a field to its default value (if there is one) immediately after SearchInit PeopleCode finishes. SearchDefault overrides SearchClear. If you call SearchClear for a

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

record, then use SearchDefault for a field, the field is set to its default value and the search key values for the rest of the record are cleared.

Parameters

None.

Returns

None.

Example

```
Local Record &REC;

&REC = GetRecord();
&REC.SearchClear();
```

Related Links

SearchDefault
SearchClear

SelectByKey

Syntax

SelectByKey([*UseChangedBuffers*])

Description

The SelectByKey method uses the key field names of the record and their values to build and execute a Select SQL statement. The field values are then fetched from the database SQL table into the record object executing the method, and the Select statement is closed.

Note: You can't use this method in dynamic views.

If you don’t specify all the key fields for a record, those you exclude are added to the Where clause with the condition equal to a blank value. If not all keys are set and more than one row is retrieved, you won't receive an error and SelectByKey won’t fetch any data.

SelectByKey returns a single row of data. To fetch more than one row, use the SQL object.

For every record read by the SelectByKey method, if the set language is not the base language and the record has related language records, the SelectByKey method tries to do related language processing.

You can also select into a record using SQLExec and meta-SQL. For example, if you need to use SelectByKey with an effective date, you can use the meta-SQL %SelectByKeyEffDt in a SQLExec statement. In the following example, &RECOBJ is the name of a record created using the CreateRecord function.

```
SQLExec("%SelectByKeyEffDt(:1, :2)", &RECOBJ, %Date, &RECOBJ);
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

Understanding SQL Class, "Understanding Data Editing in Related Language Tables and Base Tables" (PeopleTools 8.54: Global Technology), "SQLExec" (PeopleTools 8.54: PeopleCode Language Reference)

Parameters

UseChangedBuffers

Specify whether to retrieve the data into the changed or original buffers. The system keeps track of the original and changed values. This parameter takes a Boolean value: true, retrieve into the changed buffers, False, use the original buffers. The default value is true. is to retrieve the data into the changed buffers.

To use this parameter with the Save method, it is important that data be loaded into the original buffers in order for the save logic to work. To do that specify a value of false for this parameter.

See Save.

Returns

The result is true on successful completion, false if the record was not found. Any other conditions cause termination.

If false is returned, the system resets the record values to their default values for scrolls that are not derived. If you do a manual insert afterwards (using the Insert method) you may insert a record with null keys.

Example

Suppose that KEYF1 and KEYF2 are the two key fields of record definition MYRECORD. The following code reads the database record that has KEYF1 equal to "A" and KEYF2 equal to "X" into the &REC record object:

```
Local record &REC;
&REC = CreateRecord(RECORD.MYRECORD);
&REC.KEYF1.Value = "A";
&REC.KEYF2.Value = "X";
&REC.SelectByKey();
```

The following example verifies if the method completes successfully before using the Insert method.

```
if not &Rec.SelectByKey() then

     /* Must duplicate this key field population before the Insert - else can get '⇒
blank' row */

      &Rec.KEY1.Value = ...;
      &Rec.KEY2.Value = ....;
      ....

     &Rec.Insert();

end-if;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

Delete
Insert
Update
Save

SelectByKeyEffDt

Syntax

SelectByKeyEffDt(*Date*[, *UseChangedBuffers*])

Description

Use the SelectKeyByEffDt to build and execute a SQL Select statement to get the current effective row based on an "as of date". The field values are then fetched from the database SQL table into the record object executing the method, and the Select statement is closed.

Note: You can't use this method in dynamic views.

SelectByKeyEffDt returns a single row of data. To fetch more than one row, use the SQL object.

For every record read by the SelectByKeyEffDt method, if the set language is not the base language and the record has related language records, the SelectByKeyEffDt method tries to do related language processing. The system assumes that both the base table and the related language table are effective-dated and that the effective-date keys are the same in each.

To use other keys, more than just the effective date, use the SelectByKey Record class method.

Parameters

Date

Specify the "as of" date you want to use as the effective date for the Select statement.

UseChangedBuffer

Specify whether to retrieve the data into the changed or original buffers. The system keeps track of the original and changed values. This parameter takes a Boolean value: true, retrieve into the changed buffers, False, use the original buffers. The default value is true. is to retrieve the data into the changed buffers.

To use this parameter with the Save method, it is important that data be loaded into the original buffers in order for the save logic to work. To do that specify a value of false for this parameter.

See Save.

Returns

The result is True on successful completion, False if the record was not found. Any other conditions cause termination.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

If false is returned, the system resets the record values to their default values for scrolls that are not derived. If you do a manul insert afterwards (using the Insert method) you may insert a record with null keys.

Example

```
Local Record &Rec;
Local any &Date;

&Date = %Date;
&Rec = CreateRecord(Record.COMPANY_TBL);
&Rec.COMPANY.Value = "CCB";

If &Rec.SelectByKeyEffDt(&Date) Then
   &Out = &Rec.DESCR.Value | " as of " | &Rec.EFFDT.Value | "->" | &Rec.STREET1.Val⇒
ue;
   WinMessage("Found this company: " | &Out);
Else
   WinMessage("Not there!");
End-If;
```

Related Links

Delete

Insert

Update

Save

SelectByKey

Understanding SQL Class

"Understanding Data Editing in Related Language Tables and Base Tables" (PeopleTools 8.54: Global Technology)

SetDefault

Syntax

SetDefault()

Description

SetDefault sets the value of every field in the record to a null value, or to a default, depending on the type of field.

- If this method is used against data from the Component buffers, the next time default processing occurs, it is set to its default value: either a default specified in its record field definition or one set programmatically by PeopleCode located in a FieldDefault event. If neither of these defaults exist, the Component Processor leaves the field blank.
- If this method is used with a field that isn't part of the data buffer (for example, a field in a record object instantiated with CreateRecord) the field is automatically set to its default value if one is set for the field, not for the record field. Any FieldDefault PeopleCode does not run on these types of fields. To set the default values for just one field, use the SetDefault field class method.

Blank numbers correspond to zero on the database. Blank characters correspond to a space on the database. Blank dates and long characters correspond to NULL on the database. SetDefault gives each field data type its proper value.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

None.

Returns

None.

Example

```
&CHARACTER.SetDefault();
```

Related Links

SetDefault
"Default Processing" (PeopleTools 8.54: PeopleCode Developer's Guide)

SetEditTable

Syntax

SetEditTable(*%PromptField*, RECORD.*recordname*)

Description

The SetEditTable method works with the ExecuteEdits method. It sets the value of a field on a record that has its prompt table defined as *%PromptField* value. %PromptField values are used to dynamically change the prompt record for a field.

There are several steps to setting up a field so that you can dynamically change its prompt table.

To set up a field with a dynamic prompt table:

1. Define a field in the DERIVED record called *fieldname*.
2. In the record definition for the field you want to have a dynamic prompt table, define the prompt table for the field as %*PromptField*, where *PromptField* is the name of the field you created in the DERIVED record.

   Note: When you use SetEditTable, you don't have to add a hidden field to the page.

3. Use SetEditTable to dynamically set the prompt table.

%PromptField is the name of the field on the DERIVED work record. RECORD.*recordname* is the name of the record to be used as the prompt table.

```
&REC.SetEditTable("%EDITTABLE1", Record.DEPARTMENT);
&REC.SetEditTable("%EDITTABLE2", Record.JOB_ID);
&REC.SetEditTable("%EDITTABLE3", Record.EMPL_DATA);
&REC.ExecuteEdits();
```

Every field on a record that has the prompt table field %EDITTABLE1 will have the same prompt table, that is, DEPARTMENT.

See ExecuteEdits, "Understanding Record Definitions" (PeopleTools 8.54: Application Designer Developer's Guide).

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Considerations for SetEditTable and ExecuteEdits

The keys used to "select" the correct row in the prompt table record come only from the record object executing the method. All the keys from the component are not used. You may get unexpected results if not all the keys for the prompt table are filled in (or filled in correctly.)

Parameters

%PromptField	Specifies the name of the field in the DERIVED record that has been defined as the prompt table for a field in the record definition.
RECORD.*recordname*	Specifies the name of the record definition that contains the correct standard system edits to be performed for that field in the record.

Returns

None.

Example

```
/* To Set the Prompt Table */
&Der_EditRec = &TSKPRF_Det_Row.GetRecord(Record.DERIVED);
&Prompt_Editname = &Der_EditRec.EDITTABLE.Value;
&Prompt_Edittable = "Record." | &Prompt_Editname;
&TSKPRF_Det_Rec.SetEditTable("%EDITTABLE", @&Prompt_Edittable);

&Prompt_Editname2 = &Der_EditRec.EDITTABLE2.Value;
&Prompt_Edittable2 = "Record." | &Prompt_Editname2;
&TSKPRF_Det_Rec.SetEditTable("%EDITTABLE2", @&Prompt_Edittable2);

&Prompt_Editname3 = &Der_EditRec.EDITTABLE3.Value;
&Prompt_Edittable3 = "Record." | &Prompt_Editname3;
&TSKPRF_Det_Rec.SetEditTable("%EDITTABLE3", @&Prompt_Edittable3);

&Prompt_Editname4 = &Der_EditRec.EDITTABLE4.Value;
&Prompt_Edittable4 = "Record." | &Prompt_Editname4;
&TSKPRF_Det_Rec.SetEditTable("%EDITTABLE4", @&Prompt_Edittable4);

&Prompt_Editname5 = &Der_EditRec.EDITTABLE5.Value;
&Prompt_Edittable5 = "Record." | &Prompt_Editname5;
&TSKPRF_Det_Rec.SetEditTable("%EDITTABLE5", @&Prompt_Edittable5);

&Prompt_Editname6 = &Der_EditRec.EDITTABLE6.Value;
&Prompt_Edittable6 = "Record." | &Prompt_Editname6;
&TSKPRF_Det_Rec.SetEditTable("%EDITTABLE6", @&Prompt_Edittable6);

&TSKPRF_Det_Rec.ExecuteEdits(%Edit_Required + %Edit_PromptTable);
```

Related Links

ExecuteEdits

IsEditError

EditError

MessageNumber

MessageSetNumber

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Update

Syntax

Update([*KeyRecord*])

Description

The Update method uses the changed fields of the record and their values to build and execute an Update SQL statement, updating the SQL table. If you are updating the key fields of the record, you must supply a record object *KeyRecord* that contains the old values of the key record fields.

Because this method results in a database change, it can only be issued in the following events:

- SavePreChange
- WorkFlow
- SavePostChange

If your application is repeating the same instruction many times, such as doing a million UPDATEs, use the SQL object with the BulkMode property set to True, rather than the record SQL methods.

For every record updated by the Update method, if the set language is not the base language and the record has related language records, the Update method tries to do related language processing.

Note: This method does not update fields marked as system maintained in Application Designer.

Related Links

Understanding SQL Class, "Understanding Data Editing in Related Language Tables and Base Tables" (PeopleTools 8.54: Global Technology)

Parameters

KeyRecord If you're updating the key fields of the record, you must supply the old key field values in the record object *KeyRecord*.

Returns

The result is True on successful completion, False if the record was not found or (when updating the key fields) a duplicate record was found. Any other conditions cause termination.

Example

Suppose that KEYF1 and KEYF2 are the key fields of record definition MYRECORD, and that this record definition also contains the record field definitions MYRF3, MYRF4. The following code updates the MYRECORD record in the database with KEYF1 set to "A", KEYF2 set to "B", setting MYRF3 to "X" and MYRF4 to "Y":

```
Local record &REC;
&REC = CreateRecord(RECORD.MYRECORD);
&REC.KEYF1.Value = "A";
&REC.KEYF2.Value = "B";
&REC.MYRF3.Value = "X";
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
&REC.MYRF4.Value = "Y";
&REC.Update();
```

This code updates the MYRECORD record in the database with KEYF1 of "A" and KEYF2 of "B", setting KEYF2 to "C", MYRF3 to "M" and MYRF4 to "N":

```
Local record &REC1, &REC2;
&REC1 = CreateRecord(RECORD.MYRECORD);
&REC2 = CreateRecord(RECORD.MYRECORD);
&REC1.KEYF1.Value = "A";
&REC1.KEYF2.Value = "B";
&REC2.KEYF1.Value = "A";
&REC2.KEYF2.Value = "C";
&REC2.MYRF3.Value = "M";
&REC2.MYRF4.Value = "N";
&REC2.Update(&REC1);
```

Related Links

Delete

SelectByKey

Insert

Record Class Properties

In this section, we discuss the Record class properties. The properties are listed in alphabetical order.

FieldCount

Description

This property returns the total number of fields contained in the record. This value is a number.

This property is read-only.

Example

```
WinMessage("This record has this many fields : " | &REC.FieldCount);
```

fieldname

Description

If a field name is used as a property, it accesses the field object with that name. This means the following code:

```
&REC.fieldname
```

acts the same as

```
&REC.GetField(FIELD.fieldname);
```

Note: If the field you're accessing has the same name as a record property (such as, Name) you can't use this method for accessing the field. You must use the GetField method.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

If you combine the *fieldname* property with the *recname* property, you obtain the specified field object associated with that record from the row.

```
&ROW.recname.fieldname
```

This property is read-only.

Example

```
&REC.CHARACTER.Enabled = True;
```

IsChanged

Description

This property returns True if any field value on the primary database record of the row has been changed.

Note: This property is for use only with the primary database record. It does not return valid results if used with a work record.

This property is read-only.

Considerations Using IsChanged

This property and the IsChanged row property do not always return identical values.

If a row in a scroll contains multiple records (such as a primary database record and one or more work records), the IsChanged row property returns True if any of the records in the row are changed. The IsChanged record property returns True only if a specific record, namely, the primary database record, is changed.

If a row is deleted from a scroll, only the primary database record has its IsChanged property marked to False (since the row has been deleted.) Any work records in the row still have their IsChanged properties set to True.

Example

```
If &REC.IsChanged Then
    Warning("This Record has been changed");
End-if;
```

IsDeleted

Description

This property is True if the record has been deleted. For a level zero record, it is possible for a record to be deleted without the whole row being deleted. For other levels, this property is the same as the row property IsDeleted.

This property is read-only.

Example

```
&tmp = &REC.IsDeleted;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

IsDeleted

IsEditError

Description

This property is True if an error has been found for any field associated with the record after executing the ExecuteEdits method. This property can be used with the Field class properties EditError (to find out which field is in error), and MessageSetNumber and MessageNumber to find the error message set number and error message number.

The IsEditError property returns True when a field with a Null value is encountered.

This property is read-only.

Example

The following is an example showing how IsEditError, along with the ExecuteEdits method could be used:

```
&REC.ExecuteEdits();
If &REC.IsEditError Then
 For &I = 1 to &REC.FieldCount
   If &REC.GetField(&I).EditError Then
      LOG_ERROR();  /* application specific call */
   End-If;
 End-For;
End-If;
```

Related Links

ExecuteEdits

IsEditError

EditError

MessageNumber

MessageSetNumber

Name

Description

This property returns the name of the record definition of the record as a string.

To access an SQL table name for a record, use the %Table meta-SQL construct.

This property is read-only.

Example

```
WinMessage("The name of this record is : " | &REC.Name);
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

"%Table" (PeopleTools 8.54: PeopleCode Language Reference)

ParentRow

Description

This property returns the row object for the row containing the record. If the record object was created with the CreateRecord built-in function, the value for ParentRow is null because the record object isn't part of a row.

This property is read-only.

Example

```
&ROWOBJECT = &REC.ParentRow;
    &TMP = "The row number of the parent row is " | &ROWOBJECT.RowNumber;
/* note that RowNumber is a property of the row class  */
```

Related Links

"CreateRecord" (PeopleTools 8.54: PeopleCode Language Reference)

RelLangRecName

Description

This property returns the name of the related language record as a string. The value will be a null string ("") if there is no related language record.

Example

```
Local Record &REC;

&REC = GetRecord();
&RECNAME_BASE = &REC.Name;
&RELLANGRECNAME = &REC.RelLangRecName;
SQLExec("select RELLANGRECNAME from PSRECDEFN where RECNAME = :1", &RECNAME_BASE, &⇒
RELLANGRECNAME);
```

SystemIDFieldName

Description

Note: PeopleSoft Mobile Agent is a deprecated product. This mobile property currently exists for backward compatibility only.

This property returns the name of the System ID field as a string. If there is no defined value (the default) the value is a null string ("").

This property accesses the System ID field name value specified on the Use tab of the Record Properties dialog box.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The System ID field is used to create a unique way to identify the record for mobile synchronization purposes. This property is used exclusively for mobile applications. This property is not available for subrecords.

This property is read-only.

Example

```
Local Record &REC;

&REC = GetRecord();
&sSystemID = &REC.SystemIDFieldName;
```

Related Links

TimeStampFieldName

"Setting Record Properties" (PeopleTools 8.54: Application Designer Developer's Guide)

TimeStampFieldName

Description

Note: PeopleSoft Mobile Agent is a deprecated product. This mobile property currently exists for backward compatibility only.

This property returns the name of the Timestamp field as a string. If there is no defined value (the default) the value is a null string ("").

This property accesses the Timestamp field name value specified on the Use tab of the Record Properties dialog box.

The Timestamp field is used to specify a field that is automatically updated with the date and time when there's a change to the record. This property is used exclusively for mobile applications.

This property is not available for subrecords. This property is read-only.

Example

```
Local Record &REC;

&REC = GetRecord();
&sTimeStamp = &REC.TimeStampFieldName;
```

Related Links

SystemIDFieldName

"Setting Record Properties" (PeopleTools 8.54: Application Designer Developer's Guide)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Chapter 40

Row Class

Understanding Row Class

A *row* object, instantiated from the Row class, is a single row of data that consists of one to *n* records of data. A single row in a component scroll is a row.

A row object is always associated with a rowset object, that is, you cannot instantiate a row object without first either explicitly or implicitly instantiating a rowset object.

A row may have one to *n* child rowsets. For example, a row in a level two scroll may have *n* level three child rowsets.

CopyTo and GetRecord are two commonly use methods for this class. Visible and IsChanged are two commonly used properties for this class.

The row class is one of the data buffer access classes.

If a rowset object is instantiated using the CreateRowset function, the rowset object that's instantiated is a standalone rowset. Delete and insert activity on these types of rowsets aren't automatically applied at save time. Use standalone rowsets for work records.

Related Links

"Understanding Data Buffer Access" (PeopleTools 8.54: PeopleCode Developer's Guide)

"Using Standalone Rowsets" (PeopleTools 8.54: PeopleCode Developer's Guide)

Shortcut Considerations

The default method for the row class is GetRecord. This means you can specify just a record name to access a record on the row. For example, the following two lines of code are equivalent:

```
&Count = &MyRow.EMPL_CHECKLIST.FieldCount;
```

```
&Count = &MyRow.GetRecord(RECORD.EMPL_CHECKLIST).FieldCount;
```

In addition, the row class has a method *scrollname*. This enables you to access a specific child rowset *and* row within that rowset. This isn't a default method: you're not accessing a child object, but rather, something within that object. For example, the following two lines of code are equivalent:

```
&ChildRow = &MyRow.EMPL_CHKLST_ITM(&I);
```

```
&ChildRow = &MyRow.GetRowset(SCROLL.EMPL_CHKLST_ITM).GetRow(&I);
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Data Type of a Row Object

Row objects are declared as type Row. For example,

```
Local Row &MYROW;
```

Scope of a Row Object

A Row can only be instantiated from PeopleCode.

This object can be used anywhere you have PeopleCode, that is, in an application class, Application Engine PeopleCode, Component Interface PeopleCode, and so on.

Row Class Built-in Function

"GetRow" (PeopleTools 8.54: PeopleCode Language Reference)

Row Class Methods

In this section, we discuss each Row class method. The methods are discussed in alphabetical order.

CopyTo

Syntax

CopyTo(*row*)

Description

The CopyTo method copies *from*the row executing the method *to*the specified target row, copying *like-named* record fields and subscrolls at corresponding levels. The target row object must be from a "related" rowset, that is, built from the same records, but it can be under a different parent at higher levels.

This method copies *all* the records from the row object executing the method to the target row, not just the primary data record associated with the rowset.

Parameters

row	Specify a target row. This must be a row object, not a row number.

Returns

None

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

The following example copies rows from a child rowset (DERIVED_HR) to the current rows.

```
Local Row &ROW;
Local Rowset &RS1;

&RS1 = GetRowset();
For &I = 1 to &RS1.ActiveRowCount
   &ROW = GetRowset(SCROLL.DERIVED_HR).GetRow(&I);
   &ROW.CopyTo(GetRow(&I));
End-For;
```

Related Links

ParentRowset

CopyFieldsTo

CopyChangedFieldsTo

GetNextEffRow

Syntax

GetNextEffRow()

Description

The GetNextEffRow method finds the row, in the same rowset as the row executing the method, that has the next effective date (when compared to the row executing the method.)

Parameters

None

Returns

A row object. If there is no row with a later effective date, this method returns a null object.

Example

```
&ROW2 = &ROW.GetNextEff();

If &ROW2 <> NULL Then
   &TMP = &ROW2.RowNumber;
   /* other processing */
Else
   /* no effective dated row - do error processing */
End-if;
```

Related Links

GetPriorEffRow

GetCurrEffRow

DeleteEnabled

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GetPriorEffRow

Syntax

```
GetPriorEffRow()
```

Description

The GetPriorEffRow method finds the row, from the same rowset as the row executing the method, that has the prior effective date to the row executing the method.

Parameters

None

Returns

A row object. If there is no row with a prior effective date, this method returns a null object.

Example

```
&TMP = &ROW.GetPriorEffrow().RowNumber;
```

Related Links

GetNextEffRow
GetCurrEffRow
DeleteEnabled

GetRecord

Syntax

```
GetRecord({n | RECORD.recname})
```

Description

The GetRecord method creates a record object that references the specified record within the current row object. This is the *default method* for a row object. This means that any row object, followed by a parameter list, acts as if GetRecord is specified.

Parameters

n* | RECORD.*recname

Specify a record to be used for instantiating the record object. You can specify either *n* or RECORD.*recname*, Specifying *n* creates a record object for the *nth* record in the row. This might be used if writing code that needs to examine all records in a row without being aware of the record name. Specifying RECORD.*recname* creates a record object for the record *recname*.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Note: There is no way to predict the order the records will be accessed. Use the *n* option only if the order in which the records are processed doesn't matter.

Returns

A record object.

Example

The following example gets a record, then assigns the name of the record to the variable &TMP:

```
&REC = &ROW.GetRecord(RECORD.QEPC_LEVEL1_REC);

&TMP = &REC.NAME;  /* note that NAME is a property of the record class */
```

Because GetRecord is the default method for a row, the following code is identical to the previous:

```
&REC = &ROW.QEPC_LEVEL1_REC;

&TMP = &REC.NAME;
```

The following example loops through all the records for a row:

```
Local rowset &LEVEL1;
Local row &ROW;
Local record &REC;

&LEVEL1 = GetRowset(SCROLL.EMPL_CHECKLIST);
For &I = 1 to &LEVEL1.ActiveRowCount
   &ROW = &LEVEL1.GetRow(&I);
   For &J = 1 to &ROW.RecordCount
      &REC = &ROW.GetRecord(&J);
         /* do processing */
   End-For;
End-For;
```

The following function takes a rowset and a record, passed in from another program. GetRecord won't take a variable for the record, however, using the @ symbol you can convert the string to a component record name.

```
Function Get_My_Row(&PASSED_ROWSET, &PASSED_RECORD)

   For &ROWSET_ROW = 1 To &PASSED_ROWSET.RowCount
      &UNDERLYINGREC = "RECORD." | &PASSED_ROWSET.DBRecordName;
      &ROW_RECORD = &PASSED_ROWSET.GetRow(&ROWSET_ROW).GetRecord(@&UNDERLYINGREC);

      /* Do other processing */

   End-For;

End-Function;
```

Related Links

"GetRecord" (PeopleTools 8.54: PeopleCode Language Reference)

"CreateRecord" (PeopleTools 8.54: PeopleCode Language Reference)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GetRowset

Syntax

```
GetRowset({n | SCROLL.scrollname})
```

Description

The GetRowset method creates a rowset object that references a child rowset of the current row. *scrollname* must specify the primary record for the child rowset.

Parameters

n* | SCROLL.*scrollname	Specify a rowset to be used for instantiating the rowset object. You can specify either *n* or SCROLL.*scrollname.* Specifying *n* creates a rowset object for the *nth* child rowset in the row. This might be used if you are writing code that examines all rowsets in a row without being aware of the name. Specifying SCROLL.*scrollname* creates a rowset object for the record *scrollname*. *scrollname* must specify the primary record for the child rowset.

Note: There is no way to predict the order the rowsets will be accessed. Use the *n* option only if the order in which the rowsets are processed doesn't matter.

Returns

A rowset object.

Example

```
&CHILDROWSET = &ROW.GetRowset(SCROLL.QEPC_LEVEL1_REC);
```

Related Links

scrollname

"GetRowset" (PeopleTools 8.54: PeopleCode Language Reference)

scrollname

Syntax

```
scrollname(n)
```

Description

If *scrollname* is used as a method name for a row, it is used to select a child rowset and a row within that rowset.

```
&ROW.scrollname(n)
```

acts the same as

```
&ROW.GetRowset(SCROLL.scrollname).GetRow(n)
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

n	Must be a valid row number for the selected child rowset.

Returns

A row object.

Example

```
&SUBROW1 = &ROW.QEPC_LEVEL1_REC(1);
```

Related Links

"GetRowset" (PeopleTools 8.54: PeopleCode Language Reference)

Row Class Properties

In this section, we discuss the Row class properties. The properties are discussed in alphabetical order.

ChildCount

Description

This property returns the number of child rowsets of the row. It is defined by the "structure" of the scroll, so it is the same for all rows of the rowset.

It might be used, in conjunction with the GetRowset method, to write code that examines all child rowsets.

This property is read-only.

Example

```
For &I = 1 to &ROW.ChildCount
   &ROWSET = &ROW.GetRowset(&I);
      /* do processing */
End-For;
```

DeleteEnabled

Description

This property determines whether a row can be deleted (the equivalent of the user pressing ALT+8 and ENTER). This property takes a Boolean value.

Note: This property controls only whether an end-user can delete a row. Rows can still be deleted using PeopleCode.

This property is typically used to prevent deletion of an individual row that the other properties controlling deletion would allow to be deleted. The following table goes through the Boolean logic.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Will delete be allowed by user?	*Others enable*	*Others disable*
DeleteEnabled = True	Yes	No
DeleteEnabled = False	No	No

The initial value of this property is True.

Note: If No Row Delete is selected in Application Designer, setting the DeleteEnabled row property to True will *not* override this value. If you want to control whether a row can be deleted at runtime, you should *not* select No Row Delete at design time. Likewise, if the DeleteEnabled Rowset property is False, setting the DeleteEnabled Row property to True will *not* override the rowset property. If you want to control whether an individual row can be deleted at runtime, you should not set the DeleteEnabled rowset property to False.

For consistency, PeopleSoft recommends that either all rows at a level should disable deletions, or they should all allow deletions.

For rows created with non-Component Processor data (such as message rowsets, Application Engine rowsets, and so on) this property has no effect.

Note: Don't use this property with rows from rowsets created using CreateRowset. Rowsets created using the CreateRowset function are standalone rowsets, not tied to the database, so there are no database updates when they are manipulated. Delete and insert activity on these types of rowsets aren't automatically applied at save time.

This property is read-write.

Related Links

DeleteEnabled "Using Scroll Areas and Scroll Bars" (PeopleTools 8.54: Application Designer Developer's Guide) "Using Standalone Rowsets" (PeopleTools 8.54: PeopleCode Developer’s Guide)

IsChanged

Description

This property returns True if any field value on the primary database record of the row has been changed.

Note: Use this property only with the primary database record. It doesn't return valid results if used with a work record. This property returns True only if the existing row object has a field that has changed. If a field in a lower level rowset has changed, this property returns False.

This property is read-only.

Considerations Using IsChanged

This property and the IsChanged record property do *not*always return identical values.

If a row in a scroll contains multiple records (such as a primary database record and one or more work records), the IsChanged row property returns True if *any* of the records in the row are changed. The

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

IsChanged record property returns True *only* if a specific record, namely, the primary database record, is changed.

If a row is deleted from a scroll, *only*the primary database record has its IsChanged property marked to False (since the row has been deleted.) Any work records in the row *still*have their IsChanged properties set to True.

Example

```
&tmp =  &ROW.IsChanged;
if &tmp = True then
   Warning("A Field on this row has been changed");
End-If;
```

IsDeleted

Description

This property returns True if the row has been deleted.

This property is read-only.

Note: This property also returns True if the row is new and hasn't been changed.

Example

```
&tmp = &ROW.IsDeleted;
```

IsEditError

Description

This property is True if an error has been found for any field associated with any record in the current row or on any row in any child rowset of the current row after executing the ExecuteEdits method. This property can be used with the Field class properties EditError (to find out which field is in error), and MessageSetNumber and MessageNumber to find the error message set number and error message number.

This property is read-only.

Example

The following is an example showing how IsEditError, along with the ExecuteEdits method could be used:

```
&MSG.ExecuteEdits();
If &MSG.IsEditError Then
&RS = &MSG.GetRowset();
   For &J = 1 to &RS.RowCount
      &ROW = &RS.GetRow(&J);
         If &ROW.IsEditError Then
            &REC = &ROW.GetRecord();
            For &I = 1 to &REC.FieldCount
               If &REC.GetField(&I).EditError Then
                  LOG_ERROR();  /* application specific call */
               End-If;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
            End-For;
      End-If;
   End-For;
End-If;
```

Related Links

ExecuteEdits
IsEditError
EditError
MessageNumber
MessageSetNumber

IsNew

Description

This property is True if the row is a new (inserted) row.

This property is read-only.

Example

```
&tmp = &ROW.IsNew;
```

ParentRowset

Description

This property returns a rowset object referencing the rowset containing the row.

This property is read-only.

Example

```
&tmp = &ROW.ParentRowset.RowCount;

/* note that rowcount is a property of the Rowset class */
```

recname

Description

If a record name is used as a property, it accesses the record object with that name. This means the following code:

```
&ROW.somerecname
```

acts the same as

```
&ROW.GetRecord(RECORD.somerecname);
```

This property is read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

```
&REC = &ROW.QEPC_LEVEL1_REC;
```

RecordCount

Description

This property returns the number of records in the row. It is defined by the "structure" of the scroll, so it is the same for all rows of the rowset.

This property might be used in conjunction with the GetRecord method to write code that examines all records in some way.

This property is read-only.

Example

```
For &I = 1 to &ROW.RecordCount
   &REC = &ROW.GetRecord(&I);
   /* do processing */
End-For;
```

RowNumber

Description

This property returns the row number (starting from 1) of the row within its rowset.

This property is read-only.

Example

The following returns the row number of the current effective-date row.

```
&NUMBER = GetRowset(SCROLL.MYRECORD).GetCurrEffRow().RowNumber;
```

Selected

Description

This property returns True if the row is part of a grid and has been selected either by the user or programmatically.

This property is meaningful in PIA only if the grid or scroll area attribute has been set to provide the selection control. In this case, the property reflects the state of the checkbox or radio button used for selection.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

The following example determines how many rows in a grid are selected.

```
Function Count_Child_Assets(&GRIDLEVEL1 As Rowset, &NUM_CHILDREN)
   REM *** How many child assets are selected?                  *;
   &GRIDLEVEL1 = GetRowset(SCROLL.PARENT_CHILD_VW);
   For &CHILDROW_COUNT = 1 To &GRIDLEVEL1.ActiveRowCount
      If &GRIDLEVEL1.GetRow(&CHILDROW_COUNT).Selected = True Then
         &NUM_CHILDREN = &NUM_CHILDREN + 1;
      End-If;
   End-For;
End-Function;
```

Style

Description

This property returns the name of the style class if one has been set for the row. You can also use this property to change the style of a row. This property takes a string value.

Note: This property *overrides* only the existing style. It doesn't *change* it. The next time the page is accessed the original style is used.

The PSSTYLE style sheet does *not* contain a default style class for a row. The Style property for all rows is initially NULL (that is, two quotation marks with no space between them ("")). The row assumes the style of the grid alternate row style. Fields in the row assume field styles if set.

Setting the property for a row overrides the grid alternate row style and any page field styles (field styles that were set in Application Designer). It does *not* override any field styles set (using the Field class Style property) for fields in the row.

Setting the Style property back to NULL (that is, two quotation marks with no space between them ("")) turns off the override.

Note: This property is *not* valid for Windows Client applications.

Example

```
&Scroll = GetLevel0().GetRow(1).GetRowset(Scroll.IC_PC_STYLE_2);

&row_class = &Scroll.GetRow(&row);

&row_class.Style = &style;
```

Related Links

Style

"Understanding Field Definitions" (PeopleTools 8.54: Application Designer Developer's Guide)

Visible

Description

If this property is True, the row is visible if displayed on the current page. This property can be set False to hide the row.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

When Visible is set to False to hide a row, the row moves to the end of the rowset. This means that the row number of the row being hidden, and any subsequent rows, *changes* as a result of hiding a row. If the row is later made visible again, it is *not* moved back to its original position, but remains at the end of the rowset. It is just moved to the start of all the other hidden rows.

For example, if there are 4 rows in a rowset and row 2 is hidden (that is, Visible = False), that row now becomes row 4. In order to make that row visible again, row 4 must be set to Visible = True. Alternatively, you can use a row object reference: this remains valid even though the row number of the row may have been changed.

Note: If you use the Sort method on a rowset with hidden rows, the hidden rows aren't sorted. Only visible rows are sorted.

You cannot hide rows in the current context of the executing program. This means Visible cannot hide the row containing the executing program, or in a child rowset and be executed against its parent rowset. Place your PeopleCode in a parent rowset and execute it against a child rowset.

Example

```
&ROW.Visible = False;
```

The following code uses the Visible property to determine if a row is visible or not before updating the value of the row.

```
&ROWSET = GetRowset(SCROLL.LD_SHP_INV_VW)

For &I = 1 To &ROWSET.ActiveRowCount
   If &ROWSET(&I).Visible Then
      ITEM_SELECTED.value = "N";
   End-If;
End-For;
```

The following code starts with the last row and works forward to the first. If any changes are made they don't impact the position of rows that still have to be processed.

```
For &I = &ACTIVE_STREAMS to 1 Step -1
   &Row = &STREAM_ROWSET(&I);
   If &Row.QS_STREAM8.STREAM_ROOT_ID.Value <> &STREAM_ROOT_ID Then
      &Row.Visible = False;
   End-if;
End-For;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Chapter 41

Rowset Class

Understanding Rowset Class

A *rowset* object, instantiated from a Rowset class, is a collection of rows associated with buffer data. A component scroll is a rowset. You can also have a level zero rowset.

If a rowset object is instantiated using GetRowset (either the function or one of the methods) the rowset object that is instantiated is populated with data according to the context in which it was instantiated.

If a rowset object is instantiated using the CreateRowset function, the rowset object that's instantiated is a standalone rowset. Any records and field references created by this function are initialized to null values, that is, they do *not* contain any data. You can populate this rowset object using the CopyTo, Fill, or FillAppend methods.

Default processing isn't performed on a standalone rowset. In addition, a standalone rowset isn't tied to the Component Processor. When you fill it with data, no PeopleCode runs (for example, RowInsert, FieldDefault, and so on.) Delete and insert activity on these types of rowsets aren't automatically applied at save time. Use standalone rowsets for work records.

You might use a rowset object and the ActiveRowCount property to iterate over all the rows of the rowset, or to access a specific row (using the GetRow method) or to find the name of the primary record associated with the scroll (the DBName property).

The Rowset class is one of the data buffer access classes.

Related Links

"Using Standalone Rowsets" (PeopleTools 8.54: PeopleCode Developer's Guide)

"Understanding Data Buffer Access" (PeopleTools 8.54: PeopleCode Developer's Guide)

Shortcut Considerations

The default method for the Rowset class is GetRow. This means you can specify just a row number, and not use the GetRow method. For example, the following two lines of code are equivalent:

```
&MyRow = GetRowset()(5);
```

```
&MyRow = GetRowset().GetRow(5);
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Data Type of a Rowset Object

Rowset objects are declared as type Rowset. For example,

```
Local Rowset &MYROWSET;
```

Scope of a Rowset Object

A Rowset can be instantiated from PeopleCode or using Java.

This object can be used anywhere you have PeopleCode, that is, in an Application Class, record field PeopleCode, and so on.

You can't pass a rowset object in as part of a Component Interface user-defined method. (Rowsets aren't common data structures outside of a PeopleSoft system.) However, within a user-defined method for a Component Interface you can use rowset objects.

In an Application Engine program, a rowset object is the equivalent of a record object that contains one row and a single record, that is, the State Record. PeopleSoft suggests using the Record object instead of a rowset object to obtain access to the State Record.

Messages have the same structure as rowsets, that is, hierarchical data structures composed of rows, records, and fields.

File objects can have the same structure as rowsets, that is, hierarchical data structures composed of rows, records, and fields.

Related Links

"Using Standalone Rowsets" (PeopleTools 8.54: PeopleCode Developer's Guide)

Rowset Class Built-In Functions

"CreateRowset" (PeopleTools 8.54: PeopleCode Language Reference)

"CreateRowset" (PeopleTools 8.54: PeopleCode Language Reference)

"GetRowset" (PeopleTools 8.54: PeopleCode Language Reference)

Rowset Class Methods

In this section, we discuss the Rowset class methods. The methods are discussed in alphabetical order.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ClearDeletesChanges

Syntax

ClearDeletesChanges()

Description

Use the ClearDeletesChanges method to clear deleted rows and changed from a standalone rowset.

Note: This method works only with standalone rowsets, that is, rowsets created using the CreateRowset function.

This method differs from Flush in a number of ways:

- it does not remove *all* rows from the rowset, only deleted rows
- it only applies to standalone rowsets

This method first clears the deleted rows, that is, all rows that have been deleted using DeleteRow are removed from the rowset and their associated buffers are freed.

This method then clears changed rows. That means any changes done on a row (such as field values changed) or newly inserted rows are now propagated into their original state and the changed buffers, if any, are freed.

After executing this method on a standalone rowset, any row that was previously new or changed no longer has that state. The IsNew and IsChanged properties of a row return false.

This method does *not* do any database updates.

How would you use this method? Suppose you use a standalone rowset to track changes you need to make to some business process or object. After doing the appropriate database updates to reflect changes recorded in the rowset (that is, inserts or deletes or changes), you call this method to clean up the rowset in preparation for further processing. Without this method, newly inserted rows and changed rows preserve their IsNew and IsChanged status indefinitely, complicating program logic and potentially leading to duplicate inserts or deletes.

Parameters

None.

Returns

None.

Example

```
REM +-----------------------------------------------------+;
REM | Function to Update the DB for a Standalone Rowset|;
REM +-----------------------------------------------------+;
Function ProcessDatabaseUpdateforRowset(&rsIn As Rowset)

   For &i = 1 To &rsIn.RowCount

      &rwTMP = &rsIn.GetRow(&i);
      If &rwIn.IsDeleted And
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
            Not &rwIn.IsNew Then
         &rTMP = &rwIn.GetRecord(1);
         &rTMP.Delete();
      End-If;

      If &rwTMP.IsNew And
            &rwTMP.IsChanged And
            Not &rwTMP.IsDeleted Then

         &rTMP = &rwTMP.GetRecord(1);
         &rTMP.Insert()
      End-If;

      If Not &rwTMP.IsNew And
            &rwTMP.IsChanged And
            Not &rwTMP.IsDeleted Then

         &rTMP = &rwTMP.GetRecord(1);
         &rTMP.Update();
      End-If;

   End-For;

   REM +-----------------------------------------------+;
   REM | Now we need to reset the Rowset flags and     |;
   REM | remove deleted rows                           |;
   REM +-----------------------------------------------+;
   &rsIn.ClearDeletesChanges();

End-Function;
```

Related Links

Flush

FlushRow

IsChanged

IsNew

CopyTo

Syntax

CopyTo(*&DestRowset* [, *record_list*])

Where *record_list* is a list of record names in the form:

[**RECORD**.*source_recname1*, **RECORD**.*target_recname1*

[, **RECORD**.*source_recname2*, **RECORD**.*target_recname2*]]. . .

Description

The CopyTo method copies *from* the rowset executing the method *to* the specified destination rowset, copying *like-named* record fields and subscrolls at corresponding levels.

The CopyTo method uses the current data in the rowset. This might be different from the original data values if the rowset was retrieved from the database and values in it have been changed either by an end-user or a PeopleCode program

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

If pairs of source and destination record names are given, these are used to pair up the records and subscrolls *before* checking for like-named record fields. Then, after copying the named records pairs, this method copies *all* identically named records.

Note: This method does not work for Application Engine state records. If you don't specify *record_list*, *both* the record name *and* the field name have to match exactly for data to be copied from one record field to another. If you specify *record_list*, after the records have been paired up, the field names have to match before any data is copied.

If the rowset you are copying *from* has the field level EditError, as well as the MessageNumber and MessageSetNumber properties set, these values are copied to the rowset you are copying to. For example, suppose you had an application message that had errors. Using the GetSubContractInstance function, these errors would be copied into the message object. From there, you could instantiate a message rowset, copy the message rowset into a work rowset, and use the work rowset to populate Component buffers. (After the field properties are set, the Record, Row, and Rowset properties IsEditError also get set.)

Parameters

&DestRowset	Specify the rowset to be copied to. This rowset object must have already been instantiated.
SourceRecname	Specify a record to be copied from, in the rowset object being copied from.
DestRecname	Specify a record to be copied to, in the rowset object to be copied to.

Returns

None.

Example

If you set one rowset equal to another, you haven't made a copy of the rowset. Instead, you have two variables pointing to the *same* data.

To make a clone of an existing rowset, that is, to make two distinct copies, you can do the following:

```
&RS2 = CreateRowset(&RS);
&RS.CopyTo(&RS2);
```

The following example copies data from one rowset object to another. Because no like-named records exist between the two rowsets, the record names are specified. Only the like-named fields are copied from one rowset to the other:

```
Local Rowset &RS1, &RS2;
Local String &EMPLID;

&RS1 = CreateRowset(RECORD.PERSONAL_DATA);
&RS2 = CreateRowset(RECORD.PER_VENDOR_DATA);
&EMPLID = "8001";
&RS1.Fill("WHERE EMPLID =: 1", &EMPLID);
&RS1.CopyTo(&RS2, RECORD.PERSONAL_DATA, RECORD.PER_VENDOR_DATA);
```

The following example copies data from a message into the Component buffers, then calls the page (using TransferPage) to redraw the page. You could do this to fill a page with message data that is in error, so

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

that an end-user can make corrections to the message data. &WRK_ROWSET0 is the level zero rowset and &WRK_ROWSET1 is where the data is copied to.

```
/* Get the Message */
&MSG = GetSubContractInstance(&PUBID, &PUBNODE, &CHNLNAME, &MSGNAME, &SUBNAME);

/* Get the Message Rowset */
&MSG_ROWSET = &MSG.GetRowset();

/* Get Level 0 */
&WRK_ROWSET0 = GetLevel0();

/* Create Work rowset */
&WRK_ROWSET1 = GetLevel0()(1).GetRowset(SCROLL.EN_REVISION_TMP);

/* Populate Work Rowset */
&MSG_ROWSET.CopyTo(&WRK_ROWSET1, RECORD.EN_REVISION, RECORD.EN_REVISION_TMP);

SetNextPage("EN_REVISION_MSG");

TransferPage();
```

Related Links

CopyTo

"CreateRowset" (PeopleTools 8.54: PeopleCode Language Reference)

"Assigning Objects" (PeopleTools 8.54: PeopleCode Developer's Guide)

DeleteRow

Syntax

DeleteRow(*n*)

Description

The DeleteRow method deletes the row in the rowset identified by the parameter.

If the program is being run from a component against Component buffer data, a RowDelete PeopleCode event also fires, followed by the events that normally follow a RowDelete, as if the user had manually pressed ALT+8 and ENTER.

This method initially marks the row as needing to be deleted. At save time the row is actually deleted from the database and cleared from the buffer. When the row is marked as deleted, it is ignored by other methods, such as GetCurrEffRow, Sort, and so on.

DeleteRow cannot be executed from the same rowset where the deletion takes place, or from a child rowset against a parent. Place your PeopleCode in a parent rowset and execute it against a child rowset.

When DeleteRow is used in a loop, you have to process rows from high to low to achieve the correct results, that is, you must delete from the bottom up rather than from the top down. This is necessary because the rows are renumbered after they are deleted (if you delete row one, row two becomes row one).

Note: If you use DeleteRow on a rowset created using the CreateRowset function, the row isn't automatically deleted in the database when the page is saved. Rowsets created using the CreateRowset function are standalone rowsets, not tied to the database, so there are no database updates when they are manipulated. Delete and insert activity on these types of rowsets aren't automatically applied at save time.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

n	An integer identifying a row within the rowset object. This must be >= 1 and <= the number of active rows in the rowset (see ActiveRowCount).

Returns

An optional Boolean value: True if row is deleted, False otherwise.

Example

In the following example DeleteRow is used in a For loop. The example checks a value in each row, then conditionally deletes the row. Note the syntax of the For loop, including the use of the -1 in the Step clause to loop from the highest to lowest values. This ensures that the renumbering of the rows do not affect the loop.

```
For &I = &RS2.ActiveRowCount To 1 Step -1
   If None(&CHECK_SEQ) Then
      &RS2.DeleteRow(&I);
   End-If;
End-For;
```

Related Links

Flush

FlushRow

InsertRow

Insert

"Using Standalone Rowsets" (PeopleTools 8.54: PeopleCode Developer's Guide)

Fill

Syntax

Fill([*wherestring* [, *bindvalue*] . . .])

Description

The Fill method flushes the rowset then reads records from the database into successive rows. The records are read from the database tables corresponding to the primary database record of the scroll into that record. The records are selected by the optional *wherestring* SQL clause, in which the optional *bindvalues* are substituted, using the usual bind placeholders *(:n)*.

In general, use this method only with rowsets that were created using the CreateRowset function.

Note: Because Flush always leaves one row in the scroll, there will be one row in the scroll even if you don't read any records.

The actual number of records read into the rowset is an optional return of this method.

Note: This method does not work with Application Engine state records. Also, you cannot use this method in dynamic views.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

When this method executes, unlike the Select method, it does *not* cause any associated PeopleCode to run as part of reading data into the rowset.

Note: Fill reads only the primary database record. It does not read any related records, nor any subordinate rowset records.

For every record read with the Fill method, if the set language is not the base language and the record has related language records, the Fill method tries to read the related language record and does related language processing.

The Fill method uses a correlation ID of FILL for the table it reads. You must use the correlation ID if you want to refer to the rowset table name as part of the *wherestring*. You receive a runtime error if you use the table name as a column prefix instead of the correlation ID.

Sorting Considerations

Rows come unsorted from the database when using Fill. This is not a problem for SQL server, however, it can be a problem for DB2 UDB for OS/390 and z/OS and Oracle.

See Sort.

Parameters

wherestring	Specify a SQL WHERE clause to use for selecting records to fill the rowset. This can be a string or a SQL definition.
bindvalue	Specify optional bind variables to be used with the WHERE clause.

Returns

The number of records read into the rowset.

Example

The following example reads all of the QA_MYRECORD records into a rowset, and returns the number of rows read:

```
&RS = CreateRowset(RECORD.QA_MYRECORD);
&NUM_READ = &RS.Fill();
```

The following example reads all of the QA_MYRECORD records that have a MYRECORD field equal to the value of &UVAL into a rowset, and returns the number of rows read:

```
&NUM_READ = &RS.Fill("where MYRECORD = :1", &UVAL);
```

To re-use a WHERE clause for the *wherestring* you can use the SQL repository, and a SQL object.

```
&NUM_READ = &RS.Fill(SQL.MYWHERE, &UVAL);
```

The following example gets all the SET_CNTRL_REC rows related to the row on the page, then updates SETID with the value from the page. Fill is used with a rowset that was created from a message that was just created, that is, a rowset that was unpopulated.

```
If FieldChanged(SETID) Then
   &MSG = CreateMessage(OPERATION.SET_CNTRL_REC);
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
   &MSG_ROWSET = &MSG.GetRowset();
   &MSG_ROWSET.Fill("where SETCNTRLVALUE =:1 and REC_GROUP_ID =:2", SETCNTRLVALUE, ⇒
REC_GROUP_ID);

For &I = 1 To &MSG_ROWSET.ActiveRowCount
   &MSG_ROWSET.GetRow(&I).SET_CNTRL_REC.SETID.Value = SETID;
   &MSG_ROWSET.GetRow(&I).PSCAMA.AUDIT_ACTN.Value = "C";
End-For;

&MSG.Publish();

End-If;
```

When using the Fill method, the IsChanged property of each field in a part rowset is not set to true. Because the fields appear to be unchanged, this can create a problem for publication of data from Message rowsets. A technique to avoid this problem is to create a second rowset and use the CopyTo method to copy the changes to the Message rowset as shown in the following example:

```
&a = CreateMessage(Operation.MY_ASYNC);
&rs = &a.GetPartRowset(1);

&trs = CreateRowset(Record.PSPMAGENT);
&trs.Fill("where PM_AGENTID >= 12345");

&trs.CopyTo(&rs);
%IntBroker.Publish(&a);
```

The following example uses a correlation ID for the table in the Fill SELECT, to enable the use of correlated subqueries in the WHERE clause, such as the usual effective-date subquery:

```
&RSOWNER_NAME = CreateRowset(RECORD.PERSONAL_D00);
&RSOWNER_NAME.Fill("where SETID=:1 AND EMPLID=:2 AND %EffDtCheck(PERSONAL_D00,FILL,⇒
:3)", &SETID, &EMPLID, &EFFDT);
```

The Fill method implicitly uses Fill as an alias for the Rowset record. This is helpful for complex Fill *where* clauses with subqueries.

```
&oprclasscountries = CreateRowset(Record.SCRTY_TBL_GBL);

&oprclasscountries.Fill("WHERE FILL.OPRCLASS = :1 AND NOT EXISTS (SELECT 'X' FROM P⇒
S_SCRTY_SEC_GBL GBL2 WHERE GBL2.OPRCLASS = FILL.OPRCLASS AND GBL2.COUNTRY = FILL.CO⇒
UNTRY AND GBL2.PNLNAME = :2)", &OPRCLASS, %Component);
```

In the following example, the necessary key field values are loaded into a rowset, then the following function is called, and the values are used as part of the Fill method.

```
Function FillRS2();

   Local SQL &MySql;
   Local string &MySqlString;
   Local Record &ElemDefnRec;
   Local string &ElemDefnRecName, &fldname;
   Local Rowset &CompRec2RS;

   /* Build the record object that is used for building the SQL and executing the s⇒
elect */
   &ElemDefnRec = CreateRecord(@("Record." | &pkgRecName));

   /* Initialize the SQL string */
   &MySqlString = "%SelectByKey(:1 A)";

   /* Create a SQL to select a rows based on the key fields. */
   For &i = 1 To &ElemDefnRec.FieldCount
      If &ElemDefnRec.GetField(&i).IsKey Then
         &fldname = &ElemDefnRec.GetField(&i).Name;
         &ElemDefnRec.GetField(&i).Value = &CompRec2RS.GetRow(1).GetRecord(@("Recor⇒
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
d." | &pkgRecName)).GetField(@("Field." | &fldname)).Value;
      End-If;
   End-For;

   /* Create the SQL and execute the select */
   &MySql = CreateSQL(&MySqlString);
   &MySql.Execute(&ElemDefnRec);

   /* Copy each selected row into the rowset */
   While &MySql.Fetch(&ElemDefnRec)
      &ElemDefnRec.CopyFieldsTo(&CompRec2RS(&CompRec2RS.ActiveRowCount).GetRecord(1⇒
));
   End-While;

End-Function;
```

Related Links

CopyTo

Select

FillAppend

Understanding SQL Class

"CreateRowset" (PeopleTools 8.54: PeopleCode Language Reference)

"Understanding Related Language Tables" (PeopleTools 8.54: Global Technology)

FillAppend

Syntax

FillAppend([*wherestring* [, *bindvalue*] . . .])

Description

The FillAppend method reads records from the database into successive rows of the rowset starting *after* the last row that exists in the rowset. Unlike Fill, it doesn't first flush the rowset.

Note: FillAppend appends rows after the last *active* row in the rowset. If you have deleted rows in the rowset, they will still be the last rows.

When a rowset is selected into, any autoselected child rowsets are also read. The child rowsets are read using a where clause that filters the rows according to the where clause used for the parent rowset, using a subselect.

When a rowset is created using CreateRowset, it contains one empty row. If the rowset hasn't been filled with data, FillAppend fills that row also (so you don't have an empty row at the start of your rowset.)

The records are read from the database tables corresponding to the primary database record of the scroll into that record. The records are selected by the optional *wherestring* SQL clause, in which the optional *bindvalues* are substituted, using the usual bind placeholders (*:n*).

In general, use this method only with rowsets that were created using the CreateRowset function.

The actual number of records read into the rowset is an optional return of this method.

Note: This method does not work with Application Engine state records. Also, you cannot use this method in dynamic views.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

When this method executes, unlike the Select method, it does *not* cause any associated PeopleCode to run as part of reading data into the rowset.

Note: FillAppend reads only the primary database record. It does not read any related records, nor any subordinate rowset records.

For every record read with the FillAppend method, if the set language is not the base language and the record has related language records, the FillAppend method tries to read the related language record and does related language processing.

The FillAppend method uses a correlation ID of FILLAPPEND for the table it reads. You must use the correlation ID if you want to refer to the rowset table name as part of the *wherestring.* You receive a runtime error if you use the table name as a column prefix instead of the correlation ID.

Parameters

wherestring	Specify a SQL WHERE clause to use for selecting records to fill the rowset. This can be a string or a SQL definition.
bindvalue	Specify optional bind variables to be used with the WHERE clause.

Returns

The number of records read into the rowset.

Example

The following example reads all of the QA_MYRECORD records that have a MYRECORD field equal to the value of &UVAL into a rowset, and returns the number of rows read:

```
&NUM_READ = &RS.FillAppend("where MYRECORD = :1", &UVAL);
```

To re-use a WHERE clause for the *wherestring* you can use the SQL repository, and a SQL object.

```
&NUM_READ = &RS.FillAppend(SQL.MYWHERE, &UVAL);
```

Related Links

CopyTo
Select
Fill
Understanding SQL Class
"CreateRowset" (PeopleTools 8.54: PeopleCode Language Reference)
"Understanding Related Language Tables" (PeopleTools 8.54: Global Technology)

Flush

Syntax

Flush()

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the Flush method to remove all rows from the rowset and free its associated buffer. Rows that are flushed are not deleted from the database. This function is often used to clear a work scroll before using the Select method.

Note: Flush always leaves one row in the scroll.

You cannot flush the current context of the executing program. This means Flush cannot be used for the rowset containing the executing program, or in any child rowset and executed against the parent rowset. Place your PeopleCode in a parent rowset and execute it against a child rowset.

For rowsets corresponding to component buffer data, the Flush method executes in turbo mode only—that is, default processing is performed, but only on the row being flushed. Additional information on turbo mode and non-turbo mode is available in the documentation with the InsertRow PeopleCode built-in function.

See "InsertRow" (PeopleTools 8.54: PeopleCode Language Reference).

Considerations When Initializing New Rows

Flush removes all rows and inserts a row.

If you want to initialize the row, that is, have the defaults and any RowInit PeopleCode run, you must do something to invoke the default value processing. This can be as simple as setting the value of another field on the same page that has a PeopleCode program associated with it.

If the rowset is created from message data, an Application Engine program, and so on, the rows are flushed but the row that is inserted is not initialized.

Considerations for User-Sorted Grids

If a grid has a user personalized sort defined for it and your PeopleCode program flushes that grid and then repopulates it (for instance, through a Fill, a Select, or a series of InsertRow calls), this could invalidate the user's personalized sort and the current row in the user's view unless your PeopleCode program makes arrangements to reapply these user personalizations.

After flushing and repopulating the rowset, your PeopleCode program should re-sort the rowset (that is, re-sort the grid). If the user has a personalized sort, then the user's personalized sort will be reapplied via the PeopleCode sort.

Also, after flushing and repopulating a grid, it will be important to manage which row is deemed the current row. This can be managed using methods such as IsUserSorted, GetFirstUserSortedRow, MapBufRowToUserSortRow, and then by setting the TopRowNumber property accordingly.

See IsUserSorted.

Parameters

None.

Returns

None.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

The following example checks for the value of the field CHECKLIST_CD. If something exists in this field, the second level rowset is flushed and new values are selected into it.

```
If All(CHECKLIST_CD) Then
   &RS1H.Flush();
   &RS1H.Select(RECORD.CHECKLIST_ITEM, "where Checklist_CD = :1 and EffDt = (Select⇒
 Max(EffDt) from PS_CHECKLIST_ITEM Where CheckList_CD = :2)", CHECKLIST_CD, CHECKLI⇒
ST_CD);
End-If;
```

Related Links

FlushRow

DeleteRow

InsertRow

FlushRow

Syntax

FlushRow(*n*)

Description

Use the FlushRow method to remove a specific row from a rowset and from the Component buffer. Rows that are flushed are not deleted from the database.

FlushRow is a specialized and infrequently used method. In most situations, you want to use DeleteRow to remove a row from the Component buffer and remove it from the database as well when the component is saved.

You cannot flush the current context of the executing program. This means FlushRow cannot be used for the rowset containing the executing program, or in any child rowset and executed against the parent rowset. Place your PeopleCode in a parent rowset and execute it against a child rowset.

Parameters

n	An integer identifying a row within the rowset object. This must be >= 1 and <= the number of rows in the rowset (see property RowCount).

Returns

None.

Example

```
&ROWSET.FlushRow(&ROWNUMBER);
```

Related Links

DeleteRow

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Flush
InsertRow

GetCurrEffRow

Syntax

GetCurrEffRow()

Description

GetCurrEffRow returns a row object for the row with the current effective date. This includes dates equal to the current date, but not dates in the future. If the primary record associated with the rowset is not effective-dated this method returns a null object.

Newly inserted rows are intentionally skipped when looking for the current effective-dated row. This is to find the current effective row from the data that already exists in the database. In other words, a row cannot be considered as a current effective row until it is saved. To find the current effective-dated row in data that has been newly inserted and not yet saved, use the GetNewEffRow method instead.

Parameters

None.

Returns

A row object for the row with the current effective date.

Example

```
&tmp =  &ROWSET.GetCurrEffRow().RowNumber;
/* note RowNumber is a property of the row class */
```

Related Links

DeleteEnabled
GetRow
GetNextEffRow
GetNewEffRow
"GetRow" (PeopleTools 8.54: PeopleCode Language Reference)

GetFirstUserSortedRow

Syntax

GetFirstUserSortedRow(*GridName*)

Description

Use this method to get the first row from a sort view.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

GridName Specify the grid name as a string in PAGE.RECORD format in which PAGE is the page name and RECORD is the name of the grid as defined in Application Designer. (In Application Designer, select Page Field Properties, General tab to view the value for the Page Field Name field. The Page Field Name field's value defaults to the primary record name for the level at which the grid occurs; however, the value can be changed by the application developer.)

Returns

A row object for the first row from the sort view.

If the grid has not been sorted, the output row object is equivalent to the first row from the rowset.

Related Links

IsUserSorted

GetLastUserSortedRow

Syntax

```
GetLastUserSortedRow(GridName [, visible])
```

Description

Use this method to get the last row from a sort view.

Parameters

GridName Specify the grid name as a string in PAGE.RECORD format in which PAGE is the page name and RECORD is the name of the grid as defined in Application Designer. (In Application Designer, select Page Field Properties, General tab to view the value for the Page Field Name field. The Page Field Name field's value defaults to the primary record name for the level at which the grid occurs; however, the value can be changed by the application developer.)

visible Specify, as an optional Boolean parameter, whether to return the absolute last row from the rowset, which could be hidden, or the last visible row from the sort view. If true, the last visible row is returned; otherwise, the absolute last row from the rowset is returned. The default value is false—that is, return the absolute last row.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

A row object for the last row from the sort view (*visible* is true) or the absolute last row from the rowset (*visible* is false).

Related Links

IsUserSorted

GetNewEffRow

Syntax

GetNewEffRow()

Description

GetNewEffRow returns a row object for the row with the effective date closest to the current date, including newly inserted rows. This means dates equal to the current date, but not future dates. If the primary record associated with the rowset is not effective-dated this method returns a null object.

To find the current effective-dated row from the data that already exists in the database, that is, only from saved rows and *not* a newly created row, use the GetCurEffRow method instead.

Parameters

None.

Returns

A row object for the row with the current effective date.

Example

```
Local Row &MyRow = &ROWSET.GetNewEffRow();
```

Related Links

GetRow
GetNextEffRow
GetCurrEffRow
DeleteEnabled
"GetRow" (PeopleTools 8.54: PeopleCode Language Reference)

GetRow

Syntax

GetRow(*n*)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

GetRow returns a row object from a rowset. This is a default method for rowsets. This means that any rowset object, followed by a parameter list, acts as if GetRow is specified.

Parameters

n	An integer identifying a row within the rowset object. This must be >= 1 and <= the number of rows in the rowset (see property RowCount).

Returns

Returns a row object for the specified row of the rowset.

Example

In the following example, all of the lines of code do the same thing: they return the 5th row from the rowset (&ROWSET is a rowset object.)

```
&ROW = GetRowset().GetRow(5);
&ROW = GetRowset()(5);
&ROW = &ROWSET.GetRow(5);
&ROW = &ROWSET(5);
```

The following example loops through all the rows in a rowset:

```
Local rowset &LEVEL1;
Local row &ROW;

&LEVEL1 = GetRowset(SCROLL.EMPL_CHECKLIST);
For &I = 1 to &LEVEL1.ActiveRowCount
   &ROW = &LEVEL.GetRow(&I);
   /* do some processing */
End-For;
```

Related Links

"GetRow" (PeopleTools 8.54: PeopleCode Language Reference)

HideAllRows

Syntax

HideAllRows()

Description

HideAllRows hides all rows of the rowset. Using this method is equivalent to a loop setting the visible property of each row of the rowset to False.

You cannot hide rows in the current context of the executing program. This means HideAllRows cannot hide the rowset containing the executing program, or in any child rowsets and be executed against the parent rowset. Place your PeopleCode in a parent rowset and execute it against a child rowset.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

None.

Returns

None.

Example

The following example hides the second level scroll if a value exists in the NO_COMMENTS field in the first level of the scroll. The code is running from the first level of the scroll.

```
Local Rowset &RS1, &RS2;

&RS1 = GetRowset();
&RS2 = GetRowset(SCROLL.EMPL_CHKLST_ITM);

For &I = 1 to &RS1.ActiveRowCount
   If ALL(&RS1.GetRow(&I).EMPLOYEE_CHECKLIST.NO_COMMENTS) Then
      &RS2.HideAllRows();
   End-If;
/*other processing */
End-For;
```

Related Links

ShowAllRows

Visible

InsertRow

Syntax

InsertRow(*n*)

Description

InsertRow programmatically performs the ALT+7 and ENTER (RowInsert) function. InsertRow inserts a new row in the current rowset *after* the row specified by the parameter if the primary record for the rowset is not effective-dated or a standalone rowset. If the primary record for the rowset is effective-dated or a standalone rowset, the new row is inserted *before* the current row, and all values from the current row are copied into the new row, except for EFFDT, which is set to the current date.

In addition, InsertRow propagates the keys from the higher level (if any) into the inserted row.

If the program is being run from a component against Component buffer data, a RowInit PeopleCode event also fires, followed by the events that normally follow a RowInsert, as if the user had manually pressed ALT+7 and ENTER.

The InsertRow method can be executed against the same rowset where the insertion will take place.

For rowsets corresponding to component buffer data, the InsertRow method executes in turbo mode only —that is, default processing is performed, but only on the row being inserted. Additional information on turbo mode and non-turbo mode is available in the documentation with the InsertRow PeopleCode built-in function.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

See "InsertRow" (PeopleTools 8.54: PeopleCode Language Reference).

InsertRow cannot be executed from the same rowset where the insertion will take place, or from a child rowset against a parent. Place your PeopleCode in a parent rowset and execute it against a child rowset.

Note: If you use InsertRow on a rowset created using the CreateRowset function, the row isn't automatically inserted in the database when the page is saved. Rowsets created using the CreateRowset function are standalone rowsets, not tied to the database, so there are no database updates when they are manipulated. Delete and insert activity on these types of rowsets aren't automatically applied at save time.

Effective-Dated Row Considerations

When a row is inserted, if that row contains child scrolls, this method also inserts an empty row for any child scrolls. The effective-date field for this empty row is also empty. The current date is *not* used.

Parameters

n	An integer identifying a row within the rowset object. This must be >= 0 and <= the number of active rows in the rowset (see property ActiveRowCount). A value of 0 inserts in front of the first row.

Returns

An optional Boolean value: True if the row is inserted, False if the row is not inserted.

Example

In the following example, as the primary database record isn’t effective-dated, the new row is inserted *after* the second row in the rowset.

```
&ROWSET.InsertRow(2);
```

Related Links

DeleteRow
Delete
"Using Standalone Rowsets" (PeopleTools 8.54: PeopleCode Developer’s Guide)

IsUserSorted

Syntax

IsUserSorted(*GridName*)

Description

Use this method to determine whether a user sort has been performed on the specified grid.

A *user sort* is defined as a user either having clicked on a column heading on the grid or having applied a sort order on the grid’s customization page. In the case of a user sort, a *sort view* is created based on the sort order defined by the user. Since this sort view is for display purposes only, the underlying buffer

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

is not sorted and remains in the non-sorted order. Four additional methods (GetFirstUserSortedRow, GetLastUserSortedRow, MapBufRowToUserSortRow, and MapUserSortRowToBufRow) enable you to interrogate this sort view. These methods can be used to map the sort view to the buffer, to map the buffer to the sort view, to retrieve the first user-sorted row, and to retrieve the last user-sorted row.

Note: When a grid includes a hyperlink field that is user-sortable, the hyperlink label must be set in PeopleCode prior to allowing the user to perform the sort. Alternatively, the buffer can be sorted on the hyperlink field in PeopleCode upon entry into the page.

Parameters

GridName Specify the grid name as a string in PAGE.RECORD format in which PAGE is the page name and RECORD is the name of the grid as defined in Application Designer. (In Application Designer, select Page Field Properties, General tab to view the value for the Page Field Name field. The Page Field Name field's value defaults to the primary record name for the level at which the grid occurs; however, the value can be changed by the application developer.)

Returns

A Boolean value: true if a user sort has been performed on the grid, false otherwise.

Related Links

GetFirstUserSortedRow
GetLastUserSortedRow
MapBufRowToUserSortRow
MapUserSortRowToBufRow
Sort

MapBufRowToUserSortRow

Syntax

MapBufRowToUserSortRow(*GridName, number*)

Description

Use this method to return the sort view row number that corresponds to the specified buffer row number.

Parameters

GridName Specify the grid name as a string in PAGE.RECORD format in which PAGE is the page name and RECORD is the name of the grid as defined in Application Designer. (In Application Designer, select Page Field Properties, General tab to view the value for the Page Field Name field. The Page Field Name field's value defaults to the primary record name for the level at

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

which the grid occurs; however, the value can be changed by the application developer.)

number Specify the row number of the row in the buffer.

Returns

The row number, as a number, of the row in the sort view.

If the grid has not been sorted, the output row number is the same as the buffer row number.

Example

```
&szSortViewName = "QE_PIA_SORT_GRID1.L2RSSORTTEST";
Local Rowset &rsCurrent = GetLevel0()(1).GetRowset(Scroll.QE_PIA_SORTEST2)(1).GetRo⇒
wset(Scroll.QE_PIA_SORTEST3);

If &rsCurrent.IsUserSorted(&szSortViewName) Then
   WinMessage("QE_PIA_SORT_GRID1-Rowset1 User Sorted");
Else
   WinMessage("QE_PIA_SORT_GRID1-Rowset1 Not User Sorted");
End-If;

For &I = 1 To &rsCurrent.ActiveRowCount
   &index = &rsCurrent.MapBufRowToUserSortRow(&szSortViewName, &I);
   WinMessage("QE_PIA_SORT_GRID1-Rowset1, Buffer Row Index:  " | &I | ",  Sort Row ⇒
Index:  " | &index | ",  Description:  " | &rsCurrent(&I).QE_PIA_SORTEST3.DESCR30.V⇒
alue);
End-For;
```

Related Links

IsUserSorted

MapUserSortRowToBufRow

Syntax

MapUserSortRowToBufRow(*GridName*, *number*)

Description

Use this method to return the buffer row number that corresponds to the specified sort view row number.

Parameters

GridName Specify the grid name as a string in PAGE.RECORD format in which PAGE is the page name and RECORD is the name of the grid as defined in Application Designer. (In Application Designer, select Page Field Properties, General tab to view the value for the Page Field Name field. The Page Field Name field's value defaults to the primary record name for the level at which the grid occurs; however, the value can be changed by the application developer.)

number Specify the row number of the row in the sort view.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

The row number, as a number, of the row in the buffer.

If the grid has not been sorted, the output row number is the same as the buffer row number.

Example

```
&szSortViewName = "QE_PIA_SORT_GRID1.L2RSSORTTEST";
Local Rowset &rsCurrent = GetLevel0()(1).GetRowset(Scroll.QE_PIA_SORTEST2)(2).GetRo⇒
wset(Scroll.QE_PIA_SORTEST3);

If &rsCurrent.IsUserSorted(&szSortViewName) Then
   WinMessage("QE_PIA_SORT_GRID1-Rowset2 User Sorted");
Else
   WinMessage("QE_PIA_SORT_GRID1-Rowset2 Not User Sorted");
End-If;

For &I = 1 To &rsCurrent.ActiveRowCount
   &index = &rsCurrent.MapUserSortRowToBufRow(&szSortViewName, &I);
   WinMessage("QE_PIA_SORT_GRID1-Rowset2, Description:  " | &rsCurrent(&index).QE_P⇒
IA_SORTEST3.DESCR30.Value);
End-For;
```

Related Links

IsUserSorted

Refresh

Syntax

Refresh()

Description

Refresh reloads the rowset object from the database using the current page keys. This causes the page to be redrawn. The following code example refreshes the entire page:

```
GetLevel0().Refresh()
```

Important! Do not call GetLevel0().Refresh() from any context that is not at level 0. You are likely to leave invalid pointers to objects that have been cleared from the buffer, which can result in an application server crash.

If you only want a specific scroll to be redrawn, you can use the refresh method with that rowset. You don't have to use a level zero rowset with this method. This is particularly useful after using RemoteCall.

Note: If a scroll is marked as No Auto Select in Application Designer, Refresh will not work on it. The Refresh method clears the existing buffers and does a refresh from the database. You do *not* want to use this method if your rowset is based on message data. Instead, you can use the CopyTo Rowset method combined with TransferPage.

Parameters

None.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

None.

Example

The following example refreshes the entire page.

```
&Mylevel0 = GetLevel0().Refresh();
```

The following example refreshes only the second level scroll of the page:

```
&RowSetLevel2.Refresh();
```

Related Links

CopyTo
"RemoteCall" (PeopleTools 8.54: PeopleCode Language Reference)
"TransferPage" (PeopleTools 8.54: PeopleCode Language Reference)

Select

Syntax

Select([*parmlist*], **RECORD**.*selrecord* [, *wherestr, bindvars*])

Where *paramlist* is a list of child rowsets, given in the following form:

SCROLL.*scrollname1* [, *SCROLL.scrollname2*] . . .

The first *scrollname* must be a child rowset of the rowset object executing the method, the second *scrollname* must be a child of the first child, and so on.

Description

Select, like the related method SelectNew, reads data from the database tables or views into either a row or rowset object.

Note: This method is valid only when used with rowsets that reference data from the component buffers. You cannot use this method with a message rowset, a rowset from an Application Engine state record, and so on. You can't use this method with rowsets created using the CreateRowset function (use the Fill method instead.)

Select automatically places child rowsets in the rowset object executing the method under the correct parent row. If it cannot match a child rowset to a parent row, an error occurs.

When a rowset is selected into, any autoselected child rowsets is also read. The child rowsets are read using a where clause that filters the rows according to the where clause used for the parent rowset, using a subselect.

If you don't specify any child rowsets in *paramlist*, Select selects from a SQL table or view specified by *selrecord* into the rowset object executing the method.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

If you specify a child rowset in *paramlist*, Select selects from a SQL table or view specified by *selrecord* into the child rowset specified in *paramlist*, under the appropriate row of the rowset executing the method.

If the rowset executing the method is a level zero rowset, and you specify Select without specifying any child rowsets with *paramlist*, the method reads only a single row, because only one row is allowed at level zero.

The rowset executing the method *does not* have to be a level zero rowset, so the Select method can produce the functionality of both the ScrollSelect and RowScrollSelect functions.

Note: For developers familiar with previous releases of PeopleCode: If the rowset executing the method is a level zero rowset, and you specify a child rowset with *paramlist*, this method functions exactly like ScrollSelect. If the rowset executing the method is not a level zero rowset, and no child rowsets are specified with *paramlist*, the method acts like RowScrollSelect.

The record definition of the table or view being selected from is called the *select record*, and identified with **RECORD.** *selrecord*. The select record can be the same as the primary database record associated with the rowset, or it can be a different record definition that has compatible fields. If you define a select record that differs from the primary database record for the rowset, you can restrict the number of fields that are loaded into the buffers on the client workstation by including only the fields that you actually need.

Select accepts a SQL string that can contain a WHERE clause restricting the number of rows selected into the object. The SQL string can also contain an ORDER BY clause to sort the rows.

Select and its related methods generate a SQL SELECT statement at runtime, based on the fields in the select record and the WHERE clause passed to them in the method parameters.

For rowsets corresponding to component buffer data, the Select method executes in turbo mode only—that is, default processing is performed, but only on the row being selected. Additional information on turbo mode and non-turbo mode is available in the documentation with the InsertRow PeopleCode built-in function.

See "InsertRow" (PeopleTools 8.54: PeopleCode Language Reference).

Parameters

paramlist

An optional parameter list, for specifying children rowsets of the rowset executing the method, as the rowset to be selected into. The first *scrollname* in *paramlist* must be a child rowset of the rowset executing the method, the second *scrollname* must be a child of the first child, and so on.

RECORD.*selrecord*

Specifies the select record. The *selrecord* record must be defined in Application Designer and be a build SQL table (using Build, Project) as a table or a view, unless *selrecord* is the same record as the primary database record associated with the rowset. *selrecord* can contain fewer fields than the primary record associated with the rowset, although it must contain any key fields to maintain dependencies with other records.

wherestr

Contains a WHERE clause to restrict the rows selected from *selrecord* and/or an ORDER BY clause to sort the rows. The

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

WHERE clause can contain the PeopleSoft meta-SQL functions such as %DateIn() or %CurrentDateIn. It can also contain inline bind variables.

bindvars A list of bind variables to be substituted in the WHERE clause. The same restrictions that exist for SQLExec exist for these variables. See SQLExec for further information.

Returns

The number of rows read (optional.) This counts only the lines read into the specified rowset. It does not include any additional rows read into any child rowsets of the rowset.

Example

The following example selects into the level zero rowset, only one row. Depending on the autoselect settings on any child scrolls, they may be reselected too.

```
&LEVEL0 = GetLevel0();
&LEVEL0.Select(RECORD.PERSONAL_DATA, "WHERE.  .  .");
```

The following example selects into the level one scroll specified. Depending on the autoselect settings on any child (level two) scrolls, they may also be selected.

```
&LEVEL0.Select(SCROLL.EMPL_CHECKLIST, RECORD.EMPL_CHECKLIST, "WHERE.  .  .");
```

The following example selects into the child scroll of the level one rowset. Each row fetched is placed under the appropriate row in &LEVEL1. Note that instead of hard-coding the WHERE clause, the SQL repository is used to access a SQL definition named SELECT_WHERE.

```
&LEVEL1 = &LEVEL0()(1).GetRowset(SCROLL.EMPL_CHECKLIST);
&LEVEL1.Select(SCROLL.EMPL_CHKLST_ITM, RECORD.EMPL_CHKLST_ITM, SQL.SELECT_WHERE);
```

The following example first flushes the hidden work scroll, then selects into it based on a field on the page.

```
&RS1H.Flush();
&RS1H.Select(RECORD.CHECKLIST_ITEM, "where Checklist_CD = :1 and EffDt = (Select Ma⇒
x(EffDt) from PS_CHECKLIST_ITEM Where CheckList_CD = :2)", CHECKLIST_CD, CHECKLIST_⇒
CD);
```

Related Links

SelectNew

SelectByKey

SelectNew

Syntax

SelectNew([*parmlist*], **RECORD.***selrecord* [, *wherestr*, *bindvars*])

Where *paramlist* is a list of child rowsets, given in the following form:

SCROLL.*scrollname1* [, **SCROLL.***scrollname2*] . . .

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The first *scrollname* must be a child rowset of the rowset executing the method, the second *scrollname* must be a child of the first child, and so on.

Description

The SelectNew method is similar to the Select method, except that all rows read into the rowset are marked *new* so they are automatically inserted into the database at Save time. This capability can be used, for example, to insert new rows into the database by selecting data using a view of columns from other database tables.

Note: This method is valid only when used with rowsets that reference data from the Component buffers. You cannot use this method with a message rowset, a rowset from an Application Engine state record, and so on. You can't use this method with rowsets created using the CreateRowset function (use the Fill method instead.)

Parameters

paramlist

An optional parameter list, for specifying children rowsets of the rowset executing the method, as the rowset to be selected into. The first *scrollname* in *paramlist* must be a child rowset of the rowset executing the method, the second *scrollname* must be a child of the first child, and so on.

RECORD.*selrecord*

Specifies the select record. The *selrecord* record must be defined in Application Designer and be a build SQL table (using Build, Project) as a table or a view, unless *selrecord* is the same record as the primary database record associated with the rowset. *selrecord* can contain fewer fields than the primary record associated with the rowset, although it must contain any key fields to maintain dependencies with other records.

wherestr

Contains a WHERE clause to restrict the rows selected from *selrecord* and/or an ORDER BY clause to sort the rows. The WHERE clause can contain the PeopleSoft meta-SQL functions such as %DateIn() or %CurrentDateIn. It can also contain inline bind variables.

bindvars

A list of bind variables to be substituted in the WHERE clause. The same restrictions that exist for SQLExec exist for these variables. See SQLExec for further information.

Returns

The number of rows read (optional.) This counts only the lines read into the specified rowset. It does not include any additional rows read into any child rowsets of the rowset.

Example

The following example selects rows from DATA2 and reads them into a level one scroll. If the user saves the page, these rows are inserted into DATA1.

```
&LEVEL0.SelectNew(SCROLL.DATA1, RECORD.DATA2, "Where SETID = :1 and CUST_ID =:2", C⇒
USTOMER.SETID, CUSTOMER.CUST_ID);
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

If you use the same WHERE clause in more than one Select, you may want to use the SQL repository to store the SQL fragment. That way, if you ever want to change it, you will have to change it in only one place.

```
&LEVEL0.SelectNew(SCROLL.DATA1, RECORD.DATA2, SQL.Select_New);
```

Related Links

Select

SelectByKey

SetDefault

Syntax

SetDefault(*recname.fieldname*)

Description

The SetDefault method sets the value of the specified *recname.fieldname* to a null value in every row of the rowset. If this method is being run from a component against Component buffer data, the next time default processing is performed, this value is reinitialized to its default value: either a default specified in its record field definition or one set programmatically by PeopleCode located in a FieldDefault event. If neither of these defaults exist, the Component Processor leaves the field blank.

No default processing is performed against data that is not in the Component buffers.

Blank numbers correspond to zero on the database. Blank characters correspond to a space on the database. Blank dates and long characters correspond to NULL on the database. SetDefault gives each field data type its proper value.

Parameters

recname.fieldname	Specifies a field. The field must be in the specified record, on the rows of the rowset.

Returns

None.

Example

This example resets the PROVIDER to its null value. This field is reset to its default value when default processing is next performed:

```
If COVERAGE_ELECT = "W" Then
   &ROWSET.SetDefault(INS_NAME_TBL.PROVIDER);
End-if;
```

Related Links

SetDefault

"Default Processing" (PeopleTools 8.54: PeopleCode Developer’s Guide)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ShowAllRows

Syntax

ShowAllRows()

Description

ShowAllRows "unhides" all rows of the rowset object executing the method. Using this method is equivalent to a loop setting the visible property of each row of the rowset to True.

ShowAllRows cannot be executed from the same rowset you want to display, or from a child rowset against a parent. Place your PeopleCode in a parent rowset and execute it against a child rowset.

Parameters

None

Returns

None.

Example

```
&ROWSET.ShowAllRows();
```

Related Links

HideAllRows
Visible

Sort

Syntax

Sort([*paramlist*,] *sort_fields*)

Where *paramlist* is a list of child rowsets, given in the following form:

SCROLL.*scrollname1* [, **SCROLL.***scrollname2*] . . .

The first *scrollname* must be a child rowset of the rowset executing the method, the second *scrollname* must be a child of the first child, and so on.

And where *sort_fields* is a list of field specifiers in the form:

[*recordname*.]*field_1*, *order_1* [, [*recordname*.]*field_2*, *order_2*]_

Description

Sort programmatically sorts the rows in a rowset. The rows can be sorted on one or more fields.

If you specify a child rowset in *paramlist*, Sort selects a set of child rowsets to be sorted. If you don't specify a child rowset in *paramlist*, the rowset executing the method is sorted.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The type of sort done by this function, that is, whether it is a linguistic or binary sort, is determined by the Sort Order Option on the PeopleTools Options page.

Note: The Sort method sorts only *visible* rows in a rowset. If the rowset you're sorting has hidden rows, the hidden rows are not sorted. Rows marked for deletion are also not sorted.

Parameters

paramlist	An optional parameter list, for specifying children rowsets of the rowset executing the method, as the rowset to be sorted. The first *scrollname* in *paramlist* must be a child rowset of the rowset executing the method, the second *scrollname* must be a child of the first child, and so on.
sort_fields	A list of field and order specifiers which act as sort keys. The rows in the rowset will be sorted by the first field in either ascending or descending order, then by the second field in either ascending or descending order, and so on.
[*recordname*.]*field_n*	Specifies a sort key field in the rowset. The *recordname* prefix is required if you've specified a field that is not on the current record.
order_n	A single-character string. "A" specifies ascending order; "D" specifies descending order.

Returns

None.

Example

The first example repopulates a rowset in a page programmatically by first flushing its contents, selecting new contents using Select, then sorting the rows in ascending order by EXPORT_OBJECT_NAME:

```
Function populate_rowset;

   &RS1 = GetLevel0()(1).GetRowset(SCROLL.EXPORT_OBJECT);
   &RS1.Flush();
   &RS1.Select(RECORD.EXPORT_OBJECT, "where export_type =:EXPORT_TYPE_VW.EXPORT_TYP⇒
E");
   &RS1.Sort(EXPORT_OBJECT_NAME, "A");

End-Function;
```

Related Links

IsUserSorted

Select

GetRowset

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Rowset Class Properties

In this section, we discuss the Rowset class properties. The properties are discussed in alphabetical order.

ActiveRowCount

Description

This property returns the number of active (non-deleted) rows in the rowset.

This property returns a value of 1 for an empty scroll (Flush always leaves an empty row.) You can use the IsChanged or IsNew properties to verify if the row is new.

This property is read-only.

Example

```
&tmp = &ROWSET.ActiveRowCount;
```

ChangeOnInit

Description

Normally, if a field value is changed, whether through PeopleCode or by an end user, the IsChanged property for the row is set to True. The exception to this is when a change is done in the FieldDefault or FieldFormula event, that is, if a value is set in one of these events, the row is not marked as changed.

At save time, all newly inserted *and* changed rows are written to the database. All newly inserted but *not* changed rows are *not* written to the database.

Use this property to specify whether a change made to a new row from RowInit or RowInsert PeopleCode is marked as changed. This property takes a Boolean value. The default value is True.

Setting this property to False causes changes to fields for the rowset done in RowInit and RowInsert PeopleCode to *not* mark a new row as IsChanged.

This property is read-write.

Runtime Considerations

You must set this property *before* anything is changed for a row, otherwise the row is marked as changed.

This property propagates to child rowsets. That is, if it's set for a parent rowset before doing an insert row, it's automatically set on any and all child rowsets.

In addition, parent rows are marked as changed if this property is set only for the child rowset. That is, if you've changed a level three child of a level two row, the level two and level one rows are marked as changed to maintain data integrity.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

DataAreaCollapsed

Description

This property specifies whether the view of a data area is collapsed or expanded.

Note: You must set the Collapsible Data Area field on the properties for the level-based control for this property to have any effect.

This property changes to reflect the current state of the data area, according to whether the user has collapsed or expanded it. Changing the value collapses or expands the data area, but it does *not* prevent the user from collapsing (or expanding) it themselves.

Note: Because the user can change the value of this property, whatever value is set in PeopleCode isn't guaranteed to be still set the next time it is checked, because the user may have collapsed or expanded the data area in the meantime.

This property overwrites the value of the Default Initial View to Expanded field set in Application Designer. For example, if Default Initial View to Expanded is selected in Application Designer, then the value for the DataAreaCollapsed property is set to True, the control initially displays collapsed.

This property takes a Boolean value: True, initially display the data area collapsed, False, initially display the data area expanded.

This property is read-write.

Note: To collapse just a group box, use the DataAreaCollapsed field method.

Related Links

DataAreaCollapsed

Example

The following example checks the number of rows in the level one rowset. If the number of rows returned is larger than 100, the data area is initially displayed collapsed.

```
If &Level1.RowCount > 100 Then
   &Level1.DataAreaCollapsed = True;
Else
   &Level1.DataAreaCollapsed = False;
End-If;
```

DBRecordName

Description

This property returns the name of the primary database record as a string for the rowset.

This property is read-only.

Example

```
&DBNAME = &ROWSET.DBRecordName;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

DeleteEnabled

Description

This property determines whether a rowset allows rows to be deleted (the equivalent of the user pressing ALT+8 and ENTER). This property takes a Boolean value.

Note: This property controls only whether an end-user can delete a row. Rows can still be deleted using PeopleCode.

The initial value of this property depends on how the scroll was created at design time. If the No Row Delete setting is selected on the Use tab of the scroll properties dialog box, DeleteEnabled will be False: otherwise it will be True.

Note: If No Row Delete is selected in Application Designer, setting DeleteEnabled to True will *not* override this value. To control whether a rowset allows deletions at runtime, you should *not* select No Row Delete at design time.

For consistency, PeopleSoft recommends that either all rowsets at a level should disable deletions, or they should all allow deletions.

For rowsets created with non-Component Processor data (such as message rowsets, Application Engine rowsets, and so on) this property has no effect.

Note: Don't use this property with rowsets that are created using CreateRowset. Rowsets created using the CreateRowset function are standalone rowsets, not tied to the database, so there are no database updates when they are manipulated. Delete and insert activity on these types of rowsets aren't automatically applied at save time.

This property is read-write.

Related Links

DeleteEnabled, InsertEnabled "Using Scroll Areas and Scroll Bars" (PeopleTools 8.54: Application Designer Developer's Guide) "Using Standalone Rowsets" (PeopleTools 8.54: PeopleCode Developer's Guide)

EffDt

Description

This property references the effective date of the primary record associated with the rowset. If the primary record associated with the rowset is not effective-dated, this property has a null value. To find the primary record associated with a rowset object, you can use the DBRecordName property.

Note: This property isn't valid with rowsets created using the CreateRowset function.

This property is read-only.

Example

```
&tmp = &ROWSET.EffDt;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

"CreateRowset" (PeopleTools 8.54: PeopleCode Language Reference)

EffSeq

Description

This property references the effective-sequence number of the primary record associated with the rowset. If the primary record associated with the rowset does not have an effective-sequence number, this property has the value 0. To find the primary record associated with a rowset object, you can use the DBRecordName property.

Note: This property isn't valid with rowsets created using the CreateRowset function.

This property is read-only.

Example

```
&tmp = &ROWSET.EffSeq;
```

Related Links

"CreateRowset" (PeopleTools 8.54: PeopleCode Language Reference)

InsertEnabled

Description

This property determines whether a rowset allows rows to be inserted (the equivalent of the user pressing ALT+7 and ENTER). This property takes a Boolean value.

Note: This property controls only whether an end-user can insert a row. Rows can still be inserted using PeopleCode.

The initial value of this property depends on a value set at design time. If the No Row Insert setting is selected on the Use tab of the scroll properties dialog box, InsertEnabled is False: otherwise it is True.

Note: If No Row Insert is selected in Application Designer, setting InsertEnabled to True does *not* override this value. To control whether a rowset allows inserts at runtime, you should *not* select No Row Insert at design time.

For consistency, PeopleSoft recommends that either all rowsets at a level should disable inserts, or they should all allow inserts.

For rowsets created with non-Component Processor data (such as message rowsets, Application Engine rowsets, and so on) this property has no effect.

Note: Don't use this property with rowsets created using CreateRowset. Rowsets created using the CreateRowset function are standalone rowsets, not tied to the database, so there are no database updates when they are manipulated. Delete and insert activity on these types of rowsets aren't automatically applied at save time.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-write.

Related Links

DeleteEnabled "Using Scroll Areas and Scroll Bars" (PeopleTools 8.54: Application Designer Developer's Guide) "Using Standalone Rowsets" (PeopleTools 8.54: PeopleCode Developer's Guide)

IsEditError

Description

This property is True if an error has been found on any field in any record in any row or child rowset of the current rowset after executing the ExecuteEdits method on either a message object or a record object. This property can be used with the Field Class properties EditError (to find the field that's in error), MessageSetNumber and MessageNumber to find the error message set number and error message number.

This property is read-only.

Example

The following is an example showing how IsEditError, along with ExecuteEdits could be used:

```
&REC.ExecuteEdits();
If &ROWSET.IsEditError Then
   For &I = 1 to &ROWSET.ActiveRowCount
      &ROW = &ROWSET(&I);
         For &J to &ROW.RecordCount
            &REC = &ROW.GetRecord(&J);
               For &K = 1 to &REC.FieldCount
                  If &REC.GetField(&K).EditError Then
                     LOG_ERROR();
                        /* application specific call */
                  End-If;
            End-For;
         End-For;
   End-For;
End-If;
```

Related Links

ExecuteEdits

IsEditError

EditError

MessageNumber

MessageSetNumber

Level

Description

This property returns the level, that is, the nesting depth, of the rowset object. The top-level rowset has a level number of 0.

This property is read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

```
&tmp = &ROWSET.Level;
```

Name

Description

This property refers to the name of the rowset. This property returns different values, based on the type of rowset.

Type of Rowset	*Returns*
Rowset created using GetLevel0	returns an empty string
Component buffer rowset	returns primary record name
Message rowset	returns primary record name
Component Interface rowset	returns primary record name
Application Engine rowset	always returns AESTATE

This property is read-only.

Example

```
&tmp = &ROWSET.Name;
```

ParentRow

Description

This property returns a row object containing a reference to the parent row, that is, the row containing the rowset. If this is a top-level rowset (level zero), the ParentRow property has a null value.

This property is read-only.

Example

```
&tmp = &ROWSET.ParentRow.RowNumber;
/* note that RowNumber is a property of the row class */
```

ParentRowset

Description

This property returns a rowset object containing a reference to the parent rowset, that is, the rowset containing the rowset. If this is a top-level rowset (level zero), the ParentRowset property has a null value.

This property is read-only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

```
&tmp = &ROWSET.ParentRowset.Level;
/* note Level is another property of the rowset class */
```

RowCount

Description

This property returns the total number of rows in the rowset. It includes deleted rows. (The ActiveRowCount property doesn't include deleted rows.)

This property is read-only.

Example

```
&tmp = &ROWSET.RowCount;
```

SetComponentChanged

Description

This property determines whether any changes to the rowset using PeopleCode marks the component as changed and the data written to the database if the rowset is not a based on a derived/work record.

This property takes a Boolean value: true, changes to the rowset mark the component as changed, false, the component is treated as if unchanged. The default is true.

If you set this property to false, this means that no row insert, row delete, field change on the rowset using PeopleCode would cause the system to treat the component data as changed.

The SetComponentChanged rowset class property overrides the SetComponentChanged field class property. If a field has SetComponentChanged set to true, but its associated rowset has SetComponentChanged set to false, any change to the field does not mark the component as changed.

This property is read-write.

Related Links

SetComponentChanged

TopRowNumber

Description

This property returns the row that is being displayed at the top of the scroll (if any) for the rowset.

Generally, this property is used to return the top row number of a scroll. However, sometimes you want to reposition the scroll. For example, if you use SetCursorPos to move the focus to a given field, there is no guarantee that the row containing the field is at the top of the scroll.

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Chapter 42

RowsetCache Class

Understanding a Rowset Cache

Many PeopleSoft applications use a metadata based design, where application PeopleCode reads metadata from a database record or some other source, then presents the user with an interface that is modified based on the metadata.

PeopleTools stores application data in a database cache to increase system performance. The RowsetCache class enables you to access this memory structure, created at runtime, and shared by all users.

Data that would qualify as metadata and would be appropriate for the RowsetCache class would be data that was commonly used yet fairly static, for example, country or currency tables.

The RowsetCache class does not provide a mechanism for synchronizing the data between database tables and the cache. If the underlying data changes, you must repopulate the rowset cache.

Note: Non-base language users may see different performance due to language table considerations.

Related Links

"Setting MaxCacheMemory" (PeopleTools 8.54: PeopleCode Developer's Guide)

"Cache Settings" (PeopleTools 8.54: System and Server Administration)

Using the RowsetCache Class

The first time a user accesses a database, the rowset cache for that database is automatically created and populated. After that first user, all users and applications can take advantage of the rowset cache.

If the underlying data for a rowset cache changes, at the very least your application must delete the existing rowset cache. Your application can also delete, then recreate and repopulate the rowset cache if it changes the underlying data. For example:

```
Local Rowset &RS;
Local RowsetCache &CRS;
Local Boolean &RSLT = False;

Repeat
   &I = &I + 1;
   If &RS(&I).IsChanged Then
      &RSLT = True;
   End-If;
Until &RSLT or
   &RS.RowCount = &I;

If &RSLT Then
   &CRS = GetRowsetCache(&RS);
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
   &CRS.Delete();
   &CRS = CreateRowsetCache(&RS);
   &CRS.Save();
End-if;
```

PeopleSoft recommends that any standard operations used by your application, such as deleting and repopulating the rowset cache, be encapsulated in an application class.

See Understanding Application Classes.

The RowsetCache contains a rowset, and serializes the contained rowset to binary form for speed. As with most PeopleTools objects, RowsetCache objects are cached to memory and file, but they are also cached to the data base.

RowsetCache objects are intended to be local to a data base : they should not be transferred to another data base.

Error Handling

Every time you use the GetRowsetCache function, you should verify that the function executed successfully by testing for a null object. For example:

```
Local RowsetCache &RSC;

&RSC = GetRowsetCache(Rowset.MyRowset);

If (&RSC <> NULL) Then
   /* do processing */
Else
   /* call to populate rowset cache */
End-if;
```

Data Type of a RowsetCache Object

Cached rowset objects are declared as type RowsetCache. For example,

```
Local RowsetCache &Cache;
```

Scope of a RowsetCache Object

A RowsetCache object can only be instantiated from PeopleCode.

This object can be used anywhere you have PeopleCode, that is, in an application class, Application Engine PeopleCode, Component Interface PeopleCode, and so on.

Note: PeopleSoft recommends that you do not specify RowsetCache objects as Global, due to their potential size.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

RowsetCache Class Built-in Functions

"CreateRowsetCache" (PeopleTools 8.54: PeopleCode Language Reference)

"GetRowsetCache" (PeopleTools 8.54: PeopleCode Language Reference)

RowsetCache Class Methods

In this section, we discuss the RowsetCache class methods. These methods are discussed in alphabetical order.

Delete

Syntax

```
Delete()
```

Description

Use the Delete method to delete the RowsetCache from memory. The RowsetCache must have already been created, either using the CreateRowsetCache and saving the RowsetCache, or by a user using the application.

If this method is called as part of a larger transaction, such as in the SavePreChange or SavePostChange event, the commit is tied to the commit of the outer transaction. If an error occurs in this method, the outer transaction will be rolled back.

If this method is invoked in a non-transactional PeopleCode event (such as RowInit) the commit is controlled by the regular Component Processor flow.

Parameters

None.

Returns

A Boolean value: True if the delete was successful, False if the specified RowsetCache wasn't found.

This method terminates with an error message if there was another problem.

Example

```
Local RowsetCache &CRS;
Local Boolean &RSLT;

&CRS = GetRowsetCache(Rowset.MyRowset);

/* do processing*/

If (&CRS <> NULL) Then
   &RSLT = &CRS.Delete();
End-If;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

"CreateRowsetCache" (PeopleTools 8.54: PeopleCode Language Reference)

"GetRowsetCache" (PeopleTools 8.54: PeopleCode Language Reference)

Get

Syntax

Get()

Description

Use the Get method to convert a RowsetCache object into a rowset object. After using this method, you can manipulate the data in the rowset like you would any other rowset, using the regular rowset methods and properties.

Parameters

None.

Returns

A rowset object populated with the cached rowset data.

Example

```
Local Rowset &RS;
Local RowsetCache &CRS;

&CRS = GetRowsetCache(Rowset.MyRowset);

If (&CRS <> NULL) Then
   &RS = &CRS.Get();
Else
   /* do error processing */
End-if;
```

Related Links

"GetRowsetCache" (PeopleTools 8.54: PeopleCode Language Reference)

Understanding Rowset Class

Save

Syntax

Save([[**Rowset.**]*name*] [, *Description*] [, *Lang*])

Description

Use the Save method to save a new or existing rowset to the cache. If a rowset of the specified name already exists, it will be replaced. Otherwise, the rowset will be added.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

If this method is called as part of a larger transaction, such as in the SavePreChange or SavePostChange event, The commit is tied to the commit of the outer transaction. If an error occurs in this method, the outer transaction will be rolled back.

If this method is invoked in a non-transactional PeopleCode event (such as RowInit) the commit is controlled by the regular Component Processor flow.

Parameters

Rowset. ***name*** — Specify the name of the rowset to be saved to the cache. If you just specify *name*, you must enclose the name in quotation marks.

Description — Specify a text string describing the rowset.

Lang — Specify the language to use when saving the rowset. See the values below.

The values for the *Lang* parameter are:

Value	*Description*
%RowsetCache_SignonLang	Attempt to save the rowset to the cache using the sign-in language. However, if the base language rowset doesn't already exist in the cache, then the save to the sign-in language fails. This is because the system requires that base language data exist before related language data can be saved. If the *Lang* parameter is omitted, this is the default behavior.
%RowsetCache_BaseLang	Save the rowset to the cache using the base language.
%RowsetCache_SignonOrBaseLang	Attempt to save the rowset to the cache using the sign-in language. If that fails, then save the rowset using the base language.

Returns

A Boolean value: True if the save was successful, False otherwise.

Example

The following code cashes &RS as a rowset definition.

```
Local RowsetCache &CRS;
Local Rowset &RS;

&CRS = GetRowsetCache(Rowset.MyRowset);

If (&CRS <> Null) Then
   &RS = &CRS.Get();
. . . /* do processing */
Else
   /* do error processing */
End-if;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
&CRS.Save();
```

Related Links

"GetRowsetCache" (PeopleTools 8.54: PeopleCode Language Reference)

RowsetCache Class Properties

In this section, we discuss the RowsetCache class properties These properties are discussed in alphabetical order.

Content

Description

Use this property to specify the contents of a RowsetCache object.

This property is read-write.

Example

The following code example verifies if the rowset cache is populated. If it isn't, the Else statement populates the rowset cache.

```
&Cache2 = GetRowsetCache("CACHE1");
If &Cache2.Get() <> Null Then
   WinMessage("Cache found");
Else
   &RS = CreateRowset(Record.PSLANGUAGES);
   &NUM_READ = &RS.Fill();
   &Cache2.Content = &RS;
   &Cache2.Description = "test " | %Language_Data;
   &RSLT = &Cache2.Save();
End-If;
```

Description

Description

This property can be used to set the description of the rowset cache as a string.

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Chapter 43

Security Authorization Classes

Understanding the Security Authorization Classes

The security authorization classes are used in conjunction with the PeopleTools security authorization service to authorize access to PeopleSoft objects (components or content references) or to authorize access to row-level data on local and remote PeopleSoft nodes.

Note: While the security authorization service can be used to provide basic authorization for PeopleSoft queries, pagelets, iScripts, components, or content references, the security authorization classes, and in a broader sense row-level security, are only applicable to components or content references, and not to PeopleSoft queries, pagelets, or iScripts.

Related Links

"Understanding Using Web Services for Object and Row-Level Data Authorization" (PeopleTools 8.54: Security Administration)

Importing the Security Authorization Classes

The security authorization classes are application classes (not a built-in class, like Rowset, Field, Record, and so on). Therefore, before you can use these classes in your implementation, you must import the security authorization classes into your program.

An import statement either names a particular application class or imports all the classes in a package.

Using the asterisks after the package name makes all the application classes directly contained in the named package available. Application classes contained in subpackages of the named package are not made available.

For the security authorization classes, use an import statement similar to the following to import all classes in the Security subpackage:

```
import PTCS_SECURITY:Security:*;
```

AuthRequest Class

This section provides an overview of the AuthRequest class and discusses:

- AuthRequest class methods.
- AuthRequest class properties.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

An AuthRequest object represents the instantiation of an authorization request. An array of AuthRequest objects is instantiated when an authorization request message is processed by the PeopleTools security authorization service.

In this section, one method and two properties of the AuthRequest class are documented:

- GetParameterValue method
- Access property
- UserId property

In addition to these items, the AuthRequest class includes numerous read-only properties that are populated from the authorization request message if the corresponding parameter is specified in the message. You can also access the string value of these undocumented, read-only AuthRequest properties as needed:

- CompItemName.
- Component.
- CrefId.
- KeyVal (access the value of a KeyVal array element with the GetParameterValue method).
- Market.
- Menu.
- Mode.
- Node.
- Portal.
- ServiceId.
- ServiceInstId.
- ServiceType.

This topic includes an example of an authorization request message and how that message could be evaluated by a custom security authorization handler.

See Implementing a Security Authorization Handler.

Related Links

"Developing the Security Authorization Service Application Class" (PeopleTools 8.54: Security Administration)

AuthRequest Class Methods

In this section, the AuthRequest class methods are presented in alphabetical order.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GetParameterValue

Syntax

GetParameterValue(*name*)

Description

Use this method to return the value of a key as a string.

Note: If the specified key name is undefined in the request message, this method returns a null string.

Parameters

name	Specifies the name of the key as a string.

Returns

A string representing the key value.

Example

```
&emplid = &arrAuthReq [&i].GetParameterValue("EMPLID");
```

AuthRequest Class Properties

In this section, the AuthRequest class properties are presented in alphabetical order.

Access

Description

Use this property to set or return a string representing the authorization status for this request. “T” indicates that the request is authorized; “F” indicates that the request is not authorized. “F” is the default value.

This property is read-write.

Example

```
&arrAuthReq [&i].Access = "T";
```

UserId

Description

Use this property to return the user ID of the user who invoked the authorization request as a string. This property is equivalent to the Username found in the SOAP message header.

This property is read-only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

```
&userid = &arrAuthReq [&i].UserId;
```

SecurityHandler Class

This section provides an overview of the SecurityHandler class and discusses SecurityHandler class methods.

The SecurityHandler class is a generic interface class without a native implementation. Therefore, you must implement this interface by developing your own class to handle your specific authorization requirements.

SecurityHandler Class Methods

In this section, the SecurityHandler class methods are presented in alphabetical order.

GetAuthorization

Syntax

GetAuthorization(*&AuthReq_array*)

Description

Implement this method to access the information in the AuthRequest object and return whether the authorization request is authorized.

An AuthRequest object represents the instantiation of an authorization request. An array of AuthRequest objects is instantiated when an authorization request message is processed by the PeopleTools security authorization service.

This topic includes an example of an authorization request message and how that message could be evaluated by a custom security authorization handler.

See Implementing a Security Authorization Handler.

Parameters

&AuthReq_array	Specifies an array of AuthRequest objects.

Returns

None.

Related Links

AuthRequest Class

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Implementing a Security Authorization Handler

An AuthRequest object represents the instantiation of an authorization request. An array of AuthRequest objects is instantiated when an authorization request message is processed by the PeopleTools security authorization service.

An authorization request message has many standard elements such as, SERVICEID, SERVICE_TYPE, PORTAL, NODE, CREFID, and so on. In addition, an authorization request message will have one or more KEYVAL elements. Typically, you as the implementer of the GetAuthorization method should determine the structure of the corresponding authorization request message, and specifically, the number and type of KEYVAL elements. You will use the value of these KEYVAL elements along with other data in the authorization request to determine whether a specific request is authorized.

Example Scenario

In this example, employee details are available in Application A while employee performance and appraisal data resides in Application B. The user Rodrigo is the manager of a team. Rodrigo makes a request to view employee performance information for two employees: Callahan and Daniel. Rodrigo is Callahan's manager while Daniel is a higher level manager in a different part of the organization.

The PeopleTools security authorization service can be used to determine whether these requests are authorized.

Authorization Request Message

Application A will send the following authorization request as a SOAP message to Application B requesting that user Rodrigo be given access to the performance data for employees Callahan and Daniel. The authorization request message is contained between the <PARAMARRAY> </PARAMARRAY> delimiters.

```
<?xml version="1.0"?>
<soapenv:Envelope xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/" xmlns:s⇒
oapenv="http://schemas.xmlsoap.org/soap/envelope/" xmlns:wsa="http://schemas.xmlsoa⇒
p.org/ws/2003/03/addressing/" xmlns:xsd="http://www.w3.org/2001/XMLSchema/" xmlns:x⇒
si="http://www.w3.org/2001/XMLSchema-instance/">
  <soapenv:Header xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/">
    <wsse:Security soap:mustUnderstand="1" xmlns:soap="http://schemas.xmlsoap.org/w⇒
sdl/soap/" xmlns:wsse="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wsse⇒
curity-secext-1.0.xsd">
      <wsse:UsernameToken>
        <wsse:Username>RODRIGO</wsse:Username>
      </wsse:UsernameToken>
    </wsse:Security>
  </soapenv:Header>
  <soapenv:Body xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/">
    <FindAccess xmlns="http://xmlns.oracle.com/Enterprise/Tools/schemas/PTCSSecurit⇒
yReq.v1">

    <PARAMARRAY>
      <PARAMS>
        <SERVICEID>1</ SERVICEID >
        <SERVICE_TYPE>UPGE</SERVICE_TYPE>
        <NODE>APP_B_NODE</NODE>
        <MENU>PERFORMANCE_MENU</MENU>
        <COMPONENT>PERFORMANCE_DTL_COMP</COMPONENT>
        <MARKET>GBL</MARKET>
        <COMP_ITEM_NAME>PERFORMANCE_DTL</COMP_ITEM_NAME>
        <KEYVAL>EMPLID=CALLAHAN</KEYVAL>
      </PARAMS>
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
      <PARAMS>
        <SERVICEID>2</SERVICEID >
        <SERVICE_TYPE>UPGE</SERVICE_TYPE>
        <NODE>APP_B_NODE</NODE>
        <MENU>PERFORMANCE_MENU</MENU>
        <COMPONENT>PERFORMANCE_DTL_COMP</COMPONENT>
        <MARKET>GBL</MARKET>
        <COMP_ITEM_NAME>PERFORMANCE_DTL</COMP_ITEM_NAME>
        <KEYVAL>EMPLID=DANIEL</KEYVAL>
      </PARAMS>
    </PARAMARRAY>

    </FindAccess>
  </soapenv:Body>
</soapenv:Envelope>
```

Example Security Handler

The PeopleTools security authorization service receives the message and first performs basic PeopleTools security authorization (user-role-permission list). If basic PeopleTools security authorization is valid for the requested object (a component, for example), the PeopleTools security authorization service will pass the request on to the security handler defined for this object. The PeopleTools security authorization service will encapsulate all the message elements such as user ID, node, component, and, key values into an AuthRequest object.

The following code provides an example security handler class that evaluates whether a user is authorized to see the performance details for a given employee ID. If the employee is a subordinate of the invoking user, then access granted; access is denied in all other instances such as a peer requesting performance data for a peer, an employee requesting access to his or her supervisor's performance data, or an employee requesting performance data from another department in the organization.

```
import PTCS_SECURITY:Security:*;

class SampleSecurityHandler extends PTCS_SECURITY:Security:SecurityHandler
   /*method AuthRequestHandler(&arrAuthReq As array of PTCS_SECURITY:Security:AuthR⇒
equest);*/
   method GetAuthorization(&arrAuthReq As array of PTCS_SECURITY:Security:AuthReque⇒
st);
   method isEmpSubordinate(&userid As string, &emplid As string) Returns boolean;
end-class;

/*method AuthRequestHandler*/
method GetAuthorization
   /+ &arrAuthReq as Array of PTCS_SECURITY:Security:AuthRequest +/
   /+ Extends/implements PTCS_SECURITY:Security:SecurityHandler.GetAuthorization +/


   Local string &emplid;
   Local string &userid;
   Local integer &i;

   For &i = 1 To &arrAuthReq.Len

      &emplid = &arrAuthReq [&i].GetParameterValue("EMPLID");
      &userid = &arrAuthReq [&i].UserId;
      /* If the employee ID to which access is requested is a subordinate of the   ⇒
 */
      /* invoking uer, grant access; otherwise, deny access for all other requests.⇒
 */
      If %This.isEmpSubordinate(&userid, &emplid) Then
         &arrAuthReq [&i].Access = "T";
      Else
         &arrAuthReq [&i].Access = "F";
      End-If;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
   End-For;

end-method;


method isEmpSubordinate
   /+ &userid as String, +/
   /+ &emplid as String +/
   /+ Returns Boolean +/

   /* Use the organizational hierarchy to determine whether employee ID is a      *⇒
/
   /* subordinate of the invoking user.                                            *⇒
/
   /* The following example uses a simplified expression to make this              *⇒
/
   /* determination. In most organizations, this would not be a valid test.        *⇒
/

   If &userid > &emplid Then
      Return True
   Else
      Return False
   End-If;
end-method
```

Response Message

The preceding security handler class sets the Access property of the AuthRequest object to T when access is granted. It sets the Access property to F for requests that are not authorized. Then, the security handler class returns the AuthRequest object array to the PeopleTools security authorization service. The PeopleTools security authorization service returns a SOAP message similar to the following to the invoking application (Application A). The authorization request response is contained between the <PARAMARRAY> </PARAMARRAY> delimiters.

```
<?xml version="1.0"?>
<soapenv:Envelope xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/" xmlns:s⇒
oapenv="http://schemas.xmlsoap.org/soap/envelope/" xmlns:wsa="http://schemas.xmlsoa⇒
p.org/ws/2003/03/addressing/" xmlns:xsd="http://www.w3.org/2001/XMLSchema/" xmlns:x⇒
si="http://www.w3.org/2001/XMLSchema-instance/">
  <soapenv:Header xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/">
    <wsse:Security soap:mustUnderstand="1" xmlns:soap="http://schemas.xmlsoap.org/w⇒
sdl/soap/" xmlns:wsse="http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wsse⇒
curity-secext-1.0.xsd">
     <wsse:UsernameToken>
        <wsse:Username>RODRIGO</wsse:Username>
      </wsse:UsernameToken>
    </wsse:Security>
  </soapenv:Header>
  <soapenv:Body xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/">
    <FindAccess xmlns="http://xmlns.oracle.com/Enterprise/Tools/schemas/PTCSSecurit⇒
yReq.v1">

    <PARAMARRAY>
      <PARAMS>
         <SERVICEID>1</SERVICEID>
         <ACCESS>T</ACCESS>
      </PARAMS>

      <PARAMS>
         <SERVICEID>2</SERVICEID>
         <ACCESS>F</ACCESS>
      </PARAMS>
    </PARAMARRAY>
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
    </FindAccess>
  </soapenv:Body>
</soapenv:Envelope>
```

Related Links

"Developing the Security Authorization Service Application Class" (PeopleTools 8.54: Security Administration)

"Developing Request Messages for the Security Authorization Service" (PeopleTools 8.54: Security Administration)

"Working with Response Messages for the Security Authorization Service" (PeopleTools 8.54: Security Administration)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Chapter 44

Session Class

Understanding Session Class

PeopleTools provides a family of APIs for external access into the PeopleSoft system. The Session class is the root of the APIs. It controls access to the PeopleSoft system, controls the environment, and enables you to do error handling for all APIs from a central location.

The PeopleSoft APIs are intended to be used, and are supported, in the following environments.

- PeopleSoft Windows client with either an existing two-tier connection or an existing connection to an application server.
- Application Engine batch program.
- Non-PeopleSoft program connecting to an application server.

The PeopleSoft APIs are exposed to the following language environments:

- PeopleCode
- OLE/COM
- C/C++
- Java

The APIs that are accessible using a session object are:

- Component Interface Classes
- PortalRegistry Classes
- Query Classes
- Search Class
- Tree Classes

Note: Tree Classes are accessible only through PeopleCode.

A session object controls the following:

- Security and access to the PeopleSoft system.
- Errors and error handling .
- Regional settings (that is, internationalization) for language, dates, times, and numbers.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- Tracing.

Related Links

Understanding Component Interface Class
Understanding the Portal Registry
Understanding Query Classes
Understanding Session Class
Understanding Tree Classes

Security and Access to the PeopleSoft System

A session object controls security and access to the PeopleSoft system. You must "sign-on" to the PeopleSoft session with a valid user ID and password when you use the Connect method. In addition, there's an external authentication parameter that you can use with the connect.

Note: Additional authentication will be available after this release.

Error Handling

The session object handles error processing for all the APIs, such as Component Interfaces, the Query API, and so on. From the session object, you can check if there have been any errors.

Note: The exception to this is Subscription PeopleCode. All errors for Subscription PeopleCode get logged to the application message error table.

Error messages include system error messages or messages from the message catalog (a common set of error messages used by all PeopleSoft applications.) For a Component Interface, the session object level errors also contain any text errors that may have occurred from running ExecuteEdits.

On the session object, you can use the following properties to initially check for errors:

- ErrorPending indicates whether there are API errors
- WarningPending indicates whether there are API warnings

All errors are contained in the PSMessages collection. (The PSMessages property on a Session object returns this collection.)

Each item in this collection is a PSMessage object. A PSMessage object contains information about the specific error that has occurred, such as the explain text for the error, the message set number, and so on. (The type of information depends on the type of error.)

If the error was caused by a Component Interface, a contextual string is attached to the end of the Text property of the PSMessage object. This contextual string contains the exact location of the error, that is, which field in which data collection, on which row, caused the error. This string is also accessible (by itself) using the Source property.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

When errors are loaded into the PSMessages collection depends on the type of error. System errors (that is, errors in the connection to the PeopleSoft Session) are logged as they occur. When an API error is logged depends on the API, as some APIs can be run in either interactive mode (meaning errors are logged as they happen) or in non-interactive mode (so errors are logged only when a particular method is run.)

If you are using Visual Basic or another COM environment, the PeopleSoft API system raises a COM exception the first time ErrorPending changes from False to True. It will *not* raise another exception until the PSMessages collection is cleared, which sets ErrorPending back to False.

Note: If you've called an API from an Application Engine program, all errors are also logged in the Application Engine error log tables.

Related Links

Accessing a PSMessages Collection

Displaying Error Messages

Use the following PeopleCode to display messages from the PSMessage collection:

```
Local ApiObject &Session, &PSMessages;
   &Session = %Session;
   &PSMessages = &Session.PSmessages;
   If (&Session <> Null ) Then
       If &PSMessages.Count > 0 Then
               For &i = 1 To &PSMessages.Count
                  &MsgSetNbr = &PSMessages.Item(&i).MessageSetNumber;
                  &MsgNbr = &PSMessages.Item(&i).MessageNumber;
                  MessageBox( 0 , " ", &MsgSetNbr, &MsgNbr, "Message not found");
               End-For;
         &PSMessages.DeleteAll();
            End-If;
End-If;
```

Regional Settings

Regional settings enable the user to set the display of numbers, dates, times, and currencies to comply with usage in a specific locale. The session object exposes some of these values to the API through the RegionalSettings property. This property returns a regional settings object that has properties you can use to change these settings.

Related Links

Regional Settings Class Properties

Trace Settings

The PeopleSoft debug pages enables you to control the environment in which your PeopleTools session is running. These pages include:

- Trace PeopleCode

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- Trace SQL
- Trace Page

These pages enable you to select the SQL trace options and the PeopleCode trace options that you want. The TraceSettings object (assessable from a session object) lets you control many of the same options during your session.

Image: Trace PeopleCode page

This example illustrates the fields and controls on the Trace PeopleCode page. You can find definitions for the fields and controls later on this page.

Not every option on the debug pages is represented with a trace settings property.

Related Links

"Using Debug Utilities" (PeopleTools 8.54: System and Server Administration)

Session Object Declaration

All session objects are declared as type ApiObject. For example,

```
Local ApiObject &MYSESSION;
Global ApiObject &PSMessage;
```

The following session objects can be declared as Global or Component:

- Session
- PSMessages Collection
- PSMessage

All other session objects *must* be declared as Local.

In this section, we discuss the following topics:

- State considerations.
- Considerations for declaring conditions.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

State Considerations

In the PeopleSoft Pure Internet Architecture, all processing occurs on the server. If you do something in your PeopleCode program that causes a trip back to the user before the end of your PeopleCode program, the PeopleCode program *cannot*regain its state, that is, it can't reset local variables, and so on. This applies to all APIs that use the Session object.

If you must go back to the user before the end of your PeopleCode program, you must set all your objects to NULL before you go, or else you receive a runtime error.

For example, the following code causes an error:

```
&Session = %Session;
Rem &Session = Null;
WinMessage("Hello");
```

The following example does *not* cause an error:

```
&Session = %Session;
&Session = Null;
WinMessage("Hello");
```

Considerations for Declaring Collections

You *must* declare all collections for C/C++ and COM as objects, or else you receive errors at runtime.

For example if you're using RegionalSettings, include the following your declarations for a VB program:

```
Dim oRegionalSettings As Object
```

Then, use the following code to populate this variable:

```
Set oRegionalSettings = oCISession.RegionalSettings
oRegionalSettings.LanguageCd = "GER"
```

Scope of a Session Object

A Session can be instantiated from PeopleCode, from a Visual Basic program, from C++, COM, and so on.

See the example section in Connect for more details.

This object can be used anywhere you have PeopleCode, that is, in Application Engine PeopleCode, record field PeopleCode, and so on.

Session Class Built-in Function

"%Session" (PeopleTools 8.54: PeopleCode Language Reference)

"GetSession" (PeopleTools 8.54: PeopleCode Language Reference)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Session Class Methods

In this section, we discuss the Session class methods. The methods are discussed in alphabetical order.

Connect

Syntax

```
(version, {"EXISTING" | //PSoftApplicationServer:JoltPort}, UserID, Password, ExtAuth)
```

Description

The Connect method connects a session object to a PeopleSoft application server.

Note: This function remains for backward compatibility only. Use the %Session system variable to return a reference of a session object instead.

If you already have a PeopleSoft session running (you are already connected to a PeopleSoft application server and are running a component, and so on) you must specify EXISTING, and not the *// PSoftApplicationServer:JoltPort*. Typically, use the parameter value of EXISTING from PeopleCode, not from other language environments.

If you are using an existing connection to the application server, you *cannot*specify a different user ID or password. If you don't specify these values as NULL string, you must specify the exact same user ID (and password) as the one that originally started the session.

Parameters

version	Specify the API version that the client is expecting. Future releases will use this parameter. For now, you must use a 1.
EXISTING | *// PSoftApplicationServer:JoltPort*	Specify EXISTING if you're currently connected to an application server. Otherwise, specify the named application server machine and the IP port to connect to on an application server machine.
UserID	Specify the PeopleSoft user ID to use for the connection. This must be a valid user ID. If you are using an existing connection, you can specify a NULL string (that is, two quotation marks with no blank space between them ("")) for this parameter.
Password	Specify the password associated with the user ID to use for the connection. This must match the password assigned for this user ID *exactly*. If you are using an existing connection, you can specify a NULL string (that is, two quotation marks with no blank space between them ("")) for this parameter.
ExtAuth	This parameter is required, but it is unused in this release. You must enter a 0 for this parameter.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

A Boolean value: True if the connection completed successfully, False otherwise.

Example

The following is an example of the code you would use if there is an existing connection to the application server:

```
Local ApiObject &MYSESSION;

&MYSESSION = GetSession();
&MYSESSION.Connect(1, "EXISTING", "", "", 0);
```

The following is an example connecting to a PeopleSoft system using a Visual Basic program. It first checks for error messages. If there are any errors, the text of the error is displayed to the user.

```
On Error GoTo eMessage

    Dim oSession As Object
    Dim oPSMessage As Object

    Dim oBC As Object

    Set oSession = CreateObject("PeopleSoft.Session")

    oSession.Connect 1, "//PSSOFTO061998:7000", "PTDMO", "PTDMO", 0

    &lsquo;Application Specific Processing

eMessage:
    If (oSession.PSMessages.Count > 0) Then
        For i = 1 To oSession.PSMessages.Count
           Set oPSMessage = oSession.PSMessages.Item(i)
           MsgBox (oPSMessage.Text)
        Next i
    End If
```

Related Links

"%Session" (PeopleTools 8.54: PeopleCode Language Reference)

Disconnect

Syntax

Disconnect()

Description

The Disconnect method disconnects the session associated with the session object executing the method from that PeopleSoft session.

This method returns a Boolean value: True if successfully disconnected, False otherwise.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

API Instantiation Methods

The following is a list of the other methods used with the session object to instantiate an API object such as a Component Interface, a tree structure, and so on.

Component Interface:

- FindCompIntfcs(*ComponentName*): returns a collection of component interfaces based on the partial Component Interface name.
- GetCompIntfc(**COMPINTFC.***ComponentName*): returns a Component Interface object.
- ValidateCompIntfc(*ComponentInterfaceName*): indicates the success or failure of component interface validations.

Portal Registry:

- FindPortalRegistries(*partial_name*): returns a collection of PortalRegistry objects.
- GetLocalNode(): returns a node object.
- GetNodes(): returns a collection of node objects.
- GetPortalRegistry(): returns a PortalRegistry object.
- GetRemoteNodes(): returns a collection of node objects.
- GetActualRemoteNodes(): returns a collection of remote node objects only.

Query:

- FindQueryDBRecords():returns a reference to a QueryDBRecord collection, filled with zero or more records.
- FindQueries():returns a reference to a Query collection, filled with zero or more queries.
- FindQueriesDateRange(*StartDateString*, *EndDateString*): returns a reference to a Query collection, filled with zero or more queries that match the specified date range.
- GetQuery(): returns a query object.
- GetQuerySecurityProfile(): a QuerySecurityProfile object.
- SearchQueryDBRecord(*SearchType*, *Pattern*, *CaseSensitive*): returns a QueryDBRecord collection.
- SearchPrivateQueries(*QueryType, SearchType*, *Pattern*, *CaseSensitive*): a query collection.
- SearchPublicQueries(*QueryType, SearchType*, *Pattern*, *CaseSensitive*): a query collection.

Search:

- GetSearchIndexes(): returns a SearchIndexes collection.
- GetSearchQuery(): returns a search query object.

Tree:

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- GetTree(): returns a tree object.
- GetTreeStructure(): returns a tree structure object.

Session Class Properties

This section describes the Session class properties. The properties are discussed in alphabetical order.

ErrorPending

Description

This property indicates whether there are any error messages pending for the API that is currently running. After this property has been set, it returns True until the PSMessages collection is cleared (or deleted.)

This property is read-only.

Example

```
If &MYSESSION.ErrorPending Then
   &COUNT = &MYSESSION.PSMessages.Count;
   For &I = 1 To &COUNT
      &ERROR = &MYSESSION.PSMessages.Item(&I);
      &TEXT = &ERROR.Text;
      WinMessage("Error text " | &TEXT);
   End-For;

&MYSESSION.PSMessages.DeleteAll();
```

PSMessages

Description

This property returns a reference to a PSMessages collection object. If there are no messages, this property returns an object reference to PSMessages with a count of zero.

This property is read-only.

Example

```
If &SESSION.PSMessages.Count > NULL Then
   /* there are messages do processing */
End-if;
```

Related Links

PSMessages Collection Methods

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

PSMessagesMode

Description

This property is used to determine how messages are output. This property takes either a numeric value or a constant. The default value is 1 (%PSMessages_CollectionOnly).

You must set this property before you check the type of message, that is, you can't check the type of message, then decide how it's displayed.

This property sets the value for the session. You can change modes during a session, such as, if you're starting a Component Interface. However, after you run the Component Interface, you should set the value back. For example:

```
&OldMode = &Session.PSMessageMode;
&Session.PSMessagesMode = 1;
...
&Session.PSMessagesMode = &OldMode;
```

You can specify either a numeric value or a constant. The values are:

Numeric Value	*Constant Value*	*Description*
0	%PSMessages_None	None.
1	%PSMessages_CollectionOnly	PSMessage Collection only (default).
2	%PSMessages_MessageBoxOnly	Message box only.
3	%PSMessages_Both	Both collection and message box.

Note: If you set this property to 0 (%PSMessages_None), *all* messages are ignored. Use this option with caution.

This property is read-write.

Example

```
Local ApiObject &SESSION;

&SESSION = %Session;
&MMODE = &SESSION.PSMessagesMode;
&SESSION.PSMessagesMode = %PSMessages_MessageBoxOnly;
```

RegionalSettings

Description

This property returns a reference to a RegionalSettings collection object.

This property is read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

Regional Settings Class Properties

Repository

Description

This property returns a reference to a Repository object.

Related Links

Understanding the PeopleSoft API Repository

SuspendFormatting

Description

This property turns off the PeopleSoft automatic formatting when coercing a string into a field. Formatting is typically necessary for external Component Interface users (such as for a Visual Basic program,) yet should be suspended for a PeopleCode program. You should not typically need to set this value yourself, as it's set appropriately based on where the session object is created.

This property takes a Boolean value: True means formatting is suspended, False means it isn't suspended. If you start your session from a PeopleCode program, the default for this property is True. If you don't start the session from a PeopleCode program, the default is False.

This property is read-write.

TraceSettings

Description

This property returns a reference to a TraceSettings collection object.

This property is read-only.

Related Links

Trace Setting Class Properties

WarningPending

Description

This property indicates whether there are any warning messages pending for the API that is currently running.

This property is read-only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Accessing a PSMessages Collection

Use the PSMessages collection to return all of the messages that occur during the session. The following example finds all the messages listed in the PSMessages collections when the Component Interface Save methods fails. The example assumes that &CI is the Component Interface object reference.

```
If Not &CI.Save() Then
   /* save didn&rsquo;t complete */
   &COLL = &MYSESSION.PSMessages;
   For &I = 1 to &COLL.Count
      &ERROR = &COLL.Item(&I);
      &TEXT = &ERROR.Text;

      /* do message processing */

   End-For;
&COLL.DeleteAll(); /* Delete all messages in queue */
End-if;
```

As you evaluate each message, delete it from the PSMessages collection. Or, delete all the messages in the queue at once using DeleteAll.

If there are multiple errors when saving a Component Interface, all errors are logged to the PSMessages collection, not just the first occurrence of an error.

Considerations for Declaring Collections

You *must* declare all collections for C/C++ and COM as objects, or else you receive errors at runtime.

PSMessages Collection Methods

This section describes the PSMessages collection methods. The methods are discussed in alphabetical order.

DeleteAll

Syntax

DeleteAll()

Description

The DeleteAll method deletes all the PSMessage objects in the PSMessages collection executing the method. You should use this property after you have processed all the errors in the collection. This method also resets the status of ErrorPending to False.

Returns

This method returns a Boolean value: True if all PSMessages in the collection were successfully deleted, False otherwise.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

ErrorPending

DeleteItem

Syntax

DeleteItem(*number*)

Description

The DeleteItem method deletes the PSMessage object that exists at the *number* position in the PSMessages collection executing the method.

Parameters

number	Specify the position number in the collection of the PSMessage object that you want to delete. All other items within the collection are renumbered.

Returns

This method returns a Boolean value: True if the PSMessage object was successfully deleted, False otherwise.

Example

```
&ERROR.DeleteItem(&I);
```

First

Syntax

First()

Description

The First method returns the first PSMessage object in the PSMessages collection object executing the method.

Example

```
&ERROR = &PSMESSAGE.First();
```

Item

Syntax

Item(*number*)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

The Item method returns a PSMessage object that exists at the *number* position in the PSMessages collection executing the method

Parameters

number	Specify the position number in the collection of the PSMessage object that you want returned.

Returns

A reference to a PSMessage object, NULL otherwise.

Example

```
&PSMSGCOL = &SESSION.PSMessages;
For &I = 1 to &PSMSGCOL.Count;
   &PSMESSAGE = &PSMSGCOL.Item(&I);
   /* do error processing */
End-For;
```

Next

Syntax

```
Next()
```

Description

The Next method returns the next PSMessage object in the PSMessages collection object executing the method. You can use this method only after you have used either the First or Item methods: otherwise the system doesn't know where to start.

PSMessages Collection Property

This section describes the PSMessages collection property.

Count

Description

This property returns the number of PSMessage objects in the PSMessages collection object.

This property is read-only.

Example

```
&COUNT = &PSMESSAGE.Count;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

PSMessage Class Properties

This section describes the PSMessages class properties. The properties are discussed in alphabetical order.

ExplainText

Description

This property returns the explanation text (as a string) for the error message associated with the PSMessage object. You can use this property in conjunction with the MessageNumber property (which contains the error message number) and the MessageSetNumber property (which contains the error message set number.)

Note: ExplainText should be accessed only when necessary because it requires a second database read or application server roundtrip.

This property is read-only.

MessageNumber

Description

This property returns the error message number (as a number) for the error message associated with the PSMessage object. You can use this property in conjunction with the MessageSetNumber property (which contains the error message set number) and the ExplainText property (which contains text explaining the error.)

This property is read-only.

MessageSetNumber

Description

This property returns the error message set number (as a number) for the error message associated with the PSMessage object. You can use this property in conjunction with the MessageNumber property (which contains the error message number) and the ExplainText property (which contains text explaining the error.)

This property is read-only.

MessageType

Description

This property indicates the type of the message, whether it's from the message catalog, if it's a warning, error, or information error.

This property returns a numeric value. The values are:

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Value	*Description*
0	Message is not a message catalog entry or there is no message.
1	Message has a severity of Error.
2	Message has a severity of Warning.
3	Message has a severity of Information.

This property is read-only.

Source

Description

This property returns a string indicating the actual field that's in error. The syntax of the string that's returned is as follows:

```
ComponentInterfaceName.[CollectionName(Row).[CollectionName(Row).[CollectionName(Ro⇒
w)]]].PropertyName
```

Image: Sample Component Interface

The following image is an example of Sample Component Interface. The string here is also returned as part of the Text property.

For example, suppose you had a Component Interface named EMPL_CHKLST_CI.

The following indicates that the first level field, EMPLID, has the error:

```
EMPL_CHKLST_CI.EMPLID
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The Component Interface EMPL_CHKLST_BC has a data collection (scroll) called EMPL_CHKLST_ITM. Suppose that it has 3 rows, and the STATUS_DT field was in error. The **Source** property would return the following string:

```
EMPL_CHKLST_CI.EMPL_CHKLST_ITM(3).STATUS_DT
```

You can use the Source property in conjunction with the MessageNumber property (which contains the error message number), the MessageSetNumber property (which contains the error message set number), the ExplainText property (which contains text explaining the error), and the Text property (which contains the text of the message.)

This property is read-only.

Example

The following example code finds the error messages and displays them to the user. It finds the field that caused the error and displays that also.

```
Local ApiObject &PSMESSAGE;
Local Boolean &FIND;
Local string &SOURCE, &FIELD, &TEXT;
Local number &START, &LEN, &NSTART, &FLEN;
.
.
.
For &I = 1 to &SESSION.PSMessages.Count;
   &PSMESSAGE = &SESSION.PSMessages.Item(&I);
   /* only display errors, not warnings, to user */
   If &PSMESSAGE.Type = 1 Then
      &TEXT = &PSMESSAGE.Text;
      /* find name of field in error */
      &SOURCE = &PSMESSAGE.Source;
      &LEN = Len(&SOURCE);
      /* find last dot before field */
      &FIND = False;
      &START = Find(".", &SOURCE);
      While Not (&FIND)
         &NSTART = Find(".", &SOURCE, &START + 1);
            If &NSTART = 0 Then
               &FIND = True;
            Else
               &START = &NSTART;
            End-If;
         End-While;
         &FLEN = &LEN - &START;
         &FIELD = Substring(&SOURCE, &START + 1, &FLEN);
         /* display text and field to user */
         Winmessage("You received the following error: " | &TEXT | "For field " | &⇒
FIELD);
   End-If;
End-For;
```

Text

Description

This property returns the text of the message (as a string) for the error message associated with the PSMessage object. It also includes a contextual string that contains the name of the field that generated the error. The contextual string has the following syntax:

```
{ComponentInterfaceName.[CollectionName(Row).[CollectionName(Row).[CollectionName(R⇒
ow)]]].PropertyName}
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The contextual string (by itself) is available using the Source property of the PSMessage.

You can use the Text property in conjunction with the MessageNumber property (which contains the error message number), the MessageSetNumber property (which contains the error message set number), and the ExplainText property (which contains text explaining the error.)

This property is read-only.

Example

```
Local ApiObject &MYSESSION, &COL, &ERROR;
Local string &TEXT;
.
.
.
If &MYSESSION.ErrorPending Then
   /* received error */
   &COLL = &MYSESSION.PSMessages;
   For &I = 1 to &COLL.Count
      &ERROR = &COLL.Item(&I);
      &TEXT = &ERROR.Text;
         /* do error processing */
      End-For;
End-if;
```

Related Links

Source

Regional Settings Class Properties

This section describes the regional settings class properties. The properties are discussed in alphabetical order.

ClientTimeZone

Description

This property specifies the client time zone. This property takes a string value.

This property is read-write.

CurrencyFormat

Description

This property specifies how currency values are displayed. This property takes a number value. The default value is 1.

In the following values, @ represents the character specified with the CurrencySymbol property.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Value	*Description*
0	@1.1
1	1.1@
2	@.1.1
3	1.1.@

This property is read-write.

CurrencySymbol

Description

This property specifies the currency symbol. This property takes a string value. The default value is "$".

This property is read-write.

DateFormat

Description

This property specifies the date format defaults. PeopleTools supports the Short Date Format specification (MDY, DMY, or YMD), and the Date separator setting. When you add a Date field in a record definition, you indicate whether you want to display the century. PeopleTools Date and DateTime fields always show leading zeros for month, day, and year.

This property takes a number value. The values for this property are:

Value	*Description*
0	MDY (default)
1	DMY
2	YMD
3	Default value on system

This property is read-write.

DateSeparator

Description

This property specifies the character used to separate the month, day, year in the date. This property takes a string value. The default value is "/".

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-write.

DecimalSymbol

Description

This property specifies the character used to separate the fractional of the number from the whole. This property takes a string value. The default value for this property is ".".

Note: If you change the value of this property to a comma (,), you should adjust the DigitGroupingSymbol to a different character or some applications may not operate correctly.

This property is read-write.

DigitGroupingSymbol

Description

This property specifies the character used as a thousand or other grouping separator. This property takes a string value. The default value for this property is ",".

This property is read-write.

LanguageCD

Description

This property specifies the language to be used for the transaction. This property takes a string value. The default value for this property is the user's base language.

This property is read-write.

Note: If you change this value dynamically using PeopleCode, this value will *not* change back to the original value when you disconnect. You must manually set it back to the original value.

Example

The following example sets the language code, then at the end of the program, sets it back to the original value.

```
Local ApiObject &SESSION;
Local ApiObject &CI;

/** Get Session ApiObject **/
&SESSION = %Session;

/** Get Message ApiObject **/
&MSG = %IntBroker.GetMessage();
&RS = &MSG.GetRowset();

/** Get Component Interface **/
&CI = &SESSION.GetCompIntfc(compIntfc.NAMES_CI);

&REG_LNG = &SESSION.RegionalSettings.LanguageCd;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
For &TRANS_NUM = 1 To &RS.RowCount

/** Store Language Code in Temp Var **/
&LNG = &RS(&TRANS_NUM).PSCAMA.LANGUAGE_CD.Value;

/** Set the Language for this Transaction **/
If &LNG <> &REG_LNG Then
&SESSION.RegionalSettings.LanguageCd = &LNG;
End-If;
/* application specific processing */

&SESSION.RegionalSettings.LanguageCd = &REG_LNG;
&SESSION.Disconnect();
End-For
```

UseLocalTime

Description

This property specifies whether the local time zone of the client should be used to format time fields. This property takes a Boolean value. The default value is True.

This property is read-write.

1159Separator

Description

This property specifies the morning designator. This property takes a string value up to five characters. The default value is AM.

Use the 2359Separator property to specify the afternoon designator.

This property is read-write.

Considerations Using the 1159Separator Property

You cannot use this property as you would other properties. You must use the ObjectGetProperty function for accessing the property. For example:

```
Local ApiObject &SESSION;
Local ApiObject &reg;

/** Get Session ApiObject **/
&SESSION = %Session;
&reg = &SESSION.RegionalSettings;

&REG_LNG = &SESSION.RegionalSettings.LanguageCd;
&MornDesigination = ObjectGetProperty(&reg, "1159Separator");
```

Related Links

"ObjectGetProperty" (PeopleTools 8.54: PeopleCode Language Reference)

2359Separator

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

2359Separator

Description

This property specifies the afternoon designator. This property takes a string value up to five characters. The default value is PM.

Use the 1159Separator property to specify the morning designator.

This property is read-write.

Considerations Using the 2359Separator Property

You cannot use this property as you would other properties. You must use the ObjectGetProperty function for accessing the property. For example:

```
Local ApiObject &SESSION;
Local ApiObject &reg;

/** Get Session ApiObject **/
&SESSION = %Session;
&reg = &SESSION.RegionalSettings;

&REG_LNG = &SESSION.RegionalSettings.LanguageCd;
&AfternoonDesigination = ObjectGetProperty(&reg, "2359Separator");
```

Related Links

"ObjectGetProperty" (PeopleTools 8.54: PeopleCode Language Reference)

1159Separator

Trace Setting Class Properties

Each of the following properties relates to the debug pages in PeopleTools.

This section describes the trace setting class properties. The properties are discussed in alphabetical order.

Related Links

"Using Debug Utilities" (PeopleTools 8.54: System and Server Administration)

API

Description

This property is part of the PeopleSoft API trace and sets the API Information value.

This property takes a Boolean value: True means the trace will be run, False means it won’t.

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

COBOLStmtTimings

Description

This property is part of the SQL trace and sets the COBOL Statement Timings value.

This property takes a Boolean value: True means the trace will be run, False means it won't.

This property is read-write.

ConnDisRollbackCommit

Description

This property is part of the SQL trace and sets the Connect, disconnect, rollback, and commit value.

This property takes a Boolean value: True means the trace will be run, False means it won't.

This property is read-write.

DBSpecificCalls

Description

This property is part of the SQL trace and sets the Database API-specific Calls value.

This property takes a Boolean value: True means the trace will be run, False means it won't.

This property is read-write.

ManagerInfo

Description

This property is part of the SQL trace and sets the Manager Information value.

This property takes a Boolean value: True means the trace will be run, False means it won't.

This property is read-write.

NetworkServices

Description

This property is part of the SQL trace and sets the Network Services value.

This property takes a Boolean value: True means the trace will be run, False means it won't.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

NonSSBs

Description

This property is part of the SQL trace and sets the All Other API Calls besides SSBs value.

This property takes a Boolean value: True means the trace will be run, False means it won't.

This property is read-write.

OutputUNICODE

Description

This property specifies if the trace file is written in ANSI or UNICODE (for example, Output Unicode Trace File).

This property takes a Boolean value: True means the file will be written in UNICODE, False means it will be ANSI.

This property is read-write.

PCExtFcnCalls

Description

This property is part of the PeopleCode trace and sets the Trace External Function Calls value.

This property takes a Boolean value: True means the trace will be run, False means it won't.

This property is read-write.

PCFcnReturnValues

Description

This property is part of the PeopleCode trace and sets the Show Function Return Value value.

This property takes a Boolean value: True means the trace will be run, False means it won't.

This property is read-write.

PCFetchedValues

Description

This property is part of the PeopleCode trace and sets the Show Fetched Values value.

This property takes a Boolean value: True means the trace will be run, False means it won't.

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

PCIntFcnCalls

Description

This property is part of the PeopleCode trace and sets the Trace Internal Function Calls value.

This property takes a Boolean value: True means the trace will be run, False means it won't.

This property is read-write.

PCListProgram

Description

This property is part of the PeopleCode trace and sets the List the Program value.

This property takes a Boolean value: True means the trace will be run, False means it won't.

This property is read-write.

PCParameterValues

Description

This property is part of the PeopleCode trace and sets the Show Parameter Values value.

This property takes a Boolean value: True means the trace will be run, False means it won't.

This property is read-write.

PCProgramStatements

Description

This property is part of the PeopleCode trace and sets the Trace Each Statement in Program value.

This property takes a Boolean value: True means the trace will be run, False means it won't.

This property is read-write.

PCStack

Description

This property is part of the PeopleCode trace and sets the Show Stack value.

This property takes a Boolean value: True means the trace will be run, False means it won't.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

PCStartOfPrograms

Description

This property is part of the PeopleCode trace and sets the Trace Start of Programs value.

This property takes a Boolean value: True means the trace will be run, False means it won't.

This property is read-write.

PCTraceProgram

Description

This property is part of the PeopleCode trace and sets the Trace Evaluator Instructions value.

This property takes a Boolean value: True means the trace will be run, False means it won't.

This property is read-write.

PCVariableAssignments

Description

This property is part of the PeopleCode trace and sets the Show Assignments to Variables value.

This property takes a Boolean value: True means the trace will be run, False means it won't.

This property is read-write.

RowFetch

Description

This property is part of the SQL trace and sets the Row Fetch value.

This property takes a Boolean value: True means the trace will be run, False means it won't.

This property is read-write.

SQLStatement

Description

This property is part of the SQL trace and sets the SQL Statement value.

This property takes a Boolean value: True means the trace will be run, False means it won't.

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SQLStatementVariables

Description

This property is part of the SQL trace and sets the SQL Statement Variables value.

This property takes a Boolean value: True means the trace will be run, False means it won't.

This property is read-write.

SSBs

Description

This property is part of the SQL trace and sets the Set Select Buffers value.

This property takes a Boolean value: True means the trace will be run, False means it won't.

This property is read-write.

SybBindInfo

Description

This property is part of the SQL trace and sets the Sybase Bind Information value.

This property takes a Boolean value: True means the trace will be run, False means it won't.

This property is read-write.

SybFetchInfo

Description

This property is part of the SQL trace and sets the Sybase Fetch Information value.

This property takes a Boolean value: True means the trace will be run, False means it won't.

This property is read-write.

TraceFile

Description

This property specifies the location of the trace file (that is, PeopleTools Trace File value.)

This property takes a string value.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Chapter 45

SOAPDoc Class

Understanding theSOAPDoc Class

The Simple Object Access Protocol (SOAP) is a lightweight protocol for defining synchronous messages in a distributed Web environment. It's an XML based protocol that can be used in combination with other protocols such as HTTP using URLs as endpoints for a message. SOAP is an application of XML and XML namespaces and optionally uses XML Schemas.

Image: SOAP is an application built with XML and HTTP technologies

SOAP is an industry standard, defined by the World Wide Web Consortium (W3C), that defines an XML grammar for identifying a method name and the method parameters and for returning the results.

More specific information about SOAP can be found in the W3C specification on SOAP. The SOAP serialization rules can also be found in the complete specifications and aren't outlined in this topic. Also included in the W3C specification are sections on using SOAP with HTTP, which is also outside the domain of this topic. You can also send and receive HTTP messages through the Integration Gateway.

Related Links

"Understanding Sending and Receiving Messages" (PeopleTools 8.54: Integration Broker)

SOAP Message Exchange Model

SOAP messages are always synchronous. They can implement Request/Response synchronous messages with the response having the output parameters returned in another SOAP document to the sender.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SOAP supports HTTP-POST and HTTP-GET formats. PeopleSoft supports only HTTP, using the Integration Gateway.

Processing the message requires validation of the mandatory sections of the SOAP XML document and understanding SOAP namespaces.

SOAP Message Document

A SOAP Message is an ordinary XML document that consists of the following parts:

- A mandatory SOAP envelope.
- An optional SOAP header.
- A mandatory SOAP body.

SOAP Message Part	*Description*
SOAP Envelope	Is the top element of the XML document representing the message. It defines the content of the message, as well as the framework of what is in a message, how to process it, who should deal with it and whether it is optional or mandatory.
SOAP Header	Contains header information, and attributes that can be set to encode and further identify the type of processing as well as additional features of the message. This portion is optional.
SOAP Body	Contains the call and response information intended for the recipient of the message. A SOAP Fault element can appear in the body of the SOAP message to carry error or status information.

Image: SOAP parts in an XML document

The following image illustrates SOAP parts in an XML document.

The following are *required* for a SOAP message:

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- Encoded using XML.
- Have a SOAP envelope.
- Have a SOAP body.
- Use the SOAP encoding and envelope namespaces.

The following are optional for a SOAP message:

- SOAP Header.
- XML Schema use.

The following are *invalid* for a SOAP message:

- DTD references.
- XML Processing Instructions.
- XML CData Sections.

The SOAPDoc Class

The SOAPDoc class is a separate class in PeopleCode that works similarly to the XmlDoc and XmlNode classes. Many of the same methods and properties that work with an XmlDoc or XmlNode object also work with a SOAPDoc object. However, there are also methods and properties that don't apply to a SOAPDoc object.

The following XmlDoc and XmlNode methods do *not* apply to a SOAPDoc object:

- AddCDataSection
- AddProcessInstruction
- CopyToPSFTMessage
- CreateDocumentType
- InsertCDataSection
- InsertProcessInstruction
- LoadIBContent

If a Merchant Profile has been created it can be used with the SOAPDoc class and the Message class. You can use the XmlDoc property to convert the message object to an SOAPDoc object, then use the SOAPDoc methods and properties, as well as the XmlDoc methods and properties that are applicable.

You can only use the message object when the XmlDoc object is structured.

It should be noted that a SOAPDoc object is really an extension of the XmlDoc class. You have the option of getting portions of the SOAPDoc–like the body node–and accessing it or manipulating it as if it were a standard element in an XML document, because in actuality it is.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SOAPDoc Object Creation

There are a few steps to creating a SOAPDoc. The following is an overview of these steps. More detail about the methods and properties mentioned in this section can be found in the reference section of this topic.

SOAP Header Section

Because the SOAP header is optional, the header is not validated when you use the ValidateSOAPDoc method.

A SOAP header must be added *before* any other parts of the SOAPdoc.

Use the AddHeader method to add a header to a SOAPDoc.

Use the HeaderNode property to access an existing SOAPDoc header.

After you have a reference to the header, you can use XmlDoc methods to read the contents of the header (like any node.)

Related Links

AddHeader
HeaderNode

SOAP Envelope Section

A SOAP envelope is a required portion of the XML Message and is generated automatically using the SOAP schema as specified by SOAP W3C.

A SOAP envelope must be added *before* you add a SOAP body or a SOAP method. This is an optional method. You need to use this method only if you need to set any additional attributes for the Envelope section. The default SOAP schemas are added automatically.

To set additional custom attributes or schemas on the Envelope element, use the AddEnvelope method. This method adds the envelope element tags and the default schemas for either SOAP or UDDI depending on the value of the parameter passed in. The default encoding styles are also set here. Only one envelope section can be set within one PeopleSoft SOAP XmlDoc.

The SOAPDoc adds only a default URL to the envelope. For some UDDI sites, you may need to add a specific schema yourself. To do this, generate the envelope with no schema, then access the envelope section and add the specific schema URL using the AddAttribute method.

Related Links

AddEnvelope

SOAP Body Section

The body is the XmlDoc where the method is defined. The method AddBody starts the body section of the XML SOAPDoc and must be in the XmlDoc before adding in method sections of the message. Only one body section can be set within one SOAPDoc. This is an optional method and must called only if

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

you need to set any additional attributes for the body section. Otherwise the body section is automatically generated in the XmlDoc.

The SOAP body must be added *after* you add the SOAP envelope, and *before* you add any methods.

Related Links

AddBody

SOAP Method Section

The AddMethod method adds the name of the method element being processed. Additional attributes for this method can be set using the AddAttribute and InsertAttribute XmlNode methods.

You don't have to specifically add a SOAP body section. The body is automatically added when you call the AddMethod method.

The AddParm method sets the parameters for the parameter element of the method as a name, value pair. Multiple parameters can be set and are used in the order that this method is called. If an XML Schema is defined, types can be used using the AddAttribute XmlNode method. Any number of parameter name-value pairs can be added for a method and are added to the XmlDoc in the order that the AddParm methods are called.

You can add parameters to a method only *after* you add the method. The parameters are added in the order you add them in the PeopleCode program.

Related Links

AddMethod
AddParm
AddAttribute

SOAPDoc Section Access

Use the following properties to access the different parts of a SOAPDoc object. All of these properties return an XmlNode object.

- BodyNode
- EnvelopeNode
- MethodNode

After you have access to the portion of the SOAPDoc that you want, use the XmlNode properties and methods to manipulate the SOAPDoc.

Use the XmlDoc property to convert a SOAPDoc object to an XmlDoc object, and vice-versa.

The MethodName property returns the name of the method in the SOAPDoc object.

Note: If you use the MethodName property, you receive only the method name, as a string, not a reference to an XmlNode object that represents the method.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Use the GetParmName and GetParmValue methods to get the name and the values in a SOAPDoc object for each output parameter. You must use the index number of the parameter you want with these methods. You can determine the total number of parameters with the ParmCount property.

Related Links

BodyNode
EnvelopeNode
MethodName
MethodNode
GetParmValue

PeopleCode to Create a SOAPDoc

The following is the order in which the Soap methods *must* be called in order to create a valid SOAPDoc.

```
&SOAPDoc = CreateSOAPDoc(); /* required */
&SOAPDoc.AddEnvelope(0); /* optional */
&SOAPDoc.AddBody(); /* optional */
&SOAPDoc.AddMethod("GetQuote", 1); /* required */
&SOAPDoc.AddParm("symbols", "PSFT");
&SOAPDoc.AddParm("format", "l1c1d1t1");
&OK = &SOAPDoc.ValidateSOAPDoc(); /* optional */
```

SOAPDoc Fault Section

In the body of a SOAP XML response document, you can define a fault section. Generally this is used if in an inbound message has been processed and some sort of error occurred. The text of the message gives further information about the error.

Use the AddFault method to add a fault code and a fault string to the body of a SOAPDoc. Only one fault section can be set within one SOAP XML document.

If you receive a response message that contains a fault, use the FaultCode and FaultString methods to return these values.

Related Links

AddFault
FaultCode
FaultString

The ValidateSOAPDoc Method

Use the ValidateSOAPDoc method to validate the SOAP document for correctness as follows:

- Encoded using XML.
- Has SOAP envelope.
- Has SOAP Body.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- Has a SOAP Method.
- Used SOAP encoding and envelope namespaces.

Related Links

ValidateSOAPDoc

SOAPDoc Objects and Messages

To publish the data of a SOAPDoc, you must first transform the SOAPDoc into an XmlDoc object by using the XmlDoc property. After you do this, you can use the XmlDoc object with the SyncRequestXmlDoc, PublishXmlDoc, or GetXmlDoc functions, to publish the data either synchronously or asynchronously.

All XmlDoc messages must be associated with a message definition. An XmlDoc message must be associated with an *unstructured* message, that is, a message definition that's created without any record definitions.

Use the SOAPDoc class if all of the following are true:

- Your third-party source or target node requires SOAP-compliant messages.
- Your third-party source or target node requires synchronous transactions.
- Your message conforms to the SOAP specification.

Related Links

Understanding XmlDoc Classes

"Understanding Sending and Receiving Messages" (PeopleTools 8.54: Integration Broker)

Data Type of a SOAPDoc Object

SOAPDoc objects are declared as type SOAPDoc. For example,

```
Local SOAPDoc &MyDoc;
```

```
Global SOAPDoc &SOAPDoc;
```

Scope of a SOAPDoc Object

A SOAPDoc object can only be instantiated from PeopleCode.

This object can be used anywhere you have PeopleCode, that is, in an application class, Application Engine PeopleCode, record field PeopleCode, and so on.

Note: Do not extend a SOAPDoc with an application class. This is currently not supported.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SOAPDoc Built-In Functions

"CreateSOAPDoc" (PeopleTools 8.54: PeopleCode Language Reference)

SOAPDoc Class Methods

In addition to the methods listed here, most of the XmlDoc and XmlNode class methods can be used with a SOAPDoc object. The methods are discussed in alphabetical order.

Related Links

Understanding XmlDoc Classes

AddBody

Syntax

AddBody()

Description

Use the AddBody method to add the body section of the SOAP XML document.

This method is optional when you're creating a SOAP document. Use it only if you must set any additional attributes for the body. Otherwise, the body section is automatically generated in the XML document.

If you're going to add a body section, you must do it *after* you've added the envelope section. If you are going to modify the body section, you must do this *before* you add the method sections of the SOAP XML document by calling the BodyNode property and using XmlNode methods and properties.

Note: Only one body section can be set within one Peoplesoft SOAP XML document.

Parameters

None.

Returns

None.

Example

From the following code:

```
&MyDoc.AddBody();
```

the following XML is created:

```
<SOAP-ENV:Body >
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
</SOAP-ENV:Body>
```

Related Links

AddMethod
AddEnvelope
AddAttribute

AddEnvelope

Syntax

AddEnvelope(*SOAP_Schema*)

Description

Use the AddEnvelope method to add the envelope element tags and the default schema. The default encoding styles are also set with this method.

Note: Only one envelope section can be set within one Peoplesoft SOAP XML document.

If you're going to be adding an envelope section, you must do this *before* you add the body section or any methods by calling the EnvelopeNode property and using XmlNode methods and properties.

Parameters

SOAP_Schema Specify whether to use the default SOAP schema or the UDDI schema. You can specify either a numeric value or a constant for this property. The values are:

Numeric Value	*Constant Value*	*Description*
0	%SOAP_Schema	Use the SOAP schema. Specifying this value adds the following attributes to the SOAP envelope: `xmlns:SOAP-ENV= "http://schemas.xmlsoap.org/soap/envelope/" xmlns:SOAP-ENV= "http://schemas.xmlsoap.org/soap/encoding/"`
1	%SOAP_UDDI	Use the UDDI schema. Specifying this value adds the following attribute to the SOAP envelope: `xmlns:SOAP-ENV= "urn:uddi-org:api"`

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Numeric Value	*Constant Value*	*Description*
2	%SOAP_Custom	Specify this value to add custom Namespace schemas to the SOAP envelope instead of the default SOAP schemas. **Note:** You must create the custom schema before you use it. See XML Schema. You must add the SOAP_ENV URI (as an attribute, using AddAttribute) before adding any other SOAP attributes. **Note:** For highly customized SOAP documents, PeopleSoft recommends using the XmlDoc class and creating the tags yourself.

Returns

None.

Example

The following example uses the default SOAP schema. The following PeopleCode program:

```
&MyDoc.AddEnvelope(%SOAP_Schema);
```

Creates the following XML:

```
<?xml version="1.0"?>

<SOAP-ENV:Envelope xmlns:SOAP-ENV= "http://schemas.xmlsoap.org/soap/envelope/"
xmlns:SOAP-ENV= "http://schemas.xmlsoap.org/soap/encoding/">

</SOAP-ENV:Envelope>
```

The following example creates an envelope and validates it.

The following PeopleCode program:

```
&soapReq = CreateSOAPDoc(); /* required */
/* manually add SOAP XML envelope, header, body, method and parameters */
/* &soapReq.AddHeader(); MUST come before any other section, but is optional */
&soapReq.AddEnvelope(%SOAP_Custom);
&EnvNode = &soapReq.EnvelopeNode;
&AddEnvelopeAttribute = &EnvNode.AddAttribute("xmlns:SOAP-ENV", "urn:MyCustomSchema⇒
.org");
&AddEnvelopeAttribute = &EnvNode.AddAttribute("xmlns:xsi", http://www.w3.org/2001/X⇒
MLSchema-instance);
&AddEnvelopeAttribute = &EnvNode.AddAttribute("xmlns:xsd", http://www.w3.org/2001/X⇒
MLSchema);
&AddEnvelopeAttribute = &EnvNode.AddAttribute("xmlns:soap", http://schemas.xmlsoap.⇒
org/soap/envelope/);
&soapReq.AddMethod("requestAccessCode", 1);
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
/* Validate the message */
MessageBox(%MsgStyle_OK, "", 0, 0, "Validate the message");
&OK = &soapReq.ValidateSOAPDoc();
MessageBox(%MsgStyle_OK, "", 0, 0, "Message Validated and &OK = " | &OK);

/* Convert SOAP XML to XML */
MessageBox(%MsgStyle_OK, "", 0, 0, "Sending the message next");

&string = &soapReq.GenXmlString();
MessageBox(%MsgStyle_OK, "", 0, 0, "SOAP XML = " | &string);
```

Creates the following XML:

```
<?xml version="1.0"?>
<SOAP-ENV:Envelope xmlns:xsd= "http://www.w3.org/2001/XMLSchema"
xmlns:xsi= "http://www.w3.org/2001/XMLSchema-instance"
xmlns:soap= "http://schemas.xmlsoap.org/soap/envelope/"
xmlns:SOAP-ENV= "urn:MyCustomSchema.org">
<SOAP-ENV:Body>
   <requestAccessCode/>
</SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

Related Links

AddBody

AddFault

Syntax

AddFault(*Fault_Code*, *Fault_String*)

Description

Use the AddFault method to add a fault code, with its corresponding fault string, to a SOAPDoc. Use this method only in a Response SOAP XML Document. The Envelope and Body sections of the XML Document are automatically added if they don't exist.

Parameters

Fault_Code Specify the fault code to add, as a string.

Fault_String Specify the fault string to add, as a sting.

The following fault codes are supported:

Fault Code	*Fault String*	*Description*
100	Version Mismatch	The XML version or SOAP version is not supported by the current implementation.
300	Client error	An error occurred on the client while processing the SOAP document.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Fault Code	*Fault String*	*Description*
400	Server error	An error occurred on the server while processing the SOAP document.

Returns

None.

Example

The following example program:

```
&SOAPDoc = CreateSOAPDoc();
&SOAPDoc.AddFault("400", "Server Error");


/* ===> The following statement executes this instance: */
&FaultCode = &SOAPDoc.FaultCode;
&FaultString = &SOAPDoc.FaultString;
&OK = &SOAPDoc.ValidateSOAPDoc();
```

Creates the following XML:

```
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/" SOAP-⇒
ENV:encodingStyle="http://schemas.xmlsoap.org/soap/encoding/">
- <SOAP-ENV:Body>
- <SOAP-ENV:Fault>
  <faultcode>400</faultcode>
  <faultstring>SOAP Server Error</faultstring>
  </SOAP-ENV:Fault>
  </SOAP-ENV:Body>
  </SOAP-ENV:Envelope>
```

Related Links

FaultCode
FaultString
FaultCodeS

AddHeader

Syntax

AddHeader()

Description

Use the AddHeader method to add the header section of the SOAP XML document.

This method is optional when you're creating a SOAP document. Use it only if you want to include a header in your SOAP XML document.

If you're going to add a header, you must do it *before* you've added any other sections, such as the envelope or the body.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

After you've created the header, you can access it using the HeaderNode property. Once you have a reference to the node, you must use the XmlDoc methods to add specifics to the header section such as encription, as well as any required child nodes.

Note: Only one header section can be set within one Peoplesoft SOAP XML document.

Parameters

None.

Returns

None.

Example

The following test adds a header section into a SOAP XML document where all sections are created explicitly:

```
Local SOAPDoc &Sdoc;
Local XMLNode &Node;

/* ===> Add inputs: */
&Sdoc = CreateSOAPDoc(); /* required */
&Sdoc.AddEnvelope(0); /* optional */
&Sdoc.AddHeader(); /* optional */
&Sdoc.AddBody(); /* optional */
&Sdoc.AddMethod("SOAPXml", 1); /* required */
&Sdoc.AddParm("symbols", "PSFT");

&OK = &Sdoc.ValidateSOAPDoc();

/*Append to TEMP file*/
&Xstring = &Sdoc.GenXmlString();
&myfile = GetFile("cmsDoc.xml", "A");
&myfile.WriteLine(&Xstring);
&myfile.Close();

&METHOD = &Sdoc.MethodName;
&ParmCnt = &Sdoc.ParmCount;
&HdrNode= &Sdoc.HeaderNode;

&HdrName = &HdrNode.NodeName; //returns SOAP-ENV:Header

/* Echo out the Returned Outputs */
out_BI_results("SOAP Header test 1");
out_BI_results(" ");
out_BI_results("Validated: " | &OK);
out_BI_results("Method: " | &METHOD);
out_BI_results("Parm Count: " | &ParmCount);
out_BI_results("Header : " | &HdrName);

out_BI_results("End-of-Test");
```

Related Links

HeaderNode

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

AddMethod

Syntax

AddMethod(*MethodName*, *IsRequest*)

Description

Use the AddMethod method to set the name of the method element being processed. Additional attributes for the added method can be set using the AddAttribute and InsertAttribute method. Executing AddMethod automatically adds any missing Envelope and Body sections.

Note: Only one method can be set within one Peoplesoft SOAP XML document.

The SOAPDoc method can be used only *after* the envelope and body sections have been added.

Set the parameters for the method using the AddParm method.

Parameters

MethodName Specify the name of the method element being added.

IsRequest Specify if the message is a request message. This parameter takes a numeric value:

- 1 if the message is a request message
- 0 if the message is a response message

Returns

None.

Example

The following sample program:

```
&MyDoc.AddMethod("GetPrice", 0);
```

Creates the following XML:

```
<GetPrice>

</GetPriceResponse>
```

The following sample program:

```
&MyDoc.AddMethod("GetPrice", 1);
```

Creates the following XML:

```
<GetPrice>

</GetPrice>
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

AddParm
MethodName
MethodNode
AddAttribute

AddParm

Syntax

AddParm(*ParmName*, *ParmValue*)

Description

Use the AddParm method to set the parameters for the parameter element of the current method. To set more than one parameter, use the method more than once. The parameters are set and used in the order that this method is called. Any number of parameter name-value pairs can be set for a method and are added to the XML document in the order that this method is called from the PeopleCode program.

Parameters

ParmName	Specify the name of the parameter as a string.
ParmValue	Specify the value of the parameter as a string.

Returns

None.

Example

The following PeopleCode:

```
&MyDoc.AddParm("Item", "Apples");
```

Creates the following XML:

```
<Item >Apples</Item>
```

Related Links

AddMethod

GetParmName

Syntax

GetParmName(*Index*)

Description

Use the GetParmName method access the parameter names for a method.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

Index	Specify the number of the parameter that you want to access. Values start at 1.

Returns

A string.

Example

```
For &I = 1 to &SOAPDoc.ParmCount

&ParmName = &SOAPDoc.GetParmName(&I);
&ParmValue = &SOAPDoc.GetParmValue(&I);

   /* Do processing */

End-For;
```

Related Links

GetParmValue

ParmCount

GetParmValue

Syntax

GetParmValue(*Index*)

Description

Use the GetParmValue method to access the parameter values for a method.

Parameters

Index	Specify the number of the parameter you want to access. Values start at 1.

Returns

A string.

Example

```
For &I = 1 to &SOAPDoc.ParmCount

&ParmName = &SOAPDoc.GetParmName(&I);
&ParmValue = &SOAPDoc.GetParmValue(&I);

   /* Do processing */

End-For;
```


Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

GetParmName
ParmCount

ValidateSOAPDoc

Syntax

ValidateSOAPDoc()

Description

Use the ValidateSOAPDoc method to validate the SOAP document for correctness as follows:

SOAP message is:

- Encoded using XML.
- Has SOAP envelope.
- Has SOAP body.
- Used SOAP encoding and envelope namespaces.

Returns

This method returns either a number or a constant. The values are:

Numeric Value	*Constant Value*	*Description*
0	%SOAP_Valid	The SOAPDoc is valid.
1	%SOAP_NoEnvelope	Missing or invalid envelope section in XML document.
2	%SOAP_InvalidEnvelope	Envelope has improper Namespace used. Should be: SOAP-ENV or SOAP-ENC
3	%SOAP_NoBody	Missing body section in XML document.
4	%SOAP_NoMethod	Missing or invalid method section in XML document.
6	%SOAP_InvalidXml	Invalid XML syntax in SOAPDoc.

Example

```
&Return = &MyDoc.ValidateSOAPDoc();
If &Return <> 0 Then
   /* do error processing */
End-if;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

FaultCode
FaultString

SOAPDoc Class Properties

In addition to the properties listed here, most of the XmlDoc and XmlNode class properties can be used with a SOAPDoc object. The properties are discussed in alphabetical order.

Related Links

Understanding XmlDoc Classes

BodyNode

Description

This property returns a reference to the body section of a SOAPDoc, as an XmlNode.

This property is read-only.

Related Links

Understanding XmlDoc Classes

EnvelopeNode

Description

This property returns a reference to the envelope section of a SOAPDoc, as an XmlNode.

This property is read-only.

Related Links

Understanding XmlDoc Classes

FaultCode

Description

Use the FaultCode property to return the fault code if the SOAP message has one. Not every message has a fault code. It is returned only when the SOAP method has had an error in processing *and* the SOAP method supports fault codes. This property returns a number.

If the fault code in the message cannot be converted to a number, the value 0 is returned. Use FaultCodeS to get the fault code value as a string.

This property is read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

```
Local SOAPDoc &MyDoc;
Local integer &Fault;

&MyDoc = CreateSOAPDoc();
&MyDoc.AddFault("400", "Server Error");

&Fault = &MyDoc.FaultCode;
```

Related Links

FaultString

FaultCodeS

AddFault

FaultCodeS

Description

Use the FaultCodeS property to return the fault code if the SOAP message has one. Not every message has a fault code. It is returned only when the SOAP method has had an error in processing *and* the SOAP method supports fault codes. This property returns a string.

This property is read-only.

Example

```
Local SOAPDoc &MyDoc;
Local string &Fault;

&MyDoc = CreateSOAPDoc();
&MyDoc.AddFault("400", "Server Error");

&Fault = &MyDoc.FaultCodeS;
```

Related Links

AddFault

FaultCode

FaultString

FaultString

Description

Use the FaultString property to return the fault string if the reply has one. Not every SOAP message has a fault string. It is only returned when the SOAP method has had an error in processing *and* the SOAP method supports fault strings.

Example

```
&Fault = &MyDoc.FaultString;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

FaultCode
FaultCodeS
AddFault

HeaderNode

Description

Use the HeaderNode property to return a reference to the header node. After you have a reference, you can use the XmlDoc methods to read and make changes to the node.

This property is read-write.

Example

The following test adds a header section, validates the SOAPDoc, then access the header.

```
Local SOAPDoc &Sdoc;
Local XMLNode &Node;

/* ===> Add inputs: */
&Sdoc = CreateSOAPDoc(); /* required */

&Sdoc.AddHeader(); /* optional */
&Sdoc.AddMethod("SOAPXml", 1); /* required */

&OK = &Sdoc.ValidateSOAPDoc();

/*Append to TEMP file*/
&Xstring = &Sdoc.GenXmlString();
&myfile = GetFile("cmsDoc.xml", "A");
&myfile.WriteLine(&Xstring);
&myfile.Close();

&METHOD = &Sdoc.MethodName;
&ParmCnt = &Sdoc.ParmCount;
&HdrNode= &Sdoc.HeaderNode; //returns SOAP-ENV:Header

&HdrName = &HdrNode.NodeName;

/* Echo out the Returned Outputs */
out_BI_results("SOAP Header test 1");
out_BI_results(" ");
out_BI_results("Validated: " | &OK);
out_BI_results("Method: " | &METHOD);
out_BI_results("Parm Count: " | &ParmCount);
out_BI_results("Header : " | &HdrName);

out_BI_results("End-of-Test");
```

Related Links

AddHeader

MethodName

Description

This property returns the name of the method of the SOAPDoc, as a string.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

If you want a reference to the method that you can work with, as an XmlNode, use the MethodNode property.

This property is read-only.

MethodNode

Description

This property returns a reference to the method section of a SOAPDoc, as an XmlNode.

If you want only the name of the method returned, use the MethodName property.

This property is read-only.

Related Links

Understanding XmlDoc Classes

ParmCount

Description

This property returns the total number of parameters for the method section in a SOAP XML document as a number.

This property is read-only.

Example

```
For &I = 1 to &SOAPDoc.ParmCount
   &ParmName = &SOAPDoc.GetParmName(&I);
   &ParmValue = &SOAPDoc.GetParmValue(&I);
   /* do processing */
End-For;
```

XmlDoc

Description

This property transforms a SOAPDoc object to an XmlDoc object. This is necessary only when sending or receiving a response message. You do *not* need to do this conversion to use the XmlDoc or XmlNode methods and properties.

This property is read-write.

Example

The following is an example of sending a SOAP message and receiving the response:

```
Local XmlDoc &request, &response;
Local string &strXml;
Local SOAPDoc &soapReq, &soapRes;

/* create the SOAP XML Document */
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
&soapReq = CreateSOAPDoc();
&soapReq.AddMethod("GetPrice");
&soapReq.AddParm("Item", "Apples");

/* convert SOAP to XmlDoc */
&request = &soapReq.XmlDoc;

/* Send the Request */
&response = SyncRequestXmlDoc(&request, Message.QE_SOAP_REQ, Node.UNDERDOG);

/* Get the SOAP response from the XmlDoc response */
&soapRes = CreateSOAPDoc();
&soapRes.XmlDoc = &response;
&OK = &soapRes.ValidateSOAPDoc();
&strXml = &soapRes.GenXmlString();
```

SOAPDoc Class Examples

The following are typical example of how you would use a SOAPDoc object.

Creating a SOAP Document

The following is the minimal PeopleCode you need to create a SOAP XML document:

```
Local SOAPDoc &SOAPDoc;

&SOAPDoc = CreateSOAPDoc();
&SOAPDoc.AddMethod("GetPrice");
&SOAPDoc.AddParm("Item", "Apples");
```

The following is an example of creating a SOAP XML document with a simple method.

```
Local SOAPDoc &SOAPDoc;

&SOAPDoc = CreateSOAPDoc();

&SOAPDoc.AddEnvelope(0);
&SOAPDoc.AddBody();
&SOAPDoc.AddParm("symbols", "PSFT");
&SOAPDoc.AddParm("format", "l1c1d1t1");

&OK = &SOAPDoc.ValidateSOAPDoc();
```

Reading an Existing SOAP Document

The following code loads an SOAP XML document from a URL, then finds the method name and parameters to call that method.

```
Local SOAPDoc &SOAPDoc;
Local Number &ParmCount;
Local Boolean &Result;

&SOAPDoc = CreateSOAPDoc();
&SOAPDoc.ParseXmlFromURL("C:\ptdvl\840S2\files\inputSOAP.xml");

&ParmCount = &SOAPDoc.ParmCount;
For &I = 1 to &ParmCount

   &ParmName = &SOAPDoc.GetParmName(&I);
   &ParmValue = &SOAPDoc.GetParmValue(&I);

/* Do processing */
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
End-for;
```

Using SOAP XML Text

The following shows a SOAP XML Document text for the following pseudo-code:

```
Item = "Apples"
Price = GetPrice(Item);
```

Example of SOAP Request Header

Here's the HTTP Header for a SOAP message. This Host URL is the server where the method defined in the SOAP envelope is processed:

```
POST /GetPrice HTTP/1.1
Host: www.farmersmarket.com
Content-Type: text/xml; charset="utf-8"
Content-Length: nnnn
SOAPAction:"GetPrice"
```

This is a simple example of a SOAP XML Document, requesting the price of Apples. It uses the default SOAP schemas. The name of the method is GetPrice with the parameter Item which has a value of "Apples".

```
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.SOAP.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.SOAP.org/soap/encoding/"
>
    <SOAP-ENV:Body>
        <m:GetPrice xmnls:m="SomeURI">
        <Item>Apples</Item>
        </m:GetPrice>
    </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

Example of SOAP HTML Reply Header

Here's the HTTP Header for a SOAP message Reply with a 200 return code that the message was processed OK.

```
HTTP/1.1 200 OK
Content-Type: text/xml; charset="utf-8"
Content-Length: nnnn
```

This simple example of a SOAP XML Document reply returns the price of Apples as 34. The SOAP reply always codes the name of the requested method with the Response tag attached to it, GetPriceResponse in this case.

```
<SOAP-ENV:Envelope
  xmlns:SOAP-ENV="http://schemas.SOAP.org/soap/envelope/"
  xmlns:SOAP-ENC="http://schemas.SOAP.org/soap/encoding/"
>
   <SOAP-ENV:Body>
       <m:GetPriceResponse xmlns:m="Some-URI">
          <Price>34</Price>
       </m:GetPriceResponse>
     </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Chapter 46

SQL Class

Understanding SQL Class

You can create SQL definitions in Application Designer. These can be entire SQL programs, or just fragments of SQL statements that you want to re-use. PeopleCode provides the SQL class for accessing these SQL definitions in your PeopleCode program at runtime.

The SQL class provides capability beyond that offered by SQLExec. Unlike SQLExec, which fetches just the first SELECTed row, operations for the SQL class allow iteration over all rows fetched. This can dramatically improve performance if you’re doing a million operations and you’ve set the BulkMode property to True.

A list of input (bind) values, and a list of output variables are supported, as they are in SQLExec. The input and output variables are limited to the same PeopleCode types that can be used with SQLExec, with the addition of a new class called Record.

At runtime, you instantiate a record object from the Record class. A record object is a "one row" instantiation of a record definition.

- When used as an output from an SQL object, each next field in the record is populated with the next column returned.
- When used as an input, several fields in the record are used to replace a single bind marker in the SQL statement. The bind marker for a record describes the type of substitution to be done.

Both records and other PeopleCode types can be mixed in both the output and input.

At runtime, you instantiate a SQL object from the SQL class. The SQL object is loaded by either a constructor for the object, or an explicit Open method call. Optionally, a SQL constructor and the Open method support setting the SQL statement through a string parameter. This capability enables the creation and execution of ad-hoc SQL statements.

The SQL class has a Fetch method for iterating through the rows fetched by a select. A *cursor* is used to control this connection between the runtime SQL object and the database. The cursor is closed automatically when the object goes out of scope. The cursor can be closed before that by using the Close method. The status of the connection is available from the Boolean IsOpen property.

The general status of operations is available from function or method return values or properties. Detailed status is not available, as the operations are designed to terminate on unexpected errors or errors that cannot be reasonably recovered from by application level logic.

Considerations for Extra Spaces

On the DB2 UDB for OS/390 and z/OS platform, when the **zparm** option is set to decimal equals comma (so comma is used as the database decimal separator), extra blanks are added after commas to ensure that they are not mistaken for decimal separators.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Considerations for Case Sensitivity

When processing a SQL statement, the system automatically casts all fieldnames and possibly record names to uppercase when processing a SQL statement. When processing records from a third party, fields that are lowercase get cast into uppercase, which can create a runtime issue on case sensitive platforms.

To prevent this, use the %NoUppercase meta-SQL statement at the beginning of the SQL statement.

Related Links

Understanding SQL Objects and Application Engine Programs
Understanding Record Class
"Understanding Data Buffer Access" (PeopleTools 8.54: PeopleCode Developer's Guide)
"%NoUppercase" (PeopleTools 8.54: PeopleCode Language Reference)

Using Record Class SQL

There are some SQL type operations that you can do with the Record class, such as INSERT, DELETE and UPDATE. The advantage of using the Record class methods is ease of use, re-use of code, and so on. However, if you're doing many iterations of the same operation (like a million UPDATEs) you should use the SQL object with the BulkMode property set to True.

The SQL object maintains a state (that is, a cursor). Hence, if your database can take advantage of BulkMode, instead of a million operations, the commands are "bulked up" and committed only once. This can improve performance dramatically.

Creating a SQL Definition

You can create SQL definitions in Application Designer, using the SQL editor. These SQL statements can be entire SQL programs, or just fragments that you want to re-use. After you have created a SQL definition, you can use it to populate a SQL object (using FetchSQL, Open, or GetSQL)

You can also create a SQL statement in PeopleCode (using CreateSQL), save it as a SQL definition (StoreSQL), then access it in Application Designer.

Related Links

Open
"Understanding the SQL Editor Window" (PeopleTools 8.54: PeopleCode Developer's Guide)
"FetchSQL" (PeopleTools 8.54: PeopleCode Language Reference)
"CreateSQL" (PeopleTools 8.54: PeopleCode Language Reference)
"GetSQL" (PeopleTools 8.54: PeopleCode Language Reference)
"StoreSQL" (PeopleTools 8.54: PeopleCode Language Reference)

Binding and Executing of SQL Statements

The processing of an SQL statement involves a series of steps.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

1. The binding process is the replacement of (variable) input values in the statement, in places indicated by bind placeholders.

   The input values are substituted into the SQL statement in place of the bind placeholders. These placeholders have the form "*:number*", or "*%bindop*(*:number* [, *parm*]. . .)" where the *number* indicates which input value is to be substituted, and the *bindop* and *parm* strings indicate what meta-SQL binding function is to be performed.

   Note: There must be no spaces between the *bindop* and the left parenthesis.

   The following binding meta-SQL functions are used with record objects to substitute various forms of fieldnames and values into the SQL statement. The goal of these binding functions is to enable the writing of SQL and PeopleCode that can manipulate records without dependencies on the exact fields in the records.

   - %DTTM
   - %InsertValues
   - %KeyEqual
   - %KeyEqualNoEffDt
   - %List
   - %OldKeyEqual
   - %Table
   - %UpdatePairs

2. The execution of an SQL statement is the carrying out of the operation of the statement by the database engine.

   This view of SQL statement processing is actually simpler than what actually occurs. In actual practice, the binding occurs in two distinct phases. The database engine (or its supporting routines) is aware of only the latter phase. For some operations, some database engines are able to delay the second stage of binding and the execution of an SQL statement, so the statement can be rebound and re-executed (with different input values). The advantage of this is that these bindings and executions can be accumulated and transmitted across the network to the database server, with several database operations being done in one network operation. This is sometimes referred to as *bulk mode*. Because the network time consumes most database time operations, the performance advantages of bulk mode can be significant.

   However, in bulk mode, individual operations might not be executed immediately by the database engine. The result is that the application might not see errors that arise until later operations are performed.

   SQL SELECT statements are not bound multiple times, rather the retrieved rows are accumulated and sent across the network many rows at a time, also decreasing the effect of network delays.

Related Links

"Understanding Meta-SQL" (PeopleTools 8.54: PeopleCode Language Reference)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Fetching From a SELECT

Some operations fetch a row of data into a list of output variables. The values of the fields from the select row are assigned in order to the given output variables. If one of these is a reference to a PeopleCode record object, the fields in the record are assigned the successive values from the row of the select, until all the fields are assigned. Assignment then continues with the next output variable, if any. The number of output fields and variables must equal the number of fields in the row of the select.

Related Links

"Understanding Data Buffer Access" (PeopleTools 8.54: PeopleCode Developer's Guide)

Using Array of Any for Bind Values or Fetch Results

You can use a parameter of type "Array of Any" in place of a list of bind values or in place of a list of fetch result variables for the Execute, Fetch, and Open methods. This is generally used when you don't know how many values are needed until the code runs.

For example, suppose that you had a SQL definition INSERT_TEST, that dynamically (that is, at runtime) generated the following SQL statement:

```
"INSERT INTO PS_TESTREC (TESTF1, TESTF2, TESTF3, TESTF4, . . . N) VALUES (:1, :2, %⇒
DateTimeIn(:3), %TextIn(:4)), . . . N";
```

Suppose you have placed the values to be inserted into an Array of Any, say &AAny:

```
&AAny = CreateArrayAny("a", 1, %DateTime, "abcdefg", . . . N);
```

You can execute the insert with the following:

```
&AAny = CreateArrayAny("a", 1, %DateTime, "abcdefg", . . . N);
&SQL = GetSQL(SQL.INSERT_TEST);
While /* Still something to do */
   &SQL.Execute(&AAny);
End-While;
&SQL.Close();
```

Because the Array of Any promotes to absorb any remaining select columns, it must be the last parameter for the SQL object Fetch method or (for results) SQLExec. For binding, it must be the only bind parameter, as it is expected to supply all the bind values needed.

Reusing a Cursor

Reusing a cursor means *compiling* a SQL statement just once, but *executing* it more than once. When a SQL statement is compiled, the database checks the syntax and chooses a query path. By doing this only once, but executing this statement several times, you can obtain an improvement in performance.

In PeopleCode, you can reuse a cursor either by using the ReuseCursor property or by following certain restrictions in your code. In this section, we discuss how to:

- Use the ReuseCursor property.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- Reuse a cursor without the ReuseCursor property.

Using the ReuseCursor Property

If you specify the ReuseCursor property as True, the cursor isn't closed until either the SQL object is explicitly closed or re-opened. This provides greater control over the cursor associated with your SQL object. However, when you set ReuseCursor to True, you're essentially pledging to do the right thing in your program. There are some considerations for how you use this property:

In a Application Engine program, if your program can be restarted, you *must*check for a restart after a checkpoint by testing to see if the SQL object is open after the checkpoint. If it isn't open, that means a restart has happened, and you must reopen the SQL object. In most cases, on checkpoints, your open SQL objects aren't closed, saving the overhead of re-establishing the SQL object after the checkpoint. If the SQL object is open on a select statement at a checkpoint it isn't restored to the open state because you cannot reliably establish the state of the execute-fetch sequence.

In the following example the SQL object is established on a select statement which is executed twice with different bind parameters but is compiled only once. Without the ReuseCursor property the SQL object would be closed after the first fetch cycle completes.

```
Local SQL &Sql;
Local String &Company1 = "CCB";
Local String &Company2 = "CCF";

&Sql = CreateSQL("SELECT A.COMPANY, %Timeout(A.EFFDT) FROM %Table(COMPANY_TBL) A WH⇒
ERE A.COMPANY=:1", &Company1);
/* commenting this out should make the subsequent Execute fail */
&Sql.ReuseCursor = True;

While &Sql.Fetch(&Company1, &Effdt)
   /* processing for the first Company */

End-While;

&Sql.Execute(&Company2);

While &Sql.Fetch(&Company1, &Effdt)
/* processing for the second company */

End-While;

&Sql.Close();
```

Reusing a Cursor Without the ReuseCursor Property

If you want to reuse a cursor in your program, there are several conditions:

- You have to use the SQL object. Only SQL objects retain SQL cursor information.
- For INSERT, DELETE, and UPDATE statements, you automatically reuse the cursor as long as you don't change the SQL statement as part of the binding process. If the SQL statement is textually the same, so only the binds have changed, you get reuse. For example, you won't get reuse if you first bind one kind of record object to %Insert(), then bind another, different kind of record object.
- For SELECTs, you *must*use the meta-SQL shortcuts (%SelectAll, %SelectByKey, or %SelectByKeyEffDt), *and* the CreateSQL or GetSQL functions without supplying any bind or buffer parameters. The bind parameters are supplied in the Execute function. The Fetch parameter must be

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

the fetch buffer, and be the same as the first Execute parameter. You can supply WHERE clauses, ORDER-BY, and so on, on the end of the SQL string containing the meta-SQL.

Note: BulkMode doesn't reuse the cursor in the same way as the SQL object. BulkMode requests that, when the system can reuse the cursor, it also holds all the changes so they can be communicated to the database in batches.

By using one of the forms of the Select meta-SQL, you're guaranteeing the resulting fetched values are all put into one record object (buffer). This means the implementation doesn't have to ask the database for the length and type of each column: the record buffer is already defined. So this sample code uses the SQL object to maintain the state of the connection with the database, and the record object, to maintain a series of fields suitable for database operations.

```
Local SQL &SQL;
Local Record &REC;

&REC = CreateRecord(Record.KP_KPI_DFN);

/* start with select statement, no bind refs, no */
/* bind parameters */

&SQL = CreateSQL("%Selectall(:1) Where SETID = :2 and KPI_ID = :3 and EFFDT = (SELE⇒
CT MAX(EFFDT) FROM PS_KP_KPI_DFN WHERE SETID = :4 AND KPI_ID = :5 AND EFFDT <= %Dat⇒
eIn(:6))");
```

Start Loop

```
/* bind and execute the statement */

&SQL.Execute(&REC, &SETID_KPI, &COMPID, &SETID_KPI, &COMPID, &EFFDT);

/* Note record parameter for Fetch statement must be
the same as the first Execute parameter
the results are in this record */

If &SQL.Fetch(&REC) Then

   /*process this record */

End-If;
```

End Loop

```
&SQL.Close(); /* there is no implicit close on a Fetch returning False */
```

The following example comes from a Application Engine program. Because the loop goes in and out of PeopleCode, you must declare the SQL object as Global. This example is in three parts.

1. Program called by Application Engine before the loop:

   ```
   Global SQL &SQL;

   &SQL = CreateSQL("INSERT INTO %Table(MY_WORK) (TRANS , REGISTERWRITE) VALUES (⇒
   :1, :2)");

   &SQL.BulkMode = True; /* not required for reuse, but will get better performan⇒
   ce on platforms that support bulk insert */
   ```

2. Program called in the Application Engine loop on SELECT 'X' FROM PSRECDEFN WHERE RECNAME LIKE '%A':

   ```
   Global SQL &SQL;
   ```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
&var1 = "X";
&var2 = "Y";

&SQL.Execute(&var1, &var2);
```

3. Program called by Application Engine after the loop:

```
Global SQL &SQL;

&SQL.Close();
```

Understanding SQL Objects and Application Engine Programs

A global variable won't go out of scope until a Application Engine program finishes. However, all SQL objects are forced closed (that is, the cursor closed) sooner than that. *Any open SQL object is forced closed just before any checkpoint in an Application Engine program.*This is to ensure that the application can be restarted successfully from the checkpoint. After the SQL object is closed, you can reopen the SQL object, or query its properties, (such as Status, IsOpen). The simplest way to avoid unnecessary closing of the SQL object is to set the ReuseCursor property to True. A restartable program should always check that SQL objects are open before using them in steps where it's expected they're open. In the absence of an intervening checkpoint, an open SQL object remains open until the Application Engine program finishes.

Declaring a SQL Object

SQL objects are declared as type SQL. For example:

```
Local SQL &MYSQL;

Global SQL &MySql = CreateSQL(SQL.MySql);
```

Scope of an SQL Object

An SQL object can be instantiated only from PeopleCode.

This object can be used anywhere you have PeopleCode, that is, in an application class, Application Engine PeopleCode, record field PeopleCode, and so on.

Your SQL statements sometimes change the database. When your SQL changes the database, your code should be only in one of the following events:

- SavePreChange
- WorkFlow
- SavePostChange
- Message Subscription
- FieldChange

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- Application Engine PeopleCode action

SQL Class Built-in Functions

"CreateSQL" (PeopleTools 8.54: PeopleCode Language Reference)

"DeleteSQL" (PeopleTools 8.54: PeopleCode Language Reference)

"FetchSQL" (PeopleTools 8.54: PeopleCode Language Reference)

"GetSQL" (PeopleTools 8.54: PeopleCode Language Reference)

"StoreSQL" (PeopleTools 8.54: PeopleCode Language Reference)

SQL Class Methods

In this section, we discuss the SQL class methods. The methods are discussed in alphabetical order.

Close

Syntax

```
Close()
```

Description

The Close method closes the SQL object. This terminates any incomplete fetching of select result rows, completes any buffered operations (that is, using BulkMode), and disassociates the SQL object from any SQL statement that was open on it.

After BulkMode operations, the RowsAffected property is not valid.

Parameters

None

Returns

True on successful completion, False if there was a duplicate record error. Any errors associated with buffered operations (that is, using BulkMode), other than duplicate record errors, cause termination.

Example

```
&SQL = CreateSQL("%Delete(:1)");
While /* Still something to do */
   /* Set key field values of &ABS_HIST */
   &SQL.Execute(&ABS_HIST);
End-While;
&SQL.Close();
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

Open

"CreateSQL" (PeopleTools 8.54: PeopleCode Language Reference)

Execute

Syntax

Execute(*paramlist*)

Where *paramlist* is an arbitrary-length list of values in the form:

inval1 [, *inval2*] ...

Description

The Execute method executes the SQL statement of the SQL object. The SQL object must be open and unbound on a delete, insert, or update statement. That is, the CreateSQL, GetSQL, or Open preceding the Execute must have specified a delete, insert, or update statement with bind placeholders and must not have supplied any input values.

The values in *paramlist* are used to bind the SQL statement before it gets executed.

When using the optional BulkMode, the Execute operations may be buffered and are not guaranteed to have been presented to the database until a Close is done. Thus, in BulkMode, errors that arise may not be reported until later operations are done.

Parameters

paramlist	Specify input values for the SQL string.

Returns

True on successful completion, False for "record not found" and "duplicate record" errors. Any other errors cause termination.

Example

The following example creates a SQL object for inserting. The statement isn't automatically executed when it's created because there aren't any bind variables. The Execute occurs after other processing is finished. The name of the record is passed in as the bind variable in the Execute method.

```
&SQL = CreateSQL("%Insert(:1)");
While /* Still something to do */
   /* Set all the field values of &ABS_HIST.  */
   &SQL.Execute(&ABS_HIST);
End-While;
&SQL.Close();
```

The following example creates two SQL objects, one to be used for fetching, the other for updating the record. The first SQL object selects all the records in the &ABS_HIST record that match &EMPLID. The data is actually retrieved using the Fetch method. After values are set on the record, the update is performed by the Execute.

```
&SQL1 = CreateSQL("%Select(:1) where EMPLID = :2", &ABS_HIST, &EMPLID);
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
&SQL_UP = CreateSQL("%Update(:1)");
While &SQL1.Fetch(&ABS_HIST);
   /* Set some field values of &ABS_HIST.  */
   &SQL_UP.Execute(&ABS_HIST);
End-While;
&SQL_UP.Close();
```

The following is an example of inserting an array of records:

```
Local SQL &SQL;
Local array of Record &RECS;

/* Set up the array of records.  */
.  .  .

/* Create the SQL object open on an insert */
/* statement, and unbound */
&SQL = CreateSQL("%Insert(:1)");
   /* While the array has something in it */
   While &RECS.Len
   /* Insert the first record of the array, */
   /* and remove it from the array.  */
   &SQL.Execute(&RECS.Shift());
   End-While;
```

Related Links

Close

BulkMode

"CreateSQL" (PeopleTools 8.54: PeopleCode Language Reference)

Fetch

Syntax

Fetch(*paramlist*)

Where *paramlist* is an arbitrary-length list of values in the form:

outvar1 [, *outvar2*] ...

Description

The Fetch method retrieves the next row of data from the SELECT that is open on the SQL object. Any errors result in termination of the PeopleCode program with an error message.

If there are no more rows to fetch, Fetch returns as False, the *outvars* are set to their default PeopleCode values, and the SQL object is automatically closed.

Using Fetch with a closed SQL object is processed the same as when there are no more rows to fetch.

Note: If you want to fetch only a single row, the SQLExec function can perform better, as it fetches only a single row from the server.

The return of Fetch is not optional, that is, you *must* check for the value of the fetch.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Setting Data Fields to Null

This method will *not* set Component Processor data buffer fields to NULL after a row not found fetching error. However, it does set fields that aren't part of the Component Processor data buffers to NULL. It does set work record fields to NULL.

Parameters

paramlist Specify output variables from the SQL Select statement.

Returns

The result of Fetch is True if a row was fetched. If there are no more rows to fetch, the result is False.

Example

In the following example, the Fetch method is used first to process a single row, then to process the ABS_HIST record.

```
Local SQL &SQL;
Local Record &ABS_HIST;

&ABS_HIST = CreateRecord(RECORD.ABSENCE_HIST);
&SQL = GetSQL(SQL.SEL27, 15, "Smith");
While &SQL.Fetch(&NAME1, &BIRTH_DT)
   /* Process NAME1, BIRTHDT from the selected row.  */
End-While;

&SQL.Open(SQL.SEL_ABS_HIST, &NAME1, "Smith");
While &SQL.Fetch(&ABS_HIST)
   /* Process ABS_HIST record.  */
```

The following is an example of reading in an array of record objects:

```
Local SQL &SQL;
Local Record &REC;
Local Array of Record &RECS;

/* Get the SQL object open and ready for fetches.  */
&SQL = CreateSQL("%SelectAll(:1) where EMPLID = :2", RECORD.ABSENCE_HIST, &EMPLID);
/* Create the first record.  */
&REC = CreateRecord(RECORD.ABSENCE_HIST);
/* Create an empty array of records.  *
&RECS = CreateArrayRept(&REC, 0);
While &SQL.Fetch(&REC)
   /* We got a record, add it to the array */
   /* and create another.*/
   &RECS.Push(&REC);
   &REC = CreateRecord(RECORD.ABSENCE_HIST);
End-While;
```

Related Links

Open

"GetSQL" (PeopleTools 8.54: PeopleCode Language Reference)

"SQLExec" (PeopleTools 8.54: PeopleCode Language Reference)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Open

Syntax

```
Open(sql [, paramlist])
```

Where *paramlist* is an arbitrary-length list of values in the form:

```
inval1 [, inval2] ...
```

Description

The Open method associates the *sql* statement with the SQL object. The *sql* parameter can be either:

- A string value giving the SQL statement.
- A reference to a SQL definition in the form **SQL**.*sqlname*.

If the SQL object was already open, it is first closed. This terminates any incomplete fetching of select result rows, completes any buffered operations (that is, using BulkMode), and disassociates the SQL object from any SQL statement that was open on it.

Opening and Processing sql

If *sql* is a SELECT statement, it is immediately bound with the *inval* input values and executed. The SQL object should subsequently be the subject of a series of Fetch method calls to retrieve the selected rows. If you want to fetch only a single row, use the SQLExec function instead. If you want to fetch a single row into a PeopleCode record object, use the record Select method.

If *sql* is not a SELECT statement, and either: there are some inval parameters, or there are no bind placeholders in the SQL statement, the statement is immediately bound and executed. This means that there is nothing further to be done with the SQL statement and the IsOpen property of the returned SQL object will be False. In this case, using the SQLExec function would generally be more effective. If you want to delete, insert, or update a record object, use the record Delete, Insert, or Update methods with the record object.

If *sql* is not a SELECT statement, there are no *inval* parameters, *and* there are bind placeholders in the SQL statement, the statement is neither bound nor executed. The resulting SQL object should subsequently be the subject of a series of Execute method calls to affect the desired rows.

Setting Data Fields to Null

This method will *not* set Component Processor data buffer fields to NULL after a row not found fetching error. However, it does set fields that aren't part of the Component Processor data buffers to NULL.

Parameters

sql	Specify either a SQL string or a reference to a SQL definition in the form **SQL.** *sqlname*.
paramlist	Specify input values for the SQL string.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

None.

Example

Generally, you use the Open method only after you've already gotten a reference to another SQL object. SELECT and SEL_ABS_HIST are the names of the SQL definitions created in Application Designer.

```
Local SQL &SQL;

&SQL = GetSQL(SQL.SELECT);

/* do other processing */

/* get next SQL statement for additional processing */
/* The open automatically closes the previous */
/* SQL statement */

&SQL.Open(SQL.SEL_ABS_HIST, &NAME1, "Smith");
While &SQL.Fetch(&ABS_HIST)
   /* Process ABS_HIST record.  */
End-While;
```

Related Links

"CreateSQL" (PeopleTools 8.54: PeopleCode Language Reference)

"GetSQL" (PeopleTools 8.54: PeopleCode Language Reference)

SQL Class Properties

In this section, we discuss the SQL class properties. The properties are discussed in alphabetical order.

BulkMode

Description

This property controls the use of bulk mode. Setting this property to True enables the use of bulk mode, and hence removes any guarantee of the synchronous presentation of error status.

Bulk mode is used only with those database connections and operations that support it. Bulk mode can be used with any SQL operation, that is, with INSERTs, DELETEs, or UPDATEs.

If you're using a Application Engine program, and have set this property to True, the rows inserted in BulkMode are committed at the next database commit in your program.

After BulkMode operations, the RowsAffected property is not valid.

The default value for BulkMode is False.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

The following code is an example of inserting an array of records using bulk mode:

```
Local SQL &SQL;
Local array of Record &RECS;

/* Set up the array of records.  */
   .  .  .
   /* Create the SQL object open on an insert */
   /* statement, and unbound.*/
   &SQL = CreateSQL("%Insert(:1)");
   /* Try for bulk mode.  */
   &SQL.BulkMode = True;
   /* While the array has something in it&mldr; */
   While &RECS.Len
      /* Insert the first record of the array, */
      /* and remove it from the array.  */
      If not &SQL.Execute(&RECS.Shift) then
         /* A duplicate record found, possibly */
         /* in bulk mode.  There is no way to  */
         /* tell which record had the problem. */
         /* One approach to recovery is to fail*/
         /* the transaction and retry it with a*/
         /* process that does only one record  */
         /* at a time, that is, doesn&rsquo;t use    */
         /* bulk mode.*/
         .  .  .;
      End-If;
End-While;
```

Related Links

RowsAffected

Binding and Executing of SQL Statements

IsOpen

Description

This property returns as True if the SQL object is open on some SQL statement.

This property is read-only.

Example

You might use the following in a Application Engine program, after a checkpoint. MYSELECT is the name of a SQL definition created in Application Designer:

```
If Not &MYSQL.IsOpen Then
   &MYSQL.Open(SQL.MYSELECT);
End-if;
```

LTrim

Description

This property specifies whether values read by the Fetch method are trimmed of blanks on the left, except in the following cases:

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- For long columns.
- The record is directly used to buffer the incoming data. In the following example, the values aren't LTrimmed - regardless of the setting of the LTrim property.

```
Local Record &Rec = CreateRecord(Record.QA_TEST);
Local SQL &Sql = CreateSQL("%SelectAll(:1)");
&Sql.LTrim = True; /* the default */
&Sql.Execute(&Rec);
While &Sql.Fetch(&Rec)
   /* do processing */
End-While;
```

This property takes a Boolean value. The default value is True. If this property is set to False, the selected values are not trimmed of blanks on the left.

This property is read-write.

Note: The removal of blanks from the right end of fetched values (RTrimming) still occurs for non-long columns.

Example

```
Local Record &Rec = CreateRecord(Record.QA_TEST);
Local SQL &Sql = CreateSQL(%SelectAll(:1)", &Rec);
&Sql.LTrim = False;
While &Sql.Fetch(&Rec)
   /* do processing */
End-While;
```

ReuseCursor

Description

This property specifies whether the SQL object tries to reuse the open cursor. This property takes a Boolean value, True, to reuse the SQL cursor.

If specified as True, the SQL object won't be closed at checkpoints, and any non-SELECT SQL is restored. In addition the SQL object is not closed after a fetch cycle completes. It remains open ready to be executed, perhaps with different bind parameters.

If you use this property in your application program, you *must* close the SQL object explicitly or it is closed when the object goes out of scope (that is, when the program finishes.)

You must instantiate a SQL object first before you can reuse it.

This property is read-write.

Related Links

Reusing a Cursor

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

RowsAffected

Description

This property returns the number of rows affected by the last INSERT, UPDATE, or DELETE statement of the SQL object. After BulkMode operations, the RowsAffected property is not valid.

This property is read-only.

Example

The following code is an example that determines if a delete statement actually deleted anything:

```
Local SQL &SQL;

/* Create the SQL object and do the deletion.  */
   &SQL = CreateSQL("Delete from %Table(:1) where EMPLID = :1", RECORD.ABSENCE_HIST⇒
, &EMPLID);
   If &SQL.RowsAffected = 0 Then
   /* We did not delete any rows.  */
   .  .  .
End-If;
```

Related Links

BulkMode

Status

Description

This property returns the status of the last statement executed. You can use either the constant or the numeric value for this property. The values for this property are:

Numeric Value	*Constant Value*	*Description*
0	%SQLStatus_OK	No Errors.
1	%SQLStatus_NotFound	Record not found.
2	%SQLStatus_Duplicate	Duplicate Record Found

This property is read-only.

Example

The following example determines what went wrong after an update:

```
Local SQL &SQL;
Local Record &NEWREC, &OLDREC;

/* Create and initialize &OLDREC with the keys of the
record to be updated.  Create and initialize &NEWREC
with the new field values for the record.  */
...;

/* Create and execute the update.  */
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
&SQL = CreateSQL("%Update(:1, :2)", &NEWREC, &OLDREC);
Evaluate &SQL.Status
When = %SQLStatus_OK
   /* It worked.  */
When = %SQLStatus_NotFound
   /* The OLDREC keys were not found.  */
When = %SQLStatus_Duplicate
   /* The NEWREC keys were already there.  */
End-Evaluate;
```

TraceName

Description

This property enables you to assign a name to a SQL statement that has been created in PeopleCode using CreateSQL. This name is used in the Application Engine timings trace. This property takes a string value.

Note: You *cannot* associate the TraceName property with the execution of a simple SELECT statement created with CreateSQL. This is because the SELECT is executed when the SQL is created, before it has the TraceName assigned. To do this, create a SQL object instead.

If this property isn't set, it defaults to a substring of the SQL statement, indicating the operation and table, (for example, SELECT PS_VOUCHER_LINE.) It may be useful to set TraceName to indicate the origin of the SQL statement.

This property is read-write.

Example

```
&REC = CreateRecord(Record.VOUCHER_LINE);
&SQL = CreateSQL("%selectall(:1) WHERE BUSINESS_UNIT =:2 AND VOUCHER_ID =:3 AND VOU⇒
CHER_LINE_NUM = :4");
&SQL.TraceName = "AEPROG.SECT1.STEP1.SQL2";
&SQL.Execute(&REC, MATCHING_AET.BUSINESS_UNIT, MATCHING_AET.VOUCHER_ID, &count);
If &SQL.Fetch(&REC) Then
      &count2 = &count2 + 1;
End-If;
```

Image: Trace Timings Example

The previous example would produce the following in the timings trace.

```
SQL Statement              Count   Time     Count   Time     Count   Time     Time
-------------------------- ------- -------- ------- -------- ------- -------- --------

PeopleCode

AEPROG1.SECT1.STEP1.SQL1                      169    5.371     169    3.083    4.000
AEPROG1.SECT1.STEP1.SQL2                      100    5.371     100    3.083    4.454
                                                                            --------
                                                                               8.454
```

You can use this parameter with the Open statement also. The following is an example of how this works:

```
&Sql1 = CreateObject("SQL");
&Sql1.TraceName = "sql1";
&Sql1.Open("Select %FirstRows(1) 'x' FROM psstatus");
&Sql1.Fetch(&Temp);

&Sql2 = CreateObject("SQL");
&Sql2.TraceName = "sql2";
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
&Sql2.Open("Select 'x' FROM psstatus");
&Sql2.Fetch(&Temp);
```

Value

Description

This property returns the SQL statement associated with the SQL object as a string.

This property is read-only.

Example

To report an error in a SQL definition, including the actual SQL executed, use the Value property to get the text of the SQL statement:

```
Local SQL &SQL;

/* Execute some SQL.  */
&SQL = CreateSQL(SQL.SOMESQL, &EMPLID);
If &SQL.Status = %SQLStatus.NotFound Then
   /* Get the SQL string used.  */
   &SQLSTR = &SQL.Value;
   /* Report the error.  */
   .  .  .;
End-If;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Chapter 47

TransformData Class

Understanding the TransformData Class

When Integration Broker invokes a Application Engine transform program, it inserts the message content into a PeopleCode system variable, %TransformData, which remains in scope throughout the Application Engine program. Each program step can access the variable in turn and modify its content, which then becomes available to the next step.

In the Application Engine program, XSLT steps and PeopleCode steps access %TransformData differently:

- In XSLT, the data is automatically made available to your program. The XSLT program is literally a presentation of the output structure and data, which includes XSL tags that reference, process, and incorporate the input data into the output structure. There's no need to explicitly refer to %TransformData, which automatically receives the interpreted result of the XSLT step.
- In PeopleCode, use the PeopleCode %TransformData system variable to access the TransformData object. You access the XML data as the XmlDoc property of the TransformData object, which you then assign to an XmlDoc object and process normally. Because the XmlDoc object is a reference to the data portion of %TransformData, your modifications are automatically passed back to the system variable.

Related Links

"Understanding Filtering, Transformation, and Translation" (PeopleTools 8.54: Integration Broker)

"%TransformData" (PeopleTools 8.54: PeopleCode Language Reference)

Creating a TransformData Object

A TransformData object is returned from the system variable %TransformData. You cannot create a TransformData object directly.

When Integration Broker invokes a Application Engine transform program, it inserts the message content into the %TransformData system variable.

TransformData Class Properties

In this section, the TransformData class properties are presented in alphabetical order.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

DestMsgName

Description

This property returns the name of the message at the receiving node as a string.

This property is read-only.

DestMsgVersion

Description

This property returns the name of the message version at the receiving node as a string.

This property is read-only.

DestNode

Description

This property returns the name of the node receiving the message as a string.

This property is read-only.

RejectTransform

Description

Use this property to terminate asynchronous transactions (asynchronous physical transformations only).

Use the following system constant to set this property: %IB_Transform_Rejected.

If this property is set within a transform program for an inbound asynchronous transaction, the result will be that no subscription contract is created. On the Service Operation Monitor Details page for the transaction, an informational message will be part of the error message link indicating that the transaction was terminated.

If this property is set within a transform program for an outbound asynchronous transaction, the publication contract status will be updated to done. The outbound message will not be sent. In addition, on the Service Operation Monitor Details page for the transaction, an informational message will be part of the error message link indicating that the transaction was terminated.

This property is read-write.

RoutingDefnName

Description

This property returns the routing definition name as a string. You can use this property to retrieve the connector's routing properties.

This property is read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

LoadConnectorPropFromRouting

SourceMsgName

Description

This property returns the name of the message at the sending node as a string.

This property is read-only.

SourceMsgVersion

Description

This property returns the name of the message version at the sending node as a string.

This property is read-only.

SourceNode

Description

This property returns the name of the node sending the message as a string.

This property is read-only.

Status

Description

Use this property to communicate the success or failure of the transform program step to Integration Broker. Use the following values to set this property:

Integer Value	*System Constant*	*Description*
0 (default)	—	Indicates success.
1	—	Indicates that the message failed a filtering step.
2	%IB_Transform_Error	Indicates that an error occurred.

This property is read-write.

Related Links

"Understanding Filtering, Transformation, and Translation" (PeopleTools 8.54: Integration Broker)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

XmlDoc

Description

This property contains the XML message data.

You can assign this to an XmlDoc object and process the data using the XmlDoc class methods and properties.

This property is read-write.

Related Links

Understanding XmlDoc Classes

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Chapter 48

Tree Classes

Understanding Tree Classes

Using the tree classes in your PeopleCode, you have access to all the functionality of PeopleSoft Tree Manager. Your application should instantiate the appropriate tree objects when it must work with the tree system database data, call the appropriate methods and properties, then close the objects when it is finished.

Creating or deleting a tree *object* does not create or delete tree system database information. You must call the method for that tree object directly to create or delete database information, that is, the Create or Delete method.

One instance of a tree or tree structure object can be created to work on multiple database entities. However, only one tree or tree structure can be open at a time. If you open a Tree before closing the one that's currently open, you receive an error. You must explicitly close a tree or tree structure (using the Close method) before you try to open a second one.

All of the classes, and most of the properties and methods that make up the Tree Classes have a GUI representation in PeopleSoft Tree Manager. This document assumes that the reader is familiar with PeopleSoft Tree Manager.

The following classes make up the tree classes:

- Branch Collection
- Leaf
- Level
- Level Collection
- Node
- Tree
- Tree Structure

With most of the classes of objects in PeopleTools, when you use a *Getxxx* method, you are fully instantiating an object. However, for the tree class, when you use GetTree (from the Session object), you get a closed tree. A closed tree is a tree object with just the key fields filled in. The rest of the data is not present. To open the tree, you must use the Open method. Working with closed trees can improve your performance. The same applies to a tree structure: it's closed when you get it from the Session object, and you must open it before you can access its properties or change it.

There aren't any built-in functions for the tree classes: objects are instantiated from identifiers, from other objects, or from a Session object.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Using the GenerateTree function, you can produce a GUI representation of a tree in the PeopleSoft Pure Internet Architecture.

Related Links

"TreeDetailInNode" (PeopleTools 8.54: PeopleCode Language Reference)

Understanding Session Class

"Using the GenerateTree Function" (PeopleTools 8.54: PeopleCode Developer's Guide)

"Understanding Types of Trees" (PeopleTools 8.54: Tree Manager)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Relationships Between Different Tree Classes

Image: Tree classes and their relationships

The following diagram shows the tree classes and their relationships. Objects at the tip of the arrowhead are accessed or created from the object at the left of the arrowhead. Squares indicate objects. Ovals indicate collections.

- From the session object, you can get identifiers for a tree or a tree structure.
- From the level collection object, you can instantiate a level object.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- From the branch collection object, you can get an identifier for a branch.
- From the tree object, you can instantiate a tree, a tree structure, a branch collection, a leaf, a node, and a level collection.
- From the node object, you can instantiate a leaf object or a node object.
- From the leaf object, you can instantiate a leaf object or a node object.

Collections in the Tree Classes

A *collection* is a set of similar things, like a group of already existing branches or levels. Like everything else in the tree classes, collections have a GUI representation. For example, when you find an existing branch from PeopleSoft Tree Manager, you get a dialog that lets you select the branches you want.

Image: Example of level collection

The following screen image is an example of different levels of collections in the Tree classes. And the dialog box data is represented in PeopleCode as the *tree level collection.*

The following collections are part of the tree classes:

- Branch collection
- Level collection

Error Handling With Trees

The tree classes log descriptive information regarding errors and warnings to the PSMessages collection, instantiated from a session object.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

In your program, use the PSMessages collection to identify and report to the user any errors that are encountered during processing.

The tree classes log errors "interactively", that is, as they happen. For example, suppose you had created a new tree, and were setting the effective date using the effective date property (EffDt). If you used an invalid value for the effective date, the error would be logged in the PSMessages collection as soon as you set the value, not when you saved the tree.

When you want to check for errors depends on your application. However, if you check for errors after every assignment, you may see a performance degradation.

One way to check for errors is to check the number of messages in the PSMessages collection, using the Count property. If the Count is 0, no error or warning messages have been logged to the PSMessages collection.

```
Local ApiObject &MYSESSION;
Local ApiObject &ERRORCOL;
Local ApiObject &TREE, TREELIST;

&MYSESSION = %Session;

If &MYSESSION Then
   /* connection is good */

&MyTree = &Session.GetTree();
    /* open a tree */
   &TreeReturn = &MyTree.Open("", "", "PERSONAL_DATA", "1999-06-01", "",true);
    /* Do error checking */

   &ERRORCOL = &MYSESSION.PSMessages;
   If (&ERRORCOL.Count <> 0) Then
      /* errors occurred - do processing */
   Else
      /* no errors */
   End-If;
   Else
   /* do processing for no connection */
End-If;
```

You can also do an error check based on the return value of your API calls

```
If ALL(&TreeReturn) then
   /* processing errors */
End-if:
```

Related Links

Error Handling

Leaves and Nodes Insert Verification

InsertChildLeaf, InsertSibNode, InsertChildNode, and so on, can return False or a Null object reference, depending upon the type of error encountered. You may want to declare references to new leaves or nodes as type ANY until after you verify they were actually created. You can do this by using the None or All PeopleCode functions to determine whether a valid Leaf or Node Object was created. If a Leaf or Node object was created ALL()returns True and None() returns False.

```
&NewLeaf = &RootNode.InsertChildLeaf("8000", "8999");
If NONE(&NewLeaf) Then
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
   /* Leaf not inserted, do error processing */
   &Messages = &Session.PSMessages;
   If &Messages.WarningPending Then
      /* do error processing */
   End-if;
End-if;
```

Related Links

"None" (PeopleTools 8.54: PeopleCode Language Reference)

"All" (PeopleTools 8.54: PeopleCode Language Reference)

Restrictions on Trees When Used as a SmartNavigation Data Source

When a tree is used as a SmartNavigation data source, the values of several tree-specific properties are passed to the SmartNavigation application via URL. Certain characters are inappropriate for use in a URL and must be avoided. When using a tree as a SmartNavigation data source, do not use any of the following characters in the tree name, setID, user key value, and tree branch values:

pound (#)	percent (%)	dollar ($)
ampersand (&)	plus (+)	comma (,)
forward slash/virgule (/)	colon (:)	semi-colon (;)
equals (=)	question mark (?)	at symbol (@)
space ( )	quotation marks(")	less than symbol (<)
greater than symbol (>)	left curly brace ({)	right curly brace (})
vertical bar/pipe (|)	backslash (\)	caret (^)
tilde (~)	left square bracket ([)	right square bracket (])
grave accent (`)		

When using Tree class methods such as Copy, Create, Rename, SaveAs, SaveAsDraft, and others, take care to avoid using these invalid characters in the values for the tree name, setID, user key value, and tree branch.

Related Links

"Defining SmartNavigation Folders" (PeopleTools 8.54: Portal Technology)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Data Types for Tree Objects

All tree objects, that is, trees, tree structures, nodes, levels, and so on, are declared as type ApiObject. For example:

```
Local ApiObject &MYTREE;

Global ApiObject &MYNODE;
```

All tree objects can be declared as Local, Component or Global.

Scope of the Tree Objects

All tree objects, that is, trees, tree structures, nodes, leaves, and so on, can *only* be instantiated from PeopleCode.

This object can be used anywhere you have PeopleCode, that is, in an application class, Application Engine PeopleCode, record field PeopleCode, and so on.

You can instantiate a tree or tree structure object only from a session object. You have to instantiate the session object, and connect to the database, before you can instantiate a tree or tree structure.

```
Local ApiObject &TREELIST;
Local ApiObject &MYSESSION;

&MYSESSION = %Session;

If &MYSESSION Then
   /* connection is good */
Else
   /* do error processing */
End-if;
```

Note: Tree Classes are accessible only through PeopleCode.

Tree Classes Implementation

You will often want to create a new tree. The following procedure discusses this action in more detail.

The TreeMover Application Engine program uses the Tree API (and File Layouts) for importing a tree from a flat file or exporting a tree to a flat file.

To create a new tree:

In this example, you are creating a new tree based on an existing tree structure. The following is the complete code sample: the steps explain each line.

```
Local ApiObject &Session;
Local ApiObject &TreeList, &MyTree;
Local ApiObject &LvlColl;

&Session = %Session;

&MyTree = &Session.GetTree();
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
   /* create new tree */

If All(&MyTree) Then
  &TreeReturn = &MyTree.Create("", "", "PERSONAL_DATA2", "1999-06-01", "PERSONAL_DA⇒
TA");

   If &TreeReturn <> 0 then
      /* check PSMessages collection */
   End-if;

   &MyTree.description = "test tree";

   /* add level */
   &LvlColl = &MyTree.levels;
   &Level = &LvlColl.add("FIRST LVL");
   &Level.description = "First Level";

   /* add root node */
   &RootNode= &MyTree.insertroot("00001");

If ALL(&RootNode) Then
 /* insert a leaf */
       &NewLeaf = &RootNode.InsertChildLeaf("8000", "8999");

   /* save new tree */
   &RSLT = &MyTree.Save();

   /* Do error checking */
   If &RSLT <> 0 Then
      /* errors occurred = do error checking */
      &ERRORCOL = &Session.PSMessages;
      For &I = 1 To &ERRORCOL.count
         /* do error processing */
      End-For;
   Else
      /* no errors - saved correctly - do other processing */
   End-If;
End-if;

End-if;
```

1. Get a session object.

   Before you can get a tree, you have to get a session object. The session controls access to the tree, provides error tracing, enables you to set the runtime environment, and so on. Use the %Session system variable to return a reference to the current PeopleSoft session.

   ```
   &Session = %Session;
   ```

2. Get a tree object.

   Use the GetTree method specifying a null value `(" ")` to return a closed tree object.

   ```
   &MyTree = &Session.GetTree();
   ```

3. Create the Tree.

   The Create method creates a new tree with the name PERSONAL_DATA2. To ensure that you have a valid tree, use the All built-in function. Description is a required property (if you don't specify something for Description you cannot save the tree.)

   ```
   &TreeReturn = &MyTree.Create("", "", "PERSONAL_DATA2", "1999-06-01", "PERSONAL⇒
   _DATA");

   &MyTree.description = "test tree";
   ```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

4. Add a level.

   To add a level, you have to instantiate a level collection. Although there aren't any levels in the tree, you can still access this collection. Use the Add method with the level collection to add a new level. Remember, the level name must be 8 characters or less. Description is a required property (if you don't specify something for Description you cannot save the tree.)

```
&LvlColl = &MyTree.levels;
&Level = &LvlColl.add("FIRST LVL");
&Level.description = "First Level";
```

5. Add the root node.

   Because this is a new tree, you must first add the root node.

```
&RootNode = &MyTree.insertroot("00001");
```

6. Add a leaf.

   To add a new leaf, you must have a reference to the parent node object. Using the All built-in function ensures that there is a root node before you try to insert the leaf with the InsertChildLeaf method.

```
If ALL(&RootNode) Then
   &NewLeaf = &RootNode.InsertChildLeaf("8000", "8999");
```

7. Save the tree.

   When you execute the Save method, the new tree is saved to the database.

```
&RSLT = &MyTree.Save();
```

Note: If you're running the tree API from an Application Engine program, the data won't actually be committed to the database until the Application Engine program performs a COMMIT.

---

8. Check for errors.

   You can check if there were any errors using the PSMessages property on the session object.

```
If All (&RSLT) Then
   /* errors occurred = do error checking */
   &ERRORCOL = &Session.PSMessages;
   For &I = 1 To &ERRORCOL.count
      /* do error processing */
   End-For;
Else
   /* no errors - saved correctly - do other processing */
End-If;
```

   If there are multiple errors, all errors are logged to the PSMessages collection, not just the first occurrence of an error.

Note: If you've called the Tree API from an Application Engine program, all errors are also logged in the application engine error log tables.

Related Links

"Understanding TreeMover" (PeopleTools 8.54: Tree Manager)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Tree Classes Reference

This section provides a reference to the following topics:

- Session class methods in the tree API.
- Branch collection.
- Leaf class.
- Level collection.
- Level class.
- Node class.
- Tree class.
- Tree structure class.

Session Class Methods

Tree Classes don't have any built-in functions. Instead, they're instantiated from the Session Class.

In this section, we discuss the Session class methods. The methods are discussed in alphabetical order.

GetTree

Syntax

GetTree()

Description

The GetTree method returns a closed tree object. Before you can use some of the methods or any of the properties, you must use the Open method to open a tree object.

Parameters

None.

Returns

A reference to a closed tree object.

Example

To create a new tree, use the following:

```
&MYTREE = %Session.GetTree();
&MYTREE.Create("","","PERSONAL_NEW", "05-05-1997", "PERSONAL_DATA");
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

To determine if a tree already exists in the database, use the following code:

```
&MYTREE = %Session.GetTree();
If &MYTREE.Exists("","","PERSONAL_OLD", "05-05-1997", "PERSONAL_DATA") = 0 then
     /* Do processing */
End-If;
```

To open an existing tree, use the following code:

```
&MYTREE = %Session.GetTree();
&MYTREE.Open("","","PERSONAL_OLD", "05-05-1997", "PERSONAL_DATA", True);
```

GetTreeStructure

Syntax

GetTreeStructure()

Description

The GetTreeStructure method returns a closed tree structure object. Before you can use some of the methods or any of the properties, you must use the Open method to open the tree structure object.

Branch Collection

A branch collection is returned from the Branches property, used with an open tree object.

```
&MYBRANCHCOLL = &MYTREE.Branches;
```

&MYTREE must be a branched tree. To verify whether a tree is branched, you can check the value of the IsBranched property of a tree object (Boolean value: True or False.)

See Branches.

Branch Collection Property

In this section, we discuss the Branch collection properties. The properties are discussed in alphabetical order.

Count

Description

Returns the number of branches for the branch collection object.

Leaf Class

Leaf objects are instantiated from other tree classes as follows:

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- From a tree object with the FindLeaf method.
- From a node object with the FirstChildLeaf property.
- From another leaf object with the NextSib and PrevSib properties.

See FindLeaf, FirstChildLeaf, NextSib, PrevSib.

Leaf Class Methods

In this section, we discuss the Leaf class methods. The methods are discussed in alphabetical order.

Cut

Syntax

```
Cut()
```

Description

The Cut method cuts the leaf and puts it into a buffer (the clipboard.) You can then use the PasteSib method to add the leaf back as a sibling of a different leaf. You can also use the PasteChild node method to add the leaf back as a child of a different node.

You can only have one object at a time on the clipboard. If you cut another leaf or node, the leaf in the clipboard is overwritten.

Parameters

None.

Returns

A number; 0 if the cut is successful.

Related Links

Cut
PasteSib
PasteChild

Delete

Syntax

```
Delete()
```

Description

The Delete method deletes the leaf object executing the method *from the database*.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

A number; 0 if the delete is successful.

Example

```
&MYLEAF = &MYTREE.FindLeaf("8200", "8300");
&MYLEAF.Delete();
```

DeleteByRange

Syntax

DeleteByRange(*RangeFrom*, *RangeTo*)

Description

The DeleteByRange method deletes the specified leaf object from the database. The leaf specified by the parameters does *not* have to match the leaf executing the method. That is, if &MYLEAF is associated with a range 8200-8300, you can specify a different range with the DeleteByRange method. For example:

```
&MYLEAF = &MYTREE.FindLeaf("8200", "8300");
/* some processing */
&RET_VALUE = &MYLEAF.DeleteByRange("8400", "8500");
```

Parameters

RangeFrom	Specify the starting range of the leaf to be deleted. This parameter takes a string value.
RangeTo	Specify the ending range of the leaf to be deleted. This parameter takes a string value.

Returns

A number; 0 if the delete is successful.

Example

```
&RET_VALUE= &MYLEAF.DeleteByRange("8400", "8500");
```

GenABNMenuElement

Syntax

GenABNMenuElement()

Description

Use this method to generate a single <li> element for this tree leaf.

The <li> element from this leaf and the <li> elements from its sibling leaves and nodes are concatenated to form an HTML code fragment to be consumed by the portal.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

None.

Returns

A string representing the <li> element for this tree leaf.

Example

```
&LI_list = &LI_list | &ChildLeaf.GenABNMenuElement();
```

Related Links

GenABNMenuElementWithImage

GenABNMenuElementWithImage

Syntax

GenABNMenuElementWithImage(*CREF_img_class_ID*)

Description

Use this method to generate a single <li> element for this tree leaf using the specified custom CREF icon.

The <li> element from this leaf and the <li> elements from its sibling leaves and nodes are concatenated to form an HTML code fragment to be consumed by the portal.

Parameters

CREF_img_class_ID

Specifies the class ID for a custom CREF icon as a string. This class must be defined in a style sheet, and the style sheet must be assigned to the SmartNavigation folder.

See "Understanding SmartNavigation Icons" (PeopleTools 8.54: Portal Technology).

This is an optional parameter. To use the default CREF icon, you can omit this parameter or specify the null string "". However, to ensure forward compatibility, you must specify the null string.

Returns

A string representing the <li> element for this tree leaf.

Example

```
&LI_list = &LI_list | &ChildLeaf.GenABNMenuElementWithImage("mycreficon");
```

Related Links

GenABNMenuElement

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

InsertDynSib

Syntax

```
InsertDynSib()
```

Description

The InsertDynSib method inserts a dynamic leaf as a sibling leaf to the leaf object executing the method. The leaf is a *new*node.

A leaf object associated with the new leaf is returned. The new leaf is inserted as the next sibling leaf. If the new leaf isn't inserted successfully, the method returns Null.

Note: To insert a sibling leaf with a specific range, use the InsertSib method.

Parameters

None.

Returns

A reference to the new leaf. If this method fails, it returns either False or a Null object reference, depending upon the type of error encountered. The best way to test whether the object was inserted is to test the result using either the All or None functions.

Example

```
&NEWLEAF = &MYLEAF.InsertDynSib();
```

Related Links

InsertSib

"All" (PeopleTools 8.54: PeopleCode Language Reference)

"None" (PeopleTools 8.54: PeopleCode Language Reference)

InsertSib

Syntax

```
InsertSib(RangeFrom, RangeTo)
```

Description

The InsertSib method inserts a new leaf as a sibling leaf under the leaf currently executing the method. The leaf specified by the range parameters must be a *new* leaf. You receive an error if the leaf already exists.

A leaf object associated with the new leaf is returned. The new leaf is inserted as the next sibling leaf, although there is no explicit ordering of leaves: leaves take the order of the alphanumeric database sort on their range fields.

Note: To insert a dynamic sibling leaf (that is, without specifying a range) use the InsertDynSib method.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

RangeFrom	Specify the starting range of the new leaf. This parameter takes a string value.
RangeTo	Specify the ending range of the new leaf. This parameter takes a string value.

Returns

A leaf object associated with the new leaf. If this method fails, it returns either False or a Null object reference, depending upon the type of error encountered. The best way to test whether the object was inserted is to test the result using either the All or None functions.

Example

```
&NEWLEAF = &MYLEAF.InsertSib("10090", "10100");
```

Related Links

InsertDynSib

"All" (PeopleTools 8.54: PeopleCode Language Reference)

"None" (PeopleTools 8.54: PeopleCode Language Reference)

LoadABNChart

Syntax

LoadABNChart(*&chart_rowset*, *&relactions_rowset*)

Description

Use this method to load a child leaf of the current tree node into the SmartNavigation chart rowset and the component buffer.

Parameters

&chart_rowset	Specifies the SmartNavigation chart rowset. Typically, this is the rowset returned by the GetABNChartRowSet function.
&relactions_rowset	Specifies the related actions rowset. Typically, this is the rowset returned by the GetABNRelActnRowSet function.

Returns

None.

Example

```
&ChildLeaf.LoadABNChart(&chart_rs, &ra_rs);
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

LoadABNChartOrdered

"GetABNChartRowSet" (PeopleTools 8.54: PeopleCode Language Reference)

"GetABNRelActnRowSet" (PeopleTools 8.54: PeopleCode Language Reference)

LoadABNChartOrdered

Syntax

LoadABNChartOrdered(*&chart_rowset*, *&relactions_rowset*, *order*)

Description

Use this method to load a child leaf of the current tree node into the SmartNavigation chart rowset and the component buffer. The order for the leaf within its chart level is specified by this method.

Parameters

&chart_rowset	Specifies the SmartNavigation chart rowset. Typically, this is the rowset returned by the GetABNChartRowSet function.
&relactions_rowset	Specifies the related actions rowset. Typically, this is the rowset returned by the GetABNRelActnRowSet function.
order	Specify the order for the leaf as a number.

Note: For a given chart level, all chart leaves must have a display order greater than zero.

Returns

None.

Example

```
&ChildLeaf.LoadABNChartOrdered(&chart_rs, &ra_rs, 5);
```

Related Links

LoadABNChart

"GetABNChartRowSet" (PeopleTools 8.54: PeopleCode Language Reference)

"GetABNRelActnRowSet" (PeopleTools 8.54: PeopleCode Language Reference)

MoveAsChild

Syntax

MoveAsChild(*Node*)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

The MoveAsChild method moves the leaf executing the method to a different node in the tree. The leaf becomes the first child leaf under the node, even though there is no explicit ordering of leaves: leaves take the order of the alphanumeric database sort on their range fields. The specified node becomes the new parent to the leaf.

Parameters

Node Specify a node object. This parameter value must be an object, not a string or a name.

Note: To specify a node name, not a node object, use the MoveAsChildByName method.

Returns

A number; 0 if the move is successful.

Example

The following example moves leaf 8001 from node 10100 (old parent) to node 00001 (new parent)

```
&MY_LEAF = &MY_TREE.FindLeaf("8001", "8001");
&NEW_PARENT = &MY_TREE.FindNode("00001", "");
If &NEW_PARENT <> Null Then
   &RET_VALUE = &MY_LEAF.MoveAsChild(&NEW_PARENT);
End-If;
```

Related Links

MoveAsChildByName

MoveAsChildByName

Syntax

MoveAsChildByName(*NodeName*)

Description

The MoveAsChildByName method moves the leaf executing the method to a different node in the tree. The leaf becomes the first child leaf under the node, although there is no explicit ordering of leaves: leaves take the order of the alphanumeric database sort on their range fields. The specified node becomes the new parent to the leaf. The node specified by *NodeName* must be a valid node name.

Parameters

NodeName Specify the name of a node. *NodeName* must be a valid node for the existing tree. This parameter takes a string value.

Note: To specify a node object, not a node name, use the MoveAsChild method.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

A number; 0 if the move is successful.

Example

The following example moves leaf 8001 from node 10100 (old parent) to node 00001 (new parent)

```
&MY_LEAF = &MY_TREE.FindLeaf("8001", "8001");
If &MY_LEAF <> Null Then
   &RET_VALE = &MY_LEAF.MoveAsChildByName("00001");
End-If;
```

Related Links

MoveAsChild

MoveAsSib

Syntax

MoveAsSib(*Leaf*)

Description

The MoveAsSib method moves the leaf executing the method to a new place in the tree. The current leaf becomes the next sibling leaf under the specified leaf object, although there is no explicit ordering of leaves: leaves take the order of the alphanumeric database sort on their range fields.

Parameters

Leaf	Specify a leaf object. This parameter value must be an object, not a string or a name.

Note: To specify a range, not a leaf object, use the MoveAsSibByRange method.

Returns

A number; 0 if the move is successful.

Example

```
&MYLEAF = &MYTREE.FindLeaf("8000", "8000");
&MYLEAF2 = &MYTREE.FindLeaf("9000", "9000");
&RET_VALUE = &MYLEAF.MoveAsSib(&MYLEAF2);
```

Related Links

MoveAsSibByRange

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

MoveAsSibByRange

Syntax

MoveAsSibByRange(*RangeFrom*, *RangeTo*)

Description

The MoveAsSibByRange method moves the leaf executing the method to a new place in the tree. The current leaf becomes the next sibling leaf under the specified leaf object.

Parameters

RangeFrom Specify the starting range of the leaf that you want as the parent of the leaf executing the method. This parameter takes a string value.

RangeTo Specify the ending range of the leaf that you want as the parent of the leaf executing the method. This parameter takes a string value.

Note: To specify a leaf object, not a range, use the MoveAsSib method.

Returns

A number; 0 if the move is successful.

Example

```
&MYLEAF = &MYTREE.FindLeaf("8000", "8000");
&RET_VALUE = &MYLEAF.MoveAsSibByRange("9000", "9000");
```

Related Links

MoveAsSib

PasteSib

Syntax

PasteSib()

Description

The PasteSib method makes the leaf from the buffer (clipboard) a sibling to the leaf executing the method. You must use the Cut leaf method before you can paste a leaf.

You can have only one object at a time on the clipboard. If you cut another leaf or node, the leaf in the clipboard is overwritten.

Parameters

None.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

A number; 0 if the paste is successful.

RefreshDescription

Syntax

RefreshDescription(*expand_range*)

Description

Use this method to reload the tree leaf's description from the database.

Note: This method is currently supported for what is known as a single detail leaf. Do not use this method with ranged or dynamic leaves.

Parameters

expand_range	Specify a Boolean value; however, this parameter is currently ignored. **Note:** This parameter is reserved for future use.

Returns

A number: 0 if the refresh was successful.

Related Links

Description

UpdateRanges

Syntax

UpdateRanges(*RangeFrom*, *RangeTo*)

Description

The UpdateRanges method performs validation of edited ranges, updating as necessary.

Parameters

RangeFrom	Specify the starting range of the leaf that you updated. This parameter takes a string value.
RangeTo	Specify the ending range of the leaf you want updated. This parameter takes a string value.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

A number; 0 if the update is successful.

Leaf Class Properties

In this section, we discuss the Leaf class properties. The properties are discussed in alphabetical order.

Description

Description

Use this property to return the tree leaf's description as a string.

Note: This property is currently supported for what is known as a single detail leaf. Do not use this property with ranged or dynamic leaves.

This property is read-only.

Related Links

RefreshDescription

DisplayLevelNumber

Description

When using the Tree API to create a graphic representation of the tree (such as for HTML Tree Manager or other application pages) use this property to indicate the *display* level, that is, tell the user how many levels deep the leaf is. This is generally used for trees where levels aren't used and the LevelNumber property always returns 0. This property always returns a number.

This property is read-only.

Related Links

LevelNumber

Dynamic

Description

This property specifies whether the leaf has a dynamic range or a specified range. If you set this property to True, the leaf has a dynamic range. If this is a new leaf, and you do not set this property, the value is automatically set is False.

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

"Understanding Steps to Create Trees" (PeopleTools 8.54: Tree Manager)

HasNextSib

Description

This property returns True if the leaf has a next sibling, that is, it isn't the last leaf listed under the parent node.

This property is read-only.

HasPrevSib

Description

This property returns True if the leaf has a previous sibling, that is, it isn't the first leaf listed under the parent node.

This property is read-only.

ImageName

Description

This property sets the which image is used to display the leaf. This property takes a string value for the image name of the leaf.

This property is read-write.

IsChanged

Description

This property returns True if the leaf has been edited or changed.

This property is read-only.

Example

```
If &MYLEAF.IsChanged Then
   &MYTREE.Save();
End-If;
```

IsCut

Description

This property returns True if the leaf has been cut from the displayed tree. This property is generally used with the HTML Tree Manager.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-only.

IsDeleted

Description

This property returns True if the leaf has been deleted from the tree but the tree hasn't been saved.

This property is read-only.

IsInserted

Description

This property returns True if the leaf has been inserted as a new leaf in the tree but the tree hasn't been saved.

This property is read-only.

NextSib

Description

This property returns a leaf object associated with the next sibling leaf. The next sibling of a leaf is the leaf appearing under the current leaf. If there is no next sibling and you try to assign it to a variable, you receive a runtime error.

This property is read-only.

Example

The following code traversed the leaves from top to bottom.

```
While &MYLEAF.HasNextSib
   &MYLEAF = &MYLEAF.NextSib;
   /* do some processing */
End-While;
```

Parent

Description

This property returns a node object associated with the parent node for the leaf.

This property is read-only.

Example

```
&PARENTNODE = &MYLEAF.Parent;
/* do node processing with node object */
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

PrevSib

Description

This property returns a leaf object associated with the previous sibling leaf. The previous sibling of a leaf is the leaf appearing above the current leaf. If there is no previous sibling and you try to assign it to a variable, you receive a runtime error.

This property is read-only.

Example

The following code traverses the leaves from bottom to top.

```
While &MYLEAF.HasPrevSib
   &MYLEAF = &MYLEAF.PrevSib;
   /* do some processing */
End-While;
```

RangeFrom

Description

This property returns the starting range, as a string, of the leaf.

This property is read-write.

RangeTo

Description

This property returns the ending range, as a string, of the leaf.

This property is read-write.

TreeBranchName

Description

This property returns the branch name of the tree as a string if the tree is branched. If not branched, this property returns a blank string.

This property is read-only.

TreeEffDt

Description

This property returns the effective date of the tree as a string if the tree is effective-dated. If not effective-dated, this property returns a blank string.

This property is read-only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

TreeName

Description

This property returns the name of the tree as a string.

This property is read-only.

TreeSetId

Description

This property returns the SetID of the tree as a string if the tree has a SetID. If the tree doesn't have a SetID, this property returns a blank string.

This property is read-only.

TreeUserKeyValue

Description

This property returns the UserKeyValue of the tree as a string if the tree has a UserKeyValue. If the tree doesn't have a UserKeyValue, this property returns a blank string.

This property is read-only.

Level Collection

Level collection is instantiated from a tree object with the Levels property.

See Levels.

Level Collection Methods

In this section, we discuss the Level Collection methods. The methods are discussed in alphabetical order.

Add

Syntax

Add(*LevelName*)

Description

The Add method adds a new level called *LevelName* to the database. The specified level must be a new level, that is, it cannot exist in the database. *LevelName* takes a string value.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Note: *LevelName* must be 8 characters or less.

If no levels currently exist in the tree, the level is added at the top level. If levels already exist in the tree, the new level is added as the last level. You can change the level number of a level using the Number property.

If the new level is the first level, the AllValuesAudit property is automatically set to True.

The new level is notadded to the database until the tree is explicitly saved.

This method returns a reference to the new level object.

Related Links

Number, AllValuesAudit

Item

Syntax

Item(*LevelName, LevelNumber*)

Description

The Item method returns a reference to the specified level in the level collection executing the method as an object. The *LevelName* parameter specifies the name of the level to access. This parameter takes a string value. The *LevelNumber* parameter specifies the number at which the level exists. This parameter takes a number value. For example, suppose your level collection contains the following levels, in this order:

1. CORPORATE
2. COMPANY
3. DIVISION
4. DEPARTMENT
5. BRANCH

You want to access the fourth level, DEPARTMENT. You would use the following code:

```
&MYLEVEL = &LVLCOLLECTION.Item("DEPARTMENT", 4);
```

Remove

Syntax

Remove()

Description

The Remove method deletes the current level from the database. You can use this method only after you have used the First, Next, or Item properties: otherwise the system doesn’t know which level to delete

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

from the tree. If no level has been indicated yet system tries to remove the last level. If the level to remove has nodes associated with it, the system doesn't remove the level. The rest of the levels in the collection after the deleted level are moved up in the list and renumbered so that the levels remain consecutively numbered.

Returns

A number; 0 if the level is successfully removed.

Level Collection Properties

In this section, we discuss the Level collection properties. The properties are discussed in alphabetical order.

Count

Description

Returns the number of levels for the level collection object.

First

Description

The First property returns a reference to the first level in the level collection executing the method as an open object.

Last

Description

The Last property returns a reference to the last level in the level collection executing the method as an open object.

Next

Description

The Next property returns a reference to the next level in the level collection executing the method as an open object. You can use this method only after you have used either the First or Item properties: otherwise the system doesn’t know where to start in the tree.

Level Class

Level objects are instantiated from the level class collection object with the Item method or one of the following properties:

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- First
- Last
- Next

See Item, First, Last, Next.

Level Class Methods

In this section, we discuss the Leaf class properties. The properties are discussed in alphabetical order.

Create

Syntax

```
Create(LevelName, LevelNumber)
```

Description

Note: This method has been deprecated. If you create a level using this method, there is no way of saving the level to the database. Use the Add level collection method instead.

Level Class Properties

In this section, we discuss the Level class properties. The properties are discussed in alphabetical order.

AllValuesAudit

Description

This property specifies whether PeopleSoft Tree Manager permits nodes to skip over this level. To allow nodes to skip this level, specify this parameter as True. If you are creating a new level, and this level is the first level in a tree, this property is automatically set to True. If the level isn't the first level, this property is set to False by default..

This property is read-write.

Related Links

"Modifying Tree Definitions" (PeopleTools 8.54: Tree Manager)

Description

Description

This property returns the description of the level.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-write.

Name

Description

This property returns the name of the level.

This property is read-write.

Number

Description

This property returns the number of the level.

Note: Though you can use this property to set the level of the number, you should not do so, as level numbers are automatically assigned when the level is inserted to the level collection using the Add method.

This property is read-write.

TreeBranchName

Description

This property returns the branch name of the tree as a string if the tree is branched. If not branched, this property returns a blank string.

This property is read-only.

TreeEffDt

Description

This property returns the effective date of the tree as a string if the tree is effective-dated. If not-effective dated, this property returns a blank string.

This property is read-only.

TreeName

Description

This property returns the name of the tree as a string.

This property is read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

TreeSetId

Description

This property returns the SetID of the tree as a string if the tree has a SetID. If the tree doesn't have a SetID, this property returns a blank string.

This property is read-only.

TreeUserKeyValue

Description

This property returns the UserKeyValue of the tree as a string if the tree has a UserKeyValue. If the tree doesn't have a UserKeyValue, this property returns a blank string.

Node Class

Node objects are instantiated from other tree classes, as follows:

- From a tree object with the FindNode method.
- From a leaf object with the Parent property.
- From another node object with the FirstChildNode, NextSib, PrevSib, and Parent properties.

See FindNode, FirstChildNode, NextSib, PrevSib.

See Parent.

See Parent.

Node Class Methods

In this section, we discuss the Node class methods. The methods are discussed in alphabetical order.

Branch

Syntax

Branch()

Description

The Branch method branches the node executing this method, identifying all of its child nodes and leaves as part of that branch. *Branching* means taking a limb of a tree and creating another subtree to hold that limb. (Technically is it not creating a real tree.) The subtree is accessed through the Branches collection.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

After you use the Branch method, you can no longer access the child nodes and leaves of the node that executed the method until you close the current tree, open the new branched tree, and find the node again. To unbranch the tree, use the Unbranch method.

Returns

A number; 0 if method is successful.

Example

```
&MYNODE = &MYTREE.FindNode("10900", "");
&MYNODE.Branch();
```

Related Links

"Working with Tree Branches" (PeopleTools 8.54: Tree Manager)

Cut

Syntax

Cut()

Description

The Cut method cuts the node executing the method and puts it into a buffer (the clipboard). You can then use the PasteSib method to add the node back as a sibling of a different node. You can also use the PasteChild node method to add the node back as a child of a different node.

You can have only one object at a time on the clipboard. If you cut another leaf or node, the node on the clipboard is overwritten.

Parameters

None.

Returns

A number; 0 if method is successful.

Delete

Syntax

Delete()

Description

The Delete method deletes the node object executing the method *from the database.*

Returns

A number; 0 if method is successful.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

DeleteByName

Syntax

DeleteByName(*NodeName*)

Description

The DeleteByName method deletes the specified node from the database. The *NodeName* parameter takes a string value. The node specified by *NodeName* does not have to match the node executing the method. That is, if &MYNODE is associated with node 100200, you can specify a different node with the DeleteByName method. For example:

```
&MYNODE = &MYTREE.FindNode("100200", "");
/* some processing */
&MYNODE.DeleteByName("100300");
```

The node name specified by *NodeName* must be a valid node in the existing open tree object. If *NodeName* doesn't exist, you receive a runtime error.

Returns

A number; 0 if method is successful.

Expand

Syntax

Expand(*ExpandType*)

Description

The Expand method gets the next level of nodes or leaves into memory from the selected node. What leaves or nodes get expanded depends on the *ExpandType*.

Parameters

ExpandType Specifies which leaves or nodes get expanded. Values are:

Value	*Description*
0	Expand only nodes
1	Expand nodes and leaves
2	Expand only one level

Returns

A number; 0 if method is successful.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

```
If (&MYNODE.State = 2 AND &MYNODE.HasChildren);
   /* if node is collapsed */
   &MYNODE.Expand(2);
End-if;
```

GenABNMenuElement

Syntax

GenABNMenuElement(*initial_node*)

Description

Use this method to generate a single <li> element for this tree node.

The <li> element from this node and any sibling nodes and leaves are concatenated to form an HTML code fragment to be consumed by the portal.

Parameters

initial_node	Specifies the initial chart node. Typically, this is returned directly by calling the GetABNInitialNode function.

Returns

A string representing the <li> element for this tree node.

Example

```
&LI_list = &LI_list | &ChildNode.GenABNMenuElement(GetABNInitialNode(&reqParams));
```

Related Links

GenABNMenuElementWithImage

"GetABNInitialNode" (PeopleTools 8.54: PeopleCode Language Reference)

GenABNMenuElementWithImage

Syntax

GenABNMenuElementWithImage(*initial_node*, *fldr_img_class_ID*, *CREF_img_class_ID*)

Description

Use this method to generate a single <li> element for this tree node using the specified custom folder and CREF icons.

The <li> element from this node and any sibling nodes and leaves are concatenated to form an HTML code fragment to be consumed by the portal.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

initial_node

Specifies the initial chart node. Typically, this is returned directly by calling the GetABNInitialNode function.

fldr_img_class_ID

Specifies the class ID for a custom folder icon as a string. This class must be defined in a style sheet, and the style sheet must be assigned to the SmartNavigation folder.

See "Understanding SmartNavigation Icons" (PeopleTools 8.54: Portal Technology).

This is an optional parameter. To use the default folder icon, you can omit this parameter or specify the null string "". However, to ensure forward compatibility, you must specify the null string.

CREF_img_class_ID

Specifies the class ID for a custom CREF icon as a string. This class must be defined in a style sheet, and the style sheet must be assigned to the SmartNavigation folder.

See "Understanding SmartNavigation Icons" (PeopleTools 8.54: Portal Technology).

This is an optional parameter. To use the default CREF icon, you can omit this parameter or specify the null string "". However, to ensure forward compatibility, you must specify the null string.

Returns

A string representing the <li> element for this tree node.

Example

```
&LI_list = &LI_list | &ChildNode.GenABNMenuElementWithImage(GetABNInitialNode(&reqP⇒
arams), "myfldricon", "mycreficon");
```

Related Links

GenABNMenuElement

"GetABNInitialNode" (PeopleTools 8.54: PeopleCode Language Reference)

GenBreadCrumbs

Syntax

GenBreadCrumbs(*list*)

Description

Call the GenBreadCrumbs method from the requested node to generate an HTML code fragment that will be rendered in the browser as breadcrumbs.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The <li> elements in the input string are created by the GenRelatedActions and GenABNMenuElement methods of the Node class, and the GenABNMenuElement method of the Leaf class.

Parameters

list	Specifies the list of elements as a string.

Returns

A string with the <li> elements for the bread crumbs for this tree node appended.

Example

The following example shows how the list of <li> elements is created for a node. In this example, <li> elements are generated for related actions, the first child node, and child leaves. This list is then passed to the GenHTMLMenu function.

```
&LI_lis = &MyNode.GenBreadCrumbs(&LI_list);
```

Related Links

GenABNMenuElement
GenABNMenuElement
GenRelatedActions

GenRelatedActions

Syntax

GenRelatedActions()

Description

Use this method to generate the list of <li> elements for the related actions menu for the current tree node. Call this function before calling GenABNMenuElement for the same node. The <li> elements from this function, from this node, from any child nodes and leaves traversed, and from the parent tree nodes are concatenated to form an HTML code fragment to be consumed by the portal.

Parameters

None.

Returns

A string representing the <li> elements for the related actions for this tree node.

Example

```
&LI_list = &LI_list | &MyNode.GenRelatedActions();
```

Related Links

GenABNMenuElement

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GenBreadCrumbs

InsertChildLeaf

Syntax

InsertChildLeaf(*RangeFrom*, *RangeTo*)

Description

The InsertChildLeaf method inserts a new leaf (as specified by the range parameters) under the node object executing the method.

A leaf object associated with the new leaf is returned.

The new leaf is inserted as the child of the current node, although there is no explicit ordering of leaves: leaves take the order of the alphanumeric database sort on their range fields.

Note: You must specify a range with this method. To insert a dynamic range leaf (that is, one with no range) use the InsertDynChildLeaf method.

Parameters

RangeFrom	Specify the starting range of the new leaf. This parameter takes a string value.
RangeTo	Specify the ending range of the new leaf. This parameter takes a string value.

Returns

A leaf object associated with the new leaf. If this method fails, it returns either False or a Null object reference, depending upon the type of error encountered. The best way to test whether the object was inserted is to test the result using either the All or None functions.

Example

```
&NEWLEAF = &MYLNODE.InsertChildLeaf("10090", "10100");

If None(&NEWLEAF) Then
   /* Error Processing */
End-If;
```

Related Links

InsertDynChildLeaf

"All" (PeopleTools 8.54: PeopleCode Language Reference)

"None" (PeopleTools 8.54: PeopleCode Language Reference)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

InsertChildNode

Syntax

InsertChildNode(*NodeName*)

Description

The InsertChildNode method inserts a new node (as specified by *NodeName*) as a child node under the node object executing the method. The node specified by *NodeName* must be a new node. You receive an error if the node already exists.

A node object associated with the new node is returned. If the new node isn't inserted successfully, the method returns False or Null.

Parameters

NodeName Specify a name for the new node. This parameter takes a string value. *NodeName* must not already exist.

Returns

A reference to the new node. If this method fails, it returns either False or a Null object reference, depending upon the type of error encountered. The best way to test whether the object was inserted is to test the result using either the All or None functions.

Example

```
&NEWNODE = &MYNODE.InsertChildNode("100500");

If None(&NEWNODE) Then
   /* Do error processing */
End-If;
```

Related Links

"All" (PeopleTools 8.54: PeopleCode Language Reference)

"None" (PeopleTools 8.54: PeopleCode Language Reference)

InsertChildRecord

Syntax

InsertChildRecord(*NodeName*)

Description

The InsertChildRecord method inserts a new record (as specified by *NodeName*) as a node under the parent node executing this method. This method works only on trees that are Query Access Trees.

A node object associated with the new node is returned, otherwise this method returns False or Null.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

NodeName	Specify an existing record name. This parameter takes a string value. This record must not already be a node under the parent node (that is, a parent node can't have the same record as a child node more than once.)

Returns

A reference to the new node. If this method fails, it returns either False or a Null object reference, depending upon the type of error encountered. The best way to test whether the object was inserted is to test the result using either the All or None functions.

Example

```
&NEWNODE = &MYNODE.InsertChildRecord("PERSONAL_DATA");

If None(&NEWNODE) Then
   /* Do error processing */
End-if;
```

Related Links

"All" (PeopleTools 8.54: PeopleCode Language Reference)

"None" (PeopleTools 8.54: PeopleCode Language Reference)

InsertDynChildLeaf

Syntax

InsertDynChildLeaf()

Description

The InsertDynChildLeaf method inserts a dynamic leaf under the node object executing the method.

A leaf object associated with the new leaf is returned.

The new leaf is inserted as the child of the current node, although there is no explicit ordering of leaves.

Note: To insert a leaf with a specific range, use the InsertChildLeaf method.

Parameters

None.

Returns

A leaf object associated with the new leaf. If this method fails, it returns either False or a Null object reference, depending upon the type of error encountered. The best way to test whether the object was inserted is to test the result using either the All or None functions.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

```
&NEWLEAF = &MYLNODE.InsertDynChildLeaf();

If None(&NEWLEAF) Then
   /* Do error processing */
End-If;
```

Related Links

InsertChildLeaf

"All" (PeopleTools 8.54: PeopleCode Language Reference)

"None" (PeopleTools 8.54: PeopleCode Language Reference)

InsertSib

Syntax

InsertSib(*NodeName*)

Description

The InsertSib method inserts a new node (as specified by *NodeName*) as a sibling node to the node object executing the method. The node specified by *NodeName* must be a *new* node. You receive an error if the node already exists.

A node object associated with the new node is returned. If the new node isn't inserted successfully, the method returns Null.

Parameters

NodeName	Specify a name for the new node. This parameter takes a string value. *NodeName* must not already exist.

Returns

A reference to the new node. If this method fails, it returns False.

Example

```
&NEWNODE = &MYNODE.InsertSib("100500");
```

InsertSibRecord

Syntax

InsertSibRecord(*NodeName*)

Description

The InsertSibRecord method inserts a new record (as specified by *NodeName*) as a sibling node of the parent node executing this method. This method works only on trees that are Query Access Trees.

A node object associated with the new node is returned, otherwise this method returns Null.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

NodeName	Specify an existing record name. This parameter takes a string value. This record must not already be a sibling node for the node executing the object (that is, a node can't have the same record as a node more than once.)

Returns

A reference to the new node. If this method fails, it returns False.

Example

```
&NEWNODE = &MYNODE.InsertSibRecord("PERSONAL_DATA");
```

LoadABNChart

Syntax

LoadABNChart(*&chart_rowset*, *&relactions_rowset*, *requested_node*, *initial_node*)

Description

Use this method to load the requested tree node into the SmartNavigation chart rowset and the component buffer.

Parameters

&chart_rowset	Specifies the SmartNavigation chart rowset. Typically, this is the rowset returned by the GetABNChartRowSet function.
&relactions_rowset	Specifies the related actions rowset. Typically, this is the rowset returned by the GetABNRelActnRowSet function.
requested_node	Specifies as a Boolean value whether the calling node is the requested node.
initial_node	Specifies the initial chart node. Typically, this is returned directly by calling the GetABNInitialNode function.

Returns

None.

Example

```
&MyNode.LoadABNChart(&chart_rs, &ra_rs, True, GetABNInitialNode(&reqParams));
&ChildNode.LoadABNChart(&chart_rs, &ra_rs, False, GetABNInitialNode(&reqParams));
```

Related Links

LoadABNChartOrdered

"GetABNChartRowSet" (PeopleTools 8.54: PeopleCode Language Reference)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

"GetABNInitialNode" (PeopleTools 8.54: PeopleCode Language Reference)
"GetABNRelActnRowSet" (PeopleTools 8.54: PeopleCode Language Reference)

LoadABNChartOrdered

Syntax

```
LoadABNChartOrdered(&chart_rowset, &relactions_rowset, requested_node, initial_node,
order)
```

Description

Use this method to load the requested tree node into the SmartNavigation chart rowset and the component buffer. The order for this node within its chart level is specified by this method.

Parameters

&chart_rowset Specifies the SmartNavigation chart rowset. Typically, this is the rowset returned by the GetABNChartRowSet function.

&relactions_rowset Specifies the related actions rowset. Typically, this is the rowset returned by the GetABNRelActnRowSet function.

requested_node Specifies as a Boolean value whether the calling node is the requested node.

initial_node Specifies the initial chart node. Typically, this is returned directly by calling the GetABNInitialNode function.

order Specify the order for the node as a number.

Note: For a given chart level, all chart leaves must have a display order greater than zero.

Returns

None.

Example

```
&MyNode.LoadABNChartOrdered(&chart_rs, &ra_rs, True, GetABNInitialNode(&reqParams),⇒
 5);
&ChildNode.LoadABNChartOrdered(&chart_rs, &ra_rs, False, GetABNInitialNode(&reqPara⇒
ms), 5);
```

Related Links

LoadABNChart
"GetABNChartRowSet" (PeopleTools 8.54: PeopleCode Language Reference)
"GetABNInitialNode" (PeopleTools 8.54: PeopleCode Language Reference)
"GetABNRelActnRowSet" (PeopleTools 8.54: PeopleCode Language Reference)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

MoveAsChild

Syntax

MoveAsChild(*Node*)

Description

The MoveAsChild method moves the node executing the method to a different node in the tree. The node becomes the first child node under the named node. The specified node becomes the new parent to the child node. The node specified by *Node* must be an existing node in the current tree. All child nodes and details are also moved with the node.

Parameters

Node	Specify a node object. This parameter value must be an object, not a string or a name.

Note: To specify a node name, not a node object, use the MoveAsChildByName method.

Returns

A number; 0 if method is successful.

Example

The following example moves node 10200 from node 10100 (old parent) to node 00001 (new parent).

```
&MY_NODE = &MY_TREE.FindNode("10200", "");
&NEW_PARENT = &MY_TREE.FindNode("00001", "");
If &NEW_PARENT <> Null Then
   &MY_NODE.MoveAsChild(&NEW_PARENT);
End-If;
```

Related Links

MoveAsChildByName

MoveAsChildByName

Syntax

MoveAsChildByName(*NodeName*)

Description

The MoveAsChildByName method moves the node executing the method to a different node in the tree. The node becomes the first child node under the parent node. The specified node becomes the new parent to the node. The node specified by *NodeName* must be a valid node name. All child nodes and details are also moved with the node.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

NodeName Specify the name of a node. This parameter takes a string value. *NodeName* must be a valid node for the existing tree.

Note: To specify a node object, not a node name, use the MoveAsChild method.

Returns

A number; 0 if method is successful.

Example

The following moves node 10200 from node 10100 (old parent) to node 00001 (new parent)

```
&MY_NODE = &MY_TREE.FindNode("10200", "");
If &MY_NODE <> Null Then
   &MY_NODE.MoveAsChildByName("00001");
End-If;
```

Related Links

MoveAsChild

MoveAsSib

Syntax

MoveAsSib(*Node*)

Description

The MoveAsSib method moves the node executing the method to a new place in the tree. The current node becomes the next sibling node under the specified node. All child nodes and details are also moved with the node.

Parameters

Node Specify a node object. This parameter value must be an object, not a string or a name.

Note: To specify a node name, not a node object, use the MoveAsSibByName method.

Returns

A number; 0 if method is successful.

Example

```
&MYNODE = &MYTREE.FindNode("20000", "");
&MYNODE2 = &MYTREE.FindNode("20100", "");
&MYNODE.MoveAsSib(&MYNODE2);
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

MoveAsSibByName

MoveAsSibByName

Syntax

MoveAsSibByName(*NodeName*)

Description

The MoveAsSibByName method moves the node executing the method to a new place in the tree. The current node becomes the next sibling node under the specified node. All child nodes and details are also moved with the node.

Parameters

NodeName	Specify the name of a node. This parameter takes a string value. *NodeName* must be a valid node for the existing tree.

Note: To specify a node object, not a node name, use the MoveAsSib method.

Returns

A number; 0 if method is successful.

Example

```
&MYNODE = &MYTREE.FindNode("20000", "");
&MYNODE.MoveAsSibByName("10100");
```

Related Links

MoveAsSib

PasteChild

Syntax

PasteChild()

Description

The PasteChild method makes the node or leaf from the buffer (clipboard) a child to the node executing the method. You must use the Cut node or leaf method before you can paste a node or leaf.

You can have only one object at a time on the clipboard. If you cut another node or leaf, the node or leaf on the clipboard is overwritten.

Parameters

None.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

A number; 0 if method is successful.

PasteSib

Syntax

PasteSib()

Description

The PasteSib method makes the node from the buffer (clipboard) a sibling to the node executing the method. You must use the Cut node method before you can paste a node.

You can have only one object at a time on the clipboard. If you cut another leaf or node, the node on the clipboard is overwritten.

Parameters

None.

Returns

A number; 0 if method is successful.

RefreshDescription

Syntax

RefreshDescription()

Description

The RefreshDescription method enables you to change the description of a node on a page and have the update be displayed immediately. If you don't use RefreshDescription, you must save the tree and reopen it for the change to be displayed.

Parameters

None.

Returns

A zero (0) if description is refreshed successfully, a different error number otherwise.

Example

```
&result= &NodeObj.refreshdescription();
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Rename

Syntax

Rename(*NodeName*)

Description

The Rename method renames the node object executing the method without changing any other properties. The parameter *NodeName* takes a string value. The node specified by *NodeName* must be a new node. You receive an error if the node already exists.

Note: The Rename method does not rename the node in a user node component. Your application needs to do that.

Returns

A number; 0 if method is successful.

Example

```
&MYNODE = &MYTREE.FindNode("10900", "");
&MYNODE.Rename("10200");
```

SwitchLevel

Syntax

SwitchLevel(*NewLevelNumber*)

Description

The SwitchLevel methods enables you to move a node down from one level to another.

NewLevelNumber must specify a valid level number. For trees in which the Level Use parameter is set to Strictly Enforce Levels, the new level must be at least one level lower than the node’s parent level.

If the level specified by *NewLevelNumber* doesn't exist, it's automatically generated and added to the tree.

Parameters

NewLevelNumber	Specify the level number to where you want the node moved.

Returns

A zero (0) if node is moved successfully, a different error number otherwise.

Unbranch

Syntax

Unbranch()

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

The Unbranch method is the opposite of the Branch method: that is, it unbranches the node executing the method if it is branched. All of the child node and leaves of the node become part of the current open tree and accessible in that tree. You can't unbranch the Root Node in a branched tree.

If the node executing the method isn't branched, you receive a runtime error. Use the IsBranched property to make sure a node is branched.

Returns

A number; 0 if method is successful.

Example

```
&MYNODE = &MYTREE.FindNode("10900", "");
&MYNODE.Unbranch();
```

Related Links

"Working with Tree Branches" (PeopleTools 8.54: Tree Manager)

Node Class Properties

In this section, we discuss the Node class properties. The properties are discussed in alphabetical order.

AllChildCount

Description

This property returns the number of all the child nodes and leaves of the node, that is, all the nodes and leaves below this node.

This property is read-only.

AllChildNodeCount

Description

This property returns the number of child nodes of the node, that is, all the nodes below this node.

To determine all the leaves below a node, subtract the AllChildNodeCount from the AllChildCount

This property is read-only.

Example

To determine all the leaves below a node, use the AllChildNodeCount with the AllChildCount property.

```
&AllCount = (&MyNode.AllChildCount - &MyNode.AllChildNodeCount);
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ChildLeafCount

Description

This property returns the number of immediate child leaves below this node.

This property is read-only.

ChildNodeCount

Description

This property returns the number of immediate child nodes below this node.

This property is read-only.

CollmageName

Description

This property enables you to specify the image name for a collapsed node.

This property is read-write.

Description

Description

This property returns the description of the node.

This property is read-only.

DisplayLevelNumber

Description

When using the Tree API to create a graphic representation of the tree (such as for HTML Tree Manager or other application pages) use this property to indicate the display level, that is, tell the user how many levels deep the node is. This is generally used for trees where levels aren't used and the LevelNumber property always returns 0.

This property is read-only.

Related Links

LevelNumber

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ExpImageName

Description

This property enables you to specify the expanded image name for a node.

This property is read-write.

FirstChildLeaf

Description

This property returns a reference to the first child leaf of the node. This is the leaf that appears highest in the list of children of the node in PeopleSoft Tree Manager.

This property is read-only.

Example

```
&NEWLEAF = &MYNODE.FirstChildLeaf;
```

FirstChildNode

Description

This property returns a reference to the first child node of the node. This is the node that appears highest in the list of children of the node in PeopleSoft Tree Manager.

This property is read-only.

Example

```
&CHILDNODE = &MYNODE.FirstChildNode;
```

HasChildLeaves

Description

This property returns True if the node has immediate child leaves, False otherwise.

This property is read-only.

HasChildNodes

Description

This property returns True if the node has immediate child nodes, False otherwise.

This property is read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

HasChildren

Description

This property returns True if the node has either child leaves or child nodes anywhere in the subtree, not just immediately under the node.

This property is read-only.

HasNextSib

Description

This property returns True if the node has a next sibling, that is, if it isn't the last node.

This property is read-only.

Example

```
While &MYNODE.HasNextSib
   &MYNODE = &MYNODE.NextSib;
   /* do some processing */
End-While;
```

HasPrevSib

Description

This property returns True if the node has a previous sibling, that is, if it isn't the first node.

This property is read-only.

IsBranched

Description

This property returns True if the node is branched, False otherwise.

This property is read-only.

IsChanged

Description

This property returns True if the node has been edited or changed but the current tree hasn't been saved.

This property is read-only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

IsCut

Description

This property returns True if the node has been cut from the displayed tree. This property is generally used with the HTML Tree Manager.

This property is read-only.

IsDeleted

Description

This property returns True if the node has been deleted but the current tree hasn't been saved.

This property is read-only.

IsInserted

Description

This property returns True if the node was inserted as a new node into the tree but the tree hasn't been saved.

This property is read-only.

Example

```
If &MYNODE.IsInserted Then
   &MYTREE.Save();
End-if;
```

IsRoot

Description

This property returns True for both of the following:

- the node is the root node of an unbranched tree.
- the node is the top node of an opened tree branch.

Otherwise, the property returns False.

This property is read-only.

LastChildLeaf

Description

This property returns a reference to the last child leaf of the node. This is the leaf that appears lowest in the list of children of the node in PeopleSoft Tree Manager.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-only.

Example

```
&NEWLEAF = &MYNODE.LastChildLeaf;
```

LastChildNode

Description

This property returns a reference to the last child node of the node. This is the node that appears lowest in the list of children of the node in PeopleSoft Tree Manager.

This property is read-only.

Example

```
&CHILDNODE = &MYNODE.LastChildNode;
```

LevelNumber

Description

This property returns the level number of the node. Values are 1-99 for Strict or Loose level trees. This property returns 0 for trees that don't have levels.

Note: PeopleSoft does not recommend using this property to set the level of the node. Instead, use the SwitchLevel method.

This property is read-write.

Related Links

SwitchLevel

Name

Description

This property returns the name of the node (as a string.) You must set this property to a valid value if you are creating a new node.

Note: Do not use this property to change the name of an existing node. The change will not be reflected in the database. You must use the Rename method to change the name of an existing node.

This property is read-write.

Related Links

Rename

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

NextSib

Description

This property returns a reference to the next sibling node. If there isn't a next sibling node, Null is returned.

This property is read-only.

Example

```
While &MYNODE.HasNextSib
   &MYNODE = &MYNODE.NextSib;
   /* do some processing */
End-While;
```

Parent

Description

This property returns a reference to the node that is the parent of the node executing the property. If the current node has no parent (is a root node) False is returned.

This property is read-only.

Example

```
&PARENT = &MYNODE.Parent;
```

PrevSib

Description

This property returns a reference to the node that is the previous sibling node to the node executing the property. If there isn't a previous sibling, Null is returned.

This property is read-only.

Example

```
If &MYNODE.PrevSib Then
   /* do processing */
End-if;
```

State

Description

This property returns the *state* of the node, that is, does it have children, and are they expanded or collapsed.

See Expand.

The values for this property are:

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Value	*Description*
0	Node has no children
1	Children are expanded
2	Children are collapsed
3	Leaves are collapsed

This property is read-only.

Example

```
&VALUE = &MYNODE.State;
If &VALUE = 2 Then
   &MYNODE.Expand(0);
End-if;
```

TreeBranchName

Description

This property returns the branch name of the tree as a string if the tree is branched. If not branched, this property returns a blank string.

This property is read-only.

TreeEffDt

Description

This property returns the effective date of the tree as a string if the tree is effective-dated. If not effective-dated, this property returns a blank string.

This property is read-only.

TreeName

Description

This property returns the name of the tree as a string.

This property is read-only.

TreeSetId

Description

This property returns the SetID of the tree as a string if the tree has a SetID. If the tree doesn’t have a SetID, this property returns a blank string.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-only.

TreeUserKeyValue

Description

This property returns the UserKeyValue of the tree as a string if the tree has a UserKeyValue. If the tree doesn't have a UserKeyValue, this property returns a blank string.

Type

Description

This property returns the type of the node. This property takes a string value. Values are:

- "G" (Group): normal unbranched node or record group
- "B" (Branched nodes)
- "R" (Query Record): used for Query Access Trees only

This property is read-only.

Tree Class

Tree objects are instantiated from a session object with the GetTree method.

The following code sample gets a tree, then opens the tree structure associated with that tree:

```
Local string &TREE_NAME;
Local string &TREE_DT;
Local ApiObject &MYSESSION, &VC_TREE, &STRUCT;


/* Get and Open the Tree using the Tree API */
&MYSESSION = %Session;

/* Get the Tree Name and Effective Date from the level 0 record */
&TREE_NAME = "CUSTOMER";
&TREE_DT = "1900-01-01";

/* Get and Open the Tree  */

&VC_TREE = &MYSESSION.GetTree();

/* open the tree with read access only */

&VC_TREE.OPEN("BKINV", "", &TREE_NAME, &TREE_DT, "", False);

/* Get and Open Tree Structure */

&STRUCT = VC_TREE.Structure;
```

See GetTree.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Tree Class Methods

In this section, we discuss the Tree class methods. The methods are discussed in alphabetical order.

Audit

Syntax

```
Audit()
```

Description

The Audit method audits the tree object executing the method to determine its validity.

The Audit method can be used only on an open tree, not on a closed tree. This means you must have opened the tree with the Open method before you can audit it.

Returns

A number: 0 if the tree passes all audits. If Audit returns a value not equal to 0, an error is logged.

Related Links

Open
"Understanding the Auditing and Repairing of Trees" (PeopleTools 8.54: Tree Manager)

AuditByName

Syntax

```
AuditByName(SetID, UserKeyValue, TreeName, EffDt, BranchName)
```

Description

The AuditByName method audits the tree specified by the parameters passed to it. The AuditByName method can be used only with a tree identifier, it cannot be used on a fully instantiated, open tree. Before you use the AuditByName method, you must explicitly close any open tree objects (with the Close method.) You receive an error if there are any open trees.

Parameters

SetID

Specify the table indirection key for the tree. This parameter takes a string value. If the tree structure the tree is based on has its IndirectionMethod specified as "S", you must specify a SetID.

If the tree structure doesn’t have its IndirectionMethod specified as "S", you must enter a Null string (that is, two quotation marks with no blank space between them (“”)) for this parameter.

UserKeyValue

Specify the User Key Value for the tree. This parameter takes a string value. If the tree structure the tree is based on has its

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

IndirectionMethod specified as "U" or "B", you must specify a User Key Value.

If the tree structure doesn't have its IndirectionMethod specified as "U" or "B", you must enter a Null string (that is, two quotation marks with no blank space between them ("")) for this parameter.

TreeName Specify the name for this tree. This parameter takes a string value.

EffDt Specify the effective date for this tree. This parameter takes a string value.

BranchName This parameter is required, but it is unused in this release. You must enter a Null string (that is, two quotation marks with no blank space between them ("")) for this parameter.

Returns

A number: 0 if the tree passes all audits. If this method returns a value not equal to 0, an error is logged.

Example

```
&ISVALID = &MYTREE.AuditByName("", "", "PERSONAL_DATA", "05-05-1997", "");
```

Related Links

Close
IndirectionMethod
"Understanding the Auditing and Repairing of Trees" (PeopleTools 8.54: Tree Manager)

Close

Syntax

```
Close()
```

Description

The Close method closes the tree, freeing the memory associated with that object, and discarding any changes made to the tree since the last save. The Close method can be used only on an open tree, not a closed tree. This means you must have opened the tree with the Open method before you can close it. To save any changes, you must use the Save method before using Close.

Returns

A number: 0 if the method completed successfully.

Related Links

Open

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Copy

Syntax

```
Copy(FromSetId, FromUserKeyValue, FromTreeName, FromEffDt, FromBranchName, ToSetId,
ToUserKeyValue, ToTreeName, ToEffDt, ToBranchName)
```

Description

The Copy method copies from the tree identified by the *From* parameters and copies it to the tree identified with the *To* parameters. The tree specified by the *To* parameters must be a *new* tree. You receive an error if the tree already exists. The tree specified by the *From* parameters does *not* have to match the tree identifier executing the method.

The Copy method can be used only with a *closed* tree, it cannot be used on an open tree. Before you use the Copy method, you must explicitly close any open tree objects (with the Close method.) You receive an error if there are any open trees.

To access the new tree, you must use the Open method.

Parameters

FromSetId

Specify the table indirection key for the tree to be copied from. This parameter takes a string value. If the tree structure the tree is based on has its IndirectionMethod specified as "S", you must specify a SetID.

If the tree structure doesn't have its IndirectionMethod specified as "S", you must enter a Null string (that is, two quotation marks with no blank space between them (""")) for this parameter.

FromUserKeyValue

Specify the User Key Value for the tree to be copied from. This parameter takes a string value. If the tree structure the tree is based on has its IndirectionMethod specified as "U" or "B", you must specify a User Key Value.

If the tree structure doesn't have its IndirectionMethod specified as "U" or "B", you must enter a Null string (that is, two quotation marks with no blank space between them (""")) for this parameter.

FromTreeName

Specify the name for the tree to be copied from. This parameter takes a string value.

FromEffDt

Specify the effective date for the tree to be copied from. This parameter takes a string value.

FromBranchName

This parameter is required, but it is unused in this release. You must enter a Null string (that is, two quotation marks with no blank space between them (""")) for this parameter.

ToSetId

Specify the table indirection key for the tree to be copied to. This parameter takes a string value. If the tree structure the tree is based on has its IndirectionMethod specified as "S", you must specify a SetID.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

If the tree structure doesn't have its IndirectionMethod specified as "S", you must enter a Null string (that is, two quotation marks with no blank space between them ("")) for this parameter.

ToUserKeyValue

Specify the User Key Value for the tree to be copied to. This parameter takes a string value. If the tree structure the tree is based on has its IndirectionMethod specified as "U" or "B", you must specify a User Key Value.

If the tree structure doesn't have its IndirectionMethod specified as "U" or "B" you must enter a Null string (that is, two quotation marks with no blank space between them ("")) for this parameter.

ToTreeName

Specify the name for the tree to be copied to. This parameter takes a string value.

ToEffDt

Specify the effective date for the tree to be copied to. This parameter takes a string value.

ToBranchName

This parameter is required, but it is unused in this release. You must enter a Null string (that is, two quotation marks with no blank space between them ("")) for this parameter.

Returns

An integer: 0 if copied successfully.

Example

```
&MYTREE.Copy("","","PERSONAL_DATA", "05-05-1997", "", "","","PERSONAL_EDIT1", "05-0⇒
5-1997", "");
```

Related Links

Close
Open
IndirectionMethod

Create

Syntax

Create(*SetID*, *UserKeyValue*, *TreeName*, *EffDt*, *StructureName*)

Description

The Create method creates a new tree, based on the parameters passed with the method. The specified tree must be a new tree. You receive an error if the tree already exists.

The Create method can be used only with a closed tree, it cannot be used on an open tree. Before you use the Create method, you must explicitly close any open tree objects (with the Close method.) You receive an error if there are any open trees.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

After you create a new tree, you don't have to open it with the Open method. The existing tree object points to the new tree.

The tree structure specified with *StructureName* determines what database fields the new tree is based on, what pages you can use to create tree nodes and detail values, and what record definitions PeopleSoft Tree Manager saves tree-related data in. The tree structure must already exist.

The new tree must be saved (Save, SaveAs, and so on) for this tree to be saved to the database.

Parameters

SetID

Specify the table indirection key for the tree. This parameter takes a string value. If the tree structure the tree is based on has its IndirectionMethod specified as "S", you must specify a SetID.

If the tree structure doesn’t have its IndirectionMethod specified as "S", you must enter a Null string (that is, two quotation marks with no blank space between them (“”)) for this parameter.

UserKeyValue

Specify the User Key Value for the tree. This parameter takes a string value. If the tree structure the tree is based on has its IndirectionMethod specified as "U" or "B", you must specify a User Key Value.

If the tree structure doesn’t have its IndirectionMethod specified as "U" or "B", you must enter a Null string (that is, two quotation marks with no blank space between them (“”)) for this parameter.

TreeName

Specify the name for this tree. This parameter takes a string value.

EffDt

Specify the effective date for this tree. This parameter takes a string value.

StructureID

Specify the name of the tree structure to use for this tree. This parameter takes a string value.

Returns

An integer: 0 if created successfully.

Example

```
&MYTREE.Create("","","PERSONAL_NEW", "05-05-1997", "PERSONAL_DATA");
```

Related Links

Close

IndirectionMethod

"Understanding Steps to Create Trees" (PeopleTools 8.54: Tree Manager)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Delete

Syntax

Delete(*SetID*, *UserKeyValue*, *TreeName*, *EffDt*, *BranchName*)

Description

The Delete method deletes the specified tree from the database. The Delete method can be used only with a closed tree, it cannot be used on an open tree. Before you use the Delete method, you must explicitly close any open tree objects (with the Close method.) You receive an error if there are any open trees.

The specified tree does not have to match the tree identifier executing the method.

Parameters

SetID

Specify the table indirection key for the tree. This parameter takes a string value. If the tree structure the tree is based on has its IndirectionMethod specified as "S", you must specify a SetID.

If the tree structure doesn't have its IndirectionMethod specified as "S", you must enter a Null string (that is, two quotation marks with no blank space between them ("")) for this parameter.

UserKeyValue

Specify the User Key Value for the tree. This parameter takes a string value. If the tree structure the tree is based on has its IndirectionMethod specified as "U" or "B", you must specify a User Key Value.

If the tree structure doesn't have its IndirectionMethod specified as "U" or "B", you must enter a Null string (that is, two quotation marks with no blank space between them ("")) for this parameter.

TreeName

Specify the name for this tree. This parameter takes a string value.

EffDt

Specify the effective date for this tree. This parameter takes a string value.

BranchName

Specify the name of the branch for the tree. This parameter takes a string value. If the tree is unbranched, you must enter a Null string (that is, two quotation marks with no blank space between them ("")) for this parameter.

Returns

An integer: 0 if deleted successfully.

Example

```
&MYTREE=&Session.GetTree();
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
If ALL(&MYTREE) Then
   &RETVALUE = &MYTREE.Delete("","","PERSONAL_REN2", "05-05-1997", "");
End-If;
```

Related Links

Close

IndirectionMethod

Exists

Syntax

Exists(*SetID*, *UserKeyValue*, *TreeName*, *EffDt*, *BranchName*)

Description

The Exists method finds an existing tree, as specified by the parameters. The parameters must specify a unique tree. If a tree matching the parameters is found, the method returns 0. This method works with either open or closed trees.

Parameters

SetID

Specify the table indirection key for the tree. This parameter takes a string value. If the tree structure the tree is based on has its IndirectionMethod specified as "S", you must specify a SetID.

If the tree structure doesn’t have its IndirectionMethod specified as "S", you must enter a Null string (that is, two quotation marks with no blank space between them (")) for this parameter.

UserKeyValue

Specify the User Key Value for the tree. This parameter takes a string value. If the tree structure the tree is based on has its IndirectionMethod specified as "U" or "B", you must specify a User Key Value.

If the tree structure doesn’t have its IndirectionMethod specified as "U" or "B", you must enter a Null string (that is, two quotation marks with no blank space between them (")) for this parameter.

TreeName

Specify the name for this tree. This parameter takes a string value.

EffDt

Specify the effective date for this tree. This parameter takes a string value.

BranchName

This parameter is required, but it is unused in this release. You must enter a Null string (that is, two quotation marks with no blank space between them (")) for this parameter.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

An integer: 0 if tree exists.

Example

```
&RSLT = &MYTREE.Exists("", "", "VENDOR_PER_DATA", "05-03-1998", "");

If &RSLT = 0 Then
   /* tree exists, do processing */
Else
   /* tree doesn't exist, do error processing */
End-if;
```

Related Links

IndirectionMethod

FindLeaf

Syntax

FindLeaf(*RangeFrom*, *RangeTo*)

Description

The FindLeaf method finds an existing leaf (specified by the *range* parameters) in the tree executing this method. If the leaf is found, a leaf object is returned. If the leaf isn't found, a Null is returned.

You can use wildcards with the *range* parameters. Use an asterisk (*) in place of a number of characters. Use a question mark (?) in place of one character. You can also provide one of the ranges, and specify a Null string for the other.

Suppose you wanted to find the leaf with the range 81005 to 82000. The following would be valid:

```
&MyLeaf = &MyTree.FindLeaf("81*", "82000");
```

This would also be valid:

```
&MyLeaf = &MyTree.FindLeaf("8100?", "82000");
```

You could also specify this:

```
&MYLEAF = &MYTREE.FindLeaf("81000", "");
```

If you specify the exact same value for both *RangeFrom* and *RangeTo*, the *RangeTo* parameter is ignored.

Parameters

RangeFrom	Specify the starting range of the leaf to be found. This parameter takes a string value.
RangeTo	Specify the ending range of the leaf to be found. This parameter takes a string value.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

A reference to a leaf object.

Example

```
&MYLEAF = &MYTREE.FindLeaf("81000", "");
```

FindNode

Syntax

FindNode(*NodeName*, *Description*)

Description

The FindNode method returns a reference to the node object specified by the parameters passed to the method. If the node is found, a node object is returned. If the node isn't found, a Null is returned.

Note: If you've only specified a node name, and the node you're searching for is in an unexpanded portion of the tree, this method expands the tree down to that node. If you've only specified a node description the search, occurs only in the memory. If the node isn't found, the tree is not expanded.

You should specify either the node name other description, not both. You should specify a Null string for the other. If both are provided, only the node name is used and the description is ignored.

You can use wildcards with the parameters. Use an asterisk (*) in place of a number of characters. Use a question mark (?) in place of one character.

Suppose you wanted to find the node called 10200, with a description of "Human Resources". The following would be valid:

```
&MyNode = &MyTree.FindNode("", "Human*");
```

This would also be valid:

```
&MyNode = &MyTree.FindNode("1020?", "");
```

You could also use the following:

```
&MYNODE = &MYTREE.FindNode("10200", "");
```

Note: If you're searching using wildcared characters and more than one node matches the search conditions, only the first occurence of the node is returned

---

Parameters

NodeName	Specify the name of the node that you want to find. This parameter takes a string value. Specify either the node name or the description.
Description	Specify the description of the node that you want to find. This parameter takes a string value. Specify either the node name or the description.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

A reference to a node object.

Example

```
&MYNODE = &MYTREE.FindNode("10200", "");
```

FindRoot

Syntax

FindRoot()

Description

The FindRoot method returns a reference to the root node object of the tree object executing the method. This method can be used only on an open tree, not on a closed tree. This means you must have opened the tree with the Open method before you can find the root node.

This method returns an error if the tree has no nodes associated with it.

Returns

A reference to a node object.

Example

```
&MYNODE = &MYTREE.FindRoot();
```

Related Links

Open

InsertRoot

Syntax

InsertRoot(*NodeName*)

Description

The InsertRoot method inserts a node at the top of the tree object executing the method. *NodeName* is the name of the node you are creating. This parameter takes a string value. The InsertRoot method can be used only on an open tree, not on a closed tree. This means you must have opened the tree with the Open method before you can insert any nodes.

You can insert the root node only in a new tree, that is, a tree that was just created with the Create method. Also, after you create a new tree, you must insert the root node before you can insert any other nodes.

In a strict level tree, the first level must be defined before you can insert the root node.

This method returns an error if the tree already has nodes in it.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

A reference to a node object.

Example

```
&MyRootNode = &MYTREE.InsertRoot("000001");
```

Related Links

Open

LeafExists

Syntax

LeafExists(*RangeFrom*, *RangeTo*)

Description

The LeafExists method enables you to verify if the leaf specified by the parameters exists in the current tree.

Suppose you wanted to check the leaf with the range 81005 to 82000 exists. The following would be valid:

```
&MyResult = &MyTree.LeafExists("81005", "82000");
```

This would also be valid, and would check on leaves up to 82000:

```
&MyResult = &MyTree.LeafExists("", "82000");
```

If you specify the exact same value for both *RangeFrom* and *RangeTo*, the *RangeTo* parameter is ignored.

Parameters

RangeFrom	Specify the starting range of the leaf you're verifying. This parameter takes a string value.
RangeTo	Specify the ending range of the leaf you're verifying. This parameter takes a string value.

Returns

An integer: 0 if the leaf exists.

Related Links

NodeExists
FindLeaf

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

LockTree

Syntax

```
LockTree()
```

Description

Use the LockTree method to check out a tree for editing. Use this method to prevent saving conflicts when you have multiple users accessing the same tree, using both the Tree API and PeopleSoft Tree Manager. To release a tree, use the UnlockTree method.

Note: In order to use this method, you must have Tree multi-user environment enabled. You can check if it is enabled by using UseUpdateReservation Tree property.

To verify if a tree is already locked, use the LockStatus property.

This method can be used only on an open tree, not on a closed tree. This means you must have opened the tree with the Open method.

Parameters

None.

Returns

An integer: 0 if locked successfully.

Related Links

TreeLocksNumber
UnlockTree
HasLockedBranches
LockStatus
UseUpdateReservation

Open

Syntax

```
Open(SetID, UserKeyValue, TreeName, EffDt, BranchName, Update)
```

Description

The Open method opens the tree object specified by the parameters. The Open method can be used only with a closed tree, it cannot be used on an open tree. You cannot read or set any properties of a tree until after you open it. When you open a tree, you can specify whether you want to open it for update, or in read-only mode, with the *Update* parameter. If you try updating or writing to a tree opened in read-only mode, you receive an error.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Note: Because EFFDT is a key field for a tree definition, an exact match is required to open a tree with the Open method. A less restrictive method, OpenAsOfDate, provides an alternative to Open by specifying an *AsOfDate* parameter instead of the *EffDt* parameter.

Parameters

SetID

Specify the table indirection key for the tree. This parameter takes a string value. If the tree structure the tree is based on has its IndirectionMethod specified as "S", you must specify a SetID.

If the tree structure doesn't have its IndirectionMethod specified as "S", you must enter a Null string (that is, two quotation marks with no blank space between them ("")) for this parameter.

UserKeyValue

Specify the User Key value for the tree. This parameter takes a string value. If the tree structure the tree is based on has its IndirectionMethod specified as "U" or "B", you must specify a User Key Value.

If the tree structure doesn't have its IndirectionMethod specified as "U" or "B", you must enter a Null string (that is, two quotation marks with no blank space between them ("")) for this parameter.

TreeName

Specify the name for the tree. This parameter takes a string value.

EffDt

Specify the effective date for the tree. This parameter takes a string value. The format must be in the correct format for the database platform the code is executing on.

BranchName

This parameter is required, but it is unused in this release. You must enter a Null string (that is, two quotation marks with no blank space between them ("")) for this parameter.

Update

Specify if you want to open the tree for update or in read-only mode. This parameter takes a Boolean value. Values for *Update* are:

- True: open tree structure in update mode (read-write).
- False: open tree structure in read-only mode.

If you try updating or writing to a tree structure opened in read-only mode, you receive an error.

Returns

An integer: 0 if opened successfully.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

The following example opens a tree object, then tests to see if the tree was actually opened:

```
&RSLT = &MYTREE.Open("","","PERSONAL_DATA", "05-05-1997", "", True);

If &RSLT = 0 Then
   /* normal processing */
Else
   /* error processing tree isn't open */
End-if;
```

Related Links

Close
OpenAsOfDate
IndirectionMethod

OpenAsOfDate

Syntax

OpenAsOfDate(*SetID*, *UserKeyValue*, *TreeName*, *AsOfDate*, *BranchName*, *Update*)

Description

The OpenAsOfDate method operates similarly to the Open method and uses the same parameters except that instead of requiring the *EffDt* parameter, OpenAsOfDate uses a less restrictive *AsOfDate* parameter. The OpenAsOfDate method opens the most recent tree based on *AsOfDate.* If *AsOfDate* is not supplied, the current date is used.

Note: Because EFFDT is a key field for a tree definition, an exact match is required to open a tree with the Open method.

The OpenAsOfDate method can be used only with a closed tree; it cannot be used on an open tree. You cannot read or set any properties of a tree until after you open it. When you open a tree, you can specify whether you want to open it for update, or in read-only mode, with the Update parameter. If you try updating or writing to a tree opened in read-only mode, you receive an error.

Parameters

SetID

Specify the table indirection key for the tree. This parameter takes a string value. If the tree structure the tree is based on has its IndirectionMethod specified as "S", you must specify a SetID.

If the tree structure doesn’t have its IndirectionMethod specified as "S", you must enter a Null string (that is, two quotation marks with no blank space between them (“”)) for this parameter.

UserKeyValue

Specify the User Key value for the tree. This parameter takes a string value. If the tree structure the tree is based on has its IndirectionMethod specified as "U" or "B", you must specify a User Key Value.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

If the tree structure doesn't have its IndirectionMethod specified as "U" or "B", you must enter a Null string (that is, two quotation marks with no blank space between them ("")) for this parameter.

TreeName

Specify the name for the tree. This parameter takes a string value.

AsOfDate

Specify the "as-of-date" for the tree as a string. The format must be in the correct format for the database platform the code is executing on.

If this parameter is not supplied, then the current date is used.

If more than one tree matches the *SetID, UserKeyValue, TreeName,* and *BranchName* parameters, the tree with most recent effective date less than or equal to the as-of-date is opened.

BranchName

This parameter is required, but it is unused in this release. You must enter a Null string (that is, two quotation marks with no blank space between them ("")) for this parameter.

Update

Specify if you want to open the tree for update or in read-only mode. This parameter takes a Boolean value. Values for *Update* are:

- True: open tree structure in update mode (read-write).
- False: open tree structure in read-only mode.

If you try updating or writing to a tree structure opened in read-only mode, you receive an error.

Returns

An integer: 0 if opened successfully.

Example

The following example opens a tree object with most recent effective date matching the other tree criteria. Then, the program tests to see if the tree was actually opened:

```
&ret = &MyTree.OpenAsOfDate("QEDM1","","PERSONAL_DATA", "", "", True);

If &ret = 0 Then
   /* normal processing */
Else
   /* error processing tree isn't open */
End-if;
```

Related Links

Open

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

OpenForExport

Syntax

OpenForExport(*SetID*, *UserKeyValue*, *TreeNameEffDt*)

Description

Use the OpenForExport method to open a tree for export processes (using TreeMover.)

Parameters

SetID

Specify the table indirection key for the tree. This parameter takes a string value. If the tree structure the tree is based on has its IndirectionMethod specified as "S", you must specify a SetID.

If the tree structure doesn't have its IndirectionMethod specified as "S", you must enter a Null string (that is, two quotation marks with no blank space between them (""")) for this parameter.

UserKeyValue

Specify the User Key value for the tree. This parameter takes a string value. If the tree structure the tree is based on has its IndirectionMethod specified as "U" or "B", you must specify a User Key Value.

If the tree structure doesn't have its IndirectionMethod specified as "U" or "B", you must enter a Null string (that is, two quotation marks with no blank space between them (""")) for this parameter.

TreeName

Specify the name for the tree. This parameter takes a string value.

EffDt

Specify the effective date for the tree. This parameter takes a string value. The format must be in the correct format for the database platform the code is executing on.

Returns

An integer: 0 if opened successfully.

Example

```
If &TREE.OpenForExport(&SETID, &USERKEYVALUE, &TREE_NAME, &TREE_EFFDT) <> 0 Then

/* processing */

End-if;
```

Related Links

"File Layout Details" (PeopleTools 8.54: Tree Manager)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

OpenWholeTree

Syntax

OpenWholeTree(*SetID*, *UserKeyValue*, *TreeName*, *EffDt*)

Description

The OpenWholeTree method enables you to open a tree as if it were an unbranched tree. With this kind of tree, branched nodes cannot be distinguished from unbranched nodes. This means you can traverse the entire tree. It also means that branches have a node icon, not a branch icon. This method can be used only with a closed tree, it cannot be used on an open tree. You cannot read any properties of a tree until after you open it. This tree is always opened as read-only.

Note: You can't open a tree using this method and update it. The tree is opened in read-only mode.

Parameters

SetID

Specify the table indirection key for the tree. This parameter takes a string value. If the tree structure the tree is based on has its IndirectionMethod specified as "S", you must specify a SetID.

If the tree structure doesn’t have its IndirectionMethod specified as "S", you must enter a Null string (that is, two quotation marks with no blank space between them (“”)) for this parameter.

UserKeyValue

Specify the User Key value for the tree. This parameter takes a string value. If the tree structure the tree is based on has its IndirectionMethod specified as "U" or "B", you must specify a User Key Value.

If the tree structure doesn’t have its IndirectionMethod specified as "U" or "B", you must enter a Null string (that is, two quotation marks with no blank space between them (“”)) for this parameter.

TreeName

Specify the name for the tree. This parameter takes a string value.

EffDt

Specify the effective date for the tree. This parameter takes a string value. The format must be in the correct format for the database platform the code is executing on.

Returns

An integer: 0 if opened successfully.

Example

```
&pSession = %Session;

&pTreeObj = &pSession.GetTree();
&status = &pTreeObj.OpenWholeTree(&Setid, &SetCntrlValue, &TreeName, String(&EffDt)⇒
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
);
```

Related Links

Close
IndirectionMethod

NodeExists

Syntax

```
NodeExists(NodeName)
```

Description

The NodeExists method enables you to verify if the node specified by *NodeName* exists in the current tree.

Note: If the node you're searching for is in an unexpanded portion of the tree, this method expands the tree down to that node.

Parameters

NodeName	Specify the name of the node that you want to find. This parameter takes a string value.

Returns

An integer: 0 if the node exists.

Related Links

FindLeaf
FindNode
LeafExists

Rename

Syntax

```
Rename(FromSetId, FromUserKeyValue, FromTreeName, FromEffDt, FromBranchName,
ToTreeName)
```

Description

The Rename method renames a tree specified with the *From* parameters to the tree specified with *ToTreeName*. The tree specified by *ToTreeName* must be a new tree. You receive an error if the tree already exists. The tree specified by the *From* parameters does not have to match the tree executing the method.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The Rename method can be used only with a closed tree, it cannot be used on an open tree. Before you use the Rename method, you must explicitly close any open tree objects (with the Close method.) You receive an error if there are any open trees.

To access the new tree, you must use the Open method.

Parameters

FromSetId

Specify the table indirection key for the tree to be copied from. This parameter takes a string value. If the tree structure the tree is based on has its IndirectionMethod specified as "S", you must specify a SetID.

If the tree structure doesn't have its IndirectionMethod specified as "S", you must enter a Null string (that is, two quotation marks with no blank space between them ("")) for this parameter.

FromUserKeyValue

Specify the User Key Value for the tree to be copied from. This parameter takes a string value. If the tree structure the tree is based on has its IndirectionMethod specified as "U" or "B", you must specify a User Key Value.

If the tree structure doesn't have its IndirectionMethod specified as "U" or "B" you must enter a Null string (that is, two quotation marks with no blank space between them ("")) for this parameter.

FromTreeName

Specify the name for the tree to be copied from. This parameter takes a string value.

FromEffDt

Specify the effective date for the tree to be copied from. This parameter takes a string value.

FromBranchName

This parameter is required, but it is unused in this release. You must enter a Null string (that is, two quotation marks with no blank space between them ("")) for this parameter.

ToTreeName

Specify the new name of the tree. This parameter takes a string value.

Returns

An integer: 0 if renamed successfully.

Example

```
&MYTREE.Rename("","","PERSONAL_DATA3", "05-05-1997","", "PERSONAL_REN2");
```

Related Links

Close
Open
Close
IndirectionMethod

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Save

Syntax

```
Save()
```

Description

The Save method writes any changes to the tree executing the method to the database. It also performs audits.

The Save method can be used only on an open tree, not on a closed tree. This means you must have opened the tree with the Open method before you can save it.

The tree object remains open after executing Save. You must execute the Close method on the object before it is closed and the memory freed.

This method returns an optional Boolean value: True if the tree was saved with no errors, False if there are one or more errors.

Note: If you're calling the Tree API from an Application Engine program, the data won't actually be committed to the database until the Application Engine program performs a COMMIT.

Related Links

"Understanding the Auditing and Repairing of Trees" (PeopleTools 8.54: Tree Manager)

Parameters

None.

Returns

An integer: 0 if save successfully.

SaveAs

Syntax

```
SaveAs(SetID, UserKeyValue, TreeName, EffDt, BranchName)
```

Description

The SaveAs method writes any changes to the tree executing the method to the new tree specified with the parameters. It also performs audits.

The tree specified with the parameters must be a new tree. You receive an error if the tree already exists. The new tree must have at least one different key field from the original tree.

The SaveAs method automatically closes the tree that is associated with the tree object executing the method, and associates that tree object with the new tree. Any changes made to the original tree since the last time the tree was saved are discarded. For example, suppose you opened a tree named DEPENDENT_BENEF and associated it with the variable &MYTREE. If you executed the SaveAs

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

method with &MYTREE, changing the name to DEPENDENT_BENEF2, &MYTREE would now be associated with DEPENDENT_BENEF2, and the original tree, DEPENDENT_BENEF, would be closed.

```
&MYTREE.Open("", "", "DEPENDENT_BENEF", "02-02-1999", "", False);
/* do some processing */
&MYTREE.SaveAs("", "", "DEPENDENT_BENEF2", "02-05-1999", "");
```

&MYTREE is now associated with DEPENDENT_BENEF2, not with the original open tree.

Note: If you're calling the Tree API from an Application Engine program, the data won't actually be committed to the database until the Application Engine program performs a COMMIT.

Parameters

SetID

Specify the table indirection key for the tree. This parameter takes a string value. If the tree structure the tree is based on has its IndirectionMethod specified as "S", you must specify a SetID.

If the tree structure doesn't have its IndirectionMethod specified as "S", you must enter a Null string (that is, two quotation marks with no blank space between them ("")) for this parameter.

UserKeyValue

Specify the User Key Value for the tree. This parameter takes a string value. If the tree structure the tree is based on has its specified as "U" or "B", you must specify a User Key Value.

If the tree structure doesn't have its IndirectionMethod specified as "U" or "B", you must enter a Null string (that is, two quotation marks with no blank space between them ("")) for this parameter.

TreeName

Specify the name for this tree. This parameter takes a string value.

EffDt

Specify the effective date for this tree. This parameter takes a string value.

BranchName

This parameter is required, but it is unused in this release. You must enter a Null string (that is, two quotation marks with no blank space between them ("")) for this parameter.

Returns

This method returns an integer: 0 if saved successfully, a number greater than 0 otherwise.

Example

```
&MYTREE.SaveAs("", "", "DEPENDENT_BENEF2", "02-05-1999", "");
```

Related Links

"Understanding the Auditing and Repairing of Trees" (PeopleTools 8.54: Tree Manager)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SaveAsDraft

Syntax

SaveAsDraft(*SetID*, *UserKeyValue*, *TreeName*, *EffDt*, *Branch`Name*)

Description

The SaveAsDraft method writes any changes to the tree executing the method to the new tree specified with the parameters. However, it does not perform audits. Trees that are saved in this way are marked as "draft" and will not be valid (that is, cannot be used with other PeopleTools) until the tree audit is passed during Save, SaveAs, or the Tree Audits Application Engine Tree Utility program..

The tree specified with the parameters must be a new tree. You receive an error if the tree already exists. The new tree must have at least one different key field from the original tree.

The SaveAsDraft method automatically closes the tree that is associated with the tree object executing the method, and associates that tree object with the new tree. Any changes made to the original tree since the last time the tree was saved are discarded.

See SaveAs for more details.

Note: If you're calling the Tree API from an Application Engine program, the data won't actually be committed to the database until the Application Engine program performs a Commit.

Parameters

SetID

Specify the table indirection key for the tree. This parameter takes a string value. If the tree structure the tree is based on has its IndirectionMethod specified as "S", you must specify a SetID.

If the tree structure doesn't have its IndirectionMethod specified as "S", you must enter a Null string (that is, two quotation marks with no blank space between them ("")) for this parameter.

UserKeyValue

Specify the User Key Value for the tree. This parameter takes a string value. If the tree structure the tree is based on has its IndirectionMethod specified as "U" or "B", you must specify a User Key Value.

If the tree structure doesn't have its IndirectionMethod specified as "U" or "B", you must enter a Null string (that is, two quotation marks with no blank space between them ("")) for this parameter.

TreeName

Specify the name for this tree. This parameter takes a string value.

EffDt

Specify the effective date for this tree. This parameter takes a string value.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

BranchName This parameter is required, but it is unused in this release. You must enter a Null string (that is, two quotation marks with no blank space between them ("")) for this parameter.

Returns

This method returns an integer: 0 if saved successfully, a number greater than 0 otherwise.

Example

```
&MYTREE.  SaveAsDraft("","","PERSONAL_EDIT2", "05-05-1997", "");
```

Related Links

"Understanding the Auditing and Repairing of Trees" (PeopleTools 8.54: Tree Manager)

SaveDraft

Syntax

SaveDraft()

Description

The SaveDraft method writes any changes to the tree executing the method to the database. However, it does not perform audits. Trees that are saved in this way are marked as "draft" and will not be valid (that is, cannot be used with other PeopleTools) until the tree audit is passed.

The SaveDraft method can be used only on an open tree, not on a closed tree. This means you must have opened the tree with the Open method before you can save it.

The tree object remains open after executing SaveDraft. You must execute the Close method on the object before it is closed and the memory freed.

Note: If you're calling the Tree API from an Application Engine program, the data won't actually be committed to the database until the Application Engine program performs a Commit.

Parameters

None.

Returns

This method returns an integer: 0 if saved successfully, a number greater than 0 otherwise.

Related Links

Close

Open

"Understanding the Auditing and Repairing of Trees" (PeopleTools 8.54: Tree Manager)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SetImportMode

Syntax

SetImportMode(*Nodes_NumberLeaves_Number*)

Description

Use the SetImportMode method to set up special memory allocation and simplified processing rules when running Tree Import.

This special mode also cuts back on the number of SQL calls by not getting node descriptions. This mode also blocks internal validation while inserting new node or leaf from an input file. All validation occurs during saving.

Parameters

Nodes_Number Specify the number of nodes.

Leaves_Number Specify the number of leaves.

Returns

An integer: 0 if set successfully.

Related Links

"File Layout Details" (PeopleTools 8.54: Tree Manager)

TreeLocksNumber

Syntax

TreeLocksNumber(*setID*, *UserKeyValue*, *TreeName*, *EffDt*)

Description

Use the TreeLocksNumber method to determine how many users have checked out any branches of a current tree. This method should be used to check if a tree definition could be changed without affecting other users working in different branches of a tree.

Note: In order to use this method, you must have Tree multi-user environment enabled. You can check if it is enabled by using UseUpdateReservation Tree property.

You can use the TreeLocksNumber method with a both an open as well as a closed tree.

Parameters

SetID Specify the table indirection key for the tree. This parameter takes a string value. If the tree structure the tree is based on has its IndirectionMethod specified as "S", you must specify a SetID.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

If the tree structure doesn't have its IndirectionMethod specified as "S", you must enter a Null string (that is, two quotation marks with no blank space between them ("")) for this parameter.

UserKeyValue Specify the User Key Value for the tree. This parameter takes a string value. If the tree structure the tree is based on has its IndirectionMethod specified as "U" or "B", you must specify a User Key Value.

If the tree structure doesn't have its IndirectionMethod specified as "U" or "B", you must enter a Null string (that is, two quotation marks with no blank space between them ("")) for this parameter.

TreeName Specify the name for this tree. This parameter takes a string value.

EffDt Specify the effective date for this tree. This parameter takes a string value.

Returns

The number of locked branches. If the tree is not branched, but is checked out, the return value is 1.

Related Links

LockTree
UnlockTree
UnlockTree
UseUpdateReservation

UnlockTree

Syntax

`UnlockTree``()`

Description

Use the UnlockTree method to release a tree after editing. Use this method to prevent saving conflicts when you have multiple users accessing the same tree, using both the Tree API and PeopleSoft Tree Manager. To checkout a tree, use the LockTree method.

Note: In order to use this method, you must have Tree multi-user environment enabled. You can check if it is enabled by using UseUpdateReservation Tree property.

To verify if a tree is checked out, use the LockStatus property.

This method can be used only on an open tree, not on a closed tree. This means you must have opened the tree with the Open method.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

None.

Returns

An integer: 0 if the tree is released successfully.

Related Links

LockTree
LockStatus
UseUpdateReservation

UpdateLock

Syntax

`UpdateLock``()`

Description

Use the UpdateLock method to update the timestamp representing time when the user who has the tree checked out performed the last action on a tree.

Note: In order to use this method, you must have Tree multi-user environment enabled. You can check if it is enabled by using UseUpdateReservation Tree property.

Use this method to indicate that user who has the tree checked out is still working with it. The tree won't be released unless the Tree Inactivity Period specified on the People Tools Options page is expired.

This method should be called from PeopleCode in a response to any user action happened on a Tree Manager page.

This method can be used only on an open tree, not on a closed tree. This means you must have opened the tree with the Open method.

Parameters

None.

Returns

An integer: 0 if activity time was updated successfully.

Related Links

LockTree
UnlockTree
UseUpdateReservation

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Tree Class Properties

In this section, we discuss the Tree class properties. The properties are discussed in alphabetical order.

AllValues

Description

When the tree is audited, the AllValues property specifies whether the audit should verify that the tree includes all user data detail values. This property returns a Boolean value: True, check all values, False, do not check all values.

If this is a new tree, and you do not set this property, a default value of False is automatically set.

This property can be used only with an open tree, that is, you must use the Open method on the tree before you can use this property.

This property is read-write.

Example

```
&MyTree.AllValues = False;
```

AuditDetails

Description

Set this property to False in cases when you do not want to perform Detail Audit. It could happend if you are reusing existing structure that contains Detail information for tree that does not use details('Winter' tree).

The default value for this property is True.

This property is read-write.

Branches

Description

This property returns a reference to a branch collection object. This property is used only with branched trees: it returns Null for trees that aren’t branched.

This property can be used only with an open tree, that is, you must use the open the tree using the Open method before you can use this property.

This property is read-only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

BranchImageName

Description

Use this property to specify the image used to display branches on a page. This property takes a string value.

This property is read-write.

BranchLevel

Description

This property returns the level number (as a number) where this branch occurs in the tree. This property is used only with trees with levels: it returns zero for trees that don't have levels.

This property can be used only with an open tree, that is, you must open the tree using the Open method before you can use this property.

This property is read-only.

Example

```
&LevelNumber = &MyTree.BranchLevel;
```

BranchName

Description

This property returns the name of the specific branch for the tree, as a string. This property is used only with branched trees: it returns an empty string for trees that aren't branched.

This property can be used only with an open tree, that is, you must open the tree using the Open method before you can use this property.

This property is read-only.

Example

```
&BranchName = &MyTree.BranchName;
```

Category

Description

This property returns the category name for the tree, as a string. The category is a high-level grouping under which you can organize your tree structures and tree definitions. If you are creating a new tree, this property is required.

This property can be used only with an open tree, that is, you must open the tree using the Open method before you can use this property.

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

```
&MyTree.Category = "PurchaseOrders";
```

Description

Description

This property returns the description of the tree, as a string. If you are creating a new tree, this property is required.

This property can be used only with an open tree, that is, you must open the tree using the Open method before you can use this property.

This property is read-write.

Example

```
&MyTree.Description = "Departmental Security";
```

DuplicateLeaves

Description

In most trees, you want each detail value to appear only once in the tree. To permit duplicate values, set this property to True.

If this is a new tree, and you do not set this property, a default value of False is automatically set.

This property can be used only with an open tree, that is, you must open the tree using the Open method before you can use this property.

This property is read-write.

EffDt

Description

This property returns the effective date of the tree, as a date.

Note: PeopleSoft does not recommnd using this property to change data, as changes are not stored in the database.

If this is a new tree, and you do not set this property, a default value of the current date is automatically set.

This property can be used only with an open tree, that is, you must open the tree using the Open method before you can use this property.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

```
&TreeEffDt = &MYTREE.EffDt;
```

HasDetailRanges

Description

This property returns True if the tree has any detail ranges.

This property can be used only with an open tree, that is, you must open the tree using the Open method before you can use this property.

This property is read-only.

HasLockedBranches

Description

This property indicates whether any user other then current one has checked out any branch in a tree. This property returns a Boolean value: true if the tree has checked out branches, false otherwise.

Note: In order to use this method, you must have Tree multi-user environment enabled. You can check if it is enabled by using UseUpdateReservation Tree property.

This property can be used only with an open tree, that is, you must open the tree using the Open method before you can use this property.

This property is read-only.

IsBranched

Description

This property indicates whether the tree is branched. Possible values for this property are True and False: True if the tree is branched, False if it isn't.

This property can be used only with an open tree, that is, you must open the tree using the Open method before you can use this property.

This property is read-only.

Example

```
If &MyTree.IsBranched Then
   /* Do branched processing */
Else
   /*Do unbranched processing */
End-If;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

IsChanged

Description

This property returns True if the tree has been changed but not saved, False if the tree is unchanged.

This property can be used only with an open tree, that is, you must open the tree using the Open method before you can use this property.

This property is read-only.

Example

```
If &MyTree.IsChanged Then
   &MyTree.Save();
End-if;
&MyTree.Close();
```

IsOpen

Description

This property returns True if the tree is open, False if the tree is closed.

This property is read-only.

Example

```
If Not &MyTree.IsOpen Then
   &MyTree.Open("","","PERSONAL_DATA", &Date, "", True);
End-If;
```

IsQueryTree

Description

This property returns True if the tree is a Query access tree. It returns False if the tree is not a Query Access Tree.

This property can be used only with an open tree, that is, you must open the tree using the Open method before you can use this property.

This property is read-only.

IsValid

Description

This property returns True if the tree is a valid tree that has passed all audits. It returns False otherwise.

This property can be used only with an open tree, that is, you must open the tree using the Open method before you can use this property.

This property is read-only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

"Understanding the Auditing and Repairing of Trees" (PeopleTools 8.54: Tree Manager)

IsVersionChanged

Description

This property indicates if a tree version has been changed in the database. This property returns a Boolean value, true if the version was changed, false otherwise.

Use this function in a multi-user environment to check if a tree loaded in a read-only mode by User1 should be reloaded. A possible reason why it needs to be reloaded could be triggered by tree version change after User2, who had this tree checked out, released it.

This property can be used only with an open tree, that is, you must open the tree using the Open method before you can use this property.

This property is read-only.

IsWholeTree

Description

This property indicates whether the entire tree is accessible. This property is set to True if a tree was opened using OpenWholeTree method. The OpenWholeTree method opens a tree in read-only mode without paying attention to the existing tree branches.

This property can be used only with an open tree, that is, you must open the tree using the Open method before you can use this property.

This property is read-only.

Example

```
If &MyTree.IsWholeTree Then
   /* Do processing */
Else
   /* close tree and reopen using OpenWholeTree method */
End-If;
```

KeyBranchName

Description

This property returns the branch name of the tree as a string if the tree is branched. If not branched, this property returns a blank string.

This property can be used with a closed tree, that is, before you use the Open method.

If the tree has already been opened, you can use the KeyBranchName property to get the tree branch name

This property is read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

KeyEffDt

Description

This property returns the effective date of the tree as a string if the tree is effective-dated. If not effective-dated, this property returns a blank string.

This property can be used with a closed tree, that is, before you use the Open method.

If the tree has already been opened, you can use the KeyEffDt property to get the tree effective date

This property is read-only.

KeyName

Description

This property returns the name of the tree as a string.

This property can be used with a closed tree, that is, before you use the Open method.

If the tree has already been opened, you can use the Name property to get the tree name.

This property is read-only.

KeySetId

Description

This property returns the SetID of the tree as a string if the tree has a SetID. If the tree doesn't have a SetID, this property returns a blank string.

This property can be used with a closed tree, that is, before you use the Open method.

If the tree has already been opened, you can use the KeySetId to get the tree Set Id.

This property is read-only.

KeyUserKeyValue

Description

This property returns the UserKeyValue of the tree as a string if the tree has a UserKeyValue. If the tree doesn't have a UserKeyValue, this property returns a blank string.

This property can be used with a closed tree, that is, before you use the Open method.

If the tree has already been opened, you can use the KeyUserKeyValue to get the tree UserKeyValue.

This property is read-only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

LeafCount

Description

This property returns the number of leaves in the tree.

This property can be used only with an open tree, that is, you must use the Open method on the tree before you can use this property.

This property is read-only.

LeafImageName

Description

Use this property to specify the image used to display leaves on a page. This property takes a string name.

This property is read-write.

LeafOnClipboard

Description

Use this property to determine if a leaf has been cut and is available to be 'pasted' into tree. This property returns a Boolean value: True if a leaf object exists on the clipboard, False otherwise.

This property is read-only.

LevelCount

Description

This property returns the number of levels defined for the tree. If the tree doesn't have any levels, this property returns zero (0).

See the LevelUse property.

Valid value range is a number between 0 and 99.

This property can only be used with an open tree, that is, you must use the Open method on the tree before you can use this property.

This property is read-only.

Related Links

LevelUse

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Levels

Description

This property returns a reference to a level collection object. This property is used only with trees that have levels: it returns Null for trees that don't have levels.

This property can be used only with an open tree, that is, you must open the tree using the Open method before you can use this property.

This property is read-only.

Related Links

Level Collection Methods

LevelUse

Description

This property returns the level use of the tree. The values are:

Value	*Description*
"S"	Strict levels
"L"	Loose levels
"N"	No levels

If this is a new tree, and you do not set this property, the default value is Strict Levels.

This property can be used only with an open tree, that is, you must open the tree using the Open method before you can use this property.

This property is read-write.

Example

```
If &MyTree.LevelUse = "S" Then
/* add levels */
End-If;
```

LockOwner

Description

This property returns the user ID of the user who has checked out a specific tree or a tree branch, as a string.

Note: In order to use this method, you must have Tree multi-user environment enabled. You can check if it is enabled by using UseUpdateReservation Tree property.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property can be used only with an open tree, that is, you must open the tree using the Open method before you can use this property.

This property is read-only.

LockStatus

Description

This property indicates if an opened tree is checked out.

Note: In order to use this method, you must have Tree multi-user environment enabled. You can check if it is enabled by using UseUpdateReservation Tree property.

Possible values are:

Value	*Description*
0	Tree is not checked out by any user.
1	Tree is checked out by another user.
2	Tree is checked out by the current user and is editable.

This property is read-only.

Related Links

LockTree
TreeLocksNumber
UnlockTree
LockOwner

Name

Description

This property returns the name of the tree, as a string.

Note: Do not use this property to change the name of an existing tree. The change will not be reflected in the database. You must use the Rename method to change the name of an existing tree.

This property can be used only with an open tree, that is, you must open the tree using the Open method before you can use this property.

This property is read-write.

Example

```
&TreeName = &MyTree.Name;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

Rename

NodeColImageName

Description

Use this property to specify the image displayed for a collapsed node. This property takes a string value.

This property is read-write.

NodeCount

Description

This property returns the number of nodes for the tree. A valid tree must have at least one node.

This property can be used only with an open tree, that is, you must open the tree using the Open method before you can use this property.

This property is read-only.

NodeExpImageName

Description

Use this property to specify the displayed image of an expanded node. This property takes a string value.

This property is read-write.

NodeOnClipboard

Description

Use this property to determine if a node has been cut and is available to be 'pasted' into a tree. This property returns a Boolean value: True if a node object exists on the clipboard, False otherwise.

This property is read-only.

ParentLevel

Description

This property returns the number of the parent branch level in a branched tree. If the tree does not have levels or is an unbranched tree, zero (0) is returned. Valid value range is a number between 0 and 100.

This property can be used only with an open tree, that is, you must open the tree using the Open method before you can use this property.

This property is read-only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ParentName

Description

This property returns the name of the parent branch in a branched tree, as a string. If the tree does not have levels, is an unbranched tree, or if the tree is the root level, Null is returned.

This property can be used only with an open tree, that is, you must open the tree using the Open method before you can use this property.

This property is read-only.

PerformanceMethod

Description

This property sets the method to use for select and join statements used to generate SQL with the tree. This property is used with nVision layouts and Query.

The values for this property are:

Value	*Description*
"L"	Suppress Join: Use Literal Values.
"S"	Sub-SELECT Tree Selector.
"J"	Join to Tree Selector.
"D"	User Application Defaults.

If this is a new tree, and you do not set this property, the default value "D" is automatically set.

This property can be used only with an open tree, that is, you must open the tree using the Open method before you can use this property.

This property is read-write.

Related Links

"Understanding Types of Trees" (PeopleTools 8.54: Tree Manager), "PS/nVision Overview" (PeopleTools 8.54: PS/nVision)

PerformanceSelector

Description

This property selects the tree selectors for nVision for the tree. This property is used with nVision layouts and Query.

The values for this property are:

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Value	*Description*
"D"	Dynamic Selectors
"S"	Static Selectors

If this is a new tree, and you do not set this property, the default value "S" is automatically set.

This property can be used only with an open tree, that is, you must open the tree using the Open method before you can use this property.

This property is read-write.

Related Links

"PS/nVision Overview" (PeopleTools 8.54: PS/nVision)

PerformanceSelectorOption

Description

This property selects the tree selector options for nVision for the tree. This property is used with nVision layouts and Query.

The values for this property are:

Value	*Description*
"S"	Single values
"R"	Ranges of values (>=…<=).
"B"	Range of values (BETWEEN).

If this is a new tree, and you do not set this property, the default value "R" is automatically set.

This property can be used only with an open tree, that is, you must open the tree using the Open method before you can use this property.

This property is read-write.

Related Links

"PS/nVision Overview" (PeopleTools 8.54: PS/nVision)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SetID

Description

This property returns the SetID for the tree, as a string. This property is used only when the IndirectionMethod property for the tree structure the tree is based on has been set to "S". Otherwise, this property returns Null.

This property can be used only with an open tree, that is, you must open the tree using the Open method before you can use this property.

This property is read-write.

Note: PeopleSoft does not recommend setting the SetID for a tree, as there is no way to save this value to the database.

Related Links

IndirectionMethod

Status

Description

This property returns the effective status of the tree. The values are:

Value	*Description*
"A"	Active
"I"	Inactive

This property can be used only with an open tree, that is, you must open the tree using the Open method before you can use this property.

This property is read-write.

Structure

Description

This property returns a reference to the tree structure of the tree. Before you can use some of the methods or any of the properties of a tree structure, you must use the Open method to open the tree structure.

This property can be used only with an open tree, that is, you must open the tree using the Open method before you can use this property.

This property is read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

StructureName

Description

This property returns the name (*structure ID*) of the tree structure the tree is based on, as a string. This property can be set only with a new tree.

Note: Even though this is a writable property, you will receive an error if you try to change the tree structure for an existing tree.

This property can be used only with an open tree, that is, you must open the tree using the Open method before you can use this property.

This property is read-write.

Related Links

SetID

TreeImageName

Description

Use this property to specify the displayed image for a tree. This property takes a string value.

This property is read-write.

UserKeyValue

Description

Use this property to read the key field value for the Node User Key Field specified from the NodeRecord on the associated tree structure.

This property is used only when the IndirectionMethod property for the tree structure has been set to "U" or "B". Otherwise, this property returns Null.

This property is read-write.

Note: PeopleSoft does not recommend setting the UserKeyValue for a tree, as there is no way to save this value to the database.

Related Links

NodeRecord, IndirectionMethod

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

UseUpdateReservation

Description

This property indicates if multi-user environment features are used. This property returns a Boolean value, true if multi-user environments features are used, false otherwise.

This property can be used with either an open or a closed tree.

This property is read-only.

Tree Structure Class

Tree structure objects are instantiated from the following:

- From a session object with the GetTreeStructure method.
- From a tree object with the Structure property.

See GetTreeStructure, Structure.

Tree Structure Class Methods

In this section, we discuss the Tree Structure class methods. The methods are discussed in alphabetical order.

Close

Syntax

Close()

Description

The Close method closes the tree structure object executing the method, freeing the memory associated with that object, and discarding any changes made to the tree structure. The Close method can be used only on an open tree structure, not on a closed tree structure. This means you must have opened the tree structure with the Open method before you can save it. To save any changes, you must use the Save method before using Close.

Returns

A number; 0 if the method completed successfully.

Copy

Syntax

Copy(*FromStructId, ToStructId*)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

The Copy method copies the tree structure specified with *FromStructId* to the tree structure specified with *ToStructId*. Both parameters take string values. The tree structure specified by *ToStructId* must be a *new* tree structure. You receive an error if the tree structure already exists.

The Copy method can only be used with a closed tree structure, it cannot be used on an open tree structure. Before you use the Copy method, you must explicitly close any open tree structure objects (with the Close method.) You receive an error if there are any open tree structures.

To access the new tree structure, you must use the Open method.

Returns

A number; 0 if the method completed successfully.

Example

```
&MyTreeStruct = &MySession.GetTreeStructure();
&RetValue = &MyTreeStruct.Copy(PERSONAL_DATA, PERSONAL_DATA2);
```

Create

Syntax

Create(*StructId*, *Type*)

Description

The Create method creates a tree structure with the name *StructId*, and of the type *Type*. Both parameters take a string value.

Note: If the tree structure already exists, it is overwritten with the newly created tree structure.

The Create method can be used only with a closed tree structure, it cannot be used on an open tree structure. Before you use the Create method, you must explicitly close any open tree structure objects (with the Close method.) You receive an error if there are any open tree structures.

The new tree structure must be saved (using the Save method) for this structure to be saved to the database.

After you create a new tree structure, you can open it with the Open method.

The values for *Type* are:

- "D": create a detail tree structure.
- "S": create a summary tree structure.

Currently, only the value of "D" is supported for the *Type* parameter. You can specify an empty string for *Type*. If you need to create a summary structure follow the example below:

```
&MYSTRUCT=&SESSION.GETSTRUCTURE();
IF ALL( &MYSTRUCT) THEN
   &RETVALUE=&MYSTRUCT.CREATE('DEPARTMENT_SUM',' ');
     IF NONE(&RETVALUE) THEN
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
        &MYSTRUCT.TYPE = 'S';
      END-IF;
   &RETVALUE=&MYSTRUCT.SAVE();
   &RETVALUE=&MYSTRUCT.CLOSE();
END-IF;
```

Delete

Syntax

Delete(*StructId*)

Description

The Delete method deletes the tree structure specified by *StructId* from the database. The Delete method can be used only with a tree structure identifier, it cannot be used on a fully instantiated, open tree structure. Before you use the Delete method, you must explicitly close any open tree structure objects (with the Close method.) You receive an error if there are any open tree structures.

The tree structure specified by *StructId* does not have to match the tree structure identifier executing the method.

Returns

A number: 0 if the method completed successfully.

Open

Syntax

Open(*StructId*, *Update*)

Description

The Open method opens the tree structure specified by *StructId*. *StructId* takes a string value. You cannot read or set any properties of a tree structure until after you open it.

When you open a tree structure, you can specify whether you want to open it for update, or in read-only mode, with the *Update* parameter. *Update* takes a Boolean value. Values for *Update* are:

- "True": open tree structure in update mode (read-write).
- "False": open tree structure in read-only mode.

If you try updating or writing to a tree structure opened in read-only mode, your changes are ignored.

Returns

A number: 0 if the method completes successfully.

Example

```
&MyTreeStruct = &MySession.GetTreeStructure();
&REtValue = &MyTreeStruct.Open("ACCESS_GROUP", True);
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Rename

Syntax

```
Rename(FromStructId, ToStructId)
```

Description

The Rename method renames the tree structure specified with *FromStructId* to the new name specified by *ToStructId*. Both parameters take a string value. The tree structure specified by *ToStructId* must be a *new* tree structure. You receive an error if the tree structure already exists. The change is automatically reflected in the database.

The Rename method can only be used with a closed tree structure, it cannot be used on an open tree structure. Before you use the Rename method, you must explicitly close any open tree structure objects (with the Close method.) You receive an error if there are any open tree structures.

Returns

A number: 0 if the method completes successfully.

Save

Syntax

```
Save()
```

Description

The Save method writes any changes to the tree structure executing the method to the database.

The Save method can be used only on an open tree structure, not on a closed tree structure. This means you must have opened the tree structure with the Open method before you can save it.

The tree structure object remains open after executing Save. You must execute the Close method on the object before it is closed and the memory freed.

Note: If you're calling the Tree API from an Application Engine program, the data won't actually be committed to the database until the Application Engine program performs a Commit.

Returns

A number: 0 if the method completes successfully.

Tree Structure Class Properties

In this section, we discuss the Tree Structure class properties. The properties are discussed in alphabetical order.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Description

This property returns the description for the tree structure, as a string. The description is the text that displays in list boxes or reports.

This property can be used only with an open tree structure, that is, you must use the Open method on the tree structure before you can use this property.

This property is read-write.

Example

```
&MYTREESTRUCT.Description = "Department Security Chart";
```

DetailComponent

Description

This property returns the name of the detail component for the tree structure as a string.

This property can be used only with an open tree structure, that is, you must use the Open method on the tree structure before you can use this property.

This property is read-write.

DetailField

Description

This property returns the name of the detail field for the tree structure, as a string. This property is valid only if you define a detail tree structure. If you create a node-oriented tree structure, this property is not required. This field must exist on the specified DetailRecord.

This property can be used only with an open tree structure, that is, you must use the Open method on the tree structure before you can use this property.

This property is read-write.

Example

The following example sets the DetailPage, DetailRecord, and DetailField properties for a tree structure. Note that the names of the page, record, and field are all capitalized: this is required for all PeopleSoft page, record, and field names.

```
&MYTREESTRUCT.DetailPage = "BUS_UNIT_TREE_INV";
&MYTREESTRUCT.DetailRecord = "BUS_UNIT_TBL_IN";
&MYTREESTRUCT.DetailField = "BUSINESS_UNIT";
```

Related Links

DetailRecord

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

DetailMenu

Description

This property returns the name of the detail menu for the tree structure, as a string. If the page you use for detail values (DetailPage property) is part of a component, and you want to have access to the other pages in that group when you edit a node value, enter the name of the menu and menu bar for the component in the DetailMenu and DetailMenuBar properties.

This property is valid only if you define a detail tree structure. If you create a node-oriented tree structure, this property isn't required.

This property can be used only with an open tree structure, that is, you must use the Open method on the tree structure before you can use this property.

This property is read-write.

DetailMenuBar

Description

This property returns the name of the detail menu bar for the tree structure, as a string. If the page you use for detail values (DetailPage property) is part of a component, and you want to have access to the other pages in that group when you edit a node value, enter the name of the menu and menu bar for the component in the DetailMenu and DetailMenuBar properties.

This property is valid only if you're define a detail tree structure. If you create a node-oriented tree structure, this property isn't required.

This property can be used only with an open tree structure, that is, you must use the Open method on the tree structure before you can use this property.

This property is read-write.

DetailMenuItem

Description

This property returns the name of the detail menu item for the tree structure as a string.

This property can be used only with an open tree, that is, you must open the tree using the Open method before you can use this property.

This property is read-write.

DetailMultiNavigate

Description

This property sets or returns a Boolean value indicating whether the detail multi-navigation tree structure navigation option has been selected or not: True, the Detail Multi-Navigation check box has been selected, False otherwise.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-write.

Related Links

NodeMultiNavigate, "Using Multinavigation Paths" (PeopleTools 8.54: Tree Manager)

DetailPage

Description

This property returns the name of the detail page for the tree structure as a string. If the page you use for detail values (DetailPage property) is part of a component, and you want to have access to the other pages in that group when you edit a node value, enter the name of the menu and menu bar for the component in the DetailMenu and DetailMenuBar properties.

This property is valid only if you’re defining a detail tree structure. If you’re creating a node-oriented tree structure, this property isn’t required.

This property can be used only with an open tree structure, that is, you must open the tree structure with the Open method before you can use this property.

This property is read-write.

Example

The following example sets the DetailPage, DetailRecord, and DetailField properties for a tree structure. Note that the names of the page, record, and field are all capitalized: this is required for all PeopleSoft page, record, and field names.

```
&MYTREESTRUCT.DetailPage = "BUS_UNIT_TREE_INV";
&MYTREESTRUCT.DetailRecord = "BUS_UNIT_TBL_IN";
&MYTREESTRUCT.DetailField = "BUSINESS_UNIT";
```

DetailRecord

Description

This property returns the name of the detail record for the tree structure as a string. This property is valid only if you define a detail tree structure. If you create a node-oriented tree structure, this property isn’t required.

This property can be used only with an open tree structure, that is, you must open the tree structure with the Open method before you can use this property.

This property is read-write.

Example

The following example sets the DetailPage, DetailRecord, and DetailField properties for a tree structure. Note that the names of the page, record, and field are all capitalized: this is required for all PeopleSoft page, record, and field names.

```
&MYTREESTRUCT.DetailPage = "BUS_UNIT_TREE_INV";
&MYTREESTRUCT.DetailRecord = "BUS_UNIT_TBL_IN";
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
&MYTREESTRUCT.DetailField = "BUSINESS_UNIT";
```

IndirectionMethod

Description

Image: Structure tab for Tree Structure setup

The following screen image is an example of Structure tab for Tree Structure setup. When you set up a tree structure, you can set the indirection at the bottom of the Structure tab, with the radio buttons in the Additional Key Field.

In the Tree Classes API, you set these same values with the IndirectionMethod property. The values are:

- "S": SetID Indirection.
- "B": Business Unit.
- "U": User Defined Node Key.
- "N": None.

Both the *User Defined Node Key* and the *Business Unit* are the key field set with the NodeRecord property for this tree structure. If *Business Unit* is set, the key field set with the NodeRecord property is a business unit.

If you are creating a new tree structure, and you do not explicitly set this property, None ("N") is the default value, and is automatically set.

This property can be used only with an open tree structure, that is, you must open the tree structure with the Open method before you can use this property.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-write.

Related Links

IndirectionMethod, NodeRecord

KeyName

Description

This property returns the name of the tree structure as a string.

This property can be used with a closed tree structure.

This property is read-only.

LevelComponent

Description

This property returns the name of the level component for the tree structure as a string.

This property can be used only with an open tree structure, that is, you must open the tree structure with the Open method before you can use this property.

This property is read-write.

LevelMenu

Description

This property returns the name of the level menu for the tree structure as a string. If the page you use for level values (LevelPage property) is part of a component, and you want to have access to the other pages in that group when you edit a node value, enter the name of the menu and menu bar for the component in the LevelMenu and LevelMenuBar properties.

This property can be used only with an open tree structure, that is, you must open the tree structure with the Open method before you can use this property.

This property is read-write.

LevelMenuBar

Description

This property returns the name of the level menu bar for the tree structure as a string. If the page you use for level values (LevelPage property) is part of a component, and you want to have access to the other pages in that group when you edit a node value, enter the name of the menu and menu bar for the component in the LevelMenu and LevelMenuBar properties.

This property can be used only with an open tree structure, that is, you must open the tree structure with the Open method before you can use this property.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-write.

LevelMenuItem

Description

This property returns the name of the level menu item for the tree structure as a string.

This property can be used only with an open tree structure, that is, you must open the tree structure with the Open method before you can use this property.

This property is read-write.

LevelPage

Description

This property returns the name of the level page for the tree structure object as a string. If you create a new tree structure, and you do not explicitly set this property, TREE_LEVEL is the default value, and is automatically set.

This property can be used only with an open tree structure, that is, you must open the tree structure with the Open method before you can use this property.

This property is read-write.

LevelRecord

Description

This property returns the name of the level record for the tree structure object as a string. If you create a new tree structure, and you do not explicitly set this property, TREE_LEVEL_TBL is the default value, and is automatically set.

This property can be used only with an open tree structure, that is, you must open the tree structure with the Open method before you can use this property.

This property is read-write.

Name

Description

This property returns the name of the tree structure as a string. This is also called the *structure ID*. Use this property to set the name (structure ID) of a tree structure. This property is required if you are creating a new tree structure.

Note: Do not use this property to change the name of an existing tree structure. The change will not be reflected in the database. You must use the Rename method to change the name of an existing tree structure.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property can be used only with an open tree structure, that is, you must open the tree structure with the Open method before you can use this property.

This property is read-write.

Example

```
&Name = &MYTREESTRUCT.Name;
```

Related Links

Rename

NodeComponent

Description

This property returns the name of the node component for the tree structure as a string.

This property can be used only with an open tree structure, that is, you must open the tree structure with the Open method before you can use this property.

This property is read-write.

NodeField

Description

This returns the name of the field used for storing information about nodes for the tree structure as a string. If you create a new tree structure, and you do not explicitly set this property, TREE_NODE is the default value, and is automatically set. This field must exist on the specified NodeRecord.

This property can be used only with an open tree structure, that is, you must open the tree structure with the Open method before you can use this property.

This property is read-write.

Example

```
&MYTREESTRUCT.NodeField = "DEPT_ID";
```

NodeMenu

Description

This property returns the name of the node menu for the tree structure as a string. If the page you use for node values (NodePage property) is part of a component, and you want to have access to the other pages in that group when you edit a node value, enter the name of the menu and menu bar for the component in the NodeMenu and NodeMenuBar properties.

If you create a new tree structure, and you do not explicitly set this property, TREE_MANAGER is the default value, and is automatically set.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property can be used only with an open tree structure, that is, you must open the tree structure with the Open method before you can use this property.

This property is read-write.

NodeMenuBar

Description

This property returns the name of the node menu bar for the tree structure as a string. If the page you use for node values (NodePage property) is part of a component, and you want to have access to the other pages in that group when you edit a node value, enter the name of the menu and menu bar for the component in the NodeMenu and NodeMenuBar properties.

This property can be used only with an open tree structure, that is, you must open the tree structure with the Open method before you can use this property.

This property is read-write.

NodeMenuItem

Description

This property returns the name of the node menu item for the tree structure as a string.

This property can be used only with an open tree structure, that is, you must open the tree structure with the Open method before you can use this property.

This property is read-write.

NodeMultiNavigate

Description

This property sets or returns a Boolean value indicating whether the node multi-navigation tree structure navigation option has been selected: True, the Node Multi-Navigation check box has been selected, False otherwise.

This property is read-write.

Related Links

DetailMultiNavigate, "Using Multinavigation Paths" (PeopleTools 8.54: Tree Manager)

NodePage

Description

This returns the name of the page used for storing information about nodes for the tree structure as a string. If you create a new tree structure, and you do not explicitly set this property, TREE_NODE is the default value, and is automatically set.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property can be used only with an open tree structure, that is, you must open the tree structure with the Open method before you can use this property.

This property is read-write.

NodeRecord

Description

This returns the name of the record used for storing information about nodes for the tree structure as a string. If you create a new tree structure, and you do not explicitly set this property, TREE_NODE_TBL is the default value, and is automatically set.

If the IndirectionMethod property of this tree structure has been set to "U" or "B", use this property to specify the record that the NodeUserKeyField property will use.

This property can be used only with an open tree structure, that is, you must open the tree structure with the Open method before you can use this property.

This property is read-write.

Related Links

IndirectionMethod

NodeUserKeyField

Description

Use this property to set the key field from the record specified with NodeRecord for use with the IndirectionMethod. This property is identical to the UserKeyValue property for a tree.

This property is used only when the IndirectionMethod property for the tree structure has been set to "U" or "B". Otherwise, this property returns Null.

This property can be used only with an open tree structure, that is, you must open the tree structure with the Open method before you can use this property.

This property is read-write.

Related Links

IndirectionMethod, UserKeyValue

SummarySetId

Description

This property returns the SetID for the detail tree whose detail values the summary tree structure as a string summarizes. This property is valid only for Summary tree structures. Otherwise, this property returns Null.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property can be used only with an open tree structure, that is, you must open the tree structure with the Open method before you can use this property.

This property is read-write.

SummaryLevelNumber

Description

This property returns the level number for the detail tree whose detail values the summary tree structure summarizes. The level number indicates the level in the detail tree whose nodes the summary tree will use as detail values. The top level in the detail tree is 1, the next is level two, and so on. Valid values are numbers between 1 and 99.

This property is only valid for Summary tree structures. Otherwise, this property returns Null.

This property can be used only with an open tree structure, that is, you must open the tree structure with the Open method before you can use this property.

This property is read-write.

SummaryTreeName

Description

This property returns the name of the detail tree whose detail values the summary tree structure summarizes, as a string. This property is valid only for Summary tree structures. Otherwise, this property returns Null.

This property can be used only with an open tree structure, that is, you must open the tree structure with the Open method before you can use this property.

This property is read-write.

SummaryUserKeyValue

Description

This property returns the name of the tree that the node records the tree structure is summarized to, as a string. This property is valid only for Summary tree structures. This property is used only when the IndirectionMethod property for the tree structure has been set to "U" for *User Defined Keys* or "B" for *Business Unit.* Otherwise, this property returns Null.

This property can be used only with an open tree structure, that is, you must open the tree structure with the Open method before you can use this property.

This property is read-write.

Related Links

IndirectionMethod

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Type

Description

This property returns the type of the tree structure as a string, whether it is a detail or summary tree structure. The values are:

- "D": detail tree structure.
- "S": summary tree structure.

This property can be used only with an open tree structure, that is, you must open the tree structure with the Open method before you can use this property.

This property is read-write.

Traverse Tree Hierarchy Example

The following is an example to transverse a tree hierarchy and write the information to a file.

```
Local ApiObject &TreeObj, &RootNodeObj;
Local number &Res;
Local string &sSetId, &sSetCntrlValue, &sTreeName, &sBranchName;
Local File &MyFile;

Function ProcessNodeChildren(&ParentNodeObj As ApiObject)

   Local ApiObject &ChildNodeObj, &ChildLeafObj;
   Local boolean &First;

   If &ParentNodeObj.HasChildren Then

      &ChildLeafObj = &ParentNodeObj.FirstChildLeaf;
      While All(&ChildLeafObj)
         &MyFile.WriteLine("Process Leaf Range From : " | &ChildLeafObj.RangeFrom);⇒

         &ChildLeafObj = &ChildLeafObj.NextSib;
      End-While;

      If &ParentNodeObj.HasChildNodes Then
         &First = True;
         &ChildNodeObj = &ParentNodeObj.FirstChildNode;
         While &First Or
               &ChildNodeObj.HasNextSib

            If &First Then
               &First = False;
            Else
               &ChildNodeObj = &ChildNodeObj.NextSib;
            End-If;
            &MyFile.WriteLine("Process Node : " | &ChildNodeObj.Name);
            ProcessNodeChildren(&ChildNodeObj);

         End-While;
      End-If;
   End-If;
End-Function;

&TreeObj = %Session.GetTree();

If None(&TreeObj) then
   Error("Cannot get a tree");
End-if;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
&sSetId = "";
&sSetCntrlValue = "";
&sTreeName = "QE_JOBCODES";
&TreeEffDt = Date("1999-01-01");
&sBranchName = "";

&Res = &TreeObj.OPEN(&sSetId, &sSetCntrlValue, &sTreeName, &TreeEffDt, &sBranchName⇒
, False);
If All(&Res) Then
   Error("Cannot open a tree");
End-If;

&MyFile = GetFile("TreeDump.txt", "A");
&RootNodeObj = &TreeObj.FindRoot();

&MyFile.WriteLine("Process Root Node : " | &RootNodeObj.Name);

ProcessNodeChildren(&RootNodeObj);
&MyFile.Close();
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Chapter 49

Universal Queue Classes

Understanding Universal Queue Classes

The universal queue classes provide the means by which applications can inspect objects that are processed by the queue server, such as tasks, agents, and queues. The classes also enable tasks to reenter the queue with their original task ID, as well as keep task times based on its original entry into the system.

All of the classes, and most of the properties and methods that make up the universal queue classes have a GUI representation in the PeopleSoft Multi-Channel Framework. This document assumes that the reader is familiar with PeopleSoft Multi-Channel Framework.

Related Links

"PeopleSoft MultiChannel Framework" (PeopleTools 8.54: MultiChannel Framework)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

MCFFactory Class Hierarchy

Image: MCFFactory class hierarchy

The MCFFactory class is the root class from which the other classes are derived. Instantiate an object in this class, then traverse down the properties to inspect other individual objects, such as tasks, agents or queues. You can also instantiate individual MCFFactory objects directly and inspect their properties. The following diagram illustrates hierarchy in MCFFactory class.

Scope of the Universal Queue Classes

The universal queue classes can be instantiated only from PeopleCode.

The universal queue classes can be called from a component, an internet script, or an Application Engine program.

Universal queue classes can be of Local, Global, or Component scope.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Data Types of the Universal Queue Classes

Every universal queue class is its own data type, that is, Agent objects are declared as data type Agent, LogicalQueue objects are declared as type LogicalQueue, and so on.

The following are the data types of the universal queue classes:

- Agent
- AgentPhysQueueProps
- AgentPhysQueueTasks
- Broadcast
- LogicalQueue
- MCFFactory
- PhysicalQueue
- Task
- TaskList
- Util

How to Import Universal Queue Classes

The universal queue classes are *not* built-in classes, like rowset, field, record, and so on. They are application classes. You must import the universal queue application package before you can use the classes in your PeopleCode program.

An import statement names either all the classes in a package or one particular application class. For importing the universal queue classes, PeopleSoft recommends that you import all the classes in the application package.

The application package PT_MCF_UQAPI contains the following sub-packages:

- Agent
- AgentPhysQueueProps
- AgentPhysQueueTasks
- Broadcast
- LogicalQueue
- MCFFactory
- PhysicalQueue

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- Task
- TaskList
- Util

The import statements you should use are as follows:

```
import PT_MCF_UQAPI:Agent:*;
import PT_MCF_UQAPI:AgentPhysQueueProps:*;
import PT_MCF_UQAPI:AgentPhysQueueTasks:*;
import PT_MCF_UQAPI:Broadcast:*;
import PT_MCF_UQAPI:LogicalQueue:*;
import PT_MCF_UQAPI:MCFFactory:*;
import PT_MCF_UQAPI:PhysicalQueue:*;
import PT_MCF_UQAPI:Task:*;
import PT_MCF_UQAPI:TaskList:*;
import PT_MCF_UQAPI:Util:*;
```

Using the asterisks after the package name makes all the application classes directly contained in the named package available. Application classes contained in subpackages of the named package are *not* made available.

Related Links

Understanding Application Classes

How to Create a Universal Queue Object

After you've imported the universal queue classes, you instantiate an object of one of those classes using the constructor for the class and the *Create* function.

The following example creates a new instance of the MCFFactory class, as the variable &MyMCFFactory, with local scope:

```
Local MCFFactory &myMCFFactory  = Create MCFFactory ();
```

Related Links

Universal Queue Classes Constructors

Universal Queue Classes Built-in Functions

"DeQueue" (PeopleTools 8.54: PeopleCode Language Reference)

"EnQueue" (PeopleTools 8.54: PeopleCode Language Reference)

"Forward" (PeopleTools 8.54: PeopleCode Language Reference)

"InitChat" (PeopleTools 8.54: PeopleCode Language Reference)

"MCFBroadcast" (PeopleTools 8.54: PeopleCode Language Reference)

"NotifyQ" (PeopleTools 8.54: PeopleCode Language Reference)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Universal Queue Classes Constructors

You must use the constructor for each class to instantiate an instance of that class. The following are the constructors for the universal queue Classes.

Agent

Syntax

Agent(*AgentID*)

Description

Use the Agent constructor to instantiate an Agent object.

All objects encapsulated by this object are created when the constructor is called.

Note: When an MCFFactory object is created, Agent objects are automatically created. In this case, the number of tasks in the list is limited by the *MAX_TASKLIST_ITEMS* parameter used when creating the MCFFactory object.

Parameters

AgentID	Specify a valid AgentID as a string.

Returns

An Agent object.

Example

```
Create Agent(&AgentID);
```

Related Links

Agent Class

AgentPhysQueueProps

Syntax

AgentPhysQueueProps(*AgentID*, *PhysicalQueueID*)

Description

Use the AgentPhysQueueProps constructor to instantiate an agent physical queue properties object.

Parameters

AgentId	Specify as valid AgentId as a string.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

PyhscialQueueId Specify a PhyscialQueueId as a string.

Returns

An agent physical queue properties object.

Related Links

AgentPhysQueueProps Class

AgentPhysQueueTasks

Syntax

AgentPhysQueueTasks(*AgentID*, *PhysicalQueueID*)

Description

Use the AgentPhysQueueTasks constructor to instantiate an agent physical queue task object.

Parameters

AgentID Specify an agent ID as a string.

PhysicalQueueID Specify a PhysicalQueueID as a string.

Returns

An agent physical queue task object.

Related Links

AgentPhysQueueTasks Class

Broadcast

Syntax

Broadcast()

Description

Use the Broadcast constructor to instantiate a Broadcast object.

Parameters

None.

Returns

A Broadcast object.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

Broadcast Class

LogicalQueue

Syntax

LogicalQueue(*LogicalQueueID*)

Description

Use the LogicalQueue constructor to instantiate a LogicalQueue object.

Parameters

LogicalQueueID	Specify the ID of a logical queue as a string.

Returns

A LogicalQueue object.

Example

```
Local LogicalQueue &MyLogQueue = Create LogicalQueue(&LogicalQueueID);
```

Related Links

LogicalQueue Class

MCFFactory

Syntax

MCFFactory([*MAX_TASKLIST_ITEMS*])

Description

Use the MCFFactory constructor to instantiate an MCFFactory object.

Parameters

MAX_TASKLIST_ITEMS	Specify the maximum number of tasks loaded on a TaskList.

Returns

An MCFFactory object.

Example

```
Local MCFFactory &myMCFFactory = Create MCFFactory(MAX_TASKLIST_ITEMS);
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

MCFFactory Class

PhysicalQueue

Syntax

PhysicalQueue(*PhysicalQueueID*)

Description

Use the PhysicalQueue constructor to instantiate a PhysicalQueue object. All objects encapsulated by this object are created when the constructor is called.

Note: When an MCFFactory object is created, the PhysicalQueue objects are automatically created. In this case, the number of tasks in the list is limited by the *MAX_TASKLIST_ITEMS* parameter used when creating the MCFFactory object.

Parameters

PhysicalQueueID Specify a physical queue ID as a string.

Returns

A PhysicalQueue object.

Example

```
Local PhysicalQueue &myPhysicalQueue = Create PhysicalQueue(&PhysicalQueueID);
```

Related Links

PhysicalQueue Class

Task

Syntax

Task(*TaskNumber*)

Description

Use the Task constructor to instantiate a task object.

Only persistent tasks (email and generic tasks) are available for introspection. Each persistent task goes through a lifecycle that is recorded by the following statuses:

State	***Indicated Action***	***Status of Task Object***
Enqueued by the universal queue server	Enqueued	ENQ

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

State	*Indicated Action*	*Status of Task Object*
Universal queue assigns to physical queue	Assigned	ASGN
Agent accepts task	Accepted	ACPT
Agent completes task	Done	DONE
Task is not accepted within the overflow (action) time period	Overflowed	OVFL
Agent does not complete task or task not assigned within the escalation (complete) time period	Escalated	ESCL
Inderminate Task (task not found in system)	Indeterminate	IND

Parameters

TaskNumber Specify a task number.

Returns

A task object if the task exists, or an error message if the task number is not in the expected format. If the task number is properly formatted, but the task is not found, the task object is returned with a task status of IND.

Example

```
Local string &tasknumber, &status;

Local Task &myTask = Create Task(&tasknumber);

&status = &myTask.Status;
```

Related Links

Task Class

TaskList

Syntax

TaskList(*Status*, *TaskType*, *PhysicalQueueID*, *AgentID*)

Description

Use the TaskList constructor to instantiate a task list.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

If the queue is not provided, a list of tasks for all physical queues for that *TaskType* and *Status* is returned. To get all tasks on all queues do not specify any of the optional parameters.

Parameters

Status Specify a task status, as an uppercase string. If you do not specify a valid status, an empty tasklist is returned. Valid values are:

Value	***Description***
ACPT	Accepted
ASGN	Assigned
ENQ	Enqueued
ESCL	Escalated
OVFL	Overflowed

TaskType Specify a task type as a lowercase string. Valid values are:

Value	***Description***
chat	Chat tasks.
email	Email tasks.
generic	Generic type tasks.
voice	Voice type tasks.

PhysicalQueueID Specify a physical queue ID as a string.

AgentID Specify an agent ID as a string.

Returns

A task list object.

Example

```
Local string &sStatus;

/* get all enqueued task on the UQ server*/

&sStatus = "ENQ";
Local TaskList &myTaskList = Create TaskList (&sStatus, "", "", "");
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

TaskList Class

Util

Syntax

```
Util()
```

Description

Use the Util constructor to instantiate a util object.

Parameters

None.

Returns

A Util object.

Example

```
Create Util();
```

```
Local &myUtil = create Util();
```

Related Links

Util Class

Agent Class

Use the agent class to refresh or view the properties, such as the agent ID or buddy list associated with a particular agent.

Related Links

"Defining Agents" (PeopleTools 8.54: MultiChannel Framework)

Agent Methods

In this section, we discuss the agent class methods. The methods are discussed in alphabetical order.

Delete

Syntax

```
Delete()
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the Delete method to delete an agent from the database. You cannot delete an agent that has still has open tasks.

Parameters

None.

Returns

A number. The values are:

Value	*Description*
0	Agent deleted successfully.
1	Invalid agent ID.
2	Agent has accepted task and cannot be deleted.
3	Other SQL error in executing deletion. Possibly there are errors in the child tables.

Example

```
import PT_MCF_UQAPI:*;

   &testAgent = create PT_MCF_UQAPI:Agent("QEMGR");

   /* Delete an UQ Agent definition */
   &retCode = &testAgent.Delete();
```

Refresh

Syntax

Refresh()

Description

Use the Refresh method to refresh the properties of the agent.

An agent on a queue is processing tasks as they are assigned to them. Use this method to see realtime statistics on how much load an agent has, or possibly before running any metrics.

If you're interested in how tasklists have changed, use the RefreshQTaskList method instead.

Parameters

None.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

None.

Example

The following refreshes all the properties of the agent:

```
&MyAgent.Refresh();
```

Related Links

RefreshQTaskList

RefreshQTaskList

Syntax

RefreshQTaskList(*PhysQ*)

Description

Use the RefreshQTaskList method to refresh the task list properties for the specified physical queue.

You might use this method if you're interested in seeing the realtime statistics for a particular tasklist. If you are only interested in an agent's work, use the Refresh method.

Parameters

PhysQ	Specify a physical queue ID as a string.

Returns

None.

Example

The following refreshes all task lists on the first physical queue of the agent:

```
&MyAgent.RefreshQTaskList(&myAgent.PhysicalQueueID [1]);
```

Related Links

Refresh

Agent Properties

In this section, we discuss the agent class properties. The properties are discussed in alphabetical order.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

AgentID

Description

This property returns the agent ID as a string.

This property is read-only.

AgentProps

Description

This property returns the agent properties associated with this agent as an array of AgentPhysQueueProps objects.

This property is read-only.

Example

The following example returns the workload for physical queue SALES of agent properties object:

```
Local number &i = 1;

While &i < &myAgent.TotalPhysicalQueues
   If &myAgent.AgentProps[&i].PhysicalQueueID = "SALES" Then
      &AgentWorkLoad = &myAgent.AgentProps[&i].WorkLoad
      break;
   End-If;
End-While;
```

Related Links

AgentPhysQueueProps Class

AgentTasks

Description

This property returns the agent tasks associated with this agent as an array of AgentPhysQueueTasks objects.

This property is read-only.

Example

The following example returns the task number for the second task on physical queue SALES in the accepted task list:

```
Local Number &i = 1;

While &i < &myAgent.TotalPhysicalQueues
   If &myAgent.AgentProps[&i].PhysicalQueueID = "SALES" then
      &Tasknumber = &myAgent.AgentsTasks [&i].AcceptedTaskList.Task[2].TaskNumber
      break;
   End-If;
End-While;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

AgentPhysQueueTasks Class

Buddy

Description

This property returns a list of buddies for this agent, as an array of string.

This property is read-only.

Example

The following example returns the total number of buddies on the list:

```
&BuddyTotal = &myAgent.Buddy.Len;
```

Language

Description

This property returns the list of languages associated with the agent as an array of string.

This property is read-only.

Example

The following code example returns the first language code in the list of languages associated with the agent:

```
&Language = &myAgent.Language[1];
```

Name

Description

This property returns the name of the agent as a string.

This property is read-only.

NickName

Description

This property returns the nick name of the agent as a string.

This property

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

PhysicalQueueID

Description

This property returns the physical queues to which this agent is assigned as an array of string.

This property is read-only.

Example

The following example returns the first physical queue of agent.

```
&PhysicalQueueID = &myAgent.PhysicalQueueID[1];
```

Related Links

PhysicalQueue Class

TotalPhysicalQueues

Description

This property returns the total number of physical queues to which this agent is assigned as a number.

This property is read-only.

Example

```
&TotalPhysicalQueues = &myAgent.TotalPhysicalQueues;
```

Related Links

PhysicalQueue Class

AgentPhysQueueProps Class

Use the AgentPhysQueueProps class to view the properties of the physical queue assigned to an agent.

AgentPhysQueueProps Properties

In this section, we discuss the agent physical queue properties class properties. The properties are discussed in alphabetical order.

AgentID

Description

This property returns the agent ID as a string.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-only.

PhysicalQueueID

Description

This property returns the physical queue ID as a string.

This property is read-only.

Example

The following code example returns the physical queue ID for the physical queue of agent.

```
&PhyscalQueueID = &myAgentPhysQueueProps.PhysicalQueueID;
```

Related Links

PhysicalQueue Class

SkillLevel

Description

This property returns the skill level as a number.

This property is read-only.

Example

The following code example returns the skill level on physical queue.

```
&SkillLevel = &myAgentPhysQueueProps.SkillLevel;
```

WorkLoad

Description

This property returns the maximum work load that can be assigned to the agent, as an integer.

This property is read-only.

AgentPhysQueueTasks Class

Use the AgentPhysQueueTasks class to refresh or view the tasks associated with the physical queue assigned to the agent.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

AgentPhysQueueTasks Method

In this section, we discuss the agent physical queue tasks class method Refresh.

Refresh

Syntax

Refresh(*TaskList*)

Description

Use the Refresh method to refresh the specified task list.

Parameters

TaskList	Specify the task list you want refereshed. You must specify a task list for this parameter.

Returns

None.

Example

The following code example refresehs the accepted task list of the physical queue (&MyAgentPhysQueueTasks) for the agent.

```
&myAgentPhysQueueTasks.Refresh(&myAgentPhysQueueTasks.AcceptedTaskList);
```

Related Links

TaskList Class

AgentPhysQueueTasks Properties

In this section, we discuss the agent physical queue tasks class properties. The properties are discussed in alphabetical order.

AcceptedTaskList

Description

This property returns the accepted task list as a task list object.

This property is read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

The following code example returns the task number of the first accepted task:

```
&TaskNumber = &myAgentPhysQueueTasks.AcceptedTaskList.Task[1].TaskNumber;
```

AssignedTaskList

Description

This property returns the assigned task list as a task list object.

This property is read-only.

AgentID

Description

This property returns the agent ID as a string.

This property is read-only.

PhysicalQueueID

Description

This property returns the physical queue ID as a string.

This property is read-only.

Example

The following code example returns the physical queue ID for the physical queue of agent.

```
&PhyscalQueueID = &myAgentPhysQueueTasks.PhysicalQueueID;
```

Related Links

PhysicalQueue Class

Broadcast Class

The Broadcast class has a single method, Broadcast. Use the Broadcast method to broadcast a notification message. You can specify whether to send the message to agents, to a queue, or even system wide.

Broadcast Class Method

The following is the description of the Broadcast class method Broadcast.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Broadcast

Syntax

```
Broadcast(ClusterID,QueueID, ChannelID, AgentState, AgentPresence, Message,
MessageSetNumber, MessageNumber, DefaultMessage, SecurityLevel, ImportanceLevel,
SenderId, NameValueString)
```

Description

Use the Broadcast function to broadcast a notification message. You can specify whether to send the message to agents, to a queue, or even system wide.

Parameters

ClusterID
Specify the name of the cluster that you want to broadcast the message to, such as, RENCLSTR_001, as a string.

QueueID
Specify the name of the physical or logical queue that you want to broadcast the message to, such as, SALES, as a string.

ChannelID
Specify the name of the channel, or task, for the broadcast, such as Email, Chat, Voice or Generic, as a string.

AgentState
Specify the state of the agents you want to broadcast the message to, such as Available, as a string.

AgentPresence
Specify the presence of the agents you want to broadcast the message to, such as Active, as a string.

Message
Specify the text of the message you want to broadcast, as a string.

MessageSetNumber
Specify the message set number of a message from the message catalog if you want to broadcast a message from the message catalog. You must also specify values for the *MessageNumber* and *DefaultMessageText* parameters if you want to broadcast this type of message. Specify the message set number as a number.

MessageNumber
Specify the message number of a message from the message catalog if you want to broadcast a message from the message catalog. You must also specify values for the *MessageSetNumber* and *DefaultMessageText* parameters if you want to broadcast this type of message. Specify the message number as a number.

DefaultMessageText
Specify the text to be used if the specified message catalog message isn't found. Use the *MessageSetNumber* and *MessageNumber* parameters to specify the catalog message. Specify the default message text as a string.

SercurityLevel
Specify the security level for the broadcast message, as a string.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ImportanceLevel	Specify the importance level of the broadcast message, as a string.
SenderID	Specify the ID of the sender of the broadcast message, as a string.
NameValueString	Specify a string containing name-value pairs specific to your application.

Returns

None.

Example

The following example would broadcast a message to a specific logical queue:

```
import PT_MCF_UQAPI:Broadcast:*;
Local PT_MCF_UQAPI:Broadcast &BC;

&BC.Broadcast("", "SALES", "", "", "Best of Luck!", "", "", "Default Message", "PRI⇒
V1", "URGENT", "Admin", "EffDate, 2005-10-25:12:00:45");
```

Related Links

"MCFBroadcast" (PeopleTools 8.54: PeopleCode Language Reference)

LogicalQueue Class

A logical queue is an application level queue that receives work requests (tasks) relating to an application area, such as chat requests regarding sales information, and routes them to agents capable of handling the work. Use the LogicalQueue class to view the properties for a logical queue.

LogicalQueue Properties

In this section, we discuss the logical queue class properties. The properties are discussed in alphabetical order.

LogicalQueueID

Description

This property returns the logical queue ID as a string.

This property is read-only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

PhysicalQueueID

Description

This property returns all the physical queues associated with this logical queue as an array of PhysicalQueue objects.

This property is read-only.

Example

The following code example returns the physical queue ID for the fourth physical queue.

```
&PhyscalQueueID = &myLogicalQueue.PhysicalQueue[4].PhyscalQueueID;
```

MCFFactory Class

The MCFFactory class is the base class of the universal queue classes. Instantiating an object in this class automatically instantiates all the associated universal queue classes. The MCFFactory contains all the logical queues operating on the MCF universal queue. The logical queues are comprised of physical queues. Agents log onto these physical queues. Tasks are queued to physical queues, and later, assigned and accepted by agents. If agents aren't available on a physical queue to accept the tasks on that queue, the tasks are either escalated or put into overflow.

MCFFactory Property

In this section, we discuss the MCFFactory class property LogicalQueue.

LogicalQueue

Description

This property returns all the logical queues with which this MCFFactory object is associated, as an array of LogicalQueue objects.

This property is read-only.

Example

The following code example returns the physical queue ID for the first physical queue on the logical queue, as well as the total of overflowed taskes on the first physical queue on the logical queue.

```
Local number &TotalTasks;

Local MCFFactory &myMCFFactory  = Create MCFFactory ();

&PhyscalQueueID = &myMCFFactory.LogicalQueue [1].PhysicalQueue [1].PhysicalQueueID;

&TotalTasks  = &myMCFFactory.LogicalQueue [1].PhysicalQueue [1].OverflowedTaskList.⇒
Total;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

PhysicalQueue Class

Logical queues can be partitioned into physical queues for scalability. Use the PhysicalQueue class to refresh and view the properties of a physical queue.

PhysicalQueue Methods

In this section, we discuss the physical queue class methods. The methods are discussed in alphabetical order.

Refresh

Syntax

Refresh()

Description

Use the Refresh method to refresh all the objects in the physical queue.

Parameters

None.

Returns

None.

Example

```
&myPhysicalQueue.Refresh();
```

RefreshTaskList

Syntax

RefreshTaskList(*TaskList*)

Description

Use the RefreshTaskList method to refresh the specified task list.

Parameters

TaskList	Specify the task list you want refereshed. You must specify a task list for this parameter.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

None.

Example

The following code example refreshes the accepted task list for the physical queue.

```
&myPhysicalQueue.RefreshTaskList(&myPhysicalQueue.AcceptedTaskList);
```

PhysicalQueue Properties

In this section, we discuss the physical queue class properties. The properties are discussed in alphabetical order.

AcceptedTaskList

Description

This property returns the accepted task list as a task list object.

This property is read-only.

Example

The following code example returns the task number of the first accepted task:

```
&TaskNumber = &myPhysicalQueue.AcceptedTaskList.Task[1].TaskNumber;
```

Related Links

TaskList Class

AssignedTaskList

Description

This property returns the assigned task list as a task list object.

This property is read-only.

Related Links

TaskList Class

Agent

Description

This property returns all the agents assigned to the physical queue as an array of agent objects.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-only.

Example

The following example returns the name of the third agent.

```
&AgentName = &MyPhysicalQueue.Agent[3].Name;
```

BrowserURL

Description

This property returns the URL of the browser as a string. The format is that of an absolute URL.

The URL for the REN server that serves this MCF cluster for external clients and for agent chat. The Browser URL may be different from the InternalURL, which should not have to go through any firewall, reverse proxy server or other outward-facing security barrier.

This property is read-only.

Related Links

InternalURL

EnqueuedTaskList

Description

This property returns the enqueued task list as a task list object.

This property is read-only.

Related Links

TaskList Class

EscalatedTaskList

Description

This property returns the escalated task list as a task list object.

This property is read-only.

Related Links

TaskList Class

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

InternalURL

Description

This property returns the internal URL as a string. The format is that of an absolute URL.

This property is read-only.

Related Links

BrowserURL

IsActive

Description

This property returns true if the physical queue is active, false otherwise.

This property is read-only.

Example

```
Local LogicalQueue &myLogicalQueue  = Create LogicalQueue (&LogicalQueueID);

For &I = 1 to &myLogicalQueue.PhysicalQueue.Len

&PhyscalQueueID = &myLogicalQueue.PhysicalQueue[&I].PhyscalQueueID;
&myPhysicalQueue = Create PhysicalQueue (&PhysicalQueueID);

   If &myPhysicalQueue.IsActive Then
      /* do work */
   Else
      /* return error */
   End-If;

End-For;
```

LogicalQueueID

Description

This property returns the logical queue ID associated with the physical queue as a string.

This property is read-only.

Example

```
&LogicalQueueID = &myPhysicalQueue.LogicalQueueID;
```

OverflowedTaskList

Description

This property returns the overflowed task list as a task list object.

This property is read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

TaskList Class

PhysicalQueueID

Description

This property returns the physical queue ID of this physical queue.

This property is read-only.

RENURLID

Description

This property returns the ID of the REN server for the MCFFactory as a string.

This property is read-only.

TotalAgents

Description

This property returns the total number of agents belonging to this physical queue as a number. They may or may not be logged to the queue at that time.

This property is read-only.

Task Class

Use the task class to manipulate tasks or to view the properties of a specific task.

Task Methods

In this section, we discuss the task class methods. The methods are discussed in alphabetical order.

Close

Syntax

Close(*Comment*)

Description

Use the Close method to close the task. Only use this method with overflowed or escalated tasks.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Note: This method does *not* resubmit the task. Use the Enqueue method to resubmit the task, then use this method to close it.

Parameters

Comments

Specify any comments you want associated with this closed task.

You can specify a null value (`""`) for this parameter.

Returns

None.

Related Links

Enqueue

Enqueue

Syntax

Enqueue(*LogicalQueueID*,*AgentID*, *Timeout*, *ResponseTime*, *Cost*, *Priority*, *MinSkill*)

Description

Use the Enqueue method to add a task to the logical queue that the task was first assigned to. Every task enters the universal queue by being assigned to a logical queue.

Considerations Specifying Time

If no value (zero) is provided for the time parameters (such as *Timeout* or *ResponseTime*) the Timeout or ResponseTime properties from the task are used, respectively. This may cause the time to never occur as it creates a moving deadline. To avoid such a problem the time can be calculated for each task prior to enqueue as shown below.

Note: This logic is not included in the task's enqueue function, so as to allow you the choice for how you want your application to handle this situation.

```
&Utilobj = create Util();
&CurrentTask = create Task(&Task_Number);
&TimeDelta = &Utilobj.GetTimeDiff(&currenttime, &CurrentTask.EscalationTime) / 60;
&AgentAcceptTime = &Utilobj.GetTimeDiff(&CurrentTask.EnqueueTime, &CurrentTask.Over⇒
FlowTime) / 60;
    If AddToDateTime(&currenttime, 0, 0, 0, 0, &AgentAcceptTime, 0) >= &CurrentTask⇒
.EscalationTime Then
       If &TimeDelta > 0 Then
          &AgentAcceptTime = &TimeDelta;
       Else
/* The current time already exceeds the Escalationn time*/
       End-If;
    End-If;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

LogicalQueueId

Specify the logical queue that you want to add this task to, as a string. You can specify a null value (`""`) for this parameter. If no value is provided , the logicalQueueID that is a property of task is used.

AgentID

Specify the agent ID for this task, as a string. You can specify a null value (`""`) for this parameter. If you specify a null value, the task is given to any available agent. You might expect to use a null for this parameter generally, as most tasks are to be reassinged for random agent allocation. However, there may be cases where a particular agent (such as one who previously worked on this task) might be required to take this task. In this case an agentID is provided

Timeout

Specify the time out period for this task as a number of minutes. You can specify a zero for this parameter. If no value is provided, the Timeout property of the task is used.

The acceptance timeout is the period of time that an agent has to accept an assigned task (click on the flashing icon on the MultiChannel console). If the task is not accepted within this time, the task is re-enqueued.

ResponseTime

Specify the response time for this task as a number of minutes. You can specify a zero for this parameter. If no value is provided, the ResponseTime property of the task is used.

The response time refers to the when a task should be completed by in order to satisfy customer contracts (such as, a platinum customer who requires a response in one day for a email. If by the end of 24 hours the task is not completed, it is escalated or the response time is exceeded.)

Cost

Specify the cost of this task as a number. You can specify a zero for this parameter. This is the cost of the task as set by the application when the task was enqueued. If no cost is set at that time, then the default cost is used.

Priority

Specify the priority of the task as a number. One is the lowest possible priority. Higher numbers indicate high priorities. If no priority is set, the default priority for the task is used.

MinSkill

Specify the minimum skill level required to do this task, as a number. You can specify a zero for this parameter.

Returns

None.

Example

```
&CurrentTask = create Task(&Task_Number);
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
&CurrentTask.Enqueue(&CurrentTask.PhysicalQueueID, "", &AgentAcceptTime, &TaskCompl⇒
eteTime, &CurrentTask.Cost, &CurrentTask.Priority, &CurrentTask.SkillLevel);
```

Refresh

Syntax

Refresh()

Description

Use the Refresh method to refresh the task properties. If you only want to refresh the status, use the RefreshStatus method.

Parameters

None.

Returns

None.

Example

The following refreshes all the properties of the task:

```
&MyTask.Refresh();
```

Related Links

RefreshStatus

RefreshStatus

Syntax

RefreshStatus()

Description

Use the RefreshStatus method to refresh only the status of the task. If you want to refresh all the task properties, use the Refresh method.

Parameters

None.

Returns

None.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

The following refreshes the status of the task:

```
&MyTask.RefreshStatus();
```

Related Links

Refresh

Task Properties

In this section, we discuss the task class properties. The properties are discussed in alphabetical order.

AgentID

Description

This property returns the agent ID as a string.

This property is read-only.

ApplicationData

Description

This property returns a string in which data relevent to the task is passed. Typically, for a task, it contains the URL to show when an agent access this task, the subject, and so on. This data is not really useful to the end-user, but only for administrators and for test purposes.

This property is read-only.

Comments

Description

Use this property to either set or return the comments associated with this task, as a string.

This property is read-write.

EnqueueTime

Description

This property returns the date and time when the task was submitted to the universal queue as a DateTime value.

This property is read-only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

EscalationTime

Description

This property returns the date and time when the task will be removed from the queue and placed in the escalated pool as a DateTime value.

This property is read-only.

Language

Description

This property returns the language associated with the task as a string.

This property is read-only.

OriginalTime

Description

This property returns the date and time when the task was first submitted to the universal queue as a DateTime value. This value is maintained for a task through its various stages and cannot change.

This property is read-only.

OverFlowTime

Description

This property returns a DateTime value representing the date and time when the task has reached the stipulated time during which the universal queue server could not find an agent to accept the task.

This property is read-only.

PhysicalQueueID

Description

This property returns the physical queue associated with the task as a string.

This property is read-only.

TiedAgentID

Description

This property returns the agent ID of the agent this task is enqueued for as a string.

This property is read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

TaskList Class

Use the task list class to refresh or view a task list.

TaskList Method

This section discusses the task list method Refresh.

Refresh

Syntax

Refresh()

Description

Use the Refresh method to refresh the task list properties.

Parameters

None.

Returns

None.

Example

The following refreshes all the properties of the task list:

```
&MyTaskList.Refresh();
```

TaskList Properties

This sections discusses all the properties for the task list class. The properties are discussed in alphabetical order.

AgentID

Description

This property returns the agent ID as a string.

This property is read-only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

PhysicalQueueID

Description

This property returns the physical queue associated with the task list as a string.

This property is read-only.

Task

Description

This property returns all of the tasks in the task list as an array of task objects.

This property is read-only.

Example

```
For &I = 1 to &MyTaskList.Total
   &MyTask = &MyTaskList[&I];
   /* do work on every task in list */
End-For;
```

TaskType

Description

This property returns the task type as a string. A tasklist only contains tasks of a single type. The following are the valid task types for a tasklisk:

Value	*Description*
ACPT	Accepted
ASGN	Assigned
ENQ	Enqueued
ESCL	Escalated
OVFL	Overflowed

This property is read-only.

Total

Description

This property returns the total number of tasks in the list as a number.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-only.

Util Class

The Util class is used to perform certain useful tasks, such as calculating times (so a task will timeout).

Util Methods

This section discusses the Util class methods. The methods are discussed in alphabetical order.

GetLogicalQueue

Syntax

GetLogicalQueue(*PhysicalQueueID*)

Description

Use the GetLogicalQueue to get the logical queue ID for the specified physical queue.

Parameters

physicalQueueID	Specify the physical queue ID that you want to find the logical queue for, as a string.

Returns

A string containing the logical queue ID.

Example

The following code example returns the logical queue ID for a given physical queue ID .

```
&LogicalQueueID = &testUtil.GetLogicalQueue(&PhysicalQueueID);
```

GetTimeDiff

Syntax

GetTimeDiff(*DateTime1*, *DateTime2*)

Description

Use the GetTimeDiff method to determine the difference between two DateTime values.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

DateTime1	Specify the starting date and time as a DateTime value.
DateTime2	Specify the ending date and time as a DateTime value.

Returns

A number specifying the difference between the two DateTime values (in seconds.)

Example

In the following example, &nPeriod is 15 minutes.

```
&DTM1 = DateTimeValue("10/09/97 10:35:36");
&DTM2 = DateTimeValue("10/09/97 10:50:36");

Local number &nPeriod = &myUtil.GetTimeDiff(&DTM1, &DTM2) / 60;
```

MCFFactory Example

The following is an example of creating an MCFFactory, then traversing the branches to reach elements from different points. It is the loops that are important—any code within the loops is just an example of retrieval.

```
&testMCFFactory = create MCFFactory(100); /* set a maximum number of tasks in a tas⇒
k  list to 100 */

Local integer &i, &j, &k;
&i = 1;
&j = 1;
&k = 1;
&l = 1;
&m = 1;
&n = 1;

While &j < &testMCFFactory.LogicalQueue.Len + 1
   /*looping through the logical queues*/
   While &i < &testMCFFactory.LogicalQueue [&j].PhysicalQueue.Len + 1
      /*looping through the physical queues*/

      /*  e.g. Tasklists by physical queues*/
      &PhysQID = &testMCFFactory.LogicalQueue [&j].PhysicalQueue [&i].PhysicalQueue⇒
ID;
      &nOvflTaskTotal = &testMCFFactory.LogicalQueue [&j].PhysicalQueue [&i].OverFl⇒
owedTaskList.Total;

      While &k < &testMCFFactory.LogicalQueue [&j].PhysicalQueue [&i].OverFlowedTas⇒
kList.Total + 1
         /*looping through the Tasklist on physical queues*/

         /*  e.g. Tasks by physical queues*/
         &tasknum = &testMCFFactory.LogicalQueue [&j].PhysicalQueue [&i].OverFlowed⇒
TaskList.Task [&k].TaskNumber;

         &k = &k + 1;
      End-While; /* &k loop */
      /*Task List by Agents on a Physical Queue */
      While &l < &testMCFFactory.LogicalQueue [&j].PhysicalQueue [&i].TotalAgents +⇒
 1
         While &m < &testMCFFactory.LogicalQueue [&j].PhysicalQueue [&i].Agent [&l]⇒
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
.TotalPhysicalQueues + 1
            /*  e.g. Workload of agents on physical queues.  NOTE: &m  and &i are n⇒
ot the same value for the same physical queue.*/
            &AgentMaxWorkload = &testMCFFactory.LogicalQueue [&j].PhysicalQueue [&i⇒
].Agent [&l].AgentProps [&m].Workload;
            While &n < &testMCFFactory.LogicalQueue [&j].PhysicalQueue [&i].Agent [⇒
&l].AgentsTasks [&m].AcceptedTaskList.Total + 1
               /* e.g. tasks on Agent's accepted list  NOTE: &m  and &i are not the⇒
 same value for the same physical queue.*/
               &tasknum = &testMCFFactory.LogicalQueue [&j].PhysicalQueue [&i].Agen⇒
t [&l].AgentsTasks [&m].AcceptedTaskList.Task [&n];
               &n = &n + 1;
            End-While; /* &n Loop - tasks on Phys Q of Agents  */
            &n = 1;
            &m = &m + 1;
         End-While; /* &m loop - Phys Q of Agents  - convoluted*/
         &m = 1;
         &l = &l + 1;
      End-While; /* &l loop - Agents on Phys Q */
      &i = &i + 1;
      &k = 1;
   End-While; /* &i loop- Physical Queues*/
   &j = &j + 1;
   &i = 1;
End-While; /* &j loop - Logical Queues*/
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Chapter 50

Verity Search Classes

Understanding the Verity Search Classes

The Verity search classes enable you to create a logical search index as well as access a search index and query its contents. Every Verity search index in the PeopleSoft system must have a logical search index created to describe it.

The SearchIndex objects can be created for the following types of content:

- Indexing content references in a PeopleSoft portal.
- Indexing data in PeopleSoft records.
- Web crawling a file system.
- Web crawling URLs.
- User defined indexes (such as a PeopleSoft application).

Portal users can index and search on content references through the Verity search classes using PeopleCode. The Portal Administration pages provide a GUI access to indexing a portal. This search index is what is used when doing searches on the portal. Users can create search indexes and index data in PeopleSoft records. The Search Index Designer provides a GUI tool to create these indexes.

Users can create search indexes and spider files systems or URL's. The Search Index Designer provides a GUI tool to create these indexes.

Users can create their own custom search indexes.

PeopleSoft has integrated the Verity search engine into PeopleTools.

All searches done using the Verity search classes are executed against a Verity search index. A search index is similar to a record in many ways:

- It has fields that hold information about a document.
- It stores one row of information for each document indexed.
- It can store information in different languages.

You must build a search index before you can use the Verity search classes.

For the portal, you can build a search index either using the Verity search classes (BuildSearchIndex) PortalRegistry method) or using the Portal Administration.

To index and search something that isn't registered in the portal, you must build your own search index.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

After you've built a search index, you can execute a search against the index, and execute a search query. A search query (SearchQuery object) represents the items in an index that match a query. These matched items are retrieved in the SearchResult collection.

In addition, you can also check for any errors that were generated by the search.

If you specify multiple indexes to search over, and none of the collections' indexes are built, an error is returned. Otherwise, if there is at least one built index collection, and there is a matching search result, it is displayed.

Related Links

"Understanding Verity Search Indexes" (PeopleTools 8.54: System and Server Administration)

BuildSearchIndex

Using the SearchResult Collection

You specify the size of the SearchResult collection when you execute the search. If more search results were returned than can be contained in the single SearchResult collection, you can access the next set of search results by executing the search again, specifying only a different starting point.

For example, suppose your search returns 28 documents that match the query, but the size you specified when you executed the search was 10. You have to execute the search three times to access all the documents that matched the query.

The following pseudo-code could be behind a "Next Matches" button.

- &Start indicates at what document you want to start your search query.
- &Size is the number of search results returned in every search.
- &SearchQuery is the query object you created at the start of your program.

```
&Start = &Start + &Size;

&SearchQuery.Execute(&Start, &Size);
```

Understanding Search Results

Each search result in the SearchResult collection contains:

- Key
- Score
- SearchFields

The key uniquely identifies each document in the SearchResult collection. Keys provide a link back to the item that was indexed. The value returned by the Key property depends on the search index. If you're using a search index with the portal, the key contains the content provider and the URL. If you're not using the portal search index, the key is determined by the developer who created the search index.

Each query returns matched documents in relevance-ranked order, with those documents considered most relevant appearing at the top of the list. During search processing, a score is calculated for each retrieved

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

document. This is the value stored in the Score property. A Score is assigned a value from 0.00 to 1.00, where 1.00 represents a perfect match to the search criteria provided.

Each search result contains fields. If this is a non-portal search, these fields were specified by the developer when they created the search index. If this is a portal search, the fields are the following:

Field	*Description*
VALID_FROM_DATE	Valid from date
VALID_TO_DATE	Valid to date
CREATION_DATE	Creation date
CONTENT_PROVIDER	Content provider name
URL	URL
DESCRIPTION	Description

An external URL has the full URI attached so it might look like this:

```
URL: http://sports.mysports.com/nba/teams/chi/
```

Whereas a URL with a content provider specified is comprised of two portions.

```
Content Provider: HRMS

URL:ICType=Panel&Menu=ADMINISTER_WORKFORCE_(U.S.)&Market=GBL&PanelGroupName=ABSENCE⇒
_HISTORY1
```

You can interrogate each field in the SearchField collection to find its name and value.

Related Links

Key
Score
SearchFields

Understanding the Differences Between Verity Search Classes and the PeopleTools Search Framework Classes

The Verity search classes were implemented specifically to support PeopleTools integration with the Verity search engine. Conversely, the PeopleTools Search Framework was developed to provide an interaction layer that is independent of any specific search engine.

The Verity search objects are implemented as PeopleCode built-in objects. PeopleTools Search Framework objects are implemented through an open source PeopleCode application package. In both cases, the primary interaction class is the SearchQuery class. With Verity, a SearchQuery object is instantiated using the PortalRegistry or Session built-in classes. With the PeopleTools Search Framework, a SearchQuery object is instantiated from a SearchQueryService object.

Related Links

Understanding the PeopleSoft Search Framework Classes

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Data Type and Scope of Verity Search Objects

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Verity Search Classes Hierarchy

The following flowcharts show the different Verity search classes and how they are interrelated.

Image: Search class hierarchy (part 1 of 2)

The following flowchart shows the different Verity search classes and how they are interrelated.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Image: Search class hierarchy (part 2 of 2)

Here is another flowcharts that shows the different Verity search classes and their correlation.

Error Handling with the Verity Search Classes

All errors for the Verity search classes, like the other APIs, are logged in the PSMessages collection, instantiated from a session object.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The search classes log errors "interactively", that is, as they happen. For example, suppose you specified an invalid SearchField name. The error would be logged in the PSMessages collection as soon as you executed the ItemByName method.

If you want to search for errors in the query string before you execute the search, you can use the SearchQuery Parse method.

When to check for errors depends on your application. However, if you check for errors after every assignment, you may see a performance degradation.

The easiest way to check for errors is to check the number of messages in the PSMessages collection, using the Count property. If the Count is 0, there are no errors.

```
Local ApiObject &MySession;
Local ApiObject &ERRORCOL;
Component ApiObject &SearchQuery, &SearchResultCol, &SearchResult;
Component Number &Start, &Size;

&MySession = %Session;

If &MySession Then
   /* connection is good */

   &SearchQuery = &MySession.GetSearchQuery();
   &SearchQuery.Indexes = "PSC";
   &SearchQuery.Language = %Language;
   &SearchQuery.QueryText = SEARCH_RECORD.USER_QUESTION.Value;

   &Start = 1;
   &Size = 20;

   &SearchResultsCol = &SearchQuery.Execute(&Start, &Size);

   If &SearchResult.HitCount > 0 Then
      For &I = 1 to &SearchResultCol.Count
         &SearchResult = &SearchResultCol.Item(&I);

         /* Do processing */

      /* Do error checking */

         &ERRORCOL = &MySession.PSMessages;
         If (&ERRORCOL.Count <> 0) Then
            /* errors occurred . . . do processing */
         Else
            /* no errors */
         End-If;

      End-For;
   Else
      /* do processing for no returned matches to query */
   End-if;
Else
   /* do processing for no connection */
End-If;
```

Related Links

Error Handling

Parse

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Data Type and Scope of Verity Search Objects

All search objects, like a SearchResult collection, a SearchField, and so on, are declared as type ApiObject. For example,

```
Local ApiObject &SearchResultCol;

Local ApiObject &SearchField;
```

Note: All Search objects can be declared only as Local.

A search object can be instantiated only from PeopleCode using a PortalRegistry or Session object.

This object can be used anywhere you have PeopleCode, that is, in an application class, Application Engine PeopleCode, record field PeopleCode, and so on. The limits placed on where you can use this object depend on how the object is used. For example, if you're doing search index administration, you are updating the database, and that can be done only in certain events.

Note: The Verity search classes are not supported for Application Engine programs run via the PSAESRV process. In addition, the Verity search classes do not work in Application Engine programs run on the System 390.

Verity Search Classes Reference

A SearchQuery object must be instantiated from either a Session object or a PortalRegistry object. The Verity search classes do not have any built-in functions. Therefore, this reference section includes documentation on specific, search-related methods from the Session class and the PortalRegistry class.

This reference section documents the following Verity search classes:

- SearchQuery class.
- ParseResult collection.
- ParseResult class.
- SearchResult collection.
- SearchResult class.
- SearchField collection.
- SearchField class.
- SearchIndex collection.
- SearchIndex class.
- SearchRecord Options class.
- SearchRecordField collection.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- SearchRecordField class.
- Search Language collection.
- Search Language class.
- Search Schedule collection.
- Search Schedule class.
- Search HTTP Options class.
- Search FS Options class.
- Search Start Options collection.
- Search Start Options class.

Session Class Methods

A SearchQuery object must be instantiated from either a Session object or a PortalRegistry object. The Verity search classes do not have any built-in functions.

In this section, the search-related Session class methods are presented in alphabetical order.

Related Links

Understanding Session Class
Understanding the Portal Registry

GetSearchIndexes

Syntax

GetSearchIndexes()

Description

The GetSearchIndexes method returns a collection of SearchIndex objects.

A SearchIndex object and its children are used only for index administration, that is, creating and building search indexes. This method is *not* used with queries.

Parameters

None.

Returns

A SearchIndex collection object, populated with zero or more SearchIndex objects.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

SearchIndex Collection

GetSearchQuery

Syntax

GetSearchQuery()

Description

The GetSearchQuery method returns an empty search query object used to start a search.

Parameters

None.

Returns

An empty search query object.

Example

```
&SearchQuery = %Session.GetSearchQuery();
```

Related Links

GetSearchQuery

PortalRegistry Class Methods

A SearchQuery object must be instantiated from either a Session object or a PortalRegistry object. The Verity search classes do not have any built-in functions.

In this section, the search-related PortalRegistry class methods are presented in alphabetical order.

Related Links

Understanding Process Request Classes

BuildSearchIndex

Syntax

BuildSearchIndex(*Language*)

Description

The BuildSearchIndex method builds a portal search index for the specified language.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Search Collection Path Considerations

The Search Collection Path field in the configuration file points to a directory where collections can be built and queried through the Verity search classes. However, the BuildSearchIndex method *always* builds the collection in the default path, that is, in the following:

PS_HOME\data\search*portal_name**db_name**lang_cd*

Parameters

Language Specify the language code that you want the search index built in.

Returns

An optional Boolean value: True if the search index is built successfully, False otherwise.

GetSearchQuery

Syntax

GetSearchQuery()

Description

The GetSearchQuery method returns an empty search query object.

Note: When you use this method to get a search query, the index property is already set to the portal registry search index, and the language property is defaulted to the end-user's language.

Parameters

None.

Returns

An empty SearchQuery object with the index and language property already set.

Example

```
&Portal = %Session.GetPortalRegistry();

&Portal.Open("PORTAL");

&SearchQuery = &Portal.GetSearchQuery();
```

Related Links

GetSearchQuery

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SearchQuery Class

The SearchQuery object is used to specify the search index and execute a query against it.

A SearchQuery object is returned by the following:

- The GetSearchQuery method from a PortalRegistry object.
- The GetSearchQuery method from a Session object.

See GetSearchQuery.

See GetSearchQuery.

SearchQuery Class Methods

In this section, we discuss the SearchQuery class methods.

Execute

Syntax

Execute(*Start*, *Size*)

Description

The Execute method runs a search query beginning at the document number specified by *Start*, and returns the number of results (or less) specified by *Size* in a SearchResult Collection.

Parameters

Start	Specify the document with which you want to start your query search. This parameter takes an integer, 1 or higher.
Size	Specify the number of results that you want returned. This parameter takes an integer value.

Returns

A SearchResult collection.

Example

```
&SearchResultCol = &SearchQuery.Execute(1, 20);
```

Related Links

SearchResult Collection

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parse

Syntax

Parse()

Description

Use the Parse method to verify the syntax of the query string specified through the QueryText property for syntax errors, such as whether there is a missing quotation mark or closing bracket.

The Parse method does not produce a collection of search results. If there are any errors, it returns a reference to a ParseResult collection that you can search through for errors. If there are not any errors, it returns a Null object.

Parameters

None.

Returns

A reference to a ParseResult collection if there are errors, Null otherwise.

Example

```
Local ApiObject &MySession;
Local ApiObject &ParseResults;
Component ApiObject &SearchQuery, &SearchResultCol, &SearchResult;
Component Number &Start, &Size;

&MySession = %Session;

If &MySession Then
   /* connection is good */

   &SearchQuery = &MySession.GetSearchQuery();
   &SearchQuery.Indexes = "PSC";
   &SearchQuery.Language = %Language;
   &SearchQuery.QueryText = SEARCH_RECORD.USER_QUESTION.Value;

   &ParseResults = &SearchQuery.Parse();

   If All(&ParseResults) AND &ParseResults.ErrorCount > 0 OR &ParseResults.WarningC⇒
ount > 0 Then

      /* Process results */

   End-if;
End-if;
```

Related Links

ParseResult Collection

SearchQuery Class Properties

In this section, we discuss the SearchQuery class properties. The properties are discussed in alphabetical order.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

HitCount

Description

The HitCount property returns the total number of documents that actually match the query.

This property is read-only.

Indexes

Description

Use the Indexes property to specify the list of indexes you want the search to query. This list is in the form of a list of comma separated index names. Use the Execute method to execute the query on all the indexes specified in this property.

If you want to search against a single index, specify the index name without any comma.

This property is read-write.

Example

The following example uses two search indexes called CATALOG1 and CATALOG2 for the word "bicycle", with the requested fields called "DESCRIPTION" and "PRICE" in the results.

```
&sqQuery = %Session.GetSearchQuery();
&sqQuery.Indexes = "CATALOG1, CATALOG2";
&sqQuery.Language = %Language;
&sqQuery.Querytext = "bicycle";
&sqQuery.SortSpecifications = "PRICE desc DESCRIPTION asc";
&sqQuery.RequestedFields = "PRICE, DESCRIPTION";

/* Execute the search, getting the first 20 results. */
&srcResults = &sqQuery.Execute(1, 20);
If &srcResults <> Null And &srcResults.Count > 0 Then

&srCurrent = &srcResults.First();
Repeat
       Local ApiObject &srFieldColl;
&srFieldsColl = &srCurrent.SearchFields;
       Local ApiObject &srField = &srFieldColl.First();
 Repeat
      /* Do something with this field. */
         &srField = &srFieldColl.Next();
       Until None(&srField);
   Until None(&srCurrent);
Else
   ReportSearchAPIErrors();
   Local string &msg;
   &msg = MsgGetText(145, 40, "No results for your search");
End-If;

Function ReportSearchAPIErrors()
   Local ApiObject &msgColl = %Session.PSMessages;
   Local number &i;
   For &i = 1 To &msgColl.count
      Local ApiObject &msg = &msgColl.item(&i);
      Error (&msg.Text);
   End-For;
   &msgColl.DeleteAll();
End-Function;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

IndexName

Description

Note: This property remains for backward compatibility only. Use the Indexes property instead.

See Indexes.

The IndexName property specifies the SearchIndex this query is to retrieve the result from.

You *must* set this property before a query can be performed on the SearchQuery object returned from the GetSearchQuery method.

This property is read-write.

Example

```
&SearchQuery.IndexName = "PSA";
```

KnowledgeBase

Description

Use the KnowledgeBase property to specify a topicset (that is, a file generated by using the mktopics Verity command for a search query. This property takes the name of a file, as a string.

This property is read-write.

Language

Description

The Language property specifies the language of the search index.

The default value for this property is the current user's language.

This property is read-write.

ProcessedCount

Description

The ProcessedCount property returns the total number of documents that were subjected to the search query.

This property is read-only.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

QueryText

Description

The QueryText property returns the query text to be submitted to the SearchQuery object.

This property is read-write.

RequestedFields

Description

The RequestedFields property specifies the set of fields to be returned with the results.

The value of this property is a list of fields, separated by commas.

If this property is not specified, all the fields (except a few internal fields) are returned with the result. You may get better performance by specifying only the fields you want returned.

This property is read-write.

Related Links

SortSpecifications SearchField Collection

ScorePrecision

Description

The ScorePrecision property specifies how precise the score should be displayed with the results.

The value of this property is a string, and can be one of the following (case is insensitive)

- 8bit
- 16bit
- 32bit

The system displays two digits after decimal point if "8bit" is selected, and 4 digits if "16bit" is selected. The default value of this property is "8bit".

If this property is set to any other value, the Execute method generates an error and terminates the search.

This property is read-write.

SortSpecifications

Description

The SortSpecifications property specifies how the results of a search should be sorted.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property should be in the following format:

```
fieldname1 {asc | desc} [fieldname2 {asc | desc} ...]
```

where *fieldname1* and *fieldname2* are field names to be used to sort the results and **asc** and **desc** are keywords for sorting in ascending or descending order.

Specifying multiple fields allows you to perform a secondary sort within the primary sorted results. For example, specifying `price asc descr desc` sorts the returned results by price in ascending order. Within the price, the results are sorted by descr field in descending order.

The default value of this property is to sort the results by score field in descending order.

Note: If you specify this property, you must also specify the RequestedFields property.

Related Links

RequestedFields

ParseResult Collection

A ParseResult Collection is returned from the Parse SearchQuery method.

See Parse.

ParseResult Collection Methods

In this section, we discuss the ParseResult collection methods. The methods are discussed in alphabetical order.

First

Syntax

```
First()
```

Description

The First method returns the first ParseResult object in the ParseResult collection. If the ParseResult collection is empty, it returns Null.

Example

```
&MyResult = &MyParseResultCollection.First();
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Next

Syntax

Next()

Description

The Next method returns the next ParseResult object in the ParseResult collection. You can use this method only after you have used the First method: otherwise the system doesn't know where to start.

This method returns a Null when there are no more ParseResult objects in the collection.

Parameters

None.

Returns

Either a reference to a ParseResult object, or, if there are no more results in the ParseResult collection, a Null.

Example

```
Repeat
   /* &parseInfo.Message() contains the message, process it */
   &parseInfo.Next()
Until None(&parseInfo);
```

ParseResult Collection Properties

In this section, we discuss the ParseResult collection properties The properties are discussed in alphabetical order.

ErrorCount

Description

The ErrorCount property returns the number of ParseResult objects in this collection with a severity of ERROR.

This property is read-only.

Example

```
For &I = 1 to &ParseResults.ErrorCount
   /* process message */
End-For;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

WarningCount

Description

The WarningCount property returns the number of ParseResult objects in this collection with a severity of WARNING.

This property is read-only.

ParseResult Class

A ParseResult object is returned from either the First or Next ParseResult Collection methods.

See ParseResult Collection.

ParseResult Class Properties

In this section, we discuss the ParseResult class properties The properties are discussed in alphabetical order.

Message

Description

The Message property returns the text of the error or warning message as a string.

This property is read-only.

Severity

Description

The Severity property returns the severity of the message as a string. Values are:

Value	*Description*
ERROR	Message is an error message.
WARNING	Message is a warning message.

This property is read-only.

SearchResult Collection

A SearchResult collection is returned from the Execute SearchQuery method.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

See Execute.

SearchResult Collection Methods

In this section, we discuss the SearchResult collection methods. The methods are discussed in alphabetical order.

First

Syntax

First()

Description

The First method returns the first SearchResult object in the SearchResult collection. If the SearchResult collection is empty, it returns Null.

Example

```
&MyResult = &MyCollection.First();
```

Item

Syntax

Item(*number*)

Description

The Item method returns the SearchResult object with the position in the SearchResult collection specified by *number*.

Parameters

Number	Specify the position number in the collection of the SearchResult object that you want returned. Values start at 1.

Returns

A SearchResult object if successful, Null otherwise.

Example

```
For &I = 1 to &MyCollection.Count

   &MyResult = &MyCollection.Item(&I);

   /* Do processing */

End-For;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Next

Syntax

```
Next()
```

Description

The Next method returns the next SearchResult object in the SearchResult collection. You can use this method only after you have used the First method: otherwise the system doesn't know where to start.

Example

```
&MyResult = &MyCollection.Next();
```

SearchResult Collection Property

In this section, we discuss the SearchResult collection property Count.

Count

Description

This property returns the number of SearchResult objects in the SearchResult collection, as a number.

This property is read-only.

Example

```
&COUNT = &MY_COLLECTION.Count;
```

SearchResult Class

The SearchResult object represents a specific SearchResult in a SearchResult Collection object.

SearchResult objects are instantiated from a SearchResult Collection with the First, ItemByName or Next methods.

See SearchResult Collection.

SearchResult Class Properties

In this section, we discuss the SearchResult class properties. The properties are discussed in alphabetical order.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Key

Description

The Key property returns the key for this SearchResult object.

This property is read-only.

Score

Description

The Score property returns the score for this SearchResult object as a string. The decimal separator in this string depends on the Peoplesoft language that was used for search. For example, if you searched in Spanish, the decimal separator would be a ',.'.

Use this property to display the score.

If you convert this string to a number using the Value function, you might not receive the correct result. This is because the Value function always expects the decimal separator character to be a period. You need to explicitly replace the decimal separator with a period before using the Value function. To avoid such conversion problems, if you want to perform score arithmetic, such as evaluating a score to see if it's below a threshold, use the ScoreAsNumber property.

This property is read-only.

Related Links

ScoreAsNumber

ScoreAsNumber

Description

This property returns the relevancy score as a floating point number between 0 and 1. This property is the same as the Score property, except that this property returns the score as a floating point number instead of a string. Use this value to perform score arithmetic such as comparing it to a threshold value. If you want to display the score, use the Score property.

This property is read-only.

Related Links

Score

SearchFields

Description

The SearchFields property returns a SearchField Collection.

This property is read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

SearchField Collection

SearchField Collection

A SearchField collection is returned by the SearchFields SearchResult property.

See SearchFields.

SearchField Collection Methods

In this section, we discuss the SearchField collection methods. The methods are discussed in alphabetical order.

First

Syntax

```
First()
```

Description

The First method returns the first SearchField object in the SearchField collection. If the SearchField collection is empty, it returns Null.

Example

```
&MyField = &MyCollection.First();
```

ItemByName

Syntax

```
ItemByName(Name)
```

Description

The ItemByName method returns the SearchField object specified by *Name*.

Parameters

Name	Specify the name of the SearchField you want returned.

Returns

A SearchField object if successful, Null otherwise.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

```
&MyField = &MyCollection.ItemByName(VALID_TO_DATE);
```

Next

Syntax

Next()

Description

The Next method returns the next SearchField object in the SearchField collection. You can use this method only after you have used the First method: otherwise the system doesn't know where to start.

Example

```
&MyField = &MyCollection.Next();
```

SearchField Collection Property

In this section, we discuss the SearchField collection property Count.

Count

Description

This property returns the number of SearchField objects in the SearchField collection, as a number.

This property is read-only.

Example

```
&COUNT = &MY_COLLECTION.Count;
```

SearchField Class

A SearchField is returned by First, ItemByName, and Next SearchField Collection methods.

See SearchField Collection.

SearchField Class Properties

In this section, we discuss the SearchField class properties. The properties are discussed in alphabetical order.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Name

Description

The Name property returns the name of this SearchField object as a string.

This property is read-only.

Value

Description

The Value property returns the value for this SearchField object as a string.

This property is read-only.

SearchIndex Collection

A SearchIndex collection is returned by the GetSearchIndexes Session class property.

The search indexes in this collection represent all of the *logical* search indexes that have been created in the PeopleSoft system.

Every search index built and used in a PeopleSoft system must have a logical search index associated with it.

See GetSearchIndexes.

SearchIndex Collection Methods

In this section, we discuss the SearchIndex collection methods. The methods are discussed in alphabetical order.

First

Syntax

```
First()
```

Description

The First method returns the first SearchIndex object in the SearchIndex collection. If the SearchIndex collection is empty, it returns Null.

Example

```
&MySearchI = &MyCollection.First();
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ItemByName

Syntax

ItemByName(*Name*)

Description

The ItemByName method returns the SearchIndex object specified by *Name*.

Parameters

Name	Specify the name of the SearchIndex that you want returned.

Returns

A SearchIndex object if successful, Null otherwise.

Example

```
&MySearchI = &MyCollection.ItemByName("MySearchIndex");
```

Next

Syntax

Next()

Description

The Next method returns the next SearchIndex object in the SearchIndex collection. You can use this method only after you have used the First method: otherwise the system doesn't know where to start.

Example

```
&MySearchI = &MyCollection.Next();
```

SearchIndex Collection Property

In this section, we discuss the SearchIndex collection property Count.

Count

Description

This property returns the number of SearchIndex objects in the SearchIndex collection, as a number.

This property is read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

```
&COUNT = &MY_COLLECTION.Count;
```

SearchIndex Class

A SearchIndex is returned by First, ItemByName, and Next SearchIndex collection methods.

A SearchIndex represents a logical search index, and all the information describing it, in the PeopleSoft system. Every search index built and used in a PeopleSoft system must have a logical search index associated with it.

See SearchIndex Collection.

SearchIndex Class Method

In this section, we discuss the SearchIndex class method Save.

Save

Syntax

Save()

Description

Use the Save method to save any changes to the search index.

Note: If you change a value of one of the properties of the subobjects (such as some of the search options, and so on) the change won't be written to the database until the SearchIndex object has been saved.

Parameters

None.

Returns

A Boolean value: True if the SearchIndex object is saved successfully, False otherwise.

SearchIndex Class Properties

In this section, we discuss the SearchIndex class properties. The properties are discussed in alphabetical order.

Note: If you change a value of one of the properties, the change won't take effect until the SearchIndex object has been saved.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ExtraOptions

Description

This property is used for the spidering search indexes. Parameters that are not covered in the SearchIndex object and its children can be passed to the Verity spidering utility using this property.

This property is read-write.

FSOpts

Description

This property returns a reference to a Search FS Options object, for FSYS type search indexes.

This property is read-only.

Related Links

Search FS Options Class

HTTPOpts

Description

This property returns a reference to a Search HTTP Options object, for HTTP type search indexes.

This property is read-only.

Related Links

Search HTTP Options Class

Languages

Description

This property returns a reference to the Search Language collection.

This property is read-only.

Related Links

Search Language Collection

Location

Description

This property specifies the file system location where the search index (collection) is located. You must use a full path name.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-write.

Name

Description

This property returns the name of the SearchIndex, as a string.

This property is read-only.

RecOpts

Description

This property returns a reference to a SearchRecord Options collection, for RECD type search indexes.

This property is read-only.

Related Links

SearchRecord Options Class

Schedules

Description

This property returns a reference to the Search Schedule collection.

This property is read-only.

Related Links

Search Schedule Collection

Type

Description

The Type property specifies the type of index. This property takes a string value. The values are:

Value	*Description*
RECD	An index generated from a PeopleSoft record
HTTP	An index generated from a spider search of the World Wide Web (WWW)
FSYS	An index generated from a spider search of a file system
PRTL	An index generated from a portal

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Value	*Description*
USER	A user defined index (that is, not one of the previous indexes)

This property is read-write.

SearchRecord Options Class

A reference to a search record options object is returned by the RecOpts SearchIndex property.

This object is valid only for Search Index types of RECD. These types of indexes are used to index data in a PeopleSoft database. The properties used with this object represent the values that must be set for this type of search index.

See RecOpts.

SearchRecord Options Class Properties

In this section, we discuss the SearchRecord option class properties. The properties are discussed in alphabetical order.

Note: If you change a value of one of the properties, the change won't take effect until the SearchIndex object has been saved.

Fields

Description

This property returns a reference to a SearchRecordField collection.

The SearchRecordField collection describes the records and fields that are indexed.

The maximum number of fields returned as part of this collection is 50.

This property is read-only.

Related Links

SearchRecordField Collection

Filter

Description

This property specifies a filter (that is, a SQL WHERE clause) used to filter out unwanted records from being indexed, as a string.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-write.

IncrementalView

Description

This property specifies a view used for accessing the records that are to be used for incremental indexing, as a string.

This property is read-write.

RecName

Description

This property returns the record name for the primary record that the search index is based on. Multiple records can be used, but they must all share a common key structure. The record name returned with this property specifies this common base key structure.

This property is read-only.

VeggieKey

Description

This property specifies a replacement pattern for the VdkVgwKey (VeggieKey) used by Verity to uniquely identify a document. The setting of this property determines what is filled in for the unique identifier for each document that gets indexed. Text in this string is replaced with either literal text in the unique identifier or a value determined by one of the following tags:

Tag	***Description***
<pairs/>	Inserts a string of NAME=VALUE; pairs for each key on the Record being indexed
<row/>	Inserts the Record keys in a SQL-like syntax
<field fieldname='*MYFIELD*'/>	Inserts the value of *MYFIELD* for the Row being indexed (if it exists in the record; an error occurs when you save the data if it is missing)
<sql stmt='*SQL STATEMENT*'/>	Inserts the value returned by the SQL statement. Only the first row returned is accepted. SQL statements that return more than one column cause an error at runtime.

To use these tags, you include them as part of the VeggieKey string. The indexing process replaces them with values. For example, given the following Row of data:

```
Record: PROD_SRCH
Field: PRODUCTID=A11111 (a key on the record)
Field: DESCR="Baby goldfish"
Field: PRICE=5.00
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

You could produce any of the following unique identifiers with various settings of VeggieKey:

VeggieKey Setting	*String Produced*
"<pairs/>"	"PRODUCTID=A11111;"
"SELECT * FROM <row/>"	"SELECT * FROM PS_PROD_SRCH WHERE PRODUCTID='A11111'"
"<pairs/> <field filedname='DESCR'/>"	"PRODUCTID=A11111; Baby goldfish"
"Total price: <sql stmt='SELECT SUM(PRICE) FROM PS_PROD_SRCH'/>"	"Total price: 550.78"

Note that the last example is not truly unique, although it is legal. It is up to the application to make sure that the setting of VeggieKey produces a unique string for each indexed document, as the indexing process does not perform this check. Applications that use VdkVgwKey to identify the results of search queries cannot find the correct document if the documents do not have a unique key.

This property is read-only.

ZoneOptions

Description

This property specifies the zone option for the index as a string. Values are:

Value	*Description*
ONE	All the fields for each row of data are inserted into the same zone in the word index. This is a simple scheme which does not allow you to search only parts of the word index but may be appropriate for applications without easily-differentiated text regions.
FLD	One zone is created for each field. The data in that field for each row is inserted into the same zone. This enables applications to search only a specific part of the word index at a time, with a potential performance gain. This does not happen automatically, however; the query interface built by the application must support searching in specific zones. The name of the zone created is the name of the field. The build process may take longer with this option set.

This property is read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SearchRecordField Collection

A SearchRecordField collection is returned from the Fields SearchRecord Options property.

The SearchRecordField collection describes the records and fields that are indexed.

The maximum number of fields returned as part of this collection is 50.

See Fields.

SearchRecordField Collection Methods

In this section, we discuss the SearchRecordField collection methods. The methods are discussed in alphabetical order.

DeleteItem

Syntax

DeleteItem(*Record, Field*)

Description

Use the DeleteItem method to delete the SearchRecordField specified by the record and field name.

This method is executed immediately, however, the values are updated in the database only when the SearchIndex is saved.

Parameters

Record	Specify a record name as a string.
Field	Specify a field name as a string.

Returns

A Boolean value: True, item was deleted successfully, False otherwise.

First

Syntax

First()

Description

The First method returns the first SearchRecordField object in the SearchRecordField collection. If the SearchRecordField collection is empty, it returns Null.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

```
&MySearchField = &MyCollection.First();
```

InsertItem

Syntax

InsertItem(*Record, Field*)

Description

Use the InsertItem method to insert a SearchRecordField object into the SearchRecordField collection.

This method is executed immediately, however, the values are updated in the database only when the SearchIndex is saved.

If the item you are trying to insert already exists, this method returns Null.

Parameters

Record	Specify a record name as a string.
Field	Specify a field name as a string.

Returns

A reference to a new SearchRecordField object if successful, Null otherwise.

ItemByName

Syntax

ItemByName(*Record, Field*)

Description

The ItemByName method returns the SearchRecordField object specified by the record and field name.

Parameters

Record	Specify a record name as a string.
Field	Specify a field name as a string.

Returns

A SearchRecordField object if successful, Null otherwise.

Example

```
&MySearchField = &MyCollection.ItemByName("SEARCH", "DATE");
```


Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Next

Syntax

```
Next()
```

Description

The Next method returns the next SearchRecordField object in the SearchRecordField collection. You can use this method only after you have used the First method: otherwise the system doesn't know where to start.

Example

```
&MySearchOpts = &MyCollection.Next();
```

SearchRecordField Collection Property

In this section, we discuss the SearchRecordField collection property Count.

Count

Description

This property returns the number of SearchRecordField objects in the SearchRecordField collection, as a number.

This property is read-only.

Example

```
&COUNT = &MY_COLLECTION.Count;
```

SearchRecordField Class

A SearchRecordField is returned by the First, ItemByName, InsertItem, and Next SearchRecordField collection methods.

A SearchRecordField object describes the records and fields that are indexed.

See SearchRecordField Collection.

SearchRecordField Class Properties

In this section, we discuss the SearchRecordField class properties. The properties are discussed in alphabetical order.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Note: If you change a value of one of the properties, the change won't take effect until the SearchIndex object has been saved.

FieldName

Description

This property returns the field name for this SearchRecordField as a string.

This property is read-only.

IsAttachment

Description

This property specifies whether the search record field is an attachment. This property takes a Boolean value: True, the field is an attachment, False otherwise.

This property is read-write.

IsVerityField

Description

This property specifies whether the search record field is a Verity field. This property takes a Boolean value: True, the field is a Verity field, False otherwise.

This property is read-write.

IsWordIndex

Description

This property specifies whether the search record field is a word index. This property takes a Boolean value: True, the field is a word index, False otherwise.

This property is read-write.

RecordName

Description

This property returns the name of the record as a string.

This property is read-only.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Search Language Collection

A reference to a Search Language collection is returned by the Languages property.

See Languages.

Search Language Collection Methods

In this section, we discuss the Search Language collection methods. The methods are discussed in alphabetical order.

DeleteItem

Syntax

DeleteItem(*Name*)

Description

Use the DeleteItem method to delete the Search Language specified by *Name*.

This method is executed immediately, however, the values are updated in the database only when the SearchIndex is saved.

Parameters

Name	Specify the name of the Search Language that you want to delete.

Returns

A Boolean value: True, item was deleted successfully, False otherwise.

First

Syntax

First()

Description

The First method returns the first Search Language object in the Search Language collection. If the Search Language collection is empty, returns Null.

Example

```
&MyLang = &MyCollection.First();
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

InsertItem

Syntax

InsertItem(*LanguageCode, MapLanguageCode*)

Description

Use the InsertItem method to insert a Search Language object into the Search Language collection.

This method is executed immediately, however, the values are updated in the database only when the SearchIndex is saved.

If the item you are trying to insert already exists, this method returns Null.

Parameters

LanguageCode	Specify a language code as a string.
MapLanguageCode	Specify a language code to map *LanguageCode* to (typically this is the same as *LanguageCode*).

Returns

A reference to a new Search Language object if successful, Null if not successful.

ItemByName

Syntax

ItemByName(*LanguageCode*)

Description

The ItemByName method returns the Search Language object specified by *LanguageCode*.

Parameters

LanguageCode	Specify the language code of the object that you want to retrieve.

Returns

A reference to a Search Language object if successful, Null otherwise.

Example

```
&MyLang = &MyCollection.ItemByName("ENG");
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Next

Syntax

```
Next()
```

Description

The Next method returns the next Search Language object in the Search Language collection. You can use this method only after you have used the First method: otherwise the system doesn't know where to start.

Example

```
&MyLang = &MyCollection.Next();
```

Search Language Collection Property

In this section, we discuss the Search Language collection property Count.

Count

Description

This property returns the number of Search Language objects in the Search Language collection, as a number.

This property is read-only.

Example

```
&COUNT = &MY_COLLECTION.Count;
```

Search Language Class

A reference to a Search Language object is returned by the First, ItemByName, InsertItem, and Next Search Language Collection methods.

See Search Language Collection.

Search Language Class Properties

In this section, we discuss the Search Language class properties. The properties are discussed in alphabetical order.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

LanguageCd

Description

This property specifies the language code for the Search Language object as a string.

This property is read-only.

MapLanguageCd

Description

Specify a language code to map the given language to (typically this is the same as LanguageCode).

This property is read-only.

Search Schedule Collection

A reference to a Search Schedule collection is returned by the Schedules SearchIndex property.

See Schedules.

Search Schedule Collection Methods

In this section, we discuss the Search Schedule collection methods. The methods are discussed in alphabetical order.

DeleteItem

Syntax

DeleteItem(*Name*)

Description

Use the DeleteItem method to delete the Search Schedule specified by *Name*.

This method is not executed automatically. It is executed only when the SearchIndex is saved.

Parameters

Name	Specify the name of the Search Schedule that you want to delete.

Returns

A Boolean value: True, item was deleted successfully, False otherwise.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

First

Syntax

First()

Description

The First method returns the first Search Schedule object in the Search Schedule collection. If the Search Schedule collection is empty, this method returns Null.

Example

```
&MySch = &MyCollection.First();
```

InsertItem

Syntax

InsertItem(*RunCntrlID*)

Description

Use the InsertItem method to insert a Search Schedule object into the Search Schedule collection.

This method is not executed automatically. It is executed only when the SearchIndex is saved.

If the item you are trying to insert already exists, this method returns Null.

Parameters

RunCntrlId	Specify the run control ID of the search schedule object as a string.

Returns

A reference to a new Search Schedule object if successful, Null if not successful.

ItemByName

Syntax

ItemByName(*RunCntrlId*)

Description

The ItemByName method returns the Search Schedule object specified by *RunCntrlId*.

Parameters

RunCntrlId	Specify the run control ID of the search schedule object as a string.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

A Search Schedule object if successful, Null otherwise.

Example

```
&MySchedule = &MyCollection.ItemByName("MySched");
```

Next

Syntax

```
Next()
```

Description

The Next method returns the next Search Schedule object in the Search Schedule collection. You can use this method only after you have used the First method: otherwise the system doesn't know where to start.

Example

```
&MySched = &MyCollection.Next();
```

Search Schedule Collection Property

In this section, we discuss the Search Schedule collection property Count.

Count

Description

This property returns the number of Search Schedule objects in the Search Schedule collection, as a number.

This property is read-only.

Example

```
&COUNT = &MY_COLLECTION.Count;
```

Search Schedule Class

A reference to a Search Schedule object is returned by the First, ItemByName, InsertItem, and Next Search Schedule Collection methods.

See Search Schedule Collection.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Search Schedule Class Properties

In this section, we discuss the Search Schedule class properties. The properties are discussed in alphabetical order.

Note: If you change a value of one of the properties, the change won't take effect until the SearchIndex object has been saved.

BuildType

Description

This property specifies how you want the index rebuilt with this schedule item. Values are:

Value	*Description*
INCR	Incremental updates an existing index. Use this schedule item for indexes with small amounts of data, and for cleaning up large indexes periodically when they start to fragment.
RBLD	Rebuild deletes the index and starts from scratch. Use this to add to an existing, large index.

This property is read-write.

RunCntlId

Description

This property returns the Run Control ID associated with the schedule item.

This property is read-only.

RunRecurrence

Description

This property specifies the name of the Recurrence Definition as a string. For example: "Daily Search Rebuild".

This property is read-write.

Related Links

"Creating Job Definitions" (PeopleTools 8.54: Process Scheduler)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ServerName

Description

This is the name of the Process Scheduler Server that processes the requests for this schedule item, for example, "PSNT".

This property is read-write.

Related Links

"Understanding Server Definitions" (PeopleTools 8.54: Process Scheduler)

Search HTTP Options Class

A reference to a Search HTTP Options object is returned by the HTTPOpts SearchIndex property.

This object is valid only for Search Index types of HTTP. These types of indexes spider URLs. The properties available using this object represent values that must be set for spidering URL's.

See HTTPOpts.

Search HTTP Options Class Properties

In this section, we discuss the Search HTTP Option class properties. The properties are discussed in alphabetical order.

Note: If you change a value of one of the properties, the change won't take effect until the SearchIndex object has been saved.

AllowHTTPS

Description

This property is used to cause the HTTP Spider Gateway to descend HTTPS (SSL) links and HTTP links when it builds the index. This property takes a Boolean value: True, use the HTTPS (SSL) links, False otherwise.

This property is read-write.

DomainLimit

Description

This property limits spidering (indexing) to the specified domain. This property takes a string value.

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GlobList

Description

This property specifies a list of filename "globs" which the indexing process uses to filter its list. The GlobListType determines how the filtering is done. The value of this property is a space-separated list of filenames with or without wildcards. The following is an example of the value for this property:

```
"*.doc *.txt *.html robots.txt"
```

This property is read-write.

Related Links

GlobListType

GlobListType

Description

This property determines how the values specified with GlobList are used. Values are:

Value	*Description*
ALL	Ignore the values specified with GlobList. Index all filenames encountered regardless of their pattern.
EXC	Exclude the values specified with GlobList. Index everything except names that match a pattern in GlobList.
INC	Include the values specified with GlobList. Index only filenames that match a pattern in GlobList and exclude all other filenames.

This property is read-write.

Related Links

GlobList

LinkDepth

Description

This property determines how many links the HTTP Spider descends from its starting point as a number.

A value of 1, for example, indexes the original page as well as the documents linked to by that page, and then stop.

A value of 2 indexes the original page, and documents linked to it, as well as documents linked to by the second page.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

PeopleSoft recommends not setting this value over 10 without combining it with the DomainLimit property as the amount of data retrieved into the index increases geometrically with the LinkDepth.

This property is read-write.

Related Links

DomainLimit

MIMEList

Description

This property is used in a similar fashion to GlobList. It is a space-separated list of MIME Types. The MIMEListType determines how they affect indexing. The following is an example of a value for this property:

```
"text/html text/plain application/*"
```

This property is read-write.

Related Links

MIMEListType, GlobList

MIMEListType

Description

This property is used like GlobListType, but applies to MIMEList instead of GlobList. Instead of testing the pattern of the filename, this property tests the MIME-type detected for the document when determining whether to index it.

This property is read-write.

Related Links

MIMEList, GlobListType

ProxyHost

Description

This property specifies the hostname or IP address of the HTTP proxy, if the HTTP Spider Gateway needs an HTTP proxy to connect to remote websites during the indexing process.

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ProxyPort

Description

This property specifies the port number of the HTTP proxy set in ProxyHost as a number.

This property is read-write.

StartOpts

Description

This property returns a reference to a Search Start Options collection.

This property is read-only.

Related Links

Search Start Options Collection

Search FS Options Class

A reference to a Search FS Options object is returned by the FSOpts SearchIndex property.

This object is valid only for Search Index types of FSYS. These types of indexes spider a file system. The properties available using this object represent the values that must be set for spidering a file system.

See FSOpts.

Search FS Options Class Properties

In this section, we discuss the Search FS Option class properties. The properties are discussed in alphabetical order.

Note: If you change a value of one of the properties, the change won't take effect until the SearchIndex object has been saved.

GlobList

Description

This property specifies a list of filename "globs" which the indexing process uses to filter its list. The GlobListType determines how they affect indexing. The value of this property is a space-separated list of filenames with or without wildcards. The following is an example of the value for this property:

```
"*.doc *.txt *.html robots.txt"
```

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

GlobListType

GlobListType

Description

This property determines how the values specified with GlobList are used. Values are:

Value	*Description*
ALL	Ignore the values specified with GlobList. Index all filenames encountered regardless of their pattern.
EXC	Exclude the values specified with GlobList. Index everything except names that match a pattern in GlobList.
INC	Include the values specified with GlobList. Index only filenames that match a pattern in GlobList and exclude all other filenames.

This property is read-write.

Related Links

GlobList

MIMEList

Description

This property is used like GlobList. It is a space-separated list of MIME Types. The MIMEListType determines how they affect indexing. The following is an example of the value for this property:

```
"text/html text/plain application/*"
```

This property is read-write.

Related Links

MIMEListType, GlobList

MIMEListType

Description

This property is used like GlobListType, but applies to MIMEList instead of GlobList. Instead of testing the pattern of the filename, this property tests the MIME-type detected for the document when determining whether to index it.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This property is read-write.

Related Links

MIMEList, GlobListType

StartOpts

Description

This property returns a reference to a Search Start Options collection.

This property is read-only.

Related Links

Search Start Options Collection

Search Start Options Collection

The values in the Search Start Options Collection get passed to the −start parameter of the Verity spider utility. These values represent the starting points for spidering.

A Search Start Option collection is returned from:

- StartOpts Search HTTP Options class property
- StartOpts Search FS Options class property

See Search HTTP Options Class property

See StartOpts.

See Search FS Options Class property

See StartOpts.

Search Start Options Collection Methods

In this section, we discuss the Search Start Options collection methods. The methods are discussed in alphabetical order.

DeleteItem

Syntax

DeleteItem(*Value*)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the DeleteItem method to delete the Search Start Options specified by *Value*.

This method is executed immediately, however, the values are updated in the database only when the SearchIndex is saved.

Parameters

Value	Specify the value of the Search Start Option that you want to delete.

Returns

A Boolean value: True, item was deleted successfully, False otherwise.

First

Syntax

```
First()
```

Description

The First method returns the first Search Start Options object in the Search Start Options collection. If the Search Start Options collection is empty, this method returns Null.

Example

```
&MySearchOpts = &MyCollection.First();
```

InsertItem

Syntax

```
InsertItem(Value)
```

Description

Use the InsertItem method to insert a Search Start Options object into the Search Start Options collection.

This method is executed immediately, however, the values are updated in the database only when the SearchIndex is saved.

If the item you are trying to insert already exists, this method returns Null.

Parameters

Value	Specify the value of the Search Start Option that you want to insert.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Returns

A reference to a new Search Start Option object if successful, Null if not successful.

ItemByName

Syntax

ItemByName(*Value*)

Description

The ItemByName method returns the Search Start Options object specified by *Value*.

Parameters

Value	Specify the value of the Search Start Options that you want returned.

Returns

A Search Start Options object if successful, Null otherwise.

Example

```
&MySearchOpts = &MyCollection.ItemByName("MyStartOptions");
```

Next

Syntax

Next()

Description

The Next method returns the next Search Start Options object in the Search Start Options collection. You can use this method only after you have used the First method: otherwise the system doesn't know where to start.

Example

```
&MySearchOpts = &MyCollection.Next();
```

Search Start Options Collection Property

In this section, we discuss the Search Start Options collection property Count.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Count

Description

This property returns the number of Search Start Options objects in the Search Start Options collection, as a number.

This property is read-only.

Example

```
&COUNT = &MY_COLLECTION.Count;
```

Search Start Options Class

A reference to a Search Start object is returned by the First, ItemByName, InsertItem, and Next Search Start Options Collection methods.

See Search Start Options Collection.

Search Start Options Class Properties

In this section, we discuss the Search Start Options class properties. The properties are discussed in alphabetical order.

Note: If you change a value of one of the properties, the change won't take effect until the SearchIndex object has been saved.

IsDomainRestricted

Description

The value of this property is passed to the **−domain** option of the Verity spider utility. This property specifies whether the domain is restricted. This property takes a Boolean value: True, the domain is restricted, False otherwise.

This property is read-write.

IsHostRestricted

Description

This property specifies whether the host is restricted. This property takes a Boolean value: True, the host is restricted, False otherwise.

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Value

Description

This property returns the value of the Search Start Options, as a string.

This property is read-only.

Verity Search Classes Examples

The following PeopleCode programs are examples of how to use the Verity search classes.

General Purpose Example

The following is a general example uses two search indexes called CATALOG1 and CATALOG2 for the word "bicycle", with the requested fields called "DESCRIPTION" and "PRICE" in the results.

```
&sqQuery = %Session.GetSearchQuery();
&sqQuery.Indexes = "CATALOG1, CATALOG2";
&sqQuery.Language = %Language;
&sqQuery.Querytext = "bicycle";
&sqQuery.SortSpecification = "PRICE desc DESCRIPTION asc";
&sqQuery.RequestedFields = "PRICE, DESCRIPTION";

/* Execute the search, getting the first 20 results. */
&srcResults = &sqQuery.Execute(1, 20);
If &srcResults <> Null And &srcResults.Count > 0 Then

&srCurrent = &srcResults.First();
Repeat
       Local ApiObject &srFieldColl;
&srFieldsColl = &srCurrent.SearchFields;
       Local ApiObject &srField = &srFieldColl.First();
 Repeat
      /* Do something with this field. */
         &srField = &srFieldColl.Next();
       Until None(&srField);
   Until None(&srCurrent);
Else
   ReportSearchAPIErrors();
   Local string &msg;
   &msg = MsgGetText(145, 40, "No results for your search");
End-If;

Function ReportSearchAPIErrors()
   Local ApiObject &msgColl = %Session.PSMessages;
   Local number &i;
   For &i = 1 To &msgColl.count
      Local ApiObject &msg = &msgColl.item(&i);
      Error (&msg.Text);
   End-For;
   &msgColl.DeleteAll();
End-Function;
```

Portal Search Example

The following is a portal search example.

```
&SearchKey = %Request.GetParameter("SEARCH_TEXT");
&StartPosition = %Request.GetParameter("START_POSITION")
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
SearchResultChunkSize = 1000;

/*----------------------------------------------------------------------------
  Get a portal registry object.
----------------------------------------------------------------------------*/
&Portal = %Session.GetPortalRegistry();

/*----------------------------------------------------------------------------
  Open the desired portal.
----------------------------------------------------------------------------*/
&Portal.Open("PORTAL")

/*---------------------------------------------------------------------------
  Get a search query object.
----------------------------------------------------------------------------*/
&SearchQuery = &PORTAL.GetSearchQuery();

/*---------------------------------------------------------------------------
  Set the text of the query the user entered
----------------------------------------------------------------------------*/
&SearchQuery.QueryText = &SearchKey

/*---------------------------------------------------------------------------
  Execute the search passing in the starting position and "chunk size" (get me the ⇒
first 20 result or the third  20)
----------------------------------------------------------------------------*/
&SearchResultsColl = &SearchQuery.Execute(&StartPosition, &SearchResultChunkSize);
/*---------------------------------------------------------------------------
 Get the first result.
----------------------------------------------------------------------------*/
&SearchResult = &SearchResultsColl.First();

While (&SearchResult <> Null)

   /*-------------------------------------------------------------------------
     Example of getting the key.  In the portal case, the key is the URL, but in th⇒
e general case it could be a product id or some kind of other database key.
   -------------------------------------------------------------------------*/
   &SearchKey = &SearchResult.Key;

   /*-------------------------------------------------------------------------
     Example of getting the Field.  In the portal case, the field is the URL.  Yes,⇒
 it is redundant with the key but the key includes some {} around the URL and this ⇒
just makes it easier to get the URL.
   -------------------------------------------------------------------------*/
   &URLSearchField = &SearchResult.SearchFields.ItemByName("URL")
   &URL = &URLSearchField.Value

   /*-------------------------------------------------------------------------
     Another example of a field using dot notation to simplify the code.
   -------------------------------------------------------------------------*/
   &ContentProvider = &SearchResult.SearchFields.ItemByName("ContentProvider").Valu⇒
e

   /*-------------------------------------------------------------------------
     Call a function to insert the result into the page.
   -------------------------------------------------------------------------*/
   AddStuffToPage(&URL, &ContentProvider);

   /*-------------------------------------------------------------------------
     Get the next result of the search.
   -------------------------------------------------------------------------*/
   &SearchResult = &SearchResultsColl.Next();

End-While;
&Portal.Close();
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Chapter 51

XmlDoc Classes

Understanding XmlDoc Classes

The Extended Markup Language (XML) describes a class of data objects called XML documents. It also partially describes the behavior of computer programs which process them. The XmlDoc class is used to create and manipulate XML data.

The Extended Markup Language (XML) is a method for putting structured data in a text file. Like HTML, XML uses tags, that is, text delimited by brackets (< and >). However, HTML specifies what each tag is, and how it's supposed to be displayed in a browser. XML uses tags only to delimit data. The interpretation of that data is entirely up to the application.

For example, <UL> in HTML specifies an unordered (bulleted) list. However, with XML, it could specify an underlined link.

Each XML document has both a physical and a logical structure:

- Physically, the XML document is composed of units called *entities*. A document begins in a "root" or document entity.
- Logically, the XML document is composed of declarations, elements, comments, character references, and processing instructions

The CreateXmlDoc function creates an XmlDoc object. An XmlDoc is composed of XmlNode objects. Each XmlNode represents an XML document *entity*. You can use PeopleCode to create the following types of entities:

- Attribute (specified both by a name and a NamespaceURI)
- CDATA Section
- Comment
- Element
- Entity References
- Process Instruction
- Text

When to Use an XmlDoc Object

You can use the XmlDoc class to access inbound messages. You can also use the XmlDoc class to create XML messages to be sent out, either synchronously or asynchronously.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

All messages must be associated with a message definition. An XmlDoc message must be associated with an *unstructured* or nonrowset-based message, that is, a message definition that's created without any record definitions.

Use the XmlDoc object if any of the following is true:

- Your message structure doesn't fit the rowset model.
- Your message data doesn't come from database records.
- Your third-party source or target node requires non-XML messages.
- Your message uses the SOAP protocol.

Do *not* use the XmlDoc object if your message contains cookies.

XmlDoc Object Creation

Use the CreateXmlDoc function to create an XmlDoc object. You can create either an empty object, and populate it with data, or you can specify an XML string that is then transformed into an XmlDoc object that you can then manipulate with PeopleCode.

If you're creating an empty XmlDoc object, and you also want to specify a particular document type declaration (DTD) to be used to validate your XML, immediately after you use the CreateXmlDoc function, you should use the CreateDocumentType method to specify the DTD, followed by the CreateDocumentElement method to associate the DTD with the root entity.

For example:

```
Local XmlDoc &inXMLDoc;
Local XmlNode &docTypeNode;
Local XmlNode &rootNode;

&inXMLDoc = CreateXmlDoc("");
&docTypeNode = &inXMLDoc.CreateDocumentType("Personal", "", "Personal.dtd");
&rootNode = &inXMLDoc.CreateDocumentElement("root", "", &docTypeNode);
```

The preceding PeopleCode program produces the following XML:

```
<?xml version="1.0"?>
<!DOCTYPE Personal SYSTEM "Personal.dtd">
</root>
```

After you've created your XmlDoc object, use the GenXmlString method to create an XML string. You can then use an Internet Script (iScript) Response object method to send the string as an XML response.

Related Links

Understanding Internet Script Classes

Considerations Using a Unique Namespace

In the root tag, the attribute **xmlns** stands for the XML namespace. This allows you to define namespaces for tag names so that collisions can be avoided and validation logic can be run.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

If you do not give a prefix for an XML namespace, but instead define it with the tag (xmlns) followed by a colon (:) and then a unique namespace, for example,

```
xmlns:psft
```

For example, this sort of functionality allows you to have two nodes named "Transaction", but one can be referenced by a "psft" namespace and another not, allowing for two nodes with the same name to exist, but each containing different data.

```
<?xml version="1.0"?>
<root xmlns:psft="http://www.peoplesoft.com">
    <psft:Transaction>Value</psft:Transaction>
    <Transaction>Another</Transaction>
</root>
```

Incorrect results can be returned when you have a namespace as in the above example, which belongs to the namespace defined in http://www.people.com. When the system tries to find the path of "root/Transaction", it may return multiple nodes when in fact the end user might only want to return one.

To avoid this, do one of the following:

- Do not use FindNode. Use GetElementByTagName instead. This does not use XPath to resolve entries in the DOM. Instead, it works at a node by node basis, for example, by getting the root node, then getting the transactions node. This code may be a bit more complex to write, but you loose the richness of XPath.
- Give every **xmlns** attribute a prefix. The system will use XPath correctly and find the node.

Considerations Using Rowsets

Unstructured XML should be transformed to structured if you want to use the full rowset abilities. PeopleSoft recommends transforming the data into a rowset-based message.

If you do not want to transform the data, you need to break it up using the Transaction tag around the equivalent of each level zero rowset, as shown in the example.

```
<?xml version="1.0" ?>
- <SAMPLE_MSG>
   - <Transaction>
      - <QE_SALES_ORDER class="R">
            <QE_ACCT_ID>26</QE_ACCT_ID>
            <QE_ACCOUNT_NAME>APG-65</QE_ACCOUNT_NAME>
            <QE_ADDRESS>F18 HORNET WAY</QE_ADDRESS>
            <QE_PHONE>(206)544-1264</QE_PHONE>
            <QE_FROMROWSET />
            <QE_TOROWSET />
            <QE_SEND_SOA_BTN />
            <QE_SEND_SOS_BTN />
            <QE_TRAN_SOA_BTN />
            <QE_SEND_SQ_BTN />
            <QE_TRAN_SOS_BTN />
            <QE_TRAN_APCODE_BTN />
            <QE_TRAN_SPCODE_BTN />
            <QE_PUBXMLDOC_BTN />
            <QE_CLEAR_BTN />
         <DESCRLONG />
      </QE_SALES_ORDER>
   </Transaction>
   - <Transaction>
      - <QE_SALES_ORDER class="R">
            <QE_ACCT_ID>27</QE_ACCT_ID>
            <QE_ACCOUNT_NAME>JASON ACCOUNT</QE_ACCOUNT_NAME>
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
            <QE_ADDRESS>THE ADDRESS</QE_ADDRESS>
            <QE_PHONE>(PHONE NUMBER</QE_PHONE>
            <QE_FROMROWSET />
            <QE_TOROWSET />
            <QE_SEND_SOA_BTN />
            <QE_SEND_SOS_BTN />
            <QE_TRAN_SOA_BTN />
            <QE_SEND_SQ_BTN />
            <QE_TRAN_SOS_BTN />
            <QE_TRAN_APCODE_BTN />
            <QE_TRAN_SPCODE_BTN />
            <QE_PUBXMLDOC_BTN />
            <QE_CLEAR_BTN />
         <DESCRLONG />
      </QE_SALES_ORDER>
   </Transaction>
</SAMPLE_MSG>
```

XmlNode Class Considerations

In general, the XmlNode Class methods and properties can be broken up into the following categories:

Category	***Description***
Add	The Addxxx methods add an entity of the specified type to the end of the list of child nodes, and returns a reference to the newly created node.
Insert	The Insertxxx methods insert an entity of the specified type at the specific location and returns a reference to the newly created node.
Get	The Getxxx methods return a reference to the specified entity. The Getxxx methods may return a single reference or an array of references.
Other	The other methods enable you to find a particular entity in an XmlDoc (FindNode), copy data from one node into another, and remove nodes.

Accessing and Traversing an XmlNode Object

If you're creating an XmlDoc object, use the CreateDocumentElement, as well as the different Add and Insert methods to create XmlNode objects. These methods return a reference to the newly created node if successful.

Use the XmlNode properties for traversing the data structure (ParentNode, PreviousSibling, NextSibling, and so on.)

You can also use the ChildNodeCount property for looping through all the child nodes of a node.

Use the NodeType property to get the type of the node (element, processing instruction, comment, and so on).

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Error Handling

Use the IsNull property to verify if the XmlNode returned by a method is a valid node. In the following example, a particular node is checked to see if it has another node after it. If it doesn't, a node is added.

```
Local XmlNode &usernode;
Local string &userName;

&usernode = &inXMLDoc.DocumentElement.FindNode("/Request/Company/Location/User");

If Not (&MyNode.IsNull) Then
   &userName = &usernode.NodeValue;
Else
   /* Do error processing */
End-If;
```

SOAPDoc Object Considerations

A SOAP Message is an ordinary XML document that consists of the following parts:

- A mandatory SOAP envelope
- An optional SOAP header
- A mandatory SOAP body

The SOAPDoc class is a separate class in PeopleCode that works similarly to the XmlDoc and XmlNode classes. Many of the same methods and properties that work with an XmlDoc or XmlNode object also work with a SOAPDoc object. However, there are also methods and properties that don't apply to a SOAPDoc object.

The following XmlDoc and XmlNode methods do *not* apply to a SOAPDoc object:

- AddCDataSection
- AddProcessInstruction
- CopyToPSFTMessage
- CreateDocumentType
- InsertCDataSection
- InsertProcessInstruction
- LoadIBContent

Related Links

Understanding theSOAPDoc Class

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Scope of XmlDoc and XmlNode Objects

XmlDoc and XmlNode objects can be instantiated only from PeopleCode.

This object can be used anywhere you have PeopleCode, that is, in Application Engine PeopleCode, record field PeopleCode, and so on.

Data Type of an XmlDoc or XmlNode Object

XmlDoc objects are declared type XmlDoc.

XmlNode objects are declared type XmlNode.

For example:

```
Component XmlDoc &MyDoc;

Local XmlNode &MyNode;
```

Note: XmlNode objects can be declared only as type Local.

XmlDoc Classes Built-in Functions

"CreateSOAPDoc" (PeopleTools 8.54: PeopleCode Language Reference)

"CreateXmlDoc" (PeopleTools 8.54: PeopleCode Language Reference)

"GetNRXmlDoc" (PeopleTools 8.54: PeopleCode Language Reference)

"ReValidateNRXmlDoc" (PeopleTools 8.54: PeopleCode Language Reference)

"Transform" (PeopleTools 8.54: PeopleCode Language Reference)

"TransformEx" (PeopleTools 8.54: PeopleCode Language Reference)

"TransformExCache" (PeopleTools 8.54: PeopleCode Language Reference)

"UpdateXmlDoc" (PeopleTools 8.54: PeopleCode Language Reference)

XmlDoc Class Methods

In this section, we discuss the XmlDoc methods. The methods are discussed in alphabetical order.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

CopyRowset

Syntax

CopyRowset(*&InRowset*[, *MessageName*][, *MessageVersion*])

Description

Use the CopyRowset method to copy rowset data to an XmlDoc object.

Warning! If the XmlDoc is *not* empty, the existing structure and data are replaced with the data and structure from *InRowset* . If *MessageName* is not specified, this function makes the best possible XML structure given the passed rowset. Not passing the message name should only occur when using a nonrowset-based message or when using a standalone rowset. For best performance, PeopleSoft recommends to always specify the message name.

Parameters

&InRowset	Specify the variable of an already instantiated and populated rowset to copy data from.
MessageName	Specify the name of the message that the rowset belongs to, as a string. If the message name is not specified, the best possible XML structure is created.
MessageVersion	Specify the message version, as a string. If you do not specify a message version, the default message version is used.

Returns

A Boolean value: True, the rowset data copied successfully, False otherwise.

Example

```
Local XmlDoc &inXMLDoc;
Local boolean &ret;

&inXMLDoc = CreateXmlDoc("");
&ret = &inXMLDoc.CopyRowset(&rs, "<insert message name>", "<insert message version"⇒
);
```

Related Links

CopyToRowset

Understanding Rowset Class

CopyToPSFTMessage

Syntax

CopyToPSFTMessage(*targetDoc*, *srcPath*, *targetPath*)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the CopyToPSFTMessage method to copy an XmlDoc to a PeopleSoft message. The *srcPath* and *targetPath* parameters enable you to map the data of the XmlDoc (using the XmlDoc structure) to the message (following the message structure.)

The XmlDoc object generally has the following structure:

```
<?xml version="1.0"?>
<MESSAGE_NAME>
  <FieldTypes>
    ...
  </FieldTypes>
  <MsgData>
    <Transaction>
      ...
    </Transaction>
  </MsgData>
</MESSAGE_NAME>
```

Parameters

targetDoc Specify the XmlDoc that contains the message structure.

srcPath Specify an array of string that contains the mapping path information.

targetPath Specify an array of string that contains the mapping path information.

Returns

A number. The values are:

Value	*Description*
0	Ok
1	Missing PSCAMA structure
2	Missing FieldType structure
3	General Error

Example

```
Local XmlDoc &srcDoc, &targetDoc;
Local array of string &srcPath, &targetPath;

&srcPath = CreateArrayRept("", 0);
&targetPath = CreateArrayRept("", 0);


&srcDoc = CreateXmlDoc("");
&targetDoc = CreateXmlDoc("");
&ret = &srcDoc.ParseXmlFromURL("c:/temp/source.xml");
&ret = &targetDoc.ParseXmlFromURL("c:/temp/target.xml");
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
&srcPath.Push("QE_EMPLOYEE");
&srcPath.Push("QE_EMPLOYEE/QE_ACCOUNT_TBL");
&srcPath.Push("QE_EMPLOYEE/QE_JOBCODE");
&srcPath.Push("QE_EMPLOYEE/DEPTID");
&srcPath.Push("EMAIL_MSG_RCD");
&srcPath.Push("EMAIL_MSG_RCD/EMAIL_FILE_RCD");

&targetPath.Push("QE_EMPLOYEE_TG");
&targetPath.Push("QE_EMPLOYEE_TG/QE_ACCOUNT_TBL_TG");
&targetPath.Push("QE_EMPLOYEE_TG/QE_JOBCODE_TG");
&targetPath.Push("QE_EMPLOYEE_TG/DEPTID_TG");
&targetPath.Push("EMAIL_MSG_RCD_TG");
&targetPath.Push("EMAIL_MSG_RCD/EMAIL_FILE_RCD_TG");

&ret = &srcDoc.CopyToPSFTMessage(&targetDoc, &srcPath, &targetPath);
```

Related Links

CopyRowset

CopyToRowset

Understanding Arrays

Understanding Message Classes

CopyToRowset

Syntax

CopyToRowset(*&Rowset*, *Message_Name*, [*Message_Version*])

Description

Use the CopyToRowset method to copy data from the XmlDoc to an already instantiated rowset.

The rowset must be based on a message object that has the same *structure* as the XmlDoc. That is, if you have a record at level two in your message and you want that data, you must have the same level zero and level one records in your message as in your XmlDoc.

For example, suppose your XmlDoc had the following structure:

```
<?xml version="1.0"?>
<QE_SALES_ORDER>
    <QE_ACCT_ID/>
    <QE_ACCOUNT_NAME/>
    <QE_ADDRESS/>
    <QE_PHONE/>
    <QE_FROMROWSET/>
    <QE_TOROWSET/>
    <QE_SEND_SOA_BTN/>
    <QE_SEND_SOS_BTN/>
    <QE_TRAN_SOA_BTN/>
    <QE_SEND_SQ_BTN/>
    <QE_TRAN_SOS_BTN/>
    <QE_TRAN_APCODE_BTN/>
    <QE_TRAN_SPCODE_BTN/>
    <QE_PUBXMLDOC_BTN/>
    <QE_CLEAR_BTN/>
    <DESCRLONG/>
</QE_SALES_ORDER>
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

If you wanted to include the information in the QE_SALES_ORDER record, you would have to have *at least* the following record structure in your message:

```
QE_SALES_ORDER
```

Any records or fields that are in the XmlDoc that aren't in the message (and vice-versa) are ignored.

Rowsets should be created using the following pseudo code:

```
Local Message &msg;
Local Rowset &rs;
Local XmlDoc &inXMLDoc;
Local boolean &ret;

&msg = CreateMessage(OPERATION.<insert message name>);
&rs = &msg.GetRowset();
&inXMLDoc = CreateXmlDoc("<insert XML structure here>");
&ret = &inXMLDoc.CopyToRowset(&rs, "<insert message name>", "<insert message versio⇒
n>");
```

XmlDoc objects have to follow the Peoplesoft message format:

```
<?xml version="1.0"?>
<PSmessage>
    <MsgData>
        <Transaction>
            <Record1 class="R">
                <Field1>xxx</Field1>
                <Field2>yyy</Field2>
                ...
                <Fieldn>nnn</Fieldn>
                <Record2>
                ...
                </Record2>
            </Record1>
        </Transaction>
    </MsgData>
</PSmessage>
```

Warning! If *MessageName* is not specified, this function makes the best possible flat structure. Not passing the message name should only occur when using a nonrowset-based message or when using a standalone rowset. For best performance, PeopleSoft recommends to always specify the message name.

Parameters

&InRowset	Specify the variable of an already instantiated rowset to copy data to.
Message_Name	Specify the message name of the message. If the message name is not specified, the best possible flat structure is created.
Message_Version	Specify the message version, as a string. If the message version is not specified, the default message version is used.

Returns

This function always returns a True value, regardless of the success of the operation.

Related Links

CopyRowset

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Understanding Rowset Class
Understanding Message Classes

CreateDocumentElement

Syntax

CreateDocumentElement(*TagName* [, *NamespaceURI*] [, *&DocType*])

where *NamespaceURI* can have *one* of the following forms:

URL.*URLname*

OR a string URL, such as

http://www.peoplesoft.com/

Description

Use the CreateDocumentElement method to create the root element of the document.

For *&DocType* you must specify an already instantiated document type node using CreateDocumentType.

Parameters

TagName	Specify the name of the tag to be used for the document element.
NamespaceURI	Specify the URI that contains the Namespaces for the XmlDoc, as a string.
&DocType	Specify the document type node. This must already be instantiated using CreateDocumentType.

Returns

A reference to an XmlNode object representing the root element.

Example

For example:

```
Local XmlDoc &inXMLDoc;
Local XmlNode &docTypeNode;
Local XmlNode &rootNode;

&inXMLDoc = CreateXmlDoc("");
&docTypeNode = &inXMLDoc.CreateDocumentType("Personal", "", "Personal.dtd");
&rootNode = &inXMLDoc.CreateDocumentElement("root", "", &docTypeNode);
```

The preceding PeopleCode program produces the following XML:

```
<?xml version="1.0"?>
<!DOCTYPE Personal SYSTEM "Personal.dtd">
<root/>
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

CreateDocumentType

CreateDocumentType

Syntax

CreateDocumentType(*Name*, *PublicID*, *SystemID*)

Description

Use the CreateDocumentType method to create the document type declaration (a document type node) in the XmlDoc.

You can specify only *one* document type node for an XmlDoc.

You need to create a document type node only if you have a document type definition (DTD). You don't need to specify a document type declaration in your XML. Generally, the DTD file is used for validating the XML.

If you do specify this type of node when creating an XmlDoc in PeopleCode, you *must* specify it immediately following the creation statement. Then, you must specify the document type when you create the root node. This means your code should start with the CreateXmlDoc function, creating the XmlDoc object, then use the CreateDocumentType method, followed by the CreateDocumentElement method, creating the root node.

Considerations Using Public and System IDs

You can specify both a public and a system ID. However, if you want to use a system ID *only,* you must specify a Null string ("") for the public ID. To use a public ID *only,* you must specify a Null string ("") for the system ID. If the system ID and public ID are both Null (""), then the document type is considered as system.

To use the Personal.dtd as a system ID, you must use the following code:

```
&DocType = &MyDoc.CreateDocumentType("Personal", "", "Personal.dtd");
```

This produces the XML:

```
<!DOCTYPE Personal SYSTEM "Personal.dtd">
```

To use the Personal.dtd as a public ID, you must use the following code:

```
&DocType = &MyDoc.CreateDocumentType("Personal", "Personal.dtd", "");
```

This produces the XML:

```
<!DOCTYPE Personal PUBLIC "Personal.dtd">
```

Parameters

Name	Specify the name of the document type declaration as a string.
PublicID	Specify the public ID of the document type declaration as a string.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SystemID Specify the system ID of the document type declaration as a string.

Returns

A reference to an XmlNode object representing the document type element.

Example

The following example creates a document type declaration using the DTD named "Personal".

```
Local XmlDoc &inXMLDoc;
Local XmlNode &docTypeNode;
Local XmlNode &rootNode;

&inXMLDoc = CreateXmlDoc("");
&docTypeNode = &inXMLDoc.CreateDocumentType("Personal", "", "Personal.dtd");
&rootNode = &inXMLDoc.CreateDocumentElement("root", "", &docTypeNode);
```

This produces the following XML:

```
<?xml version="1.0"?>
<!DOCTYPE Personal SYSTEM "Personal.dtd">
<root/>
```

Related Links

CreateDocumentElement

"CreateXmlDoc" (PeopleTools 8.54: PeopleCode Language Reference)

GenFormattedXmlString

Syntax

GenFormattedXmlString()

Description

Use the GenFormattedXmlString method to return an XML string representing the XmlDoc object.

The GenFormattedXmlString method produces an XML string with new line characters and indents. If you want an unformatted XML string, that is, with all the data on a single line, use the GenXmlString method instead.

Parameters

None.

Returns

A formatted XML string.

Example

```
Local XmlDoc &inXMLDoc;
Local string &outStr;
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
&inXMLDoc = CreateXmlDoc("<?xml version='1.0'?><PSMessage/>");
&outStr = &inXMLDoc.GenFormattedXmlString();
```

Related Links

GenXmlString

GenXmlFile

Syntax

GenXmlFile(*path*)

Description

Use the GenXmlFile method to write the content of the XmlDoc object to a file. The XML output file will be in UTF-8 format, and its elements will be formatted and named exactly the same as the XML output from the GenFormattedXmlString method.

Parameters

path	Specifies the absolute system path of the destination file.

Returns

A Boolean value: True, if the XML file was saved successfully, False otherwise.

Example

```
Local XmlDoc &xmldocRoot = CreateXmlDoc(" ");
Local XmlNode &nodeRoot = &xmldocRoot.CreateDocumentElement("root");
.
.
.
&result = &xmldocRoot.GenXmlFile("c:\data.xml");
```

Related Links

GenFormattedXmlString

GenXmlString

Syntax

GenXmlString()

Description

Use the GenXmlString method to return an XML string representing the XmlDoc object.

The GenXmlString method produces an XML string with all the data on a single line. If you want a formatted XML string, that is, with new line characters and indents, use the GenFormattedXmlString method instead.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

None.

Returns

An XML string.

Example

```
Local XmlDoc &inXMLDoc;
Local string &outStr;

&inXMLDoc = CreateXmlDoc("<?xml version='1.0'?><PSMessage/>");
&outStr = &inXMLDoc.GenXmlString();
```

Related Links

GenFormattedXmlString

GetElementsByTagName

Syntax

GetElementsByTagName(*TagName*)

Description

Use the GetElementsByTagName method to return an array of XmlNode objects that match the specified tag name.

If you specify an invalid tag name, an array is still returned, however, it has 0 elements in it.

Parameters

TagName	Specify the tag name that you want to look for.

Returns

An array of XmlNode objects.

Example

Using the following Xml structure:

```
<?xml version="1.0"?>
<PSmessage>
    <MsgData>
        <Transaction>
            <Record1 class="R">
                <Field1>one</Field1>
                <Field1>two</Field1>
                <Field1>three</Field1>
            </Record1>
        </Transaction>
    </MsgData>
</PSmessage>
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The following code finds all of the *Field1* elements:

```
Local array of XmlNode &field1List;

&field1List = &inXMLDoc.GetElementsByTagName("Field1");

If &field1List.Len = 0 Then
   /* do error processing */
Else
   /* do processing */
End-If;
```

Related Links

Understanding Arrays

LoadIBContent

Syntax

LoadIBContent(*Content*[, *RootTagName*])

Description

Use LoadIBContent to load data into an XmlDoc object. This function is primarily used for display purposes, the main use is found in the Integration Broker Monitor for viewing message structures.

When *Content* is an XML string, the XmlDoc contains the DOM representation of the XML.

When *Content* is not an XML string, LoadIBContents generates a DOM wrapper.

Parameters

Content	Specify the content of the XmlDoc.
RootTagName	Specify the root tag name to be used in the XmlDoc object used as the wrapper, if the data is non-Xml. If a root tag name is not specified, and the data is non-Xml, the contents are not wrapped with the default of root tag name of PSMessage.

Returns

This method returns a Boolean value that is always True.

Example

Using the following data:

```
John Q. Public,1234 West Eastland,925-987-0909
Jane Doe,423 Someplace,234-992-9383
```

The following PeopleCode program specifies a root name:

```
Local XmlDoc &inXMLDoc;
Local boolean &ret;
Local string &inStr;

&inStr = "John Q. Public,1234 West Eastland,925-987-0909" | Char(13) | "Jane Doe,42⇒
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
3 Someplace,234-992-9383";

&inXMLDoc = CreateXmlDoc("");
&ret = &inXMLDoc.LoadIBContent(&inStr, "Root");
```

This produces the following:

```
<?xml version="1.0"?>
<Root>
  <data PsNonXml="Yes">
    <![CDATA[John Q. Public,1234 West Eastland,925-987-0909
Jane Doe,423 Someplace,234-992-9383]]>
  </data>
</Root>
```

The following PeopleCode program does not specify a root name:

```
Local XmlDoc &inXMLDoc;
Local boolean &ret;
Local string &inStr;

&inStr = "John Q. Public,1234 West Eastland,925-987-0909" | Char(13) | "Jane Doe,42⇒
3 Someplace,234-992-9383";

&inXMLDoc = CreateXmlDoc("");
&ret = &inXMLDoc.LoadIBContent(&inStr);
```

This produces the following:

```
<?xml version="1.0"?>
<PSMessage>
  <data PsNonXml="Yes">
    <![CDATA[John Q. Public,1234 West Eastland,925-987-0909
Jane Doe,423 Someplace,234-992-9383]]>
  </data>
</PSMessage>
```

The following is an example of a valid XML document:

```
Local XmlDoc &inXMLDoc;
Local boolean &ret;
Local string &inStr;

&inStr = "<?xml version='1.0'?><root/>";

&inXMLDoc = CreateXmlDoc("");
&ret = &inXMLDoc.LoadIBContent(&inStr);
```

This produces the following:

```
<?xml version="1.0"?>
<root/>
```

ParseXmlFromURL

Syntax

ParseXmlFromURL(*path* [, *DTDValidation*])

Where *path* can have *one* of the following forms—a string URL, containing the filename and extension:

```
http://www.peoplesoft.com/filename.ext
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Or an absolute file path, including the filename and extension:

```
c:\directory\filename.ext
```

Note: HTTPS is not a supported protocol for *path*.

Description

Use the ParseXmlFromURL method to convert the XML file located at *path* into an XmlDoc object that you can then manipulate using PeopleCode. The XmlDoc object executing the method is populated with the XML string after it's been converted. Any data already existing in the XmlDoc object is overwritten.

Using this method also does basic validation of the XML string, comparing it to the document type declaration (DTD) if the DOCTYPE for the DTD is provided in the XML string.

Note: PeopleSoft only supports UTF-8 encoding. Therefore, if the input file is encoded, it must be encoded in UTF-8.

Parameters

path

Specify the URL or file path to the XML that file you want to manipulate. If you specify a string URL, the URL must be contained in quotation marks.

Note: HTTPS is not a supported protocol for *path*.

DTDValidation

Specify whether to validate a document type definition (DTD.) This parameter takes a Boolean value. If you specify true, the DTD validation occurs if a DTD is provided. If you specify false, and if a DTD is provided, it is ignored and the XML isn't validated against the DTD. The default value for this parameter is false.

In the case of application messaging, if a DTD is provided, it's always ignored and the XML isn't validated against the DTD.

If the XML cannot be validated against a DTD, an error is thrown saying that there was an XML parse error.

Returns

A Boolean value: True, the XML file converted successfully and was validated, False otherwise. (If the XML file is not valid, the PeopleCode program terminates.)

Example

The following PeopleCode program loads a file from a file path:

```
Local XmlDoc &inXMLDoc;
Local boolean &ret;

&inXMLDoc = CreateXmlDoc("");
&ret = &inXMLDoc.ParseXmlFromURL("c:\temp\in.xml");
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

The following PeopleCode program loads a file from a URL:

```
Local XmlDoc &inXMLDoc;
Local boolean &ret;

&inXMLDoc = CreateXmlDoc("");
&ret = &inXMLDoc.ParseXmlFromURL("http://www.peoplesoft.com/xmlfile.xml");
```

Related Links

ParseXmlString

ParseXmlString

Syntax

ParseXmlString(*XmlString*)

Description

Use the ParseXmlString method to convert the XML string into an XmlDoc object that you can then manipulate using PeopleCode. The XmlDoc object executing the method is populated with the XML string after it's been converted. Any data already existing in the XmlDoc object is overwritten.

Using this method also does basic validation of the XML string, comparing it to the document type declaration (DTD) if the DOCTYPE for the DTD is provided in the XML string.

Parameters

XmlString	Specify an XML string that you want to be able to manipulate using PeopleCode.

Returns

A Boolean value: True, the XML string converted successfully and was validated, False otherwise. (If the XML is not valid, the PeopleCode program terminates.)

Example

```
Local XmlDoc &inXMLDoc;
Local boolean &ret;
Local string &str;

&str = "<?xml version='1.0'?><root/>";

&inXMLDoc = CreateXmlDoc("");
&ret = &inXMLDoc.ParseXmlString(&str);

If &ret Then
   /* do processing */
Else
   /* do error processing */
End-If;
```

Related Links

ParseXmlFromURL

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

XmlDoc Properties

In this section, we discuss the XmlDoc properties. The properties are discussed in alphabetical order.

DocumentElement

Description

This property returns a reference to the root element of the document as an XmlNode.

This property is read-only.

Related Links

XmlNode Class

IsNull

Description

This property returns a Boolean value, indicating whether the doc is a valid object. This property returns True if the XmlDoc object is valid, False otherwise.

This property is read-only.

XmlNode Class

Unlike C++ and Java programming model, PeopleCode interface uses the root object XmlNode to represent all 11 different derived objects. An XmlNode object can be defined only as local.

XmlNode Class Methods

Add methods create a new node of the specific type, append this new node to the child list, and return this newly created node, while Insert methods add the node to the specified position.

In this section, we discuss the XmlNode methods. The methods are discussed in alphabetical order.

AddAttribute

Syntax

```
AddAttribute(Name, Value);
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the AddAttribute method to add an attribute to an XmlNode. A reference to the newly created attribute is returned.

If you specify an attribute name that already exists, the new value you use *replaces* the existing value, and a reference to the attribute is returned.

Attributes added by the AddAttribute method appear in an arbitrary order in the generated XML.

Parameters

Name	Specify the name of the Attribute that you want to create, as a string.
Value	Specify the value of the Attribute that you want to create, as a string.

Returns

None.

Example

Here is a set of XML response code.

```
<?xml version="1.0"?>
<myroot>
   <postreqresponse>
      <candidate>
         <user>
            <location scenery="great" density="low" blank="eh?"/>

         </user>
      </candidate>
   </postreqresponse>
</myroot>
```

Here's the PeopleCode that builds it.

```
Local XmlDoc &inXMLDoc;
Local XmlNode &postReqNode;
Local XmlNode &candidatesNode;
Local XmlNode &userNode;
Local XmlNode &locationNode;
Local XmlNode &sceneryAtt;
Local XmlNode &densityAtt;
Local XmlNode &blankAtt;
Local boolean &ret;

&inXMLDoc = CreateXmlDoc("<?xml version='1.0'?><myroot/>");

&postReqNode = &inXMLDoc.DocumentElement.AddElement("postreqresponse");
&candidatesNode = &postReqNode.AddElement("candidates");
&userNode = &candidatesNode.AddElement("user");
&locationNode = &userNode.AddElement("location");

&locationNode.AddAttribute("scenery", "great");
&locationNode.AddAttribute("density", "low");
&locationNode.AddAttribute("blank", "eh?");
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

IsNull

AddAttributeNS

Syntax

AddAttributeNS(*NamespaceURI*, *AttributeName*, *Value*)

where *NamespaceURI* can have *one* of the following forms:

URL.*URLname*

OR a string URL, such as

http://www.peoplesoft.com/

Description

Use the AddAttributeNS method to add a namespace attribute to an XmlNode. The new attribute is appended to the list of child nodes.

A reference to the newly created attribute is returned.

If you specify an attribute name that already exists, the new value you use *replaces* the existing value, and a reference to the attribute is returned.

Parameters

NamespaceURI	Specify the URI that contains the Namespaces for the XmlDoc, as a string.
AttributeName	Specify the name of the Attribute that you want to create, as a string.
Value	Specify the value of the Attribute that you want to create, as a string.

Returns

None.

Example

```
Local XmlDoc &inXMLDoc;
Local XmlNode &childNode;

&inXMLDoc = CreateXmlDoc("<?xml version='1.0'?><myroot/>");
&childNode = &inXMLDoc.DocumentElement.AddElement("child");
&childNode.AddAttributeNS("http://www.peoplesoft.com", "scenery", "great");
```

Related Links

IsNull

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

AddCDataSection

Syntax

AddCDataSection(*Data*)

Description

Use the AddCDataSection to add a CDATA section to an XmlNode.

CDATA sections may occur anywhere character data may occur; they are used to escape blocks of text containing characters which would otherwise be recognized as markup.

To insert a CDATA section at a particular place in the list of nodes, use the InsertCDataSection method instead.

A reference to the newly created CDATA section is returned.

Note: You cannot use this method with a SoapDoc object.

Parameters

Data Specify the data to be included in the CDATA section as a string.

Returns

A reference to the newly created CDATA section.

Example

For example:

```
Local XmlDoc &inXMLDoc;
Local XmlNode &childNode;
Local XmlNode &cdataNode;

&inXMLDoc = CreateXmlDoc("<?xml version='1.0'?><myroot/>");
&childNode = &inXMLDoc.DocumentElement.AddElement("child");
&cdataNode = &childNode.AddCDataSection("testing...");
```

The preceding PeopleCode program produces the following:

```
<?xml version="1.0"?>
<myroot>
  <child>
    <![CDATA[testing...]]>
  </child>
</myroot>
```

Related Links

InsertCDataSection

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

AddComment

Syntax

AddComment(*Text*)

Description

Use the AddComment method to add a comment to an XmlNode. The new attribute is appended to the list of child nodes.

To insert a comment at a particular place in the list of nodes, use the InsertComment method instead.

A reference to the newly created comment is returned.

Parameters

Text Specify the text to be used as the comment, as a string.

Returns

A reference to the newly created comment.

Example

For example:

```
Local XmlDoc &inXMLDoc;
Local XmlNode &childNode;
Local XmlNode &commentNode;

&inXMLDoc = CreateXmlDoc("<?xml version='1.0'?><myroot/>");
&childNode = &inXMLDoc.DocumentElement.AddElement("child");
&commentNode = &childNode.AddComment("This is an example of a comment.");
```

The preceding PeopleCode program produces the following XML:

```
<?xml version="1.0"?>
<myroot>
  <child>
    <!--This is an example of a comment.-->
  </child>
</myroot>
```

Related Links

InsertComment

AddElement

Syntax

AddElement(*TagName*)

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the AddElement method to add an element to the XmlNode. The new element is appended to the list of child nodes.

To insert an element at a particular place in the list of nodes, use the InsertElement method instead.

A reference to the newly created element is returned.

Parameters

TagName	Specify the tag for the new element that you are adding, as a string.

Returns

A reference to the newly created element.

Example

For example:

```
Local XmlDoc &inXMLDoc;
Local XmlNode &childNode;

&inXMLDoc = CreateXmlDoc("<?xml version='1.0'?><myroot/>");
&childNode = &inXMLDoc.DocumentElement.AddElement("child");
```

The preceding PeopleCode program produces the following XML:

```
<?xml version="1.0"?>
<myroot>
  <child/>
</myroot>
```

Related Links

InsertElement

GetElement

GetElementsByTagName

AddElementNS

Syntax

AddElementNS(*NamespaceURI, TagName*)

Where *NamespaceURI* can have *one* of the following forms:

URL.*URLName*

Or a string URL, such as:

```
http://www.peoplesoft.com/
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use AddElementNS to add a namespace element to an XmlNode. The new element is appendced to the list of child nodes.

To insert a Namespace element at a particular place in the list of nodes, use the InsertElementNS method instead. A reference to the newly created element is returned. If you specify an element name that already exists, the new value you use replaces the existing value, and a reference to the element is returned.

Parameters

NamespaceURI	Specify the URI that contains the Namespaces for the XmlDoc, as a string.
TagName	Specify the name of the Element that you want to create, as a string.

Returns

A reference to the newly created element if successful. If not successful, the IsNull property is set to True.

Example

```
Local XmlDoc &inXMLDoc;
Local XmlNode &childNode;

&inXMLDoc = CreateXmlDoc("<?xml version='1.0'?><myroot/>");
&childNode = &inXMLDoc.DocumentElement.AddElementNS("http://www.peoplesoft.com", "c⇒
hild");
```

AddEntityReference

Syntax

AddEntityReference(*Name*)

Description

Use the AddEntityReference method to add an entity reference. An entity reference refers to the content of the named entity. The new entity reference is appended to the list of child nodes. In the generated XML, the entity reference is automatically prefaced with the '&' character and suffixed with a semi-colon.

The named entity must exist in the document type declaration (DTD).

To insert an entity reference at a particular place in the list of nodes, use the InsertEntityReference method instead.

Parameters

Name	Specify the name of the entity to which this reference refers to.

Returns

A reference to the newly created entity reference.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

For example:

```
Local XmlDoc &inXMLDoc;
Local XmlNode &childNode;
Local XmlNode &entityRef;

&inXMLDoc = CreateXmlDoc("<?xml version='1.0'?><myroot/>");
&childNode = &inXMLDoc.DocumentElement.AddElement("child");
&entityRef = &childNode.AddEntityReference("MyURL");
```

The preceding PeopleCode program produces the following XML:

```
<?xml version="1.0"?>
<myroot>
  <child>
&MyURL;  </child>
</myroot>
```

Related Links

InsertEntityReference

AddNode

Syntax

AddNode(*&XmlNode*)

Description

Use the AddNode method to add an XmlNode to the XmlDoc. The new node is appended to the list of child nodes.

To insert a node at a particular place in the list of nodes, use the InsertNode method instead.

A reference to the newly created node is returned.

Parameters

&XmlNode	Specify an already instantiated XmlNode that you want to add.

Returns

None.

Example

```
Local XmlDoc &inXMLDoc, &firstDoc;
Local XmlNode &childNode;

&firstDoc = CreateXmlDoc("<?xml version='1.0'?><myroot><child><subchild/></child></⇒
myroot>");
&inXMLDoc = CreateXmlDoc("<?xml version='1.0'?><root/>");
&childNode = &firstDoc.DocumentElement.FindNode("/child");
&inXMLDoc.DocumentElement.AddNode(&childNode);
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Related Links

InsertNode

AddProcessInstruction

Syntax

AddProcessInstruction(*Target*, *Data*)

Description

Use the AddProcessInstruction method to add a processing instruction to an XmlNode. The new process instruction is appended to the end of the child list.

To insert a processing instruction at a particular place, use the InsertProcessInstruction method instead.

A reference to the newly created processing instruction is returned.

Note: You cannot use this method with a SoapDoc object.

Parameters

Target	Specify the application to which the instruction is directed, as a string.
Data	Specify the data used with the processing instruction.

Returns

A reference to the newly created processing instruction.

Example

For example:

```
Local XmlDoc &inXMLDoc;
Local XmlNode &procInst;

&inXMLDoc = CreateXmlDoc("<?xml version='1.0'?><myroot/>");
&procInst = &inXMLDoc.DocumentElement.AddProcessInstruction("xml-stylesheet", "href⇒
=""book.css"" type=""text/css""");
```

The preceding PeopleCode program produces the followingXML :

```
<?xml version="1.0"?>
<myroot>
  <?xml-stylesheet href="book.css" type="text/css"?>
</myroot>
```

Related Links

InsertProcessInstruction

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

AddText

Syntax

AddText(*Data*)

Description

Use the AddText method to add a text node to an XmlNode.

Note: A text node is *not* the same as a text declaration. The text declaration is added automatically with the CreateXmlDoc function. A text node just contains text within an XmlDoc.

To insert a text node at a particular place, use the InsertText method instead.

A reference to the newly created text node is returned.

Parameters

Data Specify the data to be used as the text node, as a string.

Returns

A reference to the newly created text node.

Example

For example:

```
Local XmlDoc &inXMLDoc;
Local XmlNode &childNode;
Local XmlNode &textNode;

&inXMLDoc = CreateXmlDoc("<?xml version='1.0'?><myroot/>");
&childNode = &inXMLDoc.DocumentElement.AddElement("child");
&textNode = &childNode.AddText("This is text");
```

The preceding PeopleCode program produces the following XML:

```
<?xml version="1.0"?>
<myroot>
  <child>This is text</child>
</myroot>
```

Related Links

InsertText

CopyNode

Syntax

CopyNode(*&Node*)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the CopyNode method to copy a node specified by *&Node* and *all* of its child nodes into the current node, as a child node. The new node is appended to the end of the list of child nodes. The specified node can belong to a different XmlDoc.

If you just want to copy a top-level node, without copying its children, you can just create a new node with the name of the node you want.

Parameters

&Node Specify an already instantiated node that you want to copy.

Returns

None.

Example

Suppose that your XmlDoc has the following structure:

```
<?xml version="1.0"?>
<myroot>
  <child>
    <subchild/>
  </child>
</myroot>
```

The following PeopleCode copies the node *child* and copies it into another doc.

```
Local XmlDoc &inXMLDoc, &firstDoc;
Local XmlNode &childNode;

&firstDoc = CreateXmlDoc("<?xml version='1.0'?><myroot><child><subchild/></child></⇒
myroot>");
&inXMLDoc = CreateXmlDoc("<?xml version='1.0'?><root/>");
&childNode = &firstDoc.DocumentElement.FindNode("/child");
&inXMLDoc.DocumentElement.CopyNode(&childNode);
```

The following is the new structure:

```
<?xml version="1.0"?>
<root>
  <child>
    <subchild/>
  </child>
</root>
```

Related Links

AddNode

InsertNode

GetChildNode

FindNode

FindNodes

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

FindNode

Syntax

FindNode(*Path*)

Description

Use the FindNode method to return a reference to an XmlNode.

The path is specified as the list of tag names, to the node that you want to find, each separated by a slash (/).

Parameters

Path

Specify the tag names up to and including the name of the node that you want returned, starting with a slash and each separated by a slash (/). This is known as the XPath query language.

See XML Path Language (XPath) Version 1.0.

Returns

An XmlNode matching the path if successful. If not successful, the IsNull property on the XmlNode is set to True.

Example

Suppose your XmlDoc has the following structure:

```
<?xml version="1.0"?>
<myroot>
   <postreqresponse>
      <candidate>
         <user>
            <location scenery="great" density="low" blank="eh?"/>
         </user>
      </candidate>
   </postreqresponse>
</myroot>
```

You want to return a reference to the location attribute. Use the following *Path* to do it:

```
&XmlNode = &MyDoc.FindNode("/myroot/postreqresponse/candidate/user/location");
```

Related Links

GetChildNode
FindNodes

FindNodes

Syntax

FindNodes(*Path*)

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Description

Use the FindNodes method to return a reference to an array containing all the XmlNodes that match the path.

The path is specified as the list of tag names, to the node that you want to find, each separated by a slash (/).

Parameters

Path

Specify the tag names up to and including the name of the node that you want returned, each separated by a slash (/). This is known as the XPath query language.

See XML Path Language (XPath) Version 1.0.

Returns

An array of XmlNode objects. If there is no match for the specified path, an array with 0 elements is returned.

Example

Using the following input:

```
<?xml version="1.0"?>
<PSmessage>
    <MsgData>
        <Transaction>
            <Record1 class="R">
                <Field1>one</Field1>
                <Field1>two</Field1>
                <Field1>three</Field1>
            </Record1>
        </Transaction>
    </MsgData>
</PSmessage>
```

The following PeopleCode program finds all of the *Field1* nodes:

```
Local array of XmlNode &field1List;

&field1List = &inXMLDoc.DocumentElement.FindNodes("MsgData/Transaction/Record1/Fiel⇒
d1");

If &field1List.Len = 0 Then
   /* do error processing, no nodes returned */
Else
   /* do regular processing */
End-If;
```

Related Links

GetChildNode

FindNode

Understanding Arrays

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GenXmlString

Syntax

GenXmlString()

Description

Use the GenXmlString method to generate an XML string of the XmlNode.

Parameters

None.

Returns

An XML String.

Example

```
&MyXML = &MyNode.GenXmlString();
```

GetAttributeName

Syntax

GetAttributeName(*Index*)

Description

Use the GetAttributeName method to return the specified attribute.

Parameters

Index	Specify an integer representing the attribute you want to access.

Returns

A string.

Example

```
Local XmlDoc &inXMLDoc;
Local string &attName;

&inXMLDoc = CreateXmlDoc("<?xml version='1.0'?><root/>");
&inXMLDoc.DocumentElement.AddAttribute("name", "Joe");
&inXMLDoc.DocumentElement.AddAttribute("address", "1234 West Eastland");

&attName = &inXMLDoc.DocumentElement.GetAttributeName(2);
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GetAttributeValue

Syntax

GetAttributeValue({*Name* | *Index*})

Description

Use the GetAttributeValue method to return the specific attribute value, given an attribute name. The attribute name is case-sensitive, so you must specify the exact name.

Parameters

Name* | *Index	Specify the name or index of the attribute whose value you want to access.

Returns

A string containing the value of the specified attribute.

Example

```
Local XmlDoc &inXMLDoc;
Local string &attName;
Local string &attValue;

&inXMLDoc = CreateXmlDoc("<?xml version='1.0'?><root/>");
&inXMLDoc.DocumentElement.AddAttribute("name", "Joe");
&inXMLDoc.DocumentElement.AddAttribute("address", "1234 West Eastland");

&attName = &inXMLDoc.DocumentElement.GetAttributeName(2);
&attValue = &inXMLDoc.DocumentElement.GetAttributeValue(&attName);
```

GetCDataValue

Syntax

GetCDataValue()

Description

Use the GetCDataValue method to return the *value* of the first CDATA section in an XmlNode.

Parameters

None.

Returns

A reference to the value of the first CDATA section as a string.

Example

```
Local XmlDoc &inXMLDoc;
Local XmlNode &dataNode;
Local XmlNode &cdataNode;
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
Local string &theData;

&inXMLDoc = CreateXmlDoc("<?xml version='1.0'?><root/>");
&dataNode = &inXMLDoc.DocumentElement.AddElement("data");
&cdataNode = &dataNode.AddCDataSection("this is a bunch of text");

&theData = &dataNode.GetCDataValue();
```

Related Links

AddCDataSection

InsertCDataSection

GetCDataValues

GetCDataValues

Syntax

GetCDataValues()

Description

Use the GetCDataValues method to return an array of string containing the *values* of the CDATA section in an XmlNode.

Parameters

None.

Returns

An array of string.

Example

```
Local XmlDoc &inXMLDoc;
Local XmlNode &dataNode;
Local XmlNode &cdataNode;
Local array of string &theData;

&inXMLDoc = CreateXmlDoc("<?xml version='1.0'?><root/>");
&dataNode = &inXMLDoc.DocumentElement.AddElement("data");
&cdataNode = &dataNode.AddCDataSection("this is a bunch of text");
&cdataNode = &dataNode.AddCDataSection("more text");
&cdataNode = &dataNode.AddCDataSection("still more text");

&theData = &dataNode.GetCDataValues();
```

Related Links

AddCDataSection

InsertCDataSection

GetCDataValue

Understanding Arrays

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GetChildNode

Syntax

GetChildNode(*index*)

Description

Use the GetChildNode method to return the specified child node of an XmlNode.

Parameters

Index	Specify an integer representing the child node that you want to access.

Returns

A reference to an XmlNode. If the specified XmlNode isn't found, the IsNull property for the XmlNode is set to True.

Example

```
Local XmlDoc &inXMLDoc;
Local XmlNode &dataNode;

&inXMLDoc = CreateXmlDoc("<?xml version='1.0'?><root/>");
&dataNode = &inXMLDoc.DocumentElement.AddElement("data");
&dataNode = &inXMLDoc.DocumentElement.AddElement("data2");

&dataNode = &inXMLDoc.DocumentElement.GetChildNode(2);
```

Related Links

FindNode

FindNodes

GetElement

Syntax

GetElement()

Description

Use the GetElement method to return the first child element node in the list of child nodes.

Parameters

None.

Returns

A reference to an element.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

```
Local XmlDoc &inXMLDoc;
Local XmlNode &dataNode;

&inXMLDoc = CreateXmlDoc("<?xml version='1.0'?><root/>");
&dataNode = &inXMLDoc.DocumentElement.AddElement("data");
&dataNode = &inXMLDoc.DocumentElement.AddElement("data2");

&dataNode = &inXMLDoc.DocumentElement.GetElement();
```

Related Links

AddElement

InsertElement

GetElements

GetElementsByTagName

GetElements

Syntax

GetElements()

Description

Use the GetElements method to return an array of all the XmlNode objects that are elements.

Parameters

None.

Returns

An array of XmlNode of all the element nodes. If there are no element nodes, an array with 0 elements is returned.

Example

```
Local XmlDoc &inXMLDoc;
Local XmlNode &dataNode;
Local array of XmlNode &dataList;

&inXMLDoc = CreateXmlDoc("<?xml version='1.0'?><root/>");
&dataNode = &inXMLDoc.DocumentElement.AddElement("data");
&dataNode = &inXMLDoc.DocumentElement.AddElement("data2");

&dataList = &inXMLDoc.DocumentElement.GetElements();

If &dataList.Len = 0 Then
   /* do error processing, no nodes returned */
Else
   /* do regular processing */
End-If;
```

Related Links

AddElement

InsertElement

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GetElement
GetElementsByTagName
Understanding Arrays

GetElementsByTagName

Syntax

GetElementsByTagName(*TagName*)

Description

Use the GetElementsByTagName method to return an array of XmlNode objects that match the specified tag name.

Parameters

TagName	Specify the tag name that you want to look for.

Returns

An array of XmlNode. If you specify an invalid tag name, the returned array has 0 elements.

Example

Using the following input:

```
<?xml version="1.0"?>
<PSmessage>
    <MsgData>
        <Transaction>
            <Record1 class="R">
                <Field1>one</Field1>
                <Field1>two</Field1>
                <Field1>three</Field1>
            </Record1>
        </Transaction>
    </MsgData>
</PSmessage>
```

The following PeopleCode program finds all *Field1* nodes:

```
Local array of XmlNode &field1List;

&field1List = &inXMLDoc.DocumentElement.GetElementsByTagName("Field1");

If &field1List.Len = 0 Then
   /* do error processing, no nodes returned */
Else
   /* do regular processing */
End-If;
```

Related Links

AddElement
InsertElement
GetElements

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

GetElement
Understanding Arrays

GetElementsByTagNameNS

Syntax

GetElementsByTagNameNS(*NamespaceURI, TagName*)

Where *NamespaceURI* can have *one* of the following forms:

URL.*URLName*

Or a string URL, such as:

```
http://www.peoplesoft.com/
```

Description

Use the GetElementsByTagNameNS method to return an array of XmlNode objects that match the specified namespace and qualified name.

Parameters

NamespaceURI	Specify the URI that contains the Namespace for the XmlDoc, as a string.
TagName	Specify the name of the element that you want to retrieve.

Returns

An array of XmlNode. If you specify an invalid NamespaceURI, the returned array has 0 elements.

Example

Using the following input:

```
<?xml version="1.0"?>
<Psmessage xmlns="http://www.peoplesoft.com">
    <MsgData>
        <Transaction>
            <Record1 class="R">
                <Field1>one</Field1>
                <Field1>two</Field1>
                <Field1>three</Field1>
            </Record1>
        </Transaction>
    </MsgData>
</PSmessage>
```

The following PeopleCode program finds all *Field1* nodes:

```
Local array of XmlNode &field1List;

&field1List = &inXMLDoc.DocumentElement.GetElementsByTagNameNS("http://www.peopleso⇒
ft.com", "Field1");

If &field1List.Len = 0 Then
   /* do error processing, no nodes returned */
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
Else
   /* do regular processing */
End-If;
```

InsertCDataSection

Syntax

InsertCDataSection(*Data*, *Position*)

Description

Use the InsertCDataSection method to insert a CDATA section in an XmlNode, at the location specified by *Position*.

Note: You cannot use this method with a SoapDoc object.

Parameters

Data	Specify the data for the CDATA section as a string.
Position	Specify where you want to insert the CDATA Section, as a number.

Returns

A reference to the newly created CDATA section.

Example

For example:

```
Local XmlDoc &inXMLDoc;
Local XmlNode &dataNode;
Local XmlNode &cdataNode;

&inXMLDoc = CreateXmlDoc("<?xml version='1.0'?><root/>");
&dataNode = &inXMLDoc.DocumentElement.AddElement("data");
&cdataNode = &dataNode.AddCDataSection("this is a bunch of text");
&cdataNode = &dataNode.AddCDataSection("still more text");

&cdataNode = &dataNode.InsertCDataSection("more text", 2);
```

This is the XML document before the insert:

```
<?xml version="1.0"?>
<root>
  <data>
    <![CDATA[this is a bunch of text]]>
    <![CDATA[still more text]]>
  </data>
</root>
```

This is the XML document after the insert:

```
<?xml version="1.0"?>
<root>
  <data>
    <![CDATA[this is a bunch of text]]>
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
    <![CDATA[more text]]>
    <![CDATA[still more text]]>
  </data>
</root>
```

Related Links

AddCDataSection

GetCDataValue

GetCDataValues

InsertComment

Syntax

InsertComment(*Data*, *Position*)

Description

Use the InsertComment method to insert a comment in an XmlNode at the location specified by *Position*.

Parameters

Data	Specify the data for the comment as a string.
Position	Specify where you want to insert the comment, as a number.

Returns

A reference to the newly created comment.

Example

For example:

```
Local XmlDoc &inXMLDoc;
Local XmlNode &dataNode;
Local XmlNode &commentNode;

&inXMLDoc = CreateXmlDoc("<?xml version='1.0'?><root/>");
&dataNode = &inXMLDoc.DocumentElement.AddElement("data");
&commentNode = &dataNode.AddComment("this is a comment");
&commentNode = &dataNode.AddComment("still another comment");

&commentNode = &dataNode.InsertComment("more comments", 2);
```

This is the XML document before the insert:

```
<?xml version="1.0"?>
<root>
  <data>
    <!--this is a comment-->
    <!--still another comment-->
  </data>
</root>
```

This is the XML document after the insert:

```
<?xml version="1.0"?>
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
<root>
  <data>
    <!--this is a comment-->
    <!--more comments-->
    <!--still another comment-->
  </data>
</root>
```

Related Links

AddComment

InsertElement

Syntax

InsertElement(*TagName*, *Position*)

Description

Use the InsertElement method to insert an element in an XmlNode at the location specified by *Position*.

Parameters

TagName	Specify the tagname for the element as a string.
Position	Specify where you want to insert the element, as a number.

Returns

A reference to the newly created element.

Example

For example:

```
Local XmlDoc &inXMLDoc;
Local XmlNode &dataNode;
Local XmlNode &elementNode;

&inXMLDoc = CreateXmlDoc("<?xml version='1.0'?><root/>");
&dataNode = &inXMLDoc.DocumentElement.AddElement("data");
&elementNode = &dataNode.AddElement("first");
&elementNode = &dataNode.AddElement("second");

&commentNode = &dataNode.InsertElement("third", 2);
```

This is the XML document before the insert:

```
<?xml version="1.0"?>
<root>
  <data>
    <first/>
    <second/>
  </data>
</root>
```

This is the XML document after the insert:

```
<?xml version="1.0"?>
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
<root>
  <data>
    <first/>
    <third/>
    <second/>
  </data>
</root>
```

Related Links

AddElement

InsertElementNS

Syntax

InsertElementNS(*NamespaceURI*, *TagName*, *Position*)

where *NamespaceURI* can have *one* of the following forms:

URL.*URLname*

OR a string URL, such as

http://www.peoplesoft.com/

Description

Use InsertElementNS to insert a new element in an XmlNode, at the location specified by *Position*.

Parameters

NamespaceURI	Specify the URI that contains the Namespaces for the XmlDoc.
TagName	Specify the name of the element that you want to create, as a string.
Position	Specify where you want to insert the element, as a number.

Returns

A reference to the newly created element.

Example

For example:

```
Local XmlDoc &inXMLDoc;
Local XmlNode &dataNode;
Local XmlNode &elementNode;

&inXMLDoc = CreateXmlDoc("<?xml version='1.0'?><root xmlns='http://www.peoplesoft.c⇒
om'/>");
&dataNode = &inXMLDoc.DocumentElement.AddElement("data");
&elementNode = &dataNode.AddElement("first");
&elementNode = &dataNode.AddElement("second");

&elementNode = &dataNode.InsertElementNS("http://www.peoplesoft.com", "third", 2);
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This is the XML document before the insert:

```
<?xml version="1.0"?>
<root xmlns="http://www.peoplesoft.com">
  <data>
    <first/>
    <second/>
  </data>
</root>
```

This is the XML document after the insert:

```
<?xml version="1.0"?>
<root xmlns="http://www.peoplesoft.com">
  <data>
    <first/>
    <third/>
    <second/>
  </data>
</root>
```

InsertEntityReference

Syntax

InsertEntityReference(*Name*, *Position*)

Description

Use the InsertEntityReference method to add an entity reference. An entity reference refers to the content of the named entity.

Parameters

Name	Specify the name of the entity to which this reference refers to.
Position	Specify where you want to insert the entity reference, as a number.

Returns

A reference to the newly created entity reference.

Example

For example:

```
Local XmlDoc &inXMLDoc;
Local XmlNode &dataNode;
Local XmlNode &entityRef;

&inXMLDoc = CreateXmlDoc("<?xml version='1.0'?><root/>");
&dataNode = &inXMLDoc.DocumentElement.AddElement("data");
&entityRef = &dataNode.AddEntityReference("first");
&entityRef = &dataNode.AddEntityReference("second");

&entityRef = &dataNode.InsertEntityReference("third", 2);
```

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

This is the XML document before the insert:

```
<?xml version="1.0"?>
<root>
  <data>
&first;&second;  </data>
</root>
```

This is the XML document after the insert:

```
<?xml version="1.0"?>
<root>
  <data>
&first;&third;&second;  </data>
</root>
```

Related Links

AddEntityReference

InsertNode

Syntax

InsertNode(*&NewNode*, {*&RefNode* | *Position*})

Description

Use the InsertNode method to insert a new node. The node is inserted either before the node specified by *&RefNode*, or at the location specified by *Position*.

&NewNode refers to an already instantiated XmlNode object. You must create the node before you can insert it.

&RefNode refers to an already instantiated XmlNode object.

Parameters

&NewNode	Specify the name of an already instantiated XmlNode that you want to insert.
&RefNode* | *Position	Specify either the name of an existing node or the location where you want the node to be inserted.

Returns

A reference to the newly inserted node.

Example

The following PeopleCode program inserts a node using a position:

```
Local XmlDoc &inXMLDoc, &firstDoc;
Local XmlNode &childNode;

&firstDoc = CreateXmlDoc("<?xml version='1.0'?><myroot><third><child/></third></myr⇒
oot>");
&inXMLDoc = CreateXmlDoc("<?xml version='1.0'?><root><first/><second/></root>");
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
&childNode = &firstDoc.DocumentElement.FindNode("third");

&inXMLDoc.DocumentElement.InsertNode(&childNode, 2);
```

The following PeopleCode program inserts a node using a reference node:

```
Local XmlDoc &inXMLDoc, &firstDoc;
Local XmlNode &childNode, &secondNode;

&firstDoc = CreateXmlDoc("<?xml version='1.0'?><myroot><third><child/></third></myr⇒
oot>");
&inXMLDoc = CreateXmlDoc("<?xml version='1.0'?><root><first/><second/></root>");
&childNode = &firstDoc.DocumentElement.FindNode("third");
&secondNode = &inXMLDoc.DocumentElement.FindNode("second");

&inXMLDoc.DocumentElement.InsertNode(&childNode, &secondNode);
```

The following is the XML document before the insert:

```
<?xml version="1.0"?>
<root>
  <first/>
  <second/>
</root>
```

The following is the XML document after the insert:

```
<?xml version="1.0"?>
<root>
  <first/>
  <third>
    <child/>
  </third>
  <second/>
</root>
```

Related Links

AddNode

InsertProcessInstruction

Syntax

InsertProcessInstruction(*Target*, *Data*, *Position*)

Description

Use the InsertProcessInstruction method to insert a processing instruction to an XmlNode at the location specified by *Position*.

Note: Youcannot use this method with a SoapDoc object.

Parameters

Target	Specify the application to which the instruction is directed, as a string.
Data	Specify the data to be used with the instruction.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Position Specify where you want to insert the process instruction, as a number.

Returns

A reference to the newly created processing instruction.

Example

For example:

```
Local XmlDoc &inXMLDoc;
Local XmlNode &procInst;

&inXMLDoc = CreateXmlDoc("<?xml version='1.0'?><root/>");
&procInst = &inXMLDoc.DocumentElement.AddProcessInstruction("first", "firstvalue");
&procInst = &inXMLDoc.DocumentElement.AddProcessInstruction("second", "secondvalue"⇒
);

&procInst = &inXMLDoc.DocumentElement.InsertProcessInstruction("third", "thirdvalue⇒
", 2);
```

This is the XML document before the insert:

```
<?xml version="1.0"?>
<root>
  <?first firstvalue?>
  <?second secondvalue?>
</root>
```

This is the XML document after the inser:

```
<?xml version="1.0"?>
<root>
  <?first firstvalue?>
  <?third thirdvalue?>
  <?second secondvalue?>
</root>
```

Related Links

AddProcessInstruction

InsertText

Syntax

InsertText(*Data*, *Position*)

Description

Use the InsertText method to insert a text node. The node is inserted at the location indicated by *Position*.

Note: A text node is *not* the same as a text declaration. The text declaration is added automatically with the CreateXmlDoc function. A text node just contains text within an XmlDoc.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Parameters

Data	Specify the data to be used for the text node, as a string.
Position	Specify where you want to insert the text ndoe, as a number.

Returns

A reference to the newly created text node.

Example

For example:

```
Local XmlDoc &inXMLDoc;
Local XmlNode &textNode;

&inXMLDoc = CreateXmlDoc("<?xml version='1.0'?><root/>");
&textNode = &inXMLDoc.DocumentElement.AddText("first text");
&textNode = &inXMLDoc.DocumentElement.AddText("second text");

&textNode = &inXMLDoc.DocumentElement.InsertText("third text", 2);
```

This is the XML document before the insert:

```
<?xml version="1.0"?>
<root>
first textsecond text</root>
```

This is the XML document after the insert:

```
<?xml version="1.0"?>
<root>
first textthird textsecond text</root>
```

Related Links

AddText

RemoveAllChildNode

Syntax

RemoveAllChildNode()

Description

Use the RemoveAllChildNode method to remove all child nodes for an XmlNode.

Parameters

None.

Returns

None.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

For example:

```
Local XmlDoc &inXMLDoc;
Local XmlNode &elementNode;

&inXMLDoc = CreateXmlDoc("<?xml version='1.0'?><root/>");
&elementNode = &inXMLDoc.DocumentElement.AddElement("first");
&elementNode = &inXMLDoc.DocumentElement.AddElement("second");
&elementNode = &inXMLDoc.DocumentElement.AddElement("third");

&inXMLDoc.DocumentElement.RemoveAllChildNode();
```

This is the XML document before the removal:

```
<?xml version="1.0"?>
<root>
  <first/>
  <second/>
  <third/>
</root>
```

This is the XML document after the removal:

```
<?xml version="1.0"?>
<root/>
```

Related Links

AddNode

InsertNode

GetChildNode

FindNode

FindNodes

RemoveChildNode

RemoveChildNode

Syntax

RemoveChildNode({*Position* | *Node*})

Description

Use the RemoveChildNode method to remove the child node in an XmlNode specified by *Node*, or located at *Position*.

Parameters

Position* | *Node	Specify the child node that you want to delete, either using its position number or its name.

Returns

A reference to the removed XmlNode.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Example

The following PeopleCode program uses a position:

```
Local XmlDoc &inXMLDoc;
Local XmlNode &elementNode, &removedNode;

&inXMLDoc = CreateXmlDoc("<?xml version='1.0'?><root/>");
&elementNode = &inXMLDoc.DocumentElement.AddElement("first");
&elementNode = &inXMLDoc.DocumentElement.AddElement("second");
&elementNode = &inXMLDoc.DocumentElement.AddElement("third");

&removedNode = &inXMLDoc.DocumentElement.RemoveChildNode(2);
```

The following PeopleCode program uses a reference node:

```
Local XmlDoc &inXMLDoc;
Local XmlNode &elementNode, &removedNode;

&inXMLDoc = CreateXmlDoc("<?xml version='1.0'?><root/>");
&elementNode = &inXMLDoc.DocumentElement.AddElement("first");
&elementNode = &inXMLDoc.DocumentElement.AddElement("second");
&elementNode = &inXMLDoc.DocumentElement.AddElement("third");

&elementNode = &inXMLDoc.DocumentElement.FindNode("/second");
&removedNode = &inXMLDoc.DocumentElement.RemoveChildNode(&elementNode);
```

This is the XML document before the removal:

```
<?xml version="1.0"?>
<root>
  <first/>
  <second/>
  <third/>
</root>
```

This is XML document after the removal:

```
<?xml version="1.0"?>
<root>
  <first/>
  <third/>
</root>
```

Related Links

AddNode

InsertNode

GetChildNode

FindNode

FindNodes

RemoveAllChildNode

XmlNode Class Properties

The following are the XmlNode properties.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

AttributesCount

Description

This property returns the number of attributes for an XmlNode, as a number.

This property is read-only.

Example

```
Local XmlDoc &inXMLDoc;

&inXMLDoc = CreateXmlDoc("<?xml version='1.0'?><root/>");
&inXMLDoc.DocumentElement.AddAttribute("first", "John");
&inXMLDoc.DocumentElement.AddAttribute("last", "Public");
&inXMLDoc.DocumentElement.AddAttribute("address", "1234 West Eastland");

For &i = 1 To &inXMLDoc.DocumentElement.AttributesCount
   /* do some processing of the attributes here */
End-For;
```

ChildNodeCount

Description

This property returns the number of child nodes for an XmlNode, as a number.

This property is read-only.

Index

Description

This property returns the location (or position) of a node in the parent's child list, as a number. The root node always returns a 1.

This property is read-only.

IsNull

Description

This property returns a Boolean value, indicating whether the node is a valid node. Use this property to verify the value of the add or insert XmlNode methods.

This property is read-only.

Example

```
Local XmlDoc &inXMLDoc;
Local XmlNode &elementNode;

&inXMLDoc = CreateXmlDoc("<?xml version='1.0'?><root/>");
&elementNode = &inXMLDoc.DocumentElement.AddElement("first");

&elementNode = &inXMLDoc.DocumentElement.FindNode("/second");
```

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

```
If &elementNode.IsNull Then
   /* do some error processing here, will not find "second" */
End-If;
```

LocalName

Description

This property returns the local part of a namespace as a string. The local part is the second part of the namespace entry. If you want access to the first part of a namespace, use the Prefix property.

This property is read-only.

Related Links

Prefix

NamespaceURI

Description

This property returns a reference to the namespace URI as a string.

This property is read-only.

NextSibling

Description

This property returns the next child node in an XmlNode, as an XmlNode.

Use the IsNull property to verify that the XmlNode that is returned is valid.

This property is read-only.

Related Links

IsNull

NodeName

Description

This property returns the name of the XmlNode as a string. You can use this property to rename an XmlNode.

This property is read-write.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

NodePath

Description

This property returns the path of the XmlNode, from the root.

This property is read-only.

NodeType

Description

This property returns the type of the XmlNode. You can use either a numeric value or a constant. The values are:

Numeric Value	*Constant Value*	*Description*
1	%ElementNode	Element node
2	%AttributeNode	Attribute node
3	%TextNode	Text node
4	%CDataSectionNode	CData section node
5	%EntityReferenceNode	Entity reference node
6	%EntityNode	Entity node
7	%ProcessingInstructionNode	Processing instruction node
8	%CommentNode	Comment node
9	%DocumentNode	Document node
10	%DocumentTypeNode	Document type node
11	%NotationNode	Notation node
12	%XmlDeclNode	XML DECL node

NodeValue

Description

This property returns the value of the XmlNode, as a string.

This property is read-write.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ParentNode

Description

This property returns a reference to the parent node for the XmlNode, as an XmlNode object.

Use the IsNull property to verify that the XmlNode that is returned is valid.

This property is read-only.

Related Links

IsNull

Prefix

Description

This property returns the prefix part of a namespace as a string. The prefix is the first part of the namespace entry. If you want access to the second part of a namespace, use the LocalName property.

This property is read-only.

Related Links

LocalName

PreviousSibling

Description

This property returns a reference to the previous node in the XmlNode, as an XmlNode object.

Use the IsNull property to verify that the XmlNode that is returned is valid.

This property is read-only.

Related Links

IsNull

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Appendix A

Quick Reference for PeopleCode Classes

PeopleCode Syntax Quick Reference

Typographical Conventions

The following topic describes typographical conventions that apply to PeopleCode and are used throughout PeopleSoft documentation:Typographical Conventions

PeopleCode Syntax

The following table describes the complete syntax for the PeopleCode language:

Term	*Syntax*
Program	ImportList (DeclList TopStList | ClassDefn)
ImportList	[ImportDecl **';'**]...
ImportDecl	**'import'** PackageName [**':'** **'*'**]
PackageName	Id [**':'** Id]...
ClassDefn	ClassDecl [**';'** ExtDecls] [**';'** MethodDefns]
ClassDecl	**'class'**| **'interface'**' Id [Extends] [ClassPublics] [ClassProtecteds] [ClassPrivates] **'end-class'** | **'end-interface'**
Extends	**'extends'** | **'implements'** QualifiedId
QualifiedId	[PackageName **':'**] Id
ClassPublics	ClassPublic [**';'** ClassPublic]...
ClassPublic	MethodDecl | PropertyDecl
MethodDecl	**'method'** Id **'('** [MethodParameters] **')'** [**'abstract'**] [**'returns'** PeopleCodeType]
MethodParameters	MethodParameter [**','** MethodParameter]...
MethodParameter	**'&'** Id **'as'** PeopleCodeType [**'out'**]

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Term	*Syntax*
PropertyDecl	**'property'** PeopleCodeType Id [(**'get'** [**'set'**] | **'abstract'**) | **'readonly'**]
ClassPrivates	**'private'** [ClassPrivate [**';'** ClassPrivate]...]
ClassPrivate	MethodDecl | InstanceDecl | ConstantDecl
ClassProtecteds	**'protected'** [ClassProtected [**';'** ClassProtected]...]
ClassProtected	MethodDecl | InstanceDecl | ConstantDecl
InstanceDecl	**'instance'** VarDeclare
ExtDecls	ExtDecl [**';'** ExtDecl]...
MethodDefns	MethodDefn [**';'** MethodDefn]...
MethodDefn	MethodMethod | GetMethod | SetMethod
MethodMethod	**'method'** Id StList **'end-method'**
GetMethod	**'get'** Id StList **'end-get'**
SetMethod	**'set'** Id StList **'end-set'**
TopStList	TopStmt [**';'** TopStmt]...
TopStmt	Stmt
StList	Stmt [**';'** Stmt]...
Stme	[LValue [Assign] | If | Evaluate | While | Repeat | For | Accept | Break | Return | Exit | Error | Warning | Try | Throw | LocalDecl]
Assign	**'='** Expression
If	**'if'** LogicalExpression **'then'** StList [**'else'** StList] **'end-if'**
Evaluate	**'evaluate'** Expression [WhenExpr... StList]... [**'when-other'** StList] **'end-evaluate'**
WhenExpr	**'when'** [RelOp] Expression
While	**'while'** LogicalExpression StList **'end-while'**
Repeat	**'repeat'** StList **'until'** LogicalExpression

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Term	***Syntax***
For	**'for'** Variable **'='** Expression **'to'** Expression [**'step'** Expression] StList **'end-for'**
Accept	**'accept'**
Return	**'return'** [Expression]
Break	**'break'**
Exit	**'exit'** [Expression]
Warning	**'warning'** Expression
Error	**'error'** Expression
Try	**'try'** StList (**'catch'** QualifiedId **'&'** Id StList)... **'end-try'**
Throw	**'throw'** Expresssion
LocalDecl	**'local'** PeopleCodeType **'&'** Id [(**','** **'&'** Id)... | **'='** Expression]
Continue	**'Continue'**
LogicalExpression	LogicalTerm [**'or'** LogicalTerm]...
LogicalTerm	Relation [**'and'** Relation]...
Relation	**'not'** Relation | Expression [Relop Expression]
Relop	**'not'** Relop | **'<'** | **'<='** | **'='** | **'>='** | **'>'** | **'!='** | **'<>'**
Expression	Term [(**'+'** | **'-'** | **'|'**) Term]...
Term	Power [(**'*'** | **'/'**) Power]...
Power	Primary [**'**'** Primary]...
Primary	LValue [**'as'** QualifiedId] | Number | String | **'true'** | **'false'** | **'null'** | **'-'** Primary | **'create'** QualifiedId Call
LValue	LValueStart [LValueObject | LValueSubscript]...
LValueStart	Variable | Id Call | **'@'** Primary | **'%'** BuiltinVar | **'('** LogicalExpression **')'**
LValueObject	**'.'** Id [Call] | Call

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Term	*Syntax*
LValueSubscript	**'['** Expression [**','** Expression]... **']'**
Variable	**'&'** Id | Id [**'.'** (Id | String)] | **'^'**
Call	**'('** [Expression [**','** Expression]...] **')'**
Constant	Number | String | **'true'** | **'false'** | **'null'** | QualifiedId **':'** Id
DecList	[Decl **';'**]...
Decl	**'local'** VarDeclare | **'function'** Function | ConstDecl | ExtDecl
VarDeclare	PeopleCodeType **'&'** Id [**','** **'&'** Id]...
Function	Id [**'('** InternalParameters **')'**] [**'returns'** PeopleCodeType] [**'noexport'**] [**'doc'** String] TopStList **'end-function'**
InternalParameters	[InternalParameter [**','** InternalParameter]...]
InternalParameter	**'&'** Id [**'as'** PeopleCodeType]
ConstDecl	**'constant'** **'&'** Id **'='** (Number | String | **'true'** | **'false'** | **'null'**)
ExtDecl	**'global'** VarDeclare | **'component'** VarDeclare | **'declare'** Declare
Declare	**'function'** Id (**'library'** DeclareLibrary | **'peoplecode'** DeclarePC)
DeclareLibrary	String [**'alias'** String] [**'('** ExternalParameters **')'**] [**'returns'** ExternalType [**'as'** PeopleCodeType]]
ExternalParameters	[ExternalParameter [**','** ExternalParameter]...]
ExternalParameter	ExternalType [**'value'** | **'ref'**] [**'as'** PeopleCodeType]
DeclarePC	Variable EventType
PeopleCode Type	[**'array'** **'of'**]... (**'number'** | **'string'** | **'date'** | **'time'** | **'datetime'** | **'any'** | **'boolean'** | **'object'** | **'array'** | **'integer'** | **'float'** | QualifiedId)
ExternalType	**'boolean'** | **'integer'** | **'long'** | **'uinteger'** | **'ulong'** | **'string'** | **'lstring'** | **'ustring'** | **'float'** | **'double'**

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

PeopleCode Classes Alphabetical Reference

This section provides an overview of typographical conventions and visual cues and lists the PeopleCode classes in alphabetical order, along with the functions, methods and properties associated with that class.

Typographical Conventions and Visual Cues

This table describes the typographical conventions and visual cues that are used in this quick reference:

Typographical Convention or Visual Cue	*Description*
D	Identifies the default method for a class.
RO	Identifies a read-only property. Properties that aren't identified as read-only are read-write.

In addition, the usual PeopleCode typographical conventions are used to distinguish between different elements of the PeopleCode language, such as **keyword** to indicate keywords or syntax that must be entered exactly as shown, *variable* for arguments, parameters, and so on.

Related Links

PeopleCode Syntax Quick Reference

Activity Guide Classes

This section lists the methods and properties, as well as returns (if applicable) for the activity guide classes.

ActionItem Methods

Method	*Returns*
delete()	None
new(*item_ID*, *title*, *list_ID*)	None
nextAction()	ActionItem object
open(*item_ID*)	None
prevAction()	ActionItem object
save()	None

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ActionItem Properties

Property	*Returns*
AppClassID	String
AssignedToOprid	String
AssignType	String
CurrentStep	Boolean
DescrLong	String
DueDate	Date
DueTm	Time
Field1	String
Field10	String
Field2	String
Field3	String
Field4	String
Field5	String
Field6	String
Field7	String
Field8	String
Field9	String
ItemId	String [RO]
Label	String
ListId	String
PackageRoot	String
ParentId	String
PercCompl	Number
Priority	String

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
QualifyPath	String
Remarks	String
Required	Boolean
Sequence	Number
ServiceId	String
StartDt	Date
StartTm	Time
Status	String
Summary	Boolean
Type	String

ContextData Methods

Method	***Returns***
ContextData(*rec_name*, *field_name*, *label*, *value*, *isKey*, *isVisible*)	None
IsEqual(*&object*)	Boolean

ContextData Properties

Property	***Returns***
ctxKey	Boolean
ctxVisible	Boolean
fieldname	String
keyLabel	String
keyValue	String
recname	String

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

List Methods

Method	***Returns***
createInstance(*instance_ID*, *title*, *&context_data*)	List object
getActionItems()	Array of string
GetContext()	PTAI_COLLECTION:Collection object
getMembers()	PTAI_COLLECTION:Collection object
GetPgltBtn()	PTAI_COLLECTION:Collection object
getRootItems()	Array of string
new(*ID*, *portal*, *title*)	None
open(*ID*)	None
save()	None
SaveContext(*&context_data*)	None
saveMembers(*&members*)	None
SavePgltBtn(*&pgltBtns*)	PTAI_COLLECTION:Collection object

List Properties

Property	***Returns***
AppClassID	String
AppClassMethod	String
DescrLong	String
Field1	String
Field10	String
Field2	String
Field3	String
Field4	String
Field5	String

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
Field6	String
Field7	String
Field8	String
Field9	String
HomeUrl	String
isActive	Boolean
IsTemplate	Boolean
Label	String
ListId	String RO
PackageRoot	String
ParentTemplate	String
pgltAppClass	String
pgltPackageRoot	String
pgltProgressBarVisible	Boolean
pgltQualifyPath	String
QualifyPath	String
Status	String

Member Methods

Method	***Returns***
IsEqual(*&object*)	Boolean
Member(*name*, *type*)	None

Member Properties

Property	***Returns***
Name	String RO

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
PrivilegeSetID	String
Type	String RO

AESection Class

This section lists the functions, methods, and properties, as well as returns (if applicable) for the AESection class.

Function

Function	***Returns***
GetAESection(*applid*, *ae_section* [, *effdt*])	AESection object

Methods

Method	***Returns***
AddStep(*ae_step_name* [,*NewStepName*])	None
Close()	None
Open(*ae_applid*, *ae_section*, [*effdt*])	AESection object
Save()	None
SetSQL(*action_type_string*, *string*)	None
SetTemplate(*ae_applid*, *ae_section*)	None

Property

Property	***Returns***
IsOpen	Boolean RO

Analytic Calculation Engine Classes

This section lists the functions, methods, and properties, as well as returns (if applicable) for the Analytic Calculation Engine Classes.

Important! The Analytic Calculation Engine classes are not supported on IBM z/OS and Linux for IBM System z.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Functions

Function	***Returns***
CreateAnalyticInstance(*AnalyticType*, *AIID*, *Descr*, *AppClassName*, *MethodName*, *&RecordRef*, *Force*)	AnalyticInstance object
GetAnalyticInstance(*AIID*)	AnalyticInstance object

AnalyticInstance Methods

Method	***Returns***
CheckAsyncStatus()	Number
CheckStatus()	Constant
Copy(*NewAIID*, *ForceDelete*, *&Record*)	None
Delete(*ForceUnload*, *&RecordRef*)	None
GetAnalyticModel((**Model.** *ModelName*)	AnalyticModel object
GetTraceLevel()	Integer
Load((**Message.** *MessageName*), *Sync*, *IdleTimeOut*)	String
RunAsync()	None
RunSync()	None
SetTraceLevel(*TraceLevel*)	Number
Terminate()	None.
Unload()	None

AnalyticInstance Properties

Property	***Returns***
AnalyticType	String[RO]
ID	Integer[RO]
Messages	Multi-dimensional array of any[RO]

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

AnalyticModel Methods

Method	***Returns***
AddMember(*DimName*, *MemberName*)	None
AttachTree(*DimName*, *TreeName*, *SetId*, *UserKeyValue*, *EffDt*, *NodeName*, *OverrideRecord*, *DetailStartLvl*, *TreeDiscardLvl*)	None
CalculateCube(*CubeName*, *Sync*)	None
DetachTree(*DimName*)	None
GetCubeCollection(*CubeCollName*)	CubeCollection object
GetCellProperties(*CubeName*, *&Node*)	Array of string
GetMembers(*DimName*, *DimFilter*)	Two-dimensional array
GetTree(*DimName*)	Array of string
Recalculate(*Sync*)	String
RenameMember(*DimName*, *OrigMemberName*, *NewMemberName*)	None

AnalyticModel Property

Property	***Returns***
Messages	Multi-dimensional array of any[RO]

CubeCollection Methods

Method	***Returns***
CollapseNode(*DimName*, *&Node*)	None
DrillIntoNode(*DimName*, *&Node*)	None
DrillOutOfNode(*DimName*, *&Node*)	None
ExpandNode(*DimName*, *&Node*, *ExpandAll*)	None
GetData(*&DataRowset*, *StartRow*, *EndRow*[, *NetChanges*])	None
GetDimFilter(*DimName*)	String
GetDimSort(*DimName*)	Array

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Method	***Returns***
GetLayout(*&SlicerArray*, *&RowAxisArray*, *&ColumnAxisArray*)	None
GetRowCount()	Integer
GetSlice(*&SliceRecord*)	None
SetData(*&DataRowset)*	None
SetDimensionOrder(*&FieldNames*)	None
SetDimFilter(*DimName*, *DimFilter*)	None
SetDimSort(*DimName*, *IsAscending*[, *Key1*, *IsAscending2*, *Key2*, *IsAscending3*, *Key3*])	None
SetLayout(*&SlicerArray*, *&RowAxisArray*, *&ColumnAxisArray*	None
SetSlice(*&SliceRecord*)	None
ShowHierarchy(*DimName*, *Show*)	None
UnsetDimFilter(*DimName*)	None
UnsetDimSort(*DimName*)	None

CubeCollection Property

Property	***Returns***
Messages	Multi-dimensional array of any[RO]

Analytic Calculation Engine Metadata Classes

This section lists the methods and properties, as well as returns (if applicable) for the Analytic Calculation Engine metadata classes.

Important! The Analytic Calculation Engine Metadata classes are not supported on IBM z/OS and Linux for IBM System z.

AnalyticModelDefn Methods

Method	***Returns***
AddCube(*CubeName*)	CubeDefn object

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Method	***Returns***
AddCubeCollection(*CubeCollectionName*)	CubeCollectionDefn object
AddDimension(*DimName*)	DimensionDefn object
AddExplicitDimensionSet (*ExplicitDimSetName*)	ExplicitDimensionSet object
AddOrganizer(*OrganizerName*)	OrganizerDefn object
AddUserFunction(*UserFunctionName*)	UserFunction object
CopyCube(*CubeName*, *NewCubeName*)	CubeDefn object
CopyCubeCollection(*CubeCollectionName*, *NewCubeCollectionName*)	CubeCollectionDefn object
CopyDimension(*DimName*, *NewDimName*)	DimensionDefn object
CopyExplicitDimensionSet(*OldExplicitDimSetName*, *NewExplicitDimSetName*)	ExplicitDimensionSet object
CopyTo(*NewModelName*)	AnalyticModelDefn object
CopyUserFunction(*UserFunctionName*, *NewUserFunctionName*)	UserFunctionDefn object
Create()	None
Delete()	None
DeleteCube(*CubeName*, *ForceDelete*)	None
DeleteCubeCollection(*CubeCollectionName*, *ForceDelete*)	None
DeleteOrganizer(*OrganizerName*)	None
DeleteDimension(*DimensionName*)	None
DeleteExplicitDimensionSet(*ExplicitDimensionSetName*)	None
DeleteUserFunction(*UserFunctionName*, *ForceDelete*)	None
Get()	None
GetCube(*CubeName*)	CubeDefn object
GetCubeCollection(*CubeCollection*)	CubeCollectionDefn object
GetCubeCollectionNames()	Array of string

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Method	***Returns***
GetCubeNames()	Array of string
GetDimension(*DimName*)	DimensionDefn object
GetDimenstionNames()	Array of string
GetExplicitDimensionSet	ExplicitDimensionSet object
GetExplicitDimensionSetNames	Array of strings
GetOrganizer(*OrganizerName*)	OrganizerDefn object
GetOrganizerNames()	Array of string
GetUserFunction(*UserFunctionNames*)	UserFunctionDefn object
GetUserFunctionNames()	Array of string
Rename(*NewModelName*)	None
RenameCube(*CubeName*, *NewCubeName*, *ForceRename*)	None
RenameCubeCollection(*CubeCollectionName*, *NewCubeCollectionName*, *ForceRename*)	None
RenameDimension(*DimensionName*, *NewDimName*, *ForceRename*)	None
RenameExplicitDimensionSet(*ExplicitDimSetName*, *NewExplicitDimSetName*, *ForceRename*)	None
RenameOrganizer(*OrganizerName*, *NewOrganizerName*, *ForceRename*)	None
RenameUserFunction(*UserFunctionName*, *NewUserFunctionName*, *ForceRename*)	None
Save()	None
Validate()	Boolean

AnalyticModelDefn Properties

Property	***Returns***
CircularFomulaWarn	Boolean

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
Description	String
IsValid	Boolean[RO]
LongDescription	String
MaxDelta	Integer
MaxIterations	Integer
Messages	Multi-dimensional array of any[RO]
Name	String[RO]
ResolveCircularDeps	Boolean

DimensionDefn Properties

Property	***Returns***
AggregateSequence	Number[RO]
AggregationUserFunction	String
Comments	String
Name	String[RO]
TotalMemberName	String

ExplicitDimensionSet Methods

Method	***Returns***
AttachDimension(*DimName*)	None.
DetachDimension(*DimName*)	None.
GetDimensionName()	Array of string.

ExplicitDimensionSet Properties

Property	***Returns***
Name	String [RO]

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
SequenceNumber	Number [RO]

CubeDefn Methods

Method	***Returns***
AttachDimension(*DimName*)	None
DetachDimension(*DimName*)	None
GetCauses(*CauseType*)	Array of string
GetCircularDeps(*DimName*)	Array of string
GetDimensionAggregate(*DimName*)	String
GetEffects(*EffectType*)	Array of string
GetDimensionNames()	Array of string
GetRule(*DimensionName*)	RuleDefn object
SetDimensionAggregate(*DimName*, *UserFunctionName*)	None
SetRule(*&RuleDefn*)	None
UsesDimension(*DimName*)	Boolean

CubeDefn Properties

Property	***Returns***
CalcAggregates	Boolean
Comments	String
DimensionCount	Number[RO]
FormatType	Varies
IsVirtual	Boolean
Name	String[RO]
Rule	String
ValueDimensionName	String

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

CubeCollectionDefn Methods

Method	***Returns***
AttachCube(*CubeName*)	None
DetachCube(*CubeName*)	None
GetAggregateMapping(*PartName*, *IsCube*)	String
GetCubeNames()	Array of string
GetDimensionNames()	Array of string
GetDimSort(*DimensionName*)	Array of string
GetFieldMapping(*PartName*, *IsCube*)	String
GetFilter(*DimensionName*)	String
GetPersistAggregate(*DimensionName*)	String
SetAggregateMapping(*PartName*, *IsCube*, *AggregateFieldName*)	String
SetDimSort(*DimName*, *IsAscending*[,*CubeName1*, *IsAscending2*, *CubeName2*, *IsAscending3*, *CubeName3*])	None
SetFieldMapping(*PartName*, *IsCube*, *FieldName*)	None
SetFilter(*DimensionName*, *FilterName*)	None
SetPersistAggregate(*DimensionName*, *AggregateType*)	None
UsesCube(*CubeName*)	Boolean
UsesDimension(*DimensionName)*	Boolean

CubeCollectionDefn Properties

Property	***Returns***
AggregateRecName	String
Comments	Number[RO]
CubeCount	Number[RO]
DimensionCount	Number[RO]

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
Name	String[RO]
RecordName	String

UserFunctionDefn Properties

Property	***Returns***
Comments	String
Name	String[RO]

UserFunctionDefn Methods

Method	***Returns***
GetRule( )	RuleDefn object
SetRule(*&Rule*)	None

OrganizerDefn Methods

Method	***Returns***
AttachPart(*PartName*, *PartType*)	None
DetachPart(*PartName*, *PartType*	None
GetPartNames()	Array of string
UsesPart(*PartName*, *PartType*)	Boolean

OrganizerDefn Properties

Property	***Returns***
Comments	String
Name	String[RO]

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

RuleDefn Methods

Method	***Returns***
AddRuleExpression(*&Expr*)	None
GenerateRule ( )	None

RuleDefn Property

Property	***Returns***
RuleString	String[RO]

Assignment Method

Method	***Returns***
GenerateRule()	String

Assignment Properties

Property	***Returns***
Expression	Depends on value
Variable	String

Comparison Method

Method	***Returns***
GenerateRule ()	String

Comparison Properties

Property	***Returns***
Operand1	RuleExpression object
Operand2	RuleExpression object
Type	String [RO]

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Constant Method

Method	***Returns***
GenerateRule()	String

Constant Properties

Property	***Returns***
Type	String RO
Value	String RO

Cube Methods

Method	***Returns***
AddIndex(*&MemberReference*)	None
GenerateRule()	String
GetIndexes()	Array of MemberReference objects

Cube Property

Property	***Returns***
Name	String RO

ExpressionBlock Methods

Method	***Returns***
AddRuleExpression(*&Expr*)	None.
GetRuleExpressions()	Array of rule expression objects.

FunctionCall Methods

Method	***Returns***
AddArgument(*&RuleExpression*)	None
GenerateRule()	String
GetArguments()	Array of RuleExpression objects

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

FunctionCall Properties

Property	*Returns*
Name	String RO
Type	String

MemberReference Method

Method	*Returns*
GenerateRule()	String

MemberReference Properties

Property	*Returns*
Dimension	String RO
Member	String RO

Operation Method

Method	*Returns*
GenerateRule()	String

Operation Properties

Property	*Returns*
Operand1	RuleExpression object
Operand2	RuleExpression object
Type	String

Variable Method

Method	*Returns*
GenerateRule()	String

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Variable Properties

Property	*Returns*
Name	String RO
Type	String RO

Analytic Grid Classes

This section lists the functions, methods, and properties, as well as returns (if applicable) for the analytic grid classes.

Important! The analytic grid classes are not supported on IBM z/OS and Linux for IBM System z.

AnalyticGrid Function

Function	*Returns*
GetAnalyticGrid(**PAGE**.*pagename*, *gridname*)	AnalyticGrid object

AnalyticGrid Methods

Method	*Returns*
GetColumn(*ColumnName*)	GridColumn object
GetCubeCollection()	CubeCollection object
LoadData()	None
SetAnalyticInstance(*AIID*)	None
SetLayout(*&SlicerArray*, *&RowAxisArray*, *&ColumnAxisArray*)	None.

AnalyticGrid Properties

Property	*Returns*
InActive	Boolean
Label	String
ShowGridLines	Boolean
SlicerVisible	Boolean

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	*Returns*
SummaryText	String

Analytic Type Classes

This section lists the methods and properties as well as returns for analytic type classes.

Important! The analytic type classes are not supported on IBM z/OS and Linux for IBM System z.

AnalyticTypeDefn Methods

Method	*Returns*
AddModel(*ModelName*, *ModelType*	AnalyticTypeModelDefn object
AddRecord(*RecordName*)	AnalyticTypeRecordDefn object
Create()	
Copy(*NewAnalyticTypeName*, *ForceCopy*)	AnalyticTyepDefn object
Delete()	
DeleteModel(*ModelName*)	None
DeleteRecord(*RecordName*)	None
Get()	None
GetModels()	Array
GetRecordNames()	Array of string
Rename(*NewAnalyticTypeName*)	None
Save()	None

AnalyticTypeDefn Properties

Property	*Returns*
Comments	String
Description	String
Name	String[RO]

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	*Returns*
AppClassPath	String
OwnerID	String [RO]

AnalyticTypeModelDefn Properties

Property	*Returns*
Name	String[RO]
Type	String[RO]

AnalyticTypeRecordDefn Methods

Method	*Returns*
GetSelectedFields()	Array of string
SetSelectedFields(*SelectedFieldsArray*)	None
UnsetSelectedFields(*FieldName*)	None

AnalyticTypeRecordDefn Properties

Property	*Returns*
Callback	Boolean
Description	String
Name	String[RO]
Readable	Boolean
ReadOnce	Boolean
ScenarioManaged	Boolean
SyncOrder	Integer[RO]
Writeable	Boolean

Application Classes

This section lists the functions, as well as returns (if applicable) for the application classes.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Functions

Function	*Returns*
Class *classname* [{**Extends** | **Implements**}*Classname*] [Method_declarations] [Property_declarations] [**Protected** [Method_declarations] [Instance_declarations] [Constant_declaration]] [**Private** [Method_declarations] [Instance_declarations] [Constant_declaration]] **End-Class**	None
Get *PropertyName* *StatementList* **End-Get**	Depends on assignment of *StatementList*
Import *PackageName*:[*PackageName*. . .:]{*Classname* | *}	None
Interface *classname* [{**Extends** | **Implements**}*Classname*] [Method_declarations] [Property_declarations] [**Protected** [Method_declarations] [Instance_declarations] [Constant_declaration]] **End-Interface**	None.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Function	*Returns*
Method *MethodName* *StatementList* **End-Method**	Depends on method
Set *PropertyName* *StatementList* **End-Set**	None

Application Data Set Classes

This section lists the methods and returns (if applicable) for the Application Data Set classes.

AdsValidationBase Methods

Method	*Returns*
AdsValidationBase(*project_name*)	None
DoADSValidations(*&ADS_rowset*, *ADS_name*)	Boolean
OnPreCopyCompare(*&ADS_rowset*, *ADS_name*)	Boolean
OnPreUpdate(*&ADS_rowset*, *ADS_name*)	Boolean
OnPostCopy(*&ADS_rowset*, *&content_list*)	Boolean
ReportErrorModified(*&recReportKey*, *&recReportError*)	None

Array Class

This section lists the functions, methods, and properties, as well as returns (if applicable) for the Array class.

Functions

Function	*Returns*
CreateArray(*paramlist*)	Array object
CreateArrayAny([*paramlist*])	Array object
CreateArrayRept(*val*, *count*)	Array object

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Function	***Returns***
Split(*string*, *separator*)	Array object

Methods

Method	***Returns***
Clone()	Array object
Find(*value*)	Index of an element
Get(*index*)	Element of array
Join([*separator* [, *arraystart, arrayend* [, *stringsizehint*]]])	String
Next(*&index*)	Boolean
Pop()	Value of last array element
Push(*paramlist*)	None
Replace(*start*, *length*, [*paramlist*])	None
Reverse()	None
Set(*index*)	None
Shift()	Value of first array element
Sort([*order*])	None
Subarray(*start*, *length*)	Array object
Substitute(*old_val*, *new_val*)	None
Unshift(*paramlist*)	None

Properties

Property	***Returns***
Dimension	Number [RO]
Len	Number

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

BI Publisher Classes

This section lists the constructors, methods, and properties, as well as returns (if applicable) for the BI Publisher (formerly XML Publisher) classes.

- Report manager definition classes
- Report manager search classes
- BI Publisher engine classes

Report Definition Manager Classes Constructors

Constructor	***Returns***
ReportDefn(*ReportId*)	ReportDefn object

ReportDefn Class Methods

Method	***Returns***
Close()	None
DisplayOutput()	None
Get()	ReportDefn object
GetOutDestFormatString(*OutDestFormat*)	String
GetPSQueryPromptRecord()	Record object
PrintOutput(*DestPrinter*)	None
ProcessReport(*TemplateId*, *LanguageCD*, *AsOfDate*, *OutputFormat*)	None
Publish(*ServerName*, *ReportPath*, *FolderName*, *ProcessInstanceId*)	None
SetPSQueryPromptRecord(*&Record*)	None
SetRuntimeDataXMLFile(*FilePath*)	None
SetRuntimeProperties(*&NameArray*, *&ValueArray*)	None

ReportDefn Class Properties

Property	***Returns***
Description	String [RO]

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
DestinationPrinter	String
FolderName	String
OutDestination	String [WO]
OutDestinationType	String [RO]
ProcessInstance	String
ReportFileName	String
Status	String[RO]
UseBurstValueAsOutputFileName	Boolean

Report Manager Search Classes Constructors

Constructor	***Returns***
Report(*RptId*, *Prcsinstance*, *Contentid*, *Dbname*, *RptName*, *RptDescr*, *RptURL*, *RptCreateDttm*, *RptExpireDt*, *FldrName*)	Report object
ReportManager()	ReportManager object
SearchAttribute(*AttrName*, *AttrValue*, *CompareOperator*)	SearchAttribute object

Report Class Properties

Property	***Returns***
contentId	Number[RO]
CreatedDateTime	DateTime[RO]
DatabaseName	String[RO]
Description	String[RO]
ExpireDate	Date[RO]
FileURL	String[RO]
FolderName	String[RO]
ProcessInstanceID	String[RO]

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
ReportInstanceID	String[RO]
ReportName	String[RO]
ReportURL	String[RO]

ReportManager Class Methods

Method	***Returns***
AddSearchFieldCriteria(*&SearchAttribute*)	Boolean
GetReportList()	Array of Report objects
SetBurstFieldCriteria(*BurstFld*, *BurstOp*, *BurstValue*)	Boolean
SetCaseSensitive(*IsCaseSensitive*)	None
SetDateCriteria(*createdDate*, *createdLastVal*, *createdUnit*)	None
SetFolderCriteria(*FolderName*)	Boolean
SetProcessInstanceCriteria(*FromPID*, *ToPID*)	Boolean
SetReportIDCriteria(*ReportId*)	Boolean
SetUserIdCriteria(*UserId*)	Boolean

SearchAttribute Class Properties

Property	***Returns***
attrName	String[RO]
attrValue	String[RO]
compareOp	String[RO]

BI Publisher Engine Classes Constructors

Constructor	***Returns***
PageNumber()	PageNumber object
PDFMerger()	PDFMerger object

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Constructor	***Returns***
Properties()	Properties object
Watermark()	Watermark object

PageNumber Class Properties

Property	***Returns***
BackgroundFile	String
FontName	String
FontSize	Number
PositionX	Number
PositionY	Number
StartFromPageNum	Number
StartNum	Number

PDFMerger Class Method

Method	***Returns***
MergePDFs(*PDFFileArray*, *PDFOutputFile*, *Error*)	Boolean

PDFMerger Class Properties

Property	***Returns***
ConfProp	Properties object
Locale	Sting
PageNumber	PageNumber object
Watermark	Watermark object

Properties Class Methods

Method	***Returns***
GetProperty(*Name*, *OutValue*)	Boolean

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Method	***Returns***
SetProperty(*Name*, *Value*)	Boolean

Watermark Class Properties

Property	***Returns***
ImageFile	String
ImageFileLowerLeftX	Number
ImageFileLowerLeftY	Number
ImageFileUpperRightX	Number
ImageFileUpperRightY	Number
PageIndex	Number
Text	String
TextAngle	Number
TextFontName	String
TextFontSize	Number
TextStartPosX	Number
TextStartPosY	Number

BPEL Classes

This section lists the constructors, methods, and properties, as well as returns (if applicable) for the BPEL classes AsyncFFSend, BPELUtil, and IBUtil.

Constructors

Constructor	***Returns***
AsyncFFSend()	AsyncFFSend object
BPELUtil()	BPELUtil object
IBUtil()	IBUtil object

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

AsyncFFSend Method

Method	*Returns*
OnRequestSend(*&Msg*)	Message object

BPELUtil Methods

Method	*Returns*
GetASyncBPELProcessInstanceURL(*TransactionID*)	String
GetBPELProcessBrowserURL(*NodeName*)	String
GetOperationType(*OperationName*)	String
GetSyncBPELProcessURL(*NodeName*, *MessageID*)	String
LaunchASyncBPELProcess(*OperationName*, *&Msg*, *Username*, *Password*)	String
LaunchSyncBPELProcess(*OperationName*, *&Msg*, *Username*, *Password*)	Message object
UpdateConnectorResponseProperties(*&Msg*)	None

IBUtil Methods

Method	*Returns*
GetBPELConsoleURL(*NodeName*)	String
GetBPELDomain(*NodeName*)	String
GetMessageId(*TransactionID*)	String
GetNode(*MessageID*)	String
GetNumberOfRoutings(*ServiceOperationName*)	Number
GetStatus(*TransactionID*)	String
GetTransactionId(*MessageId*)	String

Charting Classes

This section lists the functions, methods, and properties, as well as returns (if applicable) for the charting classes.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Charting Classes Functions

Function	***Returns***
CreateObject("**Chart**")	Chart object
CreateObject("**QuadrantSchema**")	QuadrantSchema object
GetChart(*RecordName.FieldName*)	Chart object
GetChartURL(*&Chart*)	String
GetDialGauge(*RecordName.FieldName*)	DialGauge object
GetGanttChart(*RecordName.FieldName*)	Gantt object
GetLEDGauge(*RecordName.FieldName*)	LEDGauge object
GetOrgChart(*RecordName.FieldName*)	OrgChart object
GetRatingBoxChart(*RecordName.FieldName*)	RatingBoxChart object
GetReferenceArea()	ReferenceArea object
GetReferenceLine()	ReferenceLine object
GetStatusMeterGauge(*RecordName.FieldName*)	StatusMeterGauge object
GetThreshold()	Threshold object

Chart Class Methods

Method	***Returns***
Reset()	None
SetColorArray(*&Array_of_Color*)	None
SetData({*Record_Name* | *&Rowset*})	None
SetDataAnnotations(*Recordname.FieldName*)	None
SetDataColor(*Record_Name.Field_Name*)	None
SetDataGlyphScale(*Recordname.FieldName*)	None
SetDataHints(*Record_Name.Field_Name*)	None
SetDataSeries(*Record_Name.Field_Name*)	None

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Method	***Returns***
SetDataURLs(*URLString*)	None
SetDataXAxis(*Record_Name.Field_Name*)	None
SetDataYAxis(*Record_Name.Field_Name*)	None
SetExplodedSectorsArray(*&Array*)	None
SetFunnelDataActual(*Record_Name.Field_Name*)	None
SetFunnelDataTarget(*Record_Name.Field_Name*)	None
SetGlyphArray(*&Array_of_String*)	None
SetLegend(*&Array_of_String*)	None
SetOLData({*Record_Name* | *&Rowset*})	None
SetOLDataSeries(*Record_Name.Field_Name*)	None
SetOLDataXAxis(*Record_Name.Field_Name*)	None
SetOLDataYAxis(*Record_Name.Field_Name*)	None
SetReferenceArea(*&Array_of_RefAreas*)	None
SetReferenceLine(*&Array_of_RefLines*)	None
SetXAxisLabels(*&Array_of_String*)	None
SetYAxisLabels(*&Array_of_String*)	None

Chart Class Properties

Property	***Returns***
AdditionalStyleSuffix	String
AnimationDuration	Integer
AnimationType	Integer
DataStartRow	Number
DataWidth	Number
FootNote	String

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
HasLegend	Boolean
FunnelPercentMeasure	Boolean
Height	Number
ImageMap	Image map [RO]
IsChartDrillable	Boolean
IsDrillable	Boolean
IsLineChartLineSmoothing	Boolean
IsPlainImage	Boolean
IsTrueXY	Boolean
IsXAxisInteger	Boolean
IsYAxisInteger	Boolean
LegendMaxEntries	Number
LegendPosition	String
LineChartDataGlyphSize	Integer
MainTitle	String
OLType	None
SetChartURL	String
ShowCrossHair	Boolean
SubTitle	String
Type	String
Width	Number
XAxisCrossPoint	Number
XAxisLabelOrient	String
XAxisMax	Number

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	*Returns*
XAxisMin	Number
XAxisPrecision	Number
XAxisTicks	Number
XAxisTitle	String
XAxisTitleOrient	String
YAxisCrossPoint	Number
YAxisLabelOrient	String
YAxisMax	Number
YAxisMin	Number
YAxisPrecision	Number
YAxisTicks	Number
YAxisTitle	String
YAxisTitleOrient	String

ReferenceArea Class Properties

Property	*Returns*
Association	Integer
Description	String
IsDisplayedTextInLegend	Boolean
ReferenceAreaColor	Integer
ReferenceAreaLocation	Integer
ReferenceAreaValues	Array of Number
ShortText	String

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ReferenceLine Class Properties

Property	***Returns***
Association	Integer
Description	String
IsDisplayedTextInLegend	Boolean
ReferenceLineColor	Integer
ReferenceLineLocation	Integer
ReferenceLineValue	Number
ShortText	String

DialGauge Class Methods

Method	***Returns***
Refresh()	None
SetThreshold(*&threshold*)	None

DialGauge Class Properties

Property	***Returns***
AdditionalStyleSuffix	String
AnimationDuration	Integer
AnimationType	Integer
BottomLabel	String
BottomLabelPosition	Integer
GaugeDecimalDigit	Integer
GaugeMaximum	Float
GaugeMinimum	Float
GaugeURL	String
Height	Integer

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
IsDrillable	Boolean
LegendPosition	Integer
MajorTickIncrement	Float
MetricLabelPosition	Integer
MetricLabelType	Integer
MinorTickIncrement	Float
TickLabelPosition	Integer
TopLabel	String
TopLabelPosition	Integer
Type	Integer
Width	Integer

LEDGauge Class Methods

Method	***Returns***
Refresh()	None
SetThreshold(*&threshold*)	None

LEDGauge Class Properties

Property	***Returns***
AdditionalStyleSuffix	String
AnimationDuration	Integer
AnimationType	Integer
BottomLabel	String
BottomLabelPosition	Integer
GaugeDecimalDigit	Integer
GaugeURL	String

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
Height	Integer
IsDrillable	Boolean
LegendPosition	Integer
MetricLabelPosition	Integer
MetricLabelType	Integer
TopLabel	String
TopLabelPosition	Integer
Type	Integer
Width	Integer

StatusMeterGauge Class Methods

Method	***Returns***
Refresh()	None
SetThreshold(*&threshold*)	None

StatusMeterGauge Class Properties

Property	***Returns***
AdditionalStyleSuffix	String
AnimationDuration	Integer
AnimationType	Integer
BottomLabel	String
BottomLabelPosition	Integer
GaugeDecimalDigit	Integer
GaugeMaximum	Float
GaugeMinimum	Float
GaugeURL	String

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
Height	Integer
IsDrillable	Boolean
LegendPosition	Integer
MajorTickIncrement	Float
MetricLabelPosition	Integer
MetricLabelType	Integer
MinorTickIncrement	Float
TopLabel	String
TopLabelPosition	Integer
Type	Integer
Width	Integer

Threshold Class Properties

Property	***Returns***
Colors	Array of Number
Descriptions	Array of String
Id	Number
Values	Array of Number

Gantt Class Methods

Method	***Returns***
Reset()	None
SetActualEndDate(*RecordName.FieldName*)	None
SetActualStartDate(*RecordName.FieldName*)	None
SetActualTaskBarColor(*Recordname.FieldName*)	None
SetChartArea(*Percentage*)	None

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Method	***Returns***
SetDayFormat(*Format*)	None
SetMonthFormat(*Format*)	None
SetPlannedEndDate(*RecordName.FieldName*)	None
SetPlannedStartDate(*RecordName.FieldName*)	None
SetPlannedTaskBarColor(*RecordName.FieldName*)	None
SetTaskAppData(*RecordName.FieldName1*[, *RecordName.FieldName2* [,*RecordName.FieldName3*. . .]])	None
SetTaskAppDataTitles(*&TitleArray*)	None
SetTaskBarURL(*RecordName.FieldName*)	None
SetTaskData({**Record.** *RecordName* | *&Rowset*})	None
SetTaskDependencyChildID(*RecordName.FieldName*)	None
SetTaskDependencyData({*RecordName* | *&Rowset*})	None
SetTaskDependencyParentID(*RecordName.FieldName*)	None
SetTaskDependencyType (*RecordName*, *FieldName*)	None
SetTaskDependencyURL(*RecordName.FieldName*)	None
SetTaskDrill(*Recordname.FieldName*)	None
SetTaskID(*RecordName.FieldName*)	None
SetTaskLabel(*RecordName.FieldName*)	None
SetTaskLevel(*RecordName.FieldName*)	None
SetTaskMilestone(*RecordName.FieldName*)	None
SetTaskName(*RecordName.FieldName*)	None
SetTaskProgress(*RecordName.FieldName*)	None
SetTaskProgressBarColor(*RecordName.FieldName*)	None
SetWBSNumbering(*RecordName.FieldName*)	None
SetYearFormat(*Format*)	None

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Gantt Class Properties

Property	***Returns***
AxisEndDateTime	DateTime
AxisStartDateTime	DateTime
GridLines	String
GridLineType	String
Height	Number
InteractiveEnd	Boolean
InteractiveMove	Boolean
InteractiveProgress	Boolean
InteractiveStart	Boolean
IsDrillable	Boolean
PixelsPerRow	Number
ShowTaskLabels	Boolean
Style	String
TaskDependencyLineType	Number
TaskMilestoneGlyph	Number
TaskTitle	String
Width	Number

OrgChart Methods

Method	***Returns***
SetCrumbData(*&Rowset*)	None
SetCrumbRecord(**Record**.*Record_Name*)	None
SetDropdownData(*&Rowset*)	None
SetDropDownRecord(**Record.***RecordName*)	None

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Method	***Returns***
SetIMData(*&rsRowset*)	None
SetIMRecord(**Record.***Record_Name*)	None
SetLegend(*&Array_of_String*)	None
SetLegendImg(*&Array_of_String*)	None
SetNodeData(*&Rowset*)	None
SetNodeDisplayData(*&rsRowset*)	None
SetNodeDisplayDataRecord(**Record.***Record_Name*)	None
SetNodeRecord(**Record.***Record_Name*)	None
SetNodeViewEntries(*&NodeViewArray*	None
SetNodeViewText(*&ToolTipArray*)	None
SetPopUpNodeData(*&Rowset*)	None
SetPopUpNodeRecord(**Record.***Record_Name*)	None
SetSchemaLevels(*&Array*)	None

OrgChart Class Properties

Property	***Returns***
CenterFocusNode	Number
ChartCurrentSchemaLevel	Number
ChartScrollType	Number
Collapsed_Msg	String
CollapsedImage	String
CollapseMainIconSpace	Number
CrumbDescrStyle	String
CrumbMaxDisplayLength	Number
CrumbSeparatorImage	String

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
DefaultImage	String
Direction	Number
DropDownBoxStyle	String
Expanded_Msg	String
ExpandedImage	String
HasLegend	Boolean
Height	Number
ImageHeight	Number
ImageLocation	Number
ImageMouseoverMagnificationFactor	Number
IMPresence	Boolean
IMRefreshInterval	Number
InitialView	String
LegendPosition	Number
LegendStyle	String
LegendTopSpace	Number
MainTitle	String
MainTitleStyle	String
MaxDropdownDisplayItem	Number
MaxPopupDisplayNode	Number
NodeDescr1Style	String
NodeDescr2Style	String
NodeDescr3Style	String
NodeDescr4Style	String

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
NodeDescr5Style	String
NodeDescr6Style	String
NodeDescr7Style	String
NodeMaxDisplayDescLength	Number
NodeProportion	Number
OptimizeHorizontalSpace	Number
OptimizeVerticalSpace	Number
PopupHeaderStyle	String
PopupNodeDescr1Style	String
PopupNodeDescr2Style	String
PopupNodeDescr3Style	String
PopupNodeDescr4Style	String
PopupNodeDescr5Style	String
PopupNodeDescr6Style	String
PopupNodeDescr7Style	String
PopupNodeDescr8Style	String
Style	String
SuppressPeopleCodeOnImage	Boolean
SuppressPeopleCodeOnNode	Boolean
UnlinkCrumbDescrStyle	String
VerticalSpace	Number
Width	Number

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SchemaLevel Class Properties

Property	***Returns***
ID	Number
ImageHeight	Number

RatingBoxChart Class Methods

Method	***Returns***
SetLegend(*&Array_of_String*)	None
SetLegendImg(*&Array_of_String*)	None
SetQuadrantSchemas(*&Quadrant_Array*)	None
SetRBNodeData(*&Array_of_String*)	None
SetRBNodeRecord(**Record**.*RecordName*)	None
SetXAxisLabels(*&Array_of_String*)	None
SetYAxisLabels(*&Array_of_String*)	None

RatingBoxChart Class Properties

Property	***Returns***
BoxMaxDisplayItems	Number
DraggedNodeStyle	String
EnableRelatedActions	Boolean
GridLineType	Number
HasLegend	Boolean
Height	Number
IconOnlySelectedQuadrantStyle	String
IsDragable	Boolean
LegendPosition	Number
MainTitle	String

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	*Returns*
MainTitleStyle	String
NDMaxDisplayDescLength	Number
PopUpHeaderStyle	String
PopUpHeight	Number
PopUpStyle	String
PopUpWidth	Number
SelectedQuadrantStyle	String
ShowAxisLabels	Boolean
ShowNodeDescription	Boolean
Style	String
ViewAllStyle	String
Width	Number
XAxisBoxNum	Number
XAxisLabelStyle	String
XAxisTitle	String
XAxisTitleStyle	String
YAxisBoxNum	Number
YAxisLabelStyle	String
YAxisTitle	String
YAxisTitleStyle	String

QuadrantSchema Class Properties

Property	*Returns*
LabelPosition	Integer
LabelStyle	String

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	*Returns*
LabelText	String
XRating	String
YRating	String

Component Interface Class

See Component Interface Class Methods and Properties.

Connected Query Classes

This section lists the functions, methods, and properties, as well as returns (if applicable) for the connected query classes.

Connected Query Classes Constructors

Constructor	*Returns*
CONQRSMGR([*userID*], *CONQRSNAME*);	CONQRSMGR object
SEC_PROFILE()	SEC_PROFILE object
UTILITY()	UTILITY object

CONQRSMGR Methods

Method	*Returns*
CleanOutputFile()	None
Close()	None
CopyDefn(*target_UserID*, *target_ID*)	Boolean
DeleteDefn()	Boolean
ExistsByName(*ObjName*)	Boolean
Open(*IsNew*)	Boolean
ResetQueriesPrompt()	None
Run(*Prompts*, *runProcessInfo*)	Boolean
RunToWindow()	Number

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Method	***Returns***
RunToXMLFormattedString(*Prompts*)	String
Save()	Boolean
SaveRunControlParms(*runCntlID*)	Boolean
SetRunControlData(*runCntlID*, *IsNewCtrl*, *IsChangeDB*)	Boolean
Validate()	Boolean
ValidateIfFieldsMapped()	Boolean
ValidateRunControlParms(*runCntlID*)	Boolean

CONQRSMGR Properties

Property	***Returns***
Const	CONQRS_CONST object RO
Description	String
Details	String
ErrString	String RO
ExecutionLog	Boolean RO
IgnoreRelFldOutput	Boolean RO
IsChanged	Boolean RO
IsDebugMode	Boolean RO
IsInit	Boolean RO
IsPublic	Boolean RO
LastUpdatedBy	String RO
LastUpdateDTTM	DateTime RO
MaxRowsPerQuery	Number
Name	String RO
ObjectRowset	Rowset object

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
OprID	String RO
OutProcessFileName	String RO
PropertyArray	Array of CONQRSPROPERTY objects
QueriesPromptsArray	Array of QUERYITEMPROMPT objects RO
QueryArray	Array of string RO
RegisteredBy	String RO
RegisteredDTTM	DateTime RO
RunCntlId	String RO
RunControlParArray	Array of PSCONQRSRUNPRM records RO
RunMode	Number RO
SchedInfo	SCHED_INFO object
SchedRequestType	String
SecProfile	SEC_PROFILE object RO
ShowFormattedXML	Boolean RO
Status	String
XMLDataFileName	String RO
XMLDataFullName	String RO

CONQRSPROPERTY Properties

Property	***Returns***
PROPDEFAULT	String
PROPNAME	String
PROPVALUE	String
PROPVALUEARRAY	String
PROPVALUEARRAYDESC	String

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

CONQRS_CONST Properties

Property	*Returns*
InitExisting	Boolean RO
InitNew	Boolean RO
MsgSet	Number RO
RunCntlId_Auto	String RO
RunMode_Prev	Number RO
RunMode_Prev_DefRowNumber	Number RO
RunMode_Sample	Number RO
RunMode_Sched_File	Number RO
RunMode_Sched_Web	Number RO
RunMode_Window	Number RO
RunMode_XMLFormattedString	Number RO
SchedRequest_CQR	String RO
SchedRequest_XMLP	String RO
Stat_Active	String RO
Stat_InActive	String RO
Stat_InProgress	String RO

QUERYITEMPROMPT Properties

Property	*Returns*
QueryName	String RO
QueryPromptRecord	Record object RO

SCHED_INFO Properties

Property	*Returns*
AE_ID	String

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	*Returns*
DIRLOCATION	String
OPRID	String
OUTDESTTYPE	Number
PRCSFILENAME	String
PROCESS_INSTANCE	String
RUN_CNTL_ID	String

SEC_PROFILE Properties

Property	*Returns*
CanCreatePublic	Boolean RO
CanModify	Boolean RO
CanRunQuery	Boolean RO

UTILITY Methods

Method	*Returns*
CheckQryForTreePrompt(*QryName*, *scope*)	String
CheckQrySecurity(*QryName*, *IsPublicObject*)	Boolean
GetQueryScopeByName(*QryName*)	Number
ValidateObjectID(*ID*)	String

Crypt Class

This section lists the methods and properties, as well as returns (if applicable) for the Crypt class.

Function

Function	*Returns*
CreateObject(“Crypt”)	Crypt object

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Methods

Method	***Returns***
FirstStep()	None
GoToStep(*StepNumber*)	None
LoadLibrary(*LibraryFile*, *LibraryID*)	None
NextStep()	None
Open(*ProfileName*)	None
SetParameter(*Name*,*Value*)	None
UpdateData(*Data*)	None

Properties

Property	***Returns***
Result	String [RO]
Verified	Boolean [RO]

Document Classes

This section lists the functions, methods, and properties, as well as returns (if applicable) for the connected query classes.

Document Classes Functions

Function	***Returns***
CreateDocument(*DocumentKey* | *Package*, *DocumentName*, *Version*)	Document object
CreateDocumentKey(*Package*, *DocumentName*, *Version*)	DocumentKey object

Document Methods

Method	***Returns***
GenJsonString()	String
GenXmlString([*validate*])	String

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Method	***Returns***
GetDocumentKey()	DocumentKey object
GetElement(*ElementName*)	Collection object, Compound object, or Primitive object
GetRowset()	Rowset object
GetSchema()	String
ParseJsonString(*JSON_data*[, *validate*])	Boolean
ParseXmlFromFile(*file_name* [, *validate*])	Boolean
ParseXmlFromURL(*URL* [, *validate*])	Boolean
ParseXmlString(*XML_string* [, *validate*])	Boolean
UpdateFromRowset(*&Doc_RS*)	Boolean
ValidateData()	Boolean

Document Properties

Property	***Returns***
DocumentElement	Compound object RO

DocumentKey Methods

Method	***Returns***
SetDocumentKey(*Package*, *DocumentName*, *Version*)	Boolean

DocumentKey Properties

Property	***Returns***
DocumentName	String RO
PackageName	String RO
Version	String RO

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Primitive Methods

Method	***Returns***
GetEnumName(*index*)	String
GetParent()	Collection object or Compound object
GetPath()	String

Primitive Properties

Property	***Returns***
ElementType	Integer [RO]
EnumCount	Integer [RO]
IsChanged	Boolean [RO]
IsInitialized	Boolean [RO]
IsRequired	Boolean [RO]
MaxDefinedDecimalLength	Integer [RO]
MaxDefinedLength	Integer [RO]
Name	String [RO]
OrigValue	String
PrimitiveSubType	Integer [RO]
PrimitiveType	Integer [RO]
SequenceNumber	Integer [RO]
Value	String

Compound Methods

Method	***Returns***
GetParent()	Collection object or Compound object
GetPath()	String
GetPropertyByIndex(*index*)	Collection object, Compound object, or Primitive object

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Method	***Returns***
GetPropertyByName(*prop_name*)	Collection object, Compound object, or Primitive object
GetUniqueKey()	Array of string

Compound Properties

Property	***Returns***
ElementType	Integer RO
IsChanged	Boolean RO
IsInitialized	Boolean RO
IsRequired	Boolean RO
Name	String RO
PropertyCount	Integer RO
SequenceNumber	Integer RO

Collection Methods

Method	***Returns***
AppendItem(*&Elem*)	Boolean
CreateItem()	Collection object, Compound object, or Primitive object
DeleteItem(*index*)	Boolean
GetItem(*index*)	Collection object, Compound object, or Primitive object
GetParent()	Collection object or Compound object
GetPath()	String
InsertItem(*&Elem*, *index*)	Boolean

Collection Properties

Property	***Returns***
CollectionElementType	Integer RO

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
Count	Integer RO
DefinedMaxOccurs	Integer RO
DefinedMinOccurs	Integer RO
ElementType	Integer RO
IsChanged	Boolean RO
IsInitialized	Boolean RO
IsRequired	Boolean RO
Name	String RO
SequenceNumber	Integer RO

Exception Class

This section lists the functions, methods, and properties, as well as returns (if applicable) for the exception class.

Functions

Function	***Returns***
CreateException(*message_set*, *message_num*, *default_txt* [, *subslist*])	Exception object
Throw *Expression*	None
try *Protected StatementList* catch *QualifiedID &Id* *StatementList* end-try	None

Methods

Method	***Returns***
GetSubstitution(*Index*)	String

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Method	***Returns***
Output()	String
SetSubstitution(*Index*, *String*)	None
ToString()	String

Properties

Property	***Returns***
Context	String RO
DefaultText	String
MessageNumber	Number RO
MessageSetNumber	Number RO
MessageSeverity	String RO
StackTrace	String RO
SubstitutionCount	Number RO

Feed Classes

This section lists the functions, methods, and properties, as well as returns (if applicable) for the feed classes.

Feed Classes Constructors

Constructor	***Returns***
FeedFactory.createFeed("*feed_ID*")	Feed object
FeedFactory()	FeedFactory object
FeedFactory.getDataSource("*DS_ID*")	DataSource object
DataSourceParameter("*DSP_ID*", *&Parent_DS*)	DataSourceParameter object
DataSourceParameterValue("*ID*", *&Parent_DSP*)	DataSourceParameterValue object
DataSourceSetting("*DSS_ID*", *&Parent_DS*)	DataSourceSetting object
Utility()	Utility object

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Constructor	***Returns***
FeedFactory.Utility.getFeedDoc ("*feed_ID*", *Format*, *&Attributes*)	FeedDoc object
FeedDoc.addEntry("*entry_ID*")	FeedEntry object

Feed Methods

Method	***Returns***
delete()	Boolean
equals(*&Object*)	Boolean
execute()	FeedDoc object
getAttribute(*attribute_ID*)	Attribute object
load()	Boolean
loadFromTemplate(*template_ID*)	Boolean
PopulateDSParamsWithDefaults()	None
populatePrefData(*&FeedRequest*)	None
publishToSites(*Sites*)	None
resetFeedAttributes()	FeedAttributes collection
resetFeedSecurities()	FeedSecurities collection
save()	Boolean
saveAs(*new_ID*, *CopyPrefData*)	Feed object
saveAsTemplate(*new_ID*, *CopyPrefData*)	Boolean
setAttribute(*attribute_ID*, *Value*, *XML*)	Attribute object
setDataSourceById(*DataType_ID*)	DataSource object
unpublishFromSites(*Sites*)	None

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Feed Properties

Property	***Returns***
Authorized	Boolean RO
CategoryID	String
CreateDTTM	DateTime RO
CreateNode	String
CreateOprID	String RO
CreatePortal	String
DataSource	DataSource object
DataTypeID	String RO
Description	String
FeedAttributes	FeedAttributes collection
FeedAuthorizationOprID	String
FeedAuthorizationOprPWD	String
FeedAuthorizationType	String
FeedCacheTime	*not current used*
FeedCacheType	*not current used*
FeedContentUrl	String RO
FeedFactory	FeedFactory object
FeedFormat	String
FeedSecurityType	String
FeedTemplate	Boolean
FeedUrl	String RO
HasAdminParams	Boolean RO
HasUserParams	Boolean RO
IBOperationName	String

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
ID	String RO
LastPubDTTM	DateTime RO
LastUpdDTTM	DateTime RO
LastUpdOprID	String RO
NameSpaceID	String
ObjectType	String RO
OperatingMode	Number RO
OwnerID	String
PublishedInSites	Array of string RO
Title	String
Utility	Utility object

FeedFactory Methods

Method	***Returns***
convertFeedLinksToHoverMenu(*&Links*, *Flat*)	HoverMenu object
convertFeedLinksToOPML(*&Links*, *Flat*)	OPMLDoc object
createFeed(*feed_ID*)	Feed object
deleteFeed(*feed_ID*)	Boolean
genFeedUrl(*feed_ID*, *OperationName*, *SecurityType*)	String
genUniqueFeedId(*seed*)	String
getAllPagedFeedLinks(*feed_ID*, *fromDTTM*, *allLanguages*)	Array of string
getCategory(*category_ID*, *ActiveOnly*)	Array of string
getDataSource(*DataType_ID*)	DataSource object
getFeed(*feed_ID*, *mode*)	Feed object
getFeedDoc(*&feedRequest*)	FeedDoc object

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Method	***Returns***
getFeedLink(*feed_ID*)	Link object
getFeedLinks(*&searchRequest*)	Link collection
getFeedTemplates(*&searchRequest*)	Feed collection
getRelatedFeedsHoverMenu(*&Requests*)	HoverMenu object
getRelativePageLinkForFeed(*feed_ID*, *currentFeedURL*, *linkOption*, *fromDTTM*)	String

FeedFactory Properties

Property	***Returns***
DataSources	DataSource collection RO
Feeds	Feed collection RO
Utility	Utility object

DataSource Methods

Method	***Returns***
addParameter(*DSparam_ID*, *Value*)	DataSourceParameter object
equals(*&Object*)	Boolean
getAttributeById(*attribute_ID*)	Attribute object
getContentUrl()	String
getDataSecurity()	Authorization objects
getParameterById(*DSP_ID*)	DataSourceParameter object
getParameterDetail()	String
getSettingDetail()	String
isCurrentUserAdmin()	Boolean
isCurrentUserAuthorized()	Boolean
onDelete()	None

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Method	***Returns***
resetParameters()	DataSourceParameter collection

DataSource Properties

Property	***Returns***
AdminPersonalizationPage	PSComponent object
AllowCustomParameters	Boolean RO
AllowRealTimeFeedSecurity	Boolean RO
DataSourceType	String RO
DefaultFeedAttributes	Attribute collection
DefaultIBOperationName	String RO
Description	String
HasParameters	Boolean RO
HasSettings	Boolean RO
IBOperations	IBOperation collection
ID	String RO
LongDescription	String
ObjectType	String RO
Parameters	DataSourceParameter collection RO
ParametersCompleted	Boolean RO
Parent	Feed object
PortalSpecificPersonalization	Boolean RO
Settings	DataSourceSetting collection RO
SettingsCompleted	Boolean RO
UserPersonalizationPage	PSComponent object
Utility	Utility object

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

DataSourceParameter Methods

Method	***Returns***
addUserValue(*DSPValue_ID*, *Value*)	DataSourceParameterValue object
clone()	DataSourceParameter object
equals(*&Object*)	Boolean
resetUserValues()	UserValues collection
setRangeFromFieldTranslates(*FieldName*)	None
validateValue(*Value*, *CheckPrompt*)	String

DataSourceParameter Properties

Property	***Returns***
AllowChangesToRequired	Boolean
DefaultValue	String
DefaultValueForDisplay	String [RO]
Description	String
EditType	Number
EvaluatedValue	String [RO]
FieldType	Number
ID	String
Name	String
ObjectType	String [RO]
Parent	DataSource object
PromptTable	String
Range	Array of string
Required	Boolean
SkipValidityChecks	Boolean

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
UsageType	String
UserValues	UserValues collection RO
Utility	Utility object
Value	String
ValueForDisplay	String RO

DataSourceParameterValue Methods

Method	***Returns***
clone()	DataSourceParameterValue object
equals(*&Object*)	Boolean

DataSourceParameterValue Properties

Property	***Returns***
Description	String
ID	String RO
Name	String
ObjectType	String RO
OrderNumber	Number
Parent	DataSourceParameter object
Value	String

DataSourceSetting Methods

Method	***Returns***
clone()	DataSourceSetting object
equals(*&Object*)	Boolean
setRangeFromFieldTranslates(*FieldName*)	None

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

DataSourceSetting Properties

Property	***Returns***
DefaultValue	String
DisplayOnly	Boolean RO
EditType	Number
Enabled	Boolean
FieldType	Number
ID	String RO
LongName	String
Name	String
ObjectType	String RO
Parent	DataSource object
PromptTable	String
Range	Array of string RO
RefreshOnChange	Boolean
RelatedFieldValue	String
Required	Boolean
ShowRelatedField	Boolean RO
Utility	Utility object
Value	String
Visible	Boolean

Utility Methods

Method	***Returns***
dateStringToUserPref(*DateString*)	String
datetimeToString(*Datetime*)	String

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Method	***Returns***
decodeXML(*String*)	String
encodeXML(*String*)	String
evaluateSysVar(*SysVar*)	String
genNameSpaceID(*NameSpace_ID*)	String
getExceptionText(*&Exception*)	String
getFeedDoc(*feed_ID*, *Format*, *&Attributes*)	FeedDoc object
getFeedMimeType(*Format*)	String
getFieldTranslates(*FieldName*)	Array of array of string
getNodeValue(*String*, *Tag*)	String
getUserDateFormat()	String
getUserInfo(*user_ID*)	Array of string
httpStringToDatetime(*string*)	DateTime
join(*&Array*, *Tag*)	String
join2D(*&Array*, *Tag*, *ChildTags*)	String
setMessageHeadersAndMimeType(*&Message*, *&feeddoc*, *&FeedRequest*)	Message object
setNodeValue(*Value*, *Tag*)	String
showException(*Exception*)	None
showInvalidValueException(*Name*, *Value*)	None
split()	Array of string
split2D()	Array of array of string
stringToDate(*DateString*)	Date
stringToDatetime(*DatetimeString*)	DateTime
validateSysVar(*SysVar*)	String
viewStringAsAttachment(*String*, *FileName*, *ViewAttachment*)	None

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Utility Properties

Property	*Returns*
ATTACHMENT_URL	String RO
AUTHTYPE_PERM	String RO
AUTHTYPE_ROLE	String RO
DSPARAMETER_INCREMENTAL	String RO
DSPARAMETER_MAXROW	String RO
DSPARAMETER_SF_MAXMINUTES	String RO
DSPARAMETER_SF_PAGING	String RO
EDITTYPE_NOTABLEEDIT	Integer RO
EDITTYPE_PROMPTTABLE	Integer RO
EDITTYPE_TRANSLATETABLE	Integer RO
EDITTYPE_YESNO	Integer RO
FEEDATTRIBUTE_AUTHOR	String RO
FEEDATTRIBUTE_CLOUD	String RO
FEEDATTRIBUTE_COMPLETE	String RO
FEEDATTRIBUTE_CONTRIBUTOR	String RO
FEEDATTRIBUTE_COPYRIGHT	String RO
FEEDATTRIBUTE_EXPIRES	String RO
FEEDATTRIBUTE_ICONURL	String RO
FEEDATTRIBUTE_LOGOURL	String RO
FEEDATTRIBUTE_MANAGINGEDITOR	String RO
FEEDATTRIBUTE_MAXAGE	String RO
FEEDATTRIBUTE_PERSINSTRUCTION	String RO
FEEDATTRIBUTE_RATING	String RO
FEEDATTRIBUTE_SKIPDAYS	String RO

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
FEEDATTRIBUTE_SKIPHOURS	String RO
FEEDATTRIBUTE_TEXTINPUT	String RO
FEEDATTRIBUTE_TTL	String RO
FEEDATTRIBUTE_WEBMASTER	String RO
FEEDATTRIBUTE_XSL	String RO
FEEDAUTHTYPE_ALL	String RO
FEEDAUTHTYPE_ANONYMOUS	String RO
FEEDAUTHTYPE_DEFAULT	String RO
FEEDCACHETYPE_NONE	String RO
FEEDCACHETYPE_PRIVATE	String RO
FEEDCACHETYPE_PUBLIC	String RO
FEEDCACHETYPE_ROLE	String RO
FEEDFORMAT_ATOM10	String RO
FEEDSECUTYPE_PUBLIC	String RO
FEEDSECUTYPE_REALTIME	String RO
FEEDSECUTYPE_SELECTED	String RO
FEEDTEMPLATE_NO	String RO
FEEDTEMPLATE_YES	String RO
FEEDTYPE_DYNAMIC	String RO
FEEDTYPE_PREPUBLISHED	String RO
FIELDTYPE_CHARACTER	Integer RO
FIELDTYPE_DATE	Integer RO
FIELDTYPE_DATETIME	Integer RO
FIELDTYPE_LONGCHARACTER	Integer RO

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
FIELDTYPE_NUMBER	Integer RO
FIELDTYPE_SIGNEDNUMBER	Integer RO
FIELDTYPE_TIME	Integer RO
IBSOTYPE_ASYNC	String RO
IBSOTYPE_SYNC	String RO
IBSOTYPE_UNKNOWN	String RO
ICONURL_FEED_A	String RO
ICONURL_FEED_IA	String RO
INCREMENTALOPTION_NO	String RO
INCREMENTALOPTION_YES	String RO
LINKTYPE_FIRST	String RO
LINKTYPE_LAST	String RO
LINKTYPE_NEXT	String RO
LINKTYPE_PREVIOUS	String RO
MIMETYPE_ATOM	String RO
MIMETYPE_OPML	String RO
MIMETYPE_XML	String RO
OPERATINGMODE_AUTHORIZATION	Integer RO
OPERATINGMODE_DEFAULT	Integer RO
OPERATINGMODE_DELETION	Integer RO
OPERATINGMODE_EXECUTION	Integer RO
OPERATINGMODE_EXECUTION_NOENTRY	Integer RO
QUERYPARAMETER_CHILDFEEDID	String RO
QUERYPARAMETER_DATATYPEID	String RO

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
QUERYPARAMETER_DEFLOCALNODE	String RO
QUERYPARAMETER_DSSCOUNT	String RO
QUERYPARAMETER_DSSNAME	String RO
QUERYPARAMETER_DSSVALUE	String RO
QUERYPARAMETER_FEEDFORMAT	String RO
QUERYPARAMETER_FEEDID	String RO
QUERYPARAMETER_FEEDLIST	String RO
QUERYPARAMETER_FEEDTYPE	String RO
QUERYPARAMETER_IBTRANSID	String RO
QUERYPARAMETER_IFMODIFIEDSINCE	String RO
QUERYPARAMETER_IFNONEMATCH	String RO
QUERYPARAMETER_KEYWORD	String RO
QUERYPARAMETER_LANGUAGE	String RO
QUERYPARAMETER_NODENAME	String RO
QUERYPARAMETER_PAGENUM	String RO
QUERYPARAMETER_PORTALNAME	String RO
QUERYPARAMETER_PTPPB_SEARCH_MODE	String RO
QUERYPARAMETER_PTPPB_SEARCH_TEXT	String RO
RequestInfo	FeedRequest object
SF_MAXMINUTES_ALLMSGS	Integer RO
SF_MAXROWOPTION_ALLMSGS	Integer RO
SF_MAXROWOPTION_LATESTMSG	Integer RO
SF_PAGINGOPTION_NOPAGING	Integer RO
SF_PAGINGOPTION_SEGMENTED	Integer RO

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
SYSVAR_INVALID	String RO
USAGETYPE_ADMINSPECIFIED	String RO
USAGETYPE_FIXED	String RO
USAGETYPE_INTERNAL	String RO
USAGETYPE_NOTUSED	String RO
USAGETYPE_SYSVAR	String RO
USAGETYPE_USERSPECIFIED	String RO
XMLCHILDELEMENTS_CLOUD	Array of string RO
XMLCHILDELEMENTS_PERSON	Array of string RO
XMLCHILDELEMENTS_TEXTINPUT	Array of string RO
XMLELEMENT_DAY	String RO
XMLELEMENT_DESCRIPTION	String RO
XMLELEMENT_DOMAIN	String RO
XMLELEMENT_EMAIL	String RO
XMLELEMENT_HOUR	String RO
XMLELEMENT_LINK	String RO
XMLELEMENT_NAME	String RO
XMLELEMENT_PATH	String RO
XMLELEMENT_PORT	String RO
XMLELEMENT_PROTOCOL	String RO
XMLELEMENT_REGISTERPROCEDURE	String RO
XMLELEMENT_TITLE	String RO

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

FeedDoc Methods

Method	***Returns***
addCategory(*category*)	Boolean
addEntry(*entry_ID*)	FeedEntry object
datetimeToString(*Datetime*)	String
deleteCategory(*category*)	Boolean
equals(*&Object*)	Boolean
getEntry(*entry_ID*)	FeedEntry object
resetEntries()	FeedEntry collection
stringToDatetime(*DatetimeString*)	DateTime

FeedDoc Properties

Property	***Returns***
AllowMoreEntries	Boolean RO
ApplicationRelease	String RO
Categories	Array of string RO
ContentUrl	String
Copyright	String
Description	String
Entries	FeedEntry collection RO
Expires	DateTime
FeedFormat	String RO
FeedUrl	String
FirstUrl	String
Generator	String
ID	String RO

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
LastUrl	String
Logo	String
MaxAge	Number
MaxEntries	Number
NextUrl	String
ObjectType	String RO
PreviousUrl	String
RootElement	XmlNode object RO
Title	String
Updated	DateTime

FeedEntry Methods

Method	***Returns***
addCategory(*category*)	Boolean
addContributor(*name*, *email*)	Boolean
addEnclosure(*URL*, *type*, *length*)	Boolean
delete()	None
deleteCategory(*category*)	Boolean
deleteContributor(*name*)	Boolean
deleteEnclosure(*URL*)	Boolean
equals(*&Object*)	Boolean

FeedEntry Properties

Property	***Returns***
Author	Array of string
Categories	Array of string RO

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
Comments	String
ContentUrl	String
Contributors	Array of array of string RO
Copyright	String
Description	String
Enclosures	Array of array of string RO
Expires	DateTime
FeedDoc	FeedDoc object RO
FullContent	String
GUID	String
ID	String RO
MaxAge	Number
ObjectType	String RO
Published	DateTime
Title	String
Updated	DateTime

Field Class

This section lists the functions, methods, and properties, as well as returns (if applicable) for the Field class.

Function

Function	***Returns***
GetField([*recname.fieldname*])	Field object

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Methods

Method	***Returns***
AddDropDownItem(*CodeString*, *DescriptionString*)	None
ClearDropDownList()	None
EncryptPETKey()	None
DecryptPETKey()	None
GetAuxFlag(*FlagNumber*)	Boolean
GetLongLabel(*LabelID*)	String
GetRelated(*recname.fieldname*)	Field object
GetShortLabel(*LabelID*)	String
SearchClear()	None
SetCursorPos({**Page**.*pagename* | **%Page**})	None
SetDefault()	None

Properties

Property	***Returns***
DataAreaCollapsed	Boolean
DecimalPosition	Number
DisplayFormat	String
DisplayOnly	Boolean
DisplayZero	Boolean
DisplayZeroChanged	Boolean
EditError	Boolean
Enabled	Boolean
FieldLength	Number [RO]
FormatLength	Number [RO]

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
FormattedValue	None
HoverText	String
IsAltKey	Boolean RO
IsAuditFieldAdd	Boolean RO
IsAuditFieldChg	Boolean RO
IsAuditFieldDel	Boolean RO
IsAutoUpdate	Boolean RO
IsChanged	Boolean RO
IsDateRangeEdit	Boolean RO
IsDescKey	Boolean RO
IsDuplKey	Boolean RO
IsEditTable	Boolean RO
IsEditXlat	Boolean RO
IsFromSearchField	Boolean RO
IsInBuf	Boolean RO
IsKey	Boolean RO
IsListItem	Boolean RO
IsNotUsed	Boolean RO
IsRequired	Boolean RO
IsRichTextEnabled	Boolean RO
IsSearchItem	Boolean RO
IsSystem	Boolean RO
IsThroughSearchField	Boolean RO
IsUseDefaultLabel	Boolean RO

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
IsYesNo	Boolean RO
Label	String
LabelImage	{**Image**.*imagename* | String}
LongTranslateValue	Any
MessageNumber	Number RO
MessageSetNumber	Number RO
MouseOverMsgNum	Number
MouseOverMsgSet	Number
Name	String RO
OriginalValue	Depends on field
ParentRecord	Record object RO
PromptTableName	String RO
SearchDefault	Boolean
SearchEdit	Boolean
SetComponentChanged	Boolean
ShortTranslateValue	Any
ShowRequiredFieldCue	Boolean
SmartZero	Boolean
SqlText	String
StoredFormat	String RO
Style	String
Type	String RO
Value	Depends on field
Visible	Boolean

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

File Class

This section lists the functions, methods, and properties, as well as returns (if applicable) for the file class.

Functions

Function	***Returns***
CreateDirectory(*path*, [, *pathtype*])	None
FileExists(*filename* [, *pathtype*])	Boolean
FindFiles(*filespec_pattern* [, *pathtype*])	Array object
GetFile(*filename*, *mode* [, *charset*] [,*pathtype*])	File object
GetTempFile(*filename*, *mode* [, *charset*] [,*pathtype*])	File object

Methods

Method	***Returns***
Close()	None
CreateRowset()	Rowset object
GetBase64StringFromBinary()	String
GetPosition()	Number
GetString([*Strip_Line_Terminator*])	String
Open(*filename*, *mode* [, *charset*] [, *pathtype*])	None
ReadLine(*string*)	Boolean
ReadRowset()	Rowset object
SetFileId(*fileid*, *position*)	
SetFileLayout(FILELAYOUT.*filelayoutname*)	Boolean
SetPosition(*position*)	None
SetRecTerminator(*Terminator*)	None
WriteBase64StringToBinary(*encoded_string*)	None
WriteLine(*string*)	None

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Method	***Returns***
WriteRaw(*RawBinary*)	None
WriteRecord(*record*)	Boolean
WriteRowset(*rowset* [, *Write_Data*])	Boolean
WriteString(*string*)	None

Properties

Property	***Returns***
CurrentRecord	String [RO]
IgnoreInvalidId	Boolean
IsError	Boolean [RO]
IsNewFileId	Boolean [RO]
IsOpen	Boolean [RO]
Name	String [RO]
TerminateLines	Boolean
UseSpaceForNull	Boolean
ZeroExtend	Boolean

Grid Classes

This section lists the functions, methods, and properties, as well as returns (if applicable) for the grid classes.

Grid Functions

Function	***Returns***
GetGrid(**PAGE**.*pagename*, *gridname* [, *occursnumber*])	Grid object

Grid Methods

Method	***Returns***
GetColumn(*columname*)[D]	GridColumn object

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Method	***Returns***
EnableColumns(*&Array*)	None
LabelColumns(*&Array*)	None
SetProperties(*&Array*)	None
ShowColumns(*&Array*)	None

Grid Properties

Property	***Returns***
gridcolumnn	GridColumn object
Label	String
PersistMenuOption	Boolean
SummaryText	String

GridColumn Properties

Property	***Returns***
Enabled	Boolean
Label	String
Name	String [RO]
Visible	Boolean

Internet Script Classes

This section lists the system variables, methods, and properties, as well as returns (if applicable) for the internet script (iScript) classes.

Internet Script System Variables

System Variable	***Returns***
%Request	Request object
%Response	Response object

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Request Methods

Method	***Returns***
GetCookieNames()	Array of string
GetCookieValue(*name*)	String
GetHeader(*name*)	String
GetHeaderNames()	Array of string
GetHelpURL(*HelpContext*)	String
GetParameter(*name*)	String
GetParameterNames()	Array of string
GetParameterValues(*Name*)	Array of string

Request Properties

Property	***Returns***
AuthTokenDomain	String RO
AuthType	String RO
BrowserPlatform	String RO
BrowserType	String RO
BrowserVersion	String RO
ByPassSignOn	Boolean RO
ContentURI	String RO
ExpireMeta	String RO
FullURI	String RO
HTTPMethod	String RO
LogoutURL	String RO
PathInfo	String RO
Protocol	String RO

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
QueryString	String RO
RelativeURL	String RO
RemoteAddr	String RO
RemoteHost	String RO
RequestURI	String RO
RemoteUser	String RO
Scheme	String RO
ServerName	String RO
ServerPort	String RO
ServletPath	String RO
Timeout	Integer RO

Response Methods

Method	***Returns***
Clear()	None
CreateCookie(*name*)	Cookie object
GetCookie(*name*)	Cookie object
GetCookieNames()	Array of string
GetHeader(*name*)	String
GetHeaderNames()	Array of string
GetImageURL(*ImageName*)	String
GetJavaScriptURL(HTML.*Name*)	Srting
GetStyleSheetURL(STYLESHEET.*name*)	String
RedirectURL(*name*)	None
SetContentType(*Type*)	None

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Method	***Returns***
SetHeader(*name*, *value*)	None
UseSimpleURL({*True* | *False*})	None
Write(*HTML*)	None
WriteLine(*HTML*)	None

Response Properties

Property	***Returns***
Charset	String RO
DefaultStyleSheetName	String RO

Cookie Properties

Property	***Returns***
Domain	String
MaxAge	Number
Name	String RO
Path	String
Secure	Boolean
Value	String

Java Class

This section lists the functions for the Java class.

Functions

Function	***Returns***
CopyFromJavaArray(*JavaArray*, *&PeopleCodeArray* [, *&RestrictionArray*])	None.
CopyToJavaArray(*&PeopleCodeArray*, *JavaArray* [, *&RestrictionArray*])	None.

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Function	***Returns***
CreateJavaArray(*ElementClassName[], NumberOfElements*)	Java object
CreateJavaObject(*ClassName* [*ConstructorParams*])	Java object
GetJavaClass(*ClassName*)	Java object

Mail Classes

This section lists the methods and properties as well as returns (if applicable) for the mail (MultiChannel Framework) classes.

Constructors

Constructor	***Returns***
MCFBodyPart()	MCFBodyPart object
MCFGetMail()	MCFGetMail object
MCFOutboundEmail()	MCFOutboundEmail object
MCFMailStore()	MCFMailStore object
SMTPSession()	SMTPSession object

MCFBodyPart Methods

Method	***Returns***
AddHeader(*HeaderName*, *HeaderValue*)	None.
GetHeader(*HeaderName*)	String
GetHeaderCount()	Number
GetHeaderName(*Index*)	String
GetHeaderNames()	String
GetHeaderValues(*Index*)	String
GetUnparsedHeaders()	String
SetAttachmentContent({*FilePath* | *FileURL*}, *FilePathType*, *FileName*, *FileDescr*, *OverrideContentType*, *OverrideCharset*)	None

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

MCFBodyPart Properties

Property	*Returns*
AttachmentURL	String
Charset	String
ContentType	String
Description	String
Disposition	String
Filename	String
FilePath	String
FilePathType	String
IsAttachment	Boolean RO
MultiPart	String
Text	String

MCFEmail Properties

Property	*Returns*
BCC	String
BounceTo	String
CC	String
From	String
Importance	String
Priority	Number
Recipients	String
RefIDs	String
ReplyIDs	String
ReplyTo	String

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
Sender	String
Sensitivity	String
Subject	String
Text	String

MCFGetMail Methods

Method	***Returns***
CreateQuarantineFolder ( )	Boolean
GetCount ( )	Number
GetEmailCount(*user*, *password*, *server*, *node*)	Number
ReadAllEmailHeadersWithAttach(*user*, *password*, *server*, *node*)	Rowset object
ReadEmails (*Count*)	String
ReadEmailsWithAttach(*User*, *password*, *server*, *node*, *count*)	Rowset object
ReadEmailsWithUID (*UID*)	Array of MCFInboundEmail objects
ReadEmailWithAttach(*User*, *password*, *server*, *node*, *UID*)	Rowset object
ReadHeaders ( )	Array of objects
RemoveEmail(*user*, *password*, *server*, *node*, *UID list*)	Boolean
RemoveEmails(*UID_List*)	String
SetMCFEmail (*user*, *password*, *server*, *node*)	None

MCFGetMail Properties

Property	***Returns***
AttachmentRoot	String
ContentTypes	String
ErrorCount	Number [RO]

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
IBNode	String
MailServer	String
Password	String
QuarantineCount	Number [RO]
QuarantineFolder	String
Status	String [RO]
UserID	String

MCFInboundEmail Methods

Method	***Returns***
DumpToFile (*&File*)	None
GetAttachments ( )	Array of objects
GetFrom ( )	Array of string
GetParts ( )	Array of objects
GetSender ( )	Array of string
ReadFromDatabase (*Email_ID*)	Boolean
SaveToDatabase ( )	Number

MCFInboundEmail Properties

Property	***Returns***
AttachList	String
AttachSizes	String
DttmReceived	String
DttmSaved	String
DttmSent	String
IBNode	String

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
Language	String
MessageID	String
NotifyCC	String
NotifyTo	String
OffsetReceived	Number
OffsetSent	String
Server	String
Size	Number
Status	String [RO]
UID	String
User	String

MCFMailStore Methods

Method	***Returns***
AuthorizeEmailAttach(*email ID*, *authentication name*, *authentication type* , *operation*)	Boolean
DeleteEmail*(email ID*, [*forced delete*])	Boolean
RetrieveEmail(*email ID*)	Rowset object
StoreEmail(*rowset*, *row*)	Number

MCFMailUtil Methods

Method	***Returns***
DecodeText (*TextToDecode*, *&DecodedText*)	Boolean
DecodeWord (*WordToDecode*, *&DecodedWord*)	Boolean
EncodeText (*TextToEncode*, *charset*, *EncodingStyle*, *&EncodedText*)	Boolean

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Method	***Returns***
EncodeWord (*WordToEncode*, *charset*, *EncodingStyle*, *&EncodedWord*)	Boolean
GetErrorMsgParam(*&index*)	String
IsDomainNameValid(*domainname*)	Boolean
IsEmailServerAvailable (*server*, *port*, *user*, *password*)	Boolean
ParseRichTextHtml(*richtext*)	Array of MCFBodyPart objects
ValidateAddress (*addresslist*)	Boolean

MCFMailUtil Properties

Property	***Returns***
badaddresses	Array of string[RO]
ErrorDescription	String [RO]
ErrorDetails	String[RO]
ErrorMsgParamsCount	Integer[RO]
imagesLocation	String
MessageNumber	Number [RO]
MessageSetNumber	Number [RO]

MCFMultiPart Methods

Method	***Returns***
AddBodyPart (*&bodyPart*)	None
GetBodyPart(*Index*)	MCFBodyPart object
GetContentType ( )	String
GetCount ( )	Number

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

MCFMultiPart Property

Property	***Returns***
SubType	String

MCFOutboundEmail Methods

Method	***Returns***
AddAttachment({*FilePath* | *FileURL*}, *FilePathType*, *FileName*, *FileDescr*, *OverrideContentType*, *OverrideCharset* [,*UploadPageTitle*])	None
AddHeader(*HeaderName*, *HeaderValue*)	None
GetErrorMsgParam(*&index*)	String
GetHeader(*HeaderName*)	Array of string
GetHeaderCount ()	Integer
GetHeaderName(*Index*)	String
GetHeaderNames ( )	String
GetHeaderValues (*Index*)	String
Send ( )	Number
SetSMTPParam(*ParamName*, *ParamValue*)	None

MCFOutboundEmail Properties

Property	***Returns***
BackupSMTPPort	Number
BackupSMTPServer	String
BackupSMTPSSLClientCertAlias	String
BackupSMTPSSLPort	Number
BackupSMTPUserName	String
BackupSMTPUseSSL	Boolean
BCC	String

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
BounceTo	String
CC	String
Charset	String
ContentLanguage	String
ContentType	String
DefaultCharSet	String
Description	String
Disposition	String
ErrorDescription	String [RO]
ErrorDetails	String
ErrorMsgParamsCount	Integer[RO]
Filename	String
FilePath	String
FilePathType	String
Importance	String
InvalidAddresses	String [RO]
IsAuthenticationReqd	Boolean
IsOkToSendPartial	Boolean
IsReturnReceiptReqd	Boolean
MessageNumber	Number [RO]
MessageSetNumber	Number [RO]
MultiPart	String
Priority	Number
Recipients	String

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
RefIDs	Number
ReplyIDs	Number
ReplyTo	String
ResultOfSend	Number [RO]
Sender	String
Sensitivity	String
SMTPPort	Number
SMTPServer	String
SMTPSSLClientCertAlias	String
SMTPSSLPort	Number
SMTPUserName	String
SMTPUserPassword	String
SMTPUseSSL	Boolean
StatusNotifyOptions	String
StatusNotifyReturn	String
Subject	String
Text	String
TimeToWaitForResult	Number
UsedDefaultConfig	Boolean [RO]
UsedPrimaryServer	Boolean [RO]
ValidSentAddresses	String [RO]
ValidUnsentAddresses	String [RO]

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SMTPSession Methods

Method	*Returns*
Send(*&Email*)	Constant
SendAll(*&Emails*)	Array of numbers
SetSMTPParam(*ParamName*, *ParamValue*)	None

SMTPSession Properties

Property	*Returns*
BackupPort	Number
BackupServer	String
BackupSSLClientCertAlias	String
BackupSSLPort	Number
BackupUserName	String
BackupUserPassword	String
BackupUseSSL	Boolean
IsAuthenticationReqd	Boolean
Port	Number
Server	String
SSLClientCertAlias	String
SSLPort	Number
UsedDefaultConfig	Boolean [RO]
UsedPrimaryServer	Boolean [RO]
UserName	String
UserPassword	String
UseSSL	Boolean

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

MCF IM Classes

This section lists the functions, methods, and properties, as well as returns (if applicable) for the MCF IM classes.

MCFIMInfo Functions

Function	***Returns***
CreateMCFIMInfo(*UserID*, *Network*)	MCFIMInfo object

MCFIMInfo Methods

Method	***Returns***
AddUser(*User*)	Boolean
CheckAll()	Boolean
GetAdditionalUserInfo()	String
GetErrorImageName()	String
GetOffLineImageName()	String
GetOnlineImageName()	String
GetUnknownImageName()	String
GetLaunchURL(*User*)	String
GetStatus(*User*)	Integer
RemoveUser(*User*)	Boolean

MCFIMSingleButton Methods

Method	***Returns***
generateHTML*(&RS*, *slide_dir*, *X_pos*, *Y_pos*, *width*, *height*, *seq_num*)	String
generateJavaScript()	String
insertXMPPServerUserData(*PS_user_ID*, *protocol*, *XMPP_domain*, *IM_user_ID*, *IM_pwd*)	Boolean
MCFIMSingleButton()	MCFIMSingleButton object

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Method	***Returns***
updateXMPPServerUserData(*PS_user_ID*, *protocol*, *XMPP_domain*, *IM_user_ID*, *IM_pwd*)	Boolean

MCFIMSingleButton Properties

Method	***Returns***
hideDelay	Integer

Message Classes

This section lists the functions, methods, and properties, as well as returns (if applicable) for the message classes.

Message Functions

Function	***Returns***
AddSystemPauseTimes(*StartDay*, *StartTime*, *EndDay*, *EndTime*)	Boolean
CreateMessage(**OPERATION**.*messagename* [,*Message_Type*])	Message object
DeleteSystemPauseTimes(*StartDay*, *StartTime*, *EndDay*, *EndTime*)	Boolean
GetNRXmlDoc(*NRID*, *EntityName*)	XmlDoc object
IBPurgeDomainStatus()	Boolean
IBPurgeNodeStatus()	Boolean
NodeDelete(*nodeName*)	Boolean
NodeRename(*oldNodeName*, *newNodeName*)	Boolean
NodeSaveAs(*oldNodeName*, *newNodeName*)	Boolean
PingNode(*MsgNodeName*)	Array of number
PSIGWServiceRequest(*&Req_XmlDoc*, *&Resp_XmlDoc*)	Integer
ReValidateNRXmlDoc(*NRID*, *EntityName*)	Boolean

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Message Methods

Method	***Returns***
Clone()	Message object
CopyPartRowset(*PartIndex*, *&Rowset*)	None.
CopyRowset(*source_rowset* [*, record_list*])	None
CopyRowsetDelta(*source_rowset* [*, record_list*])	None
CopyRowsetDeltaOriginal(*source_rowset*, [*, record_list*])	None
CreateNextSegment()	None
DeleteSegment(*Segment*)	None
ExecuteEdits([*editlevels*])	None
FirstCorrelation()	Boolean
GenXMLPartString(*PartIndex*)	String
GenXMLString()	String
GetContentString([*SegmentIndex*])	String
GetDocument([*segmented_messsage*])	Document object
GetPartAliasName(*PartIndex*)	String
GetPartName(*PartIndex*)	String
GetPartRowset(*PartIndex*)	Rowset object
GetPartVersion(*PartIndex*)	String
GetPartXmlDoc(*PartIndex*)	XmlDoc object
GetRowset([*version*])	Rowset object
GetSegment(*Segment*)	None
GetURIDocument()	Document object
GetURIResource([*index*])	String
GetXmlDoc()	XmlDoc object
LoadXMLPartString(*PartIndex*, *XmlString*)	None

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Method	***Returns***
LoadXMLString(*XMLString*)	None
OverrideURIResource(*string*)	None
Publish([*NodeName*] [, *Deferred_Mode*])	None
SegmentRestart(*TransactionID*, *Segment_index*, *segmentByDB*)	None
SetContentString(*string*)	Boolean
SetEditTable(*%PromptTable*, **RECORD**.*recname*)	None
SetRESTCache(*&futureDT*)	None
SetXmlDoc(*&XmlDoc*)	None
UpdateSegment()	None

Message Properties

Property	***Returns***
ActionName	String RO
AliasName	String RO
CurrentSegment	Number RO
DoNotPubToNodeName	String
HTTPMethod	Integer RO
HTTPResponseCode	Integer RO
IBInfo	IBInfo object RO
InitializeConversationId	Boolean
IsBulkLoadTruncation	Boolean RO
IsDelta	Boolean RO
IsEditError	Boolean RO
IsEmpty	Boolean RO

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
IsLocal	Boolean RO
IsOperationActive	Boolean RO
IsParts	BooleanRO
IsPartsStructured	BooleanRO
IsRequest	BooleanRO
IsSourceNodeExternal	BooleanRO
IsStructure	Boolean RO
Name	String RO
NRId	String RO
OperationName	StringRO
OperationVersion	StringRO
ParentTransactionId	StringRO
PartCount	NumberRO
PubNodeName	StringRO
QueueName	StringRO
QueueSeqId	NumberRO
ResponseStatus	Number RO
SegmentContentTransfer	String
SegmentContentType	String
SegmentCount	Number RO
SegmentsByDatabase	Boolean
Size	Number RO
TransactionId	StringRO
URIResourceIndex	Integer

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
Version	String[RO]

IntBroker System Variable

This section lists the system variables, as well as returns (if applicable) for the IntBroker class.

System Variable	***Returns***
%IntBroker	IntBroker object

IntBroker Methods

Method	***Returns***
Cancel(*TransactionId*, *QueueName*, *DataType*, *SegmentIndex* | *TransactionIdArray*, *QueueNameArray*, *DataTypeArray*, *SegmentIndexArray*)	Boolean
ConnectorRequest(*&Message*[, *process_exceptions*])	Message object
ConnectorRequestUrl(*URL*)	String
DeleteOrphanedSegments(*TransactionId*)	Boolean
DeleteRESTCache(*service_op*, *service_op_ver*	Boolean
GetArchData(*TransactionId*, *SegmentIndex*)	String
GetArchIBInfoData(*TransactionId*, *ParentTransactionId*)	String
GetIBInfoData(*TransactionId*, *DataType*)	String
GetIBTransactionIDforAE(*OperID*, *RunCtlID*)	String
GetMessage([*TransactionId*, *DataType*])	Message object
GetMessageErrors(*TransactionId*)	Array of string
GetMsgSchema(*MsgName*, *MsgVersion*)	String
GetSyncIBInfoData(*TransactionId*, *%LogType* [, *Archive*])	String
GetSyncLogData(*TransactionId*, *%LogType* [, *Archive*])	String
GetURL(*service_op_name*, *service_op_index*, *&doc_object*, [*secure_target*], [*encode_unsafe*])	String

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Method	***Returns***
InBoundPublish(*&Message*)	Boolean
IsOperationActive(*OperationName* [,*OperationVersion*])	Boolean
MsgSchemaExists(*MsgName*, *MsgVersion*)	Boolean
Publish(*&Message* [, *&ArrayofNodeNames*] [,*IsEnqueued*])	None.
Resubmit({*TransactionId*, *QueueName*, *DataType*, *SegmentIndex*} | {*TransactionIdArray*, *QueueNameArray*, *DataTypeArray*, *SegmentIndexArray*})	Boolean
SetMessageError(*TransactionID*, *MsgSet*, *MsgNumber*, *Error_Location*, *ParamListCounter*, [*Param*] ...)	Boolean
SetStatus(*&Message*, *Status*)	None
SwitchAsyncEventUserContext(*UserID*, *LanguageCode*)	Boolean
SyncRequest([*&MsgArray*, *&NodeNames*])	Array of messages
Update(*&Message*)	Boolean
UpdateXmlDoc(*&XmlDoc*, *TransactionId*, *DataType*)	Boolean

IBInfo Methods

Method	***Returns***
AddAEAttribute(*Name*, *value*	Boolean
AddAttachment(*Path*)	String
AddAttribute(*name*, *value*)	Boolean
AddContainerAttribute(*Name*, *Value*)	Boolean
ClearAEAttributes()	None
ClearAttachments()	None
ClearAttributes()	None
ClearContainerAttributes()	None
DeleteAEAttribute(*Name*)	Boolean

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Method	***Returns***
DeleteAttachment(*Index* | *Content_Id*)	Boolean
DeleteAttribute(*name*)	Boolean
DeleteContainerAttribute(*Name*)	Boolean
GetAEAttributeName(*nIndex*)	String
GetAEAttributeValue(*nIndex*)	String
GetAttachmentContentID(*Index*)	String
GetAttachmentProperty(*Content_ID*, *Property_Type*)	String
GetAttributeName(*nIndex*)	String
GetAttributeValue(*nIndex*)	String
GetContainerAttributeName(*nIndex*)	String
GetContainerAttributeValue(*nIndex*)	String
GetNumberofAEAttributes()	Integer
GetNumberOfAttributes()	Integer
GetNumberOfContainerAttributes()	Integer
GetTransactionIDforAE()	Number
InsertAEResponseAttributes()	Boolean
LoadConnectorProp(*ConnectorName*)	Boolean
LoadConnectorPropFromNode(*NodeName*)	Boolean
LoadConnectorPropFromRouting(*RoutingDefnName*)	Boolean
LoadRESTHeaders()	Boolean
SetAttachmentProperty(*Content_ID*, *Property_Type*, *Value*)	Boolean

IBInfo Properties

Property	***Returns***
AppServerDomain	String

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
CompressionOverride	String
ConnectorOverride	Boolean
ConversationId	String
DeliveryMode	Number
DestinationNode	String, RO
ExternalMessageID	Number RO
ExternalOperationName	String
ExternalUserName	String
ExternalUserPassword	String
FinalDestinationNode	String, RO
FuturePublicationDateTime	DateTime
HTTPSessionId	String
IBConnectorInfo	IBConnectorInfo collection object, RO
InReplyToID	String
MessageName	String, RO
MessageQueue	StringRO
MessageType	String, RO
MessageVersion	Number, RO
NodeDN	String, RO
NonRepudiationID	String, RO
NumberOfAttachments	String, RO
OperationType	String, RO
OperationVersion	String, RO
OrigNode	String, RO

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
OrigProcess	String, RO
OrigTimeStamp	String, RO
OrigUser	String, RO
RequestingNodeName	String, RO
RequestingNodeDescription	String, RO
ResponseAsAttachment	Boolean
SegmentsUnOrder	Boolean
SourceNode	String, RO
SyncServiceTimeout	Number
TransactionID	String, RO
UserIed	String, RO
VisitedNodes	Array of string, RO
WSA_Action	String
WSA_FaultTo	String
WSA_MessageID	String
WSA_ReplyTo	String
WSA_To	String

IBConnectorInfo Collection Methods

Method	***Returns***
AddConnectorProperties(*Name*, *Value*, *Type*)	Boolean
AddQueryStringArg(*Name*, *Value*)	Boolean
ClearConnectorProperties()	None
ClearQueryStringArgs()	None
DeleteConnectorProperties(*Name*)	Boolean

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Method	***Returns***
DeleteQueryStringArg(*Name*)	Boolean
GetConnectorPropertiesName(*Index*)	String
GetConnectorPropertiesType(*Index*)	String
GetConnectorPropertiesValue(*Index*)	String
GetNumberOf ConnectorProperties()	Number
GetNumberOfQueryStringArgs()	Number
GetQueryStringArgName(*Index*)	String
GetQueryStringArgValue(*Index*)	String

IBConnectorInfo Collection Properties

Property	***Returns***
ConnectorClassName	String
ConnectorName	String
Cookies	String
PathInfo	String
RemoteFrameworkURL	String

Notification Classes

This section lists the constructors, methods, and properties, as well as returns (if applicable) for the Notification, NotificationAddress, NotificationTemplate and WorklistEntry classes.

Constructors

Constructors	***Returns***
Notification(*NotifyFrom*, *dttmCreated*, *language_cd*)	Notification object
NotificationAddress(*Oprid*, *Description*, *Language*, *EmailId*, *Channel*)	NotificationAddress object
NotificationTemplate(*ComponentId*, *Market*, *TemplateId*, *TemplateType*)	NotificationTemplate object

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Constructors	***Returns***
OnAckForMarkedWorkedResp()	OnAckForMarkedWorkedResp object
WLEntryMarkedWorkedResp()	WLEntryMarkedWorkedResp object
WorkList()	Worklist object
WorklistEntry()	WorklistEntry object
WSWorklistEntry()	WSWorklistEntry object
WSWorklistEntryStatus()	WSWorklistEntryStatus object

Notification Class Method

Method	***Returns***
Send()	None

Notification Class Properties

Property	***Returns***
ContentType	String
dttmCreated	DateTime
EmailReplyTo	String
FileNames	Array of String
FileTitles	Array of String
language_cd	String
Message	String
NotifyBCC	Array of NotificationAddress objects
NotifyCC	Array of NotificationAddress objects
NotifyFrom	String
NotifyGuid	GUID
NotifyTo	Array of NotificationAddress objects
Rte	Boolean

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
SourceComponent	String
SourceMarket	String
SourceMenu	String
Subject	String
Template	String

NotificationAddress Properties

Property	***Returns***
Channel	String
Description	String
EmailId	String
Language	String
Oprid	String

NotificationTemplate Methods

Method	***Returns***
GetAndExpandTemplate(*Language*, *Vars*)	Boolean
SetupCompVarsAndRcpts(*&Rowset_Context*)	String
SetupGenericVars(*&AryValues*)	String

NotificationTemplate Properties

Property	***Returns***
ComponentId	String
Instruction	String
Language	String
Market	String

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
Priority	String
Responses	String
Subject	String
TemplateId	String
TemplateType	String
Text	String

Worklist Method

Method	***Returns***
Reassign*(FromOperid*, *ToOperid*)	Boolean

WorklistEntry Methods

Method	***Returns***
Create()	Number
GetResponseStatus()	Number
Reassign(*Operid*)	Boolean
Save()	Number
SaveWithCustomData(*&Message*, *&FieldNameArray*, *&FieldValueArray*)	Message object`
SelectByKey()	Boolean
SelectByMessageId()	Boolean
Update()	Number

WorklistEntry Properties

Property	***Returns***
actiondttm	DateTime
busactivity	String

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
buseventname	String
busprocname	String
commentshort	String
do_replicate_flag	String
instanceid	Number
instselectddttm	DateTime
inststatus	String
insttimeoutddttm	DateTime
instworkeddttm	DateTime
IsCreatedViaWebService	Boolean RO
oprid	String
originatorid	String RO
prevoprid	String
requestmessageid	String
ResponseStatus	String RO
syncid	Number
timedout	String
transactionid	Number
url	String
wl_priority	String
wldaystoselect	Number
wldaystowork	Number
worklistname	String

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

WSWorklistEntry Methods

Method	*Returns*
OnError(*&Message*)	Depends on implementation
OnNotify(*&Message*)	None

WSWorklistEntry Properties

Property	*Returns*
InstanceId	String RO
TransactionId	String RO

Optimization PeopleCode Classes

This section lists the functions, methods, and properties, as well as returns (if applicable) for the optimization PeopleCode classes.

Important! Optimization PeopleCode classes are not supported on IBM z/OS and Linux for IBM System z.

Functions

Function	*Returns*
CreateOptEngine(*probinst*, {**%Synch** | **%ASynch**} [, *detailedstatus*] [,*processinstance*])	OptEngine object
CreateOptInterface()	OptInterface object
DeleteOptProbInst(*probinst*[, *detailedstatus*])	Constant
GetOptEngine(*probinst*[, *detailedstatus*])	OptEngine object
GetOptProbInstList(*ProblemType* , *OutputErrorCode* [, *Prefix*] [, *detailedstatus*])	Array of string
InsertOptProbInst(*probinst, ProblemType*[, *detailedstatus*] [, *Description*])	Constant
IsValidOptProbInst(*probinst*[, *status*])	Constant

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

OptEngine Methods

Method	***Returns***
CheckOptEngineStatus()	Number
FillRowset(*PARAM_NAME, &Rowset* [, *functionstatus*])	Constant
GetDate(*PARAM_NAME*[,*status*])	Date
GetDateArray(*PARAM_NAME*)	Array of Date
GetDateTime(*PARAM_NAME*)	DateTime
GetDateTimeArray(*PARAM_NAME*)	Array of DateTime
GetNumber(*PARAM_NAME*)	Number
GetNumberArray(*PARAM_NAME*)	Array of number
GetString(*PARAM_NAME*)	String
GetStringArray(*PARAM_NAME*)	Array of string
GetTime(*PARAM_NAME*)	Time
GetTimeArray(*PARAM_NAME*)	Array of Time
GetTraceLevel(*component*)	Constant
RunAsynch(*TRANSACTION, PARM_PAIRS*)	Constant
RunSynch(*TRANSACTION, PARM_PAIRS*)	Constant
SetTraceLevel(*Component, Severity*)	Constant
ShutDown()	Constant

OptEngine Properties

Property	***Returns***
DetailMsgs	Array of String [RO]
DetailStatus	Constant

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

OptBase Methods

Method	***Returns***
GetParmDate(*ParmName*, *&ParmValue*)	Boolean
GetParmDateArray(*ParmName*, *&ParmValue*)	Boolean
GetParmDateTime(*ParmName*, *&ParmValue*)	Boolean
GetParmDateTimeArray(*ParmName*, *&ParmValue*)	Boolean
GetParmNumber(*ParmName*, *&ParmValue*)	Boolean
GetParmNumberArray(*ParmName*, *&ParmValue*)	Boolean
GetParmInt`(*ParmName*, *&ParmValue*)	Boolean
GetParmIntArray(*ParmName*, *&ParmValue*)	Boolean
GetParmString(*ParmName*, *&ParmValue*)	Boolean
GetParmStringArray(*ParmName*, *&ParmValue*)	Boolean
GetParmTime(*ParmName*, *&ParmValue*)	Boolean
GetParmTimeArray(*ParmName*, *&ParmValue*)	Boolean
Init()	Boolean
OptDeleteCallback(*&record*)	Boolean
OptInsertCallback(*&Record*)	Boolean
OptPostUpdateCallback(*&OldRecord*, *&NewRecord*)	Boolean
OptPreUpdateCallback(*&OldRecord*, *&NewRecord*)	Boolean
OptRefreshCallback()	Boolean
SetOutputParmDate(*ParmName*, *&ParmValue*)	Boolean
SetOutputParmDateArray(*ParmName*, *&ParmValue*)	Boolean
SetOutputParmDateTime(*ParmName*, *&ParmValue*)	Boolean
SetOutputParmDateTimeArray(*ParmName*, *&ParmValue*)	Boolean
SetOutputParmNumber(*ParmName*, *&ParmValue*)	Boolean
SetOutputParmNumberArray(*ParmName*, *&ParmValue*)	Boolean

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Method	***Returns***
SetOutputParmInt(*ParmName*, *&ParmValue*)	Boolean
SetOutputParmIntArray(*ParmName*, *&ParmValue*)	Boolean
SetOutputParmString(*ParmName*, *&ParmValue*)	Boolean
SetOutputParmStringArray(*ParmName*, *&ParmValue*)	Boolean
SetOutputParmTime(*ParmName*, *&ParmValue*)	Boolean
SetOutputTimeArray(*ParmName*, *&ParmValue*)	Boolean

OptInterface Methods

Method	***Returns***
ActivateModel(*ModelID*, *SolverSettingID*	Constant
ActivateObjective(*Model_Name*, *Objective_Name*)	Constant
DeactivateModel(*ModelId*)	Constant
DumpMsgToLog(*LogSeverity*, *Message*)	None
FindRowNum(*&Record*[, *StartRow*[, *EndRow* [, *field_list*]]]	Number
GetSolution(*ModelId*, *varArrayId*, *SkipZero* [, *KeyFieldNames, KeyFieldValues*[, *Sollution*]]	Constant
GetSolutionDetail(*ModelId*, *SolutionType*, *Name*, *&Solution*)	Constant
IsModelActive(*ModelId*)	Boolean
RestoreBounds(*ModelId*[, *varArrayId*])	Constant
SetVariableBoungs(*ModelId*, *varArrayId*,*BoundType*, *LowerBound*, *UpperBound*, *&KeyRecord*[, *ChangeModelBounds*])	Constant
SetVariableType(*ModelId*, *varArrayId*, *varType*)	Constant
Solve(*ModelId*, *SolutionType*[, *objValue*[, *name-value_pairs*]])	Constant

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Page Class

This section lists the functions, methods, and properties, as well as returns (if applicable) for the page class.

Function

Function	***Returns***
GetPage(**PAGE**.*pagename*)	Page object

Properties

Property	***Returns***
CopyURLLink	Boolean
CustomizePageLink	Boolean
DisplayOnly	Boolean RO
HelpLink	Boolean
Name	String RO
NewWindowLink	Boolean
Visible	Boolean

PeopleSoft Search Framework Classes

This section lists the methods and properties, as well as returns (if applicable) for the PeopleSoft Search Framework classes.

PeopleSoft Search Framework Classes Built-in Functions

Function	***Returns***
EncodeSearchCode(*search_string*)	String

AssociatedFacet Methods

Method	***Returns***
getAssociatedFacetValue(*category, facet, user*)	String

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

FacetFilter Methods

Method	***Returns***
clearFacetSorting()	None
FacetFilter(*FacetName*, *Path*)	FacetFilter object
getFacetSortings()	StringMap object
getFacetValuesSortType(*level*)	String
hasCustomFacetSorting(*level*)	Boolean
sortFacetValuesAlphabetically(*level, sort_ascending*)	None
sortFacetValuesByDocumentCount(*level, sort_ascending*)	None
sortFacetValuesByTypet(*level, sort_type*)	None
sortFacetValuesNumerically(*level, sort_ascending*)	None

FacetFilter Properties

Property	***Returns***
AssociationValue	String
FacetLabel	String
FacetName	String
Path	String

FacetNode Methods

Method	***Returns***
addChild(*&node*	None
FacetNode(*FacetName*, *NodeName*, *Path*, *DisplayValue*, *DocCount*)	FacetNode object
getChildNodes()	Array of FacetNode objects

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

FacetNode Properties

Property	***Returns***
DisplayValue	String
DocumentCount	Integer
FacetValue	String
HasChildren	Boolean

SearchAttribute Methods

Method	***Returns***
SearchAttribute(*Name*, *Type*)	SearchAttribute object

SearchAttribute Properties

Property	***Returns***
Display	String
Name	String
Type	String

SearchCategory Methods

Method	***Returns***
GetAllAttributes()	Array of SearchAttribute objects
GetConfiguredFilterAttributes()	Array of SearchAttribute objects
GetFacetFilters()	Array of FacetFilter objects
GetLastIndexedDateTime()	DateTime
GetNonConfiguredFilterAttributes()	Array of SearchAttribute objects
GetRequestedAttributes()	Array of SearchAttribute objects
GetRequestedFields()	Array of SearchField objects
SearchCategory(*Name*)	SearchCategory object

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SearchCategory Properties

Property	***Returns***
DataSourceNames	Array of string RO
Displayname	String RO
Duplicates	String RO
IsDeployed	Boolean RO
Name	String RO
ServiceName	String RO

SearchFactory Methods

Method	***Returns***
CreateQueryService(*name*	SearchQueryService object
SearchFactory()	SearchFactory object

SearchFactory Properties

Property	***Returns***
DEFAULTSERVICE	String RO

SearchField Methods

Method	***Returns***
getAsDate()	Date
getAsDateTime()	DateTime
getAsInteger()	Integer
getAsNumber()	Number

SearchField Properties

Property	***Returns***
Name	String RO

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
Type	String RO
Value	String RO

SearchFieldCollection Methods

Method	***Returns***
Count()	Integer
First()	SearchField object
Item(*index*)	SearchField object
ItemByName(*name*)	SearchField object
Next()	SearchField object

SearchFilter Methods

Method	***Returns***
setDateFilter(*date*)	None
setDateTimeFilter(*datetime*)	None

SearchFilter Properties

Property	***Returns***
Field	SearchField object
FilterConnector	String RO
Filters	Array of SearchFilter objects RO
Operator	String
Value	String

SearchFilterGenerator Methods

Method	***Returns***
AddQueryFilter(*&srch_qry*)	None

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Method	***Returns***
AfterDate(*srch_field, date*)	None
BeforeDate(*srch_field, date*)	None
ContainsPartialWord(*srch_field, fragment*)	None
ContainsPhrase(*srch_field, phrase*)	None
ContainsWord(*srch_field, word*)	None
DateToDatetime(*date*)	DateTime
EndMatchAll()	None
EndMatchAny()	None
EqualsDate(*srch_field, date*)	None
EqualsNumber(*srch_field, number*)	None
EqualsString(*srch_field, string*)	None
GreaterThanEqualsNumber(*srch_field, number*)	None
GreaterThanNumber(*srch_field, number*)	None
LessThanEqualsNumber(*srch_field, number*)	None
LessThanNumber(*srch_field, number*)	None
MatchAll()	None
MatchAllReturnTrue()	Boolean
MatchAny()	None
MatchAnyReturnTrue()	Boolean
NotEqualsDate(*srch_field, date*)	None
NotEqualsNumber(*srch_field, number*)	None
NotEqualsString(*srch_field, string*)	None
OnOrAfterDate(*srch_field, date*)	None
OnOrBeforeDate(*srch_field, date*)	None

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Method	***Returns***
SearchFilterGenerator()	None
SetQueryFilter(*&srch_qry*)	None
StringDateToDatetime(*str_date*)	DateTime

SearchQuery Methods

Method	***Returns***
BrowseFacetNodes()	Array of FacetNode objects
Execute(*start*, *size*)	SearchResultCollection object
FormatDateFilter(*datefilter*)	String
FormatDateTimeFilter(*datetmfilter*)	String

SearchQuery Properties

Property	***Returns***
Categories	Array of SearchCategory objects
ContainsAnyWords	String
ContainsExactPhrase	String
ClusteringSpecs	Reserved for future use
DocsRequested	Integer
EnableExtendedFilterOperators	Boolean
FacetFilters	Array of FacetFilter objects
FilterConnector	String
Filters	Array of SearchFilter objects
GroupingSpec	Reserved for future use
Language	String
MarkDuplicates	Boolean
MaximumNumberOfFacetValues	Integer

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
MinmumDocumentsPerFacetValue	Integer
ProgrammaticSearchString	String
QueryText	String
RemoveDuplicates	Boolean
RequestedFields	Array of SearchField objects
ReturnFacetValueCounts	Boolean
SearchWithIn	String
SortFacetValuesBy	String
SortSpecs	Reserved for future use
StartIndex	Integer
TopN	Reserved for future use
WithoutWords	String

SearchQueryCollection Methods

Method	***Returns***
addQuery(*&srch_qry*)	None
Count()	Integer
ExecuteQuerys()	Array of SearchResultsCollection objects
First()	SearchQuery object
Item(*index*)	SearchQuery object
Next()	SearchQuery object

SearchQueryService Methods

Method	***Returns***
CreateQuery()	SearchQuery object
CreateQueryCollection()	SearchQueryCollection object

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Method	***Returns***
ExecuteQuery(*&query*)	SearchResultCollection object
ExecuteQuerys(*&srch_qry_coll*)	Array of SearchResultCollection objects

SearchResult Methods

Method	***Returns***
GetCategoryNames()	Array of string
GetContentLength()	Integer
GetCustomAttributes()	SearchFieldCollection object
GetLanguage()	String
GetLastModified()	DateTime
GetScore()	Integer
GetSignature()	Integer
GetSummary()	String
GetTitle()	String
GetUrlLink()	String
HasDuplicate()	Boolean
IsDuplicate()	Boolean

SearchResultCollection Methods

Method	***Returns***
First()	SearchResult object
GetDocumentCount()	Integer
GetDuplicatesMarked()	Boolean
GetDuplicatesRemoved()	Boolean
GetEstimatedHitCount()	Integer
GetFacetNodes()	Array of FacetNode objects

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Method	***Returns***
GetQueryObject()	SearchQuery object
GetQueryText()	String
GetStartIndex()	Integer
Item(*index*)	SearchResult object
Next()	SearchResult object

SearchAuthnQueryFilter Methods

Method	***Returns***
evaluateAttrValues(*SBO_name*, *attr*, *user_ID*)	Array of string

Portal Registry Classes

See Portal Registry Classes Methods and Properties.

PostReport Class

This section lists the functions, methods, and properties, as well as returns (if applicable) for the PostReport class.

Function

Function	***Returns***
SetPostReport()	PostReport object

Methods

Method	***Returns***
AddDistributionOption(*DistIdType*, *DistId*)	Number
Put()	None

Properties

Property	***Returns***
ExpirationDate	Date

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
OutDestFormat	String
ProcessInstance	Number
ProcessName	String
ProcessType	String
ReportDesc	String
ReportFolder	String
ReportId	Number
ServerName	String

Process Request Classes

This section lists the functions, methods, and properties, as well as returns (if applicable) for the ProcessRequest class and the related PrcsApi class.

ProcessRequest Functions

Function	***Returns***
CreateProcessRequest([*ProcessType*, *ProcessName*])	ProcessRequest object
GetNextProcessInstance([*Commit*])	Number
SetupScheduleDefnItem(*ScheduleName, JobName*)	ProcessRequest object

ProcessRequest Methods

Method	***Returns***
AddDistributionOption(*DistIdType*, *DistId* [, *JobName*] [, *PrcsItemLevel*] [, *JobSeqNo*])	Number
AddNotifyInfo(*field_name*, *field_value* [, *JobName*] [, *PrcsItemLevel*] [, *JobSeqNo*])	None
PrintJobHTMLRpt()	String

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Method	***Returns***
PrintJobRqstRpt(*ProcessInstance*, *ItemInstance* [, *PrintJobTree*] [, *PrintDistList*] [, *PrintNotifyList*] [, *PrintSystemMessage*] [, *PrintApplicationMessage*] [, *PrintParamList*])	String
PrintSchdlHTMLRpt([*PrintJobTree*] [, *PrintDistList*] [, *PrintNotifyList*] [, *PrintMessageList*] [, *PrintParamList*])	String
RunJobSetNow()	None
Schedule()	None
SetEmailOption(*EmailSubject*, *EmailText*, *EmailAddress*, *EmailWebReport*, *EmailAttachLog* [, *JobName*] [, *PrcsItemLevel*] [, *JobSeqNo*])	None
SetItemFolder(*PortalFolder* [, *JobName*] [, *PrcsItemLevel*] [, *JobSeqNo*])	None
SetNotifyAppMethod(*app_class_name*, *app_class_method* [, *JobName*] [, *PrcsItemLevel*] [, *JobSeqNo*])	None
SetNotifyService(*srvc_op_name*[, *JobName*] [, *PrcsItemLevel*] [, *JobSeqNo*])	None
SetOutputOption(*OutputType*, *OutputFormat*, *OutputDest* [, *JobName*][, *PrcsItemLevel*] [, *JobSeqNo*])	None
UpdateRunStatus()	None

ProcessRequest Properties

Property	***Returns***
EmailAttachLog	Boolean
EmailSubject	String
EmailText	String
EmailWebReport	Boolean
FileName	String
JobName	String
LanguageCd	String

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
NotifyTextMsgNum	Number
NotifyTextMsgSet	Number
OutDest	String
OutDestFormat	String
OutDestType	String
PortalFolder	String
ProcessInstance	Number
ProcessName	String
ProcessType	String
RunControlID	String
RunDateTime	DateTime
RunLocation	String
RunRecurrence	String
RunStatus	Number
Status	Number [RO]
TimeZone	String

PrcsApi Constructor

Constructor	***Returns***
PrcsApi()	PrcsApi object

PrcsApi Methods

Method	***Returns***
getAllFileNames(*PrcsInstance*)	Array of string
notifyToWindows(*PrcsInstance*, *Message*)	Number

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Query Classes

See Query Classes Methods and Properties.

Record Class

This section lists the functions, methods, and properties, as well as returns (if applicable) for the Record class.

Functions

Function	***Returns***
CreateRecord(**Record**.*recname*)	Record object
GetRecord([**Record**.*recname*])	Record object

Methods

Method	***Returns***
CompareFields(*&Record*)	Boolean
CopyChangedFieldsTo(*&Record*)	None
CopyFieldsTo(*&Record*)	None
Delete()	Boolean
ExecuteEdits([*EditLevel*])	None
GetField({*n* | **Field**.*fieldname*})[D]	Field object
Insert()	Boolean
Save([*CopyToOriginal*])	Boolean
SearchClear()	None
SelectByKey([*UseChangedBuffers*])	Boolean
SelectByKeyEffDt(*Date* [, *UseChangedBuffers*])	Boolean
SetDefault()	None
SetEditTable(*%PromptField*, **Record**.*recname*)	None
Update([*KeyRecord*])	Boolean

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Properties

Property	***Returns***
FieldCount	Number [RO]
fieldname	Field object [RO]
IsChanged	Boolean [RO]
IsDeleted	Boolean [RO]
IsEditError	Boolean [RO]
Name	String [RO]
ParentRow	Row object [RO]
RelLangRecName	String [RO]

Row Class

This section lists the functions, methods, and properties, as well as returns (if applicable) for the Row class.

Function

Function	***Returns***
GetRow()	Row object

Methods

Method	***Returns***
CopyTo(*&Row*)	Row object
GetNextEffRow()	Row object
GetPriorEffRow()	Row object
GetRecord({*n*| **Record**.*recname*})[D]	Record object
GetRowset({*n* | **Scroll**.*scrollname*})	Rowset object
scrollname(*n*)	Row object

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Properties

Property	***Returns***
ChildCount	Number RO
DeleteEnabled	Boolean
IsChanged	Boolean RO
IsDeleted	Boolean RO
IsEditError	Boolean RO
IsNew	Boolean RO
ParentRowset	Rowset object RO
recname	Record object RO
RecordCount	Number RO
RowNumber	Number RO
Selected	Boolean
Style	String
Visible	Boolean

Rowset Class

This section lists the functions, methods, and properties, as well as returns (if applicable) for the Rowset class.

Functions

Function	***Returns***
CreateRowset({**Record**.*recname* | *&Rowset*} [, {**Field**.*fieldname*, **Record**.*recname* | *&Rowset*}] . . .)	Rowset object
GetLevel0()	Rowset object
GetRowset([**Scroll**.*scrollname*])	Rowset object

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Methods

Method	***Returns***
ClearDeletesChanges()	None
CopyTo(*&DestRowset* [, **Record**.*SourceRecname*, **Record**.*DestRecname*]. . .)	Number (optional)
DeleteRow(*n*)	Boolean
Fill([*wherestring* [, *bindvalue*] . . .])	Number (optional)
FillAppend([*wherestring* [, *bindvalue*] . . .])	Number
Flush()	None
FlushRow(*n*)	None
GetCurrEffRow()	Row object
GetFirstUserSortedRow(*GridName*)	Row object
GetLastUserSortedRow(*GridName* [, *visible*])	Row object
GetNewEffRow()	Row object
GetRow(*n*)[D]	Row object
HideAllRows()	None
InsertRow(*n*)	Boolean
IsUserSorted(*GridName*)	Boolean
MapBufRowToUserSortRow(*GridName*, *number*)	Number
MapUserSortRowToBufRow(*GridName*, *number*)	Number
Refresh()	None
Select([*parmlist*], **Record**.*selrecord* [, *wherestr*, *bindvars*])	Number
SelectNew([*parmlist*], **Record**.*selrecord* [, *wherestr*, *bindvars*])	Number
SetDefault(*recname.fieldname*)	None
ShowAllRows()	None
Sort([*paramlist*,] *sort_fields*)	None

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Properties

Property	*Returns*
ActiveRowCount	Number RO
ChangeOnInit	Boolean
DataAreaCollapsed	Boolean
DBRecordName	String RO
DeleteEnabled	Boolean
EffDt	Date RO
EffSeq	Number RO
InsertEnabled	Boolean
IsEditError	Boolean RO
Level	Number RO
Name	String RO
ParentRow	Row object RO
ParentRowset	Rowset object RO
RowCount	Number RO
SetComponentChanged	Boolean
TopRowNumber	Number RO

RowsetCache Class

This section lists the functions, methods, and properties, as well as the returns (if applicable) for the RowsetCache class.

Functions

Function	*Returns*
CreateRowsetCache(*&Rowset*, [**Rowset.**]*Name*, *Description*)	RowsetCache object
GetRowsetCache(([**Rowset.**]*name*)	RowsetCache object

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Methods

Method	***Returns***
Delete()	Boolean
Get()	Rowset object
Save([[**Rowset.**]*name*] [, *Description*] [, *Lang*])	Boolean

Properties

Property	***Returns***
Content	Rowset object
Description	String

Search Classes

PeopleTools and PeopleCode support two search deployment methodologies: the PeopleSoft Search Framework and Verity-based search.

See PeopleSoft Search Framework Classes.

See Verity Search Classes Methods and Properties.

Security Authorization Classes

This section lists the methods and properties, as well as returns (if applicable) for the security authorization classes.

AuthRequest Methods

Method	***Returns***
GetParameterValue(*name*)	String

AuthRequest Properties

Property	***Returns***
Access	String
UserId	String

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SecurityHandler Methods

Method	*Returns*
GetAuthorization(*&AuthReq_array*)	None

Session Classes

See Session Classes.

SOAPDoc Class

This section lists the functions, methods, and properties, as well as returns (if applicable) for the SOAPDoc class.

Function

Function	*Returns*
CreateSOAPDoc()	SOAPDoc object

Methods

Method	*Returns*
AddBody()	None
AddEnvelope(*SOAP_Schema*)	None
AddFault(*Fault_Code*, *Fault_String*)	None
AddHeader()	None
AddMethod(*MethodName*, *IsRequest*)	None
AddParm(*ParmName*, *ParmValue*)	None
GetParmName(*Index*)	String
GetParmValue(*Index*)	String
ValidateSOAPDoc([1])	String

Properties

Property	*Returns*
BodyNode	XmlNode object [RO]

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
EnvelopeNode	XmlNode object RO
FaultCode	Number RO
FaultCodeS	String RO
FaultString	String RO
HeaderNode	XmlNode object RO
MethodName	String RO
MethodNode	XmlNode object RO
ParmCount	Number RO
XmlDoc	XmlDoc object

SQL Class

This section lists the functions, methods, and properties, as well as returns (if applicable) for the SQL class.

Functions

Function	***Returns***
CreateSQL([{*sqlstring*| **SQL**.*SqlName*} [, *paramlist*]])	None
DeleteSQL([**SQL**.]*sqlname* [, *dbtype* [, *effdt*]]])	Boolean
FetchSQL([**SQL**.]*sqlname* [, *dbtype* [, *effdt*]])	String
GetSQL(**SQL**.*sqlname* [, *paramlist*])	SQL object
StoreSQL(*sqlstring*, [**SQL**.]*sqlname* [, *dbtype* [, *effdt* [, *ownerId* [, *Description*]]]])	None

Methods

Method	***Returns***
Close()	Boolean
Execute(*paramlist*)	Boolean

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Method	***Returns***
Fetch(*paramlist*)	Boolean
Open(*sql* [, *paramlist*])	None

Properties

Property	***Returns***
BulkMode	Boolean
IsOpen	Boolean RO
LTrim	Boolean
ReuseCursor	Boolean
RowsAffected	Number RO
Status	Number RO
TraceName	String
Value	String RO

TransformData Class

This section lists the variables, properties, and returns (if applicable) for the TransformData class.

System Variable

System Variable	***Returns***
%TransformData	TransformData object

Properties

Property	***Returns***
DestMsgName	String RO
DestMsgVersion	String RO
DestNode	String RO
RejectTransform	Number

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
RoutingDefnName	String RO
SourceMsgName	String RO
SourceMsgVersion	String RO
SourceNode	String RO
Status	Number
XmlDoc	XmlDoc object

Tree Classes

See Tree Classes Methods and Properties.

Universal Queue Classes

This section lists the built-in functions, constructors, methods, and properties as well as returns (if applicable) for the universal queue classes (MultiChannel Framework).

Universal Queue Built-in Functions

Function	***Returns***
DeQueue(*physical queue ID*, *task type*, *task number*, *agent ID*)	Number
EnQueue(*logical queue* , *task type*, *Relative URL*, *Language _Code* [,*subject*][, *agent ID*][, *overflow timeout*][, *escalation timeout*][, *cost*][, *priority*][, *skill level*])	Number
Forward(*from physical queue ID*, *from agent ID*, *task number*, *task type*, *to logical queue ID*[, *to agent ID*])	Number
InitChat(*logical queue ID*, *application data URL*, *customer username*, [*chat_subject*][, *chat_question*][, *wizard_URL*][, *priority*][, *skill_level*] [, *cost*])	Number
MCFBroadcast(*ClusterID*,*QueueID*, *ChannelID*, *AgentState*, *AgentPresence*, *Message*, *MessageSetNumber*, *MessageNumber*, *DefaultMessage*, *SecurityLevel*, *ImportanceLevel*, *SenderId*, *NameValueString*)	None.
NotifyQ(*logical queue ID*, *task type*)	Number

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Universal Queue Constructors

Constructor	***Returns***
Agent(*AgentID*)	Agent object
AgentPhysQueueProps()	Agent physical queue properties object
AgentPhysQueueTasks(*PhysicalQueueID*, *AgentID*)	Agent physical queue tasks object
LogicalQueue(*LogicalQueueID*)	Logical queue object
MCFFactory([*MAX_TASKLIST_ITEMS*])	MCFFactory object
PhysicalQueue(*PhysicalQueueID*)	Physical queue object
Task(*TaskNumber*)	Task object
TaskList(*Status*, *TaskType*, [*PhysicalQueueID*[, *AgentID*]])	Task list object
Util()	Util object

Agent Methods

Method	***Returns***
Delete()	Number
Refresh()	None
RefreshQTaskList(*PhysQ*)	None

Agent Properties

Property	***Returns***
AgentID	String RO
AgentProps	AgentPhysQueueProps object RO
AgentTasks	AgentPhysQueueTask object RO
Buddy	Array of string RO
Language	Array of string RO
Name	String RO
Nickname	String RO

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	*Returns*
PhysicalQueueID	Array of string RO
TotalPhysicalQueues	Number RO

AgentPhysQueueProps Properties

Property	*Returns*
AgentID	String RO
PhysicalQueueID	String RO
SkillLevel	String RO
WorkLoad	Number RO

AgentPhysQueueTasks Method

Method	*Returns*
Refresh(*TaskList*)	None.

AgentPhysQueueTasks Properties

Property	*Returns*
AcceptedTaskList	Task list object RO
AssignedTaskList	Task list object RO
PhysicalQueueID	String RO

LogicalQueue Properties

Property	*Returns*
LogicalQueueID	String RO
PhysicalQueueID	Array of PhysicalQueue objects RO

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

MCFFactory Property

Property	***Returns***
LogicalQueue	Array of LogicalQueue objects RO

PhysicalQueue Methods

Method	***Returns***
Refresh()	None
RefreshTaskList(*TaskList*)	None.

PhysicalQueue Properties

Property	***Returns***
AcceptedTaskList	Task list object RO
AssignedTaskList	Task list object RO
Agent	Array of agent objects RO
BrowserURL	String RO
EnqueuedTaskList	Task list object RO
EscalatedTaskList	Task list object RO
InternalURL	String RO
IsActive	Boolean RO
LogicalQueueID	String RO
OverflowedTaskList	Task list object RO
PhysicalQueueID	String RO
RENURLID	String RO
TotalAgents	Number RO

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Task Methods

Method	***Returns***
Close(*Comment*)	None
Enqueue(*LogicalQueueID*,*AgentID*, *Timeout*, *ResponseTime*, *Cost*, *Priority*, *MinSkill*)	None.
Refresh()	None
RefreshStatus()	None

Task Properties

Property	***Returns***
AgentID	String RO
ApplicationData	String RO
Comments	String
EnqueueTime	DateTime RO
EscalationTime	DateTime RO
Language	String RO
OriginalTime	DateTime RO
OverflowTime	DateTime RO
PhysicalQueueID	String RO
TiedAgentID	String RO

TaskList Method

Method	***Returns***
Refresh()	None

TaskList Properties

Property	***Returns***
AgentID	String RO

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
PhysicalQueueID	String RO
Task	Array of tasks RO
TaskType	String RO
Total	Number RO

XmlDoc Classes

This section lists the functions, methods, and properties, as well as returns (if applicable) for the XmlDoc class and the XmlNode class.

XmlDoc Classes Functions

Function	***Returns***
CreateXmlDoc(*XmlString*)	XmlDoc object
GetNRXmlDoc(*NRID*, *NodeName*)	XmlDoc object
RevalidateNRXmlDoc(*NRID*, *EntityName*	Boolean
Transform(*Input, AE_Program_Name*, *Initial_Node_Name*, *Initial_Message__Name*, *Initial_Message_Version*, *Result _Node_Name*, *Result_Message_Name*,*Result_Message_ Version*)	XmlDoc object
TransformEx(*XmlString*, *XsltString*)	String

XmlDoc Class Methods

Method	***Returns***
CopyRowset(*&InRowset*[, *MessageName*] [, *MessageVersion*])	Boolean
CopyToPSFTMessage(*targetDoc, srcPath, targetPath*)	Number
CopyToRowset(*&InRowset*[, *Message_Name*][, *Message_ Version*])	Boolean
CreateDocumentElement(*TagName* [, *NamespaceURI*] [, *&DocType*])	XmlNode object
CreateDocumentType(*Name*, *PublicID*, *SystemID*)	String

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Method	***Returns***
GenFormattedXmlString()	String
GenXmlFile(*path*)	Boolean
GenXmlString()	String
GetElementsByTagName(*TagName*)	Array of XmlNode objects
LoadIBContent(*Content*[, *RootTagName*])	Boolean
ParseXmlFromURL(*path*)	Boolean
ParseXmlString(*XmlString*)	Boolean

XmlDoc Class Properties

Property	***Returns***
DocumentElement	XmlNode object [RO]
IsNull	Boolean [RO]

XmlNode Class Methods

Method	***Returns***
AddAttribute(*Name*, *Value*)	None
AddAttributeNS(*NamespaceURI*, *AttributeName*, *Value*)	None
AddCDataSection(*Data*)	XmlNode object
AddComment(*Text*)	XmlNode object
AddElement(*TagName*)	XmlNode object
AddElementNS(*NameSpaceURI*, *TagName*)	XmlNode object
AddEntityReference(*Name*)	XmlNode object
AddNode(*XmlNode*)	XmlNode object
AddProcessInstruction(*Target*, *Data*)	XmlNode object
AddText(*Data*)	XmlNode object
CopyNode(*Node*)	None

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Method	***Returns***
FindNode(*Path*)	XmlNode object
FindNodes(*Path*)	Array of XmlNode objects
GenXmlString()	String
GetAttributeName(*index*)	String
GetAttributeValue({*Name* | *Index*})	String
GetCDataValue()	String
GetCDataValues()	Array of string
GetChildNode(*index*)	XmlNode object
GetElement()	XmlNode object
GetElements()	Array of XmlNode objects
GetElementsByTagName(*TagName*)	Array of XmlNode objects
GetElementsByTagNameNS(*NamespaceURI*, *TagName*)	Array of XmlNode objects
InsertCDataSection(*Data*, *Position*)	XmlNode object
InsertComment(*Data*, *Position*)	XmlNode object
InsertElement(*TagName*, *Position*)	XmlNode object
InsertElementNS(*NameSpaceURI*, *TagName*, *Position*)	XmlNode object
InsertEntityReference(*Name*, *Position*)	XmlNode object
InsertNode(*&NewNode*, {*&RefNode* | *Position*})	XmlNode object
InsertProcessInstruction(*Target*, *Data*, *Position*)	XmlNode object
InsertText(*Data*, *Position*)	XmlNode object
RemoveAllChildNode()	None
RemoveChildNode({*Position* | *Node*})	XmlNode object

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

XmlNode Class Properties

Property	*Returns*
AttributesCount	Number RO
ChildNodeCount	Number RO
Index	Number RO
IsNull	Boolean RO
LocalName	String RO
NamespaceURI	String RO
NextSibling	XmlNode object RO
NodeName	String
NodePath	String RO
NodeType	String RO
NodeValue	String
ParentNode	XmlNode object RO
Prefix	String RO
PreviousSibling	XmlNode object RO

Session Classes

This section lists:

- Session classes methods and properties
- Component interface classes methods and properties
- Verity search classes methods and properties
- Portal registry classes methods and properties
- Query classes methods and properties
- Tree classes methods and properties

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Session Classes Methods and Properties

A session object controls access to the PeopleSoft APIs as well as the environment in which they run. This section only lists the system variable, methods, and properties, as well as returns (if applicable) for the session class and the associated classes used for controlling the environment. The properties, methods, and so of the API objects (query classes, tree classes, and so on) are detailed in separate sections.

Session System Variable

System Variable	***Returns***
%Session	Session object

Session Methods

Method	***Returns***
AdvancedSearchQueries(*GetFavorites*, *QueryName*, *QueryNameOp*, *Descr*, *DescrOp*, *FolderName*, *FolderNameOp*, *RecordName*, *RecordNameOp*, *FieldName*, *FieldNameOp*, *TreeName*, *TreeNameOp*, *QueryType*, *OwnerType*, *CaseSensitive*)	Query collection
AdvancedSearchRecords(*RecordName*, *RecordNameOp*, *Descr*, *DescrOp*, *FieldName*, *FieldNameOp*, *TreeName*, *TreeNameOp*, *CaseSensitive*)	QueryDBRecord collection
FindCompIntfcs(*ComponentName*)	Component Interface collection
FindPortalRegistries(*partial_name*)	PortalRegistry collection
FindQueryDBRecords()	QueryDBRecord collection
FindQueries()	Query collection
FindQueriesDateRange(*StartDateString*, *EndDateString*)	Query collection
GetActualRemoteNodes()	Remote node collection
GetCompIntfc([**COMPINTFC.**]*ComponentName*)	Component Interface object
GetLocalNode()	Node object
GetNodes()	Node collection
GetPortalRegistry()	PortalRegistry object
GetQuery()	Query object
GetQuerySecurityProfile()	QuerySecurityProfile object

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Method	***Returns***
GetRemoteNodes()	Node collection
GetSearchIndexes()	SearchIndexes collection
GetSearchQuery()	SearchQuery object
GetTree()	Tree object
GetTreeStructure()	Tree structure
SearchQueryDBRecord(*SearchType*, *Pattern*, *CaseSensitive*)	QueryDBRecord collection
SearchPrivateQueries(*QueryType, UserId, SearchType*, *Pattern*, *CaseSensitive*)	Query collection
SearchPublicQueries(*QueryType, SearchType*, *Pattern*, *CaseSensitive*)	Query collection
ValidateCompIntfc(*ComponentInterfaceName*)	Integer

Session Properties

Property	***Returns***
ErrorPending	Boolean [RO]
PSMessages	PSMessage collection object
PSMessageMode	Number
RegionalSettings	Regional settings object
Repository	API Repository object
SuspendFormating	Boolean
TraceSettings	Trace settings object
WarningPending	Boolean [RO]

PSMessage Collection

Method	***Returns***
DeleteAll()	Boolean
DeleteItem(*number*)	Boolean

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Method	***Returns***
First()	PSMessage object
Item(*number*)	PSMessage object
Next()	PSMessage object

PSMessage Collection Property

Property	***Returns***
Count	Number [RO]

PSMessage Properties

Property	***Returns***
ExplainText	String [RO]
MessageNumber	Number [RO]
MessageSetNumber	Number [RO]
Source	String [RO]
Text	String [RO]

RegionalSettings Properties

Property	***Returns***
ClientTimeZone	String
CurrencyFormat	Number
CurrencySymbol	String
DateFormat	Number
DateSeparator	String
DecimalSymbol	String
DigitGroupingSymbol	String
LanguageCD	String

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	*Returns*
UseLocalTime	Boolean
1159Separator	String
2359Separator	String

TraceSettings Properties

Property	*Returns*
API	Boolean
COBOLStmtTimings	Boolean
ConDisRollbackCommit	Boolean
DBSpecificCalls	Boolean
ManagerInfo	Boolean
NetworkServices	Boolean
NonSSBs	Boolean
OutputUNICODE	Boolean
PCExtFcnCalls	Boolean
PCFcnReturnValues	Boolean
PCFetchedValues	Boolean
PCIntFcnCalls	Boolean
PCListProgram	Boolean
PCParameterValues	Boolean
PCProgramStatements	Boolean
PCStack	Boolean
PCStartOfPrograms	Boolean
PCTraceProgram	Boolean
PCVariableAssignments	Boolean

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	*Returns*
RowFetch	Boolean
SQLStatement	Boolean
SQLStatementVariables	Boolean
SSBs	Boolean
SybBindInfo	Boolean
SybFetchInfo	Boolean
TraceFile	String

API Repository Classes Methods and Properties

This section lists the method, properties, as well as the returns (if applicable) for the API Repository classes.

Repository Properties

Property	*Returns*
Bindings	Bindings collection object RO
NameSpaces	Namespaces collection RO

Bindings Collection Property

Property	*Returns*
Count	Number RO

Bindings Collections Method

Method	*Returns*
Item(*number*)	Binding object

Bindings Property

Property	*Returns*
Name	String RO

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Namespaces Collection Property

Property	***Returns***
Count	String RO

Namespaces Collection Methods

Method	***Returns***
Item(*Number*)	Namespaces object
ItemByName(*Name*)	Namespaces object

Namespaces Properties

Property	***Returns***
Classes	ClassInfo object RO
Name	String RO

ClassInfo Collection Property

Property	***Returns***
Count	Number RO

ClassInfo Collection Methods

Method	***Returns***
Item(*Number*)	ClassInfo object
ItemByName(*Name*)	ClassInfo object

ClassInfo Properties

Property	***Returns***
Documentation	String RO
Methods	MethodInfo collection object RO
Name	String RO
Properties	PropertyInfo collection object RO

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

MethodInfo Collection Property

Property	***Returns***
Count	String RO

MethodInfo Collection Methods

Method	***Returns***
Item(*Number*)	MethodInfo object
ItemByName(*Name*)	MethodInfo object

MethodInfo Properties

Property	***Returns***
Arguments	PropertyInfo collection object RO
Documentation	String RO
Name	String RO
Type	String RO

PropertyInfo Collection Properties

Property	***Returns***
Count	String RO

PropertyInfo Collection Methods

Method	***Returns***
Item(*Number*)	PropertyInfo object
ItemByName(*Name*)	PropertyInfo object

PropertyInfo Properties

Property	***Returns***
Documentation	String RO
Name	String RO

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
Type	String RO
Usage	Number RO

Component Interface Class Methods and Properties

This section lists the methods and properties, as well as returns (if applicable) for the component interface classes.

Component Interface Collection Methods

Method	***Returns***
First()	Component Interface structure (no data)
Item(*number*)	Component Interface structure (no data)
Next()	Component Interface structure (no data)

Component Interface Collection Property

Property	***Retuns***
Count	Number RO

Component Interface Methods

Method	***Returns***
Cancel()	Boolean
CopyRowset(*&rowset* [,*IntialRow*] [, *record_list*])	None
CopyRowsetDelta(*&rowsetI*, [,*IntialRow*] [, *record_list*])	None
CopySetupRowset(*&rowset* [,*IntialRow*] [, *record_list*])	None
CopySetupRowsetDelta(*&rowsetI*, [,*IntialRow*] [, *record_list*])	None
Create()	Component Interface with data
Find()	Component Interface collection
Get()	Component Interface with data
GetPropertyByName(*string*)	Depends on property

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Method	***Returns***
Save()	Boolean
SetPropertyByName(*string, value*)	None

Component Interface Properties

Property	***Returns***
ComponentName	String RO
CreateKeyInfoCollection	Component InterfacePropertyInfo collection object RO
FindKeyInfoCollection	Component InterfacePropertyInfo collection object RO
GetDummyRows	Boolean
GetHistoryItems	Boolean
GetKeyInfoCollection	Component InterfacePropertyInfo collection object RO
InteractiveMode	Boolean
PropertyInfoCollection	Component InterfacePropertyInfo collection object RO
StopOnFirstError	Boolean
Every user-defined property in a component interface definition can be used like a property on the instantiated object.	Depends on property

CompIntfPropInfo Collection Methods

Method	***Returns***
First()	Component InterfacePropertyInfo object
Item(*number*)	Component InterfacePropertyInfo object
Next()	Component InterfacePropertyInfo object

CompIntfPropInfo Collection Property

Property	***Returns***
Count	Number RO

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

CompIntfPropInfo Properties

Property	***Returns***
Format	String RO
IsCollection	Boolean RO
IsReadOnly	Boolean RO
Key	Boolean RO
LabelLong	String RO
LabelShort	String RO
Length	Number RO
Name	String RO
Prompt	Boolean RO
PropertyInfoCollection	Component InterfacePropertyInfo collection object
Required	Boolean RO
Type	String RO
Xlat	Boolean RO
YesNo	Boolean RO

Data Collection Methods

Method	***Returns***
CurrentItem()	Data collection item
DeleteItem(*number*)	None
GetEffectiveItem(*DateString*, *SeqNo*)	Data collection item
GetEffectiveItemNum(*DateString*, *SeqNo*)	Number
InsertItem(*number*)	Data collection item
Item(*number*)	Data collection item
ItemByKeys(*key_values*)	Data collection item

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Data Collection Properties

Property	*Returns*
Count	Number RO
CurrentItemNumber	Number RO

Verity Search Classes Methods and Properties

This section lists the methods and properties, as well as returns (if applicable) for the Verity search classes.

Note: Search class objects are instantiated from both the Session and PortalRegisty objects.

SearchQuery Methods

Method	*Returns*
Execute(*Start*, *Size*)	SearchResult collection
Parse()	ParseResult collection

SearchQuery Properties

Property	*Returns*
HitCount	Number RO
Indexes	String
KnowledgeBase	String
Language	String
ProcessedCount	Number RO
QueryText	String
RequestedFields	String
ScorePrecision	String
SortSpecifications	String

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

ParseResult Collection Methods

Method	***Returns***
First()	ParseResult object
Next()	ParseResult object or Null

ParseResult Collection Properties

Property	Returns
ErrorCount	Number RO
WarningCount	Number RO

ParseResult Properties

Property	***Returns***
Message	String RO
Severity	String RO

SearchResult Collection Methods

Method	***Returns***
First()	SearchResult
Item(*number*)	SearchResult
Next()	SearchResult

SearchResult Collection Property

Property	***Returns***
Count	Number RO

SearchResult Properties

Property	***Returns***
Key	String RO

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	*Returns*
Score	String RO
ScoreAsNumber	Floating point number RO
SearchFields	SearchField collection RO

SearchField Collection Methods

Method	*Returns*
First()	SearchField
ItemByName(*Name*)	SearchField
Next()	SearchField

SearchField Collection Property

Property	*Returns*
Count	Number RO

SearchField Properties

Property	*Returns*
Name	String RO
Value	String RO

SearchIndexes Collection Methods

Method	*Returns*
First()	SearchIndex object
ItemByName(*Name*)	SearchIndex object
Next()	SearchIndex object

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SearchIndexes Collection Property

Property	***Returns***
Count	Number RO

SearchIndex Method

Method	***Returns***
Save()	Boolean

SearchIndex Properties

Property	Returns
ExtraOptions	Any
FSOpts	Search FS Options object RO
HTTPOpts	Search HTTP Options object RO
Languages	Search Language collection RO
Location	String
Name	String RO
RecOpts	SearchRecord Options collection RO
Schedules	Search Schedule collection RO
Type	String

SearchRecord Options Properties

Property	***Returns***
Fields	SearchRecordField collection RO
Filter	String
IncrementalView	String
RecName	String RO
VeggieKey	String

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
ZoneOptions	String

SearchRecordField Collection Methods

Method	***Returns***
DeleteItem(*Record, Field*)	Boolean
First()	SearchRecordField object
InsertItem(*Record, Field*)	SearchRecordField object
ItemByName(*Record, Field*)	SearchRecordField object
Next()	SearchRecordField object

SearchRecordField Collection Property

Property	***Returns***
Count	Number RO

SearchRecordField Properties

Property	***Returns***
FieldName	String RO
IsAttachment	Boolean
IsVerityField	Boolean
IsWordIndex	Boolean
RecordName	String RO

SearchLanguage Collection Methods

Method	***Returns***
DeleteItem(*Name*)	Boolean
First()	Search Language object
InsertItem(*LanguageCode, MapLanguageCode*)	Search Language object

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Method	***Returns***
ItemByName(*LanguageCode*)	Search Language object
Next()	Search Language object

SearchLanguage Collection Property

Property	***Returns***
Count	Number RO

SearchLanguage Properties

Property	***Returns***
LanguageCd	String RO
MapLanguageCd	String RO

SearchSchedule Collection Methods

Method	***Returns***
DeleteItem(*Name*)	Boolean
First()	Search Schedule object
InsertItem(*RunCntrlID)*	Search Schedule object
ItemByName(*RunCntrlID*)	Search Schedule object
Next()	Search Schedule object

SearchSchedule Collection Property

Property	***Returns***
Count	Number RO

SearchSchedule Properties

Property	***Returns***
BuildType	String

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	*Returns*
RunCntrID	String RO
RunRecurrance	String
ServerName	String

SearchHTTPOptions Properties

Property	*Returns*
AllowHTTPS	Boolean
DomainLimit	String
GlobList	String
GlobListType	String
LinkDepth	Number
MIMEList	String
MIMEListType	String
ProxyHost	String
ProxyPort	Number
StartOpts	Search Start Options collection RO

SearchFSOptions Properties

Property	*Returns*
GlobList	String
GlobListType	String
MIMEList	String
MIMEListType	String
StartOpts	Search Start Options collection RO

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

SearchStartOptions Collection Methods

Method	***Returns***
DeleteItem(*Value*)	Boolean
First()	Search Start Options object
InsertItem(*Value*)	Search Start Options object
ItemByName(*Value*)	Search Start Options object
Next()	Search Start Options object

SearchStartOptions Collection Property

Property	***Returns***
Count	Number [RO]

SearchStartOptions Properties

Property	***Returns***
IsDomainRestricted	Boolean
IsHostRestricted	Boolean
Value	String [RO]

Portal Registry Classes Methods and Properties

This section lists the methods, and properties, as well as returns (if applicable) for the portal registry classes.

PortalRegistry Methods

Method	***Returns***
BuildSearchIndex(*Language*)	Boolean
Close()	Boolean
CopyObject(*sourcePortalName*, *sourceRefType*, *sourceObjName*, *targetPortalName*, *targetPrntFldrName*, *copyChildren*)	Boolean
Create(*RegistryName*)	Boolean

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Method	***Returns***
CreateContentRefLink(*LinkName*, *LinkLabel*, *LinkParent*, *CRefPortalName*, *CRefObjectName*)	ContentReference link object
CreateRemote(*PortalName*, *RemoteNodeName*)	Boolean
Delete(*RegistryName*)	Boolean
DeleteHomepage()	Boolean
FindCRefByName(*Name*)	ContentReference object
FindCRefByURL(*URL*)	ContentReference object
FindCrefForURL(*URL*)	ContentReference object
FindCRefLinkByName(*LinkName*)	ContentReference link object
FindFolderByName(*Name*)	Folder object
FindPgltByName(*PageletName*)	Pagelet object
GetAbsoluteContentURL(*NodeName*, *URL*)	ContentReference object
GetDefaultHPTabOID()	String
GetQualifiedURL(*ContentProvider*, *RelativeURL*)	URL string
GetSearchQuery()	SearchQuery object
GrantPermissionForComponent(*MenuName*, *ComponentName*, *Market*, *PermListName*, *NodeName*)	Boolean
GrantPermissionForScript(*RecordName*, *FieldName*, *EventName*, *FuncName*, *PermListName*, *NodeName*)	Boolean
Open(*RegistryName*)	Boolean
PermissionListDelete(*PermListName*)	Boolean
PermissionListSaveAs(*PermListSourceName*, *PermListTargetName*)	Boolean
RevokePermissionForComponent(*MenuName*, *ComponentName*, *Market*, *PermListName*, *NodeName*)	Boolean
RevokePermissionForScript(*RecordName*, *FieldName*, *EventName*, *FuncName*, *PermListName*, *NodeName*)	Boolean

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Method	***Returns***
Save()	Boolean

PortalRegistry Properties

Property	***Returns***
DefaultTemplate	String
Description	String
DisableFolderNavigation	Boolean
Favorites	Favorite Collection RO
FolderNavObject	String
Homepage	Homepage object RO
IsFolderNavigation	Booldan
Name	String RO
NodeTemplates	NodeTemplate Collection RO
OwnerId	String
PageletCategories	PageletCategories Collection RO
Portals	Portal collection RO
RootFolder	Folder object RO
TabDefinitions	TabDefinitions Collection RO
TemplateObject	ContentReference object RO

PortalRegistry Collection Methods

Method	***Returns***
First()	PortalRegistry object
Item(*number*)	PortalRegistry object
Next()	PortalRegistry object

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

PortalRegistry Collection Property

Property	*Returns*
Count	Number RO

Node Class Properties

Property	*Returns*
ActiveNode	Boolean RO
AppRelease	String RO
ContentURI	String RO
DefaultPortalName	String RO
Description	String RO
Name	String RO
NodePassword	String RO
NodeType	String RO
PortalURI	String RO
ToolsRelease	String RO

Node Collection Methods

Method	*Returns*
First()	Node object
ItemByName(*NodeName*)	Node object
Next()	Node object

Node Collection Property

Property	*Returns*
Count	Number RO

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Remote Node Collection Methods

Method	***Returns***
First()	Node object
ItemByName(*NodeName*)	Node object
Next()	Node object

Remote Node Collection Property

Property	***Returns***
Count	Number RO

Portal Class Method

Method	***Returns***
Save()	Boolean

Portal Class Properties

Property	***Returns***
HostNodeName	String
IsLocal	Boolean RO
Name	String RO

Portal Collection Methods

Method	***Returns***
First()	Portal object
ItemByName(*PortalName*)	Portal object
Next()	Portal object

Portal Collection Property

Property	***Returns***
Count	Number RO

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Node Template Class Properties

Property	***Returns***
DefaultTemplate	String
Name	String
TemplateObject	Template object [RO]

Node Template Collection Methods

Method	***Returns***
DeleteItem(*NodeName*)	Boolean
First()	NodeTemplate object
InsertItem(*NodeName*)	NodeTemplate object
ItemByName(*NodeName*)	NodeTemplate object
Next()	NodeTemplate Object

Node Template Collection Property

Property	***Returns***
Count	Number [RO]

Folder Class Method

Method	***Returns***
Save()	Boolean

Folder Class Properties

Property	***Returns***
AbnContentProvider	String
AbnDataSource	String
AbnPeopleCode	String
Attributes	Attribute collection object [RO]

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
Author	String RO
AuthorAccess	Boolean
Authorized	Boolean
CascadedPermissions	PermissionValue collection RO
CascadedRolePermissions	RolePermissionValue collection RO
ContentRefs	ContentReference Collection RO
CreationDate	String RO
DefaultChartNavigation	Boolean
Description	String
Folders	Folder collection RO
IsVisible	Boolean RO
Label	String
Name	String RO
OwnerID	String
ParentName	String RO
Path	String RO
Permissions	PermissionValue collection RO
Product	String
PublicAccess	Boolean
RolePermissions	RolePermissionValue collection RO
SequenceNumber	Number
TreeEffectiveDate	String
TreeName	String
TreeSetId	String

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
TreeStructureName	String
TreeUserKeyValue	String
ValidFrom	String
ValidTo	String

Folder Collection Methods

Method	***Returns***
DeleteItem(*FolderName*)	Boolean
First()	Folder object
InsertItem(*FolderName*, *Label*)	Folder object
ItemByName(*FolderName*)	Folder object
Next()	Folder object

Folder Collection Property

Property	***Returns***
Count	Number [RO]

ContentReference Methods

Method	***Returns***
CreateLink(*Name*, *Label*)	ContentReference link object
Save()	Boolean

ContentReference Properties

Property	***Returns***
AbsoluteContentURL	String [RO]
AbsolutePortalURL	String [RO]
AssignedPagelets	AssignedPagelets collection [RO]

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
Attributes	Attribute collection object RO
Author	String RO
AuthorAccess	Boolean
Authorized	Boolean
CascadedPermissions	PermissionValue collection RO
CascadedRolePermissions	RolePermissionValue collection RO
ContentProvider	String
CreationDate	String RO
Data	String
Description	String
HtmlText	String RO
IsVisible	Boolean RO
Label	String
Links	Link collection RO
Name	String RO
OwnerId	String
ParentName	String RO
Path	String RO
Permissions	PermissionValue collection RO
Product	String
PublicAccess	Boolean
RelativeURL	String RO
RolePermissions	RolePermissionValue collection RO
SequenceNumber	Number

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
StorageType	String
Template	String
TemplateObject	ContentReference object [RO]
TemplateType	String
URL	String
URLType	String
UsageType	String
ValidFrom	String
ValidTo	String

ContentReference Collection Methods

Method	***Returns***
DeleteItem(*ContentReferenceName*)	Boolean
First()	ContentReference object
InsertItem(*ContentReferenceName*, *ContentReferenceLabel, Node, URL*)	ContentReference object
ItemByName(*ContentReferenceName*)	ContentReference object
Next()	ContentReference object

ContentReference Collection Property

Property	***Returns***
Count	Number [RO]

AttributeValue Properties

Property	***Returns***
Label	String
Name	String [RO]

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
Translatable	Boolean
Value	String

AttributeValue Collection Methods

Method	***Returns***
DeleteItem(*AttributeValueName*)	Boolean
First()	AttributeValue object
InsertItem(*AttributeValueName*)	AttributeValue object
ItemByName(*AttributeValueName*)	AttributeValue object
Next()	AttributeValue object

AttributeValue Collection Property

Property	***Returns***
Count	Number [RO]

PermissionValue Properties

Property	***Returns***
Cascade	Boolean
Name	String

PermissionValue Collection Methods

Method	***Returns***
DeleteItem(*PermissionValueName*)	Boolean
First()	PermissionValue object
InsertItem(*PermissionValueName*)	PermissionValue object
ItemByName(*PermissionValueName*)	PermissionValue object
Next()	PermissionValue object

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

PermissionValue Collection Property

Property	***Returns***
Count	Number [RO]

RolePermissionValue Collection Methods

Method	***Returns***
DeleteItem(*PermissionValueName*)	Boolean
First()	PermissionValue object
InsertItem(*PermissionValueName*)	PermissionValue object
ItemByName(*PermissionValueName*)	PermissionValue object
Next()	PermissionValue object

RolePermissionValue Collection Property

Property	***Returns***
Count	Number [RO]

ContentReference Link Methods

Method	***Returns***
Delete()	Boolean
Save()	Boolean

ContentReference Link Properties

Property	***Returns***
AbsoluteContentURL	String [RO]
AbsolutePortalURL	String [RO]
Attributes	Attribute Collection
Author	String [RO]
AuthorAccess	Boolean [RO]

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
Authorized	Boolean RO
CascadedPermissions	PermissionValue collection RO
ContentProvider	String RO
CreationDate	String RO
Data	String
Description	String
IsVisible	Boolean RO
Label	String
Name	String
OwnerId	String
ParentName	String
Path	String RO
Permissions	PermissionValue Collection RO
Product	String
PublicAccess	Boolean RO
RelativeURL	String RO
SequenceNumber	String
Template	String
TemplateObject	String RO
TemplateType	String
URL	String
URLType	String RO
ValidFrom	Date
ValidTo	Date

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Link Collection Methods

Method	*Returns*
First	Link object
Next	Link object

Link Collection Property

Property	*Returns*
Count	Number RO

Link Class Properties

Property	*Returns*
LinksObjectName	String RO
LinksObjectType	String RO
LinksPortalName	String RO

TabDefinition Method

Method	*Returns*
Save()	Boolean

TabDefinition Properties

Property	*Returns*
AssignedPagelets	AssignedPagelets collection RO
AvailableCategories	AvailableCategories collection RO
AvailablePagelets	AvailablePagelets collection RO
Attributes	AttributeValue collection object RO
Author	String RO
AuthorAccess	Boolean
Authorized	Boolean

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
ColumnLayout	String
CreationDate	String RO
Description	String
DynamicCategories	DynamicCategories collection RO
HelpID	String
HtmlText	String RO
IsHideActionBar	Boolean
IsLayoutLocked	Boolean
IsRenamable	Boolean
Label	String
LayoutBehavior	String
Name	String RO
OwnerId	String
Product	String
PublicAccess	Boolean
QualifiedURL	String RO
SequenceNumber	Number
StyleSheet	String
ValidFrom	String
ValidTo	String

TabDefinition Collection Methods

Method	***Returns***
DeleteItem(*TabDefinitionName*)	Boolean
First()	TabDefinition object

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Method	***Returns***
InsertItem(*TabDefinitionName*)	TabDefinition object
ItemByName(*TabDefinitionName*)	TabDefinition object
Next()	TabDefinition object

TabDefinition Collection Property

Property	***Returns***
Count	Number [RO]

AssignedPagelet Properties

Property	***Returns***
Column	Number
LayoutBehavior	String
PageletName	String [RO]
Row	Number

AssignedPagelet Collection Methods

Method	***Returns***
DeleteItem(*PageletName*)	Boolean
First()	Pagelet object
InsertItem(*PageletName*, *Column*, *Row*, *LayoutBehavior*)	Pagelet object
ItemByName(*PageletName*)	Pagelet object
Next()	Pagelet object

AssignedPagelet Collection Property

Property	***Returns***
Count	Number [RO]

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

AvailableCategory Properties

Property	***Returns***
AvailablePagelets	AvailablePagelets Collection RO
CategoryName	String RO

AvailableCategory Collection Methods

Method	***Returns***
First()	AvailableCategory object
ItemByName(*Name*)	AvailableCategory object
Next()	AvailableCategory object

AvailableCategory Collection Property

Property	***Returns***
Count	Number RO

AvailablePagelet Properties

Property	***Returns***
CategoryLabel	String RO
CategoryName	String RO
Column	Number RO
LayoutBehavior	String RO
PageletLabel	String RO
PageletName	String RO
Row	Number RO

AvailablePagelet Collection Methods

Method	***Returns***
First()	AvailablePagelet object

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Method	***Returns***
ItemByName(*Name*)	AvailablePagelet object
Next()	AvailablePagelet object

AvailablePagelet Collection Property

Property	***Returns***
Count	Number [RO]

DynamicCategory Collection Methods

Method	***Returns***
DeleteItem(*Name*)	Boolean
First()	String
InsertItem(*Name*)	String
ItemByName(*Name*)	String
Next()	String

DynamicCategory Collection Property

Property	***Returns***
Count	Number [RO]

PageletCategory Method

Method	***Returns***
Save()	Boolean

PageletCategory Properties

Property	***Returns***
Attributes	AttributeValues collection object [RO]
Author	String [RO]

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
AuthorAccess	Boolean
Authorized	Boolean
CascadedPermissions	PermissionList object RO
CreationDate	String RO
Description	String
Label	String
Name	String RO
OwnerId	String
Pagelets	Pagelets Collection RO
Permissions	PermissionList Collection RO
Product	String
PublicAccess	Boolean
SequenceNumber	Number

PageletCategory Collection Methods

Method	***Returns***
DeleteItem(*Name*)	Boolean
First()	String
InsertItem(*Name*, *Label*)	String
ItemByName(*Name*)	String
Next()	String

PageletCategory Collection Property

Property	***Returns***
Count	Number RO

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Pagelet Method

Method	*Returns*
Save()	Boolean

Pagelet Properties

Property	*Returns*
Attributes	Attribute collection object RO
Author	String RO
AuthorAccess	Boolean
Authorized	Boolean
CascadedPermissions	PermissionList Collection RO
ContentProvider	Node object RO
CreationDate	String RO
DefaultColumn	Number
Description	String
HelpID	String
IsHideMinimize	Boolean
Label	String
Name	String RO
OwnerId	String
ParentName	String RO
Permissions	PermissionList Collection RO
Product	String
PublicAccess	Boolean
QualifiedURL	String RO
SequenceNumber	Number

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
URL	String
URLType	String

Pagelet Collection Methods

Method	***Returns***
DeleteItem(*Name*)	Boolean
First()	Pagelet object
InsertItem(*Name*, *Label*, *NodeName*, *URL*)	Pagelet object
ItemByName(*Name*)	Pagelet object
Next()	Pagelet object

Pagelet Collection Property

Property	***Returns***
Count	Number [RO]

UserHomepage Method

Method	***Returns***
Save()	

UserHomepage Properties

Property	***Returns***
Greeting	String
UserId	String [RO]
UserTab	UserTab Collection[RO]

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

UserTab Properties

Property	***Returns***
ColumnLayout	Number
Label	String
QualifiedURL	String [RO]
SelectedPagelets	SelectedPagelets collection[RO]
SequenceNumber	Number
TabName	String [RO]

UserTab Collection Methods

Method	***Returns***
DeleteItem(*Name*)	Boolean
First()	UserTab object
InsertItem(*Name*)	UserTab object
ItemByName(*Name*)	UserTab object
Next()	UserTab object

UserTab Collection Property

Property	***Returns***
Count	Number [RO]

SelectedPagelet Properties

Property	***Returns***
CategoryName	String [RO]
Column	Number
IsMinimized	Boolean
PageletName	String [RO]

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
Row	Number

SelectedPagelet Collection Methods

Method	***Returns***
DeleteItem(*Name*)	Boolean
First()	SelectedPagelet object
InsertItem(*Name*)	SelectedPagelet object
ItemByName(*Name*)	SelectedPagelet object
Next()	SelectedPagelet object

SelectedPagelet Collection Property

Property	***Returns***
Count	Number RO

Favorites Properties

Property	***Returns***
CRefName	String RO
IsFolder	Boolean RO
Label	String
QualifiedURL	String RO
SequenceNumber	Number
URL	String

Favorites Collection Methods

Method	***Returns***
DeleteItem(*FavoriteLabel*)	Boolean
First()	Favorite object

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Method	***Returns***
InsertFolderItem(*FavoriteLabel*, *FavoriteName*)	Favorite object
InsertItem(*FavoriteLabel*, *FavoriteName*)	Favorite object
ItemByLabel(*FavoriteLabel*)	Favorite object
Next()	Favorite object

Favorites Collection Property

Property	***Returns***
Count	Number [RO]

Query Classes Methods and Properties

This section lists the functions, methods, and properties, as well as returns (if applicable) for the query classes.

Query Collection Methods

Method	***Returns***
First()	Query object
Item(*Number*)	Query object
ItemByName(*Name*)	Query object
Next()	Query object

Query Collection Property

Property	***Returns***
Count	Number [RO]

Query Methods

Method	***Returns***
AddPrompt(*PromptName*)	Prompt object
AddQuerySelect()	QuerySelect object

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Method	***Returns***
AddTrackingURL(*URLString*)	None
Close()	None
CopyPrivateQuery(*QueryName*, *QryType*, *TargetUserId*)	Number
Create(*QueryName*, *Pubic*, *Type*, *Description*, *LongDescription*)	Query object
Delete()	Number
DeletePrompt(*PromptName*)	Number
FindExpression(*Number*)	Expression object
FormatBinaryResultString(*&Rowset*, *Output_Format*, *StartRow*, *EndRow*)	Binary object
FormatResultString(*&Rowset*, *Output_Format*, *StartRow*, *EndRow*)	String
GetTreePromptCount()	Number
Open(*QueryName*, *Public*, *Update*)	Number
Rename(*NewQueryName*)	Number
RunToFile(*&PromptRecord*, *Destination*, *OutputFormat*, *MaxRows*)	Number
RunToRowset(*&PromptRecord*, *MaxRows*)	Rowset object
RunToString (*&PromptRecord*, *ChunkSize*, *OutputFormat*, *MaxRows*)	String
Save()	Number
SetTrackingURL(*ExpressionText*, *ExpressionNumber*)	None

Query Properties

Property	***Returns***
Approved	String
ApprovedDtTm	String [RO]

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
ApprovedUserId	String
CreateDtTm	String RO
CreateUserId	String RO
Description	String
ExecAppName	String
ExecLogging	Boolean
LastSQLErrorCode	Number RO
LastUpdDttm	String RO
LastUpdOprId	String RO
LongDescription	String
Metadata	Metadata collection RO
MoreRowsAvailable	Boolean RO
Name	String RO
OutputUnicode	Boolean
PDFFont	String
Prompts	QueryPrompt collection RO
PromptRecord	Record object RO
PublicPrivate	String
QuerySelect	QuerySelect object RO
QueryStatistics	QueryStatistics object RO
RunTimePrompts	QueryPrompt Collection RO
SQL	String RO
Type	Number

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

QuerySelect Methods

Method	***Returns***
AddAllFields(*QueryRecord*)	Number
AddCriteria(*Name*)	QueryCriteria object
AddExpression(*Name*)	QueryExpression object
AddHavingCriteria(*Name*)	QueryCriteria object
AddQueryOutputField(*QueryRecord*, *index*)	QueryOutputField object
AddQueryRecord(*QueryRecordName*)	QueryRecord object
AddQuerySelectedField(*QueryRecord*, *index*)	QuerySelectedField object
DeleteCriteria(*index*)	Number
DeleteExpression(*Index*)	Number
DeleteField(*Index*)	Number
DeleteHavingCriteria(*Index*)	Number
DeleteRecord(*Index*)	Number

QuerySelect Properties

Property	***Returns***
Criteria	QueryCriteria collection RO
Distinct	Boolean
Expressions	QueryExpression collection RO
HavingCriteria	QueryCriteria collection RO
ParentSelectNum	Number RO
QueryOutputFields	QueryField collection RO
QueryRecords	QueryRecord collection RO
QuerySelectedFields	QueryField collection RO
QuerySelects	QuerySelect object RO

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
SelectNum	Number [RO]
SelectType	Number [RO]

QuerySelect Collection Methods

Method	***Returns***
AddUnion()	QuerySelect object
DeleteQuerySelect(*SelNumber*)	Number
First()	QuerySelect object
Item(*Number*)	QuerySelect object
ItemBySelNum(*SelNumber*)	QuerySelect object
Next()	QuerySelect object

QuerySelect Collection Properties

Property	***Returns***
Count	Number [RO]

QueryRecord Collection Methods

Method	***Returns***
First()	QueryRecord object
Item(*Number*)	QueryRecord object
ItemByAlias(*Alias*)	QueryRecord object
Next()	QueryRecord object

QueryRecord Collection Property

Property	***Returns***
Count	Number [RO]

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

QueryRecord Method

Method	***Returns***
GetField(*Index*)	QueryField object

QueryRecord Properties

Property	***Returns***
Description	String [RO]
JoinAlias	String
JoinFieldName	String
JoinType	Number
Name	String [RO]
QueryFields	QueryFields collection [RO]
RecordAlias	String

QueryField Collection Methods

Method	***Returns***
First()	QueryField object
Item(*Number*)	QueryField object
ItemByNameAndAlias(*Name*, *RecordAlias*)	QueryField object
ItemByExpNum(*ExpNum*)	QueryField object
Next()	QueryField object

QueryField Collection Property

Property	***Returns***
Count	Number [RO]

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

QueryField Methods

Method	***Returns***
AddTranslateExpression(*ExpressionName*)	QueryExpression object
AddTranslateField(*FieldName*)	QueryField object
GetImageFormat()	Number

QueryField Properties

Property	***Returns***
Aggregate	Number
ColumnNumber	Number
Description	String RO
Decimal	Number RO
ExpNum	Number
Flag	Number RO
Format	Number
HeadingText	String
HeadingType	String
HeadingUniqueFieldName	String
Length	Number RO
LongName	String RO
Name	String RO
OrderByDirection	Number
OrderByNumber	Number
QueryRecord	QueryRecord object RO
RecordAlias	String RO
ShortName	String RO

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
TranslateEffDtLogic	String
TranslateExpression	Expression object RO
TranslateField	QueryField RO
TranslateOption	String
Type	String

QueryCriteria Collection Methods

Method	***Returns***
First()	QueryCriteria object
Item(*Number*)	QueryCriteria object
ItemByName(*CriteriaName*)	QueryCriteria object
Next()	QueryCriteria object

QueryCriteria Collection Property

Property	***Returns***
Count	Number RO

QueryCriteria Methods

Method	***Returns***
AddExpr1Expression()	QueryExpression object
AddExpr1Field(*QueryRecordAlias*, *FieldName*)	QueryField object
AddExpr2Expression()	QueryExpression object
AddExpr2Field1(*QueryRecordAlias*, *FieldName*)	QueryField object
AddExpr2Field2(*QueryRecordAlias*, *FieldName*)	QueryField object
AddExpr2List()	QueryList object
AddExpr2Subquery()	QuerySelect object

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

QueryCriteria Properties

Property	*Returns*
Expr1Expression	QueryExpression object
Expr1Field	QueryField object RO
Expr1Type	Number
Expr2Constant1	String
Expr2Constant2	String
Expr2Expression1	QueryExpression object
Expr2Expression2	QueryExpression object
Expr2Field1	QueryField object RO
Expr2Field2	QueryField object RO
Expr2List	QueryList object RO
Expr2Subquery	QuerySelect object RO
Expr2Type	Number
Logical	Number
LParenLvl	Number
Name	String RO
Negation	Boolean
Operator	Number
R1ExprNum	Number
R2ExprNum	Number
R1ExprType	Number
R2ExprType	Number
RParenLvl	Number

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

QueryExpression Collection Methods

Method	***Returns***
First()	QueryExpression object
Item(*Number*)	QueryExpression object
ItemByName(*ExpressionName*)	QueryExpression object
Next()	QueryExpression object

QueryExpression Collection Property

Property	***Returns***
Count	Number [RO]

QueryExpression Properties

Property	***Returns***
Aggregate	Number
BindFlag	Number
Decimal	Number
ExpNum	Number
Length	Number
Name	String [RO]
OutputField	QueryField object
RightExprFlag	Number
SelectedField	QueryField object
Text	String
Type	Number

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

QueryList Methods

Method	***Returns***
AddListValue(*Value*, *IsPrompt*)	QueryListValue object
First()	QueryListValue object
Item(*Number*)	QueryListValue object
Next()	QueryListValue object

QueryList Property

Property	***Returns***
Count	Number [RO]

QueryListValue Properties

Property	***Returns***
IsPrompt	Boolean [RO]
Value	String [RO]

QueryRecordHierarchy Collection Methods

Method	***Returns***
First()	QueryRecordHierarchy object
Item(*Number*)	QueryRecordHierarchy object
ItemByName(*Name*)	QueryRecordHierarchy object
Next()	QueryRecordHierarchy object

QueryRecordHierarchy Collection Property

Property	***Returns***
Count	Number [RO]

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

QueryRecordHierarchy Properties

Property	***Returns***
Description	String RO
Level	Number RO
Name	String RO
ParentFlag	Number RO

Query Metadata Collection Methods

Method	***Returns***
First()	Query Metadata object
Item(*Number*)	Query Metadata object
ItemByName(*Name*)	Query Metadata object
Next()	Query Metadata object

Query Metadata Collection Property

Property	***Returns***
Count	Number RO

Query Metadata Properties

Property	***Returns***
Name	String RO
Value	String RO

QueryStatistics Properties

Property	***Returns***
AvgExecTime	Number RO
AvgFetchTime	Number RO
AvgNumRows	Number RO

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	*Returns*
ExecCount	Number RO
LastExecDtTm	String RO

QuerySecurityProfile Properties

Property	*Returns*
AllowAnyJoin	Boolean RO
AllowDistinct	Boolean RO
AllowExpressions	Boolean RO
AllowSubqueries	Boolean RO
AllowUnions	Boolean RO
ApprovePrivateQuery	Boolean RO
ApprovePublicQuery	Boolean RO
CanCreatePublic	Boolean RO
CanCreateWorkFlow	Boolean RO
CanModifyQuery	Boolean RO
CanRunQuery	Boolean RO
CanRunToCrystal	Boolean RO
CanRunToExcel	Boolean RO
LimitUnapproved	Boolean RO
MaxInTreeCriteria	Boolean RO
MaxJoins	Boolean RO
MaxRowsToFetch	Boolean RO
MaxUnapprovedRows	Boolean RO

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

QueryDBRecord Collection Methods

Method	***Returns***
First()	QueryDBRecord object
Item(*Number*)	QueryDBRecord object
ItemByName(*Name*)	QueryDBRecord object
Next()	QueryDBRecord object

QueryDBRecord Collection Property

Property	***Returns***
Count	Number RO

QueryDBRecord Methods

Method	***Returns***
QueryDBRecordFieldByIndex(*Index*)	QueryDBRecordField object
QueryDBRecordFieldByName(*Name*)	QueryDBRecordField object

QueryDBRecord Properties

Property	***Returns***
Description	String RO
Name	String RO
QueryDBRecordFields	QueryDBRecordFields collection
RecordHierarchy	QueryRecordHierarchy Collection RO

QueryDBRecordField Collection Methods

Method	***Returns***
First()	QueryDBRecordField object
Item(*Number*)	QueryDBRecordField object
ItemByName(*Name*)	QueryDBRecordField object

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Method	***Returns***
Next()	QueryDBRecordField object
Sort(*SortCriteria*)	0

QueryDBRecordField Collection Property

Property	***Returns***
Count	Number RO

QueryDBRecordField Method

Method	***Returns***
GetImageFormat()	Number

QueryDBRecordField Properties

Property	***Returns***
Decimal	Number RO
Description	String RO
Flag	Number RO
Format	Number RO
Length	Number RO
LongName	String RO
LookupTableName	String RO
LookupTableRecord	QueryDBRecord object RO
Name	String RO
ShortName	String RO
Type	Number RO

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

QueryPrompt Collection Methods

Method	***Returns***
First()	QueryPrompt object
Item(*Number*)	QueryPrompt object
ItemByName(*Name*)	QueryPrompt object
Next()	QueryPrompt object

QueryPrompt Collection Property

Property	***Returns***
Count	Number RO

QueryPrompt Properties

Property	***Returns***
EditType	Number
FieldDecimal	Number
FieldFormat	Number
FieldLength	Number
FieldName	String
FieldType	Number
HeadingText	String
HeadingType	Number
LangCount	Number RO
Name	String RO
PromptRecordFieldName	String RO
PromptTable	String
UniquePromptName	String
UseCount	Number RO

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Tree Classes Methods and Properties

This section lists the methods and properties, as well as returns (if applicable) for the tree classes.

Branch Collection Properties

Property	***Returns***
Count	Number [RO]

Leaf Methods

Method	***Returns***
Cut()	Number
Delete()	Number
DeleteByRange(*RangeFrom*, *RangeTo*)	Number
GenABNMenuElement()	String
GenABNMenuElementWithImage(*CREF_img_class_ID*)	String
InsertDynSib()	Number
InsertSib(*RangeFrom*, *RangeTo*)	Leaf object
LoadABNChart(*&chart_rowset*, *&relactions_rowset*	None
LoadABNChartOrdered(*&chart_rowset*, *&relactions_rowset*, *order*	None
MoveAsChild(*Node*)	Number
MoveAsChildByName(*NodeName*)	Number
MoveAsSib(*Leaf*)	Number
MoveAsSibByRange(*RangeFrom*, *RangeTo*)	Number
PasteSib()	Number
RefreshDescription(*expand_range*)	Number
UpdateRanges(*RangeFrom*, *RangeTo*)	Number

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Leaf Properties

Property	***Returns***
Description	String RO
DisplayLevelNumber	Number RO
Dynamic	Boolean
HasNextSib	Boolean RO
HasPrevSib	Boolean RO
ImageName	String
IsChanged	Boolean RO
IsCut	Boolean RO
IsDeleted	Boolean RO
IsInserted	Boolean RO
NextSib	Leaf object RO
Parent	Node object RO
PrevSib	Leaf object RO
RangeFrom	String
RangeTo	String
TreeBranchName	String RO
TreeEffDt	Date
TreeName	String RO
TreeSetID	String RO
TreeUserKeyValue	String RO

Level Collection Methods

Method	***Returns***
Add(*LevelName*)	Level object

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Method	***Returns***
Item*(LevelName*, *LevelNumber*)	Level object
Remove()	Number

Level Collection Properties

Property	***Returns***
Count	Number [RO]
First	Level object [RO]
Last	Level object [RO]
Next	Level object [RO]

Level Properties

Property	***Returns***
AllValuesAudit	Boolean
Description	String
Name	String
Number	Number
TreeBranchName	String [RO]
TreeEffDt	Date
TreeName	String [RO]
TreeSetID	String [RO]
TreeUserKeyValue	String [RO]

Node Methods

Method	***Returns***
Branch()	Number
Cut()	Number

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Method	***Returns***
Delete()	Number
DeleteByName(*NodeName*)	Number
Expand(*ExpandType*)	Number
GenABNMenuElement(*initial_node*)	String
GenABNMenuElementWithImage(*initial_node*, *fldr_img_class_ID*, *CREF_img_class_ID*)	String
GenBreadCrumbs(*list*)	String
GenRelatedActions()	String
InsertChildLeaf(*RangeFrom*, *RangeTo*)	Leaf object
InsertChildNode(*NodeName*)	Node object
InsertChildRecord(*NodeName*)	Node object
InsertDynChildLeaf()	Leaf object
InsertSib(*NodeName*)	Node object
InsertSibRecord(*NodeName*)	Node object
LoadABNChart(*&chart_rowset*, *&relactions_rowset*, *requested_node*, *initial_node*)	None
LoadABNChartOrdered(*&chart_rowset*, *&relactions_rowset*, *requested_node*, *initial_node*, *order*)	None
MoveAsChild(*Node*)	Number
MoveAsChildByName(*NodeName*)	Number
MoveAsSib(*Node*)	Number
MoveAsSibByName(*NodeName*)	Number
PasteChild()	Number
PasteSib()	Number
RefreshDescription()	Number
Rename(*NodeName*)	Number

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Method	***Returns***
SwitchLevel(*NewLevelNumber*)	Number
Unbranch()	Number

Node Properties

Property	***Returns***
AllChildCount	Number RO
AllChildNodeCount	Number RO
ChildLeafCount	Number RO
ChildNodeCount	Number RO
ColImageName	String
Description	String RO
DisplayLevelNumber	Number RO
ExpImageName	String
FirstChildLeaf	Leaf object RO
FirstChildNode	Node object RO
HasChildLeaves	Boolean RO
HasChildNodes	Boolean RO
HasChildren	Boolean RO
HasNextSib	Boolean RO
HasPrevSib	Boolean RO
IsBranched	Boolean RO
IsChanged	Boolean RO
IsCut	Boolean RO
IsDeleted	Boolean RO
IsInserted	Boolean RO

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
IsRoot	Boolean RO
LastChildLeaf	Leaf object RO
LastChildNode	Node object RO
LevelNumber	Number
Name	String
NextSib	Leaf object RO
Parent	Node object RO
PrevSib	Leaf object RO
State	Number RO
TreeBranchName	String RO
TreeEffDt	Date
TreeName	String RO
TreeSetID	String RO
TreeUserKeyValue	String RO
Type	String RO

Tree Methods

Method	***Returns***
Audit()	Number
AuditByName(*SetID, UserKeyValue, TreeName, EffDt, BranchName*)	Number
Close()	Number
Copy(*FromSetId, FromUserKeyValue, FromTreeName, FromEffDt, FromBranchName, ToSetId, ToUserKeyValue, ToTreeName, ToEffDt, ToBranchName*)	Number
Create(*SetID, UserKeyValue, TreeName, EffDt, StructureName*)	Number

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Method	***Returns***
Delete(*SetID, UserKeyValue, TreeName, EffDt, BranchName*)	Number
Exists(*SetID, UserKeyValue, TreeName, EffDt, BranchName*)	Number
FindLeaf(*RangeFrom*, *RangeTo*)	Leaf object
FindNode(*NodeName, Description*)	Node object
FindRoot()	Node object
InsertRoot(*NodeName*)	Node object
LeafExists(*RangeFrom, RangeTo*)	Number
LockTree()	Number
Open(*SetID, UserKeyValue, TreeName, EffDt, BranchName, Update*)	Number
OpenAsOfDate(*SetID, UserKeyValue, TreeName, AsOfDate, BranchName, Update*)	Number
OpenForExport(*SetID*, *UserKeyValue*, *TreeName EffDt*)	Number.
OpenWholeTree(*SetID, UserKeyValue, TreeName, EffDt*)	Number
NodeExists(*NodeName*)	Number
Rename(*FromSetId, FromUserKeyValue, FromTreeName, FromEffDt, FromBranchName, ToTreeName*)	Number
Save()	Number
SaveAs(*SetID, UserKeyValue, TreeName, EffDt, BranchName*)	Number
SaveAsDraft(*SetID, UserKeyValue, TreeName, EffDt, BranchName*)	Number
SaveDraft()	Number
SetImportMode(*Nodes_Number*, *Leaves_Number*)	Number
TreeLocksNumber(*setID*, *UserKeyValue*, *TreeName*, *EffDt*)	Number
UnlockTree()	Number
UpdateLock()	Number

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Tree Properties

Property	***Returns***
AllValues	Boolean
AuditDetails	Boolean
Branches	Branch collection object RO
BranchImageName	String
BranchLevel	Number RO
BranchName	String RO
Category	String
Description	String
DuplicateLeaves	Boolean
EffDt	Date
HasDetailRanges	Boolean RO
HasLockedBranches	Boolean RO
IsBranched	Boolean RO
IsChanged	Boolean RO
IsOpen	Boolean RO
IsQueryTree	Boolean RO
IsValid	Boolean RO
IsVersionChanged	Boolean RO
IsWholeTree	Boolean RO
KeyBranchName	String RO
KeyEffDt	String RO
KeyName	String RO
KeySetID	String RO
KeyUserKeyValue	String RO

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
LeafCount	Number RO
LeafImageName	String
LeafOnClipboard	Boolean RO
LevelCount	Number RO
Levels	Level collection object RO
LevelUse	String
LockOwner	String, RO
Name	String
NodeColImage	String
NodeCount	Number RO
NodeExpImage	String
NodeOnClipboard	Boolean RO
ParentLevel	Number RO
ParentName	String RO
PerformanceMethod	String
PerformanceSelector	String
PerformanceSelectorOption	String
SetId	String
Status	String
Structure	Tree structure object RO
StructureName	String RO
TreeImageName	String
UserKeyValue	String
UseUpdateReservation	Boolean RO

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Tree Structure Methods

Method	***Returns***
Close()	Number
Copy(*FromStructId, ToStructId*)	Number
Create(*StructId, Type*)	Number
Delete(*StructId*)	Number
Open(*StructId, Update*)	Number
Rename(*FromStructId, ToStructId*)	Number
Save()	Number

Tree Structure Properties

Property	***Returns***
Description	String
DetailComponent	String
DetailField	String
DetailMenu	String
DetailMenuBar	String
DetailMenuItem	String
DetailMultiNavigate	Boolean
DetailPage	String
DetailRecord	String
IndirectionMethod	String
KeyName	String [RO]
LevelComponent	String
LevellMenu	String
LevelMenuBar	String

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Returns***
LevelMenuItem	String
LevelPage	String
LevelRecord	String
Name	String
NodeComponent	String
NodeField	String
NodelMenu	String
NodeMenuBar	String
NodeMenuItem	String
NodeMultiNavigate	Boolean
NodePage	String
NodeRecord	String
NodeUserKeyField	String
SummarySetId	String
SummaryLevelNumber	String
SummaryTreeName	String
SummaryUserKeyValue	String
Type	String

Deprecated Items and PeopleCode No Longer Supported

This section discusses the following:

- Mapping of old objects to new objects.
- Deprecated products and classes.
- Deprecated functions.
- Deprecated methods and properties.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- Deprecated BI Publisher items.
- BI Publisher items no longer supported.
- Deprecated messaging PeopleCode functions, methods and properties.
- Functions no longer supported.

Mapping of Old Objects to New Objects

In PeopleTools 8.1, the names of some of the object definitions in Application Designer changed. The names of related built-in functions have changed accordingly.

The first table lists the old terms and new terms.

In the second table, the left column lists the old names of the functions, system variables, or reserved words. The right column lists the new names. The old functions, system variables, and reserved words in this table still work in PeopleTools; however, they have been deprecated and are being retained for backward compatibility only. New applications should be created using the new functions, system variables, and reserved words.

Old Term	***New Term***
Operator	User
Panel	Page
Panel Group	Component
Business Component	Component Interface

Deprecated Function, System Variable or Reserved Word	***New Function, System Variable or Reserved Word***
DoModalPanelGroup built-in function	DoModalComponent built-in function
GetNextNumberWithGaps	GetNextNumberWithGapsCommit built-in function
IsModalPanelGroup built-in function	IsModalComponent built-in function
IsOperatorInClass built-in function	IsUserInPermissionList built-in function
PanelGroupChanged built-in function	ComponentChanged built-in function
ScheduleProcess built-in function	CreateProcessRequest built-in function
SetNextPanel built-in function	SetNextPage built-in function
TransferPanel built-in function	TransferPage built-in function
%OperatorClass System Variable	%PrimaryPermissionList System Variable
%OperatorID System Variable	%UserId System Variable

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Deprecated Function, System Variable or Reserved Word	***New Function, System Variable or Reserved Word***
%OperatorRowLevelSecurityClass System Variable	%RowSecurityPermissionList System Variable
%Panel System Variable	%Page System Variable
%PanelGroup System Variable	%Component System Variable
PANEL reserved word	PAGE reserved word
PANELGROUP reserved word	COMPONENT reserved word
PanelGroup variable declaration	Component variable declaration

Business Components are now named Component Interfaces. Therefore, for Component Interfaces, the old reserved word, methods, and system variables *are no longer valid.* You *must* use the new reserved word, methods, or system variables.

No Longer Valid	***Use Instead***
COMPONENT reserved word	COMPINTFC reserved word
GetComponent method	GetCompIntfc method
FindComponent method	FindCompIntfcs method
%Component system variable	%CompIntfc system variable

Deprecated Products and Classes

The following products and their supporting classes have been deprecated:

- PeopleSoft Business Interlinks
  - Business Interlinks class
  - BIDocs class
- PeopleSoft Mobile Agent
  - Mobile class
  - PropertyInfo collection
  - CI collection
  - Data collection
  - ListViewAttrs class
  - PropertyAttrs class
  - PeerDefaultAttributes class

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- SyncServer class

Deprecated Business Interlinks Class

PeopleSoft Business Interlinks is a deprecated product. The Business Interlinks class currently exists for backward compatibility only. For new integrations, use Integration Broker instead.

This section lists the deprecated functions, methods, and properties, as well as returns (if applicable) for the Business Interlinks and BIDocs classes.

Deprecated Business Interlink Functions

Deprecated Function	***Returns***
GetBIDoc([*XMLString*])	BIDoc object
GetInterlink(**INTERLINK**.*name*)	Business Interlink object

Deprecated Business Interlink Methods

Deprecated Method	***Returns***
AddInputRow(*inputname*, *value*)	Boolean
BulkExecute(**RECORD**.*inputrec* [, RECORD.*outputrec*] [, *user_process_inst* | *user_operid*])	Number
Clear()	None
Execute()	Number
FetchIntoRecord(**RECORD**.*recname,* [, *user_process_inst* | *user_operid*])	Number
FetchIntoRowset(*&Rowset*)	Number
FetchNextRow(*outputname, value*)	Output row object
GetFieldCount()	Number
GetFieldType(*index*)	Number
GetFieldValue(*index*)	String
InputRowset(*&Rowset*)	Number
MoveFirst()	Boolean
MoveNext()	Boolean

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Deprecated Business Interlink Property

Deprecated Property	***Returns***
StopAtError	Boolean

Deprecated BIDoc Configuration Parameters

Deprecated Configuration Parameters	***Returns***
URL	String
All other configuration parameters can be accessed like read-write properties.	Depends on type of Interlink plug-in.

Deprecated BIDoc Methods

Deprecated Method	***Returns***
AddAttribute(*attributename*, *attributevalue*)	Number
AddComment(*comment*)	Number
AddProcessingInstruction(*instruction*)	Number
AddText(*text*)	Number
CreateElement(*elementname*)	BIDoc object
GenXMLString()	String
GetAttributeName(*attributenumber*)	String
GetAttributeValue({*attributenumber* | *attributename*})	String
GetNode({*nodenumber* | *nodename*})	BIDoc object

Other Business Interlinks Features That Have Been Deprecated

Other classes include functionality specifically added for the PeopleSoft Business Interlinks product. With the deprecation of PeopleSoft Business Interlinks, these features are deprecated as well.

Deprecated Item	***Returns***
Request class, GetContentBody() method	String

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Deprecated Mobile Classes

PeopleSoft Mobile Agent is a deprecated product. These mobile classes currently exist for backward compatibility only.

This section lists the deprecated system variables, functions, methods, and properties, as well as returns (if applicable) for the mobile classes.

Deprecated Mobile Class System Variables

Deprecated System Variable	***Returns***
%DeviceType	The type of the mobile device
%MobilePage	The name of the current mobile page
%ThisMobileObject	Mobile object

Deprecated Mobile Class Functions

Deprecated Function	***Returns***
GenerateMobileTree(*CIObject* [,*CIObject_property*])	None
TransferMobilePage(**MOBILEPAGE**.*PageName*, *Tab*, *CIObject*)	None

Deprecated Mobile Class Methods

Deprecated Method	***Returns***
Create()	Boolean
Find()	Collection of empty mobile objects
Get()	Boolean
GetName()	String
GetParent()	Mobile object
GetPropertyAttrsByName(*propertyname*)	PropertyAttrs object
GetPropertyByName(*propertyname*)	Depends on property. Will return a collection if *propertyname* is a collection.
GetPropertyInfoByName(*propertyname*)	PropertyInfo object
GetTopParent()	Mobile object

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Deprecated Method	***Returns***
IsNew()	Boolean
IsNewAndNeverSaved()	Boolean
IsSameAs(*&MobileObject*)	Boolean
ReadBlobFromFile(*blobpropertyname*, *filename*	Boolean
Save()	Boolean
SetModified(*IsModified*	Boolean
SetPropertyByName(*propertyname*)	None
ValidateEnum(*propertyname*)	Boolean
ValuesDifferFromLastSync()	Boolean
WasSaved()	Boolean
WriteBlobToFile(*blobpropertyname*, *filename*)	Boolean

Deprecated Mobile Property

Deprecated Property	***Returns***
PropertyInfoCollection	PropertyInfoCollection [RO]

Deprecated PropertyInfo Collection Method

Deprecated Method	***Returns***
Item(*number*)	PropertyInfo object

Deprecated PropertyInfo Collection Property

Deprecated Property	***Returns***
Count	Number

Deprecated PropertyInfo Properties

Deprecated Property	***Returns***
DefaultValue	Depends on the value [RO]

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Deprecated Property	***Returns***
HasDefaultValue	Boolean RO
IsCollection	Boolean RO
IsRefToParent	Boolean RO
IsPeerReference	Boolean RO
IsSimpleApplicationProperty	Boolean RO
IsSystemProperty	Boolean RO
Name	String RO
PropertyInfoCollection	PropertyInfo Collection RO

Deprecated CI Collection Method

Deprecated Method	***Returns***
Item(*index*)	Mobile object

Deprecated CI Collection Property

Deprecated Property	***Returns***
Count	Number RO

Deprecated Data Collection Methods

Deprecated Method	***Returns***
DeleteItem(*location*)	Boolean
GetListAttrs(*propertyname*)	ListViewAttrs object
InsertItem(*location*)	Boolean
Item(*Index*)	Mobile object

Deprecated Data Collection Property

Deprecated Property	***Returns***
Count	Number RO

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Deprecated ListViewAttrs Method

Deprecated Method	***Returns***
IsSet(*attribute*)	Boolean

Deprecated ListViewAttrs Properties

Deprecated Property	***Returns***
DetailViewLabel	String
Label	String
ListViewLabel	String
Visible	Boolean

Deprecated PropertyAttrs Method

Method	***Returns***
IsSet(*attribute*)	Boolean

Deprecated PropertyAttrs Properties

Deprecated Property	***Returns***
DisplayOnly	Boolean
InError	Boolean
Label	String
ShowRequiredCue	Boolean
Visible	Boolean

Deprecated PeerDefaultAttributes Method

Deprecated Method	***Returns***
IsSet(*attribute*)	Boolean

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Deprecated PeerDefaultAttributes Properties

Deprecated Property	*Returns*
DisplayOnly	Boolean
Label	String
Visible	Boolean

Other Mobile Features That Have Been Deprecated

Other classes include functionality specifically added for the PeopleSoft Mobile Agent. With the deprecation of the PeopleSoft Mobile Agent, these features are deprecated as well.

Deprecated Item	*Returns*
Record class, SystemIDFieldName property	String [RO]
Record class, TimeStampFieldName property	String [RO]
Folder class, IsMobile property	Boolean
ContentReference class, IsMobile property	Boolean
ContentReference link, IsMobile property	Boolean

Deprecated SyncServer Class

PeopleSoft Mobile Agent is a deprecated product. This mobile class currently exists for backward compatibility only.

This section lists the deprecated functions, methods, and properties, as well as returns (if applicable) for the SyncServer class.

Deprecated System Variable

Deprecated System Variable	*Returns*
%SyncServer	SyncServer object

Deprecated Methods

Deprecated Method	*Returns*
AddReference(*SyncID*[, *CIDefnName*])	None
AddReferenceType(*CIDefnName*)	None

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Deprecated Method	***Returns***
CheckForChanges(*SyncDateTime*, *TotalRowCount*[, *HasRefList*])	Boolean
SelectAll()	None

Deprecated Properties

Deprecated Property	***Returns***
ClientPlatform	String
ConflictAlgorithm	String
ConflictStatus	String
ExcludeProperty	String
ExportLocation	String
IsReferenceUnresolved	Boolean, RO
LasySyncDateTime	DateTime, RO
LastSyncRowCount	Number, RO
PropertyValue	String
SessionID	String RO
Synchronizing	String
SyncIDs	Array of number
TypeID	String
validateID	String
validateRowCount	Number RO
validateVersion	String

Deprecated Functions

The first column in the following table lists built-in PeopleCode functions that existed prior to PeopleTools 8.0. The second column lists the new method or property that should be used instead of the deprecated function. The existing functions still work in PeopleTools 8.0, however, they are being

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

retained for backward compatibility only. New applications should be created using the new classes, methods, and properties.

Deprecated Function	***Use Instead***
ActiveRowCount	Rowset class, ActiveRowCount property
ClearSearchDefault	Field class, SearchDefault property
ClearSearchEdit	Field class, SearchEdit property
CompareLikeFields	Record class, CompareFields method
CopyFields	Record class, CopyFieldsTo method or CopyChangedFieldsTo method
CopyRow	Row class, CopyTo method
CurrEffDt	Rowset class, DeleteEnabled property
CurrEffRowNum	Row class, RowNumber property in combination with Rowset class, GetCurrEffRow method
CurrEffSeq	Rowset class, EffSeq property
CurrentRowNumber	Row class, RowNumber property
DeleteRecord	Record class, Delete method
DeleteRow	Rowset class, DeleteRow method
FetchValue	Field class, Value property
FieldChanged	Field class, IsChanged property
GetRelField	Field class, GetRelated method
GetStoredFormat	Field class, StoredFormat property
Gray	Field class, Enabled property
Hide	Field class, Visible property
HideRow	Row class, Visible property
HideScroll	Rowset class, HideAllRows method
InsertRow	Rowset class, InsertRow method
IsHidden	Row class, Visible property
NextEffDt	GetNextEffRow().REC.FIELD.Value
NextRelEffDt	GetNextEffRow.()REC.FIELD.GetRelated(rec.field).value

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Deprecated Function	***Use Instead***
PriorEffDt	GetPriorEffRow().REC.Field.Value
PriorRelEffDt	GetPriorEffRow().REC.FIELD.GetRelated(rec.field).value
RecordChanged	Record class, IsChanged property
RecordDeleted	Record class, IsDeleted property
RecordNew	Row class, IsNew property
RemoteCall for Application Engine	CallAppEngine function
RowFlush	Rowset class, FlushRow method
RowScrollSelect	Rowset class, Select method
RowScrollSelectNew	Rowset class, SelectNew method
ScrollFlush	Rowset class, Flush method
ScrollSelect	Rowset class, Select method
ScrollSelectNew	Rowset class, SelectNew method
SetDefault	Field class, SearchDefault property
SetDefaultAll	Rowset class, SetDefault method
SetDefaultNext	GetNextEffRow().REC.FIELD.SetDefault()
SetDefaultNextRel	GetNextEffRow().REC.Field.GetRelated(REC.FIELD). SetDefault()
SetDefaultPrior	GetPriorEffRow().REC.FIELD.SetDefault()
SetDefaultPriorRel	GetPriorEffRow().REC.Field.GetRelated(REC.FIELD). SetDefault()
SetDisplayFormat	Field class, DisplayFormat property
SetLabel	Field class, Label property
SetSearchDefault	Field class SearchDefault property
SetSearchEdit	Field class, SearchEdit property
SetTracePC	If using API (Session object), use Trace Setting class properties.
SetTraceSQL	If using API (Session object), use Trace Setting class properties.
SortScroll	Rowset class, Sort method

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Deprecated Function	*Use Instead*
TotalRowCount	Rowset class, RowCount property
Ungray	Field class, Enabled property
UnHide	Field class, Visible property
UnHideRow	Row class, Visible property
UnhideScroll	Rowset class, ShowAllRows method
UpdateValue	Field class, Value property

Deprecated Methods and Properties

The following are the methods and properties that have been deprecated.

Method or Property	*Use Instead*
Chart class, Refresh method	Chart class, SetData method Chart class, SetOLData method
Chart class, SetOLDataAnnotations method.	NA
Chart class, SetOLDataGlyphScale method.	NA
Chart class, DeviceType property.	NA
Chart class, GridLines property.	Use the PSVERTICALGRIDLINES and PSHORIZONTALGRIDLINES style classes instead to control grid line visibility and style.
Chart class, GridLineType property.	Use the PSVERTICALGRIDLINES and PSHORIZONTALGRIDLINES style classes instead to control grid line visibility and style.
Chart class, LegendStyle property.	NA
Chart class, LineType property.	NA
Chart class, MainTitleOrient property.	NA
Chart class, MainTitleStyle property.	NA
Chart class, OLLineType property.	NA
Chart class, OverrideSystemDefaultforAccessibility property.	NA
Chart class, RevertToPre850 property.	NA
Chart class, RotationAngle property.	NA

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Method or Property	***Use Instead***
Chart class, Style property.	NA
Chart class, StyleSheet property.	NA
Chart class, XAxisCross property.	NA
Chart class, XAxisScaleResolution property.	NA
Chart class, XAxisStyle property.	NA
Chart class, XAxisTitleStyle property.	NA
Chart class, XRotationAngle property.	NA
Chart class, YAxisScaleResolution property.	NA
Chart class, YAxisStyle property.	NA
Chart class, YAxisTitleStyle property.	NA
Chart class, YRotationAngle property.	NA
Chart class, ZRotationAngle property.	NA
DialGauge class, DeviceType property.	NA
Gantt class, Refresh method	Gantt class, SetTaskAppData method Gantt class, SetTaskData method
Gantt class, SetDayFormat method: %Chart_DayFormat_ DOY_2Digit constant.	This constant has been deprecated; if specified, it defaults to %Chart_DayFormat.
Gantt class, SetHourFormat method.	The hour format is determined by a user's personalization settings.
Gantt class, SetLegend method.	NA
Gantt class, SetMinuteFormat method.	The minute format is determined by a user's personalization settings.
Gantt class, SetSecondFormat method.	The second format is determined by a user's personalization settings.
Gantt class, SetTableXScrollbar method.	NA
Gantt class, SetTaskExpanded method.	NA
Gantt class, SetTaskHints method.	NA
Gantt class, SetYearFormat method: %Chart_YearFormat constant.	This constant has been deprecated; if specified, it defaults to %Chart_YearFormat _4Digit.
Gantt class, DataEndDateTime property.	NA

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Method or Property	***Use Instead***
Gantt class, DataStartDateTime property.	NA
Gantt class, DataStartRow property.	NA
Gantt class, DataWidth property.	NA
Gantt class, HasLegend property.	NA
Gantt class, ImageMap property.	NA
Gantt class, IsPlainImage property.	NA
Gantt class, LegendPosition property.	NA
Gantt class, LegendStyle property.	NA
Gantt class, MainTitle property.	NA
Gantt class, MainTitleStyle property.	NA
Gantt class, RevertToPre850 property.	NA
Gantt class, StyleSheet property.	NA
Gantt class, XAxisPosition property.	NA
Gantt class, YAxisPosition property.	NA
LEDGauge class, DeviceType property.	NA
Query class, RunToTemplate method	No longer supported. This method remains in PeopleTools for PeopleSoft internal use only and should not be implemented in PeopleCode programs.
Session class, Connect method	%Session system variable
Session class FindTree, FindTreeStructure methods	GetTree, GetTreeStructure session class methods (respectively)
StatusMeterGauge class, DeviceType property.	NA
Tree collection	All tree collection methods and properties have been deprecated. Use GetTree to access a tree instead.
Tree structure collection	All tree structure collection methods and properties have been deprecated. Use GetTreeStructure to access a tree structure instead.
Item tree branch collection method, and the First, Last, and Next tree branch collection properties	NA

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Method or Property	*Use Instead*
Tree class methods: • FindNextDisplayObject • FindPreviousDisplayObject	NA
Tree class properties: • CheckLeafUserData • DisplayLeaf • DisplayNode • IsReadOnly	NA

Deprecated BI Publisher Items

As of PeopleTools 8.50, a number of BI Publisher (formerly XML Publisher) classes, methods and properties have been deprecated. These items remain in PeopleTools for backward compatibility only.

Deprecated BI Publisher Methods

Deprecated Method	*Use Instead*
ReportDefn class, SetRuntimeDataRowset method **Note:** The rowset data source has been deprecated.	Convert the rowset to an XML file—for example, using the file layout capabilities of the File class is one way to accomplish this. Then, use the SetRuntimeDataXMLFile method of the ReportDefn class to process the XML file as a data source.
ReportDefn class, SetRuntimeDataXMLDoc method **Note:** The XmlDoc data source has been deprecated.	Convert the XmlDoc object to an XML file—for example, using the genXmlFile method of the XmlDoc class is one way to accomplish. Then, use the SetRuntimeDataXMLFile method of the ReportDefn class to process the XML file as a data source.
Note: The rowset data source has been deprecated. RowsetDS class: • AddXMLData method • AddXSDSchema method • GetXMLData method • GetXSDSchema method • RowsetDS method	Convert the rowset to an XML file—for example, using the file layout capabilities of the File class is one way to accomplish this. Then, use the SetRuntimeDataXMLFile method of the ReportDefn class to process the XML file as a data source.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Deprecated BI Publisher Properties

Deprecated Property	*Use Instead*
OutputEditable	Use the Report Definition-Definition page (PSXPRPTPROP) to set report properties to override global properties.

BI Publisher Items No Longer Supported

As of PeopleTools 8.50, a number of BI Publisher (formerly XML Publisher) classes, methods and properties are no longer supported. These items remain in PeopleTools for PeopleSoft internal use only and should not be implemented in PeopleCode programs.

- All methods and properties of the DataSourceDefn class.
- Certain methods and properties of the ReportDefn class.
- All methods and properties of the TemplateDefn class.
- All methods and properties of the TemplateFile class.
- All methods and properties of the TranslationFile class.
- All methods of the XMLPManager class.
- All methods of the QueryDS class.
- All methods and properties of the EFTPRocessor class.
- All methods and properties of the FOProcessor class.
- All methods and properties of the FormProcessor class.
- All methods and properties of the FOUtility class.
- All methods and properties of the PDFMapTool class.
- All methods and properties of the RTFProcessor class.

DataSourceDefn Class Methods

Method	*Use Instead*
DataSourceDefn(*DataSourceID*, *DataSourceType*, *Public*)	NA
Get()	NA
GetData(*&PromptRecord*)	NA
GetSampleData()	NA
GetSchema	NA

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

DataSourceDefn Class Properties

Property	***Use Instead***
ActiveFlag	NA
Description	NA
IsPublic	NA
LastUpdatedBy	NA
LastUpdateDTTM	NA
Name	NA
ObjectOwnerId	NA
RegisteredBy	NA
RegisteredDTTM	NA
Type	NA

ReportDefn Class Methods

Method	***Use Instead***
GetActiveTemplatesByDistributionChannel(*DistributionChannel*, *AsOfDate*)	NA
GetDataSource()	NA
GetDefaultTemplate()	NA
GetTemplate(*TemplateID*)	NA
GetTemplateList()	NA
ProcessEtextReport(*TemplateID*, *LanguageCd*, *AsOfDate*)	ReportDefn class, ProcessReport method

ReportDefn Class Properties

Property	***Use Instead***
AllowRecipientEntry	NA
AllowViewerEntry	NA

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Use Instead***
ArchiveAfter	NA
BurstFieldName	NA
CategoryId	NA
ID	NA
IsReadOnly	NA
LastUpdateDTTM	NA
LastUpdatedOprId	NA
ObjectOwnerId	NA
RegisteredBy	NA
RegisteredDTTM	NA
SecurityFieldName	NA
SecurityIdType	NA
SecurityJoinTable	NA
TemplateControlFieldName	NA

TemplateDefn Class Methods

Method	***Use Instead***
TemplateDefn(*TemplateID*)	NA
Get()	NA
GetActiveTemplateFile(*AsOfDate*)	NA
GetTemplateFile()	NA
GetTemplateFileList()	NA

TemplateDefn Class Properties

Property	***Use Instead***
Description	NA

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Use Instead***
DistributionChannel	NA
ID	NA
IsReadOnly	NA
IsSubTemplate	NA
LanguageCode	NA
LastUpdateDTTM	NA
LastUpdatedOprId	NA
ObjectOwnerId	NA
RegisteredBy	NA
RegisteredDTTM	NA
ReportCategoryId	NA
Type	NA

TemplateFile Class Methods

Method	***Use Instead***
TemplateFile(*&TemplateDefn*, *EffDate*)	NA
GetFile()	NA
GetMapFile()	NA
GetTranslationFile(*LanguageCD*)	NA
GetTranslationFileList()	NA

TemplateFile Class Properties

Property	***Use Instead***
EffectiveDate	NA
FileName	NA
MapFileName	NA

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Property	***Use Instead***
Status	NA

TranslationFile Class Method

Method	***Use Instead***
TranslationFile(*&TemplateDefn*, *EffectiveDate*, *LanguageCode*)	NA
GetFile()	NA

TranslationFile Class Properties

Property	***Use Instead***
Description	NA
FileName	NA
LanguageCode	NA
Status	NA

XMLPManager Class Methods

Method	***Use Instead***
GetDatasourceDefnList(*DataSourceId*, *DataSourceIdOp*, *DataSourceType*, *Owner*, *Descr*, *DescrOp*, *ObjectOwnerId*, *Active*, *CaseSensitive*)	NA
GetReportDefnList(*ReportID*, *ReportIdOp*,*Descr*, *DescrOp* , *TemplateId*,*TemplateIdOp*, *TemplateDescr*, *TemplateDescrOp*, *DatasourceType*, *DataSourceId*, *DataSourceIdOp*, *DataSourceOwner*, *TemplateType*, *ReportCategoryId*, *ReportStatus*, *CaseSensitive*)	NA
GetTemplateDefnList(*TemplateId*, *TemplateIdOp*, *Descr*, *DescrOp*, *TemplateType*, *DistChannel*, *ReportCategoryId*, *IsSubtemplate*, *CaseSensitive*)	NA

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

QueryDS Class Methods

Method	***Use Instead***
QueryDS()	NA
GetXMLData(*&Query*, *&Rowset*, *XSDLocation*)	NA
GetXMLSampleData(*&Query*, *&Rowset*, *Rows*, *XSDLocation*)	NA
GetXSDSchema(*&Query*)	NA

ETFProcessor Class Methods

Method	***Use Instead***
EFTProcessor()	
GenerateOutput(*EFTFile*, *XMLDataFile*, *OutputFile*, *Error*)	ReportDefn class, ProcessReport method
GenerateXSL(*RTFTemplateFile*, *XSLOutputFile*, *Error*)	ReportDefn class, ProcessReport method

EFTProcessor Class Properties

Property	***Use Instead***
ConfFile	ReportDefn class, ProcessReport method
ConfProp	ReportDefn class, ProcessReport method

FOProcessor Class Methods

Method	***Use Instead***
FOProcessor()	ReportDefn class, ProcessReport method
GenerateMergedOutput(*&XSLTemplateFileArray*, *&XMLDataFileArray*, *&XliffFileArray*, *OutputFileName*, *OutputFormat*, *Error*)	ReportDefn class, ProcessReport method
GenerateMergedOutputFO(*&FOFIleArray*, *OutputFile*, *OutputFormat*, *Error*)	ReportDefn class, ProcessReport method
GenerateOutput(*XSLTemplateFile*, *XMLDataFile*, *XLiffFile*, *OutputFile*, *OutputFormat*, *Error*)	ReportDefn class, ProcessReport method
GenerateOutputFO(*FOFileName*, *OutputFile*, *OutputFormat*, *Error*)	ReportDefn class, ProcessReport method

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

FOProcessor Class Properties

Property	***Use Instead***
ConfFile	ReportDefn class, ProcessReport method
ConfProp	ReportDefn class, ProcessReport method
Locale	ReportDefn class, ProcessReport method

FormProcessor Class Methods

Method	***Use Instead***
FormProcessor()	ReportDefn class, ProcessReport method
ExtractFieldNames(*PDFTemplateFileName*, *IncludeReservedNames*, *FieldNameArray*, *Error*)	ReportDefn class, ProcessReport method
ExtractFieldValues(*PDFTemplateFileName*, *IncludeReservedNames*, *FieldValueArray*, *Error*)	ReportDefn class, ProcessReport method
FillForm(*PDFTemplateFile*, *XMLDataFile*, *PDFOutputFile*, *Error*)	ReportDefn class, ProcessReport method

FormProcessor Class Properties

Property	***Use Instead***
ConfFile	ReportDefn class, ProcessReport method
ConfProp	ReportDefn class, ProcessReport method
Locale	ReportDefn class, ProcessReport method

FOUtility Class Methods

Method	***Use Instead***
FOUtility()	ReportDefn class, ProcessReport method
GenerateFO(*XSLFile*, *XMLDataFile*, *OutputFOFile*, *Error*)	ReportDefn class, ProcessReport method
MergeFOs(*&FOFileArray*, *OutputFOFile*, *Error*)	ReportDefn class, ProcessReport method

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

FOUtility Class Property

Property	***Use Instead***
Prop	ReportDefn class, ProcessReport method

PDFMapTool Class Methods

Method	***Use Instead***
PDFMapTool()	ReportDefn class, ProcessReport method
EnableMap(*XSDFile*, *PDFTemplateFile*, *XMLInputFile*, *PDFOutputFile*)	ReportDefn class, ProcessReport method
extractMap(*PDFFile*, *OutMapFile*)	ReportDefn class, ProcessReport method
processForm(*PDFTemplateFile*, *XMLDataFile*, *MapFile*, *OutputPDFFile*)	ReportDefn class, ProcessReport method

PDFMapTool Class Property

Property	***Use Instead***
Locale	ReportDefn class, ProcessReport method

RTFProcessor Class Methods

Method	***Use Instead***
RTFProcessor()	ReportDefn class, ProcessReport method
GenerateXSL(*RTFTemplateFile*, *XSLOutputFile*, *Error*)	ReportDefn class, ProcessReport method
GenerateXSLXliff(*RTFTemplateName*, *XSLOutputFile*, *XliffOutputFile*, *Error*)	ReportDefn class, ProcessReport method

RTFProcessor Class Properties

Property	***Use Instead***
ConfFile	ReportDefn class, ProcessReport method
ConfProp	ReportDefn class, ProcessReport method
Locale	ReportDefn class, ProcessReport method

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Deprecated Messaging PeopleCode Functions, Methods and Properties

In PeopleTools 8.48, messaging changed significantly. Many of the messaging PeopleCode functions, methods and properties are either deprecated or no longer supported, or their syntax changed.

See Understanding Message Classes.

See "PeopleSoft Integration Broker Metadata" (PeopleTools 8.54: Integration Broker).

Changed Messaging PeopleCode

The following are still valid, however, their syntax changed significantly.

- CreateMessage built-in function
- IntBroker class, GetMessageErrors method
- IntBroker class, SetMessageError method

Deprecated Messaging PeopleCode Built-in Functions

The following table lists the deprecated messaging PeopleCode built-in functions, as well as the method that should be used instead.

Deprecated Function	***Replacement Method***
CancelPubHeaderXmlDoc	IntBroker class method Cancel, specifying a message type of %IntBroker_BRK
CancelPubXmlDoc	IntBroker class method Cancel, specifying a message type of %IntBroker_PUB
CancelSubXmlDoc	IntBroker class method Cancel, specifying a message type of %IntBroker_SUB
ConnectorRequest	IntBroker class method ConnectorRequest
ConnectorRequestURL	IntBroker class method ConnectorRequestURL
GetMessage	IntBroker class method GetMessage
GetMessageXmlDoc	Message class method GetXmlDoc
GetPubHeaderXmlDoc	IntBroker class method GetMessage specifying a message type of %IntBroker_BRK
GetPubXmlDoc	IntBroker class method GetMessage specifying a message type of %IntBroker_PUB
GetSubXmlDoc	IntBroker class method GetMessage specifying a message type of %IntBroker_SUB

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Deprecated Function	*Replacement Method*
GetSyncLogData	IntBroker class method GetSyncLogData
InBoundPublishXmlDoc	IntBroker class method InboundPublish
IsMessageActive	IntBroker class method IsOperationActive
PublishXmlDoc	IntBroker class method Publish
ReSubmitPubHeaderXmlDoc	IntBroker class method Resubmit specifying a message type of %IntBroker_BRK
ReSubmitPubXmlDoc	IntBroker class method Resubmit specifying a message type of %IntBroker_PUB
ReSubmitSubXmlDoc	IntBroker class method Resubmit specifying a message type of %IntBroker_SUB
SetChannelStatue	IntBroker class method SetQueueStatus
SyncRequestXmlDoc	IntBroker class method SyncRequest
UpdateXmlDoc	IntBroker class method UpdateXmlDoc

The following built-in functions are no longer supported. You will receive an error if you try to use them in a PeopleCode program.

- CreateWSDLMessage
- GetArchPubHeaderXmlDoc
- GetArchPubXmlDoc
- GetArchSubXmlDoc
- GetArchSubXmlDoc
- GetArchSyncLogData
- GetSyncLogData

Note: ReturnToServer is a special case of a built-in function that's no longer supported. The deprecated handler for OnRequest subscriptions cannot be upgraded. ReturnToServer can only be used in an OnRequest event fired using the deprecated handler. This means that ReturnToServer no longer works and is not valid in any case other than when the code has already been written and used in a deprecated handler.

Deprecated Message Class Methods and Properties

The following are the Message class methods and properties that have been deprecated.

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Deprecated Method	*Replacement Method*
GetQueryString	IBConnectorInfo collection GetQueryStringArgName method
InBoundPublish	IntBroker class InBoundPublish method
Publish	IntBroker class Publish method
SetQueryString	IBConnectorInfo collection AddQueryStringArg method
SetStatus	IntBroker class SetStatus method
SyncRequest	IntBroker class SyncRequest method
Update	IntBroker class Update method

The following are the Message class properties that have been deprecated.

Deprecated Property	*Replacement Property*
ChannelName	Message class QueueName property
Cookies	IBConnectorInfo collection Cookies property
DefaultMessageVersion	Message class OperationVersion property
GUID	Message class TransactionId property
IsActive	Message class IsOperationActive property
PubId	Message class QueueSeqId property
SubName	Message class ActionName property
SubscriptionProcessId	Message class TransactionId property
MessageChannel	IBInfo class MessageQueue property
MessageType	IBInfo class OperationType property

The following Message class properties are no longer supported. You will receive an error if you try to use them in your PeopleCode program.

- MessageDetail
- PublicationId

Additional Messaging Deprecated Methods and Properties

The following additional methods and properties are either deprecated or no longer supported:

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

- The IBInfo class method LoadConnectorPropFromTrx is no longer supported.
- The IBInfo class MessageChannel property has been deprecated. Use the IBInfo class MessageQueue property instead.
- The IBInfo class PublicationID property is no longer supported.

Integration Broker Web Service Discovery Class No Longer Supported

The Integration Broker Web Service Discovery class is no longer supported. The following methods are empty and should not be used.

- FindCIWebServices
- FindMsgWebServices
- FindWebServices
- GetCIWebServiceWSDL
- GetMsgWebServiceWSDL
- GetWSDL

Functions No Longer Supported

The following functions no longer work. You will receive an error if you try to use them in your PeopleCode program.

Function	***Description***
%MessageAgent	Used with Message Agent activities
ChDir	Used only on the client with DOS
ChDrive	Used only on the client with DOS
CheckMenuItem	Used with menu items
Codeb	Used before true Unicode integration
DBCSTrim	Used before true Unicode integration
Findb	Used before true Unicode integration
GetControl	Used with ActiveX controls
GetControlOccurence	Used with ActiveX controls
GetCwd	Used only on the client with DOS
GetMessageInstance	Used with messaging
GetPubContractInstance	Used with messaging

Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.

Function	***Description***
GetSelectedTreeNode	Used with dynamic trees
GetSubContractInstance	Used with messaging
GetTreeNodeParent	Used with dynamic trees
GetTreeNodeRecordName	Used with dynamic trees
IsDisconnectedClient	Used with PeopleSoft Mobile Agent.
MSFGetNextNumber	Used with PeopleSoft Mobile Agent.
Lenb	Used before true Unicode integration
RefreshTree	Used with dynamic trees
ScheduleProcess	Used with PeopleSoft Process Scheduler
Substringb	Used before true Unicode integration
UnCheckMenuItem	Used with menu items
WinEscape	Used only on client
WinExec	Used only on client

 Copyright © 1988, 2016, Oracle and/or its affiliates. All rights reserved.