

Oracle® Revenue Management and Billing

Version 3.1.0.0.0

Database Administrator's Guide

Revision 20.10

F45682-01

September 2021

ORACLE®

Oracle Revenue Management and Billing Database Administrator's Guide

F45682-01

Copyright Notice

Copyright © 2009, 2021 Oracle and/or its affiliates. All rights reserved.

Trademark Notice

Oracle, Java, JD Edwards, PeopleSoft, and Siebel are registered trademarks of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Xeon are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Opteron, the AMD logo, and the AMD Opteron logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

License Restrictions Warranty/Consequential Damages Disclaimer

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or de-compilation of this software, unless required by law for interoperability, is prohibited.

Warranty Disclaimer

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

Restricted Rights Notice

If this software or related documentation is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, the following notice is applicable:

U.S. GOVERNMENT RIGHTS

Oracle programs, including any operating system, integrated software, any programs installed on the hardware, documentation, and/or technical data delivered to U.S. Government end users are "commercial computer software" or "commercial technical data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, documentation, and/or technical data shall be subject to license terms and restrictions as mentioned in Oracle License Agreement, and to the extent applicable, the additional rights set forth in FAR 52.227-19, Commercial Computer Software-- Restricted Rights (June 1987). No other rights are granted to the U.S. Government.

Hazardous Applications Notice

This software is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure the safe use of this software. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software in dangerous applications.

Third-Party Content, Products, and Services Disclaimer

This software and documentation may provide access to or information on content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.

Preface

About This Document

This document will help you to understand how to install and maintain the Oracle Revenue Management and Billing (ORMB) database.

Intended Audience

This document is intended for the following audience:

- End-Users
- Database Administrators
- Consulting Team
- Implementation Team

Organization of the Document

The information in this document is organized into the following sections:

Section No.	Section Name	Description
Section 1	Database Overview	Lists the database server supported on each platform. It also lists the dos and don'ts while maintaining a database.
Section 2	Installing Oracle Revenue Management and Billing Version 3.1.0.0.0 Database	Explains how to install the Oracle Revenue Management and Billing database.
Section 3	Database Design	Lists the naming conventions for various database objects. It also lists and describes the column data types and foreign key constraints.
Section 4	Exadata Database Settings	Lists a set of activities that you need to perform if you are using the Oracle Exadata Database machine as the database server.
Section 5	Database Implementation Guidelines	Lists and describes the general guidelines for configuring various objects in the database and implementing Oracle Database.
Appendix A	New Objects in the Oracle Revenue Management and Billing V3.1.0.0.0 Database	Lists the objects that are newly added in the Oracle Revenue Management and Billing V3.1.0.0.0 database.

Section No.	Section Name	Description
Appendix B	Application Services Configured for Default User Group	Lists the application services configured for the default user groups shipped with Oracle Revenue Management and Billing Version 3.1.0.0.0.
Appendix C	Changing the DB User Password	Explains how to change the database user password.
Appendix D	New Objects in the Oracle Utilities Application Framework V4.4.0.3.0 Database	Lists the objects that are newly added in the Oracle Utilities Application Framework V4.4.0.3.0 database.
Appendix E	Oracle Utilities Application Framework System Table Guide	Lists the system tables owned by Oracle Utilities Application Framework V4.4.0.3.0 and explains the standards and guidelines to be followed while updating the data in the system tables.
Appendix F	ORMB V3.1.0.0.0 Rollup Packs	Lists the rollup packs available for Oracle Revenue Management and Billing Version 3.1.0.0.0. It also explains how to apply a rollup pack.
Appendix G	License and Copyright Notices	Lists all notices with reference to usage of third party products.

Conventions

The following conventions are used across this document:

Convention	Meaning
boldface	Boldface indicates graphical user interface elements associated with an action, or terms defined in the text.
<i>italic</i>	Italic indicates a document or book title.
<code>monospace</code>	Monospace indicates commands within a paragraph, URLs, code in examples, text that appears on the screen or entered in the application.

Acronyms

The following acronyms are used in this document:

Acronym	Meaning
ORMB	Oracle Revenue Management and Billing
RDS	Reliable Datagram Sockets
UAT	User Acceptance Testing

Acronym	Meaning
DBCA	Database Configuration Assistant
OUAF	Oracle Utilities Application Framework
FW	Framework
TDE	Transparent Data Encryption
ASSM	Automatic Segment Space Management
AMM	Automatic Memory Management
ASMM	Automatic Shared Memory Management
PDB	Pluggable Database
CDB	Container Database
LOB	Large Object
AWR	Automatic Workload Repository
CBO	Cost-Based Optimizer
USD	United States Dollar
NORTHAM	North America
EURO	Europe
CM	Customer Modification
ENG	English
UTC	Coordinated Universal Time
ICU4J	International Components for Unicode

Related Documents

You can refer to the following documents for more information:

Document Name	Description
<i>Oracle Revenue Management and Billing Version 3.1.0.0 Release Notes</i>	Provides a brief description about the new features, enhancements, and UI level changes introduced in the current release. The new features and enhancements are classified under three distinct heads – Generic (which is intended for both domains), Financial Services, and Health Insurance. It also contains high-level information about the supported platforms, framework upgrade, supported upgrades, and documentation updates. In addition, it contains a list of discontinued features, planned deprecation notices, customer bugs fixed or forward ported and known issues in the current release.

Document Name	Description
<i>Oracle Revenue Management and Billing Installation Guide</i>	<p>Provides an overview about the application architecture. It contains detailed information about the software and hardware requirements, supported platforms, application server and database space requirements, and application server pre-requisites for supported platforms. It explains the installation and configuration menu options which are available during installation and advanced menu options which are available post installation. It also explains how to configure WebSphere application server and how to install OUAF, OUAF rollup packs, ORMB, and ORMB patches or rollup packs.</p> <p>It contains appendices which lists ORMB rollup packs and notices about third party JAR and other components.</p>
<i>Oracle Revenue Management and Billing Quick Installation Guide</i>	<p>Provides information about the media packs which are available for the current release. It contains information about the supported platforms, space requirements, and release-specific documentation library. In addition, it contains high-level information on how to install ORMB and selected additional software.</p>
<i>Oracle Revenue Management and Billing Server Administration Guide</i>	<p>Provides detailed information about the product architecture, native support, directory structures, environment variables, logs, etc. It explains various concepts related to the batch server and lists and describes the scripts required for installing and configuring ORMB. It explains how to monitor the system and configure Web browser, Web application server, business application server, inbound web services, and batch server. It explains how to provide Oracle Cloud Support and how to integrate and monitor Oracle Scheduler.</p> <p>It contains various appendices which lists and describes the parameters available in the ENVIRON.INI, Web.xml, spl.properties, hibernate.properties, submitbatch.properties, threadpoolworker, coherence-cache.config.xml, and tangosol-coherence-override.xml files.</p>

Document Name	Description
<i>Oracle Revenue Management and Billing Security Guide</i>	Highlights what's new in security! Describes all the security features available in ORMB for authentication, authorization, user access, database access, LDAP and SSO integration, audit, encryption, web services, and JNDI access. It also describes how to provide support for data masking, Oracle cloud object storage, groovy, HTTP proxy, keystore, truststore, whitelist, federated architecture, and object erasure. In addition, it explains how to garble the customer information.
<i>Oracle Revenue Management and Billing Direct Database Upgrade Guide</i>	Explains how to directly upgrade the ORMB database from 2.3.0.2.0 or any later version to the current release. It also highlights any known issues during direct database upgrade and how to handle these issues in the database.

Change Log

Revision	Last Update	Updated Section	Comments
20.1	23-Sep-2021	Appendix A: New Objects in the Oracle Revenue Management and Billing V3.1.0.0.0 Database	Updated Information
		Appendix D: New Objects in the Oracle Utilities Application Framework V4.4.0.3.0 Database	Updated Information
20.2	27-Oct-2021	Appendix G.1.2: Notice Concerning Usage of Apache Software	Updated Information
		Appendix G.1.4: Notice Concerning Usage of Bouncy Castle Crypto API	Updated Information
		Appendix G.1.23: Notice Concerning Usage of SLF4J	Updated Information
		Section 2.3.1.6: Post Installation Tasks	Updated Information
		Appendix F: ORMB V3.1.0.0.0 Rollup Packs	Updated Information
		Appendix A.1.1: New Tables	Updated Information
		Appendix A.1.2: Added Columns	Updated Information
		Appendix A.2.9: Zones	Updated Information
		Appendix A.2.10: UI Maps	Updated Information
		Appendix A.2.17: To Do Types	Updated Information
20.3	22-Nov-2021	Section 2.1: Installation Overview	Added Information

Revision	Last Update	Updated Section	Comments
		Section 2.2: Creating the Database	Added Information
		Section 2.3: Oracle Database Installation	Added Information
		Section 2.3.2: Demo Install	Added Section
20.4	14-Jan-2022	-	Added Bookmarks in PDF
20.5	04-Mar-2022	Section 2.3.1.4: Installing Oracle Utilities Application Framework	Updated Information
		Section 2.3.1.5: Installing Oracle Revenue Management and Billing	Updated Information
20.6	29-Jun-2022	Section 2.3.2.1: Copying and Decompressing Demo Dump Patch	Added Information
		Section 2.3.2.4: Importing the Demo Dump File	Added Information
20.7	14-Jul-2022	Section 5.2.3: Table Partitioning Strategy	Updated Information
20.8	25-Jul-2022	Section 5.2.3: Table Partitioning Strategy	Updated Information
20.9	17-Nov-2022	Section 2.2: Creating the Database	Updated Information
		Section 2.3.1.4: Installing Oracle Utilities Application Framework	Updated Information
		Section 2.3.1.5: Installing Oracle Revenue Management and Billing	Updated Information
		Section 2.3.3: Configuring Security	Removed Section
20.10	15-Dec-2022	Section 2.3: Oracle Database Installation	Removed Information

Contents

1.	Database Overview	1
1.1	Supported Database Platforms	1
1.1.1	Supported Platforms Summary Table.....	1
1.1.2	Support for Software Patches and Upgrades	2
1.2	Database Maintenance Rules.....	2
1.2.1	Permitted Database Changes.....	2
1.2.2	Non-Permitted Database Changes.....	3
2.	Installing Oracle Revenue Management and Billing Version 3.1.0.0.0 Database	4
2.1	Installation Overview.....	4
2.2	Creating the Database	4
2.3	Oracle Database Installation	6
2.3.1	Initial Install, or Installing Version 3.1.0.0.0 for the First Time.....	7
2.3.2	Demo Install.....	20
2.3.3	Populating Language Data	26
3.	Database Design	27
3.1	Database Object Standard.....	27
3.1.1	Categories of Data.....	27
3.1.2	Naming Standards.....	27
3.2	Column Data Type and Constraints	31
3.2.1	User Defined Code	31
3.2.2	System Assigned Identifier.....	31
3.2.3	Date/Time/Timestamp.....	31
3.2.4	Number	31
3.2.5	Fixed Length/Variable Length Character Columns	31
3.2.6	Null Column Support.....	32
3.2.7	XML Type Support.....	32
3.2.8	Cache and Key Validation Flags.....	32
3.2.9	Table Classification and Table Volume Flags	32
3.2.10	Default Value Setting	33
3.2.11	Foreign Key Constraints	33
3.3	Standard Columns	33
3.3.1	Owner Flag	33
3.3.2	Version	33
4.	Exadata Database Settings	34
5.	Database Implementation Guidelines	35
5.1	Configuration Guidelines.....	35
5.1.1	Index.....	35

5.1.2	Temporary and Undo Tablespace	36
5.1.3	Transparent Data Encryption Recommendations.....	36
5.1.4	Data Compression Recommendations.....	36
5.1.5	Database Vault Recommendations.....	37
5.1.6	Information Lifecycle Management (ILM) and Data Archiving Support.....	37
5.1.7	Storage Recommendations.....	37
5.1.8	Database Configuration Recommendations.....	38
5.1.9	Database Syntax.....	38
5.1.10	Database Initialization Parameters.....	39
5.1.11	Shrink Tables	42
5.1.12	Listener.ora Settings	43
5.2	Implementation Guidelines	43
5.2.1	Materialized View	43
5.2.2	Increase INITRANS Values	45
5.2.3	Table Partitioning Strategy	47
5.2.4	Performance Monitoring	52
5.2.5	Local Undo Mode in Oracle Database 12c Release 2.....	52
5.2.6	Memory Resource Management for PDBs in Oracle Database 12c Release 2	53
5.2.7	Global Optimizer Statistics Settings	53
5.2.8	Optimizer Statistics Advisor	55
5.2.9	Using the Segment Advisor	58
Appendix A :	New Objects in the Oracle Revenue Management and Billing V3.1.0.0.0 Database	62
A.1	Schema Changes.....	62
A.1.1	New Tables.....	62
A.1.2	Added Columns.....	63
A.1.3	Dropped Tables.....	65
A.1.4	Dropped Columns	65
A.1.5	Added Views	65
A.1.6	Column Format Change	65
A.2	New System Data	65
A.2.1	Algorithm Types	65
A.2.2	Algorithms.....	66
A.2.3	Business Services	67
A.2.4	Portals	69
A.2.5	Batch Controls.....	69
A.2.6	Foreign Key References.....	70
A.2.7	Scripts.....	70
A.2.8	New Zones In Existing Portals	71
A.2.9	Zones.....	72

A.2.10 UI Maps	74
A.2.11 Lookups	76
A.2.12 Characteristic Types	77
A.2.13 Feature Configurations	78
A.2.14 Zone Types	78
A.2.15 Business Objects	78
A.2.16 Maintenance Objects	79
A.2.17 To Do Types	79
A.2.18 Application Services	79
Appendix B : Application Services Configured for Default User Group	81
B.1 ALL_SERVICES	81
B.2 C1_BSERCIVES	97
B.3 HCADMIN	110
B.4 INADMIN	121
Appendix C : Changing the DB User Password	133
Appendix D : New Objects in the Oracle Utilities Application Framework V4.4.0.3.0 Database	134
D.1 Schema Changes	134
D.1.1 New Tables	134
D.1.2 Added Views	135
D.1.3 Dropped Tables	136
D.1.4 Unsupported Tables	136
D.1.5 Added Columns	136
D.1.6 Dropped Columns	139
D.1.7 Dropped Lookups	139
D.1.8 Column Format Change	140
D.2 New System Data	140
D.2.1 Algorithms	140
D.2.2 Algorithm Types	141
D.2.3 Zones	142
D.2.4 New Zones In Existing Portals	148
D.2.5 UI Maps	149
D.2.6 Maintenance Objects	151
D.2.7 To Do Types	152
D.2.8 Business Services	152
D.2.9 Portals	154
D.2.10 Business Objects	156
D.2.11 Lookups	158
D.2.12 Foreign Key References	162
D.2.13 Batch Controls	162

D.2.14 Application Services	166
D.2.15 Characteristic Types	169
D.2.16 Scripts.....	169
Appendix E : Oracle Utilities Application Framework System Table Guide	175
E.1 About System Tables	175
E.2 System Table Standards	175
E.3 Guidelines for System Table Updates.....	176
E.3.1 Business Configuration Tables	176
E.3.2 Development and Implementation System Tables.....	178
E.4 System Table List	192
Appendix F : ORMB V3.1.0.0.0 Rollup Packs	205
F.1 Applying a Rollup Pack.....	205
Appendix G : License and Copyright Notices.....	206
G.1 Third-Party Products.....	207
G.1.1 Notice Concerning Usage of ANTLR	207
G.1.2 Notice Concerning Usage of Apache Software	207
G.1.3 Notice Concerning Usage of ASM	212
G.1.4 Notice Concerning Usage of Bouncy Castle Crypto API.....	213
G.1.5 Notice Concerning Usage of CodeMirror.....	214
G.1.6 Notice Concerning Usage of Concurrent	214
G.1.7 Notice Concerning Usage of Cordova Plugin Pin Check.....	214
G.1.8 Notice Concerning Usage of Cordova Plugin Fingerprint aio.....	215
G.1.9 Notice Concerning Usage of Cordova Plugin Secure Keystore	215
G.1.10 Notice Concerning Usage of Cordova Plugin Shared Preferences	216
G.1.11 Notice Concerning Usage of DOM4J.....	216
G.1.12 Notice Concerning Usage of FullCalendar	217
G.1.13 Notice Concerning Usage of Graph Builder	217
G.1.14 Notice Concerning Usage of International Components for Unicode (ICU4J).....	218
G.1.15 Notice Concerning Usage of Jaxen.....	218
G.1.16 Notice Concerning Usage of JQuery (3.5.1)	219
G.1.17 Notice Concerning Usage of JQueryMobile	219
G.1.18 Notice Concerning Usage of JQuery UI	220
G.1.19 Notice Concerning Usage of JSIgnition	220
G.1.20 Notice Concerning Usage of Knockout	220
G.1.21 Notice Concerning Usage of Microsoft .NET.....	221
G.1.22 Notice Concerning Usage of Moment.js	224
G.1.23 Notice Concerning Usage of SLF4J	225
G.1.24 Notice Concerning Usage of Staxmate	225
G.1.25 Notice Concerning Usage of Swagger-UI	226

G.1.26 Notice Concerning Usage of XMLPULL.....	231
G.1.27 Notice Concerning Usage of XStream	231

1. Database Overview

This section provides an overview of the Oracle Revenue Management and Billing database, including:

- [Supported Database Platforms](#)
- [Database Maintenance Rules](#)

1.1 Supported Database Platforms

This section defines the platforms on which Oracle Revenue Management and Billing is verified to operate.

1.1.1 Supported Platforms Summary Table

Oracle Revenue Management and Billing (ORMB) is supported on the following platforms:

Platform	Database Server
AIX 7.2 TL0+ ¹ (64-bit)	Oracle Database Server 19c
Oracle Linux 7.x ² or 8.x ² (64-bit)	Oracle Database Server 19c
Red Hat Enterprise Linux ³ 7.x ² or 8.x ² (64-bit)	Oracle Database Server 19c
Oracle Solaris 11.3+ ¹ (SPARC 64-bit)	Oracle Database Server 19c
Microsoft Windows Server 2016+ (64-bit)	Oracle Database Server 19c

Note:

Oracle Corporation distributes Oracle Linux with the following two kernels:

>> Red Hat Compatible Kernel – This kernel is identical to the kernel shipped in Red Hat Enterprise Linux.

>> Unbreakable Enterprise Kernel – This kernel is based on a later Linux 2.6-series kernel, with Oracle's own enhancements for OLTP, InfiniBand, SSD disk access, NUMA-optimizations, Reliable Datagram Sockets (RDS), async I/O, OCFS2, and networking.

Oracle claims that the Unbreakable Enterprise Kernel is compatible with Red Hat Enterprise Linux; and Oracle middleware and third-party Red Hat Enterprise Linux-certified applications can be installed and run unchanged on Unbreakable Enterprise Kernel. However, for users requiring strict compatibility with Red Hat or for users running kernel modules dependent on specific kernel versions, the Red Hat Compatible Kernel offers 100% compatibility with Red Hat Enterprise Linux.

The following Oracle Database Server Editions are supported:

- Oracle Database Enterprise Edition

¹ Version numbers suffixed with "+" are the MINIMUM version supported. That version and all future 4th digit updates will be supported.

² Here, **x** represents the vendor supported version.

³ Oracle Revenue Management and Billing is tested and certified on Oracle Linux 7.x and 8.x. Oracle Linux is 100% userspace-compatible with Red Hat Enterprise Linux, and therefore Oracle Revenue Management and Billing is supported on Red Hat Enterprise Linux.

Oracle Database Client 19c is required as a pre-requisite for installing the Oracle Revenue Management and Billing application.

Note:

Oracle Database Enterprise Edition with the **Advanced Compression and Partitioning** options is strongly recommended in all situations.

We strongly recommend you install Oracle Revenue Management and Billing (ORMB) on Microsoft Windows platform only for non-production activities, such as User Acceptance Testing (UAT), development setup, and so on.

1.1.2 Support for Software Patches and Upgrades

Due to the ongoing nature of software improvement, vendors will issue patches and service packs for the operating systems, application servers and database servers on top of specific versions that Oracle Revenue Management and Billing has been tested with.

If it is necessary to apply an upgrade, please do so in a test environment that is running on the same platform as your production environment prior to updating the Oracle Revenue Management and Billing production environment.

The exception from this rule is Hibernate Version 4.1 GA and Oracle Database Client 19c. These should not be upgraded.

Always contact Oracle Revenue Management and Billing Support prior to applying vendor updates that do not guarantee backward compatibility.

1.2 Database Maintenance Rules

The database supplied with the product consists of the following elements:

- A set of users to administrate, execute and read the database schema provided.
- A set of database roles to implement security for each of the users provided.
- A tablespace and a schema containing the base database objects used by the product.

The installation instructions are outlined in the installation section of this document.

1.2.1 Permitted Database Changes

During and after installation of the product the following changes may be performed by the database administrator personnel on site:

- Users supplied by product may be changed according to the site standards.
- Database objects may be added to the schema according to database naming standards outlined later in this document.
- Database views and indexes may be created against base database objects. Please make sure to prefix new items with "CM" (for customer modification).
- Database storage attributes for base indexes and base tables may be changed according to site standards and hardware used.
- Tablespace names, attributes and locations may be changed according to site standards.

- Database topology (base table/index to tablespace, tablespace to data file, data file to location) may be altered according to tuning and/or site standards.
- Database triggers may be created against base database objects unless they attempt to contravene base data integrity rules.
- Database initialization and parameter settings may be altered according to site standards unless otherwise advised by Oracle Support or outlined in this document.

1.2.2 Non-Permitted Database Changes

In order to maintain operability and upgradeability of the product, during and after the installation of the product, the following changes may not be performed by the database administration personnel on site:

- Base objects must not be removed or altered in the following ways:
 - Columns in base tables must not be altered in anyway.
 - Columns in Indexes must not be altered or removed.
 - Tables must not be renamed or removed.
 - Base views must not be renamed or removed.
 - Base Triggers and Sequences must not be renamed or removed.
 - Base indexes must not be altered or removed.

2. Installing Oracle Revenue Management and Billing Version 3.1.0.0.0 Database

This section provides the instructions for installing the Oracle Revenue Management and Billing database. This section includes the following topics:

- [Installation Overview](#)
- [Creating the Database](#)
- [Oracle Database Installation](#)

2.1 Installation Overview

Note: Refer to the [Supported Database Platforms](#) section for information about the supported platforms on which Oracle Revenue Management and Billing is verified to operate.

The following types of installation are available for Oracle Revenue Management and Billing:

- Initial Install — a database without demo data
- Demo Install — a database with demo data

The database installation requires Java Development Kit Version 8.0 and Oracle Database Client 19c on the Windows desktop where the install package is staged and run.

2.2 Creating the Database

For an initial or demo install, you will create an empty database on the UNIX or Windows database server on which you operate the production instance of Oracle Revenue Management and Billing.

To create the database:

1. Create the database using the Database Configuration Assistant (DBCA). Refer to the *Master Note: Overview of Database Configuration Assistant (DBCA) (Document ID: 1488770.1)* article on [My Oracle Support](#) for more information.
2. Ensure that you set the database character set to AL32UTF8 and national character set (NLS_NCHAR_CHARACTERSET) to AL16UTF16.

Note: In the prior versions of the product, the `cdxdba` utility (`cdxdba.plx` for UNIX and `CDXDBA.exe` for Windows) was included in the package. However, it is no longer supported. Instead of using the `cdxdba` utility, use the **Database Configuration Assistant** to create the database.

3. Enable the following mandatory software options:
 - Oracle Spatial OR Oracle Locator
 - Oracle Text
4. Execute the following SQL command to verify whether the above mandatory software options are enabled:
 - `SELECT COMP_NAME, STATUS FROM DBA_REGISTRY WHERE COMP_NAME IN ('Spatial','Oracle Text');`

5. Create the default tablespace named CISTS_01 using the following command:

```
CREATE BIGFILE TABLESPACE CISTS_01 LOGGING DATAFILE  
'<db_file_location>/oradata/<DB_NAME>/cists01.dbf' SIZE 5G REUSE  
AUTOEXTEND ON EXTENT MANAGEMENT LOCAL AUTOALLOCATE;
```

6. Create the CIS_USER and CIS_READ roles using the following commands:

```
CREATE ROLE CIS_USER;  
CREATE ROLE CIS_READ;
```

7. Assign the privileges to the CIS_USER role using the following command:

```
GRANT CREATE SYNONYM TO CIS_USER;
```

8. Assign the privileges to the CIS_READ role using the following command:

```
GRANT CREATE SYNONYM TO CIS_READ;
```

9. Create the CISADM, CISUSER, CISOPR, and CISREAD users using the following commands:

```
CREATE USER CISADM IDENTIFIED BY CISADM DEFAULT TABLESPACE  
CISTS_01 TEMPORARY TABLESPACE TEMP PROFILE DEFAULT;  
GRANT UNLIMITED TABLESPACE TO CISADM WITH ADMIN OPTION;  
GRANT SELECT ANY TABLE TO CISADM;  
GRANT CREATE DATABASE LINK TO CISADM;  
GRANT CONNECT TO CISADM;  
GRANT RESOURCE TO CISADM;  
GRANT DBA TO CISADM WITH ADMIN OPTION;  
GRANT CREATE ANY SYNONYM TO CISADM;  
GRANT SELECT ANY DICTIONARY TO CISADM;
```

```
CREATE USER CISUSER PROFILE DEFAULT IDENTIFIED BY CISUSER DEFAULT  
TABLESPACE CISTS_01 TEMPORARY TABLESPACE TEMP;  
GRANT SELECT ANY TABLE TO CISUSER;  
GRANT CIS_USER TO CISUSER;  
GRANT CIS_READ TO CISUSER;  
GRANT CONNECT TO CISUSER;
```

```
CREATE USER CISREAD IDENTIFIED BY CISREAD DEFAULT TABLESPACE  
CISTS_01 TEMPORARY TABLESPACE TEMP;  
GRANT SELECT ANY TABLE TO CISREAD;  
GRANT CIS_READ TO CISREAD;  
GRANT CONNECT TO CISREAD;
```

```
CREATE USER CISOPR PROFILE DEFAULT IDENTIFIED BY OPRPLUS DEFAULT  
TABLESPACE CISTS_01 TEMPORARY TABLESPACE TEMP;  
GRANT CONNECT, RESOURCE, EXP_FULL_DATABASE TO CISOPR;
```

10. Review the `Storage.xml` file under the `TEMPDIR\FW\Install-Upgrade` folder prior to an initial install. This file allocates all base tables and indexes to the default tablespace (CISTS_01) and the required users and roles.

Information in this file is used by `ORADBI` (i.e. `spl-oradbi-4.4.0.3.0.jar`) while installing the Oracle Revenue Management and Billing database objects. Refer to the [Updating Storage.xml](#) section for more information on how to update the `Storage.xml` file.

Note: You will need to review the `Storage.xml` file, prior to an initial install, to update the default values to custom values (for example, TableSpace Name). The `spl-oradbi-4.4.0.3.0.jar` can be executed by a non-schema owner in order to upgrade the database. The Initial Install still needs to be done by the schema owner.

If you decide to allocate some tables or indexes outside of the default tablespace, change the tablespace name from the default value to a custom value in the `Storage.xml` file.

For instance, if you decide to allocate the `CI_ACCT` table in the `MyTablespace` tablespace, change `Storage.xml` as shown:

```
<CI_ACCT>
    <TABLESPACE>MyTablespace</TABLESPACE>
</CI_ACCT>
```

For optimum storage allocation, database administrators should create multiple tablespaces with extents sized to store different types of tables/indexes. They can then edit the `storage.xml` file before install process, to spread tables and indexes across these tablespaces. Tables and indexes can be created in parallel by editing degree of parallelism. Tablespace, storage options, secure file options, Advanced Compression, and parallel information are used only for new objects. Therefore, for initial installs, information for each object should be reviewed. Be careful while editing this file. Make sure that tablespace names being used exist in the database. Do not change the basic format of this file.

Note: Prior to the installation of the database schema for the product, please ensure that the Database Management System software is installed according to your site standards and the installation guide provided by the database vendor. Also please make sure that you have necessary licenses to use some of the advanced database features, such as Advanced Compression.

2.3 Oracle Database Installation

This section describes how to install Oracle Database for Oracle Revenue Management and Billing Version 3.1.0.0.0. It contains the following topics:

- [Initial Install, or Installing Version 3.1.0.0.0 for the First Time](#)
- [Demo Install](#)
- [Populating Language Data](#)

Note: The installation tools outlined in this guide run on Windows, UNIX, and Linux only. Please refer to the [Supported Database Platforms](#) section for more information on supported platforms.

2.3.1 Initial Install, or Installing Version 3.1.0.0.0 for the First Time

This section describes how to install the database components of Oracle Revenue Management and Billing. It includes the following topics:

- [Copying and Decompressing Install Media](#)
- [Creating the Database](#)
- [Setting the MAX_STRING_SIZE Parameter to EXTENDED](#)
- [Installing Oracle Utilities Application Framework](#)
- [Installing Oracle Revenue Management and Billing](#)
- [Post Installation Tasks](#)

Note: You must have a supported version of the Java Development Kit installed on the Windows and Linux desktop where you stage and run the database installation package. Refer to the *Oracle Revenue Management and Billing Installation Guide* for more information.

Before you begin with the installation, ensure that you have Oracle Database Client installed on the Microsoft Windows desktop.

2.3.1.1 Copying and Decompressing Install Media

To download and decompress the ORMB Database package:

1. Download the **Oracle Revenue Management and Billing V3.1.0.0.0 Oracle Database** package from the **Oracle Revenue Management and Billing V3.1.0.0.0** media pack which is available on [Oracle Software Delivery Cloud](#). A zip file is downloaded.
2. Create a temporary folder named `TEMPDIR` on your local machine.
3. Unzip the downloaded file in the `TEMPDIR` folder. The contents include the following sub-folders:
 - `FW`
 - `RMB`

2.3.1.2 Creating the Database

Note: You must have Oracle Database Server 19c installed on your machine to create the database.

The Linux and Windows database creation utilities create an empty database with AL32UTF8 character set and at least one tablespace for storing the application objects before running the installation. The default name of the application tablespace is `CISTS_01`.

Creating the Database on UNIX

Create the database using the Database Configuration Assistant (DBCA). Refer to the *Master Note: Overview of Database Configuration Assistant (DBCA) (Document ID: 1488770.1)* article on [My Oracle Support](#) for more information. Ensure that you set the database character set to `AL32UTF8` and national character set (`NLS_NCHAR_CHARACTERSET`) to `AL16UTF16`.

For more information on how to create the database, refer to the [Creating the Database](#) section.

Creating the Database on Windows

You should be logged in as a user who is a member of the local ORA_DBA group on that server. The [ORA_DBA](#) group should have “administrator” privileges assigned to it.

Create the database using the Database Configuration Assistant (DBCA). Refer to the *Master Note: Overview of Database Configuration Assistant (DBCA) (Document ID: 1488770.1)* article on [My Oracle Support](#) for more information. Ensure that you set the database character set to [AL32UTF8](#) and national character set (NLS_NCHAR_CHARACTERSET) to [AL16UTF16](#).

For more information on how to create the database, refer to the [Creating the Database](#) section.

2.3.1.3 Setting the MAX_STRING_SIZE Parameter to EXTENDED

If you have created a non-container database, you need to perform the following steps to set the MAX_STRING_SIZE parameter to EXTENDED:

1. Set the [ORACLE_HOME](#) and [ORACLE_SID](#) environment variables.
2. Shutdown the target database using the following command:
`shutdown immediate`
3. Start the database in the Upgrade mode using the following command:
`startup upgrade`
4. Set the MAX_STRING_SIZE parameter to EXTENDED using the following command:
`alter system set max_string_size=extended scope=both;`
5. Execute the [utl32k.sql](#) file using the following command:
`@?/rdbms/admin/utl32k.sql;`
6. Restart the database in the Normal mode using the following commands:
`shutdown immediate`
`startup`

However, if you have created a container database, you need to perform the following steps to set the MAX_STRING_SIZE parameter to EXTENDED:

1. Set the [ORACLE_HOME](#) and [ORACLE_SID](#) environment variables.

Note: You need to connect as system administrator while executing the below steps.

2. Set the MAX_STRING_SIZE parameter to EXTENDED using the following command:
`alter system set max_string_size=extended scope=spfile;`
3. Start all pluggable databases in the Upgrade mode using the following command:
`shutdown immediate`
`startup upgrade`
`alter pluggable database all open upgrade;`
`exit`
4. Create the [utl32k_cdb_pdbs_output](#) folder to store the log files using the following command:
`mkdir /scratch/mydir/utl32k_cdb_pdbs_output`

5. Execute the `utl32k.sql` from the `catcon.pl` file for all pluggable databases using the following command:

```
cd $ORACLE_HOME/rdbms/admin
$ORACLE_HOME/perl/bin/perl $ORACLE_HOME/rdbms/admin/catcon.pl -u
SYS -d $ORACLE_HOME/rdbms/admin -
l '/scratch/mydir/utl32k_cdb_pdbs_output' -b
utl32k_cdb_pdbs_output utl32k.sql
```

6. Restart the database in the Normal mode using the following commands:

```
shutdown immediate
startup
alter pluggable database all open read write;
```

2.3.1.4 Installing Oracle Utilities Application Framework

You need to install Oracle Utilities Application Framework Version 4.4.0.3.0 prior to Oracle Revenue Management and Billing Version 3.1.0.0.0. The files for Oracle Utilities Application Framework installation are in the `TEMPDIR\FW` folder. The installation process prompts you to provide the following information:

- The target database name in which the product is to be installed.
- A database user that will own the application schema (for example, `CISADM`).
- A database user that has read-write (select, update, insert, and delete) privileges to the objects in the application schema (for example, `CISUSER`). The application will access the database as this user.
- A database user with read-only privileges to the objects in the application schema. (For example, `CISREAD`).
- A database role that has read-write (select, update, insert, and delete) privileges to the objects in the application schema. The application will access the database as this user. (For example, `CIS_USER`).
- A database role with read-only privileges to the objects in the application schema (for example, `CIS_READ`).
- Location of the jar files. (The Jar files are bundled with the database package.)
- Java Home (for example, `C:\Java\jdk1.8.0_271`)

To install Oracle Utilities Application Framework (OUAF), you need to install the following in the specified order:

1. [Oracle Utilities Application Framework Version 4.4.0.3.0](#)
2. [Rollup Pack for Oracle Utilities Application Framework Version 4.4.0.3.0](#)

Installing Oracle Utilities Application Framework Version 4.4.0.3.0

To install the schema for Oracle Utilities Application Framework Version 4.4.0.3.0, you should have the following:

- Java Development Kit 8.0
- Oracle Database
- Schema such as CISADM should exist in the database

- MAX_STRING_SIZE parameter set to EXTENDED

To install Oracle Utilities Application Framework (OUAF) Version 4.4.0.3.0:

1. Set the `JAVA_HOME` environment variable using the following command:

Windows:

```
SET JAVA_HOME=<JAVA_HOME_PATH>
```

AIX, Linux:

```
export JAVA_HOME=<JAVA_HOME_PATH>
```

Note: The `<JAVA_HOME_PATH>` is the location where Java Development Kit Version 8.0 is installed.

2. Set the `JAR_PATH` environment variable using the following command:

AIX, Linux:

```
export JAR_PATH=TEMPDIR/fw/jarfiles
```

Note:

The above command is applicable only for AIX and Linux platforms.

The `TEMPDIR` folder is the location where you have extracted the contents of the **Oracle Revenue Management and Billing V3.1.0.0.0 Oracle Database** package.

3. Set the `CLASS_PATH` environment variable using the following command:

Windows:

```
SET CLASS_PATH=TEMPDIR\fw\jarfiles\*
```

AIX, Linux:

```
export CLASS_PATH=$JAR_PATH/commons-cli-1.4-
c12260c.jar:$JAR_PATH/commons-codec-1.15.jar:$JAR_PATH/commons-
collections-3.2.2.jar:$JAR_PATH/jackson-annotations-
2.10.3.jar:$JAR_PATH/jackson-core-2.10.3.jar:$JAR_PATH/jackson-
databind-2.10.3.jar:$JAR_PATH/log4j-api-
2.13.3.jar:$JAR_PATH/log4j-core-2.13.3.jar:$JAR_PATH/ojdbc8-
19.3.0.0.0.jar:$JAR_PATH/spl-oradbi-4.4.0.3.0.jar:$JAR_PATH/spl-
shared-4.4.0.3.0.jar
```

4. Change to the `Install-Upgrade` folder using the following command:

Windows:

```
cd TEMPDIR\fw\Install-Upgrade
```

AIX, Linux:

```
cd TEMPDIR/fw/Install-Upgrade
```

5. Execute the [OraDBI](#) (Java) utility using the following command:

Windows:

```
%JAVA_HOME%\bin\java -Xmx1500M -cp %CLASS_PATH%
com.oracle.ouaf.oem.install.OraDBI -d jdbc:oracle:thin:
@<DB_SERVER_NAME>:<DB_PORT>:<DB_NAME>, <SCHEMA_NAME>,
<SCHEMA_PASSWORD>, <READWRITE_USER>, <READONLY_USER>,
<READWRITE_ROLE>, <READONLY_ROLE>, <SCHEMA NAME> -p
<READWRITE_USER_PASSWORD>, <READONLY_USER_PASSWORD> -l 1,2 -q
true
```

AIX, Linux:

```
$JAVA_HOME/bin/java -Xmx1500M -cp $CLASS_PATH
com.oracle.ouaf.oem.install.OraDBI -d jdbc:oracle:thin:
@<DB_SERVER_NAME>:<DB_PORT>:<DB_NAME>, <SCHEMA_NAME>,
<SCHEMA_PASSWORD>, <READWRITE_USER>, <READONLY_USER>,
<READWRITE_ROLE>, <READONLY_ROLE>, <SCHEMA NAME> -p
<READWRITE_USER_PASSWORD>, <READONLY_USER_PASSWORD> -l 1,2 -q
true
```

A message appears indicating that the process is completed successfully. This process generates log files in the [TEMPDIR/fw/Install-Upgrade/Logs](#) directory.

6. Ensure that you check the log files for any errors.

Note: While executing the [OraDBI](#) utility, you may receive the following message in the display output or logs. This error can be safely ignored and the process should proceed to completion.

```
- 2016-05-23 16:31:38,315 [main] ERROR
(common.cryptography.KeyStoreWrapperFactory) The keystore file
'<filename>' does not exist...
...
```

This file is either provided by the `com.oracle.ouaf.system.keystore.file` property or expected to exist at the default file location null attempting to use the legacy cryptography.

```
- 2016-05-23 16:31:38,566 [main] INFO (oem.install.OraDBI)
```

On installing Oracle Utilities Application Framework Version 4.4.0.3.0, various objects are created in the database under CISADM schema. The following table lists the number of objects that are created when you install framework:

Object Type	Count
INDEX	1017
SEQUENCE	4
TABLE	674
TRIGGER	1
VIEW	16

Note: You should use the above object count for verification only when you are doing fresh installation on the database server and not when you are upgrading the database.

Ideally, the Oracle Utilities Application Framework Version 4.4.0.3.0 installation should approximately finish in 5 minutes. The execution time can vary to great extent depending on network speed between local machine and server location.

After setting up roles and users, the utility continues upgrading schema and system data definitions. If an error occurs while executing an SQL or another utility, it logs and displays the error message and allows you to re-execute the current step.

Note:

OraDBI performs the following tasks:

- >> Interacts with the user to collect information about the name of Oracle account that will own the application schema (for example, [CISADM](#)), password of this account, and the name of the Oracle account that the application user will use (for example, [CISUSER](#)), and the name of the Oracle account that will be assigned read-only privileges to the application schema (for example, [CISREAD](#)).
- >> Verifies whether tablespace names already exist in the [Storage.xml](#) file (if not, the process will abort).
- >> Installs the schema, installs the system data, and configures security.
- >> Maintains upgrade log tables in the database.
- >> Updates release ID when the upgrade is completed successfully.
- >> If an error occurs while executing a SQL script or another utility, it logs and displays the error message and allows you to re-execute the current step. Log files [OraDBI###.log](#) are created in the same folder as OraDBI and contains all the SQL commands executed against the database along with the results. The log files are incremental so that the results are never overwritten. If warning messages are generated during the upgrade, OraDBI prompts the user at the end of the process. Users should check the log files to verify the warning messages.
- >> Warning messages are only alerts and do not necessarily mean a problem exists.
- >> Stores the Schema owner and password in the feature configuration table. The password is stored in encrypted format.
- >> OraDBI can be executed by a non-schema owner.

Installing Rollup Pack for Oracle Utilities Application Framework Version 4.4.0.3.0

You can install the rollup pack for Oracle Utilities Application Framework Version 4.4.0.3.0 from a Windows machine or Linux Standalone server. To install the rollup pack for Oracle Utilities Application Framework Version 4.4.0.3.0:

1. Download the Oracle Utilities Application Framework V4.4.0.3.0 Single Fix Prerequisite Rollup for RMB V3.1.0.0.0 package from the Oracle Revenue Management and Billing V3.1.0.0.0 media pack which is available on [Oracle Software Delivery Cloud](#). A zip file is downloaded.
2. Unzip the downloaded file in the [TEMPDIR](#) folder. The contents include the [ORMB-V31000-FW-PREREQ-MultiPlatform.jar](#) file.

3. Decompress the JAR file using the following command:

```
cd TEMPDIR  
jar -xvf ORMB-V31000-FW-PREREQ-MultiPlatform.jar
```

A sub-folder named `FW-V4.4.0.3.0-Rollup` is extracted. It contains the following two sub-folders:

- Application
- Database

4. Create a folder named `dbpatch_tools` in the `TEMPDIR` folder.

5. Copy the `db_patch_standalone.jar` file to the `dbpatch_tools` folder.

6. Decompress the JAR file using the following command:

Windows:

```
cd TEMPDIR\dbpatch_tools  
jar -xvf db_patch_standalone.jar
```

AIX, Linux:

```
cd TEMPDIR/dbpatch_tools  
jar -xvf db_patch_standalone.jar
```

The contents are extracted in the `dbpatch_tools` folder. The contents include the following three sub-folders:

- bin
- config
- lib

7. Set the `TOOLSBIN` environment variable using the following command:

Windows:

```
SET TOOLSBIN=TEMPDIR\dbpatch_tools\bin
```

AIX, Linux:

```
export TOOLSBIN=/TEMPDIR/dbpatch_tools/bin
```

8. Change to the `Database` folder using the following command:

Windows:

```
cd TEMPDIR\FW-V4.4.0.3.0-Rollup\Database
```

AIX, Linux:

```
cd TEMPDIR/FW-V4.4.0.3.0-Rollup/Database
```

9. Execute the `ouafDatabasePatch` utility using the following command:

Windows:

```
ouafDatabasePatch.cmd
```

AIX, Linux:

```
ouafDatabasePatch.sh
```

Note:

On the AIX and Linux platforms, ensure that you grant the execute permission for the `ouafDatabasePatch.sh` utility using the following command:

```
chmod 755 ouafDatabasePatch.sh
```

In the previous versions of Oracle Revenue Management and Billing, you used to execute the `cdxpatch` utility while installing the rollup pack for Oracle Utilities Application Framework. Henceforth, the `cdxpatch` utility is no longer supported and you need to use the `ouafDatabasePatch` utility.

This utility prompts you to enter values for the following parameters:

Parameter	Value
Enter the target database type (O/M/D) [O]	O (if you have Oracle database) OR M (if you have MySQL database)
Enter the username that owns the schema	<DB_USER> Example: CISADM
Enter the password for the <DB_USER> user	<DB_USER_PASSWORD>
Enter the name of the Oracle Database Connection String	<DB_SERVER:DB_PORT:DB_SID>

Note: If you have changed the database user password, you will not be able to install the rollup pack for Oracle Utilities Application Framework Version 4.4.0.3.0. You will have to first change the database user password. For more information on how to change the database user password, refer to [Appendix C: Changing the DB User Password](#).

10. Enter the required parameter value. The following message appears in the command line:
`Ready to process patches, Do you want to continue? (Y/N)`
11. Type **Y** and then press **Enter**. A message appears indicating that the patches are applied successfully.

On installing the rollup pack for Oracle Utilities Application Framework Version 4.4.0.3.0, various objects are created in the database under CISADM schema. The following table lists the number of objects that are created when you install the framework rollup pack:

Object Type	Count
INDEX	1017
SEQUENCE	4
TABLE	674
TRIGGER	1
VIEW	16

Note: You should use the above object count for verification only when you are doing fresh installation on the database server and not when you are upgrading the database.

Ideally, the framework rollup pack installation should approximately finish in 5 minutes. The execution time can vary to great extent depending on network speed between local machine and server location.

2.3.1.5 Installing Oracle Revenue Management and Billing

To install Oracle Revenue Management and Billing (ORMB) Version 3.1.0.0.0:

1. Set the `JAVA_HOME` environment variable using the following command:

Windows:

```
SET JAVA_HOME=<JAVA_HOME_PATH>
```

AIX, Linux:

```
export JAVA_HOME=<JAVA_HOME_PATH>
```

Note: The `<JAVA_HOME_PATH>` is the location where Java Development Kit Version 8.0 is installed.

2. Set the `JAR_PATH` environment variable using the following command:

AIX, Linux:

```
export JAR_PATH=TEMPDIR/RMB/jarfiles
```

Note:

The above command is applicable only for AIX and Linux platforms.

The `TEMPDIR` folder is the location where you have extracted the contents of the **Oracle Revenue Management and Billing V3.1.0.0.0 Oracle Database** package.

3. Set the `CLASS_PATH` environment variable using the following command:

Windows:

```
SET CLASS_PATH=TEMPDIR\RMB\jarfiles\*
```

AIX, Linux:

```
export CLASS_PATH=$JAR_PATH/commons-cli-1.4-
c12260c.jar:$JAR_PATH/commons-codec-1.15.jar:$JAR_PATH/commons-
collections-3.2.2.jar:$JAR_PATH/jackson-annotations-
2.10.3.jar:$JAR_PATH/jackson-core-2.10.3.jar:$JAR_PATH/jackson-
databind-2.10.3.jar:$JAR_PATH/log4j-api-
2.13.3.jar:$JAR_PATH/log4j-core-2.13.3.jar:$JAR_PATH/ojdbc8-
19.3.0.0.0.jar:$JAR_PATH/spl-oradbi-4.4.0.3.0.jar:$JAR_PATH/spl-
shared-4.4.0.3.0.jar
```

4. Change to the `Install-Upgrade` folder using the following command:

Windows:

```
cd TEMPDIR\RMB\Upgrade\Oracle\Install-Upgrade
```

AIX, Linux:

```
cd TEMPDIR/RMB/Upgrade/Oracle/Install-Upgrade
```

5. Execute the [OraDBI \(Java\)](#) utility using the following command:

Windows:

```
%JAVA_HOME%\bin\java -Xmx1500M -cp %CLASS_PATH%
com.oracle.ouaf.oem.install.OraDBI -d jdbc:oracle:thin:
@<DB_SERVER_NAME>:<DB_PORT>:<DB_NAME>, <SCHEMA_NAME>,
<SCHEMA_PASSWORD>, <READWRITE_USER>, <READONLY_USER>,
<READWRITE_ROLE>, <READONLY_ROLE>, <SCHEMA NAME> -p
<READWRITE_USER_PASSWORD>, <READONLY_USER_PASSWORD> -l 1,2 -q
true
```

AIX, Linux:

```
$JAVA_HOME/bin/java -Xmx1500M -cp $CLASS_PATH
com.oracle.ouaf.oem.install.OraDBI -d jdbc:oracle:thin:
@<DB_SERVER_NAME>:<DB_PORT>:<DB_NAME>, <SCHEMA_NAME>,
<SCHEMA_PASSWORD>, <READWRITE_USER>, <READONLY_USER>,
<READWRITE_ROLE>, <READONLY_ROLE>, <SCHEMA NAME> -p
<READWRITE_USER_PASSWORD>, <READONLY_USER_PASSWORD> -l 1,2 -q
true
```

A message appears indicating that the process is completed successfully. This process generates log files in the [TEMPDIR/fw/Install-Upgrade/Logs](#) directory.

6. Ensure that you check the log files for any errors.

Note: While executing the [OraDBI](#) utility, you may receive the following message in the display output or logs. This error can be safely ignored and the process should proceed to completion.

```
- 2016-05-23 16:31:38,315 [main] ERROR
(common.cryptography.KeyStoreWrapperFactory) The keystore file
'<filename>' does not exist...
...
```

This file is either provided by the `com.oracle.ouaf.system.keystore.file` property or expected to exist at the default file location null attempting to use the legacy cryptography.

```
- 2016-05-23 16:31:38,566 [main] INFO (oem.install.OraDBI)
```

On installing Oracle Revenue Management and Billing Version 3.1.0.0.0, various objects are created in the database under CISADM schema. The following table lists the number of objects that are created when you install ORMB:

Object Type	Count
FUNCTION	57
INDEX	4132
PACKAGE	5
PACKAGE BODY	5
PROCEDURE	2
SEQUENCE	43
TABLE	2561

Object Type	Count
TRIGGER	1
TYPE	12
TYPE BODY	1
VIEW	186

Note: You should use the above object count for verification only when you are doing fresh installation on the database server and not when you are upgrading the database.

Ideally, the Oracle Revenue Management and Billing Version 3.1.0.0.0 installation should approximately finish in 15 minutes. The execution time can vary to great extent depending on network speed between local machine and server location.

2.3.1.6 Post Installation Tasks

Once you install the Oracle Revenue Management and Billing Version 3.1.0.0.0 database, you need to do the following:

1. [Apply the ORMB Patches](#) or [Apply the ORMB Rollup Packs](#)
2. [Enable USER_LOCK Package](#)
3. [Grant Permissions to the DBMS_LOCK Package and Recompile Database Objects](#)
4. [Generate Database Statistics](#)

Note:

To view the list of patches that you need to apply on the database, refer to the *ORMB V3.1.0.0.0 Patch Guide* (Document ID: 2815177.1) on [My Oracle Support](#).

Alternatively, instead of individually applying the patches, you can download and install the rollup packs, if available, to apply a set of patches at once. For more information about the rollup packs, refer to [Appendix F: ORMB V3.1.0.0.0 Rollup Packs](#).

Apply the ORMB Patches

Once you install Oracle Revenue Management and Billing Version 3.1.0.0.0, you need to apply all patches listed in the *ORMB V3.1.0.0.0 Patch Guide* (Document ID: 2815177.1). You can apply a patch from a Windows machine and UNIX Standalone server.

To apply a patch:

1. Download the patch from [My Oracle Support](#). A zip file is downloaded.
2. Unzip the downloaded file in your local folder. The contents include three files - `README.txt`, `MultiPlatform.zip`, and `Bug_<PATCH_NUMBER>_Product_Fix_Design.pdf`.
3. Unzip the `MultiPlatform.zip` file in your local folder. The contents include the `V3.1.0.0.0-<PATCH_NUMBER>_MultiPlatform` folder.
4. Change to the `V3.1.0.0.0-<PATCH_NUMBER>_MultiPlatform` folder using the following command:

AIX, Linux:

```
cd <DESTINATION_FOLDER_1>/V3.1.0.0.0-<PATCH_NUMBER>_MultiPlatform
```

Windows:

```
cd <DESTINATION_FOLDER_1>\v3.1.0.0.0-<PATCH_NUMBER>_MultiPlatform
```

Note: The <DESTINATION_FOLDER_1> folder is the location where you have extracted the contents of the MultiPlatform.zip file.

The contents include a file named CCB.V3.1.0.0.0-<PATCH_NUMBER>.jar and a folder named database.

5. Change to the ORACLE folder using the following command:

AIX, Linux:

```
cd database/ORACLE
```

Windows:

```
cd database\ORACLE
```

The contents include a zip file named CDXPatch.

6. Unzip the CDXPatch file using the following command:

AIX, Linux:

```
unzip CDXPatch.zip -d <PATH>/<DESTINATION_FOLDER_2>
```

Windows:

```
unzip CDXPatch.zip -d <PATH>\<DESTINATION_FOLDER_2>
```

The contents of the zip file are extracted in the <DESTINATION_FOLDER_2> folder. The contents include utility files and a folder named <PATCH_NUMBER>.

7. Execute the ouafDatabasePatch utility using the following command:

Windows:

```
ouafDatabasePatch.cmd
```

AIX, Linux:

```
ouafDatabasePatch.sh
```

Note: On the AIX and Linux platforms, ensure that you grant the execute permission for the ouafDatabasePatch.sh utility using the following command:

```
chmod 755 ouafDatabasePatch.sh
```

Enable USER_LOCK Package

To enable inbound web services, you must grant permissions to the USER_LOCK package. This is a one-time activity. To grant permissions to the USER_LOCK package:

1. Login as SYS user.
2. On SQL prompt, execute the following SQL:
`@?/rdbms/admin/userlock.sql`
3. Grant permission using the following SQL command:
`grant execute on USER_LOCK to public;`

Note: You can also grant permission to a specific database user (for example, CISADM or CISUSER) instead of granting permissions to all database users.

Grant Permissions to the DBMS_LOCK Package and Recompile Database Objects

To grant permissions to the DBMS_LOCK package, execute the following commands:

AIX, Linux:

```
export ORACLE_SID=[DB_NAME]
sqlplus /nolog
conn sys as sysdba
```

Note: On executing the above command, you will be prompted to enter the `SYS` user password.

```
grant EXECUTE, DEBUG on DBMS_LOCK to <DB_USER/[CISADM]>;
```

Note:

These commands should be executed using Oracle SQL Developer.

If you have created the database using any user other than CISADM, you need to specify the respective user name in the above grant statement.

After executing the above `grant` statement, recompile the invalid objects, if any, in the database. You can recompile all invalid objects at once using the following commands:

```
export ORACLE_SID=[DB_NAME]
sqlplus /nolog
conn sys as sysdba
SQL> @?/rdbms/admin/utlrp.sql;
```

Windows:

```
set ORACLE_SID=[DB_NAME]
sqlplus /nolog
conn sys as sysdba
```

Note: On executing the above command, you will be prompted to enter the `SYS` user password.

```
grant EXECUTE, DEBUG on DBMS_LOCK to <DB_USER/[CISADM]>;
```

Note:

These commands should be executed using Oracle SQL Developer.

If you have created the database using any user other than CISADM, you need to specify the respective user name in the above alter and grant statements.

After executing the above `grant` statement, recompile the invalid objects, if any, in the database. You can recompile all invalid objects at once using the following commands:

```
export ORACLE_SID=[DB_NAME]
sqlplus /nolog
conn sys as sysdba
SQL> @?/rdbms/admin/utlrp.sql;
```

Generate Database Statistics

During the installation process, new database objects may be added to the target database. Before you use the target database, we recommend you gather statistics for the database objects. You can gather schema level statistics using the following statement:

```
BEGIN
DBMS_STATS.GATHER_SCHEMA_STATS(OWNNAME=>'CISADM', METHOD_OPT=>'FOR ALL
COLUMNS SIZE AUTO', GRANULARITY=>'ALL', CASCADE=>TRUE, DEGREE=>16);
END;
```

You can also gather the statistics for individual tables using the following statement:

```
BEGIN
DBMS_STATS.GATHER_TABLE_STATS(OWNNAME=>'CISADM',
TABNAME=>'<Table_Name>', GRANULARITY=>'ALL', CASCADE=>TRUE,
METHOD_OPT=> 'FOR ALL COLUMNS SIZE AUTO', DEGREE=>32);
END;
```

We strongly recommend you schedule batch jobs to gather the schema level statistics on the daily basis in the non-peak hours. Please note that the statistics should not be gathered while the application batches are running because this will degrade the application batch performance.

2.3.2 Demo Install

This section describes how to install the demo database components of Oracle Revenue Management and Billing. It includes the following topics:

- [Copying and Decompressing Demo Dump Patch](#)
- [Creating the Database](#)
- [Setting the MAX_STRING_SIZE Parameter to EXTENDED](#)
- [Importing the Demo Dump File](#)
- [Post Demo Database Creation Tasks](#)

2.3.2.1 Copying and Decompressing Demo Dump Patch

To download and decompress the Demo Dump patch:

1. Download the domain-specific demo dump patch from [My Oracle Support](#):

If you belong to...	Then download...
Financial Services domain	BANKING DEMO DATA DUMP FOR RMB 3.1.0.0.0 patch (Patch Number: 33526829)
Health Insurance domain	HC DEMO DATA DUMP FOR RMB 3.1.0.0.0 patch (Patch Number: 33529981)

A zip file is downloaded.

2. Create a temporary directory named `TEMPDIR` on your local machine.

3. Unzip the downloaded file in the `TEMPDIR` directory. The contents include the `Demo_Dump` folder and `README` file. The health insurance specific demo dump folder contains the `DemodataDump_OIRMB3.1.dmp` file and the financial services specific demo dump folder contains the `GTB31000_demodump.dmp` file.

2.3.2.2 Creating the Database

Note: You must have Oracle Database Server 19c installed on your machine in order to create the database.

Creating the Database on UNIX

Create the database using the Database Configuration Assistant (DBCA). Refer to the *Master Note: Overview of Database Configuration Assistant (DBCA) (Document ID: 1488770.1)* article on [My Oracle Support](#) for more information. Ensure that you set the database character set to `AL32UTF8` and national character set (`NLS_NCHAR_CHARACTERSET`) to `AL16UTF16`.

For more information on how to create the database, refer to the [Creating the Database](#) section.

Creating the Database on Windows

You should be logged in as a user who is a member of the local `ORA_DBA` group on that server. The `ORA_DBA` group should have “administrator” privileges assigned to it.

Create the database using the Database Configuration Assistant (DBCA). Refer to the *Master Note: Overview of Database Configuration Assistant (DBCA) (Document ID: 1488770.1)* article on [My Oracle Support](#) for more information. Ensure that you set the database character set to `AL32UTF8` and national character set (`NLS_NCHAR_CHARACTERSET`) to `AL16UTF16`.

For more information on how to create the database, refer to the [Creating the Database](#) section.

2.3.2.3 Setting the MAX_STRING_SIZE Parameter to EXTENDED

If you have created a non-container database, you need to perform the following steps to set the `MAX_STRING_SIZE` parameter to EXTENDED:

1. Set the `ORACLE_HOME` and `ORACLE_SID` environment variables.
2. Shutdown the target database using the following command:
`shutdown immediate`
3. Start the database in the Upgrade mode using the following command:
`startup upgrade`
4. Set the `MAX_STRING_SIZE` parameter to EXTENDED using the following command:
`alter system set max_string_size=extended scope=both;`
5. Execute the `utl32k.sql` file using the following command:
`@?/rdbms/admin/utl32k.sql;`
6. Restart the database in the Normal mode using the following commands:
`shutdown immediate`
`startup`

However, if you have created a container database, you need to perform the following steps to set the `MAX_STRING_SIZE` parameter to EXTENDED:

1. Set the `ORACLE_HOME` and `ORACLE_SID` environment variables.

Note: You need to connect as system administrator while executing the below steps.

2. Set the `MAX_STRING_SIZE` parameter to EXTENDED using the following command:

```
alter system set max_string_size=extended scope=spfile;
```

3. Start all pluggable databases in the Upgrade mode using the following command:

```
shutdown immediate
startup upgrade
alter pluggable database all open upgrade;
exit
```

4. Create the `utl32k_cdb_pdbs_output` folder to store the log files using the following command:

```
mkdir /scratch/mydir/utl32k_cdb_pdbs_output
```

5. Execute the `utl32k.sql` from the `catcon.pl` file for all pluggable databases using the following command:

```
cd $ORACLE_HOME/rdbms/admin
$ORACLE_HOME/perl/bin/perl $ORACLE_HOME/rdbms/admin/catcon.pl -u
SYS -d $ORACLE_HOME/rdbms/admin -
l '/scratch/mydir/utl32k_cdb_pdbs_output' -b
utl32k_cdb_pdbs_output utl32k.sql
```

6. Restart the database in the Normal mode using the following commands:

```
shutdown immediate
startup
alter pluggable database all open read write;
```

2.3.2.4 Importing the Demo Dump File

Once you create the database, you can import the demo dump file. To import the demo dump file:

1. Create a database directory named `data_pump_dir` (if not available) and then copy the `DemodataDump_OIRMB3.1.dmp` or `GTB31000_demodump.dmp` file from the `TEMPDIR\Demo_Dump` folder to the `data_pump_dir` folder.

Note: If you belong to the financial services domain, use the `GTB31000_demodump.dmp` file. And, if you belong to the health insurance domain, use the `DemodataDump_OIRMB3.1.dmp` file.

2. Set the `ORACLE_SID` and `ORACLE_HOME` environment variables.

3. If the target schema is `CISADM`, then use the following command to import demo dump:

```
impdp system/<pwd>@<dbname> NOLOGFILE=N DIRECTORY=DATA_PUMP_DIR
DUMPFILE=<dumpfilename>.dmp SCHEMAS=CISADM
```

4. If the target schema is other than `CISADM` (for example, `TRGSCHEM`), then use the following command to import demo dump:

```
impdp system/<pwd>@<dbname> NOLOGFILE=N DIRECTORY=DATA_PUMP_DIR
DUMPFILE=<dumpfilename>.dmp REMAP_SCHEMA=CISADM:TRGSCHEMA
```

2.3.2.5 Post Demo Database Creation Tasks

Once you import the demo dump file, you need to do the following:

1. [Apply the ORMB Patches](#) or [Apply the ORMB Rollup Packs](#)
2. [Enable USER_LOCK Package](#)
3. [Grant Permissions to the DBMS_LOCK Package and Recompile Database Objects](#)
4. [Generate Database Statistics](#)

Note:

To view the list of patches that you need to apply on the database, refer to the *ORMB V31000 Patch Guide* (Document ID: 2815177.1) on [My Oracle Support](#).

Alternatively, instead of individually applying the patches, you can download and install the rollup packs, if available, to apply a set of patches at once. For more information about the rollup packs, refer to [Appendix F: ORMB V3.1.0.0.0 Rollup Packs](#).

Apply the ORMB Patches

Once you install Oracle Revenue Management and Billing Version 3.1.0.0.0, you need to apply all patches listed in the *ORMB V31000 Patch Guide* (Document ID: 2815177.1). You can apply a patch from a Windows machine and UNIX Standalone server.

To apply a patch:

1. Download the patch from [My Oracle Support](#). A zip file is downloaded.
2. Unzip the downloaded file in your local folder. The contents include three files - `README.txt`, `MultiPlatform.zip`, and `Bug_<PATCH_NUMBER>_Product_Fix_Design.pdf`.
3. Unzip the `MultiPlatform.zip` file in your local folder. The contents include the `V3.1.0.0.0-<PATCH_NUMBER>_MultiPlatform` folder.
4. Change to the `V3.1.0.0.0-<PATCH_NUMBER>_MultiPlatform` folder using the following command:

AIX, Linux:

```
cd <DESTINATION_FOLDER_1>/V3.1.0.0.0-<PATCH_NUMBER>_MultiPlatform
```

Windows:

```
cd <DESTINATION_FOLDER_1>\V3.1.0.0.0-<PATCH_NUMBER>_MultiPlatform
```

Note: The `<DESTINATION_FOLDER_1>` folder is the location where you have extracted the contents of the `MultiPlatform.zip` file.

The contents include a file named `CCB.V3.1.0.0.0-<PATCH_NUMBER>.jar` and a folder named `database`.

5. Change to the `ORACLE` folder using the following command:

AIX, Linux:

```
cd database/ORACLE
```

Windows:

```
cd database\ORACLE
```

The contents include a zip file named `CDXPatch`.

6. Unzip the `CDXPatch` file using the following command:

AIX, Linux:

```
unzip CDXPatch.zip -d <PATH>/<DESTINATION_FOLDER_2>
```

Windows:

```
unzip CDXPatch.zip -d <PATH>\<DESTINATION_FOLDER_2>
```

The contents of the zip file are extracted in the `<DESTINATION_FOLDER_2>` folder. The contents include utility files and a folder named `<PATCH_NUMBER>`.

7. Execute the `ouafDatabasePatch` utility using the following command:

Windows:

```
ouafDatabasePatch.cmd
```

AIX, Linux:

```
ouafDatabasePatch.sh
```

Enable USER_LOCK Package

To enable inbound web services, you must grant permissions to the `USER_LOCK` package. This is a one-time activity. To grant permissions to the `USER_LOCK` package:

1. Login as `SYS` user.
2. On SQL prompt, execute the following SQL:
`@?/rdbms/admin/userlock.sql`
3. Grant permission using the following SQL command:
`grant execute on USER_LOCK to public;`

Note: You can also grant permission to a specific database user (for example, `CISADM` or `CISUSER`) instead of granting permissions to all database users.

Grant Permissions to the DBMS_LOCK Package and Recompile Database Objects

To grant permissions to the `DBMS_LOCK` package, execute the following commands:

UNIX:

```
export ORACLE_SID=[DB_NAME]
```

```
sqlplus /nolog
```

```
conn sys as sysdba
```

Note: On executing the above command, you will be prompted to enter the `SYS` user password.

```
grant EXECUTE, DEBUG on DBMS_LOCK to <DB_USER/[CISADM]>;
```

Note:

These commands should be executed using Oracle SQL Developer.

If you have created the database using any user other than `CISADM`, you need to specify the respective user name in the above alter and grant statements.

After executing the above `grant` statement, recompile the invalid objects, if any, in the database. You can recompile all invalid objects at once using the following commands:

```
export ORACLE_SID=[DB_NAME]
sqlplus /nolog
conn sys as sysdba
SQL> @?/rdbms/admin/utlrp.sql;
```

Windows:

```
set ORACLE_SID=[DB_NAME]
sqlplus /nolog
conn sys as sysdba
```

Note: On executing the above command, you will be prompted to enter the `SYS` user password.

```
grant EXECUTE, DEBUG on DBMS_LOCK to <DB_USER/[CISADM]>;
```

Note:

These commands should be executed using Oracle SQL Developer.

If you have created the database using any user other than CISADM, you need to specify the respective user name in the above alter and grant statements.

After executing the above `grant` statement, recompile the invalid objects, if any, in the database. You can recompile all invalid objects at once using the following commands:

```
export ORACLE_SID=[DB_NAME]
sqlplus /nolog
conn sys as sysdba
SQL> @?/rdbms/admin/utlrp.sql;
```

Generate Database Statistics

During the installation process, new database objects may be added to the target database. Before you use the target database, we recommend you gather statistics for the database objects. You can gather schema level statistics using the following statement:

```
BEGIN
DBMS_STATS.GATHER_SCHEMA_STATS(OWNNAME=>'CISADM', METHOD_OPT=>'FOR ALL
COLUMNS SIZE AUTO', GRANULARITY=>'ALL', CASCADE=>TRUE, DEGREE=>16);
END;
```

You can also gather the statistics for individual tables using the following statement:

```
BEGIN
DBMS_STATS.GATHER_TABLE_STATS(OWNNAME=>'CISADM',
TABNAME=>'<Table_Name>', GRANULARITY=>'ALL', CASCADE=>TRUE,
METHOD_OPT=> 'FOR ALL COLUMNS SIZE AUTO', DEGREE=>32);
END;
```

We strongly recommend you schedule batch jobs to gather the schema level statistics on the daily basis in the non-peak hours. Please note that the statistics should not be gathered while the application batches are running because this will degrade the application batch performance.

2.3.3 Populating Language Data

Please note that this database contains data in the ENGLISH language only. If you use any other supported language, you can run the F1-LANG batch program to duplicate the entries for new language records. For more information on running this batch program, refer to the user documentation section "Defining Background Processes."

Please contact your Oracle representative to receive information on these packages.

3. Database Design

This section provides a standard for database objects such as tables, columns, and indexes, for products using Oracle Utilities Application Framework. This standard helps in smooth integration and upgrade processes by ensuring clean database design, promoting communications, and reducing errors.

Just as Oracle Utilities Application Framework goes through innovation in every release of the software, it is also inevitable that the product will take advantage of various database vendors' new features in each release. The recommendations in the database installation section include only the ones that have been proved by vigorous QA processes, field tests and benchmarks. This section includes:

- [Database Object Standard](#)
- [Column Data Type and Constraints](#)
- [Standard Columns](#)

3.1 Database Object Standard

This section discusses the rules applied to naming database objects and the attributes that are associated with these objects.

3.1.1 Categories of Data

A table can belong to one of the three categories:

- Control (admin)
- Master
- Transaction

For purposes of physical table space design, metadata and control tables can belong to the same category.

Example of tables in each category:

- Control: SC_USER, CI_ADJ_TYPE, F1_BUS_OBJ
- Master: CI_PER, CI_PREM
- Transaction: F1_FACT, CI_FT

All tables have the category information in their index name. The second letter of the index carries this information. Refer to the [Indexes](#) section for more information.

3.1.2 Naming Standards

The following naming standards must be applied to database objects.

Table

Table names are prefixed with the owner flag value of the product. For customer modification, CM must be prefixed in the table name. The length of the table names must be less than or equal to 30 characters. A language table should be named by suffixing _L to the main table. The key table name should be named by suffixing _K to the main table.

It is recommended to start a table name with the 2-3 letter acronym of the subsystem name that the table belongs to. For example, MD stands for metadata subsystem and all metadata table names start with CI_MD.

Some examples are:

- CI_ADJ_TYPE
- CI_ADJ_TYPE_L

A language table stores language sensitive columns such as a description of a code. The primary key of a language table consists of the primary key of the code table plus language code (LANGUAGE_CD).

A key table accompanies a table with a surrogate key column. A key value is stored with the environment id that the key value resides in the key table.

The tables prior to V2.0.0 are prefixed with CI_ or SC_.

Columns

The length of a column name must be less than or equal to 30 characters. For customer modification, CM must be prefixed in the column name. The following conventions apply when you define special types of columns in the database.

- Use the suffix FLG to define a lookup table field. Flag columns must be CHAR (4). Choose lookup field names carefully as these column names are defined in the lookup table (CI_LOOKUP_FIELD) and must be prefixed by the product owner flag value.
- Use the suffix CD to define user-defined codes. User-defined codes are primarily found as the key column of the admin tables.
- Use the suffix ID to define system assigned key columns.
- Use the suffix SW to define Boolean columns. The valid values of the switches are 'Y' or 'N'. The switch columns must be CHAR(1)
- Use the suffix DT to define Date columns.
- Use the suffix DTTM to define Date Time columns.
- Use the suffix TM to define Time columns.

Some examples are:

- ADJ_STATUS_FLG
- CAN_RSN_CD

Indexes

Index names are composed of the following parts:

[OF][application specific prefix][C/M/T]NNN[P/S]n

- OF- Owner Flag. The standard is to use the two characters of the product's owner flag. Note that there may be some older indexes that use only the first character of the owner flag. For client specific implementation of index, use CM for Owner Flag. If implementation creates a CM index on table-columns for which the base product already provides an index, then the CM index will be overridden by the base index.
- Application specific prefix could be C, F, T or another letter.
- C/M/T - The second character can be either C or M or T. C is used for control tables

- (Admin tables). M is for the master tables. T is reserved for the transaction tables.
- NNN - A three-digit number that uniquely identifies the table on which the index is defined.
- P/S - P indicates that this index is the primary key index. S is used for indexes other than primary keys.
- n is the index number, unique across all indexes on a given table (0 for primary and 1, 2, etc., for the secondary indexes).

Some examples are:

- F1C066P0
- F1C066S1
- XT206C2
- CMT206S2

Warning! Do not use index names in the application as the names can change due to unforeseeable reasons.

Updating Storage.xml

The `storage.xml` file that comes with the product allocates all base tables and indexes to the default tablespace CISTS_01. If you decide to allocate some tables or indexes outside of the default tablespace, then this has to be reflected in the `storage.xml` file by changing the tablespace name from the default value to a custom value, according to the format shown below:

Format:

```
<Table_Name>
  <TABLESPACE>CISTS_01</TABLESPACE>
  <PARALLEL>1</PARALLEL>
  <LOB>
    <Column Name>
      <TABLESPACE>CISTS_01</TABLESPACE>
      <SECUREFILE>Y</SECUREFILE>
      <CHUNK>8192</CHUNK>
      <CACHE>N</CACHE>
      <LOGGING>Y</LOGGING>
      <INROW>Y</INROW>
      <COMPRESS>N</COMPRESS>
    </Column Name>
  </LOB>
</Table_Name>
```

Where Parallel defines the number of threads, that Oracle DB Server will use to access a table or create an index.

We recommend you create CLOBs and store them in SECUREFILE with medium compression and cache enabled. Note that, by default, medium compression is turned-off and must be enabled only if you have the Advanced Compression license.

For instance, if a DBA decided to allocate table CI_ACCT in a tablespace MyTablespace, then they would have to change the storage.xml as follows:

```
<CI_ACCT>
  <TABLESPACE>MyTablespace</TABLESPACE>
</CI_ACCT>
```

The OraDBI process uses the `storage.xml` file to place the new database objects into defined tablespaces. A tablespace referenced in the `storage.xml` file must exist in the database.

The `storage.xml` file must be updated before each upgrade and/or new installation as required to allocate the tables and indexes across those tablespaces.

Table name is included as a comment for each of the indexes for clarity.

For an initial install, information for each object should be reviewed by a DBA. For each upgrade, only tablespace information for the objects added in the new release needs to be reviewed by a DBA.

Be careful while editing this file. Make sure that the tablespace names being used exist in the database. Do not change the basic format of this file.

Sequence

We recommend you use the following settings while creating a sequence:

- Set minimum CACHE size to 5000 to enhance performance
- Use NOORDER option so that the database does not generate sequence numbers in order of request

The base sequence name must be prefixed with the owner flag value of the product. For customer modification, CM must be prefixed in the sequence name. The sequence numbers should be named as below:

1. If the sequence is used for a specific table, then use the following sequence name:
[OF] [C/M/T] NNN_SEQ
 - OF stands for Owner Flag. For example, F1 stands for Framework.
 - C/M/T stands for Control (Admin)/Master/Transaction Tables.
 - NNN is a three digit unique Identifier for a table on which the sequence is defined.

For Example: F1T220_SEQ

2. If more than one sequence is used for a specific table then use the following sequence name:
[OF] [C/M/T] NNN_Column_Name_SEQ
 - OF stands for Owner Flag. For example, F1 stands for Framework.
 - C/M/T stands for Control (Admin)/Master/Transaction tables.
 - NNN is a three digit unique identifier for a table on which the sequence is defined.

For Example: F1T220_BO_STATUS_CD_SEQ and F1T220_BUS_OBJ_CD_SEQ

3. If sequence is used for a generic requirement and not specific to a table, then use the following sequence name: [OF] Column_Name_SEQ

- OF stands for Owner Flag. For example, F1 stands for Framework.

For Example: F1FKVALID_SEQ

Trigger

The base trigger name must be prefixed with the owner flag value of the product. When implementers add database objects, such as tables, triggers and sequences, the name of the objects should be prefixed by CM.

3.2 Column Data Type and Constraints

This section discusses the rules applied to column data type and constraints, and the attributes that are associated with these objects.

3.2.1 User Defined Code

User Defined Codes are defined as CHAR type. The length can vary by the business requirements but a minimum of eight characters is recommended. You will find columns defined in less than eight characters but with internationalization in mind, new columns should be defined as CHAR(10) or CHAR(12). Also note that when the code is referenced in the application the descriptions are shown to users in most cases.

3.2.2 System Assigned Identifier

System assigned random numbers are defined as CHAR type. The length of the column varies to meet the business requirements. Number type key columns are used when a sequential key assignment is allowed or number type is required to interface with external software. For example, Notification Upload Staging ID is a Number type because most EDI software uses a sequential key assignment mechanism. For sequential key assignment implementation, the DBMS sequence generator is used in conjunction with Number Type ID columns.

3.2.3 Date/Time/Timestamp

Date, Time and Timestamp columns are defined physically as DATE in Oracle. Non-null constraints are implemented only for the required columns.

3.2.4 Number

Numeric columns are implemented as NUMBER type in Oracle. The precision of the number should always be defined. The scale of the number might be defined. Non-null constraints are implemented for all number columns.

3.2.5 Fixed Length/Variable Length Character Columns

When a character column is a part of the primary key of a table define the column in CHAR type. For the non-key character columns, the length should be the defining factor. If the column length should be greater than 10, use VARCHAR2 type in Oracle.

3.2.6 Null Column Support

The product supports Nullable columns. This means that the application can write NULLs instead of a blank space or zero (for numeric columns) by using NULLABLE_SW on CI_MD_TBL_FLD. If REQUIRED_SW is set to 'N' and the NULLABLE_SW is set to 'Y', the application will write a NULL in that column. The artifact generator will create hibernate mapping files with appropriate parameters so that the framework hibernate mapping types will know if a given property supports a null value.

NULLABLE_SW is not new, but has previously been used for certain fields such as dates, and some string and number foreign-key columns. Because of this, there is the possibility that there is incorrect metadata for some columns, and that turning on this new feature could result in incorrect behavior when using that metadata. The upgrade script fixes the metadata to make sure that the existing tables will not be affected.

This new feature only supports tables maintained by Java and does not support tables maintained by a Java program converted from COBOL. Thus, enhancing any existing tables to use null columns must be done only after ensuring that the tables are maintained by Java, and not by Java converted COBOL programs.

3.2.7 XML Type Support

The product supports XML Type. XML Type provides following advantages:

1. The ability to use XQuery for querying nodes in the XML document stored within a column defined as XMLType.
2. The option to use the XML engine, which is built into the Oracle Database, to create indexes using nodes within the XML document stored in the XMLType column.

3.2.8 Cache and Key Validation Flags

By default, the Cache Flag is set to NONE. For most of the admin tables the CACHE Flag should be 'Cached for Batch'. This specifies that the table is cached as L2 cache to reduce database trips.

By default the Key Validation Flag is set to ALL. For tables which have the user defined keys, the KEY_VALIDATION_FLG should be set as 'ALL'. This checks the existence of the key before inserting a new one.

3.2.9 Table Classification and Table Volume Flags

There are multiple types of tables in the application, namely Admin system tables, Admin non-system tables, master tables and transaction tables. The Table Classification flag (TBL_CLASSIFICATION_FLG) sets the appropriate value for this lookup field to give a better view of the table classification.

Table Volume flag (TBL_VOLUME_FLG) is a customer modifiable field which is initially populated by product, but can be overridden by implementation. The field gives an idea of the relative data volume (categorized as highVolume, lowVolume and mediumVolume) of the table to make informed decisions.

3.2.10 Default Value Setting

The rules for setting the database default values are as follows:

- When a predefined default value is not available, set the default value of Non-null CHAR or VARCHAR columns to blank except the primary key columns.
- When a predefined default value is not available, set the default value Non-null Number columns to 0 (zero) except the primary key columns.
- No database default values should be assigned to the Non Null Date, Time, and Timestamp columns.

3.2.11 Foreign Key Constraints

Referential integrity is enforced by the application. You should not define foreign key constraints in the database except for the tables where the partition is required. Indexes are created on most of Foreign Key columns to increase performance. However, in the specific case of ILM implementation, some of the tables require Foreign Key constraints due to the referential partitioning.

3.3 Standard Columns

This section discusses the rules applied to standard columns and the attributes that are associated with these objects.

3.3.1 Owner Flag

Owner Flag (OWNER_FLG) columns exist on the system tables that are shared by multiple products. Oracle Utilities Application Framework limits the data modification of the tables that have owner flag to the data owned by the product.

3.3.2 Version

The Version column is used to for optimistic concurrency control in the application code. Add the Version column to all tables that are maintained by a Row Maintenance program.

4. Exadata Database Settings

If you are using the Oracle Exadata Database machine as the database server, ensure that you do the following:

- Use the Write-Back Flash Cache feature to leverage the Exadata Flash hardware
- Use the Exadata Smart Flash Logging feature

Note: By default, 512 MB of the Exadata flash is allocated to Smart Flash Logging. This is sufficient enough to handle the load of 300 million transactions daily in TFM.

- Set the temporary tablespace size to at least 600 GB
- Create `CISTS_01` table space to store the `cisadm` objects using the BIGFILE and EXTENT MANAGEMENT LOCAL AUTOALLOCATE clauses. For example:

```
CREATE BIGFILE TABLESPACE CISTS_01 DATAFILE  
'+DATAC1/DBNAME/datafile/cists01.dbf' SIZE 800G AUTOEXTEND ON  
EXTENT MANAGEMENT LOCAL AUTOALLOCATE;
```

Note: Exadata servers can have two types of disks – High Capacity and High Performance. The Exadata throughput may vary depending on the disk type.

5. Database Implementation Guidelines

This section outlines the general implementation guidelines for the database components, including:

- [Configuration Guidelines](#)
- [Implementation Guidelines](#)

5.1 Configuration Guidelines

This section describes the general recommendations for configuring various database objects and includes a brief syntax overview. It covers the general aspects of the database objects and does not cover any specific implementation requirements. This section includes the following topics:

- [Index](#)
- [Temporary and Undo Tablespace](#)
- [Transparent Data Encryption Recommendations](#)
- [Data Compression Recommendations](#)
- [Database Vault Recommendations](#)
- [Information Lifecycle Management \(ILM\) and Data Archiving Support](#)
- [Storage Recommendations](#)
- [Database Configuration Recommendations](#)
- [Database Syntax](#)
- [Database Initialization Parameters](#)
- [Shrink Tables](#)
- [Listener.ora Settings](#)

5.1.1 Index

Index recommendations specify points that need to be considered when creating indexes on a table:

1. Indexes on a table should be created according to the functional requirements of the table and not in order to perform SQL tuning.

Note: If the implementation creates a CM index on table-columns for which the product already provides an index, then the CM index will be overridden by the base index.

Table indexes become fragmented over time. This affects the database performance. Therefore, you need to rebuild indexes periodically using the following SQL commands:

```
ALTER INDEX MY_IDX REBUILD ONLINE PARALLEL 63 NOLOGGING;  
ALTER INDEX MY_IDX NOPARALLEL;  
ALTER INDEX MY_IDX LOGGING;
```

5.1.2 Temporary and Undo Tablespace

To begin with, we recommend you set the temporary tablespace to at least 100 GB auto extendable till 500 GB and the undo tablespace to at least 100 GB auto extendable till 600 GB. The upper limit of both the tablespaces will vary as per the volume of the data and preferred chunk size of the batch. In addition, we recommend you set the value of undo retention to 50000.

5.1.3 Transparent Data Encryption Recommendations

Oracle Utilities supports Oracle Transparent Data Encryption (TDE). Oracle TDE is available by default in Oracle Database Enterprise Edition, but you have to purchase an Oracle Advanced Security license to use it. The application supports tablespace level encryption for all application data. Make sure that the hardware resources are sufficiently sized for this as TDE uses additional hardware resources. The Oracle Advanced Security license is a prerequisite for using TDE.

Please consider the following when implementing TDE:

- Create a wallet folder to store the master key. By default, the wallet folder should be created under `$ORACLE_BASE/admin/<sid>`.
- The wallet containing the master key can be created using the following command:
`ALTER SYSTEM SET ENCRYPTION KEY AUTHENTICATED BY "KEYPASSWD"`
- The wallet can be closed or opened using the following commands:
`ALTER SYSTEM SET WALLET OPEN IDENTIFIED BY "KEYPASSWD";`
`ALTER SYSTEM SET WALLET CLOSE;`
- Column level encryption can be achieved using the following commands:
`CREATE TABLE <TABLE_NAME> NAME VARCHAR2(200) DEFAULT '' NOT NULL, BO_DATA_AREA CLOB ENCRYPT USING 'AES128', BO_STATUS_CD CHAR(12) ENCRYPT USING 'AES128') LOB (BO_DATA_AREA) STORE AS SECUREFILE (CACHE COMPRESS) TABLESPACE <TABLESPACE_NAME>;`
- AES128 is the default encryption algorithm.
- Tablespace level encryption is also supported using the following command:
`CREATE TABLESPACE <TABLESPACE_NAME> LOGGING DATAFILE '<DATAFILE LOCATION>' SIZE <INITIAL SIZE> REUSE AUTOEXTEND ON NEXT <NEXT SIZE> MAXSIZE UNLIMITED EXTENT MANAGEMENT LOCAL UNIFORM SIZE <UNIFORM SIZE> ENCRYPTION USING 'AES128' DEFAULT STORAGE (ENCRYPT);`
- Indexed columns can only be encrypted using the NO SALT Option. Salt is a way to strengthen the security of encrypted data. It is a random string added to the data before it is encrypted, causing repetition of text in the clear to appear different when encrypted.

5.1.4 Data Compression Recommendations

Oracle Utilities supports Advanced Data Compression, available with Oracle 11gR1 onwards, to reduce the database storage footprint. Make sure that your resources are sufficiently sized for this as it uses additional system resources. Compression can be enabled at the Tablespace level or at the Table level.

5.1.4.1 Non-Exadata Hardware

For non-Exadata hardware the recommendations are the same as above, except that you cannot use HCC compression (it is only available in Exadata database machine). Instead of HCC, you can use any other compression tool available to you for non-Exadata hardware.

5.1.4.2 CLOB Fields

All CLOB fields should be stored as SecureFiles and Medium compressed. This requires a separate license for Advanced Data Compression. As a part of the schema, we create the product- owned tables with compression turned OFF at the LOB level. If you have the license for Advanced Data Compression, you can enable compression by updating the storage.xml.

Oracle 12c onwards:

- Admin and Master Data tables and their indexes will NOT be compressed.
 - All Transactional Tables, including ILM enabled MOs shall be compressed.
 - Compression will be done at the tablespace level.
 - All multicolumn indexes on transactional/ILM tables will be compressed.
- Use 'compress advanced low'

5.1.5 Database Vault Recommendations

The product supports Database Vault. All non-application User IDs can be prevented from using DDL or DML statements against the application schema. So SYS and SYSTEM cannot issue DDL or DML statements against [CISADM](#) schema. The application-specific administration account can issue DDL statements but should not be able to perform any DML or DCL statements. Application user must be given DML only permissions. Database Vault can be used to control access during patch process and Install/Upgrade process.

5.1.6 Information Lifecycle Management (ILM) and Data Archiving Support

The product supports data archiving based on Information Lifecycle Management (ILM). For more information, refer to the *Oracle Revenue Management and Billing Information Lifecycle Management Implementation Guide*.

5.1.7 Storage Recommendations

This section specifies recommended options for storing the database objects.

5.1.7.1 SecureFile for Storing LOBs

The DB_SECUREFILE parameter is used to specify how to store large objects (LOBs) in the database. LOBs can now be stored as SecureFiles or BasicFiles. By default, the value for this parameter is set to PERMITTED in Oracle Database Server 12c or higher. It means the LOBs are allowed to be created as SecureFiles.

Points to Note:

- The storage options with SecureFiles for Heap Tables should be ENABLE STORAGE IN ROW, CACHE and COMPRESS.

- For the IOT Table the PCTTHRESHOLD 50 OVERFLOW clause should be specified and the storage options with SecureFiles should be ENABLE STORAGE IN ROW, CACHE and COMPRESS.
- The PCTTHRESHOLD should be specified as a percentage of the block size. This value defines the maximum size of the portion of the row that is stored in the Index block when an overflow segment is used.
- The CHUNK option for storage, which is the data size used when accessing or modifying LOB values, can be set to higher than one database block size if big LOBs are used in the IO Operation.
- For SecureFiles, ensure that the `db_securefile` initialization parameter is set to `ALWAYS`.
- The Tablespace where you are creating the SecureFiles should be enabled with Automatic Segment Space Management (ASSM). In Oracle Database 11g, the default mode of Tablespace creation is ASSM so it may already be set for the Tablespace. If it's not, then you have to create the SecureFiles on a new ASSM Tablespace.

Note:

To enable compression on SecureFiles, you must have an Oracle Advanced Compression license in addition to Oracle Database Enterprise Edition.

If you are using Oracle Database Enterprise Edition, you must ensure that the COMPRESS flag is set to Y in the `Storage.xml` file. Refer to the [Database Syntax](#) section for more information on SecureFiles.

5.1.8 Database Configuration Recommendations

This section specifies the recommended methods for configuring the database with a focus on specific functional area.

5.1.8.1 Large Redo Log File Sizes

The Redo Log files are written by the Log Writer Background process. These log files are written in a serial manner. Once a log file is full, a log switch occurs and the next log file starts getting populated.

It is recommended that the size of the Redo Log files should be sufficiently high so that you do not see frequent Log Switches in the alert logs of the database. Frequent Log Switches impact the IO performance and can be avoided by having a larger Redo Log File size.

We recommend you set the redo log file size to at least 4GB or more depending on the volume of transactions. This will help you to ensure that there are not more than 5 to 6 log switches per hour.

5.1.9 Database Syntax

This sections contains the following topics:

5.1.9.1 SecureFile

```
CREATE TABLE <Table_Name>
(COLUMN1 ... , COLUMN2 (CLOB))
LOB(COLUMN2) STORE AS SECUREFILE (CACHE COMPRESS);
```

```

CREATE TABLE <Table_Name>
(COLUMN1 ... , COLUMN2 (CLOB) CONSTRAINT <> PRIMARY KEY(...))
ORGANIZATION INDEX PCTTHRESHOLD 50 OVERFLOW
LOB(COLUMN2) STORE AS SECUREFILE (ENABLE STORAGE IN ROW CHUNK CACHE
COMPRESS);

```

5.1.10 Database Initialization Parameters

This section recommends value for each parameter in the `init.ora` file. These parameters are a starting point for database tuning. The actual or optimal value for a production environment may differ from one deployment to another.

The following recommendations must be treated as guidelines and not as the actual values:

Parameter	Recommended Value	Modifiable in Pluggable Database (PDB)
DB_CACHE_SIZE	4G	Yes
LOG_CHECKPOINT_INTERVAL	0	No
MEMORY_MAX_TARGET	40-50% of total available RAM on the node	No
MEMORY_TARGET	Value should be less than or equal to the value set for the MEMORY_MAX_TARGET parameter and at the same time it should be greater than or equal to the sum of SGA_TARGET and PGA_AGGREGATE_TARGET	Yes
OPTIMIZER_INDEX_CACHING	0 Note: The value for this parameter should not be changed because it can drastically degrade the batch performance.	Yes
OPTIMIZER_INDEX_COST_ADJ	100 Note: The value for this parameter should not be changed because it can drastically degrade the batch performance.	Yes
PGA_AGGREGATE_TARGET	2G	Yes
PROCESSES	3000	No

Parameter	Recommended Value	Modifiable in Pluggable Database (PDB)
SESSION_CACHED_CURSORS	500	Yes
SESSIONS	4500	Yes
SGA_MAX_SIZE	70-80% of the value defined for the MEMORY_MAX_TARGET parameter	No
SGA_TARGET	50-70% of the value defined for the MEMORY_TARGET parameter	Yes
STATISTICS_LEVEL	TYPICAL or ALL Note: This parameter is mandatory when you want to use automatic memory management.	Yes
TRANSACTIONS	3000	No
OPEN_CURSORS	500	Yes
STREAMS_POOL_SIZE	200M	Yes
OPTIMIZER_ADAPTIVE_PLANS	TRUE Note: By default, the value is set to TRUE. We recommend you set the value to TRUE from 12.2 onwards.	Yes
OPTIMIZER_ADAPTIVE_STATISTICS	FALSE Note: By default, the value is set to FALSE. We recommend you set the value to FALSE from 12.2 onwards.	Yes
PARALLEL_DEGREE_POLICY	Manual Note: By default, the value is set to Manual. We recommend you use the default value. Otherwise, an error might occur while installing ORMB.	Yes

Parameter	Recommended Value	Modifiable in Pluggable Database (PDB)
CURSOR_SHARING	<p>EXACT</p> <p>Note: By default, the value is set to EXACT. We recommend you use the default value. Otherwise, the system performance would be impacted.</p>	Yes
CPU_MIN_COUNT	<p>Value should be specific to the server. Client DBA should decide the value.</p> <p>Note: This parameter specifies the minimum number of CPUs required by a pluggable database (PDB) at any given time. This enables you to control each PDBs minimum share of CPU utilization within a container database (CDB).</p>	Yes
MAX_DATAPUMP_PARALLEL_PER_JOB	<p>Recommend range of values - 1 to 1024</p> <p>Note: This parameter specifies the maximum number of parallel Oracle Data Pump jobs per PDB. By default, the value is set to 50. You can change the value and set it as per the requirement.</p>	Yes
LOB_SIGNATURE_ENABLE	<p>TRUE</p> <p>Note: If this parameter is set to TRUE, then when you create a large object (LOB), Oracle Database automatically assigns a signature to the LOB locator.</p>	Yes

For example, we recommend you specify the following values for 100 GB of RAM when the Automatic Memory Management (AMM) is enabled:

```
MEMORY_MAX_TARGET = 60G
MEMORY_TARGET = 60G
STATISTICS_LEVEL = TYPICAL
```

For example, we recommend you specify the following values for 100 GB of RAM when the Automatic Shared Memory Management (ASMM) is enabled:

```
SGA_TARGET = 40G
SGA_MAX_SIZE = 40G
DB_CACHE_SIZE = 4G
PGA_AGGREGATE_TARGET = 20G
STATISTICS_LEVEL = TYPICAL
```

5.1.11 Shrink Tables

A large number of rows are inserted and then deleted from the following three tables:

- CI_TXN_DTL_PRITM_SUMMARY
- CI_TXN_DETAIL_STG
- CI_ROLLBACK_TXN_DETAIL

Therefore, these tables need to be shrunk periodically. This activity should be carried out when no other transactions are active on the database.

1. Extract and keep the DDL scripts for all the existing indexes on the above tables from the data dictionary.
2. Drop all the indexes on the above tables.
3. Shrink the tables by executing following statements using SQL client:

```
ALTER TABLE CI_TXN_DTL_PRITM_SUMMARY ENABLE ROW MOVEMENT;
ALTER TABLE CI_TXN_DTL_PRITM_SUMMARY SHRINK COMPACT;
ALTER TABLE CI_TXN_DETAIL_STG ENABLE ROW MOVEMENT;
ALTER TABLE CI_TXN_DETAIL_STG SHRINK COMPACT;
ALTER TABLE CI_ROLLBACK_TXN_DETAIL ENABLE ROW MOVEMENT;
ALTER TABLE CI_ROLLBACK_TXN_DETAIL SHRINK COMPACT;
```

Alternatively, you can shrink the tables by executing the following statements during the non-peak hours which will adjust high water mark to reclaim the space:

```
ALTER TABLE CI_TXN_DTL_PRITM_SUMMARY ENABLE ROW MOVEMENT;
ALTER TABLE CI_TXN_DTL_PRITM_SUMMARY SHRINK;
ALTER TABLE CI_TXN_DETAIL_STG ENABLE ROW MOVEMENT;
ALTER TABLE CI_TXN_DETAIL_STG SHRINK;
ALTER TABLE CI_ROLLBACK_TXN_DETAIL ENABLE ROW MOVEMENT;
ALTER TABLE CI_ROLLBACK_TXN_DETAIL SHRINK;
```

4. Recreate all the indexes using scripts generated in step 1 above.

You can execute these statements either manually or through a batch process which is configured to run at regular interval.

Note: Shrink operations can be performed only on segments in locally managed tablespaces with Automatic Segment Space Management (ASSM).

Once the above statements are executed, you must gather statistics using the following statements:

```
BEGIN
DBMS_STATS.GATHER_TABLE_STATS(OWNNAME=>'CISADM',
TABNAME=>'CI_TXN_DTL_PRITM_SUMMARY', GRANULARITY=>'ALL',
CASCADE=>TRUE, METHOD_OPT=>'FOR ALL COLUMNS SIZE AUTO', DEGREE=>32);
DBMS_STATS.GATHER_TABLE_STATS(OWNNAME=>'CISADM',
TABNAME=>'CI_TXN_DETAIL_STG', GRANULARITY=>'ALL', CASCADE=>TRUE,
METHOD_OPT=>'FOR ALL COLUMNS SIZE AUTO', DEGREE=>32);
DBMS_STATS.GATHER_TABLE_STATS(OWNNAME=>'CISADM',
TABNAME=>'CI_ROLLBACK_TXN_DETAIL', GRANULARITY=>'ALL', CASCADE=>TRUE,
METHOD_OPT=>'FOR ALL COLUMNS SIZE AUTO', DEGREE=>32);
END;
```

5.1.12 Listener.ora Settings

In the Oracle 12c container database, the client must specify a service name in order to connect to the pluggable database. If you have hard-coded connect descriptors to use SID to connect to the database, then the following error occurs:

"ORA-12505: TNS: LISTENER DOES NOT CURRENTLY KNOW OF SID GIVEN IN CONNECT DESCRIPTOR TIPS"

It means the database connection has failed. You can resolve the problem using the `USE_SID_AS_SERVICE_listener_name` parameter in the `listener.ora` file. If you set the `USE_SID_AS_SERVICE_listener_name` parameter to `on`, it instructs the listener to use the SID in the connect descriptor as a service name and connect the client to the specified database. By default, the parameter is set to `off`.

Once you set the parameter to `on`, you need to bounce or reload the listener.

5.2 Implementation Guidelines

This section provides specific guidelines for implementing Oracle Database.

5.2.1 Materialized View

Oracle Database Enterprise Edition supports query rewrite using Materialized view. If you use Oracle Database Enterprise Edition, you can create the following Materialized Views to improve the performance of the Monitor batch jobs.

Prerequisite:-

Please make sure the following:

1. Set the `QUERY_REWRITE_ENABLED` parameter to `TRUE` at database level using either of the following command:

```
ALTER SYSTEM SET QUERY_REWRITE_ENABLED=TRUE;
```

OR

```
ALTER SYSTEM SET QUERY_REWRITE_ENABLED=TRUE SCOPE=BOTH;
```

2. To create a materialized view in another user's schema: You must have the CREATE ANY MATERIALIZED VIEW system privilege. The owner of the materialized view must have the CREATE TABLE system privilege. The owner must also have access to any master tables of the materialized view that the schema owner does not own (for example, if the master tables are on a remote database) and to any materialized view logs defined on those master tables, either through a SELECT object privilege on each of the tables or through the SELECT ANY TABLE system privilege.
3. To create a refresh-on-commit materialized view (ON COMMIT REFRESH clause), in addition to the preceding privileges, you must have the ON COMMIT REFRESH object privilege on any master tables that you do not own or you must have the ON COMMIT REFRESH system privilege.

To create the materialized view with query rewrite enabled, in addition to the preceding privileges: If the schema owner does not own the master tables, then the schema owner must have the GLOBAL QUERY REWRITE privilege or the QUERY REWRITE object privilege on each table outside the schema.

```

CREATE MATERIALIZED VIEW F1_BO_LIFECYCLE_STATUS_MVW
(
  BUS_OBJ_CD,
  LIFE_CYCLE_BO_CD,
  BO_STATUS_CD,
  BATCH_CD
)
BUILD IMMEDIATE REFRESH ON COMMIT ENABLE QUERY REWRITE AS SELECT
BO2.BUS_OBJ_CD, BO.LIFE_CYCLE_BO_CD, BOSA.BO_STATUS_CD,
LCBOS.BATCH_CD AS
LC_BATCH_CD
FROM
F1_BUS_OBJ BO2,
F1_BUS_OBJ BO,
F1_BUS_OBJ_STATUS LCBOS,
F1_BUS_OBJ_STATUS_ALG BOSA
WHERE
BO2.LIFE_CYCLE_BO_CD = BO.LIFE_CYCLE_BO_CD AND
BO.BUS_OBJ_CD = BOSA.BUS_OBJ_CD AND
BOSA.BO_STATUS_SEVT_FLG = 'F1AT' AND
LCBOS.BUS_OBJ_CD = BO.LIFE_CYCLE_BO_CD AND
LCBOS.BO_STATUS_CD = BOSA.BO_STATUS_CD
/
CREATE SYNONYM SPLUSR.F1_BO_LIFECYCLE_STATUS_MVW FOR
SPLADM.F1_BO_LIFECYCLE_STATUS_MVW;
GRANT SELECT ON F1_BO_LIFECYCLE_STATUS_MVW TO FW_DEV;
GRANT SELECT ON F1_BO_LIFECYCLE_STATUS_MVW TO SPL_USER;
GRANT SELECT ON F1_BO_LIFECYCLE_STATUS_MVW TO SPL_READ;

```

For more information, refer to the following documents:

Topic	Reference URL
Basic Query Rewrite (Oracle 11g)	https://docs.oracle.com/cd/B28359_01/server.111/b28313/qrbasic.htm
Basic Query Rewrite for Materialized Views (Oracle 12c)	https://docs.oracle.com/database/121/DWHSG/qrbasic.htm#DWHSG01813
Troubleshooting Materialized Views	http://docs.oracle.com/database/121/ARPLS/d_mview.htm#ARPLS67193
Debugging Materialized Views	http://docs.oracle.com/cd/B28359_01/server.111/b28313/qradv.htm

Known Issues:

The following are some of the known issues at the time of release. For more information, refer to these articles on [My Oracle Support](#):

- *Query Did Not Rewrite For A User Other Than The Owner Of the Materialized View (Document ID: 1594725.1)* - A patch is available for the 14772096 bug for some platforms.
- *Query rewrite not working as expected with SELECT DISTINCT (Document ID: 7661113.8)* – A bug reported in Oracle Database 11.2.0.1 and 11.1.0.7 and fixed in Oracle Database 12.1.0.1 (Base Release), 11.2.0.2 (Server Patch Set).

5.2.2 Increase INITRANS Values

It has been observed that while executing few batches in ORMB, customers encounter deadlock issue. Therefore, we strongly recommend to increase the INITRANS value of tables with high concurrent DML. The INITRANS values can be set as per the customer's data volume. To increase the INITRANS values of the required tables and indexes:

1. Connect to the ORMB database using any SQL client (such as Oracle SQL Developer or PL/SQL Developer) and the `cisadm` credentials.
2. Use the ALTER statement to modify the INITRANS values of the required tables.

For example, you can increase the INITRANS value of the CI_BILL table using the following SQL statement:

```
ALTER TABLE CISADM.CI_BILL INITRANS 20;
```

3. Use the ALTER statement to modify the INITRANS values of the required indexes.

For example, you can increase the INITRANS value of the indexes using the following SQL statement:

```
ALTER INDEX XT033P0 INITRANS 40;
ALTER INDEX XT033S1 INITRANS 40;
ALTER INDEX XT033S2 INITRANS 40;
ALTER INDEX XT033S3 INITRANS 40;
ALTER INDEX XT033S4 INITRANS 40;
ALTER INDEX XT033S5 INITRANS 40;
```

With the above ALTER statements, the INITRANS applies only to the data blocks subsequently allocated for the table. It will not modify the existing data blocks. To apply the changes to the existing data blocks/extents, use the ALTER statement with MOVE command during the maintenance period. With the MOVE command, all indexes of the table become unusable and therefore, you will have to rebuild the indexes of the tables. For example, you can increase the INITRANS value of the CI_BILL table using the following ALTER TABLE MOVE command:

```
ALTER TABLE CI_BILL MOVE ONLINE INITRANS 20 NOLOGGING;
```

And, you can increase the INITRANS value of the indexes using the following ALTER INDEX REBUILD command:

```
ALTER INDEX XT033P0 REBUILD ONLINE INITRANS 40 NOLOGGING;
ALTER INDEX XT033S1 REBUILD ONLINE INITRANS 40 NOLOGGING;
ALTER INDEX XT033S2 REBUILD ONLINE INITRANS 40 NOLOGGING;
ALTER INDEX XT033S3 REBUILD ONLINE INITRANS 40 NOLOGGING;
ALTER INDEX XT033S4 REBUILD ONLINE INITRANS 40 NOLOGGING;
ALTER INDEX XT033S5 REBUILD ONLINE INITRANS 40 NOLOGGING;
```

5.2.3 Table Partitioning Strategy

Partitioning is powerful functionality that allows tables, indexes, and index-organized tables to be subdivided into smaller pieces, enabling these database objects to be managed and accessed at a finer level of granularity. Oracle provides a comprehensive range of partitioning schemes to address every business requirement. We recommend you partition those tables where the customers have considerable amount of data. This helps to manage data and ensure consistent system performance with the increasing data.

You need to partition the master and child tables in such a way that the referential integrity is not hampered. There are many partitioning strategies which can be used to partition tables. However, we recommend you partition the following tables using the partition type and keys as mentioned in the below table:

Note: An out of box sample release-specific table partitioning scripts are provided by Oracle Revenue Management and Billing on [My Oracle Support](#). You can partition the tables using these sample scripts. For more information about the sample partitioning scripts, contact Oracle Revenue Management and Billing Support team.

Module Name	Table Name	Child Table Name	Partition Type	Partition Key	Sub-Partition Key
Transaction Feed Management (TFM)	CI_TXN_DETAIL		RANGE (DATE INTERVAL)	CURR_SYS_PRCSDT	-
	CI_TXN_DTL_PRITM		RANGE (DATE INTERVAL)	CURR_SYS_PRCSDT	-
	CI_ROLLBACK_TXN_DETAIL		RANGE (DATE INTERVAL)	CURR_SYS_PRCSDT	-
	CI_TXN_DETAIL_EXCP		RANGE (DATE INTERVAL)	CURR_SYS_PRCSDT	-
	CI_TXN_CALC		RANGE (DATE INTERVAL)	ILM_DT	-
	CI_TXN_SQ		RANGE (DATE INTERVAL)	ILM_DT	-
	CI_TXN_CALC_LN		RANGE (DATE INTERVAL)	ILM_DT	-
	CI_TXN_CALC_LN_CHAR		RANGE (DATE INTERVAL)	ILM_DT	-
Billing	CI_BILL		RANGE (DATE INTERVAL)	ILM_DT	BILL_ID
		CI_BILL_CHA_R	REFERENCE	BILL_ID	-

Module Name	Table Name	Child Table Name	Partition Type	Partition Key	Sub-Partition Key
		CI_BILL_EXCP	REFERENCE	BILL_ID	-
		CI_BILL_MSG_PRM	REFERENCE	BILL_ID	-
		CI_BILL_ROUTING	REFERENCE	BILL_ID	-
		CI_BILL_SA	REFERENCE	BILL_ID	-
		CI_BILL_ACH	REFERENCE	BILL_ID	-
		CI_BILL_MSGS	REFERENCE	BILL_ID	-
		CI_BILL_LOG	REFERENCE	BILL_ID	-
	CI_BSEG		RANGE (DATE INTERVAL)	ILM_DT	BSEG_ID
		CI_BSEG_CACL	REFERENCE	BSEG_ID	-
		CI_BSEG_CACL_LN	REFERENCE	BSEG_ID	-
		CI_BSEG_CL_CHAR	REFERENCE	BSEG_ID	-
		CI_BSEG_EXCP	REFERENCE	BSEG_ID	-
		CI_BSEG_ITEM	REFERENCE	BSEG_ID	-
		CI_BSEG_MSG	REFERENCE	BSEG_ID	-
		CI_BSEG_READ	REFERENCE	BSEG_ID	-
		CI_BSEG_SQ	REFERENCE	BSEG_ID	-
		CI_BSEG_EXCT	REFERENCE	BSEG_ID	-
	CI_ADJ		RANGE (DATE INTERVAL)	ILM_DT	ADJ_ID
		CI_ADJ_APREQ	REFERENCE	ADJ_ID	-

Module Name	Table Name	Child Table Name	Partition Type	Partition Key	Sub-Partition Key
Revenue Management	CI_ADJ_CAL_C_LN	CI_ADJ_CAL_C_LN	REFERENCE	ADJ_ID	-
		CI_ADJ_CHA_R	REFERENCE	ADJ_ID	-
		CI_ADJ_CL_CHAR	REFERENCE	ADJ_ID	-
	CI_BILL_CHG		RANGE (DATE INTERVAL)	ILM_DT	BILLABLE_CHG_ID
		CI_BCHG_READ	REFERENCE	BILLABLE_CHG_ID	-
		CI_BCHG_SQ	REFERENCE	BILLABLE_CHG_ID	-
		CI_BILL_CHG_CHAR	REFERENCE	BILLABLE_CHG_ID	-
		CI_B_CHG_LINE	REFERENCE	BILLABLE_CHG_ID	-
		CI_B_LN_CHAR	REFERENCE	BILLABLE_CHG_ID	-
Payment	CI_PAY		RANGE (DATE INTERVAL)	ILM_DT	PAY_ID
		CI_PAY_CHA_R	REFERENCE	PAY_ID	-
		CI_PAY_EXCP	REFERENCE	PAY_ID	-
		CI_PAY_SEG	REFERENCE	PAY_ID	-
	CI_PAY_EVENT		RANGE (DATE INTERVAL)	ILM_DT	PAY_EVENT_ID
		CI_PAY_EVT_EXCP	REFERENCE	PAY_EVENT_ID	-
		CI_P EVT_DS T_DTL	REFERENCE	PAY_EVENT_ID	-
		CI_PAY_TNDR	REFERENCE	PAY_EVENT_ID	-
	CI_PAY_TNDR		REFERENCE	PAY_EVENT_ID	-
		CI_APAY_CL_R_STG	REFERENCE	PAY_TENDER_ID	-

Module Name	Table Name	Child Table Name	Partition Type	Partition Key	Sub-Partition Key
		CI_PAY_TND_R_CHAR	REFERENCE	PAY_TENDER_ID	-
Financial Transaction	CI_FT		RANGE (DATE INTERVAL)	ILM_DT	FT_ID
		CI_FT_GL	REFERENCE	FT_ID	-
		CI_FT_PROC	REFERENCE	FT_ID	-
		CI_FT_GL_EXT	REFERENCE	FT_ID	-
		C1_FT_EXT_CHAR	REFERENCE	FT_ID	-
		C1_FT_EXT	REFERENCE	FT_ID	-
Membership	CI_MEMBERSHIP		RANGE (DATE INTERVAL)	ILM_DT	MEMBERSHIP_ID
		CI_MEMBERSHIP_CHAR	REFERENCE	MEMBERSHIP_ID	-
		CI_MEMBERSHIP_PER_CHAR	REFERENCE	MEMBERSHIP_ID	-
		CI_MEMBERSHIP_LOG	REFERENCE	MEMBERSHIP_ID	-
		CI_MEMBERSHIP_PER	REFERENCE	MEMBERSHIP_ID	-
		CI_MEMBERSHIP_SA	REFERENCE	MEMBERSHIP_ID	-
		CI_MEMBERSHIP_LOG_PARM	REFERENCE	MEMBERSHIP_ID	-
Entity Audit	C1_AUDIT_EVENT		RANGE (DATE INTERVAL)	ILM_DT	AUDIT_EVENT_ID
		C1_AUDIT_EVENT_CHAR	REFERENCE	AUDIT_EVENT_ID	-
		C1_AUDIT_EVENT_LOG	REFERENCE	AUDIT_EVENT_ID	-

Module Name	Table Name	Child Table Name	Partition Type	Partition Key	Sub-Partition Key
		C1_AUDIT_EVENT_LOG_PARM	REFERENCE	AUDIT_EVENT_ID	-
Inbound Message	C1_INBOUND_MESSAGE		RANGE (DATE INTERVAL)	ILM_DT	C1_INBOUND_MESSAGE_ID
		C1_INBOUND_MESSAGE_CHAR	REFERENCE	C1_INBOUND_MESSAGE_ID	-
		C1_INBOUND_MESSAGE_LOG	REFERENCE	C1_INBOUND_MESSAGE_ID	-
		C1_INBOUND_MESSAGE_LOG_PARM	REFERENCE	C1_INBOUND_MESSAGE_ID	-
Pricing Calculation	CI_PRCE_CALC		RANGE (DATE INTERVAL)	ILM_DT	PRCE_CALC_ID
		CI_PRCE_CALC_LN	REFERENCE	PRCE_CALC_ID	-
		CI_PRCE_CALC_PARAMS	REFERENCE	PRCE_CALC_ID	-
Match Event	CI_MATCH_EVT		RANGE	MATCH_EVT_ID	-
Membership Repricing	CI_REPRC_REQ_DTL		RANGE	REPRC_ENTITY_ID	-
	CI_REPRC_ENTITY_DTL		RANGE	PREPRCS_REQ_ID	-

You can use either of the following approach for partitioning tables:

- **Offline Partitioning (Using Export and Import for Table Partitioning)** – In this approach, you need to do the following:
 - Export data from the tables using the Oracle Export Data Pump functionality (i.e. expdp) with the **Data Only** option.
 - Drop the tables and recreate them with partition.
 - Import the data in the tables using the Oracle Import Data Pump functionality (i.e. impdp).
 - Create the indexes for the tables.

Disadvantage of using this approach: It requires downtime.

Advantage of using this approach: It is faster than online partitioning. It takes approximately 12 hours for 1 TB data using 32 parallel servers execution.

- **Online Partitioning (Using the Alter Table Command for Table Partitioning)** – You can convert the table to a partitioned table using the ALTER TABLE ... MODIFY command.

Disadvantage of using this approach: It requires more time than offline partitioning. It takes approximately 17 hours for 1 TB data using 32 parallel servers execution.

Advantage of using this approach: It does not require downtime.

5.2.4 Performance Monitoring

SQLTXPLAIN, also known as SQLT, is a tool provided by Oracle Server Technologies. It enables users to analyze and tune the performance of a single SQL statement. SQLT inputs one SQL statement and outputs a set of diagnostics files. These output files are commonly used to diagnose SQL statements performing poorly. SQLT connects to the database and collects execution plans, Cost-based Optimizer CBO statistics, schema objects metadata, performance statistics, configuration parameters, and similar elements that influence the performance of the SQL being analyzed.

Refer to the *All About the SQLT Diagnostic Tool (Document ID: 215187.1)* article on [My Oracle Support](#) for more information about:

- How to install SQLT
- How to determine the SQL_ID for an SQL Statement
- How to interpret the SQLTXPLAIN Main report

Another tool named Automatic Workload Repository (AWR) is used to collect performance statistics including:

- Wait events used to identify performance problems
- Gather system and session statistics
- Object usage statistics
- Resource intensive SQL statements

To generate the AWR report, refer to the *How to Create an AWR Report at the PDB level on 12.2 or later (Document ID: 2334006.1)* article on [My Oracle Support](#) for more information.

5.2.5 Local Undo Mode in Oracle Database 12c Release 2

In Oracle Database 12c Release 2, each container in an instance can use its own undo tablespace. This new undo management mechanism is called local undo mode. Some of the new multitenant features in 12.2 rely on local undo. We recommend you set local undo for each pluggable database (PDB).

If you are upgrading from Oracle Database 12c Release 1, then change the undo mode from Shared to Local.

To view the current undo mode, use the following code snippet:

```
Column property_name format a30
Column property_value format a30
Select property_name, property_value from database_properties where
property_name = 'LOCAL_UNDO_ENABLED';
```

The above query indicates the undo mode which is currently used. For example:

PROPERTY_NAME	PROPERTY_VALUE
LOCAL_UNDO_ENABLED	TRUE

5.2.6 Memory Resource Management for PDBs in Oracle Database 12c Release 2

In the previous release of Oracle Database, there was no way to control the amount of memory used by an individual pluggable database (PDB). Oracle Database 12c Release 2 (12.2) allows you to control the amount of memory used by a PDB, making consolidation more reliable.

You can set the following memory parameters at the pluggable database level:

- **DB_CACHE_SIZE** - The minimum buffer cache size for the pluggable database.
- **SHARED_POOL_SIZE** - The minimum shared pool size for the pluggable database.
- **PGA_AGGREGATE_LIMIT** - The maximum PGA size for the pluggable database.
- **PGA_AGGREGATE_TARGET** - The target PGA size for the pluggable database.
- **SGA_MIN_SIZE** - The minimum SGA size for the pluggable database.
- **SGA_TARGET** - The maximum SGA size for the pluggable database.

The process of setting memory parameters for a pluggable database is similar to setting memory parameters for a regular instance.

5.2.7 Global Optimizer Statistics Settings

We recommend you implement some standard settings as mentioned in this section which will help to gather statistics in a faster way.

5.2.7.1 Setting Stale Percentage

Oracle determines whether the object need statistics by validating the `STALE_STATS` and `STALE_PERCENT` values. Using the following code snippet, you can collect statistics for even single row level updates for the non-partitioned and partitioned tables:

```
BEGIN
  DBMS_STATS.SET_GLOBAL_PREFS('STALE_PERCENT', 0);
END;
```

You can verify the setting using the following SQL statement:

```
SELECT DBMS_STATS.GET_PREFS('STALE_PERCENT') FROM DUAL;
```

5.2.7.2 Incremental Statistics Gathering

We recommend you enable the incremental statistics gathering feature only for partitioned tables. This feature not only reduces the time it takes to gather global statistics, but also increases the statistics

accuracy. This feature avoids scanning whole table when computing global statistics and derives it from partition level statistics.

Set the `INCREMENTAL` option to `TRUE` for every partitioned table in the CISADM schema and set its stale percent as shown in the following code snippet:

```
BEGIN
DBMS_STATS.SET_TABLE_PREFS(NULL, 'TABLE_NAME', 'INCREMENTAL', 'TRUE');
END;
BEGIN
DBMS_STATS.SET_GLOBAL_PREFS('INCREMENTAL_STALENESS',
'USE_STALE_PERCENT');
END;
```

You can verify the setting using the following SQL statement:

```
SELECT DBMS_STATS.GET_PREFS('INCREMENTAL') FROM DUAL;
```

5.2.7.3 Setting Auto Degree

Gathering statistics with auto sample size initiates full table scans to inspect table data. We can leverage parallel execution to make these scans complete in less time. We recommend you set the `AUTO_DEGREE` property at the global level using the following code snippet:

```
BEGIN
DBMS_STATS.SET_GLOBAL_PREFS('DEGREE', DBMS_STATS.AUTO_DEGREE)
END;
```

5.2.7.4 Automatic Statistics Gathering

Oracle Database collects statistics for database objects that do not have statistics or have stale (i.e. out of date) statistics. This is done by an automatic task that executes during a predefined maintenance window. Oracle internally prioritizes the database objects that require statistics so that objects which need statistics on priority are processed first.

You can verify the last auto gather job status using the following SQL statement:

```
SELECT CLIENT_NAME, JOB_STATUS, JOB_START_TIME, JOB_DURATION FROM
DBA_AUTOTASK_JOB_HISTORY WHERE JOB_START_TIME > SYSTIMESTAMP - 3 AND
CLIENT_NAME='AUTO OPTIMIZER STATS COLLECTION' ORDER BY JOB_START_TIME
DESC;
```

If the job is not successfully completed or is incomplete due low maintenance window, then run the optimizer advisor to identify the objects which are not processed in the job. For more information, refer to the [Optimizer Statistics Advisor](#) section.

5.2.7.5 Concurrent Statistics Gathering

If the concurrent statistics gathering mode is enabled, the database can simultaneously gather optimizer statistics for multiple tables in a schema, or for multiple partitions or sub partitions in a table. Gathering statistics on multiple tables and (sub) partitions concurrently can reduce the overall time it takes to gather statistics by allowing the database server to fully utilize a multi-processor environment.

Before you enable the concurrent statistics gathering mode, you must activate an Oracle Resource Manager Plan. Statistics gathering with parallel and concurrent execution has the potential to consume lots of system resources. In order to control this usage, we need the resource manager plan in place. The aim of this resource manager plan is to control the resources used by the concurrent statistics jobs.

You need to check whether a resource manager plan is active at the database level. If no value is specified for the RESOURCE_MANAGER_PLAN parameter, the database resource manager is not activated. In this case, you should not enable the concurrent statistics gathering mode. Otherwise, the following error will occur:

ERROR AT LINE 1:

```
ORA-20000: UNABLE TO GATHER STATISTICS CONCURRENTLY: RESOURCE MANAGER IS NOT ENABLED.
```

```
ORA-06512: AT "SYS.DBMS_STATS", LINE 34634
```

```
ORA-06512: AT LINE 1
```

Assigning a resource plan is a prerequisite for using the concurrent statistics gathering feature. The user must have privileges for the following:

- CREATE JOB
- MANAGE SCHEDULER
- MANAGE ANY QUEUE

You should disable the parallel adaptive multi-user because we are using the parallel execution as part of concurrent statistics gathering. You can disable the parallel adaptive multi-user using the following statement:

```
ALTER SYSTEM SET PARALLEL_ADAPTIVE_MULTI_USER=FALSE
```

By default, the concurrency setting for statistics gathering is turned off. It can be turned on using the following code snippet:

```
BEGIN
DBMS_STATS.SET_GLOBAL_PREFS ('CONCURRENT', 'MANUAL');
END;
```

You can verify the setting using the following SQL statement:

```
SELECT DBMS_STATS.GET_PREFS ('CONCURRENT') FROM DUAL;
```

5.2.8 Optimizer Statistics Advisor

The Optimizer Statistics Advisor analyzes how optimizer statistics are gathered, and then makes some recommendations on how to improve the statistics gathering strategy in order to provide more efficient statistics to the Cost-Based Optimizer (CBO). This feature is available in Oracle Database 12c Release 2.

5.2.8.1 Creating an Optimizer Statistics Advisor Task

The DBMS_STATS.CREATE ADVISED_TASK function creates a task for Optimizer Statistics Advisor. You can create an advisor task using the following code snippet:

```
DECLARE
TNAME VARCHAR2 (32767);
```

```

RET VARCHAR2(32767);

BEGIN
TNAME := 'RMB_ADVISOR_16';
RET := DBMS_STATS.CREATE_ADVISOR_TASK(TNAME);
END;

```

You can view the advisor task using the following SQL statement:

```

SELECT TASK_NAME, ADVISOR_NAME, CREATED, STATUS FROM DBA_ADVISOR_TASKS
WHERE ADVISOR_NAME = 'STATISTICS ADVISOR';

```

5.2.8.2 Creating Filters for an Optimizer Advisor Task

Filters are useful for including or excluding a specific set of rules, schemas, or operations from Optimizer Statistics Advisor tasks. The simplest way to create filters is to use the following DBMS_STATS procedures either individually or in combination:

- **CONFIGURE_ADVISOR_OBJ_FILTER** - Use this procedure to include or exclude the specified database schemas or objects.
- **CONFIGURE_ADVISOR_RULE_FILTER** - Use this procedure to include or exclude the specified rules.
- **CONFIGURE_ADVISOR_OPR_FILTER** - Use this procedure to include or exclude the specified DBMS_STATS operations.

In the following code snippet, the 1st filter will disable the advisor for all objects; 2nd, 3rd, and 4th filters will enable the `AvoidStaleStats`, `UseIncremental`, and `NotUseIncremental` rules for the `CISADM` objects; and 5th, 6th, 7th, and 8th filters will disable the respective rules.

```

DECLARE
FILTER1 CLOB;
FILTER2 CLOB;
FILTER3 CLOB;
FILTER4 CLOB;
FILTER5 CLOB;
FILTER6 CLOB;
FILTER7 CLOB;
FILTER8 CLOB;

BEGIN
FILTER1 := DBMS_STATS.CONFIGURE_ADVISOR_OBJ_FILTER(TASK_NAME =>
'RMB_ADVISOR_16', STATS_ADV_OPR_TYPE => 'EXECUTE', RULE_NAME => NULL,
OWNNAME => NULL, TABNAME => NULL, ACTION => 'DISABLE');

FILTER2 := DBMS_STATS.CONFIGURE_ADVISOR_OBJ_FILTER(TASK_NAME =>
'RMB_ADVISOR_16', STATS_ADV_OPR_TYPE => 'EXECUTE', RULE_NAME =>
'NotUseIncremental');

```

```
'AVOIDSTALESTATS', OWNNAME => 'CISADM', TABNAME => NULL, ACTION =>
'ENABLE');

FILTER3 := DBMS_STATS.CONFIGURE_ADVISOR_OBJ_FILTER(TASK_NAME =>
'RMB_ADVISOR_16', STATS_ADV_OPR_TYPE => 'EXECUTE', RULE_NAME =>
'USEINCREMENTAL', OWNNAME => 'CISADM', TABNAME => NULL, ACTION =>
'ENABLE');

FILTER4 := DBMS_STATS.CONFIGURE_ADVISOR_OBJ_FILTER(TASK_NAME =>
'RMB_ADVISOR_16', STATS_ADV_OPR_TYPE => 'EXECUTE', RULE_NAME =>
'NOTUSEINCREMENTAL', OWNNAME => 'CISADM', TABNAME => NULL, ACTION =>
'ENABLE');

FILTER5 := DBMS_STATS.CONFIGURE_ADVISOR_RULE_FILTER(TASK_NAME =>
'RMB_ADVISOR_16', STATS_ADV_OPR_TYPE => 'EXECUTE', RULE_NAME =>
'USECONCURRENT', ACTION => 'DISABLE');

FILTER6 := DBMS_STATS.CONFIGURE_ADVISOR_RULE_FILTER(TASK_NAME =>
'RMB_ADVISOR_16', STATS_ADV_OPR_TYPE => 'EXECUTE', RULE_NAME =>
'USEDFAULTPARAMS', ACTION => 'DISABLE');

FILTER7 := DBMS_STATS.CONFIGURE_ADVISOR_RULE_FILTER(TASK_NAME =>
'RMB_ADVISOR_16', STATS_ADV_OPR_TYPE => 'EXECUTE', RULE_NAME =>
'USEAUTOJOB', ACTION => 'DISABLE');

FILTER8 := DBMS_STATS.CONFIGURE_ADVISOR_RULE_FILTER(TASK_NAME =>
'RMB_ADVISOR_16', STATS_ADV_OPR_TYPE => 'EXECUTE', RULE_NAME =>
'USEGATHERSCHEMASTATS', ACTION => 'DISABLE');

END;
```

5.2.8.3 Executing an Optimizer Statistics Advisor Task

The DBMS_STATS.EXECUTE_ADVISOR_TASK function executes a task for Optimizer Statistics Advisor. You can execute an advisor task using the following code snippet:

```
DECLARE
TNAME VARCHAR2(32767);
RET VARCHAR2(32767);
BEGIN
TNAME := 'RMB_ADVISOR_16';
RET := DBMS_STATS.EXECUTE_ADVISOR_TASK(TNAME);
END;
```

5.2.8.4 Generating a Report for an Optimizer Statistics Advisor Task

We recommend you configure daily job to run the advisor in the non-peak hours and generate the report. The DBMS_STATS.REPORT_ADVISOR_TASK function generates a report for an Optimizer Statistics Advisor task. The report summarizes the findings and rules violated by the findings and lists the recommendations (if any) for the finding. You can view the report using the following SQL statement:

```
SELECT
DBMS_STATS.REPORT_ADVISOR_TASK('RMB_ADVISOR_16',NULL,'TEXT','ALL','ALL')
' AS REPORT FROM DUAL;
```

5.2.8.5 Implementing Optimizer Statistics Advisor Recommendations

You can implement all recommendations given by the advisor automatically or manually. You can use the following code snippet to implement all recommendations automatically:

```
DECLARE
TNAME VARCHAR2(32767);
RET VARCHAR2(32767);
BEGIN
TNAME := 'RMB_ADVISOR_16';
RET := DBMS_STATS.IMPLEMENT_ADVISOR_TASK(TNAME);
END;
```

Alternatively, you can implement the recommendations manually for each table using the following code snippet:

```
BEGIN
DBMS_STATS.GATHER_TABLE_STATS(OWNNAME=>'CISADM', TABNAME=>'TABLE-NAME',
GRANULARITY=>'ALL', CASCADE=>TRUE, METHOD_OPT=>'FOR ALL COLUMNS SIZE AUTO')
END;
```

5.2.9 Using the Segment Advisor

A table may experience large number of updates. As a result, there might be performance issues while executing queries on these tables. In such case, we recommend you use the segment advisor. The segment advisor is used for identifying segments which are candidates for a shrink operation (i.e. releasing unused space and moving the High Water Mark).

The segment advisor can generate the advice with different degrees of granularity. For example, you can generate advice for all objects in a tablespace or for a specific table, index, or partition.

We recommend you run the segment advisor for the following:

- Objects with size more than 50 G or 100 G
- Temporary tables (such as, CI_TXN_DETAIL_STG) where there are large number of insertions and deletions

5.2.9.1 Manually Generating Segment Advisor Advice

To run the segment advisor manually, you need to do the following (as shown in the below code snippet):

1. Create a Task
2. Assign an Object to the Task
3. Set the Task Parameters
4. Execute the Task

```
SET SERVEROUTPUT ON
DECLARE
seg_task_id    number;
seg_task_name  varchar2(100);
seg_task_desc  varchar2(500);
OBJ_ID         number;
BEGIN
seg_task_name := 'ANALYZE_TABLE_DATA';
seg_task_desc := 'Manual Segment Advisor Run for table';

-- Step 1
dbms_advisor.create_task(
advisor_name => 'Segment Advisor',
task_id      => seg_task_id,
task_name    => seg_task_name,
task_desc    => seg_task_desc);

-- Step2
dbms_advisor.create_object(
task_name   => seg_task_name,
object_type => 'TABLE',
attr1       => 'CISADM',
attr2       => 'CI_BSEG_CALC',
attr3       => NULL,
attr4       => NULL,
attr5       => NULL,
object_id   => obj_id);
```

```
-- Step3
dbms_advisor.set_task_parameter(
task_name => seg_task_name,
parameter => 'recommend_all',
value      => 'TRUE');

-- Step4
DBMS_ADVISOR.EXECUTE_TASK(seg_task_name);

FOR cur_rec IN (SELECT f.impact, o.type, o.attr1, o.attr2, f.message,
f.more_info FROM dba_advisor_findings f JOIN dba_advisor_objects o ON
f.object_id = o.object_id AND f.task_name = o.task_name WHERE
f.task_name = seg_task_name ORDER BY f.impact DESC)
LOOP
DBMS_OUTPUT.put_line('.');
DBMS_OUTPUT.put_line('Type          : ' || cur_rec.type);
DBMS_OUTPUT.put_line('Attr1        : ' || cur_rec.attr1);
DBMS_OUTPUT.put_line('Attr2        : ' || cur_rec.attr2);
DBMS_OUTPUT.put_line('Message      : ' || cur_rec.message);
DBMS_OUTPUT.put_line('More info   : ' || cur_rec.more_info);
END LOOP;

DBMS_ADVISOR.delete_task(task_name => seg_task_name);

EXCEPTION
WHEN OTHERS THEN
DBMS_OUTPUT.put_line('Error           : ' || DBMS_UTILITY.format_error_backtrace);
DBMS_ADVISOR.delete_task(task_name => seg_task_name);
End;
```

Similarly, you can manually generate segment advisor advice for an index. You just need to change the `OBJECT_TYPE` to `INDEX` and specify the index name in the `ATTR2` in Step 2.

Using the following SQL statement, you can verify whether the advisor task is completed:

```
SELECT TASK_NAME, STATUS FROM DBA_ADVISOR_TASKS WHERE ADVISOR_NAME='SEGMENT
ADVISOR' AND TASK_NAME IN ('ANALYZE_TABLE_DATA');
```

5.2.9.2 Viewing Segment Advisor Advice

We recommend you configure daily job to run the advisor for selected objects in the non-peak hours and view the advisory recommendations. The advice will give an estimate about how much space can be reclaimable. Depending upon the estimate given by the segment advisor, you can decide whether to shrink table or not.

5.2.9.3 Shrinking Tables

Before you shrink a table, you need to enable row movement for the table using the following SQL statement:

```
ALTER TABLE SEG_TABLE ENABLE ROW MOVEMENT;
```

Then, you can shrink a table using the following SQL statement:

```
ALTER TABLE SEG_TABLE SHRINK SPACE COMPACT;
```

Appendix A : New Objects in the Oracle Revenue Management and Billing V3.1.0.0.0 Database

This section lists the objects that are newly added in the Oracle Revenue Management and Billing V3.1.0.0.0 database. These objects are classified under the following two sections:

- [Schema Changes](#)
- [New System Data](#)

A.1 Schema Changes

This section lists schema related changes made in the Oracle Revenue Management and Billing V3.1.0.0.0 database.

A.1.1 New Tables

The following tables are newly added in the Oracle Revenue Management and Billing V3.1.0.0.0 database:

Table	Description
C1_ACCOUNT_ANOMALY_DETECTED	Account Anomaly Detected
C1_BILL_ANOMALY_REQUEST	Bill Anomaly Request
C1_BILL_ANOMALY_REQUEST_K	Bill Anomaly Request Key
C1_BSEG_ANOMALY_DETECTED	BSEG Anomaly Detected
C1_BSEG_ANOMALY_REQUEST	Bill Segment Anomaly Request
C1_BSEG_ANOMALY_REQUEST_K	Bill Segment Anomaly Request Key
C1_BUS_RULE_RATE_GUARANTEE	Rate Guarantee Business Rule
C1_ENROLLED_PROD	Enrolled Product Retail
C1_GL_DL_DTL	GLDL Detail Table
C1_GL_DL_DTL_K	GL DL Detail Key
C1_GL_DL_HDR	GLDL Header Table
C1_GL_DL_HDR_K	GL DL Header Key
C1_PRODUCT_DTLS	Product Details
C1_PRODUCT_DTLS_CHAR	Product Details Characteristic
C1_PRODUCT_DTLS_DIV	Product Details Division
C1_PRODUCT_DTLS_ELIG	Product Details Eligibility
C1_PRODUCT_DTLS_ELIG_DTL	Product Details Eligibility Detail

Table	Description
C1_PRODUCT_DTLS_ELIG_L	Product Details Eligibility Language
C1_PRODUCT_DTLS_L	Product Details Language
C1_PRODUCT_DTLS_LINK	Product Details Link
C1_PRODUCT_DTLS_LOG	Product Details Log
C1_PRODUCT_DTLS_LOG_PARM	Product Details Log Parameter
C1_PRODUCT_DTLS_PLIST	Product Details Price List
C1_PRODUCT_DTLS_SVC	Product Details Service
C1_PRODUCT_SVC	Product Service
CI_ACCUM_SSL_MEMBER_DETAILS	Accumulation SSL Member Details
CI_MEMBERSHIP_RATE_GUARANTEE	Membership Rate Guarantee

A.1.2 Added Columns

The following columns are newly added in the Oracle Revenue Management and Billing V3.1.0.0.0 database:

Table	Column	Column Description	Required (Yes or No)
C1_BILL_LVL	IS_REFERRED_SW	Is Referred	No
C1_ENRL_ENTITY	ENROLL_END_BY_SYS_SW	Enroll End Date By System	Yes
	ENROLLMENT_ID	Enrollment ID	Yes
	ENTITY_CODE	Entity Code	Yes
	ENTITY_TYPE	Entity Type	Yes
	END_DT	End Date	No
	PRIORITY	Priority	Yes
	START_DT	Start Date	Yes
C1_EXTRACT_TEMPLATE	VERSION	Version	Yes
	AUDIT_LOG	Audit Log Required	Yes
	ERROR_LOG_SW	Error Log Required	Yes
C1_EXTRACT_TEMPLATE_FOR_MAT	FILE_LEVEL_FLG	File Level	Yes
	PAYLOAD_LOG_SW	Payload Log	Yes
	XML_NAMESPACE	XML Namespace	No
	FILE_NAME_FORMAT	File Name Format	No

Table	Column	Column Description	Required (Yes or No)
C1_EXTRACT_TEMPLATE_LIST_DTL	XML_NAMESPACE	XML Namespace	No
C1_EXTRACT_TEMPLATE_MAP_PING	RECORD_IDENTIFIER_SW	Record Identifier	Yes
	REQUIRED_SW	Required	No
C1_MODEL_PRICEITEM	PRICEITEM_PARM_GRP_ID	Price Item Parameters	Yes
C1_PRC_RULE_TYPE_PRICEITEM	RATEGRNT_SW	Rate Guarantee	No
	SPONSORED_SW	Sponsored	No
C1_PRODUCT	PROD_MNGR	Product Manager	No
	PROD_TYP_FLG	Product Type	No
	TC_TYPE_CD	Terms and Conditions	No
CI_APAY_CLR_STG	C1_RETRY_COUNT	Retry Counter	No
CI_APAY_STAGE_UP	LAST_EXTRACT_DT	Last Extract Date	No
CI_DATA_EX_REQ	FILENAME	File Name	Yes
CI_FT_GL	GL_DL_DTL_ID	GL Detail Id	No
CI_MEMBERSHIP_PER	CRE_DTTM	Create Date/Time	No
CI_POLICY	ADV_LF_ELIG_SW	Advance Level Funding Eligibility	No
CI_POLICY_PLAN_PRO_RULE	PRO_MEMB_TYPE_FLG	Membership Type	No
CI_PRCE_CALC	MEMO_SW	Memo Only, No GL	No
	NOWAVE_AMT	New Born Waiver Amount	No
	PRIMARY_PRICING_RULE_ID	Primary Pricing Rule ID	No
	RATE_GRNT_PRICING RULE_ID	Rate Guarantee Pricing Rule ID	No
CI_PRCE_CALC_LN	NEW_BORN_CMT_FLG	New Born Waiver Comment Flag	No
CI_REPRC_REQ_DTL	MEMO_SW	Memo Only, No GL	No
	PRIMARY_PRICING_RULE_ID	Primary Pricing Rule ID	No
	RATE_GRNT_PRICING RULE_ID	Rate Guarantee Pricing Rule ID	No

Table	Column	Column Description	Required (Yes or No)
CI_TRL_FT_GL	GL_DL_DTL_ID	GL Detail Id	No
CI_TXN_CALC_ACCUM_GRP	ACCT_ID	Account ID	No
CI_TXN_DTL_PRITM	BILL_LVL_ID	Bill Level ID	No
CI_TXN_DTL_PRITM_STG	BILL_LVL_ID	Bill Level ID	No

A.1.3 Dropped Tables

None

A.1.4 Dropped Columns

None

A.1.5 Added Views

None

A.1.6 Column Format Change

The format of the following columns is changed in the Oracle Revenue Management and Billing V3.1.0.0.0 database:

Table	Column	From	To
CI_TXN_REC_TYPE_L_UNPIVOT_VW	LANGUAGE_CD	VARCHAR2(3)	CHAR(3)

A.2 New System Data

The system data is used to configure various features in Oracle Revenue Management and Billing. This section lists the system data that is newly added in the Oracle Revenue Management and Billing V3.1.0.0.0 database.

A.2.1 Algorithm Types

The following algorithm types are newly added in the Oracle Revenue Management and Billing V3.1.0.0.0 database:

Algorithm Type	Description
C1_APAYUPDT	Update Account Autopay Details on Clearing Record
C1_FOPAGING	This Algorithm is created for FOP aging report.
C1_PRDPRC_PP	Retail Banking Effective Pricing
C1_ANMLYBILL	This algorithm inserts bill level details in anomaly request table
C1_ANMLYBSCN	Bill Segment Cancel -Anomaly Status Update

Algorithm Type	Description
C1-ANMLYBSDL	Bill Segment Delete - Anomaly Status Update
C1-ANMLYBSEG	This algorithm inserts bill segment details in anomaly request table
C1-APTDREML	Create Email for Debit Auto Pay Retry
C1-BUNDL-VAL	Bundle BO Validation for Retail Banking
C1-CUSTACCSA	Customer Account Contract Creation
C1-DISREINFO	Discrepancy Report Information
C1-ENRLCLSD	BO Transition to Closed Status for retail banking
C1-ENRLVAL	Retail Banking Enrollment BO Validation
C1-LATESET	Member Person Late Setup Notification
C1-MEMRTGRNT	Derive Rate Guarantee details for Individual membership.
C1-MP-VAL	Market Product BO Validation for Retail Banking
C1-NBORWAGE	Age Based New Born Waiver Calculation
C1-NWBORNTR	Tier Based New Born Waiver Calculation
C1-OFFER-VAL	Offer BO Validation for Retail Banking
C1-PDINFO	Market Product, Offer and Bundle Information
C1-PRDCT-VAL	Product BO Validation for Retail Banking
C1-PRDINFO	Product Information
C1-PRDPSPR	Product Post Processing
C1-PRDTLSRET	Transition Market Product, Offer and Bundle to Retired status
C1-PRD-TRN	Transition Product to Retired status
C1-RATEGRNT	Rate Guarantee Derivation for Individual Membership
C1-TFMERREML	Create Email for TFM Errors

A.2.2 Algorithms

The following algorithms are newly added in the Oracle Revenue Management and Billing V3.1.0.0.0 database:

Algorithm	Description
C1_APAYUPDT	Update Account Autopay Details on Clearing Record
C1_FOPAGING	This Algorithm is created for FOP aging report.
C1_PRDPRC_PP	Retail Banking Effective Pricing
C1-ANMLYBILL	This algorithm inserts bill level details in anomaly request table

Algorithm	Description
C1-ANMLYBSCN	This algorithm will mark the Anomaly Request Bill Segment record status to 'Cancelled' on Bill Segm
C1-ANMLYBSEG	This algorithm inserts bill segment details in anomaly request table
C1-APTDRETM	Create Email for Debit Auto Pay Retry
C1-BNDLINFO	Bundle Information
C1-BUNDL-VAL	Bundle BO Validation for Retail Banking
C1-CUSTACCSA	Algorithm to create person, account & contracts.
C1-DISREINFO	Discrepancy Report Information
C1-ENRLCLSD	BO Transition to Closed Status for Retail Banking
C1-ENRLVAL	Retail Banking Enrollment BO Validation
C1-LATESET	Member Person Late Setup Notification
C1-MEMRTGRNT	Derive Rate Guarantee details for Individual membership.
C1-MPINFO	Market Product Information
C1-MP-VAL	Market Product BO Validation for Retail Banking
C1-NBORWAGE	Age Based New Born Waiver Calculation
C1-NWBORNTR	Tier Based New Born Waiver Calculation
C1-OFFER-VAL	Offer BO Validation for Retail Banking
C1-OFFRINFO	Offer Information
C1-PRDCT-VAL	Product BO Validation for Retail Banking
C1-PRDINFO	Product Information
C1-PRDPSPR	Product Post Processing
C1-PRDTLSRET	Transition Market Product, Offer, Bundle to Retired status
C1-PRD-TRN	Transition Product to Retired status
C1-RATEGRNT	Rate Guarantee Derivation for Individual Membership
C1-TFMERREML	Create Email for TFM Errors

A.2.3 Business Services

The following business services are newly added in the Oracle Revenue Management and Billing V3.1.0.0.0 database:

Business Service	Description
C1_BUNDLEADDEDITSVC	Bundle Add Edit Service
C1_MARKETPRODUCT	Market Product Business Service

Business Service	Description
C1_OFFERADDEDITSVC	Offer Add Edit Service
C1_OFFERBUNDUSRVC	Offer and Bundle Service
C1_PRODUCT	Product Service to Add/ EDIT Products
C1_RateInfo	Rate Info
C1_SUBMSG SVC	Submit Button Information
C1-BINDERPAYBRBS	Retrieve Binder Payment Data Service
C1-BusRulRefValServ	Validate Referred Business Rule Id
C1-BusRulValAddEdit	Business Rule Value Add Edit Service
C1-BusRulValDelete	Business Rule Value Delete Service
C1-BusRulValParmSrch	Business Rule Value Parameter Fetch
C1-CheckMemberMovement	Check Member moved across Bill Groups
C1-DiscountChgPRDisp	Discount Charge price rule display
C1-GETBatchNbr	Get Batch Number from Batch Code
C1-GetHoldReqStEdDate	Get Hold Request Start and End Date
C1-GetMemTypeLookup	List of Membership Type Lookup
C1-GETPLDTL	Get pricelist detail
C1-GETPRODDIV	Product Division Service
C1-GETPRODSER	Get Prod SVC
C1-GETPRODSERV C	Get Prod SVC
C1-MIJobDetailsSearch	MI Job Details Search Service
C1-MIJobUpdate	MI Job Update Service
C1PRDCTENRL	Product Enrollment Retail Banking
C1PRODUCTSR	C1PRODUCTSRVC
C1-RetrieveBillCycle	List of Bill Cycle
C1-SSLCreditCalculationView	SSL Credit Calculation View
C1-STGRECORD	Retrieve Account AutoPay Staging Record
C1-TFMEMAILMSG	populate Email Message Content For TFM
C1-UpdHoldEntities	Update hold entities

A.2.4 Portals

The following portals are newly added in the Oracle Revenue Management and Billing V3.1.0.0.0 database:

Portal	Description
C1_DIV	Division check
C1BDLSC	Bundle Search
C1BUNDLE	Product Bundle
C1GLDLL	FT GL Drill Down Details
C1MPSRC	Market Product Search
C1MRP	Market Product
C1OFFER	Add New Promo Offer
C1OFRSRC	Offer Search
C1PDSRC	Market Product
C1PRDSRC	Product Search
C1PROM	Product Add/Edit

A.2.5 Batch Controls

The following batch controls are newly added in the Oracle Revenue Management and Billing V3.1.0.0.0 database:

Batch Control	Description
C1-APRCH	Maintain Additional Information for Staging Record and set t
C1-BLUPG	Transaction Upgrade - Stamp Bill Level ID
C1-CBIPR	Process Inactivated fully-insured Pricing Rule
C1-GATST	Gather stats procedure batch
C1-LSUB	Update create date for membership person
C1-MLDPR	Batch to prepare historical data for ML
C1-MLMCR	Batch to create ML model.
C1-MLPRE	Bill readiness ML prediction batch
C1-PDTLM	BO Monitor for Market Product,Offer,Bundle
C1-PDTRN	Transition for Market Product,Offer,Bundle
C1-PRDTR	Product Transition
C1-PREBV	Ready to Bill-Account Level Validation

Batch Control	Description
C1-UPDBL	Update Bill Level

A.2.6 Foreign Key References

The following foreign key references are newly added in the Oracle Revenue Management and Billing V3.1.0.0.0 database:

Foreign Key Reference	Description
C1-BLINF	Bundle Information
C1-MPINF	Market Product Information
C1-OFINF	Offer Information
C1-PDINF	Product Information

A.2.7 Scripts

The following scripts are newly added in the Oracle Revenue Management and Billing V3.1.0.0.0 database:

Script	Description
C1_CLRLNK	Clear id Navigation
C1_MPVAL	Market Product Search - At least one search criteria validation
C1_PDVAL	Offer and Bundle Search - At least one search criteria validation
C1_PRDVAL	Product Search - At least one search criteria validation
C1_ProdEdit	Product Edit
C1_ProdSub	Submit button Information
C1_REPCON	Condition Script for Reports Filter
C1-AddMrpd	Add Market Product .
C1-BILLANOML	UserFilter validation Script
C1-BRDefVal	Business Rule Definition Search Filter Validations
C1-BRulCrVal	Business Rule Criteria Filter Validations
C1-BRValDel	Business Rule Value Delete Action
C1-BRValEdit	Business Rule Value Edit Action
C1-BusRISrch	Search Business Rule
C1-BUSRULADD	Business Rule ADD UI Maintenance
C1-BUSRULEDT	Business Rule EDIT UI Maintenance
C1-BusRulSql	Business Rule Type Search - SQL condition

Script	Description
C1-DISADBCHG	Disaggregation For Billable Charge
C1-DISADDPER	Disaggregation For Person
C1-DISADPAID	Disaggregation For Price Assignment
C1-DISADPRIT	Disaggregation For Priceltem
C1-FTGLDrill	Zone Visibility - FT GL Drill Down Display Zone in Portal
C1-HldRqEdAI	Hold Request - Hold Edit All Actions
C1-loadFTId	Zone Visibility Script to populate FT
C1-PGPRSRCH	Search customer Zone
C1-PRDIMAGES	Return icon with label
C1-ShwIndMem	Zone Visibility - Display Zone for Individual Membership
C1-SSLCrDtVw	Display SSL Credits on Accumulation Data
C1-TFMERREML	Create Email For TFM Error Summary
C1-ValidFTGL	Validation Script for FTGL Drill Down Filter
C1-ValPMRole	Validation Script for Product Manager User Name

A.2.8 New Zones In Existing Portals

The following new zones are added to the existing portals in the Oracle Revenue Management and Billing V3.1.0.0.0 database:

Portal	Zone	Zone Description
C1ACUDAT	C1-SSLCRDTWV	SSL Credits Calculation Details
C1BUSRD	C1-BUSRULVAL	Business Rule Criteria
C1BUSRUL	C1-BRRULELOG	Business Rule Log
C1DRDIS	C1-DISREPORT	Discrepancy Report
C1MEMBSP	C1-MEMRTGRT	Membership Rate Guarantee
C1MMCPTB	C1-SPORDCHG	Sponsor Billable Charges
C1PLCYPN	C1-PLANPRO	Proration Rules
C1PRLCLM	C1-PRDCHG	Discount Charge Pricing Rule

A.2.9 Zones

The following zones are newly added in the Oracle Revenue Management and Billing V3.1.0.0.0 database:

Zone	Description
C1_BSRUL_SRC	Parameter Search
C1_BUNDMAINT	Product Bundle
C1_MRMAINT	Market Product
C1_OFFRMAINT	Add New Promo Offer
C1_ORABILCHG	Billable Charge OraSearch
C1_PGPRSERH	Product Group Details
C1_PRODMAINT	Product Maintenance
C1-BILLANM	Bill Anomaly Search
C1-BNDLSRCH	All Bundles
C1-BRRULELOG	Business Rule Log
C1-BRVALSRCH	Business Rule Criteria Parameters Search
C1-BSEGAMLY	Bill Segment Anomaly
C1-BSRULSRC	Business Rule Criteria Search
C1-BUNDLSRC	Bundle Search
C1-BUSRULRG	Rate Guarantee Rules
C1-DFVPRMVAL	Predefined Parameter Value Search
C1-DISREPORT	Discrepancy Report
C1-FTGLDLADJ	Adjustment Details
C1-FTGLDLBIL	Bill Segment Details
C1-FTGLLDLTL	Financial Transaction Details
C1-FTGLDLPAY	Payment Details
C1-FTGLDTLRB	FT GL Details
C1-FTGLDTLTB	Trial FT GL Details
C1-FTGLEXTDT	GL Extract File Details
C1-FTGLEXTTD	GL Extract File Details
C1-FTGLTRBIL	Bill Segment Details
C1-FTGLTRDTL	Financial Transaction Details
C1-GETBATCHN	Get Batch Number from Batch Code

Zone	Description
C1-GETMEMMOV	Check if member moved across Bill Groups
C1-GETMEMTYP	Fetch Membership Type Lookup
C1-HLDSTED	Business Rule Criteria Parameters Search
C1-HLTHPLN	Get Health Plan Details from Pricing Rule
C1-LATESETUP	Check Late Setup Configuration
C1-MEMRTGRT	Membership Rate Guarantee
C1-MKTPRD	All Market Products
C1-MKTPRDSRC	Market Product Search
C1-MLJOBDTL	Search ML Job Details
C1-MRPDSRCH	Search Market Product to Offer
C1-OFFERSRC	Offer Search
C1-OFFRSRH	All Offers
C1-ORAGETNBR	Batch Number Search
C1-ORASBATCH	Batch Control Search
C1-ORATRLNBR	Batch Number Search
C1-PLANPRO	Proration Rules
C1-PRDCHG	Discount Charge Pricing Rule
C1-PRDDTLS	All Products
C1-PRODDTLS	My Products
C1-PRODSERCH	Product Search
C1-PRSVCSER	Product Service Search
C1-PRTDDORLE	To Do Role Search
C1-REBILLCYC	Bill Cycle List Drop Down
C1-SPORDCHG	Sponsor Billable Charges
C1-SRCHPDMN	Search Product
C1-SRCHPROD	Search Product
C1-SSLCRDTVW	SSL Credits Calculation Details
C1-STGRECORD	Retrieve Account AutoPay Staging Record
C1-VIEWFTGL	Search GL Extract File

A.2.10 UI Maps

The following UI maps are newly added in the Oracle Revenue Management and Billing V3.1.0.0.0 database:

UI Map	Description
C1_BundleMaint	Bundle Maintenance Map
C1_BundleServiceFrag	Product Service Fragment
C1_BUS_RULE_SRCH	Business rule search
C1_FEEDTXNL3	Transaction Level information
C1_LEGEND_FRAG	Status legend Fragment
C1_MarketProdMaint	Add Market Product
C1_MarketProdTrain	Market Product Train
C1_OfferMaint	Offer Maintenance Map
C1_OffrBunServicesFrag	Offer and Bundle Service
C1_OJETLIB1010	Ojet 10.1.0 lib map
C1_PLM_LEGEND	Product Legend
C1_PRD_DTL	Product Details For Market Product
C1_ProdTrain	Product Train
C1_PRODUCT_AppTxn_Display	Display UI Map for PRODUCT Retail Banking
C1_PRODUCT_AppTxn_Input	Input UI Map for PRODUCT Retail Banking
C1_PRODUCT_AppTxn_ProductInput	Input Display for Retail Product Banking
C1_ProductAddMaint	Product Add Maintenance
C1_ProductServiceFrag	Product Service Fragment
C1_ResizePortalZone	Resize Portal zone
C1_ServiceTab	Offer and Bundle Service
C1-AddMrpdSrch	Search Market Products to Offer
C1-BinderPayAttributeData	Binder Payment Data Display
C1-BundleSrchFilter	Bundle Search Filter
C1-BusRuleValueMaint	Business Rule Criteria
C1-CheckServices	Check Services
C1-DISADDUIBCHG	Add Disaggregation Request For Billable Charge
C1-DISADDUIPAID	Add Disaggregation Request For Price Assignment

UI Map	Description
C1-DISADDUIPER	Add Disaggregation Request For Person
C1-DISADDUIPITM	Add Disaggregation Request For Price Item
C1-EligibilityRuleFrag	Eligibility Rule Fragment
C1-EligibilityRuleJsFrag	Java script for Eligibility rule
C1-FTGLDrillDLDisplayFlt	FT GL Drill Down Details- Filter
C1-FTGLDrillDLDisplayFltN	FT GL Drill Down Details- Filter
C1-FTGLDrillDLTrlDisplayFlt	FT GL Drill Down Details- Filter
C1-FTGLFTDisplayFitr	FT Details- Filter
C1-HoldRecordsEditAll	Edit all Records for Hold Request
C1-MarketProdPL	Market Product PriceList
C1-MarketProdPLFrag	Market Product PriceList
C1-MarketProdSvcFrag	Market Product Services
C1-MarketProductSrchFilter	Market Product Search Filter
C1-MarkProdCharsMaintFrag	Deal Type Char - Input UI
C1-MLJOBDTLS	ML Job Details
C1-OfferCharsMaintFrag	Offer Char Fragment
C1-OfferSrchFilter	Offer Search Filter
C1-OffrBundlePLFrag	Offer and Bundle PriceList
C1-PolicyPlanMembershipType	Populate Membership Type Field
C1-PricingRuleDisChargeDisp	Display UI for Discount Charge Pricing Rule
C1-ProdCharAddDeleteBtn	Characteristics Add/Delete Button
C1-ProdCharsMaintFrag	Product char Input Map
C1-ProductCharTypeInfo	Characteristic Type Information
C1-ProductDivFrag	Product Division Maintenance Fragment
C1-ProductSrchFilter	Product Search Filter
C1-ProductSrchFilter1	Product Search Filter
C1-ProrationRulesSrchFilter	Proration Rule Search
C1-RATEGUABSRUI	Rate Guarantee Business Rule
C1-RMInactiveCustomerUI	RM Inactive Customer Page
C1-SrchProdFilterMap	Search Product Filters

UI Map	Description
C1-SSLCreditCalculationView	View SSL Credit Calculation Details
C1-SubmitInfo	Submit Button Information
Z1_ProductAddMaint_dup	Product Add Maintenance

A.2.11 Lookups

The following lookups are newly added in the Oracle Revenue Management and Billing V3.1.0.0.0 database:

Field	Field Value	Description
ANOMALY_STATUS_FLG	IGNR	Ignore
	CLSD	Closed
	CNCL	Cancel
	OPEN	Open
BATCH_CD_ALLWD_FLG	BILL	BILLING
	BLPP	C1-BLPPR
	BSGR	BSGENREG
	BLGN	C1-BLGEN
	BOPN	BILLOPEN
	PPRC	POSTPROC
BUS_RULE_STATUS	ACTV	Active
	INAC	Inactive
ENRL_ACTION_FLAG	E	Edit
	A	Add
	C	Close
ENRL_STAT_FLAG	ACTV	Active
	INAC	Inactive
	CLSD	Closed
FILE_LEVEL_FLG	BOTH	Both Level File
	BATC	Batch Level File
	RECD	Record Level File
ML_ENTITY_TYPE	BILL	Bill
	ALL	ALL

Field	Field Value	Description
	BSEG	Bill Segment
ML_JOB_STATUS	COMP	Complete
	PEND	Pending
	IPRG	In Progress
	EROR	Error
ML_JOB_TYPE	MDBL	Model Build
	DTPR	Data Preparation
	PRED	Data Prediction
NEW_BORN_CMT_FLG	WOGD	Without Gift days
	REVL	Reversal
PRO_MEMB_TYPE_FLG	RETR	Retiree
	COBR	COBRA
	DEFL	Default
	MDCR	Medicare
PROD_TYP_FLG	PGRP	Product Group
	PROD	Product
PRODUCT_ENTITY_TYPE_FLG	HP	Health Plan
	OFFR	Offer
	BNDL	Bundle
	MP	Market Product
RATE_GRNT_STATUS_FLG	INAC	Inactive
	ACTV	Active
VALIDITY_FLG	BYDT	By Date
	INDS	In Days

A.2.12 Characteristic Types

The following characteristic types are newly added in the Oracle Revenue Management and Billing V3.1.0.0.0 database:

Characteristic Type	Description
C1-APMSG	Indicates retry counter has hit the set limits
C1-DLAVG	Deal Rate Comp to be set as avg price

Characteristic Type	Description
C1-MRWGD	Member Role Without New Born Gift Days
C1-NMBAT	Number of Re-attempts for Auto Debit Payment
C1-PERCT	Periodicity for Auto Debit on Division
C1-STWGD	Subscription Tier Without Gift Days
JRSDCTN	Jurisdiction
SPACTTYP	Sponsored Account Identifier Type
SPACTVAL	Sponsored Account Identifier Value

A.2.13 Feature Configurations

The following feature configurations are newly added in the Oracle Revenue Management and Billing V3.1.0.0.0 database:

Feature Configuration	Description
C1_CUSTINACT	Customer Inactivity Details
C1-PREBSEG	Before Bill segment Generation Validation

A.2.14 Zone Types

None

A.2.15 Business Objects

The following business objects are newly added in the Oracle Revenue Management and Billing V3.1.0.0.0 database:

Business Object	Description
C1_BUNDLE	Bundle
C1_MARKET_PRODUCT	Market Product
C1_OFFER	offer
C1_PRODENRLMENT_BO	Product Enrollment for Retail Banking
C1_PRODUCT	Product for Retail Banking
C1-DiscrepancyRep	Discrepancy Report
C1-GLDL	GLDL Drill Down
C1-PrcRuleTypeDisChg	Discount Charge Pricing Rule Type
C1-PricingRuleDiscount	Discount Charge Pricing Rule

A.2.16 Maintenance Objects

The following maintenance objects are newly added in the Oracle Revenue Management and Billing V3.1.0.0.0 database:

Maintenance Object	Description
C1_PRODDTLS	Product Details
C1-GLDL	GLDL Drill Down

A.2.17 To Do Types

The following To Do types are newly added in the Oracle Revenue Management and Billing V3.1.0.0.0 database:

To Do Type	Description
C1-APRET	Debit Autopay Retry
C1-BPCNA	Binder Payment Configuration Notification
C1-LSCN	Late Setup Notification
C1-PRDTD	Product To Do Type

A.2.18 Application Services

The following application services are newly added in the Oracle Revenue Management and Billing V3.1.0.0.0 database:

Application Service	Description
C1_DIV	Division check
C1_GLDL_SERV	GLDL Drill Down
C1_MARKETPRODUCT	Market Product Application Service
C1_OFFER	Offer Application Service
C1_PRODDTLS	Product Details
C1BDLSRC	Bundle Search
C1BUNDLE	Product Bundle
C1GLDLL	FT GL Drill Down Details
C1MPSRC	Market Product Search
C1MRP	Market Product
C1OFFER	Add New Promo Offer
C1OFRSRC	Offer Search

Application Service	Description
C1PDSRC	Market Product
C1PRDSRC	Product Search
C1PROM	Product Add/Edit

Appendix B : Application Services Configured for Default User Group

This section lists the application services configured for the default user groups shipped with Oracle Revenue Management and Billing Version 3.1.0.0.0.

B.1 ALL_SERVICES

The following table lists all application services configured for the ALL_SERVICES user group:

Application Service	Application Service	Application Service
AFHZONE	C1-CHGTYPSA	C1-EXTSTMLOGZ
APPTXADM	C1-CNTRTPPTZ	C1-EXTSTMTAD
C1-DEALAPPR	C1-CONTRACTCHARSVALI	C1-EXTSTMTCHAR
BILLGCONS	C1-CONTRACTTYPECHARS	C1-EXTSTMTED
BILLGRAPH	C1-CTCGSRV	C1-EXTSTMTITEM
C1-ACCBALCNT	C1-CTRLC	C1-EXTSTMTITMCHR
C1-ACCCRCHM	C1-DEFAULTPP	C1-EXTSTMTRC
C1-ACCCURDET	C1-DELPPTMP	C1-EXTSTMTSRZ
C1-ACCDTAILZ	C1-DFLTPPTMP	C1-EXTSTMTZ
C1-ACCDISCREZ	C1-DRRDTLSZ	C1-GETADJ
C1-ACCNBRTYPAS	C1-DUPBTN	C1-GETEFFECTVPRICING
C1-ACCOUNTCURRENT	C1-EDITPPTMP	C1-GETPPTMPL
C1-ACCQUICED	C1-EQUITYDT	C1-GETPRICING
C1-ACCREDIT	C1-EXITEMDEL	C1-INS-POLICY
C1-ACCRLOGZ	C1-EXITEMED	C1-INSDETBAK
C1-ACCSELECT	C1-EXSTMVBNF	C1-ISSUEDATEPOLICYCH
C1-ACCURERR	C1-EXTACQRYZ	C1-LINKPPTMP
C1-ACCURTEXT	C1-EXTAUTREC	C1-LINKPPTMP2
C1-ACNPOLSUMZ	C1-EXTERNALSTATEMENT	C1-MAINPINFR
C1-ACPOLSUMMZ	C1-EXTITEMAD	C1-MAINPPLAN
C1-ACTCATSRV	C1-EXTPENDG	C1-MAINPPTMP
C1-ACTPPTMPL	C1-EXTREOPN	C1-MEMBSP

Application Service	Application Service	Application Service
C1-ACURITEMD	C1-EXTSTCHM	C1-MOVEPPT
C1-ADJAPPRVLREQBOAS	C1-EXTSTIMP	C1-MSGTYPBASISBOAS
C1-APAYEXPCRREQBOAS	C1-EXTSTITCH	C1-NAVACTCUR
C1-APAYEXPCRTYPEBOAS	C1-EXTSTLDB	C1-NAVTOEXST
C1-APPTXN	C1-EXTSTMNF	C1-OUTAGE
C1-APPTXNLOG	C1-EXTSTMCAN	C1-PAY-REQ
C1-ASGNPL	C1-EXTSTMCLD	C1-PAYMENT
C1-BILLCHARGE	C1-EXTSTMCLS	C1-PAYPLAN
C1-BRD	C1-EXTSTMDTLZ	C1-PAYPLAND
C1-CASEGRPSRV	C1-EXTSTMDZ	C1-PAYPLANTMPLCOMPL
C1-PAYPLANZ	C1-PPDUP	C1-UNLINKPP
C1-PAYTEMPLATEBOAS	C1-PPEDIT	C1-UPLOADCSV
C1-PERBALCNT	C1-PPEDTTASK	C1-WRITEOFFREQ
C1-PIFVIS	C1-PPLANDET	C1ACCPOR
C1-PINFRDISP	C1-PPPDOC	C1ACCRATE
C1-PINVPOST	C1-PPSACCSRC	C1ACMACR
C1-POINFRDET	C1-PPTCNTDETZ	C1ACMACT
C1-POLCANCE	C1-PPTERROR	C1ACMARQ
C1-POLCANZ	C1-PPTMPDISP	C1ACTPER
C1-POLICY	C1-PPTMPDUP	C1ACTREE
C1-POLICYBPA	C1-PPTMPL	C1ADJSTP
C1-POLICYCANRSNSERV	C1-PPTMPLD	C1ADJUPL
C1-POLICYCHAR	C1-PPTMPLDET	C1AGING
C1-POLICYDESC	C1-PPTMPLDETZ	C1APPBOCHNZN
C1-POLICYINVOICEFREQ	C1-PPTMPLVIS	C1APPCHN
C1-POLICYPLAN	C1-PPTMPLZ	C1APPCRT
C1-POLYSUM	C1-PPTMPPOST	C1APPTXNBOCHN
C1-POLINVDETZ	C1-PRISIM	C1APPTXNBOCHNZN
C1-POLINVEDI	C1-PSTAKEHLD	C1APPTXNGRP
C1-POLINVFRE	C1-REFWOREQ	C1APROF

Application Service	Application Service	Application Service
C1-POLINVFREZ	C1-REQUEST	C1ACTIONFLAG
C1-POLINVFRQ	C1-REQUEST-TYPE	C1BNKREC
C1-POLI_FHZ	C1-RETURNDUP	C1BOCHN
C1-POLNOMINEZ	C1-REVRECSCHZ	C1CNTCR
C1-POLPERORLEAS	C1-RULEBOAS	C1COLDTL
C1-POLSUMZ	C1-SHDETAILSZ	C1COLTYP
C1-PPACCTSRC	C1-SRCHSCPT	C1CONSTRUCT
C1-PPACTV	C1-TXNAGG	C1CSEPOR
C1-PPBTNS	C1-TXNDTL	C1CTRLC
C1-PPDET	C1-HRCHYENTITY	C1DISAGR
C1-PPDETZ	C1-PRSPRODENRL	C1EXCHRT
C1-PPDISP	C1-UNLINK	C1FAAUD
C1_PROPL	C1POLSRCH	C1OFPRP
C1FLRQTY	C1POLSRH	C1_IM_EX
C1FLSRCH	C1POLTYP	PROSADD
C1FOAUD	C1PPCARS	PORTEST
C1HDRSR	C1PPLAN	C1ADDPRO
C1INSPAY	C1PPTMPL	C1VAR
C1MANAPP	C1PPTMPO	C1VARIANCE
C1MANLOG	C1PPVERSCHZ	C1VIEWRRL
C1MANMOD	C1PRICEL	C1WODET
C1MANRES	C1PRISIM	C1_ACCNBRALG
C1MEMBRS	C1PRODUCT	C1_ACCTCHAR
C1MEMBSP	C1PROFILESRVC	C1_ACCUR
C1MMTYPE	C1PSNAPP	C1_ACDTLSRCH
C1MTRADM	C1PSNMOD	C1_ACMM
C1NCISPY	C1PSNRES	C1_ACMS
C1NCPTMP	C1PTNDRH	C1_ADDEXH
C1ODBUPR	C1PTPLP	C1_ADDPL
C1PAYPLAN	C1PYRQTY	C1_ADDPROD

Application Service	Application Service	Application Service
C1PAYPTL	C1RECONDTL	C1_ADD_RTCMP
C1PAYREQ	C1REFSTP	C1_ADD_TIER
C1PAYRQ	C1REFUND	C1_ADMPI
C1PAYSRC	C1REQSTP	C1_ANSPLTCUS
C1PAYUPL	C1REQSTS	C1_APPAD
C1PERRL	C1REQTYP	C1_APPTXN_PRICEASGN
C1PLCYPL	C1RFWORT	C1_APPWF
C1PLCYPN	C1RLCHK	C1_APUR
C1PLCYTY	C1SAPPTM	C1_APVIG
C1POINFR	C1SATYPELISTZ	C1 ASNPL
C1POLCYN	C1SCHEDU	C1_AUDIT
C1POLCYP	C1SETTHR	C1_BACCGRVAL
C1POLICYCANRSN	C1SRCHRL	C1_BACCTDETL
C1POL SCH	C1TXNAGG	C1_BACCVALID
C1_BACTSRCHM	C1_CHKBIL_PA	C1_EXCHRT
C1_BAFHZ	C1_CHKTRDFLG	C1_EXHRT
C1_BCCSH	C1_CIAM	C1_EXPPITM
C1_BCONT	C1_CIGAS	C1_EXSTD
C1_BCON_INFO	C1_CIMAPZ	C1_EXSTL
C1_BCON_SRH	C1_CLACTSRCH	C1_EXSTM
C1_BCUSACCDT	C1_CLCSES RCH	C1_EXSTS
C1_BCUSACCSR	C1_CLCTR CNTR	DBMSFLJB
C1_BCUSGRVAL	C1_COLLN	C1_FILEHDRSR
C1_BCUSSRCHM	C1_COM_VALID	C1_FTRS
C1_BCUSTACDT	C1_COPYBND	C1_F_ACTSRCH
C1_BCUSVALID	C1_COPYPL	C1_F_ADDBNDT
C1_BFHIS	C1_CPBUNDL	C1_F_ADDCHLD
C1_BFH_SRH	C1_CPYBD	C1_F_ADDEXCH
C1_BNDMN	C1_CPYPL	C1_F_ADDMM
C1_BNDPRD	C1_CUSTINFO	C1_F_ADDMMSS

Application Service	Application Service	Application Service
C1_BNDPRS	C1_CUST_HR	C1_F_ADDPL
C1_BO_OPT	C1_DEL_PRD	C1_F_ADDPRBD
C1_BPAYHSRCH	C1_DEL_PROD	C1_F_ADDPRD
C1_BPH_INFO	C1_DISPBUND	C1_F_ADDPRPL
C1_BPYHS	C1_DIVPERREL	C1_F_ADDPRSS
C1_BRD_P	C1_DRRSR	C1_F_ADDRATE
C1_BSRCHOVRD	C1_DSPLY_RT	C1_F_ADMPROD
C1_BSRPT	C1_EDIT	C1_F_ADPROD
C1_BTGGLECA	C1_EDTBUND	C1_F_ADVAL
C1_BTREESRCH	C1_EDTER	C1_F_APVDTVL
C1_BTST	C1_EDTPL	C1_F_APVNFLT
C1_BUNDLE	C1_EDTPROD	C1_F_APVRJS
C1_BUNDVAL	C1_EDT_PRITM	C1_F_ASGNCUS
C1_BVCAC	C1_EFF_PRC	C1_F_ASGNPTP
C1_CASE_USR	C1_EFF_PRICE	C1_F_CHHSRCH
C1_CCC	C1_EFPRODSRC	C1_F_CIGG3V
C1_F_CLSRCH	C1_F_IGG1MM	C1_INF_PARTY
C1_F_CNCLMM	C1_F_IGG1MS	C1_INVCN
C1_F_CNCLMR	C1_F_IGG2MM	C1_INVSR
C1_F_CONTR	C1_F_IGG2MS	C1_LIST_TIER
C1_F_CON_VAL	C1_F_IGG3MM	C1_MEMBERS
C1_F_COPYPL	C1_F_IGG3MS	C1_MIG
C1_F_COPYSS	C1_F_PLCRT	C1_MIGAS
C1_F_CPYBNDL	C1_F_PLEDT	C1_MNG
C1_F_CPYPL	C1_F_PLVAL	C1_MNGRT
C1_F_CPYPLVL	C1_F_POPITEM	C1_MNGTR
C1_F_CUSSRCH	C1_F_PRCHAR	C1_MOD
C1_F_DELEXCH	C1_F_PRCHARS	C1_MPPA
C1_F_DELSCS	C1_F_PRDVL	C1_NAVIGATE
C1_F_DTVAL	C1_F_PRODVAL	C1_NAVUGATE

Application Service	Application Service	Application Service
C1_F_EDTBNDT	C1_F_PRODVL1	C1_NEXT_ACTION
C1_F_EDTEXHR	C1_F_RSCDVAL	C1_OVR_PRITM
C1_F_EDTMA	C1_F_RTDESC	C1_PAYUP
C1_F_EDTMMBS	C1_F_SAVESCS	C1_PERRL
C1_F_EDTMMMP	C1_F_SRPLVAL	C1_PLADPR
C1_F_EDTMMSS	C1_F_VAL_ACT	C1_PLAE
C1_F_EDTPPL	C1_F_VAL_ACTDTL	C1_PLASNADD
C1_F_EDTPR	C1_F_VAL_CHH	C1_PLASNEDIT
C1_F_EDTPROD	C1_F_VAL_CLDTL	C1_PLASN_ADD
C1_F_EDTPRPL	C1_F_VAL_CSTDTL	C1_PLASN_EDI
C1_F_EDTPRSS	C1_F_VAL_CUS	C1_PLASSIGN
C1_F_EXCDVAL	C1_GENERICSA	C1_PLASSIGNE
C1_F_EXCHVAL	C1_GENRCMP	C1_PLCLASSIGN
C1_F_EXHVAL	C1_GETTIER	C1_PLDISEDIT
C1_F_FH_VAL	C1_GRP	C1_PLEDIT
C1_F_FINHIS	C1_IGAI	C1_PLISTSRCH
C1_F_FINHIS1	C1_IGIMM	C1_PLMNG
C1_F_GENACBO	C1_IGMMB	C1_PLPTYAINF
C1_PLPTYINFO	C1_PROD_ADD	C1_TXNAR
C1_PLSRCH	C1_PROD_EDIT	C1_VWPRD
C1_PLSTOGGLE	C1_PROD_SAVE	CHGTYPE
C1_PLVAL	C1_PROD_SRCH	CHGTYPECD
C1_PLVALIDAT	C1_PROVR_EDT	CIACNBTY
C1_PLVIEW	C1_PRZCR	CIAPAYSTGUPL
C1_PL_ADD	C1_PRZTR	CIAPPACCTYPE
C1_PL_EDIT	C1_PRZ_CR	CIAPPCRIT
C1_PL_PI	C1_PRZ_TR	CIAPPTXNRSN
C1_PMPRC	C1_PTPLA	CICHGTYPE
C1_POLICYTYPE	C1_RATE_DEF	CICPAYPLAN
C1_PPEDT	C1_RECTIFYSRCH	CIDIVPERREL

Application Service	Application Service	Application Service
C1_PPOVR	C1_RLTPM	CFILEGRP
C1_PPOVRSRCH	C1_RLTVW	CIGETPRICING
C1_PP_DSPINF	C1_RSLV	CILAADUP
C1_PP_PLVAL	C1_RSN	CILAASCP
C1_PRCAD	C1_RTCOM_ADD	CILAAUSP
C1_PRCE_VALD	C1_RTC_VAL	CILACCDEL
C1_PRCPM	C1_RTOPT	CILACCUR
C1_PRC_EDIT	C1_SAVE_TIER	CILAACLCP
C1_PRC_OVRD	C1_SHOW_IMG	CILACTCT
C1_PRC_TR	C1_SRCH	CILBBICP
C1_PRC_VALID	C1_SRCHPL	CILBBLLP
C1_PRDPERREL	C1_SRCHPLVAL	CILBMCRP
C1_PRDREL	C1_SRCHPPL	CILBSBHP
C1CUSTPO	C1_SRCHPRD	CILBSCCP
C1DAPROF	C1_SRCH_PROF	CILBSEGP
C1_PRIPARMREFENT	C1_SRPROD	CILBSTMPP
C1_PRITSRCH	C1_STRTOLIST	CILCAAHP
C1_PROD	C1_TEMPLATE	CILCAASP
C1_PRODPL	C1_TIER_INP	CILCACCP
C1_PRODVAL	C1_TRLBL	CILCACMP
CILCACRP	CILCSCVP	CILIBDQP
CILCALZP	CILCSCZP	CILIBTVP
CILCAMRP	CILCSPZP	CILICOEP
CILCBCUP	CILCSSQP	CILINDDP
CILCBPGP	CILCSVAP	CILINPFP
CILCBRWP	CILCWOPP	CILINVVP
CILCCCIP	CILDATA	CILIPDQP
CILCCCZP	CILDIVET	CILIPRDP
CILCCIZP	CILDIVEXT	CILIRDQP
CILCCNSP	CILDRVWP	CILIRDSP

Application Service	Application Service	Application Service
CILCCNXP	CILECBLP	CILISATP
CILCCSCP	CILEFKRP	CILITDDP
CILCCSHP	CILEFLDP	CILITDQP
CILCCTXP	CILEMNUP	CILITMPP
CILCDCRP	CILEMOBP	CILITPDP
CILCENRP	CILENAVP	CILKTOSP
CILCFIZP	CILENVOP	CILLCARP
CILCLOAP	CILERPTP	CILLCAZP
CILCNBBP	CILESVCP	CILLCLPP
CILCPABP	CILETBBL	CILLODPP
CILCPASP	CILEUIZP	CILLWOPP
CILCPERP	CILFAFHP	CILMITMP
CILCPIZP	CILFBLCP	CILMITRP
CILCPLAS	CILFBPHP	CILMMRSP
CILCPMPP	CILFDRR	CILMMSUP
CILCPPPLP	CILFFNTP	CILMRBHP
CILCPPTMPL	CILFFTBP	CILMRTXP
CILCPREP	CILFFTTP	CILMSIHP
CILCPRMP	CILFMVTP	CILMSLIP
CILCQTEP	CILFSCAP	CILMSLOP
CILCSALP	CILFSFHP	CILMSMHP
CILCSCMP	CILGENACUR	CILMTRDP
CILOAPTP	CILQCASP	CILTASGP
CILODFAP	CILQTDCP	CILTATCP
CILOFACP	CILQTDEP	CILTATPP
CILOFAZP	CILQTDL	CILTATYP
CILOFORP	CILQTDQP	CILTBCRP
CILOFOSP	CILQTDSP	CILTBCTP
CILOFSUP	CILQTDTP	CILTBFFP
CILOOTGP	CILQTDZP	CILTBFP

Application Service	Application Service	Application Service
CILOSFAP	CILQTSSP	CILTBIMP
CILPAPHP	CILQTSUP	CILTBLCP
CILPAPSP	CILRCMAP	CILTBLPP
CILPARTY	CILRENGP	CILTBKNP
CILPDCNP	CILRRSMP	CILTBRTP
CILPDCSP	CILRRTCP	CILTBSTP
CILPEPLP	CILRRTSP	CILTBTCP
CILPEQAP	CILRRTVP	CILTBTRP
CILPEVTP	CILRRVMP	CILTBUDP
CILPIREL	CILRULE	CILTBXTP
CILPITXNREL	CILRULTP	CILTCAGP
CILPPAYP	CILSTEXT	CILTCAMP
CILPPCAN	CILSTEXTITEM	CILTCATP
CILPPTSP	CILTACRP	CILTCCCP
CILPQADP	CILTAGP	CILTCCNP
CILPRCITMREL	CILTALTP	CILTCCTP
CILPRICEASGN	CILTAMGP	CILTCETP
CILPRICECOMP	CILTAMTP	CILTCHTP
CILPRICMPTIER	CILTAPAP	CILTCIDP
CILPRIITEM	CILTAPFP	CILTCCLGP
CILPRLIST	C1DEALDB	CILTCLRP
CILPRLISTASGN	CILTAPSP	CILTCLWP
CILPTCNP	CILTAROP	CILTCNTP
CILQATDP	CILTARTP	CILTCOCP
CILTCPTP	CILTMHTP	CILTSCLP
CILTCQTP	CILTMMMTP	CILTSCYP
CILTCRUP	CILTMSGP	CILTSEVP
CILTCURP	CILTNBRP	CILTSICP
CILTCUSP	CILTNCDP	CILTSMIP
CILTDARP	CILNUXP	CILTSMTTP

Application Service	Application Service	Application Service
CILTDASP	CILTOCRP	CILTSOMP
CILTDCAP	CILTOETP	CILTSOPP
CILTDCLP	CILTOPTP	CILTSPPR
CILDIRP	CILTORAP	CILTSPTP
CILTDPRP	CILTPCRP	CILTSQIP
CILTDRTP	CILTPCTP	CILTSQRP
CILTDSTP	CILTPDRP	CILTSTMP
CILTDWPP	CILTPHTP	CILTSTSP
CILTDWTP	CILPIFF	CILTSVTP
CILTEBRP	CILTPKGP	CILTSWLP
CILTECRP	CILPPPTP	CILTTACP
CILTEETP	CILTPROP	CILTTAXP
CILTFNDP	CILTPRTP	CILTTGRP
CILTFREP	CILTPSDP	CILTTMRP
CILTFRQP	CILTPSTP	CILTTMTP
CILTGLDP	CILPTRTP	CILTTNSP
CILTGOTP	CILPYTP	CILTTNTP
CILTIIDTP	CILTQRTP	CILTOUP
CILTINCP	CILTRREGP	CILTTSCP
CILTINSP	CILTRREPP	CILTTTMRP
CILTITSP	CILTRGLP	CILTZNP
CILTLIDIP	CILTRLEP	CILTUOMP
CILTLETP	CILTRSCP	CILTURPP
CILTLKFP	CILTRRTYP	CILTUSCP
CILTLNGP	CILTSARP	CILTUSEP
CILTMCRP	CILTSATP	CILTUSGP
CILTWCTP	CILZFNCP	CTXZONE
CILTWDCP	CILZPORP	DEMO
CILTWETP	CILZRBPP	DISAGGP
CILTWFPP	CILZRPHP	DIV_PRICEITEMS

Application Service	Application Service	Application Service
CILTWPTP	CILZRPOP	DIV_PRICELISTS
CILTWSCP	CILZRPTP	F1-APAYEXPCRTYPEBOAS
CILTWSDP	CILZSCMP	F1-ATTACHMENTBOAS
CILTXNCD	CILZSCR	F1-BKTCONFIG
CILTXNCDL	CILZSCZP	F1-BOOKMARKS
CILTXNSRC	CILZTLZP	F1-DECRPTBOAS
CILTXNSRCL	CILZZOHP	F1-DFLTAPS
CILUPFTS	CILZZONP	F1-DFLTS
CILVFVDP	CIL_FAVORITES	F1-EXPUSERSREQBOAS
CILVFVSP	CIPOLICY	F1-GENPROC
CILVVLEP	CIPOLPERRL	F1-MIGROBJIMP
CILVVLSP	CIPOLPERROLE	F1-OBJREVBOAS
CILWDWNP	CIPRICEACCOUNT	F1-STASKTYPE
CILWJSDP	CIPRICEPARM	F1-SVCTASK
CILWJSSP	CIPYSRCH	F1-SYNCREQ
CILWNUPP	CIRATEUPLD	F1-SYNCREQIN
CILWNUSP	CIRECON	F1-SYNCREQUESTBOAS
CILWPROP	CIRECONDTL	F1-WEBSVCBOAS
CILXNDNP	CIS_DIV_ALGS	F1ADMIN
CILXOPTP	CIS_DIV_BICES	F1ANN
CILXSENP	CIS_DIV_CST_LNGS	F1ANNTPM
CILYASTP	CIS_DIV_ID_TYPES	F1ANNTPS
CILYDBPP	CIS_DIV_INV_CURS	F1ANNTYP
CILYDFQP	CIS_DIV_TXN_SRCS	F1APPSEC
CILYDPIP	CIS_DIV_VLD_CTIES	F1ATTACH
CILYROBP	CIVARIANCE	F1ATTACHMENT
CILZAFQP	CMAGING	F1BKTCFG
CILZAUQP	CNCLRSN	F1BKTCFQ
F1BNDLEM	F1MIGRDIMP	FWLBNLDP
F1BNDLES	F1MIGRDS	FWLCTDEP

Application Service	Application Service	Application Service
F1BNDLIM	F1MIGROBJ	FWLFACTP
F1BNDLIS	F1MIGRPLAN	FWLSTRJP
F1BUNEXP	F1MIGRREQ	FWLTBELP
F1BUNIMP	F1MIGRTIMP	FWLTBOJP
F1CATTCH	F1MIGRTX	FWLTBSVP
F1CONFIGLOG	F1MSTCFG	FWLTDARP
F1DEBUG	F1MTXIMP	FWLTEXSP
F1EXLKP	F1OBJREV	FWLTMGCT
F1EXLKPS	F1OBJREVCTL	FWLTOMTP
F1HEALTH	F1OBJRVH	FWLTSCHP
F1HGMAPPING	F1REQ	FWLTUIMP
F1IWSANM	F1REQTYP	FWLXOUTP
F1IWSDPL	F1REVHST	FWLZDEXP
F1IWSSVC	F1STRDIS	FWLZWLP
F1IWSVCP	F1STREAS	GOTOREC
F1IWSVCS	F1SUBRQQ	PERTREE
F1LCAMRP	F1SYNCRM	POLICYCANRSN
F1LEXTLKUP	F1SYNCRQ	RECDTSTA
F1LTAMTP	F1TBLEXC	RECON
F1MESSAGE	F1UIZONE	RECONDTL
F1MGDEXP	F1USERLOG	SACHGLNK
F1MGDEXS	F1USRCHKOUT	SATYPCHG
F1MGDIMP	F1USRPTL	SATYPES
F1MGDIMS	F1WBSVCM	F1_USRSCR
F1MGOIMP	F1WBSVCS	FILETYPE
F1MGPLNM	F1WEBSVC	F1MGREQS
F1MGPLNS	F1_BTST	F1MIGRDEXP
F1MGREQM	F1_USRFAVSCH	C1PLASGNM
C1-USRLOGINDTLS	C1DEALPASGN	C1REFUPLREQ
C1BCHGUPLREQ	C1GETELIGPT	C1UPLDRQ

Application Service	Application Service	Application Service
C1BILLCYCLEUPDTUPL	C1GLAT	C1UPLREQ
C1CONTRIDERUPDTUPL	C1GLATEMP	C1WOUPLREQ
C1DCDTLC	C1GLATRQ	C1_STDTL
C1DELCTL	C1HOLDUPLREQ	C1_STRTE
C1ELGPA	C1LASGN	C1_STRTY
DBMSJOB	C1PIASGN	CISTMEXCP_SERV
C1DEALSVC	ACRLSRCH	C1-ACCTECR
C1-CUSTINMSG	C1ADDRS	C1HCAPPSER
C1-DEALPRICING	C1ADDRSBO	C1HCBLDT
C1-FTDIST	C1ADDRSDP	C1HCSINF
C1-FTDISTRULE	C1ADDRSRC	C1INMSGP
C1-FTDISTTY	C1BK360	C1INMSRH
C1-GENRQ	C1BKAPPSEN	C1INMSTY
C1-INMSG	C1BKBLDT	C1PAREQ
C1-INMSGTYPE	C1BKSINF	C1PARQMN
C1-MEMBERINMSG	C1CUS360	C1PARQTY
C1-PROSPECTCRET	C1DSPT	C1PAYMAN
C1ACCECR	C1DSPTRQ	C1PI
C1ACRLCL	C1DSPTRT	C1PL
C1ACRLTP	C1DSPTTY	C1POLPEL
C1ACRMVW	C1FTDIST	C1REINUPLREQ
C1ADDRDP	C1FTDSRL	C1_ACCRTYPE
C1ADDRDTL	C1FTDSTT	C1_ACCRUAL_SERV
C1ADDRESS	C1FTDSTY	C1_ACTVW
C1_ACTYP	C1_DSPT_REQ	ILM_ARC
C1_ACYVW	C1_TRLIN	ACCTVIEW
C1-ACCTAPAY_SERV	C1-DISC-REPT	C1-DRRTMPLT
C1-MBR-DR-TY	C1-PRC_CALC_SM	C1-PTD-CAL
C1-RETRIEVPROSRV	C1-REVRECPLCY	C1-RN-TY
C1-SCHEDULERMONITOR	C1-SCHPGMQZ	C1-SCHSCHQZ

Application Service	Application Service	Application Service
C1ACCTAPAY	C1APAYRT	C1APAYVW
C1APYINS	C1AWFCHN	C1AWFCRT
C1AWFGRP	C1AWFRSN	C1AWFSET
C1CONADD	C1DISREP	C1DRDIS
C1DSRTY	C1MBRRCN	C1PARAM
C1PDSRCH	C1PERS	C1PERSDP
C1PERSON	C1PRDSVC	C1PRODDP
C1PRODUCTSERVICE	C1PVERDP	C1RCONTY
C1RECOLN	C1RECONCIL	C1RECONTYP
C1REPORT	C1RPTTMP	C1SCHCHN
C1SCHJOB	C1SCHPGM	C1SCHSCH
C1SCJMON	C1SRCAPP	C1SVCDSP
C1VIEPRI	PRICECOMPPRE	C1_BOCHN
C1_CONSTRUCT	C1_DRRESP	C1_DRRTM
C1_DR RTP	C1_ENLOG	C1_ENROL
C1_ENROLLMENT	C1_ENSCH	C1_PAYIN
C1_PRODUCT	C1_PRODUCT_SERVICE	C1_PRODVER
C1_SRCBUSSPRD	C1_SRCTECHPRD	CIAPPCHELGLB
CICONACT	CONRULE	CONSTRUCT
DDPRCSM	ACCT_SUBSCRPTN_SERV	C1-PRCRULE
C1-PRC_CALC_SM	C1-PRRLTYP	C1-SUBSCRTYPE
C1BILLSORT	C1BLLVLUPLREQ	C1BLLSRTUPLREQ
C1ENTITYREPORT	DBMSRNJB	C1-DLDBACTNS
C1PRICINGGROUP	C1PROAPP	C1PRTYP
C1REPORTTTP	C1RPTAUD	C1RPTDEF
C1SUBSTP	C1SUBTVW	C1-DLAPPRTOD
C1-ACCUDATA	C1-CUSTREGTEMPL_SERV	C1-CUSTREGTYPE
C1-GETPRICINGENTITY	C1-PICINGRULE	C1-PRICEASGNTREE
C1ACUDAT	C1CREGSR	C1CTRGBT
C1CTRGC	C1FILEMS	C1MASPRI

Application Service	Application Service	Application Service
C1MPRIRQ	C1MPRISR	C1RETMPL
C1DLAPDB	CIDATAEXSER	DTEX_TYP
PRICECOMPSEQ	C1CUREG	C1CURETY
C1CUSTREG	C1CUSTRG	C1DTEXFL
AUDITEVENT	C1-AUDEVTYPE	C1-BANKING
C1-HEALTHCARE	C1-PRICETREE	C1-STATE
C1ADEVSR	C1AUDEVT	C1AUDTY
C1OFFADJ	C1RETMPLBK	C1RETMPLHC
C1STATE	C1VIPRIN	C1_BILL
CILCSSEP	C1DELTYP	C1-OFFPRO
C1DTSERH	C1ENHR	C1ENHRSR
C1ENTDTL	C1-DLTODOLST	TSTPRICE
C1GETELIGPRO	C1HIERARCHY	C1HRCHYENTITY
C1HRYENT	C1INREQ	C1INRETY
C1INVRED	C1PATCH	C1PISL
GETDEALTYPE	C1PROSPO	C1PRSEAR
C1PRSSASP	C1REFPRI	C1SERDSC
C1SFTPUTS	C1SLFSER	C1TPSTRT
C1TRBLHC	C1TCND	C1_PROSPECT
C1-DEALAPPRWF	C1GETELIGPLPRO	C1_HLTH_PLAN
C1_ALRPT	C1_CHREF	C1_CONSTRUCT
C1_CREF	C1 DEAL	C1_DEALFETCHRATE
CM_TEST	C1_HEVD	C1_PDEAL
CMPER1	PRTTST	C1_PRSENROLLMENT
C1_REF	C1GETELIGPROD	CMPERTESTASE
TESTPORT	CUSPRCDT	DBMSSCHD
DWNLFILE	C1OFPREQ	C1OFPRED
PORTPRAC	PORTT	PRODSTAT
CANCPAYM	PRICEITEM_SERV	C1-BENEFITS
C1-BENFITPKG	C1-DEALRVW	C1-EXTCTTEMP

Application Service	Application Service	Application Service
C1-EXTRACTTEMPLATE	C1-FIELDMAP	C1-FIELDMAP_SERV
C1-GETFIPRCRULE	C1-TNC	C1BENFTP
C1BENFTS	C1DEAL1	C1DLPRT
C1DLTMPT	C1EXTCTTEMP	C1EXTTMP
C1FLDMAP	C1GEORTA	C1GEORTAR
C1_QUESN	C1IACUDT	C1PLSIM
C1PLSM	C1PLSMPL	C1PLSMVW
C1PRICELISTSIM	C1QUESRH	C1QUESTION
C1QUEVIEW	C1RELSTR	C1RMACCSTAT
C1RMACCTSTAT	C1RMWRKB	C1RVTRND
C1STPDL	C1TCMAP	C1TERCO
C1TERMNCO	C1TNCSRH	C1UNPINV
C1_DEAL_MAPPINGS	C1 DEAL PRICELIST	C1 DEAL TEMPLATE
C1_F_POLSRCH	C1 MEMRL SUBT	C1_RTSC
C1-BUSRULE	C1-BUSRULVAL	C1AWRSNP
C1BENSTY	C1BUSRD	C1BUSRUL
C1CONTDL	C1_HCPRODUCT	C1DIAGCE
C1MEIDTY	C1_DIV	C1_GLDL_SERV
C1_MARKETPRODUCT	C1_OFFER	C1_PRODDTLS
C1BDLSRC	C1BUNDLE	C1GLDLL
C1MPSRC	C1MRP	C1OFFER
C1OFRSRC	C1PDSRC	C1PRDSRC
C1PROM	-	-

B.2 C1_BSERCIES

The following table lists all application services configured for the C1_BSERCIES user group:

Application Service	Application Service	Application Service
AFHZONE	C1-PIFVIS	C1AGING
APPTXADM	C1-PINFRDISP	C1APPBOCHNZN
ARUNTEST	C1-PINVPOST	C1APPCHN
BILLGCONS	C1-POINFRDET	C1APPCRT
BILLGRAPH	C1-POLICY	C1APPRESP
C1-ACCBALCNT	C1-POLICYINVOICEFREQ	C1APPTXNBOCHN
C1-ACCNBRTYPAS	C1-POLINVDETZ	C1APPTXNBOCHNZN
C1-ADJAPPRVLREQBOAS	C1-POLINVRE	C1APPTXNCHAIN
C1-APAYEXPCRREQBOAS	C1-POLINVREZ	C1APPTXNCRI
C1-APAYEXPCRTYPEBOAS	C1-POLINVFRQ	C1APPTXNCRT
C1-APAY_STG_UP	C1-PRISIM	C1APPTXNGRP
C1-APPRSN	C1-REFWOREQ	C1APROF
C1-APPTXN	C1-REGENUI	ACCMULID
C1-APPTXNLOG	C1-REQUEST	C1BNKREC
C1-ASAPU	C1-REQUEST-TYPE	C1BOCHN
C1-ASGNPL	C1-RULEBOAS	C1CASEG
C1-BRD	C1-SRCHSCPT	C1CASETYPEEMP
C1-CASEASGNSRV	C1-TXNAGG	C1CHECKFT
C1-CASEGRPSRV	C1-TXNDTL	C1COLDTL
C1-CONSVPROGBOAS	C1PMTP	C1COLLTYP
C1-CONTRACTTYPECHARS	C1_CHREF	C1COLTYP
C1-CTCGSRV	C1-WRITEOFFREQ	C1CROG
C1-GETEFFECTVPRICING	C1ACC RATE	C1CSTYSR
C1-GETPRICING	C1ACMACT	C1DISAGR
C1-MAINPINFR	C1ACTCAT	C1EXCHRT
C1-OUTAGE	C1ACTPER	ACTNOCON
C1-PAY-REQ	C1ACTREE	C1FLRQTY
C1-PAYTEMPLATEBOAS	C1ACTYRSTY	C1FLSRCH

Application Service	Application Service	Application Service
C1-PERBALCNT	C1ADJSTP	C1IRSPP
C1-PERIDSER	C1ADJUPL	C1MANAPP
C1MANLOG	C1REQTYP	C1_ANSPLTCUS
C1MANMOD	C1RFWORT	C1_APACS
C1MANRES	C1RLCHK	C1_APPAD
C1NCISPY	C1RSTCAT	C1_APPTXN_PRICEASGN
C1NCPTMP	C1SACCOLLECT	F1-BOOKMARKS
C1ODBUPR	C1SACTHI	C1_APUR
C1PASGAPPROVE	C1SCHEDU	C1_APVIG
C1PASGREADMODIFY	C1SCHTMP	C1 ASNPL
C1PASGREADRESOLVE	C1SETTHR	C1_AUDIT
C1PAYMAN	C1SRCHRL	C1_BACCGRVAL
C1PAYPTL	C1TXNAGG	C1_BACCTDETL
C1PAYREQ	ADJDETAI	C1_BACCVALID
C1PAYRQ	USGSETT	C1_BACTSRCHM
C1PAYSRC	C1TXNFD	C1_BAFH
C1PAYUPL	USGMISIN	C1_BAFHZ
C1POINFR	USGMIS	C1_BCCSH
C1PPCARS	C1UNAPPR	C1_BCONT
C1PRESTGDTLS	C1VAR	C1_BCON_INFO
C1PRISIM	C1VIEWRDL	C1_BCON_SRH
C1PRODUCT	C1WODET	C1_BCUSACCDT
C1PROFILESRVC	C1_ACCNBRALG	C1_BCUSACCSR
C1PSNAPP	C1_ACCNBRTYP	C1_BCUSGRVAL
C1PSNMOD	C1_ACCTCHAR	C1_BCUSSRCHM
C1PSNRES	C1_ACDTLSRCH	C1_BCUSTACDT
C1PTNDRH	C1_ACMM	C1_BCUSVALID
C1PTPLP	C1_ACMS	C1_BDTLSRCHM
C1PYRQTY	C1_ADDEXH	C1_BFHIS
C1REFSTP	C1_ADDPL	C1_BFH_SRH
C1REFUND	C1_ADDPROD	C1_BNDMN

Application Service	Application Service	Application Service
C1REQSTP	C1_ADD_RTCMP	C1_BNDPRD
C1REQSTS	C1_ADD_TIER	C1_BNDPRS
C1REQTYP	C1_ADMPI	C1_F_ADVAL
C1_BO_OPT	C1_DIVPERREL	C1_F_APVDTVL
C1_BPAYHSRCH	C1_DSPLY_RT	C1_F_APVNFLT
C1_BPH_INFO	C1_EDIT	C1_F_APVRJS
C1_BPYHS	C1_EDTBDB	C1_F_ASNCUS
C1_BRD_P	C1_EDTBUND	C1_F_ASGNPTP
C1_BSRCHOVRD	C1_EDTER	C1_F_CHHSRCH
C1_BSRPT	C1_EDTPL	C1_F_CIGG3V
C1_BTOWGLECA	C1_EDTPROD	C1_F_CNCLMM
C1_BTREESRCH	C1_EDT_PRITM	C1_F_CNCLMR
C1_BTST	C1_EFF_PRC	C1_F_CONTR
C1_BUNDLE	C1_EFF_PRICE	C1_F_CON_VAL
C1_BUNDVAL	C1_EFPRODSRC	C1_F_COPYPL
C1_BVCAC	C1_EXCHRT	C1_F_COPYSS
C1_CHKBL_PA	C1_EXHRT	C1_F_CPYBNDL
C1_CHKTRDFLG	C1_EXPPITM	C1_F_CPYPL
C1_CIAM	C1_DEALFETCHRATE	C1_F_CPYPLVL
C1_CIGAS	C1_FTRS	C1_F_CUSSRCH
C1_COLLN	C1_F_ACTSRCH	C1_F_DELEXCH
C1_COLL_NZN	C1_F_ADDBNDT	C1_F_DELSCS
C1_COM_VALID	C1_F_ADDCHLD	C1_F_DVAL
C1_COPYBND	C1_F_ADDEXCH	C1_F_EDTBNDT
C1_COPYPL	C1_F_ADDMM	C1_F_EDTEXHR
C1_CPBUNDL	C1_F_ADDMMSS	C1_F_EDTMA
C1_CPYBD	C1_F_ADDPL	C1_F_EDTMMBS
C1_CPYPL	C1_F_ADDPRBD	C1_F_EDTMMMP
C1_CUSTINFO	C1_F_ADDPRD	C1_F_EDTMMSS
C1_CUST_HR	C1_F_ADDPRPL	C1_F_EDTPL
C1_DEGREE	C1_F_ADDPRSS	C1_F_EDTPR

Application Service	Application Service	Application Service
C1_DEL_PRD	C1_F_ADDRATE	C1_F_EDTPROD
C1_DEL_PROD	C1_F ADMPROD	C1_F_EDTPRPL
C1_DISPBU ND	C1_F_ADPROD	C1_PLASSIGNE
C1_F_EDTPRSS	C1_GENRCMP	C1_PLCLASSIGN
C1_F_EXCDVAL	C1_GETTIER	C1_PLDISEDIT
C1_F_EXCHVAL	C1_GRP	C1_PLEDIT
C1_F_EXHVAL	C1_IGAI	C1_PLISTSRCH
C1_F_FH_VAL	C1_IGIMM	C1_PLMNG
C1_F_FINHIS	C1_IGMMB	C1_PLPTYAINF
C1_F_FINHIS1	C1_INF_PARTY	C1_PLPTYINFO
C1_F_GENACBO	C1_INVCN	C1_PLSRCH
C1_F_IGG1MM	C1_INVSR	C1_PLSTOGGLE
C1_F_IGG1MS	C1_LIST_TIER	C1_PLVAL
C1_F_IGG2MM	C1_MEMBERS	C1_PLVALIDAT
C1_F_IGG2MS	C1_MIG	C1_PLVIEW
C1_F_IGG3MM	C1_MIGAS	C1_PL_ADD
C1_F_IGG3MS	C1_MNG	C1_PL_EDIT
C1_F_PLCRT	C1_MNGRT	C1_PL_PI
C1_F_PLEDT	C1_MNGTR	C1_PMPRC
C1_F_PLVAL	C1_MOD	C1_PPEDT
C1_F_POPITEM	C1_MPPA	C1_PPOVR
C1_F_PRCHAR	C1_NAVIGATE	C1_PPOVRSRCH
C1_F_PRCHARS	C1_NAVUGATE	C1_PP_DSPINF
C1_F_PRDVL	C1_OVR_PRITM	C1_PP_PLVAL
C1_F_PRODVAL	C1_PAYUP	C1_PRCAD
C1_F_PRODVL1	C1_PAY_BTN	C1_PRCE_VALID
C1_F_RSCDVAL	C1_PERRL	C1_PRCPM
C1_F_RTDESC	C1_PLADPR	C1_PRC_EDIT
C1_F_SAVESCS	C1_PLAE	C1_PRC_OVRD
C1_F_SRPLVAL	C1_PLASNADD	C1_PRC_TR
C1_F_VAL_ACT	C1_PLASNEDIT	C1_PRC_VALID

Application Service	Application Service	Application Service
C1_F_VAL_ACTDTL	C1_PLASN_ADD	C1_PRDPERREL
C1_F_VAL_CHH	C1_PLASN_EDI	C1_PRDREL
C1_F_VAL_CUS	C1_PLASSIGN	CILACTTY
GETDEALTYPE	C1_SRCHPLVAL	CILBBICP
C1_PROSPECT	C1_SRCHPPL	CILBBLLP
C1_PRITSRCH	C1_SRCHPRD	CILBSBHP
C1_PROD	C1_SRCH_PROF	CILBSCCP
C1_PRODPL	C1_SRCH_TEMP	CILBSEGP
C1_PRODVAL	C1_SRPROD	CILBSTMPP
C1_PROD_ADD	C1_STRTOLIST	CILCAASP
C1_PROD_EDIT	C1_TEMPLATE	CILCACCP
C1_PROD_SAVE	C1_TIER_INP	CILCACMP
C1_PROD_SRCH	C1_TRLBL	CILCALZP
C1_PROVR_EDT	C1_TXNAR	CILCAMRP
C1_PRZCR	C1_VWPRD	CILCASEEXTN
C1_PRZTR	CIACNBTY	CILCBCUP
C1_PRZ_CR	CIACTTYP	CILCBRWP
C1_PRZ_TR	CIAPAYSTGUBL	CILCCCIP
C1_PTPLA	CIAPPACCTYPE	CILCCCZP
C1_PYHST	CIAPPACTYPE	CILCCIZP
C1_RATE_DEF	CIAPPCHELGBL	CILCCNSP
C1_RECTIFYSRCH	CIAPPCRIT	CILCCNXP
C1_RLTPM	CIAPPTXNCHAIN	CILCCSCP
C1_RLTVW	CIAPPTXNRSN	CILCCSHP
C1_RSLV	CIDIVPERREL	CILCCTXP
C1_RSN	CIDIVPRITMPERREL	CILCENRP
C1_RTCOM_ADD	CFILEGRP	CILCFIZP
C1_RTC_VAL	CIGETPRICING	CILCONPREF
C1_RTOPT	CILAADUP	CILCPERP
C1_RTSC	CILAASCP	CILCPLAS
C1_SAVE_TIER	CILAAUSP	CILCPPLP

Application Service	Application Service	Application Service
C1_SHOW_IMG	CILACLCP	CILCPRMP
C1_SRCH	CILACTCT	CILCQTEP
C1_SRCHPL	CILACTHI	CILQATDP
CILCSALP	CILICOEP	CILQCASP
CILCSESA	CILITDDP	CILQTDEP
CILCSSEP	CILITDQP	CILQTDLP
CILCSVAP	CILITPDP	CILQTDQP
CILDATA	CILLCAZP	CILQTDSP
CILDIVET	CILLODPP	CILQTDTP
CILDIVEXT	CILMRBHP	CILQTDZP
CILDRVWP	CILPAPHP	CILQTSSP
CILECBLP	CILPAPSP	CILQTSUP
CILEFKRP	CILPARTY	CILRCMAP
CILEFLDP	CILPDCNP	CILRENGP
CILEMNUP	CILPDCSP	CILRRSMP
CILEMOBP	CILPEPLP	CILRRTCP
CILEMPDTLS	CILPEQAP	CILRRTSP
CILENAVP	CILPEVTP	CILRRTVP
CILENVOP	CILPICCHAR	CILRRVMP
CILERPTP	CILPIDIV	CILRSCAT
CILESVCP	CILPILANG	CILRSTTY
CILETBBLP	CILPIREL	CILRULE
CILEUIZP	CILPITXNREL	CILRULTP
CILEXCHRATE	CILPPAYP	CILSCHEDULE
CILFAFHP	CILPPCAN	CILTACRP
CILFBLCP	CILPPTSP	CILTALGP
CILFFEXP	CILPQADP	CILTALTP
CILFFNTP	CILPRCITMREL	CILTAMGP
CILFFTBP	CILPRICELISTCHAR	CILTAMTP
CILFFTTP	CILPRITEM	CILTAPAP
CILFLGRP	CILPRLIST	CILTAPFP

Application Service	Application Service	Application Service
CILFMVTP	CILPRLISTDIV	CILTAPRP
CILFSFHP	CILPRLISTL	CILTAPSP
CILIBTVP	CILPTCNP	CILTLNGP
CILTAROP	CILTCPRP	CILTMCRP
CILTARTP	CILTCQTP	CILTMHTP
CILTASGP	CILTCRUP	CILTMSGP
CILTATCP	CILTCURP	CILTNBRP
CILTATPP	CILTCUSP	CILTNCDP
CILTATYP	CILTCVTP	CILNUXP
CILTBCRP	CILTDARP	CILTOCRP
CILTBCTP	CILTDASP	CILTOETP
CILTBFFP	CILTDCAP	CILTOPTP
CILTBFVP	CILTDCLP	CILTORAP
CILTBIMP	CILTDIRP	CILTPCRP
CILTBLCP	CILTDLOP	CILTPCTP
CILTBLLP	CILTDPRP	CILTPDRP
CILTBKNP	CILTDSTP	CILTPHTP
CILTBRTP	CILTDWPP	CILTPKGP
CILTBSTP	CILTDWTP	CILTPMDP
CILTBTCP	CILTEBRP	CILPPPTP
CILTBTRP	CILTECRP	CILTPROP
CILTBUDP	CILTEETP	CILTPRTP
CILTBXTP	CILTFAAP	CILPSDP
CILTCAMP	CILTFNDP	CILPSTP
CILTCATP	CILTFRQP	CILPTRP
CILTCCCP	CILTFWLP	CILPYTP
CILTCCTP	CILTGLDP	CILQRTP
CILTCHTP	CILTIIDTP	CILRGLP
CILCIDP	CILTINCP	CILRLEP
CILTCLGP	CILTINSF	CILRSCP
CILTCLWP	CILTIITP	CILRTYTP

Application Service	Application Service	Application Service
CILTCNTP	CILTLDIP	CILTSATP
CILTCOCP	CILTLETP	CILTSCLP
CILTCOTP	CILTLKFP	CILXJSVP
CILTSCYP	CILTWSDP	CILXNDNP
CILTSICP	CILTXNDETAIL	CILXOPTP
CILTSOMP	CILTXNDISAGGEXC	CILXRCVP
CILTSOPP	CILTXNDISAGGREQ	CILXRTTP
CILTSQIP	CILTXNHEADER	CILXSENP
CILTSQRP	CILTXNRECTYPE	CILXSVXP
CILTSVTP	CILTXNSOURCE	CILXTPCP
CILTSWLP	CILTXNSRC	CILXXSCP
CILTTACP	CILTXNSRCD	CILXXUPP
CILTTAXP	CILTXNSRCL	CILYASTP
CILTTGRP	CILUPFTS	CILYDBPP
CILTTMRP	CILVFVDP	CILYDFQP
CILTTMTP	CILVFVSP	CILYDPIP
CILTTNSP	CILVVLEP	CILYENRP
CILTTNTP	CILVVLSP	CILYROBP
CILTOUP	CILWDWNP	CILZAFQP
CILTTRAP	CILWJSDP	CILZAUQP
CILTTRCP	CILWJSSP	CILZFNCP
CILTTTMP	CILWNUPP	CILZPORP
CILTZNP	CILWNUSP	CILZRBP
CILTUOMP	CILWPROP	CILZRPH
CILTURPP	CILXADPP	CILZRPOP
CILTUSCP	CILXAIEP	CILZSCMP
CILTUSEP	CILXAIIP	CILZSCR
CILTUSGP	CILXCLSP	CILZSCZP
CILTWCPT	CILXCONP	CILZTLZP
CILTWDPC	CILXENHP	CILZZOHP
CILTWETP	CILXFRMP	CILZZONP

Application Service	Application Service	Application Service
CILTWFPP	CILXGRPP	CIL_FAVORITES
CILTWPTP	CILXJDBP	CIMOAPPCHAIN
CILTWSCP	CILXJMSP	F1MIGRTIMP
CIPCHT3L	F1-WEBSVCBOAS	F1MIGRTX
CIPFAFHP	F1ADMIN	F1MTXIMP
CIPOLICY	F1APPSEC	F1OBJREVCTL
CIPRICEACCOUNT	F1ATTACH	F1OBJRVH
CIPRICEPARM	F1ATTACHMENT	F1REQ
CIPYSRCH	F1BUNEXP	F1REVHST
CIRECON	F1BUNIMP	F1STRDIS
CIRECONSEG	F1CATTCH	F1STREAS
CIRSTTYP	F1CONFIGLOG	F1SUBRQQ
CIS_DIV_ALGS	F1DEBUG	F1SYNCRM
CIS_DIV_BICIES	F1EXLKP	F1SYNCRQ
CIS_DIV_CST_LNGS	F1EXLKPS	F1TBLEXC
CIS_DIV_ID_TYPES	F1LCAMRP	F1UIZONE
CIS_DIV_INV_CURS	F1LEXTLKUP	F1USERLOG
CIS_DIV_TXN_SRCS	F1LTAMTP	F1USRCHKOUT
CIS_DIV_VLD_CTIES	F1MESSAGE	F1WBSVCM
CTXZONE	F1MGDEXP	F1WBSVCS
DIVS	F1MGDEXS	F1WEBSVC
DIV_PRICEITEMS	F1MGDIMP	F1_BTST
DIV_PRICELISTS	F1MGDIMS	F1_USRFAVSCH
F1-APAYEXPCRTYPEBOAS	F1MGOIMP	FILETYPE
F1-ATTACHMENTBOAS	F1MGPLNM	FWLBNDLP
F1-DFLTAPS	F1MGPLNS	FWLCTDEP
F1-DFLTS	F1MGREQM	FWLFACTP
F1-GENPROC	F1MGREQS	FWLSTRJP
F1-MIGROBJIMP	F1MIGRDEXP	FWLTBELP
F1-STASKTYPE	F1MIGRDIMP	FWLTBOJP
F1-SVCTASK	F1MIGRDS	FWLTBSVP

Application Service	Application Service	Application Service
F1-SYNCREQ	F1MIGROBJ	FWLTDARP
F1-SYNCREQIN	F1MIGRPLAN	GOTOREC
F1-SYNCREQUESTBOAS	F1MIGRREQ	PERTREE
FWLTEXSP	FWLXOUTP	VALIDCHARS
FWLTMGCT	FWLZDEXP	C1LASGN
FWLTOMTP	FWLZWLP	C1PIASGN
FWLTSCHP	FWLTUIMP	C1PLASGNM
C1-BILLCHARGE	C1ELGPA	C1REFUPLREQ
C1BCHGUPLREQ	C1GETELIGPT	C1UPLDRQ
C1BILLCYCLEUPDTUPL	C1GLAT	C1UPLREQ
C1CONTRIDERUPDTUPL	C1GLATEMP	C1WOUPLREQ
C1DCDTLC	C1GLATRQ	C1_STRTE
C1DELCTL	C1HOLDUPLREQ	CILCPASP
ACRLSRCH	C1ADDRESS	C1DSPT
C1-ACCTECR	C1ADDRS	C1DSPTRQ
C1-FTDIST	C1ADDRSBO	C1DSPTRT
C1-FTDISTRULE	C1ADDRSDP	C1DSPTTY
C1-FTDISTTY	C1ADDRSRC	C1FTDIST
C1TNCSRH	C1BK360	C1FTDSRL
C1ACCECR	C1BKAPPSE	C1FTDSTT
C1ACRLCL	C1BKBLDT	C1FTDSTY
C1ACRLTP	C1BKSINF	C1HCSINF
C1ACRMVW	C1PL	C1_ACTVW
C1ADDRDP	C1SAPPTM	C1_ACTYP
C1ADDRDTL	C1_ACCRUAL_SERV	C1_TRLIN
C1_ACYVW	C1_DSPT_REQ	F1-ARQPR
F1-AVALG	F1-LKPIL	F1-SICRL
F1-AVBT	F1-MGDIM	F1-SRCRL
F1-AVMO	F1-MGDPR	F1-SRLRQ
F1-AVTBL	F1-MGOAP	F1-STATSM
F1-AVTD	F1-MGOPR	F1-STCRL

Application Service	Application Service	Application Service
F1-BFCRL	F1-MGTAP	F1-STKDF
F1-BSFLG	F1-MGTPR	F1-STKTR
F1-BUNPR	F1-NDPUR	F1-SUBRQ
F1-DTDOM	F1-ORCRL	F1-SYNEF
F1-FCTRН	F1-OUCRL	F1-SYNIL
F1-FKVPB	C1BUNDLE	F1-SYNRQ
F1-FLUSH	F1ACGRPM	F1-SYSRQ
F1-ILMIN	F1-REQTY	F1-TDCRL
F1-LANG	F1-REVPR	F1-TDEER
F1-LDAP	F1-SAKRQ	F1-TDPG
F1-XMLPG	ACCTVIEW	C1-ACCTAPAY_SERV
C1-DISC-REPT	C1-DRRTMPLT	C1-PRC_CALC_SM
C1-REVRECSCHZ	C1-SCHEDULERMONITOR	C1-SCHPGMQZ
C1-SCHSCHQZ	C1APAYRT	C1APAYVW
C1APYINS	C1AWFCHN	C1AWFCRT
C1AWFGRP	C1AWFRSN	C1AWFSET
C1CONADD	BFEECONT	BILLVARI
C1PARAM	C1PDSRCH	C1PERS
C1PERSDP	C1PERSON	C1PRDSVC
C1PRODDP	C1PRODUCTSERVICE	C1PVERDP
C1REPORT	C1RPTTMP	C1SCHCHN
C1SCHJOB	C1SCHPGM	C1SCHSCH
C1SCJMON	C1SRCAPP	C1SVCDSP
C1VIEPRI	C1-DEALAPPR	C1_BOCHN
C1_CONSTRUCT	C1_DRSP	C1_DRSSR
C1_DRRTM	C1_DR RTP	C1_ENLOG
C1_ENROL	C1_ENROLLMENT	C1_ENSCH
C1_PRODUCT	C1_PRODUCT_SERVICE	C1_PRODVER
CICONACT	CILFDRR	CONRULE
CONSTRUCT	DDPRCSM	PRICECOMPPRE

Application Service	Application Service	Application Service
ACCT_SUBSCRPTN_SERV	C1-PRC_CALC_SM	C1-PRLRTYP
C1-SUBSCRTYPE	C1ACTSBS	C1ASBSVW
C1BANK	C1BANKVW	C1ENTITYREPORT
C1PRICINGGROUP	C1PROAPP	C1PRTYP
C1RPTAUD	C1RPTDEF	C1SUBSTP
C1SUBTVW	C1_SRCBUSSPRD	C1_SRCTECHPRD
C1-CUSTREGTEMPL_SERV	C1-CUSTREGTYPE	C1-DUPBTN
C1-GETPRICINGENTITY	C1-PRICEASGNNTREE	C1MASPRI
C1MPRIRQ	C1MPRISR	C1RETMPL
F1MSTCFG	F1OUMSTQ	F1OUMSTY
PRICECOMPSEQ	C1CREGSR	C1CTRGBK
C1CUREG	C1CURETY	C1CUSTREG
AUDITEVENT	C1-AUDEVTYPE	C1-BANKING
C1-PRICETREE	C1ADEVSR	C1AUDEVT
C1AUDTY	C1RETMPLBK	C1VIPRIN
C1_BILL	USRACCS	WEIGHTAV
C1-HRCHYENTITY	C1ADDPRO	C1CUSTPO
C1DAPROF	C1DEALDB	C1DEALPASGN
C1DEALSVC	C1DELTP	USMISINV
C1DTSERH	C1ENHR	C1ENHRSR
C1ENTDTL	C1FILEMS	C1OFPREQ
C1-DLAPPRTOD	C1GETELIGPRO	C1HIERARCHY
C1HRCHYENTITY	C1HRYENT	C1INREQ
C1INRETY	C1INVRED	C1PISL
C1OFPRED	C1PROSPO	C1PRSEAR
C1PRSSASP	C1REFPRI	C1SERDSC
C1SLFSER	C1_ALRPT	C1-DLDBACTNS
C1_CONSTRUCT	C1_CREF	CANCPAYM
PRICEITEM_SERV	C1 DEAL	C1 DEALAPP SER
C1_HEVD	C1_PDEAL	C1_PRSENROLLMENT

Application Service	Application Service	Application Service
C1_REF	CANCPAYM	CDUPPROD
CMPERTESTASE	CM_TEST	CNSTRTEM
CONTEXTR	CRITBLAN	CUSDREN
CUSPRCDT	CUSTHRCH	CUSTINVM
DATAVAL	DENTREJ	DUMMYACT
DUMMYCIS	F1TODOMG	ICRGRPID
INCRADDR	INCRBILL	INCRINAC
INCRSTAC	INCRUSAC	INCURRAD
INVCARGR	INVLDCSK	INVOICSE
INVSTLAC	MGCEXP	MISSETCO
MULCSKY	NOBILLCH	NOCISKEY
NOCUSTYP	NOSTDPRC	NUSG
OVRDPRIC	OVRRDPRC	C1-DLTODOLST
PNDPYMNT	PORTEST	PORTT
PRDPROF	PRODSTAT	PROITMPR
PROSADD	PRTTST	C1DLAPDB
SETACCMPP	STDPLREV	STNPLRLST
TBDCONIN	TBDINQAC	TRADING
TRANSREJ	TRIALBL	TRLBILDT
TRSREJPR	C1GETELIGPROD	C1GETELIGPLPRO
UAINVCNS	USAGINVA	USGACC
C1-DEALRVW	C1-EXTCTTEMP	C1-EXTRACTTEMPLATE
C1-FIELDMAP	C1-FIELDMAP_SERV	C1-PROSPECTCRET
C1-PRSPRODENRL	C1-TNC	C1DEAL1
C1DLPRT	C1DLTMPT	C1EXTCTTEMP
C1EXTTMP	C1PLSIM	C1PLSM
C1PLSMPL	C1PLSMVW	C1PRICELISTSIM
C1QUESTION	C1STPDL	C1TCMAP
C1TERCO	F1ACGRPQ	F1ALGQ
F1ALGTQ	F1APPSVM	F1APPSVQ

Application Service	Application Service	Application Service
F1BOQ	F1BSVQ	F1BTCHQ
F1CHRTYP	F1CHRTYQ	F1DTARQ
F1FCFGQ	F1FIELD	F1FKRFQ
F1FLDQ	F1LKUPQ	F1MANCQ
F1MENUQ	F1MOQ	F1MSG
F1MSGC	F1MSGQ	F1NAVQK
F1NAVOQ	F1PRTL	F1PRTLQ
F1SCRQ	F1TABLE	F1TBLQ
F1TDDASH	F1TMZNM	F1TODO
F1TODOEQ	F1UIMPQ	F1WRKCAL
F1WRKCLQ	F1ZONE	F1ZONEQ

B.3 HCADMIN

The following table lists all application services configured for the HCADMIN user group:

Application Service	Application Service	Application Service
AFHZONE	C1-INS-POLICY	C1-SRCHSCPT
APPTXADM	C1-INSDETBK	C1-UNLINK
BILLGCONS	C1-MAINPINFR	C1-UNLINKPP
BILLGRAPH	C1-MEMBSP	C1-UPLOADCSV
C1-ACCBALCNT	C1-NAVACTCUR	C1-WRITEOFFREQ
C1-ACCCURDET	C1-NAVTOEXST	C1ACC RATE
C1-ACCDISCREZ	C1-PAY-REQ	C1ACINSP
C1-ACCURTEXT	C1-PAYMENT	C1ACTPER
C1-ACNPOLSUMZ	C1-PAYTEMPLATEBOAS	C1ACTREE
C1-ACPOLSUMMZ	C1-PERBALCNT	C1ADJSTP
C1-ADJAPPRVLREQBOAS	C1-PIFVIS	C1ADJUPL
C1-APAYEXPCRREQBOAS	C1-PINFRDISP	C1APPBOCHNZN
C1-APAYEXPCRTYPEBOAS	C1-PINVPOST	C1APPCHN
C1-APPRSN	C1-POINFRDET	C1APPCRT
C1-APPTXN	C1-POLICYINVOICEFREQ	C1APPRESP

Application Service	Application Service	Application Service
C1-APPTXNLOG	C1-POLICYPLAN	C1APPTXNBOCHN
C1-ASAPU	C1-POLINVDETZ	C1APPTXNBOCHNZN
C1-ASGNPL	C1-POLINVEDI	C1APPTXNCHAIN
C1-BILLCHARGE	C1-POLINVFRE	C1APPTXNCRI
C1-BRD	C1-POLINVFREZ	C1APPTXNCRT
C1-CNTRTPPTZ	C1-POLINVFRQ	C1APPTXNGRP
C1-CONTRACTCHARSVALI	C1-PPACCTSRC	C1BOCHN
C1-CONTRACTTYPECHARS	C1-PPPROC	C1FLRQTY
C1-DEFAULTPP	C1-PPTERROR	C1FLSRCH
C1-DFLTPPTMP	C1-QUICKPAGINATION	C1INSPAY
C1-DRRDTLSZ	C1-REFWOREQ	C1MANAPP
C1-DUPBTN	C1-REQUEST-TYPE	C1MANLOG
C1-GETADJ	C1-RETURNDUP	C1MANMOD
C1-GETEFFECTVPRICING	C1-REVRECSCHZ	C1MANRES
C1-GETPPTMPL	C1-SHDETAILSZ	C1MEMBRS
C1MEMBSP	C1PTPLP	C1_BRD_P
C1NCISPY	C1PYRQTY	C1_BUNDLE
C1NCPTMP	C1REFSTP	C1_CHKBL_PA
C1ODBUPR	C1REFUND	C1_CHKTRDFLG
C1PASGAPPROVE	C1REQSTS	C1_CIGAS
C1PASGREADMODIFY	C1REQTYP	C1_CIMAPZ
C1PASGREADRESOLVE	C1RFWORT	C1_COM_VALID
C1PAYMAN	C1SAPPTM	C1_COPYPL
C1PAYPTL	C1SATYPELISTZ	C1_CPBUNDL
C1PAYREQ	C1SCHEDU	C1_CPYPL
C1PAYRQ	C1VAR	C1_CUSTINFO
C1PAYSRC	C1WODET	C1_DEL_PRD
C1PAYUPL	C1_ADDEXH	C1_DEL_PROD
C1PERRL	C1_ADDPL	C1_DISPBUND
C1PLCYPL	C1_ADDPROD	C1_DRSSR
C1PLCYPN	C1_ADD_RTCMP	C1_DSPLY_RT

Application Service	Application Service	Application Service
C1PLCYTY	C1_ADD_TIER	C1_EDTBUND
C1POINFR	C1_ADMPI	C1_EDTER
C1POLACL	C1_ANSP LTCUS	C1_EDTPL
C1POLCYN	C1_APACS	C1_EDTPROD
C1POLCYP	C1_APPAD	C1_EDT_PRITM
C1POLPEL	C1_APPTXN_PRICEASGN	C1_EFF_PRC
C1POLSCH	C1_APPWF	C1_EFF_PRICE
C1POLSRCH	C1_APUR	C1_EFPRODSRC
C1POLTYP	C1_APVIG	C1_EXCHRT
C1PPCARS	C1 ASNPL	C1_EXHRT
C1PPDUP	C1_BACCGRVAL	C1_EXPPITM
C1PRISIM	C1_BAFHZ	C1_FTRS
C1PRODUCT	C1_BFHIS	C1_F_ADDCHLD
C1PSNAPP	C1_BNDMN	C1_F_ADDEXCH
C1PSNMOD	C1_BNDPRD	C1_F_ADDPL
C1PSNRES	C1_BNDPRS	C1_F_ADDPRD
C1PTNDRH	C1_BO_OPT	C1_F_ADDPRPL
C1_F_ADDPRSS	C1_F_IGG2MS	C1_OVR_PRITM
C1_F_ADDRATE	C1_F_IGG3MM	C1_PAYUP
C1_F_ADMPROD	C1_F_IGG3MS	C1_PCUSSRCH
C1_F_ADPROD	C1_F_PERSRCH	C1_PLADPR
C1_F_APVDTVL	C1_F_PLCRT	C1_PLAE
C1_F_APVNFLT	C1_F_PLEDT	C1_PLASNADD
C1_F_ASNCUS	C1_F_PLVAL	C1_PLASNEDIT
C1_F_ASGNPTP	C1_F_POPITEM	C1_PLASN_ADD
C1_F_CIGG3V	C1_F_PRCHAR	C1_PLASN_EDI
C1_F_COPYPL	C1_F_PRCHARS	C1_PLASSIGN
C1_F_CPYBNDL	C1_F_PRDVL	C1_PLASSIGNE
C1_F_CPYPL	C1_F_PRODVAL	C1_PLCLASSIGN
C1_F_CPYPLVL	C1_F_PRODV1	C1_PLEDIT
C1_F_CUSSRCH	C1_F_RSCDVAL	C1_PLISTSRCH

Application Service	Application Service	Application Service
C1_F_DELEXCH	C1_F_RTDESC	C1_PLMNG
C1_F_DELSCS	C1_F_SAVESCS	C1_PLPTYAINF
C1_F_DTVAL	C1_F_SRPLVAL	C1_PLPTYINFO
C1_F_EDTEXHR	C1_F_VAL_CUS	C1_PLSRCH
C1_F_EDTMMP	C1_GENERICSA	C1_PLSTOGGLE
C1_F_EDTPL	C1_GENRCMP	C1_PLVAL
C1_F_EDTPR	C1_GETTIER	C1_PLVALIDAT
C1_F_EDTPROD	C1_GRP	C1_PLVIEW
C1_F_EDTPRPL	C1_IGMMB	C1_PL_ADD
C1_F_EDTPRSS	C1_INF_PARTY	C1_PL_EDIT
C1_F_EXCDVAL	C1_INVC	C1_PL_PI
C1_F_EXCHVAL	C1_LIST_TIER	C1_PMPRC
C1_F_EXHVAL	C1_MIG	C1_POLICYTYPE
C1_F_GENACBO	C1_MIGAS	C1_PPEDT
C1_F_IGG1MM	C1_MNGRT	C1_PPOVR
C1_F_IGG1MS	C1_MNGTR	C1_PPOVRSRCH
C1_F_IGG2MM	C1_MPPA	C1_PP_DSPINF
C1_PP_PLVAL	C1_SRCHPL	CILBSBHP
C1_PRCAD	C1_SRCHPLVAL	CILBSCCP
C1_PRCE_VALD	C1_SRCHPPL	CILBSEGP
C1_PRCPM	C1_SRCHPRD	CILBSTM
C1_PRC_EDIT	C1_SRCH_PROF	CILCAAHP
C1_PRC_OVRD	C1_SRPROD	CILCAASP
C1_PRC_TR	C1_STRTOLIST	CILCACCP
C1_PRC_VALID	C1_TEMPLATE	CILCALZP
C1_PRDREL	C1_TIER_INP	CILCAMRP
C1-OFFPRO	C1_VWPRD	CILCBCUP
C1_PRITSRCH	CHGTYPE	CILCCCIP
C1_PROD	CHGTYPECD	CILCCCP
C1_PRODPL	CIACNBTY	CILCCIZP
C1_PROD_ADD	CIAPAYSTGUPL	CILCCNSP

Application Service	Application Service	Application Service
C1_PROD_EDIT	CIAPPACCTYPE	CILCCNXP
C1_PROD_SRCH	CIAPPHELGBL	CILCCSCP
C1_PROVR_EDT	CIAPPCRIT	CILCCSHP
C1_PRZCR	CIAPPTXNCHAIN	CILCCTXP
C1_PRZTR	CIAPPTXNRSN	CILCFIZP
C1_PRZ_CR	CICASE	CILCPERP
C1_PRZ_TR	CICASECREATE	CILCPLAS
C1_PTPLA	CICHGTYPE	CILCPPLP
C1_RATE_DEF	CICREATEPAYMENTS	CILCPRMP
C1_RECTIFYSRCH	CIGETPRICING	CILCSALP
C1_RSN	CILAADUP	CILCSSEP
C1_RTCOM_ADD	CILAASCP	CILCSVAP
C1_RTC_VAL	CILAUSP	CILDATA
C1_RTOPT	CILACCDEL	CILDIVET
C1_SAVE_TIER	CILACLCP	CILDIVEXT
C1_SHOW_IMG	CILBBICP	CILECBLP
C1_SRCH	CILBBLPP	CILEFKRP
CILEFLDP	CILPILANG	CILRRVMP
CILEMNUP	CILPIREL	CILSACHG
CILEMOBP	CILPITXNREL	CILTACRP
CILENAVP	CILPOLMO	CILTALGP
CILENVOP	CILPPAYP	CILTALTP
CILERPTP	CILPPCAN	CILTAMGP
CILESVCP	CILPPTSP	CILTAMTP
CILETBLP	CILPQADP	CILTAPAP
CILEUIZP	CILPRCITMREL	CILTAPFP
CILEXCHRATE	CILPRICELISTCHAR	CILTAPSP
CILFAFHP	CILPRIITEM	CILTAROP
CILFBLCP	CILPRLIST	CILTARTP
CILFBPHP	CILPRLISTDIV	CILTASGP
CILFDRR	CILPRLISTL	CILTATCP

Application Service	Application Service	Application Service
CILFFNTP	CILPTCNP	CILTATPP
CILFFTBP	CILQATDP	CILTATYP
CILFFTTP	CILQCASP	CILTBCRP
CILFLGRP	CILQTDEP	CILTBCTP
CILFMVTP	CILQTDLP	CILTBFFP
CILFSFHP	CILQTDQP	CILTBFP
CILITPDP	CILQTDSP	CILTBIMP
CILLODPP	CILQTDTP	CILTBLCP
CILPAPHP	CILQTDZP	CILTBLPP
CILPAPSP	CILQTSSP	CILTBKNP
CILPDCNP	CILQTSUP	CILTBRTP
CILPDCSP	CILRCMAP	CILTBSTP
CILPEPLP	CILRENGP	CILTBTCP
CILPEQAP	CILRRSMP	CILTBTRP
CILPEVTP	CILRRTCP	CILTBXTP
CILPICCHAR	CILRRTSP	CILTCAMP
CILPIDIV	CILRRTVP	CILTCATP
CILTCCCP	CILTTTP	CILTSARP
CILTCCTP	CILTLDIP	CILTSATP
CILTCHTP	CILTLETP	CILTSCLP
CILTCIDP	CILTLKFP	CILTSCYP
CILTCLGP	CILTLNGP	CILTSICP
CILTCLRP	CILTMCRP	CILTSOMP
CILTCLWP	CILTMHTP	CILTSOPP
CILTCNTP	CILTMSGP	CILTSQIP
CILTCOCP	CILNUXP	CILTSQRP
CILTCQTP	CILTOCRP	CILTSTMP
CILTCURP	CILTOETP	CILTSVTP
CILTCUSP	CILTOPTP	CILTSWLP
CILTDARP	CILTORAP	CILTTACP
CILTDASP	CILTPCRP	CILTTAXP

Application Service	Application Service	Application Service
CILTDCAP	CILTPCTP	CILTTGRP
CILTDCLP	CILTPDRP	CILTTMRP
CILTDIRP	CILTPHTP	CILTTMTP
CILTDPRP	CILTPIFP	CILTTNSP
CILTDSTP	CILTPKGP	CILTTNTP
CILTDWPP	CILTPMDP	CILTOUP
CILTDWTP	CILPPPTP	CILTTRAP
CILTEBRP	CILTPRTP	CILTTTMP
CILTECRP	CILTPSDP	CILTZNP
CILTEFTP	CILTPSTP	CILTUOMP
CILTFNDP	CILTPTRP	CILTURPP
CILTFRQP	CILTPYTP	CILTUSCP
CILTFWLP	CILTQRTP	CILTUSEP
CILTGLDP	CILTRGLP	CILTUSGP
CILTIDTP	CILTRLEP	CILTWCTP
CILTINCP	CILTRSCP	CILTWDCP
CILTINSP	CILTRRTYP	CILTWETP
CILTWFPP	CILXOPTP	CISATYCHG
CILTWPTP	CILXRCVP	CTXZONE
CILTWSCP	CILXRTTP	DIVS
CILTWSDP	CILXSENP	DIV_PRICEITEMS
CILTXNDETAIL	CILXSVXP	DIV_PRICELISTS
CILTXNSRC	CILXTPCP	F1-APAYEXPCRTYPEBOAS
CILTXNSRCD	CILXXSCP	F1-ATTACHMENTBOAS
CILTXNSRCL	CILXXUPP	F1-DECRPTBOAS
CILUPFTS	CILYASTP	F1-DFLTAPS
CILVFVDP	CILYDBPP	F1-DFLTS
CILVFVSP	CILYDFQP	F1-EXPUSERSREQBOAS
CILVVLEP	CILYDPIP	F1-GENPROC
CILVVLSP	CILYENRP	F1-MIGROBJIMP
CILWDWNP	CILYROBP	F1-STASKTYPE

Application Service	Application Service	Application Service
CILWJSDP	CILZAFQP	F1-SVCTASK
CILWJSSP	CILZAUQP	F1-SYNCREQ
CILWNUPP	CILZFNCP	F1-SYNCREQIN
CILWNUSP	CILZPORP	F1-SYNCREQUESTBOAS
CILWPROP	CILZRBPP	F1-WEBSVCBOAS
CILXADPP	CILZRPHP	F1ADMIN
CILXAIEP	CILZRPOP	F1ATTACH
CILXAIIP	CILZRPTP	F1ATTACHMENT
CILXCLSP	CILZSCRP	F1CATTCH
CILXCONP	CILZSCZP	F1CONFIGLOG
CILXENHP	CILZTLZP	F1DEBUG
CILXFRMP	CILZZOHP	F1EXLKP
CILXGRPP	CILZZONP	F1EXLKPS
CILXJDBP	CIL_FAVORITES	F1LCAMRP
CILXJMSP	CIPRICEACCOUNT	F1LEXTLKUP
CILXJSVP	CISACHG	F1LTAMTP
CILXNDNP	CISACHGTYPE	F1MGDEXP
F1MGDEXS	F1_USRFAVSCH	F1SUBRQQ
F1MGDIMP	FILETYPE	F1SYNCRM
F1MGDIMS	FWLCTDEP	F1SYNCRQ
F1MGOIMP	FWLFACTP	F1TBLEXC
F1GPLNM	FWLSTRJP	F1UIZONE
F1GPLNS	FWLTBELP	F1USERLOG
F1GREQM	FWLTBOJP	F1WBSVCM
F1GREQS	FWLTBSVP	F1WBSVCS
F1MIGRDEXP	FWLTDARP	F1WEBSVC
F1MIGRDIMP	FWLTEXSP	F1_BTST
F1MIGRDS	FWLTMGCT	F1REQTYP
F1MIGROBJ	FWLTOMTP	F1STRDIS
F1MIGRPLAN	FWLTSCHP	F1STREAS
F1MIGRREQ	FWLTUIMP	PERTREE

Application Service	Application Service	Application Service
F1MIGRTIMP	FWLXOUTP	SACHGLNK
F1MIGRTX	FWLZDEXP	SATYPCHG
F1MTXIMP	FWLZWLP	C1LASGN
F1REQ	GOTOREC	C1PIASGN
C1BCHGUPLREQ	C1DELCTL	C1PLASGNM
C1BILLCYCLEUPDTUPL	C1ELGPA	C1REFUPLREQ
C1CONTRIDERUPDTUPL	C1GETELIGPT	C1UPLDRQ
C1DCDTLC	C1HOLDUPLREQ	C1UPLREQ
C1WOUPLREQ	CILCPASP	C1HCSINF
C1-ACCNBRTYPAS	C1ADDRESS	C1INMSGP
C1-CUSTINMSG	C1ADDRS	C1INMSRH
C1-GENRQ	C1ADDRSBO	C1INMSTY
C1-INMSG	C1ADDRSRC	C1PAREQ
C1-INMSGTYPE	C1CUS360	C1PARQMN
C1-MEMBERINMSG	C1DSPT	C1PARQTY
C1-POLPERORLEAS	C1DSPTRQ	C1PI
C1-PROSPECTCRET	C1DSPTRT	C1PL
C1-REQUEST	C1DSPTTY	C1PRICEASGN
C1ADDRDP	C1HCAPPSER	C1REINUPLREQ
C1ADDRDTL	C1HCBLDT	CILTHDHP
C1_DSPT_REQ	CIPOLPERROLE	F1-ARQPR
F1-AVALG	F1-LKPIL	F1-SICRL
F1-AVBT	F1-MGDIM	F1-SRCRL
F1-AVMO	F1-MGDPR	F1-SRLRQ
F1-AVTBL	F1-MGOAP	F1-STATSM
F1-AVTD	F1-MGOPR	F1-STCRL
F1-BFCRL	F1-MGTAP	F1-STKDF
F1-BSFLG	F1-MGTPR	F1-STKTR
F1-BUNPR	F1-NDPUR	F1-SUBRQ
F1-DTDOM	F1-ORCRL	F1-SYNEF
F1-FCTRN	F1-OUCRL	F1-SYNIL

Application Service	Application Service	Application Service
F1-FKVPB	F1ALGQ	F1-SYNRQ
F1-FLUSH	F1ALGTQ	F1-SYSRQ
F1-ILMIN	F1-REQTY	F1-TDCRL
F1-LANG	F1-REVPR	F1-TDEER
F1-LDAP	F1-SAKRQ	F1-TDPG
F1-XMLPG	ACCTVIEW	C1-ACCTAPAY_SERV
C1-DISC-REPT	C1-DRRTMPLT	C1-MBR-DR-TY
C1-REVRECPLCY	C1ACCTAPAY	C1APAYRT
C1APAYVW	C1APYINS	C1DISREP
C1DRDIS	C1DSRTY	C1ENTDTL
C1OFPBP	C1MBRRCN	C1PARAM
C1PERS	C1PERSDP	C1PERSON
C1RCONTY	C1RECOLN	C1RECONCIL
C1RECONTYP	C1SRCAPP	C1VIEWRL
C1_BPYHS	C1_DRSP	C1_DRRTM
C1_DRRTP	C1_INVCN	C1_PAYIN
C1_PRODUCT	C1_RLTPM	C1_RLTVW
CILRULTP	CONRULE	PRICECOMPPRE
GETDEALTYPE	C1-PRRLTYP	C1-RULEBOAS
C1-TXNAGG	C1-TXNDTL	C1-TXNREC
C1_TRBL	C1BILLVL	C1BILLSORT
C1_TRBLIN	C1BLLVLUPLREQ	C1BLLSRTUPLREQ
C1DISAGR	C1ENTITYREPORT	C1PRICINGGROUP
C1PROAPP	C1PRTYP	C1SRCHRL
C1TXNAGG	TRIALBL	F1TODOMG
C1TXNFD	C1OFPRED	C1GETELIGPLPRO
C1_BUNDVAL	C1_COPYBND	C1_CPYBD
C1OFPREQ	C1_PRICE	C1_TXNAR
CILTXNSOURCE	CIPRICEPARM	F1APPLYBNDL
F1BNDLEM	F1BNDLES	F1BNDLIM

Application Service	Application Service	Application Service
F1BNDLIS	F1BUNEXP	F1BUNIMP
F1IWSDPL	F1IWSSVC	F1IWSVCP
F1IWSVCS	FWLBNDLP	C1-ACCUDATA
C1-CUSTREGTEMPL_SERV	C1-CUSTREGTYPE	C1-GETPRICINGENTITY
C1-PICINGRULE	C1ACUDAT	C1MASPRI
C1MPRISR	C1RETMPL	F1OUMSTQ
F1OUMSTY	PRICECOMPSEQ	C1CREGSR
C1CTR GHC	C1CUREG	C1CURETY
C1CUSTREG	C1CUSTRG	AUDITEVENT
C1-AUDEVTYPE	C1-HEALTHCARE	C1ADEVSR
C1AUDEVT	C1AUDTY	C1RETMPLHC
C1STATE	C1_BILL	C1INREQ
C1INRETY	C1INVRED	C1TRBLHC
C1-BENEFITS	C1-BENFITPKG	C1-FIELDMAP
C1-FIELDMAP_SERV	C1-GETFIPRCRULE	C1-TNC
C1BENFTP	C1BENFTS	C1FLDMAP
C1GEORTA	C1GEORTAR	C1RELSTR
C1TERCO	C1TERMNCO	C1TNCSRH
C1_MEMRL_SUBT	PRICEITEM_SERV	C1-BUSRULE
C1-BUSRULVAL	C1BENSTY	C1BUSRD
C1BUSRUL	C1MEIDTY	C1_HCPRODUCT
C1_HLTH_PLAN	F1APPSVM	F1APPSVQ
F1BOQ	F1BSVQ	F1BTCHQ
F1CHRTYP	F1CHRTYQ	F1DTARQ
F1FCFGQ	F1FIELD	F1FKRFQ
F1FLDQ	F1LKUPQ	F1MANCQ
F1MENUQ	F1MESSAGE	F1MOQ
F1MSG	F1MSGC	F1MSGQ
F1NAVQ	F1NAVOQ	F1PRTL
F1PRTLQ	F1SCRQ	F1TABLE

Application Service	Application Service	Application Service
F1TBLQ	F1TDDASH	F1TMZNM
F1TODO	F1TODOEQ	F1UIMPQ
F1WRKCAL	F1WRKCLQ	F1ZONE
F1ZONEQ	-	-

B.4 INADMIN

The following table lists all application services configured for the INADMIN user group:

Application Service	Application Service	Application Service
AFHZONE	C1-CNTRTPPTZ	C1-EXTSTMICHZ
APPTXADM	C1-CONTRACTCHARSVALI	C1-EXTSTMLOGZ
BILLGCONS	C1-CONTRACTTYPECHARS	C1-EXTSTMTAD
BILLGRAPH	C1-CTRLC	C1-EXTSTMTCHAR
C1-ACCBALCNT	C1-DEFAULTPP	C1-EXTSTMTED
C1-ACCCRCHM	C1-DELPPTMP	C1-EXTSTMTITEM
C1-ACCCURDET	C1-DFLTPPTMP	C1-EXTSTMTITMCHR
C1-ACCDetailZ	C1-DRRDTLSZ	C1-EXTSTMTTRC
C1-ACCDISCREZ	C1-DUPBTN	C1-EXTSTMTSRZ
C1-ACCOUNTCURRENT	C1-EDITPPTMP	C1-EXTSTMTZ
C1-ACCQUICED	C1-EQUITYDT	C1-GETADJ
C1-ACCREDIT	C1-EXITEMDEL	C1-GETEFFECTVPRICING
C1-ACCRLOGZ	C1-EXITEMED	C1-GETPPTMPL
C1-ACCSELECT	C1-EXSTMVBNF	C1-INSDETBAK
C1-ACCURERR	C1-EXTACQRYZ	C1-ISSUEDATEPOLICYCH
C1-ACCURTEXT	C1-EXTAUTREC	C1-LINKPPTMP
C1-ACNPOLSUMZ	C1-EXTERNALSTATEMENT	C1-LINKPPTMP2
C1-ACPOLSUMMZ	C1-EXTITEMAD	C1-MAINPINFR
C1-ACTPPTMPL	C1-EXPENDG	C1-MAINPPLAN
C1-ACURITEMD	C1-EXTREOPN	C1-MAINPPTMP
C1-ADJAPPRVLREQBOAS	C1-EXTSTCHM	C1-MOVEPPT
C1-APAYEXPCRREQBOAS	C1-EXTSTIMP	C1-NAVACTCUR
C1-APAYEXPCRTYPEBOAS	C1-EXTSTITCH	C1-NAVTOEXST

Application Service	Application Service	Application Service
C1-APPRSN	C1-EXTSTLDB	C1-PAY-REQ
C1-APPTXN	C1-EXTSTMNF	C1-PAYMENT
C1-APPTXNLOG	C1-EXTSTM CAN	C1-PAYPLAN
C1-ASAPU	C1-EXTSTMCLD	C1-PAYPLAND
C1-ASGNPL	C1-EXTSTMCLS	C1-PAYPLANTMPLCOMPL
C1-BILLCHARGE	C1-EXTSTM DTLZ	C1-PAYPLANZ
C1-BRD	C1-EXTSTM DZ	C1-PAYPLNBPA
C1-PAYTEMPLATEBOAS	C1-PPDUP	C1ACINSP
C1-PERBALCNT	C1-PPEDIT	C1ACTPER
C1-PIFVIS	C1-PPEDTTASK	C1ACTREE
C1-PINFRDISP	C1-PPLANDET	C1ADJSTP
C1-PINVPOST	C1-PPPROC	C1ADJUPL
C1-POINFRDET	C1-PPSACCSRC	C1APPBOCHNZN
C1-POLCANCE	C1-PPTCNTDETZ	C1APPCHN
C1-POLCANZ	C1-PPTERROR	C1APPCRT
C1-POLICY	C1-PPTMPDISP	C1APPRESP
C1-POLICYBPA	C1-PPTMPDUP	C1APPTXNBOCHN
C1-POLICYCANRSNSERV	C1-PPTMPL	C1APPTXNBOCHNZN
C1-POLICYCHAR	C1-PPTMPLD	C1APPTXNCHAIN
C1-POLICYDESC	C1-PPTMPLDET	C1APPTXNCRI
C1-POLICYINVOICEFREQ	C1-PPTMPLDETZ	C1APPTXNCRT
C1-POLICYSUM	C1-PPTMPLVIS	C1APPTXNGRP
C1-POLINVDETZ	C1-PPTMPLZ	C1BOCHN
C1-POLINVEDI	C1-PPTMPPOST	C1CCACCT
C1-POLINVFRE	C1-PSTAKEHLD	C1CCPORT
C1-POLINVFREZ	C1-QUICKPAGINATION	C1CNTCR
C1-POLINVFRQ	C1-RECVAL	C1CTRLC
C1-POLI_FHZ	C1-REFWOREQ	C1FLRQTY
C1-POLNOMINEZ	C1-REQUEST-TYPE	C1FLSRCH
C1-POLPERORLEAS	C1-RETURNDUP	C1INSPAY
C1-POLREINSTSR	C1LISTBL	F1TODOMG

Application Service	Application Service	Application Service
C1-POLSUMZ	C1-SHDETAILSZ	C1MANAPP
C1-PPACCTSRC	C1-SRCHSCPT	C1MANLOG
C1-PPACTV	C1-UNLINK	C1MANMOD
C1-PPBTNS	C1-UNLINKPP	C1MANRES
C1-PPDET	C1-UPLOADCSV	C1NCISPY
C1-PPDETZ	C1-WRITEOFFREQ	C1NCPTMP
C1-PPDISP	C1ACC RATE	C1ODBUPR
C1PASGAPPROVE	C1PTPLP	C1_BACCGRVAL
C1PASGREADMODIFY	C1PYRQTY	C1_BAFHZ
C1PASGREADRESOLVE	C1RECDTLSTAT	C1_BFHIS
C1PAYMAN	C1RECONDTL	C1_BNDMN
C1PAYPLAN	C1REFSTP	C1_BNDPRD
C1PAYPTL	C1REFUND	C1_BNDPRS
C1PAYREQ	C1REQSTS	C1_BO_OPT
C1PAYRQ	C1REQTYP	C1_BRD_P
C1PAYSRC	C1RFWORT	C1_BUNDLE
C1PAYUPL	C1SAPPTM	C1_CHKBL_PA
C1PERRL	C1SATYPELISTZ	C1_CHKTRDFLG
C1POINFR	C1SCHEDU	C1_CIGAS
C1POLACL	C1VAR	C1_CIMAPZ
C1POLICYCANRSN	C1VARIANCE	C1_COM_VALID
C1POLPEL	C1WODET	C1_COPYPL
C1POLSRH	C1_ACCUR	C1_CPBUNDL
C1POLTYP	C1_ACUNV	C1_CPYPL
C1PPCAR S	C1_ADDEXH	C1_CUSTINFO
C1PPDUP	C1_ADDPL	C1_DEL_PRD
C1PPLAN	C1_ADDPROD	C1_DEL_PROD
C1PPSRH	C1_ADD_RTCMP	C1_DISP BUND
C1PPSRS	C1_ADD_TIER	PRICECOMPPRE
C1PPTMPL	C1_ADMPI	C1_DSPLY_RT
C1PPTMPO	C1_ANSP LTCUS	C1_EDTBUND

Application Service	Application Service	Application Service
C1PPVERSCHZ	C1_APACS	C1_EDTER
C1PRISIM	C1_APPAD	C1_EDTPL
C1PRODUCT	C1_APPTXN_PRICEASGN	C1_EDTPROD
C1PSNAPP	C1_APPWF	C1_EDT_PRITM
C1PSNMOD	C1_APUR	C1_EFF_PRC
C1PSNRES	C1_APVIG	C1_EFF_PRICE
C1PTNDRH	C1 ASNPL	C1_EFPRODSRC
C1_EXCHRT	C1_F_EDTMMP	C1_F_VAL_CUS
C1_EXHRT	C1_F_EDTPL	C1_GENERICSA
C1_EXPPITM	C1_F_EDTPR	C1_GENRCMP
C1_EXSTD	C1_F_EDTPROD	C1_GETTIER
C1_EXSTL	C1_F_EDTPRPL	C1_GRP
C1_EXSTM	C1_F_EDTPRSS	C1_IGMMB
C1_EXSTS	C1_F_EXCDVAL	C1_INF_PARTY
C1_FTRS	C1_F_EXCHVAL	C1_INS_SRCH
C1_F_ADDCHLD	C1_F_EXHVAL	C1_INVC
C1_F_ADDEXCH	C1_F_GENACBO	C1_LIST_TIER
C1_F_ADDPL	C1_F_IGG1MM	C1_MIG
C1_F_ADDPRD	C1_F_IGG1MS	C1_MIGAS
C1_F_ADDPRPL	C1_F_IGG2MM	C1_MNGRT
C1_F_ADDPRSS	C1_F_IGG2MS	C1_MNGTR
C1_F_ADDRATE	C1_F_IGG3MM	C1_MPPA
C1_F ADMPROD	C1_F_IGG3MS	C1_OVR_PRITM
C1_F_ADPROW	C1_F_PERSRCH	C1_PAYUP
C1_F_APVDTVL	C1_F_PLCRT	C1_PCUSRCH
C1_F_APVNFLT	C1_F_PLEDT	C1_PLADPR
C1_F_ASNCUS	C1_F_PLVAL	C1_PLAE
C1_F_ASNCPTP	C1_F_POLSRCH	C1_PLASNADD
C1_F_CIGG3V	C1_F_POPITEM	C1_PLASNEDIT
C1_F_COPYPL	C1_F_PRCHAR	C1_PLASN_ADD
C1_F_CPYBNDL	C1_F_PRCHARS	C1_PLASN_EDI

Application Service	Application Service	Application Service
C1_F_CPYPL	C1_F_PRDVL	C1_PLASSIGN
C1_F_CPYPLVL	C1_F_PRODVAL	C1_PLASSIGNE
C1_F_CUSSRCH	C1_F_PRODVL1	C1_PLCASSIGN
C1_F_DELEXCH	C1_F_RSCDVAL	C1_PLEDIT
C1_F_DELSCS	C1_F_RTDESC	C1_PLISTSRCH
C1_F_DVAL	C1_F_SAVESCS	C1_PLMNG
C1_F_EDTEXHR	C1_F_SRPLVAL	C1_PLPTYAINF
C1_PLPTYINFO	C1_PRZCR	CIAPPHELGBL
C1_PLSRCH	C1_PRZTR	CIAPPCRIT
C1_PLSTOGGLE	C1_PRZ_CR	CIAPPTXNCHAIN
C1_PLVAL	C1_PRZ_TR	CIAPPTXNRSN
C1_PLVALIDAT	C1_PTPLA	CICASE
C1_PLVIEW	C1_RATE_DEF	CICASECREATE
C1_PL_ADD	C1_RECON	CICHGTYPE
C1_PL_EDIT	C1_RECTIFYSRCH	CICPAYPLAN
C1_PL_PI	C1_RSN	CICREATEPAYMENTS
C1_PMPRC	C1_RTCOM_ADD	CIGETPRICING
C1_PPEDT	C1_RTC_VAL	CILAADUP
C1_PPOVR	C1_RTOPT	CILAASCP
C1_PPOVRSRCH	C1_SAVE_TIER	CILAAUSP
C1_PP_DSPINF	C1_SHOW_IMG	CILACCDEL
C1_PP_PLVAL	C1_SRCH	CILAACLCP
C1_PRCAD	C1_SRCHPL	CILBBICP
C1_PRCE_VALD	C1_SRCHPLVAL	CILBBLPP
C1_PRCPM	C1_SRCHPPL	CILBMCRP
C1_PRC_EDIT	C1_SRCHPRD	CILBSBHP
C1_PRC_OVRD	C1_SRCH_PROF	CILBSCCP
C1_PRC_TR	C1_SRPROD	CILBSEGP
C1_PRC_VALID	C1_STRTOLIST	CILBSTMPP
C1_PRDREL	C1_TEMPLATE	CILCAAHP
C1GETEIGPLPRO	C1_TIER_INP	CILCAASP

Application Service	Application Service	Application Service
C1_PRITSRCH	C1_VIEW	CILCACCP
C1_PROD	C1_VWPRD	CILCALZP
C1_PRODPL	CHGTYPE	CILCAMRP
C1_PROD_ADD	CHGTYPECD	CILCBCUP
C1_PROD_EDIT	CIACNBTY	CILCCCIP
C1_PROD_SRCH	CIAPAYSTGUPL	CILCCCP
C1_PROVR_EDT	CIAPPACCTYPE	CILCCIZP
CILCCNSP	CILFBLCP	CILPRLIST
CILCCNXP	CILFBPHP	CILPRLISTDIV
CILCCSCP	CONRULE	CILPRLISTL
CILCCSHP	CILFFNTP	CILPTCNP
CILCCTXP	CILFFTBP	CILQATDP
CILCFIZP	CILFFTTP	CILQCASP
CILCLOAP	CILFLGRP	CILQTDEP
CILCPERP	CILFMVTP	CILQTDLP
CILCPLAS	CILFSFHP	CILQTDQP
CILCPPPLP	CILITPDP	CILQTDSP
CILCPPTMPL	CILLODPP	CILQTDTP
CILCPRMP	CILPAPHP	CILQTDZP
CILCSALP	CILPAPSP	CILQTSSP
CILCSSEP	CILPDCNP	CILQTSUP
CILCSVAP	CILPDCSP	CILRCMAP
CILDATA	CILPEPLP	CILRENGP
CILDIVET	CILPEQAP	CILRRSMP
CILDIVEXT	CILPEVTP	CILRRTCP
CILECBLP	CILPICCHAR	CILRRTSP
CILEFKRP	CILPIDIV	CILRRTVP
CILEFLDP	CILPILANG	CILRRVMP
CILEMNUP	CILPIREL	CILSACHG
CILEMOBP	CILPITXNREL	CILSTEXTITEM
CILENAVP	CILPOLMO	CILTACRP

Application Service	Application Service	Application Service
CILENVOP	CILPPAYP	CILTALGP
CILERPTP	CILPPCAN	CILTALTP
CILESVCP	CILPPTSP	CILTAMGP
CILETBPL	CILPQADP	CILTAMTP
CILEUIZP	CILPRCITMREL	CILTAPAP
CILEXCHRATE	CILPRICELISTCHAR	CILTAPFP
CILFAFHP	CILPRIITEM	CILTAPRP
CILTAPSP	CILTCQTP	CILTOETP
CILTAROP	CILTCURP	CILTOOPTP
CILTARTP	CILTCUSP	CILTORAP
CILTASGP	CILTDARP	CILTPCRP
CILTATCP	CILTDASP	CILTPDRP
CILTATPP	CILTDACP	CILTPHTP
CILTATYP	CILTDCLP	CILTPIFP
CILTBCRP	CILTDIRP	CILTPKGP
CILTBCTP	CILTDPRP	CILTPMDP
CILTBFFP	CILTDSTP	CILTPPTP
CILTBFVP	CILTDWPP	CILTPRTP
CILTBIMP	CILTDWTP	CILTPSDP
CILTBLCP	CILTEBRP	CILTPSTP
CILTBLLP	CILTECRP	CILTPTRP
CILTBKNP	CILTFNDP	CILTPYTP
CILTBRTP	CILTFRQP	CILTQRTP
CILTBSTP	CILTFWLP	CILTRGLP
CILTBTCP	CILTGLDP	CILTRLEP
CILTBTRP	CILTIIDTP	CILTRSCP
CILTBXTP	CILTINCP	CILTRRTYP
CILTCAMP	CILTINSF	CILTSATP
CILTCATP	CILTIITP	CILTSCLP
CILTCCCP	CILTLIDP	CILTSCYP
CILTCCTP	CILTLETP	CILTSICP

Application Service	Application Service	Application Service
CILTCHTP	CILTLKFP	CILTSOMP
CILCIDP	CILTLNGP	CILTSOPP
CILTCLGP	CILTMCRP	CILTSQIP
CILTCLRP	CILTMHTP	CILTSQRP
CILTCLWP	CILTMSPG	CILTSTMP
CILTCNTP	CILNUXP	CILTSVTP
CILTCOCP	CILTOCRP	CILTSWLP
CILTTACP	CILWDWNP	CILYROBP
CILTTAXP	CILWJSDP	CILZAFQP
CILTTGRP	CILWJSSP	CILZAUQP
CILTTMRP	CILWNUPP	CILZFNCP
CILTTMTP	CILWNUSP	CILZPORP
CILTTNSP	CILWPROP	CILZRBP
CILTTNTP	CILXADPP	CILZRPH
CILTTOUP	CILXAIEP	CILZRPOP
CILTRAP	CILXAIIP	CILZRPT
CILTTTMP	CILXCLSP	CILZSCR
CILTTZNP	CILXCONP	CILZSCZ
CILTUOMP	CILXENHP	CILZTLZ
CILTRPP	CILXFRMP	CILZZOHP
CILTUSCP	CILXGRPP	CILZZONP
CILTUSEP	CILXJDBP	CIL_FAVORITES
CILTUSGP	CILXJMSP	CIPOLICY
CILTWCTP	CILXJSVP	CIPOLPERRL
CILTWDCP	CILXNDNP	CIPOLPERROLE
CILTWETP	CILXOPTP	CIPOLREINSTRSN
CILTWPTP	CILXRCVP	CIPRICEACCOUNT
CILTWSCP	CILXRTTP	CIREC
CILTWSDP	CILXSENP	CIRECCUSTSUB
CILTXNDETAIL	CILXSVXP	CIRECON
CILTXNSRC	CILXTPCP	CIRECONDTL

Application Service	Application Service	Application Service
CILTXNSRCD	CILXXSCP	CIRECONSEG
CILTXNSRCL	CILXXUPP	CIRECPRTL
CILUPFTS	CILYASTP	CISACHG
CILVFVDP	CILYDBPP	CISACHGTYPE
CILVFVSP	CILYDFQP	CISATYCHG
CILVVLEP	CILYDPIP	CIVARIANCE
CILVVLSP	CILYENRP	CNCLRSN
CTXZONE	F1MGDIMP	FILETYPE
DIVS	F1MGDIMS	FWLCTDEP
DIV_PRICEITEMS	F1MGOIMP	FWLFACTP
DIV_PRICELISTS	F1MGPLNM	FWLSTRJP
F1-APAYEXPCRTYPEBOAS	F1MGPLNS	FWLTBELP
F1-ATTACHMENTBOAS	F1MGREQM	FWLTBOJP
F1-DECRPTBOAS	F1MGREQS	FWLTBSVP
F1-DFLTAPS	F1MIGRDEXP	FWLTDARP
F1-DFLTS	F1MIGRDIMP	FWLTEXSP
F1-EXPUSERSREQBOAS	F1MIGRDS	FWLTMGCT
F1-GENPROC	F1MIGROBJ	FWLTOMTP
F1-MIGROBJIMP	F1MIGRPLAN	FWLTSCHP
F1-STASKTYPE	F1MIGRREQ	FWLTUIMP
F1-SVCTASK	F1MIGRTIMP	FWLXOUTP
F1-SYNCREQ	F1MIGRTX	FWLZDEXP
F1-SYNCREQIN	F1MTXIMP	FWLZWLP
F1-SYNCREQUESTBOAS	F1REQ	GOTOREC
F1-WEBSVCBOAS	F1REQTYP	LISTBILLVIEW
F1ADMIN	F1STRDIS	PERTREE
F1ATTACH	F1STREAS	POLICYCANRSN
F1ATTACHMENT	F1SUBRQQ	RECDTSTA
F1CATTCH	F1SYNCRM	RECON
F1CONFIGLOG	F1SYNCRQ	RECONDTL
F1DEBUG	F1TBLEXC	RSTRSN

Application Service	Application Service	Application Service
F1EXLKP	F1UIZONE	SACHGLNK
F1EXLKPS	F1USERLOG	SATYPCHG
F1LCAMRP	F1WBSVCM	SATYPES
F1LEXTLKUP	F1WBSVCS	F1_BTST
F1LTAMTP	F1WEBSVC	F1_USRFAVSCH
F1MGDEXP	F1MGDEXS	C1LASGN
C1BCHGUPLREQ	C1DELCTL	C1PIASGN
C1BILLCYCLEUPDTUPL	C1ELGPA	C1PLASGNM
C1CONTRIDERUPDTUPL	C1GETELIGPT	C1REFUPLREQ
C1DCDTLC	C1HOLDUPLREQ	C1UPLDRQ
C1UPLREQ	C1WOUPLREQ	CILCPASP
C1-PROSPECTCRET	C1ADDRS	C1DSPTTY
C1ACRLCL	C1ADDRSBO	C1PAREQ
C1ACRLTP	C1ADDRSRC	C1PARQMN
C1ADDRDP	C1DSPT	C1PARQTY
C1ADDRDTL	C1DSPTRQ	C1PI
C1ADDRESS	C1DSPTRT	C1PL
C1PRICEASGN	C1_DSPT_REQ	F1-ARQPR
F1-AVALG	F1-LKPIN	F1-SICRL
F1-AVBT	F1-MGDIM	F1-SRCRL
F1-AVMO	F1-MGDPR	F1-SRLRQ
F1-AVTBL	F1-MGOAP	F1-STATSM
F1-AVTD	F1-MGOPR	F1-STCTRL
F1-BFCRL	F1-MGTAP	F1-STKDF
F1-BSFLG	F1-MGTPR	F1-STKTR
F1-BUNPR	F1-NDPUR	F1-SUBRQ
F1-DTDOM	F1-ORCRL	F1-SYNEF
F1-FCTRN	F1-OUCRL	F1-SYNIL
F1-FKVBP	F1ACGRPM	F1-SYNRQ
F1-FLUSH	F1ACGRPQ	F1-SYSRQ
F1-ILMIN	F1-REQTY	F1-TDCRL

Application Service	Application Service	Application Service
F1-LANG	F1-REVPR	F1-TDEER
F1-LDAP	F1-SAKRQ	F1-XMLPG
C1-DISC-REPT	C1-PTD-CAL	C1APAYRT
C1OFPRED	C1OFPREQ	C1PARAM
C1PERS	C1PERSDP	C1PERSON
C1SRCAPP	C1VIEWRL	C1_INVCN
C1_PRODUCT	C1_RLTPM	C1_RLTWV
CILRULTP	C1-PRRLTYP	C1ENTITYREPORT
C1PROAPP	C1PRTYP	C1_PRICE
CIPRICEPARM	C1-CUSTREGTEMPL_SERV	C1-CUSTREGTYPE
C1-GETPRICINGENTITY	C1MASPRI	C1MPRISR
C1RETMPL	F1OUMSTQ	F1OUMSTY
PRICECOMPSEQ	C1CREGSR	C1CTR GHC
C1CUREG	C1CURETY	C1CUSTREG
C1CUSTRG	AUDITEVENT	C1-AUDEVTYPE
C1-HEALTHCARE	C1ADEVSR	C1AUDEV
C1AUDTY	C1RETMPLHC	C1ENTDTL
C1INREQ	C1INRETY	C1INVRED
GETDEALTYPE	C1-FIELDMAP	C1-FIELDMAP_SERV
C1-TNC	C1FLDMAP	C1RELSTR
C1TERCO	C1TERMNCO	C1TNCSR
C1_MEMRL_SUBT	PRICEITEM_SERV	C1MEIDTY
C1BENSTY	C1BUSRD	F1ALGQ
F1ALGTQ	F1APPSVM	F1APPSVQ
F1BOQ	F1BSVQ	F1BTCHQ
F1CHRTYP	F1CHRTYQ	F1DTARQ
F1FCFGQ	F1FIELD	F1FKRFQ
F1FLDQ	F1LKUPQ	F1MANCQ
F1MENUQ	F1MOQ	F1MSG
F1MSGC	F1MSGQ	F1NAVKQ

Application Service	Application Service	Application Service
F1NAVOQ	F1PRTL	F1PRTLQ
F1SCRQ	F1TABLE	F1TBLQ
F1TDDASH	F1TMZNM	F1TODO
F1TODOEQ	F1UIMPQ	F1WRKCAL
F1WRKCLQ	F1ZONE	F1ZONEQ

Appendix C : Changing the DB User Password

If you have changed the database user password, you need to execute the following steps before installing the rollup pack for Oracle Utilities Application Framework Version 4.4.0.3.0:

1. Download and apply the single fix available for Bug 22505470 - PATCHES APPEND EXTRA SPACE TO STRINGS AND ADD DB SERVICE CONNECTION SUPPORT on the application and database environments.
2. Perform the following steps on the application environment:
 - a. Change the DB Name using the `configureEnv` command.
 - b. Execute the `initialSetup` utility using the following command:

AIX, Linux:

```
$SPLBASE/bin/initialSetup.sh
```

Windows:

```
%SPLBASE%\bin\initialSetup.cmd
```

- c. Execute the `invokeDBUpdatePatch` utility to change the database user name and password using the following command:

AIX, Linux:

```
$SPLBASE/bin/invokeDBUpdatePatch.sh -b
```

Windows:

```
%SPLBASE%\bin\invokeDBUpdatePatch.cmd -b
```

Appendix D : New Objects in the Oracle Utilities Application Framework V4.4.0.3.0 Database

This section lists the objects that are newly added in the Oracle Utilities Application Framework V4.4.0.3.0 database. These objects are classified under the following two sections:

- [Schema Changes](#)
- [New System Data](#)

D.1 Schema Changes

This section lists schema related changes made in the Oracle Utilities Application Framework V4.4.0.3.0 database.

D.1.1 New Tables

The following tables are newly added in the Oracle Utilities Application Framework V4.4.0.3.0 database:

Table	Description
CI_ACC_GRP_ROLE	Access Group Role
F1_ACTION_METHOD	Action Method
F1_ACTION_METHOD_CHAR	Action Method Characteristic
F1_ACTION_METHOD_L	Action Method Language
F1_COLOR_OPT	Color Option
F1_COLOR_OPT_ITEM	Color Option Item
F1_COLOR_OPT_L	Color Option Language
F1_DATA_EXPORT_CTRL	Data Export Control
F1_DATA_EXPORT_CTRL_LOG	Data Export Control Log
F1_DATA_EXPORT_CTRL_LOG_PARM	Data Export Control Log Parameters
F1_FILE_INT_REC	File Integration Record
F1_FILE_INT_REC_ALG	File Integration Record Algorithm
F1_FILE_INT_REC_L	File Integration Record Language
F1_FILE_INT_TYPE	File Integration Type
F1_FILE_INT_TYPE_L	File Integration Type Language
F1_INSIGHT_GRP	Insight Group
F1_INSIGHT_GRP_CHAR	Insight Group Characteristics

Table	Description
F1_INSIGHT_GRP_L	Insight Group Language
F1_INSIGHT_GRP_TYPE	Insight Group Type
F1_INSIGHT_GRP_VISUAL_STR	Insight Group Valid Visual Structure
F1_INSIGHT_TYPE	Insight Type
F1_INSIGHT_TYPE_ALG	Insight Type Algorithm
F1_INSIGHT_TYPE_CHAR	Insight Type Characteristic
F1_INSIGHT_TYPE_L	Insight Type Language
F1_INSIGHT_TYPE_USER_ACT	Insight Type User Action
F1_INSIGHT_TYPE_USER_ACT_ALG	Insight Type User Action Algorithm
F1_INSIGHT_TYPE_VISUAL_SETTING	Insight Type Visual Setting
F1_MD_BI_TBL	Analytics Table
F1_MD_BI_TBL_FLD	Analytics Table / Field
F1_MD_BI_TBL_L	Analytics Table Language
F1_MO_UPD	Data Export Update
F1_TREE	Tree
F1_TREE_L	Tree Language
F1_TREE_NODE	Tree Node
F1_TREE_NODE_ALG	Tree Node Algorithms
F1_TREE_NODE_L	Tree Node Language

D.1.2 Added Views

The following views are newly added in the Oracle Utilities Application Framework V4.4.0.3.0 database:

View	Description
F1_CAL_FISC_PERIOD_D	Fiscal Calendar Period Dimension View
F1_CAL_FISC_QUARTER_D	Fiscal Calendar Quarter Dimension View
F1_CAL_FISC_YEAR_D	Fiscal Calendar Year Dimension View
F1_CAL_MONTH_D	Calendar Month Dimension View
F1_CAL_QUARTER_D	Calendar Quarter Dimension View
F1_CAL_WEEK_D	Calendar Week Dimension View
F1_CAL_YEAR_D	Calendar Year Dimension View

D.1.3 Dropped Tables

None

D.1.4 Unsupported Tables

None

D.1.5 Added Columns

The following columns are newly added in the Oracle Utilities Application Framework V4.4.0.3.0 database:

Table	Column	Column Description	Required (Yes or No)
CI_BATCH_INST	END_DTTM	End Date/Time	No
	FILE_DETAILS	File Details	No
	START_DTTM	Start Date/Time	No
CI_BATCH_JOB	SUBMIT METH FLG	Submission Method	Yes
	SUBMIT_USER_ID	Submission User	Yes
CI_CHAR_TYPE	FLD_NAME	Field	No
CI_MD_FLD_L	CONTEXT_LABEL1	Context Label 1	Yes
	CONTEXT_LABEL2	Context Label 2	Yes
	CONTEXT_LABEL3	Context Label 3	Yes
	CONTEXT_LABEL_TYPE1	Context Type 1	Yes
	CONTEXT_LABEL_TYPE2	Context Type 2	Yes
	CONTEXT_LABEL_TYPE3	Context Type 3	Yes
	OVRD_CONTEXT_LABEL1	Override Label 1	Yes
	OVRD_CONTEXT_LABEL2	Override Label 2	Yes
	OVRD_CONTEXT_LABEL3	Override Label 3	Yes
CI_MD_TBL	KEY_PREFIX_FLD_NAME	Inherited Key Field	No
CI_TD_ENTRY_OPEN_VW	DKSQ1	Drill Key Sequence 1	No
	DKSQ2	Drill Key Sequence 2	No
	DKSQ3	Drill Key Sequence 3	No
	DKSQ4	Drill Key Sequence 4	No
	DKSQ5	Drill Key Sequence 5	No
	SKSQ1	Sort Key Sequence 1	No
	SKSQ2	Sort Key Sequence 2	No

Table	Column	Column Description	Required (Yes or No)
	SKSQ3	Sort Key Sequence 3	No
	SKSQ4	Sort Key Sequence 4	No
	SKSQ5	Sort Key Sequence 5	No
F1_CAL_FISC_PERIOD_D	F1_FISC_QUARTER_FLG	Fiscal Quarter	No
	F1_FISC_QUARTER_END_DT	Fiscal Quarter End Date	No
	F1_FISC_QUARTER_KEY	Fiscal Quarter Key	No
	F1_FISC_QUARTER_START_DT	Fiscal Quarter Start Date	No
	F1_FISC_QUARTER_IN_YEAR	Fiscal Quarter in Year	No
	F1_FISC_YEAR	Fiscal Year	No
	F1_FISC_YEAR_END_DT	Fiscal Year End Date	No
	F1_FISC_YEAR_START_DT	Fiscal Year Start Date	No
	F1_FISC_PERIOD_FLG	Period	No
	F1_FISC_PERIOD_END_DT	Period End Date	No
	F1_FISC_PERIOD_KEY	Period Key	No
	F1_FISC_PERIOD_START_DT	Period Start Date	No
	F1_FISC_PERIOD_IN_QUARTER	Period in Quarter	No
	F1_FISC_PERIOD_IN_YEAR	Period in Year	No
F1_CAL_FISC_QUARTER_D	F1_FISC_QUARTER_FLG	Fiscal Quarter	No
	F1_FISC_QUARTER_END_DT	Fiscal Quarter End Date	No
	F1_FISC_QUARTER_KEY	Fiscal Quarter Key	No
	F1_FISC_QUARTER_START_DT	Fiscal Quarter Start Date	No
	F1_FISC_QUARTER_IN_YEAR	Fiscal Quarter in Year	No
	F1_FISC_YEAR	Fiscal Year	No
	F1_FISC_YEAR_END_DT	Fiscal Year End Date	No
	F1_FISC_YEAR_START_DT	Fiscal Year Start Date	No
F1_CAL_FISC_YEAR_D	F1_FISC_YEAR	Fiscal Year	No
	F1_FISC_YEAR_END_DT	Fiscal Year End Date	No
	F1_FISC_YEAR_START_DT	Fiscal Year Start Date	No
F1_CAL_MONTH_D	F1MONTH_ABBR	Month	No
	F1_MONTH_END_DT	Month End Date	No

Table	Column	Column Description	Required (Yes or No)
F1_CAL_MONTH_D	F1_MONTH_KEY	Month Key	No
	F1_MONTH_START_DT	Month Start Date	No
	F1_MONTH_IN_QUARTER	Month in Quarter	No
	F1_MONTH_IN_YEAR	Month in Year	No
	F1_CAL_QUARTER_FLG	Quarter	No
	F1_CAL_QUARTER_END_DT	Quarter End Date	No
	F1_CAL_QUARTER_KEY	Quarter Key	No
	F1_CAL_QUARTER_START_DT	Quarter Start Date	No
	F1_CAL_QUARTER_IN_YEAR	Quarter in Year	No
	F1_CAL_YEAR	Year	No
	F1_CAL_YEAR_END_DT	Year End Date	No
	F1_CAL_YEAR_NAME	Year Name	No
	F1_CAL_YEAR_START_DT	Year Start Date	No
F1_CAL_QUARTER_D	F1_CAL_QUARTER_FLG	Quarter	No
	F1_CAL_QUARTER_END_DT	Quarter End Date	No
	F1_CAL_QUARTER_KEY	Quarter Key	No
	F1_CAL_QUARTER_START_DT	Quarter Start Date	No
	F1_CAL_QUARTER_IN_YEAR	Quarter in Year	No
	F1_CAL_YEAR	Year	No
	F1_CAL_YEAR_END_DT	Year End Date	No
	F1_CAL_YEAR_NAME	Year Name	No
	F1_CAL_YEAR_START_DT	Year Start Date	No
F1_CAL_WEEK_D	F1_WEEK_END_DT	Week End Date	No
	F1_WEEK_KEY	Week Key	No
	F1_WEEK_NAME	Week Name	No
	F1_WEEK_START_DT	Week Start Date	No
	F1_WEEK_IN_YEAR	Week in Year	No
F1_CAL_YEAR_D	F1_CAL_YEAR	Year	No
	F1_CAL_YEAR_END_DT	Year End Date	No
	F1_CAL_YEAR_NAME	Year Name	No

Table	Column	Column Description	Required (Yes or No)
	F1_CAL_YEAR_START_DT	Year Start Date	No
F1_IWS_SVC	IWS_REST_VER_FLG	REST Engine Version	No
F1_LGCY_OBJ	LGCY_CAT_FLG	Category	Yes
	CHANGE_REF_NAME	Change Reference	No
F1_MIGR_DATA_ST_TBL	RECORD_COUNT	Record Count	No
SC_USER	DASHBOARD_LOC_FLG	Dashboard Location	No
	DASHBOARD_STATE_FLG	Dashboard State	No

D.1.6 Dropped Columns

None

D.1.7 Dropped Lookups

The following lookups are removed from the Oracle Utilities Application Framework V4.4.0.3.0 database:

Field	Description
XAI_COMMAND_FLG	Display Registry
	MPL Refresh Executer
	MPL Refresh Receiver
	MPL Refresh Sender
	MPL Start Receiver
	MPL Stop
	MPL Stop Receiver
	MPL Trace Off
	MPL Trace On
	Refresh Code and Description
	Refresh Registry
	Refresh Schema
	Refresh Service
	Refresh XSL
	Trace Off
	Trace On

Field	Description
	XAI Trace Clear
	XAI Trace Swap

D.1.8 Column Format Change

The format of the following columns is changed in the Oracle Utilities Application Framework V4.4.0.3.0 database:

Table	Column	From	To
CI_ALG_PARM	ALG_PARM_VAL	VARCHAR2(2000)	VARCHAR2(32767)
CI_ZONE_PRM	ZONE_PARM_VAL	VARCHAR2(4000)	VARCHAR2(32767)

D.2 New System Data

The system data is used to configure various features in Oracle Utilities Application Framework. This section lists the system data that is newly added in the Oracle Utilities Application Framework V4.4.0.3.0 database.

D.2.1 Algorithms

The following algorithms are newly added in the Oracle Utilities Application Framework V4.4.0.3.0 database:

Algorithm	Description
F1-ACCGRPBO	Determine Access Group BO
F1-APPSVCBO	Determine Application Service BO
F1BTMONPR	Batch Monitoring - Create Log / Check Database Operations
F1-BTMON-SR	Batch Monitoring Select Records
F1CHARMAPINF	Characteristic Mapping Information
F1CHARMAPVAL	Validate Characteristic Mapping Configuration
F1CHRMAPP	Characteristic Mapping - Default Rules
F1-CHRTYPBO	Determine Characteristic Type BO
F1CLROPTINFO	Color Option Information
F1COLORINFO	Color Information
F1DAEXCNAUD	Data Export Audit
F1DAEXCNVAL	Data Export Validation
F1DEXCTRLINF	Data Export Control Information
F1-FILEX-PR	Extract File Integration Record

Algorithm	Description
F1-FLDBO	Determine Field BO
F1HEXCOLOR	Validate Hex Color Code
F1LKUPINF	Lookup Information
F1MGPRORDINF	Migration Import Processing Order Information
F1-MO-REGCHN	Capture Change for Ongoing Export
F1-MSGBO	Determine Message BO
F1-MSGCBO	Determine Message Category BO
F1MSGCINFO	Message Category Information
F1NAVKINFO	Navigation Key Information
F1-NEXT-TDNS	Get Next To Do Assignment - No Skill Match
F1-NEXT-TDSK	Get Next To Do Assignment - Match Skills
F1-PORTALBO	Determine Portal BO
F1PORTALPST	Maintain Portal Artifacts
F1RELTDINFO	Related To Do Count
F1SFHINTINFO	Search Filter Hint Information
F1-TABLEBO	Determine Table BO
F1-TMZNBO	Determine Time Zone BO
F1-TODOBO	Determine To Do Entry BO
F1UNSMDFVAL	Unsupported Metadata Validation
F1-UNSPRTD	Unsupported Metadata
F1USRCHINF	Unified Search Information
F1VALINSGVS	Validate Insight Group Visual Structure
F1-WRKCALBO	Determine Work Calendar BO
F1-ZONEBO	Determine Zone BO

D.2.2 Algorithm Types

The following algorithm types are newly added in the Oracle Utilities Application Framework V4.4.0.3.0 database:

Algorithm Type	Description
F1BTMONPR	Batch Monitoring - Create Log / Check Database Operations
F1CHARMAPINF	Characteristic Mapping Information
F1CHARMAPVAL	Validate Characteristic Mapping Configuration

Algorithm Type	Description
F1CHRMAPP	Characteristic Mapping - Default Rules
F1CLROPTINFO	Color Option Information
F1COLORINFO	Color Information
F1DAEXCNAUD	Data Export Audit
F1DAEXCNVAL	Data Export Validation
F1DEXCTRLINF	Data Export Control Information
F1-FILEX-PR	File Integration Record Extraction
F1HEXCOLOR	Validate Hex Color Code
F1LKUPINF	Lookup Information
F1MGPRORDINF	Migration Import Processing Order Information
F1-MO-REGCHN	Capture Change for Ongoing Export
F1MSGCINFO	Message Category Information
F1NAVKINFO	Navigation Key Information
F1PORTALPST	Maintain Portal Artifacts
F1PRFMDELAY	Perform Delay of Processing
F1RELTDINFO	Related To Do Count
F1SFHINTINFO	Search Filter Hint Information
F1UNSMDVAL	Unsupported Metadata Validation
F1USRCHINF	Unified Search Information
F1VALINSGVS	Validate Insight Group Visual Structure

D.2.3 Zones

The following zones are newly added in the Oracle Utilities Application Framework V4.4.0.3.0 database:

Zone	Description
F1-ACCGRP	Access Group
F1-ACCGRPQ	Access Group Search
F1-ACCGRPQ1	Access Group Information
F1-ACMTHD	Action Method
F1-ACMTHLIST	Action Method List
F1-ALGSRCHQ	Algorithm Search
F1-ALGTYPQ	Algorithm Type Search

Zone	Description
F1-ALGTPQ1	Algorithm Type Information
F1-ANTBCHAR	Analytics Table's Characteristics Tables
F1-APPSVC	Application Service
F1-APPSVCQ1	Application Service Information
F1-BOSRAIN	Additional Information
F1-BOSRCHQ	Business Object Search
F1-BPASCSRCH	BPA Script Search
F1-BTCTLQ2	Additional Information
F1-CHKRUNBAT	Check if Batch is Running
F1-CHMPSEQ	Characteristic Mapping Sequence Rules
F1-CHTPM	Characteristic Type
F1-CHTPQ	Characteristic Type Search
F1-CHTPQ1	Characteristic Type Information
F1-CNVENTBTC	Batch Controls
F1-CNVENTDUP	Duplicate Keys
F1-CNVENTERR	Validation Errors
F1-CNVENTERS	Error Summary
F1-CNVENTQ	Conversion Entity Search
F1-CNVENTQ1	Conversion Entity Information
F1-CNVENTTBL	Tables
F1-DECEXPELG	Eligible Entities
F1-DECEXPENT	Export Entities
F1-DEXPCNTS	Data Export Control Search
F1-DSICONSRH	Display Icon Reference Search
F1-FILINTDSP	File Integration Type
F1-FILINTYQ	File Integration Type Search
F1-FILINTYQ1	File Integration Type Information
F1-FILRECLST	File Integration Records
F1-FLDSRCHQ2	Additional Information
F1-GENEXBACN	Generalized Initial Export Batch Controls
F1-INHKEY	Get Inheritance Key

Zone	Description
F1-LKUPQ	Lookup Search
F1-LKUPQ1	Lookup Information
F1-MANINSTYP	Retrieve Visual Structure lookup values
F1-MANTDTYPE	Retrieve Manual To Do Types
F1-MESSAGES	Messages
F1-MIGRREQCB	Migration Request - Entities Exist
F1-MIGRREQCL	Migration Request Entities
F1-MOBTCHCD	MO Batch Codes
F1-MOCNVBAT	MO Conversion Batch Codes
F1-MOCNVBCR	Conversion Batch Controls
F1-MOQ1	Maintenance Object Information
F1-MOQ2	Additional Information
F1-MOTABLES	Tables for a Maintenance Object
F1-MOTRNS	MOs that are Translatable (Internal Use Only)
F1-MSGSRCHC	Message Category Information
F1-MSGSRCHM	Message Information
F1-MSGSRCHQ	Message Search
F1-RELATEDTD	Related To Do Entries
F1-RELDCNT	Related To Do Entries Count
F1-SCRQ	Script Search
F1-SDR-HC	Schemas with Potential Hard-coded Labels
F1-SDR-MO	Maintenance Object ILM Configuration
F1-SDR-SC	Script Configuration
F1-SDR-ZN	Zone Configuration
F1-SELZNTYPE	Select Zone Type
F1-SPEEXELMO	MOs Eligible for Specialized Export
F1-TBLCONST	Table Constraints
F1-TBLCSTREF	Referred By Constraints
F1-TBLFLDS	Fields
F1-TBLMO	Maintenance Object for Table
F1-TBLRECCNT	Table Record Count

Zone	Description
F1-TBLSRCH2	Additional Information
F1-TBLSRCHQ	Table Search
F1-TDCHARS	To Do Characteristics
F1-TDEM	To Do Entry
F1-TDEQ1	To Do Entry Identifier
F1-TDEQ2	To Do Type
F1-TDEQRY	To Do Entry Search
F1-TODOLOG	To Do Log
F1-TREEM	Tree
F1-TREENODE	Tree Node
F1-TREEQ	Tree Search
F1-TREEQ1	Tree Information
F1-UIMPAI	Additional Information
F1-UNSADD	Objects to Add
F1-UNSLOG	Log
F1-UNSMDEX	Unsupported Metadata Exists
F1-UNSMOPK	MO / PK
F1-UNSPMD	Unsupported Metadata
F1-UNSPMDQ	Unsupported Metadata Search
F1-UNSPMDQ1	Unsupported Metadata Information
F1-UNSSDL	System Data Log
F1-USRTDVAL	User Valid for Role
F1-WORKCALQ	Work Calendar Search
F1-WRKCAL	Work Calendar
F1-WRKCALHOL	Work Calendar Holidays
F1-ZONESRCHQ	Zone Search
F1-ZONSRCH2	Additional Information
F1ALGQ1	Algorithm Information
F1ALGQ2	Additional Information
F1ANLDEXFLDS	Excluded Fields
F1ANLDMNCHR	Characteristic Mapping

Zone	Description
F1ANLDMNFDO	Fields
F1ANLDMNINFO	Dimensions
F1ANLFACTFDO	Fields
F1ANLLGDM	Logical Dimensions
F1ANLREFBY	Referenced By
F1ANLYDMN	Analytics Table
F1ANLYTBLQ	Analytics Table Search
F1ANLYTBLQ1	General Information
F1BSVQ1	Business Service Information
F1BSVQ2	Additional Information
F1BSVQS	Business Service Search
F1CHARMPQ	Characteristic Mapping Search
F1CHARMPQ2	Characteristic Mapping Information
F1COLORLST	Color Option List
F1COLOROPT	Color Option
F1DEXCNTL	Data Export Control
F1DEXCNTRLOG	Data Export Control Log
F1DTARAI	Additional Information
F1DTARQS	Data Area Search
F1ETLQ1	ETL Mapping Control Information
F1FCFGQ1	Feature Configuration Information
F1FCFGQS	Feature Configuration Search
F1FKRFQ1	Foreign Key Reference Information
F1FKRFQS	Foreign Key Reference Search
F1FLDM	Field
F1FLDTF	Tables Using Field
F1INSGPLST	Insight Group List
F1INSTGRP	Insight Group
F1INSTYLS	Insight Type List
F1INSTYPE	Insight Type
F1MANCQS	Managed Content Search

Zone	Description
F1MENUQ1	Menu Information
F1MENUQS	Menu Search
F1MEXENS	Entity Summary
F1MEXENTEX	Migration Data Set Export Entities Exist
F1MGDENS	Entity Summary
F1MGDEXS2	Identifier
F1MGDIMS3	Identifier
F1MGRQCOEN	Check if Migration Request Contains Entity
F1MIGRQCOLEN	Collect Entity
F1MSG	Message
F1MSGC	Message Category
F1MTXENS	Entity Summary
F1NAVQK1	Navigation Key Information
F1NAVQKS	Navigation Key Search
F1NAVOQ1	Navigation Option Information
F1NAVOQS	Navigation Option Search
F1OPTFK	Get Option FK Reference Details
F1PRGCOM	Program Component Search
F1PRTLAPS	Portal Additional Display Details
F1PRTLCTXZ	Context Sensitive Zones
F1PRTLM	Portal
F1PRTLOPT	Options
F1PRTLQS	Portal Search
F1PRTLTABS	Tabs
F1PRTLTABSE	Main portal's tab portals
F1PRTLTMS	Main portals referencing a tab portal
F1RELINSGRPS	Related Insight Groups
F1RELINSTY	Related Insight Types
F1SCRQ1	Script Information
F1SCRQ2	Step Information
F1TBLCLSCST	Table fields for defining a constraint

Zone	Description
F1TBLERD	Table ERD Information
F1TBLERDM	Entity Relationship Diagram
F1TBLM	Table
F1TBLREFCST	Referring Constraint Search
F1TDDAGE	To Do Entries by Days Old
F1TDDPRI	To Do Entries by Priority
F1TDDROLE	To Do Entries by Role
F1TDDSTAT	To Do Entries by Status
F1TDDTYPE	To Do Entries by Type
F1TIMEZONEL	Time Zone List
F1TREENDS	Other Tree Nodes
F1TREENODES	Tree Nodes
F1TZONEM	Time Zone
F1UIMPQS	UI Map Search
F1UNSRCHS	Unified Searches
F1VALINSTYPE	Valid Insight Types for Insight Group
F1ZNFLTRS	Filters
F1ZNMQRYOPTS	Query Options
F1ZNPRMS	General Parameters
F1ZNPRMSEDT	General Parameters Maintenance
F1ZNSQLPARMS	SQL Parameters Maintenance
F1ZNSQLPRMS	SQL Configuration
F1ZNSQLS	SQLs
F1ZNUSED	Zone References
F1ZONEM	Zone

D.2.4 New Zones In Existing Portals

The following new zones are added to the existing portals in the Oracle Utilities Application Framework V4.4.0.3.0 database:

Portal	Zone	Zone Description
CI_DASHBOARD	F1MIGRQCOLEN	Collect Entity
F1ESRCFG	F1-GENEXBACN	Generalized Initial Export Batch Controls

Portal	Zone	Zone Description
	F1-MOCNVBTCR	Conversion Batch Controls
F1MGDEXP	F1MEXENS	Entity Summary
F1MGDIMP	F1MGDENS	Entity Summary
F1MGREQM	F1-MIGRREQCL	Migration Request Entities
F1MTXIMP	F1MTXENS	Entity Summary
F1SYSDRV	F1-SDR-MO	Maintenance Object ILM Configuration
	F1-SDR-SC	Script Configuration
	F1-SDR-ZN	Zone Configuration
F1TBLEXC	F1-SDR-HC	Schemas with Potential Hard-coded Labels

D.2.5 UI Maps

The following UI maps are newly added in the Oracle Utilities Application Framework V4.4.0.3.0 database:

UI Map	Description
F1-AlgQueryFilter	Algorithm Query Filter
F1-AnalyticsFieldInfo	Analytics Table
F1AnDmChSS	Dimension Characteristic Mapping
F1-CharacteristicsMaint	Maintain Characteristics Input
F1-CheckInstallModeFragment	Function to check if install mode is cloud
F1-ColorDisplay	Color Preview Display
F1-ColorMaint	Color Maintenance with Preview
F1-ConversionEntityInfoFilter	Conversion Entity Search by Info - Filter
F1-DataExportControlUserLogAdd	Data Export Control - Add User Log Entry
F1-DEChartVisOptions	Data Explorer Chart Visualization Options
F1-FieldAddtlFilter	Field Additional Attribute Filter
F1-FieldHelpText	Field Help Text Elements
F1-FileIntRecordLayoutDisp	File Integration Record Layout Display
F1-HelpTextDisp	Help Text Display
F1-InsightPreview	Insight Preview
F1-InsTypeVisualSettingsDispla	Insight Type Visual Settings - Display
F1-InsTypeVisualSettingsInput	Insight Type Visual Settings - Maintenance
F1-MaintainOptionsInp	Maintain Options - Functions

UI Map	Description
F1-MessageCategoryMessages	Messages Maintenance
F1-MigrationReqCollectEntity	Collect Entity - Dashboard Zone
F1-MigrDataSetBatchStatus	Migration Data Set Batch Status
F1-MigrReqCriteriaBsdSrchFltr	Migration Request - Criteria Based Filter
F1-MOPKforPage	MO / PK for current page
F1-MOSearchFilter	Maintenance Object Search Filter
F1-NavOptQueryFilter	Navigation Option Query Filter
F1-OJETLIBSR	OJET libraries (Redwood Version)
F1-OverrideDescription	Description Display Only
F1-OverrideMessageText	Message Text Display Only
F1-PortalMainDisp	Portal Additional Fields
F1-PortalMainInp	Portal Additional Fields
F1-PortalOptionsInp	Portal Options Input
F1-PortalRecordInfo	Portal Record Information
F1-PortalTabsEdit	Portal Tabs Edit
F1-RecordInfoREST	Inbound REST Web Service Record Info
F1-RelatedObject	Related Object Display
F1-RelatedToDoInformation	To Do Entry - Related To Do Information
F1-RetrieveMoOptionExpBatCtrl	Display MO Export Batch Control
F1-TableAuditInp	Table Audit Program
F1-TableConstEdit	Table Constraint Maintenance
F1-TableConstFieldsEdit	Table Constraint Fields Maintenance
F1-TableERD	Table ERD
F1-TableERDIInc	Table ERD Functions
F1-TableFieldHelpText	Table Field Help Text Elements
F1-TableFieldsEditAll	Table Fields Maintenance
F1-TableMODisp	Table Maintenance Object Display
F1-ToDoActions	To Do Entry Actions
F1-ToDoAddInfo	To Do Entry - Add Information
F1-ToDoBatchDisplay	To Do Entry - Batch Process Display
F1-ToDoDrillKeyDisplay	To Do Drill Key Display

UI Map	Description
F1-ToDoEntUserQueryFilter	Valid User To Do Types Query Filter
F1-ToDoExpandedMessage	Display To Do Message
F1-ToDoSortKeyDisplay	To Do Sort Key Display
F1-ToDoUserLogAdd	To Do Entry - Add User Log Entry
F1-TreeFragment	Generic Tree
F1-UnifiedSearchFiltersDisp	Unified Search Filters - Display
F1-UnifiedSearchWidget	Unified Search Widget
F1-UnsMDAddObjectFltr	Add Objects for Unsupported Metadata - Filter
F1-UnsMDFltr	Unsupported Metadata - Filter
F1-UnsuppMDMOPKFilter	Search for Entities to Add by MO and PKs
F1-WorkCalendarHolidayMaint	Work Calendar Holiday Maintenance
F1-ZoneAdditionalActions	Zone Additional Actions
F1-ZoneColEdit	Zone Column Maintenance
F1-ZoneColHelpDisp	Zone Column Help Text Display
F1-ZoneColHelpLnk	Zone Column Help Link
F1-ZoneHelpText	Zone Help Text Elements
F1-ZoneParametersFilter	Zone parameters Filter
F1-ZoneRequiredParameters	Zone Required Parameters
F1-ZoneSQL	Zone SQL Text
F1-ZoneSQLCols	Zone SQL Columns
F1-ZoneSQLParms	Zone SQL Parameters

D.2.6 Maintenance Objects

The following maintenance objects are newly added in the Oracle Utilities Application Framework V4.4.0.3.0 database:

Maintenance Object	Description
F1-ACTNMETHOD	Action Method
F1-ANALYTICS	Analytics Table
F1-COLOROPT	Color Option
F1-DAEXPCTRL	Data Export Control
F1-FILEINT	File Integration Type

Maintenance Object	Description
F1-FLINREC	File Integration Record
F1-INSIGHGRP	Insight Group
F1-INSIGHTYP	Insight Type
F1-TABMD	Tab Metadata
F1-TREE	Tree
F1-UNSPRTD	Unsupported Metadata

D.2.7 To Do Types

None

D.2.8 Business Services

The following business services are newly added in the Oracle Utilities Application Framework V4.4.0.3.0 database:

Business Service	Description
F1-ANTBCHAR	Analytics Table's Characteristics Tables
F1-BatchMonitoringProbeService	Batch Probe Monitor
F1-CHKRUNBAT	Check if Batch is Running
F1-CHMPSEQ	Characteristic Mapping Sequence Rules
F1-DBMSCancelSteps	DBMS Scheduler - Interrupt Job Steps
F1-ExpandTreeNode	Expand Tree Node
F1-FleIntRecordSchemaRetriever	File Integration Record Schema Retriever
F1-FlushAllService	Flush the Server Cache
F1-GenericDataExplorer	Generic Data Explorer
F1-GETMANIFESTDETAIL	Verify Manifest File
F1-INHKEY	Get Inheritance Key
F1-InsightActionProcessor	Insight Action Processor
F1-MigRqContainsEntity	Check if Migration Request Contains Entity
F1-MOBTCHCD	MO Batch Codes
F1-MOCNVBAT	MO Conversion Batch Codes
F1-MOTABLES	Tables for a Maintenance Object
F1-MOTRNS	MOs that are Translatable (Internal Use Only)
F1OPTFK	Get Option FK Reference Details

Business Service	Description
F1-PrepareTreeNode	Prepare Tree Node
F1-ProgComTab-Add	Program Component Tab - Add
F1-ProgComTab-Delete	Program Component Tab - Delete
F1PRTLAPS	Portal Additional Display Details
F1PRTLTABSE	Main portal's tab portals
F1PRTLTMS	Main portals referencing a tab portal
F1-RELTDCNT	Related To Do Entries Count
F1-RetrieveActionMethodDetails	Retrieve Action Method Details
F1-RetrieveInsights	Retrieve Insights
F1-RetrieveTableInheritedFld	Retrieve Table's Inherited Key Field
F1-RetrieveTimeZoneNames	Retrieve Standard Time Zone Names
F1-SPEEXELMO	MOs Eligible for Specialized Export
F1-TableAuditProgramSearch	Table Audit Program
F1TBLCLSCST	Table fields for defining a constraint
F1TBLERD	Table ERD Information
F1-TBLMO	Maintenance Object for a Table
F1-TBLRECCNT	Table Record Count
F1TBLREFCST	Referring Constraint Search
F1-ToDoExtraActions	To Do Entry - Extra Actions
F1TREENDS	Other Tree Nodes
F1-UNSMDEX	Unsupported Metadata Exists
F1UNSRCHS	Unified Searches
F1-UserDashboardUpdate	Update User Dashboard Settings
F1-USRTDVAL	User Valid for Role
F1VALINSTYPE	Valid Insight Types for Insight Group
F1ZNPRMSEDT	General Parameters Maintenance
F1ZNSQLPARMS	SQL Parameters Maintenance

D.2.9 Portals

The following portals are newly added in the Oracle Utilities Application Framework V4.4.0.3.0 database:

Portal	Description
F1ACGRPM	Access Group
F1ACGRPQ	Access Group Query
F1ACMTHD	Action Method
F1ALGQ	Algorithm Query
F1ALGTQ	Algorithm Type Query
F1ANALYT	Analytics Dimension
F1ANFACT	Analytics Fact
F1ANLYTS	Analytics Table Query
F1APPSVM	Application Service
F1APPSVQ	Application Service Query
F1BOQ	Business Object Query
F1BSVQ	Business Service Query
F1BTCHQ	Batch Control Query
F1CHRMAP	Characteristic Mapping Query
F1CHRTYP	Characteristic Type
F1CHRTYQ	Characteristic Type Query
F1COLOPT	Color Option
F1CVENTD	Conversion Entity Dashboard
F1CVENTQ	Conversion Entity Query
F1CVENTVE	Conversion Validation Errors
F1DECLOG	Data Export Control Log
F1DEXCNS	Data Export Control Query
F1DEXCNT	Data Export Control
F1DTARQ	Data Area Query
F1FCFGQ	Feature Configuration Query
F1FIELD	Field
F1FKRFQ	Foreign Key Reference Query
F1FLDQ	Field Query
F1FLINTP	File Integration Type

Portal	Description
F1FLINTS	File Integration Type Query
F1GEXDAS	Generalized Export Dashboard
F1INSTGP	Insight Group
F1INSTYP	Insight Type
F1LKUPQ	Lookup Query
F1MANCQ	Managed Content Query
F1MENUQ	Menu Query
F1MGDIMO	Migration Data Set Import Object
F1MGDIMT	Migration Data Set Import Transaction
F1MOQ	Maintenance Object Query
F1MSG	Message
F1MSGC	Message Category
F1MSGQ	Message Query
F1NAVKQ	Navigation Key Query
F1NAVOQ	Navigation Option Query
F1PRTL	Portal
F1PRTLQ	Portal Query
F1PRUSEM	Product Use Metrics
F1SCRQ	Script Query
F1TABLE	Table
F1TBLCST	Table Constraints
F1TBLQ	Table Query
F1TBLRL	Relationship
F1TDDASH	To Do Dashboard
F1TMZNM	Time Zone
F1TODO	To Do Entry
F1TODOEQ	To Do Entry Query
F1TODOL	To Do Log
F1TREEM	Tree
F1TREEQ	Tree Query
F1UIMPQ	UI Map Query

Portal	Description
F1UNSPMD	Unsupported Metadata
F1UNSPMQ	Unsupported Metadata Query
F1WRKCAL	Work Calendar
F1WRKCLQ	Work Calendar Query
F1ZONE	Zone
F1ZONEQ	Zone Query
F1ZONEUSD	Zone References

D.2.10 Business Objects

The following business objects are newly added in the Oracle Utilities Application Framework V4.4.0.3.0 database:

Business Object	Description
F1-AccessGroup	Access Group
F1-AccessGroupBundlingAddBO	Bundling Add BO for Access Group
F1-ActionMethodPhysicalBO	Physical BO for Action Method
F1-ActionMethodRole	Action Method Role
F1-AnalyticsDimension	Analytics Dimension
F1-AnalyticsFact	Analytics Fact
F1-AnalyticsTablePhysicalBO	Physical BO for Analytics Table
F1-ApplicationService	Application Service
F1-AVAnalyticsOptions	Analytics Options
F1-BusinessFlagPhysicalBO	Physical BO for Business Flag
F1-CharacteristicType	Characteristic Type
F1-CharMapping	Characteristic Mapping
F1-Color	Color
F1-ColorCombo	Color Combination
F1-ColorOptionPhysicalBO	Physical BO for Color Option
F1-ContextualInsightType	Contextual Insight Type
F1-DBMSJobStatus	DBMS Job Status
F1-ExtractFileIntegrationRec	Extract File Integration Record
F1-ExtractFileIntegrationType	Extract File Integration Type
F1-Field	Field

Business Object	Description
F1-FileIntegRecBundlingAddBO	File Integration Record Bundling Add BO
F1-FillIntegrationRecPhysicalBO	Physical BO for File Integration Record
F1-FillIntegrationTypPhysicalBO	Physical BO for File Integration Type
F1-GeneralizedDataExport	Generalized Data Export Control
F1-InsightGroup	Insight Group
F1-InsightGroupPhysicalBO	Physical BO for Insight Group
F1-InsightTypePhysicalBO	Physical BO for Insight Type
F1-KeyRingPhysicalBO	Physical BO for Key Ring
F1-Message	Message
F1-MessageCategory	Message Category
F1-MigrImportProcessingOrder	Migration Import Processing Order
F1-OutboundMessagePhysicalBO	Physical BO for Outbound Message
F1-Portal	Portal
F1-PortalTab	Portal Tab
F1-RedirectionSecurityContext	Redirection Security Context
F1-RedirectionTargetsConfig	Redirection Targets Configuration
F1-SearchFilterHint	Search Filter Hint
F1-SearchFilterRule	Search Filter Rule
F1-ServiceTaskPhysicalBO	Physical BO for Service Task
F1-SpecializedDataExport	Specialized Data Export Control
F1-TableInheritanceKey	Update Inheritance Key
F1-Table	Table
F1-TablePhysicalBO	Physical BO for Table
F1-TimeZone	Time Zone
F1-ToDoEntry	To Do Entry
F1-Tree	Tree
F1-TreePhysicalBO	Physical BO for Tree
F1-UnifiedSearch	Unified Search
F1-UnsupportedMetadata	Unsupported Metadata
F1-WorkCalendar	Work Calendar
F1-Zonebo	Zone

D.2.11 Lookups

The following lookups are newly added in the Oracle Utilities Application Framework V4.4.0.3.0 database:

Field	Field Value	Description
APPLY_HEADER_STYLE_FLG	F1NO	No
	F1YS	Yes
BROADCAST_NODE_FLG	F1YS	Yes
	F1NO	No
COLOR_OPT_CLASS_FLG	F1SC	Single Combination
	F1SE	Series
CONTEXT_LABEL_TYPE_FLG	F1TM	Time
	F1DT	Date
	F1BS	Date and Time Base
CTXT_MENU_USAGE_FLG	F1NO	None
	F1CM	Override
	F1DF	Default
DASHBOARD_LOC_FLG	F1DL	Left
	F1DR	Right
DASHBOARD_STATE_FLG	F1DC	Closed
	F1DO	Open
F1_AGG_RULE_FLG	CNT	Count
	STD	Standard Deviation
	AVG	Average
	FRST	First
	MED	Median
	MAX	Max
	NONE	N/A
	LAST	Last
	MIN	Min
	CNTD	Count Distinct
	STDP	Standard Deviation POP

Field	Field Value	Description
	SUM	Sum
F1_BI_FLD_TYPE_FLG	F1CP	Computed
	F1PH	Physical
F1_BI_TABLE_TYPE_FLG	F1FC	Fact
	F1DM	Dimension
F1_CNV_STEP_FLG	2KEY	Key Assignment
	1VAL	Validation
	4INS	Insert to Production
	3XML	XML Resolution
F1_DATA_EXPORT_CLS_FLG	F1GE	Generalized Export
	F1SE	Specialized Export
F1_INIT_EXPORT_FLG	F1CO	Completed
	F1ST	Started
F1_INSIGHT_MODE_FLG	F1EX	Perform
	F1PR	Preview
F1_KEY_LEVEL_FLG	3	3
	1	1
	5	5
	2	2
	4	4
F1_MAP_OPT_FLG	F1MP	Mapped
	F1NM	Not Mapped
	F1AL	All
F1_ONGEXP_STATUS_FLG	F1DS	Disabled
	F1EN	Enabled
F1_PROC_OPT_FLG	F1PR	Pre-aggregation
	F1PS	Post-aggregation
F1_REDIRECTION_TARGET_FLG	F1DS	Digital Self Service
F1_RESTART_INIT_EXPORT	F1YS	Yes
	F1NO	No

Field	Field Value	Description
F1_WORK_FLD_FLG	F1NO	No
	F1YS	Yes
FILE_INT_CLASS_FLG	F1EX	Extract
FILE_INT_REC_SEVT_FLG	F1FR	Extract Record
FILE_INT_REC_STATUS_FLG	F1IN	Inactive
	F1AC	Active
FILE_INT_STATUS_FLG	F1IN	Inactive
	F1AC	Active
HEADER_CAT_FLG	F1ER	Error
	F1WN	Warning
	F1IN	Information
INITIALLY_EXPAND_FLG	F1YS	Yes
	F1NO	No
INSIGHT_ACT_CLASS_FLG	F1NG	Negative
	F1NA	Not Applicable
	F1DU	Dismissed by User
	F1NT	Neutral
	F1PO	Positive
INSIGHT_ACT_DISP_TYPE	F1BT	Button
INSIGHT_ACT_FLD_FLG	F1DC	Decline
	F1AC	Accept
INSIGHT_ACT_SEVT_FLG	F1IA	User Action
INSIGHT_ACT_TRACK_FLG	F1NO	No
INSIGHT_SEVT_FLG	F1IS	Contextual Insight
IWS_REST_VER_FLG	F110	1.0
	F120	2.0
LGCY_CAT_FLG	F1NS	No longer supported
	F1DT	Development Tools
	F1NY	Not yet supported
NODE_NAVIGATION_FLG	F1YS	Yes

Field	Field Value	Description
	F1NO	No
SUBMIT_METH_FLG	F1SC	Scheduled
	F1GE	Generated
	F1TD	Timed
	F1OT	Other
	F1ON	Online
TREE_NODE_SEVT_FLG	F1PN	Populate Node
	F1TO	Information Override
UNIFIED_SRCH_MODE_FLG	PREP	Prepare Search Details
	EXEC	Perform Search
VISUAL_SETTING_TYPE_FLG	F1DF	Default
	F1OS	Based on Algorithm Output Severity
VISUAL_STRUCTURE_FLG	F1II	Inline Insight
	F1BD	Badge Insight
	F1CI	Card Insight
	F1LI	List Insight
ZONE_COL_SRC_FLG	FUNC	Function
	SPEC	Specified
	SS	Service Script
	BS	Business Service
	COL	Column
	MSG	Message
	FKRF	FK Reference
	FORM	Formula
	ICON	Icon
ZONE_PRM_TYPE_FLG	BO	Business Object
	NBR	Number
	TIME	Time
	DATE	Date
	STR	String

Field	Field Value	Description
	DTTM	Date/time
	MON	Money

D.2.12 Foreign Key References

The following foreign key references are newly added in the Oracle Utilities Application Framework V4.4.0.3.0 database:

Foreign Key Reference	Description
F1-ACMTH	Action Method
F1-ANLYT	Analytics Table
F1AP-BO	BO Option - Action Processing BPA Script
F1-BPASR	BPA Script
F1-CLROP	Color Option
F1-CVENT	Conversion Entity
F1-DEXPC	Data Export Control
F1DI-BO	BO Option - Display Icon Reference
F1DI-MO	MO Option - Display Icon Reference
F1EC-MO	MO Option - Export Batch Control
F1-FILIT	File Integration Type
F1-FLREC	File Integration Record
F1-INSGR	Insight Group
F1-INSTY	Insight Type
F1-LKUP	Lookup
F1-PRGCM	Program Component
F1-TREE	Tree
F1-UNSMD	Unsupported Metadata

D.2.13 Batch Controls

The following batch controls are newly added in the Oracle Utilities Application Framework V4.4.0.3.0 database:

Batch Control	Description
F1ACCTPX	Initial Data Export ACCT GROUP
F1ACTNDX	Initial Data Export F1-ACTNMETHOD

Batch Control	Description
F1ALGOMX	Initial Data Export ALGORITHM
F1ALGTEX	Initial Data Export ALG TYPE
F1ANALSX	Initial Data Export F1-ANALYTICS
F1APPSEX	Initial Data Export APP SERVICE
F1BATCLX	Initial Data Export BATCH CNTL
F1BKTCGX	Initial Data Export F1-BKTCONFIG
F1-BTIDT	Upgrade Batch Thread Instance Date / Time
F1-BTMON	Batch Probe
F1BUSFGX	Initial Data Export F1-BUSFLG
F1BUSFPX	Initial Data Export F1-BUSFLGTYP
F1BUSOJX	Initial Data Export F1-BUS OBJ
F1BUSSCX	Initial Data Export F1-BUS SVC
F1CALENX	Initial Data Export F1-CALENDMMN
F1CHAREX	Initial Data Export CHAR TYPE
F1COLOTX	Initial Data Export F1-COLOROPT
F1CONTEX	Initial Data Export CONTENT ZONE
F1COUNYX	Initial Data Export COUNTRY
F1CUBEEX	Initial Data Export F1-CUBETYPE
F1CUBEWX	Initial Data Export F1-CUBEVIEW
F1CURREX	Initial Data Export CURR CODE
F1DATAAX	Initial Data Export F1-DATA AREA
F1DATASX	Initial Data Export DATA ACCESS
F1DEPL2X	Initial Data Export F1-DEPLOYPRT
F1DEPLPX	Initial Data Export F1-DEPLOYTYP
F1DISPFX	Initial Data Export DISP PROF
F1DISPNX	Initial Data Export DISP ICON
F1ETLMLX	Initial Data Export F1-ETLMPCTRL
F1EXTLPX	Initial Data Export F1-EXT LKUP
F1FAACTX	Initial Data Export F1-FACT
F1FIELDX	Initial Data Export FIELD
F1FILETX	Initial Data Export F1-FILEINT

Batch Control	Description
F1FKREFX	Initial Data Export FK REF
F1FLINCX	Initial Data Export F1-FLINREC
F1-GEXO	Generalized Ongoing Export
F1GEOTEX	Initial Data Export GEO TYPE
F1-GEXPI	Generalized Initial Export Initiator
F1INSIPX	Initial Data Export F1-INSIGHGRP
F1INSTYX	Initial Data Export F1-INSIGHTYP
F1IWSANX	Initial Data Export F1-IWSANN
F1IWSAPX	Initial Data Export F1-IWSANNTYP
F1IWSSCX	Initial Data Export F1-IWSSVC
F1JMSCTX	Initial Data Export JMS CONNECT
F1LANGEX	Initial Data Export LANGUAGE
F1LOOKPX	Initial Data Export LOOKUP
F1MAINJX	Initial Data Export MAIN OBJ
F1MANCTX	Initial Data Export F1-MAN CONT
F1MDMDTX	Initial Data Export F1-MDT
F1MDTTEX	Initial Data Export F1-MDTTYPE
F1MEENUX	Initial Data Export MENU
F1MESS2X	Initial Data Export MESSAGE
F1MIGRNX	Initial Data Export F1-MIGRPLAN
F1MIGRQX	Initial Data Export F1-MIGRREQ
F1MKTCGX	Initial Data Export F1-MKTCFG
F1MKTMNX	Initial Data Export F1-MKTMSGIN
F1MKTMPX	Initial Data Export F1-MKTMSGTYP
F1MKTMTX	Initial Data Export F1-MKTMSGOUT
F1MKTPCX	Initial Data Export F1-MKTPROC
F1MKTPPX	Initial Data Export F1-MKTPRCTYP
F1MKTPTX	Initial Data Export F1-MKTPRCEVT
F1MOBCPX	Initial Data Export F1-MOBCOMP
F1MSTCGX	Initial Data Export F1-MSTCFG
F1NAVKYX	Initial Data Export NAV KEY

Batch Control	Description
F1NAVOTX	Initial Data Export NAV OPT
F1NTDWEX	Initial Data Export NT DWN TYPE
F1NTDWFX	Initial Data Export NT DWN PROF
F1NTUPEX	Initial Data Export NT UPL TYPE
F1NTXIDX	Initial Data Export NT XID
F1OUTMPX	Initial Data Export F1-OUTMSGTYP
F1PERFTX	Initial Data Export F1-PERFTGT
F1PERFYX	Initial Data Export F1-PERFTGTTY
F1PHONEX	Initial Data Export PHONE TYPE
F1PORTLX	Initial Data Export PORTAL
F1PROCNX	Initial Data Export F1-PROCDEFN
F1REPOTX	Initial Data Export REPORT
F1REQTEX	Initial Data Export F1-REQ-TYPE
F1REREQX	Initial Data Export F1-REQ
F1RPTONX	Initial Data Export RPT OPTION
F1SCHEAX	Initial Data Export F1-SCHEMA
F1SCRITX	Initial Data Export SCRIPT
F1SECTEX	Initial Data Export SEC TYPE
F1SERVEX	Initial Data Export SERVICE
F1STASEX	Initial Data Export F1-STASKTYPE
F1STATSX	Initial Data Export F1-STATS
F1STSRRNX	Initial Data Export F1-STSREASON
F1STSSTX	Initial Data Export F1-STSSNPSHT
F1SVCTKX	Initial Data Export F1-SVCTASK
F1TABLEX	Initial Data Export TABLE
F1TIMEEX	Initial Data Export TIME ZONE
F1TIMENX	Initial Data Export F1-TIMEDMN
F1TODO4X	Initial Data Export TO DO TYPE
F1TODOEX	Initial Data Export TO DO ROLE
F1TODOYX	Initial Data Export TO DO ENTRY
F1TRREEX	Initial Data Export F1-TREE

Batch Control	Description
F1UIMAPX	Initial Data Export F1-UI MAP
F1UIZO2X	Initial Data Export UI ZONE
F1USERPX	Initial Data Export USER GROUP
F1USSERX	Initial Data Export USER
F1WEBSTX	Initial Data Export F1-WEBSVCCAT
F1WFEVEX	Initial Data Export WF EVT TYPE
F1WFMSMX	Initial Data Export WFM SYSTEM
F1WFPREX	Initial Data Export WF PROFILE
F1WFPRXLX	Initial Data Export WF PROC TMPL
F1WORKLX	Initial Data Export WORK CAL
F1XAICSX	Initial Data Export XAI CLASS
F1XAIJCX	Initial Data Export XAI JMS TPC
F1XAIJQX	Initial Data Export XAI JMS Q
F1XAIJRX	Initial Data Export XAI JNDI SVR
F1XAIOSX	Initial Data Export XAI OPTIONS
F1XAISEX	Initial Data Export XAI SERVICE
F1XAISRX	Initial Data Export XAI SENDER
F1ZONELEX	Initial Data Export ZONE HDL

D.2.14 Application Services

The following application services are newly added in the Oracle Utilities Application Framework V4.4.0.3.0 database:

Application Service	Description
F1ACGRPM	Access Group Portal
F1ACGRPQ	Access Group Query Portal
F1ACMTHD	Action Method Portal
F1-ACTIONMETHOD	Action Method MO
F1ALGQ	Algorithm Query Portal
F1ALGTQ	Algorithm Type Query Portal
F1ANALYT	Analytics Dimension Portal
F1-ANALYTICS	Analytics Table MO
F1ANFACT	Analytics Fact Portal

Application Service	Description
F1ANLYTS	Analytics Table Query Portal
F1APPSVM	Application Service Portal
F1APPSVQ	Application Service Query Portal
F1BOQ	Business Object Query Portal
F1BSVQ	Business Service Query Portal
F1BTCHQ	Batch Control Query Portal
F1-BTIDT	Upgrade Batch Thread Instance Date / Time
F1-CHARMAPBOAS	Characteristic Mapping BO
F1CHRMAP	Characteristic Mapping Query Portal
F1CHRTYP	Characteristic Type Portal
F1CHRTYQ	Characteristic Type Query Portal
F1COLENZN	Collect Entity Zone
F1COLOPT	Color Option Portal
F1COLOROPTION	Color Option MO
F1CVENTD	Conversion Entity Dashboard Portal
F1CVENTQ	Conversion Entity Query Portal
F1-DATAEXPORTCTRL	Data Export Control MO
F1DEXCNS	Data Export Control Query Portal
F1DEXCNT	Data Export Control Portal
F1DTARQ	Data Area Query Portal
F1-ETLMAPBOAS	ETL Mapping Control BO
F1FCFGQ	Feature Configuration Query Portal
F1FIELD	Field Portal
F1-FILEINT	File Integration Type MO
F1FKRFQ	Foreign Key Reference Query Portal
F1FLDQ	Field Query Portal
F1-FLINREC	File Integration Record MO
F1FLINTP	File Integration Type Portal
F1FLINTS	File Integration Type Query Portal
F1-GENEXBACN	Generalized Initial Export Batch Controls
F1GEXDAS	Generalized Export Dashboard Portal

Application Service	Description
F1INSIGHTGRP	Insight Group MO
F1INSIGHTTYP	Insight Type MO
F1INSTGP	Insight Group Portal
F1INSTYP	Insight Type Portal
F1LKUPQ	Lookup Query Portal
F1MANCQ	Managed Content Query Portal
F1MENUQ	Menu Query Portal
F1-MOCNVBTCR	Conversion Batch Controls Zone
F1-MOERSCNF	Object Erasure Configuration Zone
F1MOQ	Maintenance Object Query Portal
F1MSG	Message Portal
F1MSGC	Message Category Portal
F1MSGQ	Message Query Portal
F1NAVKQ	Navigation Key Query Portal
F1NAVOQ	Navigation Option Query Portal
F1PRTL	Portal
F1PRTLQ	Portal Query Portal
F1PRUSEM	Product Use Metrics Portal
F1-REDIRECT	Redirection Services
F1SCRQ	Script Query Portal
F1SYSMON	System Monitoring
F1TABLE	Table Portal
F1TABMD	Tab Metadata MO
F1TBLQ	Table Query Portal
F1TDDASH	To Do Dashboard Portal
F1TMZNM	Time Zone Portal
F1TODO	To Do Entry Portal
F1TODOEQ	To Do Entry Query Portal
F1TREE	Tree MO
F1TREEM	Tree Portal
F1TREEQ	Tree Query Portal

Application Service	Description
F1UIMPQ	UI Map Query Portal
F1UNSPMD	Unsupported Metadata Portal
F1UNSPMQ	Unsupported Metadata Query Portal
F1-UNSPRTD	Unsupported Metadata MO
F1WRKCAL	Work Calendar Portal
F1WRKCLQ	Work Calendar Query Portal
F1ZONE	Zone Portal
F1ZONEQ	Zone Query Portal

D.2.15 Characteristic Types

The following characteristic types are newly added in the Oracle Utilities Application Framework V4.4.0.3.0 database:

Characteristic Type	Description
F1-FLD	Field
F1-HXCOL	Hex Color Code
F1-MIGPO	Migration Import Processing Order
F1-SCR	Script
F1-SEQ	Sequence

D.2.16 Scripts

The following scripts are newly added in the Oracle Utilities Application Framework V4.4.0.3.0 database:

Script	Description
F1AccessGrpM	Access Group - Maintain
F1AccGrpDisp	Access Group - Retrieve Details for Display
F1AccGrpPre	Access Group - Pre-processing
F1ActnMthdMn	Action Method - Maintain
F1AddDebugLg	Add Log for Monitoring Probe
F1AnDmCh	Dimension Characteristic Mapping
F1AnDmCharV	Analytics Dimension Characteristic Zone Visibility
F1AnDmChSS	Dimension Characteristic Mapping
F1AnltfldInf	Analytics Field Information
F1AnlyFieldM	Maintain Analytics Field

Script	Description
F1AnlyTableM	Analytics Table - Maintain
F1AppSvcDisp	Application Service - Retrieve Details for Display
F1AppSvcM	Application Service - Maintain
F1AppSvcPre	Application Service - Pre-processing
F1BTMONPR	Batch Monitoring Process Record
F1CHARMAPINF	Characteristic Mapping Information
F1CHARMAPVAL	Validate Characteristic Mapping Configuration
F1CharsMaint	Maintain Characteristics
F1CharTyDisp	Characteristics Type - Retrieve Details for Display
F1CharTypM	Characteristic Type - Maintain
F1CharTypPre	Characteristic Type - Pre-Processing
F1CHRMAPP	Characteristic Mapping - Default Rules
F1CLROPTINFO	Color Option Information
F1CnclBatJob	Cancel Batch Job
F1ColleEnZnV	Collect Entity Dashboard Zone Visibility
F1COLORINFO	Color Information
F1ColorOptM	Color Option - Maintain
F1CondFilVal	Conditional Filter Validation
F1CopyEntity	Copy Entity
F1CtxReset	Reset portal context
F1DAEXCNAUD	Data Export Audit
F1DAEXCNVAL	Data Export Control Validation
F1DaExpCtrM	Data Export Control - Maintain
F1DataExpAud	Manage Data Export Audit Rule
F1DetUniSrch	Determine Unified Search For User
F1DEXCTRLINF	Data Export Control Information
F1DExUsrLgA	Data Export Control - Add User Log Entry
F1DtExpPost	Generalized Data Export Control - Post Processing
F1DupFileRec	Duplicate File Integration Records
F1ExpBtchDtl	Generalized Export Control - Retrieve Details for Display
F1-FieldM	Field Maintenance

Script	Description
F1FILEXPR	File Integration Record Extraction
F1FillInRcLay	Display File Integration Record Layout
F1FillInRcMnt	File Integration Record - Maintain
F1FillInTyMnt	File Integration Type - Maintain
F1FITypePost	Extract File Integration Type - Post Processing
F1FITypePre	Extract File Integration Type - Pre-processing
F1FldDisp	Field - Display
F1FldUIPre	Field - UI Pre-processing
F1HEXCOLOR	Validate Hex Color Code
F1InsGrTyp	Insight Group - Maintain Insight Types
F1InsGrTypSS	Insight Group - Maintain Insight Types
F1InsightGrM	Insight Group - Maintain
F1InsighTyM	Insight Type - Maintain
F1InsTypeDtl	Insight Type - Retrieve Details for Display
F1InsTyUIPre	Insight Type - UI Pre-processing
F1-lwsRPost	Inbound REST Web Service - Post Processing
F1-lwsSPost	Inbound SOAP Web Service - Post Processing
F1LKUPINF	Lookup Information
F1-MgIPOPost	Migration Import Processing Order - Post Processing
F1MGPRORDINF	Migration Import Processing Order Information
F1MgRqAdRmEn	Add or Remove an Entity from a Migration Request
F1MOBatchExp	Create MO Data Export Batch Controls
F1MOBExpBPA	Create MO Data Export Batch Controls
F1MOCnvBat	Create MO Conversion Batch Controls
F1MOCnvBatSS	Create MO Conversion Batch Controls
F1MsgCatDisp	Message Category - Display
F1MsgCatM	Message Category Maintenance
F1MsgCatUIPr	Message Category - UI Pre-processing
F1MSGCINFO	Message Category Information
F1MsgDisp	Message - Display
F1MsgM	Message Maintenance

Script	Description
F1MsgsM	Messages Maintenance
F1MsgsS	Messages Maintenance
F1MsgUIPre	Message - UI Pre-processing
F1NAVINFO	Navigation Key Information
F1PopBtPrNt	Populate Batch Progress Note
F1PortalDisp	Portal - Display
F1-PortalM	Portal Maintenance
F1PORTALPST	Maintain Portal Artifacts
F1PortITabM	Portal Tab Maintenance
F1PortITabsM	Portal Tabs Maintenance
F1PortUIPre	Portal - UI Pre-processing
F1PortUIPst	Portal - UI Post-processing
F1PRFMDELAY	Perform Delay of Processing
F1PrtIOpt	Portal Options Maintenance
F1PrtIOptM	Portal Options Maintenance
F1RELTDINFO	Related To Do Count
F1RetActPrSc	Retrieve Action Processing BPA Script
F1SFHINTINFO	Search Filter Hint Information
F1SpeExBaDtl	Specialized Export Control - Retrieve Details for Display
F1SubmitJob	Submit Batch Job
F1TableERD	Table ERD Information
F1TableM	Table Maintenance
F1TargetLink	Return a Hyperlink to the Redirect Servlet for a given Target
F1TblConst	Table Constraints Maintenance
F1TblDisp	Table - Display
F1TblFld	Table Field Maintenance
F1TblFldM	Table Field Maintenance
F1TblFlds	Table Fields Maintenance
F1TblUIPre	Table - UI Pre-processing
F1TimeZoneM	Time Zone - Maintain
F1TmZnDisp	Time Zone - Display

Script	Description
F1TmZnPre	Time Zone - Pre-processing
F1ToDoActs	To Do Entry - Extra Actions
F1ToDoActsSS	To Do Entry - Extra Actions
F1ToDoEnDisp	To Do Entry - Display
F1ToDoEnPre	To Do Entry - UI Pre-processing
F1ToDoEnPst	To Do Entry - UI Post-processing
F1ToDoEntryM	To Do Entry Maintenance
F1ToDoUsrLgA	To Do Entry - Add User Log Entry
F1-TreeM	Tree - Maintain
F1TreeNdDisp	Tree Node Display
F1TreeNode	Tree Node Maintenance
F1TreeNodeM	Tree Node Maintenance
F1TreeZone	Generic Tree
F1UIInds	Common Maintenance Indicators
F1UniSrchDtl	Unified Search - Details for Display
F1UniSrchHnd	Unified Search Handler
F1UnsDisp	Unsupported Metadata - Retrieve Details for Display
F1UnsMDMark	Mark / Check Record Unsupported
F1UNSMDVAL	Unsupported Metadata Validation
F1UnsMng	Unsupported Metadata - Add / Remove Objects
F1UnsMngSS	Unsupported Metadata - Add / Remove Objects
F1UnspMnt	Unsupported Metadata - Maintain
F1UnsPre	Unsupported Metadata - Pre-processing
F1UpdDExpCnt	Update Data Export Controls
F1UpdDExpCSS	Update Data Export Controls
F1UpdInhFld	Update Inheritance Key
F1UpdInhFldB	Update Inheritance Key
F1USRCHINF	Unified Search Information
F1VALINSGVS	Validate Insight Group Visual Structure
F1WCalHolMnt	Work Calendar Holiday Maintenance
F1WCalHolSS	Work Calendar Holiday Maintenance

Script	Description
F1WrkCalDsp	Work Calendar - Display
F1WrkCalM	Work Calendar - Maintain
F1WrkCalPr	Work Calendar - UI Pre-processing
F1-ZoneCol	Zone SQL Column Maintenance
F1-ZoneColM	Zone Parameter Maintenance
F1-ZoneDisp	Zone - Display
F1-ZoneGnPrm	Zone General Parameters Maintenance
F1-ZoneM	Zone - Maintain
F1-ZoneParm	Zone Parameter Maintenance
F1-ZoneSQL	Zone SQL Maintenance
F1-ZoneUIPre	Zone - UI Pre-processing
F1-ZoneUIPst	Zone - UI Post-processing

Appendix E : Oracle Utilities Application Framework System Table Guide

This section lists the system tables owned by Oracle Utilities Application Framework V4.4.0.3.0 and explains the data standards of the system tables. The data standards are required for the installation of Oracle Utilities Application Framework, development within Oracle Utilities Application Framework, and for the configuration and customization of Oracle Utilities products. Adhering to the data standards is a prerequisite for seamless upgrade to future releases.

This section includes:

- [About System Tables](#)
- [System Table Standards](#)
- [Guidelines for System Table Updates](#)
- [System Table List](#)

E.1 About System Tables

System tables are a subset of the tables that must be populated at the time the product is installed. They include metadata and configuration tables. The data stored in the system tables are the information that Oracle Utilities Application Framework product operations are based on.

As the product adds more functionality, the list of system tables can grow. The complete list of the system tables can be found in the [System Table List](#) section.

E.2 System Table Standards

System table standards must be observed for the following reasons:

- The product installation and upgrade process and customer modification data extract processes depend on the data prefix and owner flag values to determine the system data owned by each product.
- The standards ensure that there will be no data conflict in the product being developed and the future Oracle Utilities Application Framework release.
- The standards ensure that there will be no data conflict between customer modifications and future Oracle Utilities product releases.
- The data prefix is used to prevent test data from being released to production.

Developer's Note: All test data added to the system data tables must be prefixed by ZZ (all upper case) in order for the installation and upgrade utility to recognize them as test data.

E.3 Guidelines for System Table Updates

This section describes guidelines regarding the updating of the system table properties.

E.3.1 Business Configuration Tables

The majority of data in the tables in this group belongs to the customer. But these tables are shipped with some initial data in order for the customer to login to the system and begin configuring the product. Unless specified otherwise, the initial data is maintained by Oracle Utilities Application Framework and subject to subsequent upgrade.

E.3.1.1 Application Security and User Profile

These tables define the access rights of a User Group to Application Services and Application Users.

Properties	Description
Tables	SC_ACCESS_CNTL, SC_USER, SC_USR_GRP_PROF, SC_USR_GRP_USR, SC_USER_GROUP, SC_USER_GROUP_L
Initial Data	User Group ALL_SERVICES and default system user SYSUSER . Upon installation the system default User Group ALL_SERVICES is given unrestricted accesses to all services defined in Oracle Utilities Application Framework.

Developer's Note: When a new service is added to the system, all actions defined for the service must be made available to the User Group ALL_SERVICES.

E.3.1.2 Currency Code

The ISO 4217 three-letter codes are taken as the standard code for the representation of the currency.

Properties	Description
Tables	CI_CURRENCY_CD, CI_CURRENCY_CD_L
Initial Data	United States Dollar (USD).

E.3.1.3 Display Profile

The Display Profile Code is referenced in the User (SC_USER) table.

Properties	Description
Tables	CI_DISP_PROF, CI_DISP_PROF_L
Initial Data	North America (NORTHAM), HIJRI Format (HIJRI) and Europe (EURO).

Configuration Note: In order to use HIJRI Format display profile, additional configuration is needed to define the mappings between Hijri and Gregorian dates. Refer to the Display Profile documentation for more information.

E.3.1.4 Installation Options

Installation option has only one row that is shipped with the initial installation of Oracle Utilities Application Framework. The columns that can be updated in these tables have customer data and will not be overridden by the upgrade process unless a special script is written and included in the upgrade process.

Properties	Description
Tables	F1_INSTALLATION, CI_INSTALL_ALG, CI_INSTALL_MSG, CI_INSTALL_MSG_L, CI_INSTALL_PROD
Initial Data	Option 11111

Developer's Note: The system data owner of an environment is defined in the Installation Option. This Owner Flag value is stamped on all system data that is added to this environment. The installation default value is Customer Modification (CM). This value must be changed in the base product development environments.

E.3.1.5 Language Code

Language code must be a valid code defined in ISO 639-2 Alpha-3. Adding a new language code to the table without translating all language dependent objects in the system can cause errors when a user chooses the language.

Properties	Description
Tables	CI_LANGUAGE
Initial Data	English (ENG)

E.3.1.6 Time Zone

The installation options require a valid time zone. A value for UTC (Coordinated Universal Time) is provided. Implementations should define the appropriate time zone and update the installation option value accordingly.

Properties	Description
Tables	CI_TIME_ZONE, CI_TIME_ZONE_L
Initial Data	UTC

E.3.1.7 To Do Priority and Role

New To Do Types released will be linked to the default To Do Role and set to the product assigned priority value initially. These initial settings can be overridden by the implementation.

Properties	Description
Tables	CI_ROLE(L), CI_TD_VAL_ROLE

Properties	Description
Initial Data	F1_DFLT

E.3.2 Development and Implementation System Tables

This section defines the standards for the system tables that contain data for application development. The data in these tables implement business logic and UI functions shared by various products and product extensions in the same database.

E.3.2.1 Standards

When adding new data, the owner flag value of the environment must prefix certain fields of these tables. For example, when a developer adds a new algorithm type to an Oracle Revenue Management and Billing environment, C1 should prefix the new Algorithm Type code. The fields that are subject to this rule are listed in Standard Data Fields property.

The data that is already in these tables cannot be modified if the data owner is different than the environment owner. This prevents the developers from accidentally modifying system data that belongs to Oracle Utilities Application Framework or the base products. However, some fields are exempt from this rule and can be modified by Customer Modification. These fields are listed in the Customer Modification Fields property.

Note that the system supports a system upgrade rule called Override Owner flag. If duplicate data rows (data row with same primary key values) are found at the time of upgrade, the owner flag values will get overridden. The lower level application system data will override the upper level system data. For example, F1 overrides C1, F1 and C1 override CM, and so on. This rule will be applied to the following tables: CI_CHAR_ENTITY, CI_MD_MO_ALG, C1_PORTAL_OPT, F1_BUS_OBJ_ALG, F1_BUS_OBJ_STATUS_ALG, CI_MD_MO_OPT, F1_BUS_OBJ_OPT, F1_BUS_OBJ_STATUS_OPT, F1_BUS_OBJ_STATUS, and F1_BUS_OBJ_STATUS_L.

E.3.2.2 Algorithm Type

Properties	Description
Tables	CI_ALG_TYPE, CI_ALG_TYPE_L, CI_ALG_TYPE_PRM, CI_ALG_TYPE_PRM_L
Standard Data Fields	Algorithm Type (ALG_TYPE_CD)
Customer Modification	None

E.3.2.3 Algorithm

Properties	Description
Tables	CI_ALG, CI_ALG_L, CI_ALG_PARM, CI_ALG_VER
Standard Data Fields	Algorithm (ALG_CD)
Customer Modification	None

E.3.2.4 Application Security

Properties	Description
Tables	SC_APP_SERVICE, SC_APP_SERVICE_L, CI_APP_SVC_ACC
Standard Data Fields	Application Service ID (APP_SVC_ID)
Customer Modification	None

E.3.2.5 Batch Control

Properties	Description
Tables	CI_BATCH_CTRL, CI_BATCH_CTRL_L, CI_BATCH_CTRL_P, CI_BATCH_CTRL_P_L
Standard Data Fields	Batch Process (BATCH_CD), Program Name (PROGRAM_NAME)
Customer Modification	Next Batch Number (NEXT_BATCH_NBR), Last Update Instance (LAST_UPDATE_INST), Last Update Date time (LAST_UPDATE_DTTM) and the batch process update these columns. Time Interval (TIMER_INTERVAL), Thread Count (BATCH_THREAD_CNT), Maximum Commit Records (MAX_COMMIT_RECS), User (USER_ID), Language (LANGUAGE_CD), Email Address (EMAILID), Start program debug tracing (TRC_PGM_STRT_SW), End Program Debug trace (TRC_PGM_END_SW), SQL debug tracing (TRC_SQL_SW) and Standard debug tracing (TRC_STD_SW) on CI_BATCH_CTRL Table. Batch Parameter Value (BATCH_PARM_VAL) and Security flag (TEXT_SECURITY_FLG) on Batch Control Parameters Table (CI_BATCH_CTRL_P)

E.3.2.6 Business Object

Properties	Description
Tables	F1_BUS_OBJ, F1_BUS_OBJ_L, F1_BUS_OBJ_ALG, F1_BUS_OBJ_OPT, F1_BUS_OBJ_STATUS, F1_BUS_OBJ_STATUS_L, F1_BUS_OBJ_STATUS_ALG, F1_BUS_OBJ_STATUS_OPT, F1_BUS_OBJ_STATUS_RSN, F1_BUS_OBJ_STATUS_RSN_L, F1_BUS_OBJ_STATUS_RSN_CHAR, F1_BUS_OBJ_TR_RULE, F1_BUS_OBJ_TR_RULE_L
Standard Data Fields	Business Object (BUS_OBJ_CD), Status Reason (BO_STATUS_REASON_CD)

Properties	Description
Customer Modification	<p>Batch Control (BATCH_CD), Alert (BO_ALERT_FLG), Sequence (SORT_SEQ5), Status Reason (STATUS_REASON_FLG) fields on Business Object Status Table (F1_BUS_OBJ_STATUS).</p> <p>Instance Control (INSTANCE_CTRL_FLG), Application Service (APP_SVC_ID) on Business Object Table (F1_BUS_OBJ).</p> <p>Status Reason Selection (STATUS_REASON_SELECT_FLG) on Status Reason Table (F1_BUS_OBJ_STATUS_RSN).</p>

E.3.2.7 Business Service

Properties	Description
Tables	F1_BUS_SVC, F1_BUS_SVC_L
Standard Data Fields	Business Service (BUS_SVC_CD)
Customer Modification	Application Service (APP_SVC_ID)

E.3.2.8 Characteristics

Properties	Description
Tables	CI_CHAR_TYPE, CI_CHAR_TYPE_L, CI_CHAR_ENTITY, CI_CHAR_VAL, CI_CHAR_VAL_L
Standard Data Fields	Characteristic Type (CHAR_TYPE_CD), Characteristic Value (CHAR_VAL) on CI_CHAR_VAL
	<p>Note: If the characteristic type is customizable, the customer can insert a new characteristic value. CM must be prefixed when the implementation team introduces a new characteristic value.</p>
Customer Modification	Adhoc Characteristic Value Validation Rule (ADHOC_VAL_ALG_CD), Allow Search by Characteristic Value (SEARCH_FLG)

E.3.2.9 Configuration Migration Assistant

Properties	Description
Tables	F1_MIGR_PLAN, F1_MIGR_PLAN_L, F1_MIGR_PLAN_INSTR, F1_MIGR_PLAN_INSTR_L, F1_MIGR_PLAN_INSTR_ALG, F1_MIGR_REQ, F1_MIGR_REQ_L, F1_MIGR_REQ_INSTR, F1_MIGR_REQ_INST_R_L, F1_MIGR_REQ_INSTR_ENTITY, F1_MIGR_REQ_INCL_REQ
Standard Data Fields	Migration Plan Code (MIGR_PLAN_CD), Migration Request Code (MIGR_REQ_CD)
Customer Modification	None

E.3.2.10 Data Area

Properties	Description
Tables	F1_DATA_AREA, F1_DATA_AREA_L
Standard Data Fields	Data Area Code (DATA_AREA_CD)
Customer Modification	None

E.3.2.11 Deployment Part

Properties	Description
Tables	F1_DEPLOYMENT_PART, F1_DEPLOYMENT_ITEM
Standard Data Fields	Deployment ID (F1_DEPLOYMENT_ID)
Customer Modification	None

E.3.2.12 Display Icon

Properties	Description
Tables	CI_DISP_ICON, CI_DISP_ICON_L
Standard Data Fields	Display Icon Code (DISP_ICON_CD)
Customer Modification	None

E.3.2.13 Extendable Lookup

Properties	Description
Tables	F1_EXT_LOOKUP_VAL,F1_EXT_LOOKUP_VAL_L, F1_EXT_LOOKUP_VAL_CHAR
Standard Data Fields	Business Object (BUS_OBJ_CD), Extendable Lookup Value (F1_EXT_LOOKUP_VALUE)
Customer Modification	Business Object Data Area (BO_DATA_AREA) Override Description (DESCR_OVRD) on Extendable Lookup Field Value Language Table (F1_EXT_LOOKUP_VAL_L) Note: When the product releases base owned records in Extendable Lookup, if there are additional elements the business object will map the element to the BO_DATA_AREA if the value is allowed to be modified by the implementation team.

E.3.2.14 Foreign Key Reference

Properties	Description
Tables	CI_FK_REF, CI_FK_REF_L
Standard Data Fields	FK reference code (FK_REF_CD)
Customer Modification	Info Program Name (INFO_PRG), Zone (ZONE_CD)

E.3.2.15 Inbound Web Service

Properties	Description
Tables	F1_IWS_SVC_L, F1_IWS_SVC, F1_IWS_SVC_OPER_L, F1_IWS_SVC_OPER, F1_IWS_ANN_L, F1_IWS_ANN_PARM, F1_IWS_ANN, F1_IWS_ANN_TYPE_L, F1_IWS_ANN_TYPE, F1_IWS_ANN_TYPE_PARM, F1_IWS_ANN_TYPE_PARM_L
Standard Data Fields	Webservice Name (IN_SVC_NAME), Annotation (ANN_CD), Annotation Type (ANN_TYPE_CD)
Customer Modification	Debug (DEBUG_SW), Active (ACTIVE_SW), Trace (TRACE_SW), Request XSL (REQUEST_XSL), Response XSL (RESPONSE_XSL)

E.3.2.16 Unsupported Objects

Properties	Description
Tables	F1_LGCY_OBJ
Standard Data Fields	Legacy Object ID (LGCY_OBJ_ID)
Customer Modification	None

E.3.2.17 **Lookup**

Properties	Description
Tables	CI_LOOKUP_FIELD, CI_LOOKUP_VAL, CI_LOOKUP_VAL_L
Standard Data Fields	<p>Field Name (FIELD_NAME) A lookup field name must have corresponding field metadata. The name of the lookup field column must be assigned to avoid conflicts among different products. If you follow the standards for database field names, a Customer Modification lookup field name will be automatically Customer Modification prefixed.</p> <p>Field Value (FIELD_VALUE) If a lookup field is customizable, Customer Modification can insert new lookup values. X or Y must prefix when implementers introduce a new lookup value.</p> <p>Product development may add lookup values to Oracle Utilities Application Framework owned lookup field's value. When extended new value is added, the Owner Flag is used to prefix the value. For example, when the Oracle Revenue Management and Billing product adds a new value to the algorithm entity flag (ALG_ENTITY_FLG), it is prefixed with C1.</p>
Customer Modification	Override Description (DESCR_OVRD) on Lookup Field Value Language Table (CI_LOOKUP_VAL_L)

E.3.2.18 **Map**

Properties	Description
Tables	F1_MAP, F1_MAP_L
Standard Data Fields	UI Map (MAP_CD)
Customer Modification	None

E.3.2.19 **Managed Content**

Properties	Description
Tables	F1_MANAG_CONTENT, F1_MANAG_CONTENT_L
Standard Data Fields	Managed Content (MANAG_CONTENT_CD)
Customer Modification	None

E.3.2.20 Messages

Properties	Description
Tables	CI_MSG_CATEGORY, CI_MSG_CATEGORY_L, CI_MSG, CI_MSG_L
Standard Data Fields	<p>Message Category (MESSAGE_CAT_NBR)</p> <ul style="list-style-type: none"> • Messages are grouped in categories and each category has message numbers between 1 and 99999. A range of message categories is assigned to a product. An implementation may only use categories assigned for customization use. • Implementer Message Categories are 80000 and 90000 • Reserved for Tests – 99999 <p>Message Number (MESSAGE_NBR) for message categories</p> <ul style="list-style-type: none"> • Message numbers below 1000 are reserved for common messages. Implementers must not use message numbers below 1000. <p>Message Number (MESSAGE_NBR) for Java message categories</p> <ul style="list-style-type: none"> • Subsystem Standard Messages - 00001 thru 02000 • Reserved - 02001 thru 09999 • Published Messages - 10001 thru 11000 • Package Messages - 10001 thru 90000 • Reserved - 90001 thru 99999 • Each package is allocated 100 message numbers, each starting from 101. • Published Messages are messages that are special-interest messages that implementations need to know about and are therefore published in the user docs. Examples of these include messages that are highly likely to be changed for an implementation or messages that are embedded into other texts/messages and therefore the message number is never shown. • Reserved message number ranges are for future use and therefore must not be used by all products.
Customer Modification	Override Description (DESCRLONG_OVRD), Message Text Override (MESSAGE_TEXT_OVRD)

E.3.2.21 Metadata - Table and Field

Properties	Description
Tables	CI_MD_TBL, CI_MD_TBL_FLD, CI_MD_TBL_L, CI_MD_TBL_FLD_L, CI_MD_FLD, CI_MD_FLD_L, F1_DB_OBJECTS_REPO
Standard Data Fields	Table Name (TBL_NAME) Table names must match with the physical table name or view name in the database. Field Name (FLD_NAME) Field name must match with the physical column name in the database unless the field is a work field. Field name does not have to follow the prefixing standard unless the field is a work field or customer modification field. F1_DB_OBJECTS_REPO Table stores information about Indexes, Sequences, Triggers and other database objects excluding Tables and Fields (as they are already stored in the other Metadata tables)
Customer Modification	Audit Switches (AUDIT_INSERT_SW, AUDIT_UPDATE_SW, AUDIT_DELETE_SW), Override label (OVRD_LABEL) on MD Table Field Table (CI_MD_TBL_FLD). Audit Program Name (AUDIT_PGM_NAME), Audit Table Name (AUDIT_TBL_NAME), Audit Program Type (AUDIT_PGM_TYPE_FLG), Key Validation (KEY_VALIDATION_FLG) and Caching strategy (CACHE_FLG) on MD Table (CI_MD_TBL). Override Label (OVRD_LABEL) and Customer Specific Description (DESCRLONG_OVRD) on Field Table.

E.3.2.22 Metadata – Constraints

Properties	Description
Tables	CI_MD_CONST, CI_MD_CONST_FLD
Standard Data Fields	Constraint Id (CONST_ID) Index Name for Primary Constraints <Index Name>Rnn for Foreign Key Constraints Where nn: integer, 01 through 99
Customer Modification	None

E.3.2.23 Metadata - Menu

Menus can be extended to support multiple products by adding a new menu line to an existing menu. The sequence number on the menu line language table (CI_MD_MENU_LINE_L) determines the order the menu lines appear. Within the same sequence, alphabetic sorting is used.

Properties	Description
Tables	CI_MD_MENU, CI_MD_MENU_L, CI_MD_MENU_ITEM, CI_MD_MENU_ITEM_L, CI_MD_MENU_LINE, CI_MD_MENU_LINE_L
Standard Data Fields	Menu Name (MENU_NAME), Menu Item Id (MENU_ITEM_ID), Menu Line Id (MENU_LINE_ID)
Customer Modification	Override Label (OVRD_LABEL) on Menu Line Language Table (CI_MD_MENU_LINE_L)

E.3.2.24 Metadata - Program, Location and Services

Properties	Description
Tables	CI_MD_PRG_COM, CI_MD_PRG_LOC, CI_MD_SVC, CI_MD_SVC_L, CI_MD_SVC_PRG, CI_MD_PRG_MOD, CI_MD_PRG_EL_AT, CI_MD_PRG_ELEM, CI_MD_PRG_SEC, CI_MD_PRG_SQL, CI_MD_PRG_VAR, CI_MD_PRG_TAB
Standard Data Fields	Program Component Id (PROG_COM_ID), Location Id (LOC_ID), Program Component Name (PROG_COM_NAME), Service Name (SVC_NAME), Navigation Key (NAVIGATION_KEY)
Customer Modification	User Exit Program Name (USER_EXIT_PGM_NAME) on Program Components Table (CI_MD_PRG_COM),

E.3.2.25 Metadata - Maintenance Object

Properties	Description
Tables	CI_MD_MO, CI_MD_MO_L, CI_MD_MO_TBL, CI_MD_MO_OPT, CI_MD_MO_ALG
Standard Data Fields	Maintenance Object (MAINT_OBJ_CD)
Customer Modification	None

E.3.2.26 Metadata - Work Tables

Properties	Description
Tables	CI_MD_WRK_TBL, CI_MD_WRK_TBL_L, CI_MD_WRK_TBLFLD, CI_MD_MO_WRK
Standard Data Fields	Work Table Name (WRK_TBL_NAME)
Customer Modification	None

E.3.2.27 Metadata - Search Object

Properties	Description
Tables	CI_MD_SO, CI_MD_SO_L, CI_MD_SO_RSFLD, CI_MD_SO_RSFLDAT, CI_MD_SOCG, CI_MD_SOCG_FLD, CI_MD_SOCG_FLDAT, CI_MD_SOCG_L, CI_MD_SOCG_SORT
Standard Data Fields	Search Object (SO_CD)
Customer Modification	None

E.3.2.28 Mobile Component

Properties	Description
Tables	F1_MOBILE_COMPONENT, F1_MOBILE_COMPONENT_L, F1_MOB_COMP_CNT, F1_MOBILE_COMP_CHAR
Standard Data Fields	Mobile Component Code (F1_MOB_COMP_TYPE_CD)
Customer Modification	Expiration Days (F1_EXPIRATION_TIME_DUR)

E.3.2.29 Navigation Option

Properties	Description
Tables	CI_NAV_OPT, CI_NAV_OPT_L, CI_NAV_OPT_CTXT, CI_NAV_OPT_USG, CI_MD_NAV
Standard Data Fields	Navigation Option Code (NAV_OPT_CD), Navigation Key (NAVIGATION_KEY)
Customer Modification	None

E.3.2.30 Outbound Message Type

Properties	Description
Tables	F1_OUTMSG_TYPE, F1_OUTMSG_TYPE_L
Standard Data Fields	Outbound Message Type Code (OUTMSG_TYPE_CD)
Customer Modification	Priority (OUTMSG_PRIOR_FLG)

E.3.2.31 Portal and Zone

Properties	Description
Tables	CI_PORTAL, CI_PORTAL_L, CI_PORTAL_ZONE, C1_PORTAL_OPT, CI_ZONE, CI_ZONE_L, CI_ZONE_PRM, CI_ZONE_HDL, CI_ZONE_HDL_L, CI_ZONE_HDL_PRM, CI_ZONE_HDL_PRM_L, CI_UI_ZONE, CI_PORTAL_OPT
Standard Data Fields	Portal Code (PORTAL_CD), Zone Code (ZONE_CD), Zone Type Code (ZONE_HDL_CD) <ul style="list-style-type: none"> • A new Zone can be added to the Product owned Portal Pages. • The existing Zones cannot be removed from the Product owned Portal Pages.
Customer Modification	Sort Sequence (SORT_SEQ) on Context Sensitive Zone Table (CI_UI_ZONE). Show on Portal Preferences (USER_CONFIG_FLG) on Portal Table (CI_PORTAL). Override Sequence (SORT_SEQ_OVRD) on Portal Zone Table (CI_PORTAL_ZONE). Customer Specific Description (DESCRLONG_OVRD) on Zone Language Table (CI_ZONE_L). Override Parameter Value (ZONE_HDL_PARM_OVRD) on Zone Type Parameters Table (CI_ZONE_HDL_PRM). Override Parameter Value (ZONE_PARM_VAL_OVRD) on Zone Parameters Table (CI_ZONE_PRM).

E.3.2.32 Process Flow Type

Properties	Description
Tables	F1_PROC_DEFN, F1_PROC_DEFN_L, F1_PROC_NEXT_PANEL, F1_PROC_PANEL
Standard Data Fields	Process Flow Type (PROCESS_CD)
Customer Modification	None

E.3.2.33 Sequence

Properties	Description
Tables	CI_SEQ
Standard Data Fields	Sequence Name (SEQ_NAME)
Customer Modification	Sequence Number (SEQ_NBR) This field is updated by the application process and must be set to 1 initially.

E.3.2.34 Schema

Properties	Description
Tables	F1_SCHEMA
Standard Data Fields	Schema Name (SCHEMA_NAME)
Customer Modification	None

E.3.2.35 Script

Properties	Description
Tables	CI_SCR, CI_SCR_L, CI_SCR_CRT, CI_SCR_CRT_GRP, CI_SCR_CRT_GRP_L, CI_SCR_DA, CI_SCR_FLD_MAP, CI_SCR_PRMPT, CI_SCR_PRMPT_L, CI_SCR_STEP, CI_SCR_STEP_L
Standard Data Fields	Script (SCR_CD)
Customer Modification	None

E.3.2.36 To Do Type

Properties	Description
Tables	CI_TD_TYPE, CI_TD_TYPE_L, CI_TD_SRTKEY_TY, CI_TD_DRLKEY_TY, CI_TD_SRTKEY_TY_L
Standard Data Fields	To Do Type (TD_TYPE_CD)
Customer Modification	Creation Batch Code (CRE_BATCH_CD), Route Batch Code (RTE_BATCH_CD), Priority Flag (TD_PRIORITY_FLG) on To Do Type Table (CI_TD_TYPE)

E.3.2.37 Web Service Category

Properties	Description
Tables	F1_WEB_CAT, F1_WEB_CAT_L, F1_WEB_CAT_INCL_SVC
Standard Data Fields	Web Service Category code (WEB_SVC_CAT_CD)
Customer Modification	None

E.3.2.38 XAI Configuration

Properties	Description
Tables	CI_XAI_ADAPTER, CI_XAI_ADAPTER_L, CI_XAI_CLASS, CI_XAI_CLASS_L, CI_XAI_ENV_HNDL, CI_XAI_ENV_HNDL_L, CI_XAI_FORMAT, CI_XAI_FORMAT_L, CI_XAI_RCVR, CI_XAI_RCVR_L, CI_XAI_RCVR_CTX, CI_XAI_RCVR_RSP, CI_XAI_RCVR_RGRP, CI_XAI_SENDER, CI_XAI_SERNDER_L, CI_XAI_SNDR_CTX, CI_XAI_OPTION
Standard Data Fields	Adapter Id (XAI_ADAPTER_ID), Class Id (XAI_CLASS_ID), Envelope Handler Id (XAI_ENV_HNDL_ID), XAI Format Id (XAI_FORMAT_ID), Receiver Id (XAI_RCVR_ID), Sender Id (XAI_SENDER_ID)
Customer Modification	Option Value (OPTION_VALUE) on Message Option Table (CI_XAI_OPTION)

E.3.2.39 XAI Services

Properties	Description
Tables	CI_XAI_IN_SVC, CI_XAI_IN_SVC_L, CI_XAI_SVC_PARM
Standard Data Fields	XAI Inbound Service Id (XAI_IN_SVC_ID), XAI Inbound Service Name (XAI_IN_SVC_NAME)
Customer Modification	XAI Version (XAI_VERSION_ID), Trace (TRACE_SW), Debug (DEBUG_SW), Request XSL (INPUT_XSL), Response XSL (RESPONSE_XSL), Record XSL (RECORD_XSL) and Post Error (POST_ERROR_SW) on XAI Inbound Service Table (CI_XAI_IN_SVC)

E.3.2.40 Inbound Web Service Operations Parameter

Properties	Description
Tables	F1_IWS_SVC_OPER_PARM
Standard Data Fields	Inbound Service Name (IN_SVC_NAME)
Customer Modification	None

E.3.2.41 Market Configuration

Properties	Description
Tables	F1_MKTCFG
Standard Data Fields	Market Configuration Code (MKTCFG_CD)
Customer Modification	None

E.3.2.42 File Integration

Properties	Description
Tables	F1_FILE_INT_REC, F1_FILE_INT_REC_L, F1_FILE_INT_REC_ALG, F1_FILE_INT_TYPE, F1_FILE_INT_TYPE_L
Standard Data Fields	File Integration Record (FILE_INT_REC_CD), File Integration Type (FILE_INT_TYPE_CD)
Customer Modification	None

E.3.2.43 Meta Data - BI

Properties	Description
Tables	F1_MD_BI_TBL, F1_MD_BI_TBL_L, F1_MD_BI_TBL_FLD
Standard Data Fields	Table Name (BI_TBL_NAME)
Customer Modification	None

E.3.2.44 Data Export Control

Properties	Description
Tables	F1_DATA_EXPORT_CTRL, F1_DATA_EXPORT_CTRL_LOG, F1_DATA_EXPORT_CTRL_LOG_PARM
Standard Data Fields	F1_DATA_EXPORT_CTRL (DATA_EXPORT_CD)
Customer Modification	None

E.4 System Table List

This section contains the names of system tables, upgrade actions, and a brief description of the tables. The upgrade actions are explained below.

Keep (KP): The data in the table in the customer's database is kept untouched. No insert or delete is performed to this table by the upgrade process. The initial installation will add necessary data for the system.

Merge (MG): The non-base product data in the table in the database is kept untouched. If the data belongs to the base product, any changes pertaining to the new version of the software are performed.

Refresh (RF): The existing data in the table is replaced with the data from the base product table. The product does not support customer specific data in these tables.

Note: New product data is also inserted into tables marked as 'Merge'. If implementers add rows for a customer specific enhancement, it can cause duplication when the system data gets upgraded to the next version. We strongly recommend following the guidelines on how to use designated range of values or prefixes to segregate the implementation data from the base product data.

Table Name	Upgrade Action	Description
CI_ALG	MG	Algorithm
CI_ALG_L	MG	Algorithm Language
CI_ALG_PARM	MG	Algorithm Parameters
CI_ALG_TYPE	MG	Algorithm Type
CI_ALG_TYPE_L	MG	Algorithm Type Language
CI_ALG_TYPE_PRM	MG	Algorithm Type Parameter
CI_ALG_TYPE_PRM_L	MG	Algorithm Type Parameter Language
CI_ALG_VER	MG	Algorithm Version
CI_APP_SVC_ACC	MG	Application Service Access Mode
CI_BATCH_CTRL	MG	Batch Control
CI_BATCH_CTRL_ALG	MG	Batch Control Algorithm
CI_BATCH_CTRL_L	MG	Batch Control Language
CI_BATCH_CTRL_P	MG	Batch Control Parameters
CI_BATCH_CTRL_P_L	MG	Batch Control Parameters Language
CI_CHAR_ENTITY	MG	Characteristic Type Entity
CI_CHAR_TYPE	MG	Characteristic Type
CI_CHAR_TYPE_L	MG	Characteristic Type Language
CI_CHAR_VAL	MG	Characteristic Type Value
CI_CHAR_VAL_L	MG	Characteristic Type Value Language

Table Name	Upgrade Action	Description
CI_DISP_ICON	MG	Display Icon
CI_DISP_ICON_L	MG	Display Icon Language
CI_FK_REF	MG	Foreign Key Reference
CI_FK_REF_L	MG	Foreign Key Reference Language
CI_LANGUAGE	MG	Language Code
CI_LOOKUP_FIELD	MG	Lookup Field
CI_LOOKUP_VAL	MG	Lookup Field Value
CI_LOOKUP_VAL_L	MG	Lookup Field Value Language
CI_MD_CONST	MG	Constraints
CI_MD_CONST_FLD	MG	Constraint Fields
CI_MD_FLD	MG	Field
CI_MD_FLD_L	MG	Field Language
CI_MD_MENU	MG	Menu Information
CI_MD_MENU_IMOD	MG	Menu Item Module Main
CI_MD_MENU_ITEM	MG	Menu Item
CI_MD_MENU_ITEM_L	MG	Menu Item Language
CI_MD_MENU_L	MG	Menu Language
CI_MD_MENU_LINE	MG	Menu Line
CI_MD_MENU_LINE_L	MG	Menu Line Language
CI_MD_MENU_MOD	MG	Menu Product Components
CI_MD_MO	MG	Maintenance Object
CI_MD_MO_ALG	MG	Maintenance Object Algorithm
CI_MD_MO_L	MG	Maintenance Object Language
CI_MD_MO_OPT	MG	Maintenance Object Option
CI_MD_MO_TBL	MG	Maintenance Object Table
CI_MD_MO_WRK	MG	Maintenance Object Work Tables
CI_MD_NAV	MG	Navigation Key
CI_MD_PRG_COM	MG	Program Components
CI_MD_PRG_ELEM	MG	UI Page Elements
CI_MD_PRG_EL_AT	MG	UI Page Element Attributes
CI_MD_PRG_LOC	MG	Program Location

Table Name	Upgrade Action	Description
CI_MD_PRG_MOD	MG	Program Module
CI_MD_PRG_SEC	MG	UI Page Sections
CI_MD_PRG_SQL	MG	MD SQL Meta Data
CI_MD_PRG_TAB	MG	UI Tab Meta Data
CI_MD_PRG_VAR	MG	Program Variable
CI_MD_SO	MG	Search Object
CI_MD_SOCG	MG	Search Object Criteria Group
CI_MD_SOCG_FLD	MG	Search Object Criteria Group Field
CI_MD_SOCG_FLDAT	MG	Search Criteria Group Field Attribute
CI_MD_SOCG_L	MG	Search Object Criteria Group Language
CI_MD_SOCG_SORT	MG	Search Criteria Group Result Sort Order
CI_MD_SO_L	MG	Search Object Language
CI_MD_SO_RSFLD	MG	Search Object Result Field
CI_MD_SO_RSFLDAT	MG	Search Object Result Field Attribute
CI_MD_SVC	MG	MD Service
CI_MD_SVC_L	MG	MD Service Language
CI_MD_SVC_PRG	MG	MD Service Program
CI_MD_TAB_MOD	MG	UI Tab Module
CI_MD_TBL	MG	MD Table
CI_MD_TBL_FLD	MG	MD Table Field
CI_MD_TBL_FLD_L	MG	MD Table Field Language
CI_MD_TBL_L	MG	MD Table Language
CI_MD_WRK_TBL	MG	Work Table
CI_MD_WRK_TBLFLD	MG	Work Table Field
CI_MD_WRK_TBL_L	MG	Work Table Language
CI_MSG	MG	Message
CI_MSG_CATEGORY	MG	Message Category
CI_MSG_CATEGORY_L	MG	Message Category Language
CI_MSG_L	MG	Message Language
CI_NAV_OPT	MG	Navigation Option
CI_NAV_OPT_CTXT	MG	Navigation Option Context

Table Name	Upgrade Action	Description
CI_NAV_OPT_L	MG	Navigation Option Language
CI_NAV_OPT_USG	MG	Navigation Option Usage
CI_PORTAL	MG	Portal
CI_PORTAL_L	MG	Portal Language
CI_PORTAL_OPT	MG	Portal Option
CI_PORTAL_ZONE	MG	Portal Zone
CI_SCR	MG	Script
CI_SCR_CRT	MG	Script Criteria
CI_SCR_CRT_GRP	MG	Script Criteria Group
CI_SCR_CRT_GRP_L	MG	Script Criteria Group Language
CI_SCR_DA	MG	Script Data Area
CI_SCR_FLD_MAP	MG	Script Field Mapping
CI_SCR_L	MG	Script Language
CI_SCR_PRMPT	MG	Script Prompt
CI_SCR_PRMPT_L	MG	Script Prompt Language
CI_SCR_STEP	MG	Script Step
CI_SCR_STEP_L	MG	Script Step Language
CI_SEQ	MG	Sequence
CI_TD_DRLKEY_TY	MG	To Do Type Drill Key
CI_TD_SRTKEY_TY	MG	To Do Type Sort Key
CI_TD_SRTKEY_TY_L	MG	To Do Type Sort Key Language
CI_TD_TYPE	MG	To Do Type
CI_TD_TYPE_L	MG	To Do Type Language
CI_UI_ZONE	MG	Context Sensitive Zone
CI_USR_NAV_LINK	MG	User Favorite Links
CI_XAI_ADAPTER	MG	XAI Adapter
CI_XAI_ADAPTER_L	MG	XAI Adapter Lang
CI_XAI_CLASS	MG	Message Class
CI_XAI_CLASS_L	MG	Message Class Language
CI_XAI_ENV_HNDL	MG	XAI Envelope Handler
CI_XAI_ENV_HNDL_L	MG	XAI Envelope Handler Language

Table Name	Upgrade Action	Description
CI_XAI_IN_SVC	MG	XAI Inbound Service
CI_XAI_IN_SVC_L	MG	XAI Inbound Service Language
CI_XAI_SVC_PARM	MG	XAI Inbound Service Parameters
CI_ZONE	MG	Zone
CI_ZONE_HDL	MG	Zone Type
CI_ZONE_HDL_L	MG	Zone Type Language
CI_ZONE_HDL_PRM	MG	Zone Type Parameters
CI_ZONE_HDL_PRM_L	MG	Zone Type Parameters Language
CI_ZONE_L	MG	Zone Language
CI_ZONE_PRM	MG	Zone Parameters
F1_BUS_OBJ	MG	Business Object
F1_BUS_OBJ_ALG	MG	Business Object Algorithm
F1_BUS_OBJ_L	MG	Business Object Language
F1_BUS_OBJ_OPT	MG	Business Object Option
F1_BUS_OBJ_STATUS	MG	Business Object Status
F1_BUS_OBJ_STATUS_ALG	MG	Business Object Status Algorithm
F1_BUS_OBJ_STATUS_L	MG	Business Object Status Language
F1_BUS_OBJ_STATUS_OPT	MG	Business Object Status Option
F1_BUS_OBJ_STATUS_RSN	MG	Status Reason
F1_BUS_OBJ_STATUS_RSN_L	MG	Status Reason Language
F1_BUS_OBJ_TR_RULE	MG	Business Object Transition Rule
F1_BUS_OBJ_TR_RULE_L	MG	Business Object Transition Rule Language
F1_BUS_SVC	MG	Business Service
F1_BUS_SVC_L	MG	Business Service Language
F1_DATA_AREA	MG	Data Area
F1_DATA_AREA_L	MG	Data Area Language
F1_DB_OBJECTS_REPO	MG	Database Objects Repository
F1_DEPLOYMENT_ITEM	MG	Deployment Part Item
F1_DEPLOYMENT_PART	MG	Deployment Part
F1_DEPLOYMENT_PART_L	MG	Deployment Part Language
F1_EXT_LOOKUP_VAL	MG	Extendable Lookup

Table Name	Upgrade Action	Description
F1_EXT_LOOKUP_VAL_L	MG	Extendable Lookup Language
F1_EXT_LOOKUP_VAL_CHAR	MG	Extendable Lookup Characteristics
F1_IWS_ANN	MG	Web Service Annotation
F1_IWS_ANN_L	MG	Web Service Annotation Language
F1_IWS_ANN_PARM	MG	Web Service Annotation Parameter
F1_IWS_ANN_TYPE	MG	Web Service Annotation Type
F1_IWS_ANN_TYPE_L	MG	Web Service Annotation Type Language
F1_IWS_ANN_TYPE_PARM	MG	Web Service Annotation Type Parm
F1_IWS_ANN_TYPE_PARM_L	MG	Web Service Annotation Type Parameter Language
F1_IWS_SVC	MG	Inbound Web Service
F1_IWS_SVC_L	MG	Inbound Web Service Language
F1_IWS_SVC_OPER	MG	Inbound Web Service Operations
F1_IWS_SVC_OPER_PARM	MG	Inbound Web Service Operations Parameter
F1_MKTCFG	MG	Market Configuration
F1_MANAG_CONTENT	MG	Managed Content
F1_MANAG_CONTENT_L	MG	Managed Content Language
F1_MAP	MG	UI Map
F1_MAP_L	MG	UI Map Language
F1_MIGR_PLAN	MG	Migration Plan
F1_MIGR_PLAN_INSTR	MG	Migration Plan Instruction
F1_MIGR_PLAN_INSTR_ALG	MG	Migration Plan Instruction Algorithm
F1_MIGR_PLAN_INSTR_L	MG	Migration Plan Instruction Language
F1_MIGR_PLAN_L	MG	Migration Plan Language
F1_MIGR_REQ	MG	Migration Request
F1_MIGR_REQ_INCL_REQ	MG	Migration Request Grouping
F1_MIGR_REQ_INSTR	MG	Migration Request Instruction
F1_MIGR_REQ_INSTR_ENTITY	MG	Migration Request Instruction Entity
F1_MIGR_REQ_INSTR_L	MG	Migration Request Instruction Language
F1_MIGR_REQ_L	MG	Migration Request Language

Table Name	Upgrade Action	Description
F1_MOBILE_COMPONENT	MG	Mobile Component
F1_MOBILE_COMPONENT_L	MG	Mobile Component Language
F1_MOB_COMP_CHAR	MG	Mobile Component Characteristics
F1_MOB_COMP_CNT	MG	Mobile Component Content
F1_OUTMSG_TYPE	MG	Outbound Message Type
F1_OUTMSG_TYPE_L	MG	Outbound Message Type Language
F1_PROC_DEFN	MG	Process Flow Type
F1_PROC_DEFN_L	MG	Process Flow Type Language
F1_PROC_NEXT_PANEL	MG	Next Panel
F1_PROC_PANEL	MG	Process Panels
F1_SCHEMA	MG	Schema
F1_WEB_CAT	MG	Web Service Category
F1_WEB_CAT_L	MG	Web Service Category Language
F1_WEB_CAT_INCL_SVC	MG	Web Service Category Included Services
F1_FILE_INT_REC	MG	File Integration Record Table
F1_FILE_INT_REC_L	MG	File Integration Record Language Table
F1_FILE_INT_REC_ALG	MG	File Integration Record Algorithm Table
F1_FILE_INT_TYPE	MG	File Integration Type
F1_FILE_INT_TYPE_L	MG	File Integration Language Table
F1_MD_BI_TBL	MG	MD Table for BI
F1_MD_BI_TBL_L	MG	MD Language Table for BI
F1_MD_BI_TBL_FLD	MG	MD Field Table for BI
SC_ACCESS_CNTL	MG	User Group Access Control
SC_APP_SERVICE	MG	Application Service
SC_APP_SERVICE_L	MG	Application Service Language
SC_USR_GRP_PROF	MG	User Group Profile
CI_ACC_GRP	KP	Access Group
CI_ACC_GRP_DAR	KP	Access Group / Data Access Group
CI_ACC_GRP_L	KP	Access Group Language
CI_APP_SVC_SCTY	KP	Security Type Application Service
CI_CAL HOL	KP	Work Calendar Holidays

Table Name	Upgrade Action	Description
CI_CAL_HOL_L	KP	Work Calendar Holidays Language
CI_CAL_WORK	KP	Work Calendar
CI_CAL_WORK_L	KP	Work Calendar Language
CI_CHTY_TDTY	KP	To Do Type Template Characteristics
CI_COUNTRY	KP	Country
CI_COUNTRY_L	KP	Country Language
CI_CURRENCY_CD	KP	Currency Code
CI_CURRENCY_CD_L	KP	Currency Code Language
CI_DAR	KP	Data Access Role
CI_DAR_L	KP	Data Access Language
CI_DAR_USR	KP	Data Access User
CI_DISP_PROF	KP	Display Profile
CI_DISP_PROF_L	KP	Display Profile Language
CI_FUNC	KP	Function
CI_FUNC_FLD	KP	Function Field
CI_FUNC_FLD_L	KP	Function Field Language
CI_FUNC_L	KP	Function Language
CI_GEO_TYPE	KP	Geographic Type
CI_GEO_TYPE_L	KP	Geographic Type Language
CI_INSTALL_ALG	KP	Installation Algorithm
CI_INSTALL_MSG	KP	Installation Message
CI_INSTALL_MSG_L	KP	Installation Message Language
CI_INSTALL_PROD	KP	Installation Product
CI_MD_RPT	KP	Report Definition
CI_MD_RPT_L	KP	Report Language
CI_MD_RPT_LBL	KP	Report Labels
CI_MD_RPT_PARM	KP	Report Parameters
CI_MD_RPT_PARM_L	KP	Report Parameters Language
CI_MD_TOOLREP_XML	KP	MD Tool Reference XML
CI_MD_TOOL_REP	KP	MD Tool Reference
CI_NT_DNTY_CTXT	KP	Notification Download Type Context

Table Name	Upgrade Action	Description
CI_NT_DWN_FORM	KP	Notification Download Format
CI_NT_DWN_FORM_L	KP	Notification Download Format Language
CI_NT_DWN_PROF	KP	Notification Download Profile
CI_NT_DWN_PROF_L	KP	Notification Download Profile Language
CI_NT_DWN_TYPE	KP	Notification Download Type
CI_NT_DWN_TYPE_L	KP	Notification Download Type Language
CI_NT_UP_XTYPE	KP	Notification Upload Type
CI_NT_UP_XTYPE_L	KP	Notification Upload Type Language
CI_NT_XID	KP	External System
CI_NT_XID_L	KP	External System Language
CI_PHONE_TYPE	KP	Phone Type
CI_PHONE_TYPE_L	KP	Phone Type Language
CI_ROLE	KP	Role
CI_ROLE_L	KP	Role Language
CI_ROLE_USER	KP	Role User
CI_RPT_OPTION	KP	Report Options
CI_SC_AUTH_LVL	KP	Security Type Auth Level
CI_SC_AUTH_LVL_L	KP	Security Type Auth Level Language
CI_SC_TYPE	KP	Security Type
CI_SC_TYPE_L	KP	Security Type Language
CI_SEAS_SHIFT	KP	Seasonal Time Shift Schedule
CI_SEAS_TM_SHIFT	KP	Seasonal Time Shift
CI_SEAS_TM_SHIFT_L	KP	Seasonal Shift Language
CI_STATE	KP	State
CI_STATE_L	KP	State Language
CI_TD_EX_LIST	KP	To Do Type Message Overrides
CI_TD_TYPE_ALG	KP	To Do Type Algorithms
CI_TD_TYPE_CHAR	KP	To Do Type Characteristic
CI_TD_VAL_ROLE	KP	To Do Type Role
CI_TIME_ZONE	KP	Time Zone
CI_TIME_ZONE_L	KP	Time Zone Language

Table Name	Upgrade Action	Description
CI_USR_GRP_SC	KP	User Group Security Type
CI_USR_BOOKMARK	KP	User Bookmarks
CI_USR_PORTAL	KP	User Portal
CI_USR_SCR	KP	User Scripts
CI_USR_ZONE	KP	User Zone
CI_USR_ZONE_SAVE	KP	User Zone Save
CI_WFM	KP	Feature Configuration
CI_WFM_L	KP	Feature Configuration Language
CI_WFM_MSG	KP	Feature Configuration Message
CI_WFM_OPT	KP	Feature Configuration Options
CI_WF_EVT_TYPE	KP	WF Event Type
CI_WF_EVT_TYPE_L	KP	WF Event Type Language
CI_WF_PP	KP	WF Process Profile
CI_WF_PP_L	KP	WF Process Profile Language
CI_WF_PP_NT	KP	WF Process Notification
CI_WF_PP_NT_CRT	KP	WF Process Notification Criteria
CI_WF_PROC_SCHED	KP	WF Process Creation Schedule
CI_WF_PROC_SCHED_K	KP	WF Process Creation Schedule Key
CI_WF_PROC_TMPL	KP	WF Process Template
CI_WF_PROC_TMPL_L	KP	WF Process Template Language
CI_WF_RESP	KP	WF Response
CI_WF_RESP_DEP	KP	WF Response Dependency
CI_XAI_JDBC_CON	KP	XAI JDBC Connection
CI_XAI_JDBC_CON_L	KP	XAI JDBC Connection Language
CI_XAI_JMS_CON	KP	XAI JMS Connection
CI_XAI_JMS_CON_L	KP	XAI JMS Connection Language
CI_XAI_JMS_Q	KP	XAI JMS Queue
CI_XAI_JMS_Q_L	KP	XAI JMS Queue Language
CI_XAI_JMS_TPC	KP	XAI JMS Topic
CI_XAI_JMS_TPC_L	KP	XAI JMS Topic Language
CI_XAI_JNDI_SVR	KP	XAI JNDI Server

Table Name	Upgrade Action	Description
CI_XAI_JNDI_SVR_L	KP	XAI JNDI Server Language
CI_XAI_OPTION	KP	Message Option
CI_XAI_RCVR	KP	XAI Receiver
CI_XAI_RCVR_CTX	KP	XAI Receiver Context
CI_XAI_RCVR_L	KP	XAI Receiver Language
CI_XAI_RCVR_RGRP	KP	XAI Receiver Rule Group
CI_XAI_RCVR_RSP	KP	XAI Receiver Response
CI_XAI_RGRP	KP	XAI Rule Group
CI_XAI_RGRP_ATT	KP	XAI Rule Group Attachment
CI_XAI_RGRP_L	KP	XAI Rule Group Language
CI_XAI_ROUTING	KP	XAI Routing
CI_XAI_RT_TYPE	KP	XAI Route Type
CI_XAI_RT_TYPE_L	KP	XAI Route Type Language
CI_XAI_RULE	KP	XAI Rule
CI_XAI_SENDER	KP	Message Sender
CI_XAI_SENDER_L	KP	Message Sender Language
CI_XAI_SNDR_CTX	KP	Message Sender Context
F1_BKT_CONFIG	KP	Bucket Configuration
F1_BKT_CONFIG_L	KP	Bucket Configuration Language
F1_BKT_CONFIG_REL_OBJ	KP	Bucket Configuration Related Object
F1_BKT_CONFIG_VAL	KP	Bucket Configuration Value
F1_BKT_CONFIG_VAL_L	KP	Bucket Configuration Value Language
F1_BUS_OBJ_STATUS_RSN_CHAR	KP	Status Reason Characteristic
F1_EXTSYS_OUTMSG_PROF	KP	External System Outbound Message Type
F1_INSTALLATION	KP	Installation Option - Framework
F1_IWS_SVC_ANN	KP	Inbound Web Service Link to Annotation
F1_IWS_SVC_CHAR	KP	Inbound Web Service Characteristics
F1_IWS_SVC_LOG	KP	Inbound Web Service Log
F1_IWS_SVC_LOG_PARM	KP	Inbound Web Service Log Parameter
F1_MAP_OVRD	KP	UI Map Override
F1_MD_DB_OBJ	KP	MD Database Object

Table Name	Upgrade Action	Description
F1_MST_CONFIG	KP	Master Configuration
F1_OUTMSG_TYPE	KP	Outbound Message Type
F1_OUTMSG_TYPE_L	KP	Outbound Message Type Language
F1_REQ_TYPE	KP	Request Type
F1_REQ_TYPE_L	KP	Request Type Language
F1_REQ_TYPE_LOG	KP	Request Type Log
F1_REQ_TYPE_LOG_PARM	KP	Request Type Log Parameters
F1_SVC_TASK_TYPE	KP	Service Task Type
F1_SVC_TASK_TYPE_CHAR	KP	Service Task Type Characteristics
F1_SVC_TASK_TYPE_L	KP	Service Task Type Language
F1_WEB_SVC	KP	Web Service Adapter
F1_WEB_SVC_CHAR	KP	Web Service Adapter Characteristics
F1_WEB_SVC_L	KP	Web Service Adapter Language
F1_WEB_SVC_LOG	KP	Web Service Adapter Log
F1_WEB_SVC_LOG_PARM	KP	Web Service Adapter Log Parameter
F1_WEB_SVC_OPERATIONS	KP	Web Service Adapter Operations
SC_USER	KP	User
SC_USER_CHAR	KP	User Characteristic
SC_USER_GROUP	KP	User Group
SC_USER_GROUP_L	KP	User Group Language
SC_USR_GRP_USR	KP	User Group User
CI_MD_ATT_TY	RF	MD Element Attribute Type
CI_MD_AT_DTL	RF	MD Element Attribute Type Detail
CI_MD_AT_DTL_L	RF	MD Element Attribute Type Detail Language
CI_MD_CTL	RF	Generator Control
CI_MD_CTL_L	RF	Generator Control Language
CI_MD_CTL_TMPL	RF	Generator Control Template
CI_MD_ELTY	RF	MD Element Type
CI_MD_ELTY_AT	RF	Element Type Attributes
CI_MD_ELTY_L	RF	Element Type Language

Table Name	Upgrade Action	Description
CI_MD_LOOKUP_F	RF	MD Lookup Field
CI_MD_MSG	RF	MD Message
CI_MD_MSG_L	RF	MD Message Language
CI_MD_PDF	RF	Predefined Fields
CI_MD_PDF_VAL	RF	Predefined Values
CI_MD_SRC_TYPE	RF	Source Type
CI_MD_SRC_TYPE_L	RF	Source Type Language
CI_MD_TMPL	RF	Template
CI_MD_TMPL_ELTY	RF	Template Element Types
CI_MD_TMPL_L	RF	Template Language
CI_MD_TMPL_VAR	RF	Template Variable
CI_MD_TMPL_VAR_L	RF	Template Variable Language
CI_MD_VAR	RF	Variable
CI_MD_VAR_DTL	RF	Variable Detail
CI_MD_VAR_DTL_L	RF	Variable Detail Language
CI_XAI_EXECUTER	RF	XAI Executer
CI_XAI_EXECUTER_L	RF	XAI Executer Language
CI_XAI_FORMAT	RF	XAI Format
CI_XAI_FORMAT_L	RF	XAI Format Language
F1_LGCY_OBJ	RF	Unsupported Metadata

Appendix F : ORMB V3.1.0.0.0 Rollup Packs

Instead of individually applying the patches, you can download and apply the release-specific rollup packs. To view the list of rollup packs that you need to apply on the database, refer to the *ORMB V3.1.0.0.0 Patch Guide (Document ID: 2815177.1)* on [My Oracle Support](#).

F.1 Applying a Rollup Pack

Once you install Oracle Revenue Management and Billing Version 3.1.0.0.0, you need to apply the rollup packs listed in the *ORMB V3.1.0.0.0 Patch Guide (Document ID: 2815177.1)*. You can apply a rollup pack from a Windows machine and UNIX Standalone server. To apply a rollup pack:

1. Download the rollup pack from [My Oracle Support](#). A zip file is downloaded.
2. Unzip the downloaded file in your local folder. The contents include the `README.txt` file and three folders named `RMB_V3.1.0.0.0_App_Rollup`, `RMB_V3.1.0.0.0_DB_Rollup`, and `RMB_V3.1.0.0.0_PFDs`.
3. Change to the `RMB_V3.1.0.0.0_DB_Rollup` folder using the following command:

AIX, Linux:

```
cd <DESTINATION_FOLDER_1>/RMB_V3.1.0.0.0_DB_Rollup
```

Windows:

```
cd <DESTINATION_FOLDER_1>\RMB_V3.1.0.0.0_DB_Rollup
```

Note: The `<DESTINATION_FOLDER_1>` folder is the location where you have extracted the contents of the rollup pack.

4. Execute the `ouafDatabasePatch` utility using the following command:

Windows:

```
ouafDatabasePatch.cmd
```

AIX, Linux:

```
ouafDatabasePatch.sh
```

Note: On the AIX and Linux platforms, ensure that you grant the execute permission for the `ouafDatabasePatch.sh` utility using the following command:

```
chmod 755 ouafDatabasePatch.sh
```

Appendix G : License and Copyright Notices

This section provides license and copyright information for the associated products. It includes the following notices:

- [Notice Concerning Usage of ANTLR](#)
- [Notice Concerning Usage of Apache Software](#)
- [Notice Concerning Usage of ASM](#)
- [Notice Concerning Usage of Bouncy Castle Crypto API](#)
- [Notice Concerning Usage of CodeMirror](#)
- [Notice Concerning Usage of Concurrent](#)
- [Notice Concerning Usage of Cordova Plugin Pin Check](#)
- [Notice Concerning Usage of Cordova Plugin Fingerprint aio](#)
- [Notice Concerning Usage of Cordova Plugin Secure Keystore](#)
- [Notice Concerning Usage of Cordova Plugin Shared Preferences](#)
- [Notice Concerning Usage of DOM4J](#)
- [Notice Concerning Usage of FullCalendar](#)
- [Notice Concerning Usage of Graph Builder](#)
- [Notice Concerning Usage of International Components for Unicode \(ICU4J\)](#)
- [Notice Concerning Usage of Jaxen](#)
- [Notice Concerning Usage of JQuery \(3.5.1\)](#)
- [Notice Concerning Usage of JQueryMobile](#)
- [Notice Concerning Usage of JQuery UI](#)
- [Notice Concerning Usage of JSignature](#)
- [Notice Concerning Usage of Knockout](#)
- [Notice Concerning Usage of Microsoft .NET](#)
- [Notice Concerning Usage of Moment.js](#)
- [Notice Concerning Usage of SLF4J](#)
- [Notice Concerning Usage of Staxmate](#)
- [Notice Concerning Usage of Swagger-UI](#)
- [Notice Concerning Usage of XMLPULL](#)
- [Notice Concerning Usage of XStream](#)

G.1 Third-Party Products

The following sections provide notices and information about the third party products indicated.

G.1.1 Notice Concerning Usage of ANTLR

The following files are covered under this license:

- antlr-2.7.7.jar
- antlr4-runtime-4.7.2.jar

[The BSD License]

Copyright (c) 2012 Terence Parr and Sam Harwell

All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- Neither the name of the author nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

G.1.2 Notice Concerning Usage of Apache Software

The following JAR files and components are covered under this license:

- accessors-smart-1.3.jar
- ant-1.10.9.jar
- Apache Cordova 7.0.0
- apache-xmlbeans-3.1.0.jar
- batik-all-1.14.jar
- Castor 1.4.1
- cglib-3.3.0.jar

- commons-beanutils-1.9.4.jar
- commons-cli-1.4-c12260c.jar
- commons-codec-1.14.jar
- commons-codec-1.15.jar
- commons-collections-3.2.2.jar
- commons-collections4-4.4.jar
- commons-compress-1.19.jar
- commons-fileupload-1.4.jar
- commons-io-2.7.jar
- commons-io-2.8.0.jar
- commons-lang3-3.9.jar
- commons-logging-1.2.jar
- commons-logging-1.2-9f99a00.jar
- commons-math3-3.6.1.jar
- commons-text-1.9.jar
- Cordova Android 6.4.0
- Cordova App-Event Plugin 1.2.1
- Cordova Camera Plugin 4.0.3
- Cordova Command Line Interface 8.0.0
- Cordova Device Plugin 2.0.2
- Cordova File Plugin 6.0.1
- Cordova File Transfer Plugin 1.7.1
- Cordova Geolocation Plugin 4.0.1
- Cordova inappbrowser plugin 3.0.0
- Cordova iOS 4.4.0
- Cordova Local Notification Plugin 0.8.5
- Cordova Network Information Plugin 2.0.1
- Cordova SQLite storage adapter 2.3.3
- Cordova WebSQL PlugIn 0.0.10
- Cordova Whitelist Plugin 1.0.0
- cordova-plugin-compat 1.1.0
- ehcache-core-2.5.2.jar
- fontbox-2.0.22.jar
- fop-2.6.jar
- groovy-3.0.7.jar
- groovy-xml-3.0.7.jar
- httpclient-4.5.13.jar
- httpclient-cache-4.1.2.jar

- httpcore-4.4.13.jar
- httpmime-4.1.2.jar
- jackson-annotations-2.10.3.jar
- jackson-core-2.10.3.jar
- jackson-databind-2.10.3.jar
- jboss-logging-3.4.1.Final.jar
- jcl-over-slf4j-1.7.30.jar
- jettison-1.4.1.jar
- joda-time-2.9.6.jar
- json-smart-2.4.jar
- log4j-1.2-api-2.14.0.jar
- log4j-api-2.13.3.jar
- log4j-core-2.13.3.jar
- nimbus-jose-jwt-8.19.jar
- poi-4.1.2.jar
- poi-ooxml-4.1.2.jar
- poi-ooxml-schemas-4.1.2.jar
- serializer-2.7.2.jar
- SparseBitSet-1.2.jar
- velocity-engine-core-2.1.jar
- xalan-2.7.2.jar
- xercesImpl-2.12.1.jar
- xml-apis-1.4.01.jar
- xml-apis-ext-1.3.04.jar
- xmlbeans-3.1.0.jar
- xmlgraphics-commons-2.6.jar
- xmlschema-core-2.2.4.jar
- xpp3-1.1.4c.jar

Apache License

Version 2.0, January 2004

<http://www.apache.org/licenses/>

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions

“License” shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

“Licensor” shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

“Legal Entity” shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, “control” means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

“You” (or “Your”) shall mean an individual or Legal Entity exercising permissions granted by this License.

“Source” form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

“Object” form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

“Work” shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

“Derivative Works” shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

“Contribution” shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, “submitted” means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as “Not a Contribution.”

“Contributor” shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. **Grant of Copyright License**

Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License

Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution

You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that you meet the following conditions:

- You must give any other recipients of the Work or Derivative Works a copy of this License; and
- You must cause any modified files to carry prominent notices stating that You changed the files; and
- You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and
- If the Work includes a “NOTICE” text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add your own attribution notices within Derivative Works that you distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License. You may add your own copyright statement to your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of your modifications, or for any such Derivative Works as a whole, provided your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions

Unless you explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by you to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks

This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty

Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with your exercise of permissions under this License.

8. Limitation of Liability

In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability

While redistributing the Work or Derivative Works thereof, you may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

G.1.3 Notice Concerning Usage of ASM

The following file is covered under this license:

- asm-8.0.jar

Copyright (c) 2000-2005 INRIA, France Telecom

All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

- Neither the name of the copyright holders nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

G.1.4 Notice Concerning Usage of Bouncy Castle Crypto API

The following files are covered under this license:

- bcpkix-jdk15on-1.68.jar
- bcprov-jdk15on-1.68.jar
- bcpk-jdk15to18-1.68.jar
- bcprov-jdk15to18-1.68.jar

Except where otherwise stated, this software is distributed under a license based on the MIT X Consortium license. The OpenPGP library also includes a modified BZIP2 library which is licensed under the Apache Software License, Version 2.0.

MIT X Consortium License:

Copyright (c) 2000 - 2021 The Legion of the Bouncy Castle Inc. (<https://www.bouncycastle.org>)

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

G.1.5 Notice Concerning Usage of CodeMirror

Copyright (C) 2017 by Marijn Haverbeke <marijnh@gmail.com> and others.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

G.1.6 Notice Concerning Usage of Concurrent

All classes are released to the public domain and may be used for any purpose whatsoever without permission or acknowledgment.

<http://gee.cs.oswego.edu/dl/classes/EDU/oswego/cs/dl/util/concurrent/intro.html>

G.1.7 Notice Concerning Usage of Cordova Plugin Pin Check

Copyright (c) 2015 Crypho AS.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

G.1.8 Notice Concerning Usage of Cordova Plugin Fingerprint aio

Copyright (c) 2016-2018 Niklas Merz

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

G.1.9 Notice Concerning Usage of Cordova Plugin Secure Keystore

Copyright (c) 2017 Pradeep Singh

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

G.1.10 Notice Concerning Usage of Cordova Plugin Shared Preferences

Copyright (c) 2017 Adriano Di Giovanni

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

G.1.11 Notice Concerning Usage of DOM4J

The following file is covered under this license:

- dom4j-2.1.3.jar

Copyright 2001-2010 (C) MetaStuff, Ltd. All Rights Reserved.

Redistribution and use of this software and associated documentation ("Software"), with or without modification, are permitted provided that the following conditions are met:

- Redistributions of source code must retain copyright statements and notices. Redistributions must also contain a copy of this document.
- Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- The name "DOM4J" must not be used to endorse or promote products derived from this Software without prior written permission of MetaStuff, Ltd. For written permission, please contact dom4j-info@metastuff.com.
- Products derived from this Software may not be called "DOM4J" nor may "DOM4J" appear in their names without prior written permission of MetaStuff, Ltd. DOM4J is a registered trademark of MetaStuff, Ltd.
- Due credit should be given to the DOM4J Project - <http://dom4j.sourceforge.net>.

THIS SOFTWARE IS PROVIDED BY METASTUFF, LTD. AND CONTRIBUTORS ``AS IS'' AND ANY EXPRESSED OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL METASTUFF, LTD. OR ITS CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

G.1.12 Notice Concerning Usage of FullCalendar

Copyright (c) 2015 Adam Shaw

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

G.1.13 Notice Concerning Usage of Graph Builder

The following file is covered under this license:

- curvesapi-1.06.jar

Copyright (c) 2005, Graph Builder

All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- Neither the name of Graph Builder nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

G.1.14 Notice Concerning Usage of International Components for Unicode (ICU4J)

The following file is covered under this license:

- icu4j-64.2.jar

COPYRIGHT AND PERMISSION NOTICE

Copyright (c) 1995-2010 International Business Machines Corporation and others

All rights reserved.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, provided that the above copyright notice(s) and this permission notice appear in all copies of the Software and that both the above copyright notice(s) and this permission notice appear in supporting documentation.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OF THIRD PARTY RIGHTS. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR HOLDERS INCLUDED IN THIS NOTICE BE LIABLE FOR ANY CLAIM, OR ANY SPECIAL INDIRECT OR CONSEQUENTIAL DAMAGES, OR ANY DAMAGES WHATSOEVER RESULTING FROM LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR OTHER TORTIOUS ACTION, ARISING OUT OF OR IN CONNECTION WITH THE USE OR PERFORMANCE OF THIS SOFTWARE.

Except as contained in this notice, the name of a copyright holder shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Software without prior written authorization of the copyright holder.

G.1.15 Notice Concerning Usage of Jaxen

The following file is covered under this license:

- jaxen-mod-1.2.0.jar

Copyright 2003-2006 The Werken Company. All Rights Reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- Neither the name of the Jaxen Project nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

G.1.16 Notice Concerning Usage of JQuery (3.5.1)

Copyright JS Foundation and other contributors, <https://js.foundation/>

Copyright © 2019 Kyle Simpson <getify@gmail.com>

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

G.1.17 Notice Concerning Usage of JQueryMobile

jQuery Foundation projects are released under the terms of the license specified in the project's repo or if not specified, under the MIT license.

<https://tldrlegal.com/license/mit-license>

The MIT License is simple and easy to understand and it places almost no restrictions on what you can do with a jQuery Foundation project.

You are free to use any jQuery Foundation project in any other project (even commercial projects) as long as the copyright header is left intact.

G.1.18 Notice Concerning Usage of JQuery UI

Copyright jQuery Foundation and other contributors, <https://jquery.org/>

This software consists of voluntary contributions made by many individuals. For exact contribution history, see the revision history available at <https://github.com/jquery/jquery-ui>.

The following license applies to all parts of this software except as documented below: Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

G.1.19 Notice Concerning Usage of JSIgnature

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

G.1.20 Notice Concerning Usage of Knockout

Copyright (c) 2013 Steven Sanderson

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

G.1.21 Notice Concerning Usage of Microsoft .NET

MICROSOFT SOFTWARE LICENSE TERMS MICROSOFT .NET LIBRARY

These license terms are an agreement between Microsoft Corporation (or based on where you live, one of its affiliates) and you. Please read them. They apply to the software named above, which includes the media on which you received it, if any.

The terms also apply to any Microsoft updates, supplements, Internet-based services, and support services for this software, unless other terms accompany those items. If so, those terms apply. BY USING THE SOFTWARE, YOU ACCEPT THESE TERMS. IF YOU DO NOT ACCEPT THEM, DO NOT USE THE SOFTWARE.

IF YOU COMPLY WITH THESE LICENSE TERMS, YOU HAVE THE PERPETUAL RIGHTS BELOW.

1. INSTALLATION AND USE RIGHTS.

- d. **Installation and Use** - You may install and use any number of copies of the software to design, develop and test your programs.
- e. **Third Party Programs** - The software may include third party programs that Microsoft, not the third party, licenses to you under this agreement. Notices, if any, for the third party program are included for your information only.

2. ADDITIONAL LICENSING REQUIREMENTS AND/OR USE RIGHTS.

1. **DISTRIBUTABLE CODE** - The software is comprised of Distributable Code.

"Distributable Code" is code that you are permitted to distribute in programs you develop if you comply with the terms below.

i. **Right to Use and Distribute** -

- You may copy and distribute the object code form of the software.
- Third Party Distribution. You may permit distributors of your programs to copy and distribute the Distributable Code as part of those programs.

ii. **Distribution Requirements** - For any Distributable Code you distribute, you must

- add significant primary functionality to it in your programs;
- require distributors and external end users to agree to terms that protect it at least as much as this agreement;
- display your valid copyright notice on your programs; and
- indemnify, defend, and hold harmless Microsoft from any claims, including attorneys' fees, related to the distribution or use of your programs.

iii. **Distribution Restrictions** - You may not

- alter any copyright, trademark or patent notice in the Distributable Code;
- use Microsoft's trademarks in your programs' names or in a way that suggests your programs come from or are endorsed by Microsoft;
- include Distributable Code in malicious, deceptive or unlawful programs; or
- modify or distribute the source code of any Distributable Code so that any part of it becomes subject to an Excluded License. An Excluded License is one that requires, as a condition of use, modification or distribution, that the code be disclosed or distributed in source code form; or others have the right to modify it.

3. SCOPE OF LICENSE.

The software is licensed, not sold. This agreement only gives you some rights to use the software. Microsoft reserves all other rights. Unless applicable law gives you more rights despite this limitation, you may use the software only as expressly permitted in this agreement. In doing so, you must comply with any technical limitations in the software that only allow you to use it in certain ways. You may not:

- work around any technical limitations in the software;
- reverse engineer, decompile or disassemble the software, except and only to the extent that applicable law expressly permits, despite this limitation;
- publish the software for others to copy;
- rent, lease or lend the software;
- transfer the software or this agreement to any third party; or
- use the software for commercial software hosting services.

4. BACKUP COPY.

You may make one backup copy of the software. You may use it only to reinstall the software.

5. DOCUMENTATION.

Any person that has valid access to your computer or internal network may copy and use the documentation for your internal, reference purposes.

6. EXPORT RESTRICTIONS.

The software is subject to United States export laws and regulations. You must comply with all domestic and international export laws and regulations that apply to the software. These laws include restrictions on destinations, end users and end use. For additional information, see www.microsoft.com/exporting.

7. SUPPORT SERVICES.

Because this software is "as is," we may not provide support services for it.

8. ENTIRE AGREEMENT.

This agreement, and the terms for supplements, updates, Internet-based services and support services that you use, are the entire agreement for the software and support services.

9. APPLICABLE LAW.**1. United States.**

If you acquired the software in the United States, Washington state law governs the interpretation of this agreement and applies to claims for breach of it, regardless of conflict of laws principles. The laws of the state where you live govern all other claims, including claims under state consumer protection laws, unfair competition laws, and in tort.

2. Outside the United States.

If you acquired the software in any other country, the laws of that country apply.

10. LEGAL EFFECT.

This agreement describes certain legal rights. You may have other rights under the laws of your country. You may also have rights with respect to the party from whom you acquired the software. This agreement does not change your rights under the laws of your country if the laws of your country do not permit it to do so.

11. DISCLAIMER OF WARRANTY.

THE SOFTWARE IS LICENSED "AS-IS." YOU BEAR THE RISK OF USING IT. MICROSOFT GIVES NO EXPRESS WARRANTIES, GUARANTEES OR CONDITIONS. YOU MAY HAVE ADDITIONAL CONSUMER RIGHTS OR STATUTORY GUARANTEES UNDER YOUR LOCAL LAWS WHICH THIS AGREEMENT CANNOT CHANGE. TO THE EXTENT PERMITTED UNDER YOUR LOCAL LAWS, MICROSOFT EXCLUDES THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NON-INFRINGEMENT.

FOR AUSTRALIA – YOU HAVE STATUTORY GUARANTEES UNDER THE AUSTRALIAN CONSUMER LAW AND NOTHING IN THESE TERMS IS INTENDED TO AFFECT THOSE RIGHTS.

12. LIMITATION ON AND EXCLUSION OF REMEDIES AND DAMAGES.

YOU CAN RECOVER FROM MICROSOFT AND ITS SUPPLIERS ONLY DIRECT DAMAGES UP TO U.S. \$5.00. YOU CANNOT RECOVER ANY OTHER DAMAGES, INCLUDING CONSEQUENTIAL, LOST PROFITS, SPECIAL, INDIRECT OR INCIDENTAL DAMAGES.

This limitation applies to:

- anything related to the software, services, content (including code) on third party Internet sites, or third party programs; and
- claims for breach of contract, breach of warranty, guarantee or condition, strict liability, negligence, or other tort to the extent permitted by applicable law.

It also applies even if Microsoft knew or should have known about the possibility of the damages. The above limitation or exclusion may not apply to you because your country may not allow the exclusion or limitation of incidental, consequential or other damages.

Please note: As this software is distributed in Quebec, Canada, some of the clauses in this agreement are provided below in French.

Remarque : Ce logiciel étant distribué au Québec, Canada, certaines des clauses dans ce contrat sont fournies ci-dessous en français.

EXONÉRATION DE GARANTIE. Le logiciel visé par une licence est offert « tel quel ». Toute utilisation de ce logiciel est à votre seule risque et péril. Microsoft n'accorde aucune autre garantie expresse. Vous pouvez bénéficier de droits additionnels en vertu du droit local sur la protection des consommateurs, que ce contrat ne peut modifier. La ou elles sont permises par le droit locale, les garanties implicites de qualité marchande, d'adéquation à un usage particulier et d'absence de contrefaçon sont exclues.

LIMITATION DES DOMMAGES-INTÉRÊTS ET EXCLUSION DE RESPONSABILITÉ POUR LES DOMMAGES. Vous pouvez obtenir de Microsoft et de ses fournisseurs une indemnisation en cas de dommages directs uniquement à hauteur de 5,00 \$ US. Vous ne pouvez prétendre à aucune indemnisation pour les autres dommages, y compris les dommages spéciaux, indirects ou accessoires et pertes de bénéfices.

Cette limitation concerne:

- tout ce qui est relié au logiciel, aux services ou au contenu (y compris le code) figurant sur des sites Internet tiers ou dans des programmes tiers ; et
- les réclamations au titre de violation de contrat ou de garantie, ou au titre de responsabilité stricte, de négligence ou d'une autre faute dans la limite autorisée par la loi en vigueur.

Elle s'applique également, même si Microsoft connaît ou devrait connaître l'éventualité d'un tel dommage. Si votre pays n'autorise pas l'exclusion ou la limitation de responsabilité pour les dommages indirects, accessoires ou de quelque nature que ce soit, il se peut que la limitation ou l'exclusion ci-dessus ne s'appliquera pas à votre égard.

EFFET JURIDIQUE. Le présent contrat décrit certains droits juridiques. Vous pourriez avoir d'autres droits prévus par les lois de votre pays. Le présent contrat ne modifie pas les droits que vous confèrent les lois de votre pays si celles-ci ne le permettent pas.

G.1.22 Notice Concerning Usage of Moment.js

Copyright (c) 2011-2013 Tim Wood, Iskren Chernev, Moment.js contributors

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

G.1.23 Notice Concerning Usage of SLF4J

The following files are covered under this license:

- slf4j-api-1.7.30.jar

SLF4J source code and binaries are distributed under the MIT license.

Copyright (c) 2004-2013 QOS.ch. All rights reserved.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

G.1.24 Notice Concerning Usage of Staxmate

The following file is covered under this license:

- staxmate-2.4.0.jar

Copyright (c) 2007, Tatu Saloranta

All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- Neither the name of the <organization> nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY <copyright holder> ``AS IS'' AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL <copyright holder> BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

G.1.25 Notice Concerning Usage of Swagger-UI

Copyright 2016 SmartBear Software

Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except in compliance with the License. You may obtain a copy of the License at <http://apache.org/licenses/LICENSE-2.0>.

Unless required by applicable law or agreed to in writing, software distributed under the License is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the License for the specific language governing permissions and limitations under the License.

<https://github.com/es-shims/es5-shim/blob/master/LICENSE>

The MIT License (MIT)

Copyright (C) 2009-2016 Kristopher Michael Kowal and contributors

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

handlebars v4.0.5

Copyright (C) 2011-2015 by Yehuda Katz

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

jQuery BBQ: Back Button & Query Library - v1.2.1 - 2/17/2010 <http://benalman.com/projects/jquery-bbq-plugin/>

Copyright (c) 2010 "Cowboy" Ben Alman

Dual licensed under the MIT and GPL licenses. <http://benalman.com/about/license/>

Copyright © 2010 "Cowboy" Ben Alman

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

jQuery Wiggle

Author: WonderGroup, Jordan Thomas

License: MIT (http://en.wikipedia.org/wiki/MIT_License)

A common form of the MIT License (from the OSI's website, which is the same version as the "Expat License", and which is not identical to the license used in the X source code) is defined as follows:[8]

Copyright (c) <year> <copyright holders>

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

An intermediate form of license used by the X Consortium for X11 used the following wording:[9]

Copyright (C) <date> X Consortium

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE X CONSORTIUM BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Except as contained in this notice, the name of the X Consortium shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Software without prior written authorization from the X Consortium.

X Window System is a trademark of X Consortium, Inc. JSON Editor v0.7.22 - JSON Schema -> HTML Editor

By Jeremy Dorn - <https://github.com/jdorn/json-editor/>

Released under the MIT license

Date: 2015-08-12

The MIT License (MIT) Copyright (c) 2013 Jeremy Dorn

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

lodash 3.10.1 (Custom Build) lodash.com/license | Underscore.js 1.8.3 <http://underscorejs.org/LICENSE>

Build: `lodash compat -o ./lodash.js`

Copyright jQuery Foundation and other contributors <https://jquery.org/>

Based on Underscore.js, copyright Jeremy Ashkenas, DocumentCloud and Investigative

Reporters & Editors <http://underscorejs.org/>

This software consists of voluntary contributions made by many individuals. For exact contribution history, see the revision history available at <https://github.com/lodash/lodash>.

The following license applies to all parts of this software except as documented below: Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

CC0: <http://creativecommons.org/publicdomain/zero/1.0/>

Copyright and related rights for sample code are waived via CC0. Sample code is defined as all source code displayed within the prose of the documentation.

Files located in the node_modules and vendor directories are externally maintained libraries used by this software which have their own licenses; we recommend you read them, as their terms may differ from the terms above.

marked - a markdown parser

Copyright (c) 2011-2014, Christopher Jeffrey. (MIT Licensed)

<https://github.com/chjj/marked>

Copyright (c) 2011-2014, Christopher Jeffrey (<https://github.com/chjj/>) Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

swagger-ui.js

Copyright 2009-2012 Kris Kowal under the terms of the MIT license found at:

<http://github.com/kriskowal/q/raw/master/LICENSE>

Copyright 2009–2016 Kristopher Michael Kowal. All rights reserved.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

With parts by Tyler Close

Copyright 2007-2009 Tyler Close under the terms of the MIT X license found at:

<http://www.opensource.org/licenses/mit-license.html>

Forked at ref_send.js version: 2009-05-11

The MIT License (MIT)

Copyright (c) <year> <copyright holders>

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

With parts by Mark Miller

Copyright (C) 2011 Google Inc.

Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except in compliance with the License. You may obtain a copy of the License at <http://www.apache.org/licenses/LICENSE-2.0>.

Unless required by applicable law or agreed to in writing, software * distributed under the License is distributed on an "AS IS" BASIS, * WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.

See the License for the specific language governing permissions and limitations under the License.

G.1.26 Notice Concerning Usage of XMLPULL

The following file is covered under this license:

- xpp3-1.1.4c.jar

XMLPULL API IS FREE

All of the XMLPULL API source code, compiled code, and documentation contained in this distribution *except* for tests (see separate LICENSE_TESTS.txt) are in the Public Domain.

XMLPULL API comes with NO WARRANTY or guarantee of fitness for any purpose.

Initial authors: Stefan Haustein and Aleksander Slominski

2001-12-12

G.1.27 Notice Concerning Usage of XStream

The following file is covered under this license:

- xstream-1.4.15.jar

XStream is open source software, made available under BSD license.

Copyright (c) 2003-2006, Joe Walnes

Copyright (c) 2006-2009, 2011, XStream Committers

All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- Neither the name of XStream nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.