

Oracle® Analytics

Deploying Oracle Analytics Server on Oracle Cloud



5.9.0
F45232-03
February 2022

ORACLE®

Oracle Analytics Deploying Oracle Analytics Server on Oracle Cloud, 5.9.0

F45232-03

Copyright © 2021, 2022, Oracle and/or its affiliates.

Primary Authors: Rosie Harvey, Hemala Vivek

Contributing Authors: Christine Jacobs

Contributors: Oracle Analytics Server development, product management, and quality assurance teams

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software" or "commercial computer software documentation" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle, Java, and MySQL are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Inside are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Epyc, and the AMD logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

Contents

Preface

Audience	v
Documentation Accessibility	v
Conventions	v

1 About Oracle Analytics Server on Oracle Cloud

What Is Oracle Analytics Server on Oracle Cloud?	1-1
About Oracle Cloud Marketplace	1-1
Architecture on Oracle Cloud	1-2
Typical Workflow for Administrators	1-3
Where to Go for More Information	1-4

2 Deploy Oracle Analytics Server on Oracle Cloud

Before you Begin	2-1
Subscribe to Oracle Analytics Server on Oracle Cloud	2-1
Set Up Policies in Oracle Cloud Infrastructure	2-2
Set Up Users to Deploy Oracle Analytics Server on Oracle Cloud	2-2
Create Compartments	2-3
Set Up Network Resources	2-3
Set Up an Oracle Cloud Database	2-3
Plan Compute Shape and Boot Volume Size	2-4
Generate SSH Keys	2-5
Complete Predeployment Checklist	2-5
Deploy Oracle Analytics Server Using Oracle Cloud Marketplace	2-6
Complete Post Deployment Tasks	2-12
Test Connectivity to Oracle Analytics Server	2-12
Install Additional Libraries for Machine Learning in Oracle Analytics Server	2-13
Sign-in and Verify Oracle Analytics Server	2-13
Complete Cleanup Tasks	2-14
Set Up SSL in Oracle Analytics Server	2-14

3 Administer Oracle Analytics Server on Oracle Cloud

Delete Oracle Analytics Server Resources	3-1
Edit Your Oracle Analytics Server Deployment	3-1
View Usage Costs for Oracle Analytics Server on Oracle Cloud	3-2
Scale Oracle Analytics Server on Oracle Cloud	3-3
Restart Oracle Analytics Server After You Reboot the Compute Instance	3-4

A Frequently Asked Questions

B Troubleshooting

Preface

This document describes how to deploy and administer Oracle Analytics Server on Oracle Cloud using Oracle Cloud Marketplace.

Audience

This guide is intended for system administrators or application developers who are installing and configuring Oracle Analytics Server. It is assumed that readers are familiar with Oracle Cloud, Terraform, web technologies, and have a general understanding of Linux or UNIX platform.

Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

Access to Oracle Support

Oracle customers that have purchased support have access to electronic support through My Oracle Support. For information, visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

Conventions

The following text conventions are used in this document:

Convention	Meaning
boldface	Boldface type indicates graphical user interface elements associated with an action, or terms defined in text or the glossary.
<i>italic</i>	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.
<code>monospace</code>	Monospace type indicates commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter.

Videos and Images

Your company can use skins and styles to customize the look of the application, dashboards, reports, and other objects. It is possible that the videos and images included in the product documentation look different than the skins and styles your company uses.

Even if your skins and styles are different than those shown in the videos and images, the product behavior and techniques shown and demonstrated are the same.

1

About Oracle Analytics Server on Oracle Cloud

This guide explains how to deploy Oracle Analytics Server on Oracle Cloud Infrastructure using Oracle Cloud Marketplace.

- [What Is Oracle Analytics Server on Oracle Cloud?](#)
- [About Oracle Cloud Marketplace](#)
- [Architecture on Oracle Cloud](#)
- [Typical Workflow for Administrators](#)
- [Where to Go for More Information](#)

What Is Oracle Analytics Server on Oracle Cloud?

Oracle offers you the option to deploy Oracle Analytics Server on Oracle Cloud Infrastructure using Oracle Cloud Marketplace.

When deployed on Oracle Cloud, Oracle Analytics Server provides the same functionality, scalability, security, and support as the on-premise version. All sources and targets supported in the on-premise version are supported on Oracle Cloud. See Certification Information

About Oracle Cloud Marketplace

Oracle Cloud Marketplace offers a rich library of click-to-deploy Terraform stacks that provide a quick way to deploy applications and services on Oracle Cloud Infrastructure.

You can use Oracle Cloud Marketplace to quickly deploy Oracle Analytics Server on Oracle Cloud Infrastructure so your organization can benefit from a deployment on this scalable, secure, highly available, and high performance environment.

The installation for Oracle Analytics Server offered through Oracle Cloud Marketplace creates a simple topology, which represents a sample starting topology for this product.

Oracle Cloud Marketplace offers two applications for Oracle Analytics Server.

- Oracle Analytics Server - BYOL (Bring Your Own License)
- Oracle Analytics Server - UCM (Universal Credits)

See Consumption Modes in <https://www.oracle.com/cloud/marketplace/>.


Architecture on Oracle Cloud

Learn about the components and terminology related to Oracle Analytics Server deployments on Oracle Cloud Infrastructure.

Simple Oracle Analytics Server Topology

This topology represents a simple Oracle Analytics Server deployment on Oracle Cloud Infrastructure using Oracle Cloud Marketplace.

Oracle Cloud Marketplace enables you to install a compute instance with a custom Oracle Analytics Server image in a topology similar to the one shown here. The topology diagram indicates several prerequisite Oracle Cloud Infrastructure components shown in orange: virtual cloud network, subnet, cloud database.



Key Components and Terminology

- **Compute instance:** A compute host running in the cloud that allows you to utilize hosted physical hardware, ensuring a high level of security and performance. The compute shape is the resources you allocate to a compute instance.
- **Virtual cloud network and subnets:** A virtual cloud network (VCN) in Oracle Cloud Infrastructure covers a single, contiguous Classless Inter-Domain Routing (CIDR) block of your choice. A subnet is a subdivision of a VCN that consists of a contiguous range of IP addresses that don't overlap with other subnets in the VCN. A VCN includes one or more subnets, route tables, security lists, gateways, and Dynamic Host Configuration Protocol (DHCP) options. If you're new to Oracle Cloud, see [Networking](#) in Oracle Cloud Infrastructure documentation. You must set up a VCN and subnet for your Oracle Analytics Server compute instance. The Oracle Analytics Server deployment script assigns the compute instance to a VCN and subnet of your choice.

Subnets can be public or private. Any compute instances you assign to a private subnet can't be directly accessed from outside Oracle Cloud. To administer compute instances on a private subnet, you must create a separate public subnet and bastion compute instance.

- **Load balancer:** (Optional) Provides an extra layer of security, allowing the Oracle Analytics Server compute node to be isolated on a private subnet.
- **NAT gateways, subnets, and partitions:** (Optional) If you set up a NAT gateway, when using public and private subnets, the NAT gateway needs to be added to ingress rules in your load balancer security rules for partitions to work.
- **Bastion compute instance:** (Optional) Provides administrative access to an Oracle Analytics Server domain on a private subnet.
- **Oracle Cloud Database:** Oracle Analytics Server needs access to pluggable database (PDB) on an Oracle Cloud virtual machine DB system in which it can create and store various product schemas. The Oracle database version must be 12.1, 12.2, 18+, or 19+.
- **Marketplace:** Oracle Cloud Marketplace is an online store available from the Oracle Cloud Infrastructure console. You can use Oracle Cloud Marketplace to install a compute instance running Oracle Analytics Server software. When you select Oracle Analytics Server in Marketplace, it prompts you for some basic information, and directs you to Resource Manager to create Oracle Analytics Server resources on Oracle Cloud Infrastructure. See [Overview of Marketplace](#) in Oracle Cloud Infrastructure documentation.
- **Resource Manager:** You use Resource Manager to deploy Oracle Analytics Server resources on Oracle Cloud Infrastructure. See [Overview of Resource Manager](#) in Oracle Cloud Infrastructure documentation.
- **Stack:** A stack is a collection of related cloud resources created and deployed by Resource Manager.

Typical Workflow for Administrators

Use this workflow as a high-level guide to administrator tasks.

Task	Description	More Information
Complete prerequisites prior to deployment	Understand and perform the required prerequisites tasks before you deploy Oracle Analytics Server on Oracle Cloud.	Before you Begin
Deploy Oracle Analytics Server and its required stack	Use Oracle Cloud Marketplace to deploy Oracle Analytics Server on Oracle Cloud Infrastructure. Enter the required metadata, and select the options that you prefer in the setup wizards.	Deploy Oracle Analytics Server Using Oracle Cloud Marketplace
Perform post-deployment tasks	Complete the required post-deployment tasks, including security, access, and resource cleanup.	Complete Post Deployment Tasks
Set up users	Set up users and groups and assign them appropriate privileges.	Set Up Users to Deploy Oracle Analytics Server on Oracle Cloud
Monitor usage and costs	Monitor the costs of Oracle Analytics Server.	View Usage Costs for Oracle Analytics Server on Oracle Cloud
Scale an instance	Scale out or in by adjusting the number of compute instances.	Scale Oracle Analytics Server on Oracle Cloud

Where to Go for More Information

Find information on Oracle Analytics Server, Oracle Cloud, and Oracle Cloud Marketplace.

- Oracle Analytics Server Documentation
- [Oracle Cloud Documentation](#)
- [Oracle Cloud Infrastructure Documentation](#)
- [Oracle Cloud Marketplace Documentation](#)

2

Deploy Oracle Analytics Server on Oracle Cloud

Let's explore how to deploy Oracle Analytics Server on Oracle Cloud Infrastructure.

- [Before you Begin](#)
- [Deploy Oracle Analytics Server Using Oracle Cloud Marketplace](#)
- [Complete Post Deployment Tasks](#)

Before you Begin

Before you deploy Oracle Analytics Server on Oracle Cloud, you must complete various prerequisite tasks and Oracle recommends that you gather a list of the metadata that you'll need for the quick-deployment process. Oracle provides a checklist to help you plan your deployment.

- [Subscribe to Oracle Analytics Server on Oracle Cloud](#)
- [Set Up Policies in Oracle Cloud Infrastructure](#)
- [Set Up Users to Deploy Oracle Analytics Server on Oracle Cloud](#)
- [Create Compartments](#)
- [Set Up Network Resources](#)
- [Set Up an Oracle Cloud Database](#)
- [Plan Compute Shape and Boot Volume Size](#)
- [Generate SSH Keys](#)
- [Complete Predeployment Checklist](#)

Subscribe to Oracle Analytics Server on Oracle Cloud

You must have an active Oracle Cloud account (Pay As You Go or Annual Universal Credits) to deploy *Oracle Analytics Server - UCM* (Universal Credits) on Oracle Cloud Infrastructure and you're charged the UCM (Universal Credits) rate.


If you have an Oracle Middleware on-premise license for Oracle Analytics Server, you can use this license to deploy *Oracle Analytics Server - BYOL* (Bring Your Own License). You must also have an active Oracle Cloud account.

Set Up Policies in Oracle Cloud Infrastructure

In Oracle Cloud Infrastructure, you use policies to control access to resources in your tenancy.

Before deploying Oracle Analytics Server on a compartment in Oracle Cloud Infrastructure, your tenant administrator must set up policies that enable you (and other users) to access or create the following resources in specific compartments.

- Marketplace applications
- Compute instances
- Network VPNs and subnets
- Database for storing Oracle Analytics Server schemas
- Resource manager stacks and jobs

1. In Oracle Cloud Infrastructure Console, click  in the top left corner.
2. Click **Identity & Security**. Under **Identity**, select **Policies**
3. Select the root compartment, and then click **Create Policy**.

Set up policies that are appropriate for your organization. Here is a sample policy template, with each row being a policy statement.

```
allow group mygroup_name to read compartments in tenancy
allow group mygroup_name to manage instance-family in compartment
mycompartment_name
allow group mygroup_name to use virtual-network-family in compartment
mycompartment_name
allow group mygroup_name to manage orm-family in compartment
mycompartment_name
```

Set Up Users to Deploy Oracle Analytics Server on Oracle Cloud

When you activate your order for Oracle Cloud services, you get the Cloud Account Administrator role. This role gives you full administration privileges in Oracle Cloud Infrastructure so you can complete all aspects of Oracle Analytics Server setup and much more. There's no need to delegate this responsibility but, if you want to, you can give someone else privileges to deploy or manage Oracle Analytics Server compute instances.

In Oracle Cloud Infrastructure you use IAM security policies to grant permissions. First, you must add the user to a group, and then you create a security policy that grants the group permissions to deploy or manage Oracle Analytics Server on a specific compartment or the tenancy (any compartment in the tenancy). For example, you might create a policy statement that looks like one of these:

```
allow group MyOASAdminGroup to manage all-resources in tenancy

allow group MyOASAdminGroup to manage all-resources in compartment
MyOracleAnalyticsServer
```

To find out how to create security policy statements, see [Set Up Policies in Oracle Cloud Infrastructure](#).

Create Compartments

When you sign up for Oracle Cloud Infrastructure, Oracle creates your tenancy with a root compartment that holds all your cloud resources. You then create additional compartments within the tenancy (under the root compartment) and corresponding policies to control access to the resources in each compartment.

Before you deploy Oracle Analytics Server on Oracle Cloud, Oracle recommends that you set up the compartment where you want all the resources associated with Oracle Analytics Server to belong.

For example, you might want to set up separate compartments for your stacks, network, database, and Oracle Analytics Server resources. The choice is yours.

Compartment	Oracle Cloud Infrastructure Resources
root	-
<ul style="list-style-type: none">MyStacks	Marketplace stacks Terraform stacks
<ul style="list-style-type: none">MyNetwork	VCN, subnet, and other network resources
<ul style="list-style-type: none">MyOracle_Analytics_Server	Compute instance hosting Oracle Analytics Server
<ul style="list-style-type: none">MyOracle_Database	Oracle Database used by Oracle Analytics Server to host its product schemas

You create compartments in Oracle Cloud Infrastructure Identity and Access Management (IAM). See [Setting Up Your Tenancy](#) and [Managing Compartments](#).

Set Up Network Resources

You or your network administrator must set up a virtual cloud network (VCN) and a subnet for your Oracle Analytics Server compute instance before you start.

The subnet can be *public* or *private*. If you want to deploy Oracle Analytics Server on a private subnet you must set up a separate public subnet, with a bastion compute instance or load balancer to provide administrative access. See [Overview of Networking](#) in Oracle Cloud Infrastructure documentation.

Ensure that you (or whoever plans to deploy Oracle Analytics Server) has the required policies to access the VCN and subnet you plan to use.

See [Overview of VCNs and Subnets](#).

Set Up an Oracle Cloud Database

Oracle Analytics Server needs access to a database deployed on Oracle Cloud in which it can install various required database schemas. The database must be deployed in the same region as Oracle Analytics Server and accessible from the VCN where you plan to deploy Oracle Analytics Server. The Oracle database version must be 12.1, 12.2, 18+, or 19+.

When you deploy Oracle Analytics Server on Oracle Cloud using Oracle Cloud Marketplace, you're asked to provide the database connection string and database administrator credentials for the database you want to use. The database must be a pluggable database

(PDB) on an Oracle Cloud virtual machine DB system. See [Overview for Bare Metal and Virtual Machine DB Systems](#).

You must use the database connection string format: <hostname or IP address>:<port>:<PDB_name>.<DB_domain>

For example:

```
oasdb.sub12345678901.oasvcn.oraclevcn.com:1512:OASDB1213_pdb1.sub12345678901.oasvcn.oraclevcn.com
```

**Tip:**

To ensure Oracle Analytics Server deployment goes smoothly, test the database connection and database administrator credentials before you start.

Product Schemas

Oracle Analytics Server installs several schemas on the Oracle Cloud Database and uses them to store various product metadata.

- <YourSchemaPrefix>_BIPLATFORM - Oracle Analytics
- <YourSchemaPrefix>_IAU - Audit Service
- <YourSchemaPrefix>_IAU_APPEND- Audit Service Append
- <YourSchemaPrefix>_IAU_VIEWER- Audit Service Viewer
- <YourSchemaPrefix>_MDS - Metadata Services
- <YourSchemaPrefix>_OPSS - Oracle Platform Security Services
- <YourSchemaPrefix>_STB - Service Table
- <YourSchemaPrefix>_WLS - WebLogic services

Plan Compute Shape and Boot Volume Size

When you deploy Oracle Analytics Server on Oracle Cloud, you're offered a range of compute shapes to suit different scenarios. The larger the compute size (OCPUs and memory), the greater the processing power. You can also select the boot volume size. If you're not sure which sizes to use, contact your sales team to discuss sizing guidelines.

Compute Shape

Oracle Analytics Server can be Oracle Compute Unit (OCPU)-intensive depending on your application. To help you decide which compute size best suits your deployment, consider how many active users you expect to perform concurrent activities. Oracle Analytics Server supports a range of compute shapes, including:

- **VM.Standard.2.*:** The default shape is VM.Standard.2.1.
- **VM.Standard.E4.Flex** and **VM.Standard.E3.Flex:** With these flexible shapes, you can customize the number of OCPUs and the amount of memory.

The exact list of shapes available to you depends on your region. For a description of the difference between VM Standard shapes and a discussion on how to decide which to use, see [Standard Shapes](#).

Boot Volume Size

A boot volume contains the image used to boot the compute instance. Volume performance varies with volume size. The default boot volume for an Oracle Analytics Server compute instance is 400 GB, and this is the minimum size available. You can increase this value up to 32768 GB.

See [Overview of Boot Volume](#)

Generate SSH Keys

You must generate a SSH public key and corresponding private key to access the Oracle Analytics Server compute instance on Oracle Cloud using a Secure Shell (SSH) connection.

When you deploy Oracle Analytics Server using Oracle Cloud Marketplace, you're asked to provide the public key you plan to use. See [Creating a Key Pair on the Command Line](#).

Complete Predeployment Checklist

Use a checklist similar to this one to help plan your deployment and make sure you've completed all the prerequisite tasks. The checklist contains all the information you'll need for the quick-deployment process.

My Deployment Checklist


Information Required	Value
Oracle Cloud Infrastructure	
License Type (UCM or BYOL)
Tenancy
Region
Availability Domain
Network	
Subnet where the compute instance for Oracle Analytics Server is deployed	
Compartment
VPN
Subnet
Database	
Oracle Cloud database where schemas for Oracle Analytics Server are installed	
Connect String
Database Administrator Username
Database Administrator Password
Prefix for Oracle Analytics Server database schemas
Password to access Oracle Analytics Server database schemas
Compute Instance	
Details about the compute instance on which Oracle Analytics Server is deployed	

Information Required	Value
Compartment
Shape	Shape: OCPU: Memory:
Boot Volume
SSH Key Pair	Public Key: Path to Private Key:
Oracle Analytics Server Domain	
Administrator access details for the Oracle Analytics Server deployment	
Analytics Administrator Username
Analytics Administrator Password

Deploy Oracle Analytics Server Using Oracle Cloud Marketplace

If you subscribe to Oracle Cloud with Universal Credits or have an Oracle Fusion Middleware on-premise license for Oracle Analytics Server, you can deploy Oracle Analytics Server on Oracle Cloud using Oracle Cloud Marketplace. Two quick-deploy templates are available. Select the one that matches your subscription with Oracle: Universal Credits (UCM) or Bring Your Own License (BYOL).

1. Complete the prerequisites tasks and record all the information you need in the checklist provided. See [Before you Begin](#).
2. Sign into Oracle Cloud Infrastructure Console.

Ensure that you have all the required security policies to deploy Oracle Analytics Server, and access to the compartments containing the prerequisite network and database infrastructure.
3. In Oracle Cloud Infrastructure Console, click  in the top left corner.
4. Click **Marketplace**. Under Marketplace, click **All Applications**.
5. Search for Oracle Analytics Server.
6. Click **Oracle Analytics Server - UCM** or **Oracle Analytics Server - BYOL**.
7. On Oracle Analytics Server's Marketplace page, select the version of Oracle Analytics Server you want to deploy.
8. Select the compartment in which to deploy and run the stack. For example, MyStacks.

This is where you want to store Oracle Resource Manager (ORM) stack and jobs.
9. Review the Oracle standard terms and restrictions, and then select **I have reviewed and accept the Oracle Standard Terms and Restrictions**.
10. Click **Launch Stack**.

Marketplace » Oracle Analytics Server - BYOL

Oracle Analytics Server - BYOL

Fast Deployment of Oracle Analytics Server on Oracle Cloud Infrastructure

Oracle Analytics Server

Categories: Business Applications

Type: Stack

Version: **OAS 5.9.0.0.21091...**

Compartment: **oas-marketplace-compartment**

pp1-ocnativestack (root)/oas-marketplace-compartment

Software price per OCPU: **BYOL**
(Bring your own license)

There are additional fees for the infrastructure usage. ⓘ

☒ I have reviewed and accept the [Oracle standard Terms and Restrictions](#)

Launch Stack

Reminder: Patch the instance once installed.

Overview | Provider | More apps

App by Oracle

Oracle Analytics Server is a complete modern analytics platform that helps you make smarter predictions and better decisions. Embedded machine learning and artificial intelligence power intelligent enterprise reporting, ad hoc analysis, and self-service data visualization so no matter what your role – analyst, engineer, or executive – you can easily analyze data and uncover new insights.

Support

Contacts:
Support Hotline (1 (800) 223-1711)

Links:
[Oracle Support](#)

11. On the **Create Stack** page, enter details for your stack.
 - a. Enter a name for your Oracle Analytics Server stack. For example, `My-OAS-Marketplace-Stack`.
 - b. Add your own description or leave the default. For example, `Stack to install Oracle Analytics Server on my TEST compute instance.`
 - c. Add tags to organize and track resources within your tenancy.
 - d. Click **Next**.
12. In **Oracle Analytics Server Compute Instance**, set values for the compute instance on which Oracle Analytics Server will be deployed.
 - **Display Name** - Enter a name for the compute instance. For example, `MyTestOAS`.
 - **Target Compartment** - Select the compartment in which to deploy the Oracle Analytics Server compute instance that this stack generates. For example, `MyOracle_Analytics_Server`.
If you want Oracle Analytics Server to use resources located in a different compartment, ensure that you have the required policies to access them. For example, the VCN, subnet, and database you plan to use.
 - **Availability Domain** - Select the domain in which to create the compute instance. Required only if your tenancy has more than one availability domain.
 - **Shape** - Select a shape for the compute instance.
If you select a flexible shape, you can specify the number of **OCPU**s and the amount of **Memory** (GB) that you want for the compute instance.
OCPUs - Enter a value between 1 and 64. The default is 1 OCPU.
Memory - Enter a value between 1 and 1024 GB. The default is 15 GB.
 - **Boot Volume Size** - Select the size of the boot volume in GB. The minimum volume is 400 GB.

- **SSH Public Key** - Browse and select the public SSH key file or paste the value of the SSH key that you created to access the compute instance.
13. In **Network Configuration**, select the network on which you want to deploy the compute instance for Oracle Analytics Server.
- **Compartment** - Select the compartment containing the Virtual Cloud Network (VCN) you want to use. For example, `MyNetwork`.
 - **Virtual Cloud Network** - Select the Virtual Cloud Network (VCN) where you want to create the compute instance.
 - **Subnet** - Select a subnet for the compute instance.

 **Note:**

If you select a private subnet, you must set up a separate public subnet and a bastion compute instance (or load balancer) to provide administrative access to the compute instance. See [Set Up Network Resources](#).

- **Assign a Public IP Address** - Generates a public IP address for the compute instance. Only applicable if you select a public subnet. Don't select this option if the subnet is private.

If you can't see the compartment, VCN, or subnet you want, check you have the required permissions.

14. In **Oracle Analytics Server Domain Configuration**, select **Create Oracle Analytics Server Domain** and provide the details for Oracle Analytics Server domain configuration.

 **Note:**

Don't select **Create Oracle Analytics Server Domain**, if you're creating an additional Oracle Analytics Server compute instance to scale out an existing Oracle Analytics Server deployment.

- **Analytics Administrator Username** - Name of the user who will administer Oracle Analytics Server. Because this is a new user, you can enter any suitable username. For example, `myoasadmin`.
- **Analytics Administrator Password** - Password for the Oracle Analytics Server administrator. Because this is a new password, enter any suitable password. The password must be at least 8 characters long and contain only alphanumeric, underscore (`_`), dollar (`$`) or pound (`#`) characters.
- **Database Connection String** - Connect string for the database you want to use to store Oracle Analytics Server product schemas. The database must be a pluggable database (PDB) on an Oracle Cloud virtual machine DB system. Use the format: `<hostname or IP address>:<port>:<PDB_name>.<DB_domain>`
For example:
`oasdb.sub12345678901.oasvcn.oraclevcn.com:1512:OASDB1213_pdb1.sub12345678901.oasvcn.oraclevcn.com`

- **Database Administrator Username** - Name of an existing user with database administration privileges. For example, `myoasdba`.
- **Database Administrator Password** - Password of the user with database administration privileges.
- **Database Schema Prefix** - Prefix added to the name of each database schema created for Oracle Analytics Server. For example, `MyOAS`.
- **Database Schema Password** - Password to access the database schemas used by Oracle Analytics Server. This is a new password so you can enter any suitable value. The password must be at least 8 characters long and contain only alphanumeric, underscore (`_`), dollar (`$`) or pound (`#`) characters

 **Tip:**

To ensure Oracle Analytics Server deployment goes smoothly, test the database connection and database administrator credentials before you create the stack.

15. Click **Next**.
16. Review the information you provided for the compute instance.

Create Stack

1 Stack Information
2 Configure Variables
3 Review

Verify your configuration variables, and then create your stack. The apply job will automatically run to create resources specified in the configuration. Due to limited space, we show only variables without default values or that you edited.

Stack Information	
Name	My-OAS-Marketplace-Stack
Description	...tance Show Copy
Compartment	...ican4a Show Copy
Terraform version	0.12.x

Oracle Analytics Server Compute Instance	
Display Name	MyTestOAS
Target Compartment	...cygkpa Show Copy
Availability Domain	dmtQ.US-ASHBURN-AD-1
SSH Public Key	Comment: "rsa-key-20210928"

Network Configuration	
Virtual Cloud Network	...2irghq Show Copy
Subnet	...ibx5a Show Copy

Oracle Analytics Server Domain Configuration	
Create Oracle Analytics Server Domain	true
Analytics Administrator Username	oasadmin
Analytics Administrator Password	*****
Database Connection String	example.com
Database Administrator Username	dbadmin
Database Administrator Password	*****
Database Schema Prefix	OAS
Database Schema Password	*****

Run Apply on the created stack?

Immediately provision the resources defined in the Terraform configuration by running the Apply action on the new stack.

☒ Run Apply

Previous **Create** Cancel


17. Make sure that **Run Apply** is selected, and then click **Create**.

Monitor progress on the **Job Details** page. When the stack job finishes, the state changes from **In Progress** to **Succeeded**.

If you opted to create and configure a domain, the process takes about 30 - 40 minutes to complete and starts in the background immediately after the stack job finishes. The exact time depends on multiple factors, including the current load on your network and database.


18. To track the deployment process, use SSH to connect to the compute instance and monitor the deployment logs in the `/tmp` directory (`oas_install.log` and `create_domain.log`). When Oracle Analytics Server is ready to use, you see the file `/tmp/oas_install.finish`.
19. In the Job Details page, click **Job Resources** to access the compute instance (`oci_core_instance`) generated by the stack.

Click the name of the compute instance to navigate to more detail and bookmark this page because you might need this page later.



20. In the Job Details page, click **Outputs** to see the public IP address assigned to the compute instance (if any).

If available, copy the public IP address. You can use the public IP to sign-in and verify your Oracle Analytics Server deployment. See [Sign-in and Verify Oracle Analytics Server](#).



21. In the Job Details page, click **View State** to review the Terraform state file for this stack.

Resource Manager stores the Terraform state file (.tfstate) for the stack in JSON format. This file maps your stack's resources to your configuration and maintains essential configuration metadata, such as resource dependencies. See also [To view the state of a stack](#).

The Terraform state file contains all the data you provided, including the passwords you specified for the domain creation phase. If you don't want these passwords to be visible to anyone who has access to this job, you should skip the domain creation. Instead, you can add all the information required to create the domain to the files on the compute instance, and create the domain manually using the scripts provided.

Complete Post Deployment Tasks

After you deploy Oracle Analytics Server on Oracle Cloud Infrastructure using Oracle Marketplace, complete the following tasks.

- [Test Connectivity to Oracle Analytics Server](#)
- [Install Additional Libraries for Machine Learning in Oracle Analytics Server](#)
- [Sign-in and Verify Oracle Analytics Server](#)
- [Complete Cleanup Tasks](#)
- [Set Up SSL in Oracle Analytics Server](#)
- [Secure Your Network](#)

Test Connectivity to Oracle Analytics Server

Use Secure Shell (SSH) client software to connect to the Oracle Analytics Server compute instance deployed on Oracle Cloud Infrastructure to perform administrative tasks.

You need the public IP address of the compute instance to use SSH. See [Connecting to a Compute Instance on Oracle Cloud Infrastructure](#).



Note:

The way you access a private compute node depends on your environment. For example, you might decide to deploy a bastion host (see [Oracle Technical Brief](#) on post-deployment bastion host setup). If your network configuration uses FastConnection or VPN with IPSec, you must provide the network setup that allows you to use SSH to connect to the private compute node.

1. Open any SSL utility, for example openssl.
2. Connect to your Oracle Analytics Server compute instance and log in.

```
$ ssh -i path_to_private_key_file opc@oas_public_ip
```

path_to_private_key_file is the full path and name of the file that contains the private key associated with the instance you want to access. This is the private key from the public-private key pair that you generated and specified when you deployed Oracle Analytics Server using Oracle Cloud Marketplace.

opc is the default user for the compute instance *opc*.

oas_public_ip is the public IP address for the compute instance that you obtained from the Console.

Install Additional Libraries for Machine Learning in Oracle Analytics Server

If you want to use automated machine learning features in Oracle Analytics Server on Oracle Cloud you must install some additional libraries.

You must have system administrator privileges to install these libraries.

At the command line, run the following command to install the libraries:

```
(Linux) sudo yum install -y libgfortran
```

Sign-in and Verify Oracle Analytics Server

If you opted to create and configure a domain for Oracle Analytics Server, it takes another 30 - 40 minutes *after* the stack job finishes to create the domain and deploy Oracle Analytics Server. The exact time depends on multiple factors, including the current load on your network and database. After checking the logs, you can sign in.

1. If you haven't done so already, verify that Oracle Analytics Server installation is complete.

- a. Open any SSH utility and log in to the compute instance.


Use the SSH private key (*path_to_private_key*) and the public IP address of the Oracle Analytics Server (*oas_public_ip*).

```
$ ssh -i path_to_private_key opc@oas_public_ip
```

- b. Navigate to the `/tmp` directory and look for the file `oas_install.finish`. This file indicates that the installation is complete.
- c. Check the log files `oas_install.log` and `create_domain.log` to verify that the domain created successfully.

2. If you haven't done so already, obtain the public IP address of your Oracle Analytics Server compute instance.

Earlier, we showed you how to access the IP information from the Job Outputs tab in Resource Manager (see step 20 [Deploy Oracle Analytics Server Using Oracle Cloud Marketplace](#)). You can also access the public IP address from the Compute Instance Details page:

- a. In Oracle Cloud Infrastructure Console, click  in the top left corner.
 - b. Click **Compute** and then click **Instances**.
 - c. Under List Scope on the left side of the page, select the compartment where you deployed Oracle Analytics Server.
 - d. Select the name of the compute instance.
 - e. Under **Primary VNIC Information**, find and copy **Public IP Address**.
3. To verify Oracle Analytics Server, access the following URL and sign in.

```
http://OAS_Public_IP_Address:port/analytics
```

For example: `http://123.45.67.890:9502/analytics`

If you selected the **Create Oracle Analytics Server Domain** stack option, Oracle Analytics Server is set up with the default ports, and you can access Oracle Analytics Server on port 9502. If you configured the Oracle Analytics Server domain separately, use the port number you specified for the Managed Server.

Sign in using the administrator credentials you provided to deploy the stack, that is, the values for **Analytics Administrator Username** and **Analytics Administrator Password**.

When the home page displays, Oracle Analytics Server is ready to use!

4. To verify Oracle Analytics Publisher, access the following URL and sign in.

`http://OAS_IP_address:Port/xmlpserver`

For example: `http://123.45.67.890:9502/xmlpserver`

Oracle Analytics Publisher displays and is ready to use!

Complete Cleanup Tasks

After you deploy Oracle Analytics Server using Oracle Cloud Marketplace and verify your setup, Oracle recommends that you delete the domain configuration file `biconfig.rsp`. This configuration file contains sensitive password information and since it's no longer required, you're advised to delete it.

1. Use SSH to access the compute instance for Oracle Analytics Server.
2. Navigate to `/oas/oas_install`.
3. Delete the file `biconfig.rsp`.

Set Up SSL in Oracle Analytics Server

Oracle highly recommends that you configure Oracle Analytics Server components to communicate over SSL and update the SSL certificates to one that has been signed with a trusted certificate authority.

To do this, follow the same steps as in Oracle Analytics Server on-premise. See *Configure SSL in Oracle Analytics Server* in *Managing Security for Oracle Analytics Server*.

Secure Your Network

After you deploy the Oracle Analytics Server stack on Oracle Cloud Infrastructure, take steps to secure your network.

See [Ways to Secure Your Network](#).

3

Administer Oracle Analytics Server on Oracle Cloud


When you deploy Oracle Analytics Server on Oracle Cloud Infrastructure, some administration tasks take place through Oracle Cloud Infrastructure Console.

- [Delete Oracle Analytics Server Resources](#)
- [Edit Your Oracle Analytics Server Deployment](#)
- [View Usage Costs for Oracle Analytics Server on Oracle Cloud](#)
- [Scale Oracle Analytics Server on Oracle Cloud](#)
- [Restart Oracle Analytics Server After You Reboot the Compute Instance](#)

Delete Oracle Analytics Server Resources


Destroying a stack deletes all the Oracle Analytics Server resources that were created by the stack, including the Oracle Analytics Server compute node.

Billing stops immediately after the destroy operation.

1. In Oracle Cloud Infrastructure Console, click  in the top left corner, select **Resource Manager**, and then click **Stacks**.
2. Click the Oracle Analytics Server stack you want to delete.
3. Click **Destroy**.
You can monitor the progress of the Destroy job in the Logs tab. When complete, the State changes to **Succeeded**.
4. Click **Stack Details** and then click **More Actions**. Select **Delete Stack**, and then click **Delete**.
5. Optional: Delete the database schemas created for Oracle Analytics Server.

Edit Your Oracle Analytics Server Deployment

You can edit only the name of the Oracle Analytics Server compute instance.

1. In Oracle Cloud Infrastructure Console, click  in the top left corner.
2. Click **Compute**, and then click **Instances**.
3. Under List Scope on the left side of the page, select the compartment containing the compute instance you want to edit.
4. Select the compute instance and click **Edit**.
5. In the Edit instance configuration dialog, enter a new name, and then click **Save changes**.

View Usage Costs for Oracle Analytics Server on Oracle Cloud

You can analyze the cost of your Oracle Analytics Server deployment using the Cost Analysis page. Cost information for Oracle Analytics Server is available under the Compute service.

- **Product Description:** Oracle Analytics Server on OCI - UCM
- **Part Number:** B94568

1. Ensure you're assigned to a security policy that allows you to read cost information.


For example, if you have an Oracle Cloud user group called AnalyticsServerAdmins, you might want to allow this group to see cost information. For example, a policy statement that looks like this:

```
allow group AnalyticsServerAdmins to read usage-reports
```

2. Navigate to the Cost Analysis Page. Click **Billing and Cost Management**, and then click **Cost Analysis**.
3. In Reports, select **Costs by Service**.
 - a. Add a filter for **Service** and select **COMPUTE**.
 - b. For Grouping Dimensions, select **SKU Product Descriptions**.
 - c. Review costs for **Oracle Analytics Server on OCI - UCM**.



4. In Reports, select **Costs by Service**.
 - a. Add a filter for **Service** and select **COMPUTE**.
 - b. For Grouping Dimensions, select **SKU (Part Number)**.
 - c. Review costs for **B94568 (Oracle Analytics Server on OCI - UCM)**.



Scale Oracle Analytics Server on Oracle Cloud

If you want to scale Oracle Analytics Server by distributing the processing of requests across multiple virtual machine (VM) instances, add another Oracle Analytics Server instance to your environment on Oracle Cloud.

Pre-requisites for scaling Oracle Analytics Server:


- Verify that your environment meets system and network requirements. See [Networking Overview](#) and [Virtual Networking Quickstart](#).
- Deploy additional Oracle Analytics Server instance on the same virtual cloud network (VCN) as the primary Oracle Analytics Server instance.

You can use the performance metrics that are provided in Oracle Fusion Middleware Control to monitor process state and to determine when you must increase capacity to improve performance of Oracle Analytics Server on Oracle Cloud.

If you want to use a private subnet, see [Configure Public and Private Subnets with a VPN](#).


1. Use Oracle Cloud Marketplace to deploy Oracle Analytics Server on Oracle Cloud Infrastructure (node 1).

For node 1, you must select **Create Oracle Analytics Server Domain**, and provide the required domain configuration details. See [Deploy Oracle Analytics Server Using Oracle Cloud Marketplace](#).



2. Use Oracle Cloud Marketplace to deploy a secondary Oracle Analytics Server on Oracle Cloud Infrastructure without a domain (node 2).

For node 2, don't select **Create Oracle Analytics Server Domain**.



3. Set up shared files and directories between the two nodes.

The singleton data directory (SDD) stores the metadata. The default location is set to:

`DOMAIN_HOME/bidata`

The SDD path is defined in the file `bi-environment.xml`, located at

`DOMAIN_HOME/config/fmwconfig/bienv/core/bi-environment.xml`.

- a. Open any SSH utility and run the following command to log in to your primary Oracle Analytics Server instance (node 1). Use the SSH private key (`path_to_private_key`) and the public IP address of the Oracle Analytics Server (`oas_public_ip`).

```
$ ssh -i path_to_private_key opc@oas_public_ip
```

- b. Create a mount point for `bidata`. For example, run the following command:

```
mount DOMAIN_HOME/bidata /sdd/bidata
```

This makes `/sdd/bidata` the mount point for SDD.

- c. Open the `bi-environment.xml` file for editing, specify the singleton path, and save the file.

For example:

```
<bi:singleton-data-directory>Node1_IP_address:/sdd/bidata/</bi:singleton-data-directory>
```

Where:


- `bi:singleton-data-directory` is the SDD mount point.
 - `Node1_IP_address` is the private IP address of node 1.
- d. Log in to node 2 using the SSH utility and ping node 1 to check you can access node 1.

You can use the `OASFirewallPortsFix.xml` script file to configure the ports.

4. Set up the global cache. See [Set Up the Global Cache](#).
5. Add (or remove) instances on Oracle Cloud Infrastructure.
 - To add a new instance, see [Add New Computers](#).
 - To remove an existing instance, see [Remove Existing Computers](#).
6. Validate that your system scales correctly. See [Validate that Your System Has Been Scaled Correctly](#).

Restart Oracle Analytics Server After You Reboot the Compute Instance

If you reboot the compute instance on which you deployed Oracle Analytics Server, you must restart Oracle Analytics Server. For example, you might need to reboot your Oracle Analytics Server compute instance after you make changes, such as applying a patch.

1. In Oracle Cloud Infrastructure Console, click  in the top left corner.
2. Click **Compute** and then click **Instances**.

3. Under List Scope on the left side of the page, select the compartment where you deployed Oracle Analytics Server and then select the compute instance you want to reboot.
4. Click **Reboot** to stop and restart the Oracle Analytics Server compute instance.
5. Manually start Oracle Analytics Server services using `start.sh`. See [Start Oracle Analytics Server](#).

The `start.sh` script file is available in the `/oas/oas_install/Oracle/Middleware/Oracle_Home/user_projects/domains/bi/bitools/bin/` folder.

A

Frequently Asked Questions

This section contains the following topics:

- [How do I know when the deployment and domain creation is complete?](#)
- [Where can I find the logs for the installation and check on progress?](#)
- [How can I verify that Oracle Analytics Server is up and running?](#)
- [Where can I find the public IP address of my Oracle Analytics Server compute instance?](#)
- [I rebooted my Oracle Analytics Server compute instance. Why can't I access Oracle Analytics Server?](#)
- [The status of my stack job changed to "Finished". Why can't I access my Oracle Analytics Server compute instance?](#)
- [Can I customize Oracle Analytics Server deployment on Oracle Cloud using Terraform?](#)

How do I know when the deployment and domain creation is complete?

To check whether deployment and domain creation is complete, use SSH to connect to the Oracle Analytics Server compute instance and look in the `/tmp` directory for the file `oas_install.finish`. If you find this file, the installation is complete.

```
>cd /tmp/
>ls -la
>...
>-rw-r--r--. 1 root root 0 Nov 05 15:02 oas_install.finish
>...
```

If you selected the option to create and configure a domain, the entire process takes about 30 - 40 minutes to complete.

Where can I find the logs for the installation and check on progress?

The Oracle Analytics Server stack creation process generates a log called `oas_install.log`. If you opt to create an Oracle Analytics Server domain, you see an additional log called `create_domain.log`. You can find both these logs in the `/tmp` directory of your Oracle Analytics Server compute instance.

- `oas_install.log`: Logs progress information during the entire installation process. For example, you see messages about script generation, script execution, the file `biconfig` used for domain creation, the configuration file `OASFirewallPortsFix.xml` and script file `open_oas_firewall_ports.sh` used to open ports in the firewall, and details about any files removed during the cleanup phase.

- `create_domain.log`: Logs status information during the domain creation phase. If domain creation succeeds, you see the following message:

```
[CONFIG] SUCCESS:Collect logs  
Configuration:Oracle_Analytics_Configuration completed successfully  
The configuration of Oracle Distribution completed successfully.
```

If a problem occurs, you see an error message with a description of the issue.

How can I verify that Oracle Analytics Server is up and running?

Obtain the public IP address of your Oracle Analytics Server compute instance and enter a URL such as this in your web browser:

```
http://OAS_IP_Address:port/analytics
```

For example:

```
http://123.45.67.890:9502/analytics
```

If you selected the **Create Oracle Analytics Server Domain** stack option, Oracle Analytics Server is set up with the default ports, and you can access Oracle Analytics Server on port 9502. If you configured the Oracle Analytics Server domain separately, use the port number you specified for the Managed Server.

See also Next Steps After Configuring the Domain in *Installing and Configuring Oracle Analytics Server*.

Where can I find the public IP address of my Oracle Analytics Server compute instance?

You can find the public IP address (if available) in several places:

- **Stack Job Log tab**: The public IP address displays in the **Outputs** section at the end of the log.

Resource Manager » Stacks » Stack Details » Job Details

ormjob20211026035404

RMJ
SUCCEEDED

Edit Job Download Terraform Configuration Download Terraform State Add Tags

Job Information Tags Application Information

To connect to the application running on this stack, see the Usage Instructions. [View Usage Instructions](#)

OCID: ...mbyp3a [Show](#) [Copy](#) Compartment: pp1-unnativeappout (root)/oas-marketplace-compartment
 Job Type: Apply Plan Job ID: Automatically approved
 State: ● Succeeded Working Directory: Not specified
 Start Time: Tue, Oct 26, 2021, 03:54:04 UTC End Time: Tue, Oct 26, 2021, 03:55:15 UTC

Resources

Logs
Variables
Job Resources
Outputs
View State

Download Logs Show Timestamps

```
module.computeinstance.data.template_file.biconfig_template: Refreshing state...
module.computeinstance.data.template_file.installer_script_template: Refreshing state...
module.computeinstance.data.template_file.createdomain_script_template: Refreshing state...
module.computeinstance.data.template_file.firewall_ports_config_template: Refreshing state...
module.computeinstance.data.template_file.firewall_ports_script_template: Refreshing state...
module.computeinstance.data.template_file.cloud_init_file: Refreshing state...
module.computeinstance.data.template_file.cloudinit_config_biconfig: Refreshing state...
module.computeinstance.ocf_core_instance.OAS_MP_instance: Creating...
module.computeinstance.ocf_core_instance.OAS_MP_instance: Still creating... [10s elapsed]
module.computeinstance.ocf_core_instance.OAS_MP_instance: Still creating... [20s elapsed]
module.computeinstance.ocf_core_instance.OAS_MP_instance: Still creating... [30s elapsed]
module.computeinstance.ocf_core_instance.OAS_MP_instance: Still creating... [40s elapsed]
module.computeinstance.ocf_core_instance.OAS_MP_instance: Still creating... [47s elapsed]
module.computeinstance.ocf_core_instance.OAS_MP_instance: Creation complete after 47s [id=ocid1.instance.ocf1.id.anuwc1jse4k0quq3]

Apply complete! Resources: 3 added, 0 changed, 0 destroyed.

Outputs:
instance_private_ip = 10.0.0.7
instance_public_ip = 150.136.222.237
```

- **Stack Job Outputs tab:** The public IP address displays in the **Outputs** section for the job.

Resource Manager » Stacks » Stack Details » Job Details

ormjob20211026035404

RMJ
SUCCEEDED

Edit Job Download Terraform Configuration Download Terraform State Add Tags

Job Information Tags Application Information

To connect to the application running on this stack, see the Usage Instructions. [View Usage Instructions](#)

OCID: ...mbyp3a [Show](#) [Copy](#) Compartment: pp1-unnativeappout (root)/oas-marketplace-compartment
 Job Type: Apply Plan Job ID: Automatically approved
 State: ● Succeeded Working Directory: Not specified
 Start Time: Tue, Oct 26, 2021, 03:54:04 UTC End Time: Tue, Oct 26, 2021, 03:55:15 UTC

Resources

Logs
Variables
Job Resources
Outputs
View State

Outputs

Key	Value
instance_private_ip	10.0.0.7
instance_public_ip	150.136.222.237

Showing 2 Outputs < 1 of 1 >

- **Compute Instance Details page:** Navigate to the compartment where you deployed the Oracle Analytics Server and locate the compute instance. The public IP address displays in the **Instance Access** section for the compute instance.


```
oas_install/biconfig.rsp -invPtrLoc /oas/oas_install/oraInst.loc 2>&1  
> /tmp/create_domain.log
```

Can I customize Oracle Analytics Server deployment on Oracle Cloud using Terraform?

Yes. Oracle provides two customizable Terraform modules that enable you to quickly deploy Oracle Analytics Server on Oracle Cloud Infrastructure using Resource Manager or Terraform commands: *Oracle Analytics Server - UCM (Universal Credits)* and *Oracle Analytics Server - BYOL (Bring Your Own License)*

Both Terraform modules are available for download from GitHub. To find out more, go to GitHub and search or jump to:

```
oracle-quickstart/oci-oracle-analytics-server
```

For instructions, see [Oracle Analytics Server Quick Start Readme](#).

For general information about Resource Manager and Terraform in Oracle Cloud Infrastructure, see [Overview of Resource Manager](#) and [Resource Manager and Terraform](#).

B

Troubleshooting

This topic describes common problems that you might encounter deploying Oracle Analytics Server on Oracle Cloud and explains how to solve them.

- [I'm having problems creating the stack for Oracle Analytics Server](#)
- [How do I diagnose other installation issues?](#)
- [How can I confirm a problem with the connection to the database?](#)
- [Why do I see an error message about a *failed authorization* or a *resource not found* when I try to create an Oracle Analytics Server stack?](#)
- [Why do I see the error message *404-NotAuthorizedOrNotFound* while creating an Oracle Analytics Server stack?](#)
- [Why do I see an error message about public IP addresses and a subnet?](#)
- [Why do I see a maximum stack limit error message?](#)
- [What can I do when domain creation fails due to an incorrect or invalid password?](#)
- [The installation finished but I can't access Oracle Analytics Server by entering the URL in a browser. What do I need to do?](#)
- [Why can't I use automated machine learning features in Oracle Analytics Server?](#)
- [How do I get help for Marketplace?](#)
- [When do I contact Oracle Support?](#)

I'm having problems creating the stack for Oracle Analytics Server

In the Oracle Cloud Infrastructure Console, navigate to the Logs page for the stack job.

Resource Manager > Stacks > Stack Details > Job Details

ormjob20211108065607

RMJ

SUCCEEDED

Job Information | Tags | Application Information

To connect to the application running on this stack, see the Usage Instructions. [View Usage Instructions](#)

OCID: ...7xiwq [Show](#) [Copy](#) | Compartment: pp1-oac (root)/oas-marketplace-compartment

Job Type: Apply | Plan Job ID: Automatically approved

State: ● Succeeded | Working Directory: Not specified

Start Time: Mon, Nov 8, 2021, 06:56:07 UTC | End Time: Mon, Nov 8, 2021, 06:57:07 UTC

Resources

Logs

[Download Logs](#) [Show Timestamps](#)

```

Initializing modules...
- computeinstance in computeinstance
Initializing provider plugins...

The following providers do not have any version constraints in configuration,
so the latest version was installed.

To prevent automatic upgrades to new major versions that may contain breaking
changes, it is recommended to add version = "..." constraints to the
corresponding provider blocks in configuration, with the constraints strings
suggested below.

"provider.ocid: version = ">= 4.51"
"provider.template: version = ">= 2.1"
  
```

If you're not sure what to do, contact Oracle Support for assistance.

How do I diagnose other installation issues?

When you deploy Oracle Analytics Server on Oracle Cloud several logs are saved to the `tmp` directory on the compute instance created for Oracle Analytics Server:

You can use your favorite SSH client to log in to the Oracle Analytics Server compute instance to access these logs.

- `/tmp/oas_install.finish` - Indicates that the installation is complete.
- `/tmp/oas_install.log` - Logs progress information during the entire installation process. For example, you see messages about script generation, script execution, the file `biconfig` used for domain creation, the configuration file `OASFirewallPortsFix.xml` and script file `open_oas_fiewall_ports.sh` used to open ports in the firewall, and details about any files removed during the cleanup phase.
- `/tmp/create_domain.log` - Logs status information during the domain creation phase. If domain creation succeeds, you see the following message:

```

[CONFIG] SUCCESS:Collect logs
Configuration:Oracle_Analytics_Configuration completed successfully
The configuration of Oracle Distribution completed successfully.
  
```

If a problem occurs, you see an error message with a description of the issue.

How can I confirm a problem with the connection to the database?

Database connection errors can occur for various reasons including an incorrect connection string, an incorrect user name or password, and an invalid or duplicate prefix for the product schemas.

Incorrect connection string

Use SSH to access the compute instance for Oracle Analytics Server and open the `/tmp/create_domain.log` file. An error message similar to the one shown in the following example indicates that either the database isn't accessible or the connection string for the database is incorrect.

```

Validations are enabled for this session.
Verifying data
[VALIDATION] [ERROR]:Error connecting to 'Oracle database at host <IP
address> port 1521 service name
      pdb.sub07132220290.sgvcn.oraclevcn.com'. Error: 'Listener refused
the connection with the following error:
ORA-12514, TNS:listener does not currently know of service requested in
connect descriptor '
- Invalid service name.
[VALIDATION] [SUGGESTION]:Make sure the database is up and running and
connect string, user name and password are correct.
Configuration Failed. Exiting configuration due to data validation failure.
```

Incorrect user name or password

Use SSH to access the compute instance for Oracle Analytics Server and open the `/tmp/create_domain.log` file. An error message similar to the one shown in the following example indicates that credentials provided for connecting to the database are invalid.

```

Validations are enabled for this session.
Verifying data[VALIDATION]
[ERROR]:Error connecting to 'Oracle database at host <IP address> port 1521
service name <PDB_Name>.<DB domain>'
- Invalid user name/password
[VALIDATION] [SUGGESTION]:Make sure the database is up and running and
connect string, user name and password are correct. Enter a valid user name
with DBA privileges
Configuration Failed. Exiting configuration due to data validation failure.
```

If the username or password contains illegal characters, you see an error message similar to this:

```

Validations are enabled for this session.
Verifying data [VALIDATION]
[ERROR]:Password contains invalid characters
[VALIDATION] [SUGGESTION]:Ensure password contains only alphanumeric,
underscore (_), dollar ($) or pound (#) characters configuration Failed.
Exiting configuration due to data validation failure.
```

If the password is the incorrect length, you an error message similar to this:

```
Validations are enabled for this session.
Verifying data [VALIDATION]
[ERROR]:Password field 'ADMIN_PASSWORD' must have at least '1'
numerals
[VALIDATION][SUGGESTION]:Enter a more complex password with numerals
[VALIDATION] [ERROR]:Password field 'ADMIN_PASSWORD' must be at least
'8' characters long
[VALIDATION] [SUGGESTION]:Enter a longer password
```

Invalid or duplicate prefix for the product schemas

Use SSH to access the compute instance for Oracle Analytics Server and open the `/tmp/create_domain.log` file. An error message similar to the one shown in the following example indicates that an invalid or duplicate prefix was provided for Oracle Analytics Server product schemas.

```
Validations are enabled for this session.
ACTION - RCU-6016 Specify another prefix.
ERROR - RCU-6016 Invalid prefix specified.
CAUSE - RCU-6016 The specified prefix already exists.[Create schemas
using RCU]:2021-11-03T10:52:07.479+0000
ERROR - RCU-6091 Component validation failed.
CAUSE - RCU-6091 One or more component specific validation failed.
```

Why do I see an error message about a *failed authorization* or a *resource not found* when I try to create an Oracle Analytics Server stack?

If you don't have the `manage orm-family` policy, you see the following error message when you attempt to create an Oracle Analytics Server stack:

```
Authorization failed or requested resource not found
```

Ask your administrator to assign you to a group with the following policy:

```
allow group myoasgroup_name to manage orm-family in compartment myoas-
compartment_name
```

See [Set Up Policies in Oracle Cloud Infrastructure](#).

Why do I see the error message *404-NotAuthorizedOrNotFound* while creating an Oracle Analytics Server stack?

If you don't have the `manage instance-family` policy, you see the following error message when creating an Oracle Analytics Server stack:

```
Error: 404-NotAuthorizedOrNotFound...
Service: Core Instance
Error Message: Authorization failed or requested resource not found.
```

Ask your administrator to assign you to a group with the following policy:

```
allow group myoasgroup_name to manage instance-family in compartment myoas-
compartment_name
```

See [Set Up Policies in Oracle Cloud Infrastructure](#).

Why do I see an error message about public IP addresses and a subnet?

You can't assign a public IP address (ephemeral public IPs) to an Oracle Analytics Server compute instance that is deployed in a *private subnet*. If you decide to use a private subnet, don't select the stack option **Assign a Public IP Address**. If you do, you see the following error message:

```
Public IP addresses are prohibited in this subnet {ocidl.subnet...
```

Why do I see a maximum stack limit error message?

When you sign up for Oracle Cloud Infrastructure, a set of service limits is configured for your tenancy. If you reach the maximum number of stacks allowed in your tenancy you see the following error message when try to create an Oracle Analytics Server stack:

```
Tenancy has reached maximum limit for total stacks.
```

See [Requesting a Service Limit Increase](#).

What can I do when domain creation fails due to an incorrect or invalid password?

1. Use SSH to access the compute instance for Oracle Analytics Server.
2. Navigate to `/oas/oas_install`.
3. Modify `biconfig.rsp` and correct the incorrect password.
4. Delete the existing `/tmp/create_domain.log` file (`sudo rm /tmp/create_domain.log`).
5. Navigate to the `/tmp` folder
6. Do one of the following:
 - Execute the existing create domain script to create the domain: `/create_oas_domain.sh`
 - Run `config.sh`: `sudo -u opc bash /oas/oas_install/Oracle/Middleware/Oracle_Home/bi/bin/config.sh -silent -responseFile /oas/oas_install/biconfig.rsp -invPtrLoc /oas/oas_install/oraInst.loc 2>&1 > /tmp/create_domain.log`

The installation finished but I can't access Oracle Analytics Server by entering the URL in a browser. What do I need to do?

Use SSH to access the compute instance for Oracle Analytics Server, navigate to the directory `/oas/oas_install/Oracle/Middleware/Oracle_Home/user_projects/domains/bi/bitools/bin`, and then run `status.sh` to check whether all the required services are running.

The following information is displayed:

```
Domain status; Using domainHome:/oas/oas_install/Oracle/Middleware/
Oracle_Home/user_projects/domains/bi ...
Initializing WebLogic Scripting Tool (WLST) ...
Welcome to WebLogic Server Administration Scripting Shell
Type help() for help on available commands

/Servers/AdminServer/ListenPort=9500
Accessing admin server using URL t3:/<compute instance name>:9500

AdminServer already running
Status of Domain: /oas/oas_install/Oracle/Middleware/Oracle_Home/
user_projects/domains/bi
NodeManager (<compute instance name>:9506:SSL): RUNNING
```

Name	Type	Machine	Restart	Int	Max
Restart	Status				
-----	-----	-----	-----		
AdminServer	Server	<compute instance name>	unknown		
unknown	RUNNING				
bi_server1	Server	<compute instance name>	unknown		
unknown	RUNNING				
obips1	OBIPS	<compute instance name>	3600		
5000	RUNNING				
obijs1	BIJS	<compute instance name>	3600		
5000	RUNNING				
obiccs1	OBICCS	<compute instance name>	3600		
5000	RUNNING				
obiscl1	OBISCH	<compute instance name>	3600		
5000	RUNNING				
obisl1	BIS	<compute instance name>	3600		
5000	RUNNING				

If any of the services are down, restart Oracle Analytics Server manually using `start.sh`. See [Start Oracle Analytics Server](#).

Why can't I use automated machine learning features in Oracle Analytics Server?

You need to install some additional libraries. See [Install Additional Libraries for Machine Learning in Oracle Analytics Server](#).

How do I get help for Marketplace?

For general help with Oracle Cloud Marketplace, see [How Do I Get Support in Using Oracle Cloud Marketplace](#).

When do I contact Oracle Support?

If you encounter a problem deploying Oracle Analytics Server on Oracle Cloud, record any error messages you see in the user interface, and contact Oracle Support for assistance.