Oracle® Communications IDIH Alarm Forwarding



Release 8.2.3 F35864-01 October 2020

ORACLE

Oracle Communications IDIH Alarm Forwarding, Release 8.2.3

F35864-01

Copyright © 2014, 2020, Oracle and/or its affiliates.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software" or "commercial computer software documentation" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Inside are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Epyc, and the AMD logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

Contents

1 Introduction

1-1
1-1
1-1
1-1
1-2

2 Introduction to Alarm Forwarding

Overview	2-1
Setting User Preferences on IDIH Dashboard	2-1
Setting Time Format	2-1
Setting Mapping Preferences	2-2
Alarm Forwarding Key Features	2-2
Alarm Forwarding Architecture	2-3

3 Working in Alarm Forwarding

Accessing Alarm Forwarding	3-1
Alarm Forwarding Toolbar	3-1
Alarm Status Indicator	3-1
Using Alarm Forwarding	3-3
Creating a Filter	3-3
Editing a Filter	3-4
Alarm Forwarding Test Connection	3-5
Test Connection for SMTP	3-5
Test Connection for SNMP	3-6

4 SNMP Agent

SNMP Overview	4-1
Alarm Forwarding MIB	4-1



List of Figures

3-1	Alarm Forwarding Toolbar	3-1
3-2	Alarm Status Indicator	3-2
3-3	Alarm List	3-3
3-4	Filter Creation Dialog	3-4
3-5	Connection Test Dialog	3-5



List of Tables

3-1 Alarm Forwarding Toolbar Icons

1 Introduction

This section contains an overview of the available information for the Integrated Diameter Intelligence Hub.

The contents include sections on the organization, scope, and audience of the documentation, as well how to receive customer support assistance.

Revision History

Date	Description
August 2011	Initial Release
June 2016	Updated to include accessibility changes

Overview

This documentation provides information about the functions of the Alarm Forwarding application of the Integrated Diameter Intelligence Hub (IDIH).

Note:

The Alarm Forwarding application is only available to users logging into IDIH as **idihadmin**.

Scope and Audience

This user's guide provides information about the Alarm Forwarding application. This guide provides definitions and instructions to help the user efficiently and effectively define conditions and destinations for forwarding Alarms.

Manual Organization

Introduction contains general information about this document.

Introduction to Alarm Forwarding provides an introduction to the Alarm Forwarding application.

Working in Alarm Forwarding contains information about procedures used while using the Alarm Forwarding application.

SNMP Agent contains information about the SNMP Agent of the Alarm Forwarding application.



My Oracle Support

My Oracle Support (https://support.oracle.com) is your initial point of contact for all product support and training needs. A representative at Customer Access Support can assist you with My Oracle Support registration.

Call the Customer Access Support main number at 1-800-223-1711 (toll-free in the US), or call the Oracle Support hotline for your local country from the list at http://www.oracle.com/us/support/contact/index.html. When calling, make the selections in the sequence shown below on the Support telephone menu:

- 1. Select 2 for New Service Request.
- 2. Select **3** for Hardware, Networking and Solaris Operating System Support.
- 3. Select one of the following options:
 - For Technical issues such as creating a new Service Request (SR), select 1.
 - For Non-technical issues such as registration or assistance with My Oracle Support, select **2**.

You are connected to a live agent who can assist you with My Oracle Support registration and opening a support ticket.

My Oracle Support is available 24 hours a day, 7 days a week, 365 days a year.



2 Introduction to Alarm Forwarding

This chapter provides basic information about the Alarm Forwarding application.

Overview

Alarm Forwarding enables the user to forward alarms to specified destinations. The user can create alarm forwarding rules using Filters.

This application handles several types of alarms, including those pertaining to

- Traffic supervision
- Quality of service
- System errors

Setting User Preferences on IDIH Dashboard

Once inside IDIH, a user can set user preferences. These include:

- Time specifications (such as date format, time zone)
- Enumeration values (numerals vs. text)

Setting Time Format

Follow these steps to set the time format:

1. Click User Preferences on the Application board.

The User Preferences screen is displayed.

2. Click the Date/Time tab.

The Date/Time screen is displayed. The red asterisk denotes a required field.

Note:

Use the tips on the screen to help configure the time format.

- 3. Enter the format for these time-related displays.
 - Date format
 - Time format
 - Date and time fields
- 4. Select the formats for these time-related displays by using the drop-down arrow.
 - **Duration fields** how the hours, minutes, seconds, and milliseconds of the Time format is displayed



Time zone

Note:

The local time zone must be chosen to get local time.

- 5. To reset the time-related displays to default settings, click **Reset**.
- 6. Click Apply to save settings.

Setting Mapping Preferences

The user can set the Mapping settings using the User Preferences feature.

Follow these steps to set Mapping preferences.

1. Click **User Preferences** in the Application board.

The User Preferences screen is displayed.

2. Click the Mapping tab.

The Mapping screen is displayed.

3. Check Translate ENUM values to display text instead of numerals.

Enumeration is used by TDRs to display text values instead of numeric. Rather than showing the numeral for Alarm Severity, the user interface will show the actual word, such as Major or Critical.

- 4. Check IP Address to Node Name to translate an IP Address to a textual Node Name.
- 5. To reset the Mapping values to the default, click **Reset**.
- 6. Click **Apply** to save the changes.

Alarm Forwarding Key Features

The key features of Alarm Forwarding include

- A Simple Network Management Protocol (**SNMP**) agent compliant with **ITU** x721, X733.
- Acknowledge/Terminate capability from SNMP.
- For an alarm event, only one email is sent to a selective list of email addresses. Alarm Forwarding allows a list of email addresses to be attached to a filter. It is possible to send a particular type of alarm to a list of email addresses and another type of alarm to a different list of email addresses. These multiple email address are set when creating a filter and editing a filter.

Each alarm is evaluated against each filter. The same alarm can pass different filter conditions and be sent to different destinations. If the same alarm passes different filters and is forwarded using SNMP in each of those filters, the alarm is sent only once since Alarm Forwarding detects this condition and SNMP has only one destination.

Refer to Alarm Forwarding MIB for additional information.



Alarm Forwarding Architecture

Alarm Forwarding supports the forwarding of alarms to applications in an external system. It supports two protocols for alarm forwarding:

- Traps (SNMP)
- Mails (SMTP)

Alarm Forwarding supports the use of Filters. You can create, edit, and delete a **Filter** and a forwarding destination. A Filter List provides information for a Filter:

- Rec No record number; a number given for indexing alarms in the Filter alarm list
- · Rule unique system-generated number that identifies the Filter
- Filter Name name of the Filter
- Description description of the Filter
- Destination Name destination of the filtered alarm. It can be SNMP or SMTP or both.

You can set the forwarding criteria based on the Filters defined for fields such as:

- Ack State
- Alarm Cleared User
- Alarm ID
- Alarm Type
- Managed Object Class
- Managed Object ID
- Perceived Severity ID
- Probable Cause
- Specific Problem
- User Name

Note:

Destination configuration is part of platform configuration. These steps (SMTP server, SNMP version, and target IP) are described in *IDIH Installation Document*.



3 Working in Alarm Forwarding

This chapter provides information about procedures used when working in the Alarm Forwarding application.

Accessing Alarm Forwarding

To open Alarm Forwarding, follow these steps:

1. Log in to IDIH .

The IDIH Application board is displayed.

2. Click Alarm Forwarding.

The Alarm Forwarding home page is displayed.

Alarm Forwarding Toolbar

Figure 3-1 Alarm Forwarding Toolbar



Button	Explanation	
Select Columns	Allows the user to select which columns are displayed	
Navigation Arrows	Moves back and forth among the records.	
Filters	Number of records to display on a page	
Set Size	Sets the number of records to display per page	
Refresh	Resets display to include the most current data	
Add Filter	Adds a Filter, defining the types of alarms to be forwarded and their destination	
Modify Filter	Edits an existing filter's definition	
Delete Filter	Deletes a selected filter	

Table 3-1 Alarm Forwarding Toolbar Icons

Alarm Status Indicator

Test Connection

When logged in to IDIH, either directly or from **DSR** launch, the portal header displays a count of current alarms, as shown in Figure 3-2. The alarm status indicator is a count of the highest severity of all open alarms and the alarm status indicator (circle) is the color (user defined, idihadmin) of the highest severity. For example, if there are

Sends a test message to the destination

SNMP and/or SMTP




zero critical, two major, one minor, and three warnings, then the alarm status indicator contains 2+ and the color is the user-defined color for major severity. The + is used to indicate that there are additional alarms at a lesser severity. The + does not appear if, for example, there are zero critical, two major, zero minor, and zero warnings.

Initially, the alarm status is empty (non-visible). Then, after a short interval, the system queries for open alarms and updates the alarm status indicator. After the first update, the system updates the alarm status indicator every 30 seconds.

Figure 3-2 Alarm Status Indicator

You're logged as idihadmin	🐴 Logout
🚺 User pi	eferences
	2+

Selecting the alarm status indicator shows a brief description of the open alarms. The system displays the list of open alarms in tabular form, as shown in Figure 3-3. This list can be dismissed by pressing the **Close** on the Open Alarm dialog window.





	Alarm Id	Perceived Severity	Managed Object	Specific Problem
d	367	WARNING	mediation	Communication Agent Ingress Message Discarded
ed	391	WARNING	mediation	Communication Agent Egress Message Discarded
d	4	WARNING	mediation	Communication Agent Connection state Changed
d	6	WARNING	mediation	Communication Agent Peer has not responded to heartbeat
d	0	WARNING	mediation	Communication Agent DB Responder change
d	L.			contrained of Agent of Aspender Change
d				
d				
d				
d				
d				
d				
id id				
id id id				
id id id				
kd kd kd xd xd				
id id id				
d d d				
id id id				
id id id				
id id id				

Figure 3-3 Alarm List

Using Alarm Forwarding

This section explains how to set conditions and destinations for forwarding alarms.

Creating a Filter

Filters define the types of alarms to be forwarded and their destination. Filters return True or False results depending upon whether the alarm should be forwarded or not. Each Filter that returns True is forwarded to its specified destination.



Figure 3-4 Filter Creation Dialog

Filter Creation Dialog		
General		• - • • •
O TOUR20002, Specify lifter details		
Fiter Name	Description	
Filter Configuration		
Field	Operator Value	
t Add 🛌 Delete	Operator:	
Expression:		

To create a Filter,

- Click the Add Filter icon on the toolbar. The Create New Filter dialog is displayed.
 - _ _ _
- 2. Type in a Filter Name and Description.
- 3. Select Filter and click the **Add** icon.
- 4. Select a Field, Operator, and Value from the drop-down menus.
- 5. Enter an Expression.
- 6. Select **Next** to advance to the Destination display.
- 7. Select SNMP and/or SMTP.
- 8. Enter Email list (addresses) information.

Note:

Email list is only used when SMTP is selected.

- 9. To advance to the Filter Creation Dialog Summary display, select Next.
- **10.** If this information on the Summary display is correct, select finish create this filter. If there are errors in this summary information, select the previous to return to the display to correct the errors.
- **11.** To add another filter, repeat from **1**.

Editing a Filter

To edit an existing Filter:

1. Select a Filter from the Filter table.



- 2. Click the Modify Filter icon on the toolbar.
- 3. Modify the appropriate field(s) as needed.

For specific information on fields and options, see Creating a Filter.

- 4. Click Next.
- 5. Update Destination information as necessary.

Note:

For **SNMP**, only one trap destination can be defined. For SMTP, multiple email destinations are permitted.

6. Click Finish to save the record changes.

Alarm Forwarding Test Connection

The user can sends a test message to the destination SNMP and/or SMTP using the Connection Test Dialog screen after clicking **Test Connection** .

Figure 3-5 Connection Test Dialog

Connection Test	Dialog
IDIH-20025: Speci	fy test details
SNMP SMTP Smail List	
Note: Please provide	email ids with comma separated("," e.g. support@tekelec.com, abc@xyz.com)

Test Connection for SMTP

The configuring user should verify the SMTP address, SMTP availability through firewalls, and SMTP access mode. Secured destinations require additional parameters be defined and are described in the Installation Document.

1. If the message was received in the targeted mail box, the test was successful. This procedure is complete.

If the message is not in the targeted mail box, continue with this procedure.

- 2. Use the Audit Viewer application to verify if a mail sending error is logged.
- **3.** Contact the My Oracle Support to investigate and help determine the correct SMTP configuration.



Test Connection for SNMP

The configuring user should verify the SNMP address and the SNMP availability thru firewalls. Secured destinations require additional parameters be defined and are described in the *IDIH Installation Document*.

1. Verify the test trap was received by the management system. If the test trap was received by the management system, the test was successful. This procedure is complete.

If the test trap was not received by the management system, continue with this procedure.

2. Contact the My Oracle Support to investigate and help determine the correct SNMP configuration.





This chapter provides information about how the SNMP Agent functions in the Alarm Forwarding application.

SNMP Overview

The main features of the Simple Network Management Protocol (**SNMP**) agent of Alarm Forwarding are:

Overview

- The Management Information Base (**MIB**) contains Managed Object types, Managed Objects, and opened alarms in specific tables.
- The MIB is loaded at SNMP agent startup with metadata and opened alarms already forwarded.

Validation of Traps Sent

- Traps contain a sequence number (since agent startup) that permits Telecommunications Management Network (TMN) to check that none were lost.
- In case of a gap (lost trap) or if the number is lower, the process is restarted and TNM can re-synchronize its database by querying the opened alarms table.

Acknowledgment or Termination from SNMP

A dedicated Access Module for TeMIP is available to integrate easily with the NSP Forwarding SNMP agent.

Note:

SNMP trap forwarding requires the system administrator to configure the destination address, please refer to *Configure SNMP Management Server* in the *IDIH Installation Document*.

Alarm Forwarding MIB

Shown here is the Alarm Forwarding **MIB**, which is located on the NSP server at /usr/ TKLC/xIH/apps/forwarding/target/misc/NSP-FORWARDING-MIB

```
    -- File Name : NSP-FORWARDING-MIB
    -- Date : Mon Nov 21 10:18:28 CET 2006
    -- Author : AdventNet Agent Toolkit Java Edition - MIB Editor 6
    NSP-FORWARDING-MIB DEFINITIONS ::= BEGIN IMPORTS
```



RowStatus, DisplayString FROM SNMPv2-TC NOTIFICATION-GROUP, OBJECT-GROUP FROM SNMPv2-CONF enterprises, MODULE-IDENTITY, OBJECT-TYPE, Integer32, NOTIFICATION-TYPE FROM SNMPv2-SMI; steleus MODULE-IDENTITY LAST-UPDATED 200602131148Z ORGANIZATION Tekelec ttprocessing@tekelec.com CONTACT-INFO Description DESCRIPTION 200602131148Z REVISION NSP module DESCRIPTION ::= { enterprises 4404 } OBJECT IDENTIFIER nsp ::= { steleus 8 } forwarding OBJECT IDENTIFIER ::= { nsp 6 } nspManagedObjectClassTable OBJECT-TYPE SEQUENCE OF SYNTAX NspManagedObjectClassEntry MAX-ACCESS not-accessible STATUS current DESCRIPTION NSP managed object class table ::= { forwarding 1 } nspManagedObjectClassEntry OBJECT-TYPE SYNTAX NspManagedObjectClassEntry MAX-ACCESS not-accessible STATUS current NSP managed object class entry DESCRIPTION INDEX { nspManagedObjectClassId } ::= { nspManagedObjectClassTable 1 } NspManagedObjectClassEntry ::= SEQUENCE { nspManagedObjectClassId Integer32, nspManagedObjectClassName DisplayString, nspManagedObjectClassDescription DisplayString, nspManagedObjectClassRowStatus RowStatus } nspManagedObjectClassId OBJECT-TYPE SYNTAX Integer32 (-2147483648 .. 2147483647) MAX-ACCESS read-only STATUS current Value that defines an instance DESCRIPTION of managed object class in the table ::= { nspManagedObjectClassEntry 1 }



nspManagedObjectClassName OBJECT-TYPE SYNTAX DisplayString MAX-ACCESS read-only STATUS current DESCRIPTION NSP managed object class instance name ::= { nspManagedObjectClassEntry 2 } nspManagedObjectClassDescription OBJECT-TYPE SYNTAX DisplayString MAX-ACCESS read-only STATUS current DESCRIPTION NSP managed object class instance description ::= { nspManagedObjectClassEntry 3 } nspManagedObjectClassRowStatus OBJECT-TYPE SYNTAX RowStatus { active (1) , notInService (2), notReady (3), createAndGo (4), createAndWait (5), destroy (6) } read-create MAX-ACCESS STATUS current DESCRIPTION SMI v2 required attribute ::= { nspManagedObjectClassEntry 50 } nspManagedObjectTable OBJECT-TYPE SYNTAX SEQUENCE OF NspManagedObjectEntry not-accessible MAX-ACCESS STATUS current DESCRIPTION Description ::= { forwarding 2 } nspManagedObjectEntry OBJECT-TYPE SYNTAX NspManagedObjectEntry MAX-ACCESS not-accessible STATUS current DESCRIPTION Row Description INDEX { nspManagedObjectId} ::= { nspManagedObjectTable 1 } NspManagedObjectEntry ::= SEQUENCE { nspManagedObjectId Integer32, nspManagedObjectName DisplayString, nspManagedObjectClassIdRef Integer32, nspManagedObjectParent Integer32, nspManagedObjectRowStatus RowStatus } nspManagedObjectId OBJECT-TYPE SYNTAX Integer32 (-2147483648 .. 2147483647) read-only MAX-ACCESS STATUS current DESCRIPTION Value that defines an instance



of managed object in the table ::= { nspManagedObjectEntry 1 } nspManagedObjectName OBJECT-TYPE SYNTAX DisplayString MAX-ACCESS read-only current STATUS DESCRIPTION Column Description ::= { nspManagedObjectEntry 2 } nspManagedObjectClassIdRef OBJECT-TYPE SYNTAX Integer32 (-2147483648 .. 2147483647) read-only MAX-ACCESS STATUS current Value that defines an instance DESCRIPTION of managed object class ::= { nspManagedObjectEntry 10 } nspManagedObjectParent OBJECT-TYPE SYNTAX Integer32 read-only MAX-ACCESS STATUS current DESCRIPTION Value that defines an instance of parent managed object ::= { nspManagedObjectEntry 20 } nspManagedObjectRowStatus OBJECT-TYPE SYNTAX RowStatus MAX-ACCESS read-create STATUS current DESCRIPTION SMI v2 required attribute ::= { nspManagedObjectEntry 50 } nspAlarmsTable OBJECT-TYPE SYNTAX SEQUENCE OF NspAlarmsEntry not-accessible MAX-ACCESS STATUS current NSP forwarded opened alarms table DESCRIPTION ::= { forwarding 3 } nspAlarmsEntry OBJECT-TYPE SYNTAX NspAlarmsEntry not-accessible MAX-ACCESS STATUS current DESCRIPTION NSP forwarded opened alarms entry INDEX { nspAlarmId } ::= { nspAlarmsTable 1 } NspAlarmsEntry ::= SEQUENCE { nspManagedObjectIdRef Integer32, nspAlarmId Integer32, nspAlarmRowStatus RowStatus, nspManagedObjectDN DisplayString, nspAlarmLastEventTime DisplayString,

```
nspAlarmEventType INTEGER,
               nspAlarmProbableCause INTEGER,
               nspAlarmPerceivedSeverity INTEGER,
               nspAlarmTrendIndication INTEGER,
               nspAlarmThresholdLevel DisplayString,
               nspAlarmObservedValue DisplayString,
               nspAlarmAdditionalText DisplayString,
               nspAlarmSpecificProblem DisplayString,
               nspAlarmFirstDate OCTET STRING,
               nspAlarmClearDate OCTET STRING,
               nspAlarmCriticalCount Integer32,
               nspAlarmMajorCount Integer32,
               nspAlarmMinorCount Integer32,
               nspAlarmWarningCount Integer32,
               nspAlarmAcknowledged INTEGER
               }
       nspManagedObjectIdRef
                               OBJECT-TYPE
               SYNTAX
                                       Integer32 ( -2147483648 ..
2147483647 )
               MAX-ACCESS
                                       read-only
                                       current
               STATUS
                                       Value that refers to managed
               DESCRIPTION
object involved in the forwarded alarm
               ::= { nspAlarmsEntry 1 }
       nspAlarmId
                       OBJECT-TYPE
                                       Integer32 ( -2147483648 ..
               SYNTAX
2147483647 )
               MAX-ACCESS
                                       read-only
               STATUS
                                       current
               DESCRIPTION
                                       Value that defines an instance
of forwarded alarm
               ::= { nspAlarmsEntry 2 }
       nspAlarmRowStatus
                               OBJECT-TYPE
                                       RowStatus { active (1),
               SYNTAX
notInService (2), notReady (3), createAndGo (4), createAndWait
(5), destroy (6) }
               MAX-ACCESS
                                       read-create
               STATUS
                                       current
               DESCRIPTION
                                       SMI v2 required attribute
               ::= { nspAlarmsEntry 50 }
       nspManagedObjectDN
                               OBJECT-TYPE
               SYNTAX
                                       DisplayString
               MAX-ACCESS
                                       read-only
               STATUS
                                       current
               DESCRIPTION
                                       Distinguished name that refers
to managed object involved in the forwarded alarm
               ::= { nspAlarmsEntry 100 }
       nspAlarmLastEventTime
                               OBJECT-TYPE
```



SYNTAX DisplayString MAX-ACCESS read-only STATUS current DESCRIPTION Last event time in ASN.1 format for the last event of the NSP forwarded alarm on the managed object ::= { nspAlarmsEntry 1000 } nspAlarmProbableCause OBJECT-TYPE SYNTAX INTEGER { adapterError (1) , applicationSubsystemFailure (2) , bandwidthReduced (3) , callEstablishmentError (4) , communicationsprotocolError (5), communicationsSubsystemFailure (6), configurationOrCustomizationError (7), congestion (8), corruptData (9), cpuCyclesLimitExceeded (10), dataSetOrModemError (11), degradedSignal (12), dteDceInterfaceError (13), enclosureDoorOpen (14) , equipmentMalfunction (15) , excessiveVibration (16), fileError (17), fireDetected (18), floodDetected (19), framingError (20), heatingVentCoolingSystemnspblem (21), humidityUnacceptable (22), inputOutputDeviceError (23) , inputDeviceError (24) , lanError (25), leakDetected (26), localNodeTransmissionError (27), lossOfFrame (28), lossOfSignal (29), materialSupplyExhausted (30), multiplexerproblem (31), outOfMemory (32), ouputDeviceError (33), performanceDegraded (34), powerproblem (35), pressureUnacceptable (36), processorproblem (37), pumpFailure (38) , queueSizeExceeded (39) , receiveFailure (40) , receiverFailure (41) , remoteNodeTransmissionError (42) , resourceAtOrNearingCapacity (43) , responseTimeExecessive (44), retransmissionRateExcessive (45), softwareError (46), softwareprogramAbnormallyTerminated (47), softwareprogramError (48), storageCapacityproblem (49), temperatureUnacceptable (50), thresholdCrossed (51), timingproblem (52), toxicLeakDetected (53) , transmitFailure (54) , transmitterFailure (55), underlyingResourceUnavailable (56), versionMismatch (57), authenticationFailure (58), breachOfConfidentiality (59), cableTamper (60), delayedInformation (61), denialOfService (62), duplicateInformation (63), informationMissing (64), informationModificationDetected (65), informationOutOfSequence (66) , intrusionDetection (67) , keyExpired (68) , nonRepudiationFailure (69) , outOfHoursActivity (70), outOfService (71), proceduralError (72), unauthorizedAccessAttempt (73) , unexpectedInformation (74) } MAX-ACCESS read-only STATUS current DESCRIPTION Represents the probable cause values for the alarms as per [X.721], [X.733] and [X.736] for the NSP forwarded alarm on the managed object ::= { nspAlarmsEntry 1001 } nspAlarmPerceivedSeverity OBJECT-TYPE INTEGER { indeterminate SYNTAX

```
(0), critical (1), major (2), minor (3), warning (4),
cleared (5) }
               MAX-ACCESS
                                       read-write
               STATUS
                                       current
               DESCRIPTION
                                       Represents the perceived
severity values for the alarms as per [X.733] and [X.721]
                               for the NSP forwarded alarm on the
managed object
               ::= { nspAlarmsEntry 1002 }
       nspAlarmTrendIndication OBJECT-TYPE
                                       INTEGER { lessSevere ( 0 ) ,
               SYNTAX
noChange ( 1 ) , moreSevere ( 2 ) }
               MAX-ACCESS
                                       read-only
               STATUS
                                       current
               DESCRIPTION
                                       Represents the trend indication
values for the alarms as per [X.733]
                               for the NSP forwarded alarm on the
managed object
               ::= { nspAlarmsEntry 1003 }
       nspAlarmThresholdLevel OBJECT-TYPE
               SYNTAX
                                       DisplayString
                                       read-only
               MAX-ACCESS
               STATUS
                                       current
               DESCRIPTION
                                       Represents the threshold level
indication values (real) for the alarms as per [X.733]
                               for the last event of the NSP forwarded
alarm on the managed object
               ::= { nspAlarmsEntry 1004 }
       nspAlarmObservedValue
                               OBJECT-TYPE
                                       DisplayString
               SYNTAX
                                       read-only
               MAX-ACCESS
               STATUS
                                       current
               DESCRIPTION
                                       Represents the threshold
observed values (real) for the alarms as per [X.733]
                               for the last event of the NSP forwarded
alarm on the managed object
               ::= { nspAlarmsEntry 1005 }
       nspAlarmAdditionalText OBJECT-TYPE
                                       DisplayString
               SYNTAX
               MAX-ACCESS
                                       read-only
               STATUS
                                       current
               DESCRIPTION
                                       Represents the additional text
field for the alarm as per [X.733]
                               for the last event of the NSP forwarded
alarm on the managed object
               ::= { nspAlarmsEntry 1006 }
       nspAlarmEventType
                               OBJECT-TYPE
```

SYNTAX INTEGER { otherAlarm (1), communicationAlarm (2), environmentalAlarm (3), equipmentAlarm (4), integrityViolation (5), processingErrorAlarm (10), qualityOfServiceAlarm (11) } MAX-ACCESS read-only STATUS current DESCRIPTION Represents the ITU event type value for the alarms as per [X.721], [X.733] and [X.736] for the NSP forwarded alarm on the managed object ::= { nspAlarmsEntry 1007 } nspAlarmSpecificProblem OBJECT-TYPE SYNTAX DisplayString MAX-ACCESS read-only STATUS current DESCRIPTION Represents the specific problem name for the NSP forwarded alarm on the managed object ::= { nspAlarmsEntry 1008 } nspAlarmFirstDate OBJECT-TYPE SYNTAX OCTET STRING read-only MAX-ACCESS STATUS current DESCRIPTION Represents the raised date in ASN.1 format for the NSP forwarded alarm on the managed object ::= { nspAlarmsEntry 1010 } nspAlarmClearDate OBJECT-TYPE SYNTAX OCTET STRING MAX-ACCESS read-only STATUS current DESCRIPTION Represents the clear date in ASN.1 format for the NSP forwarded alarm on the managed object ::= { nspAlarmsEntry 1011 } nspAlarmCriticalCount OBJECT-TYPE Integer32 SYNTAX MAX-ACCESS read-only STATUS current DESCRIPTION Represents the number of critical events for the NSP forwarded alarm on the managed object ::= { nspAlarmsEntry 1012 } nspAlarmMajorCount OBJECT-TYPE

```
Integer32
               SYNTAX
                                        read-only
               MAX-ACCESS
               STATUS
                                        current
                                        Represents the number of major
               DESCRIPTION
events
                                for the NSP forwarded alarm on the
managed object
                ::= { nspAlarmsEntry 1013 }
        nspAlarmMinorCount
                                OBJECT-TYPE
                                        Integer32
               SYNTAX
               MAX-ACCESS
                                        read-only
               STATUS
                                        current
               DESCRIPTION
                                        Represents the number of minor
events
                                for the NSP forwarded alarm on the
managed object
                ::= { nspAlarmsEntry 1014 }
        nspAlarmWarningCount
                                OBJECT-TYPE
                SYNTAX
                                        Integer32
                                        read-only
               MAX-ACCESS
               STATUS
                                        current
               DESCRIPTION
                                        Represents the number of
warning events
                                for the NSP forwarded alarm on the
managed object
                ::= { nspAlarmsEntry 1015 }
        nspAlarmAcknowledged
                               OBJECT-TYPE
               SYNTAX
                                        INTEGER { false ( 0 ) , true
(1)}
                                        read-write
               MAX-ACCESS
                STATUS
                                        current
               DESCRIPTION
                                        Represents the acknowledged
status
                                for the NSP forwarded alarm of the
managed object
                ::= { nspAlarmsEntry 1016 }
        fwdVersion
                        OBJECT-TYPE
                                        OCTET STRING
                SYNTAX
               MAX-ACCESS
                                        read-only
               STATUS
                                        current
               DESCRIPTION
                                        Current version of the NSP
Forwarding SNMP sub-agent
                ::= { forwarding 10
                                       }
        fwdStatus
                        OBJECT-TYPE
                SYNTAX
                                        INTEGER { allGood ( 0 ) ,
failure ( 1 ) }
               MAX-ACCESS
                                        read-only
                STATUS
                                        current
               DESCRIPTION
                                        Global state of the NSP
Forwarding SNMP sub-agent
```



::= { forwarding 11 } ituAlarmEvent OBJECT IDENTIFIER $::= \{ forwarding 733 \}$ otherAlarm NOTIFICATION-TYPE OBJECTS { nspAlarmId, nspManagedObjectId, nspAlarmLastEventTime, nspAlarmProbableCause, nspAlarmPerceivedSeverity, nspAlarmTrendIndication, nspAlarmThresholdLevel, nspAlarmObservedValue, nspAlarmAdditionalText, nspAlarmSpecificProblem, nspAlarmFirstDate, nspAlarmClearDate, nspAlarmCriticalCount, nspAlarmMajorCount, nspAlarmMinorCount, nspAlarmWarningCount, nspAlarmAcknowledged, nspManagedObjectName, nspManagedObjectDN } STATUS current DESCRIPTION Represents the event type for other alarms as per [X.721], [X.733] and [X.736] ::= { ituAlarmEvent 1 } communicationAlarm NOTIFICATION-TYPE OBJECTS { nspAlarmId, nspManagedObjectId, nspAlarmLastEventTime, nspAlarmProbableCause, nspAlarmPerceivedSeverity, nspAlarmTrendIndication, nspAlarmThresholdLevel, nspAlarmObservedValue, nspAlarmAdditionalText, nspAlarmSpecificProblem, nspAlarmFirstDate, nspAlarmClearDate, nspAlarmCriticalCount, nspAlarmMajorCount, nspAlarmMinorCount, nspAlarmWarningCount, nspAlarmAcknowledged, nspManagedObjectName, nspManagedObjectDN } STATUS current DESCRIPTION Represents the event type for the communication alarms as per [X.721], [X.733] and [X.736] ::= { ituAlarmEvent 2 } environmentalAlarm NOTIFICATION-TYPE OBJECTS { nspAlarmId, nspManagedObjectId, nspAlarmLastEventTime, nspAlarmProbableCause, nspAlarmPerceivedSeverity, nspAlarmTrendIndication, nspAlarmThresholdLevel, nspAlarmObservedValue, nspAlarmAdditionalText, nspAlarmSpecificProblem, nspAlarmFirstDate, nspAlarmClearDate, nspAlarmCriticalCount, nspAlarmMajorCount, nspAlarmMinorCount, nspAlarmWarningCount, nspAlarmAcknowledged, nspManagedObjectName, nspManagedObjectDN } STATUS current DESCRIPTION Represents the event type for the environment alarms as per [X.721], [X.733] and [X.736] ::= { ituAlarmEvent 3 } equipmentAlarm NOTIFICATION-TYPE

OBJECTS { nspAlarmId, nspManagedObjectId, nspAlarmLastEventTime, nspAlarmProbableCause, nspAlarmPerceivedSeverity, nspAlarmTrendIndication, nspAlarmThresholdLevel, nspAlarmObservedValue, nspAlarmAdditionalText, nspAlarmSpecificProblem, nspAlarmFirstDate, nspAlarmCriticalCount, nspAlarmMajorCount, nspAlarmMinorCount, nspAlarmWarningCount, nspAlarmAcknowledged, nspManagedObjectName, nspManagedObjectDN }

STATUS current DESCRIPTION Represents the event type for the equipment alarms as per [X.721], [X.733] and [X.736]

::= { ituAlarmEvent 4 }

integrityViolation NOTIFICATION-TYPE OBJECTS { nspAlarmId,

nspManagedObjectId, nspAlarmLastEventTime, nspAlarmProbableCause, nspAlarmPerceivedSeverity, nspAlarmTrendIndication, nspAlarmThresholdLevel, nspAlarmObservedValue, nspAlarmAdditionalText, nspAlarmSpecificProblem, nspAlarmFirstDate, nspAlarmCriticalCount, nspAlarmMajorCount, nspAlarmMinorCount, nspAlarmWarningCount, nspAlarmAcknowledged, nspManagedObjectName, nspManagedObjectDN }

STATUS current DESCRIPTION Represents the event type for the integrity violation as per [X.721], [X.733] and [X.736]

::= { ituAlarmEvent 5 }

processingErrorAlarm NOTIFICATION-TYPE OBJECTS { nspAlarmId,

nspManagedObjectId, nspAlarmLastEventTime, nspAlarmProbableCause, nspAlarmPerceivedSeverity, nspAlarmTrendIndication, nspAlarmThresholdLevel, nspAlarmObservedValue, nspAlarmAdditionalText, nspAlarmSpecificProblem, nspAlarmFirstDate, nspAlarmCriticalCount, nspAlarmMajorCount, nspAlarmMinorCount, nspAlarmWarningCount, nspAlarmAcknowledged, nspManagedObjectName, nspManagedObjectDN }

STATUS current DESCRIPTION Represents the event type for the processing error alarms as per [X.721], [X.733] and [X.736]

> ::= { ituAlarmEvent 10 }

qualityOfServiceAlarm NOTIFICATION-TYPE OBJECTS

{ nspAlarmId,

nspManagedObjectId, nspAlarmLastEventTime, nspAlarmProbableCause, nspAlarmPerceivedSeverity, nspAlarmTrendIndication, nspAlarmThresholdLevel, nspAlarmObservedValue, nspAlarmAdditionalText, nspAlarmSpecificProblem, nspAlarmFirstDate, nspAlarmCriticalCount, nspAlarmMajorCount, nspAlarmMinorCount, nspAlarmWarningCount,

nspAlarmAcknowledged, nspManagedObjectName, nspManagedObjectDN }

STATUS current DESCRIPTION Represents the event type for the quality of service alarms as per [X.721], [X.733] and [X.736]



::= { ituAlarmEvent 11 } NOTIFICATION-GROUP ituAlarmEventGroup NOTIFICATIONS { communicationAlarm, environmentalAlarm, equipmentAlarm, integrityViolation, otherAlarm, processingErrorAlarm, qualityOfServiceAlarm } STATUS current DESCRIPTION ITU alarm Event notifications $::= \{ forwarding 500 \}$ OBJECT-GROUP managed0bject OBJECTS { nspManagedObjectClassDescription, nspManagedObjectClassId, nspManagedObjectClassIdRef, nspManagedObjectClassName, nspManagedObjectClassRowStatus, nspManagedObjectId, nspManagedObjectIdRef, nspManagedObjectName, nspManagedObjectParent, nspManagedObjectRowStatus, nspManagedObjectDN } STATUS current DESCRIPTION Data related to NSP managed objects ::= { forwarding 200 } alarm OBJECT-GROUP { nspAlarmAcknowledged, OBJECTS nspAlarmAdditionalText, nspAlarmClearDate, nspAlarmCriticalCount, nspAlarmFirstDate, nspAlarmId, nspAlarmLastEventTime, nspAlarmMajorCount, nspAlarmMinorCount, nspAlarmObservedValue, nspAlarmPerceivedSeverity, nspAlarmProbableCause, nspAlarmEventType, nspAlarmRowStatus, nspAlarmSpecificProblem, nspAlarmThresholdLevel, nspAlarmTrendIndication, nspAlarmWarningCount } STATUS current DESCRIPTION Data related to NSP alarms ::= { forwarding 300 } forward OBJECT-GROUP OBJECTS {fwdVersion, fwdStatus} STATUS current DESCRIPTION Data related to NSP forwarding module $::= \{ forwarding 100 \}$

END

