

Configuring JMS on Weblogic Server 12c  
Oracle Banking Treasury Management  
Release 14.5.4.0.0  
Part No. F53253-01  
[February] [2022]



---

# Table of Contents

<b>1. INTRODUCTION .....</b>	<b>1-2</b>
1.1 INTRODUCTION .....	1-2
1.2 PURPOSE.....	1-2
1.3 WEBLOGIC 12C NEW FEATURES .....	1-3
1.4 COMPONENTS DIAGRAM & DATA FLOW .....	1-4
<b>2. PRE-REQUISITES .....</b>	<b>2-1</b>
2.1 MACHINES .....	2-1
2.2 DYNAMIC CLUSTERS AND MANAGED SERVERS .....	2-1
2.3 DATASOURCE .....	2-2
2.4 SHARED FOLDER.....	2-2
<b>3. JMS CONFIGURATION .....</b>	<b>3-1</b>
3.1 PERSISTENCE STORE CREATION .....	3-1
3.2 JMS SERVER CREATION .....	3-3
3.3 CLUSTER CONFIGURATION FOR SERVICE MIGRATION.....	3-5
<b>4. JMS MODULE CREATION .....</b>	<b>4-6</b>
4.1 MODULE CREATION.....	4-6
4.2 SUB DEPLOYMENT CREATION .....	4-8
4.3 RESOURCE CREATION .....	4-10
4.3.1 Queue Creation .....	4-10
4.3.2 Connection Factory Creation .....	4-13
<b>5. SERVER RESTART .....</b>	<b>5-17</b>
<b>6. FOREIGN SERVER CREATION.....</b>	<b>6-1</b>
6.1 MODULE CREATION.....	6-1
6.2 FOREIGN SERVER CREATION .....	6-3
6.3 FOREIGN SERVER CONFIGURATION .....	6-7
<b>7. APPLICATION DEPLOYMENT .....</b>	<b>7-1</b>
<b>8. FREQUENTLY ASKED QUESTIONS.....</b>	<b>8-2</b>
8.1 APPLICATION AND JMS CLUSTER DEPLOYED ON SAME CLUSTER .....	8-2
8.2 APPLICATION SHOWS WARNING UPON RESTART OF MANAGED SERVERS.....	8-2
8.3 SECURING FILE STORE DATA .....	8-3
8.4 T3S PROTOCOL .....	8-3
8.5 HOW TO TEST THE DEPLOYMENT .....	8-3
8.6 INCREASE MAXIMUM NUMBER OF MESSAGE-DRIVEN BEAN THREADS.....	8-5
8.6.1 Modify weblogic-ejb-jar.xml .....	8-5
8.6.2 Work Manager Creation.....	8-6
8.7 HOW HIGH AVAILABILITY IS ACHIEVED.....	8-9
8.8 HOW TO SETUP FOR SCHEDULER/NOTIFICATIONS.....	8-10
8.9 WHAT OTHER MODULES USES JMS QUEUE'S.....	8-10
8.10 REFERENCES .....	8-10

---

# 1. Introduction

## 1.1 Introduction

Below is brief description on major components in Weblogic JMS Server architecture.

## 1.2 Purpose

The purpose of this document is to explain the steps required for JMS Configuration for

- 1) OBTR 14.5.2.0.0
- 2) WebLogic Server 12.1.4.0.0

### JMS Server

JMS server acts as management container for JMS queue and topic resources defined within JMS modules that are targeted to specific that JMS server. A JMS server's main responsibility is to maintain persistent storage for these resources, maintain the state of durable subscriber and etc. JMS servers can host a defined set of modules and any associated persistent storage that reside on a WebLogic Server instance

### JMS Module

JMS modules are application-related definitions that are independent of the domain environment. JMS modules group JMS configuration resources (such as queues, topics, and connections factories). These are outside domain configuration. JMS modules are globally available for targeting to servers and clusters configured in the domain and therefore are available to all the applications deployed on the same targeted. JMS modules contain configuration resources, such as standalone queue and topic destinations, distributed destinations, and connection factories.

### Subdeployment

Subdeployment is also known as Advanced Targeting. Subdeployment resource is a bridge between the group of JMS resources and JMS Servers. When you create a JMS resource you need to choose one Subdeployment.

### JMS Resources

- 1) **Queue** defines a point-to-point destination type, which are used for asynchronous peer communications. A message delivered to queue is distributed to only one customer.
- 2) **Topic** defines a publish/subscribe destination type, which are used for asynchronous peer communication. A message delivered to topic is distributed to all topic consumers
- 3) **Distributed queue** defines a set of queues that are distributed on multiple JMS servers, but are accessible as a single, logical queue to JMS clients
- 4) **Distributed topic** defines a set of topics that are distributed on multiple JMS servers, but which as accessible as a single, logical topic to JMS clients.

- 5) **Uniform Distributed Queue:** queue members are created uniformly from a common configuration.

## Persistence store

A persistent store provides a built-in, high-performance storage solution for weblogic server subsystems and services that required persistence. There are two type of mechanism to store the message


- 1) File based persistence store → Message is stored in a file
- 2) DB based persistence store → Message is stored in Database.

## 1.3 Weblogic 12c New Features


Before weblogic 12c JMS Servers and stores are targeted to individual WLS Servers. Scaling up requires configure the JMS server, the store and target it to new WLS Server

In 12c JMS Servers and stores are targeted to WLS cluster. Scaling up requires to add a WLS server to the cluster.

### Architecture previous to 12c




### Architecture in 12c



## 1.4 Components Diagram & Data Flow

Below is the flow diagram which indicates various components that are used and the document explain steps to create.




## 2. Pre-Requisites

The document assumes that the below are created before proceeding JMS creation.

### 2.1 Machines

MAC-1 & MAC-2



**ORACLE WebLogic Server Administration Console 12c**

Home > Summary of Servers > Summary of Machines

**Summary of Machines**

A machine is the logical representation of the computer that hosts one or more WebLogic Server instances (servers). WebLogic Server uses configured machine names to determine the optimum server in a cluster to which certain tasks, such as HTTP session replication, are delegated. The Administration Server uses the machine definition in conjunction with Node Manager to start remote servers.

This page displays key information about each machine that has been configured in the current WebLogic Server domain.

**Customize this table**


**Machines**

Name	Type
MAC-1	Machine
MAC-2	Machine

Showing 1 to 2 of 2 Previous | Next

### 2.2 Dynamic Clusters and Managed Servers

Ensure Dynamic cluster for OBTR (4 Managed Servers) and Dynamic cluster for JMS Deployment (2 Managed Servers)



**ORACLE WebLogic Server Administration Console 12c**

Home > Summary of Servers > Summary of Clusters > Summary of Server Templates > Summary of Clusters > Summary of Servers > Summary of Clusters > Summary of Server Templates > Summary of Clusters > Summary of Servers > Summary of Clusters

**Summary of Clusters**

This page summarizes the clusters that have been configured in the current WebLogic Server domain.

A cluster defines groups of WebLogic Server servers that work together to increase scalability and reliability.

**Customize this table**

**Clusters (Filtered - More Columns Exist)**

Click the **Lock & Edit** button in the Change Center to activate all the buttons on this page.

Name	Cluster Address	Cluster Messaging Mode	Migration Basis	Default Load Algorithm	Replication Type	Cluster Broadcast Channel	Servers
Cluster-App		Unicast	Database	Round Robin	(None)		DC_FCUBS_1, DC_FCUBS_2, DC_FCUBS_3, DC_FCUBS_4
Cluster-JMS		Unicast	Database	Round Robin	(None)		DC_JMS_1, DC_JMS_2

Showing 1 to 2 of 2 Previous | Next

**ORACLE WebLogic Server Administration Console 12c**

Welcome, weblogic | Connected to: FCUBSDomain

Home > Summary of Server Templates > Summary of Clusters > Summary of Servers > Summary of Clusters > Summary of Servers > Summary of Clusters > Cluster-JMS > Summary of Servers > Summary of Clusters > Summary of Servers

### Summary of Servers

**Configuration** | Control

A server is an instance of WebLogic Server that runs in its own Java Virtual Machine (JVM) and has its own configuration. This page summarizes each server that has been configured in the current WebLogic Server domain.

[Customize this table](#)

**Servers (Filtered - More Columns Exist)**

Click the **Lock & Edit** button in the Change Center to activate all the buttons on this page.

New Clone Delete Showing 1 to 7 of 7 Previous | Next

<input type="checkbox"/>	Name	Type	Cluster	Machine	State	Health	Listen Port
<input type="checkbox"/>	AdminServer (admin)	Configured			RUNNING	OK	7001
<input type="checkbox"/>	DC_FCUBS_1	Dynamic	Cluster-App	MAC-1	SHUTDOWN	Not reachable	7101
<input type="checkbox"/>	DC_FCUBS_2	Dynamic	Cluster-App	MAC-2	SHUTDOWN	Not reachable	7102
<input type="checkbox"/>	DC_FCUBS_3	Dynamic	Cluster-App	MAC-1	SHUTDOWN	Not reachable	7103
<input type="checkbox"/>	DC_FCUBS_4	Dynamic	Cluster-App	MAC-2	SHUTDOWN	Not reachable	7104
<input type="checkbox"/>	DC_JMS_1	Dynamic	Cluster-JMS	MAC-1	SHUTDOWN	Not reachable	7106
<input type="checkbox"/>	DC_JMS_2	Dynamic	Cluster-JMS	MAC-2	SHUTDOWN	Not reachable	7107

New Clone Delete Showing 1 to 7 of 7 Previous | Next

## 2.3 DataSource

Ensure that DataSource required for the MDB ear is created with Target as Cluster-App

**ORACLE WebLogic Server Administration Console**

Welcome, weblogic | Connected to: base\_domain

Home > JMS Modules > JMS\_MODULE > MDB\_QUEUE > Summary of JMS Messages > JMS Modules > JMS\_MODULE > MDB\_QUEUE > Summary of JMS Messages > Summary of Deployments > Summary of JDBC Data Sources

### Summary of JDBC Data Sources

**Configuration** | Monitoring

A JDBC data source is an object bound to the JNDI tree that provides database connectivity through a pool of JDBC connections. Applications can look up a data source on the JNDI tree and then borrow a database connection from a data source. This page summarizes the JDBC data source objects that have been created in this domain.

[Customize this table](#)

**Data Sources (Filtered - More Columns Exist)**

New Delete Showing 1 to 3 of 3 Previous | Next

<input type="checkbox"/>	Name	Type	JNDI Name	Targets
<input type="checkbox"/>	FLEXTES.WORLD	Generic	FLEXTES.WORLD	Cluster-App
<input type="checkbox"/>	jdbc/bridge	Generic	jdbc/bridge	AdminServer


## 2.4 Shared Folder

A shared folder for File Store Creation is required and this folder should be accessible across both the servers (eg, NFS mount).

## 3. JMS Configuration

### 3.1 Persistence Store Creation

- 1) Navigate to Services → Persistent Stores → New → Create FileStore



## 2) Select **Cluster-JMS** under target dropdown and Click on OK

**ORACLE WebLogic Server Administration Console 12c**

Home > Summary of Clusters > Summary of Servers > Summary of Clusters > Summary of Servers > Summary of Clusters > Cluster-JMS > Summary of Servers > Summary of Clusters > Summary of Servers > Summary of Persistent Stores

**Create a New File Store**

OK Cancel

**File Store Properties**

The following properties will be used to identify your new file store.  
\* Indicates required fields

What would you like to name your new file store?

\* Name:

Select a server instance for this file store.

Target:

The pathname to the directory on the file system where the file store is kept. This directory must exist on your system, so be sure to create it before completing this tab.

Directory:

OK Cancel

## 3) **FileStore-1** is created

**ORACLE WebLogic Server Administration Console 12c**

Home > Summary of Clusters > Summary of Servers > Summary of Clusters > Summary of Servers > Summary of Clusters > Cluster-JMS > Summary of Servers > Summary of Clusters > Summary of Servers > Summary of Persistent Stores

**Messages**

✔ All changes have been activated. No restarts are necessary.

**Summary of Persistent Stores**

A persistent store is a physical repository for storing subsystem data, such as persistent JMS messages. It can be a JDBC-accessible database, disk-based file, or replicated memory storage. This page summarizes the persistent stores that have been created for this domain.

Customize this table

**Persistent Stores**

Click the **Lock & Edit** button in the Change Center to activate all the buttons on this page.

New Delete


Name	Type	Target
FileStore-1	FileStore	Cluster-JMS

New Delete


Showing 1 to 1 of 1 Previous Next

## 3.2 JMS Server Creation


- 1) Navigate to Services → Messaging → JMS Servers → Click on **New**




- 2) Select FileStore-1 , Click **Next**




- 3) Select Target as Cluster-JMS and click on **Finish**





#### 4) JMS-Server-1 is created



#### 5) In NFS below filestores can be seen

```
[root@JMS_FILESTORE]# ll
total 2056
-rw-r----- 1 wll2c oinstall 1049088 Jun 16 14:10 FILESTORE-1@DC_JMS_1000000.DAT
-rw-r----- 1 wll2c oinstall 1049088 Jun 16 14:10 FILESTORE-1@DC_JMS_2000000.DAT
[root@JMS_FILESTORE]# pwd
/scratch/work_area/JMS_FILESTORE
[root@JMS_FILESTORE]#
```

### 3.3 Cluster Configuration for Service Migration

- 1) Click on Environment → Clusters → Cluster-JMS

The screenshot shows the Oracle WebLogic Server Administration Console. On the left, the 'Domain Structure' tree is expanded to 'Clusters'. The main content area displays the 'Summary of Clusters' page. A table lists the configured clusters:

Name	Cluster Address	Cluster Messaging Mode	Migration Basis	Default Load Algorithm	Replication Type	Cluster Bin
Cluster-App		Unicast	Database	Round Robin	(None)	
Cluster-JMS		Unicast	Database	Round Robin	(None)	

- 2) Click on **Migration** Tab


The screenshot shows the 'Settings for Cluster-JMS' page. The 'Configuration' tab is active, and the 'Migration' sub-tab is selected. The 'Migration' sub-tab contains a 'Coherence' section with a 'Save' button.

- 3) Change Migration Basis to Consensus and Click on **Save**


## 4. JMS Module Creation

### 4.1 Module Creation


- 1) Navigate to Services → Messaging → JMS Modules and Click on **New**.




- 2) Enter name as JMS\_MODULE and Click on **Next**




- 3) Select Target as Cluster-JMS and Click on **Next**



#### 4) Select the checkbox and Click on **Finish**



#### 5) JMS\_MODULE is created



## 4.2 Sub Deployment Creation

- 1) In JMS\_MODULE, Click on Sub Deployment tab , Click on **New**

The screenshot shows the Oracle WebLogic Server Administration Console 12c. The left sidebar contains the Domain Structure tree with 'JMS Modules' highlighted. The main content area displays the 'Settings for JMS\_Module' page, with the 'Subdeployments' tab selected. The 'Subdeployments-Tab' section contains a table titled 'Summary of Resources' which is currently empty, showing 'Showing 0 to 0 of 0'. A red arrow points to the 'New' button at the bottom of the table.

ORACLE WebLogic Server Administration Console 12c

Home > MS-JMS1 (migratable) > Summary of Migratable Targets > MS-JMS2 (migratable) > Summary of Clusters > Summary of Migratable Targets > MS-JMS1 (migratable) > Summary of Clusters > Summary of Migratable Targets > Summary of JMS Modules > JMS\_Module

Messages

- ✓ All changes have been activated. However 1 items must be restarted for the changes to take effect.
- ✓ The JMS module was created successfully.

Settings for JMS\_Module

Configuration Subdeployments Targets Security Notes

Subdeployments-Tab

This page displays general information about a JMS system module and its resources. It also allows you to configure new resources and access existing resources.

Name: JMS\_Module The name of this JMS system module. [More Info...](#)

Descriptor File Name: jms/jms\_module-jms.xml The name of the JMS module descriptor file. [More Info...](#)

This page summarizes the JMS resources that have been created for this JMS system module, including queue and topic destinations, connection factories, JMS templates, destination sort keys, destination quota, distributed destinations, foreign servers, and store-and-forward parameters.

Customize this table

Summary of Resources

New Delete Showing 0 to 0 of 0 Previous | Next

Name	Type	JNDI Name	Subdeployment	Targets
There are no items to display				

New Delete Showing 0 to 0 of 0 Previous | Next

WebLogic Server Version: 12.1.3.0.0  
Copyright (c) 1996, 2014, Oracle and/or its affiliates. All rights reserved.  
Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

- 2) Enter name as JMS\_SUB and click on **Next**

The screenshot shows the 'Create a New Subdeployment' dialog box in the Oracle WebLogic Server Administration Console. The 'Next' button is highlighted with a red box. The 'Subdeployment Name' field contains the text 'JMS\_SUB', with a red arrow pointing to it. The dialog also includes 'Back', 'Finish', and 'Cancel' buttons.

ORACLE WebLogic Server Administration Console 12c

Home > MS-JMS1 (migratable) > Summary of Migratable Targets > MS-JMS2 (migratable) > Summary of Clusters > Summary of Migratable Targets > MS-JMS1 (migratable) > Summary of Clusters > Summary of Migratable Targets > Summary of JMS Modules > JMS\_Module

Create a New Subdeployment

Back Next Finish Cancel

Subdeployment Properties

The following properties will be used to identify your new subdeployment.

\* Indicates required fields

\* Subdeployment Name: JMS\_SUB

Back Next Finish Cancel

### 3) Select Target as Cluster-JMS and Click on **Finish**

The screenshot shows the Oracle WebLogic Server Administration Console. The left sidebar contains the 'Change Center' and 'Domain Structure' panels. The main area displays the 'Create a New Subdeployment' wizard. The 'Targets' section is active, showing a list of targets: 'AdminServer', 'Cluster-JMS' (selected), and 'JMS Servers'. The 'Cluster-JMS' target is highlighted, and the 'All servers in the cluster' option is selected. The 'Finish' button is visible at the bottom of the wizard.

### 4) Sub-Deployment is created

The screenshot shows the Oracle WebLogic Server Administration Console. The left sidebar contains the 'Change Center' and 'Domain Structure' panels. The main area displays the 'Settings for JMS\_Module' page. The 'Subdeployments' tab is selected, showing a table with the following data:

Name	Resources	Targets
JMS_SUB		Cluster-JMS

A red arrow points to the 'JMS\_SUB' entry in the table. The 'Messages' section at the top of the page displays two green checkmarks: 'All changes have been activated. However 1 items must be restarted for the changes to take effect.' and 'Subdeployment created successfully.'

## 4.3 Resource Creation

### 4.3.1 Queue Creation


1) In JMS\_MODULE Click on **New**

The screenshot shows the Oracle WebLogic Server Administration Console. The left sidebar contains the 'Domain Structure' tree with 'JMS Modules' highlighted. The main content area is titled 'Settings for JMS\_Module' and has tabs for 'Configuration', 'Subdeployments', 'Targets', 'Security', and 'Notes'. The 'Configuration' tab is active, displaying general information about the JMS system module. Below this, there is a 'Summary of Resources' section with a table that is currently empty. A red box highlights the 'New' button in the 'Summary of Resources' section.


2) Select Distributed Queue and Click on **Next**

The screenshot shows the 'Create a New JMS System Module Resource' page. The 'Next' button is highlighted with a red box. Below the buttons, there is a section titled 'Choose the type of resource you want to create.' with a list of options: 'Connection Factory', 'Queue', 'Topic', and 'Distributed Queue'. The 'Distributed Queue' option is selected, indicated by a red arrow pointing to it. The 'Distributed Queue' option is described as defining a set of queues that are distributed on multiple JMS servers, but which are accessible as a single, logical queue to JMS clients.


3) Enter the queue name and Click on **Next**.



4) Click on **Advance Targeting**.



5) Select Subdeployment as JMS\_SUB and Click on **Finish**.



## 6) MDB\_QUEUE is created

**ORACLE WebLogic Server Administration Console 12c**

Home Log Out Preferences Record Help

Welcome, weblogic Connected to: pegjms

Home > MS-JMS1 (migratable) > Summary of Migratable Targets > MS-JMS2 (migratable) > Summary of Clusters > Summary of Migratable Targets > MS-JMS1 (migratable) > Summary of Clusters > Summary of Migratable Targets > Summary of JMS Modules > JMS\_MODULE

**Messages**

- ✓ All changes have been activated. However 1 items must be restarted for the changes to take effect.
- ✓ The JMS distributed queue was created successfully.

**Settings for JMS\_MODULE**

**Configuration** Subdeployments Targets Security Notes

This page displays general information about a JMS system module and its resources. It also allows you to configure new resources and access existing resources.

**Name:** JMS\_MODULE The name of this JMS system module. [More Info...](#)

**Descriptor File Name:** jms/jms\_module-jms.xml The name of the JMS module descriptor file. [More Info...](#)

This page summarizes the JMS resources that have been created for this JMS system module, including queue and topic destinations, connection factories, JMS templates, destination sort keys, destination quota, distributed destinations, foreign servers, and store-and-forward parameters.

**Customize this table**

**Summary of Resources**

New Delete Showing 1 to 1 of 1 Previous | Next

Name	Type	JNDI Name	Subdeployment	Targets
MDB_QUEUE	Uniform Distributed Queue	MDB_QUEUE	JMS_SUB	Cluster-JMS

New Delete Showing 1 to 1 of 1 Previous | Next

## 7) Similarly Create MDB\_QUEUE\_RESPONSE and MDB\_QUEUE\_DLQ

**ORACLE WebLogic Server Administration Console 12c**

Home Log Out Preferences Record Help

Welcome, weblogic Connected to: FCUBSDomain

Home > DC\_JMS\_Template-0 > Summary of Servers > Summary of Migratable Targets > Summary of JMS Servers > JMS\_Servers-1 > Summary of JMS Servers > JMS\_Servers-1 > Summary of Migratable Targets > Summary of JMS Modules > JMS\_MODULE

**Messages**

- ✓ All changes have been activated. No restarts are necessary.

**Settings for JMS\_MODULE**

**Configuration** Subdeployments Targets Security Notes

This page displays general information about a JMS system module and its resources. It also allows you to configure new resources and access existing resources.

**Name:** JMS\_MODULE The name of this JMS system module. [More Info...](#)

**Descriptor File Name:** jms/jms\_module-jms.xml The name of the JMS module descriptor file. [More Info...](#)

This page summarizes the JMS resources that have been created for this JMS system module, including queue and topic destinations, connection factories, JMS templates, destination sort keys, destination quota, distributed destinations, foreign servers, and store-and-forward parameters.

**Customize this table**

**Summary of Resources**

Click the **Lock & Edit** button in the Change Center to activate all the buttons on this page.

New Delete Showing 1 to 3 of 3 Previous | Next

Name	Type	JNDI Name	Subdeployment	Targets
MDB_QUEUE	Uniform Distributed Queue	MDB_QUEUE	JMS_SUB	Cluster-JMS
MDB_QUEUE_DLQ	Uniform Distributed Queue	MDB_QUEUE_DLQ	JMS_SUB	Cluster-JMS
MDB_QUEUE_RESPONSE	Uniform Distributed Queue	MDB_QUEUE_RESPONSE	JMS_SUB	Cluster-JMS

New Delete Showing 1 to 3 of 3 Previous | Next

## 4.3.2 Connection Factory Creation

1) In JMS\_MODULE, Click on **New**

**ORACLE WebLogic Server Administration Console 12c**

Home > MS-JMS1 (migratable) > Summary of Migratable Targets > MS-JMS2 (migratable) > Summary of Clusters > Summary of Migratable Targets > MS-JMS1 (migratable) > Summary of Clusters > Summary of Migratable Targets > Summary of JMS Modules > **JMS\_Module**

**Messages**

- ✓ All changes have been activated. However 1 items must be restarted for the changes to take effect.
- ✓ The JMS distributed queue was created successfully.

**Settings for JMS\_Module**

**Configuration** Subdeployments Targets Security Notes

This page displays general information about a JMS system module and its resources. It also allows you to configure new resources and access existing resources.

**Name:** JMS\_Module The name of this JMS system module. [More Info...](#)

**Descriptor File Name:** jms/jms\_module-jms.xml The name of the JMS module descriptor file. [More Info...](#)

This page summarizes the JMS resources that have been created for this JMS system module, including queue and topic destinations, connection factories, JMS templates, destination sort keys, destination quota, distributed destinations, foreign servers, and store-and-forward parameters.

[Customize this table](#)

**Summary of Resources**

New Delete Showing 1 to 3 of 3 Previous | Next

Name	Type	JNDI Name	Subdeployment	Targets
MDB_QUEUE	Uniform Distributed Queue	MDB_QUEUE	JMS_SUB	Cluster-JMS
MDB_QUEUE_DLQ	Uniform Distributed Queue	MDB_QUEUE_DLQ	JMS_SUB	Cluster-JMS
MDB_QUEUE_RESPONSE	Uniform Distributed Queue	MDB_QUEUE_RESPONSE	JMS_SUB	Cluster-JMS

New Delete Showing 1 to 3 of 3 Previous | Next

WebLogic Server Version: 12.1.3.0.0  
Copyright (c) 1996,2014, Oracle and/or its affiliates. All rights reserved.  
Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

2) Select Connection Factory and click on **Next**

**ORACLE WebLogic Server Administration Console 12c**

Home > MS-JMS1 (migratable) > Summary of Migratable Targets > MS-JMS2 (migratable) > Summary of Clusters > Summary of Migratable Targets > MS-JMS1 (migratable) > Summary of Clusters > Summary of Migratable Targets > Summary of JMS Modules > **JMS\_Module**

**Create a New JMS System Module Resource**

Back **Next** Finish Cancel

**Choose the type of resource you want to create.**

Use these pages to create resources in a JMS system module, such as queues, topics, templates, and connection factories.

Depending on the type of resource you select, you are prompted to enter basic information for creating the resource. For targetable resources, like stand-alone queues and topics, connection factories, distributed queues and topics, foreign servers, and JMS SAF destinations, you can also proceed to targeting pages for selecting appropriate server targets. You can also associate targetable resources with subdeployments, which is an advanced mechanism for grouping JMS module resources and the members to server resources.

☒ **Connection Factory** Defines a set of connection configuration parameters that are used to create connections for JMS clients. [More Info...](#)

☐ Queue Defines a point-to-point destination type, which are used for asynchronous peer communications. A message

### 3) Enter the Name and Click on **Next**

ORACLE WebLogic Server Administration Console 12c

Home Log Out Preferences Record Help

Welcome, weblogic Connected to: pegjms

Home > MS-JMS1 (migratable) > Summary of Migratable Targets > MS-JMS2 (migratable) > Summary of Clusters > Summary of Migratable Targets > MS-JMS1 (migratable) > Summary of Clusters > Summary of Migratable Targets > Summary of JMS Modules > JMS\_Module

### Create a New JMS System Module Resource

Back **Next** Finish Cancel

#### Connection Factory Properties

The following properties will be used to identify your new connection factory. The current module is JMS\_Module.

\* Indicates required fields

What would you like to name your new connection factory?

\* Name:  ←

What JNDI Name would you like to use to look up your new connection factory?

JNDI Name:  ←

### 4) Click on **Advance Targeting**

ORACLE WebLogic Server Administration Console 12c

Home Log Out Preferences Record Help

Welcome, weblogic Connected to: FCUBSDomain

Home > DC\_JMS\_Template-0 > Summary of Servers > Summary of Migratable Targets > Summary of JMS Servers > JMS-Server-1 > Summary of JMS Servers > JMS-Server-1 > Summary of Migratable Targets > Summary of JMS Modules > JMS\_MODULE

### Create a New JMS System Module Resource

Back Next Finish **Advanced Targeting** Cancel

#### The following properties will be used to target your new JMS system module resource

Use this page to view and accept the default targets where this JMS resource will be targeted. The default targets are based on the parent JMS system module targets. If you do not want to accept the default targets, then click **Advanced Targeting** to use the subdeployment mechanism for targeting this resource.

The following JMS module targets will be used as the default targets for your new JMS system module resource. If the module's targets are changed, this resource will also be retargeted appropriately.

Targets :

Clusters
<input checked="" type="checkbox"/> Cluster-JMS
⊙ All servers in the cluster

Back Next Finish **Advanced Targeting** Cancel

## 5) Select JMS\_SUB and Click on **Finish**

**ORACLE WebLogic Server Administration Console 12c**

Home Log Out Preferences Record Help Welcome, weblogic Connected to: FCUBSDomain

Home > DC\_JMS\_Template-0 > Summary of Servers > Summary of Migratable Targets > Summary of JMS Servers > JMSServer-1 > Summary of Migratable Targets > Summary of JMS Modules > JMS\_MODULE

### Create a New JMS System Module Resource

Back Next Finish Cancel

The following properties will be used to target your new JMS system module resource

Use this page to select a subdeployment to assign this system module resource. A subdeployment is a mechanism by which JMS resources are grouped and targeted to a server instance, cluster, or SAF agent. If necessary, you can create a new subdeployment by clicking the **Create a New Subdeployment** button. You can also reconfigure subdeployment targets later by using the parent module's subdeployment management page.

Select the subdeployment you want to use. If you select (none), no targeting will occur.

**Subdeployments:** JMS\_SUB Create a New Subdeployment

What targets do you want to assign to this subdeployment?

**Targets :**

**Servers**

☐ AdminServer

**Clusters**

☒ Cluster-JMS

☒ All servers in the cluster

**JMS Servers**

☐ JMSServer-1

Back Next Finish Cancel

**Change Center**

**View changes and restarts**

No pending changes exist. Click the Release Configuration button to allow others to edit the domain.

Lock & Edit

Release Configuration

**Domain Structure**

- Environment
  - Servers
    - Clusters
      - Server Templates
        - Migratable Targets
  - Coherence Clusters
  - Machines
  - Virtual Hosts
  - Work Managers
  - Startup and Shutdown Classes
  - Deployments
    - Services
      - Messaging

**How do I...**

- Configure quotas for destinations
- Configure JMS templates
- Configure destination keys
- Configure topics
- Configure queues
- Configure connection factories
- Configure uniform distributed topics
- Configure uniform distributed queues
- Configure foreign servers
- Configure JMS SAF

**System Status**

## 6) Connection Factory is **Created**.

ORACLE WebLogic Server Administration Console 12c

[Home](#)
[Log Out](#)
[Preferences](#)
[Record](#)
[Help](#)

Welcome, weblogic
Connected to: pegjms

Change Center

View changes and restarts

Configuration editing is enabled. Future changes will automatically be activated as you modify, add or delete items in this domain.

Domain Structure

- Environment
- Deployments
- Services
  - Messaging
    - JMS Servers
    - Store-and-Forward Agents
    - JMS Modules
    - Path Services
  - Bridges
  - Data Sources
  - Persistent Stores
  - Foreign JNDI Providers
  - Work Contexts

How do I...

No task help found.

System Status

Health of Running Servers

Failed (0)

Critical (0)

Overloaded (0)

Warning (0)

OK (1)

Home > MS-JMS1 (migratable) > Summary of Migratable Targets > MS-JMS2 (migratable) > Summary of Clusters > Summary of Migratable Targets > MS-JMS1 (migratable) > Summary of Clusters > Summary of Migratable Targets > Summary of JMS Modules > JMS\_Module

Messages

All changes have been activated. However 1 items must be restarted for the changes to take effect.

Connection factory created successfully.

Settings for JMS\_Module

Configuration

Subdeployments

Targets

Security

Notes

This page displays general information about a JMS system module and its resources. It also allows you to configure new resources and access existing resources.

Name:

JMS\_Module

The name of this JMS system module. [More Info...](#)

Descriptor File Name:

jms/jms\_module-jms.xml

The name of the JMS module descriptor file. [More Info...](#)

This page summarizes the JMS resources that have been created for this JMS system module, including queue and topic destinations, connection factories, JMS templates, destination sort keys, destination quota, distributed destinations, foreign servers, and store-and-forward parameters.

Customize this table

Summary of Resources

New

Delete

Showing 1 to 4 of 4

Previous

Next

Name	Type	JNDI Name	Subdeployment	Targets
MDBQCF	Connection Factory	MDBQCF	JMS_SUB	Cluster-JMS
MDB_QUEUE	Uniform Distributed Queue	MDB_QUEUE	JMS_SUB	Cluster-JMS
MDB_QUEUE_DLQ	Uniform Distributed Queue	MDB_QUEUE_DLQ	JMS_SUB	Cluster-JMS
MDB_QUEUE_RESPONSE	Uniform Distributed Queue	MDB_QUEUE_RESPONSE	JMS_SUB	Cluster-JMS

New

Delete

Showing 1 to 4 of 4

Previous

Next

4-16

ORACLE®

## 5. Server Restart

- 1) Increase the heap size of both DC\_JMS\_1 and DC\_JMS\_2 cluster

The screenshot shows the Oracle WebLogic Server Administration Console. The left sidebar contains the 'Change Center' with 'View changes and restarts' and 'Lock & Edit' buttons, and the 'Domain Structure' tree with 'Servers' expanded. The main content area is titled 'Summary of Servers' and shows a table of servers. The table has columns: Name, Type, Cluster, Machine, State, Health, and Listen Port. The servers listed are AdminServer(admin), DC\_FCUBS\_1, DC\_FCUBS\_2, DC\_FCUBS\_3, DC\_FCUBS\_4, DC\_JMS\_1, and DC\_JMS\_2. The state of DC\_JMS\_1 and DC\_JMS\_2 is 'SHUTDOWN' and 'Not reachable'.

Name	Type	Cluster	Machine	State	Health	Listen Port
AdminServer(admin)	Configured			RUNNING	OK	7001
DC_FCUBS_1	Dynamic	Cluster-App	MAC-1	SHUTDOWN	Not reachable	7101
DC_FCUBS_2	Dynamic	Cluster-App	MAC-2	SHUTDOWN	Not reachable	7102
DC_FCUBS_3	Dynamic	Cluster-App	MAC-1	SHUTDOWN	Not reachable	7103
DC_FCUBS_4	Dynamic	Cluster-App	MAC-2	SHUTDOWN	Not reachable	7104
DC_JMS_1	Dynamic	Cluster-JMS	MAC-1	SHUTDOWN	Not reachable	7106
DC_JMS_2	Dynamic	Cluster-JMS	MAC-2	SHUTDOWN	Not reachable	7107

- 2) Select the cluster 'DC\_JMS\_Template-0' and

The screenshot shows the Oracle WebLogic Server Administration Console. The left sidebar contains the 'Change Center' with 'View changes and restarts' and 'Lock & Edit' buttons, and the 'Domain Structure' tree with 'Server Templates' expanded. The main content area is titled 'Summary of Server Templates' and shows a table of server templates. The table has columns: Name, Cluster, Machine, Listen Port, and Listen Address. The templates listed are DC\_FCUBS\_Template and DC\_JMS\_Template-0. The state of DC\_JMS\_Template-0 is 'SHUTDOWN' and 'Not reachable'.

Name	Cluster	Machine	Listen Port	Listen Address
DC_FCUBS_Template	Cluster-App		7100	
DC_JMS_Template-0	Cluster-JMS		7105	

3) Click on Server Start Tab and in Arguments Section enter **-XX:MaxPermSize=512m**

The screenshot displays the Oracle WebLogic Server Administration Console. The left sidebar contains navigation panels for 'Change Center', 'Domain Structure', 'How do I...', and 'System Status'. The main content area is titled 'Settings for DC\_JMS\_Template-0' and features a tabbed interface with 'Configuration', 'Protocols', 'Logging', 'Debug', and 'Notes'. The 'Configuration' tab is active, showing sub-tabs for 'General', 'Cluster', 'Services', 'Keystores', 'SSL', 'Federation Services', 'Deployment', 'Migration', 'Tuning', 'Overload', 'Health Monitoring', 'Server Start', 'Web Services', and 'Coherence'. The 'Server Start' sub-tab is selected, revealing configuration fields for 'Java Home', 'Java Vendor', 'BEA Home', 'Root Directory', 'Class Path', and 'Arguments'. The 'Arguments' field is highlighted with a red box and contains the text '-XX:MaxPermSize=512m'. A 'Save' button is located at the top left of the configuration area.

4) **Restart** the AdminServer and DC\_JMS\_1 and DC\_JMS\_2 managed servers.

## 6. Foreign Server Creation

### 6.1 Module Creation

#### 1) JMS\_Modules and Click on **New**

ORACLE WebLogic Server Administration Console 12c

Home Log Out Preferences Record Help

Welcome, weblogic Connected to: pegjms

Home > Summary of Servers > MS-JMS2 > Summary of Virtual Hosts > Summary of Servers > Summary of Clusters > Summary of Migratable Targets > Summary of Servers > Summary of Deployments > Summary of JMS Modules

**Summary of JMS Modules**

JMS system resources are configured and stored as modules similar to standard J2EE modules. Such resources include queues, topics, connection factories, templates, destination keys, quota, distributed queues, distributed topics, foreign servers, and JMS store-and-forward (SAF) parameters. You can administratively configure and manage JMS system modules as global system resources.

This page summarizes the JMS system modules that have been created for this domain.

Customize this table

**JMS Modules**

Name	Type
JMS_Module	System

New Delete

Showing 1 to 1 of 1 Previous | Next

New Delete

Showing 1 to 1 of 1 Previous | Next

How do I...  
• Configure JMS system modules  
• Configure resources for JMS system modules

#### 2) Enter name as MDB\_MODULE and click on **Next**

ORACLE WebLogic Server Administration Console 12c

Home Log Out Preferences Record Help

Welcome, weblogic Connected to: pegjms

Home > Summary of Migratable Targets > MS-JMS1 (migratable) > Summary of Migratable Targets > MS-JMS2 (migratable) > Summary of Clusters > Summary of Migratable Targets > MS-JMS1 (migratable) > S

**Create JMS System Module**

Back Next Finish Cancel

The following properties will be used to identify your new module.

JMS system resources are configured and stored as modules similar to standard J2EE modules. Such resources include queues, topics, connection factories, templates, destination keys, quota, distributed queues, distributed topics, foreign servers, and JMS store-and-forward (SAF) parameters. You can administratively configure and manage JMS system modules as global system resources.

\* Indicates required fields

What would you like to name your System Module?

\* Name: MDB\_MODULE

What would you like to name the descriptor file name? If you do not provide a name, a default will be assigned.

Descriptor File Name:

Where would like to place the descriptor for this System Module, relative to the jms configuration sub-directory of your domain?


Location In Domain:

Back Next Finish Cancel


How do I...  
• Configure JMS system modules  
• Configure JMS servers

System Status  
Health of Running Servers  
Failed (0)


### 3) Select target as Cluster-App and click on **Next**



### 4) Select CheckBox and Click on **Finish**



### 5) MDB\_MODULE is created



## 6.2 Foreign Server Creation

In MDB\_MODULE, Click on New Resource, Select Foreign Server

Oracle WebLogic Server Administration Console 12c

Home > Summary of Servers > Summary of Deployments > Summary of JMS Modules > MDB\_MODULE > Summary of Migratable Targets > Summary of Clusters > Summary of JMS Servers > Summary of JMS Modules > MDB\_MODULE > Summary of JMS Modules

Welcome, weblogic | Connected to: pegjms

**Summary of JMS Modules**

JMS system resources are configured and stored as modules similar to standard J2EE modules. Such resources include queues, topics, connection factories, templates, destination keys, quota, distributed queues, distributed topics, foreign servers, and JMS store-and-forward (SAF) parameters. You can administratively configure and manage JMS system modules as global system resources.

This page summarizes the JMS system modules that have been created for this domain.

[Customize this table](#)

**JMS Modules**

New Delete Showing 1 to 2 of 2 Previous | Next

Name	Type
JMS_Module	System
MDB_MODULE	System

New Delete Showing 1 to 2 of 2 Previous | Next

1) Click on Configuration → New

Oracle WebLogic Server Administration Console 12c

Home > Summary of Deployments > Summary of JMS Modules > MDB\_MODULE > Summary of Migratable Targets > Summary of Clusters > Summary of JMS Servers > Summary of JMS Modules > MDB\_MODULE > Summary of JMS Modules > MDB\_MODULE

Welcome, weblogic | Connected to: pegjms

**Settings for MDB\_MODULE**

Configuration Subdeployments Targets Security Notes

This page displays general information about a JMS system module and its resources. It also allows you to configure new resources and access existing resources.

**Name:** MDB\_MODULE The name of this JMS system module. [More Info...](#)

**Descriptor File Name:** jms/mdb\_module-jms.xml The name of the JMS module descriptor file. [More Info...](#)

This page summarizes the JMS resources that have been created for this JMS system module, including queue and topic destinations, connection factories, JMS templates, destination sort keys, destination quota, distributed destinations, foreign servers, and store-and-forward parameters.

[Customize this table](#)

**Summary of Resources**

New Delete Showing 0 to 0 of 0 Previous | Next

Name	Type	JNDI Name	Subdeployment	Targets
There are no items to display				

New Delete Showing 0 to 0 of 0 Previous | Next


## 2) Select Foreign Server and Click on Next

The screenshot shows the Oracle WebLogic Server Administration Console 12c. The left sidebar contains the 'Change Center' and 'Domain Structure' panels. The 'Domain Structure' panel shows a tree view with 'Environment' > 'Servers' > 'Clusters' > 'Server Templates' > 'Migratable Targets' > 'Coherence Clusters' > 'Machines' > 'Virtual Hosts' > 'Work Managers' > 'Startup and Shutdown Classes' > 'Deployments' > 'Services' > 'Messaging'. The 'How do I...' panel lists various configuration tasks. The main content area displays the 'Create a New JMS System Module Resource' wizard. The 'Next' button is highlighted with a red box. Below the wizard title, there is a section titled 'Choose the type of resource you want to create.' with a list of resource types: Connection Factory, Queue, Topic, Distributed Queue, Distributed Topic, and Foreign Server. The 'Foreign Server' option is selected and highlighted with a red box. The 'Next' button is also highlighted with a red box.


## 3) Enter name and Click on Next

The screenshot shows the 'Foreign Server Properties' dialog box in the Oracle WebLogic Server Administration Console. The dialog box has a title bar and a main content area. The main content area contains the text 'The following properties will be used to identify your new foreign server. The current module is MDB\_MODULE.' and a list of properties. The 'Name' property is highlighted with a red box and has a red arrow pointing to it. The 'Name' field is filled with the text 'ForeignServer-1'. The 'Next' button is highlighted with a red box.


#### 4) Click on Advanced Targeting



#### 5) Click on Create New SubDeployment



#### 6) Enter Name as MDB\_SUB and Click on OK



## 7) Select Target as Cluster-App and Click on Finish

**ORACLE WebLogic Server Administration Console 12c**

Home Log Out Preferences Record Help

Welcome, weblogic Connected to: FCUBSDomain

Home > DC\_JMS\_Template-0 > Summary of Server Templates > DC\_JMS\_Template-0 > Summary of Servers > Summary of JMS Modules > JMS\_MODULE > Summary of JMS Modules > MDB\_MODULE

### Create a New JMS System Module Resource

Back Next Finish Cancel

The following properties will be used to target your new JMS system module resource

Use this page to select a subdeployment to assign this system module resource. A subdeployment is a mechanism by which JMS resources are grouped and targeted to a server instance, cluster, or SAF agent. If necessary, you can create a new subdeployment by clicking the **Create a New Subdeployment** button. You can also reconfigure subdeployment targets later by using the parent module's subdeployment management page.

Select the subdeployment you want to use. If you select (none), no targeting will occur.

**Subdeployments:** MDB\_SUB Create a New Subdeployment

What targets do you want to assign to this subdeployment?

**Targets :**

**Servers**

☐ AdminServer

**Clusters**

☒ Cluster-App

☐ All servers in the cluster

**JMS Servers**

☐ JMSServer-1

Back Next Finish Cancel

## 8) Foreign Server is created

**ORACLE WebLogic Server Administration Console 12c**

Home Log Out Preferences Record Help

Welcome, weblogic Connected to: pegjms

Home > Summary of Deployments > Summary of JMS Modules > MDB\_MODULE > Summary of Migratable Targets > Summary of Clusters > Summary of JMS Servers > Summary of JMS Modules > MDB\_MODULE > Summary of JMS Modules > MDB\_MODULE

### Settings for MDB\_MODULE

Configuration Subdeployments Targets Security Notes

This page displays general information about a JMS system module and its resources. It also allows you to configure new resources and access existing resources.

**Name:** MDB\_MODULE The name of this JMS system module. [More Info...](#)

**Descriptor File Name:** jms/mdb\_module-jms.xml The name of the JMS module descriptor file. [More Info...](#)

This page summarizes the JMS resources that have been created for this JMS system module, including queue and topic destinations, connection factories, JMS templates, destination sort keys, destination quota, distributed destinations, foreign servers, and store-and-forward parameters.

[Customize this table](#)

**Summary of Resources**

New Delete Showing 1 to 1 of 1 Previous Next

Name	Type	JNDI Name	Subdeployment	Targets
ForeignServer-1	Foreign Server	N/A	MDB_SUB	Cluster-App

New Delete Showing 1 to 1 of 1 Previous Next

## 6.3 Foreign Server Configuration

1) Click on ForeignServer-1

The screenshot displays the Oracle WebLogic Server Administration Console interface. The left sidebar contains navigation menus for "Change Center", "Domain Structure", "How do I...", and "System Status". The main content area shows the breadcrumb path: Home > Summary of Deployments > Summary of JMS Modules > MDB\_MODULE > Summary of Migratable Targets > Summary of Clusters > Summary of JMS Servers > Summary of JMS Modules > MDB\_MODULE > Summary of JMS Modules > MDB\_MODULE.

**Messages:**

- All changes have been activated. No restarts are necessary.
- The foreign server was created successfully.

**Settings for MDB\_MODULE**

The "Configuration" tab is selected, displaying general information about the JMS system module. It includes fields for Name (MDB\_MODULE) and Descriptor File Name (jms/mdb\_module-jms.xml). Below this, there is a section titled "Customize this table" which leads to the "Summary of Resources" page.

**Summary of Resources**

Name	Type	JNDI Name	Subdeployment	Targets
ForeignServer-1	Foreign Server	N/A	MDB_SUB	Cluster-App

A red arrow points to the "ForeignServer-1" entry in the table.

2) Enter the JNDI URL as Cluster URL(JMS Managed Servers) and Click on Save

**ORACLE** WebLogic Server Administration Console 12c

---

### Change Center

**View changes and restarts**

Click the Lock & Edit button to modify, add or delete items in this domain.

Lock & Edit  
Release Configuration

Home Log Out Preferences Record Help
Welcome, weblogic Connected to: FCUBSDomain

Home > Summary of Clusters > Summary of Server Templates > Summary of Servers > Summary of JMS Modules > MDB\_MODULE > ForeignServer-1 > Summary of Servers > Summary of JMS Modules > MDB\_MODULE > ForeignServer-1

**Messages**

All changes have been activated. No restarts are necessary.

**Settings for ForeignServer-1**

**Configuration** Subdeployment Notes

**General** Destinations Connection Factories

Click the **Lock & Edit** button in the Change Center to modify the settings on this page.

Save

A foreign server represents a JNDI provider that resides outside a WebLogic Server. It contains information that allows WebLogic Server to reach the remote JNDI provider. This way, a number of connection factory and destination objects (queues or topics) can be defined on one JNDI directory. Use this page to configure a foreign server.

<b>Name:</b>	ForeignServer-1	The name of this foreign server. <a href="#">More Info...</a>
<b>JNDI Initial Context Factory:</b>	weblogic.jndi.WLInitialK	The name of the class that must be instantiated to access the JNDI provider. This class name depends on the JNDI provider and the vendor that are being used. <a href="#">More Info...</a>
<b>JNDI Connection URL:</b>	t3://10.184.148.185:7106,10.184.148.189:7107	The URL that WebLogic Server will use to contact the JNDI provider. The syntax of this URL depends on which JNDI provider is being used. For WebLogic JMS, leave this field blank if you are referencing WebLogic JMS objects within the same cluster. <a href="#">More Info...</a>
<b>JNDI Properties Credential:</b>		Any Credentials that must be set for the JNDI provider. These Credentials

### 3) Click on Connection Factories

**ORACLE WebLogic Server Administration Console 12c**

Home Log Out Preferences Record Help

Welcome, weblogic Connected to: pegjms

Home > MDB\_MODULE > Summary of Migratable Targets > Summary of Clusters > Summary of JMS Servers > Summary of JMS Modules > MDB\_MODULE > Summary of JMS Modules > MDB\_MODULE > ForeignServer-1 > Configuration

**Settings for ForeignServer-1**

Configuration Subdeployment Notes

General Destinations **Connection Factories**

A foreign connection factory represents a connection factory that resides on another server, and which is accessible via JNDI. A remote connection factory can be used to refer to another instance of WebLogic Server running in a different cluster or server, or a foreign provider, as long as that provider supports JNDI.

This page summarizes the foreign connection factories that have been created for this domain.

**Customize this table**

**Foreign Connection Factories (Filtered - More Columns Exist)**

New Delete Showing 0 to 0 of 0 Previous | Next

Name	Local JNDI Name	Remote JNDI Name
There are no items to display		

New Delete Showing 0 to 0 of 0 Previous | Next

### 4) Create MDBQCF Connection Factory

**ORACLE WebLogic Server Administration Console 12c**

Home Log Out Preferences Record Help

Welcome, weblogic Connected to: pegjms

Home > MDB\_MODULE > Summary of Migratable Targets > Summary of Clusters > Summary of JMS Servers > Summary of JMS Modules > MDB\_MODULE > Summary of JMS Modules > MDB\_MODULE > ForeignServer-1 > Configuration

**Create a New Foreign JMS Connection Factory**

OK Cancel

**Foreign Connection Factory Properties**

The following properties will be used to identify your new foreign connection factory.

\* Indicates required fields

\* Name: MDBQCF

Local JNDI Name: MDBQCF

Remote JNDI Name: MDBQCF

OK Cancel

### 5) Click on Destination

**ORACLE WebLogic Server Administration Console 12c**

Home Log Out Preferences Record Help

Welcome, weblogic Connected to: pegjms

Home > MDB\_MODULE > Summary of Migratable Targets > Summary of Clusters > Summary of JMS Servers > Summary of JMS Modules > MDB\_MODULE > Summary of JMS Modules > MDB\_MODULE > ForeignServer-1 > Configuration

**Settings for ForeignServer-1**

Configuration Subdeployment Notes

General **Destinations** Connection Factories

A foreign connection factory represents a connection factory that resides on another server, and which is accessible via JNDI. A remote connection factory can be used to refer to another instance of WebLogic Server running in a different cluster or server, or a foreign provider, as long as that provider supports JNDI.

This page summarizes the foreign connection factories that have been created for this domain.

**Customize this table**

**Foreign Connection Factories (Filtered - More Columns Exist)**

New Delete Showing 1 to 1 of 1 Previous | Next

Name	Local JNDI Name	Remote JNDI Name
MDBQCF	MDBQCF	MDBQCF

New Delete Showing 1 to 1 of 1 Previous | Next

## 6) Create MDB\_QUEUE

The screenshot shows the Oracle WebLogic Server Administration Console. On the left, the 'Domain Structure' tree is visible, showing the hierarchy from Environment down to Services > Messaging. The main pane displays the 'Settings for ForeignServer-1' configuration page. The 'Destinations' tab is selected. It contains a table titled 'Foreign Destinations' which is currently empty, showing 'Showing 0 to 0 of 0' items. The page also includes a 'Customize this table' link and a brief explanation of foreign destinations.

This screenshot shows the 'Create a New Foreign JMS Destination' dialog box. The 'Foreign Destination Properties' section is active. The 'Name' field is set to 'MDB\_QUEUE'. The 'Local JNDI Name' and 'Remote JNDI Name' fields are both set to 'MDB\_QUEUE'. The 'OK' button is highlighted with a red box. The background shows the same console interface as the previous screenshot.

## 7) Similarly Create MDB\_QUEUE\_RESPONSE, MDB\_QUEUE\_DLQ

This screenshot shows the 'Create a New Foreign JMS Destination' dialog box, similar to the previous one, but for a different destination. The 'Name' field is set to 'MDB\_QUEUE\_RESPC'. The 'Local JNDI Name' and 'Remote JNDI Name' fields are both set to 'MDB\_QUEUE\_RESPONSE'. The 'OK' button is highlighted with a red box. The background shows the same console interface.

**ORACLE WebLogic Server Administration Console 12c**

Welcome, weblogic Connected to: pegjms

Home > MDB\_MODULE > Summary of Migratable Targets > Summary of Clusters > Summary of JMS Servers > Summary of JMS Modules > MDB\_MODULE > Summary of JMS Modules > MDB\_MODULE > ForeignServer-1 > Configuration

Messages  
All changes have been activated. However 1 items must be restarted for the changes to take effect.

Settings for ForeignServer-1  
Configuration Subdeployment Notes

General Destinations Connection Factories

A foreign destination (topic or queue) can be found on a remote server. When this destination is looked up on the local server, a look-up will be performed automatically on the remote JNDI directory, and the object will be returned from that directory.

This page summarizes the foreign destinations that have been created for this domain.

Customize this table

Foreign Destinations

Name	Local JNDI Name	Remote JNDI Name
MDB_QUEUE	MDB_QUEUE	MDB_QUEUE
MDB_QUEUE_RESPONSE	MDB_QUEUE_RESPONSE	MDB_QUEUE_RESPONSE

Showing 1 to 2 of 2 Previous Next

**ORACLE WebLogic Server Administration Console 12c**

Welcome, weblogic Connected to: pegjms

Home > MDB\_MODULE > Summary of Migratable Targets > Summary of Clusters > Summary of JMS Servers > Summary of JMS Modules > MDB\_MODULE > Summary of JMS Modules > MDB\_MODULE > ForeignServer-1 > Configuration

Create a New Foreign JMS Destination

OK Cancel

Foreign Destination Properties

The following properties will be used to identify your new foreign destination.

\* Indicates required fields

\* Name: MDB\_QUEUE\_DLQ

Local JNDI Name: MDB\_QUEUE\_DLQ

Remote JNDI Name: MDB\_QUEUE\_DLQ

OK Cancel

**ORACLE WebLogic Server Administration Console 12c**

Welcome, weblogic Connected to: pegjms

Home > MDB\_MODULE > Summary of Migratable Targets > Summary of Clusters > Summary of JMS Servers > Summary of JMS Modules > MDB\_MODULE > Summary of JMS Modules > MDB\_MODULE > ForeignServer-1 > Configuration

Messages  
All changes have been activated. However 1 items must be restarted for the changes to take effect.

Settings for ForeignServer-1  
Configuration Subdeployment Notes

General Destinations Connection Factories

A foreign destination (topic or queue) can be found on a remote server. When this destination is looked up on the local server, a look-up will be performed automatically on the remote JNDI directory, and the object will be returned from that directory.

This page summarizes the foreign destinations that have been created for this domain.

Customize this table

Foreign Destinations

Name	Local JNDI Name	Remote JNDI Name
MDB_QUEUE	MDB_QUEUE	MDB_QUEUE
MDB_QUEUE_DLQ	MDB_QUEUE_DLQ	MDB_QUEUE_DLQ
MDB_QUEUE_RESPONSE	MDB_QUEUE_RESPONSE	MDB_QUEUE_RESPONSE

Showing 1 to 3 of 3 Previous Next

8) After all the resources are created, **Restart** the Admin and Managed Servers.

## 7. Application Deployment

### 1) Deploy the EAR with Target as Cluster-App

The screenshot shows the Oracle WebLogic Administration Console interface. On the left is the 'Change Center' sidebar with a 'Domain Structure' tree. The main area is titled 'Settings for GWMDB' and has tabs for Overview, Deployment Plan, Configuration, Security, Targets, Control, Testing, Monitoring, and Notes. The 'Targets' tab is active, displaying a table of target assignments. The table has columns for Component, Type, and Current Targets. Two components are listed: GWMDB (Enterprise Application) and GW\_MDB\_Bean.jar (EJB). The GWMDB component is assigned the 'Cluster-App' target, while GW\_MDB\_Bean.jar has '(None specified)'. Navigation links like 'Showing 1 to 1 of 1' and 'Previous | Next' are present at the bottom of the table.

**Change Center**  
View changes and restarts  
Configuration editing is enabled. Future changes will automatically be activated as you modify, add or delete items in this domain.

**Domain Structure**

- Environment
  - Servers
  - Clusters
  - Virtual Hosts
  - Migratable Targets
  - Coherence Servers
  - Coherence Clusters
  - Machines
  - Work Managers
  - Startup and Shutdown Classes
- Deployments
- Services
  - Messaging

**How do I...**

- Start and stop a deployed Enterprise application

**Settings for GWMDB**  
Overview | Deployment Plan | Configuration | Security | **Targets** | Control | Testing | Monitoring | Notes

Use this page to specify the WebLogic Server instances and clusters to which you want to deploy this Enterprise application. These settings determine where the application is deployed at server startup time.

**Target Assignments**

Change Targets Showing 1 to 1 of 1 Previous | Next

Component	Type	Current Targets
<input type="checkbox"/> GWMDB	Enterprise Application	Cluster-App
<input type="checkbox"/> GW_MDB_Bean.jar	EJB	(None specified)

Change Targets Showing 1 to 1 of 1 Previous | Next

### 2) Health Should be OK if JMS is configured properly, otherwise Warning will be displayed

Change Center

View changes and restarts

Configuration editing is enabled. Future changes will automatically be activated as you modify, add or delete items in this domain.

Domain Structure

Environment

Deployments

Services

Messaging

JMS Servers

Store-and-Forward Agents

JMS Modules

Path Services

Bridges

Data Sources

Persistent Stores

Foreign JNDI Providers

Work Contexts

How do I...

- Install an Enterprise application
- Configure an Enterprise application
- Update (redeploy) an Enterprise application
- Start and stop a deployed Enterprise application
- Monitor the modules of an Enterprise application

Home Log Out Preferences Record Help

Welcome, weblogic | Connected to: base\_domain

Home > Summary of Environment > Summary of Servers > Summary of Deployments > JMS Modules > MDB\_MODULE > Summary of Environment > Summary of Servers > Summary of Deployments > GWMDB > Summary of Deployments

Summary of Deployments

Control Monitoring

This page displays a list of Java EE applications and stand-alone application modules that have been installed to this domain. Installed applications and modules can be started, stopped, updated (redeployed), or deleted from the domain by first selecting the application name and using the controls on this page.

To install a new application or module for deployment to targets in this domain, click the Install button.

Customize this table

Deployments

Install Update Delete Start Stop

Showing 1 to 5 of 5 Previous Next

	Name	State	Health	Type	Deployment Order
<input type="checkbox"/>	FCUBSApp	Active	OK	Enterprise Application	100
<input type="checkbox"/>	GWEEJB	Active	OK	Enterprise Application	100
<input type="checkbox"/>	GWMDB	Active	OK	Enterprise Application	100
<input type="checkbox"/>	jax-rs(1.1,1.9)	Active		Library	100
<input type="checkbox"/>	SWEJB	Active	OK	Enterprise Application	100

Install Update Delete Start Stop

Showing 1 to 5 of 5 Previous Next

## 8. Frequently Asked Questions

### 8.1 Application and JMS Cluster Deployed on Same Cluster

Application and JMS Module can be deployed on the same cluster. In this document both are on different clusters, however it is possible to deploy on the one cluster. When it is deployed on same cluster then

- 1) Foreign Server Creation is not required
- 2) Targets should be given accordingly during Sub Deployment Creation

### 8.2 Application Shows Warning upon Restart of Managed Servers

Managed Servers Start Order

- 1) Stop all managed servers.
- 2) Start only the JMS Cluster managed servers.
- 3) After these are started then start the App Cluster managed servers.

Even after proper JMS setup when the managed servers are restarted Health of the Application is Warning

The screenshot shows the Oracle WebLogic Server Administration Console. On the left, there is a 'Domain Structure' tree with 'Deployments' selected. Below it, a 'How do I...' section lists various tasks. The main area is titled 'Summary of Deployments' and contains a table of deployments. The table has columns for Name, State, Health, Type, and Deployment Order. The row for 'GWMDB' is highlighted with a red rectangle, showing a 'Warning' health status. The row for 'GWEDB' is also highlighted with a red rectangle, showing a 'Warning' health status. The row for 'GWEDB' is also highlighted with a red rectangle, showing a 'Warning' health status.

Name	State	Health	Type	Deployment Order
FCUBSApp (12.0.3.0)	Active	OK	Enterprise Application	100
GWEDB	Active	OK	Enterprise Application	100
GWMDB	Active	Warning	Enterprise Application	100
JAX-WS (1.1.1.1.1.1)	Active	OK	Library	100
GWEDB	Active	OK	Enterprise Application	100

- 1) Force Stop the Application
- 2) Then Start the Application, this would resolve the Warning and the Health of Deployment is changed to OK.

## 8.3 Securing File Store Data

In order to properly secure file store data, set appropriate directory permissions on all file store directories. If data encryption is required, use appropriate third-party encryption software.

## 8.4 t3s Protocol

To secure the communication with the JMS Server use t3s protocol instead of t3. This is applicable when connecting to the connection factory to send or receive messages and also in the JNDI Connection URL provided in foreign server creation.

NOTE: when using the t3s protocol SSL Listen Port Enabled should be checked in server template and the port number used in the URL should be secure port.

## 8.5 How to Test the Deployment

1) Navigate to Services → JMS Modules → JMS\_MODULE → MDB\_QUEUE → MONITORING

View changes and restarts  
Configuration editing is enabled. Future changes will automatically be activated as you modify, add or delete items in this domain.

Domain Structure

- Environment
  - Servers
  - Clusters
  - Virtual Hosts
  - Migratable Targets
  - Coherence Servers
  - Coherence Clusters
  - Machines
  - Work Managers
  - Startup and Shutdown Classes
- Deployments
- Services
  - Messaging

How do I...

- Manage distributed queue messages
- Configure uniform distributed queues

Settings for MDB\_QUEUE

Configuration Security **Monitoring** Subdeployment Notes

Use this page to view statistics about all of the members of a uniform distributed queue. Click on the individual member destination name in the table below to manage the messages on that destination.

To access the uniform distributed queue's message management page, select the check box next to its name, and then click the **Show Messages** button.

Customize this table

Destinations (Filtered - More Columns Exist)

Name	Consumers Current	Consumers High	Consumers Total
<input type="checkbox"/> JMS_MODULE/JMServer-1@MDB_QUEUE	64	64	64
<input type="checkbox"/> JMS_MODULE/JMServer-2@MDB_QUEUE	64	64	64

Show Messages Showing 1 to 2 of 2 Previous | Next

2) Select any one Server and Click on Show Messages

Configuration editing is enabled. Future changes will automatically be activated as you modify, add or delete items in this domain.

Domain Structure

- Environment
  - Servers
  - Clusters
  - Virtual Hosts
  - Migratable Targets
  - Coherence Servers
  - Coherence Clusters
  - Machines
  - Work Managers
  - Startup and Shutdown Classes
- Deployments
- Services
  - Messaging

How do I...

- Manage queue messages
- Manage distributed queue messages
- Manage topic durable subscribers

System Status

Summary of JMS Messages

This page summarizes the available messages for a stand-alone queue, a distributed queue, or a topic durable subscriber. Use this page to view message details, create new messages, delete selected messages, move messages to another destination, export message contents in XML format to another file, import XML formatted message contents from another file, or drain all the messages from a destination.

Click on a message to view its contents.

Message Selector:

Customize this table

JMS Messages (Filtered - More Columns Exist)

ID	CorId	Time Stamp	State String	JMS Delivery Mode	Message Size
There are no items to display					

New Delete Move Import Export Showing 1 to 0 of 0 Previous | Next

### 3) Click on New and enter the Message in Body and Click on OK

**Change Center**  
View changes and restarts  
Configuration editing is enabled. Future changes will automatically be activated as you modify, add or delete items in this domain.

**Domain Structure**

- Environment
  - Servers
  - Clusters
  - Virtual Hosts
  - Migratable Targets
  - Coherence Servers
  - Coherence Clusters
  - Machines
  - Work Managers
  - Startup and Shutdown Classes
- Deployments
- Services
  - Messaging

**How do I...**

- Manage queue messages
- Manage distributed queue messages
- Manage topic durable subscribers

**System Status**  
Health of Running Servers

Failed (0)
Critical (0)
Overloaded (0)

**Produce JMS Message**  
OK Cancel

**JMS Message**  
The following properties will be used to produce a JMS message.

Type:

Correlation ID:

Expiration:

Priority:

Delivery Mode:

Delivery Time:

Redelivery Limit:

Body:

### 4) Message is Sent

**Change Center**  
View changes and restarts  
Configuration editing is enabled. Future changes will automatically be activated as you modify, add or delete items in this domain.

**Domain Structure**

- Environment
  - Servers
  - Clusters
  - Virtual Hosts
  - Migratable Targets
  - Coherence Servers
  - Coherence Clusters
  - Machines
  - Work Managers
  - Startup and Shutdown Classes
- Deployments
- Services
  - Messaging

**How do I...**

- Manage queue messages
- Manage distributed queue messages
- Manage topic durable subscribers

**System Status**  
Health of Running Servers

Failed (0)
Critical (0)
Overloaded (0)

**Summary of JMS Messages**  
Messages  
JMS message sent successfully.

This page summarizes the available messages for a stand-alone queue, a distributed queue, or a topic durable subscriber. Use this page to view message details, create new messages, delete selected messages, move messages to another destination, export message contents in XML format to another file, import XML formatted message contents from another file, or drain all the messages from a destination.

Click on a message to view its contents.

Message Selector:  Apply

[Customize this table](#)

**JMS Messages (Filtered - More Columns Exist)**

ID	CorrId	Time Stamp	State String	JMS Delivery Mode	Message Size
ID:<257876.1411126889162.0>		Fri Sep 19 17:11:29 IST 2014	receive transaction	Persistent	472

### 5) Verify at backend or in the MDB log if the message is processed successfully.

## 8.6 Increase maximum number of message-driven bean threads

Default number of consumers for an MDB is 16. To increase or restrict this number create Custom Work Manager with a Max Threads Constraint in conjunction with MDBs.


The solution is to create a work manager with a max threads constraint and assign the proxy services dispatch policy to this work manager.

Steps to create custom work manager

- 1) Modify the MDB deployment descriptor and redploy the EAR
- 2) Create Custom Workmanager and add constraints to limit the number of the max MDB threads

### 8.6.1 Modify weblogic-ejb-jar.xml

- 1) Add below line to the weblogic-ejb-jar.xml of the MDB Ear  
<dispatch-policy>GWMDBWM</dispatch-policy>



```
<?xml version="1.0" encoding="UTF-8"?>
<weblogic-ejb-jar
  xmlns="http://xmlns.oracle.com/weblogic/weblogic-ejb-jar"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xsi:schemaLocation="http://xmlns.oracle.com/weblogic/weblogic-ejb-jar http://xmlns.oracle
  <weblogic-enterprise-bean>
    <ejb-name>GWMDB</ejb-name>
    <!-- EJB Reference Descriptions STARTS-->
    <!-- EJB Resource Reference Descriptions STARTS-->
    <resource-description>
      <res-ref-name>FLEXTEST.WORLD</res-ref-name>
      <jndi-name>FLEXTEST.WORLD</jndi-name>
    </resource-description>
    <resource-description>
      <res-ref-name>MDBQCF</res-ref-name>
      <jndi-name>MDBQCF</jndi-name>
    </resource-description>
    <!-- EJB Resource Reference Descriptions ENDS-->
    <!-- EJB Resource environment Reference Descriptions STARTS-->
    <resource-env-description>
      <resource-env-ref-name>MDB_QUEUE_RESPONSE</resource-env-ref-name>
      <jndi-name>MDB_QUEUE_RESPONSE</jndi-name>
    </resource-env-description>
    <resource-env-description>
      <resource-env-ref-name>MDB_QUEUE_DLQ</resource-env-ref-name>
      <jndi-name>MDB_QUEUE_DLQ</jndi-name>
    </resource-env-description>
    <resource-env-description>
      <resource-env-ref-name>SW_MDB_QUEUE_RESPONSE</resource-env-ref-name>
      <jndi-name>SW_MDB_QUEUE_RESPONSE</jndi-name>
    </resource-env-description>
    <!-- EJB Resource environment Reference Descriptions ENDS-->
    <!-- EJB Reference Descriptions ENDS -->
    <dispatch-policy>GWMDBWM</dispatch-policy>
  </weblogic-enterprise-bean>
</weblogic-ejb-jar>
```

- 2) Remove if any of the below tags present in weblogic-ejb-jar.xml  
max-beans-in-free-pool and initial-beans-in-free-pool
- 3) Save the ear file and redeploy the EAR file.

## 8.6.2 Work Manager Creation

- 1) Login into weblogic console, navigate to Domain → Environment → WorkManager  
Create new workmanager with the name GWMDBWM(as mentioned in property file) by following below steps

Oracle WebLogic Server Administration Console 12c

Home Log Out Preferences Record Help

Welcome, weblogic Connected to: FCUBSDomain

Home > Summary of Work Managers > MaxThreadsConstraint-0 > Summary of Work Managers > WorkManager-0 > Summary of Work Managers > MaxThreadsConstraint-0 > Summary of Servers > Summary of Environment > Summary of Servers > Summary of Work Managers

### Create a New Work Manager Component

Back Next Finish Cancel

**Select Work Manager Definition type**

What type of Work Manager, Request Class or Constraint do you want to create?

- ☒ **Work Manager**
- ☐ Response Time Request Class
- ☐ Fair Share Request Class
- ☐ Context Request Class
- ☐ Maximum Threads Constraint
- ☐ Minimum Threads Constraint
- ☐ Capacity Constraint

Back Next Finish Cancel

Oracle WebLogic Server Administration Console 12c

Home Log Out Preferences Record Help

Welcome, weblogic Connected to: FCUBSDomain

Home > Summary of Work Managers > MaxThreadsConstraint-0 > Summary of Work Managers > WorkManager-0 > Summary of Work Managers > MaxThreadsConstraint-0 > Summary of Servers > Summary of Environment > Summary of Servers > Summary of Work Managers

### Create a New Work Manager Component

Back Next Finish Cancel

**Work Manager Properties**

The following properties will be used to identify your new Work Manager.

\* Indicates required fields

What would you like to name your new Work Manager?

\* Name: GWMDBWM

Back Next Finish Cancel

Oracle WebLogic Server Administration Console 12c

Home Log Out Preferences Record Help

Welcome, weblogic Connected to: FCUBSDomain

Home > Summary of Work Managers > MaxThreadsConstraint-0 > Summary of Work Managers > WorkManager-0 > Summary of Work Managers > MaxThreadsConstraint-0 > Summary of Servers > Summary of Environment > Summary of Servers > Summary of Work Managers

### Create a New Work Manager Component

Back Next Finish Cancel

**Select deployment targets**

You can target the Work Manager to any of these WebLogic Server instances or Clusters. Select the same targets on which you will deploy applications that reference the Work Manager.

**Available targets :**

Servers	
<input type="checkbox"/>	AdminServer

Clusters	
<input checked="" type="checkbox"/>	Cluster-App
<input type="checkbox"/>	All servers in the cluster
<input type="checkbox"/>	Cluster-JMS
<input type="checkbox"/>	All servers in the cluster

Back Next Finish Cancel

**ORACLE WebLogic Server Administration Console 12c**

Home Log Out Preferences Record Help Welcome, weblogic Connected to: FCUBSDomain

Change Center  
View changes and restarts  
Pending changes exist. They must be activated to take effect.  
[Activate Changes] [Undo All Changes]

Domain Structure  
FCUBSDomain  
Environment  
Servers  
Clusters  
Coherence Clusters  
Machines  
Virtual Hosts  
Work Managers  
Startup and Shutdown Classes  
Deployments  
Services  
Security Realms  
Interoperability  
Diagnostics

How do I...  
Create application-scoped constraints

Home > Summary of Work Managers > MaxThreadsConstraint-0 > Summary of Work Managers > WorkManager-0 > Summary of Work Managers > MaxThreadsConstraint-0 > Summary of Servers > Summary of Environment > Summary of Servers > Summary of Work Managers

Messages  
Work Manager created successfully

Summary of Work Managers

A Work Manager defines a set of request classes and thread constraints that manage work performed by WebLogic Server instances. This page displays the global Work Managers, request classes and thread constraints defined for this domain.

Global Work Managers are defined at the domain level. You can also define application-level and module-level Work Managers.

Customize this table

Global Work Managers, Request Classes and Constraints

Name	Type	Targets
GWMBWM	Work Manager	Cluster-App

Showing 1 to 1 of 1 Previous | Next

2) Create new Max Thread Constraint and in the Count field give the desired thread count

**ORACLE webLogic server Administration Console 12c**

Home Log Out Preferences Record Help Welcome, weblogic Connected to: FCUBSDomain

Change Center  
View changes and restarts  
Pending changes exist. They must be activated to take effect.  
[Activate Changes] [Undo All Changes]

Domain Structure  
FCUBSDomain  
Environment  
Servers  
Clusters  
Coherence Clusters  
Machines  
Virtual Hosts  
Work Managers  
Startup and Shutdown Classes  
Deployments  
Services  
Security Realms  
Interoperability  
Diagnostics

How do I...  
Create application-scoped constraints  
Create application-scoped request classes  
Create application-scoped Work Managers

Home > Summary of Work Managers > MaxThreadsConstraint-0 > Summary of Work Managers > WorkManager-0 > Summary of Work Managers > MaxThreadsConstraint-0 > Summary of Servers > Summary of Environment > Summary of Servers > Summary of Work Managers

Create a New Work Manager Component

Back Next Finish Cancel

Select Work Manager Definition type

What type of Work Manager, Request Class or Constraint do you want to create?

☐ Work Manager  
☐ Response Time Request Class  
☐ Fair Share Request Class  
☐ Context Request Class  
☒ Maximum Threads Constraint  
☐ Minimum Threads Constraint  
☐ Capacity Constraint

Back Next Finish Cancel

**ORACLE webLogic server Administration Console 12c**

Home Log Out Preferences Record Help Welcome, weblogic Connected to: FCUBSDomain

Change Center  
View changes and restarts  
Pending changes exist. They must be activated to take effect.  
[Activate Changes] [Undo All Changes]

Domain Structure  
FCUBSDomain  
Environment  
Servers  
Clusters  
Coherence Clusters  
Machines  
Virtual Hosts  
Work Managers  
Startup and Shutdown Classes  
Deployments  
Services  
Security Realms  
Interoperability  
Diagnostics

How do I...  
Create application-scoped constraints

Home > Summary of Work Managers > MaxThreadsConstraint-0 > Summary of Work Managers > WorkManager-0 > Summary of Work Managers > MaxThreadsConstraint-0 > Summary of Servers > Summary of Environment > Summary of Servers > Summary of Work Managers

Create a New Work Manager Component

Back Next Finish Cancel

Maximum Threads Constraint Properties

The following properties will be used to identify your new Max Threads Request Class.

\* Indicates required fields

What would you like to name the new Maximum Threads Constraint?

\* Name: MaxThreadsConstraint-0

What is the maximum number of concurrent threads to allocate for requests? Enter either a fixed thread count or the name of a Data Source whose size will be used for the constraint.

Count: 25

Data Source:

Back Next Finish Cancel

**Change Center**  
View changes and restarts  
Pending changes exist. They must be activated to take effect.  
[Activate Changes] [Undo All Changes]

**Domain Structure**  
FCUBSDomain  
Environment  
Servers  
Clusters  
Coherence Clusters  
Machines  
Virtual Hosts  
Work Managers  
Startup and Shutdown Classes  
Deployments  
Services  
Security Realms  
Interoperability  
Diagnostics

**How do I...**  
• Create application-scoped constraints  
• Create application-scoped request classes  
• Create application-scoped Work Managers

Home Log Out Preferences Record Help  
Welcome, weblogic Connected to: FCUBSDomain  
Home > Summary of Work Managers > MaxThreadsConstraint-0 > Summary of Work Managers > WorkManager-0 > Summary of Work Managers > MaxThreadsConstraint-0 > Summary of Servers > Summary of Environment > Summary of Servers > Summary of Work Managers

**Create a New Work Manager Component**  
[Back] [Next] [Finish] [Cancel]

**Select deployment targets**  
You can target the Work Manager to any of these WebLogic Server instances or Clusters. Select the same targets on which you will deploy applications that reference the Work Manager.

**Available targets :**

**Servers**  
☐ AdminServer

**Clusters**  
☒ Cluster-App  
All servers in the cluster  
☐ Cluster-JMS  
All servers in the cluster

[Back] [Next] [Finish] [Cancel]

**Change Center**  
View changes and restarts  
Pending changes exist. They must be activated to take effect.  
[Activate Changes] [Undo All Changes]

**Domain Structure**  
FCUBSDomain  
Environment  
Servers  
Clusters  
Coherence Clusters  
Machines  
Virtual Hosts  
Work Managers  
Startup and Shutdown Classes  
Deployments  
Services  
Security Realms  
Interoperability  
Diagnostics

**How do I...**  
• Create application-scoped constraints  
• Create application-scoped request classes  
• Create application-scoped Work Managers

Home Log Out Preferences Record Help  
Welcome, weblogic Connected to: FCUBSDomain  
Home > Summary of Work Managers > MaxThreadsConstraint-0 > Summary of Work Managers > WorkManager-0 > Summary of Work Managers > MaxThreadsConstraint-0 > Summary of Servers > Summary of Environment > Summary of Servers > Summary of Work Managers

**Messages**  
Maximum Threads Constraint created successfully

**Summary of Work Managers**  
A Work Manager defines a set of request classes and thread constraints that manage work performed by WebLogic Server instances. This page displays the global Work Managers, request classes and thread constraints defined for this domain.  
Global Work Managers are defined at the domain level. You can also define application-level and module-level Work Managers.

**Customize this table**

**Global Work Managers, Request Classes and Constraints**  
[New] [Clone] [Delete] Showing 1 to 2 of 2 Previous | Next

Name	Type	Targets
GWMDBWM	Work Manager	Cluster-App
MaxThreadsConstraint-0	Maximum Threads Constraint	Cluster-App

[New] [Clone] [Delete] Showing 1 to 2 of 2 Previous | Next

3) Modify the newly created workmanager and assign the Maximum Thread Constraint that is created in above step.

**View changes and restarts**  
Pending changes exist. They must be activated to take effect.  
[Activate Changes] [Undo All Changes]

**Domain Structure**  
FCUBSDomain  
Environment  
Servers  
Clusters  
Coherence Clusters  
Machines  
Virtual Hosts  
Work Managers  
Startup and Shutdown Classes  
Deployments  
Services  
Security Realms  
Interoperability  
Diagnostics

**How do I...**  
• Create application-scoped constraints  
• Create application-scoped request classes  
• Create application-scoped Work Managers  
• Create global constraints  
• Create global request classes  
• Create global Work Managers

**System States**  
Health of Running Servers

Home > MaxThreadsConstraint-0 > Summary of Work Managers > WorkManager-0 > Summary of Work Managers > MaxThreadsConstraint-0 > Summary of Servers > Summary of Environment > Summary of Servers > Summary of Work Managers > GWMDBWM

**Settings for GWMDBWM**  
[Configuration] [Targets] [Notes]  
[Save]

Use this page to define the request classes and constraints for the selected global Work Manager.

**Name:** (No value specified) The user-specified name of this MBean instance. [More Info...](#)

**Request Class:** (None configured) [New](#) A request class associated with this Work Manager. This may be a FairShareRequestClass, ResponseTimeRequestClass, or a ContentRequestClass. [More Info...](#)

**Minimum Threads Constraint:** (None configured) [New](#) The minimum number of threads allocated to resolve deadlocks. [More Info...](#)

**Maximum Threads Constraint:** (None configured) [New](#) The maximum number of concurrent threads that can be allocated to execute requests. [More Info...](#)

**Capacity Constraint:** (None configured) [New](#) The total number of requests that can be queued or executing before WebLogic Server begins rejecting requests. [More Info...](#)


**Stuck Thread Action:** Use server default behavior Specify how stuck threads should be detected, and what action to take should they occur. [More Info...](#)

**Max Stuck Thread Time:** 0 Time after which a executing thread is declared as stuck. [More Info...](#)

**Stuck Thread Count:** 0 Number of stuck threads after which the WorkManager is shutdown. [More Info...](#)

☒ Resume When Unstuck Whether to resume work manager once the stuck threads were cleared. [More Info...](#)

[Save]



- 4) Restart managed servers and notice the change in the number of consumers for the QUEUE's.

## 8.7 How High Availability is achieved

- 1) Application Server:  
MDB\_MODULE and the GWEJB ear are deployed in a cluster. Cluster has 4 managed servers, if any server goes down then the messages are processed by other managed servers.
- 2) JMS Provider:  
JMS is deployed on 2 managed servers, JMSServer1 and JMSServer2, if any one goes down other will handle the messages.
- 3) FileStore:  
File store is a cluster file system or database where if one node goes down then other will handle the requests.
- 4) DB Server:  
Database is installed in RAC mode where it has more than 1 node, if a node goes down then other nodes will handle messages.

## **8.8 How to setup for Scheduler/Notifications**

The above document can be used for setting up JMS for scheduler/notifications but additional queues and connection factory needs to be created.

## **8.9 What other modules uses JMS Queue's**

JMS is used by following modules, relevant queues and factories needs to be created additionally

- 1) EMS for swift messages
- 2) GI for upload
- 3) ELCM
- 4) BIP

## **8.10 References**

- 1) FCUBS\_12.1\_Weblogic12c\_Middleware\_Practices.doc
- 2) GATEWAY\_Applications\_WL.doc
- 3) Resource\_Creation\_WL.doc



## OBTR JMS Cluster Configuration 12c

[February] [2022]

Version 14.5.4.0.0

Oracle Financial Services Software Limited  
Oracle Park  
Off Western Express Highway  
Goregaon (East)  
Mumbai, Maharashtra 400 063  
India

### Worldwide Inquiries:

Phone: +91 22 6718 3000

Fax: +91 22 6718 3001

<https://www.oracle.com/industries/financial-services/index.html>

Copyright © 2020, 2022 Oracle and/or its affiliates. All rights reserved.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

**U.S. GOVERNMENT END USERS:** Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate failsafe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.