

Deploying Oracle Banking Trade Finance Application on
WebLogic
Oracle Banking Trade Finance
Release 14.5.4.0.0
Part No. F53381-01

[February] [2022]



Table of Contents

- 1. DEPLOYING ORACLE FLEXCUBE ON WEBLOGIC 1-1
 - 1.1 INTRODUCTION 1-1
 - 1.2 BUILDING APPLICATION 1-1
 - 1.2.1 *Building Application in Centralized Mode* 1-1
 - 1.2.2 *Building Application in Decentralized Mode*..... 1-1
 - 1.3 DEPLOYING APPLICATION IN ORACLE WEBLOGIC 1-1
 - 1.3.1 *Deploying Integration Adapter EAR from WebLogic Administration Console* 1-1
 - 1.3.2 *Deploying Dependency Library “Jax-RS”* 1-7
 - 1.3.3 *Deploying FCUBS Application from WebLogic Administration Console* 1-11
 - 1.3.4 *Deploying Gateway/Scheduler Applications from WebLogic Administration Console* 1-19

1. Deploying Oracle FLEXCUBE on WebLogic

1.1 Introduction

This chapter explains the steps to deploy Oracle FLEXCUBE UBS application into Oracle WebLogic application server in centralized and decentralized modes. In centralized mode, branch and host are setup in a single PC. In decentralized mode, branch and host are setup in different PCs.

1.2 Building Application

For building Oracle FLEXCUBE Application in centralized and decentralized modes, refer to the following chapters.

1.2.1 Building Application in Centralized Mode

Refer to the chapter 'Building Application in Centralized Mode'. This includes the following details:

- Creating Property File
- Building Centralized EAR File
- Configuring Plug-ins
- Loading Properties File

1.2.2 Building Application in Decentralized Mode

Refer to the chapter 'Building Application in Decentralized Mode'. This includes the following details:

- Creating Property File
- Building Decentralized EAR File
- Configuring Plug-ins
- Loading Properties File

1.3 Deploying Application in Oracle WebLogic

This section explains the method of deploying Oracle FLEXCUBE Application into Oracle WebLogic application server.


1.3.1 Deploying Integration Adapter EAR from WebLogic Administration Console

To deploy Oracle FLEXCUBE Application from Oracle WebLogic administration console, follow the steps given below.


1. Start the Administrative Console of WebLogic application server. You can start this by entering Oracle WebLogic Admin Console URL in the address bar in an internet browser.

Eg: <http://10.10.10.10:1001/console>

The following screen is displayed:




2. Specify the WebLogic administrator user name and password. Click 'Log In'.



3. You need to deploy an Integration adapter EAR. For e.g. 'OBCLExtAdapter.ear or ExtAdapter.ear'. Go to 'Deployment'.


Click 'Lock & Edit' button to enable the buttons. This action enables the buttons.

7. Click 'Next'. The following screen is displayed.



8. Select the application Adapter EAR from the list.


9. Click 'Next'. Following screen is displayed:



10. Choose the targeting style 'Install this deployment as a library'.


11. Click 'Next'.

12. The following screen is displayed




13. Select the target of the application. You can choose the server 'AdminServer' or 'Managed Server(s)'.

14. Click 'Next'. The following screen is displayed.




15. Check the deployment name.


16. The remaining portion of the screen is shown below:



17. Click 'Finish' button. The following screen is displayed.



18. Click 'Save' button. The message 'Settings updated successfully' is displayed.




19. Click 'Activate Changes' button on the left pane. The message 'All the changes have been activated. No restarts are necessary' is displayed.

1.3.2 Deploying Dependency Library "Jax-RS"

This library must be installed before deploying FCUBSApp.ear. Follow the below steps


1. Start the Administrative Console of WebLogic application server. You can start this by entering Oracle WebLogic Admin Console URL in the address bar in an internet browser.
Eg: <http://10.10.10.10:1001/console>

2. The following screen is displayed:



3. Specify the WebLogic administrator user name and password. Click 'Log In'.

The following screen is displayed:



4. Click install button

ORACLE WebLogic Server Administration Console 12c

Home | Log Out | Preferences | Record | Help | | Welcome, infre | Connected to: STD_PAYMENTS

Change Center

View changes and restarts

No pending changes exist. Click the Release Configuration button to allow others to edit the domain.

Lock & Edit
Release Configuration

Domain Structure

STD_PAYMENTS

- Domain Partitions
- Environment
- Deployments
- Services
- Security Realms
- Interoperability
- Diagnostics

How do I...

- Install an enterprise application
- Configure an enterprise application
- Update (redeploy) an enterprise application
- Monitor the modules of an enterprise application
- Deploy EJB modules
- Install a Web application

System Status

Health of Running Servers

Failed (0)
Critical (0)
Overloaded (0)
Warning (0)
OK (2)

Summary of Deployments

Configuration | Control | Monitoring

This page displays the list of Java EE applications and standalone application modules installed to this domain.

You can update (redeploy) or delete installed applications and modules from the domain by selecting the checkbox next to the application name and then using the controls on this page.

To install a new application or module for deployment to targets in this domain, click **Install**.

Customize this table

Install | Update | Delete

| Name | State | Health | Type | Targets | Scope | Domain Partitions | Deployment Order |
|--|--------|--------|------------------------|----------------------------------|--------|-------------------|------------------|
| <input type="checkbox"/> adf.oracle.businesseditor(1.0.12.2.1.0.0) | Active | | Library | AdminServer_payments, pm_server1 | Global | | 100 |
| <input type="checkbox"/> adf.oracle.domain(1.0.12.2.1.0.0) | Active | | Library | AdminServer_payments, pm_server1 | Global | | 100 |
| <input type="checkbox"/> adf.oracle.domain.webapp(1.0.12.2.1.0.0) | Active | | Library | AdminServer_payments, pm_server1 | Global | | 100 |
| <input type="checkbox"/> coherence-transaction-rar | Active | OK | Resource Adapter | AdminServer_payments, pm_server1 | Global | | 100 |
| <input type="checkbox"/> @DMS Application (12.2.1.0.0) | Active | OK | Web Application | AdminServer_payments, pm_server1 | Global | | 5 |
| <input type="checkbox"/> em | Active | OK | Enterprise Application | AdminServer_payments | Global | | 400 |
| <input type="checkbox"/> emagentsdkimpl_priv_jar(12.4.12.1.0.4.0) | Active | | Library | AdminServer_payments | Global | | 100 |
| <input type="checkbox"/> emagentsdkimpl_jar(12.4.12.1.0.4.0) | Active | | Library | AdminServer_payments | Global | | 100 |
| <input type="checkbox"/> emagentsdk_jar(12.4.12.1.0.4.0) | Active | | Library | AdminServer_payments | Global | | 100 |
| <input type="checkbox"/> emas | Active | | Library | AdminServer_payments | Global | | 100 |
| <input type="checkbox"/> emcore | Active | | Library | AdminServer_payments | Global | | 100 |
| <input type="checkbox"/> emcoreclient_jar | Active | | Library | AdminServer_payments | Global | | 100 |
| <input type="checkbox"/> emcorecommon_jar | Active | | Library | AdminServer_payments | Global | | 100 |
| <input type="checkbox"/> emcoreconsole_jar | Active | | Library | AdminServer_payments | Global | | 100 |
| <input type="checkbox"/> emcoreintadk_jar(11.2.0.1.0.12.1.0.0.0) | Active | | Library | AdminServer_payments | Global | | 100 |
| <input type="checkbox"/> emcorepbc_jar | Active | | Library | AdminServer_payments | Global | | 100 |
| <input type="checkbox"/> emcoresdkimpl_jar(11.2.0.1.0.12.1.0.0.0) | Active | | Library | AdminServer_payments | Global | | 100 |
| <input type="checkbox"/> emcoresdk_jar(11.2.0.1.0.12.1.0.0.0) | Active | | Library | AdminServer_payments | Global | | 100 |
| <input type="checkbox"/> emcore_jar | Active | | Library | AdminServer_payments | Global | | 100 |
| <input type="checkbox"/> em_common(12.4.12.1.0.4.0) | Active | | Library | AdminServer_payments | Global | | 100 |
| <input type="checkbox"/> em_core_spac_polo_jar | Active | | Library | AdminServer_payments | Global | | 100 |

No pending changes exist. Click the Release Configuration button to allow others to edit the domain.

Lock & Edit
Release Configuration

Domain Structure

SOADOM3

- Domain Partitions
- Environment
- Deployments
- Services
 - Messaging
 - Data Sources
 - Persistent Stores
 - Foreign JNDI Providers
 - Work Contexts
 - XML Registries
 - XML Entity Caches
 - JCOM
 - Mail Sessions

How do I...

- Start and stop a deployed enterprise application
- Configure an enterprise application
- Create a deployment plan
- Target an enterprise application to a server instance
- Test the modules in an enterprise application

System Status

Health of Running Servers as of 6:13 PM

Failed (0)
Critical (0)
Overloaded (0)
Warning (0)
OK (2)

Install Application Assistant

Back | Next | Finish | Cancel

Locate deployment to install and prepare for deployment

Select the file path that represents the application root directory, archive file, exploded archive directory, or application module descriptor that you want to install. You can also enter the path of the application directory or file in the Path field.

Note: Only valid file paths are displayed below. If you cannot find your deployment files, Upload your file(s) and/or confirm that your application contains the required deployment descriptors.

Path: /scratch/app/bpm12212/user_projects/domains/SOADOM3/servers/AdminServer/upload/jax-rs-2.0.war/app/jax-rs-2.0.war


Recently Used Paths: /scratch/app/bpm12212/user_projects/domains/SOADOM3/servers/AdminServer/upload/FCUBS.ear/app

Current Location: 10.184.158.197 / scratch / app / bpm12212 / user_projects / domains / SOADOM3 / servers / AdminServer / upload / jax-rs-2.0.war / app


jax-rs-2.0.war

Back | Next | Finish | Cancel


Navigate and select jersey bundle under the path “w\server\common\deployable-libraries\jax-rs-2.0.war” and click next



Select "install this deployment as library", select target server as managed server and click next.



Click finish button



This library must appear in the deployment with Type column as “Library’


Note :- latest Jax-rs version will be jax-rs(2.0,2.22.1.0)

1.3.3 Deploying FCUBS Application from WebLogic Administration Console

To deploy Oracle FLEXCUBE Application from Oracle WebLogic administration console, follow the steps given below.

1. Start the Administrative Console of WebLogic application server. You can start this by entering Oracle WebLogic Admin Console URL in the address bar in an internet browser.
Eg: http://10.10.10.10:1001/console

The following screen is displayed:



2. Specify the WebLogic administrator user name and password. Click ‘Log In’.


The following screen is displayed:

3. You need to deploy an EAR. For e.g. 'FCUBSApp.ear'. Go to 'Deployment'.


Click 'Lock & Edit' button to enable the buttons. This action enables the buttons.

| Name | State | Health | Type | Targets | Scope | Domain Partitions | Deployment Order |
|---|--------|--------|------------------------|----------------------------------|--------|-------------------|------------------|
| self.oracle.businessaddr(1.0,12.2.1.0.0) | Active | | Library | AdminServer_payments, pm_server1 | Global | | 100 |
| self.oracle.domain(1.0,12.2.1.0.0) | Active | | Library | AdminServer_payments, pm_server1 | Global | | 100 |
| self.oracle.domain.webapp(1.0,12.2.1.0.0) | Active | | Library | AdminServer_payments, pm_server1 | Global | | 100 |
| coherence-transaction-var | Active | OK | Resource Adapter | AdminServer_payments, pm_server1 | Global | | 100 |
| DMS Application (12.2.1.0.0) | Active | OK | Web Application | AdminServer_payments, pm_server1 | Global | | 5 |
| em | Active | OK | Enterprise Application | AdminServer_payments | Global | | 400 |
| emagentdimpl_jar(12.4.12.1.0.4.0) | Active | | Library | AdminServer_payments | Global | | 100 |
| emagentdimpl_jar(12.4.12.1.0.4.0) | Active | | Library | AdminServer_payments | Global | | 100 |
| emagentd_jar(12.4.12.1.0.4.0) | Active | | Library | AdminServer_payments | Global | | 100 |
| emas | Active | | Library | AdminServer_payments | Global | | 100 |
| emcore | Active | | Library | AdminServer_payments | Global | | 100 |
| emcoreclient_jar | Active | | Library | AdminServer_payments | Global | | 100 |
| emcorecommon_jar | Active | | Library | AdminServer_payments | Global | | 100 |
| emcoreconsole_jar | Active | | Library | AdminServer_payments | Global | | 100 |
| emcoreintask_jar(11.2.0.1.0,12.1.0.0.0) | Active | | Library | AdminServer_payments | Global | | 100 |
| emcoreimpl_jar | Active | | Library | AdminServer_payments | Global | | 100 |
| emcoreimpl_jar(11.2.0.1.0,12.1.0.0.0) | Active | | Library | AdminServer_payments | Global | | 100 |
| emcoreimpl_jar(11.2.0.1.0,12.1.0.0.0) | Active | | Library | AdminServer_payments | Global | | 100 |
| emcore_jar | Active | | Library | AdminServer_payments | Global | | 100 |
| em_core_common(12.4.12.1.0.4.0) | Active | | Library | AdminServer_payments | Global | | 100 |
| em_core_var | Active | | Library | AdminServer_payments | Global | | 100 |

- Click 'Install' button. The following screen is displayed:




- In order to specify the path/location of the enterprise archive file, click the link 'upload your file(s)'.
- Click 'Next'. The following screen is displayed:




- Specify the EAR file path. You can use the 'Browse' button to locate the file.

8. Click 'Next'. The following screen is displayed.



9. Select the application FCUBS EAR from the list.


10. Click 'Next'. Following screen is displayed:



11. Choose the targeting style 'Install this deployment as an application'.


12. Click 'Next'.

The following screen is displayed




13. Select the target of the application. You can choose the server 'AdminServer' or 'Managed Server(s)'.

14. Click 'Next'. The following screen appears.




15. Check the deployment name.

The remaining portion of the screen is shown below:




16. Check whether the deployment location is accessible or not.

The following screen is displayed.




17. Click 'Finish' button. The following screen is displayed.

Change **Deployment Order** to **400** if the application includes **BPEL plug-in**.




18. Click 'Save' button. The message 'Settings updated successfully' is displayed.




19. Click 'Activate Changes' button on the left pane. The message 'All the changes have been activated. No restarts are necessary' is displayed.

The screen is given below:





Click 'Deployment' on the left pane. Switch to Control tab .The following screen is displayed.



20. Click 'Start' drop-down button and select 'Servicing all requests'.

The following screen is displayed.



21. Click 'Yes'. The following screen is displayed.

This completes the deployment process.

1.3.4 Deploying Gateway/Scheduler Applications from WebLogic Administration Console

To deploy Oracle FLEXCUBE Gateway/Scheduler Application from Oracle WebLogic administration console, follow the steps given below.


1. Launch Administrative Console of WebLogic application server. You can launch this by entering Oracle WebLogic Admin Console URL in the address bar in an internet browser.
Eg: `http://10.10.10.10:1001/console`

22. The following screen is displayed:



23. Specify the WebLogic administrator user name and password. Click 'Log In'.

The following screen is displayed:



24. You need to deploy an EAR. For e.g. 'GWEJB.ear'. Go to 'Deployment'.

Click 'Lock & Edit' button to enable the buttons. This action enables the buttons.

The screenshot shows the Oracle WebLogic Server Administration Console. On the left, the 'Change Center' section has the 'Lock & Edit' button highlighted. Below it, the 'Domain Structure' shows the 'STD_PAYMENTS' domain. The 'How do I...' section lists various tasks. The 'System Status' section shows the health of running servers. The main area is titled 'Summary of Deployments' and contains a table of installed applications and modules.


| Name | State | Health | Type | Targets | Scope | Domain Partitions | Deployment Order |
|---|--------|--------|------------------------|----------------------------------|--------|-------------------|------------------|
| adf.oracle.businesseditor(1.0,12.2.1.0.0) | Active | | Library | AdminServer_payments, pm_server1 | Global | | 100 |
| adf.oracle.domain(1.0,12.2.1.0.0) | Active | | Library | AdminServer_payments, pm_server1 | Global | | 100 |
| adf.oracle.domain.webapp(1.0,12.2.1.0.0) | Active | | Library | AdminServer_payments, pm_server1 | Global | | 100 |
| coherence-transaction-rar | Active | OK | Resource Adapter | AdminServer_payments, pm_server1 | Global | | 100 |
| OH QMS Application (12.2.1.0.0) | Active | OK | Web Application | AdminServer_payments, pm_server1 | Global | | 5 |
| em | Active | OK | Enterprise Application | AdminServer_payments | Global | | 400 |
| emagentbdiimpl.jar(12.4,12.1.0.4.0) | Active | | Library | AdminServer_payments | Global | | 100 |
| emagentbdiimpl.jar(12.4,12.1.0.4.0) | Active | | Library | AdminServer_payments | Global | | 100 |
| emagentbdi.jar(12.4,12.1.0.4.0) | Active | | Library | AdminServer_payments | Global | | 100 |
| emas | Active | | Library | AdminServer_payments | Global | | 100 |
| emcore | Active | | Library | AdminServer_payments | Global | | 100 |
| emcoreclient.jar | Active | | Library | AdminServer_payments | Global | | 100 |
| emcorecommon.jar | Active | | Library | AdminServer_payments | Global | | 100 |
| emcoreconsole.jar | Active | | Library | AdminServer_payments | Global | | 100 |
| emcoretsdb.jar(11.2.0.1.0,12.1.0.0.0) | Active | | Library | AdminServer_payments | Global | | 100 |
| emcoreimpl.jar | Active | | Library | AdminServer_payments | Global | | 100 |
| emcoresdimpl.jar(11.2.0.1.0,12.1.0.0.0) | Active | | Library | AdminServer_payments | Global | | 100 |
| emcoresd.jar(11.2.0.1.0,12.1.0.0.0) | Active | | Library | AdminServer_payments | Global | | 100 |
| emcore.jar | Active | | Library | AdminServer_payments | Global | | 100 |
| em_common(12.4,12.1.0.4.0) | Active | | Library | AdminServer_payments | Global | | 100 |
| em_core_jsp.jar | Active | | Library | AdminServer_payments | Global | | 100 |

25. Click 'Install' button. The following screen is displayed:

The screenshot shows the 'Install Application Assistant' dialog box in the Oracle WebLogic Server Administration Console. The 'Locate deployment to install and prepare for deployment' step is active. The dialog box contains a 'Path' field with the value 'D:\'. Below the path field, there is a list of files and folders in the current location, including '11.0', '9NT1272', 'APPOINT SOFTWARE SOLUTIONS', 'backup', 'bea', 'bea11g', 'bea_100', 'BrnDbgs', 'ClearCase', 'CRC', 'Desktop', and 'Documents and Settings'.


26. In order to specify the path/location of the enterprise archive file, click the link 'upload your file(s)'.

27. Click 'Next'. The following screen is displayed:




28. Specify the EAR file path. You can use the 'Browse' button to locate the file.

29. Click 'Next'. The following screen is displayed:



30. Select the application from the list.


31. Click 'Next'. Following screen is displayed:



32. Choose the targeting style 'Install this deployment as an application'.


33. Click 'Next'.

The following screen is displayed




34. Select the target of the application. You can choose the server 'AdminServer' or 'Managed Server(s)'.

35. Click 'Next'. The following screen is displayed.



36. Check the deployment name.

The remaining portion of the screen is shown below:



Check whether the deployment location is accessible or not. The following screen is displayed.

The screenshot shows the Oracle WebLogic Server Administration Console interface. The main content area is titled "Install Application Assistant" and contains the following information:

- Review your choices and click Finish:** Click Finish to complete the deployment. This may take a few moments to complete.
- Additional Configuration:** In order to work successfully, this application may require additional configuration. Do you want to review this application's configuration after completing this assistant?
 - Yes, take me to the deployment's configuration screen.
 - No, I will review the configuration later.
- Summary:**
 - Deployment:** /scratch/app/fmw122/Oracle/user_projects/domains/PM122TR2/servers/Admin_PM12R2/upload/GWEJB.ear/app/GWEJB.ear
 - Name:** GWEJB
 - Staging Mode:** Use the defaults defined by the chosen targets
 - Plan Staging Mode:** Use the same accessibility as the application
 - Security Model:** DDOnly: Use only roles and policies that are defined in the deployment descriptors.
 - Scope:** Global
- Target Summary:**

| Components | Targets |
|------------|------------------|
| GWEJB.ear | payments_server1 |


37. Click 'Finish' button. The following screen is displayed.

The screenshot shows the Oracle WebLogic Server Administration Console interface. The main content area is titled "Settings for GWEJB(12.2.0.0.0)" and contains the following information:

- Overview:** Deployment Plan | Configuration | Security | Targets | Control | Testing | Monitoring | Notes
- Save:** [Save]
- Use this page to view the general configuration of an enterprise application, such as its name, the physical path to the application files, the associated deployment plan, and so on. The table at the end of the page lists the modules (such as Web applications) contained in the enterprise application. Click on the name of the module to view and update its configuration.**
- Configuration Details:**
 - Name:** GWEJB (The name of this enterprise application. [More Info...](#))
 - Scope:** Global (Specifies if this enterprise application is accessible within the domain, a partition, or a resource template. [More Info...](#))
 - Archive Version:** 12.2.0.0.0 (The archive version, specified from from the manifest or overridden during deployment. [More Info...](#))
 - Path:** /scratch/app/fmw122/Oracle/user_projects/domains/PM122TR2/servers/Admin_PM12R2/upload/GWEJB.ear/app/GWEJB.ear (The path to the source of the deployable unit on the Administration Server. [More Info...](#))
 - Deployment Plan:** (no plan specified) (The path to the deployment plan document on the Administration Server. [More Info...](#))
 - Staging Mode:** (not specified) (Specifies whether a deployment's files are copied from a source on the Administration Server's staging area during application preparation. [More Info...](#))
 - Plan Staging Mode:** (not specified) (Specifies whether an application's deployment plan is copied from a source on the Administration Server's staging area during application preparation. [More Info...](#))
 - Security Model:** DDOnly (The security model that is used to secure a deployed module. [More Info...](#))
 - Deployment Order:** 100 (An integer value that indicates when this unit is deployed, relative to other deployable units during startup. [More Info...](#))
 - Deployment Principal Name:** (A string value that indicates the principal that should be used when deploying the file or arc and stubs. This principal will be used to set the current subject when calling out into interfaces such as ApplicationLifecycleListener. If no principal name is specified, then the arc will be used. [More Info...](#))
- Save:** [Save]
- Modules and Components:** Showing 1 to 1 of 1


| Name |
|--------------------|
| GWEJB (12.2.0.0.0) |
| FCMProcEJB |
| FCMRouterEJB |
| GWEJB |

38. Click 'Save' button. The message 'Settings updated successfully' is displayed.



39. Click 'Activate Changes' button on the left pane. The message 'All the changes have been activated. No restarts are necessary' is displayed.

The screen is given below:



Click 'Deployment' on the left pane. Switch to Control tab. The following screen is displayed.

Summary of Deployments

This page displays the list of Java EE applications and standalone application modules installed to this domain.

You can start and stop applications and modules from the domain by selecting the checkbox next to the application name and then using the controls on this page.

Customize this table

Deployments

| Start | Stop | State | Health | Type | Targets | Scope | Domain Partition |
|-------------------------------------|--------------------------|----------|---------|------------------------|------------------|--------|------------------|
| <input checked="" type="checkbox"/> | <input type="checkbox"/> | Active | OK | Resource Adapter | Admin_PM1TR2 | Global | |
| <input type="checkbox"/> | <input type="checkbox"/> | Active | OK | Web Application | Admin_PM1TR2 | Global | |
| <input type="checkbox"/> | <input type="checkbox"/> | Active | Warning | Enterprise Application | payments_server1 | Global | |
| <input checked="" type="checkbox"/> | <input type="checkbox"/> | Prepared | OK | Enterprise Application | payments_server1 | Global | |
| <input type="checkbox"/> | <input type="checkbox"/> | Active | OK | Web Application | Admin_PM1TR2 | Global | |
| <input type="checkbox"/> | <input type="checkbox"/> | Active | OK | EJB | payments_server1 | Global | |
| <input type="checkbox"/> | <input type="checkbox"/> | Active | OK | Resource Adapter | Admin_PM1TR2 | Global | |

40. Click 'Start' drop-down button and select 'Servicing all requests'.

41. The following screen is displayed.

Start Application Assistant

You have selected the following deployments to be started. Click 'Yes' to continue, or 'No' to cancel.

- GWEIB(12.2.0.0.0)

Yes **No**

42. Click 'Yes'. The following screen is displayed.

ORACLE WebLogic Server Administration Console 12c

Home | Log Out | Preferences | Record | Help

Welcome, infra Connected to: PMS122TR2

Messages

- Start requests have been sent to the selected deployments.

Summary of Deployments

Configuration | Control | Monitoring

This page displays the list of Java EE applications and standalone application modules installed to the domain. You can start and stop applications and modules from the domain by selecting the checkbox next to the application name and then using the controls on this page.

Customize this table

Deployments

| Name | State | Health | Type | Targets | Scope | Domain Partitions |
|---|--------|---------|------------------------|------------------|--------|-------------------|
| <input type="checkbox"/> coherence-transaction-rar | Active | OK | Resource Adapter | Admin_PMS12TR2 | Global | |
| <input type="checkbox"/> OMS Application (12.2.1.0.0) | Active | OK | Web Application | Admin_PMS12TR2 | Global | |
| <input type="checkbox"/> em | Active | OK | Enterprise Application | Admin_PMS12TR2 | Global | |
| <input type="checkbox"/> FCMApp (12.2.0.0.0) | Active | Warning | Enterprise Application | payments_server1 | Global | |
| <input type="checkbox"/> GWESB (12.2.0.0.0) | Active | OK | Enterprise Application | payments_server1 | Global | |
| <input type="checkbox"/> app-test | Active | OK | Web Application | Admin_PMS12TR2 | Global | |
| <input type="checkbox"/> PaymentStub | Active | OK | EJB | payments_server1 | Global | |
| <input type="checkbox"/> state-management-provider-memory-rar | Active | OK | Resource Adapter | Admin_PMS12TR2 | Global | |

Showing 1 to 8 of 8 Previous Next

Showing 1 to 8 of 8 Previous Next

How do I...
 • Configure an enterprise application
 • Start applications and modules
 • Stop applications and modules
 • View the modules of an enterprise application
 • Monitor the modules of an enterprise application

System Status
 Health of Running Servers
 Failed (0)
 Critical (0)
 Overloaded (0)
 Warning (0)
 OK (2)

WebLogic Server Version: 12.2.1.0.0
 Copyright © 1996, 2015, Oracle and/or its affiliates. All rights reserved.
 Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

This completes the deployment process.

1. Repeat the same steps from 1.3.3 for deploying GWWS(gateway webservices),Gateway MDB & Gateway HTTP servlet



Deploying Oracle FLEXCUBE on WebLogic
[February] [2022]

Version 14.5.4.0.0

Oracle Financial Services Software Limited
Oracle Park
Off Western Express Highway
Goregaon (East)
Mumbai, Maharashtra 400 063
India

Worldwide Inquiries:

Phone: +91 22 6718 3000

Fax: +91 22 6718 3001

<https://www.oracle.com/industries/financial-services/index.html>

Copyright © [2007], [2022], Oracle and/or its affiliates. All rights reserved.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate failsafe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.