

FCIS Database Setup
Oracle FLEXCUBE Investor Servicing
Release 14.6.0.0.0
[May] [2022]



Table of Contents

- 1. INSTALLING ORACLE FLEXCUBE DATABASE 1-2
 - 1.1 INTRODUCTION 1-2
 - 1.2 CREATING SCHEMA FROM SHIPMENT MEDIA 1-2
 - 1.2.1 *Loading from Shipment Media*..... 1-2
 - 1.3 LOADING STATIC DATA..... 1-17
 - 1.3.1 *Import Database Installation*..... 1-29

1. Installing Oracle FLEXCUBE Database

1.1 Introduction

Oracle FLEXCUBE database can be installed in one of the following methods.

- From Shipment Media – Load the Shipment Media objects into an empty schema using Installer.
- Import full dump – Import the Oracle FLEXCUBE objects into an empty schema using full dump. This is a manual activity.

These methods are discussed in detail under the following heads.

1.2 Creating Schema from Shipment Media

Under this method, you need to create the schema from the Shipment Media.

1.2.1 Loading from Shipment Media

Database installation includes the provision of details of the schema to connect and the location of the source objects. The objects of the selected modules are compiled as explained below.

Source input for installer for DB setup

Copy the shipment media to a folder in the local system.

Eg: C:\Installer\12.3.0.0.0_Exec\

Note: After copying all the sources from shipment media to a folder in the local system, ensure that the folder containing those has full rights for that user.

It is not mandatory to copy the sources to local system. You may also directly refer the Installer to the shipment media.

Based on the installation type, the below details will identify the list of schemas that needs to be deployed:

1. Installation without PENSION module

The below list of schema types needs to be executed:

- a. SMS
- b. SP
- c. LOB
- d. REPORTS

2. Installation including PENSION module

The below list of schema types needs to be executed:

- a. SMS
- b. SP
- c. LOB
- d. PENSION
- e. REPORTS

3. Pension Standalone module setup

The below list of schema types needs to be executed:

- a. SMS
- b. SP
- c. PENSION

Post the DB setup, it's mandatory to run the Cross Schema Scripts Utility. Refer to [Cross Schema Scripts](#) document under the Utilities folder.

Note:


The installer must be closed and re-launched after each DB operation for a schema.

1.2.1.1 Loading Objects from Shipment Media


The steps to load objects from the Shipment Media are given below:

1. Launch Oracle FLEXCUBE Investor Servicing Installer.

Click 'Next'. The following screen is displayed.



2. Choose 'Oracle FLEXCUBE Investor Servicing'. Click 'Next'. The following screen is displayed:



3. Choose 'Database'.
4. Specify the following details:

Release

Select the release status from the drop-down list. The values are as follows:

- KERNEL
- VN

File Separator Style

Select appropriate file separator style. Ex. Linux or Windows.


Application Server

Specify the application server on which you are installing Oracle FLEXCUBE.

Database Server

Specify the database server on which you are installing Oracle FLEXCUBE. Once you have specified the above details, click 'Next'.

Following screen is shown.



The schema types for Oracle FLEXCUBE Investor Servicing are given below:

- SMS
- SP
- LOB
- PENSION
- REPORTS

For all the above schema types, you need to get the execute permissions for the procedures given below:

- DBMS_CRYPTO
- UTL_MAIL
- CTX_DDL
- UTL_RAW
- CTXSYS
- DBMS_RLS
- UTL_RECOMP
- DBMS_MONITOR
- DBMS_LOCK
- DBMS_AQ
- DBMS_REDACT

For all the above schema types, you need to get the SELECT permissions for the Tables given below:

- GV_\$INSTANCE
- REDACTION_POLICIES
- REDACTION_COLUMNS

5. Select schema type which needs to be deployed and click 'Next'. The following screen is displayed:

Oracle FLEXCUBE Investor Servicing
ORACLE®

Installation Type

FC Home

New Installation
 Patch
 Rolled-up Patch

Provide schema details for patch installation.

Name	Value
Username	FCUBS121
Password	••••••••
Service Name	FC1202WI
IP Address	10.110.110.110
Port	1101
TNS Connect Descriptor	FC1102WI

FC Home is the location where FCIS sources copied from shipment media.

Select the appropriate installation option. Provide schema details for validation in case of patch and rolled up patch installation. For New Installation, schema details are not enabled. Click 'Next'.

Based on the FCHOME chosen, the valid list of deployable units are listed as shown in the next screen:

Oracle FLEXCUBE Investor ServicingORACLE®

Valid Patch List

No	Version	Type	Select
1	14.0.0.0	CONSOLE	<input checked="" type="checkbox"/>


LogBackNextExit

Choose the required set of Main and Patch releases. Click Next.


The Oracle FLEXCUBE Universal installer supports custom installation of Oracle FLEXCUBE in two methods:

- Compile objects and load static data into the database
- Load objects and data by importing data and objects from the import file


Click Next, the below screen will be displayed




6. Select 'Compile Object' under 'Custom Installation' and click 'Next'. The following screen is displayed.



7. Provide Destination directory path as required and click on Next. This directory will be used as a staging directory to copy required files for compilation.



8. Click 'Copy' to start database objects source copy.
9. The Installer will copy the source files from the source directory to the destination directory. The files are taken from this location for compilation.
10. Wait until all the files are copied. Once the copy process is completed, the following screen is displayed:



11. Click Next button, for New Installation following screen is shown:

Name	Value
Username	installer
Password	••••••••
Service Name	testdb
IP Address	10.10.10.10
Port	1000
TNS Connect Descriptor	testdb.world

No. of threads for recompilation

12. Specify the following schema details:

User Name

Specify the user name to access the schema.

Password

Enter the schema password.

Service Name

Provide service name of Database.

TNS Connect Descriptor

Specify a valid connect string that contains the details for database connectivity.

IP Address

Specify the IP address of the system where the database schema is installed.

Port

Specify the port number.

No. of threads for recompilation

Specify the number of threads that would be used to compile the objects. Defaulted to 4, if no value is given.


Once you have entered the details, you can test the database schema connection using 'Test Connection' button.

Note

- If the connection is established, the installer displays a message 'Connection Successful'.
- If there is an error in establishing the connection, the system displays the message 'Invalid DB Credentials'.
- If the TNS entry is not proper, the installer displays the message 'TNS entries are not proper'.

13. After testing the connection successfully, click 'Next'. The following screen is displayed.

On click of 'Next' following screen is shown:



14. This screen displays the parameter details of the database. This is for information purpose. You cannot modify the parameters from this screen.

15. Click 'Next'. The following screen is displayed.

Oracle FLEXCUBE Investor Servicing **ORACLE**

Database Installation
This screen displays the Grants provided to the schema.

S.No	Grant Privilege Required	Grant provided
1	CREATE SESSION	Y
2	CREATE TYPE	Y
3	CREATE TRIGGER	Y
4	CREATE TABLE	Y
5	CREATE DATABASE LINK	Y
6	CREATE LIBRARY	Y
7	CREATE SYNONYM	Y
8	CREATE SEQUENCE	Y

Generate Report

Log Back Next Exit

16. This screen displays the grants provided to the schema. This is for information purpose only. If grant privilege needs to be provided to an item then 'Generate Report' button needs to be clicked.

17. If you click 'Generate Report' button, in the 'Logs' folder, the installer creates an SQL file 'grantScript.sql' containing the script for granting the privileges. You can use this file to get the access.

Note: Only system user can execute the file 'grantScripts.sql' for granting privileges.

18. Click Next, The following screen is displayed.

Oracle FLEXCUBE Investor Servicing **ORACLE**

Database Installation
The screen displays the count of the objects already present in the Database.

S.No.	Object Type	Count	Drop
1	MATERIALIZED VIEW	0	<input type="checkbox"/>
2	TABLE	0	<input type="checkbox"/>
3	PACKAGE	0	<input type="checkbox"/>
4	PROCEDURE	0	<input type="checkbox"/>
5	FUNCTION	0	<input type="checkbox"/>
6	TRIGGER	0	<input type="checkbox"/>
7	VIEW	0	<input type="checkbox"/>

Drop Log Drop Drop All

Log Back Next Exit


19. You can select the objects to be dropped and click 'Drop' button to drop the selected objects. As you drop the objects, the count in this screen is updated. You can drop all the objects at once using 'Drop All' button.

20. Click 'Drop Log' button to view the drop log.

Note: The details of the drop process are logged in a file 'Drop_All.log' in the folder <Destination Folder>/DBLogs.

21. If all the objects do not get dropped at the first time, you can drop them again.

22. Click 'Next' button, the following screen is displayed.




23. On click of Load DDL button, the table, sequences and type objects are getting compiled.

24. Click 'DDL Log' button to view the DDL logs. The log file 'LoadDDL.log' will be available in the destination directory under the folder 'DBLogs'.

Note:

- You can rectify the missing DDL objects and recompile them either manually or by redoing the DDL compilation using Installer.
- Only for SMS setup, on click 'Next' the following screen is displayed. For other schema setup, this screen will be skipped.



25. Specify the following details:

Include Scheduler DDLs

Check this box to include scheduler DDLs. If you do not need to include the scheduler DDLs, leave this field unchecked.


Scheduler DDL Source Path

Specify the location of the 'tables_oracle.sql' folder, which is available in the extracted 'quartz.jar'.

Note: Quartz is an open source job scheduling service. You can use Quartz to create schedules for executing jobs whose tasks are defined as standard Java components. You first need to download the file 'quartz.tar' and extract it to the local machine. In the extracted folder, find the location of the folder 'dbTables' and enter that path in the field 'Scheduler DDL Source Path'. Please refer the release document for version and download url for quartz

26. Click 'Load Scheduler DDLs' to compile the files.

27. Click 'Next'. The following screen is displayed.




28. Click 'Load Objects' button. The installer loads the functions, procedures, views, triggers and packages as per your selection and compiles them.

29. Click 'Objects Log' button to view the log. The log file 'LoadAppObj.log' will be available in the destination directory under the folder 'DBLogs'.

Note: You can rectify the missing objects and recompile them either manually or by redoing the Application object compilation using Installer.

30. The installer loads the DDL and application objects based on the schema type selected.

31. Click 'Next' button, the following screen is displayed. You can view the list of invalid objects in this screen.



32. Click 'Invalid List' button to view the count of invalid objects. The installer creates the file 'InvalidList.txt' in the destination directory under the folder 'DBLogs'.
33. You can use the 'Recompile' button to do a cyclic recompilation. This will reduce the invalid objects count. The Installer allows you to use 'Recompile' button multiple times, in order to reduce the invalid objects count.
34. In case if the invalids still exists, use the recompile option after running the Cross Schema Scripts Utility. Refer to [Cross Schema Scripts](#) document under the Utilities folder.
35. You can view the recompile logs by clicking 'Log' button. The installer creates a file 'recompile.log' in the destination directory under the folder 'DBLogs'.


1.3 Loading Static Data

Once the objects are loaded, you need to insert data into the tables.

This section explains the steps to load static data into the database and the basic setup to be done.


Follow the steps given below:

1. Launch Oracle FLEXCUBE Investor Servicing Installer. The FCHOME related details mentioned in Section 1.2.1.1 (Steps 5 and 6) apply here as well if Installer is launched again.




2. Select 'Load Static Data' and click 'Next'. The following screen is displayed.

3. Click 'Next'. The following screen is displayed.



Provide required destination path and click on Next.



4. Click 'Copy' button. The Installer will copy the source files from the source directory to the destination directory. The files are taken from this location for compilation.

5. Wait until all the files are copied. Once the copy process is completed, click 'Next'.

New Installation

Oracle FLEXCUBE Investor Servicing **ORACLE**

Database Installation
Provide schema details.

Name	Value
Username	
Password	••••••••
Service Name	FCISTEST
IP Address	10.110.100.110.
Port	110.1
TNS Connect Descriptor	FCISTEST

Patch Installation

Oracle FLEXCUBE Investor Servicing **ORACLE**

Database Installation
Provide schema details.

Name	Value
Username	
Password	••••••••
Service Name	FCISTEST
IP Address	10.110.100.110.
Port	110
TNS Connect Descriptor	FCISTEST

6. Specify the following schema details:

User Name

Specify the user name to access the schema.

Password

Enter the schema password.

Service Name

Provide service name of Database.

TNS Connect Descriptor

Specify a valid connect string that contains the details for database connectivity.


IP Address

Specify the IP address of the system where the database schema is installed.

Port


Specify the port number.

1. Once you have entered the details, you can test the database schema connection using 'Test Connection' button.
2. After testing the connection, click 'Next'. The following screen is displayed.




7. This screen displays the parameter details of the database. This is for information purpose. You cannot modify the parameters displayed here.

8. Click 'Next'. The following screen is displayed.




9. This screen displays the grants provided to the schema. If object compilation is required and the privilege is not given, then you can find that out from this screen. This is for information purpose.

Click 'Next', the following screen will be displayed..



10. Click 'Start Pre-Load Process' button. The installer executes the procedures required before beginning static data compilation. All the triggers will be disabled during this process.
11. Click 'Log' button. The installer executes the process log.
12. Once the process is completed, click 'Next'.



13. Click "Load Static Data" to load the static data to schema. You can view the static data log by clicking 'Static Data Log' button.
14. For SMS setup only the below further process of Load Static Data process will be available.
For other schema setup, the Next operation will end the Load Static Data process.
15. Click 'Next'. The following screen is displayed.

Basic Setup Details

Parameters of CSTB_PARAM table in the Database.

S.No.	Param Name	Param value
1	FCUBS_INDIR	/scratch/work_area/DEV/FC1203/O
2	REPROT_TIMESTAMP_FORMAT	HH24:MI:SS
3	EXCEL_IMPORT_XML_SPOOL_A...	/tmp/FCIS121DEV/Debug
4	WORK_AREA	FCIS145INNDLY
5	BPEL_INSTALLED	N
6	FCUBS_INTEGRATION_MODULE	FMGIDNDISTEN
7	REPROT_DATE_FORMAT	DD-Mon-YYYY
8	MAXLOGLINES	1000

Log

Back

Next

Exit

Basic Setup Details

Parameters of CSTB_PARAM table in the Database.

S.No.	Param Name	Param value
8	MAXLOGLINES	1000
9	REAL_DEBUG	Y
10	RELEASE	14.5.1.0.0
11	REPORT_DATE_FORMAT	DD-Mon-YYYY
12	REPORT_TIMESTAMP_FORMAT	HH24:MI:SS
13	INTEGRATION_ENABLED	Y
14	EXCEL_FORMAT	xls
15	BPEL_ENABLED	N

Log

Back

Next

Exit

Oracle FLEXCUBE Investor Servicing		ORACLE
Basic Setup Details		
Parameters of CSTB_PARAM table in the Database.		
S.No.	Param Name	Param value
11	REPORT_DATE_FORMAT	DD-Mon-YYYY
12	REPORT_TIMESTAMP_FORMAT	HH24:MI:SS
13	INTEGRATION_ENABLED	Y
14	EXCEL_FORMAT	xls
15	BPEL_ENABLED	N
16	USERDEBUGMODE	FILE
17	DEBUG_LOG_FILE_SIZE	500
18	FCUBS_OUTDIR	/scratch/work_area/DEV/FC1203/O

Log Back Next Exit

16. Here, you can do the basic maintenances for the table 'CSTB_PARAM'.

Note: The above screen appears only when doing the db setup for a console source but not for a patch source(s).

17. Click 'Next'. The following screen is displayed.

Oracle FLEXCUBE Investor Servicing		ORACLE
Basic Setup Details		
Basic Details for bank and branch		
Bank Code	<input type="text" value="000"/>	
Bank Name	<input type="text" value="City Head Office"/>	
Branch Code	<input type="text" value="000"/>	

Log Back Next Exit

18. Here you can do the basic maintenances for the tables 'STTM_BANK' and 'STTM_BRANCH'.

19. Click 'Next'. The following screen is displayed.

The screenshot shows the Oracle FLEXCUBE Investor Servicing interface. The title bar is red with 'Oracle FLEXCUBE Investor Servicing' on the left and the 'ORACLE' logo on the right. The main content area is titled 'Basic Setup Details' and contains the text: 'Basic details about dates. The Date Format must be yyyy/mm/dd.' Below this text are four input fields: 'Input Date' (2016/09/26), 'Current Business Date' (2016/09/26), 'Previous Business Date' (2016/09/25), and 'Next Business Date' (2016/09/27). At the bottom of the window, there is a grey bar with four buttons: 'Log', 'Back', 'Next', and 'Exit'.

20. Here, you can do the basic maintenances for the table 'STTM_DATES'.

21. Click 'Next'. The following screen is displayed.

The screenshot shows the Oracle FLEXCUBE Investor Servicing interface. The title bar is red with 'Oracle FLEXCUBE Investor Servicing' on the left and the 'ORACLE' logo on the right. The main content area is titled 'Basic Setup Details' and contains the text: 'Currency Details.' Below this text are five input fields: 'Local Currency Code' (USD), 'Local Currency Name' (US Dollar), 'Current Fin Cycle' (2011), 'Current Fin Period' (QT1), and 'ISO Currency Code' (294). The 'Current Fin Cycle' and 'Current Fin Period' fields are dropdown menus. At the bottom of the window, there is a grey bar with four buttons: 'Log', 'Back', 'Next', and 'Exit'.

22. Here, you can do the basic maintenances for the table 'CYTM_CCY_DEFN'.

23. Click 'Next'. The following screen is displayed.

Oracle FLEXCUBE Investor Servicing
ORACLE

Basic Setup Details

User Creation with SMS role for login into the Oracle FLEXCUBE.

External Password

No	User Name	Password or LDAP User name
1	ADMINUSER1	••••••••
2	ADMINUSER2	••••••••

Log
Back
Next
Exit

24. Here you can do the basic maintenances for the table 'SMTB_USER' and 'SMTB_USER_ROLE'.


Password

Specify the password. You can use the following characters in the password:

- Alphabets in uppercase
- Alphabets in lowercase
- Numerals

Note: You cannot use '_' (underscore) in the password.

25. Click 'Next'. The following screen is displayed.




26. Click 'Start Setup' button to compile the entries.
27. This completes the static maintenance and basic setup process.
28. The STTM_HOST_DSN entry is to be done with the DSN Name as FCJSMS000DS for SMS and the same is to be used during datasource creation in weblogic/websphere.


1.3.1 Import Database Installation

Data import is an alternative method to load the static data into the database. This section describes the process of importing data for installation.

1. Launch Oracle FLEXCUBE Investor Servicing Installer.



2. Select 'Import Data' and click 'Next'. The following screen is displayed.



3. Specify the following schema details:

User Name

Specify the user name to access the schema.

Password

Enter the schema password.

Service Name

Provide service name of Database.

TNS Connect Descriptor

Specify a valid connect string that contains the details for database connectivity.


IP Address

Specify the IP address of the system where the database schema is installed.

Port

Specify the port number.

- 4. Once you have entered the details, you can test the database schema connection using 'Test Connection' button.
- 5. After testing the connection, click 'Next'. The following screen is displayed.



6. This screen displays the parameter details of the database. This is for information purpose.

7. Click 'Next'. The following screen is displayed.

Oracle FLEXCUBE Investor Servicing **ORACLE**

Database Installation
This screen displays the Grants provided to the schema.

S.No	Grant Privilege Required	Grant provided
1	CREATE SESSION	Y
2	CREATE TYPE	Y
3	CREATE TRIGGER	Y
4	CREATE TABLE	Y
5	CREATE DATABASE LINK	Y
6	CREATE LIBRARY	Y
7	CREATE SYNONYM	Y
8	CREATE SEQUENCE	Y

8. This screen displays the grants provided to the schema. If object compilation is required and the privilege is not given, then you can find that out from this screen. This is for information purpose.
9. Click 'Next'. The following screen is displayed.

Oracle FLEXCUBE Investor Servicing **ORACLE**

Database Installation
Data Dump Parameters

Include PAR File

PAR File Name

On including PAR File option, you are required to update the PAR File and place it in the physical directory, to the same machine where the Installer is running.

Also mention the PAR File name.

10. Specify the following details:

Include PAR File

Check this box to include the PAR file. If you check this box, you need to specify the PAR file name.

PAR file stands for Parameter File. A PAR file is a text file that contains all valid parameters and their respective values. Maintaining the parameters in text format enables you to modify or reuse them easily.

PAR File Name

If you have checked the box 'Include PAR File', you need to specify the PAR file name here.

11. Once you have specified the above details, click 'Next' button.

12. Specify the Oracle directory name. This is the directory in the server machine where the import file is located.

Click 'Next'. The following screen is displayed

Oracle FLEXCUBE Investor Servicing ORACLE

Database Installation
Data Dump Parameters

Oracle Directory Name

Please ensure that the Oracle Directory name mentioned above is created in the server.
Also, ensure that the physical directory, the Oracle directory is pointing to is also present.

Log Back Next Exit

13. Specify the following details:

Dump File Name

Specify the import file name.

Export Schema Name

Specify the export schema name from which the import file is imported.

Export Schema Tablespace

Specify the export schema tablespace from which the import file is imported.

14. Once you have specified the above details, click 'Next'. The following screen is displayed.

Oracle FLEXCUBE Investor Servicing **ORACLE**

Database Installation
Data Dump Parameters

Dump File Name

Export Schema Name

Export Schema Tablespace

Please ensure that the Dump file name mentioned is present in the Oracle Directory in the server.
For more details refer the log file associated with the dump file present in the baseline area.

Log Back Next Exit

15. Specify the following details:

Import Schema Name

Specify the import schema name to which the import file is loaded.

Import Schema Tablespace

Specify the import schema tablespace to which the import file is loaded.

16. Once you have specified the above details, click 'Next' button. The following screen is displayed.

The screenshot shows the Oracle FLEXCUBE Investor Servicing interface. The title bar is red with the text "Oracle FLEXCUBE Investor Servicing" and the Oracle logo. The main content area is titled "Database Installation" and "Data Dump Parameters". It contains two input fields: "Import Schema Name" with the value "FCTEST" and "Import Schema Tablespace" with the value "FCTEST". Below these fields is a grey box with the text: "Provide the schema name and schema tablespace which has been created to import through Datapump." At the bottom of the screen, there are four buttons: "Log", "Back", "Next", and "Exit".

The screenshot shows the Oracle FLEXCUBE Investor Servicing interface. The title bar is red with the text "Oracle FLEXCUBE Investor Servicing" and the Oracle logo. The main content area is titled "Database Installation" and "Current screen Displays the status of Data Imported." Below this text is a large empty rectangular box. At the bottom of the screen, there are three buttons: "Import Objects", "Import Data", and "Full Import". At the very bottom, there are four buttons: "Log", "Back", "Next", and "Exit".

17. This triggers the import operation. You can optionally import the objects, data or full set by using 'Import Objects', 'Import Data' or 'Full Import' buttons respectively.
18. Click 'Import' button to import the database with the PAR file parameter



Setting up Database
[May] [2022]
Version 14.6.0.0.0

Oracle Financial Services Software Limited
Oracle Park
Off Western Express Highway
Goregaon (East)
Mumbai, Maharashtra 400 063
India

Worldwide Inquiries:
Phone: +91 22 6718 3000
Fax: +91 22 6718 3001
www.oracle.com/financialservices/

Copyright © [2007], [2022], Oracle and/or its affiliates.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software" or "commercial computer software documentation" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate failsafe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.

