

Oracle HTTP Server 11g R1 Configuration  
Oracle FLEXCUBE Investor Servicing  
Release 14.6.0.0.0  
[May] [2022]



---

# Table of Contents

<b>1. PURPOSE .....</b>	<b>4</b>
<b>2. INTRODUCTION TO ORACLE HTTP SERVER (OHS) .....</b>	<b>5</b>
2.1 HTTP LISTENER .....	5
2.2 MODULES (MODS).....	5
<b>3. INSTALLATION OF OHS 11G .....</b>	<b>6</b>
<b>4. CONFIGURE ORACLE HTTP SERVER INFRONT OF WEBLOGIC SERVER .....</b>	<b>14</b>
4.1 FOR WEBLOGIC IN SINGLE INSTANCE.....	14
4.2 FOR WEBLOGIC INSTANCES IN CLUSTER .....	15
<b>5. ENABLE “WEBLOGIC PLUG-IN ENABLED” FLAG IN WEBLOGIC .....</b>	<b>16</b>
<b>6. COMPRESSION RULE SETTING.....</b>	<b>17</b>
6.1 LOADING MOD_DEFLATE.....	17
6.2 CONFIGURING FILE TYPES.....	17
6.3 HTTPD.CONF FILE CHANGES .....	18
<b>7. CONFIGURING SSL FOR ORACLE HTTP SERVER .....</b>	<b>19</b>
7.1 SSL CONFIGURATION FOR INBOUND REQUEST TO ORACLE HTTP SERVER.....	19
7.1.1 Create a new Wallet and import Certificate .....	20
7.1.2 Configuring Wallet in ssl.conf file.....	24
7.2 CONFIGURING SSL BETWEEN ORACLE HTTP SERVER AND ORACLE WEBLOGIC SERVER .....	25
7.2.1 Turn off KeepAliveEnabled .....	25
7.2.2 To enable one-way SSL .....	26
<b>8. STARTING, STOPPING, AND RESTARTING ORACLE HTTP SERVER .....</b>	<b>30</b>
8.1 START .....	30
8.2 STOP.....	30
8.3 RESTART .....	30
<b>9. TEST THE APPLICATION .....</b>	<b>31</b>
<b>10. SERVER LOGS LOCATION.....</b>	<b>32</b>

---

**11. REFERENCES ..... 33**

---

## 1. Purpose

The objective of this document is to explain the installation and configuration of Oracle HTTP Server 11g R1 (11.1.1.9.0). This includes setting up of server details, configuration of compression rules and enabling SSL.

---

## 2. Introduction to Oracle HTTP Server (OHS)

Oracle HTTP Server is the Web server component for Oracle Fusion Middleware. It is based on Apache web server, and includes all base Apache modules and modules developed specifically by Oracle. It provides a HTTP listener for Oracle WebLogic Server and the framework for hosting static pages, dynamic pages, and applications over the Web. Key aspects of Oracle HTTP Server are its technology, its serving of both static and dynamic content and its integration with both Oracle and non-Oracle products.

Oracle HTTP Server consists of several components that run within the same process. These components provide the extensive list of features that Oracle HTTP Server offers when handling client requests.

Following are the major components:

### 2.1 HTTP Listener

Oracle HTTP Server is based on an Apache HTTP listener to serve client requests. An HTTP server listener handles incoming requests and routes them to the appropriate processing utility.

### 2.2 Modules (mods)

Modules extend the basic functionality of Oracle HTTP Server, and support integration between Oracle HTTP Server and other Oracle Fusion Middleware components. There are modules developed specifically by Oracle for Oracle HTTP Server. Ex: mod\_wl\_ohs, mod\_plsql


Oracle HTTP Server also includes the base Apache and third-party modules out-of-the-box. These modules are not developed by Oracle. Ex: mod\_proxy, mod\_perl

### 3. Installation of OHS 11g



Invoke the setup exe to start the installation





Select Skip Software Updates




Select Install and Configure









Select only Oracle HTTP Server





Enter the required OHS instance and component names

The screenshot shows the 'Specify Component Details' window. The title bar reads 'Oracle Fusion Middleware 11g Web Tier Utilities Installation - Step 8 of 13'. The window contains a navigation pane on the left with the following steps: Welcome, Skip Software Updates, Install and Configure, Prerequisite Checks, Installation Location, Security Updates, Configure Components, Specify Component Detail (selected), Configure Ports, Installation Summary, Installation Progress, Configuration Progress, and Installation Complete. The main area has three input fields: 'Instance Home Location' with the value '.WT2/instances/instance1' and a 'Browse' button; 'Instance Name' with the value 'instance1'; and 'OHS Component Name' with the value 'ohs1'. At the bottom, there are buttons for '< Back', 'Next >', 'Finish', and 'Cancel'. An 'Elapsed Time: 4m 18s' indicator is visible in the bottom right corner.

The screenshot shows the 'Configure Ports' window. The title bar reads 'Oracle Fusion Middleware 11g Web Tier Utilities Installation - Step 9 of 13'. The navigation pane on the left is similar to the previous step, but 'Configure Ports' is now selected. The main area has two radio button options: 'Auto Port Configuration' (selected) and 'Specify Ports using Configuration file'. Below the second option, there is an 'File name' field with the value '/home/sachidam/staticports.ini' and a 'Browse' button. A 'View/Edit File' button is also present. At the bottom, there are buttons for '< Back', 'Next >', 'Finish', and 'Cancel'. An 'Elapsed Time: 4m 38s' indicator is visible in the bottom right corner.





This completes the installation of Oracle HTTP Server with <Instance> and <component>. Example: Instance is instance1 and component is ohs1.

If you would like to change the port after the installation (OHS Listen Port) edit `$_ORACLE_INSTANCE/config/OHS/<component_name>/httpd.conf` and change the listen port.

NOTE: This port is for http protocol and not for https.

```
httpd.conf
181
182 #
183 # Listen: Allows you to bind Apache to specific IP addresses and/or
184 # ports, instead of the default. See also the <VirtualHost>
185 # directive.
186 #
187 # Change this to Listen on specific IP addresses as shown below to
188 # prevent Apache from glomming onto all bound IP addresses (0.0.0.0)
189 #
190 # Listen 12.34.56.78:80
191
192 # OHS Listen Port
193 Listen 7777
194
195 #
196 # Dynamic Shared Object (DSO) Support
197 #
198 # To be able to use the functionality of a module which was built as a DSO you
199 # have to place corresponding 'LoadModule' lines at this location so the
200 # directives contained in it are actually available _before_ they are used.
201 # Statically compiled modules (those listed by 'httpd -l') do not need
202 # to be loaded here.
203 #
204 # Example:
205 # LoadModule foo_module "${ORACLE_HOME}/ohs/modules/mod_foo.so"
206
```

---

## 4. Configure Oracle HTTP Server in front of Weblogic Server

In Oracle HTTP Server requests from Oracle HTTP Server to Weblogic server are proxied using mod\_wl\_ohs module. This configuration file needs to be modified to include the Weblogic server and port details.

mod\_wl\_ohs.conf file is located at

```
${ORACLE_INSTANCE}/config/OHS/{COMPONENT_NAME}/mod_wl_ohs.conf
```

Add the below directives to mod\_wl\_ohs.conf file.

### 4.1 For WebLogic in Single Instance

```
<Location /<<context/url>> >  
    SetHandler weblogic-handler  
    WebLogicHost <<server name>>  
    WeblogicPort <<port>>  
</Location>
```

Example:

```
<Location /FCISNeoWeb>  
    SetHandler weblogic-handler  
    WebLogicHost wlserver1  
    WeblogicPort 7707  
</Location>
```

This will forward /FCISNeoWeb from HTTP server to /FCISNeoWeb on WebLogic Server wlserver1: 7707

```

# NOTE : This is a template to configure mod_weblogic.
LoadModule weblogic_module    "${ORACLE_HOME}/ohs/modules/mod_wl_ohs.so"

# This empty block is needed to save mod_wl related configuration from EM to this file when changes are made at the Base Virtual Host Level
<IfModule weblogic_module>
#   WebLogicHost <WEBLOGIC_HOST>
#   WebLogicPort <WEBLOGIC_PORT>
#   Debug ON
#   WLogFile /tmp/weblogic.log
#   MatchExpression *.jsp
</IfModule>

# <Location /weblogic>
#   SetHandler weblogic-handler
#   PathInfix /weblogic
#   ErrorPage http://WEBLOGIC_HOST:WEBLOGIC_PORT/
# </Location>

<Location /FCISNeoWeb>
SetHandler weblogic-handler
WebLogicHost wlsserver1
WebLogicPort 8004
WLogProxySSL ON
SecureProxy ON
SSLSessionCache "/var/snatch/work_area/Software/Weblogic10.3.6/Oracle_WT1/instances/instance1/config/OHS/ohs1/keystores/default"
</Location>

```

## 4.2 For Weblogic Instances in Cluster

<Location /<<context/url>> >

SetHandler weblogic-handler

WebLogicCluster <server1>:<port1>,<server2>:<port2>

</Location>

Example

<Location / FCISNeoWeb >

SetHandler weblogic-handler

WebLogicCluster wlsserver1:7010, wlsserver2:7010

</Location>

This will forward /FCISNeoWeb from HTTP server to /FCISNeoWeb on WebLogic Cluster wlsserver1:7010 and wlsserver2:7010

```

# NOTE : This is a template to configure mod_weblogic.
LoadModule weblogic_module    "${ORACLE_HOME}/ohs/modules/mod_wl_ohs.so"

# This empty block is needed to save mod_wl related configuration from EM to this file when changes are made at the Base Virtual Host Level
<IfModule weblogic_module>
#   WebLogicHost <WEBLOGIC_HOST>
#   WebLogicPort <WEBLOGIC_PORT>
#   Debug ON
#   WLogFile /tmp/weblogic.log
#   MatchExpression *.jsp
</IfModule>

# <Location /weblogic>
#   SetHandler weblogic-handler
#   PathInfix /weblogic
#   ErrorPage http://WEBLOGIC_HOST:WEBLOGIC_PORT/
# </Location>

<Location /FCISNeoWeb>
SetHandler weblogic-handler
WebLogicHost wlsserver1
WebLogicPort 8004
WLogProxySSL ON
SecureProxy ON
SSLSessionCache "/var/snatch/work_area/Software/Weblogic10.3.6/Oracle_WT1/instances/instance1/config/OHS/ohs1/keystores/default"
</Location>

```

---

## 5. Enable “WebLogic Plug-In Enabled” Flag in Weblogic

This flag needs to be enabled in weblogic if it is accessed through proxy plugins. When the WebLogic plugin is enabled, a call to `getRemoteAddr` will return the address of the browser client from the proprietary WL-Proxy-Client-IP header instead of the web server.

- a. Plugin flag at managed server level
  - i. Click on 'Environment' -> 'Servers' -> '<ManagedServer>' -> 'General' -> 'Advanced'
  - ii. Check the 'WebLogic Plug-In Enabled' box.
  - iii. Click 'Save'
  - iv. Restart the Server.
  
- b. Plugin flag at domain level
  - v. Click on <Domain> -> 'Web Applications'
  - vi. Check the 'WebLogic Plug-In Enabled' box.
  - vii. Click 'Save'
  - viii. Restart the server.

---

## 6. Compression Rule Setting

Content compression in Oracle HTTP Server is done using mod\_deflate. This can compress HTML, text or XML files to approx. 20 - 30% of their original sizes, thus saving on server traffic. However, compressing files causes a slightly higher load on the server, but clients' connection times to server is reduced.

### 6.1 Loading mod\_deflate


mod\_deflate is used for compression in OHS and this is installed in Oracle HTTP Server under location

"\${ORACLE\_HOME}/OHS/modules/mod\_deflate.so"

But it might not be loaded.

To load the file add the below directive in mod\_wl\_ohs.conf file

```
LoadModule deflate_module      "${ORACLE_HOME}/OHS/modules/mod_deflate.so"
```



```
mod_wl_ohs.conf
1 # NOTE : This is a template to configure mod_weblogic.
2
3 LoadModule weblogic_module      "${ORACLE_HOME}/ohs/modules/mod_wl_ohs.so"
4 LoadModule deflate_module      "${ORACLE_HOME}/ohs/modules/mod_deflate.so"
5
6 # This empty block is needed to save mod_wl related configuration from EM to this file when chang
7 <IfModule weblogic_module>
8 #     WebLogicHost <WEBLOGIC_HOST>
9 #     WebLogicPort <WEBLOGIC_PORT>
10 #     Debug ON
11 #     WLLogFile /tmp/weblogic.log
12 #     MatchExpression *.jsp
13 </IfModule>
14
15 # <Location /weblogic>
16 #     SetHandler weblogic-handler
17 #     PathTrim /weblogic
18 #     ErrorPage http://WEBLOGIC_HOME:WEBLOGIC_PORT/
19 # </Location>
```

### 6.2 Configuring File Types

mod\_deflate also requires to specify which type files are going to be compressed.

In the LOCATION section of mod\_wl\_ohs.conf file add the below entries.

```
AddOutputFilterByType DEFLATE text/plain
```

```
AddOutputFilterByType DEFLATE text/xml
```

```
AddOutputFilterByType DEFLATE application/xhtml+xml
```

```
AddOutputFilterByType DEFLATE text/css
```

```
AddOutputFilterByType DEFLATE application/xml
```

```
AddOutputFilterByType DEFLATE application/x-javascript
```

```
AddOutputFilterByType DEFLATE text/html
```

```
SetOutputFilter DEFLATE
```

Images are supposed to be in a compressed format, and therefore are bypassed by mod\_deflate.

```

21 <Location /FCJNeoWeb>
22     SetHandler weblogic-handler
23     WebLogicHost wlserver1
24     WebLogicPort 7707
25
26     AddOutputFilterByType DEFLATE text/plain
27     AddOutputFilterByType DEFLATE text/xml
28     AddOutputFilterByType DEFLATE application/xhtml+xml
29     AddOutputFilterByType DEFLATE text/css
30     AddOutputFilterByType DEFLATE application/xml
31     AddOutputFilterByType DEFLATE application/x-javascript
32     AddOutputFilterByType DEFLATE text/html
33     SetOutputFilter DEFLATE

```

### 6.3 httpd.conf File Changes

This is a server configuration file which typically contains directives that affect how the server runs, such as user and group IDs it should use, and location of other files. Cross check the existence of mod\_wl\_ohs.conf include in httpd.conf file.

httpd.conf file is present under location

"\${ORACLE\_INSTANCE}/config/OHS/{COMPONENT\_NAME}/httpd.conf"

In this file cross check for the below entry

```
include "${ORACLE_INSTANCE}/config/OHS/${COMPONENT_NAME}/mod_wl_ohs.conf"
```

If above include entry is not present, then add the above include section.

```

0013 #Directives to setup logging via ODL
0014 OraLogDir "${ORACLE_INSTANCE}/diagnostics/logs/${COMPONENT_TYPE}/${COMPONENT_NAME}"
0015 OraLogMode odl-text
0016 OraLogSeverity WARNING:32
0017 OraLogRotationParams S 10:70
0018
0019
0020 # Set it to On to enable Audit Logs
0021 OraAuditEnable On
0022
0023 # Include the configuration files needed for mod_weblogic
0024 include "${ORACLE_INSTANCE}/config/${COMPONENT_TYPE}/${COMPONENT_NAME}/mod_wl_ohs.conf"
0025
0026 # Include the SSL definitions and Virtual Host container
0027 include "${ORACLE_INSTANCE}/config/${COMPONENT_TYPE}/${COMPONENT_NAME}/ssl.conf"
0028
0029 # Include the admin virtual host (Proxy Virtual Host) related configuration
0030 include "${ORACLE_INSTANCE}/config/${COMPONENT_TYPE}/${COMPONENT_NAME}/admin.conf"
0031
0032 include "moduleconf/*.conf"
0033

```

---

## 7. Configuring SSL for Oracle HTTP Server

Secure Sockets Layer (SSL) is required to run any Web site securely. Secure Sockets Layer (SSL) is an encrypted communication protocol that is designed to securely send messages across the Internet.

Reading of “**SSL\_Configuration on Weblogic**” document provided as part of FCIS installation is recommended before proceeding with further setup.

In Oracle HTTP server, SSL configuration can be done between

- Browser to Oracle HTTP Server (Mandatory)
- Oracle HTTP Server to Oracle Weblogic Server(If required)

### 7.1 SSL Configuration for Inbound Request to Oracle HTTP Server

Perform these tasks to enable and configure SSL between browser and Oracle HTTP Server.


- Obtain a certificate from CA or create a self signed certificate.
- Create an Oracle Wallet which contains the above SSL Certificate. The default wallet that is automatically installed with Oracle HTTP Server is for testing purposes only. The default wallet is located in "\${ORACLE\_INSTANCE}/config/OHS/\${COMPONENT\_NAME}/keystores/default"
- Configuring Wallet in ssl.conf file

### 7.1.1 Create a new Wallet and import Certificate


1. Go to the \Oracle\_WT1\bin\launch.exe, this will launch your wallet manager




2. Click on Create new and then click no option.




3. Enter the wallet password and click on OK, this will create a new wallet.




4. Not it will ask for certificate request creation, Click on NO to proceed




5. Right click on trusted certificates and then import trusted certificate.



6. Browse to the folder where certificate is stored and click on Open



7. Click on Save Wallet button on the left side navigation and save the wallet either to default location("\${ORACLE\_INSTANCE}/config/OHS/\${COMPONENT\_NAME}/keystores/default") or folder of your choice.
8. Click on Wallet tab and enable Auto Login



## 7.1.2 Configuring Wallet in ssl.conf file

In ssl.conf file the newly created wallet need to updated. This file is located under folder

"\${ORACLE\_INSTANCE}/config/OHS/\${COMPONENT\_NAME}/

Change the SSLWallet directive to point to the location of new wallet created.

SSLWallet

"\${ORACLE\_INSTANCE}/config/\${COMPONENT\_TYPE}/\${COMPONENT\_NAME}/keystores/"

```

1  * Disabling cipher suites that are not permitted to negotiate.
2  SSLCipherSuite
3  SSL_RSA_WITH_RC4_128_MD5,SSL_RSA_WITH_RC4_128_SHA,SSL_RSA_WITH_3DES_EDE_CBC_SHA,SSL_RSA_WITH_DES_CBC_SHA,
4  AES_256_CBC_SHA
5
6  # SSL Certificate Revocation List Check
7  # Valid values are On and Off
8  SSLCRLCheck Off
9
10 #Path to the wallet
11 SSLWallet "${ORACLE_INSTANCE}/config/${COMPONENT_TYPE}/${COMPONENT_NAME}/keystores/"
12
13 <FilesMatch "\.(cgi|sh|html|php)$">
14     SSLOptions +StdEnvVars
15 </FilesMatch>
16
17 <Directory "${ORACLE_INSTANCE}/config/${COMPONENT_TYPE}/${COMPONENT_NAME}/cgi-bin">
18     SSLOptions +StdEnvVars
19 </Directory>
20
21 BrowserMatch ".MSIE.*" \
22     nokeepalive ssl-unclean-shutdown \
23     downgrade-1.0 force-response-1.0
24
25 </IfModule>
26 </VirtualHost>
27
28 </IfModule>

```

Change the Listen port number in ssl.conf file to the SSL enabled port, by default the value is 4443

```

1  #####
2  # Oracle HTTP Server mod_oss1 configuration file: ssl.conf      #
3  #####
4
5
6  # OHS Listen Port
7  Listen 4443
8
9  <IfModule oss1_module>
10 ##
11 ##  SSL Global Context
12 ##
13 ##  All SSL configuration in this context applies both to
14 ##  the main server and all SSL-enabled virtual hosts.
15 ##
16
17 #
18 #  Some MIME-types for downloading Certificates and CRLs
19 AddType application/x-x509-ca-cert .crt
20 AddType application/x-pkcs7-crl .crl
21
22 #  Pass Phrase Dialog:

```

## 7.2 Configuring SSL between Oracle HTTP Server and Oracle Weblogic Server

SSL for outbound requests from Oracle HTTP Server are configured in mod\_wl\_ohs.

Refer to “[SSL\\_Configuration on Weblogic](#)” document for weblogic server setting mentioned in below section.

### 7.2.1 Turn off KeepAliveEnabled

The below parameter in mod\_wl\_ohs should be turned off, by default it is on. Add the below directive under LOCATION section of mod\_wl\_ohs file

KeepAliveEnabled OFF

```
5
6     AddOutputFilterByType DEFLATE text/plain
7     AddOutputFilterByType DEFLATE text/xml
8     AddOutputFilterByType DEFLATE application/xhtml+xml
9     AddOutputFilterByType DEFLATE text/css
0     AddOutputFilterByType DEFLATE application/xml
1     AddOutputFilterByType DEFLATE application/x-javascript
2     AddOutputFilterByType DEFLATE text/html
3     SetOutputFilter DEFLATE
4
5     KeepAliveEnabled OFF
6
7     W1SSLWallet "D:\misc\ssl\"
8 </Location>
9
```

## 7.2.2 To enable one-way SSL

1. Generate a custom keystore identity.jks for Weblogic Server containing a certificate.
2. At Identity section in Keystores tab in weblogic Admin Console for server set
  - a. The custom trust store with the identity.jks file location
  - b. The keystore type as JKS
  - c. The passphrase used to created the keystore

Home > base\_domain > Summary of Environment > Summary of Servers > AdminServer

Messages

- ⚠ Changes to your Keystore configuration may require you to update your SSL Configuration. Please review your settings on the SSL tab.
- ✓ All changes have been activated. No restarts are necessary.
- ✓ Settings updated successfully.

Settings for AdminServer

Configuration Protocols Logging Debug Monitoring Control Deployments Services Security Notes

General Cluster Services **Keystores** SSL Federation Services Deployment Migration Tuning Overload Health Monitoring Server Start

Save

Keystores ensure the secure storage and management of private keys and trusted certificate authorities (CAs). This page lets you view and define various keystore configurations to manage the security of message transmissions.

Keystores: Custom Identity and Custom Trust [Change](#) Which configuration rules should be used for Custom Keystores? [More Info...](#)

Identity	
Custom Identity Keystore:	D:\misc\testidentity.jks
Custom Identity Keystore Type:	JKS
Custom Identity Keystore Passphrase:	.....
Confirm Custom Identity Keystore Passphrase:	.....
Trust	
Custom Trust Keystore:	D:\misc\testtrust.jks
Custom Trust Keystore Type:	JKS
Custom Trust Keystore Passphrase:	.....
Confirm Custom Trust Keystore Passphrase:	.....

3. Copy the certificate to Oracle HTTP Server and import the new certificate into OHS wallet as a trusted certificate.
4. Add following new directive in mod\_wl\_ohs.conf to point to the wallet location

```
WISSSLWallet "${ORACLE_INSTANCE}/config/OHS/{COMPONENT_NAME}/keystores/default"
```

5. Change the port in mod\_wl\_ohs file to point to SSL port of Weblogic server.

```
20
21 <Location /FCJNeoWeb>
22     <AuthBasic>
23         WebLogicHost wlsserver1
24         WebLogicPort 443
25
26     AddOutputFilterByType DEFLATE text/plain
27     AddOutputFilterByType DEFLATE text/xml
28     AddOutputFilterByType DEFLATE application/xhtml+xml
29     AddOutputFilterByType DEFLATE text/css
30     AddOutputFilterByType DEFLATE application/xml
31     AddOutputFilterByType DEFLATE application/javascript
32     AddOutputFilterByType DEFLATE text/html
33     SetOutputFilter DEFLATE
34
35     KeepAliveEnabled OFF
36
37     WSSSLWallet "${ORACLE_INSTANCE}/config/OHS/{COMPONENT_NAME}/keystores/"
38 </Location>
39
40
```

Restart both Weblogic Server and Oracle HTTP Server

To enable two-way SSL

- Perform one-way SSL configuration steps
- Generate a new trust store, trust.jks for Weblogic server
- Keystore created for one-way SSL could be used, but it is recommended to create a separate truststore
- Export the user certificate from Oracle HTTP Server wallet, and import it into truststore created above
- At Trust section in Keystores tab in Weblogic Admin Console for the server set

- The custom trust store with the trust.jks file location
- The keystore type as JKS
- The passphrase used to created the keystore

Messages

⚠ Changes to your Keystore configuration may require you to update your SSL Configuration. Please review your settings on the SSL tab.

✔ All changes have been activated. No restarts are necessary.

✔ Settings updated successfully.

Settings for AdminServer

Configuration Protocols Logging Debug Monitoring Control Deployments Services Security Notes

General Cluster Services **Keystores** SSL Federation Services Deployment Migration Tuning Overload Health Monitoring Server Start

Save

Keystores ensure the secure storage and management of private keys and trusted certificate authorities (CAs). This page lets you view and define various keystore o you to manage the security of message transmissions.

**Keystores:** Custom Identity and Custom Trust [Change](#) Which configuration rules should be used for trust keystores? [More Info...](#)

— Identity —

**Custom Identity Keystore:**  The path and file name of the identity keysto

**Custom Identity Keystore Type:**  The type of the keystore. Generally, this is J

**Custom Identity Keystore Passphrase:**  The encrypted custom identity keystore's pat keystore will be opened without a passphras

**Confirm Custom Identity Keystore Passphrase:**

— Trust —

**Custom Trust Keystore:**  The path and file name of the custom trust k

**Custom Trust Keystore Type:**  The type of the keystore. Generally, this is J

**Custom Trust Keystore Passphrase:**  The custom trust keystore's passphrase. If e be opened without a passphrase. [More Inf](#)

**Confirm Custom Trust Keystore Passphrase:**

## 1. Under the SSL tab

Ensure trusted CA is set as from Custom Trust Keystore.

The screenshot shows the Oracle HTTP Server configuration page for AdminServer. The page is titled "Settings for AdminServer" and has a navigation bar with tabs for Configuration, Protocols, Logging, Debug, Monitoring, Control, Deployments, Services, Security, and Notes. The "SSL" tab is selected. Below the navigation bar, there are buttons for "Save" and "Configuration - Services- Tab".

The main content area is titled "Identity and Trust Locations:" and contains several sections:

- Identity**: This section is expanded and contains the following settings:
  - Private Key Location:** from Custom Identity Keystore. The keystore attribute that defines the location of the server's private key. [More Info...](#)
  - Private Key Alias:** selfcert. The keystore attribute that defines the server's private key. [More Info...](#)
  - Private Key Passphrase:** ..... The keystore attribute that defines the server's private key. [More Info...](#)
  - Confirm Private Key Passphrase:** ..... The keystore attribute that defines the server's private key. [More Info...](#)
  - Certificate Location:** from Custom Identity Keystore. The keystore attribute that defines the location of the certificate. [More Info...](#)
- Trust**: This section is collapsed and contains the following setting:
  - Trusted Certificate Authorities:** from Custom Trust Keystore. The keystore attribute that defines the trusted certificate authorities. [More Info...](#)
- Advanced**: This section is collapsed.

## 2. Restart Weblogic Server

---

## 8. Starting, Stopping, and Restarting Oracle HTTP Server

Navigate to the below location in command prompt `${ORACLE_INSTANCE}/bin/` and run below commands

### 8.1 Start

```
opmnctl startproc ias-component={COMPONENT_NAME}
```

Example: `opmnctl startproc ias-component=ohs1`

### 8.2 Stop

```
opmnctl stopproc ias-component={COMPONENT_NAME}
```

Example: `opmnctl stopproc ias-component=ohs1`

### 8.3 Restart

```
opmnctl restartproc ias-component={COMPONENT_NAME}
```

Example: `opmnctl restartproc ias-component=ohs1`

---

## 9. Test the Application

Test the application deployed on Weblogic using Oracle HTTP Server after restarting both the oracle http server and weblogic server

`https://ohs_servername:ohs_https_port/<<context/url>>`

`http://ohs_servername:ohs_http_port/<<context/url>>`

ohs\_servername: server on which OHS is deployed

ohs\_https\_port: port number mentioned against LISTEN directive in SSL.conf file

ohs\_http\_port: port number mentioned against LISTEN directive in httpd.conf file

Example:

`https://localhost:4443/FCJNeoWeb/welcome.jsp`

Or

`http://localhost:7777/FCJNeoWeb/welcome.jsp`

---

## 10. Server Logs Location

Oracle HTTP Server Logs are generated under folder

`${ORACLE_INSTANCE}/diagnostics/logs/OHS/{COMPONENT_NAME}/`

---

## 11. References

SSL\_Configuration.doc for Weblogic provided as part of FCIS installation.

[http://docs.oracle.com/cd/E16764\\_01/web.1111/e10144/under\\_mods.htm](http://docs.oracle.com/cd/E16764_01/web.1111/e10144/under_mods.htm)

[http://docs.oracle.com/cd/E25054\\_01/core.1111/e10105/sslconfig.htm](http://docs.oracle.com/cd/E25054_01/core.1111/e10105/sslconfig.htm)



Oracle\_HTTP\_Server\_Configuration  
[May] [2022]  
Version 14.6.0.0.0

Oracle Financial Services Software Limited  
Oracle Park  
Off Western Express Highway  
Goregaon (East)  
Mumbai, Maharashtra 400 063  
India

Worldwide Inquiries:  
Phone: +91 22 6718 3000  
Fax: +91 22 6718 3001  
[www.oracle.com/financialservices/](http://www.oracle.com/financialservices/)

Copyright © 2007, 2022, Oracle and/or its affiliates.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

**U.S. GOVERNMENT END USERS:** Oracle programs (including any operating system, integrated software, any programs embedded, installed or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software" or "commercial computer software documentation" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate failsafe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.