ISPKS_TR_ADV1      Package

**Extensible   Hook   Details**

Release 14.6.0.0.0

May 2022

**ORACLE**®

Oracle Financial Services Software Limited

Oracle Park

Off Western Express
Highway Goregaon (East)
Mumbai, Maharashtra 400
063 India
Worldwide Inquiries:
Phone: +91 22 6718 3000
Fax: +91 22 6718 3001
www.oracle.com/financialservices/

# Contents

| Parameter | Description |
|---|---|
| Function | FN_GET_RTGS_RECEIVER |
| No of Parameters | 7 |
| Function Call Id | 1 |
| Cluster/Custom Function Name | FN_GET_RTGS_RECEIVER |
| Additional parameters | l_tb_cluster_data |
| Sent to Extensible layer | None |
| Received from Extensible layer | None |
| Hook Description | Hook provided to support changes in fedwire fund service (rtgs) |
| Description | Hook provided to support changes in fedwire fund service (rtgs) All parameters received by kernel function are passed to the cluster hook. Additional parameters passed to cluster hook are mentioned in field "Additional Parameters". The variables mentioned in "Sent to Extensible Layer" field are passed to cluster hook. The variables mentioned in "Received from Extensible Layer" field are reassigned to kernel. |
| Bug No | 18804641 |

| Parameter | Description |
|---|---|
| Function | FN_INSERT |
| No of Parameters | 7 |
| Function Call Id | 1 |
| Cluster/Custom Function Name | FN_INSERT |
| Additional parameters | l_tb_cluster_data |
| Sent to Extensible layer | None |
| Received from Extensible layer | None |
| Hook Description | Hook Provided for a functional capability enhancement to use SWIFT-RUR6 standards for processing financial notifications considering rules of Russian Payment system in order to perform settlements in Russian rubble (RUB). |
| Description | Hook Provided for a functional capability enhancement to use SWIFT-RUR6 standards for processing financial notifications considering rules of Russian Payment system in order to perform settlements in Russian rubble (RUB). All parameters received by kernel function are passed to the cluster hook. Additional parameters passed to cluster hook are mentioned in field "Additional Parameters". The variables mentioned in "Sent to Extensible Layer" field are passed to cluster hook. The variables mentioned in "Received from Extensible Layer" field are reassigned to kernel. |
| Bug No | 20125470 |

ORACLE®

| Parameter | Description |
|---|---|
| Function | FN_MT101 |
| No of Parameters | 4 |
| Function Call Id | 1 |
| Cluster/Custom Function Name | FN_MT101 |
| Additional parameters | l_tb_cluster_data |
| Sent to Extensible layer | None |
| Received from Extensible layer | None |
| Hook Description | Hook Provided |
| Description | Hook Provided<br><br>All parameters received by kernel function are passed to the cluster hook.<br><br>Additional parameters passed to cluster hook are mentioned in field "Additional Parameters".<br><br>The variables mentioned in "Sent to Extensible Layer" field are passed to cluster hook.<br><br>The variables mentioned in "Received from Extensible Layer" field are reassigned to kernel. |
| Bug No | 17861835 |

| Parameter | Description |
|---|---|
| Function | FN_MT102 |
| No of Parameters | 3 |
| Function Call Id | 1 |
| Cluster/Custom Function Name | FN_MT102 |
| Additional parameters | l_tb_cluster_data |
| Sent to Extensible layer | l_Tb_Cluster_Data(l_recvcorr_flag) |
| Received from Extensible layer | l_Tb_Cluster_Data(l_recvcorr_flag) |
| Hook Description | Hook Provided for a functional capability enhancement to use<br>SWIFT-RUR6 standards for processing financial notifications<br>considering rules of Russian Payment system in order to<br>perform settlements |
| Description | Hook Provided for a functional capability enhancement to use<br>SWIFT-RUR6 standards for processing financial notifications<br>considering rules of Russian Payment system in order to<br>perform settlements<br><br>All parameters received by kernel function are passed to the cluster hook.<br><br>Additional parameters passed to cluster hook are mentioned in field "Additional Parameters".<br><br>The variables mentioned in "Sent to Extensible Layer" field are passed to cluster hook.<br><br>The variables mentioned in "Received from Extensible Layer" field are reassigned to kernel. |
| Bug No | 20125470 |

| Parameter | Description |
|---|---|
| Function | FN_MT102 |
| No of Parameters | 3 |

**ORACLE®**

| Function Call Id | 2 |
|---|---|
| Cluster/Custom Function Name | FN_MT102 |
| Additional parameters | l_tb_cluster_data |
| Sent to Extensible layer | None |
| Received from Extensible layer | None |
| Hook Description | Hook Provided for a functional capability enhancement to use SWIFT-RUR6 standards for processing financial notifications considering rules of Russian Payment system in order to perform settlements |
| Description | Hook Provided for a functional capability enhancement to use SWIFT-RUR6 standards for processing financial notifications considering rules of Russian Payment system in order to perform settlements<br><br>  All parameters received by kernel function are passed to the cluster hook.<br>    Additional parameters passed to cluster hook are mentioned in field "Additional Parameters".<br>    The variables mentioned in "Sent to Extensible Layer" field are passed to cluster hook.<br>    The variables mentioned in "Received from Extensible Layer" field are reassigned to kernel. |
| Bug No | 20125470 |

| Parameter | Description |
|---|---|
| Function | FN_MT103 |
| No of Parameters | 4 |
| Function Call Id | 1 |
| Cluster/Custom Function Name | FN_MT103 |
| Additional parameters | l_tb_cluster_data |
| Sent to Extensible layer | l_Tb_Cluster_Data(Module) |
| Received from Extensible layer | None |
| Hook Description | Hook Provided |
| Description | Hook Provided<br><br>  All parameters received by kernel function are passed to the cluster hook.<br>    Additional parameters passed to cluster hook are mentioned in field "Additional Parameters".<br>    The variables mentioned in "Sent to Extensible Layer" field are passed to cluster hook.<br>    The variables mentioned in "Received from Extensible Layer" field are reassigned to kernel. |
| Bug No | 17861835 |

| Parameter | Description |
|---|---|
| Function | FN_MT103 |
| No of Parameters | 4 |
| Function Call Id | 2 |
| Cluster/Custom Function Name | FN_MT103 |
| Additional parameters | l_tb_cluster_data |

ORACLE®

| Sent to Extensible layer | l_Tb_Cluster_Data(l_20_Ref) |
| --- | --- |
| | l_Tb_Cluster_Data(p_Modproc_Rec) |
| | l_Tb_Cluster_Data(l_Fldval) |
| Received from Extensible layer | l_Tb_Cluster_Data(l_Fldval) |
| Hook Description | Hook Provided in ISPKS_ADV1 for Tag 20 Enhancement |
| | For MM module Changes. |
| Description | Hook Provided in ISPKS_ADV1 for Tag 20 Enhancement |
| | For MM module Changes. |
| | All parameters received by kernel function are passed to the cluster hook. |
| | Additional parameters passed to cluster hook are mentioned in field "Additional Parameters". |
| | The variables mentioned in "Sent to Extensible Layer" field are passed to cluster hook. |
| | The variables mentioned in "Received from Extensible Layer" field are reassigned to kernel. |
| Bug No | 17566048 |

| Parameter | Description |
| --- | --- |
| Function | FN_MT103 |
| No of Parameters | 4 |
| Function Call Id | 3 |
| Cluster/Custom Function Name | FN_MT103 |
| Additional parameters | l_tb_cluster_data |
| Sent to Extensible layer | l_Tb_Cluster_Data(l_amt_tag) |
| | l_Tb_Cluster_Data(l_Dcn) |
| | l_Tb_Cluster_Data(l_Fldtag) |
| | l_Tb_Cluster_Data(l_Loopno) |
| | l_Tb_Cluster_Data(l_module) |
| | l_Tb_Cluster_Data(l_Fldval) |
| Received from Extensible layer | l_Tb_Cluster_Data(l_amt_tag) |
| | l_Tb_Cluster_Data(l_Dcn) |
| | l_Tb_Cluster_Data(l_Fldtag) |
| | l_Tb_Cluster_Data(l_Loopno) |
| | l_Tb_Cluster_Data(l_module) |
| | l_Tb_Cluster_Data(l_Fldval) |
| Hook Description | Hook Provided |
| Description | Hook Provided |
| | All parameters received by kernel function are passed to the cluster hook. |
| | Additional parameters passed to cluster hook are mentioned in field "Additional Parameters". |
| | The variables mentioned in "Sent to Extensible Layer" field are passed to cluster hook. |
| | The variables mentioned in "Received from Extensible Layer" field are reassigned to kernel. |
| Bug No | 17472969 |

| Parameter | Description |
| --- | --- |
| Function | FN_MT103 |
| No of Parameters | 4 |
| Function Call Id | 4 |

ORACLE®

| | |
|---|---|
| Cluster/Custom Function Name | FN_MT103 |
| Additional parameters | l_tb_cluster_data |
| Sent to Extensible layer | l_Tb_Cluster_Data(l_amt_tag) |
| | l_Tb_Cluster_Data(l_Dcn) |
| | l_Tb_Cluster_Data(l_Fldtag) |
| | l_Tb_Cluster_Data(l_Loopno) |
| | l_Tb_Cluster_Data(l_module) |
| | l_Tb_Cluster_Data(l_Fldval) |
| Received from Extensible layer | l_Tb_Cluster_Data(l_amt_tag) |
| | l_Tb_Cluster_Data(l_Dcn) |
| | l_Tb_Cluster_Data(l_Fldtag) |
| | l_Tb_Cluster_Data(l_Loopno) |
| | l_Tb_Cluster_Data(l_module) |
| | l_Tb_Cluster_Data(l_Fldval) |
| Hook Description | Hook Provided |
| Description | Hook Provided |
| | All parameters received by kernel function are passed to the cluster hook. |
| | Additional parameters passed to cluster hook are mentioned in field "Additional Parameters". |
| | The variables mentioned in "Sent to Extensible Layer" field are passed to cluster hook. |
| | The variables mentioned in "Received from Extensible Layer" field are reassigned to kernel. |
| Bug No | 17472969 |

| Parameter | Description |
|---|---|
| Function | FN_MT103 |
| No of Parameters | 4 |
| Function Call Id | 5 |
| Cluster/Custom Function Name | FN_MT103 |
| Additional parameters | l_tb_cluster_data |
| Sent to Extensible layer | l_Tb_Cluster_Data(l_amt_tag) |
| | l_Tb_Cluster_Data(l_Dcn) |
| | l_Tb_Cluster_Data(l_Fldtag) |
| | l_Tb_Cluster_Data(l_Loopno) |
| | l_Tb_Cluster_Data(l_module) |
| | l_Tb_Cluster_Data(l_Fldval) |
| Received from Extensible layer | l_Tb_Cluster_Data(l_amt_tag) |
| | l_Tb_Cluster_Data(l_Dcn) |
| | l_Tb_Cluster_Data(l_Fldtag) |
| | l_Tb_Cluster_Data(l_Loopno) |
| | l_Tb_Cluster_Data(l_module) |
| | l_Tb_Cluster_Data(l_Fldval) |
| Hook Description | Hook Provided |

ORACLE®

| Description | Hook Provided |
|---|---|
| | All parameters received by kernel function are passed to the cluster hook. |
| | Additional parameters passed to cluster hook are mentioned in field "Additional Parameters". |
| | The variables mentioned in "Sent to Extensible Layer" field are passed to cluster hook. |
| | The variables mentioned in "Received from Extensible Layer" field are reassigned to kernel. |
| Bug No | 17472969 |

| Parameter | Description |
|---|---|
| Function | FN_MT103 |
| No of Parameters | 4 |
| Function Call Id | 6 |
| Cluster/Custom Function Name | FN_MT103 |
| Additional parameters | l_tb_cluster_data |
| Sent to Extensible layer | l_Tb_Cluster_Data(DCN) |
| | l_Tb_Cluster_Data(AMTTAG) |
| | l_Tb_Cluster_Data(FLDTAG) |
| | l_Tb_Cluster_Data(MODULE) |
| | l_Tb_Cluster_Data(FLD50K) |
| Received from Extensible layer | None |
| Hook Description | Hook Provided |
| Description | Hook Provided |
| | All parameters received by kernel function are passed to the cluster hook. |
| | Additional parameters passed to cluster hook are mentioned in field "Additional Parameters". |
| | The variables mentioned in "Sent to Extensible Layer" field are passed to cluster hook. |
| | The variables mentioned in "Received from Extensible Layer" field are reassigned to kernel. |
| Bug No | 17861835 |

| Parameter | Description |
|---|---|
| Function | FN_MT103 |
| No of Parameters | 4 |
| Function Call Id | 7 |
| Cluster/Custom Function Name | FN_MT103 |
| Additional parameters | l_tb_cluster_data |
| Sent to Extensible layer | l_Tb_Cluster_Data(DCN) |
| | l_Tb_Cluster_Data(AMTTAG) |
| | l_Tb_Cluster_Data(FLDTAG) |
| | l_Tb_Cluster_Data(MODULE) |
| | l_Tb_Cluster_Data(FLD50K) |
| | l_Tb_Cluster_Data(LOOPNO) |
| Received from Extensible layer | None |
| Hook Description | Hook Provided |

ORACLE®

| Description | Hook Provided |
|---|---|
| | All parameters received by kernel function are passed to the cluster hook. |
| | Additional parameters passed to cluster hook are mentioned in field "Additional Parameters". |
| | The variables mentioned in "Sent to Extensible Layer" field are passed to cluster hook. |
| | The variables mentioned in "Received from Extensible Layer" field are reassigned to kernel. |
| Bug No | 17861835 |

| Parameter | Description |
|---|---|
| Function | FN_MT103 |
| No of Parameters | 4 |
| Function Call Id | 8 |
| Cluster/Custom Function Name | FN_MT103 |
| Additional parameters | l_tb_cluster_data |
| Sent to Extensible layer | l_Tb_Cluster_Data(DCN) |
| | l_Tb_Cluster_Data(LOOPNO) |
| | l_Tb_Cluster_Data(AMTTAG) |
| | l_Tb_Cluster_Data(FLDTAG) |
| | l_Tb_Cluster_Data(MODULE) |
| | l_Tb_Cluster_Data(FLD50K) |
| Received from Extensible layer | None |
| Hook Description | Hook Provided |
| Description | Hook Provided |
| | All parameters received by kernel function are passed to the cluster hook. |
| | Additional parameters passed to cluster hook are mentioned in field "Additional Parameters". |
| | The variables mentioned in "Sent to Extensible Layer" field are passed to cluster hook. |
| | The variables mentioned in "Received from Extensible Layer" field are reassigned to kernel. |
| Bug No | 17861835 |

| Parameter | Description |
|---|---|
| Function | FN_MT103 |
| No of Parameters | 4 |
| Function Call Id | 10 |
| Cluster/Custom Function Name | FN_MT103 |
| Additional parameters | l_tb_cluster_data |
| Sent to Extensible layer | l_Tb_Cluster_Data(DCN) |
| | l_Tb_Cluster_Data(LOOPNO) |
| | l_Tb_Cluster_Data(FLDTAG) |
| | l_Tb_Cluster_Data(FLDVAL) |
| | l_Tb_Cluster_Data(l_Final_Receiver) |

**ORACLE**

| Received from Extensible layer | l_Tb_Cluster_Data(DCN) |
| --- | --- |
| | l_Tb_Cluster_Data(LOOPNO) |
| | l_Tb_Cluster_Data(FLDTAG) |
| | l_Tb_Cluster_Data(FLDVAL) |
| | l_Tb_Cluster_Data(l_Final_Receiver) |
| Hook Description | Hook Provided for FEW ADDITIONAL FIELDS. |
| Description | Hook Provided for FEW ADDITIONAL FIELDS. |
| |   All parameters received by kernel function are passed to the cluster hook. |
| |     Additional parameters passed to cluster hook are mentioned in field "Additional Parameters". |
| |     The variables mentioned in "Sent to Extensible Layer" field are passed to cluster hook. |
| |     The variables mentioned in "Received from Extensible Layer" field are reassigned to kernel. |
| Bug No | 18722579 |

| Parameter | Description |
| --- | --- |
| Function | FN_MT103 |
| No of Parameters | 4 |
| Function Call Id | 14 |
| Cluster/Custom Function Name | FN_MT103 |
| Additional parameters | l_tb_cluster_data |
| Sent to Extensible layer | l_Tb_Cluster_Data(32A) |
| Received from Extensible layer | l_Tb_Cluster_Data(32A) |
| Hook Description | Corrected code to display System generated MT202 cover with incomplete message details |
| Description | Corrected code to display System generated MT202 cover |
| | with incomplete message details |
| |   All parameters received by kernel function are passed to the cluster hook. |
| |     Additional parameters passed to cluster hook are mentioned in field "Additional Parameters". |
| |     The variables mentioned in "Sent to Extensible Layer" field are passed to cluster hook. |
| |     The variables mentioned in "Received from Extensible Layer" field are reassigned to kernel. |
| Bug No | 18730087 |

| Parameter | Description |
| --- | --- |
| Function | FN_MT103 |
| No of Parameters | 4 |
| Function Call Id | 15 |
| Cluster/Custom Function Name | FN_MT103 |
| Additional parameters | l_tb_cluster_data |
| Sent to Extensible layer | l_Tb_Cluster_Data(amttag) |
| | l_Tb_Cluster_Data(module) |
| | l_Tb_Cluster_Data(esn) |
| Received from Extensible layer | l_Tb_Cluster_Data(amttag) |
| | l_Tb_Cluster_Data(esn) |

ORACLE®

| Hook Description | Hook Provided so that amount_tag can be stored as part of insertion of data into ISTB_MSGHO and can be used while selecting data from ISTBS_CONTRACT_DETAILS for message generation. |
|---|---|
| Description | Hook Provided so that amount_tag can be stored as part of insertion of data into ISTB_MSGHO and can be used while selecting data from ISTBS_CONTRACT_DETAILS for message generation. All parameters received by kernel function are passed to the cluster hook.    Additional parameters passed to cluster hook are mentioned in field "Additional Parameters".    The variables mentioned in "Sent to Extensible Layer" field are passed to cluster hook.    The variables mentioned in "Received from Extensible Layer" field are reassigned to kernel. |
| Bug No | 18775671 |

| Parameter | Description |
|---|---|
| Function | FN_MT103 |
| No of Parameters | 4 |
| Function Call Id | 16 |
| Cluster/Custom Function Name | FN_MT103 |
| Additional parameters | l_tb_cluster_data |
| Sent to Extensible layer | l_Tb_Cluster_Data(DCN) l_Tb_Cluster_Data(LOOPNO) l_Tb_Cluster_Data(l_Final_Receiver) l_Tb_Cluster_Data(l_Module) |
| Received from Extensible layer | l_Tb_Cluster_Data(LOOPNO) |
| Hook Description | Hook Provided to introduce an extra slash in the 57A of MT103 |
| Description | Hook Provided to introduce an extra slash in the 57A of MT103 All parameters received by kernel function are passed to the cluster hook.    Additional parameters passed to cluster hook are mentioned in field "Additional Parameters".    The variables mentioned in "Sent to Extensible Layer" field are passed to cluster hook.    The variables mentioned in "Received from Extensible Layer" field are reassigned to kernel. |
| Bug No | 19537385 |

| Parameter | Description |
|---|---|
| Function | FN_MT103 |
| No of Parameters | 4 |
| Function Call Id | 17 |
| Cluster/Custom Function Name | FN_MT103 |
| Additional parameters | l_tb_cluster_data |

ORACLE®

| Sent to Extensible layer | l_Tb_Cluster_Data(DCN) |
| --- | --- |
| | l_Tb_Cluster_Data(LOOPNO) |
| | l_Tb_Cluster_Data(L_ORG_MSG_TYPE) |
| | l_Tb_Cluster_Data(l_Module) |
| | l_Tb_Cluster_Data(L_FT.DR_CCY) |
| | l_Tb_Cluster_Data(L_FT.DR_AMOUNT) |
| | l_Tb_Cluster_Data(L_RCVR_CHG_AMT) |
| | l_Tb_Cluster_Data(L_SNDR_CHG_AMT) |
| Received from Extensible layer | l_Tb_Cluster_Data(LOOPNO) |
| Hook Description | Hook Provided to skip the tags 33B and 36 in MT103. |
| Description | Hook Provided to skip the tags 33B and 36 in MT103. |
| | All parameters received by kernel function are passed to the cluster hook. |
| | Additional parameters passed to cluster hook are mentioned in field "Additional Parameters". |
| | The variables mentioned in "Sent to Extensible Layer" field are passed to cluster hook. |
| | The variables mentioned in "Received from Extensible Layer" field are reassigned to kernel. |
| Bug No | 19855568 |

| Parameter | Description |
| --- | --- |
| Function | FN_MT103 |
| No of Parameters | 4 |
| Function Call Id | 18 |
| Cluster/Custom Function Name | FN_MT103 |
| Additional parameters | l_tb_cluster_data |
| Sent to Extensible layer | l_Tb_Cluster_Data(l_Module) |
| | l_Tb_Cluster_Data(l_ft.upload_flag) |
| | l_Tb_Cluster_Data(l_ft.internal_remarks) |
| | l_Tb_Cluster_Data(l_org_msg_type) |
| | l_Tb_Cluster_Data(l_sndr_chg_amt) |
| | l_Tb_Cluster_Data(l_gen_191) |
| | l_Tb_Cluster_Data(l_rcvr_chg_amt) |
| | l_Tb_Cluster_Data(l_esn) |
| | l_Tb_Cluster_Data(l_amt_tag) |
| Received from Extensible layer | None |
| Hook Description | Hook Provided for a functional capability enhancement to use |
| | SWIFT-RUR6 standards for processing financial notifications |
| | considering rules of Russian Payment system in order to |
| | perform settlements |

ORACLE®

| Description | Hook Provided for a functional capability enhancement to use |
|---|---|
| | SWIFT-RUR6 standards for processing financial notifications |
| | considering rules of Russian Payment system in order to |
| | perform settlements |
| | All parameters received by kernel function are passed to the cluster hook. |
| | Additional parameters passed to cluster hook are mentioned in field "Additional Parameters". |
| | The variables mentioned in "Sent to Extensible Layer" field are passed to cluster hook. |
| | The variables mentioned in "Received from Extensible Layer" field are reassigned to kernel. |
| Bug No | 20125470 |

| Parameter | Description |
|---|---|
| Function | FN_MT103 |
| No of Parameters | 4 |
| Function Call Id | 25 |
| Cluster/Custom Function Name | FN_MT103 |
| Additional parameters | l_tb_cluster_data |
| Sent to Extensible layer | l_Tb_Cluster_Data(l_103_user_header) |
| Received from Extensible layer | l_Tb_Cluster_Data(l_103_user_header) |
| Hook Description | Hook Provided to check that if a payment is not through RTGS network |
| | but resulting in Bifurcation then MT202 header should be appended |
| | or populated with the value BIFURCATED in tag 108 |
| Description | Hook Provided to check that if a payment is not through RTGS network |
| | but resulting in Bifurcation then MT202 header should be appended |
| | or populated with the value BIFURCATED in tag 108 |
| | All parameters received by kernel function are passed to the cluster hook. |
| | Additional parameters passed to cluster hook are mentioned in field "Additional Parameters". |
| | The variables mentioned in "Sent to Extensible Layer" field are passed to cluster hook. |
| | The variables mentioned in "Received from Extensible Layer" field are reassigned to kernel. |
| Bug No | 23653428 |

| Parameter | Description |
|---|---|
| Function | FN_MT103 |
| No of Parameters | 4 |
| Function Call Id | 26 |
| Cluster/Custom Function Name | FN_MT103 |
| Additional parameters | l_tb_cluster_data |
| Sent to Extensible layer | l_Tb_Cluster_Data(l_103_user_header) |
| Received from Extensible layer | l_Tb_Cluster_Data(l_103_user_header) |
| Hook Description | Hook Provided to check that if a payment is not through RTGS network |
| | but resulting in Bifurcation then MT202 header should be appended |
| | or populated with the value BIFURCATED in tag 108 |

ORACLE®

| Description | Hook Provided to check that if a payment is not through RTGS network |
|---|---|
| | but resulting in Bifurcation then MT202 header should be appended |
| | or populated with the value BIFURCATED in tag 108 |
| | All parameters received by kernel function are passed to the cluster hook. |
| | Additional parameters passed to cluster hook are mentioned in field "Additional Parameters". |
| | The variables mentioned in "Sent to Extensible Layer" field are passed to cluster hook. |
| | The variables mentioned in "Received from Extensible Layer" field are reassigned to kernel. |
| Bug No | 23653428 |

| Parameter | Description |
|---|---|
| Function | FN_MT103 |
| No of Parameters | 4 |
| Function Call Id | 28 |
| Cluster/Custom Function Name | FN_MT103 |
| Additional parameters | l_tb_cluster_data |
| Sent to Extensible layer | l_Tb_Cluster_Data(l_swift_addr) |
| | l_Tb_Cluster_Data(l_fldval) |
| Received from Extensible layer | l_Tb_Cluster_Data(l_fldval) |
| Hook Description | Hook Provided so that MT103 MESSAGE cab be SENT FOR |
| | PROCESSING IN A PARTICULAR FORM |
| Description | Hook Provided so that MT103 MESSAGE cab be SENT FOR |
| | PROCESSING IN A PARTICULAR FORM |
| | All parameters received by kernel function are passed to the cluster hook. |
| | Additional parameters passed to cluster hook are mentioned in field "Additional Parameters". |
| | The variables mentioned in "Sent to Extensible Layer" field are passed to cluster hook. |
| | The variables mentioned in "Received from Extensible Layer" field are reassigned to kernel. |
| Bug No | 23652458 |

| Parameter | Description |
|---|---|
| Function | FN_MT103 |
| No of Parameters | 0 |
| Function Call Id | 32 |
| Cluster/Custom Function Name | FN_MT103 |
| Additional parameters | |
| Sent to Extensible layer | l_tb_cluster_data('33B'):=l_fldval; |
| Received from Extensible layer | l_Fldval := l_tb_cluster_data('33B'); |
| Hook Description | Hook required in ispks_adv1.fn_mt103 after deriving the field value for :33B: tag.Hook has been provided in function |
| | Fn_Mt103 in package ispks_adv1. |

ORACLE®

| Description | Hook required in ispks_adv1.fn_mt103 after deriving the field value for :33B: tag.Hook has been provided in function Fn_Mt103 in package ispks_adv1. |
|---|---|
| | All parameters received by kernel function are passed to the cluster hook. |
| |    Additional parameters passed to cluster hook are mentioned in field "Additional Parameters". |
| |    The variables mentioned in "Sent to Extensible Layer" field are passed to cluster hook. |
| |    The variables mentioned in "Received from Extensible Layer" field are reassigned to kernel. |
| Bug No | 28204509 |

| Parameter | Description |
|---|---|
| Function | FN_MT103 |
| No of Parameters | 0 |
| Function Call Id | 33 |
| Cluster/Custom Function Name | FN_MT103 |
| Additional parameters | |
| Sent to Extensible layer | l_tb_cluster_data('33B'):=l_fldval; |
| Received from Extensible layer | l_Fldval := l_tb_cluster_data('33B'); |
| Hook Description | Hook required in ispks_adv1.fn_mt103 after deriving the field value for :33B: tag.Hook has been provided in function Fn_Mt103 in package ispks_adv1. |
| Description | Hook required in ispks_adv1.fn_mt103 after deriving the field value for :33B: tag.Hook has been provided in function Fn_Mt103 in package ispks_adv1. |
| | All parameters received by kernel function are passed to the cluster hook. |
| |    Additional parameters passed to cluster hook are mentioned in field "Additional Parameters". |
| |    The variables mentioned in "Sent to Extensible Layer" field are passed to cluster hook. |
| |    The variables mentioned in "Received from Extensible Layer" field are reassigned to kernel. |
| Bug No | 28204509 |

| Parameter | Description |
|---|---|
| Function | FN_MT103 |
| No of Parameters | 0 |
| Function Call Id | 34 |
| Cluster/Custom Function Name | FN_MT103 |
| Additional parameters | |
| Sent to Extensible layer | l_tb_cluster_data('L_OPTION') := l_option; |
| Received from Extensible layer | l_Option := l_tb_cluster_data('L_OPTION'); |
| Hook Description | Inline Hook provided in function fn_mt103 in package Ispks_Adv1. |
| Description | Inline Hook provided in function fn_mt103 in package Ispks_Adv1. |
| | All parameters received by kernel function are passed to the cluster hook. |
| |    Additional parameters passed to cluster hook are mentioned in field "Additional Parameters". |
| |    The variables mentioned in "Sent to Extensible Layer" field are passed to cluster hook. |
| |    The variables mentioned in "Received from Extensible Layer" field are reassigned to kernel. |
| Bug No | 28176176 |

ORACLE®

| Parameter | Description |
|---|---|
| Function | FN_MT103 |
| No of Parameters | 0 |
| Function Call Id | 35 |
| Cluster/Custom Function Name | FN_MT103 |
| Additional parameters | |
| Sent to Extensible layer | l_tb_cluster_data('l_Fldval') := l_Fldval; |
| Received from Extensible layer | l_Fldval := l_tb_cluster_data('l_Fldval'); |
| Hook Description | Hook has been provided in function Fn_Mt103 in package ispks_adv1. |
| Description | Hook has been provided in function Fn_Mt103 in package ispks_adv1.<br><br>  All parameters received by kernel function are passed to the cluster hook.<br><br>    Additional parameters passed to cluster hook are mentioned in field "Additional Parameters".<br><br>    The variables mentioned in "Sent to Extensible Layer" field are passed to cluster hook.<br><br>    The variables mentioned in "Received from Extensible Layer" field are reassigned to kernel. |
| Bug No | 28665028 |

| Parameter | Description |
|---|---|
| Function | FN_MT202 |
| No of Parameters | 4 |
| Function Call Id | 1 |
| Cluster/Custom Function Name | FN_MT202 |
| Additional parameters | l_tb_cluster_data |
| Sent to Extensible layer | l_Tb_Cluster_Data(l_Fldval)<br>l_Tb_Cluster_Data(l_benef_flag) |
| Received from Extensible layer | l_Tb_Cluster_Data(l_Fldval)<br>l_Tb_Cluster_Data(l_benef_flag) |
| Hook Description | Hook Provided for TAG20, 21 ENHANCEMENT FOR MM<br>AND LD MODULES |
| Description | Hook Provided for TAG20, 21 ENHANCEMENT FOR MM<br>AND LD MODULES<br><br>  All parameters received by kernel function are passed to the cluster hook.<br><br>    Additional parameters passed to cluster hook are mentioned in field "Additional Parameters".<br><br>    The variables mentioned in "Sent to Extensible Layer" field are passed to cluster hook.<br><br>    The variables mentioned in "Received from Extensible Layer" field are reassigned to kernel. |
| Bug No | 17566048 |
| | |

| Parameter | Description |
|---|---|
| Function | FN_MT202 |
| No of Parameters | 4 |
| Function Call Id | 3 |
| Cluster/Custom Function Name | FN_MT202 |

ORACLE®

| Additional parameters | l_tb_cluster_data |
|---|---|
| Sent to Extensible layer | l_Tb_Cluster_Data(DCN) |
| | l_Tb_Cluster_Data(FLDTAG) |
| | l_Tb_Cluster_Data(LOOPNO) |
| | l_Tb_Cluster_Data(MODULE) |
| Received from Extensible layer | l_Tb_Cluster_Data(DCN) |
| | l_Tb_Cluster_Data(FLDTAG) |
| | l_Tb_Cluster_Data(LOOPNO) |
| | l_Tb_Cluster_Data(MODULE) |
| Hook Description | Hook Provided so that UAEFTS & QATCH MESSAGING SYSTEMS can have FEW ADDITIONAL FIELDS. |
| Description | Hook Provided so that UAEFTS & QATCH MESSAGING SYSTEMS can have FEW ADDITIONAL FIELDS. All parameters received by kernel function are passed to the cluster hook. Additional parameters passed to cluster hook are mentioned in field "Additional Parameters". The variables mentioned in "Sent to Extensible Layer" field are passed to cluster hook. The variables mentioned in "Received from Extensible Layer" field are reassigned to kernel. |
| Bug No | 18722930 |

| Parameter | Description |
|---|---|
| Function | FN_MT202 |
| No of Parameters | 4 |
| Function Call Id | 4 |
| Cluster/Custom Function Name | FN_MT202 |
| Additional parameters | l_tb_cluster_data |
| Sent to Extensible layer | l_Tb_Cluster_Data(DCN) |
| | l_Tb_Cluster_Data(FLDTAG) |
| | l_Tb_Cluster_Data(LOOPNO) |
| | l_Tb_Cluster_Data(FLDVAL) |
| | l_Tb_Cluster_Data(l_Final_Receiver) |
| | l_Tb_Cluster_Data(p_Is_Msgho_Rec.Acc_With_Instn1) |
| | l_Tb_Cluster_Data(l_Benef_Inst1_For_Cover) |
| | l_Tb_Cluster_Data(Cnt1) |
| | l_Tb_Cluster_Data(L_ACC_WITH_INST) |
| | l_Tb_Cluster_Data(L_INTERMEDIARY) |
| Received from Extensible layer | l_Tb_Cluster_Data(DCN) |
| | l_Tb_Cluster_Data(FLDTAG) |
| | l_Tb_Cluster_Data(LOOPNO) |
| | l_Tb_Cluster_Data(FLDVAL) |
| | l_Tb_Cluster_Data(L_ACC_WITH_INST) |
| | l_Tb_Cluster_Data(L_INTERMEDIARY) |
| Hook Description | Hook Provided so that UAEFTS & QATCH MESSAGING SYSTEMS can have FEW ADDITIONAL FIELDS. |

ORACLE®

| Description | Hook Provided so that UAEFTS & QATCH MESSAGING SYSTEMS can have FEW ADDITIONAL FIELDS. |
|---|---|
| | All parameters received by kernel function are passed to the cluster hook. |
| | Additional parameters passed to cluster hook are mentioned in field "Additional Parameters". |
| | The variables mentioned in "Sent to Extensible Layer" field are passed to cluster hook. |
| | The variables mentioned in "Received from Extensible Layer" field are reassigned to kernel. |
| Bug No | 18722579 |

| Parameter | Description |
|---|---|
| Function | FN_MT202 |
| No of Parameters | 4 |
| Function Call Id | 5 |
| Cluster/Custom Function Name | FN_MT202 |
| Additional parameters | l_tb_cluster_data |
| Sent to Extensible layer | l_Tb_Cluster_Data(DCN) |
| | l_Tb_Cluster_Data(FLDTAG) |
| | l_Tb_Cluster_Data(LOOPNO) |
| | l_Tb_Cluster_Data(MODULE) |
| Received from Extensible layer | l_Tb_Cluster_Data(DCN) |
| | l_Tb_Cluster_Data(FLDTAG) |
| | l_Tb_Cluster_Data(LOOPNO) |
| | l_Tb_Cluster_Data(MODULE) |
| Hook Description | Hook Provided so that UAEFTS & QATCH MESSAGING SYSTEMS can have FEW ADDITIONAL FIELDS. |
| Description | Hook Provided so that UAEFTS & QATCH MESSAGING SYSTEMS can have FEW ADDITIONAL FIELDS. |
| | All parameters received by kernel function are passed to the cluster hook. |
| | Additional parameters passed to cluster hook are mentioned in field "Additional Parameters". |
| | The variables mentioned in "Sent to Extensible Layer" field are passed to cluster hook. |
| | The variables mentioned in "Received from Extensible Layer" field are reassigned to kernel. |
| Bug No | 18722930 |

| Parameter | Description |
|---|---|
| Function | FN_MT202 |
| No of Parameters | 4 |
| Function Call Id | 6 |
| Cluster/Custom Function Name | FN_MT202 |
| Additional parameters | l_tb_cluster_data |
| Sent to Extensible layer | l_Tb_Cluster_Data(DCN) |
| | l_Tb_Cluster_Data(FLDTAG) |
| | l_Tb_Cluster_Data(LOOPNO) |
| | l_Tb_Cluster_Data(FLDVAL) |

**ORACLE**

| Received from Extensible layer | l_Tb_Cluster_Data(DCN) |
| --- | --- |
| | l_Tb_Cluster_Data(FLDTAG) |
| | l_Tb_Cluster_Data(LOOPNO) |
| | l_Tb_Cluster_Data(FLDVAL) |
| Hook Description | Hook Provided so that UAEFTS & QATCH MESSAGING SYSTEMS can have FEW ADDITIONAL FIELDS. |
| Description | Hook Provided so that UAEFTS & QATCH MESSAGING SYSTEMS can have FEW ADDITIONAL FIELDS. All parameters received by kernel function are passed to the cluster hook. Additional parameters passed to cluster hook are mentioned in field "Additional Parameters". The variables mentioned in "Sent to Extensible Layer" field are passed to cluster hook. The variables mentioned in "Received from Extensible Layer" field are reassigned to kernel. |
| Bug No | 18722930 |

| Parameter | Description |
| --- | --- |
| Function | FN_MT202 |
| No of Parameters | 4 |
| Function Call Id | 7 |
| Cluster/Custom Function Name | FN_MT202 |
| Additional parameters | l_tb_cluster_data |
| Sent to Extensible layer | l_Tb_Cluster_Data(32A) |
| Received from Extensible layer | l_Tb_Cluster_Data(32A) |
| Hook Description | Corrected code to display System generated MT202 cover with incomplete message details |
| Description | Corrected code to display System generated MT202 cover with incomplete message details All parameters received by kernel function are passed to the cluster hook. Additional parameters passed to cluster hook are mentioned in field "Additional Parameters". The variables mentioned in "Sent to Extensible Layer" field are passed to cluster hook. The variables mentioned in "Received from Extensible Layer" field are reassigned to kernel. |
| Bug No | 18730087 |

| Parameter | Description |
| --- | --- |
| Function | FN_MT202 |
| No of Parameters | 4 |
| Function Call Id | 8 |
| Cluster/Custom Function Name | FN_MT202 |
| Additional parameters | l_tb_cluster_data |
| Sent to Extensible layer | None |
| Received from Extensible layer | None |

ORACLE®

| Hook Description | Hook Provided for generating new reference number and that should be populated into user reference number during new /copy action for FTDTRONL |
|---|---|
| Description | Hook Provided for generating new reference number and that should be populated into user reference number during new /copy action for FTDTRONL<br><br>All parameters received by kernel function are passed to the cluster hook.<br><br>Additional parameters passed to cluster hook are mentioned in field "Additional Parameters".<br><br>The variables mentioned in "Sent to Extensible Layer" field are passed to cluster hook.<br><br>The variables mentioned in "Received from Extensible Layer" field are reassigned to kernel. |
| Bug No | 19928402 |

| Parameter | Description |
|---|---|
| Function | FN_MT202 |
| No of Parameters | 4 |
| Function Call Id | 12 |
| Cluster/Custom Function Name | FN_MT202 |
| Additional parameters | l_tb_cluster_data |
| Sent to Extensible layer | l_Tb_Cluster_Data(l_202_User_Header)<br>l_Tb_Cluster_Data(DCN)<br>l_Tb_Cluster_Data(FLDTAG)<br>l_Tb_Cluster_Data(LOOPNO)<br>l_Tb_Cluster_Data(l_rtgs_nw_service_identifier) |
| Received from Extensible layer | l_Tb_Cluster_Data(DCN)<br>l_Tb_Cluster_Data(FLDTAG)<br>l_Tb_Cluster_Data(LOOPNO) |
| Hook Description | Hook Provided to check that if a payment is not through RTGS network but resulting in Bifurcation then MT202 header should be appended or populated with the value BIFURCATED in tag 108 |
| Description | Hook Provided to check that if a payment is not through RTGS network but resulting in Bifurcation then MT202 header should be appended or populated with the value BIFURCATED in tag 108<br><br>All parameters received by kernel function are passed to the cluster hook.<br><br>Additional parameters passed to cluster hook are mentioned in field "Additional Parameters".<br><br>The variables mentioned in "Sent to Extensible Layer" field are passed to cluster hook.<br><br>The variables mentioned in "Received from Extensible Layer" field are reassigned to kernel. |
| Bug No | 23653428 |

| Parameter | Description |
|---|---|
| Function | FN_MT202 |
| No of Parameters | 4 |
| Function Call Id | 18 |
| Cluster/Custom Function Name | FN_MT202 |
| Additional parameters | l_tb_cluster_data |

ORACLE®

| Sent to Extensible layer | None |
|---|---|
| Received from Extensible layer | None |
| Hook Description | Automation of MT 103 and MT 202 as per bank requirement. |
| Description | Automation of MT 103 and MT 202 as per bank requirement.<br><br>  All parameters received by kernel function are passed to the cluster hook.<br><br>    Additional parameters passed to cluster hook are mentioned in field "Additional Parameters".<br><br>    The variables mentioned in "Sent to Extensible Layer" field are passed to cluster hook.<br><br>    The variables mentioned in "Received from Extensible Layer" field are reassigned to kernel. |
| Bug No | 28176283 |

| Parameter | Description |
|---|---|
| Function | FN_MT203 |
| No of Parameters | 3 |
| Function Call Id | 1 |
| Cluster/Custom Function Name | FN_MT203 |
| Additional parameters | l_tb_cluster_data |
| Sent to Extensible layer | l_Tb_Cluster_Data(DCN)<br>l_Tb_Cluster_Data(FLDVAL)<br>l_Tb_Cluster_Data(LOOPNO) |
| Received from Extensible layer | None |
| Hook Description | Hook Provided |
| Description | Hook Provided<br><br>  All parameters received by kernel function are passed to the cluster hook.<br><br>    Additional parameters passed to cluster hook are mentioned in field "Additional Parameters".<br><br>    The variables mentioned in "Sent to Extensible Layer" field are passed to cluster hook.<br><br>    The variables mentioned in "Received from Extensible Layer" field are reassigned to kernel. |
| Bug No | 17861835 |

| Parameter | Description |
|---|---|
| Function | FN_MT203 |
| No of Parameters | 3 |
| Function Call Id | 2 |
| Cluster/Custom Function Name | FN_MT203 |
| Additional parameters | l_tb_cluster_data |
| Sent to Extensible layer | l_Tb_Cluster_Data(DCN)<br>l_Tb_Cluster_Data(FLDVAL)<br>l_Tb_Cluster_Data(LOOPNO) |
| Received from Extensible layer | l_Tb_Cluster_Data(DCN)<br>l_Tb_Cluster_Data(FLDVAL)<br>l_Tb_Cluster_Data(LOOPNO) |
| Hook Description | Hook Provided for FEW ADDITIONAL FIELDS. |

**ORACLE®**

| Description | Hook Provided for FEW ADDITIONAL FIELDS. |
|---|---|
| | All parameters received by kernel function are passed to the cluster hook. |
| | Additional parameters passed to cluster hook are mentioned in field "Additional Parameters". |
| | The variables mentioned in "Sent to Extensible Layer" field are passed to cluster hook. |
| | The variables mentioned in "Received from Extensible Layer" field are reassigned to kernel. |
| Bug No | 18722930 |

| Parameter | Description |
|---|---|
| Function | FN_SNDR_CORRESP |
| No of Parameters | 5 |
| Function Call Id | 1 |
| Cluster/Custom Function Name | FN_SNDR_CORRESP |
| Additional parameters | l_tb_cluster_data |
| Sent to Extensible layer | None |
| Received from Extensible layer | None |
| Hook Description | Hook Provided sa that GCB can have different criteria for the field 53A for MT103. |
| Description | Hook Provided sa that GCB can have different criteria for the field 53A for MT103. |
| | All parameters received by kernel function are passed to the cluster hook. |
| | Additional parameters passed to cluster hook are mentioned in field "Additional Parameters". |
| | The variables mentioned in "Sent to Extensible Layer" field are passed to cluster hook. |
| | The variables mentioned in "Received from Extensible Layer" field are reassigned to kernel. |
| Bug No | 18989665 |

| Parameter | Description |
|---|---|
| Function | FN_VALIDATE_103 |
| No of Parameters | 5 |
| Function Call Id | 1 |
| Cluster/Custom Function Name | FN_VALIDATE_103 |
| Additional parameters | l_tb_cluster_data |
| Sent to Extensible layer | None |
| Received from Extensible layer | None |
| Hook Description | Hook Provided |
| Description | Hook Provided |
| | All parameters received by kernel function are passed to the cluster hook. |
| | Additional parameters passed to cluster hook are mentioned in field "Additional Parameters". |
| | The variables mentioned in "Sent to Extensible Layer" field are passed to cluster hook. |
| | The variables mentioned in "Received from Extensible Layer" field are reassigned to kernel. |
| Bug No | 17861835 |

**ORACLE®**

| Parameter | Description |
|---|---|
| Function | FN_VALIDATE_103 |
| No of Parameters | 5 |
| Function Call Id | 2 |
| Cluster/Custom Function Name | FN_VALIDATE_103 |
| Additional parameters | l_tb_cluster_data |
| Sent to Extensible layer | None |
| Received from Extensible layer | None |
| Hook Description | Hook Provided for iban validation for country at to be skipped in favour of iban |
| Description | Hook Provided for iban validation for country at to be skipped in favour of iban<br>  All parameters received by kernel function are passed to the cluster hook.<br>    Additional parameters passed to cluster hook are mentioned in field "Additional Parameters".<br>    The variables mentioned in "Sent to Extensible Layer" field are passed to cluster hook.<br>    The variables mentioned in "Received from Extensible Layer" field are reassigned to kernel. |
| Bug No | 18694488 |

| Parameter | Description |
|---|---|
| Function | FN_VALIDATE_103P |
| No of Parameters | 5 |
| Function Call Id | 1 |
| Cluster/Custom Function Name | FN_VALIDATE_103P |
| Additional parameters | l_tb_cluster_data |
| Sent to Extensible layer | None |
| Received from Extensible layer | None |
| Hook Description | Hook Provided for iban validation for country at to be skipped in favor of iban |
| Description | Hook Provided for iban validation for country at to be skipped in favor of iban<br>  All parameters received by kernel function are passed to the cluster hook.<br>    Additional parameters passed to cluster hook are mentioned in field "Additional Parameters".<br>    The variables mentioned in "Sent to Extensible Layer" field are passed to cluster hook.<br>    The variables mentioned in "Received from Extensible Layer" field are reassigned to kernel. |
| Bug No | 18694488 |

| Parameter | Description |
|---|---|
| Function | FN_VALIDATE_IS_INFO |
| No of Parameters | 10 |
| Function Call Id | 1 |

ORACLE®

| | |
|---|---|
| Cluster/Custom Function Name | FN_VALIDATE_IS_INFO |
| Additional parameters | l_tb_cluster_data |
| Sent to Extensible layer | None |
| Received from Extensible layer | None |
| Hook Description | Hook Provided for the MELOCAL common customization project |
| Description | Hook Provided for the MELOCAL common customization project<br> All parameters received by kernel function are passed to the cluster hook.<br>   Additional parameters passed to cluster hook are mentioned in field "Additional Parameters".<br>   The variables mentioned in "Sent to Extensible Layer" field are passed to cluster hook.<br>   The variables mentioned in "Received from Extensible Layer" field are reassigned to kernel. |
| Bug No | 17861835 |

ORACLE®