

Deploying Application on WebLogic
Oracle Banking Corporate Lending
Release 14.5.5.0.0
Part No. F58338-01
[May] [2022]



Table of Contents

1.	DEPLOYING ORACLE FLEXCUBE ON WEBLOGIC	1-1
1.1	INTRODUCTION	1-1
1.2	BUILDING APPLICATION	1-1
1.2.1	<i>Building Application in Centralized Mode</i>	<i>1-1</i>
1.2.2	<i>Building Application in Decentralized Mode.....</i>	<i>1-1</i>
1.3	DEPLOYING APPLICATION IN ORACLE WEBLOGIC	1-1
1.3.1	<i>Deploying Integration Adapter EAR from WebLogic Administration Console</i>	<i>1-1</i>
1.3.2	<i>Deploying Dependency Library “Jax-RS”</i>	<i>1-7</i>
1.3.3	<i>Deploying FCUBS Application from WebLogic Administration Console</i>	<i>1-10</i>
1.3.4	<i>Deploying Gateway/Scheduler Applications from WebLogic Administration Console</i>	<i>1-19</i>

1. Deploying Oracle FLEXCUBE on WebLogic

1.1 Introduction

This chapter explains the steps to deploy Oracle FLEXCUBE UBS application into Oracle WebLogic application server in centralized and decentralized modes. In centralized mode, branch and host are setup in a single PC. In decentralized mode, branch and host are setup in different PCs.

1.2 Building Application

For building Oracle FLEXCUBE Application in centralized and decentralized modes, refer to the following chapters.

1.2.1 Building Application in Centralized Mode

Refer to the chapter 'Building Application in Centralized Mode'. This includes the following details:

- Creating Property File
- Building Centralized EAR File
- Configuring Plug-ins
- Loading Properties File

1.2.2 Building Application in Decentralized Mode

Refer to the chapter 'Building Application in Decentralized Mode'. This includes the following details:

- Creating Property File
- Building Decentralized EAR File
- Configuring Plug-ins
- Loading Properties File

1.3 Deploying Application in Oracle WebLogic

This section explains the method of deploying Oracle FLEXCUBE Application into Oracle WebLogic application server.


1.3.1 Deploying Integration Adapter EAR from WebLogic Administration Console

To deploy Oracle FLEXCUBE Application from Oracle WebLogic administration console, follow the steps given below.


1. Start the Administrative Console of WebLogic application server. You can start this by entering Oracle WebLogic Admin Console URL in the address bar in an internet browser.

Eg: <http://10.10.10.10:1001/console>


The following screen is displayed:



- Specify the WebLogic administrator user name and password. Click 'Log In'.




- You need to deploy an Integration adapter EAR. For e.g. 'OBACLExtAdapter.ear' or 'ExtAdapter.ear'. Go to 'Deployment'.
- Click 'Lock & Edit' button to enable the buttons. This action enables the buttons.



5. Click 'Install' button.

The following screen is displayed:




6. In order to specify the path/location of the enterprise archive file, click the link 'upload your file(s)'.

7. Specify the EAR file path. You can use the 'Browse' button to locate the file.

8. Click 'Next'.


The following screen is displayed.



9. Select the application Adapter EAR from the list.

10. Click 'Next'.


The following screen is displayed.



11. Choose the targeting style 'Install this deployment as a library'.


12. Click 'Next'.

The following screen is displayed.




13. Select the target of the application. You can choose the server 'AdminServer' or 'Managed Server(s)'.

14. Click 'Next'. The following screen is displayed.




15. Check the deployment name.

The remaining portion of the screen is shown below:




16. Click 'Finish' button.

The following screen is displayed.



17. Click 'Save' button.

The message 'Settings updated successfully' is displayed.




18. Click 'Activate Changes' button on the left pane. The message 'All the changes have been activated. No restarts are necessary' is displayed.

1.3.2 Deploying Dependency Library "Jax-RS"


This library must be installed before deploying FCUBSApp.ear. Follow the below steps


1. Start the Administrative Console of WebLogic application server. You can start this by entering Oracle WebLogic Admin Console URL in the address bar in an internet browser.
Eg: <http://10.10.10.10:1001/console>

The following screen is displayed:




- The following screen is displayed:







4. Navigate and select jersey bundle under the path "*w\server\common\deployable-libraries\jax-rs-2.0.war*" and click next.



5. Select "install this deployment as library", select target server as managed server and click next.



6. Click finish button.



This library must appear in the deployment with Type column as "Library"

Note : Latest Jax-rs version will be jax-rs(2.0,2.22.1.0).

1.3.3 Deploying FCUBS Application from WebLogic Administration Console

To deploy Oracle FLEXCUBE Application from Oracle WebLogic administration console, follow the steps given below.


1. Start the Administrative Console of WebLogic application server. You can start this by entering Oracle WebLogic Admin Console URL in the address bar in an internet browser.
Eg: <http://10.10.10.10:1001/console>

The following screen is displayed:



2. Specify the WebLogic administrator user name and password. Click 'Log In'.

The following screen is displayed:



3. You need to deploy an EAR. For e.g. 'FCUBSApp.ear'. Go to 'Deployment'.

- Click 'Lock & Edit' button to enable the buttons. This action enables the buttons.

Oracle WebLogic Server Administration Console

Home > Summary of Deployments

Summary of Deployments

Configuration Control Monitoring

This page displays the list of Java EE applications and standalone application modules installed to this domain.

You can update (redeploy) or delete installed applications and modules from the domain by selecting the checkbox next to the application name and then using the controls on this page.

To install a new application or module for deployment to targets in this domain, click **Install**.

Customize this table

Deployments

Name	State	Health	Type	Targets	Scope	Domain Partitions	Deployment Order
adf.oracle.businesseditor(1.0,12.2.1.0.0)	Active		Library	AdminServer_payments, pm_server1	Global		100
adf.oracle.domain(1.0,12.2.1.0.0)	Active		Library	AdminServer_payments, pm_server1	Global		100
adf.oracle.domain.webapp(1.0,12.2.1.0.0)	Active		Library	AdminServer_payments, pm_server1	Global		100
coherence-transaction-rar	Active	OK	Resource Adapter	AdminServer_payments, pm_server1	Global		100
OHS Application (12.2.1.0.0)	Active	OK	Web Application	AdminServer_payments, pm_server1	Global		5
em	Active	OK	Enterprise Application	AdminServer_payments	Global		400
emagentdimplpriv_jar(12.4.12.1.0.4.0)	Active		Library	AdminServer_payments	Global		100
emagentdimpl_jar(12.4.12.1.0.4.0)	Active		Library	AdminServer_payments	Global		100
emagentdimpl_jar(12.4.12.1.0.4.0)	Active		Library	AdminServer_payments	Global		100
emas	Active		Library	AdminServer_payments	Global		100
emcore	Active		Library	AdminServer_payments	Global		100
emcoreagent_jar	Active		Library	AdminServer_payments	Global		100
emcorecommon_jar	Active		Library	AdminServer_payments	Global		100
emcoreconsole_jar	Active		Library	AdminServer_payments	Global		100
emcoreintask_jar(11.2.0.1.0,12.1.0.0.0)	Active		Library	AdminServer_payments	Global		100
emcoreimpl_jar	Active		Library	AdminServer_payments	Global		100
emcoreimpl_jar(11.2.0.1.0,12.1.0.0.0)	Active		Library	AdminServer_payments	Global		100
emcoreimpl_jar(11.2.0.1.0,12.1.0.0.0)	Active		Library	AdminServer_payments	Global		100
emcoreimpl_jar	Active		Library	AdminServer_payments	Global		100
emcommon(12.4.12.1.0.4.0)	Active		Library	AdminServer_payments	Global		100

- Click 'Install' button.

The following screen is displayed:

Oracle WebLogic Server Administration Console

Home > Summary of Deployments

Welcome, weblogic Connected to: FCUBS11

Install Application Assistant

Back Next Finish Cancel

Locate deployment to install and prepare for deployment

Select the file path that represents the application root directory, archive file, exploded archive directory, or application module descriptor that you want to install. You can also enter the path of the application directory or file in the Path field.

Note: Only valid file paths are displayed below. If you cannot find your deployment files, upload your file(s) and/or confirm that your application contains the required deployment descriptors.

Path: D:\


Recently Used Paths: (none)

Current Location: ddhp0520.i-flex.com \D:\

- 11.0
- 9NT1272
- APPOINT SOFTWARE SOLUTIONS
- backup
- bea
- bea11g
- bea_100
- BinDlogs
- ClearCase
- CRC
- Desktop
- Documents and Settings

- In order to specify the path/location of the enterprise archive file, click the link 'upload your file(s)'.
- Click 'Next'.


The following screen is displayed:



8. Specify the EAR file path. You can use the 'Browse' button to locate the file.

9. Click 'Next'.


The following screen is displayed.



10. Select the application FCUBS EAR from the list.

11. Click 'Next'.


The following screen is displayed:



12. Choose the targeting style 'Install this deployment as an application'.

13. Click 'Next'.


The following screen is displayed



14. Select the target of the application. You can choose the server 'AdminServer' or 'Managed Server(s)'.


15. Click 'Next'.

The following screen appears.



16. Check the deployment name.

The remaining portion of the screen is shown below:



17. Check whether the deployment location is accessible or not.

The following screen is displayed.

No pending changes exist. Click the Release Configuration button to allow others to edit the domain.

Lock & Edit
Release Configuration

Domain Structure

FCUBS11

- Environment
- Deployments
- Services
- Security Realms
- Interoperability
- Diagnostics

How do I...

- Start and stop a deployed Enterprise application
- Configure an Enterprise application
- Create a deployment plan
- Target an Enterprise application to a server
- Test the modules in an Enterprise application

System Status

Health of Running Servers

Install Application Assistant

Back Next Finish Cancel

Review your choices and click Finish

Click Finish to complete the deployment. This may take a few moments to complete.

Additional configuration

In order to work successfully, this application may require additional configuration. Do you want to review this application's configuration after completing this assistant?

☒ Yes, take me to the deployment's configuration screen.

☐ No, I will review the configuration later.

Summary

Deployment: D:\dev\11g11.1.1.0\user_projects\domains\FCUBS11\servers\AdminServer\upload\FCUBS11.ear

Name: FCUBS11

Staging mode: Use the defaults defined by the chosen targets

Security Model: DDOnly: Use only roles and policies that are defined in the deployment descriptors.

Target Summary

Components	Targets
FCUBS11.ear	ManagedServer_1

Back Next Finish Cancel

18. Click 'Finish' button. The following screen is displayed.

Change **Deployment Order** to **400** if the application includes **BPMN plug-in**.

ORACLE WebLogic Server® Administration Console

Home Log Out Preferences Record Help Welcome, weblogic Connected to: FCUBS11

Home > Summary of Deployments > FCUBS11

Settings for FCUBS11


Overview Deployment Plan Configuration Security Targets Control Testing Monitoring Notes

Save

Use this page to view the general configuration of an Enterprise application, such as its name, the physical path to the application files, the associated deployment plan, and so on. The table at the end of the page lists the modules (such as Web applications and EJBs) that are contained in the Enterprise application. Click on the name of the module to view and update its configuration.


Name:	FCUBS11	The name of this Enterprise Application. More Info...
Path:	D:\dev\11g11.1.1.0\user_projects\domains\FCUBS11\servers\AdminServer\upload\FCUBS11.ear	The path to the source of the deployable unit on the Administration Server. More Info...
Deployment Plan:	(no plan specified)	The path to the deployment plan document on Administration Server. More Info...
Staging Mode:	(not specified)	The mode that specifies whether a deployment's files are copied from a source on the Administration Server to the Managed Server's staging area during application preparation. More Info...
Security Model:	DDOnly	The security model that is used to secure a deployed module. More Info...
Deployment Order:	100	An integer value that indicates when this unit is deployed, relative to other deployable units on a server, during startup. More Info...
Deployment		A string value that indicates what principal should be used when deploying the file or archive during startup.

19. Click 'Save' button. The message 'Settings updated successfully' is displayed.




20. Click 'Activate Changes' button on the left pane. The message 'All the changes have been activated. No restarts are necessary' is displayed.

The screen is given below:





21. Click 'Deployment' on the left pane. Switch to Control tab .The following screen is displayed.



22. Click 'Start' drop-down button and select 'Servicing all requests'.

The following screen is displayed.





23. Click 'Yes'. The following screen is displayed.

This completes the deployment process.

1.3.4 **Deploying Gateway/Scheduler Applications from WebLogic Administration Console**

To deploy Oracle FLEXCUBE Gateway/Scheduler Application from Oracle WebLogic administration console, follow the steps given below.


1. Launch Administrative Console of WebLogic application server. You can launch this by entering Oracle WebLogic Admin Console URL in the address bar in an internet browser.
Eg: <http://10.10.10.10:1001/console>

The following screen is displayed:



2. Specify the WebLogic administrator user name and password. Click 'Log In'.

The following screen is displayed:



3. You need to deploy an EAR. For e.g. 'GWEJB.ear'. Go to 'Deployment'.

- Click 'Lock & Edit' button to enable the buttons. This action enables the buttons.

Summary of Deployments

This page displays the list of Java EE applications and standalone application modules installed to this domain. You can update (redploy) or delete installed applications and modules from the domain by selecting the checkbox next to the application name and then using the controls on this page. To install a new application or module for deployment to targets in this domain, click **Install**.

Customize this table

Install	Update	Delete	Name	State	Health	Type	Targets	Scope	Domain Partitions	Deployment Order
☐			adf.oracle.businesseditor(1.0,12.2.1.0.0)	Active		Library	AdminServer_payments, pm_server1	Global		100
☐			adf.oracle.domain(1.0,12.2.1.0.0)	Active		Library	AdminServer_payments, pm_server1	Global		100
☐			adf.oracle.domain.webapp(1.0,12.2.1.0.0)	Active		Library	AdminServer_payments, pm_server1	Global		100
☐			coherence-transaction-war	Active	OK	Resource Adapter	AdminServer_payments, pm_server1	Global		100
☐			OMS Application (12.2.1.0.0)	Active	OK	Web Application	AdminServer_payments, pm_server1	Global		5
☐			em	Active	OK	Enterprise Application	AdminServer_payments	Global		400
☐			emagentbdtkimplpriv_jar(12.4,12.1.0.4.0)	Active		Library	AdminServer_payments	Global		100
☐			emagentbdtkimpl_jar(12.4,12.1.0.4.0)	Active		Library	AdminServer_payments	Global		100
☐			emagentbdtk_jar(12.4,12.1.0.4.0)	Active		Library	AdminServer_payments	Global		100
☐			emas	Active		Library	AdminServer_payments	Global		100
☐			emencore	Active		Library	AdminServer_payments	Global		100
☐			emencoreclient_jar	Active		Library	AdminServer_payments	Global		100
☐			emencorecommon_jar	Active		Library	AdminServer_payments	Global		100
☐			emencoreconsole_jar	Active		Library	AdminServer_payments	Global		100
☐			emencorestd_jar(11.2.0.1.0,12.1.0.0.0)	Active		Library	AdminServer_payments	Global		100
☐			emencorestd_jar	Active		Library	AdminServer_payments	Global		100
☐			emencorestdimpl_jar(11.2.0.1.0,12.1.0.0.0)	Active		Library	AdminServer_payments	Global		100
☐			emencorestd_jar(11.2.0.1.0,12.1.0.0.0)	Active		Library	AdminServer_payments	Global		100
☐			emencorestd_jar(11.2.0.1.0,12.1.0.0.0)	Active		Library	AdminServer_payments	Global		100
☐			emencorestd_jar	Active		Library	AdminServer_payments	Global		100
☐			emencorestd_jar(12.4,12.1.0.4.0)	Active		Library	AdminServer_payments	Global		100
☐			emencorestd_jar	Active		Library	AdminServer_payments	Global		100

- Click 'Install' button. The following screen is displayed:

Install Application Assistant

Back Next Finish Cancel

Locate deployment to install and prepare for deployment

Select the file path that represents the application root directory, archive file, exploded archive directory, or application module descriptor that you want to install. You can also enter the path of the application directory or file in the Path field.

Note: Only valid file paths are displayed below. If you cannot find your deployment files, upload your file(s) and/or confirm that your application contains the required deployment descriptors.

Path: D:\

Recently Used Paths: (none)

Current Location: ddhp0520.i-flex.com \D:

- 11.0
- 9NT 1272
- APPOINT SOFTWARE SOLUTIONS
- backup
- bea
- bea11g
- bea_100
- BrdBgs
- ClearCase
- CRC
- Desktop
- Documents and Settings

- In order to specify the path/location of the enterprise archive file, click the link 'upload your file(s)'.

7. Click 'Next'. The following screen is displayed:

The screenshot shows the Oracle WebLogic Server Administration Console 12c. The main window is titled 'Install Application Assistant'. It has a navigation bar at the top with 'Home', 'Log Out', 'Preferences', 'Record', and 'Help'. Below the navigation bar, there's a 'Summary of Deployments' section. The main content area is divided into two sections: 'Upload a deployment to the Administration Server' and 'Upload a deployment plan (this step is optional)'. The first section has a 'Browse...' button next to the 'Deployment Archive' field, which currently contains the path 'C:\Users\shashras\Documents\GWEJB.ear\app\GWEJB.ear'. The second section has a 'Browse...' button next to the 'Deployment Plan Archive' field. On the left side of the console, there's a 'Change Center' panel with a 'View changes and restarts' section, a 'Domain Structure' tree, and a 'System Status' section showing the health of running servers. The 'System Status' section shows a table with columns for 'Health of Running Servers' and 'Status'. The table has two rows: 'Failed (0)', 'Critical (0)', 'Overloaded (0)', 'Warning (0)', and 'OK (2)'. The 'OK (2)' row is highlighted in green.

8. Specify the EAR file path. You can use the 'Browse' button to locate the file.

9. Click 'Next'. The following screen is displayed.

The screenshot shows the Oracle WebLogic Server Administration Console 12c, 'Install Application Assistant' screen, after clicking 'Next'. The main window is titled 'Install Application Assistant'. It has a navigation bar at the top with 'Home', 'Log Out', 'Preferences', 'Record', and 'Help'. Below the navigation bar, there's a 'Summary of Deployments' section. The main content area is divided into two sections: 'Locate deployment to install and prepare for deployment' and 'Upload a deployment to the Administration Server'. The first section has a 'Path' field with the value '/scratch/app/fmw122/Oracle/user_projects/domains/PM1221TR2/servers/Admin_PMTIR2/upload/GWEJB.ear/app/GWEJB.ear'. Below the 'Path' field, there's a 'Recently Used Paths' section with a list of paths. The 'Current Location' section shows the path '10.104.155.73 / scratch / app / fmw122 / Oracle / user_projects / domains / PM1221TR2 / servers / Admin_PMTIR2 / upload / GWEJB.ear / app'. On the left side of the console, there's a 'Change Center' panel with a 'View changes and restarts' section, a 'Domain Structure' tree, and a 'System Status' section showing the health of running servers. The 'System Status' section shows a table with columns for 'Health of Running Servers' and 'Status'. The table has two rows: 'Failed (0)', 'Critical (0)', 'Overloaded (0)', 'Warning (0)', and 'OK (2)'. The 'OK (2)' row is highlighted in green.

10. Select the application from the list.

11. Click 'Next'. Following screen is displayed:

The screenshot shows the Oracle WebLogic Server Administration Console. On the left, there is a 'Change Center' sidebar with sections for 'View changes and restarts', 'Domain Structure' (showing a tree with PM1221TR2, Domain Partitions, Environment, Deployments, Services, Security Realms, Interoperability, and Diagnostics), 'How do I...', and 'System Status' (showing Health of Running Servers with 0 Failed, 0 Critical, 0 Overloaded, 0 Warning, and 2 OK). The main area is titled 'Install Application Assistant' and contains the following content:

Home Log Out Preferences Record Help

Home > Summary of Deployments

Back Next Finish Cancel

Choose installation type and scope

Select if the deployment should be installed as an application or library. Also decide the scope of this deployment.

The application and its components will be targeted to the same locations. This is the most common usage.

☒ **Install this deployment as an application**

Application libraries are deployments that are available for other deployments to share. Libraries should be available on all of the targets running their referencing applications.

☐ **Install this deployment as a library**

☐ **Install this deployment as an application, but target the components individually**

Useful when one or more of the modules or components must have targets unique from the rest of the application.

Select a scope in which you want to install the deployment.

Scope: Global

Back Next Finish Cancel

12. Choose the targeting style 'Install this deployment as an application'.

13. Click 'Next'.

The following screen is displayed

The screenshot shows the Oracle WebLogic Server Administration Console. On the left, there is a 'Change Center' sidebar with sections for 'View changes and restarts', 'Domain Structure' (showing a tree with PM1221TR2, Domain Partitions, Environment, Deployments, Services, Security Realms, Interoperability, and Diagnostics), 'How do I...', and 'System Status' (showing Health of Running Servers with 0 Failed, 0 Critical, 0 Overloaded, 0 Warning, and 2 OK). The main area is titled 'Select deployment targets' and contains the following content:

Home Log Out Preferences Record Help

Home > Summary of Deployments

Back Next Finish Cancel

Select deployment targets

Select the servers and/or clusters to which you want to deploy this application. (You can reconfigure deployment targets later).

Available targets for GWEJB :

Servers
☐ Admin_PM1TR2
☒ payments_server1

Back Next Finish Cancel

14. Select the target of the application. You can choose the server 'AdminServer' or 'Managed Server(s)'.

15. Click 'Next'. The following screen is displayed.

Oracle WebLogic Server Administration Console 12c

Home > Summary of Deployments > Summary of JDBC Data Sources > Summary of Deployments

Welcome, weblogic Connected to: FCAPACK125

Install Application Assistant

Back Next Finish Cancel

Optional Settings
You can modify these settings or accept the defaults.
* Indicates required fields

General
What do you want to name this deployment?
* **Name:** GWEJB

Security
What security model do you want to use with this application?
☒ **DO Only:** Use only roles and policies that are defined in the deployment descriptors.
☐ **Custom Roles:** Use roles that are defined in the Administration Console; use policies that are defined in the deployment descriptor.
☐ **Custom Roles and Policies:** Use only roles and policies that are defined in the Administration Console.
☐ **Advanced:** Use a custom model that you have configured on the realm's configuration page.

Source Accessibility
How should the source files be made accessible?
☒ **Use the defaults defined by the deployment's targets**
☐ **Use the same accessibility as the application**

Recommended selection.
☐ **Copy this application onto every target for me**
During deployment, the files will be copied automatically to the Managed Servers to which the application is targeted.
☒ **I will make the deployment accessible from the following location**
Location: /scratch/app/vt12212/user_projects/domains/FCAPACK125/serv

Provide the location from where all targets will access this application's files. This is often a shared directory. You must ensure the application files exist in this location and that each target can reach the location.

Plan Source Accessibility
How should the plan source files be made accessible?
☒ **Use the same accessibility as the application**

Recommended selection.
☐ **Copy this plan onto every target for me**
During deployment, the plan files will be copied automatically to the Managed Servers to which the application is targeted.
☒ **Do not copy this plan to targets**
You must ensure the plan files exist in the shared location and that each target can reach the location.

Back Next Finish Cancel

16. Check the deployment name.

The remaining portion of the screen is shown below:

Oracle WebLogic Server Administration Console 12c

Home > Summary of Deployments > Summary of JDBC Data Sources > Summary of Deployments

Welcome, weblogic Connected to: FCAPACK125

Install Application Assistant

Back Next Finish Cancel

Optional Settings
You can modify these settings or accept the defaults.
* Indicates required fields

General
What do you want to name this deployment?
* **Name:** GWEJB

Security
What security model do you want to use with this application?
☒ **DO Only:** Use only roles and policies that are defined in the deployment descriptors.
☐ **Custom Roles:** Use roles that are defined in the Administration Console; use policies that are defined in the deployment descriptor.
☐ **Custom Roles and Policies:** Use only roles and policies that are defined in the Administration Console.
☐ **Advanced:** Use a custom model that you have configured on the realm's configuration page.

Source Accessibility
How should the source files be made accessible?
☒ **Use the defaults defined by the deployment's targets**
☐ **Use the same accessibility as the application**

Recommended selection.
☐ **Copy this application onto every target for me**
During deployment, the files will be copied automatically to the Managed Servers to which the application is targeted.
☒ **I will make the deployment accessible from the following location**
Location: /scratch/app/vt12212/user_projects/domains/FCAPACK125/serv

Provide the location from where all targets will access this application's files. This is often a shared directory. You must ensure the application files exist in this location and that each target can reach the location.

Plan Source Accessibility
How should the plan source files be made accessible?
☒ **Use the same accessibility as the application**

Recommended selection.
☐ **Copy this plan onto every target for me**
During deployment, the plan files will be copied automatically to the Managed Servers to which the application is targeted.
☒ **Do not copy this plan to targets**
You must ensure the plan files exist in the shared location and that each target can reach the location.

Back Next Finish Cancel

17. Check whether the deployment location is accessible or not. The following screen is displayed.

Change Center
View changes and restarts
No pending changes exist. Click the Release Configuration button to allow others to edit the domain.
Lock & Edit
Release Configuration

Domain Structure
PM1221TR2
Domain Partitions
Environment
Deployments
Services
Security Realms
Interoperability
Diagnostics

How do I...?
Start and stop a deployed enterprise application
Configure an enterprise application
Create a deployment plan
Target an enterprise application to a server instance
Test the modules in an enterprise application

System Status
Health of Running Servers
Failed (0)
Critical (0)
Overloaded (0)
Warning (0)
OK (2)

Install Application Assistant
Home Log Out Preferences Record Help
Home > Summary of Deployments
Back Next Finish Cancel
Review your choices and click Finish
Click Finish to complete the deployment. This may take a few moments to complete.
Additional Configuration
In order to work successfully, this application may require additional configuration. Do you want to review this application's configuration after completing this assistant?
Yes, take me to the deployment's configuration screen.
No, I will review the configuration later.
Summary
Deployment: /scratch/app/fmw122/Oracle/user_projects/domains/PM1221TR2/servers/Admin_PM1221TR2/upload/GWEJB.ear/app/GWEJB.ear
Name: GWEJB
Staging Mode: Use the defaults defined by the chosen targets
Plan Staging Mode: Use the same accessibility as the application
Security Model: DOOnly: Use only roles and policies that are defined in the deployment descriptors.
Scope: Global
Target Summary
Components
Targets
GWEJB.ear payments_server1
Back Next Finish Cancel

18. Click 'Finish' button. The following screen is displayed.

Change Center
View changes and restarts
Pending changes exist. They must be activated to take effect.
Activate Changes
Undo All Changes

Domain Structure
PM1221TR2
Domain Partitions
Environment
Deployments
Services
Security Realms
Interoperability
Diagnostics

How do I...?
Start and stop a deployed enterprise application
Configure an enterprise application
Create a deployment plan
Target an enterprise application to a server instance
Test the modules in an enterprise application

System Status
Health of Running Servers
Failed (0)
Critical (0)
Overloaded (0)
Warning (0)
OK (2)

Settings for GWEJB(12.2.0.0.0)
Home Log Out Preferences Record Help
Home > Summary of Deployments > GWEJB(12.2.0.0.0)
Overview Deployment Plan Configuration Security Targets Control Testing Monitoring Notes
Save
Use this page to view the general configuration of an enterprise application, such as its name, the physical path to the application files, the associated deployment plan, and so on. The table at the end of the page lists the modules (such as Web applications) contained in the enterprise application. Click on the name of the module to view and update its configuration.
Name: GWEJB The name of this enterprise application. More Info...
Scope: Global Specifies if this enterprise application is accessible within the domain, a partition, or a resor template. More Info...
Archive Version: 12.2.0.0.0 The archive version, specified from from the manifest or overridden during deployment. More Info...
Path: /scratch/app/fmw122/Oracle/user_projects/domains/PM1221TR2/servers/Admin_PM1221TR2/upload/GWEJB.ear/app/GWEJB.ear The path to the source of the deployable unit on the Administration Server. More Info...
Deployment Plan: (no plan specified) The path to the deployment plan document on the Administration Server. More Info...
Staging Mode: (not specified) Specifies whether a deployment's files are copied from a source on the Administration Server's staging area during application preparation. More Info...
Plan Staging Mode: (not specified) Specifies whether an application's deployment plan is copied from a source on the Administration Server's staging area during application preparation. More Info...
Security Model: DOOnly The security model that is used to secure a deployed module. More Info...
Deployment Order: 100 An integer value that indicates when this unit is deployed, relative to other deployable units during startup. More Info...
Deployment Principal Name: A string value that indicates the principal that should be used when deploying the file or an and shutdown. This principal will be used to set the current subject when calling out into as interfaces such as ApplicationLifecycleListener. If no principal name is specified, then the is will be used. More Info...
Save
Modules and Components
Showing 1 to 1 of 1
Name
GWEJB (12.2.0.0.0)
EJB
PCMainProcEJB
PCServletEJB
GWEJB

19. Click 'Save' button. The message 'Settings updated successfully' is displayed.

Oracle WebLogic Server Administration Console 12c

Home > Summary of Deployments > GWEJB(12.2.0.0.0)

Messages

Settings updated successfully.

Settings for GWEJB(12.2.0.0.0)

Overview | Deployment Plan | Configuration | Security | Targets | Control | Testing | Monitoring | Notes

Save

Use this page to view the general configuration of an enterprise application, such as its name, the physical path to the application files, the associated deployment plan, and so on. The table at the end of the page lists the modules (such as contained in the enterprise application. Click on the name of the module to view and update its configuration.

Name:	GWEJB	The name of this enterprise application. More Info...
Scope:	Global	Specifies if this enterprise application is accessible within the domain, template. More Info...
Archive Version:	12.2.0.0.0	The archive version, specified from the manifest or overridden d
Path:	/ scratch/ app/ fmv122/ Oracle/ user_projects/ domains/ PM1221TR2/ servers/ Admin_PM1TR2/ upload/ GWEJB. ear/ app/ GWEJB. ear	The path to the source of the deployable unit on the Administration S
Deployment Plan:	(no plan specified)	The path to the deployment plan document on the Administration Ser
Staging Mode:	(not specified)	Specifies whether a deployment's files are copied from a source on th Server's staging area during application preparation. More Info...
Plan Staging Mode:	(not specified)	Specifies whether an application's deployment plan is copied from a s Managed Server's staging area during application preparation. More Info...
Security Model:	DDOnly	The security model that is used to secure a deployed module. More Info...
Deployment Order:	100	An integer value that indicates when this unit is deployed, relative to during startup. More Info...
Deployment Principal Name:		A string value that indicates the principal that should be used when d and shutdown. This principal will be used to set the current subject v interfaces such as ApplicationLifecycleListener. If no principal name is will be used. More Info...

Save

Modules and Components

Name
GWEJB (12.2.0.0.0)
EJBs
PCMainProcEJB
PCServletEJB

20. Click 'Activate Changes' button on the left pane. The message 'All the changes have been activated. No restarts are necessary' is displayed.

The screen is given below:

Oracle WebLogic Server Administration Console 12c

Home > Summary of Deployments > GWEJB(12.2.0.0.0)

Messages

All changes have been activated. No restarts are necessary.

Settings for GWEJB(12.2.0.0.0)

Overview | Deployment Plan | Configuration | Security | Targets | Control | Testing | Monitoring | Notes

Save

Click the **Lock & Edit** button in the Change Center to modify the settings on this page.

Use this page to view the general configuration of an enterprise application, such as its name, the physical path to the application files, the associated deployment plan, and so on. The table at the end of the page lists the modules (such as Wel contained in the enterprise application. Click on the name of the module to view and update its configuration.

Name:	GWEJB	The name of this enterprise application. More Info...
Scope:	Global	Specifies if this enterprise application is accessible within the domain, a parti template. More Info...
Archive Version:	12.2.0.0.0	The archive version, specified from the manifest or overridden during c
Path:	/ scratch/ app/ fmv122/ Oracle/ user_projects/ domains/ PM1221TR2/ servers/ Admin_PM1TR2/ upload/ GWEJB. ear/ app/ GWEJB. ear	The path to the source of the deployable unit on the Administration Server.
Deployment Plan:	(no plan specified)	The path to the deployment plan document on the Administration Server. ?
Staging Mode:	(not specified)	Specifies whether a deployment's files are copied from a source on the Admi Server's staging area during application preparation. More Info...
Plan Staging Mode:	(not specified)	Specifies whether an application's deployment plan is copied from a source (Managed Server's staging area during application preparation. More Info...
Security Model:	DDOnly	The security model that is used to secure a deployed module. More Info...
Deployment Order:	100	An integer value that indicates when this unit is deployed, relative to other d during startup. More Info...
Deployment Principal Name:		A string value that indicates the principal that should be used when deployin and shutdown. This principal will be used to set the current subject when ca interfaces such as ApplicationLifecycleListener. If no principal name is specifi will be used. More Info...

Modules and Components

Name
GWEJB (12.2.0.0.0)
EJBs
PCMainProcEJB
PCServletEJB

21. Click 'Deployment' on the left pane. Switch to Control tab. The following screen is displayed.

ORACLE WebLogic Server Administration Console 12c

Home > Summary of Deployments > GWEJB(12.2.0.0.0) > Summary of Deployments

Welcome, infra Connected to

Change Center
View changes and restarts
Click the Lock & Edit button to modify, add or delete items in this domain.
Lock & Edit
Release Configuration

Domain Structure
PH1221TR2
Domain Partitions
Environment
Deployments
Services
Security Realms
Interoperability
Diagnostics

How do I...
Configure an enterprise application
Start applications and modules
Stop applications and modules
View the modules of an enterprise application
Monitor the modules of an enterprise application

System Status
Health of Running Servers
Failed (0)
Critical (0)
Overloaded (0)
Warning (0)
OK (2)

Summary of Deployments
Configuration Control Monitoring

This page displays the list of Java EE applications and standalone application modules installed to this domain.
You can start and stop applications and modules from the domain by selecting the checkbox next to the application name and then using the controls on this page.

Customize this table

Deployments
Start Stop

	State	Health	Type	Targets	Scope	Domain Partition
Servicing all requests	Active	OK	Resource Adapter	Admin_PMTTR2	Global	
Servicing only administration requests	Active	OK	Resource Adapter	Admin_PMTTR2	Global	
☐ DMS Application (12.2.1.0.0)	Active	OK	Web Application	Admin_PMTTR2	Global	
☐ em	Active	OK	Enterprise Application	Admin_PMTTR2	Global	
☐ FCUBSApp (12.2.0.0.0)	Active	Warning	Enterprise Application	payments_server1	Global	
☒ GWEJB (12.2.0.0.0)	Prepared	OK	Enterprise Application	payments_server1	Global	
☐ ops-rest	Active	OK	Web Application	Admin_PMTTR2	Global	
☐ PaymentStubs	Active	OK	EJB	payments_server1	Global	
☐ state-management-provider-memory-rar	Active	OK	Resource Adapter	Admin_PMTTR2	Global	

Showing 1 to 8 of 8 Prev

WebLogic Server Version: 12.2.1.0.0
Copyright (c) 1996-2015, Oracle and/or its affiliates. All rights reserved.
Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

22. Click 'Start' drop-down button and select 'Servicing all requests'.

The following screen is displayed.

ORACLE WebLogic Server Administration Console 12c

Home > Summary of Deployments > GWEJB(12.2.0.0.0) > Summary of Deployments

Welcome, infra Connected to

Change Center
View changes and restarts
Click the Lock & Edit button to modify, add or delete items in this domain.
Lock & Edit
Release Configuration

Domain Structure
PH1221TR2
Domain Partitions
Environment
Deployments
Services
Security Realms
Interoperability
Diagnostics

How do I...
No task help found.

System Status
Health of Running Servers
Failed (0)
Critical (0)
Overloaded (0)
Warning (0)
OK (2)

Start Application Assistant
Yes No

Start Deployments
You have selected the following deployments to be started. Click 'Yes' to continue, or 'No' to cancel.
GWEJB(12.2.0.0.0)
Yes No

WebLogic Server Version: 12.2.1.0.0
Copyright (c) 1996-2015, Oracle and/or its affiliates. All rights reserved.
Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

23. Click 'Yes'. The following screen is displayed.

Oracle WebLogic Server Administration Console 12c

Home Log Out: Preferences Record Help

Welcome, infra Connected to: PM1221TR2

Messages
Start requests have been sent to the selected deployments.

Summary of Deployments
Configuration Control Monitoring

This page displays the list of Java EE applications and standalone application modules installed to this domain.
You can start and stop applications and modules from the domain by selecting the checkbox next to the application name and then using the controls on this page.

Customize this table

Deployments
Start Stop

Name	State	Health	Type	Targets	Scope	Domain Partitions
☐ coherence-transaction-rar	Active	OK	Resource Adapter	Admin_PM1TR2	Global	
☐ CMS Application (12.2.1.0.0)	Active	OK	Web Application	Admin_PM1TR2	Global	
☐ em	Active	OK	Enterprise Application	Admin_PM1TR2	Global	
☐ FCLB5App (12.2.0.0.0)	Active	Warning	Enterprise Application	payments_server1	Global	
☐ GWESB (12.2.0.0.0)	Active	OK	Enterprise Application	payments_server1	Global	
☐ ipay-rest	Active	OK	Web Application	Admin_PM1TR2	Global	
☐ PaymentStub	Active	OK	EJB	payments_server1	Global	
☐ state-management-provider-memory-rar	Active	OK	Resource Adapter	Admin_PM1TR2	Global	

Showing 1 to 8 of 8 Previous Next

Start Stop

System Status
Health of Running Servers

Failed (0)
Critical (0)
Overloaded (0)
Warning (0)
OK (2)

WebLogic Server Version: 12.2.1.0.0
Copyright (c) 1996, 2010, Oracle and/or its affiliates. All rights reserved.
Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

This completes the deployment process.

24. Repeat the same steps from 1.3.3 for deploying GWWS(gateway webservice),Gateway MDB & Gateway HTTP servlet



Deploying Application on WebLogic
[May] [2022]
Version 14.5.5.0.0

Oracle Financial Services Software Limited
Oracle Park
Off Western Express Highway
Goregaon (East)
Mumbai, Maharashtra 400 063
India

Worldwide Inquiries:
Phone: +91 22 6718 3000
Fax: +91 22 6718 3001
<https://www.oracle.com/industries/financial-services/index.html>

Copyright © [2007], [2022], Oracle and/or its affiliates. All rights reserved.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate failsafe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.