

# Oracle® Enterprise Manager

Enterprise Manager for Oracle Utilities

Administrative Guide

F70358-01

January 2023

---

Enterprise Manager for Oracle Utilities extends Oracle Enterprise Manager Cloud Control to allow monitoring and management of Oracle Utilities Application Framework-based products on remote servers.

When Enterprise Manager for Oracle Utilities is deployed, the following features and capabilities are available:

- Product discovery
- Target monitoring
- Environment assessment
- Environment cloning
- Patch identification and installation
- Patch migration from one environment to another
- View product configuration files

This document describes the various configuration and operational activities available to administrators of Enterprise Manager for Oracle Utilities.

NOTE: Prior versions of this product were released as Application Management Pack for Oracle Utilities. Please note that any references to Application Management Pack for Oracle Utilities that may occur within this document or in images within this document refer instead to the product's new name, Enterprise Manager for Oracle Utilities.

## Related Documentation and Resources

The **Help** menu provides links to **Enterprise Manager Help**, **Oracle Online Documentation**, **Oracle Online Forums**, and the **Oracle Technology Network (OTN)**, where the complete documentation for Oracle Enterprise Manager 12c is available.

This document and other Enterprise Manager for Oracle Utilities-specific documentation is available on the [Oracle Utilities](#) section of the **Oracle Technology Network (OTN)** documentation site.

Additional information on Oracle Enterprise Manager-specific features and functionality relating to this product is available in the [Enterprise Manager Cloud Control Documentation](#) (<http://docs.oracle.com/en/enterprise-manager/>).

---

**NOTE:** The documentation that accompanies this product is subject to revision and updating. Additional information that may relate to the functionality and features in this product may be found on My Oracle Support (MOS) at <https://support.oracle.com> (sign-in required). To find all articles relating to this product, enter the search term "Enterprise Manager for Oracle Utilities" (or for related articles, search on the product's previous name, "Application Management Pack for Oracle Utilities").

---

## Architecture

### Plug-in Architecture

The following diagram illustrates the Enterprise Manager for Oracle Utilities architecture.




Figure 1: Architecture

---

**NOTE:** \* The load balancer and multiple OMSes depicted in the diagram above are included only to indicate how a sample Enterprise Manager Cloud Control architecture would look in a large organization. They are not a prerequisite or a requirement for an Enterprise Manager system installation. If you do not have a load balancer, then the Management Agents communicate directly with the OMSes.

---

## Plug-in Functionality

### Product Discovery

Any manageable entity is of a *target type*. A specific instance of a target type is a target. For example, *sf-sunapp-00.us.oracle* would be a target of target type *host*; *sf-mydb-00:1521/CD0000SF* would be a target of target type *database*.

For extensibility purposes, Enterprise Manager for Oracle Utilities provides a discovery framework and the functionality to monitor an Oracle Utilities Environment system target type with target members of type web application, web services, batch server and ouaf

home. This models an installation of the Oracle Utilities Application Framework (OUAF) containing the software binaries and runtime components.

## High-Level View of the Discovery Process

The discovery process involves Oracle Utilities Application Framework (OUAF)-based products. Each environment comprises the files necessary for the operation of the web application, the database, and the threadpool worker. Thus, each OUAF-based environment and its runtime components can be modeled as an Enterprise Manager target that contains information about the following:

- Host (the machine on which the application server runs)
- Installed products and releases
- Web applications
- Database host (the machine on which the database runs)
- Database
- Batch servers and threadpool workers

This release of Enterprise Manager for Oracle Utilities is based on Java and offers tighter integration with the application server and enhanced features. To leverage some of these features, as well as to accommodate some of the newer features of Oracle Utilities Application Framework, Enterprise Manager for Oracle Utilities offers a new target model with new target types: System Environment, [Web Application](#), [Web Services](#), [Batch Server](#) and Oracle Utilities Home.

The Web Application and Web Services target types are closely modeled on the Application Deployment type offered by Fusion Middleware and use some of the regions already developed by the Fusion Middleware Enterprise Manager Plug-in. In addition, these two models use Java Management eXtension (JMX) MXBeans (such as JVMSystems, PerformanceStatistics) that are used for discovery and to collect metrics.

Batch Server is a standalone JVM that uses MXBeans for discovery and monitoring.

In addition to these target types, a typical OUAF-based environment is modeled as a system target. This system environment has as members the other new target types as well as the application server, where the Web Application Server and the Service Application Server are deployed and to which the OEM database instance connects.

The OUAF home target type page models the installation directory, also referred to as **SPLEBASE**. Given extensive use of JMX, it must be configured properly in the OUAF environment for discovery and performance monitoring to operate correctly.

## Environment Discovery

In order for a target to be monitored, it must first be discovered and promoted. Discovery is the process of making a target instance known to OEM. Once this has been done, the target needs to be promoted from an unmanaged to a managed state. This process requires some prerequisite steps.

---

**NOTE:** Oracle recommends after upgrading the plugin, delete existing targets and re-discover.

---

1. All components of the environment should be up, namely, the web application, the web service and batch servers.

2. JMX should be configured on the target environment. To test this, use jconsole and connect to the JMX servers using the JMX URLs. You can search the WebLogic log for the Web and EJB JMX URLs. Examples:


```
service:jmx:rmi:///jndi/rmi://{host}:{ejbJmxPort}/oracle/ouaf/
ejbAppConnector
service:jmx:rmi:///jndi/rmi://{host}:{webJmxPort}/oracle/ouaf/
webAppConnector
```

The threadpoolworker logs would have the batch JMX URLs. For example,  
service:jmx:rmi:///jndi/rmi://{host}:{batchJmxPort}/oracle/ouaf/  
batchConnector


In FW 2.2, this would be service:jmx:rmi:///jndi/rmi://{host} :  
{batchJmxPort}/spl/fw/jmxConnector

Make sure you can connect to the URLs and that the OEMTargetsBean is present, as illustrated in the following image:

**NOTE:** Here, the host should be fully qualified domain name.



Expand the OEMTargetsBean, click **Operations**, then click the **toXML** button. A window should pop up and return the XML of the targets that will be discovered. Do this for each JMX connection.



3. Target monitoring can be performed via JMX or REST API. You can prefer to use REST API option, if you have any firewall restrictions. Details, to enable "JMX over REST" feature, are available below.
  1. Run configureEnv using FW menu options, choose option 57 and provide appropriate values for the displayed variables.
  2. **JMX\_REST\_SERVICE\_FLAG: This flag in the Menu options is to enable the REST API. If this is false, then the communication happens using via JMX, the old way of the plugin communication.**
  3. **JMX\_REST\_SERVICE\_FLAG is true and JMX\_HTTPSSL\_FLAG false, the communication happens over the HTTP. JMX\_REST\_SERVICE\_FLAG is true and JMX\_HTTPSSL\_FLAG true, the communication happens over the HTTPS.**
  4. More details are available in respective Utilities FW product documentation.
4. The WebLogic domain/Fusion middleware must be discovered. To do this, perform the following:
  - The WebLogic admin server must be started. Verify that it is by logging into the WebLogic console.
  - Discover the WebLogic domain and Fusion middleware using guided discovery. On the grid console, go to **Setup > Add Targets > Add Targets Manually**. Select the following options on the page:


## Add Targets Manually

Page

### Overview

#### Add Host Targets




 **Install Agent on Host**

 **Install Agent Results**

Add Host targets by installing an agent using remote installation process. View status of past Agent installations.

#### Add Non-Host Targets Using Guided Process




 **Add Using Guided Process**

Run guided discovery on a host to find manageable targets. Choose to promote some or all discovered targets to become managed.

#### Add Non-Host Targets Using Declarative Process




 **Add Target Declaratively**

Add targets by explicitly specifying monitoring properties.

- Click **Add Using Guided Process**, enter the entries for the WebLogic admin server, then continue until the WebLogic domain/Fusion middleware is discovered.

If WebLogic is configured with SSL, use the **t3s** protocol.



To discover OUAF target environments:

1. Log in to Enterprise Manager.
2. Choose **Setup > Add target > Configure Auto Discovery**.




Figure 2: Selecting Auto Discovery

3. On the **Setup Discovery** page, click the host where discovery is to be run, then click the **Discovery Modules** button.

**ORACLE** Enterprise Manager Cloud Control 13c

Page Refreshed Dec 8, 2015 8:57:06 AM PST

## Setup Discovery

**Overview**

Automatic discovery is a process that detects hosts, virtual servers and other targets so that they can be monitored and managed by Enterprise Manager. Use the following options to configure and schedule automatic discovery.

**Configure Auto Discovery**

- Setup Network Scan Discovery
- Setup Discovery on Hosts

→

**Add Targets from Auto Discovery Results**

- Promote Discovered Targets
- Ignore Discovered Targets

→

**Add Targets Manually**

- Add Targets with Guidance
- Add Targets Declaratively

Servers, Storage and Network | **Targets on Hosts** | Advanced: Discovery Modules

**Search**

View | Collection Schedule | Diagnostic Details | Discover Now | Discovery Modules | Detach

Host	Collection Schedule	Discovered Targets	Managed Targets	Enabled Discovery Modules	Most Recent Ended On
↑ msp52072.us.oracle.com	Every 1 Day	16	3	5	✓ Dec 7, 2015 10:54:38 PM PST
↑ slc03mc.us.oracle.com	Every 1 Day	17	13	1	✓ Dec 8, 2015 3:16:00 PM PST
↑ slc05ynf.us.oracle.com	Every 1 Day	5	11	1	✓ Dec 1, 2015 2:16:24 AM PST
↑ slc06fdt.us.oracle.com	Every 1 Day	4	31	5	✓ Dec 7, 2015 1:35:04 PM PST

Figure 3: Setup Discovery

4. Ensure that the **Enterprise Manager for Oracle Utilities** module is on the **Discovery Module** list.



ORACLE Enterprise Manager Cloud Control 13c SYSMAN ▾ ...

**Discovery Modules : slc03rnc.us.oracle.com**  
 Configure discovery modules and parameters on this host.

View ▾

Discovery Module	En	Target Types	Discovery P
Enterprise Manager for Oracle Utilities Application	<input checked="" type="checkbox"/>	Oracle Utilities Batch Server, Oracle Utilities Home, Oracle Utilities Web Services	
OUAEnvironmentDiscovery	<input type="checkbox"/>	Oracle Utilities Batch Environment, Oracle Utilities Scheduler Environment	
Oracle Cluster and High Availability Service	<input type="checkbox"/>	Cluster, Oracle High Availability Service	
Oracle Database, Listener and Automatic Storage Management	<input type="checkbox"/>	Database Instance, Listener, Pluggable Database	
Oracle Fusion Middleware	<input type="checkbox"/>	Oracle WebLogic Domain	
Oracle Home Discovery	<input type="checkbox"/>	Oracle Home	
Oracle Secure Backup Domain	<input type="checkbox"/>	Oracle Secure Backup Domain	

*Figure 4: Verifying the module*

- Once back on the **Setup Discovery** page, select the host again to enable the buttons at the top. When the desired host is selected, click the **Discover Now** button.

**ORACLE** Enterprise Manager Cloud Control 13c

Setup Discovery Page Refreshed Dec 8, 2015 8:58:41 AM PST

**Overview**

Automatic discovery is a process that detects hosts, virtual servers and other targets so that they can be monitored and managed by Enterprise Manager. Use the following options to configure and schedule automatic discovery.

**Configure Auto Discovery**

- Setup Network Scan Discovery
- Setup Discovery on Hosts

**Add Targets from Auto Discovery Results**

- Promote Discovered Targets
- Ignore Discovered Targets

**Add Targets Manually**

- Add Targets with Guidance
- Add Targets Declaratively

Servers, Storage and Network **Targets on Hosts** Advanced: Discovery Modules

**Search**

View  Collection Schedule  Diagnostic Details  Discover Now  Discovery Modules  Detach

Host	Collection Schedule	Discovered Targets	Managed Targets	Enabled Discovery Modules	Most Recent Ended On
msp52072.us.oracle.com	Every 1 Day	16	3	5	✓ Dec 7, 2015 10:54:38 PM PST
slc03mc.us.oracle.com	Every 1 Day	17	13	1	✓ Dec 8, 2015 3:16:00 PM PST
slc05ynf.us.oracle.com	Every 1 Day	5	11	1	✓ Dec 1, 2015 2:16:24 AM PST
slc06fdt.us.oracle.com	Every 1 Day	4	31	5	✓ Dec 7, 2015 1:35:04 PM PST

Rows Selected 1 Hosts 7

Figure 5: Running the discovery

The **Target Discovery (Agent Based)** window opens.

- Click **OK** in the **Discover Now** dialog to confirm that you want to run the discovery.





Figure 6: Confirming the discovery

- A confirmation dialog appears on successful discovery of the host. Click **Close** to dismiss the confirmation dialog.



*Figure 7: Host discovery confirmation dialog*

## Promoting Targets

To promote targets so they can be managed:

1. Log in to Enterprise Manager.
2. Choose **Setup > Configure Auto Discovery**.

The **Setup Discovery** window opens. Go to the **Targets on Hosts** tab.

ORACLE Enterprise Manager Cloud Control 13c

Setup Discovery Page Refreshed Dec 8, 2015 8:57:06 AM PST

**Overview**

Automatic discovery is a process that detects hosts, virtual servers and other targets so that they can be monitored and managed by Enterprise Manager. Use the following options to configure and schedule automatic discovery.

**Configure Auto Discovery**

- Setup Network Scan Discovery
- Setup Discovery on Hosts

→

**Add Targets from Auto Discovery Results**

- Promote Discovered Targets
- Ignore Discovered Targets

→

**Add Targets Manually**

- Add Targets with Guidance
- Add Targets Declaratively

Servers, Storage and Network **Targets on Hosts** Advanced: Discovery Modules

**Search**

View Collection Schedule Diagnostic Details Discover Now Discovery Modules Detach

Host	Collection Schedule	Discovered Targets	Managed Targets	Enabled Discovery Modules	Most Recent Ended On
↑ msp52072.us.oracle.com	Every 1 Day	16	3	5	✓ Dec 7, 2015 10:54:38 PM PST
↑ slc03mc.us.oracle.com	Every 1 Day	17	13	1	✓ Dec 8, 2015 3:16:00 PM PST
↑ slc05ynf.us.oracle.com	Every 1 Day	5	11	1	✓ Dec 1, 2015 2:16:24 AM PST
↑ slc06fdt.us.oracle.com	Every 1 Day	4	31	5	✓ Dec 7, 2015 1:35:04 PM PST


Figure 8: Setup Discovery window

- For the host on which the discovery was run, click on the number that is in the **Discovered Targets** column.

## Setup Discovery

### Overview

Automatic discovery is a process that detects hosts, virtual servers and other targets so that they can be monitored and managed by Enterprise Manager. Use the following options to



Servers, Storage and Network **Targets on Hosts** Advanced: Discovery Modules

### Search

View  Collection Schedule  Diagnostic Details

Host	Collection Schedule	Discovered Targets	Managed Targets	Enabled Discovery Modules	Most Recent Ended On
msp52072.us.oracle.com	Every 1 Day	16	3	5	Dec 7, 2015 10:54:38 PM PST
slc03rnc.us.oracle.com	Every 1 Day	22	8	1	Dec 8, 2015 6:19:48 PM PST
slc05ynf.us.oracle.com	Every 1 Day	<a href="#">View discovered targets on host</a>			Dec 1, 2015 2:16:24 AM PST
slc06fdt.us.oracle.com	Every 1 Day	4	31	5	Dec 7, 2015 1:35:04 PM PST
slc06qad.us.oracle.com	Every 1 Day	7	15	1	Dec 6, 2015 2:41:35 PM PST
slc06wud.us.oracle.com	Every 1 Day	5	9	0	May 14, 2015 11:35:08 PM PDT
slc07gzp.us.oracle.com	Every 1 Day	10	19	0	Dec 1, 2015 3:18:46 AM PST

Figure 9: Choosing a target

4. A list of targets that were discovered but not yet promoted is displayed. Select the target you want to promote, then click the **Promote** button.

ORACLE Enterprise Manager Cloud Control 13c

Enterprise Targets

### Auto Discovery Results

Overview

Review discovered targets and promote targets to be managed by Enterprise Manager.

**Configure Auto Discovery**

- Setup Network Scan Discovery
- Setup Discovery on Hosts

**Add Targets from Auto Discovery Results**

- Promote Discovered Targets
- Ignore Discovered Targets

**Add Targets Manually**

- Add Targets with Guidance
- Add Targets Declaratively

Servers, Storage and Network (0) **Targets on Hosts (50)** Ignored Targets (0)

Search

View Promote Rename Delete Ignore Detach

Target Name	Environment	Discovered On
V231_CCB_OEM_LIN_ORA_WLS_slc03mc.us.oracle.com_batch	Oracle Utilities Batch Server	Dec 8, 2015 10:19:50 AM PST
V231_CCB_OEM_LIN_ORA_WLS_slc03mc.us.oracle.com_home	Oracle Utilities Home	Dec 8, 2015 10:19:50 AM PST
V231_CCB_OEM_LIN_ORA_WLS_slc03mc.us.oracle.com_service	Oracle Utilities Web Services	Dec 8, 2015 10:19:50 AM PST
V231_CCB_OEM_LIN_ORA_WLS_slc03mc.us.oracle.com_web	Oracle Utilities Web Application	Dec 8, 2015 10:19:50 AM PST
agent12c1_2_slc03mc.us.oracle.com	Oracle Home	Sep 17, 2015 12:34:35 PM PDT
agent12c2_11_slc03mc.us.oracle.com	Oracle Home	Sep 17, 2015 12:34:35 PM PDT

Figure 10: Promoting the target

- All related members of the target system are shown and promoted at the same time. Click the **Promote** button.

ORACLE Enterprise Manager Cloud Control 13c

Enterprise Targets

Promote OUAF System Target

Select the system target and click Promote. 266800CB2A21403FE05326AFF504B11B

Promote Cancel

View

Target Type	Target Name	Host Name	Install Directory	Select
oracle_ouaf_system_util_env	V231_CCB_OEM_LIN_ORA_WLS_slc03mc.u...			<input checked="" type="checkbox"/>
oracle_ouaf_webapp_util_env	V231_CCB_OEM_LIN_ORA_WLS_slc03mc.u...	slc03mc		<input checked="" type="checkbox"/>
oracle_ouaf_service_util_env	V231_CCB_OEM_LIN_ORA_WLS_slc03mc.u...	slc03mc		<input checked="" type="checkbox"/>
oracle_ouaf_home_util_env	V231_CCB_OEM_LIN_ORA_WLS_slc03mc.u...			<input checked="" type="checkbox"/>
oracle_ouaf_batch_util_env	V231_CCB_OEM_LIN_ORA_WLS_slc03mc.u...			<input checked="" type="checkbox"/>

Figure 11: Unmanaged system targets

- A confirmation dialog appears when the promotion is successful.



*Figure 12: Confirmation dialog*

7. Click **Close** to dismiss the confirmation dialog.
8. If any changes are made to the environment configuration using the command-line utilities (e.g., `configureEnv.sh/cmd`), the corresponding changes must also be made to the target properties. The quickest way to do this is to remove the target and perform the discovery and promotion process. You can also make changes by choosing **Target > Setup > Monitoring Configuration** and making the appropriate updates on the UI page.



Figure 13: Monitoring Configuration page

## Post-Promotion Tasks

The following tasks are required after a target is promoted.

1. **Configure monitoring credentials.** This task creates the monitoring credentials for the web application, web services, and batch server targets. It involves navigating to **Setup > Security > Monitoring Credentials** and enter the JMX credentials for all three target types. For example, the following steps configure the credentials for the batch server. Follow the same steps for the web application and web services targets.
  - a) Select the target type and click the **Manage Monitoring Credentials** button.



**ORACLE** Enterprise Manager Cloud Control 13c

## Security

### Monitoring Credentials

Select target type and click Manage Monitoring Credentials to set/view monitoring credentials for target in

Target type  Search

[Manage Monitoring Credentials](#)

Target Type	Total Targets
Listener	1
OMS and Repository	1
Oracle HTTP Server	1
Oracle Management Service	1
Oracle Utilities Batch Server	1
Oracle Utilities Web Application	1
Oracle Utilities Web Services	1
Oracle WebLogic Domain	6
Oracle WebLogic Server	12

b) Select the target and click the **Set Credentials** button.

**ORACLE** Enterprise Manager Cloud Control 13c Enterprise ▾

## Security

Monitoring Credentials > Oracle Utilities Web Application

### Oracle Utilities Web Application Monitoring Credentials

Select row and click Set Credentials to edit credentials.  
Use the emcli create\_credential\_set verb with -monitoring option to create additional credential sets.

Target Name  Credential Set  Search

[Set Credentials](#) [Clear](#) [Test](#)

Target Name	Status	Credential Set
V231_CCB_OEM_LIN_ORA_WLS_slc03rnc.us.oracle.com_web	↑	OUAF JMX Credentials

c) Enter the JMX credentials. This should match the JMX credentials of the OUAF environment.

ORACLE Enterprise Manager Cloud Control 13c Enterprise ▾

## Security

Monitoring Credentials > Oracle Utilities Web Application


### Oracle Utilities Web Application Monitoring Credentials

Select row and click Set Credentials to edit credentials.  
Use the emcli create\_credential\_set verb with -monitoring option to create additional credential sets.

Target Name  Credential Set

Target Name	Status	Credential Set	Target
V231_CCB_OEM_LIN_ORA_WLS_slc03rnc.us.oracle.com_web	↑	OUAF JMX Credentials	

- d) Repeat for the Web application and Web services targets.
2. **Set up monitoring configuration.** For all Framework version 2.2.0-based environments, ensure that the target monitoring configuration contain the appropriate settings for Java Home and Oracle Home, Web Server Home and Web Server Java Home values. These are the environment variables that are set in the host before you run splenviron.cmd/sh. Note that Web Server Home is the location on which the WebLogic software is installed (e.g., /spl/middleware10.3.3./wlserver\_10.3). Web Server Java Home is the Java location that is used as JAVA\_HOME by the Web Server. For WebLogic servers on Linux, it is same value as JROCKIT\_HOME. Set up monitoring configuration for all target types.
- a) For example, to setup the monitoring configuration for the batch server, first click on the target dropdown on the upper left, then choose **Target Setup > Monitoring Configuration.**



b) Then enter the appropriate information:



c) Repeat for the Web application and Web services targets.

## Viewing a Target's Home Page

To view a target's home page:

1. Log in to Enterprise Manager.
2. Click **Targets** > **All Targets**.




Figure 14: Viewing all targets

3. To view its home page, locate and double-click a target from the sortable and searchable **All Targets** list.

ORACLE Enterprise Manager Cloud Control 13c

Enterprise Targets

All Targets

Auto Refresh Off Page Refreshed Dec 8, 2015 4:15:28 PM PST

Refine Search

Target Type

- Applications
  - Oracle Utilities Batch Server (1)
  - Oracle Utilities Environment (1)
  - Oracle Utilities Home (1)
  - Oracle Utilities Web Application (1)
  - Oracle Utilities Web Services (1)
- Cloud
  - Oracle Cloud (1)
- Databases
  - Database Instance (1)
  - Listener (1)
- Groups, Systems and Services
  - Database System (1)
  - EM Service (2)
  - Generic Service (2)
  - Generic System (1)
  - Management Servers (1)
- Middleware
  - Application Deployment (33)
  - Clustered Application Deployment (3)
  - Java Virtual Machine (1)
  - Java Virtual Machine Pool (1)
  - Metadata Repository (2)
  - Oracle Fusion Middleware Farm (1)
  - Oracle HTTP Server (1)

View Search Target Name

Target Name	Target Type	Target Status
slc06fdt.us.oracle.com	Host	↑
slc06fdt.us.oracle.com:3872	Agent	↑
slc06fdt.us.oracle.com:4889_Management_Service	Oracle Management Service	↑
slc06fdt.us.oracle.com:4889_Management_Service_CONSOLE	OMS Console	↑
slc06fdt.us.oracle.com:4889_Management_Service_FBS	OMS Platform	↑
slc06qad.us.oracle.com	Host	⚠
slc06qad.us.oracle.com:3872	Agent	⚠
slc06wud.us.oracle.com	Host	↑
slc06wud.us.oracle.com:1830	Agent	↑
slc07gzp.us.oracle.com	Host	↑
slc07gzp.us.oracle.com:3872	Agent	↑
Subnet-10.242.80.0/21	Systems Infrastructure Network	N/A
Subnet-10.244.152.0/21	Systems Infrastructure Network	N/A
Subnet-2606.b400.2010.504a.0.0.0.0/64	Systems Infrastructure Network	N/A
Subnet-2606.b400.2010.604d.0.0.0.0/64	Systems Infrastructure Network	N/A
V231_CCB_OEM_LIN_ORA_WLS_slc03mc.us.oracle.com	Oracle Utilities Environment	N/A
V231_CCB_OEM_LIN_ORA_WLS_slc03mc.us.oracle.com_batch	Oracle Utilities Batch Server	↑
V231_CCB_OEM_LIN_ORA_WLS_slc03mc.us.oracle.com_home	Oracle Utilities Home	N/A
V231_CCB_OEM_LIN_ORA_WLS_slc03mc.us.oracle.com_service	Oracle Utilities Web Services	↑
V231_CCB_OEM_LIN_ORA_WLS_slc03mc.us.oracle.com_web	Oracle Utilities Web Application	↑
WebLogicServer10_3_6_0_slc05mf.us.oracle.com_4966	Oracle Home	N/A
WebLogicServer10_3_6_0_slc06fdt.us.oracle.com_9176	Oracle Home	N/A
WebLogicServer10_3_6_0_slc06qad.us.oracle.com_4008	Oracle Home	N/A
WebLogicServer10_3_6_0_slc06wud.us.oracle.com_4008	Oracle Home	N/A
webtier12c1_23_slc06fdt.us.oracle.com	Oracle Home	N/A

Figure 15: All Targets list

# Environment Target Home Page




Figure 16: Environment Target Home Page

In the **All Targets** list under **Applications** you can find the target type **Oracle Utilities Environment** targets. This is a system target whose members comprise other targets that make up the. The page is divided into five regions. The regions are:

- **System Properties.** Contains basic information about the system.
- **System Availability.** Contains a list of all members of the system including availability.
- **Job Summary.** Contains summary information about job executions. This includes counts of all target members of the system.
- **Job Activity.** This region lists all submitted jobs.
- **Incidents & Problems.** *Problems* are classified as issues that cause the plug-in to malfunction or throw errors and exceptions. *Incidents* are issues that need not necessarily impact plug-in operations, but are related to the target being monitored. Most incidents are thrown when certain defined criteria, such as thresholds, are met. If, for example, the administrator sets a threshold of 95 percent for disk space usage, an incident is reported when that level of usage is exceeded.

## Oracle Utilities Application Framework Target Home Page

The OUAF target home page models the installation directory, also referred to as **SPLEBASE**. There is no system availability as this metric is not applicable to directories. It contains the following regions.

- **System Properties.** Contains basic information about the ouaf home directory.
- **Job Summary.** Contains summary information about job executions.
- **Job Activity.** This region lists all submitted jobs.
- **Incidents & Problems.** *Problems* are classified as issues that cause the plug-in to malfunction or throw errors and exceptions. *Incidents* are issues that need not necessarily impact plug-in operations, but are related to the target being monitored. Most incidents are thrown when certain defined criteria, such as thresholds, are met. If, for example, the administrator sets a threshold of 95 percent for disk space usage, an incident is reported when that level of usage is exceeded.
- **Incident Summary.** Summary information and messages regarding incidents recorded.

## Ensure Collection of Installed Product Configuration Information

Many of the features in this product rely on information about products that have been installed. This is collected as part of the Enterprise Manager's Metric Configuration Collection. To ensure that this has been collected (and to avoid execution errors on certain features), go to **Target > Configuration > Last Collected** from the **Target Home** page, then choose **Actions > Refresh**. This action triggers a refresh of the configuration metrics so that the common information region is complete.

Oracle Utilities Home ▾

Clone

Patch Import

Patch Install

Patch Migrate

- Home
- Open the home page in a new window.
- Monitoring ▸
- Diagnostics ▸
- Control ▸
- Job Activity
- Information Publisher Reports
- Configuration ▸
- Compliance ▸
- Target Setup ▸
- Target Sitemap
- Target Information

- Last Collected
- Comparison & Drift Management
- Compare...
- Search...
- History
- Save...
- Saved
- Topology

Updated in last 7 days 0

	-	-	-	-
	-	-	-	-
	-	-	-	-
	-	-	-	-

Total Open 0

Platform x86\_64  
Operating System Linux  
Environment ID slc03rnc.us.oracle.com\_8700  
Environment Name V231\_CCB\_OEM\_LIN\_ORA\_WLS

Figure 17: Collecting Target Configuration






Figure 18: Configuration Properties

## Target Home and Performance Monitor Pages

The system members that gather performance information are the runtime targets with target type web application, web services, and batch server. Their target home pages contain performance metrics and other information pertinent to the particular target type.

Target monitoring can be performed via JMX or REST API. You can prefer to use REST API if you have firewall restrictions. Details, to enable "JMX over REST" feature, are available in Installation documentation.

## About Performance Monitors

Application deployments that are available for discovery in Enterprise Manager for Oracle Utilities include managed beans (MBeans) that are accessed with Java Management Extensions (JMX) to retrieve metrics and measurements for batch and application-level performance monitoring.

Three target types—[Web Application](#), [Web Services](#), and [Batch Server](#)—contain the connection information among their properties to allow collection of detailed statistics over JMX.

## The Web Services Home Page

The Web Services Home page comprises five regions:

- **Called Services:** This region lists the services that were called along with such metrics as Minimum, Maximum, and Average execution times, number of times called, and information about the last call. It also has the following three command buttons:

- **Add to Watchlist:** You can select certain services to watch and click the "Add to Watchlist" button to add it to the **Service Watchlist** area.
- **Refresh:** Refreshes the **Called Services** table from the server.
- **Reset Statistics:** Resets all the counters to zero; it will also re-initialize the **Called Services** list.
- **Service Watchlist:** This table displays the list of services that you would like to watch. It supports a **Delete** button to remove the service from the watchlist.
- **Graph Area:** Displays the **Status** of the service. This is a customizable area in which the customer can add various monitoring charts. By default it displays the **Status** of the Business Application Service.

The screenshot displays the Oracle Enterprise Manager Cloud Control 13c interface. At the top, the Oracle logo and 'Enterprise Manager Cloud Control 13c' are visible. The main content area is titled 'Called Services' and includes a table with the following data:

Select	Service Name	Service Type	Min Time	Max Time	Average Time	Num
<input type="checkbox"/>	CILENMP	READ	6.0	763.0	263.3333333333333	3
<input type="checkbox"/>	CILESOP	READ	30.0	8632.0	2903.6666666666665	3
<input type="checkbox"/>	F1-OEMWEBTARGET	READ	64.0	64.0	64.0	1
<input type="checkbox"/>	Manul.comService	READ	746.0	746.0	746.0	1

Below the table is a 'Service Watchlist' section with a 'Delete' button and a table with columns 'Service Name' and 'Service Type'. The watchlist is currently empty, showing 'No Data Available'. To the right of the watchlist is a 'Service Name:' graph area with a line chart showing a constant value of 1.0 over time. The x-axis represents time from 12:00 AM to 09:00 on December 08, 2015. A 'Table View' button is located at the bottom right of the graph area.

Like other monitoring pages in this release, this UI is customizable. The user can customize the UI by clicking the **Customize** icon at the top right hand corner:



Both the layout and content of the page can be changed.

## Web Application Home Page

The Web Application target type uses the JVMSystems MBean's ThreadMXBean and MemoryMXBean to retrieve the following performance metrics:

- **From ThreadMXBean:**

- ThreadCount
- PeakThreadCount
- DaemonThreadCount
- CurrentThreadCPUTime
- CurrentThreadUserTime
- **From MemoryMXBean:**
  - HeapMemoryUsage(init)
  - HeapMemoryUsage(max)
  - HeapMemoryUsage(used)
  - NonHeapMemoryUsage(init)
  - NonHeapMemoryUsage(max)
  - NonHeapMemoryUsage(used)

The Web Application Server Home page comprises four regions:

- **General Information Region:** This is the summary of the overall status of the Web Application. It tracks close to the General Information Region in the J2EE Application Server target home. The information is extracted from **ServerRuntimeMBean**. This region reuses the Deployment Summary Region provided by the Fusion Middleware Plug-in.
- **Response And Load** shows a simple graphic indicating historic availability and load.
- **Performance Region:** This region contains performance information collected from ServletRuntimeMBean, WsseOperationRuntimeMBean, and WebAppComponentRuntimeMBean for various JSP pages. This region reuses the Most Requested Region provided by the Fusion Middleware Plug-in.
- **JVM Statistics Region:** This region displays a set of standard JVM statistics acquired from JVMSystems MBeans in a chart format. The user can customize these graphs to display any of the other metrics that are collected.




Figure 19: Web Application Home page

Like other monitoring pages in this release, this UI is customizable. The user can customize the UI by clicking the **Customize** icon in the top right-hand corner:



Both the layout and content of the page can be changed.

## Batch Server Home Page

The Batch Server Home Page allows you to monitor thread pools, nodes, and batch process details.

Batch processes are monitored using Java Management Extensions (JMX), which is provided by the Oracle Utilities Application Framework (OUAF), and performance monitoring is supported only for products that are based on OUAF 2.2 or later.

In addition to monitoring batch processes, this feature can shut down thread pools, cancel thread operations, and provides an option to set alerts based on batch metrics.

## Configuring and Connecting to JMX on an OUAF-based Product

Use this procedure only for monitoring performance for products that are based on OUAF 4.2 or later. Using it for other products will cause the process to abort with an "Operation not supported" error.

1. Obtain BATCH\_RMI\_PORT and other variables from the ENVIRON.INI file as described in the following table.

**Table 1: Common Information for JMX Connections**

Field	Comment	Source
Batch Mode	Execution Mode	BATCH_MODE (ENVIRON.INI)
Cluster Address	Cluster Address	COHERENCE_CLUSTER_ADDRESS (ENVIRON.INI)
Cluster Port	Cluster Port	COHERENCE_CLUSTER_PORT (ENVIRON.INI)
Batch JMX Port	RMI Port for connection	BATCH_RMI_PORT (ENVIRON.INI)
Online Batch Enabled	Whether Online Batch is enabled	BATCHENABLED (ENVIRON.INI)
Online Batch Threads	Number of threads allocated to DEFAULT threadpools	BATCHTHREADS (ENVIRON.INI)
Online Batch Daemon	Whether Online Batch Daemon is enabled	BATCHDAEMON (ENVIRON.INI)

2. Obtain the JMX user name and password from the following files contained in SPLEBASE/scripts:

- **Access file:** ouaf.jmx.access.file
- **Encrypted password file:** ouaf.jmx.password.file.

3. Connect to JMX using the Java API class `javax.management.remote (JMXConnector, JMXServiceURL)`.

- If connecting to a batch server target, use the URL:

```
jmx:rmi:///jndi/rmi://server:port/spl/fw/jmxConnector
```

- If connecting to a web application target, use the URL:

```
jmx:rmi:///jndi/rmi://server:port/oracle/ouaf/webAppConnector
```

- If connecting to a web services target, use the URL:

```
jmx:rmi:///jndi/rmi://server:port/oracle/ouaf/ejbAppConnector
```

If BATCH\_RMI\_PORT is not available, the error message "JMX support not configured" is issued. If a connection is not available, the error message "JMX Service not available" is issued.

4. Use the following stub/beans to obtain values from the server:

- `com.splwg.base.support.batch.management.ActiveBatchMBean`
- `com.splwg.base.support.batch.management.ActiveBatchJobMBean`
- `com.splwg.base.support.batch.management.ActiveClusteredNodeMBean`
- `com.splwg.base.support.batch.management.ActiveCobolBatchThreadMBean`
- `com.splwg.base.support.batch.management.ActiveGridNodeMBean`
- `com.splwg.base.support.batch.management.ActiveJavaBatchThreadMBean`

---

## Viewing and Managing Batch Processes

The Batch Monitor page comprises four sections:

- [Common Information](#)
- [Threadpool Summary](#)
- [Active Batch Jobs](#)
- [Batch Details](#)

**Common Information** Flush All Caches

Cluster Name: CLUST\_11824 Cluster Address: 230.44.11.148 Cluster Port: 11825  
Batch Mode: CLUSTERED Batch Daemon: false Batch RMI Port: 11824

**Threadpool Summary** Shutdown Threadpool

Pool Name	Number of Threads	Number of Members
No Data Available		

**Active Batch Jobs** Cancel Threads Refresh Reset Table

View Detach

Threadpool	JVM Name	Node	PID	Date Time Started	Elapsed Time	Status	User	Thread	Batch Worker
No Data Available									

**Batch Details** Cancel Thread Refresh

**Summary**

Batch Code:  
Batch Description:  
Thread:  
Thread Limit:  
Batch Number:  
Program Name:  
Program Type:  
Run Type:

**Performance Summary**

Elapsed Time:  
Date Time Started:  
Max Execution Attempts:  
Cancel Requested:  
Requested By:  
Records Committed:  
Records in Error:  
Work Unit Size:

Figure 20: Batch Monitor page

### Common Information

This section displays information about the cluster you are connected to. It includes the **Cluster Name**, **Cluster Address**, and **Cluster Port**. The section is populated automatically when the page is loaded. **Flush All Caches** flushes all Cache information within the cluster.

## Threadpool Summary

This section displays the individual threadpool workers that are up and running and which belong to this cluster.

The following table describes each of the columns in the summary.

**Table 2: Threadpool Summary**

Field	Comment	Attribute
ThreadPool	Name of Thread pool	Name
Available Threads	Available number of Threads	AvailableThreads
Members	Number of Active Members	NumberOfMembers

The section also offers a button to shut down a selected threadpool worker.

## Active Batch Jobs

The Active Batch Jobs section displays all currently active batch jobs. This is displayed in the form of a table with the following fields:

**Table 3: Batch Bean**

Field	Comment	Source
Thread Pool	Name of Threadpool	DistThreadPool
JVM Name	Name of JVM	Inherited from previous call
Node	Node running on	Inherited from previous call
Thread	Thread Number	ThreadNumber
Batch Number	Batch Run Number	BatchNumber
Date Time Started	Date Time Job Started	DateTimeStarted
Elapsed Time	Elapsed time since job started	ElapsedTime
Status	Status of Job	Status
User	User used to run job	UserId

When you click on an active batch job, its details populate in the **Batch Details** section.

This section also supports the following actions via buttons:

- **Cancel Threads:** Kills the selected batch job.
- **Refresh:** Refreshes the list of active batch jobs.
- **Reset Table:** Same as Refresh, except it cleans up the list and reloads it.

## Batch Details

This section displays all details about the batch job selected in the **Active Batch Job** section. The following table describes the displayed fields:

**Table 4: Batch Detail**

<b>Field</b>	<b>Comment</b>	<b>Source</b>
<b>Summary</b>		
Batch Code	Batch Control Id	BatchCd
Thread	Thread Number	ThreadNumber
Thread Limit	Max number of threads	ThreadCount
Batch Number	Batch Run Number	BatchNumber
Program Name	Program running	ProgramName
Run Type	Type of Run	RunType
Execution Strategy	Execution Commit Strategy	ExecutionStrategyClass
<b>Common Parameters</b>		
Language	Language Code used	LanguageCd
Maximum Commit Records	Commit Frueqency	MaximumCommitRecords
Maximum Timeout (min)	Commit Timeout	MaximumTimeoutMinutes
Business Date	Business Date used for job	ProcessDate
ReRun Number	Rerun Number for reruns	RerunNumber
Thread Pool	Thread Pool allocated to	DistThreadPool
Name	JVM Name	
UserId	User Running Job	UserId
Trace Program Start	Is Tracing on for Start of job?	TraceProgramStart
Trace Program End	Is Tracing on for End of job?	TraceProgramEnd
Trace SQL	Is Tracing on for all SQL in job?	TraceSQL
Trace Standard Out	Is Tracing on for debug messages for job?	TraceStandardOut
<b>Performance Summary</b>		
Elapsed Time	Elapsed Time since start	ElapsedTime
Date Time Started	Date Time Job started	DateTimeStarted
Max Execution Attempts	Number of executions	MaxExecutionAttempts
Cancel Requested	If job has been cancelled recently	CancelRequested
Requested By	If CancelRequested = true then OS userid of person who requested the cancel	CancelRequestedBy
Records Committed	Number of records processed so far	RecordsCommitted
Records in Error	Number of records in Error so far	RecordsInError
Work Unit Size	Size of Work unit within Execution Strategy	WorkUnitSize
Work Unit Size This Run	Work Unit used for this run	WorkUnitSizeThisRun
Work Units Committed	Work Units Committed so far	WorkUnitsCommitted
Work Units In Error	Work Units errored so far	WorkUnitsInError



Field	Comment	Source
Work Units Processed	Work Units processes so far	WorkUnitsProcessed
<b>Additional Parameters (List of parameters from SoftParameters)</b>		
Parameter	Parameter Name	Element before = in array
Value	Parameter Value	Element after = in array

The thread details are part of default collections, and only when a **Refresh** button is clicked will the details be refreshed by calling a job or by getting the latest information from the default collections.

## Target Control Operations

The target controls provide access to common operations performed by the administrator. It includes buttons to start and stop the application server and batch server. These buttons are available on the applicable target home page and on the target control submenu.





Figure 21: Common Target Controls

Based on the target type, you can view log and configuration files, assess a target, clone an ouaf home target (application server only), or manage the installation or migration of patches. These features can be found on the target control submenu.



*Figure 22: Procedure-based Target Control Operations*

These are job-based or deployment procedure-based operations that run the appropriate utilities that an administrator would normally submit from the command line. As such, it is the administrator's responsibility to ensure that jobs submitted do not conflict with each other. For example, during patch installation, the Start button will still be available, so if a start job is submitted, that operation will interfere with the running patch process (and vice-versa).

The following sections describe the various features available using start/stop and the target controls.

### **Start/Stop**

Start and Stop allows the operator to start or stop a given target. The start/stop buttons are prominently displayed on the target home page.

### **View Logs**

The View Logs feature allows the operator to view the contents of log files generated at the application server level.

### **View Configuration Files**

The View Configuration Files function lets the operator view the contents of configuration files used by the application server.

## Clone

The Clone function lets the operator clone the current environment (application server only).

## Assess

The Assess function assesses an environment's configuration.

## Import Patches

Patching an environment involves three steps:

1. Download the patches from My Oracle Support (performed manually outside of Enterprise Manager for Oracle Utilities).
2. Import the patches into Enterprise Manager for Oracle Utilities (via the **Import Patches** button on the **Common Operations** panel).
3. Install/Migrate the patches.

The Import Patches function must be used for the second step. This function is required for patch installs and patch migration within the Enterprise Manager for Oracle Utilities plug-in.

## Install Patches

The Install Patches function is used to install patches that have already been imported into the Enterprise Manager for Oracle Utilities plug-in in the current environment.

## Migrate Patches

The Migrate Patches function is a special form of patch installation wherein a source environment is compared to a destination environment. The source environment is used to identify patches that the administrator intends to install in the current/destination environment. The identified patches should have been imported previously for the current target's product, release and platform.

# Detailed Description of Target Control Operations

## Start/Stop

As mentioned earlier, start/stop allows operators to startup/shutdown a target. In a way, it also confirms that the environment is properly installed by checking that the configuration files contain all the values necessary to bring up/down the environment. These are available on the target home pages for the batch server target types.

These buttons open a dialog in which the administrator enters the credentials to connect to the server for the purpose of either starting or stopping the target. For the web application and web services, we need to use the “Application Deployment” targets discovered using the Oracle Fusion middleware/weblogic domain plugin.




Figure 23: Credentials Input

The types of credentials that can be selected are:

- Credentials to connect to the host on which environment is running (e.g., `cissys` or `oracle`)
- Credentials that were used to configure the environment (e.g., `cissys`)

You can either enter these values or select a saved credential.

When credentials are entered, clicking **OK** executes the selected command (**Start** server or **Stop** server). Clicking **Cancel** or closing the dialog exits without starting (or stopping) the server.

---

**NOTE:** The **Start/Stop** buttons submit jobs that perform the same function provided by the `sp1.sh/sp1.cmd` start/stop command-line utility. Thus, the environment in which you are working must be set up so that these utilities are available and properly functioning.

---

## Environment Assessment

Environment assessment allows administrators to perform basic validation of correct installation of Oracle Utilities Application Framework Home target page.

The following files, settings, and definitions are checked:

- Correct positioning of key files
- Key configuration settings

- Correct setting of security definitions
- Patch validation

To assess the current environment:

1. Open the Oracle Utilities Application Framework Home target page. On the **Target** dropdown, choose **Control** > **Assess**.




Figure 24: OUAF Home Target page: Assess

2. On the **Credentials** page, choose a set of saved credentials or enter your user name and password, then click **Next** to proceed.
3. You will be directed to the **Job Activity** page, where you can view the results of the assessment job.




Figure 25: Environment Assessment: Result

4. Click **Finish** to return to the Oracle Utilities Application Framework Home target page.

## Environment Cloning

Environment cloning allows operators or administrators to duplicate the application server portion of any Oracle Utilities Application Framework-based environment, creating new environments using the same software and definitions that exist on the source server.

Two cloning options are available:

- **Simple** cloning copies software and existing parameters to a target environment using minimal specifications. It can be particularly useful for backing up an existing environment prior to applying patches.
- **Advanced** cloning lets you modify configuration information—memory arguments, installation software locations, batch configurations for coherence settings, etc.—to create new environments with new characteristics. Other configuration changes, such as web application server-related credentials, must be changed after the cloning operation is complete by running the `configureEnv` command line utility.

**NOTE:**

- To minimize performance issues, the clone of an environment must be on the same host as the original environment. Only the application server is cloned, not the database.
- Immediately after cloning, ensure that the application server clone is connecting to the new database/schema. If the database/schema is not shared by other application server components, clear the F1\_TSPACE\_ENTRY table entries in the new database/schema as follows:

1. Shut down the environment.
2. Connect to the database with sqlplus or similar utility and run the following SQL statement:

```
delete * from F1_TSPACE_ENTRY where TSPACE_ENTRY_TY='OEM_TARGET'
```

3. Restart the environment.
- 

## Environment Cloning: Simple Clone

To clone an environment using the simple method:

1. Open the **Target UI Home Page** dropdown list and choose **Control > Clone**.




Figure 26: Simple Cloning: Select Clone

2. On the **Clone Type** page, choose **Simple Clone** from the dropdown list, then click **Next** to proceed.




Figure 27: Simple Cloning: Select Clone Type

3. On the **Credentials** page, choose a set of saved credentials or enter your user name and password, then click **Next** to proceed.



ORACLE Enterprise Manager Cloud Control 13c

Progress bar: Credentials (selected), Details, Schedule, Confirm

### Clone Environment (Simple): Credentials

▲ Credentials Input

**Host Credentials**

Credential:  Preferred  Named  New

Preferred Credential Name: Normal Host Credentials

Credential Details: Credentials will be determined at runtime.

**OUAF Credentials**

Credential:  Preferred  Named  New

Preferred Credential Name: OUAF Agent Credentials

Credential Details: Credentials will be determined at runtime.

**Figure 28: Simple Cloning: Enter Credentials**

4. On the **Details** page, provide the name and mount point for the new environment, a description of the environment, and the listed port numbers according to the screen. Other options on the target environment will match the source environment. Select the first check box if you want to restart the source environment. Select the second checkbox if you want to generate a new environment ID for the clone environment.

ORACLE Enterprise Manager Cloud Control 13c

Credentials Details Schedule Confirm

### Clone Environment (Simple): Details

#### Details

Restart  Restart source environment when cloning is complete?

Environment ID  Generate new environment ID?

#### Environment Installation Options

\* New Environment Name

\* Environment Mount Point

#### Description

\* Environment Description

#### Web Application Server Configuration

\* Web Server Port Number

Web Server Administration Port Number (Optional)

#### JMX Configuration

\* Web JMX Port No.

\* Service/Business JMX Port No.

\* Batch JMX Port No.

**Figure 29: Simple Cloning: Enter Details for Web and Batch Targets**

If the source environment has both web and batch targets, you must also enter the Web Server Port Number, Web JMX Port Number, Batch JMX Port Number, Service/Business JMX Port Number, and an optional Web Server Administration Port Number.



Credentials    **Details**    Schedule    Confirm

### Clone Environment (Simple): Details


<b>Environment ID</b>	Generate new environment ID? <input type="checkbox"/>
<b>Environment Installation Options</b>	
* New Environment Name	<input type="text"/>
* Environment Mount Point	<input type="text"/>
<b>Description</b>	
* Environment Description	<input type="text"/>
<b>Web Application Server Configuration</b>	
Web Server Port Number	<input type="text"/>
Web Server Administration Port Number (Optional)	<input type="text"/>
<b>JMX Configuration</b>	
Web JMX Port No.	<input type="text"/>
Service/Business JMX Port No.	<input type="text"/>
* Batch JMX Port No.	<input type="text"/>

Figure 30: Simple Cloning: Enter Details for Batch-Only Target

If the source environment has only a batch target, the Web Server Port Number, Web JMX Port Number, Service/Business JMX Port Number, and the optional Web Server Administration Port Number are disabled, and you need only provide the Batch JMX Port Number.


Click **Next** to proceed after all required details are entered.

5. On the **Schedule** page, choose to either perform the clone operation **Now** or **Later**. Click **Schedule** to complete the process and submit the cloning job.




**Figure 31: Simple Cloning: Scheduling**

If the source environment has both web and batch targets, the dialog box will prompt you to run `iwsdeploy.sh` manually after cloning to deploy IWS if and *only* if Web services have been enabled in the source environment.



**Figure 32: Simple Cloning: Confirmation Dialog for Web and Batch Targets**

If the source environment has only a batch target, the dialog box will simply ask you if you want to view the execution status.



*Figure 33: Simple Cloning: Confirmation Dialog for Batch-Only Target*

Simple cloning allows you to create a copy of an environment and start it for testing (since you can change the web port number). In order to make more complex configuration changes after creating a simple clone, the operator must set the appropriate values on the target environment by running the `configureEnv.sh` command-line utility. The operator must, for example, ensure that coherence settings are properly set up if clustered mode is being used.

---

**NOTE:**

After creating a clone, be sure to perform all the steps necessary to discover and promote the clone.

---

## Environment Cloning: Advanced Method

To clone an environment using the advanced method:

1. Open the **Target UI Home Page** dropdown list and choose **Control > Clone**.




Figure 34: Simple Cloning: Select Clone

2. On the **Clone Type** page, choose **Advanced Clone** from the dropdown list, then click **Next** to proceed.




Figure 35: Advanced Cloning: Select Clone Type

3. On the **Credentials** page, choose a set of saved credentials or enter your user name and password, then click **Next** to proceed.

Figure 36: Advanced Cloning: Entering Credentials

4. The **Progress** page lets you know that required details are being collected from the source environment.




Figure 37: Advanced Cloning: Retrieving Details

---

**IMPORTANT:** The details collection process cannot be interrupted, and will continue even if the browser window is closed.

---

After retrieving the source environment details, the page automatically advances to the **Details** page.

5. Use the **Details** page to make any necessary adjustments to the collected information. Select the first checkbox if you would like to restart the source environment. Select the second checkbox if you want to generate a new environment id for the clone environment. Click **Next** to proceed.




Figure 38: Advanced Cloning: Entering Details

6. On the **Schedule** page, choose to either perform the clone operation **Now** or **Later**. Click **Schedule** to complete the process and submit the cloning job.





Figure 39: Advanced Cloning: Scheduling


If the source environment has both web and batch targets, the dialog box will prompt you to run `iwsdeploy.sh` manually after cloning to deploy IWS if and only if Web services have been enabled in the source environment.





**Figure 40: Simple Cloning: Confirmation Dialog for Web and Batch Targets**

If the source environment has only a batch target, the dialog box will ask you if you want to view the execution status.




**Figure 41: Simple Cloning: Confirmation Dialog for Batch Target Only**

## Patch Import and Installation

Patching is a three-step process\*:

1. **Download** patches from My Oracle Support (MOS): This step is performed through the **My Oracle Support Plug-in** within Oracle Enterprise Manager from the top-level menu, choose **Enterprise > Provisioning and Patching > Patching & Updates**.



2. **Import** the downloaded patches: This process allows you to import downloaded patches which are subsequently unpackaged into a format that is compatible with Enterprise Manager for Oracle Utilities's installation process.
3. **Install** the imported patches: This process allows you to import downloaded patches and install them into a target environment, updating relevant files in `$SPLEBASE`. If you deploy manually to the web server, you must perform this step after the installation process completes.

### Patch Import/Installation Notes

- In addition to the procedures described in this topic, follow the steps in the [Patching Prerequisite](#) topic before installing patches in Enterprise Manager for Oracle Utilities Release 13.5.1.0.0 and later.

---

**IMPORTANT:** Installation of Service Packs for OUA products is supported in this release. Review the document *Whitepaper: Service Pack Compliance*

before installing any service pack to make sure the service pack is packaged in a compliant manner.

---

- Read-write access to the download directory is required.
- For patches containing single fixes and hot fixes: Application server patch components are installed using the standard patch install script. Database patch components are installed using a Java version of the standard `CDXPatch.exe` utility.
- Patches containing service packs using the new SP model are now supported. These type of patches contain a file called `Metadata.xml`, which is used by the plug-in to install the service pack.
- During patch installation and patch migration, the installation job copies the individual patch directories from the download staging directory to a directory on the target environment (`$SPLBASE/oem/patch/install/tmp/YYYY-MM-DD-HH-MI-SS`). The subdirectories are sorted by install sequence, e.g., `001-gf`, `002-gf`, `003-sfs`. The job output clearly states the directories from which patch installation occurs.
- During service pack installation, make sure the service pack zip file is the sole content of the download directory.
- During any installation process—service pack, single fixes, rollups—WebLogic environments are shut down automatically using the command-line utility `spl.sh/spl.cmd`. Non-WebLogic environments must be shut down manually.
- Due to packaging differences, only standard single fixes, group fixes and service packs using the new service pack model are supported. An error is generated if you choose an old service pack or rollup for import, or if the single fix or group fix is packaged in a non-standard manner.

## Patching Prerequisite

As of Enterprise Manager for Oracle Utilities Release 13.5.1.0.0, OUAF database credentials are Enterprise Manager for Oracle Utilities stored as a named credential and referenced by the patching procedures. Before patching an OUAF Home target, you must create the OUAF database credentials.

To set up the OUAF database credentials:

1. Navigate to **Setup > Security > Named Credentials**.




Figure 42: Navigating to Named Credentials

2. Click the **Create** button.




Figure 43: Creating Credentials

3. Enter the appropriate credential information. Set the **Scope** to **Global**. Do not enter a target type or target. When the credentials and **Scope** are set, click **Save**.

## Security

Named Credentials > Create Credential

### Create Credential

#### General Properties

* Credential name	<input type="text" value="my_cred"/>
Credential description	<input type="text" value="sample credential"/>
* Authenticating Target Type	<input type="text" value="Oracle Utilities Home"/>
* Credential type	<input type="text" value="ouafDBCreditsType"/>
Scope	<input type="radio"/> Target <input checked="" type="radio"/> Global

#### Credential Properties

* Username	<input type="text" value="cisadm"/>
* Password	<input type="password" value="*****"/>
* Confirm Password	<input type="password" value="*****"/>
Colon-separated users (e.g. CISUSER:CISREAD) to create synonyms	<input type="text" value="cisuser:cisread"/>
Database role which has a read-write privilege (e.g. CISUSER)	<input type="text" value="cisuser"/>
Database role which has a read only privilege (e.g. CISREAD)	<input type="text" value="cisread"/>

#### Access Control

Figure 44: Entering Credentials

## Patch Import

To import patches:

1. Open the **OUI Home Target Home** page and click the **Patch Import** button.




Figure 45: Starting the Patch Import Process

- On the first page of the **Import Patches** walk-through, enter the download directory (the directory on the server where the downloaded zip files are stored when you manually downloaded them from My Oracle Support). The path entered here should be accessible from the server on which the target environment is hosted. After entering the path, click **Next**.




Figure 46: Entering the Patch Path

- On the **Credentials** page, choose a set of saved credentials or enter your user name and password, then click **Next** to proceed.

V231\_CCB\_OEM\_LIN\_ORA\_WLS\_slc03rnc.us.oracle.com\_home

Patch Download Directory    Credentials    Schedule    Exit

### Patch Import: Credentials

#### Host Credentials

Credential  Preferred  Named  New

Credential Name: GBU

Credential Details:

Attribute	Value
UserName	aerattup
Password	*****
Privilege Type	SUDO
Run As	gbuora

[More Details](#)

#### OUIA Credentials

Credential  Preferred  Named  New

Credential Name: NC\_ORACLE\_O\_2015-12-08-162506

Credential Details:

Attribute	Value
UserName	system
Password	*****

[More Details](#)

Figure 47: Patch Import Credentials

- On the **Schedule** page, choose to either perform the import operation **Now** or **Later**. If set for **Later**, click **Schedule** to complete the process and schedule the deployment procedure.




Figure 48: Scheduling the Patch Import

- To check the output, go to **Enterprise > Provisioning and Patching > Procedure Activity**.




Figure 49: Import Patch Procedure Activity

- Search the **Procedure Activity** list for the appropriate run item, and click the link.






Figure 50: Checking a Patch Import

- Expand the **Procedure Steps** on the left and review the **Import Patch Structuring / Step** to view the output.




Figure 51: Patch Provisioning Procedure Activity page

On completion of the patch import job, the imported zip file is unpackaged in the appropriate staging directory and a \*.zip-unpacked file is created.

Example: An FW V4.1.0 patch zip file called `p12548444_4100_Generic.zip` is imported and placed in `/tugbu_oem/download`. On completion of the import procedure, the following occurs:

1. `/tugbu_oem/download/p12548444_4100_Generic.zip-unpacked` is created. This prevents patches that have already been imported from being processed again. If you would like a patch to be re-imported, delete its `*.zip-unpacked` file.
2. For a single fix or hotfix, `/tugbu_oem/download/staging_directory/FW/V4.1.0/multiplatform/FW.V4.1.0-12548444/12548444_sf_patch_info.xml` is created. This file contains information about the patch. The contents of the file are also placed in the proper product, release, platform, and patch number directory.

For a service pack containing the new SP model, the following file should be present:  
`/tugbu_oem/download/staging_directory/FW/SP/multiplatform/9999999/Metadata.xml`.

## Patch Import Enhancements

Patch import also includes the identification of patch prerequisites and the ability to download and import them. This feature is available from OUAF release 4.3.0 Service Pack 1 and later. All environments on OUAF release 4.3.0 Service Pack 1 will have the old patch import flow.




Figure 52: Source screen




Figure 53: Credentials screen




Figure 54: Prerequisite screen

The user can choose to download the prerequisite. If not, the user has to uncheck the auto download checkbox.




Figure 55: Schedule screen




Figure 56: Confirmation box

## Installing Patches

To install patches:

1. Open the **OUAF Home Target Home Page** and click the **Patch Install** button.






Figure 57: Starting the Patch Install process

2. The first page of the **Patch Install** walk-through appears. Enter the download directory used during patch import (relative to the target environment). After entering your selection, click **Next** to proceed.



*Figure 58: Specifying the Install Directory*

3. On the **Credentials** page, choose a set of saved credentials or enter the user name and password for the environment, then click **Next** to proceed.



### Patch Install: Credentials

#### Host Credentials

Credential  Preferred  Named  New

Credential Name:

Attribute	Value
UserName	aerattup
Password	*****
Privilege Type	SUDO
Run As	gbuora

[More Details](#)

#### OUAF Credentials

Credential  Preferred  Named  New

Credential Name:

Attribute	Value
UserName	system
Password	*****

[More Details](#)

Figure 59: Specifying Install Credentials

4. Enter the ouaf database credentials on the next page. The credentials should have been created previously as a named credential (see the [Patching Prerequisite](#) topic for details). After entering the credentials, click **Next** to proceed.




Figure 60: Specifying Database Credentials

5. The **Patches** page lists candidate patches. The list includes only patches that are valid for the target environment (based on product, release and platform), exist on the download directory, and have not yet been installed on the target environment. Select the patch or patches to be installed. Use **Control+Click** or **Shift+Click** to select multiple patches. After making your choice(s), click **Next** to proceed. Note that you cannot mix service packs and fixes. You also cannot install more than one service pack at a time, or the install job will fail.




Figure 61: Selecting Patches

6. On the **Schedule** page, choose to either perform the installation operation **Now** or **Later**. If set for **Later**, click **Schedule** to complete the process and schedule the deployment procedure.




Figure 62: Scheduling the Patch Install

- As with the patch import procedure, check the output by going to **Enterprise > Provisioning and Patching > Procedure Activity**. On the **Provisioning** page, search for the appropriate run and click on the link. To view the output, expand the **Procedure Steps** on the left to view the output.



**Provisioning**  
 Procedure Activity > OUAInstallPatch @2015-12-08 18:41:03.667 [Switch to Classic View](#)

**Procedure Activity: OUAInstallPatch @2015-12-08 18:41:03.667** View Data Real Time: 30 Second Refresh [Refresh](#)

**Elapsed Time: 6 seconds** Procedure Actions

Run OUAInstallPatch @2015-12-08 18:41:03.667 Scheduled Dec 8, 2015 6:41:11 PM PST Elapsed Time 6 seconds

Procedure OUAInstallPatchOUTY Start Date Dec 8, 2015 6:41:11 PM PST Execution Id 266EEC30E20B19C7E05399C0F00A9A9F

Owner SYSMAN Last Updated Dec 8, 2015 6:41:13 PM PST

Status Running Completed Date

**Procedure Steps** [Switch to Stack View](#)

View  Show All Steps

Selec	Name	Status
<input type="checkbox"/>	PatchInstallation	
<input type="checkbox"/>	V43010_Z1_OEM_QA_LIN_ORA_WLS_slc09ctq.us.oracle.com	
<input checked="" type="checkbox"/>	Install Patch	

**Install Patch** [Job Summary](#) [Download](#) Actions

Type Job Start Date Dec 8, 2015 6:41:12 PM PST

Elapsed Time 11 seconds

Completed Date

**Step: copyPatchList (Succeeded)**

Start Date 2015.12.08 18:41:13

Completed Date 2015.12.08 18:41:15

Targets V43010\_Z1\_OEM\_QA\_LIN\_ORA\_WLS\_slc09ctq.us.oracle.com\_home

**Step: Command (Running)**

Start Date 2015.12.08 18:41:15

Completed Date

Figure 63: Install Patch Procedure Activity

**Additional details regarding patch installations.**

Installation occurs in the following sequence:

- Patches are copied from the download staging directory to a temporary directory on the target (\$SPLEBASE/oem/patch/tmp).
- Patch installation is grouped by product, according to the order in which the products are listed in the PRODUCT.txt file.
- For single/hot fixes within a product, group fixes are installed first, in order of patch number. Single-fix patches are combined as a rollup, and a group install is performed. For each of these, the database components are installed first, followed by the application server component, and, finally, an error-checker is executed.
- For service packs, product versions are updated by the SP installation process. There can be a delay before this is reflected in the target home page. Refer to the section titled "Ensure Collection of Installed Product Configuration Information" for instructions on how to refresh this information.

## Patch Install Enhancements

Patch installation functionality also includes the ability to identify patch prerequisites and notify the user of the requirement to download and import them. This functionality is available from OUAF release 4.3.0 Service Pack 1 and later. All environments on OUAF release 4.3.0 Service Pack 1 will have the old patch import flow.




Figure 64: Source




Figure 65: Credentials screen




Figure 66: DB credentials




Figure 67: Patches screen




Figure 68: Prerequisite patches availability

If the prerequisite patches are not available, availability is set to *false*, the **Next** button is disabled, and a scheduling screen is made available to allow you to schedule downloading of the prerequisites.




Figure 69: Schedule screen




Figure 70: Confirmation Box

## Patch Migration

During the product implementation lifecycle, patches are normally installed and tested on an environment, and the process is repeated on each environment. The patch migration feature in Enterprise Manager for Oracle Utilities allows administrators to migrate patches to all environments from a central location.

Patch migration is special form of patch installation wherein a source environment is compared to a destination environment. The source environment is used to identify patches that the administrator intends to install in the current/destination environment. The identified patches should have been imported previously for the current target's product, release and platform.

The workflow is as follows:


1. On the destination environment's target home page, click the **Migrate** button.

2. A source target containing the patches to migrate is selected from the dropdown list.
3. Existing patches installed on both targets are analyzed and a list of patches that are installed on the source (but not on the destination target) is created. This list is compared to the contents of the download staging directory and only the patches that have been previously imported are displayed for selection.
4. The selected patches are then installed by the patch installation job (the same one used in the patch installation process), updating relevant files in `$$SPLEBASE`. If you deploy manually to the web server, you must perform this step after the installation process completes.

## The Process

Patch migration is a three-step process:

1. **Download** patches from My Oracle Support (MOS): This step is performed through the **My Oracle Support Plug-in** within Oracle Enterprise Manager from the top-level menu, choose **Enterprise > Provisioning and Patching > Provisioning & Patching**.



2. **Import** the downloaded patches: This process allows you to import downloaded patches which are subsequently unpackaged into a format that is compatible with Enterprise Manager for Oracle Utilities's installation process.
3. **Migrate/install** the imported patches.

**NOTE:** Application server patch components are installed using the standard patch install script. Database patch components are installed using a Java version of the standard `CDXPatch.exe` utility. Note that patches using the database upgrade-install

utility `cdxdbi.exe` are *not* supported and the database component of the patch will not be installed.

## Migrating Patches

To migrate patches:

1. Open the **OUAF Home Target Home Page** and click the **Migrate Patches** button to open the **Migrate Patches** walk-through.




Figure 71: Starting a Patch Migration

2. On the **Download Directory** page, enter the download directory used during patch import (relative to the destination environment). After entering your selection, click **Next** to proceed.




Figure 72: Specifying the Download Directory

3. On the **Source** page, choose the source target environment from the dropdown list. Note that only targets with identical product/version combinations are included in the list. After making your selection, click **Next** to proceed.




Figure 73: Choosing a Source Environment

4. On the **Source Credentials** page, choose a set of saved credentials or enter the user name and password for the source environment, then click **Next** to proceed.

ORACLE Enterprise Manager Cloud Control 13c SYSMAN

V43010\_Z1\_OEM\_QA\_LIN\_ORA\_WLS\_slc09ctq.us.oracle.com\_home

Overview Patch Download Directory **Source Environment** **Source Credentials** Destination Credentials DB Credentials Patch List Schedule Exit

**Patch Migrate: Source Credentials** Back Step 4 of 9 Next

---

**Host Credentials**

Credential  Preferred  Named  New

Credential Name: STD\_GBUORA\_AE1

Attribute	Value
UserName	aerattup
Password	*****
Privilege Type	SUDO
Run As	gbuora

[More Details](#)

---

**OAAF Credentials**

Credential  Preferred  Named  New

Credential Name: NC\_ORACLE\_O\_2015-12-08-162506


Attribute	Value
UserName	system
Password	*****

[More Details](#)

Figure 74: Specifying Source Credentials


5. On the **Destination Credentials** page, choose a set of saved credentials or enter the user name and password for the destination environment, then click **Next** to proceed.





*Figure 75: Specifying Destination Credentials*

6. Enter the ouaf database credentials on the next page. The credentials should have been created previously as a named credential (see the [Patching Prerequisite](#) topic for details). After entering the credentials, click **Next** to proceed.



**Figure 76: Specifying Database Credentials**

7. The **Select Patches** page lists candidate patches. The list includes only patches that are valid for the target environment based on product, release and platform), exist on the download directory, and have not yet been installed on the destination target but are already installed in the source target.

For a patch to be displayed in the list, it must meet all of the following criteria:

- It is valid for the product, release and platform of the environment;
- It must have been already been successfully imported, and, thus, exist on the download directory;
- It must not yet have been installed on the destination environment; and,
- It must already be installed on the source environment.




Figure 77: The Select Patches page

8. Select the patch or patches to be migrated. Use **Control+Click** or **Shift+Click** to select multiple patches. After making your choice(s), click **Next** to proceed.




Figure 78: Selecting Patches

9. On the **Schedule** page, choose to either perform the migration operation **Now** or **Later**. If set for **Later**, click **Schedule** to complete the process and schedule the deployment procedure.



Figure 79: Scheduling the Migration

10. As with the patch import procedure, check the output by going to **Enterprise > Provisioning and Patching > Procedure Activity**. On the **Provisioning** page, search for the appropriate run and click on the link. To view the output, expand the **Procedure Steps** on the left to view the output.

**Provisioning**  
 Procedure Activity > OUAInstallPatch @2015-12-08 18:41:03.667

**Procedure Activity: OUAInstallPatch @2015-12-08 18:41:03.667**

View Data Real Time: 30 Second Refresh

**Elapsed Time: 6 seconds**

Run OUAInstallPatch @2015-12-08 18:41:03.667 Scheduled Dec 8, 2015 6:41:11 PM PST Elapsed Time 6 seconds

Procedure OUAInstallPatchOUTY Start Date Dec 8, 2015 6:41:11 PM PST Execution Id 266EEC30E20B19C7E05399C0F00A9A9F

Owner SYSMAN Last Updated Dec 8, 2015 6:41:13 PM PST

Status Running Completed Date

**Procedure Steps**

Selec	Name	Status
<input type="checkbox"/>	PatchInstallation	
<input type="checkbox"/>	V43010_Z1_OEM_QA_LIN_ORA_WLS_slc09ctq.us.ora	
<input checked="" type="checkbox"/>	Install Patch	

**Install Patch**

Type Job Start Date Dec 8, 2015 6:41:12 PM PST

Elapsed Time 11 seconds

Completed Date

**Step: copyPatchList (Succeeded)**

Start Date 2015.12.08 18:41:13

Completed Date 2015.12.08 18:41:15

Targets V43010\_Z1\_OEM\_QA\_LIN\_ORA\_WLS\_slc09ctq.us.oracle.com\_home

**Step: Command (Running)**

Start Date 2015.12.08 18:41:15

Completed Date

Figure 80: Patch Migration Procedure Activity

## Viewing Configuration Files

The View Configuration Files feature lets you review configuration details remotely without logging into the server or the environment. This information lets you compare environments and diagnose customer setup issues.

To view configuration files:

1. From the appropriate Target Home Page (Web Application, Web Services, or Batch Server target home page), choose **Target > Control > View Config**.




Figure 81: Viewing Configuration Files

2. On the **Credentials** page, choose a set of saved credentials or enter your user name and password, then click **Next** to proceed.

**View Configuration: Credentials Input**

**Host Credentials**

Credential  Preferred  Named  New

Credential Name: GBU

Attribute	Value
UserName	aerattup
Password	*****
Privilege Type	SUDO
Run As	gbuora

[More Details](#)

---

**OAAF Credentials**

Credential  Preferred  Named  New

\* Username: system

\* Password: \*\*\*\*\*

\* Confirm Password: \*\*\*\*\*

Save As: STD\_SYSTEM\_CRED

*Figure 82: Specifying Credentials*

3. The **Configuration Files** page offers a selection region to let you choose configuration files to view, as well as a display area for the selected file.




Figure 83: Configuration File Viewer

4. Choose a configuration file by either clicking an option button from the listed items or by selecting the **Other file** option and entering the path (relative to SPLBASE) of a valid configuration file. `etc/ENVIRON.INI`, will, for example, display `$SPLBASE/etc/ENVIRON.INI`.
5. Click **Submit** to display the file in the scrollable text area.






Figure 84: Viewing a Configuration File

6. After viewing the selected configuration file, you can select other configuration files to view, or click **Cancel** to return to the Target Home Page.

## Viewing Logs

The View Logs feature allows you to view the contents of log files, including the latest thread pool worker log, that are generated at the application server level.

To view logs:

1. From the appropriate Target Home Page (Web Application, Web Services, or Batch Server target home page), choose **Target > Control > View Log**.




Figure 85: Viewing Configuration Logs

2. On the **Credentials** page, choose a set of saved server credentials or enter your user name and password, then click **Next** to proceed.

V231\_CCB\_OEM\_LIN\_ORA\_WLS\_slc03rnc.us.oracle.com\_batch

Credentials
  Log Info

View Log: Credentials

Host Credentials

Credential  Preferred  Named  New

Credential Name

Credential Details

Attribute	Value
UserName	aerattup
Password	*****
Privilege Type	SUDO
Run As	gbuora

[More Details](#)

OUAF Credentials

Credential  Preferred  Named  New

Credential Name

Credential Details

Attribute	Value
UserName	system
Password	*****

[More Details](#)

Figure 86: Specifying Credentials

- The **Log Info** page offers a selection region to let you choose from among all available logs, as well as a display area for the selected log.

Oracle Enterprise Manager Cloud Control 13c

V231\_CCB\_OEM\_LIN\_ORA\_WLS\_slc03qit.us.oracle.com\_batch

Credentials Log Info

View Log: Log Info Back

Batch  threadpoolworker.log Others - etc/ENVIRON.INI

Others  Other Files

etc/ENVIRON.INI

No. Of Lines

```

BSN_RMIPORT=8703
BATCHDAEMON=false
DBDRIVER=oracle.jdbc.driver.OracleDriver
DBPORT=1521
DBCONNECTION=jdbc:oracle:thin:@slc03qit:1521:CD2310E1
JVMMEMORYARG=256
OBSERVER=slc03qit
WEB_IsAppViewer=true
jvmcommand=/scratch/CCB231/V231_CCB_OEM_LIN_ORA_WLS/bin/splcobjrun.sh
WL_HOME=/scratch/CCB231/Software/WebLogic/wserver_10.0
JAVA_HOME=/scratch/CCB231/Software/Java/jdk1.5.0_22
ORACLE_HOME=/orasw/app/oracle/product/11.2.0/client_1
WEB_CONTEXT_ROOT=/spl
# LAST MODIFIED: Wed Nov 4 11:12:40 2015
# THIS IS A SYSTEM MODIFIED FILE!!!
# DO NOT EDIT MANUALLY
MPLSTART=N
NLS_LANG=AMERICAN_AMERICA.UTF8
SPLENCPASS=21525852545244510F0F21
JMchild_OPTIONS=-Xm256m -Dcom.microfocus.cobol.cobjvm=sun_150_64 -Dspl.runtime.socket.file.dir=/scratch/CCB231/V231_CCB_OEM_LIN_ORA_WLS/runtime
-Dfile.encoding=ISO8859_1 -cp /scratch/CCB231/V231_CCB_OEM_LIN_ORA_WLS/splapp/standalone/config/scratch/CCB231/V231_CCB_OEM_LIN_ORA_WLS/splapp
/standalone/lib/activation_api-1.1.jar:/scratch/CCB231/V231_CCB_OEM_LIN_ORA_WLS/splapp/standalone/lib/cm.jar:/scratch/CCB231/V231_CCB_OEM_LIN_ORA_WLS
/splapp/standalone/lib/coherence-3.6.0.jar:/scratch/CCB231/V231_CCB_OEM_LIN_ORA_WLS/splapp/standalone/lib/coherence-work-3.6.0.jar:/scratch/CCB231
/V231_CCB_OEM_LIN_ORA_WLS/splapp/standalone/lib/commonj-3.6.0.jar:/scratch/CCB231/V231_CCB_OEM_LIN_ORA_WLS/splapp/standalone/lib/commons-beanutils-
core-1.7.0.jar:/scratch/CCB231/V231_CCB_OEM_LIN_ORA_WLS/splapp/standalone/lib/commons-cli-1.1.jar:/scratch/CCB231/V231_CCB_OEM_LIN_ORA_WLS/splapp
/standalone/lib/commons-codec-1.3.jar:/scratch/CCB231/V231_CCB_OEM_LIN_ORA_WLS/splapp/standalone/lib/commons-collections-2.1.1.jar:/scratch/CCB231
/V231_CCB_OEM_LIN_ORA_WLS/splapp/standalone/lib/commons-fileupload-1.2.jar:/scratch/CCB231/V231_CCB_OEM_LIN_ORA_WLS/splapp/standalone/lib/commons-

```

Figure 87: Log Info page

4. Enter the number of lines that you would like to view from the selected log. If no value is entered or the value exceeds the number of lines in the selected log, the complete log is displayed.
5. Click **Submit** to display the log in the scrollable text area.
6. After viewing the selected log, you can select other logs to view, or click **Cancel** to return to the Target Home Page.

## Log Viewer Enhancements

This module allows you to view all log files relating to a specified target type. Log viewer enhancements allow display of details such as timestamp, message type, etc., lets you search for specific terms in the log file, and lets you download the file.

**NOTE:** The default preferred host credentials for the target type must be set beforehand.




Figure 88: Log viewer menu




Figure 89: Log viewer landing page

This is a generic page. To view the target-specific log files, click **Target Log Files** on the side of the screen.




Figure 90: Target-specific log files

In the following image, the list of log files relating to the target type are displayed. You can also view/download a selected log file from this screen.




Figure 91: Display content of log file




Figure 92: Searching for a term in a log file

## Performance Portal: Custom Dashboard

This feature is available for all target types. By default, it displays the availability region and a metric palette along with a chart toolbar and a time toolbar. You can customize this dashboard according to your own use cases. Various charts can be viewed by selecting the charts in the metric palette, and the time range can be selected accordingly. Also, chart values can be compared with respect to a set baseline or with another chart.

**NOTE:** Users with read-only privileges cannot access the custom dashboard.




Figure 93: Custom dashboard menu option




Figure 94: Default custom dashboard page




Figure 95: Charts selected and displayed on the UI

## Additional Features and Functionality

### Metrics Enhancement: Batch Level of Service

This feature supported from OUAF 4.2.0 Service Pack 3 with Bug 21358792.



Oracle Utilities Batch Server Start Stop

- Home
  - Open the home page in a new window.
- Monitoring
  - All Metrics
  - Metric and Collection Settings
  - Metric Collection Errors
  - Status History
  - Incident Manager
  - Alert History
  - Blackouts and Brownouts
- Diagnostics
- Control
- Logs
- Job Activity
- Information Publisher Reports
- Custom Dashboard
- Configuration
- Compliance
- Target Setup
- Target Sitemap
- Target Information

Cluster Port: 9781  
Batch RMI Port: 9750

Flush All Caches

Time	Elapsed Time	Status	User	Threa
------	--------------	--------	------	-------

Batch Code:  
Batch Description:  
Thread:  
Thread Limit:  
Batch Number:  
Program Name:  
Program Type:  
Run Type:

Figure 96: Menu to navigate to the metric




Figure 97: BatchOverAllHealth metric

## Features Available for Users with Specific Roles

### A. User: Operator Privileges

Oracle Utilities Home

Clone

Patch Import

Patch Install

Patch Migrate

- Home
  - Open the home page in a new window.
  - Monitoring
  - Diagnostics
  - Control**
  - Job Activity
  - Information Publisher Reports
  - Custom Dashboard
  - Configuration
  - Compliance
  - Target Setup
  - Target Sitemap
  - Target Information
- Create Blackout...
  - End Blackout...
  - Create Brownout...
  - End Brownout...
  - Assess
  - Clone
  - Patch Import
  - Patch Install
  - Patch Migrate

**Incidents**

Updated in last 7 days 0

Breakdown of incidents updated in the last 7 days

Category				
Availability	-	-	-	-
Performance	-	-	-	-

Figure 98: Environment Home page functions





Figure 99: Web Page functions



*Figure 100: Batch Page functions*

### **B. User: Read-Only Privileges**

Prerequisite: For a read-only plugin user role to work properly (to enable the user to access modules with previously-saved credentials), the following actions must be applied:

- Add 'Execute Command Anywhere' for 'Privileges applicable to all targets'
- Add 'Named Credential' for 'EM Resource Privileges'
- Add 'Configure Target' Privilege for Target Privileges Applicable to Specific Targets




Figure 101: Environment Home page functions





Figure 102: Web Page functions



**Figure 103: Batch Page functions**

**C. User: Administrator Privileges** (has access to all functionality)



Oracle Utilities Home

Clone

Patch Import

Patch Install

Patch Migrate

- Home
  - Open the home page in a new window.
- Monitoring
- Diagnostics
- Control
  - Create Blackout...
  - End Blackout...
  - Create Brownout...
  - End Brownout...
- Job Activity
- Information Publisher Reports
- Custom Dashboard
- Configuration
  - Assess
- Compliance
  - Clone
- Target Setup
  - Patch Import
  - Patch Install
  - Patch Migrate
- Target Sitemap
- Target Information

Incidents

Updated in last 7 days 0

Figure 104: Environment Home page functions




Figure 105: Web Page functions




Figure 106: Batch Page functions

## Tips and Troubleshooting

- Discovery and metric configuration collection log information can be found in the agent perl trace file (`.../agent_inst/sysman/log/emagent_perl.trc`).
- Environment-specific log files can be found in `$SPLEBASE/logs/system`, and are named `ouaf_oem*.log`.

## Documentation Accessibility

Our goal is to make Oracle products, services, and supporting documentation accessible to all users, including users that are disabled. To that end, our documentation includes features that make information available to users of assistive technology.

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

## Accessibility of Code Examples in Documentation

Screen readers may not always correctly read the code examples in this document. The conventions for writing code require that closing braces should appear on an otherwise empty line; however, some screen readers may not always read a line of text that consists solely of a bracket or brace.

## Accessibility of Links to External Web Sites in Documentation

This documentation may contain links to Web sites of other companies or organizations that Oracle does not own or control. Oracle neither evaluates nor makes any representations regarding the accessibility of these Web sites.

## Access to Oracle Support

Oracle customers have access to electronic support through My Oracle Support. For information, visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

---

Enterprise Manager for Oracle Utilities

Administrative Guide

Release 13.5.1.0.0

Part number F70358-01

September 2022

Documentation build: 1.17.2023 17:12:31 [AMP\_1673997151000]

Copyright © 2022, Oracle and/or its affiliates.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software" or "commercial computer software documentation" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and

other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Inside are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Epyc, and the AMD logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

Third-party licenses relating to Enterprise Manager and this plug-in are available for viewing online at: Enterprise Manager Licensing Information ([http://docs.oracle.com/cd/E24628\\_01/doc.121/e24474/title.htm](http://docs.oracle.com/cd/E24628_01/doc.121/e24474/title.htm)).

NOTE: Prior versions of this product were released as Application Management Pack for Oracle Utilities. Please note that any references to Application Management Pack for Oracle Utilities that may occur within this document or in images within this document refer instead to the product's new name, Enterprise Manager for Oracle Utilities.