

Development Workbench - Administration
Oracle FLEXCUBE Investor Servicing
Release 14.7.0.1.0
Part No. F71715-01
[May] [2023]



Table of Contents

1. Preface	3
1.1 Audience.....	3
1.2 Related Documents	3
2. Introduction	4
3. Administration	5
3.1 First Time Log in	5
4. Release	7
4.1 Release Detailed	7
4.2 Release Summary	12
5. Environment.....	13
5.1 Environment Detailed.....	13
5.2 Environment Summary	18
6. User	19
6.1 User Detailed.....	19
6.1.1 User Releases	20
6.1.2 Release Administrator.....	20
6.2 Developer	21
6.3 TCM User	21
6.4 Vercon	21
6.5 User Summary.....	23
6.6 Key Points	23
7. Appendix.....	24
7.1 File Manager.....	24
6.1.1 File Manager Deployment	24
6.1.2 Maintenance in Development Workbench.....	25

1. Preface

This document describes the Administration options available in Oracle FLEXCUBE Development Workbench for Universal Banking and guides the developers on how to use this feature.

1.1 Audience

This document is intended for FLEXCUBE Application developers/users that use Development Workbench to develop various FLEXCUBE components.

To Use this manual, you need conceptual and working knowledge of the below:

Proficiency	Resources
FLEXCUBE Technical Architecture	Training programs from Oracle Financial Software Services.
Working knowledge of Web based applications	Self-Acquired
Working knowledge of Oracle Database	Oracle Documentations

1.2 Related Documents

[01_ODT_Installation.pdf](#)

[03-Development_WorkBench_Getting_Started.pdf](#)

2. Introduction

The information in this document includes:

- [Chapter 2 , "Introduction"](#)
- [Chapter 3 , "Administration"](#)
- [Chapter 4 , "User Releases"](#)

3. Administration

Workbench segregates the developmental activity of the developers into different releases. This allows the tool to track the changes done in each release and helps the developer to follow an extensible approach to development.

Administration screens of Development Workbench are as follows:

- i) Release Creation
- ii) Environment Creation
- iii) User Creation

3.1 First Time Log in

After successful installation, user can login to the Tool using the following credentials

User Name: **RADTOOL**

Password: **RADTOOL**




Fig: Login Screen

RADTOOL user is initially mapped to Default Release. This user is only for initial login to the tool. Developers should not use this user to design new screen or to modify existing screen.

After successful login click on Administration node in left side of Tree under browser Tab.




Fig: The Browser tab with Administration option

We will find 3 options In Administration. Release Environment and User.




Fig: Options under Administration

4. Release

Expand the Release node under administration. We will get Detailed and summary options.




Fig: The options under 'Release'

Click on Detailed option to create new release. Release screen will be launched.

4.1 Release Detailed




Fig: The Release detailed Screen

Only a user with Administrator rights can create Release. It is recommended to use RADTOOL user for creating new releases

- **Release Code:** Release code/Project Code is mandatory field. It should follow FLEXCUBE naming convention.
Ex: **FC_UBS_V.UM_11.4.US.1.0.0.0**
- **Description:** Information about the release. Meaningful description of release can be provided here

- **Release Type:** Select the release type. This is mandatory field.
 - **Kernel:** This option should be used by kernel team only.
 - **Cluster:** A regional development team has to select this option.
 - **Custom:** Either offshore development team for client changes or development in Onsite has to select this option.
- **Release No:** Enter the version number of FLEXCUBE development.
- **Base Release:** Select base release from the list of values. All available releases will be shown in the List of values. Base release is of significance for migrating test case data
Example: If developer is working on customization on top of 11.3EU Cluster pack, base release will be 11.3EU
- **Environment:** Select default environment. While creating new release ignore
- **Remarks:** Enter if any additional info required regarding Release. This is information field.
- **Release SPC:** This would be used for in house developments. This is not required for custom developments
- **Stream Name:** Stream name should be same as DDL stream name. This is not applicable if DDL integration not required
- **Cluster Name:** This is an information field. If the release is a Cluster pack, name of the Cluster release can be provided here .Same name as maintained in DDL Tool.
- **Custom Name:** This is an information field. If the release is a Customization, name of the customer can be provided here .Same name as maintained in DDL Tool
- **Release Stage:** This is information field. Release stage can be Development, SQA, and ITR etc.
- **Application Name:** Provide the name of application for which the release is.
Example: FLEXCUBE, FCIS, FGL etc.
- **Migrate Test Case Data from Base Release:** If check box is checked ,all the test case data from the base release will be migrated to the new release

The below figure shows a sample entries for creating custom release done for MODEL BANK

The screenshot shows the 'Release Master' application window. The 'Release Detailed' section is active, displaying a form with the following fields:

- Release Code: FCIS_145_SUPPORT
- Description: 14.5 Support
- Release Type: Kernel (dropdown)
- Base Release: FCIS_145_SUPPORT
- Environment: FCIS_145_SUPPORT
- Remarks: (empty)
- Release SPC: (empty)
- Stream Name: (empty)
- Cluster Name: (empty)
- Custom Name: (empty)
- Release Stage: (empty)
- Application Name: (empty)

Below the form, there is a checkbox labeled 'Migrate Test Case Data From Base Release' which is unchecked. At the bottom, a summary box contains:

- Modification Number: 2
- Release Status: Open (dropdown)
- Maker Id: RADTOOL
- Maker Date Stamp: 2022-11-18 17:57:49

A 'Close' button is located in the top right corner of the window.

Fig: Creating a Release

The screenshot shows the 'Release Master' application window with an 'Information' dialog box open. The dialog box has the following content:

- Information Description: RD-SAVE-004 | Record Successfully Updated
- Information Code: (empty)

The dialog box has an 'Ok' button at the bottom right. The background window is dimmed, showing the same form as in the previous figure, but with the 'Release Stage' field now containing the value 'Open'.

Fig: Saving a Release

Querying a Release

If user want to modify existing release Details click on Release Detailed node in tree and click enter query option.



Fig: Querying details of an existing Release

Release code field gets enabled. If release name known already enter directly or select release code from provided List of values.




Fig: Selecting Release from LOVs

After selecting release code click on execute query.




Fig: The *ExecuteQuery* button to be clicked after entering release code

Modifying a Release:

Click on unlock button.

Release Master

Release Detailed

Release Code * FCIS_145_SUPPORT

Description 14.5 Support

Release Type Kernel

Base Release FCIS_145_SUPPORT

Environment FCIS_145_SUPPORT

Remarks

Release SPC

Stream Name

Cluster Name

Custom Name

Release Stage

Application Name

☐ Migrate Test Case Data From Base Release

Modification Number 2

Release Status Open

Maker Id RADTOOL

Maker Date Stamp 2022-11-18 17:57:49

Close

Fig: The Details of a Release

After unlock button clicked except release code all fields will be enabled. Release administrator can update the required fields. Click on save.

Release Master

Release Detailed

Release Code * FCIS_145_SUPPORT

Description 14.5 Support

Release Type Kernel

Base Release FCIS_145_SUPPORT

Environment FCIS_145_SUPPORT

Remarks

Release SPC gayathri.loganathan@oracle.com

Stream Name

Cluster Name

Custom Name

Release Stage

Application Name

☐ Migrate Test Case Data From Base Release

Modification Number 2

Release Status Open

Maker Id RADTOOL

Maker Date Stamp 2022-11-18 17:57:49

Close

Fig: Release after unlock

4.2 Release Summary

This screen will be used to get details of all releases already existing in Workbench. Click on execute query button, it will display all available releases in grid view. Double click on the particular release code it will take us to detailed screen.




Fig: The Summary of a Release




Fig: Details view on Double clicking

5. Environment

Workbench requires at least one environment for each release and the below environment details need to be maintained. Multiple environments can be mapped to a single release.

For instance, different environments can be maintained for different stages of the same release i.e. development, testing etc.

Note that Workbench can interact with multiple FLEXCUBE links .Each environment correspond to a FLEXCUBE environment




Fig: Options under Environment

Click on detailed node of environment. Click new button all fields will get enabled.

5.1 Environment Detailed

Fig: The Detailed Screen for Environment

- **Environment Code:** This is mandatory field. Naming convention would be <release code>_ENV.
For Example: FCIS_14.7_DEV
- **Release Code:** This is a **mandatory** field. Select the correct release code from the list of values. This field identifies the release to which the environment is mapped
- **Language:** This is **mandatory** field. Select the required language from LOV. This field is very important in environment creation as screen xml will be generated based on the language set up at the environment level.
List of values fetches the available languages from RDTM_LANGUAGE. Any new language, if required, has to be maintained in this table
- **Description:** Information field. Meaningful description to environment code.
- **JNDI Name:** Enter valid jndi name. This is **mandatory**. It should match with jndi name used while creation of Data Source for FLEXCUBE in app server. It's case sensitive. Connection to the FLEXCUBE schema is established from Workbench using the JNDI name maintained in environment definition.
If JNDI name does not match data base connection to FLEXCUBE schema won't happen.
For instance:
If server is Apache Tomcat, JNDI provided in environment creation should match with jndi provided in server.xml and context.xml
If server is web logic, JNDI provided in environment creation should match with jndi of the data source created;

Dynamic Registering of Data Source with JNDI

Dynamic Data Source Registering feature avoids the need of creating Data Source manually in the Application Server. To enable this feature, Provider URL value has to be provided during installation .A new data source will be added to the JNDI context using the Data Base details provided while creating Environment (explained below).

An Example of Properties to be specified in odt.properties for webLogic Server is given below

INITIAL_CONTEXT_FACTORY=weblogic.jndi.WLInitialContextFactory
PROVIDER_URL=t3://localhost:7101

Note that this feature won't be available if the JNDI context is read only.
Example: Apache tomcat Server

Data Base Details:

The FLEXCUBE database server details of the environment can be provided here .These are information fields. *Data base connection is achieved through jndi maintained and not with help of data provided in these fields unless dynamic registering of Data Source feature is available*

- **Data Base Instance:** Enter the valid Data base instance name.
- **Data Base Port:** Enter data base port number.
- **Data Base IP Address:** Enter data base IP address.
- **Data Base Host Name:** Enter host name or IP address of data base.
- **Data Base Name:** Enter schema name.
- **Data Base password:** Enter schema password.

If dynamic registering of Data Source feature is not available then the following has to be taken care

- 1) *If the password of FLEXCUBE schema is changed, merely changing the password in the Workbench environment wouldn't be of any help. Developer will have to update the data source in the server with the latest credentials.*
- 2) *If jndi of the data source is changed, Application server has also to be updated with the same*

Application Details:

- **Application URL:** Enter valid FCIS url.
- **Application IP Address:** Enter application IP address.
- **Application Name:** Enter application name. Information field.
- **Application Operating System:** Select on which operating system FLEXCUBE is running; two options are provided: windows or UNIX.
- **Application transfer Type:** If user requires Deploy option (Check the document [05-Development WorkBench Screen Development-II.pdf](#) to get more details about deploy option), file transfer type has to be selected.

File Transfer type depends on the operating system of application server in which FLEXCUBE is hosted

Windows: File manager/File Copy

UNIX: File Manager

File Copy: Directly copies files into specified location.

File Manager: It is a Servlet (please check the File manager section in appendix to get more details) running in app server where FLEXCUBE is deployed. This Servlet has to be deployed in the same server where FLEXCUBE is hosted for copying files from Workbench

server. This has to be selected if operating system is UNIX. Refer *Appendix* section on further details on File Manager

- **JS Directory Path:** Enter shared path of JavaScript files in FLEXCUBE server. This is also required for deploy feature of Workbench .All the system JavaScript files generated will be copied to the path mentioned in this field

Example:

Windows → [\\10.184.46.209\\js\\](http://10.184.46.209\\js\\) (*Each forward slash should be appended by one more*)

UNIX→

/oraint1/web1034/Oracle/Middleware/user_projects/domains/FCISDevDomain/servers/FC114EXT/tmp/_WL_user/FC114EXT/eq6wn/war/Script/JS/ (*It should contain only single backward slash*).

Note that slash has to be provided, at the end, in the path provided. Make sure write permission is provided on this folder.

- **UIXML Directory Path:** Enter shared path of UIXML (language xml) files. This is also required for deploy feature of WORKBENCH .All the system JavaScript files generated will be copied to the path mentioned in this field

Example:

Windows → [\\10.184.46.209\\eng\\](http://10.184.46.209\\eng\\)

UNIX→

/oraint1/web1034/Oracle/Middleware/user_projects/domains/FCISDevDomain/servers/FC114EXT/tmp/_WL_user/FC114EXT/eq6wn/war/UIXML/ENG/

Note that slash has to be provided, at the end, in the path provided. Make sure write permission is provided on this folder.

If Transfer Type is File manager then the below details has to be provided mandatorily

Server User Name: Enter application server user name.

Serve Password: Enter application server password.

File Manager URL: Enter file manager url as shown below.

Format: http://<ipaddress>:<portnumber>/FileManager/FileManageServlet

Eg: <http://10.184.74.143:7755/FileManager/FileManageServlet>

- **File Manager User Name:** Enter user name. This is optional field
- **File Manager Password:** Enter password. This is optional field

The below figure shows a sample environment with data input.

Environment Master

Environment Details

Environment Code: FCIS_145_SUPPORT
Release Code: FCIS_145_SUPPORT
Language Code: ENG
Description:

JNDI name

JNDI Name: jdbc/FCIS_145_SUPPOR

Database Details

Database Instance: FCIS145SUP
Database Port: 1521
Database IP Address: 100.76.156.40
Database Host Name: FCIS145SUP
Database Name: ISSMS145
Database Password:

Application Details

Application URL:
Application IP Address:
Application Name:
Application OS: Unix
Application Transfer Type: File Manager
JS Directory Path:
UI XML Directory Path:
Server User Name:
Server Password:
Server Filemanager URL:
File Manager User Name:
File Manager Password:

Test JNDI Test Environment

Modification Number 1 Maker Id RADTOOL Maker Date Stamp 2022-10-18 12:30:54

Close

Fig: Creating a new Environment

Information

Information Description

RD-SAVE-004 | Record Successfully Updated

Information Code

Ok

Database Port: 1521
Database IP Address: 100.76.156.40
Database Host Name: FCIS145SUP
Database Name: ISSMS145
Database Password:

Server Filemanager URL:
File Manager User Name:
File Manager Password:

Test JNDI Test Environment

Modification Number 2 Maker Id RADTOOL Maker Date Stamp 2022-11-18 18:04:39

Close

Fig: After Saving Environment details

Modify Environment

We can modify the existing environment details. Click on detailed node of environment list.
Click enter query .Environment code field will get enabled. Enter the environment code directly or select from List of values.
Click unlock button and modify required fields
Click on save.




Fig: Modifying an environment by using Query and Unlock

5.2 Environment Summary

This screen will be used to get details of all environments which already exist in Workbench. Click on execute query button, it will display all available releases in grid view. Double click on the particular environment code; it will take us to detailed screen.




Fig: Environment Summary Screen

6. User

User screen is used for creating new user for Workbench. Only Administrator or Release Administrator can create new users. Releases can be attached to the particular user and roles for the user on the attached release code can also be maintained.

The screenshot shows the 'User Definition' window. It has a title bar with standard window controls and a 'Close' button. The window is divided into several sections. On the left, under 'User Details', there are input fields for 'User ID' (marked with a red asterisk), 'User Name', 'User Password', 'Default Release', and 'Default Environment'. To the right of these fields are 'Save Format' (set to 'Zip'), 'Work Directory', 'Excel format' (set to 'XLS'), and checkboxes for 'XML Formatting' and 'LDAP Authentication'. Below these is a table with two columns: 'Release Code' and 'User Role'. The first row shows an empty 'Release Code' field and 'Developer' in the 'User Role' column. At the bottom of the window, there are three input fields: 'Modification Number', 'Maker Id', and 'Maker Date Stamp'.

Fig: User Detailed Screen

6.1 User Detailed

- **User ID:** This is the unique ID given to each user, used to login into Workbench
- **User Name:** Enter User Name.
- **User Password:** The password the user has to enter to login to Workbench
- **Default Release:** Select Release code from the List of values. This will be the release to which user will be mapped on logging in to the Tool. If user mapped to more than one release, user can switch between the releases using User Preferences screen.
- Refer [03-Development WorkBench Getting Started.pdf](#) for further details on User Preferences
- **Default Environment:** Select the corresponding environment code created for the selected default release. If not selected user can set environment in User Preferences screen after logging in
- **Save Format :** User can access the generated files in one of the following modes
 - **Zip:** Files will be zipped and downloaded from the server to the client. This is the default save format.
 - **Server Path:** If user has access to Server, then this mode can be selected. A path in Server has to be specified as Work Directory. Files will be copied to this path from where user can pick it up
 - **Client Path:** For ease of use for users of Older Versions, the earlier mode has also been retained. Here user has to provide a path in his machine as the Work Directory. Note that this

mode uses ActiveX Scripting; hence settings have to be set accordingly. This option is available only in Internet Explorer.

- **Work Directory:** It is the path of the folder where the Workbench generated files will be saved. User can specify default directory where all his work should be saved. This field is applicable only if Save format is either Server Path or Client Path
If the Save Format is Server Path, a path in the server has to be specified.
If the Save Format is Client Path, a path in the client machine has to be specified.
If value is specified as **CURRENT_DIRECTORY** generated files will be saved to location path specified at the design screen level.
- **Excel Format:** This field defines the default extension of the excel files generated from the Tool. XLS and XLSX are the supported formats
- **XML Formatting:** Any XML file which is generated by Workbench will be formatted.
- **LDAP Authentication:** This option can be selected if the user has to be authenticated against a LDAP. Password need not be specified in this case. LDAP properties has to be specified in the **odt.properties** file for availing this feature

Sample LDAP Properties

```
LDAPSSLEn = N  
LDAP_DOMAIN=MODELBANK.COM  
LDAP_SERVER_URL=ldap://10.184.xx.xx.389
```

6.1.1 User Releases

Single user can be mapped to many releases. **Make sure that selected default release is available here.** Along with release code user role should be specified

The tool has below User Roles for controlling the access rights

- Release Administrator
- Developer
- TCM User
- VERCON

User will be allowed to perform various tasks based on the Role assigned to the user. Same user can have different role for different releases.

6.1.2 Release Administrator

- This role is meant for project leaders and team leaders and allows them to perform release administration activities
- Users with this role would be allowed to perform the below tasks
 - Creation of Environment(s) for the Release
 - Creation of users
 - Provide access to the Release for required User

6.2 Developer

- This Role is for Developers. Users mapped with this role would be able to access the Function development related features of the Workbench
- User will also be able to Switch between the releases and Environments using the “User Preferences” Option.


6.3 TCM User

- This Role is for meant for users of TCM. Users mapped with this role would be able to access only the TCM screens through the console
- User will also be able to Switch between the releases and Environments using the “User Preferences” Option.

6.4 Vercon

- This Role is for meant for Vercon Team. Users mapped with this role would be able to access only the bulk gen operation through the console
- User will also be able to Switch between the releases and Environments using the “User Preferences” Option.

New User will be created by RADTOOL user. After adding one user as Release Administrator, using same user we can create as many users. Use RADTOOL user to create only one user with role as Release Administrator.



The screenshot shows the 'User Definition' window. On the left, under 'User Details', there are fields for User ID (KARTHEEK), User Name (KARTHEEK), User Password (masked), Default Release (FCIS_145_SUPPORT), and Default Environment (FCIS_145_SUPPORT). On the right, there are options for Save Format (Zip), Work Directory, Excel format (XLS), and checkboxes for XML Formatting and LDAP Authentication. At the bottom, there is a table with columns 'Release Code' and 'User Role'. The table contains one row with 'FCIS_145_SUPPORT' and 'Developer'. At the very bottom, there are fields for Modification Number (5), Maker Id (RADTOOL), and Maker Date Stamp (2022-11-18 18:16:36).

Release Code	User Role
FCIS_145_SUPPORT	Developer

Fig: Creating New User by RADTOOL user

Error Information screen




Fig: After Successful Creation of New User

Modifying User

User can modify by launching detailed user creation screen; Click on enter query; Enter the user id and click on execute query button .It will retrieve user details and display. Except user id all fields can be modified.




Fig: Unlocked User for Modification

6.5 User Summary

This screen will be used to get details of all users already exists in the Workbench. Click on execute query button, it will display all available releases in grid view. Double click on the particular user it will take us to detailed screen.

The screenshot shows a web application window titled "User Summary". At the top, there is a search bar labeled "User ID *" with a magnifying glass icon. To the right of the search bar are buttons for "Search", "Reset", and "Close". Below the search bar is a table with three columns: "User Id", "User Name", and "Default Release". The table contains 13 rows of user data. Each row has a checkbox in the first column. The table is paginated, showing "1 of 2" records. The table is scrollable, with a vertical scrollbar on the right side.

<input type="checkbox"/>	User Id	User Name	Default Release
<input type="checkbox"/>	SKGUBBA	SKGUBBA	FCUBS_12.5.0.0.0
<input type="checkbox"/>	NAMESING	IBOCHOUBA	FCUBS_14.0_SUPP
<input type="checkbox"/>	OBTRDEV	OBTRDEV	OBTR_14.6
<input type="checkbox"/>	ELCM146INV1	ELCM146INV1	FCUBS_14.6.0.0.0
<input type="checkbox"/>	PORAVI		FCUBS_12.5.0.0.0
<input type="checkbox"/>	MTAQHEE	Mohammed Taqhee	FC146INV
<input type="checkbox"/>	RADTOOL	Admin	OBTR_14.6
<input type="checkbox"/>	KARTHEEK	KARTHEEK	FCIS_145_SUPPORT
<input type="checkbox"/>	ELCM144	ELCM144	FCELCM_14.5_SUPPOR
<input type="checkbox"/>	SUSHIPAN	SUSHIPAN	FCELCM_14.5_SUPPOR
<input type="checkbox"/>	ELCM145NLS	ELCM145NLS	FCELCM_14.5_NLS

Fig: Summary Screen for User

6.6 Key Points

1. Use user name RADTOOL to create new release.
2. In Release Creation, Release Code and Release type are mandatory.
3. In Environment creation Environment Code, Release Code, Language and JNDI Name are mandatory.
4. In user creation provide User Id, Password, Default Release, Default environment, Save Format ,Work Directory
5. Default release selected should be available in the user releases multi record grid. Otherwise Login would be un successful

7. Appendix

7.1 File Manager

File Manager Servlet will be shipped along with Workbench sources. This application helps in copying files from one machine to another

This application has to be deployed for successfully deploying files to the FLEXCUBE application server from Workbench

6.1.1 File Manager Deployment

File Manager has to be deployed in the server hosting FLEXCUBE (for which environment is created in Workbench)

IP address of the Workbench server has to be mentioned in the property file of File Manager

Path: **FileManager\WEB-INF\classes\com\ofss\manager**

File: **fileupload.properties**

This file should have the IP address of the server where ODT is hosted. If more than one Workbench server is accessing the same FLEXCUBE application (or in case of servers in cluster), multiple IP address can be provided separated by semi colon




Fig: ODT File Manager path of fileupload.properties

After modifying the property file, file manager has to deploy in the server where FLEXCUBE is hosted.

6.1.2 Maintenance in Development Workbench

File Manager has to be maintained in the environment.(which links to the particular FLEXCUBE environment) .

File Manager url has to be provided in the Server File Manager url as shown in the figure

Format: `http://<ipaddress>:<portnumber>/FileManager/FileManageServlet`

Example: <http://10.184.74.143:7755/FileManager/FileManageServlet>

The screenshot displays the 'Environment Master' application window, which is divided into two main sections: 'Environment Details' and 'Application Details'. The 'Environment Details' section includes fields for Environment Code (FCIS_145_SUPPORT), Release Code (FCIS_145_SUPPORT), Language Code (ENG), Description (FCIS_145_SUPPORT), JNDI name (jdbc/FCIS_145_SUPPORT), and Database Details (Database Instance: FCIS145SUP, Database Port: 1521, Database IP Address: 100.76.156.40, Database Host Name: FCIS145SUP, Database Name: ISSMS145, Database Password: masked). The 'Application Details' section includes fields for Application URL (http://10.184.74.143:7755), Application IP Address (10.184.74.143), Application Name (FCIS_145_SUPP), Application OS (Unix), Application Transfer Type (File Manager), JS Directory Path (/scratch/app/w1032/user/), UI XML Directory Path (/scratch/app/w1032/user/), Server User Name (server1), Server Password (masked), Server Filemanager URL (http://10.184.74.143:7755), File Manager User Name, and File Manager Password. At the bottom, there are buttons for 'Test JNDI' and 'Test Environment', and a status bar showing Modification Number (3), Maker Id (RADTOOL), and Maker Date Stamp (2022-11-18 18:05:55).

Environment Details		Application Details	
Environment Code	FCIS_145_SUPPORT	Application URL	http://10.184.74.143:7755
Release Code	FCIS_145_SUPPORT	Application IP Address	10.184.74.143
Language Code	ENG	Application Name	FCIS_145_SUPP
Description	FCIS_145_SUPPORT	Application OS	Unix
JNDI name	jdbc/FCIS_145_SUPPORT	Application Transfer Type	File Manager
Database Instance	FCIS145SUP	JS Directory Path	/scratch/app/w1032/user/
Database Port	1521	UI XML Directory Path	/scratch/app/w1032/user/
Database IP Address	100.76.156.40	Server User Name	server1
Database Host Name	FCIS145SUP	Server Password	*****
Database Name	ISSMS145	Server Filemanager URL	http://10.184.74.143:7755
Database Password	*****	File Manager User Name	
		File Manager Password	

Test JNDI Test Environment

Modification Number: 3 Maker Id: RADTOOL Maker Date Stamp: 2022-11-18 18:05:55

Fig: Workbench Environment Detailed Screen



Development Workbench - Administration
[May] [2023]
Version 14.7.0.1.0

Oracle Financial Services Software Limited
Oracle Park
Off Western Express Highway
Goregaon (East)
Mumbai, Maharashtra 400 063
India

Worldwide Inquiries:
Phone: +91 22 6718 3000
Fax: +91 22 6718 3001
www.oracle.com/financialservices/

Copyright © [2007], [2023], Oracle and/or its affiliates. All rights reserved.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate failsafe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.