

JMS Configuration Multi Entity Guide
Oracle Banking Digital Experience
Patchset Release 22.2.5.0.0

Part No. F72987-01

October 2024

JMS Configuration Multi Entity Guide

October 2024

Oracle Financial Services Software Limited

Oracle Park

Off Western Express Highway

Goregaon (East)

Mumbai, Maharashtra 400 063

India

Worldwide Inquiries:

Phone: +91 22 6718 3000

Fax: +91 22 6718 3001

www.oracle.com/financialservices/

Copyright © 2006, 2024, Oracle and/or its affiliates. All rights reserved.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate failsafe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.



Table of Contents

1. Preface.....	1-1
1.1 Purpose	1-1
1.2 Audience.....	1-1
1.3 Documentation Accessibility.....	1-1
1.4 Critical Patches.....	1-1
1.5 Diversity and Inclusion.....	1-1
1.6 Conventions.....	1-1
1.7 Screenshot Disclaimer.....	1-2
1.8 Acronyms and Abbreviations.....	1-2
2. Objective and Scope.....	2-1
2.1 Background.....	2-1
2.2 Objective and Scope.....	2-1
3. JMS Step 1: Create foreign server in a weblogic server	3-1
3.1 Introduction and Definitions	3-1
4. JMS Step 2 - How to Create a Simple JMS Queue in Weblogic Server	4-1
4.1 Introduction and Definitions	4-1
5. JMS Creation	5-1
5.1 Sample creation of Queue	5-1
5.2 Sample creation of Connection Factory	5-3
5.3 Sample Creation of Topic	5-5
6. JMS Configuration	6-1
6.1 Access Functionality	6-1
6.2 Audit Functionality	6-2
6.3 Authentication Functionality.....	6-3
6.4 ExtSystemReceiver Functionality	6-3
6.5 ExtSystemSender Functionality.....	6-4
6.6 File Upload Functionality	6-5
6.7 GCIF Functionality	6-7
6.8 jpa-cache Functionality	6-16
6.9 Multiple Transaction Approval Functionality	6-17
6.10 NotificationServer	6-18
6.11 OBPMSystemModule	6-19

6.12	Payment Functionality	6-20
6.13	Policies Functionality	6-21
6.14	Reports Functionality	6-21
6.15	UBSSystemModule functionality	6-22
6.16	UserGroupUser Functionality	6-23
6.17	Party Movement Report Functionality	6-23

1. Preface

1.1 Purpose

Welcome to the User Guide for Oracle Banking Digital Experience. This guide explains the operations that the user will follow while using the application.

1.2 Audience

This manual is intended for Customers and Partners who setup and use Oracle Banking Digital Experience.

1.3 Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc>.

Access to Oracle Support

Oracle customers that have purchased support have access to electronic support through My Oracle Support. For information, visit, <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info> or visit <http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs> if you are hearing impaired.

1.4 Critical Patches

Oracle advises customers to get all their security vulnerability information from the Oracle Critical Patch Update Advisory, which is available at [Critical Patches, Security Alerts and Bulletins](#). All critical patches should be applied in a timely manner to ensure effective security, as strongly recommended by [Oracle Software Security Assurance](#).

1.5 Diversity and Inclusion

Oracle is fully committed to diversity and inclusion. Oracle respects and values having a diverse workforce that increases thought leadership and innovation. As part of our initiative to build a more inclusive culture that positively impacts our employees, customers, and partners, we are working to remove insensitive terms from our products and documentation. We are also mindful of the necessity to maintain compatibility with our customers' existing technologies and the need to ensure continuity of service as Oracle's offerings and industry standards evolve. Because of these technical constraints, our effort to remove insensitive terms is ongoing and will take time and external cooperation.

1.6 Conventions

The following text conventions are used in this document:

Convention	Meaning
------------	---------

boldface	Boldface type indicates graphical user interface elements associated with an action, or terms defined in text or the glossary.
<i>Italic</i>	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.
monospace	Monospace type indicates commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter.

1.7 Screenshot Disclaimer

The images of screens used in this user manual are for illustrative purpose only, to provide improved understanding of the functionality; actual screens that appear in the application may vary based on selected browser, theme, and mobile devices.

1.8 Acronyms and Abbreviations


The list of the acronyms and abbreviations that you are likely to find in the manual are as follows:

Abbreviation	Description
OBDX	Oracle Banking Digital Experience

2. Objective and Scope

2.1 Background

JMS (Java Message Service) is an API that provides the facility to create, send and read messages. It provides loosely coupled, reliable communication. Messaging enables distributed communication that is loosely coupled. A component sends a message to a destination, and the recipient can retrieve the message from the destination. However, the sender and the receiver do not have to be available at the same time in order to communicate. In fact, the sender does not need to know anything about the receiver; nor does the receiver need to know anything about the sender. The sender and the receiver need to know only which message format and which destination to use. JMS configuration is required to send message (request) to external system and receive processed message (response) from external system.



2.2 Objective and Scope

Define a common set of messaging concepts and facilities. The scope of this document is to provide steps to configure foreign server for connecting external system using JNDI provider and configure JMS queue to receive data from external system. Foreign server is used to send message to external system with help of JNDI Initial, JNDI connection url, JNDI connection factory and JNDI destination. To configure JMS receiver queue in web logic we have to create JMS server and JMS module. Where JMS module include creation of JMS connection factory, JMS queue and SubDeployment.


3. JMS Step 1: Create foreign server in a weblogic server

3.1 Introduction and Definitions

A Foreign Server represents a JNDI provider that is outside WebLogic server. It contains information that allows a local WebLogic Server instance to reach a remote JNDI provider, thereby allowing for a number of foreign connection factory and destination objects to be defined on one JNDI directory.

3.1.1 Create a JMS Module


- Services > Messaging > JMS Modules
- Select New
- Name: HostSystemModule
- Leave the other options empty
- Targets: obdx_server
- Press Next
- Leave “Would you like to add resources to this JMS system module” unchecked and press Finish .



Name	Type	Scope	Domain Partitions
AsyncFailureLogJMS	JMSSystemResource	Global	
AuditJMS	JMSSystemResource	Global	
EndPointJMSModule	JMSSystemResource	Global	
extXfaceJMSModule	JMSSystemResource	Global	
FileUploadJMS	JMSSystemResource	Global	
HostSystemModule	JMSSystemResource	Global	
UBSSystemModule	JMSSystemResource	Global	

3.1.2 Create a foreign Server

- Services > Messaging > JMS Modules
- Select HostSystemModule and press New
- Select Foreign Server and Next
- Name: ForeignServer (Once you create a foreign server, you cannot rename it. Instead, you must delete it and create another one that uses the new name) and Click Next to proceed to the targeting page or click **Finish** to create the foreign server.



Name	Type	JNDI Name	Subdeployment	Targets
ForeignServer	Foreign Server	N/A	Default Targeting	obdx_server

3.1.3 To configure additional properties for the new foreign server

- Services > Messaging > JMS Modules
- Select HostSystemModule
- Click on ForeignServer
- On the Configuration> General tab
- Enter Following details.
 - JNDI Initial: enter the name of the class that must be instantiated to access the JNDI provider. For example (weblogic.jndi.WLInitialContextFactory)
 - JNDI Connection URL: enter the URL that WebLogic Server uses to contact the JNDI provider. (http://IP:port)
- Click **Save**.

The screenshot shows the 'Configuration' page for a foreign server. The 'General' tab is selected. The 'Name' field is 'ForeignServer'. The 'JNDI Initial Context Factory' field is 'weblogic.jndi.WLInitialCont' (highlighted with a yellow box). The 'JNDI Connection URL' field is 'http://mum00aoz.in.oracle.com:6003' (highlighted with a yellow box). The 'JNDI Properties Credential' field is empty. A 'Save' button is at the top left. A descriptive paragraph explains that a foreign server represents a JNDI provider outside the WebLogic Server. To the right of each field is a 'More Info...' link.

3.1.4 Create foreign connection factories

- Services > Messaging > JMS Modules
- Select HostSystemModule
- Click on ForeignServer
- On the Configuration> **Connection Factories** tab press **New**
- Enter Following details
 - Name: enter a name for the foreign connection factory.
 - Local JNDI Name: specify the name that the remote object will be bound to in the local server's JNDI tree and is used to look up the object on the local server.
 - Remote JNDI Name: specify the name of the remote object that will be looked up in the remote JNDI directory.
- Click **Ok**.

Settings for ForeignConnectionFactory

Configuration Notes

Save

A foreign connection factory is a connection factory that resides on another server instance and is accessible via JNDI. A remote connection factory can be used to refer to another instance of WebLogic Server running in a different cluster or server, or a foreign provider, as long as that provider supports JNDI.

Use this page to create a foreign connection factory.

Name: ForeignConnectionFactory The name of this foreign connection factory. [More Info...](#)

Local JNDI Name: HostQCF The name that the remote object will be bound to in the local server's JNDI tree. This is the name that should be used to look up the object on the local server. [More Info...](#)

Remote JNDI Name: HostQCF The name of the remote object that will be looked up in the remote JNDI directory. [More Info...](#)

Settings for ForeignServer

Configuration Subdeployment Notes

General Destinations Connection Factories

A foreign connection factory represents a connection factory that resides on another server, and which is accessible via JNDI. A remote connection factory can be used to refer to another instance of WebLogic Server running in a different cluster or server, or a foreign provider, as long as that provider supports JNDI.

This page summarizes the foreign connection factories that have been created for this domain.

[Customize this table](#)

Foreign Connection Factories (Filtered - More Columns Exist)

New Delete Showing 1 to 1 of 1 Previous | Next

Name	Local JNDI Name	Remote JNDI Name
ForeignConnectionFactory	HostQCF	HostQCF

New Delete Showing 1 to 1 of 1 Previous | Next

3.1.5 Create foreign destinations

- Services > Messaging > JMS Modules
- Select HostSystemModule
- Click on ForeignServer
- On the Configuration>Destination tab press New
- Enter Following details
 - Name: enter a name for the foreign destination.
 - Local JNDI Name: specify the name that the remote object will be bound to in the local server's JNDI tree and is used to look up the object on the local server.
 - Remote JNDI Name: specify the name of the remote object that will be looked up in the remote JNDI directory.
- Click Ok.

Settings for ForeignDestination

Configuration Notes

Save

A foreign destination (topic or queue) is a destination on a remote server. When this destination is looked up on the local server, a look-up will be performed automatically on the remote JNDI directory, and the object will be returned from that directory.

Use this page to configure a foreign destination.

Name: ForeignDestination

The name of this foreign destination. [More Info...](#)

Local JNDI Name: HostProcess

The name that the remote object will be bound to in the local server's JNDI tree. This is the name that should be used to look up the object on the local server. [More Info...](#)

Remote JNDI Name: HostProcess

The name of the remote object that will be looked up in the remote JNDI directory. [More Info...](#)

Configuration Subdeployment Notes

General Destinations Connection Factories

A foreign destination (topic or queue) can be found on a remote server. When this destination is looked up on the local server, a look-up will be performed automatically on the remote JNDI directory, and the object will be returned from that directory.

This page summarizes the foreign destinations that have been created for this domain.

[Customize this table](#)

Foreign Destinations

New	Delete	Showing 1 to 1 of 1		Previous	Next
☐	Name	Local JNDI Name	Remote JNDI Name		
☐	ForeignDestination	HostProcess	HostProcess		
New	Delete	Showing 1 to 1 of 1		Previous	Next

4. JMS Step 2 - How to Create a Simple JMS Queue in Weblogic Server

4.1 Introduction and Definitions

A JMS queue in Weblogic Server is associated with a number of additional resources:

JMS Server

A JMS server acts as a management container for resources within JMS modules. Some of its responsibilities include the maintenance of persistence and state of messages and subscribers. A JMS server is required in order to create a JMS module.

JMS Module

A JMS module is a definition which contains JMS resources such as queues and topics. A JMS module is required in order to create a JMS queue.

Subdeployment

JMS modules are targeted to one or more WLS instances or a cluster. Resources within a JMS module, such as queues and topics are also targeted to a JMS server or WLS server instances. A subdeployment is a grouping of targets. It is also known as advanced targeting.

Connection Factory

A connection factory is a resource that enables JMS clients to create connections to JMS destinations.

JMS Queue

A JMS queue (as opposed to a JMS topic) is a point-to-point destination type. A message is written to a specific queue or received from a specific queue.

The objects used in this example are:


Object Name	Type	JNDI Name
ExtXfaceJMSServer	JMS Server	
extXfaceJMSModule	JMS Module	
extXfaceSubdeployment	Subdeployment	
ReceiverQCF	Connection Factory	

Object Name	Type	JNDI Name
ReceiverQueue	JMS Queue	


1. Configuration Steps-The following steps are done in the WebLogic Server Console, beginning with the left-hand navigation menu.

Create Persistent store-


- Here you have to Create a new persistent store (Once the persistent store is created that can be used for both sender and receiver server. Hence there is no need to create a different persistent store for two different servers.) Hence Before creating a JMS server you need to create the Persistent store if its not already created. Follow the steps shown below for creating a persistent store.
- Select **Services > Persistent Stores**.




First Select Lock & Edit as shown-



- Select new and the select create FileStore from the list as shown below-



- Give the name of the filestore. Example- **EndPointFS** and the Directory location, example **/scratch/obdx/wls**. Directory location field is optional and the path given above is just an example , it may vary according to the server.
- Click **Next**.
- Select the target server as shown in following snapshot-



- Click **Finish**.

4.1.1 Create a JMS Server

Services > Messaging > JMS Servers



- Select **New**.

JMS Servers (Filtered - More Columns Exist)

[New](#) [Delete](#) Showing 1 to 6 of 6 [Previous](#) | [Next](#)

☐	Name ↕	Persistent Store	Target	Current Target	Health	Scope	Domain Partitions
☐	AsyncFailureLogJMServer	AsyncFailureLogFileStore	obdx_server1	obdx_server1		Global	
☐	AuditJMServer	AuditFileStore	obdx_server1	obdx_server1		Global	
☐	ExtxfaceReceiverServer	EndPointFS	obdx_server1	obdx_server1		Global	
☐	ExtxfaceSenderServer	EndPointFS	obdx_server1	obdx_server1		Global	
☐	FileUploadJMServer	FileUploadFileStore	obdx_server1	obdx_server1		Global	
☐	ReportsJMServer	ReportsFileStore	obdx_server1	obdx_server1		Global	

[New](#) [Delete](#) Showing 1 to 6 of 6 [Previous](#) | [Next](#)

- Name: Give name as for example-**ExtxfaceReceiverServer** .
- After naming the server **Click next** as shown in following example screenshot.

Create a New JMS Server

[Back](#) [Next](#) [Finish](#) [Cancel](#)

JMS Server Properties

The following properties will be used to identify your new JMS Server.

* Indicates required fields

What would you like to name your new JMS server?

* Name:

Would you like this new JMS server to be restricted to a specific resource group template or resource group ?

Scope:

[Back](#) [Next](#) [Finish](#) [Cancel](#)

- **Persistent Store**: Select the name Persistent store from the dropdown list which was created in the previous step. Example-**EndPointFS**.
- Click **Next**.

Create a New JMS Server

Back Next Finish Cancel

Select Persistent Store

Specify a persistent store for the new JMS server.

Persistent Store: EndPointFS Create a New Store

Back Next Finish Cancel

- **Target:** Target should Point to the **Weblogic server cluster** as in this case target is set to **obdx_server1** cluster. (Or any other available cluster).
- Click **Finish**.

Create a New JMS Server

Back Next Finish Cancel

Select targets

Select the server instance or migratable target on which you would like to deploy this JMS server.

Target: obdx_server1

Back Next Finish Cancel

The JMS server should now be visible in the list.

[Customize this table](#)

JMS Servers (Filtered - More Columns Exist)

Click the **Lock & Edit** button in the Change Center to activate all the buttons on this page.


Name	Persistent Store	Target	Current Target	Health	Scope	Domain Partitions
AsyncFailureLogJMServer	AsyncFailureLogFileStore	obdx_server1	obdx_server1		Global	
AuditJMServer	AuditFileStore	obdx_server1	obdx_server1		Global	
ExbfaceReceiverServer	EndPointFS	obdx_server1	obdx_server1		Global	
ExbfaceSenderServer	EndPointFS	obdx_server1	obdx_server1		Global	
FileUploadJMServer	FileUploadFileStore	obdx_server1	obdx_server1		Global	
ReportsJMServer	ReportsFileStore	obdx_server1	obdx_server1		Global	

4.1.2 Create a JMS Module

- Services > Messaging > JMS Modules.



- Select **New**.



- Name: Provide name for JMS Module.
- Leave **the other options empty**.
- Click **Next**.

What would you like to name your System Module?

* **Name:**

Would you like this new JMS System Module to be restricted to a specific resource group template or resource group ?

Scope:

What would you like to name the descriptor file name? If you do not provide a name, a default will be assigned.

Descriptor File Name:

Where would like to place the descriptor for this System Module, relative to the jms configuration sub-directory of your domain?

Location In Domain:

- **Targets: Obdx_Cluster** (or choose any other clusters available).
- **Press Next.**

Targets :

Servers
☐ AdminServer

Clusters
☒ obdx_cluster
☒ All servers in the cluster
☐ Part of the cluster
☐ obdx_server1

Leave **“Would you like to add resources to this JMS system module”** unchecked and press **Finish** .

Create JMS System Module

Add resources to this JMS system module

Use this page to indicate whether you want to immediately add resources to this JMS system module after it is created. JMS resources include queues, topics, connection factories, and such.

☐ **Would you like to add resources to this JMS system module?**

Customize this table

JMS Modules

New Delete Showing 1 to 9 of 9 Previous | Next

☐	Name ↕	Type	Scope	Domain Partitions
☐	AsyncFailureLogJMS	JMSSystemResource	Global	
☐	AuditJMS	JMSSystemResource	Global	
☐	ExtbfacerReceiverModule	JMSSystemResource	Global	
☐	ExtbfacerReceiverModule2	JMSSystemResource	Global	
☐	ExtbfacerSenderModule	JMSSystemResource	Global	
☐	ExtbfacerSenderModule2	JMSSystemResource	Global	
☐	FileUploadJMS	JMSSystemResource	Global	
☐	ReportsJMSModule	JMSSystemResource	Global	
☐	UBSSystemModule	JMSSystemResource	Global	

New Delete Showing 1 to 9 of 9 Previous | Next

4.1.3 Create a SubDeployment

A subdeployment is not necessary for the JMS queue to work, but it allows you to easily target subcomponents of the JMS module to a single target or group of targets. We will use the subdeployment in this example to target the following connection factory and JMS queue to the JMS server we created earlier.

- Services > Messaging > JMS Modules.
- Select **ExtbfacerReceiverModule**.

Customize this table

JMS Modules

New Delete Showing 1 to 9 of 9 Previous | Next

☐	Name ↕	Type	Scope	Domain Partitions
☐	AsyncFailureLogJMS	JMSSystemResource	Global	
☐	AuditJMS	JMSSystemResource	Global	
☐	ExtbfacerReceiverModule	JMSSystemResource	Global	
☐	ExtbfacerReceiverModule2	JMSSystemResource	Global	
☐	ExtbfacerSenderModule	JMSSystemResource	Global	
☐	ExtbfacerSenderModule2	JMSSystemResource	Global	
☐	FileUploadJMS	JMSSystemResource	Global	
☐	ReportsJMSModule	JMSSystemResource	Global	
☐	UBSSystemModule	JMSSystemResource	Global	

New Delete Showing 1 to 9 of 9 Previous | Next

- Select the **Subdeployments** tab and click **New**.

Settings for ExtxfaceReceiverModule

Configuration **Subdeployments** Targets Security Notes

This page displays subdeployments created for a JMS system module. A subdeployment is a mechanism by which JMS module resources (such as queues, topics, and connection factories) are grouped and targeted to a server resource (such as JMS servers, server instances, or cluster).

[Customize this table](#)

Subdeployments

[New](#) [Delete](#) Showing 1 to 1 of 1 Previous | Next

☐ Name	Resources	Targets
☐ ExtxfaceReceiverSubDep	ExtxfaceReceiverQueue	ExtxfaceReceiverServer

[New](#) [Delete](#) Showing 1 to 1 of 1 Previous | Next

- Subdeployment Name: give subdeployment name. example- **ExtxfaceReceiverSubDep**
- Press **Next**.

Create a New Subdeployment

[Back](#) [Next](#) [Finish](#) [Cancel](#)

Subdeployment Properties

The following properties will be used to identify your new subdeployment.

* Indicates required fields

* Subdeployment Name:

[Back](#) [Next](#) [Finish](#) [Cancel](#)

- Here you can select the target(s) for the subdeployment. You can choose either Servers (i.e. WebLogic managed servers, such as the **obdx_server**) or JMS Servers such as the JMS Server created earlier. As the purpose of our subdeployment in this example is to target a specific JMS server, we will choose the JMS Server option. Select the **ExtxfaceReceiverServer** created earlier.
- Press **Finish**.

Targets

Please select targets for the Subdeployment

Clusters

☐ obdx_cluster

☐ All servers in the cluster

☐ Part of the cluster

☐ obdx_server1

JMS Servers

☐ AsyncFailureLogJMSServer

☐ AuditJMSServer

☒ ExtxfaceReceiverServer

☐ ExtxfaceSenderServer

☐ FileUploadJMSServer

☐ ReportsJMSServer

[Back](#) [Next](#) [Finish](#) [Cancel](#)

4.1.4 Create a Connection Factory

- Services > Messaging > JMS Modules
- Select **ExtxfaceReceiverModule** and press **New**.

Customize this table

JMS Modules

New Delete Showing 1 to 9 of 9 Previous | Next

☐	Name	Type	Scope	Domain Partitions
☐	AsyncFailureLogJMS	JMSSystemResource	Global	
☐	AuditJMS	JMSSystemResource	Global	
☐	ExtxfaceReceiverModule	JMSSystemResource	Global	
☐	ExtxfaceReceiverModule2	JMSSystemResource	Global	
☐	ExtxfaceSenderModule	JMSSystemResource	Global	
☐	ExtxfaceSenderModule2	JMSSystemResource	Global	
☐	FileUploadJMS	JMSSystemResource	Global	
☐	ReportsJMSModule	JMSSystemResource	Global	
☐	UBSSystemModule	JMSSystemResource	Global	

New Delete Showing 1 to 9 of 9 Previous | Next

Customize this table

Summary of Resources

New Delete Showing 1 to 2 of 2 Previous | Next

☐	Name	Type	JNDI Name	Subdeployment	Targets
☐	ExtxfaceReceiverQCF	Connection Factory	ExtSystemReceiverQCF	Default Targeting	obdx_server1
☐	ExtxfaceReceiverQueue	Queue	ExtSystemReceiverQueue	ExtxfaceReceiverSubDep	ExtxfaceReceiverServer

New Delete Showing 1 to 2 of 2 Previous | Next

- Select **Connection Factory** and click **Next**.

Create a New JMS System Module Resource

Back Next Finish Cancel

Choose the type of resource you want to create.

Use these pages to create resources in a JMS system module, such as queues, topics, templates, and connection factories.

Depending on the type of resource you select, you are prompted to enter basic information for creating the resource. For targetable resources, like stand-alone queues and topics, connection factories, distributed queues and topics, foreign servers, and JMS SAF destinations, you can also proceed to targeting pages for selecting appropriate server targets. You can also associate targetable resources with subdeployments, which is an advanced mechanism for grouping JMS module resources and the members to server resources.

☒ **Connection Factory** Defines a set of connection configuration parameters that are used to create connections for JMS clients. [More Info...](#)

☐ Queue Defines a point-to-point destination type, which are used for asynchronous peer communications. A message delivered to a queue is distributed to only one consumer. [More Info...](#)

☐ Topic Defines a publish/subscribe destination type, which are used for asynchronous peer communications. A message delivered to a topic is distributed to all topic consumers. [More Info...](#)

- Name: Give name of the connection factory example- **ExtxfaceReceiverQCF**.
JNDI Name: **ExtSystemReceiverQCF**.
- Click **Next**.

Create a New JMS System Module Resource

Back Next Finish Cancel

Connection Factory Properties

The following properties will be used to identify your new connection factory. The current module is ExtfaceReceiverModule.
* Indicates required fields

What would you like to name your new connection factory?

* Name: ExtfaceReceiverQCF

What JNDI Name would you like to use to look up your new connection factory?

JNDI Name: ExtSystemReceiverQCF

The Connection Factory Subscription Sharing Policy Subscribers can be used to control which subscribers can access new subscriptions. Should subscriptions created using this factory be sharable?

Subscription Sharing Policy: Exclusive

The Client ID Policy indicates whether more than one JMS connection can use the same Client ID. Oracle recommends setting the Client ID policy to Unrestricted if sharing durable subscribers. Subscriptions created with different Client ID policies are always treated as independent subscriptions. What Client ID Policy would you like to use?

Client ID Policy: Restricted

A connection factory can limit the number of messages that can be queued for an asynchronous session. Should this connection factory impose a limit?

Maximum Messages per Session: 10

- Select Default Targeting Enabled and Press **Finish**
- The connection factory should be listed on the following page with **Default Targeting** as Subdeployment and WebLogic cluster as the target.

4.1.5 Create a JMS Queue

- Services > Messaging > JMS Modules
- Select **ExtfaceReceiverModule** and Click **New**.

Customize this table

JMS Modules

New Delete Showing 1 to 9 of 9 Previous Next

Name	Type	Scope	Domain Partitions
AsyncFailureLogJMS	JMSSystemResource	Global	
AuditJMS	JMSSystemResource	Global	
ExtfaceReceiverModule	JMSSystemResource	Global	
ExtfaceReceiverModule2	JMSSystemResource	Global	
ExtfaceSenderModule	JMSSystemResource	Global	
ExtfaceSenderModule2	JMSSystemResource	Global	
FileUploadJMS	JMSSystemResource	Global	
ReportsJMSModule	JMSSystemResource	Global	
UBSSystemModule	JMSSystemResource	Global	

New Delete Showing 1 to 9 of 9 Previous Next

Customize this table

Summary of Resources

New Delete Showing 1 to 2 of 2 Previous Next

Name	Type	JNDI Name	Subdeployment	Targets
ExtfaceReceiverQCF	Connection Factory	ExtSystemReceiverQCF	Default Targeting	obdx_server1
ExtfaceReceiverQueue	Queue	ExtSystemReceiverQueue	ExtfaceReceiverSubDep	ExtfaceReceiverServer

New Delete Showing 1 to 2 of 2 Previous Next

- Select **Queue** and Click **Next**.

Back Next Finish Cancel

Choose the type of resource you want to create.

Use these pages to create resources in a JMS system module, such as queues, topics, templates, and connection factories.

Depending on the type of resource you select, you are prompted to enter basic information for creating the resource. For targetable resources, like stand-alone queues and topics, connection factories, distributed queues and topics, foreign servers, and JMS SAF destinations, you can also proceed to targeting pages for selecting appropriate server targets. You can also associate targetable resources with subdeployments, which is an advanced mechanism for grouping JMS module resources and the members to server resources.

☐ Connection Factory	Defines a set of connection configuration parameters that are used to create connections for JMS clients. More Info...
☒ Queue	Defines a point-to-point destination type, which are used for asynchronous peer communications. A message delivered to a queue is distributed to only one consumer. More Info...
☐ Topic	Defines a publish/subscribe destination type, which are used for asynchronous peer communications. A message delivered to a topic is distributed to all topic consumers. More Info...
☐ Distributed Queue	Defines a set of queues that are distributed on multiple JMS servers, but which are accessible as a single, logical queue to JMS clients. More Info...

- **Name:** Provide name of the message queue. example- **ExtxfaceReceiverQueue**.
JNDI Name: Provide JNDI name. example- **ExtSystemReceiverQueue**.
Template: None.
- Press **Next**.

Create a New JMS System Module Resource

Back Next Finish Cancel

JMS Destination Properties

The following properties will be used to identify your new Queue. The current module is ExtxfaceReceiverModule.

* Indicates required fields

* Name: ExtxfaceReceiverQueue

JNDI Name: ExtSystemReceiverQueue

Template: None ▼

Back Next Finish Cancel

- **Subdeployments:** Give the name of the sub-deployment name in which Queue is supposed to be added. **Example-** ExtxfaceReceiverSubDep.
- Select the Target as **ExtxfaceReceiverServer**
Click **Finish**.

Back Next Finish Cancel

The following properties will be used to target your new JMS system module resource

Use this page to select a subdeployment to assign this system module resource. A subdeployment is a mechanism by which JMS resources are grouped and targeted to a server instance, cluster, or SAF agent. If necessary, you can create a new subdeployment by clicking the **Create a New Subdeployment** button. You can also reconfigure subdeployment targets later by using the parent module's subdeployment management page.

Select the subdeployment you want to use. If you select (none), no targeting will occur.

Subdeployments: **ExtxfaceReceiverSubDep** Create a New Subdeployment

What targets do you want to assign to this subdeployment?

Targets :

JMS Servers
☐ AsyncFailureLogJMServer
☐ AuditJMServer
☒ ExtxfaceReceiverServer
☐ ExtxfaceSenderServer
☐ FileUploadJMServer
☐ ReportsJMServer

The **ReceiverQueue** should be listed on the following page with Sub-deployment as **ExtxfaceReceiverSubDep** and target as **ExtxfaceReceiverServer**.

Customize this table

Summary of Resources

New Delete Showing 1 to 2 of 2 Previous Next

Name	Type	JNDI Name	Subdeployment	Targets
ExtxfaceReceiverQCF	Connection Factory	ExtSystemReceiverQCF	Default Targeting	obdx_server1
ExtxfaceReceiverQueue	Queue	ExtSystemReceiverQueue	ExtxfaceReceiverSubDep	ExtxfaceReceiverServer

New Delete Showing 1 to 2 of 2 Previous Next

Confirm the resources for the **ExtxfaceReceiverModule**. Using the Domain Structure tree, navigate to Services > Messaging > JMS Modules then select **ExtxfaceReceiverModule**

Domain Structure

- obdx_domain
 - Domain Partitions
 - Environment
 - Deployments
 - Services
 - Messaging
 - JMS Servers
 - Store-and-Forward Agents
 - JMS Modules**
 - Path Services
 - Bridges
 - Data Sources
 - Persistent Stores

How do I...

- Configure JMS system modules
- Configure resources for JMS system modules

System Status

Customize this table

JMS Modules

New Delete Showing 1 to 9 of 9 Previous Next

Name	Type	Scope	Domain Partitions
AsyncFailureLogJMS	JMSSystemResource	Global	
AuditJMS	JMSSystemResource	Global	
ExtxfaceReceiverModule	JMSSystemResource	Global	
ExtxfaceReceiverModule2	JMSSystemResource	Global	
ExtxfaceSenderModule	JMSSystemResource	Global	
ExtxfaceSenderModule2	JMSSystemResource	Global	
FileUploadJMS	JMSSystemResource	Global	
ReportsJMSModule	JMSSystemResource	Global	
UBSSystemModule	JMSSystemResource	Global	

New Delete Showing 1 to 9 of 9 Previous Next

You should see the following resources-

[Customize this table](#)

Summary of Resources

[New](#) [Delete](#) Showing 1 to 2 of 2 [Previous](#) | [Next](#)

☐	Name 	Type	JNDI Name	Subdeployment	Targets
☐	ExtbfacerReceiverQCF	Connection Factory	ExtSystemReceiverQCF	Default Targeting	obdx_server1
☐	ExtbfacerReceiverQueue	Queue	ExtSystemReceiverQueue	ExtbfacerReceiverSubDep	ExtbfacerReceiverServer

[New](#) [Delete](#) Showing 1 to 2 of 2 [Previous](#) | [Next](#)

The JMS queue is now complete and can be accessed using the JNDI names

ExtSystemReceiverQCF And ExtSystemReceiverQueue..

Note: Repeat the above process from the step 4.1 i.e Create File-Store to create the JMS Configuration for Sender module. Separate JMS Server , Module and Queues would get created for Sender.

5. JMS Creation

5.1 Sample creation of Queue

1. Step 1 :

Go to the path where you want to create the Queue.

(E.g., Home > Services > Messaging > JMS Modules > MultipleTransactionApprovalJMSModule)

Get the lock and edit in WebLogic.

Click on **New**.

Then select uniform Queue from the options.

Back Next Finish Cancel

Choose the type of resource you want to create.

Use these pages to create resources in a JMS system module, such as queues, topics, templates, and connection factories.

Depending on the type of resource you select, you are prompted to enter basic information for creating the resource. For targetable resources, like stand-alone queues and topics, connection factories, distributed queues and topics, foreign servers, and JMS SAF destinations, you can also proceed to targeting pages for selecting appropriate server targets. You can also associate targetable resources with subdeployments, which is an advanced mechanism for grouping JMS module resources and the members to server resources.

☐ Connection Factory	Defines a set of connection configuration parameters that are used to create connections for JMS clients. More Info...
☐ Queue	Defines a point-to-point destination type, which are used for asynchronous peer communications. A message delivered to a queue is distributed to only one consumer. More Info...
☐ Topic	Defines a publish/subscribe destination type, which are used for asynchronous peer communications. A message delivered to a topic is distributed to all topic consumers. More Info...
☒ Distributed Queue	Defines a set of queues that are distributed on multiple JMS servers, but which are accessible as a single, logical queue to JMS clients. More Info...
☐ Distributed Topic	Defines a set of topics that are distributed on multiple JMS servers, but which are accessible as a single, logical topic to JMS clients. More Info...
☐ Foreign Server	Defines foreign messaging providers or remote WebLogic Server instances that are not part of the current domain. More Info...
☐ Quota	Controls the allotment of system resources available to destinations. More Info...
☐ Destination Sort Key	Defines a unique sort order that destinations can apply to arriving messages. More Info...
☐ JMS Template	Defines a set of default configuration settings for multiple destinations. More Info...
☐ SAF Imported Destinations	Defines a collection of imported store-and-forward (SAF) destinations. A SAF destination is a representation of a queue or topic in a remote server instance or cluster that is imported into the local cluster or server instance, so that the local server instance or cluster can send messages to the remote server instance or cluster. More Info...

2. Step 2 : Then fill in the data such as Name of the Queue and the JNDI Name from the Table given at the start of the document. Then click on **Next**.

Create a New JMS System Module Resource

Back Next Finish Cancel

JMS Distributed Destination Properties

The following properties will be used to identify your new Distributed Queue. The current module is MultipleTransactionApprovalJMS

* Indicates required fields

What would you like to name your new destination?

* Name:

What JNDI Name would you like to use to look up your new destination?

JNDI Name:

Queue members may be either created uniformly from a common configuration, or created and weighted individually to fine tune performance. How would you like to create queue members?

Destination Type:

Templates provide an efficient means of defining multiple destinations with similar configuration values. Would you like to use a template for this destination?

Template:

Back Next Finish Cancel

3. Step 3 : Then select on advanced targeting.

Create a New JMS System Module Resource

Back Next Finish Advanced Targeting Cancel

The following properties will be used to target your new JMS system module resource

Use this page to view and accept the default targets where this JMS resource will be targeted. The default targets are based on the parent JMS system module targets. If you do not want to accept the default targets, then click **Advanced Targeting** to use the subdeployment mechanism for targeting this resource.

The following JMS module targets will be used as the default targets for your new JMS system module resource. If the module's targets are changed, this resource will also be retargeted appropriately.

Targets :

Clusters

- ☒ obdx_Cluster
 - ☐ All servers in the cluster
 - ☐ Part of the cluster
 - ☐ obdx_server1

Back Next Finish Advanced Targeting Cancel

4. Step 4 : Then select MultipleTransactionApprovalSD from the subdeployments dropdown and make sure to select MultipleTransactionApprovalJMSServer in the targets and then click on finish.

Select the subdeployment you want to use. If you select (none), no targeting will occur.

Subdeployments: MultipleTransactionApprovalSD Create a New Subdeployment

(none)

MultipleTransactionApprovalSD

What targets do you want to assign to

Targets :

JMS Servers
☐ AccountAccessJMSServer
☐ AuditJMSServer
☐ AuthJMSServer
☐ ExtSystemReceiver
☐ ExtSystemSender
☐ FileUploadJMSServer
☐ GcifJMSServer
☐ JPACacheJMSServer
☒ MultipleTransactionApprovalJMSServer
☐ PartyMovementReportJMSServer
☐ PaymentJMSServer
☐ PoliciesJMSServer
☐ ReportsJMSServer
☐ UserGroupUserJMSServer

5.2 Sample creation of Connection Factory

1. Step 1 : Go to the path where you want to create a connection Factory.

(E.g., Home > Services > Messaging > JMS Modules > MultipleTransactionApprovalJMSModule)

Get the lock and edit in WebLogic. Click on New. Then select Connection Factory from the options.

Note : If the Connection Factory is already present with another Sub deployment and Target please delete it and make it fresh

Create a New JMS System Module Resource

Back Next Finish Cancel

Choose the type of resource you want to create.

Use these pages to create resources in a JMS system module, such as queues, topics, templates, and connection factories.

Depending on the type of resource you select, you are prompted to enter basic information for creating the resource. For targetable resources, like stand-alone queues and topics, connection factories, distributed queues and topics, foreign servers, and JMS SAF destinations, you can also proceed to targeting pages for selecting appropriate server targets. You can also associate targetable resources with subdeployments, which is an advanced mechanism for grouping JMS module resources and the members to server resources.

☒ Connection Factory	Defines a set of connection configuration parameters that are used to create connections for JMS clients. More Info...
☐ Queue	Defines a point-to-point destination type, which are used for asynchronous peer communications. A message delivered to a queue is distributed to only one consumer. More Info...
☐ Topic	Defines a publish/subscribe destination type, which are used for asynchronous peer communications. A message delivered to a topic is distributed to all topic consumers. More Info...
☐ Distributed Queue	Defines a set of queues that are distributed on multiple JMS servers, but which are accessible as a single, logical queue to JMS clients. More Info...
☐ Distributed Topic	Defines a set of topics that are distributed on multiple JMS servers, but which are accessible as a single, logical topic to JMS clients. More Info...
☐ Foreign Server	Defines foreign messaging providers or remote WebLogic Server instances that are not part of the current domain. More Info...
☐ Quota	Controls the allotment of system resources available to destinations. More Info...

2. Step 2 : Then fill out the Name and JNDI name of the connection Factory that you are creating.

Create a New JMS System Module Resource

Back Next Finish Cancel

Connection Factory Properties

The following properties will be used to identify your new connection factory. The current module is MultipleTransactionApprovalJMS.

* Indicates required fields

What would you like to name your new connection factory?

* Name: MultipleTransactionServiceIn

What JNDI Name would you like to use to look up your new connection factory?

JNDI Name: MultipleTransactionServiceInvocationQCF

The Connection Factory Subscription Sharing Policy Subscribers can be used to control which subscribers can access new subscriptions. Should subscriptions created using this factory be sharable?

Subscription Sharing Policy: Exclusive

The Client ID Policy indicates whether more than one JMS connection can use the same Client ID. Oracle recommends setting the Client ID policy to Unrestricted if sharing durable subscribers. Subscriptions created with different Client ID policies are always treated as independent subscriptions. What Client ID Policy would you like to use?

Client ID Policy: Restricted

A connection factory can limit the number of messages that can be queued for an asynchronous session. Should this connection factory impose a limit?

Maximum Messages per Session: 10

Should this connection factory create sessions that are JTA aware, and create XA queues and XA topics?

☒ XA Connection Factory Enabled

Should the authenticated user name be attached to sent messages if the JMS destination is configured to support this behavior?

☐ Attach JMSX UserID

Back Next Finish Cancel

3. Step 3 : Then on the next page. Select advanced Targeting.

[Back](#) [Next](#) [Finish](#) [Advanced Targeting](#) [Cancel](#)

The following properties will be used to target your new JMS system module resource

Use this page to view and accept the default targets where this JMS resource will be targeted. The default targets are based on the parent JMS system module targets. If you do not want to accept the default targets, then click **Advanced Targeting** to use the subdeployment mechanism for targeting this resource.

The following JMS module targets will be used as the default targets for your new JMS system module resource. If the module's targets are changed, this resource will also be retargeted appropriately.

And then select MultipleTransactionApprovalSD from the Sub deployments dropdown.

Select the subdeployment you want to use. If you select (none), no targeting will occur.

Subdeployments: MultipleTransactionApprovalSD ▼ Create a New Subdeployment

(none)

What targets do you want to assign to MultipleTransactionApprovalSD

Targets :

Then select MultipleTransactionApprovalJMSServer from the targets and then click on **Finish**.

JMS Servers
☐ AccountAccessJMSServer
☐ AuditJMSServer
☐ AuthJMSServer
☐ ExtSystemReceiver
☐ ExtSystemSender
☐ FileUploadJMSServer
☐ GcifJMSServer
☐ JPAcacheJMSServer
☒ MultipleTransactionApprovalJMSServer
☐ PartyMovementReportJMSServer
☐ PaymentJMSServer
☐ PoliciesJMSServer
☐ ReportsJMSServer
☐ UserGroupUserJMSServer

This process need to be repeated for all the Queues and Connection Factories given in the table a the start of the document.

Once the entire process is done. The final list of the Queues and the Connection Factories should look something like this.

Summary of Resources

Click the **Lock & Edit** button in the Change Center to activate all the buttons on this page.

Name	Type	JNDI Name	Subdeployment	Targets
MultipleTransactionServiceInvocationQCF	Connection Factory	MultipleTransactionServiceInvocationQCF	MultipleTransactionApprovalSD	MultipleTransactionApprovalJMSServer
MultipleTransactionServiceInvocationQueue	Uniform Distributed Queue	MultipleTransactionServiceInvocationQueue	MultipleTransactionApprovalSD	MultipleTransactionApprovalJMSServer
MultipleTransactionServiceInvocationResponseQCF	Connection Factory	MultipleTransactionServiceInvocationResponseQCF	MultipleTransactionApprovalSD	MultipleTransactionApprovalJMSServer
MultipleTransactionServiceInvocationResponseQueue	Uniform Distributed Queue	MultipleTransactionServiceInvocationResponseQueue	MultipleTransactionApprovalSD	MultipleTransactionApprovalJMSServer
MultipleTransactionServiceInvocationTopic	Uniform Distributed Topic	MultipleTransactionServiceInvocationTopic	Default Targeting	obdx_cluster

And the sub deployments should look something like this.

Subdeployments

Click the **Lock & Edit** button in the Change Center to activate all the buttons on this page.

Name	Resources	Targets
Default Targeting		obdx_cluster
MultipleTransactionApprovalSD	MultipleTransactionServiceInvocationResponseQueue, MultipleTransactionServiceInvocationQueue, MultipleTransactionServiceInvocationQCF, MultipleTransactionServiceInvocationResponseQCF	MultipleTransactionApprovalJMSServer

5.3 Sample Creation of Topic

- Step 1: Go to the following path → Home > Services > Messaging > JMS Modules > MultipleTransactionApprovalJMSModule

Get the lock and edit in WebLogic.

Click on **New**.

Then select Distributed Topic from the options.

☐ Connection Factory	Defines a set of connection configuration parameters that are used to create connections for JMS clients. More Info...
☐ Queue	Defines a point-to-point destination type, which are used for asynchronous peer communications. A message delivered to a queue is distributed to only one consumer. More Info...
☐ Topic	Defines a publish/subscribe destination type, which are used for asynchronous peer communications. A message delivered to a topic is distributed to all topic consumers. More Info...
☐ Distributed Queue	Defines a set of queues that are distributed on multiple JMS servers, but which are accessible as a single, logical queue to JMS clients. More Info...
☒ Distributed Topic	Defines a set of topics that are distributed on multiple JMS servers, but which are accessible as a single, logical topic to JMS clients. More Info...
☐ Foreign Server	Defines foreign messaging providers or remote WebLogic Server instances that are not part of the current domain. More Info...
☐ Quota	Controls the allotment of system resources available to destinations. More Info...
☐ Destination Sort Key	Defines a unique sort order that destinations can apply to arriving messages. More Info...
☐ JMS Template	Defines a set of default configuration settings for multiple destinations. More Info...

- Step 2 :Then fill out the Name and JNDI name of the connection Factory that you are creating.

The screenshot shows the 'Create a New JMS System Module Resource' wizard, specifically the 'JMS Distributed Destination Properties' step. The wizard has a title bar and navigation buttons (Back, Next, Finish, Cancel). The main content area contains the following fields and options:

- JMS Distributed Destination Properties**: The following properties will be used to identify your new Distributed Topic. The current module is MultipleTransactionApprovalJMS. * Indicates required fields.
- Name**: A text input field containing 'SampleTopic1'.
- JNDI Name**: A text input field containing 'SampleTopic1'.
- Destination Type**: A dropdown menu set to 'Uniform'.
- Forwarding Policy**: A dropdown menu set to 'Partitioned'.
- Template**: A dropdown menu set to 'None'.

At the bottom, there are navigation buttons: Back, Next, Finish, and Cancel.

Note: Make sure the Forwarding policy is partitioned.

This is a close-up of the 'Forwarding Policy' dropdown menu. The menu is open, showing three options: 'Partitioned' (selected), 'Replicated', and 'Partitioned' (repeated). The text 'The Forwarding Policy for a topic defines how messages are forwarded to members. What forwarding policy would you like to use for this new destination?' is visible above the dropdown. Below the dropdown, the text 'Templates provide an efficient means of defining multiple destinations with similar configuration values. Would you like to use a template for this destination?' is visible.

- Step 3 :Click on **finish**

The screenshot shows the 'Targets' page of the JMS wizard. The page has a title bar and navigation buttons (Back, Next, Finish, Advanced Targeting, Cancel). The main content area contains the following information:

- Use this page to view and accept the default targets where this JMS resource will be targeted.** The default targets are accept the default targets, then click **Advanced Targeting** to use the subdeployment mechanism for targeting this r
- The following JMS module targets will be used as the default targets for your new JMS system module resource. If the appropriately.**
- Targets :**
- Clusters**: A table with the following content:

Clusters
☒ obdx_Cluster
☐ All servers in the cluster
☐ Part of the cluster
☐ obdx_server1

At the bottom, there are navigation buttons: Back, Next, Finish, Advanced Targeting, and Cancel.

Sample topic is created

Home >Summary of JMS Modules >MultipleTransactionApprovalJMS >Summary of Services >Summary of Service JMS >Summary of JMS Modules >GcifJMS

Messages

The JMS distributed topic was created successfully.

Settings for GcifJMS

☐	OnboardingDraftDeleteTopic	Connection Factory	OnboardingDraftDeleteTopic	GcifSD	GcifJMSServer
☐	OnboardingDraftDeleteTopic	Uniform Distributed Topic	OnboardingDraftDeleteTopic	Default Targeting	obdx_Cluster
☐	SampleQueue	Uniform Distributed Queue	SampleQueue	GcifSD	GcifJMSServer
☐	SampleTopic1	Uniform Distributed Topic	SampleTopic1	Default Targeting	obdx_Cluster
☐	UBSNotificationTCF	Connection Factory	UBSNotificationTCF	GcifSD	GcifJMSServer

NewDelete

Showing 1 to 45 of 45PreviousNext

6. JMS Configuration

6.1 Access Functionality

6.1.1 Regular Access Functionality

Changes to User Account Access when there is change in Party Account Access.

Sr No.	Name	Type	JNDI Name	Subdeployments	Targest
1.	AccountAccessQCF	Connection Factory	AccountAccessQCF	Default Targeting	obdx_cluster
2.	ACCOUNTACCESSQUEUE	Uniform Distributed Queue	ACCOUNTACCESSQUEUE	AccessSD	AccessJMSModule

6.1.2 Account Access for a particular bucket

For splitting bulk account access request to multiple requests. If count of accounts is greater than dayone config value then request is split into N buckets which are handled parallelly.

Sr No.	Name	Type	JNDI Name	Subdeployments	Targest
1.	ACCOUNT_ACCESS_ASYNC_BUCKET_QCF	Connection Factory	ACCOUNT_ACCESS_ASYNC_BUCKET_QCF	Default Targeting	obdx_cluster
2.	ACCOUNT_ACCESS_ASYNC_BUCKET_QUEUE	Uniform Distributed Queue	ACCOUNT_ACCESS_ASYNC_BUCKET_QUEUE	AccessSD	AccessJMSModule

6.1.3 Account Access in Bulk

Each request received on this queue will call Host in paginated manner and update status once completed.

Sr No.	Name	Type	JNDI Name	Subdeployments	Targest
1.	ACCOUNT_ACCESS_ASYNC_BULK_QCF	Connection Factory	ACCOUNT_ACCESS_ASYNC_BULK_QCF	Default Targeting	obdx_cluster
2.	ACCOUNT_ACCESS_ASYNC_BULK_QUEUE	Uniform Distributed Queue	ACCOUNT_ACCESS_ASYNC_BULK_QUEUE	AccessSD	AccessJMSModule

6.1.4 Subdeployment View

Sr. No.	Name	Resources	Subdeployment
1	AccessSD	ACCOUNTACCESSQUEUE, ACCOUNT_ACCESS_ASYNC_BUCKET_QUEUE, ACCOUNT_ACCESS_ASYNC_BULK_QUEUE	AccessJMSModule

6.2 Audit Functionality

6.2.1 Audit Functionality

Sr No.	Name	Type	JNDI Name	Subdeployments	Targest
1.	API_AUDIT_QUEUE	Uniform Distributed Queue	API_AUDIT_QUEUE	AuditSD	AuditJMSServer
2.	AUDITQCF	Connection Factory	AUDITQCF	Default Targeting	obdx_cluster
3.	AUDIT_ANALYTICS_QUEUE	Uniform Distributed Queue	AUDIT_ANALYTICS_QUEUE	AuditSD	AuditJMSServer
4.	AUDIT_QUEUE	Uniform Distributed Queue	AUDIT_QUEUE	AuditSD	AuditJMSServer

6.2.2 Subdeployments Views:

Sr. No.	Name	Resources	Subdeployment
1	AuditSD	AUDIT_QUEUE, API_AUDIT_QUEUE, AUDIT_ANALYTICS_QUEUE	AuditJMSServer

6.3 Authentication Functionality

6.3.1 Authentication Functionality

Sr N o.	Name	Type	JNDI Name	Subdeployments	Targest
1.	AUTHAUDITQCF	Connect ion Factory	AUTHAUDITQCF	Default Targeting	obdx_cluster
2.	AUTH_API_AUDIT_QUEUE	Uniform Distribut ed Queue	AUTH_API_AUDIT_QUEUE	AuthSD	AuthJMSModule

6.3.2 Subdeployment View:

Sr. No.	Name	Resources	Subdeployment
1	AuthSD	AUTH_API_AUDIT_QUEUE	AuthJMSModule

6.4 ExtSystemReceiver Functionality

6.4.1 ExtSystemReceiver Functionality

Sr N o.	Name	Type	JNDI Name	Subdeployment s	Targest
1.	ExtSystemReceive rQCF	Connect ion Factory	ExtSystemReceive rQCF	Default Targeting	obdx_cluster

Sr No.	Name	Type	JNDI Name	Subdeployments	Target
2.	ExtSystemReceiverQueue	Uniform Distributed Queue	ExtSystemReceiverQueue	ExtSystemReceiverSub	ExtSystemReceiver

6.4.2 Subdeployment View :

Sr. No.	Name	Resources	Subdeployment
1	ExtSystemReceiverSub	ExtSystemReceiverQueue	ExtSystemReceiver

6.5 ExtSystemSender Functionality

6.5.1 ExtSystemSender Functionality

Sr No.	Name	Type	JNDI Name	Subdeployments	Target
1.	ExtSystemSenderQCF	ConnectionFactory	ExtSystemSenderQCF	Default Targeting	obdx_cluster
2.	ExtSystemSenderQueue	Uniform Distributed Queue	ExtSystemSenderQueue	ExtSystemSenderSub	ExtSystemSender

6.5.2 Subdeployment View :

Sr. No.	Name	Resources	Subdeployment
1	ExtSystemSenderSub	ExtSystemSenderQueue	ExtSystemSender

6.6 File Upload Functionality

6.6.1 Bulk CMS functionality

Sr N o.	Name	Type	JNDI Name	Subdeployments	Targest
1.	BULKCMS_PREPROCESS	Uniform Distributed Queue	BULKCMS_PREPROCESS	FileUploadSD	FileUploadJMS Server
2.	BULKCMS_RAPPROVAL	Uniform Distributed Queue	BULKCMS_RAPPROVAL	FileUploadSD	FileUploadJMS Server

6.6.2 BULK CORPORATE LOAN PROCESSING AND APPROVAL

S r N o.	Name	Type	JNDI Name	Subdeployments	Targest
1.	BULKCORPORATELOAN_PREPROCESS	Uniform Distributed Queue	BULKCORPORATELOAN_PREPROCESS	Default Targeting	obdx_cluster
2.	BULKCORPORATELOAN_RAPPROVAL	Uniform Distributed Queue	BULKCORPORATELOAN_RAPPROVAL	Default Targeting	obdx_cluster

6.6.3 BULK Electronic Bill Payment Processing and Approval

Sr No	Name	Type	JNDI Name	Subdeployments	Targest
1.	BULKEBPP_PREPROCESS	Uniform Distributed Queue	BULKEBPP_PREPROCESS	FileUploadSD	FileUploadJMSServer
2.	BULKEBPP_RAPPROVAL	Uniform Distributed Queue	BULKEBPP_RAPPROVAL	FileUploadSD	FileUploadJMSServer

6.6.4 BULK PAYMENT FUNCTIONALITY

Sr No.	Name	Type	JNDI Name	Subdeployments	Targest
1.	BULKPAYMENT_PREPROCESS	Uniform Distributed Queue	BULKPAYMENT_PREPROCESS	FileUploadSD	FileUploadJMSServer
2.	BULKPAYMENT_PROCESS	Uniform Distributed Queue	BULKPAYMENT_PROCESS	FileUploadSD	FileUploadJMSServer
3.	BULKPAYMENT_RAPPROVAL	Uniform Distributed Queue	BULKPAYMENT_RAPPROVAL	FileUploadSD	FileUploadJMSServer

6.6.5 BULK SCFCM FUNCTIONALITY

Sr No.	Name	Type	JNDI Name	Subdeployments	Targest
1.	BULKSCFCM_PREPROCESS	Uniform Distributed Queue	BULKSCFCM_PREPROCESS	FileUploadSD	FileUploadJMS Server

6.6.6 Subdeployment View

Sr. No.	Name	Resources	Subdeployment
1	FileUploadSD	RAPPROVAL, PREPROCESS, BULKVAM_RAPPROVAL, BULKVAM_PREPROCESS, BULKTRADEFINANCE_RAPPROVAL, BULKTRADEFINANCE_PREPROCESS, BULKSCFCM_RAPPROVAL, BULKSCFCM_PREPROCESS, BULKPAYMENT_RAPPROVAL, BULKPAYMENT_PREPROCESS, BULKEBPP_RAPPROVAL, BULKEBPP_PREPROCESS, BULKCMS_RAPPROVAL, BULKCMS_PREPROCESS, BULKPAYMENT_PROCESS	FileUploadJMSServer

6.7 GCIF Functionality

6.7.1 Onboarding Draft updation functionality

Updation of GCIF Status after the GCIF is System Rejected by approval.

Sr No.	Name	Type	JNDI Name	Subdeployments	Targest
1.	GcifOnboardingDraftUpdateQCF	Connection Factory	GcifOnboardingDraftUpdateQCF	Default Targeting	obdx_cluster
2.	GcifOnboardingDraftUpdateQueue	Uniform Distributed Queue	GcifOnboardingDraftUpdateQueue	Default Targeting	obdx_cluster

6.7.2 Access point functionality

Changes to Party Account Access is handled by these queues.

S r N o.	Name	Type	JNDI Name	Subdepl oyments	Targes t
1.	GCIF_ACCESS_POINT_U PDATE_QCF	Conne ction Factor y	GCIF_ACCESS_POINT_U PDATE_QCF	Default Targeting	obdx_cl uster
2.	GCIF_ACCESS_POINT_U PDATE_QUEUE	Unifor m Distrib uted Queue	GCIF_ACCESS_POINT_U PDATE_QUEUE	Default Targeting	obdx_cl uster
3.	GCIF_ACCESS_SUBMIT_ QCF	Conne ction Factor y	GCIF_ACCESS_SUBMIT_ QCF	Default Targeting	obdx_cl uster
4.	GCIF_ACCESS_SUBMIT_ QUEUE	Unifor m Distrib uted Queue	GCIF_ACCESS_SUBMIT_ QUEUE	Default Targeting	obdx_cl uster

6.7.3 Report mapping functionality at GCIF level

Sr No.	Name	Type	JNDI Name	Subdeployments	Target
1.	GCIF_GCIFREPORT_MAPPING_QCF	Connection Factory	GCIF_GCIFREPORT_MAPPING_QCF	Default Targeting	obdx_cluster
2.	GCIF_GCIFREPORT_MAPPING_QUEUE	Uniform Distributed Queue	GCIF_GCIFREPORT_MAPPING_QUEUE	Default Targeting	obdx_cluster

6.7.4 GCIF onboarding draft functionality

Submission of GCIF Onboarding Wizard.

Sr No.	Name	Type	JNDI Name	Subdeployments	Target
1.	GCIF_ONBOARDING_DRAFT_QCF	Connection Factory	GCIF_ONBOARDING_DRAFT_QCF	Default Targeting	obdx_cluster
2.	GCIF_ONBOARDING_DRAFT_QUEUE	Uniform Distributed Queue	GCIF_ONBOARDING_DRAFT_QUEUE	Default Targeting	obdx_cluster

6.7.5 GCIF party functionality

Sr No	Name	Type	JNDI Name	Subdeployments	Targest
1.	GCIF_PARTY_FINAL_MIGRATION_QCF	Connection Factory	GCIF_PARTY_FINAL_MIGRATION_QCF	Default Targeting	obdx_cluster
2.	GCIF_PARTY_FINAL_MIGRATION_QUEUE	Uniform Distributed Queue	GCIF_PARTY_FINAL_MIGRATION_QUEUE	Default Targeting	obdx_cluster
3.	GCIF_PARTY_MOVEMENT_REPORT_RESPONSE_QCF	Connection Factory	GCIF_PARTY_MOVEMENT_REPORT_RESPONSE_QCF	Default Targeting	obdx_cluster
4.	GCIF_PARTY_MOVEMENT_REPORT_RESPONSE_QUEUE	Uniform Distributed Queue	GCIF_PARTY_MOVEMENT_REPORT_RESPONSE_QUEUE	Default Targeting	obdx_cluster

6.7.6 GCIF processing party

Updation of GCIF Processing status based on status of various transactions performed in the individual steps.

Sr No.	Name	Type	JNDI Name	Subdeployments	Targest
1.	GCIF_PROCESSING_STATUS_QCF	Connection Factory	GCIF_PROCESSING_STATUS_QCF	Default Targeting	obdx_cluster
2.	GCIF_PROCESSING_STATUS_QUEUE	Uniform Distributed Queue	GCIF_PROCESSING_STATUS_QUEUE	Default Targeting	obdx_cluster

6.7.7 GCIF profile creation and updation functionality

Sr N o.	Name	Type	JNDI Name	Subdeploy ments	Targest
1.	GCIF_PROFILE_CREATE_QCF	Connec tion Factory	GCIF_PROFILE_CREATE_QCF	Default Targeting	obdx_cl uster
2.	GCIF_PROFILE_CREATE_QUEUE	Uniform Distribu ted Queue	GCIF_PROFILE_CREATE_QUEUE	Default Targeting	obdx_cl uster
3.	GCIF_PROFILE_UPDATE_QCF	Connec tion Factory	GCIF_PROFILE_UPDATE_QCF	Default Targeting	obdx_cl uster
4.	GCIF_PROFILE_UPDATE_QUEUE	Uniform Distribu ted Queue	GCIF_PROFILE_UPDATE_QUEUE	Default Targeting	obdx_cl uster

6.7.8 GCIF report mapping functionality at user level

Sr N o.	Name	Type	JNDI Name	Subdeploy ments	Targest
1.	GCIF_REPORT_MAPPING_QCF	Connec tion Factory	GCIF_REPORT_MAPPING_QCF	Default Targeting	obdx_cl uster
2.	GCIF_REPORT_MAPPING_QUEUE	Unifor m Distribu ted Queue	GCIF_REPORT_MAPPING_QUEUE	Default Targeting	obdx_cl uster

6.7.9 GCIF Rule functionality

Create and Update Rule for a GCIf via Onboarding Wizard.

Sr N o.	Name	Type	JNDI Name	Subdeployments	Targest
1.	GCIF_RULE_CREATE_QCF	Connect ion Factory	GCIF_RULE_CREATE_QCF	Default Targeting	obdx_clu ster
2.	GCIF_RULE_CREATE_QUEUE	Uniform Distribut ed Queue	GCIF_RULE_CREATE_QUEUE	Default Targeting	obdx_clu ster
3.	GCIF_RULE_DELETE_QCF	Connect ion Factory	GCIF_RULE_DELETE_QCF	Default Targeting	obdx_clu ster
4.	GCIF_RULE_DELETE_QUEUE	Uniform Distribut ed Queue	GCIF_RULE_DELETE_QUEUE	Default Targeting	obdx_clu ster
5.	GCIF_RULE_UPDATE_QCF	Connect ion Factory	GCIF_RULE_UPDATE_QCF	Default Targeting	obdx_clu ster
6.	GCIF_RULE_UPDATE_QUEUE	Uniform Distribut ed Queue	GCIF_RULE_UPDATE_QUEUE	Default Targeting	obdx_clu ster

6.7.10 GCIF USER ACCESS functionality

Any changes to User account access in GCIF flow will be handled by these queues.

S r N o.	Name	Type	JNDI Name	Subdeploy ments	Targest
1.	GCIF_USERACCESS_S UBMIT_QCF	Conne ction Factor y	GCIF_USERACCESS_S UBMIT_QCF	Default Targeting	obdx_cl uster
2.	GCIF_USERACCESS_S UBMIT_QUEUE	Unifor m Distrib uted Queue	GCIF_USERACCESS_S UBMIT_QUEUE	Default Targeting	obdx_cl uster

6.7.11 GCIF USERGROUP functionality

Create and Update UserGroup for a GCIf via Onboarding Wizard.

S r N o.	Name	Type	JNDI Name	Subdeploy ments	Targest
1.	GCIF_USERGROUP_CR EATE_QCF	Conne ction Factor y	GCIF_USERGROUP_CR EATE_QCF	Default Targeting	obdx_cl uster
2.	GCIF_USERGROUP_CR EATE_QUEUE	Unifor m Distrib uted Queue	GCIF_USERGROUP_CR EATE_QUEUE	Default Targeting	obdx_cl uster
3.	GCIF_USERGROUP_UP DATE_QCF	Conne ction Factor y	GCIF_USERGROUP_UP DATE_QCF	Default Targeting	obdx_cl uster
4.	GCIF_USERGROUP_UP DATE_QUEUE	Unifor m Distrib uted Queue	GCIF_USERGROUP_UP DATE_QUEUE	Default Targeting	obdx_cl uster

6.7.12 GCIF User create and update functionality

Create and Update User for a GCIf via Onboarding Wizard.

Sr N o.	Name	Type	JNDI Name	Subdeploy ments	Targest
1.	GCIF_USER_CREATE_QCF	Connect ion Factory	GCIF_USER_CREATE_QCF	Default Targeting	obdx_clu ster
2.	GCIF_USER_CREATE_QUEUE	Uniform Distribut ed Queue	GCIF_USER_CREATE_QUEUE	Default Targeting	obdx_clu ster
3.	GCIF_USER_UPDATE_QCF	Connect ion Factory	GCIF_USER_UPDATE_QCF	Default Targeting	obdx_clu ster
4.	GCIF_USER_UPDATE_QUEUE	Uniform Distribut ed Queue	GCIF_USER_UPDATE_QUEUE	Default Targeting	obdx_clu ster

6.7.13 GCIF workflow create functionality

Create and Update Workflow for a GCIf via Onboarding Wizard.

Sr N o.	Name	Type	JNDI Name	Subdeploy ments	Targest
1.	GCIF_WORKFLOW_CREATE_QCF	Conne ction Factor y	GCIF_WORKFLOW_CREATE_QCF	Default Targeting	obdx_cl uster

Sr N o.	Name	Type	JNDI Name	Subdeploy ments	Targest
2.	GCIF_WORKFLOW_CREATE_QUEUE	Uniform Distributed Queue	GCIF_WORKFLOW_CREATE_QUEUE	Default Targeting	obdx_cluster
3.	GCIF_WORKFLOW_UPDATE_QCF	Connection Factory	GCIF_WORKFLOW_UPDATE_QCF	Default Targeting	obdx_cluster
4.	GCIF_WORKFLOW_UPDATE_QUEUE	Uniform Distributed Queue	GCIF_WORKFLOW_UPDATE_QUEUE	Default Targeting	obdx_cluster

6.7.14 GCIF Onboarding Draft cancellation functionality

The Following Topic and QCF is used in the below two cases :

- 1) Used in case of Cancellation of GCIF by maker.
- 2) Used in case where the GCIF is rejected by one of its approvers.

Sr N o.	Name	Type	JNDI Name	Subdeploy ments	Targest
1.	OnboardingDraftDeleteQCF	Connection Factory	OnboardingDraftDeleteQCF	Default Targeting	obdx_cluster
2.	OnboardingDraftDeleteTopic	Uniform Distributed Queue	OnboardingDraftDeleteTopic	Default Targeting	obdx_cluster

6.7.15 Subdeployment View

Sr. No.	Name	Resources	Subdeployment
1	GcifSD		GcifJmsServer

6.8 jpa-cache Functionality

6.8.1 jpa-cache Functionality

Sr No.	Name	Type	JNDI Name	Subdeployments	Targest
1.	jms/jpa-cache-cf	Connection Factory	jms/jpa-cache-cf	Default Targeting	obdx_cluster
2.	jms/jpa-cache-topic	Uniform Distributed Queue	jms/jpa-cache-topic	Default Targeting	obdx_cluster

6.8.2 Subdeployment View

Sr. No.	Name	Resources	Subdeployment
1	jpa-cache-sd		jpa-cache

6.9 Multiple Transaction Approval Functionality

6.9.1 Multiple Transaction Approval Functionality

Approval of any transactions from the pending-for-approval listing screen

Sr No	Name	Type	JNDI Name	Subdeployments	Targest
1.	MultipleTransactionServiceInvocationQueue	Uniform Distributed Queue	MultipleTransactionServiceInvocationQueue	MultipleTransactionApprovalISD	MultipleTransactionApprovalJMSServer
2.	MultipleTransactionServiceInvocationQCF	ConnectionFactory	MultipleTransactionServiceInvocationQCF	MultipleTransactionApprovalISD	MultipleTransactionApprovalJMSServer
3.	MultipleTransactionServiceInvocationResponseQCF	ConnectionFactory	MultipleTransactionServiceInvocationResponseQCF	MultipleTransactionApprovalISD	MultipleTransactionApprovalJMSServer
4.	MultipleTransactionServiceInvocationResponseQueue	Uniform Distributed Queue	MultipleTransactionServiceInvocationResponseQueue	MultipleTransactionApprovalISD	MultipleTransactionApprovalJMSServer

6.9.2 Subdeployment View

Sr. No.	Name	Resources	Subdeployment
1	MultipleTransactionApprovalSD	MultipleTransactionServiceInvocationResponseQueue, MultipleTransactionServiceInvocationQueue, MultipleTransactionServiceInvocationQCF, MultipleTransactionServiceInvocationResponseQCF	MultipleTransactionApprovalSD

6.10 NotificationServer

6.10.1 NotificationServer functionality

This contains Queues/Topics which are consumed by Demand Deposit, Term Deposit, Loan, Insights, Config modules

1. Queues which listens to Host(UBS) queues and transfers messages to internal topics for various operation. This includes Account Access automapping, sending host alerts to customer, insights updates.

2. Queues which listens to any changes to dayone configuration and update the cache.

Sr No.	Name	Type	JNDI Name	Subdeployments	Targest
1.	NotificationQCF	Connection Factory	NotificationQCF	Default Targeting	obdx_cluster
2.	NotificationTCF	Connection Factory	NotificationTCF	Default Targeting	obdx_cluster
3.	NOTIFICATION_QUEUE	Uniform Distributed Queue	NOTIFICATION_QUEUE	Default Targeting	obdx_cluster
4.	NOTIFICATION_TOPIC	Uniform Distributed Queue	NOTIFICATION_TOPIC	Default Targeting	obdx_cluster

Sr No.	Name	Type	JNDI Name	Subdeployments	Targest
5.	UBSNotificationTCF	Connec tion Factory	UBSNotificationTCF	Default Targeting	obdx_cluste r
6.	UBS_NOTIFICATION_TOPIC	Uniform Distribut ed Topic	UBS_NOTIFICATION_TOPIC	Default Targeting	obdx_cluste r

6.10.2 Subdeployment View

Sr. No.	Name	Resources	Subdeployment
1	NotificationSD		NotificationServer

6.11 OBPMSystemModule

6.11.1 OBPMSystemModule

Sr No.	Name	Type	JNDI Name	Subdeployments	Targest
1.	OBPMForeignServer	Foreign Server	N/A	OBPMSubdeployment	obdx_cluster

6.11.2 Subdeployment View

Sr. No.	Name	Resources	Subdeployment
1	OBPMSubdeployment		obdx_cluster

6.12 Payment Functionality

6.12.1 Payment Functionality

Sr No .	Name	Type	JNDI Name	Subdeployments	Target
1.	DMS_QUEUE_FOREIGN_SERVER	Foreign Server	N/A	PaymentSD	PaymentJMSServer

6.12.2 Subdeployment View

Sr. No.	Name	Resources	Subdeployment
1	PaymentSD		PaymentJMSServer

6.13 Policies Functionality

6.13.1 Policies Functionality

PoliciesTopic is used to update RTM cache asynchronously after creating or updating role so that RTM changes get reflected on the fly without server restart.

Sr No.	Name	Type	JNDI Name	Subdeployments	Targest
1.	POLICIESQCF	Connection Factory	POLICIESQCF	Default Targeting	obdx_cluster
2.	PoliciesTopic	Uniform Distributed Queue	PoliciesTopic	Default Targeting	obdx_cluster

6.13.2 Subdeployment View

Sr. No.	Name	Resources	Subdeployment
1	PoliciesSD		PoliciesJMS

6.14 Reports Functionality

6.14.1 Reports Functionality

This queues are used in Adhoc and schedules reports.

Sr No.	Name	Type	JNDI Name	Subdeployments	Targest
1.	REPORTADHOC	Uniform Distributed Queue	REPORTADHOC	Default Targeting	obdx_cluster
2.	REPORTSCHEDULED	Uniform Distributed Queue	REPORTSCHEDULED	Default Targeting	obdx_cluster

Sr No.	Name	Type	JNDI Name	Subdeployments	Targest
3.	ReportsQCF	Connection Factory	ReportsQCF	Default Targeting	obdx_cluster

6.14.2 Subdeployment View

Sr. No.	Name	Resources	Subdeployment
1	PoliciesSD		PoliciesJMS

6.15 UBSSystemModule functionality

6.15.1 UBSSystemModule functionality

Sr No.	Name	Type	JNDI Name	Subdeployments	Targest
1.	UBSForeignServer	Foreign Server	N/A	UBSSubdeployment	obdx_cluster

6.15.2 Subdeployment View

Sr. No.	Name	Resources	Subdeployment
1	UBSSubdeployment		obdx_cluster

6.16 UserGroupUser Functionality

6.16.1 UserGroupUser Functionality

Sr N o.	Name	Type	JNDI Name	Subdeployments	Targest
1.	UserGroupUser QCF	Connecti on Factory	UserGroupUser QCF	Default Targeting	obdx_cluster
2.	UserGroupUser Topic	Topic	UserGroupUser Topic	UserGroupUse rSD	UserGroupUserJMS Server

6.16.2 Subdeployment View

Sr. No.	Name	Resources	Subdeployment
1	UserGroupUserSD	UserGroupUserTopic	UserGroupUserJMSServer

6.17 Party Movement Report Functionality

6.17.1 Party Movement Report Functionality

Party Movement Report indicates usage/dependencies of the parties to be moved from one GCIF to another GCIF among specified modules.

Sr N o.	Name	Type	JNDI Name	Subdeployments	Targest
1.	PartyMovementReport QCF	Connecti on Factory	PartyMovementReport QCF	Default Targeting	obdx_clus ter
2.	PartyMovementReport Topic	Uniform Distribut ed Topic	PartyMovementReport Topic	Default Targeting	obdx_clus ter

6.17.2 Subdeployment View

Sr. No.	Name	Resources	Subdeployment
1	PartyMovementReportSD		PartyMovementReportJMS