Development of Launch Forms and Others Screens Oracle Banking Trade Finance Release 14.7.0.0.0 [November][2022]



### Contents

1. Prefa	1Ce	
1.1	Audience	3
1.2	Related Documents	3
2. Intro	duction	
2.1	How to use this Guide	3
3. Laun	ich Forms	4
3.1	Screen Development	4
3.2	Generated units	
3.3	Attaching Launch Form to the Main Function Id	6
3.4	Extensible development	8
4. Othe	rs Screens	8
4.1	Screen Development	8
4.2	Generated units	11
4.3	Extensible development	11

## 1. Preface

This document describes the features of a Launch Form and Others Screen in FLEXCUBE and the process of designing these screens using Oracle FLEXCUBE Development Workbench for Universal Banking.

## 1.1 Audience

This document is intended for FLEXCUBE Application developers/users that use Development Workbench to develop various FLEXCUBE components.

Proficiency	Resources
FLEXCUBE Functional Architecture	Training programs from Oracle
	Financial Software Services.
FLEXCUBE Technical Architecture	Training programs from Oracle
	Financial Software Services.
FLEXCUBE Screen Development	04-Development_WorkBench
	_Screen_Development-I.docx
Working knowledge of Web based applications	Self Acquired
Working knowledge of Oracle Database	Oracle Documentations
Working knowledge of PLSQL & SQL Language	Self Acquired
Working knowledge of XML files	Self Acquired

To Use this manual, you need conceptual and working knowledge of the below:

### **1.2** Related Documents

<u>04-Development\_WorkBench\_Screen\_Development-I.docx</u> <u>05-Development\_WorkBench\_Screen\_Development-II.docx</u> <u>14-Development\_of\_Online\_Forms.docx</u> <u>15-Development\_of\_Call\_Form.docx</u>

# 2. Introduction

### 2.1 How to use this Guide

The information in this document includes:

- <u>Chapter 2 , "Introduction"</u>
- <u>Chapter 3 , "Launch Forms"</u>

• <u>Chapter 4 , "Others Screen"</u>

# 3. Launch Forms

Launch Forms are nothing but normal screens; which are called from another function id for view data purpose. Launch Forms are used for querying (viewing) the data only; no other processing can be done on launch forms unlike call forms.

Usually, any screen which is used across multiple screens for view purpose is treated as Launch Forms.

Example: Contract Events Screen

Contract Events screen is used across many contract screens for viewing the events that has got fired for the particular contract. So a single screen can be designed for the same and re used across all contract screens

Launch Forms can be launched independently and query operation can be done on the screen independently

# 3.1 Screen Development

Technically Launch Forms are the same as normal maintenance or transaction screens. There is no difference in development of a launch form from a maintenance or transaction screen.

Launch forms can be designed as of type

i) Maintenance

ii) Transaction

Note that a maintenance launch form can be used if it is invoked from maintenance screens and similarly for transaction launch forms.

Naming Convention:

Launch Form is nothing but a normal function Id. So it has to follow the same naming convention as any other detail screen. Third letter has to be 'D' and it should have 8 characters.

Example: CSDEVENT, CSDACCNT are valid names for a Launch Form screen

Menu details has to be provided for the Launch form screen as it is a an independent screen . Entries has to be present in *smtb\_function\_description* unlike Call Forms

Function Generation Action Load • Function Id <u>CSDEVENT</u> Save XML Path CSDEVENT_F	Function Type Parent  Parent Function BROWSE Parent Xml Data Source Details	
Preferences DataSource  Gamma DataSource  Gamma DataSource  Gamma DataSource  Gamma DataBlocks  Gamma	Data Source CSTBS_CONTRACT Master Yes  Relation Type One To One  Mutil Record No  PK Cols * CONTRACT_REF_NO PK Types * VARCHAR2 Upload Table	Parent Relation Where Clause Default Order By Type Normal Mandatory

Fig 3.1 A Launch Form function Id showing master Data Source Properties

Refer documents on screen development, development of maintenance and transaction screens for designing a Launch Form screens.

#### **Screen Arguments:**

#### Screen Arguments has to be maintained for the main screen of the launch form.

Launch Forms are used only for querying data. Hence ACTION\_CODE has to be passed as a screen argument with argument value as EXECUTEQUERY and the Primary Key values for querying in launch Form screen should be passed as the other parameters

Action Load		Function Type Parent	*		Function Category			
Function Id CSDEVENT		Parent Function			Header Template			
Save XML Path CSDEVENT_F	BROWSE	Parent Xml			Footer Template	None -		
h	Screen Details						<u> </u>	1 📮
Preferences	Screen Name	CVS_EVENTS		Main Screen				
DataSource		LBL_MAIN	×E	Visible				
ListOfValues DataBlocks	Screen Size	Large	*					
Screens	Exit Button Type	Default Cancel	•					
CVS_EVENTS FieldSets								
Actions							+	-
CallForms LaunchForms	Argument	Name Source Block	Source Field	Argument Value	Target Block	Target Field	Active	*
Summary	CONTREF		-		BLK_EVENT -	REFNO +	Yes 👻	
	ACTION_CODE			EXECUTEQUERY	7	-	Yes -	
	L							-

Fig 3.2 Defining Screen arguments for Launch Form Main Screen

Summary screens if required can be designed for the launch form screen

### 3.2 Generated units

All the units for a normal maintenance or transaction screen will be generated for a Launch Form screen as well.

Note the following while deploying units for Launch Forms

 Entry has to made manually in CSTB\_CALL\_FORM\_NODES for the launch form. Script won't be generated by the Tool while designing the Launch Form. Hence it has to inserted manually providing the screen arguments as maintained for Launch Form main screen

Screen arguments has to be inserted in SCREEN\_ARGS column of CSTB\_CALL\_FORM\_NODES separated by tilde (~)

## 3.3 Attaching Launch Form to the Main Function Id

Launch Forms has to be attached to the main function Id in Launch Form Node

Function Generation		_ >
		🔚 🗷 🗏 🐬 🇐 🔿
Action Load  Function Id STDCIF Save XML Path STDCIF_RAD.	Function Type Parent  Parent Function ROWSE Parent Xml	Function Category Maintenance  Header Template None  Footer Template Maint Audit
Search	Launch Form Details	ن ا
Preferences CataSource ListOValues Control Control FieldSets CallForms LaunchForms Summary		Screen Arguments
		~

Fig 3.3 Attaching Launch forms to a Function Id

Screen Arguments has to be passed from the main function Id to the Launch Form screen

Action Load *		Function Type Parent	-		Function Category Ma	Intenance 👻	
Function Id STECIE	p	arent Function			Header Templale No	ne *	
Save XML Pain STDCIF_RAD.		Parent Xml			FoolerTemplate Ma	Ini Audil 👻	
	Launch Form Details						
eferances							
ilaSource itOfValues						Screen Arguments	
laBlocks			Free address of F			Active	
reens		_	Function IE				
IdSets	CSDEVENT					Yes *	
tions IliForms	MSDAMLMSIG					Yes 💌	
unchForms	CSDHGVW					Yes *	
mmary	CSDFTDUP					Yes *	
				Populate Re	eset		
	Argument Name		Source Field	Argument Value	_1		
	KYC_REF_NO	BLK_CUSTCORP -	KYCREFNO -				
	ACTION_CODE	-	•	EXECUTEQUERY			
				EXECCIEGOEICI			

Fig 3.4 Passing Screen Arguments to Launch Form

Launch forms can be launched by clicking on button placed in the main screen.

Button events have to be maintained such that Launch Form will be launched on clicking it.

Refer Launch Form section on 04-Development\_WorkBench \_Screen\_Development-I.docx for detailed explanation

## 3.4 Extensible development

Developer can add his code in hook packages and release specific JavaScript file. This is similar to any other Maintenance or Transaction screen.

Any enhancements or change in query logic for the screen can be code in **fn\_post\_query** of the Hook package of the particular release

# 4. Others Screens

If the developer does not want to use the business logic provided by the ODT generated code, he can create the function Id with function type as OTHERS.

In the generated package, code will handle only parsing the Ts list to composite PL/SQL type and vice versa. No other processing logic would be provided by the code. Developer has to write the whole business logic in hook packages.

This can be useful when developer wishes to reduce unnecessary code in main package. *For example: Batch function Ids* 

Function Id's for processing a batch can designed as an OTHERS screen. No conventional actions (NEW, SAVE, MODIFY etc) is required for a batch processing screen; only batch processing will need to be done. This can be handled better by designing the screen as OTHERS and write the batch processing logic in the Hook packages

## 4.1 Screen Development

Screen development for an Others screen is similar to a normal maintenance function id

#### Naming Convention:

Others screen should adhere to the same naming convention as a normal maintenance function id. Name of the function id should be of 8 characters and third letter should be 'D'

#### **Function Type**:


Function Type has to be selected as OTHERS

Function Generation				
				📓 🗶 🗏 🐼 🤤 ሩ
Action Load -	Function Type	Parent 👻	Function Categor	y Maintenance 🔻
Function Id STDCSNET	Parent Function		Header Templat	e None 🔻
Save XML Path STDCSNET_F	BROWSE Parent Xml		Footer Templat	e None 👻
Search	Block Field Properties			- R Q 9
Preferences  ListOfValues  DataBlocks  DLLK_NET_BATCH  EROUPCO  DESCR  TXNCD  BRANCH  COUNT  BTN_BATCH  FieldSets  Actions  Califorms  LaunchForms  Summary	Field Name       GROUPCD         Field Label       LBL_GRPCD         DataSource       STWW_NET_GROUP_E         Column Name       GROUPCD         Data Type       Varchar2         Display Type       Text         Item Type       DataSose Item         Parent Field       Parent Field         CV Name       LOV_GROUPCD         Off Line LOV Name       FST_GROUP         Custom Attributes       Events	BATC Maxin Mini Maximur TextArc TextArc	XSD Tag GRPCD	Read Only Calender Text Popup Edit Required Uppercase Only LOV Validation Required Input by LOV Only Not Required In Xsd Report Parameter
	Attribute Name	Attribute Value	Active	Position



Normally user defined actions would be used in an OTHERS screen .These actions are invoked on click of the buttons placed in the screen.

Action Load - Function Id STDCSNET		Function Type Parent Parent Function			nction Category Mainter	nance -
Save XML Path STDCSNET_F	BROWSE	Parent Xml			Footer Template None	-
ch	Block Field Prope	rties				- 🛛 🗖 🕻
Preferences DataSource ListOVAlues DataBlocks DataBlocks DataBlocks DBLK_NET_BATCH GROUPCD DESCR TXINCD BRANCH COUNT BTN_BATCH Screens FieldSets Actions CallForms LaunchForms Summary	Field Name Field Label DataSource Column Name Data Type Display Type Item Type Parent Field Related Block Related Block Related Field LOV Name Off Line LOV Name Fields et Name	Button V Control V V FST_BTN	XSD Tag XSD Annotation Field Size * Maximum Length Minimum Value Maximum Decimals TextArea Rows TextArea Columns Default Value Preview Value Mask Id	PROCESS		Required      Visible      Read Only      Calender Text      Popup Edit Require      Uppercase Only      LOV Validation     Required      Input by LOV Only      Not Required In Xs      Report Parameter
	C Event Nam	e Function Name		tton Screen	CallForm Name	Screen Name



Netting Group Batch Processing						
🖹 New 🦻 Enter Query						
Group Code Description		Branch				
Number of Un-netted Entries	Process					
				Exit		

Fig 5.3 Preview of the batch processing screen

# 4.2 Generated units

All the units for a normal maintenance or transaction screen will be generated for a Launch Form screen as well.

## 4.3 Extensible development

Developer can add his code in hook packages and release specific JavaScript file. This is similar to any other Maintenance or Transaction screen.

Coding in JavaScript:

Custom action codes defined by the developer are defined in the JavaScript file. It is usually defined on click of a button .The action code is defined and the request xml is built and passed to the server.

These codes are written in release specific JavaScript file Example: Figure below shows a snippet from STDCSNET\_CLUSTER.js Notice the *fn batch* () which is invoked on clicking of the *Process* button.

```
function fn_batch()
{
    appendData();
    gAction = 'NET_BATCH';
    fcjRequestDOM = buildUBSXml();
    fcjResponseDOM = fnPost(fcjRequestDOM, servletURL, functionId);
    var msgStatus =getNodeText( selectSingleNode(fcjResponseDOM, "FCUBS_RES_ENV/FCUBS_HEADER/MSGSTAT"));
    if (!fnProcessResponse()) {
        return true;
    }
}
```

Fig 5.4 Code Snippet from STDCSNET\_CLUSTER.js

Here action code is set as 'NET\_BATCH' and request xml built and passed to the server and response processed based on response xml

#### Coding in Packages:

Developer can write the business logic in  $fn_main$  which will be present in the release specific hook package

Skip Handlers can be used to skip the code in any previous release stages if required.

Processing logic has to be written for the user defined action codes in the release specific hook package




Fig 5.5 Code Snippet from stpks\_stdcsnet\_cluster.js

The above figure shows the handling for the user defined action code 'NET\_BATCH' in *fn\_main* of stpks\_stdcsnet\_cluster.sql



Development of Launch Forms and Others Screens

[November] [2022] Version 14.7.0.0.0

Oracle Financial Services Software Limited Oracle Park Off Western Express Highway Goregaon (East) Mumbai, Maharashtra 400 063 India

Worldwide Inquiries: Phone: +91 22 6718 3000 Fax:+91 22 6718 3001 www.oracle.com/financialservices/

Copyright © 2022, Oracle and/or its affiliates. All rights reserved.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate failsafe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.