

Oracle
Primavera Unifier
Data Reference Guide

Version 23
December 2023

Oracle Primavera Unifier Data Reference Guide
Copyright © 1998, 2023, Oracle and/or its affiliates.
Primary Author: Oracle Corporation

Contents

Introduction	23
Unifier Data Definitions (DDs)	25
Asset Manager DDs.....	25
Shell Picker.....	26
SYS Business Process Datasource	26
SYS Date Logical Datasource	26
SYS Depreciation Name.....	27
SYS Numeric Logical Datasource.....	27
SYS Overbooking Options	28
SYS Project Cost Datasource.....	28
SYS Yes No	29
Configurable Manager DDs.....	29
CM[1...25] Picker	29
Data Picker	29
Shell Picker.....	31
SYS BP Currency Amount.....	31
SYS BP Decimal Amount.....	31
SYS BP Integer Amount.....	32
SYS Overbooking Options	32
SYS Yes No	32
User Data Picker.....	33
Cost Manager DDs	33
Cost Attribute Forms DDs	34
Cost Attribute.....	34
Cost Item Type.....	34
Fund Attribute Forms DDs	34
Funding Category.....	34
Cost Business Processes DDs.....	35
Account Code Picker	35
Asset Picker	35
Cost Code Separator	35
Funding Category.....	36
SYS Before After	36
Document Manager DDs.....	36
SYS Auto Sequence.....	36
SYS Category	37
SYS Overbooking Options	37
SYS Yes No	38
Lease Business Process DDs	38

SYS Pay Creation Day of Month	38
SYS Pay Day of Month.....	38
SYS Payment Frequency	39
SYS Payment Type.....	39
SYS Proration Method.....	39
Planning Manager DDs	40
Planning Item Creator	40
Planning Item Picker	40
Shell Picker.....	41
SYS Date Datasource.....	41
SYS Date Logical Datasource	41
SYS Numeric Datasource.....	42
SYS Numeric Logical Datasource	42
Resource Manager DDs	43
Activity Picker.....	43
Resource Picker	43
Role Picker.....	43
SYS Resc Calendar NW Day Type.....	44
SYS Resc Work Type	44
SYS Resource Interest	44
SYS Resource Proficiency.....	44
SYS Resource Skill	45
Week Picker	45
SYSRoleType.....	45
Schedule Manager DDs	46
Activity Constraint.....	46
Activity Picker.....	47
Filtered Group.....	47
Resource Type	47
Role Data Picker.....	47
Role Picker.....	49
SYS Activity Calendar	49
SYS Activity Codes.....	49
SYS Activity Status.....	49
SYS Date Logical Datasource	50
SYS Numeric Logical Datasource.....	50
SYS Project Cost Datasource.....	51
Shell Manager DDs.....	51
Auto-update Status Setup Picker	51
Date Picker	52
Project Phase.....	52
SYS Shell Number	52
Shell Picker.....	53

SYS Shell Name.....	53
User Data Picker.....	53
SYSP6ScheduleType	54
Space Manager DDs	54
Data Picker	55
Level Picker	56
Space Picker.....	56
SYS Overbooking Options	56
SYS Space Name.....	57
SYS Space Unit of Measure.....	57
SYS Yes No	58
User Data Picker.....	58
Global DDs	59
BP Creator.....	59
BP Picker.....	59
Company Picker.....	60
Currency Amount.....	60
Date Only	61
Decimal Amount.....	61
Description Text.....	62
Discipline	62
Group Name Picker.....	62
Hyperlink Picker.....	62
Image Picker.....	63
Integer Amount.....	63
Multi Select.....	64
Line Item Data Picker.....	64
Project Picker.....	64
Project Site	65
Project Type	65
Record Number Data	65
Shell Picker.....	65
Short Description Text.....	66
Space Picker.....	66
SYS Auto Sequence.....	66
SYS Check Box.....	67
SYS Description Text 500	67
SYS Description Text 2000.....	68
SYS Line Item Status.....	68
SYS Long Description Text.....	68
SYS Long Name	68
SYS Medium Name	69
SYS Numeric Query Based.....	69

SYS Short Description Text 32	70
SYS Short Description Text 36	70
SYS Short Description Text 40	70
SYS Short Description Text 50	70
SYS Short Description Text 120	71
SYS Short Description Text 250	71
SYS Short Description Text 255	71
SYS Short Name	71
SYS Yes No	72
Unit of Measure	72
User Data Picker.....	72
User Picker.....	73
Other DDs (in Alphabetical Order: A-G)	73
Bid Picker.....	73
BP Line Item Creator.....	74
BP Line Item Picker.....	74
Date Only Picker	74
Other DDs (in Alphabetical Order: H-N).....	75
Other DDs (in Alphabetical Order: O-T).....	75
Record Status Pulldown.....	75
Seasonal Dates Picker.....	75
SYS Barcode	75
SYS Cost Line Item Type	76
SYS Duration Type.....	76
SYS Expense Category	76
SYS Family Identifier	77
SYS Frequency Units.....	77
SYS Meter Type	77
SYS Reading Type	78
SYS Rich Text.....	78
SYS Schedule Type.....	78
SYS User Type.....	79
Other DDs (in Alphabetical Order: U-Z).....	79
P6 DDs	79
P6 Activity Picker	79
SYS P6 Activity Constraint	79
SYS P6 Indicator.....	80
SYS P6 Rate Source.....	81
SYS P6 Resource Status.....	81
SYS P6 Role Status	81
Earned Value Manager DDs	82
SYS Rate Breakdown Type.....	82
SYS Cost Breakdown Type.....	82

Data Elements (DEs)	83
Activity Sheet Manager	84
uuu_activity_constraint_type	84
uuu_activity_early_finish	84
uuu_activity_early_start	85
uuu_activity_late_start	85
uuu_activity_late_finish	85
uuu_activity_successor	85
Asset Manager DEs	85
uuu_asset_acquisition_cost	86
uuu_asset_acquisition_date	86
uuu_asset_calc_as_of_date	86
uuu_asset_code	86
uuu_asset_cum_depreciation	87
uuu_asset_curr_period_dep	87
uuu_asset_depreciation_prd	87
uuu_asset_name	88
uuu_asset_navigation_code	88
uuu_asset_net_book_value	88
uuu_asset_salvage_value	89
uuu_rsv_reservable	89
uuu_rsv_overbook	89
Configurable Shells DEs	90
uuu_administrator	90
uuu_location	90
Cost Manager DEs	91
Account Code Attribute Forms DEs	91
uuu_company_account_code	91
uuu_company_account_name	91
Cost Attribute Forms DEs	91
uuu_cost_cost_type	92
uuu_cost_costattribute	92
uuu_cost_description	92
uuu_cost_external_refid	92
uuu_cost_exposed_to_p6	93
uuu_cost_imported_from_p6	93
uuu_cost_item	93
uuu_cost_owner	94
uuu_cost_status	94
Fund Attribute Forms DEs	94
row_id	94
uuu_fund_code	95
uuu_fund_description	95
uuu_fund_fundcategory	95

uuu_fund_fundname	95
uuu_fund_long_desc.....	96
Cost Business Processes DEs	96
bitemID.....	96
currencyid	97
currencyrate.....	97
ref_bpo.....	98
ref_bpo_lineitem	99
refid	99
row_id.....	100
scheduled_value	100
usd_currencyrate.....	101
uuu_asset_picker.....	101
uuu_base_rate_override.....	102
uuu_before_after.....	102
uuu_calendar_item_name.....	103
uuu_cancellation_notes.....	103
uuu_cancelled	103
uuu_commit_breakdown	103
uuu_commit_short_desc	103
uuu_commit_remaining_balance.....	104
uuu_company_acc_codepicker	104
uuu_cost_code	104
uuu_effective_date	105
uuu_from_date	105
uuu_fund_description	106
uuu_fund_fundcategory.....	106
uuu_fund_fundname	106
uuu_fund_long_desc.....	106
uuu_project_rate_override	106
uuu_recurrence	107
uuu_rsv_trigger_date	107
uuu_rsv_trigger_days.....	107
uuu_rsv_trigger_hrs	108
uuu_rsv_trigger_mins	108
uuu_sovlinum	108
uuu_scheduled_value.....	109
uuu_to_date	110
uuu_unit_cost_contract.....	110
uuu_unit_price.....	110
wpid	110
Configurable Manager DEs.....	111
uuu_cm[1...25]_code.....	111
uuu_cm[1...25]_name	111
uuu_cm[1...25]_status	111
uuu_code_navigation_code	112

uuu_cm[1...25]_picker	112
uuu_rsv_overbook.....	112
uuu_rsv_reservable.....	113
Document Manager DEs.....	113
uuu_dm_create_by	113
uuu_dm_create_date.....	114
uuu_dm_description	114
uuu_dm_node_name.....	114
uuu_dm_node_path.....	115
uuu_dm_percent_complete	115
uuu_doc_attribute_url	115
uuu_file_create_by.....	116
uuu_file_create_date.....	116
uuu_file_issue_date.....	116
uuu_file_revision_no.....	116
uuu_file_size.....	117
uuu_file_title.....	117
uuu_file_version.....	117
uuu_issue_date.....	118
uuu_line_item_status	118
uuu_li_last_update_date.....	118
uuu_name.....	119
uuu_rsv_overbook.....	119
uuu_rsv_reservable.....	119
uuu_revision_no.....	120
uuu_title.....	120
Generic Cost Manager DEs.....	120
uuu_cm0_code.....	120
uuu_cm0_name	121
uuu_cm0_status	121
uuu_effective_date	121
ref_bpo.....	122
ref_bpo_lineitem	122
scheduled_value	123
uuu_sovlinum	123
Global DEs	124
amount.....	124
description	125
due_date.....	125
otherCompanyID.....	125
record_no.....	126
short_desc	126
status	126

title	127
uuu_bp_record_url.....	127
uuu_creation_date.....	128
uuu_dm_publish_path.....	128
uuu_dm_record_info_path	129
uuu_default_shell_picker	129
uuu_line_item_status	130
uuu_phy_space_picker.....	130
uuu_project_phase	130
uuu_project_picker	131
uuu_quantity.....	131
uuu_record_last_update_date	131
uuu_shell_status.....	132
uuu_sovref_num	132
Lease Business Processes DEs.....	133
uuu_allocation_amount.....	133
uuu_lse_allocation_name	133
uuu_lse_first_pay_due_date	133
uuu_lse_pay_creat_lead_time	134
uuu_lse_add_pay_amt	135
uuu_lse_commencement_date	135
uuu_lse_end_date	135
uuu_lse_esc_freq_len.....	136
uuu_lse_esc_freq_type.....	136
uuu_lse_esc_method.....	137
uuu_lse_esc_value.....	138
uuu_lse_frequency.....	138
uuu_lse_pay_amount	139
uuu_lse_pay_creation_date	139
uuu_lse_pay_due_date.....	139
uuu_lse_pay_due_day	140
uuu_lse_pay_latest_due_date	140
uuu_lse_pay_latest_due_day.....	140
uuu_lse_pay_type	141
uuu_lse_proration_method	141
uuu_lse_sl_adjustment	142
uuu_lse_sl_rent.....	142
uuu_lse_start_date	143
uuu_lse_straight_line.....	143
uuu_lse_term_modifier.....	143
uuu_lse_termination_date	144
Index Rate Business Process DEs.....	144
uuu_index_rate	144

uuu_index_code	144
Planning Manager DEs.....	145
uuu_last_update_date.....	145
uuu_planning_item	145
Request for Bid (RFB) DEs	145
uuu_bid_count.....	145
uuu_bidders_count.....	145
uuu_contact_company	146
uuu_contact_first_name.....	146
uuu_contact_lang.....	146
uuu_contact_last_name	147
uuu_rfb_due_date.....	147
uuu_rfb_initiate_date	148
uuu_rfb_winning_bid	148
uuu_user_id.....	149
Resource Manager DEs	149
uuu_activity_picker	149
uuu_from_date.....	149
uuu_resc_capacity	150
uuu_resc_code.....	150
uuu_resc_sun_reg_hours uuu_resc_sat_reg_hours	150
uuu_resc_interest	150
uuu_resc_sun_ot_hours uuu_resc_sat_ot_hours.....	151
uuu_resc_mon_capacity uuu_resc_sun_capacity	151
uuu_resc_name.....	151
uuu_resc_non_project_time.....	152
uuu_resc_nwd_type	152
uuu_resc_ot_rate	152
uuu_resc_picker.....	152
uuu_resc_proficiency	153
uuu_resc_skill.....	153
uuu_resc_status.....	154
uuu_resc_tot_reg_hours.....	154
uuu_resc_tot_amount.....	154
uuu_role_amt	154
uuu_role_name	155
uuu_role_imported_from_p6	155
uuu_role_id.....	155
uuu_role_picker.....	156
uuu_role_status	156
uuu_role_type.....	156
uuu_role_uom	157
uuu_to_date	157

uuu_user_address	158
uuu_user_city	158
uuu_user_country	158
uuu_user_email.....	158
uuu_user_fax.....	159
uuu_user_firstname.....	159
uuu_user_homephone.....	159
uuu_user_lastname	159
uuu_user_mobilephone.....	160
uuu_user_pager	160
uuu_user_state	160
uuu_user_timezone	160
uuu_user_title	161
uuu_user_workphone	161
uuu_user_zip	161
uuu_week_picker	161
Schedule Manager DEs.....	162
uuu_act_cost1.....	162
uuu_act_cost2.....	162
uuu_act_latest_prog_as_of.....	162
uuu_act_pct_complete	162
uuu_act_tot_cost1_per_CBS.....	163
uuu_act_tot_cost2_per_CBS.....	163
uuu_activity_calendar.....	163
uuu_activity_codes	163
uuu_activity_constraint.....	164
uuu_activity_earn_amt	164
uuu_activity_earn_progress	165
uuu_activity_etc_amount	165
uuu_activity_ev_filter	165
uuu_activity_fc_start_1	165
uuu_activity_fc_finish_1.....	166
uuu_activity_fc_duration_1.....	166
uuu_activity_fc_start_2	166
uuu_activity_fc_finish_2.....	166
uuu_activity_fc_duration_2.....	167
uuu_activity_id	167
uuu_activity_level.....	167
uuu_activity_name	167
uuu_activity_per_1.....	168
uuu_activity_predecessors.....	168
uuu_activity_resources.....	168
uuu_activity_status	169

uuu_activity_CBS_codes.....	169
uuu_activity_work_hrs	169
uuu_actual_duration.....	170
uuu_actual_finish_date	170
uuu_actual_start_date.....	170
uuu_auto_update_activity	171
uuu_duration	171
uuu_duration_baseline.....	171
uuu_duration_baseline[1...10].....	172
uuu_duration_type	172
uuu_early_finish	173
uuu_early_start	173
uuu_estimated_duration	173
uuu_estimated_finish_date.....	174
uuu_estimated_start_date	174
uuu_filtered_groups.....	174
uuu_finish	175
uuu_finish_baseline.....	175
uuu_finish_baseline[1...10]	175
uuu_fixed_cost	176
uuu_flag_complete	176
uuu_flag_milestone	176
uuu_float.....	177
uuu_labor_cost.....	177
uuu_late_finish.....	177
uuu_late_start	177
uuu_linked_bp_name	178
uuu_linked_record_status.....	178
uuu_non_labor_cost	178
uuu_outline_code.....	179
uuu_resc_assign_amt.....	179
uuu_resc_assign_amt_bl.....	179
uuu_resc_assign_amt_bl[1...10]	179
uuu_resc_assign_compl_per.....	180
uuu_resc_assign_earn_amt	180
uuu_resc_assign_earn_prog.....	180
uuu_resc_assign_etc_amt.....	180
uuu_resc_assign_etc_qty	181
uuu_resc_assign_per_1	181
uuu_resc_assign_prog_qty.....	181
uuu_resc_assign_qty	181
uuu_resc_assign_qty_bl	182
uuu_resc_assign_rate.....	182

uuu_resc_assign_rate_bl	182
uuu_resc_assign_untper	183
uuu_resc_assign_untper_bl	183
uuu_resc_assign_uom.....	183
uuu_resc_assign_uom_bl.....	183
uuu_resc_code	184
uuu_resc_name.....	184
uuu_resc_picker.....	184
uuu_resc_sun_capacity uuu_resc_sat_capacity.....	185
uuu_resc_type	185
uuu_role_name	186
uuu_start	186
uuu_start_baseline	186
uuu_start_baseline[1...10].....	187
uuu_tag.....	187
uuu_total_cost.....	188
uuu_total_cost_baseline[1...10]	188
Shell Manager DEs.....	188
uuu_administrator.....	188
uuu_au_setup_picker	189
uuu_int_schedule_type.....	189
uuu_location.....	189
uuu_proj_template_picker	190
uuu_proj_address_1.....	190
uuu_proj_address_2.....	190
uuu_proj_address_3.....	191
uuu_proj_city	191
uuu_proj_country	191
uuu_proj_fax.....	192
uuu_proj_phone	192
uuu_proj_state	192
uuu_proj_zip.....	193
uuu_project_creator.....	193
uuu_project_start_date	193
uuu_record_last_update_date.....	194
uuu_shell_creator	194
uuu_shell_image	195
uuu_shell_location	195
uuu_shell_status.....	195
uuu_shell_template_picker.....	196
Space Manager DEs.....	196
uuu_record_last_update_date	196
uuu_rsv_overbook.....	196

uuu_rsv_reservable.....	197
uuu_sp_area.....	197
uuu_sp_level_name.....	198
uuu_sp_level_picker.....	198
uuu_sp_uom.....	198
User Administration DEs	198
uuu_user_company.....	198
uuu_user_dateformat.....	199
uuu_user_email.....	199
uuu_user_fax.....	200
uuu_user_firstname.....	200
uuu_user_homephone.....	200
uuu_user_lastname	200
uuu_user_loginname	201
uuu_user_mobilephone	201
uuu_user_name	201
uuu_user_pager	201
uuu_user_password.....	202
uuu_user_proxy	202
uuu_user_status	202
uuu_user_timezone_pref.....	202
uuu_user_title	203
uuu_user_workphone	203
Bluebeam DEs	204
uuu_review_session_name	204
uuu_review_session_id.....	204
uuu_review_file_name.....	205
uuu_review_revision_no	206
uuu_review_pub_no.....	206
Other DEs (in Alphabetical Order: A-G).....	207
uuu_address_code.....	207
uuu_attachment_count	208
uuu_cmwbs_picker	209
uuu_cost_li_type	209
uuu_costed_amt	210
uuu_costed_qty	210
uuu_not_costed_amt.....	211
uuu_not_costed_qty.....	211
Other DEs (in Alphabetical Order: H-N)	212
uuu_integrated_with.....	212
uuu_int_internal_proj_id.....	213
uuu_int_p6_project_id.....	213
uuu_latitude	214

uuu_li_consolidated.....	214
uuu_longitude.....	215
uuu_lse_accrual_amount.....	215
uuu_lse_annual_discnt_rate.....	215
uuu_lse_inc_in_npv.....	216
uuu_lse_npv_amount.....	216
uuu_meter_avg_units.....	217
uuu_meter_base_rdng.....	217
uuu_meter_cumu_rdng.....	217
uuu_meter_init_rdng.....	218
uuu_meter_latest_rdng.....	218
uuu_meter_reading.....	218
uuu_meter_rdng_type.....	218
uuu_meter_rollover_pt.....	218
uuu_navigation_code.....	219
uuu_no_upd.....	219
Other DEs (in Alphabetical Order: O-T).....	219
uuu_planning_item_picker.....	220
uuu_proj_currency.....	220
uuu_rec_asset_bp.....	221
uuu_rec_ast_meter_li.....	221
uuu_rec_ctr_adjustment.....	221
uuu_rec_family_identifier.....	221
uuu_rec_related_family_id.....	222
uuu_rec_frequency.....	223
uuu_rec_frequency_unit.....	223
uuu_rec_gauge_gt.....	223
uuu_rec_gauge_lt.....	223
uuu_rec_lead_time.....	224
uuu_rec_meter_type.....	224
uuu_rec_next_due_date.....	224
uuu_rec_next_trgr_date.....	225
uuu_rec_prev_trgr_date.....	225
uuu_rec_prev_trgr_rdng.....	225
uuu_rec_schedule_type.....	226
uuu_rec_sequence_ctr.....	226
uuu_rec_li_start_date.....	226
uuu_rec_ses_desc.....	227
uuu_rec_ses_dates_pkr.....	227
uuu_rec_tolerance.....	227
uuu_rec_wo_bpc.....	228
uuu_rich_text.....	228
uuu_spa_amt_tp.....	229

uuu_spa_mat_stored	229
uuu_spa_other_tp	230
uuu_spa_per_comp	231
uuu_spa_prev_amt	232
uuu_spa_qty_tp	232
Other DEs (in Alphabetical Order: U-Z)	233
uuu_user_proxy_config	233
uuu_user_type	233
P6 DEs	233
uuu_P6ActivityCalendar	234
uuu_P6ActivityId	234
uuu_P6ActivityName	234
uuu_P6ActivityStatus	234
uuu_P6ActivityType	235
uuu_P6ActualCost	235
uuu_P6ActualDuration	235
uuu_P6ActualFinish	235
uuu_P6ActualStart	236
uuu_P6ActualTotalCost	236
uuu_P6ActualTotalUnits	236
uuu_P6ActualUnits	236
uuu_P6AtCompletionCost	237
uuu_P6AtCompletionDuration	237
uuu_P6AtCompletionTotalCost	237
uuu_P6AtCompletionTotalUnits	238
uuu_P6AtCompletionUnits	238
uuu_P6BAC	238
uuu_P6CBSCode	238
uuu_P6CBSName	239
uuu_P6CBSPath	239
uuu_P6ControlAccounts	239
uuu_P6CostVariance	240
uuu_P6CPIIndex	240
uuu_P6CSIndex	240
uuu_P6Duration	241
uuu_P6EAC	241
uuu_P6EACCost	241
uuu_P6ETC	241
uuu_P6ETCUserValue	242
uuu_P6EV	242
uuu_P6EVCost	242
uuu_P6Finish	242
uuu_P6PercentComplete	243

uuu_P6PerfPercComplete	243
uuu_P6PlannedCost	243
uuu_P6PlannedDuration	243
uuu_P6PlannedStart.....	244
uuu_P6PlannedFinish.....	244
uuu_P6PlannedTotalCost	244
uuu_P6PlannedTotalUnits	244
uuu_P6PlannedUnits	245
uuu_P6PricePerUnit.....	245
uuu_P6PrimaryConstraint.....	245
uuu_P6PV	246
uuu_P6PVCost.....	246
uuu_P6RateCurrency	246
uuu_P6RateEffectiveFrom.....	246
uuu_P6RemainingCost	247
uuu_P6RemainingDuration	247
uuu_P6RemainingEarlyFinish	247
uuu_P6RemainingEarlyStart	248
uuu_P6RemainingTotalCost.....	248
uuu_P6RemainingTotalUnits.....	248
uuu_P6RemainingUnits	248
uuu_P6ResourceName.....	249
uuu_P6ResourceStatus	249
uuu_P6RoleID.....	249
uuu_P6RoleName	250
uuu_P6RoleStatus	250
uuu_P6ScheduleVariance	250
uuu_P6SecondaryConstraint.....	250
uuu_P6SPIndex	251
uuu_P6Start	251
uuu_P6TCPIIndex	251
uuu_P6TotalActualUnits	252
uuu_P6TotalAtCompletionUnits	252
uuu_P6TotalPlannedUnits.....	252
uuu_P6TotalRemainingUnits.....	252
uuu_P6VAC.....	253
uuu_P6WBSCategory	253
uuu_P6WorkPackage.....	253
uuu_P6WBSPath	254
Earned Value Manager DEs	254
Organization Breakdown Structure	254
uuu_obs_recordno	254
uuu_obs_fullnameTopic.....	254

uuu_obs_title.....	255
uuu_obs_department.....	255
uuu_obs_status.....	255
uuu_obs_assignee	255
Work Breakdown Structure (WBS)	256
uuu_P6ETCComputeType	256
uuu_P6WBSCode	256
uuu_P6WBSName.....	256
uuu_P6WBSType	256
Data Types for User Defined Reports (UDRs)	259
Accounts Sheet.....	262
Active Task Information	263
Asset Summary Sheet (Company-level)	266
CashFlow (Project/Shell).....	266
CashFlow: Summary Snapshot (Project/Shell).....	268
Commitment Funding.....	269
Commitment Summary	271
Company CashFlow	273
Company Cost.....	275
Company Funding.....	276
Company User Information	276
Cost Sheet (CBS)	277
Cost Transactions (CBS).....	278
Cost (Project/Shell)	279
Cost Transactions MC (CBS).....	280
Document Manager (Project/Shell)	284
Document Manager (Company-level).....	288
Funding	290
Gates.....	292
Groups (Project/Shell).....	295
Partner User Information	295
Planning Manager Items (Project/Shell).....	296
Planning Manager Sheets (Project/Shell)	297
Resource Manager: All Actuals (Company-level)	297
Resource Manager: Allocated Roles	298
Resource Manager: Booked Resources.....	300
Resource Manager: Project Actuals	302
Resource Manager: Resources	303
Resource Manager: Roles.....	304
Resource Manager: Sheets	305
Schedule (Project/Shell)	306
Schedule of Value (SOV)	308
Shell Information	310

Users (Project/Shell)	312
Workflow Information	313
Codes for Importing User Records	317
Currency	317
Currencies and codes (A-G)	317
Currencies and codes (H-N)	319
Currencies and codes (O-T)	321
Currencies and codes (U-Z)	323
Time Zone	323
Server Time Zone	328
Date Format	346
User Type	348
Company Address	348
Status	348
Check Box	349
Pickers	351
Account Code Picker	353
Activity Picker	353
Allocation Template Picker	353
Asset Picker	354
Auto-update Status Setup Picker	354
Bid Picker	354
BP Line Item Picker	354
BP Picker	355
BP Line Item Data Picker	356
CBS Picker	356
CBS Code Picker	356
CM0 Picker (Generic Cost Manager)	357
CMx (Code based) Picker	357
CMx (Code and Records-based) Picker	357
Commit Line Item Picker	358
Company Picker	358
Configurable Manager [Name] Picker	359
Cost Attribute Picker	359
Cost Code Picker	359
Currency Picker	359
Data Picker	360
Date Only Picker	360
Date Picker	360
Date Only Picker	366
Fund Picker	367
Generic Cost Code Picker	367

Group Name Picker	368
Hyperlink Picker.....	368
Image Picker	368
Level Picker.....	368
Location Picker	369
P6 Activity Picker	369
Planning Item Picker/Planning Line Item Picker	369
Planning Period Picker	369
Project Picker.....	370
Project Template Picker	370
Resource Picker.....	370
Role Picker.....	371
Role Data Picker	371
Seasonal Dates Picker	371
Shell Picker	372
Shell Template Picker	372
Shell Data Picker	372
Single User Picker.....	373
SOV Picker.....	373
Space Picker	373
SYS Date Picker	373
User Picker.....	374
User Data Picker.....	375
WBS Code Picker	375
WBS Picker.....	375
Week Picker	375
Work Package Picker	375
Glossary.....	377
In Alphabetical Order A-G.....	377
In Alphabetical Order H-N	389
In Alphabetical Order O-T	393
In Alphabetical Order U-Z	402

Introduction

Within our documentation, some content might be specific for cloud deployments while other content is relevant for on-premises deployments. Any content that applies to only one of these deployments is labeled accordingly.

This guide provides details about data definitions (including for P6 integration and for the Earned Value Manager), data elements, UDR data types, codes for importing user records, pickers or selection lists, and Unifier dictionary.

All users should read this guide.

Unifier Data Definitions (DDs)

This section contains the predefined Data Definitions (DDs) that are the "building blocks" on which you can create the data elements that become the fields on the forms you design.

To see the DDs, go to **Unifier > Company Workspace > Admin mode > Data Structure Setup > Data Definitions**.

The data definitions are divided into topics for each manager, as well as a topic of global data definitions that can be used for almost any form.

At the end of this section an alphabetical listing of all the data definitions are provided.

Each topic includes descriptions of the data definitions and where you can use the data elements built on them.

In addition to the data definitions described here, you can create other data definitions as you need them. For information on creating new data definitions (DDs), refer to the *Unifier uDesigner User Guide*.

Note: The following information includes the forms where elements built on these data definitions can be used. Using these definitions on forms not listed here can result in unexpected behavior.

In This Section

Asset Manager DDs.....	25
Configurable Manager DDs	29
Cost Manager DDs	33
Document Manager DDs	36
Lease Business Process DDs.....	38
Planning Manager DDs.....	40
Resource Manager DDs	43
Schedule Manager DDs.....	46
Shell Manager DDs.....	51
Space Manager DDs	54
Global DDs	59
Other DDs (in Alphabetical Order: A-G)	73
Other DDs (in Alphabetical Order: H-N)	75
Other DDs (in Alphabetical Order: O-T)	75
Other DDs (in Alphabetical Order: U-Z)	79
P6 DDs	79
Earned Value Manager DDs	82

Asset Manager DDs

Use the following data definitions for creating asset classes for the **Asset Manager**.

Shell Picker

Type: Integer

Size: 0

Input Type (Input Method): Picker

Use on:

- Upper or detail form of any business process.
- Asset class attribute form.
- Planning item attribute form.
- Configurable manager attribute form
- Detail form of any asset, planning item, or configurable manager.
- Detail form of Timesheet BP.

This DD is available for the same forms on mobile device.

Description: Picker for selecting a shell in Unifier.

You can create any number of data elements (fields) using this definition.

SYS Business Process Datasource

Type: Float

Size: 0

Input Type (Input Method): Currency

Use on: Asset class forms

Description: Use this data definition to create data elements to gather numeric values from business processes for projects linked to an asset.

Fields using this definition create the columns on asset sheets. (Creates read-only fields.)

SYS Date Logical Datasource

Type: Date

Size: 0

Input Type (Input Method): Picker

Use on:

- Detail form of any business process
- Asset attribute and class forms
- Planning item attribute forms
- Activity attribute forms

This DD is available for the same forms on mobile device.

Description: Use this definition to create fields for use in “date add” type formulas (using integers or decimals) to produce a new date.

You can also use this definition for a manual-entry field where the user chooses the date from a date picker.

Fields using this definition create the columns on:

- ▶ Planning Sheets
- ▶ Asset Sheets
- ▶ Schedule Sheets

Creates read-only fields; not available for auto-population or dynamic data sets.

SYS Depreciation Name

Type: String

Size: 120

Input Type (Input Method): Pull-down Menu (Drop-down list)

Use on: Asset attribute and class forms

Description: Pull-down Menu (Drop-down list) for selecting the kind of depreciation to use for an asset.

The data set for this field will be specified in Unifier.

SYS Numeric Logical Datasource

Type: Float

Size: 0

Input Type (Input Method): Currency

Use on:

- ▶ Asset attribute and class forms
- ▶ Planning item attribute forms
- ▶ Activity attribute forms

Description: Use this definition to create fields for use in numeric formulas and also in “date difference” type numeric formulas to produce the number of days between two dates.

You can also use this definition for a manual-entry field where the user enters decimal values, such as currencies.

Fields using this definition create the columns on:

- ▶ Asset sheets
- ▶ Planning sheets
- ▶ Schedule sheets

Note: This DD creates read-only fields, and it is not available for

auto-population or dynamic data sets.

SYS Overbooking Options

Type: String

Size: 50

Input Type (Input Method): Pull-down Menu (Drop-down list)

Use on:

- ▶ Asset class forms
- ▶ Detail (attribute form) for a configurable manager
- ▶ Detail (attribute form) for a document
- ▶ Detail (attribute form) for a space

Note: The Data Elements (DEs) must be placed in a Shell Business Process, and the Activity Sheet must be located in the same Shell.

Description:

Pull-down Menu (Drop-down list) for selecting overbooking options for reservable assets/objects. The options are:

- ▶ Even if confirmed booking exists
- ▶ Only if tentative booking exists
- ▶ No overbooking

SYS Project Cost Datasource

Type: Float

Size: 0

Input Type (Input Method): Currency

Use on:

- ▶ Asset class detail form
- ▶ Activity Attribute form

Description: Use this data definition to create data elements to gather numeric values from the cost sheet of the project associated with an asset.

Fields using this definition create the columns on:

- ▶ Asset class sheets
- ▶ Schedule sheets

For Schedule Manager, use this data definition to create data elements to gather numeric values from the cost sheet of a project into columns on a schedule sheet. Fields using this definition create the columns on schedule sheets.

SYS Yes No

Type: String

Size: 0

Input Type (Input Method): Pull-down Menu (Drop-down list)

Use on:

- ▶ Asset class forms
- ▶ Detail (attribute form) for a configurable manager
- ▶ Detail (attribute form) for a document
- ▶ Detail (attribute form) for a space

Description: Use this data definition to create any number of data elements that need a yes or no response.

Configurable Manager DDs

Use the following data definitions for creating the forms for any **Configurable Manager**.

CM[1...25] Picker

Type: Integer

Size: 0

Input Type (Input Method): Picker

Use on: Detail forms of Cost BPs and Line Item BPs, including any detail form for a tab on multiple-tab BPs of these types.

This DD is available for forms on mobile device.

Description: Picker for selecting a code or record from a configurable manager.

The code picker is created automatically when the manager is created.

The picker auto-populates elements from the manager record onto BP forms.

Unifier populates this picker with codes that were created with the configurable manager's attribute form.

Data Picker

Type: Integer

Size: 0

Input Type (Input Method): Pickers

Use on:

- ▶ Upper or detail forms of any business process

- ▶ Detail (attribute) form for a shell
- ▶ Detail (attribute) form for a space in the Space Manager
- ▶ Detail form of a Code and Records-based Configurable Manager
- ▶ Line items

This DD is available for forms on mobile device.

Description:

Picker for selecting a record from:

- ▶ From a master business process log
- ▶ From a class in a Configurable Manager that operates across shells
- ▶ From a type of space in the Space Manager
- ▶ For BP auto-creation across shells

Picker for selecting a date:

- ▶ This picker can be used to collect date and time information about a business process record.

Data pickers are **not** available:

- ▶ As a master element in a dynamic data set (DDS)
- ▶ As a value for a dynamic data set (DDS)
- ▶ For linked elements
- ▶ In validation rules

You can create any number of data elements from this definition.

Data pickers help prevent users from inadvertently choosing the wrong record from a picker list by filtering the content of the picker list. You can use them to filter large amounts of records into more manageable lists for users to choose from.

Data pickers work with master business process logs, shells, space types (in the Space Manager), and configurable managers that function across a shell hierarchy.

In operation, a data picker navigates to a specific business process, shell, space type, or configurable manager and extracts records to display on the picker list by using a query the Unifier Administrator sets up.

A data picker can be designed to display a navigation structure to guide users to the correct location where a record resides.

You can auto-populate and reverse auto-populate data pickers.

You can also create a hyperlink for a data picker. The hyperlink will be read-only, and will appear as a blank field if the picker has no values.

Note: The data displayed on data pickers is not restricted by permissions. Users will see all business processes, manager classes, or shells, regardless of their permissions.

See **Data Picker** (on page 360).

Shell Picker

Type: Integer

Size: 0

Input Type (Input Method): Picker

Use on:

- ▶ Upper or detail form of any business process.
- ▶ Asset class attribute form.
- ▶ Planning item attribute form.
- ▶ Configurable manager attribute form
- ▶ Detail form of any asset, planning item, or configurable manager.
- ▶ Detail form of Timesheet BP.

This DD is available for the same forms on mobile device.

Description: Picker for selecting a shell in Unifier.

You can create any number of data elements (fields) using this definition.

SYS BP Currency Amount

Type: Float

Size: 0

Input Type (Input Method): Currency

Use on:

- ▶ Code-based Manager forms
- ▶ Code and Records-based Manager forms

Description: Use this data definition to create data elements to gather currency values from the line items of a business process.

Fields using this definition create the columns on manager sheets.

SYS BP Decimal Amount

Type: Float

Size: 0

Input Type (Input Method): Text Box

Use on:

- ▶ Code-Based Manager forms
- ▶ Code and Records-based Manager forms

Description: Use this data definition to create data elements to gather decimal values from the line items of a business process.

Fields using this definition create the columns on manager sheets.

SYS BP Integer Amount

Type: Integer

Size: 0

Input Type (Input Method): Text Box

Use on:

- ▶ Code-Based Manager forms
- ▶ Code and Records-based Manager forms

Description: Use this data definition to create data elements to gather integer values from the line items of a business process.

Fields using this definition create the columns on manager sheets.

SYS Overbooking Options

Type: String

Size: 50

Input Type (Input Method): Pull-down Menu (Drop-down list)

Use on:

- ▶ Asset class forms
- ▶ Detail (attribute form) for a configurable manager
- ▶ Detail (attribute form) for a document
- ▶ Detail (attribute form) for a space

Note: The Data Elements (DEs) must be placed in a Shell Business Process, and the Activity Sheet must be located in the same Shell.

Description:

Pull-down Menu (Drop-down list) for selecting overbooking options for reservable assets/objects. The options are:

- ▶ Even if confirmed booking exists
- ▶ Only if tentative booking exists
- ▶ No overbooking

SYS Yes No

Type: String

Size: 0

Input Type (Input Method): Pull-down Menu (Drop-down list)

Use on:

- ▶ Asset class forms
- ▶ Detail (attribute form) for a configurable manager
- ▶ Detail (attribute form) for a document
- ▶ Detail (attribute form) for a space

Description: Use this data definition to create any number of data elements that need a yes or no response.

User Data Picker

Type: Integer

Size: 0

Input Type (Input Method): Data Picker

Category: Company

Use on:

- ▶ Both upper and detail forms of business processes at the company and project/shell level, including all non-standard tabs.
- ▶ Code and Records-based configurable manager attribute forms.
- ▶ Detail form for a space in the Space Manager.
- ▶ Shell attribute forms

Description:

- ▶ Picker for selecting a user and connecting to the user's attribute form.
- ▶ Works with the User Attribute form to auto-populate and reverse-auto-populate other forms.
- ▶ Differs from the User Picker because it can, itself, be auto-populated and reverse-auto-populated.
- ▶ This data picker does not use an advanced log navigation. Instead, the log for this user data picker uses the partner log designed in uDesigner.
- ▶ This picker will show all company and partner users, based on the conditions defined by the Unifier Administrator when the business process, configurable manager, space, or shell is configured.
- ▶ User data pickers can be updated via bulk edit and integration.
- ▶ You can create any number of data definitions and data elements (fields) using this definition.

Note: Data elements created with this data definition cannot be auto-populated via Web Services, or CSV files.

Cost Manager DDs

Use the following data definitions for creating the forms and the business processes for the **Cost Manager**.

Cost Attribute Forms DDs

The following are the data definitions used in **Cost Attribute Forms**.

Cost Attribute

Type: String

Size: 64

Input Method: Pull-down Menu (Drop-down list)

Use on: Cost Attribute Forms

Description: Unifier defines a default data element with this definition and only one is allowed per company.

The data set for this definition can be specified in Unifier.

Cost Item Type

Type: String

Size: 25

Input Type (Input Method): Pull-down Menu (Drop-down list)

Use on: Cost Attribute Forms

Description: Unifier defines a default data element with this definition, and only one is allowed per company.

The data set for this definition can be specified in Unifier.

Fund Attribute Forms DDs

The following are the data definitions used in **Fund Attribute Forms**.

Funding Category

Type: String

Size: 100

Input Type (Input Method): Pull-down Menu (Drop-down list)

Use on:

- ▶ Fund Attribute Forms
- ▶ Detail forms of Cost business processes

Description:

- ▶ You can create any number of data elements (fields) using this definition.
- ▶ Fields using this definition are usually used for defining funds.
- ▶ The data set for this definition will be specified in Unifier.

Cost Business Processes DDs

The following are the data definitions used in **Cost Business Processes**.

Account Code Picker

Type: Integer

Size: 0

Input Type (Input Method): Picker

Use on: Detail forms of company-level cost BPs of sub-type Line Items with Company Account Code.

This DD is available for the same forms on mobile device.

Description: Picker for selecting company-level account codes.

This definition is fixed and cannot be used to create any other data element.

Unifier populates this picker with the account codes from the company-level account sheet, which were created with the Account Code attribute form.

Asset Picker

Type: Integer

Size: 0

Input Type (Input Method): Picker

Use on: Upper or detail forms of company-level Cost BPs of sub-type Line Items with Asset Code.

This DD is available for the same forms on mobile device.

Description: Picker for selecting an asset for a project from the asset sheet.

This definition is fixed and cannot be used to create any other data element.

Unifier populates this picker with the asset records that were created with the Asset attribute form.

Cost Code Separator

Type: String

Size: 1

Input Type (Input Method): Text Box

Use on: Cost Manager, when defining CBS codes.

Description: Separator used between segments of a CBS code.

Values for this separator are specified in Unifier.

Only one value can be set per company.

Funding Category

Type: String

Size: 100

Input Type (Input Method): Pull-down Menu (Drop-down list)

Use on:

- ▶ Fund Attribute Forms
- ▶ Detail forms of Cost business processes

Description:

- ▶ You can create any number of data elements (fields) using this definition.
- ▶ Fields using this definition are usually used for defining funds.
- ▶ The data set for this definition will be specified in Unifier.

SYS Before After

Type: String

Size: 0

Input Type (Input Method): Pull-down Menu (Drop-down list)

Use on: Upper or detail forms of Reservation business processes that auto-create other BPs.

Description: Pull-down Menu (Drop-down list) for selecting when an auto-creation must occur (before or after a reservation event).

Document Manager DDs

Use the following data definitions for creating the attribute forms for the **Document Manager**.

SYS Auto Sequence

Type: String

Size: 512

Input Type (Input Method): Text Box

Use on: Document Attribute forms

Description:

- ▶ You can create any number of data elements (fields) using this definition.
- ▶ Fields using this definition provide auto-sequencing of unique numbers for all documents created.
- ▶ The content of the field is automatically generated based on the format for the autosequence data elements that is configured in Unifier. As a result:

- ▶ In the case of a workflow BP, the autosequence data elements in the BP record, or in the line item, get automatically generated when the workflow BP advances to the next step.
- ▶ In the case of a non-workflow BP, the autosequence data elements in the BP record, or in the line item, get automatically generated when the non-workflow BP is submitted.
- ▶ You can place two data elements with the SYS Auto Sequence data definition on a form.

Data elements that use this data definition:

- ▶ Are always read-only
- ▶ Can be placed in a hidden block
- ▶ Are available for Mobile configuration
- ▶ Can be selected as a display element of a Data Picker
- ▶ Can be added to Integration, marked as Output only
- ▶ Cannot be selected as a linked element
- ▶ Cannot auto-populate or reverse auto-populate
- ▶ Cannot use a hyperlink
- ▶ Cannot be part of a Dynamic Data Set definition

SYS Category

Type: String

Size: 128

Input Type (Input Method): Pull-down Menu (Drop-down list)

Use on:

- ▶ Folder Attribute forms
- ▶ Document Attribute forms

Description: Use this data definition to create a category for folders or documents.

The data set for this field will be specified in Unifier.

SYS Overbooking Options

Type: String

Size: 50

Input Type (Input Method): Pull-down Menu (Drop-down list)

Use on:

- ▶ Asset class forms
- ▶ Detail (attribute form) for a configurable manager
- ▶ Detail (attribute form) for a document
- ▶ Detail (attribute form) for a space

Note: The Data Elements (DEs) must be placed in a Shell Business Process, and the Activity Sheet must be located in the same Shell.

Description:

Pull-down Menu (Drop-down list) for selecting overbooking options for reservable assets/objects. The options are:

- ▶ Even if confirmed booking exists
- ▶ Only if tentative booking exists
- ▶ No overbooking

SYS Yes No

Type: String

Size: 0

Input Type (Input Method): Pull-down Menu (Drop-down list)

Use on:

- ▶ Asset class forms
- ▶ Detail (attribute form) for a configurable manager
- ▶ Detail (attribute form) for a document
- ▶ Detail (attribute form) for a space

Description: Use this data definition to create any number of data elements that need a yes or no response.

Lease Business Process DDs

Use the following data definitions for designing **Lease** business processes.

SYS Pay Creation Day of Month

Type: Integer

Size: 0

Input Type (Input Method): Pull-down Menu (Drop-down list)

Use on: Lease business processes

Description: Menu for choosing the amount of time (in days, zero to 30) before the payment due date that the invoice (payment request) should be created.

This time should include time for both creation and approval.

SYS Pay Day of Month

Type: Integer

Size: 0

Input Type (Input Method): Pull-down Menu (Drop-down list)

Use on: Lease business processes

Description: You can create any number of data elements (fields) using this definition.

Fields using this definition will allow Unifier users to specify a pay date for a lease or invoice business process.

SYS Payment Frequency

Type: String

Size: 50

Input Type (Input Method): Pull-down Menu (Drop-down list)

Use on: Lease business processes

Description: You can create any number of data elements (fields) using this definition.

Fields using this definition will allow Unifier users to select a payment frequency for an invoice or payment request business process.

SYS Payment Type

Type: String

Size: 100

Input Type (Input Method): Pull-down Menu (Drop-down list)

Use on:

- ▶ Lease Allocation Template
- ▶ Lease business process

Description: You can create any number of data elements (fields) using this definition.

Fields using this definition will allow Unifier users to select a payment type for a lease allocation template.

Note: For this data definition, the Unifier Administrator must create a data set of payment types.

SYS Proration Method

Type: String

Size: 50

Input Type (Input Method): Pull-down Menu (Drop-down list)

Use on: Lease business processes

Description: You can create any number of data elements (fields) using this definition.

Fields using this definition will allow Unifier users to specify the method by which lease payments should be calculated.

Planning Manager DDs

Use the following data definitions for designing the planning items and planning sheets for the **Planning Manager**.

Planning Item Creator

Type: Integer

Size: 0

Input Type (Input Method): Creator

Use on: Upper or detail form of any business process

Description: Use this definition to create data elements that will automatically create a new planning item based on a condition, such as a:

- ▶ Dollar amount
- ▶ Time frequency: daily or weekly

You can use multiple planning item creators on a single BP to create different types of planning item types.

When the BP reaches the condition or frequency trigger in the workflow, the creator element on the form will automatically create a new planning item. For example, you could create a data element using this definition called Downtown Remodel Plan that would generate a new planning item when an initiative kind of business process is approved. This new planning item can then be fleshed out to include budget estimates, personnel, dates, and so on.

Data elements built on the Planning Item Creator definition are visible on forms in two ways:

- ▶ If the Unifier user must manually create the new planning item, the element appears on the source BP as a text box with a **Create** option.
- ▶ If the new planning item is automatically created, the element will appear as a hyperlink from the source BP to the destination record.

Planning Item Picker

Type: Integer

Size: 0

Input Type (Input Method): Picker

Use on: Any business process form

This DD is available for forms on mobile device (read-only).

Description: This DD is a picker for selecting planning items from a planning sheet.

You can use this DD to create any number of data elements (fields).

Shell Picker

Type: Integer

Size: 0

Input Type (Input Method): Picker

Use on:

- ▶ Upper or detail form of any business process.
- ▶ Asset class attribute form.
- ▶ Planning item attribute form.
- ▶ Configurable manager attribute form
- ▶ Detail form of any asset, planning item, or configurable manager.
- ▶ Detail form of Timesheet BP.

This DD is available for the same forms on mobile device.

Description: Picker for selecting a shell in Unifier.

You can create any number of data elements (fields) using this definition.

SYS Date Datasource

Type: Date

Size: 0

Input Type (Input Method): Picker

Use on: Planning Item Attribute forms

This DD is available for the same forms on mobile device.

Description: Use this data definition to create data elements to gather date values from business processes.

Fields using this definition create the columns on Planning Sheets.

Creates read-only fields; not available for auto-population or dynamic data sets (DDSs).

SYS Date Logical Datasource

Type: Date

Size: 0

Input Type (Input Method): Picker

Use on:

- ▶ Detail form of any business process
- ▶ Asset attribute and class forms

- ▶ Planning item attribute forms
- ▶ Activity attribute forms

This DD is available for the same forms on mobile device.

Description: Use this definition to create fields for use in “date add” type formulas (using integers or decimals) to produce a new date.

You can also use this definition for a manual-entry field where the user chooses the date from a date picker.

Fields using this definition create the columns on:

- ▶ Planning Sheets
- ▶ Asset Sheets
- ▶ Schedule Sheets

Creates read-only fields; not available for auto-population or dynamic data sets.

SYS Numeric Datasource

Type: Float

Size: 0

Input Type (Input Method): Currency

Use on: Planning Sheet

Description: Use this data definition to create data elements to gather numeric values from business processes.

Fields using this definition create the columns on Planning Sheets.

Creates read-only fields; not available for auto-population or dynamic data sets.

SYS Numeric Logical Datasource

Type: Float

Size: 0

Input Type (Input Method): Currency

Use on:

- ▶ Asset attribute and class forms
- ▶ Planning item attribute forms
- ▶ Activity attribute forms

Description: Use this definition to create fields for use in numeric formulas and also in “date difference” type numeric formulas to produce the number of days between two dates.

You can also use this definition for a manual-entry field where the user enters decimal values, such as currencies.

Fields using this definition create the columns on:

- ▶ Asset sheets
- ▶ Planning sheets
- ▶ Schedule sheets

Note: This DD creates read-only fields, and it is not available for auto-population or dynamic data sets.

Resource Manager DDs

Use the following data definitions for designing the business processes and forms for the **Resource Manager**.

Activity Picker

Type: Integer

Size: 0

Input Type (Input Method): Picker

Use on: Detail forms of Time Sheet BPs

This DD is available for the same forms on mobile device (read-only).

Description: Picker for selecting an activity from the master schedule sheet.

This definition is fixed and cannot be used to create any other data element.

Unifier populates this picker with the activity records that were created with the Activity Attribute form.

Resource Picker

Type: Integer

Size: 0

Input Type (Input Method): Picker

Use on: Upper forms of Time Sheet BPs

This DD is available for the same forms on mobile device (read-only).

Description: This DD is a picker for selecting resources for assignment to projects and for report time worked.

This DD is fixed and cannot be used to create any other data element.

For more information, see **Resource Picker** (on page 370).

Role Picker

Type: Integer

Size: 0

Input Type (Input Method): Picker

Use on: Detail forms of Time Sheet BPs

This DD is available for the same forms on mobile device (read-only).

Description: Picker for selecting roles for assignment to resources and projects.

This definition is fixed and cannot be used to create any other data element.

SYS Resc Calendar NW Day Type

Type: String

Size: 50

Input Type (Input Method): Pull-down Menu (Drop-down list)

Use on: Created for the resource calendar in Unifier.

Description: Menu for choosing a non-working type of day.

The data set for this field will be specified in Unifier.

SYS Resc Work Type

Type: String

Size: 50

Input Type (Input Method): Pull-down Menu (Drop-down list)

Use on: Detail forms of Time Sheet BPs

Description: Pull-down Menu (Drop-down list) for selecting work types.

The data set for this field will be specified in Unifier.

SYS Resource Interest

Type: String

Size: 50

Input Type (Input Method): Pull-down Menu (Drop-down list)

Use on: Resource Attribute Forms

Description: Pull-down Menu (Drop-down list) for selecting an employee's interests.

The data set for this field will be specified in Unifier.

SYS Resource Proficiency

Type: String

Size: 50

Input Type (Input Method): Pull-down Menu (Drop-down list)

Use on: Resource Attribute Forms

Description: Pull-down Menu (Drop-down list) for selecting an employee's proficiency at a role.
The data set for this field will be specified in Unifier.

SYS Resource Skill

Type: String

Size: 50

Input Type (Input Method): Pull-down Menu (Drop-down list)

Use on: Resource Attribute Forms

Description: Pull-down Menu (Drop-down list) for selecting an employee's skill set.
The data set for this field will be specified in Unifier.

Week Picker

Type: Integer

Size: 0

Input Type (Input Method): Picker

Use on: Time Sheet BPs

This DD is available for the same forms on mobile device (read-only).

Description: Picker for selecting a week on time sheet business processes.
This definition is fixed and cannot be used to create any other data element.

SYSRoleType

Category: System

Type: String

Size: 128

Input Type (Input Method): Pull-down Menu (Drop-down list)

Use for: Capturing the "Type" of Role when a Role gets created via P6 integration.

Description: This is an internal data definition and will not be visible to end user for edits of any kind.

Dataset:

- ▶ Labor
- ▶ Nonlabor

- ▶ Material
- ▶ Expense

Default Value: None

Schedule Manager DDs

Use the following data definitions for designing the attribute forms for the **Schedule Manager**.

Activity Constraint

Type: Integer

Size: 0

Input Type (Input Method): Pull-down Menu (Drop-down list)

Use on: Schedule sheets

Description: Pull-down Menu (Drop-down list) for selecting a constraint between activities on a schedule sheet.

A constraint ties a successor activity start date to a predecessor activity completion date, after observing dependencies and lags.

The available constraints in Unifier are **As soon as possible (ASAP)** and **None**.

As soon as possible (ASAP): If the start date of a predecessor activity changes, this option either pulls in or pushes out the start date **For role amount recalculations**.

Any changes to start and finish dates, duration, predecessor activities, constraints, available days (via the calendar), activity levels (indent or out-dent), role rates, or currency exchange rates can trigger recalculation of the activity role amount. These rate changes will be reflected in cash flow distribution. The system calculates all values on a daily basis and adds up all amounts.

For activity amounts

An activity can have more than one role, each with its own costs. Unifier tallies the role amounts for an activity and displays the activity amount in cash flow, provided the activity is associated with at least one CBS code.

If you include a Role Data Picker on the form, you must also include the Role Amount **[uuu_ role_amt]** field on the form of an ASAP-constrained successor activity accordingly.

If an ASAP-constrained activity does not have a predecessor, the schedule sheet start date determines the activity start date; un-started ASAP-constrained successor activities align accordingly.

None: The start date of a None-constrained activity does not change if the start date of a predecessor activity changes. The schedule sheet start date does not determine the start date of None-constrained activities that do not have predecessor activities.

This data definition is fixed and cannot be used to create any other data elements.

It is reportable and is available for user defined reports and data views.

Activity Picker

Type: Integer

Size: 0

Input Type (Input Method): Picker

Use on: Detail forms of Time Sheet BPs

This DD is available for the same forms on mobile device (read-only).

Description: Picker for selecting an activity from the master schedule sheet.

This definition is fixed and cannot be used to create any other data element.

Unifier populates this picker with the activity records that were created with the Activity Attribute form.

Filtered Group

Type: String

Size: 128

Input Type (Input Method): Pull-down Menu (Drop-down list)

Use on: Activity Attribute forms

Description: Pull-down Menu (Drop-down list) for selecting groups.

The data set for this field will be specified in Unifier.

Resource Type

Type: String

Size: 128

Input Type (Input Method): Pull-down Menu (Drop-down list)

Use on: Resource Assignment Attribute forms

Description: This DD is a Pull-down Menu (Drop-down list) for selecting resource types (either hard booked or a resource category, such as Man-hours, Equipment, or Groups).

The data set for this field will be specified in Unifier.

Role Data Picker

Type: Integer

Size: 0

Input Type (Input Method): Picker

Use on: Resource Assignment Attribute forms

Description: This DD is a picker for selecting roles for assignment to schedule sheet activities.

You can create any number of data elements (fields) using this definition.

This data definition is not available for auto-population and reverse auto-population.

If this picker is included on the attribute form, the user can assign a role to an activity and Unifier will use the role information to calculate role costs.

The following explains how Unifier calculates the:

- ▶ Activity role rates
- ▶ Activity role amounts
- ▶ Role amount recalculations
- ▶ Activity amounts

Activity role rates

The system takes into account the effective date of the current role rate and the active currency exchange rate, and recalculates the role amount under these circumstances:

- ▶ Activity dates change
- ▶ Future-dated exchange rates become active
- ▶ The activity role rate changes
- ▶ The role changes

Activity role amounts

The system calculates the activity role amount on a daily basis. It considers the:

- ▶ Value of the role rate, as of the effective date (this can differ by effective date)
- ▶ Length of time the role rate was applicable before another role rate or exchange rate became effective.
- ▶ Active currency exchange rate (this can change due to currency fluctuations).
- ▶ Percentage of a role's assignment to the activity (%Unit) (this can differ during the activity)

The system uses active currency exchange rates for transaction-to-project currency conversions.

Role amount recalculations

Any changes to start and finish dates, duration, predecessor activities, constraints, available days (via the calendar), activity levels (indent or out-dent), role rates, or currency exchange rates can trigger recalculation of the activity role amount. These rate changes will be reflected in cash flow distribution. Unifier calculates all values on a daily basis and adds up all amounts.

Activity amounts

An activity can have more than one role, each with its own costs. The system tallies the role amounts for an activity and displays the activity amount in cash flow, provided the activity is associated with at least one CBS code.

Note: If you include a Role Data Picker on the form, you must also include the Role Amount (uuu_ role_amt) field on the form.

Role Picker

Type: Integer

Size: 0

Input Type (Input Method): Picker

Use on: Detail forms of Time Sheet BPs

This DD is available for the same forms on mobile device (read-only).

Description: Picker for selecting roles for assignment to resources and projects.

This definition is fixed and cannot be used to create any other data element.

SYS Activity Calendar

Type: Integer

Size: 0

Input Type (Input Method): Pull-down Menu (Drop-down list)

Use on: Activity Attribute forms

Description: Pull-down Menu (Drop-down list) for selecting an activity calendar.

SYS Activity Codes

Type: Integer

Size: Not Applicable

Input Type (Input Method): Pull-down Menu (Drop-down list)

Use on: Activity Attribute forms

Description: Pull-down Menu (Drop-down list) for selecting an activity code.

The data set for this field will be specified in Unifier.

SYS Activity Status

Type: String

Size: 50

Input Type (Input Method): Pull-down Menu (Drop-down list)

Use on: Activity Attribute forms

Description: This data definition supports the Scope Management feature of the Schedule Manager.

You cannot create a data element using this definition.

Unifier provides fixed activity statuses of:

- ▶ Not Started

- In Progress
- Complete
- Not Applicable

SYS Date Logical Datasource

Type: Date

Size: 0

Input Type (Input Method): Picker

Use on:

- Detail form of any business process
- Asset attribute and class forms
- Planning item attribute forms
- Activity attribute forms

This DD is available for the same forms on mobile device.

Description: Use this definition to create fields for use in “date add” type formulas (using integers or decimals) to produce a new date.

You can also use this definition for a manual-entry field where the user chooses the date from a date picker.

Fields using this definition create the columns on:

- Planning Sheets
- Asset Sheets
- Schedule Sheets

Creates read-only fields; not available for auto-population or dynamic data sets.

SYS Numeric Logical Datasource

Type: Float

Size: 0

Input Type (Input Method): Currency

Use on:

- Asset attribute and class forms
- Planning item attribute forms
- Activity attribute forms

Description: Use this definition to create fields for use in numeric formulas and also in “date difference” type numeric formulas to produce the number of days between two dates.

You can also use this definition for a manual-entry field where the user enters decimal values, such as currencies.

Fields using this definition create the columns on:

- ▶ Asset sheets
- ▶ Planning sheets
- ▶ Schedule sheets

Note: This DD creates read-only fields, and it is not available for auto-population or dynamic data sets.

SYS Project Cost Datasource

Type: Float

Size: 0

Input Type (Input Method): Currency

Use on:

- ▶ Asset class detail form
- ▶ Activity Attribute form

Description: Use this data definition to create data elements to gather numeric values from the cost sheet of the project associated with an asset.

Fields using this definition create the columns on:

- ▶ Asset class sheets
- ▶ Schedule sheets

For Schedule Manager, use this data definition to create data elements to gather numeric values from the cost sheet of a project into columns on a schedule sheet. Fields using this definition create the columns on schedule sheets.

Shell Manager DDs

Use the following data definitions for designing the forms for the **Shell Manager**.

Auto-update Status Setup Picker

Type: String

Size: 100

Input Type (Input Method): Pull-down Menu (Drop-down list)

Use on:

- ▶ Shell attribute forms
- ▶ Project details

Description: Pull-down Menu (Drop-down list) for selecting Auto-update Status Setups, which are defined in Unifier under the Company Workspace.

This definition supports the automatic update of shell status in Unifier.

Date Picker

Type: Timestamp

Size: 0

Input Type (Input Method): Picker

Use on: Upper or detail forms of any business process

This DD is available for the same forms on mobile device.

Description: Picker for selecting a date.

This picker can be used to collect date and time information about a business process record.

Project Phase

Type: String

Size: 64

Input Type (Input Method): Pull-down Menu (Drop-down list)

Use on:

- ▶ Upper or detail forms of project/shell level BPs
- ▶ Project/Shell Creation BP

Description: Use this DD to create any number of data elements (fields).

Fields using this DD can be used to enter the name of the project phase.

The data set for this field will be specified in Unifier and will be available under the project shell as a project phase field when users are defining a project, or when a project is auto-created using the Project/Shell Creation BP.

SYS Shell Number

Type: String

Size: 128

Input Type (Input Method): Text Box

Use on:

- ▶ Shell attribute forms
- ▶ Project/Shell Creation BP

Description: You can create any number of data elements (fields) using this definition.

Fields using this definition will allow Unifier users to enter a number for a shell.

For Project/Shell Creation type BPs, you need to create a data element based on this definition.

This data definition is a mandatory field for the form.

Shell Picker

Type: Integer

Size: 0

Input Type (Input Method): Picker

Use on:

- ▶ Upper or detail form of any business process.
- ▶ Asset class attribute form.
- ▶ Planning item attribute form.
- ▶ Configurable manager attribute form
- ▶ Detail form of any asset, planning item, or configurable manager.
- ▶ Detail form of Timesheet BP.

This DD is available for the same forms on mobile device.

Description: Picker for selecting a shell in Unifier.

You can create any number of data elements (fields) using this definition.

SYS Shell Name

Type: String

Size: 128

Input Type (Input Method): Text Box

Use on:

- ▶ Shell attribute forms
- ▶ Project/Shell Creation BP

Description: You can create any number of data elements (fields) using this definition.

Fields using this definition will allow Unifier users to enter a name for a shell or project.

For Project/Shell Creation type BPs, you need to create a data element based on this definition.

This data definition is a mandatory field for the form.

User Data Picker

Type: Integer

Size: 0

Input Type (Input Method): Data Picker

Category: Company

Use on:

- ▶ Both upper and detail forms of business processes at the company and project/shell level, including all non-standard tabs.
- ▶ Code and Records-based configurable manager attribute forms.
- ▶ Detail form for a space in the Space Manager.
- ▶ Shell attribute forms

Description:

- ▶ Picker for selecting a user and connecting to the user's attribute form.
- ▶ Works with the User Attribute form to auto-populate and reverse-auto-populate other forms.
- ▶ Differs from the User Picker because it can, itself, be auto-populated and reverse-auto-populated.
- ▶ This data picker does not use an advanced log navigation. Instead, the log for this user data picker uses the partner log designed in uDesigner.
- ▶ This picker will show all company and partner users, based on the conditions defined by the Unifier Administrator when the business process, configurable manager, space, or shell is configured.
- ▶ User data pickers can be updated via bulk edit and integration.
- ▶ You can create any number of data definitions and data elements (fields) using this definition.

Note: Data elements created with this data definition cannot be auto-populated via Web Services, or CSV files.

SYSP6ScheduleType

Category: System

Type: String

Size: 128

Input Type (Input Method): Pull-down Menu (Drop-down list)

Use for: Capturing the P6 Schedule Type: Duration Based, Resource Loaded or Cost Loaded

Description: This is an internal Data definition and will not be visible to end user for edits of any kind.

Dataset:

- ▶ Duration Based
- ▶ Resource Loaded
- ▶ Cost Loaded

Default Value: None

Space Manager DDs

Use the following data definitions for designing the forms for the **Space Manager**.

Data Picker

Type: Integer

Size: 0

Input Type (Input Method): Pickers

Use on:

- ▶ Upper or detail forms of any business process
- ▶ Detail (attribute) form for a shell
- ▶ Detail (attribute) form for a space in the Space Manager
- ▶ Detail form of a Code and Records-based Configurable Manager
- ▶ Line items

This DD is available for forms on mobile device.

Description:

Picker for selecting a record from:

- ▶ From a master business process log
- ▶ From a class in a Configurable Manager that operates across shells
- ▶ From a type of space in the Space Manager
- ▶ For BP auto-creation across shells

Picker for selecting a date:

- ▶ This picker can be used to collect date and time information about a business process record.

Data pickers are **not** available:

- ▶ As a master element in a dynamic data set (DDS)
- ▶ As a value for a dynamic data set (DDS)
- ▶ For linked elements
- ▶ In validation rules

You can create any number of data elements from this definition.

Data pickers help prevent users from inadvertently choosing the wrong record from a picker list by filtering the content of the picker list. You can use them to filter large amounts of records into more manageable lists for users to choose from.

Data pickers work with master business process logs, shells, space types (in the Space Manager), and configurable managers that function across a shell hierarchy.

In operation, a data picker navigates to a specific business process, shell, space type, or configurable manager and extracts records to display on the picker list by using a query the Unifier Administrator sets up.

A data picker can be designed to display a navigation structure to guide users to the correct location where a record resides.

You can auto-populate and reverse auto-populate data pickers.

You can also create a hyperlink for a data picker. The hyperlink will be read-only, and will appear as a blank field if the picker has no values.

Note: The data displayed on data pickers is not restricted by permissions. Users will see all business processes, manager classes, or shells, regardless of their permissions.

See **Data Picker** (on page 360).

Level Picker

Type: Integer

Size: 0

Input Type (Input Method): Picker

Use on: Space detail forms

This DD is available for the same forms on mobile device (read-only).

Description: This is a picker for selecting a level to view in Unifier.

Use this DD to create any number of data elements (fields).

This DD Cannot be used to create any other data elements.

This DD Is available for auto-population.

Space Picker

Type: Integer

Size: 0

Input Type (Input Method): Picker

Use on:

- ▶ Upper form of any business process
- ▶ Asset class

This DD is available for the same forms on mobile device.

Description: Picker for selecting a space from the Space Manager records.

This definition cannot be used to create any other data element.

SYS Overbooking Options

Type: String

Size: 50

Input Type (Input Method): Pull-down Menu (Drop-down list)

Use on:

- ▶ Asset class forms
- ▶ Detail (attribute form) for a configurable manager
- ▶ Detail (attribute form) for a document
- ▶ Detail (attribute form) for a space

Note: The Data Elements (DEs) must be placed in a Shell Business Process, and the Activity Sheet must be located in the same Shell.

Description:

Pull-down Menu (Drop-down list) for selecting overbooking options for reservable assets/objects. The options are:

- ▶ Even if confirmed booking exists
- ▶ Only if tentative booking exists
- ▶ No overbooking

SYS Space Name

Type: String

Size: 50

Input Type (Input Method): Text Box

Use on: Detail forms for spaces

Description: You can create any number of data elements (fields) using this definition.

Fields using this definition will allow Unifier users to enter a name for a space at runtime.

The name can be up to 50 characters long.

SYS Space Unit of Measure

Type: String

Size: 128

Input Type (Input Method): Pull-down Menu (Drop-down list)

Use on: Space and level forms

Description: You can create any number of data elements (fields) using this definition.

Fields using this definition can be used to enter the unit of measure to use for measuring a space.

The data set for this field will be specified in Unifier.

SYS Yes No

Type: String

Size: 0

Input Type (Input Method): Pull-down Menu (Drop-down list)

Use on:

- ▶ Asset class forms
- ▶ Detail (attribute form) for a configurable manager
- ▶ Detail (attribute form) for a document
- ▶ Detail (attribute form) for a space

Description: Use this data definition to create any number of data elements that need a yes or no response.

User Data Picker

Type: Integer

Size: 0

Input Type (Input Method): Data Picker

Category: Company

Use on:

- ▶ Both upper and detail forms of business processes at the company and project/shell level, including all non-standard tabs.
- ▶ Code and Records-based configurable manager attribute forms.
- ▶ Detail form for a space in the Space Manager.
- ▶ Shell attribute forms

Description:

- ▶ Picker for selecting a user and connecting to the user's attribute form.
- ▶ Works with the User Attribute form to auto-populate and reverse-auto-populate other forms.
- ▶ Differs from the User Picker because it can, itself, be auto-populated and reverse-auto-populated.
- ▶ This data picker does not use an advanced log navigation. Instead, the log for this user data picker uses the partner log designed in uDesigner.
- ▶ This picker will show all company and partner users, based on the conditions defined by the Unifier Administrator when the business process, configurable manager, space, or shell is configured.
- ▶ User data pickers can be updated via bulk edit and integration.
- ▶ You can create any number of data definitions and data elements (fields) using this definition.

Note: Data elements created with this data definition cannot be

auto-populated via Web Services, or CSV files.

Global DDs

Use the following data definitions for creating most forms.

BP Creator

Type: Integer

Size: 0

Input Type (Input Method): Creator

Use on: Upper or detail form of any business process

This DD is available for the same forms on mobile device.

You *cannot* use a BP Creator element to create the following types of BPs:

- ▶ Single record
- ▶ Payment Application
- ▶ Change Commit
- ▶ General Spends
- ▶ Commit at Company Level

Description: Use this definition to create data elements that will automatically create a new business process based on a condition, such as a dollar amount, or a time frequency, such as daily or weekly.

You can use multiple BP creators on a single BP to create different types of BPs.

When the BP reaches the condition or frequency trigger in the workflow, the BP creator element on the form will automatically create a new business process. For example, you could create a data element using this definition called Work Order Creator that would generate work orders for your company's assets at periodic intervals depending on the service needs of the asset.

Data elements built on the BP Creator definition are visible on forms in two ways:

- ▶ If the Unifier user must manually create the new BP, the element appears on the source BP as a text box with a **Create** button.
- ▶ If the new BP is automatically created, the element will appear as a hyperlink from the source BP to the destination BP.

BP Picker

Type: Integer

Size: 0

Input Type (Input Method): Picker

Use on: Any upper or detail form

This DD is available for the same forms on mobile device.

Description: Picker for linking one business process to another.

Note: This definition is fixed and cannot be used to create any other data element.

You can create any number of data elements (fields) using this definition.

You receive several predefined pickers based on this definition. For a list of these pickers, see **Pickers** (on page 351).

This picker is populated by the reference process that accompanies the business process.

Company Picker

Type: Integer

Size: 0

Input Type (Input Method): Picker

Use on: Any upper form or detail form

This DD is available for the same forms on mobile device.

You can use this picker on business processes at both the company and project/shell levels.

- ▶ For a company-level BP, it will show partner companies
- ▶ For a project/shell level BP, it will show member companies.

Description: Picker for selecting a partner or member company.

This definition is fixed and cannot be used to create any other data element.

Note: You must enter the display element value of the Company Picker field in order to see the picker.

Currency Amount

Type: Float

Size: 0

Input Type (Input Method): Currency

Use on: Any form

Description: Use this definition to create data elements that will collect the currency amount on a business process.

The currency amount will be automatically formatted to honor the currency specified in the currency details window. (**Company Workspace > Admin mode > Standards & Libraries > Currencies > [Currency]**)

If the data has a decimal value, the number of decimal values will follow the number of decimal places specified in the currency details window.

Date Only

Type: Date

Size: 0

Input Type (Input Method): Picker

Use on: Any form

This DD is available for forms on mobile device.

Description: Picker for selecting a date.

This data definition differs from the Date Picker in that it includes the date only; no time or time zone.

This definition stores the time as midnight (00:00) and the time zone as the zone where the server resides, but it does not display these values.

Use this data definition for “date-add” and “date-difference” formulas, as well as simple date-only fields on forms.

The behavior of data elements in formulas differs, depending on the formula and the numeric form.

The “Date add” and “date difference” formulas with integers can be used with other Date Only elements.

The “Date add” formulas using decimal numbers are calculated from midnight as in the following examples:

- ▶ 08/29/2008 + 2.21 = 08/31/2008
- ▶ 08/29/2008 + [-2.21] = 08/26/2008

Decimal Amount

Type: Float

Size: 0

Input Type (Input Method): Text Box

Use on: Any Form

Description: You can create any number of data elements (fields) using this definition.

Fields using this definition can be used to collect numeric decimal data. The numeric decimal will be automatically formatted with comma (,) separators and the number of decimal places will vary depending on the maximum number of decimal places allowed by the browser.

Description Text

Type: String

Size: 250

Input Type (Input Method): Multiple Text Lines

Use on: Any form

Description: You can create any number of data elements (fields) using this definition.

Fields using this definition will allow Unifier users to enter 250 characters at runtime.

Discipline

Type: String

Size: 64

Input Type (Input Method): Pull-down Menu (Drop-down list)

Use on: Any form

Description: You can create any number of data elements (fields) using this definition.

The data set for this definition will be specified in Unifier.

Group Name Picker

Type: String

Size: 4000

Input Type (Input Method): Picker

Use on: Any form

This DD is available for forms on mobile device.

Note: Do not use this picker on configurable manager attribute forms.

Description: Picker for selecting a group of personnel from the groups defined at the company level. See **Group Name Picker** (on page 368).

You can create any number of data elements (fields) using this definition.

Hyperlink Picker

Type: Hyperlink

Size: 0

Input Type (Input Method): Picker

Use on: Any form

This DD is available for forms on mobile device, *except for Shell attribute forms*.

Description: Use this definition to create hyperlinks to URLs external to Unifier.

When users click the hyperlink, the URL will appear in a new window.

This data definition stores the hyperlink name and the URL with the record.

This definition will support elements for manual entry, formulas (for the destination element, not the source element), auto-population, UDR or BI Report printing, and integration.

Only the URL name is mandatory for a hyperlink picker. You can design the hyperlink to appear on an action form as the URL only, or as a URL plus the name.

Image Picker

Type: Integer

Size: 0

Input Type (Input Method): Picker

Use on: Any form, *except cost and document attribute forms.*

This DD is available for the same forms on mobile device, *but the field only displays the image file-name.*

Description: Picker for selecting images to display on records or other pages in the Unifier user interface (UI).

When creating the data element, you will need to specify the height of the image in pixels. The horizontal size of the image is automatically adjusted to fit the column width.

Image files cannot be larger than 1MB and must be in the one of the following formats:

- ▶ .jpg
- ▶ .jpeg
- ▶ .gif
- ▶ .png
- ▶ .tif

Note: Images will appear in the Unifier UI, but they will not appear in print on forms, reports, or email notifications.

In addition, if you auto-populate this picker, the values will not appear if the record is created via CSV file integration.

Integer Amount

Type: String

Size: 0

Input Type (Input Method): Text Box

Use on: Any form.

Note: Do not use this picker on configurable manager attribute forms.

Description: You can create any number of data elements (fields) using this definition.

Fields using this definition can be used to collect numeric data.

The data will be automatically formatted with comma (,) separators.

Decimal values are not allowed.

Multi Select

Type: String

Size: 4000

Input Type (Input Method): Pull-down Menu (Drop-down list).

Use on: Any form.

Description: Use this DD to create any number of data elements (fields).

Fields using this DD can be used to collect multiple choices from a list. The data will be automatically formatted with comma (,) separators.

Line Item Data Picker

Type: String

Size: 4000

Input Type (Input Method): Pull-down Menu (Drop-down list).

Use on: Any form.

Description: Use this DD to create any number of data elements (fields), based on Line Item Data Picker data definition.

Project Picker

Type: Integer

Size: 0

Input Type (Input Method): Picker

Use on:

- ▶ Upper or detail forms of project/shell level BPs
- ▶ Detail form of Timesheet BPs

Description: This DD is a picker for selecting a project. For more information, see **Project Picker** (on page 370).

This DD is fixed and cannot be used to create any other data element.

Project Site

Type: String

Size: 3

Input Type (Input Method): Pull-down Menu (Drop-down list)

Use on: Upper or detail forms of project/shell level BPs.

Description: Use this DD to create any number of data elements (fields).

The data set for this field will be specified in Unifier and will be available under the project/shell.

Project Type

Type: String

Size: 5

Input Type (Input Method): Pull-down Menu (Drop-down list)

Use on: Upper or detail forms of project/shell level BPs

Description: Use this DD to create any number of data elements (fields).

The data set for this field will be specified in Unifier and will be available under the project/shell as a project type field when you are defining a project.

Record Number Data

Type: String

Size: 20

Input Type (Input Method): Text Box

Use on: Upper forms.

Description: You can create any number of data elements (fields) using this definition.

Unifier provides a default-field based on this definition and will assign a record number based on the configuration in Unifier.

Shell Picker

Type: Integer

Size: 0

Input Type (Input Method): Picker

Use on:

- ▶ Upper or detail form of any business process.
- ▶ Asset class attribute form.
- ▶ Planning item attribute form.

- ▶ Configurable manager attribute form
- ▶ Detail form of any asset, planning item, or configurable manager.
- ▶ Detail form of Timesheet BP.

This DD is available for the same forms on mobile device.

Description: Picker for selecting a shell in Unifier.

You can create any number of data elements (fields) using this definition.

Short Description Text

Type: String

Size: 50

Input Type (Input Method): Text Box

Use on: Any form

Description: You can create any number of data elements (fields) using this definition.

Fields using this definition will allow Unifier users to enter 50 characters at runtime.

Space Picker

Type: Integer

Size: 0

Input Type (Input Method): Picker

Use on:

- ▶ Upper form of any business process
- ▶ Asset class

This DD is available for the same forms on mobile device.

Description: Picker for selecting a space from the Space Manager records.

This definition cannot be used to create any other data element.

SYS Auto Sequence

Type: String

Size: 512

Input Type (Input Method): Text Box

Use on: Document Attribute forms

Description:

- ▶ You can create any number of data elements (fields) using this definition.

- ▶ Fields using this definition provide auto-sequencing of unique numbers for all documents created.
- ▶ The content of the field is automatically generated based on the format for the autosequence data elements that is configured in Unifier. As a result:
 - ▶ In the case of a workflow BP, the autosequence data elements in the BP record, or in the line item, get automatically generated when the workflow BP advances to the next step.
 - ▶ In the case of a non-workflow BP, the autosequence data elements in the BP record, or in the line item, get automatically generated when the non-workflow BP is submitted.
- ▶ You can place two data elements with the SYS Auto Sequence data definition on a form.

Data elements that use this data definition:

- ▶ Are always read-only
- ▶ Can be placed in a hidden block
- ▶ Are available for Mobile configuration
- ▶ Can be selected as a display element of a Data Picker
- ▶ Can be added to Integration, marked as Output only
- ▶ Cannot be selected as a linked element
- ▶ Cannot auto-populate or reverse auto-populate
- ▶ Cannot use a hyperlink
- ▶ Cannot be part of a Dynamic Data Set definition

SYS Check Box

Type: Integer

Size: 0

Input Type (Input Method): Checkbox

Use on: Any form

Description: You can create any number of data elements (fields) using this definition.

Fields using this definition will be displayed as check boxes on business process forms.

SYS Description Text 500

Type: String

Size: 500

Input Type (Input Method): Multiple Text Lines

Use on: Any form

Description: You can create any number of data elements (fields) using this definition.

Fields using this definition will allow Unifier users to enter 500 characters at runtime.

SYS Description Text 2000

Type: String

Size: 2000

Input Type (Input Method): Multiple Text Lines

Use on: Any form

Description: You can create any number of data elements (fields) using this definition.
Fields using this definition will allow Unifier users to enter 2000 characters at runtime.

SYS Line Item Status

Type: String

Size: 50

Input Type (Input Method): Pull-down Menu (Drop-down list)

Use on: The detail form of:

- ▶ Line Item BPs
- ▶ Document BPs

Description: You can create any number of data elements (fields) using this definition.
Fields using this definition can be used as the line item status.
The data set for this field will be specified in uDesigner.

SYS Long Description Text

Type: String

Size: 4000

Input-Method: Multiple Text Lines

Use on: Any form

Description: You can create any number of data elements (fields) using this definition.
Fields using this definition will allow Unifier users to enter 4000 characters at runtime.

SYS Long Name

Type: String

Size: 250

Input Type (Input Method): Text Box

Use on: Any form

Description: You can create any number of data elements (fields) using this definition.

Fields using this definition will allow Unifier users to enter 250 characters at runtime.

SYS Medium Name

Type: String

Size: 64

Input Type (Input Method): Text Box

Use on: Any form

Description: You can create any number of data elements (fields) using this definition.

Fields using this definition will allow Unifier users to enter 64 characters at runtime.

SYS Numeric Query Based

Type: Float

Size: 0

Input Type (Input Method): Currency

Use on: Upper form of any business process, *except the RFB bidders form and company-level single record BPs.*

This DD is available for the same forms on mobile device, *except the RFB bidders form and company-level single record BPs.*

Note: You can place up to five query-based elements on a form.

Description: You can create any number of data elements using this definition.

Data elements built on the **SYS Numeric Query Based** data definition extract data from any business process or manager sheet.

These elements prompt Unifier to run a query to extract the information.

Note: This query is created by the administrator at the time the business process is configured.

These elements are updated:

- ▶ When a user opens the business process. The system runs the query and, if conditions are met, displays the latest value in the query-based field.
- ▶ When a user changes the value in a “trigger element” on a business process form. The trigger element prompts Unifier to run the query again and dynamically update the value in the query-based field.

This DD creates a read-only field.

SYS Short Description Text 32

Type: String

Size: 32

Input Type (Input Method): Text Box

Use on: Any form

Description: You can create any number of data elements (fields) using this definition.

Fields using this definition will allow Unifier users to enter 32 characters at runtime.

SYS Short Description Text 36

Type: String

Size: 36

Input Type (Input Method): Text Box

Use on: Any form

Description: You can create any number of data elements (fields) using this definition.

Fields using this definition will allow Unifier users to enter 40 characters at runtime.

SYS Short Description Text 40

Type: String

Size: 40

Input Type (Input Method): Text Box

Use on: Any form

Description: You can create any number of data elements (fields) using this definition.

Fields using this definition will allow Unifier users to enter 40 characters at runtime.

SYS Short Description Text 50

Type: String

Size: 50

Input Type (Input Method): Text Box

Use on: Any form

Description: You can create any number of data elements (fields) using this definition.

Fields using this definition will allow Unifier users to enter 50 characters at runtime.

SYS Short Description Text 120

Type: String

Size: 120

Input Type (Input Method): Text Box

Use on: Any form

Description: You can create any number of data elements (fields) using this definition.

Fields using this definition will allow Unifier users to enter 120 characters at runtime.

SYS Short Description Text 250

Type: String

Size: 250

Input Type (Input Method): Text Box

Use on: Any form

Description: You can create any number of data elements (fields) using this definition.

Fields using this definition will allow Unifier users to enter 250 characters at runtime.

SYS Short Description Text 255

Type: String

Size: 255

Input Type (Input Method): Text Box

Use on: Any form

Description: You can create any number of data elements (fields) using this definition.

Fields using this definition will allow Unifier users to enter 255 characters at runtime.

SYS Short Name

Type: String

Size: 8

Input Type (Input Method): Text Box

Use on: Any form

Description: You can create any number of data elements (fields) using this definition.

Fields using this definition will allow Unifier users to enter 8 characters at runtime.

SYS Yes No

Type: String

Size: 0

Input Type (Input Method): Pull-down Menu (Drop-down list)

Use on:

- ▶ Asset class forms
- ▶ Detail (attribute form) for a configurable manager
- ▶ Detail (attribute form) for a document
- ▶ Detail (attribute form) for a space

Description: Use this data definition to create any number of data elements that need a yes or no response.

Unit of Measure

Type: String

Size: 25

Input Type (Input Method): Pull-down Menu (Drop-down list)

Use on: Any form

Description: You can create any number of data elements (fields) using this definition.

The data set for this field will be specified in Unifier.

User Data Picker

Type: Integer

Size: 0

Input Type (Input Method): Data Picker

Category: Company

Use on:

- ▶ Both upper and detail forms of business processes at the company and project/shell level, including all non-standard tabs.
- ▶ Code and Records-based configurable manager attribute forms.
- ▶ Detail form for a space in the Space Manager.
- ▶ Shell attribute forms

Description:

- ▶ Picker for selecting a user and connecting to the user's attribute form.
- ▶ Works with the User Attribute form to auto-populate and reverse-auto-populate other forms.

- ▶ Differs from the User Picker because it can, itself, be auto-populated and reverse-auto-populated.
- ▶ This data picker does not use an advanced log navigation. Instead, the log for this user data picker uses the partner log designed in uDesigner.
- ▶ This picker will show all company and partner users, based on the conditions defined by the Unifier Administrator when the business process, configurable manager, space, or shell is configured.
- ▶ User data pickers can be updated via bulk edit and integration.
- ▶ You can create any number of data definitions and data elements (fields) using this definition.

Note: Data elements created with this data definition cannot be auto-populated via Web Services, or CSV files.

User Picker

Type: Integer

Size: 0

Input Type (Input Method): Picker

Use on: Any form

- ▶ At a company-level BP, it will show active company users.
- ▶ At the project-level, it will show active and on-hold project users.
- ▶ At the shel- level, it will show active and on-hold users.

This DD is available for the same forms on mobile device.

Description: Picker for selecting a user name.

Note: The behavior of this definition differs from the User Data Picker.

Other DDs (in Alphabetical Order: A-G)

Use the following Data Definitions (DDs), presented alphabetically, for creating the attribute forms, Business Processes, and other entities.

Bid Picker

Type: Integer

Size: 0

Input Type (Input Method): Picker

Use on: Upper or detail form of any business process

Description: This Data Definition will be used to create System Data Element: **Winning Bid**.

You will be able to see all received bids and select a winning bid using this picker.

BP Line Item Creator

Type: Integer

Size: 0

Input Type (Input Method): Picker

Use on: Upper or detail form of any business process

Description: Use this definition to create data elements that will automatically create new business process line items based on a condition, such as a dollar amount.

You can use multiple BP line item creators on a single BP to create different types of line items.

When the BP reaches the condition in the workflow, the BP creator line item element on the form will automatically create a new business process line item on another, existing, record.

Data elements built on the BP Line Item Creator definition are visible on forms in two ways:

- ▶ If the Unifier user must manually create the new line item, the element appears on the source line item as a text box with a Create button.
- ▶ The element will appear as a hyperlink from the source line item to the destination line item.

BP Line Item Picker

Type: Integer

Size: 0

Input Type (Input Method): Picker

Use on: Can be used anywhere where BP Pickers are supported.

Note: You cannot use a BP Line Item Picker in an Activity Attribute Form.

Description: Use this data definition to create:

- ▶ Data elements for line item pickers.
- ▶ Any number of data elements that need a yes or no response.

Date Only Picker

Type: Timestamp

Size: 0

Input Type (Input Method): Picker

Use on: Any form

This DD is available for forms on mobile device.

Description: This is a system calculated picker.

This picker cannot be used in Dynamic Data Sets (DDSs), Validation rules, linked elements, or as part of formula (source or destination).

Other DDs (in Alphabetical Order: H-N)

Use the following Data Definitions (DDs), presented alphabetically, for creating the attribute forms, Business Processes, and other entities.

Other DDs (in Alphabetical Order: O-T)

Use the following Data Definitions (DDs), presented alphabetically, for creating the attribute forms, Business Processes, and other entities.

Record Status Pulldown

Type: String

Size: 128

Input Type (Input Method): String

Use on: Upper or detail forms of a non-Workflow Business Processes forms

Description: Use this DD to create DEs which can Reverse Auto-Populate into the Status element of non-Workflow Business Processes.

Seasonal Dates Picker

Type: Integer

Size: 0

Input Type (Input Method): Picker

Use on: DE based on this DD can be placed on one or more detail forms of a WF or NWF, single or multi-record, Company or Shell level Generic or Preventive Maintenance Line Item BP.

Description: Picker for selecting seasonal dates records.

SYS Barcode

Type: String

Size: 128

Input Type (Input Method): Text Box

Use on:

Use SYS Barcode to create data elements that can be used to scan bar codes on assets, in the Unifier application.

Description: Any number of custom data elements can be defined for this data definition.

Note: The SYS Bar Code data definition cannot be selected when the user creates a new data element.

Additional Features:

Features available for regular text box fields.

SYS Cost Line Item Type

Type: Integer

Size: Not applicable

Input Type (Input Method): Pull-down Menu (System)

Use on: This system DD is used in Cost BPs of Summary Payment Application SOV type.

When users create new Data Elements, they should not be able to select this DD.

Pull-down Data Set: Lump Sum, Unit Cost, Variable Unit Cost

Description: This system DD is used by the system in order to determine if a line item is of Lump Sum or of Unit Cost Type.

This is a system defined Data Definition (DD). Users will not be able to create new DEs of this DD type.

SYS Duration Type

Type: String pull down

Size: 0

Input Type (Input Method): Pull-down Menu (Drop-down list)

Pull-down Data Set:

- ▶ Fixed Duration
- ▶ Fixed Units
- ▶ Fixed Units/Time

Note: This system DD is shown in basic data definitions, under the Data Structure Setup. Users are not allowed to update or edit the data set options.

SYS Expense Category

Category: String

Type: String

Size: 128

Input Type (Input Method): Pull-down Menu (Drop-down list)

Use in: P6-Unifier Integration.

The dataset values will get populated from P6 global object “Expense Categories”

Description: The values are from P6, available via integration.

The user cannot set a default value, add new dataset values, or edit the existing dataset values.

SYS Family Identifier

Type: Integer

Size: 0

Input Type (Input Method): Pull-down Menu (Drop-down list)

Use on: Time detail form and Continuous Meter detail form of PM Book.

Description: The DE **uuu_rec_family_identifier** uses this Integer Pull-down Menu (Drop-down list) DD that has a user-defined dataset.

Note: All the lines that have the same value as this Pull-down Menu (Drop-down list) must be treated as belonging to the same family.

SYS Frequency Units

Type: Integer

Size: 0

Input Type (Input Method): Pull-down Menu (Drop-down list)

Use on:

- ▶ PM Book Time detail form
- ▶ PM Book template Time detail form
- ▶ PM Book Meter Detail form of subtype Continuous

Description: The DE **uuu_rec_frequency_unit** which uses this Integer drop-down DD.

The data set values for this DD are:

- ▶ Day(s)
- ▶ Week(s)
- ▶ Month(s)
- ▶ Year(s)

SYS Meter Type

Type: Integer

Size: 0

Input Type (Input Method): Pull-down Menu (Drop-down list)

Use on:

- ▶ Meter detail form of Asset BP
- ▶ Meter detail form of Asset template BP
- ▶ Upper form of Meter Reading BP

Description: Use this data definition to capture the type of Meter that is being captured on the Asset forms.

SYS Reading Type

Type: Integer

Size: 0

Input Type (Input Method): Pull-down Menu (Drop-down list)

Use on: Detail form of Meter Reading BP

Description: The DE `uuu_meter_rdnng_type` uses this DD to capture if the entered meter reading is a regular reading, a rollover reading or a New Meter reading.

SYS Rich Text

Type: String

Size: Restricted to 2 MB size

Input Type (Input Method): Picker

Use on: BP Upper Form

Pull-down Data Set: N/A

Description: Enables you to enter large text data in Unifier in an organized manner and format it so that it is easy to enter, read, and share.

Note: The SYS Rich Text Data Elements are not available to be set as Display Element, in a Data Picker configuration.

SYS Schedule Type

Type: Integer

Size: 0

Input Type (Input Method): Pull-down Menu (Drop-down list)

Use on:

- ▶ Time detail form of PM Book and in Continuous Meter Detail form of PM Book.
- ▶ It can be added to the corresponding forms in PM Book templates as well.

Description: The DE **uuu_rec_schedule_type** which uses this DD is captures the schedule for a work order. It can either be fixed (generate new record irrespective of status of previous record) or floating (schedule next record only when previous record is completed/canceled/and so on).

SYS User Type

Type: Integer

Size: 0

Input Type (Input Method): Pull-down Menu

Use on: See **uuu_user_type** (on page 233).

Other DDs (in Alphabetical Order: U-Z)

Use the following Data Definitions (DDs), presented alphabetically, for creating the attribute forms, Business Processes, and other entities.

P6 DDs

Use the following data definitions for P6 integration.

P6 Activity Picker

Type: Integer

Size: 0

Input Type (Input Method): Picker (During runtime, the display Element for this picker will be "Activity ID")

Use on: The Data Elements (DEs) must be placed in a Shell Business Process, and the Activity Sheet must be located in the same Shell.

Description: To create number of Data Elements (DEs) that can pick activities from an Activity Sheet.

Note: You cannot place the DEs of type P6 Activity Picker in the Company-level Business Processes, Request for Bidder Business Process forms, Resource type Business Processes, and Project Creation BPs.

Category: System

SYS P6 Activity Constraint

Type: String

Size: 50

Input Type (Input Method): Pull-down Menu (Drop-down list)

Use on: The Data Elements (DEs) must be placed in a Shell Business Process, and the Activity Sheet must be located in the same Shell.

Description: To create DEs that map to Activity Constraint fields in P6.

The user cannot add new dataset values, edit, or remove the existing dataset values.

Category: System

Dataset:

- ▶ Start On
- ▶ Start On or Before
- ▶ Start On or After
- ▶ Finish On
- ▶ Finish On or Before
- ▶ Finish On or After
- ▶ As Late As Possible
- ▶ Mandatory Start
- ▶ Mandatory Finish

Default Value: None.

The user has the ability to set default to any value.

The user cannot add new dataset values, edit, or remove the existing dataset values.

SYS P6 Indicator

Type: String

Size: 50

Input Type (Input Method): Pull-down Menu (Drop-down list)

Use on:

Description: Pull-down Menu (Drop-down list) for creating DEs that map to P6 fields whose Data Definition = "Indicator"

Category: System

Dataset:

- ▶ Red
- ▶ Yellow
- ▶ Green
- ▶ Blue

Default Value: None.

The user has the ability to set default to any value.

The user cannot add new dataset values, edit, or remove the existing dataset values.

Additional information:

- ▶ The P6 application has a "Data Type" called "Indicator." Fields of type "Indicator" display as a color on the UI (Red, Yellow, Green, or Blue).
- ▶ Unifier Data Elements can map to P6 "Indicator" fields because of the Basic Pull-Down Data Definition.

SYS P6 Rate Source**Type:** String**Size:** 0**Input-Method:** Pulldown menu**Dataset:** Resource, Role, Override (Default value = None)**Use on:** Activity Sheet (Assignments)**Description:** Drop-down list to capture Rate source which will be used to calculate cost in Activity Assignments. End-user is not be allowed to:

- ▶ Add new dataset values
- ▶ Edit existing dataset values
- ▶ Update the default value

SYS P6 Resource Status**Type:** String**Size:** 0**Input-Method:** Pulldown menu**Dataset:** Active, Inactive (Default value = None)**Use on:** Rate Sheet (Resources)**Description:** Drop-down list to capture Resource status when it gets created/updated via P6 Integration. End user is not be allowed to:

- ▶ Add new dataset values
- ▶ Edit existing dataset values
- ▶ Update the default value

SYS P6 Role Status**Type:** String**Size:** 0**Input-Method:** Pulldown menu**Dataset:** Active, Inactive (Default value = None)**Use on:** Rate Sheet (Roles)

Description: Drop-down list to capture Role status when it gets created/updated via P6 Integration. End-user is not be allowed to:

- ▶ Add new dataset values
- ▶ Edit existing dataset values
- ▶ Update the default value

Earned Value Manager DDs

Use the following data definitions for creating the business processes and attribute forms for the **Earned Value Manager**.

SYS Rate Breakdown Type

Type: String

Size: 0

Input-Method: Pulldown menu

Dataset: Standard, External, Internal (default = Standard)

Use on: Rate Sheet

Description: Drop-down list to capture type of cost in rate sheet. End user should be allowed to:

- ▶ Add new dataset values,
- ▶ Edit existing dataset values,
- ▶ Update the default value

SYS Cost Breakdown Type

Type: String

Size: 0

Input-Method: Pulldown menu

Dataset: Direct, Indirect (default = Direct)

Use on: Rate Sheet

Description: Drop-down list to capture type of cost in rate sheet. End user should be allowed to:

- ▶ Add new dataset values,
- ▶ Edit existing dataset values,
- ▶ Update the default value

Data Elements (DEs)

This section contains the predefined Data Elements (DEs) you receive with the system.

To see the DEs, go to **Company Workspace > Admin mode > Data Structure Setup > Data Elements**.

The data elements are divided into topics for each manager, as well as a topic for global data elements that can be used for almost any Business Process (BP), or Attribute, form.

At the end of this section an alphabetical listing of all the data elements is provided.

Each topic includes descriptions of the data elements and where you can use them.

In addition to the data elements described here, you can create other data elements as you need them. For information on creating new data elements (DEs), refer to the *Unifier uDesigner User Guide*.

The following sections list the forms on which each element can be used.

Note: The following information includes the forms where data elements can be used. Using these definitions on forms not listed here can result in unexpected behavior in the system.

In This Section

Activity Sheet Manager.....	84
Asset Manager DEs	85
Configurable Shells DEs.....	90
Cost Manager DEs	91
Configurable Manager DEs	111
Document Manager DEs	113
Generic Cost Manager DEs.....	120
Global DEs	124
Lease Business Processes DEs.....	133
Index Rate Business Process DEs	144
Planning Manager DEs.....	145
Request for Bid (RFB) DEs	145
Resource Manager DEs	149
Schedule Manager DEs.....	162
Shell Manager DEs	188
Space Manager DEs	196
User Administration DEs	198
Bluebeam DEs	204
Other DEs (in Alphabetical Order: A-G).....	207
Other DEs (in Alphabetical Order: H-N).....	212
Other DEs (in Alphabetical Order: O-T).....	219
Other DEs (in Alphabetical Order: U-Z)	233
P6 DEs.....	233
Earned Value Manager DEs.....	254

Activity Sheet Manager

uuu_activity_constraint_type

Data Definition: Activity Constraint Type

Form Label (Field Label): Activity Constraint Type

of Characters:50

Where to use it: Activity Sheets and Business Processes

Use this element for: Showing the constraints available at the activity level.

uuu_activity_early_finish

Data Definition: Date Only Picker

Form Label (Field Label): Early Finish

of Characters: Not applicable

Where to use it: Activity Sheets and Business Processes

Use this element for: Capturing the early finish date of the activity for float calculation.

uuu_activity_early_start

Data Definition: Date Only Picker

Form Label (Field Label): Early Start

of Characters: Not applicable

Where to use it: Activity Sheets and Business Processes

Use this element for: Capturing the early start date of the activity for float calculation.

uuu_activity_late_start

Data Definition: Date Only Picker

Form Label (Field Label): Late Start

of Characters: Not applicable

Where to use it: Activity Sheets and Business Processes

Use this element for: Capturing the late start date of the activity for float calculation.

uuu_activity_late_finish

Data Definition: Date Only Picker

Form Label (Field Label): Late Finish

of Characters: Not applicable

Where to use it: Activity Sheets and Business Processes

Use this element for: Capturing the late finish date of the activity for float calculation.

uuu_activity_successor

Data Definition: SYS Description Text 2000

Form Label (Field Label): Successor

of Characters: 2000

Use this element for: Displaying the successor activities for the selected activity.

Asset Manager DEs

Use the following data elements for creating the Asset classes for the **Asset Manager**.

uuu_asset_acquisition_cost

Data Definition: Currency Amount

Form Label (Field Label): Asset Acquisition Cost

of Characters: 50

Where to use it: Detail form of an Asset class

Use this element for: Entering the acquisition cost of an asset.

This value will be used in depreciation calculations.

uuu_asset_acquisition_date

Data Definition: Date Picker

Form Label (Field Label): Asset Acquisition Date

of Characters: Not applicable

Where to Use it: Asset classes

Use this element for: Specifying the date the asset was acquired.

This value will be used in depreciation calculations.

uuu_asset_calc_as_of_date

Data Definition: Date Picker

Form Label (Field Label): Calculations as of

of Characters: Not applicable

Where to Use it: Asset classes

Use this element for: Displaying calculated depreciation as of the date picked.

This date is associated with cumulative and current-period depreciations and net book value calculations.

Unifier automatically updates this date, based on the current (system) time and the depreciation period.

uuu_asset_code

Data Definition: SYS Short Description Text 250

Form Label (Field Label): Asset Code

of Characters: 250

Where to Use it: Detail form of an Asset class

Use this element for: Entering an asset code for an asset.

The code is composed of segments, which, together, constitute the **asset structure**. Each segment can be used separately on a detail form of an Asset class so that users can create a unique code for any asset at runtime in Unifier. There should be at least one segment specified for the code.

uuu_asset_cum_depreciation

Data Definition: Currency Amount

Form Label (Field Label): Cumulative Depreciation

of Characters: 50

Where to Use it: Asset classes

Use this element for: Displaying the asset's cumulative depreciation amount with respect to the "calculation as of" date.

uuu_asset_curr_period_dep

Data Definition: Currency Amount

Form Label (Field Label): Current Period Depreciation

of Characters: 50

Where to Use it: Asset classes

Use this element for: Current Period Depreciation. Viewing the asset's amount of depreciation for the current period, as calculated by Unifier.

uuu_asset_depreciation_prd

Data Definition: Decimal Amount

Form Label (Field Label): Depreciation Period

of Characters: Not applicable

Where to Use it: Asset classes

Use this element for: Entering the number of years the asset should be depreciated. This value can only be expressed in years, up to 50.

uuu_asset_name

Data Definition: SYS Short Description Text 120

Form Label (Field Label): Asset Name

of Characters: 120

Where to Use it: Asset classes

Use this element for: Entering a name for an asset.

Note: Class names must be unique; otherwise, Unifier will not be able to select the correct class among the managers. The best way to avoid redundant class names is to preface the class name with the name of the manager it belongs to, such as “Asset—Heavy Equipment” to distinguish it from a configurable manager like “Inventory—Heavy Equipment.”

uuu_asset_navigation_code

Data Definition: SYS Short Description Text 250

Form Label (Field Label): Asset Navigation Code

of Characters: 250

Where to Use it: Detail form of an Asset class

Use this element for: Entering an asset navigation code to build a tree format for assets within an Asset class. This tree appears as an extra column in the log.

This data element can be built using one or more segments by using a string formula designed in uDesigner.

Note: You must use a string formula to create this field, and the formula must have a least 2 segments to create the tree hierarchy.

Each segment can be a data element that is placed on detail form of an Asset class.

Data elements that form the asset navigation code segments are not required and can be empty at runtime in Unifier.

uuu_asset_net_book_value

Data Definition: Currency Amount

Form Label (Field Label): Net Book Value

of Characters: 250

Where to Use it: Asset classes

Use this element for: Viewing the asset net book value, as calculated by Unifier.

uuu_asset_salvage_value

Data Definition: Currency Amount

Form Label (Field Label): Asset Salvage Value

of Characters: 50

Where to Use it: Asset classes

Use this element for: Entering the salvage value of an asset. This value will be used to calculate depreciation.

uuu_rsv_reservable

Data Definition: SYS_Yes_No

Form Label (Field Label): Allow Reservation

of Characters: Not applicable

Where to use it:

- ▶ Asset classes
- ▶ Configurable manager attribute forms
- ▶ Document type Business Processes
- ▶ Space detail form

Use this element for:

- ▶ Specifying that the asset can be reserved for use.
- ▶ Specifying that the object can be reserved for use.
- ▶ Specifying that the space can be reserved for use.

uuu_rsv_overbook

Data Definition: SYS_Overbooking_Options

Form Label (Field Label): Allow Overbooking

of Characters: Not applicable

Where to use it:

- ▶ Asset classes
- ▶ Configurable manager attribute forms

- Document type Business Processes
- Space detail form

Use this element for:

- Specifying that the asset can be overbooked on reservation.
- Specifying that the object can be overbooked on reservation.
- Specifying that the space can be overbooked on reservation.

There are three overbooking options:

- Even if confirmed booking exists
- Only if tentative booking exists
- No overbooking

Configurable Shells DEs

Use the following data elements for creating the forms for any Configurable Shells.

uuu_administrator

Data Definition: User Picker

Form Label (Field Label): Administrator

of Characters: Not applicable

Where to use it:

- Configurable shell attribute forms
- Shell attribute form
- Shell detail form
- Upper or detail form of a Project/Shell Creation BP

Note: Do not use this picker on configurable manager attribute forms.

Use this element for: Selecting the administrator of a shell.

uuu_location

Data Definition: Location Picker

Form Label (Field Label): Location

of Characters: Not applicable

Where to use it: Shell detail form; cannot be used on an anchor shell (a single-instance shell)

Note: Do not use this picker on configurable manager attribute forms.

Use this element for: Specifying the hierarchy between shells.

From this picker, the user picks the parent shell under which a sub-shell should be created.

This element will display the complete path location of the shell.

Cost Manager DEs

Use the following data elements for creating the forms and the business processes and attribute forms for the **Cost Manager**.

Account Code Attribute Forms DEs

Use the following data elements for creating the **Account Code Attribute Forms**.

uuu_company_account_code

Data Definition: SYS Short Description Text 250

Form Label (Field Label): Company Account Code

of Characters: 250

Where to Use it: Account Code Attribute forms

Use this element for: Building a company-level account structure to collect cost-related transactions generated by projects, assets, and company-level cost business processes.

Entering a definition for a company-level account code created in Unifier. Specifies company-level costs related to assets, resources, facility maintenance, and so on.

uuu_company_account_name

Data Definition: SYS Short Description Text 120

Form Label (Field Label): Company Account Name

of Characters: 120

Where to Use it: Account Code Attribute Form

Use this element for: Entering a name for a company account code.

Cost Attribute Forms DEs

Use the following data elements for creating the **Cost Attribute Forms**.

uuu_cost_cost_type

Data Definition: SYS Cost Type

Form Label (Field Label): Cost type

of Characters: 32

Where to Use it: Cost Attribute forms

Use this element for: Entering a cost code type (expense/capital)

uuu_cost_costattribute

Data Definition: Cost Attribute Picker

Form Label (Field Label): Cost Attribute

of Characters: 32

Where to Use it: Cost Attribute forms

Note: Do not use this picker on configurable manager attribute forms.

Use this element for: Entering cost attribute information. The data set for this element comes from the Cost Attribute data definition.

uuu_cost_description

Data Definition: SYS Description Text 500

Form Label (Field Label): Description

of Characters: 500

Where to Use it: Cost Attribute forms

Use this element for: 500

uuu_cost_external_refid

Data Definition: Short Description Text

Form Label (Field Label): External Ref. ID

of Characters: 120

Where to Use it: Cost Attribute forms

Use this element for: Entering an external reference number for a CBS code.

uuu_cost_exposed_to_p6

Data Definition: SYS Checkbox

Form Label (Field Label): Shared with External System

of Characters: Not applicable

Where to Use it: Cost attribute form

Use this element for: The integration interface to identify which CBS codes should be exposed to P6 Schedule Activities/Resources Assignments.

This DE is required if you are integrating CBS Codes with P6.

This DE helps to identify whether a CBS code should be exposed to P6 Schedule.

This is not a required DE for a Cost attribute form.

If you place this DE on a Cost attribute form, ensure that the DE is marked as Editable.

This element can be placed on any other form (a custom check box) and can be marked as Required or Read-only.

uuu_cost_imported_from_p6

Data Definition: SYS Checkbox

Form Label (Field Label): Imported from External System

of Characters: Not applicable

Where to Use it: Cost attribute form

Use this element for: Identifying which CBS Codes in the Cost Sheet are created via integration.

This DE is required if you are integrating CBS Codes with P6.

This DE helps to identify whether a code is integrated with P6 or manually created.

This is not a required DE for a Cost attribute form.

If you place this DE on a Cost attribute form, ensure that the DE is marked as Read-Only.

The value for this DE is populated via integration.

This element can be placed on any other form (a custom check box) and can be marked as Editable, Required, or Read-only.

uuu_cost_item

Data Definition: SYS Short Description Text 120

Form Label (Field Label): CBS Item

Note: WBS changes to CBS only for Labels and System Strings. For existing customers, by default, WBS does not change to CBS for the Data Structure Data Element labels such as "WBS code" and "WBS

item.”

of Characters: 120

Where to Use it: Cost Attribute forms

Use this element for: Entering description information about a CBS or cost code.

uuu_cost_owner

Data Definition: User Picker

Form Label (Field Label): Owner

of Characters: Not applicable

Where to Use it: Cost Attribute forms

Use this element for: Specifying the owner of a cost code and displaying the owner's user information. At runtime, this element shows a list of project users.

uuu_cost_status

Data Definition: SYS Cost Status

Form Label (Field Label): Status

of Characters: 50

Where to Use it: Cost Attribute forms

Use this element for: Entering the status of a CBS code (active/inactive).

Fund Attribute Forms DEs

Use the following data elements for creating the **Fund Attribute Forms**.

row_id

Data Definition: Fund Picker

Form Label (Field Label): Funding Source

of Characters: Not applicable

Where to Use it:

- ▶ Fund Attribute forms
- ▶ Detail form of cost type business processes of sub-type:
 - ▶ Line Items with Fund Code
 - ▶ Line Items with Both CBS and Fund Codes

Note: Do not use this picker on configurable manager attribute forms.

Use this element for: Selecting a fund code.

The element shows active company-level fund codes.

If a Fund Attribute form has not been created in uDesigner, the system will define the layout of the data element.

If you create a Fund Attribute form, you can configure your own layout based on the attributes added to the form.

uuu_fund_code

Data Definition: SYS Short Description Text 250

Form Label (Field Label): Fund Code

of Characters: 250

Where to Use it: Fund Attribute Forms

Use this element for: Entering a fund code. This is a system-defined data element.

uuu_fund_description

Data Definition: SYS Short Description Text 120

Form Label (Field Label): Fund Description

of Characters: 120

Where to use it: Fund Attribute Forms

Use this element for: Entering additional information about a fund.

uuu_fund_fundcategory

Data Definition: Funding Category

Form Label (Field Label): Fund Category

of Characters: 100

Where to Use it: Fund Attribute Forms

Use this element for: Entering the category of a fund. The data set for this field is specified in the system.

uuu_fund_fundname

Data Definition: SYS Short Description Text 120

Form Label (Field Label): Fund Name

of Characters: 120

Where to Use it: Fund Attribute Forms

Use this element for: Entering the name of the fund.

uuu_fund_long_desc

Data Definition: SYS Long Description Text 2000

Form Label (Field Label): Fund Long Description

of Characters: 2000

Where to use it: Fund Attribute Forms

Use this element for: Entering additional information about a fund.

Cost Business Processes DEs

Use the following data elements for creating the **Cost Business Processes** forms.

bitemID

Data Definition: CBS Picker

Form Label (Field Label): CBS Code

of Characters: Not applicable

Where to Use it:

- ▶ Upper form of any business process in a project or shell, except an RFB bidder BP.
- ▶ Detail form of:
 - ▶ Line Items with CBS Code types of cost BPs
 - ▶ Line Items with Both CBS Code and Fund Code types of cost BPs
 - ▶ Commit at Company Level cost BPS
 - ▶ RFBs

Note: Do not use this picker on configurable manager attribute forms.

Use this element for: Selecting a CBS code. The codes the user can choose from depend on the CBS codes defined on the cost sheet of the project.

When placed on an upper form, note the following behaviors:

This element is typically placed on an upper form for the purpose of auto-creating line items on a cost business process using a BP Line Item Creator. When used in this case, the picker will populate the CBS code field on the line item being created.

It will **not** roll up values to the Cost Sheet.

The user will be able to remove the CBS code from the picker, if it is editable. When this happens, any field values that were auto-populated from the CBS attribute form will be reset.

If the user copies a record containing a CBS picker that has been marked “inactive,” the code will still be copied.

If the user copies a record containing a CBS picker that has been deleted from the Cost Sheet, the picker will appear blank on the created record.

The picker cannot be auto-populated or reverse-auto-populated; however, it can be reset or used as a trigger element for a query-based data element.

The picker can be included as an element in the behavior set of a dynamic data set, but not in the value set.

This element is not supported in generic shells, as generic shells cannot use CBS codes.

The picker is available for bulk edits and bulk actions.

currencyid

Data Definition: Currency Picker

Form Label (Field Label):

- ▶ “Transaction Currency” on business processes
- ▶ “Resource Currency” on Resource attribute forms

of Characters: Not applicable

Where to Use it:

- ▶ Upper form of Cost business processes
- ▶ Resource attribute forms

Use this element for: Selecting the currency on a Cost-type BP or on a Resource attribute form.

If the user does not choose a currency, or if you do not include a currency picker on the form, the default is the project currency. The system populates this picker with the currencies in the database.

Note: Do not use this picker on configurable manager attribute forms.

currencyrate

Data Definition: Float

Form Label (Field Label): Rate in Project Currency

of Characters: Not applicable

Where to Use it:

- ▶ Upper forms of Cost BPs in CBS and generic shells.
- ▶ Can be used for:
 - ▶ Formulas
 - ▶ Email notifications
 - ▶ Unifier on mobile
 - ▶ Data cubes
 - ▶ Data views

Use this element for: Use this element to compute the project currency rate, based on the transaction currency and the current exchange rate. The resulting field will be read-only.

The system uses this exchange rate for computing project currency amounts.

Example

A multinational company might create purchase orders in different currencies, Euro, US\$, and Chilean Pesos. The company has an approval matrix based on the Euro, so the currency amount of each PO must be converted to Euro.

This element will reflect the locked exchange rate based on the selected transaction currency when the record is created and sent (for a workflow BP) or edited and completed (non-workflow BP) for the first time.

ref_bpo

Data Definition: BP Picker

Form Label (Field Label): Reference BPO

of Characters: Not applicable

Where to use it: Upper form of a commit or change commit type of business process to refer to a commit at the company level, or a blanket purchase order.

Use only on a project-level business process.

Note: Do not use this picker on configurable manager attribute forms.

Use this element for: Referencing a “Commit at Company Level,” or “Blanket PO” business process.

A business process can have only one data element of this type.

Picker works in conjunction with the reference process created as part of a business process definition in uDesigner.

ref_bpo_lineitem

Data Definition: BP Line Item Picker

Form Label (Field Label): Reference BPO Line Item

of Characters: Not applicable

Where to use it: Detail form of a Line Items with CBS Code type or Commit at Company Level type Commit or Change Commit of business process.

Notes:

- Do not use this picker on configurable manager attribute forms.
- You cannot use a BP Line Item Picker in an Activity Attribute Form.

Use this element for: Referencing line items of “Commit at Company Level” or “Blanket PO” business processes.

A business process detail form can have only one data element of this type.

Picker works in conjunction with the Reference BPO picker on the upper form of the business process.

refid

Data Definition: BP Picker

Form Label (Field Label): Reference Commit

of Characters: Not applicable

Where to Use it: Upper form of any Change Order, Spends, Payment Applications, or Summary Payment Applications Business Processes (BPs) to refer to the base commit.

Used in either the standard or generic Cost Managers.

Note: Do not use this picker on configurable manager attribute forms.

Use this element for: Referencing a “Base Commits” Business Process (BP).

A BP can have only one data element of this type on the upper form.

Picker works in conjunction with the Reference Process created as part of a business process definition in uDesigner.

row_id

Data Definition: Fund Picker

Form Label (Field Label): Funding Source

of Characters: Not applicable

Where to Use it:

- ▶ Fund Attribute forms
- ▶ Detail form of cost type business processes of sub-type:
 - ▶ Line Items with Fund Code
 - ▶ Line Items with Both CBS and Fund Codes

Note: Do not use this picker on configurable manager attribute forms.

Use this element for: Selecting a fund code.

The element shows active company-level fund codes.

If a Fund Attribute form has not been created in uDesigner, the system will define the layout of the data element.

If you create a Fund Attribute form, you can configure your own layout based on the attributes added to the form.

scheduled_value

Data Definition: Currency Amount

Form Label (Field Label): Scheduled Value

of Characters: 50

Where to use it:

- ▶ Detail form of Commit at Company level type Payment Applications or Summary Payment Applications Business Processes (BPs).
- ▶ Detail form of Generic Cost Manager Payment Applications or Summary Payment Applications Business Processes (BPs).

Use this element for: Viewing the sum total of the contract (“Base Commits” + “Change Commits”) against a line item.

Note: This is a system-defined element.

usd_currencyrate

Data Definition: Float

Form Label (Field Label): Rate in Base Currency

of Characters: Not applicable

Where to Use it:

- ▶ Upper forms of Cost BPs in CBS and generic shells.
- ▶ Can be used for:
 - ▶ Formulas
 - ▶ Email notifications
 - ▶ Unifier on mobile
 - ▶ Data cubes
 - ▶ Data views

Use this element for: Displaying the converted currency rate (as a read-only field).

The system uses this element to compute the base currency rate based on the transaction currency and the current exchange rate.

Example

A multinational company might create purchase orders in different currencies, Euro, US\$, and Chilean Pesos. The company has an approval matrix based on the Euro, so the currency amount of each PO must be converted to Euro.

uuu_asset_picker

Data Definition: Asset Picker

Form Label (Field Label): Asset Picker

of Characters: Not applicable

Where to Use it:

Detail form a company-level cost type business processes of sub-type Line Item with Asset Code.

Detail form a company-level commit type business processes of sub-type Line Item with Asset Code.

Note: Do not use this picker on configurable manager attribute forms.

Use this element for: Selecting an asset for a project. The assets listed will be filtered to include only those assets that are at a specific status or statuses.

uuu_base_rate_override

Data Definition: Float

Form Label (Field Label): Base Currency Rate Override

of Characters: Not applicable

Where to Use it: Upper form of any cost BP

Note: Not available for company-level BPs

Use this element for: Overriding the base currency exchange rate when creating a cost transaction.

To accommodate this rate override, the BP must also contain a Currency Picker.

The user can override the exchange rate only on the Creation step of a business process, or before clicking “Finished Editing” on a non-workflow business process.

If the user overrides the exchange rate, the override value will become the currency exchange rate and will be copied to the existing currency exchange rate fields on the form.

Because the exchange rate must be overridden on the Creation step only, this element cannot be auto-populated.

For integration, you can specify a direction of Input, Output, or Both. These directions will be used only when the business process is created; otherwise, they will be ignored.

uuu_before_after

Data Definition: SYS_Before_After

Form Label (Field Label): Before/After

of Characters: Not applicable

Where to Use it: Upper or detail form of Reservation BPs that auto-create new BPs.

Use this element for: Selecting when a BP should be auto-created, relative to the event (before or after).

This element works in conjunction with these elements to specify the days/hours/minutes before or after the event:

- ▶ **uuu_rsv_trigger_date**
- ▶ **uuu_rsv_trigger_days**
- ▶ **uuu_rsv_trigger_hrs**
- ▶ **uuu_rsv_trigger_min**

Note: Unifier will automatically add these elements to the design if it was omitted on the Reservation form.

uuu_calendar_item_name

Data Definition: SYS Short Description Text 250

Form Label (Field Label): Reservation Name

of Characters: 250

Where to Use it: Upper form of a Reservation BP

Use this element for: Entering the name of the reservation on a Reservation type BP.

uuu_cancellation_notes

Data Definition: SYS Description Text 500

Form Label (Field Label): Cancellation

of Characters: 500

Where to Use it: Upper form of a Reservation BP

Use this element for: Entering optional notes about a cancellation.

uuu_cancelled

Data Definition: SYS_Yes_No

Form Label (Field Label): Yes/No

of Characters: Not applicable

Where to Use it: Upper form of a Reservation BP

Use this element for: Specifying that a reservation is or is not canceled.

uuu_commit_breakdown

Data Definition: SYS Short Description Text 120

Form Label (Field Label): Breakdown

of Characters: 120

Where to Use it: Detail form of a Payment Applications or Summary Payment Applications Business Process (BP)

Use this element for: Viewing the breakdown name that was defined in the Schedule of Values sheet for a line item (CBS Code).

uuu_commit_short_desc

Data Definition: SYS Short Description Text

Form Label (Field Label): Commit Short Description

of Characters: 120

Where to Use it: Detail form of a Payment Applications or Summary Payment Applications Business Process (BP)

Use this element for: Viewing description information that was entered on Base Commit and Change Commit line items.

uuu_commit_remaining_balance

Data Definition: Currency Amount

Form Label (Field Label): Remaining Balance

of Characters: Not applicable.

Where to Use it: Detail form of a Payment Applications or Summary Payment Applications Business Process (BP)

uuu_company_acc_codepicker

Data Definition: Account Code Picker

Form Label (Field Label): Account Code Picker

of Characters: Not applicable

Where to Use it: Detail form of cost business processes of sub-type Line Items with Company Account Code

Note: Do not use this picker on configurable manager attribute forms.

Use this element for: Selecting account codes created at runtime in Unifier. The element shows a list of active account codes from a company-level accounting sheet.

uuu_cost_code

Data Definition: CBS Code Picker

Form Label (Field Label): CBS Code

Note: WBS changes to CBS only for Labels and System Strings. For existing customers, by default, WBS does not change to CBS for the Data Structure Data Element labels such as "WBS code" and "WBS item."

of Characters: 32

Where to Use it: Cost Manager attribute form

Use this element for: Selecting a CBS code that has been defined on a Project Cost Sheet.

This element is based on the CBS Picker data definition.

The picker will show only active CBS codes.

If the element was designed in uDesigner, or system-defined in Unifier, Unifier determines how to display CBS codes based on Cost Sheet properties and the Cost Attribute form.

uuu_effective_date

Data Definition: Date Picker

Form Label (Field Label): Effective Date

of Characters: Not applicable

Where to use it:

- ▶ Detail form of cost type business processes.
- ▶ Detail forms of Generic Cost Manager business process of types:
 - ▶ Base Commit
 - ▶ Change Commit
 - ▶ Spends

Use this element for: Selecting an effective date for a line item on a cost BP.

This element is useful when the user wants to generate a cash flow curve based on the business process record and line items.

The line items and the costs associated with them will be placed in the appropriate time period based on the date picked with this element.

uuu_from_date

Data Definition: Date Picker

Form Label (Field Label): From Date

of Characters: Not applicable

Where to use it:

- ▶ Upper form of a Reservation business process
- ▶ Resource Booking business process

Use this element for: Entering the time-frame for a reserved object, for example, the time-frame for resource that is being booked.

uuu_fund_description

Data Definition: SYS Short Description Text 120

Form Label (Field Label): Fund Description

of Characters: 120

Where to use it: Fund Attribute Forms

Use this element for: Entering additional information about a fund.

uuu_fund_fundcategory

Data Definition: Funding Category

Form Label (Field Label): Fund Category

of Characters: 100

Where to Use it: Fund Attribute Forms

Use this element for: Entering the category of a fund. The data set for this field is specified in the system.

uuu_fund_fundname

Data Definition: SYS Short Description Text 120

Form Label (Field Label): Fund Name

of Characters: 120

Where to Use it: Fund Attribute Forms

Use this element for: Entering the name of the fund.

uuu_fund_long_desc

Data Definition: SYS Long Description Text 2000

Form Label (Field Label): Fund Long Description

of Characters: 2000

Where to use it: Fund Attribute Forms

Use this element for: Entering additional information about a fund.

uuu_project_rate_override

Data Definition: Float

Form Label (Field Label): Project Currency Rate Override

of Characters: Not applicable

Where to use it: Upper form of any cost BP

Note: Not available for company-level BPs.

Use this element for: Overriding the project currency exchange rate when creating a cost transaction.

To accommodate this rate override, the BP must also contain a Currency Picker.

The user can override the exchange rate only on the Creation step of a business process, or before clicking “Finished Editing” on a non-workflow business process.

If the user overrides the rate, the override value will become the currency exchange rate and will be copied to the existing currency exchange rate fields on the form.

Because the rate must be overridden on the Creation step only, this element cannot be auto-populated.

For integration, you can specify a direction of Input, Output, or Both. These directions will be used only when the business process is created; otherwise, they will be ignored.

uuu_recurrence

Data Definition: SYS Short Description Text

Form Label (Field Label): Recurrence

of Characters: 250

Where to use it: Upper form of Reservation BPs

Use this element for: Specifying how often a reservation should be automatically created.

When this element is included on the BP form, it is read-only and the Unifier user populates it by using the **Recurrence** button on the toolbar.

uuu_rsv_trigger_date

Data Definition: Date Picker

Form Label (Field Label): Trigger Date

of Characters: Not applicable

Where to use it: Upper or detail form of Reservation BPs that auto-create new BPs

Use this element for: Entering the date a new BP should be created.

Note: Unifier will automatically add this element to the design if it was omitted on the Reservation form.

uuu_rsv_trigger_days

Data Definition: Integer Amount

Form Label (Field Label): Time (Days)

of Characters: Not applicable

Where to use it: Upper or detail form of Reservation BPs that auto-create new BPs

Use this element for: Entering the number of days before or after the event that the BP should be auto-created.

This element works in conjunction with the **uuu_before_after** element to specify the days before or after the event.

Note: Unifier will automatically add this element to the design if it was omitted on the Reservation form.

uuu_rsv_trigger_hrs

Data Definition: Integer Amount

Form Label (Field Label): Time (Hrs)

of Characters: Not applicable

Where to use it: Upper or detail form of Reservation BPs that auto-create new BPs

Use this element for: Entering the number of hours before or after the event that the BP should be auto-created.

This element works in conjunction with the **uuu_before_after** element to specify the hours before or after the event.

Note: Unifier will automatically add this element to the design if it was omitted on the Reservation form.

uuu_rsv_trigger_mins

Data Definition: Integer Amount

Form Label (Field Label): Time (Min)

of Characters: Not applicable

Where to use it: Upper or detail form of Reservation BPs that auto-create new BPs

Use this element for: Entering the number of minutes before or after the event that the BP should be auto-created.

This element works in conjunction with the **uuu_before_after** element to specify the minutes before or after the event.

Note: Unifier will automatically add this element to the design if it was omitted on the Reservation form.

uuu_sovlinum

Data Definition: Commit Line Item Picker

Form Label (Field Label): Reference

of Characters: Not applicable

Where to use it:

- ▶ Detail form of Change Commit business processes (BPs) with all Schedule of Values (SOV) Types (General Spends, Payment Applications, and Summary Payment Applications) of Individual commit line items.
- ▶ Detail form of Generic Cost Manager BP of type Change Commit with “Commitments Summary” type individual line items.

Note: Do not use this picker on configurable manager attribute forms.

Use this element for:

- ▶ Selecting line items from the SOV for a Change Commit BP.
- ▶ Selecting line items from the Commitment Summary for a Change Commit BP for Generic Cost Manager.

This element works in conjunction with the:

- ▶ CBS picker that you specify on the detail form of a Change Commit BP.
- ▶ Generic cost code picker that you specify on the detail form of a Change Commit BP.

This element is applicable only if the Base Commit BP SOV line item type was defined as “Individual Commit Line Items.”

Note: In the Change Commit BP, this DE cannot be used to define any type of query conditions on the line items.

uuu_scheduled_value

Data Definition: Currency Amount

Form Label (Field Label): Remaining Balance

of Characters: Not applicable.

Where to Use it: Detail form of a Payment Applications or Summary Payment Applications Business Process (BP)

Use this element for selecting line items from the schedule of values (SOV) for Base commit BPs and change commit BPs.

uuu_to_date

Data Definition: Date Picker

Form Label (Field Label): To Date

of Characters: Not applicable

Where to use it:

- ▶ Upper form of Reservation BPs
- ▶ Resource Booking business processes

Use this element for:

- ▶ Entering the time frame for a reserved object.
- ▶ Entering the time frame for which a resource is being booked.

uuu_unit_cost_contract

Data Definition: SYS Check Box

Form Label (Field Label): Unit Cost Contract

of Characters: Not applicable

Where to use it: Upper Form of the Base Commit business process (Company-level type Base Commit business process) with Payment Application SOVs and SOV line items of **Individual Commit Line Items** type.

Use this element for: Specifying whether or not the system should freeze and copy unit price information onto a Change Commit or payment application.

This check box works in conjunction with the **uuu_unit_price** and **uuu_quantity** data elements.

uuu_unit_price

Data Definition: Currency Amount

Form Label (Field Label): Item Unit Cost

of Characters: 50

Where to use it: Detail form of Commit at Company level of Base Commits Business Processes: Payment Applications or Summary Payment Applications SOV sheets.

Use this element for: Enter the unit cost of a line item. This data element works in conjunction with the **uuu_unit_cost_contract** and **uuu_quantity** data elements.

wpid

Data Definition: Work Package Picker

Form Label (Field Label): Work Package

of Characters: Not applicable

Where to use it: Detail form of any cost business process

Note: Do not use this picker on configurable manager attribute forms.

Use this element for: Selecting a work package while creating a line item.

If the user specifies a work package for a Base Commit, the system will also tie that package to the PayApp, General Spends, and Change Commit records associated with that Base Commit.

If the user is using CSV or Web Services, this data element must be present in both the detail form and the integration form in order for the system to make the work package connection between the Base Commit and the other business processes.

Configurable Manager DEs

Use the following data elements for creating the forms for any **Configurable Manager**.

uuu_cm[1...25]_code

Data Definition: SYS Short Description Text 120

Form Label (Field Label): Code

of Characters: 120

Where to Use it: Configurable manager attribute forms

Use this element for: Entering a code for the manager to use on the sheet. Can be alphanumeric.

uuu_cm[1...25]_name

Data Definition: SYS Short Description Text 120

Form Label (Field Label): Name

of Characters: 120

Where to Use it: Configurable manager attribute forms

Note: Do not use this field as part of a **uuu_cm[0...25]_code** code.

Use this element for: Specifying a name for a code. Can be alphanumeric.

uuu_cm[1...25]_status

Data Definition: SYS Short Description Text 120

Form Label (Field Label): Status

of Characters: 120

Where to Use it: Configurable manager attribute forms

Use this element for: Specifying a status for a code. Can be alphanumeric.

uuu_code_navigation_code

Data Definition: SYS Short Description Text 250

Form Label (Field Label): Navigation Code

of Characters: 250

Where to Use it: Detail form of a Code and Records-based manager

Use this element for: Entering a code navigation code to build a tree format for items within a class. This tree appears as an extra column in the log.

This data element can be built using one or more segments by using a string formula designed in uDesigner. Each segment can be a data element that is placed on the detail form of a class. Data elements that form the navigation code segments are not required and can be empty at runtime in Unifier.

uuu_cm[1...25]_picker

Data Definition: CM[1...25] Picker

Form Label (Field Label): [manager name] Picker

of Characters: Not applicable

Where to Use it: Detail forms of Cost BPs and Line Item BPs, including any detail form for a tab on multiple-tab BPs of these types

Note: Do not use this picker on configurable manager attribute forms.

Use this element for: Selecting a code or record from a configurable manager.

The code picker is created automatically when the manager is created.

The picker auto-populates elements from the manager record onto BP forms.

Note: A code picker from a company-level manager cannot be placed on a BP at Project/Shell level and vice versa.

uuu_rsv_overbook

Data Definition: SYS_Overbooking_Options

Form Label (Field Label): Allow Overbooking

of Characters: Not applicable

Where to use it:

- Asset classes
- Configurable manager attribute forms
- Document type Business Processes
- Space detail form

Use this element for:

- Specifying that the asset can be overbooked on reservation.
- Specifying that the object can be overbooked on reservation.
- Specifying that the space can be overbooked on reservation.

There are three overbooking options:

- Even if confirmed booking exists
- Only if tentative booking exists
- No overbooking

uuu_rsv_reservable

Data Definition: SYS_Yes_No

Form Label (Field Label): Allow Reservation

of Characters: Not applicable

Where to use it:

- Asset classes
- Configurable manager attribute forms
- Document type Business Processes
- Space detail form

Use this element for:

- Specifying that the asset can be reserved for use.
- Specifying that the object can be reserved for use.
- Specifying that the space can be reserved for use.

Document Manager DEs

Use the following data elements for creating the business processes and attribute forms for the **Document Manager**.

uuu_dm_create_by

Data Definition: User Picker

Form Label (Field Label): Owner

of Characters: Not applicable

Where to use it:

- ▶ Document Folder Attribute Forms
- ▶ Document Attribute Forms
- ▶ Document business processes

Use this element for: Specifying the owner of a folder or document and displaying the user information.

uuu_dm_create_date

Data Definition: Date Picker

Form Label (Field Label): Creation Date

of Characters: Not applicable

Where to use it:

- ▶ Document Folder Attribute Forms
- ▶ Document Attribute Forms
- ▶ Document business processes

Use this element for: Entering the date and time a folder was created.

uuu_dm_description

Data Definition: SYS Short Description Text 250

Form Label (Field Label): Description

of Characters: 250

Where to use it:

- ▶ Document Folder Attribute Forms
- ▶ Document Attribute Forms
- ▶ Document business processes

Use this element for: Entering a description of a document or folder.

uuu_dm_node_name

Data Definition: SYS Short Description Text 250

Form Label (Field Label): Name

of Characters: 250

Where to use it:

- ▶ Document Folder Attribute Forms
- ▶ Document Attribute Forms

- ▶ Document business processes

Use this element for: Entering a folder or document name.

uuu_dm_node_path

Data Definition: SYS Long Description Text

Form Label (Field Label): Location

of Characters: 4000

Where to use it:

- ▶ Document Folder Attribute Forms
- ▶ Document Attribute Forms
- ▶ Document business processes

Use this element for: Entering the location of a folder or document with respect to the project documents folder (root node) in the Document Manager.

uuu_dm_percent_complete

Data Definition: Integer Amount

Form Label (Field Label): % Complete

of Characters: Not applicable

Where to use it:

- ▶ Document Folder Attribute Forms
- ▶ Document Attribute Forms
- ▶ Document business processes

Use this element for: Entering the percent complete for a folder or document.

uuu_doc_attribute_url

Data Definition: SYS Short Description Text 250

Form Label (Field Label): Document URL

of Characters: 250

Where to use it: On the Document Attribute form

Use this element for: Displaying a document URL. When this element is added to the document attribute form, all documents, including empty documents, display a URL after document creation. The document URL can be used to view a document from your browser.

This is a read-only data element and can also be used in the Document Log.

uuu_file_create_by

Data Definition: User Picker

Form Label (Field Label): Upload By

of Characters: Not applicable

Where to use it:

- ▶ Document Folder Attribute Forms
- ▶ Document Attribute Forms
- ▶ Document business processes

Use this element for: Specifying the name of the person who uploaded a document.

uuu_file_create_date

Data Definition: Date Picker

Form Label (Field Label): Upload Date

of Characters: Not applicable

Where to use it:

- ▶ Document Folder Attribute Forms
- ▶ Document Attribute Forms
- ▶ Document business processes

Use this element for: Entering the date and time a document was created.

uuu_file_issue_date

Data Definition: Date Picker

Form Label (Field Label): Issue Date

of Characters: Not applicable

Where to use it:

- ▶ Document Folder Attribute Forms
- ▶ Document Attribute Forms

Use this element for: Entering the date that a document was issued.

uuu_file_revision_no

Data Definition: SYS Short Description Text 250

Form Label (Field Label): Revision No.

of Characters: 250

Where to use it:

- ▶ Document Folder Attribute Forms
- ▶ Document Attribute Forms
- ▶ Document business processes

Use this element for: Entering the revision number of a document. You can use this as a place holder.

uuu_file_size

Data Definition: Integer Amount

Form Label (Field Label): Size

of Characters: Not applicable

Where to use it:

- ▶ Document Folder Attribute Forms
- ▶ Document Attribute Forms
- ▶ Document business processes

Use this element for: Displaying the size, in bytes, of a document. (The system automatically calculates this amount.)

uuu_file_title

Data Definition: SYS Short Description Text 250

Form Label (Field Label): Title

of Characters: 250

Where to use it:

- ▶ Document Folder Attribute Forms
- ▶ Document Attribute Forms
- ▶ Document business processes

Use this element for: Entering a title for a document (rather than use the file name as the title).

uuu_file_version

Data Definition: Integer Amount

Form Label (Field Label): Pub No.

of Characters: Not applicable

Where to use it:

- ▶ Document Folder Attribute Forms
- ▶ Document Attribute Forms
- ▶ Document business processes

Use this element for: Displaying the version number of a document. (The system automatically updates this number whenever the document is revised.)

uuu_issue_date

Data Definition: Date Picker

Form Label (Field Label): Issue Date

of Characters: Not applicable

Where to use it: Detail form of document business processes

Use this element for: Selecting the issue date of a document that is attached to a line item.

uuu_line_item_status

Data Definition: Designer Line Item Status

Form Label (Field Label): Line Item Status

of Characters: 128

Where to use it: Detail form of:

- ▶ Document business processes
- ▶ Line item type business processes

Use this element for: Selectively modifying line item information on a workflow step.

uuu_li_last_update_date

Data Definition: Date Picker

Form Label (Field Label): Line Item Last Update Date

of Characters: Not Applicable

Where to use it: Detail Forms of any Business Process. Can be placed in any of the line item tabs.

Use this element for: To capture the date and time that the line item was either created or updated.

Additional features:

- ▶ Default Behavior: Read Only
- ▶ This is an optional field that may or may not exist on the form. No error-check specific to this DE is needed.
- ▶ Cannot be marked as Editable or Editable Required
- ▶ Because this DE is Read-Only in the line items, it cannot be part of DDS
- ▶ Remaining behavior will be the same as the "uuu_record_last_update_date"
- ▶ This DE will not be allowed to be added anywhere other than in the detail form of the line-item BPs

- ▶ This DE cannot be placed in the bidder's form of Request for Bid type of BP

uuu_name

Data Definition: SYS Short Description Text 250

Form Label (Field Label): Name

of Characters: 250

Where to use it: Detail form of document business processes

Use this element for: Entering a file name.

uuu_rsv_overbook

Data Definition: SYS_Overbooking_Options

Form Label (Field Label): Allow Overbooking

of Characters: Not applicable

Where to use it:

- ▶ Asset classes
- ▶ Configurable manager attribute forms
- ▶ Document type Business Processes
- ▶ Space detail form

Use this element for:

- ▶ Specifying that the asset can be overbooked on reservation.
- ▶ Specifying that the object can be overbooked on reservation.
- ▶ Specifying that the space can be overbooked on reservation.

There are three overbooking options:

- ▶ Even if confirmed booking exists
- ▶ Only if tentative booking exists
- ▶ No overbooking

uuu_rsv_reservable

Data Definition: SYS_Yes_No

Form Label (Field Label): Allow Reservation

of Characters: Not applicable

Where to use it:

- ▶ Asset classes
- ▶ Configurable manager attribute forms
- ▶ Document type Business Processes
- ▶ Space detail form

Use this element for:

- ▶ Specifying that the asset can be reserved for use.
- ▶ Specifying that the object can be reserved for use.
- ▶ Specifying that the space can be reserved for use.

uuu_revision_no

Data Definition: SYS Short Description Text 250

Form Label (Field Label): Revision No.

of Characters: 250

Where to use it: Detail form of document business processes

Use this element for: Entering the revision number of a document.

uuu_title

Data Definition: SYS Short Description Text 250

Form Label (Field Label): Title

of Characters: 250

Where to use it: Detail form of document business processes

Note: This title will not appear in the “view reference records” feature. If you want the title to appear in this feature, use the system-defined “title” element instead.

Use this element for: Entering the title of a file.

Generic Cost Manager DEs

Use the following data elements for creating the forms and the business processes and attribute forms for the **Generic Cost Manager**.

uuu_cm0_code

Data Definition: Generic Cost Code Picker

Form Label (Field Label): Cost Code

of Characters: Not applicable

Where to use it:

- ▶ Generic Cost Manager Attribute Form
- ▶ Generic Cost Manager business processes

► RFB detail forms

Note: Do not use this element on a Shell or configurable manager attribute forms.

Use this element for: Defining a cost code for a generic cost manager at runtime in Unifier.

The picker will show only active codes.

Unifier determines how to display codes based on the Generic Cost Manager Attribute form.

uuu_cm0_name

Data Definition: SYS Short Description Text 120

Form Label (Field Label): Code Name

of Characters: 120

Where to use it: Generic Cost Manager Attribute Form

Use this element for: Assigning a name to a cost code for a Generic Cost Manager.

uuu_cm0_status

Data Definition: SYS Cost Status

Form Label (Field Label): Status

of Characters: 20

Where to use it: Generic Cost Manager Attribute Form

Use this element for: Specifying the status (active or inactive) of a cost code for a Generic Cost Manager.

uuu_effective_date

Data Definition: Date Picker

Form Label (Field Label): Effective Date

of Characters: Not applicable

Where to use it:

- Detail form of cost type business processes.
- Detail forms of Generic Cost Manager business process of types:
 - Base Commit
 - Change Commit
 - Spends

Use this element for: Selecting an effective date for a line item on a cost BP.

This element is useful when the user wants to generate a cash flow curve based on the business process record and line items.

The line items and the costs associated with them will be placed in the appropriate time period based on the date picked with this element.

ref_bpo

Data Definition: BP Picker

Form Label (Field Label): Reference BPO

of Characters: Not applicable

Where to use it: Upper form of a commit or change commit type of business process to refer to a commit at the company level, or a blanket purchase order.

Use only on a project-level business process.

Note: Do not use this picker on configurable manager attribute forms.

Use this element for: Referencing a “Commit at Company Level,” or “Blanket PO” business process.

A business process can have only one data element of this type.

Picker works in conjunction with the reference process created as part of a business process definition in uDesigner.

ref_bpo_lineitem

Data Definition: BP Line Item Picker

Form Label (Field Label): Reference BPO Line Item

of Characters: Not applicable

Where to use it: Detail form of a Line Items with CBS Code type or Commit at Company Level type Commit or Change Commit of business process.

Notes:

- Do not use this picker on configurable manager attribute forms.
 - You cannot use a BP Line Item Picker in an Activity Attribute Form.
-

Use this element for: Referencing line items of “Commit at Company Level” or “Blanket PO” business processes.

A business process detail form can have only one data element of this type.

Picker works in conjunction with the Reference BPO picker on the upper form of the business process.

scheduled_value

Data Definition: Currency Amount

Form Label (Field Label): Scheduled Value

of Characters: 50

Where to use it:

- ▶ Detail form of Commit at Company level type Payment Applications or Summary Payment Applications Business Processes (BPs).
- ▶ Detail form of Generic Cost Manager Payment Applications or Summary Payment Applications Business Processes (BPs).

Use this element for: Viewing the sum total of the contract (“Base Commits” + “Change Commits”) against a line item.

Note: This is a system-defined element.

uuu_sovlinum

Data Definition: Commit Line Item Picker

Form Label (Field Label): Reference

of Characters: Not applicable

Where to use it:

- ▶ Detail form of Change Commit business processes (BPs) with all Schedule of Values (SOV) Types (General Spends, Payment Applications, and Summary Payment Applications) of Individual commit line items.

- ▶ Detail form of Generic Cost Manager BP of type Change Commit with “Commitments Summary” type individual line items.

Note: Do not use this picker on configurable manager attribute forms.

Use this element for:

- ▶ Selecting line items from the SOV for a Change Commit BP.
- ▶ Selecting line items from the Commitment Summary for a Change Commit BP for Generic Cost Manager.

This element works in conjunction with the:

- ▶ CBS picker that you specify on the detail form of a Change Commit BP.
- ▶ Generic cost code picker that you specify on the detail form of a Change Commit BP.

This element is applicable only if the Base Commit BP SOV line item type was defined as “Individual Commit Line Items.”

Note: In the Change Commit BP, this DE cannot be used to define any type of query conditions on the line items.

Global DEs

Use the following data elements for creating most business processes and attribute forms.

amount

Data Definition: Currency Amount

Form Label (Field Label): Amount

of Characters: Not applicable

Where to use it:

- ▶ Any formula calculation on any business process
- ▶ Any cost business process at company or project level.
- ▶ On a detail form, this element can be editable.

If you use this element on an upper form, it will be read-only. It will automatically add up all values from amount fields on detail forms; therefore, it cannot contain a formula, be auto-populated, or reset.

Note: In Classic Payment Application BPs, the amount DE must be a product of **uuu_unit_price** DE and **uuu_quantity** DE. Therefore, ensure the amount field is editable for manual entry.

Use this element for: Entering currency data on any business process.

The element is automatically formatted to use the currency specified in the currency details window. (**Company Workspace > Admin mode > Standards & Libraries > Currencies > [Currency]**)

If the data has a decimal value, the number of decimal values will follow the number of decimal places specified in the currency details window.

description

Data Definition: SYS Description Text

Form Label (Field Label): Description

of Characters: 250

Where to use it: Any business process

Use this element for: Entering text information on a business process.

due_date

Data Definition: Date Picker

Form Label (Field Label): Due Date

of Characters: Not applicable

Where to use it: Any business process with a workflow

Use this element for: Entering date and time information on a business process.

User can select the value of this element at run time, or the system can calculate the value based on the workflow duration specified in the business process setup.

The late task-notification and task-indicators work based on this data element.

otherCompanyID

Data Definition: Company Picker

Form Label (Field Label): Company

of Characters: Not applicable

Where to use it: Upper or detail form of any company-level or project-level business process.

Note: Do not use this picker on configurable manager attribute forms.

Use this element for: Viewing Partner Company information or Member Company information.

At the company-level, the picker will show partner companies.

At the project level, the picker will show member companies.

record_no

Data Definition: Record Number

Form Label (Field Label): Record Number

of Characters: 20

Where to use it:

- ▶ Any business process
- ▶ Schedule Activity Attribute Forms

Use this element for: Viewing the number of a record.

Based on Record Number Data data definition. The system will assign a record number or identifier (based on configuration) to this element.

This element can also be a hyperlink that opens a BP record created by an activity that is part of a “scope management” function.

Gaps in Generated Business Process Record Number

Business Process (BP) record number is sequentially generated when you create a new record. The newly generated record number is locked so that other records (being created at the same time) cannot use that number. If the BP record cannot be created for any reason (for example, Cost Sheet rules or validations that exist at the SOV level), the system only voids the generated record number and does not reset the record numbering sequence to allow another BP record to pick up that generated number. This operation generates gaps in BP record number generation.

short_desc

Data Definition: SYS Short Description Text

Form Label (Field Label): Short Description

of Characters: 50

Where to use it: Detail form of any Line Item type business process.

Use this element for: Entering additional information regarding a line item.

Note: This is a system-defined element.

status

Data Definition: SYS Short Description Text

Form Label (Field Label): Status

of Characters: 20

Where to use it: Upper form of any business process.

Note: You *cannot* use this element as the master element in a dynamic data set (DDS).

Use this element for: Viewing or entering the status of a business process record.

This is a *required* field on both workflow and non-workflow business processes.

The data set for this data element is based on the statuses that are selected as part of the business process design in uDesigner.

For workflow business processes, this element will be read-only and will be changed or updated based on the workflow step status.

For non-workflow business processes, this element is editable and required.

title

Data Definition: Short Description Text

Form Label (Field Label): Title

of Characters: 50

Where to use it: Any business process.

Use this element for: Entering a title for a business process record.

This element is useful if you want the title of the business process record to appear in notifications and task logs.

uuu_bp_record_url

Data Definition: SYS Short Description Text 250

Form Label (Field Label): Business Process Record UR

of Characters: 250

Where to use it: Upper form of any business process

Use this element for: Displaying a URL a user can use to access a view-only copy of a business process record from an external system.

If you include this element on the upper form, the system will automatically populate it with a URL when the business process is created.

In order for this URL data element to operate, the business process record must be available from a Master Log.

uuu_creation_date

Data Definition: SYS Date Picker

Form Label (Field Label): Creation Date

of Characters: Not applicable

Where to use it: Any business process

Use this element for: Viewing the date a business process record was created.

The system automatically populates this element.

uuu_dm_publish_path

Data Definition: SYS Long Description Text 2000

Form Label (Field Label): Publish Path

of Characters: 2000

Where to use it:

- ▶ Upper form of any business process.
- ▶ Detail form of business processes that have line items.

Use this element for: Specifying the folder path to enable the automatic publishing of documents attached to business processes.

The folder path is specified in a formula.

By default, documents attached to business processes are published in the Unpublished Documents folder. This specified folder structure overrides the default publication of attached documents.

The **Document Manager** folders, created and used for automatic publication, are based on the values of the data elements specified in the **uuu_dm_publish_path** data element.

Use the forward slash (/) delimiter to build the path in a formula (for example State/County/City). The forward slash (/) delimiter is the only valid delimiter. You do not need to use the forward slash (/) delimiter in the beginning or the end of the path.

This DE can be placed in a hidden block.

For document-type business processes With Folder Structure, you can specify that a configured folder path be appended to the folder structure. This appended path is based on the path configured in the **uuu_dm_publish_path** data element on the business process form, and the selection of the Append Line Items Folder Structure to AutoPublish Path option. Refer to the *Unifier uDesigner User Guide* for details.

uuu_dm_record_info_path

Data Definition: SYS Long Description 2000

Form Label (Field Label): Record Information Publish Path

of Characters: 2000

Where to use it: Upper form of any business process

Use this element for: Automatically publishing a business process, along with its comments and attachments, to the Document Manager.

Depending on how the administrator sets up the business process, it can be automatically published to the Document Manager when it reaches a specific step in the workflow, or whenever an email notification is sent regarding the status of the business process, or both.

The folder path is specified with a formula when the business process is designed.

The **Document Manager** folders, created and used for automatic publication, are based on the values of the data elements specified in the **uuu_dm_record_info_path** data element.

Use the forward slash (/) delimiter to build the path in a formula (for example State/County/City). The forward slash (/) delimiter is the only valid delimiter. You do not need to use the forward slash (/) delimiter in the beginning or the end of the path.

This DE can be placed in a hidden block.

uuu_default_shell_picker

Data Definition: Shell Picker

Form Label (Field Label): Shell Picker

of Characters: Not applicable

Where to use it:

- ▶ Upper form of any business process
- ▶ Asset class
- ▶ Planning item

Do *not* use the Shell Picker on the following forms; it will produce an error at runtime:

- ▶ Schedule Activity attribute form
- ▶ Generic Cost Manager attribute form
- ▶ Any configurable manager attribute form

Use this element for: Selecting a shell in Unifier.

This element can work in conjunction with the Space Picker (**uuu_phy_space_picker**).

This element is *mandatory* on any company-level BP or Asset class that includes a **Space Picker**.

This element is *optional* on any project/shell-level BP that includes a **Space Picker**.

uuu_line_item_status

Data Definition: Designer Line Item Status

Form Label (Field Label): Line Item Status

of Characters: 128

Where to use it: Detail form of:

- ▶ Document business processes
- ▶ Line item type business processes

Use this element for: Selectively modifying line item information on a workflow step.

uuu_phy_space_picker

Data Definition: Space Picker

Form Label (Field Label): Space Picker

of Characters: Not applicable

Where to use it:

- ▶ Upper form of any business process
- ▶ Asset class

Note: Do not use this picker on configurable manager attribute forms.

Use this element for: Selecting a space record.

If you use this element on a company-level BP or Asset class, you must include the Shell Picker (**uuu_default_shell_picker**).

If you include this element on project/shell-level BPs, the Shell Picker is optional.

uuu_project_phase

Data Definition: Project Phase

Form Label (Field Label): Project Phase

of Characters: 64

Where to use it: Upper form of project-level business processes, its logs (Standard and Advanced) and find.

Note: The **uuu_project_phase** data element is not supported on Shell Attribute form.

Use this element for: Viewing the phase of a project; always a read-only field.

The data set for this field will be specified in Unifier and will be available under the project as a project phase field when you are defining a project.

You can also use this element as a master element for a dynamic data set.

On the action form of a BP, this field is always updated with the current value of the standard Project Phase element.

uuu_project_picker

Data Definition: Project Picker

Form Label (Field Label): Project

of Characters: Not applicable

Where to use it: Detail form of a company-level BP

Use this element for: Selecting a project.

You can place multiple project pickers on a form.

The picker will show the user a list of the company-sponsored projects to which the user has access.

The picker shows active, inactive, and on-hold projects.

uuu_quantity

Data Definition: Decimal Amount

Form Label (Field Label): Item Quantity

of Characters: 50

Where to use it: Detail form of any business process : Payment Applications or Summary Payment Applications SOV sheets. This data element will roll up to the SOV sheet only when the Payment BP record is Approved.

Note: In Classic Payment Application BPs, uuu_quantity will not populate from Base Commit and Change Commit BPs. It will always be zero. Therefore, ensure the field is editable for manual entry. You can also use this data element in a formula DE which can then be used to populate another data element in the same detail form. Unlike SPA, it will not be the consolidated quantity of base commit and all change commits.

Use this element for: Entering quantity of a line item. This data element works in conjunction with uuu_unit_price data element.

uuu_record_last_update_date

Data Definition: Date Picker

Form Label (Field Label): Record Last Update Date

of Characters: Not applicable

Where to use it:

- ▶ Upper form or log of any business process
- ▶ Shell attribute form
- ▶ Shell log
- ▶ Space or Level detail form or log
- ▶ Unifier Mobile

Use this element for: Specifying the date and time on which the record was last updated.

Updates can include changes that occur due to auto-population, integration, or any other change to the business process, including adding or removing attachments and general comments.

This data element is populated using the system date.

It is recommended that you place this field on the:

- ▶ Shell attribute form to track changes to the shell.
- ▶ Upper form and log of business processes that are enabled for the Self-Service Portal.

uuu_shell_status

Data Definition: Integer

Form Label (Field Label): Status

of Characters: Not applicable

Where to use it:

- ▶ Shell detail form
- ▶ Upper or detail form of a Project/Shell Creation BP

Use this element for: Selecting the status of a shell at runtime. Valid values are:

- ▶ Inactive = 0
- ▶ View-Only
- ▶ Active = 1
- ▶ On-Hold = 2

uuu_sovref_num

Data Definition: Integer Amount

Form Label (Field Label): SOV Reference Number

of Characters: Not applicable

Where to use it: Detail form of General Spends, Payment Applications, or Summary Payment Applications Business Processes (BPs).

Use this element for: Preserving the SOV reference number order for line items to ensure the correct payment of lines by third-party payment application.

Using this data element ensures that the SOV line items match those in the external payment application. For example, line items reference numbers can become mismatched if a line is deleted in Unifier but not deleted in the third-party payment application.

This data element is system-populated and read-only.

If it is used in the detail form, it must also be used in the detail Integration form.

Lease Business Processes DEs

Use the following data elements for creating **Lease** business processes.

uuu_allocation_amount

Data Definition: Currency Amount

Form Label (Field Label): Allocation Amount

of Characters: Not applicable

Where to use it: On the detail form of the payment request BP that is auto-created from the lease BP.

Use this element for: Entering the amount of rent that has been allocated to this line item

uuu_lse_allocation_name

Data Definition: Allocation Template Picker

Form Label (Field Label): Allocation Template

of Characters: Not applicable

Where to use it: Detail form of a Lease BP

Use this element for: Selecting an allocation template to link to a line item on a lease.

Unifier users can create an “allocation template” to pro-rate lease payments into different amounts for multiple tenants in a building.

The template will designate a breakdown of the costs for each tenant and Unifier will use this breakdown to create the payment calculations.

uuu_lse_first_pay_due_date

Data Definition: Date Only Picker

Form Label (Field Label): First Payment Due Date

of Characters: Not applicable

Where to use it: Detail form of a Lease BP

Use this element for: Manually specifying a first payment due date.

Users would typically use this in cases where the landlord is offering a “first month free rent” to the tenant. In these cases, the user would want to manually specify the first rent payment’s due date.

To calculate the lead time for this first payment, Unifier will subtract the value of the **uuu_lse_pay_creat_lead_time** field from this first payment due date. Thereafter, the payment due date will be calculated as usual (see **uuu_lse_pay_due_date**).

Note: If the resulting date is prior to the current date, Unifier will create the first payment record immediately, with the creation date as the current date.

This field can be auto-populated and can contain a formula.

uuu_lse_pay_creat_lead_time

Data Definition: SYS Pay Creation Day of Month

Form Label (Field Label): Payment creation lead time

of Characters: Not applicable

Where to use it:

- ▶ Detail form of a Lease BP
- ▶ Payment requests auto-created by Lease BPs

Use this element for:

- ▶ Specifying the amount of time (in days, zero to 30) before the payment due date that the invoice (payment request) must be created.

This time should include time for both creation and approval.

- ▶ Calculating the creation date of a Payment Request BP.

The field triggers the auto-creation of payment request BP records from the Lease BP.

This value is the difference in days between 1 and 30 and produces the lead time—the number of days before the latest payment due date—at which the generated record should be created.

Unifier uses this value with the value of the **uuu_lse_pay_latest_due_date** field to auto-populate the **uuu_lse_pay_creation_date** field. For example, if the value in the **uuu_lse_pay_latest_due_date** field is 3/15/2009, and the value the user specifies in this lead time field is 5, then the creation date of the payment request will be 3/10/2009.

Pull-down Menu (Drop-down list).

uuu_lse_add_pay_amt

Data Definition: Currency Amount

Form Label (Field Label): Additional Payment Amount

of Characters: Not applicable

Where to use it: Lease BPs

Use this element for: Adding an additional amount to the lease payment.

Users can use this in cases such as when a lease amount increases by a percentage of gross sales.

Anything entered in this field will increase the value in the Payment Amount field of the auto-created BP.

uuu_lse_commencement_date

Data Definition: Date Only Picker

Form Label (Field Label): Lease Commencement Date

of Characters: Not applicable

Where to use it: Upper form of a Lease BP

Use this element for: Specifying a start date for the lease that overrides the start date for a lease term.

When Unifier calculates the payment schedule for straight-line rent, it will use this date to calculate the start of the lease, rather than the start date on the lease line item.

This DE does not change the start date on the line item. Unifier takes this commencement date field into consideration when it calculates the straight-line payments after you click **Save** or

Finish Editing on the business process form

When you open the form in view mode, you will see the commencement date adjustment reflected on the Payment Schedule you open from the **Payment Schedule** button on the toolbar.

This DE is available for auto-population and formulas.

uuu_lse_end_date

Data Definition: Date Only Picker

Form Label (Field Label): End Date

of Characters: Not applicable

Where to use it: Lease BPs

Use this element for: Specifying the date on which a lease term ends.

This date must be greater than the start date and cannot be more than 100 years per line item.

Example

January 2000 to December 2099 is valid, but January 2000 to December 2100 is not. If a lease for longer than 100 years is necessary, you will have to set up multiple payment term lines to accommodate it.

uuu_lse_esc_freq_len

Data Definition: Decimal Amount

Form Label (Field Label): Escalation Frequency Term Length

of Characters: Not applicable

Where to use it: Lease BPs

Use this element for: Specifying how often the escalation should occur, time-wise (such as every 12 months).

Note: Not applicable if **None** is chosen for the Escalation Method.

This element works in conjunction with these elements:

- ▶ **uuu_lse_esc_freq_type**
- ▶ **uuu_lse_esc_method**
- ▶ **uuu_lse_esc_value**

Examples

For a lease that escalates by 2% every 5 years:

- ▶ **uuu_lse_esc_method** = %
- ▶ **uuu_lse_esc_value** = 2
- ▶ **uuu_lse_esc_freq_len** = 5
- ▶ **uuu_lse_esc_freq_type** = Years

For a lease that escalates by \$200 every 5 years:

- ▶ **uuu_lse_esc_method** = Fixed
- ▶ **uuu_lse_esc_value** = 200
- ▶ **uuu_lse_esc_freq_len** = 5
- ▶ **uuu_lse_esc_freq_type** = Years

Note: Escalation will differ slightly, depending on the frequency used. Over a 10-year lease term, an escalation frequency of 1 year will differ from a frequency of 52 weeks or 365 days because of leap years. Years with 366 days will make a difference; and a frequency of 52 weeks might be a day, or two, short of a full year.

uuu_lse_esc_freq_type

Data Definition: SYS Escalation Frequency Term Type

Form Label (Field Label): Escalation Frequency Term Type

of Characters: Not applicable

Where to use it: Lease BPs

Use this element for: Specifying how often the escalation should occur, time-wise (such as every 12 months).

This data element is a Pull-down Menu (Drop-down list) that offers a choice of term types:

- ▶ Days
- ▶ Weeks
- ▶ Months
- ▶ Years

Note: Not applicable if **None** is chosen for the Escalation Method.

This element works in conjunction with these elements:

- ▶ `uuu_lse_esc_freq_type`
- ▶ `uuu_lse_esc_method`
- ▶ `uuu_lse_esc_value`

Examples

For a lease that escalates by 2% every 5 years:

- ▶ `uuu_lse_esc_method = %`
- ▶ `uuu_lse_esc_value = 2`
- ▶ `uuu_lse_esc_freq_len = 5`
- ▶ `uuu_lse_esc_freq_type = Years`

For a lease that escalates by \$200 every 5 years:

- ▶ `uuu_lse_esc_method = Fixed`
- ▶ `uuu_lse_esc_value = 200`
- ▶ `uuu_lse_esc_freq_len = 5`
- ▶ `uuu_lse_esc_freq_type = Years`

Escalation will differ slightly, depending on the frequency used. Over a 10-year lease term, an escalation frequency of 1 year will differ from a frequency of 52 weeks or 365 days because of leap years. Years with 366 days will make a difference; and a frequency of 52 weeks might be a day, or two, short of a full year.

`uuu_lse_esc_method`

Data Definition: SYS Escalation Method

Form Label (Field Label): Escalation Method

of Characters: Not applicable

Where to use it: Lease BPs

Use this element for: Specifying the method by which rents should be escalated.

This data element is a Pull-down Menu (Drop-down list) that offers a choice of fixed escalation methods such as:

- ▶ **Fixed amount**
Escalates the rent by fixed periodic increases
- ▶ **% (Percentage)**
Escalates the rent by a percentage, such as an amount based on changes in landlord expenses.
- ▶ **None**
No escalations in rent
- ▶ **Index Rate**
Escalates the rent based on the index rate selected in the index rate BP data picker.
Unifier uses the values of the elements **uuu_index_rate** and **uuu_index_code** set in the index rate BP to calculate the rent escalation.
The payment schedules are updated whenever the index rate value gets changed.

uuu_lse_esc_value

Data Definition: Decimal Amount

Form Label (Field Label): Escalation Value

of Characters: Not applicable

Where to use it: Lease BPs

Use this element for: Specifying how much a rent should be escalated, either in a dollar amount or a percentage.

Note: Not applicable if **None** is chosen for the Escalation Method (**uuu_lse_esc_method**).

uuu_lse_frequency

Data Definition: SYS Payment Frequency

Form Label (Field Label): Frequency

of Characters: Not applicable

Where to use it: Lease BPs

Use this element for: Specifying the frequency with which the lease should be paid—one-time payment, 3 months, 6 months, 9 months, or 12 months.

Pull-down Menu (Drop-down list).

Used in conjunction with the lease start and end dates, the payment will be automatically prorated (on days per month), except for one-time payments.

The calculated daily rates are based on:

- ▶ 3 months = 90 days
- ▶ 6 months = 180 days
- ▶ 9 months = 270 days
- ▶ 12 months = 360 days

uuu_lse_pay_amount

Data Definition: Currency Amount

Form Label (Field Label): Payment Amount

of Characters: Not applicable

Where to use it: Lease BPs

Use this element for: Displaying the payment amount requested.

This is a read-only element.

Unifier uses the values of the following DEs to calculate the value for **uuu_lse_pay_amount**:

- ▶ **uuu_lse_start_date**
- ▶ **uuu_lse_end_date**
- ▶ **uuu_lse_frequency**
- ▶ **uuu_lse_proration_method**
- ▶ **uuu_lse_add_pay_amt**
- ▶ **uuu_lse_esc_method**
- ▶ **uuu_lse_esc_freq_len**
- ▶ **uuu_lse_esc_freq_type**

uuu_lse_pay_creation_date

Data Definition: Date Only Picker

Form Label (Field Label): Payment Creation Date

of Characters: Not applicable

Where to use it: Must be included on the standard detail form of Lease BPs.

Use this element for: Displaying the payment creation date.

This is a read-only field that is auto-populated.

Unifier uses the value of the **uuu_lse_pay_creat_lead_time** element to calculate the value for this field.

uuu_lse_pay_due_date

Data Definition: Date Only Picker

Form Label (Field Label): Payment Due Date

of Characters: Not applicable

Where to use it: Must be included on the standard detail form of Lease BPs

Use this element for: Displaying the payment due date.

This is a read-only field that is auto-populated.

Unifier uses the values of the **uuu_lse_frequency** and **uuu_lse_pay_due_day** elements to calculate the value for this field.

uuu_lse_pay_due_day

Data Definition: SYS Pay Day of Month

Form Label (Field Label): Payment due day

of Characters: Not applicable

Where to use it: Lease BPs

Use this element for: Specifying the day or month on which payment is due.

Pull-down Menu (Drop-down list).

The valid values are 1 to 28. Unifier uses the value, in conjunction with the **uuu_lse_frequency** element, to calculate the value for the **uuu_lse_pay_due_date** field.

uuu_lse_pay_latest_due_date

Data Definition: Date Only Picker

Form Label (Field Label): Latest Payment Due Date

of Characters: Not applicable

Where to use it: Must be included on the standard detail form of Lease BPs.

Use this element for: Displaying the latest payment due date.

This is a read-only field that is auto-populated. Unifier uses the values of these elements to calculate the value for this field:

- ▶ **uuu_lse_frequency**
- ▶ **uuu_lse_pay_latest_due_day**
- ▶ **uuu_lse_start_date**
- ▶ **uuu_lse_end_date**
- ▶ **uuu_lse_pay_latest_due_day**

uuu_lse_pay_latest_due_day

Data Definition: SYS Pay Day of Month

Form Label (Field Label): Latest payment due day

of Characters: Not applicable

Where to use it: Lease BPs

Use this element for: Specifying the latest day of the month on which the payment must be received. Includes a grace period.

Pull-down Menu (Drop-down list).

The valid values are 1 to 28. Unifier uses the value to calculate the value for the **uuu_lse_pay_latest_due_date** field.

If the value in **uuu_lse_pay_due_day** equals the value in this field, the calculations for both these fields will be the same. In all other cases, the latest due day will always be after the due day.

Example

If the due day is 28 and the *latest* due day is 5, this implies the 5th of the following month.

uuu_lse_pay_type

Data Definition: SYS Payment Type

Form Label (Field Label): Payment Type

of Characters: Not applicable

Where to use it: Lease BPs

Use this element for: Specifying the payment type.

Pull-down Menu (Drop-down list).

The data set for this field can be specified in Unifier.

uuu_lse_proration_method

Data Definition: SYS Proration Method

Form Label (Field Label): Proration Method

of Characters: Not applicable

Where to use it: Lease BPs

Use this element for: Pro-rating rent over a period of time.

This data element is a pull-down that offers a choice of fixed proration periods:

- ▶ 365 Days/Year
- ▶ Yearly rent divided by # of days = daily rent

Example

A lease has a monthly rent of \$3000. If the user chooses this option, for 15 days of a 30-day month, the rent will be \$1479.45 ($\$36,000/365 \times 15 = 1479.45$).

360 Days/Year

Yearly rent divided by # of days = daily rent

Example

A lease has a monthly rent of \$3000. If the user chooses this option, for 15 days of a 30-day month, the rent will be \$1500 ($\$36,000/360 \times 15 = 1500$).

Days/Month

Monthly rent divided by # of days per month = daily rent.

Example

A lease has a monthly rent of \$3000. If the user chooses this option, for 15 days of a 30-day month, the rent will be \$1500 ($\$3000/360 \times 15 = 1500$).

Note: In all options, Unifier counts the days starting with and including the start date; so January 15 to January 31 is 17 days, not 16.

uuu_lse_sl_adjustment

Data Definition: Currency Amount

Form Label (Field Label): Straight Line Rent Amount Adjustment

of Characters: Not applicable

Where to use it: Upper form of a Lease BP

Use this element for: Specifying a currency amount adjustment to the lease that is added or subtracted from the lease amount.

You can use negative amounts in the calculation.

When Unifier calculates the payment schedule for straight-line rent, it will use this amount adjustment (plus or minus) to calculate the amount of the lease, along with the currency amount on the lease line item.

This field does not change the amount on the line item. Unifier takes this adjustment amount into consideration when it calculates the straight-line payments after you click **Save** or **Finish Editing** on the business process form.

When you open the form in view mode, you will see the currency amount adjustment reflected on the **Payment Schedule** that you opened using the **Payment Schedule** option on the toolbar.

This DE is available for auto-population and formulas.

uuu_lse_sl_rent

Data Definition: Currency Amount

Form Label (Field Label): Straight Line Rent Amount

of Characters: Not applicable

Where to use it: Upper form of a Lease BP

Use this element for: Displaying the straight line rent amount on the upper form of a lease.

This is a read-only field that will be updated dynamically whenever a user changes a line item or other amount that impacts the rent amount. The updated value will appear as the user makes changes to the form; however, the payment schedule will not be re-calculated until the user clicks **Finish Editing** or sends the form on to the next step in a workflow.

This DE is not available for auto-population and formulas.

uuu_lse_start_date

Data Definition: Date Only Picker

Form Label (Field Label): Start Date

of Characters: Not applicable

Where to use it: Upper form of a Lease BP

Use this element for: Specifying the date on which a lease term starts.

uuu_lse_straight_line

Data Definition: Radio Button

Form Label (Field Label): Straight Line

of Characters: Not applicable

Where to use it: Lease BPs

Use this element for: Specifying whether or not the lease payment calculation must be based on a straight line calculation.

uuu_lse_term_modifier

Data Definition: Integer

Form Label (Field Label): Term Modifier

of Characters: Not applicable

Where to use it: Upper form of a Lease BP

Use this element for: Specifying a lease term modification, such as plus or minus 60 days, that should be added or subtracted from the term of the lease.

When Unifier calculates the payment schedule for straight-line rent, it will accumulate the start and end dates included in the line items, and add or subtract the value in this field when it calculates the term of the lease to calculate the term of the lease.

This DE does not change the dates on the line items.

When you open the form in view mode, you will see the lease term adjustment reflected on the *Payment Schedule* that you opened using the **Payment Schedule** option on the toolbar.

This DE is available for auto-population and formulas.

uuu_lse_termination_date

Data Definition: Date Only Picker

Form Label (Field Label): Lease Termination Date

of Characters: Not applicable

Where to use it: Upper form of a Lease BP

Use this element for: Specifying a termination date for the lease that overrides the end date for a lease term.

When Unifier calculates the payment schedule for straight-line rent, it will use this date to calculate the end of the lease, rather than the end date on the lease line item.

This field does not change the end date on the line item. Unifier takes this termination date field into consideration when it calculates the straight-line payments after you click **Finish Editing** or send the form on to the next step in a workflow.

When you open the form in view mode, you will see the termination date adjustment reflected on the *Payment Schedule* that you opened using the **Payment Schedule** option on the toolbar.

This DE is available for auto-population and formulas.

Index Rate Business Process DEs

Use the following data elements for creating the **Index Rate Business Process**.

The **Index Rate Business Process** is a simple type of business process that you can use as the basis for index rate data picker in the **Lease** business process, for index rate-based rent escalation.

uuu_index_rate

Data Definition: Float

Default Behavior: Editable (Required)

Where to use it: Upper form of the index rate BP

Use it for: Capturing the index rate value in the index rate BP.

uuu_index_code

Data Definition: String

Default Behavior: Editable (Required)

Where to use it: Upper form of the index rate BP

Use it for: Capturing the index code in the index rate BP.

Planning Manager DEs

Use the following data elements for creating the planning items and planning sheets for the **Planning Manager**.

uuu_last_update_date

Data Definition: Date Picker

Form Label (Field Label): Last Update Date

of Characters: Not applicable

Where to use it:

- ▶ Planning Sheet Attribute Forms
- ▶ Planning Sheets

Use this element for: Specifying the date on which the planning sheet was last updated.

uuu_planning_item

Data Definition: SYS Short Description Text 120

Form Label (Field Label): Planning Item

of Characters: 120

Where to use it: Detail form of a Planning Item

Use this element for: Entering a name for a planned project or initiative.

Request for Bid (RFB) DEs

Use the following data elements for creating the **Request for Bid (RFB)** business processes.

uuu_bid_count

Data Definition: Integer Amount

Form Label (Field Label): Bid Count

of Characters: 10

Where to use it: RFB business processes

Use this element for: Viewing the number of bids received.

uuu_bidders_count

Data Definition: Integer Amount

Form Label (Field Label): Bidders Count

of Characters: 10

Where to use it: RFB business processes

Use this element for: Viewing the number of bidders who were invited.

uuu_contact_company

Data Definition: SYS Medium Name

Form Label (Field Label): Contact Company

of Characters: 64

Where to use it: RFB business process form that is flagged as the “vendor master” at the company level.

Use this element for: Entering a vendor or bidder company name as part of a business process.

Example

Vendor Master

The RFB business processes will display values under this data element during the bid invitation process.

uuu_contact_first_name

Data Definition: SYS Medium Name

Form Label (Field Label): Contact First Name

of Characters: 64

Where to use it: RFB business process form that is flagged as the “vendor master” at the company level

Use this element for: Entering the vendor or bidder contact's first name as part of a business process

Example

Vendor Master

The RFB business process will display values under this data element during the bid invitation process.

uuu_contact_lang

Data Definition: i18n_locales

Form Label (Field Label): Contact Language

of Characters: 64

Where to use it: The Upper Form of Company-level (Simple or Line Item) Business process that has been marked as Master Vendor Business Process.

uDesigner option: Use this process as RFB master vendor list is checked.

Use this element for: Capturing the language of the contact user for the bidding company, in the master vendor list.

At runtime, while creating a record for the bidder, the language of the bidder can be specified using this data element.

This DE is not a mandatory field that must exist on the form.

When this DE exists in the form, the bidder email notification will be based on the value selected in this field.

This DE:

- ▶ Can be marked as Editable/ Editable Required.
- ▶ Cannot be part of DDS which has it as a Master Data element on the Upper Form.
- ▶ The remaining behavior is the same as any other pull-down DE.
- ▶ At runtime, the list of languages displayed are 12 languages.

uuu_contact_last_name

Data Definition: SYS Medium Name

Form Label (Field Label): Contact Last Name

of Characters: 64

Where to use it: On the RFB business process form that is flagged as the “vendor master,” at the company level.

Use this element for: Entering the vendor or bidder contact's last name as part of a business process.

Example

Vendor Master

The RFB business process will display values under this data element during the bid invitation process.

uuu_rfb_due_date

Data Definition: Date Picker

Form Label (Field Label): RFB Due Date

of Characters: Not applicable

Where to use it: RFB business processes.

Use this element for: Entering a due date for a bid request.

Note: The system might not allow the requestor to view the bid response until this due date is passed.

uuu_rfb_initiate_date

Data Definition: SYS Date Logical Datasource

Form Label (Field Label): RFB Initiate Date

of Characters: Not applicable

Where to use it: RFB business processes.

Use this element for:

This Data Element captures the date and time of the first bid invitation sent out, for the concerned RFB.

Any of the Requestor Upper Forms of "Request for Bid" BP.

The DE would be enabled only for the requestor upper form.

It would be restricted for any other forms on RFB BP like - Requestor detail form , Bidder Upper form, Bidder Detail form.

Note: This field (read-only) holds the value of the date and time of the first invite sent for a particular RFB.

Additional information

This DE is not a mandatory field; however, after the first invitation is sent, the date value will be captured in this DE, by the system, irrespective of this DE being added on any of the upper forms, or not. If this DE is added on any of the upper forms, then the value captured will be reflected.

This DE cannot be marked as Editable or Editable Required.

Since this DE is read-only in the RFB BP, it cannot be a part of DDS which has this DE as a Master Data element on the form. The remaining behavior is as any other read-only date-type data element

Note: The date-type data element can be used as display element for the BP Picker and the BP Creator - Reference Type.

uuu_rfb_winning_bid

Data Definition: Bid Picker

Form Label (Field Label): Winning Bid

of Characters: Not applicable

Where to use it: Only for the RFB "Requestor" business processes.

Note: You are not required to place this DE on an RFB "Requestor" Upper form.

Use this element for: Selecting a winning bid from all bids received.

uuu_user_id

Data Definition: SYS Long Name

Form Label (Field Label): User ID

of Characters: Not applicable

Where to use it: The RFB business processes to send out bid invitations.

Use this element for: Entering vendor or bidder contact information.

Note: This data element only accepts the email address as input.

Resource Manager DEs

Use the following data elements for creating the business processes and attribute forms for the **Resource Manager**.

uuu_activity_picker

Data Definition: Activity Picker

Form Label (Field Label): Activity Picker

of Characters: Not applicable

Where to use it: Time Sheet business processes in the company workspace, or in a CBS shell (not available for generic shells).

Note: Do not use this picker on configurable manager attribute forms.

Use this element for: Selecting an activity from the master schedule sheet.

uuu_from_date

Data Definition: Date Picker

Form Label (Field Label): From Date

of Characters: Not applicable

Where to use it:

- ▶ Upper form of a Reservation business process
- ▶ Resource Booking business process

Use this element for: Entering the time-frame for a reserved object, for example, the time-frame for resource that is being booked.

uuu_resc_capacity

Data Definition: Integer Amount

Form Label (Field Label): Default Resource Capacity

of Characters: Not applicable

Where to use it: Resource Attribute forms.

Use this element for: Entering the capacity (hours available for work) for the resource per day.

Use this element if resources normally work the same hours each day.

If you need to note different hours for different days, use the **uuu_resc_mon_capacity** through **uuu_resc_sun_capacity** data elements instead.

uuu_resc_code

Data Definition: SYS Short Description Text 120

Form Label (Field Label): Resource Code

of Characters: 120

Where to use it:

- ▶ Resource Attribute forms
- ▶ Resource Assignment Attribute Forms

Use this element for: Viewing or entering the resource code of the assigned resource.

If a Hard Booked Resource is selected, this field is populated with the code of the selected resource; otherwise, this field is editable and the user must enter a value manually.

uuu_resc_sun_reg_hours uuu_resc_sat_reg_hours

Data Definition: Decimal Amount

Form Label (Field Label): (day) Regular Hours

of Characters: Not applicable

Where to use it: Detail form of Time Sheet business processes.

Use this element for: Entering regular hours for each weekday on a time sheet.

uuu_resc_interest

Data Definition: Pull-down menu

Form Label (Field Label): Interest

of Characters: Not applicable

Where to use it:

- ▶ Resource Attribute form
- ▶ Skill tab while defining a resource in Unifier

Use this element for: Specifying a user's skill interest on a 1 to 10 scale, 1 being minimum interest, 10 being maximum.

uuu_resc_sun_ot_hours uuu_resc_sat_ot_hours

Data Definition: Decimal Amount

Form Label (Field Label): (day) Overtime Hours

of Characters: Not applicable

Where to use it: Detail form of Time Sheet business processes.

Use this element for: Entering overtime hours for each weekday on a time sheet.

uuu_resc_mon_capacity uuu_resc_sun_capacity

Data Definition: Integer Amount

Form Label (Field Label): (day) Capacity (Hrs.)

of Characters: Not applicable

Where to use it: Resource Attribute forms

Use this element for: Entering the number of hours a resource can work on that day.

Use these elements if resources work differing hours on each day.

Resource capacity impacts the resource's availability for booking.

These elements, together, are used to calculate the weekly hours that a resource is available.

With these values, Unifier will calculate and display the resource's available hours on the Availability sheet.

Note: If you implement resource capacity calculating, you must place all seven of these elements on the attribute form.

uuu_resc_name

Data Definition: SYS Short Description Text 120

Form Label (Field Label): Resource Name

of Characters: 120

Where to use it:

- ▶ Resource Attribute forms
- ▶ Resource Assignment Attribute Forms

Use this element for:

- ▶ Entering the name of the person on whom to report time.
- ▶ Viewing or entering the name of the assigned resource.

If a Hard Booked Resource is selected, this field is populated and is read only; otherwise, this field is editable and the user must enter a value manually.

uuu_resc_non_project_time

Data Definition: SYS Resc Work Type

Form Label (Field Label): Non-Project Time

of Characters: 70

Where to use it: Resource Attribute forms

Use this element for: Booking non-project time manually on a Booking Summary Sheet.

uuu_resc_nwd_type

Data Definition: SYS Resc Calendar NW Day Type

Form Label (Field Label): Non-Working Day Type

of Characters: Not applicable

Where to use it: Time Sheet business processes

Use this element for: Specifying the type of non-working day, such as PTO, holiday, and so on.

uuu_resc_ot_rate

Data Definition: Decimal Amount

Form Label (Field Label): Overtime Rate

of Characters: Not applicable

Where to use it: Time Sheet business processes

Use this element for: Entering the overtime rate of a resource/role combination.

If this element is automatically calculated, the calculated rate will be displayed.

uuu_resc_picker

Data Definition: Resource Picker

Form Label (Field Label): Resource Picker

of Characters: Not applicable

Where to use it:

- ▶ Detail form of Time Sheet and Booking business processes.
- ▶ Resource Assignment Attribute Forms.

Note: Do not use this picker on configurable manager attribute forms.

Use this element for:

- ▶ Selecting a resource to report on or assign.
- ▶ Selecting a resource that is booked to a project.

This picker always opens in “Find” mode and requires the user to enter at least one search criteria, such as a name or a skill, to narrow the field of names to choose from.

This picker should be used to allow users to select hard booked resources.

For timesheet BPs, users will use this picker to select the personnel to report time on.

At runtime, the picker will default to read-only mode and show the current user's name, as Unifier assumes the user will be reporting his or her own time; however, depending on permissions, the picker can be editable in order to allow others, such as project managers, to complete time sheets on behalf of other workers.

uuu_resc_proficiency

Data Definition: SYS Resource Proficiency

Form Label (Field Label): Proficiency

of Characters: Not applicable

Where to use it:

- ▶ Resource Attribute form
- ▶ Skill tab while defining a resource in Unifier

Use this element for: Specifying a user's skill proficiency on a 1 to 10 scale, 1 being minimum proficiency, 10 being maximum.

uuu_resc_skill

Data Definition: SYS Resource Skill

Form Label (Field Label): Skill Name

of Characters: Not applicable

Where to use it:

- ▶ Resource Attribute form
- ▶ Skill tab while defining a resource in Unifier

Use this element for: Specifying a user's job skills.

uuu_resc_status

Data Definition: SYS Resource Status

Form Label (Field Label): Resource Status

of Characters: Not applicable

Where to use it: Resource Attribute forms

Use this element for: Viewing or entering the status (active or inactive) of a resource.

uuu_resc_tot_reg_hours

Data Definition: Decimal Amount

Form Label (Field Label): Total Regular Hours

of Characters: Not applicable

Where to use it: Time Sheet business processes

Use this element for: Entering the total number of regular (non-overtime) hours on a Time Sheet BP for the reporting period.

uuu_resc_tot_amount

Data Definition: Decimal Amount

Form Label (Field Label): Total Amount

of Characters: Not applicable

Where to use it: Time Sheet business processes

Use this element for: Entering the total dollar amount earned for the hours reported on a Time Sheet BP.

uuu_role_amt

Data Definition: Decimal Amount

Form Label (Field Label): Total Amount

of Characters: Not applicable

Where to use it: Resource Attribute forms

Use this element for: Entering the total dollar amount for the hours reported on a Schedule Sheet.

This DE is used to calculate the role rate based on the exchange rate.

The total cost = (role rate) x (currency rate) x (quantity).

If the resources are not allocated, the total cost is manual entry (from a formula).

uuu_role_name**Data Definition:** Short Description Text 120**Form Label (Field Label):** Role Name**# of Characters:** 120**Where to use it:**

- ▶ Role Attribute Forms
- ▶ Resource Assignment Attribute Forms

Use this element for:

- ▶ Identifying the type of work to be performed for a scheduled activity.
- ▶ Viewing the role of the resource assigned to the activity.

If a hard booked resource is selected, then this field is populated.

Read-only field.

uuu_role_imported_from_p6**Data Definition:** SYS Checkbox**Form Label (Field Label):** Imported from P6 (Checkbox)**# of Characters:** Not applicable**Where to use it:** Role attribute form

Use this element for: Role attribute form so Unifier can identify which Roles were created via integration with P6.

If user is creating Unifier Roles via integration with P6, this DE helps identify if a Role is integrated with P6, or it is manually created in Unifier.

Note: This DE is not required for Role attribute forms that are not integrated with P6.

This element is "Read-only" when used on a Role attribute form.

The value for this element is populated during role creation via P6-Unifier integration.

This element can be placed on any other form (like other check box DEs) and can be marked as Editable, Required, or Read-only.

uuu_role_id**Data Definition:** SYS Short Description Text**Form Label (Field Label):** Role ID (Checkbox)**# of Characters:** 50**Where to use it:** Role attribute form

Use this element for: When Roles in Unifier are created via integration with P6.

When a new Role is created via integration, this DE is populated with the P6 Resource ID.

This DE is necessary for successful integration of a Shell with P6 when its `uuu_int_schedule_type` = 'Resource Loaded' or 'Cost Loaded.'

Note: This DE is not required for Role attribute forms that are not integrated with P6.

If you place this DE on a Role attribute form, ensure that the DE is marked as Editable

If you place this DE on a Role attribute form, you can mark this DE, Required or Read-only.

This element can be placed on any other form (a custom PD DE) and can be marked as Editable, Required, or Read-only.

uuu_role_picker

Data Definition: Role Picker

Form Label (Field Label): Role

of Characters: Not applicable

Where to use it:

- ▶ Detail form of Time Sheet business processes
- ▶ Resource Allocation Sheets

Note: Do not use this picker on configurable manager attribute forms.

Use this element for: Selecting the role to report on or assign.

When you use this picker on a timesheet BP at the project level, it will filter out those roles that have already been booked for other projects.

uuu_role_status

Data Definition: SYS Role Status

Form Label (Field Label): Role Status

of Characters: Not applicable

Where to use it: Role Attribute Forms

Use this element for: Specifying the status (active or inactive) of a role.

Pull-down Menu (Drop-down list).

uuu_role_type

Data Definition: SYS Role Type

Form Label (Field Label): Role Type (Checkbox)

of Characters: Not applicable

Where to use it: Role attribute form

Use this element for: When Roles in Unifier are created via integration and from P6.

P6 Resources will be mapped to create Roles in Unifier.

When a "P6 Resource" creates a Role, the Role Type can be either Labor, Nonlabor, or Material.

Note: This DE is not required for Role attribute forms that are not integrated with P6 (Shell with P6 when its `uuu_int_schedule_type` = 'Resource Loaded' or 'Cost Loaded').

If this element is placed on a Role attribute form, it must be marked as Editable.

You can mark this element as Required or Read-Only.

This element can be placed on any other form (a custom PD DE) and can be marked as Editable, Required, or Read-only.

uuu_role_uom

Data Definition: System DD

Form Label (Field Label): Unit of Measure (Checkbox)

of Characters: Not applicable

Where to use it: Role attribute form

Use this element for: When Roles in Unifier are created via integration with P6.

When a new Role is created via integration (Role Type = 'Material'), this DE is populated with the Unit of Measure from P6 Resource.

Note: This DE is necessary for successful integration of a Shell with P6 when its `uuu_int_schedule_type` = 'Resource Loaded' or 'Cost Loaded'.

This DE is not a required DE for a Role attribute form.

If you place this DE on a Role attribute form, ensure that the DE is marked as Editable

If you place this DE on a Role attribute form, you can mark this DE, Required or Read-only.

This element can be placed on any other form (a custom PD DE) and can be marked as Editable, Required, or Read-only.

uuu_to_date

Data Definition: Date Picker

Form Label (Field Label): To Date

of Characters: Not applicable

Where to use it:

- ▶ Upper form of Reservation BPs
- ▶ Resource Booking business processes

Use this element for:

- ▶ Entering the time frame for a reserved object.
- ▶ Entering the time frame for which a resource is being booked.

uuu_user_address

Data Definition: SYS Medium Name

Form Label (Field Label): Address Line 1

of Characters: Not applicable

Where to use it: Resource Attribute form

Use this element for: Entering the street address of a user or resource.

uuu_user_city

Data Definition: SYS Medium Name

Form Label (Field Label): City

of Characters: Not applicable

Where to use it: Resource Attribute form

Use this element for: Entering the city of a user or resource.

uuu_user_country

Data Definition: SYS Medium Name

Form Label (Field Label): Country

of Characters: Not applicable

Where to use it: Resource Attribute form

Use this element for: Entering the country of a user or resource.

uuu_user_email

Data Definition: SYS Medium Name

Form Label (Field Label): E-Mail

of Characters: 64

Where to use it:

- ▶ Resource Attribute form

- ▶ User Administration form

Use this element for: Entering the email address of a resource or user.

uuu_user_fax

Data Definition: SYS Medium Name

Form Label (Field Label): Fax

of Characters: 64

Where to use it:

- ▶ Resource Attribute form
- ▶ User Administration form

Use this element for: Entering the fax number of a resource or user.

uuu_user_firstname

Data Definition: SYS Medium Name

Form Label (Field Label): First Name

of Characters: 64

Where to use it:

- ▶ Resource Attribute form
- ▶ User Administration form

Use this element for: Entering the first name of a resource or user.

uuu_user_homephone

Data Definition: SYS Medium Name

Form Label (Field Label): Home Phone

of Characters: 64

Where to use it:

- ▶ Resource Attribute form
- ▶ User Administration form

Use this element for: Entering the phone number of a resource or user.

uuu_user_lastname

Data Definition: SYS Medium Name

Form Label (Field Label): Last Name

of Characters: 64

Where to use it:

- ▶ Resource Attribute form
- ▶ User Administration form

Use this element for: Entering the last name of a resource or user.

uuu_user_mobilephone

Data Definition: SYS Medium Name

Form Label (Field Label): Mobile Phone

of Characters: 64

Where to use it:

- ▶ Resource Attribute form
- ▶ User Administration form

Use this element for: Entering the mobile phone number of a resource or user.

uuu_user_pager

Data Definition: SYS Medium Name

Form Label (Field Label): Pager

of Characters: 64

Where to use it:

- ▶ Resource Attribute form
- ▶ User Administration form

Use this element for: Entering the pager number of a resource or user.

uuu_user_state

Data Definition: SYS Medium Name

Form Label (Field Label): State

of Characters: Not applicable

Where to use it: Resource Attribute form

Use this element for: Entering the state of a user or resource.

uuu_user_timezone

Data Definition: SYS Medium Name

Form Label (Field Label): Time Zone

of Characters: Not applicable

Where to use it: Resource Attribute form

Use this element for: Entering the time zone of a user or resource.

uuu_user_title

Data Definition: SYS Medium Name

Form Label (Field Label): Title

of Characters: 64

Where to use it:

- ▶ Resource Attribute form
- ▶ User Administration form

Use this element for: Entering the title of a user or resource.

uuu_user_workphone

Data Definition: SYS Medium Name

Form Label (Field Label): Work Phone

of Characters: 64

Where to use it:

- ▶ Resource Attribute form
- ▶ User Administration form

Use this element for: Entering the work phone number of a user or resource.

uuu_user_zip

Data Definition: SYS Medium Name

Form Label (Field Label): Zip Code

of Characters: 64

Where to use it: Resource Attribute form

Use this element for: Entering the zip code of a user or resource.

uuu_week_picker

Data Definition: Date Picker

Form Label (Field Label): Week of

of Characters: Not applicable

Where to use it:

- ▶ Resource Booking business processes

- ▶ Time Sheet business processes

Use this element for: Indicating a specific week for something, such as a time sheet entry.

Schedule Manager DEs

Use the following data elements for creating the schedule sheets and attribute forms for the **Schedule Manager**.

uuu_act_cost1

Data Definition: Currency Amount

Form Label (Field Label): Activity Cost 1

of Characters: Not applicable

Where to use it: Schedule Activity Attribute Forms

Use this element for: Entering or viewing cost data at the activity level.

uuu_act_cost2

Data Definition: Currency Amount

Form Label (Field Label): Activity Cost 2

of Characters: Not applicable

Where to use it: Schedule Activity Attribute Forms

Use this element for: Entering or viewing cost data at the activity level.

uuu_act_latest_prog_as_of

Data Definition: Date Picker

Form Label (Field Label): Activity Latest Progress As Of

of Characters: Not applicable

Where to use it: Schedule Activity Attribute Forms

Use this element for: Viewing latest progress modification date for an activity.

uuu_act_pct_complete

Data Definition: Decimal Amount

Form Label (Field Label): Activity Percent Complete

of Characters: Not applicable

Where to use it: Schedule Activity Attribute Forms

Use this element for: Viewing the activity percentage of completeness, derived as an average of work complete for assigned resources.

uuu_act_tot_cost1_per_CBS

Data Definition: Currency Amount

Form Label (Field Label): Activity Total Cost 1 Per CBS

of Characters: Not applicable

Where to use it: Schedule Activity Attribute Forms

Use this element for: Viewing cost totals.

Use in association with **uuu_act_cost1**.

uuu_act_tot_cost2_per_CBS

Data Definition: Currency Amount

Form Label (Field Label): Activity Total Cost 2 Per CBS

of Characters: Not applicable

Where to use it: Schedule Activity Attribute Forms

Use this element for: Viewing cost totals.

Use in association with **uuu_act_cost2**.

uuu_activity_calendar

Data Definition: SYS Activity Calendar

Form Label (Field Label): Calendar

of Characters: Not applicable

Where to use it: Schedule Activity Attribute Forms

Use this element for: Activity calendar choice.

You can add this data element to any custom Activity Attribute form.

This DE is added by default to the default attribute form.

This DE can be marked editable, required, or read-only.

This DE cannot be used:

- ▶ For auto-population or reverse auto-population.
- ▶ In a formula, or as a linked element.

uuu_activity_codes

Data Definition: SYS Activity Codes

Form Label (Field Label): Activity Code

of Characters: Not applicable

Where to use it: Schedule Activity Attribute Forms

Use this element for: Use this element in Scope Management to standardize activities and also to use the bulk edit feature using the Activity Sheet.

uuu_activity_constraint

Data Definition: Activity Constraint

Form Label (Field Label): Constraint

of Characters: Not applicable

Where to use it: Schedule sheets

Use this element for: Gathering constraint information about an activity.

Pull-down Menu (Drop-down list) for selecting a constraint between activities on a schedule sheet.

A constraint ties a successor activity start date to a predecessor activity completion date, after observing dependencies and lags.

The available constraints in Unifier are **As soon as possible (ASAP)** and **None**:

As soon as possible: If the start date of a predecessor activity changes, this option either pulls in or pushes out the start date of an ASAP-constrained successor activity accordingly. If an ASAP-constrained activity does not have a predecessor, the schedule sheet start date determines the activity start date; un-started ASAP-constrained successor activities align accordingly.

None: The start date of a None-constrained activity does not change if the start date of a predecessor activity changes. The schedule sheet start date does not determine the start date of None-constrained activities that do not have predecessor activities.

When the schedule sheet is imported, Unifier sets all values to None; the user must set any desired activity constraints.

This DE is available for user-defined reports (UDRs) and data views.

uuu_activity_earn_amt

Data Definition: Currency Amount

Form Label (Field Label): Earned Amount

of Characters: Not applicable

Where to use it: Schedule Activity Attribute Forms

Use this element for: Entering the earned progress in form of an amount.

The user can define a formula in uDesigner to calculate the earned amount, or enter an amount.

uuu_activity_earn_progress

Data Definition: Decimal Amount

Form Label (Field Label): Earned Progress

of Characters: Not applicable

Where to use it: Schedule Activity Attribute Forms

Use this element for: Viewing or entering the earned progress of resource effort.

If the earned progress is calculated in Unifier based on the Budget and Progress Setup, this field is read-only. Otherwise, this data element is editable.

uuu_activity_etc_amount

Data Definition: Currency Amount

Form Label (Field Label): ETC Amount

of Characters: Not applicable

Where to use it: Schedule Activity Attribute Forms

Use this element for: Viewing the calculated additional effort to complete the activity in the form of an amount.

This data element is read-only and gets calculated by summing up the ETC Amount of all resources assigned to that activity.

uuu_activity_ev_filter

Data Definition: SYS Short Description Text 120

Form Label (Field Label): Activity Earned Value Filter

of Characters: 120

Where to use it: Schedule Attribute form

Use this element for: Filtering earned value sheets by progress data.

You can include a formula for this element to narrow filtering conditions.

uuu_activity_fc_start_1

Data Definition: Date Picker

Form Label (Field Label): Forecast 1 Start

of Characters: Not applicable

Where to use it: Schedule Activity Attribute Forms

Use this element for: Entering the forecast start date of an activity.

The user can also define a formula in uDesigner to calculate this date.

The following DEs are available, if you want to work with more than one activity start, finish, and duration:

- ▶ **uuu_activity_fc_start_2**
- ▶ **uuu_activity_fc_finish_2**
- ▶ **uuu_activity_fc_duration_2**

uuu_activity_fc_finish_1

Data Definition: Date Picker

Form Label (Field Label): Forecast 1 Finish

of Characters: Not applicable

Where to use it: Schedule Activity Attribute Forms

Use this element for: Entering the forecast finish date of an activity.

The user can also define a formula in uDesigner to calculate this date.

uuu_activity_fc_duration_1

Data Definition: Decimal Amount

Form Label (Field Label): Forecast 1 Duration

of Characters: Not applicable

Where to use it: Schedule Activity Attribute Forms

Use this element for: Viewing the forecast duration of an activity.

This value is calculated based on the Forecast 1 Start date and the Forecast 1 Finish date.
Read-only field.

uuu_activity_fc_start_2

Data Definition: Date Picker

Form Label (Field Label): Forecast 2 Start

of Characters: Not applicable

Where to use it: Schedule Activity Attribute Forms

Use this element for: Entering the forecast start date of an activity.

The user can also define a formula in uDesigner to calculate this date.

uuu_activity_fc_finish_2

Data Definition: Date Picker

Form Label (Field Label): Forecast 2 Finish

of Characters: Not applicable

Where to use it: Schedule Activity Attribute Forms

Use this element for: Entering the forecast finish date of an activity.

The user can also define a formula in uDesigner to calculate this date.

uuu_activity_fc_duration_2

Data Definition: Decimal Amount

Form Label (Field Label): Forecast 2 Duration

of Characters: Not applicable

Where to use it: Schedule Activity Attribute Forms

Use this element for: Viewing the forecast duration of an activity.

This value is calculated based on the **Forecast 2 Start date** and the **Forecast 2 Finish date**.
Read-only field.

uuu_activity_id

Data Definition: Integer Amount

Form Label (Field Label): Activity ID

of Characters: Not applicable

Where to use it:

- ▶ Schedule Activity Attribute Forms
- ▶ Schedule Sheets

Use this element for: Viewing a system-generated ID for activities.

Use this element while importing or exporting activities from a schedule sheet.

uuu_activity_level

Data Definition: Integer Amount

Form Label (Field Label): Level

of Characters: Not applicable

Where to use it: Schedule Activity Attribute Forms

Use this element for: Showing the activity level in the hierarchy of the Schedule Sheet.

The field is automatically populated when the activity is placed on the Schedule Sheet.

uuu_activity_name

Data Definition: SYS Short Description Text 120

Form Label (Field Label): Activity Name

of Characters: 120

Where to use it:

- ▶ Schedule Activity Attribute Forms
- ▶ Schedule Sheets

Use this element for: Entering the name of a schedule activity.

uuu_activity_per_1

Data Definition: Decimal Amount

Form Label (Field Label): Activity Percent 1

of Characters: Not applicable

Where to use it: Schedule Activity Attribute Forms

Use this element for: Entering a percent value at the activity level.

This is an editable field and value of this field gets calculated as a weighted average of the resource cost (if there are resources).

The weighted average is based on the **uuu_resc_assign_per_1** data element.

The user can define a formula in uDesigner to calculate this amount, or enter an amount

uuu_activity_predecessors

Data Definition: SYS Medium Name

Form Label (Field Label): Predecessors

of Characters: 64

Where to use it: Schedule Activity Attribute forms

Use this element for: Viewing a comma-separated list of predecessor IDs.

If this data element is marked as Editable, users can enter dependencies in the Predecessors column of a schedule sheet, or in the Predecessors field on the General tab of the Activity Properties.

uuu_activity_resources

Data Definition: SYS Description Text 500

Form Label (Field Label): Assigned Resources

of Characters: 500

Where to use it:

- ▶ Schedule Activity Attribute Forms
- ▶ Schedule Sheets

Use this element for: Viewing a list of personnel currently assigned to an activity.

This field is updated whenever resources are assigned or removed from the activity.

uuu_activity_status

Data Definition: SYS Activity Status

Form Label (Field Label): Status

of Characters: Not applicable

Where to use it: Schedule Activity Attribute forms

Use this element for: Selecting the status of an activity that is part of a “scope management” schedule.

The statuses for these activities are predefined and cannot be modified. The statuses are:

- ▶ **Not Started**
- ▶ **In Progress**
- ▶ **Complete**
- ▶ **Not Applicable**

When an activity is part of a scope management schedule, this is read-only; otherwise, it becomes a pull-down menu from which the user must choose the status.

Note: The **Not Applicable** status is available only for scope management activities that have been switched to manual mode. A **Not Applicable** status will retain existing dates and duration.

uuu_activity_CBS_codes

Data Definition: SYS Description Text 500

Form Label (Field Label): CBS Codes

of Characters: 500

Where to use it: Schedule Activity Attribute forms

Use this element for: Viewing the CBS code associated with an activity.

This DE:

- ▶ Displays CBS code that were added to the CBS tab in the Activity Properties.
- ▶ Is always read-only and can be added as a schedule sheet column.

uuu_activity_work_hrs

Data Definition: Decimal Amount

Form Label (Field Label): Activity Work Hours

of Characters: Not applicable

Where to use it:

- ▶ Schedule Activity Attribute form
- ▶ Schedule sheet

Use this element for: Viewing or entering the calculated work hours when a person is assigned to an activity.

This field is automatically populated through the Resource Assignment tab of the Activity Attribute form.

The user can override the calculation and enter the hours directly onto the schedule sheet via the Activities Resource tab.

uuu_actual_duration

Data Definition: Decimal Amount

Form Label (Field Label): Actual Duration

of Characters: Not applicable

Where to use it: Schedule Activity Attribute forms

Use this element for: Viewing the actual duration of an activity that is part of a “scope management” schedule.

The value of this DE is calculated from the actual start and finish dates.

uuu_actual_finish_date

Data Definition: Date Picker

Form Label (Field Label): Actual Finish Date

of Characters: Not applicable

Where to use it: Schedule Activity Attribute forms

Use this element for: Selecting the actual finish date of an activity that is part of a “scope management” schedule.

uuu_actual_start_date

Data Definition: Date Picker

Form Label (Field Label): Actual Start Date

of Characters: Not applicable

Where to use it: Schedule Activity Attribute forms

Use this element for: Selecting the actual start date of an activity that is part of a “scope management” schedule.

uuu_auto_update_activity

Data Definition: SYS Checkbox

Form Label (Field Label): Auto-Update Activity Data

of Characters: Not applicable

Where to use it: Schedule Activity Attribute Forms

Use this element for: Turning on/off the auto-updating of actual start and finish dates for an activity that is part of a “scope management” schedule.

If you use this element, users can take manual control over an activity at any time by deselecting the **Auto-update Activity Data** check box on the activity's **Properties** window at runtime.

If the users do this, then:

- ▶ Unifier retains the link to the BP record (if any) and the activity's current status.
- ▶ Unifier continues to enforce the Scope Management update rules for the activity's status; however, the user must manually attach the status to the activity.
- ▶ Unifier does **not** track the activity's actual start and finish dates and completion. The user must manually enter these dates.

The user can return the activity to Scope Management mode by selecting the **Auto-update Activity Data** check box on the activity's **Properties** window. To resume Scope Management, Unifier:

- ▶ Updates the BP record status for the activity
- ▶ Checks the record for “complete” conditions
- ▶ Sets the appropriate status of the activity (either In Progress or Complete)

If the activity is not yet linked to a BP, Unifier checks internal scope conditions. If:

- ▶ Conditions are satisfied, then the system launches the appropriate BP and sets the activity's status to In Progress.
- ▶ Conditions are not satisfied, then the system sets the activity's status to Not Started.

uuu_duration

Data Definition: Decimal Amount

Form Label (Field Label): Duration

of Characters: Not applicable

Where to use it:

- ▶ Schedule Activity Attribute Forms
- ▶ Schedule Sheets

Use this element for: Entering an activity's duration.

uuu_duration_baseline

Data Definition: Decimal Amount

Form Label (Field Label): Baseline Duration

of Characters: Not applicable

Where to use it:

- ▶ Schedule Activity Attribute forms
- ▶ Schedule Sheets

Use this element for: Displaying the baseline duration of a project on the schedule sheet.

This element produces an automatic formula of: **duration = finish - start**.

This is one element of a set that includes **uuu_start_baseline** and **uuu_finish_baseline**. You must include all 3 of these elements on the form for the baseline function to work correctly.

As the designer, you can assign a name to the baseline; for example "Baseline Electrical."

uuu_duration_baseline[1...10]

Data Definition: Decimal Amount

Form Label (Field Label): Baseline Duration

of Characters: Not applicable

Where to use it:

- ▶ Schedule Activity Attribute forms
- ▶ Schedule Sheets
- ▶ Resource Assignment Attribute Forms

Use this element for: Displaying the baseline duration of a project **phase** on a schedule sheet.

This element produces an automatic formula of: **duration = finish - start**.

This is one element of a set that includes **uuu_start_baseline[1...10]** and **uuu_finish_baseline[1...10]**. You must include all 3 of these elements on the form for the baseline function to work correctly.

uuu_duration_type

Data Definition: SYS Duration Type

Form Label (Field Label): Duration Type

of Characters: Not applicable

Data Set values:

- ▶ Fixed Duration
- ▶ Fixed Units
- ▶ Fixed Units/Time

Where to use it:

The Manual Activity attribute form, using the custom data elements.

Use this element for:

This data element can be added as part of formula definition, but the user cannot define formula based on this data element.

Additional information:

The data element

The system does not allow auto-populate or reverse auto-populate definition for **uuu_duration_type**.

The **uuu_duration_type** data element cannot be part of trigger element.

At runtime, **uuu_duration_type** data element will be read-only on the form, with default value set as "Fixed Duration." The "Duration Type" cannot be updated to any other duration types, at runtime and at the activity level.

uuu_early_finish

Data Definition: Date Picker

Form Label (Field Label): Early Finish Date

of Characters: Not applicable

Where to use it:

- ▶ Schedule Activity Attribute Forms
- ▶ Schedule Sheets

Use this element for: Viewing how soon an activity can be completed without impacting dependencies.

The value of this DE is calculated as a result of the critical path calculation.

uuu_early_start

Data Definition: Date Picker

Form Label (Field Label): Early Start Date

of Characters: Not applicable

Where to use it:

- ▶ Schedule Activity Attribute Forms
- ▶ Schedule Sheets

Use this element for: Viewing how soon an activity can be started without impacting dependencies.

The value of this DE is calculated as a result of the critical path calculation.

uuu_estimated_duration

Data Definition: Decimal Amount

Form Label (Field Label): Estimated Duration

of Characters: Not applicable

Where to use it: Schedule Activity Attribute forms

Use this element for: Viewing the estimated duration of an activity that is part of a “scope management” schedule.

The value of this DE is calculated from the estimated start and finish dates.

uuu_estimated_finish_date

Data Definition: Date Picker

Form Label (Field Label): Estimated Finish Date

of Characters: Not applicable

Where to use it: Schedule Activity Attribute forms

Use this element for: Selecting the estimated finish date of an activity that is part of a “scope management” schedule.

uuu_estimated_start_date

Data Definition: Date Picker

Form Label (Field Label): Estimated Start Date

of Characters: Not applicable

Where to use it: Schedule Activity Attribute forms

Use this element for: Selecting the estimated start date of an activity that is part of a “scope management” schedule.

uuu_filtered_groups

Data Definition: Filtered Group

Form Label (Field Label): Filtered Group

of Characters: Not applicable

Where to use it: Schedule Activity Attribute forms

Use this element for: Filtered group choice to enforce activity-level editing permissions assigned by group.

The value of this DE is filtered list of groups that have cell-level permissions and restrictions on what they can edit on the sheet.

This DE:

- ▶ Allows each activity to be assigned a group.
- ▶ Can be marked required and editable.

- ▶ Cannot be added to a hidden block.
- ▶ Cannot be auto-populated or reverse auto-populated (RAP).

uuu_finish

Data Definition: Date Picker

Form Label (Field Label): Finish Date

of Characters: Not applicable

Where to use it:

- ▶ Schedule Activity Attribute Forms
- ▶ Schedule Sheets

Use this element for: Entering an activity's finish date.

uuu_finish_baseline

Data Definition: Date Picker

Form Label (Field Label): Baseline Finish

of Characters: Not applicable

Where to use it:

- ▶ Schedule Activity Attribute forms
- ▶ Schedule Sheets
- ▶ Resource Assignment Attribute Forms

Use this element for: Display the baseline finish date of a project on a schedule sheet.

This is one element of a set that includes:

- ▶ **uuu_start_baseline**
- ▶ **uuu_duration_baseline**
- ▶ **uuu_total_cost_baseline**

You must include all of these elements on the form for the baseline function to work correctly.

uuu_finish_baseline[1...10]

Data Definition: Date Picker

Form Label (Field Label): Baseline[1...10] Start

of Characters: Not applicable

Where to use it:

- ▶ Schedule Activity Attribute forms
- ▶ Schedule Sheets
- ▶ Resource Assignment Attribute Forms

Use this element for: Displaying the baseline finish date of a project **phase** on a schedule sheet.

This is one element of a set that includes:

- ▶ **uuu_start_baseline[1...10]**
- ▶ **uuu_duration_baseline[1...10]**

Note: You must include all 3 of these elements on the form for the baseline function to work correctly.

As the designer, you can assign a name to the baseline; for example “Baseline Electrical.”

uuu_fixed_cost

Data Definition: Currency Amount

Form Label (Field Label): Fixed Cost

of Characters: Not applicable

Where to use it:

- ▶ Schedule Activity Attribute Forms
- ▶ Schedule Sheets

Use this element for: Entering the fixed cost of an activity.

The value in this data element will be rolled up to the cost sheet if that activity is associated with a CBS code.

uuu_flag_complete

Data Definition: SYS Check Box

Form Label (Field Label): Mark Activity as Complete

of Characters: Not applicable

Where to use it:

- ▶ Schedule Activity Attribute Forms
- ▶ Schedule Sheets

Use this element for: Specifying that a scheduled activity is complete.

uuu_flag_milestone

Data Definition: SYS Check Box

Form Label (Field Label): Show as Milestone

of Characters: Not applicable

Where to use it:

- ▶ Schedule Activity Attribute Forms
- ▶ Schedule Sheets

Use this element for: Specifying that a scheduled activity is a milestone.

uuu_float

Data Definition: Decimal Amount

Form Label (Field Label): Float

of Characters: Not applicable

Where to use it:

- ▶ Schedule Activity Attribute Forms
- ▶ Schedule Sheets

Use this element for: Viewing the float (slack) value for each activity. This is calculated as a result of the critical path calculation.

uuu_labor_cost

Data Definition: Currency Amount

Form Label (Field Label): Labor Cost

of Characters: Not applicable

Where to use it: Schedule Activity Attribute Forms

Use this element for: Entering the total labor cost, based on the resource assignment and resource rates. Unifier automatically updates when resources are assigned to an activity.

uuu_late_finish

Data Definition: Date Picker

Form Label (Field Label): Late Finish Date

of Characters: Not applicable

Where to use it:

- ▶ Schedule Activity Attribute Forms
- ▶ Schedule Sheets

Use this element for: Specifying how late an activity can be completed without impacting dependencies. This is calculated as a result of the critical path calculation.

uuu_late_start

Data Definition: Date Picker

Form Label (Field Label): Late Start Date

of Characters: Not applicable

Where to use it:

- ▶ Schedule Activity Attribute Forms
- ▶ Schedule Sheets

Use this element for: Specifying how late an activity can be started without impacting dependencies. This is calculated as a result of the critical path calculation.

uuu_linked_bp_name

Data Definition: SYS Medium Name

Form Label (Field Label): Linked BP Name

of Characters: 64

Where to use it: Schedule Activity Attribute Forms

Use this element for: Displaying the name of the BP that was auto-created by an activity that is part of a “scope management” function.

uuu_linked_record_status

Data Definition: SYS Short Name

Form Label (Field Label): Record Status

of Characters: 8

Where to use it: Schedule Activity Attribute Forms

Use this element for: Displaying the status of the BP that was auto-created by an activity that is part of a “scope management” function.

uuu_non_labor_cost

Data Definition: Currency Amount

Form Label (Field Label): Non-Labor Cost

of Characters: Not applicable

Where to use it:

- ▶ Schedule Activity Attribute Forms
- ▶ Schedule Sheets

Use this element for: Entering the non-labor cost of an activity.

The value in this data element will be rolled up to a cost sheet if that activity is associated with a CBS code.

uuu_outline_code

Data Definition: SYS Short Description Text 250

Form Label (Field Label): Outline Code

of Characters: Not applicable

Where to use it:

- ▶ Schedule Activity Attribute Forms
- ▶ Schedule Sheets

Use this element for: Viewing the level of an activity within the schedule sheet.

The code will change as activities are added above or below or outside the or inside the activity. This is a read-only field.

uuu_resc_assign_amt

Data Definition: Currency Amount

Form Label (Field Label): Amount

of Characters: Not applicable

Where to use it: Resource Assignment Attribute Forms

Use this element for: Viewing or entering the amount or cost of the effort.

If the resource selected is hard booked, this field is read-only and the value is calculated automatically by multiplying Quantity (Qty) with Rate; otherwise, this data element is editable.

The user can enter a value in Unifier or create a formula in uDesigner to calculate the amount.

uuu_resc_assign_amt_bl

Data Definition: Currency Amount

Form Label (Field Label): Baseline Amount

of Characters: Not applicable

Where to use it: Resource Assignment Attribute Forms

Use this element for: Viewing the baseline information of an amount when user sets a baseline in Unifier.

The information in the Amount data element is copied into this data element. Read-only field.

uuu_resc_assign_amt_bl[1...10]

Data Definition: Currency Amount

Form Label (Field Label): Baseline Amount [1...10]

of Characters: Not applicable

Where to use it: Resource Assignment Attribute Forms

Use this element for: Viewing the baseline information of an amount when user sets a baseline in Unifier.

The information in the **Amount** data element is copied into this data element.

Read-only field.

uuu_resc_assign_compl_per

Data Definition: Decimal Amount

Form Label (Field Label): % Complete

of Characters: Not applicable

Where to use it: Resource Assignment Attribute Forms

Use this element for: Viewing resource percent complete of the effort.

The value of this data element is calculated using Progress Quantity / Quantity (Qty).

Read-only field.

uuu_resc_assign_earn_amt

Data Definition: Currency Amount

Form Label (Field Label): Earned Amount

of Characters: Not applicable

Where to use it: Resource Assignment Attribute Forms

Use this element for: Viewing or entering the calculated earned progress in form of an amount.

The user can define a formula in uDesigner to calculate the earned amount, or enter an amount.

uuu_resc_assign_earn_prog

Data Definition: Decimal Amount

Form Label (Field Label): Earned Progress

of Characters: Not applicable

Where to use it: Resource Assignment Attribute Forms

Use this element for: Viewing or entering the earned progress of resource effort.

If the earned progress is calculated in Unifier based on the Budget and Progress Setup, this field is read-only; otherwise, this data element is editable.

uuu_resc_assign_etc_amt

Data Definition: Decimal Amount

Form Label (Field Label): ETC Amount

of Characters: Not applicable

Where to use it: Resource Assignment Attribute Forms

Use this element for: Entering the additional effort to complete work in the form of an amount.
The user can define a formula in uDesigner to calculate the ETC Amount.

uuu_resc_assign_etc_qty

Data Definition: Decimal Amount

Form Label (Field Label): ETC

of Characters: Not applicable

Where to use it: Resource Assignment Attribute Forms

Use this element for: Entering additional effort to complete work assigned to a resource.
The user can define a formula in uDesigner to calculate this value, or enter a value.

uuu_resc_assign_per_1

Data Definition: Decimal Amount

Form Label (Field Label): Resource Percent 1

of Characters: Not applicable

Where to use it: Resource Assignment Attribute Forms

Use this element for: Entering the resource percent value.
The user can define a formula in uDesigner to calculate the percent value, or enter a value.

uuu_resc_assign_prog_qty

Data Definition: Decimal Amount

Form Label (Field Label): Progress Quantity

of Characters: Not applicable

Where to use it: Resource Assignment Attribute Forms

Use this element for: Entering the progress with respect to effort (Quantity).
The value entered determines the progress of the resource.
The user can define a formula in uDesigner to calculate the amount, or enter an amount.

uuu_resc_assign_qty

Data Definition: Decimal Amount

Form Label (Field Label): Quantity (Qty)

of Characters: Not applicable

Where to use it: Resource Assignment Attribute Forms

Use this element for: Entering the effort of the resource.

uuu_resc_assign_qty_bl

Data Definition: Decimal Amount

Form Label (Field Label): Baseline Quantity

of Characters: Not applicable

Where to use it: Resource Assignment Attribute Forms

Use this element for: Viewing baseline information of effort or Quantity (Qty) when the user sets a baseline in Unifier.

Information in the Quantity (Qty) data element is copied into this data element.

Read-only field.

uuu_resc_assign_rate

Data Definition: Decimal Amount

Form Label (Field Label): Rate

of Characters: Not applicable

Where to use it: Resource Assignment Attribute Forms

Use this element for: Viewing or entering the unit rate of the effort.

If the selected resource is hard booked, this value is populated based on the rate at which the resource is booked on the project, and is read-only; otherwise, this data element is editable.

The user can enter a value or define a formula in uDesigner to calculate the rate.

uuu_resc_assign_rate_bl

Data Definition: Decimal Amount

Form Label (Field Label): Baseline Rate

of Characters: Not applicable

Where to use it: Resource Assignment Attribute Forms

Use this element for: Viewing the baseline information of the effort's rate when the user sets a baseline in Unifier.

Information in the Rate data element is copied into this data element.

Read-only field.

uuu_resc_assign_untper

Data Definition: Decimal Amount

Form Label (Field Label): % Units

of Characters: Not applicable

Where to use it: Resource Assignment Attribute Forms

Use this element for: Viewing or entering the percentage of effort.

This field is required when a Hard Booked Resource is added.

For non-Hard Booked Resources, this field defaults to 100%, but it is editable.

uuu_resc_assign_untper_bl

Data Definition: Decimal Amount

Form Label (Field Label): Baseline% Units

of Characters: Not applicable

Where to use it: Resource Assignment Attribute Forms

Use this element for: Viewing the baseline information of % units when user sets a baseline in Unifier.

Information in % Units data element is copied into this data element.

Read-only field.

uuu_resc_assign_uom

Data Definition: Unit of Measure

Field Label: UOM

of Characters: Not applicable

Where to use it: Resource Assignment Attribute Forms

Use this element for: Selecting the unit of measure associated with the effort. For example, if the Resource Type is Manhours, the unit of measure is hours.

uuu_resc_assign_uom_bl

Data Definition: Unit of Measure

Form Label (Field Label): Baseline UOM

of Characters: Not applicable

Where to use it: Resource Assignment Attribute Forms

Use this element for: Viewing the baseline information of the effort's unit of measure when the user sets a baseline in Unifier.

Information in the UOM data element is copied into this data element.

Read-only field.

uuu_resc_code

Data Definition: SYS Short Description Text 120

Form Label (Field Label): Resource Code

of Characters: 120

Where to use it:

- ▶ Resource Attribute forms
- ▶ Resource Assignment Attribute Forms

Use this element for: Viewing or entering the resource code of the assigned resource.

If a Hard Booked Resource is selected, this field is populated with the code of the selected resource; otherwise, this field is editable and the user must enter a value manually.

uuu_resc_name

Data Definition: SYS Short Description Text 120

Form Label (Field Label): Resource Name

of Characters: 120

Where to use it:

- ▶ Resource Attribute forms
- ▶ Resource Assignment Attribute Forms

Use this element for:

- ▶ Entering the name of the person on whom to report time.
- ▶ Viewing or entering the name of the assigned resource.

If a Hard Booked Resource is selected, this field is populated and is read only; otherwise, this field is editable and the user must enter a value manually.

uuu_resc_picker

Data Definition: Resource Picker

Form Label (Field Label): Resource Picker

of Characters: Not applicable

Where to use it:

- ▶ Detail form of Time Sheet and Booking business processes.
- ▶ Resource Assignment Attribute Forms.

Note: Do not use this picker on configurable manager attribute forms.

Use this element for:

- ▶ Selecting a resource to report on or assign.
- ▶ Selecting a resource that is booked to a project.

This picker always opens in “Find” mode and requires the user to enter at least one search criteria, such as a name or a skill, to narrow the field of names to choose from.

This picker should be used to allow users to select hard booked resources.

For timesheet BPs, users will use this picker to select the personnel to report time on.

At runtime, the picker will default to read-only mode and show the current user's name, as Unifier assumes the user will be reporting his or her own time; however, depending on permissions, the picker can be editable in order to allow others, such as project managers, to complete time sheets on behalf of other workers.

uuu_resc_sun_capacity uuu_resc_sat_capacity

Data Definition: Integer Amount

Form Label (Field Label): (day) Capacity (Hrs.)

of Characters: Not applicable

Where to use it: Resource Attribute forms

Use this element for: Entering the number of hours a resource can work on that day.

Use these elements if resources work differing hours on each day.

Resource capacity impacts the resource's availability for booking. These elements, together, are used to calculate the weekly hours that a resource is available. With these values, Unifier will calculate and display the resource's available hours on the Availability sheet.

Note: If you implement resource capacity calculating, you must place all seven of these elements on the attribute form.

uuu_resc_type

Data Definition: Resource Type

Form Label (Field Label): Resource Type

of Characters: Not applicable

Where to use it: Resource Assignment Attribute Forms

Use this element for: Selecting a resource type.

This system-defined data element is based on a system defined data definition called Resource Type.

The data set values for this data definition can be defined in Unifier.

By default a new option will be added called Hard Booked Resources to the data set values of this data definition.

This data element is used to identify whether the resource assigned is a Hard Booked resource or a resource category (for example, Manhours or Equipment) created by the user.

uuu_role_name

Data Definition: Short Description Text 120

Form Label (Field Label): Role Name

of Characters: 120

Where to use it:

- ▶ Role Attribute Forms
- ▶ Resource Assignment Attribute Forms

Use this element for:

- ▶ Identifying the type of work to be performed for a scheduled activity.
- ▶ Viewing the role of the resource assigned to the activity.

If a hard booked resource is selected, then this field is populated.

Read-only field.

uuu_start

Data Definition: Date Picker

Form Label (Field Label): Start Date

of Characters: Not applicable

Where to use it:

- ▶ Schedule Activity Attribute forms
- ▶ Schedule Sheets

Use this element for: Displaying the baseline start date of a project on a schedule sheet.

This is one element of a set that includes **uuu_finish_baseline** and **uuu_duration_baseline**.

You must include all 3 of these elements on the form for the baseline function to work correctly.

uuu_start_baseline

Data Definition: Date Picker

Form Label (Field Label): Baseline Start

of Characters: Not applicable

Where to use it:

- ▶ Schedule Activity Attribute forms

‣ Schedule Sheets

Use this element for: Displaying the baseline start date of a project on a schedule sheet.

This is one element of a set that includes **uuu_finish_baseline** and **uuu_duration_baseline**.

You must include all 3 of these elements on the form for the baseline function to work correctly.

uuu_start_baseline[1...10]

Data Definition: Date Picker

Form Label (Field Label): Baseline [1...10] Start

of Characters: Not applicable

Where to use it:

- Schedule Activity Attribute forms
- Schedule Sheets
- Resource Assignment Attribute Forms

Use this element for: Specifying the baseline start date of a project phase on a schedule sheet.

This is one data element of a set that includes:

- **uuu_finish_baseline[1...10]**
- **uuu_duration_baseline[1...10]**
- **uuu_total_cost_baseline[1...10]**

You must include all of these elements on the form for the baseline function to work correctly.

As the designer, you can assign a name to the baseline; for example “Baseline Electrical.”

uuu_tag

Data Definition: Schedule Default Tag

Form Label (Field Label): Tag

of Characters: 20

Where to use it:

Use this element for: Connecting schedule sheet activities with business processes, shells, spaces in the Space Manager, and configurable manager objects.

When this element is connected from the sheet to the business process, and so on, users can view key activity dates, such as milestones, on forms without having to open the schedule sheet.

This element creates a “Tags” column on the schedule sheet. In this column on an activity row of the schedule, users must select the linked element from the business process, shell, space, or configurable manager that will display activity dates on the form.

uuu_total_cost

Data Definition: Currency Amount

Form Label (Field Label): Total Cost

of Characters: Not applicable

Where to use it: Schedule Activity attribute forms

Use this element for: Entering or calculating the total cost of an activity.

This data element can be calculated by specifying a formula for the field: Labor Cost + Non-Labor Cost + Fixed Cost.

uuu_total_cost_baseline[1...10]

Data Definition: Currency Amount

Form Label (Field Label): Currency Amount

of Characters: Not applicable

Where to use it:

- ▶ Schedule Activity Attribute forms
- ▶ Schedule Sheets
- ▶ Resource Assignment Attribute Forms

Use this element for: Specifying the baseline cost of a project *phase* on a schedule sheet.

This is one element of a set that includes **uuu_finish_baseline[1...10]**, **uuu_duration_baseline[1...10]**, and **uuu_total_cost_baseline[1...10]**.

You must include all of these elements on the form for the baseline function to work correctly.

Shell Manager DEs

Use the following data elements for creating the business processes and attribute forms for the **Shell Manager**.

uuu_administrator

Data Definition: User Picker

Form Label (Field Label): Administrator

of Characters: Not applicable

Where to use it:

- ▶ Configurable shell attribute forms
- ▶ Shell attribute form
- ▶ Shell detail form

- ▶ Upper or detail form of a Project/Shell Creation BP

Note: Do not use this picker on configurable manager attribute forms.

Use this element for: Selecting the administrator of a shell.

uuu_au_setup_picker

Data Definition: SYS String

Form Label (Field Label): Auto-update Status Setup

of Characters: Not applicable

Where to use it:

- ▶ Shell detail form
- ▶ Project details

Use this element for: Specifying an automatic status update setup under the Company Workspace. These setups are defined by the administrator.

uuu_int_schedule_type

Data Definition: SYSP6ScheduleType

Form Label (Field Label): Schedule Type (Drop-down)

of Characters: Not applicable

Where to use it: Shell attribute form

Use this element for: Shell instances that are required to be integrated with P6 (CBS Single or Multiple type Shells).

This DE is:

- ▶ Not required for Shell attribute forms that are not integrated with P6.
- ▶ "Read-only" when used on a Shell attribute form of a CBS (Single or Multiple Instance).

The value for this element originates from P6 and User cannot update the value via CSV or WebServices.

uuu_location

Data Definition: Location Picker

Form Label (Field Label): Location

of Characters: Not applicable

Where to use it: Shell detail form; cannot be used on an anchor shell (a single-instance shell)

Note: Do not use this picker on configurable manager attribute forms.

Use this element for: Specifying the hierarchy between shells.

From this picker, the user picks the parent shell under which a sub-shell should be created.

This element will display the complete path location of the shell.

uuu_proj_template_picker

Data Definition: Project Template Picker

Form Label (Field Label): Project Templates

of Characters: Not applicable

Where to use it: Upper or detail form of a Project/Shell Creation BP

Use this element for: Choosing a template for an auto-created project.

You must include this element if you use the **uuu_project_creator** element although it does not need to be on the same form.

uuu_proj_address_1

Data Definition: SYS Medium Name

Form Label (Field Label): Address 1

of Characters: Not applicable

Where to use it: Upper or detail form of a Project/Shell Creation BP

Note: Use this element for the project address only; not for billing, shipping, and so on, addresses.

Use this element for: Entering the street address of the project.

You must include this element if you use the **uuu_project_creator** element, although it does not need to be on the same form.

uuu_proj_address_2

Data Definition: SYS Medium Name

Form Label (Field Label): Address 2

of Characters: Not applicable

Where to use it: Upper or detail form of a Project/Shell Creation BP

Note: Use this element for the project address only; not for billing, shipping, and so on, addresses.

Use this element for: Entering address information for the project.

You must include this element if you use the **uuu_project_creator** element although it does not need to be on the same form.

uuu_proj_address_3

Data Definition: SYS Medium Name

Form Label (Field Label): Address 3

of Characters: Not applicable

Where to use it: Upper or detail form of a Project/Shell Creation BP

Note: Use this element for the project address only; not for billing, shipping, and so on, addresses.

Use this element for: Entering additional address information for the project.

You must include this element if you use the **uuu_project_creator** element although it does not need to be on the same form.

uuu_proj_city

Data Definition: SYS Medium Name

Form Label (Field Label): City

of Characters: Not applicable

Where to use it: Upper or detail form of a Project/Shell Creation BP

Note: Use this element for the project address only; not for billing, shipping, and so on, addresses.

Use this element for: Entering the city line of the project address.

You must include this element if you use the **uuu_project_creator** element although it does not need to be on the same form.

uuu_proj_country

Data Definition: SYS Country

Form Label (Field Label): Country

of Characters: Not applicable

Where to use it: Upper or detail form of a Project/Shell Creation BP

Note: Use this element for the project address only; not for billing, shipping, and so on, addresses.

Use this element for: Entering the country line of the project address.

You must include this element if you use the **uuu_project_creator** element although it does not need to be on the same form.

uuu_proj_fax

Data Definition: SYS Medium Name

Form Label (Field Label): Fax

of Characters: Not applicable

Where to use it: Upper or detail form of a Project/Shell Creation BP

Use this element for: Entering the project fax number.

You must include this element if you use the **uuu_project_creator** element although it does not need to be on the same form.

uuu_proj_phone

Data Definition: SYS Medium Name

Form Label (Field Label): Phone

of Characters: Not applicable

Where to use it: Upper or detail form of a Project/Shell Creation BP

Use this element for: Entering the project phone number.

You must include this element if you use the **uuu_project_creator** element although it does not need to be on the same form.

uuu_proj_state

Data Definition: SYS Medium Name

Form Label (Field Label): State

of Characters: Not applicable

Where to use it: Upper or detail form of a Project/Shell Creation BP

Note: Use this element for the project address only; not for billing, shipping, and so on, addresses.

Use this element for: Entering the state line of the project address.

You must include this element if you use the **uuu_project_creator** element although it does not need to be on the same form.

uuu_proj_zip

Data Definition: SYS Medium Name

Form Label (Field Label): Zip

of Characters: Not applicable

Where to use it: Upper or detail form of a Project/Shell Creation BP

Note: Use this element for the project address only; not for billing, shipping, and so on, addresses.

Use this element for: Entering the zip code of the project address.

You must include this element if you use the **uuu_project_creator** element although it does not need to be on the same form.

uuu_project_creator

Data Definition: Project Picker

Form Label (Field Label): Created Project

of Characters: Not applicable

Where to use it: Upper or detail form of a Project/Shell Creation BP

Use this element for: Auto-creating a project from a company-level Project/Shell Creation BP.

If you use this element on a form, you cannot use a **uuu_shell_creator** element.

This element will create a project, even if the field is hidden.

uuu_project_start_date

Data Definition: Date Only Picker

Form Label (Field Label): Project Start Date

of Characters: Not applicable

Where to use it: Shell attribute form

Use this element for: Specifying the project start date.

This data element interacts with schedule sheet properties, in that if this data element is added to the shell attribute form, the Manual and Shell Attribute radio buttons are active for the master schedule sheet in the Schedule Manager for the CBS shell (provided no activity has started on the sheet). These buttons allow users to specify whether the Schedule Start Date should be set manually, or automatically populate from the Project Start Date on the shell attribute form. For non-master schedule sheets, the choice is always Manual, and Shell Attribute is not selectable.

If the user selects the Manual radio button, a Schedule Start Date can be selected.

If the user selects Shell Attribute radio button, the Schedule Start Date automatically populates from the Project Start Date specified on the General tab of the shell properties.

uuu_record_last_update_date

Data Definition: Date Picker

Form Label (Field Label): Record Last Update Date

of Characters: Not applicable

Where to use it:

- ▶ Upper form or log of any business process
- ▶ Shell attribute form
- ▶ Shell log
- ▶ Space or Level detail form or log
- ▶ Unifier Mobile

Use this element for: Specifying the date and time on which the record was last updated.

Updates can include changes that occur due to auto-population, integration, or any other change to the business process, including adding or removing attachments and general comments.

This data element is populated using the system date.

It is recommended that you place this field on the:

- ▶ Shell attribute form to track changes to the shell.
- ▶ Upper form and log of business processes that are enabled for the Self-Service Portal.

uuu_shell_creator

Data Definition: Shell Picker

Form Label (Field Label): Created Shell

of Characters: Not applicable

Where to use it: Upper or detail form of a Project/Shell Creation BP

Use this element for: Auto-creating a shell from a company-level or shell-level Project/Shell Creation BP.

If you use this element on a form, you cannot use a **uuu_project_creator** element.

This element will create a shell, even if the field is hidden.

uuu_shell_image

Data Definition: Image Picker

Form Label (Field Label): Image

of Characters: Not applicable

Where to use it: Upper or detail form of a Project/Shell Creation BP

Use this element for: Picker for selecting images to display on the shell page.

When the field value is passed to the project or shell, only the file location is passed.

uuu_shell_location

Data Definition: Shell Picker

Form Label (Field Label): Shell Location

of Characters: Not applicable

Where to use it: Upper or detail form of a Project/Shell Creation BP (unless it is a Line Item sub-type with a Shell and Sub-Shell classification, in which case, it should not be included on the detail form).

Use this element for: Specifying the parent location under which a new shell is to be auto-created.

You must include this element if you use the **uuu_shell_creator** element, although it does not need to be on the same form.

User-defined reports (UDRs) that contain this data element will show the entire path of the location.

uuu_shell_status

Data Definition: Integer

Form Label (Field Label): Status

of Characters: Not applicable

Where to use it:

- ▶ Shell detail form
- ▶ Upper or detail form of a Project/Shell Creation BP

Use this element for: Selecting the status of a shell at runtime. Valid values are:

- ▶ Inactive = 0
- ▶ View-Only
- ▶ Active = 1
- ▶ On-Hold = 2

uuu_shell_template_picker

Data Definition: Shell Template Picker

Form Label (Field Label): Shell Templates

of Characters: Not applicable

Where to use it: Upper or detail form of a Project/Shell Creation BP

Use this element for: Choosing a template for an auto-created shell.

You must include this element if you use the **uuu_shell_creator** element, although it does not need to be on the same form.

Space Manager DEs

Use the following data elements for creating the detail forms for the **Space Manager**.

uuu_record_last_update_date

Data Definition: Date Picker

Form Label (Field Label): Record Last Update Date

of Characters: Not applicable

Where to use it:

- ▶ Upper form or log of any business process
- ▶ Shell attribute form
- ▶ Shell log
- ▶ Space or Level detail form or log
- ▶ Unifier Mobile

Use this element for: Specifying the date and time on which the record was last updated.

Updates can include changes that occur due to auto-population, integration, or any other change to the business process, including adding or removing attachments and general comments.

This data element is populated using the system date.

It is recommended that you place this field on the:

- ▶ Shell attribute form to track changes to the shell.
- ▶ Upper form and log of business processes that are enabled for the Self-Service Portal.

uuu_rsv_overbook

Data Definition: SYS_Overbooking_Options

Form Label (Field Label): Allow Overbooking

of Characters: Not applicable

Where to use it:

- Asset classes
- Configurable manager attribute forms
- Document type Business Processes
- Space detail form

Use this element for:

- Specifying that the asset can be overbooked on reservation.
- Specifying that the object can be overbooked on reservation.
- Specifying that the space can be overbooked on reservation.

There are three overbooking options:

- Even if confirmed booking exists
- Only if tentative booking exists
- No overbooking

uuu_rsv_reservable

Data Definition: SYS_Yes_No

Form Label (Field Label): Allow Reservation

of Characters: Not applicable

Where to use it:

- Asset classes
- Configurable manager attribute forms
- Document type Business Processes
- Space detail form

Use this element for:

- Specifying that the asset can be reserved for use.
- Specifying that the object can be reserved for use.
- Specifying that the space can be reserved for use.

uuu_sp_area

Data Definition: Decimal Amount

Form Label (Field Label): Area

of Characters: Not applicable

Where to use it: Space detail form

Use this element for: Entering the area of a space.

uuu_sp_level_name

Data Definition: SYS Short Description Text 50

Form Label (Field Label): Level Name

of Characters: 50

Where to use it: Level detail form

Use this element for: Entering the name of a level or space.

uuu_sp_level_picker

Data Definition: Level Picker

Form Label (Field Label): Level Picker

of Characters: Not applicable

Where to use it: Space detail form

Use this element for: Selecting a level record.

Auto-populating Level information into Space attribute forms.

uuu_sp_uom

Data Definition: SYS Space Unit of Measure

Form Label (Field Label): Unit of Measure

of Characters: 128

Where to use it: Space detail form

Use this element for: Entering the unit of measure for space measurements

User Administration DEs

Use the following data elements for creating the detail forms for the **User Administration**.

uuu_user_company

Data Definition: SYS Medium Name

Form Label (Field Label): Company

of Characters: 64

Where to use it: User Administration form

Use this element for: Entering the company name of a user.

uuu_user_dateformat

Data Definition: SYS Date Format

Form Label (Field Label): Date Format

of Characters: Not applicable

Where to use it:

- ▶ User Administration form
- ▶ The Upper Form of Company-level (Simple or Line Item Business process) which has been marked as Master Vendor Business Process.

uDesigner option: Use this process as RFB master vendor list is checked.

Use this element for: Entering the date format of a user.

When placed in the Upper Form, this DE captures the date format of the Contact user for the Bidding Company in the Master Vendor list.

At runtime, while creating a record for the bidder, the Date Format of the bidder can be specified using this field. In this type of business process, the default value is editable.

Additional features:

This DE is not a mandatory field that must exist on the form.

When this DE exists in the form, the format of the due date, specified for the bid in bidder email notification, is based on the value selected in this field.

This DE:

- ▶ Can be marked as Editable/ Editable Required.
- ▶ Cannot be part of DDS which has it as a Master Data element on the Upper Form.
- ▶ The remaining behavior is the same as when the DE is placed in any other BP.
- ▶ At runtime, the list of all supported Date formats is displayed.

uuu_user_email

Data Definition: SYS Medium Name

Form Label (Field Label): E-Mail

of Characters: 64

Where to use it:

- ▶ Resource Attribute form
- ▶ User Administration form

Use this element for: Entering the email address of a resource or user.

uuu_user_fax

Data Definition: SYS Medium Name

Form Label (Field Label): Fax

of Characters: 64

Where to use it:

- ▶ Resource Attribute form
- ▶ User Administration form

Use this element for: Entering the fax number of a resource or user.

uuu_user_firstname

Data Definition: SYS Medium Name

Form Label (Field Label): First Name

of Characters: 64

Where to use it:

- ▶ Resource Attribute form
- ▶ User Administration form

Use this element for: Entering the first name of a resource or user.

uuu_user_homephone

Data Definition: SYS Medium Name

Form Label (Field Label): Home Phone

of Characters: 64

Where to use it:

- ▶ Resource Attribute form
- ▶ User Administration form

Use this element for: Entering the phone number of a resource or user.

uuu_user_lastname

Data Definition: SYS Medium Name

Form Label (Field Label): Last Name

of Characters: 64

Where to use it:

- ▶ Resource Attribute form
- ▶ User Administration form

Use this element for: Entering the last name of a resource or user.

uuu_user_loginname

Data Definition: SYS Medium Name

Form Label (Field Label): Login User Name

of Characters: 64

Where to use it: User Administration form

Use this element for: Entering the login name of a user.

uuu_user_mobilephone

Data Definition: SYS Medium Name

Form Label (Field Label): Mobile Phone

of Characters: 64

Where to use it:

- ▶ Resource Attribute form
- ▶ User Administration form

Use this element for: Entering the mobile phone number of a resource or user.

uuu_user_name

Data Definition: SYS Medium Name

Form Label (Field Label): Name

of Characters: Not applicable

Where to use it: User Administration form

Use this element for: Predefined to be a concatenation of the First Name and Last Name.

It is recommended that you:

- ▶ Add this field to a hidden block in the User Detail form and the View Profile form, and to expose it only in the User Picker and Find.
- ▶ Add this field to the View Profile form.
- ▶ Only expose it in the User Picker and Find.

uuu_user_pager

Data Definition: SYS Medium Name

Form Label (Field Label): Pager

of Characters: 64

Where to use it:

- ▶ Resource Attribute form
- ▶ User Administration form

Use this element for: Entering the pager number of a resource or user.

uuu_user_password

Data Definition: SYS Medium Name

Form Label (Field Label): Password

of Characters: 64

Where to use it: User Administration form

Use this element for: Entering the user password.

uuu_user_proxy

Data Definition: User Picker

Form Label (Field Label): Proxy Name

of Characters: Not applicable

Where to use it: User Administration form

Use this element for: Entering the proxy name of a user.

uuu_user_status

Data Definition: SYS User Status

Form Label (Field Label): Status

of Characters: Not applicable

Where to use it: User Administration form

Use this element for: Radio button to select the status of a user (Active, Inactive, or On-Hold).
By default, the status is Inactive.

uuu_user_timezone_pref

Data Definition: SYS User Time Zone

Form Label (Field Label): SYS User Time Zone

of Characters: Not applicable

Where to use it: User Administration form

Use this element for: Entering the time zone preference of a user.

Where to use it:

- ▶ User Administration form
- ▶ The Upper Form of Company-level (Simple or Line Item Business process) which has been marked as Master Vendor Business Process.

uDesigner option: Use this process as RFB master vendor list is checked.

Additional features: This DE is not a mandatory field that must exist on the form.

When placed in the Upper Form, this DE captures the time zone of the Contact user for the Bidding Company in the Master Vendor list.

When this DE exists in the form, the dates displayed are based on the user time zone, as specified in the field.

At runtime, while creating a record for the bidder, the Time Zone of the bidder can be specified using this field. In this type of business process, the default value is editable.

This DE:

- ▶ Can be marked as Editable/ Editable Required.
- ▶ Cannot be part of DDS which has it as a Master Data element on the Upper Form.
- ▶ The remaining behavior is the same as when the DE is placed in any other BP.
- ▶ At runtime, the list of all supported time zones is displayed.

uuu_user_title

Data Definition: SYS Medium Name

Form Label (Field Label): Title

of Characters: 64

Where to use it:

- ▶ Resource Attribute form
- ▶ User Administration form

Use this element for: Entering the title of a user or resource.

uuu_user_workphone

Data Definition: SYS Medium Name

Form Label (Field Label): Work Phone

of Characters: 64

Where to use it:

- ▶ Resource Attribute form

- ▶ User Administration form

Use this element for: Entering the work phone number of a user or resource.

Bluebeam DEs

Use the following data elements for creating the detail forms for the **Bluebeam**.

uuu_review_session_name

Data Definition: SYS Short Description Text 250

Form Label (Field Label): Session Name

of Characters: Not applicable

Where to use it:

- ▶ The Detail form of a business process design.
- ▶ This data element **cannot** be placed in the System defined tab
- ▶ It **cannot** be placed in the Detail/Attribute Form of any manager.
- ▶ This data element is available only for the following types of BPs that support multiple line item tabs -
 - ▶ Line Item type
 - ▶ Cost Type
 - ▶ Document Type
- ▶ This data element **can** be placed in the Upper form of the above-mentioned Business Processes, and BPs of type Simple and Text Type

Use this element for: This Data Element captures the name of the Bluebeam Review session that the file belonged to

Default Behavior in the above mentioned BPs: Always Read Only

Additional features:

- ▶ This is an optional field that may exist in the form
- ▶ For a given BP design, this field can only be placed in **one** of the Line Item tabs
- ▶ Cannot be marked as Editable/ Editable Required
- ▶ Cannot be part of any auto-population definition
- ▶ This DE cannot be part of any DDS
- ▶ This DE cannot be part of any formula or advanced formula, both as a source and destination
- ▶ Cannot be marked as a display element in the data picker definition

uuu_review_session_id

Data Definition: SYS Short Description Text 250

Form Label (Field Label): Session ID

of Characters: Not applicable

Where to use it:

- ▶ The Detail form of a business process design.
- ▶ This data element **cannot** be placed in the System defined tab
- ▶ It **cannot** be placed in the Detail/Attribute Form of any manager.
- ▶ This data element is available only for the following types of BPs that support multiple line item tabs -
 - ▶ Line Item type
 - ▶ Cost Type
 - ▶ Document Type
- ▶ This data element **can** be placed in the Upper form of the above-mentioned Business Processes, and BPs of type Simple and Text Type

Use this element for: This Data Element captures the ID of the Bluebeam Review session that the file belonged to

Default Behavior in the above mentioned BPs: Always Read Only

Additional features:

- ▶ This is an optional field that may exist in the form
- ▶ For a given BP design, this field can only be placed in **one** of the Line Item tabs
- ▶ Cannot be marked as Editable/ Editable Required
- ▶ Cannot be part of any auto-population definition
- ▶ This DE cannot be part of any DDS
- ▶ This DE cannot be part of any formula or advanced formula, both as a source and destination
- ▶ Cannot be marked as a display element in the data picker definition

uuu_review_file_name

Data Definition: SYS Short Description Text 250

Form Label (Field Label): File Name

of Characters: Not applicable

Where to use it:

- ▶ The Detail form of a business process design that has the Bluebeam Session related fields
- ▶ This data element **cannot** be placed in the System defined tab
- ▶ When this data element is added in the Upper form or detail form of any Business Process, it will behave like any other text field.

Use this element for: This Data Element captures the name of the file that was part of the Bluebeam Review session

Special Behavior in the Line Item tab which has Session Name & Session ID: Always Read Only

Additional features:

- ▶ This is an optional field that may exist in the form
- ▶ For a given BP design, this field can only be placed in **one** of the Line Item tabs
- ▶ Cannot be marked as Editable/ Editable Required
- ▶ Cannot be part of any auto-population definition
- ▶ This DE cannot be part of any DDS
- ▶ This DE cannot be part of any formula or advanced formula, both as a source and destination
- ▶ Cannot be marked as a display element in the data picker definition

uuu_review_revision_no

Data Definition: SYS Short Description Text 250

Form Label (Field Label): File Revision Number

of Characters: Not applicable

Where to use it:

- ▶ The Detail form of a business process design that has the Bluebeam Session related fields
- ▶ This data element **cannot** be placed in the System defined tab
- ▶ When this data element is added in the Upper form or detail form of any Business Process, it will behave like any other text field.

Use this element for: This Data Element captures the revision number of the file that was part of the Bluebeam Review session

Special Behavior in the Line Item tab which has Session Name & Session ID: Always Read Only

Additional features:

- ▶ This is an optional field that may exist in the form
- ▶ For a given BP design, this field can only be placed in **one** of the Line Item tabs
- ▶ Cannot be marked as Editable/ Editable Required
- ▶ Cannot be part of any auto-population definition
- ▶ This DE cannot be part of any DDS
- ▶ This DE cannot be part of any formula or advanced formula, both as a source and destination
- ▶ Cannot be marked as a display element in the data picker definition

uuu_review_pub_no

Data Definition: SYS Short Description Text 250

Form Label (Field Label): File Pub. Number

of Characters: Not applicable

Where to use it:

- ▶ The Detail form of a business process design that has the Bluebeam Session related fields
- ▶ This data element **cannot** be placed in the System defined tab
- ▶ When this data element is added in the Upper form or detail form of any Business Process, it will behave like any other text field.

Use this element for: This Data Element captures the pub number of the file that was part of the Bluebeam Review session

Special Behavior in the Line Item tab which has Session Name & Session ID: Always Read Only

Additional features:

- ▶ This is an optional field that may exist in the form
- ▶ For a given BP design, this field can only be placed in **one** of the Line Item tabs
- ▶ Cannot be marked as Editable/ Editable Required
- ▶ Cannot be part of any auto-population definition
- ▶ This DE cannot be part of any DDS
- ▶ This DE cannot be part of any formula or advanced formula, both as a source and destination
- ▶ Cannot be marked as a display element in the data picker definition

Other DEs (in Alphabetical Order: A-G)

Use the following Data Elements (DEs), presented alphabetically, for creating the attribute forms, Business Processes, and other entities.

uuu_address_code

Data Definition: SYS Description Text 500

Form Label (Field Label): Address Code

of Characters: 500

Where to use it: On upper forms and logs for these components:

- ▶ Shell attribute forms
- ▶ Line Item BPs
- ▶ Simple BPs
- ▶ Text BPs
- ▶ Document BPs
- ▶ Generic Cost BPs for project, company, or shell levels

Use this element for: Showing the map of a location for shells and certain business processes. If you use this element, the user must enter an exact address for map plotting.

You can build this field using a formula, or it can be a manual-entry field.

Note: If you are using a formula to create the code, be sure to include the delimiter between the fields; otherwise, the map might not appear.

To use coordinates to plot a map, see the **uuu_latitude** and **uuu_longitude** elements.

uuu_attachment_count

Data Definition: Integer Amount

Form Label (Field Label): Attachment

of Characters: N/A

Use it on:

- ▶ The upper form of a business process design to capture the count of attachments on the upper form of a record
- ▶ The detail form of a business process design to capture the count of attachments on the line item
- ▶ It cannot be placed in the Detail/Attribute Form of any manager
- ▶ It cannot be placed in the upper form of business process of type Document Type with folder
- ▶ This DE can be placed in any form of any business process other than the one mentioned above
- ▶ This DE can also be placed in the bidder detail form as well as in the bid comparison sheet

Use it for:

Capturing the total count of files in the respective form that it is placed in.

Behavior in the forms:

Always Read Only

Additional features:

- ▶ This is an optional field that may exist in the form
- ▶ For a given BP design, this field can be placed in a hidden block
- ▶ Cannot be marked as Editable/ Editable Required
- ▶ Cannot be marked for auto-population
- ▶ Can be source for RAP but not destination.
- ▶ Cannot be marked for 'Reset'.
- ▶ Can be an auto-population source for other data element.
- ▶ This DE cannot be part of any DDS .
- ▶ This DE can be part of a basic formula as a source.
- ▶ This DE can be part of an advanced formula as a source. This means that the value of this DE can be used in other fields.
- ▶ This DE cannot be a destination for a formula.

- ▶ Since this is of DD Integer Amount, this cannot be set as a display element in the data picker definition.
- ▶ This DE can be placed in the log layout of the design both for the Standard log and the Picker log .
- ▶ This DE can be used to define query conditions on data pickers or line item data pickers of their respective sources. Example: If the DE is placed in Action Items BP, a data picker that points to Action Items, can have this DE as a query parameter in the Data picker configuration.
- ▶ This DE should not be available to select as a display element for all Data Pickers, BP Pickers, Line item pickers and Line item data pickers.
- ▶ When added to an existing BP design which already has records with attachments, the DE value is not updated for existing records. The value is zero (0) for reports from any database or data views. However, when the existing records are opened in the user interface, the DE is calculated accordingly.

uuu_cmwbs_picker

Data Definition: P6 WBS Picker

Form Label (Field Label): WBS Picker

of Characters: Not applicable

Where to use it: Activity Attributes, Business Processes, and WBS Attributes

Use this element for: Selecting a unique WBS code.

uuu_cost_li_type

Data Definition: SYS Cost Line Item Type

Form Label (Field Label): Cost Line Item Type

of Characters: Not applicable

Where to use it:

- ▶ Standard Detail form of Base Commit / Change Commit BPs with SOV type = Summary Payment Applications, or
- ▶ Standard Detail form of Payment Application type BPs which will be linked to Base Commits of SOV type = Summary Payment Applications

Use this element for:

To define whether a line item will capture a lump sum amount, or a calculated amount as per unit cost/quantity.

If a line item is of Type = Unit Cost, when referenced on a Change Commit, it will automatically retrieve the Unit Cost as a read-only value on the Change Commit.

The default behavior, in the listed BPs, is read-only.

Place this DE on any Detail form of Summary SOV or Detail form of other types of BPs.

The DE is editable in all other BPs.

Additional information:

This is a mandatory field that has to exist on the form.

This field cannot be marked as Editable/Editable Required

Since this DE is Read-Only in the listed BPs, it cannot be part of DDS which has it as a Master Data element on these forms.

Note: The remaining behavior is like any other drop-down (Pull-down) DE.

uuu_costed_amt

Data Definition: Currency Amount

Form Label (Field Label): Costed Amount

of Characters: Not applicable

Where to use it: Standard Detail form of Base Commit / Change Commit BPs with SOV type = Summary Payment Applications.

Use this element for: Knowing how much of a Line Item amount has been allocated (Costed) to Cost Sheet cost codes.

The costed amount is calculated by system for unit cost and lump sum.

The default behavior, in the listed BPs, is read-only.

You can add this DE to any Detail form of Summary SOV type BPs, or to Detail forms of other types of BPs. This DE is editable in all other BPs.

Additional information:

In the listed BPs, this DE is populated by system as sum of amount DE, from the distribution detail lines below a Summary Line Item.

This DE is not available as a part of Dynamic Datasets.

This DE cannot be set as a formula, or auto-populate, because it is a read-only field.

Note: The remaining behavior is like any other Read Only Currency Amount DE.

uuu_costed_qty

Data Definition: Decimal Amount

Form Label (Field Label): Costed Quantity

of Characters: Not applicable

Where to use it: Standard Detail form of Base Commit / Change Commit BPs with SOV type = Summary Payment Applications.

Use this element for: Knowing how much of a Line Item quantity has been allocated (Costed) to Cost Sheet cost codes.

It is used when the Line Item type = Unit Price.

The default behavior, in the listed BPs, is read-only.

You can add this DE to any Detail form of Summary SOV type BPs, or to Detail forms of other types of BPs. This DE is editable in all other BPs.

Additional information:

In the listed BPs, this DE is populated by system as sum of **uuu_quantity DE**, from the distribution detail lines below a Summary Line Item.

This DE is not available as a part of Dynamic Datasets.

This DE cannot be set as a formula, or auto-populate, because it is a read-only field.

Note: The remaining behavior is like any other Read Only Decimal Amount DE.

uuu_not_costed_amt

Data Definition: Currency Amount

Form Label (Field Label): Not Costed Amount

of Characters: Not applicable

Where to use it: Standard Detail form of Base Commit / Change Commit BPs with SOV type = Summary Payment Applications.

Use this element for: Knowing how much of a Line Item amount has not been allocated (not Costed) to Cost Sheet cost codes.

The not costed amount is calculated by system for unit cost and lump sum.

The default behavior, in the listed BPs, is read-only.

You can add this DE to any Detail form of Summary SOV type BPs, or to Detail forms of other types of BPs. This DE is editable in all other BPs.

Additional information:

In the listed BPs, this DE is populated by system as Line Item Amount (Costed Amount).

This DE is not available as a part of Dynamic Datasets.

This DE cannot be set as a formula, or auto-populate, because it is a read-only field.

Note: The remaining behavior is like any other Read Only Currency Amount DE.

uuu_not_costed_qty

Data Definition: Decimal Amount

Form Label (Field Label): Not Costed Quantity

of Characters: Not applicable

Where to use it: Standard Detail form of Base Commit / Change Commit BPs with SOV type = Summary Payment Applications.

Use this element for: Knowing how much of a Line Item quantity has not been allocated (not Costed) to Cost Sheet cost codes.

It is used when the Line Item type = Unit Cost.

The default behavior, in the listed BPs, is read-only.

You can add this DE to any Detail form of Summary SOV type BPs, or to Detail forms of other types of BPs. This DE is editable in all other BPs.

Additional information:

In the listed BPs, this DE is populated by system as Line Item Quantity (Costed Quantity).

This DE is not available as a part of Dynamic Datasets.

This DE cannot be set as a formula, or auto-populate, because it is a read-only field.

Note: The remaining behavior is like any other Read Only Decimal Amount DE.

Other DEs (in Alphabetical Order: H-N)

Use the following Data Elements (DEs), presented alphabetically, for creating the attribute forms, Business Processes, and other entities.

uuu_integrated_with

Data Definition: SYS Short Description Text 255

Form Label (Field Label): Integrated With

of Characters: 255

Where to use it: The Data Elements (DEs) must be placed in a Shell Business Process, and the Activity Sheet must be located in the same Shell.

This Data element will always render as "Read-Only" on a Shell attribute form.

Use this element for: Identifying if a Shell instance is integrated or not, and if the Shell instance is integrated, with which application.

Add this DE to a CBS type Shell Attribute form if you want to integrate P6 with Unifier (integrate to Activity Sheet node, or to the P6 Summary Sheets node).

Additional information:

- ▶ Any CBS type Shell attribute form can be integrated with an external application.

- ▶ Even if this DE is not added, integration will continue to work. As Unifier projects continue to be integrated with external applications, this DE will store the name of each application as comma separated value.
- ▶ The only way to populate this DE is by way of integration.
- ▶ If this DE is populated, it means that the Shell instance is integrated. If this DE is not populated, it means that the Shell instance is not integrated.
- ▶ The value of this DE can be used to identify the various applications with which a given Project is linked.
- ▶ It is not mandatory to place this DE on a CBS type Shell Attribute form.
- ▶ The user cannot set this DD for Auto-Populate, or use it in a Dynamic Data Set (DDS).

uuu_int_internal_proj_id

Data Definition: Integer Amount

Form Label (Field Label): P6 Internal Project ID

of Characters: 32

Where to use it: The Data Elements (DEs) must be placed in a Shell Business Process, and the Activity Sheet must be located in the same Shell.

This Data element will always render as "Read-Only" on a Shell attribute form.

Use this element for: Bringing the P6 internal Project id to Unifier, once the integration is successful.

uuu_int_p6_project_id

Data Definition: SYS Short Description Text 32

Form Label (Field Label): P6 Project ID

of Characters: 32

Where to use it: The Data Elements (DEs) must be placed in a Shell Business Process, and the Activity Sheet must be located in the same Shell.

This Data element will always render as "Read-Only" on a Shell attribute form.

Use this element for: The user must place this DE on CBS type Shell attribute form, if the Unifier Project ID is different than the P6 Project ID.

Add this DE on a CBS type Shell Attribute form if the Unifier Project ID and the P6 Project ID do not match, so Gateway can establish a link between the two products.

Additional information

- ▶ This DE holds the ID of the P6 Project with which a Unifier Shell instance must be linked.
- ▶ The P6 Project ID cannot be greater than 20 characters.
- ▶ The user can use this DE if there is a need to integrate a Unifier Shell instance with P6, such that the Unifier Shell ID is not the same as P6 Project ID.
- ▶ The user can mark this DE as editable, required, or read-only.
- ▶ The user can update the Attribute form by way of Web Services.

- ▶ If the user creates a new Shell by way of "copy," the value of this DE will not be copied in the new Shell instance.
- ▶ Bulk editing is not available.
- ▶ All remaining behavior of this DE is the same as any text DE.

uuu_latitude

Data Definition: SYS Short Description Text 50

Form Label (Field Label): SYS Short Description Text 50

of Characters: 50

Where to use it: On upper forms and logs for:

- ▶ Shell Attribute forms
- ▶ Line Item BPs
- ▶ Simple BPs
- ▶ Text BPs
- ▶ Document BPs
- ▶ Generic Cost BPs for project, company, or shell level

Use this element for: Showing a location map of a shell or business process.

If you use this element, you must include the **uuu_longitude** element on the form.

On the form, this element is accompanied by a globe icon, which users can use to open a map and enter the address or coordinates of the shell or BP they want to see.

To use a direct address to plot a map, see the **uuu_address_code** element.

uuu_li_consolidated

Data Definition: Yes/No (drop-down list with a default value of No)

Form Label (Field Label): Consolidated

of Characters: Not applicable

Where to use it: Detail form section of any Business Process form

Use this element for: To capture whether or not a line item has been consolidated into a destination.

Default Behavior: Read-only

Additional Features:

Cannot be marked as Editable/Required on any form.

Always populated by the system.

Not mandatory on any form, but it can be placed on any Business Process detail form.

Note: The `uuu_li_consolidated` DE is not available to be added to the Upper Form of any Business Process.

`uuu_longitude`

Data Definition: SYS Short Description Text

Form Label (Field Label): Longitude

of Characters: 50

Where to use it: On upper forms and logs for:

- ▶ Shell Attribute forms
- ▶ Line Item BPs
- ▶ Simple BPs
- ▶ Text BPs
- ▶ Document BPs
- ▶ Generic Cost BPs for project, company, or shell level

Use this element for: Showing a location map of a shell or business process.

If you use this element, you must include the `uuu_latitude` element on the form.

To use a direct address to plot a map, see the `uuu_address_code` element.

`uuu_lse_accrual_amount`

Data Definition: Decimal Amount

Form Label (Field Label): Lease Accrual Amount

of Characters: Not applicable

Where to use it: Lease

Use this element for: Reporting.

Additional information

- ▶ The field label is editable.
- ▶ Available only in Upper Form.
- ▶ Available as both input/output, while defining integration interface.

`uuu_lse_annual_discnt_rate`

Data Definition: Decimal Amount

Form Label (Field Label): Annual discount rate

of Characters: na

Where to use it: Lease

Use this element for: Holding annual discount rate.

Additional information:

The field label is read-only.

Can be added to both Upper Form and system-defined Detail form (payment setup).

Supports auto-population and reverse auto-population (RAP).

Available to be used in formula in other data elements.

By default, it uses the value from Upper Form in Net Present Value (NPV) calculations.

If present in the system-defined Detail form (payment setup), then the value will be used as an over-write of the Upper Form value.

If exists in the system-defined Detail form (payment setup), then the value will be used in the NPV calculation, but if it exists only on the Upper Form, then it will use the value from the Upper Form.

uuu_lse_inc_in_npv

Data Definition: Checkbox (YES/NO)

Form Label (Field Label): Include in Net Present Value

of Characters: Not applicable

Where to use it: Lease BPs

Use this element for: Choosing line items to be included in NPV Calculations.

Additional information:

- ▶ The field label is editable
- ▶ Available only in Detail form.
- ▶ If the user selects "NO," in User mode, then the amount rate will be grayed out for that line item.

uuu_lse_npv_amount

Data Definition: Currency

Form Label (Field Label): NPV Amount

of Characters: Not applicable

Where to use it: Lease BPs

Use this element for: Holding calculated NPV amount.

Additional information:

- ▶ The field label is read-only.
- ▶ Can be added to both Upper Form and system-defined Detail form (payment setup).
- ▶ Supports auto-population and reverse auto-population (RAP).
- ▶ Available to be used in formula in other data elements.
- ▶ By default, it uses the value from Upper Form in Net Present Value (NPV) calculations.
- ▶ If present in the system-defined Detail form (payment setup), then the value will be used as an over-write of the Upper Form value.
- ▶ If exists in the system-defined Detail form (payment setup), then the value will be used in the NPV calculation, but if it exists only on the Upper Form, then it will use the value from the Upper Form.

uuu_meter_avg_units

Data Definition: Decimal Amount

Form Label (Field Label): Average units per day

of Characters: Not applicable

Where to use it: Upper form of Meter Reading Business Process (BP)

Use this element for: Capturing the average units consumed by the Meter, per day.

uuu_meter_base_rdng

Data Definition: Decimal Amount

Form Label (Field Label): Base Reading

of Characters: Not applicable

Where to use it: Meter Reading Upper form

Use this element for: Keeping track of how many times the meter rollover point has been reached (Rollover point value gets added to the value in this DE, each time there is a rollover), and if the meter gets replaced by a new meter, how many units were already consumed by the previous meter (so that the readings from the new meter are always added to value in this DE to figure out how many units have been consumed by the meter on a whole).

uuu_meter_cumu_rdng

Data Definition: Decimal Amount

Form Label (Field Label): Cumulative Reading

of Characters: Not applicable

Where to use it: Meter Reading Upper form

Use this element for: Capturing the actual units consumed by the asset for that meter (including rollover, meter replacement due to broken/defective meters).

uuu_meter_init_rdnng

Data Definition: Decimal Amount

Form Label (Field Label): Initial Reading

of Characters: Not applicable

Where to use it: Meter Reading Detail form

Use this element for: Capturing the initial meter reading, if the meter reading is of type “New Meter.”

uuu_meter_latest_rdnng

Data Definition: Decimal Amount

Form Label (Field Label): Latest Reading

of Characters: Not applicable

Where to use it: Meter Reading Upper Form

Use this element for: Capturing the latest reading from all the readings captured within the meter record.

Latest reading value is figured out by sorting the readings based on their effective date value.

uuu_meter_reading

Data Definition: Decimal Amount

Form Label (Field Label): Meter Reading

of Characters: Not applicable

Where to use it: Capturing the reading on the meter record.

Use this element for: Capturing the reading on the meter record.

uuu_meter_rdnng_type

Data Definition: SYS Reading Type

Form Label (Field Label): Reading Type

of Characters: Not applicable

Where to use it: Meter Reading Detail form

Use this element for: Capturing if the entered meter reading is a regular reading, a rollover reading, or a New Meter reading.

uuu_meter_rollover_pt

Data Definition: Decimal Amount

Form Label (Field Label): Rollover Point

of Characters: Not applicable

Where to use it: Meter Reading Upper Form

Use this element for: Capturing the rollover point of the meter (the point after which the meter resets itself back to zero).

uuu_navigation_code

Data Definition: SYS Short Description Text 250

Form Label (Field Label): Navigation Code

of Characters: 250

Where to use it: Generic managers that use a tree format

Use this element for: Designating where the entity should appear in the tree.

uuu_no_upd

Data Definition: SYS Check Box

Form Label (Field Label): Prevent Business Process Updates

of Characters: Not applicable

Where to use it:

- ▶ The Upper forms of Asset and PM Book.
- ▶ The value in this DE determines whether or not the Preventive Maintenance Book (PM Book) record must be updated (when a PM Book template record Push is done to the auto created PM Book records).
- ▶ This is an optional field in the Upper Form design.
- ▶ This field can be marked as editable and required.

Use this element for:

This DE is available to be placed on the Upper and Detail forms of other Business Processes.

The behavior is similar to the other system-defined check boxes.

Additional information:

- ▶ By default, the check box is deselected when placed in the above mentioned BP.
- ▶ When this option is checked, no updates take place from the PM Book Template.
- ▶ When an Asset type Business Process auto-creates a PM Book record, this field is copied over.

Other DEs (in Alphabetical Order: O-T)

Use the following Data Elements (DEs), presented alphabetically, for creating the attribute forms, Business Processes, and other entities.

uuu_planning_item_picker

Data Definition: Planning Item Picker

Form Label (Field Label): Item

of Characters: Not applicable

Where to use it: Company or project level business processes

Note: Do not use this picker on configurable manager attribute forms.

Use this element for: Selecting a plan.

If you use a Planning Item Picker on a Shell Creation/Project Creation BP, once the project/shell is created it links back to the new Project/Shell created.

If you use this element for this purpose, it must be on the same form that the shell or project creator element is on.

uuu_proj_currency

Data Definition: currency picker

Form Label (Field Label): Project Currency

of Characters: Not applicable

Where to use it: Project or Shell Creator business process of Simple type or Line Item type (upper or detail form).

Note: Use this element for the project address only; not for billing, shipping, and so on, addresses.

Use this element for: Overriding the default project or shell currency defined in the project or shell template with a substitute currency.

The currency must be defined in **Standards & Libraries** node > Exchange Rates.

The currency code must be valid.

If the currency is not defined in the project or shell template, and a valid currency code was used, the system will add it to the template as a float rate and create the project or shell with this currency as the default project or shell currency.

The currency cannot be a future currency.

In a line item Project or Shell Creator BP you can use this field to auto-populate from the upper form to the same field on the detail form. You cannot reverse auto-populate from detail form to upper form. The field cannot have a formula or be reset.

uuu_rec_asset_bp

Data Definition: BP Picker

Form Label (Field Label): Asset

of Characters: Not applicable

Where to use it:

- ▶ PM Book Upper form
- ▶ PM Book Template Upper form
- ▶ Meter Reading Upper form
- ▶ Detail form of Asset business processes

Use this element for: Selecting Asset Business Process.

uuu_rec_ast_meter_li

Data Definition: BP Line Item Picker

Form Label (Field Label): Asset Meter LI Ref

of Characters: Not applicable

Where to use it:

- ▶ PM Book Meter Detail form
- ▶ It is also required in PM Book Template's Meter Detail form and in Meter Reading Upper form

Note: You cannot use a BP Line Item Picker in an Activity Attribute Form.

Use this element for: Picking line items from Meters detail tab of the Asset in the PM Book.

uuu_rec_ctr_adjustment

Data Definition: Integer Amount

Form Label (Field Label): Counter Adjustment

of Characters: Not applicable

Where to use it: PM Book Meter Detail form of subtype Continuous

Use this element for: Meter floating schedules that are continuous.

uuu_rec_family_identifier

Data Definition: SYS Family Identifier

Form Label (Field Label): Family Identifier

of Characters: Not applicable

Where to use it:

- ▶ PM Book Meter detail form of subtype Continuous.
- ▶ PM Book template Meter detail form of subtype Continuous.

Use this element for: Grouping line items with the same data values.

uuu_rec_related_family_id

Data Definition: SYS Family Identifier

Form Label (Field Label): Related Family ID

of Characters: Not applicable

Where to use it:

- ▶ Detail form of the Preventive Maintenance (PM) Book Template
- ▶ Preventive Maintenance Book type BPs, where detail form Type =
 - a. Time, OR
 - b. Meter, Sub-Type = Continuous

The default behavior on the form must be editable.

This DE:

- ▶ Is not allowed to be placed on the upper or detail forms of any other BP type.
- ▶ Can be marked as, "Required" or "Editable."
- ▶ Cannot be, "Read-Only."
- ▶ Cannot be auto-populated or reverse auto-populated; otherwise, Unifier displays, "This data entry is not suitable for defining auto-population." when the user tries to do these operations in uDesigner.
- ▶ Cannot be part of any Dynamic Data Set.
- ▶ Cannot be part of any formula.

If you want to create a link between time and meter schedules, Oracle recommends that you place "uuu_rec_related_family_id" in the Detail tab line item list log (along with the "Family Identifier: uuu_rec_family_identifier"). At runtime, this DE will show the Family Identifier of the selected or picked Line Item.

When there is no links on a line item, the value of this DE will be blank.

Note: Prior to 19.12, this DE will not be editable in the line item grid, and it will open in read-only mode.

Use this element for: Linking families in Time and Continuous Meter type detail tabs in PM book or PM Book template type BPs.

Default Tooltip for this DE: Select any line item from the family that needs to be linked to this line item or family.

uuu_rec_frequency

Data Definition: Integer Amount

Form Label (Field Label): Frequency

of Characters: Not applicable

Where to use it: This DE is mainly used in PM Book's Time detail form, PM Book template's Time detail form, PM Book's Meter Detail form of subtype Continuous.

Use this element for: Usage for this DE varies based on where its placed:

- ▶ When used in Meter Continuous Detail form, it captures the meter reading frequency at which the new record should be generated.
- ▶ When used in Time Detail form it captures the time frequency at which the new record should be generated.

uuu_rec_frequency_unit

Data Definition: SYS Frequency Unit

Form Label (Field Label): Frequency Unit

of Characters: Not applicable

Where to use it: This DE is mainly used in PM Book's Time detail form and in PM Book template's Time detail form.

Use this element for: Time frequency unit of a recurrence.

It captures whether the frequency is in multiples of days, weeks, months, or years.

uuu_rec_gauge_gt

Data Definition: Decimal (precision of 2); can be GT or LT zero

Form Label (Field Label): Greater Than

of Characters: Not applicable

Where to use it: PM Book's Meter detail form of subtype Gauge and in PM Book Template's Meter detail form of subtype Gauge.

Use this element for: Triggering a new record, if the Meter reading is "greater than" the given value, as a part of formula (source) or in Validation rule, and as a part of Dynamic Data Sets (DDSs).

uuu_rec_gauge_lt

Data Definition: Decimal (precision of 2); can be GT or LT zero

Form Label (Field Label): Less Than

of Characters: Not applicable

Where to use it: Triggering a new record, if the Meter reading is “less than” the given value, as a part of formula (source) or in Validation rule, and as a part of Dynamic Data Sets (DDSs).

Use this element for: Triggering a new record, if the Meter reading is “less than” the given value, as a part of formula (source) or in Validation rule, and as a part of Dynamic Data Sets (DDSs).

uuu_rec_lead_time

Data Definition: Integer Amount

Form Label (Field Label): Lead Time

of Characters: Not applicable

Where to use it: This DE is required in PM Book's Time Detail form and can be added to PM Book Template's Time Detail form.

Use this element for: Capturing the number of days by which the new record generates in advance.

uuu_rec_meter_type

Data Definition: Integer

Form Label (Field Label): Meter Type

of Characters: Not applicable

Where to use it:

- ▶ Capturing the type of Meter that is being captured on the Asset form.
- ▶ Can be used as a part of formula (source) or in Validation rule.
- ▶ Cannot be used in DDSs; Available for AP, and RAP.

Use this element for: Capturing the type of Meter that is being captured on the Asset form.

uuu_rec_next_due_date

Data Definition: Date Only Picker

Form Label (Field Label): Next Due Date

of Characters: Not applicable

Where to use it: It is required in PM Book's Time detail form and can be used in PM Book Template's Time detail form.

Note: Do not use this Data Element as a part of formula (source or destination), in Dynamic Data Sets (DDSs), and for creating Validation rules.

Use this element for: Capturing the next due date as per the time frequency as captured on the recurrence pattern on the given schedule line item.

uuu_rec_next_trgr_date

Data Definition: Date Only Picker

Form Label (Field Label): Next Trigger Date

of Characters: Not applicable

Where to use it:

- ▶ It is required in PM Book's Time detail form and can be used in PM Book Template's Time detail form.
- ▶ Cannot be used in Dynamic Data Sets (DDSs), for creating Validation rules, and Linked Elements.

Use this element for: This DE captures the estimated date when a recurring BP Creator will trigger next.

uuu_rec_prev_trgr_date

Data Definition: Date Only Picker

Form Label (Field Label): Previous Trigger Date

of Characters: Not applicable

Where to use it:

- ▶ It is required in PM Book's Time Detail form and Meter detail form of both the Subtypes; Continuous and Gauge.
- ▶ It can also be placed in PM Book Template's Time detail form and meter detail form of both the subtypes; Continuous and Gauge.

Use this element for: System populates this DE as the date when the BP Creator gets triggered to generate a new record.

uuu_rec_prev_trgr_rdng

Data Definition: Decimal Amount

Form Label (Field Label): Previous Trigger Reading

of Characters: Not applicable

Where to use it:

- ▶ Required on PM Book's Meter detail form of both subtypes Continuous and Gauge.
- ▶ Can be placed in PM Book Templates's Continuous and Gauge Meter Detail form.
- ▶ Cannot be used in Dynamic Data Sets (DDSs), for creating Validation rules, and Linked Elements.

Use this element for: System populates this DE as the reading when the BP creator gets triggered to generate a new record.

uuu_rec_schedule_type

Data Definition: SYS Schedule Type

Form Label (Field Label): Schedule Type

of Characters: Not applicable

Where to use it:

- ▶ This DE is required in Time detail form of PM Book and in Continuous Meter Detail form of PM Book.
- ▶ It can be added to the corresponding forms in PM Book templates as well.

Use this element for: This DE captures whether a schedule is fixed (generate new record irrespective of status of previous record) or floating (schedule next record only when previous record is completed/canceled/and so on).

uuu_rec_sequence_ctr

Data Definition: Integer Amount

Form Label (Field Label): Sequence Counter

of Characters: Not applicable

Where to use it: This DE is required in Time detail form of PM Book and in Continuous and Gauge Meter Detail form of PM Book. It can be added to the corresponding forms in PM Book templates as well.

Note: Do not use this Data Element in formulas, Reverse Auto Population (RAP), Dynamic Data Sets (DDSs), and for creating Validation rules.

Use this element for: Capturing the number of frequency units which will be elapsed between the line item Start date and Next Due date.

uuu_rec_li_start_date

Data Definition: Date Only picker

Form Label (Field Label): Start Date

of Characters: Not applicable

Where to use it:

- ▶ This DE is required in Time detail form of PM Book and in both Continuous and Gauge Meter detail forms of PM Book.
- ▶ It can also be placed in the corresponding forms in PM Book template.

Note: Do not use this Data Element in formulas, Reverse Auto Population (RAP), and Dynamic Data Sets (DDSs).

Use this element for: Scheduling line item such as the date from when the schedule line starts triggering, on a recurring basis.

uuu_rec_ses_desc

Data Definition: SYS Description Text 500 (5 Lines)

Form Label (Field Label): Seasonal Dates Description

of Characters: 500

Where to use it:

- ▶ Detail forms of a work flow or non workflow, single or multi-record, Company or Shell level Generic, or Preventive Maintenance Line Item business process.
- ▶ It is a system defined picker to pick "Seasonal Dates" record in Unifier.

Use this element for: This field should get populated based on the seasonal dates object selected by the user.

uuu_rec_ses_dates_pkr

Data Definition: Seasonal Dates Picker

Form Label (Field Label): Seasonal Dates Picker

of Characters: Not applicable

Where to use it:

- ▶ Detail forms of a work flow or non workflow, single or multi-record, Company or Shell level Generic, or Preventive Maintenance Line Item business process.

Use this element for: This DE is used to pick a "Seasonal Dates" record in Unifier.

uuu_rec_tolerance

Data Definition: Decimal (precision of 2)

Form Label (Field Label): Tolerance

of Characters: Not applicable

Where to use it:

- ▶ This DE is used in Continuous Meter detail form of PM Book.
- ▶ It can also be placed in the corresponding form in PM Book template.

Note: Do not use in Dynamic Data Sets (DDSs).

Use this element for: Used in conjunction with `uuu_rec_frequency` - trigger new record if meter reading has increased by any amount > (Frequency -Tolerance).

`uuu_rec_wo_bpc`

Data Definition: BP Creator

Form Label (Field Label): Work Order

of Characters: Not applicable

Where to use it:

- ▶ It is required in Time detail form and both Continuous and Gauge detail form of PM Book.
- ▶ It can also be placed in the corresponding detail forms in Pm Book template.

Use this element for: This DE captures the Work order generated by the PM Book.

`uuu_rich_text`

Data Definition: SYS Rich Text

Form Label (Field Label): User-defined name

of Characters: 2 MB size is allowed, restricting in runtime

Where to use it: Only in BP Upper Form

Use this element for: It is a lightweight HTML editor and style Markdown editor that provides the best user-interface for creating and editing content.

Additional Information:

- ▶ DEs of SYS Rich Text type should not be available to be set as Display Element in a Data Picker configuration.
- ▶ When you create a DE with the DD, the **New Data Element** window displays one box, at the bottom: **Default height of box (in pixels)**. The value, as entered by the user in this box, will be the default height of the Rich Text Editor DE box, in user mode.
- ▶ If the source of the data cube definition contains a DE of Rich Text type, then the DE of SYS Rich Text type should be available to be added in data cube definition, the **Data Elements** tab. The DE is not available to create queries, in the Query tab.
- ▶ DEs of SYS Rich Text type should be available to be added in the Behavior Set of Dynamic Data Sets.
- ▶ You can create data views from business and show the data (from the SYS Rich Text DE). When creating a data view, you must join the business process model (that is, the table) with the view "model_richtext," when creating data view to show rich text fields:
 - ▶ The BP model table holds columns to show data from rich text DE, but if the data is extracted from those columns, it will not be formatted (plain text).

- ▶ The model_richtext holds columns from the BP to show rich text fields in HTML format; as a result, if the BP model and the view model_richtext are joined in an SQL query, you should choose columns from the view model_richtext only but not from the BP model.

Additional expected behavior for following options:

- Export as CSV: This action gets the rich text DE data as per the column pulled using the SQL query (plain text from BP model or rich text from <model>_richtext).
- Export as SQL: The HTML elements of rich text should be inserted as null.

uuu_spa_amt_tp

Data Definition: Currency Amount

Form Label (Field Label): Amount this Period

of Characters: Not applicable

Where to use it: Standard Detail form of Payment Application type BPs which will reference a Base Commits of SOV type = Summary Payment Application.

Use this element for:

- ▶ Entering the value of of completed work for the current period. This DE is used when the Cost Line Item type = Lump Sum.
- ▶ Adding to the Detail form of other types of BPs.

Additional information:

- ▶ This DE is editable and mandatory (required in the form).
- ▶ You can enter the Amount this Period field manually, or it can be calculated by the system if you enter Percentage Complete to Date field.
- ▶ The calculation of the Amount this Period field, when you enter the Percentage Complete to Date (uuu_spa_per_comp) and when the DE is placed on the listed BP, is as follows:
Amount this Period **uuu_spa_amt_tp** = (Scheduled Value * **uuu_spa_per_comp**) - (uuu_spa_other_tp + uuu_spa_mat_stored + uuu_spa_prev_amt)
- ▶ This DE is not available as a part of Dynamic Datasets.
- ▶ The DE cannot be set as a formula, or Auto-Populate, in the listed BP.
- ▶ At runtime, this field is editable only when the Cost Line Item Type = Lump Sum. You can add the Lump Sum amount when Cost LI Type = Lump Sum.

Note: The remaining behavior is like any other Currency Amount DE.

uuu_spa_mat_stored

Data Definition: Currency Amount

Form Label (Field Label): Stored Materials Amount

of Characters: Not applicable

Where to use it:

Where to use it:

- ▶ Standard Detail form of Payment Application type BPs which will reference a Base Commits of type = Summary Payment Application.
- ▶ To add to the Detail form of other types of BPs.

Use this element for: Entering the value of stored materials for the project.

This DE is editable and mandatory (required in the form).

Additional information:

- ▶ The Stored Materials Amount is used to calculate the Percentage Complete to Date field.
- ▶ This DE can be set as a formula in the BP listed.
- ▶ This DE can be set as an Auto-Populate field.
- ▶ This DE is available as a part of Dynamic Datasets.
- ▶ At runtime, this field is editable only when the Cost Line Item Type = Lump Sum. You can add the value of the material stored for the project regardless of the Cost LI Type.

Note: The remaining behavior is like any other editable Currency Amount DE.

uuu_spa_other_tp

Data Definition: Currency Amount

Form Label (Field Label): Other Amount this Period

of Characters: Not applicable

Where to use it:

- ▶ Standard Detail form of Payment Application type BPs which will reference a Base Commits of type = Summary Payment Application.
- ▶ To add to the Detail Form of other types of BPs.

Use this element for: Entering the value of additional incurred cost.

Note: The cost might have been incurred because of additional work which the contractor could not have reasonably anticipated at the time of tendering.

Additional information:

- ▶ At runtime, this DE can be edited.
- ▶ You can enter the Other Amount this Period field manually, or it can be set as a formula in the form design, which adds other columns for other requested amounts for this period.
- ▶ This DE is editable and mandatory (required in the form)
- ▶ This DE can be set as a formula in the BP listed.

- ▶ This DE is available as a part of Dynamic Datasets.
- ▶ The field is editable both at the summary and child row levels. You can add the Quantity when Cost LI Type = Unit Cost. Also, you can add the amount that was not previously considered, regardless of the Cost LI Type.

Note: The remaining behavior is like any other editable Currency Amount DE.

uuu_spa_per_comp

Data Definition: Decimal Amount

Form Label (Field Label): Percentage Complete to Date

of Characters: Not applicable

Where to use it:

- ▶ Standard Detail form of Payment Application type BPs which will reference a Base Commits of type = Summary Payment Application.
- ▶ To add to the Detail form of other types of BPs.

Use this element for: Entering the total percentage of work completed to date.

The percentage represents work completed and stored materials for all periods to date, not just the current period.

This DE is editable and mandatory (required in the form).

Additional information:

- ▶ At runtime, the value stored in this DE varies based on your/user input.
- ▶ The DE is calculated by the system as Completed and Stored to Date Amount / Scheduled Value:

$$\text{uuu_spa_mat_stored} + \text{uuu_spa_other_tp} + \text{uuu_spa_per_comp} + \text{uuu_spa_amt_tp} + (\text{uuu_spa_qty_tp} * \text{Unit Cost}) / \text{scheduled_value} * 100 = \% \text{ Complete}$$
- ▶ You can enter the % column manually, based on the type of the Line Item (Lump sum vs. Unit Cost), and the corresponding Amount this Period and Quantity this Period change respectively.
- ▶ This DE is not available as a part of Dynamic Datasets.
- ▶ To prevent circular referencing, the DE cannot be part of formula definition and formula definitions cannot use this field as a source.
- ▶ The field is only editable at the summary. Based on the summary row percent entered, the Amount this Period is re-calculated. You must manually change the distribution in the child rows amount in order to change the child row Percentage Complete to Date.

Note: The remaining behavior is like any other DE.

uuu_spa_prev_amt

Data Definition: Currency Amount

Form Label (Field Label): Total Previous Payments

of Characters: Not applicable

Where to use it: Standard Detail form of Payment Application type BPs which will reference a Base Commits of type = Summary Payment Application

Use this element for: Knowing the amount that was previously submitted.

You can add this DE to any Detail form of Summary SOV type BPs, or to Detail forms of other types of BPs.

This DE is editable in all other BPs.

Additional information:

- ▶ At runtime, this DE is Read-Only.
- ▶ The default behavior, in the listed BPs, is read-only.
- ▶ When placed on the Detail form, this value will get populated with the Amount + Total Previous Payments from the SOV. This value comes from the SOV.
- ▶ This DE is not available as a part of Dynamic Datasets.
- ▶ This DE cannot be set as a formula, or auto-populate, because it is a read-only field.

Note: The remaining behavior is like any other Currency Amount DE.

uuu_spa_qty_tp

Data Definition: Decimal Amount

Form Label (Field Label): Quantity this Period

of Characters: Not applicable

Where to use it:

- ▶ Standard Detail form of Payment Application type BPs which will reference a Base Commits of type = Summary Payment Application
- ▶ When Cost Line item type = Unit Cost
- ▶ To add on Detail Forms of other types of BPs

Use this element for: Entering the quantity for the current period.

Additional information:

- ▶ At runtime, this DE is only editable if the Cost Line Item type = Unit Cost.
- ▶ The value of this DE changes if the user:
 - ▶ Enters the Percentage Complete to Date (uuu_spa_per_comp), and
 - ▶ The Cost Type is Unit Cost.
- ▶ The Quantity this Period:

$$\text{uuu_spa_qty_tp} = ((\text{Scheduled Value} * \text{uuu_spa_per_comp}) - (\text{uuu_spa_other_tp} + \text{uuu_spa_mat_stored} + \text{uuu_spa_prev_amt})) / \text{uuu_unit_price}$$

- ▶ This DE is not available as a part of Dynamic Datasets.
- ▶ To prevent circular referencing, the DE cannot be part of formula definition and formula definitions cannot use this field as a source.

Note: The remaining behavior is like any other DE.

Other DEs (in Alphabetical Order: U-Z)

Use the following Data Elements (DEs), presented alphabetically, for creating the attribute forms, Business Processes, and other entities.

uuu_user_proxy_config

Data Definition: SYS Check Box

Form Label (Field Label): Proxy Configuration Allowed

of Characters: Not applicable, or 0

Where to use it:

- ▶ User Log, User Picker
- ▶ User Data Picker
- ▶ Integration Interface
- ▶ Company Users Log
- ▶ Partner Users Log

Use this element for: Integration, Controlling Proxy login setup for users.

uuu_user_type

Data Definition: SYS User Type

Form Label (Field Label): User Type

of Characters: 256

Where to use it: Company and Partner User Log

Use this element for: Displaying the User type, based on License Terms.

P6 DEs

Use the following data elements for P6 integration.

uuu_P6ActivityCalendar

Data Definition: SYS Activity Calendar

Form Label (Field Label): Activity Calendar

of Characters: Not applicable

Where to use it: Activity Sheets (Activity Attributes)

Use this element for: Selecting an individual calendar for each calendar from a list of defined calendars in custom calendars node.

uuu_P6ActivityId

Data Definition: SYS Short Description Text 40

Form Label (Field Label): Is picked from the specifications

of Characters: Is picked from the specifications (DD of the field)

Where to use it: Activity Sheet (Activity attributes)

Similar to other regular Data Element of its Data Definition, it can be placed in any form.

Use this element for: Capturing Activity ID data from P6.

uuu_P6ActivityName

Data Definition: SYS Short Description Text 120

Form Label (Field Label): Is picked from the specifications

of Characters: Is picked from the specifications (DD of the field)

Where to use it: Activity Sheet (Activity attributes)

Similar to other regular Data Element of its Data Definition, it can be placed in any form.

Use this element for: Capturing Activity Name data from P6.

uuu_P6ActivityStatus

Data Definition: SYS Short Description Text 50

Form Label (Field Label): Is picked from the specifications

of Characters: Is picked from the specifications (DD of the field)

Where to use it: Activity Sheet (Activity attributes)

Similar to other regular Data Element of its Data Definition, it can be placed in any form.

Use this element for: Capturing Activity Status data from P6

uuu_P6ActivityType

Data Definition: SYS Short Description Text 50

Form Label (Field Label): Is picked from the specifications

of Characters: Is picked from the specifications (DD of the field)

Where to use it: Activity Sheet (Activity attributes)

Similar to other regular Data Element of its Data Definition, it can be placed in any form.

Use this element for: Capturing Activity Type data from P6

uuu_P6ActualCost

Data Definition: Currency Amount

Field Label: Actual Cost

of Characters: Not applicable

Where to use it: Activity Sheet (Assignment attributes)

Use this element for: capturing the actual cost consumed for an assignment corresponding to the activity

Behavior: This data element will be present in out of the box Activity Sheet. It should always be 'Read-only' and its value will always be populated from P6 via integration. DE can be placed on any other form and should behave like a custom DE on those forms (that is, can be marked as Editable, Required, or Read-only).

uuu_P6ActualDuration

Data Definition: Decimal Amount

Form Label (Field Label): Is picked from the specifications

of Characters: Is picked from the specifications (DD of the field)

Where to use it: Activity Sheet (Activity attributes), Activity Sheet (Assignment attributes)

Similar to other regular Data Element of its Data Definition, it can be placed in any form.

Use this element for: Capturing Actual Duration data from P6

uuu_P6ActualFinish

Data Definition: Date Picker

Form Label (Field Label): Is picked from the specifications

of Characters: Is picked from the specifications (DD of the field)

Where to use it: Activity Sheet (Activity attributes), Activity Sheet (Assignment attributes)

Similar to other regular Data Element of its Data Definition, it can be placed in any form.

Use this element for: Capturing Actual Finish data from P6

uuu_P6ActualStart

Data Definition: Date Picker

Form Label (Field Label): Is picked from the specifications

of Characters: Is picked from the specifications (DD of the field)

Where to use it: Activity Sheet (Activity attributes), Activity Sheet (Assignment attributes)

Similar to other regular Data Element of its Data Definition, it can be placed in any form.

Use this element for: Capturing Actual Start data from P6

uuu_P6ActualTotalCost

Data Definition: Currency Amount

Form Label (Field Label): Is picked from the specifications

of Characters: Is picked from the specifications (DD of the field)

Where to use it: Activity Sheet (Activity attributes)

Similar to other regular Data Element of its Data Definition, it can be placed in any form.

Use this element for: Capturing Actual Total Cost data from P6

uuu_P6ActualTotalUnits

Data Definition: Decimal Amount

Field Label: Actual Total Units

of Characters: Not applicable

Where to use it: Activity Sheet (Activity attributes)

Use this element for: capturing the total number of actual units consumed for an activity

Behavior: This data element will be present in out of the box Activity Sheet. It should always be 'Read-only' and its value will always be populated from P6 via integration. DE can be placed on any other form and should behave like a custom DE on those forms (that is, can be marked as Editable, Required, or Read-only).

uuu_P6ActualUnits

Data Definition: Decimal Amount

Field Label: Actual Units

of Characters: Not applicable

Where to use it: Activity Sheet (Assignment attributes)

Use this element for: capturing the number of actual units consumed for an assignment corresponding to the activity

Behavior: This data element will be present in out of the box Activity Sheet. It should always be 'Read-only' and its value will always be populated from P6 via integration. DE can be placed on any other form and should behave like a custom DE on those forms (that is, can be marked as Editable, Required, or Read-only).

uuu_P6AtCompletionCost

Data Definition: Currency Amount

Field Label: At Completion Cost

of Characters: Not applicable

Where to use it: Activity Sheet (Assignment attributes)

Use this element for: capturing the at completion cost required for an assignment corresponding to the activity

Behavior: This data element will be present in out of the box Activity Sheet. It should always be 'Read-only' and its value will always be populated from P6 via integration. DE can be placed on any other form and should behave like a custom DE on those forms (that is, can be marked as Editable, Required, or Read-only).

uuu_P6AtCompletionDuration

Data Definition: Decimal Amount

Form Label (Field Label): Is picked from the specifications

of Characters: Is picked from the specifications (DD of the field)

Where to use it: Activity Sheet (Activity attributes), Activity Sheet (Assignment attributes)

Similar to other regular Data Element of its Data Definition, it can be placed in any form.

Use this element for: Capturing Completion Duration data from P6

uuu_P6AtCompletionTotalCost

Data Definition: Currency Amount

Form Label (Field Label): Is picked from the specifications

of Characters: Is picked from the specifications (DD of the field)

Where to use it: Activity Sheet (Activity attributes)

Similar to other regular Data Element of its Data Definition, it can be placed in any form.

Use this element for: Capturing At Completion Total Cost data from P6

uuu_P6AtCompletionTotalUnits

Data Definition: Decimal Amount

Field Label: At Completion Total Units

of Characters: Not applicable

Where to use it: Activity Sheet (Activity attributes)

Use this element for: capturing the total number of at completion units required for an activity

Behavior: This data element will be present in out of the box Activity Sheet. It should always be 'Read-only' and its value will always be populated from P6 via integration. DE can be placed on any other form and should behave like a custom DE on those forms (that is, can be marked as Editable, Required, or Read-only).

uuu_P6AtCompletionUnits

Data Definition: Decimal Amount

Field Label: At Completion Units

of Characters: Not applicable

Where to use it: Activity Sheet (Assignment attributes)

Use this element for: capturing the number of at completion units required for an assignment corresponding to the activity

Behavior: This data element will be present in out of the box Activity Sheet. It should always be 'Read-only' and its value will always be populated from P6 via integration. DE can be placed on any other form and should behave like a custom DE on those forms (that is, can be marked as Editable, Required, or Read-only).

uuu_P6BAC

Data Definition: Currency Amount

Field Label: Budget At Completion

of Characters: Not applicable

Where to use it: Activity Attributes form

Use this element for: capturing the budget at completion for cost loaded schedule. This will be calculated for a resource loaded schedule.

Behavior: This data element will be present in out of the box sheet mentioned above. DE can be placed on any other form and should behave like a custom DE on those forms (that is, can be marked as Editable, Required, or Read-only).

uuu_P6CBSCode

Data Definition: SYS Short Description Text 40

Form Label (Field Label): Is picked from the specifications

of Characters: Is picked from the specifications (DD of the field)

Note: The P6 UI does not allow CBS Code to be more than 20 characters. The P6 Database stores the CBS Code field as Varchar (40 characters).

Where to use it: Activity attribute form.

Similar to other regular Data Element of its Data Definition, it can be placed in any form.

Use this element for: Capturing CBS Code data from P6.

uuu_P6CBSName

Data Definition: SYS Short Description Text 120

Form Label (Field Label): Is picked from the specifications

of Characters: Is picked from the specifications (DD of the field)

Where to use it: Activity attribute form.

Similar to other regular Data Element of its Data Definition, it can be placed in any form.

Use this element for: Capturing CBS Name data from P6.

uuu_P6CBSPath

Data Definition: SYS Description Text 500

Form Label (Field Label): Is picked from the specifications

of Characters: Is picked from the specifications (DD of the field)

Note: The P6 UI does not allow the CBS Name to be greater than 100 characters.

Where to use it: Activity attribute form.

Similar to other regular Data Element of its Data Definition, it can be placed in any form.

Use this element for: Capturing CBS Path data from P6

uuu_P6ControlAccounts

Data Definition: SYS Check Box

Field Label: Control Accounts

of Characters: Not applicable

Where to use it: Activity Sheet (WBS attributes)

Use this element for: To indicate if the WBS is a control account

Behavior: This data element will be present in out of the box Activity Sheet. It should always be 'Read-only' and its value will always be populated from P6 via integration. DE can be placed on any other form and should behave like a custom DE on those forms (that is, can be marked as Editable, Required, or Read-only).

uuu_P6CostVariance

Data Definition: Currency Amount

Field Label: Cost Variance

of Characters: Not applicable

Where to use it: Activity Sheet (Activity Attributes)

Use this element for: capturing the cost variance for cost loaded schedule. This will be calculated for a resource loaded schedule.

Behavior: This data element will be present in out of the box sheet mentioned above. DE can be placed on any other form and should behave like a custom DE on those forms (that is, can be marked as Editable, Required, or Read-only).

uuu_P6CPIndex

Data Definition: Decimal Amount

Field Label: Cost Performance Index

of Characters: Not applicable

Where to use it: Activity Sheet (Activity Attributes)

Use this element for: capturing the Cost Performance Index for cost loaded schedule. This will be calculated for a resource loaded schedule.

Behavior: This data element will be present in out of the box sheet mentioned above. DE can be placed on any other form and should behave like a custom DE on those forms (that is, can be marked as Editable, Required, or Read-only).

uuu_P6CSIndex

Data Definition: Decimal Amount

Form Label (Field Label): Cost Schedule Index

of Characters: Not applicable

Where to use it: Activity Sheet

Use this element for: Checking the overall status of the cost schedule by combining cost and schedule.

uuu_P6Duration

Data Definition: Decimal Amount

Form Label (Field Label): Duration

of Characters: Not applicable

Where to use it: Activity Sheet and Business Processes

Use this element for: Calculating the duration between start and finish dates.

uuu_P6EAC

Data Definition: Currency Amount

Field Label: Estimate At Completion

of Characters: Not applicable

Where to use it: Activity Sheet (Activity Attributes)

Use this element for: capturing the estimate at completion cost for cost loaded schedule. This will be calculated for a resource loaded schedule.

Behavior: This data element will be present in out of the box sheet mentioned above. DE can be placed on any other form and should behave like a custom DE on those forms (that is, can be marked as Editable, Required, or Read-only).

uuu_P6EACCost

Data Definition: Decimal Amount

Form Label (Field Label): Estimate at Completion Cost

of Characters: Not applicable

Where to use it: Activity Sheet and Business Processes

Use this element for: Populating the Estimate at Completion cost used for Earned Value Management analysis.

uuu_P6ETC

Data Definition: Currency Amount

Field Label: Estimate To Completion

of Characters: Not applicable

Where to use it: Activity Sheet (Activity Attributes)

Use this element for: capturing the estimate to completion for cost loaded schedule. This will be calculated for a resource loaded schedule.

Behavior: This data element will be present in out of the box sheet mentioned above. DE can be placed on any other form and should behave like a custom DE on those forms (that is, can be marked as Editable, Required, or Read-only).

uuu_P6ETCUserValue

Data Definition: Decimal Amount

Form Label (Field Label): ETC User Value

of Characters: Not applicable

Where to use it: WBS Attributes

Use this element for: Calculating ETC from user entered value.

uuu_P6EV

Data Definition: Currency Amount

Field Label: Earned Value

of Characters: NA

Where to use it: Activity Sheet (Activity Attributes)

Use this element for: capturing the earned value cost for cost loaded schedule. This will be calculated in Unifier for a resource loaded schedule.

Behavior: This data element will be present in out of the box sheet mentioned above. DE can be placed on any other form and should behave like a custom DE on those forms (that is, can be marked as Editable, Required, or Read-only).

uuu_P6EVCost

Data Definition: Decimal Amount

Form Label (Field Label): Earned Value Cost

of Characters: Not applicable

Where to use it: Activity Attributes and Business Processes

Use this element for: Populating the Earned Value Cost used for Earned Value Management analysis.

uuu_P6Finish

Data Definition: Date Picker

Form Label (Field Label): Is picked from the specifications

of Characters: Is picked from the specifications (DD of the field)

Where to use it:

- ▶ Spreads
- ▶ Activity attribute form.
- ▶ Similar to other regular Data Element of its Data Definition, it can be placed in any form.

Use this element for: Capturing Finish data from P6

uuu_P6PercentComplete

Data Definition: Decimal Amount

Form Label (Field Label): Is picked from the specifications

of Characters: Is picked from the specifications (DD of the field)

Where to use it: Activity Sheet (Activity attributes)

Similar to other regular Data Element of its Data Definition, it can be placed in any form.

Use this element for: Capturing Percent Complete data from P6

uuu_P6PerfPercComplete

Data Definition: SYS Short Description Text 50

Form Label (Field Label): Performance Percent Complete

of Characters: 50

Where to use it: Activity Sheet

Use this element for: Calculating earned value based on the performance percent complete.

uuu_P6PlannedCost

Data Definition: Currency Amount

Field Label: Planned Cost

of Characters: Not applicable

Where to use it: Activity Sheet (Assignment attributes)

Use this element for: capturing the planned cost for an assignment to be consumed corresponding to the activity.

Behavior: This data element will be present in out of the box Activity Sheet. It should always be 'Read-only' and its value will always be populated from P6 via integration. DE can be placed on any other form and should behave like a custom DE on those forms (that is, can be marked as Editable, Required, or Read-only).

uuu_P6PlannedDuration

Data Definition: Decimal Amount

Form Label (Field Label): Is picked from the specifications

of Characters: Is picked from the specifications (DD of the field)

Where to use it: Activity Sheet (Activity attributes), Activity Sheet (Assignment attributes)

Similar to other regular Data Element of its Data Definition, it can be placed in any form.

Use this element for: Capturing Planned Duration data from P6

uuu_P6PlannedStart

Data Definition: Date Picker

Form Label (Field Label): Is picked from the specifications

of Characters: Is picked from the specifications (DD of the field)

Where to use it: Activity Sheet (Activity attributes), Activity Sheet (Assignment attributes)

Similar to other regular Data Element of its Data Definition, it can be placed in any form.

Use this element for: Capturing Planned Start data from P6

uuu_P6PlannedFinish

Data Definition: Date Picker

Form Label (Field Label): Is picked from the specifications

of Characters: Is picked from the specifications (DD of the field)

Where to use it: Activity Sheet (Activity attributes), Activity Sheet (Assignment attributes)

Similar to other regular Data Element of its Data Definition, it can be placed in any form.

Use this element for: Capturing Planned Finish data from P6

uuu_P6PlannedTotalCost

Data Definition: Currency Amount

Form Label (Field Label): Is picked from the specifications

of Characters: Is picked from the specifications (DD of the field)

Where to use it: Activity Sheet (Activity attributes)

Similar to other regular Data Element of its Data Definition, it can be placed in any form.

Use this element for: Capturing Planned Total Cost data from P6

uuu_P6PlannedTotalUnits

Data Definition: Decimal Amount

Form Label (Field Label): Planned Total Units

of Characters: Not applicable

Where to use it: Activity Sheet

Use this element for: Capturing the total number of planned units required for an activity.

uuu_P6PlannedUnits

Data Definition: Decimal Amount

Field Label: Planned Units

of Characters: Not applicable

Where to use it: Activity Sheet (Assignment attributes)

Use this element for: capturing the number of planned units for an assignment item to be consumed corresponding to the activity.

Behavior: This data element will be present in out of the box Activity Sheet. It should always be 'Read-only' and its value will always be populated from P6 via integration. DE can be placed on any other form and should behave like a custom DE on those forms (that is, can be marked as Editable, Required, or Read-only).

uuu_P6PricePerUnit

Data Definition: Integer Amount

Field Label: Price/Unit

of Characters: Not applicable

Where to use it: Activity Sheet (Role attributes), Rate Sheet (Rate attributes)

Use this element for: capturing the price per unit for an assignment in activity sheet or role/resource in rate sheet

Behavior: This data element will be present in out of the box sheets mentioned above. DE can be placed on any other form and should behave like a custom DE on those forms (that is, can be marked as Editable, Required, or Read-only).

uuu_P6PrimaryConstraint

Data Definition: SYS P6 Activity Constraints

Form Label (Field Label): Is picked from the specifications

of Characters: Is picked from the specifications (DD of the field)

Where to use it: Activity attribute form.

Similar to other regular Data Element of its Data Definition, it can be placed in any form.

Use this element for: Capturing Primary Constraint data from P6

uuu_P6PV

Data Definition: Currency Amount

Field Label: Planned Value

of Characters: Not applicable

Where to use it: Activity Sheet (Activity Attributes)

Use this element for: capturing the planned value cost for cost loaded schedule. This will be calculated for a resource loaded schedule.

Behavior: This data element will be present in out of the box sheet mentioned above. DE can be placed on any other form and should behave like a custom DE on those forms (that is, can be marked as Editable, Required, or Read-only).

uuu_P6PVCost

Data Definition: Currency Amount

Form Label (Field Label): Planned Value Cost

of Characters: Not applicable

Where to use it: Activity Sheet

Use this element for: Capturing the portion of the baseline total cost of the activity or project that is scheduled to be completed as of the project date.

uuu_P6RateCurrency

Data Definition: Currency Picker

Field Label: Rate Currency

of Characters: Not applicable

Where to use it: Rate Sheet (Role attributes), Rate Sheet (Resource attributes)

Use this element for: Capturing the currency in which the rates of a role or resource are defined.

Behavior: This data element will be present in out of the box sheet mentioned above. DE can be placed on any other form and should behave like a custom DE on those forms (that is, it can be marked as 'Editable', 'Required' or 'Read-only').

uuu_P6RateEffectiveFrom

Data Definition: Date Picker

Field Label: Effective From

of Characters: Not applicable

Where to use it: Rate Sheet (Rate attributes)

Use this element for: Capturing the effective date of a price per unit. Multiple effective from dates are supported by creating a tabular format where in which multiple entries for multiple rates with different dates are added.

Behavior: This data element will be present in out of the box sheet mentioned above. DE can be placed on any other form and should behave like a custom DE on those forms (that is, it can be marked as 'Editable', 'Required' or 'Read-only').

uuu_P6RemainingCost

Data Definition: Currency Amount

Field Label: Remaining Cost

of Characters: Not applicable

Where to use it: Activity Sheet (Assignments attributes)

Use this element for: capturing the remaining cost for an assignment corresponding to the activity

Behavior: This data element will be present in out of the box Activity Sheet. It should always be 'Read-only' and its value will always be populated from P6 via integration. DE can be placed on any other form and should behave like a custom DE on those forms (that is, can be marked as Editable, Required, or Read-only).

uuu_P6RemainingDuration

Data Definition: Decimal Amount

Form Label (Field Label): Is picked from the specifications

of Characters: Is picked from the specifications (DD of the field)

Where to use it: Activity Sheet (Activity attributes), Activity Sheet (Assignment attributes)

Similar to other regular Data Element of its Data Definition, it can be placed in any form.

Use this element for: Capturing Remaining Duration data from P6

uuu_P6RemainingEarlyFinish

Data Definition: Date Picker

Form Label (Field Label): Is picked from the specifications

of Characters: Is picked from the specifications (DD of the field)

Where to use it: Activity Sheet (Activity attributes), Activity Sheet (Assignment attributes)

Similar to other regular Data Element of its Data Definition, it can be placed in any form.

Use this element for: Capturing Remaining Early Finish data from P6

uuu_P6RemainingEarlyStart

Data Definition: Date Picker

Form Label (Field Label): Is picked from the specifications

of Characters: Is picked from the specifications (DD of the field)

Where to use it: Activity Sheet (Activity attributes), Activity Sheet (Assignment attributes)

Similar to other regular Data Element of its Data Definition, it can be placed in any form.

Use this element for: Capturing Remaining Early Start data from P6

uuu_P6RemainingTotalCost

Data Definition: Currency Amount

Form Label (Field Label): Is picked from the specifications

of Characters: Is picked from the specifications (DD of the field)

Where to use it: Activity Sheet (Activity attributes)

Similar to other regular Data Element of its Data Definition, it can be placed in any form.

Use this element for: Capturing Remaining Total Cost data from P6

uuu_P6RemainingTotalUnits

Data Definition: Decimal Amount

Field Label: Remaining Total Units

of Characters: Not applicable

Where to use it: Activity Sheet (Activity attributes)

Use this element for: capturing the number of remaining units for an activity

Behavior: This data element will be present in out of the box Activity Sheet. It should always be 'Read-only' and its value will always be populated from P6 via integration. DE can be placed on any other form and should behave like a custom DE on those forms (that is, can be marked as Editable, Required, or Read-only).

uuu_P6RemainingUnits

Data Definition: Decimal Amount

Field Label: Remaining Units

of Characters: Not applicable

Where to use it: Activity Sheet (Assignments attributes)

Use this element for: capturing the number of remaining units for an assignment corresponding to the activity

Behavior: This data element will be present in out of the box Activity Sheet. It should always be 'Read-only' and its value will always be populated from P6 via integration. DE can be placed on any other form and should behave like a custom DE on those forms (that is, can be marked as Editable, Required, or Read-only).

uuu_P6ResourceName

Data Definition: SYS Short Description Text 32

Field Label: Resource Name

of Characters: 32

Where to use it: Activity Sheet (Assignment attributes), Rate Sheet (Resource attributes)

Use this element for: capturing the Resource Name

Behavior: This data element will be present in out of the box sheets mentioned above. It should always be 'Read-only' and its value will always be populated from P6 via integration. DE can be placed on any other form and should behave like a custom DE on those forms (that is, can be marked as Editable, Required, or Read-only).

uuu_P6ResourceStatus

Data Definition: SYS Resource Status

Field Label: Resource Status

of Characters: Not applicable

Where to use it: Rate Sheet (Resource attributes)

Use this element for: capturing the Resource Status

Behavior: This data element will be present in out of the box sheet mentioned above. It should always be 'Read-only' and its value will always be populated from P6 via integration. DE can be placed on any other form and should behave like a custom DE on those forms (that is, can be marked as Editable, Required, or Read-only).

uuu_P6RoleID

Data Definition: SYS Short Description Text 8

Field Label: Role ID

of Characters: 8

Where to use it: Activity Sheet (Assignment attributes), Rate Sheet (Role attributes)

Use this element for: capturing the Role ID

Behavior: This data element will be present in out of the box sheets mentioned above. It should always be 'Read-only' and its value will always be populated from P6 via integration. DE can be placed on any other form and should behave like a custom DE on those forms (that is, can be marked as Editable, Required, or Read-only).

uuu_P6RoleName

Data Definition: SYS Short Description Text 32

Field Label: Role Name

of Characters: 32

Where to use it: Activity Sheet (Assignment attributes), Rate Sheet (Role attributes)

Use this element for: capturing the Role Name

Behavior: This data element will be present in out of the box sheets mentioned above. It should always be 'Read-only' and its value will always be populated from P6 via integration. DE can be placed on any other form and should behave like a custom DE on those forms (that is, can be marked as Editable, Required, or Read-only).

uuu_P6RoleStatus

Data Definition: SYS Role Status

Field Label: Role Status

of Characters: Not applicable

Where to use it: Rate Sheet (Role attributes)

Use this element for: capturing the Role Status

Behavior: This data element will be present in out of the box sheet mentioned above. It should always be 'Read-only' and its value will always be populated from P6 via integration. DE can be placed on any other form and should behave like a custom DE on those forms (that is, can be marked as Editable, Required, or Read-only).

uuu_P6ScheduleVariance

Data Definition: Currency Amount

Field Label: Schedule Variance

of Characters: Not applicable

Where to use it: Activity Sheet (Activity Attributes)

Use this element for: capturing the schedule variance for cost loaded schedule. This will be calculated for a resource loaded schedule.

Behavior: This data element will be present in out of the box sheet mentioned above. DE can be placed on any other form and should behave like a custom DE on those forms (that is, can be marked as Editable, Required, or Read-only).

uuu_P6SecondaryConstraint

Data Definition: SYS P6 Activity Constraints

Form Label (Field Label): Is picked from the specifications

of Characters: Is picked from the specifications (DD of the field)

Where to use it: Activity attribute form.

Similar to other regular Data Element of its Data Definition, it can be placed in any form.

Use this element for: Capturing Secondary Constraint data from P6

uuu_P6SPIndex

Data Definition: Decimal Amount

Field Label: Schedule Performance Index

of Characters: Not applicable

Where to use it: Activity Sheet (Activity Attributes)

Use this element for: capturing the Schedule Performance Index for cost loaded schedule. This will be calculated for a resource loaded schedule.

Behavior: This data element will be present in out of the box sheet mentioned above. DE can be placed on any other form and should behave like a custom DE on those forms (that is, can be marked as Editable, Required, or Read-only).

uuu_P6Start

Data Definition: Date Picker

Form Label (Field Label): Is picked from the specifications

of Characters: Is picked from the specifications (DD of the field)

Where to use it:

- ▶ Spreads
- ▶ Activity attribute form.
- ▶ Similar to other regular Data Element of its Data Definition, it can be placed in any form.

Use this element for: Capturing Start data from P6

uuu_P6TCPIIndex

Data Definition: Decimal Amount

Field Label: To Complete Performance Index

of Characters: Not applicable

Where to use it: Activity Sheet (Activity Attributes)

Use this element for: capturing the To Complete Performance Index for cost loaded schedule. This will be calculated for a resource loaded schedule.

Behavior: This data element will be present in out of the box sheet mentioned above. DE can be placed on any other form and should behave like a custom DE on those forms (that is, can be marked as Editable, Required, or Read-only).

uuu_P6TotalActualUnits

Data Definition: Decimal Amount

Field Label: Total Actual Units

of Characters: Not applicable

Where to use it: Activity Sheet (Activity attributes)

Use this element for: capturing the total number of actual units consumed for an activity

Behavior: This data element will be present in out of the box Activity Sheet. It should always be 'Read-only' and its value will always be populated from P6 via integration. DE can be placed on any other form and should behave like a custom DE on those forms (that is, can be marked as Editable, Required, or Read-only).

uuu_P6TotalAtCompletionUnits

Data Definition: Decimal Amount

Field Label: At Completion Units

of Characters: Not applicable

Where to use it: Activity Sheet (Activity attributes)

Use this element for: capturing the total number of at completion units required for an activity

Behavior: This data element will be present in out of the box Activity Sheet. It should always be 'Read-only' and its value will always be populated from P6 via integration. DE can be placed on any other form and should behave like a custom DE on those forms (that is, can be marked as Editable, Required, or Read-only).

uuu_P6TotalPlannedUnits

Data Definition: Decimal Amount

Field Label: Total Planned Units

of Characters: Not applicable

Where to use it: Activity Sheet (Activity Attributes)

Use this element for: capturing the total number of planned units for an activity.

Behavior: This data element will be present in out of the box Activity Sheet. It should always be 'Read-only' and its value will always be populated from P6 via integration. DE can be placed on any other form and should behave like a custom DE on those forms (that is, can be marked as Editable, Required, or Read-only).

uuu_P6TotalRemainingUnits

Data Definition: Decimal Amount

Field Label: Total Remaining Units

of Characters: Not applicable

Where to use it: Activity Sheet (Activity attributes)

Use this element for: capturing the total number of remaining units for an activity

Behavior: This data element will be present in out of the box Activity Sheet. It should always be 'Read-only' and its value will always be populated from P6 via integration. DE can be placed on any other form and should behave like a custom DE on those forms (that is, can be marked as Editable, Required, or Read-only).

uuu_P6VAC

Data Definition: Currency Amount

Field Label: Variance At Completion

of Characters: Not applicable

Where to use it: Activity Sheet (Activity Attributes)

Use this element for: capturing the variance at completion for cost loaded schedule. This will be calculated for a resource loaded schedule.

Behavior: This data element will be present in out of the box sheet mentioned above. DE can be placed on any other form and should behave like a custom DE on those forms (that is, can be marked as Editable, Required, or Read-only).

uuu_P6WBSCategory

Data Definition: SYS Long Name

Field Label: WBS Category

of Characters: 250

Where to use it: Activity Sheet (WBS attributes)

Use this element for: capturing the WBS category present in P6

Behavior: This data element will be present in out of the box Activity Sheet. It should always be 'Read-only' and its value will always be populated from P6 via integration. DE can be placed on any other form and should behave like a custom DE on those forms (that is, can be marked as Editable, Required, or Read-only).

uuu_P6WorkPackage

Data Definition: SYS Check Box

Field Label: Work Package

of Characters: Not applicable

Where to use it: Activity Sheet (WBS attributes)

Use this element for: To indicate if the WBS is a Work Package

Behavior: This data element will be present in out of the box Activity Sheet. It should always be 'Read-only' and its value will always be populated from P6 via integration. DE can be placed on any other form and should behave like a custom DE on those forms (that is, can be marked as Editable, Required, or Read-only).

uuu_P6WBSPath

Data Definition: SYS Long Description Text

Form Label (Field Label): WBS Path

of Characters:500

Where to use it: Activity Sheet (WBS attributes)

Use this element for: Populating the WBS hierarchy path of a WBS code.

Earned Value Manager DEs

Use the following data elements for creating the business processes and attribute forms for the **Earned Value Manager**.

Organization Breakdown Structure

The following lists the OBS Data Elements (DEs).

uuu_obs_recordno

Data Definition: TBC

Field Label: Record Number

of Characters: 6

Where to Use it: OBS Sheet

Use This Element For: capturing the OBS Record Number

Behavior: It should always be 'Read-only' and its value will always be automatically populated while creating the OBS Structure. DE can be placed on any other form and should behave like a custom DE on those forms (that is, can be marked as Editable, Required, or Read-only).

uuu_obs_fullnameTopic

Data Definition: TBC

Field Label: Full Name

of Characters: 64

Where to Use it: OBS Sheet

Use This Element For: capturing the OBS Full Name

Behavior: DE can be placed on any other form and should behave like a custom DE on those forms (that is, can be marked as Editable, Required, or Read-only).

uuu_obs_title

Data Definition: TBC

Field Label: Title

of Characters: 64

Where to Use it: OBS Sheet

Use This Element For: capturing the OBS Title

Behavior: DE can be placed on any other form and should behave like a custom DE on those forms (that is, can be marked as Editable, Required, or Read-only).

uuu_obs_department

Data Definition: TBC

Field Label: Department

of Characters: 64

Where to Use it: OBS Sheet

Use This Element For: capturing the OBS Department

Behavior: DE can be placed on any other form and should behave like a custom DE on those forms (that is, can be marked as Editable, Required, or Read-only).

uuu_obs_status

Data Definition: TBC

Field Label: Status (Active/Inactive)

of Characters: 16

Where to Use it: OBS Sheet

Use This Element For: capturing the OBS Status

Behavior: DE can be placed on any other form and should behave like a custom DE on those forms (that is, can be marked as Editable, Required, or Read-only).

uuu_obs_assignee

Data Definition: User Picker

Field Label: Unifier user

of Characters: TBD

Where to Use it: OBS Sheet

Use This Element For: capturing the OBS Status

Behavior: DE can be placed on any other form and should behave like a custom DE on those forms (that is, can be marked as Editable, Required, or Read-only).

Work Breakdown Structure (WBS)

The following lists the WBS Data Elements (DEs).

uuu_P6ETCComputeType

Data Definition: SYS Short Description Text 50

Field Label: ETC Technique

of Characters:

Where to Use it: Activity Sheet, WBS Sheet

Use This Element For: Defining ETC formula for Activities

Behavior: Disabled and Read-only in Activity Sheet grid and General tab

uuu_P6WBSCode

Data Definition: SYS Short Description Text 40

Field Label: WBS Code

of Characters: N/A

Where to Use it: This element is used in WBS Sheet.

Use This Element For: To uniquely identify the WBS Code

Behavior: Editable on Sheet grid and form view

uuu_P6WBSName

Data Definition: SYS Short Description Text 120

Field Label: WBS Name

of Characters:

Where to Use it: CBSWBS BP and Activity Sheet

Use This Element For: Defining name for WBS Codes

Behavior: Editable in WBS Sheet grid and General tab

uuu_P6WBSType

Data Definition: SYS Short Description Text 250

Field Label: WBS Type

of Characters:

Where to Use it: WBS Sheet and CBSWBS BP

Use This Element For:

Behavior:

Data Types for User Defined Reports (UDRs)

The following table lists the standard data types that are available for user-defined reports (UDRs), and which level you can use them on.

Use this data type:	Shell	Program	Company	UDR Template
Accounts Sheet			x	
Active Task Information	x		x	x
Asset Summary Sheet			x	
Commitment Funding	x	x	x	x
Commitment Summary	x			x
Company Cash Flow			x	
Company Cost			x	
Company User Information			x	
Cost Sheet - CBS	x	x		x
Cost Transactions -CBS	x	x		x
Cost Transactions MC - CBS	x			
Data View	x	x	x	x
Document Manager	x	x	x	x
Document Manager—Company			x	
Funding		x	x	x

Use this data type:	Shell	Program	Company	UDR Template
Gates	x	x		x
Partner User Information			x	
Program Cash flow		x		
Program Cost		x		
Program Schedule		x		
Resource Booking				x
Resource Manager—All Actuals			x	
Resource Manager—Allocated Roles		x		x
Resource Manager—Booked Resources		x		x
Resource Manager—Project Actuals		x		x
Resource Manager - Resources (Company)				x
Resource Manager—Roles			x	
Resource Manager—Sheets		x		x
Schedule of Values	x	x	x	x
Shell or Project Cash Flow	x	x		x
Shell or Project Cash Flow	x			x

Use this data type:	Shell	Program	Company	UDR Template
Summary Snapshot				
Shell or Project Cost	x	x		x
Shell or Project Groups	x	x		x
Shell or Project Information	x			x
Shell or Project Users	x			x
Workflow Information	x	x	x	x
(Asset class name)			x	
(Business process name)	x		x	
(Planning type name)			x	

The following table lists the standard data types, data sources, and data elements you can use to extract the data you want for a user-defined report.

Note: This table notes the standard data sources and data elements that are included with the system. It does not include business processes, asset classes, shell types, and so on, that were designed specifically for your company. What you can extract from them for reports depends on their designs.

In This Section

Accounts Sheet	262
Active Task Information	263
Asset Summary Sheet (Company-level)	266
CashFlow (Project/Shell)	266
CashFlow: Summary Snapshot (Project/Shell)	268
Commitment Funding	269
Commitment Summary	271
Company CashFlow	273
Company Cost	275
Company Funding	276
Company User Information	276
Cost Sheet (CBS)	277
Cost Transactions (CBS)	278
Cost (Project/Shell)	279
Cost Transactions MC (CBS)	280
Document Manager (Project/Shell)	284
Document Manager (Company-level)	288
Funding	290
Gates	292
Groups (Project/Shell)	295
Partner User Information	295
Planning Manager Items (Project/Shell)	296
Planning Manager Sheets (Project/Shell)	297
Resource Manager: All Actuals (Company-level)	297
Resource Manager: Allocated Roles	298
Resource Manager: Booked Resources	300
Resource Manager: Project Actuals	302
Resource Manager: Resources	303
Resource Manager: Roles	304
Resource Manager: Sheets	305
Schedule (Project/Shell)	306
Schedule of Value (SOV)	308
Shell Information	310
Users (Project/Shell)	312
Workflow Information	313

Accounts Sheet

Use this Data Source:	To get these details	Additional details:
Accounts Sheet	Account Code Account Name	
Company	Company Contact	Contact Email

Use this Data Source:	To get these details	Additional details:
	Company Creation Date Company Description Company Name Company Short Name Company URL	Help URL Instructions Label Registry Share with Wire URL (eLearning)
Company Accounts Sheet	Company account codes Assets	Projects Resource Actuals
Company/Company Accounts Summary in Base Currency	Account Codes Assets	Projects Resource Actuals
Company/Company Funding Summary in Base Currency	Commitment Funding Company Funds Company Funding Funds Manual Funding by Project Manual Funding by CBS Project Funding Records Funded at Commitment level	Records Funded at Project level Records Funded at CBS level Transient Records Funded at Commitment level Transient Records Funded at Project level Transient Records Funded at CBS level CBS Funding

Active Task Information

Use this Data Source:	To get these details	Additional details:
Active Task Information	Business Process Name Record Number Record Title Record Type Sent for Sent From Setup Description	Setup Name Task Due Date Task Start Date Task Status Workflow Due Date Workflow Start
Company	Company Contact Company Creation Date	Email Notifications Help URL

Use this Data Source:	To get these details	Additional details:
	Company Description Company Name Company Short Name Company URL Contact Email	Instructions Label Registry Share with Wire URL (eLearning)
Shell	Administrator Construction Type Description Location Creation Date Name Number Organization Category Phase	Shell Type Status Top Level Shell Name
Sub-workflow	Sub-workflow Allowed Duration Sub-workflow Description Sub-workflow Due Date	Sub-workflow Name Sub-workflow Start Date
Task Assignee	Cell Phone Company Name Company Short Name Creation Date Email Fax First Name Home Phone Last Name	Login ID Name Pager Registry Role Title Welcome Email Work Phone
Company / Company Accounts Summary in Base Currency	Account Codes Assets	Projects Resource Actuals
Company / Company Funding Summary in Base Currency	Commitment Funding Company Funds Company Funding Funds Manual Funding by Project Manual Funding by CBS Project Funding	Records Funded at Project level Records Funded at CBS level Transient Records Funded at Commitment level Transient Records Funded

Use this Data Source:	To get these details	Additional details:
	Records Funded at Commitment level	at Project level Transient Records Funded at CBS level CBS Funding
Shell / Funding Summary in Base Currency	Commitment Funding Funds Manual Funding by Project Manual Funding by CBS Project Funding Records Funded at Commitment level Records Funded at Project level	Records Funded at CBS level Transient Records Funded at Commitment level Transient Records Funded at Project level Transient Records Funded at CBS level CBS Funding
Shell/Project Schedule Summary	Finish Date	Start Date
Shell/Projects Custom	Type	Not applicable
Shell/CBS Cost Summary in Base Currency Shell/CBS Cost Summary in Default Currency	AFC Assigned Budget Company Budget Remaining Balance Company Budget Variance Company Commits Company Costs Company Forecasts Company Forecasts Variance Company Forecasts (Unaccepted) Company Manual Funding by CBS Company Revised Budget Company Spends Company CBS Funding Fixed Cost Funded Records	Labor Costs Non-Labor Costs Prior Forecasts Project Budget Remaining Balance Project Budget Variance Project Commits Project Costs Project Forecasts Project Forecasts Variance Project Forecasts (Unaccepted) Project Manual Funding by CBS Project Revised Budget Project Spends Project CBS Funding Resource Actuals Unfunded Records Yet To Buy

Asset Summary Sheet (Company-level)

Use this Data Source:	To get these details	Additional details:
Asset Attribute	Asset Prefix	Asset Class

CashFlow (Project/Shell)

Use this Data Source:	To get these details	Additional details:
Project Cash Flow	Base Commit Record Business Process Description Detail Level Name	Reference Elements Reference Elements No Rollup Status Time Scale By Time Scale Format
Curves	Curve Name Curve Type Datapoint Date Datapoint Value in Project Currency Datapoint Value in Transaction Currency Description From Date Line Number Name	Number Profile To Date Total in Project Currency Total in Transaction Currency Unassigned in Project Currency Unassigner in Transaction Currency CBS Code
Shell	Administrator Construction Type Creation Date Description Location Name Number Organization Category Phase Status	Shell Type Top Level Shell Name

Use this Data Source:	To get these details	Additional details:
Snapshots	Creator Date Created Title	Not applicable
Shell/Funding Summary in Base Currency	Project Funds Manual Funding by Project Manual Funding by CBS Project Funding	Records Funded at Project Level Records Funded at CBS Level CBS Funding
Shell/Projects Custom	Project Type	Not applicable
Shell/CBS Cost Summary in Base Currency Shell/CBS Cost Summary in Default Currency	AFC Assigned Budget Company Budget Remaining Balance Company Budget Variance Company Commits Company Costs Company Forecasts Company Forecasts Variance Company Forecasts (Unaccepted) Company Manual Funding by CBS Company Revised Budget Company Spends Company CBS Funding Fixed Costs Funded Records	Labor Costs Non-Labor Costs Prior Forecasts Project Budget Remaining Balance Project Budget Variance Project Commits Project Costs Project Forecasts Project Forecasts Variance Project Forecasts (Unaccepted) Project Manual Funding by CBS Project Revised Budget Project Spends Project CBS Funding Resource Actuals Unfunded Records Yet To Buy
Snapshots/Curves	Curve Name Curve Type Datapoint Date Datapoint Value in Project Currency Datapoint Value in Transaction Currency	From Date Profile To Date Total Total Project Unassigned Unassigned Project

CashFlow: Summary Snapshot (Project/Shell)

Use this Data Source:	To get these details	Additional details:
Project Summary CashFlow	Name	Status
Shell	Administrator Construction Type Creation Date Description Location Name Number Organization Category Phase	Project/Shell Mailbox email id Shell Type Status Top Level Shell Name
Snapshots	Creator Date Created	Title
Shell/ Funding Summary in Base Currency	Commitment Funding Funds Manual Funding by Project Manual Funding by CBS Project Funding Records Funded at Commitment level Records Funded at Project level	Records Funded at CBS Level Transient Records Funded at Commitment level Transient Records Funded at Project level Transient Records Funded at CBS level CBS Funding
Shell / Project Schedule Summary	Finish Date	Start Date
Shell/Projects Custom	Type	Not applicable
Shell/CBS Cost Summary in Base Currency Shell/CBS Cost Summary in Default Currency	AFC Assigned Budget Company Budget Remaining Balance Company Budget Variance Company Commits Company Costs Company Forecasts Company Forecasts Variance Company Forecasts	Labor Costs Non-Labor Costs Prior Forecasts Project Budget Remaining Balance Project Budget Variance Project Commits Project Costs Project Forecasts Project Forecasts Variance Project Forecasts

Use this Data Source:	To get these details	Additional details:
	(Unaccepted) Company Manual Funding by CBS Company Revised Budget Company Spends Company CBS Funding Fixed Costs Funded Records	(Unaccepted) Project Manual Funding by CBS Project Revised Budget Project Spends Project CBS Funding Resource Actuals Unfunded Records Yet To Buy
Snapshots / Curves	Curve Name Curve Type Datapoint Date Datapoint Value in Project Currency Datapoint Value in Transaction Currency	From Date Profile To Date Total Total Project Unassigned Unassigned Project

Commitment Funding

Use this Data Source:	To get these details	Additional details:
Commitment Funding	Name Description	Record No
Commitment Funding Sheet	Commitment Funding 1 to 25 Fund Balance Across All Funds Fund Balance By Discrete Fund Fund Code Fund Name Funding By All Funds	Funding By Discrete Fund Funding Ratio Across All Funds Records Funded Across All Funds Records Funded By Discrete Funds
Company	Company Contact Company Creation Date Company Description Company Name	Email Notifications Help URL Instructions Label

Use this Data Source:	To get these details	Additional details:
	Company Short Name Company URL Contact Email	Registry Share with Wire URL (eLearning)
Shell	Administrator Construction Type Creation Date Description Location Creation Date Name Number Organization Category Phase	Project / Shell email id Shell Type Status Top Level Shell Name
Company / Company Accounts Summary in Base Currency	Account Codes Assets	Projects Resource Actuals
Company / Company Funding Summary in Base Currency	Commitment Funding Company Funds Company Funding Funds Manual Funding by Project Manual Funding by CBS Project Funding Records Funded at Commitment level	Records Funded at Project level Records Funded at CBS level Transient Records Funded at Commitment level Transient Records Funded at Project level Transient Records Funded at CBS level CBS Funding
Shell / Funding Summary in Base Currency	Commitment Funding Funds Manual Funding by Project Manual Funding by CBS Project Funding Records Funded at Commitment level	Records Funded at Project level Records Funded at CBS level Transient Records Funded at Commitment level Transient Records Funded at

Use this Data Source:	To get these details	Additional details:
		Project level Transient Records Funded at CBS level CBS Funding
Shell/Project Schedule Summary	Finish Date	Start Date
Shell/Projects Custom	Type	NA
Shell/CBS Cost Summary in Base Currency Shell/CBS Cost Summary in Default Currency	AFC Assigned Budget Company Budget Remaining Balance Company Budget Variance Company Commits Company Costs Company Forecasts Company Forecasts Variance Company Forecasts (Unaccepted) Company Manual Funding by CBS Company Revised Budget Company Spends Company CBS Funding Fixed Cost Funded Records	Labor Costs Non-Labor Costs Prior Forecasts Project Budget Remaining Balance Project Budget Variance Project Commits Project Costs Project Forecasts Project Forecasts Variance Project Forecasts (Unaccepted) Project Manual Funding by CBS Project Revised Budget Project Spends Project CBS Funding Resource Actuals Unfunded Records Yet To Buy

Commitment Summary

Use this Data Source:	To get these details	Additional details:
Commitment Summary	Breakdown Description Breakdown Name	Commitment Base Record Commitment Description
Commitment Cost Attributes	Cost Code Code Name	Segments <any other generic cost

Use this Data Source:	To get these details	Additional details:
		attribute form fields>
Commitment Summary Sheet	[base commits, all statuses] [change commits, all statuses] [general spends, all statuses]	Commitment Summary 1 to 25 Commit Remaining Balance
Company	Company Contact Company Creation Date Company Description Company Name	Company Short Name Company URL Help URL Registry
Company / Company Accounts Summary in Base Currency	Account Codes Assets	Projects Resource Actuals
Company/Company Funding Summary in Base Currency	Commitment Funding Company Funds Company Funding Funds Manual Funding by Project Manual Funding by CBS Project Funding Records Funded at Commitment level	Records Funded at Project level Records Funded at CBS level Transient Records Funded at Commitment level Transient Records Funded at Project level Transient Records Funded at CBS level CBS Funding
Shell	Administrator Construction Type Creation Date Description Location Name Number Organization Category Phase	Shell Type Status Top Level Shell Name
Shell/CBS Cost Summary in Base Currency Shell/CBS Cost Summary in Default Currency	Project Costs Company Costs AFC Assigned Budget Company Budget	Funded Records Labor Costs Non-Labor Costs Prior Forecasts Project Budget Remaining

Use this Data Source:	To get these details	Additional details:
	Remaining Balance Company Budget Variance Company Commits Company Costs Company Forecasts Company Forecasts Variance Company Forecasts (Unaccepted) Company Manual Funding by CBS Company Revised Budget Company Spends Company CBS Funding Fixed Costs	Balance Project Budget Variance Project Commits Project Forecasts Project Forecasts Variance Project Forecasts (Unaccepted) Project Manual Funding by CBS Project Revised Budget Project Spends Project CBS Funding Resource Actuals Unfunded Records Yet To Buy

Company CashFlow

Use this Data Source:	To get these details	Additional details:
Company CashFlow	Description Name	Time Scale By Time Scale Format
Curves	Curve Name Datapoint Date Datapoint Value From Date	Project Name Project Number To Date
Shell	Administrator Construction Type Creation Date Description Location Name Number Organization Category Phase	Shell Type Status Top Level Shell Name
Snapshots	Creator Date Created	Title

Use this Data Source:	To get these details	Additional details:
Shell/Funding Summary in Base Currency	Commitment Funding Funds Manual Funding by Project Manual Funding by CBS Project Funding Records Funded at Commitment Level Records Funded at Project Level	Records Funded at CBS Level Transient Records Funded at Commitment Level Transient Records Funded at Project Level Transient Records Funded at CBS Level CBS Funding
Shell/Project Schedule Summary	Finish Date Start Date	Not applicable
Shell/Projects Custom	Project Type	Not applicable
Shell/CBS Cost Summary in Base Currency Shell/CBS Cost Summary in Default Currency	AFC Assigned Budget Company Budget Remaining Balance Company Budget Variance Company Commits Company Costs Company Forecasts Company Forecasts Variance Company Forecasts (Unaccepted) Company Manual Funding by CBS Company Revised Budget Company Spends Company CBS Funding Fixed Costs Funded Records	Labor Costs Non-Labor Costs Prior Forecasts Project Budget Remaining Balance Project Budget Variance Project Commits Project Costs Project Forecasts Project Forecasts Variance Project Forecasts (Unaccepted) Project Manual Funding by CBS Project Revised Budget Project Spends Project CBS Funding Resource Actuals Unfunded Records Yet To Buy
Snapshots/Curves	Curve Name Datapoint Date Datapoint Value	From Date To Date Unassigned

Use this Data Source:	To get these details	Additional details:
Company CashFlow Curves	Curve Datasource Curve Name Curve Type Datapoint Date	Datapoint Value End Date Granularity Start Date

Company Cost

Use this Data Source:	To get these details	Additional details:
Project Attribute	Project Number Project Name	Not applicable
CBS Cost	Project Costs Company Costs AFC Assigned Budget Company Budget Remaining Balance Company Budget Variance Company Commits Company Costs Company Forecasts Company Forecasts Variance Company Forecasts (Unaccepted) Company Manual Funding by CBS Company Revised Budget Company Spends Company CBS Funding Fixed Costs	Funded Records Labor Costs Non-Labor Costs Prior Forecasts Project Budget Remaining Balance Project Budget Variance Project Commits Project Forecasts Project Forecasts Variance Project Forecasts (Unaccepted) Project Manual Funding by CBS Project Revised Budget Project Spends Project CBS Funding Resource Actuals Unfunded Records Yet To Buy

Company Funding

Use this Data Source:	To get these details	Additional details:
Company	Company Contact Company Creation Date Company Description Company Name	Company Short Name Company URL Help URL Registry
Company/Company Accounts Summary in Base Currency	Account Codes Assets	Projects Resource Actuals
Company Funding	Fund Category Fund code Fund Description	Fund Long Description Fund Name
Company Funding Sheet	CBS Funding Records Funded at CBS Level Records Funded at Project Level Project Funding Manual Funding by CBS	Manual Funding by Project Project Funds Company Funds Company Funding
Company/Company Funding Summary in Base Currency	Commitment Funding Company Funds Company Funding Funds Manual Funding by Project Manual Funding by CBS Project Funding Records Funded at Commitment level	Records Funded at Project Level Records Funded at CBS Level Transient Records Funded at Commitment level Transient Records Funded at Project level Transient Records Funded at CBS level CBS Funding

Company User Information

Use this Data Source:	To get these details	Additional details:
Company User Information	Company Name Date Format Email	Mobile Phone Name Pager

Use this Data Source:	To get these details	Additional details:
	Fax First Name Home Phone Last Name Login User Name	Proxy Name Status Time Zone Title Work Phone
Company	Company Contact Company Description	Company Name Company Short Name DUNS
Group	Description Group Name Manager	Not applicable
User Preference	Default Login View Email Subscription File Transfer Option Viewer Option	Not applicable

Cost Sheet (CBS)

Use this Data Source:	To get these details	Additional details:
Project	Project Site Project Number Project Name	Project Status Project Phase Type
CBS Attribute	CBS Segments CBS Code CBS Item Summary CBS Summary Level Display Order WBE Segments	Cost Type Status Description Cost Attribute External Ref. ID Owner
CBS Cost	Project Costs BP Status AFC Assigned Budget Funded Records Unfunded Records	Yet To Buy Fixed Cost Labor Cost Non-Labor Cost Resource Actuals Transient Funded Records

Use this Data Source:	To get these details	Additional details:
	Prior Forecasts	
Work Package	Title Reference No. Creation Date	Description Owner

Cost Transactions (CBS)

Use this Data Source:	To get these details	Additional details:
BP Record	Record No. Title Due Date Approval Date Send Date	Reference Number Rate in Project Currency Rate in Base Currency Status Business Process Type
Line Item	Short Description Item No. Description	Effective Date Amount
Project	Project Site Project Number Project Name	Project Status Project Phase Project type
CBS	Datasource Type	Not applicable
CBS Attribute	CBS Segments CBS Code CBS Item Summary CBS Summary Level Display Order	Cost Type Status Description Cost Attribute External Ref. ID Owner
Work Package	Title Reference No. Creation Date	Description Owner

Use this Data Source:	To get these details	Additional details:
Commit Summary	CBS Base Commits (pending and approved) CBS Change Commits (pending and approved)	CBS General Spends (pending and approved)

Cost (Project/Shell)

Use this Data Source:	To get these details	Additional details:
Project	Project Site Project Number Project Name	Project Status Project Phase Type
CBS Attribute	CBS Segments CBS Item Summary CBS Summary Level Display Order Cost Type	Status Description Cost Attribute External Ref. ID Owner
CBS Cost	Project Costs AFC Assigned Budget Project Costs Fixed Costs Funded Records Unfunded Records Labor Costs Non-Labor Costs Prior Forecasts Project Budget Remaining Balance Project Budget Variance Project Commits	Project Forecasts Project Forecasts Variance Project Forecasts (Unaccepted) Project CBS Funding Project Manual Funding by CBS Project Revised Budget Project Spends Resource Actuals Yet To Buy Company Forecasts Variance Company CBS Funding Company Manual Funding by CBS

Cost Transactions MC (CBS)

Use this Data Source:	To get these details	Additional details:
BP Record	Record No. Title Due Date Approval Date Send Date	Reference Number Rate in Project Currency Rate in Base Currency Status Business Process Type
Line Item	Short Description Item No. Description	Effective Date Amount
Project	Project Site Project Number Project Name	Project Status Project Phase Project type
CBS	Datasource Type	Not applicable
CBS Attribute	CBS Segments CBS Code CBS Item Summary CBS Summary Level Display Order	Cost Type Status Description Cost Attribute External Ref. ID Owner
Work Package	Title Reference No. Creation Date	Description Owner
Commit Summary	CBS Base Commits (pending and approved) CBS Change Commits (pending and approved)	CBS General Spends(pending and approved)
Attachment - Attachment/Comment/Attachment - Attachment/Reference File - Attachment/Comment/Attachment/Reference File - Attachment/Comment/Attachment/Markup	File Name File Size Issue Date Publication Date Publication No.	Reference Status Revision No. Title Upload By

Use this Data Source:	To get these details	Additional details:
<ul style="list-style-type: none"> - General Comment/Attachment - General Comment/Attachment/Comment/Attachment - General Comment/Attachment/Reference File - General Comment/Attachment/Comment/ - Attachment/Reference File 		
<ul style="list-style-type: none"> - Attachment/Comment - General Comment - General Comment/Attachment/Comment 	Attachments Create Date Creator	Creator Company Text Comment
Attachment/Markup Attachment/Comment/Attachment/Markup	Cell Phone Company Name Company Short Name Creation Date Creator Email Fax First Name Home Phone	Last Name Login ID Markup Name Pager Registry Role Size Welcome Email Work Phone
Commit Summary/Cost Attributes	Cost Attribute Cost Type Description Display Order External Reference ID Owner	Status Summary Level summary CBS CBS Code CBS Item CBS code segments
Company	Company Contact Company Creation Date Company Description Company Name Company Short Name Company URL	Help URL Instructions Label Registry Share with Wire URL

Use this Data Source:	To get these details	Additional details:
Company/Company Accounts Summary in Base Currency	Account Codes Assets	Projects Resource Actuals
Company/Company Funding Summary in Base Currency	Commitment Funding Company Funds Company Funding Funds Manual Funding by Project Manual Funding by CBS Project Funding Records Funded at Commitment level	Records Funded at Project Level Records Funded at CBS Level Transient Records Funded at Commitment level Transient Records Funded at Project level Transient Records Funded at CBS level CBS Funding
Cost Record	Approval Date Base Currency Base Currency Label business Process Name Business Process Type Creator Due Date Project Currency Project Currency Label Rate in Base Currency Rate in Project Currency Record Amount	Record Amount in Base Currency Record Amount in Project Currency Record No. Reference Number Send Date Status Title Transaction Currency Transaction Currency Label Update SOV Status
General Comment/Attachment/Markup General Comment/Attachment/Comment/Attachment/Markup	Cell Phone Company Name Company Short Name Creation Date Creator Email Fax First Name Home Phone	Last Name Login ID Markup Name Pager Registry Role Size Welcome Email Work Phone

Use this Data Source:	To get these details	Additional details:
Line Item	Amount Amount in Base Currency Amount in Project Currency Description Effective Date Funding Source	Item No. Rolled Up Short Description CBS Code CBS Item Work Package
Line Item/Funding Source	Fund Category Fund Code Fund Description	Fund Long Description Fund Name
Line Item/CBS Code	Cost Attribute Cost type Description Display Order External Ref. ID	Owner Status Summary Level Summary CBS CBS Code CBS Item
Shell	Administrator Construction Type Description Location Creation Date Name Number Organization Category Phase Status	Project/Shell Mailbox email id Shell Type Status Top Level Shell Name

Cost Transactions MC (CBS) (continued)

Use this Data Source:	To get these details	Additional details:
Shell/CBS Cost Summary in Base Currency Shell/CBS Cost Summary in Default Currency	AFC Assigned Budget Company Budget Remaining Balance Company Budget Variance Company Commits Company Costs Company Forecasts Company Forecasts	Labor Costs Non-Labor Costs Prior Forecasts Project Budget Remaining Balance Project Budget Variance Project Commits Project Costs Project Forecasts

Use this Data Source:	To get these details	Additional details:
	Variance Company Forecasts (Unaccepted) Company Manual Funding by CBS Company Revised Budget Company Spends Company CBS Funding Fixed Costs Funded Records	Project Forecasts Variance Project Forecasts (Unaccepted) Project Manual Funding by CBS Project Revised Budget Project Spends Project CBS Funding Resource Actuals Unfunded Records Yet To Buy
Shell/Projects Custom	Project Type	Not applicable
Shell/Funding Summary in Base Currency	Commitment Funding Funds Manual Funding by Project Manual Funding by CBS Project Funding Records Funded at Commitment level Records Funded at Project level	Records Funded at CBS level Transient Records Funded at Commitment level Transient Records Funded at Project level Transient Records Funded at CBS level CBS Funding
Shell/Project Schedule Summary	Start Dates Finish Dates	Not applicable

Document Manager (Project/Shell)

Use this Data Source:	To get these details	Additional details:
Category	Category	Not applicable
Comment Comment/Attachment/Comment	Attachments Create Date Creator	Creator Company Text Comment
Comment/Attachment Comment/Attachment/Refer	File Name File Size	Not applicable

Use this Data Source:	To get these details	Additional details:
<p>ence File</p> <p>Comment/Attachment/Comment/Attachment</p> <p>Comment/Attachment/Comment/Attachment/Reference File</p> <p>Reference File</p> <p>Revision/Comment/Attachment/Reference File</p> <p>Revision/Reference File</p>	<p>Issue Date</p> <p>Publication Date</p> <p>Publication No.</p> <p>Reference Status</p> <p>Revision No.</p> <p>Title</p> <p>Upload By</p>	
<p>Comment/Attachment/Markup</p> <p>Comment/Attachment/Comment/Attachment/Markup</p> <p>Revision/Comment/Attachment/Markup</p>	<p>Cell Phone</p> <p>Company Name</p> <p>Company Short Name</p> <p>Creation Date</p> <p>Creator</p> <p>Email</p> <p>Fax</p> <p>First Name</p> <p>Home Phone</p>	<p>Last Name</p> <p>Login ID</p> <p>Markup Name</p> <p>Pager</p> <p>Registry</p> <p>Role</p> <p>Size</p> <p>Welcome Email</p> <p>Work Phone</p>
Company	<p>Company Contact</p> <p>Company Creation Date</p> <p>Company Description</p> <p>Company Name</p> <p>Company Short Name</p> <p>Company URL</p> <p>Contact Email</p>	<p>Email Notifications</p> <p>Help URL</p> <p>Instructions</p> <p>Label</p> <p>Registry</p> <p>Share with Wire URL</p>
Company/Company Accounts Summary in Base Currency	<p>Account Codes</p> <p>Assets</p>	<p>Projects</p> <p>Resource Actuals</p>
Company/Company Funding Summary in Base Currency	<p>Commitment Funding</p> <p>Company Funds</p> <p>Company Funding Funds</p> <p>Manual Funding by Project</p> <p>Manual Funding by CBS</p> <p>Project Funding</p> <p>Records Funded at Commitment level</p>	<p>Records Funded at CBS level</p> <p>Transient Records Funded at Commitment level</p> <p>Transient Records Funded at Project level</p> <p>Transient Records Funded at CBS level</p> <p>CBS Funding</p>

Use this Data Source:	To get these details	Additional details:
	Records Funded at Project level	
Document Attribute	% Complete Creation Date Description Issue Date Location Locked By Name Node Status Node Type	Owner Publication Date Publication No. Reference Node Type Reference Status Revision No. Size Title Uploaded By
Linked BP Record	Record No.	Not applicable
Markup Revision/Markup	Attachments Create Date Creator	Creator Company Status Text Comment
Phase	Phase	Not applicable
Owner	Cell Phone Company Name Company Short Name Creation Date Email Fax First Name Home Phone Last Name	Login ID Name Pager Registry Role Title Welcome Email Work Phone
Permission	Comment Copy Document/Shortcut Copy Folder Create Document/Shortcut Create Folder Delete Document/Shortcut Delete Folder Download Document	Group Name Modify Document/Shortcut Modify Document/Shortcut Permission Revise Document User Name View Document/Shortcut View Folder
Shell	Construction Type Description Location	Shell Type Top Level Shell Name

Use this Data Source:	To get these details	Additional details:
	Creation Date Name Number Organization Category Phase Status	
Shell/CBS Cost Summary in Base Currency Shell/CBS Cost Summary in Default Currency	AFC Assigned Budget Company Budget Remaining Balance Company Budget Variance Company Commits Company Costs Company Forecasts Company Forecasts Variance Company Forecasts (Unaccepted) Company Manual Funding by CBS Company Revised Budget Company Spends Company CBS Funding Fixed Costs Funded Records	Labor Costs Non-Labor Costs Prior Forecasts Project Budget Remaining Balance Project Budget Variance Project Commits Project Costs Project Forecasts Project Forecasts Variance Project Forecasts (Unaccepted) Project Manual Funding by CBS Project Revised Budget Project Spends Project CBS Funding Resource Actuals Unfunded Records Yet To Buy
Shell/Projects Custom	Project Type	Not applicable
Shell/Funding Summary in Base Currency	Commitment Funding Funds Manual Funding by Project Manual Funding by CBS Project Funding Records Funded at Commitment level Records Funded at Project level	Records Funded at CBS level Transient Records Funded at Commitment level Transient Records Funded at Project level Transient Records Funded at CBS level CBS Funding
Shell/Project Schedule Summary	Start Date Finish Date	Not applicable

Use this Data Source:	To get these details	Additional details:
Revision/Linked BP Record	Record No.	Not applicable

Document Manager (Company-level)

Use this Data Source:	To get these details	Additional details:
Comment Comment/Attachment/Comment Markup Revision Comment Revision/Markup	Attachments Create Date Creator Creator Company Text Comment	Not applicable
Comment/Attachment Comment/Attachment/Reference File Comment/Attachment/Comment/Attachment Comment/Attachment/Comment/Attachment/ Reference File Reference File Revision/Comment/Attachment Revision/Comment/Attachment/Reference File Revision/Reference File	File Name File Size Issue Date Publication Date Publication No. Reference Status Revision No. Title Upload By	Not applicable
Comment/Attachment/Markup Comment/Attachment/Comment/Attachment/Markup Revision/Comment/Attachment/Markup	Cell Phone Company Name Company Short Name Creation Date Creator Email Fax First Name Home Phone	Last Name Login ID Markup Name Pager Registry Role Size Welcome Email Work Phone
Company	Company Contact Company Creation Date Company Description	Email Notifications Help URL Instructions

Use this Data Source:	To get these details	Additional details:
	Company Name Company Short Name Company URL Contact Email	Label Registry Share with Wire URL
Company/Company Accounts Summary in Base Currency	Account Codes Assets	Projects Resource Actuals
Company/Company Funding Summary in Base Currency	Commitment Funding Company Funds Company Funding Funds Manual Funding by Project Manual Funding by CBS Project Funding Records Funded at Commitment level	Records Funded at Project Level Records Funded at CBS Level Transient Records Funded at Commitment level Transient Records Funded at Project level Transient Records Funded at CBS level CBS Funding
Document Attribute	% Complete Creation Date Description Issue Date Location Locked By Name Node Status Node Type	Owner Publication Date Publication No. Reference Node Type Reference Status Revision No. Size Title Uploaded By
Linked BP Record	Record No.	Not applicable
Owner	Cell Phone Company Name Company Short Name Creation Date Email Fax First Name Home Phone Last Name	Login ID Name Pager Registry Role Title Welcome Email Work Phone
Permission	Comment	Group Name

Use this Data Source:	To get these details	Additional details:
	Copy Document/Shortcut Copy Folder Create Document/Shortcut Create Folder Delete Document/Shortcut Delete Folder Download Document	Modify document/Shortcut Modify Document/Shortcut Permission Revise document User Name View document/Shortcut View Folder
Revision	File Name File Size Issue Date Owner Publication Date	Publication No. Reference Status Revision by Revision No. Title
Revision/Linked BP Record	Record No.	Not applicable

Funding

Use this Data Source:	To get these details	Additional details:
Company	Company Contact Company Creation Date Company Description Company Name Company Short Name Company URL Contact Email	Email Notifications Help URL Instructions Label Registry Share with Wire URL
Company/Company Accounts Summary in Base Currency	Account Codes Assets Projects Resource Actuals	Not applicable
Company Funding Sheet	CBS Funding Records Funded at CBS Level Records Funded at Project Level Project Funding Manual Funding by CBS	Manual Funding by Project Project Funds Company Funds Company Funding

Use this Data Source:	To get these details	Additional details:
Company/Company Funding Summary in Base Currency	Commitment Funding Company Funds Company Funding Funds Manual Funding by Project Manual Funding by CBS Project Funding Records Funded at Commitment level	Records Funded at Project Level Records Funded at CBS Level Transient Records Funded at Commitment Level Transient Records Funded at Project Level Transient Records Funded at CBS Level CBS Funding
Funding	Fund Category Fund Code Fund Description	Fund Long Description Fund Name
Funding Sheet	Manual Funding by Project Manual Funding by CBS Project Funding Records Funded at Project level	Records Funded at CBS level CBS Funding Funds
Shell/Projects Custom	Project Type	Not applicable
Shell/Funding Summary in Base Currency	Commitment Funding Funds Manual Funding by Project Manual Funding by CBS Project Funding Records Funded at Commitment level Records Funded at Project level	Records Funded at CBS level Transient Records Funded at Commitment level Transient Records Funded at Project level Transient Records Funded at CBS level CBS Funding
Shell/Project Schedule Summary	Start Dates Finish Dates	Not applicable
Shell	Administrator Construction Type Description Location Creation Date Name Number	Shell Type Top Level Shell Name

Use this Data Source:	To get these details	Additional details:
	Organization Category Phase Status	
Shell/CBS Cost Summary in Base Currency Shell/CBS Cost Summary in Default Currency	AFC Assigned Budget Company Budget Remaining Balance Company Budget Variance Company Commits Company Costs Company Forecasts Company Forecasts Variance Company Forecasts (Unaccepted) Company Manual Funding by CBS Company Revised Budget Company Spends Company CBS Funding Fixed Costs Funded Records	Labor Costs Non-Labor Costs Prior Forecasts Project Budget Remaining Balance Project Budget Variance Project Commits Project Costs Project Forecasts Project Forecasts Variance Project Forecasts (Unaccepted) Project Manual Funding by CBS Project Revised Budget Project Spends Project CBS Funding Resource Actuals Unfunded Records Yet To Buy

Gates

Use this Data Source:	To get these details	Additional details:
Project Gates	Auto Email as PDF Attachment End By Last Update Date Schedule Frequency	Setup Creator Setup Description Setup Name Setup Status
Company	Company Contact Company Creation Date Company Description Company Name Company Short Name	Email Notifications Help URL Instructions Label Registry

Use this Data Source:	To get these details	Additional details:
	Company URL Contact Email	Share with Wire URL
Company/Company Accounts Summary in Base Currency	Account Codes Assets	Projects Resource Actuals
Company/Company Funding Summary in Base Currency	Commitment Funding Company Funds Company Funding Manual Funding by Project Manual Funding by CBS Project Funding Records Funded at Commitment level Records Funded at Project level	Records Funded at CBS level Transient Records Funded at Commitment level Transient Records Funded at Project level Transient Records Funded at CBS level CBS Funding
Gate Phase	Advanced By Auto Advance to Next Project Phase Phase End Date	Phase Name Phase Order Phase Start Date Phase Status
Gate Phase/Comment	Attachments Create Date Creator	Creator Company Text Comment
Gate Phase/Comment/Attachmen t Gate Phase/Comment/Attachmen t/Reference	File Name File Size Issue Date Publication Date Publication No.	Reference Status Revision No. Title Upload By File
Gate Phase/Comment/Attachmen t/Markup	Cell Phone Company Name Company Short Name Creation Date Creator Email Fax First Name Home Phone	Last Name Login ID Markup Name Pager Registry Role Size Welcome Email Work Phone
Gate Phase/Gate Condition	Gate Element Condition	Gate Element Value

Use this Data Source:	To get these details	Additional details:
	Gate Element Name	Ignore Condition
Shell	Administrator Construction Type Description Location Creation Date Name Number Organization Category Phase Status	Shell Type Top Level Shell Name
Shell/CBS Cost Summary in Base Currency Shell/CBS Cost Summary in Default Currency	AFC Assigned Budget Company Budget Remaining Balance Company Budget Variance Company Commits Company Costs Company Forecasts Company Forecasts Variance Company Forecasts (Unaccepted) Company Manual Funding by CBS Company Revised Budget Company Spends Company CBS Funding Fixed Costs Funded Records	Labor Costs Non-Labor Costs Prior Forecasts Project Budget Remaining Balance Project Budget Variance Project Commits Project Costs Project Forecasts Project Forecasts Variance Project Forecasts (Unaccepted) Project Manual Funding by CBS Project Revised Budget Project Spends Project CBS Funding Resource Actuals Unfunded Records Yet To Buy
Shell/Projects Custom	Project Type	Not applicable
Shell/Funding Summary in Base Currency	Commitment Funding Funds Manual Funding by Project Manual Funding by CBS Project Funding Records Funded at	Records Funded at CBS level Transient Records Funded at Commitment level Transient Records Funded at Project level

Use this Data Source:	To get these details	Additional details:
	Commitment level Records Funded at Project level	Transient Records Funded at CBS level CBS Funding
Shell/Project Schedule Summary	Start Dates Finish Dates	Not applicable

Groups (Project/Shell)

Use this Data Source:	To get these details	Additional details:
Company	Company Name Company Contact	Company Short Name Active Status
Project Group	Group Name Description	Creation Date
Project User	Project Title Creation Date	Active Status
Project	Project Site Project Number Project Name	Project Status Project Phase Type
User	Login ID First Name Last Name Email Work Phone Home Phone Fax Cell Phone	Pager Role Welcome Email Title Creation Date Active Status User Name

Partner User Information

Use this Data Source:	To get these details	Additional details:
Partner User Information	Company Name Date Format Email	Mobile Phone Name Pager

Use this Data Source:	To get these details	Additional details:
	Fax First Name Home Phone Last Name Login User Name	Proxy Name Status Time Zone Title Work Phone
Partner	Company Contact Company Description Company Name	Company Short Name DUNS
Group	Description Group Name	Manager
User Preference	Default Login View Email Subscription	File Transfer Option Viewer Option

Planning Manager Items (Project/Shell)

Use this Data Source:	To get these details	Additional details:
Planning Manager for Project/Shell	Creator Due Date End Date Planning Item Project Picker	Record Last Update Date Record Number Status Title
Creator	Cell Phone Company Name Company Short Name Creation Date Email Fax First Name Home Phone Last Name	Login ID Name Pager Registry Role Title Welcome Email Work Phone

Planning Manager Sheets (Project/Shell)

Use this Data Source:	To get these details	Additional details:
Planning Manager for Project/Shell Sheet	Creator Last Update Date Name	NA

Resource Manager: All Actuals (Company-level)

Use this Data Source:	To get these details	Additional details:
All Actuals	Cost Date	Hours Timesheet BP Name
Resources	Address City Country Default Role Description Email Fax First Name Home Phone Last Name Mobile Phone Pager	Resource Created Date Resource Last Modified Resource Timezone Resource Capacity Resource Code Resource Name Resource Status State Time Zone Title Work Phone Zip code
Roles	Currency Name Description Role Created Date	Role Last Modified Role Name Role Status
Shell	Administrator Construction Type Creation Date Description Location Name Number Organization Category Phase	Project/Shell Mailbox email id Shell Type Status Top Level Shell Name
Shell/Funding Summary in	Commitment Funding	Records Funded at CBS

Use this Data Source:	To get these details	Additional details:
Base Currency	Funds Manual Funding by Project Manual Funding by CBS Project Funding Records Funded at Commitment level Records Funded at Project level	level Transient Records Funded at Commitment level Transient Records Funded at Project level Transient Records Funded at CBS level CBS Funding
Shell/Project Schedule Summary	Finish Date	Start Date
Shell/Projects Custom	Type	NA
Shell/CBS Cost Summary in Base Currency Shell/CBS Cost Summary in Default Currency	AFC Assigned Budget Company Budget Remaining Balance Company Budget Variance Company Commits Company Costs Company Forecasts Company Forecasts Variance Company Forecasts (Unaccepted) Company Manual Funding by CBS Company Revised Budget Company Spends Company CBS Funding Fixed Costs Funded Records	Labor Costs Non-Labor Costs Prior Forecasts Project Budget Remaining Balance Project Budget Variance Project Commits Project Costs Project Forecasts Project Forecasts Variance Project Forecasts (Unaccepted) Project Manual Funding by CBS Project Revised Budget Project Spends Project CBS Funding Resource Actuals Unfunded Records Yet To Buy

Resource Manager: Allocated Roles

Use this Data Source:	To get these details	Additional details:
Allocated Roles	Cost in Company Currency [Base Currency]	Total Hours

Use this Data Source:	To get these details	Additional details:
	Cost in Project Currency	
Roles	Currency Name Description Role Created Date	Role Last Modified Role Name Role Status
Shell	Administrator Construction Type Creation Date Description Location Name Number Organization Category Phase	Project/Shell Mailbox email id Shell Type Status Top Level Shell Name
Shell/Funding Summary in Base Currency	Commitment Funding Funds Manual Funding by Project Manual Funding by CBS Project Funding Records Funded at Commitment level Records Funded at Project level	Records Funded at CBS level Transient Records Funded at Commitment level Transient Records Funded at Project level Transient Records Funded at CBS level CBS Funding
Shell/Projects Schedule Summary	Finish Date	Start Date
Shell/Projects Custom	Type	NA
Shell/CBS Cost Summary in Base Currency Shell/CBS Cost Summary in Default Currency	AFC Assigned Budget Company Budget Remaining Balance Company Budget Variance Company Commits Company Costs Company Forecasts Company Forecasts Variance Company Forecasts (Unaccepted) Company Manual Funding	Labor Costs Non-Labor Costs Prior Forecasts Project Budget Remaining Balance Project Budget Variance Project Commits Project Costs Project Forecasts Project Forecasts Variance Project Forecasts (Unaccepted)

Use this Data Source:	To get these details	Additional details:
	by CBS Company Revised Budget Company Spends Company CBS Funding Fixed Costs Funded Records	Project Manual Funding by CBS Project Revised Budget Project Spends Project CBS Funding Resource Actuals Unfunded Records Yet To Buy

Resource Manager: Booked Resources

Use this Data Source:	To get these details	Additional details:
Booked Resources	Cost in Company Currency [Base Currency] Cost in Project Currency	Total Hours
Resources	Address City Country Default Role Description Email Fax First Name Home Phone Last Name Mobile Phone Pager	Resource Created Date Resource Last Modified Resource Timezone Resource Capacity Resource Code Resource Name Resource Status State Time Zone Title Work Phone Zip code
Roles	Currency Name Description Role Created Date	Role Last Modified Role Name Role Status
Shell	Administrator Construction Type Creation Date Description Location Name	Project/Shell Mailbox email id Shell Type Status Top Level Shell Name

Use this Data Source:	To get these details	Additional details:
	Number Organization Category Phase	
Shell/Funding Summary in Base Currency	Commitment Funding Funds Manual Funding by Project Manual Funding by CBS Project Funding Records Funded at Commitment level Records Funded at Project level	Records Funded at CBS level Transient Records Funded at Commitment level Transient Records Funded at Project level Transient Records Funded at CBS level CBS Funding
Shell/Projects Schedule Summary	Finish Date	Start Date
Shell/Projects Custom	Type	NA
Shell/CBS Cost Summary in Base Currency Shell/CBS Cost Summary in Default Currency	AFC Assigned Budget Company Budget Remaining Balance Company Budget Variance Company Commits Company Costs Company Forecasts Company Forecasts Variance Company Forecasts (Unaccepted) Company Manual Funding by CBS Company Revised Budget Company Spends Company CBS Funding Fixed Costs Funded Records	Labor Costs Non-Labor Costs Prior Forecasts Project Budget Remaining Balance Project Budget Variance Project Commits Project Costs Project Forecasts Project Forecasts Variance Project Forecasts (Unaccepted) Project Manual Funding by CBS Project Revised Budget Project Spends Project CBS Funding Resource Actuals Unfunded Records Yet To Buy

Resource Manager: Project Actuals

Use this Data Source:	To get these details	Additional details:
Project Actuals	Cost Date	Hours Timesheet BP Name
Resources	Address City Country Default Role Description Email Fax First Name Home Phone Last Name Mobile Phone Pager	Resource Created Date Resource Last Modified Resource Timezone Resource Capacity Resource Code Resource Name Resource Status State Time Zone Title Work Phone Zip code
Roles	Currency Name Description Role Created Date	Role Last Modified Role Name Role Status
Shell	Administrator Construction Type Creation Date Description Location Name Number Organization Category Phase	Project/Shell Mailbox email id Shell Type Status Top Level Shell Name
Shell/Funding Summary in Base Currency	Commitment Funding Funds Manual Funding by Project Manual Funding by CBS Project Funding Records Funded at Commitment level Records Funded at Project level	Records Funded at CBS level Transient Records Funded at Commitment level Transient Records Funded at Project level Transient Records Funded at CBS level CBS Funding

Use this Data Source:	To get these details	Additional details:
Shell/Projects Schedule Summary	Finish Date	Start Date
Shell/Projects Custom	Type	NA
Shell/CBS Cost Summary in Base Currency Shell/CBS Cost Summary in Default Currency	AFC Assigned Budget Company Budget Remaining Balance Company Budget Variance Company Commits Company Costs Company Forecasts Company Forecasts Variance Company Forecasts (Unaccepted) Company Manual Funding by CBS Company Revised Budget Company Spends Company CBS Funding Fixed Costs Funded Records	Labor Costs Non-Labor Costs Prior Forecasts Project Budget Remaining Balance Project Budget Variance Project Commits Project Costs Project Forecasts Project Forecasts Variance Project Forecasts (Unaccepted) Project Manual Funding by CBS Project Revised Budget Project Spends Project CBS Funding Resource Actuals Unfunded Records Yet To Buy

Resource Manager: Resources

Use this Data Source:	To get these details	Additional details:
Resources	Address City Country Default Role Description Email Fax First Name Home Phone	Resource Created Date Resource Last Modified Resource Timezone Resource Capacity Resource Code Resource Name Resource Status State Time Zone

Use this Data Source:	To get these details	Additional details:
	Last Name Mobile Phone Pager	Title Work Phone Zip code
Calendar	Calendar Date Earliest Booking Date Hours Latest Booking Date	Project Name Project Number Reason Type
Roles	Currency Name Description Role Created Date	Role Last Modified Role Name Role Status
Skills	Interest Proficiency	Skill Name

Resource Manager: Roles

Use this Data Source:	To get these details	Additional details:
Roles	Currency Name Description Role Created Date	Role Last Modified Role Name Role Status
Rates	Effective Date Last Modified	Overtime Rate Role Rate
Resources	Address City Country Default Role Description Email Fax First Name Home Phone Last Name Mobile Phone Pager	Resource Created Date Resource Last Modified Resource Timezone Resource Capacity Resource Code Resource Name Resource Status State Time Zone Title Work Phone Zip code

Resource Manager: Sheets

Use this Data Source:	To get these details	Additional details:
Sheets	Cost in Base Currency Cost in Project Currency Date	Hours Sheet Type
Resources	Address City Country Default Role Description Email Fax First Name Home Phone Last Name Mobile Phone Pager	Resource Created Date Resource Last Modified Resource Timezone Resource Capacity Resource Code Resource Name Resource Status State Time Zone Title Work Phone Zip code
Roles	Currency Name Description Role Created Date	Role Last Modified Role Name Role Status
Shell	Administrator Construction Type Creation Date Description Location Name Number Organization Category Phase	Project/Shell Mailbox email id Shell Type Status Top Level Shell Name
Shell/Funding Summary in Base Currency	Commitment Funding Funds Manual Funding by Project Manual Funding by CBS Project Funding Records Funded at Commitment level Records Funded at Project	Records Funded at CBS level Transient Records Funded at Commitment level Transient Records Funded at Project level Transient Records Funded at CBS level

Use this Data Source:	To get these details	Additional details:
	level	CBS Funding
Shell/Projects Schedule Summary	Finish Date	Start Date
Shell/Projects Custom	Type	NA
Shell/CBS Cost Summary in Base Currency Shell/CBS Cost Summary in Default Currency	AFC Assigned Budget Company Budget Remaining Balance Company Budget Variance Company Commits Company Costs Company Forecasts Company Forecasts Variance Company Forecasts (Unaccepted) Company Manual Funding by CBS Company Revised Budget Company Spends Company CBS Funding Fixed Costs Funded Records	Labor Costs Non-Labor Costs Prior Forecasts Project Budget Remaining Balance Project Budget Variance Project Commits Project Costs Project Forecasts Project Forecasts Variance Project Forecasts (Unaccepted) Project Manual Funding by CBS Project Revised Budget Project Spends Project CBS Funding Resource Actuals Unfunded Records Yet To Buy

Schedule (Project/Shell)

Use this Data Source:	To get these details	Additional details:
Project Schedule	Auto Control Description	Name Schedule Sheet Type
Activity	Activity Code Activity Costs (1 & 2) Activity ID Activity Latest Progress As Of Activity Name	Estimated Finish Date Estimated Start Date Filtered Group Finish Date Float Forecast Duration (1 & 2)

Use this Data Source:	To get these details	Additional details:
	Activity Percent Complete Activity Resources Activity Status Activity Total Costs Per CBS Activity Work Hours Actual Duration Actual Finish Date Actual Start Date Auto-update Activity Data Duration ETC Amount Early Finish Early Start Earned Amount Earned Progress Estimated Duration	Forecast Finish (1 & 2) Forecast Start Is Summary Row Late Finish Late Start Linked BP Name Non-Labor Costs Outline Level Outline Number Predecessor Record Number Record Status Show as Milestone Start Date Tag
Shell	Administrator Construction Type Creation Date Description Location Name Number Organization Category Phase	Project/Shell Mailbox email id Shell Type Status Top Level Shell Name
Activity/Dependency	Activity Name Lag Task Relation	NA
Activity/CBS Codes	Split Percent CBS Code CBS Item	NA
Shell/Funding Summary in Base Currency	Commitment Funding Funds Manual Funding by Project Manual Funding by CBS Project Funding Records Funded at	Records Funded at CBS Level Transient Records Funded at Commitment Level Transient Records Funded at Project Level Transient Records Funded

Use this Data Source:	To get these details	Additional details:
	Commitment Level Records Funded at Project Level	at CBS Level CBS Funding
Shell/Project Schedule Summary	Finish Date	Start Date
Shell/Projects Custom	Type	NA
Shell/CBS Cost Summary in Base Currency Shell/CBS Cost Summary in Default Currency	AFC Assigned Budget Company Budget Remaining Balance Company Budget Variance Company Commits Company Costs Company Forecasts Company Forecasts Variance Company Forecasts (Unaccepted) Company Manual Funding by CBS Company Revised Budget Company Spends Company CBS Funding Fixed Costs Funded Records	Labor Costs Non-Labor Costs Prior Forecasts Project Budget Remaining Balance Project Budget Variance Project Commits Project Costs Project Forecasts Project Forecasts Variance Project Forecasts (Unaccepted) Project Manual Funding by CBS Project Revised Budget Project Spends Project CBS Funding Resource Actuals Transient Funded Records Unfunded Records Yet To Buy

Schedule of Value (SOV)

Use this Data Source:	To get these details	Additional details:
SOV	Assignment Breakdown Description Breakdown Name	SOV Base Record SOV Description
Company	Company Contact Company Creation Date	Email Notifications Help URL

Use this Data Source:	To get these details	Additional details:
	Company Description Company Name Company Short Name Company URL Contact Email	Instructions Label Registry Share with Wire URL
SOV Cost Attributes	Cost Attribute Cost Type Description Display Order External Ref. ID Owner	Status Summary Level Summary CBS CBS Code CBS Item CBS Segments
SOV Sheet	Commits Remaining Balance	Scheduled Value
Shell	Construction Type Creation Date Description Location Name Number Organization Category Phase	Shell Type Status Top Level Shell Name
Company/Company Accounts Summary in Base Currency	Account Codes Assets	Projects Resource Actuals
Company/Company Funding Summary in Base Currency	Commitment Funding Funds Manual Funding by Project Manual Funding by CBS Project Funding Records Funded at Commitment level Records Funded at Project level	Records Funded at CBS level Transient Records Funded at Commitment level Transient Records Funded at Project level Transient Records Funded at CBS level CBS Funding
Shell/Funding Summary in Base Currency	Project Funds Manual Funding by Project Manual Funding by CBS Project Funding	Records Funded at Project Level Records Funded at CBS Level CBS Funding

Use this Data Source:	To get these details	Additional details:
Shell/Project Schedule Summary	Finish Date	Start Date
Shell/Projects Custom	Project Type	Not applicable
Shell/CBS Cost Summary in Base Currency Shell/CBS Cost Summary in Default Currency	AFC Assigned Budget Company Budget Remaining Balance Company Budget Variance Company Commits Company Costs Company Forecasts Company Forecasts Variance Company Forecasts (Unaccepted) Company Manual Funding by CBS Company Revised Budget Company Spends Company CBS Funding Fixed Costs Funded Records	Labor Costs Non-Labor Costs Prior Forecasts Project Budget Remaining Balance Project Budget Variance Project Commits Project Costs Project Forecasts Project Forecasts Variance Project Forecasts (Unaccepted) Project Manual Funding by CBS Project Revised Budget Project Spends Project CBS Funding Resource Actuals Unfunded Records Yet To Buy

Shell Information

Use this Data Source:	To get these details	Additional details:
Shell Information	Base Currency Base Currency Label Company Company name Default Currency Default Currency Label	Description Manager Name Number Organization Category Status
Company	Company Contact Company Creation Date Company Description	Email Notifications Help URL Instructions

Use this Data Source:	To get these details	Additional details:
	Company Name Company Short Name Company URL Contact URL Contact Email	Instructions (elearning) Label Registry Share with Wire URL
Shell	Administrator Construction Type Description Location Creation Date Name Number Organization Category Phase Status	Shell Type Top Level Shell Name
Company/ Accounts Summary in Base Currency	Account Codes Assets	Projects Resource Actuals
Company/ Company Funding Summary in Base Currency	Commitment Funding Company Funds Funds Manual Funding by Project Manual Funding by CBS Project Funding Records Funded at Commitment level	Records Funded at Project level Records Funded at CBS level Transient Records Funded at Commitment level Transient Records Funded at Project level Transient Records Funded at CBS level CBS Funding
Shell/ Funding Summary in Base Currency	Commitment Funding Funds Manual Funding by Project Manual Funding by CBS Project Funding Records Funded at Commitment level	Records Funded at Project level Records Funded at CBS level Transient Records Funded at Commitment level Transient Records Funded at Project level Transient Records Funded at CBS level

Use this Data Source:	To get these details	Additional details:
		CBS Funding
Shell / Project Schedule Summary	Finish Date	Start Date
Shell/Projects Custom	Type	Not applicable
Shell/CBS Cost Summary in Base Currency Shell/CBS Cost Summary in Default Currency	AFC Assigned Budget Company Budget Remaining Balance Company Budget Variance Company Commits Company Costs Company Forecasts Company Forecasts Variance Company Forecasts (Unaccepted) Company Manual Funding by CBS Company Revised Budget Company Spends Company CBS Funding Fixed Costs Funded Records	Labor Costs Non-Labor Costs Prior Forecasts Project Budget Remaining Balance Project Budget Variance Project Commits Project Costs Project Forecasts Project Forecasts Variance Project Forecasts (Unaccepted) Project Manual Funding by CBS Project Revised Budget Project Spends Project CBS Funding Resource Actuals Unfunded Records Yet To Buy

Users (Project/Shell)

Use this Data Source:	To get these details	Additional details:
Company	Company	Short Name
Project User	Project Title Active Status	Creation Date
Project	Project Name	Project Number
User	User Login Active Status First Name	Work Phone Home Phone Cell Phone

Use this Data Source:	To get these details	Additional details:
	Last Name Email Address	FAX Pager

Workflow Information

Use this Data Source:	To get these details	Additional details:
Workflow	Actual Duration Allowed Duration Business Process Name Due Date End Date Record Number	Record Title Setup Description Setup Name Start Date Workflow Status
Company	Company Contact Company Creation Date Company Description Company Name Company Short Name Company URL Contact URL Contact Email	Email Notifications Help URL Instructions Instructions (elearning) Label Registry Share with Wire URL
Shell and Projects	Administrator Construction Type Description Location Creation Date Name Number Organization Category Phase	Shell Type Status Top Level Shell Name

Use this Data Source:	To get these details	Additional details:
Sub-workflow Task/Sub-workflow	Sub-workflow Actual Duration Sub-workflow Allowed Duration Sub-workflow Description Sub-workflow Due Date	Sub-workflow End Date Sub-workflow Name Sub-workflow Start Date
Task	Sent For Sent From Task Action Task Actual Duration Task Allowed Duration	Task Due Date Task End Date Task Start Date To or CC Workflow Action
Company/Company Accounts Summary in Base Currency	Account Codes Assets	Projects Resource Actuals
Company/Company Funding Summary in Base Currency	Commitment Funding Company Funds Funds Manual Funding by Project Manual Funding by CBS Project Funding Records Funded at Commitment Level	Records Funded at Project Level Records Funded at CBS Level Transient Records Funded at Commitment Level Transient Records Funded at Project Level Transient Records Funded at CBS Level CBS Funding
Shell/Funding Summary in Base Currency	Commitment Funding Funds Manual Funding by Project Manual Funding by CBS Project Funding Records Funded at Commitment Level Records Funded at Project	Records Funded at CBS Level Transient Records Funded at Commitment Level Transient Records Funded at Project Level Transient Records Funded at CBS Level CBS Funding

Use this Data Source:	To get these details	Additional details:
	Level	
Shell/Project Schedule Summary	Finish Date	Start Date
Shell/Projects Custom	Project Type	Not applicable
Shell/CBS Cost Summary in Base Currency Shell/CBS Cost Summary in Default Currency	AFC Assigned Budget Company Budget Remaining Balance Company Budget Variance Company Commits Company Costs Company Forecasts Company Forecasts Variance Company Forecasts (Unaccepted) Company Manual Funding by CBS Company Revised Budget Company Spends Company CBS Funding Fixed Costs Funded Records	Labor Costs Non-Labor Costs Prior Forecasts Project Budget Remaining Balance Project Budget Variance Project Commits Project Costs Project Forecasts Project Forecasts Variance Project Forecasts (Unaccepted) Project Manual Funding by CBS Project Revised Budget Project Spends Project CBS Funding Resource Actuals Unfunded Records Yet To Buy
Task / Task Assignee and CC	Cell Phone Company Name Company Short Name Creation Date Email Fax First Name	Login ID Name Pager Registry Role Title Welcome Email

Use this Data Source:	To get these details	Additional details:
	Home Phone Last Name	Work Phone

Codes for Importing User Records

The tables in this section list valid entry codes for non-text-entry fields. Use these codes for importing user records into the system using CSV files. For information about importing records into the system, see the section on integration in the uDesigner User Guide.

In This Section

Currency	317
Time Zone	323
Server Time Zone.....	328
Date Format	346
User Type.....	348
Company Address.....	348
Status.....	348
Check Box.....	349

Currency

When importing Business Processes (BPs), you often must specify a project currency that the system can use for cost BPs and other calculations. You may need to enter the code corresponding to the currency used where the project is located. The currency can also be set in a user preference template.

The following tables list the supported currencies and their supporting codes.

Currencies and codes (A-G)

Currency Name	Code
Afghani	AFN
Algeria Dinar	DZD
Ariary	MGA
Australia Dollar	AUD
Azerbaijani Manat	AZN
Bahamas Dollar	BSD
Bahrain Dinar	BHD
Barbados Dollar	BBD
BCEAO Franc	XOF

Currency Name	Code
Belarus Ruble	BYR
Belize Dollar	BZD
Bermuda Dollar	BMD
Bhutan Ngultrum	BTN
Bolivia Boliviano	BOB
Botswana Pula	BWP
Brazil Real	BRL
Burundi Franc	BIF
Canada Dollar	CAD
Cape Verde Escudo	CVE
Cayman Islands Dollar	KYD
CFA Franc BEAC	XAF
Chile Peso	CLP
Chile UF	CLF
China Yuan Renminbi	CNY
Colombia Peso	COP
Comoros Franc	KMF
Comptoirs Francais du Pacifique Franc	XPF
Congo-Kinshasa Franc	CDF
Convertible Marka	BAM
Costa Rica Colon	CRC
Croatia Kuna	HRK
Cuba Peso	CUP
Cyprus Pound	CYP
Czech Republic Koruna	CZK
Denmark Krone	DKK
Dirham	AED
Djibouti Franc	DJF
Dobra	STD
Dominican Republic Peso	DOP
Dram	AMD

Currency Name	Code
East Caribbean Dollar	XCD
Egypt Pound	EGP
El Salvador Colon	SVC
Eritrea Nakfa	ERN
Estonia Kroon	EEK
Ethiopia Birr	ETB
Euro	EUR
Falkland Islands Pound	FKP
Fiji Dollar	FJD
Gambia Dalasi	GMD
Georgia Lari	GEL
Ghana New Cedi	GHs
Gibraltar Pound	GIP
Guatemala Quetzal	GTQ
Guilder	AWG
Guinea Franc	GNF
Guyana Dollar	GYD

Currencies and codes (H-N)

Currency Name	Code
Haiti Gourde	HTG
Honduras Lempira	HNL
Hong Kong Dollar	HKD
Hungary Forint	HUF
Iceland Krona	ISK
Indian Rupee	INR
Indonesia Rupiah	IDR
Iran Rial	IRR
Iraq Dinar	IQD

Currency Name	Code
Israel New Shekel	ILS
Jamaica Dollar	JMD
Jordan Dinar	JOD
Kazakhstan Tenge	KZT
Kenya Shilling	KES
Kuwait Dinar	KWD
Kwanza	AOA
Laos Kip	LAK
Latvia Lat	LVL
Lebanon Pound	LBP
Lek	ALL
Lesotho Loti	LSL
Lev	BGN
Liberia Dollar	LRD
Libya Dinar	LYD
Lithuania Litas	LTL
Macao Pataca	MOP
Macedonia Denar	MKD
Malawi Kwacha	MWK
Malaysia Ringgit	MYR
Maldives Rufiyaa	MVR
Malta Lira	MTL
Mauritania Ouguiya	MRO
Mauritius Rupee	MUR
Mexico Peso	MXN
Mongolia Tughrig	MNT
Morocco Dirham	MAD
Myanmar Kyat	MMK
Namibia Dollar	NAD
Nepal Rupee	NPR
Netherlands Antilles Guilder	ANG

Currency Name	Code
New Mozambique Metical	MZN
New Romania Leu	RON
New Turkish Lira	TRY
New Zealand Dollar	NZD
Nicaragua Gold Cordoba	NIO
Nigeria Naira	NGN
North Korea Won	KPW
Norway Krone	NOK

Currencies and codes (O-T)

Currency Name	Code
Oman Rial	OMR
Paanga	TOP
Pakistan Rupee	PKR
Panama Balboa	PAB
Papua New Guinea Kina	PGK
Paraguay Guarani	PYG
Peru Nuevo Sol	PEN
Peso	ARS
Philippines Peso	PHP
Poland Zloty	PLN
Pound Sterling	GBP
Qatar Riyal	QAR
Riel	KHR
Russia Ruble	RUB
Rwanda Franc	RWF
Saint Helena Pound	SHP
Saudi Arabia Riyal	SAR
Serbian Dinar	RSD

Currency Name	Code
Seychelles Rupee	SCR
Sierra Leone Leone	SLL
Singapore Dollar	SGD
Slovakia Koruna	SKK
Slovenia Tolar	SIT
Solomon Islands Dollar	SBD
Som	KGS
Somalia Shilling	SOS
South Africa Rand	ZAR
South Korea Won	KRW
South Sudanese Pound	SSP
Sri Lanka Rupee	LKR
Sudanese Dinar	SDG
Suriname Dollar	SDG
Sweden Krona	SEK
Switzerland Franc	CHF
Syria Pound	SYF
Taiwan New Dollar	TWD
Taka	BDT
Tala	WST
Tanzania Shilling	TZS
Thailand Baht	THB
Transnistria Moldova Leu	MDL
Trinidad and Tobago Dollar	TTD
Tunisia Dinar	TND
Turkmenistan Manat	TMM
Tuvalu Dollar	TVD

Currencies and codes (U-Z)

Currency Name	Code
Uganda Shilling	UGX
Ukraine Hryvna	UAH
United States Dollar	USD
Uruguay Peso	UYU
Uzbekistan Som	UZS
Vatu	VUV
Venezuela Bolivar Fuerte	VEF
Vietnam Dong	VND
Yemen Rial	YER
Yen	JPY
Zambia Kwacha	ZMK
Zimbabwe Dollar	ZWD

Time Zone

When importing user records, you must enter a starting time zone that the system can use for time stamps. You might want to enter the code corresponding to the company office where the user is located. Time zone is a user preference setting that the user can change later if necessary. The time zone can also be set in a user preference template.

About UTC

The Coordinated Universal Time (UTC) is a 24-hour time standard. The westernmost time zone uses UTC-12, being twelve hours behind UTC; the easternmost time zone, theoretically, uses UTC+12, being twelve hours ahead of UTC. Calculation of the UTC time standard is the same as with Greenwich Mean Time (GMT).

Note: The local time in London is the same as UTC time.

The following table lists the UTC time standards used in the system.

Code	Time Standard/Zone	Information	Type
10	UTC+13:00	Samoa	Pacific/Apia
20	UTC-12:00	International Date Line West	Etc/GMT+12
21	UTC-10:00	Hawaii	Pacific/Honolulu

Code	Time Standard/Zone	Information	Type
30	UTC-11:00	Coordinated Universal Time-11	Etc/GMT+11
40	UTC-09:00	Alaska	America/Anchorage
41	UTC-07:00	Chihuahua, La Paz, Mazatlan	America/Chihuahua
50	UTC-08:00	Pacific Time (US and Canada)	America/Los_Angeles
51	UTC-08:00	Baja California	America/Santa_Isabel
70	UTC-07:00	Arizona	America/Phoenix
71	UTC-07:00	Mountain Time (US and Canada)	America/Denver
80	UTC-06:00	Central America	America/Guatemala
90	UTC-06:00	Central Time (US and Canada)	America/Chicago
91	UTC-06:00	Saskatchewan	America/Regina
92	UTC-06:00	Guadalajara, Mexico City, Monterrey	America/Mexico_City
110	UTC-05:00	Eastern Time (US and Canada)	America/New_York
111	UTC-05:00	Indiana (East)	America/Indianapolis
112	UTC-05:00	Bogota, Lima, Quito	America/Bogota
130	UTC-04:00	Atlantic Time (Canada)	America/Halifax
131	UTC-04:30	Caracas	America/Caracas
132	UTC-04:00	Asuncion	America/Asuncion
133	UTC-04:00	Cuiaba	America/Cuiaba
134	UTC-04:00	Georgetown, La Paz, Manaus, San Juan	America/La_Paz
135	UTC-04:00	Santiago	America/Santiago
140	UTC-03:30	Newfoundland	America/St_Johns
150	UTC-03:00	Brasilia	America/Sao_Paulo
151	UTC-03:00	Buenos Aires	America/Buenos_Aires

Code	Time Standard/Zone	Information	Type
			es
152	UTC-03:00	Cayenne, Fortaleza	America/Cayenne
153	UTC-03:00	Greenland	America/Godthab
154	UTC-03:00	Montevideo	America/Montevideo
155	UTC-03:00	Salvador	America/Bahia
160	UTC-02:00	Coordinated Universal Time-02	Etc/GMT+2
170	UTC-01:00	Azores	Atlantic/Azores
171	UTC-01:00	Cape Verde Is.	Atlantic/Cape_Verde
180	UTC	Dublin, Edinburgh, Lisbon, London	Europe/London
181	UTC	Dublin	Europe/Dublin
182	UTC	Casablanca	Africa/Casablanca
183	UTC	Coordinated Universal Time	Etc/GMT
184	UTC	Monrovia, Reykjavik	Atlantic/Reykjavik
200	UTC+01:00	Amsterdam	Europe/Amsterdam
201	UTC+01:00	Brussels, Copenhagen, Madrid, Paris	Europe/Paris
202	UTC+01:00	Belgrade, Bratislava, Budapest, Ljubljana, Prague	Europe/Budapest
203	UTC+01:00	Amsterdam, Berlin, Bern, Rome, Stockholm, Vienna	Europe/Berlin
204	UTC+01:00	Sarajevo, Skopje, Warsaw, Zagreb	Europe/Warsaw
205	UTC+01:00	West Central Africa	Africa/Lagos
206	UTC+01:00	Windhoek	Africa/Windhoek
210	UTC+02:00	Athens, Bucharest	Europe/Bucharest
211	UTC+02:00	Cairo	Africa/Cairo
212	UTC+02:00	Beirut	Asia/Beirut
213	UTC+02:00	Jerusalem	Asia/Jerusalem

Code	Time Standard/Zone	Information	Type
214	UTC+02:00	Helsinki, Kyiv, Riga, Sofia, Tallinn, Vilnius	Europe/Helsinki
215	UTC+02:00	Harare, Pretoria	Africa/Johannesburg
220	UTC+02:00	Damascus	Asia/Damascus
221	UTC+02:00	Istanbul	Europe/Istanbul
222	UTC+02:00	Tripoli	Africa/Tripoli
223	UTC+03:00	Amman	Asia/Amman
224	UTC+03:00	Kaliningrad, Minsk	Europe/Kaliningrad
225	UTC+03:00	Kuwait, Riyadh	Asia/Riyadh
230	UTC+03:00	Nairobi	Africa/Nairobi
231	UTC+04:00	Moscow, St. Petersburg, Volgograd	Europe/Moscow
232	UTC+03:00	Baghdad	Asia/Baghdad
240	UTC+03:30	Tehran	Asia/Tehran
250	UTC+04:00	Abu Dhabi, Muscat	Asia/Dubai
251	UTC+04:00	Baku	Asia/Baku
252	UTC+04:00	Port Louis	Indian/Mauritius
253	UTC+04:00	Tbilisi	Asia/Tbilisi
254	UTC+04:00	Yerevan	Asia/Yerevan
260	UTC+04:30	Kabul	Asia/Kabul
261	UTC+05:00	Ashgabat, Tashkent	Asia/Tashkent
270	UTC+06:00	Yekaterinburg	Asia/Yekaterinburg
280	UTC+05:00	Islamabad, Karachi	Asia/Karachi
290	UTC+05:30	Chennai, Kolkata, Mumbai, New Delhi	Asia/Calcutta
300	UTC+06:00	Astana	Asia/Almaty
301	UTC+06:00	Dhaka	Asia/Dhaka
302	UTC+06:30	Yangon (Rangoon)	Asia/Rangoon
310	UTC+07:00	Bangkok, Hanoi, Jakarta	Asia/Bangkok
311	UTC+08:00	Krasnoyarsk	Asia/Krasnoyarsk

Code	Time Standard/Zone	Information	Type
320	UTC+08:00	Perth	Australia/Perth
321	UTC+08:00	Beijing, Chongqing, Hong Kong, Urumqi	Asia/Shanghai
322	UTC+08:00	Kuala Lumpur, Singapore	Asia/Singapore
323	UTC+08:00	Taipei	Asia/Taipei
324	UTC+09:00	Irkutsk	Asia/Irkutsk
340	UTC+09:00	Seoul	Asia/Seoul
341	UTC+09:00	Osaka, Sapporo, Tokyo	Asia/Tokyo
342	UTC+10:00	Yakutsk	Asia/Yakutsk
350	UTC+09:30	Darwin	Australia/Darwin
351	UTC+09:30	Adelaide	Australia/Adelaide
360	UTC+10:00	Brisbane	Australia/Brisbane
361	UTC+10:00	Canberra, Melbourne, Sydney	Australia/Sydney
362	UTC+10:00	Hobart	Australia/Hobart
363	UTC+11:00	Vladivostok	Asia/Vladivostok
364	UTC+10:00	Guam, Port Moresby	Pacific/Port_Moresby
380	UTC+07:00	Novosibirsk	Asia/Novosibirsk
390	UTC+08:00	Ulaanbaatar	Asia/Ulaanbaatar
391	UTC+11:00	Solomon Is., New Caledonia	Pacific/Guadalcanal
392	UTC+12:00	Magadan	Asia/Magadan
400	UTC+12:00	Coordinated Universal Time+12	Etc/GMT-12
410	UTC+12:00	Fiji	Pacific/Fiji
411	UTC+12:00	Auckland, Wellington	Antarctica/McMurdo
420	UTC+13:00	Nuku'alofa	Pacific/Tongatapu
430	UTC+05:30	Sri Jayawardenepura	Asia/Colombo
440	UTC+05:45	Kathmandu	Asia/Katmandu

Server Time Zone

The following is a list of available server time zones supported by JDK.

- 1 Zone Name = Greenwich Mean Time, Zone Id = Africa/Abidjan, Offset = (GMT + 00:00)
- 2 Zone Name = Ghana Mean Time, Zone Id = Africa/Accra, Offset = (GMT + 00:00)
- 3 Zone Name = Eastern African Time, Zone Id = Africa/Addis_Ababa, Offset = (GMT + 03:00)
- 4 Zone Name = Central European Time, Zone Id = Africa/Algiers, Offset = (GMT + 01:00)
- 5 Zone Name = Eastern African Time, Zone Id = Africa/Asmara, Offset = (GMT + 03:00)
- 6 Zone Name = Eastern African Time, Zone Id = Africa/Asmera, Offset = (GMT + 03:00)
- 7 Zone Name = Greenwich Mean Time, Zone Id = Africa/Bamako, Offset = (GMT + 00:00)
- 8 Zone Name = Western African Time, Zone Id = Africa/Bangui, Offset = (GMT + 01:00)
- 9 Zone Name = Greenwich Mean Time, Zone Id = Africa/Banjul, Offset = (GMT + 00:00)
- 10 Zone Name = Greenwich Mean Time, Zone Id = Africa/Bissau, Offset = (GMT + 00:00)
- 11 Zone Name = Central African Time, Zone Id = Africa/Blantyre, Offset = (GMT + 02:00)
- 12 Zone Name = Western African Time, Zone Id = Africa/Brazzaville, Offset = (GMT + 01:00)
- 13 Zone Name = Central African Time, Zone Id = Africa/Bujumbura, Offset = (GMT + 02:00)
- 14 Zone Name = Eastern European Time, Zone Id = Africa/Cairo, Offset = (GMT + 02:00)
- 15 Zone Name = Western European Time, Zone Id = Africa/Casablanca, Offset = (GMT + 00:00)
- 16 Zone Name = Central European Time, Zone Id = Africa/Ceuta, Offset = (GMT + 01:00)
- 17 Zone Name = Greenwich Mean Time, Zone Id = Africa/Conakry, Offset = (GMT + 00:00)
- 18 Zone Name = Greenwich Mean Time, Zone Id = Africa/Dakar, Offset = (GMT + 00:00)
- 19 Zone Name = Eastern African Time, Zone Id = Africa/Dar_es_Salaam, Offset = (GMT + 03:00)
- 20 Zone Name = Eastern African Time, Zone Id = Africa/Djibouti, Offset = (GMT + 03:00)
- 21 Zone Name = Western African Time, Zone Id = Africa/Douala, Offset = (GMT + 01:00)
- 22 Zone Name = Western European Time, Zone Id = Africa/EI_Aaiun, Offset = (GMT + 00:00)
- 23 Zone Name = Greenwich Mean Time, Zone Id = Africa/Freetown, Offset = (GMT + 00:00)
- 24 Zone Name = Central African Time, Zone Id = Africa/Gaborone, Offset = (GMT + 02:00)
- 25 Zone Name = Central African Time, Zone Id = Africa/Harare, Offset = (GMT + 02:00)
- 26 Zone Name = South Africa Standard Time, Zone Id = Africa/Johannesburg, Offset = (GMT + 02:00)
- 27 Zone Name = Eastern African Time, Zone Id = Africa/Juba, Offset = (GMT + 03:00)
- 28 Zone Name = Eastern African Time, Zone Id = Africa/Kampala, Offset = (GMT + 03:00)
- 29 Zone Name = Eastern African Time, Zone Id = Africa/Khartoum, Offset = (GMT + 03:00)
- 30 Zone Name = Central African Time, Zone Id = Africa/Kigali, Offset = (GMT + 02:00)
- 31 Zone Name = Western African Time, Zone Id = Africa/Kinshasa, Offset = (GMT + 01:00)
- 32 Zone Name = Western African Time, Zone Id = Africa/Lagos, Offset = (GMT + 01:00)
- 33 Zone Name = Western African Time, Zone Id = Africa/Libreville, Offset = (GMT + 01:00)

34 Zone Name = Greenwich Mean Time, Zone Id = Africa/Lome, Offset = (GMT + 00:00)
35 Zone Name = Western African Time, Zone Id = Africa/Luanda, Offset = (GMT + 01:00)
36 Zone Name = Central African Time, Zone Id = Africa/Lubumbashi, Offset = (GMT + 02:00)
37 Zone Name = Central African Time, Zone Id = Africa/Lusaka, Offset = (GMT + 02:00)
38 Zone Name = Western African Time, Zone Id = Africa/Malabo, Offset = (GMT + 01:00)
39 Zone Name = Central African Time, Zone Id = Africa/Maputo, Offset = (GMT + 02:00)
40 Zone Name = South Africa Standard Time, Zone Id = Africa/Maseru, Offset = (GMT + 02:00)
41 Zone Name = South Africa Standard Time, Zone Id = Africa/Mbabane, Offset = (GMT + 02:00)
42 Zone Name = Eastern African Time, Zone Id = Africa/Mogadishu, Offset = (GMT + 03:00)
43 Zone Name = Greenwich Mean Time, Zone Id = Africa/Monrovia, Offset = (GMT + 00:00)
44 Zone Name = Eastern African Time, Zone Id = Africa/Nairobi, Offset = (GMT + 03:00)
45 Zone Name = Western African Time, Zone Id = Africa/Ndjamena, Offset = (GMT + 01:00)
46 Zone Name = Western African Time, Zone Id = Africa/Niamey, Offset = (GMT + 01:00)
47 Zone Name = Greenwich Mean Time, Zone Id = Africa/Nouakchott, Offset = (GMT + 00:00)
48 Zone Name = Greenwich Mean Time, Zone Id = Africa/Ouagadougou, Offset = (GMT + 00:00)
49 Zone Name = Western African Time, Zone Id = Africa/Porto-Novo, Offset = (GMT + 01:00)
50 Zone Name = Greenwich Mean Time, Zone Id = Africa/Sao_Tome, Offset = (GMT + 00:00)
51 Zone Name = Greenwich Mean Time, Zone Id = Africa/Timbuktu, Offset = (GMT + 00:00)
52 Zone Name = Eastern European Time, Zone Id = Africa/Tripoli, Offset = (GMT + 02:00)
53 Zone Name = Central European Time, Zone Id = Africa/Tunis, Offset = (GMT + 01:00)
54 Zone Name = Western African Time, Zone Id = Africa/Windhoek, Offset = (GMT + 02:00)
55 Zone Name = Hawaii Standard Time, Zone Id = America/Adak, Offset = (GMT - 10:00)
56 Zone Name = Alaska Standard Time, Zone Id = America/Anchorage, Offset = (GMT - 09:00)
57 Zone Name = Atlantic Standard Time, Zone Id = America/Anguilla, Offset = (GMT - 04:00)
58 Zone Name = Atlantic Standard Time, Zone Id = America/Antigua, Offset = (GMT - 04:00)
59 Zone Name = Brasilia Time, Zone Id = America/Araguaina, Offset = (GMT - 03:00)
60 Zone Name = Argentine Time, Zone Id = America/Argentina/Buenos_Aires, Offset = (GMT - 03:00)
61 Zone Name = Argentine Time, Zone Id = America/Argentina/Catamarca, Offset = (GMT - 03:00)
62 Zone Name = Argentine Time, Zone Id = America/Argentina/ComodRivadavia, Offset = (GMT - 03:00)
63 Zone Name = Argentine Time, Zone Id = America/Argentina/Cordoba, Offset = (GMT - 03:00)
64 Zone Name = Argentine Time, Zone Id = America/Argentina/Jujuy, Offset = (GMT - 03:00)
65 Zone Name = Argentine Time, Zone Id = America/Argentina/La_Rioja, Offset = (GMT - 03:00)
66 Zone Name = Argentine Time, Zone Id = America/Argentina/Mendoza, Offset = (GMT - 03:00)
67 Zone Name = Argentine Time, Zone Id = America/Argentina/Rio_Gallegos, Offset = (GMT - 03:00)

68 Zone Name = Argentine Time, Zone Id = America/Argentina/Salta, Offset = (GMT - 03:00)
69 Zone Name = Argentine Time, Zone Id = America/Argentina/San_Juan, Offset = (GMT - 03:00)
70 Zone Name = Argentine Time, Zone Id = America/Argentina/San_Luis, Offset = (GMT - 03:00)
71 Zone Name = Argentine Time, Zone Id = America/Argentina/Tucuman, Offset = (GMT - 03:00)
72 Zone Name = Argentine Time, Zone Id = America/Argentina/Ushuaia, Offset = (GMT - 03:00)
73 Zone Name = Atlantic Standard Time, Zone Id = America/Aruba, Offset = (GMT - 04:00)
74 Zone Name = Paraguay Time, Zone Id = America/Asuncion, Offset = (GMT - 03:00)
75 Zone Name = Eastern Standard Time, Zone Id = America/Atikokan, Offset = (GMT - 05:00)
76 Zone Name = Hawaii Standard Time, Zone Id = America/Atka, Offset = (GMT - 10:00)
77 Zone Name = Brasilia Time, Zone Id = America/Bahia, Offset = (GMT - 03:00)
78 Zone Name = Central Standard Time, Zone Id = America/Bahia_Banderas, Offset = (GMT - 06:00)
79 Zone Name = Atlantic Standard Time, Zone Id = America/Barbados, Offset = (GMT - 04:00)
80 Zone Name = Brasilia Time, Zone Id = America/Belem, Offset = (GMT - 03:00)
81 Zone Name = Central Standard Time, Zone Id = America/Belize, Offset = (GMT - 06:00)
82 Zone Name = Atlantic Standard Time, Zone Id = America/Blanc-Sablon, Offset = (GMT - 04:00)
83 Zone Name = Amazon Time, Zone Id = America/Boa_Vista, Offset = (GMT - 04:00)
84 Zone Name = Colombia Time, Zone Id = America/Bogota, Offset = (GMT - 05:00)
85 Zone Name = Mountain Standard Time, Zone Id = America/Boise, Offset = (GMT - 07:00)
86 Zone Name = Argentine Time, Zone Id = America/Buenos_Aires, Offset = (GMT - 03:00)
87 Zone Name = Mountain Standard Time, Zone Id = America/Cambridge_Bay, Offset = (GMT - 07:00)
88 Zone Name = Amazon Time, Zone Id = America/Campo_Grande, Offset = (GMT - 03:00)
89 Zone Name = Eastern Standard Time, Zone Id = America/Cancun, Offset = (GMT - 05:00)
90 Zone Name = Venezuela Time, Zone Id = America/Caracas, Offset = (GMT - 04:00)
91 Zone Name = Argentine Time, Zone Id = America/Catamarca, Offset = (GMT - 03:00)
92 Zone Name = French Guiana Time, Zone Id = America/Cayenne, Offset = (GMT - 03:00)
93 Zone Name = Eastern Standard Time, Zone Id = America/Cayman, Offset = (GMT - 05:00)
94 Zone Name = Central Standard Time, Zone Id = America/Chicago, Offset = (GMT - 06:00)
95 Zone Name = Mountain Standard Time, Zone Id = America/Chihuahua, Offset = (GMT - 07:00)
96 Zone Name = Eastern Standard Time, Zone Id = America/Coral_Harbour, Offset = (GMT - 05:00)
97 Zone Name = Argentine Time, Zone Id = America/Cordoba, Offset = (GMT - 03:00)
98 Zone Name = Central Standard Time, Zone Id = America/Costa_Rica, Offset = (GMT - 06:00)
99 Zone Name = Mountain Standard Time, Zone Id = America/Creston, Offset = (GMT - 07:00)
100 Zone Name = Amazon Time, Zone Id = America/Cuiaba, Offset = (GMT - 03:00)

101 Zone Name = Atlantic Standard Time, Zone Id = America/Curacao, Offset = (GMT - 04:00)
102 Zone Name = Greenwich Mean Time, Zone Id = America/Danmarkshavn, Offset = (GMT + 00:00)
103 Zone Name = Pacific Standard Time, Zone Id = America/Dawson, Offset = (GMT - 08:00)
104 Zone Name = Mountain Standard Time, Zone Id = America/Dawson_Creek, Offset = (GMT - 07:00)
105 Zone Name = Mountain Standard Time, Zone Id = America/Denver, Offset = (GMT - 07:00)
106 Zone Name = Eastern Standard Time, Zone Id = America/Detroit, Offset = (GMT - 05:00)
107 Zone Name = Atlantic Standard Time, Zone Id = America/Dominica, Offset = (GMT - 04:00)
108 Zone Name = Mountain Standard Time, Zone Id = America/Edmonton, Offset = (GMT - 07:00)
109 Zone Name = Acre Time, Zone Id = America/Eirunepe, Offset = (GMT - 05:00)
110 Zone Name = Central Standard Time, Zone Id = America/El_Salvador, Offset = (GMT - 06:00)
111 Zone Name = Pacific Standard Time, Zone Id = America/Ensenada, Offset = (GMT - 08:00)
112 Zone Name = Mountain Standard Time, Zone Id = America/Fort_Nelson, Offset = (GMT - 07:00)
113 Zone Name = Eastern Standard Time, Zone Id = America/Fort_Wayne, Offset = (GMT - 05:00)
114 Zone Name = Brasilia Time, Zone Id = America/Fortaleza, Offset = (GMT - 03:00)
115 Zone Name = Atlantic Standard Time, Zone Id = America/Glace_Bay, Offset = (GMT - 04:00)
116 Zone Name = Western Greenland Time, Zone Id = America/Godthab, Offset = (GMT - 03:00)
117 Zone Name = Atlantic Standard Time, Zone Id = America/Goose_Bay, Offset = (GMT - 04:00)
118 Zone Name = Atlantic Standard Time, Zone Id = America/Grand_Turk, Offset = (GMT - 04:00)
119 Zone Name = Atlantic Standard Time, Zone Id = America/Grenada, Offset = (GMT - 04:00)
120 Zone Name = Atlantic Standard Time, Zone Id = America/Guadeloupe, Offset = (GMT - 04:00)
121 Zone Name = Central Standard Time, Zone Id = America/Guatemala, Offset = (GMT - 06:00)
122 Zone Name = Ecuador Time, Zone Id = America/Guayaquil, Offset = (GMT - 05:00)
123 Zone Name = Guyana Time, Zone Id = America/Guyana, Offset = (GMT - 04:00)
124 Zone Name = Atlantic Standard Time, Zone Id = America/Halifax, Offset = (GMT - 04:00)
125 Zone Name = Cuba Standard Time, Zone Id = America/Havana, Offset = (GMT - 05:00)
126 Zone Name = Mountain Standard Time, Zone Id = America/Hermosillo, Offset = (GMT - 07:00)
127 Zone Name = Eastern Standard Time, Zone Id = America/Indiana/Indianapolis, Offset = (GMT - 05:00)

128 Zone Name = Central Standard Time, Zone Id = America/Indiana/Knox, Offset = (GMT - 06:00)

129 Zone Name = Eastern Standard Time, Zone Id = America/Indiana/Marengo, Offset = (GMT - 05:00)

130 Zone Name = Eastern Standard Time, Zone Id = America/Indiana/Petersburg, Offset = (GMT - 05:00)

131 Zone Name = Central Standard Time, Zone Id = America/Indiana/Tell_City, Offset = (GMT - 06:00)

132 Zone Name = Eastern Standard Time, Zone Id = America/Indiana/Vevay, Offset = (GMT - 05:00)

133 Zone Name = Eastern Standard Time, Zone Id = America/Indiana/Vincennes, Offset = (GMT - 05:00)

134 Zone Name = Eastern Standard Time, Zone Id = America/Indiana/Winamac, Offset = (GMT - 05:00)

135 Zone Name = Eastern Standard Time, Zone Id = America/Indianapolis, Offset = (GMT - 05:00)

136 Zone Name = Mountain Standard Time, Zone Id = America/Inuvik, Offset = (GMT - 07:00)

137 Zone Name = Eastern Standard Time, Zone Id = America/Iqaluit, Offset = (GMT - 05:00)

138 Zone Name = Eastern Standard Time, Zone Id = America/Jamaica, Offset = (GMT - 05:00)

139 Zone Name = Argentine Time, Zone Id = America/Jujuy, Offset = (GMT - 03:00)

140 Zone Name = Alaska Standard Time, Zone Id = America/Juneau, Offset = (GMT - 09:00)

141 Zone Name = Eastern Standard Time, Zone Id = America/Kentucky/Louisville, Offset = (GMT - 05:00)

142 Zone Name = Eastern Standard Time, Zone Id = America/Kentucky/Monticello, Offset = (GMT - 05:00)

143 Zone Name = Central Standard Time, Zone Id = America/Knox_IN, Offset = (GMT - 06:00)

144 Zone Name = Atlantic Standard Time, Zone Id = America/Kralendijk, Offset = (GMT - 04:00)

145 Zone Name = Bolivia Time, Zone Id = America/La_Paz, Offset = (GMT - 04:00)

146 Zone Name = Peru Time, Zone Id = America/Lima, Offset = (GMT - 05:00)

147 Zone Name = Pacific Standard Time, Zone Id = America/Los_Angeles, Offset = (GMT - 08:00)

148 Zone Name = Eastern Standard Time, Zone Id = America/Louisville, Offset = (GMT - 05:00)

149 Zone Name = Atlantic Standard Time, Zone Id = America/Lower_Princes, Offset = (GMT - 04:00)

150 Zone Name = Brasilia Time, Zone Id = America/Maceio, Offset = (GMT - 03:00)

151 Zone Name = Central Standard Time, Zone Id = America/Managua, Offset = (GMT - 06:00)

152 Zone Name = Amazon Time, Zone Id = America/Manaus, Offset = (GMT - 04:00)

153 Zone Name = Atlantic Standard Time, Zone Id = America/Marigot, Offset = (GMT - 04:00)

154 Zone Name = Atlantic Standard Time, Zone Id = America/Martinique, Offset = (GMT - 04:00)

155 Zone Name = Central Standard Time, Zone Id = America/Matamoros, Offset = (GMT - 06:00)

156 Zone Name = Mountain Standard Time, Zone Id = America/Mazatlan, Offset = (GMT - 07:00)
157 Zone Name = Argentine Time, Zone Id = America/Mendoza, Offset = (GMT - 03:00)
158 Zone Name = Central Standard Time, Zone Id = America/Menominee, Offset = (GMT - 06:00)
159 Zone Name = Central Standard Time, Zone Id = America/Merida, Offset = (GMT - 06:00)
160 Zone Name = Alaska Standard Time, Zone Id = America/Metlakatla, Offset = (GMT - 09:00)
161 Zone Name = Central Standard Time, Zone Id = America/Mexico_City, Offset = (GMT - 06:00)
162 Zone Name = Pierre & Miquelon Standard Time, Zone Id = America/Miquelon, Offset = (GMT - 03:00)
163 Zone Name = Atlantic Standard Time, Zone Id = America/Moncton, Offset = (GMT - 04:00)
164 Zone Name = Central Standard Time, Zone Id = America/Monterrey, Offset = (GMT - 06:00)
165 Zone Name = Uruguay Time, Zone Id = America/Montevideo, Offset = (GMT - 03:00)
166 Zone Name = Eastern Standard Time, Zone Id = America/Montreal, Offset = (GMT - 05:00)
167 Zone Name = Atlantic Standard Time, Zone Id = America/Montserrat, Offset = (GMT - 04:00)
168 Zone Name = Eastern Standard Time, Zone Id = America/Nassau, Offset = (GMT - 05:00)
169 Zone Name = Eastern Standard Time, Zone Id = America/New_York, Offset = (GMT - 05:00)
170 Zone Name = Eastern Standard Time, Zone Id = America/Nipigon, Offset = (GMT - 05:00)
171 Zone Name = Alaska Standard Time, Zone Id = America/Nome, Offset = (GMT - 09:00)
172 Zone Name = Fernando de Noronha Time, Zone Id = America/Noronha, Offset = (GMT - 02:00)
173 Zone Name = Central Standard Time, Zone Id = America/North_Dakota/Beulah, Offset = (GMT - 06:00)
174 Zone Name = Central Standard Time, Zone Id = America/North_Dakota/Center, Offset = (GMT - 06:00)
175 Zone Name = Central Standard Time, Zone Id = America/North_Dakota/New_Salem, Offset = (GMT - 06:00)
176 Zone Name = Mountain Standard Time, Zone Id = America/Ojinaga, Offset = (GMT - 07:00)
177 Zone Name = Eastern Standard Time, Zone Id = America/Panama, Offset = (GMT - 05:00)
178 Zone Name = Eastern Standard Time, Zone Id = America/Pangnirtung, Offset = (GMT - 05:00)
179 Zone Name = Suriname Time, Zone Id = America/Paramaribo, Offset = (GMT - 03:00)
180 Zone Name = Mountain Standard Time, Zone Id = America/Phoenix, Offset = (GMT - 07:00)
181 Zone Name = Eastern Standard Time, Zone Id = America/Port-au-Prince, Offset = (GMT - 05:00)
182 Zone Name = Atlantic Standard Time, Zone Id = America/Port_of_Spain, Offset = (GMT - 04:00)
183 Zone Name = Acre Time, Zone Id = America/Porto_Acre, Offset = (GMT - 05:00)
184 Zone Name = Amazon Time, Zone Id = America/Porto_Velho, Offset = (GMT - 04:00)

185 Zone Name = Atlantic Standard Time, Zone Id = America/Puerto_Rico, Offset = (GMT - 04:00)

186 Zone Name = Central Standard Time, Zone Id = America/Rainy_River, Offset = (GMT - 06:00)

187 Zone Name = Central Standard Time, Zone Id = America/Rankin_Inlet, Offset = (GMT - 06:00)

188 Zone Name = Brasilia Time, Zone Id = America/Recife, Offset = (GMT - 03:00)

189 Zone Name = Central Standard Time, Zone Id = America/Regina, Offset = (GMT - 06:00)

190 Zone Name = Central Standard Time, Zone Id = America/Resolute, Offset = (GMT - 06:00)

191 Zone Name = Acre Time, Zone Id = America/Rio_Branco, Offset = (GMT - 05:00)

192 Zone Name = Argentine Time, Zone Id = America/Rosario, Offset = (GMT - 03:00)

193 Zone Name = Pacific Standard Time, Zone Id = America/Santa_Isabel, Offset = (GMT - 08:00)

194 Zone Name = Brasilia Time, Zone Id = America/Santarem, Offset = (GMT - 03:00)

195 Zone Name = Chile Time, Zone Id = America/Santiago, Offset = (GMT - 03:00)

196 Zone Name = Atlantic Standard Time, Zone Id = America/Santo_Domingo, Offset = (GMT - 04:00)

197 Zone Name = Brasilia Time, Zone Id = America/Sao_Paulo, Offset = (GMT - 02:00)

198 Zone Name = Eastern Greenland Time, Zone Id = America/Scoresbysund, Offset = (GMT - 01:00)

199 Zone Name = Mountain Standard Time, Zone Id = America/Shiprock, Offset = (GMT - 07:00)

200 Zone Name = Alaska Standard Time, Zone Id = America/Sitka, Offset = (GMT - 09:00)

201 Zone Name = Atlantic Standard Time, Zone Id = America/St_Barthelemy, Offset = (GMT - 04:00)

202 Zone Name = Newfoundland Standard Time, Zone Id = America/St_Johns, Offset = (GMT - 03:30)

203 Zone Name = Atlantic Standard Time, Zone Id = America/St_Kitts, Offset = (GMT - 04:00)

204 Zone Name = Atlantic Standard Time, Zone Id = America/St_Lucia, Offset = (GMT - 04:00)

205 Zone Name = Atlantic Standard Time, Zone Id = America/St_Thomas, Offset = (GMT - 04:00)

206 Zone Name = Atlantic Standard Time, Zone Id = America/St_Vincent, Offset = (GMT - 04:00)

207 Zone Name = Central Standard Time, Zone Id = America/Swift_Current, Offset = (GMT - 06:00)

208 Zone Name = Central Standard Time, Zone Id = America/Tegucigalpa, Offset = (GMT - 06:00)

209 Zone Name = Atlantic Standard Time, Zone Id = America/Thule, Offset = (GMT - 04:00)

210 Zone Name = Eastern Standard Time, Zone Id = America/Thunder_Bay, Offset = (GMT - 05:00)

211 Zone Name = Pacific Standard Time, Zone Id = America/Tijuana, Offset = (GMT - 08:00)

212 Zone Name = Eastern Standard Time, Zone Id = America/Toronto, Offset = (GMT - 05:00)

213 Zone Name = Atlantic Standard Time, Zone Id = America/Tortola, Offset = (GMT - 04:00)
214 Zone Name = Pacific Standard Time, Zone Id = America/Vancouver, Offset = (GMT - 08:00)
215 Zone Name = Atlantic Standard Time, Zone Id = America/Virgin, Offset = (GMT - 04:00)
216 Zone Name = Pacific Standard Time, Zone Id = America/Whitehorse, Offset = (GMT - 08:00)
217 Zone Name = Central Standard Time, Zone Id = America/Winnipeg, Offset = (GMT - 06:00)
218 Zone Name = Alaska Standard Time, Zone Id = America/Yakutat, Offset = (GMT - 09:00)
219 Zone Name = Mountain Standard Time, Zone Id = America/Yellowknife, Offset = (GMT - 07:00)
220 Zone Name = Australian Western Standard Time, Zone Id = Antarctica/Casey, Offset = (GMT + 08:00)
221 Zone Name = Davis Time, Zone Id = Antarctica/Davis, Offset = (GMT + 07:00)
222 Zone Name = Dumont-d'Urville Time, Zone Id = Antarctica/DumontDUrville, Offset = (GMT + 10:00)
223 Zone Name = Macquarie Island Standard Time, Zone Id = Antarctica/Macquarie, Offset = (GMT + 11:00)
224 Zone Name = Mawson Time, Zone Id = Antarctica/Mawson, Offset = (GMT + 05:00)
225 Zone Name = New Zealand Standard Time, Zone Id = Antarctica/McMurdo, Offset = (GMT + 13:00)
226 Zone Name = Chile Time, Zone Id = Antarctica/Palmer, Offset = (GMT - 03:00)
227 Zone Name = Rothera Time, Zone Id = Antarctica/Rothera, Offset = (GMT - 03:00)
228 Zone Name = New Zealand Standard Time, Zone Id = Antarctica/South_Pole, Offset = (GMT + 13:00)
229 Zone Name = Syowa Time, Zone Id = Antarctica/Syowa, Offset = (GMT + 03:00)
230 Zone Name = Coordinated Universal Time, Zone Id = Antarctica/Troll, Offset = (GMT + 00:00)
231 Zone Name = Vostok Time, Zone Id = Antarctica/Vostok, Offset = (GMT + 06:00)
232 Zone Name = Central European Time, Zone Id = Arctic/Longyearbyen, Offset = (GMT + 01:00)
233 Zone Name = Arabia Standard Time, Zone Id = Asia/Aden, Offset = (GMT + 03:00)
234 Zone Name = Alma-Ata Time, Zone Id = Asia/Almaty, Offset = (GMT + 06:00)
235 Zone Name = Eastern European Time, Zone Id = Asia/Amman, Offset = (GMT + 02:00)
236 Zone Name = Anadyr Time, Zone Id = Asia/Anadyr, Offset = (GMT + 12:00)
237 Zone Name = Aqtau Time, Zone Id = Asia/Aqtau, Offset = (GMT + 05:00)
238 Zone Name = Aqtobe Time, Zone Id = Asia/Aqtobe, Offset = (GMT + 05:00)
239 Zone Name = Turkmenistan Time, Zone Id = Asia/Ashgabat, Offset = (GMT + 05:00)
240 Zone Name = Turkmenistan Time, Zone Id = Asia/Ashkhabad, Offset = (GMT + 05:00)
241 Zone Name = Arabia Standard Time, Zone Id = Asia/Baghdad, Offset = (GMT + 03:00)
242 Zone Name = Arabia Standard Time, Zone Id = Asia/Bahrain, Offset = (GMT + 03:00)
243 Zone Name = Azerbaijan Time, Zone Id = Asia/Baku, Offset = (GMT + 04:00)
244 Zone Name = Indochina Time, Zone Id = Asia/Bangkok, Offset = (GMT + 07:00)

245 Zone Name = GMT+07:00, Zone Id = Asia/Barnaul, Offset = (GMT + 07:00)
246 Zone Name = Eastern European Time, Zone Id = Asia/Beirut, Offset = (GMT + 02:00)
247 Zone Name = Kirgizstan Time, Zone Id = Asia/Bishkek, Offset = (GMT + 06:00)
248 Zone Name = Brunei Time, Zone Id = Asia/Brunei, Offset = (GMT + 08:00)
249 Zone Name = India Standard Time, Zone Id = Asia/Calcutta, Offset = (GMT + 05:30)
250 Zone Name = Yakutsk Time, Zone Id = Asia/Chita, Offset = (GMT + 09:00)
251 Zone Name = Choibalsan Time, Zone Id = Asia/Choibalsan, Offset = (GMT + 08:00)
252 Zone Name = China Standard Time, Zone Id = Asia/Chongqing, Offset = (GMT + 08:00)
253 Zone Name = China Standard Time, Zone Id = Asia/Chungking, Offset = (GMT + 08:00)
254 Zone Name = India Standard Time, Zone Id = Asia/Colombo, Offset = (GMT + 05:30)
255 Zone Name = Bangladesh Time, Zone Id = Asia/Dacca, Offset = (GMT + 06:00)
256 Zone Name = Eastern European Time, Zone Id = Asia/Damascus, Offset = (GMT + 02:00)
257 Zone Name = Bangladesh Time, Zone Id = Asia/Dhaka, Offset = (GMT + 06:00)
258 Zone Name = Timor-Leste Time, Zone Id = Asia/Dili, Offset = (GMT + 09:00)
259 Zone Name = Gulf Standard Time, Zone Id = Asia/Dubai, Offset = (GMT + 04:00)
260 Zone Name = Tajikistan Time, Zone Id = Asia/Dushanbe, Offset = (GMT + 05:00)
261 Zone Name = Eastern European Time, Zone Id = Asia/Gaza, Offset = (GMT + 02:00)
262 Zone Name = China Standard Time, Zone Id = Asia/Harbin, Offset = (GMT + 08:00)
263 Zone Name = Eastern European Time, Zone Id = Asia/Hebron, Offset = (GMT + 02:00)
264 Zone Name = Indochina Time, Zone Id = Asia/Ho_Chi_Minh, Offset = (GMT + 07:00)
265 Zone Name = Hong Kong Time, Zone Id = Asia/Hong_Kong, Offset = (GMT + 08:00)
266 Zone Name = Hovd Time, Zone Id = Asia/Hovd, Offset = (GMT + 07:00)
267 Zone Name = Irkutsk Time, Zone Id = Asia/Irkutsk, Offset = (GMT + 08:00)
268 Zone Name = Eastern European Time, Zone Id = Asia/Istanbul, Offset = (GMT + 02:00)
269 Zone Name = West Indonesia Time, Zone Id = Asia/Jakarta, Offset = (GMT + 07:00)
270 Zone Name = East Indonesia Time, Zone Id = Asia/Jayapura, Offset = (GMT + 09:00)
271 Zone Name = Israel Standard Time, Zone Id = Asia/Jerusalem, Offset = (GMT + 02:00)
272 Zone Name = Afghanistan Time, Zone Id = Asia/Kabul, Offset = (GMT + 04:30)
273 Zone Name = Petropavlovsk-Kamchatski Time, Zone Id = Asia/Kamchatka, Offset = (GMT + 12:00)
274 Zone Name = Pakistan Time, Zone Id = Asia/Karachi, Offset = (GMT + 05:00)
275 Zone Name = Xinjiang Standard Time, Zone Id = Asia/Kashgar, Offset = (GMT + 06:00)
276 Zone Name = Nepal Time, Zone Id = Asia/Kathmandu, Offset = (GMT + 05:45)
277 Zone Name = Nepal Time, Zone Id = Asia/Katmandu, Offset = (GMT + 05:45)
278 Zone Name = Yakutsk Time, Zone Id = Asia/Khandyga, Offset = (GMT + 09:00)
279 Zone Name = India Standard Time, Zone Id = Asia/Kolkata, Offset = (GMT + 05:30)
280 Zone Name = Krasnoyarsk Time, Zone Id = Asia/Krasnoyarsk, Offset = (GMT + 07:00)
281 Zone Name = Malaysia Time, Zone Id = Asia/Kuala_Lumpur, Offset = (GMT + 08:00)
282 Zone Name = Malaysia Time, Zone Id = Asia/Kuching, Offset = (GMT + 08:00)
283 Zone Name = Arabia Standard Time, Zone Id = Asia/Kuwait, Offset = (GMT + 03:00)

284 Zone Name = China Standard Time, Zone Id = Asia/Macao, Offset = (GMT + 08:00)
285 Zone Name = China Standard Time, Zone Id = Asia/Macau, Offset = (GMT + 08:00)
286 Zone Name = Magadan Time, Zone Id = Asia/Magadan, Offset = (GMT + 11:00)
287 Zone Name = Central Indonesia Time, Zone Id = Asia/Makassar, Offset = (GMT + 08:00)
288 Zone Name = Philippines Time, Zone Id = Asia/Manila, Offset = (GMT + 08:00)
289 Zone Name = Gulf Standard Time, Zone Id = Asia/Muscat, Offset = (GMT + 04:00)
290 Zone Name = Eastern European Time, Zone Id = Asia/Nicosia, Offset = (GMT + 02:00)
291 Zone Name = Krasnoyarsk Time, Zone Id = Asia/Novokuznetsk, Offset = (GMT + 07:00)
292 Zone Name = Novosibirsk Time, Zone Id = Asia/Novosibirsk, Offset = (GMT + 06:00)
293 Zone Name = Omsk Time, Zone Id = Asia/Omsk, Offset = (GMT + 06:00)
294 Zone Name = Oral Time, Zone Id = Asia/Oral, Offset = (GMT + 05:00)
295 Zone Name = Indochina Time, Zone Id = Asia/Phnom_Penh, Offset = (GMT + 07:00)
296 Zone Name = West Indonesia Time, Zone Id = Asia/Pontianak, Offset = (GMT + 07:00)
297 Zone Name = Korea Standard Time, Zone Id = Asia/Pyongyang, Offset = (GMT + 08:30)
298 Zone Name = Arabia Standard Time, Zone Id = Asia/Qatar, Offset = (GMT + 03:00)
299 Zone Name = Qyzylorda Time, Zone Id = Asia/Qyzylorda, Offset = (GMT + 06:00)
300 Zone Name = Myanmar Time, Zone Id = Asia/Rangoon, Offset = (GMT + 06:30)
301 Zone Name = Arabia Standard Time, Zone Id = Asia/Riyadh, Offset = (GMT + 03:00)
302 Zone Name = Indochina Time, Zone Id = Asia/Saigon, Offset = (GMT + 07:00)
303 Zone Name = Sakhalin Time, Zone Id = Asia/Sakhalin, Offset = (GMT + 11:00)
304 Zone Name = Uzbekistan Time, Zone Id = Asia/Samarkand, Offset = (GMT + 05:00)
305 Zone Name = Korea Standard Time, Zone Id = Asia/Seoul, Offset = (GMT + 09:00)
306 Zone Name = China Standard Time, Zone Id = Asia/Shanghai, Offset = (GMT + 08:00)
307 Zone Name = Singapore Time, Zone Id = Asia/Singapore, Offset = (GMT + 08:00)
308 Zone Name = Srednekolymsk Time, Zone Id = Asia/Srednekolymsk, Offset = (GMT + 11:00)
309 Zone Name = China Standard Time, Zone Id = Asia/Taipei, Offset = (GMT + 08:00)
310 Zone Name = Uzbekistan Time, Zone Id = Asia/Tashkent, Offset = (GMT + 05:00)
311 Zone Name = Georgia Time, Zone Id = Asia/Tbilisi, Offset = (GMT + 04:00)
312 Zone Name = Iran Standard Time, Zone Id = Asia/Tehran, Offset = (GMT + 03:30)
313 Zone Name = Israel Standard Time, Zone Id = Asia/Tel_Aviv, Offset = (GMT + 02:00)
314 Zone Name = Bhutan Time, Zone Id = Asia/Thimbu, Offset = (GMT + 06:00)
315 Zone Name = Bhutan Time, Zone Id = Asia/Thimphu, Offset = (GMT + 06:00)
316 Zone Name = Japan Standard Time, Zone Id = Asia/Tokyo, Offset = (GMT + 09:00)
317 Zone Name = GMT+07:00, Zone Id = Asia/Tomsk, Offset = (GMT + 07:00)
318 Zone Name = Central Indonesia Time, Zone Id = Asia/Ujung_Pandang, Offset = (GMT + 08:00)
319 Zone Name = Ulaanbaatar Time, Zone Id = Asia/Ulaanbaatar, Offset = (GMT + 08:00)
320 Zone Name = Ulaanbaatar Time, Zone Id = Asia/Ulan_Bator, Offset = (GMT + 08:00)
321 Zone Name = Xinjiang Standard Time, Zone Id = Asia/Urumqi, Offset = (GMT + 06:00)
322 Zone Name = Ust-Nera Time, Zone Id = Asia/Ust-Nera, Offset = (GMT + 10:00)

323 Zone Name = Indochina Time, Zone Id = Asia/Vientiane, Offset = (GMT + 07:00)
324 Zone Name = Vladivostok Time, Zone Id = Asia/Vladivostok, Offset = (GMT + 10:00)
325 Zone Name = Yakutsk Time, Zone Id = Asia/Yakutsk, Offset = (GMT + 09:00)
326 Zone Name = Yekaterinburg Time, Zone Id = Asia/Yekaterinburg, Offset = (GMT + 05:00)
327 Zone Name = Armenia Time, Zone Id = Asia/Yerevan, Offset = (GMT + 04:00)
328 Zone Name = Azores Time, Zone Id = Atlantic/Azores, Offset = (GMT - 01:00)
329 Zone Name = Atlantic Standard Time, Zone Id = Atlantic/Bermuda, Offset = (GMT - 04:00)
330 Zone Name = Western European Time, Zone Id = Atlantic/Canary, Offset = (GMT + 00:00)
331 Zone Name = Cape Verde Time, Zone Id = Atlantic/Cape_Verde, Offset = (GMT - 01:00)
332 Zone Name = Western European Time, Zone Id = Atlantic/Faeroe, Offset = (GMT + 00:00)
333 Zone Name = Western European Time, Zone Id = Atlantic/Faroe, Offset = (GMT + 00:00)
334 Zone Name = Central European Time, Zone Id = Atlantic/Jan_Mayen, Offset = (GMT + 01:00)
335 Zone Name = Western European Time, Zone Id = Atlantic/Madeira, Offset = (GMT + 00:00)
336 Zone Name = Greenwich Mean Time, Zone Id = Atlantic/Reykjavik, Offset = (GMT + 00:00)
337 Zone Name = South Georgia Standard Time, Zone Id = Atlantic/South_Georgia, Offset = (GMT - 02:00)
338 Zone Name = Greenwich Mean Time, Zone Id = Atlantic/St_Helena, Offset = (GMT + 00:00)
339 Zone Name = Falkland Is. Time, Zone Id = Atlantic/Stanley, Offset = (GMT - 03:00)
340 Zone Name = Australian Eastern Standard Time (New South Wales), Zone Id = Australia/ACT, Offset = (GMT + 11:00)
341 Zone Name = Australian Central Standard Time (South Australia), Zone Id = Australia/Adelaide, Offset = (GMT + 10:30)
342 Zone Name = Australian Eastern Standard Time (Queensland), Zone Id = Australia/Brisbane, Offset = (GMT + 10:00)
343 Zone Name = Australian Central Standard Time (South Australia/New South Wales), Zone Id = Australia/Broken_Hill, Offset = (GMT + 10:30)
344 Zone Name = Australian Eastern Standard Time (New South Wales), Zone Id = Australia/Canberra, Offset = (GMT + 11:00)
345 Zone Name = Australian Eastern Standard Time (New South Wales), Zone Id = Australia/Currie, Offset = (GMT + 11:00)
346 Zone Name = Australian Central Standard Time (Northern Territory), Zone Id = Australia/Darwin, Offset = (GMT + 09:30)
347 Zone Name = Australian Central Western Standard Time, Zone Id = Australia/Eucla, Offset = (GMT + 08:45)
348 Zone Name = Australian Eastern Standard Time (Tasmania), Zone Id = Australia/Hobart, Offset = (GMT + 11:00)
349 Zone Name = Lord Howe Standard Time, Zone Id = Australia/LHI, Offset = (GMT + 11:00)
350 Zone Name = Australian Eastern Standard Time (Queensland), Zone Id = Australia/Lindeman, Offset = (GMT + 10:00)
351 Zone Name = Lord Howe Standard Time, Zone Id = Australia/Lord_Howe, Offset = (GMT + 11:00)

352 Zone Name = Australian Eastern Standard Time (Victoria), Zone Id = Australia/Melbourne, Offset = (GMT + 11:00)

353 Zone Name = Australian Eastern Standard Time (New South Wales), Zone Id = Australia/NSW, Offset = (GMT + 11:00)

354 Zone Name = Australian Central Standard Time (Northern Territory), Zone Id = Australia/North, Offset = (GMT + 09:30)

355 Zone Name = Australian Western Standard Time, Zone Id = Australia/Perth, Offset = (GMT + 08:00)

356 Zone Name = Australian Eastern Standard Time (Queensland), Zone Id = Australia/Queensland, Offset = (GMT + 10:00)

357 Zone Name = Australian Central Standard Time (South Australia), Zone Id = Australia/South, Offset = (GMT + 10:30)

358 Zone Name = Australian Eastern Standard Time (New South Wales), Zone Id = Australia/Sydney, Offset = (GMT + 11:00)

359 Zone Name = Australian Eastern Standard Time (Tasmania), Zone Id = Australia/Tasmania, Offset = (GMT + 11:00)

360 Zone Name = Australian Eastern Standard Time (Victoria), Zone Id = Australia/Victoria, Offset = (GMT + 11:00)

361 Zone Name = Australian Western Standard Time, Zone Id = Australia/West, Offset = (GMT + 08:00)

362 Zone Name = Australian Central Standard Time (South Australia/New South Wales), Zone Id = Australia/Yancowinna, Offset = (GMT + 10:30)

363 Zone Name = Acre Time, Zone Id = Brazil/Acre, Offset = (GMT - 05:00)

364 Zone Name = Fernando de Noronha Time, Zone Id = Brazil/DeNoronha, Offset = (GMT - 02:00)

365 Zone Name = Brasilia Time, Zone Id = Brazil/East, Offset = (GMT - 02:00)

366 Zone Name = Amazon Time, Zone Id = Brazil/West, Offset = (GMT - 04:00)

367 Zone Name = Central European Time, Zone Id = CET, Offset = (GMT + 01:00)

368 Zone Name = Central Standard Time, Zone Id = CST6CDT, Offset = (GMT - 06:00)

369 Zone Name = Atlantic Standard Time, Zone Id = Canada/Atlantic, Offset = (GMT - 04:00)

370 Zone Name = Central Standard Time, Zone Id = Canada/Central, Offset = (GMT - 06:00)

371 Zone Name = Central Standard Time, Zone Id = Canada/East-Saskatchewan, Offset = (GMT - 06:00)

372 Zone Name = Eastern Standard Time, Zone Id = Canada/Eastern, Offset = (GMT - 05:00)

373 Zone Name = Mountain Standard Time, Zone Id = Canada/Mountain, Offset = (GMT - 07:00)

374 Zone Name = Newfoundland Standard Time, Zone Id = Canada/Newfoundland, Offset = (GMT - 03:30)

375 Zone Name = Pacific Standard Time, Zone Id = Canada/Pacific, Offset = (GMT - 08:00)

376 Zone Name = Central Standard Time, Zone Id = Canada/Saskatchewan, Offset = (GMT - 06:00)

377 Zone Name = Pacific Standard Time, Zone Id = Canada/Yukon, Offset = (GMT - 08:00)

378 Zone Name = Chile Time, Zone Id = Chile/Continental, Offset = (GMT - 03:00)
379 Zone Name = Easter Is. Time, Zone Id = Chile/EasterIsland, Offset = (GMT - 05:00)
380 Zone Name = Cuba Standard Time, Zone Id = Cuba, Offset = (GMT - 05:00)
381 Zone Name = Eastern European Time, Zone Id = EET, Offset = (GMT + 02:00)
382 Zone Name = Eastern Standard Time, Zone Id = EST5EDT, Offset = (GMT - 05:00)
383 Zone Name = Eastern European Time, Zone Id = Egypt, Offset = (GMT + 02:00)
384 Zone Name = Greenwich Mean Time, Zone Id = Eire, Offset = (GMT + 00:00)
385 Zone Name = Greenwich Mean Time, Zone Id = Etc/GMT, Offset = (GMT + 00:00)
386 Zone Name = Greenwich Mean Time, Zone Id = Etc/GMT+0, Offset = (GMT + 00:00)
387 Zone Name = GMT-01:00, Zone Id = Etc/GMT+1, Offset = (GMT - 01:00)
388 Zone Name = GMT-10:00, Zone Id = Etc/GMT+10, Offset = (GMT - 10:00)
389 Zone Name = GMT-11:00, Zone Id = Etc/GMT+11, Offset = (GMT - 11:00)
390 Zone Name = GMT-12:00, Zone Id = Etc/GMT+12, Offset = (GMT - 12:00)
391 Zone Name = GMT-02:00, Zone Id = Etc/GMT+2, Offset = (GMT - 02:00)
392 Zone Name = GMT-03:00, Zone Id = Etc/GMT+3, Offset = (GMT - 03:00)
393 Zone Name = GMT-04:00, Zone Id = Etc/GMT+4, Offset = (GMT - 04:00)
394 Zone Name = GMT-05:00, Zone Id = Etc/GMT+5, Offset = (GMT - 05:00)
395 Zone Name = GMT-06:00, Zone Id = Etc/GMT+6, Offset = (GMT - 06:00)
396 Zone Name = GMT-07:00, Zone Id = Etc/GMT+7, Offset = (GMT - 07:00)
397 Zone Name = GMT-08:00, Zone Id = Etc/GMT+8, Offset = (GMT - 08:00)
398 Zone Name = GMT-09:00, Zone Id = Etc/GMT+9, Offset = (GMT - 09:00)
399 Zone Name = Greenwich Mean Time, Zone Id = Etc/GMT-0, Offset = (GMT + 00:00)
400 Zone Name = GMT+01:00, Zone Id = Etc/GMT-1, Offset = (GMT + 01:00)
401 Zone Name = GMT+10:00, Zone Id = Etc/GMT-10, Offset = (GMT + 10:00)
402 Zone Name = GMT+11:00, Zone Id = Etc/GMT-11, Offset = (GMT + 11:00)
403 Zone Name = GMT+12:00, Zone Id = Etc/GMT-12, Offset = (GMT + 12:00)
404 Zone Name = GMT+13:00, Zone Id = Etc/GMT-13, Offset = (GMT + 13:00)
405 Zone Name = GMT+14:00, Zone Id = Etc/GMT-14, Offset = (GMT + 14:00)
406 Zone Name = GMT+02:00, Zone Id = Etc/GMT-2, Offset = (GMT + 02:00)
407 Zone Name = GMT+03:00, Zone Id = Etc/GMT-3, Offset = (GMT + 03:00)
408 Zone Name = GMT+04:00, Zone Id = Etc/GMT-4, Offset = (GMT + 04:00)
409 Zone Name = GMT+05:00, Zone Id = Etc/GMT-5, Offset = (GMT + 05:00)
410 Zone Name = GMT+06:00, Zone Id = Etc/GMT-6, Offset = (GMT + 06:00)
411 Zone Name = GMT+07:00, Zone Id = Etc/GMT-7, Offset = (GMT + 07:00)
412 Zone Name = GMT+08:00, Zone Id = Etc/GMT-8, Offset = (GMT + 08:00)
413 Zone Name = GMT+09:00, Zone Id = Etc/GMT-9, Offset = (GMT + 09:00)
414 Zone Name = Greenwich Mean Time, Zone Id = Etc/GMT0, Offset = (GMT + 00:00)
415 Zone Name = Greenwich Mean Time, Zone Id = Etc/Greenwich, Offset = (GMT + 00:00)
416 Zone Name = Coordinated Universal Time, Zone Id = Etc/UCT, Offset = (GMT + 00:00)

417 Zone Name = Coordinated Universal Time, Zone Id = Etc/UTC, Offset = (GMT + 00:00)
418 Zone Name = Coordinated Universal Time, Zone Id = Etc/Universal, Offset = (GMT + 00:00)
419 Zone Name = Coordinated Universal Time, Zone Id = Etc/Zulu, Offset = (GMT + 00:00)
420 Zone Name = Central European Time, Zone Id = Europe/Amsterdam, Offset = (GMT + 01:00)
421 Zone Name = Central European Time, Zone Id = Europe/Andorra, Offset = (GMT + 01:00)
422 Zone Name = GMT+04:00, Zone Id = Europe/Astrakhan, Offset = (GMT + 04:00)
423 Zone Name = Eastern European Time, Zone Id = Europe/Athens, Offset = (GMT + 02:00)
424 Zone Name = Greenwich Mean Time, Zone Id = Europe/Belfast, Offset = (GMT + 00:00)
425 Zone Name = Central European Time, Zone Id = Europe/Belgrade, Offset = (GMT + 01:00)
426 Zone Name = Central European Time, Zone Id = Europe/Berlin, Offset = (GMT + 01:00)
427 Zone Name = Central European Time, Zone Id = Europe/Bratislava, Offset = (GMT + 01:00)
428 Zone Name = Central European Time, Zone Id = Europe/Brussels, Offset = (GMT + 01:00)
429 Zone Name = Eastern European Time, Zone Id = Europe/Bucharest, Offset = (GMT + 02:00)
430 Zone Name = Central European Time, Zone Id = Europe/Budapest, Offset = (GMT + 01:00)
431 Zone Name = Central European Time, Zone Id = Europe/Busingen, Offset = (GMT + 01:00)
432 Zone Name = Eastern European Time, Zone Id = Europe/Chisinau, Offset = (GMT + 02:00)
433 Zone Name = Central European Time, Zone Id = Europe/Copenhagen, Offset = (GMT + 01:00)
434 Zone Name = Greenwich Mean Time, Zone Id = Europe/Dublin, Offset = (GMT + 00:00)
435 Zone Name = Central European Time, Zone Id = Europe/Gibraltar, Offset = (GMT + 01:00)
436 Zone Name = Greenwich Mean Time, Zone Id = Europe/Guernsey, Offset = (GMT + 00:00)
437 Zone Name = Eastern European Time, Zone Id = Europe/Helsinki, Offset = (GMT + 02:00)
438 Zone Name = Greenwich Mean Time, Zone Id = Europe/Isle_of_Man, Offset = (GMT + 00:00)
439 Zone Name = Eastern European Time, Zone Id = Europe/Istanbul, Offset = (GMT + 02:00)
440 Zone Name = Greenwich Mean Time, Zone Id = Europe/Jersey, Offset = (GMT + 00:00)
441 Zone Name = Eastern European Time, Zone Id = Europe/Kaliningrad, Offset = (GMT + 02:00)
442 Zone Name = Eastern European Time, Zone Id = Europe/Kiev, Offset = (GMT + 02:00)
443 Zone Name = GMT+03:00, Zone Id = Europe/Kirov, Offset = (GMT + 03:00)
444 Zone Name = Western European Time, Zone Id = Europe/Lisbon, Offset = (GMT + 00:00)
445 Zone Name = Central European Time, Zone Id = Europe/Ljubljana, Offset = (GMT + 01:00)
446 Zone Name = Greenwich Mean Time, Zone Id = Europe/London, Offset = (GMT + 00:00)
447 Zone Name = Central European Time, Zone Id = Europe/Luxembourg, Offset = (GMT + 01:00)
448 Zone Name = Central European Time, Zone Id = Europe/Madrid, Offset = (GMT + 01:00)
449 Zone Name = Central European Time, Zone Id = Europe/Malta, Offset = (GMT + 01:00)
450 Zone Name = Eastern European Time, Zone Id = Europe/Mariehamn, Offset = (GMT + 02:00)

451 Zone Name = Moscow Standard Time, Zone Id = Europe/Minsk, Offset = (GMT + 03:00)
452 Zone Name = Central European Time, Zone Id = Europe/Monaco, Offset = (GMT + 01:00)
453 Zone Name = Moscow Standard Time, Zone Id = Europe/Moscow, Offset = (GMT + 03:00)
454 Zone Name = Eastern European Time, Zone Id = Europe/Nicosia, Offset = (GMT + 02:00)
455 Zone Name = Central European Time, Zone Id = Europe/Oslo, Offset = (GMT + 01:00)
456 Zone Name = Central European Time, Zone Id = Europe/Paris, Offset = (GMT + 01:00)
457 Zone Name = Central European Time, Zone Id = Europe/Podgorica, Offset = (GMT + 01:00)
458 Zone Name = Central European Time, Zone Id = Europe/Prague, Offset = (GMT + 01:00)
459 Zone Name = Eastern European Time, Zone Id = Europe/Riga, Offset = (GMT + 02:00)
460 Zone Name = Central European Time, Zone Id = Europe/Rome, Offset = (GMT + 01:00)
461 Zone Name = Samara Time, Zone Id = Europe/Samara, Offset = (GMT + 04:00)
462 Zone Name = Central European Time, Zone Id = Europe/San_Marino, Offset = (GMT + 01:00)
463 Zone Name = Central European Time, Zone Id = Europe/Sarajevo, Offset = (GMT + 01:00)
464 Zone Name = Moscow Standard Time, Zone Id = Europe/Simferopol, Offset = (GMT + 03:00)
465 Zone Name = Central European Time, Zone Id = Europe/Skopje, Offset = (GMT + 01:00)
466 Zone Name = Eastern European Time, Zone Id = Europe/Sofia, Offset = (GMT + 02:00)
467 Zone Name = Central European Time, Zone Id = Europe/Stockholm, Offset = (GMT + 01:00)
468 Zone Name = Eastern European Time, Zone Id = Europe/Tallinn, Offset = (GMT + 02:00)
469 Zone Name = Central European Time, Zone Id = Europe/Tirane, Offset = (GMT + 01:00)
470 Zone Name = Eastern European Time, Zone Id = Europe/Tiraspol, Offset = (GMT + 02:00)
471 Zone Name = GMT+04:00, Zone Id = Europe/Ulyanovsk, Offset = (GMT + 04:00)
472 Zone Name = Eastern European Time, Zone Id = Europe/Uzhgorod, Offset = (GMT + 02:00)
473 Zone Name = Central European Time, Zone Id = Europe/Vaduz, Offset = (GMT + 01:00)
474 Zone Name = Central European Time, Zone Id = Europe/Vatican, Offset = (GMT + 01:00)
475 Zone Name = Central European Time, Zone Id = Europe/Vienna, Offset = (GMT + 01:00)
476 Zone Name = Eastern European Time, Zone Id = Europe/Vilnius, Offset = (GMT + 02:00)
477 Zone Name = Moscow Standard Time, Zone Id = Europe/Volgograd, Offset = (GMT + 03:00)
478 Zone Name = Central European Time, Zone Id = Europe/Warsaw, Offset = (GMT + 01:00)
479 Zone Name = Central European Time, Zone Id = Europe/Zagreb, Offset = (GMT + 01:00)
480 Zone Name = Eastern European Time, Zone Id = Europe/Zaporozhye, Offset = (GMT + 02:00)
481 Zone Name = Central European Time, Zone Id = Europe/Zurich, Offset = (GMT + 01:00)
482 Zone Name = Greenwich Mean Time, Zone Id = GB, Offset = (GMT + 00:00)
483 Zone Name = Greenwich Mean Time, Zone Id = GB-Eire, Offset = (GMT + 00:00)
484 Zone Name = Greenwich Mean Time, Zone Id = GMT, Offset = (GMT + 00:00)
485 Zone Name = Greenwich Mean Time, Zone Id = GMT0, Offset = (GMT + 00:00)

486 Zone Name = Greenwich Mean Time, Zone Id = Greenwich, Offset = (GMT + 00:00)
487 Zone Name = Hong Kong Time, Zone Id = Hongkong, Offset = (GMT + 08:00)
488 Zone Name = Greenwich Mean Time, Zone Id = Iceland, Offset = (GMT + 00:00)
489 Zone Name = Eastern African Time, Zone Id = Indian/Antananarivo, Offset = (GMT + 03:00)
490 Zone Name = Indian Ocean Territory Time, Zone Id = Indian/Chagos, Offset = (GMT + 06:00)
491 Zone Name = Christmas Island Time, Zone Id = Indian/Christmas, Offset = (GMT + 07:00)
492 Zone Name = Cocos Islands Time, Zone Id = Indian/Cocos, Offset = (GMT + 06:30)
493 Zone Name = Eastern African Time, Zone Id = Indian/Comoro, Offset = (GMT + 03:00)
494 Zone Name = French Southern & Antarctic Lands Time, Zone Id = Indian/Kerguelen, Offset = (GMT + 05:00)
495 Zone Name = Seychelles Time, Zone Id = Indian/Mahe, Offset = (GMT + 04:00)
496 Zone Name = Maldives Time, Zone Id = Indian/Maldives, Offset = (GMT + 05:00)
497 Zone Name = Mauritius Time, Zone Id = Indian/Mauritius, Offset = (GMT + 04:00)
498 Zone Name = Eastern African Time, Zone Id = Indian/Mayotte, Offset = (GMT + 03:00)
499 Zone Name = Reunion Time, Zone Id = Indian/Reunion, Offset = (GMT + 04:00)
500 Zone Name = Iran Standard Time, Zone Id = Iran, Offset = (GMT + 03:30)
501 Zone Name = Israel Standard Time, Zone Id = Israel, Offset = (GMT + 02:00)
502 Zone Name = Eastern Standard Time, Zone Id = Jamaica, Offset = (GMT - 05:00)
503 Zone Name = Japan Standard Time, Zone Id = Japan, Offset = (GMT + 09:00)
504 Zone Name = Marshall Islands Time, Zone Id = Kwajalein, Offset = (GMT + 12:00)
505 Zone Name = Eastern European Time, Zone Id = Libya, Offset = (GMT + 02:00)
506 Zone Name = Middle Europe Time, Zone Id = MET, Offset = (GMT + 01:00)
507 Zone Name = Mountain Standard Time, Zone Id = MST7MDT, Offset = (GMT - 07:00)
508 Zone Name = Pacific Standard Time, Zone Id = Mexico/BajaNorte, Offset = (GMT - 08:00)
509 Zone Name = Mountain Standard Time, Zone Id = Mexico/BajaSur, Offset = (GMT - 07:00)
510 Zone Name = Central Standard Time, Zone Id = Mexico/General, Offset = (GMT - 06:00)
511 Zone Name = New Zealand Standard Time, Zone Id = NZ, Offset = (GMT + 13:00)
512 Zone Name = Chatham Standard Time, Zone Id = NZ-CHAT, Offset = (GMT + 13:45)
513 Zone Name = Mountain Standard Time, Zone Id = Navajo, Offset = (GMT - 07:00)
514 Zone Name = China Standard Time, Zone Id = PRC, Offset = (GMT + 08:00)
515 Zone Name = Pacific Standard Time, Zone Id = PST8PDT, Offset = (GMT - 08:00)
516 Zone Name = West Samoa Standard Time, Zone Id = Pacific/Apia, Offset = (GMT + 14:00)
517 Zone Name = New Zealand Standard Time, Zone Id = Pacific/Auckland, Offset = (GMT + 13:00)
518 Zone Name = Bougainville Standard Time, Zone Id = Pacific/Bougainville, Offset = (GMT + 11:00)
519 Zone Name = Chatham Standard Time, Zone Id = Pacific/Chatham, Offset = (GMT + 13:45)
520 Zone Name = Chuuk Time, Zone Id = Pacific/Chuuk, Offset = (GMT + 10:00)
521 Zone Name = Easter Is. Time, Zone Id = Pacific/Easter, Offset = (GMT - 05:00)

522 Zone Name = Vanuatu Time, Zone Id = Pacific/Efate, Offset = (GMT + 11:00)
523 Zone Name = Phoenix Is. Time, Zone Id = Pacific/Enderbury, Offset = (GMT + 13:00)
524 Zone Name = Tokelau Time, Zone Id = Pacific/Fakaofo, Offset = (GMT + 13:00)
525 Zone Name = Fiji Time, Zone Id = Pacific/Fiji, Offset = (GMT + 12:00)
526 Zone Name = Tuvalu Time, Zone Id = Pacific/Funafuti, Offset = (GMT + 12:00)
527 Zone Name = Galapagos Time, Zone Id = Pacific/Galapagos, Offset = (GMT - 06:00)
528 Zone Name = Gambier Time, Zone Id = Pacific/Gambier, Offset = (GMT - 09:00)
529 Zone Name = Solomon Is. Time, Zone Id = Pacific/Guadalcanal, Offset = (GMT + 11:00)
530 Zone Name = Chamorro Standard Time, Zone Id = Pacific/Guam, Offset = (GMT + 10:00)
531 Zone Name = Hawaii Standard Time, Zone Id = Pacific/Honolulu, Offset = (GMT - 10:00)
532 Zone Name = Hawaii Standard Time, Zone Id = Pacific/Johnston, Offset = (GMT - 10:00)
533 Zone Name = Line Is. Time, Zone Id = Pacific/Kiritimati, Offset = (GMT + 14:00)
534 Zone Name = Kosrae Time, Zone Id = Pacific/Kosrae, Offset = (GMT + 11:00)
535 Zone Name = Marshall Islands Time, Zone Id = Pacific/Kwajalein, Offset = (GMT + 12:00)
536 Zone Name = Marshall Islands Time, Zone Id = Pacific/Majuro, Offset = (GMT + 12:00)
537 Zone Name = Marquesas Time, Zone Id = Pacific/Marquesas, Offset = (GMT - 09:30)
538 Zone Name = Samoa Standard Time, Zone Id = Pacific/Midway, Offset = (GMT - 11:00)
539 Zone Name = Nauru Time, Zone Id = Pacific/Nauru, Offset = (GMT + 12:00)
540 Zone Name = Niue Time, Zone Id = Pacific/Niue, Offset = (GMT - 11:00)
541 Zone Name = Norfolk Time, Zone Id = Pacific/Norfolk, Offset = (GMT + 11:00)
542 Zone Name = New Caledonia Time, Zone Id = Pacific/Noumea, Offset = (GMT + 11:00)
543 Zone Name = Samoa Standard Time, Zone Id = Pacific/Pago_Pago, Offset = (GMT - 11:00)
544 Zone Name = Palau Time, Zone Id = Pacific/Palau, Offset = (GMT + 09:00)
545 Zone Name = Pitcairn Standard Time, Zone Id = Pacific/Pitcairn, Offset = (GMT - 08:00)
546 Zone Name = Pohnpei Time, Zone Id = Pacific/Pohnpei, Offset = (GMT + 11:00)
547 Zone Name = Pohnpei Time, Zone Id = Pacific/Ponape, Offset = (GMT + 11:00)
548 Zone Name = Papua New Guinea Time, Zone Id = Pacific/Port_Moresby, Offset = (GMT + 10:00)
549 Zone Name = Cook Is. Time, Zone Id = Pacific/Rarotonga, Offset = (GMT - 10:00)
550 Zone Name = Chamorro Standard Time, Zone Id = Pacific/Saipan, Offset = (GMT + 10:00)
551 Zone Name = Samoa Standard Time, Zone Id = Pacific/Samoa, Offset = (GMT - 11:00)
552 Zone Name = Tahiti Time, Zone Id = Pacific/Tahiti, Offset = (GMT - 10:00)
553 Zone Name = Gilbert Is. Time, Zone Id = Pacific/Tarawa, Offset = (GMT + 12:00)
554 Zone Name = Tonga Time, Zone Id = Pacific/Tongatapu, Offset = (GMT + 13:00)
555 Zone Name = Chuuk Time, Zone Id = Pacific/Truk, Offset = (GMT + 10:00)
556 Zone Name = Wake Time, Zone Id = Pacific/Wake, Offset = (GMT + 12:00)
557 Zone Name = Wallis & Futuna Time, Zone Id = Pacific/Wallis, Offset = (GMT + 12:00)
558 Zone Name = Chuuk Time, Zone Id = Pacific/Yap, Offset = (GMT + 10:00)
559 Zone Name = Central European Time, Zone Id = Poland, Offset = (GMT + 01:00)
560 Zone Name = Western European Time, Zone Id = Portugal, Offset = (GMT + 00:00)

561 Zone Name = Korea Standard Time, Zone Id = ROK, Offset = (GMT + 09:00)
562 Zone Name = Singapore Time, Zone Id = Singapore, Offset = (GMT + 08:00)
563 Zone Name = Atlantic Standard Time, Zone Id = SystemV/AST4, Offset = (GMT - 04:00)
564 Zone Name = Atlantic Standard Time, Zone Id = SystemV/AST4ADT, Offset = (GMT - 04:00)
565 Zone Name = Central Standard Time, Zone Id = SystemV/CST6, Offset = (GMT - 06:00)
566 Zone Name = Central Standard Time, Zone Id = SystemV/CST6CDT, Offset = (GMT - 06:00)
567 Zone Name = Eastern Standard Time, Zone Id = SystemV/EST5, Offset = (GMT - 05:00)
568 Zone Name = Eastern Standard Time, Zone Id = SystemV/EST5EDT, Offset = (GMT - 05:00)
569 Zone Name = Hawaii Standard Time, Zone Id = SystemV/HST10, Offset = (GMT - 10:00)
570 Zone Name = Mountain Standard Time, Zone Id = SystemV/MST7, Offset = (GMT - 07:00)
571 Zone Name = Mountain Standard Time, Zone Id = SystemV/MST7MDT, Offset = (GMT - 07:00)
572 Zone Name = Pacific Standard Time, Zone Id = SystemV/PST8, Offset = (GMT - 08:00)
573 Zone Name = Pacific Standard Time, Zone Id = SystemV/PST8PDT, Offset = (GMT - 08:00)
574 Zone Name = Alaska Standard Time, Zone Id = SystemV/YST9, Offset = (GMT - 09:00)
575 Zone Name = Alaska Standard Time, Zone Id = SystemV/YST9YDT, Offset = (GMT - 09:00)
576 Zone Name = Eastern European Time, Zone Id = Turkey, Offset = (GMT + 02:00)
577 Zone Name = Coordinated Universal Time, Zone Id = UCT, Offset = (GMT + 00:00)
578 Zone Name = Alaska Standard Time, Zone Id = US/Alaska, Offset = (GMT - 09:00)
579 Zone Name = Hawaii Standard Time, Zone Id = US/Aleutian, Offset = (GMT - 10:00)
580 Zone Name = Mountain Standard Time, Zone Id = US/Arizona, Offset = (GMT - 07:00)
581 Zone Name = Central Standard Time, Zone Id = US/Central, Offset = (GMT - 06:00)
582 Zone Name = Eastern Standard Time, Zone Id = US/East-Indiana, Offset = (GMT - 05:00)
583 Zone Name = Eastern Standard Time, Zone Id = US/Eastern, Offset = (GMT - 05:00)
584 Zone Name = Hawaii Standard Time, Zone Id = US/Hawaii, Offset = (GMT - 10:00)
585 Zone Name = Central Standard Time, Zone Id = US/Indiana-Starke, Offset = (GMT - 06:00)
586 Zone Name = Eastern Standard Time, Zone Id = US/Michigan, Offset = (GMT - 05:00)
587 Zone Name = Mountain Standard Time, Zone Id = US/Mountain, Offset = (GMT - 07:00)
588 Zone Name = Pacific Standard Time, Zone Id = US/Pacific, Offset = (GMT - 08:00)
589 Zone Name = Pacific Standard Time, Zone Id = US/Pacific-New, Offset = (GMT - 08:00)
590 Zone Name = Samoa Standard Time, Zone Id = US/Samoa, Offset = (GMT - 11:00)
591 Zone Name = Coordinated Universal Time, Zone Id = UTC, Offset = (GMT + 00:00)
592 Zone Name = Coordinated Universal Time, Zone Id = Universal, Offset = (GMT + 00:00)
593 Zone Name = Moscow Standard Time, Zone Id = W-SU, Offset = (GMT + 03:00)
594 Zone Name = Western European Time, Zone Id = WET, Offset = (GMT + 00:00)
595 Zone Name = Coordinated Universal Time, Zone Id = Zulu, Offset = (GMT + 00:00)
596 Zone Name = Eastern Standard Time, Zone Id = EST, Offset = (GMT - 05:00)

597 Zone Name = Hawaii Standard Time, Zone Id = HST, Offset = (GMT - 10:00)
598 Zone Name = Mountain Standard Time, Zone Id = MST, Offset = (GMT - 07:00)
599 Zone Name = Australian Central Standard Time (Northern Territory), Zone Id = ACT, Offset = (GMT + 09:30)
600 Zone Name = Australian Eastern Standard Time (New South Wales), Zone Id = AET, Offset = (GMT + 11:00)
601 Zone Name = Argentine Time, Zone Id = AGT, Offset = (GMT - 03:00)
602 Zone Name = Eastern European Time, Zone Id = ART, Offset = (GMT + 02:00)
603 Zone Name = Alaska Standard Time, Zone Id = AST, Offset = (GMT - 09:00)
604 Zone Name = Brasilia Time, Zone Id = BET, Offset = (GMT - 02:00)
605 Zone Name = Bangladesh Time, Zone Id = BST, Offset = (GMT + 06:00)
606 Zone Name = Central African Time, Zone Id = CAT, Offset = (GMT + 02:00)
607 Zone Name = Newfoundland Standard Time, Zone Id = CNT, Offset = (GMT - 03:30)
608 Zone Name = Central Standard Time, Zone Id = CST, Offset = (GMT - 06:00)
609 Zone Name = China Standard Time, Zone Id = CTT, Offset = (GMT + 08:00)
610 Zone Name = Eastern African Time, Zone Id = EAT, Offset = (GMT + 03:00)
611 Zone Name = Central European Time, Zone Id = ECT, Offset = (GMT + 01:00)
612 Zone Name = Eastern Standard Time, Zone Id = IET, Offset = (GMT - 05:00)
613 Zone Name = India Standard Time, Zone Id = IST, Offset = (GMT + 05:30)
614 Zone Name = Japan Standard Time, Zone Id = JST, Offset = (GMT + 09:00)
615 Zone Name = West Samoa Standard Time, Zone Id = MIT, Offset = (GMT + 14:00)
616 Zone Name = Armenia Time, Zone Id = NET, Offset = (GMT + 04:00)
617 Zone Name = New Zealand Standard Time, Zone Id = NST, Offset = (GMT + 13:00)
618 Zone Name = Pakistan Time, Zone Id = PLT, Offset = (GMT + 05:00)
619 Zone Name = Mountain Standard Time, Zone Id = PNT, Offset = (GMT - 07:00)
620 Zone Name = Atlantic Standard Time, Zone Id = PRT, Offset = (GMT - 04:00)
621 Zone Name = Pacific Standard Time, Zone Id = PST, Offset = (GMT - 08:00)
622 Zone Name = Solomon Is. Time, Zone Id = SST, Offset = (GMT + 11:00)
623 Zone Name = Indochina Time, Zone Id = VST, Offset = (GMT + 07:00)

Date Format

The date format is a user preference. You must enter a value for the user. The date format is a user preference setting that the user can change later if necessary. The date format can also be set in a user preference template.

The following lists the supported date formats:

Note: The time format for all dates is: HH:MM AM.

Date Format	Code
MM/DD/YYYY	0
DD/MM/YYYY	1
MM/DD/YY	2
DD/MM/YY	3
MM-DD-YYYY	4
DD-MM-YYYY	5
MM-DD-YY	6
DD-MM-YY	7
DD.MM.YYYY	8
YYYY-MM-DD	9
MMM/DD/YYYY	10
DD/MMM/YYYY	11
YYYY/MMM/DD	12
M/D/YYYY	13
M/D/YY	14
D/M/YYYY	15
D/M/YY	16
YY/M/D	17
YYYY/M/D	18
YY/MM/DD	19
YYYY/MM/DD	20

User Type

Use the values included in the following table for any record in which Standard or Portal are the User Type choices.

The User Type you choose, for the import value, will be used as soon as the record is imported.

For example, if you enter a “0” for the User Type, the user will be a Standard user upon successful import of the record; if you enter “1”, the user will be a Portal user.

User Type	Value
Standard	0
Portal	1

Company Address

Use the codes included in the following table for the address fields, when entering the user records.

Address Type	Code
Headquarters	1
Main	2
Branch Office	3
Billing	4
Shipping	5
Billing and Shipping	6
Satellite Office	7

Status

Use the values included in the following table for any record in which Active, Inactive, or On Hold are the status choices. The status you choose for the import value will be effective as soon as the record is imported. For example, if you enter a “1” for the status, the user will be an active user upon successful import of the record; if you enter “2”, the user will be On Hold until an administrator activates the user record.

Status	Value
Inactive	0

Status	Value
Active	1
On Hold	2

Check Box

For check boxes on BP forms, you can import the following values to select ("check") a check box or leave it unchecked.

Check Box	Value
Check box not selected	0
Check box selected	1

Pickers

This section describes the pickers that come with the system, and each subsection includes the following information about each picker:

- ▶ **Data Element Name**
- ▶ **Label that will Appear on the Form**
- ▶ **Available for Forms on Mobile Device**
- ▶ **What it Does**

For more details about these pickers, review the corresponding data definition name (in the Data Definitions section of this guide), or the corresponding data element name (in the Data Elements of this guide).

Note: When you are designing a form, you will see these pickers on the list of custom elements; however, the list will vary depending on the type of business process, or other Unifier component, that you are designing.

In This Section

Account Code Picker.....	353
Activity Picker.....	353
Allocation Template Picker.....	353
Asset Picker.....	354
Auto-update Status Setup Picker.....	354
Bid Picker.....	354
BP Line Item Picker.....	354
BP Picker.....	355
BP Line Item Data Picker.....	356
CBS Picker.....	356
CBS Code Picker.....	356
CM0 Picker (Generic Cost Manager).....	357
CMx (Code based) Picker.....	357
CMx (Code and Records-based) Picker.....	357
Commit Line Item Picker.....	358
Company Picker.....	358
Configurable Manager [Name] Picker.....	359
Cost Attribute Picker.....	359
Cost Code Picker.....	359
Currency Picker.....	359
Data Picker.....	360
Date Only Picker.....	360
Date Picker.....	360
Date Only Picker.....	366
Fund Picker.....	367
Generic Cost Code Picker.....	367
Group Name Picker.....	368
Hyperlink Picker.....	368
Image Picker.....	368
Level Picker.....	368
Location Picker.....	369
P6 Activity Picker.....	369
Planning Item Picker/Planning Line Item Picker.....	369
Planning Period Picker.....	369
Project Picker.....	370
Project Template Picker.....	370
Resource Picker.....	370
Role Picker.....	371
Role Data Picker.....	371
Seasonal Dates Picker.....	371
Shell Picker.....	372
Shell Template Picker.....	372
Shell Data Picker.....	372
Single User Picker.....	373
SOV Picker.....	373
Space Picker.....	373

SYS Date Picker.....	373
User Picker.....	374
User Data Picker	375
WBS Code Picker.....	375
WBS Picker	375
Week Picker	375
Work Package Picker	375

Account Code Picker

Data Element Name: uuu_company_acc_codepicker

Label that will Appear on the Form: Account Code Picker

Available for Forms on Mobile Device: Yes

What it Does: Use this picker on company-level cost BPs for choosing company account codes.

Unifier populates this picker with the account codes from the company-level account sheet (which were created with the Account Code attribute form).

Note: Do not use this picker on configurable manager attribute forms.

Activity Picker

Data Element Name: uuu_activity_picker

Label that will Appear on the Form: Activity Picker

Available for Forms on Mobile Device: No

What it Does: Use this picker on Timesheet BPs (Line Item Details form) to select activities from the master schedule sheet. Unifier populates this picker with the activity records that were created with the Activity attribute form.

Note: This picker on any other form will produce an error.

Allocation Template Picker

Data Element Name: uuu_lse_allocation_name

Label that will Appear on the Form: Allocation Template Picker

Available for Forms on Mobile Device: No

Place holder for Type Ahead: Type a Allocation Name...

What it Does: Enables you to select allocations which are defined in Allocation Template.

Asset Picker

Data Element Name: uuu_asset_picker

Label that will Appear on the Form: Asset Picker

Available for Forms on Mobile Device: Yes

What it Does: Use this picker to select an asset for a project. The assets listed for the user's choice are based on user permissions, and will be filtered to include only those assets that are at specific statuses. Asset pickers can be placed on company-level business processes only.

Unifier populates this picker with the asset records that were created with the Asset attribute form.

Note: Do not use this picker on configurable manager attribute forms.

Auto-update Status Setup Picker

Data Element Name:

Label that will Appear on the Form:

Available for Forms on Mobile Device:

Place holder for Type Ahead:

What it Does:

Bid Picker

Data Element Name: uuu_rfb_winning_bid

Label that will Appear on the Form: Winning Bid

The label is configurable and based on the label corresponding to the place-holder for Type Ahead.

Available for Forms on Mobile Device: No

What it Does: Selects a winning bid from all bids received.

BP Line Item Picker

Data Element Name: ref_bpo_lineitem and uuu_rec_ast_meter_li

Label that will Appear on the Form: Reference BPO Line Item, Asset Meter LI Ref

The label is configurable and based on the label corresponding to the place-holder for Type Ahead.

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: It creates Data Elements (DEs) for line item pickers (DEs that require Yes or No response)

Note: You cannot use a BP Line Item Picker in an Activity Attribute Form.

BP Picker

The **BP Picker** links one business process to another (for example, an invoice BP to a purchase order BP). BP pickers are populated by a link you must create to a specific reference process. Unifier comes with several BP pickers. In addition to the pickers listed here, you can create your own BP pickers using the BP Picker data definition.

Note: Do not use these pickers on configurable manager attribute forms.

The following lists each DE for **BP Picker**:

- ▶ **ref_bpo**
- ▶ **ref_bpo_lineitem**
- ▶ **Reference BPO Line Item**

The following explains each DE for **BP Picker**:

Data Element Name: ref_bpo

Label that will Appear on the Form: Reference BPO

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: Reference BPO (Blanket Purchase Order)

Use this picker to choose an approved blanket purchase order (BPO) to reference. The transaction amount of the BP will be rolled up to the Blanket PO Manager.

Data Element Name: ref_bpo_lineitem

Label that will Appear on the Form: Reference BPO Line Item

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: Reference BPO Line Item

Use this picker to reference a "Commit at Company Level" or "Blanket PO" business process for line items.

This picker works in conjunction with the business process picker on the upper form.

Data Element Name: refid

Label that will Appear on the Form: Reference Commit

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: Reference Commit

Use this picker to reference a "Base Commits" Business Process (BP) for a change order, invoice, or payment BP.

BP Line Item Data Picker

Data Element Name: *BP Line Item Data Picker*

Label that will Appear on the Form: BP Line Item Data Picker

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: Use this picker to view the detail forms of the source BP as different line items.

Note: Only tabs that are set as visible in picker configuration are displayed.

CBS Picker

Data Element Name: bitemID

Label that will Appear on the Form: CBS Code

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: Use this picker on Cost-type BPs (except line item BPs) to choose CBS codes. The picker will show all active CBS codes in the project.

This picker is populated by the CBS code records that were created with the Cost attribute form.

The bitemID is *only* available for selection in the **Detail Form, Standard** tab.

Note: Do not use this picker on configurable manager attribute forms.

CBS Code Picker

Data Element Name: uuu_cost_code

Label that will Appear on the Form: CBS Code

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: Use this picker on a Cost BP to choose a CBS code. The picker will show only active CBS codes.

This picker is populated by the CBS code records that were created with the Cost attribute form.

Note: Do not use this picker on configurable manager attribute forms.

CM0 Picker (Generic Cost Manager)

Data Element Name: uuu_cm0_picker

Label that will Appear on the Form: Account Code

The labels are configurable and based on the label corresponding to the place-holder for Type Ahead.

Place holder for Type Ahead: Type an Account Code

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: It will search and fetch the records whose account code contains the entered value.

CMx (Code based) Picker

Data Element Name: uuu_cmX_picker (X represents a number ranging from 1 to 25. For example: uuu_cm4_picker)

Label that will Appear on the Form: Building System

The labels are configurable and based on the label corresponding to the place-holder for Type Ahead.

Place holder for Type Ahead: Type a Building System Code...

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: It will search and fetch the records whose Building System Code contains the entered value.

CMx (Code and Records-based) Picker

Data Element Name: uuu_cmX_picker (X represents a number ranging from 1 to 25. For example: uuu_cm5_picker)

Label that will Appear on the Form: Material Inventory Code

The labels are configurable and based on the label corresponding to the place-holder for Type Ahead.

Place holder for Type Ahead: Type a Material Inventory Code...

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: It will search and fetch the records whose Building System Code contains the entered value.

Commit Line Item Picker

Data Element Name: uuu_sovlinum

Label that will Appear on the Form: Reference

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: Use this picker for creating a new line item on a change commit BP. This picker displays a composite view of base commit and change commits. This picker is required on the detail form of line-item type Change Commit BPs and is populated by a link you must create to a specific reference process.

Note: Do not use this picker on configurable manager attribute forms.

Company Picker

In addition to the picker listed here, you can create your own company pickers using the **Company Picker** data definition.

Data Element Name: otherCompanyID

Label that will Appear on the Form: Company

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: Use this picker to choose from a list of partner or member companies. Unifier populates this picker with the names of the companies in the database. At the company level, the picker will show partner companies. At the project level, the picker will show member companies.

Note: Do not use this picker on configurable manager attribute forms.

Configurable Manager [Name] Picker

Data Element Name: uuu_cm[1...25]_picker

Label that will Appear on the Form: [manager name] Picker

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: Use this picker to select a code for an item.

The code picker is created automatically when the manager is created. The picker auto-populates elements from the manager record onto BP forms.

For code-based managers, Unifier populates this picker with codes from the manager sheet itself. For Code and Records-based managers, the system populates this picker with the codes that were created with the manager's attribute form.

Cost Attribute Picker

Data Element Name: uuu_cost_costattribute

Label that will Appear on the Form: Cost Attribute

Available for Forms on Mobile Device: No

What it Does: Use this picker to enter cost attribute information on a Cost Attribute form. The values that populate this picker come from the Cost Attribute data definition.

Note: Do not use this picker on configurable manager attribute forms.

Cost Code Picker

Data Element Name: bltemID

Label that will Appear on the Form: Cost Code (User defined - editable)

Available for Forms on Mobile Device: Yes

Place holder for Type Ahead: Type CBS Code or Name...

What it Does: Use this picker to pick one CBS Code

Currency Picker

Data Element Name: currencyid

Label that will Appear on the Form: "Transaction Currency" on business processes

"Resource Currency" on Resource attribute forms

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: Use this picker for choosing the currency on a Cost-type BP or on a Resource attribute form. If the user does not choose a currency, or if you do not include a currency picker on the form, the default is the project currency. The system populates this picker with the currencies in the database.

Note: Do not use this picker on configurable manager attribute forms.

Data Picker

The **Data Picker** (*Data Picker* (on page 29)) is the data definition (DD).

Data Element Name: The DE is specified by customer

Label that will Appear on the Form: The display element of the DD.

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: It lets you pick users.

Date Only Picker

Data Element Name: upoExpiryDateDOP

Label that will Appear on the Form: Eg.Expiry Date (user defined)

Available for Forms on Mobile Device: Yes

What it Does: Use this picker to select a date from the calendar.

Date Picker

The **Date Picker** displays an interactive calendar from which the date can be chosen. In addition to the pickers listed here, you can create your own date pickers using the Date Picker data definition.

The system comes with the following DEs for **Date Picker**:

- ▶ **uuu_asset_acquisition_date**
- ▶ **uuu_seet_calc_as_of_date**
- ▶ **due_date**
- ▶ **uuu_rfb_due_date**
- ▶ **uuu_issue_date**

- `uuu_effective_date`
- `uuu_file_issue_date`
- `uuu_dm_create_date`
- `uuu_file_create_date`
- `uuu_from_date`
- `uuu_to_date`
- `uuu_last_update_date`
- `uuu_week_picker`
- `uuu_start`
- `uuu_finish`
- `uuu_early_start`
- `uuu_early_finish`
- `uuu_late_start`
- `uuu_late_finish`
- `uuu_actual_start_date`
- `uuu_actual_finish_date`
- `uuu_estimated_finish_date`
- `uuu_estimated_start_date`
- `uuu_start_baseline`
- `uuu_finish_baseline`
- `uuu_start_baseline[1...10]`
- `uuu_finish_baseline[1...10]`

The following explains each DE in detail:

Data Element Name: `uuu_asset_acquisition_date`

Label that will Appear on the Form: Asset Acquisition Date

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: Asset Acquisition Date

Use this picker on any asset form to specify the date an asset was acquired.

Data Element Name: `uuu_seet_calc_as_of_date`

Label that will Appear on the Form: Calculation as of

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: Calculation as of

Use this picker on any asset form to show the calculated depreciation as of the date the user chooses.

Data Element Name: `due_date`

Label that will Appear on the Form: Due Date

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: Due Date

Use this picker to specify a due date on any type of business process form.

Data Element Name: uuu_rfb_due_date

Label that will Appear on the Form: RFB Due Date

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: RFB Due Date

Use this picker to specify the due date for a bid on any RFB type of business process form.

Data Element Name: uuu_issue_date

Label that will Appear on the Form: Issue Date

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: Issue Date

Use this picker to specify an issue date for a document that is attached to a line item.

Data Element Name: uuu_effective_date

Label that will Appear on the Form: Effective Date

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: Effective Date

Use this picker to specify an effective date on a cost-type business process form.

Data Element Name: uuu_file_issue_date

Label that will Appear on the Form: Issue Date

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: Issue Date

Use these pickers on any Document attribute form to specify the date and time a document was issued, created, or uploaded to the Document Manager.

Data Element Name: uuu_dm_create_date

Label that will Appear on the Form: Creation Date

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: Creation Date

Use these pickers on any Document attribute form to specify the date and time a document was issued, created, or uploaded to the Document Manager.

Data Element Name: uuu_file_create_date

Label that will Appear on the Form: Upload Date

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: Upload Date

Use these pickers on any Document attribute form to specify the date and time a document was issued, created, or uploaded to the Document Manager.

Data Element Name: uuu_from_date

Label that will Appear on the Form: From Date

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: From Date

Use this picker to specify the “from” date for a date range on a Resource type business process form.

Data Element Name: uuu_to_date

Label that will Appear on the Form: To Date

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: To Date

Use this picker to specify the “to” date for a date range on a Resource type business process form.

Data Element Name: uuu_last_update_date

Label that will Appear on the Form: Last Update Date

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: Last Update Date

Use this picker on a planning sheet to specify the last date the sheet was updated.

Data Element Name: uuu_week_picker

Label that will Appear on the Form: Week of

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: Week of

Use this picker on Resource or Time Sheet business processes to indicate a specific week for reporting.

Data Element Name: uuu_start

Label that will Appear on the Form: Start Date

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: Start Date

Use these pickers on schedule activity attribute forms and schedule sheets to specify start and finish dates for scheduled activities.

Data Element Name: uuu_finish

Label that will Appear on the Form: Finish Date

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: Finish Date

Use these pickers on schedule activity attribute forms and schedule sheets to specify start and finish dates for scheduled activities.

Data Element Name: uuu_early_start

Label that will Appear on the Form: Early Start Date

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: Early Start Date

Use these pickers on schedule activity attribute forms and schedule sheets to specify start and finish dates for scheduled activities.

Data Element Name: uuu_early_finish

Label that will Appear on the Form: Early Finish Date

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: Early Finish Date

Use these pickers on schedule activity attribute forms and schedule sheets to specify start and finish dates for scheduled activities.

Data Element Name: uuu_late_start

Label that will Appear on the Form: Late Start Date

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: Late Start Date

Use these pickers on schedule activity attribute forms and schedule sheets to specify start and finish dates for scheduled activities.

Data Element Name: uuu_late_finish

Label that will Appear on the Form: Late Finish Date

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: Late Finish Date

Use these pickers on schedule activity attribute forms and schedule sheets to specify start and finish dates for scheduled activities.

Data Element Name: uuu_actual_start_date

Label that will Appear on the Form: Actual Start Date

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: Actual Start Date

Use these pickers on schedule activity attribute forms to specify actual and estimated start and finish dates of an activity that is part of an automatically scheduled project or shell; that is, part of a “scope management” schedule.

Data Element Name: uuu_actual_finish_date

Label that will Appear on the Form: Actual Finish Date

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: Actual Finish Date

Use these pickers on schedule activity attribute forms to specify actual and estimated start and finish dates of an activity that is part of an automatically scheduled project or shell; that is, part of a “scope management” schedule.

Data Element Name: uuu_estimated_finish_date

Label that will Appear on the Form: Estimated Start Date

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: Estimated Start Date

Use these pickers on schedule activity attribute forms to specify actual and estimated start and finish dates of an activity that is part of an automatically scheduled project or shell; that is, part of a “scope management” schedule.

Data Element Name: uuu_estimated_start_date

Label that will Appear on the Form: Estimated Finish Date

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: Estimated Finish Date

Use these pickers on schedule activity attribute forms to specify actual and estimated start and finish dates of an activity that is part of an automatically scheduled project or shell; that is, part of a “scope management” schedule.

Data Element Name: uuu_start_baseline

Label that will Appear on the Form: Baseline Start

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: Baseline Start

Use these pickers on schedules and schedule activity attribute forms for the baseline start and finish dates of a project.

Data Element Name: uuu_finish_baseline

Label that will Appear on the Form: Baseline Finish

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: Baseline Finish

Use these pickers on schedules and schedule activity attribute forms for the baseline start and finish dates of a project.

Data Element Name: uuu_start_baseline[1...10]

Label that will Appear on the Form: Baseline [1...10] Start

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: Baseline [1...10] Start

Use these pickers to display the baseline start and finish dates of a project phase on a schedule sheet.

Data Element Name: uuu_finish_baseline[1...10]

Label that will Appear on the Form: Baseline [1...10] Finish

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: Baseline [1...10] Finish

Use these pickers to display the baseline start and finish dates of a project phase on a schedule sheet.

Date Only Picker

The **Date Only Picker** displays an interactive calendar from which the date can be chosen.

The difference between this picker and a **Date Picker** is that a date-only date will not include a time stamp.

In addition to the pickers listed here, you can create your own date only pickers using the Date Only Picker data definition.

Unifier comes with the following DEs for **Date Only Picker**:

Note: These are read-only fields that are auto-populated.

- ▶ **uuu_lse_pay_due_date**
- ▶ **uuu_lse_pay_latest_due_date**
- ▶ **uuu_lse_end_date**
- ▶ **uuu_lse_pay_creation_date**
- ▶ **uuu_lse_start_date**

The following explains each DE in detail:

Data Element Name: uuu_lse_pay_due_date

Label that will Appear on the Form: Payment Due Date

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: Payment Due Date

Use this picker on Lease BPs to display the Payment due date.

Data Element Name: uuu_lse_pay_latest_due_date

Label that will Appear on the Form: Latest Payment Due Date

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: Latest Payment Due Date

Use this picker on Lease BPs to display the Latest payment due date.

Data Element Name: uuu_lse_end_date

Label that will Appear on the Form: End Date

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: End Date

Use this picker on Lease BPs to display the Date on which a lease term ends.

Data Element Name: uuu_lse_pay_creation_date

Label that will Appear on the Form: Payment Creation Date

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: Payment Creation Date

Use this picker on Lease BPs to display the Payment creation date.

Data Element Name: uuu_lse_start_date

Label that will Appear on the Form: Start Date

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: Start Date

Use this picker on Lease BPs to display the Date on which a lease term starts.

Fund Picker

Data Element Name: row_id

Label that will Appear on the Form: Funding Source

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: Use this picker on Cost-type BPs to choose which fund (from the Company Funding Sheet) the BP will allocate funds to or consume funds from.

The system populates this picker with the fund codes created with the Fund attribute form.

Note: Do not use this picker on configurable manager attribute forms.

Generic Cost Code Picker

Data Element Name: uuu_cm0_code

Label that will Appear on the Form: Cost Code

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: Use this picker to define a cost code for a generic cost manager at runtime in Unifier. The picker will show only active codes.

The system populates this picker with the cost codes created with the Generic Cost Manager Attribute form.

Group Name Picker

The **Group Name Picker** (*Group Name Picker* (on page 62)) is the data definition (DD).

Data Element Name: The DE is specified by customer

Label that will Appear on the Form: The display element of the DE.

Available for Forms on Mobile Device: No

What it Does: It lets you pick users.

Hyperlink Picker

The **Hyperlink Picker** is the data definition (DD).

Data Element Name: Specified by customer.

Label that will Appear on the Form: The hyperlink name.

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: It lets you enter hyperlinks for web pages.

Image Picker

The **Image Picker** is the data definition (DD).

Data Element Name: Specified by customer

Label that will Appear on the Form: The file name.

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: It lets you pick images.

Level Picker

Data Element Name: uuu_sp_level_picker

Label that will Appear on the Form: Level

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: Use this picker to select a level record from the Space Manager log.

This picker is populated by the level records that were created with the Level attribute form.

Note: Do not use this picker on configurable manager attribute forms.

Location Picker

Data Element Name: uuu_location

Label that will Appear on the Form: Location

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: Specifying the hierarchy between shells. From this picker, the user picks the parent shell under which another shell should belong.

Note: Do not use this picker on configurable manager attribute forms or on an anchor shell (a single-instance shell).

P6 Activity Picker

Data Element Name: ugenActivityDPK

Label that will Appear on the Form: P6 Activity

Available for Forms on Mobile Device: No

Place holder for Type Ahead: Type Activity ID...

What it Does: This picker displays the list of Activities from Activity Sheet.

Planning Item Picker/Planning Line Item Picker

Data Element Name: uuu_planning_item_picker

Label that will Appear on the Form: Planning Item Picker

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: Use this picker on the upper or detail form of business processes to select a planning item at the company level. Only one Planning Item Picker is allowed per company.

This picker is populated by the planning item records that were created with the Planning Item attribute form.

Note: Do not use this picker on configurable manager attribute forms.

Planning Period Picker

Data Element Name: uuu_ppm_period_picker

Label that will Appear on the Form: Planning Period

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: Use this picker to select a planning period for a portfolio to use. The planning periods for this picker are created under the Standards & Libraries > Period Structure node after the portfolio is imported. At runtime, the picker will show the planning periods the user can choose from (yearly, monthly, or quarterly) and the format in which the period will be displayed (such as YY or YYYY).

The picker will automatically display the current year, plus the next four years.

Project Picker

Data Element Name: uuu_project_picker

Label that will Appear on the Form: Project Picker

Available for Forms on Mobile Device: Project Picker

What it Does: Use this picker on the upper or detail form of company-level business processes to choose a project. You can place multiple project pickers on a form. The picker will show the user a list of the company-sponsored projects to which the user has access. The picker is designed to show active, and on-hold projects.

The system populates this picker with the information from the project shells in the database. Users can use this picker to populate data elements on BP fields with project shell information.

Note: Do not use this picker on configurable manager attribute forms.

See **Project Picker** (on page 64) in the Unifier Data Definitions (DDs) section.

Project Template Picker

Data Element Name: uuu_proj_template_picker

Label that will Appear on the Form: Project Templates

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: Use this picker on the upper or detail form of a Project/Shell Creation BP to specify the template that should be used by this BP to auto-create a project. The picker will show the user a list of active project templates.

Resource Picker

Data Element Name: uuu_resc_picker

Label that will Appear on the Form: Resource Picker

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: Use this picker on a Time Sheet or Booking BP to choose the resource to report on or assign. This picker always opens in “Find” mode and requires the user to enter at least one search criteria, such as a name or a skill, to narrow the field of names to choose from.

For timesheet BPs, users will use this picker to select the personnel to report time on. At runtime, the picker will default to read-only mode and show the current user's name, as Unifier assumes the user will be reporting his or her own time. However, depending on permissions, the picker can be editable in order to allow others, such as project managers, to complete time sheets on behalf of other workers.

This picker is populated by the resource records that were created with the Resource attribute form.

Note: Do not use this picker on configurable manager attribute forms.

See Resource Picker in *Unifier Data Definitions (DDs)*.

Role Picker

Data Element Name: uuu_role_picker

Label that will Appear on the Form: Role Picker

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: Use this picker on a timesheet or booking BP, or for Resource Allocation Sheets. It allows the user to choose the role to report on or assign.

When you use this picker on a timesheet BP at the project level, it will filter out those roles that have already been booked for other projects.

This picker is populated by the role records that were created with the Role attribute form.

Note: Do not use this picker on configurable manager attribute forms.

Role Data Picker

The **Role Data Picker** is the data definition (DD).

Data Element Name: The DE is specified by customer

Label that will Appear on the Form: The display element of the DD.

Available for Forms on Mobile Device: No

What it Does: It enables you to pick users.

Seasonal Dates Picker

Data Element Name: uuu_rec_ses_dates_pkr

Label that will Appear on the Form: Additional Scheduling Conditions

The labels are configurable and based on the label corresponding to the place-holder for Type Ahead.

Place holder for Type Ahead: Type a Name...

Available for Forms on Mobile Device: Yes (iOS & Android)

The Type Ahead is not supported on mobile device.

What it Does: It will search and fetch the seasonal dates whose Name contains the entered value.

Shell Picker

Data Element Name: uuu_default_shell_picker

Label that will Appear on the Form: Shell Picker

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: Use this picker on a business process, Asset class forms, Planning Item form, or configurable manager to select a shell to view in Unifier. This picker usually works in conjunction with the Space Picker. It is mandatory on any company-level BP or Asset class that includes a Space Picker and optional on all others.

This picker is populated by the shell types that were created with the space detail (attribute) form.

Do *not* use the Shell Picker on the following forms; it will produce an error at runtime:

- ▶ Schedule Activity attribute form
- ▶ Generic Cost Manager attribute form
- ▶ Any configurable manager attribute form

Shell Template Picker

Data Element Name: uuu_shell_template_picker

Label that will Appear on the Form: Shell Templates

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: Use this picker on the upper or detail form of a Project/Shell Creation BP to specify the template that should be used by this BP to auto-create a shell. The picker will show the user a list of active templates that have been created for the shell.

This picker works in conjunction with the **uuu_shell_location** data element so that the picker list displays only those shell templates belonging to a specific shell type.

Shell Data Picker

Data Element Name: User-defined.

Label that will Appear on the Form: User-defined.

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: Use this picker to select a shell instance (location).

Single User Picker

Data Element Name: There is no specific DE name for Single User Picker. The user can create a user picker with any name.

Label that will Appear on the Form: User can create a user picker with any label.

Available for Forms on Mobile Device: It is available for Forms and mobile device.

What it Does: Enables the user to select one single user from the picker.

SOV Picker

Data Element Name: WBS Picker

Label that will Appear on the Form: Cost Code

Available for Forms on Mobile Device: No

What it Does: It lets you pick CBS codes from referenced Base Commit record (includes CBS codes selected in base Commit and change Commit).

Space Picker

Data Element Name: uuu_phy_space_picker

Label that will Appear on the Form: Space

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: Use this picker on any business process, asset, resource, or planning item to select a space record from the Space Manager. This picker often works in conjunction with the Shell Picker. A Shell Picker is mandatory on any company-level BP or Asset class that includes a Space Picker.

This picker is populated by the space records that were created with the space detail (attribute) form.

Note: Do not use this picker on configurable manager attribute forms.

SYS Date Picker

Data Element Name: uuu_creation_date

Label that will Appear on the Form: Creation Date

Available for Forms on Mobile Device: Yes

What it Does: This picker views the date a business process record was created. The system automatically populates this element.

User Picker

Use **User Picker** to choose members of a project team or any user defined within a company; for example, to designate a contact person unrelated to the workflow assignees. The system populates these pickers with user names in the database.

In addition to the pickers listed here, you can create your own user pickers using the User Picker data definition.

The system comes with the following DEs for **User Picker**:

- ▶ **uuu_cost_owner**
- ▶ **uuu_dm_created_by**
- ▶ **uuu_file_create_by**
- ▶ **creator_id**

The following explains each DE in detail:

Data Element Name: uuu_cost_owner

Label that will Appear on the Form: Owner

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: Owner

Use this picker on a Cost attribute form to identify the owner of a cost code.

Data Element Name: uuu_dm_created_by

Label that will Appear on the Form: Owner

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: Owner

Use this picker on a Document attribute form to identify the owner of a document.

Data Element Name: uuu_file_create_by

Label that will Appear on the Form: Upload By

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: Upload By

Use this picker on a Document attribute form to identify the person who uploaded the document to the Document Manager.

Data Element Name: creator_id

Label that will Appear on the Form: Creator ID

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: Creator ID

Use this picker on any type of business process form to identify the person who created the BP record.

User Data Picker

The **User Data Picker** is the data definition (DD).

Data Element Name: The DE is specified by customer

Label that will Appear on the Form: The display element of the DD.

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: It lets you pick users.

WBS Code Picker

Data Element Name: bltemID

Label that will Appear on the Form: Cost Code (User defined - editable)

Available for Forms on Mobile Device: Yes

Place holder for Type Ahead: Type WBS Code or Name...

What it Does: This picker selects a WBS code.

WBS Picker

Data Element Name: uuu_cmwbs_picker

Label that will Appear on the Form: WBS Picker

Available for Forms on Mobile Device: Yes

Place holder for Type Ahead: Type WBS Code...

What it Does: This picker displays the list of WBS Codes from WBS Sheet.

Week Picker

Data Element Name: uuu_week_picker

Label that will Appear on the Form: Week of

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: Use this picker on Resource or Time Sheet business processes to indicate a specific week for reporting.

Work Package Picker

Data Element Name: wpid

Label that will Appear on the Form: Work Package

Available for Forms on Mobile Device: Yes (iOS & Android)

What it Does: Use this picker on the detail form of any Cost type business process to select a work package. Users create the work packages from a specific Cost Sheet. The system then populates this picker with the work packages that have been created.

For Base Commit business processes, the value selected in the Work Package Picker in a line item is automatically populated in the Work Package Picker in the line items in the associated General Spends, Payment Application, and Change Commit business processes. This value can be updated manually, through CSV import, or through Web Services Integration. This automatic population applies only to Base Commits with the Commitment Summary Line Items specified as Individual commit line items in the Options tab of the business process Properties. Also, the Integration Detail Forms designed for the associated business processes must contain the Work Package Picker to facilitate the automatic population of the Work Package Picker in the line items of those business processes.

Notes:

- Do not use this picker on configurable manager attribute forms.
 - This picker is not available for Summary Payment Application (SPA) type business process.
-

Glossary

The following provides definitions for most common terms used in the system.

In This Section

In Alphabetical Order A-G	377
In Alphabetical Order H-N	389
In Alphabetical Order O-T	393
In Alphabetical Order U-Z	402

In Alphabetical Order A-G

Account Code

A company-level cost code that is associated with cost line-item transactions. You can roll up company-level BP, project, and asset related cost transactions into this account code.

Project and asset cost transactions are rolled up using mapping.

Accounts Sheet

An Accounts Sheet is a detailed accounting of the company's budget and costs. An accounts sheet works like a spreadsheet, calculating and maintaining the company cost information.

Cost information is either entered manually or rolls up into the company Cost Sheet when transactions occur.

Action Form

The Action Form is the version of the business process form that opens when the recipient accepts the task implicit in the form. As a business process arrives at each step in a workflow, the system notifies the appropriate users if they are involved in the step.

When they open the notification, the system displays a view-only form of the step's task.

If the user accepts the task, the form becomes an action form where the user can enter or edit information and attach additional documents. See also "View Form."

Activity

A part of the work or event that must be completed on a schedule.

Acquisition Cost

The purchase price of an asset.

Acquisition Date

The date an asset was purchased or installed. This is the date from which the depreciation calculation will begin.

Actuals

The actual hours entered via time sheets and the costs calculated from the hours entered.

Actual Cost of Work Performed (ACWP)

The actual cost incurred for work performed. This cost is usually captured by invoices, Payment Applications, or Summary Payment Application. It is a key component for determining Earned Value. See also "Earned Value."

Administration Mode

Administration (Admin) mode allows administrators to set up and configure Unifier and Primavera uDesigner functions.

Administrators

There are three types of administrators: System Administrator (or Site Administrator), Company Administrator, and Project Administrator.

Although the system allows complete flexibility in assigning individual users permission to access its features, the administrators typically perform certain administration functions. See "System Administrator", "Company Administrator", "Project Administrator."

Allocation

The process of distributing available capacity, by role, to projects. Places constraints on how much resource capacity individual projects can utilize. Also, the process of distributing funds to projects. After you allocate the funds to the project, they are assigned for consumption.

Assignees

The users or groups assigned to a business process workflow step, for review, approval, response, and so on.

Attribute Form

An attribute form collects "meta data," or additional information about a business process, manager, or other system component; often referred to as the component's "properties." It is for collecting information that is not part of a workflow. For example, you can design a cost attribute form with fields that will track extended information about a CBS code. You can design a fund attribute form with fields to define segments, and reference fields for fund codes.

Typically, the information collected by attribute forms populates fields in many of the system's windows and dialogs.

Auto-creation

The process of automatically creating a business process record. There are different ways to auto-create a record:

► **From a workflow**

In uDesigner, a business process form can be designed to automatically create a new BP record after the form reaches a specified step in the workflow. The new record will contain an exact duplicate of the information in the original record—all the information that was contained in that transaction, including forms, attachments, and comments. After being created, the new BP is sent automatically to the next step in the workflow. The original BP record can automatically populate the upper form and detail form on the new BP record, provided the data elements of the form fields are the same on both records.

► **From a form**

In uDesigner, a business process form can be designed to automatically create a new BP record based on:

- A condition, such as a dollar amount
- A frequency, such as a daily or weekly time frame
- Both a condition and a frequency

When the business process reaches the condition or frequency trigger(s) in the workflow, the form will automatically create a new business process record. After being created, new workflow BP records are sent to an initiation step (I step) before the beginning of the workflow. When the user accepts the task, he/she can choose a new workflow schema, BP owner, and workflow duration. For non-workflow BP records, the new record opens immediately to a view only form when the user accepts the task; there is no workflow schema to choose.

► **Using Scope Management**

Scope Management creates a BP record from any activity on a schedule sheet that is set for scope management. Activities that use scope management are similar to BPs in that they move through a workflow in the Schedule Manager. Scope management defines the project deliverables, the responsible roles, the actual resource assignees and their schedules, and drives the coordinated production of the deliverables. It initiates the activities that produce the deliverables; routes the activities to the responsible person or group; monitors its completion; and updates the deliverables statuses automatically.

Auto-population

A feature that automatically populates the fields on a business process form with data from other business processes (called “Reference Process”). Auto population is supported for text boxes, text areas, drop-downs, check boxes, radio buttons, and date pickers only. Before you can auto-populate a business process, you must design a reference process from which to draw the data. To auto-populate an element, the data definition of both the source and the destination element must match.

You can also auto-populate a Payment Application from a Base Commit BP. You can use this feature only on SOV type payment applications or SOV line item type individual commit line items. Although you can use the auto-populating method described in the paragraphs above, you can, alternatively, do this in one step when you create a Base Commit BP. To accomplish the auto-population in one step, use the **Options** tab to map the fields when you launch the Base Commit BP.

Base Currency

Currency under which a company is operating. Additional currencies can be added and made available for use within projects and shells, and even for individual transactions. These additional currencies will apply a defined exchange rate calculation based on the base currency.

Baseline

The original schedule produced at the beginning of a project and accepted as the contractual project schedule. This baseline is the schedule against which progress and payments are measured until the schedule is revised.

A baseline is essential for tracking progress. The original estimates it contains are permanent reference points against which you can compare the updated task information that you enter into your project plan as the project progresses.

You can create additional baselines for construction **phases** (up to 11 in a single project plan).

BP

See “Business Process (BP)”

Bid items

The line items of a Request for Bid (RFB) business process record.

Bid Package

The header and details of a bid request.

Bid tabulation

A comparative view of the bids submitted by the bidders on a project.

Bidder

A vendor or supplier who bids on a project.

Blanket Purchase Order (Blanket PO)

A blanket PO is a company-level sub-type of a cost business process. It is independent of a budget or cost sheet and is used for tracking non-CBS expenses across projects. Blanket PO records are stored in the Company Data Manager.

Block

A block is a grouping of cells on a BP form. uDesigner users can add blocks to Upper Forms and Detail Forms, customizing fields, order, size, positioning, number of columns and rows, and so on. Once blocks are created, the user can insert fields (data elements) into the blocks.

Booking Process

The process of finding and committing resources (personnel) to fill project roles. Hard booking denotes a firm or approved commitment. Soft booking denotes a pending commitment.

Budget at Completion (BAC)

The sum of all the budget values established for the work to be performed on a project or a work breakdown structure component or a schedule activity. The total planned value for the project.

Budget Cost of Work Performed (BCWP)

Also known as earned value. This is the cost of the percentage of work completed with respect to the Budget Cost of Work Scheduled.

For example, a simple construction project has a budget of \$1000. This budget is scheduled to be consumed over a period of five days. If construction activity is 60% complete on the third day, the BCWP is \$600 ($.60 \times \1000). It is a key component for determining Earned Value. See also "Earned Value".

Budget Cost of Work Scheduled (BCWS)

This is a time-based budget that is assigned and scheduled by the Work Breakdown Schedule for an entire project.

For example, a simple construction project has a budget of \$1000. This budget is scheduled to be consumed over a period of five days. The BCWS will be \$200 per day. It is a key component for determining Earned Value. See also "Earned Value".

Budget of an Activity

In terms of cost, the total expense that will be incurred to complete an activity. Contributors to this cost can be labor, material, equipment, or other costs.

In terms of units of measure, it is the total units that will be spent to complete an activity. These units can be hours, linear feet, or other units of measure, depending on the activity and the resources assigned to that activity.

Business Process (BP)

A business process (BP) is a set of coordinated tasks and activities that lead to the accomplishment of a specific business goal. For example, creating, routing, and approving a purchase order is a business process. BPs often include a workflow to specify how the business process should proceed, from start to finish. BP also refers to the *forms* that drive the business process. For most BPs, these BP forms will become attached to the steps in a workflow for the purpose of exchanging information. As part of the workflow, users will use these forms to collaborate as a team to complete the business process.

Business Process Types

Different business needs require different types of business processes. There are currently ten types of business processes that are used in Unifier, and can be created in uDesigner: Cost, Line Item, Text, Document, and Simple, RFB, Schedule, Resource, Planning, and Lease.

Cash Flow

The Cash Flow feature is a way to view a time-based record of income and expenditures, which can be presented in tabular or graphical format. It enables users to create a baseline for project expenditures, track actual costs, and calculate future expenditures based on a known forecast or calculate from trends compared to “Baseline” curves.

CBS Code

See "Work Breakdown Structure (WBS)/CBS Code."

Commitment Summary

Works the same way a Schedule of Values works, except that it is used by a Generic Cost Manager in a shell. See “Schedule of Values (SOV).”

Company Administrator

Company administrators can (depending on permissions) create or modify projects, create data definitions for custom attributes on BP forms, activate business process schemas and define record numbering schemas, create users and groups and grant their permissions, set up templates, and add currencies.

Company Dashboard

A dashboard that is accessible at the Company level and can be used to view company data across projects or shells.

Company Funding Sheet

The Company Funding Sheet tracks all sources of funding across all projects. You can create only one sheet per company. Funding sources that are made available at project sheet level are rolled up to the company sheet, which maintains the overall fund information.

Conditional Routing

A divergence in the route of a business process, depending on a specific condition or situation.

BP workflows can be created to include a conditional step; that is, a step that must be resolved before the workflow can continue. Conditional steps entail separate (conditional) routing. This routing is triggered by a condition or situation that was set in uDesigner when the workflow was designed. An example of conditional routing is a purchase order that follows one workflow if the total amount is less than a certain amount, and follows another if it is equal to or greater than that amount. (These trigger values are assigned when the business process is set up in Unifier.)

Conditional Step

A step that must be resolved before the workflow can continue. Conditional steps entail separate (conditional) routing. This routing is triggered by a condition or situation. An example of conditional routing is a purchase order that follows one workflow if the total amount is less than a certain amount, and follows another if it is equal to or greater than that amount. These trigger values are assigned when the business process is set up in the system and can specify multiple data elements that must be satisfied to activate the trigger.

Configurable Manager

A configurable manager is a manager that has been especially created for your company. Up to 25 managers can be created consolidate and monitor any entities you want. Configurable managers differ from the managers that are shipped with Unifier in that configurable managers can roll up not only currency amounts, but also quantity amounts.

You can design two kinds of managers: **Code and Records-based** and **Code-based**.

- ▶ A **Code and Records-based** manager employs both codes to create a tracking sheet and records of individual items.
- ▶ A **Code-based** manager employs only a sheet to keep track of the values it is monitoring.

From a **Code and Records-based** manager, you can drill down from the sheet to individual items; from a **Code-based** manager, you cannot.

Consolidate Comments

Collect the comments from multiple business process records into a single record. When you consolidate comments, you can also opt to copy any attachments along with the comments.

Consolidate Line Items

Collect the line items from multiple business process records into a single record. When you consolidate line items, you can also opt to copy the line item attachments.

Consolidate Markups

Collect the markups from multiple document business process records into a single record. When you consolidate markups, you can also opt to copy any attachments along with the markups.

Contingency

Contingency is a data source on a cost sheet that represents the budget amount allocated to contingency spending for each CBS code. It is useful for users in forecasting their contingency spending.

Cost Codes

Displays the type of cost code (fields that define the structure of the Cost Codes) specified in uDesigner for the project/shell.

Cost Performance Index

A measure of cost efficiency on a project. It is the ratio of earned value (EV) to actual cost of work performed (ACWP), or earned value divided by ACWP.

A value equal to or greater than one indicates a favorable condition; a value less than one indicates an unfavorable condition.

Cost Sheet

A Cost Sheet is a detailed accounting of the project's budget and costs. A cost sheet works like a spreadsheet within the system, calculating and maintaining the project cost information stored in the project. Cost information is either entered manually or rolls up into the Project Cost Sheet when transactions occur in the system.

Cost Type BP

BP forms that track and manage cost information. The system can be configured to show this information automatically on the cost sheet. Examples include change orders, base contracts, invoices, and budget change requests.

uDesigner users can create custom BPs that have additional cost-related features, such as automatic generation of “Schedule of Values (SOV)” sheets for commit BPs, and funding allocations with spend BPs.

Cost Variance

Any difference between the estimated cost of an activity and the actual cost of that activity. It is usually the budgeted cost of work performed minus the actual cost of work performed. A negative variance means more money was spent for the work accomplished than was planned.

Critical Path

The series of tasks (or even a single task) that dictates the calculated finish date of a project. When the last task in the critical path is complete, the project is complete. By knowing and tracking the critical path for the project, as well as the resources assigned to critical tasks, you can determine which tasks can impact the project's finish date and whether or not the project will finish on time.

Specifically, the critical path takes the sequence of inter-dependent project network activities with the longest overall duration and determines the shortest possible time the project can be completed. The critical path algorithm calculates the starting and ending times for each activity, determines which activities are critical to the completion of a project (the critical path) and notes those activities that are less critical with “float time.” There is no float time on the critical path.

Critical Task

A task that must be completed on schedule for the project to finish on time. If a critical task is delayed, the project completion date might also be delayed. A series of critical tasks makes up a project's critical path.

Cumulative Depreciation

The total reduction of the value of an asset over a period of time.

Current Period Depreciation

The current reduction in the value of the asset.

Custom Element

A data element you have created. See “Data Elements”

Data Cube Definition

A Data cube definition is a query tool you can use to extract data and display it on a block of a configurable dashboard.

Data Definitions

Data definitions describe how data is entered and stored. The definition consists of the data type (whether it is an alphabetical string or a number), the data size (in number of characters for strings), and the input method (from a text box, drop-down [pull-down] menu, radio button, or check box). You must create data definitions before you specify the data elements for forms. The data definitions dictate how the data element will enter and store the information. A data definition can belong to one of the following categories:

- ▶ **Basic:** Predefined or user-defined Data Definitions that contain all Data Definitions except the Cost Code definitions.
- ▶ **Cost Codes:** Displays the type of cost code (fields that define the structure of the Cost Codes) specified in uDesigner for the project/shell.
- ▶ **Data Picker:** Data pickers work with master business process logs, shells, and configurable managers that function across a shell hierarchy. The purpose of a data picker is to make it easier for users to choose records:
 - From a master business process log
 - From a class in a configurable manager that operates across shells
 - For auto-creation across shells

A data picker usually displays an extra navigation structure that makes it easier for users to choose records to work with. In operation, a data picker navigates to a specific business process, shell, or configurable manager and then extracts the records to display on the list by using a query the Administrator sets up.

- ▶ **Access:** Data Structure Setup node

Data Elements

Data elements combine a “Data Definitions” with a field label to become what users see on the forms. The fields on the forms the users see are filled by data elements. A data element can be a text box, where the user types in information; a drop-down (pull-down) menu of choices (also known as a picker), such as dates or names; radio buttons, where the user must select one of the options presented; or a check box, where the user has the option of choosing something or not.

Data elements are the name and form label only—the element is essentially an empty “shell” that will not contain values until they are specified.

Data Indexes

Allows the creation of user-defined database indexes that speed up the performance of large data sets. The database index name is constructed by a fixed prefix, UUU, plus internal row_id, followed by _ and a user-defined suffix and description.

Access: Data Structure Setup node

Data Pickers

Data pickers work with master business process logs, shells, and configurable managers that function across a shell hierarchy. The purpose of a data picker is to make it easier for users to choose records:

- ▶ From a master business process log
- ▶ From a class in a configurable manager that operates across shells
- ▶ For auto-creation across shells

A data picker usually displays an extra navigation structure that makes it easier for users to choose records to work with.

In operation, a data picker navigates to a specific business process, shell, or configurable manager and then extracts the records to display on the list by using a query the Administrator sets up.

Access: Data Structure Setup node > Data Definitions

Data Source

A data source is the source from which you can extract data for any component of Unifier or Primavera uDesigner. For example, when creating a cost column on a cost sheet, the data source might be a cost BP transaction.

Data Views

Provides a view of data obtained via SQL query. It allows access to all database tables in a company registry (registry dependency ensures data security).

Data Views enable administrators to design and deploy custom reports (shell-level), create user-defined reports (UDRs), and utilize data as a source for Data Cubes (used to display live, or cached data in a custom company or shell dashboards).

Access: Data Structure Setup node

Dependency

An activity or task that must occur before another activity or task. See “Predecessor.”

Depreciation

The reduction in the value of an asset. Users can choose the method by which they want to depreciate an asset—straight line, double decline, sum of years, or manual.

Depreciation Period

The time over which an asset is depreciated; can be in years, months, or quarters.

Detail Form

The detail form is the form the user is presented with to add or modify a line item on certain business processes. The detail form contains the fields (data elements) that will be displayed on the line items list. See also “Upper Form”

DMS

See “Document Manager”

Document Manager

The Document Manager allows team members to manage and share project documents and organize them into folder structures. The manager ensures that project members are always using the most current versions of documents and makes accessing and distributing documents efficient.

Document Type BP

This is a BP form that can be used as an “envelope” to package a set of files, such as spreadsheets, drawings, and design documentation, that flow from one group to another. An example is a Transmittal.

Drafts (Drafts log)

A storage log where users can save a draft or copy of any BP they are creating or responding to.

Dynamic Data Element

Dynamic data elements are fields on BP forms that behave differently, depending on what the user chooses in a **master element** field. The master element dictates what the other fields in the set will show and how they will behave. For example, on a form that requires a state and city designation, the “city” field will show a different list of cities, depending on the state the user chooses. See Dynamic Data Set

Dynamic Data Set

Dynamic data sets control what other data elements display or how they behave. You can use data sets to dictate how drop-down (pull-down) lists, radio buttons, and check boxes behave when the user has multiple-choice options. The data sets are considered “dynamic” because the data values change, depending on what the user chooses in the master element field. For example, on a form that requires a state and city designation, the list of cities changes, depending on the state the user chooses. The state and city elements become a dynamic data set, and the master element (state) dictates what cities will appear in the drop-down list.

Earned Progress

A quantitative measurement to indicate how much has been earned on an activity over the duration of the activity. Earned progress can be represented as an amount, a quantity, or a percentage. It is a key component for determining Earned Value.

See also “Earned Value”.

Earned Value

Earned value is a method for measuring project performance. It compares the amount of work that was planned with what was actually accomplished to determine if cost and schedule progress are as planned.

Earned value analysis is an industry standard used to measure a project's progress, forecast its completion date and final cost, and provide schedule and budget variances.

Element

See “Data Elements”

ER Views (Entity Reference Views)

Provides a tabular view of the database tables that exist for each of the entities.

For example, if you open the ER View for Business Processes, it shows you the tables that are available for existing business processes in the company.

When data views are defined, the ER Views feature becomes particularly helpful for users without access to back-end and allows the users to see information within the application.

Access: Data Structure Setup node

Escalation

A clause in a lease which provides for the rent to be increased to reflect changes in expenses paid by the landlord, such as real estate taxes, operating costs, and so on. This may be accomplished by several means, such as fixed periodic increases, increases tied to the Consumer Price Index, or adjustments based on changes in expenses paid by the landlord in relation to a dollar or base year reference.

Estimate at Completion (EAC)

The final cost of any other key quantity (for example, hours, feet of material, or other quantity) based on provided estimates.

Estimate to Complete (ETC)

An estimate of cost or any other key quantity that a project can still incur based on estimates and the actual cost incurred so far by the project.

Exchange Rate

The price of currency of one country expressed in units of another currency. The exchange rate is used when converting transactions made in currencies other than the base currency.

Exchange Rate Set

Consists of all of the currencies and exchange rates currently available for transactions. When your company is first set up by the site administrator, the set contains only your company's base currency. Any time you add additional currencies or modify exchange rates, a new set is created and replaces the last one.

Extrapolate

When users create a cash flow curve, they have the option of **extrapolating** the actual cost based on a provided data set. For example, they can estimate (extrapolate) the cash flow curve for this year based on last year's data. They will need to specify which data from last year's Cash Flow Sheet they want to base the extrapolation on.

See also "Interpolate"

Finish to Finish

Denotes that a task cannot end until another ends.

Finish to Start

Denotes that a task cannot start until another ends.

Float

The float (slack) value for each activity. This is calculated as a result of the critical path calculation.

Form Validation Rules

Form validation rules are created to validate form field values. Validation occurs at runtime when users click the Send or Save button. These rules apply to all forms, including BP forms and attribute forms.

Funding Appropriation (Automated)

Cost type commit BPs can be set up in uDesigner to allow Unifier users to allocate or consume funds. Funds are chosen from an available list using a fund picker. When the BP reaches its terminal status, the funds are allocated or consumed automatically. A button becomes available on the form allowing the user to access the funding sheet directly from the BP form.

Funding Manager/Funding Sheets

The Funding Manager tracks where project funding comes from, and how it is being spent. Funding is defined first at the company level, where individual funding sources are set up on the Company Funding Sheet. Project Funding Sheets track how funding is being spent on each project; individual transactions are rolled up to the Company Funding Sheet.

Gate

A set of conditions applied to a project phase which, when fulfilled, moves the project to the next phase.

Gate Elements

The criteria that define what the gate is. These are the conditions that a project phase must meet or complete before the project can progress to the next phase.

Generic Cost Manager

Generic cost managers monitor cost-related activities for shells. Unlike the Standard Cost Manager, the data analyzed by a generic cost manager comes from the cost sheets of shells and sub-shells. Generic cost managers are well-suited for projects/shells of an ongoing nature, such as a building shell, where you would typically want to collect and analyze operating and maintenance costs for a specific building over the life of that building.

To accommodate the on-going nature of shells, a generic cost manager reflects rolled up **quantity amounts** as well as currency amounts. In addition, it uses a "Commitments Summary" instead of an SOV, and employs a different, "commit" coding structure; it does not support CBS codes. Compare with "Standard Cost Manager."

In Alphabetical Order H-N

I Step

An I Step is a step that is automatically created under the following circumstances:

- ▶ An activity on a schedule has been configured for Scope Management. Under Scope Management, the activity moves through a workflow; but first the activity is sent to an initiation step before the beginning of the workflow. At this point, the user can specify a new workflow schema, new owner of the activity, duration of the activity, and a new location (such as a different project) for the activity.

- ▶ A new business process is spawned by a BP Creator element from an upper form or a line item list based on:
 - ▶ A condition, such as a dollar amount
 - ▶ A frequency, such as a daily or weekly time frame

After being created, the new BP is sent to an initiation step before the beginning of the workflow. At this point, the user can specify a new workflow schema, new owner of the business process, duration of the process, and a new location (such as a different project) for the business process. Compare to “S Step.”

Instance

A reproduction of a component, based on a type, usually a shell. Instance can also refer to a BP record.

Integration

The integration feature imports and exports business process data en masse between Unifier and an outside application via Web Services. Integration automatically creates BP records, which is useful in cases where the user wants to populate the system with a large amount of user information that exists in another form, such as an Excel spreadsheet.

Integration Interface

To integrate data, you must create an integration interface; from this interface, you create a template that will import or export the data in a form that will be usable by both Unifier and the outside application. The data you can import or export comes from the fields on the forms that are part of a business process. The integration interface that you create determines what fields from the business process will be included on the import or export template.

Interpolate

Interpolation is estimating a cash flow curve based on known start and end values. There is not an equivalent option to “interpolate” as there is for “extrapolate based on data set,” but it is possible to interpolate data by specifying end point cost data. For interpolation, the curve will be based on a specified end point. The base curve and interpolated curve will merge together if the end values are the same.

See also “Extrapolate”

Latitude

An angular measurement in degrees ranging from 0° at the equator (low latitude) to 90° at the poles (90° N for the North Pole, 90° S for the South Pole; high latitude. Latitude denotes the location of a place either north or south of the equator.

See also “Longitude”

Lease

An agreement whereby the owner of real property (landlord/lessor) gives the right of possession to another (tenant/lessee) for a specified period of time (called a term) and for a specified consideration, such as rent.

Level

A level is the “platform” on which spaces reside in the Space Manager. A level could be “Floor 10” or “Parking Garage,” or “Basement.”

See also “Space.”

Line Item BP

A business process that may be used for any generic data. The line item format is similar to cost BPs, but without currency restrictions.

Linked Records

This is a field that appears as a link at the bottom of a BP record, and allows users to dynamically attach read-only copies of supporting BP records to the BP. Linked records can be opened and reviewed from within the BP to which they are attached.

Linked Schedule Sheets

Project or shell schedule sheets that are dynamically linked to a schedule sheet template. Linked project or shell schedule sheets can be updated with changes from the schedule sheet template as needed.

Log

Every business process, manager, and shell includes a log.

These logs list:

For business processes All the records that were created whenever a business process completed its cycle through a workflow. The logs contain one record for each cycle of the workflow. Each record contains all the information that was generated during the cycle, including the forms, documents, comments, and other data that was collected in the system during the BP's runtime.

For manager classes Everything that belongs to that class. Each record contains all information on that item in the class.

For manager sheets All the sheets that have been created for the manager. These sheets consolidate information and display whatever data they were designed to monitor.

For shells (visible in Admin mode only) Every shell that was created for that shell type. Each record contains all the information about how the shell is configured.

For business processes, shells, the Space Manager, and Code and Records-based managers, you can design either a standard log, or an advanced log that will work with the master business process log and data pickers. An advanced log creates an extra navigation structure that makes it easier for users to choose records to work with.

Longitude

An angular measurement in degrees ranging from 0° at the prime meridian to +180° eastward and -180° westward. Longitude denotes the location of a place either east or west of the prime meridian.

See also “Latitude”

Manager

Managers are a means to create, consolidate, and monitor such things as schedule activities, company assets, or project/shell or company costs. Most managers work as nodes in the navigator where users can create both the items to manage, and an electronic “sheet” where these items can be consolidated and monitored. You can, however, create your own managers to consolidate and monitor any entities you want. After you have created a manager, you can deploy it at the company or project/shell level. You can create up to 25 managers.

Master Data Element

A data element on a form that controls the behavior of other data elements. For example, on a form that requires a state and city designation, the list of cities changes, depending on the state the user chooses. The state and city elements become a dynamic data set, and the master data element (state) dictates what cities will appear in the pulldown list.

See also “Dynamic Data Element”

Master Log

Permission-controlled business process log that is accessible from the Home node for all project and shell business processes and provides access to business process records of the same type that may exist in multiple shells or projects.

Master Schedule Sheet

The schedule that drives activity start and finish dates, resource assignments, and resource availability through other modules, such as resource management. Only one master schedule sheet can exist for any given project.

Message (Messages Log)

The Messages Log displays copies of BP records that a user has been “cc'd” on during the workflow. BPs in the messages log are view-only copies for reference only.

Milestone

An activity or task that represents a significant point in time, such as a hand-over date. Milestones have zero duration.

Modes of Operation

The system has two modes of operation: User mode and Administration (Admin) mode.

My Dashboard

Dashboard specific to signed-in user in a shell, and configured by the user, or by the administrator for the user. End users can modify these dashboards. By default, all shells have a dashboard that the end user can configure if they have configure permissions. The dashboard is the user's personal dashboard, with their personally configured view of shell data. This dashboard is recommended if the user wants a personalized dashboard to view data that they specifically need to see regarding the shell.

Named Users

Used in the License Manager. The License Manager counts the number of “named users,” which is the number of users a company pays for. An “active named user” refers to any user in the system with a status of “Active” or “On hold”; that is, they have a user name and password. Users with a status of “Inactive” are not counted against the license terms.

Net Book Value

The difference between an asset's starting book value and the current value (at the current depreciation period).

Numeric Formula

A formula used for calculating numeric field values. Any numeric, integer, currency, or decimal amount data element can be used to design a formula. There must be other numeric data elements available in order to design a formula. The formula is based on calculations that are assigned to the field by selecting from a list of available numeric data elements.

In Alphabetical Order O-T

Owner Company/Sponsor Company

The entity that engages in business and has the complete control (or ownership) of Unifier with all its rights and privileges.

Partner Company/Member Company

The consultants, contractors, and vendors that have been invited to participate in a project by the Owner Company/Sponsor Company. The system allows the addition of Partner Company/Member Company to enable project users to collaborate on (and coordinate) the execution of a project.

Payment Applications

Payment applications are a sub-type of cost-type BPs. They are used for scheduling payments against construction contracts. Transactions on this type of BP roll up to the Cost Manager.

Percentage of Work Complete

A percentage value that indicates the current status of a task, resource, or assignment, expressed as the percentage of work that has been completed. It is between 0 (when no work has been performed on the task) and 100 (when all the work has been completed on the task). Using this value, you can compare planned work to actual completed work.

Planning Item

Initiatives, projects, plans, or proposals that a company is planning to start. These are not yet real projects in Unifier; however, the planning phases can be managed as business processes.

Planning Manager

The Planning Manager is where users can plan for new projects and proposals and create forecasts for those projects that are already running. They cannot administer planned projects the way they administer real projects in Unifier; however, they can manage the planning phases for these projects as business processes using the same functions used by other business processes.

Planning Sheet

The company Planning Sheet provides an overview of all plans being considered by the company. The Planning Sheet is central to Planning Manager functions. It is from this sheet that users access, create, update, and import or export company plans. From the planning sheet, users can automatically update plans with changes made on the planning sheet. Reciprocally, they can refresh the planning sheet with changes made to individual plans.

Pickers

Pickers appear as selection lists on business processes and other components. These pickers allow the user to choose elements such as dates, blanket POs, other users, companies, line items, funds, or currencies.

Predecessor

A dependency; an activity or task that must occur before another activity or task. On schedules, predecessor relationships between activities are shown as lines terminated by arrows.

Private bid

A bidding process open to a specific set of bidders that have been selected during the invitation process.

Project Administrator

Performs tasks necessary to the administration of projects within the system; typically, creating projects, adding project users, creating groups and granting permissions, creating project cost sheets, creating business process setups, and defining workflows.

Project Funding Sheet

Project funding sheets track how your company's funding is being spent on each project. It tracks individual transactions, which are rolled up to the company funding sheet.

Project Phase

An intermediary milestone of a project.

Public bid

A bidding process open all vendors currently active on a project.

RFB

See "Request for Bid".

Record

A set of related data items treated as a unit. For example, in stock control, the data for each invoice could constitute one record. Also, all the fields on a BP form constitute a record.

Reference Process

A Reference Process is a business process that another business process has referenced by way of a picker on a form. Users use pickers on one business process form to call data from another—a referenced—business process. The picker establishes a link between the records of the two business processes (for example, an invoice BP to purchase order BP). Reference processes are usually used to auto-populate pickers. They are necessary for any BP form that uses BP pickers and line item pickers.

Reference processes contain the list of items the user can choose from the picker. Because a reference process establishes a link, record to record, you can populate the fields or pickers of one business process with the data from the referenced process.

Request for Bid

The Request for Bid (RFB) is a type of line item BP. RFBs are unique business processes that require participation from personnel outside your company. For an RFB, two sets of BP forms are required—one for the **requestor** (the user who creates the RFB and invites bids) and another for the **bidders** (the vendors) to fill out with bid information. An RFB must include a reference process to a vendor list business process, which contains the pool of vendors to whom the RFB will be sent.

Requestor

The user who initiates a Request for Bid (RFB) and invites bids.

Resource

Any individual who can fit a role in a project or company work and whose time and activities can be planned from the Resource Manager. Resources can be from sponsor or partner companies. This is known as a hard booked resource.

If the Administrator has imported the Earned Value-related Assignment Attribute form, resources can also be represented by resource categories, such as Man Hours or Equipment. These resource categories are defined in the Schedule Manager, on the Resources tab of the Activity Properties window for a schedule sheet.

See also “Role”

Resource Allocation

The process of distributing available resources, by role, to a project. Resource allocation places constraints on how much resource capacity an individual project can utilize.

Resource allocation is accomplished through the booking process. See also “Booking Process”

Resource Daily Capacity (RDC)

The total capacity of the resource per day. The resource daily capacity for a given time period equals the RDC times the number of working days in the period.

Resource Manager

The Resource Manager is where users can set up and manage a company's personnel resources. These resources are always maintained at the company level, to be distributed among the company's projects.

The Resource Manager classifies job functions into **roles** that can then be allocated to projects. These roles are used to define billable rates, which are used in budgeting, and can also be used in planning for resource demands across projects. Roles are associated with personnel **resources**—the people who can perform these roles in a project. The Resource Manager is where users assign personnel to roles and projects.

The Resource Manager manages time sheets, and also hard and soft resource bookings using a calendar that shows what projects a resource has been booked for, as well as the resource's availability.

Role

Roles are job types or functions that are necessary to carry out a project's tasks. Roles usually include billable rates and the currency in which the rates should be paid. Roles are associated with personnel **resources**—the people who can perform these roles in a project. See also “Resource”

Run Time

When a report is run. Also, the duration of a project, during which time users use the business processes that were created in uDesigner for the project.

S Step

An S Step is a step that is created by a **link in a workflow** that automatically creates a new business process record after the form reaches a specific step. The new record will contain an exact duplicate of the information in the original record—all the information that was contained in that transaction, including forms, attachments, and comments. The user who owns the original BP record becomes the owner of the auto-created record. After being created, the new BP is sent automatically to the next step in the workflow.

In addition to creating a new record, you can direct the original BP record to automatically populate the upper form and detail form information on the new BP record.

An S Step is visible in the workflow, denoted by an icon in the link.

Compare to “I Step.”

Salvage Value

The residual value of an asset; the value of an asset after the depreciation period. This can be zero, or a value at which the asset can be sold.

Schedule Manager

The Schedule Manager is where users can create and manage schedules at the project/shell level. They can create a schedule sheet that is customized to a project's or shell's needs. Once these sheets are created, users can then use them to create project/shell activities and tasks, assign resources to tasks, create relationships between activities, track schedule progress and variables, and calculate the schedule's critical path.

Schedule of Values (SOV)

An SOV is a way to assemble information from contract, change order, and invoice/payment application business processes into a single sheet. This SOV sheet streamlines the process of invoicing for completed phases of a project/shell.

The Schedule of Values is a detailed statement furnished by a construction contractor, builder, or others, outlining the portions of the contract sum. It allocates values for the various parts of the work and is also used as the basis for submitting and reviewing progress payments.

An SOV works in conjunction with commit types of business processes, such as a purchase order. Commit-types of business processes can be designed to automatically create an SOV sheet when they reach a designated step in a workflow.

The following lists the types of SOV sheets:

- ▶ **A General SOV.**
A General SOV gathers information from any contract, change order, or invoice/payment application BP into an SOV sheet.
- ▶ **A Payment SOV.**
An SOV for Payment Applications allows users to enter values directly onto the SOV sheet. Unifier then automatically adds these values to the payment application sheet.
- ▶ **A Summary Payment Application SOV.**
An SOV for Summary payment Applications shows structured view of the SOV lines. Allows user to enter the values directly onto the SOV sheet. The system then automatically adds these values to the payment application sheet.

Schedule Performance Index

A measure of schedule efficiency on a project. It is the ratio of earned value (EV) to planned value (PV), or EV divided by PV.

A Schedule Performance Index equal to or greater than one indicates a favorable condition; a value of less than one indicates an unfavorable condition.

Schedule Sheet

The schedule sheet shows the schedule of activities in a project. It also shows resource assignments. It is used to track progress of activities over the lifetime of the project. Multiple schedule sheets can exist within a project, but only one master schedule sheet can be created in a project.

Schedule Variance

As work is performed, it is “earned” on the same basis as it was planned, in dollars or other quantifiable units, such as labor hours. The planned value, when compared with the earned value, measures the dollar volume of work planned vs. the equivalent dollar volume of work accomplished. Any difference is called a schedule variance.

Schema

The flow of business process steps and the forms the users will use at each step.

Scope Management

Scope Management is a feature of the Schedule Manager that can be used for those projects that can “self-manage” themselves. Scope Management creates project deliverables, assigns resources to the deliverables, and drives the coordinated completion of the deliverables. It initiates the activities that produce the deliverables based on fixed durations and the completion of dependencies; routes the activities to the responsible person or group; monitors their completion; and updates the activity's status automatically.

Self-Service Portal

Log-in accessible to company user that allows them to submit request, track submitted requests, and communicate with the call center.

Sequence Policy

A sequence policy determines how the record numbers for each BP record are ordered. The record number is displayed on the form and in the business process log.

For a company, record numbering starts with this number on the first record of the first project and is sequential on each record after that, no matter what project a BP record is created in.

For a project, record numbering starts over in each new project, and is sequential within the project.

Service Providers

Partner companies whose users perform specific duties for the sponsoring company, both within and outside of a project.

Shell

A shell is a “container” in which users can organize entities, such as projects or facilities. This shell is where users can organize business information in one place to make managing it easy. A shell can include the functions and features necessary to manage the information in that shell, such as a Schedule Manager, a Document Manager, and a Cost Manager.

Standard "projects" work in a similar manner. The difference is that a shell is not required to function like a time-based project. A shell can encompass a static entity, such as a university campus, where maintenance activities are on-going. An example of such a shell could encompass a college campus to track building maintenance and new additions. You could include a Space Manager for improvements and remodeling, a Document Manager for all the documents and drawings necessary for new additions, and a Generic Cost Manager for costing functions.

Shells can be arranged in hierarchies to represent a company's physical or organizational structure, such as:

State

City

Property

Building

Shell Dashboard

A dashboard that is accessible at the shell level and can be used to view data within a particular shell hierarchy. There are several types of shell dashboard, including My Dashboard and Shell Instance Dashboard.

Shell Instance

See “Shell Type”

Shell Instance Dashboard

Dashboard created by an Administrator at a shell instance level. These dashboards are created in either a shell instance or a shell template. These dashboards are shell specific and not user specific. End users cannot modify these dashboards. This differs from My Dashboard in that it is a shell view of the shell for all users to use, and My Dashboard is a personalized view for a specific user, and displays the information that the user wants to see. The shell instance dashboard is a general view of specific shell data, and is not specific to any one user view of data. Administrators can create multiple shell instance dashboards per shell instance.

Shell Manager

The Shell Manager is where uDesigner users create the shell types that will be used in Unifier. In Unifier, administrators group shells into hierarchies, create shell “instances,” and specify what functions and features will be included in the shell, such as a cost manager (standard or generic), Document Manager, Schedule Manager, and so on.

See also “Shell”

Shell Type

Shells are defined by type. From this type, users can create copies, called instances. For example, a shell type could be “Country,” and instances of this type could be “Germany,” “India,” and “China.” These instances would be linked to the Country shell.

See also “Shell”

Simple BP

Business process that consists of an upper form only (like a line-item BP without the line items). It is a way to add company or project information that does not require line items.

Snapshot

The snapshot feature of the system takes a working “picture” of the schedule sheet, asset sheet, or planning sheet at any point in time. You can use a snapshot on these sheets to drill down into the process to expose specific activities or milestones, plans or planning phases, for particular attention. On an asset sheet, a snapshot can show the progress of an asset and its depreciation during any specific time range.

A snapshot can also be used to make working “versions” of a business process that you can use as an audit trail of the changes you have made to the process. This use of the snapshot feature makes the ongoing evolution of a business process design easier to track and control. As a business process evolves, you might need to return to a prior version of it to re-design some elements of the forms or the workflow(s). If this is the case, you can restore to uDesigner any one of the snapshots you have taken and proceed with the design.

SOV

See “Schedule of Values (SOV)”

Space

A space is an entity—such as a cubicle, office, or conference room—that resides on a level in the Space Manager.

See also “Level”

Standard Project

As of release 9.1, the concept of a project in Unifier was superseded by a new functionality called shells. However, you can still create standard projects if they are more appropriate to your business need.

A standard project is a “container” that represents a scope of work that is time-based. A standard project contains business processes, the Standard Cost Manager (CBS cost and funding data) a Document Manager, a Schedule Manager, a Resource Manager, and reports. It can also contain any configurable managers that have been designed for your company. Standard projects work in a similar manner to shells. The difference is that they cannot be part of a hierarchy, and they are time-based (where shells are not).

See also Shell.

Start to Finish

Denotes that a task cannot end until another begins.

Start to Start

Denotes that a task cannot begin until another begins.

Status

Status indicates the position a record, line item, or asset is in at any point in the business process, such as “approved,” “pending,” or “closed.”

Each business process produces at least one, and sometimes many, transaction records during its workflow. At each transaction, the user must apply a status to the record. The status is what drives the workflow from one step to the next.

A line item status is distinct from a record status, and unlike a record status, it is not a visible part of a workflow; it is part of the form that moves through the workflow.

Asset statuses differ from other statuses. Instead of impacting the disposition of a business process, or line item, an asset status controls which assets are displayed on an Asset class sheet.

Statuses are created in uDesigner and accompany the business process when it is imported into Unifier.

Straight Line

A method of dividing lease payments over a specific period of time. Straight line method assumes that incoming cash flow is in the form of fixed lease payments over the term of the lease. These payments are totaled and divided by the lease term to arrive at the monthly income or expense. This results in an equal impact on the income statement in each reporting period, irrespective of the fact that cash flows differ.

String Formula

A composite field that combines multiple data elements, normally used for building fund code segments. String formulas involve combining values from text box data elements and specifying a string-type pull-down; for example, designing a field called “Project Identifier” using a formula that includes Project, Record No., and location.

String formulas can be defined only for text box and text area data elements.

Summary Line Items

Cost-type and line item-type BPs support summary line items, which group multiple line items together. Only the summary will appear on the BP form. The individual line items appear on the line item window (the detail form), and can be rolled up to other elements, such as the cost sheet, as needed.

Summary Payment Applications

The Summary Payment Applications SOV allows users to allocate cost to line items based on the line item type (Lump Sum or Unit Cost).

Use the Summary Payment Applications SOV type in association with Commit and Spends Business Processes (BPs) that are designed for Summary payment applications SOV type.

Note: The Summary Payment Applications sub-node will be available under the Schedule of Values node only if a Base Commits, or Change Commits, of SOV type Summary Payment Applications is deployed in uDesigner.

System Administrator

System Administrators (or Site Administrators) are responsible for the end-to-end administration of the application. They are the only administrators who have permission to perform certain tasks (unless they grant these permissions to others), which include creating sponsor companies and partner/member companies, loading modules, loading reports, adding the first user(s) to a company, and adding a company administrator.

Tasks (Tasks Log)

When a BP is sent to the next step in its workflow, it becomes a task for the recipient. The recipient is notified by email that someone has sent a BP record for review or other action, and the task also appears on the BP tasks log.

Terminal Status

A terminal status denotes the end of a business process, usually on a workflow. A terminal status has a significant impact on the business processes in that it can be made to trigger an automatic action in the system.

After any BP reaches a terminal status, users can copy it to create another BP of the same type.

A terminal status on a **change commit BP** can update SOV sheet and SOV line items. If you use this feature, users will be able to access the SOV directly from the change commit BP form. On change commit BPs linked to a general spends SOV, a terminal status is not necessary for updates; it is necessary, however, on a change commit linked to a payment application BP.

A terminal status on a **base commit BP** can create an SOV sheet and SOV line items. If you use this feature, users will be able to access the SOV directly from the base commit BP form. On base commit BPs linked to a general spends SOV, a terminal status is not necessary for updates; it is necessary, however, on a base commit linked to a payment application BP.

A terminal status on a **commit or spends BP** can automate project fund consumption or appropriation. It can also create an SOV sheet. If you use this feature, users will be able to access the SOV directly from the commit or spends BP form.

After a **cost BP** reaches a terminal status, users can directly view funding transaction details from the cost BP.

After a **Payment Applications BP** reaches terminal status, users can directly accept line item history from the BP record.

A terminal status on a **resource booking BP** can assign (hard book) a resource and update the booking sheet.

On **timesheet BPs**, a terminal status can roll up time and money to the master timesheet, as well as the project cost sheet.

Text Type BP

A business process that is typically a text comment in the lower portion of the form. Examples of text BPs include RFIs (Request for Information) and action items, which track issue resolution. Text BPs can be used for any text-based collaboration.

Tracking Gantt

A tracking Gantt chart compares dates on activities.

Transient Record

A record that has not yet completed the workflow; used specifically in the Funding Manager to allow funding of “in process” records.

In Alphabetical Order U-Z

uLink

uLink is a Java application that uses Web Services requests to integrate information between other enterprise applications and Unifier.

Unifier Mobile

The Unifier Mobile application lets users download and view company-level user defined reports, including crosstab, tabular, and summary reports, on a mobile device.

Upper Form

An upper form is the upper portion of a business process form. The upper form contains the basic information that the form is managing, such as the name of a record and its description, who created the record and when, and so on. It also contains general data entry, informational, or reference fields for the business process form.

See also "Detail Form"

User Mode

User mode is the collaboration mode project users work in when creating and sending BPs, or using functions such as the cost manager, schedule manager, or the document management system.

Vendor Master

A company-level business process that maintains a master list of all vendors or suppliers that a company or project works with. RFBs refer to this master list during the bid process. The master vendor list can be filtered for specific projects to contain a sub-set of the list.

View Form

The View form is the read-only version of a business process form that appears when the recipient first opens the form. The fields cannot be edited. A view form may also be used when the designer does not want the user to be able to change the data on the form. Business process forms can only be printed from a view form.

See also "Action Form"

Work Breakdown Structure (WBS)/CBS Code

CBS codes are standard in the construction industry for tracking project/shell costs. They are used in project management to break down a project into manageable pieces that can be more effectively estimated and monitored. These codes describe a cost item on a cost sheet and are typically composed of segments that can precisely describe the cost item at one or multiple levels, from a general level down to any number of specific levels. Each segment of the code is a cost code data definition in uDesigner.

See also "Cost Codes"

Workflow

Workflows specify how a business process should proceed, from start to finish. They illustrate each step in the business process and govern the behavior of each step. Workflows also include the movement of documents around the organization for purposes including sign-off, evaluation, or performing activities in a process.

Most business processes will include a workflow or workflows; however, some business processes have a single purpose of storing data. They are often data entry forms designed to enter information directly into the system (for example, vendor lists). These business processes are called non-workflow BPs.

Worksheet

A worksheet reflects a cost sheet, but can be altered for specific purposes, such as manual data entry, or to conceal particular information from non-company personnel. They can also perform complex cost calculations that can, in turn, roll up to the cost sheet.

For example, you might have an independent estimator who is developing an estimate for the project. The estimator should not see information about the current project budget. For this case, you could create a worksheet that displays only the CBS codes and an “estimate” column where the estimator can enter values directly into the worksheet. That data would then roll up to the project cost sheet.

Work Package

A work package is a group of cost sheet rows that are a subset of the project cost sheet. It is the lowest-level deliverable that can be broken down into distinct activities. Work packages provide insight into the budget without providing full access to the details of the project cost sheet.

Yet to Buy (YTB)

Yet to Buy is a data source on a cost sheet that represents the budget yet to be spent on each CBS code. It is useful for users in forecasting their anticipated commits. The system never allows a negative value in this data source.