Oracle® TimesTen In-Memory Database Kubernetes Operator User's Guide





Oracle TimesTen In-Memory Database Kubernetes Operator User's Guide, Release 18.1

G13590-01

Copyright © 2020, 2024, Oracle and/or its affiliates.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software, software documentation, data (as defined in the Federal Acquisition Regulation), or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software," "commercial computer software documentation," or "limited rights data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle®, Java, MySQL and NetSuite are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Inside are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Epyc, and the AMD logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

Contents

What's New

New Features in Release 22.1.1.19.0	XİV
New features in Release 22.1.1.9.0	xiv
New features in Release 22.1.1.3.0	XV
New features in Release 22.1.1.1.0	Χ\
Overview of the Oracle TimesTen Kubernetes Operator	
Overview of Containers and Kubernetes	1-1
Custom Resource Definition	1-2
Kubernetes Operator	1-2
About the TimesTen Kubernetes Operator	1-2
About TimesTenClassic and TimesTenScaleout Objects	1-3
About Provisioning Active Standby Pairs	1-4
About Deploying a TimesTenClassic Object	1-5
About Objects Created by the TimesTen Operator	1-5
StatefulSet	1-6
Service	1-7
Secret	1-7
Pods	1-7
Events	1-7
About the TimesTen Containers and the TimesTen Agent	1-7
Simple Deployment	1-8
About Deploying a TimesTen Scaleout Grid and Database	1-8
StatefulSets	1-9
Services	1-9
Secret	1-10
Persistent Volume Claims and Pods	1-10
Password-less ssh	1-10
	1-10



2 Set Up the Environment

	Prerequisites	2-1
	About TimesTen Container Images	2-2
	Option 1: Use the Official TimesTen Container Images	2-2
	Accept the Oracle TimesTen License Agreement	2-3
	Obtain the TimesTen Operator Manifest Files from the Official TimesTen Image	2-4
	Option 2: Build the TimesTen Container Image	2-6
	Unpack the TimesTen and the TimesTen Operator Distributions	2-6
	Copy the TimesTen Distribution	2-9
	Choose How to Build	2-9
	Option 2a: Build with Defaults	2-10
	Option 2b: Build with Customizations	2-11
	About Deploying the TimesTen Operator	2-13
	Create the Service Account and the TimesTen Custom Resource Definitions (CRDs)	2-14
	About Readiness and Liveness Probes	2-15
	Customize the TimesTen Operator	2-16
	Verify the TimesTen Operator is Running	2-19
3	Use Configuration Metadata	
	Overview of Configuration Metadata and Kubernetes Facilities	3-1
	List of Configuration Metadata	3-1
	About Configuration Metadata Details	3-3
	adminUser	3-3
	cachegroups.sql	3-3
	cacheUser	3-4
	csWallet	3-5
	db.ini	3-5
	epilog.sql	3-6
	replicationWallet	3-7
	schema.sql	3-7
	sqlnet.ora	3-7
	testUser	3-7
	tnsnames.ora	3-8
	*.connect	3-8
	*.csconnect	3-9
	Populate the /ttconfig Directory	3-9
	Using ConfigMaps and Secrets	3-9
	Example Using One ConfigMap	3-10
	Example Using One ConfigMap and One Secret	3-13
	Example Using One ConfigMap for a TimesTenScaleout Object	3-16



	Using an init container	3-18
	Additional Configuration Options	3-20
	Persistent Storage	3-20
	Additional Resource Specifications	3-22
	About Readiness Probes for TimesTen Containers	3-23
	About /tmp/active Readiness Probes	3-24
	About /tmp/readiness Readiness Probes	3-24
4	Specify CPU and Memory Requests and Limits	
	About Resource Requests and Limits	4-1
	About TimesTen Containerized Deployments	4-3
	About Specifying Requests and Limits for TimesTen Containers	4-4
	Approach 1: Use Specific Datum for Requests and Limits	4-5
	Approach 2: Use Templates for Requests and Limits	4-8
	About Specifying Requests and Limits to Kubernetes	4-10
	About Verifying databaseMemorySize	4-10
	About Runtime Memory Monitoring	4-11
5	Deploy TimesTen Classic Databases	
	About the Deployment Process	5-1
	Define and Create a TimesTenClassic Object	5-2
	Monitor Progress of an Active Standby Pair Deployment	5-3
	Monitor the State of a TimesTenClassic Object	5-3
	Verify Underlying Objects Exist	5-8
	Verify Connection to Active Database	5-8
6	Deploy TimesTen Scaleout Databases	
	About Deploying a Grid	6-1
	About Planning a Grid	6-2
	About Configuring a Grid	6-2
	About Provisioning a Grid	6-3
	About ssh	6-4
	About Creating a Grid	6-4
	Deploy a Grid	6-5
	Create Configuration Metadata and a Kubernetes ConfigMap for a Grid	6-6
	Define and Deploy a TimesTenScaleout Object	6-8
	Monitor the High Level State of a TimesTenScaleout Object	6-10
	Verify Underlying Objects	6-12
	Connect to the Database	6-15



7	Use Helm to Deploy the TimesTen Kubernetes Operator and
	TimesTenClassic Objects

7-2 7-3 7-4 7-4 7-5 7-6 7-9
7-3 7-4 7-5 7-6 7-9
7-4 7-2 7-6 7-9
7-4 7-5 7-6 7-9
7-6 7-6
7-6 7-9
7-9
7-10
7-17
7-18
7-20
7-24
7-31
7-36
de 7-38
7-39
7-39
7-41
7-42
8-1
8-3
9-1
9-2
9-2
9-2
9-2
9-2
9-2



ierminai	9-2
Unknown	9-3
UpgradeFailed	9-3
About Monitoring the Health of an Active Standby Pair of Databases	9-3
ActiveDown	9-3
ActiveTakeover	9-2
BothDown	9-4
ConfiguringActive	9-2
Failed	9-2
Initializing	9-4
ManualInterventionRequired	9-5
Normal	9-5
Reexamine	9-5
StandbyCatchup	9-5
StandbyDown	9-5
StandbyStarting	9-5
WaitingForActive	9-6
About the BothDown State	9-6
About the ManualInterventionRequired State	9-7
About Bringing Up One Database	9-9
Verify Conditions Are Met for the Database	9-9
Set the reexamine Value	9-11
Suspend Management of a TimesTenClassic Object	9-16
About Suspending Management	9-16
Suspend Management	9-17
Locate the Operator	9-18
Manage the TimesTen Databases	9-19
Manually Invoke TimesTen Utilities	9-19
Modify TimesTen Connection Attributes	9-20
Manually Edit the db.ini File	9-20
Modify First Connection Attributes	9-22
Modify General Connection Attributes	9-24
Revert to Manual Control	9-27
Delete an Active Standby Pair of TimesTen Databases	9-29
Manage TimesTen Scaleout	
About Managing TimesTen Scaleout	10-1
About Single Data Instance Failure	10-2
About Management Instance Failure	10-2
About the waiting for seed State	10-2



10

	About Failure of All Data Instances	10-3
	About High Level States	10-3
	DatabaseDown	10-4
	DatabaseImpeded	10-4
	DatabasePartial	10-4
	DatabaseRestarting	10-4
	DatabaseRestartRequired	10-4
	Failed	10-4
	Initializing	10-4
	ManualInterventionRequired	10-4
	Normal	10-5
	Reexamine	10-5
	Unmanaged	10-5
	About Management States	10-5
	ActiveAgentUp	10-6
	ActiveDaemonUp	10-6
	ActiveDown	10-6
	Error	10-6
	Normal	10-6
	Unknown	10-6
	About Database and Element States	10-6
	About the ManualInterventionRequired State	10-7
	About Suspending Management	10-7
	Simulate Single Data Instance Failure	10-8
	Simulate Management Instance Failure	10-9
	Simulate Replica Set Failure with Restart	10-11
	Simulate Replica Set Failure with Manual	10-13
	Suspend Management	10-15
	Set reexamine Datum	10-17
11	Expose TimesTen Metrics with the TimesTen Kubernetes Operator	
	Overview of TimesTen Metrics	11-1
	Overview of the TimesTen Kubernetes Operator and the TimesTen Exporter	11-2
	About the Prometheus Operator	11-2
	About Exposing TimesTen Metrics	11-4
	About Using http or https for TimesTen Metrics	11-5
	About Transport Layer Security (mutual TLS) Certificates for TimesTen Metrics	11-6
	About Creating PodMonitor Objects	11-7
	About the TimesTen Metrics Service	11-8
	About Choosing to Expose TimesTen Metrics	11-8



Expose TimesTen Metrics Automatically	11-9
Expose Metrics from the TimesTen Kubernetes Opera	ator
About Exposing Metrics from the TimesTen Kubernetes Operator	12-1
About Using http or https	12-3
About Transport Layer Security (mutual TLS) Certificates	12-3
About Creating ServiceMonitor Objects	12-4
About the TimesTen Kubernetes Operator's Metrics Service	12-4
About TimesTen Operator Metrics	12-5
Demonstrate How to Expose TimesTen Kubernetes Operator Metrics	12-5
Work with TimesTen Cache	
About Using TimesTen Cache	13-1
Use Encryption for Data Transmission	
Create TLS Certificates for Replication and Client/Server	14-1
Configure TLS for Replication	14-3
Create Metadata Files and Kubernetes Facilities	14-3
Create a Kubernetes Secret	14-4
Create a ConfigMap	14-5
Create a TimesTenClassic Object	14-6
Monitor Deployment of a TimesTenClassic Object	14-8
Verify TLS Is Being Used for Replication	14-9
Configure TLS for Client/Server	14-11
Configuration Requirements for the Server	14-11
Overview of Metadata Files and Kubernetes Facilities	14-11
Create a Kubernetes Secret for the csWallet Metadata File	14-12
Create a ConfigMap for the Server-Side Attributes	14-13
Create a TimesTenClassic Object	14-15
Monitor Deployment of the TimesTenClassic Object	14-16
Configuration Requirements for the Client	14-17
Copy a Client Wallet	14-18
Configure Client-Side Attributes	14-18
Handle Failover and Recovery in TimesTen Classic	
About Handling Failover and Recovery	15-1
Illustrate the Failover and Recovery Process	15-1



16 Perform Upgrades

About New TimesTen Container Images	16-1
Upgrade the Operator	16-3
About Upgrading TimesTen Classic	16-6
Perform an Automated Upgrade	16-7
Modify a TimesTenClassic Object: Automated Upgrade	16-8
Monitor an Automated Upgrade	16-11
Perform a Manual Upgrade	16-15
Modify a TimesTenClassic Object: Manual Upgrade	16-16
Upgrade the Standby Database	16-19
Fail Over	16-23
Verify the Active Standby Pair of Databases Are Upgraded	16-28
About Upgrading Direct Mode Applications	16-30
About Failures During an Upgrade	16-30
The TimesTen Kubernetes Operator Object Types	
Overview of the TimesTen Kubernetes Operator Object Types	17-1
About the TimesTenClassic Object Type	17-1
TimesTenClassic	17-2
TimesTenClassicSpec	17-2
TimesTenClassicSpecSpec	17-3
TimesTenClassicSpecSpecPrometheus	17-17
TimesTenClassicStatus	17-19
About the TimesTenScaleout Object Type	17-20
TimesTen Scaleout	17-20
TimesTenScaleoutSpec	17-21
TimesTenScaleoutSpecSpec	17-22
TimesTenScaleoutSpecSpecPrometheus	17-33
TimesTenScaleoutStatus	17-35
Helm Charts for the TimesTen Kubernetes Operator	
Tienn Charts for the Times fell Rubernetes Operator	
The ttoperator Chart	18-1



20 TimesTen Kubernetes Operator Environment Variables

21 Dockerfile ARGs

Active Standby Pair Example	
Before You Begin	A-1
Create a ConfigMap Object	A-1
Create a TimesTenClassic Object	A-3
Monitor Deployment	A-4
Verify Existence of Underlying Objects	A-9
Verify Connection to the Active TimesTen Database	A-10
Recover from Failure	A-10
Clean Up	A-11
TimesTen Cache in TimesTen Classic Example	
Set Up the Oracle Database to Cache Data	B-1
Create the Oracle Database Users	B-1
Grant Privileges to the Cache Administration User	B-2
Create the Oracle Database Tables to Be Cached	B-4
Create Metadata Files and a Kubernetes Facility	B-5
Create a TimesTenClassic Object	B-10
Monitor Deployment of a TimesTenClassic Object	B-11
Verify TimesTen Cache Configuration	B-14
Perform Operations On Cache Group Tables	B-15
Perform Operations on the oratt.readtab Table	B-15
Perform Operations on the oratt.writetab Table	B-16
Clean Up Cache Metadata on the Oracle Database	B-18
TimesTen Cache in TimesTen Scaleout Example	
Set Up the Oracle Database to Cache Data	C-1
Create the Oracle Database Users	C-1
Grant Privileges to the Cache Administration User	C-3
Create the Oracle Database Table to Be Cached	C-5
Create Metadata Files and a Kubernetes Facility	C-7
Create a TimesTenScaleout Object	C-12



C-15 C-17 C-19
C-19
xposing
D-1
D-2
D-3
D-3 D-4
-



About This Content

This document covers TimesTen support for the TimesTen Kubernetes Operator.

Audience

This document is intended for anyone who wants to use the TimesTen Kubernetes Operator in a Kubernetes environment.

Kubernetes is a portable, extensible, open-source platform for managing containerized workloads and services, that facilitates both declarative configuration and automation. The Oracle TimesTen Kubernetes Operator (TimesTen Operator) is a Kubernetes Operator that provides the ability to do the following:

- Create and deploy highly available replicated pairs of TimesTen Classic databases to a
 Kubernetes cluster with minimal effort. It also provides the ability to automate failure
 detection and recovery.
- Create and deploy TimesTen Scaleout grids and their associated databases to a Kubernetes cluster with minimal effort.

Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc.

Access to Oracle Support

Oracle customers that have purchased support have access to electronic support through My Oracle Support. For information, visit http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info or visit http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs if you are hearing impaired.

Conventions

The following text conventions are used in this document.

Convention	Meaning
boldface	Boldface type indicates graphical user interface elements associated with an action, or terms defined in text or the glossary.
italic	Italic type indicates book titles, emphasis, or placeholder variables for which you supply particular values.
monospace	Monospace type indicates commands within a paragraph, URLs, code in examples, text that appears on the screen, or text that you enter.



What's New

This section summarizes the new features of Oracle TimesTen In-Memory Database Release 22.1 that are documented in this guide. It provides links to more information.

New Features in Release 22.1.1.19.0

- The TimesTen Kubernetes Operator (TimesTen Operator) provides TimesTenspecific Helm charts. These charts let you use Helm to install the TimesTen CRDs, TimesTen Operator, and TimesTenClassic objects in your Kubernetes cluster. See Use Helm to Deploy the TimesTen Kubernetes Operator and TimesTenClassic Objects.
- By default, the TimesTen Operator automatically exports and exposes TimesTen metrics to Prometheus. See Expose TimesTen Metrics with the TimesTen Kubernetes Operator.

You can control how TimesTen metrics are exported and exposed by using specific datum in your TimesTenClassic and TimesTenScaleout object YAML manifest files. See About Exposing TimesTen Metrics and TimesTenClassicSpecSpecPrometheus and TimesTenScaleoutSpecSpecPrometheus.

 The TimesTen Operator automatically exposes metrics about its own functionality as well as the status of TimesTenClassic and TimesTenScaleout objects that it manages to Prometheus. See Expose Metrics from the TimesTen Kubernetes Operator.

You can control how these metrics are exposed by unsetting or setting TimesTen Operator environment variables located in the operator.yaml YAML manifest file of your TimesTen Operator deployment. See About Exposing Metrics from the TimesTen Kubernetes Operator and TimesTen Kubernetes Operator Environment Variables.

- The TimesTen Operator provides readiness and liveness probes so that Kubernetes can determine the health of the TimesTen Operator. See About Readiness and Liveness Probes.
- The TimesTen Operator creates and manages readiness probes for TimesTen containers. See About Readiness Probes for TimesTen Containers.

New features in Release 22.1.1.9.0

• The TimesTen Operator monitors and manages TimesTen Scaleout objects that are deployed in your Kubernetes cluster. It also detects, repairs, and recovers from failures in your grid and associated database. See Manage TimesTen Scaleout.



- The Operator supports TimesTen Cache in TimesTen Scaleout. See Work with TimesTen Cache. For a complete example, see TimesTen Cache in TimesTen Scaleout Example.
- It is essential to specify memory requests and limits to Kubernetes. TimesTen
 recommends that CPU requests and limits be specified as well. See Specify CPU and
 Memory Requests and Limits. To support this functionality, there are new datum added to
 the .spec.ttspec fields of the TimesTenClassic and TimesTenScaleout object custom
 resource definitions. See TimesTenClassicSpecSpec and TimesTenScaleoutSpecSpec.
- TimesTen container images use the Oracle Linux base image. Oracle Java is installed
 into the TimesTen images using JDK script friendly URLs and Dockerfile techniques. For
 details about setting up your environment, see Set Up the Environment. For specific
 information about TimesTen container images, see About TimesTen Container Images.
 For information about Dockerfile ARGS, see Dockerfile ARGS.

New features in Release 22.1.1.3.0

- The TimesTen Operator can deploy TimesTen Scaleout grids and their associated TimesTen databases in your Kubernetes cluster. See Deploy TimesTen Scaleout Databases.
 - The TimesTen Operator supports the TimesTenScaleout object type. This object type provides the syntax you need to deploy a TimesTen Scaleout grid and database. See About the TimesTenScaleout Object Type.
- In previous releases, the TimesTen Operator required the creation of two container images, one for the Operator and one for TimesTen. In this release, one container image is used for both the Operator and TimesTen. You can create this container image or pull it from the Oracle Container Registry at container-registry.oracle.com. See Set Up the Environment.
- When using the TimesTen Operator, the name of the Linux user that is created in the container image is timesten with a numeric UID of 3429. The name of the Linux group that is created in the container image is timesten with a GID of 3429. The timesten user is the user who runs TimesTen and the timesten group is the TimesTen users group. You can override these defaults. This lets you tailor attributes of the image to meet your requirements. See Option 2b: Build with Customizations and Dockerfile ARGs.
- The TimesTen Operator supports the TimesTen Prometheus Exporter. You can configure
 your TimesTenClassic and your TimesTenScaleout objects to use the Exporter. The
 Exporter can then collect metrics from the TimesTen databases that are running in your
 Kubernetes cluster, and expose these metrics to Prometheus. See Create Your Own
 Oracle Wallet, Certificates, and Secrets for Exposing TimesTen Metrics.

The TimesTen Operator provides the prometheus object type as part of the TimesTenClassic and TimesTenScaleout object type definitions. Use the prometheus object type to configure the Exporter to meet your Prometheus requirements. See TimesTenClassicSpecSpecPrometheus and TimesTenScaleoutSpecSpecPrometheus.

New features in Release 22.1.1.1.0

You can define a readiness probe to tell Kubernetes that a TimesTen (tt) container is ready. See About Readiness Probes for TimesTen Containers.



1

Overview of the Oracle TimesTen Kubernetes Operator

This chapter provides an overview of containers and Kubernetes. It also gives an overview of the TimesTen Kubernetes Operator. It discusses the TimesTenClassic and TimesTenScaleout *Custom Resource Definitions* (CRDs) and the TimesTen Operator. The chapter details the role the TimesTen Operator plays in deploying, managing, and monitoring active standby pairs of TimesTen Classic databases as well as in deploying TimesTen Scaleout grids and their associated databases in your Kubernetes cluster.

Topics:

- Overview of Containers and Kubernetes
- About the TimesTen Kubernetes Operator
- About TimesTenClassic and TimesTenScaleout Objects
- About Provisioning Active Standby Pairs
- About Deploying a TimesTenClassic Object
- About Deploying a TimesTen Scaleout Grid and Database

Overview of Containers and Kubernetes

A container is a lightweight virtual machine, running the Linux operating system. A container usually runs one application that is started from an image. Files that are created and modified are usually not persistent. However, persistent storage is available. Containers are a key component of cloud computing environments.

Kubernetes is a portable, extensible, open-source platform for managing containerized workloads and services, that facilitates both declarative configuration and automation. Kubernetes has the ability to manage the resources of multiple hosts (called *Nodes*) in a cluster, and to run containers as required across these nodes. It can automatically spawn containers to react to various failures. Kubernetes also manages the networking among the containers and to the outside world. Kubernetes is portable across many cloud and on-premises environments.

Key Kubernetes concepts include:

 Pod: One or more containers that share an IP address. For more information on Pods, see:

https://kubernetes.io/docs/concepts/workloads/pods/pod/

• Deployment: A named collection of n identical Pods (where n is the number of Pods). Kubernetes ensures that n identical Pods are running. For more information on Deployments, see:

https://kubernetes.io/docs/concepts/workloads/controllers/deployment/

 PersistentVolume: Storage that can be mounted to a Pod and is persistent beyond the lifetime of Pod. For more information on Persistent Volumes, see: https://kubernetes.io/docs/concepts/storage/persistent-volumes/

 StatefulSet: Similar to a Deployment, but each Pod has an associated PersistentVolume. For more information on StatefulSets, see:

https://kubernetes.io/docs/concepts/workloads/controllers/statefulset/

 Service: A network endpoint for a Deployment or StatefulSet. It defines the set of addresses and ports that should be exposed to applications in the Kubernetes cluster. For more information on a Service, see:

https://kubernetes.io/docs/concepts/services-networking/service/

Kubernetes provides the facilities for the provisioning of Pods and other Kubernetes resources that are required to deploy applications. Once deployed, the objects must be monitored and managed.

Kubernetes does some monitoring and managing of applications, but not all. It does handle problems at the Pod level automatically. For example, if a container fails, Kubernetes restarts it automatically. If an entire Node fails, Kubernetes starts replacement Pods on the other Nodes. However, Kubernetes has no knowledge about problems inside a container. This is not problematic for stateless applications, but for databases (which are stateful), Kubernetes needs help managing what is inside the containers.

This help comes in the form of:

- Custom Resource Definition
- Kubernetes Operator

Custom Resource Definition

A *Custom Resource Definition* (commonly known as a CRD) extends the Kubernetes' object model. It adds a new object type to the Kubernetes cluster, similar to the Pod, the StatefulSet, and the Service object types that it natively supports.

Kubernetes Operator

A *Kubernetes Operator* (also called *Operator*) is the brains behind a CRD. An Operator is an application that performs the functions of a human computer operator. It starts, stops, monitors, and manages other applications.

An Operator runs in one or more Pods, one active and the others idle. The active Operator performs the work. The remaining Operators are idle and remain idle until the active Operator fails. The active Operator manages all objects of a particular type and when combined with a CRD enables you to add custom facilities to Kubernetes.

About the TimesTen Kubernetes Operator

The TimesTen Kubernetes Operator provides the ability for you to deploy both active standby pairs of TimesTen Classic databases as well as TimesTen Scaleout grids and their associated databases in your Kubernetes cluster.

The TimesTen Kubernetes Operator consists of these interrelated components:

 Custom Resource Definitions (CRDs): There are two CRDs. The TimesTenClassic CRD defines an object of type TimesTenClassic to Kubernetes. This



TimesTenClassic object type provides the metadata for deploying active standby pairs of TimesTen Classic databases. The TimesTenScalout CRD defines an object of type TimesTenScaleout to Kubernetes. This TimesTenScaleout object type provides the metadata for deploying TimesTen Scaleout grids and their associated databases.

- TimesTen Operator: There is one TimesTen Operator. The Operator monitors the TimesTenClassic and TimesTenScaleout objects and properly handles both. It deploys, manages, and monitors active standby pairs of TimesTen Classic database. This same Operator deploys TimesTen Scaleout grids and their associated databases.
- TimesTen Agent: There is one TimesTen agent. This agent runs inside each container that runs TimesTen. The TimesTen Operator communicates with these agents both to determine the state of TimesTen insides of the container as well as to create, start, stop, and control TimesTen instances. The agent does not know how to manage TimesTen. It gives information to the Operator and the Operator provides the instructions for the agent. This agent knows how to work with TimesTen Classic and TimesTen Scaleout.

About TimesTenClassic and TimesTenScaleout Objects

The TimesTen Operator distribution provides the file you need to deploy the TimesTenClassic and TimesTenScaleout CRDs in the Kubernetes cluster. Once deployed, Kubernetes understands the TimesTenClassic and TimesTenScaleout object types, just as it understands Pods, Secrets, and Services.

You can define objects of type TimesTenClassic or of type TimesTenScaleout or both. This lets you define the specific attributes for your TimesTen configuration and TimesTen database.

Objects in Kubernetes are named and typed. You can define a TimesTenClassic object named <code>sample</code> and another TimesTenClassic object named <code>sample2</code>. Similarly, you can define a TimesTenScaleout object named <code>sample</code> and another TimesTenScaleout object named <code>sample2</code>. You can have as many of these Kubernetes objects as you want, limited only by the available resources in your Kubernetes cluster.

Objects of different types have different meanings. For example, an object of type TimesTenClassic has a different meaning than an object of type ConfigMap. Therefore, you can define a sample TimesTenClassic object and a sample ConfigMap. The same is true for TimesTenScaleout objects.

Kubernetes supports namespaces. Namespaces split a cluster into multiple independent ones. Each namespace has a completely independent set of names. There can be an object of type a called x in namespace1 and a different object of type a called x in namespace2. For example, you can define an object of type TimesTenClassic called sample in the namespace1 namespace, and a different object of type TimesTenClassic called sample in the namespace2 namespace. The same is true for TimesTenScaleout objects.



CRDs are cluster-scoped, not namespace-scoped.

Kubernetes object definitions are expressed in JSON or YAML. The examples in this book use YAML.



About Provisioning Active Standby Pairs

TimesTen Classic databases almost always run in active standby pairs. Figure 1-1 illustrates an active standby pair replication scheme. There are two databases. One database is the active, and the second database is the standby. Applications update the active database. The standby database is read-only and receives replicated updates from the active database. Only one of the two databases function as the active database at any one time. If the active database fails, the standby database is promoted to be the active. After the failed (active) database is recovered, it becomes the standby database. See Types of Replication Schemes in the *Oracle TimesTen In-Memory Database Replication Guide* for more information on the active standby pair replication scheme.

Application
Transactions

Application Reads on
Hot Standby

Active

Standby

ORACLE
Times Ten IMDB

Checkpoint and
Transaction Log Files

Application Reads on
Hot Standby

Checkpoint and
Transaction Log Files

Figure 1-1 Active standby pair of TimesTen databases

An active standby pair replication scheme is a good fit for Kubernetes. Specifically, consider a pair of Pods, each with persistent storage, that are running an active standby pair of TimesTen databases. If the Pod containing the active database fails, Kubernetes automatically spawns another Pod to take its place, and attaches the appropriate storage to it.

But, since Kubernetes doesn't know anything about TimesTen, it will not automatically perform the necessary operations to cause the standby database on the surviving Pod to become the active database. This is where the TimesTen Operator comes in.

TimesTen provides a CRD that adds the *TimesTenClassic* object type to Kubernetes as well as an Operator for managing TimesTen databases. The Operator automates setup and initial configuration, manages databases and replication, and automates failover and recovery.

When you define a TimesTenClassic object, you can specify the configuration of your TimesTen deployment using Kubernetes facilities. When you create a TimesTenClassic object in a Kubernetes cluster, a pair of Pods are created, each running TimesTen. Each Pod contains a TimesTen instance. Each instance provides one TimesTen database. Database replication, through active standby pairs, is automatically



configured. In short, you can deploy highly available replicated pairs of TimesTen databases and manage them by issuing a small number of commands.

A Kubernetes Operator manages objects of a particular type. TimesTen provides an Operator that manages Kubernetes objects of type TimesTenClassic. In so doing, TimesTen can be deployed, monitored, managed, and controlled in an automated manner with no required human intervention.

About Deploying a TimesTenClassic Object

When you create a TimesTenClassic object in the Kubernetes cluster, the process to create and configure your active standby pair of databases begins. The Operator is invoked and creates several Kubernetes objects that are required to run TimesTen. After the objects are created and linked together, the TimesTen containers run a script to configure and start the TimesTen agent. The Operator communicates with the TimesTen agent that is running in each Pod in order to monitor and control TimesTen. The Operator configures one database as the active database, copies the active database to the standby, and then configures the active standby pair replication scheme. The process is described in detail in these sections:

- About Objects Created by the TimesTen Operator
- About the TimesTen Containers and the TimesTen Agent
- Simple Deployment

About Objects Created by the TimesTen Operator

The Operator creates a number of Kubernetes objects that are required to run TimesTen, including a StatefulSet, a Service, and a Secret. These objects in turn create other objects. All of these objects are linked together by Kubernetes and are associated with the TimesTenClassic object you created. Figure 1-2 shows the objects that are created and how they are linked together.






Figure 1-2 Creating the TimesTenClassic object

The objects that are created are described in the following sections:

- StatefulSet
- Service
- Secret
- Pods
- Events

StatefulSet

The Operator creates a StatefulSet consisting of two Pods to run TimesTen. Each Pod has one or more PersistentVolumes (persistent storage), that are mounted in the TimesTen containers. This is where your TimesTen databases are stored. Applications running in the containers with PersistentVolumes mounted can create files that live beyond the lifetime of the container. (By default, all files that containers create and modify automatically vanish when the container exits. Containers are ephemeral.)

One attribute of a StatefulSet is the number of replicas that can be provisioned. Each TimesTenClassic object has an associated StatefulSet with two replicas. If one Pod fails, Kubernetes automatically creates a new one to replace it, and automatically mounts the appropriate PersistentVolume(s) to it.

For example, for a TimesTenClassic object called <code>sample</code>, the Operator creates a StatefulSet called <code>sample</code>, in the same Kubernetes namespace. The StatefulSet, in turn, create two Pods in the namespace, called <code>sample-0</code> and <code>sample-1</code>.



Service

A Kubernetes Service defines the set of network addresses and ports that should be exposed to applications in the cluster.

The Operator automatically creates a *headless* Service when you create the TimesTenClassic object. It automatically associates this Service with the StatefulSet. This causes Kubernetes to define entries in the Kubernetes cluster's DNS for the Pods in the StatefulSet, and to keep those DNS entries up to date.

A headless Service is used such that the DNS name/address entry for the active database is different than the DNS name/address entry for the standby database. This enables incoming client connections to be routed to the database that is active. For more information on a headless Service, see:

https://kubernetes.io/docs/concepts/services-networking/service/#headless-services/

For a TimesTenClassic object called sample, a headless Service called sample is also created in the same Kubernetes namespace. This results in entries in the cluster's DNS for sample-0.sample.namespace.svc.cluster.local and sample-1.sample.namespace.svc.cluster.local.

Secret

The TimesTen Operator creates a Secret to inject an SSL certificate into the TimesTen containers. This secures the communication between the TimesTen Operator and the TimesTen Agent.

Pods

The StatefulSet creates two pods. Each Pod contains two containers:

- The tt container. This TimesTen container is always present in the Pods. It executes the TimesTen agent and runs TimesTen.
- The daemonlog container: This container copies the contents of the TimesTen ttmesg.log file to stdout, resulting in Kubernetes logging the file. This enables the daemon log of the TimesTen instances to be recorded by the Kubernetes infrastructure.

Events

The Operator creates a Kubernetes event whenever important changes occur.

About the TimesTen Containers and the TimesTen Agent

After the objects are created, the TimesTen containers run a script that configures and starts the TimesTen agent. The Operator communicates with the TimesTen agent running in each Pod, in order to configure, manage, and monitor TimesTen in that Pod. The agent provides an HTTPS endpoint in the Pod that the Operator uses to query and control the tt container in the Pod. If the TimesTen agent fails, the tt container automatically terminates and is respawned by Kubernetes. Figure 1-3 illustrates the two way communication between the Operator and the TimesTen agent.






Figure 1-3 The Operator and the TimesTen agent

The TimesTen agent starts TimesTen and thus runs as the instance administrator user. It has full control over TimesTen.

Simple Deployment

The TimesTen Operator is designed for simple deployment of your active standby pairs of TimesTen Classic databases and for automated failure detection and recovery. For example,

- You decide you want to deploy a new replicated pair of TimesTen databases.
- You decide the attributes of those databases.
- You create the configuration files for those attributes.
- You use the kubectl create command to create a TimesTenClassic object to represent the replicated pair.
- You use the kubectl get and kubectl describe commands to observe the provisioning of the active standby pair.
- Applications that run in other Pods use TimesTen's standard client/server drivers to access TimesTen databases.

You do not have to monitor the TimesTen databases continually, configure replication, perform failover, or re-duplicate a database after failure. The TimesTen Operator performs all these functions and works to keep the databases up and running with minimal effort on your part.

About Deploying a TimesTen Scaleout Grid and Database

When you create a TimesTenScaleout object in the Kubernetes cluster, the process to create and configure the TimesTen Scaleout grid and its associated database begins. Kubernetes informs the TimesTen Operator that a TimesTenScaleout object has been

created. The Operator begins the process of creating several Kubernetes objects that are required to deploy the grid.

Topics:

- StatefulSets
- Services
- Secret
- Persistent Volume Claims and Pods
- Password-less ssh
- Quick Rollout

StatefulSets

The TimesTen Operator creates the following StatefulSets:

- One StatefulSet that provides the management instance for the grid. The underlying Pod for this management instance is also created.
- One StatefulSet that provides one or more ZooKeeper instances. There is one StatefulSet replica for each Zookeeper instance. For example, if there are three ZooKeeper instances, there is one StatefulSet and this one StatefulSet has three replicas.
- One or more additional StatefulSets, the number of which is determined by your K-Safety (k) value. For example, a k value of 2 means that there are two copies of your TimesTen database. One copy of your database resides in data space one, and the second copy in data space two. In the Kubernetes environment, the TimesTen Operator creates k StatefulSets. Using the previous example, if k is set to 2, the Operator creates two StatefulSets. Each of the k StatefulSets provides Pods to implement a single data space in the resultant grid.

The number of replicas for each StatefulSet is determined by the number of replica sets you want in your grid. A replica set contains k elements, where each element in the replica set is an exact copy of the other elements in the replica set. For example, if you want three replica sets in your grid, each StatefulSet has three replicas. Each replica contains a Pod for one data instance. Therefore, in this example, one StatefulSet has three Pods each of which contain one data instance. The second StatefulSet (assuming k=2) also has three replicas and each replica also contains a Pod for one data instance. Therefore, the second StatefulSet has three Pods each of which contain one data instance.

In summary, in a case where k is set to 2 and the number of replica sets is 3, the Operator creates two StatefulSets, each with three replicas. Each StatefulSet provides the Pods to implement a single data space. There are a total of six Pods created for the six data instances.

Services

The TimesTen Operator creates the following headless Services:

 One headless Service that provides DNS names for the Pods that contain the management and data instances. This Service enables client/server access to the Pods using the TimesTen client/server port 6625.



• One headless Service that provides DNS names for the Pods that contain the ZooKeeper instances. This Service enables access to the Zookeeper internal ports 2888 and 3888, as well as the external port 2181.

Secret

The TimesTen Operator creates a Secret to inject an SSL certificate into the TimesTen containers. This secures the communication between the TimesTen Operator and the TimesTen Agent.

Persistent Volume Claims and Pods

The TimesTen Operator creates Persistent Volume Claims (PVCs) for the TimesTen and ZooKeeper Pods. These PVCs cause persistent volumes to be allocated by Kubernetes and attached to the TimesTen and ZooKeeper Pods. See Persistent Storage.

Each Pod that runs a ZooKeeper instance consists of a single container called zookeeper.

Each Pod that runs TimesTen consists of at least two containers:

- tt container: Runs the TimesTen Agent and TimesTen.
- daemonlog container: Writes the TimesTen daemonlog to stdout. This enables the daemon log of the TimesTen instances to be recorded by the Kubernetes infrastructure.

As the tt containers in the TimesTen Pods start, the Operator assembles them into a working grid.

Password-less ssh

A TimesTen Scaleout grid relies on password-less ssh among the instances of the grid. The TimesTen Operator automatically configures password-less ssh among the tt containers in the grid in your Kubernetes environment. There is no intervention that you need to do.

Quick Rollout

The TimesTen Kubernetes Operator provides the functionality for deploying TimesTen Scaleout grids and their associated databases. The TimesTen Operator rolls out the grid quickly and proficiently.

The Operator creates the StatefulSets and Services that are required to deploy the grid. It creates the ZooKeeper Pods. When the TimesTen Agent in the management Pod starts up, the Operator instructs the agent to create a TimesTen instance and grid. The Operator waits for all of the TimesTen agents in all of the Pods to start. Once all of the agents have started, the Operator instructs the agent in the management instance to create the hosts, the installations, and the instances in the grid's model for the data instances in the grid. The DbDef is created as are any direct and client/server connectables. The model is applied and the data instances of the grid are created.



The Operator instructs the management instance to create the database and to create the initial distribution map. The Operator then instructs the TimesTen agent in one data instance to run the TimesTen ttlsql utility to create initial database users and objects.

The grid and databases are created. The TimesTen agent opens the database for connections.

The grid rollout is quick and proficient with little or no intervention from you. Once the grid is rolled out, the TimesTen Operator does not manage the grid or database or perform maintenance operations.

Here is additional information:

- For information about TimesTen Scaleout: See Overview of TimesTen Scaleout in the Oracle TimesTen In-Memory Database Scaleout User's Guide.
- For information about deploying a TimesTen Scaleout grid and database in Kubernetes: See Deploy TimesTen Scaleout Databases in this book.



Set Up the Environment

This chapter describes the process for setting up the TimesTen Kubernetes Operator (TimesTen Operator).

Topics:

- Prerequisites
- About TimesTen Container Images
- Option 1: Use the Official TimesTen Container Images
- Option 2: Build the TimesTen Container Image
- About Deploying the TimesTen Operator
- Create the Service Account and the TimesTen Custom Resource Definitions (CRDs)
- About Readiness and Liveness Probes
- Customize the TimesTen Operator
- Verify the TimesTen Operator is Running

Prerequisites

Review and complete the following prerequisites:

- Ensure you have a working Kubernetes cluster.
 - Your cluster must provide a *StorageClass* that can be used to request Persistent Volumes. You must know the name of this storage class. For example, in OKE, you can use the oci-by storage class. For more information on Storage Classes, see:

https://kubernetes.io/docs/concepts/storage/storage-classes/

- The nodes in your cluster must have their clocks synchronized through NTP, or equivalent.
- Ensure you have a development host to access the Kubernetes cluster. This
 development host must reside outside the Kubernetes cluster, and you must be able to
 access and to control the Kubernetes cluster from this host. On it, you must install:
 - The kubectl command line tool: You use the kubectl command line tool to control and mange the Kubernetes cluster.
 - The docker command line tool: You use the docker command line tool when working with the TimesTen container image. For example, you use the docker command line tool to build the TimesTen container image and to push it to your container registry.

Note:

For a list of supported Kubernetes releases, see the *Oracle TimesTen In-Memory Database Release Notes*.

About TimesTen Container Images

In order to use and deploy the TimesTen Operator and TimesTenClassic and TimesTenScaleout objects in your Kubernetes cluster, a TimesTen container image is required. This container image contains TimesTen and its prerequisites. The image has everything that is needed to run the TimesTen Operator and to run TimesTen containers in the TimesTen Pods created by this TimesTen Operator.

A TimesTen container image uses the Oracle Linux base image. Oracle Java is installed into the TimesTen image using JDK script friendly URLs and Dockerfile techniques.

You have two options for obtaining and then using the TimesTen container image. It is your choice as to which option to use. The options are as follows:

- Option 1: Use a TimesTen container image located on the Oracle Container Registry at https://container-registry.oracle.com. Before using this image, you must accept the Oracle Standard Terms and Restrictions for the image. See Option 1: Use the Official TimesTen Container Images.
- **Option 2**: Build the TimesTen container image: The TimesTen distribution contains the TimesTen Operator distribution. The TimesTen Operator distribution provides a Dockerfile that lets you build a TimesTen container image. See Option 2: Build the TimesTen Container Image.

Option 1: Use the Official TimesTen Container Images

This option uses an official TimesTen container image on the Oracle Container Registry located at https://container-registry.oracle.com. There are two TimesTen repositories located on the Oracle Container Registry called timesten and timesten-repository container images for Oracle TimesTen In-Memory Database. The timesten and timesten-registry called timesten and timesten-registry called timesten and timesten-registry.oracle.com. The timesten repository contains official container images for Oracle TimesTen In-Memory Database Express Edition (TimesTen XE) TimesTen XE.

To view the list of TimesTen container images in these repositories, navigate to the Oracle Container Registry at https://container-registry.oracle.com. In the Search Oracle Container Registry field, enter timesten. Next press Enter. You can then choose either the timesten or the timesten-xe repository. The examples in this chapter and throughout the book use the timesten repository for the TimesTen container images.

The predefined values in this image are as follows. You cannot change these values:

- timesten: The name of the Linux user and the Linux group that is created in the container image. The Linux user is the user who runs TimesTen. The Linux group is the TimesTen users group.
- 3429: The numeric UID and GID of the timesten user and the TimesTen users group.

Let's walk through the tasks to obtain and use a TimesTen container image located in the timesten repository on Oracle Container Registry.

- Accept the Oracle TimesTen License Agreement
- Obtain the TimesTen Operator Manifest Files from the Official TimesTen Image



Accept the Oracle TimesTen License Agreement

You need to complete the steps in this section one time. If you have previously accepted the Oracle TimesTen license agreement and created your Kubernetes Secret, proceed to Obtain the TimesTen Operator Manifest Files from the Official TimesTen Image.

The official TimesTen container images are located on the Oracle Container Registry at https://container-registry.oracle.com/. To use a licensed Oracle software image such as TimesTen, you must log into the Oracle Container Registry web interface and accept the Oracle Standard Terms and Restrictions for the image. After you complete the following steps, you can reference the official TimesTen container image in your YAML manifest files.



There are a list of TimesTen images available in the <code>container-registry.oracle.com/timesten</code> repository. Choose the image you want to use. The examples in this book use various images. An example of a TimesTen container image is <code>container-registry.oracle.com/timesten/timesten:22.1.1.19.0</code>.

- 1. In a web browser, using your Oracle Account, log into the Oracle Container Registry located at https://container-registry.oracle.com/.
- On the Oracle Container Registry page, in the Browse Containers section, click TimesTen.
- 3. On the TimesTen Repositories page, in the Repository column, choose timesten.
- 4. On the Official container images for the Oracle TimesTen In-Memory Database page, to the right of the Quick Reference Description, locate the Select Language drop down list. In the Select Language drop down list, choose your language. Then, review the text before the Continue button and click Continue.
 - The text that is displayed before the **Continue** button is similar to the following: "You must agree to and accept the *Oracle Standard Terms and Restrictions* prior to downloading from the Oracle Container Registry. Please read the license agreement on the following page carefully."
- 5. On the **Oracle Standard Terms and Restrictions** page, review the information on the page, then at the bottom of the page, click **Accept**.
 - The Official container images for the Oracle TimesTen In-Memory Database page displays for a second time. To the right of the Quick Reference Description, look for a green check mark with text similar to the following: "You last accepted the Oracle Standard Terms and Restrictions on 01/08/2023 at 01:28 PM Coordinated Universal Time (UTC)."
- 6. On your development host, use the docker login command to authenticate against the Oracle Container Registry, using the same Oracle Account you used to log into the Oracle Container Registry web interface.

```
docker login container-registry.oracle.com
```

You are prompted to enter your Oracle Account and password.



The text is similar to the following:

```
Username (oracleuser@oracle.com):
Password:
WARNING! Your password will be stored unencrypted in /home/
oracleuser/.docker/config.json.
Configure a credential helper to remove this warning. See
https://docs.docker.com/engine/reference/commandline/login/
#credentials-store
Login Succeeded
```

7. Create the image pull secret for container-registry.oracle.com.

```
kubectl create secret generic sekret \
--from-file=.dockerconfigjson=$HOME/.docker/config.json \
--type=kubernetes.io/dockerconfigjson
```

Save the name of the image pull secret. You need it later when deploying your TimesTenClassic or TimesTenScaleout objects. See Define and Create a TimesTenClassic Object and Define and Deploy a TimesTenScaleout Object.

For more information about creating a Kubernetes Secret, see Pulling Images from Registry during Deployment.

You have successfully logged into the Oracle Container Registry and accepted the *Oracle Standard Terms and Conditions* for the official TimesTen container image. You can now reference the TimesTen container image in your YAML manifest files. Proceed to Obtain the TimesTen Operator Manifest Files from the Official TimesTen Image.

Obtain the TimesTen Operator Manifest Files from the Official TimesTen Image

The TimesTen Operator manifest files are included within the official TimesTen container image. In this example, the official TimesTen container image is located in the timesten repository on the Oracle Container Registry.

For information about how to navigate to the official TimesTen container images location, see Option 1: Use the Official TimesTen Container Images.

The examples in this section use the container-registry.oracle.com/timesten/timesten:22.1.1.19.0 image.

Let's walk through the steps to obtain the TimesTen Operator manifest files located within the container-registry.oracle.com/timesten/timesten:22.1.1.19.0 container image.



 On your development host, from the directory of your choice, create the subdirectories for the TimesTen Operator files. This example creates the kube_files and kube_files/ deploy directories.

```
mkdir -p kube_files
cd kube_files
mkdir -p deploy
```

2. Create a new container from the container-registry.oracle.com/timesten/timesten:22.1.1.19.0 image, supplying a name for the new container. In this example, the name of the container is ttoper.

```
docker create --name ttoper container-registry.oracle.com/timesten/
timesten:22.1.1.19.0
```

The output is similar to the following.

```
Unable to find image 'container-registry.oracle.com/timesten/
timesten:22.1.1.19.0' locally
Trying to pull repository container-registry.oracle.com/timesten/
timesten:22.1.1.19.0 ...
20221215: Pulling from container-registry.oracle.com/timesten/
timesten:22.1.1.19.0
...
Digest:
sha256:bb58e32d2e08a66c55fb09afd8958feb91300134fc7a019bcb39a241f48fd995
Status: Downloaded newer image for container-registry.oracle.com/timesten/
timesten:22.1.1.19.0
d03a6e534e8bcce435b86795e8b3082487e5f18af64a522ebfbabff3baec321a
```

3. Copy the TimesTen Operator files from the ttoper container to the recently created kube_files/deploy. In addition, copy the helm directory from the ttoper container.

```
docker cp ttoper:/timesten/operator/deploy/crd.yaml deploy/crd.yaml
docker cp ttoper:/timesten/operator/deploy/operator.yaml deploy/
operator.yaml
docker cp ttoper:/timesten/operator/deploy/service_account.yaml deploy/
service_account.yaml
docker cp ttoper:/timesten/operator/helm .
```

The crd.yaml, operator.yaml, and service_account.yaml files are copied to the kube_files/deploy directory. The helm directory and its contents are copied to the kube files directory. These files are discussed later.

4. Remove the ttoper container.

```
docker rm ttoper
```

The output is the following.

ttoper



5. Remove the TimesTen container image.

```
docker image rm container-registry.oracle.com/timesten/
timesten:22.1.1.19.0
```

The output is similar to the following.

```
Untagged: container-registry.oracle.com/timesten/
timesten:22.1.1.19.0
```

You successfully obtained the TimesTen Operator manifest files. Proceed to About Deploying the TimesTen Operator to deploy the TimesTen Operator.

Option 2: Build the TimesTen Container Image

The following example assumes you want to build a TimesTen container image from a TimesTen distribution. If instead you want to use an official TimesTen container image located on Oracle Container Registry, see Option 1: Use the Official TimesTen Container Images.

The base image used in this Dockerfile is container-registry.oracle.com/os/oraclelinux:8. The Dockerfile supports a number of ARGs that let you override various attributes of the TimesTen container image. For example, you can specify a custom TimesTen user and TimesTen users group to run TimesTen instead of using the default timesten user and the default timesten group. You can also specify which TimesTen release to embed in the TimesTen container image. For the supported Dockerfile ARGs, see Dockerfile ARGs.

To build the TimesTen container image, complete these steps::

- Unpack the TimesTen and the TimesTen Operator Distributions
- Copy the TimesTen Distribution
- Choose How to Build

Unpack the TimesTen and the TimesTen Operator Distributions

To unpack the TimesTen distribution and the TimesTen Operator distribution, complete the following steps:

- 1. On your development host, from the directory of your choice:
 - Create one subdirectory for the TimesTen distribution. This example creates the installation_dir subdirectory.
 - Create a second subdirectory for the TimesTen Operator distribution. This
 example creates the kube_files subdirectory.

```
mkdir -p installation_dir
mkdir -p kube files
```



2. Change to the TimesTen distribution subdirectory.

```
cd installation dir
```

3. Copy the TimesTen distribution that you previously downloaded into this TimesTen distribution directory.

```
cp download location/timesten2211190.server.linux8664.zip .
```

4. Unpack the TimesTen distribution.

```
unzip timesten2211190.server.linux8664.zip
```

The output is similar to the following:

```
Archive: timesten2211190.server.linux8664.zip
    creating: tt22.1.1.19.0/
    ...
    creating: tt22.1.1.19.0/kubernetes/
extracting: tt22.1.1.19.0/kubernetes/operator.zip
```

The TimesTen Operator distribution is <code>installation_dir/tt22.1.1.19.0/kubernetes/operator.zip</code>.

Do not delete the TimesTen distribution (installation_dir/tt22.1.1.19.0, in this example). You need it later.

5. Change to the TimesTen Operator subdirectory you created in a previous step. (In this example, *kube files*.)

```
cd kube files
```

6. Unpack the TimesTen Operator distribution.

```
unzip installation dir/tt22.1.1.19.0/kubernetes/operator.zip
```

The output is similar to the following:

```
Archive: installation_dir/tt22.1.1.19.0/kubernetes/operator.zip creating: operator/
...
  creating: deploy/
inflating: deploy/service_account.yaml
inflating: deploy/crd.yaml
inflating: deploy/operator.yaml
inflating: README.md
  creating: helm/
  creating: helm/ttcrd/
inflating: helm/ttcrd/Chart.yaml
  creating: helm/ttcrd/templates/
inflating: helm/ttcrd/templates/NOTES.txt
inflating: helm/ttcrd/templates/crd.yaml
```



```
inflating: helm/ttcrd/templates/ helpers.tpl
inflating: helm/ttcrd/.helmignore
 creating: helm/ttclassic/
inflating: helm/ttclassic/Chart.yaml
inflating: helm/ttclassic/values.yaml
 creating: helm/ttclassic/templates/
inflating: helm/ttclassic/templates/dbconfigmap.yaml
inflating: helm/ttclassic/templates/pdb.yaml
inflating: helm/ttclassic/templates/NOTES.txt
inflating: helm/ttclassic/templates/classic.yaml
inflating: helm/ttclassic/templates/dbsecret.yaml
inflating: helm/ttclassic/templates/customservice.yaml
 creating: helm/ttclassic/templates/tests/
inflating: helm/ttclassic/templates/tests/verify.yaml
inflating: helm/ttclassic/templates/ helpers.tpl
inflating: helm/ttclassic/.helmignore
 creating: helm/ttoperator/
inflating: helm/ttoperator/Chart.yaml
inflating: helm/ttoperator/values.yaml
 creating: helm/ttoperator/templates/
inflating: helm/ttoperator/templates/pdb.yaml
inflating: helm/ttoperator/templates/service account.yaml
inflating: helm/ttoperator/templates/NOTES.txt
inflating: helm/ttoperator/templates/operator.yaml
 creating: helm/ttoperator/templates/tests/
inflating: helm/ttoperator/templates/tests/verify.yaml
inflating: helm/ttoperator/templates/ helpers.tpl
inflating: helm/ttoperator/.helmignore
 creating: image/
inflating: image/Dockerfile
```

The TimesTen Operator distribution format includes the following directories:

- helm: Contains the directories and files needed to deploy the TimesTen Custom Resource Definitions (CRDs), the TimesTen Operator, and TimesTenClassic objects using Helm charts. For more information, see Use Helm to Deploy the TimesTen Kubernetes Operator and TimesTenClassic Objects.
- deploy: Contains the YAML manifest files that are used to create the required Kubernetes service account, role, and rolebinding objects and the TimesTen CRDs. The deploy directory also contains the YAML manifest file that you use to deploy the TimesTen Operator in the Kubernetes cluster. These files are discussed in Create the Service Account and the TimesTen Custom Resource Definitions (CRDs) and Customize the TimesTen Operator.
- operator: Contains the timesten-operator TimesTen Operator binary as well as the TimesTen Agent and the support files the TimesTen Agent uses at runtime. You do not need to use or make any modifications to the files in this directory.
- image: Contains the Dockerfile file that is used to create the TimesTen container image. If you are building the TimesTen container image, you use this Dockerfile.



Make a note of these directories. You need to work with files in the <code>deploy</code> and the <code>image</code> directories later in this chapter. If you are using Helm and Helm charts, you need to work with the directories and files in the <code>helm</code> directory in Use Helm to Deploy the TimesTen Kubernetes Operator and TimesTenClassic Objects.

You successfully unpacked the TimesTen and TimesTen Operator distributions.

Copy the TimesTen Distribution

The files that you need to build the TimesTen container image are provided in the unzipped TimesTen Operator distribution. In this example, the directory that contains the unzipped TimesTen Operator distribution is $kube_files$. See Unpack the TimesTen and the TimesTen Operator Distributions.

To build the TimesTen container image, complete the following steps:

1. On your development host, change to the image directory of the unzipped TimesTen Operator distribution (*kube files*/image, in this example).

```
cd kube_files/image
```

2. Copy the TimesTen distribution into the directory. In a previous example, you created the installation dir directory. This directory contains the TimesTen distribution.

```
cp installation dir/timesten2211190.server.linux8664.zip .
```

For information on <code>installation_dir</code>, see Unpack the TimesTen and the TimesTen Operator Distributions.

3. Create the image pull secret for container-registry.oracle.com.

```
kubectl create secret generic sekret \
--from-file=.dockerconfigjson=$HOME/.docker/config.json \
--type=kubernetes.io/dockerconfigjson
```

Save the name of the image pull secret. You need it later when deploying your TimesTenClassic or TimesTenScaleout objects. See Define and Create a TimesTenClassic Object and Define and Deploy a TimesTenScaleout Object.

For more information about creating a Kubernetes Secret, see Pulling Images from Registry during Deployment.

You successfully copied the TimesTen distribution to the <code>kube_files/image</code> directory and created the image pull secret.

Choose How to Build

You can choose to build the TimesTen image with the defaults specified in Dockerfile ARGs or you can choose to customize the TimesTen container image by overriding the defaults specified in Dockerfile ARGs.

Choose one of the following options:

- Option 2a: Build with Defaults
- Option 2b: Build with Customizations



Option 2a: Build with Defaults

The following example assumes you want to build the TimesTen container image with the defaults specified in Dockerfile ARGs.

- On your development host, change to the kube_files/image directory (if not already in this directory).
- 2. Use the docker build command to build the TimesTen image. You must specify the following Dockerfile ARGs on the command line:
 - TT_DISTRO: The name of the file containing the TimesTen distribution (timesten2211190.server.linux8664.zip, in this example).
 - TT_RELEASE: The name of the TimesTen release in dotted format (22.1.1.19.0, in this example).

```
docker build -t tt2211190image:1 \
--build-arg TT_DISTRO=timesten2211190.server.linux8664.zip \
--build-arg TT RELEASE=22.1.1.19.0 .
```

The output is similar to the following:

```
Sending build context to Docker daemon 461.6MB
Step 1/35: ARG TT_BASE=container-registry.oracle.com/os/
oraclelinux:8
Step 2/35: ARG UNZIP_BASE=container-registry.oracle.com/os/
oraclelinux:8
Step 3/35: FROM $UNZIP_BASE as unzipper
...
Successfully built a0d9e74ad31f
Successfully tagged tt2211190image:1
```

- 3. Tag the TimesTen container image. Replace the following:
 - tt2211190image:1 with the name you chose in the previous step.
 - phx.ocir.io/youraccount with the location of your image registry.

```
docker tag tt2211190image:1 phx.ocir.io/youraccount/tt2211190image:1
```

- 4. Push the TimesTen container image to your registry. Replace the following:
 - phx.ocir.io/youraccount with the location of your image registry.
 - tt2211190image:1 with the name you chose previously.

```
docker push phx.ocir.io/youraccount/tt2211190image:1
```

The output is similar to the following:

```
The push refers to repository [phx.ocir.io/youraccount/tt2211190image]
5f494d8654f2: Pushed
cf1cdb416e24: Pushed
```



```
511cc991c8e6: Pushed

a9abe4002691: Pushed

8894990e5ffe: Pushed

c94f317a0997: Pushed

7774e1cbdcf4: Pushed

d8c569c85182: Pushed

1: digest:

sha256:8d280bd65059f089a9ca0f2131c9f2928f71f79b0708ed6920fd4df1ea7cfd68

size: 2007
```

Note:

To reduce the size of the final TimesTen container image, the Dockerfile uses a multi-stage build. This results in a dangling image left behind. To locate dangling images, use the <code>docker</code> command with the <code>-f</code> filter flag with a value of <code>dangling=true</code>. Once you locate the dangling image, you can use the <code>docker</code> image <code>prune</code> command to remove it. For example,

```
docker images -f dangling=true
docker image prune
```

You successfully built the TimesTen container image. It is pushed to your image registry. Proceed to About Deploying the TimesTen Operator to deploy the TimesTen Operator.

Option 2b: Build with Customizations

The following example assumes you want to customize the TimesTen container image by overriding the defaults specified in Dockerfile ARGs. If you instead want to use these defaults, see Option 2a: Build with Defaults.

This example creates a custom TimesTen user and a custom TimesTen users group to run TimesTen in the TimesTen containers.

- 1. On your development host, change to the <code>kube_files/image</code> directory (if not already in this directory).
- 2. Use the docker build command to build the TimesTen image. To customize the image with a custom user and a custom TimesTen users group, specify the following Dockerfile ARGs on the command line:
 - TT_USER: The name of the Linux operating system user created in the container image. This is the user that runs TimesTen. In this example, the name of the user is customuser.
 - TT_UID: The numeric UID of \$TT_USER. In this example, the UID is 9876.
 - TT_GROUP: The name of the Linux group created in the container image. This is the name of the TimesTen users group. In this example, the name of the group is customgroup.
 - TT_GID: The numeric GID of \$TT_GROUP. In this example, the GID is 9876.

In addition, specify these required Dockerfile ARGs:



- TT_DISTRO: The name of the file containing the TimesTen distribution (timesten2211210.server.linux8664.zip, in this example).
- TT_RELEASE: The name of the TimesTen release in dotted format (22.1.1.21.0, in this example).

```
docker build -t tt2211190customimage:1 \
--build-arg TT_USER=customuser --build-arg TT_UID=9876 \
--build-arg TT_GROUP=customgroup --build-arg TT_GID=9876 \
--build-arg TT_DISTRO=timesten2211190.server.linux8664.zip \
--build-arg TT RELEASE=22.1.1.19.0 .
```

The output is similar to the following:

```
Sending build context to Docker daemon 461.6MB
Step 1/35: ARG TT_BASE=container-registry.oracle.com/os/
oraclelinux:8
Step 2/35: ARG UNZIP_BASE=container-registry.oracle.com/os/
oraclelinux:8
Step 3/35: FROM $UNZIP_BASE as unzipper
...
Successfully built 49101e32b5d5
Successfully tagged tt2211190customimage:1
```

- 3. Tag the TimesTen container image. Replace the following:
 - tt2211190customimage:1 with the name you chose in the previous step.
 - phx.ocir.io/youraccount with the location of your image registry.

docker tag tt2211190customimage:1 phx.ocir.io/youraccount/
tt2211190customimage:1

- **4.** Push the TimesTen container image to your registry. Replace the following:
 - phx.ocir.io/youraccount with the location of your image registry.
 - tt2211190customimage:1 with the name you chose previously.

docker push phx.ocir.io/youraccount/tt2211190customimage:1

The output is similar to the following:

```
The push refers to repository [phx.ocir.io/youraccount/tt2211190customimage]
3b5c7ba355aa: Pushed
30047b487811: Pushed
aa10ef33fac5: Pushed
7290609fca00: Pushed
676cb8be497d: Pushed
57a50dacb378: Pushed
d59ca9ca76e7: Pushed
d8c569c85182: Layer already exists
1: digest:
```



sha256:616cbbb94f1a8b003a45865b51d401bc5f2b48d4f99bbe7584bcbb6304d6b75b size: 2007



To reduce the size of the final TimesTen container image, the Dockerfile uses a multi-stage build. This results in a dangling image left behind. To locate dangling images, use the docker command with the -f filter flag with a value of dangling=true. Once you locate the dangling image, you can use the docker image prune command to remove it. For example,

docker images -f dangling=true
docker image prune

You successfully built the TimesTen container image. It is pushed to your image registry. Proceed to About Deploying the TimesTen Operator to deploy the TimesTen Operator.

About Deploying the TimesTen Operator

The TimesTen Operator manages and monitors TimesTenClassic and TimesTenScaleout objects that are deployed in your namespace. You deploy the TimesTen Operator in your namespace as a Kubernetes Deployment. Before deploying the TimesTen Operator, review the Expose Metrics from the TimesTen Kubernetes Operator chapter. This chapter discusses how the TimesTen Operator, by default, automatically exposes metrics about its own functionality as well as the status of TimesTenClassic and TimesTenScaleout objects to Prometheus or any other scraping mechanism. You have several options when considering if and how TimesTen Operator metrics are exposed. Although we recommend accepting the default behavior, you can decide which option works best for your environment.

The TimesTen Operator provides liveness and readiness probes that allow Kubernetes to determine the health of the TimesTen Operator. There are default values for the attributes of these probes. See About Readiness and Liveness Probes.

You have two options when deploying the TimesTen Operator:

- Use the procedures in the upcoming sections in this chapter: These procedures show you how to deploy the TimesTen Operator by using the kubectl command.
- Use TimesTen Helm charts: The TimesTen Operator provides Helm charts specific to TimesTen. These charts give you the ability to deploy the TimesTen Operator and TimesTenClassic objects using Helm. If you choose this option, proceed to Use Helm to Deploy the TimesTen Kubernetes Operator and TimesTenClassic Objects. This chapter provides all the information you need to use TimesTen Helm charts.

The following sections should you how to deploy the TimesTen Operator using the kubectl command.

- Create the Service Account and the TimesTen Custom Resource Definitions (CRDs)
- About Readiness and Liveness Probes
- Customize the TimesTen Operator
- Verify the TimesTen Operator is Running



Create the Service Account and the TimesTen Custom Resource Definitions (CRDs)

The TimesTen Operator requires a Kubernetes *service account* in order to run properly. This service account requires permissions and privileges in your namespace. These permissions and privileges are granted through a *role*. The role is assigned to the service account through a role binding.

In addition, the TimesTen Operator provides TimesTen CRDs. These CRDs define the TimesTenClassic and the TimesTenScaleout object types to the Kubernetes cluster.

When you unpacked the TimesTen Operator distribution, one of the directories that was created was the /deploy directory. This directory contains the following YAML manifest files:

- service_account.yaml: Defines the role, the role binding, and the service account for the Operator.
- crd.yaml: Defines the TimesTenClassic and the TimesTenScaleout object types.

The following example creates the TimesTen Operator's service account and the TimesTen CRDs to the Kubernetes cluster:

1. On your development host, change to the *kube files*/deploy directory.

```
cd kube files/deploy
```

2. Create the service account.

```
kubectl create -f service_account.yaml
```

The output is the following:

```
role.rbac.authorization.k8s.io/timesten-operator created
serviceaccount/timesten-operator created
rolebinding.rbac.authorization.k8s.io/timesten-operator created
```

Create the TimesTen CRDs.

```
kubectl create -f crd.yaml
```

The output is the following:

```
customresourcedefinition.apiextensions.k8s.io/
timestenclassics.timesten.oracle.com created
timestenscaleouts.timesten.oracle.com created
```

You successfully created the TimesTen Operator's service account and TimesTen CRDs.



About Readiness and Liveness Probes

The TimesTen Operator provides readiness and liveness probes so that Kubernetes can determine the health of the TimesTen Operator.

The readiness and liveness probes are defined in the operator. yaml YAML manifest file.

Here is a snippet of the operator. yaml file, showing the readiness and liveness probes:

```
# Copyright (c) 2019 - 2023, Oracle and/or its affiliates.
apiVersion: apps/v1
kind: Deployment
metadata:
  name: timesten-operator
spec:
          ports:
          - name: probes
            containerPort: 8081
            protocol: TCP
          readinessProbe:
            httpGet:
              scheme: HTTP
              path: /healthz
              port: probes
            initialDelaySeconds: 10
            periodSeconds: 10
            timeoutSeconds: 10
            successThreshold: 1
            failureThreshold: 1
          livenessProbe:
            httpGet:
              scheme: HTTP
              path: /healthz
              port: probes
            initialDelaySeconds: 10
            periodSeconds: 30
            timeoutSeconds: 10
            successThreshold: 1
            failureThreshold: 3
          env:
            - name: EXPOSE PROBES
              value: "1"
 . . .
```

The TimesTen Operator exposes these probes to applications in the Kubernetes cluster by creating the timesten-operator Kubernetes Service.

Although we do not recommend it, you can choose to not expose these probes by setting the TimesTen Operator EXPOSE PROBES environment variable to "0".

Note:

If you do set <code>EXPOSE_PROBES</code> to "0", helm test will not work properly. For information about using Helm to test the TimesTen Operator deployment, see Test the TimesTen Operator.

For information about the TimesTen Operator environment variables, see TimesTen Kubernetes Operator Environment Variables.

The operator.yaml file that is provided by the TimesTen Operator is discussed in the upcoming Customize the TimesTen Operator section. This section shows you how to customize the TimesTen Operator and shows you the liveness and readiness probes entries in the operator.yaml file.

Customize the TimesTen Operator

You can customize the TimesTen Operator by specifying the number of replicas (copies) of the TimesTen Operator that you want running in your Kubernetes cluster. You also must provide the image pull secret, and the location and name of the TimesTen container image for the TimesTen Operator.

 On your development host, change to the kube_files/deploy directory (if not already in this directory).

```
cd kube files/deploy
```

- 2. Use a text editor to modify the operator. yaml file, making changes to these fields:
 - replicas: 1

Replace 1 with the number of copies of the TimesTen Operator. A value of 1 is acceptable for development and testing. However, you can specify more than one replica for high availability purposes.

Note:

TimesTen Operator metrics are accurate when you have one TimesTen Operator defined in your TimesTen Operator Deployment. For more information about exposing TimesTen Operator metrics, see Expose Metrics from the TimesTen Kubernetes Operator.

• Replace sekret with the name of the image pull secret that Kubernetes uses to pull images from your registry.

For the TimesTen container image:

 Replace container-registry.oracle.com/timesten with the location of your image registry. You determined this location in a previous step. See About TimesTen Container Images. This example uses containerregistry.oracle.com/timesten.



• Replace timesten: 22.1.1.19.0 with the name of the TimesTen container image. You determined this name in a previous step. See About TimesTen Container Images. This example uses timesten: 22.1.1.19.0.

```
vi operator.yaml
# Copyright (c) 2019 - 2023, Oracle and/or its affiliates.
apiVersion: apps/v1
kind: Deployment
metadata:
  name: timesten-operator
spec:
  replicas: 1
  selector:
   matchLabels:
      name: timesten-operator
  template:
    metadata:
      labels:
        name: timesten-operator
    spec:
      serviceAccountName: timesten-operator
      imagePullSecrets:
      - name: sekret
      containers:
        - name: timesten-operator
          image: container-registry.oracle.com/timesten/
timesten:22.1.1.19.0
          command:
          - /timesten/operator/operator/timesten-operator
          ports:
          - name: probes
            containerPort: 8081
            protocol: TCP
          - name: metrics
            containerPort: 8080
            protocol: TCP
          readinessProbe:
            httpGet:
              scheme: HTTP
              path: /healthz
              port: probes
            initialDelaySeconds: 10
            periodSeconds: 10
            timeoutSeconds: 10
            successThreshold: 1
            failureThreshold: 1
          livenessProbe:
            httpGet:
              scheme: HTTP
              path: /healthz
              port: probes
            initialDelaySeconds: 10
            periodSeconds: 30
            timeoutSeconds: 10
```

```
successThreshold: 1
  failureThreshold: 3
env:
  - name: WATCH NAMESPACE
   valueFrom:
     fieldRef:
        fieldPath: metadata.namespace
  - name: POD NAME
   valueFrom:
      fieldRef:
        fieldPath: metadata.name
  - name: OPERATOR NAME
   value: "timesten-operator"
  - name: TT DEBUG
   value: "0"
  - name: EXPOSE METRICS
   value: "1"
  - name: METRICS SCHEME
   value: "https"
  - name: EXPOSE PROBES
   value: "1"
  - name: CREATE SERVICEMONITOR
   value: "1"
resources:
  requests:
      cpu: "250m"
      memory: "1G"
  limits:
      cpu: "250m"
     memory: "1G"
securityContext:
   runAsNonRoot: true
   privileged: false
   allowPrivilegeEscalation: false
    capabilities:
       drop:
          - all
```

Let's take a look at some of the fields in this operator.yaml file.

- The name of the TimesTen Operator Deployment is timesten-operator.
- The default value for replicas is 1. The value is not changed in the example.
- The image pull Secret is sekret. The value is not changed in the example.
- The image is container-registry.oracle.com/timesten/
 timesten:22.1.1.19.0. This example uses the containerregistry.oracle.com/timesten repository. The name of the offical TimesTen
 container image is timesten:22.1.1.19.0 to reflect the 22.1.1.19.0
 TimesTen release.
- The TimesTen Operator's readiness and liveness probes are included in the operator.yaml file. These probes allow Kubernetes to determine the health of the TimesTen Operator. See About Readiness and Liveness Probes.

- The following TimesTen Operator environment variables are included in the operator.yaml file.
 - EXPOSE_METRICS: A value of "1" indicates that TimesTen Operator metrics are
 exposed. This is the default. For more information about TimesTen Operator
 metrics, see Expose Metrics from the TimesTen Kubernetes Operator and
 TimesTen Kubernetes Operator Environment Variables.
 - METRICS_SCHEME: A value of "https" indicates TimesTen Operator metrics are
 exposed using https. This is the default. For more information about TimesTen
 Operator metrics, see Expose Metrics from the TimesTen Kubernetes Operator
 and TimesTen Kubernetes Operator Environment Variables.
 - EXPOSE_PROBES: A value of "1" indicates that TimesTen Operator probes are exposed. This is the default. For more information, see About Readiness and Liveness Probes and TimesTen Kubernetes Operator Environment Variables.
 - CREATE_SERVICEMONITOR: A value of "1" indicates that the TimesTen Operator creates a SERVICEMONITOR object. This is the default. For more information, see Expose Metrics from the TimesTen Kubernetes Operator and TimesTen Kubernetes Operator Environment Variables.
- There are default CPU and memory requests and limits provided in the operator.yaml file.



The operator.yaml file can change from release to release.

3. Deploy the TimesTen Operator in the namespace of your Kubernetes cluster.

```
% kubectl create -f operator.yaml
deployment.apps/timesten-operator created
```

You successfully deployed the TimesTen Operator. The TimesTen Operator should now be running.

Verify the TimesTen Operator is Running

Use the kubectl get pods command to verify that the TimesTen Operator is running. If the STATUS field has a value of Running, the TimesTen Operator is running.

```
kubectl get pods
```

The output is similar to the following:

NAME	READY	STATUS	RESTARTS	AGE
timesten-operator-5c7558cd75-dfbd7	1/1	Running	0	13s

You successfully verified that the TimesTen Operator is running.



Use Configuration Metadata

This chapter gives an overview of the configuration metadata that is supported in the TimesTen Operator. It also discusses the Kubernetes facilities that you can use to get the configuration metadata into your TimesTen containers. The chapter then discusses additional configuration options. There are examples throughout.

Topics:

- Overview of Configuration Metadata and Kubernetes Facilities
- List of Configuration Metadata
- About Configuration Metadata Details
- Populate the /ttconfig Directory
- Additional Configuration Options

Overview of Configuration Metadata and Kubernetes Facilities

Configuration metadata lets you define the attributes of your TimesTen database and how that database is to interact with other applications and components. The TimesTen Operator supports several metadata files that contain the configuration metadata. Each metadata file has a specific name. You use a text editor to create the metadata file with the specific name and then add the appropriate metadata to it. For example, the TimesTen Operator supports the db.ini metadata file. You use your editor to create the db.ini file and in it you define attributes for you database.

There is configuration metadata for the following TimesTen Operator deployments:

- Active standby pair of TimesTen databases in TimesTen Classic
- Active standby pair of TimesTen databases with TimesTen Cache in TimesTen Classic
- TimesTen Scaleout grid and the database within the grid

Kubernetes supports various facilities that places the metadata files into the /ttconfig directory of the TimesTen containers. See Populate the /ttconfig Directory.

List of Configuration Metadata

Table 3-1 lists the metadata files that are supported by the TimesTen Operator. The table provides a description for each of the metadata files and indicates if the metadata file is supported in TimesTen Classic, in TimesTen Scaleout, or in both.



Table 3-1 TimesTen Operator metadata files

Name	Description	TimesTen Classic support	TimesTen Scaleout support
adminUser	Defines an initial user in the database and assigns this user ADMIN privileges.	Yes	Yes
	Optional.		
cachegroups.sql	Defines the cache groups in the database. This file is specific to TimesTen Cache.	Yes	No
	Required if using TimesTen Cache.		
cacheUser	Defines the cache administration user in the database. This file is specific to TimesTen Cache.	Yes	No
	Required if using TimesTen Cache.		
csWallet	Defines the credentials that are used for Transport Layer Security (TLS) encryption of client/server communications.	Yes	Yes
	Required if using TLS.		
db.ini	Defines the connection attributes of the database. See List of Connection Attributes in the <i>Oracle TimesTen In-Memory Database Reference</i> .	Yes	Yes
	Required if using TimesTen Cache. Otherwise, optional.		
epilog.sql	Performs operations after the replication scheme is created.	Yes	No
	Optional.		
replicationWallet	Defines the credentials that are used for Transport Layer Security (TLS) encryption of replication traffic between the TimesTen databases.	Yes	No
	Required if using TLS.		
schema.sql	Defines an initial schema for the database.	Yes	Yes
	Optional.		
sqlnet.ora	Defines how client applications communicate with an Oracle database. This file is specific to TimesTen Cache.	Yes	No
	Optional.		
testUser	Defines a test user in the database. This user is used for testing TimesTen using Helm. The user is assigned CONNECT privileges.	Yes	No
	Optional.		
tnsnames.ora	Defines the Oracle Database service that TimesTen Cache uses to connect to Oracle Database.	Yes	No
	Required if using TimesTen Cache.		



Table 3-1 (Cont.) TimesTen Operator met

Name	Description	TimesTen Classic support	TimesTen Scaleout support
*.connect	Defines one or more direct connectables for the database in TimesTen Scaleout. Optional.	No	Yes
*.csconnect	Defines one or more client/server connectables for the database in TimesTen Scaleout. Optional.	No	Yes

About Configuration Metadata Details

Metadata files let you specify the attributes and the metadata for your TimesTen database. After you create these files, and you choose a facility to get these files in your TimesTen containers, TimesTen accesses them to determine the attributes and the metadata that is specific to your database.

adminUser

The adminUser file creates an initial user with ADMIN privileges in the TimesTen database. If you provide this file, this user is created after the database is created. This file must contain one line of the form:

user/password

cachegroups.sql

The <code>cachegroups.sql</code> file contains the create cache group definitions and the cache group operations for your database. You can specify the following cache group definitions and cache operations in this file:

- (Required): CREATE CACHE GROUP statements to create TimesTen cache groups
- (Optional): LOAD CACHE GROUP statements to load data from the Oracle database into your cache groups
- (Optional): ttOptUpdateStats or ttOptEstimateStats TimesTen built-in procedures to update statistics on the cache tables

The <code>cachegroups.sql</code> file is required if you are using TimesTen Cache in your TimesTenClassic deployment. This requirement ensures cache groups are created before replication is configured. Note: The instance administrator uses the ttlsql utility to run the <code>cachegroups.sql</code> file.

See:

- CREATE CACHE GROUP and LOAD CACHE GROUP in the Oracle TimesTen In-Memory Database SQL Reference
- Cache Group Types in the Oracle TimesTen In-Memory Database Cache Guide



ttOptUpdateStats and ttOptEstimateStats in the Oracle TimesTen In-Memory Database Reference

Here is an example of a cachegroups.sql file. The file defines two cache groups and loads data into one cache group.

```
CREATE DYNAMIC ASYNCHRONOUS WRITETHROUGH CACHE GROUP writecache
FROM oratt.writetab (
 pk NUMBER NOT NULL PRIMARY KEY,
 attr VARCHAR2(40)
CREATE READONLY CACHE GROUP readcache
AUTOREFRESH
 INTERVAL 5 SECONDS
FROM oratt.readtab (
 keyval NUMBER NOT NULL PRIMARY KEY,
  str VARCHAR2(32)
);
```

LOAD CACHE GROUP readcache COMMIT EVERY 256 ROWS;

cacheUser

The cacheUser file lets you create the TimesTen cache manager user. This user must have the same name as the cache administration user in the Oracle database, and must already exist in the Oracle database. See Create the Oracle Database Users and Default Tablespace in the Oracle TimesTen In-Memory Database Cache Guide.

This file must contain one line of the form.

```
cacheUser/ttPassword/oraPassword
```

where cacheUser is the TimesTen cache manager user, ttPassword is the TimesTen password for the TimesTen cacheUser user, and oraPassword is the Oracle database password you specified when you created the cacheUser user in the Oracle database.

For example, assume you have created the cacheuser2 cache administration user in the Oracle Database with password oraclepwd. Assume you designate this cacheuser2 user as the TimesTen cache manager user with a TimesTen password of ttpwd. In this example, the cacheUser metadata file contains this one line:

```
cacheuser2/ttpwd/oraclepwd
```

The TimesTen Operator creates the cacheuser2 user with the ttpwd in the TimesTen database. This cacheuser2 user then serves as the cache manager user in your TimesTen database. You do not need to create this TimesTen user. The Operator does it for you.

See Create the TimesTen Users in the Oracle TimesTen In-Memory Database Cache Guide.

The Operator grants privileges to the TimesTen cacheuser user (cacheuser2, in this example) that are appropriate for this user's role as the cache manager. These privileges are:

- CREATE SESSION
- CACHE MANAGER



- CREATE ANY TABLE
- LOAD ANY CACHE GROUP
- REFRESH ANY CACHE GROUP
- FLUSH ANY CACHE GROUP
- DROP ANY CACHE GROUP
- ALTER ANY CACHE GROUP
- UNLOAD ANY CACHE GROUP
- SELECT ANY TABLE
- INSERT ANY TABLE
- UPDATE ANY TABLE
- DELETE ANY TABLE

csWallet

In a TimesTen Client/Server environment, data is transmitted between your client applications and your TimesTen database unencrypted by default. However, you can configure TLS for Client/Server to ensure secure network communication between TimesTen clients and servers. To encrypt Client/Server traffic, specify the /ttconfig/csWallet file. This file contains the Oracle wallet for the server, which contains the credentials that are used for configuring TLS encryption between your TimesTen database and your Client/Server applications. The file will be available in the containers of your TimesTen databases in the directory /tt/home/timesten/csWallet. You can reference this directory in your db.ini file (by specifying the wallet connection attribute). See Create TLS Certificates for Replication and Client/Server.

The client wallet must also be available to your client applications. See Create TLS Certificates for Replication and Client/Server and Configure TLS for Client/Server.

db.ini

The db.ini file contains the TimesTen DSN definition for your database.

In TimesTen Classic, the <code>db.ini</code> file contains the connection attributes for your database. This file is used to to generate the <code>sys.odbc.ini</code> file for the instances. You can specify data store attributes, first connection attributes, and general connection attributes in the <code>db.ini</code> file. The name of the DSN is the name of the TimesTenClassic object. For example, if your TimesTenClassic object is called <code>sample</code>, the name of your DSN is <code>sample</code>.

In TimesTenScaleout, the <code>db.ini</code> file contains the connection attributes for each element of your database in the grid. The database definition file (dbDef) and its contents are used to create a TimesTen Scaleout database definition. The name of the database definition is the name of the TimesTenScaleout object. For example, if the name of your TimesTenScaleout object is <code>sample</code>, the name of the database definition is <code>sample</code>. The TimesTen Scaleout database is created based on the database definition. For information about creating a database and creating a database definition in TimesTen Scaleout, see Creating a Database in the <code>Oracle TimesTen In-Memory Database Scaleout User's Guide</code>.

If you are using TimesTen Cache in your TimesTenClassic deployment, you must specify the OracleNetServiceName and the DatabaseCharacterSet connection attributes in the db.ini



file. The DatabaseCharacterSet value must match the value of the database character set in the Oracle Database.

Do not specify the the <code>DataStore</code> or the <code>LogDir</code> connection attributes in the <code>db.ini</code> file. The Operator sets these attributes, placing the database files in Kubernetes Persistent Volumes.

See List of Connection Attributes in the *Oracle TimesTen In-Memory Database Reference* for information on the TimesTen connection attributes.



If the /ttconfig/db.ini file is not present in a TimesTen container, TimesTen creates a default sys.odbc.ini file. For this default sys.odbc.ini, the connection attributes are: Permsize=200 and DatabaseCharacterSet=AL32UTF8.

This example shows a sample db.ini file that contains various connection attributes for TimesTen databases in TimesTen Classic or TimesTen Scaleout.

PermSize=500 LogFileSize=1024 LogBufMB=1024 DatabaseCharacterSet=AL32UTF8

Here is an example that shows a sample db.ini file that contains the OracleNetServiceName for TimesTen databases that use TimesTen Cache in TimesTen Classic.

PermSize=500 LogFileSize=1024 LogBufMB=1024 DatabaseCharacterSet=AL32UTF8 OracleNetServiceName=OraCache

epilog.sql

In TimesTen Classic, the <code>epilog.sql</code> file includes operations that occur after the replication scheme has been created and the replication agent has been started. For example, if you want to create replicated bookmarks in XLA, you can include the <code>ttXlaBookmarkCreate</code> TimesTen built-in procedure in this file.

The Operator instructs the instance administrator to run the epilog.sql file using the ttlsql utility.

Here is an example of an <code>epilog.sql</code> file. The example calls the <code>ttXlaBookmarkCreate</code> TimesTen built-in procedure to create XLA bookmarks.

call ttXlaBookmarkCreate('mybookmark',0x01);

For information about replicated bookmarks, see the ttXlaBookmarkCreate TimesTen built-in procedure in the *Oracle TimesTen In-Memory Database Reference*.



replicationWallet

In TimesTen Classic, TimesTen replication transmits data between your TimesTen databases unencrypted by default. However, you can configure TLS for replication to ensure secure network communication between your replicated TimesTen databases. To do this, specify the /ttconfig/replicationWallet file. This file contains an Oracle wallet, which contains the credentials that are used by TimesTen replication for configuring TLS encryption between your active standby pair of TimesTen databases. See Create TLS Certificates for Replication and Client/Server and Configure TLS for Replication.

If you specify this file, you must include the replicationCipherSuite field and optionally include the replicationSSLMandatory field in your TimesTenClassic object definition. See the replicationCipherSuite entry and the replicationSSLMandatory entry in TimesTenClassicSpecSpec and Configure TLS for Replication.

schema.sql

The TimesTen Operator can automatically initialize your database with schema objects, such as users, tables, and sequences. To have the Operator do this, create the schema.sql file.

The Operator directs the instance administrator to use the ttlsql utility to run the schema.sql file immediately after the database is created. This operation occurs before the Operator configures replication or cache in your TimesTen database.

In TimesTen Cache, one or more cache table users own the cache tables. If this cache table user is not the cache manager user, then you must specify the <code>schema.sql</code> file and in it you must include the schema user and assign the appropriate privileges to this schema user. For example, if the <code>oratt</code> schema user was created in the Oracle database, and this user is not the TimesTen cache manager user, you must create the TimesTen <code>oratt</code> user in this file. See Create the Oracle Database Users.

Do not include cache definitions in this file. Instead, use the cachegroups.sql metadata file. See cachegroups.sql.

sqlnet.ora

The Oracle Database sqlnet.ora file defines the options for how client applications communicate with the Oracle Database. To use TimesTen Cache or to use tools like ttLoadFromOracle, define a sqlnet.ora file. This file describes how applications, including TimesTen, can connect to your Oracle database. Note: If you define a sqlnet.ora file, you must define a tnsnames.ora file. See tnsnames.ora.

This is an example of a sqlnet.ora file:

```
NAME.DIRECTORY_PATH= {TNSNAMES, EZCONNECT, HOSTNAME}
SQLNET.EXPIRE_TIME = 10
SSL VERSION = 1.2
```

testUser

The testUser file defines a test user. This user is used for testing TimesTen with the helm test command. The user is granted CONNECT privileges. The test connects to a TimesTen



database as the test user. The test verifies that both the active and standby databases are up and running and that replication between them is functional.

The testUser file must contain one line of the form:

```
testuser/testuserpassword
```

where testuser is the name of your test user and testuserpassword is the password for this test user.

For more information about using Helm and using the helm test command to test TimesTen, see Use Helm to Deploy the TimesTen Kubernetes Operator and TimesTenClassic Objects and Test TimesTen.

tnsnames.ora

The Oracle Database tnsnames.ora file defines Oracle Net Services to which applications connect. You need to use tnsnames.ora (and perhaps a sqlnet.ora file, described in sqlnet.ora) if you are using:

- TimesTen Cache
- SQL APIs, such as Pro*C, OCI, or ODPI-C
- The ttLoadFromOracle feature

For information about the ttLoadFromOracle TimesTen built-in procedure, see ttLoadFromOracle in the *Oracle TimesTen In-Memory Database Reference*.

Here is an example of a tnsnames.ora file:

*.connect

Files with names that end with the .connect extension define one or more direct connectables for direct mode access to a database in TimesTen Scaleout. You can create as many direct connectables as you like. A direct connectable specifies a set of general connection attribute settings for the database. You can choose any name for the direct connectable as long as it is a valid DSN name. The TimesTen Operator creates one direct connectable for each direct connectable file you create.

The .connect extension denotes a direct connectable. Ensure the .connect extension is in lowercase.

The following example creates one direct connectable. The name of the file is sample.connect. The TimesTen Operator creates the sample direct connectable based on the contents of the sample.connect file.

ConnectionCharacterSet=AL32UTF8

For more information about direct connectables, see Connectable Operations in the *Oracle TimesTen In-Memory Database Reference* and Connecting to a Database in the *Oracle TimesTen In-Memory Database Scaleout User's Guide*.

*.csconnect

Files with names that end with the .csconnect extension define one or more client/server connectables for client/server access to a database in TimesTen Scaleout. You can create as many client/server connectables as you like. A client/server connectable specifies a set of general connection attribute settings for the database. You can choose any name for the client/server connectable as long as it is a valid DSN name. The TimesTen Operator creates one client/server connectable for each client/server connectable file you create.

The .csconnect extension denotes a client/server connectable. Ensure the .csconnect extension is in lowercase.

The following example creates one client/server connectable. The name of the file is samplecs.csconnect. The TimesTen Operator creates the samplecs client/server connectable based on the contents of the samplecs.csconnect file.

ConnectionCharacterSet=AL32UTF8
TTC Timeout=30

For more information about client/server connectables, see Connectable Operations in the Oracle TimesTen In-Memory Database Reference and Connecting to a Database in the Oracle TimesTen In-Memory Database Scaleout User's Guide.

Populate the /ttconfig Directory

You can use different methods to ensure metadata files are placed in the /ttconfig directory of TimesTen containers. There is no requirement as to which method to use. Kubernetes provides such facilities as ConfigMaps, Secrets, and init containers for you to consider.

- Using ConfigMaps and Secrets
- Using an init container

Using ConfigMaps and Secrets

You can use one or more ConfigMaps and one or more Secrets to incorporate metadata files into the TimesTen containers. This lets you specify different TimesTen metadata for different deployments. In addition, you can use Secrets for metadata that contains sensitive data, like passwords and certificates.

The use of a ConfigMap to populate the metadata into Pods is a standard Kubernetes technique. One benefit is that you can modify the ConfigMap after it is created, which results in the immediate update of the files that are in the Pod.



Note:

TimesTen may not immediately notice and act on the changed content of the files.

When you use ConfigMaps and Secrets to hold your metadata and then reference them in the TimesTenClassic object definition, the TimesTen Operator creates a Projected Volume called tt-config. This tt-config volume contains the contents of all the ConfigMaps and all the Secrets specified in the dbConfigMap and the dbSecret fields of your TimesTenClassic or your TimesTenScaleout object. This volume is mounted as /ttconfig in the TimesTen containers.

Note:

You can specify one or more ConfigMaps and/or Secrets in your TimesTenClassic or TimesTenScaleout object using the <code>dbConfigMap</code> and <code>dbSecret</code> datum. The result is that these ConfigMaps and/or Secrets are mounted read-only at <code>/ttconfig</code>. Since such a mount is read-only, you cannot write into it from an init container. Alternatively, you can use an <code>emptydir</code> volume and use an init container to write files into it. However, you cannot combine ConfigMaps and Secrets with an init container. For information about using an init container, see <code>Using an init container</code>.

To use ConfigMaps and Secrets, follow this process:

- Decide what facilities will contain what metadata files. For example, you can use one ConfigMap for all the metadata files. Or, for example, you can use one ConfigMap for the db.ini metadata file and one Secret for the adminUser and the schema.sql metadata files. There is no specific requirement.
- Create the directory (or directories) that will contain the metadata files.
- Use the kubectl create command to create the ConfigMap and the Secrets in the Kubernetes cluster.
- Include the ConfigMaps and Secrets in your TimesTenClassic or your TimesTenScaleout object definition.

The following examples illustrate how to use ConfigMaps and Secrets for a TimesTenClassic or a TimesTenScaleout object.

- Example Using One ConfigMap
- Example Using One ConfigMap and One Secret
- Example Using One ConfigMap for a TimesTenScaleout Object

Example Using One ConfigMap

This example uses one ConfigMap (called sample) for the db.ini, the adminUser, and the schema.sql metadata files.

You can use this ConfigMap for a TimesTenClassic or a TimesTenScaleout object.



 On your development host, from the directory of your choice, create an empty subdirectory for the metadata files. This example creates the cm_sample subdirectory. (The cm_sample directory is used in the remainder of this example to denote this directory.)

```
mkdir -p cm sample
```

2. Change to the ConfigMap directory.

```
cd cm sample
```

3. Create the db.ini file. In this db.ini file, define the PermSize and DatabaseCharacterSet connection attributes.

```
vi db.ini

PermSize=200

DatabaseCharacterSet=AL32UTF8

ConnectionCharacterSet=AL32UTF8
```

4. Create the adminUser file. In this adminUser file, create the sampleuser user with the samplepw password.

```
vi adminUser
sampleuser/samplepw
```

5. Create the schema.sql file. In this schema.sql file, define the s sequence and the emp table for the sampleuser user. The Operator automatically initializes your database with these object definitions.

```
vi schema.sql
create sequence sampleuser.s;
create table sampleuser.emp (
  id number not null primary key,
  name char(32)
);
```

6. Create the ConfigMap. The files in the <code>cm_sample</code> directory are included in the ConfigMap. These files are later available in the TimesTen containers.

In this example:

- The name of the ConfigMap is sample. Replace sample with a name of your choosing.
- This example uses cm_sample as the directory where the files that will be copied into the ConfigMap reside. If you use a different directory, replace cm_sample with the name of your directory.

```
kubectl create configmap sample --from-file=cm_sample
```

The output is the following:

```
configmap/sample created
```

7. Verify the contents of the ConfigMap.

```
kubectl describe configmap sample
```



The output is the following:

```
Name:
              sample
Namespace:
             mynamespace
Labels:
              <none>
Annotations: <none>
Data
====
adminUser:
sampleuser/samplepw
db.ini:
PermSize=200
DatabaseCharacterSet=AL32UTF8
ConnectionCharacterSet=AL32UTF8
schema.sql:
create sequence sampleuser.s;
create table sampleuser.emp (
 id number not null primary key,
  name char (32)
);
Events: <none>
```

B. Include the ConfigMap in the object definition. In the dbConfigMap field, specify the name of the your ConfigMap (sample, in this example).

Note this example uses a storageSize of 250Gi (suitable for a production environment). For demonstration purposes, a storageSize of 50Gi is adequate.

This is an example of using the ConfigMap for a TimesTenClassic object.

```
apiVersion: timesten.oracle.com/v1
kind: TimesTenClassic
metadata:
   name: sample
spec:
   ttspec:
    storageClassName: oci-bv
    storageSize: 250Gi
   image: container-registry.oracle.com/timesten/timesten:22.1.1.19.0
   imagePullSecret: sekret
   dbConfigMap:
   - sample
```

This is an example of using the ConfigMap for a TimesTenScaleout object.

```
apiVersion: timesten.oracle.com/v1
kind: TimesTenScaleout
metadata:
   name: sample
spec:
```



```
ttspec:
   storageClassName: oci-bv
   storageSize: 250Gi
   image: container-registry.oracle.com/timesten/timesten:22.1.1.19.0
   imagePullSecret: sekret
   k: 2
   nReplicaSets: 3
   nZookeeper: 3
   dbConfigMap:
   - sample
```

The sample ConfigMap holds the metadata files. The tt-config volume contains the contents of the sample ConfigMap.

Example Using One ConfigMap and One Secret

This example uses one ConfigMap (called myconfig) for the db.ini metadata file and one Secret (called mysecret) for the adminuser and the schema.sql metadata files.

You can use this ConfigMap and Secret for a TimesTenClassic or a TimesTenScaleout object.

- 1. On your development host, from the directory of your choice:
 - Create one empty subdirectory for the ConfigMap. This example creates the cm_myconfig subdirectory. (The cm_myconfig directory is used in the remainder of this example to denote this directory.) This directory will contain the db.ini metadata file.
 - Create a second empty subdirectory for the Secret. This example creates the secret_mysecret subdirectory. (The secret_mysecret directory is used in the remainder of this example to denote this directory.) This directory will contain the adminUser and the schema.sql metadata files.

```
mkdir -p cm_myconfig
mkdir -p secret mysecret
```

Change to the ConfigMap directory.

```
cd cm_myconfig
```

3. Create the db.ini file in this ConfigMap directory (cm_myconf, in this example). In this db.ini file, define the PermSize and DatabaseCharacterSet connection attributes.

```
vi db.ini
PermSize=200
DatabaseCharacterSet=AL32UTF8
ConnectionCharacterSet=AL32UTF8
```

4. Change to the Secret directory.

```
cd secret_mysecret
```

5. Create the adminUser file in this Secret directory (secret_mysecret in this example). In this adminUser file, create the sampleuser user with the samplepw password.

```
vi adminUser
sampleuser/samplepw
```



6. Create the schema.sql file in this Secret directory (secret_mysecret in this example). In this schema.sql file, define the s sequence and the emp table for the sampleuser user. The Operator automatically initializes your database with these object definitions.

```
vi schema.sql
create sequence sampleuser.s;
create table sampleuser.emp (
  id number not null primary key,
  name char(32)
);
```

7. Create the ConfigMap. The files in the <code>cm_myconfig</code> directory are included in the ConfigMap and, later, will be available in the TimesTen containers.

In this example:

- The name of the ConfigMap is myconfig. Replace myconfig with a name of your choosing.
- This example uses cm_myconfig as the directory where the files that will be copied into the ConfigMap reside. If you use a different directory, replace cm myconfig with the name of your directory.

Create the ConfigMap.

```
kubectl create configmap myconfig --from-file=cm_myconfig
```

The output is the following:

```
configmap/myconfig created
```

8. Verify the contents of the ConfigMap.

```
kubectl describe configmap myconf
```

myconfig

The output is the following:

Name:

```
Namespace: mynamespace
Labels: <none>
Annotations: <none>

Data
====
db.ini:
----
PermSize=200
DatabaseCharacterSet=AL32UTF8
ConnectionCharacterSet=AL32UTF8
Events: <none>
```

9. Create the Secret. The files in the secret_mysecret directory are included in the Secret and, later, will be available in the TimesTen containers.

In this example:



- The name of the Secret is mysecret. Replace mysecret with a name of your choosing.
- This example uses secret_mysecret as the directory where the files that will be copied into the Secret reside. If you use a different directory, replace secret mysecret with the name of your directory.

```
kubectl create secret generic mysecret --from-file=secret_mysecret
```

The output is the following:

```
secret/mysecret created
```

10. Verify the Secret. Note the contents of the adminUser and the schema.sql files are not displayed.

```
kubectl describe secret mysecret
```

The output is the following:

```
Name: mysecret
Namespace: mynamespace
Labels: <none>
Annotations: <none>

Type: Opaque

Data
====
adminUser: 12 bytes
schema.sql: 98 bytes
```

- **11.** Include the ConfigMap and the Secret in the object definition.
 - In the dbConfigMap field, specify the name of the your ConfigMap.
 - In the dbSecret field, specify the name of the your Secret.

This is an example of using the ConfigMap and the Secret for a TimesTenClassic object.

```
apiVersion: timesten.oracle.com/v1
kind: TimesTenClassic
metadata:
   name: sample
spec:
   ttspec:
    storageClassName: oci-bv
    storageSize: 250Gi
   image: container-registry.oracle.com/timesten/timesten:22.1.1.19.0
   imagePullSecret: sekret
   dbConfigMap:
   - myconfig
   dbSecret:
   - mysecret
```



This is an example of using the ConfigMap and the Secret for a TimesTenScaleout object.

```
apiVersion: timesten.oracle.com/v1
kind: TimesTenScaleout
metadata:
 name: sample
spec:
 ttspec:
   storageClassName: oci-bv
   storageSize: 250Gi
    image: container-registry.oracle.com/timesten/
timesten:22.1.1.19.0
    imagePullSecret: sekret
   k: 2
   nReplicaSets: 3
   nZookeeper: 3
   dbConfigMap:
    - myconfig
    dbSecret:
    - mysecret
```

The myconfig ConfigMap and the mysecret Secret holds the metadata files. The tt-config volume contains the contents of the myconfig ConfigMap and the mysecret Secret.

Example Using One ConfigMap for a TimesTenScaleout Object

This example shows you how to create a metadata file for a direct connectable and a metadata file for a client/server connectable. It then shows you how to include these connectables in a ConfigMap for a TimesTenScaleout object. The ConfigMap also includes the db.ini, adminUser, and schema.sql metadata files.

1. On your development host, from the directory of your choice, create an empty subdirectory for the metadata files. This example creates the <code>cm_samplescaleout</code> subdirectory. (The <code>cm_samplescaleout</code> directory is used in the remainder of this example to denote this directory.)

```
mkdir -p cm samplescaleout
```

2. Change to the ConfigMap directory.

```
cd cm samplescaleout
```

3. Create the direct connectable.

```
vi samplescaleout.connect
ConnectionCharacterSet=AL32UTF8
```

4. Create the client/server connectable.

```
vi samplecsscaleout.csconnect
```



```
ConnectionCharacterSet=AL32UTF8
TTC Timeout=30
```

5. Create the db.ini file. In this db.ini file, define the PermSize and DatabaseCharacterSet connection attributes.

```
vi db.ini
PermSize=200
DatabaseCharacterSet=AL32UTF8
```

6. Create the adminuser file. In this adminuser file, create the sampleuser user with the samplepw password.

```
vi adminUser
sampleuser/samplepw
```

7. Create the schema.sql file. In this schema.sql file, define the s sequence and the emp table for the sampleuser user. The Operator automatically initializes your database with these object definitions.

```
vi schema.sql
create sequence sampleuser.s;
create table sampleuser.emp (
  id number not null primary key,
  name char(32)
);
```

8. Create the ConfigMap. The files in the <code>cm_samplescaleout</code> directory are included in the ConfigMap. These files are later available in the TimesTen containers.

In this example:

- The name of the ConfigMap is samplescaleout. Replace samplescaleout with a name of your choosing.
- This example uses cm_samplescaleout as the directory where the files that will be copied into the ConfigMap reside. If you use a different directory, replace cm samplescaleout with the name of your directory.

```
\verb+kubectl create configmap samplescaleout -- from - file = \verb+cm_samplescaleout|
```

The output is the following:

```
configmap/samplescaleout created
```

9. Verify the contents of the ConfigMap.

```
kubectl describe configmap samplescaleout
```

The output is the following:

```
Name: samplescaleout
Namespace: mynamespace
Labels: <none>
Annotations: <none>
```



```
adminUser:
sampleuser/samplepw
db.ini:
PermSize=200
DatabaseCharacterSet=AL32UTF8
sampleconnectable.connect:
ConnectionCharacterSet=AL32UTF8
samplecsconnectable.csconnect:
ConnectionCharacterSet=AL32UTF8
TTC Timeout=30
schema.sql:
create sequence sampleuser.s;
create table sampleuser.emp (
 id number not null primary key,
 name char (32)
);
Events: <none>
```

10. Include the ConfigMap in the object definition.

Note this example uses a storageSize of 250Gi (suitable for a production environment). For demonstration purposes, a storageSize of 50Gi is adequate.

```
apiVersion: timesten.oracle.com/v1
kind: TimesTenScaleout
metadata:
   name: samplescaleout
spec:
   ttspec:
    storageClassName: oci-bv
    storageSize: 250Gi
    image: container-registry.oracle.com/timesten/
timesten:22.1.1.19.0
   imagePullSecret: sekret
   k: 2
   nReplicaSets: 3
   nZookeeper: 3
   dbConfigMap:
   - samplescaleout
```

Using an init container

You can use an init container to place your metadata files into the /ttconfig directory of the TimesTen containers. An init container lets you to create your own scripts to

populate the /ttconfig directory. You can use an init container for TimesTenClassic and for TimesTenScaleout objects. For more information about init containers, see:

https://kubernetes.io/docs/concepts/workloads/pods/init-containers



You can specify one or more ConfigMaps and/or Secrets in your TimesTenClassic or TimesTenScaleout object using the <code>dbConfigMap</code> and <code>dbSecret</code> datum. The result is that these ConfigMaps and/or Secrets are mounted read-only at <code>/ttconfig</code>. Since such a mount is read-only, you cannot write into it from an init container. Alternatively, you can use an <code>emptydir</code> volume and use an init container to write files into it. However, you cannot combine ConfigMaps and Secrets with an init container. For information about using ConfigMaps and Secrets, see Using ConfigMaps and Secrets.

Here is an example that illustrates how to use an init container for a TimesTenClassic object. The template element is required. This element is applied to Pods that contain the TimesTen Classic instances. The example shows you where to specify the script that populates the / ttconfig directory. It also uses the tt-config volume name in the volumes field of the TimesTenClassic object. If you specify a volume with the tt-config name, it is automatically mounted at /ttconfig in your TimesTen containers.

```
apiVersion: timesten.oracle.com/v1
kind: TimesTenClassic
metadata:
 name: init1
spec:
  ttspec:
   storageClassName: oci-bv
    storageSize: 250Gi
    image: container-registry.oracle.com/timesten/timesten:22.1.1.19.0
    imagePullSecret: sekret
  template:
    spec:
      imagePullSecrets:
      - name: sekret
      initContainers:
      - name: initclassic
        image: container-registry.oracle.com/timesten/timesten:22.1.1.19.0
        command:
        - sh
        - "-c"
          /bin/bash <<'EOF'
          Your script to populate /ttconfig goes here
          EOF
        volumeMounts:
        - name: tt-config
          mountPath: /ttconfig
      volumes:
      - name: tt-config
        emptyDir: {}
```

When using an init container for a TimesTenScaleout object, the metadata files must be placed in both the dataTemplate and the mgmtTemplate elements.

Additional Configuration Options

This section discusses additional configuration options. These are optional configurations for your environment:

- Persistent Storage
- Additional Resource Specifications

Persistent Storage

When you create a TimesTenClassic object, the Operator automatically creates one or two Persistent Volume Claims (PVCs) per Pod. These PVCs cause Persistent Volumes (PVs) to be allocated by Kubernetes and to be attached to the TimesTen Pods. TimesTen uses the PVs to hold the TimesTen instance and the TimesTen database. If you specify two PVCs, one PV holds the instance and the checkpoint files and the second PV holds the transaction log files.

When you create a TimesTenScaleout object, the same mechanism is used to provision persistent storage for the data instances, the management instance, and the ZooKeeper instances:

- For the data instances: The Operator creates one or two PVCs per Pod. TimesTen
 uses the PVs to hold the TimesTen instance and the TimesTen database. If you
 specify two PVCs, one PV holds the instance and the checkpoint files and the
 second PV holds the transaction log files.
- For the management instance: The Operator creates one PVC for the Pod that contains the management instance. The PV holds the the TimesTen management instance and the grid database.
- For the ZooKeeper instances: The Operator creates one PVC for each Pod that runs a ZooKeeper instance. The PV holds ZooKeeper's persistent data.

When you create a TimesTenClassic object, you must specify <code>storageClassName</code> and you may specify <code>storageSize</code>. These attributes determine the characteristics of the Persistent Volumes. The <code>storageClassName</code> must be one that is provided in your Kubernetes environment. For example, in Oracle Kubernetes Environment (OKE), you may use <code>oci-bv</code>.

The default storage is 50Gi. Use the storageSize attribute to request a different size. A storage size of 50Gi may be adequate for demonstration purposes, but in production environments, you should consider greater storage.

TimesTen places the TimesTen installation, the instance, and the database in this storage. It is mounted in each container, in each Pod, as /tt. The TimesTen instance is located at /tt/home/timesten/instances/instance1.

When you create a TimesTenScaleout object, the following attributes are supported:

- Storage class name:
 - dataStorageClassName: Name of the storage class that is used to request persistent volumes for the elements of the TimesTen database in the grid. If not specified, the default is the value of storageClassName.



- mgmtStorageClassName: Name of the storage class that is used to request persistent volumes for the database of the management instance. If not specified, the default is the value of storageClassName.
- zookeeperStorageClassName: Name of the storage class that is used to request persistent volumes for ZooKeeper's persistent data. If not specified, the default is the value of storageClassName.
- storageClassName: If the data storage class name, the management storage class name, and the zookeeper storage class name are the same, you can just specify storageClassName.

Storage size:

- dataStorageSize: Amount of storage to be provisioned for each element of the TimesTen database in the grid. The default is 50Gi.
- mgmtStorageSize: Amount of storage to be provisioned for the database of the management instance. The default is 50Gi.
- zookeeperStorageSize: Amount of storage to be provisioned for ZooKeeper's persistent data. The default is 50Gi.
- storageSize: If the data storage size, the management storage size, and the zookeeper storage size are the same, you can just specify storageSize. For example, if the dataStorageSize is 75Gi, and the mgmtStorageSize is 75Gi, and the zookeeperStorageSize is 75Gi, you can specify storageSize with a value of 75Gi. The value for dataStorageSize, for mgmtStorageSize, and for zookeeperStorageSize is set to the value of storageSize.

For the TimesTen databases (using TimesTen Classic) and for the TimesTen database (using TimesTen Scaleout):

- TimesTen best practices recommends that the transaction log files associated with a TimesTen database be located on a different storage volume than the checkpoint files for the database. This provides separate paths to storage for the checkpoint and the transaction log operations. For example, you can store the transaction log files in a high performance storage, while storing the checkpoint files in a slower storage. See Locate Checkpoint and Transaction Log Files on Separate Physical Device in the *Oracle TimesTen In-Memory Database Operations Guide* for more information.
- To locate the checkpoint files and the transaction log files on a separate path of storage, provide a value for a second persistent storage that is used only for the transaction log files. Use the <code>logStorageSize</code> attribute for this and control its placement by using the <code>logStorageClassName</code> attribute. This causes a second PVC to be created for each Pod, which will then be available in each container at <code>/ttlog</code>. (This second storage volume has a <code>/ttlog</code> mount point.)

Here is an example for a TimesTenClassic object. The same example can be used for a TimesTenScaleout object:

```
apiVersion: timesten.oracle.com/v1
kind: TimesTenClassic
metadata:
   name: sample
spec:
   ttspec:
    storageClassName: slower
   storageSize: 750Gi
```



```
logStorageClassName: faster
logStorageSize: 200G
```

Additional Resource Specifications

Kubernetes supports affinity and anti-affinity settings that let applications control their placement within the Kubernetes cluster. These settings can be used to ensure all replicas do not reside on a single physical host.

You can specify affinity settings, node selectors, additional containers, tolerations, resource requirements, and other Kubernetes attributes for the TimesTen Pods and the containers within these Pods that are created by the TimesTen Operator.

In a TimesTenClassic deployment, you specify these resource specifications in the TimesTenClassic object's <code>.spec.template</code> datum. The TimesTen Operator passes this <code>template</code> to the StatefulSet. For example, when you deploy a TimesTenClassic object, the Operator configures a replicated pair of TimesTen databases that provide high availability. However, since the Operator does not control the placement of Pods, you can achieve an even greater level of high availability by controlling the placement of the TimesTen Pods. TimesTen Pods can then be available in different availability zones or are on different Kubernetes nodes. To do this, you specify the <code>affinity</code> option in the <code>.spec.template</code> datum for the TimesTenClassic object.

Similar to a TimesTenClassic deployment, you can specify the same resource specifications for a TimesTenScaleout object. The TimesTenScaleout object supports the .spec.mgmtTemplate, .spec.dataTemplate and .spec.zookeeperTemplate attributes. You can use these attributes to pass affinity and other settings to Kubernetes. These are of type PodTemplateSpec:

- mgmtTemplate: Applied to the Pod that contains the TimesTen Scaleout management instance. Consists of a single PodTemplateSpec.
- dataTemplate: Applied to the Pods that contain the TimesTen Scaleout data instances. Consists of an array of PodTemplateSpec. If specified, there must be one entry in the array for each data space in the grid (k entries in the array). This lets you specify a different placement for each data space. For example, you can have data space one reside in availability zone 1 and data space two reside in availability zone 2.
- zookeeperTemplate: Applied to the Pods that contain the ZooKeeper instances used by Scaleout. Consists of a single PodTemplateSpec.

For information about PodTemplateSpec see, https://kubernetes.io/docs/reference/kubernetes-api/

Here is an example of specifying the affinity setting for a TimesTenClassic object.



```
labelSelector:
matchExpressions:
    - key: "app"
    operator: In
    values:
    - ds1
topologyKey: "kubernetes.io/hostname"
```

About Readiness Probes for TimesTen Containers

Kubernetes *readiness probes* allow Kubernetes to determine whether a particular application is *ready*. For example, consider an application that, when it starts, has to perform a lengthy startup procedure. When the application is started by Kubernetes, it is not immediately ready. It cannot handle requests or workloads until the startup procedure is complete.

The TimesTen Kubernetes Operator (TimesTen Operator) provides two readiness probes for two different definitions of the term readiness. In order to determine if a TimesTen container is ready to Kubernetes in each of these different situations, the TimesTen Operator creates and manages two files in TimesTen containers. The presence or absence of one or more of these files indicates if TimesTen in that container is ready or not.

Let's take a look at these two definitions and the specific TimesTen readiness probe file that is applicable for each definition. After reviewing the definitions, choose if either of these definitions is applicable to your situation and is useful for you. You can only choose one of these definitions.

- The first definition defines readiness for both TimesTen Classic and TimesTen Scaleout databases. In a TimesTen Classic active standby pair, the tt container providing the active database is considered ready. In TimesTen Scaleout, all instances with elements that are up and usable are considered ready.
 - For this definition of readiness, the TimesTen Operator creates and manages the / tmp/active file, which is located in the TimesTen container's file system. If this file exists in the container, the container is. Otherwise, the container is not ready.
- The second definition defines readiness specifically for TimesTen Classic databases. In TimesTen Classic, a TimesTen instance that is created by the TimesTen Operator and is running in the tt container of a Pod is ready if the database inside of that Pod is loaded, replication is configured, and the database is either a fully functional active or a fully functional standby. A database that is down or in the process of being created or duplicated is not ready.

For this definition of readiness, the TimesTen Operator creates and manages the /tmp/readiness file, which is located in the TimesTen container's file system. If the file exists in the container, the container is ready to Kubernetes. Otherwise, the container is not ready.

Here is a code snippet that illustrates the use of a TimesTen readiness probe. The sample TimesTenClassic object definition includes a TimesTen readiness probe. Kubernetes runs the cat command in the tt container every 10 seconds. If the command exits with a return code of 0, the container is ready. If the command returns any other value, the container is not ready.

```
apiVersion: timesten.oracle.com/v1
kind: TimesTenClassic
metadata:
   name: sample
spec:
```



Let's discuss these readiness probes in more detail and let's look at specific use cases.

- About /tmp/active Readiness Probes
- About /tmp/readiness Readiness Probes

About /tmp/active Readiness Probes

In a TimesTen Classic active standby pair, the /tmp/active file is present in the container providing the active TimesTen database. In TimesTen Scaleout, the file is present on all instances with elements that are up and usable. In short, in TimesTen Classic and TimesTen Scaleout, the file is present in containers that have databases that can be used to run workloads.

Let's look at a use case for this type of readiness probe.

If you are using TimesTen client/server from applications within your Kubernetes cluster, you could list all the TimesTen Pods in your connection string, and the TimesTen Operator automatically routes client connections to ready instances. However, to avoid listing all TimesTen Pods in your connection string, you could create a Service that routes incoming client connections to ready instances. For this Service to work correctly, you need to use a /tmp/active readiness probe. This causes Kubernetes to only route incoming connections to appropriate TimesTen instances.

If you are using TimesTen client/server from applications outside your Kubernetes cluster, you must create such a Service. In this case, you must use a NodePort Service type. For this Service to work correctly, you need to use a /tmp/active readiness probe.

For information on a Kubernetes Service, see https://kubernetes.io/docs/concepts/services-networking/service/. For information on the NodePort Service type, see https://kubernetes.io/docs/concepts/services-networking/service/#type-nodeport.

About /tmp/readiness Readiness Probes

Readiness probes can also be useful if you want to replace one or more Nodes in your Kubernetes cluster. In this case, you can cause Kubernetes to drain the workload from the Node. This causes Kubernetes to evict any Pods that are running on that



Node and create new Pods on other Nodes in the cluster to replace them. Kubernetes supports a *Pod disruption budget* whereby you specify a budget for your application. This budget tells Kubernetes how many evicted Pods in a given Deployment can be tolerated. For example, assume you configure a Deployment with 20 replicas of your application. You could tell Kubernetes to tolerate up to 5 of the replicas being down at a time. When moving a workload from one Node to another, Kubernetes is careful not to delete more than 5 replicas at a time, and waits for their replacements to become ready before deleting more.

In the case of the TimesTen Operator, you can use the /tmp/readiness readiness probe to prevent Kubernetes from terminating both the active and standby TimesTen Classic databases simultaneously while draining Kubernetes Nodes.

If you use a Pod disruption budget of 1 on TimesTen, you can drain the workload from one or more Nodes without creating a total TimesTen outage. When Kubernetes deletes a Pod that is running TimesTen in TimesTen Classic, Kubernetes does not know if the Pod contains an active or a standby database. Therefore, it may choose to delete the Pod that contains the active database. This causes a failover to the standby, which disrupts applications if performed during normal hours. There is no way to prevent this. However, Kubernetes does not proceed to delete the other database until the one that was deleted comes back up and is completely in the Healthy state.

For more information on the health of a Pod and the Healthy state, see About Monitoring the Health of Each Pod in an Active Standby Pair.

For information on Kubernetes Pod disruption budgets, see https://kubernetes.io/docs/tasks/run-application/configure-pdb/.



4

Specify CPU and Memory Requests and Limits

This chapter discusses the importance of specifying CPU and memory requests and limits for TimesTen Classic and TimesTenScaleout objects. It also provides an understanding of Linux cgroups and gives background information about the Linux out of memory (OOM) killer.

Topics:

- About Resource Requests and Limits
- About TimesTen Containerized Deployments
- · About Specifying Requests and Limits for TimesTen Containers
- Approach 1: Use Specific Datum for Requests and Limits
- Approach 2: Use Templates for Requests and Limits
- · About Specifying Requests and Limits to Kubernetes
- About Verifying databaseMemorySize
- About Runtime Memory Monitoring

About Resource Requests and Limits

One of the core Linux technologies that is used to implement containers is cgroups. Cgroups can be used to enforce CPU and memory use limitations on a process or processes.

Kubernetes provides facilities that let you specify the amount of CPU and memory that a container consumes. When specified, Kubernetes uses your requests to do the following:

- Determine the node a particular Pod should be created on: Kubernetes determines which nodes have enough free resources to satisfy your request.
- Enforce these limits at runtime: Kubernetes ensures that applications do not exceed their requests.

Kubernetes chooses which node of the cluster to run a Pod on based on the Pod's resource requests, and the resources available on each node in the cluster. But once a Pod is scheduled onto a node, Kubernetes does not directly enforce limits at runtime. Rather, Kubernetes passes requests to Linux through cgroups. The node's Linux kernel then enforces the limits on Kubernetes behalf.

Let's look at an example of a Pod with the following definition:

```
apiVersion: v1
kind: Pod
metadata:
  name: samplePod
spec:
  containers:
  - image: container-registry.oracle.com/timesten/timesten:22.1.1.19.0
```

```
name: sample
resources:
  limits:
    cpu: 20
    memory: 41Gi
requests:
    cpu: 20
    memory: 41Gi
```

Kubernetes determines which node it will run the Pod on. It does this by examining the Pod's resources requests to determine which node has enough free resources to accommodate the Pod.

Once the node is determined, Kubernetes creates a cpu cgroup for the container (sample in this example) and configures the cgroup to have a limit of 20 CPUs. Kubernetes also creates a memory cgroup for the container and configures it to have a limit of 200 gigabytes. Kubernetes then forks off the lead process of the newly created container, and associates the initial process with the cpu and memory cgroups.

Since the lead process is associated with or running under these cgroups, that process and all its children are subject to the limits that the cgroups define. The Linux kernel on the node where the container is running automatically enforces these limits without any involvement from Kubernetes.

CPU limits are easily enforced by Linux. If an application wants to use more CPU than its limit, the kernel can choose not to dispatch the application for a period of time to keep its usage under control.

Memory limit enforcement is different than CPU enforcement. Linux has a component called the out of memory (OOM) killer. If processes exceed their intended memory usage, or if the system gets stressed, the OOM killer terminates processes abruptly.

Next, let's consider a Pod with this definition:

```
apiVersion: v1
kind: Pod
metadata:
   name: samplePod
spec:
   containers:
   - image: container-registry.oracle.com/timesten/timesten:22.1.1.19.0
   name: sample
```

In this Pod, there are no specified memory limits. The container runs in default cgroups with infinite limits. This cgroup is shared by all processes on the node that have no specified memory limit, whether the processes are running in containers or not. In this case, if the Linux node becomes memory constrained, the OOM killer chooses processes from the entire node to terminate. The victim might be TimesTen, it might be the Kubernetes kubelet, it might be some other process, or it might be all of them.



About TimesTen Containerized Deployments

As an in-memory database, TimesTen uses a large amount of memory by design. Processes that run TimesTen may be the largest memory users on a given node. If the operating system gets stressed, TimesTen is likely a prime candidate to get terminated by the Linux OOM killer. Therefore, it is crucial that memory requests and limits be specified for your TimesTen containers. TimesTen also recommends that CPU requests and limits be specified.

Note:

Ensure the value of a request and the value of a limit for a resource is the same. For example, if the memory request for the daemonlog container has a value of 30Mi ensure the memory limit for this daemonlog container also has a value of 30Mi. There are examples later in the chapter that illustrate this.

The memory request and memory limit for the tt container is the most essential and crucial to specify. The value is dependent on the memory required to hold the TimesTen database as well as the memory required for the TimesTen daemon, subdaemons, cache and replication agents, Client/Server server, and so on. The memory required to hold the database is dependent on the size of your database.

The TimesTen Operator provides functionality to accurately size your TimesTen database. This functionality is discussed later. The additional memory required for the TimesTen daemon, subdaemons, Client/Server server is dependent on your SQL and PL/SQL usage and the memory requirements vary with your workload. The TimesTen Operator provides a default of 2Gi for this additional memory. You can use this default or change it. How to change it is discussed later.

Let's take a look at the defaults for the TimesTen containers. In all cases, you have the option of changing the default.

- tt container:
 - memory: This value is discussed in detail throughout this chapter.
 - cpu: The value is dependent on how much CPU the tt container requires. This
 includes CPU used by the TimesTen daemon, subdaemons, replication agents,
 cache agents, and by the Client/Server server. The Client/Server server executes
 SQL on behalf of your applications, so the value depends on the workload. There is
 no default.
- daemonlog container:
 - memory: The default is 200Mi.
 - cpu: The default is 200m.
- exporter container (if provisioned):
 - memory: The default is 200Mi.
 - cpu: The default is 200m.

In addition, if you are using TimesTen Scaleout, there are additional TimesTen containers to consider:



- tt container of the management instance:
 - memory: The default is 3Gi.
 - cpu: The default is 1.
- zookeeper container:
 - memory: The default is 1Gi.
 - cpu: The default is 500m.

About Specifying Requests and Limits for TimesTen Containers

For TimesTen Classic and TimesTen Scaleout, the TimesTen Operator provides default values for memory and CPU requests for the <code>daemonlog</code> and <code>exporter</code> containers. For TimesTen Scaleout specifically, the TimesTen Operator provides default values for CPU and memory requests for the <code>tt</code> container of the management instance and for the <code>zookeeper</code> container. You can override these defaults by specifying specific datum in the <code>.spec.ttspec</code> section of your TimesTenClassic and TimesTenScaleout object definitions.

These datum are as follows:

- daemonLogMemoryRequest
- daemonLogCPURequest
- exporterMemoryRequest
- exporterCPURequest
- mgmtMemoryRequest: (TimesTen Scaleout)
- mgmtCPURequest: (TimesTenScaleout)
- zookeeperMemoryRequest: (TimesTen Scaleout)
- zookeeperCPURequest: (TimesTen Scaleout)

The TimesTen Operator does not provide a default value for the CPU request of a tt container. If you want to specify a value for this CPU request, use the <code>.spec.ttspec.databaseCPURequest</code> datum in your TimesTenClassic and TimesTenScaleout object definitions.

For details about these datum, see TimesTenClassicSpecSpec and TimesTenScaleoutSpecSpec.

Let's explore how the TimesTen Operator gathers information for memory and CPU requests and limits and passes the information to Kubernetes. There are two approaches:

• Use specific datum in .spec.ttspec for requests and limits: This is the default approach and the approach we recommend. The TimesTen Operator provides specific datum in the .spec.ttspec section of your TimesTenClassic and TimesTenScaleout object definitions and passes the information in these datum to Kubernetes. The TimesTen Operator also automatically determines an appropriate memory request and limit for your tt containers.



 Use templates for requests and limits: This approach uses memory and CPU requests and limits information in templates. In this approach, you specify values for memory and CPU requests for the TimesTen containers. The TimesTen Operator passes this information to Kubernetes.

The specific datum are discussed in detail in subsequent sections in this chapter.

Here is a summary list of the datum:

- automaticMemoryRequests
- databaseCPURequest
- databaseMemorySize
- additionalMemoryRequest
- memoryWarningPercent

For details about these datum, see TimesTenClassicSpecSpec and TimesTenScaleoutSpecSpec.

Approach 1: Use Specific Datum for Requests and Limits

In this approach, the TimesTen Operator automatically determines the appropriate memory request and limit for the tt containers. This is the default behavior

(.spec.ttspec.automaticMemoryRequests is set to true by default) for a TimesTenClassic or TimesTenScaleout object.

For the remaining TimesTen containers, the TimesTen Operator uses specific datum in the <code>.spec.ttspec</code> section of the TimesTenClassic and TimesTenScaleout object definitions to determine the memory request and limit and the CPU request and limit for each of the TimesTen containers. The TimesTen Operator either uses the default values for the datum or uses a value that you specify. The exception is the CPU request and limit for the <code>tt</code> container. Since there is no default, if you want to define a CPU request and limit, you must manually specify a value in the <code>.spec.ttspec.databaseCPURequest</code> datum of your TimesTenClassic and TimesTenScaleout objects. The TimesTen Operator then supplies all this information for memory and CPU requests and limits to Kubernetes.

For details about these datum, including defaults, see TimesTenClassicSpecSpec and TimesTenScaleoutSpecSpec.

It is essential that the value for the memory request for the tt container that holds the TimesTen database be accurate.

Recall that the memory request for the tt container is based on:

- Shared memory for the database: This is dependent on the size of the database.
- Additional memory: This is the memory required in addition to the database. It includes memory that is used for the TimesTen daemon, subdaemons, agents, Client/Server server.

The TimesTen Operator provides the .spec.ttspec.databaseMemorySize and .spec.ttspec.additionalMemoryRequest datum for these specific memory requirements. The .spec.ttspec.databaseMemorySize is used to specify the size of the database and the .spec.ttspec.additionalMemoryRequest is used for the additional memory.



The TimesTen Operator adds the value of .spec.ttspec.additionalMemoryRequest to the value of .spec.ttspec.databaseMemorySize. The sum is the memory request and memory limit to Kubernetes.

You do not have to specifically specify the <code>.spec.ttspec.databaseMemorySize</code> datum for a TimesTenClassic or TimesTenScaleout object. If not specified, the TimesTen Operator attempts to determine the appropriate value.

TimesTen provides the ttShmSize utility to determine the shared memory requirements of a database, given its sys.odbc.ini entry. For information about ttShmSize, see ttShmSize in the *Oracle TimesTen In-Memory Database Reference*.

The equivalent for a TimesTen sys.odbc.ini file is the TimesTen Operator db.ini metadata file. You can provide the db.ini file in several ways:

- Embed in a ConfigMap referenced in .spec.ttspec.dbConfigMap.
- Embed in a Secret referenced in .spec.ttspec.dbSecret.
- Use an init container.

For details about the facilities that you can use to provide metadata files, see Populate the /ttconfig Directory.

TimesTen recommends that you provide the <code>db.ini</code> metadata file in either a ConfigMap or a Secret. The TimesTen Operator examines the Configmaps and Secrets, if any, in your TimesTenClassic or TimesTenScaleout objects. If the <code>db.ini</code> is found in a Configmap or Secret, the TimesTen Operator uses the TimesTen <code>ttshmSize</code> utility to determine the appropriate amount of shared memory to request based on your database definition. This value is then used for

the .spec.ttspec.databaseMemorySize value. With this approach, the TimesTen Operator does the database sizing for you.

Let's look at an example:

```
kind: ConfigMap
metadata:
  name: resource9
data:
  adminUser: |
    adminuser/adminuserpwd
  schema.sql: |
    create user sampleuser identified by sampleuserpwd;
    grant admin to sampleuser;
    create table sampleuser.a (b number not null primary key, c
number, d timestamp);
    insert into sampleuser.a values(-1, -1, sysdate);
  db.ini:
    Permsize=32768
    TempSize=4096
    LogBufMB=1024
    Connections=2048
    DatabaseCharacterSet=AL32UTF8
apiVersion: timesten.oracle.com/v1
kind: TimesTenClassic
metadata:
```



```
name: recommendedoption
spec:
  ttspec:
    dbConfigMap:
    - option1
    storageClassName: standard
    storageSize: 200Gi
    image: container-registry.oracle.com/timesten/timesten:22.1.1.19.0
    imagePullSecret: sekret
    prometheus:
        insecure: true
```

In this case, the TimesTen Operator runs ttShmSize against your provided db.ini file and determines the value for .spec.ttspec.databaseMemorySize automatically. The TimesTen Operator then adds this value to the value for .spec.ttspec.additionalMemoryRequest. The sum is the memory request and memory limit to Kubernetes.

If you provide the db.ini file by using an init container or other mechanism, the TimesTen Operator cannot determine the value for <code>.spec.ttspec.databaseMemorySize</code>. By the time the Pod is provisioned and the init container is executed, the Pod has already been created and its memory requirements defined. In such cases, you must manually provide the <code>.spec.ttspec.databaseMemorySize</code> as part of your YAML.

TimesTen recommends that you use the ttShmSize utility in a TimesTen instance outside of Kubernetes to determine the appropriate value for .spec.ttspec.databaseMemorySize. You do not need to create the database.

This example assumes you have created a TimesTen instance outside of Kubernetes and have created a DSN in your sys.odbc.ini file with the name database1. Use the ttShmSize utility based on provided values for the PermSize, TempSize, LogBufMB, and Connections connection attributes.

```
ttShmSize -connstr "DSN=database1;PermSize=32768;TempSize=4096;LogBufMB=1024;Connections=2048" The required shared memory size is 39991547720 bytes.
```

Specify this value in the .spec.ttspec.databaseMemorySize datum.

Let's look at an example that uses an init container and uses the calculated value for .spec.ttspec.databaseMemorySize.

```
apiVersion: timesten.oracle.com/v1
kind: TimesTenClassic
metadata:
   name: init1
spec:
   ttspec:
    databaseMemorySize: 41Gi
   storageClassName: standard
   storageSize: 200Gi
   image: container-registry.oracle.com/timesten/timesten:22.1.1.19.0
   imagePullSecret: sekret
   prometheus:
    insecure: true
```



```
template:
  spec:
   initContainers:
    - name: initla
      command:
      - sh
      - "-c"
      - |
        /bin/bash <<'EOF'
        echo adminuser/adminuserpwd > /ttconfig/adminUser
        echo PermSize=32768 > /ttconfig/db.ini
        echo TempSize=4096 > /ttconfig/db.ini
        echo LogBufMB=1024 > /ttconfig/db.ini
        echo Connections=2048 > /ttconfiq/db.ini
        echo DatabaseCharacterSet=AL32UTF8 >> /ttconfig/db.ini
       ls -1 /ttconfig
       EOF
      volumeMounts:
      - name: tt-config
       mountPath: /ttconfig
    - name: tt-config
      emptyDir: {}
```

In this case, the TimesTen Operator uses the value you specified for <code>.spec.ttspec.databaseMemorySize</code> to determine the size of the shared memory segment to hold the TimesTen database. The TimesTen Operator then adds this value to the value for <code>.spec.ttspec.additionalMemoryRequest</code>. The sum is the <code>memory</code> request and <code>memory</code> limit to Kubernetes.



In TimesTen Scaleout, the <code>sys.odbc.ini</code> file (and corresponding <code>db.ini</code> file) define the size of a single element of the database, not the entire database. When provisioning a TimesTenScaleout object, the TimesTen Operator uses the provided data in the same manner as it does for a TimesTenClassic object.

Approach 2: Use Templates for Requests and Limits

This approach uses a template for specifying resource requests and limits. To enable this behavior, set the <code>.spec.ttspec.automaticMemoryRequests</code> datum to <code>false</code> for your TimesTenClassic or TimesTenScaleout object.

In your YAML for TimesTenClassic and TimesTenScaleout objects, you can specify a template for Pods. In this template, you specify attributes of various containers in the Pods, including the tt container. If you specify a template for one or more containers, the resource requests and limits for the containers are used by Kubernetes.

TimesTen recommends that you use the ttShmSize utility in a TimesTen instance outside of Kubernetes to determine the appropriate value for the memory request and limit for the tt container. You do not need to create the database.

This example assumes you have created a TimesTen instance outside of Kubernetes and have created a DSN in your <code>sys.odbc.ini</code> file with the name <code>database1</code>. Use the <code>ttShmSize</code> utility based on provided values for the <code>PermSize</code>, <code>TempSize</code>, <code>LogBufMB</code>, and <code>Connections</code> connection attributes.

```
ttShmSize -connstr "DSN=database1;PermSize=32768;TempSize=4096;LogBufMB=1024;Connections=2048" The required shared memory size is 39991547720 bytes.
```

For information about ttShmSize, see ttShmSize in the Oracle TimesTen In-Memory Database Reference.

Let's look at an example:

```
apiVersion: timesten.oracle.com/v1
kind: TimesTenClassic
metadata:
  name: resource1
spec:
  ttspec:
    storageClassName: standard
    storageSize: 100Gi
    image: container-registry.oracle.com/timesten/timesten:22.1.1.19.0
    imagePullSecret: sekret
    prometheus:
      insecure: true
  template:
    spec:
      containers:
      - name: tt
        resources:
          requests:
            memory: "41Gi"
                    "20"
            cpu:
          limits:
            memory: "41Gi"
                     "20"
            cpu:
      - name: daemonlog
        resources:
          requests:
            memory: "30Mi"
                    "210"
            cpu:
          limits:
            memory: "30Mi"
            cpu:
                    "210"
      - name: exporter
        resources:
          requests:
            memory: "22Mi"
                    "310m"
            cpu:
          limits:
            memory: "22Mi"
            cpu:
                    "310m"
```



In this example, cpu and memory requests and limits for the tt, daemonlog, and exporter containers are included in the template. These resources are specified to Kubernetes.

About Specifying Requests and Limits to Kubernetes

The TimesTen Operator follows a specific order in determining the cpu and memory request and limits to Kubernetes:

- For the tt container that holds your TimesTen database, the TimesTen Operator looks for the following in this order:
 - If you specify a template, the TimesTen Operator uses the values in it.
 - If you specify .spec.ttspec.databaseMemorySize, the TimesTen Operator uses its value.
 - If there is a db.ini file, the TimesTen Operator uses the values in it.
 - If none of the above are true, the TimesTen Operator uses the default.

In addition, if you specified a value for <code>.spec.ttspec.databaseCPURequest</code>, that value is used as the <code>cpu</code> request and <code>cpu</code> limit to Kubernetes.

- If you specify resource requests or limits for the daemonlog container in your container templates in your TimesTenClassic or TimesTenScaleout object, the TimesTen Operator honors those requests. If you do not, the TimesTen Operator uses the values you supply in your object's .spec.ttspec.daemonLogMemoryRequest and .spec.ttspec.daemonLogCPURequest datum.
- If you specify resource requests or limits for the exporter container in your container templates in your TimesTenClassic or TimesTenScaleout object, the TimesTen Operator honors those requests. If you do not, the TimesTen Operator uses the values you supply in your object's .spec.ttspec.exporterMemoryRequest and .spec.ttspec.exporterCPURequest datum.
- If you specify a template for the tt container in the mgmtTemplate in a TimesTenScaleout object, the TimesTen Operator uses the resource data in that template. If you do not, the TimesTen Operator uses the values you supply in your object's .spec.ttspec.mgmtMemoryRequest and .spec.ttspec.mgmtCPURequest datum.
- If you specify a template for the zookeeper container in the zookeeperTemplate in a TimesTenScaleout object, the TimesTen Operator uses the resource data in that template. If you do not, the TimesTen Operator uses the values you supply in your object's .spec.ttspec.zookeeperMemoryRequest and .spec.ttspec.zookeeperCPURequest datum.

About Verifying databaseMemorySize

Whether specified by you or determined by the TimesTen Operator, before a database is created, the TimesTen Operator and the TimesTen agent checks that the $t\bar{t}$ containers in the relevant TimesTen Pods have the memory resources required to create the database. The TimesTen Operator accomplishes this by running the



TimesTen ttShmSize utility and comparing it with the memory quotas in the tt container's cgroup.

If the required resources are not available, the TimesTen Operator returns an error message (as an Event) and moves the TimesTenClassic or TimesTenScaleout object to the Failed state.

This checking is performed even if the value of .spec.ttspec.automaticMemoryRequests is false.

About Runtime Memory Monitoring

The TimesTen Operator monitors the memory usage of TimesTen Pods at runtime. It informs you of the following:

- If any tt containers are approaching their specified memory limits.
- If any TimesTen containers have been terminated by the Linux OOM killer.

Kubernetes Events are generated to report on these conditions.

Every .spec.ttspec.pollingInterval seconds, the TimesTen agent in each tt container queries the container's underlying Linux cgroup to determine the cgroup's memory.limit_in_bytes and memory.usage_in_bytes and reports these values to the TimesTen Operator. The Kubernetes status of each container is similarly queried. The TimesTen Operator uses this data to generate appropriate Events as needed.

If the usage is greater than .spec.ttspec.memoryWarningPercent of the limit, an Event is generated to notify you. In addition, if the TimesTen Operator observes that one or more of the TimesTen related containers have been terminated or restarted (by the OOM killer or otherwise), the TimesTen Operator reports the observation by using appropriate Events.



5

Deploy TimesTen Classic Databases

You can deploy TimesTen Classic databases by using Helm or by using the procedures in this chapter. If you are using Helm to deploy TimesTen Classic databases, see Use Helm to Deploy the TimesTen Kubernetes Operator and TimesTenClassic Objects.

This chapter discusses the process for deploying active standby pairs of TimesTen databases. It describes the process for creating TimesTenClassic objects in your environment. It also provides examples that demonstrate how to monitor the provisioning of the active standby pair of TimesTen databases. The chapter concludes with examples that show you how to connect to the database and run operations in it.

Topics:

- About the Deployment Process
- Define and Create a TimesTenClassic Object
- Monitor Progress of an Active Standby Pair Deployment

About the Deployment Process

The TimesTen Operator extends the Kubernetes API to provide the TimesTenClassic object type. This type provides the definitions you need to successfully deploy your TimesTen databases to the Kubernetes cluster. You customize these definitions for your particular environment. Specifically, you create a YAML file and, in it, you specify the required TimesTenClassic definitions for the TimesTenClassic object. By assigning values to the fields of these definitions, you customize and define your deployment environment. For example, when you supply the oci-bv value for the storageClassName field, you are telling the Operator the name of the storage class you want to use. See "The TimesTen Kubernetes Operator Object Types" for the object definitions, and the fields that you define in your YAML file.

Examples of the YAML file were introduced previously when discussing ConfigMaps and Secrets, an init container, and other configuration options. (See "Using ConfigMaps and Secrets" for information on ConfigMaps and Secrets. Also see "Using an init container" and "Additional Configuration Options" for other configuration options.) However, "Define and Create a TimesTenClassic Object" shows you how to define the TimesTenClassic object in detail.

After specifying your configuration in the YAML file, you use the kubectl create command from your Linux development host to create the corresponding TimesTenClassic object in your cluster. After you issue this command, the process for deploying your active standby pair of TimesTen databases begins. You can view this process by issuing kubectl get and kubectl describe commands, such as, kubectl get pods and kubectl describe timestenclassic. Once your databases are deployed, you can then connect to your active database, issue queries, and perform other operations to verify your database is working as it should.



Define and Create a TimesTenClassic Object

Defining your environment involves creating TimesTenClassic objects with attributes customized for your environment. The fields include the name of the image pull secret, the name of your TimesTen image, and the other definitions required to successfully deploy your TimesTen databases. See "About the TimesTenClassic Object Type" for information on defining objects of type TimesTenClassic.

Perform these steps to define and create the TimesTenClassic object:

1. Create an empty YAML file. You can choose any name, but you may want to use the same name you used for the name of the TimesTenClassic object. (In this example, sample.) The YAML file contains the definitions for the TimesTenClassic object. See "TimesTenClassicSpecSpec" for information on the fields that you must specify in this YAML file as well as the fields that are optional.

In this example, replace the following. (The values you can replace are represented in **bold**.)

- name: Replace sample with the name of your TimesTenClassic object.
- storageClassName: Replace oci-bv with the name of the storage class used to allocate PersistentVolumes to hold TimesTen.
- storageSize: Replace 250Gi with the amount of storage that should be requested for each Pod to hold TimesTen. (This example assumes a production environment and uses 250Gi for storage. For demonstration purposes, you can use 50Gi of storage. See the storageSize and the logStorageSize entries in "Table 17-3" for information.)
- image: Replace container-registry.oracle.com/timesten/ timesten:22.1.1.19.0 with the location and name of your image. In this example, container-registry.oracle.com/timesten is the location of the image registry and timesten:22.1.1.19.0 is the name of the image.
- imagePullSecret: Replace sekret with the image pull secret that Kubernetes should use to fetch the TimesTen image.
- dbConfigMap: This example uses one ConfigMap (called sample) for the
 db.ini, the adminUser, and the schema.sql metadata files. This ConfigMap
 will be included in the ProjectedVolume. This volume is mounted as /ttconfig
 in the TimesTen containers. See "Using ConfigMaps and Secrets" and
 "Example Using One ConfigMap" for information on ConfigMaps.

```
% vi sample.yaml
apiVersion: timesten.oracle.com/v1
kind: TimesTenClassic
metadata:
   name: sample
spec:
   ttspec:
   storageClassName: oci-bv
   storageSize: 250Gi
   image: container-registry.oracle.com/timesten/timesten:22.1.1.19.0
   imagePullSecret: sekret
   dbConfigMap:
   - sample
```



2. Use the kubectl create command to create the TimesTenClassic object from the contents of the YAML file (in this example, sample.yaml). Doing so begins the process of deploying your active standby pair of TimesTen databases in the Kubernetes cluster.

```
% kubectl create -f sample.yaml
timestenclassic.timesten.oracle.com/sample created
```

You successfully created the TimesTenClassic object in the Kubernetes cluster. The process of deploying your TimesTen databases begins, but is not yet complete.

Monitor Progress of an Active Standby Pair Deployment

You can use various kubectl commands to monitor the progress of the active standby pair deployment. After the deployment is complete and successful, you can connect to the database and run operations in it to verify it is working as it should.

- Monitor the State of a TimesTenClassic Object
- Verify Underlying Objects Exist
- Verify Connection to Active Database

Monitor the State of a TimesTenClassic Object

Use the kubectl get and the kubectl describe commands to monitor the progress of the active standby pair as it is provisioned.

Note:

For the kubectl get timestenclassic and kubectl describe timestenclassic commands, you can alternatively specify kubectl get ttc and kubectl describe ttc respectively. timestenclassic and ttc are synonymous when used in these commands, and return the same results. The first kubectl get and the first kubectl describe examples in this chapter use timestenclassic. The remaining examples in this book use ttc for simplicity.

1. Use the kubectl get command and review the STATE field. Observe the value is Initializing. The active standby pair provisioning has begun, but is not yet complete.

```
% kubectl get timestenclassic sample
NAME STATE ACTIVE AGE
sample Initializing None 11s
```

2. Use the kubectl describe command to view the initial provisioning in detail.

```
% kubectl describe timestenclassic sample
Name: sample
Namespace: mynamespace
Labels: <none>
Annotations: <none>
API Version: timesten.oracle.com/v1
Kind: TimesTenClassic
Metadata:
   Creation Timestamp: 2023-04-30T15:35:12Z
   Generation: 1
```



```
Resource Version: 20231755
 Self Link:
/apis/timesten.oracle.com/v1/namespaces/mynamespace/timestenclassics/sample
 UID:
                     517a8646-a354-11ea-a9fb-0a580aed5e4a
Spec:
 Ttspec:
   Db Config Map:
     sample
                       container-registry.oracle.com/timesten/
   Image:
timesten:22.1.1.19.0
   Image Pull Policy: Always
   Image Pull Secret:
                      sekret
   Storage Class Name: oci-bv
   Storage Size:
                       250Gi
Status:
 Active Pods: None
 High Level State: Initializing
             3
 Last Event:
 Pod Status:
   Cache Status:
     Cache Agent:
                       Down
     Cache UID Pwd Set: false
     N Cache Groups:
                       0
   Db Status:
     Db:
                   Unknown
     Db Id:
     Db Updatable: Unknown
   Initialized: true
   Pod Status:
     Agent:
                          Down
     Last Time Reachable: 0
     Pod IP:
     Pod Phase:
                          Pending
   Replication Status:
     Last Time Rep State Changed: 0
     Rep Agent:
     Rep Peer P State:
                                 Unknown
     Rep Scheme:
                                 Unknown
     Rep State:
                                 Unknown
   Times Ten Status:
     Daemon: Down
                    Unknown
     Instance:
     Release:
                   Unknown
   Admin User File: false
   Cache User File: false
   Cg File:
                    false
   High Level State: Down
   Intended State: Active
   Name:
                    sample-0
   Schema File:
                    false
   Cache Status:
     Cache Agent:
                       Down
     Cache UID Pwd Set: false
     N Cache Groups:
   Db Status:
                   Unknown
     Db:
     Db Id:
     Db Updatable: Unknown
   Initialized:
                   true
   Pod Status:
     Agent:
                          Down
```



```
Last Time Reachable: 0
     Pod IP:
     Pod Phase:
                         Pending
   Replication Status:
     Last Time Rep State Changed: 0
     Rep Agent:
                                 Down
     Rep Peer P State:
                                Unknown
     Rep Scheme:
                                 Unknown
     Rep State:
                                 Unknown
   Times Ten Status:
                    Down
Unknown
     Daemon:
               Unknown
     Instance:
     Release:
   Admin User File: false
Cache User File: false
   Cg File:
                       false
   High Level State: Unknown
   Intended State: Standby
   Name:
                     sample-1
   Schema File:
                      false
 Rep Create Statement: create active standby pair "sample" on
 "sample-0.sample.mynamespace.svc.cluster.local", "sample" on
"sample-1.sample.mynamespace.svc.cluster.local" NO RETURN store "sample" on
"sample-0.sample.mynamespace.svc.cluster.local" PORT 4444 FAILTHRESHOLD 0
store "sample" on "sample-1.sample.mynamespace.svc.cluster.local" PORT 4444
FAILTHRESHOLD 0
                       4444
 Rep Port:
 Status Version:
                     1.0
Events:
 Type Reason Age From
                             Message
 ---- ----- ----
      Create 50s ttclassic Secret tt517a8646-a354-11ea-a9fb-0a580aed5e4a
created
     Create 50s ttclassic Service sample created
       Create 50s ttclassic StatefulSet sample created
```

3. Use the kubectl get command again to see if value of the STATE field has changed. In this example, the value is Normal, indicating the active standby pair of databases are now provisioned and the process is complete.

```
% kubectl get ttc sample
NAME STATE ACTIVE AGE
sample Normal sample-0 3m5s
```

4. Use the kubectl describe command again to view the active standby pair provisioning in detail.

Note: In this example, the now Normal line displays on its own line. In the actual output, this line does not display as its own line, but at the end of the StateChange previous line.

```
% kubectl describe ttc sample
Name: sample
Namespace: mynamespace
Labels: <none>
Annotations: <none>
API Version: timesten.oracle.com/v1
Kind: TimesTenClassic
Metadata:
   Creation Timestamp: 2023-04-30T15:35:12Z
Generation: 1
Resource Version: 20232668
Self Link:
```



```
/apis/timesten.oracle.com/v1/namespaces/mynamespace/timestenclassics/sample
                     517a8646-a354-11ea-a9fb-0a580aed5e4a
 UID:
Spec:
 Ttspec:
   Db Config Map:
     sample
   Image:
                       container-registry.oracle.com/timesten/
timesten:22.1.1.19.0
   Image Pull Policy: Always
   Image Pull Secret: sekret
   Storage Class Name: oci-bv
                      250Gi
   Storage Size:
Status:
 Active Pods:
                sample-0
 High Level State: Normal
 Last Event:
 Pod Status:
   Cache Status:
     Cache Agent:
                      Not Running
     Cache UID Pwd Set: true
     N Cache Groups:
   Db Status:
                  Loaded
     Db:
     Db Id:
                  26
     Db Updatable: Yes
   Initialized: true
   Pod Status:
     Agent:
                         Uρ
     Last Time Reachable: 1590939597
     Pod IP:
                         192.0.2.1
     Pod Phase:
                         Running
   Replication Status:
     Last Time Rep State Changed: 0
     Rep Agent:
                                 Running
     Rep Peer P State:
     Rep Scheme:
                                 Exists
     Rep State:
                                 ACTIVE
   Times Ten Status:
     Daemon: Up
                    Exists
     Instance:
     Release:
                    22.1.1.19.0
   Admin User File: true
   Cache User File: false
   Cq File:
                    false
   High Level State: Healthy
   Intended State: Active
   Name:
                    sample-0
   Schema File:
                   true
   Cache Status:
     Cache Agent:
                      Not Running
     Cache UID Pwd Set: true
     N Cache Groups:
   Db Status:
     Db:
                  Loaded
     Db Id:
                  26
     Db Updatable: No
   Initialized:
   Pod Status:
     Agent:
                         Uр
     Last Time Reachable: 1590939597
     Pod IP:
                         192.0.2.2
```



```
Pod Phase:
                          Running
    Replication Status:
      Last Time Rep State Changed: 1590939496
      Rep Agent:
                                     Running
     Rep Peer P State:
                                    start
     Rep Scheme:
                                    Exists
     Rep State:
                                    STANDBY
    Times Ten Status:
      Daemon:
                       Exists
      Instance:
                        22.1.1.19.0
      Release:
    Admin User File:
                        true
    Cache User File:
                         false
    Cq File:
                         false
    High Level State: Healthy
    Intended State: Standby
   Name:
                        sample-1
    Schema File:
                         true
 Rep Create Statement: create active standby pair "sample" on
"sample-0.sample.mynamespace.svc.cluster.local", "sample" on
"sample-1.sample.mynamespace.svc.cluster.local" NO RETURN store "sample" on
"sample-0.sample.mynamespace.svc.cluster.local" PORT 4444 FAILTHRESHOLD 0
store "sample" on "sample-1.sample.mynamespace.svc.cluster.local" PORT 4444
FAILTHRESHOLD 0
 Rep Port:
                         4444
 Status Version:
                         1.0
 Type Reason
                   Age From
                                      Message
       Create
                   4m43s ttclassic Secret tt517a8646-a354-11ea-
a9fb-0a580aed5e4a created
      Create 4m43s ttclassic Service sample created
Create 4m43s ttclassic StatefulSet sample created
       StateChange 3m47s ttclassic Pod sample-0 Daemon Unknown
       StateChange 3m47s ttclassic Pod sample-0 CacheAgent Unknown StateChange 3m47s ttclassic Pod sample-0 RepAgent Unknown StateChange 3m47s ttclassic Pod sample-1 Daemon Unknown
       {\tt StateChange} \quad {\tt 3m47s} \quad {\tt ttclassic} \quad {\tt Pod sample-1} \quad {\tt CacheAgent} \quad {\tt Unknown}
       StateChange 3m47s ttclassic Pod sample-1 RepAgent Unknown
       StateChange 3m26s ttclassic Pod sample-0 Agent Up
        StateChange 3m26s ttclassic Pod sample-0 Release 22.1.1.19.0
        StateChange 3m26s ttclassic Pod sample-0 Daemon Down
        StateChange 3m26s ttclassic Pod sample-1 Agent Up
        StateChange 3m26s ttclassic Pod sample-1 Release 22.1.1.19.0
       StateChange 3m26s ttclassic Pod sample-1 Daemon Down
        StateChange 3m26s ttclassic Pod sample-0 Daemon Up
        StateChange 3m25s ttclassic Pod sample-1 Daemon Up
        StateChange 2m13s ttclassic Pod sample-0 RepState IDLE
       StateChange 2m13s ttclassic Pod sample-0 Database Updatable
        StateChange 2m13s ttclassic Pod sample-0 CacheAgent Not Running
        StateChange 2m13s ttclassic Pod sample-0 RepAgent Not Running
       StateChange 2m13s ttclassic Pod sample-0 RepScheme None
       StateChange 2m13s ttclassic Pod sample-0 Database Loaded
       StateChange 2m11s ttclassic Pod sample-0 RepAgent Running
        StateChange 2m10s ttclassic Pod sample-0 RepScheme Exists
        StateChange 2m10s ttclassic Pod sample-0 RepState ACTIVE
       StateChange 113s ttclassic Pod sample-1 Database Loaded
        StateChange 113s ttclassic Pod sample-1 Database Not Updatable
       StateChange 113s ttclassic Pod sample-1 CacheAgent Not Running
       StateChange 113s ttclassic Pod sample-1 RepAgent Not Running
        StateChange 113s ttclassic Pod sample-1 RepScheme Exists
```



```
- StateChange 113s ttclassic Pod sample-1 RepState IDLE
- StateChange 106s ttclassic Pod sample-1 RepAgent Running
- StateChange 101s ttclassic Pod sample-1 RepState STANDBY
- StateChange 101s ttclassic TimesTenClassic was Initializing, now Normal
```

Your active standby pair of TimesTen databases are successfully deployed (as indicated by Normal.) There are two TimesTen databases, configured as an active standby pair. One database is active. (In this example, sample-0 is the active database, as indicated by Rep State ACTIVE). The other database is standby. (In this example, sample-1 is the standby database as indicated by Rep State STANDBY). The active database can be modified and queried. Changes made on the active database are replicated to the standby database. If the active database fails, the Operator automatically promotes the standby database to be the active. The formerly active database will be repaired or replaced, and will then become the standby.

Verify Underlying Objects Exist

The Operator creates other underlying objects automatically. Verify that these objects are created.

StatefulSet:

```
% kubectl get statefulset sample
NAME    READY    AGE
sample    2/2    8m21s
```

2. Service:

3. Pods:

4. PersistentVolumeClaims (PVCs):

```
% kubectl get pvc
NAME
                           STATUS VOLUME
CAPACITY ACCESS MODES STORAGECLASS AGE
tt-persistent-sample-0
                         Bound
ocid1.volume.oc1.phx.abyhqljrbxcgzyixa4pmmcwiqxgqclc7gxvdnoty367w2qn26tij6kfp
6qq
250Gi
           RWO
                          oci-bv
                                        10m
tt-persistent-sample-1
                          Bound
ocid1.volume.oc1.phx.abyhqljtt4qxxoj5jqiskriskh66hakaw326rbza4uigmuaezdnu53qh
h
oaa
250Gi
           RWO
                          oci-bv
                                        10m
```

Verify Connection to Active Database

You can run the kubectl exec command to invoke shells in your Pods and control TimesTen, which is running in those Pods. By default, TimesTen runs in the Pods as

the timesten user. Once you have established a shell in the Pod, verify you can connect to the sample database, and that the information from the metadata files is correct. You can optionally run queries against the database or any other operations.

1. Establish a shell in the Pod.

```
% kubectl exec -it sample-0 -c tt -- /bin/bash
```

2. Connect to the sample database. Verify the information in the metadata files is in the database correctly. For example, attempt to connect to the database as the sampleuser user. Check that the PermSize value of 200 is correct. Check that the sampleuser.emp table exists.

```
% ttIsql sample
Copyright (c) 1996, 2023, Oracle and/or its affiliates. All rights reserved.
Type ? or "help" for help, type "exit" to quit ttIsql.
connect "DSN=sample";
Connection successful:
DSN=sample; UID=timesten; DataStore=/tt/home/timesten/datastore/sample;
DatabaseCharacterSet=AL32UTF8; ConnectionCharacterSet=AL32UTF8; PermSize=200;
DDLReplicationLevel=3;
(Default setting AutoCommit=1)
Command> connect adding "uid=sampleuser;pwd=samplepw" as sampleuser;
Connection successful:
DSN=sample;UID=sampleuser;DataStore=/tt/home/timesten/datastore/sample;
DatabaseCharacterSet=AL32UTF8; ConnectionCharacterSet=AL32UTF8; PermSize=200;
DDLReplicationLevel=3;
(Default setting AutoCommit=1)
sampleuser: Command> tables;
 SAMPLEUSER.EMP
1 table found.
```



6

Deploy TimesTen Scaleout Databases

The TimesTen Operator supports the deployment of a TimesTen Scaleout grid and associated databases in your Kubernetes cluster.

This chapter provides background information about the deployment process. It summarizes the planning process for configuring a grid and shows you how to apply that plan when configuring a grid in the Kubernetes environment. It describes the steps the TimesTen Operator takes to deploy and provision a grid based on the information you provide. Use this information to gain an understanding of how the Operator functions when deploying your TimesTen Scaleout grid.

The second part of the chapter provides you with an end-to-end example that shows you the steps to deploy your grid in the Kubernetes cluster.

If you want to advance directly to the example, see Deploy a Grid.

The TimesTen Operator also supports TimesTen Cache in TimesTen Scaleout. See Work with TimesTen Cache.



You cannot use Helm to deploy TimesTen Scaleout databases. Instead, use the procedures in this chapter.

Topics:

- About Deploying a Grid
- Deploy a Grid

About Deploying a Grid

The information in this section provides background information about configuring and deploying a grid in the Kubernetes environment.

Topics:

- About Planning a Grid
- About Configuring a Grid
- About Provisioning a Grid
- About ssh
- About Creating a Grid



About Planning a Grid

One of the features of the TimesTen Operator is the ability for it to provision a TimesTen Scaleout grid and its database in the Kubernetes cluster. Just like in any other TimesTen Scaleout environment, you must do some planning for your grid.

Here are some considerations:

- K-Safety (represented by k): How many copies of your TimesTen database? The
 K-Safety factor determines the number of data spaces in your grid. For example, if
 you set k to 2, there are two copies of your database: one copy resides in data
 space one and the second copy in data space two.
- Replica sets: How many replica sets in your grid? A replica set contains k
 elements, where each element in the replica set is an exact copy of the other
 elements in the replica set. The value of k, combined with the number of replica
 sets, determines the number of data instances in the grid. For example, if you set
 k to 2, and replica sets to 3, then there are six data instances in the grid.
- ZooKeeper instances: How many ZooKeeper instances for the grid?
- Database definition file (DbDef): What data store and first connection attributes are needed for the database in the grid?
- Direct connectable: What general connection attributes are needed for the database when using direct access?
- Client/server connectable: What general connection attributes are needed for the database when using client/server access?

After you define your configuration, you provide that information to the TimesTen Operator. The Operator takes over from there. It automatically does the provisioning and the deployment of the grid and database for you.

About Configuring a Grid

The TimesTen Operator provides the TimesTenScaleout object type and configuration metadata so that you can define and then deploy your TimesTen Scaleout grid and database. The TimesTenScaleout object type provides the syntax for configuring your grid. The configuration metadata lets you define the connection attributes for your database. Taken together, the Operator has the necessary information to provision your grid and database in the Kubernetes cluster.

Based on your planned configuration in About Planning a Grid, you can apply that configuration to the Kubernetes environment:

- K-Safety (k): The Operator provides the .spec.ttspec.k element as part of the syntax for the TimesTenScaleout object type. You specify k in the YAML manifest file for your TimesTenScaleout object.
- Replica sets: The Operator provides the .spec.ttspec.nReplicaSets element as
 part of the syntax for the TimesTenScaleout object type. You specify nReplicaSets
 in the YAML manifest file for your TimesTenScaleout object.
- ZooKeeper instances: The Operator provides the .spec.ttspec.nZookeeper element as part of the syntax for the TimesTenScaleout object type. You specify nZookeeper in the YAML manifest file for your TimesTenScaleout object.



- Database definition file (DbDef): The Operator creates a DbDef from the contents of the db.ini metadata file. You create this metadata file and then use a Kubernetes facility (or some other means) to place this file in the /ttconfig directory of the tt containers.
- One or more direct connectables: The Operator creates one or more direct connectables from the contents of the *.connect metadata files. You create one or more of these *.connect files and then use a Kubernetes facility (or some other means) to place the files in the /ttconfig directory of the tt containers.
- One or more client/server connectables: The Operator creates one or more client/server connectables from the contents of the *.csconnect metadata files. You create one or more of these *.csconnect files and then use a Kubernetes facility (or some other means) to place the files in the /ttconfig directory of the tt containers.

See TimesTenScaleoutSpecSpec, List of Configuration Metadata, and Populate the /ttconfig Directory.

After the metadata files are placed in the /ttconfig directory of the tt containers, and you configure and then deploy your TimesTenScaleout object in the Kubernetes cluster, Kubernetes informs the Operator that a TimesTenScaleout object has been created. The Operator begins the process of creating additional Kubernetes objects in order to implement your grid.

About Provisioning a Grid

The TimesTen Operator gathers the information from the TimesTenScaleout object and begins instantiating the TimesTen Scaleout grid and database. It creates the following StatefulSets:

- One StatefulSet that provides the management instance for the grid. The Operator supports one management instance. The underlying Pod for this management instance is also created.
- One StatefulSet that provides one or more ZooKeeper instances. The Operator determines the number of ZooKeeper instances by the value you specified for the nZookeeper field in your TimesTenScaleout object definition. For example, if you specified a value of 3 for nZookeeper, the Operator creates one StatefulSet with three replicas. The underlying Pods for these ZooKeeper instances are also created. There is one Pod per ZooKeeper instance.
- Additional StatefulSets, the number of which is determined by the value you specified for the k field in your TimesTenScaleout object definition. For example, if you specified a value of 2 for k, the Operator creates two StatefulSets. These StatefulSets provide data instances for the grid. Each of the k StatefulSets provides Pods to implement a single data space in the resultant grid. The StatefulSet has M replicas, the number of which is determined by the value you specified for the nReplicaSets field in your TimesTenScaleout object definition. For example, if you set nReplicaSets to 3, each StatefulSet has three replicas. This number of replicas determines the number of replica sets in the resultant grid.

In the preceding example, one StatefulSet has three replicas. This one StatefulSet contains three data instances in data space one. A Pod is created for each data instance, so there are three Pods created. The second StatefulSet contains three data instances in data space two. A Pod is created for each data instance, so there are three Pods created. There are a total of six total Pods created for the six data instances.

In addition, the Operator creates the following Kubernetes headless Services:



- One headless Service that provides DNS names for the Pods that contain the management and data instances. This service enables client/server access to the Pods using the TimesTen client/server port 6625.
- One headless Service that provides DNS names for the Pods that contain the ZooKeeper instances. This service enables access to the ZooKeeper internal ports 2888 and 3888, as well as the external port 2181.

There is an example of these StatefulSets and headless Services in Verify Underlying Objects.

The Operator also creates Persistent Volume Claims (PVCs) for the Pods. These PVCs cause persistent volumes to be allocated by Kubernetes and attached to the TimesTen Pods and ZooKeeper Pods. See Persistent Storage.

Pods that run ZooKeeper consists of a single container called <code>zookeeper</code>. Each Pod that is running TimesTen consists of at least two containers. The <code>tt</code> container runs the TimesTen agent and TimesTen. The <code>daemonlog</code> container writes the TimesTen daemon log to stdout.

As the tt containers in the TimesTen Pods start, the Operator assembles them into a working grid. The grid's model is configured with several objects, including:

- Hosts for the data instances in each of the data space groups
- Each host configured with an installation of TimesTen
- Each host configured with a single TimesTen instance
- A DbDef (the contents of which are from the db.ini file)
- Direct mode connectables, if any, (the contents of which are from the *.connect files)
- Client/server connectables, if any, (the contents of which are from the *.csconnect files)

About ssh

A TimesTen Scaleout grid relies on password-less ssh among the instances of the grid. The TimesTen Operator automatically configures password-less ssh among the $t\bar{t}$ containers in the grid in your Kubernetes environment. There is no intervention that you need to do.

About Creating a Grid

When creating the grid, the TimeTen Operator transitions to and from various High Level states. Here is an explanation of these states:

After you create your TimesTenScaleout object in the Kubernetes cluster, the TimesTen Operator creates the StatefulSets and Services that are required to deploy your TimesTenScaleout grid and database. The Operator assigns a High Level state of Initializing to the TimesTenScaleout object.

The Operator periodically polls the status of the StatefulSets' objects and their underlying Pods. When the ZooKeeper Pods are ready, the TimesTenScaleout object transitions from the Initializing state to the ZooKeeperReady state.



When the TimesTen agent in the management Pod starts up, the Operator instructs the agent to create a TimesTen instance and grid. The TimesTenScaleout object transitions to the <code>GridCreated state</code>.

The Operator waits for all of the TimesTen agents in all of the Pods to start. Once all have started, the Operator instructs the TimesTen agent in the management instance to create the hosts, the installations, and the instances in the grid's model for the data instances in the grid.

The DbDef is then created from the contents of the db.ini file. The direct connectables are created from the contents of the *.connect files. The client/server connectables are created from the contents of the *.csconnect files.

The model is applied and the data instances of the grid are created. The TimesTenScaleout object transitions to the InstanceCreated state.

The Operator then instructs the management instance to create the database (by using the TimesTen ttGridAdmin utility with the dbCreate option) and to create the initial distribution map (by using the TimesTen ttGridAdmin utility with the dbDistribute -add all -apply options). The TimesTenScaleout object then transitions to the DbCreated state.

The Operator then instructs the TimesTen agent in one data instance to run the TimesTen ttlsql utility to create the user in the adminUser file and run the schema.sql file (if you provided these files). The TimesTenScaleout object transitions to the Normal state.

The grid and databases are created. The TimesTen agent then opens the database for connections.

The Operator manages and monitors the TimesTenScaleout objects after they are deployed in your Kubernetes cluster. The Operator also detects, repairs, and recovers from failures in your grid and associated databases. See Manage TimesTen Scaleout.

There is an example showing the Operator transitioning to and from these High Level states in Monitor the High Level State of a TimesTenScaleout Object.

Deploy a Grid

This section provides a step by step walk-through that shows you how to create and deploy a TimesTen Scaleout grid and database in your Kubernetes cluster. The walk-through starts with an example that shows you how to create metadata files and create a Kubernetes ConfigMap. It continues with an example that shows you how to create a YAML file that contains the definitions for your TimesTenScaleout object. It shows you how to deploy that YAML file in your Kubernetes cluster. You learn how to monitor the provisioning of the TimesTen grid and database, and verify the underlying Kubernetes objects were created by the TimesTen Operator. The walk-through completes with one example that shows you how to connect to the TimesTen database and run operations in it. The final example shows you how to connect to the management instance to verify the health of the database and its elements.

- Create Configuration Metadata and a Kubernetes ConfigMap for a Grid
- Define and Deploy a TimesTenScaleout Object
- Monitor the High Level State of a TimesTenScaleout Object
- Verify Underlying Objects
- Connect to the Database
- Manage a Grid and Its Database



Create Configuration Metadata and a Kubernetes ConfigMap for a Grid

The following example creates the <code>db.ini</code>, the <code>adminUser</code>, and the <code>schema.sql</code> metadata files for the TimesTen grid and the database. The example also creates a direct and a client/server connectable. The example creates a Kubernetes ConfigMap to place these metadata files into the <code>/ttConfig</code> directory of the TimesTen containers.



You can use any Kubernetes mechanism to place these metadata files into the /ttConfig directory of the TimesTen containers. See Populate the /ttconfig Directory.

On your development host, complete the following steps:

1. From the directory of your choice, create an empty subdirectory for the metadata files. This example creates the <code>cm_scaleout</code> subdirectory. (The <code>cm_scaleout</code> directory is used in the remainder of this example to denote this directory.)

```
mkdir -p cm scaleout
```

2. Change to this ConfigMap directory.

```
cd cm scaleout
```

3. Create the db.ini file in this ConfigMap directory. In this example, define the PermSize and the DatabaseCharacterSet connection attributes.

```
vi db.ini
PermSize=200
DatabaseCharacterSet=AL32UTF8
```

4. Create the adminuser file.

```
vi adminUser
adminuser/adminuserpwd
```

5. Create the schema.sql file. In this schema.sql file, create the sampleuser user, create the s sequence for the sampleuser user, and the emp table for the sampleuser user. The Operator automatically initializes each element of the TimesTen database with these object definitions.

```
vi schema.sql
create user sampleuser identified by sampleuserpwd;
grant admin to sampleuser;
create sequence sampleuser.s;
```



create table sampleuser.emp (id number not null primary key, name char
(32));

6. Create the sampledirect direct connectable.

```
vi sampledirect.connect
ConnectionCharacterSet=AL32UTF8
```

7. Create the sampleclient client/server connectable.

```
vi sampleclient.csconnect
ConnectionCharacterSet=AL32UTF8
TTC Timeout=30
```

8. Optional: Verify the metadata files are present in the cm scaleout ConfigMap directory.

ls

The output is the following:

```
adminUser
db.ini
sampleclient.csconnect
sampledirect.connect
schema.sql
```

9. From the cm_scaleout directory, create the samplescaleout ConfigMap. The files in the cm_scaleout directory are included in the ConfigMap. These files are later available in the TimesTen containers. Replace samplescaleout with a name of your choosing.

```
kubectl create configmap samplescaleout --from-file .
```

The output is the following:

```
configmap/samplescaleout created
```

10. Use the kubectl describe command to verify the contents of the samplescaleout ConfigMap.

kubectl describe configmap samplescaleout

The output is the following:

Name: samplescaleout
Namespace: mynamespace
Labels: <none>
Annotations: <none>

Data



```
adminUser:
adminuser/adminuserpwd
db.ini:
PermSize=200
DatabaseCharacterSet=AL32UTF8
sampleclient.csconnect:
ConnectionCharacterSet=AL32UTF8
TTC Timeout=30
sampledirect.connect:
ConnectionCharacterSet=AL32UTF8
schema.sql:
create user sampleuser identified by sampleuserpwd;
grant admin to sampleuser;
create sequence sampleuser.s;
create table sampleuser.emp (id number not null primary key, name
char (32));
Events: <none>
```

You successfully created the metadata files and the ConfigMap.

Define and Deploy a TimesTenScaleout Object

Defining your environment involves creating your TimesTenScaleout object with attributes customized for your environment. These attributes are described in the steps below. For additional information on defining objects of type TimesTenScaleout, see TimesTenScaleout.

To define and create the TimesTenScaleout object, complete the following steps:

- 1. Create a YAML file. You can choose any name for this YAML file, but you may want to use the same name you used for the name of the TimesTenScaleout object. (This example uses samplescaleout.) The YAML file contains the definitions for the TimesTenScaleout object. In this example, the fields that are specific to a TimesTenScaleout object are as follows:
 - k: Set the value of k to the number of copies of data for your TimesTen database. This value determines the number of StatefulSets that the TimesTen Operator creates. A StatefulSet provides the Pods that are used to implement a single data space in the grid. For example, if you set k to 2, the Operator creates two StatefulSets. One StatefulSet provides the Pods for the data instances in data space one. The second StatefulSet provides the Pods for the data instances in data space two.

This example sets k to 2.



For information on K-safety and determining an appropriate value for k, see K-Safety in the *Oracle TimesTen In-Memory Database Scaleout User's Guide*.

• nReplicaSets: Set the value to the number of replica sets in the grid. A replica set contains k elements (where each element is an exact copy of the other elements in the replica set). The nReplicaSets value determines the number of replicas for each StatefulSet. For example, if you set k to 2, the TimesTen Operator creates two StatefulSets for the data instances. If you set nReplicaSets to 3, each StatefulSet contains three replicas, and the total number of replica sets in the database is three.

This example sets nReplicaSets to 3.

For information on replica sets, see Understanding Replica Sets in the *Oracle TimesTen In-Memory Database Scaleout User's Guide*.

• nZookeeper: Set the value to the number of ZooKeeper Pods to provision in a StatefulSet. Your options are 1 or 3 or 5.

This example sets nZookeeper to 3.

You also need to specify the following fields:

- name: Replace samplescaleout with the name of your TimesTenScaleout object.
- storageClassName: Replace oci-bv with the name of the storage class in your Kubernetes cluster that is used to allocate Persistent Volumes to hold the TimesTen database.
- storageSize: Replace 250Gi with the amount of storage that should be requested for each Pod to hold TimesTen. (This example assumes a production environment and uses 250Gi for storage. For demonstration purposes, you can use 50Gi of storage.) See the storageSize and the logStorageSize entries in Table 17-7.
- image: Replace container-registry.oracle.com/timesten/timesten:22.1.1.19.0 with the location of the image registry and the name of the image. If you are using the Oracle container-registry.oracle.com/timesten registry as the image registry and the timesten:22.1.1.19.0 image as the container image, no replacement is necessary.
- imagePullSecret: Replace sekret with the image pull secret that Kubernetes should use to fetch the TimesTen image.
- dbConfigMap: This example uses one ConfigMap (called samplescaleout) for the
 db.ini, the adminUser, the schema.sql, the sampledirect.connect, and the
 sampleclient.csconnect metadata files. This ConfigMap is included in the Projected
 Volume. The volume is mounted as /ttconfig in the TimesTen containers. See
 Using ConfigMaps and Secrets.

```
vi samplescaleout.yaml
kind: TimesTenScaleout
metadata:
  name: samplescaleout
spec:
  ttspec:
    storageClassName: oci-bv
    storageSize: 250Gi
    image: container-registry.oracle.com/timesten/timesten:22.1.1.19.0
  imagePullSecret: sekret
```



dbConfigMap:
 - samplescaleout
k: 2
nReplicaSets: 3
nZookeeper: 3

Create the TimesTenScaleout object from the contents of the YAML file. Doing so begins the process of creating and provisioning a TimesTen grid and database in your Kubernetes cluster.

kubectl create -f samplescaleout.yaml

The output is the following:

timestenscaleout.timesten.oracle.com/samplescaleout created

You successfully created the TimesTenScaleout object in the Kubernetes cluster. The process of provisioning your TimesTen grid and database begins, but is not yet complete.

Monitor the High Level State of a TimesTenScaleout Object

Use the kubectl get and the kubectl describe commands to monitor the progress of the grid and database creation.



For the kubectl get timestenscaleout command, you can alternatively specify kubectl get tts. When used in the kubectl get command, timestenscaleout and tts are synonymous, and return the same results. The first kubectl get examples in this chapter use timestenscaleout. For simplicity, the remaining examples in this book use tts.

1. Review the High Level state of the TimesTenScaleout object. Use the kubectl get command and observe the STATE field. Notice that the value is Initializing. The Operator has created the Kubernetes StatefulSets and Services. The process to deploy and provision your grid and database has begun, but is not yet complete. As you issue additional kubectl get commands, observe how the TimesTenScaleout object transitions to different states. For more information on these states, see About Creating a Grid.

kubectl get tts samplescaleout



The output is similar to the following:

NAME OVERALL MGMT CREATE LOAD OPEN AGE samplescaleout **Initializing** 20s

kubectl get tts samplescaleout

The output is similar to the following:

NAME OVERALL MGMT CREATE LOAD OPEN AGE samplescaleout **ZookeeperReady** 2m48s

kubectl get tts samplescaleout

The output is similar to the following:

NAME OVERALL MGMT CREATE LOAD OPEN AGE samplescaleout **GridCreated** 3m58s

kubectl get tts samplescaleout

The output is similar to the following:

NAME OVERALL MGMT CREATE LOAD OPEN AGE samplescaleout InstancesCreated 6m4s

kubectl get tts samplescaleout

The output is similar to the following:

NAME OVERALL MGMT CREATE LOAD OPEN AGE

samplescaleout DatabaseCreated

6m10s

2. Use the kubectl get command again to observe if the High Level state has transitioned from DatabaseCreated to Normal. A Normal state indicates the grid and database are provisioned and the process is complete.

kubectl get tts samplescaleout

The output is similar to the following:

NAME OVERALL MGMT CREATE LOAD OPEN AGE

samplescaleout Normal Normal created loaded-complete open

6m52s



Your TimesTen Scaleout grid and database are successfully created and provisioned in your Kubernetes cluster. The database is open for connections.

Verify Underlying Objects

The TimesTen Operator creates the following objects for the samplescaleout TimesTenScaleout object.

StatefulSets:

kubectl get statefulsets

The output is the following:

NAME	READY	AGE
samplescaleout-data-1	3/3	26m
samplescaleout-data-2	3/3	26m
samplescaleout-mgmt	1/1	26m
samplescaleout-zk	3/3	26m

The Operator creates the <code>samplescaleout-data-1</code> and the <code>samplescaleout-data-2</code> StatefulSets. Two StatefulSets are created because the value of <code>k</code> is set to <code>2</code>. Each StatefulSet provides the Pods for a single data space. There are two data spaces in the grid. Each of the StatefulSets has three replicas (<code>nReplicaSets</code> is set to <code>3</code>). Therefore, the number of replica sets in the grid is three. There are three data instances in data space one and three data instances in data space two.

The samplescaleout-mgmt StatefulSet provides the Pod for the management instance. There is one management instance.

The samplscaleout-zk StatefulSet provides the Pods for the ZooKeeper instances. There are three ZooKeeper instances (nZookeeper is set to 3).

2. Pods:

kubectl get pods

The output is the following:

NAME	READY	STATUS	RESTARTS
AGE			
samplescaleout-data-1-0	2/2	Running	0
27m			
samplescaleout-data-1-1	2/2	Running	0
27m			
samplescaleout-data-1-2	2/2	Running	0
27m			
samplescaleout-data-2-0	2/2	Running	0
27m			
samplescaleout-data-2-1	2/2	Running	0
27m			
samplescaleout-data-2-2	2/2	Running	0
27m			
<pre>samplescaleout-mgmt-0</pre>	2/2	Running	0



27m				
samplescaleout-zk-0	1/1	Running	0	27m
samplescaleout-zk-1	1/1	Running	0	26m
samplescaleout-zk-2	1/1	Running	0	25m
timesten-operator-7677964df9-sp2zp	1/1	Running	0	3d20h

The samplescaleout-data-1 StatefulSet contains the data instances in data space one. This StatefulSet creates the samplescaleout-data-1-0, samplescaleout-data-1-1, and samplescaleout-data-1-2 Pods. The samplescaleout-data-2 contains the data instances in data space two. This StatefulSet creates the samplescaleout-data-2-0, samplescaleout-data-2-1, and samplescaleout-data-2-2 Pods.

The samplescaleout-mgmt-0 StatefulSet contains the management instance for the grid. This StatefulSet creates the samplescaleout-mgmt-0 Pod.

Each of the Pods previously mentioned run TimesTen. Each Pod contains at least two containers. In this example, each Pod contains two containers. The tt container runs the TimesTen agent and TimesTen. The daemonlog container writes the TimesTen daemon log to stdout.

The samplescaleout-zk StatefulSet contains the three ZooKeepers instances. This StatefulSet creates the samplescaleout-zk-1, samplescaleout-zk-2, and samplescaleout-zk-3 Pods. Each of these Pods contain a single container called zookeeper.

The TimesTen Operator is running in the timesten-operator-554887b4c-48zwk Pod.

3. Headless Services:

kubectl get services

The output is the following:

NAME	TYPE	CLUSTER-IP	EXTERNAL-IP			
PORT(S)		AGE				
samplescaleout	ClusterIP	None	<none></none>			
6625/TCP		28m				
samplescaleout-zk	ClusterIP	None	<none></none>	2181/		
TCP, 2888/TCP, 3888/TCP 28m						

The Operator creates the samplescaleout Headless Service. This Service provides the DNS names for the Pods that contain the TimesTen management and data instances. The Service allows client/server access to the Pods that use the client/server port (6625). The DNS names are in the format:

podname.samplescaleout.namespace.svc.cluster.local.

The following example shows the DNS names for the samplescaleout Headless Service:

```
samplescaleout-mgmt-0.samplescaleout.mynamespace.svc.cluster.local samplescaleout-data-1-0.samplescaleout.mynamespace.svc.cluster.local samplescaleout-data-1-1.samplescaleout.mynamespace.svc.cluster.local samplescaleout-data-1-2.samplescaleout.mynamespace.svc.cluster.local samplescaleout-data-2-0.samplescaleout.mynamespace.svc.cluster.local
```



samplescaleout-data-2-1.samplescaleout.mynamespace.svc.cluster.local samplescaleout-data-2-2.samplescaleout.mynamespace.svc.cluster.local

The Operator creates a second Headless Service called samplescaleout-zk. This Service allows access to the ZooKeeper internal ports (2888 and 3888) as well as the external port (2181). The DNS names are in the format: samplescaleout-zk-n.samplescaleout-zk.namespace.svc.cluster.local.

The following example shows the DNS names for the samplescaleout-zk Headless Service:

sample scale out-zk-0.sample scale out-zk.myname space.svc.cluster.local sample scale out-zk-1.sample scale out-zk.myname space.svc.cluster.local sample scale out-zk-2.sample scale out-zk.myname space.svc.cluster.local sample scale out-zk-2.sample scale out-zk.myname space.svc.cluster.local scale out-zk-2.sample scale out-zk-myname space.svc.cluster.local scale out-zk-2.sample scale out-zk-2.sample scale out-zk-myname space.svc.cluster.local scale out-zk-2.sample scale out-zk-2

4. Persistent Volume Claims (PVCs):

kubectl get pvc

The output is the following:

NAME STATUS VOLUME CAPACITY ACCESS MODES STORAGECLASS tt-persistent-samplescaleout-data-1-0 Bound ocid1.volume.oc1.phx.abyhqljtl63wgaxd3nvengilkaxs5h2b23kmtinpzmmqt7b kzjdpnfu2c2fg 53687091200 RWO oci-bv tt-persistent-samplescaleout-data-1-1 Bound ocid1.volume.oc1.phx.abyhqljthxuwtpqx7rjtwvwsxjjkbgr25amjk7wtk26untb grealcghe324g 53687091200 RWO oci-bv 14m tt-persistent-samplescaleout-data-1-2 Bound ocid1.volume.oc1.phx.abyhqljthtm6frcjtttp6ye7hq4w5vm3jxyay54f4xtcbol v2ercjeca5khq 53687091200 RWO oci-bv tt-persistent-samplescaleout-data-2-0 Bound ocid1.volume.oc1.phx.abyhqljtxgzm3raxj5sfoe56aonlh2mqqjre4quva4k3q3z oci-bv bbe7lftwqk3xa 53687091200 RWO tt-persistent-samplescaleout-data-2-1 Bound ocid1.volume.oc1.phx.abyhqljtk3htdair4akll5dfrwpkipv3acjtww5hx3x2fz4 6af7zdew7gsig 53687091200 RWO oci-bv tt-persistent-samplescaleout-data-2-2 Bound ocid1.volume.oc1.phx.abyhqljtiekgulpbadtwigehsuml75sngcuqjgqmx771fpi 3wdeecbecavfa 53687091200 RWO oci-bv 14m tt-persistent-samplescaleout-mgmt-0 Bound ocid1.volume.oc1.phx.abyhqljtacxwop7r2wqx6hsvun4haaydnco3y6g3rkgbwp5 oci-bv hq35alay7uwaq 53687091200 RWO tt-persistent-samplescaleout-zk-0 Bound ocid1.volume.oc1.phx.abyhqljtyoa5hdchax4sus652jtp665ckaef2cq3lakac2l q52vfbls6kkcq 53687091200 RWO oci-bv tt-persistent-samplescaleout-zk-1 Bound ocid1.volume.oc1.phx.abyhqljtongpcoggzpg2is25vmumijmah5gustwc3avgnij rjigtqphtrana 53687091200 RWO oci-bv 13m tt-persistent-samplescaleout-zk-2 Bound



```
ocid1.volume.oc1.phx.abyhqljttmgoljskb2ruawzv365uit7lsln2sbfno5e4vhh6plbgh 4tiblfq 53687091200 RWO oci-bv 10m
```

The Operator automatically creates one or two Persistent Volume Claims (PVCs) per Pod. These PVCs cause Persistent Volumes (PVs) to be allocated by Kubernetes and attached to the TimesTen Pods. TimesTen uses these PVs to hold the TimesTen instance and database. If you specify two PVCs, one PV holds the TimesTen instance and the checkpoint files and the second PV holds the TimesTen transaction logs. In this example, the Operator creates one PVC for each Pod for a total of six PVCs. Each of the six PVs hold the TimesTen instance and an element of the database.

The Operator creates one PVC for the Pod that contains the management instance.

The Operator creates one PVC for each Pod that runs a ZooKeeper instance. This PVC causes a PV to be allocated by Kubernetes and attached to the ZooKeeper Pod. Each PV holds ZooKeeper's persistent data. In this example, since there are three ZooKeeper instances, the Operator created three PVCs.

Connect to the Database

You can establish a shell in a TimesTen Pod and connect to the TimesTen database in the grid. You can then run operations in this TimesTen database.

1. Establish a shell in the TimesTen samplescaleout-data-1-0 Pod.

```
kubectl exec -it samplescaleout-data-1-0 -c tt -- /bin/bash
```

2. Connect to the samplescaleout database. Verify the information from the metadata files is in the database. This example connects to the database as the sampleuser user. (This user was created in the schema.sql file). The example then calls the ttConfiguration built-in procedure to check that the PermSize connection attribute has a value of 200 for this element of the database. The example then verifies the sampleuser.emp table exists.

```
ttisql -connstr "DSN=samplescaleout;uid=sampleuser;pwd=sampleuserpwd";
```

The output is similar to the following:

```
Copyright (c) 1996, 2023, Oracle and/or its affiliates. All rights
reserved.
Type ? or "help" for help, type "exit" to quit ttIsql.

connect "DSN=samplescaleout; uid=sampleuser; pwd=*******";
Connection successful:
DSN=samplescaleout; Durability=0; UID=sampleuser; DataStore=/tt/home/
timesten/datastore/samplescaleout;
DatabaseCharacterSet=AL32UTF8; ConnectionCharacterSet=AL32UTF8; PermSize=200;
Connections=100;
(Default setting AutoCommit=1)
Command> call ttConfiguration ('PermSize');
< PermSize, 200 >
1 row found.
```



```
Command> tables;
   SAMPLEUSER.EMP
1 table found.
```

Manage a Grid and Its Database

You can establish a shell in the TimesTen Pod of the management instance. You can then use the ttGridAdmin utility to manage and monitor the grid, including the health of the TimesTen database and its elements.

1. Establish a shell in the TimesTen samplescaleout-management-0 Pod.

```
kubectl exec -it samplescaleout-mgmt-0 -c tt -- /bin/bash
```

2. Run the ttGridAdmin dbStatus -all to check the status of the TimesTen database.

```
ttGridAdmin dbStatus -all
```

The output is the following:

```
Database samplescaleout summary status as of Sun Jan 15 17:00:11
UTC 2023
created, loaded-complete, open
Completely created elements: 6 (of 6)
Completely loaded elements: 6 (of 6)
Completely created replica sets: 3 (of 3)
Completely loaded replica sets: 3 (of 3)
Open elements: 6 (of 6)
Database samplescaleout element level status as of Sun Jan 15
17:00:11 UTC 2023
                       Instance Elem Status Cache Agent Date/Time
Host
of Event Message
_____
samplescaleout-data-1-0 instance1 1 opened stopped
2023-01-15 16:28:57
samplescaleout-data-1-1 instance1 2 opened stopped
2023-01-15 16:28:57
samplescaleout-data-1-2 instance1
                                    3 opened stopped
2023-01-15 16:28:56
samplescaleout-data-2-0 instance1
                                    4 opened stopped
2023-01-15 16:28:57
samplescaleout-data-2-1 instance1
                                    5 opened stopped
2023-01-15 16:28:56
samplescaleout-data-2-2 instance1
                                    6 opened stopped
2023-01-15 16:28:56
Database samplescaleout Replica Set status as of Sun Jan 15
```



RS DS Elem Host Instance Status Cache Agent Date/Time of Event Message

1 1 1 samplescaleout-data-1-0 instance1 opened stopped

2023-01-15 16:28:57
1 2 4 samplescaleout-data-2-0 instance1 opened stopped

2023-01-15 16:28:57
2 1 2 samplescaleout-data-1-1 instance1 opened stopped

2023-01-15 16:28:57
2 2 5 samplescaleout-data-2-1 instance1 opened stopped

2023-01-15 16:28:56

3 1 3 samplescaleout-data-1-2 instance1 opened stopped 2023-01-15 16:28:56

3 2 6 samplescaleout-data-2-2 instance1 opened stopped 2023-01-15 16:28:56

Database samplescaleout **Data Space Group** status as of Sun Jan 15 17:00:11 UTC 2023

DS RS Elem Host Instance Status Cache Agent Date/Time of Event Message

-- -- ---- ------

17:00:11 UTC 2023

1 1 1 samplescaleout-data-1-0 instance1 opened stopped 2023-01-15 16:28:57

1 2 2 samplescaleout-data-1-1 instance1 opened stopped 2023-01-15 16:28:57

1 3 3 samplescaleout-data-1-2 instance1 opened stopped 2023-01-15 16:28:56

2 1 4 samplescaleout-data-2-0 instance1 opened stopped 2023-01-15 16:28:57

2 2 5 samplescaleout-data-2-1 instance1 opened stopped 2023-01-15 16:28:56

2 3 6 samplescaleout-data-2-2 instance1 opened stopped 2023-01-15 16:28:56



7

Use Helm to Deploy the TimesTen Kubernetes Operator and TimesTenClassic Objects

You can use Helm to deploy TimesTen-specific Helm charts. These charts allow you to deploy TimesTen Custom Resource Definitions (CRDs), the TimesTen Operator, and TimesTen Classic objects.

The techniques for using Helm with the TimesTen Operator are optional. If you do not want to use Helm, you can deploy the TimesTen CRDs, the TimesTen Operator, and TimesTenClassic objects using alternative techniques. For more information, see About Deploying the TimesTen Operator and Deploy TimesTen Classic Databases.

This chapter provides an overview of Helm and discusses how you use Helm charts to install releases of software. The chapter details the charts that the TimesTen Operator provides. In addition, it illustrates how you use these charts to deploy the TimesTen-specific Custom Resource Definitions (CRDs), the TimesTen Operator, and one or more TimesTenClassic objects in your Kubernetes cluster.

Topics:

- · Overview of Helm
- About a Helm Chart
- About Helm Charts for TimesTen
- · About Versions in a Chart.yaml File
- About the Helm Substitution Engine and Language
- About Installing and Testing a Release
- Install the TimesTen Custom Resource Definitions (CRDs)
- Install the TimesTen Operator
- Test the TimesTen Operator
- Install TimesTen Databases
- Test TimesTen
- Upgrade the TimesTen Custom Resource Definitions (CRDs)
- Upgrade the TimesTen Operator
- Upgrade TimesTen
- · Roll Back a TimesTen Upgrade
- Roll Back a TimesTen Operator Upgrade
- Roll Back a TimesTen Custom Resource Definitions (CRDs) Upgrade
- About Uninstalling a Release
- Delete TimesTen Databases



- Delete the TimesTen Operator
- Delete the TimesTen Custom Resource Definitions (CRDs)

Overview of Helm

Helm is the package manager for Kubernetes. It is an open source project by the Cloud Native Computing Foundation (CNCF).

Kubernetes provides a rich interface for deploying applications through an extensible object model. Typically, you write manifest YAML files describing objects and then use the kubectl command to feed the YAML files to Kubernetes. Kubernetes then configures the Kubernetes cluster to match. Built-in object types include include Pod, Service, and Persistent Volume. The TimesTen Operator extends the Kubernetes object type system by adding objects of type TimesTenClassic and TimesTen Scaleout.

Helm is an optional layer on top of this architecture. Rather than manually creating YAML files and using kubectl to apply the files, Helm gives application developers the ability to package a set of YAML files into a single entity called a chart. Such a chart can be installed into a Kubernetes cluster using a single command.

The YAML files provided in a chart are templates. When installing a chart, you can specify a set of values to replace into the chart. Helm processes the YAML in the chart, substituting values provided by you, and submits the final version to Kubernetes through the kubectl command.

Helm also provides advanced facilities to manage applications:

- Charts can depend on other charts. Helm can assist in maintaining the dependency relationships. Helm can install an application and its dependencies as a unit.
- You can list charts that have been installed in your Kubernetes cluster and refer to them by name.
- You can use the helm test command to verify the functioning of the application.
- You can upgrade an installed application by applying a new version of the chart that installed the application.
- You can delete charts by name.

For more information about Helm, see https://helm.sh/docs/.

About a Helm Chart

A Helm chart is a collection of files in a directory. A chart consists of at minimum the following:

- Chart.yaml: This file contains metadata about the chart, including its name and version.
- templates: This is a directory containing one or more YAML file templates. A
 sophisticated templating language allows variables to be substituted into these
 files. Ultimately, when the chart is installed, Helm substitutes values into these
 templates and presents the result to Kubernetes with the kubectl command.
- values.yaml: This file contains default values for the variables, which are used in the chart's templates.



About Helm Charts for TimesTen

Helm charts that are used to deploy the TimesTen Operator and TimesTen are included in each TimesTen release.

Each TimesTen release contains a TimesTen Operator distribution. The distribution is located in a file called <code>kubernetes/operator.zip</code>. When unzipped, this file expands into the TimesTen Operator distribution. There is a directory called <code>helm</code> that is included in the TimesTen Operator distribution. The Helm charts that TimesTen publishes are included in separate directories in the <code>helm</code> directory. For more information about the <code>helm</code> directory, see Set Up the Environment .

The following charts are included in the TimesTen Operator distribution:

- ttcrd: Deploys the TimesTen Custom Resource Definitions (CRDs) into the Kubernetes cluster.
- ttoperator: Deploys the TimesTen Operator.
- ttclassic: Creates a TimesTenClassic object, thus deploying an active standby pair of TimesTen databases.

Each chart requires a different level of authority. As a result, the charts are packaged as separate charts so they can be installed with appropriate privileges. In addition, a single TimesTen Operator can simultaneously create and manage multiple TimesTen databases and/or multiple TimesTen active standby pairs. Because the relationship between TimesTen Operators and TimesTen databases is not one to one, there is a chart (ttoperator) to deploy the TimesTen Operator and a separate chart (ttclassic) to deploy a TimesTen active standby pair.



The TimesTen Operator does not provide a chart for TimesTen Scaleout.

About Versions in a Chart.yaml File

Each chart contains metadata in its Chart.yaml file.

Let's take a look at the Chart. yaml file for the ttoperator chart. In particular, let's look at the appVersion and version metadata.

apiVersion: v2

appVersion: 22.1.1.19.0

description: A Helm chart for Kubernetes

name: ttoperator
type: application
version: 2211190.1.0

The value of appVersion is the TimesTen release number of the distribution that includes the charts. For example, consider a TimesTen 22.1.1.19.0 release. When you unzip the operator.zip file that is included in the 22.1.1.19.0 release, there are several charts in the



operator.zip's helm directory. The value of appVersion in each chart's Chart.yaml file is 22.1.1.19.0.

Similarly, the value of version is set to the TimesTen release number without dots (.) followed by .1.0. For a TimesTen 22.1.1.19.0 release, the value of version in each chart's Chart.yaml file is 2211190.1.0.

About the Helm Substitution Engine and Language

Helm has a robust substitution engine and language that lets you specify your own values for variables in a chart's template YAML manifest files. For more information about chart templates, see https://helm.sh/docs/chart_template_guide/getting_started/.

For each chart, the TimesTen Operator provides variables specific to the chart. For example, the ttoperator chart has variables and default values specific to the TimesTen Operator deployment. Similarly, the ttclassic chart has variables and default values specific to the deployment of an active standby pair of TimesTen Classic databases. You can change the default values for the provided variables.

You can define variables and values for those variables either on the helm command line or by providing a YAML file with the values. The values may be strings, lists, arbitrary YAML, or entire files.

For information about the variables for the TimesTen-specific Helm charts, see Helm Charts for the TimesTen Kubernetes Operator.

About Installing and Testing a Release

The TimesTen Operator provides specific Helm charts for the TimesTen Custom Resource Definitions (CRDs), the TimesTen Operator, and TimesTenClassic objects. You use Helm to install these charts.

The installation of each chart serves a different purpose. For example:

- The ttcrd chard defines the TimesTen CRDs to your Kubernetes cluster.
- The ttoperator chart deploys the TimesTen Operator in your namespace.
- The ttclassic chart deploys a TimesTenClassic object in your namespace, which results in the deployment of an active standby pair of TimesTen Classic databases.

The examples in the upcoming sections show you how to install these charts.

Before you install the charts, ensure you have completed the following:

- Unpacked the TimesTen Operator distribution. This distribution contains the directories for the TimesTen-specific Helm charts. See Set Up the Environment.
- Installed Helm on your development host. See https://helm.sh/docs/intro/install/ in the Helm documentation.

After you install a chart, you can test it with the <code>helm test</code> command. The <code>helm test</code> command creates a <code>test</code> Pod. The Pod runs a command specific to the chart being tested. If the command finishes with exit code <code>0</code>, the test succeeds and the <code>test</code> Pod is deleted. Any other error code indicates failure. In the case of failure, the <code>test</code> Pod is not deleted.



The examples in the upcoming sections show you how to use helm test to test the ttoperator and ttclassic charts.

Install the TimesTen Custom Resource Definitions (CRDs)

The TimesTen Operator provides two Custom Resource Definitions (CRDs) called timestenclassics.timesten.oracle.com and timestenscaleouts.timesten.oracle.com. These CRDs define the TimesTenClassic and TimesTenScaleout object types.

Let's use Helm to install the TimesTen CRDs into your Kubernetes cluster. Since CRDs are cluster-wide, the CRDs are available to all namespaces after they are installed. Let's install the CRDs by installing the TimesTen Operator's ttcrd chart. You cannot customize the ttcrd chart. Therefore, let's install the chart as is.

For more information about using Helm to install a chart, see https://helm.sh/docs/intro/using_helm/.

1. On your development host, change to the helm directory. For more information about the helm directory, see Set Up the Environment.

```
cd kube files/helm
```

2. Install the ttcrd chart.

```
helm install ttcrd ./ttcrd
```

Output.

```
NAME: ttcrd
LAST DEPLOYED: Tue Oct 17 22:00:53 2023

NAMESPACE: mynamespace
STATUS: deployed
REVISION: 1
NOTES:
Version 2211190.1.0 of the ttcrd chart has been installed.

This release is named "ttcrd".

To learn more about the release, try:

$ helm status ttcrd
$ helm get all ttcrd
$ helm history ttcrd

To rollback to a previous version of the chart, run:

$ helm rollback ttcrd <REVISION>
- run 'helm history ttcrd' for a list of revisions.
```

The ttcrd release is installed in your namespace.



3. Confirm the CRDs are defined in your Kubernetes cluster.

```
kubectl get crds | grep timesten
```

Output.

```
timestenclassics.timesten.oracle.com 2023-10-17T22:00:53Z timestenscaleouts.timesten.oracle.com 2023-10-17T22:00:53Z
```

The TimesTenClassic and TimesTenScaleout CRDs are defined in your Kubernetes cluster.

Install the TimesTen Operator

The ttoperator chart contains all the information necessary to deploy the TimesTen Operator in your namespace. The chart contains a default configuration for deploying the TimesTen Operator. You have the option of customizing the chart to meet your preferred configuration. Specifically, the TimesTen Operator provides several variables whose values you can change to meet your configuration needs. For information about these variables, see The ttoperator Chart.

After you decide the variables you want to customize, you have two options:

- Create a YAML file that defines the variables that you want to use to configure
 your environment. Next, to install the chart, pass this YAML file to the helm
 install command by specifying the -f option.
- Specify the variables on the command line by running the helm install command with the --set option.

For more information about these options, see https://helm.sh/docs/intro/using helm/.

The examples in the section use a YAML file.

Let's walk through an example illustrating how to install the ttoperator chart, which deploys the TimesTen Operator. In this example, let's make the following modifications:

- imagePullSecret: Let's assume that sekret is the name of the Secret used to pull images from the repository. Therefore, let's specify sekret for the imagePullSecret variable.
- Container image: Rather that use a container image in containerregistry.oracle.com/timesten, let's assume you built you own container image
 as discussed in Option 2: Build the TimesTen Container Image. Let's assume the
 name of the container image you built and want to use is phx.ocir.io/
 youraccount/tt2211190image:1. Based on this container image, let's modify the
 following variables:
 - repository: For the repository variable, specify a value of phx.ocir.io/ youraccount/tt2211190image.
 - tag: For the tag variable, specify a value of 1.

Let's also assume you have created a kube_files/helm/customyaml directory for your customized YAML files.



Note:

By default, the ttoperator chart creates timesten-operator ServiceAccount, Role, and RoleBinding Kubernetes objects. The Role and RoleBinding objects grant the timesten-operator ServiceAccount the privileges needed to run the TimesTen Operator. See The ttoperator Chart.

1. On your development host, change to the helm directory. For more information about the helm directory, see Set Up the Environment.

```
cd kube files/helm
```

2. Create a YAML file that defines the variables for your configuration.

```
vi customyaml/samplettop.yaml
image:
   repository: phx.ocir.io/youraccount/tt2211190image
   tag: "1"
   pullPolicy: Always
imagePullSecrets:
   - name: sekret
```

The customizations are as follows:

- Since the container image you built and want to use is phx.ocir.io/youraccount/tt2211190image:1, the value of the repository variable is phx.ocir.io/youraccount/tt2211190image and the value of the tag variable is 1.
- The image pull Secret is sekret.
- 3. To install the TimesTen Operator in your namespace, install the ttoperator chart.

```
helm install -f customyaml/samplettop.yaml samplettop ./ttoperator
```

Let's look at this helm install command:

- The -f option is used to pass the customized YAML file to the helm install command.
- The name of the file that contains the customizations is samplettop.yaml, which is located in the customyaml directory.
- The name of the release is samplettop.
- The name of the chart that installs the TimesTen Operator is ttoperator, which is located in the helm/ttoperator directory.

Let's look at the output from the helm install command.

```
NAME: samplettop
LAST DEPLOYED: Mon Oct 23 23:04:40 2023
NAMESPACE: mynamespace
STATUS: deployed
```



```
REVISION: 1
NOTES:
Version 2211190.1.0 of the ttoperator chart has been installed.
This release is named "samplettop".

To learn more about the release, try:

$ helm status samplettop
$ helm get all samplettop
$ helm history samplettop

To rollback to a previous version of the chart, run:

$ helm rollback samplettop <REVISION>
- run 'helm history samplettop' for a list of revisions.

To test the operator, run:

$ helm test samplettop
```

Note the following:

- The ttoperator chart version is 2211190.1.0 corresponding to the 22.1.1.19.0 TimesTen release.
- The release name is samplettop.
- The status of the release is deployed.
- 4. (Optional) Verify the release.

helm list

Output.

NAME	NAMESPACE	REVISION	1	
UPDATED			STATUS	
CHART	APP V	ERSION		
samplettop	mynamespace	1		2023-10-23
23:04:40.492890	589 +0000 UTC	deployed		
ttoperator-2211	190.1.0 22.1.	1.19.0		
ttcrd	mynamespace	1		2023-10-17
22:00:53.530832	896 +0000 UTC	deployed		
ttcrd-2211190.1	.0 22.1.	1.19.0		

The helm list command shows the samplettop release exists and is installed in your namespace.

5. Confirm the TimesTen Operator is running in your namespace.

kubectl get pods



Output.

NAME READY STATUS RESTARTS AGE timesten-operator-65ddf9cfbb-jkqbn 1/1 Running 0 12s

6. Confirm the ServiceAccount, Role, and RoleBinding objects are created.

kubectl get serviceaccount timesten-operator NAME SECRETS AGE timesten-operator 0 25s

kubectl get role timesten-operator NAME $$\operatorname{CREATED}$$ AT

timesten-operator 2023-10-23T22:04:43Z

kubectl get rolebinding timesten-operator

NAME ROLE AGE timesten-operator Role/timesten-operator 10s

By default, the ttoperator chart created the timesten-operator ServiceAccount, Role, and RoleBinding objects.

Congratulations! You successfully installed the ttoperator chart. The TimesTen Operator is running in your namespace.

Test the TimesTen Operator

To test the TimesTen Operator, the test Pod uses the curl command to access the TimesTen Operator's readiness probe endpoint. If the TimesTen Operator self-reports that it is ready, the test succeeds.

The TimesTen Operator's readiness endpoint is exposed to the Kubernetes cluster through the TimesTen Operator's <code>EXPOSE_PROBES</code> manifest variable. In the default configuration (<code>EXPOSE_PROBES=1</code>), the TimesTen Operator creates a Kubernetes Service. This Service makes the endpoint available from within the cluster. You can prevent this Service from being created by setting <code>probes.expose=0</code> in your customized YAML file. See The ttoperator Chart.

To test the TimesTen Operator, you test the ttoperator chart release running in your namespace. Let's test the TimesTen Operator.

1. Examine the ttoperator chart release.

helm list

Output.

NAME NAMESPACE REVISION

UPDATED STATUS

CHART APP VERSION

samplettop mynamespace 1 2023-10-23
23:04:40.492890589 +0000 UTC deployed ttoperator-2211190.1.0
22.1.1.19.0



```
ttcrd mynamespace 1 2023-10-17 22:00:53.530832896 +0000 UTC deployed ttcrd-2211190.1.0 22.1.1.19.0
```

The samplettop release of the ttoperator chart is installed in your namespace. You installed this release in Install the TimesTen Operator.

2. Test the release.

```
helm test samplettop
```

Output.

```
NAME: samplettop
LAST DEPLOYED: Mon Oct 23 23:04:40 2023
NAMESPACE: mynamespace
STATUS: deployed
REVISION: 1
TEST SUITE:
               samplettop-ttoperator-test
Last Started: Mon Oct 23 23:14:12 2023
Last Completed: Mon Oct 23 23:14:16 2023
               Succeeded
Phase:
NOTES:
Version 2211190.1.0 of the ttoperator chart has been installed.
This release is named "samplettop".
To learn more about the release, try:
 $ helm status samplettop
 $ helm get all samplettop
 $ helm history samplettop
To rollback to a previous version of the chart, run:
  $ helm rollback samplettop <REVISION>
    - run 'helm history samplettop' for a list of revisions.
To test the operator, run:
  $ helm test samplettop
```

The test for the samplettop release succeeded.

Congratulations! You successfully tested the TimesTen Operator. The test succeeded and the TimesTen Operator is successfully running in your namespace.

Install TimesTen Databases

The ttclassic chart contains all the information necessary to deploy an active standby pair of TimesTen Classic databases in your namespace. The chart contains a default configuration for deploying TimesTen. You have the option of customizing the chart to meet your preferred configuration. Specifically, the TimesTen Operator

provides several variables whose values you can change to meet your configuration needs. For information about these variables, see The ttclassic Chart.

When customizing your environment, consider the following:

- The method you are using to place metadata files into the /ttconfig directory of TimesTen containers. If you are using Kubernetes ConfigMaps or Secrets:
 - You do not need to create them. The ttclassic chart installation generates
 ConfigMaps and Secrets for you.
 - You must create a directory in the helm/ttclassic directory tree of the ttclassic chart. Place all your metadata files in this directory. All of the files in this directory are added to the generated ConfigMap or Secret.
 - You must specify the dbConfigMap (if using a ConfigMap) or dbSecret (if using a Secret) variable in your customized YAML manifest file. For more information about these variables, see The ttclassic Chart.

The example in this section illustrates how to use a ConfigMap for your metadata files. For more information about using ConfigMaps or Secrets, see Populate the /ttconfig Directory.

- If you are using helm test to test TimesTen:
 - You must define a test user. The test connects to the TimesTen database as this
 user.
 - The TimesTen Operator provides a metadata file called testUser. Use this metadata file to define the test user. This file must contain one line of the form:

testuser/testuserpassword

where testuser is the name of your test user and testuserpassword is the password for this test user.

For more information about testing TimesTen using Helm, see Test TimesTen.

After you decide the variables you want to customize, you have two options:

- Create a YAML file that defines the variables that you want to use to configure your environment. Next, to install the chart, pass this YAML file to the helm install command by specifying the -f option.
- Specify the variables on the command line by running the helm install command with the --set option.

For more information about these options, see https://helm.sh/docs/intro/using helm/.

The examples in the section use a YAML file.

Let's walk through an example illustrating how to install the ttclassic chart, which deploys an active standby pair of TimesTen Classic databases. In this example, let's do the following:

- Create a directory for the metadata files. In this example, the ttclassic chart installation generates a ConfigMap from the files in this directory.
- Create the testUser metadata file. This file defines a test user. This user must be defined in order to test TimesTen using Helm.
- Make modifications to the following ttclassic chart's variables:



- imagePullSecret: Let's assume that sekret is the name of the Secret used to pull images from the repository. Therefore, let's specify sekret for the imagePullSecret variable.
- Container image: Rather that use a container image in container-registry.oracle.com/timesten, let's assume you built you own container image as discussed in Option 2: Build the TimesTen Container Image. Let's assume the name of the container image you built and want to use is phx.ocir.io/youraccount/tt2211190image:1. Based on this container image, let's modify the following variables:
 - * repository: For the repository variable, specify a value of phx.ocir.io/youraccount/tt2211190image.
 - * tag: For the tag variable, specify a value of 1.
- storageClassName: Let's specify oci-bv for the storage class name. Since there is no default for this variable, you must specify it.
- storageSize: Rather than use the default value of 50Gi, let's specify a value of 10Gi for the storage size.
- dbConfigMap: Since you are using a ConfigMap for the metadata files, you
 must specify the dbConfigMap variable. This variable requires that you specify
 a name for the ConfigMap as well as the directory where the metadata files
 are located. The use of this variable is shown later in this example.

In addition, lets' assume you have created a $kube_files/helm/customyaml$ directory for your customized YAML files.

1. On your development host, change to the helm directory. For more information about the helm directory, see Set Up the Environment.

```
cd kube_files/helm
```

2. Create a directory for the metadata files. The directory must be created in the directory tree of the /ttclassic chart.

```
mkdir -p ttclassic/cm
```

The cm directory is the directory that will contain the metadata files. When you install the ttclassic chart, a ConfigMap will be created and will contain the metadata files located in the directory. There are steps in this example that later illustrate this.

3. Create the testUser metadata file.

```
vi ttclassic/cm/testUser
sampletestuser/sampletestuserpwd1
```

In this example, the sampletestuser is the name of the test user that is used for testing TimesTen with the helm test command. The password for sampletestuser is sampletestuserpwd1. See Test TimesTen.



4. (Optional) Create additional metadata files as needed.

```
vi ttclassic/cm/adminUser
adminuser/adminuserpwd

vi ttclassic/cm/db.ini

PermSize=200
DatabaseCharacterSet=AL32UTF8

vi ttclassic/cm/schema.sql

create table adminuser.emp (id number not null primary key, name char (32));
```

The cm directory contains the testUser, adminUser, db.ini, and schema.sql metadata files. A ConfigMap is the facility that will be used to place these metadata files in the / ttconfig directory of the TimesTen containers. For more information about metadata files and using a ConfigMap, see About Configuration Metadata Details and Populate the /ttconfig Directory.

5. Create a YAML file that defines the variables for your configuration.

```
vi customyaml/samplettc.yaml

storageClassName: oci-bv
storageSize: 10Gi
image:
   repository: phx.ocir.io/youraccount/tt2211190image
   tag: "1"
   pullPolicy: Always
imagePullSecret: sekret
dbConfigMap:
   - name: samplettc
   directory: cm
```

The customizations are as follows:

- The storage class name is oci-bv.
- The storage size is 10Gi.
- Since the container image you built and want to use is phx.ocir.io/youraccount/tt2211190image:1, the value of the repository variable is phx.ocir.io/youraccount/tt2211190image and the value of the tag variable is 1.
- The image pull Secret is sekret.
- The name of the Kubernetes ConfigMap is samplettc. The location of the metadata files is the cm directory. This directory is located within the kube_files/helm/ ttclassic directory tree.



To deploy an active standby pair of TimesTen databases, install the ttclassic chart.

helm install -f customyaml/samplettc.yaml samplettc ./ttclassic

Let's look at this helm install command:

- The -f option is used to pass the customized YAML file to the helm install command.
- The name of the file that contains the customizations is samplettc.yaml, which is located in the customyaml directory.
- The name of the release is samplettc.
- The name of the chart that installs the TimesTen Operator is ttclassic, which is located in the helm/ttclassic directory.

Let's look at the output from the helm install command.

```
NAME: samplettc
LAST DEPLOYED: Mon Oct 23 23:18:03 2023
NAMESPACE: mynamespace
STATUS: deployed
REVISION: 1
NOTES:
Version 2211190.1.0 of the ttclassic chart has been installed.
This release is named "samplettc".

To learn more about the release, try:

$ helm status samplettc
$ helm get all samplettc
$ helm history samplettc

To rollback to a previous version of the chart, run:

$ helm rollback samplettc <REVISION>
- run 'helm history samplettc' for a list of revisions.
```

Note the following:

- The ttclassic chart version is 2211190.1.0 corresponding to the 22.1.1.19.0 TimesTen release.
- The release name is samplettc.
- The status of the release is deployed.
- 7. (Optional) Verify the release.

helm list



Output.

NAME NAMESPACE REVISION UPDATED STATUS

CHART APP VERSION

samplettc mynamespace 1 2023-10-23

23:18:03.740512897 +0000 UTC deployed ttclassic-2211190.1.0

22.1.1.19.0

samplettop mynamespace 1 2023-10-23

23:04:40.492890589 +0000 UTC deployed ttoperator-2211190.1.0

22.1.1.19.0

ttcrd mynamespace 1 2023-10-17 22:00:53.530832896 +0000 UTC deployed ttcrd-2211190.1.0

22.1.1.19.0

The helm list command shows the samplettc release exists and is installed in your namespace.

8. Wait a few minutes, then confirm the TimesTenClassic object is deployed in your namespace and is in the Normal state.

kubectl get ttc samplettc

Output.

NAME STATE ACTIVE AGE samplettc Normal samplettc-0 114s

The samplette TimesTenClassic object is deployed and is in the Normal state.

9. Confirm the ConfigMap was created and the metadata files are in the ConfigMap.

kubectl get configmap samplettc

Output.

NAME DATA AGE samplettc 4 2m17s

Check metadata files.

kubectl describe configmap samplettc

Output.

Name: samplettc
Namespace: mynamespace

Labels: app.kubernetes.io/managed-by=Helm
Annotations: meta.helm.sh/release-name: samplettc

meta.helm.sh/release-namespace: mynamespace

Data



```
adminUser:
----
adminuser/adminuserpwd

db.ini:
----
PermSize=200
DatabaseCharacterSet=AL32UTF8

schema.sql:
----
create table adminuser.emp (id number not null primary key, name char (32));

testUser:
----
sampletestuser/sampletestuserpwd1

BinaryData
====
Events: <none>
```

The samplettc ConfigMap was created and the metadata files are included in the ConfigMap. Since the testUser is defined, you can use Helm to test TimesTen. See Test TimesTen.

10. (Optional) Confirm the active and standby Pods are running.

```
kubectl get pods
```

Output.

NAME	READY	STATUS	RESTARTS
AGE			
samplettc-0	3/3	Running	0
2m51s			
samplettc-1	3/3	Running	0
2m41s			
timesten-operator-65ddf9cfbb-jkqbn	1/1	Running	0
12m			

The samplettc-0 and samplettc-1 Pods are running in your namespace.

Congratulations! You successfully installed the ttclassic chart. An active standby pair of TimesTen Classic databases is deployed in your namespace. Both the active and standby databases are up and running.



Test TimesTen

To test TimesTen, the test Pod runs a script that attempts to connect to the TimesTen database by using TimesTen's client/server access. If the script can connect to the database, the script then looks at internal metadata to verify that the database is functioning properly.

The test connects to the database as the test user. The TimesTen Operator provides the testUser metadata file that lets you define this test user. For more information about the testUser metadata file and this test user, see testUser and Install TimesTen Databases.

If you do not define a test user, the test fails. If you do define a test user, the user only has CONNECT privileges. This limits the test and the test user's access to the database.

The test verifies that the active standby pair of TimesTen Classic databases are up and running and that replication between them is functional.

To test TimesTen, you test the ttclassic chart release running in your namespace. Let's test TimesTen.

1. Confirm the ttclassic release.

helm list

Output.

NAME	NAMESPACE	REVISIO	N
UPDATED			STATUS
CHART	APP VI	ERSION	
samplettc	mynamespace	1	2023-10-23
23:18:03.7405128	897 +0000 UTC o	deployed	ttclassic-2211190.1.0
22.1.1.19.0			
samplettop	mynamespace	1	2023-10-23
23:04:40.492890	589 +0000 UTC (deployed	ttoperator-2211190.1.0
22.1.1.19.0			
ttcrd	mynamespace	1	2023-10-17
22:00:53.5308328	896 +0000 UTC (deployed	ttcrd-2211190.1.0
22.1.1.19.0			

The samplettc release is installed in your namespace. You installed this release in Install TimesTen Databases.

2. Confirm the TimesTenClassic object is running in your namespace.

```
kubectl get ttc samplettc
```

Output.

NAME STATE ACTIVE AGE samplettc Normal samplettc-0 10m

The samplette TimesTenClassic object is deployed in your namespace.



3. Test TimesTen.

```
helm test samplettc
```

Output.

```
NAME: samplettc
LAST DEPLOYED: Mon Oct 23 23:18:03 2023
NAMESPACE: mynamespace
STATUS: deployed
REVISION: 1
TEST SUITE:
               samplettc-ttclassic-test
Last Started: Mon Oct 23 23:29:27 2023
Last Completed: Mon Oct 23 23:29:32 2023
Phase:
               Succeeded
NOTES:
Version 2211190.1.0 of the ttclassic chart has been installed.
This release is named "samplettc".
To learn more about the release, try:
 $ helm status samplettc
 $ helm get all samplettc
 $ helm history samplettc
To rollback to a previous version of the chart, run:
  $ helm rollback samplettc <REVISION>
    - run 'helm history samplettc' for a list of revisions.
```

The test for the samplettc release succeeded. Since the test succeeded, the test Pod is deleted.

Congratulations! You successfully tested TimesTen. The active and standy databases are up and running and replication between them is functional.

Upgrade the TimesTen Custom Resource Definitions (CRDs)

To upgrade the TimesTen Custom Resource Definitions (CRDs) in your cluster, use the ttcrd chart from the new release.

This example upgrades from TimesTen release 22.1.1.19.0 to 22.1.1.20.0. For more information about TimesTen releases, see Overview of release numbers in the Oracle TimesTen In-Memory Database Installation, Migration, and Upgrade Guide.

Let's assume you previously created the <code>new_kube_files</code> directory and unpacked the new release of the TimesTen Operator distribution into this directory.



1. Review the current ttcrd release that is deployed in your namespace.

helm list

Output.

NAME NAMESPACE REVISION UPDATED STATUS CHART APP VERSION 2023-10-23 samplettc mynamespace 1 ttclassic-2211190.1.0 23:18:03.740512897 +0000 UTC deployed 22.1.1.19.0 samplettop 1 2023-10-23 mynamespace 23:04:40.492890589 +0000 UTC deployed ttoperator-2211190.1.0 22.1.1.19.0 ttcrd mynamespace 1 2023-10-17 22:00:53.530832896 +0000 UTC deployed ttcrd-2211190.1.0 22.1.1.19.0

The ttcrd chart version is 2211190.1.0 and appversion is 22.1.1.19.0 corresponding to the TimesTen 22.1.1.19.0 release.

2. On your development host, change to the new kube files/helm directory.

```
cd new kube files/helm
```

This directory contains the new release of the charts. For more information about the helm directory, see Set Up the Environment .

3. Upgrade to the new release.

```
helm upgrade ttcrd ./ttcrd
```

Output.

```
Release "ttcrd" has been upgraded. Happy Helming!

NAME: ttcrd

LAST DEPLOYED: Tue Oct 24 16:00:21 2023

NAMESPACE: mynamespace

STATUS: deployed

REVISION: 2

NOTES:

Version 2211200.1.0 of the ttoperator chart has been installed.

This release is named "ttcrd".

To learn more about the release, try:

$ helm status ttcrd
$ helm get all ttcrd
$ helm history ttcrd
```

To rollback to a previous version of the chart, run:



```
$ helm rollback ttcrd <REVISION>
- run 'helm history ttcrd' for a list of revisions.
```

The TimesTen CRDs are upgraded to the new release. The ttcrd chart's version is 2211200.1.0.

Congratulations! You successfully upgraded the TimesTen CRDs.

Upgrade the TimesTen Operator

You can upgrade the TimesTen Operator to a new release. You can perform the upgrade while there are TimesTenClassic or TimesTenScaleout objects deployed in your namespace.

To upgrade the TimesTen Operator in your namespace, use the ttoperator chart from the new release.

This example upgrades from TimesTen release 22.1.1.19.0 to 22.1.1.20.0. For more information about TimesTen releases, see Overview of release numbers in the Oracle TimesTen In-Memory Database Installation, Migration, and Upgrade Guide.

Let's assume you previously created the <code>new_kube_files</code> directory and unpacked the new release of the TimesTen Operator distribution into this directory.

The ttoperator chart contains all the information necessary to upgrade the TimeTen Operator in your namespace. The chart contains a default configuration for deploying a new release of the TimesTen Operator. In addition, if the default container image is not the image you want to upgrade to, you can modify the ttoperator's chart default image variable to reference your new container image. For example, if the default container image for the new release is container-registry.oracle.com/timesten/timesten/22.1.1.20.0 and instead you want to use your newly built phx.ocir.io/youraccount/tt2211200image:2 container image, you modify the image variable as follows:

```
image:
    repository: phx.ocir.io/youraccount/tt2211200image
    tag: "2"
```

Let's walk through an example illustrating how to upgrade the TimesTen Operator to a new release. In the example, let's assume you want to use your phx.ocir.io/youraccount/tt2211200image:2 container image.

The example uses a customized YAML file to define the container image that contains the new release. Let's assume you have previously created a <code>new_kube_files/helm/customyaml</code> directory for your customized YAML files.

1. Verify the TimesTen Operator that is deployed in your namespace is running the expected image.

Review Pods.

```
kubectl get pods
NAME READY STATUS RESTARTS
AGE
```



samplettc-0	3/3	Running	0	14h
samplettc-1	3/3	Running	0	14h
timesten-operator-65ddf9cfbb-jkqbn	1/1	Running	0	15h

Verify the TimesTen Operator is running the expected image.

```
kubectl get pod timesten-operator-65ddf9cfbb-jkqbn -o yaml | grep image
```

Output.

```
image: phx.ocir.io/youraccount/tt2211190image:1
imagePullPolicy: Always
```

The TimesTen Operator is running the expected image. See Install the TimesTen Operator.

2. On your development host, change to the helm directory of the new release.

```
cd new_kube_files/helm
```

This directory contains the new release of the charts. For more information about the helm directory, see Set Up the Environment .

3. Create a YAML file that references the new container image.

```
vi customyaml/upgradeoperator.yaml
image:
   repository: phx.ocir.io/youraccount/tt2211200image
   tag: "2"
imagePullSecrets:
   - name: sekret
```

The customizations are as follows:

- Since the container image you built and want to use for the upgrade is phx.ocir.io/youraccount/tt2211200image:2, the value of the repository variable is phx.ocir.io/youraccount/tt2211200image and the value of the tag variable is 2.
- The image pull Secret is sekret.
- 4. Confirm the name of the TimesTen Operator release.

```
helm list
```

Output.

NAME	NAMESPACE	REVISIO	N		
UPDATED			STATUS		
CHART	APP V	ERSION			
samplettc	mynamespace	1	2	023-10-23	
23:18:03.74051	2897 +0000 UTC	deployed	ttcl	assic-2211190.	1.0



```
22.1.1.19.0

samplettop mynamespace 1 2023-10-23
23:04:40.492890589 +0000 UTC deployed
ttoperator-2211190.1.0 22.1.1.19.0
ttcrd mynamespace 2 2023-10-24
16:00:21.530832896 +0000 UTC deployed
ttcrd-2211200.1.0 22.1.1.20.0
```

The helm list command shows the samplettop release exists and is installed in your namespace. For more information about installing the TimesTen Operator, see Install the TimesTen Operator.

5. Upgrade the TimesTen Operator to the new release. To upgrade the TimesTen Operator, use the ttoperator chart from the new release and use the customized YAML file that references the new image.

```
helm get values samplettop --all > prev-values-ttop.yaml && helm upgrade -f prev-values-ttop.yaml -f customyaml/ upgradeoperator.yaml samplettop ./ttoperator
```

Let's look at this helm upgrade command:

- The get values samplettop Helm command retrieves the values for the current release, including existing customizations. The result of this command is piped into the prev-values-ttop.yaml file. You can choose any name for this file.
- The helm upgrade command uses the prev-values-ttop.yaml file with the customized upgradeoperator.yaml file to do the upgrade.



We recommend this syntax. This ensures existing customizations are preserved.

Let's look at the output from the helm upgrade command.

\$ helm history samplettop

```
Release "samplettop" has been upgraded. Happy Helming!

NAME: samplettop

LAST DEPLOYED: Tue Oct 24 16:15:21 2023

NAMESPACE: mynamespace

STATUS: deployed

REVISION: 2

NOTES:

Version 2211200.1.0 of the ttoperator chart has been installed.

This release is named "samplettop".

To learn more about the release, try:

$ helm status samplettop

$ helm get all samplettop
```



```
To rollback to a previous version of the chart, run:

$ helm rollback samplettop <REVISION>
- run 'helm history samplettop' for a list of revisions.

To test the operator, run:

$ helm test samplettop
```

Note the following:

- The samplettop release is upgraded. The release revision is 2.
- The status of the release is deployed.
- The ttoperator chart version is 2211200.1.0 corresponding to the 22.1.1.20.0 TimesTen release.
- **6.** Verify the TimesTen Operator is running in your namespace.

```
kubectl get pods
NAME
                                     READY
                                             STATUS
                                                       RESTARTS
                                                                  AGE
samplettc-0
                                     3/3
                                             Running
                                                       0
                                                                  17h
                                                                  17h
samplettc-1
                                     3/3
                                             Running 0
timesten-operator-767b8f9477-1297n
                                     1/1
                                             Running 0
                                                                  2m53s
```

7. Verify the TimesTen Operator is running the new image.

```
kubectl get pod timesten-operator-767b8f9477-1297n -o yaml | grep image
```

Output.

```
image: phx.ocir.io/youraccount/tt2211200image:2
imagePullPolicy: Always
```

The TimesTen Operator is running the new image.

8. (Optional): Test the ttoperator release.

```
helm test samplettop
```

Output.

```
NAME: samplettop

LAST DEPLOYED: Tue Oct 24 16:15:21 2023

NAMESPACE: mynamespace

STATUS: deployed

REVISION: 2

TEST SUITE: samplettop-ttoperator-test

Last Started: Tue Oct 24 16:32:15 2023

Last Completed: Tue Oct 24 16:32:18 2023

Phase: Succeeded
```



```
NOTES:
Version 2211200.1.0 of the ttoperator chart has been installed.
This release is named "samplettop".

To learn more about the release, try:

$ helm status samplettop
$ helm get all samplettop
$ helm history samplettop

To rollback to a previous version of the chart, run:

$ helm rollback samplettop <REVISION>
- run 'helm history samplettop' for a list of revisions.

To test the operator, run:

$ helm test samplettop
```

The test succeeded.

Congratulations! You successfully upgraded the ttoperator chart. The TimesTen Operator that is running in your namespace is using the new image.

Upgrade TimesTen

You can upgrade a TimesTenClassic object and its active standby pair of TimesTen Classic databases to a new TimesTen release.

To upgrade TimesTen, use the ttclassic chart from the new release.

This example upgrades from TimesTen release 22.1.1.19.0 to 22.1.1.20.0. For more information about TimesTen releases, see Overview of release numbers in the *Oracle TimesTen In-Memory Database Installation, Migration, and Upgrade Guide*.

Let's assume you previously created the new_kube_files directory and unpacked the new release of the TimesTen Operator distribution into this directory.

The ttclassic chart contains all the information necessary to upgrade an active standby pair of TimesTen Classic databases that are deployed in your namespace. The chart contains a default configuration for deploying a new release of TimesTen. In addition, if the default container image is not the image you want to upgrade to, you can modify the ttclassic's chart default image variable to reference your new container image. For example, if the default container image for the new release is container-registry.oracle.com/timesten/timesten/22.1.1.20.0 and instead you want to use your newly built phx.ocir.io/youraccount/tt2211200image:2 container image, you modify the image variable in the following way:

```
image:
    repository: phx.ocir.io/youraccount/tt2211200image
    tag: "2"
```



Let's walk through an example illustrating how to upgrade the ttclassic chart, which upgrades an active standby pair of TimesTen databases to a new release. In the example, let's assume you want to use your phx.ocir.io/youraccount/tt2211200image:2 container image.

The example uses a customized YAML file to define the container image that contains the new release. Let's assume you have previously created a <code>new_kube_files/helm/customyaml</code> directory for your customized YAML files.



When an upgrade is performed, the standby is terminated first. It takes some time for the standby to come back up. During this wait period, the standby is upgraded to the new release. During the upgrade of the standby, depending on your replication configuration, there may be disruption on the active database. This may impact your applications. Next, the failover from the active to the standby occurs. The active is terminated. There is a wait period for the former active to come back up. During this wait period, the active is upgraded to the new release. The standby database is promoted to the active and the former active becomes the standby.

Ensure you perform an upgrade at the appropriate time. We recommend that you do not perform upgrades at the busiest time of a production day. Applications see shortages and perhaps reduced performance as a result of the upgrade procedure.

1. Review the TimesTenClassic object is deployed and is in the Normal state.

```
kubectl get ttc samplettc
```

Output.

```
NAME STATE ACTIVE AGE samplettc Normal samplettc-0 20h
```

2. Verify the TimesTenClassic object is running the expected image.

```
kubectl get ttc samplettc -o yaml | grep image
```

Output.

image: phx.ocir.io/youraccount/tt2211190image:1

imagePullPolicy: Always
imagePullSecret: sekret
imageUpdatePending: false

The TimesTenClassic object is running the expected image.

3. On your development host, change to the helm directory of the new release.

```
cd new kube files/helm
```



This directory contains the new release of the charts. For more information about the helm directory, see Set Up the Environment .

4. Create a YAML file that references the new container image.

```
vi customyaml/samplettc.yaml
image:
  repository: phx.ocir.io/youraccount/tt2211200image
  tag: "2"
imagePullSecret: sekret
```

The customizations are as follows:

- Since the container image you built and want to use for the upgrade is phx.ocir.io/youraccount/tt2211200image:2, the value of the repository variable is phx.ocir.io/youraccount/tt2211200image and the value of the tag variable is 2.
- The image pull Secret is sekret.
- 5. Confirm the name of the release for the ttclassic chart.

helm list

Output.

NAME	NAMESPACE	REVISIO	N	
UPDATED			STATUS	
CHART	APP VER	RSION		
samplettc	mynamespace	1		2023-10-23
23:18:03.740512	897 +0000 UTC de	ployed		
ttclassic-22111	90.1.0 22.1.1.	19.0		
samplettop	mynamespace	2		2023-10-24
16:15:24.896107	706 +0000 UTC de	ployed		
ttoperator-2211	200.1.0 22.1.1.	20.0		
ttcrd	mynamespace	2		2023-10-24
16:10:21.530832	896 +0000 UTC de	ployed		
ttcrd-2211200.1	.0 22.1.1.	20.0		

The helm list command shows the samplette release exists and is installed in your namespace.

6. Upgrade the TimesTenClassic object and its active standby pair of databases to a new release. To upgrade, use the ttclassic chart from the new release and use the customized YAML file that references the new image.

```
helm get values samplettc --all > prev-values-ttc.yaml && helm upgrade -f prev-values-ttc.yaml -f customyaml/upgradettc.yaml samplettc ./ttclassic
```

Let's look at this helm upgrade command:

 The get values samplettc Helm command retrieves the values for the current release, including existing customizations. The result of this command



is piped into the prev-values-ttc.yaml file. You can choose any name for this file.

• The helm upgrade command uses the prev-values-ttc.yaml file with the customized upgradettc.yaml file to do the upgrade.



We recommend this syntax. This ensures existing customizations are preserved.

Let's look at the output from the helm upgrade command.

```
Release "samplettc" has been upgraded. Happy Helming!
NAME: samplettc
LAST DEPLOYED: Tue Oct 24 19:55:45 2023
NAMESPACE: mynamespace
STATUS: deployed
REVISION: 2
NOTES:
Version 2211200.1.0 of the ttclassic chart has been installed.
This release is named "samplettc".
To learn more about the release, try:
 $ helm status samplettc
 $ helm get all samplettc
 $ helm history samplettc
To rollback to a previous version of the chart, run:
 $ helm rollback samplettc <REVISION>
    - run 'helm history samplettc' for a list of revisions.
```

Note the following:

- The samplettc release is upgraded. The release revision is 2.
- The status of the release is deployed.
- The ttclassic chart version is 2211200.1.0 corresponding to the 22.1.1.20.0 TimesTen release.
- The TimesTenClassic object will be replaced by one that is using the new image. This causes the TimesTen Operator to automatically upgrade both databases in the active standby pair to the new release.
- Observe the automatic upgrade.

kubectl describe ttc samplettc



Output.

Name: samplettc Namespace: mynamespace Labels: app.kubernetes.io/managed-by=Helm Annotations: meta.helm.sh/release-name: samplettc meta.helm.sh/release-namespace: mynamespace Events: Type Reason Age From Message --------Normal Upgrade 7m44s timesten Image updated, automatic upgrade started Normal Upgrade 7m44s timesten Deleted standby pod samplettc-1 during upgrade Normal Info 6m43s timesten Pod samplettc-1 Agent Down Normal Info 6m42s timesten Pod samplettc-1 Agent Up Normal Info 6m42s timesten Pod samplettc-1 Instance Exists Normal Info 6m42s timesten Pod samplettc-1 Daemon Down Normal StateChange 6m42s timesten Pod samplettc-1 is Not Ready Warning StateChange 6m42s timesten TimesTenClassic was Normal, now ActiveTakeover Normal StateChange 6m42s timesten TimesTenClassic was ActiveTakeover, now StandbyDown Normal Info 6m42s timesten Pod samplettc-1 Agent Down Normal Info 6m37s timesten Pod samplettc-1 Agent Up Normal Info 6m37s timesten Pod samplettc-1 Instance Exists Normal Info 6m37s timesten Pod samplettc-1 Daemon Down Normal Info 6m37s timesten Pod samplettc-1 Daemon Up Normal Info 6m37s timesten Pod samplettc-1 Database Unloaded Normal 6m35s timesten Pod samplettc-1 Database Info None DEBUG Info 6m32s timesten pollAsyncStatus: Async polling for RepDuplicate, timeout in 597 secs Info 6m29s timesten pollAsyncStatus: Async DEBUG polling for RepDuplicate, timeout in 594 secs 6m26s timesten pollAsyncStatus: Async DEBUG Info polling for RepDuplicate, timeout in 591 secs DEBUG Info 6m23s timesten pollAsyncStatus: Async polling for RepDuplicate, timeout in 588 secs 6m20s timesten Pod samplettc-1 Database Normal Info Loaded Normal Info 6m19s timesten Pod samplettc-1 RepAgent Not Running Normal 6m19s timesten Pod samplettc-1 RepScheme Info Exists StateChange 6m19s timesten Pod samplettc-1 RepState Normal TDLE Normal Info 6m14s timesten Pod samplettc-1 RepAgent Running Normal StateChange 6m14s timesten TimesTenClassic was



StandbyDow	StandbyDown, now StandbyStarting				
Normal	StateChange	6m13s	timesten	TimesTenClassic was	
StandbySta	rting, now St	andbyCa	tchup		
Normal	StateChange	5m36s	timesten	Pod samplettc-1 RepState STANDBY	
Normal	Upgrade	5m36s	timesten	Upgrade of standby complete	
Normal	StateChange	5m36s	timesten	TimesTenClassic was	
StandbyCat	chup, now Nor	mal			
Normal	Upgrade	5m4s	timesten	Deleted active pod samplettc-0	
during upo	grade				
Normal	Info	5m4s	timesten	Pod samplettc-0 Agent Down	
Normal			timesten	Pod samplettc-0 is Not Ready	
Normal	StateChange	4m59s	timesten	Pod samplettc-0 is Not Active	
Ready					
Normal	StateChange	4m59s	timesten	Pod samplettc-1 is Ready	
Warning	StateChange	4m59s	timesten	TimesTenClassic was Normal, now	
ActiveDown	1				
Normal	Info	4m57s	timesten	Pod samplettc-1 Database	
Updatable					
Normal	StateChange	4m57s	timesten	Pod samplettc-1 RepState ACTIVE	
Normal	StateChange	4m57s	timesten	Pod samplettc-1 is Not Ready	
Normal	StateChange	4m57s	timesten	TimesTenClassic was ActiveDown,	
now Active					
Normal	StateChange	4m56s		Pod samplettc-1 is Ready	
Normal	2	4m56s	timesten	Pod samplettc-1 is Active Ready	
Normal	StateChange	4m56s	timesten	TimesTenClassic was	
ActiveTake	over, now Sta	ndbyDow	n		
Normal	Info	4m6s	timesten	Pod samplettc-0 Agent Up	
Normal	Info	4m6s	timesten	Pod samplettc-0 Instance Exists	
Normal	Info	4m6s	timesten	Pod samplettc-0 Daemon Down	
Normal	Info	4m6s	timesten	Pod samplettc-0 Daemon Up	
Normal	Info	4m6s	timesten	Pod samplettc-0 Database Unloaded	
Normal	Info	4m4s	timesten	Pod samplettc-0 Database None	
DEBUG	Info	4m1s	timesten	pollAsyncStatus: Async polling	
for RepDup	olicate, timeo	ut in 5	97 secs		
DEBUG	Info	3m58s	timesten	pollAsyncStatus: Async polling	
for RepDup	olicate, timeo	ut in 5	94 secs		
DEBUG	Info	3m55s	timesten	pollAsyncStatus: Async polling	
for RepDup	olicate, timeo				
DEBUG	Info	3m52s		pollAsyncStatus: Async polling	
	olicate, timed				
Normal	Info	3m48s		Pod samplettc-0 Database Loaded	
Normal	Info	3m48s	timesten	Pod samplettc-0 RepAgent Not	
Running					
Normal	Info	3m48s	timesten	Pod samplettc-0 RepScheme Exists	
Normal	StateChange	3m48s	timesten	Pod samplettc-0 RepState IDLE	
Normal	Info	3m43s	timesten	Pod samplettc-0 RepAgent Running	
Normal	StateChange	3m43s	timesten	TimesTenClassic was StandbyDown,	
now Standb					
Normal	StateChange	3m42s	timesten	TimesTenClassic was	
=	rting, now St	_			
Normal	StateChange	2m56s	timesten	Pod samplettc-0 RepState STANDBY	
Normal	Upgrade	2m56s	timesten	Upgrade of active complete	
Normal	Upgrade	2m56s	timesten	Upgrade completed in 288 secs	
Normal	StateChange	2m56s	timesten	TimesTenClassic was	
StandbyCat	chup, now Nor	mal			



8. Confirm the TimesTenClassic object is in the Normal state.

```
kubectl get ttc samplettc
```

Output.

```
NAME STATE ACTIVE AGE samplettc Normal samplettc-1 20h
```

The TimesTenClassic object is in the Normal state. The samplettc-1 is now the active.

9. Confirm the TimesTenClassic object is running the new image.

```
kubectl get ttc samplettc -o yaml | grep image
```

Output.

```
image: phx.ocir.io/youraccount/tt2211200image:2
imagePullPolicy: Always
imagePullSecret: sekret
imageUpdatePending: false
```

The TimesTenClassic object is running the new image.

10. (Optional): Test the ttclassic release.

```
helm test samplettc
```

Output.

```
NAME: samplettc
LAST DEPLOYED: Tue Oct 24 19:55:45 2023
NAMESPACE: mynamespace
STATUS: deployed
REVISION: 2
TEST SUITE:
              samplettc-ttclassic-test
Last Started: Tue Oct 24 20:12:30 2023
Last Completed: Tue Oct 24 20:12:35 2023
Phase:
              Succeeded
Version 2211200.1.0 of the ttclassic chart has been installed.
This release is named "samplettc".
To learn more about the release, try:
  $ helm status samplettc
  $ helm get all samplettc
  $ helm history samplettc
To rollback to a previous version of the chart, run:
```



```
$ helm rollback samplettc <REVISION>
- run 'helm history samplettc' for a list of revisions.
```

The test for revision 2 of the samplettc release succeeded.

11. Confirm the samplettc release is upgraded.

helm list

Output.

NAME	NAMESPACE	REVISIO	Ň
UPDATED			STATUS
CHART	APP V	ERSION	
samplettc	mynamespace	2	2023-10-24
19:55:45.303709	067 +0000 UTC	deployed	ttclassic-2211200.1.0
22.1.1.20.0			
samplettop	mynamespace	2	2023-10-24
16:15:35.896107	706 +0000 UTC	deployed	ttoperator-2211200.1.0
22.1.1.20.0			
ttcrd	mynamespace	2	2023-10-24
16:00:21.530832	896 +0000 UTC	deployed	ttcrd-2211200.1.0
22.1.1.20.0			

The ttclassic chart version is 2211200.1.0 corresponding to the 22.1.1.20.0 TimesTen release.

Congratulations! You successfully performed the upgrade. The TimesTenClassic object is upgraded and is in the Normal state. The associated active standby pair of TimesTen Classic databases are upgraded. Both databases are up and running.

Roll Back a TimesTen Upgrade

You can use Helm to roll back a TimesTen upgrade. This reverts the TimesTenClassic object and its associated active standby pair of TimesTen Classic databases to the initial release.

Let's assume you upgraded TimesTen as discussed in Upgrade TimesTen. However, you now want to roll back the upgrade. Here's how to perform the rollback using Helm.

This example downgrades from TimesTen release 22.1.1.20.0 to 22.1.1.19.0. For more information about TimesTen releases, see Overview of release numbers in the *Oracle TimesTen In-Memory Database Installation, Migration, and Upgrade Guide*.



Ensure you perform a downgrade at the appropriate time. We recommend that you do not perform a downgrade at the busiest time of a production day. Applications see shortages and perhaps reduced performance as a result of the downgrade procedure.



1. Review the current release of the ttclassic chart that is deployed in your namespace.

helm list

Output.

NAME	NAMESPACE	REVISIO	N	
UPDATED			STATUS	
CHART	APP V	/ERSION		
samplettc	mynamespace	2		2023-10-24
19:55:45.303709	067 +0000 UTC	deployed		
ttclassic-22112	00.1.0 22.1.	.1.20.0		
samplettop	mynamespace	2		2023-10-24
16:15:21.796835	95 +0000 UTC	deployed		
ttoperator-2211	200.1.0 22.1.	.1.20.0		
ttcrd	mynamespace	2		2023-10-24
16:00:21.530832	896 +0000 UTC	deployed		
ttcrd-2211200.1	.0 22.1.	.1.20.0		

The samplettc release that is deployed is revision 2. The ttclassic chart version is 2211200.1.0 corresponding to the 22.1.1.20.0 TimesTen release.

2. Review the ttclassic chart's revision history.

helm history samplettc

Output.

REVISION	UPDATED			STATUS
CHART		APP VERSION	DESCRIPT	TION
1	Mon Oct	23 23:18:03	2023	superseded
ttclassic-22111	90.1.0	22.1.1.19.0	Install	complete
2	Tue Oct	24 19:55:45	2023	deployed
ttclassic-22112	00.1.0	22.1.1.20.0	Upgrade	complete

Revision 2 of the samplettc ttclassic chart is currently deployed. The ttclassic chart version for revision 1 is 2211190.1.0 corresponding to TimesTen release 22.1.1.19.0.

3. Roll back to revision 1.

 $\verb|helm rollback samplettc 1|\\$

Output.

Rollback was a success! Happy Helming!



4. Review the revision history.

helm history samplettc

Output.

REVISION	UPDATED			STATUS
CHART		APP VERSION	DESCRIPT	TION
1	Mon Oct	23 23:18:03	2023	superseded
ttclassic-22111	90.1.0	22.1.1.19.0	Install	complete
2	Tue Oct	24 19:55:45	2023	superseded
ttclassic-22112	00.1.0	22.1.1.20.0	Upgrade	complete
3	Tue Oct	24 21:31:06	2023	deployed
ttclassic-22111	90.1.0	22.1.1.19.0	Rollback	to 1

Revision 3 of the samplettc release is now deployed in your namespace. The ttclassic chart version is 2211190.1. The TimesTenClassic object is replaced, which triggers the TimesTen Operator to initiate an downgrade to TimesTen release 22.1.1.19.0.

5. Observe the downgrade.

kubectl describe ttc samplettc

Output.

Name:	samplettc			
Namespace:	mynamespa	ce		
Labels: app.kubernetes.io/managed				by=Helm
Events:				
Type	Reason	Age	From	Message
Normal	Upgrade	6m38s	timesten	Image updated, automatic upgrade
started				
Normal	Upgrade	6m38s	timesten	Deleted standby pod samplettc-0
during upg	rade			
Normal	Info	6m34s	timesten	Pod samplettc-0 Agent Down
Normal	StateChange	6m34s	timesten	Pod samplettc-0 is Not Ready
Warning	StateChange	6m34s	timesten	TimesTenClassic was Normal, now
ActiveTakeover				
Normal	StateChange	6m33s	timesten	TimesTenClassic was
ActiveTake	over, now Sta	ndbyDow	n	
Normal	Info	5m38s	timesten	Pod samplettc-0 Agent Up
Normal	Info	5m38s	timesten	Pod samplettc-0 Instance Exists
Normal	Info	5m38s	timesten	Pod samplettc-0 Daemon Down
Normal	Info	5m37s	timesten	Pod samplettc-0 Daemon Up
Normal	Info	5m37s	timesten	Pod samplettc-0 Database Unloaded
Normal	Info	5m35s	timesten	Pod samplettc-0 Database None
DEBUG	Info	5m32s	timesten	pollAsyncStatus: Async polling
for RepDup	licate, timeo	ut in 5	97 secs	
DEBUG	Info	5m29s	timesten	pollAsyncStatus: Async polling
for RepDup	licate, timeo	ut in 5	94 secs	
DEBUG	Info	5m26s	timesten	pollAsyncStatus: Async polling

for RenDur	licate, timeo	11t in 5	91 secs		
DEBUG	Info	5m23s	timesten	pollAsyncStatus: Async	,
	r RepDuplicat			secs	
DEBUG	Info	5m20s	timesten	pollAsyncStatus: Async	,
	r RepDuplicat				
Normal	Info	5m16s	timesten	Pod samplettc-0 Databa	990
Loaded	11110	JIIII OJ	CIMCSCCII	Tod Samplecee o Databe	150
Normal	Info	5m16s	timesten	Pod samplettc-0 RepAge	nt
Not Runnin		0111100	CIMODOCII	Tod bampiette o Reprige	211 C
Normal	Tnfo	5m16s	timesten	Pod samplettc-0 RepSch	neme
Exists	11110	01112 00	01111000011	Tod Dampieces o Reposi	TOMO
Normal	StateChange	5m16s	timesten	Pod samplettc-0 RepSta	ate
IDLE	2000001101190	02 00	02000011	Tod Sampleson t Repose	
Normal	Info	5m11s	timesten	Pod samplettc-0 RepAge	ent.
Running	11120	02.20	02000011	Tod Sampleson t Hopily	,,,,
Normal	StateChange	5m11s	timesten	Pod samplettc-0 RepSta	ate
STANDBY					
Normal	StateChange	5m11s	timesten	Pod samplettc-0 is Rea	adv
Normal	Upgrade	5m10s	timesten	Upgrade of standby com	_
Normal	StateChange	5m10s	timesten	TimesTenClassic was	•
StandbyDow	n, now Normal				
Normal	Upgrade	4m39s	timesten	Deleted active pod	
samplettc-	·1 during upgr	ade		-	
Normal	Info	3m38s	timesten	Pod samplettc-1 Agent	Down
Normal	StateChange	3m38s	timesten	Pod samplettc-1 is Not	
Ready	,			-	
Normal	StateChange	3m38s	timesten	Pod samplettc-1 is Not	-
Active Rea	ıdy			<u>-</u>	
Warning	StateChange	3m38s	timesten	TimesTenClassic was	
=	StateChange w ActiveDown	3m38s	timesten	TimesTenClassic was	
=	=	3m38s 3m37s	timesten timesten	TimesTenClassic was Pod samplettc-0 Databa	ase
Normal, no	w ActiveDown				ase
Normal, no	w ActiveDown				
Normal, no Normal Updatable	w ActiveDown Info	3m37s	timesten	Pod samplettc-0 Databa	
Normal, no Normal Updatable Normal	w ActiveDown Info	3m37s	timesten	Pod samplettc-0 Databa	ate
Normal, no Normal Updatable Normal ACTIVE	w ActiveDown Info StateChange	3m37s	timesten timesten	Pod samplettc-0 Databa Pod samplettc-0 RepSta	ate
Normal, no Normal Updatable Normal ACTIVE Normal	w ActiveDown Info StateChange	3m37s	timesten timesten	Pod samplettc-0 Databa Pod samplettc-0 RepSta	ate
Normal, no Normal Updatable Normal ACTIVE Normal Ready Normal	ow ActiveDown Info StateChange StateChange	3m37s 3m37s 3m37s 3m37s	timesten timesten timesten timesten	Pod samplettc-0 Databa Pod samplettc-0 RepSta Pod samplettc-0 is Not	ate
Normal, no Normal Updatable Normal ACTIVE Normal Ready Normal	ActiveDown Info StateChange StateChange StateChange	3m37s 3m37s 3m37s 3m37s 3m37s	timesten timesten timesten timesten	Pod samplettc-0 Databa Pod samplettc-0 RepSta Pod samplettc-0 is Not	ate
Normal, no Normal Updatable Normal ACTIVE Normal Ready Normal	ActiveDown Info StateChange StateChange StateChange At now ActiveT	3m37s 3m37s 3m37s 3m37s 3m37s	timesten timesten timesten timesten	Pod samplettc-0 Databa Pod samplettc-0 RepSta Pod samplettc-0 is Not TimesTenClassic was	nte E
Normal, no Normal Updatable Normal ACTIVE Normal Ready Normal ActiveDown	ActiveDown Info StateChange StateChange StateChange StateChange A, now ActiveT StateChange	3m37s 3m37s 3m37s 3m37s akeover 3m36s	timesten timesten timesten timesten timesten	Pod samplettc-0 Databa Pod samplettc-0 RepSta Pod samplettc-0 is Not TimesTenClassic was Pod samplettc-0 is Rea	nte E
Normal, no Normal Updatable Normal ACTIVE Normal Ready Normal ActiveDown Normal	ActiveDown Info StateChange StateChange StateChange StateChange A, now ActiveT StateChange	3m37s 3m37s 3m37s 3m37s akeover 3m36s	timesten timesten timesten timesten timesten	Pod samplettc-0 Databa Pod samplettc-0 RepSta Pod samplettc-0 is Not TimesTenClassic was Pod samplettc-0 is Rea	nte E
Normal, no Normal Updatable Normal ACTIVE Normal Ready Normal Normal Ready Normal	StateChange StateChange StateChange StateChange StateChange StateChange StateChange StateChange StateChange	3m37s 3m37s 3m37s 3m37s akeover 3m36s 3m36s 3m36s	timesten timesten timesten timesten timesten timesten timesten timesten	Pod samplettc-0 Databa Pod samplettc-0 RepSta Pod samplettc-0 is Not TimesTenClassic was Pod samplettc-0 is Rea Pod samplettc-0 is Act	nte E
Normal, no Normal Updatable Normal ACTIVE Normal Ready Normal Normal Ready Normal	StateChange StateChange StateChange StateChange StateChange A, now ActiveT StateChange StateChange StateChange	3m37s 3m37s 3m37s 3m37s akeover 3m36s 3m36s 3m36s ndbyDow 3m33s	timesten timesten timesten timesten timesten timesten timesten timesten	Pod samplettc-0 Databa Pod samplettc-0 RepSta Pod samplettc-0 is Not TimesTenClassic was Pod samplettc-0 is Rea Pod samplettc-0 is Act TimesTenClassic was Pod samplettc-1 Agent	ate ady cive
Normal, no Normal Updatable Normal ACTIVE Normal Ready Normal ActiveDown Normal Normal Ready Normal	StateChange StateChange StateChange StateChange A, now ActiveT StateChange StateChange StateChange StateChange	3m37s 3m37s 3m37s 3m37s akeover 3m36s 3m36s 3m36s ndbyDow	timesten timesten timesten timesten timesten timesten timesten timesten	Pod samplettc-0 Databa Pod samplettc-0 RepSta Pod samplettc-0 is Not TimesTenClassic was Pod samplettc-0 is Rea Pod samplettc-0 is Act TimesTenClassic was	ate ady cive
Normal, no Normal Updatable Normal ACTIVE Normal Ready Normal ActiveDown Normal Normal Ready Normal Ready Normal	StateChange StateChange StateChange StateChange Anow ActiveT StateChange StateChange StateChange StateChange StateChange StateChange	3m37s 3m37s 3m37s 3m37s akeover 3m36s 3m36s 3m36s 3m36s 3m33s 3m33s	timesten	Pod samplettc-0 Databa Pod samplettc-0 RepSta Pod samplettc-0 is Not TimesTenClassic was Pod samplettc-0 is Rea Pod samplettc-0 is Act TimesTenClassic was Pod samplettc-1 Agent Pod samplettc-1 Instan	ady cive
Normal, no Normal Updatable Normal ACTIVE Normal Ready Normal ActiveDown Normal Normal Ready Normal Ready Normal Rormal Ready Normal Rormal Normal	ActiveDown Info StateChange StateChange StateChange A, now ActiveT StateChange StateChange StateChange StateChange Info Info Info	3m37s 3m37s 3m37s 3m37s 3m37s akeover 3m36s 3m36s 3m36s 3m36s 3m33s 3m33s	timesten	Pod samplettc-0 Databa Pod samplettc-0 RepSta Pod samplettc-0 is Not TimesTenClassic was Pod samplettc-0 is Rea Pod samplettc-0 is Act TimesTenClassic was Pod samplettc-1 Agent Pod samplettc-1 Instar Pod samplettc-1 Daemon	ady cive
Normal, no Normal Updatable Normal ACTIVE Normal Ready Normal ActiveDown Normal Normal Ready Normal Ready Normal Ready Normal Ready Normal Normal Normal Normal Normal	StateChange Info Info Info Info	3m37s 3m37s 3m37s 3m37s 3m37s akeover 3m36s 3m36s 3m36s 3m33s 3m33s 3m33s	timesten	Pod samplettc-0 Databa Pod samplettc-0 RepSta Pod samplettc-0 is Not TimesTenClassic was Pod samplettc-0 is Rea Pod samplettc-0 is Act TimesTenClassic was Pod samplettc-1 Agent Pod samplettc-1 Instan Pod samplettc-1 Daemor Pod samplettc-1 Daemor	ady cive Up nce n Down
Normal, no Normal Updatable Normal ACTIVE Normal Ready Normal Normal Normal Ready Normal Ready Normal Ready Normal Ready Normal Rormal Normal Normal Normal Normal	ActiveDown Info StateChange StateChange StateChange A, now ActiveT StateChange StateChange StateChange StateChange Info Info Info	3m37s 3m37s 3m37s 3m37s 3m37s akeover 3m36s 3m36s 3m36s 3m36s 3m33s 3m33s	timesten	Pod samplettc-0 Databa Pod samplettc-0 RepSta Pod samplettc-0 is Not TimesTenClassic was Pod samplettc-0 is Rea Pod samplettc-0 is Act TimesTenClassic was Pod samplettc-1 Agent Pod samplettc-1 Instar Pod samplettc-1 Daemon	ady cive Up nce n Down
Normal, no Normal Updatable Normal ACTIVE Normal Ready Normal Normal Normal Ready Normal Ready Normal Ready Normal Rormal Rormal Normal Normal Normal Unloaded	StateChange StateChange StateChange StateChange StateChange A, now ActiveT StateChange StateChange StateChange StateChange StateChange Info Info Info Info Info Info Info	3m37s 3m37s 3m37s 3m37s 3m37s 3m37s akeover 3m36s 3m36s 3m36s 3m33s 3m33s 3m33s 3m33s	timesten	Pod samplettc-0 Databa Pod samplettc-0 is Not TimesTenClassic was Pod samplettc-0 is Rea Pod samplettc-0 is Act TimesTenClassic was Pod samplettc-1 Agent Pod samplettc-1 Instan Pod samplettc-1 Daemor	ady dy Live Up nce n Down n Up
Normal, no Normal Updatable Normal ACTIVE Normal Ready Normal ActiveDown Normal Ready Normal Ready Normal Ready Normal Ready Normal Normal Normal Normal Unloaded Normal	StateChange Info Info Info Info	3m37s 3m37s 3m37s 3m37s 3m37s akeover 3m36s 3m36s 3m36s 3m33s 3m33s 3m33s	timesten	Pod samplettc-0 Databa Pod samplettc-0 RepSta Pod samplettc-0 is Not TimesTenClassic was Pod samplettc-0 is Rea Pod samplettc-0 is Act TimesTenClassic was Pod samplettc-1 Agent Pod samplettc-1 Instan Pod samplettc-1 Daemor Pod samplettc-1 Daemor	ady dy Live Up nce n Down n Up
Normal, no Normal Updatable Normal ACTIVE Normal Ready Normal Normal Ready Normal Ready Normal Ready Normal Ready Normal Cormal Normal	Info StateChange StateChange StateChange StateChange A, now ActiveT StateChange StateChange StateChange StateChange StateChange Info Info Info Info Info Info Info Info	3m37s 3m37s 3m37s 3m37s 3m37s akeover 3m36s 3m36s 3m36s 3m33s 3m33s 3m33s 3m33s 3m33s	timesten	Pod samplettc-0 Databa Pod samplettc-0 is Not TimesTenClassic was Pod samplettc-0 is Rea Pod samplettc-0 is Act TimesTenClassic was Pod samplettc-1 Agent Pod samplettc-1 Instar Pod samplettc-1 Daemor Pod samplettc-1 Daemor Pod samplettc-1 Databa Pod samplettc-1 Databa	ady cive Up nce n Down n Up
Normal, no Normal Updatable Normal ACTIVE Normal Ready Normal Normal Ready Normal Ready Normal Ready Normal Ready Normal Unloaded Normal	Info StateChange StateChange StateChange StateChange A, now ActiveT StateChange StateChange StateChange StateChange StateChange Info Info Info Info Info Info Info Info	3m37s 3m37s 3m37s 3m37s 3m37s akeover 3m36s 3m36s 3m36s 3m33s 3m33s 3m33s 3m33s 3m33s 3m33s 3m33s	timesten	Pod samplettc-0 Databa Pod samplettc-0 is Not TimesTenClassic was Pod samplettc-0 is Rea Pod samplettc-0 is Act TimesTenClassic was Pod samplettc-1 Agent Pod samplettc-1 Instar Pod samplettc-1 Daemor Pod samplettc-1 Daemor Pod samplettc-1 Databa Pod samplettc-1 Databa Pod samplettc-1 Databa	ady cive Up nce n Down n Up
Normal, no Normal Updatable Normal ACTIVE Normal Ready Normal Normal Ready Normal Ready Normal Ready Normal Ready Normal Unloaded Normal	Info StateChange StateChange StateChange StateChange A, now ActiveT StateChange StateChange StateChange StateChange StateChange Info Info Info Info Info Info Info Info	3m37s 3m37s 3m37s 3m37s 3m37s akeover 3m36s 3m36s 3m36s 3m33s 3m33s 3m33s 3m33s 3m33s 3m33s 3m33s	timesten	Pod samplettc-0 Databa Pod samplettc-0 is Not TimesTenClassic was Pod samplettc-0 is Rea Pod samplettc-0 is Act TimesTenClassic was Pod samplettc-1 Agent Pod samplettc-1 Instar Pod samplettc-1 Daemor Pod samplettc-1 Daemor Pod samplettc-1 Databa Pod samplettc-1 Databa	ady cive Up nce n Down n Up ase

```
polling for RepDuplicate, timeout in 594 secs
                     3m22s timesten pollAsyncStatus: Async polling
         Info
for RepDuplicate, timeout in 591 secs
 DEBUG Info 3m19s timesten pollAsyncStatus: Async polling
for RepDuplicate, timeout in 588 secs
 Normal Info 3m15s timesten Pod samplettc-1 Database Loaded
                 3m15s timesten Pod samplettc-1 RepAgent Not
 Normal Info
Running
 Normal Info 3m15s timesten Pod samplettc-1 RepScheme Exists
 Normal StateChange 3m15s timesten Pod samplettc-1 RepState IDLE
 Normal Info 3m10s timesten Pod samplettc-1 RepAgent Running
 Normal StateChange 3m10s timesten TimesTenClassic was StandbyDown,
now StandbyStarting
         StateChange 3m9s timesten TimesTenClassic was
 Normal
StandbyStarting, now StandbyCatchup
 Normal StateChange 2m31s timesten Pod samplettc-1 RepState STANDBY
 Normal Upgrade
                     2m30s timesten Upgrade completed in 248 secs
         StateChange 2m30s timesten TimesTenClassic was
 Normal
StandbyCatchup, now Normal
```

6. Confirm the TimesTenClassic object is in the Normal state.

kubectl get ttc samplettc

Output.

NAME STATE ACTIVE AGE samplettc Normal samplettc-0 22h

The TimesTenClassic object is in the Normal state. The samplettc-0 is now the active.

7. Confirm the TimesTenClassic object is running the original image.

```
kubectl get ttc samplettc -o yaml | grep image
```

Output.

image: phx.ocir.io/youraccount/tt2211190image:1

imagePullPolicy: Always
imagePullSecret: sekret
imageUpdatePending: false

The TimesTenClassic object is running the new image.

8. Confirm the samplettc release is downgraded.

helm list

Output.

NAME NAMESPACE REVISION UPDATED STATUS

CHART	APP	VERSION		
samplettc	mynamespace	3	2023-1	0-24
21:31:06.8662558	24 +0000 UTC	deployed		
ttclassic-221119	0.1.0 22.1	.1.19.0		
samplettop	mynamespace	2	2023-1	0-24
16:15:21.8961077	06 +0000 UTC	deployed		
ttoperator-22112	00.1.0 22.1	.1.20.0		
ttcrd	mynamespace	2	2023-1	0-24
16:10:21.5308328	96 +0000 UTC	deployed		
ttcrd-2211200.1.	0 22.1	.1.20.0		

The ttclassic chart version is 2211190.1.0 corresponding to the 22.1.1.19.0 TimesTen release.

Congratulations! You successfully completed the rollback.

Roll Back a TimesTen Operator Upgrade

You can use Helm to roll back a TimesTen Operator upgrade.

Let's assume you upgraded the TimesTen Operator as discussed in Upgrade the TimesTen Operator. However, you now want to roll back the upgrade. Here's how to perform the rollback using Helm.

This example downgrades from TimesTen release 22.1.1.20.0 to 22.1.1.19.0. For more information about TimesTen releases, see Overview of release numbers in the Oracle TimesTen In-Memory Database Installation, Migration, and Upgrade Guide.

1. Review the current release of the ttoperator chart that is deployed in your namespace.

helm list

Output.

NAME	NAMESPACE	REVISIO	N	
UPDATED			STATUS	
CHART	APP VE	ERSION		
samplettc	mynamespace	3		2023-10-23
21:31:06.740512	2897 +0000 UTC o	deployed		
ttclassic-22111	190.1.0 22.1.1	1.19.0		
samplettop	mynamespace	2		2023-10-24
16:15:21.796835	595 +0000 UTC c	deployed		
ttoperator-2211	1200.1.0 22.1.1	1.20.0		
ttcrd	mynamespace	2		2023-10-24
16:00:21.530832	2896 +0000 UTC o	deployed		
ttcrd-2211200.1	1.0 22.1.1	L.20.0		

The samplettop release that is deployed is revision 2. The ttoperator chart version is 2211200.1.0 corresponding to the 22.1.1.20.0 TimesTen release.



2. Review the ttoperator chart's revision history.

helm history samplettop

Output.

REVISION	UPDATED				STATUS
CHART		API	P VERSION	DESCRIPT	TION
1	Mon Oct	23	23:04:40	2023	superseded
ttoperator-2211	190.1.0	22.	.1.1.19.0	Install	complete
2	Tue Oct	24	16:15:21	2023	deployed
ttoperator-2211	200.1.0	22.	.1.1.20.0	Upgrade	complete

Revision 2 of the samplettop ttoperator chart is currently deployed. The ttoperator chart version for revision 1 is 2211190.1.0 corresponding to TimesTen release 22.1.1.19.0.

3. Roll back to revision 1.

helm rollback samplettop 1

Output.

Rollback was a success! Happy Helming!

4. Review the revision history.

helm history samplettop

Output.

REVISION	UPDATED				STATUS
CHART		AP	P VERSION	DESCRIP:	TION
1	Mon Oct	23	23:04:40	2023	superseded
ttoperator-2211	190.1.0	22	.1.1.19.0	Install	complete
2	Tue Oct	24	16:15:21	2023	superseded
ttoperator-2211	200.1.0	22	.1.1.20.0	Upgrade	complete
3	Tue Oct	24	22:31:06	2023	deployed
ttoperator-2211	190.1.0	22	.1.1.19.0	Rollbacl	k to 1

Revision 3 of the samplettop release is now deployed in your namespace. The ttoperator chart version is 2211190.1.

5. Verify the new TimesTen Operator is running in your namespace.

kubectl get pods

Output.

NAME	READY	STATUS	RESTARTS	AGE
samplettc-0	3/3	Running	0	17h



```
samplettc-1 3/3 Running 0
17h
timesten-operator-65ddf9cfbb-cplhl 1/1 Running 0
3m26s
```

6. Verify the TimesTen Operator is running the original image.

```
kubectl get pod timesten-operator-65ddf9cfbb-cplhl -o yaml | grep image
```

Output.

```
image: phx.ocir.io/youraccount/tt2211190image:1
imagePullPolicy: Always
```

The TimesTen Operator is running the original image.

Congratulations! You successfully completed the rollback. The TimesTen Operator that is running in your namespace is using the original image.

Roll Back a TimesTen Custom Resource Definitions (CRDs) Upgrade

You can use Helm to roll back the TimesTen Custom Resource Definitions (CRDs) in your cluster.

Let's assume you upgraded the TimesTen CRDs in your cluster as discussed in Upgrade the TimesTen Custom Resource Definitions (CRDs). However, you now want to roll back the upgrade. Here's how to perform the rollback using Helm.

This example downgrades from TimesTen release 22.1.1.20.0 to 22.1.1.19.0. For more information about TimesTen releases, see Overview of release numbers in the *Oracle TimesTen In-Memory Database Installation, Migration, and Upgrade Guide*.

1. Review the current ttcrd release that is deployed in your namespace.

```
helm list
```

Output.

```
NAME NAMESPACE REVISION
UPDATED STATUS
CHART APP VERSION
...
ttcrd mynamespace 2 2023-10-24
16:00:21.530832896 +0000 UTC deployed
ttcrd-2211200.1.0 22.1.1.20.0
```

The ttcrd release that is deployed is revision 2. The ttcrd chart version is 2211200.1.0 corresponding to the 22.1.1.20.0 TimesTen release.

2. Roll back to the previous revision.

```
helm rollback ttcrd 1
```

Output.

Rollback was a success! Happy Helming!

3. Confirm the ttcrd release is at revision 3.

```
helm list
```

Output.

```
NAME NAMESPACE REVISION

UPDATED STATUS

CHART APP VERSION

...

ttcrd mynamespace 3 2023-10-24
23:31:21.530832896 +0000 UTC deployed ttcrd-2211190.1.0
22.1.1.19.0
```

Revision 3 of the ttcrd release is now deployed. The ttcrd chart version is 2211190.1.

Congratulations! You successfully completed the rollback.

About Uninstalling a Release

You can uninstall a release by using the helm uninstall command. This command deletes the Kubernetes objects created by the helm install command. Uninstalling a release results in TimesTen databases being deleted or being unmanaged or both.

Delete TimesTen Databases

To delete a TimesTenClassic object and the active standby pair of TimesTen Classic databases associated with this TimesTenClassic object, you uninstall the ttclassic release that your previously installed.

1. List the releases.

```
helm list
```

Output.

NAME	NAMESPACE	REVISION	I
UPDATED			STATUS
CHART	APP VER	RSION	
samplettop	mynamespace	3	2023-10-17
22:31:06.530832	896 +0000 UTC de	ployed	ttoperator-2211190.1.0
22.1.1.19.0			



```
      samplettc
      mynamespace
      3
      2023-10-17

      21:31:06.164158714 +0000 UTC deployed
      ttclassic-2211190.1.0
      22.1.1.19.0

      ttcrd
      mynamespace
      3
      2023-10-17

      23:31:06.530832896 +0000 UTC deployed
      ttcrd-2211190.1.0
      22.1.1.19.0
```

The samplette release is installed in your namespace. The chart is ttclassic.

2. Confirm the TimesTenClassic object is deployed in your namespace.

```
kubectl get ttc samplettc
```

Output.

```
NAME STATE ACTIVE AGE samplettc Normal samplettc-0 2d1h
```

3. Uninstall the samplettc release. This operation deletes the samplettc TimesTenClassic object, deletes the active standby pair of TimesTen Classic databases associated with the samplettc TimesTenClassic object, and deletes any other relevant Kubernetes objects. Since the Persistent Volume Claims (PVCs) are not automatically deleted, you must manually delete them. A later step shows you how to do this.

```
helm uninstall samplettc
```

Output.

```
release "samplettc" uninstalled
```

The samplettc release is uninstalled.

4. Confirm the TimesTenClassic object is deleted.

```
kubectl get ttc samplettc
```

Output.

```
Error from server (NotFound): timestenclassics.timesten.oracle.com
"samplettc" not found
```

5. Confirm the ConfigMap is deleted.

```
kubectl get configmap samplettc
```

Output.

```
Error from server (NotFound): configmaps "samplettc" not found
```

6. Delete the Persistent Volume Claims.

```
kubectl get pvc
```

Output.

```
NAME
                           STATUS
VOLUME
         CAPACITY ACCESS MODES
                                  STORAGECLASS
                                                 AGE
tt-persistent-samplettc-0 Bound
ocid1.volume.oc1.phx.abyhqljswsjqkcbdo2om3gvfinqs7bfjoaup22uurjji15q3o5kk6
5expxjq
        10Gi
                   RWO
                                   oci-bv
                                                 43m
tt-persistent-samplettc-1 Bound
ocid1.volume.oc1.phx.abyhqljt5ql4xiof6t6hbwaoaiol7w5zyobagexpoapxkoq3wcq2n
sftehvq
        10Gi
                  RWO
                                  oci-bv
```

Delete.

```
kubectl delete pvc tt-persistent-samplettc-0
kubectl delete pvc tt-persistent-samplettc-1
```

The samplettc TimesTenClassic object, the samplettc ConfigMap, the TimesTen databases associated with the samplettc TimesTenClassic object, and all other Kubernetes objects created by the helm install samplettc command are deleted. Since the Persistent Volume Claims on which the databases are stored are not automatically deleted, you deleted them manually.

Delete the TimesTen Operator

To stop running the TimesTen Operator in your namespace, you uninstall the ttoperator release that your previously installed.

1. List the releases.

```
helm list
```

Output.

NAME	NAMESPACE	REVISION	√.
UPDATED			STATUS
CHART	APP 7	VERSION	
samplettop	mynamespace	3	2023-10-24
22:31:06.530832	2896 +0000 UTC	deployed	ttoperator-2211190.1.0
22.1.1.19.0			
ttcrd	mynamespace	3	2023-10-24
23:31:06.530832	2896 +0000 UTC	deployed	ttcrd-2211190.1.0
22.1.1.19.0			

The samplettop release is installed in your namespace. The chart is ttoperator.

2. Uninstall the samplettop release. This operation stops the running of the TimesTen Operator and deletes the TimesTen Operator Deployment.

helm uninstall samplettop

Output.

release "samplettop" uninstalled

The samplettop release is uninstalled.

3. Confirm the TimesTen Operator Pod is deleted.

kubectl get pod timesten-operator-65ddf9cfbb-cplhl

Output.

Error from server (NotFound): pods "timesten-operator-65ddf9cfbb-cplh1" not found

4. Confirm the TimesTen Operator Deployment is deleted.

kubectl get deployment timesten-operator

Output.

Error from server (NotFound): deployments.apps "timesten-operator" not found

The TimesTen Operator is no longer running in your namespace. The TimesTen Operator Deployment that is used to run the TimesTen Operator is deleted.

Delete the TimesTen Custom Resource Definitions (CRDs)

To delete the TimesTen Custom Resource Definitions (CRDs) from your cluster, you uninstall the ttcrd release that you previously installed.



Use caution when deleting the TimesTen CRDs. This action may cause the immediate deletion of any TimesTen databases that are deployed.

1. Confirm the ttcrd release.

helm list



Output.

NAME NAMESPACE REVISION UPDATED STATUS

CHART APP VERSION

ttcrd mynamespace 3 2023-10-24 23:31:06.530832896 +0000 UTC deployed ttcrd-2211190.1.0 22.1.1.19.0

The ttcrd release is installed. The chart is ttcrd.

2. Uninstall the ttcrd release. This operation deletes the TimesTen CRDs.

helm uninstall ttcrd

Output.

release "ttcrd" uninstalled

You successfully deleted the TimesTen CRDs.



8

Use TimesTen Databases

This chapter explains how to use direct mode applications and Client/Server drivers to access and use TimesTen Classic databases in an active standby pair configuration and a TimesTen Scaleout database in the grid.

Topics:

- About Using Direct Mode Applications
- About Using Client/Server Drivers

About Using Direct Mode Applications

You can run direct mode applications inside of the Pods in your TimesTenClassic and TimesTenScaleout deployments.

When configured in your TimesTenClassic deployment, each Pod in your active standby pair runs two or more containers. When configured in your TimesTenScaleout deployment, each Pod containing a data instance runs two or more containers. One container in each Pod runs TimesTen and the TimesTen agent and the other container(s) run whatever applications you choose. The applications that are running in your containers can use TimesTen in direct mode. For information on direct mode applications, see Managing TimesTen Databases in the *Oracle TimesTen In-Memory Database Operations Guide*.

TimesTen Pods are created with the Kubernetes *shareProcessNamespace* option. This option allows direct mode applications running in other containers within the same Pod to function properly.



The standard security issues that surround direct mode apply in this environment as in a non-Kubernetes environment. Segregating your applications into separate containers from TimesTen is intended for ease of management and ease of upgrade. It is not intended as a security barrier and provides no additional security.

Use the <code>.spec.template.spec.containers</code> attribute of your TimesTenClassic object or the <code>.spec.dataTemplate.spec.containers</code> of your TimesTenScaleout object to cause one or more containers to be created within each of the TimesTen Pods that runs the <code>tt</code> container. Such containers are created in addition to the <code>tt</code> container that runs TimesTen.

This example illustrates how to include the <code>.spec.template.spec.containers</code> attribute in your TimesTenClassic object definition. For a TimesTenScaleout object, replace <code>template</code> with one or more <code>dataTemplates</code>.

apiVersion: timesten.oracle.com/v1
kind: TimesTenClassic
metadata:



```
name: directmode
spec:
  ttspec:
   storageClassName: oci-bv
    storageSize: 250Gi
    image: container-registry.oracle.com/timesten/timesten:22.1.1.19.0
    imagePullSecret: sekret
    dbConfigMap:
    - directmode
  template:
    spec:
      containers:
      - name: yourapp
        image: phx.ocir.io/youraccount/yourapplication:2
        command: ["/bin/yourapp"]
      - name: anotherapp
        image: phx.ocir.io/youraccount/anotherapplication:2
        command: ["/bin/anotherapp"]
```

You can specify any other Kubernetes configuration for these containers.

The Operator automatically adds appropriate mounts to the containers. This gives your containers the ability to access TimesTen.

To use TimesTen in direct mode, your application containers must know how TimesTen is configured in the tt container. You must configure your application containers similarly.

In particular:

- You must know the name of the TimesTen users group. If you are using a
 container image located at container-registry.oracle.com/timesten, the name
 of the TimesTen users group is timesten. If you built the TimesTen container
 image, and changed the timesten default, ensure you use the name you used
 when you built the container image. See Option 2b: Build with Customizations and
 Dockerfile ARGs.
- You must know the name of the Linux operating system user that runs TimesTen.
 The default is timesten. As was mentioned in the previous bullet, if you changed
 this default, ensure you use the name you used when you built the container
 image.
- You must configure your application containers to run your applications as a member of the TimesTen users group. Only members of this group can run TimesTen in direct mode.
- You can run your direct mode applications as a user with the same UID as that of the TimesTen user that runs TimesTen (3429 is the default). However, this grants the application instance administrator permissions on the TimesTen instance. Alternatively, you can create a group with the same GID as that of the TimesTen users group of and then create a user whose primary or secondary group is that group, but with a UID that is not the UID of the TimesTen user that is running TimesTen. In this case, you can run your application as this user and also use TimesTen in direct mode. You can then grant this user privileges up to and including the ADMIN privilege. For more information on primary and secondary groups, see Creating an Installation on Linux/UNIX in the Oracle TimesTen In-Memory Database Installation, Migration, and Upgrade Guide. For information on TimesTen privileges, see System Privileges and Object Privileges in the Oracle TimesTen In-Memory Database SQL Reference.



- The direct mode application must use the TimesTen instance that is configured at /tt/home/timesten/instances/instance1. The scripts to configure the TimesTen environment variables are located at /tt/home/timesten/instances/instance1/bin/ttenv.*.
- Do not modify any file that is located in the TimesTen instance. In addition, ensure you do not create any new files in the \$TIMESTEN HOME directory tree of the instance.
- Do not add entries to the /tt/home/timesten/instances/instance1/conf/sys.odbc.ini file. These files can be overwritten by the Operator. However, you can store your own DSN entries in the \$HOME/.odbc.ini file located in your application container.
- Do not create additional TimesTen databases.

Kubernetes, not the Operator, is responsible for monitoring and managing the life cycle of the direct mode containers. In particular:

- Applications are started by Kubernetes regardless of the state of TimesTen (located in its own container). Kubernetes manages the life cycle of containers individually. It does not sequence. Your application must know how to wait for TimesTen to become available.
- For a TimesTenClassic object, a direct mode application runs in the Pod containing the active TimesTen database and in the Pod containing the standby TimesTen database. The application may need to use the ttRepStateGet built-in procedure to determine whether it is running on the active or on the standby and perhaps quiesce itself on the standby. For more information on the ttRepStateGet built-in procedure, see ttRepStateGet in the Oracle TimesTen In-Memory Database Reference.
- Kubernetes may start the application before the TimesTen database exists or before it is loaded into memory and ready for use. It is the responsibility of the direct mode application to verify the state of the TimesTen database in its Pod and to use it appropriately.
- If your application exits, the container terminates, and Kubernetes spawns another container. This does not impact TimesTen that is running in the tt container.

About Using Client/Server Drivers

Applications that are running in other Pods in your Kubernetes cluster can use your TimesTen database by using the standard TimesTen Client/Server drivers. You must configure your application containers with a TimesTen client instance. That instance must contain a configured \$TIMESTEN_HOME/conf/sys.odbc.ini file, or your application must use an appropriate Client/Server connection string.

In TimesTen Classic, if you chose to configure a <code>sys.odbc.ini</code> file, the contents of <code>sys.odbc.ini</code> contains a client DSN definition that references the Pods that are running your TimesTen databases. In TimesTen Scaleout, you can export a <code>sys.odbc.ini</code> file for use by client/server clients outside of the <code>grid</code>. Use the <code>ttGridAdmin</code> utility with the <code>gridClientExport</code> or <code>gridClientExportAll</code> for this purpose. See <code>ttGridAdmin</code> in the <code>Oracle TimesTen In-Memory Database Reference</code>.

This example creates the sample DSN and references the sample TimesTenClassic object in the mynamespace namespace.

% vi \$TIMESTEN HOME/conf/sys.odbc.ini

[sample]



```
TTC_SERVER_DSN=sample
TTC_SERVER1=sample-0.sample.mynamespace.svc.cluster.local
TTC_SERVER2=sample-1.sample.mynamespace.svc.cluster.local
```

Applications connect to the TimesTen database using this DSN. In the TimesTen Classic active standby pair configuration, TimesTen automatically routes application connections to the active database. (sample-0 and sample-1 are used for example purposes.)

Client/Server applications must connect to the database using a defined username and password. The Operator can create such a user with ADMIN privileges. You can then connect to the database, as that user, to create other users and grant these users the CREATE SESSION privilege. See Overview of Configuration Metadata and Kubernetes Facilities.

In this example, use a connection string to connect to the sample database as the sampleuser user. (If you use a connection string that requires all the required connection attributes, you do not need to define them in the <code>sys.odbc.ini</code> file.) The sampleuser user was created by the Operator and already exists in the <code>sample</code> database. After connecting, you can verify that the <code>sampleuser.emp</code> table exists. (The Operator also previously created this table. See <code>schema.sql</code> for information on how the Operator created this table.)

```
% ttIsqlCS -connstr "TTC SERVER1=sample-0.sample.mynamespace.svc.cluster.local;
TTC SERVER2=sample-1.sample.mynamespace.svc.cluster.local;
TTC_SERVER_DSN=sample;UID=sampleuser;PWD=samplepw";
Copyright (c) 1996, 2023, Oracle and/or its affiliates. All rights
reserved.
Type ? or "help" for help, type "exit" to quit ttIsql.
connect "TTC SERVER1=sample-0.sample.mynamespace.svc.cluster.local;
TTC SERVER DSN=sample; uid=sampleuser; pwd=*******;
Connection successful:
DSN=;TTC SERVER=sample-0.sample.mynamespace.svc.cluster.local;
TTC SERVER DSN=sample; UID=sampleuser; DATASTORE=/tt/home/timesten/datastore/
sample;
DATABASECHARACTERSET=AL32UTF8; CONNECTIONCHARACTERSET=AL32UTF8; PERMSIZE=200;
DDLREPLICATIONLEVEL=3;
(Default setting AutoCommit=1)
Command> tables;
 SAMPLEUSER.EMP
1 table found.
```



9

Manage and Monitor Active Standby Pairs

This chapter discusses how to monitor the health of each Pod in your active standby pair as well as the health of the active standby pairs themselves. It details the BothDown and the ManualInterventionRequired states with an emphasis of how the Operator behaves in each of these states. The chapter discusses how to suspend the management of your TimesTenClassic object by the Operator. It concludes with various manual operations you can perform on your TimesTen databases.

Topics:

- · About Monitoring the Health of Each Pod in an Active Standby Pair
- About Monitoring the Health of an Active Standby Pair of Databases
- About the BothDown State
- About the ManualInterventionRequired State
- · About Bringing Up One Database
- Suspend Management of a TimesTenClassic Object
- Locate the Operator
- Manage the TimesTen Databases

About Monitoring the Health of Each Pod in an Active Standby Pair

The Operator keeps track of the individual health and state of each Pod in the active standby pair. How often the Operator checks the health is defined by the value of the pollingInterval. See "TimesTenClassicSpecSpec" for information on pollingInterval.

Each Pod is assigned a high level state based on the state of various components of Kubernetes and the state of TimesTen. These states are:

- CatchingUp
- Down
- Healthy
- HealthyActive
- HealthyStandby
- OtherDown
- Terminal
- Unknown
- UpgradeFailed



CatchingUp

The standby has completed the process of duplicating the database from the active. The newly created standby is catching up to any transactions that ran on the active while the duplicate operation was running.

Down

Either the Pod or the TimesTen components within the Pod (or both) are not functioning properly, given this Pod's role in the active standby pair.

Healthy

The Pod and the TimesTen components within the Pod are in a healthy state, given this Pod's role in the active standby pair.

HealthyActive

When a TimesTenClassic object is in the Reexamine state, the Operator examines the state of both TimesTen instances. The Operator does not know which instance (if any) contains a properly configured active database (or a properly configured standby database). The Operator must examine both instances to see. If a healthy instance is found and that instance contains a properly configured active database, the state of the Pod is reported as HealthyActive.

HealthyStandby

When a TimesTenClassic object is in the Reexamine state, the Operator examines the state of both TimesTen instances. The Operator does not know which instance (if any) contains a properly configured standby database (or a properly configured active database). The Operator must examine both instances to see. If a healthy instance is found and that instance contains a properly configured standby database, the state of the Pod is reported as HealthyStandby.

OtherDown

The Pod and the TimesTen components within the Pod are in a healthy state, but TimesTen in this Pod believes that TimesTen in the other Pod has failed. In particular, the <code>OtherDown</code> state indicates that this Pod contains an active database, and the database's peer has reached the <code>failThreshold</code>. The database in this Pod is no longer keeping transaction logs for its peer, as the peer is too far behind. Recovering the peer requires re-duplicating the active database (which the Operator will perform automatically).

Terminal

TimesTen in the Pod cannot be repaired by the Operator.



Unknown

The state of this Pod is unknown. Either the Pod is unreachable or the TimesTen agent contained within the Pod has failed.

UpgradeFailed

An automated upgrade was attempted on TimesTen in this Pod and the upgrade failed. See About Upgrading TimesTen Classic.

About Monitoring the Health of an Active Standby Pair of Databases

The Operator monitors and manages the health of each of your active standby pairs. The Operator assigns high level states to the TimesTenClassic object, which you can monitor and review. For example, you can use the kubectl get command to return the high level state of your TimesTenClassic object. Specifically, in this example, the value returned for the STATE field is Normal, indicating that the active and the standby databases are up and running, and working as they should.

```
% kubectl get ttc sample
NAME STATE ACTIVE AGE
sample Normal sample-0 15h
```

The states:

- ActiveDown
- ActiveTakeover
- BothDown
- ConfiguringActive
- Failed
- Initializing
- ManualInterventionRequired
- Normal
- Reexamine
- StandbyCatchup
- StandbyDown
- StandbyStarting
- WaitingForActive

ActiveDown

If the Operator detects that TimesTen in the Pod containing the active database has failed, then the TimesTenClassic object immediately enters the ActiveDown state.



The unreachableTimeout timeout value controls how long the state of the Pod containing the active database can be Unknown before the TimesTenClassic object's state becomes ActiveDown.

When the TimesTenClassic object's state becomes ActiveDown, the standby database immediately becomes the active, and the state of the TimesTenClassic object becomes StandbyDown.

ActiveTakeover

When the TimesTenClassic object is in the Normal state, and the standby database goes down, the state briefly changes to ActiveTakeover.

When AWT cache groups are used, the standby is normally responsible for pushing updates from TimesTen to Oracle Database. However, if the standby fails, the active database takes over this responsibility. This occurs during the ActiveTakeover state.

BothDown

Neither the active nor the standby database is functioning properly. The Operator attempts to bring up the pair of databases.

If both Pods in the active standby pair fail, the Operator uses the information in TimesTenClassicStatus to minimize data loss. See "About the BothDown State" for details.

ConfiguringActive

When the TimesTenClassic object is in the <code>WaitingForActive</code> state, and when the database that should be the active database comes up, the TimesTenClassic object enters the <code>ConfiguringActive</code> state. The Operator then configures this database to be the active. Once the database is configured as the active, the TimesTenClassic object enters the <code>StandbyDown</code> state. See "About the BothDown State" for details.

Failed

If a problem occurs while Initializing a TimesTenClassic object, the object transitions to the Failed state. Once in this state, the Operator does not attempt to repair the object. You must delete it. Use the kubectl describe command to examine the Operator logs to determine the cause of the problem and then recreate the object.

Initializing

This state is reported while the two Pods are starting up for the first time. In your active standby pair configuration, the Pod whose name ends with -0 is initially configured as the active database, and the Pod whose name ends with -1 is initially configured as the standby database. Specifically, if you specified the name for TimesTenClassic as sample, the sample-0 Pod is configured as the active database, and the sample-1 Pod is configured as the standby database. Once the active/standby pair is completely deployed, the TimesTenClassic object transitions to the Normal state.



ManualInterventionRequired

When a TimesTenClassic object enters the ManualInterventionRequired state, the Operator takes no further action for the object. It does not query the TimesTen agents associated with the object to determine the state of TimesTen and it does not command TimesTen to do anything. See "About the ManualInterventionRequired State" and "About Bringing Up One Database" for details.

Normal

Both databases are up and running, and operating as they should.

Reexamine

When the TimesTenClassic object is in the ManualInterventionRequired state, you can specify the <code>.spec.ttspec.reexamine</code> datum to cause the Operator to take over the management of the object again. The Operator moves the object to the <code>Reexamine</code> state. The Operator then examines the state of TimesTen. If you correctly repaired TimesTen, the TimesTenClassic object may then enter the <code>Normal</code> or the <code>StandbyDown</code> state, depending on the nature of your repair. If you did not correctly repair TimesTen, the TimesTenClassic object re-enters the <code>ManualInterventionRequired</code> state. See "About the ManualInterventionRequired State" for details.

StandbyCatchup

This state is entered after the <code>StandbyStarting</code> state. During the <code>StandbyStarting</code> state, the standby copies the active database to the standby Pod. When the duplicate process is complete, the state changes from <code>StandbyStarting</code> to <code>StandbyCatchup</code>. See "StandbyStarting" for more information on the <code>StandbyStarting</code> state. In the <code>StandbyCatchup</code> state, the duplicate process has completed. Transactions that ran during this duplicate process must now be copied over to the standby. Thus the <code>StandbyCatchup</code> state is the state when the newly created standby catches up to any transactions that ran on the active while the duplicate operation was running. Applications can continue to use the active without restriction.

StandbyDown

The active database is functioning properly, but the standby database is not. The Operator automatically attempts to restart and reconfigure the standby database. Applications can continue to use the active database without restriction.

StandbyStarting

The standby is duplicating the database from the active. The <code>StandbyStarting</code> state is complete when the duplicate operation completes. The <code>StandbyCatchup</code> state is then entered. See "StandbyCatchup" for more information on the <code>StandbyCatchup</code> state. Applications can continue to use the active without restriction.



WaitingForActive

When the TimesTenClassic object is in the BothDown state, if the Operator can determine which database contains the most up-to-date data, the TimesTenClassic object enters the WaitingForActive state. The object remains in this state until the Pod that contains the database is running, and the TimesTen agent within the tt container (within that Pod) is responding to the Operator. See "About the BothDown State" for details.

About the BothDown State

The Operator provisions, monitors, and manages active standby pairs of TimesTen databases. It detects and reacts to the failure of the active or the standby database. For example, when one database in the active standby pair is down, the Operator does the following:

- If the active database fails, the Operator promotes the standby to be the active.
- If the standby database fails, the Operator keeps the active running and repairs the standby.

However, if both databases fail at the same time, it is essential that the databases are brought back up appropriately. TimesTen replication does not atomically commit transactions in both database simultaneously. Transactions are committed in one database and then later are committed in the other database. (The database on which transactions are committed first is considered the database that is *ahead*.) Depending on how replication is configured, transactions on the active database may be ahead of the standby or the standby may be ahead of the active. To avoid data loss, the database that is ahead must become the active database after the failure is corrected.

In most cases, the Operator can determine which database was ahead at the time of the failure. However, there are cases where the Operator cannot determine which database was ahead. In particular, the Operator cannot determine which database is ahead if all of the following conditions occur:

- Both databases failed during the polling interval. Specifically, the Operator
 examined both databases and the TimesTen Pods were in the Healthy state. The
 Operator waited pollingInterval seconds, and when the Operator examined the
 databases again (after this pollingInterval), both databases were down and
- RETURN TWOSAFE replication was configured and
- DISABLE RETURN **or** LOCAL COMMIT ACTION COMMIT **(or both) were configured.**

See TimesTenClassicSpecSpec for more information on the .spec.ttspec.pollingInterval datum and on the RETURN TWOSAFE and DISABLE RETURN replication configurations options. Also, see CREATE ACTIVE STANDBY PAIR in the Oracle TimesTen In-Memory Database SQL Reference and Defining an Active Standby Pair Replication Scheme in the Oracle TimesTen In-Memory Database Replication Guide for information on defining an active standby pair replication scheme.

This combination of events indicates that some transactions may have committed on the standby and not on the active and/or some transactions may have committed on the active and not on the standby. The Operator takes no action in this case.



When both databases fail, the TimesTenClassic object enters the BothDown state. See BothDown for more information on the BothDown state. The Operator must then determine the appropriate action to take. The Operator first examines the value of the .spec.bothDownBehavior datum to determine what to do. See TimesTenClassicSpecSpec.

If .spec.ttspec.bothDownBehavior is set to Manual, the TimesTenClassic object immediately enters the ManualInterventionRequired state. The Operator takes no further action even if either TimesTen container subsequently becomes available. See About the ManualInterventionRequired State for information on the ManualInterventionRequired state.

If .spec.ttspec.bothDownBehavior is set to Best (the default setting), the Operator attempts to determine which database was ahead at the time of failure.

- If the Operator cannot determine which database is ahead, the TimesTenClassic object immediately enters the ManualInterventionRequired state. See About the ManualInterventionRequired State.
- If the Operator can determine which database is ahead:
 - The TimesTenClassic object enters the WaitingForActive state. The object remains in this state until the Pod containing that database is running and the TimesTen agent located in the tt container within that Pod is responding to the Operator. At this point, the TimesTenClassic object enters the ConfiguringActive state.
 - While the TimesTenClassic object is in the ConfiguringActive state, TimesTen in this Pod is started, the database is loaded and is configured for use as the new active database. If there are any problems with these steps, the TimesTenClassic object enters the ManualInterventionRequired state. If the database is successfully loaded and successfully configured as the new active, the TimesTenClassic object enters the StandbyDown state. See About Monitoring the Health of an Active Standby Pair of Databases for information on the states of your TimesTenClassic object.
 - You can specify the maximum amount of time (expressed in seconds) that the TimesTenClassic object remains in the WaitingForActive state by specifying a value for the spec.ttspec.waitingForActiveTimeout datum. After this period of time, if the object is still in the WaitingForActive state, the object automatically transitions to the ManualInterventionRequired state. The default is 0, which indicates that there is no timeout, and the object will remain in this state indefinitely. See TimesTenClassicSpecSpec for more information on the spec.ttspec.waitingForActiveTimeout datum.
 - The time to recover the database varies by the size of the database. You should consider the size of your database when deciding the value for spec.ttspec.waitingForActiveTimeout.
 - If the database that is ahead cannot be loaded, the TimesTenClassic object enters the ManualInterventionRequired state. See About the ManualInterventionRequired State.

About the ManualInterventionRequired State

When a TimesTenClassic object enters the ManualInterventionRequired state, the Operator takes no further action for this object. It does not query the TimesTen agents associated with the object to determine the state of TimesTen and does not command TimesTen to do anything. It is important for you to address why the TimesTenClassic object is in this state.



If your TimesTenClassic object is in the ManualInterventionRequired state and it is not the result of it first being in the BothDown state, perform the operations necessary to manually repair one of the databases. Then, perform the steps to bring up this database. These steps are covered in About Bringing Up One Database later in this chapter.

If, however, the TimesTenClassic object is in the ManualInterventionRequired state as a result of it first being in the BothDown state:

- It may be unclear which database, if either, is suitable to be the new active. There
 may be transactions that have committed on the active database and not on the
 standby database, and simultaneously there may be transactions that have
 committed on the standby database and not on the active database.
- You need to manually examine both databases and may need to reconcile the data before you can choose which database should be the new active.
- If you can reconcile the data, and can manually fix one of the databases, then you
 can perform the steps to bring up one database. These steps are covered in About
 Bringing Up One Database later in this chapter. If you cannot reconcile the data,
 contact Oracle Support for further assistance.

In order for you to direct the Operator to move the TimesTenClassic object out of the ManualInterventionRequired state, you must either:

- Bring up exactly one database: The Operator treats this database as the active database. All of these conditions must be met:
 - The TimesTen agent in the container is running.
 - The TimesTen the instance in the container is running.
 - The TimesTen database is loaded.
 - There is no replication scheme in the database.
 - The replication agent is not running.
 - The replication state is IDLE.

If these conditions are met, the Operator moves the TimesTenClassic object to the StandbyDown state. If any of these conditions are not met, the TimesTenClassic object remains in the ManualInterventionRequired state. Note that when no replication scheme exists in the database, the Operator will still create the appropriate replication scheme based on how it is defined in the TimesTenClassic object definition. See About Bringing Up One Database for an example of how you can direct the Operator to take action once one database is up and running.

- Bring up both databases: In this case, you must configure the active standby pair. Specifically, each database must meet all of the following conditions:
 - The TimesTen agent in the container is running.
 - The TimesTen instance in the container is running.
 - The database is loaded.
 - The replication scheme is defined in both databases.
 - The replication agents are started and are running.
 - One database must be in the ACTIVE state and the other database must be in the STANDBY state.



If these conditions are met, the Operator moves the TimesTenClassic object to the Normal state. If any of these conditions are not met, the TimesTenClassic object remains in the ManualInterventionRequired state.

If you cannot bring up either database, the TimesTenClassic object remains in the ManualInterventionRequired state.

You direct the Operator to examine the databases by specifying the <code>.spec.ttspec.reexamine</code> datum. Every <code>.spec.ttspec.pollingInterval</code>, the Operator examines the value of <code>.spec.ttspec.reexamine</code>. If the value has changed since the last iteration for this TimesTenClassic object, the Operator examines the state of the TimesTen containers for this object. See <code>TimesTenClassicSpecSpec</code> for more information on the <code>.spec.ttspec.pollingInterval</code> and the <code>.spec.ttspec.reexamine</code> datum.

The examination of the databases is performed exactly one time after you change the <code>.spec.ttspec.reexamine</code> value. If the required conditions were not met, you may again attempt to meet them. You must then modify the <code>.spec.ttspec.reexamine</code> value again to cause the Operator to reexamine the databases.

Note that whenever a TimesTenClassic object changes state, a Kubernetes Event is created. You can monitor these events with the kubectl describe command to be informed of such state transitions.

About Bringing Up One Database

This section assumes you have manually repaired or have manually performed maintenance on one of the databases associated with the TimesTenClassic object. The TimesTenClassic object is currently in the ManualInterventionRequired state. You now want to direct the Operator to treat the repaired database as the active, to perform the necessary steps to duplicate this database to the standby, and to bring up both databases, such that both are running and operating successfully.

Recall that all of these conditions must be met for the database:

- TimesTen agent in the container is running.
- TimesTen daemon (the instance) in the container is running.
- TimesTen database is loaded.
- There is no replication scheme in the database.
- The replication agent is not running.
- The replication state is IDLE.

These sections show you how to verify the conditions are met for the database and how to set the reexamine value:

- Verify Conditions Are Met for the Database
- Set the reexamine Value

Verify Conditions Are Met for the Database

Perform these steps to ensure the conditions are met for the database (the database to be the active). In this example, sample-1 will be the new active.



Note: These steps require you to use TimesTen utilities and TimesTen built-in procedures. See Utilities and Built-In Procedures in the *Oracle TimesTen In-Memory Database Reference* for details.

1. Confirm the TimesTenClassic object (sample, in this example) is in the ManualInterventionRequired state (represented in **bold**).

```
% kubectl get ttc sample
NAME STATE ACTIVE AGE
sample ManualInterventionRequired sample-0 12h
```

2. Use the kubectl exec -it command to invoke the shell within the sample-1 Pod that contains the TimesTen database. (This database will be the new active.)

The remaining procedures take place within this shell.

```
% kubectl exec -it sample-1 -c tt -- /bin/bash
```

3. Use the ttDaemonAdmin utility to start TimesTen daemon (if not already started). Then use the ttAdmin utility to load the TimesTen database into memory (if not already loaded).

```
% ttDaemonAdmin -start
TimesTen Daemon (PID: 5948, port: 6624) startup OK.
% ttAdmin -ramLoad sample
RAM Residence Policy : manual
Manually Loaded In RAM : True
Replication Agent Policy : manual
Replication Manually Started : False
Cache Agent Policy : manual
Cache Agent Manually Started : False
Database State : Open
```

4. Use the ttIsql utility to connect to the sample database. Then, call the ttRepStop built-in procedure to stop the replication agent.

```
% ttIsql sample
Copyright (c) 1996, 2023, Oracle and/or its affiliates. All rights reserved.
Type ? or "help" for help, type "exit" to quit ttIsql.

connect "DSN=sample";
Connection successful: DSN=sample;UID=timesten;DataStore=/tt/home/timesten/datastore/sample;
DatabaseCharacterSet=AL32UTF8;ConnectionCharacterSet=AL32UTF8;AutoCreate=0;PermSize=200;DDLReplicationLevel=3;ForceDisconnectEnabled=1;
(Default setting AutoCommit=1)
Command> call ttRepStop;
```

5. From within ttlsql, use the SQL DROP ACTIVE STANDBY PAIR statement to drop the active standby pair replication scheme. Then use the ttlsql repschemes command to verify there are no replication schemes in the database. Exit from ttlsql.

```
Command> DROP ACTIVE STANDBY PAIR;
Command> repschemes;
```

0 replication schemes found.

6. Use the ttStatus utility to verify the TimesTen daemon is running and the replication agent is not running.

```
% ttStatus
 TimesTen status report as of Sat Apr 24 02:14:15 2023
 Daemon pid 5948 port 6624 instance instance1
 TimesTen server pid 5955 started on port 6625
 Data store /tt/home/timesten/datastore/sample
 Daemon pid 5948 port 6624 instance instance1
 TimesTen server pid 5955 started on port 6625
 There are 15 connections to the data store
 Shared Memory KEY 0x0a100c60 ID 196609
 PL/SQL Memory Key 0x0b100c60 ID 229378 Address 0x5000000000

        Type
        PID
        Context
        Connection Name

        Process
        10418
        0x000000000218a6e0
        sample

        Process
        8338
        0x000000001cbb6e0
        sample

        Subdaemon
        5953
        0x0000000015075f0
        Manager

        Subdaemon
        5953
        0x0000000015072f0
        Checkpoint

        Subdaemon
        5953
        0x000007f132c0008c0
        Flusher

        Subdaemon
        5953
        0x00007f132c0008c0
        Flusher

        Subdaemon
        5953
        0x00007f133c0008c0
        Monitor

        Subdaemon
        5953
        0x00007f13340008c0
        Monitor

        Subdaemon
        5953
        0x00007f13380008c0
        Aging

        Subdaemon
        5953
        0x00007f13380008c0
        AsyncMV

        Subdaemon
        5953
        0x00007f133c0008c0
        Deadlock Detector

        Subdaemon
        5953
        0x00007f133c0008c0
        Garbage Collector

        Subdaemon
        5953
        0x00007f135c0008c0
        Garbage Collector

        Subdaemon
        5953
        0x00007f13600e8e20
        XactId Rollback

 Type PID Context
                                                                                 Connection Name
                                                                                                                                                               ConnID
                                                                                                                                                                             1
                                                                                                                                                                    2047
                                                                                                                                                                    2046
                                                                                                                                                                    2041
                                                                                                                                                                    2045
                                                                                                                                                                    2040
                                                                                                                                                                    2044
                                                                                                                                                                    2037
                                                                                                                                                                    2042
                                                                                                                                                                    2039
                                                                                                                                                                   2043
                                                                                                                                                                    2038
                                                                                                                                                                   2035
                                                                                                                                                                    2036
 Open for user connections
 RAM residence policy: Manual
 Data store is manually loaded into RAM
 Replication policy : Manual
 Cache Agent policy : Manual
 PL/SOL enabled.
 ______
 Accessible by group timesten
 End of report
```

You have successfully verified the conditions for the database. The database is up and running. The Operator will treat this database as the active. You are now ready to set the value for the <code>.spec.ttspec.reexamine</code> datum.

Set the reexamine Value

This example shows you how to set the reexamine value in the TimesTenClassic object definition (sample, in this example). The example also illustrates the action the Operator takes after the reexamine value has been changed.

1. Set the reexamine value. The value must be different than the current value for the TimesTenClassic object. When the Operator examines this value and notices it has changed since the last iteration, it will take appropriate action.

Use the kubectl edit command to edit the TimesTenClassic object.

- If there is a line for reexamine in the file, then modify its value. It must be different than the current value.
- If there is no line for reexamine in the file, then add a line and specify a value.

In this example, there is no reexamine line. This example adds the reexamine line and sets the value for reexamine to April 22 reexamine 1 (represented in **bold**).

Note: Not all output is shown.

```
% kubectl edit timestenclassic sample
# Please edit the object below. Lines beginning with a '#' will be ignored,
# and an empty file will abort the edit. If an error occurs while saving
this
# file will be reopened with the relevant failures.
apiVersion: timesten.oracle.com/v1
kind: TimesTenClassic
metadata:
 name: sample
 namespace: mynamespace
repCreateStatement: |
 create active standby pair
    "{{tt-name}}" on "{{tt-node-0}}",
    "{{tt-name}}" on "{{tt-node-1}}"
 RETURN TWOSAFE
 store "{{tt-name}}" on "{{tt-node-0}}"
   PORT {{tt-rep-port}} FAILTHRESHOLD 0 TIMEOUT 999
 store "{{tt-name}}" on "{{tt-node-1}}"
   PORT {{tt-rep-port}} FAILTHRESHOLD 0 TIMEOUT 999
spec:
 ttspec:
   bothDownBehavior: Best
   dbConfigMap:
    - sample
   image: container-registry.oracle.com/timesten/timesten:22.1.1.19.0
   imagePullSecret: sekret
   storageClassName: oci-bv
   storageSize: 250Gi
   reexamine: April22reexamine1
timestenclassic.timesten.oracle.com/sample edited
```

2. Use the kubectl get command to assess the state of the sample TimesTenClassic object. Observe how the state changes as you issue multiple kubectl get commands. Also note that the Operator has successfully configured sample-1 to be the active.

```
% kubectl get ttc sample
       STATE ACTIVE AGE
sample Reexamine None 68m
% kubectl get ttc sample
                        ACTIVE AGE
NAME
      STATE
sample ConfiguringActive None 68m
% kubectl get ttc sample
       STATE ACTIVE AGE
NAME
sample StandbyDown sample-1 68m
% kubectl get ttc sample
NAME STATE ACTIVE sample Normal sample-1
                         AGE
                        71m
```

3. Use the kubectl describe command to further review the actions of the Operator (represented in **bold**).

Not all output is shown:

```
% kubectl describe ttc sample
Name:
           sample
Namespace: mynamespace
Kind:
             TimesTenClassic
Rep Create Statement: create active standby pair
 "{{tt-name}}" on "{{tt-node-0}}",
 "{{tt-name}}" on "{{tt-node-1}}"
RETURN TWOSAFE
store "{{tt-name}}" on "{{tt-node-0}}"
 PORT {{tt-rep-port}} FAILTHRESHOLD 0 TIMEOUT 999
store "{{tt-name}}" on "{{tt-node-1}}"
 PORT {{tt-rep-port}} FAILTHRESHOLD 0 TIMEOUT 999
Spec:
 Ttspec:
   Both Down Behavior: Best
   Db Config Map:
     sample
   Image:
                        container-registry.oracle.com/timesten/
timesten:22.1.1.19.0
   Image Pull Policy: Always
   Image Pull Secret: sekret
   Reexamine:
                        April22reexamine1
   Stop Managing: April21Stop1
   Storage Class Name: oci-bv
   Storage Size:
                       250Gi
Status:
 Classic Upgrade Status:
   Active Start Time:
                                0
   Active Status:
   Image Update Pending:
                                false
   Last Upgrade State Switch:
   Prev Reset Upgrade State:
   Prev Upgrade State:
   Standby Start Time:
                                0
   Standby Status:
   Upgrade Start Time:
   Upgrade State:
 Active Pods:
                                sample-1
 High Level State:
                                Normal
 Last Event:
 Last High Level State Switch: 1619230912
 Pod Status:
   Cache Status:
     Cache Agent:
                         Not Running
     Cache UID Pwd Set: true
     N Cache Groups:
   Db Status:
     Db:
                                  Loaded
     Db Id:
                                  475
     Db Updatable:
                                  No
   Initialized:
                                  true
   Last High Level State Switch: ?
   Pod Status:
     Agent:
                           Uр
     Last Time Reachable: 1619231126
     Pod IP:
                           10.244.7.89
     Pod Phase:
                           Running
   Prev High Level State: Healthy
```

```
Prev Image:
 Replication Status:
   Last Time Rep State Changed: 0
   Rep Agent:
                                Running
   Rep Peer P State:
                               start
   Rep Scheme:
                               Exists
                                STANDBY
   Rep State:
 Times Ten Status:
   Daemon: Up
                  Exists
   Instance:
             Ex. 3000
22.1.1.19.0
   Release:
 Admin User File: false
 Cache User File: false
 Cq File:
                   false
 Disable Return:
                   false
 High Level State: Healthy
 Intended State: Standby
 Local Commit: false
 Name:
                  sample-0
 Schema File:
                  false
 Using Twosafe:
                  false
 Cache Status:
   Cache Agent: Not Running
   Cache UID Pwd Set: true
   N Cache Groups:
 Db Status:
   Db:
                               Loaded
   Db Id:
                               476
   Db Updatable:
                               Yes
 Initialized:
                               true
 Last High Level State Switch: ?
 Pod Status:
   Agent:
   Last Time Reachable: 1619231126
   Pod IP:
                        10.244.6.149
   Pod Phase:
                        Running
 Prev High Level State: Healthy
 Prev Image:
 Replication Status:
   Last Time Rep State Changed: 1619228670
   Rep Agent:
                               Running
   Rep Peer P State:
                               start
   Rep Scheme:
                               Exists
                               ACTIVE
   Rep State:
 Times Ten Status:
   Daemon:
                    Up
   Instance:
Release:
                    Exists
                    22.1.1.19.0
 Admin User File:
                    false
 Cache User File:
                     false
 Cg File:
                      false
                      false
 Disable Return:
 High Level State:
                     Healthy
 Intended State:
                      Active
 Local Commit:
                      false
 Name:
                      sample-1
 Schema File:
                      false
 Using Twosafe:
                      false
Prev High Level State: StandbyDown
Prev Reexamine:
                      April22reexamine1
Prev Stop Managing:
                      April21Stop1
```



```
Rep Create Statement: create active standby pair "sample" on
"sample-0.sample.mynamespace.svc.cluster.local", "sample" on
"sample-1.sample.mynamespace.svc.cluster.local" NO RETURN store "sample" on
"sample-0.sample.mynamespace.svc.cluster.local" PORT 4444 FAILTHRESHOLD 0 store
"sample" on "sample-1.sample.mynamespace.svc.cluster.local" PORT 4444
FAILTHRESHOLD 0
 Rep Port:
 Status Version:
                       1.0
Events:
                                  Message
 Type Reason Age From
                    ----
       StateChange 58m ttclassic TimesTenClassic was Normal, now
ManualInterventionRequired
       StateChange 46m ttclassic Pod sample-0 Daemon Down
       StateChange 41m ttclassic Pod sample-1 Daemon Down
       StateChange 41m ttclassic Pod sample-1 Daemon Up
       StateChange 41m ttclassic Pod sample-1 Database Unloaded
       StateChange 40m ttclassic Pod sample-1 Database Loaded
       StateChange 40m ttclassic Pod sample-1 RepState IDLE
       StateChange 40m ttclassic Pod sample-1 RepAgent Not Running
       StateChange 17m ttclassic Pod sample-1 Database Updatable
       StateChange 17m ttclassic Pod sample-1 RepScheme None
       StateChange 4m21s ttclassic TimesTenClassic was
ManualInterventionRequired, now Reexamine
               4m16s ttclassic Active error: Daemon Down
       StateChange 4m16s ttclassic TimesTenClassic was Reexamine, now
ConfiguringActive
       StateChange 4m10s ttclassic Pod sample-1 RepState ACTIVE
       StateChange 4m10s ttclassic Pod sample-1 RepScheme Exists
       StateChange 4m10s ttclassic Pod sample-1 RepAgent Running
       StateChange 4m8s ttclassic TimesTenClassic was ConfiguringActive, now
StandbyDown
       StateChange 4m3s ttclassic Pod sample-0 Daemon Up
       StateChange 4m3s ttclassic Pod sample-0 Database Unloaded
       StateChange 3m56s ttclassic Pod sample-0 Database None
StateChange 3m42s ttclassic Pod sample-0 Database Loaded
StateChange 3m42s ttclassic Pod sample-0 Database Not Updatable
       StateChange 3m42s ttclassic Pod sample-0 RepAgent Not Running
       StateChange 3m42s ttclassic Pod sample-0 RepState IDLE
       StateChange 3m36s ttclassic Pod sample-0 RepAgent Running
       StateChange 3m36s ttclassic Pod sample-0 RepState STANDBY
       StateChange 3m36s ttclassic TimesTenClassic was StandbyDown, now Normal
```

4. Use the kubectl exec -it command to invoke the shell within the sample-1 Pod that contains the TimesTen database. Then, verify you can connect to the active database.

```
% kubectl exec -it sample-1 -c tt -- /bin/bash
$ ttIsql sample

Copyright (c) 1996, 2023, Oracle and/or its affiliates. All rights reserved.
Type ? or "help" for help, type "exit" to quit ttIsql.

connect "DSN=sample";
Connection successful: DSN=sample;UID=timesten;DataStore=/tt/home/timesten/datastore/sample;
DatabaseCharacterSet=AL32UTF8;ConnectionCharacterSet=AL32UTF8;AutoCreate=0;PermSize =200;DDLReplicationLevel=3;ForceDisconnectEnabled=1;
(Default setting AutoCommit=1)
Command> call ttRepStateGet;
```

```
< ACTIVE > 1 row found.
```

5. Use the kubectl exec -it command to invoke the shell within the sample-0 Pod that contains the TimesTen database. Then, verify you can connect to the standby database.

```
% kubectl exec -it sample-0 -c tt -- /bin/bash
% ttIsql sample

Copyright (c) 1996, 2023, Oracle and/or its affiliates. All rights reserved.
Type ? or "help" for help, type "exit" to quit ttIsql.

connect "DSN=sample";
Connection successful: DSN=sample;UID=timesten;DataStore=/tt/home/timesten/datastore/sample;
DatabaseCharacterSet=AL32UTF8;ConnectionCharacterSet=AL32UTF8;AutoCreate=0;PermSize=200;DDLReplicationLevel=3;ForceDisconnectEnabled=1;(Default setting AutoCommit=1)
Command> call ttRepStateGet;
< STANDBY >
1 row found.
```

The Operator is now managing and monitoring your TimesTenClassic object. The TimesTenClassic object is in the Normal state. Both databases are up and running and ready for use.

Suspend Management of a TimesTenClassic Object

These sections discuss why you may want to suspend the management of your TimesTenClassic object by the Operator and then how to do it:

- About Suspending Management
- Suspend Management

About Suspending Management

The Operator periodically examines the state of the TimesTen instances and the databases associated with each TimesTenClassic object. It takes actions to repair anything that is broken. You may have a situation in which you want to manually perform maintenance operations. In such a situation, you do not want the Operator to interfere and attempt to perform repair operations.

You could stop the Operator (by deleting the Deployment of the timesten-operator). This action prevents the Operator from interfering. See "Revert to Manual Control" for more information. However, if you have more than one TimesTenClassic object and you delete the Operator, this interferes with the management of all the TimesTenClassic objects, when perhaps only one of them needs manual intervention.

Alternatively, you can direct the Operator to take no action for one TimesTenClassic object by specifying the <code>.spec.stopManaging</code> datum for this TimesTenClassic object. See "TimesTenClassicSpecSpec" for more information on this element. The Operator examines the value of <code>.spec.ttspec.stopManaging</code> and if it has changed since the last time the Operator examined it, the Operator changes the state of the TimesTenClassic object to <code>ManualInterventionRequired</code>. This causes the Operator to



no longer examine the status of the TimesTen Pods, the containers, the instances, and the databases associated with the TimesTenClassic object. The Operator takes no action on the object or its Pods.

When you want the Operator to manage the TimesTenClassic object again, you change the value of the .spec.ttspec.reexamine datum. See "About the ManualInterventionRequired State" for more information on the ManualInterventionRequired state and the .spec.ttspec.reexamine datum.

In this way, you can perform manual operations on TimesTen without deleting the Deployment of the timesten-operator.

Suspend Management

This example illustrates how to use the <code>.spec.ttspec.stopManaging</code> datum to direct the Operator to stop managing one of the TimesTenClassic objects running in your Kubernetes cluster. In this example, there are two TimesTenClassic objects (<code>sample</code> and <code>sample2</code>) that are running. There is a requirement for you to perform manual maintenance operations on the TimesTen databases associated with one of the objects (<code>sample</code>, in this example). You want the Operator to stop managing this <code>sample</code> TimesTenClassic object. However, you want the Operator to continue managing the other TimesTenClassic object (<code>sample2</code>, in this example).

Perform these steps:

1. Review the Pods that are running.

% kubectl get pods				
NAME	READY	STATUS	RESTARTS	AGE
sample-0	2/2	Running	0	6m33s
sample-1	2/2	Running	0	6m32s
sample2-0	2/2	Running	0	6m32s
sample2-1	2/2	Running	0	6m32s
timesten-operator-846cb5c97c-cxb12	1/1	Running	0	4d20h

2. Confirm the sample TimesTenClassic object is in the Normal state. Recall that you want to perform maintenance on the TimesTen databases associated with this object.

```
% kubectl get ttc sample
NAME STATE ACTIVE AGE
sample Normal sample-0 13m
```

3. Set the .spec.ttspec.stopManaging value. The value must be different than the current value for the TimesTenClassic object. When the Operator examines this value and notices it has changed since the last iteration, it will take appropriate action.

Use the kubectl edit command to edit the TimesTenClassic object.

- If there is a line for .spec.ttspec.stopManaging in the file, then modify its value. It must be different than the current value.
- If there is no line for .spec.ttspec.stopManaging in the file, then add a line and specify a value.

In this example, there is no .spec.ttspec.stopManaging line. This example adds the .spec.ttspec.stopManaging line and sets the value for .spec.ttspec.stopManaging to April21Stop1 (represented in **bold**).

Note: Not all output is shown:

```
% kubectl edit timestenclassic sample
# Please edit the object below. Lines beginning with a '#' will be ignored,
```



```
# and an empty file will abort the edit. If an error occurs while saving
# file will be reopened with the relevant failures.
apiVersion: timesten.oracle.com/v1
kind: TimesTenClassic
metadata:
 name: sample
 namespace: mynamespace
repCreateStatement: |
 create active standby pair
    "{{tt-name}}" on "{{tt-node-0}}",
    "{{tt-name}}" on "{{tt-node-1}}"
 RETURN TWOSAFE
 store "{{tt-name}}" on "{{tt-node-0}}"
    PORT {{tt-rep-port}} FAILTHRESHOLD 0 TIMEOUT 999
  store "{{tt-name}}" on "{{tt-node-1}}"
    PORT {{tt-rep-port}} FAILTHRESHOLD 0 TIMEOUT 999
spec:
 ttspec:
   bothDownBehavior: Best
   dbConfigMap:
    image: container-registry.oracle.com/timesten/timesten:22.1.1.19.0
    imagePullSecret: sekret
    storageClassName: oci-bv
    storageSize: 250Gi
    stopManaging: April21Stop1
timestenclassic.timesten.oracle.com/sample edited
```

4. Use the kubectl get command to check the state of the sample TimesTenClassic object. Note that the sample TimesTenClassic object has transitioned to the ManualInterventionRequired state. This is the expected behavior after changing the .spec.ttspec.stopManaging value to a new value.

```
% kubectl get ttc sample
NAME STATE ACTIVE AGE
sample ManualInterventionRequired sample-0 15m
```

The sample TimesTenClassic object is in the ManualInterventionRequired state. The Operator has suspended the monitoring and the management of the sample TimesTenClassic object. It will take no further action on this TimesTenClassic object or its Pods. You can now perform manual operations on your TimesTen databases. When you have completed such operations and are ready for the Operator to resume management, proceed to About Bringing Up One Database.

Locate the Operator

The Operator is configured in your Kubernetes cluster using a Deployment. Kubernetes automatically monitors the Operator and restarts it if it fails. The Operator runs in a Pod and the name of the Operator begins with timesten-operator, followed by arbitrary characters to make the name unique. If you specify multiple replicas when you deploy the Operator, there are multiple Pods. Only one Pod is active at a time. The remainder of the Pods wait for the active to fail, and if it does, then one of the Pods becomes active. Active standby pairs of TimesTen databases, provisioned by the Operator, continue to function if the Operator fails. When a new Operator is started by

Kubernetes, it automatically monitors and manages all existing active standby pairs of databases.

Use the kubectl get pods command to display the Pods that are running the Operator. In this example, there is one Pod for the Operator. When you deployed the Operator, you specified the value of 1 for the replicas field. Therefore, Kubernetes created one Pod. See About Deploying the TimesTen Operator.

Manage the TimesTen Databases

The Operator strives to keep your active standby pair of databases running once they are deployed. Kubernetes manages the lifecycle of the Pods. It recreates the Pods if they fail. It also recreates the Pods on available Kubernetes cluster nodes, if the nodes on which the Pods are running fail. The Operator monitors TimesTen running in the Pods, and initiates the appropriate operations to keep the pair of databases operational. These operations are done automatically by the Operator, and should require minimal human intervention.

These sections discuss the manual operations you can perform:

- Manually Invoke TimesTen Utilities
- Modify TimesTen Connection Attributes
- Revert to Manual Control
- Delete an Active Standby Pair of TimesTen Databases

Manually Invoke TimesTen Utilities

You can use the kubectl exec -it command to manually invoke TimesTen utilities on your TimesTen instances. This command invokes shells in the Pods and enables you to control the running of TimesTen in the Pods.

TimesTen runs in the tt container, as the timesten user.



The Operator is still querying the status of the Pod, and the status of TimesTen within the Pod. If you invoke a command that disrupts the functioning of either the Pod or TimesTen, the Operator may act to try to fix what you did.

This example shows how to use the kubectl exec -it command to invoke the shell within the sample-0 Pod that contains the TimesTen database. Then, you can run the ttlsql utility.

```
% kubectl exec -it sample-0 -c tt -- /bin/bash
% ttIsql sample
Copyright (c) 1996, 2023, Oracle and/or its affiliates. All rights reserved.
Type ? or "help" for help, type "exit" to quit ttIsql.
```



```
connect "DSN=sample";
Connection successful:
DSN=sample;UID=timesten;DataStore=/tt/home/timesten/datastore/sample;
DatabaseCharacterSet=AL32UTF8;ConnectionCharacterSet=AL32UTF8;PermSize=200;
DDLReplicationLevel=3;
(Default setting AutoCommit=1)
```

Modify TimesTen Connection Attributes

TimesTen uses connection attributes to define the attributes of a database. There are three types of connection attributes:

- Data store attributes: Define the characteristics of a database that can only be changed by destroying and recreating the database.
- First connection attributes: Define the characteristics of a database that can be changed by unloading and reloading the database into memory.
- General connection attributes: Control how applications access the database.
 These attributes persist for the duration of the connection.

For more information on TimesTen connection attributes, see List of Connection Attributes in the *Oracle TimesTen In-Memory Database Reference* and Connection Attributes for Data Manager DSNs or Server DSNs in the *Oracle TimesTen In-Memory Database Operations Guide*.

In a Kubernetes environment:

- You can only modify data store attributes by deleting the TimesTenClassic object and the PersistentVolumeClaims associated with the TimesTenClassic object.
 Doing so results in the deletion of the TimesTen databases. See Delete an Active Standby Pair of TimesTen Databases and Clean Up for information on the deletion process.
- You can modify first connection and general connection attributes without deleting the TimesTenClassic object (which deletes the databases) and the PersistentVolumeClaims associated with the TimesTenClassic object. Note that there are TimesTen restrictions when modifying some of the first connection attributes.

To modify first or general connection attributes:

 You must first edit the db.ini file. Complete the procedure in the Manually Edit the db.ini File section. This section must be completed first.

Then, take these steps:

- If you are modifying first connection attributes, follow the procedure in the Modify First Connection Attributes section.
- If you are modifying general connection attributes, follow the procedure in the Modify General Connection Attributes section.

Manually Edit the db.ini File

Complete this section if you are modifying first or general connection attributes or both. This section must be completed before proceeding to the Modify First Connection Attributes or the Modify General Connection Attributes sections.



To modify first or general connection attribute requires a change in the sys.odbc.ini file.

If you have already created your active standby pair of TimesTen databases by creating a TimesTenClassic object, and you now want to change one or more first or general connection attributes in your sys.odbc.ini file, you must change the db.ini file.

The details as to how you should modify your db.ini file depends on the facility originally used to contain the db.ini file. (Possible facilities include ConfigMaps, Secrets, or init containers. See Populate the /ttconfig Directory for details.)

In this example, the ConfigMap facility was originally used to contain the db.ini file and to populate the /ttconfig directory of the TimesTen containers. The example modifies the sample ConfigMap.

The steps are:

1. Use the kubectl describe command to review the contents of the db.ini file (represented in **bold**) located in the original sample ConfigMap.

```
% kubectl describe configmap sample
Name:
           sample
Namespace: mynamespace
Labels: <none>
Annotations: <none>
Data
====
adminUser:
sampleuser/samplepw
db.ini:
PermSize=200
DatabaseCharacterSet=AL32UTF8
ConnectionCharacterSet=AL32UTF8
schema.sql:
create sequence sampleuser.s;
create table sampleuser.emp (id number not null primary key, name char (32));
Events: <none>
```

2. Use the kubectl edit command to modify the db.ini file in the original sample ConfigMap. Change the PermSize first connection attribute to 600 (represented in bold). Add the TempSize first connection attribute and set its value to 300 (represented in bold). Add the ConnectionCharacterSet connection attribute.

```
% kubectl edit configmap sample
# Please edit the object below. Lines beginning with a '#' will be ignored,
# and an empty file will abort the edit. If an error occurs while saving this
# file will be reopened with the relevant failures.
#
apiVersion: v1
data:
   adminUser: |
        sampleuser/samplepw
   db.ini: |
        PermSize=600
        TempSize=300
```



```
DatabaseCharacterSet=AL32UTF8

ConnectionCharacterSet=AL32UTF8

schema.sql: |
    create sequence sampleuser.s;
    create table sampleuser.emp (id number not null primary key, name char (32));
kind: ConfigMap

metadata:
    creationTimestamp: "2023-04-30T19:23:59Z"
    name: sample
    namespace: mynamespace
    resourceVersion: "71907255"
    selfLink: /api/v1/namespaces/mynamespace/configmaps/sample
    uid: 0171ff7f-f789-11ea-82ad-0a580aed0453
...
configmap/sample edited
```

3. Use the kubectl describe command to verify the changes to the sample ConfigMap. (The changes are represented in **bold**.)

```
% kubectl describe configmap sample
Name:
         sample
Namespace: mynamespace
Labels: <none>
Annotations: <none>
Data
schema.sql:
create sequence sampleuser.s;
create table sampleuser.emp (id number not null primary key, name char (32));
adminUser:
sampleuser/samplepw
db.ini:
PermSize=600
TempSize=300
DatabaseCharacterSet=AL32UTF8
ConnectionCharacterSet=AL32UTF8
Events: <none>
```

You have successfully changed the sample ConfigMap. If you are modifying first connection attributes, proceed to the Modify First Connection Attributes section. If you are modifying only general connection attributes, proceed to the Modify General Connection Attributes section.

Modify First Connection Attributes

If you have not modified the <code>db.ini</code> file, proceed to the Manually Edit the <code>db.ini</code> File section. You must now delete the standby Pod and then delete the active Pod. When you delete a Pod that contains a container running TimesTen, the Operator creates a new Pod to replace the deleted Pod. This new Pod contains a new <code>sys.odbc.ini</code> file which is created from the contents of the <code>db.ini</code> file located in the <code>/ttconfig</code> directory.

Perform these steps to delete the standby Pod.

1. Use the kubectl get command to determine which Pod is the standby Pod for the sample TimesTenClassic object. The active Pod is the Pod represented in the ACTIVE column. The standby Pod is the other Pod (not represented in the ACTIVE column). Therefore, for the sample TimesTenClassic object, the active Pod is sample-0, (represented in bold) and the standby Pod is sample-1.

```
% kubectl get ttc sample
NAME STATE ACTIVE AGE
sample Normal sample-0 47h
```

2. Delete the standby Pod (sample-1, in this example). This results in the Operator creating a new standby Pod to replace the deleted Pod. When the new standby Pod is created, it will use the newly modified sample ConfigMap. (You modified this ConfigMap in the Manually Edit the db.ini File section.)

```
% kubectl delete pod sample-1
pod "sample-1" deleted
```

3. Use the kubectl get command to verify the standby Pod is up and running and the state is Normal.

Note that the state is StandbyDown (represented in **bold**).

```
% kubectl get ttc sample
NAME STATE ACTIVE AGE
sample StandbyDown sample-0 47h
```

Wait a few minutes, then run the command again. Note that the state has changed to Normal (represented in **bold**).

```
% kubectl get ttc sample
NAME STATE ACTIVE AGE
sample Normal sample-0 47h
```

4. Use the kubectl exec -it command to invoke the shell in the standby Pod (sample-1, in this example). Then, run the ttlsql utility to connect to the sample database. Note the new PermSize value of 600 and the new TempSize value of 300 in the connection output (represented in **bold**).

```
% kubectl exec -it sample-1 -c tt -- /bin/bash
% ttIsql sample
Copyright (c) 1996, 2023, Oracle and/or its affiliates. All rights reserved.
Type ? or "help" for help, type "exit" to quit ttIsql.
connect "DSN=sample";
Connection successful:
DSN=sample;UID=timesten;DataStore=/tt/home/timesten/datastore/sample;
DatabaseCharacterSet=AL32UTF8;ConnectionCharacterSet=AL32UTF8;
AutoCreate=0;PermSize=600;TempSize=300;DDLReplicationLevel=3;
ForceDisconnectEnabled=1;
(Default setting AutoCommit=1)
```

5. Fail over from the active Pod to the standby Pod. See "Fail Over" for details of the fail over process. Before you begin this step, ensure you quiesce your applications and you use the ttRepAdmin -wait command to wait until replication is caught up, such that all transactions that were executed on the active database have been replicated to the standby database. Once the standby is caught up, fail over from the active database to the standby by deleting the active Pod. When you delete the active Pod, the Operator automatically detects the failure and promotes the standby database to be the active.

Delete the active Pod (sample-0, in this example).



```
% kubectl delete pod sample-0
pod "sample-0" deleted
```

6. Wait a few minutes, then use the kubectl get command to verify the active Pod is now sample-1 for the sample TimesTenClassic object and the state is Normal (represented in **bold**).

```
% kubectl get ttc sample
NAME STATE ACTIVE AGE
sample Normal sample-1 47h
```

7. Use the kubectl exec -it command to invoke the shell in the active Pod (sample-1, in this example). Then, run the ttIsql utility to connect to the sample database. Note the new PermSize value of 600 and the new TempSize value of 300 in the connection output (represented in **bold**).

```
% kubectl exec -it sample-1 -c tt -- /bin/bash
Last login: Fri Apr 08 15:50:29 UTC 2023 on pts/0
[timesten@sample-1 ~]$ ttIsql sample

Copyright (c) 1996, 2023, Oracle and/or its affiliates. All rights reserved.
Type ? or "help" for help, type "exit" to quit ttIsql.

connect "DSN=sample";
Connection successful:
DSN=sample;UID=timesten;DataStore=/tt/home/timesten/datastore/sample;
DatabaseCharacterSet=AL32UTF8;ConnectionCharacterSet=AL32UTF8;
AutoCreate=0;PermSize=600;TempSize=300;DDLReplicationLevel=3;
ForceDisconnectEnabled=1;
(Default setting AutoCommit=1)
```

8. Use the kubectl exec -it command to invoke the shell in the standby Pod (sample-0, in this example). Then, run the ttlsql utility to connect to the sample database. Note the new PermSize value of 600 and the new TempSize value of 300 in the connection output (represented in **bold**).

```
% kubectl exec -it sample-0 -c tt -- /bin/bash
% ttIsql sample

Copyright (c) 1996, 2023, Oracle and/or its affiliates. All rights reserved.
Type ? or "help" for help, type "exit" to quit ttIsql.

connect "DSN=sample";
Connection successful:
DSN=sample;UID=timesten;DataStore=/tt/home/timesten/datastore/sample;
DatabaseCharacterSet=AL32UTF8;ConnectionCharacterSet=AL32UTF8;
AutoCreate=0;PermSize=600;TempSize=300;DDLReplicationLevel=3;
ForceDisconnectEnabled=1;
(Default setting AutoCommit=1)
```

You have successfully modified the PermSize and the TempSize first connection attributes.

Modify General Connection Attributes

If you have not modified the db.ini file, proceed to the Manually Edit the db.ini File section. You can either directly modify the sys.odbc.ini file for the active TimesTen



database and the <code>sys.odbc.ini</code> file for the standby TimesTen database or you can follow the steps in the Modify First Connection Attributes section. The first approach (modifying the <code>sys.odbc.ini</code> file directly) is less disruptive.

This section discusses the procedure for directly modifying the sys.odbc.ini files.

The sys.odbc.ini file is located in the TimesTen container of the Pod containing the active TimesTen database and in the TimesTen container of the Pod containing the standby TimesTen database. After you complete the modifications to the sys.odbc.ini files, subsequent applications can connect to the database using these general connection attributes.

This example illustrates how to edit the sys.odbc.ini files.

1. Use the kubectl exec -it command to invoke a shell in the active Pod. (In this example, sample-0 is the active Pod.)

```
% kubectl exec -it sample-0 -c tt -- /bin/bash
Last login: Fri Apr 08 22:43:26 UTC 2023 on pts/8
```

2. Verify the current directory (/tt/home/timesten).

```
% pwd
/tt/home/timesten
```

3. Navigate to the directory where the sys.odbc.ini file is located. The sys.odbc.ini file is located in the /tt/home/timesten/instances/instance1/conf directory. Therefore, navigate to the instances/instance1/conf directory.

```
% cd instances/instance1/conf
```

4. Edit the sys.odbc.ini file, adding, modifying, or deleting the general connection attributes for your DSN. (sample, in this example.)



Ensure that you only make modifications to the TimesTen general connection attributes. Data store attributes and first connection attributes cannot be modified by directly editing the sys.odbc.ini file.

This example modifies the sample DSN, adding the ConnectionCharacterSet general connection attribute and setting its value equal to AL32UTF8 (represented in **bold**).

```
vi sys.odbc.ini
[ODBC Data Sources]
sample=TimesTen 22.1 Driver
tt=TimesTen 22.1 Driver

[sample]
Datastore=/tt/home/timesten/datastore/sample
PermSize=200
DatabaseCharacterSet=AL32UTF8
ConnectionCharacterSet=AL32UTF8
DDLReplicationLevel=3
AutoCreate=0
ForceDisconnectEnabled=1
...
```



5. Use the ttIsql utility to connect to the sample database and verify the value of the ConnectionCharacterSet attribute is AL32UTF8 (represented in **bold**).

```
% ttIsql sample
Copyright (c) 1996, 2023, Oracle and/or its affiliates. All rights reserved.
Type ? or "help" for help, type "exit" to quit ttIsql.

connect "DSN=sample";
Connection successful:
DSN=sample;UID=timesten;DataStore=/tt/home/timesten/datastore/sample;
DatabaseCharacterSet=AL32UTF8;ConnectionCharacterSet=AL32UTF8;
AutoCreate=0;PermSize=200;DDLReplicationLevel=3;ForceDisconnectEnabled=1;
(Default setting AutoCommit=1)
```

You have successfully modified the sys.odbc.ini file located in the TimesTen container of the active Pod (in this example, sample-0). Use the same procedure to modify the sys.odbc.ini file located in the TimesTen container of the standby Pod (in this example, sample-1).

For example:

1. Use the kubectl exec -it command to invoke a shell in the standby Pod (sample-1, in this example).

```
% kubectl exec -it sample-1 -c tt -- /bin/bash
Last login: Fri Apr 08 23:08:08 UTC 2023 on pts/0
```

2. Verify the current directory (/tt/home/timesten).

```
% pwd
/tt/home/timesten
```

3. Navigate to the directory where the sys.odbc.ini file is located. The sys.odbc.ini file is located in the /tt/home/timesten/instances/instance1/conf directory. Therefore, navigate to the instances/instance1/conf directory.

```
% cd instances/instance1/conf
```

4. Edit the sys.odbc.ini file, adding, modifying, or deleting the same general connection attributes that you modified for the active database. Therefore, this example modifies the sample DSN, adding the ConnectionCharacterSet general connection attribute and setting its value equal to AL32UTF8 (represented in **bold**).

```
vi sys.odbc.ini

[ODBC Data Sources]
sample=TimesTen 22.1 Driver
tt=TimesTen 22.1 Driver

[sample]
Datastore=/tt/home/timesten/datastore/sample
PermSize=200
DatabaseCharacterSet=AL32UTF8

ConnectionCharacterSet=AL32UTF8

DDLReplicationLevel=3
AutoCreate=0
ForceDisconnectEnabled=1
```



5. Use the ttIsql utility to connect to the sample database and verify the value of the ConnectionCharacterSet attribute is AL32UTF8 (represented in **bold**).

```
% ttIsql sample
Copyright (c) 1996, 2023, Oracle and/or its affiliates. All rights reserved.
Type ? or "help" for help, type "exit" to quit ttIsql.

connect "DSN=sample";
Connection successful:
DSN=sample;UID=timesten;DataStore=/tt/home/timesten/datastore/sample;
DatabaseCharacterSet=AL32UTF8;ConnectionCharacterSet=AL32UTF8;
AutoCreate=0;PermSize=200;DDLReplicationLevel=3;ForceDisconnectEnabled=1;
(Default setting AutoCommit=1)
```

You have successfully modified the sys.odbc.ini file located in the TimesTen container of the active Pod (sample-0) and the sys.odbc.ini file located in the TimesTen container of the standby Pod (sample-1). The ConnectionCharacterSet general connection attribute has also been modified.

Revert to Manual Control

If you want to manually operate your active standby pair, you can delete the timesten-operator Deployment. The Operator stops, and does not restart. This affects all of the TimesTenClassic objects that are running in your Kubernetes cluster. If you do not want the Operator to stop managing all of the TimesTenClassic objects, you can suspend the management of individual TimesTenClassic objects. See "Suspend Management of a TimesTenClassic Object" for information.

The TimesTenClassic object, representing the active standby pair of TimesTen databases, remains in Kubernetes, as do the other Kubernetes objects associated with them. You can use the kubectlexec-it command to invoke shells in the Pods, and then you can control Timesten that is running in those Pods.

If one or both Pods in your active standby pair fails, Kubernetes creates new ones to replace them. This is due to the StatefulSet object that the Operator had previously created in Kubernetes. However, since the Operator is not running the new Pods, it cannot automatically start TimesTen. In this case, your active standby pair cannot be configured or started. You are responsible for the operation of TimesTen in the Pods.

If you want the Operator to take control again, you must redeploy the Operator. Once the Operator is redeployed, the Operator automatically identifies the TimesTenClassic objects in your Kubernetes cluster, and will attempt to manage them again.

This example shows you how to manually control TimesTen.

1. Verify the Operator and the TimesTen databases are running.

```
% kubectl get pods
NAME
                                         READY
                                                STATUS
                                                         RESTARTS
                                                                    AGE
sample-0
                                         2/2
                                                Running 0
                                                                    18h
sample-1
                                         2/2
                                                Running 0
                                                                    18h
timesten-operator-5d7dcc7948-pzj58
                                         1/1
                                                Running 0
                                                                    18h
```

Navigate to the /deploy directory where the operator.yaml resides. (kube_files/deploy, in this example.)

```
% cd kube files/deploy
```



3. Use the kubectl delete command to delete the Operator. The Operator is stopped and no longer deployed.

```
% kubectl delete -f operator.yaml
deployment.apps "timesten-operator" deleted
```

4. Verify the Operator is no longer running, but the TimesTen databases are.

```
% kubectl get pods
       READY STATUS
NAME
                      RESTARTS
                              AGE
sample-0 2/2
              Running 0
                              19h
sample-1 2/2
              Running 0
                              19h
```

5. Use the kubectl exec -it command to invoke the shell in the Pod that runs TimesTen.

```
% kubectl exec -it sample-0 -c tt -- /bin/bash
Last login: Fri Apr 8 14:30:45 UTC 2023 on pts/0
```

6. Run the ttStatus utility.

```
% t.t.St.at.us
TimesTen status report as of Fri Apr 8 14:36:31 2023
Daemon pid 183 port 6624 instance instance1
TimesTen server pid 190 started on port 6625
```

Data store /tt/home/timesten/datastore/sample Daemon pid 183 port 6624 instance instance1 TimesTen server pid 190 started on port 6625 There are 20 connections to the data store Shared Memory KEY 0x02200bbc ID 32769 PL/SQL Memory Key 0x03200bbc ID 65538 Address 0x5000000000 PID Context Type Connection Name Replication 263 0x00007f99fc0008c0 LOGFORCE:140299698493184 2029
 Replication
 263
 0x00007f9a040008c0
 XLA_PARENT:140300350273280
 2031

 Replication
 263
 0x00007f9a080008c0
 REPLISTENER:140300347123456
 2030
 Replication

Replication 263 0x00007f9a080acd60 RECEIVER:140299429472000 263 0x00007f9a0c0008c0 FAILOVER:140300353423104 Replication 263 0x00007f9a2c0009b0 TRANSMITTER(M):140299695343360 2034 Replication 263 0x00007f9a300008c0 REPHOLD:140300356572928 2033 Subdaemon 187 0x00000000023365b0 Manager 2047 Subdaemon 187 0x00000000023b57f0 Rollback 2046 187 0x0000000002432cf0 Log Marker Subdaemon 2041 Subdaemon 187 0x000000000244fc00 Garbage Collector 2035 Subdaemon 187 0x00007f90c80008c0 Aging 2038 Subdaemon 187 0x00007f90d00008c0 Deadlock Detector 2044 Subdaemon 0x00007f90d001d7d0 HistGC 187 2039 Subdaemon 187 0x00007f90d40008c0 Checkpoint 2042 Subdaemon 187 0x00007f90d401d7d0 AsyncMV 2036 187 0x00007f90d80008c0 Monitor



Subdaemon

ConnID

2028

2032

```
2043
Subdaemon
             187
                     0x00007f90f808b360 IndexGC
                                                                      2037
Subdaemon
Subdaemon
             187 0x00007f90fc0008c0 Flusher
                                                                      2045
             187 0x00007f910004efd0 XactId Rollback
                                                                      2040
Open for user connections
RAM residence policy: Always
Replication policy : Manual
Replication agent is running.
Cache Agent policy : Manual
PL/SQL enabled.
-----
Accessible by group timesten
End of report
```

7. Run the ttIsql utility to connect to the sample database and perform various operations.

```
% ttIsql sample
Copyright (c) 1996, 2023, Oracle and/or its affiliates. All rights reserved.
Type ? or "help" for help, type "exit" to quit ttIsql.
connect "DSN=sample";
Connection successful:
DSN=sample; UID=timesten; DataStore=/tt/home/timesten/datastore/sample;
DatabaseCharacterSet=AL32UTF8; ConnectionCharacterSet=AL32UTF8; PermSize=200;
DDLReplicationLevel=3;
(Default setting AutoCommit=1)
Command> describe sampleuser.emp;
Table SAMPLEUSER.EMP:
 Columns:
   *ID
                                    NUMBER NOT NULL
   NAME
                                    CHAR (32)
1 table found.
(primary key columns are indicated with *)
Command> INSERT INTO sampleuser.emp VALUES (1, 'This is a test.');
1 row inserted.
Command> SELECT * FROM sampleuser.emp;
< 1, This is a test.
1 row found.
```

Delete an Active Standby Pair of TimesTen Databases

If you delete the TimesTenClassic object that represents the active standby pair of TimesTen databases, Kubernetes automatically deletes all the Kubernetes objects and the resources it is using. The StatefulSet, the Service, and the Pods, that are associated with the pair are all deleted from Kubernetes. However, the PersistentVolumeClaims (that contain the TimesTen databases) are not deleted. You must manually delete the PersistentVolumeClaims (PVCs) after you delete the TimesTenClassic object. After you manually delete the PVCs, the PersistentVolumes, holding the databases, are recycled by Kubernetes. (You may be able to control this using the Kubernetes volume retention policy, but this is not controlled by the Operator.)

As an example, use the kubectl delete command to delete the PVCs for the sample databases.

% kubectl delete pvc tt-persistent-sample-0
persistentvolumeclaim "tt-persistent-sample-0" deleted
% kubectl delete pvc tt-persistent-sample-1
persistentvolumeclaim "tt-persistent-sample-1" deleted



10

Manage TimesTen Scaleout

This chapter discusses how the TimesTen Operator manages and repairs TimesTen Scaleout.

Topics:

- About Managing TimesTen Scaleout
- About Single Data Instance Failure
- About Management Instance Failure
- About the waiting for seed State
- About Failure of All Data Instances
- About High Level States
- About Management States
- About Database and Element States
- About the ManualInterventionRequired State
- About Suspending Management
- Simulate Single Data Instance Failure
- Simulate Management Instance Failure
- Simulate Replica Set Failure with Restart
- Simulate Replica Set Failure with Manual
- Suspend Management
- Set reexamine Datum

About Managing TimesTen Scaleout

TimesTen Scaleout delivers high performance, fault tolerance, and scalability within a highly available in-memory database that provides persistence and recovery. Since a database is distributed across multiple hosts, some components of the database may fail while others continue to operate.

TimesTen Scaleout supports error and failure detection with automatic recovery for many error and failure situations in order to maintain a continuous operation for all applications.

The TimesTen Operator implements best practices for how to handle failures for TimesTen Scaleout. For more information about how TimesTen Scaleout handles failures, see Recovering from Failure in the *Oracle TimesTen In-Memory Database Scaleout User's Guide*

In particular, the Operator detects and handles the following failure cases:

- If a TimesTen instance or element fails, the Operator restarts it.
- If an entire replica set fails and if all elements in the replica set reach the waiting for seed state, the Operator unloads and reloads the database to resolve it (by default). For

details about how TimesTen Scaleout recovers from a down replica set, see Recovering from a Down Replica Set in the *Oracle TimesTen In-Memory Database* Scaleout User's Guide.

If all data instances fail, the Operator detects and reports the failure.

The Operator communicates to the TimesTen agent running in the tt container in each Pod running TimesTen. The agent determines information about the state of TimesTen running in the container and sends that information back to the Operator. The Operator analyzes this information and determines the health and state of TimesTen. This information is summarized in well-defined states. The Operator uses state machines to determine the appropriate set of commands to be executed to detect failures and, if possible, repair TimesTen. These states are discussed later in the chapter.

Let's take a deeper look at how the Operator detects and repairs TimesTen Scaleout. Specifically, let's look at how the Operator handles single data instance failure, management instance failure, entire replica set failure, and total database failure.

About Single Data Instance Failure

TimesTen Scaleout is intended to be resilient to single data instance failures. In your Kubernetes environment, if a data instance fails, the TimesTen Operator starts it back up. Once it is restarted, TimesTen Scaleout reloads the element of the database. See Recovering When a Data Instance Is Down in the *Oracle TimesTen In-Memory Database Scaleout User's Guide*.

About Management Instance Failure

The TimesTen Operator supports one management instance per TimesTenScaleout object. If the management instance is down, the Operator ignores the state of the data instances until the management instance is back up. Without a management instance, the grid and TimesTen database continue to function. However, should a data instance fail without a working management instance, it is not possible to repair the data instance.

About the waiting for seed State

In TimesTen Scaleout, there could be a situation where an entire replica set fails simulataneously. If all elements in a replica set fail at the same time, it may not be possible to reload any of the elements without unloading the entire database and reloading it. In addition, a reload may cause TimesTen Scaleout to discard transactions against other replica sets that were committed prior to the unload operation.

For more information about replica set failure in TimesTen Scaleout, see Recovering from a Down Replica Set in the *Oracle TimesTen In-Memory Database Scaleout User's Guide*.

If this case occurs in your Kubernetes environment, the default behavior is for the TimesTen Operator to detect this situation and forcibly unload and reload the database when the situation occurs. This operation is triggered when the Operator notices that all elements in a replica set are in the waiting for seed state.

You have the option of controlling the behavior of the Operator when all elements in a replica set are in the waiting for seed state. You do this by using a TimesTenScaleout



object's <code>.spec.ttspec.replicaSetRecovery</code> datum, and setting a particular value for the datum. Accepted values are the following:

- Restart: The Operator forcibly unloads and reloads the database when a total replica set failure occurs. This is the default.
- Manual: The Operator changes the state of the TimesTenScaleout object to
 ManualInterventionRequired when a total replica set failure occurs. The Operator takes
 no further action to repair the grid. You must repair it. See About the
 ManualInterventionRequired State and Set reexamine Datum for details.

For more information on the .spec.ttspec.replicaSetRecovery datum for a TimesTenScaleout object, see TimesTenScaleoutSpecSpec.

About Failure of All Data Instances

If all elements in a database fail simultaneously, there must be caution taken in reloading the database. TimesTen Scaleout does not automatically reload a database if all data instances fail. You must perform this reload. It is essential that all possible data instances are up before a reload is attempted.

For more information about failure of all data instances in TimesTen Scaleout, see Database Recovery in the *Oracle TimesTen In-Memory Database Scaleout User's Guide*.

If this case occurs in a Kubernetes environment, the TimesTen Operator does not attempt to reload the database after all data instances fail. However, the Operator does detect this case and changes the state of a TimesTenScaleout object to ManualInterventionRequired. See About the ManualInterventionRequired State and Set reexamine Datum.

About High Level States

The TimesTen Operator maintains a High Level state for TimesTenScaleout objects.

These High Level states are as follows:

- DatabaseDown
- DatabaseImpeded
- DatabasePartial
- DatabaseRestarting
- DatabaseRestartRequired
- Failed
- Initializing
- ManualInterventionRequired
- Normal
- Reexamine
- Unmanaged



DatabaseDown

The database is unusable. The Operator attempts to fix it. If it cannot be fixed, the Operator moves the object to the ManualInterventionRequired state.

DatabaseImpeded

The database within the grid is fully operational, but one or more elements are not functional. All data in the database is available and all SQL is accepted.

DatabasePartial

The database is up, but some data is not available. One or more replica sets are not available.

DatabaseRestarting

The database is in the process of being forcibly unloaded and reloaded after a DatabaseRestartRequired condition.

DatabaseRestartRequired

While the database is up (at least partially), it must be stopped and restarted (unloaded and reloaded) in order to restore functionality. This can occur when all elements in a replica set fail simultaneously and all elements are unloadable due to a waiting for seed condition. When this occurs, the database must be unloaded and reloaded. During this time, committed transactions may be lost. See Database Recovery and Recovering from a Down Replica Set in the *Oracle TimesTen In-Memory Database Scaleout User's Guide*.

Failed

If a problem occurs while Initializing a TimesTenScaleout object, the object transitions to the Failed state. Once in this state, the Operator does not attempt to repair the object. You must delete it. Use the kubectl describe command to examine the Operator logs to determine the cause of the problem and then recreate the object.

Initializing

After you create a TimesTenScaleout object in your Kubernetes cluster, the Operator creates the StatefulSets and Services that are required to deploy a TimesTenScaleout grid and database. The Operator assigns a High Level state of Initializing to the TimesTenScaleout object.

ManualInterventionRequired

If the Operator encounters a problem that it does not know how to fix, the Operator places a TimesTenScaleout object into this state. The Operator takes no further action to fix the object. You can set the object's .spec.ttspec.reexamine datum to cause the



Operator to re-engage with the object. For information about .spec.ttspec.reexamine, see Set reexamine Datum.

Normal

The grid and database are up and operating as they should.

Reexamine

If a TimesTenScaleout object is in the ManualInterventionRequired state, and you modify the object's .spec.ttspec.reexamine datum, the TimesTen Operator moves the object into the Reexamine state. The Operator examines the state of grid and database. If healthy, the Operator returns the object to the Normal state. Otherwise, the object re-enters the ManualInterventionRequired state.

Unmanaged

The grid does not have a functional management instance. Until the management instance is fixed, the grid cannot be further monitored, managed or controlled. The Operator will attempt to fix the management instance.

About Management States

The Operator uses the TimesTen ttGridAdmin mgmtExamine utility to determine the health of the management instance. The Operator also synthesizes a management state that describes the status of the management instance in a single value.

For information about the TimesTen ttGridAdmin mgmtExamine utility, see Examine Management Instances (mgmtExamine) in the *Oracle TimesTen In-Memory Database Reference*.

For example, you can use the <code>kubectl get tts</code> command to observe the state of a TimesTenScaleout object.

```
kubectl get tts samplescaleout

NAME OVERALL MGMT CREATE LOAD OPEN AGE
samplescaleout Normal Normal created loaded-complete open 10m
```

Note that the management state is **Normal**. There are additional examples in the chapter where you have the opportunity to observe the management state.

Here are the management states:

- ActiveAgentUp
- ActiveDaemonUp
- ActiveDown
- Error
- Normal
- Unknown



ActiveAgentUp

The TimesTen agent in the container that should be running the management instance is up, but the management instance has not yet been started.

ActiveDaemonUp

The management instance has been started, but is not yet functional.

ActiveDown

The management instance is down.

Error

There is an unexpected error with the management instance.

Normal

The management instance is functioning normally.

Unknown

The state of the management instance cannot be determined.

About Database and Element States

TimesTen Scaleout defines a set of overall database and element status values to determine the status of a database or element. The TimesTen Operator uses these status values to assess the state of the database represented by a TimesTenScaleout object.

In TimesTen Scaleout, the overall database status is encoded in three strings:

- How created is the database?
- How loaded is the database?
- How open is the database?

This triplet of strings is returned as part of the output of the TimesTen ttGridAdmin dbStatus utility.

For information about the database states, see Display the Status of the Database and All Elements in the *Oracle TimesTen In-Memory Database Scaleout User's Guide*. For information about the ttGridAdmin dbstatus utility, see Monitor the Status of a Database (dbStatus) in the *Oracle TimesTen In-Memory Database Reference*.

The TimesTen Operator uses TimesTen Scaleout database states to report the state of the database for a TimesTenScaleout object.



For example, this code snippet uses the kubectl get command to return the status for a deployed TimesTenScaleout object.

kubectl get tts samplescaleout

NAME OVERALL MGMT CREATE

LOAD OPEN AGE

samplescaleout Normal Normal created loadedcomplete open 2d

Note the following:

- The High Level state of the TimesTenScaleout object is Normal (as indicated by the OVERALL field).
- The management instance state is Normal (as indicated by the MGMT field).
- The database creation state is created (as indicated by the CREATE field).
- The database loaded state is loaded-complete (as indicated by the LOAD field).
- The database open state is open (as indicated by the OPEN field).

TimesTen Scaleout also keeps a state for each element in a database. See Troubleshooting Based on Element Status in the *Oracle TimesTen In-Memory Database Scaleout User's Guide* for details on element states.

The Operator does not monitor these element states. However, if all the elements in a replica set are in the waiting for seed state, the Operator checks the value of a TimesTenScaleout object's .spec.ttspec.replicaSetRecovery datum:

- If the value is Restart, the DatabaseRestartRequired High Level state is triggered.
- If the value is Manual, the Operator moves the TimesTenScaleout object to the ManualInterventionRequired state.

About the ManualInterventionRequired State

If the TimesTen Operator determines it cannot repair a TimesTenScaleout object, the Operator changes the High Level state of the object to ManualInterventionRequired. The Operator does not further manage an object in this state. In addition, the Operator makes no attempt to determine its state nor to repair it.

In TimesTen Scaleout, there are several troubleshooting scenarios that you can review to identify and possibly fix the problem. For more information about the troubleshooting scenarios, see Recovering from Failure in the *Oracle TimesTen In-Memory Database Scaleout User's Guide*.

If you identify and fix the problem, you can cause the Operator to resume management of a TimesTenScaleout object. You do this by specifying a TimesTenScaleout object's spec.ttspec.reexamine datum. When this datum is specified, the Operator moves the object to the Reexamine state. For information about the Reexamine state, see Set reexamine Datum.

About Suspending Management

There may be a situation in which you want to manually perform maintenance operations. In such a situation, you do not want the Operator to interfere and attempt to perform repair or recovery operations on your grid and database.



One alternative is to stop the Operator (by deleting the timesten-operator Deployment). This action prevents the Operator from interfering or performing repair/ recovery operations. However, if you have more than one TimesTenScaleout object deployed in your Kubernetes environment and you delete the Operator, this interferes with the management of all the TimesTenScaleout objects, when perhaps only one of them needs manual intervention.

Another approach is to ask the Operator to take no action for one TimesTenScaleout object. To do this, specify a TimesTenScaleout object's <code>.spec.ttspec.stopManaging</code> datum. The Operator examines the value of <code>.spec.ttspec.stopManaging</code> and if it has changed since the last time the Operator examined it, the Operator changes the state of the TimesTenScaleout object to <code>ManualInterventionRequired</code>. This causes the Operator to no longer examine the status of the grid and database. Nor does the Operator examine the Pods, the containers, and the instances associated with this particular TimesTenScaleout object. For an example showing how to set the <code>.spec.ttspec.stopManaging</code> datum for a TimesTenScaleout object, see <code>SuspendManagement</code>.

To cause the Operator to resume management of the TimesTenScaleout object, change the value of the object's .spec.ttspec.reexamine datum. See Set reexamine Datum for details.

See TimesTenScaleoutSpecSpec for information about the TimesTenScaleout object definition.

Simulate Single Data Instance Failure

Let's simulate a single data instance failure and observe how a TimesTenScaleout object transitions through various state changes.



This example is for demonstration purposes only. Do not attempt this example in a production environment.

In the example, there is a deployed TimesTenScaleout object that is functioning properly.

kubectl get tts samplescaleout
NAME OVERALL MGMT CREATE LOAD OPEN
AGE
samplescaleout Normal Normal created loaded-complete open
10m

Note the High Level state is Normal, the management state is Normal, and the database state is created, loaded-complete, open.

To simulate a single data instance failure, let's delete a Pod that contains a data instance. Here are the Pods:

kubectl get pods NAME READY STATUS RESTARTS AGE



samplescaleout-data-1-0	2/2	Running	0	11m
samplescaleout-data-1-1	2/2	Running	0	11m
samplescaleout-data-1-2	2/2	Running	0	11m
samplescaleout-data-2-0	2/2	Running	0	11m
samplescaleout-data-2-1	2/2	Running	0	11m
samplescaleout-data-2-2	2/2	Running	0	11m
samplescaleout-mgmt-0	2/2	Running	0	11m
samplescaleout-zk-0	1/1	Running	0	11m
samplescaleout-zk-1	1/1	Running	0	10m
samplescaleout-zk-2	1/1	Running	0	9m35s
timesten-operator-7677964df9-sp2zp	1/1	Running	0	7d3h

Let's delete the samplescaleout-data-1-0 Pod and observe the behavior.

1. Delete the Pod.

```
kubectl delete pod samplescaleout-data-1-0
pod "samplescaleout-data-1-0" deleted
```

2. Use the kubectl get command to observe state transitions.

The High Level state is <code>DatabaseImpeded</code>, indicating that the database within the grid is fully operational, but one or more elements is not functional. The database <code>loaded state</code> is <code>loaded-functional</code>, indicating loading is in progress and at least one element from each replica set is loaded.

The object transitioned to the Normal High Level state, indicating the grid and database are functioning normally. The database state is loaded-complete, indicating the element loaded successfully.

Even though there was a single data instance failure, TimesTen Scaleout fully recovered. There was no manual intervention required.

Simulate Management Instance Failure

Let's simulate a management instance failure. Let's observe how a TimesTenScaleout object transitions through various state changes.





This example is for demonstration purposes only. Do not attempt this example in a production environment.

In the example, there is a deployed TimesTenScaleout object that is functioning properly.

kubectl get tts	samplescal	eout			
NAME	OVERALL	MGMT	CREATE	LOAD	OPEN
AGE					
samplescaleout	Normal	Normal	created	loaded-complete	open
68m					

Note the High Level state is Normal, the management state is Normal, and the database state is created, loaded-complete, open.

To simulate a management instance failure, let's delete the Pod that contains the management instance. Here are the Pods:

kubectl get pods				
NAME	READY	STATUS	RESTARTS	AGE
samplescaleout-data-1-0	2/2	Running	0	57m
samplescaleout-data-1-1	2/2	Running	0	73m
samplescaleout-data-1-2	2/2	Running	0	73m
samplescaleout-data-2-0	2/2	Running	0	73m
samplescaleout-data-2-1	2/2	Running	0	73m
samplescaleout-data-2-2	2/2	Running	0	73m
samplescaleout-mgmt-0	2/2	Running	0	73m
samplescaleout-zk-0	1/1	Running	0	73m
samplescaleout-zk-1	1/1	Running	0	72m
samplescaleout-zk-2	1/1	Running	0	71m
timesten-operator-7677964df9-sp2zp	1/1	Running	0	7d4h

Let's delete the samplescaleout-mgmt-0 Pod and observe the behavior.

1. Delete the Pod.

```
kubectl delete pod samplescaleout-mgmt-0
pod "samplescaleout-mgmt-0" deleted
```

2. Use the kubectl get command to observe state transitions.

```
kubectl get tts samplescaleout

NAME OVERALL MGMT CREATE

LOAD OPEN AGE

samplescaleout Unmanaged ActiveDown created loaded-
complete open 79m
```

The High Level state is Unmanaged, indicating that the grid has no functional management instance. As a result, the grid cannot be further managed, monitored,



or controlled. The management instance state is ActiveDown, indicating the management instance is down. Note that since the management instance is down, the Operator ignores the state of the data instances until the management instance is back up.

The object remains in the <code>Unmanaged</code> High Level state. The management state transitions to <code>ActiveDaemonUp</code>, indicating the management instance has been started, but is not yet functional.

The object transitioned to the Normal High Level state, indicating the grid and database are functioning normally. The management state is Normal, indicating that management instance is functioning normally.

Even though there was a management instance failure, TimesTen Scaleout fully recovered. There was no manual intervention required.

Simulate Replica Set Failure with Restart

Let's simulate a replica set failure. In this example, a TimesTenScaleout object's .spec.ttspec.replicaSetRecovery datum has not been specified. The default of Restart is assumed, indicating that the TimesTen Operator forcibly unloads and reloads the database when a total replica set failure occurs.

Let's observe how a TimesTenScaleout object transitions through various state changes.

Note:

This example is for demonstration purposes only. Do not attempt this example in a production environment.

In the example, there is a deployed TimesTenScaleout object that is functioning properly.

Note the High Level state is Normal, the management state is Normal, and the database state is created, loaded-complete, open.



In this example, there are t	three replica sets	
------------------------------	--------------------	--

kubectl get pods				
NAME	READY	STATUS	RESTARTS	AGE
samplescaleout-data-1-0	2/2	Running	0	11m
samplescaleout-data-1-1	2/2	Running	0	11m
samplescaleout-data-1-2	2/2	Running	0	11m
samplescaleout-data-2-0	2/2	Running	0	11m
samplescaleout-data-2-1	2/2	Running	0	11m
samplescaleout-data-2-2	2/2	Running	0	11m
samplescaleout-mgmt-0	2/2	Running	0	11m
samplescaleout-zk-0	1/1	Running	0	11m
samplescaleout-zk-1	1/1	Running	0	10m
samplescaleout-zk-2	1/1	Running	0	9m35s
timesten-operator-7677964df9-sp2zp	1/1	Running	0	7d3h

Let's delete the samplescaleout-data-1-0 and samplescaleout-data-2-0 Pods that belong to one of the replica sets.

1. Delete the Pods.

```
kubectl delete pod samplescaleout-data-1-0;kubectl delete pod
samplescaleout-data-2-0
pod "samplescaleout-data-1-0" deleted
pod "samplescaleout-data-2-0" deleted
```

2. Use the kubectl get command to observe state transitions.

The High Level state is <code>DatabasePartial</code> indicating that the database is up, but some data is not available. One or more replica sets have failed completely. The database <code>loaded</code> state is <code>loaded-incomplete</code>, indicating that at least one replica set has no elements that finished loading successfully.

The object transitions to the <code>DatabaseRestartRequired</code> High Level state. This state indicates that while the database is up (at least partially), the database must be stopped and restarted (unloaded and reloaded) in order to restore functionality. This can occur when all elements in a replica set fail simultaneously and such elements are unloadable due to a <code>waiting for seed condition</code>. When this happens



the database must be unloaded and reloaded. At that time, committed transactions may be lost.

kubectl get tts samplescaleout

NAME OVERALL MGMT CREATE

LOAD OPEN AGE

samplescaleout DatabaseRestarting Normal created loading-

incomplete open 114m

The object transitions to the DatabaseRestarting High Level state. This state indicates that the database is being forcibly unloaded and reloaded after a

DatabaseRestartRequired condition.

kubectl get tts samplescaleout

NAME OVERALL MGMT CREATE LOAD OPEN

AGE

samplescaleout Normal Normal created loaded-complete closed

114m

The object transitions to the Normal High Level state, indicating that the grid and database are functioning normally. The database loaded state changed to loaded-complete, indicating every element was loaded successfully. The database open state is closed, indicating the database is closed for connections.

kubectl get tts samplescaleout

NAME OVERALL MGMT CREATE LOAD OPEN AGE

samplescaleout Normal Normal created loaded-complete open

114m

The object remains in the Normal High Level state. The database open state changed to open, indicating the database is now open for connections.

Even though there was a total replica set failure, TimesTen Scaleout forcibly unloaded and reloaded the database. The Operator returned the grid and database to a Normal state, indicating both are functioning normally. There was no manual intervention required.

Simulate Replica Set Failure with Manual

Let's simulate a total replica set failure where a TimesTenScaleout object's .spec.ttspec.replicaSetRecovery datum has a value of Manual.



This example is for demonstration purposes only. Do not attempt this example in a production environment.

Let's take a look at the TimesTenScaleout object definition.

cat samplescaleout2.yaml
apiVersion: timesten.oracle.com/v1



```
kind: TimesTenScaleout
metadata:
 name: samplescaleout2
spec:
  ttspec:
    storageClassName: oci-bv
    storageSize: 250G
    image: container-registry.oracle.com/timesten/timesten:22.1.1.19.0
    imagePullSecret: sekret
    replicaSetRecovery: Manual
    dbConfigMap:
    - samplescaleout2
    k: 2
    nReplicaSets: 3
    nMgmt: 1
    nZookeeper: 3
```

Note the .spec.ttspec.replicaSetRecovery datum for the object has a value of Manual, indicating that the Operator will set this TimesTenScaleout object's High Level state to ManualInterventionRequired when a total replica set failure occurs.

Let's simulate a total replica set failure with this object. Before we begin, let's do a quick check of the state of the object.

```
kubectl get tts samplescaleout2

NAME OVERALL MGMT CREATE LOAD

OPEN AGE
samplescaleout2 Normal Normal created loaded-complete

open 11m
```

Note the High Level state is Normal, the management state is Normal, and the database state is created, loaded-complete, open.

In this example, there are three replica sets.

kubectl get pods				
NAME	READY	STATUS	RESTARTS	AGE
samplescaleout2-data-1-0	2/2	Running	0	12m
samplescaleout2-data-1-1	2/2	Running	0	12m
samplescaleout2-data-1-2	2/2	Running	0	12m
samplescaleout2-data-2-0	2/2	Running	0	12m
samplescaleout2-data-2-1	2/2	Running	0	12m
samplescaleout2-data-2-2	2/2	Running	0	12m
<pre>samplescaleout2-mgmt-0</pre>	2/2	Running	0	13m
samplescaleout2-zk-0	1/1	Running	0	13m
samplescaleout2-zk-1	1/1	Running	0	12m
samplescaleout2-zk-2	1/1	Running	0	11m
timesten-operator-7677964df9-sp2zp	1/1	Running	0	7d6h

Let's delete the samplescaleout2-data-1-0 and samplescaleout2-data-2-0 Pods that belong to one of the replica sets.

1. Delete the Pods.

```
kubectl delete pod samplescaleout2-data-1-0;kubectl delete pod
samplescaleout2-data-2-0
pod "samplescaleout2-data-1-0" deleted
pod "samplescaleout2-data-2-0" deleted
```

2. Use the kubectl get command to observe state transitions.

The High Level state is <code>DatabasePartial</code> indicating that the database is up, but some data is not available. One or more replica sets have failed completely. The database <code>loaded state</code> is <code>loaded-incomplete</code>, indicating that at least one replica set has no elements that finished loading successfully.

```
kubectl get tts samplescaleout2

NAME OVERALL MGMT CREATE

LOAD OPEN AGE

samplescaleout2 ManualInterventionRequired Normal created loading-
incomplete open 20m
```

The object transitions to the ManualInterventionRequired High Level state. The Operator takes no further action to fix the object. The database loaded state remains loading-incomplete. Recall that you can set the .spec.ttspec.reexamine datum to cause the Operator to re-engage with the object. See Set reexamine Datum for details.

There was a total replica set failure. Because the TimesTen Scaleout object's .spec.ttspec.replicaSetRecovery datum had a value of Manual, the Operator set the object to the ManualInterventionRequired state. Review the information in Recovering from a Down Replica Set in the *Oracle TimesTen In-Memory Database Scaleout User's Guide* for details about how to fix this failure. Next, review Set reexamine Datum in this book to give control back to the Operator.

Suspend Management

Let's walk through an example that shows you how to suspend management of a TimesTenScaleout object.

In the example, there is a deployed TimesTenScaleout object that is functioning properly.

```
kubectl get tts samplescaleout

NAME OVERALL MGMT CREATE LOAD OPEN AGE
samplescaleout Normal Normal created loaded-complete open 3h33m
```

Note the High Level state is Normal, the management state is Normal, and the database state is created, loaded-complete, open.



- 1. Use the kubectl edit command to edit the TimesTenScaleout object, making the following changes:
 - If there is a line for .spec.ttspec.stopManaging in the file, then modify its value. It must be different than the current value.
 - If there is no line for .spec.ttspec.stopManaging in the file, then add a line and specify a value.

In this example, there is no .spec.ttspec.stopManaging line. This example adds the .spec.ttspec.stopManaging line and adds a value of Suspend.

```
kubectl edit timestenscaleout samplescaleout
# Please edit the object below. Lines beginning with a '#' will be
ignored,
# and an empty file will abort the edit. If an error occurs while
saving this file will be
# reopened with the relevant failures.
apiVersion: timesten.oracle.com/v1
kind: TimesTenScaleout
metadata:
 creationTimestamp: "2023-01-18T23:57:56Z"
 generation: 1
spec
 ttspec:
   dbConfigMap:
   - samplescaleout
   k: 2
    . . .
   nReplicaSets: 3
   nZookeeper: 3
    replicaSetRecovery: Restart
    stopManaging: Suspend
timestenscaleout.timesten.oracle.com/samplescaleout edited
```

2. Use the kubectl get command to observe the behavior...

The Operator sets the TimesTenScaleout object to the ManualInterventionRequired High Level state. The Operator takes no further action on the object. You can now perform manual operations on your grid and database. When you have completed such operations and are ready for the Operator to resume management, you can set the .spec.ttspec.rexamine datum for the object. For an example that shows you how to set a TimesTenScaleout object's .spec.ttspec.rexamine datum, see Set reexamine Datum.

Set reexamine Datum

If a TimesTenScaleout object is in the ManualInterventionRequired state, you can set/modify the object's .spec.ttspec.reexamine datum to instruct the TimesTen Operator to move the object into the Reexamine state. In the Reexamine state, the Operator examines the state of TimesTen and the database. If both are healthy, the Operator returns the object to the High Level Normal state. If not healthy, the object re-enters the ManualInterventionRequired state.

Let's walk through an example that shows you how to reexamine a TimesTenScaleout object.

1. Verify a TimesTenScaleout object is in the ManualInterventionRequired state.

- 2. Use the kubectl edit command to edit the TimesTenScaleout object, making the following changes:
 - If there is a line for .spec.ttspec.reexamine in the file, then modify its value. It must be different than the current value.
 - If there is no line for .spec.ttspec.reexamine in the file, then add a line and specify a value.

In this example, there is no .spec.ttspec.reexamine line. This example adds the .spec.ttspec.reexamine line and assigns a value of Reexamine1.

```
kubectl edit timestenscaleout samplescaleout
# Please edit the object below. Lines beginning with a '#' will be
ignored,
# and an empty file will abort the edit. If an error occurs while saving
this file will be
# reopened with the relevant failures.
apiVersion: timesten.oracle.com/v1
kind: TimesTenScaleout
metadata:
 creationTimestamp: "2023-01-18T23:57:56Z"
 generation: 1
. . .
spec
. . .
 ttspec:
    dbConfigMap:
    - samplescaleout
    . . .
    k: 2
    nReplicaSets: 3
```



```
nZookeeper: 3
    replicaSetRecovery: Restart
    reexamine: Reexamine1
...
timestenscaleout.timesten.oracle.com/samplescaleout edited
```

3. Use the kubectl get command to observe the behavior..

```
kubectl get tts samplescaleout

NAME OVERALL MGMT CREATE LOAD

OPEN AGE
samplescaleout Reexamine Normal created loaded-complete
open 3h52m
```

The object is in the Reexamine High Level state. The Operator examines the state of TimesTen and the database. If healthy, the Operator moves the object to the High Level Normal state. If not healthy, the object re-enters the ManualInterventionRequired State.

The object transitioned to the Normal High Level state, indicating the grid and database are functioning normally.



11

Expose TimesTen Metrics with the TimesTen Kubernetes Operator

The TimesTen Kubernetes Operator (TimesTen Operator) can expose TimesTen metrics to Prometheus or any other scraping mechanism. This chapter shows you how.

Topics:

- Overview of TimesTen Metrics
- Overview of the TimesTen Kubernetes Operator and the TimesTen Exporter
- About the Prometheus Operator
- About Exposing TimesTen Metrics
- · About Using http or https for TimesTen Metrics
- About Transport Layer Security (mutual TLS) Certificates for TimesTen Metrics
- About Creating PodMonitor Objects
- About the TimesTen Metrics Service
- About Choosing to Expose TimesTen Metrics
- Expose TimesTen Metrics Automatically

Overview of TimesTen Metrics

There are several TimesTen metrics that can be exposed to Prometheus or another scraping mechanism. These metrics are collected from a variety of sources, including TimesTen system tables and views and TimesTen built-in procedures and utilities. For more information about TimesTen metrics, see The Metrics Supported by the TimesTen exporter in the *Oracle TimesTen In-Memory Database Monitoring and Troubleshooting Guide*.

Prometheus is an open source monitoring and alerting toolkit. It collects and stores metrics from monitored targets by scraping the http (or https) metrics endpoint on these targets.

TimesTen exports TimesTen metrics to Prometheus by using the TimesTen ttExporter (TimesTen exporter) utility. The TimesTen exporter presents itself as an http or https server. When the TimesTen exporter receives an http or https request to the /metrics endpoint, it retrieves the TimesTen metrics from each database that it monitors and prepares a plain text http or https response with the metrics.

The TimesTen exporter converts TimesTen metrics into a form supported by Prometheus. This simple integration lets you monitor the health and operation of your TimesTen databases.

The TimesTen exporter is supported in TimesTen Classic and in TimesTen Scaleout. In TimesTen Scaleout, the TimesTen exporter is deployed on each data instance and on the management instance.

For information about Prometheus and the TimesTen exporter, see About Prometheus and About the TimesTen exporter in the *Oracle TimesTen In-Memory Database Monitoring and Troubleshooting Guide*.

Overview of the TimesTen Kubernetes Operator and the TimesTen Exporter

The TimesTen Operator supports the TimesTen exporter and lets you configure TimesTenClassic and TimesTenScaleout objects to use this TimesTen exporter. Once configured, the TimesTen Operator starts, stops, and manages the TimesTen exporter. As the TimesTen exporter collects metrics from the TimesTen databases running in your Kubernetes environment, the TimesTen Operator works to expose these metrics to Prometheus.

The TimesTen exporter runs in its own <code>exporter</code> container. This container exists in the same TimesTen Pods as the <code>tt</code> and the <code>daemonlog</code> containers. These TimesTen Pods run in your Kubernetes cluster.

The TimesTen Operator creates the Pods that are running TimesTen with the Kubernetes <code>shareProcessNamespace</code> Pod attribute. This attribute allows the TimesTen exporter that is running in the <code>exporter</code> container to access TimesTen that is running in the <code>tt</code> container, both of which are in the TimesTen Pod. For more information about the <code>shareProcessNamespace</code> attribute, see Share Process Namespace between Containers in a Pod in the Kubernetes documentation.

The TimesTen Operator configures the exporter container with the same TimesTen container image as the tt and the daemonlog containers. If the TimesTen exporter fails or exits, Kubernetes destroys the exporter container and creates another one to take its place. Kubernetes monitors and manages the exporter container. Because the lifecycle of individual containers in a Pod are independent, the TimesTen Operator ensures that the ttexporter command starts after TimesTen. The TimesTen Operator waits until the TimesTen agent creates the TimesTen instance and waits until the TimesTen main daemon is running in the tt container of the TimesTen Pod. The Operator then starts the TimesTen exporter in the exporter container of the same TimesTen Pod.

Once configured, the TimesTen exporter functions as an http or https server. It listens for incoming GET requests and responds to them by gathering a set of metrics from TimesTen. It then returns these metrics as the response to the GET request.

To facilitate the listening process, the TimesTen Operator creates a Kubernetes headless Service. This Service exposes the port on which the TimesTen exporter is listening to the remainder of the Kubernetes cluster. This lets a Prometheus server running in the cluster to fetch the TimesTen metrics from TimesTen and process them.

About the Prometheus Operator

In Overview of the TimesTen Kubernetes Operator and the TimesTen Exporter, we discussed how the TimesTen Operator and the TimesTen exporter work together to collect and export TimesTen metrics. Now let's look at how we can expose these metrics to Prometheus.





You can expose TimesTen metrics to any scraping target. Our documentation focuses on Prometheus.

There are several ways to configure Prometheus in Kubernetes. One of the most popular is the Prometheus Operator. The Prometheus Operator simplifies the deployment, monitoring, and management of Prometheus in Kubernetes.

Similar to the TimesTen Kubernetes Operator, the Prometheus Operator add several custom resource definitions (CRDs) to Kubernetes. Just as you deploy TimesTen by creating an object of type TimesTenClassic or type TimesTenScaleout, deploying Prometheus in Kubernetes involves creating an object of type *Prometheus*. The Prometheus Operator automatically detects the creation of such an object and responds by starting a server using the configuration included in the object.

Note:

It is beyond the scope of this book to detail how to create an object of type Prometheus. Refer to the Prometheus Operator documentation.

The Prometheus Operator also simplifies the configuration of Prometheus servers that it deploys. The Prometheus Operator can automatically edit the Prometheus server's configuration files to include data sources that should be scraped from the <code>/metrics</code> endpoint. This is done through the creation of Kubernetes objects of type <code>ServiceMonitor</code> and of type <code>PodMonitor</code>. (The ServiceMonitor object type is discussed in About Creating <code>ServiceMonitor</code> Objects.)

For details on these object types, see Prometheus Operator API Reference.

Let's look at a basic example of a PodMonitor object:

```
apiVersion: monitoring.coreos.com/v1
kind: PodMonitor
metadata:
   name: sample
spec:
   selector:
    matchLabels:
      app: sample
podMetricsEndpoints:
   - port: metrics
```

If you create such a PodMonitor object, the Prometheus Operator automatically responds by editing the Prometheus server's configuration files to cause the Prometheus server to scrape metrics from any Pod created with a label of app: sample. All Pods with the specified label automatically appear as scrape targets in Kubernetes. As Pods matching the selector are created or deleted, the Prometheus configuration is automatically kept in synchronization.

Using a Prometheus Operator offers a simplified approach to not only deploying, managing, and monitoring Prometheus, but also configuring Prometheus servers.

About Exposing TimesTen Metrics

The TimesTen Operator supports the TimesTen exporter, providing the ability for TimesTen databases deployed in your Kubernetes cluster to have TimesTen metrics exported. In addition, the Prometheus Operator configures and stands up Prometheus servers and creates and manages configuration files associated with these Prometheus servers. However, there are additional tasks that Prometheus requires to scrape TimesTen metrics.

For example:

- If you are using https to serve TimesTen metrics, an Oracle Wallet and certificates must be created.
- The certificates must be made available to Prometheus.
- Prometheus configuration files must be edited to cause Prometheus to scrape metrics from TimesTen. This is true whether TimesTen metrics are served using https or http.

Let's look at these tasks, examine our options for completing these tasks, and discuss how the TimesTen Operator can automatically perform these tasks for you.

Startung with TimesTen release 22.1, the TimesTen Operator automatically exports and exposes TimesTen metrics. In addition, if the Prometheus Operator is installed in your Kubernetes cluster, the TimesTen Operator provides Prometheus with all the information it needs to scrape TimesTen metrics from TimesTen databases.

Let's look at how the TimesTen Operator does this.

By default, the TimesTen Operator does the following:

- Exports and exposes TimesTen metrics from TimesTen databases deployed in your Kubernetes cluster.
- Uses https/Transport Layer Security (mutual TLS) to make these metrics available.
- If the Prometheus Operator is installed, creates the necessary objects to cause Prometheus to be automatically modified, which then causes Prometheus to scrape TimesTen metrics from the TimesTen databases.
- Exposes TimesTen metrics outside of the TimesTen Pods.

Although this default behavior is recommended, you have the option of changing the default behavior. Let's examine our options:

- https or http?: TimesTen metrics are available by https (default) or http.
- Create a Kubernetes PodMonitor object?: If the Prometheus Operator is installed
 in your Kubernetes cluster, the TimesTen Operator can create a PodMonitor
 object. This object contains the information needed by the Prometheus Operator to
 configure TimesTen databases as a scrape target. If the Prometheus Operator has
 been installed in your Kubernetes cluster, then by default the TimesTen Operator
 attempts to create a PodMonitor object.
- Expose TimesTen metrics outside of the TimesTen Pods?: The TimesTen exporter listens on and accepts GETs on the sampleobject.mynamespace.svc.cluster.local:8080/metrics endpoint (where

sampleobject is the name of a TimesTenClassic or TimesTenScaleout object and mynamespace is the name of your namespace). By default, the TimesTen Operator



deploys a Kubernetes Service that makes this endpoint available to other Pods in the Kubernetes cluster.



Having the TimesTen Operator automatically expose TimesTen metrics is not available in TimesTen release 18.1. This functionality is available in TimesTen release 22.1 and above.

Now let's look at how we can change this default behavior.

A TimesTenClassic or TimesTenScaleout object that is deployed in your namespace has specific datum associated with the object. These datum define the characteristics of a TimesTenClassic or TimesTenScaleout object, including the TimesTen databases associated with the object. You have the option of customizing a TimesTenClassic or TimesTenScaleout object by specifying values for particular datum in the object's YAML manifest file.

For exposing TimesTen metrics, the TimesTen Operator provides the .spec.ttspec.prometheus datum/clause and provides specific datum for use within this clause. This clause and its associated datum determine if and how the TimesTen Operator exports and exposes TimesTen metrics.

Let's look at the specific datum in the .spec.ttspec.prometheus clause in greater detail:

- .spec.ttspec.prometheus.publish: Determines if the TimesTen Operator provisions an exporter container for the TimesTen exporter. The default is true. We discuss this in About Choosing to Expose TimesTen Metrics.
- .spec.ttspec.prometheus.insecure: Determines if TimesTen metrics are served using https or http. If the value is false or not specified, TimesTen metrics are served using https. If the value is true, TimesTen metrics are served using http. For more information, see About Using http or https for TimesTen Metrics.
- spec.ttspec.prometheus.certSecret: If specified, contains a Kubernetes Secret that
 you have previously created. This Secret contains an Oracle Wallet and the necessary
 certificates for https. If not specified, the TimesTen Operator automatically creates an
 Oracle Wallet, the necessary certificates, and the Kubernetes Secrets.
 - We recommend that you do not specify .spec.ttspec.prometheus.certSecret and instead let the TimesTen Operator automate this process for you. For more information, see About Transport Layer Security (mutual TLS) Certificates for TimesTen Metrics. If you want to specify .spec.ttspec.prometheus.certSecret, see Create Your Own Oracle Wallet, Certificates, and Secrets for Exposing TimesTen Metrics.
- .spec.ttspec.prometheus.createPodMonitors: Determines if the TimesTen Operator should create a PodMonitor object. The default is true. We discuss this in About Creating PodMonitor Objects.

For additional information about .spec.ttspec.prometheus and its associated datum, see TimesTenClassicSpecSpecPrometheus for a TimesTenClassic object and TimesTenScaleoutSpecSpecPrometheus for a TimesTen Scaleout object.

About Using http or https for TimesTen Metrics

TimesTen metrics are available by http or https.



The default behavior is https and is discussed in About Transport Layer Security (mutual TLS) Certificates for TimesTen Metrics.

To cause the TimesTen Operator to use http for TimesTen metrics, specify the .spec.ttspec.prometheus.insecure datum in a TimesTenClassic or TimesTenScaleout object YAML manifest file.

Here is a code snippet of a TimesTenClassic object YAML manifest file showing you how to do this:

```
apiVersion: timesten.oracle.com/v1
kind: TimesTenClassic
metadata:
   name: usehttp
spec:
   ttspec:
...
   prometheus:
   insecure: true
   port: 7777
```

Note the following:

• The .spec.ttspec.insecure datum is specified in the .spec.ttspec.prometheus clause of the TimesTenClassic object. This causes the TimesTen Operator to configure the TimesTen exporter to serve TimesTen metrics using http.

The .spec.ttspec.port datum is specified. This is the port on which the TimesTen exporter listens. The causes the TimesTen Operator to set up the http server on TCP port 7777 in each TimesTen Pod.

About Transport Layer Security (mutual TLS) Certificates for TimesTen Metrics

When https is used, the TimesTen Operator automatically creates self-signed certificates. The TimesTen Operator also creates two Kubernetes Secrets to hold these certificates.

As an example, for a TimesTen object called sample, these Secrets are automatically created:

- sample-metrics: This Secret is automatically mounted in the TimesTen exporter containers of the TimesTen Pods. It contains an Oracle Wallet, which contains all certificates needed by the TimesTen exporter for https.
- sample-metrics-client: This Secret contains files that a Prometheus server (or other scraper) requires to scrape TimesTen metrics. This Secret contains the following three files:
 - ca.crt: The Certificate Authority certificate needed by the client to authenticate the self-signed certificate used by the TimesTen exporter.
 - client.crt: The client certificate that the TimesTen exporter uses to authenticate any clients that try to scrape metrics from it.



client.key: The private key that is associated with the client.crt client certificate.

Both Secrets are created with appropriate Kubernetes owner references. If you delete the associated TimesTenClassic or TimesTenScaleout object, these Secrets are automatically deleted.

Although not recommended, you have the option of creating your own certificates to serve TimesTen metrics using https. See Create Your Own Oracle Wallet, Certificates, and Secrets for Exposing TimesTen Metrics.



If TimesTen metrics are served by using either http or https whereby you create your own self-signed certificates, then the TimesTen Operator does not automatically create certificates, Oracle Wallets, or Kubernetes Secrets.

About Creating PodMonitor Objects

By default, if the Prometheus Operator has been installed in your Kubernetes cluster, the TimesTen Operator automatically creates PodMonitor objects when it provisions TimesTen in your namespace. Specifically, the TimesTen Operator automatically creates a PodMonitor object for each deployed TimesTenClassic or TimesTenScaleout object.

This automates all of the steps required to get TimesTen metrics into Prometheus. As TimesTen objects are created and deleted, the appropriate scrape targets are automatically provisioned and removed from the Prometheus configuration without any intervention by you.

Although recommended, this is an optional capability. If you choose not to use the Prometheus Operator, you can export TimesTen metrics into Prometheus yourself. The Prometheus Operator is not a prerequisite for using the TimesTen Operator.

If you have installed the Prometheus Operator and you do not want the TimesTen Operator to automatically create PodMonitor objects, set

the <code>.spec.ttspec.prometheus.createPodMonitors</code> datum of your TimesTenClassic or TimesTenScaleout object to false.

This capability is available whether a TimesTenClassic or TimesTenScaleout object is using http or https. It is also available with TimesTen Operator-created certificates and Secrets.

However, this capability is not available if you specify

the .spec.ttspec.prometheus.certSecret datum in a TimesTenClassic or TimesTenScaleout object definition. If you provide your own Kubernetes Secret that contains your own Oracle Wallet (and this Oracle Wallet contains the necessary certificates for using https), the TimesTen Operator cannot automatically produce a PodMonitor object with sufficient information to allow Prometheus to access TimesTen. In this case, you must create your own PodMonitor objects, or otherwise edit Prometheus configuration files to access TimesTen and have TimesTen metrics scraped.

If the TimesTen Operator attempts to create a PodMonitor object and is unable to do so, the TimesTen Operator generates an appropriate Event and continues on with provisioning and other normal operations. This can happen if the Prometheus Operator is not installed in your Kubernetes cluster or if the TimesTen Operator has not been granted appropriate role-based access control (RBAC) privileges in your Kubernetes cluster. For more information about RBAC privileges, see https://kubernetes.io/docs/reference/access-authn-authz/rbac/.



A PodMonitor object created by the TimesTen Operator has an owner reference to the appropriate TimesTenClassic or TimesTenScaleout object. This ensures that the PodMonitor object is automatically deleted if the TimesTenClassic or TimesTenScaleout object is deleted.



The .spec.ttspec.prometheus.createPodMonitors datum can be added to new TimesTenClassic and TimesTenScaleout objects, but cannot be added to existing TimesTenClassic and TimesTenScaleout objects (by using the kubectl upgrade or the kubectl patch commands or by other means).

For more information about PodMonitor objects, see https://prometheus-operator.dev/docs/operator/design/#podmonitor.

About the TimesTen Metrics Service

The TimesTen Operator automatically creates a Kubernetes Service for the TimesTen exporter. This Service exposes the port on which the TimesTen exporter listens to the Pods in the Kubernetes cluster. This Service exposes the port at

sample.mynamespace.svc.cluster.local:port/metrics where:

- sample is the name of a TimesTenClassic or TimesTenScaleout object.
- mynamespace is the name of your namespace.
- port is the port number on which the TimesTen exporter listens.

The default port is 8888.

You can change the port on which the TimesTen exporter listens by specifying the .spec.ttspec.prometheus.port datum in a TimesTenClassic or TimesTenScaleout object YAML manifest file.

Here is a code snippet of a TimesTenClassic object YAML manifest file showing the .spec.ttspec.prometheus.port datum.

```
apiVersion: timesten.oracle.com/v1
kind: TimesTenClassic
metadata:
   name: sample
spec:
   ttspec:
...
   prometheus:
       port: 7777
```

In this snippet, the TimesTen exporter listens on port 7777.

About Choosing to Expose TimesTen Metrics

By default, the TimesTen Operator exposes TimesTen metrics for TimesTenClassic and TimesTenScaleout objects.

You have the option of not exposing TimesTen metrics by setting

the .spec.ttspec.prometheus.publish datum to false in a TimesTenClassic or TimesTenScaleout object YAML manifest file. Doing so causes the TimesTen Operator to not provision an exporter container for the TimesTen exporter. If an exporter container is not provisioned, the TimesTen exporter is not configured, started, or managed. In this case, TimesTen metrics for the databases associated with this TimesTenClassic or TimesTenScaleout object are not exported or exposed.

Here is a code snippet showing how to set the value of

the .spec.ttspec.prometheus.publish datum to false in a TimesTenClassic object YAML manifest file:

```
apiVersion: timesten.oracle.com/v1
kind: TimesTenClassic
metadata:
   name: sample
spec:
   ttspec:
...
   prometheus:
    publish: false
```

In this example, the TimesTen Operator does not provision an exporter container for the sample TimesTenClassic object.

The default value for the .spec.ttspec.prometheus.publish datum is true. If you want the TimesTen Operator to provision an exporter container, you can choose the default or you can specify a value of true for the .spec.ttspec.prometheus.publish datum.

If you do not specify the publish datum, and any other datum is specified in the .spec.ttspec.prometheus clause, the default value for the publish datum is true.

If you do not specify the .spec.ttspec.prometheus clause and the TimesTen release is 22.1 or greater, the default value for the publish datum is dependent on the value of the EXPOSE METRICS TimesTen Operator environment variable:

- If EXPOSE_METRICS is "1" (or not specified), the TimesTen Operator treats the publish datum as true.
- If EXPOSE METRICS is "0", the TimesTen Operator treats the publish datum as false.

For more information about the .spec.ttspec.prometheus clause of a TimesTenClassic or TimesTenScaleout object, see TimesTenClassicSpecSpecPrometheus or TimesTenScaleoutSpecSpecPrometheus respectively.

For information about TimesTen Operator environment variables, see TimesTen Kubernetes Operator Environment Variables.

We recommend that you let the TimesTen Operator automatically export, expose, and publish TimesTen metrics. For a complete example, see Expose TimesTen Metrics Automatically.

Expose TimesTen Metrics Automatically

Let's walk through an example showing how the TimesTen Operator automatically exports and exposes TimesTen metrics. In this example, let's create a TimesTenClassic object and

observe how the TimesTen Operator automatically creates the objects needed to automatically export and expose TimesTen metrics to Prometheus.

Let's assume you have installed the Prometheus Operator in your Kubernetes cluster and there is a Prometheus server running in your namespace. Let's also assume you have started the TimesTen Operator following the steps in About Deploying the TimesTen Operator and there are no TimesTenClassic or TimesTenScaleout objects deployed in your namespace.

1. Create a TimesTenClassic object.

```
vi samplepublish.yaml

apiVersion: timesten.oracle.com/v1
kind: TimesTenClassic
metadata:
   name: samplepublish
spec:
   ttspec:
    storageClassName: oci
   storageSize: 250G
   image: container-registry.oracle.com/timesten/
timesten:22.1.1.19.0
   imagePullSecret: sekret
   prometheus:
        port: 6666
```

In this example, the port on which the TimesTen exporter listens is 6666.

Deploy the TimesTenClassic object.

```
kubectl create -f samplepublish.yaml
```

The output is the following:

```
timestenclassic.timesten.oracle.com/samplepublish created
```

Wait a few minutes, then confirm the TimesTenClassic object is in the Normal state.

```
kubectl get ttc samplepublish
```

The output is similar to the following:

```
NAME STATE ACTIVE AGE samplepublish Normal samplepublish-0 3m56s
```

 Confirm the TimesTen Operator provisioned an exporter container in each TimesTen Pod

```
kubectl get pods
```



The output is similar to the following:

NAME	READY	STATUS	RESTARTS	AGE
samplepublish-0 samplepublish-1	3/3 3/3	Running Running	0	7m33s 7m33s
• • •				

The TimesTen Operator automatically provisioned 3 containers in each TimesTen Pod. One of these containers is the exporter container, which is running the TimesTen exporter.

5. Confirm the TimesTen Operator automatically created the appropriate Kubernetes Secrets.

```
kubectl get secrets
```

The output is similar to the following:

NAME		
TYPE	DATA	AGE
•••		
samplepublish-metrics		
Opaque	1	15m
samplepublish-metrics-client		
Opaque	3	15m

By default, TimesTen metrics are served using https. As a result, the TimesTen Operator automatically created an Oracle Wallet, the certificates, and the Kubernetes Secrets needed for https. For more information, see About Transport Layer Security (mutual TLS) Certificates for TimesTen Metrics.

6. Confirm the appropriate files are in the samplepublish-metrics-client Kubernetes Secret.

kubectl describe secret samplepublish-metrics-client

The output is similar to the following:

Name: samplepublish-metrics-client
Namespace: mynamespace
Labels: <none>

Labels: <none>
Annotations: <none>

Type: Opaque

Data

ca.crt: 1461 bytes
client.crt: 1273 bytes
client.key: 1675 bytes



The TimesTen Operator automatically created the ca.crt, client.crt, and client.key files. The samplepublish-metrics-client Kubernetes Secret holds these files. See About Transport Layer Security (mutual TLS) Certificates for TimesTen Metrics.

7. Confirm the TimesTen Operator automatically created the samplepublish PodMonitor object.

kubectl describe podmonitor samplepublish

The output is similar to the following:

```
samplepublish
Name:
Namespace:
             mynamespace
Labels:
           app=samplepublish
             database.timesten.oracle.com=samplepublish
Annotations: <none>
API Version: monitoring.coreos.com/v1
           PodMonitor
Metadata:
 Creation Timestamp: 2023-09-25T15:36:08Z
 Generation:
                    1
 Owner References:
   API Version:
                         timesten.oracle.com/v1
   Block Owner Deletion: true
   Controller:
                        true
   Kind:
                        TimesTenClassic
   Name:
                        samplepublish
   UID:
                        d0f46bf7-b1d8-4499-876c-51410a469772
 Resource Version:
                        284346942
 UID:
                         5a61ec9e-df7d-4a98-be47-dce1e7c3d217
Spec:
 Namespace Selector:
 Pod Metrics Endpoints:
   Bearer Token Secret:
     Key:
   Interval: 15s
   Path:
            /metrics
   Port:
             exporter
   Scheme:
             https
   Tls Config:
     Ca:
       Secret:
         Key: ca.crt
         Name: samplepublish-metrics-client
     Cert:
       Secret:
         Key: client.crt
         Name: samplepublish-metrics-client
     Key Secret:
                   client.key
       Key:
       Name:
                   samplepublish-metrics-client
     Server Name:
```

 ${\tt sample publish.sample publish.myname space.svc.cluster.local}$

```
Selector:
   Match Labels:
     database.timesten.oracle.com: samplepublish
Events:
                                     <none>
```

Let's look at the important information in this PodMonitor object:

- There is an app=samplepublish label. If there are Pods with a label that matches app=samplepublish, Prometheus scrapes metrics from them. The TimesTen Pods contain the app=samplepublish label. Prometheus will therefore scrape metrics from these Pods. We will see this later.
- Prometheus scrapes metrics from the /metrics endpoint.
- Metrics are exposed using https.
- The TimesTen Operator placed the samplepublish-metrics and samplepublishmetrics-client Kubernetes Secrets in the PodMonitor object. These Secrets and their contents are used by the Prometheus Operator.

The Prometheus Operator edits the Prometheus server configuration files based on the information in this PodMonitor object.

8. Confirm the TimesTen Operator automatically created the appropriate Kubernetes Service.

```
kubectl describe service samplepublish
```

The output is similar to the following:

Name: samplepublish Namespace: mynamespace Labels: app=samplepublish

Annotations:

app=samplepublish Selector:

Type: ClusterIP IP Family Policy: SingleStack

IP Families: IPv4 IP: None None IPs:

Port: cs 6625/TCP TargetPort: Endpoints: 6625/TCP

10.244.0.120:6625,10.244.1.144:6625

Port: exporter 6666/TCP

TargetPort: 6666/TCP

Endpoints: 10.244.0.120:6666,10.244.1.144:6666

Session Affinity: None Events: <none>

The TimesTen exporter listens on port 6666.

9. Confirm there is a Prometheus server running in your namespace.

kubectl get pods



The output is similar to the following:

```
NAME READY STATUS RESTARTS
AGE
prometheus-sampleprometheusserver-0 2/2 Running 2
18d
...
```

The prometheus-sampleprometheusserver-0 Prometheus server is running in your namespace.

10. Confirm the Prometheus Operator edited the Prometheus server configuration file based on the information in the samplepublish PodMonitor object.

```
kubectl exec prometheus-sampleprometheusserver-0 -c prometheus --
cat /etc/prometheus/config out/prometheus.env.yaml
```

The output is similar to the following:

```
global:
 evaluation interval: 30s
 scrape interval: 30s
 external labels:
   prometheus: mynamespace/sampleprometheusserver
   prometheus replica: prometheus-sampleprometheusserver-0
scrape configs:
- job name: podMonitor/mynamespace/samplepublish/0
 honor labels: false
  kubernetes sd configs:
  - role: pod
   namespaces:
     names:
     - mynamespace
  scrape interval: 15s
 metrics path: /metrics
  scheme: https
  tls config:
    insecure skip verify: false
    ca file: /etc/prometheus/certs/secret mynamespace samplepublish-
metrics-client ca.crt
    cert file: /etc/prometheus/certs/
secret mynamespace samplepublish-metrics-client client.crt
   key file: /etc/prometheus/certs/
secret mynamespace samplepublish-metrics-client client.key
    server name:
samplepublish.samplepublish.mynamespace.svc.cluster.local
  relabel configs:
  - source labels:
    - job
   target label: tmp prometheus job name
  - action: drop
    source labels:
    - meta kubernetes pod phase
    regex: (Failed|Succeeded)
```



```
- action: keep
  source labels:
  - meta kubernetes pod label database timesten oracle com
  - meta kubernetes pod labelpresent database timesten oracle com
  regex: (samplepublish); true
- action: keep
  source labels:
  - meta kubernetes pod container port name
  regex: exporter
- source labels:
  - meta kubernetes namespace
  target label: namespace
- source labels:
  - meta kubernetes pod container name
  target label: container
- source labels:
  - meta kubernetes pod name
  target label: pod
- target label: job
  replacement: mynamespace/samplepublish
- target label: endpoint
  replacement: exporter
- source labels:

    address

  target label: __tmp_hash
 modulus: 1
  action: hashmod
- source labels:
  - tmp hash
 regex: 0
  action: keep
metric relabel configs: []
```

Prometheus has the information it needs to scrape TimesTen metrics.

- 11. Review some of the TimesTen metrics: In your browser, go to your Prometheus server.
 - a. In the Prometheus server search bar, type a TimesTen metric. For example, timesten_databases. Next, click Execute.

The output is similar to the following:

```
timesten_databases{container="exporter", endpoint="exporter",
instance="10.244.0.120:6666", instancename="instance1",
job="mynamespace/samplepublish",
namespace="mynamespace", pod="samplepublish-0"} 1

timesten_databases{container="exporter", endpoint="exporter",
instance="10.244.1.144:6666", instancename="instance1",
job="mynamespace/samplepublish",
namespace="mynamespace", pod="samplepublish-1"} 1
```

There is one TimesTen database in the samplepublish-0 Pod and one TimesTen database in the samplepublish-1 Pod as evidenced by the value of 1 for the metric.

b. In the Prometheus server search bar, type a second TimesTen metric. For example, **timesten_database_loaded**. Next, click **Execute**.

The output is similar to the following:

```
timesten_database_loaded{container="exporter",
dsn="samplepublish",
endpoint="exporter", instance="10.244.0.120:6666",
instancename="instance1",
job="mynamespace/samplepublish", namespace="mynamespace",
pod="samplepublish-0"} 1

timesten_database_loaded{container="exporter",
dsn="samplepublish",
endpoint="exporter", instance="10.244.1.144:6666",
instancename="instance1",
job="mynamespace/samplepublish", namespace="mynamespace",
pod="samplepublish-1"} 1
```

The samplepublish database in the samplepublish-0 Pod and the samplepublish database in the samplepublish-1 Pod are both loaded into memory as evidenced by the value of **1** for the metric.

Congratulations! You successfully created TimesTen databases whose metrics are collected by Prometheus.

12

Expose Metrics from the TimesTen Kubernetes Operator

The TimesTen Kubernetes Operator (TimesTen Operator) can expose metrics about its own functionality as well as the status of TimesTenClassic and TimesTenScaleout objects to Prometheus or any other scraping mechanism.

This chapter shows you how.

Topics:

- About Exposing Metrics from the TimesTen Kubernetes Operator
- About Using http or https
- About Transport Layer Security (mutual TLS) Certificates
- About Creating ServiceMonitor Objects
- About the TimesTen Kubernetes Operator's Metrics Service
- About TimesTen Operator Metrics
- Demonstrate How to Expose TimesTen Kubernetes Operator Metrics

About Exposing Metrics from the TimesTen Kubernetes Operator

By default, the TimesTen Kubernetes Operator exposes metrics about its own functionality as well as the status of TimesTenClassic and TimesTenScaleout objects it manages.

Let's look at how the TimesTen Operator does this. Let's examine the default behavior and let's determine how you can change the default behavior if you choose to do so.

By default, the TimesTen Operator does the following:

- Exports and exposes metrics about its own functionality and the overall status of the TimesTenClassic and TimesTenScaleout objects that it manages.
- Uses https/Transport Layer Security (mutual TLS) to make these metrics available.
- Automatically creates certificates, Oracle Wallets, and Kubernetes Secrets required for TLS.
- If the Prometheus Operator is installed, creates the appropriate objects to cause Prometheus to be automatically modified, which then causes Prometheus to scrape metrics from the TimesTen Operator.
- Exposes metrics outside of the TimesTen Operator Pods.

Although this default behavior is recommended, you have the option of changing the default behavior. Let's examine our options:

https or http?: TimesTen Operator metrics are available by https (default) or http.

- Create a Kubernetes ServiceMonitor object?: If the Prometheus Operator is
 installed in your Kubernetes cluster, the TimesTen Operator can create a
 Kubernetes ServiceMonitor object. This object contains the information needed by
 the Prometheus Operator to configure the TimesTen Operator as a scrape target.
 If the Prometheus Operator has been installed in your Kubernetes cluster, then by
 default the TimesTen Operator creates a ServiceMonitor object.
- Expose TimesTen Operator metrics outside of the TimesTen Operator Pods?: The TimesTen Operator listens on and accepts GETs on the timesten-operator.mynamespace.svc.cluster.local:8080/metrics endpoint (where mynamespace is the name of your namespace). By default, the TimesTen Operator deploys a Kubernetes Service that makes this endpoint available to other Pods in the Kubernetes cluster. You can choose not to create this Service.

Now, let's look at how we can change the default behavior.

The TimesTen Operator is deployed in your namespace as a Kubernetes Deployment. We provide an <code>operator.yaml</code> YAML manifest file that lets you customize this Deployment. The file is located in the <code>deploy</code> directory of the TimesTen Operator distribution. For more information, see About Deploying the TimesTen Operator.

The operator.yaml file contains various environment variables. Three of these variables govern if and how the TimesTen Operator exports and exposes metrics about its own operation and the status of the TimesTenClassic and TimesTenScaleout objects that it manages.

- METRICS_SCHEME: Determines if metrics should be made available by https or http.
 A setting of "https" (default) indicates https should be used. A setting of "http" indicates http should be used.
- CREATE_SERVICEMONITOR: Determines if the TimesTen Operator should create a
 Kubernetes ServiceMonitor object (discussed in a later section). A setting of "1"
 (default) indicates the TimesTen Operator should create a ServiceMonitor object. A
 setting of "0" indicates the TimesTen Operator should not create a ServiceMonitor
 object.
- EXPOSE_METRICS: Determines if metrics are exposed outside of the TimesTen
 Operator Pods. A setting of "1" (default) indicates metrics should be exposed
 outside of the TimesTen Operator Pods. A setting of "0" indicates metrics should
 not be exposed outside of the TimesTen Operator Pods.

Let's look at a snippet of an operator. yaml file that shows the existence of these environment variables and the default settings.



```
- name: EXPOSE_PROBES
  value: "1"
- name: CREATE_SERVICEMONITOR
  value: "1"
```

For reference information about these variables, see TimesTen Kubernetes Operator Environment Variables.



TimesTen Operator metrics are accurate when you have one TimesTen Operator defined in your TimesTen Operator Deployment (replicas:1 in your operator.yaml file).

About Using http or https

TimesTen Operator metrics are available by http or https.

The default behavior is https. To cause the TimesTen Operator to use http instead of https, set the METRICS_SCHEME environment variable to "http" in your operator.yaml YAML manifest file.



In TimesTen release 18.1, if you specify https for the METRICS_SCHEME environment variable, the TimesTen Operator acts as though you specified http.

About Transport Layer Security (mutual TLS) Certificates

When https is used, the TimesTen Operator automatically creates self-signed certificates. The TimesTen Operator also creates two Kubernetes Secrets to hold these certificates:

- timesten-operator-metrics: This Secret is used internally by the TimesTen Operator. It contains all the certificates needed by the TimesTen Kubernetes Operator for https/TLS. You do not need to use or examine this Secret.
- timesten-operator-metrics-client: This Secret contains files that a Prometheus server (or other scraper) requires to scrape metrics from the TimesTen Operator. This Secret contains the following three files:
 - ca.crt: The Certificate Authority certificate needed by the client to authenticate the self-signed certificate used by the TimesTen Operator.
 - client.crt: The client certificate that the TimesTen Operator uses to authenticate any clients that try to scrape metrics from it.
 - client.key: The private key that is associated with the client.crt client certificate.

Both Secrets are created with appropriate Kubernetes owner references. If you delete the TimesTen Operator deployment, these Secrets are automatically deleted.



When http is used, these certificates, Wallets, and Secrets are not created.

About Creating ServiceMonitor Objects

By default, if the Prometheus Operator is installed in your Kubernetes cluster, the TimesTen Operator attempts to create a Kubernetes ServiceMonitor object called timesten-operator. This object includes the information needed by Prometheus to configure the TimesTen Operator as a scrape target. If installed in your cluster, the Prometheus Operator responds to the creation of this object by editing the Prometheus configuration files to scrape metrics from the corresponding Service. For more information about ServiceMonitor objects, see https://prometheus-operator.dev/docs/operator/design/#servicemonitor.

A ServiceMonitor object created by the TimesTen Operator has an owner reference to the appropriate TimesTen Operator deployment. This ensures that the ServiceMonitor object is automatically deleted if the TimesTen Operator deployment is deleted.

The CREATE_SERVICEMONITOR environment variable determines if the TimesTen Operator creates a ServiceMonitor object. If you do not want the TimesTen Operator to create a ServiceMonitor object, then set CREATE_SERVICEMONITOR to "0" in your operator.yaml YAML manifest file..

About the TimesTen Kubernetes Operator's Metrics Service

The TimesTen Operator always makes metrics available. However, you can limit access to the TimesTen Operator's /metrics endpoint. By default, the TimesTen Operator's /metrics endpoint is available to other Pods in the Kubernetes cluster. Specifically, the TimesTen Operator automatically creates a Kubernetes Service called timesten-operator. This Service exposes the metrics port in the active TimesTen Operator Pod to the rest of the cluster at timesten-

operator.mynamespace.svc.cluster.local:8080/metrics (where mynamespace is the name of your namespace).

If you choose not to expose TimesTen Operator metrics outside of the TimesTen Operator's Pods, set the <code>EXPOSE_METRICS</code> environment variable to "0" in your operator.yaml YAML manifest file. In this case, the metrics port is not exposed by a Kubernetes Service. (You could still fetch metrics by using the <code>kubectl exec</code> command to run <code>curl</code> or a similar tool within the TimesTen Operator Pod itself.)

If you set the EXPOSE_METRICS environment variable to "0" and the CREATE_SERVICEMONITOR environment variable is set to "1" (default), the CREATE SERVICEMONITOR environment variable is treated as though it was set to "0".

In addition, if you set the <code>EXPOSE_METRICS</code> environment variable to "0", the value of the <code>METRICS</code> <code>SCHEME</code> environment variable is ignored and http is always used.



About TimesTen Operator Metrics

The TimesTen Operator publishes metrics about its own functionality as well as the status of TimesTenClassic and TimesTenScaleout objects that it manages.

These are the metrics that we have customized specifically for the TimesTen Operator:

- timesten classic state normal
- timesten classic state not normal
- timesten classic state
- timesten scaleout state normal
- timesten scaleout state not normal
- timesten_scaleout_state

For details about these metrics, see TimesTen Kubernetes Operator Metrics.

Demonstrate How to Expose TimesTen Kubernetes Operator Metrics

Let's walk through an example illustrating how the TimesTen Kubernetes Operator exposes metrics about its own functionality as well as the status of TimesTenClassic or TimesTenScaleout objects. Let's assume Prometheus is installed in your Kubernetes cluster and you have a Prometheus server running in your namespace.

Let's make the following decisions:

- https or http?: Let's choose https. The METRICS_SCHEME environment variable determines
 if metrics should be made available by https or http. A setting of "1" (default) indicates
 https.
- Create a ServiceMonitor object?: Let's have the TimesTen Operator create a
 ServiceMonitor object. This object contains the information needed by Prometheus to
 configure the TimesTen Operator as a scrape target. The CREATE_SERVICEMONITOR
 environment variable determines if the TimesTen Operator should create a
 ServiceMonitor object. A setting of "1" (default) indicates the TimesTen Operator should
 create the object.
- Expose TimesTen Operator metrics outside of the TimesTen Operator Pods?: Let's have the metrics exposed outside of the TimesTen Operator Pods so that Prometheus can scrape metrics from it. The <code>EXPOSE_METRICS</code> environment variable determines if metrics are exposed outside of the TimesTen Operator Pods. A setting of "1" (default) indicates metrics should be exposed. This means that the TimesTen Operator will create a Kubernetes Service (called timesten-operator) that allows the <code>/metrics</code> endpoint to be available to other Pods in the Kubernetes cluster.

Since we have chosen the defaults for the TimesTen Operator environment variables, you do not have to modify these variables in the <code>operator.yaml</code> YAML manifest file. For more information about the <code>operator.yaml</code> YAML manifest file, see Customize the TimesTen Operator.

1. Start the TimesTen Operator following the steps in About Deploying the TimesTen Operator.



2. (Optional) Review the TimesTen Operator deployment running in your namespace.

kubectl describe deployment timesten-operator

Output.

Name: timesten-operator Namespace: mynamespace CreationTimestamp: Sat, 23 Sep 2023 20:48:48 +0000 <none> Labels: deployment.kubernetes.io/revision: 1 Annotations: Selector: name=timesten-operator 1 desired | 1 updated | 1 total | 1 Replicas: available | 0 unavailable StrategyType: RollingUpdate MinReadySeconds: 0 RollingUpdateStrategy: 25% max unavailable, 25% max surge Pod Template: Labels: name=timesten-operator Service Account: timesten-operator Containers: timesten-operator: container-registry.oracle.com/timesten/ timesten:22.1.1.19.0 Ports: 8081/TCP, 8080/TCP Host Ports: 0/TCP, 0/TCP Command: /timesten/operator/operator/timesten-operator Liveness: http-get http://:probes/healthz delay=10s timeout=10s period=30s #success=1 #failure=3 Readiness: http-get http://:probes/healthz delay=10s timeout=10s period=10s #success=1 #failure=1 Environment: WATCH_NAMESPACE: (v1:metadata.namespace)
POD NAME: (v1:metadata.name) OPERATOR NAME: timesten-operator EXPOSE METRICS: 1 METRICS SCHEME: https EXPOSE PROBES: CREATE SERVICEMONITOR: 1 <none> Mounts: Volumes: <none> Conditions: Туре Status Reason -----____ Available True MinimumReplicasAvailable Progressing True NewReplicaSetAvailable OldReplicaSets: <none> NewReplicaSet: timesten-operator-7f77c749fd (1/1 replicas created) Events: Type Reason Age From Message ----Normal ScalingReplicaSet 73s deployment-controller Scaled up replica set timesten-operator-7f77c749fd to 1



The EXPOSE_METRICS and CREATE_SERVICEMONITOR TimesTen Operator environment variables are set to 1 (defaults) and the METRICS_SCHEME is set to https (default).

3. Confirm the TimesTen Operator created the appropriate Kubernetes Secrets.

```
kubectl get secrets
```

Output:

NAME
TYPE DATA AGE
...
timesten-operator-metrics
Opaque 1 11m
timesten-operator-metrics-client
Opaque 3 11m

The TimesTen Operator created the timesten-operator-metrics Kubernetes Secret. This Secret contains the certificates needed by the TimesTen Operator for https/TLS. This Secret is used internally by the TimesTen Operator.

The TimesTen Operator also created the timesten-operator-metrics-client Kubernetes Secret. This Secret contains the files that a Prometheus server needs to scrape metrics from the TimesTen Operator Pods.

4. Confirm the appropriate files are in the timesten-operator-metrics-client Kubernetes Secret.

kubectl describe secret timesten-operator-metrics-client

Output:

Name: timesten-operator-metrics-client

Namespace: mynamespace Labels: <none>

Annotations: <none>

Type: Opaque

Data

ca.crt: 1465 bytes
client.crt: 1277 bytes
client.key: 1675 bytes

The Secret contains the following files:

- ca.crt: The Certificate Authority file needed by the client to authenticate the self-signed certificate used by the TimesTen Operator.
- client.crt: The client certificate that the TimesTen Operator uses to authenticate clients that are attempting to scrape metrics from it.
- client.key: The private key that is associated with the client.crt file.



Confirm the TimesTen Operator created the timesten-operator ServiceMonitor object.

kubectl describe servicemonitor timesten-operator

Output:

Name: timesten-operator Namespace: mynamespace Labels: app=timesten-operator database.timesten.oracle.com=timesten-operator Annotations: deployment.kubernetes.io/revision: 1 API Version: monitoring.coreos.com/v1 Kind: ServiceMonitor Metadata: Creation Timestamp: 2023-09-23T20:49:33Z Generation: 1 Owner References: API Version: apps/v1 Block Owner Deletion: true Controller: Kind: Deployment Name: timesten-operator 3084af2d-90ca-49d1-874a-cde1174f50b5 UID: 282625424 Resource Version: UID: 6337b813-9d62-43b0-8594-60e387e7a30d Spec: Endpoints: Bearer Token Secret: Key: Interval: 15s /metrics Path: Port: metrics Scheme: https Tls Config: Secret: Key: ca.crt Name: timesten-operator-metrics-client Cert: Secret: Key: client.crt Name: timesten-operator-metrics-client Key Secret: client.key Key: Name: timesten-operator-metrics-client Server Name: timesten-operator.mynamespace.svc.cluster.local Namespace Selector: Selector: Match Labels: App: timesten-operator

Let's look at the important information in this ServiceMonitor object:

Events: <none>



- There is an app=timesten-operator label. If there are Pods with a label that matches
 app=timesten-operator, Prometheus scrapes metrics from them. The TimesTen
 Operator Pod contains the app=timesten-operator label. Prometheus will therefore
 scrape metrics from it. We will see this later.
- Prometheus scrapes metrics from the /metrics endpoint.
- Metrics are exposed using https.
- The TimesTen Operator placed the timesten-operator-metrics and timesten-operator-metrics-client Kubernetes Secrets in the ServiceMonitor object. These Secrets are used by the Prometheus Operator.

The Prometheus Operator edits the Prometheus server configuration files based on the information in this ServiceMonitor object.

6. Confirm the TimesTen Operator created the appropriate Kubernetes Service.

kubectl describe service timesten-operator

Output:

Name: timesten-operator
Namespace: mynamespace

Labels: app=timesten-operator

database.timesten.oracle.com=timesten-operator

Annotations: deployment.kubernetes.io/revision: 1

Selector: name=timesten-operator

Type: ClusterIP
IP Family Policy: SingleStack

IP Families: IPv4

IP: 10.96.169.59 IPs: 10.96.169.59

Port: metrics 8080/TCP

TargetPort: 8080/TCP

Endpoints: 10.244.8.180:8080 Port: probe 8081/TCP

TargetPort: 8081/TCP

Endpoints: 10.244.8.180:8081

Session Affinity: None
Events: <none>

7. Confirm there is a Prometheus server running in your namespace.

kubectl get pods

Output.

NAME READY STATUS RESTARTS AGE prometheus-sampleprometheusserver-0 2/2 Running 0 10d

The prometheus-sampleprometheusserver-0 Prometheus server is running in your namespace.

8. Confirm the Prometheus Operator edited the Prometheus server configuration file based on the information in the timesten-operator ServiceMonitor object.

```
kubectl exec prometheus-sampleprometheusserver-0 -c prometheus --
cat /etc/prometheus/config out/prometheus.env.yaml
```

Output.

```
global:
 evaluation interval: 30s
 scrape interval: 30s
 external labels:
   prometheus: mynamespace/sampleprometheusserver
   prometheus replica: prometheus-sampleprometheusserver-0
scrape configs:
- job name: serviceMonitor/mynamespace/timesten-operator/0
 honor labels: false
 kubernetes sd configs:
 - role: endpoints
   namespaces:
     names:
     - mynamespace
  scrape interval: 15s
 metrics path: /metrics
  scheme: https
  tls config:
   insecure skip_verify: false
    ca file: /etc/prometheus/certs/secret mynamespace timesten-
operator-metrics-client ca.crt
    cert file: /etc/prometheus/certs/secret mynamespace timesten-
operator-metrics-client client.crt
   key file: /etc/prometheus/certs/secret mynamespace timesten-
operator-metrics-client client.key
    server name: timesten-operator.mynamespace.svc.cluster.local
  relabel configs:
  - source labels:
    - job
   target label: tmp prometheus job name
  - action: keep
   source labels:
   - meta kubernetes service label app
   - meta kubernetes service labelpresent app
   regex: (timesten-operator); true
  - action: keep
    source labels:
    - meta kubernetes endpoint port name
   regex: metrics
  - source labels:
    - meta kubernetes endpoint address target kind
    - meta kubernetes endpoint address target name
    separator: ;
   regex: Node; (.*)
   replacement: ${1}
    target label: node
```



```
- source labels:
  - __meta_kubernetes_endpoint_address_target_kind
  - meta kubernetes endpoint address target name
  separator: ;
  regex: Pod; (.*)
  replacement: ${1}
  target label: pod
- source labels:
  - meta kubernetes_namespace
  target label: namespace
- source_labels:
  - meta kubernetes service name
  target label: service
- source labels:
  - meta kubernetes pod name
  target label: pod
- source labels:
  - meta kubernetes pod container name
  target label: container
- action: drop
  source labels:
  - meta kubernetes pod phase
 regex: (Failed|Succeeded)
- source labels:
  - meta kubernetes_service_name
  target label: job
  replacement: ${1}
- target label: endpoint
  replacement: metrics
- source labels:

    address

  target_label: __tmp_hash
 modulus: 1
  action: hashmod
- source labels:
  - tmp hash
 regex: 0
  action: keep
metric relabel configs: []
```

Prometheus has the information it needs to scrape TimesTen Operator metrics.

Review then deploy a TimesTenClassic object.

Review.

```
cat sample.yaml
```

Output.

```
apiVersion: timesten.oracle.com/v1
kind: TimesTenClassic
metadata:
   name: sample
spec:
```



```
ttspec:
    storageClassName: oci
    storageSize: 250G
    image: container-registry.oracle.com/timesten/
timesten:22.1.1.19.0
    imagePullSecret: sekret

Deploy:
kubectl create -f sample.yaml

Output:
```

 ${\tt timestenclassic.timesten.oracle.com/sample\ created}$

10. Wait a few minutes, then confirm the sample TimesTenClassic object is in the Normal state.

```
kubectl get ttc sample
```

Output:

```
NAME STATE ACTIVE AGE sample Normal sample-0 2m37s
```

- **11.** Review some of the TimesTen Operator metrics. In your browser, go to your Prometheus server.
 - **a.** In the Prometheus server search bar, type a TimesTen Operator metric. For example, **timesten_classic_state_normal**. Next, click **Execute**.

Output.

```
timesten_classic_state_normal{container="timesten-operator",
endpoint="metrics", instance="10.244.8.180:8080", job="timesten-
operator",
name="sample", namespace="mynamespace", pod="timesten-
operator-7f77c749fd-2lt5x",
service="timesten-operator"} 1
```

There is one TimesTenClassic object (sample) and it is in the Normal state.

b. In the Prometheus server search bar, type a second TimesTen Operator metric. For example, timesten_classic_state_not_normal. Next, click Execute.

Output.

```
timesten_classic_state_not_normal{container="timesten-operator",
endpoint="metrics", instance="10.244.8.180:8080", job="timesten-
operator",
name="sample", namespace="mynamespace", pod="timesten-
operator-7f77c749fd-2lt5x",
service="timesten-operator"} 0
```



There is one TimesTenClassic object (sample) and it is in either Normal or Initializing state. A value of 0 indicates it is not in any other state.

In the Prometheus server search bar, type a third TimesTen Operator metric. For example, timesten_classic_state. Next, click Execute.
 Output.

```
timesten_classic_state{container="timesten-operator",
endpoint="metrics",
instance="10.244.8.180:8080", job="timesten-operator", name="sample",
namespace="mynamespace", pod="timesten-operator-7f77c749fd-2lt5x",
service="timesten-operator", state="Initializing"} 0

timesten_classic_state{container="timesten-operator",
endpoint="metrics",
instance="10.244.8.180:8080", job="timesten-operator", name="sample",
namespace="mynamespace", pod="timesten-operator-7f77c749fd-2lt5x",
service="timesten-operator", state="Normal"} 1
```

The sample TimesTenClassic object is no longer in the Initializing state. It is now in the Normal state.

Congratulations! You successfully walked through an example demonstrating how TimesTen Operator metrics are exposed, scraped, and published.



Work with TimesTen Cache

The TimesTen Operator supports the use of TimesTen Cache with TimesTen Classic and TimesTen Scaleout in your Kubernetes environment.

About Using TimesTen Cache

The TimesTen Operator provides interfaces that you can use in TimesTen Classic and TimesTen Scaleout to configure cache groups.

These are the cache-related metadata files that you can provide:

• cacheUser: This file contains the TimesTen cache manager user. Its format is user/ ttpwd/orapwd, containing the username, TimesTen password, and Oracle password for the user. The Oracle user (called the cache administration user in Oracle Database) must exist prior to creating and deploying TimesTen Classic or TimesTen Scaleout. The Operator creates the TimesTen user in the the TimesTen database with the given name and password. The Operator also grants this user the appropriate privileges.

Here is an example:

cachemanageruser/ttmgrpwd/oramgrpwd

See cacheUser for more information.

cachegroups.sql: This file may contain CREATE CACHE GROUP statements as well as LOAD CACHE GROUP statements for the Operator to automatically run when the TimesTen database is created. The file also contains TimesTen built-in procedures to update statistics on the cache group tables (such as, ttOptEstimateStats and ttOptUpdateStats).

Here is an example:

```
CREATE READONLY CACHE GROUP readcache
AUTOREFRESH
INTERVAL 5 SECONDS
FROM oratt.readtab (
keyval NUMBER NOT NULL PRIMARY KEY,
str VARCHAR2(32)
);
LOAD CACHE GROUP readcache COMMIT EVERY 256 ROWS;
```

See cachegroups.sql for more information.

If you provide the <code>cacheUser</code> and <code>cachegroups.sql</code> files, the Operator uses them to provision TimesTen Cache when a new database is created.

The following metadata files are also relevant for TimesTen Cache:

- tnsnames.ora: This file is required. It defines Oracle Net Services that applications connect to. For TimesTen Cache, this file configures the connectivity between the TimesTen and the Oracle Database (from which data is being cached). In this context, TimesTen is the application that is the connection to the Oracle Database. See tnsnames.ora for details.
- sqlnet.ora: This file is optional. However, it may be necessary depending on your Oracle Database configuration. The file defines options for how client applications communicate with the Oracle Database. In this context, TimesTen is the application. The tnsnames.ora and sqlnet.ora files together define how an application communicates with the Oracle Database.

See sqlnet.ora for details.

• db.ini: This file is required. Its contents contain TimesTen connection attributes for your TimesTen database. The files are included in TimesTen's sys.odbc.ini file in TimesTen Classic or in the database definition file (dbDef) in TimesTen Scaelout. You must specify the OracleNetServiceName and the DatabaseCharacterSet connection attributes in this file. The DatabaseCharacterSet value must match the value of the Oracle database character set value.

See db.ini for details.

• schema.sql: This file may be required. In TimesTen Cache, one or more cache table users own the cache tables. If this cache table user is not the cache manager user, then you must specify the schema.sql file and in it include the schema user. You must also assign the appropriate privileges to this schema user. For example, if the oratt schema user was created in the Oracle Database, and this user is not the TimesTen cache manager user, you must create the TimesTen oratt user in this file.

The instance administrator uses the ttIsql utility to run this file immediately after the database is created. This file is run before the Operator configures TimesTen Cache, so ensure there are no cache definitions in this file.

See Create the Oracle Database Users for more information on the schema users in the Oracle Database. See schema.sql for details about the schema.sql file.

In TimesTen Classic, the contents of the <code>cachegroups.sql</code> file runs on the active database before it is duplicated to the standby. If there are autorefresh cache groups specified in the <code>cachegroups.sql</code> file, they are paused by the agent prior to duplicating the active database to the standby. After the duplication process completes, these autorefresh cache groups are re-enabled.

In TimesTen Scaleout, the contents of the cachegroups.sql file runs during database creation.

Once created and rolled out, the Operator does not monitor or manage TimesTen Cache. Specifically, the Operator does not monitor the health of the cache agents, nor does it take further action to start or stop them. In addition, the Operator does not verify that data is propagating correctly between the TimesTen database and the Oracle Database.

If you delete your TimesTenClassic or TimesTenScaleout object, the Operator automatically cleans up the Oracle Database metadata. If, however, you want to retain the Oracle Database metadata, specify the <code>cacheCleanUp</code> datum in your TimesTenClassic or TimesTen Scaleout object definition and set its value to <code>false</code>.



See cacheCleanup datum in TimesTenClassicSpecSpec and TimesTenScaleoutSpecSpec.

For complete examples, see the following:

- For TimesTen Classic deployments: See TimesTen Cache in TimesTen Classic Example.
- For TimesTen Scaleout deployments: See TimesTen Cache in TimesTen Scaleout Example.



14

Use Encryption for Data Transmission

TimesTen replication and TimesTen Client/Server support the use of Transport Layer Security (TLS) for communication between TimesTen instances.

This chapter details the process for configuring and using TLS in your Kubernetes environment. This enables encrypted data transmission between your replicated TimesTen databases and, if in a Client/Server environment, between your TimesTen client applications and your TimesTen Server (your TimesTen database).

Topics include:

- Create TLS Certificates for Replication and Client/Server
- Configure TLS for Replication
- Configure TLS for Client/Server

Create TLS Certificates for Replication and Client/Server

By default, TimesTen replication transmits data between your TimesTen databases unencrypted. In addition, in a TimesTen Client/Server environment, by default data is transmitted unencrypted between your application and your TimesTen database.

You can choose to enable encryption for replication and for Client/Server through the use of Transport Layer Security (TLS). TimesTen provides the ttCreateCerts utility to generate self-signed certificates for TLS. For more information on TLS certificates and wallets, see About Using Certificates with Client/Server in the *Oracle TimesTen In-Memory Database Security Guide*.



Java must be installed on your development host in order for you to use the ${\tt ttCertsCreate} \ \ {\tt utility}. \ \ {\tt The} \ \ {\tt utility} \ \ {\tt searches} \ \ {\tt for} \ \ {\tt Java} \ \ \ {\tt according} \ \ {\tt to} \ \ {\tt the} \ \ {\tt JRE_HOME}, \\ {\tt JAVA_HOME}, \ \ {\tt and} \ \ {\tt PATH} \ \ {\tt settings}.$

The ttCreateCerts utility is located in the /bin directory of a TimesTen instance. The utility creates three wallets: rootWallet, clientWallet, and serverWallet.

From your Linux development host, perform these steps to create the certificates.

Navigate to the bin directory of the installation and run the ttInstanceCreate utility
interactively to create an instance. Recall that the installation_dir directory was
created when you unpacked the TimesTen distribution. See "Unpack the TimesTen and
the TimesTen Operator Distributions" for information on unpacking the TimesTen
distribution.

You have to create a TimesTen instance as the ttCreateCerts utility is run from a TimesTen instance. For more information on the ttInstanceCreate utility, see ttInstanceCreate in the Oracle TimesTen In-Memory Database Reference.

Create the instance directory (/scratch/ttuser/instance_dir, in this example), then run the ttInstanceCreate utility, supplying the -name and the -location parameters. This example uses instance1 as the name of the instance and uses / scratch/ttuser/instance_dir as the location of the instance.

2. Set the <code>TIMESTEN_HOME</code> environment variable. This variable must be set before you run the <code>ttCertsCreate</code> utility. From the <code>bin</code> directory of the instance, source the <code>ttenv.csh</code> or the <code>ttenv.sh</code> script.

This example uses the bash Bourne-type shell. (Not all output is shown.)

```
% . /scratch/ttuser/instance_dir/instance1/bin/ttenv.sh
LD_LIBRARY_PATH set to
...
PATH set to
...
CLASSPATH set to
TIMESTEN_HOME set to /scratch/ttuser/instance_dir/instance1
```

3. Run the ttCreateCerts utility from the bin directory of the instance. This example uses the -verbose qualifier to show detailed output. See Using TLS for Client/ Server in TimesTen Classic in the *Oracle TimesTen In-Memory Database Security Guide* for more information on the ttCreateCerts utility.

The default wallet directory is <code>timesten_home/conf</code>, where <code>timesten_home</code> is the TimesTen instance home directory. This example uses this default wallet directory.



4. Review the wallet locations and the certificates (represented in **bold**). The cwallet.sso in the serverWallet directory is the file you will supply as the replicationWallet metadata file for replication and for the server in a Client/Server environment. The cwallet.sso in the clientWallet directory is the file you will use for the client in a Client/Server environment. See "About Configuration Metadata Details" for information on the replicationWallet and the clientWallet metadata files. Also see "Configure TLS for Replication" and "Configure TLS for Client/Server" for information on using these metadata files.

(These cwallet.sso files are also represented in **bold**).

```
% ls $TIMESTEN_HOME/conf
client1.cert root.cert server1.cert snmp.ini sys.ttconnect.ini
clientWallet rootWallet serverWallet sys.odbc.ini timesten.conf
% ls $TIMESTEN_HOME/conf/*Wallet*
/scratch/ttuser/instance_dir/instance1/conf/clientWallet:
cwallet.sso cwallet.sso.lck
/scratch/ttuser/instance_dir/instance1/conf/rootWallet:
cwallet.sso cwallet.sso.lck
/scratch/ttuser/instance_dir/instance1/conf/serverWallet:
cwallet.sso cwallet.sso.lck
```

You have successfully created the certificates that can be used for TLS for both replication and TimesTen Client/Server. You are now ready to configure and use TLS for replication, for Client/Server, or for both replication and Client/Server.

Configure TLS for Replication

You can configure TLS for replication to ensure secure network communication between your replicated TimesTen databases. See Transport Layer Security for TimesTen Replication in the *Oracle TimesTen In-Memory Database Security Guide* for detailed information.

These sections describe how to configure and use TLS for replication:

- Create Metadata Files and Kubernetes Facilities
- Create a TimesTenClassic Object
- Monitor Deployment of a TimesTenClassic Object
- Verify TLS Is Being Used for Replication

Create Metadata Files and Kubernetes Facilities

The /ttconfig/replicationWallet metadata file is required for TLS support for replication. (The /ttconfig directory is located in the containers of your TimesTen databases.) This file must contain the cwallet.sso file (the Oracle wallet) that was generated when you created the TLS certificates. Recall that this file was located in the /scratch/ttuser/instance_dir/instance1/conf/serverWallet directory. See Create TLS Certificates for Replication and Client/Server for information on creating these certificates. This wallet contains the credentials that are used by TimesTen replication for configuring TLS encryption between your active standby pair of TimesTen databases.



In addition to the /ttconfig/replicationWallet metadata file, you may use the other supported metadata files. See About Configuration Metadata Details for information on these supported metadata files.

You can include these metadata files in one or more Kubernetes facilities (for example, in a Kubernetes Secret, in a ConfigMap, or in an init container). This ensures the metadata files are populated in the /ttconfig directory of the TimesTen containers. Note that there is no requirement as to how to get the metadata files into this /ttconfig directory. See Populate the /ttconfig Directory for more information.

The example in the following sections illustrates how to include the replicationWallet metadata file in a Kubernetes Secret. It also creates the db.ini, the adminUser, and the schema.sql metadata files and includes these metadata files in a ConfigMap:

- Create a Kubernetes Secret
- Create a ConfigMap

Create a Kubernetes Secret

This section creates the repl-tls Kubernetes Secret. The repl-tls Secret will contain the replicationWallet metadata file.

On your Linux development host:

1. From the directory of your choice, create an empty subdirectory. This example creates the serverWallet subdirectory. (The serverWallet directory is used in the remainder of this example to denote this directory.)

```
% mkdir -p serverWallet
```

2. Copy the /scratch/ttuser/instance_dir/instance1/conf/serverWallet/ cwallet.sso file into the serverWallet directory that you just created. Recall that this file was generated when you used the ttCreateCerts utility to create the TLS certificates. See "Create TLS Certificates for Replication and Client/Server" for information.

```
% cp /scratch/ttuser/instance_dir/instance1/conf/serverWallet/cwallet.sso
serverWallet/cwallet.sso
```

3. Create the Kubernetes Secret.

In this example:

- The name of the Secret is repl-tls. Replace repl-tls with a name of your choosing. (repl-tls is represented in **bold**.)
- The name of the metadata file required for TLS replication is replicationWallet (represented in bold).
- The location of the wallet directory is serverWallet (in this example, represented in **bold**). If you use a different directory, replace serverWallet with the name of your directory.
- The name of the Oracle wallet is cwallet.sso (represented in bold).

Use the kubectl create command to create the Secret:

```
% kubectl create secret generic repl-tls
--from-file=replicationWallet=serverWallet/cwallet.sso
secret/repl-tls created
```



You have successfully created and deployed the repl-tls Kubernetes Secret. The replicationWallet/cwallet.sso file will later be available in the /ttconfig directory of the TimesTen containers. In addition, the file will be available in the /tt/home/timesten/replicationWallet directory of the TimesTen containers.

Create a ConfigMap

This section creates the repl-tls ConfigMap. This ConfigMap contains the db.ini, the adminUser, and the schema.sql metadata files.

These metadata files are not required for TLS, but are included as additional attributes for your TimesTen databases. See "Overview of Configuration Metadata and Kubernetes Facilities" for information on the metadata files and the ConfigMap facility.

On your Linux development host:

1. From the directory of your choice, create an empty subdirectory for the metadata files. This example creates the <code>cm_replTLS</code> subdirectory. (The <code>cm_replTLS</code> directory is used in the remainder of this example to denote this directory.)

```
% mkdir -p cm replTLS
```

2. Navigate to the ConfigMap directory.

```
% cd cm replTLS
```

3. Create the db.ini file in this ConfigMap directory (cm_replTLS, in this example). In this db.ini file, define the PermSize and DatabaseCharacterSet connection attributes.

```
vi db.ini
PermSize=200
DatabaseCharacterSet=AL32UTF8
```

4. Create the adminUser file in this ConfigMap directory (cm_replTLS, in this example). In this adminUser file, create the sampleuser user with the samplepw password.

```
vi adminUser
sampleuser/samplepw
```

5. Create the schema.sql file in this ConfigMap directory (cm_replTLS, in this example). In this schema.sql file, define the s sequence and the emp table for the sampleuser user. The Operator will automatically initialize your database with these object definitions.

```
vi schema.sql
create sequence sampleuser.s;
create table sampleuser.emp (
  id number not null primary key,
  name char(32)
);
```

6. Create the ConfigMap. The files in the cm_replTLS directory are included in the ConfigMap and, later, will be available in the TimesTen containers.

In this example:

- The name of the ConfigMap is repl-tls. Replace repl-tls with a name of your choosing. (repl-tls is represented in **bold** in this example.)
- This example uses cm_replTLS as the directory where the files that will be copied into the ConfigMap reside. If you use a different directory, replace cm_replTLS with the name of your directory. (cm_replTLS is represented in bold in this example.)

Use the kubectl create command to create the ConfigMap:

```
% kubectl create configmap repl-tls --from-file=cm_replTLS
configmap/repl-tls created
```

7. Use the kubectl describe command to verify the contents of the ConfigMap. (repl-tls, in this example.)

You have successfully created and deployed the repl-tls ConfigMap.

Create a TimesTenClassic Object

This section creates the TimesTenClassic object. See "Define and Create a TimesTenClassic Object" and "About the TimesTenClassic Object Type" for detailed information on the TimesTenClassic object.

Perform these steps:

1. Create an empty YAML file. You can choose any name, but you may want to use the same name you used for the name of the TimesTenClassic object. (In this example, repltls.) The YAML file contains the definitions for the TimesTenClassic object. See "TimesTenClassicSpecSpec" for information on the fields that you must specify in this YAML file as well as the fields that are optional.

In this example, the fields of particular interest for TLS replication are:

• dbSecret: This example uses one Kubernetes Secret (called repl-tls) for the replicationWallet metadata file.

- replicationCipherSuite: This field is required for TLS for replication. In this
 example, the value is SSL_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256. See Task 3:
 Configure TLS for Replication in the Oracle TimesTen In-Memory Database Security
 Guide and see the replicationCipherSuite entry in "Table 17-3" in this book for
 more information.
- replicationSSLMandatory: This field is optional. In this example, set replicationSSLMandatory equal to 1. See Task 3: Configure TLS for Replication in the *Oracle TimesTen In-Memory Database Security Guide* and see the replicationSSLMandatory entry in Table 17-3 in this book for more information.

In addition, this example includes:

- name: Replace repltls with the name of your TimesTenClassic object.
- storageClassName: Replace oci-by with the name of the storage class used to allocate PersistentVolumes to hold TimesTen.
- storageSize: Replace 250Gi with the amount of storage that should be requested for each Pod to hold TimesTen. Note: This example assumes a production environment and uses a value of 250Gi for storageSize. For demonstration purposes, a value of 50Gi is adequate. See the storageSize and the logStorageSize entries in "Table 17-3" for information.
- image: Replace container-registry.oracle.com/timesten/timesten:22.1.1.19.0 with the location and the name of image.
- imagePullSecret: Replace sekret with the image pull secret that Kubernetes should use to fetch the TimesTen image.
- dbConfigMap: This example uses one ConfigMap (called repl-tls) for the db.ini, the adminUser, and the schema.sql metadata files.

```
% vi repltls.yaml
apiVersion: timesten.oracle.com/v1
kind: TimesTenClassic
metadata:
 name: repltls
spec:
 ttspec:
   storageClassName: oci-bv
    storageSize: 250Gi
    image: container-registry.oracle.com/timesten/timesten:22.1.1.19.0
    imagePullSecret: sekret
   dbConfigMap:
    - repl-tls
   dbSecret:
    - repl-tls
    replicationCipherSuite: SSL ECDHE ECDSA WITH AES 128 GCM SHA256
    replicationSSLMandatory: 1
```

2. Use the kubectl create command to create the TimesTenClassic object from the contents of the YAML file (in this example, repltls.yaml). Doing so begins the process of deploying your active standby pair of TimesTen databases in the Kubernetes cluster.

```
% kubectl create -f repltls.yaml
timestenclassic.timesten.oracle.com/repltls created
```

You have successfully created the TimesTenClassic object in the Kubernetes cluster. The process of deploying your TimesTen databases begins, but is not yet complete.

Monitor Deployment of a TimesTenClassic Object

Use the kubectl get and the kubectl describe commands to monitor the progress of the active standby pair as it is provisioned.

 Use the kubectl get command and review the STATE field. Observe the value is Initializing. The active standby pair provisioning has begun, but is not yet complete.

```
% kubectl get ttc repltls
NAME STATE ACTIVE AGE
repltls Initializing None 50s
```

2. Use the kubectl get command again to see if value of the STATE field has changed. In this example, the value is Normal, indicating the active standby pair of databases are now provisioned and the process is complete.

```
% kubectl get ttc repltls
NAME STATE ACTIVE AGE
repltls Normal repltls-0 3m45s
```

Use the kubectl describe command to view the active standby pair provisioning in detail.

Note the following have been correctly set in the repltls TimesTenClassic object definition:

- The repl-tls Secret has been correctly referenced in the dbSecret field (represented in **bold**).
- The repl-tls Configmap has been correctly referenced in the dbConfigMap field (represented in **bold**).
- The replicationCipherSuite field has been correctly set to SSL_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256 (represented in bold).
- The replicationSSLMandatory field has been correctly set to 1 (represented in bold).

Note: Not all of the output is shown in this example.

```
% kubectl describe ttc repltls
Name: repltls
Namespace: mynamespace
           <none>
Labels:
Annotations: <none>
API Version: timesten.oracle.com/v1
            TimesTenClassic
Metadata:
 Creation Timestamp: 2023-04-30T18:51:43Z
 Generation:
 Resource Version: 75029797
 Self Link:
/apis/timesten.oracle.com/v1/namespaces/mynamespace/timestenclassics/repltls
 UID:
                    a2915ef3-0fe0-11eb-8b9a-aaa0151611fe
Spec:
 Ttspec:
   Db Config Map:
     repl-tls
   Db Secret:
     repl-tls
```



```
Image:
                               container-registry.oracle.com/timesten/
timesten:22.1.1.19.0
   Image Pull Policy:
                               Always
   Image Pull Secret:
                               sekret
   Replication Cipher Suite: SSL ECDHE ECDSA WITH AES 128 GCM SHA256
   Replication SSL Mandatory: 1
   Storage Class Name: oci-bv
   Storage Size:
                             250Gi
Events:
 Type Reason Age From Message
       Create 4m17s ttclassic Secret tta2915ef3-0fe0-11eb-8b9a-
aaa0151611fe created
       Create 4m17s ttclassic Service repltls created
Create 4m17s ttclassic StatefulSet repltls created
       StateChange 3m10s ttclassic Pod repltls-1 Agent Up
       StateChange 3m10s ttclassic Pod repltls-1 Release 22.1.1.19.0
       StateChange 3m10s ttclassic Pod repltls-1 Daemon Up
       StateChange 2m3s ttclassic Pod repltls-0 Agent Up
       StateChange 2m3s ttclassic Pod repltls-0 Release 22.1.1.19.0
       StateChange 2mls ttclassic Pod repltls-0 Daemon Up
       StateChange 68s ttclassic Pod repltls-0 Database Loaded
       StateChange 68s ttclassic Pod repltls-0 Database Updatable
       StateChange 68s ttclassic Pod repltls-0 CacheAgent Not Running
       StateChange 68s ttclassic Pod repltls-0 RepAgent Not Running
      StateChange 67s ttclassic Pod repltls-0 RepState IDLE
     StateChange 67s ttclassic Pod repltls-0 RepScheme None
     StateChange 66s ttclassic Pod repltls-0 RepAgent Running
      StateChange 66s ttclassic Pod repltls-0 RepScheme Exists
      StateChange 66s ttclassic Pod repltls-0 RepState ACTIVE
      StateChange 47s ttclassic Pod repltls-1 Database Loaded
       StateChange 47s ttclassic Pod repltls-1 Database Not Updatable
       StateChange 47s ttclassic Pod repltls-1 CacheAgent Not Running
       StateChange 47s ttclassic Pod repltls-1 RepAgent Not Running StateChange 47s ttclassic Pod repltls-1 RepScheme Exists StateChange 47s ttclassic Pod repltls-1 RepState IDLE
       StateChange 41s ttclassic Pod repltls-1 RepAgent Running
       StateChange 36s ttclassic Pod repltls-1 RepState STANDBY
       StateChange 36s ttclassic TimesTenClassic was Initializing, now Normal
```

Your active standby pair of TimesTen databases are successfully deployed (as indicated by Normal.) You are now ready to verify that TLS is being used for replication.

Verify TLS Is Being Used for Replication

To verify TLS is being used for replication, perform the following steps:

1. Review the active (repltls-0, in this example) pod and the standby pod (repltls-1, in this example).

2. Optional: Use the kubectl exec -it command to invoke the shell in the active Pod (repltls-0, in this example).

```
% kubectl exec -it repltls-0 -c tt -- /bin/bash
```

3. Optional: From the shell in the active pod, verify the cwallet.sso file is located in the /tt/home/timesten/replicationWallet directory.

```
% ls /tt/home/timesten/replicationWallet
cwallet.sso
```

4. Optional: From the shell in the active pod, verify that the TLS replication-specific values are correct in the timesten.conf configuration file. (This file is located in the /tt/home/timesten/instances/instance1/conf directory.)

In particular, note that:

- replication_wallet is correctly set to /tt/home/timesten/ replicationWallet (represented in bold).
- replication_cipher_suite is correctly set to
 SSL_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256 (represented in bold).
- replication ssl mandatory is correctly set to 1 (represented in bold).

See Task 3: Configure TLS for Replication in the *Oracle TimesTen In-Memory Database Security Guide* for more information on these timesten.conf attributes.

```
% cat /tt/home/timesten/instances/instance1/conf/timesten.conf
admin uid=3429
admin user=timesten
daemon port=6624
group name=timesten
hostname=repltls-0
instance guid=48AC5964-56A1-4C66-AB89-5646A2431EA3
instance name=instance1
replication cipher suite=SSL ECDHE ECDSA WITH AES 128 GCM SHA256
replication ssl mandatory=1
replication wallet=/tt/home/timesten/replicationWallet
server port=6625
show date=1
timesten release=22.1.1
tns admin=/ttconfig
verbose=1
```

5. From the shell in the active pod, run the ttRepAdmin utility with the -showstatus - detail options to verify the replication agent transmitters and receivers are using TLS (as indicated by SSL, represented in **bold**). See ttRepAdmin in the *Oracle TimesTen In-Memory Database Reference* for information on this utility.

Note: Not all output is shown in this example.

```
% ttRepAdmin -showstatus -detail repltls
Replication Agent Status as of: 2023-04-30 19:01:55

DSN : repltls
...
TRANSMITTER thread(s) (TRANSMITTER(M):139870727366400):
For : REPLTLS (track 0) (SSL)
    Start/Restart count : 1
    Current state : STATE_META_PEER_INFO

RECEIVER thread(s) (RECEIVER:139870719887104):
For : REPLTLS (track 0) (SSL)
    Start/Restart count : 1
```



```
Current state : STATE_RCVR_READ_NETWORK_LOOP
```

You have successfully verified that TLS for replication is being used.

Configure TLS for Client/Server

You can configure TLS for Client/Server to ensure secure network communication between TimesTen clients and servers. See Transport Layer Security for TimesTen Client/Server in the Oracle TimesTen In-Memory Database Security Guide for detailed information.

There are both server-side and client-side configuration requirements for using TLS for Client/Server. These requirements are detailed in these sections:

- · Configuration Requirements for the Server
- · Configuration Requirements for the Client

Configuration Requirements for the Server

These sections discuss the configuration requirements for the server. The sections also include an example of how to configure TLS for the server in your Kubernetes cluster.

- Overview of Metadata Files and Kubernetes Facilities
- · Create a Kubernetes Secret for the csWallet Metadata File
- Create a ConfigMap for the Server-Side Attributes
- Create a TimesTenClassic Object
- Monitor Deployment of the TimesTenClassic Object

Overview of Metadata Files and Kubernetes Facilities

The /ttconfig/csWallet metadata file is required for TLS support for Client/Server. (The /ttconfig directory is located in the containers of your TimesTen databases.) This file must contain the cwallet.sso file (the Oracle wallet) that was generated when you created the TLS certificates. This file is the Oracle wallet required for the server. Recall that this file was located in the /scratch/ttuser/instance_dir/instance1/conf/serverWallet directory. See Create TLS Certificates for Replication and Client/Server for information on creating these certificates. This wallet contains the credentials that are used for configuring TLS encryption between your TimesTen database and your Client/Server applications.

There are also server-side connection attributes that must be set. You can define these attributes in the <code>db.ini</code> metadata file. After the <code>db.ini</code> file is placed in the <code>/ttconfig</code> directory of the <code>TimesTen</code> containers, the Operator copies the contents of the <code>db.ini</code> file to the <code>timesten_home/conf/sys.odbc.ini</code> file located in the <code>TimesTen</code> containers. (Note that <code>timesten_home</code> is the <code>TimesTen</code> instance directory. This instance directory is <code>/tt/home/timesten/instances/instance1</code> in your <code>TimesTen</code> containers.)

These required server-side attributes are: Wallet, CipherSuites, and Encryption. See Create a ConfigMap for the Server-Side Attributes for information on these attributes. Also see Server Attributes for TLS in the Oracle TimesTen In-Memory Database Security Guide.

In addition to the csWallet and the db.ini metadata files, you may use other supported metadata files. See About Configuration Metadata Details for information on these supported metadata files.



You can include these metadata files in one or more Kubernetes facilities (for example, in a Kubernetes Secret, in a ConfigMap, or in an init container). This ensures the metadata files are populated in the /ttconfig directory of the TimesTen containers. Note that there is no requirement as to how to get the metadata files into this /ttconfig directory. See Populate the /ttconfig Directory.

The following example includes the csWallet metadata file in a Kubernetes Secret. It also creates the db.ini, the adminUser, and the schema.sql metadata files and includes these metadata files in a ConfigMap.

Create a Kubernetes Secret for the csWallet Metadata File

This section creates the cs-tls Kubernetes Secret. The cs-tls Secret will contain the csWallet metadata file.

On your Linux development host:

1. From the directory of your choice, create an empty subdirectory. This example creates the serverWallet subdirectory. (The serverWallet directory is used in the remainder of this example to denote this directory.)

```
% mkdir -p serverWallet
```

2. Copy the cwallet.sso file into the serverWallet directory that you just created. Recall that the cwallet.sso file was generated when you used the ttCreateCerts utility to create the TLS certificates. Also recall that this file was located in the / scratch/ttuser/instance_dir/instance1/conf/serverWallet directory. See "Create TLS Certificates for Replication and Client/Server" for information.

% cp /scratch/ttuser/instance_dir/instance1/conf/serverWallet/cwallet.sso
serverWallet/cwallet.sso

3. Create the Kubernetes Secret.

In this example:

- The name of the Secret is cs-tls. Replace cs-tls with a name of your choosing. (cs-tls is represented in **bold**.)
- The name of the metadata file required for TLS for Client/Server is csWallet (represented in **bold**).
- The location of the wallet directory is serverWallet (in this example, represented in **bold**). If you use a different directory, replace serverWallet with the name of your directory.
- The name of the Oracle wallet: cwallet.sso (represented in bold).

Use the kubectl create command to create the Secret:

```
% kubectl create secret generic cs-tls
--from-file=csWallet=serverWallet/cwallet.sso
secret/cs-tls created
```

You have successfully created and deployed the cs-tls Kubernetes Secret. The csWallet.sso file will later be available in the /ttconfig directory of the TimesTen containers. In addition, the file will be available in the /tt/home/timesten/csWallet directory of the TimesTen containers.



Create a ConfigMap for the Server-Side Attributes

This section creates the cs-tls ConfigMap. This ConfigMap contains the db.ini, the adminUser, and the schema.sql metadata files.

On your Linux development host:

1. From the directory of your choice, create an empty subdirectory for the metadata files. This example creates the <code>cm_csTLS</code> subdirectory. (The <code>cm_csTLS</code> directory is used in the remainder of this example to denote this directory.)

```
% mkdir -p cm csTLS
```

2. Navigate to the ConfigMap directory.

```
\% cd cm csTLS
```

3. Create the db.ini file in this ConfigMap directory (cm_csTLS, in this example). In this db.ini file, define the server-side attributes for TLS for Client/Server. These server-side attributes will later be included in the sys.odbc.ini file located in the timesten_home/conf directory in your TimesTen containers. (Note that timesten_home is the TimesTen instance directory. This instance directory is tt/home/timesten/instances/instance1 in your TimesTen containers.)

These are the required server-side attributes for TLS for Client/Server:

- wallet: This is the directory in your TimesTen containers that contains the server wallet. Specify /tt/home/timesten/csWallet.
- ciphersuites: This is the cipher suite setting. Valid values are
 SSL_ECDHE_ECDSA_WITH_AES_128_GCM_256 or
 SSL_ECDHE_ECDSA_WITH_AES_256_GCM_384, or both, comma separated and in order of
 preference. There is no default setting. For TLS to be used, the server and the client
 settings must include at least one common suite. This example specifies
 SSL_ECDHE_ECDSA_WITH_AES_128_GCM_256. See Server Attributes for TLS in the
 Oracle TimesTen In-Memory Database Security Guide for information on the cipher
 suite settings.
- encryption: This is the encryption setting for the server. This example specifies the required setting. See Server Attributes for TLS in the *Oracle TimesTen In-Memory Database Security Guide* for information on the valid encryption settings.

This example also specifies the PermSize and the DatabaseCharacterSet connection attributes.

```
vi db.ini

PermSize=200

DatabaseCharacterSet=AL32UTF8

wallet=/tt/home/timesten/csWallet
ciphersuites=SSL_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256
encryption=required
```

4. Create the adminUser file in this ConfigMap directory (cm_csTLS, in this example). In this adminUser file, create the sampleuser user with the samplepw password.



```
vi adminUser
sampleuser/samplepw
```

5. Create the schema.sql file in this ConfigMap directory (cm_csTLS, in this example). In this schema.sql file, define the s sequence and the emp table for the sampleuser user. The Operator will automatically initialize your database with these object definitions.

```
vi schema.sql
create sequence sampleuser.s;
create table sampleuser.emp (
  id number not null primary key,
  name char(32)
);
```

6. Create the ConfigMap. The files in the <code>cm_csTLS</code> directory are included in the ConfigMap and, later, will be available in the TimesTen containers.

In this example:

- The name of the ConfigMap is cs-tls. Replace cs-tls with a name of your choosing. (cs-tls is represented in **bold** in this example.)
- This example uses cm_csTLS as the directory where the files that will be copied into the ConfigMap reside. If you use a different directory, replace cm_csTLS with the name of your directory. (cm_csTLS is represented in **bold** in this example.)

Use the kubectl create command to create the ConfigMap:

```
% kubectl create configmap cs-tls --from-file=cm_csTLS
configmap/cs-tls created
```

7. Use the kubectl describe command to verify the contents of the ConfigMap. (cstls, in this example.)

```
% kubectl describe configmap cs-tls
       cs-tls
Name:
Namespace: mynamespace Labels: <none>
Annotations: <none>
Data
db.ini:
PermSize=200
DatabaseCharacterSet=AL32UTF8
wallet=/tt/home/timesten/csWallet
ciphersuites=SSL ECDHE ECDSA WITH AES 128 GCM SHA256
encryption=required
schema.sql:
create sequence sampleuser.s;
create table sampleuser.emp (id number not null primary key, name char (32));
adminUser:
sampleuser/samplepw
```

```
Events: <none>
```

You have successfully created and deployed the cs-tls ConfigMap.

Create a TimesTenClassic Object

This section creates the TimesTenClassic object. See Define and Create a TimesTenClassic Object and About the TimesTenClassic Object Type for detailed information on the TimesTenClassic object.

Perform these steps:

 Create an empty YAML file. You can choose any name, but you may want to use the same name you used for the name of the TimesTenClassic object. (In this example, cstls.) The YAML file contains the definitions for the TimesTenClassic object. See <u>TimesTenClassicSpecSpec</u> for information on the fields that you must specify in this YAML file as well as the fields that are optional.

In this example, the fields of particular interest for TLS Client/Server are:

- dbSecret: This example uses one Kubernetes Secret (called cs-tls) for the csWallet metadata file.
- dbConfigMap: This example uses one ConfigMap (called cs-tls). The db.ini file is contained in the cs-tls ConfigMap. Recall that the db.ini file contains the server-side attributes for TLS for Client/Server.

In addition, this example includes:

- name: Replace cstls with the name of your TimesTenClassic object.
- storageClassName: Replace oci-by with the name of the storage class used to allocate PersistentVolumes to hold TimesTen.
- storageSize: Replace 250Gi with the amount of storage that should be requested for each Pod to hold TimesTen. Note: This example assumes a production environment and uses a value of 250Gi for storageSize. For demonstration purposes, a value of 50Gi is adequate. See the storageSize and the logStorageSize entries in "Table 17-3" for information.
- image: Replace container-registry.oracle.com/timesten/timesten:22.1.1.19.0 with the location and name of your image.
- imagePullSecret: Replace sekret with the image pull secret that Kubernetes should use to fetch the TimesTen image.

```
% vi cstls.yaml
apiVersion: timesten.oracle.com/v1
kind: TimesTenClassic
metadata:
   name: cstls
spec:
   ttspec:
    storageClassName: oci-bv
   storageSize: 250Gi
   image: container-registry.oracle.com/timesten/timesten:22.1.1.19.0
   imagePullSecret: sekret
   dbConfigMap:
   - cs-tls
```



```
dbSecret:
    cs-tls
```

Use the kubectl create command to create the TimesTenClassic object from the
contents of the YAML file (in this example, cstls.yaml). Doing so begins the
process of deploying your active standby pair of TimesTen databases in the
Kubernetes cluster.

```
% kubectl create -f cstls.yaml
timestenclassic.timesten.oracle.com/cstls created
```

You have successfully created the TimesTenClassic object in the Kubernetes cluster. The process of deploying your TimesTen databases begins, but is not yet complete.

Monitor Deployment of the TimesTenClassic Object

Use the kubectl get and the kubectl describe commands to monitor the progress of the active standby pair as it is provisioned.

 Use the kubectl get command and review the STATE field. Observe the value is Initializing. The active standby pair provisioning has begun, but is not yet complete.

```
% kubectl get ttc cstls
NAME STATE ACTIVE AGE
cstls Initializing None 15s
```

2. Use the kubectl get command again to see if value of the STATE field has changed. In this example, the value is Normal, indicating the active standby pair of databases are now provisioned and the process is complete.

```
% kubectl get ttc cstls
NAME STATE ACTIVE AGE
cstls Normal cstls-0 3m30s
```

3. Use the kubectl describe command to view the active standby pair provisioning in detail.

Note the following have been correctly set in the cstls TimesTenClassic object definition:

- The cs-tls Secret has been correctly referenced in the dbSecret field (represented in **bold**).
- The cs-tls Configmap has been correctly referenced in the dbConfigMap field (represented in bold).

Note: Note all of the output is shown in this example.



```
UID:
                     150128b3-10ac-11eb-b019-d681454a288b
Spec:
  Ttspec:
   Db Config Map:
     cs-tls
   Db Secret:
     cs-tls
   Image:
                        container-registry.oracle.com/timesten/
timesten:22.1.1.19.0
   Image Pull Policy: Always
   Image Pull Secret:
                       sekret
   Storage Class Name: oci
   Storage Size:
                        250Gi
Events:
                                    Message
 Type Reason Age From
                  4m21s ttclassic Service cstls created
       Create
       Create
Create
                  4m21s ttclassic StatefulSet cstls created
                   4m21s ttclassic Secret tt150128b3-10ac-11eb-b019-
d681454a288b created
     StateChange 3m5s ttclassic Pod cstls-1 Daemon Up
       StateChange 3m5s ttclassic Pod cstls-0 Agent Up
     StateChange 3m5s ttclassic Pod cstls-0 Release 22.1.1.19.0
     StateChange 3m5s ttclassic Pod cstls-1 Agent Up
      StateChange 3m5s ttclassic Pod cstls-1 Release 22.1.1.19.0
     StateChange 3m5s ttclassic Pod cstls-0 Daemon Up
     StateChange 116s ttclassic Pod cstls-0 Database Loaded
      StateChange 116s ttclassic Pod cstls-0 Database Updatable
      StateChange 116s ttclassic Pod cstls-0 CacheAgent Not Running
       StateChange 116s ttclassic Pod cstls-0 RepAgent Not Running
       StateChange 116s ttclassic Pod cstls-0 RepState IDLE
       StateChange 116s ttclassic Pod cstls-0 RepScheme None
       StateChange 115s ttclassic Pod cstls-0 RepAgent Running
       StateChange 115s ttclassic Pod cstls-0 RepScheme Exists StateChange 115s ttclassic Pod cstls-0 RepState ACTIVE StateChange 96s ttclassic Pod cstls-1 Database Loaded
       StateChange 96s ttclassic Pod cstls-1 Database Not Updatable
       StateChange 96s ttclassic Pod cstls-1 CacheAgent Not Running
       StateChange 96s ttclassic Pod cstls-1 RepAgent Not Running
       StateChange 96s ttclassic Pod cstls-1 RepScheme Exists
       StateChange 96s ttclassic Pod cstls-1 RepState IDLE
       StateChange 90s ttclassic Pod cstls-1 RepAgent Running
       StateChange 84s ttclassic Pod cstls-1 RepState STANDBY
       StateChange 84s ttclassic TimesTenClassic was Initializing, now Normal
```

Your active standby pair of TimesTen databases are successfully deployed (as indicated by Normal.)

Configuration Requirements for the Client

These sections cover the client requirements for TLS.

- Copy a Client Wallet
- Configure Client-Side Attributes

Copy a Client Wallet

When you used the ttCreateCerts utility to create TLS certificates, the cwallet.sso wallet file located in the /scratch/ttuser/instance_dir/instance1/conf/clientWallet directory was generated. This file must be copied to the application container that is running your TimesTen client instance. See "Create TLS Certificates for Replication and Client/Server" for information on creating the TLS certificates.

This example uses the kubectl cp command to copy the /scratch/ttuser/instance_dir/instance1/conf/clientWallet/cwallet.sso file from your Linux development host to the application container running your TimesTen client instance.

1. Use the kubectl exec -it command to invoke the shell in the application container that contains your TimesTen client instance. (cstls-0, in this example).

```
% kubectl exec -it cstls-0 -c tt -- /bin/bash
```

2. From the shell just invoked, and from the directory of your choice, create an empty subdirectory. This example creates the clientWallet subdirectory.

```
% mkdir -p clientWallet
```

3. From your Linux development host, use the <code>kubectl cp command to copy</code> the <code>cwallet.sso</code> file from the <code>/scratch/ttuser/instance_dir/instancel/conf/clientWallet directory on your Linux development host to the <code>clientWallet</code> directory that you just created. (This directory is located in the application container that is running your TimesTen client instance.) Recall that the <code>cwallet.sso</code> file was generated when you used the <code>ttCreateCerts</code> utility to create the TLS certificates. See Create TLS Certificates for Replication and Client/Server for information.</code>

```
% kubectl cp /scratch/ttuser/instance_dir/instance1/conf/clientWallet/
cwallet.sso cstls-0:clientWallet/cwallet.sso -c tt
```

4. From your shell, verify the cwallet.sso file is located in the clientWallet directory.

```
% ls clientWallet
cwallet.sso
```

You have successfully copied the <code>cwallet.sso</code> client wallet file to the application container that is running your TimesTen client instance.

Configure Client-Side Attributes

You must set client-side attributes for TLS for Client/Server. The attributes can be set in the client DSN definition in <code>timesten_home/conf/sys.odbc.ini</code> or in an appropriate Client/Server connection string. See About Using Client/Server Drivers for additional information.

These are the required client-side attributes for TLS for Client/Server:

wallet: This is the directory that contains the cwallet.sso client wallet file. This
directory is located in your application container that is running the TimesTen client
instance. There is no default directory. In this example, recall that the
clientWallet directory was created to denote this directory. (See Copy a Client
Wallet for information.) For purposes of this example, the full path to the



clientWallet directory is /tt/home/timesten/clientWallet. Therefore, in this example, /tt/home/timesten/clientWallet is used to denote this directory.

- ciphersuites: This is the cipher suite setting. Valid values are
 SSL_ECDHE_ECDSA_WITH_AES_128_GCM_256 or SSL_ECDHE_ECDSA_WITH_AES_256_GCM_384,
 or both, comma separated and in order of preference. There is no default setting. For
 TLS to be used, the server and the client settings must include at least one common
 suite. This example specifies SSL_ECDHE_ECDSA_WITH_AES_128_GCM_256. See
 Configuration for TLS for Client/Server in the Oracle TimesTen In-Memory Database
 Security Guide for information on the cipher suite settings.
- encryption: This is the encryption setting for the client. This example specifies the required setting. See Configuration for TLS for Client/Server in the Oracle TimesTen In-Memory Database Security Guide for information on the valid encryption settings.

This example uses a connection string to connect to the <code>cstsl</code> database as the <code>sampleuser</code> user. The <code>sampleuser</code> user was created by the Operator and already exists in the <code>cstsl</code> database. The example then uses the <code>sqlgetconnectattr</code> command from <code>ttlsqlcs</code> on the client to verify TLS is configured correctly on the Server and on the Client and TLS is being used.

1. Connect to the database.

```
% ttIsqlcs -connstr "TTC SERVER1=cstls-0.cstls.mynamespace.svc.cluster.local;
TTC SERVER2=cstls-1.cstls.mynamespace.svc.cluster.local;
TTC SERVER DSN=cstls; UID=sampleuser; PWD=samplepw;
WALLET=tt/home/timesten/clientWallet;
CIPHERSUITES=SSL ECDHE ECDSA WITH AES 128 GCM SHA256;
ENCRYPTION=required";
Copyright (c) 1996, 2023, Oracle and/or its affiliates. All rights reserved.
Type ? or "help" for help, type "exit" to quit ttIsql.
connect "TTC SERVER1=cstls-0.cstls.mynamespace.svc.cluster.local;
TTC SERVER2=cstls-1.cstls.mynamespace.svc.cluster.local;
TTC SERVER DSN=cstls;UID=sampleuser;PWD=******;
WALLET=tt/home/timesten/clientWallet;
CipherSuites=SSL ECDHE ECDSA WITH AES 128 GCM SHA256;
ENCRYPTION=REQUIRED;";
Connection successful:
DSN=;TTC SERVER=cstls-0.cstls.mynamespace.svc.cluster.local;
TTC SERVER DSN=cstls;UID=sampleuser;
DATASTORE=/tt/home/timesten/datastore/cstls; DATABASECHARACTERSET=AL32UTF8;
CONNECTIONCHARACTERSET=AL32UTF8; AUTOCREATE=0; PERMSIZE=200;
DDLREPLICATIONLEVEL=3; FORCEDISCONNECTENABLED=1; (SERVER) ENCRYPTION=Required;
(SERVER) WALLET=file:/tt/home/timesten/csWallet; (client) Encryption=Required;
(client) Wallet=/tt/home/timesten/clientWallet;
(client) CipherSuites=SSL ECDHE ECDSA WITH AES 128 GCM SHA256;
(Default setting AutoCommit=1)
```

2. Use the sqlgetconnectattr command in ttIsqlCS to verify TLS is being used. A return value of 1 indicates TLS is being used.

```
Command> sqlgetconnectattr tt_tls_session;
TT TLS SESSION = 1 (SQL TRUE)
```

You have successfully connected to the database and verified that TLS for Client/Server is being used.

15

Handle Failover and Recovery in TimesTen Classic

This chapter is specific to active standby pair of Classic TimesTen databases. It illustrates how the TimesTen Operator recovers from failure.

- About Handling Failover and Recovery
- Illustrate the Failover and Recovery Process

About Handling Failover and Recovery

The Operator automatically detects failures of the active TimesTen database and the standby TimesTen database and works to fix any failures. When the Operator detects a failure of the active database, it promotes the standby TimesTen database to be the active. Client/server applications that are using the database are automatically reconnected to the new active database. Transactions in flight are rolled back. Prepared statements need to be re-prepared by the applications. The Operator will configure a new standby database.

Illustrate the Failover and Recovery Process

This example simulates a failure of the active TimesTen database. This is for demonstration purposes only. Do not do this in a production environment.

1. Use the kubectl delete pod command to delete the active database (sample-0 in this case)

```
% kubectl delete pod sample-0
```

2. Use the kubectl describe command to observe how the Operator recovers from the failure. The Operator promotes the standby database (sample-1) to be active. Any applications that were connected to the sample-0 database are automatically reconnected to the sample-1 database by TimesTen. After a brief outage, the applications can continue to use the database. See "About Monitoring the Health of an Active Standby Pair of Databases" for information on the health and states of the active standby pair.

Note: In this example, the text for the Message column displays on two lines for three state changes. However, the actual output displays on one line for each of these three state changes.

```
- StateChange 115s ttclassic Pod sample-1 RepState ACTIVE
- StateChange 110s ttclassic Pod sample-0 High Level State Unknown
- StateChange 63s ttclassic Pod sample-0 Pod Phase Running
- StateChange 63s ttclassic Pod sample-0 Agent Up
- StateChange 63s ttclassic Pod sample-0 Instance Exists
- StateChange 63s ttclassic Pod sample-0 Daemon Up
- StateChange 63s ttclassic Pod sample-0 Database None
- StateChange 42s ttclassic Pod sample-0 Database Loaded
- StateChange 42s ttclassic Pod sample-0 Database Updatable: No
- StateChange 42s ttclassic Pod sample-0 RepAgent Running
- StateChange 42s ttclassic Pod sample-0 CacheAgent Not Running
- StateChange 42s ttclassic Pod sample-0 RepScheme Exists
- StateChange 42s ttclassic Pod sample-0 RepState IDLE
- StateChange 36s ttclassic Pod sample-0 RepState STANDBY
- StateChange 36s ttclassic TimesTenClassic sample:was
```

Kubernetes has automatically respawned a new sample-0 Pod to replace the Pod you deleted. The Operator configured TimesTen within that Pod, bringing the database in the Pod up as the new standby database. The replicated pair of databases are once again functioning normally.



Perform Upgrades

If you deployed the TimesTen Operator and TimesTenClassic objects using Helm, you must upgrade using Helm. For information about using Helm, see Use Helm to Deploy the TimesTen Kubernetes Operator and TimesTenClassic Objects.

This chapter shows you how to upgrade the TimesTen Operator. It also shows you how to upgrade TimesTen Classic to a new patch or patchset. The process also applies to downgrades.

For information on TimesTen releases and patches, see Overview of release numbers in the Oracle TimesTen In-Memory Database Installation, Migration, and Upgrade Guide.

Topics include:

- About New TimesTen Container Images
- Upgrade the Operator
- About Upgrading TimesTen Classic
- Perform an Automated Upgrade
- Perform a Manual Upgrade
- Verify the Active Standby Pair of Databases Are Upgraded
- About Upgrading Direct Mode Applications
- About Failures During an Upgrade

About New TimesTen Container Images

The TimesTen Kubernetes Operator lets you upgrade the TimesTen Operator and TimesTen Classic to a new patch or patch set release. There are separate procedures in place for upgrading the Operator and for upgrading TimesTen Classic.

Both the Operator as well as each TimesTenClassic and TimesTenScaleout object require a TimesTen container image. You tell the Operator the location of the image registry and the name of the container image when you initially deploy the Operator and a TimesTenClassic or a TimesTenScaleout object.

When you upgrade the Operator to a new patch or patch set, you need to decide if you want to use a TimesTen container image that is located in a timesten repository on container-registry.oracle.com or if you want to build your own TimesTen container image. It is your choice as to which option you choose. For information about TimesTen container images, see About TimesTen Container Images.

Option 1: Use container-registry.oracle.com/timesten or container-registry.oracle.com/timesten-xe.

There are multiple container images available on the <code>container-registry.oracle.com/timesten</code> and <code>container-registry.oracle.com/timesten-xe</code> repositories. Browse the repositories and choose a container image that you want to use for the upgrade.

For example, if you want to upgrade to TimesTen release 22.1.1.19.0, a suitable TimesTen container image is:

```
container-registry.oracle.com/timesten/timesten:22.1.1.19.0
```

After you choose the container image, you must obtain the Operator manifest files from it.

For information about how to use a TimesTen container image located in a container-registry.oracle.com timesten repository, and how to obtain the Operator manifest files from it, see Option 1: Use the Official TimesTen Container Images.

Option 2: Build a TimesTen container image

The TimesTen distribution contains the TimesTen Operator distribution. The TimesTen Operator distribution provides a Dockerfile for building a TimesTen container image. For the upgrade, choose the pertinent TimesTen patch or patchset distribution. Download and unpack it. Next, unpack the Operator distribution. The Operator distribution not only includes the Dockerfile to build your container image, but also contains the Operator manifest files.

For example, if you want to upgrade to TimesTen release 22.1.1.19.0, a suitable TimesTen distribution is:

```
timesten2211190.server.linux8664.zip
```

For information about building a TimesTen container image, see Option 2: Build the TimesTen Container Image.

After you complete the tasks for either Option 1 or Option 2, you should know the following:

Name of image registry

For example, container-registry.oracle.com/timesten Or phx.ocir.io/youraccount

Name of image

For example, timesten:22.1.1.19.0

Directory that contains the Operator manifest files

```
For example, new_kube_files
```

The Operator manifest files include the new crd.yaml and the new service_account.yaml files. You update your Kubernetes cluster with these files. There is also a new operator.yaml file. You edit this file with the location and name of the new TimesTen container image. These tasks are described in Upgrade the Operator.

For the examples in the upcoming sections, let's assume:

- Location of the image registry is container-registry.oracle.com/timesten.
- Name of the image is timesten: 22.1.1.19.0.
- Operator manifest files reside in the new_kube_files directory on your development host.



Upgrade the Operator

The tasks in this section show you how to upgrade the Operator to a new patch or patchset. You can perform an Operator upgrade while there are TimesTenClassic and TimesTenScaleout objects deployed in your namespace.

Let's first update the Kubernetes cluster with the new CRD and service account.

1. On your development host, change to the <code>new_kube_files</code> directory. Next, replace the CRD running in your Kubernetes cluster.

```
cd new_kube_files
kubectl replace -f crd.yaml
```

The output is the following.

```
customresourcedefinition.apiextensions.k8s.io/
timestenclassics.timesten.oracle.com/
timestenscaleouts.timesten.oracle.com replaced
```

2. Replace the service account.

```
kubectl replace -f service account.yaml
```

The output is the following.

```
role.rbac.authorization.k8s.io/timesten-operator replaced
serviceaccount/timesten-operator replaced
rolebinding.rbac.authorization.k8s.io/timesten-operator replaced
```

Next, let's upgrade the Operator.

3. (Optional): Confirm there is an Operator running.

```
kubectl get pods
```

The output is similar to the following.

NAME	READY	STATUS	RESTARTS	AGE
sample-0	2/2	Running	0	14h
sample-1	2/2	Running	0	14h
sample2-0	2/2	Running	0	14h
sample2-1	2/2	Running	0	14h
timesten-operator-778878dc6b-4mc77	1/1	Running	0	15h

The name of the Operator is timesten-operator-778878dc6b-4mc77. The other Pods are associated with sample and sample2 TimesTenClassic objects in your namespace.

4. Upgrade the timesten-operator Deployment.



Edit these fields in the operator.yaml file:

• replicas: 1

Replace 1 with the number of copies of the Operator that you want to run. A value of 1 is acceptable for development and testing. However, you can run more than one replica for high availability purposes.

- Replace sekret with the name of the image pull secret that you want Kubernetes to use to pull images from your registry.
- Replace the image line to reference the new TimesTen container image. In this example, the new image is container-registry.oracle.com/timesten/timesten:22.1.1.19.0.

```
vi operator.yaml
apiVersion: apps/v1
kind: Deployment
metadata:
 name: timesten-operator
spec:
 replicas: 1
 selector:
   matchLabels:
     name: timesten-operator
  template:
   metadata:
     labels:
        name: timesten-operator
    spec:
      serviceAccountName: timesten-operator
      imagePullSecrets:
      - name: sekret
      containers:
        - name: timesten-operator
          image: container-registry.oracle.com/timesten/
timesten:22.1.1.19.0
          command:
          - /timesten/operator/operator/timesten-operator
          imagePullPolicy: Always
          env:
            - name: WATCH NAMESPACE
              valueFrom:
                fieldRef:
                  fieldPath: metadata.namespace
            - name: POD NAME
              valueFrom:
                fieldRef:
                  fieldPath: metadata.name
            - name: OPERATOR NAME
              value: "timesten-operator"
          securityContext:
              runAsNonRoot: true
              privileged: false
              allowPrivilegeEscalation: false
```



capabilities: drop: - all

5. Update the timesten-operator Deployment.

kubectl replace -f operator.yaml

The output is the following.

deployment.apps/timesten-operator replaced

6. Verify that the new Operator is running.

kubectl get pods

The output is similar to the following.

NAME	READY	STATUS	RESTARTS	AGE
sample-0	2/2	Running	0	15h
sample-1	2/2	Running	0	15h
sample2-0	2/2	Running	0	15h
sample2-1	2/2	Running	0	15h
timesten-operator-6f9d96bdfc-h221m	1/1	Running	0	9s

The name of the new Operator is timesten-operator-6f9d96bdfc-h221m.

7. Review the new timesten-operator Deployment.

kubectl describe deployment timesten-operator

The output is similar to the following.

Name: timesten-operator Namespace: mynamespace

Sun, 08 Jan 2023 01:22:28 +0000 CreationTimestamp:

Labels: <none>

Annotations: deployment.kubernetes.io/revision: 3
name=timestan_enerator

Selector: name=timesten-operator

Replicas: 1 desired | 1 updated | 1 total | 1 available | 0

unavailable

StrategyType: RollingUpdate

MinReadySeconds:

RollingUpdateStrategy: 25% max unavailable, 25% max surge

Pod Template:

name=timesten-operator Labels: Service Account: timesten-operator

Containers:

timesten-operator:

Image: container-registry.oracle.com/timesten/

timesten:22.1.1.19.0 Port: <none>



```
Host Port: <none>
   Command:
     /timesten/operator/operator/timesten-operator
   Environment:
     WATCH NAMESPACE: (v1:metadata.namespace)
     POD NAME:
                     (v1:metadata.name)
     OPERATOR NAME: timesten-operator
            <none>
   Mounts:
 Volumes:
                   <none>
Conditions:
             Status Reason
 Type
 ----
             -----
 Available True MinimumReplicasAvailable
 Progressing True NewReplicaSetAvailable
OldReplicaSets: <none>
NewReplicaSet: timesten-operator-6f9d96bdfc (1/1 replicas created)
Events:
 . . .
```

You have successfully updated the timesten-operator Deployment. The new Operator is using the container-registry.oracle.com/timesten/timesten:22.1.1.19.0 container image, and is automatically managing any existing TimesTenClassic and TimesTenScaleout objects in your namespace.

About Upgrading TimesTen Classic

The TimesTen Kubernetes Operator supports the upgrade of TimesTen Classic to a new patch or patchset.

There are two options for upgrading:

- Auto (default): The Operator does the upgrade for you.
- Manual: You do the upgrade manually.

The .spec.ttspec.imageUpgradeStrategy datum for a TimesTenClassic object lets you choose the type of upgrade. You set a value for this datum when you initially create and deploy a TimesTenClassic object. For more information about the imageUpgradeStrategy datum, see TimesTenClassicSpecSpec.

No matter what type of upgrade you choose, what happens during the upgrade is similar. The standby is terminated first. It takes some time for the standby to come back up. During this wait period, the standby is upgraded to the new release. During this upgrade of the standby, depending on your replication configuration, there may be disruption on the active database. This may impact your applications. Next, the failover from the active to the standby occurs. The active is terminated. There is a wait period for the former active to come back up. During this wait period, the active is upgraded to the new release. The standby database is promoted to be the active and the former active becomes the standby.

There are examples illustrating both types of upgrades later in Perform an Automated Upgrade and Perform a Manual Upgrade.

Note:

If you are using AWT cache groups, the standby is normally responsible for transmitting committed transactions from TimesTen to the Oracle Database. While the standby is being upgraded, the active takes on this responsibility. This may increase the load on the active. In addition, part of the upgrade process involves copying the database from the active to the standby. This also increases the workload on the active. These increases may temporarily reduce the performance of the active database.

Ensure you perform an upgrade at the appropriate time. TimesTen recommends that you do not perform upgrades at the busiest time of a production day. Applications see shortages and perhaps reduced performance as a result of the upgrade procedure.

Perform an Automated Upgrade

The .spec.ttspec.imageUpgradeStrategy datum of a TimesTenClassic object determines the upgrade strategy. You can use the kubectl get ttc -o yaml command to determine the value of this datum for any TimesTenClassic object. For example, let's assume there is a sample TimesTenClassic object in our namespace. Let's review the setting for the .spec.ttspec.imageUpgradeStrategy datum for sample.

```
kubectl get ttc sample -o yaml
```

The output is similar to the following. Note: Not all output is shown.

```
apiVersion: timesten.oracle.com/v1
kind: TimesTenClassic
metadata:
  name: sample
  namespace: mynamespace
  resourceVersion: "74826407"
  uid: 76038b9b-4635-4974-88cf-385739499ec4
spec:
  . . .
  ttspec:
    additionalMemoryRequest: 1Gi
    automaticMemoryRequests: true
    daemonLogCPURequest: 200m
    daemonLogMemoryRequest: 20Mi
    dbConfigMap:
    - sample
    exporterCPURequest: 200m
    exporterMemoryRequest: 200Mi
    imageUpgradeStrategy: Auto
    memoryWarningPercent: 90
```



The value for .spec.ttspec.imageUpgradeStrategy is Auto.

Let's walk through the steps for an automated upgrade.



Recall that when you do an automated upgrade, your databases are taken down, restarted, and failed over **immediately**. Do not perform this procedure at the busiest time of your production day. Applications see short outages and perhaps reduced performance as a result of the upgrade procedure.

Modify a TimesTenClassic Object: Automated Upgrade

The automated upgrade process requires you to modify the <code>.spec.image</code> datum of a TimesTenClassic object to reference the new TimesTen container image. After you modify the TimesTenClassic object to reference the new TimesTen image, the Operator notices the change and modifies the StatefulSet that it created. The Operator then starts the upgrade process. You can use the <code>kubectl describe</code> command to monitor this upgrade process.

 On your development host, edit the sample TimesTenClassic object, changing the .spec.ttspec.image datum to reference the new TimesTen container image. In this example, the location and name of the new container image is container-registry.oracle.com/timesten/timesten:22.1.1.19.0.

Note: Not all output is shown.

- sample

```
kubectl edit timestenclassic sample
# Please edit the object below. Lines beginning with a '#' will be
# and an empty file will abort the edit. If an error occurs while
saving this file will be
# reopened with the relevant failures.
apiVersion: timesten.oracle.com/v1
kind: TimesTenClassic
metadata:
 name: sample
 namespace: mynamespace
  resourceVersion: "74909603"
 uid: 76038b9b-4635-4974-88cf-385739499ec4
spec:
 ttspec:
    additionalMemoryRequest: 1Gi
    automaticMemoryRequests: true
    daemonLogCPURequest: 200m
    daemonLogMemoryRequest: 20Mi
    dbConfigMap:
```



```
exporterCPURequest: 200m
exporterMemoryRequest: 200Mi
image: container-registry.oracle.com/timesten/timesten:22.1.1.19.0
imagePullPolicy: Always
imagePullSecret: sekret
imageUpgradeStrategy: Auto
memoryWarningPercent: 90
storageClassName: oci-bv
storageSize: 250G
```

The output is the following.

timestenclassic.timesten.oracle.com/sample edited

2. Verify that the Operator has modified the sample StatefulSet and replaced the image with the new image.

```
kubectl describe statefulset sample
```

The output is similar to the following.

```
sample
Name:
                   mynamespace
Namespace:
Replicas:
                  2 desired | 2 total
                   OnDelete
Update Strategy:
Pods Status:
                   1 Running / 1 Waiting / 0 Succeeded / 0 Failed
Pod Template:
 Labels:
             app=sample
               database.timesten.oracle.com=sample
 Annotations: TTC: 76038b9b-4635-4974-88cf-385739499ec4
 Init Containers:
  ttinit:
               container-registry.oracle.com/timesten/
    Image:
timesten:22.1.1.19.0
   Ports: 8443/TCP, 6624/TCP, 6625/TCP, 4444/TCP
   Host Ports: 0/TCP, 0/TCP, 0/TCP, 0/TCP
   Environment:
     TT OPERATOR MANAGED:
     TIMESTEN HOME:
                               /tt/home/timesten/instances/instance1
     LD LIBRARY PATH:
                               /tt/home/timesten/instances/instance1/
ttclasses/lib:/tt/home/timesten/instances/instance1/install/lib:/tt/home/
timesten/instances/instance1/install/ttoracle home/instantclient 11 2:/tt/
home/timesten/instances/instance1/install/ttoracle home/instantclient
      TT REPLICATION TOPOLOGY: activeStandbyPair
      TT INIT CONTAINER:
     TTC UID:
                               76038b9b-4635-4974-88cf-385739499ec4
   Mounts:
      /tt from tt-persistent (rw)
      /ttagent from tt-agent (rw)
      /ttconfig from tt-config (rw)
  Containers:
   tt:
```



```
Image:
                 container-registry.oracle.com/timesten/
timesten:22.1.1.19.0
                8443/TCP, 6624/TCP, 6625/TCP, 4444/TCP
   Host Ports: 0/TCP, 0/TCP, 0/TCP, 0/TCP
    Environment:
      TT OPERATOR MANAGED:
      TIMESTEN HOME:
                                /tt/home/timesten/instances/
instance1
      LD LIBRARY PATH:
                                /tt/home/timesten/instances/
instance1/ttclasses/lib:/tt/home/timesten/instances/instance1/
install/lib:/tt/home/timesten/instances/instance1/install/
ttoracle home/instantclient 11 2:/tt/home/timesten/instances/
instance1/install/ttoracle home/instantclient
      TT REPLICATION TOPOLOGY: activeStandbyPair
   Mounts:
      /tt from tt-persistent (rw)
      /ttagent from tt-agent (rw)
      /ttconfig from tt-config (rw)
   daemonlog:
    Image:
               container-registry.oracle.com/timesten/
timesten:22.1.1.19.0
    Port:
               <none>
   Host Port: <none>
    Command:
      sh
      -0
      /bin/bash <<'EOF'
     while [ 1 ] ; do tail --follow=name /tt/home/timesten/
instances/instance1/diag/ttmesg.log --max-unchanged-stats=5; sleep
1; done
     exit 0
     EOF
   Requests:
      cpu:
              100m
     memory: 20Mi
   Environment:
     TIMESTEN HOME:
                            /tt/home/timesten/instances/instance1
      TT OPERATOR MANAGED: 1
      LD LIBRARY PATH:
                            /tt/home/timesten/instances/instance1/
ttclasses/lib:/tt/home/timesten/instances/instance1/install/lib:/tt/
home/timesten/instances/instance1/install/ttoracle home/
instantclient 11 2:/tt/home/timesten/instances/instance1/install/
ttoracle home/instantclient
   Mounts:
      /tt from tt-persistent (rw)
 Volumes:
   tt-agent:
                 Secret (a volume populated by a Secret)
    SecretName: tt76038b9b-4635-4974-88cf-385739499ec4
                false
   Optional:
   tt-config:
    Type:
                        Projected (a volume that contains injected
data from multiple sources)
   ConfigMapName:
    ConfigMapOptional: <nil>
```

Volume Claims:

Name: tt-persistent

StorageClass: oci-bv
Labels: <none>
Annotations: <none>
Capacity: 50G

Access Modes: [ReadWriteOnce]

Events:

Type Reason Age From Message

---- -----

Normal SuccessfulCreate 22s (x2 over 18h) statefulset-controller create Pod sample-1 in StatefulSet sample successful

You have modified the sample TimesTenClassic object to use the new TimesTen container image. You are now ready to monitor the automated upgrade process performed by the Operator.

Monitor an Automated Upgrade

You can monitor the automated upgrade process performed by the Operator. These steps are optional.

 Use the kubectl get command to assess the state of the sample TimesTenClassic object.

kubectl get ttc sample

Note that the initial state is StandbyDown.

NAME STATE ACTIVE AGE sample StandbyDown sample-0 18h

Wait a few minutes, then run the command again.

kubectl get ttc sample

Note that the state has changed to Normal.

NAME STATE ACTIVE AGE sample Normal sample-1 18h

The Operator promoted sample-1 to be the active.

2. Use the kubectl describe command to observe how the Operator promoted the standby database (sample-1) to be the active.

kubectl describe ttc sample



The output is similar to the following.

Name: sample Namespace: mynamespace TimesTenClassic Kind: Metadata: Spec: Ttspec: Additional Memory Request: 1Gi Automatic Memory Requests: true Daemon Log CPU Request: 200m Daemon Log Memory Request: 20Mi Db Config Map: sample Exporter CPU Request: 200m Exporter Memory Request: 200Mi Image: container-registry.oracle.com/ timesten/timesten:22.1.1.19.0 Image Pull Policy: Always Image Pull Secret: sekret Image Upgrade Strategy: Auto Memory Warning Percent: 90 Storage Class Name: oci-bv 250G Storage Size: Status: . . . Pod Status: Active: false Admin User File: true Cache Status: Not Running Cache Agent: Cache UID Pwd Set: true N Cache Groups: false Cache User File: Cg File: false Db Status: Db: Loaded Disable Return: false Has Been Seen: true High Level State: Healthy Initialized: true Intended State: Standby Last High Level State Switch: 1673208466 Local Commit: false Name: sample-0 Pod Status: qU Last Time Reachable: 1673208466 Pod IP: 192.0.2.1 Pod Phase: Running Prev Active: false



Prev High Level State: Healthy Prev Image: container-registry.oracle.com/timesten/ timesten:22.1.1.9.0 Prev Intended State: Active Prev Ready: true Ready: true Replication Status: Last Time Rep State Changed: 1673208234 Rep Agent: Running Rep Peer P State: start Rep Scheme: Exists STANDBY Rep State: Scaleout Status: Instance Type: classic Schema File: true Timesten Status: Daemon: Up Instance: Exists Release: 22.1.1.19.0 Tt Pod Type: Database Using Twosafe: false Active: true Admin User File: true Cache Status: Cache Agent: Not Running Cache UID Pwd Set: true N Cache Groups: Cache User File: false Cq File: false Db Status: Db: Loaded Name: sample-1 Pod Status: Agent: Uр Last Time Reachable: 1673208466 Pod IP: 192.0.2.2 Pod Phase: Running Prev Active: true Prev High Level State: Healthy Prev Image: container-registry.oracle.com/timesten/ timesten:22.1.1.9.0 Prev Intended State: Standby Prev Ready: true Ready: true Replication Status: Last Time Rep State Changed: 1673208191 Rep Agent: Running Rep Peer P State: start Rep Scheme: Exists Rep State: ACTIVE Scaleout Status: Instance Type: classic Schema File: true Timesten Status:

```
Daemon:
                        Uр
     Instance:
                       Exists
                        22.1.1.19.0
     Release:
   Tt Pod Type:
                        Database
   Using Twosafe:
                        false
  Prev High Level State: StandbyDown
 Prev Reexamine:
 Prev Stop Managing:
 Rep Create Statement: create active standby pair "sample" on
"sample-0.sample.mynamespace.svc.cluster.local", "sample" on
"sample-1.sample.mynamespace.svc.cluster.local" NO RETURN store
"sample" on "sample-0.sample.mynamespace.svc.cluster.local" PORT
4444 FAILTHRESHOLD 0 store "sample" on
"sample-1.sample.mynamespace.svc.cluster.local" PORT 4444
FAILTHRESHOLD 0
                        4444
 Rep Port:
 Rep Start Fail Count: 0
 Standby Cache Agent:
                        Not Running
 Standby Down Standby AS:
   Async Id:
                      5f083b21-20a9-4b93-93bf-8a42a160a0bc
   Destroy Db:
   Id:
                      8bd89bbd-fb69-4249-822d-4dd729443e4b
   Pod Name:
                     sample-0
   Rep Duplicate:
                     true
   Start Rep Agent: true
   Status:
                     complete
 Standby Perm In Use: 17134
 Standby Perm Size: 200
 Standby Rep Agent: Running
 Status Version:
                   1.0
 Using Twosafe:
                     false
Events:
 Type Reason Age From
                                     Message
                     ----
          -----
                                       -----
 Normal Upgrade 6m41s timesten Image updated, automatic
upgrade started
 Normal Upgrade 6m41s timesten Deleted standby pod
sample-1 during upgrade
 Normal Info 6m29s timesten Pod sample-1 Agent Down
 Normal StateChange 6m29s timesten Pod sample-1 is Not Ready
 Warning StateChange 6m29s timesten TimesTenClassic was
Normal, now ActiveTakeover
 Normal StateChange 6m23s timesten TimesTenClassic was
ActiveTakeover, now StandbyDown
 Normal Info 5m4s timesten Pod sample-1 Agent Up
 Normal Info
                     5m4s timesten Pod sample-1 Instance
Exists
 Normal Info 5m4s timesten Pod sample-1 Daemon Down Normal Info 5m3s timesten Pod sample-1 Daemon Up Normal Info 5m3s timesten Pod sample-1 Database
Unloaded
 Normal Info 5m1s timesten Pod sample-1 Database None
 Normal StateChange 4m46s timesten Pod sample-1 RepState IDLE
 Normal Info 4m46s timesten Pod sample-1 Database
Loaded
```

```
Normal Info 4m46s timesten Pod sample-1 RepScheme Exists
Normal Info 4m46s timesten Pod sample-1 RepAgent Not Running
Normal Info 4m40s timesten Pod sample-1 RepAgent Running
  Normal StateChange 4m40s timesten TimesTenClassic was StandbyDown,
now StandbyStarting
  Normal StateChange 4m40s timesten TimesTenClassic was
StandbyStarting, now StandbyCatchup
  Normal StateChange 4m35s timesten Pod sample-1 RepState STANDBY
  Normal StateChange 4m34s timesten TimesTenClassic was
StandbyCatchup, now Normal
  Normal Upgrade 4m3s timesten Deleted active pod sample-0
during upgrade
  Normal Info 3m52s timesten Pod sample-0 Agent Down
  Normal StateChange 3m52s timesten Pod sample-0 is Not Ready
  Normal StateChange 3m52s timesten Pod sample-0 is Not Active Ready
  Warning StateChange 3m52s timesten TimesTenClassic was Normal, now
ActiveDown
  Normal StateChange 3m52s timesten Pod sample-1 is Ready
  Normal Info 3m50s timesten Pod sample-1 Database Updatable
  Normal StateChange 3m50s timesten Pod sample-1 RepState ACTIVE
 Normal StateChange 3m50s timesten Pod sample-1 is Not Ready
  Normal StateChange 3m50s timesten TimesTenClassic was ActiveDown,
now ActiveTakeover
  Normal StateChange 3m45s timesten Pod sample-1 is Ready
  Normal StateChange 3m45s timesten Pod sample-1 is Active Ready
  Normal StateChange 3m45s timesten TimesTenClassic was
ActiveTakeover, now StandbyDown
 Normal Info 3mls timesten Pod sample-0 Agent Up
Normal Info 3mls timesten Pod sample-0 Instance Exists
Normal Info 3mls timesten Pod sample-0 Daemon Down
Normal Info 3mls timesten Pod sample-0 Daemon Up
Normal Info 3mls timesten Pod sample-0 Database Unloaded
Normal Info 2m58s timesten Pod sample-0 Database None
Normal Info 2m43s timesten Pod sample-0 Database Loaded
Normal Info 2m43s timesten Pod sample-0 RepAgent Not Running
Normal Info 2m43s timesten Pod sample-0 RepScheme Exists
  Normal StateChange 2m43s timesten Pod sample-0 RepState IDLE
  Normal Info 2m37s timesten Pod sample-0 RepAgent Running
  Normal StateChange 2m37s timesten Pod sample-0 RepState STANDBY
  Normal StateChange 2m37s timesten Pod sample-0 is Ready
  Normal Upgrade 2m37s timesten Upgrade of active complete
Normal Upgrade 2m37s timesten Upgrade completed in 244 secs
  Normal StateChange 2m37s timesten TimesTenClassic was StandbyDown,
now Normal
```

The automated upgrade is successful. The active and standby Pods are running the new TimesTen image, which contains the new TimesTen release.

Perform a Manual Upgrade

This section describes the process for performing a manual upgrade of your TimesTenClassic objects and includes the following subsections:

Modify a TimesTenClassic Object: Manual Upgrade

- Upgrade the Standby Database
- Fail Over

Modify a TimesTenClassic Object: Manual Upgrade

The manual upgrade process requires you to modify the <code>.spec.ttspec.image</code> datum of a TimesTenClassic object to reference the new TimesTen container image. After you modify the TimesTenClassic object to reference the new TimesTen image, the Operator notices the change and modifies the StatefulSet that it created.

Let's modify the TimesTenClassic sample2 object to reference the new TimesTen image. Let's assume the sample2 object's .spec.ttspec.imageUpgradeStrategy is Manual.

 On your development host, edit the sample TimesTenClassic object, changing the .spec.ttspec.image datum to reference the new TimesTen container image. In this example, the location and name of the new container image is container-registry.oracle.com/timesten/timesten:22.1.1.19.0.

Note: Not all output is shown.

```
kubectl edit timestenclassic sample2
# Please edit the object below. Lines beginning with a '#' will be
ignored,
# and an empty file will abort the edit. If an error occurs while
saving this file will be
# reopened with the relevant failures.
apiVersion: timesten.oracle.com/v1
kind: TimesTenClassic
metadata:
 name: sample2
 namespace: mynamespace
  resourceVersion: "74928067"
 uid: e6d49f75-05ed-4b4b-9412-4a577ad19bbe
spec:
  ttspec:
    additionalMemoryRequest: 1Gi
    automaticMemoryRequests: true
    daemonLogCPURequest: 200m
    daemonLogMemoryRequest: 20Mi
    dbConfigMap:
    - sample2
    exporterCPURequest: 200m
    exporterMemoryRequest: 200Mi
    image: container-registry.oracle.com/timesten/
timesten:22.1.1.19.0
    imagePullPolicy: Always
    imagePullSecret: sekret
    imageUpgradeStrategy: Manual
    memoryWarningPercent: 90
    storageClassName: oci-bv
```



```
storageSize: 250G
```

The output is the following.

timestenclassic.timesten.oracle.com/sample2 edited

2. Verify that the Operator has modified the sample2 StatefulSet and replaced the image with the new image.

```
kubectl describe statefulset sample2
```

The output is similar to the following.

```
Name:
                    sample2
Namespace:
                  mynamespace
                  2 desired | 2 total
Replicas:
Update Strategy:
                   OnDelete
Pods Status:
                   2 Running / O Waiting / O Succeeded / O Failed
Pod Template:
 Labels:
             app=sample2
               database.timesten.oracle.com=sample2
 Annotations: TTC: e6d49f75-05ed-4b4b-9412-4a577ad19bbe
 Init Containers:
   ttinit:
               container-registry.oracle.com/timesten/
    Image:
timesten:22.1.1.19.0
   Ports: 8443/TCP, 6624/TCP, 6625/TCP, 4444/TCP
   Host Ports: 0/TCP, 0/TCP, 0/TCP, 0/TCP
   Environment:
      TT OPERATOR MANAGED:
      TIMESTEN HOME:
                               /tt/home/timesten/instances/instance1
     LD LIBRARY PATH:
                               /tt/home/timesten/instances/instance1/
ttclasses/lib:/tt/home/timesten/instances/instance1/install/lib:/tt/home/
timesten/instances/instance1/install/ttoracle home/instantclient 11 2:/tt/
home/timesten/instances/instance1/install/ttoracle home/instantclient
      TT REPLICATION TOPOLOGY: activeStandbyPair
      TT INIT CONTAINER:
      TTC UID:
                               e6d49f75-05ed-4b4b-9412-4a577ad19bbe
   Mounts:
      /tt from tt-persistent (rw)
      /ttagent from tt-agent (rw)
      /ttconfig from tt-config (rw)
  Containers:
   tt:
    Image:
                container-registry.oracle.com/timesten/
timesten:22.1.1.19.0
                8443/TCP, 6624/TCP, 6625/TCP, 4444/TCP
   Host Ports: 0/TCP, 0/TCP, 0/TCP, 0/TCP
   Environment:
      TT OPERATOR MANAGED:
                               /tt/home/timesten/instances/instance1
      TIMESTEN HOME:
```

```
LD LIBRARY PATH:
                                /tt/home/timesten/instances/
instance1/ttclasses/lib:/tt/home/timesten/instances/instance1/
install/lib:/tt/home/timesten/instances/instance1/install/
ttoracle home/instantclient 11 2:/tt/home/timesten/instances/
instance1/install/ttoracle home/instantclient
      TT REPLICATION TOPOLOGY: activeStandbyPair
   Mounts:
     /tt from tt-persistent (rw)
      /ttagent from tt-agent (rw)
      /ttconfig from tt-config (rw)
   daemonlog:
    Image:
               container-registry.oracle.com/timesten/
timesten:22.1.1.9.0
   Host Port: <none>
    Command:
      sh
      /bin/bash <<'EOF'
     while [ 1 ] ; do tail --follow=name /tt/home/timesten/
instances/instance1/diag/ttmesg.log --max-unchanged-stats=5; sleep
1; done
     exit 0
     EOF
   Requests:
              100m
     cpu:
     memory: 20Mi
   Environment:
     TIMESTEN HOME:
                           /tt/home/timesten/instances/instance1
      TT OPERATOR MANAGED: 1
      LD LIBRARY PATH:
                           /tt/home/timesten/instances/instance1/
ttclasses/lib:/tt/home/timesten/instances/instance1/install/lib:/tt/
home/timesten/instances/instance1/install/ttoracle home/
instantclient 11 2:/tt/home/timesten/instances/instance1/install/
ttoracle home/instantclient
   Mounts:
      /tt from tt-persistent (rw)
 Volumes:
   tt-agent:
   Type:
                Secret (a volume populated by a Secret)
    SecretName: tte6d49f75-05ed-4b4b-9412-4a577ad19bbe
   Optional:
                false
   tt-config:
    Type:
                        Projected (a volume that contains injected
data from multiple sources)
   ConfigMapName:
                        sample2
   ConfigMapOptional: <nil>
Volume Claims:
 Name:
                tt-persistent
  StorageClass: oci-bv
 Labels:
                <none>
 Annotations: <none>
 Capacity:
                50G
 Access Modes: [ReadWriteOnce]
Events:
                <none>
```

You successfully modified the sample2 TimesTenClassic object to use the new TimesTen container image. Let's continue the manual upgrade by upgrading the standby database.

Upgrade the Standby Database

Perform these steps to upgrade the standby database.



Even though you are upgrading the standby database, depending on your replication configuration, this may result in disruption on your active database. This may impact your applications. Perform the upgrade at the appropriate time.

- 1. Use the kubectl get ttc command to:
 - Determine which Pod is the standby. The active Pod is the Pod represented in the ACTIVE column. The standby Pod is the other Pod (not represented in the ACTIVE column). Therefore, for the sample2 TimesTenClassic object, the active Pod is sample2-0 and the standby Pod is sample2-1.
 - Ensure the state for the TimesTenClassic object (sample2, in this example) is Normal.

```
kubectl get ttc sample2
```

The output is the following.

```
NAME STATE ACTIVE AGE sample2 Normal sample2-0 19h
```

2. To upgrade the standby to the new TimesTen image, delete the standby Pod (sample2-1, in this example).

```
kubectl delete pod sample2-1
```

The output is the following.

```
pod "sample2-1" deleted
```

Kubernetes automatically creates a new sample2-1 Pod to replace the deleted Pod. The Operator configures the new sample2-1 Pod as the standby Pod. This new Pod will now run the newly created TimesTen image.

3. Verify the standby is up and running and the state is Normal.

```
kubectl get ttc sample2
```



Note that the state is initially StandbyDown.

```
NAME STATE ACTIVE AGE sample2 StandbyDown sample2-0 19h
```

Wait a few minutes, then run the command again.

```
kubectl get ttc sample2
```

Note that the state has changed to Normal.

```
NAME STATE ACTIVE AGE sample2 Normal sample2-0 19h
```

4. Verify that the standby is up and running again and that the active standby pair health is Normal. During the upgrade of the standby, your applications are not disrupted. Your applications can continue to use the active database.

```
kubectl describe ttc sample2
```

The output is similar to the following.

```
Name:
             sample2
Namespace:
             mynamespace
Kind:
             TimesTenClassic
. . .
Spec:
 Ttspec:
   Additional Memory Request: 1Gi
   Automatic Memory Requests: true
   Daemon Log CPU Request:
                               200m
   Daemon Log Memory Request: 20Mi
   Db Config Map:
     sample2
   Exporter CPU Request:
                              200m
   Exporter Memory Request: 200Mi
    Image:
                             container-registry.oracle.com/
timesten/timesten:22.1.1.19.0
    Image Pull Policy:
                             Always
    Image Pull Secret:
                             sekret
   Image Upgrade Strategy: Manual
   Memory Warning Percent: 90
   Storage Class Name: oci-bv
   Storage Size:
                             250G
Status:
 Classic Upgrade Status:
 High Level State:
                                Normal
  . . .
```

```
Pod Status:
   Active:
                   true
   Admin User File: true
   Cache Status:
     Cache Agent: Not Running
     Cache UID Pwd Set: true
     N Cache Groups:
   Cache User File:
                       false
   Cq File:
                        false
   Db Status:
     . . .
   Name:
                                                 sample2-0
   Pod Status:
     Agent:
                          Uр
     Last Time Reachable: 1673213068
     Pod IP:
                         192.0.2.3
     Pod Phase:
                         Running
   Prev Active:
                          true
   Prev High Level State: Healthy
   Prev Image:
                          container-registry.oracle.com/timesten/
timesten:22.1.1.9.0
   Prev Intended State:
   Prev Ready:
                          true
   Ready:
                          true
   Replication Status:
     Last Time Rep State Changed: 0
     Rep Agent:
                                  Running
     Rep Peer P State:
                                  start
     Rep Scheme:
                                 Exists
     Rep State:
                                 ACTIVE
   Scaleout Status:
     Instance Type: classic
   Schema File: true
   Timesten Status:
               Up
     Daemon:
                  Exists
     Instance:
     Release:
                  22.1.1.9.0
                   Database
   Tt Pod Type:
   Using Twosafe: false
   Active:
                    false
   Admin User File: true
   Cache Status:
     Cache Agent:
                        Not Running
     Cache UID Pwd Set: true
     N Cache Groups:
   Cache User File: false
   Cq File:
                        false
   Db Status:
     . . .
   Name:
                                                       sample2-1
   Pod Status:
     Agent:
     Last Time Reachable: 1673213068
     Pod IP:
                          192.0.2.4
     Pod Phase:
                          Running
```

Prev Active: false Prev High Level State: Healthy Prev Image: container-registry.oracle.com/timesten/ timesten:22.1.1.9.0 Prev Intended State: Prev Ready: true Ready: true Replication Status: Last Time Rep State Changed: 1673212993 Rep Agent: Rep Peer P State: start Rep Scheme: Exists Rep State: STANDBY Scaleout Status: Instance Type: classic Schema File: true Timesten Status: Daemon: Uр Exists Instance: Release: 22.1.1.19.0 Tt Pod Type: Database Using Twosafe: false Prev High Level State: StandbyCatchup Prev Reexamine: Prev Stop Managing: Rep Create Statement: create active standby pair "sample2" on "sample2-0.sample2.mynamespace.svc.cluster.local", "sample2" on "sample2-1.sample2.mynamesoace.svc.cluster.local" NO RETURN store "sample2" on "sample2-0.sample2.mynamespace.svc.cluster.local" PORT 4444 FAILTHRESHOLD 0 store "sample2" on "sample2-1.sample2.mynamespace.svc.cluster.local" PORT 4444 FAILTHRESHOLD 0 Rep Port: 4444 Rep Start Fail Count: Standby Cache Agent: Not Running Standby Down Standby AS: c3cf41af-61c2-438c-a4d0-f3dfbdb6043d Async Id: Destroy Db: true 8a9a22ee-deaa-4eb6-8e00-c0d8932af623 Id: Pod Name: sample2-1 Rep Duplicate: true Start Rep Agent: true Status: complete Standby Perm In Use: 15291 Standby Perm Size: 200 Standby Rep Agent: Running 1.0 Status Version: Using Twosafe: false Events: Reason Message Type Age From 4m15s timesten Image updated, automatic Normal Upgrade upgrade disabled 3m24s timesten Pod sample2-1 Agent Down Normal Info Normal StateChange 3m24s timesten Pod sample2-1 is Not Ready

Warning	StateChange	3m19s	timesten	TimesTenClassic was Normal, now
ActiveTake	over			
Normal	StateChange	3m14s	timesten	TimesTenClassic was
ActiveTake	over, now Sta	ndbyDow	n	
Normal	Info	2m19s	timesten	Pod sample2-1 Agent Up
Normal	Info	2m19s	timesten	Pod sample2-1 Instance Exists
Normal	Info	2m19s	timesten	Pod sample2-1 Daemon Down
Normal	Info	2m19s	timesten	Pod sample2-1 Daemon Up
Normal	Info	2m19s	timesten	Pod sample2-1 Database Unloaded
Normal	Info	2m12s	timesten	Pod sample2-1 Database None
Normal	Info	116s	timesten	Pod sample2-1 Database Loaded
Normal	Info	116s	timesten	Pod sample2-1 RepAgent Not
Running				
Normal	Info	116s	timesten	Pod sample2-1 RepScheme Exists
Normal	StateChange	116s	timesten	Pod sample2-1 RepState IDLE
Normal	Info	111s	timesten	Pod sample2-1 RepAgent Running
Normal	StateChange	111s	timesten	TimesTenClassic was StandbyDown,
now Standb	yStarting			
Normal	StateChange	110s	timesten	TimesTenClassic was
StandbySta	rting, now St	andbyCa	tchup	
Normal	StateChange	75s	timesten	Pod sample2-1 RepState STANDBY
Normal	StateChange	75s	timesten	TimesTenClassic was
StandbyCat	chup, now Nor	mal		
Normal	StateChange	70s	timesten	Pod sample2-1 is Ready

Note the following:

- The image is upgraded to the new release.
- The active database (sample2-0) is not upgraded to the new release.
- The standby database (sample2-1) is upgraded to the new release.

You have successfully upgraded the standby database. You are now ready to fail over from the active database to the standby.

Fail Over

You must now fail over from the active database to the standby.



When you fail over, your active database will be taken down, and failed over **immediately**. Do not perform this procedure at the busiest time of your production day.

Before failing over, quiesce your applications on the active database. (You can also use the ttAdmin -close and the ttAdmin -disconnect commands. See Opening and Closing the Database for User Connections and Disconnecting from a Database in the *Oracle TimesTen In-Memory Database Operations Guide*.

To avoid potential data loss, use the ttRepAdmin-wait command to wait until replication is caught up, such that all transactions that were executed on the active database have been

replicated to the standby database. See ttRepAdmin in the *Oracle TimesTen In-Memory Database Reference*.

Once the standby is caught up, fail over from the active database to the standby by deleting the active Pod. When you delete the active Pod, the Operator automatically detects the failure and promotes the standby database to be the active. Client/server applications that are using the active database (sample2-0, in this example) are automatically reconnected to the new active database (sample2-1, in this example). Transactions in flight are rolled back. Prepared SQL statements will need to be reprepared by the applications. See About Handling Failover and Recovery for more information about client/server failover.

Kubernetes automatically creates a new sample2-0 Pod to replace the deleted Pod. The Operator will configure the new Pod as the standby Pod. This new Pod will run the newly created TimesTen image.



You may want to perform this operation during a scheduled production outage.

1. Use the kubectl delete command to delete the active Pod (sample2-0, in this example).

```
kubectl delete pod sample2-0
```

The output is the following.

```
pod "sample2-0" deleted
```

2. Use the kubectl get command to assess the state of the sample2 TimesTenClassic object.

```
kubectl get ttc sample2
```

Note that the state is initially ActiveDown.

```
NAME STATE ACTIVE AGE sample2 ActiveDown None 19h
```

Wait a few minutes, then run the command again.

```
kubectl get ttc sample2
```

Note that the state has changed to Normal.

```
NAME STATE ACTIVE AGE sample2 Normal sample2-1 19h
```



The Operator promoted sample-1 to be the active.

3. Use the kubectl describe command to observe how the Operator recovers from the failure. The Operator promotes the standby database (sample2-1) to be active. Any applications that were connected to the sample2-0 database are automatically reconnected to the sample2-1 database by TimesTen. After a brief outage, the applications can continue to use the database. See About Monitoring the Health of an Active Standby Pair of Databases for information on the health and states of the active standby pair.

```
kubectl describe ttc sample2
```

The output is similar to the following.

```
Name:
             sample2
           mynamespace
Namespace:
. . .
             TimesTenClassic
Kind:
Spec:
 Ttspec:
   Additional Memory Request: 1Gi
   Automatic Memory Requests: true
   Daemon Log CPU Request:
                               200m
   Daemon Log Memory Request: 20Mi
   Db Config Map:
     sample2
   Exporter CPU Request:
                             200m
   Exporter Memory Request: 200Mi
   Image:
                             container-registry.oracle.com/timesten/
timesten:22.1.1.19.0
   Image Pull Policy:
                            Always
   Image Pull Secret:
                            sekret
   Image Upgrade Strategy: Manual
   Memory Warning Percent: 90
   Storage Class Name:
                            oci-bv
   Storage Size:
                             250G
Status:
 Classic Upgrade Status:
 High Level State:
                               Normal
 Last Event:
 Last High Level State Switch: 1673214034
 Last Reconcile:
                              1673214897250
 Last Reconciling Operator: timesten-operator-6f9d96bdfc-h22lm
 Observed Generation:
 Pod Status:
   Active:
                   false
   Admin User File: true
   Cache Status:
     Cache Agent: Not Running
     Cache UID Pwd Set: true
```

N Cache Groups: Cache User File: false Cq File: false Db Status: Db: Loaded . . . Name: sample2-0 Pod Status: Agent: Uр Last Time Reachable: 1673214897 Pod IP: 192.0.2.3 Pod Phase: Running Prev Active: false Prev High Level State: Healthy container-registry.oracle.com/timesten/ Prev Image: timesten:22.1.1.9.0 Prev Intended State: Active Prev Ready: true Ready: true Replication Status: Last Time Rep State Changed: 1673213965 Rep Agent: Running Rep Peer P State: start Exists Rep Scheme: Rep State: STANDBY Scaleout Status: Instance Type: classic Schema File: true Timesten Status: Daemon: Up Instance: Exists 22.1.1.19.0 Release: Tt Pod Type: Database Using Twosafe: false Active: true Admin User File: true Cache Status: Cache Agent: Not Running Cache UID Pwd Set: true N Cache Groups: 0 Cache User File: false Ca File: false Db Status: Db: Loaded High Level State: Healthy Initialized: true Intended State: Active Last High Level State Switch: 1673214897 Local Commit: false Name: sample2-1 Pod Status: Agent: Uр Last Time Reachable: 1673214897 Pod IP: 192.0.2.4

Pod Phase: Running Prev Active: true Prev High Level State: Healthy Prev Image: container-registry.oracle.com/timesten/ timesten:22.1.1.9.0 Prev Intended State: Standby Prev Ready: true Ready: true Replication Status: Last Time Rep State Changed: 1673212993 Rep Agent: Running Rep Peer P State: start Rep Scheme: Exists Rep State: ACTIVE Scaleout Status: Instance Type: classic Schema File: true Timesten Status: Daemon: Instance: Exists 22.1.1.19.0 Release: Tt Pod Type: Database Using Twosafe: false Prev High Level State: StandbyDown Prev Reexamine: Prev Stop Managing: . . . Events: Type Reason Age From Message ------------Warning StateChange 15m timesten TimesTenClassic was Normal, now ActiveDown Normal Info 15m timesten Pod sample2-0 Agent Down Normal StateChange 15m timesten Pod sample2-0 is Not Ready Normal StateChange 15m timesten Pod sample2-0 is Not Active Ready Normal Info 15m timesten Pod sample2-1 Database Updatable Normal StateChange 15m timesten Pod sample2-1 RepState ACTIVE Normal StateChange 15m timesten Pod sample2-1 is Not Ready Normal StateChange 15m timesten TimesTenClassic was ActiveDown, now ActiveTakeover Normal StateChange 15m timesten Pod sample2-1 is Ready Normal StateChange 15m timesten TimesTenClassic was ActiveTakeover, now StandbyDown Normal StateChange 15m timesten Pod sample2-1 is Active Ready Normal StateChange 15m timesten Pod sample2-1 is Active Ready
Normal Info 14m timesten Pod sample2-0 Agent Up
Normal Info 14m timesten Pod sample2-0 Instance Exists
Normal Info 14m timesten Pod sample2-0 Daemon Down
Normal Info 14m timesten Pod sample2-0 Daemon Up
Normal Info 14m timesten Pod sample2-0 Database Unloaded
Normal Info 14m timesten Pod sample2-0 Database None
Normal Info 14m timesten Pod sample2-0 Database Loaded
Normal Info 14m timesten Pod sample2-0 RepAgent Not Running
Normal Info 14m timesten Pod sample2-0 RepScheme Exists
Normal StateChange 14m timesten Pod sample2-0 RepScheme Exists Normal StateChange 14m timesten Pod sample2-0 RepState IDLE



StandbyDo	wn. now Normal			
Normal	StateChange	14m	timesten	TimesTenClassic was
Normal	StateChange	14m	timesten	Pod sample2-0 is Ready
STANDBY				
Running Normal	StateChange	14m	timesten	Pod sample2-0 RepState
Normal	Info	14m	timesten	Pod sample2-0 RepAgent

You successfully upgraded to a new release of TimesTen. The active and the standby Pods are running the new TimesTen image, which contains the new TimesTen release.

In this example, the sample and the sample2 TimesTenClassic objects are now upgraded. The upgrade process is complete. Let's verify the active and the standby databases are running the new release of TimesTen.

Verify the Active Standby Pair of Databases Are Upgraded

After the upgrade process is complete for your TimesTenClassic objects, you can verify the active and standby databases are running the new release of TimesTen.

1. For the sample TimesTenClassic object, invoke a shell in the active Pod (sample-1, in this example). Then, run the TimesTen ttVersion utility to verify the release is the new release (22.1.1.19.0, in this example).

```
kubectl exec -it sample-1 -c tt -- /bin/bash
```

Run the TimesTen ttVersion utility.

ttVersion

The output is similar to the following.

```
TimesTen Release 22.1.1.19.0 (64 bit Linux/x86_64) (instance1:6624) 2023-09-29T07:40:22Z

Instance admin: timesten
Instance home directory: /tt/home/timesten/instances/instance1
Group owner: timesten
Daemon home directory: /tt/home/timesten/instances/instance1/info
PL/SQL enabled.
```

Exit from the shell.

exit

2. Invoke a shell in the standby Pod (sample-0, in this example). Then, run the ttVersion utility to verify the release is the new release (22.1.1.19.0, in this example).

```
kubectl exec -it sample-0 -c tt -- /bin/bash
```



Run the TimesTen ttVersion utility.

ttVersion

The output is similar to the following.

```
TimesTen Release 22.1.1.19.0 (64 bit Linux/x86_64) (instance1:6624) 2023-09-29T07:40:22Z

Instance admin: timesten
Instance home directory: /tt/home/timesten/instances/instance1
Group owner: timesten
Daemon home directory: /tt/home/timesten/instances/instance1/info PL/SQL enabled.
```

Exit from the shell.

exit

3. For the sample2 TimesTenClassic object, invoke a shell in the active Pod (sample2-1, in this example). Then, use the ttVersion utility to verify the release is the new release (22.1.1.19.0, in this example).

```
kubectl exec -it sample2-1 -c tt -- /bin/bash
```

Run the TimesTen ttVersion utility.

ttVersion

The output is similar to the following.

```
TimesTen Release 22.1.1.19.0 (64 bit Linux/x86_64) (instance1:6624) 2023-09-29T07:40:22Z

Instance admin: timesten
Instance home directory: /tt/home/timesten/instances/instance1

Group owner: timesten
Daemon home directory: /tt/home/timesten/instances/instance1/info
PL/SQL enabled.
```

Exit from the shell.

exit

4. Invoke a shell in the standby Pod (sample2-0, in this example). Then, use the ttVersion utility to verify the release is the new release (22.1.1.19.0, in this example).

```
kubectl exec -it sample2-0 -c tt -- /bin/bash
```



Run the TimesTen ttVersion utility.

ttVersion

The output is similar to the following.

```
TimesTen Release 22.1.1.19.0 (64 bit Linux/x86_64) (instance1:6624) 2023-09-29T07:40:22Z

Instance admin: timesten
Instance home directory: /tt/home/timesten/instances/instance1
Group owner: timesten
Daemon home directory: /tt/home/timesten/instances/instance1/info PL/SQL enabled.
```

Exit from the shell.

exit

The upgrade to a new release of TimesTen is successful for the sample and the sample2 TimesTenClassic objects. The active and the standby Pods for each TimesTenClassic object are running the new TimesTen image, which contains the new TimesTen release.

About Upgrading Direct Mode Applications

You cannot use this automated upgrade process to upgrade direct mode applications that are running in their own containers. The Operator does propagate the changes from a TimesTenClassic object to the associated StatefulSet, but the changes do not initiate the automated upgrade process. You must manually terminate the applications that are running in their containers. In so doing, StatefulSet spawns new containers to replace the original containers. These new containers run the newly specified TimesTen image. For more information about direct mode applications, see About Using Direct Mode Applications.

About Failures During an Upgrade

If there are failures in any step of the upgrade process, a TimesTenClassic object enters the ManualInterventionRequired state. The remaining steps of the upgrade process are cancelled. You must manually fix the active/standby pair to return the pair to management by the Operator. Even when the pair is returned to automatic management, the remaining steps in the upgrade process are not automatically performed. See About the ManualInterventionRequired State.



17

The TimesTen Kubernetes Operator Object Types

This chapter gives an overview of the TimesTenClassic and the TimesTenScaleout object types. The chapter describes the syntax for each object type.

Topics:

- Overview of the TimesTen Kubernetes Operator Object Types
- About the TimesTenClassic Object Type
- About the TimesTenScaleout Object Type

Overview of the TimesTen Kubernetes Operator Object Types

The TimesTen Kubernetes Operator (TimesTen Operator) installation defines the TimesTenClassic and the TimesTenScaleout object types to the Kubernetes cluster. An object of type TimesTenClassic describes the metadata for an active standby pair of TimesTen databases using TimesTen Classic. An object of type TimesTenScaleout describes the metadata for a TimesTen grid and a TimesTen database within the grid using TimesTen Scaleout. You can create as many of these TimesTenClassic and TimesTenScaleout objects as you like.

The definition of the TimesTenClassic and the TimesTenScaleout object types use the same basic format that the formal Kubernetes documentation uses to define objects that are built-in to Kubernetes. The facilities available in any given Kubernetes cluster depend on what release of Kubernetes the cluster is using. For information on the Kubernetes API documentation, see:

https://kubernetes.io/docs/reference/kubernetes-api/

The Kubernetes API reference documentation refers to a number of built-in Kubernetes types used in the definition of the TimesTenClassic and the TimesTenScaleout object types. A Kubernetes StatefulSet is of particular importance. The TimesTenClassic and the TimesTenScaleout object types are basically a wrapper around a StatefulSet type. For more information, see:

https://kubernetes.io/docs/reference/kubernetes-api/



All of the metadata is passed from the object to the StatefulSet.

About the TimesTenClassic Object Type

The definition of the TimesTenClassic object type uses the following object definitions:

- TimesTenClassic
- TimesTenClassicSpec
- TimesTenClassicSpecSpec
- TimesTenClassicSpecSpecPrometheus
- TimesTenClassicStatus

TimesTenClassic

An object of type TimesTenClassic describes the metadata for an active standby pair of TimesTen databases in TimesTen Classic.

The following table describes the syntax for the TimesTenClassic object type:

Table 17-1 TimesTenClassic syntax

Field	Туре	Description
apiVersion	string	Versioned schema of this representation of an object.
		The value must be $timesten.oracle.com/v1$.
kind	string	Type of object (in this example, TimesTenClassic).
metadata	ObjectMeta	Metadata about the object, such as its name. For information on ObjectMeta, see:
		https://kubernetes.io/docs/reference/kubernetes-api/
spec	TimesTenClassicSpec	Desired configuration of the TimesTen Pods and databases.
status	TimesTenClassicStatus	Current status of the Pods in this TimesTenClassic object as well as the status of various TimesTen components within those Pods. This data may be out of date by some window of time.

TimesTenClassicSpec

TimesTenClassicSpec appears in TimesTenClassic. The following table describes the syntax for TimesTenClassicSpec:

Table 17-2 TimesTenClassicSpec syntax

Field	Туре	Description
ttspec	TimesTenClassicSpecSpec	TimesTen specific attributes.



Table 17-2 (Cont.) TimesTenClassicSpec syntax

Field	Туре	Description
template	PodTemplateSpec	Describes the Pods provisioned for the TimesTenClassic object. In addition to Pods specified by template, there are the tt and daemonlog containers that are automatically included in each Pod. TimesTen runs in the tt container. If you configure and use Prometheus, the exporter container is also included. For information on PodTemplateSpec, see:
		https://kubernetes.io/docs/reference/kubernetes-api/
volumeClaimTemplates PersistentVolumeClaim	TimesTen automatically provisions PersistentVolumeClaims (PVCs) for /tt (and for /ttlog, if specified). If you have applications that are running in containers in the TimesTen Pods, and those applications require additional PVCs, specify them in this field. For information on PersistentVolumeClaim, see:	
		https://kubernetes.io/docs/reference/kubernetes-api/

TimesTenClassicSpecSpec

TimesTenClassicSpecSpec appears in TimesTenClassicSpec.

The following table describes the syntax for TimesTenClassicSpecSpec. There are some fields of type quantity. The specified value is of the same format as Kubernetes resource limits. For example, 200Gi, 200G, 1000Mi, 1000M, and so on.



There are datum that are reserved for internal use and are not documented in this table. The names of these datum typically begin with zz. For example, zzTestInfo is reserved for internal use.

Table 17-3 TimesTenClassicSpecSpec syntax

Field	Туре	Description
additionalMemoryRequest	quantity	The amount of memory to request in addition to whatever is required for the TimesTen database.
		This memory is used for the TimesTen daemon, subdaemons, agents, and the Client/Server server.
		This value is added to databaseMemorySize that was either specified by you or calculated. The sum is the memory request to Kubernetes.
		The default is 2Gi.
agentAsyncTimeout	integer	At times the TimesTen Operator needs to perform operations on a TimesTen instance or database. When the TimesTen Operator needs to perform such operations, it asks the TimesTen Agent running in the tt container of the appropriate Pod to perform the operation. The Agent issues TimesTen commands and utilities and, using the TimesTen ttlsql utility, runs SQL operations on the appropriate instance or database.
		The Agent runs the operation either synchronously (while the TimesTen Operator waits) or asynchronously (while the TimesTen Operator is not waiting and can perform other operations for other TimesTen objects).
		The only operation that is performed asynchronously is duplicate, where a TimesTen Classic database is copied from the active Pod to the standby Pod. This is done as part of the initial rollout of an active standby pair, and at various times during its lifecycle.
		These duplicate operations can take a long time, and the amount of time increases as the size of the database increases. If an asynchronous operation does not complete within agentAsyncTimeout seconds, the TimesTen Operator decides that it has failed and acts accordingly.
		If your database is large, you may need to increase the default value for agentAsyncTimeout.
		The default is 600 and is expressed in seconds.



Table 17-3 (Cont.) TimesTenClassicSpecSpec syntax

Field	Туре	Description
agentGetTimeout	integer	Time in seconds that the TimesTen Operator waits for an https GET request to be processed by the TimesTen agent. This includes the TCP and the TLS times as well as the time it takes for the TimesTen agent to implement the GET request. The default is 60. A value of 0 indicates
		that there is no timeout. If the timeout is exceeded, the TimesTen Operator considers the agent to be down.
agentPostTimeout	integer	Time in seconds that the TimesTen Operator waits for an https POST request to be processed by the TimesTen agent. This includes the TCP and the TLS times as well as the time it takes for the TimesTen agent to implement the POST request. The POST requests may take a long time and the time may be proportional to the size of the database. (An example is a POST request to duplicate a database from the active to the standby.)
		The default is 600. A value of 0 indicates that there is no timeout. If the timeout is exceeded, the TimesTen Operator considers the POST request to have failed.
agentTcpTimeout	integer	Time in seconds that the TimesTen Operator waits for a TCP handshake when communicating with the TimesTen agent. The default is 10. A value of 0 indicates that there is no timeout. If the timeout is exceeded, the TimesTen Operator considers the agent to be down.
agentTlsTimeout	integer	Time in seconds that the TimesTen Operator waits for a TLS (https) credential exchange when communicating with the TimesTen agent. The default is 10. A value of 0 indicates that there is no timeout. If the timeout is exceeded, the TimesTen Operator



Table 17-3 (Cont.) TimesTenClassicSpecSpec syntax

Field	Туре	Description
automaticMemoryRequests	boolean	Determines if the TimesTen Operator attempts to set appropriate memory limits and requests for TimesTen Pods.
		 Valid values: true (default): The TimesTen Operator attempts to set memory limits and requests. false: The TimesTen Operator does not set memory limits and requests.
bothDownBehavior	string	If the TimesTenClassic object enters the BothDown state, the TimesTen Operator examines the bothDownBehavior setting to determine what to do. Acceptable values are Best (default) or Manual. See BothDown.
cacheCleanup	boolean	Determines if the metadata in the Oracle Database should be cleaned up when this TimesTenClassic object is deleted. Use for TimesTen Cache only.
		 Valid values: true (or not specified): The metadata is cleaned up. false: The metadata is not cleaned up. See Dropping Oracle Database Objects Used by Cache Groups with Autorefresh
		in the <i>Oracle TimesTen In-Memory</i> Database Cache Guide.
daemonLogCPURequest	quantity	The amount of CPU requested for the daemonlog container.
		The default is 200m (one-fifth of a CPU).
daemonLogMemoryRequest	quantity	The amount of memory requested for the daemonlog container.
		The default is 200Mi.
daemonLogSidecar	boolean	Determines if a daemon log container is created in each TimesTen Pod. This container writes the TimesTen daemon logs (from ttmesg.log) to stdout. This causes Kubernetes to record these logs. Valid values:
		 true (or not specified): A daemon log container is created. false: A daemon log container is not created.



Table 17-3 (Cont.) TimesTenClassicSpecSpec syntax

Field	Туре	Description
databaseCPURequest	quantity	Specify this value to tell the TimesTen Operator how much CPU your tt containers require. This includes CPU used by the TimesTen daemon, subdaemons, replication agents, cache agents, and the Client/Server server. There is no default.
databaseMemorySize	quantity	You can specify this value to tell the TimesTen Operator how much shared memory your database requires. If you specify a value, that value will be used. If you do not specify a value, the TimesTen Operator attempts to determine the required size from the provided db.ini file.
		If the TimesTen Operator cannot determine the database size, the value 580911104 is used. This is the size required for a default database with a PermSize of 200Mbyte, rounded up to 2Mi. This may be useful for experimentation, but is likely insufficient for production purposes.
		TimesTen recommends that you provide a db.ini file to the TimesTen Operator by using a Configmap or Secret, and that you not specify databaseMemorySize.

Note:

If you provide a db.ini file by using an init container, you must specify database MemorySi ze.



Table 17-3 (Cont.) TimesTenClassicSpecSpec syntax

Field	Туре	Description
dbConfigMap	array of strings	Name of one or more ConfigMaps to be included in a projected volume. This projected volume is mounted as / ttconfig in the TimesTen containers. If you do not specify dbConfigMap or dbSecret, you must place the metadata files into the /ttconfig directory by using other means. See Populate the /ttconfig Directory.
dbSecret	array of strings	Name of one or more Secrets to be included in a projected volume. This projected volume is mounted as / ttconfig in the TimesTen containers. If you do not specify dbSecret or dbConfigMap, you must place the metadata files into the /ttconfig directory by using other means. See Populate the /ttconfig Directory.
exporterCPURequest	quantity	The amount of CPU requested for the exporter container (if provisioned). The default is 200m (one-fifth of a CPU).
exporterMemoryRequest	quantity	The amount of memory requested for
enporternemory nequest	quantity	the exporter container (if provisioned).
		The default is 200Mi.
image	string	Name of the TimesTen image that is executed in the created containers.
		There is no default. You must specify the name of the image.
imagePullPolicy	string	Determines if and when Kubernetes pulls the TimesTen image from the image repository. Valid values: Always IfNotPresent (default) Never Note: Values are case sensitive.
imagePullSecret	string	Image pull secret that is used to authenticate and give permission to Kubernetes to fetch the specified TimesTen image from its image repository. There is no default. You must specify the name of the image pull secret.



Table 17-3 (Cont.) TimesTenClassicSpecSpec syntax

Field	Туре	Description
imageUpgradeStrategy	string	Determines if the TimesTen Operator performs automated upgrades. Valid values: Auto (or not specified): The TimesTen Operator performs automated upgrades. Manual: The TimesTen Operator does not perform an automated upgrade. Values are case sensitive. See Perform Upgrades.
logStorageClassName	string	Name of the storage class that is used to request persistent volumes for the TimesTen database transaction log files. This field is optional.
logStorageSelector	metav1.LabelSelector	When choosing to use a persistent volume to store the TimesTen transaction logs, the primary determinant of what volumes to use is the logStorageClassName datum that you specify. You can optionally specify a label selector by using the logStorageSelector datum. This label selector further filters the set of volumes. See:
		https://kubernetes.io/docs/ concepts/storage/persistent- volumes/#selector
logStorageSize	string	Amount of storage to be provisioned for the TimesTen transaction logs. For information on determining the amount of storage needed for the transaction log files, see Storage Provisioning for TimesTen in the Oracle TimesTen In- Memory Database Operations Guide
		The default is 50Gi. This default value may be suitable when you are experimenting with the product or using it for demonstration purposes. However, in a production environment, consider choosing a value greater than 50Gi. The examples in this book assume a production environment and use a value of 250Gi.



Table 17-3 (Cont.) TimesTenClassicSpecSpec syntax

Field	Туре	Description
memoryWarningPercent	integer	At runtime, if a container's memory usage is more than its percentage of its limit (both as reported by cgroups), the TimesTen Operator generates Events to inform you of this occurrence.
		The memory usage refers to the container's memory allocation.
		The default is 90.
pollingInterval	integer	Determines how often (expressed in seconds) that the TimesTen Operator checks the status of the TimesTenClassic active standby pair object. For example, if you set this value to 10, the TimesTen Operator checks the status of the TimesTenClassic object every ten seconds. This value interacts with unreachableTimeout. The pollingInterval value should be smaller than the unreachableTimeout value.
		The value must be a positive integer (greater than 0). The default is 5.
prometheus	TimesTenClassicSpecSpecPr ometheus	Determines if the TimesTen Exporter is deployed. If specified, the Exporter is deployed. The datum for the prometheus object are defined in TimesTenClassicSpecSpecPrometheus.
reexamine	string	When a TimesTenClassic object is in the ManualInterventionRequired state, the TimesTen Operator examines the reexamine value every pollingInterval seconds. If the value has changed since the last iteration for this object, the TimesTen Operator examines the state of the TimesTen containers for this object. See About the ManualInterventionRequired State and About Bringing Up One Database.



Table 17-3 (Cont.) TimesTenClassicSpecSpec syntax

Field	Туре	Description
repCreateStatement	string	The repReturnServiceAttribute and the repStoreAttribute datum provide some control over the CREATE ACTIVE STANDBY statement that you use to configure your active standby pai replication scheme. However, these datum do not provide a mechanism to set all the replication options. The repCreateStatement datum provides more control over the active standby pair replication configuration. If you choose to define a replication scheme, you must choose either the repCreateStatement approach or the repReturnServiceAttribute and the repStoreAttribute approach. You cannot use both approaches simultaneously in a single TimesTenClassic object definition. For example, you cannot use the repCreateStatement datum and the repReturnServiceAttribute datum in a single TimesTenClassic object definition. However, you can use the repReturnServiceAttribute and the repStoreAttribute datum in a
		single TimesTenClassic object definition. Example of using the repCreateStatement datum: apiVersion: timesten.oracle.com/v1
		<pre>kind: TimesTenClassic metadata: name: sample spec:</pre>
		<pre>ttspec: repCreateStatement: create active standby pair "{{tt-name}}" on "{{tt-</pre>
		<pre>node-0}}", "{{tt-name}}" on "{{tt- node-1}}" RETURN TWOSAFE</pre>
		store "{{tt-name}}" on "{{tt-node-0}}" PORT {{tt-rep-port}} FAILTHRESHOLD 10 TIMEOUT 5
		DISABLE RETURN ALL 10 store "{{tt-name}}" on "{{tt-node-1}}"
		PORT {{tt-rep-port}} FAILTHRESHOLD 10 TIMEOUT 5 DISABLE RETURN ALL 10

Table 17-3 (Cont.) TimesTenClassicSpecSpec syntax

Field	Type	Description
1 1014	1,000	Description

The TimesTen Operator does the substitutions for you.

- {{tt-name}}: The name of the TimesTenClassic object. (For example, sample.)
- {{tt-node-0}}}: The fully qualified DNS name of the -0 Pod for the TimesTenClassic object. (For example,
 - sample-0.sample.mynamespace
 .svc.cluster.local.)
- {{tt-node-1}}: The fully qualified DNS name of the -1 Pod for the TimesTenClassic object. (For example,
 - sample-1.sample.mynamespace
 .svc.cluster.local.)
- {{tt-rep-port}}: The TCP port either chosen by the TimesTen Operator or specified in the repPort datum.

When you use the

repCreateStatement datum, you have nearly complete control over the replication configuration. The TimesTen Operator executes the statement you define (after substituting a number of values into it). Since the TimesTen Operator is using the CREATE statement that you define, ensure that the statement you specify is correct and appropriate. If the creation of your active standby pair replication scheme fails, your TimesTenClassic object transitions from the Initializing state to the Failed state. You must then delete the TimesTenClassic object to clean up the resources it holds. See About Monitoring the Health of an Active Standby Pair of Databases.

The configuration has the following restrictions:

- Must be an active standby pair.
- Must not be configured with subscribers.

See CREATE ACTIVE STANDBY PAIR in the Oracle TimesTen In-Memory Database SQL Reference and Defining an Active Standby Pair Replication Scheme in the Oracle TimesTen In-Memory Database Replication Guide.



Table 17-3 (Cont.) TimesTenClassicSpecSpec syntax

Field	Туре	Description
replicationCipherSuite	string	Determines the encryption algorithm to be used by TimesTen replication. If specified, replication traffic is encrypted.
		You can specify one or more values. Possible values include the following:
		• SSL_ECDHE_ECDSA_WITH_AES_12 8 GCM SHA256
		• SSL_ECDHE_ECDSA_WITH_AES_25 6 GCM_SHA384
		See About Using Certificates with Client/Server in the <i>Oracle TimesTen In-Memory Database Security Guide</i> for more information.
replicationSSLMandatory	integer	Determines if SSL encryption is mandatory for replication.
		Valid values:
		 0 (or not specified): SSL encryption is not mandatory for replication. 1: SSL encryption is mandatory for replication.
		This value is only examined if replicationCipherSuite is specified.
		See About Using Certificates with Client/Server in the <i>Oracle TimesTen In-Memory Database Security Guide</i> for more information.
repPort	integer	TCP port used for replication. The default is 4444.



Table 17-3 (Cont.) TimesTenClassicSpecSpec syntax

Field	Туре	Description
repReturnServiceAttribute	string	You can use the repReturnServiceAttribute datum to specify the ReturnServiceAttribute clause. This clause is part of the syntax for the CREATE ACTIVE STANDBY PAIR statement. The information you specify is included in your active standby pair's CREATE ACTIVE STANDBY PAIR statement by the TimesTen Operator. Do not specify the repReturnServiceAttribute datum if you have specified the repCreateStatement datum. If you do not specify the repReturnServiceAttribute datum (or the repCreateStatement datum), the default is NO RETURN. See CREATE ACTIVE STANDBY PAIR in the Oracle TimesTen In-Memory Database SQL Reference and Defining an Active Standby Pair Replication Scheme in the Oracle TimesTen In-Memory Database Replication Guide for information on the CREATE ACTIVE STANDBY PAIR statement and the
Q1 1 T'		ReturnServiceAttribute clause.
repStateTimeout	integer	Time in seconds a replicated database remains in the recovering replication state as reported by the TimesTen ttRepStateGet built-in procedure. The recovering replication state indicates the database is in the process of synchronizing updates with the active database after a failure. See ttRepStateGet in the Oracle TimesTen In-Memory Database Reference. The default is 30.



Table 17-3 (Cont.) TimesTenClassicSpecSpec syntax

Field	Туре	Description
repStoreAttribute	string	You can use the repStoreAttribute datum to specify the StoreAttribute clause. This clause is part of the CREATE ACTIVE STANDBY PAIR statement. The information you specify is included in your active standby pair's CREATE ACTIVE STANDBY PAIR statement by the TimesTen Operator. Do not specify the repStoreAttribute datum if you have specified the repCreateStatement datum. If you do not specify the repStoreAttribute datum (or the repCreateStatement datum), the default is: PORT repPort FAILTHRESHOLD 0.
		If you specify the repStoreAttribute, you must specify the port. This port is used by replication. The port must match the port provided in the repPort datum (or must match the default value if repPort is not specified). If the ports do not match, the TimesTenClassic object enters the Failed state.
		See CREATE ACTIVE STANDBY PAIR in the Oracle TimesTen In-Memory Database SQL Reference and Defining an Active Standby Pair Replication Scheme in the Oracle TimesTen In-Memory Database Replication Guide for information on the CREATE ACTIVE STANDBY PAIR statement and the StoreAttribute clause.
resetUpgradeState	string	The resetUpgradeState datum allows an online upgrade to be canceled.
stopManaging	string	If you change the value of stopManaging for the TimesTenClassic object, the TimesTen Operator places the object in the ManualInterventionRequired state. See About the ManualInterventionRequired State and About Bringing Up One Database.
storageClassName	string	Name of the storage class that is used to request persistent volumes for the TimesTen database.



Table 17-3 (Cont.) TimesTenClassicSpecSpec syntax

Field	Туре	Description
storageSelector	metav1.LabelSelector	When choosing to use a persistent volume to store a TimesTen database, the primary determinant of what volumes to use is the StorageClassName that you specify. You can optionally specify a label selector by using the storageSelector field. This label selector further filters the set of volumes. See:
		https://kubernetes.io/docs/ concepts/storage/persistent- volumes/#selector
storageSize	string	Amount of storage to be provisioned for TimesTen and the database. For information on determining the amount of storage needed for TimesTen, see Storage Provisioning for TimesTen in the Oracle TimesTen In-Memory Database Operations Guide.
		The default is 50Gi. This default value may be suitable when you are experimenting with the product or using it for demonstration purposes. However, in a production environment, consider choosing a value greater than 50Gi. The examples in this book assume a production environment and use a value of 250Gi.
unreachableTimeout	integer	Number of seconds that a TimesTen instance or TimesTen database is unavailable before the TimesTen Operator takes action to fail over or otherwise recover from the issue.
		This value interacts with pollingInterval. The pollingInterval value should be smaller than the unreachableTimeout value.
		The value must be a positive integer (greater than 0). The default is 30.



Table 17-3 (Cont.) TimesTenClassicSpecSpec syntax

Field	Туре	Description
upgradeDownPodTimeout	integer	Maximum amount of seconds that the TimesTenClassic object remains in the WaitingForActive state. After this period of time, if the TimesTenClassic object is still in the WaitingForActive state, it transitions to the ManualInterventionRequired state.
		The default is 0 (which means there is no timeout. The TimesTenClassic object waits forever, if required).
		For information on the WaitingForActive and the ManualInterventionRequired states, see About Monitoring the Health of an Active Standby Pair of Databases.

Times Ten Classic Spec Spec Prometheus

TimesTenClassicSpecSpecPrometheus appears in TimesTenClassicSpecSpec. The following table describes the syntax for TimesTenClassicSpecSpecPrometheus.

Table 17-4 TimesTenClassicSpecSpecPrometheus syntax

Field	Туре	Description
certSecret	string	When using https to serve TimesTen metrics, a Kubernetes Secret is required.
		If you create your own Kubernetes Secret, use the certSecret datum to specify the name of this Secret. This Secret contains an Oracle Wallet that holds the necessary certificates used by the TimesTen exporter for serving TimesTen metrics by https. See Create Your Own Oracle Wallet, Certificates, and Secrets for Exposing TimesTen Metrics.
		If you want the TimesTen Operator to automatically create an Oracle Wallet, certificates, and Kubernetes Secrets that are required for https, do not specify the certSecret datum. We recommend this approach. See About Transport Layer Security (mutual TLS) Certificates for TimesTen Metrics.



Table 17-4 (Cont.) TimesTenClassicSpecSpecPrometheus syntax

Field	Туре	Description
createPodMonitors	boolean	Determines if the TimesTen Kubernetes Operator creates PodMonitors.
		Valid values:
		 true (or not specified): The TimesTen Operator creates PodMonitors.
		 false: The TimesTen Operator does not create PodMonitors.
		See Expose TimesTen Metrics with the TimesTen Kubernetes Operator.
insecure	boolean	Determines if the TimesTen exporter is started with no authentication or with Transport Layer Security (mutual TLS).
		Valid values:
		 true: The TimesTen exporter is started with no authentication and serves data by http.
		 false (or not specified): The TimesTen exporter is started with mutual TLS and serves data by https.
		For more information, see About Using http or https for TimesTen Metrics.
		For information about the TimesTen exporter, see About the TimesTen exporter in the <i>Oracle TimesTen In-Memory Database Monitoring and Troubleshooting Guide</i> .
limitRate	integer	Determines the limit of GET requests per minute that the TimesTen exporter accepts. The value can be any integer value from 1 to 15.
		The default is 10.
port	integer	Port on which the TimesTen exporter listens. The default is 8888.



Table 17-4 (Cont.) TimesTenClassicSpecSpecPrometheus syntax

Field	Туре	Description
publish	boolean	Determines if the TimesTen Operator provisions a TimesTen exporter container. Valid values:
		 true (or not specified): The TimesTen Operator provisions a TimesTen exporter container. false: The TimesTen Operator does not provision a TimesTen exporter container. If you do not specify the publish datum, and any other datum is specified in the .spec.ttspec.prometheus clause, the default value for the publish datum is true. If you do not specify
		the .spec.ttspec.prometheus clause and the TimesTen release is 22.1 or greater, the default value for the publish datum is dependent on the value of the EXPOSE_METRICS TimesTen Operator environment variable: If EXPOSE_METRICS is "1" (or not specified), the TimesTen Operator treats the publish datum as true. If EXPOSE_METRICS is "0", the TimesTen Operator treats the publish datum as false.
		For more information, see Expose TimesTen Metrics with the TimesTen Kubernetes Operator and TimesTen Kubernetes Operator Environment Variables.

TimesTenClassicStatus

TimesTenClassicStatus appears in TimesTenClassic. The Operator stores various persistent information in TimesTenClassicStatus.

The output of the kubectl get and kubectl describe commands display information in TimesTenClassicStatus. This information includes the following:

- awtBehindMb: a field that is present only if AWT (Asynchronous WriteThrough) is in use. The field represents how many megabytes of log is present in TimesTen that has not yet been pushed to Oracle Database. For more information on AWT cache group, see Overview of Cache Groups in the *Oracle TimesTen In-Memory Database Cache Guide*.
- High Level state of the Active Standby Pair: a string that describes the High Level state of the active standby pair.
- Detailed state of TimesTen in each Pod, which includes the following:



- Is the TimesTen agent running?
- Is the TimesTen main daemon running?
- Is the TimesTen replication agent running?
- Is the TimesTen cache agent running?
- Is there a database in the instance?
- Is the database loaded?
- Is the database updatable or read only?
- Is there a replication scheme in the database?
- What is the replication state of this database?
- What does this database think the replication state of its peer is?
- What is the role for TimesTen in this Pod (active or standby)?
- What is the High Level state of the Pod?



Unknown values can occur if, for example, the agent is not running or a Pod is unavailable.

About the TimesTenScaleout Object Type

The TimesTenScaleout object type is defined using the following object definitions:

- TimesTen Scaleout
- TimesTenScaleoutSpec
- TimesTenScaleoutSpecSpec
- TimesTenScaleoutSpecSpecPrometheus
- TimesTenScaleoutStatus

TimesTen Scaleout

An object of type TimesTenScaleout describes the metadata for a TimesTen grid and the TimesTen database within the grid in TimesTen Scaleout.

The following table describes the syntax for the TimesTenScaleout object type:

Table 17-5 TimesTenScaleout syntax

Field	Туре	Description
apiVersion	string	Versioned schema of this representation of an object.
		The value must be timesten.oracle.com/v1.



Table 17-5 (Cont.) TimesTenScaleout syntax

Field	Туре	Description
kind	string	Type of object (in this example, TimesTenScaleout).
metadata	ObjectMeta	Metadata about the object, such as its name. For information on ObjectMeta, see:
		<pre>https://kubernetes.io/docs/reference/ kubernetes-api/</pre>
spec	TimesTenScaleoutSpec	Desired configuration of the TimesTen Scaleout grid and the databases within the grid.
status	TimesTenScaleoutStatus	Current status of the Pods in this TimesTenScaleout object as well as the status of various TimesTen components within those Pods. This data may be out of date by some window of time.

TimesTenScaleoutSpec

TimesTenScaleoutSpec appears in TimesTenScaleout. The following table describes the syntax for TimesTenScaleoutSpec:

Table 17-6 TimesTenScaleoutSpec syntax

Field	Туре	Description
ttspec	TimesTenScaleoutSpecSpec	Specific TimesTen attributes for deploying a grid in TimesTen Scaleout.
dataTemplate	Array of PodTemplateSpec	Array of specifications for the Pods that contain the TimesTen Scaleout data instances. This field is optional. If specified, there must be k entries in the array. Each entry is the template for the Pods in a different data space. For example, if k is set to 2, then the first entry is for data space 1, and the second entry is for data space 2. Use dataTemplate to pass affinity and other settings to Kubernetes. For information about PodTemplateSpec, see:
		https://kubernetes.io/docs/ reference/kubernetes-api/
dataVolumeClaimTemplate s	Array of arrays of PersistentVolumeClaim	Array of arrays of Volume Claim Templates to be added to just the data instance Pods. There is one list (of lists) per data space.
mgmtTemplate	PodTemplateSpec	Specification for the Pod that contains the TimesTen Scaleout management instance. Use mgmtTemplate to pass affinity and other settings to Kubernetes. For information about PodTemplateSpec, see:
		https://kubernetes.io/docs/ reference/kubernetes-api/



Table 17-6 (Cont.) TimesTenScaleoutSpec syntax

Field	Туре	Description
mgmtVolumeClaimTemplate s	Array of PersistentVolumeClaim	Array of Volume Claim Templates to be added to just the management instance Pod.
volumeClaimTemplates	PersistentVolumeClaim	TimesTen automatically provisions PersistentVolumeClaims (PVCs) for /tt (and for /ttlog, if specified). If you have applications that are running in containers in the TimesTen Pods, and those applications require additional PVCs, specify them in this field. For information on PersistentVolumeClaim, see:
		https://kubernetes.io/docs/reference/kubernetes-api/
zookeeperTemplate	Array of PodTemplateSpec	Specification for the Pods that contains the TimesTen Scaleout ZooKeeper instances. Use zookeeperTemplate to pass affinity and other settings to Kubernetes. For information about PodTemplateSpec, see:
		https://kubernetes.io/docs/reference/kubernetes-api/
zookeeperVolumeClaimTem plates	Array of PersistentVolumeClaim	Array of Volume Claim Templates to be added to just the ZooKeeper Pods.

TimesTenScaleoutSpecSpec

TimesTenScaleoutSpecSpec appears in TimesTenScaleoutSpec.

The following table describes the syntax for TimesTenScaleoutSpecSpec. There are some fields of type quantity. The specified value is of the same format as Kubernetes resource limits. For example, 200Gi, 200G, 1000Mi, 1000M, and so on.



There are datum that are reserved for internal use and are not documented in this table. The names of these datum typically begin with zz. For example, zzTestInfo is reserved for internal use.



Table 17-7 TimesTenScaleoutSpecSpec

Field	Туре	Description
additionalMemoryRequest	quantity	The amount of memory to request in addition to whatever is required for an element of the TimesTen database.
		This memory is used for the TimesTen daemon, subdaemons, agents, and the Client/Server server.
		This value is added to databaseMemorySize that was either specified by you or calculated. The sum is the memory request to Kubernetes.
		The default is 2Gi.
agentGetTimeout	integer	Time in seconds that the Operator waits for an https GET request to be processed by the TimesTen agent. This includes the TCP and the TLS times as well as the time it takes for the TimesTen agent to implement the GET request.
		The default is 60. A value of 0 indicates that there is no timeout. If the timeout is exceeded, the Operator considers the agent to be down.
agentPostTimeout	integer	Time in seconds that the Operator waits for an https POST request to be processed by the TimesTen agent. This includes the TCP and the TLS times as well as the time it takes for the TimesTen agent to implement the POST request. The POST requests may take a long time and the time may be proportional to the size of the database. (An example is a POST request to duplicate a database from the active to the standby.)
		The default is 600. A value of 0 indicates that there is no timeout. If the timeout is exceeded, the Operator considers the POST request to have failed.
agentTcpTimeout	integer	Time in seconds that the Operator waits for a TCP handshake when communicating with the TimesTen agent.
		The default is 10. A value of 0 indicates that there is no timeout. If the timeout is exceeded, the Operator considers the agent to be down.



Table 17-7 (Cont.) TimesTenScaleoutSpecSpec

Field	Туре	Description
agentTlsTimeout	integer	Time in seconds that the Operator waits for a TLS (https) credential exchange when communicating with the TimesTen agent.
		The default is 10. A value of 0 indicates that there is no timeout. If the timeout is exceeded, the Operator considers the agent to be down.
automaticMemoryRequests	boolean	Determines if the Operator attempts to set appropriate memory limits and requests for TimesTen Pods.
		 Valid values: true (default): The Operator attempts to set memory limits and requests.
		 false: The Operator does not set memory limits and requests.
cacheCleanup	boolean	Determines if the metadata in the Oracle Database should be cleaned up when this TimesTenClassic object is deleted. Use for TimesTen Cache only.
		Valid values:
		 true (or not specified): The metadata is cleaned up. false: The metadata is not
		cleaned up. See Dropping Oracle Database Objects Used by Cache Groups with Autorefresh in the Oracle TimesTen In-Memory Database Cache Guide.
daemonLogCPURequest	quantity	The amount of CPU requested for the daemonlog container.
		The default is $200\mbox{m}$ (one-fifth of a CPU).
daemonLogMemoryRequest	quantity	The amount of memory requested for the daemonlog container.
		The default is 200Mi.
daemonLogSidecar	boolean	Determines if a daemon log container is created in each TimesTen Pod. This container writes the TimesTen daemon logs (from ttmesg.log) to stdout. This causes Kubernetes to record these logs. Valid values:
		 true (or not specified): A daemon log container is created. false: A daemon log container is not created.



Table 17-7 (Cont.) TimesTenScaleoutSpecSpec

Field	Туре	Description
databaseCPURequest	Quantity	Specify this value to tell the Operator how much CPU your tt containers require. This includes CPU used by the TimesTen daemon, subdaemons, replication agents, cache agents, and the Client/Server server.
		There is no default.
databaseMemorySize	Quantity	You can specify this value to tell the Operator how much shared memory an element of your database requires.
		If you specify a value, that value will be used. If you do not specify a value, the Operator attempts to determine the required size from the provided db.ini file.
		If the Operator cannot determine the database size, the value 580911104 is used. This is the size required for a default database with a PermSize of 200Mbyte, rounded up to 2Mi. This may be useful for experimentation, but is likely insufficient for production purposes.
		TimesTen recommends that you provide a db.ini file to the Operator by using a Configmap or Secret, and that you not specify databaseMemorySize.
		Note: If you provide a db.ini file by using an init container, you must specify database MemorySi ze.
dataStorageClassName	string	Name of the storage class that is used to request persistent volumes for the elements of the TimesTen database in the grid. If not specified, the default is the value of storageClassName.

Table 17-7 (Cont.) TimesTenScaleoutSpecSpec

Field	Туре	Description
dataStorageSelector	metav1.LabelSelector	When choosing to use a persistent volume to store the elements of a TimesTen database in the grid, the primary determinant of what volumes to use is the dataStorageClassName that you specify. You can optionally specify a label selector by using the dataStorageSelector field. This label selector further filters the set of volumes. See:
		https://kubernetes.io/docs/ concepts/storage/persistent- volumes/#selector
dataStorageSize	string	Amount of storage to be provisioned for each element of the TimesTen database in the grid.
		The default is 50Gi. This default value may be suitable when you are experimenting with the product or using it for demonstration purposes. However, in a production environment, consider choosing a value greater than 50Gi. The examples in this book assume a production environment and use a value of 250Gi.
dbConfigMap	array of strings	Name of one or more ConfigMaps to be included in a projected volume. This projected volume is mounted as / ttconfig in the TimesTen containers. If you do not specify dbConfigMap or dbSecret, you must place the metadata files into the /ttconfig directory by using other means. See Populate the /ttconfig Directory.
dbSecret	array of strings	Name of one or more Secrets to be included in a projected volume. This projected volume is mounted as / ttconfig in the TimesTen containers. If you do not specify dbSecret or dbConfigMap, you must place the metadata files into the /ttconfig directory by using other means. See Populate the /ttconfig Directory.
exporterCPURequest	quantity	The amount of CPU requested for the exporter container (if provisioned). The default is 200m (one-fifth of a CPU).
exporterMemoryRequest	quantity	The amount of memory requested for the exporter container (if provisioned). The default is 200Mi.



Table 17-7 (Cont.) TimesTenScaleoutSpecSpec

Field	Туре	Description
image	string	Name of the TimesTen image that is executed in the created containers.
		There is no default. You must specify the name of the image.
imagePullPolicy	string	Determines if and when Kubernetes pulls the TimesTen image from the image repository.
		Valid values:
		• Always
		 IfNotPresent (default)
		• Never
		Note: Values are case sensitive.
imagePullSecret	string	Image pull secret that is used to authenticate and give permission to Kubernetes to fetch the specified TimesTen image from its image repository.
		There is no default. You must specify the name of the image pull secret.
k	integer	K-Safety value for this TimesTen grid. This value determines the number of copies of data for your TimesTen database. This value also determines the number of StatefulSets that the TimesTen Operator creates. A StatefulSet provides the Pods that are used to implement a single data space in the grid. For example, if you set k to 2, the Operator creates two StatefulSets. One StatefulSet provides the Pods for the data instances in data space one. The second StatefulSet provides the Pods for the data instances in data space two. The Operator also creates a StatefulSet for the management instance and a StatefulSe for ZooKeeper.
		For more information on K-Safety, see K-Safety in the <i>Oracle TimesTen In-Memory Database Scaleout User's Guide</i> .
logStorageClassName	string	Name of the storage class that is used to request persistent volumes for the TimesTen database transaction log files This field is optional and is valid only for data instances.



Table 17-7 (Cont.) TimesTenScaleoutSpecSpec

Field	Туре	Description
logStorageSelector	metav1.LabelSelector	When choosing to use a persistent volume to store the TimesTen transaction log files, the primary determinant of what volumes to use is the logStorageClassName that you specify. You can optionally specify a label selector by using the logStorageSelector field. This label selector further filters the set of volumes. Valid only for data instances. See: https://kubernetes.io/docs/concepts/storage/persistent-volumes/#selector
logStorageSize	string	Amount of storage to be provisioned for the TimesTen transaction log files. This value is for each element of the TimesTen database in the grid. Valid only for data instances.
memoryWarningPercent	integer	At runtime, if a container's memory usage is more than its percentage of its limit (both as reported by cgroups), the Operator generates Events to inform you of this occurrence. The memory usage refers to the container's memory allocation.
		The default is 90.
mgmtCPURequest	quantity	The amount of cpu requested for the tt container of management instances. The default is 1.
mgmtMemoryRequest	quantity	The amount of memory requested for the tt container of management instances. The default is 3Gi.
mgmtStorageClassName	string	Name of the storage class that is used to request persistent volumes for the database of the management instance. If not specified, the default is the value of storageClassName.



Table 17-7 (Cont.) TimesTenScaleoutSpecSpec

Field	Туре	Description
mgmtStorageSelector	metav1.LabelSelector	When choosing to use a persistent volume to store the database of the management instance, the primary determinant of what volumes to use is the mgmtStorageClassName that you specify. You can optionally specify a label selector by using the mgmtstorageSelector field. This label selector further filters the set of volumes. If you do not specify mgmtstorageSelector, the value is the value of StorageSelector. See:
		https://kubernetes.io/docs/ concepts/storage/persistent- volumes/#selector
mgmtStorageSize	string	Amount of storage to be provisioned for the database of the management instance.
		The default is 50Gi.
nReplicaSets	integer	Number of replica sets in the grid. A replica set contains <code>k</code> elements (where each element is an exact copy of the other elements in the replica set). The <code>nReplicaSets</code> value also determines the number of replicas for each StatefulSet. For example, if you set <code>k</code> to 2, the TimesTen Operator creates two StatefulSets for the data instances. If you set <code>nReplicaSets</code> to 3, each StatefulSet contains three replicas, and the total number of replica sets in the grid is three.
		The default is 1.
		For more information on replica sets, see Understanding Replica Sets in the Oracle TimesTen In-Memory Database Scaleout User's Guide.
nZookeeper	integer	Number of ZooKeeper Pods to provision in a StatefulSet. Valid values: 1 3 (default) 5



Table 17-7 (Cont.) TimesTenScaleoutSpecSpec

Field	Туре	Description
pollingInterval	integer	Determines how often (expressed in seconds) that the Operator checks the status of the TimesTenScaleout object. For example, if you set this value to 10, the Operator checks the status of the TimesTenScaleout object every ten seconds. The value must be a positive integer (greater than 0). The default is 5.
prometheus	TimesTenScaleoutSpecSpecP rometheus	Determines if the TimesTen Exporter is deployed. If specified, the Exporter is deployed. The datum for the prometheus object are defined in TimesTenScaleoutSpecSpecPrometheus.
reexamine	string	When a TimesTenScaleout object is in the ManualInterventionRequired state, the Operator examines the reexamine value every pollingInterval seconds. If the value has changed since the last iteration for this object, the Operator reexamines the TimesTenScaleout object and attempts to resume management of the object.
replicaSetRecovery	string	Controls the behavior of the Operator when a total replica set failure occurs. Valid values: Restart (default): The Operator forcibly unloads and reloads the database when a total replica set failure occurs. Manual: The Operator changes the state of the TimesTenScaleout object to ManualInterventionRequired when a total replica set failure occurs.
stopManaging	string	If you change the value of stopManaging for the TimesTenScaleout object, the Operator places the object in the ManualInterventionRequired state.



Table 17-7 (Cont.) TimesTenScaleoutSpecSpec

Field	Туре	Description
storageClassName	string	Name of the storage class that is used to request persistent volumes for the TimesTen database.
		If the value for storageClassName is the same as the value for dataStorageClassName, for mgmtStorageClassName, and for zookeeperStorageClassName, you can just specify storageClassName. In this case, the value for dataStorageClassName, for mgmtStorageClassName, and for zookeeperStorageClassName is set to the value of storageClassName.
storageSelector	metav1.LabelSelector	When choosing to use a persistent volume to store an element of a TimesTen database in a grid, the primary determinant of what volumes to use is the StorageClassName that you specify. You can optionally specify a label selector by using the storageSelector field. This label selector further filters the set of volumes.
		If the value for storageSelector is the same as the value for dataStorageSelector, for mgmtStorageSelector, and for zookeeperStorageSelector, you can just specify storageSelector. In this case, the value for dataStorageSelector, for mgmtStorageSelector, and for zookeeperStorageSelector is set to the value of storageSelector. See:
		https://kubernetes.io/docs/ concepts/storage/persistent- volumes/#selector



Table 17-7 (Cont.) TimesTenScaleoutSpecSpec

Field	Туре	Description
storageSize	string	Amount of storage to be used for each element of a TimesTen database in the grid. If the value for storageSize is the same as the value for dataStorageSize, for mgmtStorageSize, and for zookeeperStorageSize, you can just specify storageSize. In this case, the value for dataStorageSize, for mgmtStorageSize, and for zookeeperStorageSize is set to the value of storageSize. The default is 50Gi.
		For information on determining the amount of storage needed for TimesTen, see Storage Provisioning for TimesTen in the Oracle TimesTen In-Memory Database Operations Guide.
zookeeperCPURequest	quantity	The amount of cpu requested for the zookeeper container of Zookeeper Pods. The default is 500m.
zookeeperMemoryRequest	quantity	The amount of memory requested for the zookeeper container of Zookeeper Pods. The default is 1Gi.
zookeeperStorageClassName	string	Name of the storage class that is used to request persistent volumes for ZooKeeper's persistent data. If not specified, the default is the value of storageClassName.
zookeeperStorageSelector	metav1.LabelSelector	When choosing to use a persistent volume to store ZooKeeper's persistent data, the primary determinant of what volumes to use is the zookeeperStorageClassName that you specify. You can optionally specify a label selector by using the zookeeperStorageSelector field. This label selector further filters the set of volumes. See: https://kubernetes.io/docs/concepts/storage/persistent-
zookeeperStorageSize	string	volumes/#selector Amount of storage to be provisioned for ZooKeeper's persistent data.



TimesTenScaleoutSpecSpecPrometheus

 $\label{thm:continuous} Times Ten Scale out Spec Spec Prometheus \ appears \ in \ \ Times Ten Scale out Spec Spec \ . \ The following \ table \ describes \ the \ syntax \ for \ Times Ten Scale out Spec Spec Prometheus.$

Table 17-8 TimesTenScaleoutSpecSpecPrometheus syntax

Field	Туре	Description
certSecret	string	When using https to serve TimesTen metrics, a Kubernetes Secret is required.
		If you create your own Kubernetes Secret, use the certSecret datum to specify the name of this Secret. This Secret contains an Oracle Wallet that holds the necessary certificates used by the TimesTen exporter for serving TimesTen metrics by https. See Create Your Own Oracle Wallet, Certificates, and Secrets for Exposing TimesTen Metrics.
		If you want the TimesTen Operator to automatically create an Oracle Wallet, certificates, and Kubernetes Secrets that are required for https, do not specify the certSecret datum. We recommend this approach. See About Transport Layer Security (mutual TLS) Certificates for TimesTen Metrics.
createPodMonitors	boolean	Determines if the TimesTen Kubernetes Operator creates PodMonitors.
		Valid values:
		 true (or not specified): The TimesTen Operator creates PodMonitors. false: The TimesTen Operator
		does not create PodMonitors.
		See Expose TimesTen Metrics with the TimesTen Kubernetes Operator for details.



Table 17-8 (Cont.) TimesTenScaleoutSpecSpecPrometheus syntax

Field	Туре	Description
insecure	boolean	Determines if the TimesTen exporter is started with no authentication or with Transport Layer Security (mutual TLS).
		Valid values:
		 true: The TimesTen exporter is started with no authentication and serves data by http.
		 false (or not specified): The TimesTen exporter is started with mutual TLS and serves data by https.
		For more information, see About Using http or https for TimesTen Metrics.
		For information about the TimesTen exporter, see About the TimesTen exporter in the <i>Oracle TimesTen In-Memory Database Monitoring and Troubleshooting Guide.</i>
limitRate	integer	Determines the limit of GET requests per minute that the TimesTen exporter accepts. The value can be any integer value from 1 to 15.
		The default is 10.
port	integer	Port on which the TimesTen exporter listens.
		The default is 8888.



Table 17-8 (Cont.) TimesTenScaleoutSpecSpecPrometheus syntax

Field	Туре	Description
publish	boolean	Determines if the TimesTen Operator provisions a TimesTen exporter container. Valid values:
		 true (or not specified): The TimesTen Operator provisions a TimesTen exporter container. false: The TimesTen Operator does not provision a TimesTen exporter container. If you do not specify the publish datum, and any other datum is specified in the .spec.ttspec.prometheus clause, the default value for the publish datum is true.
		If you do not specify the .spec.ttspec.prometheus clause and the TimesTen release is 22.1 or greater, the default value for the publish datum is dependent on the value of the EXPOSE_METRICS TimesTen Operator environment variable: If EXPOSE_METRICS is "1" (or not specified), the TimesTen Operator treats the publish datum as true. If EXPOSE_METRICS is "0", the TimesTen Operator treats the publish datum as false.
		For more information, see Expose TimesTen Metrics with the TimesTen Kubernetes Operator and TimesTen Kubernetes Operator Environment Variables.

TimesTenScaleoutStatus

TimesTenScaleoutStatus appears in TimesTen Scaleout. The Operator stores various persistent information in TimesTenScaleoutStatus.

The output of the kubectl get and kubectl describe commands display information in TimesTenScaleoutStatus.

The information includes the following:

- High Level state of the TimesTen grid and the database within the grid.
- · Detailed state of TimesTen in each Pod, including:
 - Are the TimesTen agents running?
 - Are the TimesTen daemons running?



- Is there a database in the instance?
- Is the database loaded?
- Is the database updatable or read only?
- What is the High Level state of the Pods?

Note:

Unknown values can occur if, for example, the agent is not running or a Pod is unavailable.



18

Helm Charts for the TimesTen Kubernetes Operator

Helm is the package manager for Kubernetes. The TimesTen Kubernetes Operator (TimesTen Operator) provides Helm charts that allow you to deploy the TimesTen CRDs, TimesTen Operator, and TimesTenClassic objects that the TimesTen Operator manages.

The TimesTen Operator supports the following charts:

- ttcrd: Deploys the TimesTen Custom Resource Definitions (CRDs) into the Kubernetes cluster.
- ttoperator: Deploys the TimesTen Operator.
- ttclassic: Creates a TimesTenClassic object, thus deploying an active standby pair of TimesTen databases.

Each chart contains variables and default values that are specific to the chart. For example, the ttclassic chart contains the variables and default values that are specific to creating and deploying a TimesTenClassic object. You have the option of defining your own values for the variables in the charts. The exception is the ttcrd chart. You cannot change the values of the variables in this chart.

The following sections describe the values and defaults values for the ttoperator and the ttclassic charts:

- The ttoperator Chart
- The ttclassic Chart

For detailed information about using Helm, see Use Helm to Deploy the TimesTen Kubernetes Operator and TimesTenClassic Objects.

The ttoperator Chart

The ttoperator chart deploys the TimesTen Operator.

The following table describes the variables and default values for the ttoperator chart. Indentation and case sensitivity must be correct for each variable.

Table 18-1 Variables for the ttoperator Chart

Variable	Description	Example
affinity	Variable to define Kubernetes nodeAffinity, podAffinity, and podAntiAffinity parameters. There is no default.	affinity: nodeAffinity:
	There is no deladit.	<pre>requiredDuringSchedulingIgn oredDuringExecution: nodeSelectorTerms: - matchExpressions: - key:</pre>
		topology.kubernetes.io/zone operator: In values: - antarctica-
		east1 - antarctica-west1
annotations	A list of annotations to be applied to a TimesTen Operator Deployment and the Pods that the TimesTen Operator manages.	annotations: x: y
	There is no default.	
image	Parameters that affect container images.	image:
	<pre>Default: repository: Location of the container image. For example, container- registry.oracle.com/ timesten/timesten.</pre>	<pre>repository: phx.ocir.io/ youraccount/tt2211190image tag: "1" pullPolicy: Always</pre>
	 tag: TimesTen release number that contains the relevant Helm charts. For example, "22.1.1.19.0". 	
	 pullPolicy: Pull policy for the container image. For example, Always. 	
imagePullSecrets	A list of pull Secrets required to pull container images.	imagePullSecrets: sekret
	Default: There is no default.	
labels	A list of labels applied to a TimesTen Operator Deployment and the Pods that the TimesTen Operator manages.	labels: x: y
	Default: There is no default.	



Table 18-1 (Cont.) Variables for the ttoperator Chart

Variable	Description	Example
livenessFailureThreshold	Variable that sets the FailureThreshold attribute for the TimesTen Operator's liveness probe. Default: 3	livenessFailureThreshold: 2
livenessInitialDelaySeconds	Variable that sets the InitialDelaySeconds attribute for the TimesTen Operator's liveness probe. Default: 10	livenessInitialDelaySeconds : 15
livenessPeriodSeconds	Variable that sets the PeriodSeconds attribute for the TimesTen Operator's liveness probe. Default: 30	livenessPeriodSeconds: 20
livenessSuccessThreshold	Variable that sets the SuccessThreshold attribute for the TimesTen Operator's liveness probe. Default: 1	livenessSuccessThreshold: 2
livenessTimeoutSeconds	Variable that sets the TimeoutSeconds attribute for the TimesTen Operator's liveness probe. Default: 10	livenessTimeoutSeconds: 15



Table 18-1 (Cont.) Variables for the ttoperator Chart

Variable	Description	Example
metrics	Variable to determine if and how TimesTen Operator metrics are exposed. Valid values are as follows: • expose: 1 or expose: 0: If you specify expose: 1 (or do not specify it), TimesTen Operator metrics are exposed. If you specify expose: 0, TimesTen Operator metrics are not exposed. • scheme: https or scheme: http: If you specify scheme: https (or do not specify it), TimesTen Operator metrics are available by using https/ Transport Layer Security (mutual TLS). If you specify scheme: http, TimesTen Operator metrics are available by using http. • createServiceMonitor: 1 or createServiceMonitor: 0: If you specify createServiceMonitor: 0: If you specify createServiceMonitor: 0. If you specify createServiceMonitor: 0, the TimesTen Operator does not create a ServiceMonitor object. If you specify createServiceMonitor: 0, the TimesTen Operator does not create a ServiceMonitor object. Default: expose: 1 scheme: https createServiceMonitor: 1 See Expose Metrics from the TimesTen Kubernetes Operator.	metrics: expose: 0 scheme: http createServiceMonitor: 0
name	Name of the TimesTen Operator Deployment. Default: timesten-operator	name: timesten-operator2



Table 18-1 (Cont.) Variables for the ttoperator Chart

Variable	Description	Example
podDisruptionBudget	Variable that determines if a podDisruptionBudget is created. If created, uses the provided values. Default: create: false A podDisruptionBudget is not created by default.	<pre>podDisruptionBudget: create: true pdbName: samplepdb maxUnvailable: 1 minAvailable: 1 matchLabels: "x": "y"</pre>
probes	Variable to determine if TimesTen Operator probes are exposed. If you specify expose: 1 (or do not specify it), TimesTen Operator probes are exposed. If you specify expose: 0, TimesTen Operator probes are not exposed. Default: expose: 1	probes: expose: 0
	See About Readiness and Liveness Probes.	
readinessFailureThreshold	Variable that sets the FailureThreshold attribute for the TimesTen Operator's readiness probe. Default: 1	<pre>readinessFailureThreshold: 2</pre>
readinessInitialDelaySeconds	Variable that sets the InitialDelaySeconds attribute for the TimesTen Operator's readiness probe. Default: 10	readinessInitialDelaySecond s: 15
readinessPeriodSeconds	Variable that sets the PeriodSeconds attribute for the TimesTen Operator's readiness probe. Default: 10	readinessPeriodSeconds: 15
readinessSuccessThreshold	Variable that sets the SuccessThreshold attribute for the TimesTen Operator's readiness probe. Default: 1	readinessSuccessThreshold: 2
readinessTimeoutSeconds	Variable that sets the TimeoutSeconds attribute for the TimesTen Operator's readiness probe. Default: 10	readinessTimeoutSeconds: 15



Table 18-1 (Cont.) Variables for the ttoperator Chart

Variable	Description	Example
replicas	Number of replica Pods in a TimesTen Operator Deployment. Default: 1	replicas: 3
resources	Variable used to define resource requests and limits. Default: requests: cpu: "250m" memory: "1G" limits: cpu: "250m" memory: "1G"	resources: requests: cpu: "300m" memory: "1G" limits: cpu: "300m" memory: "1G"
serviceAccount	Variable to determine if a service account is created and what annotations to apply (if any). Default: create: true By default or if you specify create: true, the chart creates a Kubernetes ServiceAccount called timesten-operator as well as a Kubernetes Role object and a Kubernetes RoleBinding object. The Role and RoleBinding objects grant the ServiceAccount the privileges needed to run the TimesTen Operator. If you specify create: false, the chart does not create the ServiceAccount, Role, and RoleBinding objects. You must create these objects by running the kubectl create service_account.yaml command. The service_account.yaml command. The service_account.yaml yaml manifest file is included in the TimesTen Operator distribution. See Create the Service Account and the TimesTen Custom Resource	<pre>serviceAccount: create: false</pre>



Table 18-1 (Cont.) Variables for the ttoperator Chart

Variable	Description	Example
testAffinity	Variable to define Kubernetes nodeAffinity, podAffinity, and podAntiAffinity parameters. These affinity configurations are only applied to the Helm test Pod. There is no default.	<pre>testAffinity: nodeAffinity: requiredDuringSchedulingIgn oredDuringExecution: nodeSelectorTerms: - matchExpressions: - key: topology.kubernetes.io/zone</pre>
testAnnotations	A list of annotations to be applied to a Helm test Pod. This Pod is created when you run the helm test command. Default: helm.sh/hook-delete-policy: hook-succeeded	testAnnotations: x: y
testLabels	A list of labels to be applied to a Helm test Pod. This Pod is created when you run the helm test command. Default: There is no default.	testLabels: x: y

The ttclassic Chart

The ${\tt ttclassic}$ chart creates a TimesTen Classic object, which deploys a TimesTen active standby pair.

The following table describes the variables and default values for the ttclassic chart. Indentation and case sensitivity must be correct for each variable.

Table 18-2 Variables for the ttclassic Chart

Variable	Default	Example
additionalMemoryRequest	Amount of memory to request in addition to what is required for the TimesTen database. This memory is used for the TimesTen daemon, subdaemons, replication agents, cache agents, and the server in a client/server environment. Default: 2Gi	additionalMemoryRequest: 3Gi
	See TimesTenClassicSpecSpec.	
affinity	Variable to define Kubernetes nodeAffinity, podAffinity, and podAntiAffinity parameters. There is no default.	<pre>affinity: nodeAffinity:</pre>
	There is no default.	requiredDuringSchedulingIgn
		<pre>oredDuringExecution: nodeSelectorTerms: - matchExpressions: - key:</pre>
		topology.kubernetes.io/zone operator: In values:
		- antarctica- east1
		- antarctica- west1
agentTcpTimeout	Variable that determines the time in seconds that the TimesTen Operator waits for a TCP handshake when communicating with the TimesTen agent.	agentTcpTimeout: 20
	The default is 10. A value of 0 indicates that there is no timeout. If the timeout is exceeded, the TimesTen Operator considers the agent to be down.	
	See TimesTenClassicSpecSpec.	
agentTlsTimeout	Variable that determines the time in seconds that the Operator waits for a TLS (https) credential exchange when communicating with the TimesTen agent.	agentTlsTimeout: 20
	The default is 10. A value of 0 indicates that there is no timeout. If the timeout is exceeded, the TimesTen Operator considers the agent to be down.	
	•	



Table 18-2 (Cont.) Variables for the ttclassic Chart

Variable	Default	Example
annotations	A list of annotations to be applied to a TimesTenClassic object. There is no default.	annotations: x: y
containers	Variable to define a custom container. This container is created in each Pod in a TimesTenClassic object. The provided YAML is copied directly to the .spec.template.spec.containers section of a TimesTenClassic object YAML manifest. Default: There is no default. See TimesTenClassicSpec.	<pre>containers: - name: sampleapp image: sample.com/ sample:latest command: - /bin/sample</pre>
customerService[1-5]	Variable to create one or more Services (up to 5). A Service maps to your TimesTen database, which allows applications outside of your Kubernetes cluster to access TimesTen through client/server. You can define a maximun of five custom Services, named customService1, customService2,	<pre>customService1: apiVersion: v1 kind: Service metadata: name: sampleexternal spec: type: NodePort selector:</pre>
	<pre>customService3, customService4, and customService5.</pre>	<pre>database.timesten.oracle.co m: payroll ports:</pre>
	Note:	targetPort: 6625 nodePort: 31625
	The YAML that you provide for a custom Servic e definitio n is used without	<pre>customService2: apiVersion: v1 kind: Service metadata: name: sampleinteral spec: type: NodePort selector: database.timesten.oracle.com: payroll norts:</pre>
	modific ation.	<pre>ports:</pre>

Table 18-2 (Cont.) Variables for the ttclassic Chart

Variable	Default	Example
daemonLogCPURequest	Amount of CPU requested for the daemonlog container.	daemonlogCPURequest: 400m
	Default: 200m	
	See TimesTenClassicSpecSpec.	
daemonLogMemoryRequest	Amount of memory requested for the daemonlog container. Default: 200Mi	daemonLogMemoryRequest: 300Mi
	See TimesTenClassicSpecSpec.	300111
databaseCPURequest	Amount of CPU your tt containers require. This includes the CPU used by the TimesTen daemon, subdaemons, replication agents, cache agents, and the server in a client/server environment.	databaseCPURequest: 2
	Default: There is no default.	
	See TimesTenClassicSpecSpec.	
databaseMemorySize	Amount of shared memory your database requires.	databaseMemorySize: 20Gi
	Default: There is no default.	-
	See TimesTenClassicSpecSpec.	
dbConfigMap	Variable that creates a Kubernetes ConfigMap based on the provided values and adds a dbConfigMap entry to a TimesTenClassic object definition.	<pre>dbConfigMap:</pre>
	Default: There is no default. By default, a ConfigMap is not created by a ttclassic chart.	Note: You must create a directory in the /ttclassic directory of the
	See TimesTenClassicSpecSpec.	ttclassic chart. All files in the directory are added to the generate ConfigMap. This example assumes you have created a cm directory in the /ttclassic directory tree.
dbSecret	Variable that creates a Kubernetes Secret based on the provided values and adds a dbSecret entry to a TimesTenClassic object definition.	<pre>dbSecret: - name: sample directory: seekret</pre>
	Default: There is no default. By default, a Secret is not created by a ttclassic chart.	Note: You must create a directory in
	See TimesTenClassicSpecSpec.	the /ttclassic directory of the ttclassic chart. All files in the directory are added to the generated Secret. This example assumes you have created a seekret directory in the /ttclassic directory tree.



Table 18-2 (Cont.) Variables for the ttclassic Chart

Variable	Default	Example
exporterCPURequest	Amount of CPU requested for the exporter container (if provisioned).	exporterCPURequest: 400m
	Default: 200m	-
	See TimesTenClassicSpecSpec.	
exporterMemoryRequest	Amount of memory requested for the exporter container (if provisioned).	exporterMemoryRequest:
	Default: 200Mi	400Mi
image	Parameters that affect container images. Default: • repository: Location of the container image. For example, container-registry.oracle.com/timesten/timesten. • tag: TimesTen release number that contains the relevant Helm charts. For example, "22.1.1.19.0". • pullPolicy: Pull policy for the container image. For example, Always.	<pre>image: repository: phx.ocir.io/ youraccount/tt2211190image tag: "1" pullPolicy: Always</pre>
imagePullSecret	Pull Secret required to pull container images. Default: There is no default. See TimesTenClassicSpecSpec.	imagePullSecret: sekret
imageUpgradeStrategy	Variable to determine if the TimesTen Operator performs automated upgrades. If set to Manual, Helm cannot automatically upgrade or rollback a release. Default: Auto See TimesTenClassicSpecSpec.	imageUpgradeStrategy: Manual



Table 18-2 (Cont.) Variables for the ttclassic Chart

Variable	Default	Example
initContainers	Variable used to define an init container. This init container is created in each Pod in a TimesTenClassic object. The provided YAML is copied directly to the .spec.template.spec section of a TimesTenClassic object YAML manifest. Default: There is no default.	<pre>initContainers: - name: sample image: command: - sh - "-c" - /bin/bash <<'EOF' echo test/user > / ttconfig/testUser ls -l /ttconfig EOF volumeMounts: - name: tt-config mountPath: /ttconfig</pre>
labels	A list of labels to be applied to a TimesTenClassic object. Default: There is no default.	labels: x: y
logStorageClassName	Name of the storage class that is used to request persistent volumes for the TimesTen database transaction log files. Default: There is no default. If you do not specify logStorageClassName, a log volume is not allocated. See TimesTenClassicSpecSpec.	logStorageClassName: fast
logStorageSize	Amount of storage to be provisioned for the TimesTen transaction log files. Default: 50Gi See TimesTenClassicSpecSpec.	logStorageSize: 100Gi
name	Name of the TimesTenClassic object to be created. Default: releaseName	name: sample
podDisruptionBudget	Variable that determines if a podDisruptionBudget is created. If created, uses the provided values. Default: create: false A podDisruptionBudget is not created by default.	<pre>podDisruptionBudget: create: true pdbName: samplepdb maxUnvailable: 1 minAvailable: 1 matchLabels: "x": "y"</pre>



Table 18-2 (Cont.) Variables for the ttclassic Chart

Variable	Default	Example
repStateTimeout	Variable that indicates the time in seconds a replicated database remains in the recovering replication state as reported by the TimesTen ttRepStateGet built-in procedure.	repStateTimeout: 40
	The recovering replication state indicates that the database is in the process of synchronizing updates with the active database after a failure. For more information about the TimesTen ttRepStateGet built-in procedure, see ttRepStateGet in the Oracle TimesTen In-Memory Database Reference.	
	Default: 30 (expressed in seconds). For more information about repStateTimeout, see TimesTenClassicSpecSpec.	
securityContext	Variable used to create an optional securityContext definition. This securityContext definition is applied to TimesTenClassic at the Pod level.	securityContext runAsNonRoot: true
	The provided YAML is copied directly to the .spec.template.spec section of a TimesTenClassic object YAML manifest. Default: There is no default.	
serviceAccountName	Name of the service account that is assigned to the Pods that are created by the TimesTen Operator.	serviceAccountName: xyz
	By default, when the TimesTen Operator creates StatefulSets (which in turn create Pods that run TimesTen), the StatefulSets and Pods have no service account. Specifying serviceAccountName lets you define a Kubernetes ServiceAccount that the TimesTen Pods run under.	
	Default: There is no default.	
storageClassName	Name of the storage class that is used to request persistent volumes for a TimesTen database.	storageClassName: oci-bv
	Default: There is no default. However, you must specify a value for storageClassName.	
	See TimesTenClassicSpecSpec.	



Table 18-2 (Cont.) Variables for the ttclassic Chart

Variable	Default	Example
storageSize	Amount of storage to be provisioned for TimesTen and the TimesTen database. Default: 50Gi	storageSize: 250Gi
templateSpec	Variable used to insert arbitrary YAML into the .spec.template.spec section of a TimesTenClassic object. Default: There is no default. See TimesTenClassicSpec.	<pre>templateSpec: preemptionPolicy: Never</pre>
testAffinity	Variable to define Kubernetes nodeAffinity, podAffinity, and podAntiAffinity parameters. These affinity configurations are only applied to the Helm test Pod. There is no default.	testAffinity: nodeAffinity: requiredDuringSchedulingIgn oredDuringExecution: nodeSelectorTerms: - matchExpressions: - key: topology.kubernetes.io/zone operator: In values: - antarctica- east1 - antarctica- west1
testAnnotations	A list of annotations to be applied to a Helm test Pod. This Pod is created when you run the helm test command. Default: helm.sh/hook-delete-policy: hook-succeeded	testAnnotations: x: y
testLabels	A list of labels to be applied to a Helm test Pod. This Pod is created when you run the helm test command. Default: There is no default.	testLabels: x: y



Table 18-2 (Cont.) Variables for the ttclassic Chart

Variable	Default	Example
tolerations	Variable to define tolerations to be applied to the Pods in a TimesTenClassic object. The provided YAML is copied directly to the .spec.template.spec section of a TimesTenClassic object YAML manifest.	tolerations: - key: "key1" operator: "Equal" value: "value1" effect: "NoSchedule"
	Default: There is no default.	
ttspec	Variable to insert arbitrary YAML into the .spec.ttspec section of a TimesTenClassic object. Use this variable to specify additional datum that are supported by the TimesTenClassic object type, but are not explicitly supported by the ttclassic chart.	<pre>ttspec: agentGetTimeout: 10 prometheus: port: 7777</pre>
	Default: There is no default.	
	See TimesTenClassicSpecSpec.	
volumes	Variable used to create optional volume definitions. These definitions are applied to TimesTenClassic objects.	<pre>volumes: - name: tt-config emptyDir: {}</pre>
	The provided YAML is copied directly to the .spec.template.spec section of a TimesTenClassic object YAML manifest.	
	Default: There is no default.	



TimesTen Kubernetes Operator Metrics

There are several TimesTen Kubernetes Operator (TimesTen Operator) metrics that can be exposed and then published by Prometheus or some other scraper. These metrics include information about the TimesTen Operator functionality as well as the overall status of TimesTenClassic and TimesTenScaleout objects that it manages.

The following table details the TimesTen Operator metrics:

Table 19-1 TimesTen Operator Metrics

Metric	Туре	Description
timesten_classic_state_norma 1	Gauge	Number of TimesTenClassic objects in Normal state.
timesten_classic_state_not_n ormal	Gauge	Number of TimesTenClassic objects in states other than Normal or Initializing.
timesten_classic_state	Gauge	The state of each TimesTenClassic object. The specific state is reported in the state label.
timesten_scaleout_state_norm al	Gauge	Number of TimesTenScaleout objects in Normal state.
timesten_scaleout_state_not_ normal	Gauge	Number of TimesTenScaleout objects in states other than Normal or Initializing.
timesten_scaleout_state	Gauge	The state of each TimesTenScaleout object. The specific state is reported in the state label.

Each metric has these labels:

- namespace: The namespace of the TimesTen object that the metric describes.
- name: The name of the TimesTen object that the metric describes.

In addition there are several other labels of secondary importance:

- container: The name of the container that generated the metric. For example, timestenoperator.
- endpoint: The name of the endpoint that the metric came from. For example, metrics.
- instance: The IP address and port of the TimesTen Operator Pod that generated the metric. For example, 10.244.1.111:8080
- job: The name of the job. For example, timesten-operator.
- pod: The name of the TimesTen Operator Pod that generated the metric. For example, timesten-operator-5f4f4c69f6-z9h2k.
- service. The name of the Service. For example, timesten-operator.



Here is an example of a sample timesten classic state normal metric:

```
timesten_classic_state_normal{container="timesten-operator",
endpoint="metrics", instance="10.244.1.111:8080", job="timesten-
operator",
name="sample", namespace="mynamespace", pod="timesten-
operator-5f4f4c69f6-z9h2k",
service="timesten-operator"}
```

The metric has a value of 1 or 0, depending on whether the TimesTenClassic object (sample, in this case) is healthy or not.

Here is an example of a sample timesten_classic_state metric:

```
timesten_classic_state{container="timesten-operator",
endpoint="metrics", instance="10.244.1.111:8080", job="timesten-
operator",
name="sample", namespace="mynamespace", pod="timesten-
operator-5f4f4c69f6-z9h2k",
service="timesten-operator", state="Normal"}
```

The metric has a value of 1 or 0, depending on whether the TimesTenClassic object (sample, in this case) is in the Normal state or not.

For details on how the TimesTen Operator exposes metrics, see Expose Metrics from the TimesTen Kubernetes Operator.



The TimesTen Operator automatically exposes many other additional metrics. We cannot guarantee these additional metrics will exist from release to release. In addition, these metrics may not be specifically pertinent or useful for the TimesTen Operator.



20

TimesTen Kubernetes Operator Environment Variables

There are TimesTen Kubernetes Operator (TimesTen Operator) environment variables that are used for TimesTen Operator metrics.

The environment variables are included in the <code>operator.yaml</code> file located in the <code>deploy</code> directory of the TimesTen Kubernetes Operator distribution. The variables have default settings. You can change them depending on your needs.

The following table describes these variables:

Table 20-1 TimesTen Operator Environment Variables

Environment Variable	Description	
CREATE_SERVICEMONITOR	Determines if the TimesTen Operator should create a Kubernetes ServiceMonitor object. Valid values: "1" (default): The TimesTen Operator should create a ServiceMonitor object. "0": The TimesTen Operator should not create a ServiceMonitor object.	
	If EXPOSE_METRICS is set to "0" and CREATE_SERVICEMONITOR is set to "1" (default), CREATE_SERVICEMONITOR is treated as though it was set to "0".	
EXPOSE_METRICS	Determines if TimesTen Operator metrics are exposed outside of the TimesTen Operator's Pods. Valid values: "1" (default): Metrics should be exposed outside of the TimesTen Operator's Pods. "0": Metrics should not be exposed outside of the TimesTen Operator's Pods. If EXPOSE_METRICS is set to "0" and CREATE_SERVICEMONITOR is set to "1" (default), CREATE_SERVICEMONITOR is treated as though it was set to "0". In addition, if EXPOSE_METRICS is set to "0", the value	
EXPOSE_PROBES	of METRICS_SCHEME is ignored and http is always used. Determines if liveness probes should be exposed outside of the TimesTen Operator's Pods. Valid values: "1" (default): Probes should be exposed. "0": Probes should not be exposed.	



Table 20-1 (Cont.) TimesTen Operator Environment Variables

Environment Variable	Description Determines if TimesTen Operator metrics should be made available by https or http.	
METRICS_SCHEME		
	Valid values:"https" (default): https should be used.	
	"http": http should be used.	
	If EXPOSE_METRICS is set to "0", the value of METRICS_SCHEME is ignored and http is always used.	

For more information about the TimesTen Operator environment variables, see Expose Metrics from the TimesTen Kubernetes Operator.



21

Dockerfile ARGs

Images containing TimesTen and its prerequisites are available at <code>container-registry.oracle.com</code>. You can use these images as is with the TimesTen Kubernetes Operator. You also have the choice to build your own TimesTen container image by using the <code>Dockerfile</code> provided in the <code>/image</code> directory of the <code>operator.zip</code> distribution. The <code>operator.zip</code> distribution is located in the <code>/kubernetes</code> directory of the TimesTen distribution. See <code>Unpack</code> the <code>TimesTen</code> and the <code>TimesTen</code> Operator <code>Distributions</code>.

The Dockerfile supports a number of ARGs. These ARGs let you override the attributes of the Dockerfile (and its resultant image). You supply these ARGs on the <code>docker build</code> command line.

Table 21-1 describes the supported ARGs:

Table 21-1 Dockerfile ARGs

ARG name	Default value	Description
TT_BASE	<pre>container- registry.oracle.com/os/ oraclelinux:8</pre>	Name of the base image.
UNZIP_BASE	<pre>container- registry.oracle.com/os/ oraclelinux:8</pre>	Name of the image that is used to unzip the TimesTen distribution.
TT_DISTRO	timesten2211190.server.linux 8664.zip	Name of the TimesTen distribution that you are including in the container image.
		If you are building the TimesTen container image, you must supply this ARG on the docker build command line.
TT_RELEASE	22.1.1.19.0	Release number (in dotted decimal format) of the TimesTen release that is included in \$TT_DISTRO.
		If you are building the TimesTen container image, you must supply this ARG on the docker build command line.
TT_USER	timesten	Name of the Linux user that is created in the container image. This is the user who runs TimesTen.
		To define a different user to run TimesTen, supply this ARG on the docker build command line.



Table 21-1 (Cont.) Dockerfile ARGs

ARG name	Default value	Description
TT_UID	3429	The numeric UID of \$TT_USER.
		To define a different UID for \$TT_USER, supply this ARG on the docker build command line.
TT_GROUP	timesten	Name of the Linux group that is created in the container image. This is the name of the TimesTen users group.
		To define a different name for the TimesTen group, supply this ARG on the docker build command line.
TT_GID	3429	The numeric GID of \$TT_GROUP.
		To define a different GID for \$TT_GROUP, supply this ARG on the docker build command line.
TT_EXTRA_LINUX_PACKAGES	There is no default.	Additional Linux packages that you want installed in the container image by the yum install command.



A

Active Standby Pair Example

This appendix provides an example showing you the complete process for deploying and running your active standby pair of TimesTen databases in the Kubernetes cluster. After the databases are up and running, the example demonstrates how the Operator controls and manages the databases. If the active database fails, the Operator performs the necessary tasks to failover to the standby database, making that standby database the active one. The example concludes with procedures to delete the TimesTen databases and to stop the Operator.

Note:

You have the option of using Helm to deploy your active standby pair of TimesTen databases. For more information about using Helm, see Use Helm to Deploy the TimesTen Kubernetes Operator and TimesTenClassic Objects.

- · Before You Begin
- Create a ConfigMap Object
- Create a TimesTenClassic Object
- Monitor Deployment
- Verify Existence of Underlying Objects
- Verify Connection to the Active TimesTen Database
- Recover from Failure
- Clean Up

Before You Begin

Review the following sections and complete if you have not already done so.

- 1. Prerequisites
- 2. Set Up the Environment

Create a ConfigMap Object

This section creates the sample ConfigMap. This ConfigMap contains the db.ini, the adminUser, and the schema.sql metadata files. This ConfigMap will be referenced when you define the TimesTenClassic object. See "Overview of Configuration Metadata and Kubernetes Facilities" for information on the configuration files and the ConfigMap facility.

On your Linux development host:

1. From the directory of your choice, create an empty subdirectory for the metadata files. This example creates the <code>cm_sample</code> subdirectory. (The <code>cm_sample</code> directory is used in the remainder of this example to denote this directory.)

```
% mkdir -p cm sample
```

2. Navigate to the ConfigMap directory.

```
% cd cm sample
```

 Create the db.ini file in this ConfigMap directory (cm_sample, in this example). In this db.ini file, define the PermSize and DatabaseCharacterSet connection attributes.

```
vi db.ini
PermSize=200
DatabaseCharacterSet=AL32UTF8
```

4. Create the adminUser file in this ConfigMap directory (cm_sample in this example). In this adminUser file, create the sampleuser user with the samplepw password.

```
vi adminUser
sampleuser/samplepw
```

5. Create the schema.sql file in this ConfigMap directory (cm_sample in this example). In this schema.sql file, define the s sequence and the emp table for the sampleuser user. The Operator will automatically initialize your database with these object definitions.

```
vi schema.sql
create sequence sampleuser.s;
create table sampleuser.emp (
  id number not null primary key,
  name char(32)
);
```

6. Create the ConfigMap. The files in the <code>cm_sample</code> directory are included in the ConfigMap and, later, will be available in the TimesTen containers.

In this example:

- The name of the ConfigMap is sample. Replace sample with a name of your choosing. (sample is represented in **bold** in this example.)
- This example uses cm_sample as the directory where the files that will be copied into the ConfigMap reside. If you use a different directory, replace cm_sample with the name of your directory. (cm_sample is represented in bold in this example.)

Use the kubectl create command to create the ConfigMap:

```
% kubectl create configmap sample --from-file=cm_sample
configmap/sample created
```

You successfully created and deployed the sample ConfigMap.

7. Use the kubectl describe command to verify the contents of the ConfigMap. (sample, in this example.)

```
% kubectl describe configmap sample
Name: sample
```



```
Namespace: mynamespace
Labels: <none>
Annotations: <none>

Data
====
adminUser:
----
sampleuser/samplepw

db.ini:
----
PermSize=200
DatabaseCharacterSet=AL32UTF8

schema.sql:
----
create sequence sampleuser.s;
create table sampleuser.emp (
  id number not null primary key,
  name char(32)
);
```

Events: <none>

Create a TimesTenClassic Object

This section creates the TimesTenClassic object. See "Define and Create a TimesTenClassic Object" and "About the TimesTenClassic Object Type" for detailed information on the TimesTenClassic object.

Perform these steps:

1. Create an empty YAML file. You can choose any name, but you may want to use the same name you used for the name of the TimesTenClassic object. (In this example, sample.) The YAML file contains the definitions for the TimesTenClassic object. See "TimesTenClassicSpecSpec" for information on the fields that you must specify in this YAML file as well as the fields that are optional.

In this example, replace the following. (The values you can replace are represented in **bold**.)

- name: Replace sample with the name of your TimesTenClassic object.
- storageClassName: Replace oci-by with the name of the storage class used to allocate PersistentVolumes to hold TimesTen.
- storageSize: Replace 250Gi with the amount of storage that should be requested for each Pod to hold TimesTen. Note: This example assumes a production environment and uses a value of 250Gi for storageSize. For demonstration purposes, a value of 50Gi is adequate. See the storageSize and the logStorageSize entries in "Table 17-3" for information.
- image: Replace container-registry.oracle.com/timesten/timesten:22.1.1.19.0 with the location and name of your image.
- imagePullSecret: Replace sekret with the image pull secret that Kubernetes should use to fetch the TimesTen image.



dbConfigMap: This example uses one ConfigMap (called sample) for the
 db.ini, the adminUser, and the schema.sql metadata files. This ConfigMap
 will be included in the ProjectedVolume. This volume is mounted as /ttconfig
 in the TimesTen containers. See "Using ConfigMaps and Secrets" and
 "Example Using One ConfigMap" for information on ConfigMaps.

```
% vi sample.yaml
apiVersion: timesten.oracle.com/v1
kind: TimesTenClassic
metadata:
   name: sample
spec:
   ttspec:
   storageClassName: oci-bv
   storageSize: 250Gi
   image: container-registry.oracle.com/timesten/timesten:22.1.1.19.0
   imagePullSecret: sekret
   dbConfigMap:
   - sample
```

Use the kubectl create command to create the TimesTenClassic object from the
contents of the YAML file (in this example, sample.yaml). Doing so begins the
process of deploying your active standby pair of TimesTen databases in the
Kubernetes cluster.

```
% kubectl create -f sample.yaml
configmap/sample created
timestenclassic.timesten.oracle.com/sample created
```

You successfully created the TimesTenClassic object in the Kubernetes cluster. The process of deploying your TimesTen databases begins, but is not yet complete.

Monitor Deployment

Use the kubectl get and the kubectl describe commands to monitor the progress of the active standby pair as it is provisioned.



For the kubectl get timestenclassic and kubectl describe timestenclassic commands, you can alternatively specify kubectl get ttc and kubectl describe ttc respectively. timestenclassic and ttc are synonymous when used in these commands, and return the same results. The first kubectl get and the first kubectl describe examples in this appendix use timestenclassic. The remaining examples in this appendix use ttc for simplicity.

 Use the kubectl get command and review the STATE field. Observe the value is Initializing. The active standby pair provisioning has begun, but is not yet complete.

```
% kubectl get timestenclassic sample
NAME STATE ACTIVE AGE
sample Initializing None 11s
```



2. Use the kubectl describe command to view the initial provisioning in detail.

```
% kubectl describe timestenclassic sample
Name:
        sample
Namespace: mynamespace
Labels: <none>
Annotations: <none>
API Version: timesten.oracle.com/v1
Kind: TimesTenClassic
Metadata:
 Creation Timestamp: 2021-05-31T15:35:12Z
 Generation:
 Resource Version: 20231755
 Self Link:
/apis/timesten.oracle.com/v1/namespaces/mynamespace/timestenclassics/sample
 UID:
                    517a8646-a354-11ea-a9fb-0a580aed5e4a
Spec:
 Ttspec:
   Db Config Map:
     sample
   Image:
                      container-registry.oracle.com/timesten/
timesten:22.1.1.19.0
   Image Pull Policy: Always
   Image Pull Secret: sekret
   Storage Class Name: oci-bv
   Storage Size:
                      250Gi
Status:
 Active Pods: None
 High Level State: Initializing
 Last Event: 3
 Pod Status:
   Cache Status:
     Cache Agent:
     Cache UID Pwd Set: false
     N Cache Groups:
   Db Status:
     Db:
                  Unknown
     Db Id:
                 Ω
     Db Updatable: Unknown
   Initialized: true
   Pod Status:
     Agent:
                          Down
     Last Time Reachable: 0
     Pod IP:
     Pod Phase:
                         Pending
   Replication Status:
     Last Time Rep State Changed: 0
     Rep Agent:
                                 Down
                                Unknown
     Rep Peer P State:
     Rep Scheme:
                                Unknown
                                Unknown
     Rep State:
   Times Ten Status:
     Daemon:
                   Down
     Instance:
                   Unknown
     Release:
   Admin User File: false
   Cache User File: false
   Cg File:
                    false
   High Level State: Down
   Intended State: Active
   Name:
                    sample-0
```



```
Schema File: false
    Cache Status:
     Cache Agent:
                        Down
     Cache UID Pwd Set: false
     N Cache Groups:
    Db Status:
     Db:
                   Unknown
               0
     Db Id:
     Db Updatable: Unknown
    Initialized: true
    Pod Status:
     Agent:
                            Down
     Last Time Reachable: 0
     Pod IP:
     Pod Phase:
                          Pending
    Replication Status:
     Last Time Rep State Changed: 0
                                  Down
     Rep Agent:
     Rep Peer P State: Unknown
Rep Scheme: Unknown
     Rep State:
                                   Unknown
   Times Ten Status:
   Daemon: Down
Instance: Unknown
Release: Unknown
Admin User File: false
Cache User File: false
Cg File: false
   High Level State: Unknown
   High Level State.

Intended State: Standby
sample-1
   Schema File: false
 Rep Create Statement: create active standby pair "sample" on
"sample-0.sample.mynamespace.svc.cluster.local", "sample" on
"sample-1.sample.mynamespace.svc.cluster.local" NO RETURN store "sample" on
"sample-0.sample.mynamespace.svc.cluster.local" PORT 4444 FAILTHRESHOLD 0
store "sample" on "sample-1.sample.mynamespace.svc.cluster.local" PORT 4444
FAILTHRESHOLD 0
 Rep Port:
                        4444
 Status Version: 1.0
Events:
                              Message
 Type Reason Age From
 ---- ----- ----
       Create 50s ttclassic Secret tt517a8646-a354-11ea-
a9fb-0a580aed5e4a created
 - Create 50s ttclassic Service sample created
       Create 50s ttclassic StatefulSet sample created
```

3. Use the kubectl get command again to see if value of the STATE field has changed. In this example, the value is Normal, indicating the active standby pair of databases are now provisioned and the process is complete.

```
% kubectl get ttc sample
NAME STATE ACTIVE AGE
sample Normal sample-0 3m5s
```

 Use the kubectl describe command again to view the active standby pair provisioning in detail.

Note: In this example, the <code>now Normal</code> line displays on its own line. In the actual output, this line does not display as its own line, but at the end of the <code>StateChange</code> previous line.

```
% kubectl describe ttc sample
Name:
        sample
Namespace: mynamespace
Labels:
           <none>
Annotations: <none>
API Version: timesten.oracle.com/v1
       TimesTenClassic
Metadata:
 Creation Timestamp: 2021-05-31T15:35:12Z
 Generation:
 Resource Version:
                     20232668
 Self Link:
/apis/timesten.oracle.com/v1/namespaces/mynamespace/timestenclassics/sample
 UID:
                     517a8646-a354-11ea-a9fb-0a580aed5e4a
Spec:
 Ttspec:
   Db Config Map:
     sample
   Image:
                       container-registry.oracle.com/timesten/
timesten:22.1.1.19.0
   Image Pull Policy: Always
   Image Pull Secret: sekret
   Storage Class Name: oci-bv
   Storage Size:
                      250Gi
 Active Pods: sample-0
 High Level State: Normal
 Last Event:
 Pod Status:
   Cache Status:
     Cache Agent: Not Running
     Cache UID Pwd Set: true
     N Cache Groups:
   Db Status:
     Db:
                   Loaded
     Db Id:
                  26
     Db Updatable: Yes
   Initialized: true
   Pod Status:
     Agent:
                         Uр
     Last Time Reachable: 1590939597
     Pod IP:
                         192.0.2.1
     Pod Phase:
                         Running
   Replication Status:
     Last Time Rep State Changed: 0
     Rep Agent:
                                Running
     Rep Peer P State:
                                start
     Rep Scheme:
                                Exists
                                ACTIVE
     Rep State:
   Times Ten Status:
     Daemon: Up
                   Exists
     Instance:
                    22.1.1.19.0
     Release:
   Admin User File: true
   Cache User File: false
   Cg File:
                     false
   High Level State: Healthy
   Intended State: Active
   Name:
                    sample-0
   Schema File:
                     true
   Cache Status:
```

```
Cache Agent:
                      Not Running
     Cache UID Pwd Set: true
     N Cache Groups:
   Db Status:
     Db:
                  Loaded
     Db Id:
     Db Updatable: No
   Initialized: true
   Pod Status:
                         Up
     Agent:
     Last Time Reachable: 1590939597
     Pod IP:
                         192.0.2.2
     Pod Phase:
                         Running
   Replication Status:
     Last Time Rep State Changed: 1590939496
     Rep Agent:
                                 Running
     Rep Peer P State:
                                 start
     Rep Scheme:
                                 Exists
                                 STANDBY
     Rep State:
   Times Ten Status:
     Daemon: Up
     Instance:
                     Exists
                     22.1.1.19.0
     Release:
   Admin User File: true
   Cache User File: false
   Cg File:
                     false
   High Level State: Healthy
   Intended State: Standby
   Name:
                     sample-1
   Schema File:
                     true
 Rep Create Statement: create active standby pair "sample" on
"sample-0.sample.mynamespace.svc.cluster.local", "sample" on
"sample-1.sample.mynamespace.svc.cluster.local" NO RETURN store "sample" on
"sample-0.sample.mynamespace.svc.cluster.local" PORT 4444 FAILTHRESHOLD 0
store "sample" on "sample-1.sample.mynamespace.svc.cluster.local" PORT 4444
FAILTHRESHOLD 0
 Rep Port:
                       4444
 Status Version:
Events:
 Type Reason
                 Age From Message
                 ----
                         ----
                  4m43s ttclassic Secret tt517a8646-a354-l1ea-
      Create
a9fb-0a580aed5e4a created

    Create 4m43s ttclassic Service sample created
    Create 4m43s ttclassic StatefulSet sample created

      StateChange 3m47s ttclassic Pod sample-0 Daemon Unknown
     StateChange 3m47s ttclassic Pod sample-0 CacheAgent Unknown
      StateChange 3m47s ttclassic Pod sample-0 RepAgent Unknown
       StateChange 3m47s ttclassic Pod sample-1 Daemon Unknown
       StateChange 3m47s ttclassic Pod sample-1 CacheAgent Unknown
      StateChange 3m47s ttclassic Pod sample-1 RepAgent Unknown
      StateChange 3m26s ttclassic Pod sample-0 Agent Up
      StateChange 3m26s ttclassic Pod sample-0 Release 22.1.1.19.0
      StateChange 3m26s ttclassic Pod sample-0 Daemon Down
       StateChange 3m26s ttclassic Pod sample-1 Agent Up
       StateChange 3m26s ttclassic Pod sample-1 Release 22.1.1.19.0
       StateChange 3m26s ttclassic Pod sample-1 Daemon Down
       StateChange 3m26s ttclassic Pod sample-0 Daemon Up
       StateChange 3m25s ttclassic Pod sample-1 Daemon Up
       StateChange 2m13s ttclassic Pod sample-0 RepState IDLE
       StateChange 2m13s ttclassic Pod sample-0 Database Updatable
```



```
StateChange 2m13s ttclassic Pod sample-0 CacheAgent Not Running
StateChange 2m13s ttclassic Pod sample-0 RepAgent Not Running
StateChange 2m13s ttclassic Pod sample-0 RepScheme None
StateChange 2m13s ttclassic Pod sample-0 Database Loaded
StateChange 2m11s ttclassic Pod sample-0 RepAgent Running
StateChange 2m10s ttclassic Pod sample-0 RepScheme Exists
StateChange 2m10s ttclassic Pod sample-0 RepState ACTIVE
StateChange 113s ttclassic Pod sample-1 Database Loaded
StateChange 113s ttclassic Pod sample-1 Database Not Updatable
StateChange 113s ttclassic Pod sample-1 CacheAgent Not Running
StateChange 113s ttclassic Pod sample-1 RepAgent Not Running
StateChange 113s ttclassic Pod sample-1 RepScheme Exists
StateChange 113s ttclassic Pod sample-1 RepState IDLE
StateChange 106s ttclassic Pod sample-1 RepAgent Running
StateChange 101s ttclassic Pod sample-1 RepState STANDBY
StateChange 101s ttclassic TimesTenClassic was Initializing, now Normal
```

Your active standby pair of TimesTen databases are successfully deployed (as indicated by Normal.) There are two TimesTen databases, configured as an active standby pair. One database is active. (In this example, sample-0 is the active database, as indicated by Rep State ACTIVE). The other database is standby. (In this example, sample-1 is the standby database as indicated by Rep State STANDBY). The active database can be modified and queried. Changes made on the active database are replicated to the standby database. If the active database fails, the Operator automatically promotes the standby database to be the active. The formerly active database will be repaired or replaced, and will then become the standby.

Verify Existence of Underlying Objects

Use the kubectl describe commands to verify the underlying objects.

StatefulSet:

```
% kubectl get statefulset sample
NAME    READY    AGE
sample    2/2    8m21s
```

2. Service:

3. Pods:

```
      % kubectl get pods
      READY
      STATUS
      RESTARTS
      AGE

      sample-0
      2/2
      Running
      0
      10m

      sample-1
      2/2
      Running
      0
      10m

      timesten-operator-5d7dcc7948-8mnz4
      1/1
      Running
      0
      11h
```

4. PersistentVolumeClaims (PVCs):



```
ocid1.volume.oc1.phx.abyhqljtt4qxxoj5jqiskriskh66hakaw326rbza4uigmuaezdnu53qh
h
oaa
250Gi RWO oci-bv 10m
```

Verify Connection to the Active TimesTen Database

You can run the <code>kubectlexec</code> command to invoke shells in your Pods and control TimesTen, which is running in those Pods. By default, TimesTen runs in the Pods as the <code>timesten</code> user. Once you have established a shell in the Pod, verify you can connect to the <code>sample</code> database, and that the information from the metadata files is correct. You can optionally run queries against the database or any other operations.

Establish a shell in the Pod.

```
% kubectl exec -it sample-0 -c tt -- /bin/bash
```

 Connect to the sample database. Verify the information in the metadata files is in the database correctly. For example, attempt to connect to the database as the sampleuser user. Check that the PermSize value of 200 is correct. Check that the sampleuser.emp table exists.

```
% ttIsql sample
Copyright (c) 1996, 2023, Oracle and/or its affiliates. All rights reserved.
Type ? or "help" for help, type "exit" to quit ttIsql.
connect "DSN=sample";
Connection successful:
DSN=sample;UID=timesten;DataStore=/tt/home/timesten/datastore/sample;
DatabaseCharacterSet=AL32UTF8; ConnectionCharacterSet=AL32UTF8; PermSize=200;
DDLReplicationLevel=3;
(Default setting AutoCommit=1)
Command> connect adding "uid=sampleuser;pwd=samplepw" as sampleuser;
Connection successful:
DSN=sample;UID=sampleuser;DataStore=/tt/home/timesten/datastore/sample;
DatabaseCharacterSet=AL32UTF8; ConnectionCharacterSet=AL32UTF8; PermSize=200;
DDLReplicationLevel=3;
(Default setting AutoCommit=1)
sampleuser: Command> tables;
 SAMPLEUSER.EMP
1 table found.
```

Recover from Failure

This example simulates a failure of the active TimesTen database. This is for demonstration purposes only. Do not do this in a production environment.

 Use the kubectl delete pod command to delete the active database (sample-0 in this case)

```
% kubectl delete pod sample-0
```

2. Use the kubectl describe command to observe how the Operator recovers from the failure. The Operator promotes the standby database (sample-1) to be active. Any applications that were connected to the sample-0 database are automatically

reconnected to the sample-1 database by TimesTen. After a brief outage, the applications can continue to use the database. See "About Monitoring the Health of an Active Standby Pair of Databases" for information on the health and states of the active standby pair.

Note: In this example, the text for the Message column displays on two lines for three state changes. However, the actual output displays on one line for each of these three state changes.

```
% kubectl describe ttc sample
Name: sample
Events:
 Type Reason Age From Message
 - StateChange 2mls ttclassic TimesTenClassic sample: was Normal, now
ActiveDown
    StateChange 115s ttclassic Pod sample-1 Database Updatable: Yes
       StateChange 115s ttclassic TimesTenClassic sample:was ActiveDown, now
StandbyDown
 - StateChange 115s ttclassic Pod sample-1 RepState ACTIVE
     StateChange 110s ttclassic Pod sample-O High Level State Unknown
    StateChange 63s ttclassic Pod sample-0 Pod Phase Running
    StateChange 63s ttclassic Pod sample-0 Agent Up
     StateChange 63s ttclassic Pod sample-0 Instance Exists
     StateChange 63s ttclassic Pod sample-0 Daemon Up
     StateChange 63s ttclassic Pod sample-0 Database None
     StateChange 42s ttclassic Pod sample-0 Database Loaded
    StateChange 42s ttclassic Pod sample-0 Database Updatable: No
     StateChange 42s ttclassic Pod sample-0 RepAgent Running
     StateChange 42s ttclassic Pod sample-0 CacheAgent Not Running
     StateChange 42s ttclassic Pod sample-0 RepScheme Exists
     StateChange 42s ttclassic Pod sample-0 RepState IDLE
      StateChange 36s ttclassic Pod sample-0 High Level State Healthy
      StateChange 36s ttclassic Pod sample-0 RepState STANDBY
StateChange 36s ttclassic TimesTenClassic sample:was StandbyDown, now
Normal
```

Kubernetes has automatically respawned a new sample-0 Pod to replace the Pod you deleted. The Operator configured TimesTen inside of that Pod, bringing the database in the Pod up as the new standby database. The replicated pair of databases are once again functionally normally.

Clean Up

This example concludes with deleting the databases and all objects associated with TimesTenClassic. These steps are used for example purposes only. Doing these steps results in the termination of the Pods that are running the TimesTen databases as well as the deletion of the TimesTen databases themselves.

1. Delete the ConfigMap object. (sample, in this example.)

```
% kubectl delete configmap sample
configmap "sample" deleted
```

2. Delete the TimesTenClassic object and the underlying objects.

```
% kubectl delete -f sample.yaml
timestenclassic.timesten.oracle.com "sample" deleted
```

3. Verify the Pods that were running the TimesTen databases no longer exist.

```
% kubectl get pods
NAME READY STATUS RESTARTS AGE
timesten-operator-5d7dcc7948-8mnz4 1/1 Running 0
5d23h
```

4. Delete the persistent storage used to hold your databases. You have to do this manually.

```
% kubectl get pvc
NAME STATUS VOLUME
CAPACITY ACCESS MODES STORAGECLASS AGE
tt-persistent-sample-0 Bound
...

tt-persistent-sample-1 Bound
...

% kubectl delete pvc tt-persistent-sample-0
persistentvolumeclaim "tt-persistent-sample-0" deleted
% kubectl delete pvc tt-persistent-sample-1
persistentvolumeclaim "tt-persistent-sample-1" deleted
```

5. If you no longer want to run the Operator, you can stop it. Navigate to the /deploy directory (kube_files/deploy, in this example) and use the kubectl delete command to stop the operator.

```
% cd kube_files/deploy
% kubectl delete -f operator.yaml
deployment.apps "timesten-operator" deleted
```



B

TimesTen Cache in TimesTen Classic Example

This appendix provides a working example for using TimesTen Cache with active standby pair of TimesTen databases in your Kubernetes environment. This example should not be used for production purposes. It assumes a test environment. Your Oracle Database should be customized with the settings specific to your environment.

Topics:

- Set Up the Oracle Database to Cache Data
- Create Metadata Files and a Kubernetes Facility
- Create a TimesTenClassic Object
- Monitor Deployment of a TimesTenClassic Object
- Verify TimesTen Cache Configuration
- Perform Operations On Cache Group Tables
- Clean Up Cache Metadata on the Oracle Database

Set Up the Oracle Database to Cache Data

The following sections describe the tasks that must be performed in the Oracle Database:

- Create the Oracle Database Users
- Grant Privileges to the Cache Administration User
- Create the Oracle Database Tables to Be Cached

Create the Oracle Database Users

Before you can use TimesTen Cache, you must create the following users in your Oracle database:

- A cache administration user. This user creates and maintains Oracle Database objects that store information about the cache environment. This user also enforces predefined behaviors of cache group types.
- One or more schema users who owns Oracle Database tables that are cached in a TimesTen database.

See Create the Oracle Database Users and Default Tablespace in the *Oracle TimesTen In-Memory Database Cache Guide* for information.

This example creates the cacheuser2 cache administration user and the oratt schema user in the Oracle Database.

1. Create a shell from which you can access your Oracle Database and then use SQL*Plus to connect to the Oracle Database as the sys user. Then, create a default tablespace to

store the TimesTen Cache management objects. See Create the Oracle Database Users and Default Tablespace in the *Oracle TimesTen In-Memory Database Cache Guide* for information.

This example creates the cachetablespace2 tablespace.

```
% sqlplus sys/syspwd@oracache as sysdba
SQL> CREATE TABLESPACE cachetablespace2 DATAFILE 'datatt2.dbf' SIZE 100M;
Tablespace created.
```

 Use SQL*Plus to create the schema user. Grant this schema user the minimum privileges required to create tables in the Oracle Database to be cached in your TimesTen database.

This example creates the oratt schema user.

```
SQL> CREATE USER oratt IDENTIFIED BY oraclepwd;
User created.
SQL> GRANT CREATE SESSION, RESOURCE TO oratt;
Grant succeeded.
```

3. Use SQL*Plus to create the cache administration user. Assign the cachetablespace2 tablespace to this user. You will later use the same name of this Oracle cache administration user in the cacheUser metadata file.

This example creates the cacheuser2 user.

Grant Privileges to the Cache Administration User

The cache administration user must be granted a specific set of privileges depending on the cache group types that will be created in the TimesTen databases and the operations performed on those cache groups. TimesTen provides the <code>grantCacheAdminPrivileges.sql SQL*Plus</code> script that you can run in your Oracle Database to grant the cache administration user the minimum set of privileges required to perform cache operations. See Grant Privileges to the Oracle Cache Administration User and see Required Privileges for Cache Administration User for Cache Operations in the *Oracle TimesTen In-Memory Database Cache Guide*.

Perform these steps to run the grantCacheAdminPrivileges.sql script:

 Create a shell from which you can access your Oracle Database, and then from the directory of your choice, create an empty subdirectory. This example creates the oraclescripts subdirectory.



```
% mkdir -p oraclescripts
```

2. From your Linux development host, use the <code>kubectl cp</code> command to copy the <code>grantCacheAdminPrivileges.sql</code> script from the <code>installation_dir/oraclescripts</code> directory on your Linux development host to the <code>oraclescripts</code> directory that you just created. Recall that the <code>installation_dir</code> directory was created when you unpacked the TimesTen distribution. See <code>Unpack</code> the <code>TimesTen</code> and the <code>TimesTen</code> Operator <code>Distributions</code> for information on unpacking the <code>TimesTen</code> distribution.

```
\ cp\ /installation\_dir/oraclescripts/grantCacheAdminPrivileges.sql database-oracle:oraclescripts/grantCacheAdminPrivileges.sql
```

3. From your shell, verify the script is located in the oraclescripts directory.

```
% ls oraclescripts
grantCacheAdminPrivileges.sgl
```

4. Use SQL*Plus to connect to the Oracle Database as the sys user. Then, run the oraclescripts/grantCacheAdminPrivileges.sql script. This script grants the cacheuser2 cache administration user the minimum set of privileges required to perform cache group operations. See Grant Privileges to the Oracle Cache Administration User in the Oracle TimesTen In-Memory Database Cache Guide for more information.

```
% sqlplus sys/syspwd@oracache as sysdba
SQL> @grantCacheAdminPrivileges "cacheuser2";
Please enter the administrator user id
The value chosen for administrator user id is cacheuser2
TT CACHE ADMIN ROLE role already exists
0. Granting the CREATE SESSION privilege to CACHEUSER2
1. Granting the TT CACHE ADMIN ROLE to CACHEUSER2
2. Granting the DBMS LOCK package privilege to CACHEUSER2
3. Granting the DBMS DDL package privilege to CACHEUSER2
4. Granting the DBMS FLASHBACK package privilege to CACHEUSER2
5. Granting the CREATE SEQUENCE privilege to CACHEUSER2
6. Granting the CREATE CLUSTER privilege to CACHEUSER2
7. Granting the CREATE OPERATOR privilege to CACHEUSER2
8. Granting the CREATE INDEXTYPE privilege to CACHEUSER2
9. Granting the CREATE TABLE privilege to CACHEUSER2
10. Granting the CREATE PROCEDURE privilege to CACHEUSER2
11. Granting the CREATE ANY TRIGGER privilege to CACHEUSER2
12. Granting the GRANT UNLIMITED TABLESPACE privilege to CACHEUSER2
13. Granting the DBMS LOB package privilege to CACHEUSER2
14. Granting the SELECT on SYS.ALL OBJECTS privilege to CACHEUSER2
15. Granting the SELECT on SYS.ALL SYNONYMS privilege to CACHEUSER2
16. Checking if the cache administrator user has permissions on the
   default tablespace
   Permission exists
18. Granting the CREATE TYPE privilege to CACHEUSER2
19. Granting the SELECT on SYS.GV$LOCK privilege to CACHEUSER2
20. Granting the SELECT on SYS.GV$SESSION privilege to CACHEUSER2
21. Granting the SELECT on SYS.DBA DATA FILES privilege to CACHEUSER2
22. Granting the SELECT on SYS.USER USERS privilege to CACHEUSER2
23. Granting the SELECT on SYS.USER_FREE_SPACE privilege to CACHEUSER2
24. Granting the SELECT on SYS.USER TS QUOTAS privilege to CACHEUSER2
25. Granting the SELECT on SYS.USER SYS PRIVS privilege to CACHEUSER2
26. Granting the SELECT on SYS.V$DATABASE privilege to CACHEUSER2 (optional)
27. Granting the SELECT ANY TRANSACTION privilege to CACHEUSER2
****** Initialization for cache admin user done successfully *******
```



You have successfully run the <code>grantCacheAdminPrivileges.sql</code> script in the Oracle Database.

Create the Oracle Database Tables to Be Cached

This example creates two tables in the oratt user schema. See "Create the Oracle Database Users" for information on this user.

- readtab: This table will later be cached in a read-only cache group.
- writetab: This table will later be cached in an AWT cache group.
- 1. Create a shell from which you can access your Oracle Database and then use SQL*Plus to connect to the Oracle Database as the sys user. Then create the oratt.readtab and the oratt.writetab tables.

2. Use SQL*Plus to insert rows into the oratt.readtab and the oratt.writetab tables. Then verify the rows have been inserted.

```
SQL> INSERT INTO oratt.readtab VALUES (1,'Hello');
1 row created.

SQL> INSERT INTO oratt.readtab VALUES (2,'World');
1 row created.

SQL> INSERT INTO oratt.writetab VALUES (100, 'TimesTen');
1 row created.

SQL> INSERT INTO oratt.writetab VALUES (101, 'Cache');
1 row created.

SQL> commit;
Commit complete.
```

Verify the rows have been inserted into the tables.

```
SQL> SELECT * FROM oratt.readtab;

KEYVAL STR

1 Hello
2 World

SQL> SELECT * FROM oratt.writetab;
```



```
PK ATTR
------
100 TimesTen
101 Cache
```

3. Use SQL*Plus to grant the SELECT privilege on the oratt.readtab table and the SELECT, INSERT, UPDATE, and DELETE privileges on the oratt.writetab table to the cache administration user (cacheuser2, in this example).

```
SQL> GRANT SELECT ON oratt.readtab TO cacheuser2;
Grant succeeded.

SQL> GRANT SELECT ON oratt.writetab TO cacheuser2;
Grant succeeded.

SQL> GRANT INSERT ON oratt.writetab TO cacheuser2;
Grant succeeded.

SQL> GRANT UPDATE ON oratt.writetab TO cacheuser2;
Grant succeeded.

SQL> GRANT DELETE ON oratt.writetab TO cacheuser2;
Grant succeeded.
```

4. Use SQL*Plus to query the nls_database_parameters system view to determine the Oracle Database database character set. The Oracle Database database character set must match the TimesTen database character set. (The TimesTen database character set will be set later. See "Create Metadata Files and a Kubernetes Facility" for details.)

In this example, the guery returns the AL32UTF8 database character set.

You have successfully created the Oracle Database tables that will be cached in the TimesTen cache group tables.

Create Metadata Files and a Kubernetes Facility

There are metadata files that are specific to using TimesTen Cache:

- cacheUser: This file is required. The user in this file is created in the TimesTen databases
 and serves as the cache manager. The name of this user must match the name of the
 cache administration user that you created in the Oracle Database. See "Create the
 Oracle Database Users" for information on the cache administration user in the Oracle
 Database. Also see "cacheUser" for more information on the cacheUser metadata file.
- cachegroups.sql: This file is required. The contents of this file contain the CREATE CACHE GROUP definitions. The file can also contain the LOAD CACHE GROUP statement and the built-in procedures to update statistics on the cache group tables (such as,

ttOptEstimateStats and ttOptUpdateStats). See "cachegroups.sql" for more information on this file.

- tnsnames.ora: This file is required. It defines Oracle Net Services to which
 applications connect. For TimesTen Cache, this file configures the connectivity
 between TimesTen and the Oracle Database (from which data is being cached). In
 this context, TimesTen is the application that is the connection to the Oracle
 Database. See "tnsnames.ora" for more information on this file.
- sqlnet.ora: This file may be required. It may be necessary depending on your
 Oracle Database configuration. The file defines options for how client applications
 communicate with the Oracle Database. In this context, TimesTen is the
 application. The tnsnames.ora and sqlnet.ora files together define how an
 application communicates with the Oracle Database. See "sqlnet.ora" for
 information on this file.
- db.ini: This file is required if you are using TimesTen Cache. The contents of this file contain TimesTen connection attributes for your TimesTen databases, which will be included in TimesTen's sys.odbc.ini file. For TimesTen Cache, you must specify the OracleNetServiceName and the DatabaseCharacterSet connection attributes. The DatabaseCharacterSet connection attribute must match the Oracle database character set. See "db.ini" for more information on this file.
- schema.sql: The contents of this file contain database objects, such as tables, sequences, and users. The instance administrator uses the ttlsql utility to run this file immediately after the database is created. This file is run before the Operator configures TimesTen Cache or replication, so ensure there are no cache definitions in this file.

In TimesTen Cache, one or more cache table users own the cache tables. If this cache table user is not the cache manager user, then you must specify the schema.sql file and in it you must include the schema user and assign the appropriate privileges to this schema user. For example, if the oratt schema user was created in the Oracle Database, and this user is not the TimesTen cache manager user, you must create the TimesTen oratt user in this file. See "Create the Oracle Database Users" for more information on the schema users in the Oracle Database. Also see "schema.sql" for more information on the schema.sql file

In addition, you can use these other supported metadata files:

- adminUser: The user in this file is created in the TimesTen databases and is granted ADMIN privileges. See "adminUser" for more information on this file.
- epilog.sql: The contents of this file contain operations that must be performed
 after the Operator configures replication. For example, if you are using XLA, you
 could create replicated bookmarks for XLA in this file. This file is run after cache
 and replication have been configured. See "epilog.sql" for more information on this
 file.

You can include these metadata files in one or more Kubernetes facilities (for example, in a Kubernetes Secret, in a ConfigMap, or in an init container). This ensures the metadata files are populated in the /ttconfig directory of the TimesTen containers. Note that there is no requirement as to how to get the metadata files into this /ttconfig directory. See "Populate the /ttconfig Directory" for more information.

This example uses the ConfigMap facility to populate the /ttconfig directory in your TimesTen containers. The adminUser, db.ini, schema.sql, cacheUser,



cachegroups.sql, tnsnames.ora, and sqlnet.ora metadata files are used in this example.

On your Linux development host:

1. From the directory of your choice, create an empty subdirectory for the metadata files. This example creates the cm_cachetest subdirectory. (The cm_cachetest directory is used in the remainder of this example to denote this directory.)

```
% mkdir -p cm cachetest
```

2. Navigate to the ConfigMap directory.

```
% cd cm cachetest
```

3. Create the adminUser file in this ConfigMap directory (cm_cachetest, in this example). In this adminUser file, create the sampleuser user with the samplepw password.

```
vi adminUser
sampleuser/samplepw
```

4. Create the db.ini file in this ConfigMap directory (cm_cachetest, in this example). In this db.ini file, define the PermSize, DatabaseCharacterSet, and the OracleNetServiceName connection attributes. The DatabaseCharacterSet value must match the database character set value in the Oracle Database. See "Create the Oracle Database Tables to Be Cached" for information on how to query the nls_database_parameters system view to determine the Oracle Database database character set. In this example, the value is AL32UTF8.

```
vi db.ini
PermSize=200
DatabaseCharacterSet=AL32UTF8
OracleNetServiceName=Oracache
```

5. Create the schema.sql file in this ConfigMap directory (cm_cachetest, in this example). In this example, create the oratt user. Recall that this user was previously created in the Oracle Database. See "Create the Oracle Database Users" for information on the oratt user in the Oracle Database.

```
vi schema.sql
create user oratt identified by ttpwd;
grant admin to oratt;
```

6. Create the cacheUser metadata file in this ConfigMap directory (cm_cachetest, in this example). The cacheUser file must contain one line of the form cacheuser/ttpassword/ orapassword, where cacheuser is the user you wish to designate as the cache manager in the TimesTen database, ttpassword is the TimesTen password you wish to assign to this user, and orapassword is the Oracle Database password that has already been assigned to the Oracle Database cache administration user. Note that the cacheUser name in this file must match the Oracle Database cache administration user that you previously created. See "Create the Oracle Database Users" for more information on the Oracle Database cache administration user.

In this example, the <code>cacheuser2</code> user with password of <code>oraclepwd</code> was already created in the Oracle Database. Therefore, supply <code>cacheuser2</code> as the TimesTen cache manager user. You can assign any TimesTen password to this TimesTen cache manager user. This example assigns <code>ttpwd</code>.



```
vi cacheuser
cacheuser2/ttpwd/oraclepwd
```

7. Create the cachegroups.sql metadata file in this ConfigMap directory (cm_cachetest, in this example). The cachegroups.sql file contains the cache group definitions. In this example, a dynamic AWT cache group and a read-only cache group are created. In addition, the LOAD CACHE GROUP statement is included to load rows from the oratt.readtab cached table in the Oracle Database into the oratt.readtab cache table in the TimesTen database.

```
vi cachegroups.sql

CREATE DYNAMIC ASYNCHRONOUS WRITETHROUGH CACHE GROUP writecache
FROM oratt.writetab (pk NUMBER NOT NULL PRIMARY KEY, attr VARCHAR2(40));

CREATE READONLY CACHE GROUP readcache
AUTOREFRESH
INTERVAL 5 SECONDS
FROM oratt.readtab (keyval NUMBER NOT NULL PRIMARY KEY, str VARCHAR2(32));

LOAD CACHE GROUP readcache COMMIT EVERY 256 ROWS;
```

8. Create the tnsnames.ora metadata file in this ConfigMap directory (cm_cachetest, in this example).

9. Create the sqlnet.ora metadata file in this ConfigMap directory (cm_cachetest, in this example).

```
vi sqlnet.ora

NAME.DIRECTORY_PATH= {TNSNAMES, EZCONNECT, HOSTNAME}
SQLNET.EXPIRE_TIME = 10
SSL VERSION = 1.2
```

10. Use the Linux 1s command to verify the metadata files are in the ConfigMap directory (cm_cachetest, in this example).

```
% ls
adminUser cacheUser schema.sql tnsnames.ora
cachegroups.sql db.ini sqlnet.ora
```

11. Create the ConfigMap. The files in the cm_cachetest directory are included in the ConfigMap and, later, will be available in the TimesTen containers.

In this example:



- The name of the ConfigMap is cachetest. Replace cachetest with a name of your choosing. (cachetest is represented in **bold** in this example.)
- This example uses cm_cachetest as the directory where the files that will be copied into the ConfigMap reside. If you use a different directory, replace cm_cachetest with the name of your directory. (cm_cachetest is represented in **bold** in this example.)

Use the kubectl create command to create the ConfigMap:

```
% kubectl create configmap cachetest --from-file=cm_cachetest
configmap/cachetest created
```

12. Use the kubectl describe command to verify the contents of the ConfigMap. (cachetest, in this example.) The metadata files are represented in **bold**.

```
% kubectl describe configmap cachetest;
Name: cachetest
Namespace: mynamespace Labels: <none>
Annotations: <none>
Data
tnsnames.ora:
OraTest =
   (ADDRESS = (PROTOCOL = TCP) (HOST = database.myhost.svc.cluster.local)
     (PORT = 1521))
   (CONNECT DATA =
     (SERVER = DEDICATED)
     (SERVICE NAME = OraTest.my.sample.com)))
OraCache =
 (DESCRIPTION =
   (ADDRESS = (PROTOCOL = TCP) (HOST = database.myhost.svc.cluster.local)
     (PORT = 1521))
   (CONNECT DATA =
     (SERVER = DEDICATED)
     (SERVICE NAME = OraCache.my.sample.com)))
adminUser:
sampleuser/samplepw
cacheUser:
cacheuser2/ttpwd/oraclepwd
cachegroups.sql:
CREATE DYNAMIC ASYNCHRONOUS WRITETHROUGH CACHE GROUP writecache
FROM oratt.writetab (
 pk NUMBER NOT NULL PRIMARY KEY,
 attr VARCHAR2(40)
);
CREATE READONLY CACHE GROUP readcache
AUTOREFRESH
 INTERVAL 5 SECONDS
FROM oratt.readtab (
  keyval NUMBER NOT NULL PRIMARY KEY,
```



You have successfully created and deployed the cachetest ConfigMap.

Create a TimesTenClassic Object

This section creates a TimesTenClassic object.

Perform these steps:

1. Create an empty YAML file. You can choose any name, but you may want to use the same name you used for the name of the TimesTenClassic object. (In this example, cachetest.) The YAML file contains the definitions for the TimesTenClassic object. See TimesTenClassicSpecSpec for information on the fields that you must specify in this YAML file as well as the fields that are optional.

In this example, note these fields:

- name: Replace cachetest with the name of your TimesTenClassic object (represented in **bold**).
- storageClassName: Replace oci-bv with the name of the storage class used to allocate PersistentVolumes to hold TimesTen.
- storageSize: Replace 250Gi with the amount of storage that should be requested for each Pod to hold TimesTen. Note: This example assumes a production environment and uses a value of 250Gi for storageSize. For demonstration purposes, a value of 50Gi is adequate.
- image: Replace container-registry.oracle.com/timesten/ timesten:22.1.1.19.0 with the location and name of your image.
- imagePullSecret: Replace sekret with the image pull secret that Kubernetes should use to fetch the TimesTen image.
- dbConfigMap: This example uses one ConfigMap (called cachetest) for the metadata files (represented in bold).

```
% vi cachetest.yaml
apiVersion: timesten.oracle.com/v1
kind: TimesTenClassic
metadata:
   name: cachetest
spec:
   ttspec:
    storageClassName: oci-bv
   storageSize: 250Gi
   image: container-registry.oracle.com/timesten/timesten:22.1.1.19.0
   imagePullSecret: sekret
   dbConfigMap:
   - cachetest
```

Use the kubectl create command to create the TimesTenClassic object from the
contents of the YAML file (in this example, cachetest.yaml). Doing so begins the
process of deploying your active standby pair of TimesTen databases in the Kubernetes
cluster.

```
% kubectl create -f cachetest.yaml
timestenclassic.timesten.oracle.com/cachetest created
```

You have successfully created the TimesTenClassic object in the Kubernetes cluster. The process of deploying your TimesTen databases begins, but is not yet complete.

Monitor Deployment of a TimesTenClassic Object

Use the kubectl get and the kubectl describe commands to monitor the progress of the active standby pair as it is provisioned.

1. Use the kubectl get command and review the STATE field. Observe the value is Initializing. The active standby pair provisioning has begun, but is not yet complete.

```
% kubectl get ttc cachetest
NAME STATE ACTIVE AGE
cachetest Initializing None 41s
```

2. Use the kubectl get command again to see if value of the STATE field has changed. In this example, the value is Normal, indicating the active standby pair of databases are now provisioned and the process is complete.

```
% kubectl get ttc cachetest
NAME STATE ACTIVE AGE
cachetest Normal cachetest-0 3m58s
```

Use the kubectl describe command to view the active standby pair provisioning in detail.

Note the following:

- The cachetest Configmap has been correctly referenced in the dbConfigMap field (represented in **bold**).
- The cache agent is running in the active and the standby Pods (represented in bold).
- The cache administration user UID and password have been set in the active and the standby Pods (represented in **bold**).
- Two cache groups have been created in the active and the standby Pods (represented in **bold**).

 The replication agent is running in the active and standby Pods (represented in **bold**).

```
% kubectl describe ttc cachetest
Name: cachetest
Namespace: mynamespace
Labels:
        <none>
Annotations: <none>
API Version: timesten.oracle.com/v1
        TimesTenClassic
Metadata:
 Creation Timestamp: 2023-10-24T03:29:48Z
 Generation:
                    1
 Resource Version: 78390500
Self Link: /apis/timesten.oracle.com/v1/namespaces/mynamespace/
timestenclassics/cachetest
                    2b18d81d-15a9-11eb-b999-be712d29a81e
Spec:
 Ttspec:
   Db Config Map:
     cachetest
   Image:
                      container-registry.oracle.com/timesten/
timesten:22.1.1.19.0
   Image Pull Policy: Always
   Image Pull Secret: sekret
   Storage Class Name: oci-bv
   Storage Size:
                      250Gi
Status:
 Active Pods: cachetest-0
 High Level State: Normal
 Last Event:
                 28
 Pod Status:
   Cache Status:
     Cache Agent:
                       Running
     Cache UID Pwd Set: true
     N Cache Groups:
   Db Status:
    Db:
                  Loaded
             30
     Db Id:
     Db Updatable: Yes
   Initialized: true
   Pod Status:
     Agent:
                        Uр
     Last Time Reachable: 1603510527
                        10.244.7.92
     Pod IP:
     Pod Phase:
                        Running
   Replication Status:
     Last Time Rep State Changed: 0
     Rep Agent:
                               Running
     Rep Peer P State:
                               start
     Rep Scheme:
                               Exists
     Rep State:
                                ACTIVE
   Times Ten Status:
     Daemon: Up
     Instance: Exists
Release: 22.1.1.19.0
     Release:
   Admin User File: true
   Cache User File: true
   Cg File:
                    true
   High Level State: Healthy
   Intended State: Active
```



```
Name:
                    cachetest-0
   Schema File:
                    true
   Cache Status:
     Cache Agent:
                        Running
     Cache UID Pwd Set: true
     N Cache Groups:
   Db Status:
     Db:
                  Loaded
     Db Td:
                  3.0
     Db Updatable: No
   Initialized:
                   true
   Pod Status:
     Agent:
     Last Time Reachable: 1603510527
     Pod IP:
                         10.244.8.170
     Pod Phase:
                         Running
   Replication Status:
     Last Time Rep State Changed: 1603510411
     Rep Agent:
                               Running
     Rep Peer P State:
                                start
     Rep Scheme:
                                Exists
     Rep State:
                                 STANDBY
   Times Ten Status:
     Daemon: Up
Instance: Exists
                    22.1.1.19.0
     Release:
   Admin User File: true
   Cache User File: true
   Cq File:
                      true
   High Level State: Healthy
                    Standby
   Intended State:
   Name:
                       cachetest-1
   Schema File:
                  true
  Rep Create Statement: create active standby pair "cachetest" on
  "cachetest-0.cachetest.mynamespace.svc.cluster.local", "cachetest" on
  "cachetest-1.cachetest.mynamespace.svc.cluster.local" NO RETURN store
  "cachetest" on "cachetest-0.cachetest.mynamespace.svc.cluster.local"
 PORT 4444 FAILTHRESHOLD 0 store "cachetest" on
 "cachetest-1.cachetest.mynamespace.svc.cluster.local" PORT 4444 FAILTHRESHOLD 0
 Rep Port:
                      4444
 Status Version:
                     1.0
Events:
                 Age From Message
 Type Reason
                   ----
  ----
                                   -----
      Create
                  5m40s ttclassic Secret tt2b18d81d-15a9-11eb-b999-
be712d29a81e created
      Create 5m40s ttclassic Service cachetest created
                 5m40s ttclassic StatefulSet cachetest created
       Create
       StateChange 4m28s ttclassic Pod cachetest-0 Agent Up
       StateChange 4m28s ttclassic Pod cachetest-0 Release 22.1.1.19.0
       StateChange 4m28s ttclassic Pod cachetest-0 Daemon Up
       StateChange 3m18s ttclassic Pod cachetest-0 RepScheme None
       StateChange 3m18s ttclassic Pod cachetest-0 RepAgent Not Running
       StateChange 3m18s ttclassic Pod cachetest-0 RepState IDLE
       StateChange 3m18s ttclassic Pod cachetest-0 Database Loaded
       StateChange 3m18s ttclassic Pod cachetest-0 Database Updatable
       StateChange 3m18s ttclassic Pod cachetest-0 CacheAgent Not Running
       StateChange 2m57s ttclassic Pod cachetest-0 CacheAgent Running
       StateChange 2m47s ttclassic Pod cachetest-1 Agent Up
       StateChange 2m47s ttclassic Pod cachetest-1 Release 22.1.1.19.0
       StateChange 2m46s ttclassic Pod cachetest-0 RepAgent Running
```



```
- StateChange 2m46s ttclassic Pod cachetest-0 RepScheme Exists
- StateChange 2m46s ttclassic Pod cachetest-0 RepState ACTIVE
- StateChange 2m46s ttclassic Pod cachetest-1 Daemon Up
- StateChange 2m9s ttclassic Pod cachetest-1 CacheAgent Running
- StateChange 2m9s ttclassic Pod cachetest-1 Database Not Updatable
- StateChange 2m9s ttclassic Pod cachetest-1 Database Loaded
- StateChange 2m9s ttclassic Pod cachetest-1 RepAgent Not Running
- StateChange 2m9s ttclassic Pod cachetest-1 RepScheme Exists
- StateChange 2m9s ttclassic Pod cachetest-1 RepScheme Exists
- StateChange 2m9s ttclassic Pod cachetest-1 RepState IDLE
- StateChange 2m3s ttclassic Pod cachetest-1 RepAgent Running
- StateChange 118s ttclassic Pod cachetest-1 RepState STANDBY
- StateChange 118s ttclassic TimesTenClassic was Initializing, now
```

Your active standby pair of TimesTen databases are successfully deployed (as indicated by Normal.) You are now ready to verify that TimesTen Cache is configured correctly and is working properly.

Verify TimesTen Cache Configuration

To verify that TimesTen Cache is configured correctly and is working properly, perform the following steps:

1. Review the active (cachetest-0, in this example) Pod and the standby Pod (cachetest-1, in this example).

2. Use the kubectl exec -it command to invoke the shell in the active Pod (cachetest-0, in this example).

```
% kubectl exec -it cachetest-0 -c tt -- /bin/bash
```

3. Use ttIsql to connect to the cachetest database. Confirm the TimesTen connection attributes are correct. In particular, note that the OracleNetServiceName connection attribute is correctly set to Oracache (represented in **bold**).

```
% ttIsql cachetest;
Copyright (c) 1996, 2023, Oracle and/or its affiliates. All rights reserved.
Type ? or "help" for help, type "exit" to quit ttIsql.

connect "DSN=cachetest";
Connection successful: DSN=cachetest;UID=timesten;DataStore=/tt/home/
timesten/datastore/cachetest;
DatabaseCharacterSet=AL32UTF8;ConnectionCharacterSet=AL32UTF8;AutoCreate=0;
PermSize=200;OracleNetServiceName=Oracache;DDLReplicationLevel=3;
ForceDisconnectEnabled=1;
(Default setting AutoCommit=1)
```

4. Use the ttIsql cachegroups to view the definition of the cacheuser2.readcache and the cacheuser2.writecache cache groups.

```
Command> cachegroups;
Cache Group CACHEUSER2.READCACHE:
 Cache Group Type: Read Only
 Autorefresh: Yes
 Autorefresh Mode: Incremental
 Autorefresh State: On
 Autorefresh Interval: 5 Seconds
 Autorefresh Status: ok
 Aging: No aging defined
 Root Table: ORATT.READTAB
 Table Type: Read Only
Cache Group CACHEUSER2.WRITECACHE:
 Cache Group Type: Asynchronous Writethrough (Dynamic)
 Autorefresh: No
 Aging: LRU on
 Root Table: ORATT.WRITETAB
 Table Type: Propagate
2 cache groups found.
```

5. Use ttIsql to query the oratt.readtab cache table. Note that the data from the oratt.readtab cached table in the Oracle Database is correctly loaded in the oratt.readcache cache table in the TimesTen database. Recall that you specified the LOAD CACHE GROUP statement in the cachegroups.sql metadata file. See Create Metadata Files and a Kubernetes Facility for information on this cachegroups.sql metadata file.

```
Command> SELECT * FROM oratt.readtab;
< 1, Hello >
< 2, World >
2 rows found.
```

You have verified that the cache groups were created and data was correctly loaded in the oratt.readtab table.

Perform Operations On Cache Group Tables

The examples in this section perform operations on the <code>oratt.readtab</code> and the <code>oratt.writetab</code> tables to verify that TimesTen Cache is working properly.

- Perform Operations on the oratt.readtab Table
- Perform Operations on the oratt.writetab Table

Perform Operations on the oratt.readtab Table

This section performs operations on the oratt.readtab table.

Create a shell from which you can access your Oracle Database and then use SQL*Plus
to connect to the Oracle Database as the schema user (oratt, in this example). Then,
insert a new row, delete an existing row, and update an existing row in the
oratt.readtab table of the Oracle Database and commit the changes.



```
% sqlplus oratt/oraclepwd@oracache;
SQL> INSERT INTO oratt.readtab VALUES (3,'Welcome');
1 row created.
SQL> DELETE FROM oratt.readtab WHERE keyval=2;
1 row deleted.
SQL> UPDATE oratt.readtab SET str='Hi' WHERE keyval=1;
1 row updated.
SQL> COMMIT;
Commit complete.
```

Since the read-only cache group was created with an autorefresh interval of 5 seconds, the TimesTen <code>oratt.readtab</code> cache table in the <code>readcache</code> cache group is automatically refreshed after 5 seconds with the committed updates from the <code>cached oratt.readtab</code> table of the Oracle Database. The next step is to test that the data was correctly propagated from the Oracle Database to the TimesTen database.

2. Use the kubectl exec -it command to invoke the shell in the container of the Pod that is running the TimesTen active database (cachetest-0, in this example).

```
% kubectl exec -it cachetest-0 -c tt -- /bin/bash
```

3. Use the TimesTen ttIsql utility to connect to the cachetest database. Query the TimesTen oratt.readtab table to verify that the table has been updated with the committed updates from the Oracle Database.

```
% ttIsql cachetest;
Copyright (c) 1996, 2023, Oracle and/or its affiliates. All rights reserved.
Type ? or "help" for help, type "exit" to quit ttIsql.

connect "DSN=cachetest";
Connection successful: DSN=cachetest;UID=timesten;DataStore=/tt/home/
timesten/datastore/cachetest;
DatabaseCharacterSet=AL32UTF8;ConnectionCharacterSet=AL32UTF8;AutoCreate=0;
PermSize=200;OracleNetServiceName=Oracache;DDLReplicationLevel=3;
ForceDisconnectEnabled=1;
(Default setting AutoCommit=1)

Command> SELECT * FROM oratt.readtab;
< 1, Hi >
< 3, Welcome >
2 rows found.
```

You have verified that TimesTen Cache is working correctly for the <code>oratt.readtab</code> table and the <code>readcache</code> cachegroup.

Perform Operations on the oratt.writetab Table

This example performs operations on the oratt.writetab table.



1. Use the kubectl exec -it command to invoke the shell in the container of the Pod that is running the TimesTen active database (cachetest-0, in this example).

```
% kubectl exec -it cachetest-0 -c tt -- /bin/bash
```

2. Use the TimesTen ttlsql utility to connect to the cachetest database as the cache manager user (cacheuser2, in this example). Issue a SELECT statement on the TimesTen oratt.writetab table. Recall that the writecache cache group is a dynamic cache group. Thus by issuing the SELECT statement, the cache instance is automatically loaded from the cached Oracle Database table, if the data is not found in the TimeTen cache table.

```
% ttIsql "DSN=cachetest;UID=cacheuser2;PWD=ttpwd;OraclePWD=oraclepwd";
Copyright (c) 1996, 2023, Oracle and/or its affiliates. All rights reserved.
Type ? or "help" for help, type "exit" to quit ttIsql.

connect "DSN=cachetest;UID=cacheuser2;PWD=*******;OraclePWD=********;
Connection successful: DSN=cachetest;UID=cacheuser2;DataStore=/tt/home/timesten/datastore/cachetest;
DatabaseCharacterSet=AL32UTF8;ConnectionCharacterSet=AL32UTF8;AutoCreate=0;PermSize=200;OracleNetServiceName=Oracache;DDLReplicationLevel=3;ForceDisconnectEnabled=1;
(Default setting AutoCommit=1)

Command> SELECT * FROM oratt.writetab WHERE pk=100;
< 100, TimesTen >
1 row found.
```

3. Use ttIsql to insert a new row, delete an existing row, and update an existing row in the TimesTen oratt.writetab cache table, and commit the changes.

```
Command> INSERT INTO oratt.writetab VALUES (102,'Cache');
1 row inserted.
Command> DELETE FROM oratt.writetab WHERE pk=101;
1 row deleted.
Command> UPDATE oratt.writetab SET attr='Oracle' WHERE pk=100;
1 row updated.
Command> COMMIT;
```

The committed updates on the TimesTen oratt.writetab cache table in the writecache cache group should automatically be propagated to the oratt.writetab table in the Oracle Database.

4. Create a shell from which you can access your Oracle Database and then use SQL*Plus to connect to the Oracle database as the schema user (oratt, in this example). Then query the contents of the oratt.writetab table in the Oracle Database to verify the committed updates from the TimesTen database have been propagated to the oratt.writetab table of the Oracle Database.

```
% sqlplus oratt/oraclepwd@orapcache;
SQL> SELECT * FROM oratt.writetab ORDER BY pk;

PK ATTR

100 Oracle
102 Cache
```



You have verified that TimesTen Cache is working correctly for the <code>oratt.writetab</code> table and the <code>writecache</code> cachegroup.

Clean Up Cache Metadata on the Oracle Database

When you create certain types of cache groups in a TimesTen database, TimesTen stores metadata about that cache group in the Oracle Database. If you later delete that TimesTen database, TimesTen does not automatically delete the metadata in the Oracle Database. As a result, metadata can accumulate on the Oracle Database. See Dropping Oracle Database Objects Used by Cache Groups with Autorefresh in the Oracle TimesTen In-Memory Database Cache Guide for more information.

However, in a Kubernetes environment, if you provide a cacheUser metadata file and a cachegroups.sql metadata file when you initially create the TimesTenClassic object, then, by default, the Operator automatically cleans up the Oracle Database metadata if you delete that TimesTenClassic object.

If you do not want the Operator to automatically clean up the Oracle Database, you set the <code>cacheCleanup</code> field in the TimesTenClassic object definition to <code>false</code>. See the <code>cacheCleanup</code> entry in "Table 17-3" for more information. Also see "About Configuration Metadata Details" for information on the <code>cacheUser</code> and the <code>cachegroups.sql</code> files.



C

TimesTen Cache in TimesTen Scaleout Example

The TimesTen Operator supports the use of TimesTen Cache with TimesTen Scaleout in your Kubernetes environment.

This appendix shows a complete example. The example should not be used for production purposes. It assumes a test environment. Your Oracle Database should be customized with the settings specific to your environment.

Topics:

- Set Up the Oracle Database to Cache Data
- Create Metadata Files and a Kubernetes Facility
- Create a TimesTenScaleout Object
- Monitor Deployment of a TimesTenScaleout Object
- Verify TimesTen Cache Configuration
- Perform Operations on the oratt_grid.readtab Table
- Clean Up Cache Metadata on the Oracle Database

Set Up the Oracle Database to Cache Data

You need to complete tasks in the Oracle database before using TimesTen Cache. The tasks are described in the following sections:

- Create the Oracle Database Users
- Grant Privileges to the Cache Administration User
- Create the Oracle Database Table to Be Cached

Create the Oracle Database Users

Before you can use TimesTen Cache, you need to create the following users in your Oracle database:

- A cache administration user. This user creates and maintains Oracle Database objects that store information about the cache environment. This user also enforces predefined behaviors of cache group types.
- One or more schema users who owns Oracle Database tables that are cached in a TimesTen database.

See Create the Oracle Database Users and Default Tablespace in the *Oracle TimesTen In-Memory Database Cache Guide*.

This example creates the cacheuser_grid cache administration user and the oratt_grid schema user in the Oracle Database.

 Create a shell from which you can access your Oracle Database and then use SQL*Plus to connect to the Oracle Database as the sys user. Then, create a default tablespace for the schema user and a default tablespace for the cache administration user.

sqlplus sys/syspwd@oracache as sysdba

Create a tablespace for the schema user (oratt grid).

CREATE TABLESPACE cachegridtablespace1 DATAFILE 'datattgrid1.dbf' SIZE 100M;

The output is the following.

Tablespace created.

Create a tablespace for the cache administration user (cacheuser grid).

CREATE TABLESPACE cachegridtablespace2 DATAFILE 'datattgrid2.dbf' SIZE 100M;

The output is the following.

Tablespace created.

See Create the Oracle Database Users and Default Tablespace in the *Oracle TimesTen In-Memory Database Cache Guide*.

 Use SQL*Plus to create the schema user. Grant this schema user the minimum privileges required to create tables in the Oracle Database to be cached in your TimesTen database.

This example creates the oratt grid schema user.

CREATE USER oratt_grid IDENTIFIED BY oraclepwd DEFAULT TABLESPACE cachegridtablespace1 QUOTA UNLIMITED ON cachegridtablespace1;

The output is the following.

User created.

GRANT CREATE SESSION, RESOURCE TO oratt grid;

The output is the following.

Grant succeeded.

3. Use SQL*Plus to create the cache administration user. Later, you will use the same name in the cacheUser metadata file.



This example creates the cacheuser grid user.

CREATE USER cacheuser_grid IDENTIFIED BY oraclepwd DEFAULT TABLESPACE cachegridtablespace2 QUOTA UNLIMITED ON cachegridtablespace2;

The output is the following.

User created.

Commit and then exit SQL*Plus.

commit;

exit;

Exit the shell.

exit;

Grant Privileges to the Cache Administration User

The cache administration user needs a specific set of privileges to work with TimesTen cache groups. TimesTen provides the <code>grantCacheAdminPrivileges.sql</code> SQL*Plus script as part of the TimesTen installation distribution. You run this script in your Oracle database to grant the cache administration user the minimum set of privileges required to perform cache operations. See Grant Privileges to the Oracle Cache Administration User and see Required Privileges for Cache Administration User for Cache Operations in the <code>Oracle TimesTen In-Memory Database Cache Guide</code>.

Perform these steps to run the grantCacheAdminPrivileges.sql script:

 Create a shell from which you can access your Oracle Database, and then from the directory of your choice, create an empty subdirectory. This example creates the oraclescripts subdirectory.

```
mkdir -p oraclescripts
```

2. From your Linux development host, use the kubectl cp command to copy the grantCacheAdminPrivileges.sql script from the installation_dir/oraclescripts directory on your Linux development host to the oraclescripts directory that you just created.





You must unpack the TimesTen distribution to retrieve the <code>installation_dir/oraclescripts/grantCacheAdminPrivileges.sql</code> directory. See Unpack the TimesTen and the TimesTen Operator Distributions.

kubectl cp /installation_dir/oraclescripts/
grantCacheAdminPrivileges.sql
database-oracle:oraclescripts/grantCacheAdminPrivileges.sql

(Optional): From your shell, verify the script is located in the oraclescripts directory.

ls oraclescripts

The output is the following.

grantCacheAdminPrivileges.sql

4. Change to the database-oracle:oraclescripts directory. Next, use SQL*Plus to connect to the Oracle Database as the sys user. Next, run the grantCacheAdminPrivileges.sql script.

cd oraclescripts

sqlplus sys/syspwd@oracache as sysdba

In SQL*Plus, run the SQL script.

@grantCacheAdminPrivileges "cacheuser grid";

The output is similar to the following.

Please enter the administrator user id
The value chosen for administrator user id is cacheuser grid

- 0. Granting the CREATE SESSION privilege to CACHEUSER GRID
- 1. Granting the TT CACHE ADMIN ROLE to CACHEUSER GRID
- 2. Granting the DBMS LOCK package privilege to CACHEUSER GRID
- 3. Granting the DBMS DDL package privilege to CACHEUSER GRID
- 4. Granting the DBMS FLASHBACK package privilege to CACHEUSER GRID
- 5. Granting the CREATE SEQUENCE privilege to CACHEUSER GRID
- 6. Granting the CREATE CLUSTER privilege to CACHEUSER GRID
- 7. Granting the CREATE OPERATOR privilege to CACHEUSER GRID
- 8. Granting the CREATE INDEXTYPE privilege to CACHEUSER GRID



```
9. Granting the CREATE TABLE privilege to CACHEUSER GRID
10. Granting the CREATE PROCEDURE privilege to CACHEUSER GRID
11. Granting the CREATE ANY TRIGGER privilege to CACHEUSER GRID
12. Granting the GRANT UNLIMITED TABLESPACE privilege to CACHEUSER GRID
13. Granting the DBMS LOB package privilege to CACHEUSER GRID
14. Granting the SELECT on SYS.ALL OBJECTS privilege to CACHEUSER GRID
15. Granting the SELECT on SYS.ALL SYNONYMS privilege to CACHEUSER GRID
16. Checking if the cache administrator user has permissions on the
default
tablespace
    Permission exists
18. Granting the CREATE TYPE privilege to CACHEUSER GRID
19. Granting the SELECT on SYS.GV$LOCK privilege to CACHEUSER GRID
20. Granting the SELECT on SYS.GV$SESSION privilege to CACHEUSER GRID
21. Granting the SELECT on SYS.DBA DATA FILES privilege to CACHEUSER GRID
22. Granting the SELECT on SYS.USER USERS privilege to CACHEUSER GRID
23. Granting the SELECT on SYS.USER FREE SPACE privilege to
CACHEUSER GRID
24. Granting the SELECT on SYS.USER TS QUOTAS privilege to CACHEUSER GRID
25. Granting the SELECT on SYS.USER SYS PRIVS privilege to CACHEUSER GRID
26. Granting the SELECT on SYS.V$DATABASE privilege to CACHEUSER GRID
(optional)
27. Granting the SELECT on SYS.GV$PROCESS privilege to CACHEUSER GRID
(optional)
28. Granting the SELECT ANY TRANSACTION privilege to CACHEUSER GRID
29. Creating the CACHEUSER GRID.TT 07 ARDL CG COUNTER table
30. Granting SELECT privilege on CACHEUSER GRID.TT 07 ARDL CG COUNTER
table to
PUBLIC
****** Initialization for cache admin user done successfully *******
Exit from SQL*Plus and the shell.
exit;
exit;
```

You successfully ran the script to grant privileges to the cache administration user.

Create the Oracle Database Table to Be Cached

This example creates the readtab table in the oratt_grid user schema. Later, the table is cached in a read-only cache group.

1. Create a shell from which you can access your Oracle Database and then use SQL*Plus to connect to the Oracle Database as the sys user. Then create the oratt grid.readtab table.

```
sqlplus sys/syspwd@oracache as sysdba

CREATE TABLE oratt_grid.readtab (keyval NUMBER NOT NULL PRIMARY
KEY,str VARCHAR2(32));
```

The output is the following.

Table created.

2. Use SQL*Plus to insert rows into the <code>oratt_grid.readtab</code> table. Next, verify the rows have been inserted.

```
INSERT INTO oratt_grid.readtab VALUES (1,'Hello');
INSERT INTO oratt grid.readtab VALUES (2,'World');
```

Commit.

commit;

Verify the rows have been inserted into the tables.

```
SELECT * FROM oratt grid.readtab;
```

The output is the following.

```
KEYVAL STR

1 Hello
2 World
```

3. Use SQL*Plus to grant the SELECT privilege on the oratt grid.readtab table.

```
GRANT SELECT ON oratt grid.readtab TO cacheuser grid;
```

The output is the following.

Grant succeeded.

4. Use SQL*Plus to query the nls_database_parameters system view to determine the Oracle Database database character set. The Oracle Database database character set must match the TimesTen database character set.



In this example, the guery returns the AL32UTF8 database character set.

You successfully created the Oracle Database table. Later, this table is cached in the TimesTen cache group.

Create Metadata Files and a Kubernetes Facility

The following metadata files are specific to using TimesTen Cache:

- cacheUser: This file is required. The user in this file is created in the TimesTen databases
 and serves as the cache manager. The name of this user must match the name of the
 cache administration user that you created in the Oracle Database. See Create the
 Oracle Database Users for information on the cache administration user in the Oracle
 Database. See cacheUser for more information on the cacheUser metadata file.
- cachegroups.sql: This file is required. The contents of this file contain the CREATE CACHE
 GROUP definitions. The file can also contain the LOAD CACHE GROUP statement and the builtin procedures to update statistics on the cache group tables (such as,
 ttOptEstimateStats and ttOptUpdateStats). See cachegroups.sql.
- tnsnames.ora: This file is required. It defines Oracle Net Services to which applications
 connect. For TimesTen Cache, this file configures the connectivity between TimesTen
 and the Oracle Database (from which data is being cached). In this context, TimesTen is
 the application that is the connection to the Oracle Database. See tnsnames.ora.
- sqlnet.ora: This file may be required. It may be necessary depending on your Oracle
 Database configuration. The file defines options for how client applications communicate
 with the Oracle Database. In this context, TimesTen is the application. The tnsnames.ora
 and sqlnet.ora files together define how an application communicates with the Oracle
 Database. See sqlnet.ora.
- db.ini: This file is required if you are using TimesTen Cache. The contents of this file contain TimesTen connection attributes for your TimesTen databases, which will be included in TimesTen's sys.odbc.ini file. For TimesTen Cache, you must specify the OracleNetServiceName and the DatabaseCharacterSet connection attributes. The DatabaseCharacterSet connection attribute must match the Oracle database character set. See db.ini.



schema.sql: The contents of this file contain database objects, such as tables, sequences, and users. The instance administrator uses the ttlsql utility to run this file immediately after the database is created. This file is run before the Operator configures TimesTen Cache or replication, so ensure there are no cache definitions in this file.

In TimesTen Cache, one or more cache table users own the cache tables. If this cache table user is not the cache manager user, then you must specify the <code>schema.sql</code> file and in it you must include the schema user and assign the appropriate privileges to this schema user. For example, if the <code>oratt_grid</code> schema user was created in the Oracle Database, and this user is not the TimesTen cache manager user, you must create the TimesTen <code>oratt_grid</code> user in this file. See Create the Oracle Database Users for more information on the schema users in the Oracle Database. Also see <code>schema.sql</code> for more information on the <code>schema.sql</code> file.

In addition, use these metadata files for TimesTenScaleout objects:

- *.connect: A file with the .connect extension signifies a direct connectable that is
 used for direct mode access to a database in TimesTen Scaleout. The * prefix is
 the name you choose for the connectable. You can define more than one. See
 *.connect.
- *.csconnect: A file with the .csconnect extension signifies a client/server connectable that is used for client/server access to a database in TimesTen Scaleout. The * prefix is the name you choose for the connectable. You can define more than one. See *.csconnect.
- adminUser (Optional): The user in this file is created in the TimesTen databases and is granted ADMIN privileges. See adminUser for more information on this file.

You can include these metadata files in one or more Kubernetes facilities (for example, in a Kubernetes Secret, in a ConfigMap, or in an init container). This ensures the metadata files are populated in the /ttconfig directory of the TimesTen containers. Note that there is no requirement as to how to get the metadata files into this /ttconfig directory. See Populate the /ttconfig Directory for more information.

This example uses the ConfigMap facility to populate the <code>/ttconfig</code> directory in your TimesTen containers.

On your Linux development host:

1. From the directory of your choice, create an empty subdirectory for the metadata files. This example creates the cm cachegrid subdirectory.

```
mkdir -p cm_cachegrid
```

2. Change to the cm cachegrid directory.

```
cd cm cachegrid
```

3. Create the adminuser file in this ConfigMap directory.

```
vi adminUser
adminuser grid/adminuserpwd
```



4. Create the db.ini file in this ConfigMap directory. In this db.ini file, define the PermSize, DatabaseCharacterSet, and the OracleNetServiceName connection attributes. The DatabaseCharacterSet value must match the database character set value in the Oracle Database. See Create the Oracle Database Tables to Be Cached for information on how to query the nls_database_parameters system view to determine the Oracle Database database character set. In this example, the value is AL32UTF8.

```
vi db.ini
permSize=200
databaseCharacterSet=AL32UTF8
oracleNetServiceName=Oracache
```

5. Create the schema.sql file in this ConfigMap directory. In this example, create the oratt_grid user. Recall that this user was previously created in the Oracle Database. See Create the Oracle Database Users for information on the oratt_grid user in the Oracle Database.

```
vi schema.sql
create user oratt_grid identified by ttpwd;
grant admin to oratt grid;
```

6. Create the cacheUser metadata file in this ConfigMap directory. The cacheUser file must contain one line of the form cacheuser_grid/ttpassword/orapassword, where cacheuser_grid is the user you wish to designate as the cache manager in the TimesTen database, ttpassword is the TimesTen password you wish to assign to this user, and orapassword is the Oracle Database password that has already been assigned to the Oracle Database cache administration user. Note that the name in this file must match the Oracle Database cache administration user that you previously created. See Create the Oracle Database Users for more information on the Oracle Database cache administration user.

In this example, the <code>cacheuser_grid</code> user with password of <code>oraclepwd</code> was already created in the Oracle Database. Therefore, supply <code>cacheuser_grid</code> as the TimesTen cache manager user. You can assign any TimesTen password to this TimesTen cache manager user. This example assigns <code>ttpwd</code>.

```
vi cacheuser_grid
cacheuser_grid/ttpwd/oraclepwd
```

7. Create the cachegroups.sql metadata file in this ConfigMap directory. The cachegroups.sql file contains the cache group definitions. In this example, a read-only cache group is created. In addition, the LOAD CACHE GROUP statement is included to load rows from the oratt_grid.readtab table in the Oracle Database into the oratt_grid.readtab cache table in the TimesTen database.

```
vi cachegroups.sql

CREATE READONLY CACHE GROUP readcache
AUTOREFRESH
INTERVAL 5 SECONDS
FROM oratt grid.readtab (
```



```
keyval NUMBER NOT NULL PRIMARY KEY,
str VARCHAR2(32)
);
LOAD CACHE GROUP readcache COMMIT EVERY 256 ROWS;
```

8. Create the tnsnames.ora metadata file in this ConfigMap directory.

```
vi tnsnames.ora
OraTest =
 (DESCRIPTION =
   (ADDRESS = (PROTOCOL = TCP) (HOST =
database.mynamespace.svc.cluster.local)
     (PORT = 1521))
   (CONNECT DATA =
     (SERVER = DEDICATED)
     (SERVICE NAME = OraTest.my.sample.com)))
OraCache =
 (DESCRIPTION =
   (ADDRESS = (PROTOCOL = TCP) (HOST =
database.mynamespace.svc.cluster.local)
     (PORT = 1521))
   (CONNECT DATA =
     (SERVER = DEDICATED)
     (SERVICE NAME = OraCache.my.sample.com)))
```

9. Create the sqlnet.ora metadata file in this ConfigMap directory.

```
vi sqlnet.ora

NAME.DIRECTORY_PATH= {TNSNAMES, EZCONNECT, HOSTNAME}
SQLNET.EXPIRE_TIME = 10
SSL VERSION = 1.2
```

10. Create the direct connectable.

```
vi cachegriddirect.connect
ConnectionCharacterSet=AL32UTF8
```

11. Create the client/server connectable.

```
vi cachegridclient.csconnect
ConnectionCharacterSet=AL32UTF8
TTC_Timeout=30
```

12. (Optional): Use the Linux ls command to verify the metadata files are in the ConfigMap directory.

ls



The output is the following.

```
adminUser cachegroups.sql schema.sql cachegridclient.csconnect cacheUser sqlnet.ora cachegriddirect.connect db.ini tnsnames.ora
```

13. Create the ConfigMap.

In this example:

- The name of the ConfigMap is cachegrid. Replace cachegrid with a name of your choosing.
- This example uses cm_cachegrid as the directory for the ConfigMap files. If you use a different directory, replace cm_cachegrid with the name of your directory.

```
kubectl create configmap cachegrid --from-file .
```

The files in the <code>cm_cachegrid</code> directory are included in the ConfigMap and, later, will be available in the TimesTen containers.

14. Use the kubectl describe command to verify the contents of the ConfigMap.

```
kubectl describe configmap cachegrid
```

The output is the following.

```
cachegrid
Name:
Namespace: mynamespace
Labels:
            <none>
Annotations: <none>
Data
cachegroups.sql:
CREATE READONLY CACHE GROUP readcache
AUTOREFRESH
 INTERVAL 5 SECONDS
FROM oratt grid.readtab (
 keyval NUMBER NOT NULL PRIMARY KEY,
 str VARCHAR2(32)
);
LOAD CACHE GROUP readcache COMMIT EVERY 256 ROWS;
db.ini:
permSize=200
databaseCharacterSet=AL32UTF8
oracleNetServiceName=Oracache
sqlnet.ora:
NAME.DIRECTORY PATH= {TNSNAMES, EZCONNECT, HOSTNAME}
```

```
SQLNET.EXPIRE TIME = 10
SSL VERSION = 1.2
tnsnames.ora:
OraTest = (DESCRIPTION =
             (ADDRESS = (PROTOCOL = TCP)(HOST =
database.myhost.svc.cluster.local)
                (PORT = 1521))
              (CONNECT DATA =
                (SERVER = DEDICATED)
                (SERVICE NAME = Oratest.my.sample.com)))
OraCache =
            (DESCRIPTION =
               (ADDRESS = (PROTOCOL = TCP) (HOST =
database.myhost.svc.cluster.local)
                 (PORT = 1521))
               (CONNECT DATA =
                 (SERVER = DEDICATED)
                 (SERVICE NAME = OraCache)))
adminUser:
adminuser grid/adminuserpwd
cachegridclient.csconnect:
ConnectionCharacterSet=AL32UTF8
TTC Timeout=30
cachegriddirect.connect:
ConnectionCharacterSet=AL32UTF8
cacheUser:
cacheuser grid/ttpwd/oraclepwd
schema.sql:
create user oratt grid identified by ttpwd;
grant admin to oratt grid;
Events: <none>
```

You successfully created and deployed the cachegrid ConfigMap.

Create a TimesTenScaleout Object

This section creates the TimesTenScaleout object.

Perform these steps:

1. Create an empty YAML file. You can choose any name, but you may want to use the same name you used for the name of the TimesTenScaleout object. (In this

example, cachegrid.) See TimesTenScaleoutSpecSpec for information on the fields that you must specify in this YAML file as well as the fields that are optional.

Specify these TimesTen Scaleout specific fields:

• k: Set the value of k to the number of copies of data for your TimesTen database. This value determines the number of StatefulSets that the TimesTen Operator creates. A StatefulSet provides the Pods that are used to implement a single data space in the grid. For example, if you set k to 2, the Operator creates two StatefulSets. One StatefulSet provides the Pods for the data instances in data space one. The second StatefulSet provides the Pods for the data instances in data space two.

This example sets k to 2.

For information on K-safety and determining an appropriate value for k, see K-Safety in the *Oracle TimesTen In-Memory Database Scaleout User's Guide*.

• nReplicaSets: Set the value to the number of replica sets in the grid. A replica set contains k elements (where each element is an exact copy of the other elements in the replica set). The nReplicaSets value determines the number of replicas for each StatefulSet. For example, if you set k to 2, the TimesTen Operator creates two StatefulSets for the data instances. If you set nReplicaSets to 3, each StatefulSet contains three replicas, and the total number of replica sets in the database is three.

This example sets nReplicaSets to 3.

For information on replica sets, see Understanding Replica Sets in the *Oracle TimesTen In-Memory Database Scaleout User's Guide*.

• nZookeeper: Set the value to the number of ZooKeeper Pods to provision in a StatefulSet. Your options are 1 or 3 or 5.

This example sets nZookeeper to 3.

Next, specify these fields:

- name: Replace cachegrid with the name of your TimesTenClassic object.
- storageClassName: Replace oci-by with the name of the storage class used to allocate PersistentVolumes to hold TimesTen.
- storageSize: Replace 250Gi with the amount of storage that should be requested for each Pod to hold TimesTen. Note: This example assumes a production environment and uses a value of 250Gi for storageSize. For demonstration purposes, a value of 50Gi is adequate.
- image: Replace container-registry.oracle.com/timesten/timesten:22.1.1.19.0 with the location and name of your image.
- imagePullSecret: Replace sekret with the image pull secret that Kubernetes should use to fetch the TimesTen image.
- dbConfigMap: This example uses one ConfigMap (called cachegrid) for the metadata files.

```
vi cachetest.yaml
apiVersion: timesten.oracle.com/v1
kind: TimesTenScaleout
metadata:
```



```
name: cachegrid
spec:
  ttspec:
    storageClassName: oci-bv
    storageSize: 250Gi
    image: container-registry.oracle.com/timesten/
timesten:22.1.1.19.0
    imagePullSecret: sekret
    dbConfigMap:
    - cachegrid
    k: 2
    nReplicaSets: 3
    nZookeeper: 3
```

2. Create the TimesTenScaleout object.

```
kubectl create -f cachegrid.yaml
```

The output is the following.

```
timestenscaleout.timesten.oracle.com/cachegrid created
```

You successfully created the TimesTenScaleout object. The process of deploying your grid and associated databases begins, but is not yet complete.

Monitor Deployment of a TimesTenScaleout Object

Use the kubectl get and the kubectl describe commands to monitor the progress of the grid and its associated databases. There is one database in this example.

1. Use the kubectl get command and review the OVERALL field. Observe the value is Initializing.

```
kubectl get tts cachegrid
```

The output is similar to the following.

```
NAME OVERALL MGMT CREATE LOAD OPEN AGE cachegrid Initializing 12s
```

```
kubectl get tts cachegrid
```

The output is similar to the following.

```
NAME OVERALL MGMT CREATE LOAD OPEN AGE cachegrid ZookeeperReady 3m
```

kubectl get tts cachegrid



The output is similar to the following.

NAME OVERALL MGMT CREATE LOAD OPEN AGE cachegrid **GridCreated** 3m54s

kubectl get tts cachegrid

The output is similar to the following.

cachegrid	InstancesCreated					6m17s
NAME	OVERALL	MGMT	CREATE	LOAD	OPEN	AGE

kubectl get tts cachegrid

The output is similar to the following.

NAME	OVERALL	MGMT	CREATE	LOAD	OPEN	AGE
cachegrid	DatabaseCreated					6m59s

2. Use the kubectl get command again to see if the TimesTenScaleout object has transitioned to the Normal state. A Normal state indicates the grid and database are provisioned, and the process is complete.

kubectl get tts cachegrid

The output is similar to the following.

NAME	OVERALL	MGMT	CREATE	LOAD	OPEN	AGE
cachegrid	Normal	Normal	created	loaded-complete	open	8m29s

You successfully deployed your grid and database. Let's verify TimesTen Cache is configured correctly, and is working properly.

Verify TimesTen Cache Configuration

To verify that TimesTen Cache is configured correctly and is working properly, perform the following steps:

1. Review the Pods.

kubectl get pods

The output is similar to the following.

NAME	READY	STATUS	RESTARTS	AGE
cachegrid-data-1-0	2/2	Running	0	33m
cachegrid-data-1-1	2/2	Running	0	33m
cachegrid-data-1-2	2/2	Running	0	33m
cachegrid-data-2-0	2/2	Running	0	33m



cachegrid-data-2-1	2/2	Running	0
33m cachegrid-data-2-2	2/2	Running	0
33m cachegrid-mgmt-0	2/2	Running	0
33m	,	,	O
cachegrid-zk-0 33m	1/1	Running	0
cachegrid-zk-1	1/1	Running	0
32m cachegrid-zk-2	1/1	Running	0
31m	1 /1	D	0
timesten-operator-7677964df9-sp2zp 4d16h	1/1	Running	0

2. Use the kubectl exec -it command to invoke the shell in one of the data instances (cachegrid-data-1-0, in this example).

```
kubectl exec -it cachegrid-data-1-0 -c tt -- /bin/bash
```

3. Use ttIsql to connect to the cachegrid database. Confirm the TimesTen connection attributes are correct. In particular, note that the OracleNetServiceName connection attribute is correctly set to Oracache.

```
ttIsql cachegrid
```

The output is similar to the following.

```
Copyright (c) 1996, 2023, Oracle and/or its affiliates. All rights reserved.

Type ? or "help" for help, type "exit" to quit ttIsql.

connect "DSN=cachegrid";
Connection successful: DSN=cachegrid; Durability=0; UID=timesten;
DataStore=/tt/home/timesten/datastore/
cachegrid; DatabaseCharacterSet=AL32UTF8;
ConnectionCharacterSet=AL32UTF8; PermSize=200; Connections=100;
OracleNetServiceName=Oracache;
(Default setting AutoCommit=1)
```

4. Use the ttIsql cachegroups to view the cache group.

```
cachegroups;
```

The output is similar to the following.

Cache Group CACHEUSER_GRID.READCACHE:

Cache Group Type: Read Only

Autorefresh: Yes

Autorefresh Mode: Incremental

```
Autorefresh State: On
Autorefresh Interval: 5 Seconds
Autorefresh Status: ok
Aging: No aging defined

Root Table: ORATT_GRID.READTAB
Table Type: Read Only

1 cache group found.
```

5. Use ttIsql to query the oratt_grid.readtab cache table. Note that the data from the oratt_grid.readtab cached table in the Oracle Database is correctly loaded in the oratt_grid.readcache cache table in the TimesTen database. Recall that you specified the LOAD CACHE GROUP statement in the cachegroups.sql metadata file.

```
SELECT * FROM oratt_grid.readtab;
```

The output is similar to the following.

```
< 1, Hello > < 2, World > 2 rows found.
```

Exit ttIsql and the shell.

```
exit;
exit;
```

You verified that the cache group was created and data was correctly loaded.

Perform Operations on the oratt_grid.readtab Table

This section performs operations on the oratt grid.readtab table.

1. Create a shell from which you can access your Oracle Database and then use SQL*Plus to connect to the Oracle Database as the schema user (oratt_grid, in this example). Then, insert a new row, delete an existing row, and update an existing row in the oratt_grid.readtab table of the Oracle Database and commit the changes.

```
sqlplus oratt_grid/oraclepwd@oracache;

INSERT INTO oratt_grid.readtab VALUES (3,'Welcome');

DELETE FROM oratt_grid.readtab WHERE keyval=2;

UPDATE oratt_grid.readtab SET str='Hi' WHERE keyval=1;
```



Commit.

commit;

The output is the following.

```
Commit complete.
```

Since the read-only cache group was created with an autorefresh interval of 5 seconds, the TimesTen oratt_grid.readtab cache table in the readcache cache group is automatically refreshed after 5 seconds with the committed updates from the cached oratt_grid.readtab table of the Oracle Database. The next step is to test that the data was correctly propagated from the Oracle Database to the TimesTen database.

Exit ttlsql and exit the shell.

```
exit;
exit;
```

2. Use the kubectl exec -it command to invoke the shell in the container of the Pod that is running a data instance.

```
kubectl exec -it cachegrid-data-1-0 -c tt -- /bin/bash
```

3. Use the TimesTen ttlsql utility to connect to the cachegrid database. Query the TimesTen oratt_grid.readtab table to verify that the table has been updated with the committed updates from the Oracle Database.

```
ttIsql cachegrid
```

The output is similar to the following.

```
Copyright (c) 1996, 2023, Oracle and/or its affiliates. All rights reserved.

Type ? or "help" for help, type "exit" to quit ttIsql.

connect "DSN=cachegrid";
Connection successful: DSN=cachegrid; Durability=0; UID=timesten;
DataStore=/tt/home/timesten/datastore/cachegrid;
DatabaseCharacterSet=AL32UTF8; ConnectionCharacterSet=AL32UTF8; PermSize=200;
Connections=100; OracleNetServiceName=Oracache;
(Default setting AutoCommit=1)

SELECT * FROM oratt_grid.readtab;
```



The output is the following.

```
< 1, Hi >
< 3, Welcome >
2 rows found.

Exit ttIsql and exit the shell.

exit;
exit;
```

You have verified that TimesTen Cache is working correctly.

Clean Up Cache Metadata on the Oracle Database

When you create certain types of cache groups in a TimesTen database, TimesTen stores metadata about that cache group in the Oracle Database. If you later delete that TimesTen database, TimesTen does not automatically delete the metadata in the Oracle Database. As a result, metadata can accumulate on the Oracle Database. See Dropping Oracle Database Objects Used by Cache Groups with Autorefresh in the *Oracle TimesTen In-Memory Database Cache Guide* for more information.

However, in a Kubernetes environment, if you provide a cacheUser metadata file and a cachegroups.sql metadata file when you initially create the TimesTenScaleout object, then, by default, the Operator automatically cleans up the Oracle Database metadata if you delete that TimesTenScaleout object.

If you do not want the Operator to automatically clean up the Oracle Database, set the cacheCleanup field in the TimesTenScaleout object definition to false. See the cacheCleanup datum in TimesTenScaleoutSpecSpec.



D

Create Your Own Oracle Wallet, Certificates, and Secrets for Exposing TimesTen Metrics

By default, the TimesTen Operator automatically exposes TimesTen metrics and uses Transport Layer Security (mutual TLS)/https to serve these metrics. It exposes these metrics to Prometheus or any other scrape target.

The TimesTen Operator works with the TimesTen exporter to expose these metrics. For more information about the TimesTen exporter, see Overview of the TimesTen Kubernetes Operator and the TimesTen Exporter.

If TimesTen metrics are served by https, then by default the TimesTen Operator automatically creates an Oracle Wallet, all necessary certificates, and Kubernetes Secrets so that https can be used to expose TimesTen metrics securely.

For more information about how the TimesTen Operator exposes TimesTen metrics, see Expose TimesTen Metrics with the TimesTen Kubernetes Operator.

Although not recommended, you have the option of creating your own Oracle Wallet, certificates, and Kubernetes Secrets for use in exporting these metrics.

This appendix shows you how.

Topics:

- About Creating Your Own Oracle Wallet, Certificates, and Kubernetes Secrets
- Create Your Own Oracle Wallet, Certificates, and Kubernetes Secrets

About Creating Your Own Oracle Wallet, Certificates, and Kubernetes Secrets

You have the option of creating your own Oracle Wallet, certificates, and Kubernetes Secrets to serve TimesTen metrics by https. If you choose this option, the TimesTen Operator cannot create a PodMonitor object with sufficient information to allow Prometheus to access TimesTen. You can create a PodMonitor object yourself or otherwise edit the Prometheus configuration files to cause Prometheus to scrape TimesTen metrics.

After you create a Kubernetes Secret containing an Oracle Wallet (that contains the necessary certificates), you must include this Secret in your TimesTenClassic or TimesTenClassic object YAML manifest file. You do this by specifying the .spec.ttspec.prometheus.certSecret datum in your object definition.

Here is a code snippet of a TimesTenClassic object YAML manifest file:

apiVersion: timesten.oracle.com/v1
kind: TimesTenClassic
metadata:
 name: samplecertsecret
spec:



ttspec:

prometheus:

certSecret: prometheuscert

port: 7777

Note the following:

- The .spec.ttspec.prometheus datum is specified in the TimesTen Classic object YAML manifest file. This causes the TimesTen Operator to automatically deploy the TimesTen exporter in a separate container within each Pod running TimesTen.
- The certSecret datum is specified in the .spec.ttspec.prometheus clause of the TimesTenClassic object. The wallet contained in the prometheusecert Kubernetes Secret is used for Transport Layer Security (mutual TLS)/https.

The port datum is specified. This is the port on which the TimesTen exporter listens. The causes the TimesTen Operator to set up the http server on TCP port 7777 in each TimesTen Pod.

Here is a summary of the tasks you need to complete to create your own Oracle Wallet, certificates, and Kubernetes Secret. The summary also includes the tasks to include the appropriate Kubernetes Secret in a TimesTenClassic or TimesTenScaleout object YAML manifest file. There is a complete example in Create Your Own Oracle Wallet, Certificates, and Kubernetes Secrets.

- Create a TimesTen instance. See Before You Begin.
- Use the TimesTen ttExporter utility to generate the certificates. One of the certificates that is created is the self-signed server certificate. This certificate is placed in an Oracle Wallet. See Create Certificates.
- Place the Oracle Wallet into a Kubernetes Secret. See Create a Kubernetes Secret Containing an Oracle Wallet.
- Specify the name of the Secret in the <code>spec.ttspec.prometheus.certSecret</code> datum of a TimesTenClassic or TimesTenScaleout object YAML manifest file. See Define and Deploy a TimesTenClassic Object.
- Save the PEM formatted file containing the server certificate, the client certificate, and the client private key that were created when you ran the TimesTen ttExporter utility. You need these later to configure the Prometheus server. See Create Certificates.

Here are additional references:

- For information about the spec.ttspec.prometheus.certSecret datum, see TimesTenClassicSpecSpecPrometheus and TimesTenScaleoutSpecSpecPrometheus.
- For information about the command line options for the ttExporter utility, see ttExporter in the *Oracle TimesTen In-Memory Database Reference*.

Create Your Own Oracle Wallet, Certificates, and Kubernetes Secrets

Let's look at an example that shows you how to create your own Oracle Wallet, certificates, and Kubernetes Secrets. The example also shows you how to specify a



Kubernetes Secret that contains an Oracle Wallet in a TimesTenClassic object YAML manifest file.



The steps are the same for a TimesTenScaleout object.

- Before You Begin
- Create Certificates
- Create a Kubernetes Secret Containing an Oracle Wallet
- Define and Deploy a TimesTenClassic Object

Before You Begin

The TimesTen ttExporter utility is located in the /bin directory of a TimesTen instance. Since the ttExporter utility is located in the TimesTen instance, you are required to create a TimesTen instance on your development host so that you have access to the ttExporter utility. You create a TimesTen instance from a TimesTen installation. A TimesTen installation is created when you unzip the TimesTen distribution.

You must download the TimesTen distribution and unzip it to create a TimesTen installation before beginning these steps. You may have already completed this process if you chose to build the TimesTen container image. See Unpack the TimesTen and the TimesTen Operator Distributions.

- 1. If you have not already done so, download and unzip the TimesTen distribution into a directory on your development host.
- On your development host from a directory of your choice, create a directory for the TimesTen instance. This example assumes you have previously created the /scratch/ ttuser directory. The example creates the /scratch/ttuser/instancel_exporter_dir directory.

```
mkdir /scratch/ttuser/instance1_exporter_dir
```

- Create the TimesTen instance located in the TimesTen installation directory. Replace the following:
 - *installation_dir*: Name of the TimesTen installation directory. This is the directory where you unzipped the TimesTen distribution.
 - tt22.1.1.19.0: TimesTen release number in ttdottedrelease format, where dottedrelease is 22.1.1.19.0 in this example.
 - instance1 exporter: Name of the TimesTen instance.
 - /scratch/ttuser/instancel_exporter_dir: Location of the TimesTen instance. You created this directory in the previous step.

```
./installation_dir/tt22.1.1.19.0/bin/ttInstanceCreate -name
instance1 exporter -location /scratch/ttuser/instance1 exporter dir
```



The output is similar to the following:

4. Set the TIMESTEN_HOME environment variable. You must set this variable before you run the ttExporter utility. This example uses the bash Bourne-type shell.

```
. /scratch/ttuser/instancel_exporter_dir/instancel_exporter/bin/
ttenv.sh
```

The output is similar to the following, with not all output shown:

```
LD_LIBRARY_PATH set to ...

PATH set to ...

CLASSPATH set to ...

TIMESTEN_HOME set to /scratch/ttuser/instancel_exporter_dir/
instancel_exporter
```

You successfully created the TimesTen instance on your development host. You are now ready to use the ttExporter utility to create the certificates.

Create Certificates

There are certificates that are necessary in order to use Transport Layer Security (mutual TLS)/https. They are as follows:

- Server certificate: A self-signed certificate that is stored in an Oracle Wallet. This certificate is used by the TimesTen exporter. The name of the Oracle Wallet is cwallet.sso.
- Exported server certificate: The self-signed server certificate in PEM format. This
 certificate is required for your Prometheus configuration.



 Client certificate and client private key: The client certificate and the client private key required for your Prometheus configuration.

The following steps show you how to create these certificates:

1. Check that the TIMESTEN_HOME environment variable is set. You set this environment variable in a previous step. See Before You Begin.

```
echo $TIMESTEN_HOME
```

The output is the following:

```
/scratch/ttuser/instancel exporter dir/instancel exporter
```

2. On your development host, from a directory of your choice, create a subdirectory to store an Oracle Wallet. This example creates the exportercertdir directory.

```
mkdir -p exportercertdir
```

3. Create the self-signed server certificate. This certificate is stored as an Oracle Wallet. The name of the file that contains the Oracle Wallet is <code>cwallet.sso</code>. It contains the certificate information required by the TimesTen exporter. Later, you will use a Kubernetes Secret to place the <code>cwallet.sso</code> Oracle Wallet file into the <code>/ttconfig/exporterWallet</code> location of the exporter container.

```
ttExporter -create-server-certificate -certificate-common-name
*.samplecertsecret.mynamespace.svc.cluster.local -certificate-alt-names
*.samplecertsecret.mynamespace.svc.cluster.local -certificate-directory
exportercertdir
```

The -certificate-common-name and -certificate-alt-names ttExporter options are required. For detailed information on these options, see ttExporter in the *Oracle TimesTen In-Memory Database Reference*.

The -certificate-common-name option is the Common Name (CN) that is included in the certificate. It matches the DNS name where the certificate is installed. This CN can contain only one name. Single-level wildcards are acceptable. In this example, the CN name is *.samplecertsecret.mynamespace.svc.cluster.local, where:

- * is a single level wildcard.
- samplecertsecret is the name of your TimesTenClassic or your TimesTenScaleout object.
- *mynamespace* is the name of your namespace.
- svc.cluster.local completes the required format for the DNS name.

The -certificate-alt-names option is the Subject Alternative Name (SAN) that is included in the certificate. This name includes the CN mentioned previously as well as any other DNS names that need access to the TimesTen Exporter. Single level wildcards are acceptable. In this example, the SAN name includes only the CN name. Specifically, the SAN name is *.samplecertsecret.mynamespace.svc.cluster.local, where:

* is a single level wildcard.



- samplecertsecret is the name of your TimesTenClassic or your TimesTenScaleout object.
- mynamespace is the name of your namespace.
- svc.cluster.local completes the required format for the DNS name.

Since these options require you to specify the name of the TimesTenClassic (or the TimesTenScaleout) object and the name of your namespace, you must know these names before completing this step. In addition, you must use these same names when defining your TimesTen Classic or your TimesTenScaleout object.

4. Export the server certificate.

```
ttExporter -export-server-certificate exportercertdir/server.crt -certificate-directory exportercertdir
```

This command exports the server certificate in PEM format. In this example, the name of the file that contains the certificate is server.crt. Save this file. You need it later when configuring Prometheus.

5. Create and export the client certificate and the client private key.

```
ttExporter -export-client-certificate exportercertdir/client.crt -export-client-private-key exportercertdir/key.crt -certificate-directory exportercertdir
```

This command creates the client certificate. In this example, the contents of the client certificate is stored in the client.crt file. The example also creates the client private key and stores its contents in the key.crt file. Save these files. You need them later when configuring Prometheus.

6. (Optional): Verify the certificates are created.

```
ls -a exportercertdir
```

The output is similar to the following:

```
. client.crt server.crt
.. key.crt .ttwallet.BA0F2D86-B6D2-4095-A4D0-CDF1FF89E9BF
```

Verify the ttExporter utility has created the Oracle Wallet.

```
ls -a exportercertdir/.ttwallet*
```

The output is the following:

```
. .. cwallet.sso
```

You have successfully created the server certificate, the client certificate, and the client private key. Make a note of these files and their location. You need them later. Specifically, you need to specify the <code>cwallet.sso</code> Oracle Wallet file when you create the Kubernetes Secret. See Create a Kubernetes Secret Containing an Oracle Wallet.



In addition, you need to specify the server.crt, the client.crt, and the key.crt files later when you configure Prometheus.



Configuring Prometheus is outside the scope of this book. For information on configuring Prometheus, see About configuring the TimesTen exporter and Prometheus with client certificate authentication in the *Oracle TimesTen In-Memory Database Monitoring and Troubleshooting Guide*.

Create a Kubernetes Secret Containing an Oracle Wallet

The following steps show you how to create a Kubernetes Secret for an Oracle Wallet. This Oracle Wallet contains the self-signed server certificate. You created the Oracle Wallet in Create Certificates.

1. On your development host, from a directory of your choice, create an empty subdirectory for the Oracle Wallet (the cwallet.sso file). This example creates the walletdir subdirectory.

```
mkdir -p walletdir
```

2. Copy the cwallet.sso Oracle Wallet to the directory.

```
cp exportercertdir/.ttwallet*/cwallet.sso walletdir/cwallet.sso
```

In this example, the Oracle Wallet is located in the exportercertdir/.ttwallet*/cwallet.sso walletdir directory. You created this directory in Create Certificates.

Create the Kubernetes Secret for the Oracle Wallet. Ensure to specify the / exporterWallet directory.

```
kubectl create secret generic prometheuscert --from-
file=exporterWallet=walletdir/cwallet.sso
```

The kubectl create generic secret command does the following:

- Creates the prometheuscert Kubernetes Secret.
- Includes the exporterWallet metadata file. This file is required when including the cwallet.sso file in the Secret.
- Defines walletdir as the location for the cwallet.sso file.
- Defines the cwallet.sso file as the name of the Oracle Wallet file.

The output is the following:

```
secret/prometheuscert created
```

You have successfully created the Kubernetes Secret. Make a note of the name of the Secret. You use it later when you create your TimesTenClassic or TimesTenScaleout object.



Define and Deploy a TimesTenClassic Object

Let's define a TimesTenClassic object with the appropriate information such that the TimesTen Operator automatically provisions the TimesTen exporter in a separate container within each Pod that is running TimesTen. Let's use

the .spec.ttspec.prometheus.certSecret datum to instruct the TimesTen Operator to use the Oracle Wallet located in the Kubernetes Secret that you previously created. (You created this Secert in Create a Kubernetes Secret Containing an Oracle Wallet).

Define a TimesTenClassic object.

```
vi samplecertsecret.yaml
apiVersion: timesten.oracle.com/v1
kind: TimesTenClassic
metadata:
 name: samplecertsecret
spec:
 ttspec:
   storageClassName: oci-bv
    storageSize: 250G
   image: container-registry.oracle.com/timesten/
timesten:22.1.1.19.0
    imagePullSecret: sekret
   prometheus:
     certSecret: prometheuscert
     port: 7777
    dbConfigMap:
    - samplecertsecret
```

Note the following:

- The .spec.ttspec.prometheus clause is specified. The TimesTen Operator provisions a TimesTen exporter container in each TimesTen Pod.
- The .spec.ttspec.prometheus.certSecret datum is specified. The value of this datum is the name of the Kubernetes Secret containing the Oracle Wallet you previously created.
- The TimesTen exporter is listening on port 7777.
- 2. Create the TimesTenClassic object from the contents of the YAML file.

```
kubectl create -f samplecertsecret.yaml
```

The output is the following:

```
configmap/samplecertsecret created
timestenclassic.timesten.oracle.com/samplecertsecret created
```



3. Wait a few minutes then confirm the TimesTenClassic object is in the Normal state. Confirm also that the TimesTen Operator provisioned a TimesTen exporter container in each TimesTen Pod.

kubectl get ttc samplecertsecret

Output.

samplecertsecret	Normal	samplecertsecret-0	6m19s
NAME	STATE	ACTIVE	AGE

Confirm there is a TimesTen exporter container.

kubectl get pods

Output.

NAME	READY	STATUS	RESTARTS	AGE
samplecertsecret-0	3/3	Running	0	2m59s
samplecertsecret-1	3/3	Running	0	2m59s
timesten-operator-7f77c749fd-lkhtr	1/1	Running	0	60m

The TimesTen Operator provisioned three containers for each TimesTen Pod. One container is running the TimesTen exporter. The TimesTen exporter is listening on port 7777 and functions as an https server.

Your next step is to edit the appropriate Prometheus configuration files to cause Prometheus to scrape TimesTen metrics. For more information about configuring Prometheus, see https://prometheus.io/docs/prometheus/latest/configuration/configuration/.

