Resources to be created
Oracle Banking Treasury Management
Release 14.6.2.0.0
Part No. F75605-01
[November] [2022]



Table of Contents

1. RESO	OURCES TO BE CREATED ON APPLICATION SERVER	1-
1.1 In	NTRODUCTION	1-1
1.2 R	ESOURCE TYPES	1-1
1.3 R	ESOURCE PREREQUISITES FOR PLUG-INS	1-
1.3.1	Banking Treasury Management	1
1.3.2	SMS	
1.3.3	Scheduler	
1.3.4	Gateway	1-3
1.3.5	ELCM	
1.3.6	REST API services	1-2



1. Resources to be created on Application Server

Introduction 1.1

This chapter explains list of resources to be created for OBTR application.

Resource Types 1.2

Configure the application server for Oracle Banking Treasury Management Application. Ensure that the following resources are available before deployment:

- Data source
- JMS resources
- Debug paths for host and branch



Note the following:

In case of Multi Entity, all data sources must be created separately for each entity. The JNDI name will be differentiated by suffixing entity name.

Examples: If Data source is 'jdbc/fcjDevDs' then jdbc/fcjDevDs+entity name will be lookup the application. (jdbc/fcjDevDs+entity name) jndi should be presented in application server

Resource prerequisites for Plug-ins 1.3

Resource prerequisites for different plug-ins are explained below. In case you wish to include a plug-in, ensure that the corresponding resources are created.

1.3.1 Oracle Banking Treasury Management

OBTR needs below resources before deployment. Create the following queues and connection factories in the application server.

JMS Connection Factories

QCF Label	QCF
Notify Destination QCF	NotifyDestQCF
Deferred QCF	DefferedDestQCF
Notify QCF	NOTIFY_MDB_QCF
Incoming QCF	EmsQcf
BIP QCF	BIPQCF
GI Upload QCF	GI_UPLOAD_QCF
Sanction Check QCF	SNCKREQQCF
<internally referred=""></internally>	ELMDBQCF
<internally referred=""></internally>	EL_NOTIFY_QCF




Queues

Create the following queues:

QUEUE Label	QUEUE	
Notify Destination Queue Name	NOTIFY_DEST_QUEUE	
Deferred Queue Name	DEFFERED_DEST_QUEUE	
Notify Queue Name	NOTIFY_QUEUE	
Dead Letter Queue name	NOTIFY_QUEUE_DLQ	
Incoming BackupQueue name	EMS_QUEUE_BACK	
Incoming Dead Letter Queue		
name	EMS_QUEUE_DLQ	
Incoming Queue Name	EMS_INQUEUE	
Outgoing Queue Name	EMS_OUTQUEUE	
SFMS Incoming Queue	SFMS_INQUEUE	
RTGS Incoming Queue	RTGS_INQUEUE	
BIP Queue Name	BIPREPORT_QUEUE	
BIP Dead Letter Queue Name	INTERNAL_BIP_QUEUE_DLQ	
BIPadvice Queue Name	BIPADVREPORT_QUEUE	
BIPadvice Dead Letter Queue		
Name	INTERNAL_BIP_ADVICE_QUEUE_DLQ	
GI Upload Queue Name	INTERNAL_GI_UPLOAD_QUEUE	
GI Upload Dead Letter Queue		
Name	INTERNAL_GI_UPLOAD_DLQ	
BulkerMDB Queue	EMS_BULKERQUE	
Sanction Check Request Queue	SNCKREQ_QUEUE	
Sanction Check Response Queue	SNCKRES_QUEUE	
Sanction Check Listener Queue	SNCKASYNC_QUEUE	
<internally referred=""></internally>	ELMDB_REQ_Q	
<internally referred=""></internally>	ELMDB_RES_Q	
<internally referred=""></internally>	ELMDB_DLQ	
<internally referred=""></internally>	EL_NOTIFY_REQ_Q	
<internally referred=""></internally>	EL_NOTIFY_RES_Q	
<internally referred=""></internally>	EL_NOTIFY_DLQ	

Data source

Datasource Name	Datasource Label	Туре	Default Value
INIT_DATASOURCE	Data Source	NON-XA	jdbc/fcjdevDS
SCHEDULER_DS	Scheduler Datasource	XA	jdbc/fcjSchedulerDS





You need to create two more data sources for Oracle FCUBS

- <u>Scheduler</u>: You need to create XA data source for Oracle FCUBS with the JNDI name '_XA' for scheduler. For example, if the Oracle FCUBS HOST Non XA data source JNDI name is 'jdbc/fcjdevDS', then you need to create another data source for FCUBS with the JNDI name 'jdbc/fcjdevDS_XA'.
- <u>Batch Process:</u> You need to create data source for Oracle FCUBS with the JNDI name '_ASYNC for batch process. For example, if the Oracle FCUBS HOST Non XA data source JNDI name is 'jdbc/fcjdevDS', then you need to create another data source for FCUBS with the JNDI name 'jdbc/fcjdevDS ASYNC.

1.3.2 SMS

SMS needs below Data sources before deployment.

DataSource

Datasource Name	Datasource Label	Туре	Default Value
FCUBS_SMS_POOL_NAME	DataSource	NON-XA	jdbc/fcjdevDS

1.3.3 Scheduler

If scheduler is included in the property file, create the following queues and connection factories in the application server.

In case of Remote Scheduler, create the following queues, connection factories and Datasources in the application server where scheduler EAR will be deployed.

Connection Factories

Create the following connection factories:

QCF Label	QCF
Notify Destination QCF	NotifyDestQCF
Deferred QCF	DefferedDestQCF
Notify QCF	NOTIFY_MDB_QCF
Incoming QCF	EmsQcf
BIP QCF	BIPQCF
Sanction Check QCF	SNCKREQQCF
GI Upload QCF	GI_UPLOAD_QCF



All these must be XA enabled.

Queues

Create the following queues:

QUEUE Label	QUEUE
Notify Destination Queue Name	NOTIFY_DEST_QUEUE
Deferred Queue Name	DEFFERED_DEST_QUEUE
Notify Queue Name	NOTIFY_QUEUE
Dead Letter Queue name	NOTIFY_QUEUE_DLQ
Incoming BackupQueue name	EMS_QUEUE_BACK
Incoming Dead Letter Queue name	EMS_QUEUE_DLQ
Incoming Queue Name	EMS_INQUEUE
Outgoing Queue Name	EMS_OUTQUEUE
SFMS Incoming Queue	SFMS_INQUEUE
RTGS Incoming Queue	RTGS_INQUEUE
Sanction Check Request Queue	SNCKREQ_QUEUE
Sanction Check Response Queue	SNCKRES_QUEUE
Sanction Check Listener Queue	SNCKASYNC_QUEUE
BIP Queue Name	BIPREPORT_QUEUE
BIP Dead Letter Queue Name	INTERNAL_BIP_QUEUE_DLQ
BIPadvice Queue Name	BIPADVREPORT_QUEUE
BIPadvice Dead Letter Queue Name	INTERNAL_BIP_ADVICE_QUEUE_DLQ
GI Upload Queue Name	INTERNAL_GI_UPLOAD_QUEUE
GI Upload Dead Letter Queue Name	INTERNAL_GI_UPLOAD_DLQ

Topic Connection Factory

NotifyDestTCF

Topic

NOTIFY_DEST_TOPIC


To configure scheduler and EMS with MQ series, follow the steps given below.

- Create queues in MQ Series
- Create binding file
- Copy the MQ series JAR files to Oracle WebLogic domain library folder

Datasources

Datasource Name	Datasource Label	Туре	Default Value
INIT_DATASOURCE	Data Source	NON-XA	jdbc/fcjdevDS
SCHEDULER_DS	Scheduler Datasource	XA	jdbc/fcjSchedulerDS





You need to create another XA data source for Oracle FCUBS with the JNDI name '_XA' for Scheduler. For example, if the Oracle FCUBS HOST Non XA data source JNDI name is 'jdbc/fcjdevDS', then you need to create another data source for FCUBS with the JNDI name 'jdbc/fcjdevDS_XA'.

Security Provider Libraries

If you wish to include signing process for SFMS messages, you need to set the following library.

File Name	Download Location	Instructions
bcprov- jdk(Latest Qualified Version).jar	http://www.bouncycastle.org/latest_releases.html	Copy the file 'bcprov- jdk(Latest Qualified Version).jar' to the directory '{WL_JAVA_HOME}/jre/lib/ext'
		Here, 'WL_JAVA_HOME' is the Java root directory from which WebLogic server is running.
		Restart Oracle WebLogic server.

For details on latest version of the software qualified with Oracle Banking Treasury Management, refer to the release certificate.

1.3.4 Gateway

If scheduler is included in the property file, create the following queues and connection factories in the application server.

Connection Factories

Create the following connection factories:

QCF Label	QCF
MDB QCF	MDBQCF

All these must be XA enabled.

Queues

Create the following queues:

QUEUE Label	QUEUE
MDB Request Queue	MDB_QUEUE
MDB Response	
Queue	MDB_QUEUE_RESPONSE
MDB DL Queue	MDB_QUEUE_DLQ

DataSource



Datasource Name	Datasource		Default Value
	Label	Туре	
FCUBS MSG SCHEMA CON POOLNAM		XA for MDB	FLEXTEST.WORL
E	DataSourc	and NON-	D
	е	XA for	
		others	
FCUBS SMS POOL NAME	DataSourc		jdbc/fcjdevDS
	е	NON-XA	

1.3.5 ELCM

If ELCM application has to be deployed, create the following queues and connection factories in the application server.

JMS Connection Factories

Create the following connection factories:

QCF Label	QCF
EL gateway Notify QCF	EL_NOTIFY_QCF
EL Gateway MDB QCF	ELMDBQCF
Notify Destination QCF	NotifyDestQCF
Deferred QCF	DefferedDestQCF
Notify QCF	NOTIFY_MDB_QCF
Incoming QCF	EmsQcf
BIP QCF	BIPQCF
GI Upload QCF	GI_UPLOAD_QCF

JMS Queues

Create the following queues:

QUEUE Label	QUEUE		
EL gateway Notify Request Queue Name	EL_NOTIFY_REQ_Q		
EL gateway Notify Response Queue Name	EL_NOTIFY_RES_Q		
EL gateway Notify DeadLetter Queue Name	EL_NOTIFY_DLQ		
EL Gateway MDB Request Queue Name	ELMDB_REQ_Q		
EL Gateway MDB Response Queue Name	ELMDB_RES_Q		
EL Gateway MDB DeadLetter Queue Name	ELMDB_DLQ		
Notify Destination Queue Name	NOTIFY_DEST_QUEUE		
Deferred Queue Name	DEFFERED_DEST_QUEUE		
Notify Queue Name	NOTIFY_QUEUE		
Dead Letter Queue name	NOTIFY_QUEUE_DLQ		
Incoming BackupQueue name	EMS_QUEUE_BACK		
Incoming Dead Letter Queue name	EMS_QUEUE_DLQ		
Incoming Queue Name	EMS_INQUEUE		



Outgoing Queue Name	EMS_OUTQUEUE	
SFMS Incoming Queue	SFMS_INQUEUE	
RTGS Incoming Queue	RTGS_INQUEUE	
BIP Queue Name	BIPREPORT_QUEUE	
BIP Dead Letter Queue Name	INTERNAL_BIP_QUEUE_DLQ	
BIPadvice Queue Name	BIPADVREPORT_QUEUE	
BIPadvice Dead Letter Queue Name	INTERNAL_BIP_ADVICE_QUEUE_DLQ	
GI Upload Queue Name	INTERNAL_GI_UPLOAD_QUEUE	
GI Upload Dead Letter Queue Name	INTERNAL_GI_UPLOAD_DLQ	

For ELCM, We need to create the following data sources for JDBC resources:

Datasource Name	Datasource Label	Туре	Default Value
INIT_DATASOURCE	Data Source	NON-XA	jdbc/fcjdevDS
EL_INIT_DATASOURCE	Scheduler DataSource	NON-XA	jdbc/fcjSchedulerDS

1.3.6 REST API services

The following Datasource has to be created for REST API Service Application:

Data Source:

Datasource Name	Datasource Label	Туре	Default Value
INIT_DATASOURCE	Data Source	XA	jdbc/fcjdevDS





Resources to be created [November] [2022] Version 14.6.2.0.0

Oracle Financial Services Software Limited Oracle Park Off Western Express Highway Goregaon (East) Mumbai, Maharashtra 400 063 India Worldwide Inquiries:

Phone: +91 22 6718 3000 Fax: +91 22 6718 3001

https://www.oracle.com/industries/financial-services/index.html

Copyright © 2020, 2022 Oracle and/or its affiliates. All rights reserved.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate failsafe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications. This software and related documentation are provided under a license agreement containing restrictions on use and

disclosure and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.