IDCS-OBAPI Setup Guide
Oracle Banking APIs Cloud Service
Release 22.2.1.0.0

Part No. F76130-01

May 2023

ORACLE®

IDCS-OBAPI Setup Guide

May 2023

Oracle Financial Services Software Limited

Oracle Park

Off Western Express Highway

Goregaon (East)

Mumbai, Maharashtra 400 063

India

Worldwide Inquiries:

Phone: +91 22 6718 3000

Fax:+91 22 6718 3001

www.oracle.com/financialservices/

Table of Contents

1. Preface

1.1 Intended Audience

This document is intended for the following audience*:*

- Customers
- Partners

1.2 Documentation Accessibility

For information about Oracle's commitment to accessibility, visit the Oracle Accessibility Program website at http://www.oracle.com/pls/topic/lookup?ctx=acc&id=docacc.

1.3 Access to Oracle Support

Oracle customers have access to electronic support through My Oracle Support. For information, visit

http://www.oracle.com/pls/topic/lookup?ctx=acc&id=info or visit

http://www.oracle.com/pls/topic/lookup?ctx=acc&id=trs if you are hearing impaired.

1.4 Structure

This manual is organized into the following categories:

Preface gives information on the intended audience. It also describes the overall structure of the User Manual.

The subsequent chapters describes following details:

- Introduction
- Preferences & Database
- Configuration / Installation.

ORACLE®

2. Pre-requisite step

2.1 To create users in IDCS

1. Access your Oracle Identity Cloud Service instance (for example: https://<tenant-base-url>/ui/v1/adminconsole) and log in with your Identity Domain Administrator credentials.

    Glossary of Parameters:

<tenant-name>	Tenant name of your IDCS instance
<tenant-base-url>	Tenant base URL used to access your IDCS instance
<base-url>	Base URL used to access your IDCS instance without tenant name

2. Click on **Add a user** button on **Dashboard** screen as shown below.

3. On the next screen, enter details of a new user 'superadmin' shown below.

ORACLE®

4. Click **Next**. You will get a list of existing groups in IDCS to which the user 'superadmin' can be assigned.

5. Click **Finish**. The user 'superadmin' will be created and assigned 'administrator' group.

By using above steps create retail & corporate users. The same user (with same username) must be created in OBAPI through OBAPI admin console

Home

ORACLE®

# 3. Create an OBAPI Client Application in IDCS Console

1. Go to IDCS Admin Console → Enter Admin user name and Password.

2. On Applications tab → Click on + sign →Enterprise Application

3. Click **Next** by skipping OAuth Configurations. Add SSO resources as shown below.

ORACLE

ORACLE®

4. The final list should look as below.

ORACLE®

5. In **Authentication Policy** add resources and order as shown below

ORACLE®

6. Final list should look as below

ORACLE®

4. Installing App Gateway (Cloudgate)

Use below steps for installing and configuring app gateway

https://docs.oracle.com/en/cloud/paas/identity-cloud/uaids/set-app-gateway.html#GUID-40307BF8-5357-4832-BAD0-EA7FB0010685

Home

ORACLE

5. Changes in OBAPI UI

In OBAPI UI which is deployed on OHS make sure the authenticator type is set to "OAMAuthenticator" in file → framework/js/configurations/config.js

Home

ORACLE®