Oracle® Database Getting Started with Oracle Developer Tools for VS Code





Oracle Database Getting Started with Oracle Developer Tools for VS Code, Release 21.8.0

F91598-01

Copyright © 2022, 2024, Oracle and/or its affiliates.

Primary Authors: Christian Shay, Maitreyee Chaliha

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish, or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

If this is software, software documentation, data (as defined in the Federal Acquisition Regulation), or related documentation that is delivered to the U.S. Government or anyone licensing it on behalf of the U.S. Government, then the following notice is applicable:

U.S. GOVERNMENT END USERS: Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs) and Oracle computer documentation or other Oracle data delivered to or accessed by U.S. Government end users are "commercial computer software," "commercial computer software documentation," or "limited rights data" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, the use, reproduction, duplication, release, display, disclosure, modification, preparation of derivative works, and/or adaptation of i) Oracle programs (including any operating system, integrated software, any programs embedded, installed, or activated on delivered hardware, and modifications of such programs), ii) Oracle computer documentation and/or iii) other Oracle data, is subject to the rights and limitations specified in the license contained in the applicable contract. The terms governing the U.S. Government's use of Oracle cloud services are defined by the applicable contract for such services. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate fail-safe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

Oracle®, Java, MySQL and NetSuite are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

Intel and Intel Inside are trademarks or registered trademarks of Intel Corporation. All SPARC trademarks are used under license and are trademarks or registered trademarks of SPARC International, Inc. AMD, Epyc, and the AMD logo are trademarks or registered trademarks of Advanced Micro Devices. UNIX is a registered trademark of The Open Group.

This software or hardware and documentation may provide access to or information about content, products, and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services unless otherwise set forth in an applicable agreement between you and Oracle. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services, except as set forth in an applicable agreement between you and Oracle.

Contents

1 Getting Started with Oracle Developer Tools for VS Code

Installing and Updating Oracle Developer Tools for VS Code	1-1
Installing Oracle Developer Tools for VS Code	1-1
Updating this Extension	1-2
Creating and Managing Oracle Autonomous Databases (Oracle Cloud)	1-2
Configuring Walletless Connectivity and Network Access for Oracle Autonomous Databases (Oracle Cloud)	1-3
Exploring Database Schema with Oracle Database Explorer	1-4
Connecting to Oracle Database	1-5
Connecting Using Host Name/IP Address and Service Name	1-5
Connecting Using a TNSNAMES.ORA Connection Alias	1-6
Connecting Using a Proxy User	1-7
Connecting Using a Directory Server (LDAP)	1-7
Connecting Using OS Authentication	1-9
Connecting to Oracle Autonomous Database (ADB)	1-9
Connecting Using Oracle Cloud Infrastructure Explorer to Connect Without Using Credentials Files (Walletless)	1-9
Connecting Using Oracle Cloud Infrastructure Explorer to Automatically Download Credentials Files (Wallets)	1-10
Connecting Using Credentials Files Obtained Elsewhere	1-11
Connecting Without Using Credentials Files	1-13
Connecting Using OCI IAM Single Sign-on	1-14
Organizing Connections by User, Workspace, or Folder Scope	1-14
Applying Filters to Oracle Database Explorer and IntelliSense Suggestions	1-15
Changing the Default Schema for a Connection	1-16
Selecting a Default Connection to be used when Opening SQL files	1-16
Running a SQL Script Each Time a Connection is Established	1-17
Colorizing Oracle Explorer Connections and Code Windows	1-17
Viewing other Schemas in Oracle Explorer	1-17
Editing PL/SQL in your Database	1-18
Saving PL/SQL in Database to a File	1-18
Opening .SQL or .PL/SQL File	1-18
Changing Database Connection for an Open .SQL or .PL/SQL File	1-19



	1-19
Using Auto Save when Editing PL/SQL	1-19
Executing SQL and PL/SQL	1-19
Viewing an Explain Plan/Execution Plan for a SQL Statement	1-20
Using Real-Time SQL Monitoring	1-21
Formatting SQL and PL/SQL with a Configurable Formatter	1-22
Jsing Lowercase/Title Case Characters with Autocomplete/Intellisense	1-22
Navigating through SQL Scripts and PL/SQL Packages	1-22
Executing SQL*Plus Commands	1-23
Disabling and Enabling Auto Commit	1-23
Viewing and Saving Result Sets	1-24
Debugging PL/SQL	1-24
Debugging PL/SQL from Oracle Database Explorer	1-24
Debugging PL/SQL Called By an Application or SQL Scripts	1-25
Viewing SQL History	1-26
Creating a SQL Bookmark	1-27
Configure the Location of the Query Results Window	1-27
Creating and Modifying Keyboard Shortcuts	1-27
Learn What's New in This Version	

Index



1

Getting Started with Oracle Developer Tools for VS Code

Welcome! Oracle Developer Tools for VS Code enables Visual Studio Code developers to connect to Oracle Database and Oracle Autonomous Database; edit SQL and PL/SQL with IntelliSense, breadcrumbs, Hover, and Go To/Peek; execute SQL and PL/SQL and view and save the results; and debug PL/SQL using VS Code's native debugging features. The Oracle Database Explorer tree control allows you to quickly explore your database schema, view table data, and edit, debug, execute and save PL/SQL. Create and manage Oracle Autonomous Databases (ADBs) using Oracle Cloud Infrastructure Explorer tree control. Create, start, stop and terminate ADB instances, and automatically create a walletless database connection or download credentials files.

This Quick Start will help you install, connect, configure and get started using Oracle Developer Tools for VS Code.



This document assumes you are using version 21.8.0 (released January 2024). Follow the instructions for updating in Installing and Updating Oracle Developer Tools for VS Code if you are using an older version.

Installing and Updating Oracle Developer Tools for VS Code

Installing Oracle Developer Tools for VS Code

To install Oracle Developer Tools for VS Code:

- Upgrade Visual Studio Code to version 1.67.0 or later. You can check the version by using the Help->About menu item. To upgrade select Help->Check for Updates.
- Click on the Extensions icon in the Activity Bar on the side of VS Code or use the View: Show Extensions command (Ctrl+Shift+X)
- 3. Type **Oracle Developer Tools** in the extension search bar
- 4. Locate Oracle Developer Tools for VS Code and click Install
- 5. When the installation is complete, restart Visual Studio Code

During the installation, the NET Runtime is now automatically installed if no compatible runtime is currently installed. If there is a problem installing the .NET Runtime, then you may be prompted to manually install it. Installation instructions are as follows:

Linux

- macOS(x64, Arm64/Apple M1)
- Windows (x64)

Updating this Extension

To be able to update to new versions of this extension, upgrade Visual Studio Code to version **1.67.0** or later. You can check the version by using the **Help->About** menu item.

- To upgrade to the latest version of Visual Studio Code, select **Help->Check for Updates**.
- If you have disabled automatic extension updates, press F1 to open the Command Palette and enter the Check for Extension Updates command and click the Update... button which will appear in the list of installed extensions.



Extension Marketplace

Creating and Managing Oracle Autonomous Databases (Oracle Cloud)

Follow these instructions to create an Oracle Cloud account, generate the required config file and key files, and connect the **Oracle Cloud Infrastructure Explorer** tree control to the Oracle Cloud. Once the Oracle Cloud Infrastructure Explorer is connected to the Oracle Cloud, you can create and manage Oracle Autonomous Databases:

- To change the compartment or region: Right click on the profile name (usually DEFAULT) and select Change Compartment or Region from the menu
- To create a new Autonomous Database (ADB), including an Always Free ADB, right click on Autonomous Transaction Processing Databases, Autonomous Data Warehouses, or Autonomous JSON Databases and select Create New.
- To view an existing database, expand Autonomous Transaction Processing Databases, Autonomous Data Warehouses, or Autonomous JSON Databases and view the list of databases. Change the region or compartment if your databases are not shown. Database icons with a red ball are not available, those with a yellow ball are starting or stopping, and icons with no ball are available. Icons with a green star are Always Free databases. Icons containing a D are dedicated instances.
- To easily and automatically create a connection in Database Explorer, right click on database icon and select Create Connection in Database Explorer. For more information, see Connecting Without Using Credentials Files or Connecting Using Oracle Cloud Infrastructure Explorer to Automatically Download Credentials Files (Wallets).



- To download credentials files, right click on database icon and select **Download** Credentials Files.
- To obtain a connection string for this database, right click on database icon and select Get Connection Strings. Select the Authentication type and TNS Name (Service Level) from the drop down lists.
- To configure walletless connectivity and network access right click on database icon and select Configure Walletless Connectivity and Network Access. For more information, see Configuring Walletless Connectivity and Network Access for Oracle Autonomous Databases (Oracle Cloud).
- To Start an ADB, right click on database icon and select Start.
- To Stop an ADB, right click on database icon and select Stop.
- To Terminate an ADB, right click on database icon and select **Terminate**.
- To change the ADMIN password for an ADB, right click on database icon and select
 Change Administrator Password.
- To refresh the tree control, click on any item and select Refresh

Configuring Walletless Connectivity and Network Access for Oracle Autonomous Databases (Oracle Cloud)

To connect to Oracle Autonomous Database without using credentials files (walletless), the database must be configured to allow this and Network Access Control rules should be set up.

- See Creating and Managing Oracle Autonomous Databases (Oracle Cloud) for instructions on how to configure Oracle Cloud Infrastructure Explorer tree control for first use
- Expand Autonomous Transaction Processing Databases, Autonomous Data Warehouses, or Autonomous JSON Databases and view the list of databases.
- Right click on database icon and select Configure Walletless Connectivity and Network Access.
- If you wish to enable walletless access, in the Network Access Type drop down list, select Secure access from allowed IPs and VCNs only (wallet optional) and check the Enable walletless connectivity (TLS) checkbox
- To disable walletless access, select Secure access from everywhere (wallet required).
- To modify Access Control Rules, click the Update Accesss Control button.
- In the Update Accesss Control dialog, click Add Access Control Rule for a new rule, or update an existing rule. Select a IP Notation Type and populate the Values field, then press OK. For example, select a type of IP address, then click the Add my IP Address Button to populate the field with the public IP address of your system as visible on the public internet.
- Press the **Apply Changes** button in the **Configure Walletless Connectivity and Network Access** dialog. The database will temporarily be offline while the change is being processed.



Exploring Database Schema with Oracle Database Explorer

To view Database Explorer, click the database icon in the Activity Bar on the far left side of Visual Studio Code.

- Connect: Click the plus (+) sign to create a new connection, following the steps in Connecting to Oracle Database or Connecting to Oracle Autonomous Database (ADB). Once connection nodes display, you can click on the node to view the database schema.
- Delete Connection: Right click on any connection node and select Delete
- Update Connection info: Right click on any connection node and select Update
- Set a connection to be the default used when opening a SQL or PL/SQL file: Right click on any connection and select Set as Default Connection. The icon for the default connection will contain an asterix(*) in the upper left hand corner.
- Unset a connection as a default connection: Right click on the default connection and select Unset as Default Connection.
- Disconnect: Right click on any connection node and select Disconnect
- View Other Users/Other Schemas: Click to expand the *Other Users* node. Select
 the schema you wish to view. Alternately, click on the connection node and select *Update*. In the connection dialog, check the *Show more options* checkbox then
 select a different schema in the *Current Schema* dropdown. Press the *Update Connection* button.
- View and Save Table/View Data: On a Table and View node's menu, select Show Data. For more information see Viewing and Saving Result Sets below.
- Generate SELECT, INSERT, or DELETE statements for a table: On a Table node, right click and select Generate Select SQL, Generate Insert SQL, or Generate Delete SQL from the menu. The SQL will be added to an open SQL script file that is selected, or a new SQL file will be opened containing the SQL.
- View metadata for a schema object (describe): On any schema object node, right click and select the **Describe** menu item.
- Edit PL/SQL: On stored procedures, functions, packages, or trigger nodes select
 Open/Open Package Body/Open Specification to open PL/SQL into a file for
 editing. See Editing PL/SQL in your Database for more details.
- Save PL/SQL to database: If the PL/SQL was opened with the *Open* menu item in Database Explorer, you can save changes to the database by right clicking in the PL/SQL code and selecting *Save*. If there are errors when saving, they will be listed in the Problems panel, and you can click on an error to go to the line that contains the error. (Note: these menu names were previously named *Edit PL/SQL* and *Save to Database* in earlier releases.)
- Save PL/SQL to file: In Oracle Database Explorer right click a package, procedure, function, or trigger and from the menu and select *Download*. Alternatively, after opening the package, procedure, function, or trigger from Database Explorer select the tab with the PL/SQL code in it. In Visual Studio Code menu select *File->Save As* and then click *Show Local*.
- Execute PL/SQL:From menu, select *Run* to execute a stored procedure or function



- Debug PL/SQL: Right click on a connection name and select PL/SQL Debugger and Compiler Settings to set the ip address and port number range that will be used. A script to grant privileges and configure the database is also provided in the dialog. To compile with debug information, right click on a procedure/function/package and select Compile Debug from the menu. To begin debugging, from the same menu select Step Into or Run Debug (if the PL/SQL is already open and breakpoints set). To listen for and debug PL/SQL procedures and functions called by applications or SQL scripts, right click on a connection name and select Start External Application Debugger. For more details on PL/SQL debugging, see the Debugging PL/SQL from Oracle Database Explorer and Debugging PL/SQL Called By an Application or SQL Scripts sections.
- Refresh: Right click on any node and select Refresh to refresh that node and all child nodes
- Filter: Right click on the connection node and select *Filters* to open the Filters dialog.
 See Applying Filters to Oracle Database Explorer and IntelliSense Suggestions.

Connecting to Oracle Database

Connecting Using Host Name/IP Address and Service Name

If your database is in the Oracle Cloud go to **Connecting to Oracle Autonomous Database** (ADB). For additional help using the connection dialog, visit the connection dialog help.

- 1. You can connect to the Oracle Database using one of the following ways:
 - To connect to Oracle Database from a .SQL or .PL/SQL file, press F1 to open Command Palette and select Oracle:Connect from the dropdown. Then select New Connection.

Or,

- To connect from Oracle Database Explorer, click the plus (+) sign:
- 2. A connection dialog will open. In the **Connection Type** dropdown, select **Basic (Host, Port, Service Name)**.
- 3. Enter the database hostname or IP Address, port number, and service name.
- 4. Select the database role from the **Role** drop down list.
- 5. Enter the username and password.
- 6. If you are using Proxy Authentication, check the **Show more options** checkbox and provide the proxy username and password. To guide you in entering the fields, note that in other tools, you may have connected using this format:

proxyusername[username]/[proxypassword]



For more details about connecting with a proxy, see Connecting Using a Proxy User.



- 7. If you wish to use a different schema than the default schema associated with your username, check the **Show more options** checkbox and select the schema name from the **Current Schema** dropdown.
- 8. Provide a connection name to be used to reference this connection in Database Explorer and elsewhere.
- 9. Click the Create Connection button.



Connection information and settings may be stored with a User, Workspace, or Folder Scope. For more information see Organizing Connections by User, Workspace, or Folder Scope.

Connecting Using a TNSNAMES.ORA Connection Alias

If your database is in the Oracle Cloud go to **Connecting to Oracle Autonomous Database (ADB)**. For additional help using the connection dialog, visit the connection dialog help.

- Copy the TNSNAMES.ORA file that you want to use into the directory that is set as Config Files Folder in the Oracle Developer Tools for VS Code Extension Settings, or change this setting as desired. By default this location is ~IOracleI network/admin on Linux and Mac and %USERPROFILE% \Oracle\network\admin on Windows.
- If you don't have a TNSNAMES.ORA but would like to create one, see the example located in ~I.vscode/extensions/oracle.oracledevtools-21.7.1/sample/ network on Linux and Mac and %USERPROFILE% \.vscode\extensions\oracle.oracledevtools-21.7.1\sample\network on Windows .
- 3. You can connect to the Oracle Database using one of the following ways:
 - To connect to Oracle Database from a .SQL or .PL/SQL file, press F1 to open Command Palette and select Oracle:Connect from the dropdown. Then select New Connection.

Or,

- To connect from Oracle Database Explorer, click the plus (+) sign:
- 4. A connection dialog will open. In the **Connection Type** dropdown, select **Use TNSNAMES.ORA**.
- **5.** Make sure the **TNS Admin Location** field is set to the directory where your TNSNAMES.ORA file is located. If not, change it.
- 6. Select an alias from the **TNS Alias** dropdown list.
- 7. Select the database role from the **Role** drop down list.
- 8. Enter the username and password.
- 9. If you are using Proxy Authentication, check the **Show more options** checkbox and provide the proxy username and password. To guide you in entering the fields, note that in other tools, you may have connected using this format:



proxyusername[username]/[proxypassword]



For more details about connecting with a proxy, see Connecting Using a Proxy User.

- **10.** If you wish to use a different schema than the default schema associated with your username, check the **Show more options** checkbox and select the schema name from the **Current Schema** dropdown.
- Provide a connection name to be used to reference this connection in Database Explorer and elsewhere.
- 12. Click the Create Connection button.



Connection information and settings may be stored with a User, Workspace, or Folder Scope. For more information see Organizing Connections by User, Workspace, or Folder Scope.

Connecting Using a Proxy User

If your database is in the Oracle Cloud go to **Connecting to Oracle Autonomous Database** (ADB). For additional help using the connection dialog, visit the connection dialog help.

- Follow the steps in Connecting to Oracle Database to open the connection dialog and provide the connection information.
- If you are using Proxy Authentication, check the **Show more options** checkbox and provide the proxy username and password. To guide you in entering the fields, note that in other tools, you may have connected using this format:

proxyusername[username]/[proxypassword]



See the connection dialog help for more information about other proxy scenarios such as using external authentication (that is, OS/Kerberos/ Certificate) or if using Secure External Password Store (SEPS) wallet for database username and password.

Connecting Using a Directory Server (LDAP)

If your database is in the Oracle Cloud go to **Connecting to Oracle Autonomous Database** (ADB). For additional help using the connection dialog, visit the connection dialog help.



Connections using a directory server (LDAP) are now supported on all platforms (Windows, MacOS, and Linux).

- Copy the LDAP.ORA and SQLNET.ORA files that you want to use into the directory that is set as *Config Files Folder* in the Oracle Developer Tools for VS Code Extension Settings, or change this setting as desired. By default this location is ~/Oracle/network/admin on Linux and Mac and %USERPROFILE% \Oracle\network\admin on Windows.
- To connect to Oracle Database from a .SQL or .PL/SQL file, press F1 to open Command Palette and select *Oracle:Connect* from the dropdown. Then select *New Connection*.
- 3. To connect from Oracle Database Explorer, click the plus sign button
- A connection dialog will open. In the Connection Type dropdown, select LDAP Directory Server
- Make sure the TNS Admin Location field is set to the directory where your LDAP.ORA and SQLNET.ORA files are located. If not, change it.
- 6. In the **TNS Alias** field, type in the database service name.
- 7. Select the database role from the *Role* drop down list
- 8. Enter the username and password
- 9. If you are using Proxy Authentication, check the **Show more options** checkbox and provide the proxy username and password. To guide you in entering the fields, note that in other tools, you may have connected using this format:

proxyusername[username]/[proxypassword]



For more details about connecting with a proxy, see Connecting Using a Proxy User.

- 10. If you wish to use a different schema than the default schema associated with your username, check the Show more options checkbox and select the schema name from the Current Schema dropdown
- 11. Provide a connection name to be used to reference this connection in Database Explorer and elsewhere
- 12. Click the Create Connection button



Connection information and settings may be stored with a User, Workspace, or Folder Scope. For more information, see Organizing Connections by User, Workspace, or Folder Scope.



Connecting Using OS Authentication

If your database is in the Oracle Cloud go to **Connecting to Oracle Autonomous Database** (ADB). For additional help using the connection dialog, visit the connection dialog help.

If using both Windows Client and Windows Database Server, set **SQLNET.AUTHENTICATION_SERVICES=(NTS)** in a SQLNET.ORA file located in the directory that is set as **Config Files Folder** in the Oracle Developer Tools for VS Code Extension Settings. By default this location is **%USERPROFILE%\Oracle\network\admin**

Follow the steps in Connecting Using Host Name/IP Address and Service Name or Connecting Using a TNSNAMES.ORA Connection Alias above, except

- In the User name field, enter a forward slash: /
- The Password field should be left empty.



For more details about connecting with a proxy, see Connecting Using a Proxy User.

Connecting to Oracle Autonomous Database (ADB)

Connecting Using Oracle Cloud Infrastructure Explorer to Connect Without Using Credentials Files (Walletless)

If your Oracle Database is On-prem, then go to **Connecting to Oracle Database**. For additional help using the connection dialog, visit the connection dialog help.

Oracle Cloud Infrastructure Explorer makes connecting to your Autonomous Database easier by automatically obtaining the connection string pre-populating the connection dialog.

Follow the steps in the Creating and Managing Oracle Autonomous Databases (Oracle Cloud) and Configuring Walletless Connectivity and Network Access for Oracle Autonomous Databases (Oracle Cloud) to connect Oracle Cloud Infrastructure Explorer tree control to the Oracle Cloud, locate the Autonomous Database instance you wish to connect to and configure the Autonomous database for walletless access if necessary.

- Right click on the Autonomous Database instance name and select Create Connection in Database Explorer. The Select Authentication and Connection String will open. If this dialog does not open but instead a Download Credentials Files dialog opens, this means that the database is not configured for walletless access.
- 2. Set Authentication to **TLS(walletless)**, select a choice from the **TNS Name (Service Level)** drop down, and press **OK**.
 - The connection dialog will open.
- 3. Select **Default** from the Role drop down list



- **4.** Enter the username and password. (If you are new to Oracle Autonomous Database, use username ADMIN).
- 5. If you are using Proxy Authentication, check the **Show more options** checkbox and provide the proxy username and password.



For more details about connecting with a proxy, see Connecting Using a Proxy User.

- 6. If you want to use a different schema than the default schema associated with your username, check the **Show more options** checkbox and select the schema from the Current Schema dropdown.
- 7. Provide a connection name to be used to reference this connection in Database Explorer and elsewhere.
- 8. Click the Create Connection button.
- 9. If you are using macOS, and receive a Connection request timed out error when trying to connect, please update .NET Runtime to version 6.0.



Connection information and settings may be stored with a User, Workspace, or Folder Scope. For more information see Organizing Connections by User, Workspace, or Folder Scope.

Connecting Using Oracle Cloud Infrastructure Explorer to Automatically Download Credentials Files (Wallets)

If your Oracle Database is On-prem, then go to **Connecting to Oracle Database**. For additional help using the connection dialog, visit the connection dialog help.

Follow the steps in **Create and Manage Oracle Autonomous Databases** to connect Oracle Cloud Infrastructure Explorer tree control to the Oracle Cloud and locate the Autonomous Database instance you wish to connect to.

Oracle Cloud Infrastructure Explorer makes connecting to your Autonomous Database easier by automatically downloading credentials files if needed, and by pre-populating the connection dialog.

- Right click on the Autonomous Database instance name and select *Create Connection in Database Explorer*. Depending on hour your database is configured, you may see a *Select Authentication and Connection String* dialog. If you do, Set Authentication to TLS (walletless), select a choice from the *TNS Name (Service Level)* drop down, and press *OK*.
- 2. When the Download Credentials Files dialog opens, verify the file path and press OK. A prepopulated connection dialog will open.



- Select the alias name you wish to connect to, for example mydb_high, from the TNS
 Alias dropdown list.
- 4. Select **Default** from the **Role** drop down list
- **5.** Enter the username and password. (If you are new to Oracle Autonomous Database, use username **ADMIN**)
- 6. If you are using Proxy Authentication, check the **Show more options** checkbox and provide the proxy username and password. To guide you in entering the fields, note that in other tools, you may have connected using this format:

proxyusername[username]/[proxypassword]



For more details about connecting with a proxy, see Connecting Using a Proxy User.

- 7. If you want to use a different schema than the default schema associated with your username, check the **Show more options** checkbox and select the schema from the **Current Schema** dropdown.
- 8. Provide a connection name to be used to reference this connection in Database Explorer and elsewhere
- 9. Click the **Create Connection** button
- **10.** If you are using macOS, and receive a *Connection request timed out* error when trying to connect, please update .NET Runtime to version 6.0.

Note:

Connection information and settings may be stored with a User, Workspace, or Folder Scope. For more information see Organizing Connections by User, Workspace, or Folder Scope.

Connecting Using Credentials Files Obtained Elsewhere

If your Oracle Database is On-prem, then go to **Connecting to Oracle Database**. For additional help using the connection dialog, visit the connection dialog help.

The easiest way to connect to Autonomous Database is to use Oracle Cloud Infrastructure Explorer . Follow the steps described in Connecting Using Oracle Cloud Infrastructure Explorer to Automatically Download Credentials Files (Wallets) . However, if you have obtained the credentials files from another source, such as the Administration Console or from your administrator, follow these steps:

- Unzip the credentials files into the directory that is set as Config Files Folder in the Oracle Developer Tools for VS Code Extension Settings. By default this location is ~/ Oracle/network/admin on Linux and Mac and %USERPROFILE% \Oracle\network\admin on Windows.
- 2. To connect from Oracle Database Explorer, click the plus sign button



- 3. To connect to Oracle Database from a .SQL or .PL/SQL file, press F1 to open Command Palette and select *Oracle:Connect* from the dropdown. Then select *New Connection*.
- A connection dialog will open. In the Connection Type dropdown, select TNS Alias
- **5.** Make sure the **TNS Admin Location** field is set to the directory containing your credentials files. If not, change it.
- 6. Check the **Use Wallet File** checkbox
- 7. Make sure the *Wallet File Location* field is set to the directory containing your credentials files. If not, change it.
- 8. Select the alias name you wish to connect to, for example *mydb_high*, from the *TNS Alias* dropdown list.
- 9. Select **Default** from the **Role** drop down list
- **10.** Enter the username and password. (If you are new to Oracle Autonomous Database, use username **ADMIN**)
- 11. If you are using Proxy Authentication, check the **Show more options** checkbox and provide the proxy username and password. To guide you in entering the fields, note that in other tools, you may have connected using this format:

proxyusername[username]/[proxypassword]



For more details about connecting with a proxy, see Connecting Using a Proxy User.

- **12.** If you want to use a different schema than the default schema associated with your username, then check the *Show more options* checkbox and select the schema from the **Current Schema** dropdown.
- **13.** Provide a connection name to be used to reference this connection in Database Explorer and elsewhere
- 14. Click the Create Connection button
- **15.** If you are using macOS, and receive a *Connection request timed out* error when trying to connect, please update .NET Runtime to version 6.0.

Note:

Connection information and settings may be stored with a User, Workspace, or Folder Scope. For more information see Organizing Connections by User, Workspace, or Folder Scope.



Connecting Without Using Credentials Files

If your Oracle Database is On-prem, then go to **Connecting to Oracle Database**. For additional help using the connection dialog, visit the connection dialog help.

The easiest way to connect to Autonomous Database is to use Oracle Cloud Infrastructure Explorer. See Connecting Using Oracle Cloud Infrastructure Explorer to Connect Without Using Credentials Files (Walletless). However, if you have obtained the connection string from another source, such as the Administration Console or from your administrator, and the database is configured for walletless connectivity, perform the following steps.

- 1. You can connect to the Oracle Database using one of the following ways:
 - To connect to Oracle Database from a .SQL or .PL/SQL file, press F1 to open Command Palette and select Oracle:Connect from the dropdown. Then select New Connection.

Or.

- To connect from Oracle Database Explorer, click the plus (+) sign:
- 2. A connection dialog will open. In the Connection Type dropdown, select Advanced
- 3. Paste the connect string into the *Connect String* box.
- 4. Select **Default** from the **Role** drop down list
- **5.** Enter the username and password. (If you are new to Oracle Autonomous Database, use username **ADMIN**)
- 6. If you are using Proxy Authentication, check the **Show more options** checkbox and provide the proxy username and password. To guide you in entering the fields, note that in other tools, you may have connected using this format:

proxyusername[username]/[proxypassword]



For more details about connecting with a proxy, see Connecting Using a Proxy User.

- 7. If you want to use a different schema than the default schema associated with your username, then check the **Show more options** checkbox and select the schema from the **Current Schema** dropdown
- 8. Provide a connection name to be used to reference this connection in Database Explorer and elsewhere
- 9. Click the **Create Connection** button
- For information on how to enable walletless connectivity from Visual Studio Code, go to Configuring Walletless Connectivity and Network Access for Oracle Autonomous Databases (Oracle Cloud).



Note:

Connection information and settings may be stored with a User, Workspace, or Folder Scope. For more information see Organizing Connections by User, Workspace, or Folder Scope.

Connecting Using OCI IAM Single Sign-on

If your Oracle Database is On-prem, then go to **Connecting to Oracle Database**. For additional help using the connection dialog, visit the connection dialog help.

Note:

This connection method requires that your administrator has enabled OCI IAM Single Sign-on with ADB. You must also have installed .NET Runtime version 5.0 or later.

- Follow the instructions in the following documentation section to use OCI CLI to create a token, and to modify your sqlnet.ora and/or tnsnames.ora to use that token: Configuring a Client Connection for SQL*Plus That Uses an IAM Token. Disregard the portions of those instructions specific to SQL*Plus.
- Follow the steps from the quickstart sections in Connecting to Oracle Autonomous Database (ADB) as applicable, except:
 - In the *User name* field, enter a forward slash "/" (without the quotes)
 - The Password field should be left empty.

Organizing Connections by User, Workspace, or Folder Scope

Workspace and Folder scoped connection information and settings can be stored in a project along with the code for that project. This can also allow multiple Visual Studio Code users to share connection information via source controlled projects.

Connection information and settings can be stored at a user scope in the Visual Studio Code settings.json file for the user. If a workspace is currently open, then it can also be stored at a Workspace scope in a settings file in the workspace. And it can also be stored at a Workspace Folder scope in a settings file in a folder in the workspace.

Connections created with a workspace or folder scope will appear in Oracle Database Explorer when the Visual Studio Code workspace is open. When the workspace is closed or another workspace opened, those connections in Oracle Database Explorer will disappear.

For more information about Visual Studio Code User and Workspace settings see:

https://code.visualstudio.com/docs/getstarted/settings



To set the scope of a connection:

- Create a connection in Oracle Database Explorer by clicking the plus (+) sign to create a new connection.
- Select User, Workspace, or Folder tab at the top of the connection dialog. The
 Workspace scope will only be visible if a workspace is opened in Visual Studio Code. If
 the workspace contains folders, the folder names will be selectable from the Folders
 dropdown.



The scope of the connection can only be set when it is being created. It cannot be modified later. For example, you cannot modify it later using the **Update** Connection menu item.

- 3. Check Append 'workspace' to connection name or Append folder name to connection name if you wish the workspace or folder name to be included alongside the name of the connection node for easier identification.
- 4. Continue to populate the connection dialog, following the steps in Connecting to Oracle Database or Connecting to Oracle Autonomous Database (ADB).



Passwords cannot be saved for connections with Workspace or Folder scope.

Applying Filters to Oracle Database Explorer and IntelliSense Suggestions

You can apply filters to limit the amount of database schema objects that are shown in the Oracle Database Explorer tree control and that are offered as IntelliSense (autocomplete) suggestions.

Filters are applied on existing Oracle Database Explorer connections. To create a filter, follow these steps:

- 1. If needed, first create a connection by clicking the plus (+) sign to create a new connection, and following the steps in Connecting to Oracle Database or Connecting to Oracle Autonomous Database (ADB).
- 2. Right click on the connection node and select **Filters** to open the Filters dialog.
- From the list on the left side of the dialog, select the filter type, for example **Tables** or **Procedures**. If you wish to create a filter that applies to all object types, then select the **Connection** filter type.
- 4. Under Filter Properties select Match Any or Match All. Match Any means that any filter property, if evaluated to be true, results in the object being displayed or suggested by IntelliSense (autocomplete). Match All means that all Filter Properties must be evaluated to be true for the object to be displayed or suggested in IntelliSense (autocomplete).



- 5. If no Filter Properties are shown click **Add Filter** to begin adding one.
- 6. Select the Property and Condition drop down boxes and enter a value in the Value field. If the value is a string, check the Case Sensitive check box if the value should be used exactly as entered (without being uppercased first).
- Once you have entered the value, click the Add Filter button if you wish to add add additional Filter Properties.
- 8. To delete filter properties, click the **X** on the right of the filter property.
- 9. Check or uncheck the checkboxes labelled Enable filters for database explorer and Enable filters for intellisense as desired. You can enable/disable all of your filters across all object types for database explorer, intellisense or both by going to the top of the dialog and clicking the Enable/Disable All Filters dropdown and selecting one of the options.
- If you wish this filter to override any connection filter, then check the Override filter properties checkbox specified at the Connection level.
- 11. When you are finished, save your work by pressing the **Save** button.
- **12.** A Filter icon (funnel) will appear next to Filter Types shown on the left side of the Filters dialog if the Filter Type has an enabled filter on it.
- 13. Icons in Oracle Database Explorer will change to include a small funnel image to indicate that a filter is being applied
- **14.** To permanently delete all filters and start over fresh, click the **Delete All Filters** button near the top right portion of this filters dialog.

Changing the Default Schema for a Connection

To use a different schema than the default for the user you logged in as (for example, you logged in as ADMIN but want to default to using the HR schema when executing SQL or when browsing with Oracle Explorer), follow the steps in **Connecting to Oracle Database** or **Connecting to Oracle Autonomous Database** (ADB) to open the connection dialog and provide the connection information.

• In the connection dialog, check the **Show more options** checkbox and then select a different schema in the **Current Schema** dropdown.

Selecting a Default Connection to be used when Opening SQL files

You can select a connection in Oracle Database Explorer to be the default connection. This connection will be used when a SQL file is opened that is not explicitly associated with a connection. For example, when opening folders containing many SQL scripts this will associate the connection with all of them, saving you from having to associate each file with a connection.

To set a connection as default (replacing any existing default connection):

- 1. Create a connection in Oracle Explorer. See Connecting to Oracle Database.
- Right click on the connection and choose Set as Default Connection. The icon will change to indicate that the connection is now default.



- 3. Alternatively, in the connection dialog, check the **Set as default connection** check box.
- 4. To unset the default connection (so that there is no default), right click on the connection and choose **Unset as Default Connection**.

Running a SQL Script Each Time a Connection is Established

Each time a connection is established, you may wish to run a SQL script (login SQL script). This could be used to alter session settings to modify NLS parameters or anything else. A login SQL script may be used for all connections, and it can be overridden on a per connection basis.

- To set a login SQL script for all connections, go to the Extension Settings for Oracle Developer Tools for VS Code and set the **Connection Configuration: Login Script** value to the location of a sql script. For example, /myscripts/login.sql. Leave this setting blank if you only wish a log script to run for certain connections.
- To set a login SQL script for a particular connection in Oracle Explorer, open the
 connection dialog. For example, select the connection and choose the **Update** menu
 item. In the connection dialog, check the **Show more options** checkbox and then
 populate the **Login Script** field. This script will override any login script set in the
 extension settings.
- To view any output of the login SQL script, view the Results tab.

Colorizing Oracle Explorer Connections and Code Windows

You can colorize Oracle Database Explorer connection node names and their corresponding code window to make it easier to identify which code window is using which database connection.

To set a color for a connection in Oracle Database Explorer, open the connection dialog. For example, select an existing connection and choose the **Update** menu item, or click the Plus (+) icon to open a new connection.

In the connection dialog, click the **Color** button next to the **Connection Name** field. Select a color from the picker dialog and press the **Done** button. If you do not wish to use color you can click the **No Color** button in the picker dialog. Press the **Update Connection** or **Create Connection** on the connection dialog to save the changes.

Viewing other Schemas in Oracle Explorer

- In Oracle Explorer, click to expand the Other Users node. Select the schema you wish to view.
- If you will mostly be using the alternate schema and wish it to be the default schema shown in Oracle Explorer, follow the steps in Changing the Default Schema for a Connection.



Editing PL/SQL in your Database

- View Database Explorer by clicking the database icon in the Activity Bar on the far left side of Visual Studio Code.
- If the Database Explorer pane is empty (no connection nodes showing), click the
 plus (+) sign to create a new connection, following the steps in Connecting to
 Oracle Database or Connecting to Oracle Autonomous Database (ADB).
 Once connection nodes display, you can click on the node to view the database
 schema.
- Navigate in the tree control to the PL/SQL package, stored procedure/function, or trigger you want to edit.
- Right click on the PL/SQL package, stored procedure/function, or trigger and select *Open/Open Package Body/Open Specification* to open PL/SQL for editing. (Note: this menu item was previously named *Edit/Edit Package Body/Edit Specification* in earlier releases.)
- When done editing, right click in the PL/SQL code and select Save. (Note: this
 menu item was previously named Save to Database in earlier releases.)
- Errors that occur when saving will be listed in the Problems Panel. Click on an error to go to the line that contains the error.
- If you are using Visual Studio Code Auto Save, we recommend that you follow the steps in Saving PL/SQL in Database to a File. You can use Download instead of Open, or adjust the VS Code Auto Save Delay setting.

Saving PL/SQL in Database to a File

- In Oracle Database Explorer you can right click a package, procedure, function, or trigger and from the menu and select *Download/Download Package Body/ Download Package Specification*.
- To change the default directory where the file is saved, go to the settings and change *Download: Folder Type* to *Other Folder*. Then, change the setting *Download:Other Folder* to the path to the folder you wish downloads to be saved in.
- Alternatively, after opening the package, procedure, function, or trigger from
 Database Explorer select the tab with the PL/SQL code in it. In Visual Studio Code
 menu select File->Save As and then click Show Local.

Opening .SQL or .PL/SQL File

- In Oracle Explorer, right click on a connection node and select Open Existing SQL File.
- If a connection does not exist, create a new one by pressing the plus (+) icon and using the steps in Connecting to Oracle Database or Connecting to Oracle Autonomous Database (ADB).



Changing Database Connection for an Open .SQL or .PL/SQL File

- Press F1 to open Command Palette and select Oracle: Update Connection from the dropdown.
- Select an existing connection profile from the list or create a new one using the steps in Connecting to Oracle Database or Connecting to Oracle Autonomous Database (ADB).

Creating a New .SQL or .PLSQL File

- In Oracle Explorer, right click on a existing connection node and select *Open New SQL File*. If a connection does not exist, create a new one by pressing the plus (+) icon and using the steps in Connecting to Oracle Database or Connecting to Oracle Autonomous Database (ADB).
- Alternately, Press F1 to open Command Palette and select Oracle:Develop New SQL or PLSQL from the dropdown. Select an existing connection profile from the list or create a new one
- When done editing, in the VS Code menu select *File->Save As* to save the file.
- Alternately, you may execute the SQL*Plus CONNECT command. This command will associate the file with the connection specified in the command.

Using Auto Save when Editing PL/SQL

- Visual Studio Code Auto Save is enabled by going to the VS Code menu and selecting
 File->Auto Save.
- We recommend that you do not use the *Open* menu item in Database Explorer when
 Auto Save is enabled as it results in very frequent updates to the database. Instead, use
 the *Download* menu item as described in the Saving PL/SQL in Database to a File
 section.
- Alternatively, you can adjust the VS Code Auto Save Delay setting to a larger value.

Executing SQL and PL/SQL

- 1. Type some SQL or PL/SQL you wish to execute into the .SQL or .PLSQL file
- 2. While typing, autocomplete suggestions will appear as you type, for example column names. You can click the *i* icon in the suggestions to get more details such as the schema objects the suggestion is associated with. Use the arrow keys to navigate through the suggestions, and the enter key to select a suggestion. If you wish to use lower case characters with autocomplete suggestions, go to the settings and change *Intellisense > Suggestions: Keyword Casing* and *Intellisense > Suggestions: Object Name Casing* to *Iowercase*.



- **3.** Type a schema name followed by a period, for example *HR*. to use intellisense to view and select database objects.
- **4.** While typing, some code snippet suggestions may appear. You can view more snippets by typing *oracle* on a new line.
- 5. Position the cursor on a line that contains the SQL or PL/SQL that you wish to execute. Alternately, you can select (highlight) one or more SQL or PL/SQL statements. Right click and select *Execute SQL* from the menu. Select *Execute All* if you wish to execute all SQL and PL/SQL in the current file.
- 6. After executing SQL, a new document (Results Window) will open or the results will be appended to an open Results window. The maximum number of rows that can be returned is controlled by the *Max Rows* extension setting. As you scroll through the rows, more will be fetched up to this maximum.
- 7. To clear the results window, click the *Clear Results Window* button located in the area near the document tabs. To change the default to always clear the results window after every execution, change the *Clear Results Window* extension setting.
 - Errors that occur when running the script will be listed in the Problems Panel. Click on an error to go to the line that contains the error.
 - By default, SQL statements will automatically commit (auto commit is on). To change this, see **Disable/Enable Auto Commit** in the section below.
 - In addition to SQL and PL/SQL, you can enter SQL*Plus commands as well.
 For more information see the Executing SQL*Plus Commands section and visit Using SQL*Plus Commands with Oracle Developer Tools for VS Code

Viewing an Explain Plan/Execution Plan for a SQL Statement

You can view an Explain Plan for a SQL Statement in the code window to see the predicted plan for its execution. Similarly, you can view the Execution Plan after SQL has already been executed to see the actual plan used.

Both grid based and text based plan output are available and are configurable using the settings.

To view an Explain Plan for SQL you have entered into the code window, perform the following steps:

- Position the cursor on the line that contains the SQL and press the Explain Plan (grid) or the Explain Plan (text) icon in the toolbar. Alternatively, right click and select Explain Plan (grid) or the Explain Plan (text) from the menu.
- 2. To configure the results of Explain Plan, right click on the connection node and select Explain Plan and Execution Plan Settings



Explain Plan (grid) uses PLAN_TABLE while Explain Plan (text) uses the DBMS XPLAN PL/SQL package.



To view an Execution Plan for SQL you have executed in the code window, perform the following steps:

1. In order to view an execution plan you must have **SELECT** privileges on V\$SQL_PLAN. This can be granted using the statement:

```
GRANT SELECT on V $SQL PLAN to <user>
```

- 2. Type a SQL statement you are interested in and execute it. The statement must be executed before you can request an Execution Plan.
- Position the cursor on the line that contains the SQL and click the Execution Plan (grid)
 or the Execution Plan (text) icon in the toolbar. Alternatively, right click and select
 Execution Plan (grid) or the Execution Plan (text) from the menu.
- 4. To configure the results of Execution plan, right click on the connection node and select **Explain Plan and Execution Plan Settings**



Execution Plan (grid) uses V\$SQL_PLAN while Execution Plan (text) uses the DBMS XPLAN PL/SQL package.

Using Real-Time SQL Monitoring

Real-Time SQL Monitoring provides automatic monitoring of SQL statements, PL/SQL blocks, or composite database operations that are considered expensive. You can view a list of monitored SQL, view and save SQL Monitor Active Reports, and generate an Active Report for ad hoc SQL. The information provided by Real-Time SQL Monitoring is especially useful for long-running SQL statements.

Note:

The use of Real-time SQL Monitoring feature requires an Oracle Tuning Pack license (except for Oracle Database Free which requires no license). For more details, please refer to "Database Licensing Information User Manual" for the database version being used.

- Connect to a database in Oracle Explorer. Any user can view complete Active Reports for SQL they execute using schema objects they own. If your user has been granted the SELECT_CATALOG_ROLE, then you will be able to view Active Reports for SQL executed by other users. When this role has not been granted, and the schema objects involved are not owned by the user, the Active Report may be missing information, such as the Explain Plan.
- To view a list of monitored SQL, right click on a connection in Oracle Explorer and select
 Real Time SQL Monitoring from the menu. In the list of monitored SQL that appears,
 click the Activity Last: drop down and select the time frame you are interested in. Click
 the Top 100 by: drop down and select the metric you are interested in. Click the arrows
 in the column headers to sort by that column.



- To view an Active Report for a SQL statement in the list, click on the SQL ID you are interested in.
- To save a report, click the Save icon to choose to save as text, HTML, XML or as a Active Report.
- To generate an Active Report for ad-hoc SQL, type some SQL in the SQL editor, right click and select Execute and Monitor SQL.

Note

The ad-hoc SQL will be executed in order for it to be monitored, however the query results for the SQL will not be displayed as it usually is when you execute SQL.

Formatting SQL and PL/SQL with a Configurable Formatter

This extension includes a built in and configurable SQL and PL/SQL formatter that you can use to enforce style guidelines on your code.

- To modify the formatter settings, right click on an Oracle Explorer Connection and select SQL and PL/SQL Formatter Settings. Alternatively, in the SQL editor, click the SQL and PL/SQL Formatter Settings icon.
- To format SQL or PL/SQL, in the editor, click the Format Document icon, or right click and select Format Document with.. and then select Oracle Developer Tools for VS Code (SQL and PL/SQL)
- To undo a formatting attempt, use the editor's "Undo" function (Edit->Undo).

Using Lowercase/Title Case Characters with Autocomplete/ Intellisense

- While typing SQL or PL/SQL, autocomplete suggestions will appear as you type, for example column names. You can also type a schema name followed by a period, for example *HR*. to use intellisense to view and select database objects.
- You can click the i icon in the suggestions to get more details such as the schema objects the suggestion is associated with. Use the arrow keys to navigate through the suggestions, and the enter key to select a suggestion.
- By default upper case characters will be used with autocomplete or intellisense suggestions. If you wish to use lower case or title case instead, go to the settings and change Intellisense > Suggestions: Keyword Casing and Intellisense > Suggestions: Object Name Casing to Iowercase or titlecase.

Navigating through SQL Scripts and PL/SQL Packages

To navigate through long SQL scripts using breadcrumbs, click on the breadcrumb
at the top of the editor (it will usually be a file name or schema object). This will
show a drop down of all SQL commands, PL/SQL packages, anonymous blocks,

- etc in the script. For some items like PL/SQL packages, procedures or functions you can further expand the breadcrumb to see additional details.
- To make breadcrumbs easier to use, you may wish to modify the Visual Studio Code settings. In particular, setting *Breadcrumbs: File Path* to *last* or *off* decreases the amount of space taken by the file path.
- You can also navigate through PL/SQL packages/procedures/functions that are in the database by using Oracle Explorer to right click on the procedure or function and choosing Open from the menu.
- While viewing SQL or PL/SQL scripts, you can right click on schema object names and from the menu select Go to Definition/Peek Definition, Go to/Peek Type Definition and Go to/Peek Implementation. In the case of Go to, these will open a new window with the PL/SQL code where the object is defined or implemented. For Peek, it will allow you to view and edit the code in place in the current editor window.

Executing SQL*Plus Commands

- SQL*Plus commands provide useful functionality such as connecting and disconnecting, enabling and disabling autocommit, running other SQL*Plus scripts, describing database object metadata, defining and using substitution variables, defining and using bind variables, controlling output display size, saving script output to a file, and more. To execute SQL*Plus commands do the following:
 - Type a SQL*Plus command into the .SQL or .PLSQL file.
 While typing, autocompletion suggestions will appear as you type
 - 2. Select (highlight) one or more SQL*Plus commands and SQL or PL/SQL statements.
 - 3. Right click and select *Execute SQL* from the menu.
 - Select Execute All if you wish to execute all SQL*Plus commands, SQL, and PL/SQL in the current file.
 - If one more more SQL*Plus commands are not supported, you will receive a warning message
 - The SQL*Plus **CONNECT** command will associate the file with the connection specified in the command. After executing this command, intellisense/autocomplete will use the new connection and schema.
- For more information, including a reference guide of supported SQL*Plus commands, visit Using SQL*Plus Commands with Oracle Developer Tools for VS Code

Disabling and Enabling Auto Commit

When executing multiple SQL statements (for example, running a script), auto commit automatically commits work after each statement. If auto commit is disabled, an explicit COMMIT or ROLLBACK statement can be used to control the behavior

- In your SQL file, enter SET AUTOCOMMIT OFF or SET AUTOCOMMIT ON and then
 right click and select Execute SQL from the menu. This autocommit setting will be in
 effect for the life of your connection and will override the default extension setting.
- To set the default for all SQL files opened with this extension, Press F1 to open the Command Palette and enter *Preferences: Open Settings (UI)* command.



- 3. Expand the *Extensions* node and select *Oracle Developer Tools for VS Code Configuration*.
- Check the SQLPlus:Auto Commit checkbox to enable auto commit and uncheck it to disable it.

Viewing and Saving Result Sets

After executing SQL, a new document (Results Window) will open with the result set or the results will be appended to an open Results window. The maximum number of rows that can be returned is controlled by the *Max Rows* extension setting. As you page through the rows, more will be fetched - up to this maximum.

- To save results, choose the format: .CSV or JSON. To change the delimiter or text qualifier in a .CSV file, go to the extension settings and set Query>Result Set>CSV:Delimiter and/or Query>Result Set>CSV:Text Qualifier. Then click the icon to Save Selected Rows or Save All Rows. After providing a file name and location, the file will open in Visual Studio Code.
- To copy the selected rows to the clipboard, click the Copy Selected Row(s) to Clipboard icon
- To clear the results window, click the *Clear Results Window* button located in the area near the document tabs. To change the default to always clear the results window after every execution, change the *Clear Results Window* extension setting.

Debugging PL/SQL

Debugging PL/SQL from Oracle Database Explorer



PL/SQL debugging in Visual Studio Code works with both on-premises and databases in Oracle Cloud. However, Oracle Autonomous Database is not currently supported.

When first using PL/SQL debugging, configure both the PL/SQL debugger and the database:

- In Oracle Database Explorer, right click on a connection name and select *PL/SQL Debugger and Compiler Settings* and set the ip address and port number range that will be used by the debugger (the Oracle Database will connect back to your machine using that IP address and one of the ports)
- 2. A script to grant privileges and configure the database is provided in the same dialog. Copy the script and then right click on the connection node for the database and select *Open New SQL File*. Paste the script into the new file, modify it as needed, and then right click in the editor and select *Execute All* from the menu.



- 3. The PL/SQL procedure/function/packages you wish to debug must be compiled with debug information: Right click on the procedure/function/package and select *Compile Debug* from the menu. The Oracle Explorer icons will change to alert you and also to remind you to issue a *Compile* when done debugging to restore them to their non-debug state.
- Right click on the procedure/function/package and select *Open*, or *Open Package Body* from the menu. Set breakpoints as desired (note: conditional breakpoints are not currently supported).
- 5. To begin debugging, from the same menu select **Step Into** or **Run Debug**.



Debugging PL/SQL with Visual Studio Code (and more), for a walkthrough showing how to use PL./SQL debugging.

Debugging PL/SQL Called By an Application or SQL Scripts

Note:

PL/SQL debugging in Visual Studio Code works with both on-premises and databases in Oracle Cloud. However, Oracle Autonomous Database is not currently supported.

- The PL/SQL Debugger can listen for calls to a procedure/function/package and start debugging them when they are called. Any application (web app or command line, using any programming language) or SQL script can make the PL/SQL call, and the application or script can be located on any machine.
- When first using PL/SQL debugging, configure both the PL/SQL debugger and the database:
- In Oracle Database Explorer, right click on a connection name and select *PL/SQL Debugger and Compiler Settings* and set the ip address and port number range that will be used by the debugger (the Oracle Database will connect back to your machine using that IP address and one of the ports)
- A script to grant privileges and configure the database is provided in the same dialog.
 Copy the script and then right click on the connection node for the database and select
 Open New SQL File. Paste the script into the new file, modify it as needed, and then right click in the editor and select Execute All from the menu.
- The PL/SQL procedure/function/packages you wish to debug must be compiled with debug information: Right click on the procedure/function/package and select *Compile Debug* from the menu. The Oracle Explorer icons will change to alert you and also to remind you to issue a *Compile* when done debugging to restore them to their non-debug state.
- Right click on the procedure/function/package and select *Open*, or *Open Package Body* from the menu. Set breakpoints as desired (note: conditional breakpoints are not currently supported).



- To start the debugger, right click on any connection name and select Start
 External Application Debugger. The Debug Console will display the IP address and port number that is being used. Make a note of these.
- If the PL/SQL call is being made by an application (using Oracle data access driver other than the Oracle JDBC thin client), set a *ORA_DEBUG_JDWP* environment variable in the environment of the application with the value host=ipaddress;port=portnumber. For example: host=127.0.0.1;port=65000. The IP address and port number should be the same values reported in the Debug Console. This environment variable must be set before the connection is made by the application to the Oracle Database. For example, this can be set in a Visual Studio Code project in the launch.json file in the configurations section (eg "env":

 { "ORA_DEBUG_JDWP": "host=127.0.0.1;port=65000" }) or it can be set on a command line before launching the application.
- If the PL/SQL call is being made by an application using the Oracle JDBC thin client, or if you cannot enable debugging at the time the connection to the Oracle database is made, modify your code to make a call to the DBMS_DEBUG_JDWP.CONNECT_TCP package procedure at some point in your code before the call is made to the stored procedure/function/or package that you wish to debug. In this call to CONNECT_TCP provide the same IP address and port number reported in the Debug Console. For example, if using JDBC: String sql = "CALL DBMS_DEBUG_JDWP.CONNECT_TCP(?,?)"; CallableStatement callStmt = conn.prepareCall(sql)); callStmt.setString(1, host); callStmt.setString(2, port); callStmt.execute();. At a point in your code after the PL/SQL call is made and debugging is finished, add a call to DBMS_DEBUG_JDWP.DISCONNECT as well.
- If the PL/SQL call is being made by an SQL script in Visual Studio Code, add the following line in the SQL script at some point before the call is made to the stored procedure/function/or package that you wish to debug: exec (DBMS_DEBUG_JDWP.CONNECT_TCP('ip address', 'port'));. For example: exec (DBMS_DEBUG_JDWP.CONNECT_TCP('127.0.0.1', '65000')); The IP address and port number should be the same values reported in the Debug Console. At a point in the script after the PL/SQL call is made and debugging is finished, add exec (DBMS_DEBUG_JDWP.DISCONNECT();).
- When the application or SQL script is run, a message will appear in the Debug Console stating A database has connected to the PL/SQL Debugger on host: youripaddress and port: yourport. This indicates that the Oracle Database has successfully connected back to Visual Studio Code and debugging can begin.

See Also:

Debugging PL/SQL with Visual Studio Code (and more), for a walkthrough showing how to use PL./SQL debugging.

Viewing SQL History

- 1. In Oracle Explorer, click on the *History* control to open it.
- 2. Expand the connection name for which you want to see the history. Previously executed SQL commands from this session will be listed.



- 3. Hover over a long SQL statement to view a tooltip containing the complete statement.
- 4. To execute a SQL statement directly from the history, right click on it and select *Run*.
- 5. To copy the SQL to an open editor, right click on it and select *Copy to Editor*.
- 6. To copy the SQL to an new SQL File and open it in an editor, right click on it and select *Open in Editor*. Then press F1 to open Command Palette and select *Oracle:Connect* from the dropdown.
- SQL history does not persist across sessions. For permanent storage, save the SQL as a bookmark by right clicking and selecting **Bookmark SQL** from the menu.

Creating a SQL Bookmark

- Select one or more lines of SQL or PL/SQL in the editor, right click and select Bookmark SQL from the menu
- 2. Provide a bookmark name and a folder name
- 3. In Oracle Explorer, click on the **Bookmarks** control to open it.
- 4. Expand the folder name. Bookmarks will be listed.
- 5. Hover over a bookmark to view a tooltip containing the complete statement.
- 6. To execute the SQL statement directly, right click on the bookmark and select *Run*.
- 7. To copy the SQL to an open editor, right click on it and select *Copy to Editor*.
- 8. To copy the SQL to a new SQL file, right click on the bookmark and choose *Open in Editor* from the menu.

Configure the Location of the Query Results Window

To modify the default location of the Query Results Window, for example, to have the SQL code editor in an upper pane and the Query Results window in a lower pane, open the extension settings and modify the **Query: Open Results Window** setting as shown below:

- Select Right to open results window to the right of the currently active editor.
- Select Below to open results window below the currently active editor.
- Select Workbench > Editor Management: Open Positioning to open the results window using the Visual Studio Code Workbench > Editor Management: Open Positioning setting.

Creating and Modifying Keyboard Shortcuts

- To create keyboard shortcuts (keybindings) or to modify existing ones, go to the *File* menu in VS Code and select *Preferences->Keyboard Shortcuts*
- 2. In the search text box, enter a portion of the name of the extension whose shortcut you would like to modify, for example "oracle".
- 3. A list of commands and their shortcuts will appear. Click the pencil icon on the left side of a row to edit a shortcut, or the plus (+) sign to create a new one.



- **4.** When prompted, enter the key combination and if it is not being used by another extension, press enter. If it is being used by another extension, press escape and try again.
- 5. To delete a shortcut, right click on the shortcut and select *Remove Keybinding*



2

Learn What's New in This Version

To see a list of new features in this release, visit the Visual Studio Code Marketplace



3

Get Help or Provide Feedback

Visit the Oracle Developer Tools for VS Code help forums to ask questions and provide feedback about this extension



Glossary



Index

