

Deploying Oracle Banking Treasury Management Application
on WebLogic
Oracle Banking Treasury Management
Release 14.7.1.0.0
Part No. F84403-01
[May] [2023]



Table of Contents

1.	DEPLOYING ORACLE BANKING TREASURY MANAGEMENT ON WEBLOGIC	1-1
1.1	INTRODUCTION	1-1
1.2	BUILDING APPLICATION	1-1
1.2.1	<i>Building Application</i>	<i>1-1</i>
1.3	DEPLOYING APPLICATION IN ORACLE WEBLOGIC	1-1
1.3.1	<i>Deploying Integration Adapter EAR from WebLogic Administration Console</i>	<i>1-1</i>
1.3.2	<i>Deploying Dependency Library “Jax-RS”</i>	<i>1-7</i>
1.3.3	<i>Deploying OBTR Application from WebLogic Administration Console.....</i>	<i>1-11</i>
1.3.4	<i>Deploying Gateway/Scheduler Applications from WebLogic Administration Console</i>	<i>1-19</i>

1. Deploying Oracle Banking Treasury Management on WebLogic

1.1 Introduction

This chapter explains the steps to deploy Oracle Banking Treasury Management application into Oracle WebLogic application server.

1.2 Building Application

For building Oracle Banking Treasury Management Application, refer to the following chapters.

1.2.1 Building Application

Refer to the chapter 'Building Application'. This includes the following details:

- Creating Property File
- Building EAR File
- Configuring Plug-ins
- Loading Properties Files

1.3 Deploying Application in Oracle WebLogic


This section explains the method of deploying Oracle Banking Treasury Management Application into Oracle WebLogic application server.

1.3.1 Deploying Integration Adapter EAR from WebLogic Administration Console


To deploy Oracle Banking Treasury Management Application from Oracle WebLogic administration console, follow the steps given below.

1. Start the Administrative Console of WebLogic application server. You can start this by entering Oracle WebLogic Admin Console URL in the address bar in an internet browser.
Eg: <http://10.10.10.10:1001/console>


The following screen is displayed:




2. Specify the WebLogic administrator user name and password. Click 'Log In'.



- You need to deploy an Integration adapter EAR. For e.g. 'OBTextAdapter.ear'. Go to 'Deployment'. Click 'Lock & Edit' button to enable the buttons. This action enables the buttons.




- Click 'Install' button. The following screen is displayed:




- In order to specify the path/location of the enterprise archive file, click the link 'upload your file(s)'.
- Specify the EAR file path. You can use the 'Browse' button to locate the file.

7. Click 'Next'. The following screen is displayed.



8. Select the application Adapter EAR from the list.


9. Click 'Next'. Following screen is displayed:



10. Choose the targeting style 'Install this deployment as a library'.


11. Click 'Next'.

12. The following screen is displayed




13. Select the target of the application. You can choose the server 'AdminServer' or 'Managed Server(s)'.

14. Click 'Next'. The following screen is displayed.




15. Check the deployment name.


16. The remaining portion of the screen is shown below:



17. Click 'Finish' button. The following screen is displayed.



18. Click 'Save' button. The message 'Settings updated successfully' is displayed.




19. Click 'Activate Changes' button on the left pane. The message 'All the changes have been activated. No restarts are necessary' is displayed.

1.3.2 Deploying Dependency Library "Jax-RS"

This library must be installed before deploying OBTR.ear. Follow the below steps


1. Start the Administrative Console of WebLogic application server. You can start this by entering Oracle WebLogic Admin Console URL in the address bar in an internet browser.
Eg: <http://10.10.10.10:1001/console>

2. The following screen is displayed:



3. Specify the WebLogic administrator user name and password. Click 'Log In'.

The following screen is displayed:



4. Click install button

ORACLE WebLogic Server Administration Console 12c

Home Log Out Preferences Record Help

Welcome, infra Connected to: STD_PAYMENTS

Summary of Deployments

Configuration Control Monitoring

This page displays the list of Java EE applications and standalone application modules installed to this domain.

You can update (redeploy) or delete installed applications and modules from the domain by selecting the checkbox next to the application name and then using the controls on this page.

To install a new application or module for deployment to targets in this domain, click **Install**.

Customize this table

Deployments

Name	State	Health	Type	Targets	Scope	Domain Partitions	Deployment Order
adf.oracle.businesseditor(1.0,12.2.1.0.0)	Active		Library	AdminServer_payments, pm_server1	Global	100	
adf.oracle.domain(1.0,12.2.1.0.0)	Active		Library	AdminServer_payments, pm_server1	Global	100	
adf.oracle.domain.webapp(1.0,12.2.1.0.0)	Active		Library	AdminServer_payments, pm_server1	Global	100	
coherence-transaction-rar	Active	OK	Resource Adapter	AdminServer_payments, pm_server1	Global	100	
DMS Application (12.2.1.0.0)	Active	OK	Web Application	AdminServer_payments, pm_server1	Global	5	
em	Active	OK	Enterprise Application	AdminServer_payments	Global	400	
emagenttaskimpl_jar(12.4,12.1.0.4.0)	Active		Library	AdminServer_payments	Global	100	
emagenttaskimpl_jar(12.4,12.1.0.4.0)	Active		Library	AdminServer_payments	Global	100	
emagenttask_jar(12.4,12.1.0.4.0)	Active		Library	AdminServer_payments	Global	100	
emas	Active		Library	AdminServer_payments	Global	100	
emcore	Active		Library	AdminServer_payments	Global	100	
emcoreclient_jar	Active		Library	AdminServer_payments	Global	100	
emcorecommon_jar	Active		Library	AdminServer_payments	Global	100	
emcoreconsole_jar	Active		Library	AdminServer_payments	Global	100	
emcoreendtk_jar(11.2.0.1.0,12.1.0.0.0)	Active		Library	AdminServer_payments	Global	100	
emcoreepbs_jar	Active		Library	AdminServer_payments	Global	100	
emcoresdkimpl_jar(11.2.0.1.0,12.1.0.0.0)	Active		Library	AdminServer_payments	Global	100	
emcoresdk_jar(11.2.0.1.0,12.1.0.0.0)	Active		Library	AdminServer_payments	Global	100	
emcore_jar	Active		Library	AdminServer_payments	Global	100	
em_common(12.4,12.1.0.4.0)	Active		Library	AdminServer_payments	Global	100	
em core ppc polo jar	Active		Library	AdminServer_payments	Global	100	

No pending changes exist. Click the Release Configuration button to allow others to edit the domain.

Lock & Edit
Release Configuration

Domain Structure

- SOAADM3
 - Domain Partitions
 - Environment
 - Deployments
 - Services
 - Messaging
 - Data Sources
 - Persistent Stores
 - Foreign JNDI Providers
 - Work Contexts
 - XML Registries
 - XML Entity Caches
 - JCOM
 - Mail Sessions

How do I...

- Start and stop a deployed enterprise application
- Configure an enterprise application
- Create a deployment plan
- Target an enterprise application to a server instance
- Test the modules in an enterprise application

System Status

Health of Running Servers as of 6:13 PM

- Failed (0)
- Critical (0)
- Overloaded (0)
- Warning (0)
- OK (2)

Install Application Assistant

Back Next Finish Cancel

Locate deployment to install and prepare for deployment

Select the file path that represents the application root directory, archive file, exploded archive directory, or application module descriptor that you want to install. You can also enter the path of the application directory or file in the Path field.

Note: Only valid file paths are displayed below. If you cannot find your deployment files, Upload your file(s) and/or confirm that your application contains the required deployment descriptors.

Path: /scratch/app/bpm12212/user_projects/domains/soaadm3/servers/AdminServer/upload/jax-rs-2.0.war/app/jax-rs-2.0.war

Recently Used Paths: /scratch/app/bpm12212/user_projects/domains/soaadm3/servers/AdminServer/upload/FCUBS.ear/app


Current Location: 10.184.158.197 / scratch / app / bpm12212 / user_projects / domains / soaadm3 / servers / AdminServer / upload / jax-rs-2.0.war / app

jax-rs-2.0.war


Back Next Finish Cancel

WebLogic Server Version: 12.2.1.2.0
Copyright (c) 1996-2016, Oracle and/or its affiliates. All rights reserved.


Navigate and select jersey bundle under the path “w\server\common\deployable-libraries\jax-rs-2.0.war” and click next



Select "install this deployment as library", select target server as managed server and click next.



Click finish button



This library must appear in the deployment with Type column as “Library”


Note :- latest Jax-rs version will be jax-rs(2.0,2.22.1.0)

1.3.3 **Deploying OBTR Application from WebLogic Administration Console**


To deploy Oracle Banking Treasury Management Application from Oracle WebLogic administration console, follow the steps given below.

1. Start the Administrative Console of WebLogic application server. You can start this by entering Oracle WebLogic Admin Console URL in the address bar in an internet browser.
Eg: <http://10.10.10.10:1001/console>

The following screen is displayed:




2. Specify the WebLogic administrator user name and password. Click ‘Log In’.




3. You need to deploy an EAR. For e.g. 'OBTR.ear'. Go to 'Deployment'.


Click 'Lock & Edit' button to enable the buttons. This action enables the buttons.



4. Click 'Install' button. The following screen is displayed:




5. In order to specify the path/location of the enterprise archive file, click the link 'upload your file(s)'.
6. Click 'Next'. The following screen is displayed:




7. Specify the EAR file path. You can use the 'Browse' button to locate the file.

8. Click 'Next'. The following screen is displayed.



9. Select the application OBTR EAR created from the list.


10. Click 'Next'. Following screen is displayed:



11. Choose the targeting style 'Install this deployment as an application'.


12. Click 'Next'.

The following screen is displayed



13. Select the target of the application. You can choose the server 'AdminServer' or 'Managed Server(s)'.

14. Click 'Next'. The following screen appears.



15. Check the deployment name.

The remaining portion of the screen is shown below:


The screenshot shows the 'Security' and 'Source accessibility' configuration screens. On the left, there is a navigation pane with 'Security Realms', 'Interoperability', and 'Diagnostics'. Below it, a 'How do I...' section lists tasks like 'Start and stop a deployed Enterprise application'. The 'System Status' section shows 'Health of Running Servers' with a bar chart indicating 'Failed (0)', 'Critical (0)', 'Overloaded (0)', 'Warning (0)', and 'OK (1)'. The main area is divided into two sections: 'Security' and 'Source accessibility'. The 'Security' section asks 'What security model do you want to use with this application?' and offers three options: 'DD Only' (selected), 'Custom Roles', and 'Custom Roles and Policies'. The 'Source accessibility' section asks 'How should the source files be made accessible?' and offers two options: 'Use the defaults defined by the deployment's targets' (selected) and 'Copy this application onto every target for me'. A 'Location' field is set to 'D:\dev11g11.1.1.0\user_projects\domains\FCUBS11\src'. At the bottom, there are 'Back', 'Next', 'Finish', and 'Cancel' buttons.

16. Check whether the deployment location is accessible or not.


The following screen is displayed.

The screenshot shows the 'Install Application Assistant' screen. On the left, there is a navigation pane with 'Domain Structure' showing 'FCUBS11' and its sub-components: 'Environment', 'Deployments', 'Services', 'Security Realms', 'Interoperability', and 'Diagnostics'. Below it, a 'How do I...' section lists tasks like 'Start and stop a deployed Enterprise application'. The 'System Status' section shows 'Health of Running Servers'. The main area is titled 'Review your choices and click Finish' and contains a 'Summary' section. The 'Summary' section displays the following information: 'Deployment: D:\dev11g11.1.1.0\user_projects\domains\FCUBS11\servers\AdminServer\upload\FCUBS11.ear', 'Name: FCUBS11', 'Staging mode: Use the defaults defined by the chosen targets', and 'Security Model: DDOnly: Use only roles and policies that are defined in the deployment descriptors'. Below the summary, there is a 'Target Summary' table with two columns: 'Components' and 'Targets'. The table contains one row: 'FCUBS11.ear' under 'Components' and 'ManagedServer_1' under 'Targets'. At the bottom, there are 'Back', 'Next', 'Finish', and 'Cancel' buttons.

17. Click 'Finish' button. The following screen is displayed.




18. Click 'Save' button. The message 'Settings updated successfully' is displayed.




19. Click 'Activate Changes' button on the left pane. The message 'All the changes have been activated. No restarts are necessary' is displayed.

The screen is given below:





Click 'Deployment' on the left pane. Switch to Control tab .The following screen is displayed.



20. Click 'Start' drop-down button and select 'Servicing all requests'.

The following screen is displayed.



21. Click 'Yes'. The following screen is displayed.

This completes the deployment process.

1.3.4 Deploying Gateway/Scheduler Applications from WebLogic Administration Console

To deploy Oracle Banking Treasury Management Gateway/Scheduler Application from Oracle WebLogic administration console, follow the steps given below.


1. Launch Administrative Console of WebLogic application server. You can launch this by entering Oracle WebLogic Admin Console URL in the address bar in an internet browser.
Eg: <http://10.10.10.10:1001/console>

22. The following screen is displayed:




23. Specify the WebLogic administrator user name and password. Click 'Log In'.

The following screen is displayed:




24. You need to deploy an EAR. For e.g. 'GWEJB.ear'. Go to 'Deployment'.

Click 'Lock & Edit' button to enable the buttons. This action enables the buttons.




25. Click 'Install' button. The following screen is displayed:




26. In order to specify the path/location of the enterprise archive file, click the link 'upload your file(s)'.

27. Click 'Next'. The following screen is displayed:



28. Specify the EAR file path. You can use the 'Browse' button to locate the file.

29. Click 'Next'. The following screen is displayed:



30. Select the application from the list.

31. Click 'Next'. Following screen is displayed:

The screenshot shows the Oracle WebLogic Server Administration Console 12c. The main window is titled 'Install Application Assistant'. On the left, there is a sidebar with sections: 'Change Center' (with 'View changes and restarts' and 'Release Configuration' buttons), 'Domain Structure' (a tree view showing 'PM1221TR2' with sub-items like 'Domain Partitions', 'Environment', 'Deployments', 'Services', 'Security Realms', 'Interoperability', and 'Diagnostics'), 'How do I...' (a list of tasks), and 'System Status' (a 'Health of Running Servers' section showing 'Failed (0)', 'Critical (0)', 'Overloaded (0)', 'Warning (0)', and 'OK (2)'). The main content area has a breadcrumb 'Home > Summary of Deployments' and a search bar. Below this, there are 'Back', 'Next', 'Finish', and 'Cancel' buttons. The 'Choose installation type and scope' section contains three radio buttons: 'Install this deployment as an application' (selected), 'Install this deployment as a library', and 'Install this deployment as an application, but target the components individually'. Below these, there is a 'Scope:' dropdown menu set to 'Global'.

32. Choose the targeting style 'Install this deployment as an application'.

33. Click 'Next'.

The following screen is displayed

The screenshot shows the Oracle WebLogic Server Administration Console 12c, specifically the 'Select deployment targets' screen. The sidebar is identical to the previous screen. The main content area has a breadcrumb 'Home > Summary of Deployments' and a search bar. Below this, there are 'Back', 'Next', 'Finish', and 'Cancel' buttons. The 'Select deployment targets' section contains a text box with the instruction: 'Select the servers and/or clusters to which you want to deploy this application. (You can reconfigure deployment targets later.)'. Below this, there is a table titled 'Available targets for GWEJB :'. The table has two columns: 'Servers' and a checkbox. The first row is 'Admin_PM1TR2' with an unchecked checkbox. The second row is 'payments_server1' with a checked checkbox. Below the table, there are 'Back', 'Next', 'Finish', and 'Cancel' buttons.

34. Select the target of the application. You can choose the server 'AdminServer' or 'Managed Server(s)'.

35. Click 'Next'. The following screen is displayed.

Oracle WebLogic Server Administration Console 12c

Home Log Out Preferences Record Help

Welcome, weblogic Connected to: FCAPACK125

Change Center

View changes and restarts

No pending changes exist. Click the Release Configuration button to allow others to edit the domain.

Lock & Edit

Release Configuration

Domain Structure

FCAPACK125

- Domain Partitions
- Environment
- Deployments
- Services
 - Messaging
 - Data Sources
 - Persistent Stores
 - Foreign JNDI Providers
 - Work Contexts
 - XML Registries
 - XML Entity Caches
 - JCOH
 - Mail Sessions

How do I...?

- Start and stop a deployed enterprise application
- Configure an enterprise application
- Create a deployment plan
- Target an enterprise application to a server instance
- Test the modules in an enterprise application

System Status

Health of Running Servers as of 2:13 AM

Health	Count
Failed	(0)
Critical	(0)
Overloaded	(0)
Warning	(0)
OK	(2)

Install Application Assistant

Back Next Finish Cancel

Optional Settings

You can modify these settings or accept the defaults.

* Indicates required fields

General

What do you want to name this deployment?

Name: GWEJB

Security

What security model do you want to use with this application?

DD Only: Use only roles and policies that are defined in the deployment descriptors.

Custom Roles: Use roles that are defined in the Administration Console; use policies that are defined in the deployment descriptor.

Custom Roles and Policies: Use only roles and policies that are defined in the Administration Console.

Advanced: Use a custom model that you have configured on the realm's configuration page.

Source Accessibility

How should the source files be made accessible?

Use the defaults defined by the deployment's targets

Recommended selection.

Copy this application onto every target for me

During deployment, the files will be copied automatically to the Managed Servers to which the application is targeted.

I will make the deployment accessible from the following location

Locations: /scratch/app/v12212/user_projects/domains/FCAPACK125/serv

Provide the location from where all targets will access this application's files. This is often a shared directory. You must ensure the application files exist in this location and that each target can reach the location.

Plan Source Accessibility

How should the plan source files be made accessible?

Use the same accessibility as the application

Recommended selection.

Copy this plan onto every target for me

During deployment, the plan files will be copied automatically to the Managed Servers to which the application is targeted.

Do not copy this plan to targets

You must ensure the plan files exist in the shared location and that each target can reach the location.

Back Next Finish Cancel

36. Check the deployment name.

The remaining portion of the screen is shown below:

Oracle WebLogic Server Administration Console 12c

Home Log Out Preferences Record Help

Welcome, weblogic Connected to: FCAPACK125

Change Center

View changes and restarts

No pending changes exist. Click the Release Configuration button to allow others to edit the domain.

Lock & Edit

Release Configuration

Domain Structure

FCAPACK125

- Domain Partitions
- Environment
- Deployments
- Services
 - Messaging
 - Data Sources
 - Persistent Stores
 - Foreign JNDI Providers
 - Work Contexts
 - XML Registries
 - XML Entity Caches
 - JCOH
 - Mail Sessions

How do I...?

- Start and stop a deployed enterprise application
- Configure an enterprise application
- Create a deployment plan
- Target an enterprise application to a server instance
- Test the modules in an enterprise application

System Status

Health of Running Servers as of 2:13 AM

Health	Count
Failed	(0)
Critical	(0)
Overloaded	(0)
Warning	(0)
OK	(2)

Install Application Assistant

Back Next Finish Cancel

Optional Settings

You can modify these settings or accept the defaults.

* Indicates required fields

General

What do you want to name this deployment?

Name: GWEJB

Security

What security model do you want to use with this application?

DD Only: Use only roles and policies that are defined in the deployment descriptors.

Custom Roles: Use roles that are defined in the Administration Console; use policies that are defined in the deployment descriptor.

Custom Roles and Policies: Use only roles and policies that are defined in the Administration Console.

Advanced: Use a custom model that you have configured on the realm's configuration page.

Source Accessibility

How should the source files be made accessible?

Use the defaults defined by the deployment's targets

Recommended selection.

Copy this application onto every target for me

During deployment, the files will be copied automatically to the Managed Servers to which the application is targeted.

I will make the deployment accessible from the following location

Locations: /scratch/app/v12212/user_projects/domains/FCAPACK125/serv

Provide the location from where all targets will access this application's files. This is often a shared directory. You must ensure the application files exist in this location and that each target can reach the location.

Plan Source Accessibility

How should the plan source files be made accessible?

Use the same accessibility as the application

Recommended selection.

Copy this plan onto every target for me

During deployment, the plan files will be copied automatically to the Managed Servers to which the application is targeted.

Do not copy this plan to targets

You must ensure the plan files exist in the shared location and that each target can reach the location.

Back Next Finish Cancel

Check whether the deployment location is accessible or not. The following screen is displayed.

ORACLE WebLogic Server Administration Console 12c

Home Log Out Preferences Record Help

Home > Summary of Deployments

Install Application Assistant

Back Next Finish Cancel

Review your choices and click Finish

Click Finish to complete the deployment. This may take a few moments to complete.

Additional Configuration

In order to work successfully, this application may require additional configuration. Do you want to review this application's configuration after completing this assistant?

☒ Yes, take me to the deployment's configuration screen.

☐ No, I will review the configuration later.

Summary

Deployment: /scratch/app/fmw122/Oracle/user_projects/domains/PM1221TR2/servers/Admin_PM1TR2/upload/GWEJB.ear/app/GWEJB.ear

Name: GWEJB

Staging Mode: Use the defaults defined by the chosen targets

Plan Staging Mode: Use the same accessibility as the application

Security Model: DDOOnly: Use only roles and policies that are defined in the deployment descriptors.

Scope: Global

Components	Targets
GWEJB.ear	payments_server1

Back Next Finish Cancel

37. Click 'Finish' button. The following screen is displayed.

ORACLE WebLogic Server Administration Console 12c

Home Log Out Preferences Record Help

Welcome, admin | C...

Home > Summary of Deployments > GWEJB(12.2.0.0.0)

Settings for GWEJB(12.2.0.0.0)

Overview Deployment Plan Configuration Security Targets Control Testing Monitoring Notes

Save

Use this page to view the general configuration of an enterprise application, such as its name, the physical path to the application files, the associated deployment plan, and so on. The table at the end of the page lists the modules (such as Web applications) contained in the enterprise application. Click on the name of the module to view and update its configuration.

Name: GWEJB The name of this enterprise application. [More Info...](#)

Scope: Global Specifies if this enterprise application is accessible within the domain, a partition, or a resource template. [More Info...](#)

Archive Version: 12.2.0.0.0 The archive version, specified from the manifest or overridden during deployment. [More Info...](#)

Path: /scratch/app/fmw122/Oracle/user_projects/domains/PM1221TR2/servers/Admin_PM1TR2/upload/GWEJB.ear/app/GWEJB.ear The path to the source of the deployable unit on the Administration Server. [More Info...](#)

Deployment Plan: (no plan specified) The path to the deployment plan document on the Administration Server. [More Info...](#)

Staging Mode: (not specified) Specifies whether a deployment's files are copied from a source on the Administration Server's staging area during application preparation. [More Info...](#)

Plan Staging Mode: (not specified) Specifies whether an application's deployment plan is copied from a source on the Administration Server's staging area during application preparation. [More Info...](#)

Security Model: DDOOnly The security model that is used to secure a deployed module. [More Info...](#)

Deployment Order: 100 An integer value that indicates when this unit is deployed, relative to other deployable units during startup. [More Info...](#)

Deployment Principal Name: A string value that indicates the principal that should be used when deploying the file or arc and shutdown. This principal will be used to set the current subject when calling out into interfaces such as ApplicationLifecycleListener. If no principal name is specified, then the arc will be used. [More Info...](#)

Save

Modules and Components Showing 1 to 1 of 1

Name
GWEJB (12.2.0.0.0)
- EDB - PCMainProcEJB - PCSnvRouterEJB - GWEJB

38. Click 'Save' button. The message 'Settings updated successfully' is displayed.

The screenshot shows the Oracle WebLogic Server Administration Console. On the left, the 'Change Center' pane displays a message: 'Settings updated successfully.' Below this, the 'Domain Structure' pane shows a tree view with 'PM1221TR2' expanded, showing 'Domain Partitions', 'Environments', 'Deployments', 'Services', 'Security Realms', 'Interoperability', and 'Diagnostics'. The 'How do I...' pane lists tasks like 'Start and stop a deployed enterprise application', 'Configure an enterprise application', 'Create a deployment plan', 'Target an enterprise application to a server instance', and 'Test the modules in an enterprise application'. The 'System Status' pane shows 'Health of Running Servers' with a bar chart indicating 'Failed (0)', 'Critical (0)', 'Overloaded (0)', 'Warning (0)', and 'OK (2)'. The main content area is titled 'Settings for GWEJB (12.2.0.0.0)' and has tabs for 'Overview', 'Deployment Plan', 'Configuration', 'Security', 'Targets', 'Control', 'Testing', 'Monitoring', and 'Notes'. The 'Overview' tab is active, showing a 'Save' button and a message: 'Use this page to view the general configuration of an enterprise application, such as its name, the physical path to the application files, the associated deployment plan, and so on. The table at the end of the page lists the modules (such as contained in the enterprise application. Click on the name of the module to view and update its configuration.' Below this is a table with configuration details for GWEJB. At the bottom, the 'Modules and Components' section lists the components of GWEJB: GWEJB (12.2.0.0.0), EJBs, PCMainProcEJB, and PCSrvRouterEJB.

Name	Value	Description
Name	GWEJB	The name of this enterprise application. More Info...
Scope	Global	Specifies if this enterprise application is accessible within the domain, template. More Info...
Archive Version	12.2.0.0.0	The archive version, specified from the manifest or overridden during deployment. More Info...
Path	/scratch/app/fmw122/Oracle/user_projects/domains/PM1221TR2/servers/Admin_PM12TR2/upload/GWEJB.ear/app/GWEJB.ear	The path to the source of the deployable unit on the Administration Server. More Info...
Deployment Plan	(no plan specified)	The path to the deployment plan document on the Administration Server. More Info...
Staging Mode	(not specified)	Specifies whether a deployment's files are copied from a source on the Administration Server's staging area during application preparation. More Info...
Plan Staging Mode	(not specified)	Specifies whether an application's deployment plan is copied from a source on the Administration Server's staging area during application preparation. More Info...
Security Model	DOOnly	The security model that is used to secure a deployed module. More Info...
Deployment Order	100	An integer value that indicates when this unit is deployed, relative to other units during startup. More Info...
Deployment Principal Name		A string value that indicates the principal that should be used when deploying and shutting down. This principal will be used to set the current subject when calling interfaces such as ApplicationLifecycleListener. If no principal name is specified, the current subject will be used. More Info...

Modules and Components

Name
GWEJB (12.2.0.0.0)
EJBs
PCMainProcEJB
PCSRvRouterEJB

39. Click 'Activate Changes' button on the left pane. The message 'All the changes have been activated. No restarts are necessary' is displayed.

The screen is given below:

The screenshot shows the Oracle WebLogic Server Administration Console. On the left, the 'Change Center' pane displays a message: 'All changes have been activated. No restarts are necessary.' Below this, the 'Domain Structure' pane shows a tree view with 'PM1221TR2' expanded, showing 'Domain Partitions', 'Environments', 'Deployments', 'Services', 'Security Realms', 'Interoperability', and 'Diagnostics'. The 'How do I...' pane lists tasks like 'Start and stop a deployed enterprise application', 'Configure an enterprise application', 'Create a deployment plan', 'Target an enterprise application to a server instance', and 'Test the modules in an enterprise application'. The 'System Status' pane shows 'Health of Running Servers' with a bar chart indicating 'Failed (0)', 'Critical (0)', 'Overloaded (0)', 'Warning (0)', and 'OK (2)'. The main content area is titled 'Settings for GWEJB (12.2.0.0.0)' and has tabs for 'Overview', 'Deployment Plan', 'Configuration', 'Security', 'Targets', 'Control', 'Testing', 'Monitoring', and 'Notes'. The 'Overview' tab is active, showing a 'Save' button and a message: 'Click the Lock & Edit button in the Change Center to modify the settings on this page.' Below this is a table with configuration details for GWEJB. At the bottom, the 'Modules and Components' section lists the components of GWEJB: GWEJB (12.2.0.0.0) and its sub-components: EJBs, PCMainProcEJB, and PCSrvRouterEJB.

Name	Value	Description
Name	GWEJB	The name of this enterprise application. More Info...
Scope	Global	Specifies if this enterprise application is accessible within the domain, a part template. More Info...
Archive Version	12.2.0.0.0	The archive version, specified from the manifest or overridden during deployment. More Info...
Path	/scratch/app/fmw122/Oracle/user_projects/domains/PM1221TR2/servers/Admin_PM12TR2/upload/GWEJB.ear/app/GWEJB.ear	The path to the source of the deployable unit on the Administration Server. More Info...
Deployment Plan	(no plan specified)	The path to the deployment plan document on the Administration Server. More Info...
Staging Mode	(not specified)	Specifies whether a deployment's files are copied from a source on the Administration Server's staging area during application preparation. More Info...
Plan Staging Mode	(not specified)	Specifies whether an application's deployment plan is copied from a source on the Administration Server's staging area during application preparation. More Info...
Security Model	DOOnly	The security model that is used to secure a deployed module. More Info...
Deployment Order	100	An integer value that indicates when this unit is deployed, relative to other units during startup. More Info...
Deployment Principal Name		A string value that indicates the principal that should be used when deploying and shutting down. This principal will be used to set the current subject when calling interfaces such as ApplicationLifecycleListener. If no principal name is specified, the current subject will be used. More Info...

Modules and Components

Name
GWEJB (12.2.0.0.0)
EJBs
PCMainProcEJB
PCSRvRouterEJB

Click 'Deployment' on the left pane. Switch to Control tab. The following screen is displayed.

ORACLE WebLogic Server Administration Console 12c

Home Log Out Preferences Record Help

Welcome, infra Connected to

Home > Summary of Deployments > GWEJB(12.2.0.0.0) > Summary of Deployments

Summary of Deployments

Configuration Control Monitoring

This page displays the list of Java EE applications and standalone application modules installed to this domain.

You can start and stop applications and modules from the domain by selecting the checkbox next to the application name and then using the controls on this page.

Customize this table

Deployments

Start Stop

Showing 1 to 8 of 8 Prev

	State	Health	Type	Targets	Scope	Domain Partition
☒ Servicing all requests	Active	OK	Resource Adapter	Admin_PMTIR2	Global	
☒ Servicing only administration requests	Active	OK	Resource Adapter	Admin_PMTIR2	Global	
☐ DMS Application (12.2.1.0.0)	Active	OK	Web Application	Admin_PMTIR2	Global	
☐ em	Active	OK	Enterprise Application	Admin_PMTIR2	Global	
☐ FCUBSApp (12.2.0.0.0)	Active	Warning	Enterprise Application	payments_server1	Global	
☒ GWEJB (12.2.0.0.0)	Prepared	OK	Enterprise Application	payments_server1	Global	
☐ opss-rest	Active	OK	Web Application	Admin_PMTIR2	Global	
☐ PaymentStubs	Active	OK	EJB	payments_server1	Global	
☐ state-management-provider-memory-rar	Active	OK	Resource Adapter	Admin_PMTIR2	Global	

Start Stop

Showing 1 to 8 of 8 Prev

WebLogic Server Version: 12.2.1.0.0
Copyright (c) 1996,2015, Oracle and/or its affiliates. All rights reserved.
Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

40. Click 'Start' drop-down button and select 'Servicing all requests'.

41. The following screen is displayed.

ORACLE WebLogic Server Administration Console 12c

Home Log Out Preferences Record Help

Welcome, infra Connected to

Home > Summary of Deployments > GWEJB(12.2.0.0.0) > Summary of Deployments

Start Application Assistant

Yes No

Start Deployments

You have selected the following deployments to be started. Click 'Yes' to continue, or 'No' to cancel.

- GWEJB(12.2.0.0.0)

Yes No

WebLogic Server Version: 12.2.1.0.0
Copyright (c) 1996,2015, Oracle and/or its affiliates. All rights reserved.
Oracle is a registered trademark of Oracle Corporation and/or its affiliates. Other names may be trademarks of their respective owners.

42. Click 'Yes'. The following screen is displayed.

The screenshot shows the Oracle WebLogic Server Administration Console. The main content area is titled 'Summary of Deployments' and displays a table of deployed applications and modules. The table has columns for Name, State, Health, Type, Targets, Scope, and Domain Partitions. The left sidebar shows the Domain Structure and System Status. The top navigation bar includes Home, Log Out, Preferences, Record, and Help.

Name	State	Health	Type	Targets	Scope	Domain Partitions
coherence-transaction-war	Active	OK	Resource Adapter	Admin_PMTSR2	Global	
OMS Application (12.2.1.0.0)	Active	OK	Web Application	Admin_PMTSR2	Global	
em	Active	OK	Enterprise Application	Admin_PMTSR2	Global	
FCMSSApp (12.2.0.0.0)	Active	Warning	Enterprise Application	payments_server1	Global	
GWSS (12.2.0.0.0)	Active	OK	Enterprise Application	payments_server1	Global	
opss-rest	Active	OK	Web Application	Admin_PMTSR2	Global	
PaymentStub	Active	OK	DB	payments_server1	Global	
state-management-provider-memory-war	Active	OK	Resource Adapter	Admin_PMTSR2	Global	

This completes the deployment process.

1. Repeat the same steps from 1.3.3 for deploying GWWS(gateway webservices),Gateway MDB & Gateway HTTP servlet



Deploying Oracle Banking Treasury Management on WebLogic

[May] [2023]

Version 14.7.1.0.0

Oracle Financial Services Software Limited

Oracle Park

Off Western Express Highway

Goregaon (East)

Mumbai, Maharashtra 400 063

India

Worldwide Inquiries:

Phone: +91 22 6718 3000

Fax: +91 22 6718 3001

<https://www.oracle.com/industries/financial-services/index.html>

Copyright © [2020], [2022], Oracle and/or its affiliates. All rights reserved.

Oracle and Java are registered trademarks of Oracle and/or its affiliates. Other names may be trademarks of their respective owners.

U.S. GOVERNMENT END USERS: Oracle programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, delivered to U.S. Government end users are "commercial computer software" pursuant to the applicable Federal Acquisition Regulation and agency-specific supplemental regulations. As such, use, duplication, disclosure, modification, and adaptation of the programs, including any operating system, integrated software, any programs installed on the hardware, and/or documentation, shall be subject to license terms and license restrictions applicable to the programs. No other rights are granted to the U.S. Government.

This software or hardware is developed for general use in a variety of information management applications. It is not developed or intended for use in any inherently dangerous applications, including applications that may create a risk of personal injury. If you use this software or hardware in dangerous applications, then you shall be responsible to take all appropriate failsafe, backup, redundancy, and other measures to ensure its safe use. Oracle Corporation and its affiliates disclaim any liability for any damages caused by use of this software or hardware in dangerous applications.

This software and related documentation are provided under a license agreement containing restrictions on use and disclosure and are protected by intellectual property laws. Except as expressly permitted in your license agreement or allowed by law, you may not use, copy, reproduce, translate, broadcast, modify, license, transmit, distribute, exhibit, perform, publish or display any part, in any form, or by any means. Reverse engineering, disassembly, or decompilation of this software, unless required by law for interoperability, is prohibited.

The information contained herein is subject to change without notice and is not warranted to be error-free. If you find any errors, please report them to us in writing.

This software or hardware and documentation may provide access to or information on content, products and services from third parties. Oracle Corporation and its affiliates are not responsible for and expressly disclaim all warranties of any kind with respect to third-party content, products, and services. Oracle Corporation and its affiliates will not be responsible for any loss, costs, or damages incurred due to your access to or use of third-party content, products, or services.