CLPKS_PAYMENT Package
**Extensible Hook Details**
Release 14.7.4.0.0
**Part No.F98075-01**

June 2024

**ORACLE**®

Oracle Financial Services Software Limited

Oracle Park

Off western Express Highway
Goregaon(East)
Mumbai,Maharashtra 400 063
India

Worldwide Inquiries:
Phone: +91 22 6718 3000
Fax:+91 22 6718 3001
www.oracle.com/financialservices/

# Contents

| Parameter | Description |
|---|---|
| Function | FN_AUTHORIZE |
| No of Parameters | 3 |
| Function Call Id | 1 |
| Cluster/Custom Function Name | FN_POST_AUTHORIZE |
| Additional parameters | l_fn_call_id,<br>l_tb_cluster_data |
| Sent to Extensible layer | None |
| Received from Extensible layer | None |
| Hook Description | Post Hook is placed in clpks_payment.Fn_Authorize(),<br>to check the normal Principal payment in between due date and<br>grace due date during MLIQ. |
| Description | Post Hook is placed in clpks_payment.Fn_Authorize(),<br>to check the normal Principal payment in between due date and<br>grace due date during MLIQ.<br>All parameters received by kernel function are passed to the cluster hook.<br>Additional parameters passed to cluster hook are mentioned in field "Additional Parameters".<br>The variables mentioned in "Sent to Extensible Layer" field are passed to cluster hook.<br>The variables mentioned in "Received from Extensible Layer" field are reassigned to kernel. |
| Bug No | 19217457 |

| Parameter | Description |
|---|---|
| Function | FN_AUTHORIZE |
| No of Parameters | 3 |
| Function Call Id | 1 |
| Cluster/Custom Function Name | FN_PRE_UDE_BATCH_HDBC |
| Additional parameters | l_fn_call_id,<br>l_tb_cluster_data |
| Sent to Extensible layer | None |
| Received from Extensible layer | None |
| Hook Description | Pre Hook is placed in clpks_payment.Fn_Authorize(),<br>to have Stamp Duty Component charges at end of Month and MLIQ, ALIQ<br>stages based on Monthly, Quarterly, Half yearly, Yearly basis with<br>respect to Value date and Maturity date of accounts. |

ORACLE®

| Description | Pre Hook is placed in clpks_payment.Fn_Authorize(), to have Stamp Duty Component charges at end of Month and MLIQ, ALIQ stages based on Monthly, Quarterly, Half yearly, Yearly basis with respect to Value date and Maturity date of accounts. All parameters received by kernel function are passed to the cluster hook. Additional parameters passed to cluster hook are mentioned in field "Additional Parameters". The variables mentioned in "Sent to Extensible Layer" field are passed to cluster hook. The variables mentioned in "Received from Extensible Layer" field are reassigned to kernel. |
|---|---|
| Bug No | 24702528 |

| Parameter | Description |
|---|---|
| Function | FN_AUTHORIZE |
| No of Parameters | 3 |
| Function Call Id | 1 |
| Cluster/Custom Function Name | FN_POST_UDE_BATCH_HDBC |
| Additional parameters | l_fn_call_id, l_tb_cluster_data |
| Sent to Extensible layer | None |
| Received from Extensible layer | None |
| Hook Description | Post Hook is placed in clpks_payment.Fn_Authorize(), to have Stamp Duty Component charges at end of Month and MLIQ, ALIQ stages based on Monthly, Quarterly, Half yearly, Yearly basis with respect to Value date and Maturity date of accounts. |
| Description | Post Hook is placed in clpks_payment.Fn_Authorize(), to have Stamp Duty Component charges at end of Month and MLIQ, ALIQ stages based on Monthly, Quarterly, Half yearly, Yearly basis with respect to Value date and Maturity date of accounts. All parameters received by kernel function are passed to the cluster hook. Additional parameters passed to cluster hook are mentioned in field "Additional Parameters". The variables mentioned in "Sent to Extensible Layer" field are passed to cluster hook. The variables mentioned in "Received from Extensible Layer" field are reassigned to kernel. |
| Bug No | 24702528 |

| Parameter | Description |
|---|---|
| Function | FN_DELETE_PAYMENT_RECORDS |
| No of Parameters | 5 |
| Function Call Id | 1 |
| Cluster/Custom Function Name | FN_DELETE_PAYMENT_RECORDS |
| Additional parameters | l_fn_call_id, l_tb_cluster_data |
| Sent to Extensible layer | None |
| Received from Extensible layer | None |

| Hook Description | Hook is placed in clpks_payment.Fn_Delete_Payment_Records(), to capture the provision amount for interest and commitment fees at the time of account opening and track the utilization of the amount provisioned. |
|---|---|
| Description | Hook is placed in clpks_payment.Fn_Delete_Payment_Records(), to capture the provision amount for interest and commitment fees at the time of account opening and track the utilization of the amount provisioned. All parameters received by kernel function are passed to the cluster hook. Additional parameters passed to cluster hook are mentioned in field "Additional Parameters". The variables mentioned in "Sent to Extensible Layer" field are passed to cluster hook. The variables mentioned in "Received from Extensible Layer" field are reassigned to kernel. |
| Bug No | 23652533 |

| Parameter | Description |
|---|---|
| Function | FN_DO_ACCRUAL |
| No of Parameters | 9 |
| Function Call Id | 1 |
| Cluster/Custom Function Name | FN_POST_DO_ACCRUAL |
| Additional parameters | l_fn_call_id, l_tb_cluster_data |
| Sent to Extensible layer | None |
| Received from Extensible layer | None |
| Hook Description | Post Hook is placed in clpks_payment.Fn_Do_Accrual(), to handle the restructuring functionality and to skip RACR processing for a special interest component. |
| Description | Post Hook is placed in clpks_payment.Fn_Do_Accrual(), to handle the restructuring functionality and to skip RACR processing for a special interest component. All parameters received by kernel function are passed to the cluster hook. Additional parameters passed to cluster hook are mentioned in field "Additional Parameters". The variables mentioned in "Sent to Extensible Layer" field are passed to cluster hook. The variables mentioned in "Received from Extensible Layer" field are reassigned to kernel. |
| Bug No | 24702528 |

| Parameter | Description |
|---|---|
| Function | FN_DO_ACCRUAL |
| No of Parameters | 9 |
| Function Call Id | 1 |
| Cluster/Custom Function Name | FN_PRE_DO_ACCRUAL |
| Additional parameters | l_fn_call_id, l_tb_cluster_data |
| Sent to Extensible layer | None |
| Received from Extensible layer | None |

| Hook Description | Pre Hook is placed in clpks_payment.Fn_Do_Accrual(), to handle the restructuring functionality and to skip RACR processing for a special interest component. |
|---|---|
| Description | Pre Hook is placed in clpks_payment.Fn_Do_Accrual(), to handle the restructuring functionality and to skip RACR processing for a special interest component. All parameters received by kernel function are passed to the cluster hook. Additional parameters passed to cluster hook are mentioned in field "Additional Parameters". The variables mentioned in "Sent to Extensible Layer" field are passed to cluster hook. The variables mentioned in "Received from Extensible Layer" field are reassigned to kernel. |
| Bug No | 24702528 |

| Parameter | Description |
|---|---|
| Function | FN_DO_MLIQ_FOR_AN_ACC |
| No of Parameters | 4 |
| Function Call Id | 1 |
| Cluster/Custom Function Name | FN_POST_MLIQ_FOR_AN_ACC |
| Additional parameters | l_fn_call_id, l_tb_cluster_data |
| Sent to Extensible layer | None |
| Received from Extensible layer | None |
| Hook Description | Post Hook is placed in clpks_payment.Fn_Do_Mliq_For_An_Acc() to avoid the prepaid amount settlement after save of a CL prepayment. |
| Description | Post Hook is placed in clpks_payment.Fn_Do_Mliq_For_An_Acc() to avoid the prepaid amount settlement after save of a CL prepayment. All parameters received by kernel function are passed to the cluster hook. Additional parameters passed to cluster hook are mentioned in field "Additional Parameters". The variables mentioned in "Sent to Extensible Layer" field are passed to cluster hook. The variables mentioned in "Received from Extensible Layer" field are reassigned to kernel. |
| Bug No | 24702528 |

| Parameter | Description |
|---|---|
| Function | FN_DO_MLIQ_FOR_AN_ACC |
| No of Parameters | 4 |
| Function Call Id | 1 |
| Cluster/Custom Function Name | FN_PRE_MLIQ_FOR_AN_ACC |
| Additional parameters | l_fn_call_id, l_tb_cluster_data |
| Sent to Extensible layer | None |
| Received from Extensible layer | None |

ORACLE®

| Hook Description | Pre Hook is placed in clpks_payment.Fn_Do_Mliq_For_An_Acc(), to avoid the prepaid amount settlement after save of a CL prepayment. |
|---|---|
| Description | Pre Hook is placed in clpks_payment.Fn_Do_Mliq_For_An_Acc(), to avoid the prepaid amount settlement after save of a CL prepayment.  All parameters received by kernel function are passed to the cluster hook.    Additional parameters passed to cluster hook are mentioned in field "Additional Parameters".    The variables mentioned in "Sent to Extensible Layer"  field are passed to cluster hook.    The variables mentioned in "Received from Extensible Layer"  field are reassigned to kernel. |
| Bug No | 24702528 |

| Parameter | Description |
|---|---|
| Function | FN_DO_MLIQ_FOR_AN_ACC |
| No of Parameters | 4 |
| Function Call Id | 1 |
| Cluster/Custom Function Name | FN_PRE_DO_MLIQ_FOR_AN_ACC |
| Additional parameters | l_fn_call_id, l_tb_cluster_data |
| Sent to Extensible layer | None |
| Received from Extensible layer | None |
| Hook Description | Pre Hook is placed in clpks_payment.Fn_Do_Mliq_For_An_Acc(), to call custom pre handler for deletion of reversal of STSH entries similar to accrual entries for Late fifth batch payments. |
| Description | Pre Hook is placed in clpks_payment.Fn_Do_Mliq_For_An_Acc(), to call custom pre handler for deletion of reversal of STSH entries similar to accrual entries for Late fifth batch payments.  All parameters received by kernel function are passed to the cluster hook.    Additional parameters passed to cluster hook are mentioned in field "Additional Parameters".    The variables mentioned in "Sent to Extensible Layer"  field are passed to cluster hook.    The variables mentioned in "Received from Extensible Layer"  field are reassigned to kernel. |
| Bug No | 24702528 |

| Parameter | Description |
|---|---|
| Function | FN_DO_MLIQ_FOR_AN_ACC |
| No of Parameters | 4 |
| Function Call Id | 1 |
| Cluster/Custom Function Name | FN_PRE_UTILIZATION |
| Additional parameters | l_fn_call_id,  l_tb_cluster_data |
| Sent to Extensible layer | None |
| Received from Extensible layer | None |

ORACLE®

| Hook Description | Pre Hook is placed in clpks_payment.Fn_Do_Mliq_For_An_Acc(), to avoid the decrease of utilization in the facility on doing the payment. |
|---|---|
| Description | Pre Hook is placed in clpks_payment.Fn_Do_Mliq_For_An_Acc(), to avoid the decrease of utilization in the facility on doing the payment. All parameters received by kernel function are passed to the cluster hook. Additional parameters passed to cluster hook are mentioned in field "Additional Parameters". The variables mentioned in "Sent to Extensible Layer"  field are passed to cluster hook. The variables mentioned in "Received from Extensible Layer"  field are reassigned to kernel. |
| Bug No | 19929865 |
|  |  |

| Parameter | Description |
|---|---|
| Function | FN_DO_MLIQ_FOR_AN_ACC |
| No of Parameters | 4 |
| Function Call Id | 1 |
| Cluster/Custom Function Name | FN_POST_UTILIZATION |
| Additional parameters | l_fn_call_id, l_tb_cluster_data |
| Sent to Extensible layer | None |
| Received from Extensible layer | None |
| Hook Description | Post Hook is placed in clpks_payment.Fn_Do_Mliq_For_An_Acc(), to avoid the decrease of utilization in the facility on doing the payment. |
| Description | Post Hook is placed in clpks_payment.Fn_Do_Mliq_For_An_Acc(), to avoid the decrease of utilization in the facilitly on doing the payment. All parameters received by kernel function are passed to the cluster hook. Additional parameters passed to cluster hook are mentioned in field "Additional Parameters". The variables mentioned in "Sent to Extensible Layer"  field are passed to cluster hook. The variables mentioned in "Received from Extensible Layer"  field are reassigned to kernel. |
| Bug No | 19929865 |

| Parameter | Description |
|---|---|
| Function | FN_DO_MLIQ_FOR_AN_ACC |
| No of Parameters | 4 |
| Function Call Id | 2 |
| Cluster/Custom Function Name | FN_POST_DO_MLIQ_FOR_AN_ACC |
| Additional parameters | pkg_tb_amount_recd_his, pkg_tb_backup_amt_recd_his, l_fn_call_id, l_tb_cluster_data |
| Sent to Extensible layer | None |
| Received from Extensible layer | None |

ORACLE®

| Hook Description | Post Hook is placed in clpks_payment.Fn_Do_Mliq_For_An_Acc(), to allow the system to post ADCH for EXCESS_PFT even when the loan is not fully liquidated. |
|---|---|
| Description | Post Hook is placed in clpks_payment.Fn_Do_Mliq_For_An_Acc(), to allow the system to post ADCH for EXCESS_PFT even when the loan is not fully liquidated. All parameters received by kernel function are passed to the cluster hook. Additional parameters passed to cluster hook are mentioned in field "Additional Parameters". The variables mentioned in "Sent to Extensible Layer" field are passed to cluster hook. The variables mentioned in "Received from Extensible Layer" field are reassigned to kernel. |
| Bug No | 24702528 |

| Parameter | Description |
|---|---|
| Function | FN_DO_MLIQ_FOR_AN_ACC |
| No of Parameters | 4 |
| Function Call Id | 2 |
| Cluster/Custom Function Name | FN_ADJUST_EVENT_ENTRIES |
| Additional parameters | l_Rec_Event_Entries, l_Tot_Amount_Paid, Idxcomp, l_fn_call_id, l_tb_cluster_data |
| Sent to Extensible layer | None |
| Received from Extensible layer | None |
| Hook Description | Hook is placed in clpks_payment.Fn_Do_Mliq_For_An_Acc(), to capture the provision amount for interest and commitment fees at the time of account opening and track the utilization of the amount provisioned. |
| Description | Hook is placed in clpks_payment.Fn_Do_Mliq_For_An_Acc(), to capture the provision amount for interest and commitment fees at the time of account opening and track the utilization of the amount provisioned. All parameters received by kernel function are passed to the cluster hook. Additional parameters passed to cluster hook are mentioned in field "Additional Parameters". The variables mentioned in "Sent to Extensible Layer" field are passed to cluster hook. The variables mentioned in "Received from Extensible Layer" field are reassigned to kernel. |
| Bug No | 21223530 |

| Parameter | Description |
|---|---|
| Function | FN_DO_MLIQ_FOR_AN_ACC |
| No of Parameters | 4 |
| Function Call Id | 2 |

ORACLE®

| Cluster/Custom Function Name | FN_PRE_DO_MLIQ_FOR_AN_ACC |
|---|---|
| Additional parameters | l_fn_call_id,<br> l_tb_cluster_data |
| Sent to Extensible layer | None |
| Received from Extensible layer | None |
| Hook Description | Pre Hook is placed in clpks_payment.Fn_Do_Mliq_For_An_Acc(),<br>to allow the system to post ADCH for EXCESS_PFT even when the<br>loan is not fully liquidated. |
| Description | Pre Hook is placed in clpks_payment.Fn_Do_Mliq_For_An_Acc(),<br>to allow the system to post ADCH for EXCESS_PFT even when the<br>loan is not fully liquidated.<br>  All parameters received by kernel function are passed to the cluster hook.<br>    Additional parameters passed to cluster hook are mentioned in field "Additional Parameters".<br>    The variables mentioned in "Sent to Extensible Layer"  field are passed to cluster hook.<br>    The variables mentioned in "Received from Extensible Layer"  field are reassigned to kernel. |
| Bug No | 24702528 |

| Parameter | Description |
|---|---|
| Function | FN_DO_MLIQ_FOR_AN_ACC |
| No of Parameters | 4 |
| Function Call Id | 4 |
| Cluster/Custom Function Name | FN_DO_MLIQ_FOR_AN_ACC |
| Additional parameters | l_fn_call_id,<br>l_tb_cluster_data, |
| Sent to Extensible layer | |
| Received from Extensible layer | |
| Hook Description | The online call to process YACR from CLPKS_PAYMENT, CLPKS_MROLL, PKG_CLDADCHG AND PKG_CLDMDSBR package<br> has to be skiped as the client only want the processing of YACR should happen at the EOD |
| Description | The online call to process YACR from CLPKS_PAYMENT, CLPKS_MROLL, PKG_CLDADCHG AND PKG_CLDMDSBR package<br> has to be skiped as the client only want the processing of YACR should happen at the EOD<br>  All parameters received by kernel function are passed to the cluster hook.<br>    Additional parameters passed to cluster hook are mentioned in field "Additional Parameters".<br>    The variables mentioned in "Sent to Extensible Layer"  field are passed to cluster hook.<br>    The variables mentioned in "Received from Extensible Layer"  field are reassigned to kernel. |
| Bug No | 31544577 |

| Parameter | Description |
|---|---|
| Function | FN_DO_MLIQ_FOR_AN_ACC |
| No of Parameters | 0 |
| Function Call Id | 1 |

ORACLE®

| Cluster/Custom Function Name | FN_DO_MLIQ_FOR_AN_ACC |
|---|---|
| Additional parameters | |
| Sent to Extensible layer | l_tb_cluster_data('idxcomp') :=   idxcomp; |
| Received from Extensible layer | |
| Hook Description | Hook has been provided in function Fn_Do_Mliq_For_An_Acc in package clpks_payment. |
| Description | Hook has been provided in function Fn_Do_Mliq_For_An_Acc in package clpks_payment.<br>  All parameters received by kernel function are passed to the cluster hook.<br>    Additional parameters passed to cluster hook are mentioned in field "Additional Parameters".<br>    The variables mentioned in "Sent to Extensible Layer"  field are passed to cluster hook.<br>    The variables mentioned in "Received from Extensible Layer"  field are reassigned to kernel. |
| Bug No | 28118145 |

| Parameter | Description |
|---|---|
| Function | FN_GEN_ALLOCATE |
| No of Parameters | 4 |
| Function Call Id | 1 |
| Cluster/Custom Function Name | FN_GEN_POST_ALLOCATE |
| Additional parameters | l_fn_call_id,<br>l_tb_cluster_data |
| Sent to Extensible layer | None |
| Received from Extensible layer | None |
| Hook Description | Hook is placed in clpks_payment.Fn_Gen_Allocate(),<br>to capture the provision amount for interest and commitment fees<br>at the time of account opening and track the utilization<br>of the amount provisioned. |
| Description | Hook is placed in clpks_payment.Fn_Gen_Allocate(),<br>to capture the provision amount for interest and commitment fees<br>at the time of account opening and track the utilization<br>of the amount provisioned.<br>  All parameters received by kernel function are passed to the cluster hook.<br>    Additional parameters passed to cluster hook are mentioned in field "Additional Parameters".<br>    The variables mentioned in "Sent to Extensible Layer"  field are passed to cluster hook.<br>    The variables mentioned in "Received from Extensible Layer"  field are reassigned to kernel. |
| Bug No | 19619243 |

| Parameter | Description |
|---|---|
| Function | FN_GEN_ALLOCATE |
| No of Parameters | 0 |
| Function Call Id | 4 |
| Cluster/Custom Function Name | FN_GEN_ALLOCATE |
| Additional parameters | |

| Sent to Extensible layer | l_tb_cluster_data('component_name') := l_tb_schedules(i).component_name; |
| --- | --- |
| | l_tb_cluster_data('accrued_amount') := l_tb_schedules(i).accrued_amount; |
| | l_tb_cluster_data('amount_waived') := l_tb_schedules(i).amount_waived; |
| | l_tb_cluster_data('amount_due') := l_tb_schedules(i).amount_due; |
| | l_tb_cluster_data('amount_settled') := l_tb_schedules(i).amount_settled; |
| | l_tb_cluster_data('schedule_st_date') := l_tb_schedules(i).schedule_st_date; |
| | l_tb_cluster_data('schedule_due_date') := l_tb_schedules(i).schedule_due_date; |
| Received from Extensible l ayer | |
| Hook Description | Hook has been provided in function fn_gen_allocate in package clpks_payment. |
| Description | Hook has been provided in function fn_gen_allocate in package clpks_payment.<br>  All parameters received by kernel function are passed to the cluster hook.<br>    Additional parameters passed to cluster hook are mentioned in field "Additional Parameters".<br>    The variables mentioned in "Sent to Extensible Layer"  field are passed to cluster hook.<br>    The variables mentioned in "Received from Extensible Layer"  field are reassigned to kernel. |
| Bug No | 28118145 |

| Parameter | Description |
| --- | --- |
| Function | FN_GEN_AUTHORIZE |
| No of Parameters | 3 |
| Function Call Id | 1 |
| Cluster/Custom Function  Name | FN_POST_GEN_AUTHORIZE |
| Additional parameters | l_fn_call_id,<br>l_tb_cluster_data |
| Sent to Extensible layer | None |
| Received from Extensible l ayer | None |
| Hook Description | Post Hook is placed in clpks_payment.Fn_Gen_Authorize(),<br>to check the normal Principal payment in between due date and<br>grace due date during MLIQ. |
| Description | Post Hook is placed in clpks_payment.Fn_Gen_Authorize(),<br>to check the normal Principal payment in between due date and<br>grace due date during MLIQ.<br>  All parameters received by kernel function are passed to the cluster hook.<br>    Additional parameters passed to cluster hook are mentioned in field "Additional Parameters".<br>    The variables mentioned in "Sent to Extensible Layer"  field are passed to cluster hook.<br>    The variables mentioned in "Received from Extensible Layer"  field are reassigned to kernel. |
| Bug No | 19217457 |

| Parameter | Description |
| --- | --- |
| Function | FN_GEN_DELETE |
| No of Parameters | 7 |
| Function Call Id | 1 |

ORACLE®

| | |
|---|---|
| Cluster/Custom Function Name | FN_GEN_DELETE |
| Additional parameters | l_fn_call_id<br>l_tb_cluster_data |
| Sent to Extensible layer | |
| Received from Extensible layer | |
| Hook Description | The online call to process YACR from CLPKS_PAYMENT, CLPKS_MROLL, PKG_CLDADCHG AND PKG_CLDMDSBR package has to be skiped as the client only want the processing of YACR should happen at the EOD. |
| Description | The online call to process YACR from CLPKS_PAYMENT, CLPKS_MROLL, PKG_CLDADCHG AND PKG_CLDMDSBR package has to be skiped as the client only want the processing of YACR should happen at the EOD.<br>  All parameters received by kernel function are passed to the cluster hook.<br>    Additional parameters passed to cluster hook are mentioned in field "Additional Parameters".<br>    The variables mentioned in "Sent to Extensible Layer"  field are passed to cluster hook.<br>    The variables mentioned in "Received from Extensible Layer"  field are reassigned to kernel. |
| Bug No | 31544577 |

| Parameter | Description |
|---|---|
| Function | FN_GEN_DUMP |
| No of Parameters | 3 |
| Function Call Id | 1 |
| Cluster/Custom Function Name | FN_POST_GEN_DUMP |
| Additional parameters | pkg_tb_accdiarystatus,<br>pkg_tb_brndiarystatus,<br>l_fn_call_id,<br>l_tb_cluster_data |
| Sent to Extensible layer | None |
| Received from Extensible layer | None |
| Hook Description | Post Hook is placed in clpks_payment.Fn_Gen_Dump(),<br>to deactivate the tracking of block amount for the liquidated<br>account during batch LIQD(ALIQ). |
| Description | Post Hook is placed in clpks_payment.Fn_Gen_Dump(),<br>to deactivate the tracking of block amount for the liquidated<br>account during batch LIQD(ALIQ).<br>  All parameters received by kernel function are passed to the cluster hook.<br>    Additional parameters passed to cluster hook are mentioned in field "Additional Parameters".<br>    The variables mentioned in "Sent to Extensible Layer"  field are passed to cluster hook.<br>    The variables mentioned in "Received from Extensible Layer"  field are reassigned to kernel. |
| Bug No | 19235740 |
| | |

| Parameter | Description |
|---|---|
| Function | FN_GEN_DUMP |
| No of Parameters | 3 |
| Function Call Id | 1 |

ORACLE®

| Cluster/Custom Function Name | FN_GEN_DUMP |
|---|---|
| Additional parameters | l_fn_call_id,<br>l_tb_cluster_data |
| Sent to Extensible layer | |
| Received from Extensible layer | |
| Hook Description | The online call to process YACR from CLPKS_PAYMENT, CLPKS_MROLL, PKG_CLDADCHG AND PKG_CLDMDSBR package has to be skiped as the client only want the processing of YACR should happen at the EOD. |
| Description | The online call to process YACR from CLPKS_PAYMENT, CLPKS_MROLL, PKG_CLDADCHG AND PKG_CLDMDSBR package has to be skiped as the client only want the processing of YACR should happen at the EOD.<br>  All parameters received by kernel function are passed to the cluster hook.<br>    Additional parameters passed to cluster hook are mentioned in field "Additional Parameters".<br>    The variables mentioned in "Sent to Extensible Layer"  field are passed to cluster hook.<br>    The variables mentioned in "Received from Extensible Layer"  field are reassigned to kernel. |
| Bug No | 31544577 |

| Parameter | Description |
|---|---|
| Function | FN_GEN_POPULATE_DUE |
| No of Parameters | 3 |
| Function Call Id | 1 |
| Cluster/Custom Function Name | FN_GEN_POST_POPULATE_DUE |
| Additional parameters | l_fn_call_id,<br>l_tb_cluster_data |
| Sent to Extensible layer | None |
| Received from Extensible layer | None |
| Hook Description | Hook is placed in clpks_payment.Fn_Gen_Populate_Due(),<br>to capture the provision amount for interest and commitment fees<br>at the time of account opening and track the utilization<br>of the amount provisioned. |
| Description | Hook is placed in clpks_payment.Fn_Gen_Populate_Due(),<br>to capture the provision amount for interest and commitment fees<br>at the time of account opening and track the utilization<br>of the amount provisioned.<br>  All parameters received by kernel function are passed to the cluster hook.<br>    Additional parameters passed to cluster hook are mentioned in field "Additional Parameters".<br>    The variables mentioned in "Sent to Extensible Layer"  field are passed to cluster hook.<br>    The variables mentioned in "Received from Extensible Layer"  field are reassigned to kernel. |
| Bug No | 19619243 |

| Parameter | Description |
|---|---|
| Function | FN_GEN_POPULATE_DUE |
| No of Parameters | 0 |
| Function Call Id | 1 |

| Cluster/Custom Function Name | FN_GEN_POPULATE_DUE |
|---|---|
| Additional parameters | |
| Sent to Extensible layer | l_tb_cluster_data('idxcomp') :=   idxcomp; |
| Received from Extensible l ayer | |
| Hook Description | Inline Hook has been provided in function Fn_Gen_Populate_Due in package clpks_payment. |
| Description | Inline Hook has been provided in function Fn_Gen_Populate_Due in package clpks_payment. <br> All parameters received by kernel function are passed to the cluster hook. <br>   Additional parameters passed to cluster hook are mentioned in field "Additional Parameters". <br>   The variables mentioned in "Sent to Extensible Layer"  field are passed to cluster hook. <br>   The variables mentioned in "Received from Extensible Layer"  field are reassigned to kernel. |
| Bug No | 28118145 |

| Parameter | Description |
|---|---|
| Function | FN_GEN_POPULATE_DUE |
| No of Parameters | 0 |
| Function Call Id | 0 |
| Cluster/Custom Function Name | FN_IS_PENL_ON_SAME_DATE |
| Additional parameters | l_penl_process |
| Sent to Extensible layer | |
| Received from Extensible l ayer | |
| Hook Description | Hook has been provided in function Fn_Gen_Populate_Due in package Clpks_Payment.Call has been given to functi on fn_is_penl_on_same_date of package clpks_payment. |
| Description | Hook has been provided in function Fn_Gen_Populate_Due in package Clpks_Payment.Call has been given to functi on fn_is_penl_on_same_date of package clpks_payment. <br>  All parameters received by kernel function are passed to the cluster hook. <br>   Additional parameters passed to cluster hook are mentioned in field "Additional Parameters". <br>   The variables mentioned in "Sent to Extensible Layer"  field are passed to cluster hook. <br>   The variables mentioned in "Received from Extensible Layer"  field are reassigned to kernel. |
| Bug No | 28118145 |

| Parameter | Description |
|---|---|
| Function | FN_GEN_PREPARE_EVENT_ENTRIES |
| No of Parameters | 6 |
| Function Call Id | 4 |
| Cluster/Custom Function Name | FN_ADJUST_EVENT_ENTRIES |
| Additional parameters | l_Rec_Event_Entries, <br> l_Tot_Amount_Paid, <br> Idxcomp, <br> l_fn_call_id, <br> l_tb_cluster_data |
| Sent to Extensible layer | None |

ORACLE®

| | |
|---|---|
| Received from Extensible layer | None |
| Hook Description | Hook is placed in clpks_payment.Fn_Gen_Prepare_Event_Entries(), to capture the provision amount for interest and commitment fees at the time of account opening and track the utilization of the amount provisioned. |
| Description | Hook is placed in clpks_payment.Fn_Gen_Prepare_Event_Entries(), to capture the provision amount for interest and commitment fees at the time of account opening and track the utilization of the amount provisioned. All parameters received by kernel function are passed to the cluster hook. Additional parameters passed to cluster hook are mentioned in field "Additional Parameters". The variables mentioned in "Sent to Extensible Layer" field are passed to cluster hook. The variables mentioned in "Received from Extensible Layer" field are reassigned to kernel. |
| Bug No | 21223530 |

| Parameter | Description |
|---|---|
| Function | FN_GEN_PREPARE_EVENT_ENTRIES |
| No of Parameters | 6 |
| Function Call Id | 5 |
| Cluster/Custom Function Name | FN_ADJUST_EVENT_ENTRIES |
| Additional parameters | l_Rec_Event_Entries, l_Tot_Amount_Paid, Idxcomp, l_fn_call_id, l_tb_cluster_data |
| Sent to Extensible layer | None |
| Received from Extensible layer | None |
| Hook Description | Hook is placed in clpks_payment.Fn_Gen_Prepare_Event_Entries(), to capture the provision amount for interest and commitment fees at the time of account opening and track the utilization of the amount provisioned. |
| Description | Hook is placed in clpks_payment.Fn_Gen_Prepare_Event_Entries(), to capture the provision amount for interest and commitment fees at the time of account opening and track the utilization of the amount provisioned. All parameters received by kernel function are passed to the cluster hook. Additional parameters passed to cluster hook are mentioned in field "Additional Parameters". The variables mentioned in "Sent to Extensible Layer" field are passed to cluster hook. The variables mentioned in "Received from Extensible Layer" field are reassigned to kernel. |
| Bug No | 21223530 |

| Parameter | Description |
|---|---|
| Function | FN_GEN_REVERSE_PAYMENT |
| No of Parameters | 3 |
| Function Call Id | 3 |

ORACLE®

| Cluster/Custom Function Name | FN_GEN_REVERSE_PAYMENT |
|---|---|
| Additional parameters | l_fn_call_id<br>l_tb_cluster_data |
| Sent to Extensible layer | |
| Received from Extensible layer | |
| Hook Description | The online call to process YACR from CLPKS_PAYMENT, CLPKS_MROLL, PKG_CLDADCHG AND PKG_CLDMDSBR package has to be skiped as the client only want the processing of YACR should happen at the EOD. |
| Description | The online call to process YACR from CLPKS_PAYMENT, CLPKS_MROLL, PKG_CLDADCHG AND PKG_CLDMDSBR package has to be skiped as the client only want the processing of YACR should happen at the EOD.<br>  All parameters received by kernel function are passed to the cluster hook.<br>    Additional parameters passed to cluster hook are mentioned in field "Additional Parameters".<br>    The variables mentioned in "Sent to Extensible Layer"  field are passed to cluster hook.<br>    The variables mentioned in "Received from Extensible Layer"  field are reassigned to kernel. |
| Bug No | 31544577 |

| Parameter | Description |
|---|---|
| Function | FN_GEN_TAKE_BACKUP |
| No of Parameters | 7 |
| Function Call Id | 1 |
| Cluster/Custom Function Name | FN_GEN_TAKE_BACKUP |
| Additional parameters | |
| Sent to Extensible layer | |
| Received from Extensible layer | |
| Hook Description | The online call to process YACR from CLPKS_PAYMENT, CLPKS_MROLL, PKG_CLDADCHG AND PKG_CLDMDSBR package has to be skiped as the client only want the processing of YACR should happen at the EOD. |
| Description | The online call to process YACR from CLPKS_PAYMENT, CLPKS_MROLL, PKG_CLDADCHG AND PKG_CLDMDSBR package has to be skiped as the client only want the processing of YACR should happen at the EOD.<br>  All parameters received by kernel function are passed to the cluster hook.<br>    Additional parameters passed to cluster hook are mentioned in field "Additional Parameters".<br>    The variables mentioned in "Sent to Extensible Layer"  field are passed to cluster hook.<br>    The variables mentioned in "Received from Extensible Layer"  field are reassigned to kernel. |
| Bug No | 31544577 |

| Parameter | Description |
|---|---|
| Function | FN_POPULATE_READ_ENTRIES |
| No of Parameters | 0 |
| Function Call Id | 1 |
| Cluster/Custom Function Name | FN_PRE_POPULATE_READ_ENTRIES |
| Additional parameters | |
| Sent to Extensible layer | |

ORACLE®

| Received from Extensible layer | |
|---|---|
| Hook Description | Pre and Post Hook has been provided for function Fn_Populate_Read_Entries in package clpks_payment. |
| Description | Pre and Post Hook has been provided for function Fn_Populate_Read_Entries in package clpks_payment.<br>All parameters received by kernel function are passed to the cluster hook.<br>Additional parameters passed to cluster hook are mentioned in field "Additional Parameters".<br>The variables mentioned in "Sent to Extensible Layer" field are passed to cluster hook.<br>The variables mentioned in "Received from Extensible Layer" field are reassigned to kernel. |
| Bug No | 28118145 |

| Parameter | Description |
|---|---|
| Function | FN_POPULATE_READ_ENTRIES |
| No of Parameters | 0 |
| Function Call Id | 2 |
| Cluster/Custom Function Name | FN_POST_POPULATE_READ_ENTRIES |
| Additional parameters | |
| Sent to Extensible layer | |
| Received from Extensible layer | |
| Hook Description | Pre and Post Hook has been provided for function Fn_Populate_Read_Entries in package clpks_payment. |
| Description | Pre and Post Hook has been provided for function Fn_Populate_Read_Entries in package clpks_payment.<br>All parameters received by kernel function are passed to the cluster hook.<br>Additional parameters passed to cluster hook are mentioned in field "Additional Parameters".<br>The variables mentioned in "Sent to Extensible Layer" field are passed to cluster hook.<br>The variables mentioned in "Received from Extensible Layer" field are reassigned to kernel. |
| Bug No | 28118145 |

| Parameter | Description |
|---|---|
| Function | FN_UPD_ALIQ_TRACK_RECV |
| No of Parameters | 4 |
| Function Call Id | 1 |
| Cluster/Custom Function Name | FN_TRACK_RECEIVABLE |
| Additional parameters | l_Account_Master.Product_Code,<br>l_Account_Master.Customer_Id,<br>Eachrec,<br>l_Comp_Dtl.Component_Ccy,<br>l_Comp_Dtl.Exchange_Rate,<br>l_Comp_Dtl.Org_Exch_Rate,<br>l_Amt_Settled,<br>l_fn_call_id,<br>l_tb_cluster_data |
| Sent to Extensible layer | None |
| Received from Extensible layer | None |

| Hook Description | Hook is placed in clpks_payment.Fn_Upd_Aliq_Track_Recv(), to maintain multiple recovery accounts for each component and due amounts should be settled with proportionate recovery percentage specified. |
|---|---|
| Description | Hook is placed in clpks_payment.Fn_Upd_Aliq_Track_Recv(), to maintain multiple recovery accounts for each component and due amounts should be settled with proportionate recovery percentage specified.<br> All parameters received by kernel function are passed to the cluster hook.<br>    Additional parameters passed to cluster hook are mentioned in field "Additional Parameters".<br>    The variables mentioned in "Sent to Extensible Layer"  field are passed to cluster hook.<br>    The variables mentioned in "Received from Extensible Layer"  field are reassigned to kernel. |
| Bug No | 24702528 |

| Parameter | Description |
|---|---|
| Function | PR_POP_COMPWISE_SCHEDULES |
| No of Parameters | 1 |
| Function Call Id | 1 |
| Cluster/Custom Function Name | FN_POST_POP_COMPWISE_SCH |
| Additional parameters | l_fn_call_id,<br>l_tb_cluster_data |
| Sent to Extensible layer | None |
| Received from Extensible layer | None |
| Hook Description | Post Hook is placed in clpks_payment.Pr_Pop_Compwise_Schedules(), so that the overdue will be repaid first and then the due amount for all components. |
| Description | Post Hook is placed in clpks_payment.Pr_Pop_Compwise_Schedules(), so that the overdue will be repaid first and then the due amount for all components.<br> All parameters received by kernel function are passed to the cluster hook.<br>    Additional parameters passed to cluster hook are mentioned in field "Additional Parameters".<br>    The variables mentioned in "Sent to Extensible Layer"  field are passed to cluster hook.<br>    The variables mentioned in "Received from Extensible Layer"  field are reassigned to kernel. |
| Bug No | 19225938 |

| Parameter | Description |
|---|---|
| Function | PR_POP_COMPWISE_SCHEDULES |
| No of Parameters | 6 |
| Function Call Id | 3 |
| Cluster/Custom Function Name | FN_POST_POP_COMPWISE_SCH |

ORACLE®

| Additional parameters | l_Rec_Event_Entries, l_Tot_Amount_Paid, Idxcomp, l_fn_call_id, l_tb_cluster_data |
|---|---|
| Sent to Extensible layer | None |
| Received from Extensible layer | None |
| Hook Description | Hook is placed in clpks_payment.Fn_Gen_Prepare_Event_Entries(), to capture the provision amount for interest and commitment fees at the time of account opening and track the utilization of the amount provisioned. |
| Description | Hook is placed in clpks_payment.Fn_Gen_Prepare_Event_Entries(), to capture the provision amount for interest and commitment fees at the time of account opening and track the utilization of the amount provisioned. All parameters received by kernel function are passed to the cluster hook. Additional parameters passed to cluster hook are mentioned in field "Additional Parameters". The variables mentioned in "Sent to Extensible Layer" field are passed to cluster hook. The variables mentioned in "Received from Extensible Layer" field are reassigned to kernel. |
| Bug No | 21223530 |

ORACLE®